

$\langle Version \rangle \equiv$
2.2.6


$\langle Date \rangle \equiv$
Apr 01 2015

WHIZARD¹

Wolfgang Kilian,² Thorsten Ohl,³ Jürgen Reuter⁴

Version 2.2.6, Apr 01 2015

with contributions from: Fabian Bach, Felix Braam, Hans-Werner
Boschmann, Bijan Chokoufé Nejad, David Gordo Gomez,
Sebastian Schmidt, Marco Sekulla, Christian Speckner, Christian
Weiss, Daniel Wiesler



¹The original meaning of the acronym is *W, Higgs, Z, And Respective Decays*. The current program is much more than that, however.

²e-mail: kilian@physik.uni-siegen.de

³e-mail: ohl@physik.uni-wuerzburg.de

⁴e-mail: juergen.reuter@desy.de

Abstract

WHIZARD is an application of the VAMP algorithm: Adaptive multi-channel integration and event generation. The bare VAMP library is augmented by modules for Lorentz algebra, particles, phase space, etc., such that physical processes with arbitrary complex final states [well, in principle. . .] can be integrated and *unweighted* events be generated.

Contents

1	Changes	22
2	Preliminaries	23
3	Utilities	25
3.1	File Utilities	25
3.1.1	Deleting a file	26
3.2	File Registries	26
3.2.1	File handle	27
3.2.2	File handles registry	29
3.3	String Utilities	31
3.3.1	Upper and Lower Case	31
3.3.2	C-compatible Output	32
3.3.3	Number Conversion	33
3.4	Format Utilities	34
3.4.1	Line Output	34
3.4.2	TEX-compatible Output	35
3.4.3	Metapost-compatible Output	36
3.4.4	Conditional Formatting	37
3.4.5	Compressed output of integer arrays	37
3.5	Format Definitions	38
4	Testing	40
4.1	Unit tests	40
4.1.1	Parameters	41
4.1.2	Type for storing test results	41
4.1.3	Wrapup	43
4.1.4	Tool for Unit Tests	43
4.1.5	Convenience functions	45
5	System: Interfaces and Handlers	48
5.1	Constants	48
5.1.1	Version	49
5.1.2	Text Buffer	49
5.1.3	IOSTAT Codes	49
5.1.4	Character Codes	49
5.2	C wrapper for sigaction	49
5.3	C wrapper for printf	52

5.4	Error, Message and Signal Handling	53
5.4.1	Logfile	63
5.4.2	Checking values	64
5.4.3	Suppression of numerical noise	67
5.4.4	Signal handling	67
5.5	Operating-system interface	70
5.5.1	Path variables	71
5.5.2	System dependencies	72
5.5.3	Dynamic linking	78
5.5.4	Predicates	81
5.5.5	Shell access	81
5.5.6	Querying for a directory	82
5.5.7	Fortran compiler and linker	83
5.5.8	Controlling OpenMP	86
5.5.9	Unit tests	87
5.6	Interface for formatted I/O	89
5.6.1	Parsing a C format string	90
5.6.2	API	97
5.6.3	Test	97
5.7	CPU timing	99
5.7.1	Timer	104
5.7.2	Unit tests	105
6	Combinatorics	111
6.1	Bytes and such	111
6.1.1	8-bit words: bytes	112
6.1.2	32-bit words	113
6.1.3	Operations on 32-bit words	116
6.1.4	64-bit words	119
6.2	Hashtables	121
6.2.1	The hash function	121
6.2.2	The hash table	122
6.2.3	Hashtable insertion	124
6.2.4	Hashtable lookup	125
6.3	MD5 Checksums	126
6.3.1	Blocks	127
6.3.2	Messages	129
6.3.3	Message I/O	131
6.3.4	Auxiliary functions	133
6.3.5	Auxiliary stuff	133
6.3.6	MD5 algorithm	134
6.3.7	User interface	136
6.3.8	Unit tests	137
6.4	Permutations	139
6.4.1	Permutations	139
6.4.2	Operations on binary codes	144
6.5	Sorting	145
6.5.1	Implementation	145
6.5.2	Concatenating arrays	149
6.5.3	Unit tests	150

6.6	Grids	152
6.6.1	Initializer and finalizer	153
6.6.2	Segment finding and memory mapping	154
6.6.3	Grid manipulations	156
6.6.4	Input and Output to screen and disk	157
6.6.5	Unit tests	159
6.6.6	Unit tests	167
7	Text handling	170
7.1	Internal files	171
7.1.1	The line type	171
7.1.2	The ifile type	172
7.1.3	I/O on ifiles	173
7.1.4	Ifile tools	176
7.1.5	Line pointers	176
7.1.6	Access lines via pointers	177
7.2	Lexer	179
7.2.1	Input streams	180
7.2.2	Keyword list	184
7.2.3	Lexeme templates	186
7.2.4	The lexer setup	191
7.2.5	The lexeme type	193
7.2.6	The lexer object	196
7.2.7	The lexer routine	198
7.2.8	Diagnostics	200
7.2.9	Unit tests	201
7.3	Syntax rules	203
7.3.1	Syntax rules	203
7.3.2	I/O	206
7.3.3	Completing syntax rules	208
7.3.4	Accessing rules	210
7.3.5	Syntax tables	212
7.3.6	Accessing the syntax table	218
7.3.7	I/O	219
7.4	The parser	221
7.4.1	The token type	221
7.4.2	Retrieve token contents	226
7.4.3	The parse tree: nodes	228
7.4.4	Filling nodes	230
7.4.5	Accessing nodes	234
7.4.6	The parse tree	238
7.4.7	Access the parser	244
7.4.8	Tools	244
7.4.9	Applications	246
7.4.10	Unit tests	247
7.5	XML Parser	249
7.5.1	Cached Stream	249
7.5.2	Attributes	250
7.5.3	The Tag Type	252
7.5.4	Unit tests	259

7.5.5	Auxiliary Routines	259
7.5.6	Basic Tag I/O	260
7.5.7	Optional Tag	262
7.5.8	Optional Tag	264
7.5.9	Basic Tag I/O	266
8	Random-Number Generator	268
8.1	Generic Random-Number Generator	269
8.1.1	Generator type	269
8.1.2	RNG Factory	271
8.1.3	Unit tests	272
8.2	Select from a weighted sample	277
8.2.1	Selector type	277
8.2.2	Unit tests	280
8.3	TAO Random-Number Generator	281
8.3.1	Generator type	282
8.3.2	Unit tests	285
9	Physics	288
9.1	Physics Constants	289
9.1.1	Units	289
9.1.2	SM and QCD constants	289
9.1.3	Parameter Reference values	289
9.1.4	Particle codes	290
9.1.5	Spin codes	291
9.1.6	NLO status codes	292
9.2	C-compatible Particle Type	293
9.3	Lorentz algebra	295
9.3.1	Three-vectors	295
9.3.2	Four-vectors	301
9.3.3	Conversions	307
9.3.4	Angles	310
9.3.5	More kinematical functions (some redundant)	316
9.3.6	Lorentz transformations	320
9.3.7	Functions of Lorentz transformations	321
9.3.8	Invariants	322
9.3.9	Boosts	323
9.3.10	Rotations	325
9.3.11	Composite Lorentz transformations	327
9.3.12	Applying Lorentz transformations	328
9.3.13	Special Lorentz transformations	329
9.3.14	Special functions	331
9.4	Special Physics functions	335
9.4.1	Running α_s	335
9.4.2	Catani-Seymour Parameters	338
9.4.3	Mathematical Functions	339
9.4.4	Loop Integrals	340
9.4.5	More on α_s	342
9.4.6	Functions for Catani-Seymour dipoles	343
9.4.7	Distributions for integrated dipoles and such	345

9.4.8	Splitting Functions	354
9.4.9	Unit tests	355
9.5	QCD Coupling	357
9.5.1	Coupling: Abstract Data Type	357
9.5.2	Fixed Coupling	358
9.5.3	Running Coupling	359
9.5.4	Running Coupling, determined by Λ_{QCD}	360
9.5.5	Wrapper type	361
9.5.6	Unit tests	362
9.6	Shower algorithms	366
9.6.1	Unit tests	367
10	Quantum Field Theory Concepts	369
10.1	Model Data	370
10.1.1	Physics Parameters	370
10.1.2	Field Data	374
10.1.3	Vertex data	390
10.1.4	Vertex lookup table	393
10.1.5	Model Data Record	397
10.1.6	Toy Models	413
10.2	Model Testbed	418
10.2.1	Abstract Model Handlers	418
10.3	Helicities	420
10.3.1	Helicity types	420
10.3.2	Predicates	423
10.3.3	Accessing contents	423
10.3.4	Comparisons	424
10.3.5	Tools	425
10.4	Colors	426
10.4.1	The color type	426
10.4.2	Predicates	432
10.4.3	Accessing contents	433
10.4.4	Comparisons	435
10.4.5	Tools	436
10.4.6	Unit tests	446
10.4.7	The Madgraph color model	447
10.5	Flavors: Particle properties	451
10.5.1	The flavor type	451
10.6	Quantum numbers	468
10.6.1	The quantum number type	468
10.6.2	I/O	470
10.6.3	Accessing contents	472
10.6.4	Predicates	473
10.6.5	Comparisons	474
10.6.6	Operations	476
10.6.7	The quantum number mask	480
10.6.8	Setting mask components	482
10.6.9	Mask predicates	483
10.6.10	Operators	483
10.6.11	Mask comparisons	484

10.6.12 Apply a mask	484
11 Transition Matrices and Evaluation	487
11.1 State matrices	488
11.1.1 Nodes of the quantum state trie	488
11.1.2 State matrix	493
11.1.3 State iterators	504
11.1.4 Operations on quantum states	510
11.1.5 Factorization	517
11.1.6 Unit tests	524
11.2 Interactions	533
11.2.1 External interaction links	534
11.2.2 Internal relations	535
11.2.3 The interaction type	537
11.2.4 Methods inherited from the state matrix member	543
11.2.5 Accessing contents	549
11.2.6 Modifying contents	555
11.2.7 Handling Linked interactions	557
11.2.8 Recovering connections	563
11.2.9 Unit tests	564
11.3 Matrix element evaluation	566
11.3.1 Array of pairings	568
11.3.2 The evaluator type	568
11.3.3 Auxiliary structures for evaluator creation	571
11.3.4 Creating an evaluator: Matrix multiplication	579
11.3.5 Creating an evaluator: square	589
11.3.6 Creating an evaluator: identity	606
11.3.7 Creating an evaluator: quantum number sum	607
11.3.8 Evaluation	609
11.3.9 Unit tests	610
12 Sindarin Built-In Types	620
12.1 Particle Specifiers	620
12.1.1 Base type	621
12.1.2 Wrapper type	622
12.1.3 The atomic type	624
12.1.4 List	629
12.1.5 Sum	632
12.1.6 Expression Expansion	634
12.1.7 Test	634
12.2 PDG arrays	639
12.2.1 Type definition	640
12.2.2 Basic operations	641
12.2.3 Matching	644
12.2.4 Sorting	649
12.2.5 PDG array list	651
12.2.6 Unit tests	659
12.3 Jets	667
12.3.1 Re-exported symbols	667
12.3.2 Unit tests	668

12.4	Subevents	670
12.4.1	Particles	670
12.4.2	subevents	678
12.4.3	Eliminate numerical noise	692
12.5	Analysis tools	694
12.5.1	Output formats	695
12.5.2	Graph options	695
12.5.3	Drawing options	700
12.5.4	Observables	704
12.5.5	Output	708
12.5.6	Histograms	710
12.5.7	Plots	720
12.5.8	Graphs	726
12.5.9	Analysis objects	732
12.5.10	Analysis object iterator	738
12.5.11	Analysis store	741
12.5.12	L ^A T _E X driver file	744
12.5.13	API	745
12.5.14	Unit tests	754
13	Matrix Element Handling	757
13.1	Process data block	759
13.2	Process library interface	762
13.2.1	Overview	762
13.2.2	Workflow	763
13.2.3	The module	763
13.2.4	Writers	764
13.2.5	Process records in the library driver	768
13.2.6	The process library driver object	770
13.2.7	Write makefile	775
13.2.8	Write driver file	777
13.2.9	Interface bodies for informational functions	780
13.2.10	Interfaces for C-library matrix element	795
13.2.11	Retrieving the tables	797
13.2.12	Returning a procedure pointer	799
13.2.13	Hooks	801
13.2.14	Make source, compile, link	801
13.2.15	Clean up generated files	802
13.2.16	Further Tools	804
13.2.17	Load the library	804
13.2.18	MD5 sums	807
13.2.19	Test	809
13.3	Abstract process core configuration	836
13.3.1	Process core definition type	837
13.3.2	Process core template	840
13.3.3	Process driver	840
13.3.4	Process driver for intrinsic process	841
13.4	Process library access	842
13.4.1	Auxiliary stuff	843
13.4.2	Process definition objects	843

13.4.3	Process library	866
13.4.4	Use the library	881
13.4.5	Collect model-specific libraries	883
13.4.6	Test	885
13.5	Process Library Stacks	906
13.5.1	The stack entry type	907
13.5.2	The prclib stack type	907
13.5.3	Operating on Stacks	908
13.5.4	Accessing Contents	909
13.5.5	Unit tests	910
13.6	Trivial matrix element for tests	911
13.6.1	Process definition	912
13.6.2	Driver	914
13.6.3	Shortcut	916
13.6.4	Test	917
14	Particles	925
14.1	Polarization	926
14.1.1	The polarization type	927
14.1.2	Basic initializer and finalizer	927
14.1.3	I/O	928
14.1.4	Accessing contents	929
14.1.5	Initialization from state matrix	930
14.1.6	Specific initializers	930
14.1.7	Operations	937
14.1.8	Sparse Matrix	939
14.1.9	Polarization Matrix	941
14.1.10	Data Translation	945
14.1.11	Unit tests	946
14.2	Particles	954
14.2.1	The particle type	955
14.2.2	Particle sets	970
14.2.3	I/O formats	975
14.2.4	Expression interface	992
14.2.5	Unit tests	995
15	Beams	1014
15.1	Beam structure	1015
15.1.1	Beam structure elements	1015
15.1.2	Beam structure type	1016
15.1.3	Polarization	1021
15.1.4	Beam momenta	1022
15.1.5	Get contents	1023
15.1.6	Unit Tests	1027
15.2	Beams for collisions and decays	1033
15.2.1	Beam data	1033
15.2.2	Initializers: beam structure	1038
15.2.3	Initializers: collisions	1039
15.2.4	Initializers: decays	1041
15.2.5	Sanity check	1042

15.2.6	The beams type	1042
15.2.7	Inherited procedures	1044
15.2.8	Accessing contents	1045
15.2.9	Unit tests	1045
15.3	Tools	1051
15.3.1	Momentum splitting	1052
15.3.2	Constant data	1054
15.3.3	Sampling recoil	1055
15.3.4	Splitting	1057
15.3.5	Recovering the splitting	1059
15.3.6	Extract data	1060
15.3.7	Unit tests	1060
15.4	Mappings for structure functions	1078
15.4.1	Base type	1078
15.4.2	Methods for self-tests	1080
15.4.3	Implementation: standard mapping	1082
15.4.4	Implementation: resonance pair mapping	1084
15.4.5	Implementation: on-shell mapping	1086
15.4.6	Implementation: endpoint mapping	1088
15.4.7	Implementation: endpoint mapping with resonance	1090
15.4.8	Implementation: endpoint mapping for on-shell particle	1092
15.4.9	Implementation: ISR endpoint mapping	1094
15.4.10	Implementation: ISR endpoint mapping, resonant	1096
15.4.11	Implementation: ISR on-shell mapping	1099
15.4.12	Implementation: Endpoint + ISR power mapping	1101
15.4.13	Implementation: Endpoint + ISR + resonance	1103
15.4.14	Implementation: Endpoint + ISR power mapping, on-shell	1105
15.4.15	Basic formulas	1108
15.4.16	Unit tests	1126
15.5	Structure function base	1144
15.5.1	Abstract structure-function data type	1145
15.5.2	Structure-function chain configuration	1147
15.5.3	Structure-function instance	1148
15.5.4	Accessing the structure function	1160
15.5.5	Direct calculations	1162
15.5.6	Structure-function instance	1163
15.5.7	Structure-function chain	1163
15.5.8	Chain instances	1168
15.5.9	Access to the chain instance	1182
15.5.10	Unit tests	1184
15.5.11	Test implementation: structure function	1184
15.5.12	Test implementation: pair spectrum	1190
15.5.13	Test implementation: generator spectrum	1195
15.6	Photon radiation: ISR	1240
15.6.1	Physics	1240
15.6.2	Implementation	1242
15.6.3	The ISR data block	1243
15.6.4	The ISR object	1247
15.6.5	Kinematics	1248
15.6.6	ISR application	1251

15.6.7	Unit tests	1253
15.7	EPA	1266
15.7.1	Physics	1266
15.7.2	The EPA data block	1267
15.7.3	The EPA object	1271
15.7.4	Kinematics	1274
15.7.5	EPA application	1276
15.7.6	Unit tests	1277
15.8	EWA	1288
15.8.1	Physics	1288
15.8.2	The EWA data block	1290
15.8.3	The EWA object	1295
15.8.4	Kinematics	1299
15.8.5	EWA application	1302
15.8.6	Unit tests	1303
15.9	Energy-scan spectrum	1314
15.9.1	Data type	1315
15.9.2	The Energy-scan object	1317
15.9.3	Kinematics	1319
15.9.4	Energy scan application	1320
15.9.5	Unit tests	1321
15.10	Using beam event data	1324
15.10.1	The beam-data file registry	1325
15.10.2	Data type	1325
15.10.3	The beam events object	1328
15.10.4	Kinematics	1330
15.10.5	Beam events application	1332
15.10.6	Unit tests	1332
15.11	Lepton collider beamstrahlung: CIRCE1	1338
15.11.1	Physics	1338
15.11.2	The CIRCE1 data block	1339
15.11.3	Random Number Generator for CIRCE	1343
15.11.4	The CIRCE1 object	1343
15.11.5	Kinematics	1347
15.11.6	CIRCE1 application	1350
15.11.7	Unit tests	1351
15.12	Lepton Collider Beamstrahlung and Photon collider: CIRCE2	1358
15.12.1	Physics	1358
15.12.2	The CIRCE2 data block	1359
15.12.3	Random Number Generator for CIRCE	1363
15.12.4	The CIRCE2 object	1363
15.12.5	Kinematics	1366
15.12.6	CIRCE2 application	1367
15.12.7	Unit tests	1368
15.13	HOPPET interface	1375
15.14	Builtin PDF sets	1376
15.14.1	The module	1376
15.14.2	Codes for default PDF sets	1377
15.14.3	The PDF builtin data block	1377
15.14.4	The PDF object	1380

15.14.5	Kinematics	1382
15.14.6	Structure function	1384
15.14.7	Strong Coupling	1385
15.14.8	Unit tests	1386
15.15	LHAPDF	1391
15.15.1	The module	1391
15.15.2	Codes for default PDF sets	1392
15.15.3	LHAPDF library interface	1392
15.15.4	The LHAPDF status	1394
15.15.5	LHAPDF initialization	1395
15.15.6	Kinematics	1397
15.15.7	The LHAPDF data block	1398
15.15.8	The LHAPDF object	1403
15.15.9	Structure function	1405
15.15.10	Strong Coupling	1407
15.15.11	Unit tests	1408
16	Interface for Matrix Element Objects	1414
16.1	Abstract process core	1414
16.1.1	The process core	1415
16.1.2	Storage for intermediate results	1421
16.1.3	Helicity selection data	1421
16.2	Template matrix elements	1422
16.2.1	Process definition	1423
16.2.2	The Template Matrix element writer	1426
16.2.3	Driver	1438
16.2.4	High-level process definition	1439
16.2.5	The <code>prc_template_me_t</code> wrapper	1440
16.2.6	Test	1445
16.3	O'MEGA Interface	1452
16.3.1	Process definition	1453
16.3.2	The O'MEGA writer	1457
16.3.3	Driver	1467
16.3.4	High-level process definition	1467
16.3.5	The <code>prc_omega_t</code> wrapper	1468
16.3.6	Test	1476
17	Generic Event Handling	1496
17.1	Generic Event Handling	1497
17.1.1	generic event type	1497
17.1.2	Initialization	1498
17.1.3	Access particle set	1498
17.1.4	Access sqme and weight	1499
17.1.5	Pure Virtual Methods	1504
17.1.6	Utilities	1507
17.1.7	Event normalization	1507
17.2	Event Sample Data	1509
17.2.1	Event Sample Data	1510
17.2.2	Unit tests	1512
17.3	Abstract I/O Handler	1516

17.3.1	Type	1517
17.3.2	Unit tests	1521
17.4	Event Generation Checkpoints	1527
17.4.1	Type	1528
17.4.2	Specific Methods	1528
17.4.3	Common Methods	1528
17.4.4	Message header	1532
17.4.5	Unit tests	1532
17.5	Event Weight Output	1534
17.5.1	Type	1534
17.5.2	Specific Methods	1535
17.5.3	Common Methods	1535
17.5.4	Unit tests	1538
17.6	ASCII File Formats	1541
17.6.1	Type	1541
17.6.2	Specific Methods	1543
17.6.3	Common Methods	1544
17.6.4	Unit tests	1550
17.7	HEP Common Blocks	1568
17.7.1	Event characteristics	1569
17.7.2	Particle characteristics	1569
17.7.3	The HEPRUP common block	1570
17.7.4	Run parameter output (verbose)	1578
17.7.5	Run parameter output (other formats)	1579
17.7.6	The HEPEUP common block	1580
17.7.7	The HEPEVT common block	1584
17.7.8	Event output	1587
17.7.9	Event output in various formats	1589
17.7.10	Event input in various formats	1591
17.7.11	Data Transfer: particle sets	1592
17.8	HepMC events	1595
17.8.1	Interface check	1596
17.8.2	FourVector	1596
17.8.3	Polarization	1599
17.8.4	GenParticle	1602
17.8.5	GenVertex	1610
17.8.6	Vertex-particle-in iterator	1613
17.8.7	Vertex-particle-out iterator	1615
17.8.8	GenEvent	1618
17.8.9	Event-particle iterator	1626
17.8.10	I/O streams	1628
17.8.11	Unit tests	1630
17.9	LCIO events	1634
17.9.1	Interface check	1635
17.9.2	LCIO Run Header	1635
17.9.3	LCIO Event and LC Collection	1636
17.9.4	LCIO Particle	1639
17.9.5	Polarization	1644
17.9.6	LCIO Writer type	1649
17.9.7	LCIO Reader type	1651

17.9.8	Unit tests	1654
17.10	HEP Common and Events	1657
17.10.1	Data Transfer: events	1658
17.10.2	Unit tests	1670
17.11	LHEF Input/Output	1674
17.11.1	Type	1675
17.11.2	Specific Methods	1675
17.11.3	Common Methods	1676
17.11.4	Les Houches Event File: header/footer	1686
17.11.5	Version-Specific Code: 1.0	1688
17.11.6	Version-Specific Code: 2.0	1689
17.11.7	Version-Specific Code: 3.0	1692
17.11.8	Unit tests	1695
17.12	STDHEP File Formats	1708
17.12.1	Type	1709
17.12.2	Specific Methods	1710
17.12.3	Common Methods	1711
17.12.4	Variables	1717
17.12.5	Unit tests	1717
17.13	HepMC Output	1726
17.13.1	Type	1727
17.13.2	Specific Methods	1728
17.13.3	Common Methods	1728
17.13.4	Unit tests	1733
17.14	LCIO Output	1737
17.14.1	Type	1738
17.14.2	Specific Methods	1739
17.14.3	Common Methods	1739
17.14.4	Unit tests	1744
18	Phase Space	1749
18.1	Abstract phase-space module	1751
18.1.1	Phase-space channels	1751
18.1.2	Property collection	1756
18.1.3	Kinematics configuration	1759
18.1.4	Extract data	1764
18.1.5	Phase-space point instance	1765
18.1.6	Auxiliary stuff	1773
18.1.7	Unit tests	1774
18.2	Single-particle phase space	1788
18.2.1	Configuration	1788
18.2.2	Kinematics implementation	1790
18.2.3	Unit tests	1794
18.3	Mappings	1802
18.3.1	Default parameters	1802
18.3.2	The Mapping type	1804
18.3.3	Screen output	1804
18.3.4	Define a mapping	1805
18.3.5	Retrieve contents	1807
18.3.6	Compare mappings	1808

18.3.7	Mappings of the invariant mass	1809
18.3.8	Step mapping	1815
18.3.9	Mappings of the polar angle	1817
18.4	Phase-space trees	1821
18.4.1	Particles	1822
18.4.2	The phase-space tree type	1824
18.4.3	PHS tree setup	1828
18.4.4	Phase-space evaluation	1839
18.5	The phase-space forest	1850
18.5.1	Phase-space setup parameters	1851
18.5.2	Equivalences	1853
18.5.3	Groves	1855
18.5.4	The forest type	1857
18.5.5	Screen output	1859
18.5.6	Accessing contents	1862
18.5.7	Read the phase space setup from file	1864
18.5.8	Preparation	1871
18.5.9	Accessing the particle arrays	1873
18.5.10	Find equivalences among phase-space trees	1875
18.5.11	Interface for channel equivalences	1876
18.5.12	Phase-space evaluation	1878
18.5.13	Unit tests	1880
18.6	Finding phase space parameterizations	1883
18.6.1	The mapping modes	1884
18.6.2	The cascade type	1884
18.6.3	Creating new cascades	1892
18.6.4	Tools	1893
18.6.5	Hash entries for cascades	1893
18.6.6	The cascade set	1896
18.6.7	Adding cascades	1905
18.6.8	External particles	1908
18.6.9	Cascade combination I: flavor assignment	1910
18.6.10	Cascade combination II: kinematics setup and check . . .	1911
18.6.11	Cascade combination III: node connections and tree fusion	1917
18.6.12	Cascade set generation	1920
18.6.13	Groves	1923
18.6.14	Generate the phase space file	1924
18.6.15	Unit tests	1926
18.7	WOOD phase space	1928
18.7.1	Configuration	1929
18.7.2	Phase-space generation	1931
18.7.3	Phase-space configuration	1934
18.7.4	Kinematics implementation	1940
18.7.5	Evaluation	1942
18.7.6	Unit tests	1943

19 Multi-Channel Integration	1961
19.1 Generic Integrator	1962
19.1.1 MCI: integrator	1962
19.1.2 MCI instance	1972
19.1.3 MCI state	1976
19.1.4 MCI sampler	1977
19.1.5 Results record	1979
19.1.6 Unit tests	1980
19.2 Iterations	2003
19.2.1 The iterations list	2003
19.2.2 Tools	2006
19.2.3 Test	2007
19.3 Integration results	2009
19.3.1 Integration results entry	2010
19.3.2 Combined integration results	2017
19.3.3 Access results	2026
19.3.4 Results display	2030
19.4 Simple midpoint integration	2036
19.4.1 Integrator	2036
19.4.2 Integrator instance	2043
19.4.3 Unit tests	2047
19.5 VAMP interface	2063
19.5.1 Grid parameters	2064
19.5.2 History parameters	2065
19.5.3 Integration pass	2066
19.5.4 Integrator	2072
19.5.5 Sampler as Workspace	2092
19.5.6 Integrator instance	2092
19.5.7 Sampling function	2102
19.5.8 Integrator instance: evaluation	2104
19.5.9 VAMP exceptions	2105
19.5.10 Unit tests	2106
20 Parton shower and interface to PYTHIA6	2144
20.1 Basics of the shower	2144
20.1.1 Shower implementations	2145
20.1.2 PDF Parameters	2146
20.1.3 Shower settings	2147
20.1.4 Abstract matching settings and data types	2151
20.1.5 Abstract Shower Type	2152
20.1.6 Additional parameters	2153
20.2 Parton module for the shower	2157
20.2.1 The basic type defintions	2157
20.2.2 Routines	2158
20.2.3 The analytic FSR	2174
20.3 Main shower module	2179
20.4 Interface to PYTHIA	2263
20.5 Matching	2284
20.5.1 MLM matching	2284
20.5.2 CKKW matching	2308

21 Multiple Interactions (MPI) Code	2314
21.1 Basic types	2314
21.2 Transverse momenta	2379
21.3 Multi parton interactions	2386
21.4 VEGAS and CUBA integration routines	2424
21.5 Trapezoidal integration routines	2443
21.6 Fibonacci trees	2477
21.7 Adaptive Quadrature	2517
21.8 Integrands for Multiple Interactions	2531
21.9 MC Integrations for QCD $2 \rightarrow 2$ processes	2536
21.10 Proton remnants	2565
21.11 The Multiple Interactions main module	2600
21.11.1 The main Multiple Interactions type	2607
22 User Plugin Support	2623
22.1 User Code Interface	2624
22.1.1 User Code Management	2624
22.1.2 Interfaces for user-defined functions	2627
22.1.3 Interfaces for user-defined interactions	2629
22.2 User Plugin for Structure Functions	2631
22.2.1 The module	2631
22.2.2 The user structure function data block	2632
22.2.3 The interaction	2634
22.2.4 The user structure function	2637
22.2.5 Kinematics	2638
23 BLHA Interface	2641
23.1 Module definition	2641
23.2 Configuration	2671
23.3 OLP matrix element interface	2699
23.4 OLP driver	2703
24 GoSam Interface	2704
24.1 Save previously generated loop libraries	2705
24.2 Gosam Interface	2709
25 FKS Subtraction Scheme	2723
25.1 Brief outline of FKS subtraction	2723
25.2 Identifying singular regions	2725
25.3 FKS Regions	2727
25.4 Virtual contribution to the cross section	2760
25.5 Real Subtraction	2771
25.5.1 Collinear and soft-collinear subtraction terms	2774
25.5.2 Real Subtraction	2778
25.5.3 The real contribution to the cross section	2779
25.5.4 xxx	2782
25.6 Combining the FKS Pieces	2785
25.6.1 Putting it together	2802
25.6.2 xxx	2813
25.7 The FKS phase space	2815

25.7.1	Creation of the real phase space - FSR	2826
25.7.2	Creation of the real phase space - ISR	2832
25.7.3	Unit tests	2839
25.8	Subtraction of initial-state divergences	2843
26	Model Handling and Features	2850
26.1	Automatic generation of process components	2851
26.1.1	Constraints: Abstract types	2851
26.1.2	Specific constraints	2854
26.1.3	Tables of states	2860
26.1.4	Top-level methods	2865
26.1.5	Splitting algorithm	2866
26.1.6	Tools	2870
26.1.7	Access results	2871
26.1.8	Unit tests	2871
26.2	Creating the real flavor structure	2879
26.2.1	Unit tests	2889
26.3	Sindarin Expression Implementation	2893
26.3.1	Tree nodes	2894
26.3.2	Operation types	2911
26.3.3	Specific operators	2916
26.3.4	Compiling the parse tree	2944
26.3.5	Auxiliary functions for the compiler	3004
26.3.6	Evaluation	3005
26.3.7	Evaluation syntax	3012
26.3.8	Set up appropriate parse trees	3021
26.3.9	The evaluation tree	3023
26.3.10	Direct evaluation	3032
26.3.11	Factory Type	3036
26.3.12	Unit tests	3037
26.4	Physics Models	3043
26.4.1	Module	3043
26.4.2	Physics Parameters	3044
26.4.3	Model Object	3047
26.4.4	Model Access via Variables	3056
26.4.5	Reading models from file	3058
26.4.6	Model list	3068
26.4.7	Model instances	3073
26.4.8	Unit tests	3074
26.5	The SUSY Les Houches Accord	3081
26.5.1	Preprocessor	3081
26.5.2	Lexer and syntax	3083
26.5.3	Interpreter	3085
26.5.4	Auxiliary function	3091
26.5.5	Parser	3102
26.5.6	API	3103
26.5.7	Unit tests	3104

27 Integration and Process Objects	3107
27.1 Process observables	3107
27.1.1 Abstract base type	3108
27.1.2 Initialization	3109
27.1.3 Evaluation	3111
27.1.4 Implementation for partonic events	3112
27.1.5 Implementation for full events	3119
27.2 Parton states	3125
27.2.1 Abstract base type	3126
27.2.2 Common Initialization	3129
27.2.3 Evaluator initialization: isolated state	3130
27.2.4 Evaluator initialization: connected state	3132
27.2.5 Cuts and expressions	3135
27.2.6 Evaluation	3137
27.2.7 Accessing the state	3139
27.3 Complete Elementary Processes	3140
27.3.1 The Process Object	3143
27.3.2 Metadata	3169
27.3.3 Generic Configuration Data	3174
27.3.4 Beam configuration	3178
27.3.5 Multi-channel integration	3185
27.3.6 Process Components	3194
27.3.7 Process terms	3199
27.3.8 Default Iterations	3203
27.3.9 Constant process data	3206
27.3.10 Compute an amplitude	3211
27.3.11 Process instances	3213
27.3.12 Accessing the process instance	3270
27.3.13 Particle sets	3275
27.3.14 Unit tests	3280
27.4 Process Stacks	3316
27.4.1 The process entry type	3317
27.4.2 The process stack type	3317
27.4.3 Link	3319
27.4.4 Push	3320
27.4.5 Data Access	3321
27.4.6 Unit tests	3322
28 Event Implementation	3327
28.1 Abstract Event Transforms	3327
28.1.1 Abstract base type	3328
28.1.2 Implementation: Trivial transform	3333
28.1.3 Unit tests	3335
28.2 Hadronization interface	3337
28.2.1 Hadronization implementations	3338
28.2.2 Abstract Hadronization Type	3339
28.2.3 PYTHIA6 Hadronization Type	3340
28.2.4 Pythia8 Hadronization Type	3341
28.2.5 Hadronization Event Transform	3342
28.3 Decays	3344

28.3.1	Final-State Particle Configuration	3345
28.3.2	Final-State Particle	3346
28.3.3	Decay Term Configuration	3347
28.3.4	Decay Term	3349
28.3.5	Decay Root Configuration	3353
28.3.6	Decay Root Instance	3356
28.3.7	Decay Configuration	3360
28.3.8	Decay Instance	3362
28.3.9	Stable Particles	3365
28.3.10	Unstable Particles	3367
28.3.11	Decay Chain	3372
28.3.12	Decay as Event Transform	3377
28.3.13	Unit tests	3380
28.4	Shower	3392
28.4.1	Configuration Parameters	3394
28.4.2	Event Transform	3394
28.4.3	Unit Tests	3401
28.5	Complete Events	3407
28.5.1	Event configuration	3408
28.5.2	The event type	3409
28.5.3	Initialization	3413
28.5.4	Evaluation	3416
28.5.5	Reset to empty state	3418
28.5.6	Squared Matrix Element and Weight	3419
28.5.7	Generation	3421
28.5.8	Recovering an event	3422
28.5.9	Access content	3425
28.5.10	Unit tests	3427
28.6	Raw Event I/O	3437
28.6.1	File Format Version	3438
28.6.2	Type	3438
28.6.3	Unit tests	3446
28.7	User-controlled File I/O	3451
28.7.1	The file type	3452
28.7.2	The file list	3454
28.8	Runtime data	3458
28.8.1	Strategy for models and variables	3459
28.8.2	Container for parse nodes	3459
28.8.3	The data type	3462
28.8.4	Output	3462
28.8.5	Clear	3465
28.8.6	Initialization	3466
28.8.7	Local copies	3483
28.8.8	Finalization	3486
28.8.9	Model Management	3487
28.8.10	Managing Variables	3490
28.8.11	Further Content	3496
28.8.12	Miscellaneous	3496
28.8.13	Test	3500
28.9	Select implementations	3515

28.9.1	Interfaces	3517
28.9.2	Process Core Definition	3517
28.9.3	Process core allocation	3520
28.9.4	Process core update and restoration	3521
28.9.5	Integrator allocation	3521
28.9.6	Phase-space allocation	3523
28.9.7	FKS parameter	3524
28.9.8	Random-number generator	3525
28.9.9	Structure function configuration data	3526
28.9.10	Event I/O stream	3540
28.9.11	QCD coupling	3546
28.9.12	Parton Shower	3548
28.9.13	Event Transform	3548
28.9.14	SLHA Interface	3550
28.9.15	Test	3551
28.10	Process Configuration	3572
28.10.1	Data Type	3572
28.10.2	Test	3575
28.11	Compilation	3581
28.11.1	The data type	3581
28.11.2	API for library compilation and loading	3583
28.11.3	Compiling static executable	3584
28.11.4	API for executable compilation	3588
28.11.5	Test	3589
28.11.6	Test static build	3593
28.12	Integration	3597
28.12.1	The integration type	3598
28.12.2	Initialization	3598
28.12.3	Integration	3605
28.12.4	API for integration objects	3606
28.12.5	Test	3611
28.13	Event Streams	3629
28.13.1	Event Stream Array	3629
28.13.2	Unit Tests	3634
28.14	Simulation	3641
28.14.1	Event counting	3642
28.14.2	Simulation: component sets	3644
28.14.3	Process-core Safe	3645
28.14.4	Process Object	3645
28.14.5	Simulation entry	3646
28.14.6	Entries for alternative environment	3655
28.14.7	The simulation type	3657
28.14.8	Event Stream I/O	3672
28.14.9	Event Stream Array	3673
28.14.10	Recover event	3675
28.14.11	Extract contents	3675
28.14.12	Auxiliary	3678
28.14.13	Test	3678

29 More Unit Tests	3709
29.1 Expression Testing	3709
29.1.1 Test	3710
30 Top Level	3726
30.1 Commands	3727
30.1.1 The command type	3728
30.1.2 Options	3732
30.1.3 Specific command types	3733
30.1.4 User-controlled output to data files	3803
30.1.5 Print custom-formatted values	3805
30.1.6 The command list	3854
30.1.7 Compiling the parse tree	3855
30.1.8 Executing the command list	3855
30.1.9 Command list syntax	3856
30.1.10 Unit Tests	3863
30.2 Toplevel module WHIZARD	3920
30.2.1 Options	3922
30.2.2 Parse tree stack	3922
30.2.3 The <code>whizard</code> object	3923
30.2.4 Initialization and finalization	3924
30.2.5 Initialization and finalization (old version)	3926
30.2.6 Execute command lists	3928
30.2.7 The WHIZARD shell	3930
30.2.8 Self-tests	3931
30.3 Driver program	3940
30.4 Whizard-C-Interface	3950
31 Cross References	3959
31.1 Identifiers	3959
31.2 Chunks	3959

Chapter 1

Changes

For a comprehensive list of changes confer the ChangeLog file or the subversion log.

Chapter 2

Preliminaries

The WHIZARD file header:

```
<File header>≡
! WHIZARD <Version> <Date>
!
! Copyright (C) 1999-2015 by
!   Wolfgang Kilian <kilian@physik.uni-siegen.de>
!   Thorsten Ohl <ohl@physik.uni-wuerzburg.de>
!   Juergen Reuter <juergen.reuter@desy.de>
!
!   with contributions from
!   Fabian Bach <fabian.bach@desy.de>
!   Christian Speckner <cnspeckn@googlemail.com>
!   Christian Weiss <christian.weiss@desy.de>
!   and Hans-Werner Boschmann, Felix Braam,
!   Sebastian Schmidt, Daniel Wiesler
!
! WHIZARD is free software; you can redistribute it and/or modify it
! under the terms of the GNU General Public License as published by
! the Free Software Foundation; either version 2, or (at your option)
! any later version.
!
! WHIZARD is distributed in the hope that it will be useful, but
! WITHOUT ANY WARRANTY; without even the implied warranty of
! MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
! GNU General Public License for more details.
!
! You should have received a copy of the GNU General Public License
! along with this program; if not, write to the Free Software
! Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
! This file has been stripped of most comments. For documentation, refer
! to the source 'whizard.nw'
```

We are strict with our names:

```
<Standard module head>≡
  implicit none
  private
```

This is the way to invoke the kinds module (not contained in this source)

```
<Use kinds>≡  
    use kinds, only: default
```

```
<Use kinds with double>≡  
    use kinds, only: default, double
```

And we make heavy use of variable-length strings

```
<Use strings>≡  
    use iso_varying_string, string_t => varying_string
```

Chapter 3

Utilities

These modules are intended as part of WHIZARD, but in fact they are generic and could be useful for any purpose.

The modules depend only on modules from the **basics** set.

file_utils Procedures that deal with external files, if not covered by Fortran built-ins.

file_registries Manage files that are accessed by their name.

string_utils Some string-handling utilities. Includes conversion to C string.

format_utils Utilities for pretty-printing.

format_defs Predefined format strings.

3.1 File Utilities

This module provides miscellaneous tools associated with named external files. Currently only:

- Delete a named file

```
<file_utils.f90>≡  
<File header>  
  
module file_utils  
  
    use io_units  
  
<Standard module head>  
  
<File utils: public>  
  
contains  
  
<File utils: procedures>  
  
end module file_utils
```

3.1.1 Deleting a file

Fortran does not contain a command for deleting a file. Here, we provide a subroutine that deletes a file if it exists. We do not handle the subtleties, so we assume that it is writable if it exists.

```
<File utils: public>≡
    public :: delete_file

<File utils: procedures>≡
    subroutine delete_file (name)
        character(*), intent(in) :: name
        logical :: exist
        integer :: u
        inquire (file = name, exist = exist)
        if (exist) then
            u = free_unit ()
            open (unit = u, file = name)
            close (u, status = "delete")
        end if
    end subroutine delete_file
```

3.2 File Registries

This module provides a file-registry facility. We can open and close files multiple times without inadvertently accessing a single file by two different I/O unit numbers. Opening a file the first time enters it into the registry. Opening again just returns the associated I/O unit. The registry maintains a reference count, so closing a file does not actually complete until the last reference is released.

File access will always be sequential, however. The file can't be opened at different positions simultaneously.

```
<file_registries.f90>≡
    <File header>

    module file_registries

        <Use strings>
        use io_units

        <Standard module head>

        <File registries: public>

        <File registries: types>

        contains

        <File registries: procedures>

    end module file_registries
```

3.2.1 File handle

This object holds a filename (fully qualified), the associated unit, and a reference count. The idea is that the object should be deleted when the reference count drops to zero.

```
<File registries: types>≡
  type :: file_handle_t
    type(string_t) :: file
    integer :: unit = 0
    integer :: refcount = 0
  contains
    <File registries: file handle: TBP>
  end type file_handle_t
```

Debugging output:

```
<File registries: file handle: TBP>≡
  procedure :: write => file_handle_write

<File registries: procedures>≡
  subroutine file_handle_write (handle, u, show_unit)
    class(file_handle_t), intent(in) :: handle
    integer, intent(in) :: u
    logical, intent(in), optional :: show_unit
    logical :: show_u
    show_u = .false.; if (present (show_unit)) show_u = show_unit
    if (show_u) then
      write (u, "(3x,A,1x,I0,1x,'( ',I0,') ')" &
        char (handle%file), handle%unit, handle%refcount
    else
      write (u, "(3x,A,1x,'( ',I0,') ')" &
        char (handle%file), handle%refcount
    end if
  end subroutine file_handle_write
```

Initialize with a file name, don't open the file yet:

```
<File registries: file handle: TBP>+≡
  procedure :: init => file_handle_init

<File registries: procedures>+≡
  subroutine file_handle_init (handle, file)
    class(file_handle_t), intent(out) :: handle
    type(string_t), intent(in) :: file
    handle%file = file
  end subroutine file_handle_init
```

We check the `refcount` before actually opening the file.

```
<File registries: file handle: TBP>+≡
  procedure :: open => file_handle_open

<File registries: procedures>+≡
  subroutine file_handle_open (handle)
    class(file_handle_t), intent(inout) :: handle
    if (handle%refcount == 0) then
      handle%unit = free_unit ()
```

```

        open (unit = handle%unit, file = char (handle%file), action = "read", &
              status = "old")
    end if
    handle%refcount = handle%refcount + 1
end subroutine file_handle_open

```

Analogously, close if the refcount drops to zero. The caller may then delete the object.

```

<File registries: file handle: TBP>+≡
    procedure :: close => file_handle_close

<File registries: procedures>+≡
    subroutine file_handle_close (handle)
        class(file_handle_t), intent(inout) :: handle
        handle%refcount = handle%refcount - 1
        if (handle%refcount == 0) then
            close (handle%unit)
            handle%unit = 0
        end if
    end subroutine file_handle_close

```

The I/O unit will be nonzero when the file is open.

```

<File registries: file handle: TBP>+≡
    procedure :: is_open => file_handle_is_open

<File registries: procedures>+≡
    function file_handle_is_open (handle) result (flag)
        class(file_handle_t), intent(in) :: handle
        logical :: flag
        flag = handle%unit /= 0
    end function file_handle_is_open

```

Return the filename, so we can identify the entry.

```

<File registries: file handle: TBP>+≡
    procedure :: get_file => file_handle_get_file

<File registries: procedures>+≡
    function file_handle_get_file (handle) result (file)
        class(file_handle_t), intent(in) :: handle
        type(string_t) :: file
        file = handle%file
    end function file_handle_get_file

```

For debugging, return the I/O unit number.

```

<File registries: file handle: TBP>+≡
    procedure :: get_unit => file_handle_get_unit

<File registries: procedures>+≡
    function file_handle_get_unit (handle) result (unit)
        class(file_handle_t), intent(in) :: handle
        integer :: unit
        unit = handle%unit
    end function file_handle_get_unit

```

3.2.2 File handles registry

This is implemented as a doubly-linked list. The list exists only once in the program, as a private module variable.

Extend the handle type to become a list entry:

```
<File registries: types>+≡  
  type, extends (file_handle_t) :: file_entry_t  
    type(file_entry_t), pointer :: prev => null ()  
    type(file_entry_t), pointer :: next => null ()  
  end type file_entry_t
```

The actual registry. We need only the pointer to the first entry.

```
<File registries: public>≡  
  public :: file_registry_t  
  
<File registries: types>+≡  
  type :: file_registry_t  
    type(file_entry_t), pointer :: first => null ()  
    contains  
    <File registries: file_registry: TBP>  
  end type file_registry_t
```

Debugging output.

```
<File registries: file_registry: TBP>≡  
  procedure :: write => file_registry_write  
  
<File registries: procedures>+≡  
  subroutine file_registry_write (registry, unit, show_unit)  
    class(file_registry_t), intent(in) :: registry  
    integer, intent(in), optional :: unit  
    logical, intent(in), optional :: show_unit  
    type(file_entry_t), pointer :: entry  
    integer :: u  
    u = given_output_unit (unit)  
    if (associated (registry%first)) then  
      write (u, "(1x,A)") "File registry:"  
      entry => registry%first  
      do while (associated (entry))  
        call entry%write (u, show_unit)  
        entry => entry%next  
      end do  
    else  
      write (u, "(1x,A)") "File registry: [empty]"  
    end if  
  end subroutine file_registry_write
```

Open a file: find the appropriate entry. Create a new entry and add to the list if necessary. The list is extended at the beginning. Return the I/O unit number for the records.

```
<File registries: file_registry: TBP>+≡  
  procedure :: open => file_registry_open
```



```

<File registries: procedures>+=
subroutine file_registry_open (registry, file, unit)
  class(file_registry_t), intent(inout) :: registry
  type(string_t), intent(in) :: file
  integer, intent(out), optional :: unit
  type(file_entry_t), pointer :: entry
  entry => registry%first
  FIND_ENTRY: do while (associated (entry))
    if (entry%get_file () == file) exit FIND_ENTRY
    entry => entry%next
  end do FIND_ENTRY
  if (.not. associated (entry)) then
    allocate (entry)
    call entry%init (file)
    if (associated (registry%first)) then
      registry%first%prev => entry
      entry%next => registry%first
    end if
    registry%first => entry
  end if
  call entry%open ()
  if (present (unit)) unit = entry%get_unit ()
end subroutine file_registry_open

```

Close a file: find the appropriate entry. Delete the entry if there is no file connected to it anymore.

```

<File registries: file registry: TBP>+=
procedure :: close => file_registry_close

<File registries: procedures>+=
subroutine file_registry_close (registry, file)
  class(file_registry_t), intent(inout) :: registry
  type(string_t), intent(in) :: file
  type(file_entry_t), pointer :: entry
  entry => registry%first
  FIND_ENTRY: do while (associated (entry))
    if (entry%get_file () == file) exit FIND_ENTRY
    entry => entry%next
  end do FIND_ENTRY
  if (associated (entry)) then
    call entry%close ()
    if (.not. entry%is_open ()) then
      if (associated (entry%prev)) then
        entry%prev%next => entry%next
      else
        registry%first => entry%next
      end if
      if (associated (entry%next)) then
        entry%next%prev => entry%prev
      end if
      deallocate (entry)
    end if
  end if
end subroutine file_registry_close

```

3.3 String Utilities

This module provides tools associated with strings (built-in and variable). Currently:

- Upper and lower case for strings
- Convert to null-terminated C string

```
<string_utils.f90>≡  
<File header>  
  
module string_utils  
  
    use, intrinsic :: iso_c_binding  
    <Use kinds>  
    <Use strings>  
  
    <Standard module head>  
  
    <String utils: public>  
  
    <String utils: interfaces>  
  
contains  
  
    <String utils: procedures>  
  
end module string_utils
```

3.3.1 Upper and Lower Case

These are, unfortunately, not part of Fortran.

```
<String utils: public>≡  
    public :: upper_case  
    public :: lower_case  
  
<String utils: interfaces>≡  
    interface upper_case  
        module procedure upper_case_char, upper_case_string  
    end interface  
    interface lower_case  
        module procedure lower_case_char, lower_case_string  
    end interface  
  
<String utils: procedures>≡  
    function upper_case_char (string) result (new_string)  
        character(*), intent(in) :: string  
        character(len(string)) :: new_string  
        integer :: pos, code  
        integer, parameter :: offset = ichar('A')-ichar('a')  
        do pos = 1, len (string)
```

```

        code = ichar (string(pos:pos))
        select case (code)
        case (ichar('a'):ichar('z'))
            new_string(pos:pos) = char (code + offset)
        case default
            new_string(pos:pos) = string(pos:pos)
        end select
    end do
end function upper_case_char

function lower_case_char (string) result (new_string)
    character(*), intent(in) :: string
    character(len(string)) :: new_string
    integer :: pos, code
    integer, parameter :: offset = ichar('a')-ichar('A')
    do pos = 1, len (string)
        code = ichar (string(pos:pos))
        select case (code)
        case (ichar('A'):ichar('Z'))
            new_string(pos:pos) = char (code + offset)
        case default
            new_string(pos:pos) = string(pos:pos)
        end select
    end do
end function lower_case_char

function upper_case_string (string) result (new_string)
    type(string_t), intent(in) :: string
    type(string_t) :: new_string
    new_string = upper_case_char (char (string))
end function upper_case_string

function lower_case_string (string) result (new_string)
    type(string_t), intent(in) :: string
    type(string_t) :: new_string
    new_string = lower_case_char (char (string))
end function lower_case_string

```

3.3.2 C-compatible Output

Convert a FORTRAN string into a zero terminated C string.

```

<String utils: public>+≡
    public :: string_f2c

<String utils: interfaces>+≡
    interface string_f2c
        module procedure string_f2c_char, string_f2c_var_str
    end interface string_f2c

<String utils: procedures>+≡
    pure function string_f2c_char (i) result (o)
        character(*), intent(in) :: i
        character(kind=c_char, len=len (i) + 1) :: o

```

```

    o = i // c_null_char
end function string_f2c_char

pure function string_f2c_var_str (i) result (o)
    type(string_t), intent(in) :: i
    character(kind=c_char, len=len (i) + 1) :: o
    o = char (i) // c_null_char
end function string_f2c_var_str

```

3.3.3 Number Conversion

Create a string from a number. We use fixed format for the reals and variable format for integers.

```

<String utils: public>+≡
    public :: str

<String utils: interfaces>+≡
    interface str
        module procedure str_int, str_real
    end interface

<String utils: procedures>+≡
    function str_int (i) result (s)
        integer, intent(in) :: i
        type(string_t) :: s
        character(32) :: buffer
        write (buffer, "(I0)") i
        s = var_str (trim (adjustl (buffer)))
    end function str_int

    function str_real (x) result (s)
        real(default), intent(in) :: x
        type(string_t) :: s
        character(32) :: buffer
        write (buffer, "(ES17.10)") x
        s = var_str (trim (adjustl (buffer)))
    end function str_real

```

Auxiliary: Read real, integer, string value.

```

<String utils: public>+≡
    public :: read_rval
    public :: read_ival

<String utils: procedures>+≡
    function read_rval (s) result (rval)
        type(string_t), intent(in) :: s
        real(default) :: rval
        character(80) :: buffer
        buffer = s
        read (buffer, *) rval
    end function read_rval

    function read_ival (s) result (ival)

```

```

    type(string_t), intent(in) :: s
    integer :: ival
    character(80) :: buffer
    buffer = s
    read (buffer, *) ival
end function read_ival

```

3.4 Format Utilities

This module provides miscellaneous tools associated with formatting and pretty-printing.

- Horizontal separator lines in output
- Indenting an output line
- Formatting a number for T_EX output.
- Formatting a number for MetaPost output.
- Alternate numeric formats.

```

⟨format_utils.f90⟩≡
  ⟨File header⟩

  module format_utils

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use string_utils, only: lower_case

    ⟨Standard module head⟩

    ⟨Format utils: public⟩

    contains

    ⟨Format utils: procedures⟩

  end module format_utils

```

3.4.1 Line Output

Write a separator line.

```

⟨Format utils: public⟩≡
  public :: write_separator

⟨Format utils: procedures⟩≡
  subroutine write_separator (u, mode)
    integer, intent(in) :: u
    integer, intent(in), optional :: mode
    integer :: m
    m = 1; if (present (mode)) m = mode

```

```

select case (m)
case default
  write (u, "(A)") repeat("-", 72)
case (1)
  write (u, "(A)") repeat("-", 72)
case (2)
  write (u, "(A)") repeat("=", 72)
end select
end subroutine write_separator

```

Indent the line with given number of blanks.

```

⟨Format utils: public⟩+≡
  public :: write_indent

⟨Format utils: procedures⟩+≡
  subroutine write_indent (unit, indent)
    integer, intent(in) :: unit
    integer, intent(in), optional :: indent
    if (present (indent)) then
      write (unit, "(1x,A)", advance="no") repeat (" ", indent)
    end if
  end subroutine write_indent

```

3.4.2 T_EX-compatible Output

Quote underscore characters for use in T_EX output.

```

⟨Format utils: public⟩+≡
  public :: quote_underscore

⟨Format utils: procedures⟩+≡
  function quote_underscore (string) result (quoted)
    type(string_t) :: quoted
    type(string_t), intent(in) :: string
    type(string_t) :: part
    type(string_t) :: buffer
    buffer = string
    quoted = ""
    do
      call split (part, buffer, "_")
      quoted = quoted // part
      if (buffer == "") exit
      quoted = quoted // "\_"
    end do
  end function quote_underscore

```

Format a number with n significant digits for use in T_EX documents.

```

⟨Format utils: public⟩+≡
  public :: tex_format

⟨Format utils: procedures⟩+≡
  function tex_format (rval, n_digits) result (string)
    type(string_t) :: string

```

```

real(default), intent(in) :: rval
integer, intent(in) :: n_digits
integer :: e, n, w, d
real(default) :: absval
real(default) :: mantissa
character :: sign
character(20) :: format
character(80) :: cstr
n = min (abs (n_digits), 16)
if (rval == 0) then
  string = "0"
else
  absval = abs (rval)
  e = int (log10 (absval))
  if (rval < 0) then
    sign = "-"
  else
    sign = ""
  end if
  select case (e)
  case (:-3)
    d = max (n - 1, 0)
    w = max (d + 2, 2)
    write (format, "('(F',IO,'.',IO,'A,IO,A)')") w, d
    mantissa = absval * 10._default ** (1 - e)
    write (cstr, fmt=format) mantissa, "\times 10^{", e - 1, "}"
  case (-2:0)
    d = max (n - e, 1 - e)
    w = max (d + e + 2, d + 2)
    write (format, "('(F',IO,'.',IO,')')") w, d
    write (cstr, fmt=format) absval
  case (1:2)
    d = max (n - e - 1, -e, 0)
    w = max (d + e + 2, d + 2, e + 2)
    write (format, "('(F',IO,'.',IO,')')") w, d
    write (cstr, fmt=format) absval
  case default
    d = max (n - 1, 0)
    w = max (d + 2, 2)
    write (format, "('(F',IO,'.',IO,'A,IO,A)')") w, d
    mantissa = absval * 10._default ** (- e)
    write (cstr, fmt=format) mantissa, "\times 10^{", e, "}"
  end select
  string = sign // trim (cstr)
end if
end function tex_format

```

3.4.3 Metapost-compatible Output

Write a number for use in Metapost code:

```

⟨Format utils: public⟩+=≡
public :: mp_format

```

```

<Format utils: procedures>+=
function mp_format (rval) result (string)
  type(string_t) :: string
  real(default), intent(in) :: rval
  character(16) :: tmp
  write (tmp, "(G16.8)") rval
  string = lower_case (trim (adjustl (trim (tmp))))
end function mp_format

```

3.4.4 Conditional Formatting

Conditional format string, intended for switchable numeric precision.

```

<Format utils: public>+=
public :: pac_fmt

<Format utils: procedures>+=
subroutine pac_fmt (fmt, fmt_orig, fmt_pac, pacify)
  character(*), intent(in) :: fmt_orig, fmt_pac
  character(*), intent(out) :: fmt
  logical, intent(in), optional :: pacify
  logical :: pacified
  pacified = .false.
  if (present (pacify)) pacified = pacify
  if (pacified) then
    fmt = fmt_pac
  else
    fmt = fmt_orig
  end if
end subroutine pac_fmt

```

3.4.5 Compressed output of integer arrays

```

<Format utils: public>+=
public :: write_compressed_integer_array

<Format utils: procedures>+=
subroutine write_compressed_integer_array (chars, array)
  character(len=*), intent(out) :: chars
  integer, intent(in), allocatable, dimension(:) :: array
  logical, dimension(:), allocatable :: used
  character(len=16) :: tmp
  type(string_t) :: string
  integer :: i, j, start_chain, end_chain
  chars = '[none]'
  string = ""
  if (allocated (array)) then
    if (size (array) > 0) then
      allocate (used (size (array)))
      used = .false.
      do i = 1, size (array)
        if (.not. used(i)) then
          start_chain = array(i)

```



```

end_chain = array(i)
used(i) = .true.
EXTEND: do
  do j = 1, size (array)
    if (array(j) == end_chain + 1) then
      end_chain = array(j)
      used(j) = .true.
      cycle EXTEND
    end if
    if (array(j) == start_chain - 1) then
      start_chain = array(j)
      used(j) = .true.
      cycle EXTEND
    end if
  end do
  exit
end do EXTEND
if (end_chain - start_chain > 0) then
  write (tmp, "(I0,A,I0)") start_chain, "-", end_chain
else
  write (tmp, "(I0)") start_chain
end if
string = string // trim (tmp)
if (any (.not. used)) then
  string = string // ','
end if
end if
end do
chars = string
end if
end if
chars = adjustr (chars)
end subroutine write_compressed_integer_array

```

3.5 Format Definitions

This module provides named integer parameters that specify certain format strings, used for numerical output.

<format_defs.f90>≡

<File header>

`module format_defs`

<Standard module head>

<Format defs: public parameters>

`end module format_defs`

We collect format strings for various numerical output formats here.

<Format defs: public parameters>≡

`character(*), parameter, public :: FMT_19 = "ES19.12"`

```
character(*), parameter, public :: FMT_18 = "ES18.11"  
character(*), parameter, public :: FMT_17 = "ES17.10"  
character(*), parameter, public :: FMT_16 = "ES16.9"  
character(*), parameter, public :: FMT_15 = "ES15.8"  
character(*), parameter, public :: FMT_14 = "ES14.7"  
character(*), parameter, public :: FMT_13 = "ES13.6"  
character(*), parameter, public :: FMT_12 = "ES12.5"  
character(*), parameter, public :: FMT_11 = "ES11.4"  
character(*), parameter, public :: FMT_10 = "ES10.3"
```

Chapter 4

Testing

This part contains tools for automatic testing.

unit_tests A handler that executes test procedures and compares and collects results.

4.1 Unit tests

We provide functionality for automated unit tests. Each test is required to produce output which is compared against a reference file. If the two are identical, we signal success. Otherwise, we signal failure and write the output to a file.

```
(unit_tests.f90)≡  
  <File header>  
  
  module unit_tests  
  
    <Use kinds>  
    use constants, only: zero, tiny_10, tiny_13  
    <Use strings>  
    use format_defs  
    use io_units  
  
    <Standard module head>  
  
    <Tests: public>  
  
    <Tests: parameters>  
  
    <Tests: types>  
  
    <Tests: interfaces>  
  
    contains  
  
    <Tests: procedures>  
  
  end module unit_tests
```

4.1.1 Parameters

Building blocks of file names. The directory names and suffixes are hard-coded here, and they must reflect actual Makefile targets where applicable.

```
<Tests: parameters>≡
    character(*), parameter :: ref_prefix = "ref-output/"
    character(*), parameter :: ref = ".ref"

    character(*), parameter :: err_prefix = "err-output/"
    character(*), parameter :: err = ".out"
```

4.1.2 Type for storing test results

We store the results of the individual unit tests in a linked list. Here is the entry:

```
<Tests: public>≡
    public :: test_results_t

<Tests: types>≡
    type :: test_result_t
        logical :: success = .false.
        type(string_t) :: name
        type(string_t) :: description
        type(test_result_t), pointer :: next => null ()
    end type test_result_t

    type :: test_results_t
        private
        type(test_result_t), pointer :: first => null ()
        type(test_result_t), pointer :: last => null ()
        integer :: n_success = 0
        integer :: n_failure = 0
        contains
        <Tests: test results: TBP>
    end type test_results_t
```

Add a test result.

```
<Tests: test results: TBP>≡
    procedure, private :: add => test_results_add

<Tests: procedures>≡
    subroutine test_results_add (list, name, description, success)
        class(test_results_t), intent(inout) :: list
        character(len=*), intent(in) :: name
        character(len=*), intent(in) :: description
        logical, intent(in) :: success
        type(test_result_t), pointer :: result
        allocate (result)
        result%success = success
        result%name = name
        result%description = description
        if (associated (list%first)) then
            list%last%next => result
        end if
    end subroutine
```

```

else
    list%first => result
end if
list%last => result
if (success) then
    list%n_success = list%n_success + 1
else
    list%n_failure = list%n_failure + 1
end if
end subroutine test_results_add

```

Display the current state.

(Tests: test results: TBP)+≡

```

    procedure, private :: write => test_results_write

```

(Tests: procedures)+≡

```

subroutine test_results_write (list, u)
class(test_results_t), intent(in) :: list
integer, intent(in) :: u
type(test_result_t), pointer :: result
write (u, "(A)")  "*** Test Summary ***"
if (list%n_success > 0) then
    write (u, "(2x,A)")  "Success:"
    result => list%first
    do while (associated (result))
        if (result%success) write (u, "(4x,A,': ',A)") &
            char (result%name), char (result%description)
        result => result%next
    end do
end if
if (list%n_failure > 0) then
    write (u, "(2x,A)")  "Failure:"
    result => list%first
    do while (associated (result))
        if (.not. result%success) write (u, "(4x,A,': ',A)") &
            char (result%name), char (result%description)
        result => result%next
    end do
end if
write (u, "(A,I0)")  "Total    = ", list%n_success + list%n_failure
write (u, "(A,I0)")  "Success = ", list%n_success
write (u, "(A,I0)")  "Failure = ", list%n_failure
write (u, "(A)")  "*** End of test Summary ***"
end subroutine test_results_write

```

Return true if all tests were successful (or no test).

(Tests: test results: TBP)+≡

```

    procedure, private :: report => test_results_report

```

(Tests: procedures)+≡

```

subroutine test_results_report (list, success)
class(test_results_t), intent(in) :: list
logical, intent(out) :: success
success = list%n_failure == 0

```

```
end subroutine test_results_report
```

Delete the list.

```
<Tests: test results: TBP>+=
  procedure, private :: final => test_results_final

<Tests: procedures>+=
  subroutine test_results_final (list)
    class(test_results_t), intent(inout) :: list
    type(test_result_t), pointer :: result
    do while (associated (list%first))
      result => list%first
      list%first => result%next
      deallocate (result)
    end do
    list%last => null ()
    list%n_success = 0
    list%n_failure = 0
  end subroutine test_results_final
```

4.1.3 Wrapup

This will write results, report status, and finalize. This is the only method which we need to access from outside.

```
<Tests: test results: TBP>+=
  procedure :: wrapup => test_results_wrapup

<Tests: procedures>+=
  subroutine test_results_wrapup (list, u, success)
    class(test_results_t), intent(inout) :: list
    integer, intent(in) :: u
    logical, intent(out), optional :: success
    call list%write (u)
    if (present (success)) call list%report (success)
    call list%final ()
  end subroutine test_results_wrapup
```

4.1.4 Tool for Unit Tests

This procedure takes a test routine as an argument. It runs the test, output directed to a temporary file. Then, it compares the file against a reference file.

The test routine must take the output unit as argument.

```
<Tests: interfaces>=
  abstract interface
    subroutine unit_test (u)
      integer, intent(in) :: u
    end subroutine unit_test
  end interface
```

The test routine can print to screen and, optionally, to a logging unit.

```

<Tests: public>+≡
    public :: test
<Tests: procedures>+≡
    subroutine test (test_proc, name, description, u_log, results)
        procedure(unit_test) :: test_proc
        character(*), intent(in) :: name
        character(*), intent(in) :: description
        integer, intent(in) :: u_log
        type(test_results_t), intent(inout) :: results
        integer :: u_test, u_ref, u_err
        logical :: exist
        character(256) :: buffer1, buffer2
        integer :: iostat1, iostat2
        logical :: success
        write (*, "(A)", advance="no") "Running test: " // name
        write (u_log, "(A)") "Test: " // name
        u_test = free_unit ()
        open (u_test, status="scratch", action="readwrite")
        call test_proc (u_test)
        rewind (u_test)
        inquire (file=ref_prefix//name//ref, exist=exist)
        if (exist) then
            u_ref = free_unit ()
            open (u_ref, file=ref_prefix//name//ref, status="old", action="read")
            COMPARE_FILES: do
                read (u_test, "(A)", iostat=iostat1) buffer1
                read (u_ref, "(A)", iostat=iostat2) buffer2
                if (iostat1 /= iostat2) then
                    success = .false.
                    exit COMPARE_FILES
                else if (iostat1 < 0) then
                    success = .true.
                    exit COMPARE_FILES
                else if (buffer1 /= buffer2) then
                    success = .false.
                    exit COMPARE_FILES
                end if
            end do COMPARE_FILES
            close (u_ref)
        else
            write (*, "(A)", advance="no") " ... no reference output available"
            write (u_log, "(A)") " No reference output available."
            success = .false.
        end if
        if (success) then
            write (*, "(A)") " ... success."
            write (u_log, "(A)") " Success."
        else
            write (*, "(A)") " ... failure. See: " // err_prefix//name//err
            write (u_log, "(A)") " Failure."
            rewind (u_test)
            u_err = free_unit ()
            open (u_err, file=err_prefix//name//err, &

```

```

        action="write", status="replace")
WRITE_OUTPUT: do
    read (u_test, "(A)", end=1) buffer1
    write (u_err, "(A)") trim (buffer1)
end do WRITE_OUTPUT
1    close (u_err)
end if
close (u_test)
call results%add (name, description, success)
end subroutine test

```

4.1.5 Convenience functions

Unit tests should include a lot of assertions that only involve IO if something is wrong. `assert` allows to streamline this method.

```

<Tests: public>+≡
    public :: assert

<Tests: procedures>+≡
    subroutine assert (unit, ok, description)
        integer, intent(in) :: unit
        logical, intent(in) :: ok
        character(*), intent(in), optional :: description
        if (.not. ok) then
            if (present(description)) then
                write (unit, "(A)") "* FAIL: " // description
            else
                write (unit, "(A)") "* FAIL: Assertion error"
            end if
        end if
    end subroutine assert

```

Compare numbers and output error message if not equal.

```

<Tests: public>+≡
    public:: assert_equal
    interface assert_equal
        module procedure assert_equal_real, assert_equal_integer
    end interface

<Tests: procedures>+≡
    subroutine assert_equal_real (unit, lhs, rhs, description, &
        abs_smallness, rel_smallness)
        real(default), intent(in), optional :: abs_smallness, rel_smallness
        integer, intent(in) :: unit
        real(default), intent(in) :: lhs, rhs
        character(*), intent(in), optional :: description
        logical :: ok
        ok = nearly_equal (lhs, rhs, abs_smallness, rel_smallness)
        if (.not. ok) then
            if (present(description)) then
                write (unit, "(A," // FMT_19 // ",A," // FMT_19 // ")") &
                    "* FAIL: " // description // ": ", lhs, " /= ", rhs
            end if
        end if
    end subroutine assert_equal_real

```



```

        else
            write (unit, "(A," // FMT_19 // ",A," // FMT_19 // ")") &
                "* FAIL: Assertion error: ", lhs, " /= ", rhs
        end if
    end if
end if
end subroutine assert_equal_real

```

<Tests: procedures>+≡

```

subroutine assert_equal_integer (unit, lhs, rhs, description)
    integer, intent(in) :: unit
    integer, intent(in) :: lhs, rhs
    character(*), intent(in), optional :: description
    logical :: ok
    ok = lhs == rhs
    if (.not. ok) then
        if (present(description)) then
            write (unit, "(A,IO,A,IO)") &
                "* FAIL: " // description // ": ", lhs, " /= ", rhs
        else
            write (unit, "(A,IO,A,IO)") &
                "* FAIL: Assertion error: ", lhs, " /= ", rhs
        end if
    end if
end if
end subroutine assert_equal_integer

```

Note that this poor man's check will be disabled if someone compiles with `-ffast-math` or similar optimizations.

<Tests: procedures>+≡

```

elemental function ieee_is_nan (x) result (yorn)
    logical :: yorn
    real(default), intent(in) :: x
    yorn = (x /= x)
end function ieee_is_nan

```

This is still not perfect but should work in most cases. Usually one wants to compare to a relative epsilon `rel_smallness`, except for numbers close to zero defined by `abs_smallness`. Both might need adaption to specific use cases but have reasonable defaults.

<Tests: public>+≡

```

public :: nearly_equal

```

<Tests: procedures>+≡

```

elemental function nearly_equal (a, b, abs_smallness, rel_smallness) result (r)
    logical :: r
    real(default), intent(in) :: a, b
    real(default), intent(in), optional :: abs_smallness, rel_smallness
    real(default) :: abs_a, abs_b, diff, abs_small, rel_small
    abs_a = abs (a)
    abs_b = abs (b)
    diff = abs (a - b)
    ! shortcut, handles infinities and nans
    if (a == b) then
        r = .true.
    end if

```

```

        return
    else if (ieee_is_nan (a) .or. ieee_is_nan (b) .or. ieee_is_nan (diff)) then
        r = .false.
        return
    end if
    abs_small = tiny_13; if (present (abs_smallness)) abs_small = abs_smallness
    rel_small = tiny_10; if (present (rel_smallness)) rel_small = rel_smallness
    if (abs_a < abs_small .and. abs_b < abs_small) then
        r = diff < abs_small
    else
        r = diff / max (abs_a, abs_b) < rel_small
    end if
end function nearly_equal

```

Often we will need to check whether floats vanish:

```

<Tests: public>+≡
public:: vanishes
interface vanishes
    module procedure vanishes_real, vanishes_complex
end interface

<Tests: procedures>+≡
elemental function vanishes_real (x, abs_smallness, rel_smallness) result (r)
    logical :: r
    real(default), intent(in) :: x
    real(default), intent(in), optional :: abs_smallness, rel_smallness
    r = nearly_equal (x, zero, abs_smallness, rel_smallness)
end function vanishes_real

elemental function vanishes_complex (x, abs_smallness, rel_smallness) result (r)
    logical :: r
    complex(default), intent(in) :: x
    real(default), intent(in), optional :: abs_smallness, rel_smallness
    r = vanishes_real (abs (x), abs_smallness, rel_smallness)
end function vanishes_complex

```

Chapter 5

System: Interfaces and Handlers

Here, we collect modules that deal with the “system”: operating-system interfaces, error handlers and diagnostics.

system_defs Constants relevant for the modules in this set.

diagnostics Error and diagnostic message handling. Any messages and errors issued by WHIZARD functions are handled by the subroutines in this module, if possible.

os_interface Execute system calls, build and link external object files and libraries.

cputime Timer data type and methods, for measuring performance.

5.1 Constants

The parameters here are used in various parts of the program, starting from the modules in the current chapter. Some of them may be modified if the need arises.

```
<system_defs.f90>≡  
  <File header>  
  
  module system_defs  
  
    use, intrinsic :: iso_fortran_env, only: iostat_end, iostat_eor !NODEP!  
  
    <Standard module head>  
  
    <System defs: public parameters>  
  
  end module system_defs
```

5.1.1 Version

The version string is used for checking files. Note that the string length MUST NOT be changed, because reading binary files relies on it.

```
<System defs: public parameters>≡  
  integer, parameter, public :: VERSION_STRLEN = 255  
  character(len=VERSION_STRLEN), parameter, public :: &  
    & VERSION_STRING = "WHIZARD version <Version> (<Date>)"
```

5.1.2 Text Buffer

There is a hard limit on the line length which we should export. This buffer size is used both by the message handler, the lexer, and some further modules.

```
<System defs: public parameters>+≡  
  integer, parameter, public :: BUFFER_SIZE = 1000
```

5.1.3 IOSTAT Codes

Defined in `iso_fortran_env`, but we would like to use shorthands.

```
<System defs: public parameters>+≡  
  integer, parameter, public :: EOF = iostat_end, EOR = iostat_eor
```

5.1.4 Character Codes

Single-character constants.

```
<System defs: public parameters>+≡  
  character, parameter, public :: BLANK = ' '  
  character, parameter, public :: TAB = achar(9)  
  character, parameter, public :: CR = achar(13)  
  character, parameter, public :: LF = achar(10)  
  character, parameter, public :: BACKSLASH = achar(92)
```

Character strings that indicate character classes.

```
<System defs: public parameters>+≡  
  character(*), parameter, public :: WHITESPACE_CHARS = BLANK// TAB // CR // LF  
  character(*), parameter, public :: LCLETTERS = "abcdefghijklmnopqrstuvwxyz"  
  character(*), parameter, public :: UCLETTERS = "ABCDEFGHIJKLMNOPQRSTUVWXYZ"  
  character(*), parameter, public :: DIGITS = "0123456789"
```

5.2 C wrapper for sigaction

This implements calls to `sigaction` and the appropriate signal handlers in C. The functionality is needed for the `diagnostics` module.

```
<signal_interface.c>≡  
  /*
```

```

<File header>
*/
#include <signal.h>
#include <stdlib.h>

extern int wo_sigint;
extern int wo_sigterm;
extern int wo_sigxcpu;
extern int wo_sigxfsz;

static void wo_handler_sigint (int sig) {
    wo_sigint = sig;
}

static void wo_handler_sigterm (int sig) {
    wo_sigterm = sig;
}

static void wo_handler_sigxcpu (int sig) {
    wo_sigxcpu = sig;
}

static void wo_handler_sigxfsz (int sig) {
    wo_sigxfsz = sig;
}

int wo_mask_sigint () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigint;
    return sigaction(SIGINT, &sa, NULL);
}

int wo_mask_sigterm () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigterm;
    return sigaction(SIGTERM, &sa, NULL);
}

int wo_mask_sigxcpu () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigxcpu;
    return sigaction(SIGXCPU, &sa, NULL);
}

```

```

}

int wo_mask_sigxfsz () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigxfsz;
    return sigaction(SIGXFSZ, &sa, NULL);
}

int wo_release_sigint () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGINT, &sa, NULL);
}

int wo_release_sigterm () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGTERM, &sa, NULL);
}

int wo_release_sigxcpu () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGXCPU, &sa, NULL);
}

int wo_release_sigxfsz () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGXFSZ, &sa, NULL);
}

```

5.3 C wrapper for printf

The `printf` family of functions is implemented in C with an undefined number of arguments. This is not supported by the `bind(C)` interface. We therefore write wrappers for the versions of `sprintf` that we will actually use.

This is used by the `formats` module.

```
(sprintf_interface.c)≡
/*
  <File header>
*/
#include <stdio.h>

int sprintf_none(char* str, const char* format) {
  return sprintf(str, format);
}

int sprintf_int(char* str, const char* format, int val) {
  return sprintf(str, format, val);
}

int sprintf_double(char* str, const char* format, double val) {
  return sprintf(str, format, val);
}

int sprintf_str(char* str, const char* format, const char* val) {
  return sprintf(str, format, val);
}

(sprintf interfaces)≡
interface
  function sprintf_none (str, fmt) result (stat) bind(C)
    use iso_c_binding !NODEP!
    integer(c_int) :: stat
    character(c_char), dimension(*), intent(inout) :: str
    character(c_char), dimension(*), intent(in) :: fmt
  end function sprintf_none
end interface

interface
  function sprintf_int (str, fmt, val) result (stat) bind(C)
    use iso_c_binding !NODEP!
    integer(c_int) :: stat
    character(c_char), dimension(*), intent(inout) :: str
    character(c_char), dimension(*), intent(in) :: fmt
    integer(c_int), value :: val
  end function sprintf_int
end interface

interface
  function sprintf_double (str, fmt, val) result (stat) bind(C)
    use iso_c_binding !NODEP!
    integer(c_int) :: stat
    character(c_char), dimension(*), intent(inout) :: str
```

```

        character(c_char), dimension(*), intent(in) :: fmt
        real(c_double), value :: val
    end function sprintf_double
end interface

interface
    function sprintf_str(str, fmt, val) result (stat) bind(C)
        use iso_c_binding !NODEP!
        integer(c_int) :: stat
        character(c_char), dimension(*), intent(inout) :: str
        character(c_char), dimension(*), intent(in) :: fmt
        character(c_char), dimension(*), intent(in) :: val
    end function sprintf_str
end interface

```

5.4 Error, Message and Signal Handling

We are not so ambitious as to do proper exception handling in WHIZARD, but at least it may be useful to have a common interface for diagnostics: Results, messages, warnings, and such. As module variables we keep a buffer where the current message may be written to and a level indicator which tells which messages should be written on screen and which ones should be skipped. Alternatively, a string may be directly supplied to the message routine: this overrides the buffer, avoiding the necessity of formatted I/O in trivial cases.

(diagnostics.f90)≡

⟨File header⟩

module diagnostics

```

    use, intrinsic :: iso_c_binding !NODEP!
    use, intrinsic :: iso_fortran_env, only: output_unit !NODEP!

```

⟨Use kinds⟩

⟨Use strings⟩

```

    use io_units

```

```

    use system_dependencies

```

```

    use system_defs, only: BUFFER_SIZE, MAX_ERRORS

```

⟨Standard module head⟩

⟨Diagnostics: public⟩

⟨Diagnostics: parameters⟩

⟨Diagnostics: types⟩

⟨Diagnostics: variables⟩

⟨Diagnostics: interfaces⟩

contains

<Diagnostics: procedures>

end module diagnostics

Diagnostics levels:

```
<Diagnostics: parameters>≡  
  integer, parameter :: &  
    & TERMINATE=-2, BUG=-1, &  
    & FATAL=1, ERROR=2, WARNING=3, MESSAGE=4, RESULT=5, DEBUG=6
```

```
<Diagnostics: variables>≡  
  integer, save :: msg_level = RESULT
```

Mask fatal errors so that are treated as normal errors. Useful for interactive mode.

```
<Diagnostics: public>≡  
  public :: mask_fatal_errors
```

```
<Diagnostics: variables>+≡  
  logical, save :: mask_fatal_errors = .false.
```

How to handle bugs and unmasked fatal errors. Either execute a normal stop statement, or call the C `exit()` function, or try to cause a program crash by dereferencing a null pointer.

```
<Diagnostics: parameters>+≡  
  integer, parameter :: TERM_STOP = 0, TERM_EXIT = 1, TERM_CRASH = 2
```

```
<Diagnostics: variables>+≡  
  integer, save :: handle_fatal_errors = TERM_EXIT
```

Keep track of errors. This might be used for exception handling, later. The counter is incremented only for screen messages, to avoid double counting.

```
<Diagnostics: public>+≡  
  public :: msg_count
```

```
<Diagnostics: variables>+≡  
  integer, dimension(TERMINATE:DEBUG), save :: msg_count = 0
```

Keep a list of all errors and warnings. Since we do not know the number of entries beforehand, we use a linked list.

```
<Diagnostics: types>≡  
  type :: string_list  
    character(len=BUFFER_SIZE) :: string  
    type(string_list), pointer :: next  
  end type string_list  
  type :: string_list_pointer  
    type(string_list), pointer :: first, last  
  end type string_list_pointer
```

```
<Diagnostics: variables>+≡  
  type(string_list_pointer), dimension(TERMINATE:WARNING), save :: &  
    & msg_list = string_list_pointer (null(), null())
```

Add the current message buffer contents to the internal list.

```

<Diagnostics: procedures>≡
subroutine msg_add (level)
  integer, intent(in) :: level
  type(string_list), pointer :: message
  select case (level)
  case (TERMINATE:WARNING)
    allocate (message)
    message%string = msg_buffer
    nullify (message%next)
    if (.not.associated (msg_list(level)%first)) &
      & msg_list(level)%first => message
    if (associated (msg_list(level)%last)) &
      & msg_list(level)%last%next => message
    msg_list(level)%last => message
    msg_count(level) = msg_count(level) + 1
  end select
end subroutine msg_add

```

Initialization:

```

<Diagnostics: public>+≡
public :: msg_list_clear

<Diagnostics: procedures>+≡
subroutine msg_list_clear
  integer :: level
  type(string_list), pointer :: message
  do level = TERMINATE, WARNING
    do while (associated (msg_list(level)%first))
      message => msg_list(level)%first
      msg_list(level)%first => message%next
      deallocate (message)
    end do
    nullify (msg_list(level)%last)
  end do
  msg_count = 0
end subroutine msg_list_clear

```

Display the summary of errors and warnings (no need to count fatals...)

```

<Diagnostics: public>+≡
public :: msg_summary

<Diagnostics: procedures>+≡
subroutine msg_summary (unit)
  integer, intent(in), optional :: unit
  call expect_summary (unit)
1  format (A,1x,I2,1x,A,I2,1x,A)
  if (msg_count(ERROR) > 0 .and. msg_count(WARNING) > 0) then
    write (msg_buffer, 1) "There were", &
      & msg_count(ERROR), "error(s) and ", &
      & msg_count(WARNING), "warning(s). "
    call msg_message (unit=unit)
  else if (msg_count(ERROR) > 0) then
    write (msg_buffer, 1) "There were", &

```

```

        & msg_count(ERROR), "error(s) and no warnings."
    call msg_message (unit=unit)
else if (msg_count(WARNING) > 0) then
    write (msg_buffer, 1) "There were no errors and ", &
        & msg_count(WARNING), "warning(s)."
    call msg_message (unit=unit)
end if
end subroutine msg_summary

```

Print the list of all messages of a given level.

```

<Diagnostics: public>+≡
    public :: msg_listing

<Diagnostics: procedures>+≡
    subroutine msg_listing (level, unit, prefix)
        integer, intent(in) :: level
        integer, intent(in), optional :: unit
        character(len=*), intent(in), optional :: prefix
        type(string_list), pointer :: message
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        if (present (unit)) u = unit
        message => msg_list(level)%first
        do while (associated (message))
            if (present (prefix)) then
                write (u, "(A)") prefix // trim (message%string)
            else
                write (u, "(A)") trim (message%string)
            end if
            message => message%next
        end do
        flush (u)
    end subroutine msg_listing

```

The message buffer:

```

<Diagnostics: public>+≡
    public :: msg_buffer

<Diagnostics: variables>+≡
    character(len=BUFFER_SIZE), save :: msg_buffer = " "

```

After a message is issued, the buffer should be cleared:

```

<Diagnostics: procedures>+≡
    subroutine buffer_clear
        msg_buffer = " "
    end subroutine buffer_clear

```

The generic handler for messages. If the unit is omitted (or = 6), the message is written to standard output if the precedence is sufficiently high (as determined by the value of `msg_level`). If the string is omitted, the buffer is used. In any case, the buffer is cleared after printing. In accordance with FORTRAN custom, the first column in the output is left blank. For messages and warnings,

an additional exclamation mark and a blank is prepended. Furthermore, each message is appended to the internal message list (without prepending anything).

(Diagnostics: procedures)+≡

```

subroutine message_print (level, string, str_arr, unit, logfile)
  integer, intent(in) :: level
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: str_arr
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: logfile
  type(string_t) :: prep_string, aux_string, head_footer
  integer :: lu, i
  logical :: severe, is_error
  severe = .false.
  head_footer = "*****"
  aux_string = ""
  is_error = .false.
  select case (level)
  case (TERMINATE)
    prep_string = ""
  case (BUG)
    prep_string = "*** WHIZARD BUG: "
    aux_string = "*** "
    severe = .true.
    is_error = .true.
  case (FATAL)
    prep_string = "*** FATAL ERROR: "
    aux_string = "*** "
    severe = .true.
    is_error = .true.
  case (ERROR)
    prep_string = "*** ERROR: "
    aux_string = "*** "
    is_error = .true.
  case (WARNING)
    prep_string = "Warning: "
  case (MESSAGE, DEBUG)
    prep_string = "| "
  case default
    prep_string = ""
  end select
  if (present(string)) msg_buffer = string
  lu = log_unit
  if (present(unit)) then
    if (unit /= output_unit) then
      if (severe) write (unit, "(A)") char(head_footer)
      if (is_error) write (unit, "(A)") char(head_footer)
      write (unit, "(A,A)") char(prep_string), trim(msg_buffer)
      if (present(str_arr)) then
        do i = 1, size(str_arr)
          write (unit, "(A,A)") char(aux_string), char(trim(str_arr(i)))
        end do
      end if
      if (is_error) write (unit, "(A)") char(head_footer)
      if (severe) write (unit, "(A)") char(head_footer)
    end if
  end if
end subroutine message_print

```

```

        flush (unit)
        lu = -1
    else if (level <= msg_level) then
        if (severe) print "(A)", char(head_footer)
        if (is_error) print "(A)", char(head_footer)
        print "(A,A)", char(prepare_string), trim(msg_buffer)
        if (present (str_arr)) then
            do i = 1, size(str_arr)
                print "(A,A)", char(aux_string), char(trim(str_arr(i)))
            end do
        end if
        if (is_error) print "(A)", char(head_footer)
        if (severe) print "(A)", char(head_footer)
        flush (output_unit)
        if (unit == log_unit) lu = -1
    end if
else if (level <= msg_level) then
    if (severe) print "(A)", char(head_footer)
    if (is_error) print "(A)", char(head_footer)
    print "(A,A)", char(prepare_string), trim(msg_buffer)
    if (present (str_arr)) then
        do i = 1, size(str_arr)
            print "(A,A)", char(aux_string), char(trim(str_arr(i)))
        end do
    end if
    if (is_error) print "(A)", char(head_footer)
    if (severe) print "(A)", char(head_footer)
    flush (output_unit)
end if
if (present (logfile)) then
    if (.not. logfile) lu = -1
end if
if (logging .and. lu >= 0) then
    if (severe) write (lu, "(A)") char(head_footer)
    if (is_error) write (lu, "(A)") char(head_footer)
    write (lu, "(A,A)") char(prepare_string), trim(msg_buffer)
    if (present (str_arr)) then
        do i = 1, size(str_arr)
            write (lu, "(A,A)") char(aux_string), char(trim(str_arr(i)))
        end do
    end if
    if (is_error) write (lu, "(A)") char(head_footer)
    if (severe) write (lu, "(A)") char(head_footer)
    flush (lu)
end if
call msg_add (level)
call buffer_clear
end subroutine message_print

```

The number of non-fatal errors that we allow before stopping the program. We might trade this later for an adjustable number.

<System defs: public parameters>+≡

integer, parameter, public :: MAX_ERRORS = 10

The specific handlers. In the case of fatal errors, bugs (failed assertions) and normal termination execution is stopped. For non-fatal errors a message is printed to standard output if no unit is given. Only if the number of MAX_ERRORS errors is reached, we abort the program. There are no further actions in the other cases, but this may change.

<Diagnostics: public>+≡

```
public :: msg_terminate
public :: msg_bug, msg_fatal, msg_error, msg_warning
public :: msg_message, msg_result, msg_debug
```

<Diagnostics: procedures>+≡

```
subroutine msg_terminate (string, unit, quit_code)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  integer, intent(in), optional :: quit_code
  integer(c_int) :: return_code
  call release_term_signals ()
  if (present (quit_code)) then
    return_code = quit_code
  else
    return_code = 0
  end if
  if (present (string)) &
    call message_print (MESSAGE, string, unit=unit)
  call msg_summary (unit)
  if (return_code == 0 .and. expect_failures /= 0) then
    return_code = 5
    call message_print (MESSAGE, &
      "WHIZARD run finished with 'expect' failure(s).", unit=unit)
  else if (return_code == 7) then
    call message_print (MESSAGE, &
      "WHIZARD run finished with failed self-test.", unit=unit)
  else
    call message_print (MESSAGE, "WHIZARD run finished.", unit=unit)
  end if
  call message_print (0, &
    "|=====|", unit=unit)
  call logfile_final ()
  call msg_list_clear ()
  if (return_code /= 0) then
    call exit (return_code)
  else
    !!! Should implement WHIZARD exit code (currently only via C)
    ! stop
    call exit (0)
  end if
end subroutine msg_terminate

subroutine msg_bug (string, arr, unit)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  logical, pointer :: crash_ptr
  call message_print (BUG, string, arr, unit)
```

```

call msg_summary (unit)
select case (handle_fatal_errors)
case (TERM_EXIT)
    call message_print (TERMINATE, "WHIZARD run aborted.", unit=unit)
    call exit (-1_c_int)
case (TERM_CRASH)
    print *, "*** Intentional crash ***"
    crash_ptr => null ()
    print *, crash_ptr
end select
stop "WHIZARD run aborted."
end subroutine msg_bug

recursive subroutine msg_fatal (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    logical, pointer :: crash_ptr
    if (mask_fatal_errors) then
        call msg_error (string, arr, unit)
    else
        call message_print (FATAL, string, arr, unit)
        call msg_summary (unit)
        select case (handle_fatal_errors)
        case (TERM_EXIT)
            call message_print (TERMINATE, "WHIZARD run aborted.", unit=unit)
            call exit (1_c_int)
        case (TERM_CRASH)
            print *, "*** Intentional crash ***"
            crash_ptr => null ()
            print *, crash_ptr
        end select
        stop "WHIZARD run aborted."
    end if
end subroutine msg_fatal

subroutine msg_error (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    call message_print (ERROR, string, arr, unit)
    if (msg_count(ERROR) >= MAX_ERRORS) then
        mask_fatal_errors = .false.
        call msg_fatal (" Too many errors encountered.")
    else if (.not.present(unit) .and. .not.mask_fatal_errors) then
        call message_print (MESSAGE, "                (WHIZARD run continues)")
    end if
end subroutine msg_error

subroutine msg_warning (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    call message_print (WARNING, string, arr, unit)

```

```

end subroutine msg_warning

subroutine msg_message (string, unit, arr, logfile)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  logical, intent(in), optional :: logfile
  call message_print (MESSAGE, string, arr, unit, logfile)
end subroutine msg_message

subroutine msg_result (string, arr, unit, logfile)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  logical, intent(in), optional :: logfile
  call message_print (RESULT, string, arr, unit, logfile)
end subroutine msg_result

subroutine msg_debug (string, arr, unit)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  call message_print (DEBUG, string, arr, unit)
end subroutine msg_debug

```

Show the progress of a loop in steps of 10 %. Could be generalized to other step sizes with an optional argument.

```

<Diagnostics: public>+≡
  public :: msg_show_progress

<Diagnostics: procedures>+≡
  subroutine msg_show_progress (i_call, n_calls)
    integer, intent(in) :: i_call, n_calls
    real(default) :: progress
    integer, save :: next_check
    if (i_call == 1) next_check = 10
    progress = (i_call * 100._default) / n_calls
    if (progress >= next_check) then
      write (msg_buffer, "(F5.1,A)") progress, "%"
      call msg_message ()
      next_check = next_check + 10
    end if
  end subroutine msg_show_progress

```

Interface to the standard clib exit function

```

<Diagnostics: interfaces>≡
  interface
    subroutine exit (status) bind (C)
      use iso_c_binding !NODEP!
      integer(c_int), value :: status
    end subroutine exit
  end interface

```


Print the WHIZARD banner:

<Diagnostics: public>+≡

public :: msg_banner

<Diagnostics: procedures>+≡

subroutine msg_banner (unit)

integer, intent(in), optional :: unit

integer :: n_proc

call message_print (0, "|=====

call message_print (0, "|

call message_print (0, "| WW WW WW WW WW WWWWW WW WWWWW WWWWW

call message_print (0, "| WW WW WW WW WW WW WW WWW WW WW WW WW

call message_print (0, "| WW WW WW WW WWWWWW WW WW WW WW WWWWW WW WW WW

call message_print (0, "| WWW WWW WW WW WW WW WWWWWW WW WW WW WW

call message_print (0, "| WW WW WW WW WW WWWWW WW WW WW WW WW WW WW

call message_print (0, "|

call message_print (0, "|

call message_print (0, "| W

call message_print (0, "| sW

call message_print (0, "| WW

call message_print (0, "| sWW

call message_print (0, "| WWW

call message_print (0, "| wWWW

call message_print (0, "| wWWW

call message_print (0, "| WW WW

call message_print (0, "| WW WW

call message_print (0, "| wWW WW

call message_print (0, "| wWW WW

call message_print (0, "| WW WW

call message_print (0, "| WW WW

call message_print (0, "| WW WW

call message_print (0, "| WW WW

call message_print (0, "| WW WW

call message_print (0, "| WW WW

call message_print (0, "|

call message_print (0, "| WWWWW WW WW

call message_print (0, "| WWWWWww WW WW

call message_print (0, "| WWWWWwwww WW WW

call message_print (0, "| WWWWWwwwwww WW

call message_print (0, "| WWWWWWWWWWWWW WW

call message_print (0, "| WWWWW WW WWWWWWW

call message_print (0, "| WWW WW WW WWWWWWWww

call message_print (0, "| WWWWW WWWWWWWWWWW WWw

call message_print (0, "| WWWWW WWWWW

call message_print (0, "| WWWWWww WWWWW

call message_print (0, "| WWWWWww WWWWW

call message_print (0, "| WWWWWww WWWWWWW

call message_print (0, "|

call message_print (0, "|

call message_print (0, "|

call message_print (0, "|

call message_print (0, "| by: Wolfgang Kilian, Thorsten Ohl, Juergen Reuter

call message_print (0, "| with contributions from Christian Speckner

call message_print (0, "| Contact: <whizard@desy.de>

call message_print (0, "|

call message_print (0, "| if you use WHIZARD please cite:

by: Wolfgang Kilian, Thorsten Ohl, Juergen Reuter
with contributions from Christian Speckner
Contact: <whizard@desy.de>

if you use WHIZARD please cite:

```

call message_print (0, "|      W. Kilian, T. Ohl, J. Reuter, Eur.Phys.J.C71 (2011) 1742
call message_print (0, "|      [arXiv: 0708.4233 [hep-ph]]
call message_print (0, "|      M. Moretti, T. Ohl, J. Reuter, arXiv: hep-ph/0102195
call message_print (0, "|
call message_print (0, "|=====
call message_print (0, "|      WHIZARD " // WHIZARD_VERSION, unit=uni
call message_print (0, "|=====
end subroutine msg_banner

```

5.4.1 Logfile

All screen output should be duplicated in the logfile, unless requested otherwise.

```

<Diagnostics: public>+≡
  public :: logging

<Diagnostics: variables>+≡
  integer, save :: log_unit = -1
  logical, target, save :: logging = .false.

<Diagnostics: public>+≡
  public :: logfile_init

<Diagnostics: procedures>+≡
  subroutine logfile_init (filename)
    type(string_t), intent(in) :: filename
    call msg_message ("Writing log to '" // char (filename) // "'")
    if (.not. logging) call msg_message ("(Logging turned off.)")
    log_unit = free_unit ()
    open (file = char (filename), unit = log_unit, &
          action = "write", status = "replace")
  end subroutine logfile_init

<Diagnostics: public>+≡
  public :: logfile_final

<Diagnostics: procedures>+≡
  subroutine logfile_final ()
    if (log_unit >= 0) then
      close (log_unit)
      log_unit = -1
    end if
  end subroutine logfile_final

```

This returns the valid logfile unit only if the default is write to screen, and if logfile is not set false.

```

<Diagnostics: public>+≡
  public :: logfile_unit

<Diagnostics: procedures>+≡
  function logfile_unit (unit, logfile)
    integer :: logfile_unit
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: logfile
    if (logging) then

```

```

    if (present (unit)) then
      if (unit == output_unit) then
        logfile_unit = log_unit
      else
        logfile_unit = -1
      end if
    else if (present (logfile)) then
      if (logfile) then
        logfile_unit = log_unit
      else
        logfile_unit = -1
      end if
    else
      logfile_unit = log_unit
    end if
  else
    logfile_unit = -1
  end if
end function logfile_unit

```

5.4.2 Checking values

The `expect` function does not just check a value for correctness (actually, it checks if a logical expression is true); it records its result here. If failures are present when the program terminates, the exit code is nonzero.

```

<Diagnostics: variables>+≡
  integer, save :: expect_total = 0
  integer, save :: expect_failures = 0

<Diagnostics: public>+≡
  public :: expect_record

<Diagnostics: procedures>+≡
  subroutine expect_record (success)
    logical, intent(in) :: success
    expect_total = expect_total + 1
    if (.not. success) expect_failures = expect_failures + 1
  end subroutine expect_record

<Diagnostics: public>+≡
  public :: expect_clear

<Diagnostics: procedures>+≡
  subroutine expect_clear ()
    expect_total = 0
    expect_failures = 0
  end subroutine expect_clear

<Diagnostics: public>+≡
  public :: expect_summary

```

```

<Diagnostics: procedures>+≡
subroutine expect_summary (unit, force)
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: force
  logical :: force_output
  force_output = .false.; if (present (force)) force_output = force
  if (expect_total /= 0 .or. force_output) then
    call msg_message ("Summary of value checks:", unit)
    write (msg_buffer, "(2x,A,1x,I0,1x,A,1x,A,1x,I0)") &
      "Failures:", expect_failures, "/", "Total:", expect_total
    call msg_message (unit=unit)
  end if
end subroutine expect_summary

```

Helpers for converting integers into strings with minimal length.

```

<Diagnostics: public>+≡
public :: int2string
public :: int2char
public :: int2fixed

<Diagnostics: procedures>+≡
pure function int2fixed (i) result (c)
  integer, intent(in) :: i
  character(200) :: c
  c = ""
  write (c, *) i
  c = adjustl (c)
end function int2fixed

pure function int2string (i) result (s)
  integer, intent(in) :: i
  type (string_t) :: s
  s = trim (int2fixed (i))
end function int2string

pure function int2char (i) result (c)
  integer, intent(in) :: i
  character(len (trim (int2fixed (i)))) :: c
  c = int2fixed (i)
end function int2char

```

Dito for reals.

```

<Diagnostics: public>+≡
public :: real2string
public :: real2char
public :: real2fixed

<Diagnostics: interfaces>+≡
interface real2string
  module procedure real2string_list, real2string_fmt
end interface
interface real2char
  module procedure real2char_list, real2char_fmt
end interface

```

```

<Diagnostics: procedures>+≡
  pure function real2fixed (x, fmt) result (c)
    real(default), intent(in) :: x
    character(*), intent(in), optional :: fmt
    character(200) :: c
    c = ""
    write (c, *) x
    c = adjustl (c)
  end function real2fixed

  pure function real2fixed_fmt (x, fmt) result (c)
    real(default), intent(in) :: x
    character(*), intent(in) :: fmt
    character(200) :: c
    c = ""
    write (c, fmt) x
    c = adjustl (c)
  end function real2fixed_fmt

  pure function real2string_list (x) result (s)
    real(default), intent(in) :: x
    type(string_t) :: s
    s = trim (real2fixed (x))
  end function real2string_list

  pure function real2string_fmt (x, fmt) result (s)
    real(default), intent(in) :: x
    character(*), intent(in) :: fmt
    type(string_t) :: s
    s = trim (real2fixed_fmt (x, fmt))
  end function real2string_fmt

  pure function real2char_list (x) result (c)
    real(default), intent(in) :: x
    character(len_trim (real2fixed (x))) :: c
    c = real2fixed (x)
  end function real2char_list

  pure function real2char_fmt (x, fmt) result (c)
    real(default), intent(in) :: x
    character(*), intent(in) :: fmt
    character(len_trim (real2fixed_fmt (x, fmt))) :: c
    c = real2fixed_fmt (x, fmt)
  end function real2char_fmt

```

Dito for complex values; we do not use the slightly ugly FORTRAN output form here but instead introduce our own. Ifort and Portland seem to have problems with this, therefore temporarily disable it.

```

<CCC Diagnostics: public>≡
  public :: cmplx2string
  public :: cmplx2char

<CCC Diagnostics: procedures>≡
  pure function cmplx2string (x) result (s)

```

```

        complex(default), intent(in) :: x
        type(string_t) :: s
        s = real2string (real (x, default))
        if (aimag (x) /= 0) s = s // " + " // real2string (aimag (x)) // " I"
    end function cmplx2string

    pure function cmplx2char (x) result (c)
        complex(default), intent(in) :: x
        character(len (char (cmplx2string (x)))) :: c
        c = char (cmplx2string (x))
    end function cmplx2char

```

5.4.3 Suppression of numerical noise

```

<Diagnostics: public>+≡
    public :: pacify

<Diagnostics: interfaces>+≡
    interface pacify
        module procedure pacify_real_default
        module procedure pacify_complex_default
    end interface pacify

<Diagnostics: procedures>+≡
    elemental subroutine pacify_real_default (x, tolerance)
        real(default), intent(inout) :: x
        real(default), intent(in) :: tolerance
        if (abs (x) < tolerance) x = 0._default
    end subroutine pacify_real_default

    elemental subroutine pacify_complex_default (x, tolerance)
        complex(default), intent(inout) :: x
        real(default), intent(in) :: tolerance
        if (abs (real (x)) < tolerance) &
            x = cmplx (0._default, aimag (x), kind=default)
        if (abs (aimag (x)) < tolerance) &
            x = cmplx (real (x), 0._default, kind=default)
    end subroutine pacify_complex_default

```

5.4.4 Signal handling

Killing the program by external signals may leave the files written by it in an undefined state. This can be avoided by catching signals and deferring program termination. Instead of masking only critical sections, we choose to mask signals globally (done in the main program) and terminate the program at predefined checkpoints only. Checkpoints are after each command, within the sampling function (so the program can be terminated after each event), and after each iteration in the phase-space generation algorithm.

Signal handling is done via a C interface to the `sigaction` system call. When a signal is raised that has been masked by the handler, the corresponding

variable is set to the value of the signal. The variables are visible from the C signal handler.

The signal SIGINT is for keyboard interrupt (ctrl-C), SIGTERM is for system interrupt, e.g., at shutdown. The SIGXCPU and SIGXFSZ signals may be issued by batch systems.

```

(Diagnostics: public)+≡
    public :: wo_sigint
    public :: wo_sigterm
    public :: wo_sigxcpu
    public :: wo_sigxfsz

(Diagnostics: variables)+≡
    integer(c_int), bind(C), volatile :: wo_sigint = 0
    integer(c_int), bind(C), volatile :: wo_sigterm = 0
    integer(c_int), bind(C), volatile :: wo_sigxcpu = 0
    integer(c_int), bind(C), volatile :: wo_sigxfsz = 0

```

Here are the interfaces to the C functions. The routine `mask_term_signals` forces termination signals to be delayed. `release_term_signals` restores normal behavior. However, the program can be terminated anytime by calling `terminate_now_if_signal` which inspects the signals and terminates the program if requested..

```

(Diagnostics: public)+≡
    public :: mask_term_signals

(Diagnostics: procedures)+≡
    subroutine mask_term_signals ()
        integer(c_int) :: status
        logical :: ok
        wo_sigint = 0
        ok = wo_mask_sigint () == 0
        if (.not. ok) call msg_error ("Masking SIGINT failed")
        wo_sigterm = 0
        ok = wo_mask_sigterm () == 0
        if (.not. ok) call msg_error ("Masking SIGTERM failed")
        wo_sigxcpu = 0
        ok = wo_mask_sigxcpu () == 0
        if (.not. ok) call msg_error ("Masking SIGXCPU failed")
        wo_sigxfsz = 0
        ok = wo_mask_sigxfsz () == 0
        if (.not. ok) call msg_error ("Masking SIGXFSZ failed")
    end subroutine mask_term_signals

(Diagnostics: interfaces)+≡
    interface
        integer(c_int) function wo_mask_sigint () bind(C)
        import
    end function wo_mask_sigint
    end interface
    interface
        integer(c_int) function wo_mask_sigterm () bind(C)
        import
    end function wo_mask_sigterm
    end interface

```

```

        end function wo_mask_sigterm
    end interface
interface
    integer(c_int) function wo_mask_sigxcpu () bind(C)
        import
    end function wo_mask_sigxcpu
end interface
interface
    integer(c_int) function wo_mask_sigxfsz () bind(C)
        import
    end function wo_mask_sigxfsz
end interface

<Diagnostics: public>+≡
    public :: release_term_signals

<Diagnostics: procedures>+≡
    subroutine release_term_signals ()
        integer(c_int) :: status
        logical :: ok
        ok = wo_release_sigint () == 0
        if (.not. ok) call msg_error ("Releasing SIGINT failed")
        ok = wo_release_sigterm () == 0
        if (.not. ok) call msg_error ("Releasing SIGTERM failed")
        ok = wo_release_sigxcpu () == 0
        if (.not. ok) call msg_error ("Releasing SIGXCPU failed")
        ok = wo_release_sigxfsz () == 0
        if (.not. ok) call msg_error ("Releasing SIGXFSZ failed")
    end subroutine release_term_signals

<Diagnostics: interfaces>+≡
    interface
        integer(c_int) function wo_release_sigint () bind(C)
            import
        end function wo_release_sigint
    end interface
    interface
        integer(c_int) function wo_release_sigterm () bind(C)
            import
        end function wo_release_sigterm
    end interface
    interface
        integer(c_int) function wo_release_sigxcpu () bind(C)
            import
        end function wo_release_sigxcpu
    end interface
    interface
        integer(c_int) function wo_release_sigxfsz () bind(C)
            import
        end function wo_release_sigxfsz
    end interface

<Diagnostics: public>+≡
    public :: signal_is_pending

```



```

<Diagnostics: procedures>+≡
function signal_is_pending () result (flag)
  logical :: flag
  flag = &
    wo_sigint /= 0 .or. &
    wo_sigterm /= 0 .or. &
    wo_sigxcpu /= 0 .or. &
    wo_sigxfsz /= 0
end function signal_is_pending

<Diagnostics: public>+≡
public :: terminate_now_if_signal

<Diagnostics: procedures>+≡
subroutine terminate_now_if_signal ()
  if (wo_sigint /= 0) then
    call msg_terminate ("Signal SIGINT (keyboard interrupt) received.", &
      quit_code=int (wo_sigint))
  else if (wo_sigterm /= 0) then
    call msg_terminate ("Signal SIGTERM (termination signal) received.", &
      quit_code=int (wo_sigterm))
  else if (wo_sigxcpu /= 0) then
    call msg_terminate ("Signal SIGXCPU (CPU time limit exceeded) received.", &
      quit_code=int (wo_sigxcpu))
  else if (wo_sigxfsz /= 0) then
    call msg_terminate ("Signal SIGXFSZ (file size limit exceeded) received.", &
      quit_code=int (wo_sigxfsz))
  end if
end subroutine terminate_now_if_signal

```

5.5 Operating-system interface

For specific purposes, we need direct access to the OS (system calls). This is, of course, system dependent. The current version is valid for GNU/Linux; we expect to use a preprocessor for this module if different OSs are to be supported.

The current implementation lacks error handling.

```

<os_interface.f90>≡
<File header>

module os_interface

  use, intrinsic :: iso_c_binding !NODEP!

  <Use strings>
  use io_units
  use unit_tests
  use diagnostics
  use system_defs, only: DLERROR_LEN, ENVVAR_LEN
  use system_dependencies

  <Standard module head>

```

```

<OS interface: public>

<OS interface: types>

<OS interface: interfaces>

contains

<OS interface: procedures>

<OS interface: tests>

end module os_interface

```

5.5.1 Path variables

This is a transparent container for storing user-defined path variables.

```

<OS interface: public>≡
  public :: paths_t

<OS interface: types>≡
  type :: paths_t
    type(string_t) :: prefix
    type(string_t) :: exec_prefix
    type(string_t) :: bindir
    type(string_t) :: libdir
    type(string_t) :: includedir
    type(string_t) :: datarootdir
    type(string_t) :: localprefix
    type(string_t) :: libtool
    type(string_t) :: lhapdfdir
  end type paths_t

<OS interface: public>+≡
  public :: paths_init

<OS interface: procedures>≡
  subroutine paths_init (paths)
    type(paths_t), intent(out) :: paths
    paths%prefix = ""
    paths%exec_prefix = ""
    paths%bindir = ""
    paths%libdir = ""
    paths%includedir = ""
    paths%datarootdir = ""
    paths%localprefix = ""
    paths%libtool = ""
    paths%lhapdfdir = ""
  end subroutine paths_init

```

5.5.2 System dependencies

We store all potentially system- and user/run-dependent data in a transparent container. This includes compiler/linker names and flags, file extensions, etc. There are actually two different possibilities for extensions of shared libraries, depending on whether the Fortran compiler or the system linker (usually the C compiler) has been used for linking. The default for the Fortran compiler on most systems is `.so`.

```
<OS interface: public>+≡  
    public :: os_data_t
```

```
<OS interface: types>+≡  
    type :: os_data_t  
        logical :: use_libtool  
        logical :: use_testfiles  
        type(string_t) :: fc  
        type(string_t) :: fcflags  
        type(string_t) :: fcflags_pic  
        type(string_t) :: fc_src_ext  
        type(string_t) :: cc  
        type(string_t) :: cflags  
        type(string_t) :: cflags_pic  
        type(string_t) :: obj_ext  
        type(string_t) :: ld  
        type(string_t) :: ldflags  
        type(string_t) :: ldflags_so  
        type(string_t) :: ldflags_static  
        type(string_t) :: ldflags_hepmc  
        type(string_t) :: ldflags_hoppet  
        type(string_t) :: ldflags_looptools  
        type(string_t) :: shrlib_ext  
        type(string_t) :: fc_shrlib_ext  
        type(string_t) :: makeflags  
        type(string_t) :: prefix  
        type(string_t) :: exec_prefix  
        type(string_t) :: bindir  
        type(string_t) :: libdir  
        type(string_t) :: includedir  
        type(string_t) :: datarootdir  
        type(string_t) :: whizard_omega_binpath  
        type(string_t) :: whizard_includes  
        type(string_t) :: whizard_ldflags  
        type(string_t) :: whizard_libtool  
        type(string_t) :: whizard_modelpath  
        type(string_t) :: whizard_models_libpath  
        type(string_t) :: whizard_susypath  
        type(string_t) :: whizard_gmlpath  
        type(string_t) :: whizard_cutspath  
        type(string_t) :: whizard_texpath  
        type(string_t) :: whizard_testdatapath  
        type(string_t) :: whizard_modelpath_local  
        type(string_t) :: whizard_models_libpath_local  
        type(string_t) :: whizard_omega_binpath_local  
        type(string_t) :: whizard_circe2path
```

```

type(string_t) :: whizard_beamsimpath
type(string_t) :: whizard_mulipath
type(string_t) :: pdf_builtin_datapath
logical :: event_analysis = .false.
logical :: event_analysis_ps = .false.
logical :: event_analysis_pdf = .false.
type(string_t) :: latex
type(string_t) :: mpost
type(string_t) :: gml
type(string_t) :: dvips
type(string_t) :: ps2pdf
type(string_t) :: gosampath
type(string_t) :: golempath
type(string_t) :: formpath
type(string_t) :: qgrafpath
type(string_t) :: ninjapath
type(string_t) :: samuraipath
end type os_data_t

```

Since all are allocatable strings, explicit initialization is necessary.

```

<System defs: public parameters>+≡
integer, parameter, public :: ENVVAR_LEN = 1000

<OS interface: public>+≡
public :: os_data_init

<OS interface: procedures>+≡
subroutine os_data_init (os_data, paths)
type(os_data_t), intent(out) :: os_data
type(paths_t), intent(in), optional :: paths
character(len=ENVVAR_LEN) :: home
type(string_t) :: localprefix, local_includes
os_data%use_libtool = .true.
inquire (file = "TESTFLAG", exist = os_data%use_testfiles)
call get_environment_variable ("HOME", home)
if (present(paths)) then
if (paths%localprefix == "") then
localprefix = trim (home) // "/.whizard"
else
localprefix = paths%localprefix
end if
else
localprefix = trim (home) // "/.whizard"
end if
local_includes = localprefix // "/lib/whizard/mod/models"
os_data%whizard_modelpath_local = localprefix // "/share/whizard/models"
os_data%whizard_models_libpath_local = localprefix // "/lib/whizard/models"
os_data%whizard_omega_binpath_local = localprefix // "/bin"
os_data%fc = DEFAULT_FC
os_data%fcflags = DEFAULT_FCFLAGS
os_data%fcflags_pic = DEFAULT_FCFLAGS_PIC
os_data%fc_src_ext = DEFAULT_FC_SRC_EXT
os_data%cc = DEFAULT_CC
os_data%cflags = DEFAULT_CFLAGS
os_data%cflags_pic = DEFAULT_CFLAGS_PIC

```

```

os_data%obj_ext      = DEFAULT_OBJ_EXT
os_data%ld           = DEFAULT_LD
os_data%ldflags      = DEFAULT_LDFLAGS
os_data%ldflags_so   = DEFAULT_LDFLAGS_SO
os_data%ldflags_static = DEFAULT_LDFLAGS_STATIC
os_data%ldflags_hepmc = DEFAULT_LDFLAGS_HEPMC
os_data%ldflags_hoppet = DEFAULT_LDFLAGS_HOPPET
os_data%ldflags_looptools = DEFAULT_LDFLAGS_LOOPTOOLS
os_data%shrlib_ext   = DEFAULT_SHRLIB_EXT
os_data%fc_shrlib_ext = DEFAULT_FC_SHRLIB_EXT
os_data%makeflags    = DEFAULT_MAKEFLAGS
os_data%prefix       = PREFIX
os_data%exec_prefix  = EXEC_PREFIX
os_data%bindir       = BINDIR
os_data%libdir        = LIBDIR
os_data%includedir   = INCLUDEDIR
os_data%datarootdir  = DATAROOTDIR
if (present (paths)) then
  if (paths%prefix /= "") os_data%prefix = paths%prefix
  if (paths%exec_prefix /= "") os_data%exec_prefix = paths%exec_prefix
  if (paths%bindir /= "") os_data%bindir = paths%bindir
  if (paths%libdir /= "") os_data%libdir = paths%libdir
  if (paths%includedir /= "") os_data%includedir = paths%includedir
  if (paths%datarootdir /= "") os_data%datarootdir = paths%datarootdir
end if
if (os_data%use_testfiles) then
  os_data%whizard_omega_binpath = WHIZARD_TEST_OMEGA_BINPATH
  os_data%whizard_includes      = WHIZARD_TEST_INCLUDES
  os_data%whizard_ldflags       = WHIZARD_TEST_LDFLAGS
  os_data%whizard_libtool       = WHIZARD_LIBTOOL_TEST
  os_data%whizard_modelpath     = WHIZARD_TEST_MODELPATH
  os_data%whizard_models_libpath = WHIZARD_TEST_MODELS_LIBPATH
  os_data%whizard_susypath      = WHIZARD_TEST_SUSYPATH
  os_data%whizard_gmlpath       = WHIZARD_TEST_GMLPATH
  os_data%whizard_cutspath      = WHIZARD_TEST_CUTSPATH
  os_data%whizard_texpath       = WHIZARD_TEST_TEXPATH
  os_data%whizard_testdatapath  = WHIZARD_TEST_TESTDATAPATH
  os_data%whizard_circe2path    = WHIZARD_TEST_CIRCE2PATH
  os_data%whizard_beamsimp      = WHIZARD_TEST_BEAMSIMP
  os_data%whizard_mulipath      = WHIZARD_TEST_MULIPATH
  os_data%pdf_builtin_datapath  = PDF_BUILTIN_TEST_DATAPATH
else
  if (os_dir_exist (local_includes)) then
    os_data%whizard_includes = "-I" // local_includes // " " // &
    WHIZARD_INCLUDES
  else
    os_data%whizard_includes = WHIZARD_INCLUDES
  end if
  os_data%whizard_omega_binpath = WHIZARD_OMEGA_BINPATH
  os_data%whizard_ldflags       = WHIZARD_LDFLAGS
  os_data%whizard_libtool       = WHIZARD_LIBTOOL
  if (present(paths)) then
    if (paths%libtool /= "") os_data%whizard_libtool = paths%libtool
  end if
end if

```

```

os_data%whizard_modelpath      = WHIZARD_MODELPATH
os_data%whizard_models_libpath = WHIZARD_MODELS_LIBPATH
os_data%whizard_susypath       = WHIZARD_SUSYPATH
os_data%whizard_gmlpath        = WHIZARD_GMLPATH
os_data%whizard_cutspath       = WHIZARD_CUTSPATH
os_data%whizard_texpath        = WHIZARD_TEXPATH
os_data%whizard_testdatapath   = WHIZARD_TESTDATAPATH
os_data%whizard_circe2path     = WHIZARD_CIRCE2PATH
os_data%whizard_beamsimpath    = WHIZARD_BEAMSIMPATH
os_data%whizard_mulipath       = WHIZARD_MULIPATH
os_data%pdf_builtin_datapath   = PDF_BUILTIN_DATAPATH
end if
os_data%event_analysis         = EVENT_ANALYSIS      == "yes"
os_data%event_analysis_ps      = EVENT_ANALYSIS_PS   == "yes"
os_data%event_analysis_pdf     = EVENT_ANALYSIS_PDF  == "yes"
os_data%latex                  = PRG_LATEX // " " // OPT_LATEX
os_data%mpost                  = PRG_MPOST // " " // OPT_MPOST
if (os_data%use_testfiles) then
  os_data%gml                  = os_data%whizard_gmlpath // "/whizard-gml" // " " // &
    OPT_MPOST // " " // "--gml_dir " // os_data%whizard_gmlpath
else
  os_data%gml                  = os_data%bindir // "/whizard-gml" // " " // OPT_MPOST &
    // " " // "--gml_dir " // os_data%whizard_gmlpath
end if
os_data%dvips                  = PRG_DVIPS
os_data%ps2pdf                 = PRG_PS2PDF
call os_data_expand_paths (os_data)
os_data%gosampath              = GOSAM_DIR
os_data%golempath              = GOLEM_DIR
os_data%formpath               = FORM_DIR
os_data%qgrafpath              = QGRAF_DIR
os_data%ninjabpath             = NINJA_DIR
os_data%samuraiath             = SAMURAI_DIR
end subroutine os_data_init

```

Replace occurrences of GNU path variables (such as `${prefix}`) by their values. Do this for all strings that could depend on them, and do the replacement in reverse order, since the path variables may be defined in terms of each other.

(OS interface: procedures)+≡

```

subroutine os_data_expand_paths (os_data)
  type(os_data_t), intent(inout) :: os_data
  integer, parameter :: N_VARIABLES = 6
  type(string_t), dimension(N_VARIABLES) :: variable, value
  variable(1) = "${prefix}";      value(1) = os_data%prefix
  variable(2) = "${exec_prefix}"; value(2) = os_data%exec_prefix
  variable(3) = "${bindir}";      value(3) = os_data%bindir
  variable(4) = "${libdir}";      value(4) = os_data%libdir
  variable(5) = "${includedir}";  value(5) = os_data%includedir
  variable(6) = "${datarootdir}"; value(6) = os_data%datarootdir
  call expand_paths (os_data%whizard_omega_binpath)
  call expand_paths (os_data%whizard_includes)
  call expand_paths (os_data%whizard_ldflags)
  call expand_paths (os_data%whizard_libtool)

```

```

call expand_paths (os_data%whizard_modelpath)
call expand_paths (os_data%whizard_models_libpath)
call expand_paths (os_data%whizard_susypath)
call expand_paths (os_data%whizard_gmlpath)
call expand_paths (os_data%whizard_cutspath)
call expand_paths (os_data%whizard_texpath)
call expand_paths (os_data%whizard_testdatapath)
call expand_paths (os_data%whizard_circe2path)
call expand_paths (os_data%whizard_beamsimpath)
call expand_paths (os_data%whizard_mulipath)
call expand_paths (os_data%whizard_models_libpath_local)
call expand_paths (os_data%whizard_modelpath_local)
call expand_paths (os_data%whizard_omega_binpath_local)
call expand_paths (os_data%pdf_builtin_datapath)
call expand_paths (os_data%latex)
call expand_paths (os_data%mpost)
call expand_paths (os_data%gml)
call expand_paths (os_data%dvips)
call expand_paths (os_data%ps2pdf)
contains
  subroutine expand_paths (string)
    type(string_t), intent(inout) :: string
    integer :: i
    do i = N_VARIABLES, 1, -1
      string = replace (string, variable(i), value(i), every=.true.)
    end do
  end subroutine expand_paths
end subroutine os_data_expand_paths

```

Write contents

```

<OS interface: public>+≡
  public :: os_data_write

<OS interface: procedures>+≡
  subroutine os_data_write (os_data, unit)
    type(os_data_t), intent(in) :: os_data
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A)") "OS data:"
    write (u, *) "use_libtool      = ", os_data%use_libtool
    write (u, *) "use_testfiles   = ", os_data%use_testfiles
    write (u, *) "fc              = ", char (os_data%fc)
    write (u, *) "fcflags        = ", char (os_data%fcflags)
    write (u, *) "fcflags_pic     = ", char (os_data%fcflags_pic)
    write (u, *) "fc_src_ext      = ", char (os_data%fc_src_ext)
    write (u, *) "cc              = ", char (os_data%cc)
    write (u, *) "cflags         = ", char (os_data%cflags)
    write (u, *) "cflags_pic     = ", char (os_data%cflags_pic)
    write (u, *) "obj_ext        = ", char (os_data%obj_ext)
    write (u, *) "ld              = ", char (os_data%ld)
    write (u, *) "ldflags         = ", char (os_data%ldflags)
    write (u, *) "ldflags_so      = ", char (os_data%ldflags_so)
    write (u, *) "ldflags_static = ", char (os_data%ldflags_static)

```

```

write (u, *) "ldflags_hepmc = ", char (os_data%ldflags_hepmc)
write (u, *) "ldflags_hoppet = ", char (os_data%ldflags_hoppet)
write (u, *) "ldflags_looptools = ", char (os_data%ldflags_looptools)
write (u, *) "shrlib_ext = ", char (os_data%shrlib_ext)
write (u, *) "fc_shrlib_ext = ", char (os_data%fc_shrlib_ext)
write (u, *) "makeflags = ", char (os_data%makeflags)
write (u, *) "prefix = ", char (os_data%prefix)
write (u, *) "exec_prefix = ", char (os_data%exec_prefix)
write (u, *) "bindir = ", char (os_data%bindir)
write (u, *) "libdir = ", char (os_data%libdir)
write (u, *) "includedir = ", char (os_data%includedir)
write (u, *) "datarootdir = ", char (os_data%datarootdir)
write (u, *) "whizard_omega_binpath = ", &
char (os_data%whizard_omega_binpath)
write (u, *) "whizard_includes = ", char (os_data%whizard_includes)
write (u, *) "whizard_ldflags = ", char (os_data%whizard_ldflags)
write (u, *) "whizard_libtool = ", char (os_data%whizard_libtool)
write (u, *) "whizard_modelpath = ", &
char (os_data%whizard_modelpath)
write (u, *) "whizard_models_libpath = ", &
char (os_data%whizard_modelpath)
write (u, *) "whizard_susypath = ", char (os_data%whizard_susypath)
write (u, *) "whizard_gmlpath = ", char (os_data%whizard_gmlpath)
write (u, *) "whizard_cutspath = ", char (os_data%whizard_cutspath)
write (u, *) "whizard_texpath = ", char (os_data%whizard_texpath)
write (u, *) "whizard_circe2path = ", char (os_data%whizard_circe2path)
write (u, *) "whizard_beamsimpath = ", char (os_data%whizard_beamsimpath)
write (u, *) "whizard_mulipath = ", char (os_data%whizard_mulipath)
write (u, *) "whizard_testdatapath = ", &
char (os_data%whizard_testdatapath)
write (u, *) "whizard_modelpath_local = ", &
char (os_data%whizard_modelpath_local)
write (u, *) "whizard_models_libpath_local = ", &
char (os_data%whizard_models_libpath_local)
write (u, *) "whizard_omega_binpath_local = ", &
char (os_data%whizard_omega_binpath_local)
write (u, *) "event_analysis = ", os_data%event_analysis
write (u, *) "event_analysis_ps = ", os_data%event_analysis_ps
write (u, *) "event_analysis_pdf = ", os_data%event_analysis_pdf
write (u, *) "latex = ", char (os_data%latex)
write (u, *) "mpost = ", char (os_data%mpost)
write (u, *) "gml = ", char (os_data%gml)
write (u, *) "dvips = ", char (os_data%dvips)
write (u, *) "ps2pdf = ", char (os_data%ps2pdf)
if (os_data%gosampath /= "") then
write (u, *) "gosam = ", char (os_data%gosampath)
write (u, *) "golem = ", char (os_data%golempath)
write (u, *) "form = ", char (os_data%formpath)
write (u, *) "qgraf = ", char (os_data%qgrafpath)
write (u, *) "ninja = ", char (os_data%ninjapath)
write (u, *) "samurai = ", char (os_data%samurairpath)
end if
end subroutine os_data_write

```


5.5.3 Dynamic linking

We define a type that holds the filehandle for a dynamically linked library (shared object), together with functions to open and close the library, and to access functions in this library.

```
<OS interface: public>+≡
    public :: dlaccess_t
<OS interface: types>+≡
    type :: dlaccess_t
        private
        type(string_t) :: filename
        type(c_ptr) :: handle = c_null_ptr
        logical :: is_open = .false.
        logical :: has_error = .false.
        type(string_t) :: error
    contains
    <OS interface: dlaccess: TBP>
end type dlaccess_t
```

Output. This is called by the output routine for the process library.

```
<OS interface: dlaccess: TBP>≡
    procedure :: write => dlaccess_write
<OS interface: procedures>+≡
    subroutine dlaccess_write (object, unit)
        class(dlaccess_t), intent(in) :: object
        integer, intent(in) :: unit
        write (unit, "(1x,A)") "DL access info:"
        write (unit, "(3x,A,L1)") "is open   = ", object%is_open
        if (object%has_error) then
            write (unit, "(3x,A,A,A)") "error       = '", char (object%error), "'"
        else
            write (unit, "(3x,A)") "error       = [none]"
        end if
    end subroutine dlaccess_write
```

The interface to the library functions:

```
<OS interface: interfaces>≡
    interface
        function dlopen (filename, flag) result (handle) bind(C)
            import
            character(c_char), dimension(*) :: filename
            integer(c_int), value :: flag
            type(c_ptr) :: handle
        end function dlopen
    end interface

    interface
        function dlclose (handle) result (status) bind(C)
            import
            type(c_ptr), value :: handle
            integer(c_int) :: status
        end function dlclose
```

```

end interface

interface
  function dlerror () result (str) bind(C)
    import
    type(c_ptr) :: str
  end function dlerror
end interface

interface
  function dlsym (handle, symbol) result (fptr) bind(C)
    import
    type(c_ptr), value :: handle
    character(c_char), dimension(*) :: symbol
    type(c_funptr) :: fptr
  end function dlsym
end interface

```

This reads an error string and transforms it into a `string_t` object, if an error has occurred. If not, set the error flag to false and return an empty string.

```

<System defs: public parameters>+≡
  integer, parameter, public :: DLERROR_LEN = 160

<OS interface: procedures>+≡
  subroutine read_dlerror (has_error, error)
    logical, intent(out) :: has_error
    type(string_t), intent(out) :: error
    type(c_ptr) :: err_cptr
    character(len=DLERROR_LEN, kind=c_char), pointer :: err_fptr
    integer :: str_end
    err_cptr = dlerror ()
    if (c_associated (err_cptr)) then
      call c_f_pointer (err_cptr, err_fptr)
      has_error = .true.
      str_end = scan (err_fptr, c_null_char)
      if (str_end > 0) then
        error = err_fptr(1:str_end-1)
      else
        error = err_fptr
      end if
    else
      has_error = .false.
      error = ""
    end if
  end subroutine read_dlerror

```

This is the Fortran API. Init/final open and close the file, i.e., load and unload the library.

Note that a library can be opened more than once, and that for an ultimate close as many `dlclose` calls as `dlopen` calls are necessary. However, we assume that it is opened and closed only once.

```

<OS interface: public>+≡
  public :: dlaccess_init

```

```

    public :: dlaccess_final
<OS interface: dlaccess: TBP>+≡
    procedure :: init => dlaccess_init
    procedure :: final => dlaccess_final
<OS interface: procedures>+≡
    subroutine dlaccess_init (dlaccess, prefix, libname, os_data)
        class(dlaccess_t), intent(out) :: dlaccess
        type(string_t), intent(in) :: prefix, libname
        type(os_data_t), intent(in), optional :: os_data
        type(string_t) :: filename
        logical :: exist
        dlaccess%filename = libname
        filename = prefix // "/" // libname
        inquire (file=char(filename), exist=exist)
        if (.not. exist) then
            filename = prefix // "/.libs/" // libname
            inquire (file=char(filename), exist=exist)
            if (.not. exist) then
                dlaccess%has_error = .true.
                dlaccess%error = "Library '" // filename // "' not found"
                return
            end if
        end if
        dlaccess%handle = dlopen (char (filename) // c_null_char, ior ( &
            RTLD_LAZY, RTLD_LOCAL))
        dlaccess%is_open = c_associated (dlaccess%handle)
        call read_dlerror (dlaccess%has_error, dlaccess%error)
    end subroutine dlaccess_init

    subroutine dlaccess_final (dlaccess)
        class(dlaccess_t), intent(inout) :: dlaccess
        integer(c_int) :: status
        if (dlaccess%is_open) then
            status = dlclose (dlaccess%handle)
            dlaccess%is_open = .false.
            call read_dlerror (dlaccess%has_error, dlaccess%error)
        end if
    end subroutine dlaccess_final

```

Return true if an error has occurred.

```

<OS interface: public>+≡
    public :: dlaccess_has_error
<OS interface: procedures>+≡
    function dlaccess_has_error (dlaccess) result (flag)
        logical :: flag
        type(dlaccess_t), intent(in) :: dlaccess
        flag = dlaccess%has_error
    end function dlaccess_has_error

```

Return the error string currently stored in the dlaccess object.

```

<OS interface: public>+≡
    public :: dlaccess_get_error

```

```

<OS interface: procedures>+≡
  function dlaccess_get_error (dlaccess) result (error)
    type(string_t) :: error
    type(dlaccess_t), intent(in) :: dlaccess
    error = dlaccess%error
  end function dlaccess_get_error

```

The symbol handler returns the C address of the function with the given string name. (It is a good idea to use `bind(C)` for all functions accessed by this, such that the name string is well-defined.) Call `c_f_procpointer` to cast this into a Fortran procedure pointer with an appropriate interface.

```

<OS interface: public>+≡
  public :: dlaccess_get_c_funptr

<OS interface: procedures>+≡
  function dlaccess_get_c_funptr (dlaccess, fname) result (fptr)
    type(c_funptr) :: fptr
    type(dlaccess_t), intent(inout) :: dlaccess
    type(string_t), intent(in) :: fname
    fptr = dlsym (dlaccess%handle, char (fname) // c_null_char)
    call read_dlerror (dlaccess%has_error, dlaccess%error)
  end function dlaccess_get_c_funptr

```

5.5.4 Predicates

Return true if the library is loaded. In particular, this is false if loading was unsuccessful.

```

<OS interface: public>+≡
  public :: dlaccess_is_open

<OS interface: procedures>+≡
  function dlaccess_is_open (dlaccess) result (flag)
    logical :: flag
    type(dlaccess_t), intent(in) :: dlaccess
    flag = dlaccess%is_open
  end function dlaccess_is_open

```

5.5.5 Shell access

This is the standard system call for executing a shell command, such as invoking a compiler.

In F2008 there will be the equivalent built-in command `execute_command_line`.

```

<OS interface: public>+≡
  public :: os_system_call

<OS interface: procedures>+≡
  subroutine os_system_call (command_string, status, verbose)
    type(string_t), intent(in) :: command_string
    integer, intent(out), optional :: status
    logical, intent(in), optional :: verbose
    logical :: verb

```

```

integer :: stat
verb = .false.; if (present (verbose)) verb = verbose
if (verb) &
    call msg_message ("command: " // char (command_string))
stat = system (char (command_string) // c_null_char)
if (present (status)) then
    status = stat
else if (stat /= 0) then
    if (.not. verb) &
        call msg_message ("command: " // char (command_string))
    write (msg_buffer, "(A,I0)") "Return code = ", stat
    call msg_message ()
    call msg_fatal ("System command returned with nonzero status code")
end if
end subroutine os_system_call

```

```

<OS interface: interfaces>+≡
interface
    function system (command) result (status) bind(C)
        import
        integer(c_int) :: status
        character(c_char), dimension(*) :: command
    end function system
end interface

```

5.5.6 Querying for a directory

This queries for the existence of a directory. There is no standard way to achieve this in FORTRAN, and if we were to call into `libc`, we would need access to C macros for evaluating the result, so we resort to calling `test` as a system call.

```

<OS interface: public>+≡
public :: os_dir_exist

```

```

<OS interface: procedures>+≡
function os_dir_exist (name) result (res)
    type(string_t), intent(in) :: name
    logical :: res
    integer :: status
    call os_system_call ('test -d "' // name // '"', status=status)
    res = status == 0
end function os_dir_exist

```

```

<OS interface: public>+≡
public :: os_file_exist

```

```

<OS interface: procedures>+≡
function os_file_exist (name) result (exist)
    type(string_t), intent(in) :: name
    ! logical, intent(in), optional :: verb
    logical :: exist
    ! integer :: status
    ! call os_system_call ('test -f "' // name // '"', status=status, verbose=verb)
    ! res = (status == 0)
end function os_file_exist

```

```

    inquire (file = char (name), exist=exist)
end function os_file_exist

```

5.5.7 Fortran compiler and linker

Compile a single module for use in a shared library, but without linking.

```

<OS interface: public>+≡
    public :: os_compile_shared

<OS interface: procedures>+≡
    subroutine os_compile_shared (src, os_data, status)
        type(string_t), intent(in) :: src
        type(os_data_t), intent(in) :: os_data
        integer, intent(out), optional :: status
        type(string_t) :: command_string
        if (os_data%use_libtool) then
            command_string = &
                os_data%whizard_libtool // " --mode=compile " // &
                os_data%fc // " " // &
                "-c " // &
                os_data%whizard_includes // " " // &
                os_data%fcflags // " " // &
                "" // src // os_data%fc_src_ext // ""
        else
            command_string = &
                os_data%fc // " " // &
                "-c " // &
                os_data%fcflags_pic // " " // &
                os_data%whizard_includes // " " // &
                os_data%fcflags // " " // &
                "" // src // os_data%fc_src_ext // ""
        end if
        call os_system_call (command_string, status)
    end subroutine os_compile_shared

```

Link an array of object files to build a shared object library. In the libtool case, we have to specify a `-rpath`, otherwise only a static library can be built. However, since the library is never installed, this `rpath` is irrelevant.

```

<OS interface: public>+≡
    public :: os_link_shared

<OS interface: procedures>+≡
    subroutine os_link_shared (objlist, lib, os_data, status)
        type(string_t), intent(in) :: objlist, lib
        type(os_data_t), intent(in) :: os_data
        integer, intent(out), optional :: status
        type(string_t) :: command_string
        if (os_data%use_libtool) then
            command_string = &
                os_data%whizard_libtool // " --mode=link " // &
                os_data%fc // " " // &
                "-module " // &

```

```

        "-rpath /usr/local/lib" // " " // &
        os_data%fcflags // " " // &
        os_data%whizard_ldflags // " " // &
        os_data%ldflags // " " // &
        "-o '" // lib // ".la' " // &
        objlist
    else
        command_string = &
        os_data%ld // " " // &
        os_data%ldflags_so // " " // &
        os_data%fcflags // " " // &
        os_data%whizard_ldflags // " " // &
        os_data%ldflags // " " // &
        "-o '" // lib // os_data%shrlib_ext // "' " // &
        objlist
    end if
    call os_system_call (command_string, status)
end subroutine os_link_shared

```

Link an array of object files / libraries to build a static executable.

```

<OS interface: public>+≡
    public :: os_link_static

<OS interface: procedures>+≡
    subroutine os_link_static (objlist, exec_name, os_data, status)
        type(string_t), intent(in) :: objlist, exec_name
        type(os_data_t), intent(in) :: os_data
        integer, intent(out), optional :: status
        type(string_t) :: command_string
        if (os_data%use_libtool) then
            command_string = &
            os_data%whizard_libtool // " --mode=link " // &
            os_data%fc // " " // &
            "-static-libtool-libs " // &
            os_data%fcflags // " " // &
            os_data%whizard_ldflags // " " // &
            os_data%ldflags // " " // &
            os_data%ldflags_static // " " // &
            "-o '" // exec_name // "' " // &
            objlist // " " // &
            os_data%ldflags_hepmc // " " // &
            os_data%ldflags_hoppet // " " // &
            os_data%ldflags_looptools
        else
            command_string = &
            os_data%ld // " " // &
            os_data%ldflags_so // " " // &
            os_data%fcflags // " " // &
            os_data%whizard_ldflags // " " // &
            os_data%ldflags // " " // &
            os_data%ldflags_static // " " // &
            "-o '" // exec_name // "' " // &
            objlist // " " // &
            os_data%ldflags_hepmc // " " // &

```

```

        os_data%ldflags_hoppet // " " // &
        os_data%ldflags_looptools
    end if
    call os_system_call (command_string, status)
end subroutine os_link_static

```

Determine the name of the shared library to link. If libtool is used, this is encoded in the .la file which resides in place of the library itself.

```

<OS interface: public>+≡
    public :: os_get_dlname

<OS interface: procedures>+≡
    function os_get_dlname (lib, os_data, ignore, silent) result (dlname)
        type(string_t) :: dlname
        type(string_t), intent(in) :: lib
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: ignore, silent
        type(string_t) :: filename
        type(string_t) :: buffer
        logical :: exist, required, quiet
        integer :: u
        u = free_unit ()
        if (present (ignore)) then
            required = .not. ignore
        else
            required = .true.
        end if
        if (present (silent)) then
            quiet = silent
        else
            quiet = .false.
        end if
        if (os_data%use_libtool) then
            filename = lib // ".la"
            inquire (file=char(filename), exist=exist)
            if (exist) then
                open (unit=u, file=char(filename), action="read", status="old")
                SCAN_LTFILE: do
                    call get (u, buffer)
                    if (extract (buffer, 1, 7) == "dlname=") then
                        dlname = extract (buffer, 9)
                        dlname = remove (dlname, len (dlname))
                    exit SCAN_LTFILE
                end do SCAN_LTFILE
                close (u)
            else if (required) then
                if (.not. quiet) call msg_fatal (" Library '" // char (lib) &
                    // "': libtool archive not found")
                dlname = ""
            else
                if (.not. quiet) call msg_message ("[No compiled library '" &
                    // char (lib) // "']")
                dlname = ""
            end if
        end if
    end function os_get_dlname

```



```

        end if
    else
        dlname = lib // os_data%shrlib_ext
        inquire (file=char(dlname), exist=exist)
        if (.not. exist) then
            if (required) then
                if (.not. quiet) call msg_fatal (" Library '" // char(lib) &
                    // "' not found")
            else
                if (.not. quiet) call msg_message &
                    ("[No compiled process library '" // char(lib) // "']")
                dlname = ""
            end if
        end if
    end if
end function os_get_dlname

```

5.5.8 Controlling OpenMP

OpenMP is handled automatically by the library for the most part. Here is a convenience routine for setting the number of threads, with some diagnostics.

```

<OS interface: public>+≡
    public :: openmp_set_num_threads_verbose

<OS interface: procedures>+≡
    subroutine openmp_set_num_threads_verbose (num_threads, openmp_logging)
        integer, intent(in) :: num_threads
        integer :: n_threads
        logical, intent(in), optional :: openmp_logging
        logical :: logging
        if (present (openmp_logging)) then
            logging = openmp_logging
        else
            logging = .true.
        end if
        n_threads = num_threads
        if (openmp_is_active ()) then
            if (num_threads == 1) then
                if (logging) then
                    write (msg_buffer, "(A,I0,A)") "OpenMP: Using ", num_threads, &
                        " thread"
                    call msg_message
                end if
                n_threads = num_threads
            else if (num_threads > 1) then
                if (logging) then
                    write (msg_buffer, "(A,I0,A)") "OpenMP: Using ", num_threads, &
                        " threads"
                    call msg_message
                end if
                n_threads = num_threads
            else
                if (logging) then

```

```

        write (msg_buffer, "(A,I0,A)") "OpenMP: " &
        // "Illegal value of openmp_num_threads (", num_threads, &
        ") ignored"
        call msg_error
    end if
    n_threads = openmp_get_default_max_threads ()
    if (logging) then
        write (msg_buffer, "(A,I0,A)") "OpenMP: Using ", &
        n_threads, " threads"
        call msg_message
    end if
end if
if (n_threads > openmp_get_default_max_threads ()) then
    if (logging) then
        write (msg_buffer, "(A,I0,A)") "OpenMP: " &
        // "Number of threads is greater than library default of ", &
        openmp_get_default_max_threads ()
        call msg_warning
    end if
end if
call openmp_set_num_threads (n_threads)
else if (num_threads /= 1) then
    if (logging) then
        write (msg_buffer, "(A,I0,A)") "openmp_num_threads set to ", &
        num_threads, ", but OpenMP is not active: ignored"
        call msg_warning
    end if
end if
end if
end subroutine openmp_set_num_threads_verbose

```

5.5.9 Unit tests

```

<OS interface: public>+≡
    public :: os_interface_test

<OS interface: procedures>+≡
    subroutine os_interface_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <OS interface: execute tests>
    end subroutine os_interface_test

```

Write a Fortran source file, compile it to a shared library, load it, and execute the contained function.

```

<OS interface: execute tests>≡
    call test (os_interface_1, "os_interface_1", &
        "check OS interface routines", &
        u, results)

<OS interface: tests>≡
    subroutine os_interface_1 (u)
        integer, intent(in) :: u
        type(dlaccess_t) :: dlaccess

```

```

type(string_t) :: fname, libname, ext
type(os_data_t) :: os_data
type(string_t) :: filename_src, filename_obj
abstract interface
    function so_test_proc (i) result (j) bind(C)
        import c_int
        integer(c_int), intent(in) :: i
        integer(c_int) :: j
    end function so_test_proc
end interface
procedure(so_test_proc), pointer :: so_test => null ()
type(c_funptr) :: c_fptr
integer :: unit
integer(c_int) :: i
call os_data_init (os_data)
fname = "so_test"
filename_src = fname // os_data%fc_src_ext
if (os_data%use_libtool) then
    ext = ".lo"
else
    ext = os_data%obj_ext
end if
filename_obj = fname // ext
libname = fname // '.' // os_data%fc_shrlib_ext

write (u, "(A)")  "* Test output: OS interface"
write (u, "(A)")  "* Purpose: check os_interface routines"
write (u, "(A)")

write (u, "(A)")  "* write source file 'so_test.f90'"
write (u, "(A)")
unit = free_unit ()
open (unit=unit, file=char(filename_src), action="write")
write (unit, "(A)")  "function so_test (i) result (j) bind(C)"
write (unit, "(A)")  "  use iso_c_binding"
write (unit, "(A)")  "  integer(c_int), intent(in) :: i"
write (unit, "(A)")  "  integer(c_int) :: j"
write (unit, "(A)")  "  j = 2 * i"
write (unit, "(A)")  "end function so_test"
close (unit)
write (u, "(A)")  "* compile and link as 'so_test.so/dylib'"
write (u, "(A)")
call os_compile_shared (fname, os_data)
call os_link_shared (filename_obj, fname, os_data)
write (u, "(A)")  "* load library 'so_test.so/dylib'"
write (u, "(A)")
call dlaccess_init (dlaccess, var_str ("."), libname, os_data)
if (dlaccess_is_open (dlaccess)) then
    write (u, "(A)")  "      success"
else
    write (u, "(A)")  "      failure"
end if
write (u, "(A)")  "* load symbol 'so_test'"
write (u, "(A)")

```

```

c_fptr = dlaccess_get_c_funptr (dlaccess, fname)
if (c_associated (c_fptr)) then
  write (u, "(A)") "      success"
else
  write (u, "(A)") "      failure"
end if
call c_f_procpointer (c_fptr, so_test)
write (u, "(A)") "* Execute function from 'so_test.so/dylib'"
i = 7
write (u, "(A,1x,I1)") "      input  = ", i
write (u, "(A,1x,I1)") "      result = ", so_test(i)
if (so_test(i) / i .ne. 2) then
  write (u, "(A)") "* Compiling and linking ISO C functions failed."
else
  write (u, "(A)") "* Successful."
end if
write (u, "(A)")
write (u, "(A)") "* Cleanup"
call dlaccess_final (dlaccess)
end subroutine os_interface_1

```

5.6 Interface for formatted I/O

For access to formatted printing (possibly input), we interface the C `printf` family of functions. There are two important issues here:

1. `printf` takes an arbitrary number of arguments, relying on the C stack. This is not interoperable. We interface it with C wrappers that output a single integer, real or string and restrict the allowed formats accordingly.
2. Restricting format strings is essential also for preventing format string attacks. Allowing arbitrary format string would create a real security hole in a Fortran program.
3. The string returned by `sprintf` must be allocated to the right size.

<formats.f90>≡
<File header>

`module formats`

`use, intrinsic :: iso_c_binding`

<Use kinds>

<Use strings>

`use io_units`

`use unit_tests`

`use diagnostics`

<Standard module head>

<Formats: public>

Formats: parameters

Formats: types

Formats: interfaces

contains

Formats: procedures

Formats: tests

end module formats

5.6.1 Parsing a C format string

The C format string contains characters and format conversion specifications. The latter are initiated by a % sign. If the next letter is also a %, a percent sign is printed and no conversion is done. Otherwise, a conversion is done and applied to the next argument in the argument list. First comes an optional flag (#, 0, -, +, or space), an optional field width (decimal digits starting not with zero), an optional precision (period, then another decimal digit string), a length modifier (irrelevant for us, therefore not supported), and a conversion specifier: **d** or **i** for integer; **e**, **f**, **g** (also upper case) for double-precision real, **s** for a string.

We explicitly exclude all other conversion specifiers, and we check the specifiers against the actual arguments.

A type for passing arguments

This is a polymorphic type that can hold integer, real (double), and string arguments.

```
Formats: parameters≡
  integer, parameter :: ARGTYPE_NONE = 0
  integer, parameter :: ARGTYPE_LOG = 1
  integer, parameter :: ARGTYPE_INT = 2
  integer, parameter :: ARGTYPE_REAL = 3
  integer, parameter :: ARGTYPE_STR = 4
```

The integer and real entries are actually scalars, but we avoid relying on the allocatable-scalar feature and make them one-entry arrays. The character entry is a real array which is a copy of the string.

Logical values are mapped to strings (true or false), so this type parameter value is mostly unused.

```
Formats: public≡
  public :: sprintf_arg_t

Formats: types≡
  type :: sprintf_arg_t
  private
  integer :: type = ARGTYPE_NONE
  integer(c_int), dimension(:), allocatable :: ival
```

```

    real(c_double), dimension(:), allocatable :: rval
    character(c_char), dimension(:), allocatable :: sval
end type sprintf_arg_t

```

<Formats: public>+≡

```

    public :: sprintf_arg_init

```

<Formats: interfaces>≡

```

interface sprintf_arg_init
    module procedure sprintf_arg_init_log
    module procedure sprintf_arg_init_int
    module procedure sprintf_arg_init_real
    module procedure sprintf_arg_init_str
end interface

```

<Formats: procedures>≡

```

subroutine sprintf_arg_init_log (arg, lval)
    type(sprintf_arg_t), intent(out) :: arg
    logical, intent(in) :: lval
    arg%type = ARGTYPE_STR
    if (lval) then
        allocate (arg%sval (5))
        arg%sval = ['t', 'r', 'u', 'e', c_null_char]
    else
        allocate (arg%sval (6))
        arg%sval = ['f', 'a', 'l', 's', 'e', c_null_char]
    end if
end subroutine sprintf_arg_init_log

subroutine sprintf_arg_init_int (arg, ival)
    type(sprintf_arg_t), intent(out) :: arg
    integer, intent(in) :: ival
    arg%type = ARGTYPE_INT
    allocate (arg%ival (1))
    arg%ival = ival
end subroutine sprintf_arg_init_int

subroutine sprintf_arg_init_real (arg, rval)
    type(sprintf_arg_t), intent(out) :: arg
    real(default), intent(in) :: rval
    arg%type = ARGTYPE_REAL
    allocate (arg%rval (1))
    arg%rval = rval
end subroutine sprintf_arg_init_real

subroutine sprintf_arg_init_str (arg, sval)
    type(sprintf_arg_t), intent(out) :: arg
    type(string_t), intent(in) :: sval
    integer :: i
    arg%type = ARGTYPE_STR
    allocate (arg%sval (len (sval) + 1))
    do i = 1, len (sval)
        arg%sval(i) = extract (sval, i, i)
    end do

```

```

    arg%sval(len (sval) + 1) = c_null_char
end subroutine sprintf_arg_init_str

```

(Formats: procedures)+≡

```

subroutine sprintf_arg_write (arg, unit)
  type(sprintf_arg_t), intent(in) :: arg
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  select case (arg%type)
  case (ARGTYPE_NONE)
    write (u, *) "[none]"
  case (ARGTYPE_INT)
    write (u, "(1x,A,1x)", advance = "no") "[int]"
    write (u, *) arg%ival
  case (ARGTYPE_REAL)
    write (u, "(1x,A,1x)", advance = "no") "[real]"
    write (u, *) arg%rval
  case (ARGTYPE_STR)
    write (u, "(1x,A,1x,A)", advance = "no") "[string]", ''
    write (u, *) arg%rval, ''
  end select
end subroutine sprintf_arg_write

```

Return an upper bound for the length of the printed version; in case of strings the result is exact.

(Formats: procedures)+≡

```

elemental function sprintf_arg_get_length (arg) result (length)
  integer :: length
  type(sprintf_arg_t), intent(in) :: arg
  select case (arg%type)
  case (ARGTYPE_INT)
    length = log10 (real (huge (arg%ival(1)))) + 2
  case (ARGTYPE_REAL)
    length = log10 (real (radix (arg%rval(1))) ** digits (arg%rval(1))) + 8
  case (ARGTYPE_STR)
    length = size (arg%sval)
  case default
    length = 0
  end select
end function sprintf_arg_get_length

```

(Formats: procedures)+≡

```

subroutine sprintf_arg_apply_sprintf (arg, fmt, result, actual_length)
  type(sprintf_arg_t), intent(in) :: arg
  character(c_char), dimension(:), intent(in) :: fmt
  character(c_char), dimension(:), intent(inout) :: result
  integer, intent(out) :: actual_length
  integer(c_int) :: ival
  real(c_double) :: rval
  select case (arg%type)
  case (ARGTYPE_NONE)
    actual_length = sprintf_none (result, fmt)

```

```

case (ARGTYPE_INT)
    ival = arg%ival(1)
    actual_length = sprintf_int (result, fmt, ival)
case (ARGTYPE_REAL)
    rval = arg%rval(1)
    actual_length = sprintf_double (result, fmt, rval)
case (ARGTYPE_STR)
    actual_length = sprintf_str (result, fmt, arg%sval)
case default
    call msg_bug ("sprintf_arg_apply_sprintf called with illegal type")
end select
if (actual_length < 0) then
    write (msg_buffer, *) "Format: '", fmt, "'"
    call msg_message ()
    write (msg_buffer, *) "Output: '", result, "'"
    call msg_message ()
    call msg_error ("I/O error in sprintf call")
    actual_length = 0
end if
end subroutine sprintf_arg_apply_sprintf

```

Container type for the output

There is a procedure which chops the format string into pieces that contain at most one conversion specifier. Pairing this with a `sprintf_arg` object, we get the actual input to the `sprintf` interface. The type below holds this input and can allocate the output string.

(Formats: types)+≡

```

type :: sprintf_interface_t
    private
    character(c_char), dimension(:), allocatable :: input_fmt
    type(sprintf_arg_t) :: arg
    character(c_char), dimension(:), allocatable :: output_str
    integer :: output_str_len = 0
end type sprintf_interface_t

```

(Formats: procedures)+≡

```

subroutine sprintf_interface_init (intf, fmt, arg)
    type(sprintf_interface_t), intent(out) :: intf
    type(string_t), intent(in) :: fmt
    type(sprintf_arg_t), intent(in) :: arg
    integer :: fmt_len, i
    fmt_len = len (fmt)
    allocate (intf%input_fmt (fmt_len + 1))
    do i = 1, fmt_len
        intf%input_fmt(i) = extract (fmt, i, i)
    end do
    intf%input_fmt(fmt_len+1) = c_null_char
    intf%arg = arg
    allocate (intf%output_str (len (fmt) + sprintf_arg_get_length (arg) + 1))
end subroutine sprintf_interface_init

```


<Formats: procedures>+≡

```
subroutine sprintf_interface_write (intf, unit)
  type(sprintf_interface_t), intent(in) :: intf
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, *) "Format string = ", "'", intf%input_fmt, "'"
  write (u, "(1x,A,1x)", advance = "no") "Argument = "
  call sprintf_arg_write (intf%arg, unit)
  if (intf%output_str_len > 0) then
    write (u, *) "Result string = ", &
      "'", intf%output_str (1:intf%output_str_len), "'"
  end if
end subroutine sprintf_interface_write
```

Return the output string:

<Formats: procedures>+≡

```
function sprintf_interface_get_result (intf) result (string)
  type(string_t) :: string
  type(sprintf_interface_t), intent(in) :: intf
  character(kind = c_char, len = max (intf%output_str_len, 0)) :: buffer
  integer :: i
  if (intf%output_str_len > 0) then
    do i = 1, intf%output_str_len
      buffer(i:i) = intf%output_str(i)
    end do
    string = buffer(1:intf%output_str_len)
  else
    string = ""
  end if
end function sprintf_interface_get_result
```

<Formats: procedures>+≡

```
subroutine sprintf_interface_apply_sprintf (intf)
  type(sprintf_interface_t), intent(inout) :: intf
  call sprintf_arg_apply_sprintf &
    (intf%arg, intf%input_fmt, intf%output_str, intf%output_str_len)
end subroutine sprintf_interface_apply_sprintf
```

Import the interfaces defined in the previous section:

<Formats: interfaces>+≡

<sprintf interfaces>

Scan the format string

Chop it into pieces that contain one conversion specifier each. The zero-th piece contains the part before the first specifier. Check the specifiers and allow only the subset that we support. Also check for an exact match between conversion specifiers and input arguments. The result is an allocated array of

sprintf_interface object; each one contains a piece of the format string and the corresponding argument.

(Formats: procedures)+≡

```

subroutine chop_and_check_format_string (fmt, arg, intf)
  type(string_t), intent(in) :: fmt
  type(sprintf_arg_t), dimension(:), intent(in) :: arg
  type(sprintf_interface_t), dimension(:), intent(out), allocatable :: intf
  integer :: n_args, i
  type(string_t), dimension(:), allocatable :: split_fmt
  type(string_t) :: word, buffer, separator
  integer :: pos, length, l
  logical :: ok
  type(sprintf_arg_t) :: arg_null
  ok = .true.
  length = 0
  n_args = size (arg)
  allocate (split_fmt (0:n_args))
  split_fmt = ""
  buffer = fmt
  SCAN_ARGS: do i = 1, n_args
    FIND_CONVERSION: do
      call split (buffer, word, "%", separator=separator)
      if (separator == "") then
        call msg_message (''' // char (fmt) // ''')
        call msg_error ("C-formatting string: " &
          // "too few conversion specifiers in format string")
        ok = .false.; exit SCAN_ARGS
      end if
      split_fmt(i-1) = split_fmt(i-1) // word
      if (extract (buffer, 1, 1) /= "%") then
        split_fmt(i) = "%"
        exit FIND_CONVERSION
      else
        split_fmt(i-1) = split_fmt(i-1) // "%"
      end if
    end do FIND_CONVERSION
    pos = verify (buffer, "#0-+ ") ! Flag characters (zero or more)
    split_fmt(i) = split_fmt(i) // extract (buffer, 1, pos-1)
    buffer = remove (buffer, 1, pos-1)
    pos = verify (buffer, "123456890") ! Field width
    word = extract (buffer, 1, pos-1)
    if (len (word) /= 0) then
      call read_int_from_string (word, len (word), 1)
      length = length + 1
    end if
    split_fmt(i) = split_fmt(i) // word
    buffer = remove (buffer, 1, pos-1)
    if (extract (buffer, 1, 1) == ".") then
      buffer = remove (buffer, 1, 1)
      pos = verify (buffer, "1234567890") ! Precision
      split_fmt(i) = split_fmt(i) // "." // extract (buffer, 1, pos-1)
      buffer = remove (buffer, 1, pos-1)
    end if
    ! Length modifier would come here, but is not allowed
  end do

```

```

select case (char (extract (buffer, 1, 1))) ! conversion specifier
case ("d", "i")
    if (arg(i)%type /= ARGTYPE_INT) then
        call msg_message (''' // char (fmt) // ''')
        call msg_error ("C-formatting string: " &
            // "argument type mismatch: integer value expected")
        ok = .false.; exit SCAN_ARGS
    end if
case ("e", "E", "f", "F", "g", "G")
    if (arg(i)%type /= ARGTYPE_REAL) then
        call msg_message (''' // char (fmt) // ''')
        call msg_error ("C-formatting string: " &
            // "argument type mismatch: real value expected")
        ok = .false.; exit SCAN_ARGS
    end if
case ("s")
    if (arg(i)%type /= ARGTYPE_STR) then
        call msg_message (''' // char (fmt) // ''')
        call msg_error ("C-formatting string: " &
            // "argument type mismatch: logical or string value expected")
        ok = .false.; exit SCAN_ARGS
    end if
case default
    call msg_message (''' // char (fmt) // ''')
    call msg_error ("C-formatting string: " &
        // "illegal or incomprehensible conversion specifier")
    ok = .false.; exit SCAN_ARGS
end select
split_fmt(i) = split_fmt(i) // extract (buffer, 1, 1)
buffer = remove (buffer, 1, 1)
end do SCAN_ARGS
if (ok) then
    FIND_EXTRA_CONVERSION: do
        call split (buffer, word, "%", separator=separator)
        split_fmt(n_args) = split_fmt(n_args) // word // separator
        if (separator == "") exit FIND_EXTRA_CONVERSION
        if (extract (buffer, 1, 1) == "%") then
            split_fmt(n_args) = split_fmt(n_args) // "%"
            buffer = remove (buffer, 1, 1)
        else
            call msg_message (''' // char (fmt) // ''')
            call msg_error ("C-formatting string: " &
                // "too many conversion specifiers in format string")
            ok = .false.; exit FIND_EXTRA_CONVERSION
        end if
    end do FIND_EXTRA_CONVERSION
    split_fmt(n_args) = split_fmt(n_args) // buffer
    allocate (intf (0:n_args))
    call sprintf_interface_init (intf(0), split_fmt(0), arg_null)
    do i = 1, n_args
        call sprintf_interface_init (intf(i), split_fmt(i), arg(i))
    end do
else
    allocate (intf (0))

```

```

    end if
contains
  subroutine read_int_from_string (word, length, l)
    type(string_t), intent(in) :: word
    integer, intent(in) :: length
    integer, intent(out) :: l
    character(len=length) :: buffer
    buffer = word
    read (buffer, *) l
  end subroutine read_int_from_string
end subroutine chop_and_check_format_string

```

5.6.2 API

```

<Formats: public>+≡
  public :: sprintf

<Formats: procedures>+≡
  function sprintf (fmt, arg) result (string)
    type(string_t) :: string
    type(string_t), intent(in) :: fmt
    type(sprintf_arg_t), dimension(:), intent(in) :: arg
    type(sprintf_interface_t), dimension(:), allocatable :: intf
    integer :: i
    string = ""
    call chop_and_check_format_string (fmt, arg, intf)
    if (size (intf) > 0) then
      do i = 0, ubound (intf, 1)
        call sprintf_interface_apply sprintf (intf(i))
        string = string // sprintf_interface_get_result (intf(i))
      end do
    end if
  end function sprintf

```

5.6.3 Test

```

<Formats: public>+≡
  public :: format_test

<Formats: procedures>+≡
  subroutine format_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Formats: execute tests>
  end subroutine format_test

<Formats: execute tests>≡
  call test (format_1, "format_1", &
    "check formatting routines", &
    u, results)

```

<Formats: tests>≡

```

subroutine format_1 (u)
  integer, intent(in) :: u
  write (u, "(A)")  "*** Test 1: a string ***"
  write (u, "(A)")
  call test_run (var_str("%s"), 1, [4], ['abcdefghij'], u)
  write (u, "(A)")  "*** Test 2: two integers ***"
  write (u, "(A)")
  call test_run (var_str("%d,%d"), 2, [2, 2], ['42', '13'], u)
  write (u, "(A)")  "*** Test 3: floating point number ***"
  write (u, "(A)")
  call test_run (var_str("%8.4f"), 1, [3], ['42567.12345'], u)
  write (u, "(A)")  "*** Test 4: general expression ***"
  call test_run (var_str("%g"), 1, [3], ['3.1415'], u)
contains
  subroutine test_run (fmt, n_args, type, buffer, unit)
    type(string_t), intent(in) :: fmt
    integer, intent(in) :: n_args, unit
    logical :: lval
    integer :: ival
    real(default) :: rval
    integer :: i
    type(string_t) :: string
    type(sprintf_arg_t), dimension(:), allocatable :: arg
    integer, dimension(n_args), intent(in) :: type
    character(*), dimension(n_args), intent(in) :: buffer
    write (unit, "(A,A)")  "Format string :", char(fmt)
    write (unit, "(A,I1)")  "Number of args:", n_args
    allocate (arg (n_args))
    do i = 1, n_args
      write (unit, "(A,I1)")  "Argument (type ) = ", type(i)
      select case (type(i))
      case (ARGTYPE_LOG)
        read (buffer(i), *)  lval
        call sprintf_arg_init (arg(i), lval)
      case (ARGTYPE_INT)
        read (buffer(i), *)  ival
        call sprintf_arg_init (arg(i), ival)
      case (ARGTYPE_REAL)
        read (buffer(i), *)  rval
        call sprintf_arg_init (arg(i), rval)
      case (ARGTYPE_STR)
        call sprintf_arg_init (arg(i), var_str (trim (buffer(i))))
      end select
    end do
    string = sprintf (fmt, arg)
    write (unit, "(A,A,A)")  "Result: '", char (string), "'"
    deallocate (arg)
  end subroutine test_run
end subroutine format_1

```

5.7 CPU timing

The time is stored in a simple derived type which just holds a floating-point number.

```
<cputime.f90>≡  
  <File header>
```

```
  module cputime
```

```
    <Use kinds>
```

```
    use io_units
```

```
    <Use strings>
```

```
    use unit_tests
```

```
    use diagnostics
```

```
  <Standard module head>
```

```
  <CPU time: public>
```

```
  <CPU time: types>
```

```
  <CPU time: interfaces>
```

```
  contains
```

```
  <CPU time: procedures>
```

```
  <CPU time: tests>
```

```
end module cputime
```

The CPU time is a floating-point number with an arbitrary reference time. It is single precision (default real, not `real(default)`). It is measured in seconds.

```
<CPU time: public>≡
```

```
  public :: time_t
```

```
<CPU time: types>≡
```

```
  type :: time_t
```

```
    private
```

```
    logical :: known = .false.
```

```
    real :: value = 0
```

```
    contains
```

```
    <CPU time: time: TBP>
```

```
  end type time_t
```

```
<CPU time: time: TBP>≡
```

```
  procedure :: write => time_write
```

```
<CPU time: procedures>≡
```

```
  subroutine time_write (object, unit)
```

```
    class(time_t), intent(in) :: object
```

```
    integer, intent(in), optional :: unit
```

```
    integer :: u
```

```
    u = given_output_unit (unit)
```

```
    write (u, "(1x,A)", advance="no") "Time in seconds ="
```

```

        if (object%known) then
            write (u, "(1x,ES10.3)") object%value
        else
            write (u, "(1x,A)") "[unknown]"
        end if
    end subroutine time_write

```

Set the current time

```

<CPU time: time: TBP>+≡
    procedure :: set_current => time_set_current

<CPU time: procedures>+≡
    subroutine time_set_current (time)
        class(time_t), intent(out) :: time
        integer :: msec
        call system_clock (msec)
        time%value = real (msec) / 1000.
        time%known = time%value > 0
    end subroutine time_set_current

```

Assign to a real(default value. If the time is undefined, return zero.

```

<CPU time: public>+≡
    public :: assignment(=)

<CPU time: interfaces>≡
    interface assignment(=)
        module procedure real_assign_time
        module procedure real_default_assign_time
    end interface

<CPU time: procedures>+≡
    pure subroutine real_assign_time (r, time)
        real, intent(out) :: r
        class(time_t), intent(in) :: time
        if (time%known) then
            r = time%value
        else
            r = 0
        end if
    end subroutine real_assign_time

    pure subroutine real_default_assign_time (r, time)
        real(default), intent(out) :: r
        class(time_t), intent(in) :: time
        if (time%known) then
            r = time%value
        else
            r = 0
        end if
    end subroutine real_default_assign_time

```

Assign an integer or (single precision) real value to the time object.

```

(CPU time: time: TBP)+≡
  generic :: assignment(=) => time_assign_from_integer, time_assign_from_real
  procedure, private :: time_assign_from_integer
  procedure, private :: time_assign_from_real

(CPU time: procedures)+≡
  subroutine time_assign_from_integer (time, ival)
    class(time_t), intent(out) :: time
    integer, intent(in) :: ival
    time%value = ival
    time%known = .true.
  end subroutine time_assign_from_integer

  subroutine time_assign_from_real (time, rval)
    class(time_t), intent(out) :: time
    real, intent(in) :: rval
    time%value = rval
    time%known = .true.
  end subroutine time_assign_from_real

```

Add times and compute time differences. If any input value is undefined, the result is undefined.

```

(CPU time: time: TBP)+≡
  generic :: operator(-) => subtract_times
  generic :: operator(+) => add_times
  procedure, private :: subtract_times
  procedure, private :: add_times

(CPU time: procedures)+≡
  pure function subtract_times (t_end, t_begin) result (time)
    type(time_t) :: time
    class(time_t), intent(in) :: t_end, t_begin
    if (t_end%known .and. t_begin%known) then
      time%known = .true.
      time%value = t_end%value - t_begin%value
    end if
  end function subtract_times

  pure function add_times (t1, t2) result (time)
    type(time_t) :: time
    class(time_t), intent(in) :: t1, t2
    if (t1%known .and. t2%known) then
      time%known = .true.
      time%value = t1%value + t2%value
    end if
  end function add_times

```

Check if a time is known, so we can use it:

```

(CPU time: time: TBP)+≡
  procedure :: is_known => time_is_known

```



```

<CPU time: procedures>+=
function time_is_known (time) result (flag)
    class(time_t), intent(in) :: time
    logical :: flag
    flag = time%known
end function time_is_known

```

We define functions for converting the time into ss / mm:ss / hh:mm:ss / dd:mm:hh:ss.

```

<CPU time: time: TBP>+=
generic :: expand => time_expand_s, time_expand_ms, &
    time_expand_hms, time_expand_dhms
procedure, private :: time_expand_s
procedure, private :: time_expand_ms
procedure, private :: time_expand_hms
procedure, private :: time_expand_dhms

<CPU time: procedures>+=
subroutine time_expand_s (time, sec)
    class(time_t), intent(in) :: time
    integer, intent(out) :: sec
    if (time%known) then
        sec = time%value
    else
        call msg_bug ("Time: attempt to expand undefined value")
    end if
end subroutine time_expand_s

subroutine time_expand_ms (time, min, sec)
    class(time_t), intent(in) :: time
    integer, intent(out) :: min, sec
    if (time%known) then
        if (time%value >= 0) then
            sec = mod (int (time%value), 60)
        else
            sec = - mod (int (- time%value), 60)
        end if
        min = time%value / 60
    else
        call msg_bug ("Time: attempt to expand undefined value")
    end if
end subroutine time_expand_ms

subroutine time_expand_hms (time, hour, min, sec)
    class(time_t), intent(in) :: time
    integer, intent(out) :: hour, min, sec
    call time%expand (min, sec)
    hour = min / 60
    if (min >= 0) then
        min = mod (min, 60)
    else
        min = - mod (-min, 60)
    end if
end subroutine time_expand_hms

```

```

subroutine time_expand_dhms (time, day, hour, min, sec)
  class(time_t), intent(in) :: time
  integer, intent(out) :: day, hour, min, sec
  call time%expand (hour, min, sec)
  day = hour / 24
  if (hour >= 0) then
    hour = mod (hour, 24)
  else
    hour = - mod (- hour, 24)
  end if
end subroutine time_expand_dhms

```

Use the above expansions to generate a time string.

```

<CPU time: time: TBP>+≡
  procedure :: to_string_s => time_to_string_s
  procedure :: to_string_ms => time_to_string_ms
  procedure :: to_string_hms => time_to_string_hms
  procedure :: to_string_dhms => time_to_string_dhms

```

```

<CPU time: procedures>+≡
function time_to_string_s (time) result (str)
  class(time_t), intent(in) :: time
  type(string_t) :: str
  character(256) :: buffer
  integer :: s
  call time%expand (s)
  write (buffer, "(I0,'s')") s
  str = trim (buffer)
end function time_to_string_s

function time_to_string_ms (time, blank) result (str)
  class(time_t), intent(in) :: time
  logical, intent(in), optional :: blank
  type(string_t) :: str
  character(256) :: buffer
  integer :: s, m
  logical :: x_out
  x_out = .false.
  if (present (blank)) x_out = blank
  call time%expand (m, s)
  write (buffer, "(I0,'m:',I2.2,'s')") m, abs (s)
  str = trim (buffer)
  if (x_out) then
    str = replace (str, len(str)-1, "X")
  end if
end function time_to_string_ms

function time_to_string_hms (time) result (str)
  class(time_t), intent(in) :: time
  type(string_t) :: str
  character(256) :: buffer
  integer :: s, m, h
  call time%expand (h, m, s)

```

```

        write (buffer, "(I0,'h:',I2.2,'m:',I2.2,'s')")  h, abs (m), abs (s)
        str = trim (buffer)
    end function time_to_string_hms

function time_to_string_dhms (time) result (str)
    class(time_t), intent(in) :: time
    type(string_t) :: str
    character(256) :: buffer
    integer :: s, m, h, d
    call time%expand (d, h, m, s)
    write (buffer, "(I0,'d:',I2.2,'h:',I2.2,'m:',I2.2,'s')")  &
        d, abs (h), abs (m), abs (s)
    str = trim (buffer)
end function time_to_string_dhms

```

5.7.1 Timer

A timer can measure real (wallclock) time differences. The base type corresponds to the result, i.e., time difference. The object contains two further times for start and stop time.

```

<CPU time: public>+≡
    public :: timer_t

<CPU time: types>+≡
    type, extends (time_t) :: timer_t
        private
        logical :: running = .false.
        type(time_t) :: t1, t2
    contains
        <CPU time: timer: TBP>
    end type timer_t

```

Output. If the timer is running, we indicate this, otherwise write just the result.

```

<CPU time: timer: TBP>≡
    procedure :: write => timer_write

<CPU time: procedures>+≡
    subroutine timer_write (object, unit)
        class(timer_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        if (object%running) then
            write (u, "(1x,A)")  "Time in seconds = [running]"
        else
            call object%time_t%write (u)
        end if
    end subroutine timer_write

```

Start the timer: store the current time in the first entry and adapt the status. We forget any previous values.

```

<CPU time: timer: TBP>+≡

```

```

    procedure :: start => timer_start
  <CPU time: procedures>+≡
    subroutine timer_start (timer)
      class(timer_t), intent(out) :: timer
      call timer%t1%set_current ()
      timer%running = .true.
    end subroutine timer_start

```

Restart the timer: simply adapt the status, keeping the start time.

```

  <CPU time: timer: TBP>+≡
    procedure :: restart => timer_restart
  <CPU time: procedures>+≡
    subroutine timer_restart (timer)
      class(timer_t), intent(inout) :: timer
      if (timer%t1%known .and. .not. timer%running) then
        timer%running = .true.
      else
        call msg_bug ("Timer: restart attempt from wrong status")
      end if
    end subroutine timer_restart

```

Stop the timer: store the current time in the second entry, adapt the status, and compute the elapsed time.

```

  <CPU time: timer: TBP>+≡
    procedure :: stop => timer_stop
  <CPU time: procedures>+≡
    subroutine timer_stop (timer)
      class(timer_t), intent(inout) :: timer
      call timer%t2%set_current ()
      timer%running = .false.
      call timer%evaluate ()
    end subroutine timer_stop

```

This is separate, available for the unit test.

```

  <CPU time: timer: TBP>+≡
    procedure, private :: evaluate => timer_evaluate
  <CPU time: procedures>+≡
    subroutine timer_evaluate (timer)
      class(timer_t), intent(inout) :: timer
      timer%time_t = timer%t2 - timer%t1
    end subroutine timer_evaluate

```

5.7.2 Unit tests

```

  <CPU time: public>+≡
    public :: cputime_test

```

```

<CPU time: tests>≡
  subroutine cputime_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <CPU time: execute tests>
  end subroutine cputime_test

```

Basic tests

Check basic functions of the time object. The part which we can't check is getting the actual time from the system clock, since the output will not be reproducible. However, we can check time formats and operations.

```

<CPU time: execute tests>≡
  call test (cputime_1, "cputime_1", &
    "time operations", &
    u, results)

<CPU time: tests>+≡
  subroutine cputime_1 (u)
    integer, intent(in) :: u
    type(time_t) :: time, time1, time2
    real :: t
    integer :: d, h, m, s

    write (u, "(A)")  "* Test output: cputime_1"
    write (u, "(A)")  "* Purpose: check time operations"
    write (u, "(A)")

    write (u, "(A)")  "* Undefined time"
    write (u, *)

    call time%write (u)

    write (u, *)
    write (u, "(A)")  "* Set time to zero"
    write (u, *)

    time = 0
    call time%write (u)

    write (u, *)
    write (u, "(A)")  "* Set time to 1.234 s"
    write (u, *)

    time = 1.234
    call time%write (u)

    t = time
    write (u, "(1x,A,F6.3)")  "Time as real =", t

    write (u, *)
    write (u, "(A)")  "* Compute time difference"
    write (u, *)

```

```

time1 = 5.33
time2 = 7.55
time = time2 - time1

call time1%write (u)
call time2%write (u)
call time%write (u)

write (u, *)
write (u, "(A)") "* Compute time sum"
write (u, *)

time = time2 + time1

call time1%write (u)
call time2%write (u)
call time%write (u)

write (u, *)
write (u, "(A)") "* Expand time"
write (u, *)

time1 = ((24 + 1) * 60 + 1) * 60 + 1
time2 = ((3 * 24 + 23) * 60 + 59) * 60 + 59

call time1%expand (s)
write (u, 1) "s =", s
call time1%expand (m,s)
write (u, 1) "ms =", m, s
call time1%expand (h,m,s)
write (u, 1) "hms =", h, m, s
call time1%expand (d,h,m,s)
write (u, 1) "dhms =", d, h, m, s

call time2%expand (s)
write (u, 1) "s =", s
call time2%expand (m,s)
write (u, 1) "ms =", m, s
call time2%expand (h,m,s)
write (u, 1) "hms =", h, m, s
call time2%expand (d,h,m,s)
write (u, 1) "dhms =", d, h, m, s

write (u, *)
write (u, "(A)") "* Expand negative time"
write (u, *)

time1 = - (((24 + 1) * 60 + 1) * 60 + 1)
time2 = - (((3 * 24 + 23) * 60 + 59) * 60 + 59)

call time1%expand (s)
write (u, 1) "s =", s
call time1%expand (m,s)

```

```

write (u, 1) "ms =", m, s
call time1%expand (h,m,s)
write (u, 1) "hms =", h, m, s
call time1%expand (d,h,m,s)
write (u, 1) "dhms =", d, h, m, s

call time2%expand (s)
write (u, 1) "s =", s
call time2%expand (m,s)
write (u, 1) "ms =", m, s
call time2%expand (h,m,s)
write (u, 1) "hms =", h, m, s
call time2%expand (d,h,m,s)
write (u, 1) "dhms =", d, h, m, s

1  format (1x,A,1x,4(I0,:,''))

write (u, *)
write (u, "(A)") "* String from time"
write (u, *)

time1 = ((24 + 1) * 60 + 1) * 60 + 1
time2 = ((3 * 24 + 23) * 60 + 59) * 60 + 59

write (u, "(A)") char (time1%to_string_s ())
write (u, "(A)") char (time1%to_string_ms ())
write (u, "(A)") char (time1%to_string_hms ())
write (u, "(A)") char (time1%to_string_dhms ())

write (u, "(A)") char (time2%to_string_s ())
write (u, "(A)") char (time2%to_string_ms ())
write (u, "(A)") char (time2%to_string_hms ())
write (u, "(A)") char (time2%to_string_dhms ())

write (u, "(A)")
write (u, "(A)") "* Blanking out the last second entry"
write (u, "(A)")

write (u, "(A)") char (time1%to_string_ms ())
write (u, "(A)") char (time1%to_string_ms (.true.))

write (u, *)
write (u, "(A)") "* String from negative time"
write (u, *)

time1 = -(((24 + 1) * 60 + 1) * 60 + 1)
time2 = -(((3 * 24 + 23) * 60 + 59) * 60 + 59)

write (u, "(A)") char (time1%to_string_s ())
write (u, "(A)") char (time1%to_string_ms ())
write (u, "(A)") char (time1%to_string_hms ())
write (u, "(A)") char (time1%to_string_dhms ())

write (u, "(A)") char (time2%to_string_s ())

```

```

write (u, "(A)") char (time2%to_string_ms ())
write (u, "(A)") char (time2%to_string_hms ())
write (u, "(A)") char (time2%to_string_dhms ())

write (u, "(A)")
write (u, "(A)")  "* Test output end: cputime_1"

end subroutine cputime_1

```

Timer tests

Check a timer object.

```

<CPU time: execute tests>+≡
  call test (cputime_2, "cputime_2", &
    "timer", &
    u, results)

<CPU time: tests>+≡
subroutine cputime_2 (u)
  integer, intent(in) :: u
  type(timer_t) :: timer

  write (u, "(A)")  "* Test output: cputime_2"
  write (u, "(A)")  "* Purpose: check timer"
  write (u, "(A)")

  write (u, "(A)")  "* Undefined timer"
  write (u, *)

  call timer%write (u)

  write (u, *)
  write (u, "(A)")  "* Start timer"
  write (u, *)

  call timer%start ()
  call timer%write (u)

  write (u, *)
  write (u, "(A)")  "* Stop timer (injecting fake timings)"
  write (u, *)

  call timer%stop ()
  timer%t1 = 2
  timer%t2 = 5
  call timer%evaluate ()
  call timer%write (u)

  write (u, *)
  write (u, "(A)")  "* Restart timer"
  write (u, *)

  call timer%restart ()

```



```

call timer%write (u)

write (u, *)
write (u, "(A)") "* Stop timer again (injecting fake timing)"
write (u, *)

call timer%stop ()
timer%t2 = 10
call timer%evaluate ()
call timer%write (u)

write (u, *)
write (u, "(A)") "* Test output end: cputime_2"

end subroutine cputime_2

```

Chapter 6

Combinatorics

These modules implement standard algorithms (sorting, hashing, etc.) that are not available in Fortran.

Fortran doesn't support generic programming, therefore the algorithms are implemented only for specific data types.

bytes Derived types for bytes and words.

hashes Types and tools for setting up hashtables.

md5 The MD5 algorithm for message digest.

permutations Permuting an array of integers.

sorting Sorting integer and real values.

grids d -dimensional grids can be saved to disk and used for interpolation, maximum finding, etc.

6.1 Bytes and such

In a few instances we will need the notion of a byte (8-bit) and a word (32 bit), even a 64-bit word. A block of 512 bit is also needed (for MD5).

We rely on integers up to 64 bit being supported by the processor. The main difference to standard integers is the interpretation as unsigned integers.

`<bytes.f90>` \equiv
<File header>

```
module bytes
```

```
    use kinds, only: i8, i32, i64
    use io_units
```

```
<Standard module head>
```

```
<Bytes: public>
```

```
<Bytes: types>
```

⟨Bytes: parameters⟩

⟨Bytes: interfaces⟩

contains

⟨Bytes: procedures⟩

end module bytes

6.1.1 8-bit words: bytes

This is essentially a wrapper around 8-bit integers. The wrapper emphasises their special interpretation as a sequence of bits. However, we interpret bytes as unsigned integers.

⟨Bytes: public⟩≡

public :: byte_t

⟨Bytes: types⟩≡

type :: byte_t

private

integer(i8) :: i

end type byte_t

⟨Bytes: public⟩+≡

public :: byte_zero

⟨Bytes: parameters⟩≡

type(byte_t), parameter :: byte_zero = byte_t (0_i8)

Set a byte from 8-bit integer:

⟨Bytes: public⟩+≡

public :: assignment(=)

⟨Bytes: interfaces⟩≡

interface assignment(=)

module procedure set_byte_from_i8

end interface

⟨Bytes: procedures⟩≡

subroutine set_byte_from_i8 (b, i)

type(byte_t), intent(out) :: b

integer(i8), intent(in) :: i

b%i = i

end subroutine set_byte_from_i8

Write a byte in one of two formats: either as a hexadecimal number (two digits, default) or as a decimal number (one to three digits). The decimal version is nontrivial because bytes are unsigned integers. Optionally append a newline.

⟨Bytes: public⟩+≡

public :: byte_write

```

<Bytes: interfaces>+≡
    interface byte_write
        module procedure byte_write_unit, byte_write_string
    end interface

<Bytes: procedures>+≡
    subroutine byte_write_unit (b, unit, decimal, newline)
        type(byte_t), intent(in), optional :: b
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: decimal, newline
        logical :: dc, nl
        type(word32_t) :: w
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        dc = .false.; if (present (decimal)) dc = decimal
        nl = .false.; if (present (newline)) nl = newline
        if (dc) then
            w = b
            write (u, '(I3)', advance='no') w%i
        else
            write (u, '(z2.2)', advance='no') b%i
        end if
        if (nl) write (u, *)
    end subroutine byte_write_unit

```

The string version is hex-only

```

<Bytes: procedures>+≡
    subroutine byte_write_string (b, s)
        type(byte_t), intent(in) :: b
        character(len=2), intent(inout) :: s
        write (s, '(z2.2)') b%i
    end subroutine byte_write_string

```

6.1.2 32-bit words

This is not exactly a 32-bit integer. A word is to be filled with bytes, and it may be partially filled. The filling is done lowest-byte first, highest-byte last. We count the bits, so fill should be either 0, 8, 16, 24, or 32. In printing words, we correspondingly distinguish between printing zeros and printing blanks.

```

<Bytes: public>+≡
    public :: word32_t

<Bytes: types>+≡
    type :: word32_t
        private
        integer(i32) :: i
        integer :: fill = 0
    end type word32_t

```

Assignment: the word is filled by inserting a 32-bit integer

```

<Bytes: interfaces>+≡
    interface assignment(=)

```

```

        module procedure word32_set_from_i32
        module procedure word32_set_from_byte
    end interface
    <Bytes: procedures>+≡
    subroutine word32_set_from_i32 (w, i)
        type(word32_t), intent(out) :: w
        integer(i32), intent(in) :: i
        w%i = i
        w%fill = 32
    end subroutine word32_set_from_i32

```

Reverse assignment to a 32-bit integer. We do not check the fill status.

```

    <Bytes: interfaces>+≡
    interface assignment(=)
        module procedure i32_from_word32
    end interface
    <Bytes: procedures>+≡
    subroutine i32_from_word32 (i, w)
        integer(i32), intent(out) :: i
        type(word32_t), intent(in) :: w
        i = w%i
    end subroutine i32_from_word32

```

Filling with a 8-bit integer is slightly tricky, because in this interpretation integers are unsigned.

```

    <Bytes: procedures>+≡
    subroutine word32_set_from_byte (w, b)
        type(word32_t), intent(out) :: w
        type(byte_t), intent(in) :: b
        if (b%i >= 0_i8) then
            w%i = b%i
        else
            w%i = 2_i32*(huge(0_i8)+1_i32) + b%i
        end if
        w%fill = 32
    end subroutine word32_set_from_byte

```

Check the fill status

```

    <Bytes: public>+≡
    public :: word32_empty, word32_filled, word32_fill
    <Bytes: procedures>+≡
    function word32_empty (w)
        type(word32_t), intent(in) :: w
        logical :: word32_empty
        word32_empty = (w%fill == 0)
    end function word32_empty

    function word32_filled (w)
        type(word32_t), intent(in) :: w
        logical :: word32_filled
        word32_filled = (w%fill == 32)
    end function word32_filled

```

```

end function word32_filled

function word32_fill (w)
    type(word32_t), intent(in) :: w
    integer :: word32_fill
    word32_fill = w%fill
end function word32_fill

```

Partial assignment: append a byte to a partially filled word. (Note: no assignment if the word is filled, so check this before if necessary.)

```

<Bytes: public>+≡
    public :: word32_append_byte

<Bytes: procedures>+≡
    subroutine word32_append_byte (w, b)
        type(word32_t), intent(inout) :: w
        type(byte_t), intent(in) :: b
        type(word32_t) :: w1
        if (.not. word32_filled (w)) then
            w1 = b
            call mvbits (w1%i, 0, 8, w%i, w%fill)
            w%fill = w%fill + 8
        end if
    end subroutine word32_append_byte

```

Extract a byte from a word. The argument *i* is the position, which may be 0, 1, 2, or 3.

For the final assignment, we set the highest bit separately. Otherwise, we might trigger an overflow condition for a compiler with strict checking turned on.

```

<Bytes: public>+≡
    public :: byte_from_word32

<Bytes: procedures>+≡
    function byte_from_word32 (w, i) result (b)
        type(word32_t), intent(in) :: w
        integer, intent(in) :: i
        type(byte_t) :: b
        integer(i32) :: j
        j = 0
        if (i >= 0 .and. i*8 < w%fill) then
            call mvbits (w%i, i*8, 8, j, 0)
        end if
        b%i = int (ibclr (j, 7), kind=i8)
        if (btest (j, 7)) b%i = ibset (b%i, 7)
    end function byte_from_word32

```

Write a word to file or STDOUT. We understand words as unsigned integers, therefore we cannot use the built-in routine unchanged. However, we can make use of the existence of 64-bit integers and their output routine.

In hexadecimal format, the default version prints eight hex characters, highest-first. The `bytes` version prints four bytes (two-hex characters), lowest first, with

spaces in-between. The decimal bytes version is analogous. In the `bytes` version, missing bytes are printed as whitespace.

```

<Bytes: public>+≡
    public :: word32_write

<Bytes: interfaces>+≡
    interface word32_write
        module procedure word32_write_unit
    end interface

<Bytes: procedures>+≡
    subroutine word32_write_unit (w, unit, bytes, decimal, newline)
        type(word32_t), intent(in) :: w
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: bytes, decimal, newline
        logical :: dc, by, nl
        type(word64_t) :: ww
        integer :: i, u
        u = given_output_unit (unit); if (u < 0) return
        by = .false.; if (present (bytes)) by = bytes
        dc = .false.; if (present (decimal)) dc = decimal
        nl = .false.; if (present (newline)) nl = newline
        if (by) then
            do i = 0, 3
                if (i>0) write (u, '(1x)', advance='no')
                if (8*i < w%fill) then
                    call byte_write (byte_from_word32 (w, i), unit, decimal=decimal)
                else if (dc) then
                    write (u, '(3x)', advance='no')
                else
                    write (u, '(2x)', advance='no')
                end if
            end do
        else if (dc) then
            ww = w
            write (u, '(I10)', advance='no') ww%i
        else
            select case (w%fill)
            case ( 0)
            case ( 8); write (6, '(1x,z8.2)', advance='no') ibits (w%i, 0, 8)
            case (16); write (6, '(1x,z8.4)', advance='no') ibits (w%i, 0,16)
            case (24); write (6, '(1x,z8.6)', advance='no') ibits (w%i, 0,24)
            case (32); write (6, '(1x,z8.8)', advance='no') ibits (w%i, 0,32)
            end select
        end if
        if (nl) write (u, *)
    end subroutine word32_write_unit

```

6.1.3 Operations on 32-bit words

Define the usual logical operations, as well as addition (mod 2^{32}). We assume that all operands are completely filled.

```

<Bytes: public>+≡

```

```

    public :: not, ior, ieor, iand, ishft, ishftc
<Bytes: interfaces>+≡
    interface not
        module procedure word_not
    end interface
    interface ior
        module procedure word_or
    end interface
    interface ieor
        module procedure word_eor
    end interface
    interface iand
        module procedure word_and
    end interface
    interface ishft
        module procedure word_shft
    end interface
    interface ishftc
        module procedure word_shftc
    end interface
<Bytes: procedures>+≡
    function word_not (w1) result (w2)
        type(word32_t), intent(in) :: w1
        type(word32_t) :: w2
        w2 = not (w1%i)
    end function word_not

    function word_or (w1, w2) result (w3)
        type(word32_t), intent(in) :: w1, w2
        type(word32_t) :: w3
        w3 = ior (w1%i, w2%i)
    end function word_or

    function word_eor (w1, w2) result (w3)
        type(word32_t), intent(in) :: w1, w2
        type(word32_t) :: w3
        w3 = ieor (w1%i, w2%i)
    end function word_eor

    function word_and (w1, w2) result (w3)
        type(word32_t), intent(in) :: w1, w2
        type(word32_t) :: w3
        w3 = iand (w1%i, w2%i)
    end function word_and

    function word_shft (w1, s) result (w2)
        type(word32_t), intent(in) :: w1
        integer, intent(in) :: s
        type(word32_t) :: w2
        w2 = ishft (w1%i, s)
    end function word_shft

    function word_shftc (w1, s) result (w2)

```



```

    type(word32_t), intent(in) :: w1
    integer, intent(in) :: s
    type(word32_t) :: w2
    w2 = ishftc (w1%i, s, 32)
end function word_shftc

```

Addition is defined mod 2^{32} , i.e., without overflow checking. This means that we have to work around a possible overflow check enforced by the compiler.

```

<Bytes: public>+≡
    public :: operator(+)

<Bytes: interfaces>+≡
    interface operator(+)
        module procedure word_add
        module procedure word_add_i8
        module procedure word_add_i32
    end interface

<Bytes: procedures>+≡
    function word_add (w1, w2) result (w3)
        type(word32_t), intent(in) :: w1, w2
        type(word32_t) :: w3
        integer(i64) :: j
        j = int (ibclr (w1%i, 31), i64) + int (ibclr (w2%i, 31), i64)
        w3 = int (ibclr (j, 31), kind=i32)
        if (btest (j, 31)) then
            if (btest (w1%i, 31) .eqv. btest (w2%i, 31)) w3 = ibset (w3%i, 31)
        else
            if (btest (w1%i, 31) .neqv. btest (w2%i, 31)) w3 = ibset (w3%i, 31)
        end if
    end function word_add

    function word_add_i8 (w1, i) result (w3)
        type(word32_t), intent(in) :: w1
        integer(i8), intent(in) :: i
        type(word32_t) :: w3
        integer(i64) :: j
        j = int (ibclr (w1%i, 31), i64) + int (ibclr (i, 7), i64)
        if (btest (i, 7)) j = j + 128
        w3 = int (ibclr (j, 31), kind=i32)
        if (btest (j, 31) .neqv. btest (w1%i, 31)) w3 = ibset (w3%i, 31)
    end function word_add_i8

    function word_add_i32 (w1, i) result (w3)
        type(word32_t), intent(in) :: w1
        integer(i32), intent(in) :: i
        type(word32_t) :: w3
        integer(i64) :: j
        j = int (ibclr (w1%i, 31), i64) + int (ibclr (i, 31), i64)
        w3 = int (ibclr (j, 31), kind=i32)
        if (btest (j, 31)) then
            if (btest (w1%i, 31) .eqv. btest (i, 31)) w3 = ibset (w3%i, 31)
        else
            if (btest (w1%i, 31) .neqv. btest (i, 31)) w3 = ibset (w3%i, 31)
        end if
    end function word_add_i32

```

```

        end if
    end function word_add_i32

```

6.1.4 64-bit words

These objects consist of two 32-bit words. They thus can hold integer numbers larger than 2^{32} (to be exact, 2^{31} since FORTRAN integers are signed). The order is low-word, high-word.

```

<Bytes: public>+≡
    public :: word64_t

<Bytes: types>+≡
    type :: word64_t
        private
        integer(i64) :: i
    end type word64_t

```

Set a 64 bit word:

```

<Bytes: interfaces>+≡
    interface assignment(=)
        module procedure word64_set_from_i64
        module procedure word64_set_from_word32
    end interface

<Bytes: procedures>+≡
    subroutine word64_set_from_i64 (ww, i)
        type(word64_t), intent(out) :: ww
        integer(i64), intent(in) :: i
        ww%i = i
    end subroutine word64_set_from_i64

```

Filling with a 32-bit word:

```

<Bytes: procedures>+≡
    subroutine word64_set_from_word32 (ww, w)
        type(word64_t), intent(out) :: ww
        type(word32_t), intent(in) :: w
        if (w%i >= 0_i32) then
            ww%i = w%i
        else
            ww%i = 2_i64*(huge(0_i32)+1_i64) + w%i
        end if
    end subroutine word64_set_from_word32

```

Extract a byte from a word. The argument *i* is the position, which may be between 0 and 7.

For the final assignment, we set the highest bit separately. Otherwise, we might trigger an overflow condition for a compiler with strict checking turned on.

```

<Bytes: public>+≡
    public :: byte_from_word64, word32_from_word64

```

```

<Bytes: procedures>+≡
function byte_from_word64 (ww, i) result (b)
  type(word64_t), intent(in) :: ww
  integer, intent(in) :: i
  type(byte_t) :: b
  integer(i64) :: j
  j = 0
  if (i >= 0 .and. i*8 < 64) then
    call mvbits (ww%i, i*8, 8, j, 0)
  end if
  b%i = int (ibclr (j, 7), kind=i8)
  if (btest (j, 7)) b%i = ibset (b%i, 7)
end function byte_from_word64

```

Extract a 32-bit word from a 64-bit word. The position is either 0 or 1.

```

<Bytes: procedures>+≡
function word32_from_word64 (ww, i) result (w)
  type(word64_t), intent(in) :: ww
  integer, intent(in) :: i
  type(word32_t) :: w
  integer(i64) :: j
  j = 0
  select case (i)
    case (0); call mvbits (ww%i, 0, 32, j, 0)
    case (1); call mvbits (ww%i, 32, 32, j, 0)
  end select
  w = int (ibclr (j, 31), kind=i32)
  if (btest (j, 31)) w = ibset (w%i, 31)
end function word32_from_word64

```

Print a 64-bit word. Decimal version works up to 2^{63} . The `words` version uses the 'word32' printout, separated by two spaces. The low-word is printed first. The `bytes` version also uses the 'word32' printout. This implies that the lowest byte is first. The default version prints a hexadecimal number without spaces, highest byte first.

```

<Bytes: public>+≡
public :: word64_write

<Bytes: interfaces>+≡
interface word64_write
  module procedure word64_write_unit
end interface

<Bytes: procedures>+≡
subroutine word64_write_unit (ww, unit, words, bytes, decimal, newline)
  type(word64_t), intent(in) :: ww
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: words, bytes, decimal, newline
  logical :: wo, by, dc, nl
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  wo = .false.; if (present (words)) wo = words
  by = .false.; if (present (bytes)) by = bytes
  dc = .false.; if (present (decimal)) dc = decimal

```

```

nl = .false.; if (present (newline)) nl = newline
if (wo .or. by) then
  call word32_write_unit (word32_from_word64 (ww, 0), unit, by, dc)
  write (u, '(2x)', advance='no')
  call word32_write_unit (word32_from_word64 (ww, 1), unit, by, dc)
else if (dc) then
  write (u, '(I19)', advance='no') ww%i
else
  write (u, '(Z16)', advance='no') ww%i
end if
if (nl) write (u, *)
end subroutine word64_write_unit

```

6.2 Hashtables

Hash tables, like lists, are not part of Fortran and must be defined on a per-case basis. In this section we define a module that contains a hash function.

Furthermore, for reference there is a complete framework of hashtable type definitions and access functions. This code is to be replicated where hash tables are used, mutatis mutandis.

```

<hashes.f90>≡
  <File header>

  module hashes

    use kinds, only: i8, i32
    use bytes

    <Standard module head>

    <Hashes: public>

    contains

    <Hashes: procedures>

  end module hashes

```

6.2.1 The hash function

This is the one-at-a-time hash function by Bob Jenkins (from Wikipedia), re-implemented in Fortran. The function works on an array of bytes (8-bit integers), as could be produced by, e.g., the `transfer` function, and returns a single 32-bit integer. For determining the position in a hashtable, one can pick the lower bits of the result as appropriate to the hashtable size (which should be a power of 2). Note that we are working on signed integers, so the interpretation of values differs from the C version. This should not matter in practice, however.

```

<Hashes: public>≡
  public :: hash

```

```

<Hashes: procedures>≡
function hash (key) result (hashval)
    integer(i32) :: hashval
    integer(i8), dimension(:), intent(in) :: key
    type(word32_t) :: w
    integer :: i
    w = 0_i32
    do i = 1, size (key)
        w = w + key(i)
        w = w + ishft (w, 10)
        w = ieor (w, ishft (w, -6))
    end do
    w = w + ishft (w, 3)
    w = ieor (w, ishft (w, -11))
    w = w + ishft (w, 15)
    hashval = w
end function hash

```

6.2.2 The hash table

We define a generic hashtable type (that depends on the `hash_data_t` type) together with associated methods.

This is a template:

```

<Hashtables: types>≡
type :: hash_data_t
    integer :: i
end type hash_data_t

```

Associated methods:

```

<Hashtables: procedures>≡
subroutine hash_data_final (data)
    type(hash_data_t), intent(inout) :: data
end subroutine hash_data_final

subroutine hash_data_write (data, unit)
    type(hash_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, *) data%i
end subroutine hash_data_write

```

Each hash entry stores the unmasked hash value, the key, and points to actual data if present. Note that this could be an allocatable scalar in principle, but making it a pointer avoids deep copy when expanding the hashtable.

```

<Hashtables: types>+≡
type :: hash_entry_t
    integer(i32) :: hashval = 0
    integer(i8), dimension(:), allocatable :: key
    type(hash_data_t), pointer :: data => null ()
end type hash_entry_t

```

The hashtable object holds the actual table, the number of filled entries and the number of entries after which the size should be doubled. The mask is equal to the table size minus one and thus coincides with the upper bound of the table index, which starts at zero.

```

<Hashtables: types>+≡
type :: hashtable_t
  integer :: n_entries = 0
  real :: fill_ratio = 0
  integer :: n_entries_max = 0
  integer(i32) :: mask = 0
  type(hash_entry_t), dimension(:), allocatable :: entry
end type hashtable_t

```

Initializer: The size has to be a power of two, the fill ratio is a real (machine-default!) number between 0 and 1.

```

<Hashtables: procedures>+≡
subroutine hashtable_init (hashtable, size, fill_ratio)
  type(hashtable_t), intent(out) :: hashtable
  integer, intent(in) :: size
  real, intent(in) :: fill_ratio
  hashtable%fill_ratio = fill_ratio
  hashtable%n_entries_max = size * fill_ratio
  hashtable%mask = size - 1
  allocate (hashtable%entry (0:hashtable%mask))
end subroutine hashtable_init

```

Finalizer: This calls a `hash_data_final` subroutine which must exist.

```

<Hashtables: procedures>+≡
subroutine hashtable_final (hashtable)
  type(hashtable_t), intent(inout) :: hashtable
  integer :: i
  do i = 0, hashtable%mask
    if (associated (hashtable%entry(i)%data)) then
      call hash_data_final (hashtable%entry(i)%data)
      deallocate (hashtable%entry(i)%data)
    end if
  end do
  deallocate (hashtable%entry)
end subroutine hashtable_final

```

Output. Here, we refer to a `hash_data_write` subroutine.

```

<Hashtables: procedures>+≡
subroutine hashtable_write (hashtable, unit)
  type(hashtable_t), intent(in) :: hashtable
  integer, intent(in), optional :: unit
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  do i = 0, hashtable%mask
    if (associated (hashtable%entry(i)%data)) then
      write (u, *) i, "(hash =", hashtable%entry(i)%hashval, ")", &

```

```

        hashtable%entry(i)%key
        call hash_data_write (hashtable%entry(i)%data, unit)
    end if
end do
end subroutine hashtable_write

```

6.2.3 Hashtable insertion

Insert a single entry with the hash value as trial place. If the table is filled, first expand it.

```

(Hashtables: procedures) +=
subroutine hashtable_insert (hashtable, key, data)
    type(hashtable_t), intent(inout) :: hashtable
    integer(i8), dimension(:), intent(in) :: key
    type(hash_data_t), intent(in), target :: data
    integer(i32) :: h
    if (hashtable%n_entries >= hashtable%n_entries_max) &
        call hashtable_expand (hashtable)
    h = hash (key)
    call hashtable_insert_rec (hashtable, h, h, key, data)
end subroutine hashtable_insert

```

We need this auxiliary routine for doubling the size of the hashtable. We rely on the fact that default assignment copies the data pointer, not the data themselves. The temporary array must not be finalized; it is deallocated automatically together with its allocatable components.

```

(Hashtables: procedures) +=
subroutine hashtable_expand (hashtable)
    type(hashtable_t), intent(inout) :: hashtable
    type(hash_entry_t), dimension(:), allocatable :: table_tmp
    integer :: i, s
    allocate (table_tmp (0:hashtable%mask))
    table_tmp = hashtable%entry
    deallocate (hashtable%entry)
    s = 2 * size (table_tmp)
    hashtable%n_entries = 0
    hashtable%n_entries_max = s * hashtable%fill_ratio
    hashtable%mask = s - 1
    allocate (hashtable%entry (0:hashtable%mask))
    do i = 0, ubound (table_tmp, 1)
        if (associated (table_tmp(i)%data)) then
            call hashtable_insert_rec (hashtable, table_tmp(i)%hashval, &
                table_tmp(i)%hashval, table_tmp(i)%key, table_tmp(i)%data)
        end if
    end do
end subroutine hashtable_expand

```

Insert a single entry at a trial place `h`, reduced to the table size. Collision resolution is done simply by choosing the next element, recursively until the place is empty. For bookkeeping, we preserve the original hash value. For a good hash function, there should be no clustering.

Note that if the new key exactly matches an existing key, nothing is done.

```

<Hashtables: procedures>+=
recursive subroutine hashtable_insert_rec (hashtable, h, hashval, key, data)
  type(hashtable_t), intent(inout) :: hashtable
  integer(i32), intent(in) :: h, hashval
  integer(i8), dimension(:), intent(in) :: key
  type(hash_data_t), intent(in), target :: data
  integer(i32) :: i
  i = iand (h, hashtable%mask)
  if (associated (hashtable%entry(i)%data)) then
    if (size (hashtable%entry(i)%key) /= size (key)) then
      call hashtable_insert_rec (hashtable, h + 1, hashval, key, data)
    else if (any (hashtable%entry(i)%key /= key)) then
      call hashtable_insert_rec (hashtable, h + 1, hashval, key, data)
    end if
  else
    hashtable%entry(i)%hashval = hashval
    allocate (hashtable%entry(i)%key (size (key)))
    hashtable%entry(i)%key = key
    hashtable%entry(i)%data => data
    hashtable%n_entries = hashtable%n_entries + 1
  end if
end subroutine hashtable_insert_rec

```

6.2.4 Hashtable lookup

The lookup function has to parallel the insert function. If the place is filled, check if the key matches. Yes: return the pointer; no: increment the hash value and check again.

```

<Hashtables: procedures>+=
function hashtable_lookup (hashtable, key) result (ptr)
  type(hash_data_t), pointer :: ptr
  type(hashtable_t), intent(in) :: hashtable
  integer(i8), dimension(:), intent(in) :: key
  ptr => hashtable_lookup_rec (hashtable, hash (key), key)
end function hashtable_lookup

<Hashtables: procedures>+=
recursive function hashtable_lookup_rec (hashtable, h, key) result (ptr)
  type(hash_data_t), pointer :: ptr
  type(hashtable_t), intent(in) :: hashtable
  integer(i32), intent(in) :: h
  integer(i8), dimension(:), intent(in) :: key
  integer(i32) :: i
  i = iand (h, hashtable%mask)
  if (associated (hashtable%entry(i)%data)) then
    if (size (hashtable%entry(i)%key) == size (key)) then
      if (all (hashtable%entry(i)%key == key)) then
        ptr => hashtable%entry(i)%data
      else
        ptr => hashtable_lookup_rec (hashtable, h + 1, key)
      end if
    end if
  end if
end function hashtable_lookup_rec

```



```

        else
            ptr => hashtable_lookup_rec (hashtable, h + 1, key)
        end if
    else
        ptr => null ()
    end if
end function hashtable_lookup_rec

```

<Hashtables: public>≡

```

    public :: hashtable_test

```

<Hashtables: procedures>+≡

```

subroutine hashtable_test ()
    type(hash_data_t), pointer :: data
    type(hashtable_t) :: hashtable
    integer(i8) :: i
    call hashtable_init (hashtable, 16, 0.25)
    do i = 1, 10
        allocate (data)
        data%i = i*i
        call hashtable_insert (hashtable, [i, i+i], data)
    end do
    call hashtable_insert (hashtable, [2_i8, 4_i8], data)
    call hashtable_write (hashtable)
    data => hashtable_lookup (hashtable, [5_i8, 10_i8])
    if (associated (data)) then
        print *, "lookup:", data%i
    else
        print *, "lookup: --"
    end if
    data => hashtable_lookup (hashtable, [6_i8, 12_i8])
    if (associated (data)) then
        print *, "lookup:", data%i
    else
        print *, "lookup: --"
    end if
    data => hashtable_lookup (hashtable, [4_i8, 9_i8])
    if (associated (data)) then
        print *, "lookup:", data%i
    else
        print *, "lookup: --"
    end if
    call hashtable_final (hashtable)
end subroutine hashtable_test

```

6.3 MD5 Checksums

Implementing MD5 checksums allows us to check input/file integrity on the basis of a well-known standard. The building blocks have been introduced in the `bytes` module.

<md5.f90>≡

⟨File header⟩

```
module md5

  use kinds, only: i8, i32, i64
  use io_units
  use unit_tests
  use system_defs, only: BUFFER_SIZE
  use system_defs, only: LF, EOR, EOF
  use diagnostics
  use bytes
```

⟨Standard module head⟩

⟨MD5: public⟩

⟨MD5: types⟩

⟨MD5: variables⟩

⟨MD5: interfaces⟩

contains

⟨MD5: procedures⟩

⟨MD5: tests⟩

```
end module md5
```

6.3.1 Blocks

A block is a sequence of 16 words (64 bytes or 512 bits). We anticipate that blocks will be linked, so include a pointer to the next block. There is a fill status (word counter), as there is one for each word. The fill status is equal to the number of bytes that are in, so it may be between 0 and 64.

```
⟨MD5: types⟩≡
  type :: block_t
  private
    type(word32_t), dimension(0:15) :: w
    type(block_t), pointer :: next => null ()
    integer :: fill = 0
  end type block_t
```

Check if a block is completely filled or empty:

```
⟨MD5: procedures⟩≡
  function block_is_empty (b)
    type(block_t), intent(in) :: b
    logical :: block_is_empty
    block_is_empty = (b%fill == 0 .and. word32_empty (b%w(0)))
  end function block_is_empty

  function block_is_filled (b)
```

```

    type(block_t), intent(in) :: b
    logical :: block_is_filled
    block_is_filled = (b%fill == 64)
end function block_is_filled

```

Append a single byte to a block. Works only if the block is not yet filled.

(MD5: procedures)+≡

```

subroutine block_append_byte (bl, by)
    type(block_t), intent(inout) :: bl
    type(byte_t), intent(in) :: by
    if (.not. block_is_filled (bl)) then
        call word32_append_byte (bl%w(bl%fill/4), by)
        bl%fill = bl%fill + 1
    end if
end subroutine block_append_byte

```

The printing routine allows for printing as sequences of words or bytes, decimal or hex.

(MD5: interfaces)≡

```

interface block_write
    module procedure block_write_unit
end interface

```

(MD5: procedures)+≡

```

subroutine block_write_unit (b, unit, bytes, decimal)
    type(block_t), intent(in) :: b
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: bytes, decimal
    logical :: by, dc
    integer :: i, u
    u = given_output_unit (unit); if (u < 0) return
    by = .false.; if (present (bytes)) by = bytes
    dc = .false.; if (present (decimal)) dc = decimal
    do i = 0, b%fill/4 - 1
        call newline_or_blank (u, i, by, dc)
        call word32_write (b%w(i), unit, bytes, decimal)
    end do
    if (.not. block_is_filled (b)) then
        i = b%fill/4
        if (.not. word32_empty (b%w(i))) then
            call newline_or_blank (u, i, by, dc)
            call word32_write (b%w(i), unit, bytes, decimal)
        end if
    end if
    write (u, *)
contains
    subroutine newline_or_blank (u, i, bytes, decimal)
        integer, intent(in) :: u, i
        logical, intent(in) :: bytes, decimal
        if (decimal) then
            select case (i)
            case (0)
            case (2,4,6,8,10,12,14); write (u, *)

```

```

        case default
            write (u, '(2x)', advance='no')
        end select
    else if (bytes) then
        select case (i)
            case (0)
            case (4,8,12); write (u, *)
            case default
                write (u, '(2x)', advance='no')
            end select
        else
            if (i == 8) write (u, *)
        end if
    end subroutine newline_or_blank
end subroutine block_write_unit

```

6.3.2 Messages

A message (within this module) is a linked list of blocks.

(MD5: types)+≡

```

type :: message_t
private
type(block_t), pointer :: first => null ()
type(block_t), pointer :: last => null ()
integer :: n_blocks = 0
end type message_t

```

Clear the message list

(MD5: procedures)+≡

```

subroutine message_clear (m)
type(message_t), intent(inout) :: m
type(block_t), pointer :: b
nullify (m%last)
do
    b => m%first
    if (.not.(associated (b))) exit
    m%first => b%next
    deallocate (b)
end do
m%n_blocks = 0
end subroutine message_clear

```

Append an empty block to the message list

(MD5: procedures)+≡

```

subroutine message_append_new_block (m)
type(message_t), intent(inout) :: m
if (associated (m%last)) then
    allocate (m%last%next)
    m%last => m%last%next
    m%n_blocks = m%n_blocks + 1
else

```

```

        allocate (m%first)
        m%last => m%first
        m%n_blocks = 1
    end if
end subroutine message_append_new_block

```

Initialize: clear and allocate the first (empty) block.

```

<MD5: procedures>+≡
subroutine message_init (m)
    type(message_t), intent(inout) :: m
    call message_clear (m)
    call message_append_new_block (m)
end subroutine message_init

```

Append a single byte to a message. If necessary, allocate a new block. If the message is empty, initialize it.

```

<MD5: procedures>+≡
subroutine message_append_byte (m, b)
    type(message_t), intent(inout) :: m
    type(byte_t), intent(in) :: b
    if (.not. associated (m%last)) then
        call message_init (m)
    else if (block_is_filled (m%last)) then
        call message_append_new_block (m)
    end if
    call block_append_byte (m%last, b)
end subroutine message_append_byte

```

Append zero bytes until the current block is filled up to the required position. If we are already beyond that, append a new block and fill that one.

```

<MD5: procedures>+≡
subroutine message_pad_zero (m, i)
    type(message_t), intent(inout) :: m
    integer, intent(in) :: i
    type(block_t), pointer :: b
    integer :: j
    if (associated (m%last)) then
        b => m%last
        if (b%fill > i) then
            do j = b%fill + 1, 64 + i
                call message_append_byte (m, byte_zero)
            end do
        else
            do j = b%fill + 1, i
                call message_append_byte (m, byte_zero)
            end do
        end if
    end if
end subroutine message_pad_zero

```

This returns the number of bits within a message. We need a 64-bit word for the result since it may be more than 2^{31} . This is also required by the MD5

standard.

(MD5: procedures)+≡

```
function message_bits (m) result (length)
  type(message_t), intent(in) :: m
  type(word64_t) :: length
  type(block_t), pointer :: b
  integer(i64) :: n_blocks_filled, n_bytes_extra
  if (m%n_blocks > 0) then
    b => m%last
    if (block_is_filled (b)) then
      n_blocks_filled = m%n_blocks
      n_bytes_extra = 0
    else
      n_blocks_filled = m%n_blocks - 1
      n_bytes_extra = b%fill
    end if
    length = n_blocks_filled * 512 + n_bytes_extra * 8
  else
    length = 0_i64
  end if
end function message_bits
```

6.3.3 Message I/O

Append the contents of a string to a message. We first cast the character string into a 8-bit integer array and then append this byte by byte.

(MD5: procedures)+≡

```
subroutine message_append_string (m, s)
  type(message_t), intent(inout) :: m
  character(len=*), intent(in) :: s
  integer(i64) :: i, n_bytes
  integer(i8), dimension(:), allocatable :: buffer
  integer(i8), dimension(1) :: mold
  type(byte_t) :: b
  n_bytes = size (transfer (s, mold))
  allocate (buffer (n_bytes))
  buffer = transfer (s, mold)
  do i = 1, size (buffer)
    b = buffer(i)
    call message_append_byte (m, b)
  end do
  deallocate (buffer)
end subroutine message_append_string
```

Append the contents of a 32-bit integer to a message. We first cast the 32-bit integer into a 8-bit integer array and then append this byte by byte.

(MD5: procedures)+≡

```
subroutine message_append_i32 (m, x)
  type(message_t), intent(inout) :: m
  integer(i32), intent(in) :: x
  integer(i8), dimension(4) :: buffer
```

```

type(byte_t) :: b
integer :: i
buffer = transfer (x, buffer, size(buffer))
do i = 1, size (buffer)
    b = buffer(i)
    call message_append_byte (m, b)
end do
end subroutine message_append_i32

```

Append one line from file to a message. Include the newline character.

<MD5: procedures>+≡

```

subroutine message_append_from_unit (m, u, iostat)
    type(message_t), intent(inout) :: m
    integer, intent(in) :: u
    integer, intent(out) :: iostat
    character(len=BUFFER_SIZE) :: buffer
    read (u, *, iostat=iostat) buffer
    call message_append_string (m, trim (buffer))
    call message_append_string (m, LF)
end subroutine message_append_from_unit

```

Fill a message from file. (Each line counts as a string.)

<MD5: procedures>+≡

```

subroutine message_read_from_file (m, f)
    type(message_t), intent(inout) :: m
    character(len=*), intent(in) :: f
    integer :: u, iostat
    u = free_unit ()
    open (file=f, unit=u, action='read')
    do
        call message_append_from_unit (m, u, iostat=iostat)
        if (iostat < 0) exit
    end do
    close (u)
end subroutine message_read_from_file

```

Write a message. After each block, insert an empty line.

<MD5: interfaces>+≡

```

interface message_write
    module procedure message_write_unit
end interface

```

<MD5: procedures>+≡

```

subroutine message_write_unit (m, unit, bytes, decimal)
    type(message_t), intent(in) :: m
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: bytes, decimal
    type(block_t), pointer :: b
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    b => m%first
    if (associated (b)) then
        do

```

```

        call block_write_unit (b, unit, bytes, decimal)
        b => b%next
        if (.not. associated (b)) exit
        write (u, *)
    end do
end if
end subroutine message_write_unit

```

6.3.4 Auxiliary functions

These four functions on three words are defined in the MD5 standard:

(MD5: procedures)+≡

```

function ff (x, y, z)
    type(word32_t), intent(in) :: x, y, z
    type(word32_t) :: ff
    ff = ior (iand (x, y), iand (not (x), z))
end function ff

function fg (x, y, z)
    type(word32_t), intent(in) :: x, y, z
    type(word32_t) :: fg
    fg = ior (iand (x, z), iand (y, not (z)))
end function fg

function fh (x, y, z)
    type(word32_t), intent(in) :: x, y, z
    type(word32_t) :: fh
    fh = ieor (ieor (x, y), z)
end function fh

function fi (x, y, z)
    type(word32_t), intent(in) :: x, y, z
    type(word32_t) :: fi
    fi = ieor (y, ior (x, not (z)))
end function fi

```

6.3.5 Auxiliary stuff

This defines and initializes the table of transformation constants:

(MD5: variables)≡

```

type(word32_t), dimension(64), save :: t
logical, save :: table_initialized = .false.

```

(MD5: procedures)+≡

```

subroutine table_init
    type(word64_t) :: ww
    integer :: i
    if (.not.table_initialized) then
        do i = 1, 64
            ww = int (4294967296d0 * abs (sin (i * 1d0)), kind=i64)
            t(i) = word32_from_word64 (ww, 0)
        end do
    end if
end subroutine table_init

```



```

        end do
        table_initialized = .true.
    end if
end subroutine table_init

```

This encodes the message digest (4 words) into a 32-character string.

```

<MD5: procedures>+≡
function digest_string (aa) result (s)
    type(word32_t), dimension (0:3), intent(in) :: aa
    character(len=32) :: s
    integer :: i, j
    do i = 0, 3
        do j = 0, 3
            call byte_write (byte_from_word32 (aa(i), j), s(i*8+j*2+1:i*8+j*2+2))
        end do
    end do
end function digest_string

```

6.3.6 MD5 algorithm

Pad the message with a byte x80 and then pad zeros up to a full block minus two words; in these words, insert the message length (before padding) as a 64-bit word, low-word first.

```

<MD5: procedures>+≡
subroutine message_pad (m)
    type(message_t), intent(inout) :: m
    type(word64_t) :: length
    integer(i8), parameter :: ipad = -128 ! z'80'
    type(byte_t) :: b
    integer :: i
    length = message_bits (m)
    b = ipad
    call message_append_byte (m, b)
    call message_pad_zero (m, 56)
    do i = 0, 7
        call message_append_byte (m, byte_from_word64 (length, i))
    end do
end subroutine message_pad

```

Apply a series of transformations onto a state a,b,c,d, where the transform function uses each word of the message together with the predefined words. Finally, encode the state as a 32-character string.

```

<MD5: procedures>+≡
subroutine message_digest (m, s)
    type(message_t), intent(in) :: m
    character(len=32), intent(out) :: s
    integer(i32), parameter :: ia = 1732584193 ! z'67452301'
    integer(i32), parameter :: ib = -271733879 ! z'efcdab89'
    integer(i32), parameter :: ic = -1732584194 ! z'98badcfe'
    integer(i32), parameter :: id = 271733878 ! z'10325476'
    type(word32_t) :: a, b, c, d

```

```

type(word32_t) :: aa, bb, cc, dd
type(word32_t), dimension(0:15) :: x
type(block_t), pointer :: bl
call table_init
a = ia; b = ib; c = ic; d = id
bl => m%first
do
  if (.not.associated (bl)) exit
  x = bl%w
  aa = a; bb = b; cc = c; dd = d
  call transform (ff, a, b, c, d, 0, 7, 1)
  call transform (ff, d, a, b, c, 1, 12, 2)
  call transform (ff, c, d, a, b, 2, 17, 3)
  call transform (ff, b, c, d, a, 3, 22, 4)
  call transform (ff, a, b, c, d, 4, 7, 5)
  call transform (ff, d, a, b, c, 5, 12, 6)
  call transform (ff, c, d, a, b, 6, 17, 7)
  call transform (ff, b, c, d, a, 7, 22, 8)
  call transform (ff, a, b, c, d, 8, 7, 9)
  call transform (ff, d, a, b, c, 9, 12, 10)
  call transform (ff, c, d, a, b, 10, 17, 11)
  call transform (ff, b, c, d, a, 11, 22, 12)
  call transform (ff, a, b, c, d, 12, 7, 13)
  call transform (ff, d, a, b, c, 13, 12, 14)
  call transform (ff, c, d, a, b, 14, 17, 15)
  call transform (ff, b, c, d, a, 15, 22, 16)
  call transform (fg, a, b, c, d, 1, 5, 17)
  call transform (fg, d, a, b, c, 6, 9, 18)
  call transform (fg, c, d, a, b, 11, 14, 19)
  call transform (fg, b, c, d, a, 0, 20, 20)
  call transform (fg, a, b, c, d, 5, 5, 21)
  call transform (fg, d, a, b, c, 10, 9, 22)
  call transform (fg, c, d, a, b, 15, 14, 23)
  call transform (fg, b, c, d, a, 4, 20, 24)
  call transform (fg, a, b, c, d, 9, 5, 25)
  call transform (fg, d, a, b, c, 14, 9, 26)
  call transform (fg, c, d, a, b, 3, 14, 27)
  call transform (fg, b, c, d, a, 8, 20, 28)
  call transform (fg, a, b, c, d, 13, 5, 29)
  call transform (fg, d, a, b, c, 2, 9, 30)
  call transform (fg, c, d, a, b, 7, 14, 31)
  call transform (fg, b, c, d, a, 12, 20, 32)
  call transform (fh, a, b, c, d, 5, 4, 33)
  call transform (fh, d, a, b, c, 8, 11, 34)
  call transform (fh, c, d, a, b, 11, 16, 35)
  call transform (fh, b, c, d, a, 14, 23, 36)
  call transform (fh, a, b, c, d, 1, 4, 37)
  call transform (fh, d, a, b, c, 4, 11, 38)
  call transform (fh, c, d, a, b, 7, 16, 39)
  call transform (fh, b, c, d, a, 10, 23, 40)
  call transform (fh, a, b, c, d, 13, 4, 41)
  call transform (fh, d, a, b, c, 0, 11, 42)
  call transform (fh, c, d, a, b, 3, 16, 43)
  call transform (fh, b, c, d, a, 6, 23, 44)

```

```

    call transform (fh, a, b, c, d, 9, 4, 45)
    call transform (fh, d, a, b, c, 12, 11, 46)
    call transform (fh, c, d, a, b, 15, 16, 47)
    call transform (fh, b, c, d, a, 2, 23, 48)
    call transform (fi, a, b, c, d, 0, 6, 49)
    call transform (fi, d, a, b, c, 7, 10, 50)
    call transform (fi, c, d, a, b, 14, 15, 51)
    call transform (fi, b, c, d, a, 5, 21, 52)
    call transform (fi, a, b, c, d, 12, 6, 53)
    call transform (fi, d, a, b, c, 3, 10, 54)
    call transform (fi, c, d, a, b, 10, 15, 55)
    call transform (fi, b, c, d, a, 1, 21, 56)
    call transform (fi, a, b, c, d, 8, 6, 57)
    call transform (fi, d, a, b, c, 15, 10, 58)
    call transform (fi, c, d, a, b, 6, 15, 59)
    call transform (fi, b, c, d, a, 13, 21, 60)
    call transform (fi, a, b, c, d, 4, 6, 61)
    call transform (fi, d, a, b, c, 11, 10, 62)
    call transform (fi, c, d, a, b, 2, 15, 63)
    call transform (fi, b, c, d, a, 9, 21, 64)
    a = a + aa
    b = b + bb
    c = c + cc
    d = d + dd
    bl => bl%next
end do
s = digest_string ([a, b, c, d])
contains
<MD5: Internal subroutine transform>
end subroutine message_digest

```

And this is the actual transformation that depends on one of the previous functions, four words, and three integers. The implicit arguments are *x*, the word from the message to digest, and *t*, the entry in the predefined table.

```

<MD5: Internal subroutine transform>≡
subroutine transform (f, a, b, c, d, k, s, i)
  interface
    function f (x, y, z)
      import word32_t
      type(word32_t), intent(in) :: x, y, z
      type(word32_t) :: f
    end function f
  end interface
  type(word32_t), intent(inout) :: a
  type(word32_t), intent(in) :: b, c, d
  integer, intent(in) :: k, s, i
  a = b + ishftc (a + f(b, c, d) + x(k) + t(i), s)
end subroutine transform

```

6.3.7 User interface

```

<MD5: public>≡

```

```

        public :: md5sum
<MD5: interfaces>+=
    interface md5sum
        module procedure md5sum_from_string
        module procedure md5sum_from_unit
    end interface

```

This function computes the MD5 sum of the input string and returns it as a 32-character string

```

<MD5: procedures>+=
function md5sum_from_string (s) result (digest)
    character(len=*), intent(in) :: s
    character(len=32) :: digest
    type(message_t) :: m
    call message_append_string (m, s)
    call message_pad (m)
    call message_digest (m, digest)
    call message_clear (m)
end function md5sum_from_string

```

This funct. reads from unit u (an unformatted sequence of integers) and computes the MD5 sum.

```

<MD5: procedures>+=
function md5sum_from_unit (u) result (digest)
    integer, intent(in) :: u
    character(len=32) :: digest
    type(message_t) :: m
    character :: char
    integer :: iostat
    READ_CHARS: do
        read (u, "(A)", advance="no", iostat=iostat) char
        select case (iostat)
            case (0)
                call message_append_string (m, char)
            case (EOR)
                call message_append_string (m, LF)
            case (EOF)
                exit READ_CHARS
            case default
                call msg_fatal &
                    ("Computing MD5 sum: I/O error while reading from scratch file")
        end select
    end do READ_CHARS
    call message_pad (m)
    call message_digest (m, digest)
    call message_clear (m)
end function md5sum_from_unit

```

6.3.8 Unit tests

```

<MD5: public>+=
    public :: md5_test

```



```
end subroutine md5_1
```

6.4 Permutations

Permute arrays of integers (of specific kind).

```
<permutations.f90>≡  
<File header>
```

```
module permutations
```

```
    use kinds, only: TC
```

```
<Standard module head>
```

```
<Permutations: public>
```

```
<Permutations: types>
```

```
<Permutations: interfaces>
```

```
contains
```

```
<Permutations: procedures>
```

```
end module permutations
```

6.4.1 Permutations

A permutation is an array of integers. Each integer between one and `size` should occur exactly once.

```
<Permutations: public>≡  
    public :: permutation_t  
  
<Permutations: types>≡  
    type :: permutation_t  
    private  
        integer, dimension(:), allocatable :: p  
    end type permutation_t
```

Initialize with the identity permutation.

```
<Permutations: public>+≡  
    public :: permutation_init  
    public :: permutation_final  
  
<Permutations: procedures>≡  
    elemental subroutine permutation_init (p, size)  
        type(permutation_t), intent(inout) :: p  
        integer, intent(in) :: size  
        integer :: i  
        allocate (p%p (size))  
        forall (i = 1:size)
```

```

        p%p(i) = i
    end forall
end subroutine permutation_init

elemental subroutine permutation_final (p)
    type(permutation_t), intent(inout) :: p
    deallocate (p%p)
end subroutine permutation_final

```

I/O:

```

⟨Permutations: public⟩+=≡
    public :: permutation_write
⟨Permutations: procedures⟩+=≡
    subroutine permutation_write (p, u)
        type(permutation_t), intent (in) :: p
        integer, intent(in) :: u
        integer :: i
        do i = 1, size (p%p)
            if (size (p%p) < 10) then
                write (u,"(1x,I1)", advance="no") p%p(i)
            else
                write (u,"(1x,I3)", advance="no") p%p(i)
            end if
        end do
        write (u, *)
    end subroutine permutation_write

```

Administration:

```

⟨Permutations: public⟩+=≡
    public :: permutation_size
⟨Permutations: procedures⟩+=≡
    elemental function permutation_size (perm) result (s)
        type(permutation_t), intent(in) :: perm
        integer :: s
        s = size (perm%p)
    end function permutation_size

```

Extract an entry in a permutation.

```

⟨Permutations: public⟩+=≡
    public :: permute
⟨Permutations: procedures⟩+=≡
    elemental function permute (i, p) result (j)
        integer, intent(in) :: i
        type(permutation_t), intent(in) :: p
        integer :: j
        if (i > 0 .and. i <= size (p%p)) then
            j = p%p(i)
        else
            j = 0
        end if
    end function permute

```

Check whether a permutation is valid: Each integer in the range occurs exactly once.

```

(Permutations: public) +=
    public :: permutation_ok

(Permutations: procedures) +=
    elemental function permutation_ok (perm) result (ok)
        type(permutation_t), intent(in) :: perm
        logical :: ok
        integer :: i
        logical, dimension(:), allocatable :: set
        ok = .true.
        allocate (set (size (perm%p)))
        set = .false.
        do i = 1, size (perm%p)
            ok = (perm%p(i) > 0 .and. perm%p(i) <= size (perm%p))
            if (.not.ok) return
            set(perm%p(i)) = .true.
        end do
        ok = all (set)
    end function permutation_ok

```

Find the permutation that transforms the second array into the first one. We assume that this is possible and unique and all bounds are set correctly.

This cannot be elemental.

```

(Permutations: public) +=
    public :: permutation_find

(Permutations: procedures) +=
    subroutine permutation_find (perm, a1, a2)
        type(permutation_t), intent(inout) :: perm
        integer, dimension(:), intent(in) :: a1, a2
        integer :: i, j
        if (allocated (perm%p)) deallocate (perm%p)
        allocate (perm%p (size (a1)))
        do i = 1, size (a1)
            do j = 1, size (a2)
                if (a1(i) == a2(j)) then
                    perm%p(i) = j
                    exit
                end if
            end do
            perm%p(i) = 0
        end do
    end subroutine permutation_find

```

Find all permutations that transform an array of integers into itself. The resulting permutation list is allocated with the correct length and filled.

The first step is to count the number of different entries in `code`. Next, we scan `code` again and assign a mask to each different entry, true for all identical entries. Finally, we recursively permute the identity for each possible mask.

The permutation is done as follows: A list of all permutations of the initial one with respect to the current mask is generated, then the permutations are

generated in turn for each permutation in this list with the next mask. The result is always stored back into the main list, starting from the end of the current list.

```

(Permutations: public)+≡
    public :: permutation_array_make

(Permutations: procedures)+≡
    subroutine permutation_array_make (pa, code)
        type(permutation_t), dimension(:), allocatable, intent(out) :: pa
        integer, dimension(:), intent(in) :: code
        logical, dimension(size(code)) :: mask
        logical, dimension(:,:), allocatable :: imask
        integer, dimension(:), allocatable :: n_i
        type(permutation_t) :: p_init
        type(permutation_t), dimension(:), allocatable :: p_tmp
        integer :: psize, i, j, k, n_different, n, nn_k
        psize = size (code)
        mask = .true.
        n_different = 0
        do i=1, psize
            if (mask(i)) then
                n_different = n_different + 1
                mask = mask .and. (code /= code(i))
            end if
        end do
        allocate (imask(psize, n_different), n_i(n_different))
        mask = .true.
        k = 0
        do i=1, psize
            if (mask(i)) then
                k = k + 1
                imask(:,k) = (code == code(i))
                n_i(k) = factorial (count(imask(:,k)))
                mask = mask .and. (code /= code(i))
            end if
        end do
        n = product (n_i)
        allocate (pa (n))
        call permutation_init (p_init, psize)
        pa(1) = p_init
        nn_k = 1
        do k = 1, n_different
            allocate (p_tmp (n_i(k)))
            do i = nn_k, 1, -1
                call permutation_array_with_mask (p_tmp, imask(:,k), pa(i))
                do j = n_i(k), 1, -1
                    pa((i-1)*n_i(k) + j) = p_tmp(j)
                end do
            end do
            deallocate (p_tmp)
            nn_k = nn_k * n_i(k)
        end do
        call permutation_final (p_init)
        deallocate (imask, n_i)
    end subroutine

```

```
end subroutine permutation_array_make
```

Make a list of permutations of the elements marked true in the `mask` array. The final permutation list must be allocated with the correct length ($n!$). The third argument is the initial permutation to start with, which must have the same length as the `mask` array (this is not checked).

(*Permutations: procedures*) \equiv

```
subroutine permutation_array_with_mask (pa, mask, p_init)
  type(permutation_t), dimension(:), intent(inout) :: pa
  logical, dimension(:), intent(in) :: mask
  type(permutation_t), intent(in) :: p_init
  integer :: plen
  integer :: i, ii, j, fac_i, k, x
  integer, dimension(:), allocatable :: index
  plen = size (pa)
  allocate (index(count(mask)))
  ii = 0
  do i = 1, size (mask)
    if (mask(i)) then
      ii = ii + 1
      index(ii) = i
    end if
  end do
  pa = p_init
  ii = 0
  fac_i = 1
  do i = 1, size (mask)
    if (mask(i)) then
      ii = ii + 1
      fac_i = fac_i * ii
      x = permute (i, p_init)
      do j = 1, plen
        k = ii - mod (((j-1)*fac_i)/plen, ii)
        call insert (pa(j), x, k, ii, index)
      end do
    end if
  end do
  deallocate (index)
contains
  subroutine insert (p, x, k, n, index)
    type(permutation_t), intent(inout) :: p
    integer, intent(in) :: x, k, n
    integer, dimension(:), intent(in) :: index
    integer :: i
    do i = n, k+1, -1
      p%p(index(i)) = p%p(index(i-1))
    end do
    p%p(index(k)) = x
  end subroutine insert
end subroutine permutation_array_with_mask
```

The factorial function is needed for pre-determining the number of permutations that will be generated:

```

⟨Permutations: procedures⟩+=
  function factorial (n) result (f)
    integer, intent(in) :: n
    integer :: f
    integer :: i
    f = 1
    do i=2, abs(n)
      f = f*i
    end do
  end function factorial

```

6.4.2 Operations on binary codes

Binary codes are needed for phase-space trees. Since the permutation function uses permutations, and no other special type is involved, we put the functions here.

This is needed for phase space trees: permute bits in a tree binary code. If no permutation is given, leave as is. (We may want to access the permutation directly here if this is efficiency-critical.)

```

⟨Permutations: public⟩+=
  public :: tc_permute

⟨Permutations: procedures⟩+=
  function tc_permute (k, perm, mask_in) result (pk)
    integer(TC), intent(in) :: k, mask_in
    type(permutation_t), intent(in) :: perm
    integer(TC) :: pk
    integer :: i
    pk = iand (k, mask_in)
    do i = 1, size (perm%p)
      if (btest(k,i-1)) pk = ibset (pk, perm%p(i)-1)
    end do
  end function tc_permute

```

This routine returns the number of set bits in the tree code value **k**. Hence, it is the number of externals connected to the current line. If **mask** is present, the complement of the tree code is also considered, and the smaller number is returned. This gives the true distance from the external states, taking into account the initial particles. The complement number is increased by one, since for a scattering diagram the vertex with the sum of all final-state codes is still one point apart from the initial particles.

```

⟨Permutations: public⟩+=
  public :: tc_decay_level

⟨Permutations: interfaces⟩=
  interface tc_decay_level
    module procedure decay_level_simple
    module procedure decay_level_complement
  end interface

```

```

⟨Permutations: procedures⟩+=
  function decay_level_complement (k, mask) result (l)
    integer(TC), intent(in) :: k, mask
    integer :: l
    l = min (decay_level_simple (k), &
             & decay_level_simple (ieor (k, mask)) + 1)
  end function decay_level_complement

  function decay_level_simple (k) result(l)
    integer(TC), intent(in) :: k
    integer :: l
    integer :: i
    l = 0
    do i=0, bit_size(k)-1
      if (btest(k,i)) l = l+1
    end do
  end function decay_level_simple

```

6.5 Sorting

This small module provides functions for sorting integer or real arrays.

```

⟨sorting.f90⟩=
  ⟨File header⟩

  module sorting

    ⟨Use kinds⟩
    use unit_tests
    use diagnostics

    ⟨Standard module head⟩

    ⟨Sorting: public⟩

    ⟨Sorting: interfaces⟩

    contains

    ⟨Sorting: procedures⟩

    ⟨Sorting: tests⟩

    end module sorting

```

6.5.1 Implementation

The `sort` function returns, for a given integer or real array, the array sorted by increasing value. The current implementation is *mergesort*, which has $O(n \ln n)$ behavior in all cases, and is stable for elements of equal value.

The `sort_abs` variant sorts by increasing absolute value, where for identical absolute value, the positive number comes first.

```

<Sorting: public>≡
  public :: sort
  public :: sort_abs

<Sorting: interfaces>≡
  interface sort
    module procedure sort_int
    module procedure sort_real
  end interface

  interface sort_abs
    module procedure sort_int_abs
  end interface

```

This variant of integer sort returns The body is identical, just the interface differs.

```

<Sorting: procedures>≡
  function sort_int (val_in) result (val)
    integer, dimension(:), intent(in) :: val_in
    integer, dimension(size(val_in)) :: val
  <Sorting: sort>
  end function sort_int

  function sort_real (val_in) result (val)
    real(default), dimension(:), intent(in) :: val_in
    real(default), dimension(size(val_in)) :: val
  <Sorting: sort>
  end function sort_real

  function sort_int_abs (val_in) result (val)
    integer, dimension(:), intent(in) :: val_in
    integer, dimension(size(val_in)) :: val
  <Sorting: sort abs>
  end function sort_int_abs

<Sorting: sort>≡
  val = val_in( order (val_in) )

<Sorting: sort abs>≡
  val = val_in( order_abs (val_in) )

```

The `order` function returns, for a given integer or real array, the array of indices of the elements sorted by increasing value.

```

<Sorting: public>+≡
  public :: order
  public :: order_abs

<Sorting: interfaces>+≡
  interface order
    module procedure order_int
    module procedure order_real
  end interface

```

```

interface order_abs
  module procedure order_int_abs
end interface

```

```

⟨Sorting: procedures⟩+≡
  function order_int (val) result (idx)
    integer, dimension(:), intent(in) :: val
    integer, dimension(size(val)) :: idx
    ⟨Sorting: order⟩
  end function order_int

  function order_real (val) result (idx)
    real(default), dimension(:), intent(in) :: val
    integer, dimension(size(val)) :: idx
    ⟨Sorting: order⟩
  end function order_real

  function order_int_abs (val) result (idx)
    integer, dimension(:), intent(in) :: val
    integer, dimension(size(val)) :: idx
    ⟨Sorting: order abs⟩
  end function order_int_abs

```

We start by individual elements, merge them to pairs, merge those to four-element subarrays, and so on. The last subarray can extend only up to the original array bound, of course, and the second of the subarrays to merge should contain at least one element.

```

⟨Sorting: order⟩≡
  ⟨Sorting: order1⟩
    call merge (idx(b1:e2), idx(b1:e1), idx(b2:e2), val)
  ⟨Sorting: order2⟩

⟨Sorting: order abs⟩≡
  ⟨Sorting: order1⟩
    call merge_abs (idx(b1:e2), idx(b1:e1), idx(b2:e2), val)
  ⟨Sorting: order2⟩

⟨Sorting: order1⟩≡
  integer :: n, i, s, b1, b2, e1, e2
  n = size (idx)
  forall (i = 1:n)
    idx(i) = i
  end forall
  s = 1
  do while (s < n)
    do b1 = 1, n-s, 2*s
      b2 = b1 + s
      e1 = b2 - 1
      e2 = min (e1 + s, n)
    end do
    s = 2 * s
  end do

```

The merging step does the actual sorting. We take two sorted array sections and merge them to a sorted result array. We are working on the indices, and comparing is done by taking the associated `val` which is real or integer.

```

<Sorting: interfaces>+≡
  interface merge
    module procedure merge_int
    module procedure merge_real
  end interface

  interface merge_abs
    module procedure merge_int_abs
  end interface

<Sorting: procedures>+≡
  subroutine merge_int (res, src1, src2, val)
    integer, dimension(:), intent(out) :: res
    integer, dimension(:), intent(in) :: src1, src2
    integer, dimension(:), intent(in) :: val
    integer, dimension(size(res)) :: tmp
  <Sorting: merge>
  end subroutine merge_int

  subroutine merge_real (res, src1, src2, val)
    integer, dimension(:), intent(out) :: res
    integer, dimension(:), intent(in) :: src1, src2
    real(default), dimension(:), intent(in) :: val
    integer, dimension(size(res)) :: tmp
  <Sorting: merge>
  end subroutine merge_real

  subroutine merge_int_abs (res, src1, src2, val)
    integer, dimension(:), intent(out) :: res
    integer, dimension(:), intent(in) :: src1, src2
    integer, dimension(:), intent(in) :: val
    integer, dimension(size(res)) :: tmp
  <Sorting: merge abs>
  end subroutine merge_int_abs

<Sorting: merge>≡
  <Sorting: merge1>
    if (val(src1(i1)) <= val(src2(i2))) then
  <Sorting: merge2>

We keep the elements if the absolute values are strictly ordered. If they are
equal in magnitude, we keep them if the larger value comes first, or if they are
equal.

<Sorting: merge abs>≡
  <Sorting: merge1>
    if (abs (val(src1(i1))) < abs (val(src2(i2))) .or. &
        (abs (val(src1(i1))) == abs (val(src2(i2))) .and. &
         val(src1(i1)) >= val(src2(i2)))) then
  <Sorting: merge2>

```

```

<Sorting: merge1>≡
  integer :: i1, i2, i
  i1 = 1
  i2 = 1
  do i = 1, size (tmp)
    <Sorting: merge2>≡
      tmp(i) = src1(i1); i1 = i1 + 1
      if (i1 > size (src1)) then
        tmp(i+1:) = src2(i2:)
        exit
      end if
    else
      tmp(i) = src2(i2); i2 = i2 + 1
      if (i2 > size (src2)) then
        tmp(i+1:) = src1(i1:)
        exit
      end if
    end if
  end do
  res = tmp

```

6.5.2 Concatenating arrays

Not precisely a sorting function, but useful: Concatenate two arrays.

```

<Sorting: public>+≡
  public :: concat

<Sorting: interfaces>+≡
  interface concat
    module procedure concat_int
    module procedure concat_real
  end interface

<Sorting: procedures>+≡
  function concat_int (val1, val2) result (val12)
    integer, dimension(:), intent(in) :: val1, val2
    integer, dimension(size(val1)+size(val2)) :: val12
    <Sorting: concat>
  end function concat_int

  function concat_real (val1, val2) result (val12)
    real(default), dimension(:), intent(in) :: val1, val2
    integer, dimension(size(val1)+size(val2)) :: val12
    <Sorting: concat>
  end function concat_real

<Sorting: concat>≡
  val12(:size(val1)) = val1
  val12(size(val1)+1:) = val2

```


6.5.3 Unit tests

```

<Sorting: public>+≡
    public :: sorting_test

<Sorting: procedures>+≡
    subroutine sorting_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Sorting: execute tests>
    end subroutine sorting_test

```

This checks whether the sorting routine works correctly.

```

<Sorting: execute tests>≡
    call test (sorting_1, "sorting_1", &
        "check sorting routines", &
        u, results)

<Sorting: tests>≡
    subroutine sorting_1 (u)
        integer, intent(in) :: u
        integer, parameter :: NMAX = 10
        real(default), dimension(NMAX) :: rval
        integer, dimension(NMAX) :: ival
        real, dimension(NMAX,NMAX) :: harvest_r
        integer, dimension(NMAX,NMAX) :: harvest_i
        integer, dimension(NMAX,NMAX) :: harvest_a
        integer :: i, j
        harvest_r(:, 1) = [0.9976, 0., 0., 0., 0., 0., 0., 0., 0., 0.]
        harvest_r(:, 2) = [0.5668, 0.9659, 0., 0., 0., 0., 0., 0., 0., 0.]
        harvest_r(:, 3) = [0.7479, 0.3674, 0.4806, 0., 0., 0., 0., 0., 0., &
            0.]
        harvest_r(:, 4) = [0.0738, 0.0054, 0.3471, 0.3422, 0., 0., 0., 0., &
            0., 0.]
        harvest_r(:, 5) = [0.2180, 0.1332, 0.9005, 0.3868, 0.4455, 0., 0., &
            0., 0., 0.]
        harvest_r(:, 6) = [0.6619, 0.0161, 0.6509, 0.6464, 0.3230, &
            0.8557, 0., 0., 0., 0.]
        harvest_r(:, 7) = [0.4013, 0.2069, 0.9685, 0.5984, 0.6730, &
            0.4569, 0.3300, 0., 0., 0.]
        harvest_r(:, 8) = [0.1004, 0.7555, 0.6057, 0.7190, 0.8973, &
            0.6582, 0.1507, 0.6123, 0., 0.]
        harvest_r(:, 9) = [0.9787, 0.9991, 0.2568, 0.5509, 0.6590, &
            0.5540, 0.9778, 0.9019, 0.6579, 0.]
        harvest_r(:,10) = [0.7289, 0.4025, 0.9286, 0.1478, 0.6745, &
            0.7696, 0.3393, 0.1158, 0.6144, 0.8206]

        harvest_i(:, 1) = [18, 0, 0, 0, 0, 0, 0, 0, 0, 0]
        harvest_i(:, 2) = [14, 9, 0, 0, 0, 0, 0, 0, 0, 0]
        harvest_i(:, 3) = [ 7, 8,11, 0, 0, 0, 0, 0, 0, 0]
        harvest_i(:, 4) = [19,19,14,19, 0, 0, 0, 0, 0, 0]
        harvest_i(:, 5) = [ 1,14,15,18,14, 0, 0, 0, 0, 0]
        harvest_i(:, 6) = [16,11, 1, 9,11, 2, 0, 0, 0, 0]
        harvest_i(:, 7) = [11,10,17, 6,13,13,10, 0, 0, 0]
        harvest_i(:, 8) = [ 5, 1, 2,10, 7, 0,15,12, 0, 0]

```

```

harvest_i(:, 9) = [15,19, 2, 6,11, 0, 2, 4, 2, 0]
harvest_i(:,10) = [ 1, 4, 8, 4,11, 0, 8, 7,19,13]

harvest_a(:, 1) = [-6,  0,  0,  0,  0,  0,  0,  0,  0,  0]
harvest_a(:, 2) = [-8, -9,  0,  0,  0,  0,  0,  0,  0,  0]
harvest_a(:, 3) = [ 4, -3,  3,  0,  0,  0,  0,  0,  0,  0]
harvest_a(:, 4) = [-6,  6,  2, -2,  0,  0,  0,  0,  0,  0]
harvest_a(:, 5) = [ 1, -2,  0, -6,  8,  0,  0,  0,  0,  0]
harvest_a(:, 6) = [-2, -1, -8, -5,  8, -5,  0,  0,  0,  0]
harvest_a(:, 7) = [-9,  0, -6,  2,  5,  3,  2,  0,  0,  0]
harvest_a(:, 8) = [-5, -7,  6,  7, -3,  0, -7,  4,  0,  0]
harvest_a(:, 9) = [ 5,  0, -1, -7,  5,  2,  7, -3,  3,  0]
harvest_a(:,10) = [-9,  2, -6,  3, -9,  5,  5,  7,  5, -9]

write (u, "(A)")  "* Test output: Sorting"
write (u, "(A)")  "* Purpose: test sorting routines"
write (u, "(A)")

write (u, "(A)")  "* Sorting real values:"

do i = 1, NMAX
  write (u, "(A)")
  rval(:i) = harvest_r(:i,i)
  write (u, "(10(1x,F7.4))") rval(:i)
  rval(:i) = sort (rval(:i))
  write (u, "(10(1x,F7.4))") rval(:i)
  do j = i, 2, -1
    if (rval(j)-rval(j-1) < 0) &
      write (u, "(A)")  "*** Sorting failure. ***"
  end do
end do

write (u, "(A)")
write (u, "(A)")  "* Sorting integer values:"

do i = 1, NMAX
  write (u, "(A)")
  ival(:i) = harvest_i(:i,i)
  write (u, "(10(1x,I2))") ival(:i)
  ival(:i) = sort(ival(:i))
  write (u, "(10(1x,I2))") ival(:i)
  do j = i, 2, -1
    if (ival(j)-ival(j-1) < 0) &
      write (u, "(A)")  "*** Sorting failure. ***"
  end do
end do

write (u, "(A)")
write (u, "(A)")  "* Sorting integer values by absolute value:"

do i = 1, NMAX
  write (u, "(A)")
  ival(:i) = harvest_a(:i,i)

```

```

        write (u, "(10(1x,I2))") ival(:i)
        ival(:i) = sort_abs (ival(:i))
        write (u, "(10(1x,I2))") ival(:i)
        do j = i, 2, -1
            if (abs(ival(j))-abs(ival(j-1)) < 0 .or. &
                (abs(ival(j))==abs(ival(j-1))) .and. ival(j)>ival(j-1)) &
                write (u, "(A)")  "*** Sorting failure. ***"
        end do
    end do

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: sorting_1"

end subroutine sorting_1

```

6.6 Grids

This is not really a combinatorics module but this directory is the closest I could find. Maybe this will be moved to a seperate directory or combined with related stuff.

```

⟨grids.f90⟩≡
  ⟨File header⟩

  module grids

    ⟨Use kinds⟩
    use unit_tests
    use constants
    use io_units
    use format_defs
    use file_utils
    use diagnostics

    ⟨Standard module head⟩

    ⟨grids: public⟩

    ⟨grids: interfaces⟩

    ⟨grids: parameters⟩

    ⟨grids: types⟩

    contains

    ⟨grids: procedures⟩

  end module grids

```

Grids are used in many applications and a general implementation seems useful. The relevant properties implemented so far are

- Segments of the hypercube are represented by an integer array with size d corresponding to the dimension.
- There is a mapping from the indices to the location in the continuous memory block of values.
- Given a point in the hypercube, find the corresponding segment and the value of the grid therein.
- Update the grid sequentially to represent the maximum of a function over the unit hypercube.
- The grid can be saved to and recovered from disk.

The following might be implemented in the future

- Generate a random point in the hypercube by interpreting the grid as probability distribution.
This would most likely be solved by using projections and the `selector_t`, which would make a move of this module higher up in the dependency tree necessary.
- Update the grid sequentially to represent the *minimum* of a function over the unit hypercube.

```

<grids: public>≡
  public :: grid_t
<grids: types>≡
  type :: grid_t
    real(default), dimension(:), allocatable, private :: values
    integer, dimension(:), allocatable, private :: points
  contains
    <grids: grid: TBP>
  end type grid_t

```

6.6.1 Initializer and finalizer

For initialization, we expect the number of points for each dimension as an array or the the number of dimensions as a scalar whereby the default number of points is used then for each dimension.

```

<grids: grid: TBP>≡
  generic :: init => init_base, init_simple
  procedure :: init_base => grid_init_base
  procedure :: init_simple => grid_init_simple
<grids: procedures>≡
  pure subroutine grid_init_base (grid, points)
    class(grid_t), intent(inout) :: grid
    integer, dimension(:), intent(in) :: points
    allocate (grid%points (size (points)))
    allocate (grid%values (product (points)))
    grid%points = points
    grid%values = zero
  end subroutine grid_init_base

```

```

<grids: procedures>+≡
  pure subroutine grid_init_simple (grid, dimensions)
    class(grid_t), intent(inout) :: grid
    integer, intent(in) :: dimensions
    allocate (grid%points (dimensions))
    allocate (grid%values (DEFAULT_POINTS_PER_DIMENSION ** dimensions))
    grid%points = DEFAULT_POINTS_PER_DIMENSION
    grid%values = zero
  end subroutine grid_init_simple

```

A reasonable default

```

<grids: parameters>≡
  integer, parameter :: DEFAULT_POINTS_PER_DIMENSION = 100

```

Calling this is not mandatory, when an instance of `grid_t` goes out of scope as it will be done by Fortran automatically.

```

<grids: grid: TBP>+≡
  procedure :: final => grid_final

<grids: procedures>+≡
  pure subroutine grid_final (grid)
    class(grid_t), intent(inout) :: grid
    if (allocated (grid%values)) then
      deallocate (grid%values)
    end if
    if (allocated (grid%points)) then
      deallocate (grid%points)
    end if
  end subroutine grid_final

```

6.6.2 Segment finding and memory mapping

The `indices` array is expected to go from 1 to d whereby the entries for the different dims are from 1 to $n_{\text{points}}(\text{dim})$.

We get the value of the grid either from given `indices` or from a point `x` in the hypercube. In the latter case, we have to find the segment first.

```

<grids: grid: TBP>+≡
  generic :: get_value => get_value_from_x, get_value_from_indices
  procedure :: get_value_from_x => grid_get_value_from_x
  procedure :: get_value_from_indices => grid_get_value_from_indices

<grids: procedures>+≡
  function grid_get_value_from_indices (grid, indices)
    real(default) :: grid_get_value_from_indices
    class(grid_t), intent(in) :: grid
    integer, dimension(:), intent(in) :: indices
    grid_get_value_from_indices = grid%values(grid%get_index(indices))
  end function grid_get_value_from_indices

```

```

<grids: procedures>+=
function grid_get_value_from_x (grid, x)
  real(default) :: grid_get_value_from_x
  class(grid_t), intent(in) :: grid
  real(default), dimension(:), intent(in) :: x
  grid_get_value_from_x = grid_get_value_from_indices &
    (grid, grid_get_segment (grid, x))
end function grid_get_value_from_x

```

The segment is the part of the grid that contains the point x and is identified by a tuple of indices. This is just a brute force search, for fine grids one could also implement a binary search for $\mathcal{O}(\log N)$ behavior instead of $\mathcal{O}(N)$.

```

<grids: grid: TBP>+=
procedure :: get_segment => grid_get_segment

<grids: procedures>+=
function grid_get_segment (grid, x, unit)
  class(grid_t), intent(in) :: grid
  real(default), dimension(:), intent(in) :: x
  integer, intent(in), optional :: unit
  integer, dimension(1:size (x)) :: grid_get_segment
  integer :: dim, i
  real(default) :: segment_width
  grid_get_segment = 0
  do dim = 1, size (grid%points)
    segment_width = one / grid%points (dim)
    SEARCH: do i = 1, grid%points (dim)
      if (x (dim) <= i * segment_width) then
        grid_get_segment (dim) = i
        exit SEARCH
      end if
    end do SEARCH
    if (grid_get_segment (dim) == 0) then
      call msg_error ("grid_get_segment: Did not find x in [0,1]^d", &
        unit=unit)
    end if
  end do
end function grid_get_segment

```

This is a simple storage mapping function but more sophisticated ideas like hashing could be implemented.

$$\begin{aligned}
 \text{index} = & \text{indices}(1) + \\
 & \text{indices}(2) * \text{size}(1) + \\
 & \text{indices}(3) * \text{size}(1) * \text{size}(2) + \dots
 \end{aligned} \tag{6.1}$$

```

<grids: grid: TBP>+=
procedure :: get_index => grid_get_index

<grids: procedures>+=
pure function grid_get_index (grid, indices) result (grid_index)
  integer :: grid_index
  class(grid_t), intent(in) :: grid

```

```

integer, dimension(:), intent(in) :: indices
integer :: dim_innerloop, dim_outerloop, multiplier
grid_index = 1
do dim_outerloop = 1, size(indices)
    multiplier = 1
    do dim_innerloop = 1, dim_outerloop - 1
        multiplier = multiplier * grid%points (dim_innerloop)
    end do
    grid_index = grid_index + (indices(dim_outerloop) - 1) * multiplier
end do
end function grid_get_index

```

6.6.3 Grid manipulations

Given a point in the hypercube x and its value y , we update the grids, such that the stepwise function f defined by the grid is $f(x_i) \geq y_i \forall \{x_i, y_i\}$.

```

<grids: grid: TBP>+≡
    procedure :: update_maxima => grid_update_maxima
<grids: procedures>+≡
    subroutine grid_update_maxima (grid, x, y)
        class(grid_t), intent(inout) :: grid
        real(default), dimension(:), intent(in) :: x
        real(default), intent(in) :: y
        integer, dimension(1:size(x)) :: indices
        indices = grid%get_segment (x)
        if (grid%get_value (indices) < y) then
            grid%values (grid%get_index (indices)) = y
        end if
    end subroutine grid_update_maxima

```

More general cases have to be thought through when they are needed. *This is inefficient and non-general.*

```

<grids: grid: TBP>+≡
    procedure :: get_maximum_in_3d => grid_get_maximum_in_3d
<grids: procedures>+≡
    function grid_get_maximum_in_3d (grid, projected_index) result (maximum)
        real(default) :: maximum
        class(grid_t), intent(in) :: grid
        integer, intent(in) :: projected_index
        real(default) :: val
        integer :: i, j
        maximum = zero
        do i = 1, grid%points(1)
            do j = 1, grid%points(2)
                val = grid%get_value ([i, j, projected_index])
                if (val > maximum) then
                    maximum = val
                end if
            end do
        end do
    end function

```

```

end function grid_get_maximum_in_3d

<grids: grid: TBP>+≡
  procedure :: is_non_zero_everywhere => grid_is_non_zero_everywhere
<grids: procedures>+≡
  pure function grid_is_non_zero_everywhere (grid) result (yorn)
    logical :: yorn
    class(grid_t), intent(in) :: grid
    yorn = all (abs (grid%values) > zero)
  end function grid_is_non_zero_everywhere

```

6.6.4 Input and Output to screen and disk

```

<grids: grid: TBP>+≡
  procedure :: write => grid_write
<grids: procedures>+≡
  subroutine grid_write (grid, unit)
    class(grid_t), intent(in) :: grid
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1X,A)") "Grid"
    write (u, "(2X,A,2X)", advance='no') "Number of points per dimension:"
    if (allocated (grid%points)) then
      do i = 1, size (grid%points)
        write (u, "(I12,1X)", advance='no') &
          grid%points (i)
      end do
    end if
    write (u, *)
    write (u, "(2X,A)") "Values of the grid:"
    if (allocated (grid%values)) then
      do i = 1, size (grid%values)
        write (u, "(" // DEFAULT_OUTPUT_PRECISION // ",1X)") &
          grid%values (i)
      end do
    end if
    call grid%compute_and_write_mean_and_max (u)
  end subroutine grid_write

<grids: grid: TBP>+≡
  procedure :: compute_and_write_mean_and_max => &
    grid_compute_and_write_mean_and_max
<grids: procedures>+≡
  subroutine grid_compute_and_write_mean_and_max (grid, unit)
    class(grid_t), intent(in) :: grid
    integer, intent(in), optional :: unit
    integer :: u, i, n_values
    real(default) :: mean, val, maximum

```



```

u = given_output_unit (unit); if (u < 0) return
mean = zero
maximum = zero
n_values = size (grid%values)
do i = 1, n_values
  val = grid%values (i)
  mean = mean + val / n_values
  if (val > maximum) then
    maximum = val
  end if
end do
write (u, "(2X,A," // DEFAULT_OUTPUT_PRECISION // ")") &
  "Mean value of the grid: ", mean
write (u, "(2X,A," // DEFAULT_OUTPUT_PRECISION // ")") &
  "Max value of the grid: ", maximum
if (maximum > zero) then
  write (u, "(2X,A," // DEFAULT_OUTPUT_PRECISION // ")") &
    "Mean/Max value of the grid: ", mean / maximum
end if
end subroutine grid_compute_and_write_mean_and_max

```

<grids: grid: TBP>+≡

```

  procedure :: save_to_file => grid_save_to_file

```

<grids: procedures>+≡

```

subroutine grid_save_to_file (grid, file)
  class(grid_t), intent(in) :: grid
  character(len=*), intent(in) :: file
  integer :: iostat, u, i
  u = free_unit ()
  open (file=file, unit=u, action='write')
  if (allocated (grid%points)) then
    write (u, "(I12)") size (grid%points)
    do i = 1, size (grid%points)
      write (u, "(I12,1X)", advance='no', iostat=iostat) &
        grid%points (i)
    end do
  end if
  write (u, *)
  if (allocated (grid%values)) then
    do i = 1, size (grid%values)
      write (u, "(" // DEFAULT_OUTPUT_PRECISION // ",1X)", &
        advance='no', iostat=iostat) grid%values (i)
    end do
  end if
  if (iostat < 0) then
    call msg_warning &
      ('grid_save_to_file: Could not save grid to file')
  end if
  close (u)
end subroutine grid_save_to_file

```

<grids: parameters>+≡

```

  character(len=*), parameter :: DEFAULT_OUTPUT_PRECISION = FMT_16

```

```

<grids: grid: TBP>+=
  procedure :: load_from_file => grid_load_from_file

<grids: procedures>+=
  subroutine grid_load_from_file (grid, file)
    class(grid_t), intent(out) :: grid
    character(len=*), intent(in) :: file
    integer :: iostat, u, i, n_dimensions
    integer, dimension(:), allocatable :: points
    u = free_unit ()
    open (file=file, unit=u, action='read', iostat=iostat)
    read (u, "(I12)", iostat=iostat) n_dimensions
    allocate (points (n_dimensions))
    do i = 1, size (points)
      read (u, "(I12,1X)", advance='no', iostat=iostat) &
        points (i)
    end do
    read (u, *)
    call grid%init (points)
    do i = 1, size (grid%values)
      read (u, "(" // DEFAULT_OUTPUT_PRECISION // ",1X)", advance='no', iostat=iostat) &
        grid%values (i)
    end do
    if (iostat < 0) then
      call msg_warning ('grid_load_from_file: Could not load grid from file')
    end if
    close (u)
  end subroutine grid_load_from_file

```

6.6.5 Unit tests

```

<grids: public>+=
  public :: grids_test

<grids: procedures>+=
  subroutine grids_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <grids: execute tests>
  end subroutine grids_test

```

Test Index Function

```

<grids: execute tests>=
  call test(grids_1, "grids_1", &
    "Test Index Function", u, results)

<grids: procedures>+=
  subroutine grids_1 (u)
    integer, intent(in) :: u
    type(grid_t) :: grid
    write (u, "(A)")  "* Test output: grids_1"
    write (u, "(A)")  "* Purpose: Test Index Function"

```

```

write (u, "(A)")

call grid%init ([3])
call grid%write(u)
call assert (u, grid%get_index([1]) == 1, "grid%get_index(1) == 1")
call assert (u, grid%get_index([2]) == 2, "grid%get_index(2) == 2")
call assert (u, grid%get_index([3]) == 3, "grid%get_index(3) == 3")
call grid%final ()

call grid%init ([3,3])
call grid%write(u)
call assert (u, grid%get_index([1,1]) == 1, "grid%get_index(1,1) == 1")
call assert (u, grid%get_index([2,1]) == 2, "grid%get_index(2,1) == 2")
call assert (u, grid%get_index([3,1]) == 3, "grid%get_index(3,1) == 3")
call assert (u, grid%get_index([1,2]) == 4, "grid%get_index(1,2) == 4")
call assert (u, grid%get_index([2,2]) == 5, "grid%get_index(2,2) == 5")
call assert (u, grid%get_index([3,2]) == 6, "grid%get_index(3,2) == 6")
call assert (u, grid%get_index([1,3]) == 7, "grid%get_index(1,3) == 7")
call assert (u, grid%get_index([2,3]) == 8, "grid%get_index(2,3) == 8")
call assert (u, grid%get_index([3,3]) == 9, "grid%get_index(3,3) == 9")
call grid%final ()

call grid%init ([3,3,2])
call grid%write(u)
call assert (u, grid%get_index([1,1,1]) == 1, "grid%get_index(1,1,1) == 1")
call assert (u, grid%get_index([2,1,2]) == 2+9, "grid%get_index(2,1,2) == 2+9")
call assert (u, grid%get_index([3,3,1]) == 9, "grid%get_index(3,3,1) == 3")
call assert (u, grid%get_index([3,1,2]) == 3+9, "grid%get_index(3,1,2) == 4+9")
call assert (u, grid%get_index([2,2,1]) == 5, "grid%get_index(2,2,1) == 5")
call assert (u, grid%get_index([3,2,2]) == 6+9, "grid%get_index(3,2,2) == 6+9")
call assert (u, grid%get_index([1,3,1]) == 7, "grid%get_index(1,3,1) == 7")
call assert (u, grid%get_index([2,3,2]) == 8+9, "grid%get_index(2,3,2) == 8+9")
call assert (u, grid%get_index([3,3,2]) == 9+9, "grid%get_index(3,3,2) == 9+9")
call grid%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: grids_1"
end subroutine grids_1

```

Saving and Loading

```

<grids: execute tests>+≡
  call test(grids_2, "grids_2", &
    "Saving and Loading", u, results)

<grids: procedures>+≡
  subroutine grids_2 (u)
    integer, intent(in) :: u
    type(grid_t) :: grid
    write (u, "(A)")  "* Test output: grids_2"
    write (u, "(A)")  "* Purpose: Saving and Loading"
    write (u, "(A)")

```

```

call grid%init ([3])
grid%values = [one, two, three]
call grid%save_to_file ('grids_2_test')
call grid%final ()

call grid%load_from_file ('grids_2_test')
call grid%write (u)
call assert (u, nearly_equal (grid%get_value([1])), one), "grid%get_value(1) == 1")
call assert (u, nearly_equal (grid%get_value([2])), two), "grid%get_value(2) == 2")
call assert (u, nearly_equal (grid%get_value([3])), three), "grid%get_value(3) == 3")
call grid%final ()

call grid%init ([3,3])
grid%values = [one, two, three, four, zero, zero, zero, zero, zero]
call grid%save_to_file ('grids_2_test')
call grid%final ()

call grid%load_from_file ('grids_2_test')
call grid%write (u)
call assert (u, nearly_equal (grid%get_value([1,1])), one), "grid%get_value(1,1) == 1")
call assert (u, nearly_equal (grid%get_value([2,1])), two), "grid%get_value(2,1) == 2")
call assert (u, nearly_equal (grid%get_value([3,1])), three), "grid%get_value(3,1) == 3")
call assert (u, nearly_equal (grid%get_value([1,2])), four), "grid%get_value(1,2) == 4")
call delete_file ('grids_2_test')

write (u, "(A)")
write (u, "(A)")  "* Test output end: grids_2"
end subroutine grids_2

```

Get Segments

```

<grids: execute tests>+≡
call test(grids_3, "grids_3", &
        "Get Segments", u, results)

<grids: procedures>+≡
subroutine grids_3 (u)
integer, intent(in) :: u
type(grid_t) :: grid
integer, dimension(2) :: fail
write (u, "(A)")  "* Test output: grids_3"
write (u, "(A)")  "* Purpose: Get Segments"
write (u, "(A)")

call grid%init ([3])
call assert (u, all(grid%get_segment([0.00_default]) == [1]), &
            "all(grid%get_segment([0.00_default]) == [1])")
call assert (u, all(grid%get_segment([0.32_default]) == [1]), &
            "all(grid%get_segment([0.32_default]) == [1])")
call assert (u, all(grid%get_segment([0.52_default]) == [2]), &
            "all(grid%get_segment([0.52_default]) == [2])")
call assert (u, all(grid%get_segment([1.00_default]) == [3]), &
            "all(grid%get_segment([1.00_default]) == [3])")

```

```

call grid%final ()

call grid%init ([3,3])
call assert (u, all(grid%get_segment([0.00_default,0.00_default]) == [1,1]), &
    "all(grid%get_segment([0.00_default,0.00_default]) == [1,1])")
call assert (u, all(grid%get_segment([0.32_default,0.32_default]) == [1,1]), &
    "all(grid%get_segment([0.32_default,0.32_default]) == [1,1])")
call assert (u, all(grid%get_segment([0.52_default,0.52_default]) == [2,2]), &
    "all(grid%get_segment([0.52_default,0.52_default]) == [2,2])")
call assert (u, all(grid%get_segment([1.00_default,1.00_default]) == [3,3]), &
    "all(grid%get_segment([1.00_default,1.00_default]) == [3,3])")
write (u, "(A)")  "* A double error is expected"
fail = grid%get_segment([1.10_default,1.10_default], u)
call grid%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: grids_3"
end subroutine grids_3

```

Update Maxima

```

<grids: execute tests>+≡
    call test(grids_4, "grids_4", &
        "Update Maxima", u, results)

<grids: procedures>+≡
subroutine grids_4 (u)
    integer, intent(in) :: u
    type(grid_t) :: grid
    write (u, "(A)")  "* Test output: grids_4"
    write (u, "(A)")  "* Purpose: Update Maxima"
    write (u, "(A)")

    call grid%init ([4,4])
    call grid%update_maxima ([0.1_default, 0.0_default], 0.3_default)
    call grid%update_maxima ([0.9_default, 0.95_default], 1.7_default)
    call grid%write (u)
    call assert_equal (u, grid%get_value([1,1]), 0.3_default, &
        "grid%get_value([1,1])")
    call assert_equal (u, grid%get_value([2,2]), 0.0_default, &
        "grid%get_value([2,2])")
    call assert_equal (u, grid%get_value([4,4]), 1.7_default, &
        "grid%get_value([4,4])")

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: grids_4"
end subroutine grids_4

```

Finding and checking

```

<grids: execute tests>+≡
    call test(grids_5, "grids_5", &

```

```

        "Finding and checking", u, results)
<grids: procedures>+=
subroutine grids_5 (u)
    integer, intent(in) :: u
    type(grid_t) :: grid
    real(default) :: first, second
    write (u, "(A)")  "* Test output: grids_5"
    write (u, "(A)")  "* Purpose: Finding and checking"
    write (u, "(A)")

    call grid%init ([2,2,2])
    first = one / two - tiny_07
    second = two / two - tiny_07
    call grid%update_maxima ([0.1_default, 0.0_default, first], 0.3_default)
    call grid%update_maxima ([0.9_default, 0.95_default, second], 1.7_default)
    call grid%write (u)
    call assert (u, .not. grid%is_non_zero_everywhere (), &
        ".not. grid%is_non_zero_everywhere (")
    call assert_equal (u, grid%get_maximum_in_3d (1), 0.3_default, &
        "grid%get_maximum_in_3d (1)")
    call assert_equal (u, grid%get_maximum_in_3d (2), 1.7_default, &
        "grid%get_maximum_in_3d (2)")

    call grid%update_maxima ([0.9_default, 0.95_default, first], 1.8_default)
    call grid%update_maxima ([0.1_default, 0.95_default, first], 1.5_default)
    call grid%update_maxima ([0.9_default, 0.15_default, first], 1.5_default)
    call grid%update_maxima ([0.1_default, 0.0_default, second], 0.2_default)
    call grid%update_maxima ([0.1_default, 0.9_default, second], 0.2_default)
    call grid%update_maxima ([0.9_default, 0.0_default, second], 0.2_default)
    call grid%write (u)
    call assert (u, grid%is_non_zero_everywhere (), &
        "grid%is_non_zero_everywhere (")
    call assert_equal (u, grid%get_maximum_in_3d (1), 1.8_default, &
        "grid%get_maximum_in_3d (1)")
    call assert_equal (u, grid%get_maximum_in_3d (2), 1.7_default, &
        "grid%get_maximum_in_3d (2)")

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: grids_5"
end subroutine grids_5

```

One could think of multiple implementations of a generic type.

```

<solver.f90>≡
<File header>

module solver

<Use kinds>
    use constants
    use unit_tests
    use diagnostics

<Standard module head>

```

```

    <solver: public>

    <solver: parameters>

    <solver: types>

    <solver: interfaces>

contains

    <solver: procedures>

end module solver

<solver: public>≡
    public :: solver_function_t

<solver: types>≡
    type, abstract :: solver_function_t
contains
    procedure(solver_function_evaluate), deferred :: evaluate
end type solver_function_t

<solver: interfaces>≡
    abstract interface
        function solver_function_evaluate (solver_f, x) result (f)
            import
            complex(default) :: f
            class(solver_function_t), intent(in) :: solver_f
            real(default), intent(in) :: x
        end function
    end interface

<solver: public>+≡
    public :: solve_secant

<solver: procedures>≡
    function solve_secant (func, lower_start, upper_start, success, precision) result (x0)
        class(solver_function_t), intent(in) :: func
        real(default) :: x0
        real(default), intent(in) :: lower_start, upper_start
        real(default), intent(in), optional :: precision
        logical, intent(out) :: success
        real(default) :: desired, x_curr, x_next, f_curr, f_next, x_new
        integer :: n_iter
        desired = DEFAULT_PRECISION; if (present(precision)) desired = precision
        x_curr = lower_start
        x_next = upper_start
        n_iter = 0
        success = .false.
        SEARCH: do
            n_iter = n_iter + 1
            f_curr = real( func%evaluate (x_curr) )
            f_next = real( func%evaluate (x_next) )

```

```

    <Exit if close to zero and handle exceptions>
    x_new = x_next - (x_next - x_curr) / (f_next - f_curr) * f_next
    x_curr = x_next
    x_next = x_new
end do SEARCH
if (x0 < lower_start .or. x0 > upper_start) then
    call msg_warning ("solve: The root of the function is not in boundaries")
    return
end if
success = .true.
end function solve_secant

<Exit if close to zero and handle exceptions>≡
if (abs (f_next) < desired) then
    x0 = x_next
    exit
end if
if (n_iter > MAX_TRIES) then
    call msg_warning ("solve: Couldn't find root of function")
    return
end if
if (vanishes (f_next - f_curr)) then
    x_next = x_next + (x_next - x_curr) / 10
    cycle
end if

<solver: public>+≡
public :: solve_interval

<solver: procedures>+≡
function solve_interval (func, lower_start, upper_start, success, precision) &
    result (x0)

    class(solver_function_t), intent(in) :: func
    real(default) :: x0
    real(default), intent(in) :: lower_start, upper_start
    real(default), intent(in), optional :: precision
    logical, intent(out) :: success
    real(default) :: desired
    real(default) :: x_low, x_high, x_half
    real(default) :: f_low, f_high, f_half
    integer :: n_iter
    success = .false.
    desired = DEFAULT_PRECISION; if (present(precision)) desired = precision
    x0 = lower_start
    x_low = lower_start
    x_high = upper_start
    f_low = real( func%evaluate (x_low) )
    f_high = real( func%evaluate (x_high) )
    if (f_low * f_high > 0) return
    if (x_low > x_high) call msg_fatal ("Interval solver: Upper bound must be &
        &greater than lower bound")

    n_iter = 0
    do n_iter = 1, MAX_TRIES
        x_half = (x_high + x_low)/2
        f_half = real( func%evaluate (x_half) )

```



```

        if (abs (f_half) <= desired) then
            x0 = x_half
            exit
        end if
        if (f_low * f_half > 0._default) then
            x_low = x_half
            f_low = f_half
        else
            x_high = x_half
            f_high = f_half
        end if
    end do
    if (x0 < lower_start .or. x0 > upper_start) then
        call msg_warning ("Interval solver: The root of the function&
            & is out of boundaries")

        return
    end if
    success = .true.
contains
    subroutine display_solver_status ()
        print *, '=====
        print *, 'Status of interval solver: '
        print *, 'initial values: ', lower_start, upper_start
        print *, 'iteration: ', n_iter
        print *, 'x_low: ', x_low, 'f_low: ', f_low
        print *, 'x_high: ', x_high, 'f_high: ', f_high
        print *, 'x_half: ', x_half, 'f_half: ', f_half
    end subroutine display_solver_status
end function solve_interval

```

<solver: public>+≡

```
public :: solve_qgaus
```

<solver: procedures>+≡

```

function solve_qgaus (integrand, grid) result (integral)
    class(solver_function_t), intent(in) :: integrand
    complex(default) :: integral
    real(default), dimension(:), intent(in) :: grid
    integer :: i, j
    real(default) :: xm, xr
    real(default), dimension(5) :: dx, &
        w = (/ 0.2955242247_default, 0.2692667193_default, &
            0.2190863625_default, 0.1494513491_default, 0.0666713443_default /), &
        x = (/ 0.1488743389_default, 0.4333953941_default, 0.6794095682_default, &
            0.8650633666_default, 0.9739065285_default /)
    integral = 0.0_default
    if ( size(grid) < 2 ) then
        call msg_warning ("solve_qgaus: size of integration grid smaller than 2.")
        return
    end if
    do i=1, size(grid)-1
        xm = 0.5_default * ( grid(i+1) + grid(i) )
        xr = 0.5_default * ( grid(i+1) - grid(i) )
        do j=1, 5

```

```

        dx(j) = xr * x(j)
        integral = integral + xr * w(j) * &
            ( integrand%evaluate (xm+dx(j)) + integrand%evaluate (xm-dx(j)) )
    end do
end do
end function solve_qgaus

```

```

<solver: parameters>+=
    real(default), parameter :: DEFAULT_PRECISION = tiny_10

<solver: parameters>+=
    integer, parameter :: MAX_TRIES = 10000

```

6.6.6 Unit tests

```

<solver: types>+=
    type, extends (solver_function_t) :: test_function_1_t
    contains
        procedure :: evaluate => test_func_1
    end type test_function_1_t

```

```

<solver: types>+=
    type, extends (solver_function_t) :: test_function_2_t
    contains
        procedure :: evaluate => test_func_2
    end type test_function_2_t

```

```

<solver: types>+=
    type, extends (solver_function_t) :: test_function_3_t
    contains
        procedure :: evaluate => test_func_3
    end type test_function_3_t

```

```

<solver: types>+=
    type, extends (solver_function_t) :: test_function_4_t
    contains
        procedure :: evaluate => test_func_4
    end type test_function_4_t

```

```

<solver: procedures>+=
    function test_func_1 (solver_f, x) result (f)
        complex(default) :: f
        class(test_function_1_t), intent(in) :: solver_f
        real(default), intent(in) :: x
        f = x
    end function test_func_1

    function test_func_2 (solver_f, x) result (f)
        complex(default) :: f
        class(test_function_2_t), intent(in) :: solver_f
        real(default), intent(in) :: x

```

```

        f = x ** 2
    end function test_func_2

function test_func_3 (solver_f, x) result (f)
    complex(default) :: f
    class(test_function_3_t), intent(in) :: solver_f
    real(default), intent(in) :: x
    f = x ** 3
end function test_func_3

function test_func_4 (solver_f, x) result (f)
    complex(default) :: f
    class(test_function_4_t), intent(in) :: solver_f
    real(default), intent(in) :: x
    real(default) :: s, cutoff
    s = 100.0_default
    cutoff = 1.01_default
    if (x < cutoff) then
        f = - (log (s) * log (log (s) / log(cutoff**2)) - log (s / cutoff**2)) - &
            log (one/two)
    else
        f = - (log (s) * log (log (s) / log(x**2)) - log (s / x**2)) - &
            log (one/two)
    end if
end function test_func_4

<solver: public>+≡
    public :: solver_test

<solver: procedures>+≡
    subroutine solver_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <solver: execute tests>
    end subroutine solver_test

```

Solve trivial functions

```

<solver: execute tests>≡
    call test(solver_1, "solver_1", &
        "Solve trivial functions", u, results)

<solver: procedures>+≡
    subroutine solver_1 (u)
        integer, intent(in) :: u
        real(default) :: zero_position
        logical :: success
        type(test_function_1_t) :: test_func_1
        type(test_function_2_t) :: test_func_2
        type(test_function_3_t) :: test_func_3
        type(test_function_4_t) :: test_func_4
        write (u, "(A)")  "* Test output: solver_1"
        write (u, "(A)")  "* Purpose: Solve trivial functions"
        write (u, "(A)")
    end subroutine solver_1

```

```

zero_position = solve_interval (test_func_1, -one, one, success)
call assert (u, success, "success")
call assert_equal (u, zero_position, zero, "test_func_1: zero_position")

zero_position = solve_interval (test_func_4, two, 10.0_default, success)
call assert (u, success, "success")
call assert_equal (u, zero_position, 3.5216674014805425_default, &
    "test_func_4: zero_position", rel_smallness=1000*DEFAULT_PRECISION)

write (u, "(A)")
write (u, "(A)")  "* Test output end: solver_1"
end subroutine solver_1

```

Chapter 7

Text handling

WHIZARD has to handle complex structures in input (and output) data. Doing this in a generic and transparent way requires a generic lexer and parser. The necessary modules are implemented here:

ifiles Implementation of line-oriented internal files in a more flexible way (linked lists of variable-length strings) than the Fortran builtin features.

lexers Read text and transform it into a token stream.

syntax_rules Define the rules for interpreting tokens, to be used by the WHIZARD parser.

parser Categorize tokens (keyword, string, number etc.) and use a set of syntax rules to transform the input into a parse tree.

xml Read and parse XML text, separate from the WHIZARD parser.

7.1 Internal files

The internal files introduced here (`ifile`) are a replacement for the built-in internal files, which are fixed-size arrays of fixed-length character strings. The `ifile` type is a doubly-linked list of variable-length character strings with line numbers.

```
<ifiles.f90>≡  
  <File header>  
  
  module ifiles  
  
    <Use strings>  
    use io_units  
    use system_defs, only: EOF  
  
    <Standard module head>  
  
    <Ifiles: public>  
  
    <Ifiles: types>  
  
    <Ifiles: interfaces>  
  
    contains  
  
    <Ifiles: subroutines>  
  
  end module ifiles
```

7.1.1 The line type

The line entry type is for internal use, it is the list entry to be collected in an `ifile` object.

```
<Ifiles: types>≡  
  type :: line_entry_t  
  private  
  type(line_entry_t), pointer :: previous => null ()  
  type(line_entry_t), pointer :: next => null ()  
  type(string_t) :: string  
  integer :: index  
end type line_entry_t
```

Create a new list entry, given a varying string as input. The line number and pointers are not set, these make sense only within an `ifile`.

```
<Ifiles: subroutines>≡  
  subroutine line_entry_create (line, string)  
    type(line_entry_t), pointer :: line  
    type(string_t), intent(in) :: string  
    allocate (line)  
    line%string = string  
  end subroutine line_entry_create
```

Destroy a single list entry: Since the pointer components should not be deallocated explicitly, just deallocate the object itself.

```

<Ifiles: subroutines>+≡
  subroutine line_entry_destroy (line)
    type(line_entry_t), pointer :: line
    deallocate (line)
  end subroutine line_entry_destroy

```

7.1.2 The ifile type

The internal file is a linked list of line entries.

```

<Ifiles: public>≡
  public :: ifile_t
<Ifiles: types>+≡
  type :: ifile_t
    private
    type(line_entry_t), pointer :: first => null ()
    type(line_entry_t), pointer :: last => null ()
    integer :: n_lines = 0
    contains
    <Ifiles: ifile: TBP>
  end type ifile_t

```

We need no explicit initializer, but a routine which recursively deallocates the contents may be appropriate. After this, existing line pointers may become undefined, so they should be nullified before the file is destroyed.

```

<Ifiles: public>+≡
  public :: ifile_clear
<Ifiles: subroutines>+≡
  subroutine ifile_clear (ifile)
    class(ifile_t), intent(inout) :: ifile
    type(line_entry_t), pointer :: current
    do while (associated (ifile%first))
      current => ifile%first
      ifile%first => current%next
      call line_entry_destroy (current)
    end do
    nullify (ifile%last)
    ifile%n_lines = 0
  end subroutine ifile_clear

```

The finalizer is just an alias for the above.

```

<Ifiles: public>+≡
  public :: ifile_final
<Ifiles: ifile: TBP>≡
  procedure :: final => ifile_clear
<Ifiles: interfaces>≡
  interface ifile_final
    module procedure ifile_clear
  end interface

```

7.1.3 I/O on ifiles

Fill an ifile from an ordinary external file, i.e., I/O unit. If the ifile is not empty, the old contents will be destroyed. We can read a fixed-length character string, an ISO varying string, an ordinary internal file (character-string array), or from an external unit. In the latter case, lines are appended until EOF is reached. Finally, there is a variant which reads from another ifile, effectively copying it.

```
(Ifiles: public)+≡
    public :: ifile_read

(Ifiles: interfaces)+≡
    interface ifile_read
        module procedure ifile_read_from_string
        module procedure ifile_read_from_char
        module procedure ifile_read_from_unit
        module procedure ifile_read_from_char_array
        module procedure ifile_read_from_ifile
    end interface

(Ifiles: subroutines)+≡
    subroutine ifile_read_from_string (ifile, string)
        type(ifile_t), intent(inout) :: ifile
        type(string_t), intent(in) :: string
        call ifile_clear (ifile)
        call ifile_append (ifile, string)
    end subroutine ifile_read_from_string

    subroutine ifile_read_from_char (ifile, char)
        type(ifile_t), intent(inout) :: ifile
        character(*), intent(in) :: char
        call ifile_clear (ifile)
        call ifile_append (ifile, char)
    end subroutine ifile_read_from_char

    subroutine ifile_read_from_char_array (ifile, char)
        type(ifile_t), intent(inout) :: ifile
        character(*), dimension(:), intent(in) :: char
        call ifile_clear (ifile)
        call ifile_append (ifile, char)
    end subroutine ifile_read_from_char_array

    subroutine ifile_read_from_unit (ifile, unit, iostat)
        type(ifile_t), intent(inout) :: ifile
        integer, intent(in) :: unit
        integer, intent(out), optional :: iostat
        call ifile_clear (ifile)
        call ifile_append (ifile, unit, iostat)
    end subroutine ifile_read_from_unit

    subroutine ifile_read_from_ifile (ifile, ifile_in)
        type(ifile_t), intent(inout) :: ifile
        type(ifile_t), intent(in) :: ifile_in
        call ifile_clear (ifile)
        call ifile_append (ifile, ifile_in)
    end subroutine ifile_read_from_ifile
```


Append to an ifile. The same as reading, but without resetting the ifile. In addition, there is a routine for appending a whole ifile.

```

<Ifiles: public>+≡
    public :: ifile_append

<Ifiles: ifile: TBP>+≡
    generic :: append => &
        ifile_append_from_char
    procedure, private :: ifile_append_from_char

<Ifiles: interfaces>+≡
    interface ifile_append
        module procedure ifile_append_from_string
        module procedure ifile_append_from_char
        module procedure ifile_append_from_unit
        module procedure ifile_append_from_char_array
        module procedure ifile_append_from_ifile
    end interface

<Ifiles: subroutines>+≡
    subroutine ifile_append_from_string (ifile, string)
        class(ifile_t), intent(inout) :: ifile
        type(string_t), intent(in) :: string
        type(line_entry_t), pointer :: current
        call line_entry_create (current, string)
        current%index = ifile%n_lines + 1
        if (associated (ifile%last)) then
            current%previous => ifile%last
            ifile%last%next => current
        else
            ifile%first => current
        end if
        ifile%last => current
        ifile%n_lines = current%index
    end subroutine ifile_append_from_string

    subroutine ifile_append_from_char (ifile, char)
        class(ifile_t), intent(inout) :: ifile
        character(*), intent(in) :: char
        call ifile_append_from_string (ifile, var_str (trim (char)))
    end subroutine ifile_append_from_char

    subroutine ifile_append_from_char_array (ifile, char)
        class(ifile_t), intent(inout) :: ifile
        character(*), dimension(:), intent(in) :: char
        integer :: i
        do i = 1, size (char)
            call ifile_append_from_string (ifile, var_str (trim (char(i))))
        end do
    end subroutine ifile_append_from_char_array

    subroutine ifile_append_from_unit (ifile, unit, iostat)
        class(ifile_t), intent(inout) :: ifile
        integer, intent(in) :: unit

```

```

integer, intent(out), optional :: iostat
type(string_t) :: buffer
integer :: ios
ios = 0
READ_LOOP: do
    call get (unit, buffer, iostat = ios)
    if (ios == EOF .or. ios > 0) exit READ_LOOP
    call ifile_append_from_string (ifile, buffer)
end do READ_LOOP
if (present (iostat)) then
    iostat = ios
else if (ios > 0) then
    call get (unit, buffer) ! trigger error again
end if
end subroutine ifile_append_from_unit

subroutine ifile_append_from_ifile (ifile, ifile_in)
class(ifile_t), intent(inout) :: ifile
type(ifile_t), intent(in) :: ifile_in
type(line_entry_t), pointer :: current
current => ifile_in%first
do while (associated (current))
    call ifile_append_from_string (ifile, current%string)
    current => current%next
end do
end subroutine ifile_append_from_ifile

```

Write the ifile contents to an external unit

```

<Ifiles: public>+≡
public :: ifile_write

<Ifiles: subroutines>+≡
subroutine ifile_write (ifile, unit, iostat)
type(ifile_t), intent(in) :: ifile
integer, intent(in), optional :: unit
integer, intent(out), optional :: iostat
integer :: u
type(line_entry_t), pointer :: current
u = given_output_unit (unit); if (u < 0) return
current => ifile%first
do while (associated (current))
    call put_line (u, current%string, iostat)
    current => current%next
end do
end subroutine ifile_write

```

Convert the ifile to an array of strings, which is allocated by this function:

```

<Ifiles: public>+≡
public :: ifile_to_string_array

<Ifiles: subroutines>+≡
subroutine ifile_to_string_array (ifile, string)
type(ifile_t), intent(in) :: ifile
type(string_t), dimension(:), intent(inout), allocatable :: string

```

```

    type(line_entry_t), pointer :: current
    integer :: i
    allocate (string (ifile_get_length (ifile)))
    current => ifile%first
    do i = 1, ifile_get_length (ifile)
        string(i) = current%string
        current => current%next
    end do
end subroutine ifile_to_string_array

```

7.1.4 Ifile tools

```

<Ifiles: public>+≡
    public :: ifile_get_length

<Ifiles: subroutines>+≡
    function ifile_get_length (ifile) result (length)
        integer :: length
        type(ifile_t), intent(in) :: ifile
        length = ifile%n_lines
    end function ifile_get_length

```

7.1.5 Line pointers

Instead of the implicit pointer used in ordinary file access, we define explicit pointers, so there can be more than one at a time.

```

<Ifiles: public>+≡
    public :: line_p

<Ifiles: types>+≡
    type :: line_p
    private
        type(line_entry_t), pointer :: p => null ()
    end type line_p

```

Assign a file pointer to the first or last line in an ifile:

```

<Ifiles: public>+≡
    public :: line_init

<Ifiles: subroutines>+≡
    subroutine line_init (line, ifile, back)
        type(line_p), intent(inout) :: line
        type(ifile_t), intent(in) :: ifile
        logical, intent(in), optional :: back
        if (present (back)) then
            if (back) then
                line%p => ifile%last
            else
                line%p => ifile%first
            end if
        else
            line%p => ifile%first
        end if
    end subroutine line_init

```

```

        end if
    end subroutine line_init

```

Remove the pointer association:

```

<Ifiles: public>+≡
    public :: line_final

<Ifiles: subroutines>+≡
    subroutine line_final (line)
        type(line_p), intent(inout) :: line
        nullify (line%p)
    end subroutine line_final

```

Go one step forward

```

<Ifiles: public>+≡
    public :: line_advance

<Ifiles: subroutines>+≡
    subroutine line_advance (line)
        type(line_p), intent(inout) :: line
        if (associated (line%p)) line%p => line%p%next
    end subroutine line_advance

```

Go one step backward

```

<Ifiles: public>+≡
    public :: line_backspace

<Ifiles: subroutines>+≡
    subroutine line_backspace (line)
        type(line_p), intent(inout) :: line
        if (associated (line%p)) line%p => line%p%previous
    end subroutine line_backspace

```

Check whether we are accessing a valid line

```

<Ifiles: public>+≡
    public :: line_is_associated

<Ifiles: subroutines>+≡
    function line_is_associated (line) result (ok)
        logical :: ok
        type(line_p), intent(in) :: line
        ok = associated (line%p)
    end function line_is_associated

```

7.1.6 Access lines via pointers

We do not need the ifile as an argument to these functions, because the `line` type will point to an existing ifile.

```

<Ifiles: public>+≡
    public :: line_get_string

```

```

<Ifiles: subroutines>+=
function line_get_string (line) result (string)
  type(string_t) :: string
  type(line_p), intent(in) :: line
  if (associated (line%p)) then
    string = line%p%string
  else
    string = ""
  end if
end function line_get_string

```

Variant where the line pointer is advanced after reading.

```

<Ifiles: public>+=
public :: line_get_string_advance
<Ifiles: subroutines>+=
function line_get_string_advance (line) result (string)
  type(string_t) :: string
  type(line_p), intent(inout) :: line
  if (associated (line%p)) then
    string = line%p%string
    call line_advance (line)
  else
    string = ""
  end if
end function line_get_string_advance

```

```

<Ifiles: public>+=
public :: line_get_index
<Ifiles: subroutines>+=
function line_get_index (line) result (index)
  integer :: index
  type(line_p), intent(in) :: line
  if (associated (line%p)) then
    index = line%p%index
  else
    index = 0
  end if
end function line_get_index

```

```

<Ifiles: public>+=
public :: line_get_length
<Ifiles: subroutines>+=
function line_get_length (line) result (length)
  integer :: length
  type(line_p), intent(in) :: line
  if (associated (line%p)) then
    length = len (line%p%string)
  else
    length = 0
  end if
end function line_get_length

```

7.2 Lexer

The lexer purpose is to read from a line-separated character input stream (usually a file) and properly chop the stream into lexemes (tokens). [The parser will transform lexemes into meaningful tokens, to be stored in a parse tree, therefore we do not use the term 'token' here.] The input is read line-by-line, but interpreted free-form, except for quotes and the comment syntax. (Fortran 2003 would allow us to use a stream type for reading.)

In an object-oriented approach, we can dynamically create and destroy lexers, including the lexer setup.

The main lexer function is to return a lexeme according to the basic lexer rules (quotes, comments, whitespace, special classes). There is also a routine to write back a lexeme to the input stream (but only once).

For the rules, we separate the possible characters into classes. Whitespace usually consists of blank, tab, and line-feed, where any number of consecutive whitespace is equivalent to one. Quoted strings are enclosed by a pair of quote characters, possibly multiline. Comments are similar to quotes, but interpreted as whitespace. Numbers are identified (not distinguishing real and integer) but not interpreted. Other character classes make up identifiers.

```
<lexers.f90>≡  
  <File header>  
  
  module lexers  
  
    <Use strings>  
    use io_units  
    use string_utils  
    use unit_tests  
    use system_defs, only: EOF, EOR  
    use system_defs, only: LF  
    use system_defs, only: WHITESPACE_CHARS, LCLETTERS, UCLETTERS, DIGITS  
    use diagnostics  
    use ifiles, only: ifile_t  
    use ifiles, only: line_p, line_is_associated, line_init, line_final  
    use ifiles, only: line_get_string_advance  
  
    <Standard module head>  
  
    <Lexer: public>  
  
    <Lexer: parameters>  
  
    <Lexer: types>  
  
    <Lexer: interfaces>  
  
    contains  
  
    <Lexer: procedures>  
  
    <Lexer: tests>
```

```
end module lexers
```

7.2.1 Input streams

For flexible input, we define a generic stream type that refers to either an external file, an external unit which is already open, a string, an `ifile` object (internal file, i.e., string list), or a line pointer to an `ifile` object. The stream type actually follows the idea of a formatted external file, which is line-oriented. Thus, the stream reader always returns a whole record (input line).

Note that only in the string version, the stream contents are stored inside the stream object. In the `ifile` version, the stream contains only the line pointer, while in the external-file case, the line pointer is implicitly created by the runtime library.

```
<Lexer: public>≡
  public :: stream_t

<Lexer: types>≡
  type :: stream_t
    type(string_t), pointer :: filename => null ()
    integer, pointer :: unit => null ()
    type(string_t), pointer :: string => null ()
    type(ifile_t), pointer :: ifile => null ()
    type(line_p), pointer :: line => null ()
    integer :: record = 0
    logical :: eof = .false.
  contains
    <Lexer: stream: TBP>
  end type stream_t
```

The initializers refer to the specific version. The stream should be undefined before calling this.

```
<Lexer: public>+≡
  public :: stream_init

<Lexer: stream: TBP>≡
  generic :: init => &
    stream_init_filename, &
    stream_init_unit, &
    stream_init_string, &
    stream_init_ifile, &
    stream_init_line
  procedure, private :: stream_init_filename
  procedure, private :: stream_init_unit
  procedure, private :: stream_init_string
  procedure, private :: stream_init_ifile
  procedure, private :: stream_init_line

<Lexer: interfaces>≡
  interface stream_init
    module procedure stream_init_filename
    module procedure stream_init_unit
    module procedure stream_init_string
    module procedure stream_init_ifile
```

```

        module procedure stream_init_line
    end interface
<Lexer: procedures>≡
    subroutine stream_init_filename (stream, filename)
        class(stream_t), intent(out) :: stream
        character(*), intent(in) :: filename
        integer :: unit
        unit = free_unit ()
        open (unit=unit, file=filename, status="old", action="read")
        call stream_init_unit (stream, unit)
        allocate (stream%filename)
        stream%filename = filename
    end subroutine stream_init_filename

    subroutine stream_init_unit (stream, unit)
        class(stream_t), intent(out) :: stream
        integer, intent(in) :: unit
        allocate (stream%unit)
        stream%unit = unit
        stream%eof = .false.
    end subroutine stream_init_unit

    subroutine stream_init_string (stream, string)
        class(stream_t), intent(out) :: stream
        type(string_t), intent(in) :: string
        allocate (stream%string)
        stream%string = string
    end subroutine stream_init_string

    subroutine stream_init_ifile (stream, ifile)
        class(stream_t), intent(out) :: stream
        type(ifile_t), intent(in) :: ifile
        type(line_p) :: line
        call line_init (line, ifile)
        call stream_init_line (stream, line)
        allocate (stream%ifile)
        stream%ifile = ifile
    end subroutine stream_init_ifile

    subroutine stream_init_line (stream, line)
        class(stream_t), intent(out) :: stream
        type(line_p), intent(in) :: line
        allocate (stream%line)
        stream%line = line
    end subroutine stream_init_line

```

The finalizer restores the initial state. If an external file was opened, it is closed.

```

<Lexer: public>+≡
    public :: stream_final

<Lexer: stream: TBP>+≡
    procedure :: final => stream_final

<Lexer: procedures>+≡

```



```

subroutine stream_final (stream)
  class(stream_t), intent(inout) :: stream
  if (associated (stream%filename)) then
    close (stream%unit)
    deallocate (stream%unit)
    deallocate (stream%filename)
  else if (associated (stream%unit)) then
    deallocate (stream%unit)
  else if (associated (stream%string)) then
    deallocate (stream%string)
  else if (associated (stream%ifile)) then
    call line_final (stream%line)
    deallocate (stream%line)
    deallocate (stream%ifile)
  else if (associated (stream%line)) then
    call line_final (stream%line)
    deallocate (stream%line)
  end if
end subroutine stream_final

```

This returns the next record from the input stream. Depending on the stream type, the stream pointers are modified: Reading from external unit, the external file is advanced (implicitly). Reading from string, the string is replaced by an empty string. Reading from ifile, the line pointer is advanced. Note that the iostat argument is mandatory.

(Lexer: public)+≡

```

  public :: stream_get_record

```

(Lexer: procedures)+≡

```

subroutine stream_get_record (stream, string, iostat)
  type(stream_t), intent(inout) :: stream
  type(string_t), intent(out) :: string
  integer, intent(out) :: iostat
  if (associated (stream%unit)) then
    if (stream%eof) then
      iostat = EOF
    else
      call get (stream%unit, string, iostat=iostat)
      if (iostat == EOR) then
        iostat = 0
        stream%record = stream%record + 1
      end if
      if (iostat == EOF) then
        iostat = 0
        stream%eof = .true.
        if (len (string) /= 0) stream%record = stream%record + 1
      end if
    end if
  else if (associated (stream%string)) then
    if (len (stream%string) /= 0) then
      string = stream%string
      stream%string = ""
      iostat = 0
      stream%record = stream%record + 1
    end if
  end if
end subroutine stream_get_record

```

```

        else
            string = ""
            iostat = EOF
        end if
    else if (associated (stream%line)) then
        if (line_is_associated (stream%line)) then
            string = line_get_string_advance (stream%line)
            iostat = 0
            stream%record = stream%record + 1
        else
            string = ""
            iostat = EOF
        end if
    else
        call msg_bug (" Attempt to read from uninitialized input stream")
    end if
end subroutine stream_get_record

```

Return the current stream source as a message string.

```

<Lexer: public>+≡
    public :: stream_get_source_info_string

<Lexer: procedures>+≡
    function stream_get_source_info_string (stream) result (string)
        type(string_t) :: string
        type(stream_t), intent(in) :: stream
        character(20) :: buffer
        if (associated (stream%filename)) then
            string = "File '" // stream%filename // "' (unit = "
            write (buffer, "(I0)") stream%unit
            string = string // trim (buffer) // ")"
        else if (associated (stream%unit)) then
            write (buffer, "(I0)") stream%unit
            string = "Unit " // trim (buffer)
        else if (associated (stream%string)) then
            string = "Input string"
        else if (associated (stream%ifile) .or. associated (stream%line)) then
            string = "Internal file"
        else
            string = ""
        end if
    end function stream_get_source_info_string

```

Return the index of the record just read as a message string.

```

<Lexer: public>+≡
    public :: stream_get_record_info_string

<Lexer: procedures>+≡
    function stream_get_record_info_string (stream) result (string)
        type(string_t) :: string
        type(stream_t), intent(in) :: stream
        character(20) :: buffer
        string = stream_get_source_info_string (stream)
        if (string /= "") string = string // ", "
    end function stream_get_record_info_string

```

```

        write (buffer, "(I0)") stream%record
        string = string // "line " // trim (buffer)
    end function stream_get_record_info_string

```

7.2.2 Keyword list

The lexer should be capable of identifying a token as a known keyword. To this end, we store a list of keywords:

```

<Lexer: public>+≡
    public :: keyword_list_t

<Lexer: types>+≡
    type :: keyword_entry_t
        private
            type(string_t) :: string
            type(keyword_entry_t), pointer :: next => null ()
        end type keyword_entry_t

    type :: keyword_list_t
        private
            type(keyword_entry_t), pointer :: first => null ()
            type(keyword_entry_t), pointer :: last => null ()
        end type keyword_list_t

```

Add a new string to the keyword list, unless it is already there:

```

<Lexer: public>+≡
    public :: keyword_list_add

<Lexer: procedures>+≡
    subroutine keyword_list_add (keylist, string)
        type(keyword_list_t), intent(inout) :: keylist
        type(string_t), intent(in) :: string
        type(keyword_entry_t), pointer :: k_entry_new
        if (.not. keyword_list_contains (keylist, string)) then
            allocate (k_entry_new)
            k_entry_new%string = string
            if (associated (keylist%first)) then
                keylist%last%next => k_entry_new
            else
                keylist%first => k_entry_new
            end if
            keylist%last => k_entry_new
        end if
    end subroutine keyword_list_add

```

Return true if a string is a keyword.

```

<Lexer: public>+≡
    public :: keyword_list_contains

```

```

<Lexer: procedures>+≡
function keyword_list_contains (keylist, string) result (found)
    type(keyword_list_t), intent(in) :: keylist
    type(string_t), intent(in) :: string
    logical :: found
    found = .false.
    call check_rec (keylist%first)
contains
    recursive subroutine check_rec (k_entry)
        type(keyword_entry_t), pointer :: k_entry
        if (associated (k_entry)) then
            if (k_entry%string /= string) then
                call check_rec (k_entry%next)
            else
                found = .true.
            end if
        end if
    end subroutine check_rec
end function keyword_list_contains

```

Write the keyword list

```

<Lexer: public>+≡
public :: keyword_list_write

<Lexer: interfaces>+≡
interface keyword_list_write
    module procedure keyword_list_write_unit
end interface

<Lexer: procedures>+≡
subroutine keyword_list_write_unit (keylist, unit)
    type(keyword_list_t), intent(in) :: keylist
    integer, intent(in) :: unit
    write (unit, "(A)") "Keyword list:"
    if (associated (keylist%first)) then
        call keyword_write_rec (keylist%first)
        write (unit, *)
    else
        write (unit, "(1x,A)") "[empty]"
    end if
contains
    recursive subroutine keyword_write_rec (k_entry)
        type(keyword_entry_t), intent(in), pointer :: k_entry
        if (associated (k_entry)) then
            write (unit, "(1x,A)", advance="no") char (k_entry%string)
            call keyword_write_rec (k_entry%next)
        end if
    end subroutine keyword_write_rec
end subroutine keyword_list_write_unit

```

Clear the keyword list

```

<Lexer: public>+≡
public :: keyword_list_final

```

```

<Lexer: procedures>+≡
  subroutine keyword_list_final (keylist)
    type(keyword_list_t), intent(inout) :: keylist
    call keyword_destroy_rec (keylist%first)
    nullify (keylist%last)
  contains
    recursive subroutine keyword_destroy_rec (k_entry)
      type(keyword_entry_t), pointer :: k_entry
      if (associated (k_entry)) then
        call keyword_destroy_rec (k_entry%next)
        deallocate (k_entry)
      end if
    end subroutine keyword_destroy_rec
  end subroutine keyword_list_final

```

7.2.3 Lexeme templates

This type is handled like a rudimentary regular expression. It determines the lexer behavior when matching a string. The actual objects made from this type and the corresponding matching routines are listed below.

```

<Lexer: types>+≡
  type :: template_t
  private
  integer :: type
  character(256) :: charset1, charset2
  integer :: len1, len2
end type template_t

```

These are the types that valid lexemes can have:

```

<Lexer: public>+≡
  public :: T_KEYWORD, T_IDENTIFIER, T_QUOTED, T_NUMERIC

<Lexer: parameters>≡
  integer, parameter :: T_KEYWORD = 1
  integer, parameter :: T_IDENTIFIER = 2, T_QUOTED = 3, T_NUMERIC = 4

```

These are special types:

```

<Lexer: parameters>+≡
  integer, parameter :: EMPTY = 0, WHITESPACE = 10
  integer, parameter :: NO_MATCH = 11, IO_ERROR = 12, OVERFLOW = 13
  integer, parameter :: UNMATCHED_QUOTE = 14

```

In addition, we have EOF which is a negative integer, normally -1 . Printout for debugging:

```

<Lexer: procedures>+≡
  subroutine lexeme_type_write (type, unit)
    integer, intent(in) :: type
    integer, intent(in) :: unit
    select case (type)
    case (EMPTY);      write(unit,"(A)",advance="no") " EMPTY      "
    case (WHITESPACE); write(unit,"(A)",advance="no") " WHITESPACE "
    case (T_IDENTIFIER);write(unit,"(A)",advance="no") " IDENTIFIER  "
    case (T_QUOTED);   write(unit,"(A)",advance="no") " QUOTED      "

```

```

    case (T_NUMERIC);    write(unit,"(A)",advance="no") " NUMERIC      "
    case (IO_ERROR);    write(unit,"(A)",advance="no") " IO_ERROR    "
    case (OVERFLOW);    write(unit,"(A)",advance="no") " OVERFLOW    "
    case (UNMATCHED_QUOTE); write(unit,"(A)",advance="no") " UNMATCHEDQ  "
    case (NO_MATCH);    write(unit,"(A)",advance="no") " NO_MATCH    "
    case (EOF);         write(unit,"(A)",advance="no") " EOF        "
    case default;       write(unit,"(A)",advance="no") " [illegal]  "
  end select
end subroutine lexeme_type_write

subroutine template_write (tt, unit)
  type(template_t), intent(in) :: tt
  integer, intent(in) :: unit
  call lexeme_type_write (tt%type, unit)
  write (unit, "(A)", advance="no") " ' " // tt%charset1(1:tt%len1) // " '"
  write (unit, "(A)", advance="no") " ' " // tt%charset2(1:tt%len2) // " '"
end subroutine template_write

```

The matching functions all return the number of matched characters in the provided string. If this number is zero, the match has failed.

The `template` functions are declared `pure` because they appear in `forall` loops below.

A template for whitespace:

```

<Lexer: procedures>+≡
  pure function template_whitespace (chars) result (tt)
    character(*), intent(in) :: chars
    type(template_t) :: tt
    tt = template_t (WHITESPACE, chars, "", len (chars), 0)
  end function template_whitespace

```

Just match the string against the character set.

```

<Lexer: procedures>+≡
  subroutine match_whitespace (tt, s, n)
    type(template_t), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    n = verify (s, tt%charset1(1:tt%len1)) - 1
    if (n < 0) n = len (s)
  end subroutine match_whitespace

```

A template for normal identifiers. To match, a lexeme should have a first character in class `chars1` and an arbitrary number of further characters in class `chars2`. If the latter is empty, we are looking for a single-character lexeme.

```

<Lexer: procedures>+≡
  pure function template_identifier (chars1, chars2) result (tt)
    character(*), intent(in) :: chars1, chars2
    type(template_t) :: tt
    tt = template_t (T_IDENTIFIER, chars1, chars2, len(chars1), len(chars2))
  end function template_identifier

```

Here, the first letter must match, the others may or may not.

<Lexer: procedures>+≡

```

subroutine match_identifier (tt, s, n)
  type(template_t), intent(in) :: tt
  character(*), intent(in) :: s
  integer, intent(out) :: n
  if (verify (s(1:1), tt%charset1(1:tt%len1)) == 0) then
    n = verify (s(2:), tt%charset2(1:tt%len2))
    if (n == 0) n = len (s)
  else
    n = 0
  end if
end subroutine match_identifier

```

A template for quoted strings. The same template applies for comments. The first character set indicates the left quote (could be a sequence of several characters), the second one the matching right quote.

<Lexer: procedures>+≡

```

pure function template_quoted (chars1, chars2) result (tt)
  character(*), intent(in) :: chars1, chars2
  type(template_t) :: tt
  tt = template_t (T_QUOTED, chars1, chars2, len (chars1), len (chars2))
end function template_quoted

```

Here, the beginning of the string must exactly match the first character set, then we look for the second one. If found, return. If there is a first quote but no second one, return a negative number, indicating this error condition.

<Lexer: procedures>+≡

```

subroutine match_quoted (tt, s, n, range)
  type(template_t), intent(in) :: tt
  character(*), intent(in) :: s
  integer, intent(out) :: n
  integer, dimension(2), intent(out) :: range
  character(tt%len1) :: ch1
  character(tt%len2) :: ch2
  integer :: i
  ch1 = tt%charset1
  if (s(1:tt%len1) == ch1) then
    ch2 = tt%charset2
    do i = tt%len1 + 1, len (s) - tt%len2 + 1
      if (s(i:i+tt%len2-1) == ch2) then
        n = i + tt%len2 - 1
        range(1) = tt%len1 + 1
        range(2) = i - 1
        return
      end if
    end do
    n = -1
    range = 0
  else
    n = 0
    range = 0
  end if
end subroutine match_quoted

```

```

    end if
end subroutine match_quoted

```

A template for real numbers. The first character set is the set of allowed exponent letters. In accordance with the other functions we return the lexeme as a string but do not read it.

```

<Lexer: procedures>+≡
pure function template_numeric (chars) result (tt)
  character(*), intent(in) :: chars
  type(template_t) :: tt
  tt = template_t (T_NUMERIC, chars, "", len (chars), 0)
end function template_numeric

```

A numeric lexeme may be real or integer. We purposely do not allow for a preceding sign. If the number is followed by an exponent, this is included, otherwise the rest is ignored.

There is a possible pitfall with this behavior: while the string `1e3` will be interpreted as a single number, the analogous string `1a3` will be split into the number `1` and an identifier `a3`. There is no easy way around such an ambiguity. We should make sure that the syntax does not contain identifiers like `a3` or `e3`.

```

<Lexer: procedures>+≡
subroutine match_numeric (tt, s, n)
  type(template_t), intent(in) :: tt
  character(*), intent(in) :: s
  integer, intent(out) :: n
  integer :: i, n0
  character(10), parameter :: digits = "0123456789"
  character(2), parameter :: signs = "-+"
  n = verify (s, digits) - 1
  if (n < 0) then
    n = 0
    return
  else if (s(n+1:n+1) == ".") then
    i = verify (s(n+2:), digits) - 1
    if (i < 0) then
      n = len (s)
      return
    else if (i > 0 .or. n > 0) then
      n = n + 1 + i
    end if
  end if
  n0 = n
  if (n > 0) then
    if (verify (s(n+1:n+1), tt%charset1(1:tt%len1)) == 0) then
      n = n + 1
      if (verify (s(n+1:n+1), signs) == 0) n = n + 1
      i = verify (s(n+1:), digits) - 1
      if (i < 0) then
        n = len (s)
      else if (i == 0) then
        n = n0
      else

```



```

        n = n + i
    end if
end if
end if
end subroutine match_numeric

```

The generic matching routine. With Fortran 2003 we would define separate types and use a SELECT TYPE instead.

```

<Lexer: procedures>+≡
subroutine match_template (tt, s, n, range)
    type(template_t), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    integer, dimension(2), intent(out) :: range
    select case (tt%type)
    case (WHITESPACE)
        call match_whitespace (tt, s, n)
        range = 0
    case (T_IDENTIFIER)
        call match_identifier (tt, s, n)
        range(1) = 1
        range(2) = len_trim (s)
    case (T_QUOTED)
        call match_quoted (tt, s, n, range)
    case (T_NUMERIC)
        call match_numeric (tt, s, n)
        range(1) = 1
        range(2) = len_trim (s)
    case default
        call msg_bug ("Invalid lexeme template encountered")
    end select
end subroutine match_template

```

Match against an array of templates. Return the index of the first template that matches together with the number of characters matched and the range of the relevant substring. If all fails, these numbers are zero.

```

<Lexer: procedures>+≡
subroutine match (tt, s, n, range, ii)
    type(template_t), dimension(:), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    integer, dimension(2), intent(out) :: range
    integer, intent(out) :: ii
    integer :: i
    do i = 1, size (tt)
        call match_template (tt(i), s, n, range)
        if (n /= 0) then
            ii = i
            return
        end if
    end do
    n = 0
    ii = 0

```

```
end subroutine match
```

7.2.4 The lexer setup

This object contains information about character classes. As said above, one class consists of quoting chars (matching left and right), another one of comment chars (similar), a class of whitespace, and several classes of characters that make up identifiers. When creating the lexer setup, the character classes are transformed into lexeme templates which are to be matched in a certain predefined order against the input stream.

BLANK should always be taken as whitespace, some things may depend on this. TAB is also fixed by convention, but may in principle be modified. Newline (DOS!) and linefeed are also defined as whitespace. The lexer setup, containing the list of lexeme templates. No defaults yet. The type with index zero will be assigned to the NO_MATCH lexeme.

The keyword list is not stored, just a pointer to it. We anticipate that the keyword list is part of the syntax table, and the lexer needs not alter it. Furthermore, the lexer is typically finished before the syntax table is.

```
<Lexer: parameters>+≡
    integer, parameter :: CASE_KEEP = 0, CASE_UP = 1, CASE_DOWN = 2

<Lexer: types>+≡
    type :: lexer_setup_t
    private
    type(template_t), dimension(:), allocatable :: tt
    integer, dimension(:), allocatable :: type
    integer :: keyword_case = CASE_KEEP
    type(keyword_list_t), pointer :: keyword_list => null ()
end type lexer_setup_t
```

Fill the lexer setup object. Some things are hardcoded here (whitespace, alphanumeric identifiers), some are free: comment chars (but these must be single, and comments must be terminated by line-feed), quote chars and matches (must be single), characters to be read as one-character lexeme, special classes (characters of one class that should be glued together as identifiers).

```
<Lexer: procedures>+≡
    subroutine lexer_setup_init (setup, &
        comment_chars, quote_chars, quote_match, &
        single_chars, special_class, &
        keyword_list, upper_case_keywords)
    type(lexer_setup_t), intent(inout) :: setup
    character(*), intent(in) :: comment_chars
    character(*), intent(in) :: quote_chars, quote_match
    character(*), intent(in) :: single_chars
    character(*), dimension(:), intent(in) :: special_class
    type(keyword_list_t), pointer :: keyword_list
    logical, intent(in), optional :: upper_case_keywords
    integer :: n, i
    if (present (upper_case_keywords)) then
        if (upper_case_keywords) then
```

```

        setup%keyword_case = CASE_UP
    else
        setup%keyword_case = CASE_DOWN
    end if
else
    setup%keyword_case = CASE_KEEP
end if
n = 1 + len (comment_chars) + len (quote_chars) + 1 &
    + len (single_chars) + size (special_class) + 1
allocate (setup%tt(n))
allocate (setup%type(0:n))
n = 0
setup%type(n) = NO_MATCH
n = n + 1
setup%tt(n) = template_whitespace (WHITESPACE_CHARS)
setup%type(n) = EMPTY
forall (i = 1:len(comment_chars))
    setup%tt(n+i) = template_quoted (comment_chars(i:i), LF)
    setup%type(n+i) = EMPTY
end forall
n = n + len (comment_chars)
forall (i = 1:len(quote_chars))
    setup%tt(n+i) = template_quoted (quote_chars(i:i), quote_match(i:i))
    setup%type(n+i) = T_QUOTED
end forall
n = n + len (quote_chars)
setup%tt(n+1) = template_numeric ("EeDd")
setup%type(n+1) = T_NUMERIC
n = n + 1
forall (i = 1:len (single_chars))
    setup%tt(n+i) = template_identifier (single_chars(i:i), "")
    setup%type(n+i) = T_IDENTIFIER
end forall
n = n + len (single_chars)
forall (i = 1:size (special_class))
    setup%tt(n+i) = template_identifier &
        (trim (special_class(i)), trim (special_class(i)))
    setup%type(n+i) = T_IDENTIFIER
end forall
n = n + size (special_class)
setup%tt(n+1) = template_identifier &
    (LCLETTERS//UCLETTERS, LCLETTERS//DIGITS//"_"/UCLETTERS)
setup%type(n+1) = T_IDENTIFIER
n = n + 1
if (n /= size (setup%tt)) &
    call msg_bug ("Size mismatch in lexer setup")
setup%keyword_list => keyword_list
end subroutine lexer_setup_init

```

The destructor is needed only if the object is not itself part of an allocatable array

```

<Lexer: procedures>+≡
    subroutine lexer_setup_final (setup)

```

```

        type(lexer_setup_t), intent(inout) :: setup
        deallocate (setup%tt, setup%type)
        setup%keyword_list => null ()
    end subroutine lexer_setup_final

```

For debugging: Write the lexer setup

```

<Lexer: procedures>+≡
    subroutine lexer_setup_write (setup, unit)
        type(lexer_setup_t), intent(in) :: setup
        integer, intent(in) :: unit
        integer :: i
        write (unit, "(A)") "Lexer setup:"
        if (allocated (setup%tt)) then
            do i = 1, size (setup%tt)
                call template_write (setup%tt(i), unit)
                write (unit, '(A)', advance = "no") " -> "
                call lexeme_type_write (setup%type(i), unit)
                write (unit, *)
            end do
        else
            write (unit, *) "[empty]"
        end if
        if (associated (setup%keyword_list)) then
            call keyword_list_write (setup%keyword_list, unit)
        end if
    end subroutine lexer_setup_write

```

7.2.5 The lexeme type

An object of this type is returned by the lexer. Apart from the lexeme string, it gives information about the relevant substring (first and last character index) and the lexeme type. Interpreting the string is up to the parser.

```

<Lexer: public>+≡
    public :: lexeme_t

<Lexer: types>+≡
    type :: lexeme_t
    private
        integer :: type = EMPTY
        type(string_t) :: s
        integer :: b = 0, e = 0
    end type lexeme_t

```

Debugging aid:

```

<Lexer: public>+≡
    public :: lexeme_write

<Lexer: procedures>+≡
    subroutine lexeme_write (t, unit)
        type(lexeme_t), intent(in) :: t
        integer, intent(in) :: unit
        integer :: u

```

```

u = given_output_unit (unit); if (u < 0) return
select case (t%type)
case (T_KEYWORD)
    write (u, *) "KEYWORD:      '" // char (t%s) // "'"
case (T_IDENTIFIER)
    write (u, *) "IDENTIFIER: '" // char (t%s) // "'"
case (T_QUOTED)
    write (u, *) "QUOTED:      '" // char (t%s) // "'"
case (T_NUMERIC)
    write (u, *) "NUMERIC:      '" // char (t%s) // "'"
case (UNMATCHED_QUOTE)
    write (u, *) "Unmatched quote: "// char (t%s)
case (OVERFLOW); write (u, *) "Overflow: "// char (t%s)
case (EMPTY);    write (u, *) "Empty lexeme"
case (NO_MATCH); write (u, *) "No match"
case (IO_ERROR); write (u, *) "IO error"
case (EOF);      write (u, *) "EOF"
case default
    write (u, *) "Error"
end select
end subroutine lexeme_write

```

Store string and type in a lexeme. The range determines the beginning and end of the relevant part of the string. Check for a keyword.

(Lexer: procedures)+≡

```

subroutine lexeme_set (t, keyword_list, s, range, type, keyword_case)
    type(lexeme_t), intent(out) :: t
    type(keyword_list_t), pointer :: keyword_list
    type(string_t), intent(in) :: s
    type(string_t) :: keyword
    integer, dimension(2), intent(in) :: range
    integer, intent(in) :: type
    integer, intent(in), optional :: keyword_case
    t%type = type
    if (present (keyword_case)) then
        select case (keyword_case)
        case (CASE_KEEP); keyword = s
        case (CASE_UP); keyword = upper_case (s)
        case (CASE_DOWN); keyword = lower_case (s)
        end select
    else
        keyword = s
    end if
    if (type == T_IDENTIFIER) then
        if (associated (keyword_list)) then
            if (keyword_list_contains (keyword_list, keyword)) &
                t%type = T_KEYWORD
        end if
    end if
    select case (t%type)
    case (T_KEYWORD); t%s = keyword
    case default; t%s = s
    end select

```

```

    t%b = range(1)
    t%e = range(2)
end subroutine lexeme_set

subroutine lexeme_clear (t)
    type.lexeme_t, intent(out) :: t
    t%type = EMPTY
    t%s = ""
end subroutine lexeme_clear

```

Retrieve the lexeme string, the relevant part of it, and the type. The last function returns true if there is a break condition reached (error or EOF).

```

<Lexer: public>+≡
    public :: lexeme_get_string
    public :: lexeme_get_contents
    public :: lexeme_get_delimiters
    public :: lexeme_get_type

<Lexer: procedures>+≡
    function lexeme_get_string (t) result (s)
        type(string_t) :: s
        type.lexeme_t, intent(in) :: t
        s = t%s
    end function lexeme_get_string

    function lexeme_get_contents (t) result (s)
        type(string_t) :: s
        type.lexeme_t, intent(in) :: t
        s = extract (t%s, t%b, t%e)
    end function lexeme_get_contents

    function lexeme_get_delimiters (t) result (del)
        type(string_t), dimension(2) :: del
        type.lexeme_t, intent(in) :: t
        del(1) = extract (t%s, finish = t%b-1)
        del(2) = extract (t%s, start = t%e+1)
    end function lexeme_get_delimiters

    function lexeme_get_type (t) result (type)
        integer :: type
        type.lexeme_t, intent(in) :: t
        type = t%type
    end function lexeme_get_type

```

Check for a generic break condition (error/eof) and for eof in particular.

```

<Lexer: public>+≡
    public :: lexeme_is_break
    public :: lexeme_is_eof

<Lexer: procedures>+≡
    function lexeme_is_break (t) result (break)
        logical :: break
        type.lexeme_t, intent(in) :: t
        select case (t%type)

```

```

        case (EOF, IO_ERROR, OVERFLOW, NO_MATCH)
            break = .true.
        case default
            break = .false.
        end select
    end function lexeme_is_break

function lexeme_is_eof (t) result (ok)
    logical :: ok
    type.lexeme_t, intent(in) :: t
    ok = t%type == EOF
end function lexeme_is_eof

```

7.2.6 The lexer object

We store the current lexeme and the current line. The line buffer is set each time a new line is read from file. The working buffer has one character more, to hold any trailing blank. Pointers to line and column are for debugging, they will be used to make up readable error messages for the parser.

```

<Lexer: public>+≡
    public :: lexer_t

<Lexer: types>+≡
    type :: lexer_t
        private
        type(lexer_setup_t) :: setup
        type(stream_t), pointer :: stream => null ()
        type.lexeme_t :: lexeme
        type(string_t) :: previous_line2
        type(string_t) :: previous_line1
        type(string_t) :: current_line
        integer :: lines_read = 0
        integer :: current_column = 0
        integer :: previous_column = 0
        type(string_t) :: buffer
        type(lexer_t), pointer :: parent => null ()
    contains
        <Lexer: lexer: TBP>
    end type lexer_t

```

Create-setup wrapper

```

<Lexer: public>+≡
    public :: lexer_init

<Lexer: lexer: TBP>≡
    procedure :: init => lexer_init

<Lexer: procedures>+≡
    subroutine lexer_init (lexer, &
        comment_chars, quote_chars, quote_match, &
        single_chars, special_class, &
        keyword_list, upper_case_keywords, &
        parent)
        class(lexer_t), intent(inout) :: lexer
    end subroutine

```

```

character(*), intent(in) :: comment_chars
character(*), intent(in) :: quote_chars, quote_match
character(*), intent(in) :: single_chars
character(*), dimension(:), intent(in) :: special_class
type(keyword_list_t), pointer :: keyword_list
logical, intent(in), optional :: upper_case_keywords
type(lexer_t), target, intent(in), optional :: parent
call lexer_setup_init (lexer%setup, &
    comment_chars = comment_chars, &
    quote_chars = quote_chars, &
    quote_match = quote_match, &
    single_chars = single_chars, &
    special_class = special_class, &
    keyword_list = keyword_list, &
    upper_case_keywords = upper_case_keywords)
if (present (parent)) lexer%parent => parent
call lexer_clear (lexer)
end subroutine lexer_init

```

Clear the lexer state, but not the setup. This should be done when the lexing starts, but it is not known whether the lexer was used before.

```

<Lexer: public>+≡
    public :: lexer_clear

<Lexer: lexer: TBP>+≡
    procedure :: clear => lexer_clear

<Lexer: procedures>+≡
    subroutine lexer_clear (lexer)
        class(lexer_t), intent(inout) :: lexer
        call lexeme_clear (lexer%lexeme)
        lexer%previous_line2 = ""
        lexer%previous_line1 = ""
        lexer%current_line = ""
        lexer%lines_read = 0
        lexer%current_column = 0
        lexer%previous_column = 0
        lexer%buffer = ""
    end subroutine lexer_clear

```

Reset lexer state and delete setup

```

<Lexer: public>+≡
    public :: lexer_final

<Lexer: lexer: TBP>+≡
    procedure :: final => lexer_final

<Lexer: procedures>+≡
    subroutine lexer_final (lexer)
        class(lexer_t), intent(inout) :: lexer
        call lexer%clear ()
        call lexer_setup_final (lexer%setup)
    end subroutine lexer_final

```


7.2.7 The lexer routine

For lexing we need to associate an input stream to the lexer.

```
<Lexer: public>+≡
    public :: lexer_assign_stream

<Lexer: lexer: TBP>+≡
    procedure :: assign_stream => lexer_assign_stream

<Lexer: procedures>+≡
    subroutine lexer_assign_stream (lexer, stream)
        class(lexer_t), intent(inout) :: lexer
        type(stream_t), intent(in), target :: stream
        lexer%stream => stream
    end subroutine lexer_assign_stream
```

The lexer. The lexer function takes the lexer and returns the currently stored lexeme. If there is none, it is read from buffer, matching against the lexeme templates in the lexer setup. Empty lexemes, i.e., comments and whitespace, are discarded and the buffer is read again until we have found a nonempty lexeme (which may also be EOF or an error condition).

The initial state of the lexer contains an empty lexeme, so reading from buffer is forced. The empty state is restored after returning the lexeme. A nonempty lexeme is present in the lexer only if `lex_back` has been executed before.

The workspace is the `lexer%buffer`, treated as a sort of input stream. We chop off lexemes from the beginning, adjusting the buffer to the left. Whenever the buffer is empty, or we are matching against an open quote which has not terminated, we read a new line and append it to the right. This may result in special conditions, which for simplicity are also returned as lexemes: I/O error, buffer overflow, end of file. If the latter happens during reading a quoted string, we return an unmatched-quote lexeme. Obviously, the special-condition lexemes have to be caught by the parser.

Note that reading further lines is only necessary when reading a quoted string. Otherwise, the line-feed that ends each line is interpreted as whitespace which terminates a preceding lexeme, so there are no other valid multiline lexemes.

To enable meaningful error messages, we also keep track of the line number of the last line read, and the beginning and the end of the current lexeme with respect to this line.

The lexer is implemented as a function that returns the next lexeme (i.e., token). It uses the `lexer` setup and modifies the buffers and pointers stored within the lexer, a side effect. The lexer reads from an input stream object, which also is modified by this reading, e.g., a line pointer is advanced.

```
<Lexer: public>+≡
    public :: lex

<Lexer: procedures>+≡
    subroutine lex (lexeme, lexer)
        type(lexeme_t), intent(out) :: lexeme
        type(lexer_t), intent(inout) :: lexer
        integer :: iostat1, iostat2
        integer :: pos
```

```

integer, dimension(2) :: range
integer :: template_index, type
if (.not. associated (lexer%stream)) &
    call msg_bug ("Lexer called without assigned stream")
GET_LEXEME: do while (lexeme_get_type (lexer%lexeme) == EMPTY)
    if (len (lexer%buffer) /= 0) then
        iostat1 = 0
    else
        call lexer_read_line (lexer, iostat1)
    end if
    select case (iostat1)
    case (0)
        MATCH_BUFFER: do
            call match (lexer%setup%tt, char (lexer%buffer), &
                pos, range, template_index)
            if (pos >= 0) then
                type = lexer%setup%type(template_index)
                exit MATCH_BUFFER
            else
                pos = 0
                call lexer_read_line (lexer, iostat2)
                select case (iostat2)
                case (EOF); type = UNMATCHED_QUOTE; exit MATCH_BUFFER
                case (1);   type = IO_ERROR;         exit MATCH_BUFFER
                case (2);   type = OVERFLOW;         exit MATCH_BUFFER
                end select
            end if
        end do MATCH_BUFFER
    case (EOF); type = EOF
    case (1);   type = IO_ERROR
    case (2);   type = OVERFLOW
    end select
    call lexeme_set (lexer%lexeme, lexer%setup%keyword_list, &
        extract (lexer%buffer, finish=pos), range, type, &
        lexer%setup%keyword_case)
    lexer%buffer = remove (lexer%buffer, finish=pos)
    lexer%previous_column = lexer%current_column
    lexer%current_column = lexer%current_column + pos
end do GET_LEXEME
lexeme = lexer%lexeme
call lexeme_clear (lexer%lexeme)
end subroutine lex

```

Read a line and append it to the input buffer. If the input buffer overflows, return iostat=2. Otherwise, iostat=1 indicates an I/O error, and iostat=-1 the EOF.

The input stream may either be an external unit or a `ifile` object. In the latter case, a line is read and the line pointer is advanced.

Note that inserting LF between input lines is the Unix convention. Since we are doing this explicitly when gluing lines together, we can pattern-match against LF without having to worry about the system.

<Lexer: procedures>+≡

```

subroutine lexer_read_line (lexer, iostat)

```

```

type(lexer_t), intent(inout) :: lexer
integer, intent(out) :: iostat
type(string_t) :: current_line
current_line = lexer%current_line
call stream_get_record (lexer%stream, lexer%current_line, iostat)
if (iostat == 0) then
    lexer%lines_read = lexer%lines_read + 1
    lexer%previous_line2 = lexer%previous_line1
    lexer%previous_line1 = current_line
    lexer%buffer = lexer%buffer // lexer%current_line // LF
    lexer%previous_column = 0
    lexer%current_column = 0
end if
end subroutine lexer_read_line

```

Once in a while we have read one lexeme to many, which can be pushed back into the input stream. Do not do this more than once.

```

<Lexer: public>+≡
public :: lexer_put_back

<Lexer: procedures>+≡
subroutine lexer_put_back (lexer, lexeme)
type(lexer_t), intent(inout) :: lexer
type(lexeme_t), intent(in) :: lexeme
if (lexeme_get_type (lexer%lexeme) == EMPTY) then
    lexer%lexeme = lexeme
else
    call msg_bug (" Lexer: lex_back fails; probably called twice")
end if
end subroutine lexer_put_back

```

7.2.8 Diagnostics

For debugging: print just the setup

```

<Lexer: public>+≡
public :: lexer_write_setup

<Lexer: procedures>+≡
subroutine lexer_write_setup (lexer, unit)
type(lexer_t), intent(in) :: lexer
integer, intent(in), optional :: unit
integer :: u
u = given_output_unit (unit); if (u < 0) return
call lexer_setup_write (lexer%setup, u)
end subroutine lexer_write_setup

```

This is useful for error printing: show the current line with index and a pointer to the current column within the line.

```

<Lexer: public>+≡
public :: lexer_show_location

```

```

<Lexer: procedures>+≡
  subroutine lexer_show_location (lexer)
    type(lexer_t), intent(in) :: lexer
    type(string_t) :: loc_str
    if (associated (lexer%parent)) then
      call lexer_show_source (lexer%parent)
      call msg_message ("[includes]")
    else
      call msg_message ()
    end if
    if (associated (lexer%stream)) then
      call msg_message &
        (char (stream_get_record_info_string (lexer%stream)) // ":")
    end if
    if (lexer%lines_read >= 4) call msg_result ("[...]")
    if (lexer%lines_read >= 3) call msg_result (char (lexer%previous_line2))
    if (lexer%lines_read >= 2) call msg_result (char (lexer%previous_line1))
    if (lexer%lines_read >= 1) then
      call msg_result (char (lexer%current_line))
      loc_str = repeat (" ", lexer%previous_column)
      loc_str = loc_str // "^"
      if (lexer%current_column > lexer%previous_column) then
        loc_str = loc_str &
          // repeat ("-", max (lexer%current_column &
            - lexer%previous_column - 1, 0)) &
          // "^"
      end if
      call msg_result (char (loc_str))
    end if
  end subroutine lexer_show_location

```

This just prints the current stream source.

```

<Lexer: procedures>+≡
  recursive subroutine lexer_show_source (lexer)
    type(lexer_t), intent(in) :: lexer
    if (associated (lexer%parent)) then
      call lexer_show_source (lexer%parent)
      call msg_message ("[includes]")
    else
      call msg_message ()
    end if
    if (associated (lexer%stream)) then
      call msg_message &
        (char (stream_get_source_info_string (lexer%stream)) // ":")
    end if
  end subroutine lexer_show_source

```

7.2.9 Unit tests

```

<Lexer: public>+≡
  public :: lexer_test

```

```

<Lexer: procedures>+≡
  subroutine lexer_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Lexer: execute tests>
  end subroutine lexer_test

```

Test the lexer by lexing and printing all lexemes from unit `u`, one per line, using preset conventions.

```

<Lexer: execute tests>≡
  call test (lexer_1, "lexer_1", &
    "check lexer", u, results)

<Lexer: tests>≡
  subroutine lexer_1 (u)
    integer, intent(in) :: u
    type(lexer_t), target :: lexer
    type(stream_t), target :: stream
    type(string_t) :: string
    type(lexeme_t) :: lexeme
    string = "abcdefghij"
    call lexer_init (lexer, &
      comment_chars = "", &
      quote_chars = "<'\"", &
      quote_match = ">'\"", &
      single_chars = "?*+|=,()", &
      special_class = ["."], &
      keyword_list = null ())
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    do
      call lex (lexeme, lexer)
      call lexeme_write (lexeme, u)
      if (lexeme_is_break (lexeme)) exit
    end do
    call stream_final (stream)
    call lexer_final (lexer)
  end subroutine lexer_1

```

7.3 Syntax rules

This module provides tools to handle syntax rules in an abstract way.

```
<syntax_rules.f90>≡  
<File header>  
  
module syntax_rules  
  
  <Use strings>  
  use io_units  
  use diagnostics  
  use system_defs, only: LCLETTERS, UCLETTERS, DIGITS  
  use ifiles, only: line_p, line_init, line_get_string_advance, line_final  
  use ifiles, only: ifile_t, ifile_get_length  
  use lexers  
  
  <Standard module head>  
  
  <Syntax: public>  
  
  <Syntax: parameters>  
  
  <Syntax: types>  
  
  <Syntax: interfaces>  
  
  contains  
  
  <Syntax: subroutines>  
  
end module syntax_rules
```

7.3.1 Syntax rules

Syntax rules are used by the parser. They determine how to translate the stream of lexemes as returned by the lexer into the parse tree node. A rule may be terminal, i.e., replace a matching lexeme into a terminal node. The node will contain the lexeme interpreted as a recognized token:

- a keyword: unquoted fixed character string;
- a real number, to be determined at runtime;
- an integer, to be determined at runtime;
- a boolean value, to be determined at runtime;
- a quoted token (e.g., string), to be determined at runtime;
- an identifier (unquoted string that is not a recognized keyword), to be determined at runtime.

It may be nonterminal, i.e., contain a sequence of child rules. These are matched consecutively (and recursively) against the input stream; the resulting node will be a branch node.

- the file, i.e., the input stream as a whole;
- a sequence of syntax elements, where the last syntax element may be optional, or optional repetitive;

Sequences carry a flag that tells whether the last child is optional or may be repeated an arbitrary number of times, corresponding to the regexp modifiers `?`, `*`, and `+`.

We also need an alternative rule; this will be replaced by the node generated by one of its children that matches; thus, it does not create a node of its own.

- an alternative of syntax elements.

We also define special types of sequences as convenience macros:

- a list: a sequence where the elements are separated by a separator keyword (e.g., commas), the separators are thrown away when parsing the list;
- a group: a sequence of three tokens, where the first and third ones are left and right delimiters, the delimiters are thrown away;
- an argument list: a delimited list, containing both delimiters and separators.

It would be great to have a polymorphic type for this purpose, but until Fortran 2003 is out we have to emulate this.

Here are the syntax element codes:

```

<Syntax: public>≡
  public :: S_UNKNOWN
  public :: S_LOGICAL, S_INTEGER, S_REAL, S_COMPLEX, S_QUOTED
  public :: S_IDENTIFIER, S_KEYWORD
  public :: S_SEQUENCE, S_LIST, S_GROUP, S_ARGS
  public :: S_ALTERNATIVE
  public :: S_IGNORE

<Syntax: parameters>≡
  integer, parameter :: &
    S_UNKNOWN = 0, &
    S_LOGICAL = 1, S_INTEGER = 2, S_REAL = 3, S_COMPLEX = 4, &
    S_QUOTED = 5, S_IDENTIFIER = 6, S_KEYWORD = 7, &
    S_SEQUENCE = 8, S_LIST = 9, S_GROUP = 10, S_ARGS = 11, &
    S_ALTERNATIVE = 12, &
    S_IGNORE = 99

```

We need arrays of rule pointers, therefore this construct.

```

<Syntax: types>≡
  type :: rule_p
  private
    type(syntax_rule_t), pointer :: p => null ()
  end type rule_p

```

Return the association status of the rule pointer:

```

<Syntax: subroutines>≡
  elemental function rule_is_associated (rp) result (ok)
    logical :: ok
    type (rule_p), intent(in) :: rp
    ok = associated (rp%p)
  end function rule_is_associated

```

The rule type is one of the types listed above, represented by an integer code. The keyword, for a non-keyword rule, is an identifier used for the printed syntax table. The array of children is needed for nonterminal rules. In that case, there is a modifier for the last element (blank, "?", "*", or "+"), mirrored in the flags `opt` and `rep`. Then, we have the character constants used as separators and delimiters for this rule. Finally, the `used` flag can be set to indicate that this rule is the child of another rule.

Note: we separate `delimiter_left` and `delimiter_right` because the previous fixed dimension(2) array triggered an ICE in gfortran-4.9.2.

```

<Syntax: types>+≡
  public :: syntax_rule_t

<Syntax: types>+≡
  type :: syntax_rule_t
    private
    integer :: type = S_UNKNOWN
    logical :: used = .false.
    type(string_t) :: keyword
    type(string_t) :: separator
    type(string_t) :: delimiter_left, delimiter_right
    type(rule_p), dimension(:), allocatable :: child
    character(1) :: modifier = ""
    logical :: opt = .false., rep = .false.
  contains
    <Syntax: syntax rule: TBP>
  end type syntax_rule_t

```

Initializer: Set type and key for a rule, but do not (yet) allocate anything.

Finalizer: not needed (no pointer components).

```

<Syntax: subroutines>+≡
  subroutine syntax_rule_init (rule, key, type)
    type(syntax_rule_t), intent(inout) :: rule
    type(string_t), intent(in) :: key
    integer, intent(in) :: type
    rule%keyword = key
    rule%type = type
    select case (rule%type)
    case (S_GROUP)
      call syntax_rule_set_delimiter (rule)
    case (S_LIST)
      call syntax_rule_set_separator (rule)
    case (S_ARGS)
      call syntax_rule_set_delimiter (rule)
      call syntax_rule_set_separator (rule)
    end select
  end subroutine syntax_rule_init

```



```

        end select
    end subroutine syntax_rule_init

```

These characters will not be enclosed in quotes when writing syntax rules:

```

<Syntax: parameters>+≡
    character(*), parameter :: &
        UNQUOTED = "(),|_//LCLETTERS//UCLETTERS//DIGITS

```

7.3.2 I/O

Write an account of the rule. Setting `short` true will suppress the node type. Setting `key_only` true will suppress the definition. Setting `advance` false will suppress the trailing newline.

```

<Syntax: public>+≡
    public :: syntax_rule_write

<Syntax: syntax rule: TBP>≡
    procedure :: write => syntax_rule_write

<Syntax: subroutines>+≡
    subroutine syntax_rule_write (rule, unit, short, key_only, advance)
        class(syntax_rule_t), intent(in) :: rule
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: short, key_only, advance
        logical :: typ, def, adv
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        typ = .true.; if (present (short)) typ = .not. short
        def = .true.; if (present (key_only)) def = .not. key_only
        adv = .true.; if (present (advance)) adv = advance
        select case (rule%type)
        case (S_UNKNOWN); call write_atom ("???", typ)
        case (S_IGNORE); call write_atom ("IGNORE", typ)
        case (S_LOGICAL); call write_atom ("LOGICAL", typ)
        case (S_INTEGER); call write_atom ("INTEGER", typ)
        case (S_REAL); call write_atom ("REAL", typ)
        case (S_COMPLEX); call write_atom ("COMPLEX", typ)
        case (S_IDENTIFIER); call write_atom ("IDENTIFIER", typ)
        case (S_KEYWORD); call write_atom ("KEYWORD", typ)
        case (S_QUOTED)
            call write_quotes (typ, def, &
                del = [rule%delimiter_left, rule%delimiter_right])
        case (S_SEQUENCE)
            call write_sequence ("SEQUENCE", typ, def, size (rule%child))
        case (S_GROUP)
            call write_sequence ("GROUP", typ, def, size (rule%child), &
                del = [rule%delimiter_left, rule%delimiter_right])
        case (S_LIST)
            call write_sequence ("LIST", typ, def, size (rule%child), &
                sep = rule%separator)
        case (S_ARGS)
            call write_sequence ("ARGUMENTS", typ, def, size (rule%child), &
                del = [rule%delimiter_left, rule%delimiter_right], &
                sep = rule%separator)

```

```

case (S_ALTERNATIVE)
  call write_sequence ("ALTERNATIVE", typ, def, size (rule%child), &
    sep = var_str ("|"))
end select
if (adv) write (u, *)
contains
subroutine write_type (type)
  character(*), intent(in) :: type
  character(11) :: str
  str = type
  write (u, "(1x,A)", advance="no") str
end subroutine write_type
subroutine write_key
  write (u, "(1x,A)", advance="no") char (wkey (rule))
end subroutine write_key
subroutine write_atom (type, typ)
  character(*), intent(in) :: type
  logical, intent(in) :: typ
  if (typ) call write_type (type)
  call write_key
end subroutine write_atom
subroutine write_maybe_quoted (string)
  character(*), intent(in) :: string
  character, parameter :: q = '"'
  character, parameter :: qq = '\''
  if (verify (string, UNQUOTED) == 0) then
    write (u, "(1x,A)", advance = "no") trim (string)
  else if (verify (string, q) == 0) then
    write (u, "(1x,A)", advance = "no") qq // trim (string) // qq
  else
    write (u, "(1x,A)", advance = "no") q // trim (string) // q
  end if
end subroutine write_maybe_quoted
subroutine write_quotes (typ, def, del)
  logical, intent(in) :: typ, def
  type(string_t), dimension(2), intent(in) :: del
  if (typ) call write_type ("QUOTED")
  call write_key
  if (def) then
    write (u, "(1x,'=')", advance="no")
    call write_maybe_quoted (char (del(1)))
    write (u, "(1x,A)", advance="no") "... "
    call write_maybe_quoted (char (del(2)))
  end if
end subroutine write_quotes
subroutine write_sequence (type, typ, def, n, del, sep)
  character(*), intent(in) :: type
  logical, intent(in) :: typ, def
  integer, intent(in) :: n
  type(string_t), dimension(2), intent(in), optional :: del
  type(string_t), intent(in), optional :: sep
  integer :: i
  if (typ) call write_type (type)
  call write_key

```

```

    if (def) then
        write (u, "(1x,'=')", advance="no")
        if (present (del)) call write_maybe_quoted (char (del(1)))
        do i = 1, n
            if (i > 1 .and. present (sep)) &
                call write_maybe_quoted (char (sep))
            write (u, "(1x,A)", advance="no") &
                char (wkey (syntax_rule_get_sub_ptr(rule, i)))
            if (i == n) write (u, "(A)", advance="no") trim (rule%modifier)
        end do
        if (present (del)) call write_maybe_quoted (char (del(2)))
    end if
end subroutine write_sequence
end subroutine syntax_rule_write

```

In the printed representation, the keyword strings are enclosed as `<...>`, unless they are bare keywords. Bare keywords are enclosed as `'..'` if they contain a character which is not a letter, digit, or underscore. If they contain a single-quote character, they are enclosed as `".."`. (A keyword must not contain both single- and double-quotes.)

<Syntax: subroutines>+≡

```

function wkey (rule) result (string)
    type(string_t) :: string
    type(syntax_rule_t), intent(in) :: rule
    select case (rule%type)
    case (S_KEYWORD)
        if (verify (rule%keyword, UNQUOTED) == 0) then
            string = rule%keyword
        else if (scan (rule%keyword, "\"") == 0) then
            string = "\"" // rule%keyword // "\""
        else
            string = "'" // rule%keyword // "'"
        end if
    case default
        string = "<" // rule%keyword // ">"
    end select
end function wkey

```

7.3.3 Completing syntax rules

Set the separator and delimiter entries, using defaults:

<Syntax: subroutines>+≡

```

subroutine syntax_rule_set_separator (rule, separator)
    type(syntax_rule_t), intent(inout) :: rule
    type(string_t), intent(in), optional :: separator
    if (present (separator)) then
        rule%separator = separator
    else
        rule%separator = ","
    end if
end subroutine syntax_rule_set_separator

```

```

subroutine syntax_rule_set_delimiter (rule, delimiter)
  type(syntax_rule_t), intent(inout) :: rule
  type(string_t), dimension(2), intent(in), optional :: delimiter
  if (present (delimiter)) then
    rule%delimiter_left = delimiter(1)
    rule%delimiter_right = delimiter(2)
  else
    rule%delimiter_left = "("
    rule%delimiter_right = ")"
  end if
end subroutine syntax_rule_set_delimiter

```

Set the modifier entry and corresponding flags:

(Syntax: subroutines)+≡

```

function is_modifier (string) result (ok)
  logical :: ok
  type(string_t), intent(in) :: string
  select case (char (string))
    case (" ", "?", "*", "+"); ok = .true.
    case default; ok = .false.
  end select
end function is_modifier

subroutine syntax_rule_set_modifier (rule, modifier)
  type(syntax_rule_t), intent(inout) :: rule
  type(string_t), intent(in) :: modifier
  rule%modifier = char (modifier)
  select case (rule%modifier)
    case (" ")
    case ("?"); rule%opt = .true.
    case ("*"); rule%opt = .true.; rule%rep = .true.
    case ("+"); rule%rep = .true.
    case default
      call msg_bug (" Syntax: sequence modifier '" // rule%modifier &
        // "' is not one of '+' '*' '?'")
  end select
end subroutine syntax_rule_set_modifier

```

Check a finalized rule for completeness

(Syntax: subroutines)+≡

```

subroutine syntax_rule_check (rule)
  type(syntax_rule_t), intent(in) :: rule
  if (rule%keyword == "") call msg_bug ("Rule key not set")
  select case (rule%type)
    case (S_UNKNOWN); call bug (" Undefined rule")
    case (S_IGNORE, S_LOGICAL, S_INTEGER, S_REAL, S_COMPLEX, &
      S_IDENTIFIER, S_KEYWORD)
    case (S_QUOTED)
      if (rule%delimiter_left == "" .or. rule%delimiter_right == "") &
        call bug (" Missing quote character(s)")
    case (S_SEQUENCE)
    case (S_GROUP)

```

```

        if (rule%delimiter_left == "" .or. rule%delimiter_right == "") &
            call bug (" Missing delimiter(s)")
    case (S_LIST)
        if (rule%separator == "") call bug (" Missing separator")
    case (S_ARGS)
        if (rule%delimiter_left == "" .or. rule%delimiter_right == "") &
            call bug (" Missing delimiter(s)")
        if (rule%separator == "") call bug (" Missing separator")
    case (S_ALTERNATIVE)
    case default
        call bug (" Undefined syntax code")
    end select
    select case (rule%type)
    case (S_SEQUENCE, S_GROUP, S_LIST, S_ARGS, S_ALTERNATIVE)
        if (allocated (rule%child)) then
            if (.not.all (rule_is_associated (rule%child))) &
                call bug (" Child rules not all associated")
        else
            call bug (" Parent rule without children")
        end if
    case default
        if (allocated (rule%child)) call bug (" Non-parent rule with children")
    end select
contains
    subroutine bug (string)
        character(*), intent(in) :: string
        call msg_bug (" Syntax table: Rule " // char (rule%keyword) // ": " &
            // string)
    end subroutine bug
end subroutine syntax_rule_check

```

7.3.4 Accessing rules

This is the API for syntax rules:

```

<Syntax: public>+≡
    public :: syntax_rule_get_type

<Syntax: subroutines>+≡
    function syntax_rule_get_type (rule) result (type)
        integer :: type
        type(syntax_rule_t), intent(in) :: rule
        type = rule%type
    end function syntax_rule_get_type

<Syntax: public>+≡
    public :: syntax_rule_get_key

<Syntax: syntax rule: TBP>+≡
    procedure :: get_key => syntax_rule_get_key

<Syntax: subroutines>+≡
    function syntax_rule_get_key (rule) result (key)
        class(syntax_rule_t), intent(in) :: rule
        type(string_t) :: key

```

```

    key = rule%keyword
end function syntax_rule_get_key

```

<Syntax: public>+≡

```

public :: syntax_rule_get_separator
public :: syntax_rule_get_delimiter

```

<Syntax: subroutines>+≡

```

function syntax_rule_get_separator (rule) result (separator)
    type(string_t) :: separator
    type(syntax_rule_t), intent(in) :: rule
    separator = rule%separator
end function syntax_rule_get_separator

```

```

function syntax_rule_get_delimiter (rule) result (delimiter)
    type(string_t), dimension(2) :: delimiter
    type(syntax_rule_t), intent(in) :: rule
    delimiter = [rule%delimiter_left, rule%delimiter_right]
end function syntax_rule_get_delimiter

```

Accessing child rules. If we use `syntax_rule_get_n_sub` for determining loop bounds, we do not need a check in the second routine.

<Syntax: public>+≡

```

public :: syntax_rule_get_n_sub
public :: syntax_rule_get_sub_ptr

```

<Syntax: subroutines>+≡

```

function syntax_rule_get_n_sub (rule) result (n)
    integer :: n
    type(syntax_rule_t), intent(in) :: rule
    if (allocated (rule%child)) then
        n = size (rule%child)
    else
        n = 0
    end if
end function syntax_rule_get_n_sub

```

```

function syntax_rule_get_sub_ptr (rule, i) result (sub)
    type(syntax_rule_t), pointer :: sub
    type(syntax_rule_t), intent(in), target :: rule
    integer, intent(in) :: i
    sub => rule%child(i)%p
end function syntax_rule_get_sub_ptr

```

```

subroutine syntax_rule_set_sub (rule, i, sub)
    type(syntax_rule_t), intent(inout) :: rule
    integer, intent(in) :: i
    type(syntax_rule_t), intent(in), target :: sub
    rule%child(i)%p => sub
end subroutine syntax_rule_set_sub

```

Return the modifier flags:

<Syntax: public>+≡

```

    public :: syntax_rule_last_optional
    public :: syntax_rule_last_repetitive
<Syntax: subroutines>+=
    function syntax_rule_last_optional (rule) result (opt)
        logical :: opt
        type(syntax_rule_t), intent(in) :: rule
        opt = rule%opt
    end function syntax_rule_last_optional
    function syntax_rule_last_repetitive (rule) result (rep)
        logical :: rep
        type(syntax_rule_t), intent(in) :: rule
        rep = rule%rep
    end function syntax_rule_last_repetitive

```

Return true if the rule is atomic, i.e., logical, real, keyword etc.

```

<Syntax: public>+=
    public :: syntax_rule_is_atomic
<Syntax: subroutines>+=
    function syntax_rule_is_atomic (rule) result (atomic)
        logical :: atomic
        type(syntax_rule_t), intent(in) :: rule
        select case (rule%type)
            case (S_LOGICAL, S_INTEGER, S_REAL, S_COMPLEX, S_IDENTIFIER, &
                 S_KEYWORD, S_QUOTED)
                atomic = .true.
            case default
                atomic = .false.
        end select
    end function syntax_rule_is_atomic

```

7.3.5 Syntax tables

A syntax table contains the tree of syntax rules and, for direct parser access, the list of valid keywords.

Types

The syntax contains an array of rules and a list of keywords. The array is actually used as a tree, where the top rule is the first array element, and the other rules are recursively pointed to by this first rule. (No rule should be used twice or be unused.) The keyword list is derived from the rule tree.

Objects of this type need the target attribute if they are associated with a lexer. The keyword list will be pointed to by this lexer.

```

<Syntax: public>+=
    public :: syntax_t
<Syntax: types>+=
    type :: syntax_t
        private
        type(syntax_rule_t), dimension(:), allocatable :: rule
        type(keyword_list_t) :: keyword_list

```

```
end type syntax_t
```

Constructor/destructor

Initialize and finalize syntax tables

```
<Syntax: public>+≡
  public :: syntax_init
  public :: syntax_final
```

There are two ways to create a syntax: hard-coded from rules or dynamically from file.

```
<Syntax: interfaces>≡
  interface syntax_init
    module procedure syntax_init_from_ifile
  end interface
```

The syntax definition is read from an `ifile` object which contains the syntax definitions in textual form, one rule per line. This interface allows for determining the number of rules beforehand.

To parse the rule definitions, we make up a temporary lexer. Obviously, we cannot use a generic parser yet, so we have to hardcode the parsing process.

```
<Syntax: subroutines>+≡
  subroutine syntax_init_from_ifile (syntax, ifile)
    type(syntax_t), intent(out), target :: syntax
    type(ifile_t), intent(in) :: ifile
    type(lexer_t) :: lexer
    type(line_p) :: line
    type(string_t) :: string
    integer :: n_token
    integer :: i
    call lexer_init (lexer, &
      comment_chars = "", &
      quote_chars = "<'\"", &
      quote_match = ">'\"", &
      single_chars = "?*+|=,()", &
      special_class = ["."], &
      keyword_list = null ())
    allocate (syntax%rule (ifile_get_length (ifile)))
    call line_init (line, ifile)
    do i = 1, size (syntax%rule)
      string = line_get_string_advance (line)
      call set_rule_type_and_key (syntax%rule(i), string, lexer)
    end do
    call line_init (line, ifile)
    do i = 1, size (syntax%rule)
      string = line_get_string_advance (line)
      select case (syntax%rule(i)%type)
      case (S_QUOTED, S_SEQUENCE, S_GROUP, S_LIST, S_ARGS, S_ALTERNATIVE)
        n_token = get_n_token (string, lexer)
        call set_rule_contents &
          (syntax%rule(i), syntax, n_token, string, lexer)
      end select
    end do
```



```

end do
call line_final (line)
call lexer_final (lexer)
call syntax_make_keyword_list (syntax)
if (.not. all (syntax%rule%used)) then
  do i = 1, size (syntax%rule)
    if (.not. syntax%rule(i)%used) then
      call syntax_rule_write (syntax%rule(i), 6)
    end if
  end do
  call msg_bug (" Syntax table: unused rules")
end if
end subroutine syntax_init_from_ifile

```

For a given rule defined in the input, the first task is to determine its type and key. With these, we can initialize the rule in the table, postponing the association of children.

<Syntax: subroutines>+≡

```

subroutine set_rule_type_and_key (rule, string, lexer)
  type(syntax_rule_t), intent(inout) :: rule
  type(string_t), intent(in) :: string
  type(lexer_t), intent(inout) :: lexer
  type(stream_t), target :: stream
  type(lexeme_t) :: lexeme
  type(string_t) :: key
  character(2) :: type
  call lexer_clear (lexer)
  call stream_init (stream, string)
  call lexer_assign_stream (lexer, stream)
  call lex (lexeme, lexer)
  type = lexeme_get_string (lexeme)
  call lex (lexeme, lexer)
  key = lexeme_get_contents (lexeme)
  call stream_final (stream)
  if (trim (key) /= "") then
    select case (type)
      case ("IG"); call syntax_rule_init (rule, key, S_IGNORE)
      case ("LO"); call syntax_rule_init (rule, key, S_LOGICAL)
      case ("IN"); call syntax_rule_init (rule, key, S_INTEGER)
      case ("RE"); call syntax_rule_init (rule, key, S_REAL)
      case ("CO"); call syntax_rule_init (rule, key, S_COMPLEX)
      case ("ID"); call syntax_rule_init (rule, key, S_IDENTIFIER)
      case ("KE"); call syntax_rule_init (rule, key, S_KEYWORD)
      case ("QU"); call syntax_rule_init (rule, key, S_QUOTED)
      case ("SE"); call syntax_rule_init (rule, key, S_SEQUENCE)
      case ("GR"); call syntax_rule_init (rule, key, S_GROUP)
      case ("LI"); call syntax_rule_init (rule, key, S_LIST)
      case ("AR"); call syntax_rule_init (rule, key, S_ARGS)
      case ("AL"); call syntax_rule_init (rule, key, S_ALTERNATIVE)
      case default
        call lexer_show_location (lexer)
        call msg_bug (" Syntax definition: unknown type ' " // type // "'")
    end select
  end if
end subroutine

```

```

else
    print *, char (string)
    call msg_bug (" Syntax definition: empty rule key")
end if
end subroutine set_rule_type_and_key

```

This function returns the number of tokens in an input line.

(Syntax: subroutines)+≡

```

function get_n_token (string, lexer) result (n)
    integer :: n
    type(string_t), intent(in) :: string
    type(lexer_t), intent(inout) :: lexer
    type(stream_t), target :: stream
    type(lexeme_t) :: lexeme
    integer :: i
    call lexer_clear (lexer)
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    i = 0
    do
        call lex (lexeme, lexer)
        if (lexeme_is_break (lexeme)) exit
        i = i + 1
    end do
    n = i
    call stream_final (stream)
end function get_n_token

```

This subroutine extracts the rule contents for an input line. There are three tasks: (1) determine the number of children, depending on the rule type; (2) find and set the separator and delimiter strings, if required; (3) scan the child rules, find them in the syntax table and associate the parent rule with them.

(Syntax: subroutines)+≡

```

subroutine set_rule_contents (rule, syntax, n_token, string, lexer)
    type(syntax_rule_t), intent(inout) :: rule
    type(syntax_t), intent(in), target :: syntax
    integer, intent(in) :: n_token
    type(string_t), intent(in) :: string
    type(lexer_t), intent(inout) :: lexer
    type(stream_t), target :: stream
    type(lexeme_t), dimension(n_token) :: lexeme
    integer :: i, n_children
    call lexer_clear (lexer)
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    do i = 1, n_token
        call lex (lexeme(i), lexer)
    end do
    call stream_final (stream)
    n_children = get_n_children ()
    call set_delimiters
    if (n_children > 1) call set_separator
    if (n_children > 0) call set_children

```

```

contains
function get_n_children () result (n_children)
integer :: n_children
select case (rule%type)
case (S_QUOTED)
if (n_token /= 6) call broken_rule (rule)
n_children = 0
case (S_GROUP)
if (n_token /= 6) call broken_rule (rule)
n_children = 1
case (S_SEQUENCE)
if (is_modifier (lexeme_get_string (lexeme(n_token)))) then
if (n_token <= 4) call broken_rule (rule)
call syntax_rule_set_modifier &
(rule, lexeme_get_string (lexeme(n_token)))
n_children = n_token - 4
else
if (n_token <= 3) call broken_rule (rule)
n_children = n_token - 3
end if
case (S_LIST)
if (is_modifier (lexeme_get_string (lexeme(n_token)))) then
if (n_token <= 4 .or. mod (n_token, 2) /= 1) &
call broken_rule (rule)
call syntax_rule_set_modifier &
(rule, lexeme_get_string (lexeme(n_token)))
else if (n_token <= 3 .or. mod (n_token, 2) /= 0) then
call broken_rule (rule)
end if
n_children = (n_token - 2) / 2
case (S_ARGS)
if (is_modifier (lexeme_get_string (lexeme(n_token-1)))) then
if (n_token <= 6 .or. mod (n_token, 2) /= 1) &
call broken_rule (rule)
call syntax_rule_set_modifier &
(rule, lexeme_get_string (lexeme(n_token-1)))
else if (n_token <= 5 .or. mod (n_token, 2) /= 0) then
call broken_rule (rule)
end if
n_children = (n_token - 4) / 2
case (S_ALTERNATIVE)
if (n_token <= 3 .or. mod (n_token, 2) /= 0) call broken_rule (rule)
n_children = (n_token - 2) / 2
end select
end function get_n_children
subroutine set_delimiters
type(string_t), dimension(2) :: delimiter
select case (rule%type)
case (S_QUOTED, S_GROUP, S_ARGS)
delimiter(1) = lexeme_get_contents (lexeme(4))
delimiter(2) = lexeme_get_contents (lexeme(n_token))
call syntax_rule_set_delimiter (rule, delimiter)
end select
end subroutine set_delimiters

```

```

subroutine set_separator
  type(string_t) :: separator
  select case (rule%type)
  case (S_LIST)
    separator = lexeme_get_contents (lexeme(5))
    call syntax_rule_set_separator (rule, separator)
  case (S_ARGS)
    separator = lexeme_get_contents (lexeme(6))
    call syntax_rule_set_separator (rule, separator)
  end select
end subroutine set_separator
subroutine set_children
  allocate (rule%child(n_children))
  select case (rule%type)
  case (S_GROUP)
    call syntax_rule_set_sub (rule, 1, syntax_get_rule_ptr (syntax, &
      lexeme_get_contents (lexeme(5))))
  case (S_SEQUENCE)
    do i = 1, n_children
      call syntax_rule_set_sub (rule, i, syntax_get_rule_ptr (syntax, &
        lexeme_get_contents (lexeme(i+3))))
    end do
  case (S_LIST, S_ALTERNATIVE)
    do i = 1, n_children
      call syntax_rule_set_sub (rule, i, syntax_get_rule_ptr (syntax, &
        lexeme_get_contents (lexeme(2*i+2))))
    end do
  case (S_ARGS)
    do i = 1, n_children
      call syntax_rule_set_sub (rule, i, syntax_get_rule_ptr (syntax, &
        lexeme_get_contents (lexeme(2*i+3))))
    end do
  end select
end subroutine set_children
subroutine broken_rule (rule)
  type(syntax_rule_t), intent(in) :: rule
  call lexer_show_location (lexer)
  call msg_bug (" Syntax definition: broken rule '" &
    // char (wkey (rule)) // "'")
end subroutine broken_rule
end subroutine set_rule_contents

```

This routine completes the syntax table object. We assume that the rule array is set up. We associate the top rule with the first entry in the rule array and build up the keyword list.

The keyword list includes delimiters and separators. Filling it can only be done after all rules are set. We scan the rule tree. For each keyword that we find, we try to add it to the keyword list; the pointer to the last element is carried along with the recursive scanning. Before appending a keyword, we check whether it is already in the list.

<Syntax: subroutines>+≡

```

subroutine syntax_make_keyword_list (syntax)
  type(syntax_t), intent(inout), target :: syntax

```

```

type(syntax_rule_t), pointer :: rule
rule => syntax%rule(1)
call rule_scan_rec (rule, syntax%keyword_list)
contains
recursive subroutine rule_scan_rec (rule, keyword_list)
  type(syntax_rule_t), pointer :: rule
  type(keyword_list_t), intent(inout) :: keyword_list
  integer :: i
  if (rule%used) return
  rule%used = .true.
  select case (rule%type)
  case (S_UNKNOWN)
    call msg_bug (" Syntax: rule tree contains undefined rule")
  case (S_KEYWORD)
    call keyword_list_add (keyword_list, rule%keyword)
  end select
  select case (rule%type)
  case (S_LIST, S_ARGS)
    call keyword_list_add (keyword_list, rule%separator)
  end select
  select case (rule%type)
  case (S_GROUP, S_ARGS)
    call keyword_list_add (keyword_list, rule%delimiter_left)
    call keyword_list_add (keyword_list, rule%delimiter_right)
  end select
  select case (rule%type)
  case (S_SEQUENCE, S_GROUP, S_LIST, S_ARGS, S_ALTERNATIVE)
    if (.not. allocated (rule%child)) &
      call msg_bug (" Syntax: Non-terminal rule without children")
  case default
    if (allocated (rule%child)) &
      call msg_bug (" Syntax: Terminal rule with children")
  end select
  if (allocated (rule%child)) then
    do i = 1, size (rule%child)
      call rule_scan_rec (rule%child(i)%p, keyword_list)
    end do
  end if
end subroutine rule_scan_rec
end subroutine syntax_make_keyword_list

```

The finalizer deallocates the rule pointer array and deletes the keyword list.

(Syntax: subroutines)+≡

```

subroutine syntax_final (syntax)
  type(syntax_t), intent(inout) :: syntax
  if (allocated (syntax%rule)) deallocate (syntax%rule)
  call keyword_list_final (syntax%keyword_list)
end subroutine syntax_final

```

7.3.6 Accessing the syntax table

Return a pointer to the top rule

```

<Syntax: public>+≡
    public :: syntax_get_top_rule_ptr

<Syntax: subroutines>+≡
    function syntax_get_top_rule_ptr (syntax) result (rule)
        type(syntax_rule_t), pointer :: rule
        type(syntax_t), intent(in), target :: syntax
        if (allocated (syntax%rule)) then
            rule => syntax%rule(1)
        else
            rule => null ()
        end if
    end function syntax_get_top_rule_ptr

```

Assign the pointer to the rule associated with a given key (assumes that the rule array is allocated)

```

<Syntax: public>+≡
    public :: syntax_get_rule_ptr

<Syntax: subroutines>+≡
    function syntax_get_rule_ptr (syntax, key) result (rule)
        type(syntax_rule_t), pointer :: rule
        type(syntax_t), intent(in), target :: syntax
        type(string_t), intent(in) :: key
        integer :: i
        do i = 1, size (syntax%rule)
            if (syntax%rule(i)%keyword == key) then
                rule => syntax%rule(i)
                return
            end if
        end do
        call msg_bug (" Syntax table: Rule " // char (key) // " not found")
    end function syntax_get_rule_ptr

```

Return a pointer to the keyword list

```

<Syntax: public>+≡
    public :: syntax_get_keyword_list_ptr

<Syntax: subroutines>+≡
    function syntax_get_keyword_list_ptr (syntax) result (keyword_list)
        type(keyword_list_t), pointer :: keyword_list
        type(syntax_t), intent(in), target :: syntax
        keyword_list => syntax%keyword_list
    end function syntax_get_keyword_list_ptr

```

7.3.7 I/O

Write a readable representation of the syntax table

```

<Syntax: public>+≡
    public :: syntax_write

```

```

<Syntax: subroutines>+=
subroutine syntax_write (syntax, unit)
  type(syntax_t), intent(in) :: syntax
  integer, intent(in), optional :: unit
  integer :: u
  integer :: i
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(A)") "Syntax table:"
  if (allocated (syntax%rule)) then
    do i = 1, size (syntax%rule)
      call syntax_rule_write (syntax%rule(i), u)
    end do
  else
    write (u, "(1x,A)") "[not allocated]"
  end if
  call keyword_list_write (syntax%keyword_list, u)
end subroutine syntax_write

```

7.4 The parser

On a small scale, the parser interprets the string tokens returned by the lexer; they are interpreted as numbers, keywords and such and stored as a typed object. On a large scale, a text is read, parsed, and a syntax rule set is applied such that the tokens are stored as a parse tree. Syntax errors are spotted in this process, so the resulting parse tree is syntactically correct by definition.

```
<parser.f90>≡  
  <File header>  
  
  module parser  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use format_defs, only: FMT_19  
    use unit_tests  
    use system_defs, only: DIGITS  
    use diagnostics  
    use md5  
    use lexers  
    use syntax_rules  
  
    <Standard module head>  
  
    <Parser: public>  
  
    <Parser: types>  
  
    <Parser: interfaces>  
  
    contains  
  
    <Parser: procedures>  
  
    <Parser: tests>  
  
  end module parser
```

7.4.1 The token type

Tokens are elements of the parsed input that carry a value: logical, integer, real, quoted string, (unquoted) identifier, or known keyword. Note that non-keyword tokens also have an abstract key attached to them.

This is an obvious candidate for polymorphism.

```
<Parser: types>≡  
  type :: token_t  
    private  
    integer :: type = S_UNKNOWN  
    logical, pointer :: lval => null ()  
    integer, pointer :: ival => null ()  
    real(default), pointer :: rval => null ()
```



```

        complex(default), pointer :: cval => null ()
        type(string_t), pointer :: sval => null ()
        type(string_t), pointer :: kval => null ()
        type(string_t), dimension(:), pointer :: quote => null ()
    end type token_t

```

Create a token from the lexeme returned by the lexer: Allocate storage and try to interpret the lexeme according to the type that is requested by the parser. For a keyword token, match the lexeme against the requested key. If successful, set the token type, value, and key. Otherwise, set the type to S_UNKNOWN.

(Parser: procedures)≡

```

subroutine token_init (token, lexeme, requested_type, key)
    type(token_t), intent(out) :: token
    type(lexeme_t), intent(in) :: lexeme
    integer, intent(in) :: requested_type
    type(string_t), intent(in) :: key
    integer :: type
    type = lexeme_get_type (lexeme)
    token%type = S_UNKNOWN
    select case (requested_type)
    case (S_LOGICAL)
        if (type == T_IDENTIFIER) call read_logical &
            (char (lexeme_get_string (lexeme)))
    case (S_INTEGER)
        if (type == T_NUMERIC) call read_integer &
            (char (lexeme_get_string (lexeme)))
    case (S_REAL)
        if (type == T_NUMERIC) call read_real &
            (char (lexeme_get_string (lexeme)))
    case (S_COMPLEX)
        if (type == T_NUMERIC) call read_complex &
            (char (lexeme_get_string (lexeme)))
    case (S_IDENTIFIER)
        if (type == T_IDENTIFIER) call read_identifier &
            (lexeme_get_string (lexeme))
    case (S_KEYWORD)
        if (type == T_KEYWORD) call check_keyword &
            (lexeme_get_string (lexeme), key)
    case (S_QUOTED)
        if (type == T_QUOTED) call read_quoted &
            (lexeme_get_contents (lexeme), lexeme_get_delimiters (lexeme))
    case default
        print *, requested_type
        call msg_bug (" Invalid token type code requested by the parser")
    end select
    if (token%type /= S_UNKNOWN) then
        allocate (token%kval)
        token%kval = key
    end if
contains
subroutine read_logical (s)
    character(*), intent(in) :: s
    select case (s)

```

```

case ("t", "T", "true", "TRUE", "y", "Y", "yes", "YES")
    allocate (token%lval)
    token%lval = .true.
    token%type = S_LOGICAL
case ("f", "F", "false", "FALSE", "n", "N", "no", "NO")
    allocate (token%lval)
    token%lval = .false.
    token%type = S_LOGICAL
end select
end subroutine read_logical
subroutine read_integer (s)
    character(*), intent(in) :: s
    integer :: tmp, iostat
    if (verify (s, DIGITS) == 0) then
        read (s, *, iostat=iostat) tmp
        if (iostat == 0) then
            allocate (token%ival)
            token%ival = tmp
            token%type = S_INTEGER
        end if
    end if
end subroutine read_integer
subroutine read_real (s)
    character(*), intent(in) :: s
    real(default) :: tmp
    integer :: iostat
    read (s, *, iostat=iostat) tmp
    if (iostat == 0) then
        allocate (token%rval)
        token%rval = tmp
        token%type = S_REAL
    end if
end subroutine read_real
subroutine read_complex (s)
    character(*), intent(in) :: s
    complex(default) :: tmp
    integer :: iostat
    read (s, *, iostat=iostat) tmp
    if (iostat == 0) then
        allocate (token%cval)
        token%cval = tmp
        token%type = S_COMPLEX
    end if
end subroutine read_complex
subroutine read_identifier (s)
    type(string_t), intent(in) :: s
    allocate (token%sval)
    token%sval = s
    token%type = S_IDENTIFIER
end subroutine read_identifier
subroutine check_keyword (s, key)
    type(string_t), intent(in) :: s
    type(string_t), intent(in) :: key
    if (key == s) token%type = S_KEYWORD

```

```

end subroutine check_keyword
subroutine read_quoted (s, del)
  type(string_t), intent(in) :: s
  type(string_t), dimension(2), intent(in) :: del
  allocate (token%sval, token%quote(2))
  token%sval = s
  token%quote(1) = del(1)
  token%quote(2) = del(2)
  token%type = S_QUOTED
end subroutine read_quoted
end subroutine token_init

```

Manually set a token to a keyword.

```

(Parser: procedures)+≡
subroutine token_init_key (token, key)
  type(token_t), intent(out) :: token
  type(string_t), intent(in) :: key
  token%type = S_KEYWORD
  allocate (token%kval)
  token%kval = key
end subroutine token_init_key

```

Reset a token to an empty state, freeing allocated memory, and deallocate the token itself.

```

(Parser: procedures)+≡
subroutine token_final (token)
  type(token_t), intent(inout) :: token
  token%type = S_UNKNOWN
  if (associated (token%lval)) deallocate (token%lval)
  if (associated (token%ival)) deallocate (token%ival)
  if (associated (token%rval)) deallocate (token%rval)
  if (associated (token%sval)) deallocate (token%sval)
  if (associated (token%kval)) deallocate (token%kval)
  if (associated (token%quote)) deallocate (token%quote)
end subroutine token_final

```

Check for empty=valid token:

```

(Parser: procedures)+≡
function token_is_valid (token) result (valid)
  logical :: valid
  type(token_t), intent(in) :: token
  valid = token%type /= S_UNKNOWN
end function token_is_valid

```

Write the contents of a token.

```

(Parser: procedures)+≡
subroutine token_write (token, unit)
  type(token_t), intent(in) :: token
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  select case (token%type)

```

```

case (S_LOGICAL)
    write (u, "(L1)") token%lval
case (S_INTEGER)
    write (u, "(I0)") token%ival
case (S_REAL)
    write (u, "(" // FMT_19 // ")") token%rval
case (S_COMPLEX)
    write (u, "('('," // FMT_19 // ",','," // FMT_19 // ",')')") token%cval
case (S_IDENTIFIER)
    write (u, "(A)") char (token%sval)
case (S_KEYWORD)
    write (u, "(A,A)") '[keyword]' // char (token%kval)
case (S_QUOTED)
    write (u, "(A)") &
        char (token%quote(1)) // char (token%sval) // char (token%quote(2))
case default
    write (u, "(A)") '[empty]'
end select
end subroutine token_write

```

Token assignment via deep copy. This is useful to avoid confusion when the token is transferred to some parse-tree node.

```

(Parser: interfaces)≡
interface assignment(=)
    module procedure token_assign
    module procedure token_assign_integer
    module procedure token_assign_real
    module procedure token_assign_complex
    module procedure token_assign_logical
    module procedure token_assign_string
end interface

```

We need to copy only the contents that are actually assigned, the other pointers remain disassociated.

```

(Parser: procedures)+≡
subroutine token_assign (token, token_in)
    type(token_t), intent(out) :: token
    type(token_t), intent(in) :: token_in
    token%type = token_in%type
    select case (token%type)
    case (S_LOGICAL);    allocate (token%lval); token%lval = token_in%lval
    case (S_INTEGER);    allocate (token%ival); token%ival = token_in%ival
    case (S_REAL);       allocate (token%rval); token%rval = token_in%rval
    case (S_COMPLEX);    allocate (token%cval); token%cval = token_in%cval
    case (S_IDENTIFIER); allocate (token%sval); token%sval = token_in%sval
    case (S_QUOTED);     allocate (token%sval); token%sval = token_in%sval
                        allocate (token%quote(2)); token%quote = token_in%quote
    end select
    if (token%type /= S_UNKNOWN) then
        allocate (token%kval); token%kval = token_in%kval
    end if
end subroutine token_assign

```

We need to copy only the contents that are actually assigned, the other pointers remain disassociated.

(Parser: procedures)+≡

```

subroutine token_assign_integer (token, ival)
  type(token_t), intent(out) :: token
  integer, intent(in) :: ival
  token%type = S_INTEGER
  allocate (token%ival)
  token%ival = ival
end subroutine token_assign_integer

subroutine token_assign_real (token, rval)
  type(token_t), intent(out) :: token
  real(default), intent(in) :: rval
  token%type = S_REAL
  allocate (token%rval)
  token%rval = rval
end subroutine token_assign_real

subroutine token_assign_complex (token, cval)
  type(token_t), intent(out) :: token
  complex(default), intent(in) :: cval
  token%type = S_COMPLEX
  allocate (token%cval)
  token%cval = cval
end subroutine token_assign_complex

subroutine token_assign_logical (token, lval)
  type(token_t), intent(out) :: token
  logical, intent(in) :: lval
  token%type = S_LOGICAL
  allocate (token%lval)
  token%lval = lval
end subroutine token_assign_logical

subroutine token_assign_string (token, sval)
  type(token_t), intent(out) :: token
  type(string_t), intent(in) :: sval
  token%type = S_QUOTED
  allocate (token%sval)
  token%sval = sval
  allocate (token%quote(2)); token%quote = ''
end subroutine token_assign_string

```

7.4.2 Retrieve token contents

These functions all do a trivial sanity check that should avoid crashes.

(Parser: procedures)+≡

```

function token_get_logical (token) result (lval)
  logical :: lval
  type(token_t), intent(in) :: token
  if (associated (token%lval)) then

```

```

        lval = token%lval
    else
        call token_mismatch (token, "logical")
    end if
end function token_get_logical

function token_get_integer (token) result (ival)
    integer :: ival
    type(token_t), intent(in) :: token
    if (associated (token%ival)) then
        ival = token%ival
    else
        call token_mismatch (token, "integer")
    end if
end function token_get_integer

function token_get_real (token) result (rval)
    real(default) :: rval
    type(token_t), intent(in) :: token
    if (associated (token%rval)) then
        rval = token%rval
    else
        call token_mismatch (token, "real")
    end if
end function token_get_real

function token_get_cmplx (token) result (cval)
    complex(default) :: cval
    type(token_t), intent(in) :: token
    if (associated (token%cval)) then
        cval = token%cval
    else
        call token_mismatch (token, "complex")
    end if
end function token_get_cmplx

function token_get_string (token) result (sval)
    type(string_t) :: sval
    type(token_t), intent(in) :: token
    if (associated (token%sval)) then
        sval = token%sval
    else
        call token_mismatch (token, "string")
    end if
end function token_get_string

function token_get_key (token) result (kval)
    type(string_t) :: kval
    type(token_t), intent(in) :: token
    if (associated (token%kval)) then
        kval = token%kval
    else
        call token_mismatch (token, "keyword")
    end if
end if

```

```

end function token_get_key

function token_get_quote (token) result (quote)
  type(string_t), dimension(2) :: quote
  type(token_t), intent(in) :: token
  if (associated (token%quote)) then
    quote = token%quote
  else
    call token_mismatch (token, "quote")
  end if
end function token_get_quote

```

```

(Parser: procedures)+≡
subroutine token_mismatch (token, type)
  type(token_t), intent(in) :: token
  character(*), intent(in) :: type
  write (6, "(A)", advance="no") "Token: "
  call token_write (token)
  call msg_bug (" Token type mismatch; value required as " // type)
end subroutine token_mismatch

```

7.4.3 The parse tree: nodes

The parser will generate a parse tree from the input stream. Each node in this parse tree points to the syntax rule that was applied. (Since syntax rules are stored in a pointer-type array within the syntax table, they qualify as targets.) A leaf node contains a token. A branch node has subnodes. The subnodes are stored as a list, so each node also has a `next` pointer.

```

(Parser: public)≡
public :: parse_node_t

(Parser: types)+≡
type :: parse_node_t
private
  type(syntax_rule_t), pointer :: rule => null ()
  type(token_t) :: token
  integer :: n_sub = 0
  type(parse_node_t), pointer :: sub_first => null ()
  type(parse_node_t), pointer :: sub_last => null ()
  type(parse_node_t), pointer :: next => null ()
contains
  (Parser: parse node: TBP)
end type parse_node_t

```

Container for parse node pointers, useful for creating pointer arrays:

```

(Parser: public)+≡
public :: parse_node_p

(Parser: types)+≡
type :: parse_node_p
  type(parse_node_t), pointer :: ptr => null ()
end type parse_node_p

```

Output. The first version writes a node together with its sub-node tree, organized by indentation.

```

(Parser: parse node: TBP)≡
    procedure :: write => parse_node_write_rec

(Parser: public)+≡
    public :: parse_node_write_rec

(Parser: procedures)+≡
    recursive subroutine parse_node_write_rec (node, unit, short, depth)
        class(parse_node_t), intent(in), target :: node
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: short
        integer, intent(in), optional :: depth
        integer :: u, d
        type(parse_node_t), pointer :: current
        u = given_output_unit (unit); if (u < 0) return
        d = 0; if (present (depth)) d = depth
        call parse_node_write (node, u, short=short)
        current => node%sub_first
        do while (associated (current))
            write (u, "(A)", advance = "no") repeat ("| ", d)
            call parse_node_write_rec (current, unit, short, d+1)
            current => current%next
        end do
    end subroutine parse_node_write_rec

```

This does the actual output for a single node, without recursion.

```

(Parser: public)+≡
    public :: parse_node_write

(Parser: procedures)+≡
    subroutine parse_node_write (node, unit, short)
        class(parse_node_t), intent(in) :: node
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: short
        integer :: u
        type(parse_node_t), pointer :: current
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(' + ')", advance = "no")
        if (associated (node%rule)) then
            call syntax_rule_write (node%rule, u, &
                short=short, key_only=.true., advance=.false.)
        if (token_is_valid (node%token)) then
            write (u, "(' = ')", advance="no")
            call token_write (node%token, u)
        else if (associated (node%sub_first)) then
            write (u, "(' = ')", advance="no")
            current => node%sub_first
            do while (associated (current))
                call syntax_rule_write (current%rule, u, &
                    short=.true., key_only=.true., advance=.false.)
                current => current%next
            end do
        write (u, *)
    end subroutine parse_node_write

```



```

        else
            write (u, *)
        end if
    else
        write (u, *) "[empty]"
    end if
end subroutine parse_node_write

```

Finalize the token and recursively finalize and deallocate all sub-nodes.

```

<Parser: public>+≡
    public :: parse_node_final

<Parser: procedures>+≡
    recursive subroutine parse_node_final (node, recursive)
        type(parse_node_t), intent(inout) :: node
        type(parse_node_t), pointer :: current
        logical, intent(in), optional :: recursive
        logical :: rec
        rec = .true.; if (present (recursive)) rec = recursive
        call token_final (node%token)
        if (rec) then
            do while (associated (node%sub_first))
                current => node%sub_first
                node%sub_first => node%sub_first%next
                call parse_node_final (current)
                deallocate (current)
            end do
        end if
    end subroutine parse_node_final

```

7.4.4 Filling nodes

The constructors allocate and initialize the node. There are two possible initializers (in a later version, should correspond to different type extensions).

First, leaf (terminal) nodes. The token constructor does the actual work, looking at the requested type and key for the given rule and matching against the lexeme contents. If it fails, the token will keep the type `S_UNKNOWN` and remain empty. Otherwise, we have a valid node which contains the new token.

If the lexeme argument is absent, the token is left empty.

```

<Parser: procedures>+≡
    subroutine parse_node_create_leaf (node, rule, lexeme)
        type(parse_node_t), pointer :: node
        type(syntax_rule_t), intent(in), target :: rule
        type(lexeme_t), intent(in) :: lexeme
        allocate (node)
        node%rule => rule
        call token_init (node%token, lexeme, &
            syntax_rule_get_type (rule), syntax_rule_get_key (rule))
        if (.not. token_is_valid (node%token)) deallocate (node)
    end subroutine parse_node_create_leaf

```

This version allows us to manually create a leaf node that holds a keyword.

```

(Parser: public)+≡
    public :: parse_node_create_key

(Parser: procedures)+≡
    subroutine parse_node_create_key (node, rule)
        type(parse_node_t), intent(out) :: node
        type(syntax_rule_t), intent(in), target :: rule
        node%rule => rule
        call token_init_key (node%token, syntax_rule_get_key (rule))
    end subroutine parse_node_create_key

```

This version allows us to manually create a leaf node that holds a fixed value.
Only one of the optional values should be provided.

```

(Parser: public)+≡
    public :: parse_node_create_value

(Parser: procedures)+≡
    subroutine parse_node_create_value (node, rule, ival, rval, cval, sval, lval)
        type(parse_node_t), intent(out) :: node
        type(syntax_rule_t), intent(in), target :: rule
        integer, intent(in), optional :: ival
        real(default), intent(in), optional :: rval
        complex(default), intent(in), optional :: cval
        type(string_t), intent(in), optional :: sval
        logical, intent(in), optional :: lval
        node%rule => rule
        call parse_node_set_value (node, ival, rval, cval, sval, lval)
    end subroutine parse_node_create_value

```

Directly set the value without changing anything else.

```

(Parser: public)+≡
    public :: parse_node_set_value

(Parser: procedures)+≡
    subroutine parse_node_set_value (node, ival, rval, cval, sval, lval)
        type(parse_node_t), intent(inout) :: node
        integer, intent(in), optional :: ival
        real(default), intent(in), optional :: rval
        complex(default), intent(in), optional :: cval
        type(string_t), intent(in), optional :: sval
        logical, intent(in), optional :: lval
        if (present (ival)) then
            node%token = ival
        else if (present (rval)) then
            node%token = rval
        else if (present (cval)) then
            node%token = cval
        else if (present (lval)) then
            node%token = lval
        else if (present (sval)) then
            node%token = sval
        end if
    end subroutine parse_node_set_value

```

Second, branch nodes. We first assign the rule:

```

(Parser: public)+≡
    public :: parse_node_create_branch

(Parser: procedures)+≡
    subroutine parse_node_create_branch (node, rule)
        type(parse_node_t), pointer :: node
        type(syntax_rule_t), intent(in), target :: rule
        allocate (node)
        node%rule => rule
    end subroutine parse_node_create_branch

```

Append a sub-node. The sub-node must exist and be a valid target, otherwise nothing is done.

```

(Parser: public)+≡
    public :: parse_node_append_sub

(Parser: procedures)+≡
    subroutine parse_node_append_sub (node, sub)
        type(parse_node_t), intent(inout) :: node
        type(parse_node_t), pointer :: sub
        if (associated (sub)) then
            if (associated (node%sub_last)) then
                node%sub_last%next => sub
            else
                node%sub_first => sub
            end if
            node%sub_last => sub
        end if
    end subroutine parse_node_append_sub

```

For easy access, once the list is complete we count the number of sub-nodes. If there are no subnodes, the whole node is deleted.

```

(Parser: public)+≡
    public :: parse_node_freeze_branch

(Parser: procedures)+≡
    subroutine parse_node_freeze_branch (node)
        type(parse_node_t), pointer :: node
        type(parse_node_t), pointer :: current
        node%n_sub = 0
        current => node%sub_first
        do while (associated (current))
            node%n_sub = node%n_sub + 1
            current => current%next
        end do
        if (node%n_sub == 0) deallocate (node)
    end subroutine parse_node_freeze_branch

```

Replace the syntax rule. This makes sense only if the parse node adheres to the syntax of the new rule.

```

(Parser: public)+≡
    public :: parse_node_replace_rule

```

```

(Parser: procedures)+≡
  subroutine parse_node_replace_rule (node, rule)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    node%rule => rule
  end subroutine parse_node_replace_rule

```

Replace the last subnode by the target node. Since the subnodes are stored as a linked list, we can do this only if we copy the subnodes. Furthermore, the target node must also be copied, and the `next` pointer of the copy is nullified. This ensures that we cannot modify the originals at the subnode level.

All copies are shallow copies. This implies that further modifications at the sub-subnode level will affect the original nodes and must therefore be forbidden.

Use with care, this invites to memory mismanagement. The copy nodes can be deallocated, but not finalized, since its subnodes are the same objects as the subnodes of the target node.

```

(Parser: public)+≡
  public :: parse_node_replace_last_sub

(Parser: procedures)+≡
  subroutine parse_node_replace_last_sub (node, pn_target)
    type(parse_node_t), intent(inout), target :: node
    type(parse_node_t), intent(in), target :: pn_target
    type(parse_node_t), pointer :: current, current_copy, previous
    integer :: i
    select case (node%n_sub)
    case (1)
      allocate (current_copy)
      current_copy = pn_target
      node%sub_first => current_copy
    case (2:)
      current => node%sub_first
      allocate (current_copy)
      current_copy = current
      node%sub_first => current_copy
      previous => current_copy
      do i = 1, node%n_sub - 2
        current => current%next
        allocate (current_copy)
        current_copy = current
        previous%next => current_copy
        previous => current_copy
      end do
      allocate (current_copy)
      current_copy = pn_target
      previous%next => current_copy
    case default
      call parse_node_write (node)
      call msg_bug ("replace_last_sub' called for non-branch parse node")
    end select
    current_copy%next => null ()
    node%sub_last => current_copy
  end subroutine parse_node_replace_last_sub

```

7.4.5 Accessing nodes

Return the node contents. Check if pointers are associated. No check when accessing a sub-node; assume that `parse_node_n_sub` is always used for the upper bound.

The token extractor returns a pointer.

```
(Parser: public)+≡
  public :: parse_node_get_rule_ptr
  public :: parse_node_get_n_sub
  public :: parse_node_get_sub_ptr
  public :: parse_node_get_next_ptr
  public :: parse_node_get_last_sub_ptr

(Parser: parse node: TBP)+≡
  procedure :: get_rule_ptr => parse_node_get_rule_ptr
  procedure :: get_n_sub => parse_node_get_n_sub
  procedure :: get_sub_ptr => parse_node_get_sub_ptr
  procedure :: get_next_ptr => parse_node_get_next_ptr

(Parser: procedures)+≡
  function parse_node_get_rule_ptr (node) result (rule)
    class(parse_node_t), intent(in) :: node
    type(syntax_rule_t), pointer :: rule
    if (associated (node%rule)) then
      rule => node%rule
    else
      rule => null ()
      call parse_node_undefined (node, "rule")
    end if
  end function parse_node_get_rule_ptr

  function parse_node_get_n_sub (node) result (n)
    class(parse_node_t), intent(in) :: node
    integer :: n
    n = node%n_sub
  end function parse_node_get_n_sub

  function parse_node_get_sub_ptr (node, n, tag, required) result (sub)
    class(parse_node_t), intent(in), target :: node
    type(parse_node_t), pointer :: sub
    integer, intent(in), optional :: n
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    integer :: i
    sub => node%sub_first
    if (present (n)) then
      do i = 2, n
        if (associated (sub)) then
          sub => sub%next
        else
          return
        end if
      end do
    end if
```

```

        end do
    end if
    call parse_node_check (sub, tag, required)
end function parse_node_get_sub_ptr

function parse_node_get_next_ptr (sub, n, tag, required) result (next)
    class(parse_node_t), intent(in), target :: sub
    type(parse_node_t), pointer :: next
    integer, intent(in), optional :: n
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    integer :: i
    next => sub%next
    if (present (n)) then
        do i = 2, n
            if (associated (next)) then
                next => next%next
            else
                exit
            end if
        end do
    end if
    call parse_node_check (next, tag, required)
end function parse_node_get_next_ptr

function parse_node_get_last_sub_ptr (node, tag, required) result (sub)
    type(parse_node_t), pointer :: sub
    type(parse_node_t), intent(in), target :: node
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    sub => node%sub_last
    call parse_node_check (sub, tag, required)
end function parse_node_get_last_sub_ptr

<Parser: procedures>+≡
subroutine parse_node_undefined (node, obj)
    type(parse_node_t), intent(in) :: node
    character(*), intent(in) :: obj
    call parse_node_write (node, 6)
    call msg_bug (" Parse-tree node: " // obj // " requested, but undefined")
end subroutine parse_node_undefined

```

Check if a parse node has a particular tag, and if it is associated:

```

<Parser: public>+≡
    public :: parse_node_check

<Parser: procedures>+≡
subroutine parse_node_check (node, tag, required)
    type(parse_node_t), pointer :: node
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    if (associated (node)) then
        if (present (tag)) then
            if (parse_node_get_rule_key (node) /= tag) &

```

```

        call parse_node_mismatch (tag, node)
    end if
else
    if (present (required)) then
        if (required) &
            call msg_bug (" Missing node, expected <" // tag // ">")
        end if
    end if
end if
end subroutine parse_node_check

```

This is called by a parse-tree scanner if the expected and the actual nodes do not match

```

(Parser: public)+≡
    public :: parse_node_mismatch

(Parser: procedures)+≡
    subroutine parse_node_mismatch (string, parse_node)
        character(*), intent(in) :: string
        type(parse_node_t), intent(in) :: parse_node
        call parse_node_write (parse_node)
        call msg_bug (" Syntax mismatch, expected <" // string // ">.")
    end subroutine parse_node_mismatch

```

The following functions are wrappers for extracting the token contents.

```

(Parser: public)+≡
    public :: parse_node_get_logical
    public :: parse_node_get_integer
    public :: parse_node_get_real
    public :: parse_node_get_cmplx
    public :: parse_node_get_string
    public :: parse_node_get_key
    public :: parse_node_get_rule_key

(Parser: parse node: TBP)+≡
    procedure :: get_logical => parse_node_get_logical
    procedure :: get_integer => parse_node_get_integer
    procedure :: get_real => parse_node_get_real
    procedure :: get_cmplx => parse_node_get_cmplx
    procedure :: get_string => parse_node_get_string

(Parser: procedures)+≡
    function parse_node_get_logical (node) result (lval)
        class(parse_node_t), intent(in), target :: node
        logical :: lval
        lval = token_get_logical (parse_node_get_token_ptr (node))
    end function parse_node_get_logical

    function parse_node_get_integer (node) result (ival)
        class(parse_node_t), intent(in), target :: node
        integer :: ival
        ival = token_get_integer (parse_node_get_token_ptr (node))
    end function parse_node_get_integer

    function parse_node_get_real (node) result (rval)

```

```

class(parse_node_t), intent(in), target :: node
real(default) :: rval
rval = token_get_real (parse_node_get_token_ptr (node))
end function parse_node_get_real

function parse_node_get_cmplx (node) result (cval)
class(parse_node_t), intent(in), target :: node
complex(default) :: cval
cval = token_get_cmplx (parse_node_get_token_ptr (node))
end function parse_node_get_cmplx

function parse_node_get_string (node) result (sval)
class(parse_node_t), intent(in), target :: node
type(string_t) :: sval
sval = token_get_string (parse_node_get_token_ptr (node))
end function parse_node_get_string

function parse_node_get_key (node) result (kval)
type(string_t) :: kval
type(parse_node_t), intent(in), target :: node
kval = token_get_key (parse_node_get_token_ptr (node))
end function parse_node_get_key

function parse_node_get_rule_key (node) result (kval)
type(string_t) :: kval
type(parse_node_t), intent(in), target :: node
kval = syntax_rule_get_key (parse_node_get_rule_ptr (node))
end function parse_node_get_rule_key

function parse_node_get_token_ptr (node) result (token)
type(token_t), pointer :: token
type(parse_node_t), intent(in), target :: node
if (token_is_valid (node%token)) then
token => node%token
else
call parse_node_undefined (node, "token")
end if
end function parse_node_get_token_ptr

```

Return a MD5 sum for a parse node. The method is to write the node to a scratch file and to evaluate the MD5 sum of that file.

```

(Parser: public)+≡
public :: parse_node_get_md5sum

(Parser: procedures)+≡
function parse_node_get_md5sum (pn) result (md5sum_pn)
character(32) :: md5sum_pn
type(parse_node_t), intent(in) :: pn
integer :: u
u = free_unit ()
open (unit = u, status = "scratch", action = "readwrite")
call parse_node_write_rec (pn, unit=u)
rewind (u)
md5sum_pn = md5sum (u)

```



```

        close (u)
    end function parse_node_get_md5sum

```

7.4.6 The parse tree

The parse tree is a tree of nodes, where leaf nodes hold a valid token, while branch nodes point to a list of sub-nodes.

```

<Parser: public>+≡
    public :: parse_tree_t

<Parser: types>+≡
    type :: parse_tree_t
    private
        type(parse_node_t), pointer :: root_node => null ()
    contains
        <Parser: parse tree: TBP>
    end type parse_tree_t

```

The parser. Its arguments are the parse tree (which should be empty initially), the lexer (which should be already set up), the syntax table (which should be valid), and the input stream. The input stream is completely parsed, using the lexer setup and the syntax rules as given, and the parse tree is built accordingly.

If `check_eof` is absent or true, the parser will complain about trailing garbage. Otherwise, it will ignore it.

By default, the input stream is matched against the top rule in the specified syntax. If `key` is given, it is matched against the rule with the specified key instead.

Failure at the top level means that no rule could match at all; in this case the error message will show the top rule.

```

<Parser: public>+≡
    public :: parse_tree_init

<Parser: parse tree: TBP>≡
    procedure :: parse => parse_tree_init

<Parser: procedures>+≡
    subroutine parse_tree_init &
        (parse_tree, syntax, lexer, key, check_eof)
    class(parse_tree_t), intent(inout) :: parse_tree
    type(lexer_t), intent(inout) :: lexer
    type(syntax_t), intent(in), target :: syntax
    type(string_t), intent(in), optional :: key
    logical, intent(in), optional :: check_eof
    type(syntax_rule_t), pointer :: rule
    type(lexeme_t) :: lexeme
    type(parse_node_t), pointer :: node
    logical :: ok, check
    check = .true.; if (present (check_eof)) check = check_eof
    call lexer_clear (lexer)
    if (present (key)) then
        rule => syntax_get_rule_ptr (syntax, key)
    else

```

```

        rule => syntax_get_top_rule_ptr (syntax)
    end if
    if (associated (rule)) then
        call parse_node_match_rule (node, rule, ok)
        if (ok) then
            parse_tree%root_node => node
        else
            call parse_error (rule, lexeme)
        end if
        if (check) then
            call lex (lexeme, lexer)
            if (.not. lexeme_is_eof (lexeme)) then
                call lexer_show_location (lexer)
                call msg_fatal (" Syntax error " &
                    // "(at or before the location indicated above)")
            end if
        end if
    else
        call msg_bug (" Parser failed because syntax is empty")
    end if
contains
<Parser: internal subroutines of parse_tree_init>
end subroutine parse_tree_init

```

The parser works recursively, following the rule tree, building the tree of nodes on the fly. If the given rule matches, the node is filled on return. If not, the node remains empty.

```

<Parser: internal subroutines of parse_tree_init>≡
recursive subroutine parse_node_match_rule (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    logical, parameter :: debug = .false.
    integer :: type
    if (debug) write (6, "(A)", advance="no") "Parsing rule: "
    if (debug) call syntax_rule_write (rule, 6)
    node => null ()
    type = syntax_rule_get_type (rule)
    if (syntax_rule_is_atomic (rule)) then
        call lex (lexeme, lexer)
        if (debug) write (6, "(A)", advance="no") "Token: "
        if (debug) call lexeme_write (lexeme, 6)
        call parse_node_create_leaf (node, rule, lexeme)
        ok = associated (node)
        if (.not. ok) call lexer_put_back (lexer, lexeme)
    else
        select case (type)
        case (S_ALTERNATIVE); call parse_alternative (node, rule, ok)
        case (S_GROUP);      call parse_group (node, rule, ok)
        case (S_SEQUENCE);   call parse_sequence (node, rule, .false., ok)
        case (S_LIST);       call parse_sequence (node, rule, .true., ok)
        case (S_ARGS);       call parse_args (node, rule, ok)
        case (S_IGNORE);     call parse_ignore (node, ok)

```

```

        end select
    end if
    if (debug) then
        if (ok) then
            write (6, "(A)", advance="no") "Matched rule: "
        else
            write (6, "(A)", advance="no") "Failed rule: "
        end if
        call syntax_rule_write (rule)
        if (associated (node)) call parse_node_write (node)
    end if
end subroutine parse_node_match_rule

```

Parse an alternative: try each case. If the match succeeds, the node has been filled, so return. If nothing works, return failure.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_alternative (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    integer :: i
    do i = 1, syntax_rule_get_n_sub (rule)
        call parse_node_match_rule (node, syntax_rule_get_sub_ptr (rule, i), ok)
        if (ok) return
    end do
    ok = .false.
end subroutine parse_alternative

```

Parse a group: the first and third lexemes have to be the delimiters, the second one is parsed as the actual node, using now the child rule. If the first match fails, return with failure. If the other matches fail, issue an error, since we cannot lex back more than one item.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_group (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    type(string_t), dimension(2) :: delimiter
    delimiter = syntax_rule_get_delimiter (rule)
    call lex (lexeme, lexer)
    if (lexeme_get_string (lexeme) == delimiter(1)) then
        call parse_node_match_rule (node, syntax_rule_get_sub_ptr (rule, 1), ok)
        if (ok) then
            call lex (lexeme, lexer)
            if (lexeme_get_string (lexeme) == delimiter(2)) then
                ok = .true.
            else
                call parse_error (rule, lexeme)
            end if
        else
            call parse_error (rule, lexeme)
        end if
    else
        call lexer_put_back (lexer, lexeme)
        ok = .false.
    end if
end subroutine parse_group

```

```

    end if
end subroutine parse_group

```

Parsing a sequence. The last rule element may be special: optional and/or repetitive. Each sub-node that matches is appended to the sub-node list of the parent node.

If `sep` is true, we look for a separator after each element.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_sequence (node, rule, sep, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(in) :: sep
    logical, intent(out) :: ok
    type(parse_node_t), pointer :: current
    integer :: i, n
    logical :: opt, rep, cont
    type(string_t) :: separator
    call parse_node_create_branch (node, rule)
    if (sep) separator = syntax_rule_get_separator (rule)
    n = syntax_rule_get_n_sub (rule)
    opt = syntax_rule_last_optional (rule)
    rep = syntax_rule_last_repetitive (rule)
    ok = .true.
    cont = .true.
    SCAN_RULE: do i = 1, n
        call parse_node_match_rule &
            (current, syntax_rule_get_sub_ptr (rule, i), cont)
        if (cont) then
            call parse_node_append_sub (node, current)
            if (sep .and. (i<n .or. rep)) then
                call lex (lexeme, lexer)
                if (lexeme_get_string (lexeme) /= separator) then
                    call lexer_put_back (lexer, lexeme)
                    cont = .false.
                    exit SCAN_RULE
                end if
            end if
        else
            if (i == n .and. opt) then
                exit SCAN_RULE
            else if (i == 1) then
                ok = .false.
                exit SCAN_RULE
            else
                call parse_error (rule, lexeme)
            end if
        end if
    end do SCAN_RULE
    if (rep) then
        do while (cont)
            call parse_node_match_rule &
                (current, syntax_rule_get_sub_ptr (rule, n), cont)
            if (cont) then
                call parse_node_append_sub (node, current)
            end if
        end do
    end if
end subroutine parse_sequence

```

```

        if (sep) then
            call lex (lexeme, lexer)
            if (lexeme_get_string (lexeme) /= separator) then
                call lexer_put_back (lexer, lexeme)
                cont = .false.
            end if
        end if
    else
        if (sep) call parse_error (rule, lexeme)
    end if
end do
end if
call parse_node_freeze_branch (node)
end subroutine parse_sequence

```

Argument list: We use the `parse_group` code, but call `parse_sequence` inside.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_args (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    type(string_t), dimension(2) :: delimiter
    delimiter = syntax_rule_get_delimiter (rule)
    call lex (lexeme, lexer)
    if (lexeme_get_string (lexeme) == delimiter(1)) then
        call parse_sequence (node, rule, .true., ok)
        if (ok) then
            call lex (lexeme, lexer)
            if (lexeme_get_string (lexeme) == delimiter(2)) then
                ok = .true.
            else
                call parse_error (rule, lexeme)
            end if
        else
            call parse_error (rule, lexeme)
        end if
    else
        call lexer_put_back (lexer, lexeme)
        ok = .false.
    end if
end subroutine parse_args

```

The IGNORE syntax reads one lexeme and discards it if it is numeric, logical or string/identifier (but not a keyword). This is a successful match. Otherwise, the match fails. The node pointer is returned disassociated in any case.

(Parser: internal subroutines of parse_tree_init)+≡

```

subroutine parse_ignore (node, ok)
    type(parse_node_t), pointer :: node
    logical, intent(out) :: ok
    call lex (lexeme, lexer)
    select case (lexeme_get_type (lexeme))
    case (T_NUMERIC, T_IDENTIFIER, T_QUOTED)
        ok = .true.
    case default
        ok = .false.
    end select
end subroutine parse_ignore

```

```

        end select
        node => null ()
    end subroutine parse_ignore

```

If the match fails and we cannot step back:

```

(Parser: internal subroutines of parse_tree_init)+≡
subroutine parse_error (rule, lexeme)
    type(syntax_rule_t), intent(in) :: rule
    type(lexeme_t), intent(in) :: lexeme
    character(80) :: buffer
    integer :: u, iostat
    call lexer_show_location (lexer)
    u = free_unit ()
    open (u, status = "scratch")
    write (u, "(A)", advance="no") "Expected syntax:"
    call syntax_rule_write (rule, u)
    write (u, "(A)", advance="no") "Found token:"
    call lexeme_write (lexeme, u)
    rewind (u)
    do
        read (u, "(A)", iostat=iostat) buffer
        if (iostat /= 0) exit
        call msg_message (trim (buffer))
    end do
    call msg_fatal (" Syntax error " &
        // "(at or before the location indicated above)")
end subroutine parse_error

```

The finalizer recursively deallocates all nodes and their contents. For each node, `parse_node_final` is called on the sub-nodes, which in turn deallocates the token or sub-node array contained within each of them. At the end, only the top node remains to be deallocated.

```

(Parser: public)+≡
public :: parse_tree_final

(Parser: parse tree: TBP)+≡
procedure :: final => parse_tree_final

(Parser: procedures)+≡
subroutine parse_tree_final (parse_tree)
    class(parse_tree_t), intent(inout) :: parse_tree
    if (associated (parse_tree%root_node)) then
        call parse_node_final (parse_tree%root_node)
        deallocate (parse_tree%root_node)
    end if
end subroutine parse_tree_final

```

Print the parse tree. Print one token per line, indented according to the depth of the node.

The **verbose** version includes type identifiers for the nodes.

```

(Parser: public)+≡
public :: parse_tree_write

(Parser: parse tree: TBP)+≡
procedure :: write => parse_tree_write

```

```

(Parser: procedures)+≡
subroutine parse_tree_write (parse_tree, unit, verbose)
  class(parse_tree_t), intent(in) :: parse_tree
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  integer :: u
  logical :: short
  u = given_output_unit (unit); if (u < 0) return
  short = .true.; if (present (verbose)) short = .not. verbose
  write (u, "(A)") "Parse tree:"
  if (associated (parse_tree%root_node)) then
    call parse_node_write_rec (parse_tree%root_node, unit, short, 1)
  else
    write (u, *) "[empty]"
  end if
end subroutine parse_tree_write

```

This is a generic error that can be issued if the parse tree does not meet the expectations of the parser. This most certainly indicates a bug.

```

(Parser: public)+≡
public :: parse_tree_bug

(Parser: procedures)+≡
subroutine parse_tree_bug (node, keys)
  type(parse_node_t), intent(in) :: node
  character(*), intent(in) :: keys
  call parse_node_write (node)
  call msg_bug (" Inconsistency in parse tree: expected " // keys)
end subroutine parse_tree_bug

```

7.4.7 Access the parser

For scanning the parse tree we give access to the top node, as a node pointer. Of course, there should be no write access.

```

(Parser: public)+≡
public :: parse_tree_get_root_ptr

(Parser: parse tree: TBP)+≡
procedure :: get_root_ptr => parse_tree_get_root_ptr

(Parser: procedures)+≡
function parse_tree_get_root_ptr (parse_tree) result (node)
  class(parse_tree_t), intent(in) :: parse_tree
  type(parse_node_t), pointer :: node
  node => parse_tree%root_node
end function parse_tree_get_root_ptr

```

7.4.8 Tools

This operation traverses the parse tree and simplifies any occurrences of a set of syntax rules. If such a parse node has only one sub-node, it is replaced by that

subnode. (This makes sense only of the rules to eliminate have no meaningful token.)

<Parser: public>+≡

public :: parse_tree_reduce

<Parser: procedures>+≡

subroutine parse_tree_reduce (parse_tree, rule_key)

type(parse_tree_t), intent(inout) :: parse_tree

type(string_t), dimension(:), intent(in) :: rule_key

type(parse_node_t), pointer :: pn

pn => parse_tree%root_node

if (associated (pn)) then

call parse_node_reduce (pn, null(), null())

end if

contains

recursive subroutine parse_node_reduce (pn, pn_prev, pn_parent)

type(parse_node_t), intent(inout), pointer :: pn

type(parse_node_t), intent(in), pointer :: pn_prev, pn_parent

type(parse_node_t), pointer :: pn_sub, pn_sub_prev, pn_tmp

pn_sub_prev => null ()

pn_sub => pn%sub_first

do while (associated (pn_sub))

call parse_node_reduce (pn_sub, pn_sub_prev, pn)

pn_sub_prev => pn_sub

pn_sub => pn_sub%next

end do

if (parse_node_get_n_sub (pn) == 1) then

if (matches (parse_node_get_rule_key (pn), rule_key)) then

pn_tmp => pn

pn => pn%sub_first

if (associated (pn_prev)) then

pn_prev%next => pn

else if (associated (pn_parent)) then

pn_parent%sub_first => pn

else

parse_tree%root_node => pn

end if

if (associated (pn_tmp%next)) then

pn%next => pn_tmp%next

else if (associated (pn_parent)) then

pn_parent%sub_last => pn

end if

call parse_node_final (pn_tmp, recursive=.false.)

deallocate (pn_tmp)

end if

end if

end subroutine parse_node_reduce

function matches (key, key_list) result (flag)

logical :: flag

type(string_t), intent(in) :: key

type(string_t), dimension(:), intent(in) :: key_list

integer :: i

flag = .true.

do i = 1, size (key_list)


```

        if (key == key_list(i)) return
    end do
    flag = .false.
end function matches
end subroutine parse_tree_reduce

```

7.4.9 Applications

For a file of the form

```

process foo, bar
  <something>
process xyz
  <something>

```

get the <something> entry node for the first matching process tag. If no matching entry is found, the node pointer remains unassociated.

(Parser: public)+≡

```

public :: parse_tree_get_process_ptr

```

(Parser: procedures)+≡

```

function parse_tree_get_process_ptr (parse_tree, process) result (node)
  type(parse_node_t), pointer :: node
  type(parse_tree_t), intent(in), target :: parse_tree
  type(string_t), intent(in) :: process
  type(parse_node_t), pointer :: node_root, node_process_def
  type(parse_node_t), pointer :: node_process_phs, node_process_list
  integer :: j
  node_root => parse_tree_get_root_ptr (parse_tree)
  if (associated (node_root)) then
    node_process_phs => parse_node_get_sub_ptr (node_root)
    SCAN_FILE: do while (associated (node_process_phs))
      node_process_def => parse_node_get_sub_ptr (node_process_phs)
      node_process_list => parse_node_get_sub_ptr (node_process_def, 2)
      do j = 1, parse_node_get_n_sub (node_process_list)
        if (parse_node_get_string &
            (parse_node_get_sub_ptr (node_process_list, j)) &
            == process) then
          node => parse_node_get_next_ptr (node_process_def)
          return
        end if
      end do
      node_process_phs => parse_node_get_next_ptr (node_process_phs)
    end do SCAN_FILE
    node => null ()
  else
    node => null ()
  end if
end function parse_tree_get_process_ptr

```

7.4.10 Unit tests

```
<Parser: public>+≡
    public :: parse_test

<Parser: procedures>+≡
    subroutine parse_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Parser: execute tests>
    end subroutine parse_test
```

This checks the parser.

```
<Parser: execute tests>≡
    call test (parse_1, "parse_1", &
        "check the parser", &
        u, results)

<Parser: tests>≡
    subroutine parse_1 (u)
        use ifiles
        use lexers
        integer, intent(in) :: u

        type(ifile_t) :: ifile
        type(syntax_t), target :: syntax
        type(lexer_t) :: lexer
        type(stream_t), target :: stream
        type(parse_tree_t), target :: parse_tree

        write (u, "(A)")  "* Test output: Parsing"
        write (u, "(A)")  "* Purpose: test parse routines"
        write (u, "(A)")

        call ifile_append (ifile, "SEQ expr = term addition*")
        call ifile_append (ifile, "SEQ addition = plus_or_minus term")
        call ifile_append (ifile, "SEQ term = factor multiplication*")
        call ifile_append (ifile, "SEQ multiplication = times_or_over factor")
        call ifile_append (ifile, "SEQ factor = atom exponentiation*")
        call ifile_append (ifile, "SEQ exponentiation = '^' atom")
        call ifile_append (ifile, "ALT atom = real | delimited_expr")
        call ifile_append (ifile, "GRO delimited_expr = ( expr )")
        call ifile_append (ifile, "ALT plus_or_minus = '+' | '-'")
        call ifile_append (ifile, "ALT times_or_over = '*' | '/'")
        call ifile_append (ifile, "KEY '+'")
        call ifile_append (ifile, "KEY '-'")
        call ifile_append (ifile, "KEY '*'")
        call ifile_append (ifile, "KEY '/'")
        call ifile_append (ifile, "KEY '^'")
        call ifile_append (ifile, "REA real")

        write (u, "(A)")  "* File contents (syntax definition):"
        call ifile_write (ifile, u)
        write (u, "(A)")  "EOF"
        write (u, "(A)")
```

```

call syntax_init (syntax, ifile)
call ifile_final (ifile)
call syntax_write (syntax, u)
write (u, "(A)")

call lexer_init (lexer, &
    comment_chars = "", &
    quote_chars = "'", &
    quote_match = "'", &
    single_chars = "+-*/^()", &
    special_class = [""] , &
    keyword_list = syntax_get_keyword_list_ptr (syntax))
call lexer_write_setup (lexer, u)
write (u, "(A)")

call ifile_append (ifile, "(27+8^3-2/3)*(4+7)^2*99")
write (u, "(A)")  "* File contents (input file):"
call ifile_write (ifile, u)
write (u, "(A)")  "EOF"
print *

call stream_init (stream, ifile)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax, lexer)
call stream_final (stream)
call parse_tree_write (parse_tree, u, .true.)
print *

write (u, "(A)")  "* Cleanup, everything should now be empty:"
write (u, "(A)")

call parse_tree_final (parse_tree)
call parse_tree_write (parse_tree, u, .true.)
write (u, "(A)")

call lexer_final (lexer)
call lexer_write_setup (lexer, u)
write (u, "(A)")

call ifile_final (ifile)
write (u, "(A)")  "* File contents:"
call ifile_write (ifile, u)
write (u, "(A)")  "EOF"
write (u, "(A)")

call syntax_final (syntax)
call syntax_write (syntax, u)

write (u, "(A)")
write (u, "(A)")  "* Test output end: parser_1"

end subroutine parse_1

```

7.5 XML Parser

The XML parser is actually independent from the previous modules of `lexer` and `parser`. However, for a generic I/O interface we make use of the `stream_t` facility.

We need the XML parser for reading and writing LHEF data files. Only a subset of XML is actually relevant. The parser is of the “pull” type, i.e., the program steers the reading of XML data in a context-sensitive manner.

```
<xml.f90>≡
  <File header>

  module xml

    <Use strings>
    use io_units
    use unit_tests
    use system_defs, only: BLANK, TAB
    use diagnostics
    use ifiles
    use lexers

    <Standard module head>

    <XML: public>

    <XML: types>

    contains

    <XML: procedures>

    <XML: tests>

  end module xml
```

7.5.1 Cached Stream

The stream type as defined in the `lexer` module is versatile regarding the choice of input channel, but it does not allow reading a section more than once. Here, we define an extension where we can return a string to the stream, which is stored in a cache variable, and presented to the caller for the next read.

```
<XML: public>≡
  public :: cstream_t

<XML: types>≡
  type, extends (stream_t) :: cstream_t
    logical :: cache_is_empty = .true.
    type(string_t) :: cache
  contains
    <XML: cstream: TBP>
  end type cstream_t
```

The initializers are simply inherited.

Finalizer: also inherited, in essence:

```
<XML: cstream: TBP>≡
  procedure :: final => cstream_final

<XML: procedures>≡
  subroutine cstream_final (stream)
    class(cstream_t), intent(inout) :: stream
    stream%cache_is_empty = .true.
    call stream%stream_t%final ()
  end subroutine cstream_final
```

Get record: now, if there is a cache string, return this instead of the record from the stream.

```
<XML: cstream: TBP>+≡
  procedure :: get_record => cstream_get_record

<XML: procedures>+≡
  subroutine cstream_get_record (cstream, string, iostat)
    class(cstream_t), intent(inout) :: cstream
    type(string_t), intent(out) :: string
    integer, intent(out) :: iostat
    if (cstream%cache_is_empty) then
      call stream_get_record (cstream%stream_t, string, iostat)
    else
      string = cstream%cache
      cstream%cache_is_empty = .true.
      iostat = 0
    end if
  end subroutine cstream_get_record
```

Revert: return the (partially read) record to the stream, putting it in the cache.

```
<XML: cstream: TBP>+≡
  procedure :: revert_record => cstream_revert_record

<XML: procedures>+≡
  subroutine cstream_revert_record (cstream, string)
    class(cstream_t), intent(inout) :: cstream
    type(string_t), intent(in) :: string
    if (cstream%cache_is_empty) then
      cstream%cache = string
      cstream%cache_is_empty = .false.
    else
      call msg_bug ("CStream: attempt to revert twice")
    end if
  end subroutine cstream_revert_record
```

7.5.2 Attributes

A tag attribute has a name and a value; both are strings. When the attribute is defined, the `known` flag indicates this.

```
<XML: types>+≡
```

```

type :: attribute_t
  type(string_t) :: name
  type(string_t) :: value
  logical :: known = .false.
contains
  <XML: attribute: TBP>
end type attribute_t

```

Output in standard format, non-advancing. (If the value is unknown, we indicate this by a question mark, which is non-standard.)

```

<XML: attribute: TBP>≡
  procedure :: write => attribute_write
<XML: procedures>+≡
  subroutine attribute_write (object, unit)
    class(attribute_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(A,'=')", advance = "no") char (object%name)
    if (object%known) then
      write (u, "(A,A,A)", advance = "no") '""', char (object%value), '''
    else
      write (u, "('?'')", advance = "no")
    end if
  end subroutine attribute_write

```

This is a genuine constructor. The value is optional.

```

<XML: public>+≡
  public :: xml_attribute
<XML: procedures>+≡
  function xml_attribute (name, value) result (attribute)
    type(string_t), intent(in) :: name
    type(string_t), intent(in), optional :: value
    type(attribute_t) :: attribute
    attribute%name = name
    if (present (value)) then
      attribute%value = value
      attribute%known = .true.
    else
      attribute%known = .false.
    end if
  end function xml_attribute

```

Set a value explicitly.

```

<XML: attribute: TBP>+≡
  procedure :: set_value => attribute_set_value
<XML: procedures>+≡
  subroutine attribute_set_value (attribute, value)
    class(attribute_t), intent(inout) :: attribute
    type(string_t), intent(in) :: value
    attribute%value = value

```

```

        attribute%known = .true.
    end subroutine attribute_set_value

```

Extract a value. If unset, return "?"

```

<XML: attribute: TBP>+≡
    procedure :: get_value => attribute_get_value

<XML: procedures>+≡
    function attribute_get_value (attribute) result (value)
        class(attribute_t), intent(in) :: attribute
        type(string_t) :: value
        if (attribute%known) then
            value = attribute%value
        else
            value = "?"
        end if
    end function attribute_get_value

```

7.5.3 The Tag Type

The basic entity is the internal representation of an XML tag. The tag has a name, a well-defined set of attributes which may be mandatory or optional, and a flag that determines whether there is content or not. The content itself is not stored in the data structure.

```

<XML: public>+≡
    public :: xml_tag_t

<XML: types>+≡
    type :: xml_tag_t
        type(string_t) :: name
        type(attribute_t), dimension(:), allocatable :: attribute
        logical :: has_content = .false.
    contains
        <XML: tag: TBP>
    end type xml_tag_t

```

Initialization. There are different versions, depending on content.

```

<XML: tag: TBP>≡
    generic :: init => init_no_attributes
    procedure :: init_no_attributes => tag_init_no_attributes

<XML: procedures>+≡
    subroutine tag_init_no_attributes (tag, name, has_content)
        class(xml_tag_t), intent(out) :: tag
        type(string_t), intent(in) :: name
        logical, intent(in), optional :: has_content
        tag%name = name
        allocate (tag%attribute (0))
        if (present (has_content)) tag%has_content = has_content
    end subroutine tag_init_no_attributes

```

This version sets attributes.

```
<XML: tag: TBP>+≡
  generic :: init => init_with_attributes
  procedure :: init_with_attributes => tag_init_with_attributes

<XML: procedures>+≡
  subroutine tag_init_with_attributes (tag, name, attribute, has_content)
    class(xml_tag_t), intent(out) :: tag
    type(string_t), intent(in) :: name
    type(attribute_t), dimension(:), intent(in) :: attribute
    logical, intent(in), optional :: has_content
    tag%name = name
    allocate (tag%attribute (size (attribute)))
    tag%attribute = attribute
    if (present (has_content)) tag%has_content = has_content
  end subroutine tag_init_with_attributes
```

Set an attribute value explicitly.

```
<XML: tag: TBP>+≡
  procedure :: set_attribute => tag_set_attribute

<XML: procedures>+≡
  subroutine tag_set_attribute (tag, i, value)
    class(xml_tag_t), intent(inout) :: tag
    integer, intent(in) :: i
    type(string_t), intent(in) :: value
    call tag%attribute(i)%set_value (value)
  end subroutine tag_set_attribute
```

Get an attribute value.

```
<XML: tag: TBP>+≡
  procedure :: get_attribute => tag_get_attribute

<XML: procedures>+≡
  function tag_get_attribute (tag, i) result (value)
    class(xml_tag_t), intent(in) :: tag
    integer, intent(in) :: i
    type(string_t) :: value
    value = tag%attribute(i)%get_value ()
  end function tag_get_attribute
```

Output to an I/O unit, default STDOUT. We use non-advancing output.

```
<XML: tag: TBP>+≡
  generic :: write => write_without_content
  procedure :: write_without_content => tag_write

<XML: procedures>+≡
  subroutine tag_write (tag, unit)
    class(xml_tag_t), intent(in) :: tag
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "('<',A)", advance = "no") char (tag%name)
    do i = 1, size (tag%attribute)
```



```

        write (u, "(1x)", advance = "no")
        call tag%attribute(i)%write (u)
    end do
    if (tag%has_content) then
        write (u, "('>')", advance = "no")
    else
        write (u, "(' />')", advance = "no")
    end if
end subroutine tag_write

```

If there is content, we should write the content next (arbitrary format), the write the corresponding closing tag. Again, non-advancing.

```

<XML: tag: TBP>+≡
    procedure :: close => tag_close
<XML: procedures>+≡
    subroutine tag_close (tag, unit)
        class(xml_tag_t), intent(in) :: tag
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "<'</',A,'>')", advance = "no") char (tag%name)
    end subroutine tag_close

```

Given content as a single string, we can write tag, content, and closing at once

```

<XML: tag: TBP>+≡
    generic :: write => write_with_content
    procedure :: write_with_content => tag_write_with_content
<XML: procedures>+≡
    subroutine tag_write_with_content (tag, content, unit)
        class(xml_tag_t), intent(in) :: tag
        type(string_t), intent(in) :: content
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        call tag%write (u)
        write (u, "(A)", advance = "no") char (content)
        call tag%close (u)
    end subroutine tag_write_with_content

```

Input from stream. We know what we are looking for, so we check if the name matches, then fill attributes. We report an error if (a) an I/O error occurs, (b) we reach EOF before encountering the tag, (c) if the tag is incomplete.

Trailing text after reading a tag is put back to the input stream.

We assume that the tag is not broken across records, and that there is only one tag within the record. This is more restricted than standard XML.

```

<XML: tag: TBP>+≡
    procedure :: read => tag_read
<XML: procedures>+≡
    subroutine tag_read (tag, cstream, success)
        class(xml_tag_t), intent(inout) :: tag

```

```

type(cstream_t), intent(inout) :: cstream
logical, intent(out) :: success
type(string_t) :: string
integer :: iostat, p1, p2
character(2), parameter :: WS = BLANK // TAB
logical :: done

! Skip comments and blank lines
FIND_NON_COMMENT: do
  FIND_NONEMPTY_RECORD: do
    call cstream%get_record (string, iostat)
    if (iostat /= 0) call err_io ()
    p1 = verify (string, WS)
    if (p1 > 0) exit FIND_NONEMPTY_RECORD
  end do FIND_NONEMPTY_RECORD

  ! Look for comment beginning
  p2 = p1 + 3
  if (extract (string, p1, p2) /= "<!--") exit FIND_NON_COMMENT

  ! Look for comment end, then restart
  string = extract (string, p2 + 1)
  FIND_COMMENT_END: do
    do p1 = 1, len (string) - 2
      p2 = p1 + 2
      if (extract (string, p1, p2) == "-->") then

        ! Return trailing text to the stream
        string = extract (string, p2 + 1)
        if (string /= "") call cstream%revert_record (string)
        exit FIND_COMMENT_END

      end if
    end do
    call cstream%get_record (string, iostat)
    if (iostat /= 0) call err_io ()
  end do FIND_COMMENT_END
end do FIND_NON_COMMENT

! Look for opening <
p2 = p1
if (extract (string, p1, p2) /= "<") then
  call cstream%revert_record (string)
  success = .false.; return
else

  ! Look for tag name
  string = extract (string, p2 + 1)
  p1 = verify (string, WS); if (p1 == 0) call err_incomplete ()
  p2 = p1 + len (tag%name) - 1
  if (extract (string, p1, p2) /= tag%name) then
    call cstream%revert_record ("<" // string)
    success = .false.; return
  else

```

```

! Look for attributes
string = extract (string, p2 + 1)
READ_ATTRIBUTES: do
    call tag%read_attribute (string, done)
    if (done) exit READ_ATTRIBUTES
end do READ_ATTRIBUTES

! Look for closing >
p1 = verify (string, WS); if (p1 == 0) call err_incomplete ()
p2 = p1
if (extract (string, p1, p1) == ">") then
    tag%has_content = .true.
else

    ! Look for closing />
    p2 = p1 + 1
    if (extract (string, p1, p2) /= "/>") call err_incomplete ()
end if

! Return trailing text to the stream
string = extract (string, p2 + 1)
if (string /= "") call cstream%revert_record (string)
success = .true.

end if
end if

contains

subroutine err_io ()
    select case (iostat)
    case (:-1)
        call msg_fatal ("XML: Error reading tag '" // char (tag%name) &
            // "': end of file")
    case (1:)
        call msg_fatal ("XML: Error reading tag '" // char (tag%name) &
            // "': I/O error")
    end select
    success = .false.
end subroutine err_io

subroutine err_incomplete ()
    call msg_fatal ("XML: Error reading tag '" // char (tag%name) &
        // "': tag incomplete")
    success = .false.
end subroutine err_incomplete

end subroutine tag_read

```

Read a single attribute. If the attribute is valid, assign the value. Setting a value twice should be an error, but is not detected. If the attribute is unknown, ignore it. If we reach the closing sign, report this.

```

<XML: tag: TBP>+≡
    procedure :: read_attribute => tag_read_attribute

<XML: procedures>+≡
    subroutine tag_read_attribute (tag, string, done)
        class(xml_tag_t), intent(inout) :: tag
        type(string_t), intent(inout) :: string
        logical, intent(out) :: done
        character(2), parameter :: WS = BLANK // TAB
        type(string_t) :: name, value
        integer :: p1, p2, i

        p1 = verify (string, WS); if (p1 == 0) call err ()
        p2 = p1

        ! Look for first terminating '>' or '>''
        if (extract (string, p1, p2) == ">") then
            done = .true.
        else
            p2 = p1 + 1
            if (extract (string, p1, p2) == ">") then
                done = .true.
            else

                ! Look for '='
                p2 = scan (string, '=')
                if (p2 == 0) call err ()
                name = trim (extract (string, p1, p2 - 1))

                ! Look for '"'
                string = extract (string, p2 + 1)
                p1 = verify (string, WS); if (p1 == 0) call err ()
                p2 = p1
                if (extract (string, p1, p2) /= '"') call err ()

                ! Look for matching '"' and get value
                string = extract (string, p2 + 1)
                p1 = 1
                p2 = scan (string, '"')
                if (p2 == 0) call err ()
                value = extract (string, p1, p2 - 1)

                SCAN_KNOWN_ATTRIBUTES: do i = 1, size (tag%attribute)
                    if (name == tag%attribute(i)%name) then
                        call tag%attribute(i)%set_value (value)
                        exit SCAN_KNOWN_ATTRIBUTES
                    end if
                end do SCAN_KNOWN_ATTRIBUTES

                string = extract (string, p2 + 1)
                done = .false.
            end if
        end if

contains

```

```

subroutine err ()
  call msg_fatal ("XML: Error reading attributes of '" // char (tag%name) &
    // "' : syntax error")
end subroutine err

end subroutine tag_read_attribute

```

Read the content string of a tag. We check for the appropriate closing tag and report it. If a closing tag does not match in name, ignore it.

Note: this assumes that no tag with the same name is embedded in the current content. Also, we do not check for XML validity inside the content.

```

<XML: tag: TBP>+≡
  procedure :: read_content => tag_read_content
<XML: procedures>+≡
  subroutine tag_read_content (tag, cstream, content, closing)
    class(xml_tag_t), intent(in) :: tag
    type(cstream_t), intent(inout) :: cstream
    type(string_t), intent(out) :: content
    type(string_t) :: string
    logical, intent(out) :: closing
    integer :: iostat
    integer :: p0, p1, p2
    character(2), parameter :: WS = BLANK // TAB
    call cstream%get_record (content, iostat)
    if (iostat /= 0) call err_io ()
    closing = .false.
    FIND_CLOSING: do p0 = 1, len (content) - 1

      ! Look for terminating </
      p1 = p0
      p2 = p1 + 1
      if (extract (content, p1, p2) == "</") then

        ! Look for closing tag name
        string = extract (content, p2 + 1)
        p1 = verify (string, WS); if (p1 == 0) call err_incomplete ()
        p2 = p1 + len (tag%name) - 1
        if (extract (string, p1, p2) == tag%name) then

          ! Tag name matches: look for final >
          string = extract (string, p2 + 1)
          p1 = verify (string, WS); if (p1 == 0) call err_incomplete ()
          p2 = p1
          if (extract (string, p1, p2) /= ">") call err_incomplete ()

          ! Return trailing text to the stream
          string = extract (string, p2 + 1)
          if (string /= "") call cstream%revert_record (string)
          content = extract (content, 1, p0 -1)
          closing = .true.
          exit FIND_CLOSING
        end if
      end if
    end do
  end subroutine

```

```

        end if
    end if
end do FIND_CLOSING

contains

subroutine err_io ()
    select case (iostat)
    case (:-1)
        call msg_fatal ("XML: Error reading content of '" // char (tag%name) &
            // "': end of file")
    case (1:)
        call msg_fatal ("XML: Error reading content of '" // char (tag%name) &
            // "': I/O error")
    end select
    closing = .false.
end subroutine err_io

subroutine err_incomplete ()
    call msg_fatal ("XML: Error reading content '" // char (tag%name) &
        // "': closing tag incomplete")
    closing = .false.
end subroutine err_incomplete

end subroutine tag_read_content

```

7.5.4 Unit tests

```

<XML: public>+≡
    public :: xml_test

<XML: tests>≡
    subroutine xml_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <XML: execute tests>
end subroutine xml_test

```

7.5.5 Auxiliary Routines

Show the contents of a temporary file, i.e., open unit.

```

<XML: tests>+≡
    subroutine show (u_tmp, u)
        integer, intent(in) :: u_tmp, u
        character (80) :: buffer
        integer :: iostat
        write (u, "(A)") "File content:"
        rewind (u_tmp)
    do
        read (u_tmp, "(A)", iostat = iostat) buffer
        if (iostat /= 0) exit
    do

```

```

        write (u, "(A)") trim (buffer)
    end do
    rewind (u_tmp)
end subroutine show

```

7.5.6 Basic Tag I/O

Write a tag and read it again, using a temporary file.

```

<XML: execute tests>≡
    call test (xml_1, "xml_1", &
        "basic I/O", &
        u, results)

<XML: tests>+≡
    subroutine xml_1 (u)
        integer, intent(in) :: u
        type(xml_tag_t), allocatable :: tag
        integer :: u_tmp
        type(cstream_t) :: cstream
        logical :: success

        write (u, "(A)")  "* Test output: xml_1"
        write (u, "(A)")  "* Purpose: write and read tag"
        write (u, "(A)")

        write (u, "(A)")  "* Empty tag"
        write (u, *)

        u_tmp = free_unit ()
        open (u_tmp, status = "scratch", action = "readwrite")

        allocate (tag)
        call tag%init (var_str ("tagname"))
        call tag%write (u_tmp)
        write (u_tmp, *)
        deallocate (tag)

        call show (u_tmp, u)

        write (u, *)
        write (u, "(A)")  "Result from read:"
        call cstream%init (u_tmp)
        allocate (tag)
        call tag%init (var_str ("tagname"))
        call tag%read (cstream, success)
        call tag%write (u)
        write (u, *)
        write (u, "(A,L1)") "success = ", success
        deallocate (tag)
        call cstream%final ()

        write (u, *)
        write (u, "(A)")  "* Tag with preceding blank lines"

```

```

write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag)
call tag%init (var_str ("tagname"))
write (u_tmp, *)
write (u_tmp, "(A)") " "
write (u_tmp, "(2x)", advance = "no")
call tag%write (u_tmp)
write (u_tmp, *)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)") "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"))
call tag%read (cstream, success)
call tag%write (u)
write (u, *)
write (u, "(A,L1)") "success = ", success
deallocate (tag)
call cstream%final ()

write (u, *)
write (u, "(A)") "* Tag with preceding comments"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag)
call tag%init (var_str ("tagname"))
write (u_tmp, "(A)") "<!-- comment -->"
write (u_tmp, *)
write (u_tmp, "(A)") "<!-- multiline"
write (u_tmp, "(A)") "      comment -->"
call tag%write (u_tmp)
write (u_tmp, *)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)") "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"))
call tag%read (cstream, success)
call tag%write (u)

```



```

write (u, *)
write (u, "(A,L1)") "success = ", success
deallocate (tag)
call cstream%final ()

write (u, *)
write (u, "(A)")  "* Tag with name mismatch"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag)
call tag%init (var_str ("wrongname"))
call tag%write (u_tmp)
write (u_tmp, *)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)") "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"))
call tag%read (cstream, success)
call tag%write (u)
write (u, *)
write (u, "(A,L1)") "success = ", success
deallocate (tag)
call cstream%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: xml_1"

end subroutine xml_1

```

7.5.7 Optional Tag

Write and read two tags, one of them optional.

```

<XML: execute tests>+≡
  call test (xml_2, "xml_2", &
    "optional tag", &
    u, results)

<XML: tests>+≡
subroutine xml_2 (u)
  integer, intent(in) :: u
  type(xml_tag_t), allocatable :: tag1, tag2
  integer :: u_tmp
  type(cstream_t) :: cstream
  logical :: success

```

```

write (u, "(A)")  "* Test output: xml_2"
write (u, "(A)")  "* Purpose: handle optional tag"
write (u, "(A)")

write (u, "(A)")  "* Optional tag present"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag1)
call tag1%init (var_str ("option"))
call tag1%write (u_tmp)
write (u_tmp, *)
allocate (tag2)
call tag2%init (var_str ("tagname"))
call tag2%write (u_tmp)
write (u_tmp, *)
deallocate (tag1, tag2)

call show (u_tmp, u)

write (u, *)
write (u, "(A)")  "Result from read:"
call cstream%init (u_tmp)
allocate (tag1)
call tag1%init (var_str ("option"))
call tag1%read (cstream, success)
call tag1%write (u)
write (u, *)
write (u, "(A,L1)")  "success = ", success
write (u, *)
allocate (tag2)
call tag2%init (var_str ("tagname"))
call tag2%read (cstream, success)
call tag2%write (u)
write (u, *)
write (u, "(A,L1)")  "success = ", success
deallocate (tag1, tag2)
call cstream%final ()

write (u, *)
write (u, "(A)")  "* Optional tag absent"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag2)
call tag2%init (var_str ("tagname"))
call tag2%write (u_tmp)
write (u_tmp, *)
deallocate (tag2)

```

```

call show (u_tmp, u)

write (u, *)
write (u, "(A)") "Result from read:"
call cstream%init (u_tmp)
allocate (tag1)
call tag1%init (var_str ("option"))
call tag1%read (cstream, success)
call tag1%write (u)
write (u, *)
write (u, "(A,L1)") "success = ", success
write (u, *)
allocate (tag2)
call tag2%init (var_str ("tagname"))
call tag2%read (cstream, success)
call tag2%write (u)
write (u, *)
write (u, "(A,L1)") "success = ", success
deallocate (tag1, tag2)
call cstream%final ()

write (u, "(A)")
write (u, "(A)") "* Test output end: xml_2"

end subroutine xml_2

```

7.5.8 Optional Tag

Write and read a tag with single-line content.

```

<XML: execute tests>+≡
  call test (xml_3, "xml_3", &
    "content", &
    u, results)

<XML: tests>+≡
subroutine xml_3 (u)
  integer, intent(in) :: u
  type(xml_tag_t), allocatable :: tag
  integer :: u_tmp
  type(cstream_t) :: cstream
  logical :: success, closing
  type(string_t) :: content

  write (u, "(A)") "* Test output: xml_3"
  write (u, "(A)") "* Purpose: handle tag with content"
  write (u, "(A)")

  write (u, "(A)") "* Tag without content"
  write (u, *)

  u_tmp = free_unit ()
  open (u_tmp, status = "scratch", action = "readwrite")

```

```

allocate (tag)
call tag%init (var_str ("tagname"))
call tag%write (u_tmp)
write (u_tmp, *)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)") "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"))
call tag%read (cstream, success)
call tag%write (u)
write (u, *)
write (u, "(A,L1)") "success = ", success
write (u, "(A,L1)") "content = ", tag%has_content
write (u, *)
deallocate (tag)
call cstream%final ()

write (u, "(A)") "* Tag with content"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag)
call tag%init (var_str ("tagname"), has_content = .true.)
call tag%write (var_str ("Content text"), u_tmp)
write (u_tmp, *)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)") "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"))
call tag%read (cstream, success)
call tag%read_content (cstream, content, closing)
call tag%write (u)
write (u, "(A)", advance = "no") char (content)
call tag%close (u)
write (u, *)
write (u, "(A,L1)") "success = ", success
write (u, "(A,L1)") "content = ", tag%has_content
write (u, "(A,L1)") "closing = ", closing
deallocate (tag)
call cstream%final ()

write (u, *)

```

```

write (u, "(A)")  "* Tag with multiline content"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag)
call tag%init (var_str ("tagname"), has_content = .true.)
call tag%write (u_tmp)
write (u_tmp, *)
write (u_tmp, "(A)")  "Line 1"
write (u_tmp, "(A)")  "Line 2"
call tag%close (u_tmp)
write (u_tmp, *)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)")  "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"))
call tag%read (cstream, success)
call tag%write (u)
write (u, *)
do
    call tag%read_content (cstream, content, closing)
    if (closing) exit
    write (u, "(A)")  char (content)
end do
call tag%close (u)
write (u, *)
write (u, "(A,L1)")  "success = ", success
write (u, "(A,L1)")  "content = ", tag%has_content
deallocate (tag)
call cstream%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: xml_3"

end subroutine xml_3

```

7.5.9 Basic Tag I/O

Write a tag and read it again, using a temporary file.

```

<XML: execute tests>+≡
    call test (xml_4, "xml_4", &
        "attributes", &
        u, results)

<XML: tests>+≡
    subroutine xml_4 (u)

```

```

integer, intent(in) :: u
type(xml_tag_t), allocatable :: tag
integer :: u_tmp
type(cstream_t) :: cstream
logical :: success

write (u, "(A)")  "* Test output: xml_4"
write (u, "(A)")  "*   Purpose: handle tag with attributes"
write (u, "(A)")

write (u, "(A)")  "* Tag with one mandatory and one optional attribute,"
write (u, "(A)")  "* unknown attribute ignored"
write (u, *)

u_tmp = free_unit ()
open (u_tmp, status = "scratch", action = "readwrite")

allocate (tag)
call tag%init (var_str ("tagname"), &
               [xml_attribute (var_str ("a1"), var_str ("foo")), &
                xml_attribute (var_str ("a3"), var_str ("gee"))])
call tag%write (u_tmp)
deallocate (tag)

call show (u_tmp, u)

write (u, *)
write (u, "(A)")  "Result from read:"
call cstream%init (u_tmp)
allocate (tag)
call tag%init (var_str ("tagname"), &
               [xml_attribute (var_str ("a1")), &
                xml_attribute (var_str ("a2"), var_str ("bar"))])
call tag%read (cstream, success)
call tag%write (u)
write (u, *)
deallocate (tag)
call cstream%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: xml_4"

end subroutine xml_4

```

Chapter 8

Random-Number Generator

These modules implement abstract types and tools for random-number generation.

rng_base Abstract random-number generator and factory

selectors Selection depending on weights and random numbers

Implementation of the RNG abstract types:

Module rng_tao: Interface to the TAO random number generator which the VAMP package provides. Note that VAMP explicitly requests this generator.

8.1 Generic Random-Number Generator

For all generator implementations, we define a `rng` type which represents the state of a random-number generator with the associated methods that produce a random number. Furthermore, we define a `rng_factory` type. An object of this type is capable of allocating a sequence of `rng` objects. These generator states should be, if possible, statistically independent, so they can be used in parallel in different places of the event-generation chain.

```
<rng_base.f90>≡  
  <File header>  
  
  module rng_base  
  
    use kinds  
    use io_units  
    use format_utils, only: write_indent  
    use unit_tests  
  
    <Standard module head>  
  
    <RNG base: public>  
  
    <RNG base: types>  
  
    <RNG base: interfaces>  
  
    <RNG base: test types>  
  
    contains  
  
    <RNG base: tests>  
  
  end module rng_base
```

8.1.1 Generator type

The `rng` object is actually the state of the random-number generator. The methods `initialize/reset` and `call` the generator for this state.

```
<RNG base: public>≡  
  public :: rng_t  
  
<RNG base: types>≡  
  type, abstract :: rng_t  
    contains  
    <RNG base: rng: TBP>  
  end type rng_t
```

The `init` method initializes the generator and sets a seed. We should implement the interface such that a single integer is sufficient for a seed.

The seed may be omitted. The behavior without seed is not defined, however.

```
<RNG base: rng: TBP>≡  
  procedure (rng_init), deferred :: init
```



```

<RNG base: interfaces>≡
  abstract interface
    subroutine rng_init (rng, seed)
      import
      class(rng_t), intent(out) :: rng
      integer, intent(in), optional :: seed
    end subroutine rng_init
  end interface

```

The `final` method deallocates memory where necessary and allows for another call of `init` to reset the generator.

```

<RNG base: rng: TBP>+≡
  procedure (rng_final), deferred :: final

<RNG base: interfaces>+≡
  abstract interface
    subroutine rng_final (rng)
      import
      class(rng_t), intent(inout) :: rng
    end subroutine rng_final
  end interface

```

Output. We should, at least, identify the generator.

```

<RNG base: rng: TBP>+≡
  procedure (rng_write), deferred :: write

<RNG base: interfaces>+≡
  abstract interface
    subroutine rng_write (rng, unit, indent)
      import
      class(rng_t), intent(in) :: rng
      integer, intent(in), optional :: unit, indent
    end subroutine rng_write
  end interface

```

These routines generate a single and an array of default-precision random numbers, respectively.

```

<RNG base: rng: TBP>+≡
  generic :: generate => generate_single, generate_array
  procedure (rng_generate_single), deferred :: generate_single
  procedure (rng_generate_array), deferred :: generate_array

<RNG base: interfaces>+≡
  abstract interface
    subroutine rng_generate_single (rng, x)
      import
      class(rng_t), intent(inout) :: rng
      real(default), intent(out) :: x
    end subroutine rng_generate_single
  end interface

  abstract interface
    subroutine rng_generate_array (rng, x)

```

```

import
class(rng_t), intent(inout) :: rng
real(default), dimension(:), intent(out) :: x
end subroutine rng_generate_array
end interface

```

8.1.2 RNG Factory

A factory object has a `make` method that allocates and initializes a new generator of appropriate type. It uses a 16-bit integer for initialization. For a real-life implementation, the factory should return a sequence of statistically independent generators, and for different seeds, the sequences should also be independent.

```

⟨RNG base: public⟩+≡
  public :: rng_factory_t
⟨RNG base: types⟩+≡
  type, abstract :: rng_factory_t
  contains
  ⟨RNG base: rng factory: TBP⟩
end type rng_factory_t

```

Output. Should be short, just report the seed and current state of the factory.

```

⟨RNG base: rng factory: TBP⟩≡
  procedure (rng_factory_write), deferred :: write
⟨RNG base: interfaces⟩+≡
  abstract interface
    subroutine rng_factory_write (object, unit)
    import
    class(rng_factory_t), intent(in) :: object
    integer, intent(in), optional :: unit
    end subroutine rng_factory_write
  end interface

```

Initialize. It should be possible to do this repeatedly, resetting the state. The default seed should be 0.

```

⟨RNG base: rng factory: TBP⟩+≡
  procedure (rng_factory_init), deferred :: init
⟨RNG base: interfaces⟩+≡
  abstract interface
    subroutine rng_factory_init (factory, seed)
    import
    class(rng_factory_t), intent(out) :: factory
    integer(i16), intent(in), optional :: seed
    end subroutine rng_factory_init
  end interface

```

Spawn a new generator.

```

⟨RNG base: rng factory: TBP⟩+≡
  procedure (rng_factory_make), deferred :: make

```

```

<RNG base: interfaces>+≡
  abstract interface
    subroutine rng_factory_make (factory, rng)
      import
      class(rng_factory_t), intent(inout) :: factory
      class(rng_t), intent(out), allocatable :: rng
    end subroutine rng_factory_make
  end interface

```

8.1.3 Unit tests

```

<RNG base: public>+≡
  public :: rng_base_test

<RNG base: tests>≡
  subroutine rng_base_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <RNG base: execute tests>
  end subroutine rng_base_test

```

Test generator

The test 'mock' random generator generates a repeating series with the numbers 0.1, 0.3, 0.5, 0.7, 0.9. It has an integer stored as state. The integer must be one of 1, 3, 5, 7, 9.

```

<RNG base: public>+≡
  public :: rng_test_t

<RNG base: test types>≡
  type, extends (rng_t) :: rng_test_t
    integer :: state = 1
  contains
    procedure :: write => rng_test_write
    procedure :: init => rng_test_init
    procedure :: final => rng_test_final
    procedure :: generate_single => rng_test_generate_single
    procedure :: generate_array => rng_test_generate_array
  end type rng_test_t

```

Output. The state is a single number, so print it.

```

<RNG base: tests>+≡
  subroutine rng_test_write (rng, unit, indent)
    class(rng_test_t), intent(in) :: rng
    integer, intent(in), optional :: unit, indent
    integer :: u, ind
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    call write_indent (u, ind)
    write (u, "(A,IO,A)") "Random-number generator: &
      &test (state = ", rng%state, ")"

```

```
end subroutine rng_test_write
```

The default seed is 1.

```
<RNG base: tests>+≡
subroutine rng_test_init (rng, seed)
  class(rng_test_t), intent(out) :: rng
  integer, intent(in), optional :: seed
  if (present (seed)) rng%state = seed
end subroutine rng_test_init
```

Nothing to finalize:

```
<RNG base: tests>+≡
subroutine rng_test_final (rng)
  class(rng_test_t), intent(inout) :: rng
end subroutine rng_test_final
```

Generate a single number and advance the state.

```
<RNG base: tests>+≡
subroutine rng_test_generate_single (rng, x)
  class(rng_test_t), intent(inout) :: rng
  real(default), intent(out) :: x
  x = rng%state / 10._default
  rng%state = mod (rng%state + 2, 10)
end subroutine rng_test_generate_single
```

The array generator calls the single-item generator multiple times.

```
<RNG base: tests>+≡
subroutine rng_test_generate_array (rng, x)
  class(rng_test_t), intent(inout) :: rng
  real(default), dimension(:), intent(out) :: x
  integer :: i
  do i = 1, size (x)
    call rng%generate (x(i))
  end do
end subroutine rng_test_generate_array
```

Test Factory

This factory makes `rng_test_t` generators, initialized with integers 1, 3, 5, 7, 9 if given the input 0, 1, 2, 3, 4. The generators within one sequence are all identical, however.

```
<RNG base: public>+≡
public :: rng_test_factory_t

<RNG base: test types>+≡
type, extends (rng_factory_t) :: rng_test_factory_t
  integer :: seed = 1
contains
  <RNG base: rng test factory: TBP>
end type rng_test_factory_t
```

Output.

```
<RNG base: rng test factory: TBP>≡
  procedure :: write => rng_test_factory_write

<RNG base: tests>+≡
  subroutine rng_test_factory_write (object, unit)
    class(rng_test_factory_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A,I0,A)") "RNG factory: test (", object%seed, ")"
  end subroutine rng_test_factory_write
```

Initialize, translating the given seed.

```
<RNG base: rng test factory: TBP>+≡
  procedure :: init => rng_test_factory_init

<RNG base: tests>+≡
  subroutine rng_test_factory_init (factory, seed)
    class(rng_test_factory_t), intent(out) :: factory
    integer(i16), intent(in), optional :: seed
    if (present (seed)) factory%seed = mod (seed * 2 + 1, 10)
  end subroutine rng_test_factory_init
```

```
<RNG base: rng test factory: TBP>+≡
  procedure :: make => rng_test_factory_make

<RNG base: tests>+≡
  subroutine rng_test_factory_make (factory, rng)
    class(rng_test_factory_t), intent(inout) :: factory
    class(rng_t), intent(out), allocatable :: rng
    allocate (rng_test_t :: rng)
    select type (rng)
    type is (rng_test_t)
      call rng%init (int (factory%seed))
    end select
  end subroutine rng_test_factory_make
```

Generator check

Initialize the generator and draw random numbers.

```
<RNG base: execute tests>≡
  call test (rng_base_1, "rng_base_1", &
    "rng initialization and call", &
    u, results)

<RNG base: tests>+≡
  subroutine rng_base_1 (u)
    integer, intent(in) :: u
    class(rng_t), allocatable :: rng

    real(default) :: x
    real(default), dimension(2) :: x2
```

```

write (u, "(A)")  "* Test output: rng_base_1"
write (u, "(A)")  "* Purpose: initialize and call a test random-number &
                    &generator"
write (u, "(A)")

write (u, "(A)")  "* Initialize generator"
write (u, "(A)")

allocate (rng_test_t :: rng)
call rng%init (3)

call rng%write (u)

write (u, "(A)")
write (u, "(A)")  "* Get random number"
write (u, "(A)")

call rng%generate (x)
write (u, "(A,2(1x,F9.7))")  "x =", x

write (u, "(A)")
write (u, "(A)")  "* Get random number pair"
write (u, "(A)")

call rng%generate (x2)
write (u, "(A,2(1x,F9.7))")  "x =", x2

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call rng%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rng_base_1"

end subroutine rng_base_1

```

Factory check

Set up a factory and spawn generators.

```

<RNG base: execute tests>+≡
  call test (rng_base_2, "rng_base_2", &
            "rng factory", &
            u, results)

<RNG base: tests>+≡
  subroutine rng_base_2 (u)
    integer, intent(in) :: u
    type(rng_test_factory_t) :: rng_factory
    class(rng_t), allocatable :: rng

    write (u, "(A)")  "* Test output: rng_base_2"

```

```

write (u, "(A)")  "*"  Purpose: initialize and use a rng factory"
write (u, "(A)")

write (u, "(A)")  "*" Initialize factory"
write (u, "(A)")

call rng_factory%init ()
call rng_factory%write (u)

write (u, "(A)")
write (u, "(A)")  "*" Make a generator"
write (u, "(A)")

call rng_factory%make (rng)
call rng%write (u)

write (u, "(A)")
write (u, "(A)")  "*" Cleanup"

call rng%final ()

write (u, "(A)")
write (u, "(A)")  "*" Test output end: rng_base_2"

end subroutine rng_base_2

```

8.2 Select from a weighted sample

```
<selectors.f90>≡  
  <File header>  
  
  module selectors  
  
    use kinds  
    use io_units  
    use unit_tests  
    use diagnostics  
    use rng_base  
  
    <Standard module head>  
  
    <Selectors: public>  
  
    <Selectors: types>  
  
    contains  
  
    <Selectors: procedures>  
  
    <Selectors: tests>  
  
  end module selectors
```

8.2.1 Selector type

The rng object is actually the state of the random-number generator. The methods initialize/reset and call the generator for this state.

```
<Selectors: public>≡  
  public :: selector_t  
  
<Selectors: types>≡  
  type :: selector_t  
    integer, dimension(:), allocatable :: map  
    real(default), dimension(:), allocatable :: weight  
    real(default), dimension(:), allocatable :: acc  
    contains  
    <Selectors: selector: TBP>  
  end type selector_t
```

Display contents.

```
<Selectors: selector: TBP>≡  
  procedure :: write => selector_write  
  
<Selectors: procedures>≡  
  subroutine selector_write (object, unit)  
    class(selector_t), intent(in) :: object  
    integer, intent(in), optional :: unit  
    integer :: u, i  
    u = given_output_unit (unit)  
    write (u, "(1x,A)") "Selector: i, weight, acc. weight"
```



```

if (allocated (object%weight)) then
  do i = 1, size (object%weight)
    write (u, "(3x,I0,1x,ES19.12,1x,ES19.12)") &
      object%map(i), object%weight(i), object%acc(i)
  end do
else
  write (u, "(3x,A)") "[undefined]"
end if
end subroutine selector_write

```

We pack the input weight array such that zero-weight entries are removed. We also normalize it. This makes a `map` array for mapping the selected weight to the actual entry necessary.

We may encounter a case where all weights are zero. We do not reject this, but set up the selector so that it always returns the first entry.

<Selectors: selector: TBP>+≡

```

procedure :: init => selector_init

```

<Selectors: procedures>+≡

```

subroutine selector_init (selector, weight)
  class(selector_t), intent(out) :: selector
  real(default), dimension(:), intent(in) :: weight
  real(default) :: s
  integer :: n, i
  logical, dimension(:), allocatable :: mask
  if (size (weight) == 0) &
    call msg_bug ("Selector init: zero-size weight array")
  if (any (weight < 0)) &
    call msg_bug ("Selector init: negative weight")
  s = sum (weight)
  allocate (mask (size (weight)), &
    source = weight /= 0)
  n = count (mask)
  if (n > 0) then
    allocate (selector%map (n), &
      source = pack ([i, i = 1, size (weight)], mask))
    allocate (selector%weight (n), &
      source = pack (weight / s, mask))
    allocate (selector%acc (n))
    selector%acc(1) = selector%weight(1)
    do i = 2, n - 1
      selector%acc(i) = selector%acc(i-1) + selector%weight(i)
    end do
    selector%acc(n) = 1
  else
    allocate (selector%map (1), source = 1)
    allocate (selector%weight (1), source = 0._default)
    allocate (selector%acc (1), source = 1._default)
  end if
end subroutine selector_init

```

Select an entry based upon the number `x`, which should be a uniformly distributed random number between 0 and 1.

```

<Selectors: selector: TBP>+≡
  procedure :: select => selector_select

<Selectors: procedures>+≡
  function selector_select (selector, x) result (n)
    class(selector_t), intent(in) :: selector
    real(default), intent(in) :: x
    integer :: n
    integer :: i
    if (x < 0 .or. x > 1) &
      call msg_bug ("Selector: random number out of range")
    do i = 1, size (selector%acc)
      if (x <= selector%acc(i)) exit
    end do
    n = selector%map(i)
  end function selector_select

```

Use the provided random-number generator to select an entry. (Unless there is only one entry.)

```

<Selectors: selector: TBP>+≡
  procedure :: generate => selector_generate

<Selectors: procedures>+≡
  subroutine selector_generate (selector, rng, n)
    class(selector_t), intent(in) :: selector
    class(rng_t), intent(inout) :: rng
    integer, intent(out) :: n
    real(default) :: x
    select case (size (selector%acc))
    case (1); n = 1
    case default
      call rng%generate (x)
      n = selector%select (x)
    end select
  end subroutine selector_generate

```

Determine the normalized weight for a selected entry. We use a linear search for the inverse lookup, assuming that efficiency is not an issue for this function.

```

<Selectors: selector: TBP>+≡
  procedure :: get_weight => selector_get_weight

<Selectors: procedures>+≡
  function selector_get_weight (selector, n) result (weight)
    class(selector_t), intent(in) :: selector
    integer, intent(in) :: n
    real(default) :: weight
    integer :: i
    do i = 1, size (selector%weight)
      if (selector%map(i) == n) then
        weight = selector%weight(i)
        return
      end if
    end do
    weight = 0
  end function selector_get_weight

```

```
end function selector_get_weight
```

8.2.2 Unit tests

```

<Selectors: public>+≡
  public :: selectors_test

<Selectors: tests>≡
  subroutine selectors_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    <Selectors: execute tests>
  end subroutine selectors_test

```

Basic check

Initialize the selector and draw random numbers.

```

<Selectors: execute tests>≡
  call test (selectors_1, "selectors_1", &
    "rng initialization and call", &
    u, results)

<Selectors: tests>+≡
  subroutine selectors_1 (u)
    integer, intent(in) :: u
    type(selector_t) :: selector
    class(rng_t), allocatable, target :: rng
    integer :: i, n

    write (u, "(A)")  "* Test output: selectors_1"
    write (u, "(A)")  "* Purpose: initialize a selector and test it"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize selector"
    write (u, "(A)")

    call selector%init &
      ([2._default, 3.5_default, 0._default, &
        2._default, 0.5_default, 2._default])
    call selector%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Select numbers using predictable test generator"
    write (u, "(A)")

    allocate (rng_test_t :: rng)
    call rng%init (1)

    do i = 1, 5
      call selector%generate (rng, n)
      write (u, "(1x,I0)")  n
    end do

```

```

write (u, "(A)")
write (u, "(A)")  "* Select numbers using real input number"
write (u, "(A)")

write (u, "(1x,A,I0)")  "select(0.00) = ", selector%select (0._default)
write (u, "(1x,A,I0)")  "select(0.77) = ", selector%select (0.77_default)
write (u, "(1x,A,I0)")  "select(1.00) = ", selector%select (1._default)

write (u, "(A)")
write (u, "(A)")  "* Get weight"
write (u, "(A)")

write (u, "(1x,A,ES19.12)")  "weight(2) =", selector%get_weight(2)
write (u, "(1x,A,ES19.12)")  "weight(3) =", selector%get_weight(3)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call rng%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: selectors_1"

end subroutine selectors_1

```

8.3 TAO Random-Number Generator

This module provides an implementation for the generic random-number generator. Actually, we interface the TAO random-number generator which is available via the VAMP package.

```

⟨rng_tao.f90⟩≡
  ⟨File header⟩

module rng_tao

  use kinds
  use io_units
  use format_utils, only: write_indent
  use unit_tests
  use tao_random_numbers !NODEP!

  use rng_base

  ⟨Standard module head⟩

  ⟨RNG tao: public⟩

  ⟨RNG tao: types⟩

contains

```

```
⟨RNG tao: procedures⟩
```

```
⟨RNG tao: tests⟩
```

```
end module rng_tao
```

8.3.1 Generator type

The `rng` object is actually the state of the random-number generator. The methods `initialize/reset` and `call` the generator for this state.

We keep the seed, in case we want to recover it later, and count the number of calls since seeding.

```
⟨RNG tao: public⟩≡
```

```
public :: rng_tao_t
```

```
⟨RNG tao: types⟩≡
```

```
type, extends (rng_t) :: rng_tao_t
  integer :: seed = 0
  integer :: n_calls = 0
  type(tao_random_state) :: state
contains
  ⟨RNG tao: rng tao: TBP⟩
end type rng_tao_t
```

Output: Display seed and number of calls.

```
⟨RNG tao: rng tao: TBP⟩≡
```

```
procedure :: write => rng_tao_write
```

```
⟨RNG tao: procedures⟩≡
```

```
subroutine rng_tao_write (rng, unit, indent)
  class(rng_tao_t), intent(in) :: rng
  integer, intent(in), optional :: unit, indent
  integer :: u, ind
  u = given_output_unit (unit)
  ind = 0; if (present (indent)) ind = indent
  call write_indent (u, ind)
  write (u, "(A)") "TA0 random-number generator:"
  call write_indent (u, ind)
  write (u, "(2x,A,I0)") "seed = ", rng%seed
  call write_indent (u, ind)
  write (u, "(2x,A,I0)") "calls = ", rng%n_calls
end subroutine rng_tao_write
```

The `init` method initializes the generator and sets a seed. We should implement the interface such that a single integer is sufficient for a seed.

The seed may be omitted. The default seed is 0.

```
⟨RNG tao: rng tao: TBP⟩+≡
```

```
procedure :: init => rng_tao_init
```

```

(RNG tao: procedures)+≡
  subroutine rng_tao_init (rng, seed)
    class(rng_tao_t), intent(out) :: rng
    integer, intent(in), optional :: seed
    if (present (seed)) rng%seed = seed
    call tao_random_create (rng%state, rng%seed)
  end subroutine rng_tao_init

```

The final method deallocates memory where necessary and allows for another call of `init` to reset the generator.

```

(RNG tao: rng tao: TBP)+≡
  procedure :: final => rng_tao_final

(RNG tao: procedures)+≡
  subroutine rng_tao_final (rng)
    class(rng_tao_t), intent(inout) :: rng
    call tao_random_destroy (rng%state)
  end subroutine rng_tao_final

```

These routines generate a single and an array of default-precision random numbers, respectively.

We have to convert from explicit double to abstract default precision. Under normal conditions, both are equivalent, however. Unless, someone decides to do single precision, there is always an interface for `tao_random_numbers`.

```

(RNG tao: rng tao: TBP)+≡
  procedure :: generate_single => rng_tao_generate_single
  procedure :: generate_array => rng_tao_generate_array

(RNG tao: procedures)+≡
  subroutine rng_tao_generate_single (rng, x)
    class(rng_tao_t), intent(inout) :: rng
    real(default), intent(out) :: x
    real(default) :: r
    call tao_random_number (rng%state, r)
    x = r
    rng%n_calls = rng%n_calls + 1
  end subroutine rng_tao_generate_single

  subroutine rng_tao_generate_array (rng, x)
    class(rng_tao_t), intent(inout) :: rng
    real(default), dimension(:), intent(out) :: x
    real(default) :: r
    integer :: i
    do i = 1, size (x)
      call tao_random_number (rng%state, r)
      x(i) = r
    end do
    rng%n_calls = rng%n_calls + size (x)
  end subroutine rng_tao_generate_array

```

Factory

This factory makes `rng_tao_t` generators, initialized with the seeds

$$s_i = s_0 * 2^{16} + i \quad (8.1)$$

where s_0 is the seed (a 16-bit integer) given to the factory object, and i is the index in the generated sequence of generators, starting with zero.

```
<RNG tao: public>+≡
    public :: rng_tao_factory_t
<RNG tao: types>+≡
    type, extends (rng_factory_t) :: rng_tao_factory_t
        integer(i16) :: s = 0
        integer(i16) :: i = 0
    contains
        <RNG tao: rng tao factory: TBP>
    end type rng_tao_factory_t
```

Output.

```
<RNG tao: rng tao factory: TBP>≡
    procedure :: write => rng_tao_factory_write
<RNG tao: procedures>+≡
    subroutine rng_tao_factory_write (object, unit)
        class(rng_tao_factory_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A,2(IO,A))") &
            "RNG factory: tao (" , object%s, ", ", object%i, ")"
    end subroutine rng_tao_factory_write
```

Initialize, translating the given seed.

```
<RNG tao: rng tao factory: TBP>+≡
    procedure :: init => rng_tao_factory_init
<RNG tao: procedures>+≡
    subroutine rng_tao_factory_init (factory, seed)
        class(rng_tao_factory_t), intent(out) :: factory
        integer(i16), intent(in), optional :: seed
        if (present (seed)) factory%s = seed
    end subroutine rng_tao_factory_init
```

```
<RNG tao: rng tao factory: TBP>+≡
    procedure :: make => rng_tao_factory_make
<RNG tao: procedures>+≡
    subroutine rng_tao_factory_make (factory, rng)
        class(rng_tao_factory_t), intent(inout) :: factory
        class(rng_t), intent(out), allocatable :: rng
        allocate (rng_tao_t :: rng)
        select type (rng)
            type is (rng_tao_t)
```

```

        call rng%init (factory%s * 65536 + factory%i)
        factory%i = int (factory%i + 1, kind = i16)
    end select
end subroutine rng_tao_factory_make

```

8.3.2 Unit tests

```

<RNG tao: public>+≡
    public :: rng_tao_test

<RNG tao: tests>≡
    subroutine rng_tao_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <RNG tao: execute tests>
    end subroutine rng_tao_test

```

Generator check

Initialize the generator and draw random numbers.

```

<RNG tao: execute tests>≡
    call test (rng_tao_1, "rng_tao_1", &
        "rng initialization and call", &
        u, results)

<RNG tao: tests>+≡
    subroutine rng_tao_1 (u)
        integer, intent(in) :: u
        class(rng_t), allocatable, target :: rng

        real(default) :: x
        real(default), dimension(2) :: x2

        write (u, "(A)")  "* Test output: rng_tao_1"
        write (u, "(A)")  "*   Purpose: initialize and call the TAO random-number &
            &generator"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize generator (default seed)"
        write (u, "(A)")

        allocate (rng_tao_t :: rng)
        call rng%init ()

        call rng%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Get random number"
        write (u, "(A)")

        call rng%generate (x)
        write (u, "(A,2(1x,F9.7))")  "x =", x
    end subroutine rng_tao_1

```



```

write (u, "(A)")
write (u, "(A)")  "* Get random number pair"
write (u, "(A)")

call rng%generate (x2)
write (u, "(A,2(1x,F9.7))")  "x =", x2

write (u, "(A)")
call rng%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call rng%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rng_tao_1"

end subroutine rng_tao_1

```

Factory check

Set up a factory and spawn generators.

```

<RNG tao: execute tests>+≡
  call test (rng_tao_2, "rng_tao_2", &
    "rng factory", &
    u, results)

<RNG tao: tests>+≡
subroutine rng_tao_2 (u)
  integer, intent(in) :: u
  type(rng_tao_factory_t) :: rng_factory
  class(rng_t), allocatable :: rng
  real(default) :: x

  write (u, "(A)")  "* Test output: rng_tao_2"
  write (u, "(A)")  "* Purpose: initialize and use a rng factory"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize factory"
  write (u, "(A)")

  call rng_factory%init ()
  call rng_factory%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Make a generator"
  write (u, "(A)")

  call rng_factory%make (rng)
  call rng%write (u)
  call rng%generate (x)

```

```

write (u, *)
write (u, "(1x,A,F7.5)") "x = ", x
call rng%final ()
deallocate (rng)

write (u, "(A)")
write (u, "(A)")  "* Repeat"
write (u, "(A)")

call rng_factory%make (rng)
call rng%write (u)
call rng%generate (x)
write (u, *)
write (u, "(1x,A,F7.5)") "x = ", x
call rng%final ()
deallocate (rng)

write (u, *)
call rng_factory%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize factory with different seed"
write (u, "(A)")

call rng_factory%init (1_i16)
call rng_factory%write (u)

write (u, "(A)")
write (u, "(A)")  "* Make a generator"
write (u, "(A)")

call rng_factory%make (rng)
call rng%write (u)
call rng%generate (x)
write (u, *)
write (u, "(1x,A,F7.5)") "x = ", x
call rng%final ()
deallocate (rng)

write (u, *)
call rng_factory%write (u)

write (u, "(A)")
write (u, "(A)")  "* Test output end: rng_tao_2"

end subroutine rng_tao_2

```

Chapter 9

Physics

Here we collect definitions and functions that we need for (particle) physics in general, to make them available for the more specific needs of WHIZARD.

physics_defs Physical constants.

c_particles A simple data type for particles which is C compatible.

lorentz Define three-vectors, four-vectors and Lorentz transformations and common operations for them.

sm_physics Here, running functions are stored for special kinematical setup like running coupling constants, Catani-Seymour dipoles, or Sudakov factors.

sm_qcd Definitions and methods for dealing with the running QCD coupling.

shower_algorithms Algorithms typically used in Parton Showers as well as in their matching to NLO computations, e.g. with the POWHEG method.

9.1 Physics Constants

There is also the generic `constants` module. The constants listed here are more specific for particle physics.

```
<physics_defs.f90>≡  
<File header>  
  
module physics_defs  
  
  <Use kinds>  
  use constants, only: one, two, three  
  
  <Standard module head>  
  
  <Physics defs: public parameters>  
  
end module physics_defs
```

9.1.1 Units

Conversion from energy units to cross-section units.

```
<Physics defs: public parameters>≡  
  real(default), parameter, public :: &  
    conv = 0.38937966e12_default
```

Rescaling factor.

```
<Physics defs: public parameters>+≡  
  real(default), parameter, public :: &  
    pb_per_fb = 1.e-3_default
```

String for the default energy and cross-section units.

```
<Physics defs: public parameters>+≡  
  character(*), parameter, public :: &  
    energy_unit = "GeV"  
  character(*), parameter, public :: &  
    cross_section_unit = "fb"
```

9.1.2 SM and QCD constants

```
<Physics defs: public parameters>+≡  
  real(default), parameter, public :: &  
    NC = three, &  
    CF = (NC**2 - one) / two / NC, &  
    CA = NC, &  
    TR = one / two
```

9.1.3 Parameter Reference values

These are used exclusively in the context of running QCD parameters. In other contexts, we rely on the uniform parameter set as provided by the model definition, modifiable by the user.

```
<Physics defs: public parameters>+≡
```

```

real(default), public, parameter :: MZ_REF = 91.188_default
real(default), public, parameter :: ALPHA_QCD_MZ_REF = 0.1178_default
real(default), public, parameter :: LAMBDA_QCD_REF = 200.e-3_default

```

9.1.4 Particle codes

Let us define a few particle codes independent of the model.

We need an UNDEFINED value:

```

⟨Physics defs: public parameters⟩+=≡
    integer, parameter, public :: UNDEFINED = 0

```

SM fermions:

```

⟨Physics defs: public parameters⟩+=≡
    integer, parameter, public :: ELECTRON = 11
    integer, parameter, public :: ELECTRON_NEUTRINO = 12
    integer, parameter, public :: MUON = 13
    integer, parameter, public :: MUON_NEUTRINO = 14
    integer, parameter, public :: TAU = 15
    integer, parameter, public :: TAU_NEUTRINO = 16

```

Gauge bosons:

```

⟨Physics defs: public parameters⟩+=≡
    integer, parameter, public :: GLUON = 21
    integer, parameter, public :: PHOTON = 22
    integer, parameter, public :: Z_BOSON = 23
    integer, parameter, public :: W_BOSON = 24

```

Light mesons:

```

⟨Physics defs: public parameters⟩+=≡
    integer, parameter, public :: PION = 111
    integer, parameter, public :: PIPLUS = 211
    integer, parameter, public :: PIMINUS = - PIPLUS

```

Di-Quarks:

```

⟨Physics defs: public parameters⟩+=≡
    integer, parameter, public :: UD0 = 2101
    integer, parameter, public :: UD1 = 2103
    integer, parameter, public :: UU1 = 2203

```

Mesons:

```

⟨Physics defs: public parameters⟩+=≡
    integer, parameter, public :: K0L = 130
    integer, parameter, public :: K0S = 310
    integer, parameter, public :: K0 = 311
    integer, parameter, public :: KPLUS = 321
    integer, parameter, public :: DPLUS = 411
    integer, parameter, public :: D0 = 421
    integer, parameter, public :: B0 = 511
    integer, parameter, public :: BPLUS = 521

```

Light baryons:

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: PROTON = 2212  
  integer, parameter, public :: NEUTRON = 2112  
  integer, parameter, public :: DELTAPLUSPLUS = 2224  
  integer, parameter, public :: DELTAPLUS = 2214  
  integer, parameter, public :: DELTA0 = 2114  
  integer, parameter, public :: DELTAMINUS = 1114
```

Strange baryons:

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: SIGMAPLUS = 3222  
  integer, parameter, public :: SIGMA0 = 3212  
  integer, parameter, public :: SIGMAMINUS = 3112
```

Charmed baryons:

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: SIGMACPLUSPLUS = 4222  
  integer, parameter, public :: SIGMACPLUS = 4212  
  integer, parameter, public :: SIGMAC0 = 4112
```

Bottom baryons:

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: SIGMAB0 = 5212  
  integer, parameter, public :: SIGMABPLUS = 5222
```

81-100 are reserved for internal codes. Hadron and beam remnants:

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: BEAM_REMNANT = 9999  
  integer, parameter, public :: HADRON_REMNANT = 90  
  integer, parameter, public :: HADRON_REMNANT_SINGLET = 91  
  integer, parameter, public :: HADRON_REMNANT_TRIPLET = 92  
  integer, parameter, public :: HADRON_REMNANT_OCTET = 93
```

Further particle codes for internal use:

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: INTERNAL = 94  
  integer, parameter, public :: INVALID = 97  
  
  integer, parameter, public :: COMPOSITE = 99
```

9.1.5 Spin codes

Somewhat redundant, but for better readability we define named constants for spin types. If the mass is nonzero, this is equal to the number of degrees of freedom.

```
(Physics defs: public parameters)+≡  
  integer, parameter, public :: UNKNOWN = 0  
  integer, parameter, public :: SCALAR = 1, SPINOR = 2, VECTOR = 3, &
```

VECTORSPINOR = 4, TENSOR = 5

Isospin types and charge types are counted in an analogous way, where charge type 1 is charge 0, 2 is charge 1/3, and so on. Zero always means unknown. Note that charge and isospin types have an explicit sign.

Color types are defined as the dimension of the representation.

9.1.6 NLO status codes

Used to specify whether a component of a process instance is associated with a Born, real-subtracted, virtual-subtracted or subtraction-dummy matrix element.

```
(Physics defs: public parameters) +=  
integer, parameter, public :: BORN = 0  
integer, parameter, public :: NLO_REAL = 1  
integer, parameter, public :: NLO_VIRTUAL = 2  
integer, parameter, public :: NLO_PDF = 3  
integer, parameter, public :: NLO_SUBTRACTION = 4
```

9.2 C-compatible Particle Type

For easy communication with C code, we introduce a simple C-compatible type for particles. The components are either default C integers or default C doubles.

The `c_prt` type is transparent, and its contents should be regarded as part of the interface.

```

<c_particles.f90>≡
  <File header>

  module c_particles

    use, intrinsic :: iso_c_binding !NODEP!

    use io_units
    use format_defs, only: FMT_14, FMT_19

    <Standard module head>

    <C Particles: public>

    <C Particles: types>

    contains

    <C Particles: procedures>
    end module c_particles

  <C Particles: public>≡
    public :: c_prt_t

  <C Particles: types>≡
    type, bind(C) :: c_prt_t
      integer(c_int) :: type = 0
      integer(c_int) :: pdg = 0
      integer(c_int) :: polarized = 0
      integer(c_int) :: h = 0
      real(c_double) :: pe = 0
      real(c_double) :: px = 0
      real(c_double) :: py = 0
      real(c_double) :: pz = 0
      real(c_double) :: p2 = 0
    end type c_prt_t

```

This is for debugging only, there is no C binding. It is a simplified version of `prt_write`.

```

  <C Particles: public>+≡
    public :: c_prt_write

  <C Particles: procedures>≡
    subroutine c_prt_write (prt, unit)
      type(c_prt_t), intent(in) :: prt
      integer, intent(in), optional :: unit
      integer :: u
      u = given_output_unit (unit); if (u < 0) return

```



```

write (u, "(1x,A)", advance="no")  prt("
write (u, "(I0,':')", advance="no")  prt%type
if (prt%polarized /= 0) then
    write (u, "(I0,'/',I0,'|')", advance="no")  prt%pdg, prt%h
else
    write (u, "(I0,'|')", advance="no")  prt%pdg
end if
write (u, "(" // FMT_14 // ",',';" // FMT_14 // ",','," // &
    FMT_14 // ",','," // FMT_14 // ") ", advance="no") &
    prt%pe, prt%px, prt%py, prt%pz
write (u, "( '|'," // FMT_19 // ") ", advance="no")  prt%p2
write (u, "(A)"  " ) "
end subroutine c_prt_write

```

9.3 Lorentz algebra

Define Lorentz vectors, three-vectors, boosts, and some functions to manipulate them.

To make maximum use of this, all functions, if possible, are declared elemental (or pure, if this is not possible).

```
<lorentz.f90>≡  
  <File header>  
  
  module lorentz  
  
    <Use kinds with double>  
    use io_units  
    use constants, only: pi, twopi, degree, zero, one, eps0  
    use format_defs, only: FMT_13, FMT_15, FMT_17, FMT_19  
    use format_utils, only: pac_fmt  
    use diagnostics  
    use c_particles  
  
    <Standard module head>  
  
    <Lorentz: public>  
  
    <Lorentz: public operators>  
  
    <Lorentz: public functions>  
  
    <Lorentz: types>  
  
    <Lorentz: parameters>  
  
    <Lorentz: interfaces>  
  
    contains  
  
    <Lorentz: procedures>  
  end module lorentz
```

9.3.1 Three-vectors

First of all, let us introduce three-vectors in a trivial way. The functions and overloaded elementary operations clearly are too much overhead, but we like to keep the interface for three-vectors and four-vectors exactly parallel. By the way, we might attach a label to a vector by extending the type definition later.

```
<Lorentz: public>≡  
  public :: vector3_t  
  
<Lorentz: types>≡  
  type :: vector3_t  
    real(default), dimension(3) :: p  
  end type vector3_t
```

Output a vector

```

(Lorentz: public)+≡
    public :: vector3_write

(Lorentz: procedures)≡
    subroutine vector3_write (p, unit, testflag)
        type(vector3_t), intent(in) :: p
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: testflag
        character(len=7) :: fmt
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        call pac_fmt (fmt, FMT_19, FMT_15, testflag)
        write(u, "(1x,A,3(1x," // fmt // "))" 'P = ', p%p
    end subroutine vector3_write

```

This is a three-vector with zero components

```

(Lorentz: public)+≡
    public :: vector3_null

(Lorentz: parameters)≡
    type(vector3_t), parameter :: vector3_null = &
        vector3_t ([ zero, zero, zero ])

```

Canonical three-vector:

```

(Lorentz: public)+≡
    public :: vector3_canonical

(Lorentz: procedures)+≡
    elemental function vector3_canonical (k) result (p)
        type(vector3_t) :: p
        integer, intent(in) :: k
        p = vector3_null
        p%p(k) = 1
    end function vector3_canonical

```

A moving particle (k -axis, or arbitrary axis). Note that the function for the generic momentum cannot be elemental.

```

(Lorentz: public)+≡
    public :: vector3_moving

(Lorentz: interfaces)≡
    interface vector3_moving
        module procedure vector3_moving_canonical
        module procedure vector3_moving_generic
    end interface

(Lorentz: procedures)+≡
    elemental function vector3_moving_canonical (p, k) result(q)
        type(vector3_t) :: q
        real(default), intent(in) :: p
        integer, intent(in) :: k
        q = vector3_null
        q%p(k) = p

```

```

end function vector3_moving_canonical
pure function vector3_moving_generic (p) result(q)
  real(default), dimension(3), intent(in) :: p
  type(vector3_t) :: q
  q%p = p
end function vector3_moving_generic

```

Equality and inequality

```

<Lorentz: public operators>≡
  public :: operator(==), operator(/=)

<Lorentz: interfaces>+≡
  interface operator(==)
    module procedure vector3_eq
  end interface
  interface operator(/=)
    module procedure vector3_neq
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_eq (p, q) result (r)
    logical :: r
    type(vector3_t), intent(in) :: p,q
    r = all (abs (p%p - q%p) < eps0)
  end function vector3_eq
  elemental function vector3_neq (p, q) result (r)
    logical :: r
    type(vector3_t), intent(in) :: p,q
    r = any (abs(p%p - q%p) > eps0)
  end function vector3_neq

```

Define addition and subtraction

```

<Lorentz: public operators>+≡
  public :: operator(+), operator(-)

<Lorentz: interfaces>+≡
  interface operator(+)
    module procedure add_vector3
  end interface
  interface operator(-)
    module procedure sub_vector3
  end interface

<Lorentz: procedures>+≡
  elemental function add_vector3 (p, q) result (r)
    type(vector3_t) :: r
    type(vector3_t), intent(in) :: p,q
    r%p = p%p + q%p
  end function add_vector3
  elemental function sub_vector3 (p, q) result (r)
    type(vector3_t) :: r
    type(vector3_t), intent(in) :: p,q
    r%p = p%p - q%p
  end function sub_vector3

```

The multiplication sign is overloaded with scalar multiplication; similarly division:

```

(Lorentz: public operators)+≡
    public :: operator(*), operator(/)

(Lorentz: interfaces)+≡
    interface operator(*)
        module procedure prod_integer_vector3, prod_vector3_integer
        module procedure prod_real_vector3, prod_vector3_real
    end interface
    interface operator(/)
        module procedure div_vector3_real, div_vector3_integer
    end interface

(Lorentz: procedures)+≡
    elemental function prod_real_vector3 (s, p) result (q)
        type(vector3_t) :: q
        real(default), intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_real_vector3
    elemental function prod_vector3_real (p, s) result (q)
        type(vector3_t) :: q
        real(default), intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_vector3_real
    elemental function div_vector3_real (p, s) result (q)
        type(vector3_t) :: q
        real(default), intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = p%p/s
    end function div_vector3_real
    elemental function prod_integer_vector3 (s, p) result (q)
        type(vector3_t) :: q
        integer, intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_integer_vector3
    elemental function prod_vector3_integer (p, s) result (q)
        type(vector3_t) :: q
        integer, intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_vector3_integer
    elemental function div_vector3_integer (p, s) result (q)
        type(vector3_t) :: q
        integer, intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = p%p/s
    end function div_vector3_integer

```

The multiplication sign can also indicate scalar products:

```

(Lorentz: interfaces)+≡

```

```

interface operator(*)
  module procedure prod_vector3
end interface

<Lorentz: procedures>+≡
  elemental function prod_vector3 (p, q) result (s)
    real(default) :: s
    type(vector3_t), intent(in) :: p,q
    s = dot_product (p%p, q%p)
  end function prod_vector3

<Lorentz: public functions>≡
  public :: cross_product

<Lorentz: interfaces>+≡
  interface cross_product
    module procedure vector3_cross_product
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_cross_product (p, q) result (r)
    type(vector3_t) :: r
    type(vector3_t), intent(in) :: p,q
    integer :: i
    do i=1,3
      r%p(i) = dot_product (p%p, matmul(epsilon_three(i,:,:), q%p))
    end do
  end function vector3_cross_product

```

Exponentiation is defined only for integer powers. Odd powers mean take the square root; so `p**1` is the length of `p`.

```

<Lorentz: public operators>+≡
  public :: operator(**)

<Lorentz: interfaces>+≡
  interface operator(**)
    module procedure power_vector3
  end interface

<Lorentz: procedures>+≡
  elemental function power_vector3 (p, e) result (s)
    real(default) :: s
    type(vector3_t), intent(in) :: p
    integer, intent(in) :: e
    s = dot_product (p%p, p%p)
    if (e/=2) then
      if (mod(e,2)==0) then
        s = s**(e/2)
      else
        s = sqrt(s)**e
      end if
    end if
  end function power_vector3

```

Finally, we need a negation.

```

<Lorentz: interfaces>+≡
    interface operator(-)
        module procedure negate_vector3
    end interface

<Lorentz: procedures>+≡
    elemental function negate_vector3 (p) result (q)
        type(vector3_t) :: q
        type(vector3_t), intent(in) :: p
        integer :: i
        do i = 1, 3
            if (abs (p%p(i)) < eps0) then
                q%p(i) = 0
            else
                q%p(i) = -p%p(i)
            end if
        end do
    end function negate_vector3

```

The sum function can be useful:

```

<Lorentz: public functions>+≡
    public :: sum

<Lorentz: interfaces>+≡
    interface sum
        module procedure sum_vector3
    end interface

<Lorentz: public>+≡
    public :: vector3_set_component

<Lorentz: procedures>+≡
    subroutine vector3_set_component (p, i, value)
        type(vector3_t), intent(inout) :: p
        integer, intent(in) :: i
        real(default), intent(in) :: value
        p%p(i) = value
    end subroutine vector3_set_component

<Lorentz: procedures>+≡
    pure function sum_vector3 (p) result (q)
        type(vector3_t) :: q
        type(vector3_t), dimension(:), intent(in) :: p
        integer :: i
        do i=1, 3
            q%p(i) = sum (p%p(i))
        end do
    end function sum_vector3

```

Any component:

```

<Lorentz: public>+≡
    public :: vector3_get_component

```

```

<Lorentz: procedures>+≡
  elemental function vector3_get_component (p, k) result (c)
    type(vector3_t), intent(in) :: p
    integer, intent(in) :: k
    real(default) :: c
    c = p%p(k)
  end function vector3_get_component

```

Extract all components. This is not elemental.

```

<Lorentz: public>+≡
  public :: vector3_get_components

<Lorentz: procedures>+≡
  pure function vector3_get_components (p) result (a)
    type(vector3_t), intent(in) :: p
    real(default), dimension(3) :: a
    a = p%p
  end function vector3_get_components

```

This function returns the direction of a three-vector, i.e., a normalized three-vector. If the vector is null, we return a null vector.

```

<Lorentz: public functions>+≡
  public :: direction

<Lorentz: interfaces>+≡
  interface direction
    module procedure vector3_get_direction
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_get_direction (p) result (q)
    type(vector3_t) :: q
    type(vector3_t), intent(in) :: p
    real(default) :: pp
    pp = p**1
    if (pp > eps0) then
      q%p = p%p / pp
    else
      q%p = 0
    end if
  end function vector3_get_direction

```

9.3.2 Four-vectors

In four-vectors the zero-component needs special treatment, therefore we do not use the standard operations. Sure, we pay for the extra layer of abstraction by losing efficiency; so we have to assume that the time-critical applications do not involve four-vector operations.

```

<Lorentz: public>+≡
  public :: vector4_t

```



```

<Lorentz: types>+≡
  type :: vector4_t
    real(default), dimension(0:3) :: p = &
      [zero, zero, zero, zero]
  contains
    <Lorentz: vector4: TBP>
  end type vector4_t

```

Output a vector

```

<Lorentz: public>+≡
  public :: vector4_write

<Lorentz: vector4: TBP>≡
  procedure :: write => vector4_write

<Lorentz: procedures>+≡
  subroutine vector4_write (p, unit, show_mass, testflag, compressed)
    class(vector4_t), intent(in) :: p
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_mass, testflag, compressed
    logical :: comp, sm
    integer :: u
    character(len=7) :: fmt
    comp = .false.; if (present (compressed)) comp = compressed
    sm = .false.; if (present (show_mass)) sm = show_mass
    call pac_fmt (fmt, FMT_19, FMT_13, testflag)
    u = given_output_unit (unit); if (u < 0) return
    if (comp) then
      write (u, "(4(F12.3,1X))", advance="no") p%p(0:3)
    else
      write(u, "(1x,A,1x," // fmt // ")") 'E = ', p%p(0)
      write(u, "(1x,A,3(1x," // fmt // ")") 'P = ', p%p(1:)
      if (sm) write (u, "(1x,A,1x," // fmt // ")") 'M = ', p**1
    end if
  end subroutine vector4_write

```

Binary I/O

```

<Lorentz: public>+≡
  public :: vector4_write_raw
  public :: vector4_read_raw

<Lorentz: procedures>+≡
  subroutine vector4_write_raw (p, u)
    type(vector4_t), intent(in) :: p
    integer, intent(in) :: u
    write (u) p%p
  end subroutine vector4_write_raw

  subroutine vector4_read_raw (p, u, iostat)
    type(vector4_t), intent(out) :: p
    integer, intent(in) :: u
    integer, intent(out), optional :: iostat
    read (u, iostat=iostat) p%p
  end subroutine vector4_read_raw

```

This is a four-vector with zero components

```

(Lorentz: public)+≡
    public :: vector4_null

(Lorentz: parameters)+≡
    type(vector4_t), parameter :: vector4_null = &
        vector4_t ([ zero, zero, zero, zero ])

```

Canonical four-vector:

```

(Lorentz: public)+≡
    public :: vector4_canonical

(Lorentz: procedures)+≡
    elemental function vector4_canonical (k) result (p)
        type(vector4_t) :: p
        integer, intent(in) :: k
        p = vector4_null
        p%p(k) = 1
    end function vector4_canonical

```

A particle at rest:

```

(Lorentz: public)+≡
    public :: vector4_at_rest

(Lorentz: procedures)+≡
    elemental function vector4_at_rest (m) result (p)
        type(vector4_t) :: p
        real(default), intent(in) :: m
        p = vector4_t ([ m, zero, zero, zero ])
    end function vector4_at_rest

```

A moving particle (k -axis, or arbitrary axis)

```

(Lorentz: public)+≡
    public :: vector4_moving

(Lorentz: interfaces)+≡
    interface vector4_moving
        module procedure vector4_moving_canonical
        module procedure vector4_moving_generic
    end interface

(Lorentz: procedures)+≡
    elemental function vector4_moving_canonical (E, p, k) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: E, p
        integer, intent(in) :: k
        q = vector4_at_rest(E)
        q%p(k) = p
    end function vector4_moving_canonical
    elemental function vector4_moving_generic (E, p) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: E
        type(vector3_t), intent(in) :: p
        q%p(0) = E

```

```

    q%p(1:) = p%p
end function vector4_moving_generic

```

Equality and inequality

```

<Lorentz: interfaces>+≡
    interface operator(==)
        module procedure vector4_eq
    end interface
    interface operator(/=)
        module procedure vector4_neq
    end interface

<Lorentz: procedures>+≡
    elemental function vector4_eq (p, q) result (r)
        logical :: r
        type(vector4_t), intent(in) :: p,q
        r = all (abs (p%p - q%p) < eps0)
    end function vector4_eq
    elemental function vector4_neq (p, q) result (r)
        logical :: r
        type(vector4_t), intent(in) :: p,q
        r = any (abs (p%p - q%p) > eps0)
    end function vector4_neq

```

Addition and subtraction:

```

<Lorentz: interfaces>+≡
    interface operator(+)
        module procedure add_vector4
    end interface
    interface operator(-)
        module procedure sub_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function add_vector4 (p,q) result (r)
        type(vector4_t) :: r
        type(vector4_t), intent(in) :: p,q
        r%p = p%p + q%p
    end function add_vector4
    elemental function sub_vector4 (p,q) result (r)
        type(vector4_t) :: r
        type(vector4_t), intent(in) :: p,q
        r%p = p%p - q%p
    end function sub_vector4

```

We also need scalar multiplication and division:

```

<Lorentz: interfaces>+≡
    interface operator(*)
        module procedure prod_real_vector4, prod_vector4_real
        module procedure prod_integer_vector4, prod_vector4_integer
    end interface
    interface operator(/)
        module procedure div_vector4_real

```

```

        module procedure div_vector4_integer
    end interface
<Lorentz: procedures>+≡
    elemental function prod_real_vector4 (s, p) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: s
        type(vector4_t), intent(in) :: p
        q%p = s * p%p
    end function prod_real_vector4
    elemental function prod_vector4_real (p, s) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: s
        type(vector4_t), intent(in) :: p
        q%p = s * p%p
    end function prod_vector4_real
    elemental function div_vector4_real (p, s) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: s
        type(vector4_t), intent(in) :: p
        q%p = p%p/s
    end function div_vector4_real
    elemental function prod_integer_vector4 (s, p) result (q)
        type(vector4_t) :: q
        integer, intent(in) :: s
        type(vector4_t), intent(in) :: p
        q%p = s * p%p
    end function prod_integer_vector4
    elemental function prod_vector4_integer (p, s) result (q)
        type(vector4_t) :: q
        integer, intent(in) :: s
        type(vector4_t), intent(in) :: p
        q%p = s * p%p
    end function prod_vector4_integer
    elemental function div_vector4_integer (p, s) result (q)
        type(vector4_t) :: q
        integer, intent(in) :: s
        type(vector4_t), intent(in) :: p
        q%p = p%p/s
    end function div_vector4_integer

```

Scalar products and squares in the Minkowski sense:

```

<Lorentz: interfaces>+≡
    interface operator(*)
        module procedure prod_vector4
    end interface
    interface operator(**)
        module procedure power_vector4
    end interface
<Lorentz: procedures>+≡
    elemental function prod_vector4 (p, q) result (s)
        real(default) :: s
        type(vector4_t), intent(in) :: p,q
        s = p%p(0)*q%p(0) - dot_product(p%p(1:), q%p(1:))

```

```
end function prod_vector4
```

The power operation for four-vectors is signed, i.e., p^{**1} is positive for timelike and negative for spacelike vectors. Note that $(p^{**1})^{**2}$ is not necessarily equal to p^{**2} .

```
<Lorentz: procedures>+≡
elemental function power_vector4 (p, e) result (s)
  real(default) :: s
  type(vector4_t), intent(in) :: p
  integer, intent(in) :: e
  s = p*p
  if (e/=2) then
    if (mod(e,2)==0) then
      s = s**(e/2)
    elseif (s>=0) then
      s = sqrt(s)**e
    else
      s = -(sqrt(abs(s))**e)
    end if
  end if
end function power_vector4
```

Finally, we introduce a negation

```
<Lorentz: interfaces>+≡
interface operator(-)
  module procedure negate_vector4
end interface

<Lorentz: procedures>+≡
elemental function negate_vector4 (p) result (q)
  type(vector4_t) :: q
  type(vector4_t), intent(in) :: p
  integer :: i
  do i = 0, 3
    if (abs (p%p(i)) < eps0) then
      q%p(i) = 0
    else
      q%p(i) = -p%p(i)
    end if
  end do
end function negate_vector4
```

The sum function can be useful:

```
<Lorentz: interfaces>+≡
interface sum
  module procedure sum_vector4, sum_vector4_mask
end interface

<Lorentz: procedures>+≡
pure function sum_vector4 (p) result (q)
  type(vector4_t) :: q
  type(vector4_t), dimension(:), intent(in) :: p
  integer :: i
```

```

do i = 0, 3
  q%p(i) = sum (p%p(i))
end do
end function sum_vector4

pure function sum_vector4_mask (p, mask) result (q)
  type(vector4_t) :: q
  type(vector4_t), dimension(:), intent(in) :: p
  logical, dimension(:), intent(in) :: mask
  integer :: i
  do i = 0, 3
    q%p(i) = sum (p%p(i), mask=mask)
  end do
end function sum_vector4_mask

```

9.3.3 Conversions

Manually set a component of the four-vector:

```

<Lorentz: public>+≡
  public :: vector4_set_component

<Lorentz: procedures>+≡
  subroutine vector4_set_component (p, k, c)
    type(vector4_t), intent(inout) :: p
    integer, intent(in) :: k
    real(default), intent(in) :: c
    p%p(k) = c
  end subroutine vector4_set_component

```

Any component:

```

<Lorentz: public>+≡
  public :: vector4_get_component

<Lorentz: procedures>+≡
  elemental function vector4_get_component (p, k) result (c)
    real(default) :: c
    type(vector4_t), intent(in) :: p
    integer, intent(in) :: k
    c = p%p(k)
  end function vector4_get_component

```

Extract all components. This is not elemental.

```

<Lorentz: public>+≡
  public :: vector4_get_components

<Lorentz: procedures>+≡
  pure function vector4_get_components (p) result (a)
    real(default), dimension(0:3) :: a
    type(vector4_t), intent(in) :: p
    a = p%p
  end function vector4_get_components

```

This function returns the space part of a four-vector, such that we can apply three-vector operations on it:

```

(Lorentz: public functions)+≡
    public :: space_part

(Lorentz: interfaces)+≡
    interface space_part
        module procedure vector4_get_space_part
    end interface

(Lorentz: procedures)+≡
    elemental function vector4_get_space_part (p) result (q)
        type(vector3_t) :: q
        type(vector4_t), intent(in) :: p
        q%p = p%p(1:)
    end function vector4_get_space_part

```

This function returns the direction of a four-vector, i.e., a normalized three-vector. If the four-vector has zero space part, we return a null vector.

```

(Lorentz: interfaces)+≡
    interface direction
        module procedure vector4_get_direction
    end interface

(Lorentz: procedures)+≡
    elemental function vector4_get_direction (p) result (q)
        type(vector3_t) :: q
        type(vector4_t), intent(in) :: p
        real(default) :: qq
        q%p = p%p(1:)
        qq = q**1
        if (abs(qq) > eps0) then
            q%p = q%p / qq
        else
            q%p = 0
        end if
    end function vector4_get_direction

```

This function returns the four-vector as an ordinary array. A second version for an array of four-vectors.

```

(Lorentz: public)+≡
    public :: assignment (=)

(Lorentz: interfaces)+≡
    interface assignment (=)
        module procedure array_from_vector4_1, array_from_vector4_2, &
            array_from_vector3_1, array_from_vector3_2, &
            vector4_from_array, vector3_from_array
    end interface

(Lorentz: procedures)+≡
    pure subroutine array_from_vector4_1 (a, p)
        real(default), dimension(:), intent(out) :: a
        type(vector4_t), intent(in) :: p
        a = p%p

```

```

end subroutine array_from_vector4_1

pure subroutine array_from_vector4_2 (a, p)
  type(vector4_t), dimension(:), intent(in) :: p
  real(default), dimension(:,:), intent(out) :: a
  integer :: i
  forall (i=1:size(p))
    a(:,i) = p(i)%p
  end forall
end subroutine array_from_vector4_2

pure subroutine array_from_vector3_1 (a, p)
  real(default), dimension(:), intent(out) :: a
  type(vector3_t), intent(in) :: p
  a = p%p
end subroutine array_from_vector3_1

pure subroutine array_from_vector3_2 (a, p)
  type(vector3_t), dimension(:), intent(in) :: p
  real(default), dimension(:,:), intent(out) :: a
  integer :: i
  forall (i=1:size(p))
    a(:,i) = p(i)%p
  end forall
end subroutine array_from_vector3_2

pure subroutine vector4_from_array (p, a)
  type(vector4_t), intent(out) :: p
  real(default), dimension(:), intent(in) :: a
  p%p(0:3) = a
end subroutine vector4_from_array

pure subroutine vector3_from_array (p, a)
  type(vector3_t), intent(out) :: p
  real(default), dimension(:), intent(in) :: a
  p%p(1:3) = a
end subroutine vector3_from_array

<Lorentz: vector4: TBP>+≡
  procedure :: to_pythia6 => vector4_to_pythia6

<Lorentz: procedures>+≡
  pure function vector4_to_pythia6 (vector4) result (p)
    real(double), dimension(1:5) :: p
    class(vector4_t), intent(in) :: vector4
    p(1:3) = vector4%p(1:3)
    p(4) = vector4%p(0)
    p(5) = vector4 ** 2
  end function vector4_to_pythia6

```

Transform the momentum of a `c_prt` object into a four-vector and vice versa:

```

<Lorentz: interfaces>+≡
  interface assignment (=)

```



```

        module procedure vector4_from_c_prt, c_prt_from_vector4
    end interface
    <Lorentz: procedures>+≡
    pure subroutine vector4_from_c_prt (p, c_prt)
        type(vector4_t), intent(out) :: p
        type(c_prt_t), intent(in) :: c_prt
        p%p(0) = c_prt%pe
        p%p(1) = c_prt%px
        p%p(2) = c_prt%py
        p%p(3) = c_prt%pz
    end subroutine vector4_from_c_prt

    pure subroutine c_prt_from_vector4 (c_prt, p)
        type(c_prt_t), intent(out) :: c_prt
        type(vector4_t), intent(in) :: p
        c_prt%pe = p%p(0)
        c_prt%px = p%p(1)
        c_prt%py = p%p(2)
        c_prt%pz = p%p(3)
        c_prt%p2 = p ** 2
    end subroutine c_prt_from_vector4

```

Initialize a `c_prt_t` object with the components of a four-vector as its kinematical entries. Compute the invariant mass, or use the optional mass-squared value instead.

```

    <Lorentz: public>+≡
    public :: vector4_to_c_prt

    <Lorentz: procedures>+≡
    elemental function vector4_to_c_prt (p, p2) result (c_prt)
        type(c_prt_t) :: c_prt
        type(vector4_t), intent(in) :: p
        real(default), intent(in), optional :: p2
        c_prt%pe = p%p(0)
        c_prt%px = p%p(1)
        c_prt%py = p%p(2)
        c_prt%pz = p%p(3)
        if (present (p2)) then
            c_prt%p2 = p2
        else
            c_prt%p2 = p ** 2
        end if
    end function vector4_to_c_prt

```

9.3.4 Angles

Return the angles in a canonical system. The angle ϕ is defined between $0 \leq \phi < 2\pi$. In degenerate cases, return zero.

```

    <Lorentz: public functions>+≡
    public :: azimuthal_angle

```

```

<Lorentz: interfaces>+≡
  interface azimuthal_angle
    module procedure vector3_azimuthal_angle
    module procedure vector4_azimuthal_angle
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_azimuthal_angle (p) result (phi)
    real(default) :: phi
    type(vector3_t), intent(in) :: p
    if (any (abs (p%p(1:2)) > 0)) then
      phi = atan2(p%p(2), p%p(1))
      if (phi < 0) phi = phi + twopi
    else
      phi = 0
    end if
  end function vector3_azimuthal_angle
  elemental function vector4_azimuthal_angle (p) result (phi)
    real(default) :: phi
    type(vector4_t), intent(in) :: p
    phi = vector3_azimuthal_angle (space_part (p))
  end function vector4_azimuthal_angle

```

Azimuthal angle in degrees

```

<Lorentz: public functions>+≡
  public :: azimuthal_angle_deg

<Lorentz: interfaces>+≡
  interface azimuthal_angle_deg
    module procedure vector3_azimuthal_angle_deg
    module procedure vector4_azimuthal_angle_deg
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_azimuthal_angle_deg (p) result (phi)
    real(default) :: phi
    type(vector3_t), intent(in) :: p
    phi = vector3_azimuthal_angle (p) / degree
  end function vector3_azimuthal_angle_deg
  elemental function vector4_azimuthal_angle_deg (p) result (phi)
    real(default) :: phi
    type(vector4_t), intent(in) :: p
    phi = vector4_azimuthal_angle (p) / degree
  end function vector4_azimuthal_angle_deg

```

The azimuthal distance of two vectors. This is the difference of the azimuthal angles, but cannot be larger than π : The result is between $-\pi < \Delta\phi \leq \pi$.

```

<Lorentz: public functions>+≡
  public :: azimuthal_distance

<Lorentz: interfaces>+≡
  interface azimuthal_distance
    module procedure vector3_azimuthal_distance
    module procedure vector4_azimuthal_distance
  end interface

```

```

<Lorentz: procedures>+≡
  elemental function vector3_azimuthal_distance (p, q) result (dphi)
    real(default) :: dphi
    type(vector3_t), intent(in) :: p,q
    dphi = vector3_azimuthal_angle (q) - vector3_azimuthal_angle (p)
    if (dphi <= -pi) then
      dphi = dphi + twopi
    else if (dphi > pi) then
      dphi = dphi - twopi
    end if
  end function vector3_azimuthal_distance
  elemental function vector4_azimuthal_distance (p, q) result (dphi)
    real(default) :: dphi
    type(vector4_t), intent(in) :: p,q
    dphi = vector3_azimuthal_distance &
      (space_part (p), space_part (q))
  end function vector4_azimuthal_distance

```

The same in degrees:

```

<Lorentz: public functions>+≡
  public :: azimuthal_distance_deg

<Lorentz: interfaces>+≡
  interface azimuthal_distance_deg
    module procedure vector3_azimuthal_distance_deg
    module procedure vector4_azimuthal_distance_deg
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_azimuthal_distance_deg (p, q) result (dphi)
    real(default) :: dphi
    type(vector3_t), intent(in) :: p,q
    dphi = vector3_azimuthal_distance (p, q) / degree
  end function vector3_azimuthal_distance_deg
  elemental function vector4_azimuthal_distance_deg (p, q) result (dphi)
    real(default) :: dphi
    type(vector4_t), intent(in) :: p,q
    dphi = vector4_azimuthal_distance (p, q) / degree
  end function vector4_azimuthal_distance_deg

```

The polar angle is defined $0 \leq \theta \leq \pi$. Note that ATAN2 has the reversed order of arguments: ATAN2(Y,X). Here, x is the 3-component while y is the transverse momentum which is always nonnegative. Therefore, the result is nonnegative as well.

```

<Lorentz: public functions>+≡
  public :: polar_angle

<Lorentz: interfaces>+≡
  interface polar_angle
    module procedure polar_angle_vector3
    module procedure polar_angle_vector4
  end interface

```

```

<Lorentz: procedures>+≡
  elemental function polar_angle_vector3 (p) result (theta)
    real(default) :: theta
    type(vector3_t), intent(in) :: p
    if (any (abs (p%p) > 0)) then
      theta = atan2 (sqrt(p%p(1)**2 + p%p(2)**2), p%p(3))
    else
      theta = 0
    end if
  end function polar_angle_vector3
  elemental function polar_angle_vector4 (p) result (theta)
    real(default) :: theta
    type(vector4_t), intent(in) :: p
    theta = polar_angle (space_part (p))
  end function polar_angle_vector4

```

This is the cosine of the polar angle: $-1 \leq \cos \theta \leq 1$.

```

<Lorentz: public functions>+≡
  public :: polar_angle_ct

<Lorentz: interfaces>+≡
  interface polar_angle_ct
    module procedure polar_angle_ct_vector3
    module procedure polar_angle_ct_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function polar_angle_ct_vector3 (p) result (ct)
    real(default) :: ct
    type(vector3_t), intent(in) :: p
    if (any (abs (p%p) > 0)) then
      ct = p%p(3) / p**1
    else
      ct = 1
    end if
  end function polar_angle_ct_vector3
  elemental function polar_angle_ct_vector4 (p) result (ct)
    real(default) :: ct
    type(vector4_t), intent(in) :: p
    ct = polar_angle_ct (space_part (p))
  end function polar_angle_ct_vector4

```

The polar angle in degrees.

```

<Lorentz: public functions>+≡
  public :: polar_angle_deg

<Lorentz: interfaces>+≡
  interface polar_angle_deg
    module procedure polar_angle_deg_vector3
    module procedure polar_angle_deg_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function polar_angle_deg_vector3 (p) result (theta)
    real(default) :: theta

```

```

        type(vector3_t), intent(in) :: p
        theta = polar_angle (p) / degree
    end function polar_angle_deg_vector3
    elemental function polar_angle_deg_vector4 (p) result (theta)
        real(default) :: theta
        type(vector4_t), intent(in) :: p
        theta = polar_angle (p) / degree
    end function polar_angle_deg_vector4

```

This is the angle enclosed between two three-momenta. If one of the momenta is zero, we return an angle of zero. The range of the result is $0 \leq \theta \leq \pi$. If there is only one argument, take the positive z axis as reference.

```

<Lorentz: public functions>+≡
    public :: enclosed_angle

<Lorentz: interfaces>+≡
    interface enclosed_angle
        module procedure enclosed_angle_vector3
        module procedure enclosed_angle_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function enclosed_angle_vector3 (p, q) result (theta)
        real(default) :: theta
        type(vector3_t), intent(in) :: p, q
        theta = acos (enclosed_angle_ct (p, q))
    end function enclosed_angle_vector3
    elemental function enclosed_angle_vector4 (p, q) result (theta)
        real(default) :: theta
        type(vector4_t), intent(in) :: p, q
        theta = enclosed_angle (space_part (p), space_part (q))
    end function enclosed_angle_vector4

```

The cosine of the enclosed angle.

```

<Lorentz: public functions>+≡
    public :: enclosed_angle_ct

<Lorentz: interfaces>+≡
    interface enclosed_angle_ct
        module procedure enclosed_angle_ct_vector3
        module procedure enclosed_angle_ct_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function enclosed_angle_ct_vector3 (p, q) result (ct)
        real(default) :: ct
        type(vector3_t), intent(in) :: p, q
        if (any (abs (p%p) > 0) .and. any (abs (q%p) > 0)) then
            ct = p*q / (p**1 * q**1)
            if (ct>1) then
                ct = 1
            else if (ct<-1) then
                ct = -1
            end if
        else

```

```

        ct = 1
    end if
end function enclosed_angle_ct_vector3
elemental function enclosed_angle_ct_vector4 (p, q) result (ct)
    real(default) :: ct
    type(vector4_t), intent(in) :: p, q
    ct = enclosed_angle_ct (space_part (p), space_part (q))
end function enclosed_angle_ct_vector4

```

The enclosed angle in degrees.

```

<Lorentz: public functions>+≡
    public :: enclosed_angle_deg

<Lorentz: interfaces>+≡
    interface enclosed_angle_deg
        module procedure enclosed_angle_deg_vector3
        module procedure enclosed_angle_deg_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function enclosed_angle_deg_vector3 (p, q) result (theta)
        real(default) :: theta
        type(vector3_t), intent(in) :: p, q
        theta = enclosed_angle (p, q) / degree
    end function enclosed_angle_deg_vector3
    elemental function enclosed_angle_deg_vector4 (p, q) result (theta)
        real(default) :: theta
        type(vector4_t), intent(in) :: p, q
        theta = enclosed_angle (p, q) / degree
    end function enclosed_angle_deg_vector4

```

The polar angle of the first momentum w.r.t. the second momentum, evaluated in the rest frame of the second momentum. If the second four-momentum is not timelike, return zero.

```

<Lorentz: public functions>+≡
    public :: enclosed_angle_rest_frame
    public :: enclosed_angle_ct_rest_frame
    public :: enclosed_angle_deg_rest_frame

<Lorentz: interfaces>+≡
    interface enclosed_angle_rest_frame
        module procedure enclosed_angle_rest_frame_vector4
    end interface
    interface enclosed_angle_ct_rest_frame
        module procedure enclosed_angle_ct_rest_frame_vector4
    end interface
    interface enclosed_angle_deg_rest_frame
        module procedure enclosed_angle_deg_rest_frame_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function enclosed_angle_rest_frame_vector4 (p, q) result (theta)
        type(vector4_t), intent(in) :: p, q
        real(default) :: theta
        theta = acos (enclosed_angle_ct_rest_frame (p, q))

```

```

end function enclosed_angle_rest_frame_vector4
elemental function enclosed_angle_ct_rest_frame_vector4 (p, q) result (ct)
  type(vector4_t), intent(in) :: p, q
  real(default) :: ct
  if (invariant_mass(q) > 0) then
    ct = enclosed_angle_ct ( &
      space_part (boost(-q, invariant_mass (q)) * p), &
      space_part (q))
  else
    ct = 1
  end if
end function enclosed_angle_ct_rest_frame_vector4
elemental function enclosed_angle_deg_rest_frame_vector4 (p, q) &
  result (theta)
  type(vector4_t), intent(in) :: p, q
  real(default) :: theta
  theta = enclosed_angle_rest_frame (p, q) / degree
end function enclosed_angle_deg_rest_frame_vector4

```

9.3.5 More kinematical functions (some redundant)

The scalar transverse momentum (assuming the z axis is longitudinal)

```

<Lorentz: public functions>+≡
  public :: transverse_part

<Lorentz: interfaces>+≡
  interface transverse_part
    module procedure transverse_part_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function transverse_part_vector4 (p) result (pT)
    real(default) :: pT
    type(vector4_t), intent(in) :: p
    pT = sqrt(p%p(1)**2 + p%p(2)**2)
  end function transverse_part_vector4

```

The scalar longitudinal momentum (assuming the z axis is longitudinal). Identical to `momentum_z_component`.

```

<Lorentz: public functions>+≡
  public :: longitudinal_part

<Lorentz: interfaces>+≡
  interface longitudinal_part
    module procedure longitudinal_part_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function longitudinal_part_vector4 (p) result (pL)
    real(default) :: pL
    type(vector4_t), intent(in) :: p
    pL = p%p(3)
  end function longitudinal_part_vector4

```

Absolute value of three-momentum

```

<Lorentz: public functions>+≡
    public :: space_part_norm

<Lorentz: interfaces>+≡
    interface space_part_norm
        module procedure space_part_norm_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function space_part_norm_vector4 (p) result (p3)
        real(default) :: p3
        type(vector4_t), intent(in) :: p
        p3 = sqrt (p%p(1)**2 + p%p(2)**2 + p%p(3)**2)
    end function space_part_norm_vector4

```

The energy (the zeroth component)

```

<Lorentz: public functions>+≡
    public :: energy

<Lorentz: interfaces>+≡
    interface energy
        module procedure energy_vector4
        module procedure energy_vector3
        module procedure energy_real
    end interface

<Lorentz: procedures>+≡
    elemental function energy_vector4 (p) result (E)
        real(default) :: E
        type(vector4_t), intent(in) :: p
        E = p%p(0)
    end function energy_vector4

```

Alternative: The energy corresponding to a given momentum and mass. If the mass is omitted, it is zero

```

<Lorentz: procedures>+≡
    elemental function energy_vector3 (p, mass) result (E)
        real(default) :: E
        type(vector3_t), intent(in) :: p
        real(default), intent(in), optional :: mass
        if (present (mass)) then
            E = sqrt (p**2 + mass**2)
        else
            E = p**1
        end if
    end function energy_vector3

    elemental function energy_real (p, mass) result (E)
        real(default) :: E
        real(default), intent(in) :: p
        real(default), intent(in), optional :: mass
        if (present (mass)) then
            E = sqrt (p**2 + mass**2)
        else

```



```

        E = abs (p)
    end if
end function energy_real

```

The invariant mass of four-momenta. Zero for lightlike, negative for spacelike momenta.

```

<Lorentz: public functions>+≡
    public :: invariant_mass

<Lorentz: interfaces>+≡
    interface invariant_mass
        module procedure invariant_mass_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function invariant_mass_vector4 (p) result (m)
        real(default) :: m
        type(vector4_t), intent(in) :: p
        real(default) :: msq
        msq = p*p
        if (msq >= 0) then
            m = sqrt (msq)
        else
            m = - sqrt (abs (msq))
        end if
    end function invariant_mass_vector4

```

The invariant mass squared. Zero for lightlike, negative for spacelike momenta.

```

<Lorentz: public functions>+≡
    public :: invariant_mass_squared

<Lorentz: interfaces>+≡
    interface invariant_mass_squared
        module procedure invariant_mass_squared_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function invariant_mass_squared_vector4 (p) result (msq)
        real(default) :: msq
        type(vector4_t), intent(in) :: p
        msq = p*p
    end function invariant_mass_squared_vector4

```

The transverse mass. If the mass squared is negative, this value also is negative.

```

<Lorentz: public functions>+≡
    public :: transverse_mass

<Lorentz: interfaces>+≡
    interface transverse_mass
        module procedure transverse_mass_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function transverse_mass_vector4 (p) result (m)
        real(default) :: m
        type(vector4_t), intent(in) :: p

```

```

real(default) :: msq
msq = p%p(0)**2 - p%p(1)**2 - p%p(2)**2
if (msq >= 0) then
  m = sqrt (msq)
else
  m = - sqrt (abs (msq))
end if
end function transverse_mass_vector4

```

The rapidity (defined if particle is massive or $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
  public :: rapidity

<Lorentz: interfaces>+≡
  interface rapidity
    module procedure rapidity_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function rapidity_vector4 (p) result (y)
    real(default) :: y
    type(vector4_t), intent(in) :: p
    y = .5 * log( (energy (p) + longitudinal_part (p)) &
      &          /(energy (p) - longitudinal_part (p)))
  end function rapidity_vector4

```

The pseudorapidity (defined if $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
  public :: pseudorapidity

<Lorentz: interfaces>+≡
  interface pseudorapidity
    module procedure pseudorapidity_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function pseudorapidity_vector4 (p) result (eta)
    real(default) :: eta
    type(vector4_t), intent(in) :: p
    eta = -log( tan (.5 * polar_angle (p)))
  end function pseudorapidity_vector4

```

The rapidity distance (defined if both $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
  public :: rapidity_distance

<Lorentz: interfaces>+≡
  interface rapidity_distance
    module procedure rapidity_distance_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function rapidity_distance_vector4 (p, q) result (dy)
    type(vector4_t), intent(in) :: p, q
    real(default) :: dy

```

```

dy = rapidity (q) - rapidity (p)
end function rapidity_distance_vector4

```

The pseudorapidity distance (defined if both $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
public :: pseudorapidity_distance

<Lorentz: interfaces>+≡
interface pseudorapidity_distance
  module procedure pseudorapidity_distance_vector4
end interface

<Lorentz: procedures>+≡
elemental function pseudorapidity_distance_vector4 (p, q) result (deta)
  real(default) :: deta
  type(vector4_t), intent(in) :: p, q
  deta = pseudorapidity (q) - pseudorapidity (p)
end function pseudorapidity_distance_vector4

```

The distance on the $\eta - \phi$ cylinder:

```

<Lorentz: public functions>+≡
public :: eta_phi_distance

<Lorentz: interfaces>+≡
interface eta_phi_distance
  module procedure eta_phi_distance_vector4
end interface

<Lorentz: procedures>+≡
elemental function eta_phi_distance_vector4 (p, q) result (dr)
  type(vector4_t), intent(in) :: p, q
  real(default) :: dr
  dr = sqrt ( &
    pseudorapidity_distance (p, q)**2 &
    + azimuthal_distance (p, q)**2)
end function eta_phi_distance_vector4

```

9.3.6 Lorentz transformations

```

<Lorentz: public>+≡
public :: lorentz_transformation_t

<Lorentz: types>+≡
type :: lorentz_transformation_t
  private
  real(default), dimension(0:3, 0:3) :: L
  contains
  <Lorentz: lorentz_transformation: TBP>
end type lorentz_transformation_t

```

Output:

```

<Lorentz: public>+≡
public :: lorentz_transformation_write

```

```

<Lorentz: lorentz transformation: TBP>≡
  procedure :: write => lorentz_transformation_write

<Lorentz: procedures>+≡
  subroutine lorentz_transformation_write (L, unit)
    class(lorentz_transformation_t), intent(in) :: L
    integer, intent(in), optional :: unit
    integer :: u
    integer :: i
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1x,A,3(1x," // FMT_19 // "))" ) "L00 = ", L%L(0,0)
    write (u, "(1x,A,3(1x," // FMT_19 // "))" ) "L0j = ", L%L(0,1:3)
    do i = 1, 3
      write (u, "(1x,A,I0,A,3(1x," // FMT_19 // "))" ) &
        "L", i, "0 = ", L%L(i,0)
      write (u, "(1x,A,I0,A,3(1x," // FMT_19 // "))" ) &
        "L", i, "j = ", L%L(i,1:3)
    end do
  end subroutine lorentz_transformation_write

```

Extract all components:

```

<Lorentz: public>+≡
  public :: lorentz_transformation_get_components

<Lorentz: procedures>+≡
  pure function lorentz_transformation_get_components (L) result (a)
    type(lorentz_transformation_t), intent(in) :: L
    real(default), dimension(0:3,0:3) :: a
    a = L%L
  end function lorentz_transformation_get_components

```

9.3.7 Functions of Lorentz transformations

For the inverse, we make use of the fact that $\Lambda^{\mu\nu}\Lambda_{\mu\rho} = \delta_{\rho}^{\nu}$. So, lowering the indices and transposing is sufficient.

```

<Lorentz: public functions>+≡
  public :: inverse

<Lorentz: interfaces>+≡
  interface inverse
    module procedure lorentz_transformation_inverse
  end interface

<Lorentz: procedures>+≡
  elemental function lorentz_transformation_inverse (L) result (IL)
    type(lorentz_transformation_t) :: L
    type(lorentz_transformation_t), intent(in) :: L
    IL%L(0,0) = L%L(0,0)
    IL%L(0,1:) = -L%L(1:,0)
    IL%L(1:,0) = -L%L(0,1:)
    IL%L(1:,1:) = transpose(L%L(1:,1:))
  end function lorentz_transformation_inverse

```

9.3.8 Invariants

These are used below. The first array index is varying fastest in FORTRAN; therefore the extra minus in the odd-rank tensor epsilon.

```

(Lorentz: parameters)+≡
    integer, dimension(3,3), parameter :: delta_three = &
        & reshape( source = [ 1,0,0, 0,1,0, 0,0,1 ], &
            & shape = [3,3] )
    integer, dimension(3,3,3), parameter :: epsilon_three = &
        & reshape( source = [ 0, 0,0, 0,0,-1, 0,1,0, &
            & 0, 0,1, 0,0, 0, -1,0,0, &
            & 0,-1,0, 1,0, 0, 0,0,0 ],&
            & shape = [3,3,3] )

```

This could be of some use:

```

(Lorentz: public)+≡
    public :: identity

(Lorentz: parameters)+≡
    type(lorentz_transformation_t), parameter :: &
        & identity = &
        & lorentz_transformation_t ( &
            & reshape( source = [ one, zero, zero, zero, &
            & zero, one, zero, zero, &
            & zero, zero, one, zero, &
            & zero, zero, zero, one ],&
            & shape = [4,4] ) )

(Lorentz: public)+≡
    public :: space_reflection

(Lorentz: parameters)+≡
    type(lorentz_transformation_t), parameter :: &
        & space_reflection = &
        & lorentz_transformation_t ( &
            & reshape( source = [ one, zero, zero, zero, &
            & zero,-one, zero, zero, &
            & zero, zero,-one, zero, &
            & zero, zero, zero,-one ],&
            & shape = [4,4] ) )

```

Builds a unit vector orthogonal to the input vector in the xy-plane.

```

(Lorentz: public functions)+≡
    public :: create_orthogonal

(Lorentz: procedures)+≡
    function create_orthogonal (p_in) result (p_out)
        type(vector3_t), intent(in) :: p_in
        type(vector3_t) :: p_out
        real(default) :: ab
        ab = sqrt (p_in%p(1)**2 + p_in%p(2)**2)
        if (abs (ab) < eps0) then
            p_out%p(1) = 1
            p_out%p(2) = 0
            p_out%p(3) = 0
        else
            p_out%p(1) = p_in%p(2)

```

```

        p_out%p(2) = -p_in%p(1)
        p_out%p(3) = 0
        p_out = p_out / ab
    end if
end function create_orthogonal

<Lorentz: public functions>+≡
public :: create_unit_vector

<Lorentz: procedures>+≡
function create_unit_vector (p_in) result (p_out)
    type(vector4_t), intent(in) :: p_in
    type(vector3_t) :: p_out
    real(default) :: abs
    abs = space_part_norm (p_in)
    p_out%p(1) = p_in%p(1)/abs
    p_out%p(2) = p_in%p(2)/abs
    p_out%p(3) = p_in%p(3)/abs
end function create_unit_vector

<Lorentz: public functions>+≡
public :: normalize

<Lorentz: procedures>+≡
subroutine normalize(p)
    type(vector3_t), intent(inout) :: p
    real(default) :: abs
    abs = sqrt (p%p(1)**2 + p%p(2)**2 + p%p(3)**2)
    p = p/abs
end subroutine normalize

```

9.3.9 Boosts

We build Lorentz transformations from boosts and rotations. In both cases we can supply a three-vector which defines the axis and (hyperbolic) angle. For a boost, this is the vector $\vec{\beta} = \vec{p}/E$, such that a particle at rest with mass m is boosted to a particle with three-vector \vec{p} . Here, we have

$$\beta = \tanh \chi = p/E, \quad \gamma = \cosh \chi = E/m, \quad \beta\gamma = \sinh \chi = p/m \quad (9.1)$$

```

<Lorentz: public functions>+≡
public :: boost

<Lorentz: interfaces>+≡
interface boost
    module procedure boost_from_rest_frame
    module procedure boost_from_rest_frame_vector3
    module procedure boost_generic
    module procedure boost_canonical
end interface

```

In the first form, the argument is some four-momentum, the space part of which determines a direction, and the associated mass (which is not checked against the four-momentum). The boost vector $\gamma\vec{\beta}$ is then given by \vec{p}/m . This boosts from the rest frame of a particle to the current frame. To be explicit, if \vec{p} is the momentum of a particle and m its mass, $L(\vec{p}/m)$ is the transformation that turns $(m; \vec{0})$ into $(E; \vec{p})$. Conversely, the inverse transformation boosts a vector *into* the rest frame of a particle, in particular $(E; \vec{p})$ into $(m; \vec{0})$.

(Lorentz: procedures)+≡

```

elemental function boost_from_rest_frame (p, m) result (L)
  type(lorentz_transformation_t) :: L
  type(vector4_t), intent(in) :: p
  real(default), intent(in) :: m
  L = boost_from_rest_frame_vector3 (space_part (p), m)
end function boost_from_rest_frame
elemental function boost_from_rest_frame_vector3 (p, m) result (L)
  type(lorentz_transformation_t) :: L
  type(vector3_t), intent(in) :: p
  real(default), intent(in) :: m
  type(vector3_t) :: beta_gamma
  real(default) :: bg2, g, c
  integer :: i,j
  if (m > eps0) then
    beta_gamma = p / m
    bg2 = beta_gamma**2
  else
    bg2 = 0
  end if
  if (bg2 > eps0) then
    g = sqrt(1 + bg2); c = (g-1)/bg2
    L%L(0,0) = g
    L%L(0,1:) = beta_gamma%p
    L%L(1:,0) = L%L(0,1:)
    do i=1,3
      do j=1,3
        L%L(i,j) = delta_three(i,j) + c*beta_gamma%p(i)*beta_gamma%p(j)
      end do
    end do
  else
    L = identity
  end if
end function boost_from_rest_frame_vector3

```

A canonical boost is a boost along one of the coordinate axes, which we may supply as an integer argument. Here, $\gamma\beta$ is scalar.

(Lorentz: procedures)+≡

```

elemental function boost_canonical (beta_gamma, k) result (L)
  type(lorentz_transformation_t) :: L
  real(default), intent(in) :: beta_gamma
  integer, intent(in) :: k
  real(default) :: g
  g = sqrt(1 + beta_gamma**2)
  L = identity
  L%L(0,0) = g
  L%L(0,k) = beta_gamma

```

```

L%L(k,0) = L%L(0,k)
L%L(k,k) = L%L(0,0)
end function boost_canonical

```

Instead of a canonical axis, we can supply an arbitrary axis which need not be normalized. If it is zero, return the unit matrix.

```

(Lorentz: procedures)+≡
elemental function boost_generic (beta_gamma, axis) result (L)
  type(lorentz_transformation_t) :: L
  real(default), intent(in) :: beta_gamma
  type(vector3_t), intent(in) :: axis
  if (any (axis%p) > 0) then
    L = boost_from_rest_frame_vector3 (beta_gamma * axis, axis**1)
  else
    L = identity
  end if
end function boost_generic

```

9.3.10 Rotations

For a rotation, the vector defines the rotation axis, and its length the rotation angle.

```

(Lorentz: public functions)+≡
  public :: rotation

(Lorentz: interfaces)+≡
  interface rotation
    module procedure rotation_generic
    module procedure rotation_canonical
    module procedure rotation_generic_cs
    module procedure rotation_canonical_cs
  end interface

```

If $\cos \phi$ and $\sin \phi$ is already known, we do not have to calculate them. Of course, the user has to ensure that $\cos^2 \phi + \sin^2 \phi = 1$, and that the given axis **n** is normalized to one. In the second form, the length of **axis** is the rotation angle.

```

(Lorentz: procedures)+≡
elemental function rotation_generic_cs (cp, sp, axis) result (R)
  type(lorentz_transformation_t) :: R
  real(default), intent(in) :: cp, sp
  type(vector3_t), intent(in) :: axis
  integer :: i,j
  R = identity
  do i=1,3
    do j=1,3
      R%L(i,j) = cp*delta_three(i,j) + (1-cp)*axis%p(i)*axis%p(j) &
        & - sp*dot_product(epsilon_three(i,j,:), axis%p)
    end do
  end do
end function rotation_generic_cs
elemental function rotation_generic (axis) result (R)
  type(lorentz_transformation_t) :: R

```



```

type(vector3_t), intent(in) :: axis
real(default) :: phi
if (any (abs(axis%p) > 0)) then
    phi = abs(axis**1)
    R = rotation_generic_cs (cos(phi), sin(phi), axis/phi)
else
    R = identity
end if
end function rotation_generic

```

Alternatively, give just the angle and label the coordinate axis by an integer.

```

(Lorentz: procedures)+≡
elemental function rotation_canonical_cs (cp, sp, k) result (R)
    type(lorentz_transformation_t) :: R
    real(default), intent(in) :: cp, sp
    integer, intent(in) :: k
    integer :: i,j
    R = identity
    do i=1,3
        do j=1,3
            R%L(i,j) = -sp*epsilon_three(i,j,k)
        end do
        R%L(i,i) = cp
    end do
    R%L(k,k) = 1
end function rotation_canonical_cs
elemental function rotation_canonical (phi, k) result (R)
    type(lorentz_transformation_t) :: R
    real(default), intent(in) :: phi
    integer, intent(in) :: k
    R = rotation_canonical_cs(cos(phi), sin(phi), k)
end function rotation_canonical

```

This is viewed as a method for the first argument (three-vector): Reconstruct the rotation that rotates it into the second three-vector.

```

(Lorentz: public functions)+≡
public :: rotation_to_2nd

(Lorentz: interfaces)+≡
interface rotation_to_2nd
    module procedure rotation_to_2nd_generic
    module procedure rotation_to_2nd_canonical
end interface

(Lorentz: procedures)+≡
elemental function rotation_to_2nd_generic (p, q) result (R)
    type(lorentz_transformation_t) :: R
    type(vector3_t), intent(in) :: p, q
    type(vector3_t) :: a, b, ab
    real(default) :: ct, st
    if (any (abs (p%p) > 0) .and. any (abs (q%p) > 0)) then
        a = direction (p)
        b = direction (q)
        ab = cross_product(a,b)
        ct = a*b; st = ab**1
        if (abs(st) > eps0) then

```

```

        R = rotation_generic_cs (ct, st, ab/st)
    else if (ct < 0) then
        R = space_reflection
    else
        R = identity
    end if
else
    R = identity
end if
end function rotation_to_2nd_generic

```

The same for a canonical axis: The function returns the transformation that rotates the k -axis into the direction of p .

```

(Lorentz: procedures)+≡
elemental function rotation_to_2nd_canonical (k, p) result (R)
    type(lorentz_transformation_t) :: R
    integer, intent(in) :: k
    type(vector3_t), intent(in) :: p
    type(vector3_t) :: b, ab
    real(default) :: ct, st
    integer :: i, j
    if (any (abs (p%p) > 0)) then
        b = direction (p)
        ab%p = 0
        do i = 1, 3
            do j = 1, 3
                ab%p(j) = ab%p(j) + b%p(i) * epsilon_three(i,j,k)
            end do
        end do
        ct = b%p(k); st = ab**1
        if (abs(st) > eps0) then
            R = rotation_generic_cs (ct, st, ab/st)
        else if (ct < 0) then
            R = space_reflection
        else
            R = identity
        end if
    else
        R = identity
    end if
end function rotation_to_2nd_canonical

```

9.3.11 Composite Lorentz transformations

This function returns the transformation that, given a pair of vectors $p_{1,2}$, (a) boosts from the rest frame of the c.m. system (with invariant mass m) into the lab frame where p_i are defined, and (b) turns the given axis (or the canonical vectors $\pm e_k$) in the rest frame into the directions of $p_{1,2}$ in the lab frame. Note that the energy components are not used; for a consistent result one should have $(p_1 + p_2)^2 = m^2$.

```

(Lorentz: public functions)+≡
public :: transformation

```

```

<Lorentz: interfaces>+≡
interface transformation
  module procedure transformation_rec_generic
  module procedure transformation_rec_canonical
end interface

<Lorentz: procedures>+≡
elemental function transformation_rec_generic (axis, p1, p2, m) result (L)
  type(vector3_t), intent(in) :: axis
  type(vector4_t), intent(in) :: p1, p2
  real(default), intent(in) :: m
  type(lorentz_transformation_t) :: L
  L = boost (p1 + p2, m)
  L = L * rotation_to_2nd (axis, space_part (inverse (L) * p1))
end function transformation_rec_generic
elemental function transformation_rec_canonical (k, p1, p2, m) result (L)
  integer, intent(in) :: k
  type(vector4_t), intent(in) :: p1, p2
  real(default), intent(in) :: m
  type(lorentz_transformation_t) :: L
  L = boost (p1 + p2, m)
  L = L * rotation_to_2nd (k, space_part (inverse (L) * p1))
end function transformation_rec_canonical

```

9.3.12 Applying Lorentz transformations

Multiplying vectors and Lorentz transformations is straightforward.

```

<Lorentz: interfaces>+≡
interface operator(*)
  module procedure prod_LT_vector4
  module procedure prod_LT_LT
  module procedure prod_vector4_LT
end interface

<Lorentz: procedures>+≡
elemental function prod_LT_vector4 (L, p) result (np)
  type(vector4_t) :: np
  type(lorentz_transformation_t), intent(in) :: L
  type(vector4_t), intent(in) :: p
  np%p = matmul (L%L, p%p)
end function prod_LT_vector4
elemental function prod_LT_LT (L1, L2) result (NL)
  type(lorentz_transformation_t) :: NL
  type(lorentz_transformation_t), intent(in) :: L1, L2
  NL%L = matmul (L1%L, L2%L)
end function prod_LT_LT
elemental function prod_vector4_LT (p, L) result (np)
  type(vector4_t) :: np
  type(vector4_t), intent(in) :: p
  type(lorentz_transformation_t), intent(in) :: L
  np%p = matmul (p%p, L%L)
end function prod_vector4_LT

```

9.3.13 Special Lorentz transformations

These routines have their application in the generation and extraction of angles in the phase-space sampling routine. Since this part of the program is time-critical, we calculate the composition of transformations directly instead of multiplying rotations and boosts.

This Lorentz transformation is the composition of a rotation by ϕ around the 3 axis, a rotation by θ around the 2 axis, and a boost along the 3 axis:

$$L = B_3(\beta\gamma) R_2(\theta) R_3(\phi) \quad (9.2)$$

Instead of the angles we provide sine and cosine.

```

(Lorentz: public functions)+≡
  public :: LT_compose_r3_r2_b3

(Lorentz: procedures)+≡
  elemental function LT_compose_r3_r2_b3 &
    (cp, sp, ct, st, beta_gamma) result (L)
  type(lorentz_transformation_t) :: L
  real(default), intent(in) :: cp, sp, ct, st, beta_gamma
  real(default) :: gamma
  if (abs(beta_gamma) < eps0) then
    L%L(0,0) = 1
    L%L(1:,0) = 0
    L%L(0,1:) = 0
    L%L(1,1:) = [ ct*cp, -ct*sp, st ]
    L%L(2,1:) = [      sp,      cp, zero ]
    L%L(3,1:) = [ -st*cp, st*sp, ct ]
  else
    gamma = sqrt(1 + beta_gamma**2)
    L%L(0,0) = gamma
    L%L(1,0) = 0
    L%L(2,0) = 0
    L%L(3,0) = beta_gamma
    L%L(0,1:) = beta_gamma * [ -st*cp, st*sp, ct ]
    L%L(1,1:) = [ ct*cp, -ct*sp, st ]
    L%L(2,1:) = [      sp,      cp, zero ]
    L%L(3,1:) = gamma * [ -st*cp, st*sp, ct ]
  end if
end function LT_compose_r3_r2_b3

```

Different ordering:

$$L = B_3(\beta\gamma) R_3(\phi) R_2(\theta) \quad (9.3)$$

```

(Lorentz: public functions)+≡
  public :: LT_compose_r2_r3_b3

(Lorentz: procedures)+≡
  elemental function LT_compose_r2_r3_b3 &
    (ct, st, cp, sp, beta_gamma) result (L)
  type(lorentz_transformation_t) :: L
  real(default), intent(in) :: ct, st, cp, sp, beta_gamma
  real(default) :: gamma
  if (abs(beta_gamma) < eps0) then
    L%L(0,0) = 1

```

```

L%L(1:,0) = 0
L%L(0,1:) = 0
L%L(1,1:) = [ ct*cp,    -sp,    st*cp ]
L%L(2,1:) = [ ct*sp,    cp,    st*sp ]
L%L(3,1:) = [ -st,     zero,   ct ]
else
  gamma = sqrt(1 + beta_gamma**2)
  L%L(0,0) = gamma
  L%L(1,0) = 0
  L%L(2,0) = 0
  L%L(3,0) = beta_gamma
  L%L(0,1:) = beta_gamma * [ -st,     zero,   ct ]
  L%L(1,1:) = [ ct*cp,    -sp,    st*cp ]
  L%L(2,1:) = [ ct*sp,    cp,    st*sp ]
  L%L(3,1:) = gamma * [ -st,     zero,   ct ]
end if
end function LT_compose_r2_r3_b3

```

This function returns the previous Lorentz transformation applied to an arbitrary four-momentum and extracts the space part of the result:

$$\vec{n} = [B_3(\beta\gamma) R_2(\theta) R_3(\phi) p]_{\text{space part}} \quad (9.4)$$

The second variant applies if there is no rotation

(Lorentz: public functions)+≡

```
public :: axis_from_p_r3_r2_b3, axis_from_p_b3
```

(Lorentz: procedures)+≡

```

elemental function axis_from_p_r3_r2_b3 &
  (p, cp, sp, ct, st, beta_gamma) result (n)
  type(vector3_t) :: n
  type(vector4_t), intent(in) :: p
  real(default), intent(in) :: cp, sp, ct, st, beta_gamma
  real(default) :: gamma, px, py
  px = cp * p%p(1) - sp * p%p(2)
  py = sp * p%p(1) + cp * p%p(2)
  n%p(1) = ct * px + st * p%p(3)
  n%p(2) = py
  n%p(3) = -st * px + ct * p%p(3)
  if (abs(beta_gamma) > eps0) then
    gamma = sqrt(1 + beta_gamma**2)
    n%p(3) = n%p(3) * gamma + p%p(0) * beta_gamma
  end if
end function axis_from_p_r3_r2_b3

elemental function axis_from_p_b3 (p, beta_gamma) result (n)
  type(vector3_t) :: n
  type(vector4_t), intent(in) :: p
  real(default), intent(in) :: beta_gamma
  real(default) :: gamma
  n%p = p%p(1:3)
  if (abs(beta_gamma) > eps0) then
    gamma = sqrt(1 + beta_gamma**2)
    n%p(3) = n%p(3) * gamma + p%p(0) * beta_gamma
  end if
end function axis_from_p_b3

```

```

end if
end function axis_from_p_b3

```

9.3.14 Special functions

The standard phase space function:

```

(Lorentz: public functions)+≡
public :: lambda

(Lorentz: procedures)+≡
elemental function lambda (m1sq, m2sq, m3sq)
  real(default) :: lambda
  real(default), intent(in) :: m1sq, m2sq, m3sq
  lambda = (m1sq - m2sq - m3sq)**2 - 4*m2sq*m3sq
end function lambda

```

Return a pair of head-to-head colliding momenta, given the collider energy, particle masses, and optionally the momentum of the c.m. system.

```

(Lorentz: public functions)+≡
public :: colliding_momenta

(Lorentz: procedures)+≡
function colliding_momenta (sqrts, m, p_cm) result (p)
  type(vector4_t), dimension(2) :: p
  real(default), intent(in) :: sqrts
  real(default), dimension(2), intent(in), optional :: m
  real(default), intent(in), optional :: p_cm
  real(default), dimension(2) :: dmsq
  real(default) :: ch, sh
  real(default), dimension(2) :: E0, p0
  integer, dimension(2), parameter :: sgn = [1, -1]
  if (abs(sqrts) < eps0) then
    call msg_fatal (" Colliding beams: sqrts is zero (please set sqrts)")
    p = vector4_null; return
  else if (sqrts <= 0) then
    call msg_fatal (" Colliding beams: sqrts is negative")
    p = vector4_null; return
  end if
  if (present (m)) then
    dmsq = sgn * (m(1)**2-m(2)**2)
    E0 = (sqrts + dmsq/sqrts) / 2
    if (any (E0 < m)) then
      call msg_fatal &
        (" Colliding beams: beam energy is less than particle mass")
      p = vector4_null; return
    end if
    p0 = sgn * sqrt (E0**2 - m**2)
  else
    E0 = sqrts / 2
    p0 = sgn * E0
  end if
  if (present (p_cm)) then
    sh = p_cm / sqrts

```

```

        ch = sqrt (1 + sh**2)
        p = vector4_moving (E0 * ch + p0 * sh, E0 * sh + p0 * ch, 3)
    else
        p = vector4_moving (E0, p0, 3)
    end if
end function colliding_momenta

```

This subroutine is for the purpose of numerical checks and comparisons. The idea is to set a number to zero if it is numerically equivalent with zero. The equivalence is established by comparing with a `tolerance` argument. We implement this for vectors and transformations.

```

<Lorentz: public functions>+≡
    public :: pacify

<Lorentz: interfaces>+≡
    interface pacify
        module procedure pacify_vector3
        module procedure pacify_vector4
        module procedure pacify_LT
    end interface pacify

<Lorentz: procedures>+≡
    elemental subroutine pacify_vector3 (p, tolerance)
        type(vector3_t), intent(inout) :: p
        real(default), intent(in) :: tolerance
        where (abs (p%p) < tolerance)  p%p = zero
    end subroutine pacify_vector3

    elemental subroutine pacify_vector4 (p, tolerance)
        type(vector4_t), intent(inout) :: p
        real(default), intent(in) :: tolerance
        where (abs (p%p) < tolerance)  p%p = zero
    end subroutine pacify_vector4

    elemental subroutine pacify_LT (LT, tolerance)
        type(lorentz_transformation_t), intent(inout) :: LT
        real(default), intent(in) :: tolerance
        where (abs (LT%L) < tolerance)  LT%L = zero
    end subroutine pacify_LT

<Lorentz: public>+≡
    public :: vector_set_resuffle

<Lorentz: procedures>+≡
    subroutine vector_set_resuffle (p1, list, p2)
        type(vector4_t), intent(in), dimension(:), allocatable :: p1
        integer, intent(in), dimension(:), allocatable :: list
        type(vector4_t), intent(out), dimension(:), allocatable :: p2
        integer :: n, n_p
        n_p = size (p1)
        if (size (list) /= n_p) return
        allocate (p2 (n_p))
        do n = 1, n_p

```

```

        p2(n) = p1(list(n))
    end do
end subroutine vector_set_resuffle

```

<Lorentz: public>+≡

```
public :: vector4_write_set
```

<Lorentz: procedures>+≡

```

subroutine vector4_write_set (p, unit, show_mass, testflag)
    type(vector4_t), intent(in), dimension(:) :: p
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_mass
    logical, intent(in), optional :: testflag
    integer :: i, j
    real(default), dimension(4) :: p_tot
    character(len=7) :: fmt
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    p_tot = 0
    do i = 1, size (p)
        forall (j=1:4) p_tot(j) = p_tot(j) + vector4_get_component(p(i),j-1)
        call vector4_write (p(i), u, show_mass, testflag)
    end do
    call pac_fmt (fmt, FMT_19, FMT_15, testflag)
    if (present (testflag)) then
        if (testflag) call pacify (p_tot, 1.E-10_default)
    end if
    write (u, "(A5)") 'Total: '
    write (u, "(1x,A,1x," // fmt // ")") "E = ", p_tot(1)
    write (u, "(1x,A,3(1x," // fmt // ")") "P = ", p_tot(2:)
end subroutine vector4_write_set

```

This computes the quantities

$$\langle ij \rangle = \sqrt{|S_{ij}|} e^{i\phi_{ij}}, [ij] = \sqrt{|S_{ij}|} e^{i\tilde{\phi}_{ij}},$$

with $S_{ij} = (p_i + p_j)^2$. The phase space factor ϕ_{ij} is determined by

$$\cos \phi_{ij} = \frac{p_i^1 p_j^+ - p_j^1 p_i^+}{\sqrt{p_i^+ p_j^+ S_{ij}}}, \sin \phi_{ij} = \frac{p_i^2 p_j^+ - p_j^2 p_i^+}{\sqrt{p_i^+ p_j^+ S_{ij}}}.$$

After $\langle ij \rangle$ has been computed according to these formulae, $[ij]$ can be obtained by using the relation $S_{ij} = \langle ij \rangle [ji]$ and taking into account that $[ij] = -[ji]$. Thus, a minus-sign has to be applied.

<Lorentz: public>+≡

```
public :: spinor_product
```

<Lorentz: procedures>+≡

```

subroutine spinor_product (p1, p2, prod1, prod2)
    type(vector4_t), intent(in) :: p1, p2
    complex(default), intent(out) :: prod1, prod2
    real(default) :: sij

```



```

complex(default) :: phase
real(default) :: pp_1, pp_2
pp_1 = p1%p(0) + p1%p(3)
pp_2 = p2%p(0) + p2%p(3)
sij = (p1+p2)**2
phase = cmplx ((p1%p(1)*pp_2 - p2%p(1)*pp_1)/sqrt (sij*pp_1*pp_2), &
               (p1%p(2)*pp_2 - p2%p(2)*pp_1)/sqrt (sij*pp_1*pp_2), &
               default)

!!! <ij>
prod1 = sqrt (sij) * phase
!!! [ij]
if (abs(prod1) > 0) then
    prod2 = - sij / prod1
else
    prod2 = 0
end if
end subroutine spinor_product

```

9.4 Special Physics functions

Here, we declare functions that are specific for the Standard Model, including QCD: fixed and running α_s , Catani-Seymour dipole terms, loop functions, etc.

To make maximum use of this, all functions, if possible, are declared elemental (or pure, if this is not possible).

```

⟨sm_physics.f90⟩≡
  ⟨File header⟩

  module sm_physics

    ⟨Use kinds⟩
    use io_units
    use constants
    use unit_tests
    use diagnostics
    use physics_defs
    use lorentz

    ⟨Standard module head⟩

    ⟨SM physics: public⟩

    ⟨SM physics: parameters⟩

    contains

    ⟨SM physics: procedures⟩

    ⟨SM physics: tests⟩

  end module sm_physics

```

9.4.1 Running α_s

Then we define the coefficients of the beta function of QCD (as a reference cf. the Particle Data Group), where n_f is the number of active flavors in two different schemes:

$$\beta_0 = 11 - \frac{2}{3}n_f \quad (9.5)$$

$$\beta_1 = 51 - \frac{19}{3}n_f \quad (9.6)$$

$$\beta_2 = 2857 - \frac{5033}{9}n_f + \frac{325}{27}n_f^2 \quad (9.7)$$

$$b_0 = \frac{1}{12\pi} (11C_A - 2n_f) \quad (9.8)$$

$$b_1 = \frac{1}{24\pi^2} (17C_A^2 - 5C_A n_f - 3C_F n_f) \quad (9.9)$$

$$b_2 = \frac{1}{(4\pi)^3} \left(\frac{2857}{54} C_A^3 - \frac{1415}{54} C_A^2 n_f - \frac{205}{18} C_A C_F n_f + C_F^2 n_f + \frac{79}{54} C_A n_f * 2 + \frac{11}{9} C_F n_f * 2 \right) \quad (9.10)$$

```

<SM physics: public>≡
  public :: beta0, beta1, beta2, coeff_b0, coeff_b1, coeff_b2

<SM physics: procedures>≡
  pure function beta0 (nf)
    real(default), intent(in) :: nf
    real(default) :: beta0
    beta0 = 11.0_default - two/three * nf
  end function beta0

  pure function beta1 (nf)
    real(default), intent(in) :: nf
    real(default) :: beta1
    beta1 = 51.0_default - 19.0_default/three * nf
  end function beta1

  pure function beta2 (nf)
    real(default), intent(in) :: nf
    real(default) :: beta2
    beta2 = 2857.0_default - 5033.0_default / 9.0_default * &
      nf + 325.0_default/27.0_default * nf**2
  end function beta2

  pure function coeff_b0 (nf)
    real(default), intent(in) :: nf
    real(default) :: coeff_b0
    coeff_b0 = (11.0_default * CA - two * nf) / (12.0_default * pi)
  end function coeff_b0

  pure function coeff_b1 (nf)
    real(default), intent(in) :: nf
    real(default) :: coeff_b1
    coeff_b1 = (17.0_default * CA**2 - five * CA * nf - three * CF * nf) / &
      (24.0_default * pi**2)
  end function coeff_b1

  pure function coeff_b2 (nf)
    real(default), intent(in) :: nf
    real(default) :: coeff_b2
    coeff_b2 = (2857.0_default/54.0_default * CA**3 - &
      1415.0_default/54.0_default * &
      CA**2 * nf - 205.0_default/18.0_default * CA*CF*nf &
      + 79.0_default/54.0_default * CA*nf**2 + &
      11.0_default/9.0_default * CF * nf**2) / (four*pi)**3
  end function coeff_b2

```

There should be two versions of running α_s , one which takes the scale and Λ_{QCD} as input, and one which takes the scale and e.g. $\alpha_s(m_Z)$ as input. Here, we take the one which takes the QCD scale and scale as inputs from the PDG book.

```

<SM physics: public>+≡
  public :: running_as, running_as_lam

<SM physics: procedures>+≡
  pure function running_as (scale, al_mz, mz, order, nf) result (ascale)

```

```

real(default), intent(in) :: scale
real(default), intent(in), optional :: al_mz, nf, mz
integer, intent(in), optional :: order
integer :: ord
real(default) :: az, m_z, as_log, n_f, b0, b1, b2, ascale
real(default) :: as0, as1
if (present (mz)) then
    m_z = mz
else
    m_z = MZ_REF
end if
if (present (order)) then
    ord = order
else
    ord = 0
end if
if (present (al_mz)) then
    az = al_mz
else
    az = ALPHA_QCD_MZ_REF
end if
if (present (nf)) then
    n_f = nf
else
    n_f = 5
end if
b0 = coeff_b0 (n_f)
b1 = coeff_b1 (n_f)
b2 = coeff_b2 (n_f)
as_log = one + b0 * az * log(scale**2/m_z**2)
as0 = az / as_log
as1 = as0 - as0**2 * b1/b0 * log(as_log)
select case (ord)
case (0)
    ascale = as0
case (1)
    ascale = as1
case (2)
    ascale = as1 + as0**3 * (b1**2/b0**2 * ((log(as_log))**2 - &
        log(as_log) + as_log - one) - b2/b0 * (as_log - one))
case default
    ascale = as0
end select
end function running_as

pure function running_as_lam (nf, scale, lambda, order) result (ascale)
real(default), intent(in) :: nf, scale
real(default), intent(in), optional :: lambda
integer, intent(in), optional :: order
real(default) :: lambda_qcd
real(default) :: as0, as1, logmul, b0, b1, b2, ascale
integer :: ord
if (present (lambda)) then
    lambda_qcd = lambda

```

```

else
  lambda_qcd = LAMBDA_QCD_REF
end if
if (present (order)) then
  ord = order
else
  ord = 0
end if
b0 = beta0(nf)
logmul = log(scale**2/lambda_qcd**2)
as0 = four*pi / b0 / logmul
if (ord > 0) then
  b1 = beta1(nf)
  as1 = as0 * (one - two* b1 / b0**2 * log(logmul) / logmul)
end if
select case (ord)
case (0)
  ascale = as0
case (1)
  ascale = as1
case (2)
  b2 = beta2(nf)
  ascale = as1 + as0 * four * b1**2/b0**4/logmul**2 * &
    ((log(logmul) - 0.5_default)**2 + &
    b2*b0/8.0_default/b1**2 - five/four)
case default
  ascale = as0
end select
end function running_as_lam

```

9.4.2 Catani-Seymour Parameters

These are fundamental constants of the Catani-Seymour dipole formalism. Since the corresponding parameters for the gluon case depend on the number of flavors which is treated as an argument, there we do have functions and not parameters.

$$\gamma_q = \gamma_{\bar{q}} = \frac{3}{2}C_F \quad \gamma_g = \frac{11}{6}C_A - \frac{2}{3}T_R N_f \quad (9.11)$$

$$K_q = K_{\bar{q}} = \left(\frac{7}{2} - \frac{\pi^2}{6}\right) C_F \quad K_g = \left(\frac{67}{18} - \frac{\pi^2}{6}\right) C_A - \frac{10}{9}T_R N_f \quad (9.12)$$

```

⟨SM physics: parameters⟩≡
real(kind=default), parameter, public :: gamma_q = three/two * CF, &
  k_q = (7.0_default/two - pi**2/6.0_default) * CF

```

```

⟨SM physics: public⟩+≡
public :: gamma_g, k_g

```

```

⟨SM physics: procedures⟩+≡
elemental function gamma_g (nf) result (gg)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: gg

```

```

      gg = 11.0_default/6.0_default * CA - two/three * TR * nf
end function gamma_g

elemental function k_g (nf) result (kg)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: kg
  kg = (67.0_default/18.0_default - pi**2/6.0_default) * CA - &
      10.0_default/9.0_default * TR * nf
end function k_g

```

9.4.3 Mathematical Functions

The dilogarithm. This simplified version is bound to double precision, and restricted to argument values less or equal to unity, so we do not need complex algebra. The wrapper converts it to default precision (which is, of course, a no-op if double=default).

The routine calculates the dilogarithm through mapping on the area where there is a quickly convergent series (adapted from an F77 routine by Hans Kuijf, 1988): Map x such that x is not in the neighbourhood of 1. Note that $|z| = -\ln(1-x)$ is always smaller than 1.10, but $\frac{1 \cdot 10^{19}}{19!} \text{Bernoulli}_{19} = 2.7 \times 10^{-15}$.

<SM physics: public>+≡
 public :: Li2

<SM physics: procedures>+≡
 function Li2 (x)
 use kinds, only: double
 real(default), intent(in) :: x
 real(default) :: Li2
 Li2 = real(Li2_double (real(x, kind=double)), kind=default)
end function Li2

<SM physics: procedures>+≡
 function Li2_double (x) result (Li2)
 use kinds, only: double
 real(kind=double), intent(in) :: x
 real(kind=double) :: Li2
 real(kind=double), parameter :: pi2_6 = pi**2/6
 if (abs(1-x) < 1.E-13_double) then
 Li2 = pi2_6
 else if (abs(1-x) < 0.5_double) then
 Li2 = pi2_6 - log(1-x) * log(x) - Li2_restricted (1-x)
 else if (abs(x) > 1.d0) then
 ! Li2 = 0
 ! call msg_bug (" Dilogarithm called outside of defined range.")
 !!! Reactivate Dilogarithm identity
 Li2 = -pi2_6 - 0.5_default * log(-x) * log(-x) - Li2_restricted (1/x)
 else
 Li2 = Li2_restricted (x)
 end if
contains
 function Li2_restricted (x) result (Li2)

```

      real(kind=double), intent(in) :: x
      real(kind=double) :: Li2
      real(kind=double) :: tmp, z, z2
      z = - log (1-x)
      z2 = z**2
! Horner's rule for the powers z^3 through z^19
      tmp = 43867._double/798._double
      tmp = tmp * z2 /342._double - 3617._double/510._double
      tmp = tmp * z2 /272._double + 7._double/6._double
      tmp = tmp * z2 /210._double - 691._double/2730._double
      tmp = tmp * z2 /156._double + 5._double/66._double
      tmp = tmp * z2 /110._double - 1._double/30._double
      tmp = tmp * z2 / 72._double + 1._double/42._double
      tmp = tmp * z2 / 42._double - 1._double/30._double
      tmp = tmp * z2 / 20._double + 1._double/6._double
! The first three terms of the power series
      Li2 = z2 * z * tmp / 6._double - 0.25_double * z2 + z
    end function Li2_restricted
end function Li2_double

```

9.4.4 Loop Integrals

These functions appear in the calculation of the effective one-loop coupling of a (pseudo)scalar to a vector boson pair.

```

<SM physics: public>+≡
  public :: faux

<SM physics: procedures>+≡
  elemental function faux (x) result (y)
    real(default), intent(in) :: x
    complex(default) :: y
    if (1 <= x) then
      y = asin(sqrt(1/x))**2
    else
      y = - 1/4.0_default * (log((1 + sqrt(1 - x))/ &
        (1 - sqrt(1 - x))) - cmplx (0.0_default, pi, kind=default))**2
    end if
  end function faux

<SM physics: public>+≡
  public :: fonehalf

<SM physics: procedures>+≡
  elemental function fonehalf (x) result (y)
    real(default), intent(in) :: x
    complex(default) :: y
    if (abs(x) < eps0) then
      y = 0
    else
      y = - 2.0_default * x * (1 + (1 - x) * faux(x))
    end if
  end function fonehalf

```

```

<SM physics: public>+≡
public :: fonehalf_pseudo

<SM physics: procedures>+≡
function fonehalf_pseudo (x) result (y)
  real(default), intent(in) :: x
  complex(default) :: y
  if (abs(x) < eps0) then
    y = 0
  else
    y = - 2.0_default * x * faux(x)
  end if
end function fonehalf_pseudo

<SM physics: public>+≡
public :: fone

<SM physics: procedures>+≡
elemental function fone (x) result (y)
  real(default), intent(in) :: x
  complex(default) :: y
  if (abs(x) < eps0) then
    y = 2.0_default
  else
    y = 2.0_default + 3.0_default * x + &
      3.0_default * x * (2.0_default - x) * &
      faux(x)
  end if
end function fone

<SM physics: public>+≡
public :: gaux

<SM physics: procedures>+≡
elemental function gaux (x) result (y)
  real(default), intent(in) :: x
  complex(default) :: y
  if (1 <= x) then
    y = sqrt(x - 1) * asin(sqrt(1/x))
  else
    y = sqrt(1 - x) * (log((1 + sqrt(1 - x)) / &
      (1 - sqrt(1 - x)))) - &
      cmplx (0.0_default, pi, kind=default)) / 2.0_default
  end if
end function gaux

<SM physics: public>+≡
public :: tri_i1

<SM physics: procedures>+≡
elemental function tri_i1 (a,b) result (y)
  real(default), intent(in) :: a,b
  complex(default) :: y
  if (a < eps0 .or. b < eps0) then

```



```

        y = 0
    else
        y = a*b/2.0_default/(a-b) + a**2 * b**2/2.0_default/(a-b)**2 * &
            (faux(a) - faux(b)) + &
            a**2 * b/(a-b)**2 * (gaux(a) - gaux(b))
    end if
end function tri_i1

```

```

<SM physics: public>+≡
public :: tri_i2

```

```

<SM physics: procedures>+≡
elemental function tri_i2 (a,b) result (y)
    real(default), intent(in) :: a,b
    complex(default) :: y
    if (a < eps0 .or. b < eps0) then
        y = 0
    else
        y = - a * b / 2.0_default / (a-b) * (faux(a) - faux(b))
    end if
end function tri_i2

```

9.4.5 More on α_s

These functions are for the running of the strong coupling constants, α_s .

```

<SM physics: public>+≡
public :: run_b0

```

```

<SM physics: procedures>+≡
elemental function run_b0 (nf) result (bnull)
    integer, intent(in) :: nf
    real(default) :: bnull
    bnull = 33.0_default - 2.0_default * nf
end function run_b0

```

```

<SM physics: public>+≡
public :: run_b1

```

```

<SM physics: procedures>+≡
elemental function run_b1 (nf) result (bone)
    integer, intent(in) :: nf
    real(default) :: bone
    bone = 6.0_default * (153.0_default - 19.0_default * nf)/run_b0(nf)**2
end function run_b1

```

```

<SM physics: public>+≡
public :: run_aa

```

```

<SM physics: procedures>+≡
  elemental function run_aa (nf) result (aaa)
    integer, intent(in) :: nf
    real(default) :: aaa
    aaa = 12.0_default * PI / run_b0(nf)
  end function run_aa

```

```

<SM physics: pubic functions>≡
  public :: run_bb

```

```

<SM physics: procedures>+≡
  elemental function run_bb (nf) result (bbb)
    integer, intent(in) :: nf
    real(default) :: bbb
    bbb = run_b1(nf) / run_aa(nf)
  end function run_bb

```

9.4.6 Functions for Catani-Seymour dipoles

For the automated Catani-Seymour dipole subtraction, we need the following functions.

```

<SM physics: public>+≡
  public :: ff_dipole

```

```

<SM physics: procedures>+≡
  pure subroutine ff_dipole (v_ijk,y_ijk,p_ij,pp_k,p_i,p_j,p_k)
    type(vector4_t), intent(in) :: p_i, p_j, p_k
    type(vector4_t), intent(out) :: p_ij, pp_k
    real(kind=default), intent(out) :: y_ijk
    real(kind=default) :: z_i
    real(kind=default), intent(out) :: v_ijk
    z_i = (p_i*p_k) / ((p_k*p_j) + (p_k*p_i))
    y_ijk = (p_i*p_j) / ((p_i*p_j) + (p_i*p_k) + (p_j*p_k))
    p_ij = p_i + p_j - y_ijk/(1.0_default - y_ijk) * p_k
    pp_k = (1.0/(1.0_default - y_ijk)) * p_k
    !!! We don't multiply by alpha_s right here:
    v_ijk = 8.0_default * PI * CF * &
      (2.0 / (1.0 - z_i*(1.0 - y_ijk)) - (1.0 + z_i))
  end subroutine ff_dipole

```

```

<SM physics: public>+≡
  public :: fi_dipole

```

```

<SM physics: procedures>+≡
  pure subroutine fi_dipole (v_ija,x_ija,p_ij,pp_a,p_i,p_j,p_a)
    type(vector4_t), intent(in) :: p_i, p_j, p_a
    type(vector4_t), intent(out) :: p_ij, pp_a
    real(kind=default), intent(out) :: x_ija
    real(kind=default) :: z_i
    real(kind=default), intent(out) :: v_ija
    z_i = (p_i*p_a) / ((p_a*p_j) + (p_a*p_i))
    x_ija = ((p_i*p_a) + (p_j*p_a) - (p_i*p_j)) &

```

```

      / ((p_i*p_a) + (p_j*p_a))
p_ij = p_i + p_j - (1.0_default - x_ija) * p_a
pp_a = x_ija * p_a
!!! We don't not multiply by alpha_s right here:
v_ija = 8.0_default * PI * CF * &
      (2.0 / (1.0 - z_i + (1.0 - x_ija)) - (1.0 + z_i)) / x_ija
end subroutine fi_dipole

```

```

<SM physics: public>+≡
public :: if_dipole

<SM physics: procedures>+≡
pure subroutine if_dipole (v_kja,u_j,p_aj,pp_k,p_k,p_j,p_a)
  type(vector4_t), intent(in) :: p_k, p_j, p_a
  type(vector4_t), intent(out) :: p_aj, pp_k
  real(kind=default), intent(out) :: u_j
  real(kind=default) :: x_kja
  real(kind=default), intent(out) :: v_kja
  u_j = (p_a*p_j) / ((p_a*p_j) + (p_a*p_k))
  x_kja = ((p_a*p_k) + (p_a*p_j) - (p_j*p_k)) &
    / ((p_a*p_j) + (p_a*p_k))
  p_aj = x_kja * p_a
  pp_k = p_k + p_j - (1.0_default - x_kja) * p_a
  v_kja = 8.0_default * PI * CF * &
    (2.0 / (1.0 - x_kja + u_j) - (1.0 + x_kja)) / x_kja
end subroutine if_dipole

```

This function depends on a variable number of final state particles whose kinematics all get changed by the initial-initial dipole insertion.

```

<SM physics: public>+≡
public :: ii_dipole

<SM physics: procedures>+≡
pure subroutine ii_dipole (v_jab,v_j,p_in,p_out,flag_1or2)
  type(vector4_t), dimension(:), intent(in) :: p_in
  type(vector4_t), dimension(size(p_in)-1), intent(out) :: p_out
  logical, intent(in) :: flag_1or2
  real(kind=default), intent(out) :: v_j
  real(kind=default), intent(out) :: v_jab
  type(vector4_t) :: p_a, p_b, p_j
  type(vector4_t) :: k, kk
  type(vector4_t) :: p_aj
  real(kind=default) :: x_jab
  integer :: i
  !!! flag_1or2 decides whether this a 12 or 21 dipole
  if (flag_1or2) then
    p_a = p_in(1)
    p_b = p_in(2)
  else
    p_b = p_in(1)
    p_a = p_in(2)
  end if
  !!! We assume that the unresolved particle has always the last
  !!! momentum

```

```

p_j = p_in(size(p_in))
x_jab = ((p_a*p_b) - (p_a*p_j) - (p_b*p_j)) / (p_a*p_b)
v_j = (p_a*p_j) / (p_a * p_b)
p_aj = x_jab * p_a
k = p_a + p_b - p_j
kk = p_aj + p_b
do i = 3, size(p_in)-1
  p_out(i) = p_in(i) - 2.0*((k+kk)*p_in(i))/((k+kk)*(k+kk)) * (k+kk) + &
    (2.0 * (k*p_in(i)) / (k*k)) * kk
end do
if (flag_1or2) then
  p_out(1) = p_aj
  p_out(2) = p_b
else
  p_out(1) = p_b
  p_out(2) = p_aj
end if
v_jab = 8.0_default * PI * CF * &
  (2.0 / (1.0 - x_jab) - (1.0 + x_jab)) / x_jab
end subroutine ii_dipole

```

9.4.7 Distributions for integrated dipoles and such

Note that the following formulae are only meaningful for $0 \leq x \leq 1$.

The Dirac delta distribution, modified for Monte-Carlo sampling, centered at $x = 1 - \frac{\epsilon}{2}$:

```

<SM physics: public>+≡
  public :: delta

<SM physics: procedures>+≡
  elemental function delta (x,eps) result (z)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: z
    if (x > one - eps) then
      z = one / eps
    else
      z = 0
    end if
  end function delta

```

The $+$ -distribution, $P_+(x) = \left(\frac{1}{1-x}\right)_+$, for the regularization of soft-collinear singularities. The constant part for the Monte-Carlo sampling is the integral over the splitting function divided by the weight for the WHIZARD numerical integration over the interval.

```

<SM physics: public>+≡
  public :: plus_distr

<SM physics: procedures>+≡
  elemental function plus_distr (x,eps) result (plused)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: plused
    if (x > one - eps) then
      plused = log(eps) / eps
    end if
  end function plus_distr

```

```

else
  plusd = one / (one - x)
end if
end function plus_distr

```

The splitting function in $D = 4$ dimensions, regularized as $+$ -distributions if necessary:

$$P^{qq}(x) = P^{\bar{q}q}(x) = C_F \cdot \left(\frac{1+x^2}{1-x} \right)_+ \quad (9.13)$$

$$P^{qg}(x) = P^{\bar{q}g}(x) = C_F \cdot \frac{1+(1-x)^2}{x} \quad (9.14)$$

$$P^{gg}(x) = P^{gq}(x) = T_R \cdot [x^2 + (1-x)^2] \quad (9.15)$$

$$P^{gg}(x) = 2C_A \left[\left(\frac{1}{1-x} \right)_+ + \frac{1-x}{x} - 1 + x(1-x) \right] + \delta(1-x) \left(\frac{11}{6}C_A - \frac{2}{3}N_f T_R \right) \quad (9.16)$$

Since the number of flavors summed over in the gluon splitting function might depend on the physics case under consideration, it is implemented as an input variable.

```

⟨SM physics: public⟩+≡
  public :: pqq

⟨SM physics: procedures⟩+≡
  elemental function pqq (x,eps) result (pqqx)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: pqqx
    if (x > (1.0_default - eps)) then
      pqqx = (eps - one) / two + two * log(eps) / eps - &
        three * (eps - one) / eps / two
    else
      pqqx = (one + x**2) / (one - x)
    end if
    pqqx = CF * pqqx
  end function pqq

⟨SM physics: public⟩+≡
  public :: pgq

⟨SM physics: procedures⟩+≡
  elemental function pgq (x) result (pgqx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pgqx
    pgqx = TR * (x**2 + (one - x)**2)
  end function pgq

⟨SM physics: public⟩+≡
  public :: pqg

```

```

⟨SM physics: procedures⟩+≡
  elemental function pqg (x) result (pqgx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pqgx
    pqgx = CF * (one + (one - x)**2) / x
  end function pqg

⟨SM physics: public⟩+≡
  public :: pqg

⟨SM physics: procedures⟩+≡
  elemental function pgg (x, nf, eps) result (pggx)
    real(kind=default), intent(in) :: x, nf, eps
    real(kind=default) :: pggx
    pggx = two * CA * ( plus_distr (x, eps) + (one-x)/x - one + &
      x*(one-x)) + delta (x, eps) * gamma_g(nf)
  end function pgg

```

For the qq and gg cases, there exist “regularized” versions of the splitting functions:

$$P_{\text{reg}}^{qq}(x) = -C_F \cdot (1 + x) \quad (9.17)$$

$$P_{\text{reg}}^{gg}(x) = 2C_A \left[\frac{1-x}{x} - 1 + x(1-x) \right] \quad (9.18)$$

```

⟨SM physics: public⟩+≡
  public :: pqq_reg

⟨SM physics: procedures⟩+≡
  elemental function pqq_reg (x) result (pqqregx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pqqregx
    pqqregx = - CF * (one + x)
  end function pqq_reg

⟨SM physics: public⟩+≡
  public :: pgg_reg

⟨SM physics: procedures⟩+≡
  elemental function pgg_reg (x) result (pggregx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pggregx
    pggregx = two * CA * ((one - x)/x - one + x*(one - x))
  end function pgg_reg

```

Here, we collect the expressions needed for integrated Catani-Seymour dipoles, and the so-called flavor kernels. We always distinguish between the “ordinary” Catani-Seymour version, and the one including a phase-space slicing parameter, α .

The standard flavor kernels \overline{K}^{ab} are:

$$\overline{K}^{qg}(x) = \overline{K}^{\bar{q}g}(x) = P^{qg}(x) \log((1-x)/x) + CF \times x \quad (9.19)$$

$$\overline{K}^{gg}(x) = \overline{K}^{\bar{q}\bar{q}}(x) = P^{gg}(x) \log((1-x)/x) + TR \times 2x(1-x) \quad (9.20)$$

$$\begin{aligned} \overline{K}^{qq} = & C_F \left[\left(\frac{2}{1-x} \log \frac{1-x}{x} \right)_+ - (1+x) \log((1-x)/x) + (1-x) \right] \\ & - (5 - \pi^2) \cdot C_F \cdot \delta(1-x) \end{aligned} \quad (9.21)$$

$$\begin{aligned} \overline{K}^{gq} = & 2C_A \left[\left(\frac{1}{1-x} \log \frac{1-x}{x} \right)_+ + \left(\frac{1-x}{x} - 1 + x(1-x) \right) \log((1-x)/x) \right] \\ & - \delta(1-x) \left[\left(\frac{50}{9} - \pi^2 \right) C_A - \frac{16}{9} T_R N_f \right] \end{aligned} \quad (9.22)$$

<SM physics: public>+≡
public :: kbarqg

<SM physics: procedures>+≡
function kbarqg (x) result (kbarqgx)
 real(kind=default), intent(in) :: x
 real(kind=default) :: kbarqgx
 kbarqgx = pqg(x) * log((one-x)/x) + CF * x
end function kbarqg

<SM physics: public>+≡
public :: kbargq

<SM physics: procedures>+≡
function kbargq (x) result (kbargqx)
 real(kind=default), intent(in) :: x
 real(kind=default) :: kbargqx
 kbargqx = pgq(x) * log((one-x)/x) + two * TR * x * (one - x)
end function kbargq

<SM physics: public>+≡
public :: kbarqq

<SM physics: procedures>+≡
function kbarqq (x,eps) result (kbarqqx)
 real(kind=default), intent(in) :: x, eps
 real(kind=default) :: kbarqqx
 kbarqqx = CF*(log_plus_distr(x,eps) - (one+x) * log((one-x)/x) + (one - &
 x) - (five - pi**2) * delta(x,eps))
end function kbarqq

<SM physics: public>+≡
public :: kbargg

<SM physics: procedures>+≡
function kbargg (x,eps,nf) result (kbarggx)
 real(kind=default), intent(in) :: x, eps, nf
 real(kind=default) :: kbarggx
 kbarggx = CA * (log_plus_distr(x,eps) + two * ((one-x)/x - one + &

```

x*(one-x) * log((1-x)/x))) - delta(x,eps) * &
((50.0_default/9.0_default - pi**2) * CA - &
16.0_default/9.0_default * TR * nf)
end function kbargg

```

The \tilde{K} are used when two identified hadrons participate:

$$\tilde{K}^{ab}(x) = P_{\text{reg}}^{ab}(x) \cdot \log(1-x) + \delta^{ab} \mathbf{T}_a^2 \left[\left(\frac{2}{1-x} \log(1-x) \right)_+ - \frac{\pi^2}{3} \delta(1-x) \right] \quad (9.23)$$

```

<SM physics: public>+≡
  public :: ktildeqq

<SM physics: procedures>+≡
  function ktildeqq (x,eps) result (ktildeqqx)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: ktildeqqx
    ktildeqqx = pqq_reg (x) * log(one-x) + CF * ( - log2_plus_distr (x,eps) &
      - pi**2/three * delta(x,eps))
  end function ktildeqq

<SM physics: public>+≡
  public :: ktildeqq

<SM physics: procedures>+≡
  function ktildeqq (x,eps) result (ktildeqqx)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: ktildeqqx
    ktildeqqx = pqq (x) * log(one-x)
  end function ktildeqq

<SM physics: public>+≡
  public :: ktildegg

<SM physics: procedures>+≡
  function ktildegg (x,eps) result (ktildeggx)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: ktildeggx
    ktildeggx = pgg (x) * log(one-x)
  end function ktildegg

<SM physics: public>+≡
  public :: ktildegg

<SM physics: procedures>+≡
  function ktildegg (x,eps) result (ktildeggx)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: ktildeggx
    ktildeggx = pgg_reg (x) * log(one-x) + CA * ( - &
      log2_plus_distr (x,eps) - pi**2/three * delta(x,eps))
  end function ktildegg

```


The insertion operator might not be necessary for a GOLEM interface but is demanded by the Les Houches NLO accord. It is a three-dimensional array, where the index always gives the inverse power of the DREG expansion parameter, ϵ .

```

<SM physics: public>+≡
  public :: insert_q

<SM physics: procedures>+≡
  pure function insert_q ()
    real(kind=default), dimension(0:2) :: insert_q
    insert_q(0) = gamma_q + k_q - pi**2/three * CF
    insert_q(1) = gamma_q
    insert_q(2) = CF
  end function insert_q

<SM physics: public>+≡
  public :: insert_g

<SM physics: procedures>+≡
  pure function insert_g (nf)
    real(kind=default), intent(in) :: nf
    real(kind=default), dimension(0:2) :: insert_g
    insert_g(0) = gamma_g (nf) + k_g (nf) - pi**2/three * CA
    insert_g(1) = gamma_g (nf)
    insert_g(2) = CA
  end function insert_g

```

For better convergence, one can exclude regions of phase space with a slicing parameter from the dipole subtraction procedure. First of all, the K functions get modified:

$$K_i(\alpha) = K_i - \mathbf{T}_i^2 \log^2 \alpha + \gamma_i(\alpha - 1 - \log \alpha) \quad (9.24)$$

```

<SM physics: public>+≡
  public :: k_q_al, k_g_al

<SM physics: procedures>+≡
  pure function k_q_al (alpha)
    real(kind=default), intent(in) :: alpha
    real(kind=default) :: k_q_al
    k_q_al = k_q - CF * (log(alpha))**2 + gamma_q * &
      (alpha - one - log(alpha))
  end function k_q_al

  pure function k_g_al (alpha, nf)
    real(kind=default), intent(in) :: alpha, nf
    real(kind=default) :: k_g_al
    k_g_al = k_g (nf) - CA * (log(alpha))**2 + gamma_g (nf) * &
      (alpha - one - log(alpha))
  end function k_g_al

```

The $+$ -distribution, but with a phase-space slicing parameter, α , $P_{1-\alpha}(x) = \left(\frac{1}{1-x}\right)_{1-x}$. Since we need the fatal error message here, this function cannot be elemental.

```

<SM physics: public>+≡
  public :: plus_distr_al

```

```

⟨SM physics: procedures⟩+≡
function plus_distr_al (x,alpha,eps) result (plusd_al)
  real(kind=default), intent(in) :: x, eps, alpha
  real(kind=default) :: plusd_al
  if ((one - alpha) >= (one - eps)) then
    plusd_al = zero
    call msg_fatal ('sm_physics, plus_distr_al: alpha and epsilon chosen wrongly')
  elseif (x < (1.0_default - alpha)) then
    plusd_al = 0
  else if (x > (1.0_default - eps)) then
    plusd_al = log(eps/alpha)/eps
  else
    plusd_al = one/(one-x)
  end if
end function plus_distr_al

```

Introducing phase-space slicing parameters, these standard flavor kernels \overline{K}^{ab} become:

$$\overline{K}_\alpha^{qg}(x) = \overline{K}_\alpha^{\bar{q}g}(x) = P^{qg}(x) \log(\alpha(1-x)/x) + C_F \times x \quad (9.25)$$

$$\overline{K}_\alpha^{gq}(x) = \overline{K}_\alpha^{g\bar{q}}(x) = P^{gq}(x) \log(\alpha(1-x)/x) + T_R \times 2x(1-x) \quad (9.26)$$

$$\begin{aligned} \overline{K}_\alpha^{qq} = & C_F(1-x) + P_{\text{reg}}^{qq}(x) \log \frac{\alpha(1-x)}{x} \\ & + C_F \delta(1-x) \log^2 \alpha + C_F \left(\frac{2}{1-x} \log \frac{1-x}{x} \right)_+ \\ & - \left(\gamma_q + K_q(\alpha) - \frac{5}{6} \pi^2 C_F \right) \cdot \delta(1-x) C_F \left[+ \frac{2}{1-x} \log \left(\frac{\alpha(2-x)}{1+\alpha-x} \right) - \theta(1-\alpha-x) \cdot \left(\frac{2}{1-x} \right) \right] \end{aligned} \quad (9.27)$$

$$\begin{aligned} \overline{K}_\alpha^{gg} = & P_{\text{reg}}^{gg}(x) \log \frac{\alpha(1-x)}{x} + C_A \delta(1-x) \log^2 \alpha \\ & + C_A \left(\frac{2}{1-x} \log \frac{1-x}{x} \right)_+ - \left(\gamma_g + K_g(\alpha) - \frac{5}{6} \pi^2 C_A \right) \cdot \delta(1-x) C_A \left[+ \frac{2}{1-x} \log \left(\frac{\alpha(2-x)}{1+\alpha-x} \right) - \theta(1-\alpha-x) \cdot \left(\frac{2}{1-x} \right) \right] \end{aligned} \quad (9.28)$$

```

⟨SM physics: public⟩+≡
public :: kbarqg_al

```

```

⟨SM physics: procedures⟩+≡
function kbarqg_al (x,alpha,eps) result (kbarqgx)
  real(kind=default), intent(in) :: x, alpha, eps
  real(kind=default) :: kbarqgx
  kbarqgx = pqg (x) * log(alpha*(one-x)/x) + CF * x
end function kbarqg_al

```

```

⟨SM physics: public⟩+≡
public :: kbargq_al

```

```

⟨SM physics: procedures⟩+≡
function kbargq_al (x,alpha,eps) result (kbargqx)
  real(kind=default), intent(in) :: x, alpha, eps
  real(kind=default) :: kbargqx
  kbargqx = pgq (x) * log(alpha*(one-x)/x) + two * TR * x * (one-x)
end function kbargq_al

```

```

⟨SM physics: public⟩+≡
  public :: kbarqq_al
⟨SM physics: procedures⟩+≡
  function kbarqq_al (x,alpha,eps) result (kbarqqx)
    real(kind=default), intent(in) :: x, alpha, eps
    real(kind=default) :: kbarqqx
    kbarqqx = CF * (one - x) + pqq_reg(x) * log(alpha*(one-x)/x) &
      + CF * log_plus_distr(x,eps) &
      - (gamma_q + k_q_al(alpha) - CF * &
        five/6.0_default * pi**2 - CF * (log(alpha))**2) * &
        delta(x,eps) + &
        CF * two/(one -x)*log(alpha*(two-x)/(one+alpha-x))
    if (x < (one-alpha)) then
      kbarqqx = kbarqqx - CF * two/(one-x) * log((two-x)/(one-x))
    end if
  end function kbarqq_al

```

```

⟨SM physics: public⟩+≡
  public :: kbargg_al
⟨SM physics: procedures⟩+≡
  function kbargg_al (x,alpha,eps,nf) result (kbarggx)
    real(kind=default), intent(in) :: x, alpha, eps, nf
    real(kind=default) :: kbarggx
    kbarggx = pgg_reg(x) * log(alpha*(one-x)/x) &
      + CA * log_plus_distr(x,eps) &
      - (gamma_g(nf) + k_g_al(alpha,nf) - CA * &
        five/6.0_default * pi**2 - CA * (log(alpha))**2) * &
        delta(x,eps) + &
        CA * two/(one -x)*log(alpha*(two-x)/(one+alpha-x))
    if (x < (one-alpha)) then
      kbarggx = kbarggx - CA * two/(one-x) * log((two-x)/(one-x))
    end if
  end function kbargg_al

```

The \tilde{K} flavor kernels in the presence of a phase-space slicing parameter, are:

$$\tilde{K}^{ab}(x, \alpha) = P^{qq, \text{reg}}(x) \log \frac{1-x}{\alpha} + \dots \quad (9.29)$$

```

⟨SM physics: public⟩+≡
  public :: ktildeqq_al
⟨SM physics: procedures⟩+≡
  function ktildeqq_al (x,alpha,eps) result (ktildeqqx)
    real(kind=default), intent(in) :: x, eps, alpha
    real(kind=default) :: ktildeqqx
    ktildeqqx = pqq_reg(x) * log((one-x)/alpha) + CF*( &
      - log2_plus_distr_al(x,alpha,eps) - Pi**2/three * delta(x,eps) &
      + (one+x**2)/(one-x) * log(min(one,(alpha/(one-x)))) &
      + two/(one-x) * log((one+alpha-x)/alpha))
    if (x > (one-alpha)) then
      ktildeqqx = ktildeqqx - CF*two/(one-x)*log(two-x)
    end if
  end function ktildeqq_al

```

This is a logarithmic +-distribution, $\left(\frac{\log((1-x)/x)}{1-x}\right)_+$. For the sampling, we need the integral over this function over the incomplete sampling interval $[0, 1 - \epsilon]$, which is $\log^2(x) + 2Li_2(x) - \frac{\pi^2}{3}$. As this function is negative definite for $\epsilon > 0.1816$, we take a hard upper limit for that sampling parameter, irrespective of the fact what the user chooses.

```

⟨SM physics: public⟩+≡
  public :: log_plus_distr

⟨SM physics: procedures⟩+≡
  function log_plus_distr (x,eps) result (lpd)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: lpd, eps2
    eps2 = min (eps, 0.1816_default)
    if (x > (1.0_default - eps2)) then
      lpd = ((log(eps2))**2 + two*Li2(eps2) - pi**2/three)/eps2
    else
      lpd = two*log((one-x)/x)/(one-x)
    end if
  end function log_plus_distr

```

Logarithmic +-distribution, $2\left(\frac{\log(1/(1-x))}{1-x}\right)_+$.

```

⟨SM physics: public⟩+≡
  public :: log2_plus_distr

⟨SM physics: procedures⟩+≡
  function log2_plus_distr (x,eps) result (lpd)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: lpd
    if (x > (1.0_default - eps)) then
      lpd = - (log(eps))**2/eps
    else
      lpd = two*log(one/(one-x))/(one-x)
    end if
  end function log2_plus_distr

```

Logarithmic +-distribution with phase-space slicing parameter, $2\left(\frac{\log(1/(1-x))}{1-x}\right)_{1-\alpha}$.

```

⟨SM physics: public⟩+≡
  public :: log2_plus_distr_al

⟨SM physics: procedures⟩+≡
  function log2_plus_distr_al (x,alpha,eps) result (lpd_al)
    real(kind=default), intent(in) :: x, eps, alpha
    real(kind=default) :: lpd_al
    if ((one - alpha) >= (one - eps)) then
      lpd_al = zero
      call msg_fatal ('alpha and epsilon chosen wrongly')
    elseif (x < (one - alpha)) then
      lpd_al = 0
    elseif (x > (1.0_default - eps)) then
      lpd_al = - ((log(eps))**2 - (log(alpha))**2)/eps
    else
      lpd_al = two*log(one/(one-x))/(one-x)
    end if
  end function log2_plus_distr_al

```

```

end if
end function log2_plus_distr_al

```

9.4.8 Splitting Functions

Analogue to the regularized distributions of the last subsection, we give here the unregularized splitting functions, relevant for the parton shower algorithm. We can use this unregularized version since there will be a cut-off ϵ that ensures that $\{z, 1 - z\} > \epsilon(t)$. This cut-off separates resolvable from unresolvable emissions. p_{xxx} are the kernels that are summed over helicity:

```

⟨SM physics: public⟩+≡
  public :: p_qqg
  public :: p_gqq
  public :: p_ggg

q → qq
⟨SM physics: procedures⟩+≡
  elemental function p_qqg (z) result (P)
    real(default), intent(in) :: z
    real(default) :: P
    P = CF * (one + z**2) / (one - z)
  end function p_qqg

g → q $\bar{q}$ 
⟨SM physics: procedures⟩+≡
  elemental function p_gqq (z) result (P)
    real(default), intent(in) :: z
    real(default) :: P
    P = TR * (z**2 + (one - z)**2)
  end function p_gqq

g → gg
⟨SM physics: procedures⟩+≡
  elemental function p_ggg (z) result (P)
    real(default), intent(in) :: z
    real(default) :: P
    P = NC * ((one - z) / z + z / (one - z) + z * (one - z))
  end function p_ggg

```

Analytically integrated splitting kernels:

```

⟨SM physics: public⟩+≡
  public :: integral_over_p_qqg
  public :: integral_over_p_gqq
  public :: integral_over_p_ggg

⟨SM physics: procedures⟩+≡
  pure function integral_over_p_qqg (zmin, zmax) result (integral)
    real(default), intent(in) :: zmin, zmax
    real(default) :: integral
    integral = (two / three) * (- zmax**2 + zmin**2 - &
      two * (zmax - zmin) + four * log((one - zmin) / (one - zmax)))
  end function integral_over_p_qqg

```

```

pure function integral_over_p_gqq (zmin, zmax) result (integral)
  real(default), intent(in) :: zmin, zmax
  real(default) :: integral
  integral = 0.5_default * ((two / three) * &
    (zmax**3 - zmin**3) - (zmax**2 - zmin**2) + (zmax - zmin))
end function integral_over_p_gqq

pure function integral_over_p_ggg (zmin, zmax) result (integral)
  real(default), intent(in) :: zmin, zmax
  real(default) :: integral
  integral = three * ((log(zmax) - two * zmax - &
    log(one - zmax) + zmax**2 / two - zmax**3 / three) - &
    (log(zmin) - zmin - zmin - log(one - zmin) + zmin**2 &
    / two - zmin**3 / three) )
end function integral_over_p_ggg

```

We can also use (massless) helicity dependent splitting functions:

$\langle SM \text{ physics: public} \rangle + \equiv$

```
public :: p_qqg_pol
```

$q_a \rightarrow q_b g_c$, the helicity of the quark is not changed by gluon emission and the gluon is preferably polarized in the branching plane ($l_c = 1$):

$\langle SM \text{ physics: procedures} \rangle + \equiv$

```

elemental function p_qqg_pol (z, l_a, l_b, l_c) result (P)
  real(default), intent(in) :: z
  integer, intent(in) :: l_a, l_b, l_c
  real(default) :: P
  if (l_a /= l_b) then
    P = zero
    return
  end if
  if (l_c == -1) then
    P = one - z
  else
    P = (one + z)**2 / (one - z)
  end if
  P = P * CF
end function p_qqg_pol

```

9.4.9 Unit tests

$\langle SM \text{ physics: public} \rangle + \equiv$

```
public :: sm_physics_test
```

$\langle SM \text{ physics: tests} \rangle \equiv$

```

subroutine sm_physics_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
 $\langle SM \text{ physics: execute tests} \rangle$ 
end subroutine sm_physics_test

```

Splitting functions

```
<SM physics: execute tests>≡
  call test (sm_physics_1, "sm_physics_1", &
    "Splitting functions", &
    u, results)

<SM physics: tests>+≡
  subroutine sm_physics_1 (u)
    integer, intent(in) :: u
    real(default) :: z = 0.75_default

    write (u, "(A)")  "* Test output: sm_physics_1"
    write (u, "(A)")  "* Purpose: check analytic properties"
    write (u, "(A)")

    write (u, "(A)")  "* Splitting functions:"
    write (u, "(A)")

    call assert (u, vanishes (p_qqg_pol (z, +1, -1, +1)))
    call assert (u, vanishes (p_qqg_pol (z, +1, -1, -1)))
    call assert (u, vanishes (p_qqg_pol (z, -1, +1, +1)))
    call assert (u, vanishes (p_qqg_pol (z, -1, +1, -1)))

    call assert (u, nearly_equal ( &
      p_qqg_pol (z, +1, +1, -1) + p_qqg_pol (z, +1, +1, +1), &
      p_qqg (z)))

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: sm_physics_1"

  end subroutine sm_physics_1
```

9.5 QCD Coupling

We provide various distinct implementations of the QCD coupling. In this module, we define an abstract data type and three implementations: fixed, running with $\alpha_s(M_Z)$ as input, and running with Λ_{QCD} as input. We use the functions defined above in the module `sm_physics` but provide a common interface. Later modules may define additional implementations.

```
<sm_qcd.f90>≡  
<File header>  
  
module sm_qcd  
  
  <Use kinds>  
    use io_units  
    use format_defs, only: FMT_12  
    use unit_tests  
    use diagnostics  
    use md5  
    use physics_defs  
    use sm_physics  
  
  <Standard module head>  
  
  <SM qcd: public>  
  
  <SM qcd: types>  
  
  <SM qcd: interfaces>  
  
  contains  
  
  <SM qcd: procedures>  
  
  <SM qcd: tests>  
  
end module sm_qcd
```

9.5.1 Coupling: Abstract Data Type

This is the abstract version of the QCD coupling implementation.

```
<SM qcd: public>≡  
  public :: alpha_qcd_t  
  
<SM qcd: types>≡  
  type, abstract :: alpha_qcd_t  
    contains  
    <SM qcd: alpha qcd: TBP>  
  end type alpha_qcd_t
```

There must be an output routine.

```
<SM qcd: alpha qcd: TBP>≡  
  procedure (alpha_qcd_write), deferred :: write
```



```

⟨SM qcd: interfaces⟩≡
  abstract interface
    subroutine alpha_qcd_write (object, unit)
      import
      class(alpha_qcd_t), intent(in) :: object
      integer, intent(in), optional :: unit
    end subroutine alpha_qcd_write
  end interface

```

This method computes the running coupling, given a certain scale. All parameters (reference value, order of the approximation, etc.) must be set before calling this.

```

⟨SM qcd: alpha qcd: TBP⟩+≡
  procedure (alpha_qcd_get), deferred :: get

⟨SM qcd: interfaces⟩+≡
  abstract interface
    function alpha_qcd_get (alpha_qcd, scale) result (alpha)
      import
      class(alpha_qcd_t), intent(in) :: alpha_qcd
      real(default), intent(in) :: scale
      real(default) :: alpha
    end function alpha_qcd_get
  end interface

```

9.5.2 Fixed Coupling

In this version, the α_s value is fixed, the `scale` argument of the `get` method is ignored. There is only one parameter, the value. By default, this is the value at M_Z .

```

⟨SM qcd: public⟩+≡
  public :: alpha_qcd_fixed_t

⟨SM qcd: types⟩+≡
  type, extends (alpha_qcd_t) :: alpha_qcd_fixed_t
    real(default) :: val = ALPHA_QCD_MZ_REF
  contains
    ⟨SM qcd: alpha qcd fixed: TBP⟩
  end type alpha_qcd_fixed_t

```

Output.

```

⟨SM qcd: alpha qcd fixed: TBP⟩≡
  procedure :: write => alpha_qcd_fixed_write

⟨SM qcd: procedures⟩≡
  subroutine alpha_qcd_fixed_write (object, unit)
    class(alpha_qcd_fixed_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(3x,A)") "QCD parameters (fixed coupling):"
    write (u, "(5x,A," // FMT_12 // ")") "alpha = ", object%val
  end subroutine alpha_qcd_fixed_write

```

```
end subroutine alpha_qcd_fixed_write
```

Calculation: the scale is ignored in this case.

```
<SM qcd: alpha qcd fixed: TBP>+≡
  procedure :: get => alpha_qcd_fixed_get

<SM qcd: procedures>+≡
  function alpha_qcd_fixed_get (alpha_qcd, scale) result (alpha)
    class(alpha_qcd_fixed_t), intent(in) :: alpha_qcd
    real(default), intent(in) :: scale
    real(default) :: alpha
    alpha = alpha_qcd%val
  end function alpha_qcd_fixed_get
```

9.5.3 Running Coupling

In this version, the α_s value runs relative to the value at a given reference scale. There are two parameters: the value of this scale (default: M_Z), the value of α_s at this scale, and the number of effective flavors. Furthermore, we have the order of the approximation.

```
<SM qcd: public>+≡
  public :: alpha_qcd_from_scale_t

<SM qcd: types>+≡
  type, extends (alpha_qcd_t) :: alpha_qcd_from_scale_t
    real(default) :: mu_ref = MZ_REF
    real(default) :: ref = ALPHA_QCD_MZ_REF
    integer :: order = 0
    integer :: nf = 5
  contains
    <SM qcd: alpha qcd from scale: TBP>
  end type alpha_qcd_from_scale_t
```

Output.

```
<SM qcd: alpha qcd from scale: TBP>≡
  procedure :: write => alpha_qcd_from_scale_write

<SM qcd: procedures>+≡
  subroutine alpha_qcd_from_scale_write (object, unit)
    class(alpha_qcd_from_scale_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(3x,A)") "QCD parameters (running coupling):"
    write (u, "(5x,A," // FMT_12 // ")") "Scale mu = ", object%mu_ref
    write (u, "(5x,A," // FMT_12 // ")") "alpha(mu) = ", object%ref
    write (u, "(5x,A,I0)") "LL order = ", object%order
    write (u, "(5x,A,I0)") "N(flav) = ", object%nf
  end subroutine alpha_qcd_from_scale_write
```

Calculation: here, we call the function for running α_s that was defined in `sm_physics` above. The function does not take into account thresholds, so the number of flavors should be the correct one for the chosen scale. Normally, this should be the Z boson mass.

```

⟨SM qcd: alpha qcd from scale: TBP⟩+≡
  procedure :: get => alpha_qcd_from_scale_get

⟨SM qcd: procedures⟩+≡
  function alpha_qcd_from_scale_get (alpha_qcd, scale) result (alpha)
    class(alpha_qcd_from_scale_t), intent(in) :: alpha_qcd
    real(default), intent(in) :: scale
    real(default) :: alpha
    alpha = running_as (scale, &
      alpha_qcd%ref, alpha_qcd%mu_ref, alpha_qcd%order, &
      real (alpha_qcd%nf, kind=default))
  end function alpha_qcd_from_scale_get

```

9.5.4 Running Coupling, determined by Λ_{QCD}

In this version, the input are the value Λ_{QCD} and the order of the approximation.

```

⟨SM qcd: public⟩+≡
  public :: alpha_qcd_from_lambda_t

⟨SM qcd: types⟩+≡
  type, extends (alpha_qcd_t) :: alpha_qcd_from_lambda_t
    real(default) :: lambda = LAMBDA_QCD_REF
    integer :: order = 0
    integer :: nf = 5
  contains
    ⟨SM qcd: alpha qcd from lambda: TBP⟩
  end type alpha_qcd_from_lambda_t

```

Output.

```

⟨SM qcd: alpha qcd from lambda: TBP⟩≡
  procedure :: write => alpha_qcd_from_lambda_write

⟨SM qcd: procedures⟩+≡
  subroutine alpha_qcd_from_lambda_write (object, unit)
    class(alpha_qcd_from_lambda_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(3x,A)") "QCD parameters (Lambda_QCD as input):"
    write (u, "(5x,A," // FMT_12 // ")") "Lambda_QCD = ", object%lambda
    write (u, "(5x,A,I0)") "LL order = ", object%order
    write (u, "(5x,A,I0)") "N(flv) = ", object%nf
  end subroutine alpha_qcd_from_lambda_write

```

Calculation: here, we call the second function for running α_s that was defined in `sm_physics` above. The Λ value should be the one that is appropriate for the chosen number of effective flavors. Again, thresholds are not incorporated.

```

⟨SM qcd: alpha qcd from lambda: TBP⟩+≡
  procedure :: get => alpha_qcd_from_lambda_get

```

```

⟨SM qcd: procedures⟩+≡
function alpha_qcd_from_lambda_get (alpha_qcd, scale) result (alpha)
  class(alpha_qcd_from_lambda_t), intent(in) :: alpha_qcd
  real(default), intent(in) :: scale
  real(default) :: alpha
  alpha = running_as_lam (real (alpha_qcd%nf, kind=default), scale, &
    alpha_qcd%lambda, alpha_qcd%order)
end function alpha_qcd_from_lambda_get

```

9.5.5 Wrapper type

We could get along with a polymorphic QCD type, but a monomorphic wrapper type with a polymorphic component is easier to handle and probably safer (w.r.t. compiler bugs). However, we keep the object transparent, so we can set the type-specific parameters directly (by a `dispatch` routine).

```

⟨SM qcd: public⟩+≡
  public :: qcd_t
⟨SM qcd: types⟩+≡
  type :: qcd_t
    class(alpha_qcd_t), allocatable :: alpha
    character(32) :: md5sum = ""
  contains
    ⟨SM qcd: qcd: TBP⟩
  end type qcd_t

```

Output. We first print the polymorphic `alpha` which contains a headline, then any extra components.

```

⟨SM qcd: qcd: TBP⟩≡
  procedure :: write => qcd_write
⟨SM qcd: procedures⟩+≡
  subroutine qcd_write (qcd, unit, show_md5sum)
    class(qcd_t), intent(in) :: qcd
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_md5sum
    logical :: show_md5
    integer :: u
    u = given_output_unit (unit)
    show_md5 = .true.; if (present (show_md5sum)) show_md5 = show_md5sum
    if (allocated (qcd%alpha)) then
      call qcd%alpha%write (u)
    else
      write (u, "(3x,A)") "QCD parameters (coupling undefined)"
    end if
    if (show_md5 .and. qcd%md5sum /= "") &
      write (u, "(5x,A,A,A)") "md5sum = '", qcd%md5sum, "'"
  end subroutine qcd_write

```

Compute a MD5 sum for the `alpha_s` setup. This is done by writing them to a temporary file, using a standard format.

```

⟨SM qcd: qcd: TBP⟩+≡

```

```

        procedure :: compute_alphas_md5sum => qcd_compute_alphas_md5sum
    <SM qcd: procedures>+≡
        subroutine qcd_compute_alphas_md5sum (qcd)
            class(qcd_t), intent(inout) :: qcd
            integer :: unit
            if (allocated (qcd%alpha)) then
                unit = free_unit ()
                open (unit, status="scratch", action="readwrite")
                call qcd%alpha%write (unit)
                rewind (unit)
                qcd%md5sum = md5sum (unit)
                close (unit)
            end if
        end subroutine qcd_compute_alphas_md5sum

```

Retrieve the MD5 sum of the qcd setup.

```

    <SM qcd: qcd: TBP>+≡
        procedure :: get_md5sum => qcd_get_md5sum

    <SM qcd: procedures>+≡
        function qcd_get_md5sum (qcd) result (md5sum)
            character(32) :: md5sum
            class(qcd_t), intent(inout) :: qcd
            md5sum = qcd%md5sum
        end function qcd_get_md5sum

```

9.5.6 Unit tests

```

    <SM qcd: public>+≡
        public :: sm_qcd_test

    <SM qcd: tests>≡
        subroutine sm_qcd_test (u, results)
            integer, intent(in) :: u
            type(test_results_t), intent(inout) :: results
        <SM qcd: execute tests>
        end subroutine sm_qcd_test

```

QCD Coupling

We check two different implementations of the abstract QCD coupling.

```

    <SM qcd: execute tests>≡
        call test (sm_qcd_1, "sm_qcd_1", &
            "running alpha_s", &
            u, results)

    <SM qcd: tests>+≡
        subroutine sm_qcd_1 (u)
            integer, intent(in) :: u
            type(qcd_t) :: qcd

```

```

write (u, "(A)")  "* Test output: sm_qcd_1"
write (u, "(A)")  "* Purpose: compute running alpha_s"
write (u, "(A)")

write (u, "(A)")  "* Fixed:"
write (u, "(A)")

allocate (alpha_qcd_fixed_t :: qcd%alpha)
call qcd%compute_alphas_md5sum ()

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
      qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
      qcd%alpha%get (1000._default)
write (u, *)
deallocate (qcd%alpha)

write (u, "(A)")  "* Running from MZ (LO):"
write (u, "(A)")

allocate (alpha_qcd_from_scale_t :: qcd%alpha)
call qcd%compute_alphas_md5sum ()

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
      qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
      qcd%alpha%get (1000._default)
write (u, *)

write (u, "(A)")  "* Running from MZ (NLO):"
write (u, "(A)")

select type (alpha => qcd%alpha)
type is (alpha_qcd_from_scale_t)
  alpha%order = 1
end select
call qcd%compute_alphas_md5sum ()

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
      qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
      qcd%alpha%get (1000._default)
write (u, *)

write (u, "(A)")  "* Running from MZ (NNLO):"
write (u, "(A)")

select type (alpha => qcd%alpha)

```

```

type is (alpha_qcd_from_scale_t)
  alpha%order = 2
end select
call qcd%compute_alphas_md5sum ()

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
  qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
  qcd%alpha%get (1000._default)
write (u, *)

deallocate (qcd%alpha)
write (u, "(A)")  "* Running from Lambda_QCD (LO):"
write (u, "(A)")

allocate (alpha_qcd_from_lambda_t :: qcd%alpha)
call qcd%compute_alphas_md5sum ()

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
  qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
  qcd%alpha%get (1000._default)
write (u, *)

write (u, "(A)")  "* Running from Lambda_QCD (NLO):"
write (u, "(A)")

select type (alpha => qcd%alpha)
type is (alpha_qcd_from_lambda_t)
  alpha%order = 1
end select
call qcd%compute_alphas_md5sum ()

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
  qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
  qcd%alpha%get (1000._default)
write (u, *)

write (u, "(A)")  "* Running from Lambda_QCD (NNLO):"
write (u, "(A)")

select type (alpha => qcd%alpha)
type is (alpha_qcd_from_lambda_t)
  alpha%order = 2
end select
call qcd%compute_alphas_md5sum ()

```

```

call qcd%write (u)
write (u, *)
write (u, "(1x,A,F10.7)") "alpha_s (mz)   =", &
    qcd%alpha%get (MZ_REF)
write (u, "(1x,A,F10.7)") "alpha_s (1 TeV) =", &
    qcd%alpha%get (1000._default)

write (u, "(A)")
write (u, "(A)")  "* Test output end: sm_qcd_1"

end subroutine sm_qcd_1

```


9.6 Shower algorithms

```

⟨shower_algorithms.f90⟩≡
  ⟨File header⟩

  module shower_algorithms

    ⟨Use kinds⟩
    use constants
    use unit_tests
    use rng_base

    ⟨Standard module head⟩

    ⟨shower_algorithms: public⟩

    ⟨shower_algorithms: interfaces⟩

    contains

    ⟨shower_algorithms: procedures⟩

    ⟨shower_algorithms: tests⟩

  end module shower_algorithms

```

We want to generate emission variables $\mathbf{x} \in \mathbb{R}^d$ proportional to

$$f(\mathbf{x}) \propto \Delta(f, h(\mathbf{x})) \quad \text{with} \quad (9.30)$$

$$\Delta(f, H) = \exp \left\{ - \int d^d x' f(x') \Theta(h(x') - H) \right\} \quad (9.31)$$

The `true_function` f is however too complicated and we are only able to generate \mathbf{x} according to the `overestimator` F . This algorithm is described in Appendix B of 0709.2092 and is proven e.g. in 1211.7204 and hep-ph/0606275. Intuitively speaking, we overestimate the emission probability and can therefore set `scale_max = scale` if the emission is rejected.

```

⟨shower_algorithms: procedures⟩≡
  subroutine generate_vetoed (x, rng, overestimator, true_function, &
    sudakov, inverse_sudakov, scale_min)
    real(default), dimension(:), intent(out) :: x
    class(rng_t), intent(inout) :: rng
    procedure(XXX_function), pointer, intent(in) :: overestimator, true_function
    procedure(sudakov_p), pointer, intent(in) :: sudakov, inverse_sudakov
    real(default), intent(in) :: scale_min
    real(default) :: random, scale_max, scale
    scale_max = inverse_sudakov (one)
    do while (scale_max > scale_min)
      call rng%generate (random)
      scale = inverse_sudakov (random * sudakov (scale_max))
      call generate_on_hypersphere (x, overestimator, scale)
      call rng%generate (random)
      if (random < true_function (x) / overestimator (x)) then
        return !!! accept x
      end if
    end do
  end subroutine generate_vetoed

```

```

        end if
        scale_max = scale
    end do
end subroutine generate_vetoed

```

```

⟨shower algorithms: procedures⟩+≡
pure subroutine generate_on_hypersphere (x, overestimator, scale)
    real(default), dimension(:), intent(out) :: x
    procedure(XXX_function), pointer, intent(in) :: overestimator
    real(default), intent(in) :: scale
end subroutine generate_on_hypersphere

```

```

⟨shower algorithms: interfaces⟩≡
interface
    pure function XXX_function (x)
        import
        real(default) :: XXX_function
        real(default), dimension(:), intent(in) :: x
    end function XXX_function
end interface
interface
    pure function sudakov_p (x)
        import
        real(default) :: sudakov_p
        real(default), intent(in) :: x
    end function sudakov_p
end interface

```

9.6.1 Unit tests

```

⟨shower algorithms: public⟩≡
public :: shower_algorithms_test

⟨shower algorithms: tests⟩≡
subroutine shower_algorithms_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
⟨shower algorithms: execute tests⟩
end subroutine shower_algorithms_test

```

Splitting functions

```

⟨shower algorithms: execute tests⟩≡
call test (shower_algorithms_1, "shower_algorithms_1", &
    "veto technique", &
    u, results)

⟨shower algorithms: tests⟩+≡
subroutine shower_algorithms_1 (u)
    integer, intent(in) :: u

    write (u, "(A)")  "* Test output: shower_algorithms_1"

```

```

write (u, "(A)")  "* Purpose: check veto technique"
write (u, "(A)")

write (u, "(A)")  "* Splitting functions:"
write (u, "(A)")

!call assert (u, vanishes (p_qqg_pol (z, +1, -1, +1)))
!call assert (u, nearly_equal ( &
    !p_qqg_pol (z, +1, +1, -1) + p_qqg_pol (z, +1, +1, +1),
    !p_qqg (z))

write (u, "(A)")
write (u, "(A)")  "* Test output end: shower_algorithms_1"

end subroutine shower_algorithms_1

```

Chapter 10

Quantum Field Theory Concepts

The objects and methods defined here implement concepts and data for the underlying quantum field theory that we use for computing matrix elements and processes.

model_data Fields and coupling parameters, operators as vertex structures, for a specific model.

model_testbed Provide hooks to deal with a **model_data** extension without referencing it explicitly.

helicities Types and methods for spin density matrices.

colors Dealing with colored particles, using the color-flow representation.

flavors PDG codes and particle properties, depends on the model.

quantum_numbers Quantum numbers and density matrices for entangled particle systems.

10.1 Model Data

These data represent a specific Lagrangian in numeric terms. That is, we have the fields with their quantum numbers, the masses, widths and couplings as numerical values, and the vertices as arrays of fields.

We do not store the relations between coupling parameters. They should be represented by expressions for evaluation, implemented as Sindarin objects in a distinct data structure. Neither do we need the algebraic structure of vertices. The field content of vertices is required for the sole purpose of setting up phase space.

```
<model_data.f90>≡  
<File header>  
  
module model_data  
  
    use, intrinsic :: iso_c_binding !NODEP!  
  
    <Use kinds>  
    use kinds, only: i8, i32  
    use kinds, only: c_default_float  
    <Use strings>  
    use format_defs, only: FMT_19  
    use io_units  
    use unit_tests  
    use diagnostics  
    use md5  
    use hashes, only: hash  
    use physics_defs, only: UNDEFINED, SCALAR  
  
    <Standard module head>  
  
    <Model data: public>  
  
    <Model data: parameters>  
  
    <Model data: types>  
  
    <Model data: interfaces>  
  
contains  
  
    <Model data: procedures>  
  
    <Model data: tests>  
  
end module model_data
```

10.1.1 Physics Parameters

Couplings, masses, and widths are physics parameters. Each parameter has a unique name (used, essentially, for diagnostics output and debugging) and a value. The value may be a real or a complex number, so we provide to

implementations of an abstract type.

```

<Model data: public>≡
    public :: modelpar_data_t

<Model data: types>≡
    type, abstract :: modelpar_data_t
        private
            type(string_t) :: name
        contains
            <Model data: par data: TBP>
        end type modelpar_data_t

    type, extends (modelpar_data_t) :: modelpar_real_t
        private
            real(default) :: value
        end type modelpar_real_t

    type, extends (modelpar_data_t) :: modelpar_complex_t
        private
            complex(default) :: value
        end type modelpar_complex_t

```

Output for diagnostics. Non-advancing.

```

<Model data: par data: TBP>≡
    procedure :: write => par_write

<Model data: procedures>≡
    subroutine par_write (par, unit)
        class(modelpar_data_t), intent(in) :: par
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A,1x,A)", advance="no") char (par%name), "= "
        select type (par)
            class is (modelpar_real_t)
                write (u, "(" // FMT_19 // ")", advance="no") par%value
            class is (modelpar_complex_t)
                write (u, "(" // FMT_19 // ",1x,'+',1x," // FMT_19 // ",1x,'I')", &
                    advance="no") par%value
        end select
    end subroutine par_write

```

Pretty-printed on separate line, with fixed line length

```

<Model data: par data: TBP>+≡
    procedure :: show => par_show

<Model data: procedures>+≡
    subroutine par_show (par, l, u)
        class(modelpar_data_t), intent(in) :: par
        integer, intent(in) :: l, u
        character(len=l) :: buffer
        buffer = par%name
        select type (par)
            class is (modelpar_real_t)

```

```

        write (u, "(4x,A,1x,'=',1x," // FMT_19 // ")") buffer, par%value
        class is (modelpar_complex_t)
        write (u, "(4x,A,1x,'=',1x," // FMT_19 // ",1x,'+',1x," &
            // FMT_19 // ",1x,'I')") buffer, par%value
    end select
end subroutine par_show

```

Initialize with name and value. The type depends on the argument type. If the type does not match, the value is converted following Fortran rules.

```

<Model data: par data: TBP>+≡
    generic :: init => modelpar_data_init_real, modelpar_data_init_complex
    procedure, private :: modelpar_data_init_real
    procedure, private :: modelpar_data_init_complex

<Model data: procedures>+≡
    subroutine modelpar_data_init_real (par, name, value)
        class(modelpar_data_t), intent(out) :: par
        type(string_t), intent(in) :: name
        real(default), intent(in) :: value
        par%name = name
        par = value
    end subroutine modelpar_data_init_real

    subroutine modelpar_data_init_complex (par, name, value)
        class(modelpar_data_t), intent(out) :: par
        type(string_t), intent(in) :: name
        complex(default), intent(in) :: value
        par%name = name
        par = value
    end subroutine modelpar_data_init_complex

```

Modify the value. We assume that the parameter has been initialized. The type (real or complex) must not be changed, and the name is also fixed.

```

<Model data: par data: TBP>+≡
    generic :: assignment(=) => modelpar_data_set_real, modelpar_data_set_complex
    procedure, private :: modelpar_data_set_real
    procedure, private :: modelpar_data_set_complex

<Model data: procedures>+≡
    elemental subroutine modelpar_data_set_real (par, value)
        class(modelpar_data_t), intent(inout) :: par
        real(default), intent(in) :: value
        select type (par)
            class is (modelpar_real_t)
                par%value = value
            class is (modelpar_complex_t)
                par%value = value
        end select
    end subroutine modelpar_data_set_real

    elemental subroutine modelpar_data_set_complex (par, value)
        class(modelpar_data_t), intent(inout) :: par
        complex(default), intent(in) :: value
        select type (par)

```

```

        class is (modelpar_real_t)
            par%value = value
        class is (modelpar_complex_t)
            par%value = value
        end select
    end subroutine modelpar_data_set_complex

```

Return the parameter name.

```

<Model data: par data: TBP>+≡
    procedure :: get_name => modelpar_data_get_name

<Model data: procedures>+≡
    function modelpar_data_get_name (par) result (name)
        class(modelpar_data_t), intent(in) :: par
        type(string_t) :: name
        name = par%name
    end function modelpar_data_get_name

```

Return the value. In case of a type mismatch, follow Fortran conventions.

```

<Model data: par data: TBP>+≡
    procedure, pass :: get_real => modelpar_data_get_real
    procedure, pass :: get_complex => modelpar_data_get_complex

<Model data: procedures>+≡
    elemental function modelpar_data_get_real (par) result (value)
        class(modelpar_data_t), intent(in), target :: par
        real(default) :: value
        select type (par)
            class is (modelpar_real_t)
                value = par%value
            class is (modelpar_complex_t)
                value = par%value
        end select
    end function modelpar_data_get_real

    elemental function modelpar_data_get_complex (par) result (value)
        class(modelpar_data_t), intent(in), target :: par
        complex(default) :: value
        select type (par)
            class is (modelpar_real_t)
                value = par%value
            class is (modelpar_complex_t)
                value = par%value
        end select
    end function modelpar_data_get_complex

```

Return a pointer to the value. This makes sense only for matching types.

```

<Model data: par data: TBP>+≡
    procedure :: get_real_ptr => modelpar_data_get_real_ptr
    procedure :: get_complex_ptr => modelpar_data_get_complex_ptr

<Model data: procedures>+≡
    function modelpar_data_get_real_ptr (par) result (ptr)
        class(modelpar_data_t), intent(in), target :: par

```



```

    real(default), pointer :: ptr
    select type (par)
    class is (modelpar_real_t)
        ptr => par%value
    class default
        ptr => null ()
    end select
end function modelpar_data_get_real_ptr

function modelpar_data_get_complex_ptr (par) result (ptr)
    class(modelpar_data_t), intent(in), target :: par
    complex(default), pointer :: ptr
    select type (par)
    class is (modelpar_complex_t)
        ptr => par%value
    class default
        ptr => null ()
    end select
end function modelpar_data_get_complex_ptr

```

10.1.2 Field Data

The field-data type holds all information that pertains to a particular field (or particle) within a particular model. Information such as spin type, particle code etc. is stored within the object itself, while mass and width are associated to parameters, otherwise assumed zero.

```

<Model data: public>+≡
    public :: field_data_t

<Model data: types>+≡
    type :: field_data_t
        private
        type(string_t) :: longname
        integer :: pdg = UNDEFINED
        logical :: visible = .true.
        logical :: parton = .false.
        logical :: gauge = .false.
        logical :: left_handed = .false.
        logical :: right_handed = .false.
        logical :: has_anti = .false.
        logical :: p_is_stable = .true.
        logical :: p_decays_isotropically = .false.
        logical :: p_decays_diagonal = .false.
        logical :: p_has_decay_helicity = .false.
        integer :: p_decay_helicity = 0
        logical :: a_is_stable = .true.
        logical :: a_decays_isotropically = .false.
        logical :: a_decays_diagonal = .false.
        logical :: a_has_decay_helicity = .false.
        integer :: a_decay_helicity = 0
        logical :: p_polarized = .false.
        logical :: a_polarized = .false.
        type(string_t), dimension(:), allocatable :: name, anti

```

```

type(string_t) :: tex_name, tex_anti
integer :: spin_type = UNDEFINED
integer :: isospin_type = 1
integer :: charge_type = 1
integer :: color_type = 1
real(default), pointer :: mass_val => null ()
class(modelpar_data_t), pointer :: mass_data => null ()
real(default), pointer :: width_val => null ()
class(modelpar_data_t), pointer :: width_data => null ()
integer :: multiplicity = 1
type(string_t), dimension(:), allocatable :: p_decay
type(string_t), dimension(:), allocatable :: a_decay
contains
  <Model data: field data: TBP>
end type field_data_t

```

Initialize field data with PDG long name and PDG code. T_EX names should be initialized to avoid issues with accessing unallocated string contents.

```

<Model data: field data: TBP>≡
  procedure :: init => field_data_init

<Model data: procedures>+≡
  subroutine field_data_init (prt, longname, pdg)
    class(field_data_t), intent(out) :: prt
    type(string_t), intent(in) :: longname
    integer, intent(in) :: pdg
    prt%longname = longname
    prt%pdg = pdg
    prt%tex_name = ""
    prt%tex_anti = ""
  end subroutine field_data_init

```

Copy quantum numbers from another particle. Do not compute the multiplicity yet, because this depends on the association of the `mass_data` pointer.

```

<Model data: field data: TBP>+≡
  procedure :: copy_from => field_data_copy_from

<Model data: procedures>+≡
  subroutine field_data_copy_from (prt, prt_src)
    class(field_data_t), intent(inout) :: prt
    class(field_data_t), intent(in) :: prt_src
    prt%visible = prt_src%visible
    prt%parton = prt_src%parton
    prt%gauge = prt_src%gauge
    prt%left_handed = prt_src%left_handed
    prt%right_handed = prt_src%right_handed
    prt%p_is_stable = prt_src%p_is_stable
    prt%p_decays_isotropically = prt_src%p_decays_isotropically
    prt%p_decays_diagonal = prt_src%p_decays_diagonal
    prt%p_has_decay_helicity = prt_src%p_has_decay_helicity
    prt%p_decay_helicity = prt_src%p_decay_helicity
    prt%p_decays_diagonal = prt_src%p_decays_diagonal
    prt%a_is_stable = prt_src%a_is_stable
    prt%a_decays_isotropically = prt_src%a_decays_isotropically

```

```

prt%a_decays_diagonal = prt_src%a_decays_diagonal
prt%a_has_decay_helicity = prt_src%a_has_decay_helicity
prt%a_decay_helicity = prt_src%a_decay_helicity
prt%p_polarized = prt_src%p_polarized
prt%a_polarized = prt_src%a_polarized
prt%spin_type = prt_src%spin_type
prt%isospin_type = prt_src%isospin_type
prt%charge_type = prt_src%charge_type
prt%color_type = prt_src%color_type
prt%has_anti = prt_src%has_anti
if (allocated (prt_src%name)) then
  if (allocated (prt%name)) deallocate (prt%name)
  allocate (prt%name (size (prt_src%name)), source = prt_src%name)
end if
if (allocated (prt_src%anti)) then
  if (allocated (prt%anti)) deallocate (prt%anti)
  allocate (prt%anti (size (prt_src%anti)), source = prt_src%anti)
end if
prt%tex_name = prt_src%tex_name
prt%tex_anti = prt_src%tex_anti
if (allocated (prt_src%p_decay)) then
  if (allocated (prt%p_decay)) deallocate (prt%p_decay)
  allocate (prt%p_decay (size (prt_src%p_decay)), source = prt_src%p_decay)
end if
if (allocated (prt_src%a_decay)) then
  if (allocated (prt%a_decay)) deallocate (prt%a_decay)
  allocate (prt%a_decay (size (prt_src%a_decay)), source = prt_src%a_decay)
end if
end subroutine field_data_copy_from

```

Set particle quantum numbers.

(Model data: field data: TBP)+≡

```
procedure :: set => field_data_set
```

(Model data: procedures)+≡

```

subroutine field_data_set (prt, &
  is_visible, is_parton, is_gauge, is_left_handed, is_right_handed, &
  p_is_stable, p_decays_isotropically, p_decays_diagonal, &
  p_decay_helicity, &
  a_is_stable, a_decays_isotropically, a_decays_diagonal, &
  a_decay_helicity, &
  p_polarized, a_polarized, &
  name, anti, tex_name, tex_anti, &
  spin_type, isospin_type, charge_type, color_type, &
  mass_data, width_data, &
  p_decay, a_decay)
class(field_data_t), intent(inout) :: prt
logical, intent(in), optional :: is_visible, is_parton, is_gauge
logical, intent(in), optional :: is_left_handed, is_right_handed
logical, intent(in), optional :: p_is_stable
logical, intent(in), optional :: p_decays_isotropically, p_decays_diagonal
integer, intent(in), optional :: p_decay_helicity
logical, intent(in), optional :: a_is_stable
logical, intent(in), optional :: a_decays_isotropically, a_decays_diagonal

```

```

integer, intent(in), optional :: a_decay_helicity
logical, intent(in), optional :: p_polarized, a_polarized
type(string_t), dimension(:), intent(in), optional :: name, anti
type(string_t), intent(in), optional :: tex_name, tex_anti
integer, intent(in), optional :: spin_type, isospin_type
integer, intent(in), optional :: charge_type, color_type
class(modelpar_data_t), intent(in), pointer, optional :: mass_data, width_data
type(string_t), dimension(:), intent(in), optional :: p_decay, a_decay
if (present (is_visible)) prt%visible = is_visible
if (present (is_parton)) prt%parton = is_parton
if (present (is_gauge)) prt%gauge = is_gauge
if (present (is_left_handed)) prt%left_handed = is_left_handed
if (present (is_right_handed)) prt%right_handed = is_right_handed
if (present (p_is_stable)) prt%p_is_stable = p_is_stable
if (present (p_decays_isotropically)) &
    prt%p_decays_isotropically = p_decays_isotropically
if (present (p_decays_diagonal)) &
    prt%p_decays_diagonal = p_decays_diagonal
if (present (p_decay_helicity)) then
    prt%p_has_decay_helicity = .true.
    prt%p_decay_helicity = p_decay_helicity
end if
if (present (a_is_stable)) prt%a_is_stable = a_is_stable
if (present (a_decays_isotropically)) &
    prt%a_decays_isotropically = a_decays_isotropically
if (present (a_decays_diagonal)) &
    prt%a_decays_diagonal = a_decays_diagonal
if (present (a_decay_helicity)) then
    prt%a_has_decay_helicity = .true.
    prt%a_decay_helicity = a_decay_helicity
end if
if (present (p_polarized)) prt%p_polarized = p_polarized
if (present (a_polarized)) prt%a_polarized = a_polarized
if (present (name)) then
    if (allocated (prt%name)) deallocate (prt%name)
    allocate (prt%name (size (name)), source = name)
end if
if (present (anti)) then
    if (allocated (prt%anti)) deallocate (prt%anti)
    allocate (prt%anti (size (anti)), source = anti)
    prt%has_anti = .true.
end if
if (present (tex_name)) prt%tex_name = tex_name
if (present (tex_anti)) prt%tex_anti = tex_anti
if (present (spin_type)) prt%spin_type = spin_type
if (present (isospin_type)) prt%isospin_type = isospin_type
if (present (charge_type)) prt%charge_type = charge_type
if (present (color_type)) prt%color_type = color_type
if (present (mass_data)) then
    prt%mass_data => mass_data
    if (associated (mass_data)) then
        prt%mass_val => mass_data%get_real_ptr ()
    else
        prt%mass_val => null ()
    end if
end if

```

```

        end if
    end if
    if (present (width_data)) then
        prt%width_data => width_data
        if (associated (width_data)) then
            prt%width_val => width_data%get_real_ptr ()
        else
            prt%width_val => null ()
        end if
    end if
    if (present (spin_type) .or. present (mass_data)) then
        call prt%set_multiplicity ()
    end if
    if (present (p_decay)) then
        if (allocated (prt%p_decay)) deallocate (prt%p_decay)
        if (size (p_decay) > 0) &
            allocate (prt%p_decay (size (p_decay)), source = p_decay)
    end if
    if (present (a_decay)) then
        if (allocated (prt%a_decay)) deallocate (prt%a_decay)
        if (size (a_decay) > 0) &
            allocate (prt%a_decay (size (a_decay)), source = a_decay)
    end if
end subroutine field_data_set

```

Calculate the multiplicity given spin type and mass.

```

<Model data: field data: TBP>+≡
    procedure, private :: &
        set_multiplicity => field_data_set_multiplicity

<Model data: procedures>+≡
    subroutine field_data_set_multiplicity (prt)
        class(field_data_t), intent(inout) :: prt
        if (prt%spin_type /= SCALAR) then
            if (associated (prt%mass_data)) then
                prt%multiplicity = prt%spin_type
            else if (prt%left_handed .or. prt%right_handed) then
                prt%multiplicity = 1
            else
                prt%multiplicity = 2
            end if
        end if
    end subroutine field_data_set_multiplicity

```

Set the mass/width value (not the pointer). The mass/width pointer must be allocated.

```

<Model data: field data: TBP>+≡
    procedure, private :: set_mass => field_data_set_mass
    procedure, private :: set_width => field_data_set_width

<Model data: procedures>+≡
    subroutine field_data_set_mass (prt, mass)
        class(field_data_t), intent(inout) :: prt
        real(default), intent(in) :: mass

```

```

        if (associated (prt%mass_val)) prt%mass_val = mass
    end subroutine field_data_set_mass

subroutine field_data_set_width (prt, width)
    class(field_data_t), intent(inout) :: prt
    real(default), intent(in) :: width
    if (associated (prt%width_val)) prt%width_val = width
end subroutine field_data_set_width

```

Loose ends: name arrays should be allocated.

```

<Model data: field data: TBP>+≡
    procedure :: freeze => field_data_freeze

<Model data: procedures>+≡
    elemental subroutine field_data_freeze (prt)
        class(field_data_t), intent(inout) :: prt
        if (.not. allocated (prt%name)) allocate (prt%name (0))
        if (.not. allocated (prt%anti)) allocate (prt%anti (0))
    end subroutine field_data_freeze

```

Output

```

<Model data: field data: TBP>+≡
    procedure :: write => field_data_write

<Model data: procedures>+≡
    subroutine field_data_write (prt, unit)
        class(field_data_t), intent(in) :: prt
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(3x,A,1x,A)", advance="no") "particle", char (prt%longname)
        write (u, "(1x,I0)", advance="no") prt%pdg
        if (.not. prt%visible) write (u, "(2x,A)", advance="no") "invisible"
        if (prt%parton) write (u, "(2x,A)", advance="no") "parton"
        if (prt%gauge) write (u, "(2x,A)", advance="no") "gauge"
        if (prt%left_handed) write (u, "(2x,A)", advance="no") "left"
        if (prt%right_handed) write (u, "(2x,A)", advance="no") "right"
        write (u, *)
        write (u, "(5x,A)", advance="no") "name"
        if (allocated (prt%name)) then
            do i = 1, size (prt%name)
                write (u, "(1x,A)", advance="no") ' ' // char (prt%name(i)) // ' '
            end do
            write (u, *)
            if (prt%has_anti) then
                write (u, "(5x,A)", advance="no") "anti"
                do i = 1, size (prt%anti)
                    write (u, "(1x,A)", advance="no") ' ' // char (prt%anti(i)) // ' '
                end do
                write (u, *)
            end if
            if (prt%tex_name /= "") then
                write (u, "(5x,A)") &
                    "tex_name " // ' ' // char (prt%tex_name) // ' '
            end if
        end if
    end subroutine field_data_write

```

```

        end if
        if (prt%has_anti .and. prt%tex_anti /= "") then
            write (u, "(5x,A)") &
                "tex_anti " // ' ' // char (prt%tex_anti) // ' '
        end if
    else
        write (u, "(A)") "???"
    end if
    write (u, "(5x,A)", advance="no") "spin "
    select case (mod (prt%spin_type - 1, 2))
    case (0); write (u, "(I0)", advance="no") (prt%spin_type-1) / 2
    case default; write (u, "(I0,A)", advance="no") prt%spin_type-1, "/2"
    end select
    ! write (u, "(2x,A,I1,A)") "! [multiplicity = ", prt%multiplicity, "]"
    if (abs (prt%isospin_type) /= 1) then
        write (u, "(2x,A)", advance="no") "isospin "
        select case (mod (abs (prt%isospin_type) - 1, 2))
        case (0); write (u, "(I0)", advance="no") &
            sign (abs (prt%isospin_type) - 1, prt%isospin_type) / 2
        case default; write (u, "(I0,A)", advance="no") &
            sign (abs (prt%isospin_type) - 1, prt%isospin_type), "/2"
        end select
    end if
    if (abs (prt%charge_type) /= 1) then
        write (u, "(2x,A)", advance="no") "charge "
        select case (mod (abs (prt%charge_type) - 1, 3))
        case (0); write (u, "(I0)", advance="no") &
            sign (abs (prt%charge_type) - 1, prt%charge_type) / 3
        case default; write (u, "(I0,A)", advance="no") &
            sign (abs (prt%charge_type) - 1, prt%charge_type), "/3"
        end select
    end if
    if (prt%color_type /= 1) then
        write (u, "(2x,A,I0)", advance="no") "color ", prt%color_type
    end if
    write (u, *)
    if (associated (prt%mass_data)) then
        write (u, "(5x,A)", advance="no") &
            "mass " // char (prt%mass_data%get_name ())
        if (associated (prt%width_data)) then
            write (u, "(2x,A)") &
                "width " // char (prt%width_data%get_name ())
        else
            write (u, *)
        end if
    end if
    call prt%write_decays (u)
end subroutine field_data_write

```

Write decay and polarization data.

<Model data: field data: TBP>+≡

procedure :: write_decays => field_data_write_decays

<Model data: procedures>+≡

```

subroutine field_data_write_decays (prt, unit)
  class(field_data_t), intent(in) :: prt
  integer, intent(in), optional :: unit
  integer :: u, i
  u = given_output_unit (unit)
  if (.not. prt%p_is_stable) then
    if (allocated (prt%p_decay)) then
      write (u, "(5x,A)", advance="no") "p_decay"
      do i = 1, size (prt%p_decay)
        write (u, "(1x,A)", advance="no") char (prt%p_decay(i))
      end do
      if (prt%p_decays_isotropically) then
        write (u, "(1x,A)", advance="no") "isotropic"
      else if (prt%p_decays_diagonal) then
        write (u, "(1x,A)", advance="no") "diagonal"
      else if (prt%p_has_decay_helicity) then
        write (u, "(1x,A,I0)", advance="no") "helicity = ", &
          prt%p_decay_helicity
      end if
      write (u, *)
    end if
  else if (prt%p_polarized) then
    write (u, "(5x,A)") "p_polarized"
  end if
  if (.not. prt%a_is_stable) then
    if (allocated (prt%a_decay)) then
      write (u, "(5x,A)", advance="no") "a_decay"
      do i = 1, size (prt%a_decay)
        write (u, "(1x,A)", advance="no") char (prt%a_decay(i))
      end do
      if (prt%a_decays_isotropically) then
        write (u, "(1x,A)", advance="no") "isotropic"
      else if (prt%a_decays_diagonal) then
        write (u, "(1x,A)", advance="no") "diagonal"
      else if (prt%a_has_decay_helicity) then
        write (u, "(1x,A,I0)", advance="no") "helicity = ", &
          prt%a_decay_helicity
      end if
      write (u, *)
    end if
  else if (prt%a_polarized) then
    write (u, "(5x,A)") "a_polarized"
  end if
end subroutine field_data_write_decays

```

Screen version of output.

```

<Model data: field data: TBP>+≡
  procedure :: show => field_data_show

<Model data: procedures>+≡
  subroutine field_data_show (prt, l, u)
    class(field_data_t), intent(in) :: prt
    integer, intent(in) :: l, u
    character(len=l) :: buffer

```



```

integer :: i
type(string_t), dimension(:), allocatable :: decay
buffer = prt%get_name (.false.)
write (u, "(4x,A,1x,I8)", advance="no") buffer, &
    prt%get_pdg ()
if (prt%is_polarized ()) then
    write (u, "(3x,A)") "polarized"
else if (.not. prt%is_stable ()) then
    write (u, "(3x,A)", advance="no") "decays:"
    call prt%get_decays (decay)
    do i = 1, size (decay)
        write (u, "(1x,A)", advance="no") char (decay(i))
    end do
    write (u, *)
else
    write (u, *)
end if
if (prt%has_antiparticle ()) then
    buffer = prt%get_name (.true.)
    write (u, "(4x,A,1x,I8)", advance="no") buffer, &
        prt%get_pdg_anti ()
    if (prt%is_polarized (.true.)) then
        write (u, "(3x,A)") "polarized"
    else if (.not. prt%is_stable (.true.)) then
        write (u, "(3x,A)", advance="no") "decays:"
        call prt%get_decays (decay, .true.)
        do i = 1, size (decay)
            write (u, "(1x,A)", advance="no") char (decay(i))
        end do
        write (u, *)
    else
        write (u, *)
    end if
end if
end subroutine field_data_show

```

Retrieve data:

(Model data: field data: TBP)+≡

```

procedure :: get_pdg => field_data_get_pdg
procedure :: get_pdg_anti => field_data_get_pdg_anti

```

(Model data: procedures)+≡

```

elemental function field_data_get_pdg (prt) result (pdg)
    integer :: pdg
    class(field_data_t), intent(in) :: prt
    pdg = prt%pdg
end function field_data_get_pdg

elemental function field_data_get_pdg_anti (prt) result (pdg)
    integer :: pdg
    class(field_data_t), intent(in) :: prt
    if (prt%has_anti) then
        pdg = - prt%pdg
    else

```

```

        pdg = prt%pdg
    end if
end function field_data_get_pdg_anti

```

Predicates:

(Model data: field data: TBP)+≡

```

procedure :: is_visible => field_data_is_visible
procedure :: is_parton => field_data_is_parton
procedure :: is_gauge => field_data_is_gauge
procedure :: is_left_handed => field_data_is_left_handed
procedure :: is_right_handed => field_data_is_right_handed
procedure :: has_antiparticle => field_data_has_antiparticle
procedure :: is_stable => field_data_is_stable
procedure :: get_decays => field_data_get_decays
procedure :: decays_isotropically => field_data_decays_isotropically
procedure :: decays_diagonal => field_data_decays_diagonal
procedure :: has_decay_helicity => field_data_has_decay_helicity
procedure :: decay_helicity => field_data_decay_helicity
procedure :: is_polarized => field_data_is_polarized

```

(Model data: procedures)+≡

```

elemental function field_data_is_visible (prt) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    flag = prt%visible
end function field_data_is_visible

elemental function field_data_is_parton (prt) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    flag = prt%parton
end function field_data_is_parton

elemental function field_data_is_gauge (prt) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    flag = prt%gauge
end function field_data_is_gauge

elemental function field_data_is_left_handed (prt) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    flag = prt%left_handed
end function field_data_is_left_handed

elemental function field_data_is_right_handed (prt) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    flag = prt%right_handed
end function field_data_is_right_handed

elemental function field_data_has_antiparticle (prt) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt

```

```

    flag = prt%has_anti
end function field_data_has_antiparticle

elemental function field_data_is_stable (prt, anti) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    logical, intent(in), optional :: anti
    if (present (anti)) then
        if (anti) then
            flag = prt%a_is_stable
        else
            flag = prt%p_is_stable
        end if
    else
        flag = prt%p_is_stable
    end if
end function field_data_is_stable

subroutine field_data_get_decays (prt, decay, anti)
    class(field_data_t), intent(in) :: prt
    type(string_t), dimension(:), intent(out), allocatable :: decay
    logical, intent(in), optional :: anti
    if (present (anti)) then
        if (anti) then
            allocate (decay (size (prt%a_decay)), source = prt%a_decay)
        else
            allocate (decay (size (prt%p_decay)), source = prt%p_decay)
        end if
    else
        allocate (decay (size (prt%p_decay)), source = prt%p_decay)
    end if
end subroutine field_data_get_decays

elemental function field_data_decays_isotropically &
    (prt, anti) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    logical, intent(in), optional :: anti
    if (present (anti)) then
        if (anti) then
            flag = prt%a_decays_isotropically
        else
            flag = prt%p_decays_isotropically
        end if
    else
        flag = prt%p_decays_isotropically
    end if
end function field_data_decays_isotropically

elemental function field_data_decays_diagonal &
    (prt, anti) result (flag)
    logical :: flag
    class(field_data_t), intent(in) :: prt
    logical, intent(in), optional :: anti

```

```

if (present (anti)) then
  if (anti) then
    flag = prt%a_decays_diagonal
  else
    flag = prt%p_decays_diagonal
  end if
else
  flag = prt%p_decays_diagonal
end if
end function field_data_decays_diagonal

elemental function field_data_has_decay_helicity &
  (prt, anti) result (flag)
  logical :: flag
  class(field_data_t), intent(in) :: prt
  logical, intent(in), optional :: anti
  if (present (anti)) then
    if (anti) then
      flag = prt%a_has_decay_helicity
    else
      flag = prt%p_has_decay_helicity
    end if
  else
    flag = prt%p_has_decay_helicity
  end if
end function field_data_has_decay_helicity

elemental function field_data_decay_helicity &
  (prt, anti) result (hel)
  integer :: hel
  class(field_data_t), intent(in) :: prt
  logical, intent(in), optional :: anti
  if (present (anti)) then
    if (anti) then
      hel = prt%a_decay_helicity
    else
      hel = prt%p_decay_helicity
    end if
  else
    hel = prt%p_decay_helicity
  end if
end function field_data_decay_helicity

elemental function field_data_is_polarized (prt, anti) result (flag)
  logical :: flag
  class(field_data_t), intent(in) :: prt
  logical, intent(in), optional :: anti
  logical :: a
  if (present (anti)) then
    a = anti
  else
    a = .false.
  end if
  if (a) then

```

```

        flag = prt%a_polarized
    else
        flag = prt%p_polarized
    end if
end function field_data_is_polarized

```

Names. Return the first name in the list (or the first antiparticle name)

```

<Model data: field data: TBP>+≡
    procedure :: get_longname => field_data_get_longname
    procedure :: get_name => field_data_get_name
    procedure :: get_name_array => field_data_get_name_array

<Model data: procedures>+≡
    pure function field_data_get_longname (prt) result (name)
        type(string_t) :: name
        class(field_data_t), intent(in) :: prt
        name = prt%longname
    end function field_data_get_longname

    pure function field_data_get_name (prt, is_antiparticle) result (name)
        type(string_t) :: name
        class(field_data_t), intent(in) :: prt
        logical, intent(in) :: is_antiparticle
        name = prt%longname
        if (is_antiparticle) then
            if (prt%has_anti) then
                if (allocated (prt%anti)) then
                    if (size(prt%anti) > 0) name = prt%anti(1)
                end if
            else
                if (allocated (prt%name)) then
                    if (size (prt%name) > 0) name = prt%name(1)
                end if
            end if
        else
            if (allocated (prt%name)) then
                if (size (prt%name) > 0) name = prt%name(1)
            end if
        end if
    end function field_data_get_name

    subroutine field_data_get_name_array (prt, is_antiparticle, name)
        class(field_data_t), intent(in) :: prt
        logical, intent(in) :: is_antiparticle
        type(string_t), dimension(:), allocatable, intent(inout) :: name
        if (allocated (name)) deallocate (name)
        if (is_antiparticle) then
            if (prt%has_anti) then
                allocate (name (size (prt%anti)))
                name = prt%anti
            else
                allocate (name (0))
            end if
        else

```

```

        allocate (name (size (prt%name)))
        name = prt%name
    end if
end subroutine field_data_get_name_array

```

Same for the T_EX name.

```

<Model data: field data: TBP>+≡
    procedure :: get_tex_name => field_data_get_tex_name

<Model data: procedures>+≡
    elemental function field_data_get_tex_name &
        (prt, is_antiparticle) result (name)
        type(string_t) :: name
        class(field_data_t), intent(in) :: prt
        logical, intent(in) :: is_antiparticle
        if (is_antiparticle) then
            if (prt%has_anti) then
                name = prt%tex_anti
            else
                name = prt%tex_name
            end if
        else
            name = prt%tex_name
        end if
        if (name == "") name = prt%get_name (is_antiparticle)
    end function field_data_get_tex_name

```

Check if any of the field names matches the given string.

```

<Model data: field data: TBP>+≡
    procedure, private :: matches_name => field_data_matches_name

<Model data: procedures>+≡
    function field_data_matches_name (field, name, is_antiparticle) result (flag)
        class(field_data_t), intent(in) :: field
        type(string_t), intent(in) :: name
        logical, intent(in) :: is_antiparticle
        logical :: flag
        if (is_antiparticle) then
            if (field%has_anti) then
                flag = any (name == field%anti)
            else
                flag = .false.
            end if
        else
            flag = name == field%longname .or. any (name == field%name)
        end if
    end function field_data_matches_name

```

Quantum numbers

```

<Model data: field data: TBP>+≡
    procedure :: get_spin_type => field_data_get_spin_type
    procedure :: get_multiplicity => field_data_get_multiplicity
    procedure :: get_isospin_type => field_data_get_isospin_type

```

```

procedure :: get_charge_type => field_data_get_charge_type
procedure :: get_color_type => field_data_get_color_type

<Model data: procedures>+≡
  elemental function field_data_get_spin_type (prt) result (type)
    integer :: type
    class(field_data_t), intent(in) :: prt
    type = prt%spin_type
  end function field_data_get_spin_type

  elemental function field_data_get_multiplicity (prt) result (type)
    integer :: type
    class(field_data_t), intent(in) :: prt
    type = prt%multiplicity
  end function field_data_get_multiplicity

  elemental function field_data_get_isospin_type (prt) result (type)
    integer :: type
    class(field_data_t), intent(in) :: prt
    type = prt%isospin_type
  end function field_data_get_isospin_type

  elemental function field_data_get_charge_type (prt) result (type)
    integer :: type
    class(field_data_t), intent(in) :: prt
    type = prt%charge_type
  end function field_data_get_charge_type

  elemental function field_data_get_color_type (prt) result (type)
    integer :: type
    class(field_data_t), intent(in) :: prt
    type = prt%color_type
  end function field_data_get_color_type

```

In the MSSM, neutralinos can have a negative mass. This is relevant for computing matrix elements. However, within the WHIZARD main program we are interested only in kinematics, therefore we return the absolute value of the particle mass. If desired, we can extract the sign separately.

```

<Model data: field data: TBP>+≡
  procedure :: get_charge => field_data_get_charge
  procedure :: get_isospin => field_data_get_isospin
  procedure :: get_mass => field_data_get_mass
  procedure :: get_mass_sign => field_data_get_mass_sign
  procedure :: get_width => field_data_get_width

  <Model data: procedures>+≡
    elemental function field_data_get_charge (prt) result (charge)
      real(default) :: charge
      class(field_data_t), intent(in) :: prt
      if (prt%charge_type /= 0) then
        charge = real (sign ((abs(prt%charge_type) - 1), &
          prt%charge_type), default) / 3
      else
        charge = 0
      end if
    end function field_data_get_charge

```

```

        end if
    end function field_data_get_charge

    elemental function field_data_get_isospin (prt) result (isospin)
        real(default) :: isospin
        class(field_data_t), intent(in) :: prt
        if (prt%isospin_type /= 0) then
            isospin = real (sign (abs(prt%isospin_type) - 1, &
                prt%isospin_type), default) / 2
        else
            isospin = 0
        end if
    end function field_data_get_isospin

    elemental function field_data_get_mass (prt) result (mass)
        real(default) :: mass
        class(field_data_t), intent(in) :: prt
        if (associated (prt%mass_val)) then
            mass = abs (prt%mass_val)
        else
            mass = 0
        end if
    end function field_data_get_mass

    elemental function field_data_get_mass_sign (prt) result (sgn)
        integer :: sgn
        class(field_data_t), intent(in) :: prt
        if (associated (prt%mass_val)) then
            sgn = sign (1._default, prt%mass_val)
        else
            sgn = 0
        end if
    end function field_data_get_mass_sign

    elemental function field_data_get_width (prt) result (width)
        real(default) :: width
        class(field_data_t), intent(in) :: prt
        if (associated (prt%width_val)) then
            width = prt%width_val
        else
            width = 0
        end if
    end function field_data_get_width

```

Find the model containing the PDG given two model files.

```

<Model data: public>+≡
    public :: find_model

<Model data: procedures>+≡
    subroutine find_model (model, PDG, model_A, model_B)
        class(model_data_t), pointer, intent(out) :: model
        integer, intent(in) :: PDG
        class(model_data_t), intent(in), target :: model_A, model_B
        character(len=5) :: buffer

```



```

if (model_A%test_field (PDG)) then
  model => model_A
else if (model_B%test_field (PDG)) then
  model => model_B
else
  write (buffer, "(I5)") PDG
  call msg_fatal ("Parton " // buffer // &
    " not found in the given model files")
end if
end subroutine find_model

```

10.1.3 Vertex data

The vertex object contains an array of particle-data pointers, for which we need a separate type. (We could use the flavor type defined in another module.)

The program does not (yet?) make use of vertex definitions, so they are not stored here.

```

<Model data: types>+≡
  type :: field_data_p
    type(field_data_t), pointer :: p => null ()
  end type field_data_p

<Model data: types>+≡
  type :: vertex_t
    private
    logical :: trilinear
    integer, dimension(:), allocatable :: pdg
    type(field_data_p), dimension(:), allocatable :: prt
  contains
    <Model data: vertex: TBP>
  end type vertex_t

<Model data: vertex: TBP>≡
  procedure :: write => vertex_write

<Model data: procedures>+≡
  subroutine vertex_write (vtx, unit)
    class(vertex_t), intent(in) :: vtx
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(3x,A)", advance="no") "vertex"
    do i = 1, size (vtx%prt)
      if (associated (vtx%prt(i)%p)) then
        write (u, "(1x,A)", advance="no") &
          ''' // char (vtx%prt(i)%p%get_name (vtx%pdg(i) < 0)) &
          // '''
      else
        write (u, "(1x,I7)", advance="no") vtx%pdg(i)
      end if
    end do
    write (u, *)

```

```
end subroutine vertex_write
```

Initialize using PDG codes. The model is used for finding particle data pointers associated with the pdg codes.

```
<Model data: vertex: TBP>+≡
  procedure :: init => vertex_init

<Model data: procedures>+≡
  subroutine vertex_init (vtx, pdg, model)
    class(vertex_t), intent(out) :: vtx
    integer, dimension(:), intent(in) :: pdg
    type(model_data_t), intent(in), target, optional :: model
    integer :: i
    allocate (vtx%pdg (size (pdg)))
    allocate (vtx%prt (size (pdg)))
    vtx%trilinear = size (pdg) == 3
    vtx%pdg = pdg
    if (present (model)) then
      do i = 1, size (pdg)
        vtx%prt(i)%p => model%get_field_ptr (pdg(i))
      end do
    end if
  end subroutine vertex_init
```

Copy vertex: we must reassign the field-data pointer to a new model.

```
<Model data: vertex: TBP>+≡
  procedure :: copy_from => vertex_copy_from

<Model data: procedures>+≡
  subroutine vertex_copy_from (vtx, old_vtx, new_model)
    class(vertex_t), intent(out) :: vtx
    class(vertex_t), intent(in) :: old_vtx
    type(model_data_t), intent(in), target, optional :: new_model
    call vtx%init (old_vtx%pdg, new_model)
  end subroutine vertex_copy_from
```

Single-particle lookup: Given a particle code, we return matching codes if present, otherwise zero. Actually, we return the antiparticles of the matching codes, as appropriate for computing splittings.

```
<Model data: vertex: TBP>+≡
  procedure :: get_match => vertex_get_match

<Model data: procedures>+≡
  subroutine vertex_get_match (vtx, pdg1, pdg2)
    class(vertex_t), intent(in) :: vtx
    integer, intent(in) :: pdg1
    integer, dimension(:), allocatable, intent(out) :: pdg2
    integer :: i, j
    do i = 1, size (vtx%pdg)
      if (vtx%pdg(i) == pdg1) then
        allocate (pdg2 (size (vtx%pdg) - 1))
        do j = 1, i-1
          pdg2(j) = anti (j)
        end do
      end if
    end do
```

```

        end do
        do j = i, size (pdg2)
            pdg2(j) = anti (j+1)
        end do
        exit
    end if
end do
contains
function anti (i) result (pdg)
    integer, intent(in) :: i
    integer :: pdg
    if (vtx%prt(i)%p%has_antiparticle ()) then
        pdg = - vtx%pdg(i)
    else
        pdg = vtx%pdg(i)
    end if
end function anti
end subroutine vertex_get_match

```

To access this from the outside, we create an iterator. The iterator has the sole purpose of returning the matching particles for a given array of PDG codes.

```

<Model data: public>+≡
    public :: vertex_iterator_t

<Model data: types>+≡
    type :: vertex_iterator_t
        private
        class(model_data_t), pointer :: model => null ()
        integer, dimension(:), allocatable :: pdg
        integer :: vertex_index = 0
    contains
        procedure :: init => vertex_iterator_init
        procedure :: get_next_match => vertex_iterator_get_next_match
    end type vertex_iterator_t

```

We initialize the iterator for a particular model with the `pdg` index of the particle we are looking at.

```

<Model data: procedures>+≡
    subroutine vertex_iterator_init (it, model, pdg)
        class(vertex_iterator_t), intent(out) :: it
        class(model_data_t), intent(in), target :: model
        integer, dimension(:), intent(in) :: pdg
        it%model => model
        allocate (it%pdg (size (pdg)), source = pdg)
    end subroutine vertex_iterator_init

    subroutine vertex_iterator_get_next_match (it, pdg_match)
        class(vertex_iterator_t), intent(inout) :: it
        integer, dimension(:), allocatable, intent(out) :: pdg_match
        integer :: i, j
        do i = it%vertex_index + 1, size (it%model%vtx)
            do j = 1, size (it%pdg)
                call vertex_get_match (it%model%vtx(i), it%pdg(j), pdg_match)
            end do
        end do
    end subroutine vertex_iterator_get_next_match

```

```

        if (allocated (pdg_match)) then
            it%vertex_index = i
            return
        end if
    end do
end do
it%vertex_index = 0
end subroutine vertex_iterator_get_next_match

```

10.1.4 Vertex lookup table

The vertex lookup table is a hash table: given two particle codes, we check which codes are allowed for the third one.

The size of the hash table should be large enough that collisions are rare. We first select a size based on the number of vertices (multiplied by six because all permutations count), with some margin, and then choose the smallest integer power of two larger than this.

```

<Model data: parameters>≡
    integer, parameter :: VERTEX_TABLE_SCALE_FACTOR = 60

<Model data: procedures>+≡
    function vertex_table_size (n_vtx) result (n)
        integer(i32) :: n
        integer, intent(in) :: n_vtx
        integer :: i, s
        s = VERTEX_TABLE_SCALE_FACTOR * n_vtx
        n = 1
        do i = 1, 31
            n = ishft (n, 1)
            s = ishft (s,-1)
            if (s == 0) exit
        end do
    end function vertex_table_size

```

The specific hash function takes two particle codes (arbitrary integers) and returns a 32-bit integer. It makes use of the universal function `hash` which operates on a byte array.

```

<Model data: procedures>+≡
    function hash2 (pdg1, pdg2)
        integer(i32) :: hash2
        integer, intent(in) :: pdg1, pdg2
        integer(i8), dimension(1) :: mold
        hash2 = hash (transfer ([pdg1, pdg2], mold))
    end function hash2

```

Each entry in the vertex table stores the two particle codes and an array of possibilities for the third code.

```

<Model data: types>+≡
    type :: vertex_table_entry_t
    private
        integer :: pdg1 = 0, pdg2 = 0

```

```

        integer :: n = 0
        integer, dimension(:), allocatable :: pdg3
    end type vertex_table_entry_t

```

The vertex table:

```

<Model data: types>+≡
    type :: vertex_table_t
        type(vertex_table_entry_t), dimension(:), allocatable :: entry
        integer :: n_collisions = 0
        integer(i32) :: mask
    contains
        <Model data: vertex table: TBP>
    end type vertex_table_t

```

Output.

```

<Model data: vertex table: TBP>≡
    procedure :: write => vertex_table_write

<Model data: procedures>+≡
    subroutine vertex_table_write (vt, unit)
        class(vertex_table_t), intent(in) :: vt
        integer, intent(in), optional :: unit
        integer :: u, i
        character(9) :: size_pdg3
        u = given_output_unit (unit)
        write (u, "(A)") "vertex hash table:"
        write (u, "(A,I7)") " size = ", size (vt%entry)
        write (u, "(A,I7)") " used = ", count (vt%entry%  
n /= 0)
        write (u, "(A,I7)") " coll = ", vt%  
n_collisions
        do i = lbound (vt%entry, 1), ubound (vt%entry, 1)
            if (vt%entry(i)%  
n /= 0) then
                write (size_pdg3, "(I7)") size (vt%entry(i)%  
pdg3)
                write (u, "(A,1x,I7,1x,A,2(1x,I7),A," // &
                    size_pdg3 // "(1x,I7))") &
                    " ", i, ":", vt%entry(i)%  
pdg1, &
                    vt%entry(i)%  
pdg2, "->", vt%entry(i)%  
pdg3
            end if
        end do
    end subroutine vertex_table_write

```

Initializing the vertex table: This is done in two passes. First, we scan all permutations for all vertices and count the number of entries in each bucket of the hashtable. Then, the buckets are allocated accordingly and filled.

Collision resolution is done by just incrementing the hash value until an empty bucket is found. The vertex table size is fixed, since we know from the beginning the number of entries.

```

<Model data: vertex table: TBP>+≡
    procedure :: init => vertex_table_init

<Model data: procedures>+≡
    subroutine vertex_table_init (vt, prt, vtx)
        class(vertex_table_t), intent(out) :: vt
        type(field_data_t), dimension(:), intent(in) :: prt

```

```

type(vertex_t), dimension(:), intent(in) :: vtx
integer :: n_vtx, vt_size, i, p1, p2, p3
integer, dimension(3) :: p
n_vtx = size (vtx)
vt_size = vertex_table_size (count (vtx%trilinear))
vt%mask = vt_size - 1
allocate (vt%entry (0:vt_size-1))
do i = 1, n_vtx
  if (vtx(i)%trilinear) then
    p = vtx(i)%pdg
    p1 = p(1); p2 = p(2)
    call create (hash2 (p1, p2))
    if (p(2) /= p(3)) then
      p2 = p(3)
      call create (hash2 (p1, p2))
    end if
    if (p(1) /= p(2)) then
      p1 = p(2); p2 = p(1)
      call create (hash2 (p1, p2))
      if (p(1) /= p(3)) then
        p2 = p(3)
        call create (hash2 (p1, p2))
      end if
    end if
    if (p(1) /= p(3)) then
      p1 = p(3); p2 = p(1)
      call create (hash2 (p1, p2))
      if (p(1) /= p(2)) then
        p2 = p(2)
        call create (hash2 (p1, p2))
      end if
    end if
  end if
end do
do i = 0, vt_size - 1
  allocate (vt%entry(i)%pdg3 (vt%entry(i)%n))
end do
vt%entry%n = 0
do i = 1, n_vtx
  if (vtx(i)%trilinear) then
    p = vtx(i)%pdg
    p1 = p(1); p2 = p(2); p3 = p(3)
    call register (hash2 (p1, p2))
    if (p(2) /= p(3)) then
      p2 = p(3); p3 = p(2)
      call register (hash2 (p1, p2))
    end if
    if (p(1) /= p(2)) then
      p1 = p(2); p2 = p(1); p3 = p(3)
      call register (hash2 (p1, p2))
      if (p(1) /= p(3)) then
        p2 = p(3); p3 = p(1)
        call register (hash2 (p1, p2))
      end if
    end if
  end if
end do

```

```

        end if
        if (p(1) /= p(3)) then
            p1 = p(3); p2 = p(1); p3 = p(2)
            call register (hash2 (p1, p2))
            if (p(1) /= p(2)) then
                p2 = p(2); p3 = p(1)
                call register (hash2 (p1, p2))
            end if
        end if
    end if
end do
contains
recursive subroutine create (hashval)
    integer(i32), intent(in) :: hashval
    integer :: h
    h = iand (hashval, vt%mask)
    if (vt%entry(h)%n == 0) then
        vt%entry(h)%pdg1 = p1
        vt%entry(h)%pdg2 = p2
        vt%entry(h)%n = 1
    else if (vt%entry(h)%pdg1 == p1 .and. vt%entry(h)%pdg2 == p2) then
        vt%entry(h)%n = vt%entry(h)%n + 1
    else
        vt%n_collisions = vt%n_collisions + 1
        call create (hashval + 1)
    end if
end subroutine create
recursive subroutine register (hashval)
    integer(i32), intent(in) :: hashval
    integer :: h
    h = iand (hashval, vt%mask)
    if (vt%entry(h)%pdg1 == p1 .and. vt%entry(h)%pdg2 == p2) then
        vt%entry(h)%n = vt%entry(h)%n + 1
        vt%entry(h)%pdg3(vt%entry(h)%n) = p3
    else
        call register (hashval + 1)
    end if
end subroutine register
end subroutine vertex_table_init

```

Return the array of particle codes that match the given pair.

```

<Model data: vertex table: TBP>+≡
    procedure :: match => vertex_table_match

<Model data: procedures>+≡
    subroutine vertex_table_match (vt, pdg1, pdg2, pdg3)
        class(vertex_table_t), intent(in) :: vt
        integer, intent(in) :: pdg1, pdg2
        integer, dimension(:), allocatable, intent(out) :: pdg3
        call match (hash2 (pdg1, pdg2))
    contains
        recursive subroutine match (hashval)
            integer(i32), intent(in) :: hashval
            integer :: h

```

```

    h = iand (hashval, vt%mask)
    if (vt%entry(h)%n == 0) then
        allocate (pdg3 (0))
    else if (vt%entry(h)%pdg1 == pdg1 .and. vt%entry(h)%pdg2 == pdg2) then
        allocate (pdg3 (size (vt%entry(h)%pdg3)))
        pdg3 = vt%entry(h)%pdg3
    else
        call match (hashval + 1)
    end if
end subroutine match
end subroutine vertex_table_match

```

Return true if the triplet is represented as a vertex.

<Model data: vertex table: TBP>+≡

```

    procedure :: check => vertex_table_check

```

<Model data: procedures>+≡

```

    function vertex_table_check (vt, pdg1, pdg2, pdg3) result (flag)
        class(vertex_table_t), intent(in) :: vt
        integer, intent(in) :: pdg1, pdg2, pdg3
        logical :: flag
        flag = check (hash2 (pdg1, pdg2))
contains
    recursive function check (hashval) result (flag)
        integer(i32), intent(in) :: hashval
        integer :: h
        logical :: flag
        h = iand (hashval, vt%mask)
        if (vt%entry(h)%n == 0) then
            flag = .false.
        else if (vt%entry(h)%pdg1 == pdg1 .and. vt%entry(h)%pdg2 == pdg2) then
            flag = any (vt%entry(h)%pdg3 == pdg3)
        else
            flag = check (hashval + 1)
        end if
    end function check
end function vertex_table_check

```

10.1.5 Model Data Record

This type collects the model data as defined above.

We deliberately implement the parameter arrays as pointer arrays. We thus avoid keeping track of TARGET attributes.

<Model data: public>+≡

```

    public :: model_data_t

```

<Model data: types>+≡

```

    type :: model_data_t
    private
    type(string_t) :: name
    type(modelpar_real_t), dimension(:), pointer :: par_real => null ()
    type(modelpar_complex_t), dimension(:), pointer :: par_complex => null ()

```



```

        type(field_data_t), dimension(:), allocatable :: field
        type(vertex_t), dimension(:), allocatable :: vtx
        type(vertex_table_t) :: vt
contains
    <Model data: model data: TBP>
end type model_data_t

```

Finalizer, deallocate pointer arrays.

```

<Model data: model data: TBP>≡
    procedure :: final => model_data_final

<Model data: procedures>+≡
    subroutine model_data_final (model)
        class(model_data_t), intent(inout) :: model
        deallocate (model%par_real)
        deallocate (model%par_complex)
    end subroutine model_data_final

```

Output. The signature matches the signature of the high-level `model_write` procedure, so some of the options don't actually apply.

```

<Model data: model data: TBP>+≡
    procedure :: write => model_data_write

<Model data: procedures>+≡
    subroutine model_data_write (model, unit, verbose, &
        show_md5sum, show_variables, show_parameters, &
        show_particles, show_vertices)
        class(model_data_t), intent(in) :: model
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        logical, intent(in), optional :: show_md5sum
        logical, intent(in), optional :: show_variables
        logical, intent(in), optional :: show_parameters
        logical, intent(in), optional :: show_particles
        logical, intent(in), optional :: show_vertices
        logical :: show_par, show_prt, show_vtx
        integer :: u, i
        u = given_output_unit (unit)
        show_par = .true.; if (present (show_parameters)) &
            show_par = show_parameters
        show_prt = .true.; if (present (show_particles)) &
            show_prt = show_particles
        show_vtx = .true.; if (present (show_vertices)) &
            show_vtx = show_vertices
        if (show_par) then
            do i = 1, size (model%par_real)
                call model%par_real(i)%write (u)
                write (u, *)
            end do
            do i = 1, size (model%par_complex)
                call model%par_complex(i)%write (u)
                write (u, *)
            end do
        end if
    end subroutine model_data_write

```

```

    if (show_prt) then
        write (u, *)
        call model%write_fields (u)
    end if
    if (show_vtx) then
        write (u, *)
        call model%write_vertices (u, verbose)
    end if
end subroutine model_data_write

```

Initialize, allocating pointer arrays. The second version makes a deep copy.

```

<Model data: model data: TBP>+≡
    generic :: init => model_data_init
    procedure, private :: model_data_init

<Model data: procedures>+≡
    subroutine model_data_init (model, name, &
        n_par_real, n_par_complex, n_field, n_vtx)
        class(model_data_t), intent(out) :: model
        type(string_t), intent(in) :: name
        integer, intent(in) :: n_par_real, n_par_complex
        integer, intent(in) :: n_field
        integer, intent(in) :: n_vtx
        model%name = name
        allocate (model%par_real (n_par_real))
        allocate (model%par_complex (n_par_complex))
        allocate (model%field (n_field))
        allocate (model%vtx (n_vtx))
    end subroutine model_data_init

```

Complete model data initialization.

```

<Model data: model data: TBP>+≡
    procedure :: freeze_fields => model_data_freeze_fields

<Model data: procedures>+≡
    subroutine model_data_freeze_fields (model)
        class(model_data_t), intent(inout) :: model
        call model%field%freeze ()
    end subroutine model_data_freeze_fields

```

Deep copy. The new model should already be initialized, so we do not allocate memory.

```

<Model data: model data: TBP>+≡
    procedure :: copy_from => model_data_copy

<Model data: procedures>+≡
    subroutine model_data_copy (model, src)
        class(model_data_t), intent(inout), target :: model
        class(model_data_t), intent(in), target :: src
        class(modelpar_data_t), pointer :: data, src_data
        integer :: i
        model%par_real = src%par_real
        model%par_complex = src%par_complex

```

```

do i = 1, size (src%field)
  associate (field => model%field(i), src_field => src%field(i))
    call field%init (src_field%get_longname (), src_field%get_pdg ())
    call field%copy_from (src_field)
    src_data => src_field%mass_data
    if (associated (src_data)) then
      data => model%get_par_data_ptr (src_data%get_name ())
      call field%set (mass_data = data)
    end if
    src_data => src_field%width_data
    if (associated (src_data)) then
      data => model%get_par_data_ptr (src_data%get_name ())
      call field%set (width_data = data)
    end if
    call field%set_multiplicity ()
  end associate
end do
do i = 1, size (src%vtx)
  call model%vtx(i)%copy_from (src%vtx(i), model)
end do
call model%freeze_vertices ()
end subroutine model_data_copy

```

Return the model name.

```

<Model data: model data: TBP>+≡
  procedure :: get_name => model_data_get_name

<Model data: procedures>+≡
  function model_data_get_name (model) result (name)
    class(model_data_t), intent(in) :: model
    type(string_t) :: name
    name = model%name
  end function model_data_get_name

```

Retrieve a MD5 sum for the current model parameter values and decay/polarization settings. This is done by writing them to a temporary file, using a standard format.

```

<Model data: model data: TBP>+≡
  procedure :: get_parameters_md5sum => model_data_get_parameters_md5sum

<Model data: procedures>+≡
  function model_data_get_parameters_md5sum (model) result (par_md5sum)
    character(32) :: par_md5sum
    class(model_data_t), intent(in) :: model
    real(default), dimension(:), allocatable :: par
    type(field_data_t), pointer :: field
    integer :: unit, i
    allocate (par (model%get_n_real ()))
    call model%real_parameters_to_array (par)
    unit = free_unit ()
    open (unit, status="scratch", action="readwrite")
    write (unit, "(" // FMT_19 // ")") par
    do i = 1, model%get_n_field ()
      field => model%get_field_ptr_by_index (i)

```

```

        if (.not. field%is_stable (.false.) .or. .not. field%is_stable (.true.) &
            .or. field%is_polarized (.false.) .or. field%is_polarized (.true.))&
            then
                write (unit, "(3x,A)") char (field%get_longname ())
                call field%write_decays (unit)
            end if
        end do
        rewind (unit)
        par_md5sum = md5sum (unit)
        close (unit)
    end function model_data_get_parameters_md5sum

```

Return the MD5 sum. This is a placeholder, to be overwritten for the complete model definition.

```

<Model data: model data: TBP>+=
    procedure :: get_md5sum => model_data_get_md5sum

<Model data: procedures>+=
    function model_data_get_md5sum (model) result (md5sum)
        class(model_data_t), intent(in) :: model
        character(32) :: md5sum
        md5sum = model%get_parameters_md5sum ()
    end function model_data_get_md5sum

```

Initialize a real or complex parameter.

```

<Model data: model data: TBP>+=
    generic :: init_par => model_data_init_par_real, model_data_init_par_complex
    procedure, private :: model_data_init_par_real
    procedure, private :: model_data_init_par_complex

<Model data: procedures>+=
    subroutine model_data_init_par_real (model, i, name, value)
        class(model_data_t), intent(inout) :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: name
        real(default), intent(in) :: value
        call model%par_real(i)%init (name, value)
    end subroutine model_data_init_par_real

    subroutine model_data_init_par_complex (model, i, name, value)
        class(model_data_t), intent(inout) :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: name
        complex(default), intent(in) :: value
        call model%par_complex(i)%init (name, value)
    end subroutine model_data_init_par_complex

```

After initialization, return size of parameter array.

```

<Model data: model data: TBP>+=
    procedure :: get_n_real => model_data_get_n_real
    procedure :: get_n_complex => model_data_get_n_complex

```

```

<Model data: procedures>+=
function model_data_get_n_real (model) result (n)
  class(model_data_t), intent(in) :: model
  integer :: n
  n = size (model%par_real)
end function model_data_get_n_real

function model_data_get_n_complex (model) result (n)
  class(model_data_t), intent(in) :: model
  integer :: n
  n = size (model%par_complex)
end function model_data_get_n_complex

```

After initialization, extract the whole parameter array.

```

<Model data: model data: TBP>+=
procedure :: real_parameters_to_array &
=> model_data_real_par_to_array
procedure :: complex_parameters_to_array &
=> model_data_complex_par_to_array

<Model data: procedures>+=
subroutine model_data_real_par_to_array (model, array)
  class(model_data_t), intent(in) :: model
  real(default), dimension(:), intent(inout) :: array
  array = model%par_real%get_real ()
end subroutine model_data_real_par_to_array

subroutine model_data_complex_par_to_array (model, array)
  class(model_data_t), intent(in) :: model
  complex(default), dimension(:), intent(inout) :: array
  array = model%par_complex%get_complex ()
end subroutine model_data_complex_par_to_array

```

After initialization, set the whole parameter array.

```

<Model data: model data: TBP>+=
procedure :: real_parameters_from_array &
=> model_data_real_par_from_array
procedure :: complex_parameters_from_array &
=> model_data_complex_par_from_array

<Model data: procedures>+=
subroutine model_data_real_par_from_array (model, array)
  class(model_data_t), intent(inout) :: model
  real(default), dimension(:), intent(in) :: array
  model%par_real = array
end subroutine model_data_real_par_from_array

subroutine model_data_complex_par_from_array (model, array)
  class(model_data_t), intent(inout) :: model
  complex(default), dimension(:), intent(in) :: array
  model%par_complex = array
end subroutine model_data_complex_par_from_array

```

Analogous, for a C parameter array.

```

<Model data: model data: TBP>+=
  procedure :: real_parameters_to_c_array &
    => model_data_real_par_to_c_array

<Model data: procedures>+=
  subroutine model_data_real_par_to_c_array (model, array)
    class(model_data_t), intent(in) :: model
    real(c_default_float), dimension(:), intent(inout) :: array
    array = model%par_real%get_real ()
  end subroutine model_data_real_par_to_c_array

```

After initialization, set the whole parameter array.

```

<Model data: model data: TBP>+=
  procedure :: real_parameters_from_c_array &
    => model_data_real_par_from_c_array

<Model data: procedures>+=
  subroutine model_data_real_par_from_c_array (model, array)
    class(model_data_t), intent(inout) :: model
    real(c_default_float), dimension(:), intent(in) :: array
    model%par_real = real (array, default)
  end subroutine model_data_real_par_from_c_array

```

After initialization, get pointer to a real or complex parameter, directly by index.

```

<Model data: model data: TBP>+=
  procedure :: get_par_real_ptr => model_data_get_par_real_ptr_index
  procedure :: get_par_complex_ptr => model_data_get_par_complex_ptr_index

<Model data: procedures>+=
  function model_data_get_par_real_ptr_index (model, i) result (ptr)
    class(model_data_t), intent(inout) :: model
    integer, intent(in) :: i
    class(modelpar_data_t), pointer :: ptr
    ptr => model%par_real(i)
  end function model_data_get_par_real_ptr_index

  function model_data_get_par_complex_ptr_index (model, i) result (ptr)
    class(model_data_t), intent(inout) :: model
    integer, intent(in) :: i
    class(modelpar_data_t), pointer :: ptr
    ptr => model%par_complex(i)
  end function model_data_get_par_complex_ptr_index

```

After initialization, get pointer to a parameter by name.

```

<Model data: model data: TBP>+=
  procedure :: get_par_data_ptr => model_data_get_par_data_ptr_name

<Model data: procedures>+=
  function model_data_get_par_data_ptr_name (model, name) result (ptr)
    class(model_data_t), intent(in) :: model
    type(string_t), intent(in) :: name
    class(modelpar_data_t), pointer :: ptr

```

```

integer :: i
do i = 1, size (model%par_real)
  if (model%par_real(i)%name == name) then
    ptr => model%par_real(i)
    return
  end if
end do
do i = 1, size (model%par_complex)
  if (model%par_complex(i)%name == name) then
    ptr => model%par_complex(i)
    return
  end if
end do
ptr => null ()
end function model_data_get_par_data_ptr_name

```

Return the value by name. Again, type conversion is allowed.

```

<Model data: model data: TBP>+≡
  procedure :: get_real => model_data_get_par_real_value
  procedure :: get_complex => model_data_get_par_complex_value

<Model data: procedures>+≡
  function model_data_get_par_real_value (model, name) result (value)
    class(model_data_t), intent(in) :: model
    type(string_t), intent(in) :: name
    class(modelpar_data_t), pointer :: par
    real(default) :: value
    par => model%get_par_data_ptr (name)
    value = par%get_real ()
  end function model_data_get_par_real_value

  function model_data_get_par_complex_value (model, name) result (value)
    class(model_data_t), intent(in) :: model
    type(string_t), intent(in) :: name
    class(modelpar_data_t), pointer :: par
    complex(default) :: value
    par => model%get_par_data_ptr (name)
    value = par%get_complex ()
  end function model_data_get_par_complex_value

```

Modify a real or complex parameter.

```

<Model data: model data: TBP>+≡
  generic :: set_par => model_data_set_par_real, model_data_set_par_complex
  procedure, private :: model_data_set_par_real
  procedure, private :: model_data_set_par_complex

<Model data: procedures>+≡
  subroutine model_data_set_par_real (model, name, value)
    class(model_data_t), intent(inout) :: model
    type(string_t), intent(in) :: name
    real(default), intent(in) :: value
    class(modelpar_data_t), pointer :: par
    par => model%get_par_data_ptr (name)
    par = value
  end subroutine model_data_set_par_real

```

```

end subroutine model_data_set_par_real

subroutine model_data_set_par_complex (model, name, value)
  class(model_data_t), intent(inout) :: model
  type(string_t), intent(in) :: name
  complex(default), intent(in) :: value
  class(modelpar_data_t), pointer :: par
  par => model%get_par_data_ptr (name)
  par = value
end subroutine model_data_set_par_complex

```

List all fields in the model.

```

<Model data: model data: TBP>+≡
  procedure :: write_fields => model_data_write_fields

<Model data: procedures>+≡
  subroutine model_data_write_fields (model, unit)
    class(model_data_t), intent(in) :: model
    integer, intent(in), optional :: unit
    integer :: i
    do i = 1, size (model%field)
      call model%field(i)%write (unit)
    end do
  end subroutine model_data_write_fields

```

After initialization, return number of fields (particles):

```

<Model data: model data: TBP>+≡
  procedure :: get_n_field => model_data_get_n_field

<Model data: procedures>+≡
  function model_data_get_n_field (model) result (n)
    class(model_data_t), intent(in) :: model
    integer :: n
    n = size (model%field)
  end function model_data_get_n_field

```

Return the PDG code of a field. The field is identified by name or by index. If the field is not found, return zero.

```

<Model data: model data: TBP>+≡
  generic :: get_pdg => &
    model_data_get_field_pdg_index, &
    model_data_get_field_pdg_name
  procedure, private :: model_data_get_field_pdg_index
  procedure, private :: model_data_get_field_pdg_name

<Model data: procedures>+≡
  function model_data_get_field_pdg_index (model, i) result (pdg)
    class(model_data_t), intent(in) :: model
    integer, intent(in) :: i
    integer :: pdg
    pdg = model%field(i)%get_pdg ()
  end function model_data_get_field_pdg_index

```



```

function model_data_get_field_pdg_name (model, name, check) result (pdg)
  class(model_data_t), intent(in) :: model
  type(string_t), intent(in) :: name
  logical, intent(in), optional :: check
  integer :: pdg
  integer :: i
  do i = 1, size (model%field)
    associate (field => model%field(i))
      if (field%matches_name (name, .false.)) then
        pdg = field%get_pdg ()
        return
      else if (field%matches_name (name, .true.)) then
        pdg = - field%get_pdg ()
        return
      end if
    end associate
  end do
  pdg = 0
  call model%field_error (check, name)
end function model_data_get_field_pdg_name

```

Return an array of all PDG codes, including antiparticles. The antiparticle are sorted after all particles.

```

<Model data: model data: TBP>+≡
  procedure :: get_all_pdg => model_data_get_all_pdg

<Model data: procedures>+≡
  subroutine model_data_get_all_pdg (model, pdg)
    class(model_data_t), intent(in) :: model
    integer, dimension(:), allocatable, intent(inout) :: pdg
    integer :: n0, n1, i, k
    n0 = size (model%field)
    n1 = n0 + count (model%field%has_antiparticle ())
    allocate (pdg (n1))
    pdg(1:n0) = model%field%get_pdg ()
    k = n0
    do i = 1, size (model%field)
      associate (field => model%field(i))
        if (field%has_antiparticle ()) then
          k = k + 1
          pdg(k) = - field%get_pdg ()
        end if
      end associate
    end do
  end subroutine model_data_get_all_pdg

```

Return pointer to the field array.

```

<Model data: model data: TBP>+≡
  procedure :: get_field_array_ptr => model_data_get_field_array_ptr

<Model data: procedures>+≡
  function model_data_get_field_array_ptr (model) result (ptr)
    class(model_data_t), intent(in), target :: model
    type(field_data_t), dimension(:), pointer :: ptr

```

```

    ptr => model%field
end function model_data_get_field_array_ptr

```

Return pointer to a field. The identifier should be the unique long name, the PDG code, or the index.

We can issue an error message, if the `check` flag is set. We never return an error if the PDG code is zero, this yields just a null pointer.

```

<Model data: model data: TBP>+≡
    generic :: get_field_ptr => &
        model_data_get_field_ptr_name, &
        model_data_get_field_ptr_pdg
    procedure, private :: model_data_get_field_ptr_name
    procedure, private :: model_data_get_field_ptr_pdg
    procedure :: get_field_ptr_by_index => model_data_get_field_ptr_index

<Model data: procedures>+≡
    function model_data_get_field_ptr_name (model, name, check) result (ptr)
        class(model_data_t), intent(in), target :: model
        type(string_t), intent(in) :: name
        logical, intent(in), optional :: check
        type(field_data_t), pointer :: ptr
        integer :: i
        do i = 1, size (model%field)
            if (model%field(i)%matches_name (name, .false.)) then
                ptr => model%field(i)
                return
            else if (model%field(i)%matches_name (name, .true.)) then
                ptr => model%field(i)
                return
            end if
        end do
        ptr => null ()
        call model%field_error (check, name)
    end function model_data_get_field_ptr_name

    function model_data_get_field_ptr_pdg (model, pdg, check) result (ptr)
        class(model_data_t), intent(in), target :: model
        integer, intent(in) :: pdg
        logical, intent(in), optional :: check
        type(field_data_t), pointer :: ptr
        integer :: i, pdg_abs
        if (pdg == 0) then
            ptr => null ()
            return
        end if
        pdg_abs = abs (pdg)
        do i = 1, size (model%field)
            if (model%field(i)%get_pdg () == pdg_abs) then
                ptr => model%field(i)
                return
            end if
        end do
        ptr => null ()
        call model%field_error (check, pdg=pdg)
    end function model_data_get_field_ptr_pdg

```

```

end function model_data_get_field_ptr_pdg

function model_data_get_field_ptr_index (model, i) result (ptr)
  class(model_data_t), intent(in), target :: model
  integer, intent(in) :: i
  type(field_data_t), pointer :: ptr
  ptr => model%field(i)
end function model_data_get_field_ptr_index

```

Don't assign a pointer, just check.

```

<Model data: model data: TBP>+≡
  procedure :: test_field => model_data_test_field_pdg

<Model data: procedures>+≡
  function model_data_test_field_pdg (model, pdg, check) result (exist)
    class(model_data_t), intent(in), target :: model
    integer, intent(in) :: pdg
    logical, intent(in), optional :: check
    logical :: exist
    exist = associated (model%get_field_ptr (pdg, check))
  end function model_data_test_field_pdg

```

Error message, if check is set.

```

<Model data: model data: TBP>+≡
  procedure :: field_error => model_data_field_error

<Model data: procedures>+≡
  subroutine model_data_field_error (model, check, name, pdg)
    class(model_data_t), intent(in) :: model
    logical, intent(in), optional :: check
    type(string_t), intent(in), optional :: name
    integer, intent(in), optional :: pdg
    if (present (check)) then
      if (check) then
        if (present (name)) then
          write (msg_buffer, "(A,1x,A,1x,A,1x,A)" &
            "No particle with name", char (name), &
            "is contained in model", char (model%name))
        else if (present (pdg)) then
          write (msg_buffer, "(A,1x,I0,1x,A,1x,A)" &
            "No particle with PDG code", pdg, &
            "is contained in model", char (model%name))
        else
          write (msg_buffer, "(A,1x,A,1x,A)" &
            "Particle missing", &
            "in model", char (model%name))
        end if
        call msg_fatal ()
      end if
    end if
  end subroutine model_data_field_error

```

Assign mass and width value, which are associated via pointer. Identify the particle via pdg.

```

<Model data: model data: TBP>+≡
  procedure :: set_field_mass => model_data_set_field_mass_pdg
  procedure :: set_field_width => model_data_set_field_width_pdg

<Model data: procedures>+≡
  subroutine model_data_set_field_mass_pdg (model, pdg, value)
    class(model_data_t), intent(inout) :: model
    integer, intent(in) :: pdg
    real(default), intent(in) :: value
    type(field_data_t), pointer :: field
    field => model%get_field_ptr (pdg, check = .true.)
    call field%set_mass (value)
  end subroutine model_data_set_field_mass_pdg

  subroutine model_data_set_field_width_pdg (model, pdg, value)
    class(model_data_t), intent(inout) :: model
    integer, intent(in) :: pdg
    real(default), intent(in) :: value
    type(field_data_t), pointer :: field
    field => model%get_field_ptr (pdg, check = .true.)
    call field%set_width (value)
  end subroutine model_data_set_field_width_pdg

```

Mark a particle as unstable and provide a list of names for its decay processes. In contrast with the previous subroutine which is for internal use, we address the particle by its PDG code. If the index is negative, we address the antiparticle.

```

<Model data: model data: TBP>+≡
  procedure :: set_unstable => model_data_set_unstable
  procedure :: set_stable => model_data_set_stable

<Model data: procedures>+≡
  subroutine model_data_set_unstable &
    (model, pdg, decay, isotropic, diagonal, decay_helicity)
    class(model_data_t), intent(inout), target :: model
    integer, intent(in) :: pdg
    type(string_t), dimension(:), intent(in) :: decay
    logical, intent(in), optional :: isotropic, diagonal
    integer, intent(in), optional :: decay_helicity
    type(field_data_t), pointer :: field
    field => model%get_field_ptr (pdg)
    if (pdg > 0) then
      call field%set ( &
        p_is_stable = .false., p_decay = decay, &
        p_decays_isotropically = isotropic, &
        p_decays_diagonal = diagonal, &
        p_decay_helicity = decay_helicity)
    else
      call field%set ( &
        a_is_stable = .false., a_decay = decay, &
        a_decays_isotropically = isotropic, &
        a_decays_diagonal = diagonal, &
        a_decay_helicity = decay_helicity)
    end if
  end subroutine model_data_set_unstable

```

```

        end if
    end subroutine model_data_set_unstable

    subroutine model_data_set_stable (model, pdg)
        class(model_data_t), intent(inout), target :: model
        integer, intent(in) :: pdg
        type(field_data_t), pointer :: field
        field => model%get_field_ptr (pdg)
        if (pdg > 0) then
            call field%set (p_is_stable = .true.)
        else
            call field%set (a_is_stable = .true.)
        end if
    end subroutine model_data_set_stable

```

Mark a particle as polarized.

```

<Model data: model data: TBP>+=
    procedure :: set_polarized => model_data_set_polarized
    procedure :: set_unpolarized => model_data_set_unpolarized

<Model data: procedures>+=
    subroutine model_data_set_polarized (model, pdg)
        class(model_data_t), intent(inout), target :: model
        integer, intent(in) :: pdg
        type(field_data_t), pointer :: field
        field => model%get_field_ptr (pdg)
        if (pdg > 0) then
            call field%set (p_polarized = .true.)
        else
            call field%set (a_polarized = .true.)
        end if
    end subroutine model_data_set_polarized

    subroutine model_data_set_unpolarized (model, pdg)
        class(model_data_t), intent(inout), target :: model
        integer, intent(in) :: pdg
        type(field_data_t), pointer :: field
        field => model%get_field_ptr (pdg)
        if (pdg > 0) then
            call field%set (p_polarized = .false.)
        else
            call field%set (a_polarized = .false.)
        end if
    end subroutine model_data_set_unpolarized

```

Revert all polarized (unstable) particles to unpolarized (stable) status, respectively.

```

<Model data: model data: TBP>+=
    procedure :: clear_unstable => model_clear_unstable
    procedure :: clear_polarized => model_clear_polarized

<Model data: procedures>+=
    subroutine model_clear_unstable (model)
        class(model_data_t), intent(inout), target :: model

```

```

integer :: i
type(field_data_t), pointer :: field
do i = 1, model%get_n_field ()
    field => model%get_field_ptr_by_index (i)
    call field%set (p_is_stable = .true.)
    if (field%has_antiparticle ()) then
        call field%set (a_is_stable = .true.)
    end if
end do
end subroutine model_clear_unstable

subroutine model_clear_polarized (model)
class(model_data_t), intent(inout), target :: model
integer :: i
type(field_data_t), pointer :: field
do i = 1, model%get_n_field ()
    field => model%get_field_ptr_by_index (i)
    call field%set (p_polarized = .false.)
    if (field%has_antiparticle ()) then
        call field%set (a_polarized = .false.)
    end if
end do
end subroutine model_clear_polarized

```

List all vertices, optionally also the hash table.

```

<Model data: model data: TBP>+≡
    procedure :: write_vertices => model_data_write_vertices

<Model data: procedures>+≡
    subroutine model_data_write_vertices (model, unit, verbose)
    class(model_data_t), intent(in) :: model
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: i, u
    u = given_output_unit (unit)
    do i = 1, size (model%vtx)
        call vertex_write (model%vtx(i), unit)
    end do
    if (present (verbose)) then
        if (verbose) then
            write (u, *)
            call vertex_table_write (model%vt, unit)
        end if
    end if
end subroutine model_data_write_vertices

```

Vertex definition.

```

<Model data: model data: TBP>+≡
    generic :: set_vertex => &
        model_data_set_vertex_pdg, model_data_set_vertex_names
    procedure, private :: model_data_set_vertex_pdg
    procedure, private :: model_data_set_vertex_names

```

```

<Model data: procedures>+≡
  subroutine model_data_set_vertex_pdg (model, i, pdg)
    class(model_data_t), intent(inout), target :: model
    integer, intent(in) :: i
    integer, dimension(:), intent(in) :: pdg
    call vertex_init (model%vtx(i), pdg, model)
  end subroutine model_data_set_vertex_pdg

  subroutine model_data_set_vertex_names (model, i, name)
    class(model_data_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(string_t), dimension(:), intent(in) :: name
    integer, dimension(size(name)) :: pdg
    integer :: j
    do j = 1, size (name)
      pdg(j) = model%get_pdg (name(j))
    end do
    call model%set_vertex (i, pdg)
  end subroutine model_data_set_vertex_names

```

Finalize vertex definition: set up the hash table.

```

<Model data: model data: TBP>+≡
  procedure :: freeze_vertices => model_data_freeze_vertices

<Model data: procedures>+≡
  subroutine model_data_freeze_vertices (model)
    class(model_data_t), intent(inout) :: model
    call model%vt%init (model%field, model%vtx)
  end subroutine model_data_freeze_vertices

```

Number of vertices in model

```

<Model data: model data: TBP>+≡
  procedure :: get_n_vtx => model_data_get_n_vtx

<Model data: procedures>+≡
  function model_data_get_n_vtx (model) result (n)
    class(model_data_t), intent(in) :: model
    integer :: n
    n = size (model%vtx)
  end function model_data_get_n_vtx

```

Lookup functions

```

<Model data: model data: TBP>+≡
  procedure :: match_vertex => model_data_match_vertex

<Model data: procedures>+≡
  subroutine model_data_match_vertex (model, pdg1, pdg2, pdg3)
    class(model_data_t), intent(in) :: model
    integer, intent(in) :: pdg1, pdg2
    integer, dimension(:), allocatable, intent(out) :: pdg3
    call model%vt%match (pdg1, pdg2, pdg3)
  end subroutine model_data_match_vertex

```

```

<Model data: model data: TBP>+=
  procedure :: check_vertex => model_data_check_vertex

<Model data: procedures>+=
  function model_data_check_vertex (model, pdg1, pdg2, pdg3) result (flag)
    logical :: flag
    class(model_data_t), intent(in) :: model
    integer, intent(in) :: pdg1, pdg2, pdg3
    flag = model%vt%check (pdg1, pdg2, pdg3)
  end function model_data_check_vertex

```

10.1.6 Toy Models

This is a stripped-down version of the (already trivial) model 'Test'.

```

<Model data: model data: TBP>+=
  procedure :: init_test => model_data_init_test

<Model data: procedures>+=
  subroutine model_data_init_test (model)
    class(model_data_t), intent(out) :: model
    type(field_data_t), pointer :: field
    integer, parameter :: n_real = 4
    integer, parameter :: n_field = 2
    integer, parameter :: n_vertex = 2
    integer :: i
    call model%init (var_str ("Test"), &
      n_real, 0, n_field, n_vertex)
    i = 0
    i = i + 1
    call model%init_par (i, var_str ("gy"), 1._default)
    i = i + 1
    call model%init_par (i, var_str ("ms"), 125._default)
    i = i + 1
    call model%init_par (i, var_str ("ff"), 1.5_default)
    i = i + 1
    call model%init_par (i, var_str ("mf"), 1.5_default * 125._default)
    i = 0
    i = i + 1
    field => model%get_field_ptr_by_index (i)
    call field%init (var_str ("SCALAR"), 25)
    call field%set (spin_type=1)
    call field%set (mass_data=model%get_par_real_ptr (2))
    call field%set (name = [var_str ("s")])
    i = i + 1
    field => model%get_field_ptr_by_index (i)
    call field%init (var_str ("FERMION"), 6)
    call field%set (spin_type=2)
    call field%set (mass_data=model%get_par_real_ptr (4))
    call field%set (name = [var_str ("f")], anti = [var_str ("fbar")])
    call model%freeze_fields ()
    i = 0
    i = i + 1
    call model%set_vertex (i, [var_str ("fbar"), var_str ("f"), var_str ("s")])

```



```

i = i + 1
call model%set_vertex (i, [var_str ("s"), var_str ("s"), var_str ("s")])
call model%freeze_vertices ()
end subroutine model_data_init_test

```

This procedure prepares a subset of QED for testing purposes.

```

<Model data: model data: TBP>+≡
  procedure :: init_qed_test => model_data_init_qed_test

<Model data: procedures>+≡
  subroutine model_data_init_qed_test (model)
    class(model_data_t), intent(out) :: model
    type(field_data_t), pointer :: field
    integer, parameter :: n_real = 1
    integer, parameter :: n_field = 2
    integer :: i
    call model%init (var_str ("QED_test"), &
      n_real, 0, n_field, 0)
    i = 0
    i = i + 1
    call model%init_par (i, var_str ("me"), 0.000510997_default)
    i = 0
    i = i + 1
    field => model%get_field_ptr_by_index (i)
    call field%init (var_str ("E_LEPTON"), 11)
    call field%set (spin_type=2, charge_type=-4)
    call field%set (mass_data=model%get_par_real_ptr (1))
    call field%set (name = [var_str ("e-")], anti = [var_str ("e+")])
    i = i + 1
    field => model%get_field_ptr_by_index (i)
    call field%init (var_str ("PHOTON"), 22)
    call field%set (spin_type=3)
    call field%set (name = [var_str ("A")])
    call model%freeze_fields ()
    call model%freeze_vertices ()
  end subroutine model_data_init_qed_test

```

This procedure prepares a subset of the Standard Model for testing purposes. We can thus avoid dependencies on model I/O, which is not defined here.

```

<Model data: model data: TBP>+≡
  procedure :: init_sm_test => model_data_init_sm_test

<Model data: procedures>+≡
  subroutine model_data_init_sm_test (model)
    class(model_data_t), intent(out) :: model
    type(field_data_t), pointer :: field
    integer, parameter :: n_real = 11
    integer, parameter :: n_field = 19
    integer, parameter :: n_vtx = 9
    integer :: i
    call model%init (var_str ("SM_test"), &
      n_real, 0, n_field, n_vtx)
    i = 0
    i = i + 1

```

```

call model%init_par (i, var_str ("mZ"), 91.1882_default)
i = i + 1
call model%init_par (i, var_str ("mW"), 80.419_default)
i = i + 1
call model%init_par (i, var_str ("me"), 0.000510997_default)
i = i + 1
call model%init_par (i, var_str ("mmu"), 0.105658389_default)
i = i + 1
call model%init_par (i, var_str ("mb"), 4.2_default)
i = i + 1
call model%init_par (i, var_str ("mtop"), 173.1_default)
i = i + 1
call model%init_par (i, var_str ("wZ"), 2.443_default)
i = i + 1
call model%init_par (i, var_str ("wW"), 2.049_default)
i = i + 1
call model%init_par (i, var_str ("ee"), 0.3079561542961_default)
i = i + 1
call model%init_par (i, var_str ("cw"), 8.819013863636E-01_default)
i = i + 1
call model%init_par (i, var_str ("sw"), 4.714339240339E-01_default)
i = 0
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("D_QUARK"), 1)
call field%set (spin_type=2, color_type=3, charge_type=-2, isospin_type=-2)
call field%set (name = [var_str ("d")], anti = [var_str ("dbar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("U_QUARK"), 2)
call field%set (spin_type=2, color_type=3, charge_type=3, isospin_type=2)
call field%set (name = [var_str ("u")], anti = [var_str ("ubar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("S_QUARK"), 3)
call field%set (spin_type=2, color_type=3, charge_type=-2, isospin_type=-2)
call field%set (name = [var_str ("s")], anti = [var_str ("sbar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("C_QUARK"), 4)
call field%set (spin_type=2, color_type=3, charge_type=3, isospin_type=2)
call field%set (name = [var_str ("c")], anti = [var_str ("cbar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("B_QUARK"), 5)
call field%set (spin_type=2, color_type=3, charge_type=-2, isospin_type=-2)
call field%set (mass_data=model%get_par_real_ptr (5))
call field%set (name = [var_str ("b")], anti = [var_str ("bbar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("T_QUARK"), 6)
call field%set (spin_type=2, color_type=3, charge_type=3, isospin_type=2)
call field%set (mass_data=model%get_par_real_ptr (6))
call field%set (name = [var_str ("t")], anti = [var_str ("tbar")])

```

```

i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("E_LEPTON"), 11)
call field%set (spin_type=2)
call field%set (mass_data=model%get_par_real_ptr (3))
call field%set (name = [var_str ("e-")], anti = [var_str ("e+")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("E_NEUTRINO"), 12)
call field%set (spin_type=2, is_left_handed=.true.)
call field%set (name = [var_str ("nue")], anti = [var_str ("nuebar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("MU_LEPTON"), 13)
call field%set (spin_type=2)
call field%set (mass_data=model%get_par_real_ptr (4))
call field%set (name = [var_str ("mu-")], anti = [var_str ("mu+")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("MU_NEUTRINO"), 14)
call field%set (spin_type=2, is_left_handed=.true.)
call field%set (name = [var_str ("numu")], anti = [var_str ("numubar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("GLUON"), 21)
call field%set (spin_type=3, color_type=8)
call field%set (name = [var_str ("gl")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("PHOTON"), 22)
call field%set (spin_type=3)
call field%set (name = [var_str ("A")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("Z_BOSON"), 23)
call field%set (spin_type=3)
call field%set (mass_data=model%get_par_real_ptr (1))
call field%set (width_data=model%get_par_real_ptr (7))
call field%set (name = [var_str ("Z")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("W_BOSON"), 24)
call field%set (spin_type=3)
call field%set (mass_data=model%get_par_real_ptr (2))
call field%set (width_data=model%get_par_real_ptr (8))
call field%set (name = [var_str ("W+")], anti = [var_str ("W-")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("HIGGS"), 25)
call field%set (spin_type=1)
!   call field%set (mass_data=model%get_par_real_ptr (2))
!   call field%set (width_data=model%get_par_real_ptr (8))
call field%set (name = [var_str ("H")])
i = i + 1

```

```

field => model%get_field_ptr_by_index (i)
call field%init (var_str ("PROTON"), 2212)
call field%set (spin_type=2)
call field%set (name = [var_str ("p")], anti = [var_str ("pbar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("HADRON_REMNANT_SINGLET"), 91)
call field%set (color_type=1)
call field%set (name = [var_str ("hr1")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("HADRON_REMNANT_TRIPLET"), 92)
call field%set (color_type=3)
call field%set (name = [var_str ("hr3")], anti = [var_str ("hr3bar")])
i = i + 1
field => model%get_field_ptr_by_index (i)
call field%init (var_str ("HADRON_REMNANT_OCTET"), 93)
call field%set (color_type=8)
call field%set (name = [var_str ("hr8")])
call model%freeze_fields ()
i = 0
i = i + 1
call model%set_vertex (i, [var_str ("dbar"), var_str ("d"), var_str ("A")])
i = i + 1
call model%set_vertex (i, [var_str ("ubar"), var_str ("u"), var_str ("A")])
i = i + 1
call model%set_vertex (i, [var_str ("gl"), var_str ("gl"), var_str ("gl")])
i = i + 1
call model%set_vertex (i, [var_str ("dbar"), var_str ("d"), var_str ("gl")])
i = i + 1
call model%set_vertex (i, [var_str ("ubar"), var_str ("u"), var_str ("gl")])
i = i + 1
call model%set_vertex (i, [var_str ("dbar"), var_str ("d"), var_str ("Z")])
i = i + 1
call model%set_vertex (i, [var_str ("ubar"), var_str ("u"), var_str ("Z")])
i = i + 1
call model%set_vertex (i, [var_str ("ubar"), var_str ("d"), var_str ("W+")])
i = i + 1
call model%set_vertex (i, [var_str ("dbar"), var_str ("u"), var_str ("W-")])
call model%freeze_vertices ()
end subroutine model_data_init_sm_test

```

10.2 Model Testbed

The standard way of defining a model uses concrete variables and expressions to interpret the model file. Some of this is not available at the point of use. This is no problem for the WHIZARD program as a whole, but unit tests are kept local to their respective module and don't access all definitions.

Instead, we introduce a separate module that provides hooks, one for initializing a model and one for finalizing a model. The main program can assign real routines to the hooks (procedure pointers of abstract type) before unit tests are called. The unit tests can call the abstract routines without knowing about their implementation.

```
<model_testbed.f90>≡
  module model_testbed

    <File header>

    <Use strings>
    use model_data
    use var_base

    <Standard module head>

    <Model testbed: public>

    <Model testbed: variables>

    <Model testbed: interfaces>

  end module model_testbed
```

10.2.1 Abstract Model Handlers

Both routines take a polymorphic model (data) pointer, which is allocated/deallocated inside the subroutine. The model constructor `prepare_model` requires the model name as input. It can, optionally, return a link to the variable list of the model.

```
<Model testbed: public>≡
  public :: prepare_model
  public :: cleanup_model

<Model testbed: variables>≡
  procedure (prepare_model_proc), pointer :: prepare_model => null ()
  procedure (cleanup_model_proc), pointer :: cleanup_model => null ()

<Model testbed: interfaces>≡
  abstract interface
    subroutine prepare_model_proc (model, name, vars)
      import
      class(model_data_t), pointer, intent(inout) :: model
      type(string_t), intent(in) :: name
      class(vars_t), pointer, intent(out), optional :: vars
    end subroutine prepare_model_proc
  end interface
```

```
abstract interface
  subroutine cleanup_model_proc (model)
    import
    class(model_data_t), pointer, intent(inout) :: model
  end subroutine cleanup_model_proc
end interface
```

10.3 Helicities

This module defines types and tools for dealing with helicity information.

```
<helicities.f90>≡  
  <File header>
```

```
  module helicities
```

```
    use io_units
```

```
  <Standard module head>
```

```
  <Helicities: public>
```

```
  <Helicities: types>
```

```
  <Helicities: interfaces>
```

```
  contains
```

```
  <Helicities: procedures>
```

```
  end module helicities
```

10.3.1 Helicity types

Helicities may be defined or undefined, corresponding to a polarized or unpolarized state. Each helicity is actually a pair of helicities, corresponding to an entry in the spin density matrix. Obviously, diagonal entries are distinguished.

```
<Helicities: public>≡  
  public :: helicity_t  
<Helicities: types>≡  
  type :: helicity_t  
    private  
    logical :: defined = .false.  
    integer :: h1, h2  
    contains  
    <Helicities: helicity: TBP>  
  end type helicity_t
```

Constructor functions, for convenience:

```
<Helicities: public>+≡  
  public :: helicity  
<Helicities: interfaces>≡  
  interface helicity  
    module procedure helicity0, helicity1, helicity2  
  end interface helicity
```

```

<Helicities: procedures>≡
  pure function helicity0 () result (hel)
    type(helicity_t) :: hel
  end function helicity0

  elemental function helicity1 (h) result (hel)
    type(helicity_t) :: hel
    integer, intent(in) :: h
    call hel%init (h)
  end function helicity1

  elemental function helicity2 (h2, h1) result (hel)
    type(helicity_t) :: hel
    integer, intent(in) :: h1, h2
    call hel%init (h2, h1)
  end function helicity2

```

Initializers.

Note: conceptually, the argument to initializers should be INTENT(OUT). However, Interp. F08/0033 prohibited this. The reason is that, in principle, the call could result in the execution of an impure finalizer for a type extension of `hel` (ugh).

```

<Helicities: helicity: TBP>≡
  generic :: init => helicity_init0, helicity_init1, helicity_init2
  procedure, private :: helicity_init0
  procedure, private :: helicity_init1
  procedure, private :: helicity_init2

<Helicities: procedures>+≡
  elemental subroutine helicity_init0 (hel)
    class(helicity_t), intent(inout) :: hel
    hel%defined = .false.
  end subroutine helicity_init0

  elemental subroutine helicity_init1 (hel, h)
    class(helicity_t), intent(inout) :: hel
    integer, intent(in) :: h
    hel%defined = .true.
    hel%h1 = h
    hel%h2 = h
  end subroutine helicity_init1

  elemental subroutine helicity_init2 (hel, h2, h1)
    class(helicity_t), intent(inout) :: hel
    integer, intent(in) :: h1, h2
    hel%defined = .true.
    hel%h2 = h2
    hel%h1 = h1
  end subroutine helicity_init2

```

Undefine:

```

<Helicities: helicity: TBP>+≡
  procedure :: undefine => helicity_undefine

```



```

<Helicities: procedures>+≡
  elemental subroutine helicity_undefine (hel)
    class(helicity_t), intent(inout) :: hel
    hel%defined = .false.
  end subroutine helicity_undefine

```

Diagonalize by removing the second entry (use with care!)

```

<Helicities: helicity: TBP>+≡
  procedure :: diagonalize => helicity_diagonalize

<Helicities: procedures>+≡
  elemental subroutine helicity_diagonalize (hel)
    class(helicity_t), intent(inout) :: hel
    hel%h2 = hel%h1
  end subroutine helicity_diagonalize

```

Output (no linebreak). No output if undefined.

```

<Helicities: helicity: TBP>+≡
  procedure :: write => helicity_write

<Helicities: procedures>+≡
  subroutine helicity_write (hel, unit)
    class(helicity_t), intent(in) :: hel
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit(unit); if (u < 0) return
    if (hel%defined) then
      write (u, "(A)", advance="no") "h("
      write (u, "(I0)", advance="no") hel%h1
      if (hel%h1 /= hel%h2) then
        write (u, "(A)", advance="no") "|"
        write (u, "(I0)", advance="no") hel%h2
      end if
      write (u, "(A)", advance="no") ")"
    end if
  end subroutine helicity_write

```

Binary I/O. Write contents only if defined.

```

<Helicities: helicity: TBP>+≡
  procedure :: write_raw => helicity_write_raw
  procedure :: read_raw => helicity_read_raw

<Helicities: procedures>+≡
  subroutine helicity_write_raw (hel, u)
    class(helicity_t), intent(in) :: hel
    integer, intent(in) :: u
    write (u) hel%defined
    if (hel%defined) then
      write (u) hel%h1, hel%h2
    end if
  end subroutine helicity_write_raw

  subroutine helicity_read_raw (hel, u, iostat)
    class(helicity_t), intent(out) :: hel

```

```

integer, intent(in) :: u
integer, intent(out), optional :: iostat
read (u, iostat=iostat) hel%defined
if (hel%defined) then
    read (u, iostat=iostat) hel%h1, hel%h2
end if
end subroutine helicity_read_raw

```

10.3.2 Predicates

Check if the helicity is defined:

```

<Helicities: helicity: TBP>+≡
    procedure :: is_defined => helicity_is_defined

<Helicities: procedures>+≡
    elemental function helicity_is_defined (hel) result (defined)
        logical :: defined
        class(helicity_t), intent(in) :: hel
        defined = hel%defined
    end function helicity_is_defined

```

Return true if the two helicities are equal or the particle is unpolarized:

```

<Helicities: helicity: TBP>+≡
    procedure :: is_diagonal => helicity_is_diagonal

<Helicities: procedures>+≡
    elemental function helicity_is_diagonal (hel) result (diagonal)
        logical :: diagonal
        class(helicity_t), intent(in) :: hel
        if (hel%defined) then
            diagonal = hel%h1 == hel%h2
        else
            diagonal = .true.
        end if
    end function helicity_is_diagonal

```

10.3.3 Accessing contents

This returns a two-element array and thus cannot be elemental. The result is unpredictable if the helicity is undefined.

```

<Helicities: helicity: TBP>+≡
    procedure :: to_pair => helicity_to_pair

<Helicities: procedures>+≡
    pure function helicity_to_pair (hel) result (h)
        integer, dimension(2) :: h
        class(helicity_t), intent(in) :: hel
        h(1) = hel%h2
        h(2) = hel%h1
    end function helicity_to_pair

```

10.3.4 Comparisons

When comparing helicities, if either one is undefined, they are considered to match. In other words, an unpolarized particle matches any polarization. In the `dmatch` variant, it matches only diagonal helicity.

```
(Helicities: helicity: TBP)+≡
  generic :: operator(.match.) => helicity_match
  generic :: operator(.dmatch.) => helicity_match_diagonal
  generic :: operator(==) => helicity_eq
  generic :: operator(/=) => helicity_neq
  procedure, private :: helicity_match
  procedure, private :: helicity_match_diagonal
  procedure, private :: helicity_eq
  procedure, private :: helicity_neq

(Helicities: procedures)+≡
  elemental function helicity_match (hel1, hel2) result (eq)
    logical :: eq
    class(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      eq = (hel1%h1 == hel2%h1) .and. (hel1%h2 == hel2%h2)
    else
      eq = .true.
    end if
  end function helicity_match

  elemental function helicity_match_diagonal (hel1, hel2) result (eq)
    logical :: eq
    class(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      eq = (hel1%h1 == hel2%h1) .and. (hel1%h2 == hel2%h2)
    else if (hel1%defined) then
      eq = hel1%h1 == hel1%h2
    else if (hel2%defined) then
      eq = hel2%h1 == hel2%h2
    else
      eq = .true.
    end if
  end function helicity_match_diagonal

  elemental function helicity_eq (hel1, hel2) result (eq)
    logical :: eq
    class(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      eq = (hel1%h1 == hel2%h1) .and. (hel1%h2 == hel2%h2)
    else if (.not. hel1%defined .and. .not. hel2%defined) then
      eq = .true.
    else
      eq = .false.
    end if
  end function helicity_eq

(Helicities: procedures)+≡
```

```

elemental function helicity_neq (hel1, hel2) result (neq)
  logical :: neq
  class(helicity_t), intent(in) :: hel1, hel2
  if (hel1%defined .and. hel2%defined) then
    neq = (hel1%h1 /= hel2%h1) .or. (hel1%h2 /= hel2%h2)
  else if (.not. hel1%defined .and. .not. hel2%defined) then
    neq = .false.
  else
    neq = .true.
  end if
end function helicity_neq

```

10.3.5 Tools

Merge two helicity objects by taking the first entry from the first and the second entry from the second argument. Makes sense only if the input helicities were defined and diagonal. The handling of ghost flags is not well-defined; one should verify beforehand that they match.

(Helicities: helicity: TBP)+≡

```

generic :: operator(.merge.) => merge_helicities
procedure, private :: merge_helicities

```

(Helicities: procedures)+≡

```

elemental function merge_helicities (hel1, hel2) result (hel)
  type(helicity_t) :: hel
  class(helicity_t), intent(in) :: hel1, hel2
  if (hel1%defined .and. hel2%defined) then
    call helicity_init2 (hel, hel2%h1, hel1%h1)
  else if (hel1%defined) then
    call helicity_init2 (hel, hel1%h2, hel1%h1)
  else if (hel2%defined) then
    call helicity_init2 (hel, hel2%h2, hel2%h1)
  end if
end function merge_helicities

```

10.4 Colors

This module defines a type and tools for dealing with color information.

Each particle can have zero or more (in practice, usually not more than two) color indices. Color indices are positive; flow direction can be determined from the particle nature.

While parton shower matrix elements are diagonal in color, some special applications (e.g., subtractions for NLO matrix elements) require non-diagonal color matrices.

```
<colors.f90>≡  
  <File header>  
  
  module colors  
  
    <Use kinds>  
    use io_units  
    use unit_tests  
    use diagnostics  
  
    <Standard module head>  
  
    <Colors: public>  
  
    <Colors: types>  
  
    <Colors: interfaces>  
  
    contains  
  
    <Colors: procedures>  
  
    <Colors: tests>  
  
  end module colors
```

10.4.1 The color type

A particle may have an arbitrary number of color indices (in practice, from zero to two, but more are possible). This object acts as a container. (The current implementation has a fixed array of length two.)

The fact that color comes as an array prohibits elemental procedures in some places. (May add interfaces and multi versions where necessary.)

The color may be undefined.

NOTE: Due to a compiler bug in nagfor 5.2, we do not use allocatable but fixed-size arrays with dimension 2. Only nonzero entries count. This may be more efficient anyway, but gives up some flexibility. However, the squaring algorithm currently works only for singlets, (anti)triplets and octets anyway, so two components are enough.

This type has to be generalized (abstract type and specific implementations) when trying to pursue generalized color flows or Monte Carlo over continuous color.

```
<Colors: public>≡
```

```

    public :: color_t
<Colors: types>≡
    type :: color_t
        private
        logical :: defined = .false.
        integer, dimension(2) :: c1 = 0, c2 = 0
        logical :: ghost = .false.
    contains
    <Colors: color: TBP>
end type color_t

```

Initializers:

```

<Colors: color: TBP>≡
    generic :: init => &
        color_init_trivial, color_init_trivial_ghost, &
        color_init_array, color_init_array_ghost, &
        color_init_arrays, color_init_arrays_ghost
    procedure, private :: color_init_trivial
    procedure, private :: color_init_trivial_ghost
    procedure, private :: color_init_array
    procedure, private :: color_init_array_ghost
    procedure, private :: color_init_arrays
    procedure, private :: color_init_arrays_ghost

```

Undefined color: array remains unallocated

```

<Colors: procedures>≡
    pure subroutine color_init_trivial (col)
        class(color_t), intent(inout) :: col
        col%defined = .true.
        col%c1 = 0
        col%c2 = 0
        col%ghost = .false.
    end subroutine color_init_trivial

    pure subroutine color_init_trivial_ghost (col, ghost)
        class(color_t), intent(inout) :: col
        logical, intent(in) :: ghost
        col%defined = .true.
        col%c1 = 0
        col%c2 = 0
        col%ghost = ghost
    end subroutine color_init_trivial_ghost

```

This defines color from an arbitrary length color array, suitable for any representation. We may have two color arrays (non-diagonal matrix elements). This cannot be elemental. The third version assigns an array of colors, using a two-dimensional array as input.

```

<Colors: procedures>+≡
    pure subroutine color_init_array (col, c1)
        class(color_t), intent(inout) :: col
        integer, dimension(:), intent(in) :: c1
        col%defined = .true.

```

```

    col%c1 = pack (c1, c1 /= 0, [0,0])
    col%c2 = col%c1
    col%ghost = .false.
end subroutine color_init_array

pure subroutine color_init_array_ghost (col, c1, ghost)
    class(color_t), intent(inout) :: col
    integer, dimension(:), intent(in) :: c1
    logical, intent(in) :: ghost
    call color_init_array (col, c1)
    col%ghost = ghost
end subroutine color_init_array_ghost

pure subroutine color_init_arrays (col, c1, c2)
    class(color_t), intent(inout) :: col
    integer, dimension(:), intent(in) :: c1, c2
    col%defined = .true.
    if (size (c1) == size (c2)) then
        col%c1 = pack (c1, c1 /= 0, [0,0])
        col%c2 = pack (c2, c2 /= 0, [0,0])
    else if (size (c1) /= 0) then
        col%c1 = pack (c1, c1 /= 0, [0,0])
        col%c2 = col%c1
    else if (size (c2) /= 0) then
        col%c1 = pack (c2, c2 /= 0, [0,0])
        col%c2 = col%c1
    end if
    col%ghost = .false.
end subroutine color_init_arrays

pure subroutine color_init_arrays_ghost (col, c1, c2, ghost)
    class(color_t), intent(inout) :: col
    integer, dimension(:), intent(in) :: c1, c2
    logical, intent(in) :: ghost
    call color_init_arrays (col, c1, c2)
    col%ghost = ghost
end subroutine color_init_arrays_ghost

```

This version is restricted to singlets, triplets, antitriplets, and octets: The input contains the color and anticolor index, each of the may be zero.

```

<Colors: color: TBP>+≡
    procedure :: init_col_acl => color_init_col_acl

<Colors: procedures>+≡
    elemental subroutine color_init_col_acl (col, col_in, acl_in)
        class(color_t), intent(inout) :: col
        integer, intent(in) :: col_in, acl_in
        integer, dimension(0) :: null_array
        select case (col_in)
        case (0)
            select case (acl_in)
            case (0)
                call color_init_array (col, null_array)
            case default

```

```

        call color_init_array (col, [-acl_in])
    end select
case default
    select case (acl_in)
    case (0)
        call color_init_array (col, [col_in])
    case default
        call color_init_array (col, [col_in, -acl_in])
    end select
end select
end subroutine color_init_col_acl

```

This version is used for the external interface. We convert a fixed-size array of colors (for each particle) to the internal form by packing only the nonzero entries.

Some of these procedures produce an array, so they can't be all type-bound. We implement them as ordinary procedures.

<Colors: public>+≡

```
public :: color_init_from_array
```

<Colors: interfaces>≡

```

interface color_init_from_array
    module procedure color_init_from_array1
    module procedure color_init_from_array1g
    module procedure color_init_from_array2
    module procedure color_init_from_array2g
end interface color_init_from_array

```

<Colors: procedures>+≡

```

pure subroutine color_init_from_array1 (col, c1)
    type(color_t), intent(inout) :: col
    integer, dimension(:), intent(in) :: c1
    logical, dimension(size(c1)) :: mask
    mask = c1 /= 0
    col%defined = .true.
    col%c1 = pack (c1, mask, col%c1)
    col%c2 = col%c1
    col%ghost = .false.
end subroutine color_init_from_array1

pure subroutine color_init_from_array1g (col, c1, ghost)
    type(color_t), intent(inout) :: col
    integer, dimension(:), intent(in) :: c1
    logical, intent(in) :: ghost
    call color_init_from_array1 (col, c1)
    col%ghost = ghost
end subroutine color_init_from_array1g

pure subroutine color_init_from_array2 (col, c1)
    integer, dimension(:, :), intent(in) :: c1
    type(color_t), dimension(:), intent(inout) :: col
    integer :: i
    do i = 1, size (c1,2)

```



```

        call color_init_from_array1 (col(i), c1(:,i))
    end do
end subroutine color_init_from_array2

pure subroutine color_init_from_array2g (col, c1, ghost)
    integer, dimension(:,,:), intent(inout) :: c1
    type(color_t), dimension(:), intent(out) :: col
    logical, intent(in), dimension(:) :: ghost
    call color_init_from_array2 (col, c1)
    col%ghost = ghost
end subroutine color_init_from_array2g

```

Set the ghost property

```

<Colors: color: TBP>+≡
    procedure :: set_ghost => color_set_ghost

<Colors: procedures>+≡
    elemental subroutine color_set_ghost (col, ghost)
        class(color_t), intent(inout) :: col
        logical, intent(in) :: ghost
        col%ghost = ghost
    end subroutine color_set_ghost

```

Undefine the color state:

```

<Colors: color: TBP>+≡
    procedure :: undefine => color_undefine

<Colors: procedures>+≡
    elemental subroutine color_undefine (col, undefine_ghost)
        class(color_t), intent(inout) :: col
        logical, intent(in), optional :: undefine_ghost
        col%defined = .false.
        if (present (undefine_ghost)) then
            if (undefine_ghost) col%ghost = .false.
        else
            col%ghost = .false.
        end if
    end subroutine color_undefine

```

Output. As dense as possible, no linebreak. If color is undefined, no output.

The separate version for a color array suggest two distinct interfaces.

```

<Colors: public>+≡
    public :: color_write

<Colors: interfaces>+≡
    interface color_write
        module procedure color_write_single
        module procedure color_write_array
    end interface color_write

<Colors: color: TBP>+≡
    procedure :: write => color_write_single

```

<Colors: procedures>+≡

```

subroutine color_write_single (col, unit)
  class(color_t), intent(in) :: col
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  if (col%ghost) then
    write (u, "(A)", advance="no") "c*"
  else if (col%defined) then
    write (u, "(A)", advance="no") "c("
    if (col%c1(1) /= 0) write (u, "(I0)", advance="no") col%c1(1)
    if (any (col%c1 /= 0)) write (u, "(1x)", advance="no")
    if (col%c1(2) /= 0) write (u, "(I0)", advance="no") col%c1(2)
    if (.not. col%is_diagonal ()) then
      write (u, "(A)", advance="no") "|"
      if (col%c2(1) /= 0) write (u, "(I0)", advance="no") col%c2(1)
      if (any (col%c2 /= 0)) write (u, "(1x)", advance="no")
      if (col%c2(2) /= 0) write (u, "(I0)", advance="no") col%c2(2)
    end if
    write (u, "(A)", advance="no") ")"
  end if
end subroutine color_write_single

subroutine color_write_array (col, unit)
  type(color_t), dimension(:), intent(in) :: col
  integer, intent(in), optional :: unit
  integer :: u
  integer :: i
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(A)", advance="no") "["
  do i = 1, size (col)
    if (i > 1) write (u, "(1x)", advance="no")
    call color_write_single (col(i), u)
  end do
  write (u, "(A)", advance="no") "]"
end subroutine color_write_array

```

Binary I/O. For allocatable colors, this would have to be modified.

<Colors: color: TBP>+≡

```

procedure :: write_raw => color_write_raw
procedure :: read_raw => color_read_raw

```

<Colors: procedures>+≡

```

subroutine color_write_raw (col, u)
  class(color_t), intent(in) :: col
  integer, intent(in) :: u
  logical :: defined
  defined = col%is_defined () .or. col%is_ghost ()
  write (u) defined
  if (defined) then
    write (u) col%c1, col%c2
    write (u) col%ghost
  end if
end subroutine color_write_raw

```

```

subroutine color_read_raw (col, u, iostat)
  class(color_t), intent(inout) :: col
  integer, intent(in) :: u
  integer, intent(out), optional :: iostat
  logical :: defined
  read (u, iostat=iostat) col%defined
  if (col%defined) then
    read (u, iostat=iostat) col%c1, col%c2
    read (u, iostat=iostat) col%ghost
  end if
end subroutine color_read_raw

```

10.4.2 Predicates

Return the definition status. A color state may be defined but trivial.

```

<Colors: color: TBP>+≡
  procedure :: is_defined => color_is_defined
  procedure :: is_nonzero => color_is_nonzero

<Colors: procedures>+≡
  elemental function color_is_defined (col) result (defined)
    logical :: defined
    class(color_t), intent(in) :: col
    defined = col%defined
  end function color_is_defined

  elemental function color_is_nonzero (col) result (flag)
    logical :: flag
    class(color_t), intent(in) :: col
    flag = col%defined &
      .and. .not. col%ghost &
      .and. any (col%c1 /= 0 .or. col%c2 /= 0)
  end function color_is_nonzero

```

Diagonal color objects have only one array allocated:

```

<Colors: color: TBP>+≡
  procedure :: is_diagonal => color_is_diagonal

<Colors: procedures>+≡
  elemental function color_is_diagonal (col) result (diagonal)
    logical :: diagonal
    class(color_t), intent(in) :: col
    if (col%defined) then
      diagonal = all (col%c1 == col%c2)
    else
      diagonal = .true.
    end if
  end function color_is_diagonal

```

Return the ghost flag

```

<Colors: color: TBP>+≡
  procedure :: is_ghost => color_is_ghost

```

```

<Colors: procedures>+≡
  elemental function color_is_ghost (col) result (ghost)
    logical :: ghost
    class(color_t), intent(in) :: col
    ghost = col%ghost
  end function color_is_ghost

```

The ghost parity: true if the color-ghost flag is set. Again, no TBP since this is an array.

```

<Colors: procedures>+≡
  pure function color_ghost_parity (col) result (parity)
    type(color_t), dimension(:), intent(in) :: col
    logical :: parity
    parity = mod (count (col%ghost), 2) == 1
  end function color_ghost_parity

```

10.4.3 Accessing contents

Return the number of color indices. We assume that it is identical for both arrays.

```

<Colors: color: TBP>+≡
  procedure, private :: get_number_of_indices => color_get_number_of_indices

<Colors: procedures>+≡
  elemental function color_get_number_of_indices (col) result (n)
    integer :: n
    class(color_t), intent(in) :: col
    if (col%defined .and. .not. col%ghost) then
      n = count (col%c1 /= 0)
    else
      n = 0
    end if
  end function color_get_number_of_indices

```

Return the (first) color/anticolor entry (assuming that color is diagonal). The result is a positive color index.

```

<Colors: color: TBP>+≡
  procedure :: get_col => color_get_col
  procedure :: get_acl => color_get_acl

<Colors: procedures>+≡
  elemental function color_get_col (col) result (c)
    integer :: c
    class(color_t), intent(in) :: col
    integer :: i
    if (col%defined .and. .not. col%ghost) then
      do i = 1, size (col%c1)
        if (col%c1(i) > 0) then
          c = col%c1(i)
          return
        end if
      end do
    end if
  end function color_get_col

```

```

end if
c = 0
end function color_get_col

elemental function color_get_acl (col) result (c)
integer :: c
class(color_t), intent(in) :: col
integer :: i
if (col%defined .and. .not. col%ghost) then
do i = 1, size (col%c1)
if (col%c1(i) < 0) then
c = - col%c1(i)
return
end if
end do
end if
c = 0
end function color_get_acl

```

Return the color index with highest absolute value

<Colors: public>+≡

```
public :: color_get_max_value
```

<Colors: interfaces>+≡

```
interface color_get_max_value
module procedure color_get_max_value0
module procedure color_get_max_value1
module procedure color_get_max_value2
end interface color_get_max_value

```

<Colors: procedures>+≡

```

elemental function color_get_max_value0 (col) result (cmax)
integer :: cmax
type(color_t), intent(in) :: col
if (col%defined .and. .not. col%ghost) then
cmax = maxval (abs (col%c1))
else
cmax = 0
end if
end function color_get_max_value0

```

```

pure function color_get_max_value1 (col) result (cmax)
integer :: cmax
type(color_t), dimension(:), intent(in) :: col
cmax = maxval (color_get_max_value0 (col))
end function color_get_max_value1

```

```

pure function color_get_max_value2 (col) result (cmax)
integer :: cmax
type(color_t), dimension(:,:), intent(in) :: col
integer, dimension(size(col, 2)) :: cm
integer :: i
forall (i = 1:size(col, 2))
cm(i) = color_get_max_value1 (col(:,i))

```

```

end forall
cmax = maxval (cm)
end function color_get_max_value2

```

10.4.4 Comparisons

Similar to helicities, colors match if they are equal, or if either one is undefined.

```

<Colors: color: TBP>+=
generic :: operator(.match.) => color_match
generic :: operator(==) => color_eq
generic :: operator(/=) => color_neq
procedure, private :: color_match
procedure, private :: color_eq
procedure, private :: color_neq

<Colors: procedures>+=
elemental function color_match (col1, col2) result (eq)
  logical :: eq
  class(color_t), intent(in) :: col1, col2
  if (col1%defined .and. col2%defined) then
    if (col1%ghost .and. col2%ghost) then
      eq = .true.
    else if (.not. col1%ghost .and. .not. col2%ghost) then
      eq = all (col1%c1 == col2%c1) .and. all (col1%c2 == col2%c2)
    else
      eq = .false.
    end if
  else
    eq = .true.
  end if
end function color_match

elemental function color_eq (col1, col2) result (eq)
  logical :: eq
  class(color_t), intent(in) :: col1, col2
  if (col1%defined .and. col2%defined) then
    if (col1%ghost .and. col2%ghost) then
      eq = .true.
    else if (.not. col1%ghost .and. .not. col2%ghost) then
      eq = all (col1%c1 == col2%c1) .and. all (col1%c2 == col2%c2)
    else
      eq = .false.
    end if
  else if (.not. col1%defined &
    .and. .not. col2%defined) then
    eq = col1%ghost .eqv. col2%ghost
  else
    eq = .false.
  end if
end function color_eq

```

```

<Colors: procedures>+≡
  elemental function color_neq (col1, col2) result (neq)
    logical :: neq
    class(color_t), intent(in) :: col1, col2
    if (col1%defined .and. col2%defined) then
      if (col1%ghost .and. col2%ghost) then
        neq = .false.
      else if (.not. col1%ghost .and. .not. col2%ghost) then
        neq = any (col1%c1 /= col2%c1) .or. any (col1%c2 /= col2%c2)
      else
        neq = .true.
      end if
    else if (.not. col1%defined &
      .and. .not. col2%defined) then
      neq = col1%ghost .neqv. col2%ghost
    else
      neq = .true.
    end if
  end function color_neq

```

10.4.5 Tools

Shift color indices by a common offset.

```

<Colors: color: TBP>+≡
  procedure :: add_offset => color_add_offset

<Colors: procedures>+≡
  elemental subroutine color_add_offset (col, offset)
    class(color_t), intent(inout) :: col
    integer, intent(in) :: offset
    if (col%defined .and. .not. col%ghost) then
      where (col%c1 /= 0) col%c1 = col%c1 + sign (offset, col%c1)
      where (col%c2 /= 0) col%c2 = col%c2 + sign (offset, col%c2)
    end if
  end subroutine color_add_offset

```

Reassign color indices for an array of colored particle in canonical order. The allocated size of the color map is such that two colors per particle can be accommodated.

The algorithm works directly on the contents of the color objects, it

```

<Colors: public>+≡
  public :: color_canonicalize

<Colors: procedures>+≡
  subroutine color_canonicalize (col)
    type(color_t), dimension(:), intent(inout) :: col
    integer, dimension(2*size(col)) :: map
    integer :: n_col, i, j, k
    n_col = 0
    do i = 1, size (col)
      if (col(i)%defined .and. .not. col(i)%ghost) then
        do j = 1, size (col(i)%c1)

```

```

        if (col(i)%c1(j) /= 0) then
            k = find (abs (col(i)%c1(j)), map(:n_col))
            if (k == 0) then
                n_col = n_col + 1
                map(n_col) = abs (col(i)%c1(j))
                k = n_col
            end if
            col(i)%c1(j) = sign (k, col(i)%c1(j))
        end if
        if (col(i)%c2(j) /= 0) then
            k = find (abs (col(i)%c2(j)), map(:n_col))
            if (k == 0) then
                n_col = n_col + 1
                map(n_col) = abs (col(i)%c2(j))
                k = n_col
            end if
            col(i)%c2(j) = sign (k, col(i)%c2(j))
        end if
    end do
end if
end do
contains
function find (c, array) result (k)
    integer :: k
    integer, intent(in) :: c
    integer, dimension(:), intent(in) :: array
    integer :: i
    k = 0
    do i = 1, size (array)
        if (c == array (i)) then
            k = i
            return
        end if
    end do
end function find
end subroutine color_canonicalize

```

Return an array of different color indices from an array of colors. The last argument is a pseudo-color array, where the color entries correspond to the position of the corresponding index entry in the index array. The colors are assumed to be diagonal.

The algorithm works directly on the contents of the color objects.

(Colors: procedures)+≡

```

subroutine extract_color_line_indices (col, c_index, col_pos)
    type(color_t), dimension(:), intent(in) :: col
    integer, dimension(:), intent(out), allocatable :: c_index
    type(color_t), dimension(size(col)), intent(out) :: col_pos
    integer, dimension(:), allocatable :: c_tmp
    integer :: i, j, k, n, c
    allocate (c_tmp (sum (col%get_number_of_indices ())), source=0)
    n = 0
    SCAN1: do i = 1, size (col)
        if (col(i)%defined .and. .not. col(i)%ghost) then

```



```

SCAN2: do j = 1, 2
  c = abs (col(i)%c1(j))
  if (c /= 0) then
    do k = 1, n
      if (c_tmp(k) == c) then
        col_pos(i)%c1(j) = k
        cycle SCAN2
      end if
    end do
    n = n + 1
    c_tmp(n) = c
    col_pos(i)%c1(j) = n
  end if
end do SCAN2
end if
end do SCAN1
allocate (c_index (n))
c_index = c_tmp(1:n)
end subroutine extract_color_line_indices

```

Given a color array, pairwise contract the color lines in all possible ways and return the resulting array of arrays. The input color array must be diagonal, and each color should occur exactly twice, once as color and once as anticolor.

Gluon entries with equal color and anticolor are explicitly excluded.

This algorithm is generic, but for long arrays it is neither efficient, nor does it avoid duplicates. It is intended for small arrays, in particular for the state matrix of a structure-function pair.

The algorithm works directly on the contents of the color objects, it thus depends on the implementation.

(Colors: public)+≡

```
public :: color_array_make_contractions
```

(Colors: procedures)+≡

```

subroutine color_array_make_contractions (col_in, col_out)
  type(color_t), dimension(:), intent(in) :: col_in
  type(color_t), dimension(:, :), intent(out), allocatable :: col_out
  type :: entry_t
    integer, dimension(:), allocatable :: map
    type(color_t), dimension(:), allocatable :: col
    type(entry_t), pointer :: next => null ()
    logical :: nlo_event = .false.
  end type entry_t
  type :: list_t
    integer :: n = 0
    type(entry_t), pointer :: first => null ()
    type(entry_t), pointer :: last => null ()
  end type list_t
  type(list_t) :: list
  type(entry_t), pointer :: entry
  integer, dimension(:), allocatable :: c_index
  type(color_t), dimension(size(col_in)) :: col_pos
  integer :: n_prt, n_c_index
  integer, dimension(:), allocatable :: map

```

```

integer :: i, j, c
n_prt = size (col_in)
call extract_color_line_indices (col_in, c_index, col_pos)
! print *, c_index      !!! Debugging
n_c_index = size (c_index)
allocate (map (n_c_index))
map = 0
call list_append_if_valid (list, map)
entry => list%first
do while (associated (entry))
  do i = 1, n_c_index
    if (entry%map(i) == 0) then
      c = c_index(i)
      do j = i + 1, n_c_index
        if (entry%map(j) == 0) then
          map = entry%map
          map(i) = c
          map(j) = c
          call list_append_if_valid (list, map)
        end if
      end do
    end if
  end do
  entry => entry%next
end do
call list_to_array (list, col_out)
contains
subroutine list_append_if_valid (list, map)
  type(list_t), intent(inout) :: list
  integer, dimension(:), intent(in) :: map
  type(entry_t), pointer :: entry
  integer :: i, j, c, p
  entry => list%first
  do while (associated (entry))
    if (all (map == entry%map)) return
    entry => entry%next
  end do
  allocate (entry)
  allocate (entry%map (n_c_index))
  entry%map = map
  allocate (entry%col (n_prt))
  do i = 1, n_prt
    do j = 1, 2
      c = col_in(i)%c1(j)
      if (c /= 0) then
        p = col_pos(i)%c1(j)
        entry%col(i)%defined = .true.
        if (map(p) /= 0) then
          entry%col(i)%c1(j) = sign (map(p), c)
        else
          entry%col(i)%c1(j) = c
        endif
        entry%col(i)%c2(j) = entry%col(i)%c1(j)
      end if
    end do
  end do
end if

```

```

        end do
        if (any (entry%col(i)%c1 /= 0) .and. &
            entry%col(i)%c1(1) == - entry%col(i)%c1(2)) return
    end do
    ! call color_write (entry%col); print *, map      !!! Debugging
    if (associated (list%last)) then
        list%last%next => entry
    else
        list%first => entry
    end if
    list%last => entry
    list%n = list%n + 1
end subroutine list_append_if_valid
subroutine list_to_array (list, col)
    type(list_t), intent(inout) :: list
    type(color_t), dimension(:, :), intent(out), allocatable :: col
    type(entry_t), pointer :: entry
    integer :: i
    allocate (col (n_prt, list%n - 1))
    do i = 0, list%n - 1
        entry => list%first
        list%first => list%first%next
        if (i /= 0) col(:, i) = entry%col
        deallocate (entry)
    end do
    list%last => null ()
end subroutine list_to_array
end subroutine color_array_make_contractions

```

Invert the color index, switching from particle to antiparticle. For gluons, we have to swap the order of color entries.

```

<Colors: color: TBP>+≡
    procedure :: invert => color_invert

<Colors: procedures>+≡
    elemental subroutine color_invert (col)
        class(color_t), intent(inout) :: col
        if (col%defined .and. .not. col%ghost) then
            col%c1 = - col%c1
            col%c2 = - col%c2
            if (col%c1(1) < 0 .and. col%c1(2) > 0) then
                col%c1 = col%c1(2:1:-1)
                col%c2 = col%c2(2:1:-1)
            end if
        end if
    end subroutine color_invert

```

Make a color map for two matching color arrays. The result is an array of integer pairs.

```

<Colors: public>+≡
    public :: make_color_map

<Colors: interfaces>+≡
    interface make_color_map

```

```

    module procedure color_make_color_map
end interface make_color_map

```

<Colors: procedures>+≡

```

subroutine color_make_color_map (map, col1, col2)
    integer, dimension(:,:), intent(out), allocatable :: map
    type(color_t), dimension(:), intent(in) :: col1, col2
    integer, dimension(:,:), allocatable :: map1
    integer :: i, j, k
    allocate (map1 (2, 2 * sum (col1%get_number_of_indices ())))
    k = 0
    do i = 1, size (col1)
        if (col1(i)%defined .and. .not. col1(i)%ghost) then
            do j = 1, size (col1(i)%c1)
                if (col1(i)%c1(j) /= 0 &
                    .and. all (map1(1,:k) /= abs (col1(i)%c1(j)))) then
                    k = k + 1
                    map1(1,k) = abs (col1(i)%c1(j))
                    map1(2,k) = abs (col2(i)%c1(j))
                end if
                if (col1(i)%c2(j) /= 0 &
                    .and. all (map1(1,:k) /= abs (col1(i)%c2(j)))) then
                    k = k + 1
                    map1(1,k) = abs (col1(i)%c2(j))
                    map1(2,k) = abs (col2(i)%c2(j))
                end if
            end do
        end do
    end do
    allocate (map (2, k))
    map(:, :) = map1(:, :k)
end subroutine color_make_color_map

```

Translate colors which have a match in the translation table (an array of integer pairs). Color that do not match an entry are simply transferred; this is done by first transferring all components, then modifying entries where appropriate.

<Colors: public>+≡

```

    public :: color_translate

```

<Colors: interfaces>+≡

```

interface color_translate
    module procedure color_translate0
    module procedure color_translate0_offset
    module procedure color_translate1
end interface color_translate

```

<Colors: procedures>+≡

```

subroutine color_translate0 (col, map)
    type(color_t), intent(inout) :: col
    integer, dimension(:,:), intent(in) :: map
    type(color_t) :: col_tmp
    integer :: i
    if (col%defined .and. .not. col%ghost) then

```

```

        col_tmp = col
        do i = 1, size (map,2)
            where (abs (col%c1) == map(1,i))
                col_tmp%c1 = sign (map(2,i), col%c1)
            end where
            where (abs (col%c2) == map(1,i))
                col_tmp%c2 = sign (map(2,i), col%c2)
            end where
        end do
        col = col_tmp
    end if
end subroutine color_translate0

subroutine color_translate0_offset (col, map, offset)
    type(color_t), intent(inout) :: col
    integer, dimension(:,:), intent(in) :: map
    integer, intent(in) :: offset
    logical, dimension(size(col%c1)) :: mask1, mask2
    type(color_t) :: col_tmp
    integer :: i
    if (col%defined .and. .not. col%ghost) then
        col_tmp = col
        mask1 = col%c1 /= 0
        mask2 = col%c2 /= 0
        do i = 1, size (map,2)
            where (abs (col%c1) == map(1,i))
                col_tmp%c1 = sign (map(2,i), col%c1)
                mask1 = .false.
            end where
            where (abs (col%c2) == map(1,i))
                col_tmp%c2 = sign (map(2,i), col%c2)
                mask2 = .false.
            end where
        end do
        col = col_tmp
        where (mask1) col%c1 = sign (abs (col%c1) + offset, col%c1)
        where (mask2) col%c2 = sign (abs (col%c2) + offset, col%c2)
    end if
end subroutine color_translate0_offset

subroutine color_translate1 (col, map, offset)
    type(color_t), dimension(:), intent(inout) :: col
    integer, dimension(:,:), intent(in) :: map
    integer, intent(in), optional :: offset
    integer :: i
    if (present (offset)) then
        do i = 1, size (col)
            call color_translate0_offset (col(i), map, offset)
        end do
    else
        do i = 1, size (col)
            call color_translate0 (col(i), map)
        end do
    end if
end if

```

```
end subroutine color_translate1
```

Merge two color objects by taking the first entry from the first and the first entry from the second argument. Makes sense only if the input colors are defined (and diagonal). If either one is undefined, transfer the defined one.

```
<Colors: color: TBP>+≡
  generic :: operator(.merge.) => merge_colors
  procedure, private :: merge_colors

<Colors: procedures>+≡
  elemental function merge_colors (col1, col2) result (col)
    type(color_t) :: col
    class(color_t), intent(in) :: col1, col2
    if (color_is_defined (col1) .and. color_is_defined (col2)) then
      if (color_is_ghost (col1) .and. color_is_ghost (col2)) then
        call color_init_trivial_ghost (col, .true.)
      else
        call color_init_arrays (col, col1%c1, col2%c1)
      end if
    else if (color_is_defined (col1)) then
      call color_init_array (col, col1%c1)
    else if (color_is_defined (col2)) then
      call color_init_array (col, col2%c1)
    end if
  end function merge_colors
```

Compute the color factor, given two interfering color arrays.

```
<Colors: public>+≡
  public :: compute_color_factor

<Colors: procedures>+≡
  function compute_color_factor (col1, col2, nc) result (factor)
    real(default) :: factor
    type(color_t), dimension(:), intent(in) :: col1, col2
    integer, intent(in), optional :: nc
    type(color_t), dimension(size(col1)) :: col
    integer :: ncol, nloops, nghost
    ncol = 3; if (present (nc)) ncol = nc
    col = col1 .merge. col2
    nloops = count_color_loops (col)
    nghost = count (col%is_ghost ())
    factor = real (ncol, default) ** (nloops - nghost)
    if (color_ghost_parity (col)) factor = - factor
  end function compute_color_factor
```

We have a pair of color index arrays which corresponds to a squared matrix element. We want to determine the number of color loops in this square matrix element. So we first copy the colors (stored in a single color array with a pair of color lists in each entry) to a temporary where the color indices are shifted by some offset. We then recursively follow each loop, starting at the first color that has the offset, resetting the first color index to the loop index and each further index to zero as we go. We check that (a) each color index occurs twice

within the left (right) color array, (b) the loops are closed, so we always come back to a line which has the loop index.

In order for the algorithm to work we have to conjugate the colors of initial state particles (one for decays, two for scatterings) into their corresponding anticolors of outgoing particles.

```

<Colors: public>+≡
    public :: count_color_loops

<Colors: procedures>+≡
    function count_color_loops (col) result (count)
        integer :: count
        type(color_t), dimension(:), intent(in) :: col
        type(color_t), dimension(size(col)) :: cc
        integer :: i, n, offset
        ! print *, "Count color loops:"      !!! Debugging
        ! call color_write (col); print *    !!! Debugging
        cc = col
        n = size (cc)
        offset = n
        call color_add_offset (cc, offset)
        ! print *, offset                    !!! Debugging
        ! call color_write (cc); print *    !!! Debugging
        count = 0
        SCAN_LOOPS: do
            do i = 1, n
                ! print *, i, ':', cc(i)%c1  !!! Debugging
                if (color_is_nonzero (cc(i))) then
                    if (any (cc(i)%c1 > offset)) then
                        ! print *, 'start', i  !!! Debugging
                        count = count + 1
                        call follow_line1 (pick_new_line (cc(i)%c1, count, 1))
                        cycle SCAN_LOOPS
                    end if
                end if
            end do
            exit SCAN_LOOPS
        end do SCAN_LOOPS
contains
    function pick_new_line (c, reset_val, sgn) result (line)
        integer :: line
        integer, dimension(:), intent(inout) :: c
        integer, intent(in) :: reset_val
        integer, intent(in) :: sgn
        integer :: i
        if (any (c == count)) then
            line = count
        else
            do i = 1, size (c)
                if (sign (1, c(i)) == sgn .and. abs (c(i)) > offset) then
                    line = c(i)
                    c(i) = reset_val
                    return
                end if
            end do
        end if
    end function pick_new_line

```

```

        call color_mismatch
    end if
end function pick_new_line
subroutine reset_line (c, line)
    integer, dimension(:), intent(inout) :: c
    integer, intent(in) :: line
    integer :: i
    do i = 1, size (c)
        if (c(i) == line) then
            c(i) = 0
            return
        end if
    end do
end subroutine reset_line
recursive subroutine follow_line1 (line)
    integer, intent(in) :: line
    integer :: i
    ! print *, 'follow line 1:', line      !!! Debugging
    if (line == count) then
        ! print *, 'loop closed'          !!! Debugging
        return
    end if
    do i = 1, n
        if (any (cc(i)%c1 == -line)) then
            call reset_line (cc(i)%c1, -line)
            ! print *, 'found', -line, ' resetting c1:'  !!! Debugging
            ! call color_write (cc); print *              !!! Debugging
            call follow_line2 (pick_new_line (cc(i)%c2, 0, sign (1, -line)))
            return
        end if
    end do
    call color_mismatch ()
end subroutine follow_line1
recursive subroutine follow_line2 (line)
    integer, intent(in) :: line
    integer :: i
    ! print *, 'follow line 2:', line      !!! Debugging
    do i = 1, n
        if (any (cc(i)%c2 == -line)) then
            call reset_line (cc(i)%c2, -line)
            ! print *, 'found', -line, ' resetting c2:'  !!! Debugging
            ! call color_write (cc); print *              !!! Debugging
            call follow_line1 (pick_new_line (cc(i)%c1, 0, sign (1, -line)))
            return
        end if
    end do
    call color_mismatch ()
end subroutine follow_line2
subroutine color_mismatch ()
    call color_write (col)
    print *
    call msg_bug (" Color flow mismatch (color loops should be closed)")
end subroutine color_mismatch
end function count_color_loops

```


10.4.6 Unit tests

```
<Colors: public>+≡
    public :: color_test

<Colors: procedures>+≡
    subroutine color_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Colors: execute tests>
    end subroutine color_test
```

This is a color counting test.

```
<Colors: execute tests>≡
    call test (color_1, "color_1", &
        "check color counting", &
        u, results)

<Colors: tests>≡
    subroutine color_1 (u)
        integer, intent(in) :: u
        type(color_t), dimension(4) :: col1, col2, col
        type(color_t), dimension(:), allocatable :: col3
        type(color_t), dimension(:,:), allocatable :: col_array
        integer :: count, i
        call col1%init_col_acl ([1, 0, 2, 3], [0, 1, 3, 2])
        col2 = col1
        call color_write (col1, u)
        write (u, "(A)")
        call color_write (col2, u)
        write (u, "(A)")
        col = col1 .merge. col2
        call color_write (col, u)
        write (u, "(A)")
        count = count_color_loops (col)
        write (u, "(A,I1)") "Number of color loops (3): ", count
        call col2%init_col_acl ([1, 0, 2, 3], [0, 2, 3, 1])
        call color_write (col1, u)
        write (u, "(A)")
        call color_write (col2, u)
        write (u, "(A)")
        col = col1 .merge. col2
        call color_write (col, u)
        write (u, "(A)")
        count = count_color_loops (col)
        write (u, "(A,I1)") "Number of color loops (2): ", count
        write (u, "(A)")
        allocate (col3 (4))
        call color_init_from_array (col3, &
            reshape ([1, 0, 0, -1, 2, -3, 3, -2], &
                [2, 4]))
        call color_write (col3, u)
```

```

write (u, "(A)")
call color_array_make_contractions (col3, col_array)
write (u, "(A)") "Contractions:"
do i = 1, size (col_array, 2)
    call color_write (col_array(:,i), u)
    write (u, "(A)")
end do
deallocate (col3)
write (u, "(A)")
allocate (col3 (6))
call color_init_from_array (col3, &
    reshape ([1, -2, 3, 0, 0, -1, 2, -4, -3, 0, 4, 0], &
    [2, 6]))
call color_write (col3, u)
write (u, "(A)")
call color_array_make_contractions (col3, col_array)
write (u, "(A)") "Contractions:"
do i = 1, size (col_array, 2)
    call color_write (col_array(:,i), u)
    write (u, "(A)")
end do
end subroutine color_1

```

10.4.7 The Madgraph color model

This section describes the method for matrix element and color flow calculation within Madgraph.

For each Feynman diagram, the colorless amplitude for a specified helicity and momentum configuration (in- and out- combined) is computed:

$$A_d(p, h) \quad (10.1)$$

Inserting color, the squared matrix element for definite helicity and momentum is

$$M^2(p, h) = \sum_{dd'} A_d(p, h) C_{dd'} A_{d'}^*(p, h) \quad (10.2)$$

where $C_{dd'}$ describes the color interference of the two diagrams A_d and $A_{d'}$, which is independent of momentum and helicity and can be calculated for each Feynman diagram pair by reducing it to the corresponding color graph. Obviously, one could combine all diagrams with identical color structure, such that the index d runs only over different color graphs. For colorless diagrams all elements of $C_{dd'}$ are equal to unity.

The hermitian matrix $C_{dd'}$ is diagonalized once and for all, such that it can be written in the form

$$C_{dd'} = \sum_{\lambda} c_d^{\lambda} \lambda c_{d'}^{\lambda*}, \quad (10.3)$$

where the eigenvectors c_d are normalized,

$$\sum_d |c_d^{\lambda}|^2 = 1, \quad (10.4)$$

and the λ values are the corresponding eigenvalues. In the colorless case, this means $c_d = 1/\sqrt{N_d}$ for all diagrams (N_d = number of diagrams), and $\lambda = N_d$ is the only nonzero eigenvalue.

Consequently, the squared matrix element for definite helicity and momentum can also be written as

$$M^2(p, h) = \sum_{\lambda} A_{\lambda}(p, h) \lambda A_{\lambda}(p, h)^* \quad (10.5)$$

with

$$A_{\lambda}(p, h) = \sum_d c_d^{\lambda} A_d(p, h). \quad (10.6)$$

For generic spin density matrices, this is easily generalized to

$$M^2(p, h, h') = \sum_{\lambda} A_{\lambda}(p, h) \lambda A_{\lambda}(p, h')^* \quad (10.7)$$

To determine the color flow probabilities of a given momentum-helicity configuration, the color flow amplitudes are calculated as

$$a_f(p, h) = \sum_d \beta_d^f A_d(p, h), \quad (10.8)$$

where the coefficients β_d^f describe the amplitude for a given Feynman diagram (or color graph) d to correspond to a definite color flow f . They are computed from $C_{dd'}$ by transforming this matrix into the color flow basis and neglecting all off-diagonal elements. Again, these coefficients do not depend on momentum or helicity and can therefore be calculated in advance. This gives the color flow transition matrix

$$F^f(p, h, h') = a_f(p, h) a_f^*(p, h') \quad (10.9)$$

which is assumed diagonal in color flow space and is separate from the color-summed transition matrix M^2 . They are, however, equivalent (up to a factor) to leading order in $1/N_c$, and using the color flow transition matrix is appropriate for matching to hadronization.

Note that the color flow transition matrix is not normalized at this stage. To make use of it, we have to fold it with the in-state density matrix to get a pseudo density matrix

$$\hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h'_{\text{out}}) = \sum_{h_{\text{in}} h'_{\text{in}}} F^f(p, h, h') \rho_{\text{in}}(p, h_{\text{in}}, h'_{\text{in}}) \quad (10.10)$$

which gets a meaning only after contracted with projections on the outgoing helicity states k_{out} , given as linear combinations of helicity states with the unitary coefficient matrix $c(k_{\text{out}}, h_{\text{out}})$. Then the probability of finding color flow f when the helicity state k_{out} is measured is given by

$$P^f(p, k_{\text{out}}) = Q^f(p, k_{\text{out}}) / \sum_f Q^f(p, k_{\text{out}}) \quad (10.11)$$

where

$$Q^f(p, k_{\text{out}}) = \sum_{h_{\text{out}} h'_{\text{out}}} c(k_{\text{out}}, h_{\text{out}}) \hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h'_{\text{out}}) c^*(k_{\text{out}}, h'_{\text{out}}) \quad (10.12)$$

However, if we can assume that the out-state helicity basis is the canonical one, we can throw away the off diagonal elements in the color flow density matrix and normalize the ones on the diagonal to obtain

$$P^f(p, h_{\text{out}}) = \hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h_{\text{out}}) / \sum_f \hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h_{\text{out}}) \quad (10.13)$$

Finally, the color-summed out-state density matrix is computed by the scattering formula

$$\rho_{\text{out}}(p, h_{\text{out}}, h'_{\text{out}}) = \sum_{h_{\text{in}} h'_{\text{in}}} M^2(p, h, h') \rho_{\text{in}}(p, h_{\text{in}}, h'_{\text{in}}) \quad (10.14)$$

$$= \sum_{h_{\text{in}} h'_{\text{in}} \lambda} A_\lambda(p, h) \lambda A_\lambda(p, h')^* \rho_{\text{in}}(p, h_{\text{in}}, h'_{\text{in}}), \quad (10.15)$$

The trace of ρ_{out} is the squared matrix element, summed over all internal degrees of freedom. To get the squared matrix element for a definite helicity k_{out} and color flow f , one has to project the density matrix onto the given helicity state and multiply with $P^f(p, k_{\text{out}})$.

For diagonal helicities the out-state density reduces to

$$\rho_{\text{out}}(p, h_{\text{out}}) = \sum_{h_{\text{in}} \lambda} \lambda |A_\lambda(p, h)|^2 \rho_{\text{in}}(p, h_{\text{in}}). \quad (10.16)$$

Since no basis transformation is involved, we can use the normalized color flow probability $P^f(p, h_{\text{out}})$ and express the result as

$$\rho_{\text{out}}^f(p, h_{\text{out}}) = \rho_{\text{out}}(p, h_{\text{out}}) P^f(p, h_{\text{out}}) \quad (10.17)$$

$$= \sum_{h_{\text{in}} \lambda} \frac{|a^f(p, h)|^2}{\sum_f |a^f(p, h)|^2} \lambda |A_\lambda(p, h)|^2 \rho_{\text{in}}(p, h_{\text{in}}). \quad (10.18)$$

From these considerations, the following calculation strategy can be derived:

- Before the first event is generated, the color interference matrix $C_{dd'}$ is computed and diagonalized, so the eigenvectors c_d^λ , eigenvalues λ and color flow coefficients β_d^f are obtained. In practice, these calculations are done when the matrix element code is generated, and the results are hardcoded in the matrix element subroutine as **DATA** statements.
- For each event, one loops over helicities once and stores the matrices $A_\lambda(p, h)$ and $a^f(p, h)$. The allowed color flows, helicity combinations and eigenvalues are each labeled by integer indices, so one has to store complex matrices of dimension $N_\lambda \times N_h$ and $N_f \times N_h$, respectively.
- The further strategy depends on the requested information.
 1. If colorless diagonal helicity amplitudes are required, the eigenvalues $A_\lambda(p, h)$ are squared, summed with weight λ , and the result contracted with the in-state probability vector $\rho_{\text{in}}(p, h_{\text{in}})$. The result is a probability vector $\rho_{\text{out}}(p, h_{\text{out}})$.

2. For colored diagonal helicity amplitudes, the color coefficients $a^f(p, h)$ are also squared and used as weights to obtain the color-flow probability vector $\rho_{\text{out}}^f(p, h_{\text{out}})$.
3. For colorless non-diagonal helicity amplitudes, we contract the tensor product of $A_\lambda(p, h)$ with $A_\lambda(p, h')$, weighted with λ , with the correlated in-state density matrix, to obtain a correlated out-state density matrix.
4. In the general (colored, non-diagonal) case, we do the same as in the colorless case, but return the un-normalized color flow density matrix $\hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h'_{\text{out}})$ in addition. When the relevant helicity basis is known, the latter can be used by the caller program to determine flow probabilities. (In reality, we assume the canonical basis and reduce the correlated out-state density to its diagonal immediately.)

10.5 Flavors: Particle properties

This module contains a type for holding the flavor code, and all functions that depend on the model, i.e., that determine particle properties.

The PDG code is packed in a special **flavor** type. (This prohibits meaningless operations, and it allows for a different implementation, e.g., some non-PDG scheme internally, if appropriate at some point.)

There are lots of further particle properties that depend on the model. Implementing a flyweight pattern, the associated field data object is to be stored in a central area, the **flavor** object just receives a pointer to this, so all queries can be delegated.

```
<flavors.f90>≡  
<File header>
```

```
module flavors
```

```
<Use kinds>
```

```
<Use strings>
```

```
  use io_units
```

```
  use diagnostics
```

```
  use physics_defs, only: UNDEFINED
```

```
  use physics_defs, only: INVALID
```

```
  use physics_defs, only: HADRON_REMNANT
```

```
  use physics_defs, only: HADRON_REMNANT_SINGLET
```

```
  use physics_defs, only: HADRON_REMNANT_TRIPLET
```

```
  use physics_defs, only: HADRON_REMNANT_OCTET
```

```
  use model_data
```

```
  use colors, only: color_t
```

```
<Standard module head>
```

```
<Flavors: public>
```

```
<Flavors: types>
```

```
<Flavors: interfaces>
```

```
contains
```

```
<Flavors: procedures>
```

```
end module flavors
```

10.5.1 The flavor type

The flavor type is an integer representing the PDG code, or undefined (zero). Negative codes represent ant flavors. They should be used only for particles which do have a distinct antiparticle.

The **radiated** flag can be set for particles that are the result of a beam-structure interaction (hadron beam remnant, ISR photon, etc.), not of the hard interaction itself.

Further properties of the given flavor can be retrieved via the particle-data pointer, if it is associated.

```

<Flavors: public>≡
    public :: flavor_t

<Flavors: types>≡
    type :: flavor_t
        private
            integer :: f = UNDEFINED
            logical :: radiated = .false.
            type(field_data_t), pointer :: field_data => null ()
        contains
            <Flavors: flavor: TBP>
        end type flavor_t

```

Initializer form. If the model is assigned, the procedure is impure, therefore we have to define a separate array version.

Note: The pure elemental subroutines can't have an intent(out) CLASS argument (because of the potential for an impure finalizer in a type extension), so we stick to intent(inout) and (re)set all components explicitly.

```

<Flavors: flavor: TBP>≡
    generic :: init => &
        flavor_init0_empty, &
        flavor_init0, &
        flavor_init0_field_data, &
        flavor_init0_model, &
        flavor_init0_model_alt, &
        flavor_init0_name_model
    procedure, private :: flavor_init0_empty
    procedure, private :: flavor_init0
    procedure, private :: flavor_init0_field_data
    procedure, private :: flavor_init0_model
    procedure, private :: flavor_init0_model_alt
    procedure, private :: flavor_init0_name_model

<Flavors: procedures>≡
    elemental subroutine flavor_init0_empty (flv)
        class(flavor_t), intent(inout) :: flv
        flv%f = UNDEFINED
        flv%radiated = .false.
        flv%field_data => null ()
    end subroutine flavor_init0_empty

    elemental subroutine flavor_init0 (flv, f)
        class(flavor_t), intent(inout) :: flv
        integer, intent(in) :: f
        flv%f = f
        flv%radiated = .false.
        flv%field_data => null ()
    end subroutine flavor_init0

    impure elemental subroutine flavor_init0_field_data (flv, field_data)
        class(flavor_t), intent(inout) :: flv
        type(field_data_t), intent(in), target :: field_data

```

```

        flv%f = field_data%get_pdg ()
        flv%radiated = .false.
        flv%field_data => field_data
    end subroutine flavor_init0_field_data

    impure elemental subroutine flavor_init0_model (flv, f, model)
        class(flavor_t), intent(inout) :: flv
        integer, intent(in) :: f
        class(model_data_t), intent(in), target :: model
        flv%f = f
        flv%radiated = .false.
        flv%field_data => model%get_field_ptr (f, check=.true.)
    end subroutine flavor_init0_model

    impure elemental subroutine flavor_init0_model_alt (flv, f, model, alt_model)
        class(flavor_t), intent(inout) :: flv
        integer, intent(in) :: f
        class(model_data_t), intent(in), target :: model, alt_model
        flv%f = f
        flv%radiated = .false.
        flv%field_data => model%get_field_ptr (f, check=.false.)
        if (.not. associated (flv%field_data)) then
            flv%field_data => alt_model%get_field_ptr (f, check=.false.)
            if (.not. associated (flv%field_data)) then
                write (msg_buffer, "(A,1x,I0,1x,A,1x,A,1x,A,1x,A)") &
                    "Particle with code", f, &
                    "found neither in model", char (model%get_name ()), &
                    "nor in model", char (alt_model%get_name ())
                call msg_fatal ()
            end if
        end if
    end subroutine flavor_init0_model_alt

!   subroutine flavor_init1_model (flv, f, model)
!       type(flavor_t), dimension(:), intent(out) :: flv
!       integer, dimension(:), intent(in) :: f
!       class(model_data_t), intent(in), target :: model
!       integer :: i
!       do i = 1, size (f)
!           call flavor_init0_model (flv(i), f(i), model)
!       end do
!   end subroutine flavor_init1_model
!
!   subroutine flavor_init1_model_alt (flv, f, model, alt_model)
!       type(flavor_t), dimension(:), intent(out) :: flv
!       integer, dimension(:), intent(in) :: f
!       class(model_data_t), intent(in), target :: model, alt_model
!       integer :: i
!       do i = 1, size (f)
!           call flavor_init0_model_alt (flv(i), f(i), model, alt_model)
!       end do
!   end subroutine flavor_init1_model_alt
!
!   subroutine flavor_init2_model (flv, f, model)

```



```

!      type(flavor_t), dimension(:,:), intent(out) :: flv
!      integer, dimension(:,:), intent(in) :: f
!      class(model_data_t), intent(in), target :: model
!      integer :: i
!      do i = 1, size (f, 2)
!          call flavor_init1_model (flv(:,i), f(:,i), model)
!      end do
!  end subroutine flavor_init2_model
!
!  subroutine flavor_init2_model_alt (flv, f, model, alt_model)
!      type(flavor_t), dimension(:,:), intent(out) :: flv
!      integer, dimension(:,:), intent(in) :: f
!      class(model_data_t), intent(in), target :: model, alt_model
!      integer :: i
!      do i = 1, size (f, 2)
!          call flavor_init1_model_alt (flv(:,i), f(:,i), model, alt_model)
!      end do
!  end subroutine flavor_init2_model_alt
!
!  impure elemental subroutine flavor_init0_name_model (flv, name, model)
!      class(flavor_t), intent(inout) :: flv
!      type(string_t), intent(in) :: name
!      class(model_data_t), intent(in), target :: model
!      flv%f = model%get_pdg (name)
!      flv%radiated = .false.
!      flv%field_data => model%get_field_ptr (name, check=.true.)
!  end subroutine flavor_init0_name_model
!
!  subroutine flavor_init1_name_model (flv, name, model)
!      type(flavor_t), dimension(:), intent(out) :: flv
!      type(string_t), dimension(:), intent(in) :: name
!      class(model_data_t), intent(in), target :: model
!      integer :: i
!      do i = 1, size (name)
!          call flavor_init0_name_model (flv(i), name(i), model)
!      end do
!  end subroutine flavor_init1_name_model

```

Set the radiated flag.

```

<Flavors: flavor: TBP>+≡
    procedure :: tag_radiated => flavor_tag_radiated

<Flavors: procedures>+≡
    elemental subroutine flavor_tag_radiated (flv)
        class(flavor_t), intent(inout) :: flv
        flv%radiated = .true.
    end subroutine flavor_tag_radiated

```

Undefine the flavor state:

```

<Flavors: flavor: TBP>+≡
    procedure :: undefine => flavor_undefine

<Flavors: procedures>+≡
    elemental subroutine flavor_undefine (flv)

```

```

class(flavor_t), intent(inout) :: flv
flv%f = UNDEFINED
flv%field_data => null ()
end subroutine flavor_undefine

```

Output: dense, no linebreak

```

<Flavors: flavor: TBP>+≡
  procedure :: write => flavor_write

<Flavors: procedures>+≡
  subroutine flavor_write (flv, unit)
    class(flavor_t), intent(in) :: flv
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    if (associated (flv%field_data)) then
      write (u, "(A)", advance="no") "f("
    else
      write (u, "(A)", advance="no") "p("
    end if
    write (u, "(I0)", advance="no") flv%f
    if (flv%radiated) then
      write (u, "('*)", advance="no")
    end if
    write (u, "(A)", advance="no") ")"
  end subroutine flavor_write

```

Binary I/O. Currently, the model information is not written/read, so after reading the particle-data pointer is empty.

```

<Flavors: flavor: TBP>+≡
  procedure :: write_raw => flavor_write_raw
  procedure :: read_raw => flavor_read_raw

<Flavors: procedures>+≡
  subroutine flavor_write_raw (flv, u)
    class(flavor_t), intent(in) :: flv
    integer, intent(in) :: u
    write (u) flv%f
    write (u) flv%radiated
  end subroutine flavor_write_raw

  subroutine flavor_read_raw (flv, u, iostat)
    class(flavor_t), intent(out) :: flv
    integer, intent(in) :: u
    integer, intent(out), optional :: iostat
    read (u, iostat=iostat) flv%f
    if (present (iostat)) then
      if (iostat /= 0) return
    end if
    read (u, iostat=iostat) flv%radiated
  end subroutine flavor_read_raw

```

Assignment

Default assignment of flavor objects is possible, but cannot be used in pure procedures, because a pointer assignment is involved.

Assign the particle pointer separately. This cannot be elemental, so we define a scalar and an array version explicitly. We refer to an array of flavors, not an array of models.

```
<Flavors: flavor: TBP>+≡
  procedure :: set_model => flavor_set_model_single

<Flavors: procedures>+≡
  impure elemental subroutine flavor_set_model_single (flv, model)
    class(flavor_t), intent(inout) :: flv
    class(model_data_t), intent(in), target :: model
    if (flv%f /= UNDEFINED) &
      flv%field_data => model%get_field_ptr (flv%f)
  end subroutine flavor_set_model_single
```

Predicates

Return the definition status. By definition, the flavor object is defined if the flavor PDG code is nonzero.

```
<Flavors: flavor: TBP>+≡
  procedure :: is_defined => flavor_is_defined

<Flavors: procedures>+≡
  elemental function flavor_is_defined (flv) result (defined)
    class(flavor_t), intent(in) :: flv
    logical :: defined
    defined = flv%f /= UNDEFINED
  end function flavor_is_defined
```

Check for valid flavor (including undefined). This is distinct from the `is_defined` status. Invalid flavor is actually a specific PDG code.

```
<Flavors: flavor: TBP>+≡
  procedure :: is_valid => flavor_is_valid

<Flavors: procedures>+≡
  elemental function flavor_is_valid (flv) result (valid)
    class(flavor_t), intent(in) :: flv
    logical :: valid
    valid = flv%f /= INVALID
  end function flavor_is_valid
```

Return true if the particle-data pointer is associated. (Debugging aid)

```
<Flavors: flavor: TBP>+≡
  procedure :: is_associated => flavor_is_associated

<Flavors: procedures>+≡
  elemental function flavor_is_associated (flv) result (flag)
    class(flavor_t), intent(in) :: flv
    logical :: flag
    flag = associated (flv%field_data)
```

```
end function flavor_is_associated
```

Check the **radiated** flag. A radiated particle has a definite PDG flavor status, but it is actually a pseudoparticle (a beam remnant) which may be subject to fragmentation.

```
<Flavors: flavor: TBP>+≡
  procedure :: is_radiated => flavor_is_radiated

<Flavors: procedures>+≡
  elemental function flavor_is_radiated (flv) result (flag)
    class(flavor_t), intent(in) :: flv
    logical :: flag
    flag = flv%radiated
  end function flavor_is_radiated
```

Accessing contents

With the exception of the PDG code, all particle property enquiries are delegated to the **field_data** pointer. If this is unassigned, some access function will crash.

Return the flavor as an integer

```
<Flavors: flavor: TBP>+≡
  procedure :: get_pdg => flavor_get_pdg

<Flavors: procedures>+≡
  elemental function flavor_get_pdg (flv) result (f)
    integer :: f
    class(flavor_t), intent(in) :: flv
    f = flv%f
  end function flavor_get_pdg
```

Return the flavor of the antiparticle

```
<Flavors: flavor: TBP>+≡
  procedure :: get_pdg_anti => flavor_get_pdg_anti

<Flavors: procedures>+≡
  elemental function flavor_get_pdg_anti (flv) result (f)
    integer :: f
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
      if (flv%field_data%has_antiparticle ()) then
        f = -flv%f
      else
        f = flv%f
      end if
    else
      f = 0
    end if
  end function flavor_get_pdg_anti
```

Absolute value:

```
(Flavors: flavor: TBP)+≡  
  procedure :: get_pdg_abs => flavor_get_pdg_abs  
  
(Flavors: procedures)+≡  
  elemental function flavor_get_pdg_abs (flv) result (f)  
    integer :: f  
    class(flavor_t), intent(in) :: flv  
    f = abs (flv%f)  
  end function flavor_get_pdg_abs
```

Generic properties

```
(Flavors: flavor: TBP)+≡  
  procedure :: is_visible => flavor_is_visible  
  procedure :: is_parton => flavor_is_parton  
  procedure :: is_beam_remnant => flavor_is_beam_remnant  
  procedure :: is_gauge => flavor_is_gauge  
  procedure :: is_left_handed => flavor_is_left_handed  
  procedure :: is_right_handed => flavor_is_right_handed  
  procedure :: is_antiparticle => flavor_is_antiparticle  
  procedure :: has_antiparticle => flavor_has_antiparticle  
  procedure :: is_stable => flavor_is_stable  
  procedure :: get_decays => flavor_get_decays  
  procedure :: decays_isotropically => flavor_decays_isotropically  
  procedure :: decays_diagonal => flavor_decays_diagonal  
  procedure :: has_decay_helicity => flavor_has_decay_helicity  
  procedure :: get_decay_helicity => flavor_get_decay_helicity  
  procedure :: is_polarized => flavor_is_polarized  
  
(Flavors: procedures)+≡  
  elemental function flavor_is_visible (flv) result (flag)  
    logical :: flag  
    class(flavor_t), intent(in) :: flv  
    if (associated (flv%field_data)) then  
      flag = flv%field_data%is_visible ()  
    else  
      flag = .false.  
    end if  
  end function flavor_is_visible  
  
  elemental function flavor_is_parton (flv) result (flag)  
    logical :: flag  
    class(flavor_t), intent(in) :: flv  
    if (associated (flv%field_data)) then  
      flag = flv%field_data%is_parton ()  
    else  
      flag = .false.  
    end if  
  end function flavor_is_parton  
  
  elemental function flavor_is_beam_remnant (flv) result (flag)  
    logical :: flag  
    class(flavor_t), intent(in) :: flv  
    select case (abs (flv%f))
```

```

        case (HADRON_REMNANT, &
              HADRON_REMNANT_SINGLET, HADRON_REMNANT_TRIPLET, HADRON_REMNANT_OCTET)
            flag = .true.
        case default
            flag = .false.
        end select
    end function flavor_is_beam_remnant

    elemental function flavor_is_gauge (flv) result (flag)
        logical :: flag
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            flag = flv%field_data%is_gauge ()
        else
            flag = .false.
        end if
    end function flavor_is_gauge

    elemental function flavor_is_left_handed (flv) result (flag)
        logical :: flag
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            if (flv%f > 0) then
                flag = flv%field_data%is_left_handed ()
            else
                flag = flv%field_data%is_right_handed ()
            end if
        else
            flag = .false.
        end if
    end function flavor_is_left_handed

    elemental function flavor_is_right_handed (flv) result (flag)
        logical :: flag
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            if (flv%f > 0) then
                flag = flv%field_data%is_right_handed ()
            else
                flag = flv%field_data%is_left_handed ()
            end if
        else
            flag = .false.
        end if
    end function flavor_is_right_handed

    elemental function flavor_is_antiparticle (flv) result (flag)
        logical :: flag
        class(flavor_t), intent(in) :: flv
        flag = flv%f < 0
    end function flavor_is_antiparticle

    elemental function flavor_has_antiparticle (flv) result (flag)
        logical :: flag

```

```

class(flavor_t), intent(in) :: flv
if (associated (flv%field_data)) then
    flag = flv%field_data%has_antiparticle ()
else
    flag = .false.
end if
end function flavor_has_antiparticle

elemental function flavor_is_stable (flv) result (flag)
logical :: flag
class(flavor_t), intent(in) :: flv
if (associated (flv%field_data)) then
    flag = flv%field_data%is_stable (anti = flv%f < 0)
else
    flag = .true.
end if
end function flavor_is_stable

subroutine flavor_get_decays (flv, decay)
class(flavor_t), intent(in) :: flv
type(string_t), dimension(:), intent(out), allocatable :: decay
logical :: anti
anti = flv%f < 0
if (.not. flv%field_data%is_stable (anti)) then
    call flv%field_data%get_decays (decay, anti)
end if
end subroutine flavor_get_decays

elemental function flavor_decays_isotropically (flv) result (flag)
logical :: flag
class(flavor_t), intent(in) :: flv
if (associated (flv%field_data)) then
    flag = flv%field_data%decays_isotropically (anti = flv%f < 0)
else
    flag = .true.
end if
end function flavor_decays_isotropically

elemental function flavor_decays_diagonal (flv) result (flag)
logical :: flag
class(flavor_t), intent(in) :: flv
if (associated (flv%field_data)) then
    flag = flv%field_data%decays_diagonal (anti = flv%f < 0)
else
    flag = .true.
end if
end function flavor_decays_diagonal

elemental function flavor_has_decay_helicity (flv) result (flag)
logical :: flag
class(flavor_t), intent(in) :: flv
if (associated (flv%field_data)) then
    flag = flv%field_data%has_decay_helicity (anti = flv%f < 0)
else

```

```

        flag = .false.
    end if
end function flavor_has_decay_helicity

elemental function flavor_get_decay_helicity (flv) result (hel)
    integer :: hel
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
        hel = flv%field_data%decay_helicity (anti = flv%f < 0)
    else
        hel = 0
    end if
end function flavor_get_decay_helicity

elemental function flavor_is_polarized (flv) result (flag)
    logical :: flag
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
        flag = flv%field_data%is_polarized (anti = flv%f < 0)
    else
        flag = .false.
    end if
end function flavor_is_polarized

```

Names:

$\langle \text{Flavors: flavor: TBP} \rangle + \equiv$

```

    procedure :: get_name => flavor_get_name
    procedure :: get_tex_name => flavor_get_tex_name

```

$\langle \text{Flavors: procedures} \rangle + \equiv$

```

    elemental function flavor_get_name (flv) result (name)
        type(string_t) :: name
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            name = flv%field_data%get_name (flv%f < 0)
        else
            name = "?"
        end if
    end function flavor_get_name

    elemental function flavor_get_tex_name (flv) result (name)
        type(string_t) :: name
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            name = flv%field_data%get_tex_name (flv%f < 0)
        else
            name = "?"
        end if
    end function flavor_get_tex_name

```

$\langle \text{Flavors: flavor: TBP} \rangle + \equiv$

```

    procedure :: get_spin_type => flavor_get_spin_type
    procedure :: get_multiplicity => flavor_get_multiplicity
    procedure :: get_isospin_type => flavor_get_isospin_type

```



```

procedure :: get_charge_type => flavor_get_charge_type
procedure :: get_color_type => flavor_get_color_type

(Flavors: procedures)+=
  elemental function flavor_get_spin_type (flv) result (type)
    integer :: type
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
      type = flv%field_data%get_spin_type ()
    else
      type = 1
    end if
  end function flavor_get_spin_type

  elemental function flavor_get_multiplicity (flv) result (type)
    integer :: type
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
      type = flv%field_data%get_multiplicity ()
    else
      type = 1
    end if
  end function flavor_get_multiplicity

  elemental function flavor_get_isospin_type (flv) result (type)
    integer :: type
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
      type = flv%field_data%get_isospin_type ()
    else
      type = 1
    end if
  end function flavor_get_isospin_type

  elemental function flavor_get_charge_type (flv) result (type)
    integer :: type
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
      type = flv%field_data%get_charge_type ()
    else
      type = 1
    end if
  end function flavor_get_charge_type

  elemental function flavor_get_color_type (flv) result (type)
    integer :: type
    class(flavor_t), intent(in) :: flv
    if (associated (flv%field_data)) then
      if (flavor_is_antiparticle (flv)) then
        type = - flv%field_data%get_color_type ()
      else
        type = flv%field_data%get_color_type ()
      end if
    end if
    select case (type)
    case (-1,-8); type = abs (type)
  end function flavor_get_color_type

```

```

        end select
    else
        type = 1
    end if
end function flavor_get_color_type

```

These functions return real values:

```

<Flavors: flavor: TBP>+=
    procedure :: get_charge => flavor_get_charge
    procedure :: get_mass => flavor_get_mass
    procedure :: get_width => flavor_get_width
    procedure :: get_isospin => flavor_get_isospin

<Flavors: procedures>+=
    elemental function flavor_get_charge (flv) result (charge)
        real(default) :: charge
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            if (flavor_is_antiparticle (flv)) then
                charge = flv%field_data%get_charge ()
            else
                charge = - flv%field_data%get_charge ()
            end if
        else
            charge = 0
        end if
    end function flavor_get_charge

    elemental function flavor_get_mass (flv) result (mass)
        real(default) :: mass
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            mass = flv%field_data%get_mass ()
        else
            mass = 0
        end if
    end function flavor_get_mass

    elemental function flavor_get_width (flv) result (width)
        real(default) :: width
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            width = flv%field_data%get_width ()
        else
            width = 0
        end if
    end function flavor_get_width

    elemental function flavor_get_isospin (flv) result (isospin)
        real(default) :: isospin
        class(flavor_t), intent(in) :: flv
        if (associated (flv%field_data)) then
            if (flavor_is_antiparticle (flv)) then
                isospin = flv%field_data%get_isospin ()
            end if
        else
            isospin = 0
        end if
    end function flavor_get_isospin

```

```

        else
            isospin = - flv%field_data%get_isospin ()
        end if
    else
        isospin = 0
    end if
end function flavor_get_isospin

```

Comparisons

If one of the flavors is undefined, the other defined, they match.

(Flavors: flavor: TBP)+≡

```

generic :: operator(.match.) => flavor_match
generic :: operator(==) => flavor_eq
generic :: operator(/=) => flavor_neq
procedure, private :: flavor_match
procedure, private :: flavor_eq
procedure, private :: flavor_neq

```

(Flavors: procedures)+≡

```

elemental function flavor_match (flv1, flv2) result (eq)
    logical :: eq
    class(flavor_t), intent(in) :: flv1, flv2
    if (flv1%f /= UNDEFINED .and. flv2%f /= UNDEFINED) then
        eq = flv1%f == flv2%f
    else
        eq = .true.
    end if
end function flavor_match

elemental function flavor_eq (flv1, flv2) result (eq)
    logical :: eq
    class(flavor_t), intent(in) :: flv1, flv2
    if (flv1%f /= UNDEFINED .and. flv2%f /= UNDEFINED) then
        eq = flv1%f == flv2%f
    else if (flv1%f == UNDEFINED .and. flv2%f == UNDEFINED) then
        eq = .true.
    else
        eq = .false.
    end if
end function flavor_eq

```

(Flavors: procedures)+≡

```

elemental function flavor_neq (flv1, flv2) result (neq)
    logical :: neq
    class(flavor_t), intent(in) :: flv1, flv2
    if (flv1%f /= UNDEFINED .and. flv2%f /= UNDEFINED) then
        neq = flv1%f /= flv2%f
    else if (flv1%f == UNDEFINED .and. flv2%f == UNDEFINED) then
        neq = .false.
    else
        neq = .true.
    end if

```

```
end function flavor_neq
```

Tools

Merge two flavor indices. This works only if both are equal or either one is undefined, because we have no off-diagonal flavor entries. Otherwise, generate an invalid flavor.

We cannot use elemental procedures because of the pointer component.

```
(Flavors: public)+≡
  public :: operator(.merge.)

(Flavors: interfaces)≡
  interface operator(.merge.)
    module procedure merge_flavors0
    module procedure merge_flavors1
  end interface

(Flavors: procedures)+≡
  function merge_flavors0 (flv1, flv2) result (flv)
    type(flavor_t) :: flv
    type(flavor_t), intent(in) :: flv1, flv2
    if (flavor_is_defined (flv1) .and. flavor_is_defined (flv2)) then
      if (flv1 == flv2) then
        flv = flv1
      else
        flv%f = INVALID
      end if
    else if (flavor_is_defined (flv1)) then
      flv = flv1
    else if (flavor_is_defined (flv2)) then
      flv = flv2
    end if
  end function merge_flavors0

  function merge_flavors1 (flv1, flv2) result (flv)
    type(flavor_t), dimension(:), intent(in) :: flv1, flv2
    type(flavor_t), dimension(size(flv1)) :: flv
    integer :: i
    do i = 1, size (flv1)
      flv(i) = flv1(i) .merge. flv2(i)
    end do
  end function merge_flavors1
```

Generate consecutive color indices for a given flavor. The indices are counted starting with the stored value of *c*, so new indices are created each time this (impure) function is called. The counter can be reset by the optional argument *c_seed* if desired. The optional flag **reverse** is used only for octets. If set, the color and anticolor entries of the octet particle are exchanged.

```
(Flavors: public)+≡
  public :: color_from_flavor
```

```

<Flavors: interfaces>+≡
  interface color_from_flavor
    module procedure color_from_flavor0
    module procedure color_from_flavor1
  end interface
<Flavors: procedures>+≡
  function color_from_flavor0 (flv, c_seed, reverse) result (col)
    type(color_t) :: col
    type(flavor_t), intent(in) :: flv
    integer, intent(in), optional :: c_seed
    logical, intent(in), optional :: reverse
    integer, save :: c = 1
    logical :: rev
    if (present (c_seed)) c = c_seed
    rev = .false.; if (present (reverse)) rev = reverse
    select case (flavor_get_color_type (flv))
    case (1)
      call col%init ()
    case (3)
      call col%init ([c]); c = c + 1
    case (-3)
      call col%init ([-c]); c = c + 1
    case (8)
      if (rev) then
        call col%init ([c+1, -c]); c = c + 2
      else
        call col%init ([c, -(c+1)]); c = c + 2
      end if
    end select
  end function color_from_flavor0

  function color_from_flavor1 (flv, c_seed, reverse) result (col)
    type(flavor_t), dimension(:), intent(in) :: flv
    integer, intent(in), optional :: c_seed
    logical, intent(in), optional :: reverse
    type(color_t), dimension(size(flv)) :: col
    integer :: i
    col(1) = color_from_flavor0 (flv(1), c_seed, reverse)
    do i = 2, size (flv)
      col(i) = color_from_flavor0 (flv(i), reverse=reverse)
    end do
  end function color_from_flavor1

```

This procedure returns the flavor object for the antiparticle. The antiparticle code may either be the same code or its negative.

```

<Flavors: flavor: TBP>+≡
  procedure :: anti => flavor_anti
<Flavors: procedures>+≡
  function flavor_anti (flv) result (aflv)
    type(flavor_t) :: aflv
    class(flavor_t), intent(in) :: flv
    if (flavor_has_antiparticle (flv)) then
      aflv%f = - flv%f
    end if
  end function flavor_anti

```

```
else
    aflv%f = flv%f
end if
aflv%field_data => flv%field_data
end function flavor_anti
```

10.6 Quantum numbers

This module collects helicity, color, and flavor in a single type and defines procedures

```
<quantum_numbers.f90>≡  
  <File header>  
  
  module quantum_numbers  
  
    use io_units  
    use model_data  
    use helicities  
    use colors  
    use flavors  
  
    <Standard module head>  
  
    <Quantum numbers: public>  
  
    <Quantum numbers: types>  
  
    <Quantum numbers: interfaces>  
  
    contains  
  
    <Quantum numbers: procedures>  
  
  end module quantum_numbers
```

10.6.1 The quantum number type

```
<Quantum numbers: public>≡  
  public :: quantum_numbers_t  
  
<Quantum numbers: types>≡  
  type :: quantum_numbers_t  
    private  
    type(flavor_t) :: f  
    type(color_t) :: c  
    type(helicity_t) :: h  
    contains  
    <Quantum numbers: quantum numbers: TBP>  
  end type quantum_numbers_t
```

Define quantum numbers: Initializer form. All arguments may be present or absent.

Some elemental initializers are impure because they set the `flv` component. This implies transfer of a pointer behind the scenes.

```
<Quantum numbers: quantum numbers: TBP>≡  
  generic :: init => &  
    quantum_numbers_init0_f, &  
    quantum_numbers_init0_c, &  
    quantum_numbers_init0_h, &
```

```

        quantum_numbers_init0_fc, &
        quantum_numbers_init0_fh, &
        quantum_numbers_init0_ch, &
        quantum_numbers_init0_fch
    procedure, private :: quantum_numbers_init0_f
    procedure, private :: quantum_numbers_init0_c
    procedure, private :: quantum_numbers_init0_h
    procedure, private :: quantum_numbers_init0_fc
    procedure, private :: quantum_numbers_init0_fh
    procedure, private :: quantum_numbers_init0_ch
    procedure, private :: quantum_numbers_init0_fch
<Quantum numbers: procedures>≡
    impure elemental subroutine quantum_numbers_init0_f (qn, flv)
        class(quantum_numbers_t), intent(inout) :: qn
        type(flavor_t), intent(in) :: flv
        qn%f = flv
        call qn%c%undefine ()
        call qn%h%undefine ()
    end subroutine quantum_numbers_init0_f

    elemental subroutine quantum_numbers_init0_c (qn, col)
        class(quantum_numbers_t), intent(inout) :: qn
        type(color_t), intent(in) :: col
        call qn%f%undefine ()
        qn%c = col
        call qn%h%undefine ()
    end subroutine quantum_numbers_init0_c

    elemental subroutine quantum_numbers_init0_h (qn, hel)
        class(quantum_numbers_t), intent(inout) :: qn
        type(helicity_t), intent(in) :: hel
        call qn%f%undefine ()
        call qn%c%undefine ()
        qn%h = hel
    end subroutine quantum_numbers_init0_h

    impure elemental subroutine quantum_numbers_init0_fc (qn, flv, col)
        class(quantum_numbers_t), intent(inout) :: qn
        type(flavor_t), intent(in) :: flv
        type(color_t), intent(in) :: col
        qn%f = flv
        qn%c = col
        call qn%h%undefine ()
    end subroutine quantum_numbers_init0_fc

    impure elemental subroutine quantum_numbers_init0_fh (qn, flv, hel)
        class(quantum_numbers_t), intent(inout) :: qn
        type(flavor_t), intent(in) :: flv
        type(helicity_t), intent(in) :: hel
        qn%f = flv
        call qn%c%undefine ()
        qn%h = hel
    end subroutine quantum_numbers_init0_fh

```



```

elemental subroutine quantum_numbers_init0_ch (qn, col, hel)
  class(quantum_numbers_t), intent(inout) :: qn
  type(color_t), intent(in) :: col
  type(helicity_t), intent(in) :: hel
  call qn%f%undefine ()
  qn%c = col
  qn%h = hel
end subroutine quantum_numbers_init0_ch

impure elemental subroutine quantum_numbers_init0_fch (qn, flv, col, hel)
  class(quantum_numbers_t), intent(inout) :: qn
  type(flavor_t), intent(in) :: flv
  type(color_t), intent(in) :: col
  type(helicity_t), intent(in) :: hel
  qn%f = flv
  qn%c = col
  qn%h = hel
end subroutine quantum_numbers_init0_fch

```

10.6.2 I/O

Write the quantum numbers in condensed form, enclosed by square brackets. Color is written only if nontrivial. For convenience, introduce also an array version.

If the `col_verbose` option is set, show the quantum number color also if it is zero, but defined. Otherwise, suppress zero color.

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_write

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: write => quantum_numbers_write_single

<Quantum numbers: interfaces>≡
  interface quantum_numbers_write
    module procedure quantum_numbers_write_single
    module procedure quantum_numbers_write_array
  end interface

<Quantum numbers: procedures>+≡
  subroutine quantum_numbers_write_single (qn, unit, col_verbose)
    class(quantum_numbers_t), intent(in) :: qn
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: col_verbose
    integer :: u
    logical :: col_verb
    u = given_output_unit (unit); if (u < 0) return
    col_verb = .false.; if (present (col_verbose)) col_verb = col_verbose
    write (u, "(A)", advance="no") "["
    if (qn%f%is_defined ()) then
      call qn%f%write (u)
      if (qn%c%is_nonzero () .or. qn%h%is_defined ()) &
        write (u, "(1x)", advance="no")
    end if
    if (col_verb) then

```

```

        if (qn%c%is_defined () .or. qn%c%is_ghost ()) then
            call color_write (qn%c, u)
            if (qn%h%is_defined ()) write (u, "(1x)", advance="no")
        end if
    else
        if (qn%c%is_nonzero () .or. qn%c%is_ghost ()) then
            call color_write (qn%c, u)
            if (qn%h%is_defined ()) write (u, "(1x)", advance="no")
        end if
    end if
    if (qn%h%is_defined ()) then
        call qn%h%write (u)
    end if
    write (u, "(A)", advance="no") "]"
end subroutine quantum_numbers_write_single

subroutine quantum_numbers_write_array (qn, unit, col_verbose)
    type(quantum_numbers_t), dimension(:), intent(in) :: qn
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: col_verbose
    integer :: i
    integer :: u
    logical :: col_verb
    u = given_output_unit (unit); if (u < 0) return
    col_verb = .false.; if (present (col_verbose)) col_verb = col_verbose
    write (u, "(A)", advance="no") "["
    do i = 1, size (qn)
        if (i > 1) write (u, "(A)", advance="no") " / "
        if (qn(i)%f%is_defined ()) then
            call qn(i)%f%write (u)
            if (qn(i)%c%is_nonzero () .or. qn(i)%h%is_defined ()) &
                write (u, "(1x)", advance="no")
        end if
        if (col_verb) then
            if (qn(i)%c%is_defined () .or. qn(i)%c%is_ghost ()) then
                call color_write (qn(i)%c, u)
                if (qn(i)%h%is_defined ()) write (u, "(1x)", advance="no")
            end if
        else
            if (qn(i)%c%is_nonzero () .or. qn(i)%c%is_ghost ()) then
                call color_write (qn(i)%c, u)
                if (qn(i)%h%is_defined ()) write (u, "(1x)", advance="no")
            end if
        end if
        if (qn(i)%h%is_defined ()) then
            call qn(i)%h%write (u)
        end if
    end do
    write (u, "(A)", advance="no") "]"
end subroutine quantum_numbers_write_array

```

Binary I/O.

$\langle \text{Quantum numbers: quantum numbers: TBP} \rangle + \equiv$

```

procedure :: write_raw => quantum_numbers_write_raw
procedure :: read_raw => quantum_numbers_read_raw

<Quantum numbers: procedures>+≡
  subroutine quantum_numbers_write_raw (qn, u)
    class(quantum_numbers_t), intent(in) :: qn
    integer, intent(in) :: u
    call qn%f%write_raw (u)
    call qn%c%write_raw (u)
    call qn%h%write_raw (u)
  end subroutine quantum_numbers_write_raw

  subroutine quantum_numbers_read_raw (qn, u, iostat)
    class(quantum_numbers_t), intent(out) :: qn
    integer, intent(in) :: u
    integer, intent(out), optional :: iostat
    call qn%f%read_raw (u, iostat=iostat)
    call qn%c%read_raw (u, iostat=iostat)
    call qn%h%read_raw (u, iostat=iostat)
  end subroutine quantum_numbers_read_raw

```

10.6.3 Accessing contents

Color and helicity can be done by elemental functions. Flavor needs impure elemental. We export also the functions directly, this allows us to avoid temporaries in some places.

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_get_flavor
  public :: quantum_numbers_get_color
  public :: quantum_numbers_get_helicity

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: get_flavor => quantum_numbers_get_flavor
  procedure :: get_color => quantum_numbers_get_color
  procedure :: get_helicity => quantum_numbers_get_helicity

<Quantum numbers: procedures>+≡
  impure elemental function quantum_numbers_get_flavor (qn) result (flv)
    type(flavor_t) :: flv
    class(quantum_numbers_t), intent(in) :: qn
    flv = qn%f
  end function quantum_numbers_get_flavor

  elemental function quantum_numbers_get_color (qn) result (col)
    type(color_t) :: col
    class(quantum_numbers_t), intent(in) :: qn
    col = qn%c
  end function quantum_numbers_get_color

  elemental function quantum_numbers_get_helicity (qn) result (hel)
    type(helicity_t) :: hel
    class(quantum_numbers_t), intent(in) :: qn
    hel = qn%h
  end function quantum_numbers_get_helicity

```

This just resets the ghost property of the color part:

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: set_color_ghost => quantum_numbers_set_color_ghost

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_set_color_ghost (qn, ghost)
    class(quantum_numbers_t), intent(inout) :: qn
    logical, intent(in) :: ghost
    call qn%c%set_ghost (ghost)
  end subroutine quantum_numbers_set_color_ghost

```

Assign a model to the flavor part of quantum numbers.

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: set_model => quantum_numbers_set_model

<Quantum numbers: procedures>+≡
  impure elemental subroutine quantum_numbers_set_model (qn, model)
    class(quantum_numbers_t), intent(inout) :: qn
    class(model_data_t), intent(in), target :: model
    call qn%f%set_model (model)
  end subroutine quantum_numbers_set_model

```

Set the radiated flag for the flavor component.

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: tag_radiated => quantum_numbers_tag_radiated

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_tag_radiated (qn)
    class(quantum_numbers_t), intent(inout) :: qn
    call qn%f%tag_radiated ()
  end subroutine quantum_numbers_tag_radiated

```

This is a convenience function: return the color type for the flavor (array).

Note: keep the public version temporarily, this will be used in a complicated expression which triggers a compiler bug (nagfor 5.3) in the TBP version.

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_get_color_type

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: get_color_type => quantum_numbers_get_color_type

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_get_color_type (qn) result (color_type)
    integer :: color_type
    class(quantum_numbers_t), intent(in) :: qn
    color_type = qn%f%get_color_type ()
  end function quantum_numbers_get_color_type

```

10.6.4 Predicates

Check if the flavor index is valid (including UNDEFINED).

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: are_valid => quantum_numbers_are_valid

```

```

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_are_valid (qn) result (valid)
    logical :: valid
    class(quantum_numbers_t), intent(in) :: qn
    valid = qn%f%is_valid ()
  end function quantum_numbers_are_valid

```

Check if the flavor part has its particle-data pointer associated (debugging aid).

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: are_associated => quantum_numbers_are_associated

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_are_associated (qn) result (flag)
    logical :: flag
    class(quantum_numbers_t), intent(in) :: qn
    flag = qn%f%is_associated ()
  end function quantum_numbers_are_associated

```

Check if the helicity and color quantum numbers are diagonal. (Unpolarized/colorless also counts as diagonal.) Flavor is diagonal by definition.

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: are_diagonal => quantum_numbers_are_diagonal

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_are_diagonal (qn) result (diagonal)
    logical :: diagonal
    class(quantum_numbers_t), intent(in) :: qn
    diagonal = qn%h%is_diagonal () .and. qn%c%is_diagonal ()
  end function quantum_numbers_are_diagonal

```

Check if the color part has the ghost property.

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: is_color_ghost => quantum_numbers_is_color_ghost

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_is_color_ghost (qn) result (ghost)
    logical :: ghost
    class(quantum_numbers_t), intent(in) :: qn
    ghost = qn%c%is_ghost ()
  end function quantum_numbers_is_color_ghost

```

10.6.5 Comparisons

Matching and equality is derived from the individual quantum numbers. The variant `fhmatch` matches only flavor and helicity. The variant `dhmatch` matches only diagonal helicity, if the matching helicity is undefined.

```

<Quantum numbers: quantum numbers: TBP>+≡
  generic :: operator(.match.) => quantum_numbers_match
  generic :: operator(.fmatch.) => quantum_numbers_match_f
  generic :: operator(.fhmatch.) => quantum_numbers_match_fh
  generic :: operator(.dhmatch.) => quantum_numbers_match_hel_diag

```

```

generic :: operator(==) => quantum_numbers_eq
generic :: operator(/=) => quantum_numbers_neq
procedure, private :: quantum_numbers_match
procedure, private :: quantum_numbers_match_f
procedure, private :: quantum_numbers_match_fh
procedure, private :: quantum_numbers_match_hel_diag
procedure, private :: quantum_numbers_eq
procedure, private :: quantum_numbers_neq

(Quantum numbers: procedures) +=
  elemental function quantum_numbers_match (qn1, qn2) result (match)
    logical :: match
    class(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f) .and. &
             (qn1%c .match. qn2%c) .and. &
             (qn1%h .match. qn2%h)
  end function quantum_numbers_match

  elemental function quantum_numbers_match_f (qn1, qn2) result (match)
    logical :: match
    class(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f)
  end function quantum_numbers_match_f

  elemental function quantum_numbers_match_fh (qn1, qn2) result (match)
    logical :: match
    class(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f) .and. &
             (qn1%h .match. qn2%h)
  end function quantum_numbers_match_fh

  elemental function quantum_numbers_match_hel_diag (qn1, qn2) result (match)
    logical :: match
    class(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f) .and. &
             (qn1%c .match. qn2%c) .and. &
             (qn1%h .dmatch. qn2%h)
  end function quantum_numbers_match_hel_diag

  elemental function quantum_numbers_eq (qn1, qn2) result (eq)
    logical :: eq
    class(quantum_numbers_t), intent(in) :: qn1, qn2
    eq = (qn1%f == qn2%f) .and. &
          (qn1%c == qn2%c) .and. &
          (qn1%h == qn2%h)
  end function quantum_numbers_eq

  elemental function quantum_numbers_neq (qn1, qn2) result (neq)
    logical :: neq
    class(quantum_numbers_t), intent(in) :: qn1, qn2
    neq = (qn1%f /= qn2%f) .or. &
           (qn1%c /= qn2%c) .or. &
           (qn1%h /= qn2%h)
  end function quantum_numbers_neq

```

Two sets of quantum numbers are compatible if the individual quantum numbers are compatible, depending on the mask. Flavor has to match, regardless of the flavor mask.

If the color flag is set, color is compatible if the ghost property is identical. If the color flag is unset, color has to be identical. I.e., if the flag is set, the color amplitudes can interfere. If it is not set, they must be identical, and there must be no ghost. The latter property is used for expanding physical color flows.

Helicity is compatible if the mask is unset, otherwise it has to match. This determines if two amplitudes can be multiplied (no mask) or traced (mask).

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_are_compatible

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_are_compatible (qn1, qn2, mask) &
        result (flag)
        logical :: flag
        type(quantum_numbers_t), intent(in) :: qn1, qn2
        type(quantum_numbers_mask_t), intent(in) :: mask
        if (mask%h .or. mask%hd) then
            flag = (qn1%f .match. qn2%f) .and. (qn1%h .match. qn2%h)
        else
            flag = (qn1%f .match. qn2%f)
        end if
        if (mask%c) then
            flag = flag .and. (qn1%c%is_ghost () .eqv. qn2%c%is_ghost ())
        else
            flag = flag .and. &
                .not. (qn1%c%is_ghost () .or. qn2%c%is_ghost ()) .and. &
                (qn1%c == qn2%c)
        end if
    end function quantum_numbers_are_compatible

```

This is the analog for a single quantum-number set. We just check for color ghosts; they are excluded if the color mask is unset (color-flow expansion).

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_are_physical

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_are_physical (qn, mask) result (flag)
        logical :: flag
        type(quantum_numbers_t), intent(in) :: qn
        type(quantum_numbers_mask_t), intent(in) :: mask
        if (mask%c) then
            flag = .true.
        else
            flag = .not. qn%c%is_ghost ()
        end if
    end function quantum_numbers_are_physical

```

10.6.6 Operations

Inherited from the color component: reassign color indices in canonical order.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_canonicalize_color

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_canonicalize_color (qn)
        type(quantum_numbers_t), dimension(:), intent(inout) :: qn
        call color_canonicalize (qn%c)
    end subroutine quantum_numbers_canonicalize_color

```

Inherited from the color component: make a color map for two matching quantum-number arrays.

```

<Quantum numbers: public>+≡
    public :: make_color_map

<Quantum numbers: interfaces>+≡
    interface make_color_map
        module procedure quantum_numbers_make_color_map
    end interface make_color_map

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_make_color_map (map, qn1, qn2)
        integer, dimension(:,:), intent(out), allocatable :: map
        type(quantum_numbers_t), dimension(:), intent(in) :: qn1, qn2
        call make_color_map (map, qn1%c, qn2%c)
    end subroutine quantum_numbers_make_color_map

```

Inherited from the color component: translate the color part using a color-map array

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_translate_color

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_translate_color
        module procedure quantum_numbers_translate_color0
        module procedure quantum_numbers_translate_color1
    end interface

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_translate_color0 (qn, map, offset)
        type(quantum_numbers_t), intent(inout) :: qn
        integer, dimension(:,:), intent(in) :: map
        integer, intent(in), optional :: offset
        call color_translate (qn%c, map, offset)
    end subroutine quantum_numbers_translate_color0

    subroutine quantum_numbers_translate_color1 (qn, map, offset)
        type(quantum_numbers_t), dimension(:), intent(inout) :: qn
        integer, dimension(:,:), intent(in) :: map
        integer, intent(in), optional :: offset
        call color_translate (qn%c, map, offset)
    end subroutine quantum_numbers_translate_color1

```


Inherited from the color component: return the color index with highest absolute value.

Since the algorithm is not elemental, we keep the separate procedures for different array rank.

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_get_max_color_value

<Quantum numbers: interfaces>+≡
  interface quantum_numbers_get_max_color_value
    module procedure quantum_numbers_get_max_color_value0
    module procedure quantum_numbers_get_max_color_value1
    module procedure quantum_numbers_get_max_color_value2
  end interface

<Quantum numbers: procedures>+≡
  pure function quantum_numbers_get_max_color_value0 (qn) result (cmax)
    integer :: cmax
    type(quantum_numbers_t), intent(in) :: qn
    cmax = color_get_max_value (qn%c)
  end function quantum_numbers_get_max_color_value0

  pure function quantum_numbers_get_max_color_value1 (qn) result (cmax)
    integer :: cmax
    type(quantum_numbers_t), dimension(:), intent(in) :: qn
    cmax = color_get_max_value (qn%c)
  end function quantum_numbers_get_max_color_value1

  pure function quantum_numbers_get_max_color_value2 (qn) result (cmax)
    integer :: cmax
    type(quantum_numbers_t), dimension(:,,:), intent(in) :: qn
    cmax = color_get_max_value (qn%c)
  end function quantum_numbers_get_max_color_value2

```

Inherited from the color component: add an offset to the indices of the color part

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: add_color_offset => quantum_numbers_add_color_offset

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_add_color_offset (qn, offset)
    class(quantum_numbers_t), intent(inout) :: qn
    integer, intent(in) :: offset
    call qn%c%add_offset (offset)
  end subroutine quantum_numbers_add_color_offset

```

Given a quantum number array, return all possible color contractions, leaving the other quantum numbers intact.

```

<Quantum numbers: public>+≡
  public :: quantum_number_array_make_color_contractions

<Quantum numbers: procedures>+≡
  subroutine quantum_number_array_make_color_contractions (qn_in, qn_out)
    type(quantum_numbers_t), dimension(:), intent(in) :: qn_in

```

```

    type(quantum_numbers_t), dimension(:,:), intent(out), allocatable :: qn_out
    type(color_t), dimension(:,:), allocatable :: col
    integer :: i
    call color_array_make_contractions (qn_in%c, col)
    allocate (qn_out (size (col, 1), size (col, 2)))
    do i = 1, size (qn_out, 2)
        qn_out(:,i)%f = qn_in%f
        qn_out(:,i)%c = col(:,i)
        qn_out(:,i)%h = qn_in%h
    end do
end subroutine quantum_number_array_make_color_contractions

```

Inherited from the color component: invert the color, switching particle/antiparticle.

```

<Quantum numbers: quantum numbers: TBP>+≡
    procedure :: invert_color => quantum_numbers_invert_color

<Quantum numbers: procedures>+≡
    elemental subroutine quantum_numbers_invert_color (qn)
        class(quantum_numbers_t), intent(inout) :: qn
        call qn%c%invert ()
    end subroutine quantum_numbers_invert_color

```

Merge two quantum number sets: for each entry, if both are defined, combine them to an off-diagonal entry (meaningful only if the input was diagonal). If either entry is undefined, take the defined one.

For flavor, off-diagonal entries are invalid, so both flavors must be equal, otherwise an invalid flavor is inserted.

```

<Quantum numbers: public>+≡
    public :: operator(.merge.)

<Quantum numbers: interfaces>+≡
    interface operator(.merge.)
        module procedure merge_quantum_numbers0
        module procedure merge_quantum_numbers1
    end interface

<Quantum numbers: procedures>+≡
    function merge_quantum_numbers0 (qn1, qn2) result (qn3)
        type(quantum_numbers_t) :: qn3
        type(quantum_numbers_t), intent(in) :: qn1, qn2
        qn3%f = qn1%f .merge. qn2%f
        qn3%c = qn1%c .merge. qn2%c
        qn3%h = qn1%h .merge. qn2%h
    end function merge_quantum_numbers0

    function merge_quantum_numbers1 (qn1, qn2) result (qn3)
        type(quantum_numbers_t), dimension(:), intent(in) :: qn1, qn2
        type(quantum_numbers_t), dimension(size(qn1)) :: qn3
        qn3%f = qn1%f .merge. qn2%f
        qn3%c = qn1%c .merge. qn2%c
        qn3%h = qn1%h .merge. qn2%h
    end function merge_quantum_numbers1

```

10.6.7 The quantum number mask

The quantum numbers mask is true for quantum numbers that should be ignored or summed over. The three mandatory entries correspond to flavor, color, and helicity, respectively.

There is an additional entry `cg`: If false, the color-ghosts property should be kept even if color is ignored. This is relevant only if `c` is set, otherwise it is always false.

The flag `hd` tells that only diagonal entries in helicity should be kept. If `h` is set, `hd` is irrelevant and will be kept `.false.`

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_mask_t

<Quantum numbers: types>+≡
    type :: quantum_numbers_mask_t
        private
        logical :: f = .false.
        logical :: c = .false.
        logical :: cg = .false.
        logical :: h = .false.
        logical :: hd = .false.
    contains
    <Quantum numbers: quantum numbers mask: TBP>
end type quantum_numbers_mask_t

```

Define a quantum number mask: Constructor form

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_mask

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_mask &
        (mask_f, mask_c, mask_h, mask_cg, mask_hd) result (mask)
    type(quantum_numbers_mask_t) :: mask
    logical, intent(in) :: mask_f, mask_c, mask_h
    logical, intent(in), optional :: mask_cg
    logical, intent(in), optional :: mask_hd
    call quantum_numbers_mask_init &
        (mask, mask_f, mask_c, mask_h, mask_cg, mask_hd)
end function quantum_numbers_mask

```

Define quantum numbers: Initializer form

```

<Quantum numbers: quantum numbers mask: TBP>≡
    procedure :: init => quantum_numbers_mask_init

<Quantum numbers: procedures>+≡
    elemental subroutine quantum_numbers_mask_init &
        (mask, mask_f, mask_c, mask_h, mask_cg, mask_hd)
    class(quantum_numbers_mask_t), intent(inout) :: mask
    logical, intent(in) :: mask_f, mask_c, mask_h
    logical, intent(in), optional :: mask_cg, mask_hd
    mask%f = mask_f
    mask%c = mask_c
    mask%h = mask_h
    mask%cg = .false.

```

```

    if (present (mask_cg)) then
        if (mask%c) mask%cg = mask_cg
    else
        mask%cg = mask_c
    end if
    mask%hd = .false.
    if (present (mask_hd)) then
        if (.not. mask%h) mask%hd = mask_hd
    end if
end subroutine quantum_numbers_mask_init

```

Write a quantum numbers mask. We need the stand-alone subroutine for the array case.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_mask_write

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_mask_write
        module procedure quantum_numbers_mask_write_single
        module procedure quantum_numbers_mask_write_array
    end interface

<Quantum numbers: quantum numbers mask: TBP>+≡
    procedure :: write => quantum_numbers_mask_write_single

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_mask_write_single (mask, unit)
        class(quantum_numbers_mask_t), intent(in) :: mask
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        write (u, "(L1)", advance="no") mask%f
        write (u, "(L1)", advance="no") mask%c
        if (.not.mask%cg) write (u, "('g')", advance="no")
        write (u, "(L1)", advance="no") mask%h
        if (mask%hd) write (u, "('d')", advance="no")
        write (u, "(A)", advance="no") "]"
    end subroutine quantum_numbers_mask_write_single

    subroutine quantum_numbers_mask_write_array (mask, unit)
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        do i = 1, size (mask)
            if (i > 1) write (u, "(A)", advance="no") "/"
            write (u, "(L1)", advance="no") mask(i)%f
            write (u, "(L1)", advance="no") mask(i)%c
            if (.not.mask(i)%cg) write (u, "('g')", advance="no")
            write (u, "(L1)", advance="no") mask(i)%h
            if (mask(i)%hd) write (u, "('d')", advance="no")
        end do
        write (u, "(A)", advance="no") "]"

```

```
end subroutine quantum_numbers_mask_write_array
```

10.6.8 Setting mask components

```
<Quantum numbers: quantum numbers mask: TBP>+≡
  procedure :: set_flavor => quantum_numbers_mask_set_flavor
  procedure :: set_color => quantum_numbers_mask_set_color
  procedure :: set_helicity => quantum_numbers_mask_set_helicity

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_mask_set_flavor (mask, mask_f)
    class(quantum_numbers_mask_t), intent(inout) :: mask
    logical, intent(in) :: mask_f
    mask%f = mask_f
  end subroutine quantum_numbers_mask_set_flavor

  elemental subroutine quantum_numbers_mask_set_color (mask, mask_c, mask_cg)
    class(quantum_numbers_mask_t), intent(inout) :: mask
    logical, intent(in) :: mask_c
    logical, intent(in), optional :: mask_cg
    mask%c = mask_c
    if (present (mask_cg)) then
      if (mask%c) mask%cg = mask_cg
    else
      mask%cg = mask_c
    end if
  end subroutine quantum_numbers_mask_set_color

  elemental subroutine quantum_numbers_mask_set_helicity (mask, mask_h, mask_hd)
    class(quantum_numbers_mask_t), intent(inout) :: mask
    logical, intent(in) :: mask_h
    logical, intent(in), optional :: mask_hd
    mask%h = mask_h
    if (present (mask_hd)) then
      if (.not. mask%h) mask%hd = mask_hd
    end if
  end subroutine quantum_numbers_mask_set_helicity
```

The following routines assign part of a mask, depending on the flags given.

```
<Quantum numbers: quantum numbers mask: TBP>+≡
  procedure :: assign => quantum_numbers_mask_assign

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_mask_assign &
    (mask, mask_in, flavor, color, helicity)
    class(quantum_numbers_mask_t), intent(inout) :: mask
    class(quantum_numbers_mask_t), intent(in) :: mask_in
    logical, intent(in), optional :: flavor, color, helicity
    if (present (flavor)) then
      if (flavor) then
        mask%f = mask_in%f
      end if
    end if
```

```

    if (present (color)) then
      if (color) then
        mask%c = mask_in%c
        mask%cg = mask_in%cg
      end if
    end if
    if (present (helicity)) then
      if (helicity) then
        mask%h = mask_in%h
        mask%hd = mask_in%hd
      end if
    end if
  end subroutine quantum_numbers_mask_assign

```

10.6.9 Mask predicates

Return true if either one of the entries is set:

```

<Quantum numbers: public>+≡
  public :: any

<Quantum numbers: interfaces>+≡
  interface any
    module procedure quantum_numbers_mask_any
  end interface

<Quantum numbers: procedures>+≡
  function quantum_numbers_mask_any (mask) result (match)
    logical :: match
    type(quantum_numbers_mask_t), intent(in) :: mask
    match = mask%f .or. mask%c .or. mask%h .or. mask%hd
  end function quantum_numbers_mask_any

```

10.6.10 Operators

The OR operation is applied to all components.

```

<Quantum numbers: quantum numbers mask: TBP>+≡
  generic :: operator(.or.) => quantum_numbers_mask_or
  procedure, private :: quantum_numbers_mask_or

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_mask_or (mask1, mask2) result (mask)
    type(quantum_numbers_mask_t) :: mask
    class(quantum_numbers_mask_t), intent(in) :: mask1, mask2
    mask%f = mask1%f .or. mask2%f
    mask%c = mask1%c .or. mask2%c
    if (mask%c) mask%cg = mask1%cg .or. mask2%cg
    mask%h = mask1%h .or. mask2%h
    if (.not. mask%h) mask%hd = mask1%hd .or. mask2%hd
  end function quantum_numbers_mask_or

```

10.6.11 Mask comparisons

Return true if the two masks are equivalent / differ:

```

<Quantum numbers: quantum numbers mask: TBP>+≡
  generic :: operator(.eqv.) => quantum_numbers_mask_eqv
  generic :: operator(.neqv.) => quantum_numbers_mask_neqv
  procedure, private :: quantum_numbers_mask_eqv
  procedure, private :: quantum_numbers_mask_neqv

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_mask_eqv (mask1, mask2) result (eqv)
    logical :: eqv
    class(quantum_numbers_mask_t), intent(in) :: mask1, mask2
    eqv = (mask1%f .eqv. mask2%f) .and. &
          (mask1%c .eqv. mask2%c) .and. &
          (mask1%cg .eqv. mask2%cg) .and. &
          (mask1%h .eqv. mask2%h) .and. &
          (mask1%hd .eqv. mask2%hd)
  end function quantum_numbers_mask_eqv

  elemental function quantum_numbers_mask_neqv (mask1, mask2) result (neqv)
    logical :: neqv
    class(quantum_numbers_mask_t), intent(in) :: mask1, mask2
    neqv = (mask1%f .neqv. mask2%f) .or. &
          (mask1%c .neqv. mask2%c) .or. &
          (mask1%cg .neqv. mask2%cg) .or. &
          (mask1%h .neqv. mask2%h) .or. &
          (mask1%hd .neqv. mask2%hd)
  end function quantum_numbers_mask_neqv

```

10.6.12 Apply a mask

Applying a mask to the quantum number object means undefining those entries where the mask is set. The others remain unaffected.

The `hd` mask has the special property that it “diagonalizes” helicity, i.e., the second helicity entry is dropped and the result is a diagonal helicity quantum number.

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: undefine => quantum_numbers_undefine
  procedure :: undefined => quantum_numbers_undefined0

<Quantum numbers: public>+≡
  public :: quantum_numbers_undefined

<Quantum numbers: interfaces>+≡
  interface quantum_numbers_undefined
    module procedure quantum_numbers_undefined0
    module procedure quantum_numbers_undefined1
    module procedure quantum_numbers_undefined11
  end interface

```

```

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_undefine (qn, mask)
    class(quantum_numbers_t), intent(inout) :: qn
    type(quantum_numbers_mask_t), intent(in) :: mask
    if (mask%f) call qn%f%undefine ()
    if (mask%c) call qn%c%undefine (undefine_ghost=mask%cg)
    if (mask%h) then
      call qn%h%undefine ()
    else if (mask%hd) then
      if (.not. qn%h%is_diagonal ()) then
        call qn%h%diagonalize ()
      end if
    end if
  end subroutine quantum_numbers_undefine

function quantum_numbers_undefined0 (qn, mask) result (qn_new)
  class(quantum_numbers_t), intent(in) :: qn
  type(quantum_numbers_mask_t), intent(in) :: mask
  type(quantum_numbers_t) :: qn_new
  select type (qn)
    type is (quantum_numbers_t); qn_new = qn
  end select
  call quantum_numbers_undefine (qn_new, mask)
end function quantum_numbers_undefined0

function quantum_numbers_undefined1 (qn, mask) result (qn_new)
  type(quantum_numbers_t), dimension(:), intent(in) :: qn
  type(quantum_numbers_mask_t), intent(in) :: mask
  type(quantum_numbers_t), dimension(size(qn)) :: qn_new
  qn_new = qn
  call quantum_numbers_undefine (qn_new, mask)
end function quantum_numbers_undefined1

function quantum_numbers_undefined11 (qn, mask) result (qn_new)
  type(quantum_numbers_t), dimension(:), intent(in) :: qn
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
  type(quantum_numbers_t), dimension(size(qn)) :: qn_new
  qn_new = qn
  call quantum_numbers_undefine (qn_new, mask)
end function quantum_numbers_undefined11

```

Return true if the input quantum number set has entries that would be removed by the applied mask, e.g., if polarization is defined but `mask%h` is set:

```

<Quantum numbers: quantum numbers: TBP>+≡
  procedure :: are_redundant => quantum_numbers_are_redundant

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_are_redundant (qn, mask) &
    result (redundant)
    logical :: redundant
    class(quantum_numbers_t), intent(in) :: qn
    type(quantum_numbers_mask_t), intent(in) :: mask
    redundant = .false.
    if (mask%f) then

```



```

        redundant = qn%f%is_defined ()
    end if
    if (mask%c) then
        redundant = qn%c%is_defined ()
    end if
    if (mask%h) then
        redundant = qn%h%is_defined ()
    else if (mask%hd) then
        redundant = .not. qn%h%is_diagonal ()
    end if
end function quantum_numbers_are_redundant

```

Return true if the helicity flag is set or the diagonal-helicity flag is set.

```

<Quantum numbers: quantum numbers mask: TBP>+≡
    procedure :: diagonal_helicity => quantum_numbers_mask_diagonal_helicity

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_mask_diagonal_helicity (mask) &
        result (flag)
        logical :: flag
        class(quantum_numbers_mask_t), intent(in) :: mask
        flag = mask%h .or. mask%hd
    end function quantum_numbers_mask_diagonal_helicity

```

Chapter 11

Transition Matrices and Evaluation

The modules in this chapter implement transition matrices and calculations. The functionality is broken down in three modules

state_matrices represent state and transition density matrices built from particle quantum numbers (helicity, color, flavor)

interactions extend state matrices with the record of particle momenta. They also distinguish in- and out-particles and store parent-child relations.

evaluators These objects extend interaction objects by the information how to calculate matrix elements from products and squares of other interactions. They implement the methods to actually compute those matrix elements.

11.1 State matrices

This module deals with the internal state of a particle system, i.e., with its density matrix in flavor, color, and helicity space.

```
<state_matrices.f90>≡  
<File header>  
  
module state_matrices  
  
  <Use kinds>  
  use io_units  
  use format_utils, only: pac_fmt  
  use format_defs, only: FMT_17, FMT_19  
  use unit_tests  
  use diagnostics  
  use sorting  
  use model_data  
  use flavors  
  use colors  
  use helicities  
  use quantum_numbers  
  
  <Standard module head>  
  
  <State matrices: public>  
  
  <State matrices: parameters>  
  
  <State matrices: types>  
  
  <State matrices: interfaces>  
  
  contains  
  
  <State matrices: procedures>  
  
  <State matrices: tests>  
  
end module state_matrices
```

11.1.1 Nodes of the quantum state trie

A quantum state object represents an unnormalized density matrix, i.e., an array of possibilities for flavor, color, and helicity indices with associated complex values. Physically, the trace of this matrix is the summed squared matrix element for an interaction, and the matrix elements divided by this value correspond to the flavor-color-helicity density matrix. (Flavor and color are diagonal.)

We store density matrices as tries, that is, as trees where each branching represents the possible quantum numbers of a particle. The first branching is the first particle in the system. A leaf (the node corresponding to the last particle) contains the value of the matrix element.

Each node contains a flavor, color, and helicity entry. Note that each of those

entries may be actually undefined, so we can also represent, e.g., unpolarized particles.

The value is meaningful only for leaves, which have no child nodes. There is a pointer to the parent node which allows for following the trie downwards from a leaf, it is null for a root node. The child nodes are implemented as a list, so there is a pointer to the first and last child, and each node also has a **next** pointer to the next sibling.

The root node does not correspond to a particle, only its children do. The quantum numbers of the root node are irrelevant and will not be set. However, we use a common type for the three classes (root, branch, leaf); they may easily be distinguished by the association status of parent and child.

Node type

The node is linked in all directions: the parent, the first and last in the list of children, and the previous and next sibling. This allows us for adding and removing nodes and whole branches anywhere in the trie. (Circular links are not allowed, however.). The node holds its associated set of quantum numbers. The integer index, which is set only for leaf nodes, is the index of the corresponding matrix element value within the state matrix.

Temporarily, matrix-element values may be stored within a leaf node. This is used during state-matrix factorization. When the state matrix is **frozen**, these values are transferred to the matrix-element array within the host state matrix.

```

<State matrices: types>≡
  type :: node_t
  private
    type(quantum_numbers_t) :: qn
    type(node_t), pointer :: parent => null ()
    type(node_t), pointer :: child_first => null ()
    type(node_t), pointer :: child_last => null ()
    type(node_t), pointer :: next => null ()
    type(node_t), pointer :: previous => null ()
    integer :: me_index = 0
    integer, dimension(:), allocatable :: me_count
    complex(default) :: me = 0
  end type node_t

```

Operations on nodes

Recursively deallocate all children of the current node. This includes any values associated with the children.

```

<State matrices: procedures>≡
  pure recursive subroutine node_delete_offspring (node)
    type(node_t), pointer :: node
    type(node_t), pointer :: child
    child => node%child_first
    do while (associated (child))
      node%child_first => node%child_first%next
      call node_delete_offspring (child)
    end do
  end subroutine node_delete_offspring

```

```

        deallocate (child)
        child => node%child_first
    end do
    node%child_last => null ()
end subroutine node_delete_offspring

```

Remove a node including its offspring. Adjust the pointers of parent and siblings, if necessary.

```

<State matrices: procedures>+≡
pure subroutine node_delete (node)
    type(node_t), pointer :: node
    call node_delete_offspring (node)
    if (associated (node%previous)) then
        node%previous%next => node%next
    else if (associated (node%parent)) then
        node%parent%child_first => node%next
    end if
    if (associated (node%next)) then
        node%next%previous => node%previous
    else if (associated (node%parent)) then
        node%parent%child_last => node%previous
    end if
    deallocate (node)
end subroutine node_delete

```

Append a child node

```

<State matrices: procedures>+≡
subroutine node_append_child (node, child)
    type(node_t), target, intent(inout) :: node
    type(node_t), pointer :: child
    allocate (child)
    if (associated (node%child_last)) then
        node%child_last%next => child
        child%previous => node%child_last
    else
        node%child_first => child
    end if
    node%child_last => child
    child%parent => node
end subroutine node_append_child

```

I/O

Output of a single node, no recursion. We print the quantum numbers in square brackets, then the value (if any).

```

<State matrices: procedures>+≡
subroutine node_write (node, me_array, verbose, unit, col_verbose, testflag)
    type(node_t), intent(in) :: node
    complex(default), dimension(:), intent(in), optional :: me_array
    logical, intent(in), optional :: verbose, col_verbose, testflag
    integer, intent(in), optional :: unit

```

```

logical :: verb
integer :: u
character(len=7) :: fmt
call pac_fmt (fmt, FMT_19, FMT_17, testflag)
verb = .false.; if (present (verbose)) verb = verbose
u = given_output_unit (unit); if (u < 0) return
call node%qn%write (u, col_verbose)
if (node%me_index /= 0) then
  write (u, "(A,I0,A)", advance="no") " => ME(", node%me_index, ")"
  if (present (me_array)) then
    write (u, "(A)", advance="no") " = "
    write (u, "('(',')" // fmt // ",',''," // fmt // ",')')", &
      advance="no") pacify_complex (me_array(node%me_index))
  end if
end if
write (u, *)
if (verb) then
  call ptr_write ("parent      ", node%parent)
  call ptr_write ("child_first", node%child_first)
  call ptr_write ("child_last ", node%child_last)
  call ptr_write ("next       ", node%next)
  call ptr_write ("previous  ", node%previous)
end if
contains
subroutine ptr_write (label, node)
  character(*), intent(in) :: label
  type(node_t), pointer :: node
  if (associated (node)) then
    write (u, "(10x,A,1x,'->',1x)", advance="no") label
    call node%qn%write (u, col_verbose)
    write (u, *)
  end if
end subroutine ptr_write
end subroutine node_write

```

Recursive output of a node:

$\langle \text{State matrices: procedures} \rangle + \equiv$

```

recursive subroutine node_write_rec (node, me_array, verbose, &
  indent, unit, col_verbose, testflag)
  type(node_t), intent(in), target :: node
  complex(default), dimension(:), intent(in), optional :: me_array
  logical, intent(in), optional :: verbose, col_verbose, testflag
  integer, intent(in), optional :: indent
  integer, intent(in), optional :: unit
  type(node_t), pointer :: current
  logical :: verb
  integer :: i, u
  verb = .false.; if (present (verbose)) verb = verbose
  i = 0; if (present (indent)) i = indent
  u = given_output_unit (unit); if (u < 0) return
  current => node%child_first
  do while (associated (current))
    write (u, "(A)", advance="no") repeat (" ", i)
    call node_write (current, me_array, verbose=verb, &

```

```

        unit=u, col_verbose=col_verbose, testflag=testflag)
    call node_write_rec (current, me_array, verbose=verb, &
        indent=i+2, unit=u, col_verbose=col_verbose, testflag=testflag)
    current => current%next
end do
end subroutine node_write_rec

```

Binary I/O. Matrix elements are written only for leaf nodes.

(State matrices: procedures)+≡

```

recursive subroutine node_write_raw_rec (node, u)
    type(node_t), intent(in), target :: node
    integer, intent(in) :: u
    logical :: associated_child_first, associated_next
    call node%qn%write_raw (u)
    associated_child_first = associated (node%child_first)
    write (u) associated_child_first
    associated_next = associated (node%next)
    write (u) associated_next
    if (associated_child_first) then
        call node_write_raw_rec (node%child_first, u)
    else
        write (u) node%me_index
        write (u) node%me
    end if
    if (associated_next) then
        call node_write_raw_rec (node%next, u)
    end if
end subroutine node_write_raw_rec

recursive subroutine node_read_raw_rec (node, u, parent, iostat)
    type(node_t), intent(out), target :: node
    integer, intent(in) :: u
    type(node_t), intent(in), optional, target :: parent
    integer, intent(out), optional :: iostat
    logical :: associated_child_first, associated_next
    type(node_t), pointer :: child
    call node%qn%read_raw (u, iostat=iostat)
    read (u, iostat=iostat) associated_child_first
    read (u, iostat=iostat) associated_next
    if (present (parent)) node%parent => parent
    if (associated_child_first) then
        allocate (child)
        node%child_first => child
        node%child_last => null ()
        call node_read_raw_rec (child, u, node, iostat=iostat)
        do while (associated (child))
            child%previous => node%child_last
            node%child_last => child
            child => child%next
        end do
    else
        read (u, iostat=iostat) node%me_index
        read (u, iostat=iostat) node%me
    end if
end if

```

```

    if (associated_next) then
        allocate (node%next)
        call node_read_raw_rec (node%next, u, parent, iostat=iostat)
    end if
end subroutine node_read_raw_rec

```

11.1.2 State matrix

Definition

The quantum state object is a container that keeps and hides the root node. For direct accessibility of values, they are stored in a separate array. The leaf nodes of the quantum-number tree point to those values, once the state matrix is finalized.

The `norm` component is redefined if a common factor is extracted from all nodes.

```

<State matrices: public>≡
    public :: state_matrix_t

<State matrices: types>+≡
    type :: state_matrix_t
    private
        type(node_t), pointer :: root => null ()
        integer :: depth = 0
        integer :: n_matrix_elements = 0
        logical :: leaf_nodes_store_values = .false.
        integer :: n_counters = 0
        complex(default), dimension(:), allocatable :: me
        real(default) :: norm = 1
    contains
        <State matrices: state matrix: TBP>
    end type state_matrix_t

```

This initializer allocates the root node but does not fill anything. We declare whether values are stored within the nodes during state-matrix construction, and how many counters should be maintained (default: none).

```

<State matrices: state matrix: TBP>≡
    procedure :: init => state_matrix_init

<State matrices: procedures>+≡
    subroutine state_matrix_init (state, store_values, n_counters)
        class(state_matrix_t), intent(out) :: state
        logical, intent(in), optional :: store_values
        integer, intent(in), optional :: n_counters
        allocate (state%root)
        if (present (store_values)) &
            state%leaf_nodes_store_values = store_values
        if (present (n_counters)) state%n_counters = n_counters
    end subroutine state_matrix_init

```


This recursively deletes all children of the root node, restoring the initial state. The matrix element array is not finalized, since it does not contain physical entries, just pointers.

```

<State matrices: state matrix: TBP>+≡
  procedure :: final => state_matrix_final

<State matrices: procedures>+≡
  subroutine state_matrix_final (state)
    class(state_matrix_t), intent(inout) :: state
    if (allocated (state%me)) deallocate (state%me)
    if (associated (state%root)) call node_delete (state%root)
    state%depth = 0
    state%n_matrix_elements = 0
  end subroutine state_matrix_final

```

Output: Present the tree as a nested list with appropriate indentation.

```

<State matrices: state matrix: TBP>+≡
  procedure :: write => state_matrix_write

<State matrices: procedures>+≡
  subroutine state_matrix_write (state, unit, write_value_list, &
    verbose, col_verbose, testflag)
    class(state_matrix_t), intent(in) :: state
    logical, intent(in), optional :: write_value_list, verbose, col_verbose
    logical, intent(in), optional :: testflag
    integer, intent(in), optional :: unit
    complex(default) :: me_dum
    character(len=7) :: fmt
    integer :: u
    integer :: i
    call pac_fmt (fmt, FMT_19, FMT_17, testflag)
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1x,A," // fmt // ")") "State matrix:  norm = ", state%norm
    if (associated (state%root)) then
      if (allocated (state%me)) then
        call node_write_rec (state%root, state%me, verbose=verbose, &
          indent=1, unit=u, col_verbose=col_verbose, testflag=testflag)
      else
        call node_write_rec (state%root, verbose=verbose, indent=1, &
          unit=u, col_verbose=col_verbose, testflag=testflag)
      end if
    end if
    if (present (write_value_list)) then
      if (write_value_list .and. allocated (state%me)) then
        do i = 1, size (state%me)
          write (u, "(1x,I0,A)", advance="no") i, ":"
          me_dum = state%me(i)
          if (real(state%me(i)) == -real(state%me(i))) then
            me_dum = &
              cmplx (0._default, aimag(me_dum), kind=default)
          end if
          if (aimag(me_dum) == -aimag(me_dum)) then
            me_dum = &
              cmplx (real(me_dum), 0._default, kind=default)
          end if
        end do
      end if
    end if

```

```

        end if
        write (u, "('(', " // fmt // ",','," // fmt // &
              ",')')") me_dum
    end do
end if
end if
end subroutine state_matrix_write

```

Binary I/O. The auxiliary matrix-element array is not written, but reconstructed after reading the tree.

Note: To be checked. Might be broken, don't use (unless trivial).

```

<State matrices: state matrix: TBP>+=
  procedure :: write_raw => state_matrix_write_raw
  procedure :: read_raw => state_matrix_read_raw

<State matrices: procedures>+=
  subroutine state_matrix_write_raw (state, u)
    class(state_matrix_t), intent(in), target :: state
    integer, intent(in) :: u
    logical :: is_defined
    integer :: depth, j
    type(state_iterator_t) :: it
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    is_defined = state%is_defined ()
    write (u) is_defined
    if (is_defined) then
      write (u) state%get_norm ()
      write (u) state%get_n_leaves ()
      depth = state%get_depth ()
      write (u) depth
      allocate (qn (depth))
      call it%init (state)
      do while (it%is_valid ())
        qn = it%get_quantum_numbers ()
        do j = 1, depth
          call qn(j)%write_raw (u)
        end do
        write (u) it%get_me_index ()
        write (u) it%get_matrix_element ()
        call it%advance ()
      end do
    end if
  end subroutine state_matrix_write_raw

  subroutine state_matrix_read_raw (state, u, iostat)
    class(state_matrix_t), intent(out) :: state
    integer, intent(in) :: u
    integer, intent(out) :: iostat
    logical :: is_defined
    real(default) :: norm
    integer :: n_leaves, depth, i, j
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: me_index
    complex(default) :: me
  end subroutine state_matrix_read_raw

```

```

read (u, iostat=iostat) is_defined
if (iostat /= 0) goto 1
if (is_defined) then
  call state%init (store_values = .true.)
  read (u, iostat=iostat) norm
  if (iostat /= 0) goto 1
  call state_matrix_set_norm (state, norm)
  read (u) n_leaves
  if (iostat /= 0) goto 1
  read (u) depth
  if (iostat /= 0) goto 1
  allocate (qn (depth))
  do i = 1, n_leaves
    do j = 1, depth
      call qn(j)%read_raw (u, iostat=iostat)
      if (iostat /= 0) goto 1
    end do
    read (u, iostat=iostat) me_index
    if (iostat /= 0) goto 1
    read (u, iostat=iostat) me
    if (iostat /= 0) goto 1
    call state%add_state (qn, index = me_index, value = me)
  end do
  call state_matrix_freeze (state)
end if
return

! Clean up on error
1 continue
call state%final ()
end subroutine state_matrix_read_raw

```

Assign a model pointer to all flavor entries. This will become necessary when we have read a state matrix from file.

```

<State matrices: state matrix: TBP>+≡
  procedure :: set_model => state_matrix_set_model

<State matrices: procedures>+≡
  subroutine state_matrix_set_model (state, model)
    class(state_matrix_t), intent(inout), target :: state
    class(model_data_t), intent(in), target :: model
    type(state_iterator_t) :: it
    call it%init (state)
    do while (it%is_valid ())
      call it%set_model (model)
      call it%advance ()
    end do
  end subroutine state_matrix_set_model

```

Properties of the quantum state

A state is defined if its root is allocated:

```

<State matrices: state matrix: TBP>+≡

```

```

    procedure :: is_defined => state_matrix_is_defined
<State matrices: procedures>+≡
    elemental function state_matrix_is_defined (state) result (defined)
        logical :: defined
        class(state_matrix_t), intent(in) :: state
        defined = associated (state%root)
    end function state_matrix_is_defined

```

A state is empty if its depth is zero:

```

<State matrices: state matrix: TBP>+≡
    procedure :: is_empty => state_matrix_is_empty
<State matrices: procedures>+≡
    elemental function state_matrix_is_empty (state) result (flag)
        logical :: flag
        class(state_matrix_t), intent(in) :: state
        flag = state%depth == 0
    end function state_matrix_is_empty

```

Return the number of matrix-element values.

```

<State matrices: state matrix: TBP>+≡
    procedure :: get_n_matrix_elements => state_matrix_get_n_matrix_elements
<State matrices: procedures>+≡
    function state_matrix_get_n_matrix_elements (state) result (n)
        integer :: n
        class(state_matrix_t), intent(in) :: state
        n = state%n_matrix_elements
    end function state_matrix_get_n_matrix_elements

```

Return the number of leaves. This can be larger than the number of independent matrix elements.

```

<State matrices: state matrix: TBP>+≡
    procedure :: get_n_leaves => state_matrix_get_n_leaves
<State matrices: procedures>+≡
    function state_matrix_get_n_leaves (state) result (n)
        integer :: n
        class(state_matrix_t), intent(in) :: state
        type(state_iterator_t) :: it
        n = 0
        call it%init (state)
        do while (it%is_valid ())
            n = n + 1
            call it%advance ()
        end do
    end function state_matrix_get_n_leaves

```

Return the depth:

```

<State matrices: state matrix: TBP>+≡
    procedure :: get_depth => state_matrix_get_depth

```

```

<State matrices: procedures>+≡
function state_matrix_get_depth (state) result (depth)
  integer :: depth
  class(state_matrix_t), intent(in) :: state
  depth = state%depth
end function state_matrix_get_depth

```

Return the norm:

```

<State matrices: state matrix: TBP>+≡
procedure :: get_norm => state_matrix_get_norm

<State matrices: procedures>+≡
function state_matrix_get_norm (state) result (norm)
  real(default) :: norm
  class(state_matrix_t), intent(in) :: state
  norm = state%norm
end function state_matrix_get_norm

```

Retrieving contents

Return the quantum number array, using an index. We have to scan the state matrix since there is no shortcut.

```

<State matrices: state matrix: TBP>+≡
procedure :: get_quantum_numbers => state_matrix_get_quantum_numbers

<State matrices: procedures>+≡
function state_matrix_get_quantum_numbers (state, i) result (qn)
  class(state_matrix_t), intent(in), target :: state
  integer, intent(in) :: i
  type(quantum_numbers_t), dimension(state%depth) :: qn
  type(state_iterator_t) :: it
  integer :: k
  k = 0
  call it%init (state)
  do while (it%is_valid ())
    k = k + 1
    if (k == i) then
      qn = it%get_quantum_numbers ()
      return
    end if
    call it%advance ()
  end do
end function state_matrix_get_quantum_numbers

```

Return a single matrix element using its index. Works only if the shortcut array is allocated.

```

<State matrices: state matrix: TBP>+≡
procedure :: get_matrix_element => state_matrix_get_matrix_element

<State matrices: procedures>+≡
function state_matrix_get_matrix_element (state, i) result (me)
  complex(default) :: me

```

```

class(state_matrix_t), intent(in) :: state
integer, intent(in) :: i
if (allocated (state%me)) then
    me = state%me(i)
else
    me = 0
end if
end function state_matrix_get_matrix_element

```

Return the color index with maximum absolute value that is present within the state matrix.

```

<State matrices: state matrix: TBP>+≡
    procedure :: get_max_color_value => state_matrix_get_max_color_value

<State matrices: procedures>+≡
    function state_matrix_get_max_color_value (state) result (cmax)
        integer :: cmax
        class(state_matrix_t), intent(in) :: state
        if (associated (state%root)) then
            cmax = node_get_max_color_value (state%root)
        else
            cmax = 0
        end if
    contains
        recursive function node_get_max_color_value (node) result (cmax)
            integer :: cmax
            type(node_t), intent(in), target :: node
            type(node_t), pointer :: current
            cmax = quantum_numbers_get_max_color_value (node%qn)
            current => node%child_first
            do while (associated (current))
                cmax = max (cmax, node_get_max_color_value (current))
                current => current%next
            end do
        end function node_get_max_color_value
    end function state_matrix_get_max_color_value

```

Building the quantum state

The procedure generates a branch associated to the input array of quantum numbers. If the branch exists already, it is used.

Optionally, we set the matrix-element index, a value (which may be added to the previous one), and increment one of the possible counters. We may also return the matrix element index of the current node.

```

<State matrices: state matrix: TBP>+≡
    procedure :: add_state => state_matrix_add_state

<State matrices: procedures>+≡
    subroutine state_matrix_add_state &
        (state, qn, index, value, sum_values, counter_index, me_index)
        class(state_matrix_t), intent(inout) :: state
        type(quantum_numbers_t), dimension(:), intent(in) :: qn

```

```

integer, intent(in), optional :: index
complex(default), intent(in), optional :: value
logical, intent(in), optional :: sum_values
integer, intent(in), optional :: counter_index
integer, intent(out), optional :: me_index
logical :: set_index, get_index, add
set_index = present (index)
get_index = present (me_index)
add = .false.; if (present (sum_values)) add = sum_values
if (state%depth == 0) then
    state%depth = size (qn)
else if (state%depth /= size (qn)) then
    call state%write ()
    call msg_bug ("State matrix: depth mismatch")
end if
if (size (qn) > 0) call node_make_branch (state%root, qn)
contains
recursive subroutine node_make_branch (parent, qn)
    type(node_t), pointer :: parent
    type(quantum_numbers_t), dimension(:), intent(in) :: qn
    type(node_t), pointer :: child
    logical :: match
    match = .false.
    child => parent%child_first
    SCAN_CHILDREN: do while (associated (child))
        match = child%qn == qn(1)
        if (match) exit SCAN_CHILDREN
        child => child%next
    end do SCAN_CHILDREN
    if (.not. match) then
        call node_append_child (parent, child)
        child%qn = qn(1)
    end if
    select case (size (qn))
    case (1)
        if (.not. match) then
            state%n_matrix_elements = state%n_matrix_elements + 1
            child%me_index = state%n_matrix_elements
        end if
        if (set_index) then
            child%me_index = index
        end if
        if (get_index) then
            me_index = child%me_index
        end if
        if (present (counter_index)) then
            if (.not. allocated (child%me_count)) then
                allocate (child%me_count (state%n_counters))
                child%me_count = 0
            end if
            child%me_count(counter_index) = child%me_count(counter_index) + 1
        end if
        if (present (value)) then
            if (add) then

```

```

        child%me = child%me + value
    else
        child%me = value
    end if
end if
case (2:)
    call node_make_branch (child, qn(2:))
end select
end subroutine node_make_branch
end subroutine state_matrix_add_state

```

Remove irrelevant flavor/color/helicity labels and the corresponding branchings. The masks indicate which particles are affected; the masks length should coincide with the depth of the trie (without the root node). Recursively scan the whole tree, starting from the leaf nodes and working up to the root node. If a mask entry is set for the current tree level, scan the children there. For each child within that level make a new empty branch where the masked quantum number is undefined. Then recursively combine all following children with matching quantum number into this new node and move on.

```

<State matrices: state matrix: TBP>+≡
    procedure :: collapse => state_matrix_collapse

<State matrices: procedures>+≡
    subroutine state_matrix_collapse (state, mask)
        class(state_matrix_t), intent(inout) :: state
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
        type(state_matrix_t) :: red_state
        if (state%is_defined ()) then
            call state%reduce (mask, red_state)
            call state%final ()
            state = red_state
        end if
    end subroutine state_matrix_collapse

```

Transform the given state matrix into a reduced state matrix where some quantum numbers are removed, as indicated by the mask. The procedure creates a new state matrix, so the old one can be deleted after this if it is no longer used.

```

<State matrices: state matrix: TBP>+≡
    procedure :: reduce => state_matrix_reduce

<State matrices: procedures>+≡
    subroutine state_matrix_reduce (state, mask, red_state)
        class(state_matrix_t), intent(in), target :: state
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
        type(state_matrix_t), intent(out) :: red_state
        type(state_iterator_t) :: it
        type(quantum_numbers_t), dimension(size(mask)) :: qn
        call red_state%init ()
        call it%init (state)
        do while (it%is_valid ())
            qn = it%get_quantum_numbers ()
            call qn%undefine (mask)
            call red_state%add_state (qn)
        end do
    end subroutine state_matrix_reduce

```



```

        call it%advance ()
    end do
end subroutine state_matrix_reduce

```

This subroutine sets up the matrix-element array. The leaf nodes acquire the index values that point to the appropriate matrix-element entry.

We recursively scan the trie. Once we arrive at a leaf node, the index is increased and associated to that node. Finally, we allocate the matrix-element array with the appropriate size.

If matrix element values are temporarily stored within the leaf nodes, we scan the state again and transfer them to the matrix-element array.

```

<State matrices: state matrix: TBP>+=
    procedure :: freeze => state_matrix_freeze

<State matrices: procedures>+=
    subroutine state_matrix_freeze (state)
        class(state_matrix_t), intent(inout), target :: state
        type(state_iterator_t) :: it
        if (associated (state%root)) then
            if (allocated (state%me)) deallocate (state%me)
            allocate (state%me (state%n_matrix_elements))
            state%me = 0
        end if
        if (state%leaf_nodes_store_values) then
            call it%init (state)
            do while (it%is_valid ())
                state%me(it%get_me_index ()) = it%get_matrix_element ()
                call it%advance ()
            end do
            state%leaf_nodes_store_values = .false.
        end if
    end subroutine state_matrix_freeze

```

Direct access to the value array

Several methods for setting a value directly are summarized in this generic:

```

<State matrices: state matrix: TBP>+=
    generic :: set_matrix_element => set_matrix_element_qn
    generic :: set_matrix_element => set_matrix_element_all
    generic :: set_matrix_element => set_matrix_element_array
    generic :: set_matrix_element => set_matrix_element_single
    generic :: set_matrix_element => set_matrix_element_clone
    procedure :: set_matrix_element_qn => state_matrix_set_matrix_element_qn
    procedure :: set_matrix_element_all => state_matrix_set_matrix_element_all
    procedure :: set_matrix_element_array => &
        state_matrix_set_matrix_element_array
    procedure :: set_matrix_element_single => &
        state_matrix_set_matrix_element_single
    procedure :: set_matrix_element_clone => &
        state_matrix_set_matrix_element_clone

```

Set a value that corresponds to a quantum number array:

```

<State matrices: procedures>+≡
subroutine state_matrix_set_matrix_element_qn (state, qn, value)
  class(state_matrix_t), intent(inout) :: state
  type(quantum_numbers_t), dimension(:), intent(in) :: qn
  complex(default), intent(in) :: value
  type(state_iterator_t) :: it
  if (.not. allocated (it%state%me)) then
    allocate (it%state%me (size(qn)))
  end if
  call it%init (state)
  do while (it%is_valid ())
    if (all (qn == it%get_quantum_numbers ())) then
      call it%set_matrix_element (value)
      return
    end if
    call it%advance ()
  end do
end subroutine state_matrix_set_matrix_element_qn

```

Set all matrix elements to a single value

```

<State matrices: procedures>+≡
subroutine state_matrix_set_matrix_element_all (state, value)
  class(state_matrix_t), intent(inout) :: state
  complex(default), intent(in) :: value
  if (.not. allocated (state%me)) then
    allocate (state%me (state%n_matrix_elements))
  end if
  state%me = value
end subroutine state_matrix_set_matrix_element_all

```

Set the matrix-element array directly.

```

<State matrices: procedures>+≡
subroutine state_matrix_set_matrix_element_array (state, value)
  class(state_matrix_t), intent(inout) :: state
  complex(default), dimension(:), intent(in) :: value
  if (.not. allocated (state%me)) then
    allocate (state%me (size (value)))
  end if
  state%me = value
end subroutine state_matrix_set_matrix_element_array

pure subroutine state_matrix_set_matrix_element_single (state, i, value)
  class(state_matrix_t), intent(inout) :: state
  integer, intent(in) :: i
  complex(default), intent(in) :: value
  if (.not. allocated (state%me)) then
    allocate (state%me (state%n_matrix_elements))
  end if
  state%me(i) = value
end subroutine state_matrix_set_matrix_element_single

```

Clone the matrix elements from another (matching) state matrix.

```

<State matrices: procedures>+≡
  subroutine state_matrix_set_matrix_element_clone (state, state1)
    class(state_matrix_t), intent(inout) :: state
    type(state_matrix_t), intent(in) :: state1
    if (.not. allocated (state1%me)) return
    if (.not. allocated (state%me)) allocate (state%me (size (state1%me)))
    state%me = state1%me
  end subroutine state_matrix_set_matrix_element_clone

```

Add a value to a matrix element

```

<State matrices: state matrix: TBP>+≡
  procedure :: add_to_matrix_element => state_matrix_add_to_matrix_element

<State matrices: procedures>+≡
  subroutine state_matrix_add_to_matrix_element (state, i, value)
    class(state_matrix_t), intent(inout) :: state
    integer, intent(in) :: i
    complex(default), intent(in) :: value
    state%me(i) = state%me(i) + value
  end subroutine state_matrix_add_to_matrix_element

```

11.1.3 State iterators

Accessing the quantum state from outside is best done using a specialized iterator, i.e., a pointer to a particular branch of the quantum state trie. Technically, the iterator contains a pointer to a leaf node, but via parent pointers it allows to access the whole branch where the leaf is attached. For quick access, we also keep the branch depth (which is assumed to be universal for a quantum state).

```

<State matrices: public>+≡
  public :: state_iterator_t

<State matrices: types>+≡
  type :: state_iterator_t
    private
    integer :: depth = 0
    type(state_matrix_t), pointer :: state => null ()
    type(node_t), pointer :: node => null ()
  contains
    <State matrices: state iterator: TBP>
  end type state_iterator_t

```

The initializer: Point at the first branch. Note that this cannot be pure, thus not be elemental, because the iterator can be used to manipulate data in the state matrix.

```

<State matrices: state iterator: TBP>≡
  procedure :: init => state_iterator_init

<State matrices: procedures>+≡
  subroutine state_iterator_init (it, state)
    class(state_iterator_t), intent(out) :: it
    type(state_matrix_t), intent(in), target :: state

```

```

it%state => state
it%depth = state%depth
if (state%is_defined ()) then
    it%node => state%root
    do while (associated (it%node%child_first))
        it%node => it%node%child_first
    end do
else
    it%node => null ()
end if
end subroutine state_iterator_init

```

Go forward. Recursively programmed: if the next node does not exist, go back to the parent node and look at its successor (if present), etc.

There is a possible pitfall in the implementation: If the dummy pointer argument to the `find_next` routine is used directly, we still get the correct result for the iterator, but calling the recursion on `node%parent` means that we manipulate a parent pointer in the original state in addition to the iterator. Making a local copy of the pointer avoids this. Using pointer intent would be helpful, but we do not yet rely on this F2003 feature.

```

<State matrices: state iterator: TBP>+≡
    procedure :: advance => state_iterator_advance

<State matrices: procedures>+≡
    subroutine state_iterator_advance (it)
        class(state_iterator_t), intent(inout) :: it
        call find_next (it%node)
    contains
        recursive subroutine find_next (node_in)
            type(node_t), intent(in), target :: node_in
            type(node_t), pointer :: node
            node => node_in
            if (associated (node%next)) then
                node => node%next
                do while (associated (node%child_first))
                    node => node%child_first
                end do
                it%node => node
            else if (associated (node%parent)) then
                call find_next (node%parent)
            else
                it%node => null ()
            end if
        end subroutine find_next
    end subroutine state_iterator_advance

```

If all has been scanned, the iterator is at an undefined state. Check for this:

```

<State matrices: state iterator: TBP>+≡
    procedure :: is_valid => state_iterator_is_valid

<State matrices: procedures>+≡
    function state_iterator_is_valid (it) result (defined)
        logical :: defined

```

```

        class(state_iterator_t), intent(in) :: it
        defined = associated (it%node)
    end function state_iterator_is_valid

```

Return the matrix-element index that corresponds to the current node

```

<State matrices: state iterator: TBP>+≡
    procedure :: get_me_index => state_iterator_get_me_index

<State matrices: procedures>+≡
    function state_iterator_get_me_index (it) result (n)
        integer :: n
        class(state_iterator_t), intent(in) :: it
        n = it%node%me_index
    end function state_iterator_get_me_index

```

Return the number of times this quantum-number state has been added (noting that it is physically inserted only the first time). Note that for each state, there is an array of counters.

```

<State matrices: state iterator: TBP>+≡
    procedure :: get_me_count => state_iterator_get_me_count

<State matrices: procedures>+≡
    function state_iterator_get_me_count (it) result (n)
        integer, dimension(:), allocatable :: n
        class(state_iterator_t), intent(in) :: it
        if (allocated (it%node%me_count)) then
            allocate (n (size (it%node%me_count)))
            n = it%node%me_count
        else
            allocate (n (0))
        end if
    end function state_iterator_get_me_count

```

Use the iterator to retrieve quantum-number information:

```

<State matrices: state iterator: TBP>+≡
    generic :: get_quantum_numbers => get_qn_multi, get_qn_slice, &
        get_qn_range, get_qn_single
    generic :: get_flavor => get_flv_multi, get_flv_slice, &
        get_flv_range, get_flv_single
    generic :: get_color => get_col_multi, get_col_slice, &
        get_col_range, get_col_single
    generic :: get_helicity => get_hel_multi, get_hel_slice, &
        get_hel_range, get_hel_single

<State matrices: state iterator: TBP>+≡
    procedure :: get_qn_multi => state_iterator_get_qn_multi
    procedure :: get_qn_slice => state_iterator_get_qn_slice
    procedure :: get_qn_range => state_iterator_get_qn_range
    procedure :: get_qn_single => state_iterator_get_qn_single
    procedure :: get_flv_multi => state_iterator_get_flv_multi
    procedure :: get_flv_slice => state_iterator_get_flv_slice
    procedure :: get_flv_range => state_iterator_get_flv_range
    procedure :: get_flv_single => state_iterator_get_flv_single

```

```

procedure :: get_col_multi => state_iterator_get_col_multi
procedure :: get_col_slice => state_iterator_get_col_slice
procedure :: get_col_range => state_iterator_get_col_range
procedure :: get_col_single => state_iterator_get_col_single
procedure :: get_hel_multi => state_iterator_get_hel_multi
procedure :: get_hel_slice => state_iterator_get_hel_slice
procedure :: get_hel_range => state_iterator_get_hel_range
procedure :: get_hel_single => state_iterator_get_hel_single

```

These versions return the whole quantum number array

```

⟨State matrices: procedures⟩+≡
function state_iterator_get_qn_multi (it) result (qn)
  class(state_iterator_t), intent(in) :: it
  type(quantum_numbers_t), dimension(it%depth) :: qn
  type(node_t), pointer :: node
  integer :: i
  node => it%node
  do i = it%depth, 1, -1
    qn(i) = node%qn
    node => node%parent
  end do
end function state_iterator_get_qn_multi

function state_iterator_get_flv_multi (it) result (flv)
  class(state_iterator_t), intent(in) :: it
  type(flavor_t), dimension(it%depth) :: flv
  flv = quantum_numbers_get_flavor &
    (it%get_quantum_numbers ())
end function state_iterator_get_flv_multi

function state_iterator_get_col_multi (it) result (col)
  class(state_iterator_t), intent(in) :: it
  type(color_t), dimension(it%depth) :: col
  col = quantum_numbers_get_color &
    (it%get_quantum_numbers ())
end function state_iterator_get_col_multi

function state_iterator_get_hel_multi (it) result (hel)
  class(state_iterator_t), intent(in) :: it
  type(helicity_t), dimension(it%depth) :: hel
  hel = quantum_numbers_get_helicity &
    (it%get_quantum_numbers ())
end function state_iterator_get_hel_multi

```

An array slice (derived from the above).

```

⟨State matrices: procedures⟩+≡
function state_iterator_get_qn_slice (it, index) result (qn)
  class(state_iterator_t), intent(in) :: it
  integer, dimension(:), intent(in) :: index
  type(quantum_numbers_t), dimension(size(index)) :: qn
  type(quantum_numbers_t), dimension(it%depth) :: qn_tmp
  qn_tmp = state_iterator_get_qn_multi (it)
  qn = qn_tmp(index)
end function state_iterator_get_qn_slice

```

```

function state_iterator_get_flv_slice (it, index) result (flv)
  class(state_iterator_t), intent(in) :: it
  integer, dimension(:), intent(in) :: index
  type(flavor_t), dimension(size(index)) :: flv
  flv = quantum_numbers_get_flavor &
    (it%get_quantum_numbers (index))
end function state_iterator_get_flv_slice

function state_iterator_get_col_slice (it, index) result (col)
  class(state_iterator_t), intent(in) :: it
  integer, dimension(:), intent(in) :: index
  type(color_t), dimension(size(index)) :: col
  col = quantum_numbers_get_color &
    (it%get_quantum_numbers (index))
end function state_iterator_get_col_slice

function state_iterator_get_hel_slice (it, index) result (hel)
  class(state_iterator_t), intent(in) :: it
  integer, dimension(:), intent(in) :: index
  type(helicity_t), dimension(size(index)) :: hel
  hel = quantum_numbers_get_helicity &
    (it%get_quantum_numbers (index))
end function state_iterator_get_hel_slice

```

An array range (implemented directly).

(State matrices: procedures)+≡

```

function state_iterator_get_qn_range (it, k1, k2) result (qn)
  class(state_iterator_t), intent(in) :: it
  integer, intent(in) :: k1, k2
  type(quantum_numbers_t), dimension(k2-k1+1) :: qn
  type(node_t), pointer :: node
  integer :: i
  node => it%node
  SCAN: do i = it%depth, 1, -1
    if (k1 <= i .and. i <= k2) then
      qn(i-k1+1) = node%qn
    else
      node => node%parent
    end if
  end do SCAN
end function state_iterator_get_qn_range

function state_iterator_get_flv_range (it, k1, k2) result (flv)
  class(state_iterator_t), intent(in) :: it
  integer, intent(in) :: k1, k2
  type(flavor_t), dimension(k2-k1+1) :: flv
  flv = quantum_numbers_get_flavor &
    (it%get_quantum_numbers (k1, k2))
end function state_iterator_get_flv_range

function state_iterator_get_col_range (it, k1, k2) result (col)
  class(state_iterator_t), intent(in) :: it
  integer, intent(in) :: k1, k2

```

```

    type(color_t), dimension(k2-k1+1) :: col
    col = quantum_numbers_get_color &
        (it%get_quantum_numbers (k1, k2))
end function state_iterator_get_col_range

function state_iterator_get_hel_range (it, k1, k2) result (hel)
    class(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k1, k2
    type(helicity_t), dimension(k2-k1+1) :: hel
    hel = quantum_numbers_get_helicity &
        (it%get_quantum_numbers (k1, k2))
end function state_iterator_get_hel_range

```

Just a specific single element

(State matrices: procedures)+≡

```

function state_iterator_get_qn_single (it, k) result (qn)
    class(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k
    type(quantum_numbers_t) :: qn
    type(node_t), pointer :: node
    integer :: i
    node => it%node
    SCAN: do i = it%depth, 1, -1
        if (i == k) then
            qn = node%qn
            exit SCAN
        else
            node => node%parent
        end if
    end do SCAN
end function state_iterator_get_qn_single

function state_iterator_get_flv_single (it, k) result (flv)
    class(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k
    type(flavor_t) :: flv
    flv = quantum_numbers_get_flavor &
        (it%get_quantum_numbers (k))
end function state_iterator_get_flv_single

function state_iterator_get_col_single (it, k) result (col)
    class(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k
    type(color_t) :: col
    col = quantum_numbers_get_color &
        (it%get_quantum_numbers (k))
end function state_iterator_get_col_single

function state_iterator_get_hel_single (it, k) result (hel)
    class(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k
    type(helicity_t) :: hel
    hel = quantum_numbers_get_helicity &
        (it%get_quantum_numbers (k))
end function state_iterator_get_hel_single

```



```
end function state_iterator_get_hel_single
```

Assign a model pointer to the current flavor entries.

```
<State matrices: state iterator: TBP>+≡
  procedure :: set_model => state_iterator_set_model

<State matrices: procedures>+≡
  subroutine state_iterator_set_model (it, model)
    class(state_iterator_t), intent(inout) :: it
    class(model_data_t), intent(in), target :: model
    type(node_t), pointer :: node
    integer :: i
    node => it%node
    do i = it%depth, 1, -1
      call node%qn%set_model (model)
      node => node%parent
    end do
  end subroutine state_iterator_set_model
```

Retrieve the matrix element value associated with the current node.

```
<State matrices: state iterator: TBP>+≡
  procedure :: get_matrix_element => state_iterator_get_matrix_element

<State matrices: procedures>+≡
  function state_iterator_get_matrix_element (it) result (me)
    complex(default) :: me
    class(state_iterator_t), intent(in) :: it
    if (it%state%leaf_nodes_store_values) then
      me = it%node%me
    else if (it%node%me_index /= 0) then
      me = it%state%me(it%node%me_index)
    else
      me = 0
    end if
  end function state_iterator_get_matrix_element
```

Set the matrix element value using the state iterator.

```
<State matrices: state iterator: TBP>+≡
  procedure :: set_matrix_element => state_iterator_set_matrix_element

<State matrices: procedures>+≡
  subroutine state_iterator_set_matrix_element (it, value)
    class(state_iterator_t), intent(inout) :: it
    complex(default), intent(in) :: value
    if (it%node%me_index /= 0) then
      it%state%me(it%node%me_index) = value
    end if
  end subroutine state_iterator_set_matrix_element
```

11.1.4 Operations on quantum states

Return a deep copy of a state matrix.

```
<State matrices: public>+≡
```

```

    public :: assignment(=)
<State matrices: interfaces>≡
    interface assignment(=)
        module procedure state_matrix_assign
    end interface

<State matrices: procedures>+≡
    subroutine state_matrix_assign (state_out, state_in)
        type(state_matrix_t), intent(out) :: state_out
        type(state_matrix_t), intent(in), target :: state_in
        type(state_iterator_t) :: it
        if (.not. state_in%is_defined ()) return
        call state_out%init ()
        call it%init (state_in)
        do while (it%is_valid ())
            call state_out%add_state (it%get_quantum_numbers (), &
                it%get_me_index ())
            call it%advance ()
        end do
        if (allocated (state_in%me)) then
            allocate (state_out%me (size (state_in%me)))
            state_out%me = state_in%me
        end if
    end subroutine state_matrix_assign

```

Determine the indices of all diagonal matrix elements.

```

<State matrices: state matrix: TBP>+≡
    procedure :: get_diagonal_entries => state_matrix_get_diagonal_entries

<State matrices: procedures>+≡
    subroutine state_matrix_get_diagonal_entries (state, i)
        class(state_matrix_t), intent(in) :: state
        integer, dimension(:), allocatable, intent(out) :: i
        integer, dimension(state%n_matrix_elements) :: tmp
        integer :: n
        type(state_iterator_t) :: it
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        n = 0
        call it%init (state)
        allocate (qn (it%depth))
        do while (it%is_valid ())
            qn = it%get_quantum_numbers ()
            if (all (qn%are_diagonal ())) then
                n = n + 1
                tmp(n) = it%get_me_index ()
            end if
            call it%advance ()
        end do
        allocate (i(n))
        if (n > 0) i = tmp(:n)
    end subroutine state_matrix_get_diagonal_entries

```

Normalize all matrix elements, i.e., multiply by a common factor. Assuming that the factor is nonzero, of course.

```

<State matrices: state matrix: TBP>+≡
  procedure :: renormalize => state_matrix_renormalize

<State matrices: procedures>+≡
  subroutine state_matrix_renormalize (state, factor)
    class(state_matrix_t), intent(inout) :: state
    complex(default), intent(in) :: factor
    state%me = state%me * factor
  end subroutine state_matrix_renormalize

```

Renormalize the state matrix by its trace, if nonzero. The renormalization is reflected in the state-matrix norm.

```

<State matrices: state matrix: TBP>+≡
  procedure :: normalize_by_trace => state_matrix_normalize_by_trace

<State matrices: procedures>+≡
  subroutine state_matrix_normalize_by_trace (state)
    class(state_matrix_t), intent(inout) :: state
    real(default) :: trace
    trace = state%trace ()
    if (trace /= 0) then
      state%me = state%me / trace
      state%norm = state%norm * trace
    end if
  end subroutine state_matrix_normalize_by_trace

```

Analogous, but renormalize by maximal (absolute) value.

```

<State matrices: state matrix: TBP>+≡
  procedure :: normalize_by_max => state_matrix_normalize_by_max

<State matrices: procedures>+≡
  subroutine state_matrix_normalize_by_max (state)
    class(state_matrix_t), intent(inout) :: state
    real(default) :: m
    m = maxval (abs (state%me))
    if (m /= 0) then
      state%me = state%me / m
      state%norm = state%norm * m
    end if
  end subroutine state_matrix_normalize_by_max

```

Explicitly set the norm of a state matrix.

```

<State matrices: state matrix: TBP>+≡
  procedure :: set_norm => state_matrix_set_norm

<State matrices: procedures>+≡
  subroutine state_matrix_set_norm (state, norm)
    class(state_matrix_t), intent(inout) :: state
    real(default), intent(in) :: norm
    state%norm = norm
  end subroutine state_matrix_set_norm

```

Return the sum of all matrix element values.

```

<State matrices: state matrix: TBP>+=
  procedure :: sum => state_matrix_sum

<State matrices: procedures>+=
  function state_matrix_sum (state) result (value)
    complex(default) :: value
    class(state_matrix_t), intent(in) :: state
    value = sum (state%me)
  end function state_matrix_sum

```

Return the trace of a state matrix, i.e., the sum over all diagonal values. If `qn_in` is provided, only branches that match this quantum-numbers array are considered.

```

<State matrices: state matrix: TBP>+=
  procedure :: trace => state_matrix_trace

<State matrices: procedures>+=
  function state_matrix_trace (state, qn_in) result (trace)
    complex(default) :: trace
    class(state_matrix_t), intent(in), target :: state
    type(quantum_numbers_t), dimension(:), intent(in), optional :: qn_in
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    type(state_iterator_t) :: it
    allocate (qn (state%get_depth ()))
    trace = 0
    call it%init (state)
    do while (it%is_valid ())
      qn = it%get_quantum_numbers ()
      if (present (qn_in)) then
        if (.not. all (qn .match. qn_in)) then
          call it%advance (); cycle
        end if
      end if
      if (all (qn%are_diagonal ())) then
        trace = trace + it%get_matrix_element ()
      end if
      call it%advance ()
    end do
  end function state_matrix_trace

```

Append new states which are color-contracted versions of the existing states. The matrix element index of each color contraction coincides with the index of its origin, so no new matrix elements are generated. After this operation, no `freeze` must be performed anymore.

```

<State matrices: state matrix: TBP>+=
  procedure :: add_color_contractions => state_matrix_add_color_contractions

<State matrices: procedures>+=
  subroutine state_matrix_add_color_contractions (state)
    class(state_matrix_t), intent(inout), target :: state
    type(state_iterator_t) :: it
    type(quantum_numbers_t), dimension(:,:), allocatable :: qn
    type(quantum_numbers_t), dimension(:,:), allocatable :: qn_con

```

```

integer, dimension(:), allocatable :: me_index
integer :: depth, n_me, i, j
depth = state%get_depth ()
n_me = state%get_n_matrix_elements ()
allocate (qn (depth, n_me))
allocate (me_index (n_me))
i = 0
call it%init (state)
do while (it%is_valid ())
  i = i + 1
  qn(:,i) = it%get_quantum_numbers ()
  me_index(i) = it%get_me_index ()
  call it%advance ()
end do
do i = 1, n_me
  call quantum_number_array_make_color_contractions (qn(:,i), qn_con)
  do j = 1, size (qn_con, 2)
    call state%add_state (qn_con(:,j), index = me_index(i))
  end do
end do
end subroutine state_matrix_add_color_contractions

```

This procedure merges two state matrices of equal depth. For each quantum number (flavor, color, helicity), we take the entry from the first argument where defined, otherwise the second one. (If both are defined, we get an off-diagonal matrix.) The resulting trie combines the information of the input tries in all possible ways. Note that values are ignored, all values in the result are zero.

(State matrices: public)+≡

```
public :: merge_state_matrices
```

(State matrices: procedures)+≡

```

subroutine merge_state_matrices (state1, state2, state3)
  type(state_matrix_t), intent(in), target :: state1, state2
  type(state_matrix_t), intent(out) :: state3
  type(state_iterator_t) :: it1, it2
  type(quantum_numbers_t), dimension(state1%depth) :: qn1, qn2
  if (state1%depth /= state2%depth) then
    call state1%write ()
    call state2%write ()
    call msg_bug ("State matrices merge impossible: incompatible depths")
  end if
  call state3%init ()
  call it1%init (state1)
  do while (it1%is_valid ())
    qn1 = it1%get_quantum_numbers ()
    call it2%init (state2)
    do while (it2%is_valid ())
      qn2 = it2%get_quantum_numbers ()
      call state3%add_state (qn1 .merge. qn2)
      call it2%advance ()
    end do
    call it1%advance ()
  end do
  call state3%freeze ()

```

```
end subroutine merge_state_matrices
```

Multiply matrix elements from two state matrices. Choose the elements as given by the integer index arrays, multiply them and store the sum of products in the indicated matrix element. The suffixes mean: c=conjugate first factor; f=include weighting factor.

Note that the `dot_product` intrinsic function conjugates its first complex argument. This is intended for the c suffix case, but must be reverted for the plain-product case.

We provide analogous subroutines for just summing over state matrix entries. The `evaluate_sum` variant includes the state-matrix norm in the evaluation, the `evaluate_me_sum` takes into account just the matrix elements proper.

(State matrices: state matrix: TBP)+≡

```
procedure :: evaluate_product => state_matrix_evaluate_product
procedure :: evaluate_product_cf => state_matrix_evaluate_product_cf
procedure :: evaluate_square_c => state_matrix_evaluate_square_c
procedure :: evaluate_sum => state_matrix_evaluate_sum
procedure :: evaluate_me_sum => state_matrix_evaluate_me_sum
```

(State matrices: procedures)+≡

```
pure subroutine state_matrix_evaluate_product &
  (state, i, state1, state2, index1, index2)
  class(state_matrix_t), intent(inout) :: state
  integer, intent(in) :: i
  type(state_matrix_t), intent(in) :: state1, state2
  integer, dimension(:), intent(in) :: index1, index2
  state%me(i) = &
    dot_product (conjg (state1%me(index1)), state2%me(index2))
  state%norm = state1%norm * state2%norm
end subroutine state_matrix_evaluate_product

pure subroutine state_matrix_evaluate_product_cf &
  (state, i, state1, state2, index1, index2, factor)
  class(state_matrix_t), intent(inout) :: state
  integer, intent(in) :: i
  type(state_matrix_t), intent(in) :: state1, state2
  integer, dimension(:), intent(in) :: index1, index2
  complex(default), dimension(:), intent(in) :: factor
  state%me(i) = &
    dot_product (state1%me(index1), factor * state2%me(index2))
  state%norm = state1%norm * state2%norm
end subroutine state_matrix_evaluate_product_cf

pure subroutine state_matrix_evaluate_square_c (state, i, state1, index1)
  class(state_matrix_t), intent(inout) :: state
  integer, intent(in) :: i
  type(state_matrix_t), intent(in) :: state1
  integer, dimension(:), intent(in) :: index1
  state%me(i) = &
    dot_product (state1%me(index1), state1%me(index1))
  state%norm = abs (state1%norm) ** 2
end subroutine state_matrix_evaluate_square_c
```

```

pure subroutine state_matrix_evaluate_sum (state, i, state1, index1)
  class(state_matrix_t), intent(inout) :: state
  integer, intent(in) :: i
  type(state_matrix_t), intent(in) :: state1
  integer, dimension(:), intent(in) :: index1
  state%me(i) = &
    sum (state1%me(index1)) * state1%norm
end subroutine state_matrix_evaluate_sum

pure subroutine state_matrix_evaluate_me_sum (state, i, state1, index1)
  class(state_matrix_t), intent(inout) :: state
  integer, intent(in) :: i
  type(state_matrix_t), intent(in) :: state1
  integer, dimension(:), intent(in) :: index1
  state%me(i) = sum (state1%me(index1))
end subroutine state_matrix_evaluate_me_sum

```

Outer product (of states and matrix elements):

```

<State matrices: public>+≡
  public :: outer_multiply

<State matrices: interfaces>+≡
  interface outer_multiply
    module procedure outer_multiply_pair
    module procedure outer_multiply_array
  end interface

```

This procedure constructs the outer product of two state matrices.

```

<State matrices: procedures>+≡
  subroutine outer_multiply_pair (state1, state2, state3)
    type(state_matrix_t), intent(in), target :: state1, state2
    type(state_matrix_t), intent(out) :: state3
    type(state_iterator_t) :: it1, it2
    type(quantum_numbers_t), dimension(state1%depth) :: qn1
    type(quantum_numbers_t), dimension(state2%depth) :: qn2
    type(quantum_numbers_t), dimension(state1%depth+state2%depth) :: qn3
    complex(default) :: val1, val2
    call state3%init (store_values=.true.)
    call it1%init (state1)
    do while (it1%is_valid ())
      qn1 = it1%get_quantum_numbers ()
      val1 = it1%get_matrix_element ()
      call it2%init (state2)
      do while (it2%is_valid ())
        qn2 = it2%get_quantum_numbers ()
        val2 = it2%get_matrix_element ()
        qn3(:state1%depth) = qn1
        qn3(state1%depth+1:) = qn2
        call state3%add_state (qn3, value=val1 * val2)
        call it2%advance ()
      end do
      call it1%advance ()
    end do
  end do

```

```

        call state3%freeze ()
    end subroutine outer_multiply_pair

```

This executes the above routine iteratively for an arbitrary number of state matrices.

<State matrices: procedures>+≡

```

subroutine outer_multiply_array (state_in, state_out)
    type(state_matrix_t), dimension(:), intent(in), target :: state_in
    type(state_matrix_t), intent(out) :: state_out
    type(state_matrix_t), dimension(:), allocatable, target :: state_tmp
    integer :: i, n
    n = size (state_in)
    select case (n)
    case (0)
        call state_out%init ()
    case (1)
        state_out = state_in(1)
    case (2)
        call outer_multiply_pair (state_in(1), state_in(2), state_out)
    case default
        allocate (state_tmp (n-2))
        call outer_multiply_pair (state_in(1), state_in(2), state_tmp(1))
        do i = 2, n - 2
            call outer_multiply_pair (state_tmp(i-1), state_in(i+1), state_tmp(i))
        end do
        call outer_multiply_pair (state_tmp(n-2), state_in(n), state_out)
        do i = 1, size(state_tmp)
            call state_tmp(i)%final ()
        end do
    end select
end subroutine outer_multiply_array

```

11.1.5 Factorization

In physical events, the state matrix is factorized into single-particle state matrices. This is essentially a measurement.

In a simulation, we select one particular branch of the state matrix with a probability that is determined by the matrix elements at the leaves. (This makes sense only if the state matrix represents a squared amplitude.) The selection is based on a (random) value *x* between 0 and one that is provided as the third argument.

For flavor and color, we select a unique value for each particle. For polarization, we have three options (modes). Option 1 is to drop helicity information altogether and sum over all diagonal helicities. Option 2 is to select a unique diagonal helicity in the same way as flavor and color. Option 3 is, for each particle, to trace over all remaining helicities in order to obtain an array of independent single-particle helicity matrices.

Only branches that match the given quantum-number array *qn_in*, if present, are considered. For this array, color is ignored.

If the optional *correlated_state* is provided, it is assigned the correlated density matrix for the selected flavor-color branch, so multi-particle spin corre-

lations remain available even if they are dropped in the single-particle density matrices.

The algorithm is as follows: First, we determine the normalization by summing over all diagonal matrix elements. In a second scan, we select one of the diagonal matrix elements by a cumulative comparison with the normalized random number. In the corresponding quantum number array, we undefine the helicity entries. Then, we scan the third time. For each branch that matches the selected quantum number array (i.e., definite flavor and color, arbitrary helicity), we determine its contribution to any of the single-particle state matrices. The matrix-element value is added if all other quantum numbers are diagonal, while the helicity of the chosen particle may be arbitrary; this helicity determines the branch in the single-particle state.

As a result, flavor and color quantum numbers are selected with the correct probability. Within this subset of states, each single-particle state matrix results from tracing over all other particles. Note that the single-particle state matrices are not normalized.

The flag `ok` is set to false if the matrix element sum is zero, so factorization is not possible. This can happen if an event did not pass cuts.

```

<State matrices: parameters>≡
  integer, parameter, public :: FM_IGNORE_HELICITY = 1
  integer, parameter, public :: FM_SELECT_HELICITY = 2
  integer, parameter, public :: FM_FACTOR_HELICITY = 3

<State matrices: state matrix: TBP>+≡
  procedure :: factorize => state_matrix_factorize

<State matrices: procedures>+≡
  subroutine state_matrix_factorize &
    (state, mode, x, ok, single_state, correlated_state, qn_in)
    class(state_matrix_t), intent(in), target :: state
    integer, intent(in) :: mode
    real(default), intent(in) :: x
    logical, intent(out) :: ok
    type(state_matrix_t), &
      dimension(:), allocatable, intent(out) :: single_state
    type(state_matrix_t), intent(out), optional :: correlated_state
    type(quantum_numbers_t), dimension(:), intent(in), optional :: qn_in
    type(state_iterator_t) :: it
    real(default) :: s, xt
    complex(default) :: value
    integer :: i, depth
    type(quantum_numbers_t), dimension(:), allocatable :: qn, qn1
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
    logical, dimension(:), allocatable :: diagonal
    logical, dimension(:,,:), allocatable :: mask
    ok = .true.
    if (x /= 0) then
      xt = x * state%trace (qn_in)
    else
      xt = 0
    end if
    s = 0
    depth = state%get_depth ()

```

```

allocate (qn (depth), qn1 (depth), diagonal (depth))
call it%init (state)
do while (it%is_valid ())
  qn = it%get_quantum_numbers ()
  if (present (qn_in)) then
    if (.not. all (qn .fmatch. qn_in)) then
      call it%advance (); cycle
    end if
  end if
  if (all (qn%are_diagonal ())) then
    value = it%get_matrix_element ()
    if (real (value, default) < 0) then
      call state%write ()
      print *, value
      call msg_bug ("Event generation: " &
        // "Negative real part of squared matrix element value")
      value = 0
    end if
    s = s + value
    if (s > xt) exit
  end if
  call it%advance ()
end do
if (.not. it%is_valid ()) then
  if (s == 0) ok = .false.
  call it%init (state)
end if
allocate (single_state (depth))
do i = 1, depth
  call single_state(i)%init (store_values=.true.)
end do
if (present (correlated_state)) &
  call correlated_state%init (store_values=.true.)
qn = it%get_quantum_numbers ()
select case (mode)
case (FM_SELECT_HELICITY) ! single branch selected; shortcut
  do i = 1, depth
    call single_state(i)%add_state ([qn(i)], value=value)
  end do
  if (.not. present (correlated_state)) then
    do i = 1, size(single_state)
      call single_state(i)%freeze ()
    end do
    return
  end if
end select
allocate (qn_mask (depth))
call qn_mask%init (.false., .false., .false., .true.)
call qn%undefine (qn_mask)
select case (mode)
case (FM_FACTOR_HELICITY)
  allocate (mask (depth, depth))
  mask = .false.
  forall (i = 1:depth) mask(i,i) = .true.

```

```

end select
call it%init (state)
do while (it%is_valid ())
  qn1 = it%get_quantum_numbers ()
  if (all (qn .match. qn1)) then
    diagonal = qn1%are_diagonal ()
    value = it%get_matrix_element ()
    select case (mode)
    case (FM_IGNORE_HELICITY) ! trace over diagonal states that match qn
      if (all (diagonal)) then
        do i = 1, depth
          call single_state(i)%add_state &
            ([qn(i)], value=value, sum_values=.true.)
        end do
      end if
    case (FM_FACTOR_HELICITY) ! trace over all other particles
      do i = 1, depth
        if (all (diagonal .or. mask(:,i))) then
          call single_state(i)%add_state &
            ([qn1(i)], value=value, sum_values=.true.)
        end if
      end do
    end select
    if (present (correlated_state)) &
      call correlated_state%add_state (qn1, value=value)
  end if
  call it%advance ()
end do
do i = 1, depth
  call single_state(i)%freeze ()
end do
if (present (correlated_state)) &
  call correlated_state%freeze ()
end subroutine state_matrix_factorize

```

Quantum-number matching

This feature allows us to check whether a given string of PDG values matches, in any ordering, any of the flavor combinations that the state matrix provides. We will also request the permutation of the successful match.

This type provides an account of the state's flavor content. We store all flavor combinations, as `pdg` values, in an array, assuming that the length is uniform.

We check only the entries selected by `mask_match`. Among those, only the entries selected by `mask_sort` are sorted and thus matched without respecting array element order. The entries that correspond to a true value in the associated `mask` are sorted. The mapping from the original state to the sorted state is given by the index array `map`.

```

<State matrices: public>+≡
public :: state_flv_content_t

```

```

<State matrices: types>+≡
  type :: state_flv_content_t
    private
    integer, dimension(:,:), allocatable :: pdg
    integer, dimension(:,:), allocatable :: map
    logical, dimension(:), allocatable :: mask
  contains
    <State matrices: state flv content: TBP>
  end type state_flv_content_t

```

Output (debugging aid).

```

<State matrices: state flv content: TBP>≡
  procedure :: write => state_flv_content_write

<State matrices: procedures>+≡
  subroutine state_flv_content_write (state_flv, unit)
    class(state_flv_content_t), intent(in), target :: state_flv
    integer, intent(in), optional :: unit
    type(state_iterator_t) :: it
    integer :: u, n, d, i, j
    u = given_output_unit (unit)
    d = size (state_flv%pdg, 1)
    n = size (state_flv%pdg, 2)
    do i = 1, n
      write (u, "(2x,'PDG =')", advance="no")
      do j = 1, d
        write (u, "(1x,I0)", advance="no") state_flv%pdg(j,i)
      end do
      write (u, "(' :: map = (')", advance="no")
      do j = 1, d
        write (u, "(1x,I0)", advance="no") state_flv%map(j,i)
      end do
      write (u, "(' )')")
    end do
  end subroutine state_flv_content_write

```

Initialize with table length and mask. Each row of the map array, of length d , is initialized with $(0, 1, \dots, d)$.

```

<State matrices: state flv content: TBP>+≡
  procedure :: init => state_flv_content_init

<State matrices: procedures>+≡
  subroutine state_flv_content_init (state_flv, n, mask)
    class(state_flv_content_t), intent(out) :: state_flv
    integer, intent(in) :: n
    logical, dimension(:), intent(in) :: mask
    integer :: d, i
    d = size (mask)
    allocate (state_flv%pdg (d, n), source = 0)
    allocate (state_flv%map (d, n), source = spread ([i, i = 1, d], 2, n))
    allocate (state_flv%mask (d), source = mask)
  end subroutine state_flv_content_init

```

Manually fill the entries, one flavor set and mapping at a time.

```

<State matrices: state flv content: TBP>+≡
  procedure :: set_entry => state_flv_content_set_entry

<State matrices: procedures>+≡
  subroutine state_flv_content_set_entry (state_flv, i, pdg, map)
    class(state_flv_content_t), intent(inout) :: state_flv
    integer, intent(in) :: i
    integer, dimension(:), intent(in) :: pdg, map
    state_flv%pdg(:,i) = pdg
    where (map /= 0)
      state_flv%map(:,i) = map
    end where
  end subroutine state_flv_content_set_entry

```

Given a state matrix, determine the flavor content. That is, scan the state matrix and extract flavor only, build a new state matrix from that.

```

<State matrices: state flv content: TBP>+≡
  procedure :: fill => state_flv_content_fill

<State matrices: procedures>+≡
  subroutine state_flv_content_fill &
    (state_flv, state_full, mask)
    class(state_flv_content_t), intent(out) :: state_flv
    type(state_matrix_t), intent(in), target :: state_full
    logical, dimension(:), intent(in) :: mask
    type(state_matrix_t), target :: state_tmp
    type(state_iterator_t) :: it
    type(flavor_t), dimension(:), allocatable :: flv
    integer, dimension(:), allocatable :: pdg, pdg_subset
    integer, dimension(:), allocatable :: idx, map_subset, idx_subset, map
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: n, d, c, i
    call state_tmp%init ()
    d = state_full%get_depth ()
    allocate (flv (d), qn (d), pdg (d), idx (d), map (d))
    idx = [(i, i = 1, d)]
    c = count (mask)
    allocate (pdg_subset (c), map_subset (c), idx_subset (c))
    call it%init (state_full)
    do while (it%is_valid ())
      flv = it%get_flavor ()
      call qn%init (flv)
      call state_tmp%add_state (qn)
      call it%advance ()
    end do
    n = state_tmp%get_n_leaves ()
    call state_flv%init (n, mask)
    i = 0
    call it%init (state_tmp)
    do while (it%is_valid ())
      i = i + 1
      flv = it%get_flavor ()
      pdg = flv%get_pdg ()

```

```

        idx_subset = pack (idx, mask)
        pdg_subset = pack (pdg, mask)
        map_subset = order_abs (pdg_subset)
        map = unpack (idx_subset (map_subset), mask, idx)
        call state_flv%set_entry (i, &
            unpack (pdg_subset(map_subset), mask, pdg), &
            order (map))
        call it%advance ()
    end do
    call state_tmp%final ()
end subroutine state_flv_content_fill

```

Match a given flavor string against the flavor content. We sort the input string and check whether it matches any of the stored strings. If yes, return the mapping.

Only PDG entries under the preset mask are sorted before matching. The other entries must match exactly (i.e., without reordering). A zero entry matches anything. In any case, the length of the PDG string must be equal to the length d of the individual flavor-state entries.

(State matrices: state flv content: TBP)+≡

```

    procedure :: match => state_flv_content_match

```

(State matrices: procedures)+≡

```

subroutine state_flv_content_match (state_flv, pdg, success, map)
    class(state_flv_content_t), intent(in) :: state_flv
    integer, dimension(:), intent(in) :: pdg
    logical, intent(out) :: success
    integer, dimension(:), intent(out) :: map
    integer, dimension(:), allocatable :: pdg_subset, pdg_sorted, map1, map2
    integer, dimension(:), allocatable :: idx, map_subset, idx_subset
    integer :: i, n, c, d
    c = count (state_flv%mask)
    d = size (state_flv%pdg, 1)
    n = size (state_flv%pdg, 2)
    allocate (idx (d), source = [(i, i = 1, d)])
    allocate (idx_subset (c), pdg_subset (c), map_subset (c))
    allocate (pdg_sorted (d), map1 (d), map2 (d))
    idx_subset = pack (idx, state_flv%mask)
    pdg_subset = pack (pdg, state_flv%mask)
    map_subset = order_abs (pdg_subset)
    pdg_sorted = unpack (pdg_subset(map_subset), state_flv%mask, pdg)
    success = .false.
    do i = 1, n
        if (all (pdg_sorted == state_flv%pdg(:,i) &
            .or. pdg_sorted == 0)) then
            success = .true.
            exit
        end if
    end do
    if (success) then
        map1 = state_flv%map(:,i)
        map2 = unpack (idx_subset(map_subset), state_flv%mask, idx)
        map = map2(map1)
    end if
end subroutine state_flv_content_match

```

```

        where (pdg == 0) map = 0
    end if
end subroutine state_flv_content_match

```

```

<State matrices: procedures>+≡
    elemental function pacify_complex (c_in) result (c_pac)
        complex(default), intent(in) :: c_in
        complex(default) :: c_pac
        c_pac = c_in
        if (real(c_pac) == -real(c_pac)) then
            c_pac = &
                cmplx (0._default, aimag(c_pac), kind=default)
        end if
        if (aimag(c_pac) == -aimag(c_pac)) then
            c_pac = &
                cmplx (real(c_pac), 0._default, kind=default)
        end if
    end function pacify_complex

```

11.1.6 Unit tests

```

<State matrices: public>+≡
    public :: state_matrix_test

<State matrices: procedures>+≡
    subroutine state_matrix_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <State matrices: execute tests>
    end subroutine state_matrix_test

```

Create two quantum states of equal depth and merge them.

```

<State matrices: execute tests>≡
    call test (state_matrix_1, "state_matrix_1", &
        "check merge of quantum states of equal depth", &
        u, results)

<State matrices: tests>≡
    subroutine state_matrix_1 (u)
        integer, intent(in) :: u
        type(state_matrix_t) :: state1, state2, state3
        type(flavor_t), dimension(3) :: flv
        type(color_t), dimension(3) :: col
        type(quantum_numbers_t), dimension(3) :: qn

        write (u, "(A)")  "* Test output: state_matrix_1"
        write (u, "(A)")  "* Purpose: create and merge two quantum states"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")
    end subroutine state_matrix_1

```

```

write (u, "(A)")  "* State matrix 1"
write (u, "(A)")

call state1%init ()
call flv%init ([1, 2, 11])
call qn%init (flv, helicity ([ 1, 1, 1]))
call state1%add_state (qn)
call qn%init (flv, helicity ([ 1, 1, 1], [-1, 1, -1]))
call state1%add_state (qn)
call state1%freeze ()
call state1%write (u)

write (u, "(A)")
write (u, "(A)")  "* State matrix 2"
write (u, "(A)")

call state2%init ()
call col(1)%init ([501])
call col(2)%init ([-501])
call col(3)%init ([0])
call qn%init (col, helicity ([-1, -1, 0]))
call state2%add_state (qn)
call col(3)%init ([99])
call qn%init (col, helicity ([-1, -1, 0]))
call state2%add_state (qn)
call state2%freeze ()
call state2%write (u)

write (u, "(A)")
write (u, "(A)")  "* Merge the state matrices"
write (u, "(A)")

call merge_state_matrices (state1, state2, state3)
call state3%write (u)

write (u, "(A)")
write (u, "(A)")  "* Collapse the state matrix"
write (u, "(A)")

call state3%collapse (quantum_numbers_mask (.false., .false., &
      [.true., .false., .false.]))
call state3%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"
write (u, "(A)")

call state1%final ()
call state2%final ()
call state3%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: state_matrix_1"
write (u, "(A)")

```



```
end subroutine state_matrix_1
```

Create a correlated three-particle state matrix and factorize it.

(State matrices: execute tests)+≡

```
call test (state_matrix_2, "state_matrix_2", &
  "check factorizing 3-particle state matrix", &
  u, results)
```

(State matrices: tests)+≡

```
subroutine state_matrix_2 (u)
  integer, intent(in) :: u
  type(state_matrix_t) :: state
  type(state_matrix_t), dimension(:), allocatable :: single_state
  type(state_matrix_t) :: correlated_state
  complex(default) :: z, val
  complex(default), dimension(-1:1) :: v
  integer :: f, h11, h12, h21, h22, i, mode
  type(flavor_t), dimension(2) :: flv
  type(color_t), dimension(2) :: col
  type(helicity_t), dimension(2) :: hel
  type(quantum_numbers_t), dimension(2) :: qn
  logical :: ok

  write (u, "(A)")
  write (u, "(A)")  "* Test output: state_matrix_2"
  write (u, "(A)")  "* Purpose: factorize correlated 3-particle state"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization"
  write (u, "(A)")

  z = 1 / 2._default
  v(-1) = (0.6_default, 0._default)
  v( 1) = (0._default, 0.8_default)
  call state%init ()
  do f = 1, 2
    do h11 = -1, 1, 2
      do h12 = -1, 1, 2
        do h21 = -1, 1, 2
          do h22 = -1, 1, 2
            call flv%init ([f, -f])
            call col(1)%init ([1])
            call col(2)%init ([-1])
            call hel%init ([h11,h12], [h21, h22])
            call qn%init (flv, col, hel)
            val = z * v(h11) * v(h12) * conjg (v(h21) * v(h22))
            call state%add_state (qn)
          end do
        end do
      end do
    end do
  end do
  call state%freeze ()
```

```

call state%write (u)

write (u, "(A)")
write (u, "(A,'(', " // FMT_19 // ",',', " // FMT_19 // ",')')") &
    "* Trace = ", state%trace ()
write (u, "(A)")

do mode = 1, 3
    write (u, "(A)")
    write (u, "(A,I1)")    "* Mode = ", mode
    call state%factorize &
        (mode, 0.15_default, ok, single_state, correlated_state)
    do i = 1, size (single_state)
        write (u, "(A)")
        call single_state(i)%write (u)
        write (u, "(A,'(', " // FMT_19 // ",',', " // FMT_19 // ",')')") &
            "Trace = ", single_state(i)%trace ()
    end do
    write (u, "(A)")
    call correlated_state%write (u)
    write (u, "(A,'(', " // FMT_19 // ",',', " // FMT_19 // ",')')") &
        "Trace = ", correlated_state%trace ()
    do i = 1, size(single_state)
        call single_state(i)%final ()
    end do
    call correlated_state%final ()
end do

write (u, "(A)")
write (u, "(A)")    "* Cleanup"

call state%final ()

write (u, "(A)")
write (u, "(A)")    "* Test output end: state_matrix_2"

end subroutine state_matrix_2

```

Create a colored state matrix and add color contractions.

(State matrices: execute tests)+≡

```

call test (state_matrix_3, "state_matrix_3", &
    "check factorizing 3-particle state matrix", &
    u, results)

```

(State matrices: tests)+≡

```

subroutine state_matrix_3 (u)
    use physics_defs, only: HADRON_REMNANT_TRIPLET, HADRON_REMNANT_OCTET
    integer, intent(in) :: u
    type(state_matrix_t) :: state
    type(flavor_t), dimension(4) :: flv
    type(color_t), dimension(4) :: col
    type(quantum_numbers_t), dimension(4) :: qn

    write (u, "(A)")    "* Test output: state_matrix_3"

```

```

write (u, "(A)")  "*   Purpose: add color connections to colored state"
write (u, "(A)")

write (u, "(A)")  "*   Initialization"
write (u, "(A)")

call state%init ()
call flv%init ([ 1, -HADRON_REMNANT_TRIPLET, -1, HADRON_REMNANT_TRIPLET ])
call col(1)%init ([17])
call col(2)%init ([-17])
call col(3)%init ([-19])
call col(4)%init ([19])
call qn%init (flv, col)
call state%add_state (qn)
call flv%init ([ 1, -HADRON_REMNANT_TRIPLET, 21, HADRON_REMNANT_OCTET ])
call col(1)%init ([17])
call col(2)%init ([-17])
call col(3)%init ([3, -5])
call col(4)%init ([5, -3])
call qn%init (flv, col)
call state%add_state (qn)
call state%freeze ()

write (u, "(A)")  "* State:"
write (u, "(A)")

call state%write (u)
call state%add_color_contractions ()

write (u, "(A)")  "* State with contractions:"
write (u, "(A)")

call state%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call state%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: state_matrix_3"

end subroutine state_matrix_3

```

Create a correlated three-particle state matrix, write it to file and read again.

```

<State matrices: execute tests>+≡
  call test (state_matrix_4, "state_matrix_4", &
    "check raw I/O", &
    u, results)

<State matrices: tests>+≡
  subroutine state_matrix_4 (u)
    integer, intent(in) :: u
    type(state_matrix_t), allocatable :: state

```

```

complex(default) :: z, val
complex(default), dimension(-1:1) :: v
integer :: f, h11, h12, h21, h22, i, mode
type(flavor_t), dimension(2) :: flv
type(color_t), dimension(2) :: col
type(helicity_t), dimension(2) :: hel
type(quantum_numbers_t), dimension(2) :: qn
integer :: unit, iostat

write (u, "(A)")
write (u, "(A)")  "* Test output: state_matrix_4"
write (u, "(A)")  "* Purpose: raw I/O for correlated 3-particle state"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

allocate (state)

z = 1 / 2._default
v(-1) = (0.6_default, 0._default)
v( 1) = (0._default, 0.8_default)
call state%init ()
do f = 1, 2
  do h11 = -1, 1, 2
    do h12 = -1, 1, 2
      do h21 = -1, 1, 2
        do h22 = -1, 1, 2
          call flv%init ([f, -f])
          call col(1)%init ([1])
          call col(2)%init ([-1])
          call hel%init ([h11,h12], [h21, h22])
          call qn%init (flv, col, hel)
          val = z * v(h11) * v(h12) * conjg (v(h21) * v(h22))
          call state%add_state (qn)
        end do
      end do
    end do
  end do
end do
call state%freeze ()

call state%set_norm (3._default)
do i = 1, state%get_n_leaves ()
  call state%set_matrix_element (i, cmplx (2 * i, 2 * i + 1, default))
end do

call state%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write to file and read again "
write (u, "(A)")

unit = free_unit ()

```

```

open (unit, action="readwrite", form="unformatted", status="scratch")
call state%write_raw (unit)
call state%final ()
deallocate (state)

allocate(state)
rewind (unit)
call state%read_raw (unit, iostat=iostat)
close (unit)

call state%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call state%final ()
deallocate (state)

write (u, "(A)")
write (u, "(A)")  "* Test output end: state_matrix_4"

end subroutine state_matrix_4

```

Create a flavor-content object for a given state matrix and match it against trial flavor (i.e., PDG) strings.

```

<State matrices: execute tests>+≡
call test (state_matrix_5, "state_matrix_5", &
  "check flavor content", &
  u, results)

<State matrices: tests>+≡
subroutine state_matrix_5 (u)
  integer, intent(in) :: u
  type(state_matrix_t), allocatable, target :: state
  type(state_iterator_t) :: it
  type(state_flv_content_t), allocatable :: state_flv
  type(flavor_t), dimension(4) :: flv1, flv2, flv3, flv4
  type(color_t), dimension(4) :: col1, col2
  type(helicity_t), dimension(4) :: hel1, hel2, hel3
  type(quantum_numbers_t), dimension(4) :: qn
  logical, dimension(4) :: mask

  write (u, "(A)")  "* Test output: state_matrix_5"
  write (u, "(A)")  "* Purpose: check flavor-content state"
  write (u, "(A)")

  write (u, "(A)")  "* Set up arbitrary state matrix"
  write (u, "(A)")

  call flv1%init ([1, 4, 2, 7])
  call flv2%init ([1, 3, -3, 8])
  call flv3%init ([5, 6, 3, 7])
  call flv4%init ([6, 3, 5, 8])
  call hel1%init ([0, 1, -1, 0])

```

```

call hel2%init ([0, 1, 1, 1])
call hel3%init ([1, 0, 0, 0])
call col1(1)%init ([0])
call col1(2)%init ([0])
call col1(3)%init ([0])
call col1(4)%init ([0])
call col2(1)%init ([5, -6])
call col2(2)%init ([0])
call col2(3)%init ([6, -5])
call col2(4)%init ([0])

allocate (state)
call state%init ()
call qn%init (flv1, col1, hel1)
call state%add_state (qn)
call qn%init (flv1, col1, hel2)
call state%add_state (qn)
call qn%init (flv3, col1, hel3)
call state%add_state (qn)
call qn%init (flv4, col1, hel3)
call state%add_state (qn)
call qn%init (flv1, col2, hel3)
call state%add_state (qn)
call qn%init (flv2, col2, hel2)
call state%add_state (qn)
call qn%init (flv2, col2, hel1)
call state%add_state (qn)
call qn%init (flv2, col1, hel1)
call state%add_state (qn)
call qn%init (flv3, col1, hel1)
call state%add_state (qn)
call qn%init (flv3, col2, hel3)
call state%add_state (qn)
call qn%init (flv1, col1, hel1)
call state%add_state (qn)

write (u, "(A)")  "* Quantum number content"
write (u, "(A)")

call it%init (state)
do while (it%is_valid ())
    call quantum_numbers_write (it%get_quantum_numbers (), u)
    write (u, *)
    call it%advance ()
end do

write (u, "(A)")
write (u, "(A)")  "* Extract the flavor content"
write (u, "(A)")

mask = [.true., .true., .true., .false.]

allocate (state_flv)
call state_flv%fill (state, mask)

```

```

call state_flv%write (u)

write (u, "(A)")
write (u, "(A)")  "* Match trial sets"
write (u, "(A)")

call check ([1, 2, 3, 0])
call check ([1, 4, 2, 0])
call check ([4, 2, 1, 0])
call check ([1, 3, -3, 0])
call check ([1, -3, 3, 0])
call check ([6, 3, 5, 0])

write (u, "(A)")
write (u, "(A)")  "* Determine the flavor content with mask"
write (u, "(A)")

mask = [.false., .true., .true., .false.]

call state_flv%fill (state, mask)
call state_flv%write (u)

write (u, "(A)")
write (u, "(A)")  "* Match trial sets"
write (u, "(A)")

call check ([1, 2, 3, 0])
call check ([1, 4, 2, 0])
call check ([4, 2, 1, 0])
call check ([1, 3, -3, 0])
call check ([1, -3, 3, 0])
call check ([6, 3, 5, 0])

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

deallocate (state_flv)

call state%final ()
deallocate (state)

write (u, "(A)")
write (u, "(A)")  "* Test output end: state_matrix_5"

contains

subroutine check (pdg)
  integer, dimension(4), intent(in) :: pdg
  integer, dimension(4) :: map
  logical :: success
  call state_flv%match (pdg, success, map)
  write (u, "(2x,4(1x,I0),':',1x,L1)", advance="no")  pdg, success
  if (success) then
    write (u, "(2x,'map = (',4(1x,I0),',' )')")  map
  end if
end subroutine check

```

```

        else
            write (u, *)
        end if
    end subroutine check

end subroutine state_matrix_5

```

11.2 Interactions

This module defines the `interaction_t` type. It is an extension of the `state_matrix_t` type.

The state matrix is a representation of a multi-particle density matrix. It implements all possible flavor, color, and quantum-number assignments of the entries in a generic density matrix, and it can hold a complex matrix element for each entry. (Note that this matrix can hold non-diagonal entries in color and helicity space.) The `interaction_t` object associates this with a list of momenta, such that the whole object represents a multi-particle state.

The `interaction_t` holds information about which particles are incoming, virtual (i.e., kept for the records), or outgoing. Each particle can be associated to a source within another interaction. This allows us to automatically fill those interaction momenta which have been computed or defined elsewhere. It also contains internal parent-child relations and flags for (virtual) particles which are to be treated as resonances.

A quantum-number mask array summarizes, for each particle within the interaction, the treatment of flavor, color, or helicity (expose or ignore). A list of locks states which particles are bound to have an identical quantum-number mask. This is useful when the mask is changed at one place.

```

<interactions.f90>≡
  <File header>

  module interactions

    <Use kinds>
    use io_units
    use unit_tests
    use diagnostics
    use sorting
    use lorentz
    use flavors
    use colors
    use helicities
    use quantum_numbers
    use state_matrices

    <Standard module head>

    <Interactions: public>

    <Interactions: types>

```



```
⟨Interactions: interfaces⟩
```

```
contains
```

```
⟨Interactions: procedures⟩
```

```
⟨Interactions: tests⟩
```

```
end module interactions
```

11.2.1 External interaction links

Each particle in an interaction can have a link to a corresponding particle in another interaction. This allows to fetch the momenta of incoming or virtual particles from the interaction where they are defined. The link object consists of a pointer to the interaction and an index.

```
⟨Interactions: types⟩≡
  type :: external_link_t
  private
    type(interaction_t), pointer :: int => null ()
    integer :: i
  end type external_link_t
```

Set an external link.

```
⟨Interactions: procedures⟩≡
  subroutine external_link_set (link, int, i)
    type(external_link_t), intent(out) :: link
    type(interaction_t), target, intent(in) :: int
    integer, intent(in) :: i
    if (i /= 0) then
      link%int => int
      link%i = i
    end if
  end subroutine external_link_set
```

Reassign an external link to a new interaction (which should be an image of the original target).

```
⟨Interactions: procedures⟩+≡
  subroutine external_link_reassign (link, int_src, int_target)
    type(external_link_t), intent(inout) :: link
    type(interaction_t), intent(in) :: int_src
    type(interaction_t), intent(in), target :: int_target
    if (associated (link%int)) then
      if (link%int%tag == int_src%tag) link%int => int_target
    end if
  end subroutine external_link_reassign
```

Return true if the link is set

```
⟨Interactions: procedures⟩+≡
  function external_link_is_set (link) result (flag)
    logical :: flag
```

```

        type(external_link_t), intent(in) :: link
        flag = associated (link%int)
    end function external_link_is_set

```

Return the interaction pointer.

```

<Interactions: public>≡
    public :: external_link_get_ptr
<Interactions: procedures>+≡
    function external_link_get_ptr (link) result (int)
        type(interaction_t), pointer :: int
        type(external_link_t), intent(in) :: link
        int => link%int
    end function external_link_get_ptr

```

Return the index within that interaction

```

<Interactions: public>+≡
    public :: external_link_get_index
<Interactions: procedures>+≡
    function external_link_get_index (link) result (i)
        integer :: i
        type(external_link_t), intent(in) :: link
        i = link%i
    end function external_link_get_index

```

Return a pointer to the momentum of the corresponding particle. If there is no association, return a null pointer.

```

<Interactions: procedures>+≡
    function external_link_get_momentum_ptr (link) result (p)
        type(vector4_t), pointer :: p
        type(external_link_t), intent(in) :: link
        if (associated (link%int)) then
            p => link%int%p(link%i)
        else
            p => null ()
        end if
    end function external_link_get_momentum_ptr

```

11.2.2 Internal relations

In addition to the external links, particles within the interaction have parent-child relations. Here, more than one link is possible, and we set up an array.

```

<Interactions: types>+≡
    type :: internal_link_list_t
        private
        integer :: length = 0
        integer, dimension(:), allocatable :: link
    contains
        <Interactions: internal link list: TBP>
    end type internal_link_list_t

```

Output, non-advancing.

```

<Interactions: internal link list: TBP>≡
  procedure :: write => internal_link_list_write

<Interactions: procedures>+≡
  subroutine internal_link_list_write (object, unit)
    class(internal_link_list_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    do i = 1, object%length
      write (u, "(1x,I0)", advance="no") object%link(i)
    end do
  end subroutine internal_link_list_write

```

Append an item. Start with an array size of 2 and double the size if necessary.

Make sure that the indices are stored in ascending order. To this end, shift the existing entries right, starting from the end, as long as they are larger than the new entry.

```

<Interactions: internal link list: TBP>+≡
  procedure :: append => internal_link_list_append

<Interactions: procedures>+≡
  subroutine internal_link_list_append (link_list, link)
    class(internal_link_list_t), intent(inout) :: link_list
    integer, intent(in) :: link
    integer :: l, j
    integer, dimension(:), allocatable :: tmp
    l = link_list%length
    if (allocated (link_list%link)) then
      if (l == size (link_list%link)) then
        allocate (tmp (2 * l))
        tmp(:l) = link_list%link
        call move_alloc (from = tmp, to = link_list%link)
      end if
    else
      allocate (link_list%link (2))
    end if
    link_list%link(l+1) = link
    SHIFT_LINK_IN_PLACE: do j = l, 1, -1
      if (link >= link_list%link(j)) then
        exit SHIFT_LINK_IN_PLACE
      else
        link_list%link(j+1) = link_list%link(j)
        link_list%link(j) = link
      end if
    end do SHIFT_LINK_IN_PLACE
    link_list%length = l + 1
  end subroutine internal_link_list_append

```

Return true if the link list is nonempty:

```

<Interactions: internal link list: TBP>+≡
  procedure :: has_entries => internal_link_list_has_entries

```

```

⟨Interactions: procedures⟩+≡
  function internal_link_list_has_entries (link_list) result (flag)
    class(internal_link_list_t), intent(in) :: link_list
    logical :: flag
    flag = link_list%length > 0
  end function internal_link_list_has_entries

```

Return the list length

```

⟨Interactions: internal link list: TBP⟩+≡
  procedure :: get_length => internal_link_list_get_length

⟨Interactions: procedures⟩+≡
  function internal_link_list_get_length (link_list) result (length)
    class(internal_link_list_t), intent(in) :: link_list
    integer :: length
    length = link_list%length
  end function internal_link_list_get_length

```

Return an entry.

```

⟨Interactions: internal link list: TBP⟩+≡
  procedure :: get_link => internal_link_list_get_link

⟨Interactions: procedures⟩+≡
  function internal_link_list_get_link (link_list, i) result (link)
    class(internal_link_list_t), intent(in) :: link_list
    integer, intent(in) :: i
    integer :: link
    if (i <= link_list%length) then
      link = link_list%link(i)
    else
      call msg_bug ("Internal link list: out of bounds")
    end if
  end function internal_link_list_get_link

```

11.2.3 The interaction type

An interaction is an entangled system of particles. Thus, the interaction object consists of two parts: the subevent, and the quantum state which technically is a trie. The subnode levels beyond the trie root node are in correspondence to the subevent, so both should be traversed in parallel.

The subevent is implemented as an allocatable array of four-momenta. The first **n_in** particles are incoming, **n_vir** particles in-between can be kept for bookkeeping, and the last **n_out** particles are outgoing.

Distinct interactions are linked by their particles: for each particle, we have the possibility of links to corresponding particles in other interactions. Furthermore, for bookkeeping purposes we have a self-link array **relations** where the parent-child relations are kept, and a flag array **resonant** which is set for an intermediate resonance.

Each momentum is associated with masks for flavor, color, and helicity. If a mask entry is set, the associated quantum number is to be ignored for that particle. If any mask has changed, the flag **update** is set.

We can have particle pairs locked together. If this is the case, the corresponding mask entries are bound to be equal. This is useful for particles that go through the interaction.

The interaction tag serves bookkeeping purposes. In particular, it identifies links in printout.

```

<Interactions: public>+≡
    public :: interaction_t

<Interactions: types>+≡
    type :: interaction_t
    private
    integer :: tag = 0
    type(state_matrix_t) :: state_matrix
    integer :: n_in = 0
    integer :: n_vir = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    logical, dimension(:), allocatable :: p_is_known
    type(vector4_t), dimension(:), allocatable :: p
    type(external_link_t), dimension(:), allocatable :: source
    type(internal_link_list_t), dimension(:), allocatable :: parents
    type(internal_link_list_t), dimension(:), allocatable :: children
    logical, dimension(:), allocatable :: resonant
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
    integer, dimension(:), allocatable :: hel_lock
    logical :: update_state_matrix = .false.
    logical :: update_values = .false.
contains
    <Interactions: interaction: TBP>
end type interaction_t

```

Initialize the particle array with a fixed size. The first `n_in` particles are incoming, the rest outgoing. Masks are optional. There is also an optional tag. The interaction still needs fixing the values, but that is to be done after all branches have been added.

Interaction tags are assigned consecutively, using a `saved` variable local to this procedure. If desired, we can provide a seed for the interaction tags. Such a seed should be positive. The default seed is one. `tag=0` indicates an empty interaction.

If `set_relations` is set and true, we establish parent-child relations for all incoming and outgoing particles. Virtual particles are skipped; this option is normally used only for interactions without virtual particles.

```

<Interactions: interaction: TBP>≡
    procedure :: basic_init => interaction_init

<Interactions: procedures>+≡
    subroutine interaction_init &
        (int, n_in, n_vir, n_out, &
         tag, resonant, mask, hel_lock, set_relations, store_values)
    class(interaction_t), intent(out) :: int
    integer, intent(in) :: n_in, n_vir, n_out
    integer, intent(in), optional :: tag
    logical, dimension(:), intent(in), optional :: resonant

```

```

type(quantum_numbers_mask_t), dimension(:), intent(in), optional :: mask
integer, dimension(:), intent(in), optional :: hel_lock
logical, intent(in), optional :: set_relations, store_values
logical :: set_rel
integer :: i, j
set_rel = .false.; if (present (set_relations)) set_rel = set_relations
call interaction_set_tag (int, tag)
call int%state_matrix%init (store_values)
int%n_in = n_in
int%n_vir = n_vir
int%n_out = n_out
int%n_tot = n_in + n_vir + n_out
allocate (int%p_is_known (int%n_tot))
int%p_is_known = .false.
allocate (int%p (int%n_tot))
allocate (int%source (int%n_tot))
allocate (int%parents (int%n_tot))
allocate (int%children (int%n_tot))
allocate (int%resonant (int%n_tot))
if (present (resonant)) then
    int%resonant = resonant
else
    int%resonant = .false.
end if
allocate (int%mask (int%n_tot))
allocate (int%hel_lock (int%n_tot))
if (present (mask)) then
    int%mask = mask
end if
if (present (hel_lock)) then
    int%hel_lock = hel_lock
else
    int%hel_lock = 0
end if
int%update_state_matrix = .false.
int%update_values = .true.
if (set_rel) then
    do i = 1, n_in
        do j = 1, n_out
            call int%relate (i, n_in + j)
        end do
    end do
end if
end subroutine interaction_init

```

Set or create a unique tag for the interaction. Without interaction, reset the tag counter.

(Interactions: procedures)+≡

```

subroutine interaction_set_tag (int, tag)
type(interaction_t), intent(inout), optional :: int
integer, intent(in), optional :: tag
integer, save :: stored_tag = 1
if (present (int)) then

```

```

        if (present (tag)) then
            int%tag = tag
        else
            int%tag = stored_tag
            stored_tag = stored_tag + 1
        end if
    else if (present (tag)) then
        stored_tag = tag
    else
        stored_tag = 1
    end if
end subroutine interaction_set_tag

```

The public interface for the previous procedure only covers the reset functionality.

```

<Interactions: public>+≡
    public :: reset_interaction_counter

<Interactions: procedures>+≡
    subroutine reset_interaction_counter (tag)
        integer, intent(in), optional :: tag
        call interaction_set_tag (tag=tag)
    end subroutine reset_interaction_counter

```

Finalizer: The state-matrix object contains pointers.

```

<Interactions: interaction: TBP>+≡
    procedure :: final => interaction_final

<Interactions: procedures>+≡
    subroutine interaction_final (object)
        class(interaction_t), intent(inout) :: object
        call object%state_matrix%final ()
    end subroutine interaction_final

```

Output. The `verbose` option refers to the state matrix output.

```

<Interactions: interaction: TBP>+≡
    procedure :: basic_write => interaction_write

<Interactions: procedures>+≡
    subroutine interaction_write &
        (int, unit, verbose, show_momentum_sum, show_mass, show_state, &
         col_verbose, testflag)
        class(interaction_t), intent(in) :: int
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
        logical, intent(in), optional :: show_state, col_verbose, testflag
        integer :: u
        integer :: i, index_link
        type(interaction_t), pointer :: int_link
        logical :: show_st
        u = given_output_unit (unit); if (u < 0) return
        show_st = .true.; if (present (show_state)) show_st = show_state
        if (int%tag /= 0) then
            write (u, "(1x,A,I0)") "Interaction: ", int%tag

```

```

do i = 1, int%n_tot
  if (i == 1 .and. int%n_in > 0) then
    write (u, "(1x,A)") "Incoming:"
  else if (i == int%n_in + 1 .and. int%n_vir > 0) then
    write (u, "(1x,A)") "Virtual:"
  else if (i == int%n_in + int%n_vir + 1 .and. int%n_out > 0) then
    write (u, "(1x,A)") "Outgoing:"
  end if
  write (u, "(1x,A,1x,I0)", advance="no") "Particle", i
  if (allocated (int%resonant)) then
    if (int%resonant(i)) then
      write (u, "(A)") "[r]"
    else
      write (u, *)
    end if
  else
    write (u, *)
  end if
  if (allocated (int%p)) then
    if (int%p_is_known(i)) then
      call vector4_write (int%p(i), u, show_mass, testflag)
    else
      write (u, "(A)") " [momentum undefined]"
    end if
  else
    write (u, "(A)") " [momentum not allocated]"
  end if
  if (allocated (int%mask)) then
    write (u, "(1x,A)", advance="no") "mask [fch] = "
    call int%mask(i)%write (u)
    write (u, *)
  end if
  if (int%parents(i)%has_entries () &
    .or. int%children(i)%has_entries ()) then
    write (u, "(1x,A)", advance="no") "internal links:"
    call int%parents(i)%write (u)
    if (int%parents(i)%has_entries () &
      write (u, "(1x,A)", advance="no") "=>"
    write (u, "(1x,A)", advance="no") "X"
    if (int%children(i)%has_entries () &
      write (u, "(1x,A)", advance="no") "=>"
    call int%children(i)%write (u)
    write (u, *)
  end if
  if (allocated (int%hel_lock)) then
    if (int%hel_lock(i) /= 0) then
      write (u, "(1x,A,1x,I0)") "helicity lock:", int%hel_lock(i)
    end if
  end if
  if (external_link_is_set (int%source(i))) then
    write (u, "(1x,A)", advance="no") "source:"
    int_link => external_link_get_ptr (int%source(i))
    index_link = external_link_get_index (int%source(i))
    write (u, "(1x,'(,I0,)',I0)", advance="no") &

```



```

        int_link%tag, index_link
        write (u, *)
    end if
end do
if (present (show_momentum_sum)) then
    if (allocated (int%p) .and. show_momentum_sum) then
        write (u, "(1x,A)") "Incoming particles (sum):"
        call vector4_write &
            (sum (int%p(1:int%n_in)), u, show_mass = show_mass)
        write (u, "(1x,A)") "Outgoing particles (sum):"
        call vector4_write &
            (sum (int%p(int%n_in+int%n_vir+1:)), u, show_mass = show_mass)
        write (u, *)
    end if
end if
if (show_st) then
    call int%state_matrix%write (write_value_list=verbose, &
        verbose=verbose, unit=unit, col_verbose=col_verbose, &
        testflag = testflag)
end if
else
    write (u, "(1x,A)") "Interaction: [empty]"
end if
end subroutine interaction_write

```

Assignment: We implement this as a deep copy. This applies, in particular, to the state-matrix and internal-link components. Furthermore, the new interaction acquires a new tag.

```

<Interactions: public>+=
    public :: assignment(=)

<Interactions: interfaces>=
    interface assignment(=)
        module procedure interaction_assign
    end interface

<Interactions: procedures>+=
    subroutine interaction_assign (int_out, int_in)
        type(interaction_t), intent(out) :: int_out
        type(interaction_t), intent(in), target :: int_in
        call interaction_set_tag (int_out)
        int_out%state_matrix = int_in%state_matrix
        int_out%n_in = int_in%n_in
        int_out%n_out = int_in%n_out
        int_out%n_vir = int_in%n_vir
        int_out%n_tot = int_in%n_tot
        if (allocated (int_in%p_is_known)) then
            allocate (int_out%p_is_known (size (int_in%p_is_known)))
            int_out%p_is_known = int_in%p_is_known
        end if
        if (allocated (int_in%p)) then
            allocate (int_out%p (size (int_in%p)))
            int_out%p = int_in%p
        end if
    end subroutine

```

```

end if
if (allocated (int_in%source)) then
  allocate (int_out%source (size (int_in%source)))
  int_out%source = int_in%source
end if
if (allocated (int_in%parents)) then
  allocate (int_out%parents (size (int_in%parents)))
  int_out%parents = int_in%parents
end if
if (allocated (int_in%children)) then
  allocate (int_out%children (size (int_in%children)))
  int_out%children = int_in%children
end if
if (allocated (int_in%resonant)) then
  allocate (int_out%resonant (size (int_in%resonant)))
  int_out%resonant = int_in%resonant
end if
if (allocated (int_in%mask)) then
  allocate (int_out%mask (size (int_in%mask)))
  int_out%mask = int_in%mask
end if
if (allocated (int_in%hel_lock)) then
  allocate (int_out%hel_lock (size (int_in%hel_lock)))
  int_out%hel_lock = int_in%hel_lock
end if
int_out%update_state_matrix = int_in%update_state_matrix
int_out%update_values = int_in%update_values
end subroutine interaction_assign

```

11.2.4 Methods inherited from the state matrix member

Until F2003 is standard, we cannot implement inheritance directly. Therefore, we need wrappers for “inherited” methods.

Make a new branch in the state matrix if it does not yet exist. This is not just a wrapper but it introduces the interaction mask: where a quantum number is masked, it is not transferred but set undefined. After this, the value array has to be updated.

```

<Interactions: interaction: TBP>+≡
  procedure :: add_state => interaction_add_state

<Interactions: procedures>+≡
  subroutine interaction_add_state &
    (int, qn, index, value, sum_values, counter_index, me_index)
    class(interaction_t), intent(inout) :: int
    type(quantum_numbers_t), dimension(:), intent(in) :: qn
    integer, intent(in), optional :: index
    complex(default), intent(in), optional :: value
    logical, intent(in), optional :: sum_values
    integer, intent(in), optional :: counter_index
    integer, intent(out), optional :: me_index
    type(quantum_numbers_t), dimension(size(qn)) :: qn_tmp
    qn_tmp = qn

```

```

    call qn_tmp%undefine (int%mask)
    call int%state_matrix%add_state (qn_tmp, index, value, sum_values, &
        counter_index, me_index)
    int%update_values = .true.
end subroutine interaction_add_state

```

Freeze the quantum state: First collapse the quantum state, i.e., remove quantum numbers if any mask has changed, then fix the array of value pointers.

```

<Interactions: interaction: TBP>+≡
    procedure :: freeze => interaction_freeze

<Interactions: procedures>+≡
    subroutine interaction_freeze (int)
        class(interaction_t), intent(inout) :: int
        if (int%update_state_matrix) then
            call int%state_matrix%collapse (int%mask)
            int%update_state_matrix = .false.
            int%update_values = .true.
        end if
        if (int%update_values) then
            call int%state_matrix%freeze ()
            int%update_values = .false.
        end if
    end subroutine interaction_freeze

```

Return true if the state matrix is empty.

```

<Interactions: interaction: TBP>+≡
    procedure :: is_empty => interaction_is_empty

<Interactions: procedures>+≡
    function interaction_is_empty (int) result (flag)
        class(interaction_t), intent(in) :: int
        logical :: flag
        flag = int%state_matrix%is_empty ()
    end function interaction_is_empty

```

Get the number of values stored in the state matrix:

```

<Interactions: interaction: TBP>+≡
    procedure :: get_n_matrix_elements => &
        interaction_get_n_matrix_elements

<Interactions: procedures>+≡
    function interaction_get_n_matrix_elements (int) result (n)
        class(interaction_t), intent(in) :: int
        integer :: n
        n = int%state_matrix%get_n_matrix_elements ()
    end function interaction_get_n_matrix_elements

```

Get the norm of the state matrix (if the norm has been taken out, otherwise this would be unity).

```

<Interactions: interaction: TBP>+≡
    procedure :: get_norm => interaction_get_norm

```

```

<Interactions: procedures>+≡
function interaction_get_norm (int) result (norm)
  real(default) :: norm
  class(interaction_t), intent(in) :: int
  norm = int%state_matrix%get_norm ()
end function interaction_get_norm

```

Get the quantum number array that corresponds to a given index.

```

<Interactions: interaction: TBP>+≡
procedure :: get_quantum_numbers => interaction_get_quantum_numbers

<Interactions: procedures>+≡
function interaction_get_quantum_numbers (int, i) result (qn)
  class(interaction_t), intent(in), target :: int
  type(quantum_numbers_t), dimension(:), allocatable :: qn
  integer, intent(in) :: i
  allocate (qn (int%state_matrix%get_depth ()))
  qn = int%state_matrix%get_quantum_numbers (i)
end function interaction_get_quantum_numbers

```

Get the matrix element that corresponds to a set of quantum numbers, a given index, or return the whole array.

```

<Interactions: interaction: TBP>+≡
procedure :: get_matrix_element => interaction_get_matrix_element

<Interactions: procedures>+≡
function interaction_get_matrix_element (int, i) result (me)
  class(interaction_t), intent(in) :: int
  complex(default) :: me
  integer, intent(in) :: i
  me = int%state_matrix%get_matrix_element (i)
end function interaction_get_matrix_element

```

Set the complex value(s) stored in the quantum state.

```

<Interactions: interaction: TBP>+≡
generic :: set_matrix_element => interaction_set_matrix_element_qn, &
  interaction_set_matrix_element_all, &
  interaction_set_matrix_element_array, &
  interaction_set_matrix_element_single, &
  interaction_set_matrix_element_clone
procedure :: interaction_set_matrix_element_qn
procedure :: interaction_set_matrix_element_all
procedure :: interaction_set_matrix_element_array
procedure :: interaction_set_matrix_element_single
procedure :: interaction_set_matrix_element_clone

```

Indirect access via the quantum number array:

```

<Interactions: procedures>+≡
subroutine interaction_set_matrix_element_qn (int, qn, val)
  class(interaction_t), intent(inout) :: int
  type(quantum_numbers_t), dimension(:), intent(in) :: qn
  complex(default), intent(in) :: val
  call int%state_matrix%set_matrix_element (qn, val)

```

```
end subroutine interaction_set_matrix_element_qn
```

Set all entries of the matrix-element array to a given value.

(Interactions: procedures)+≡

```
subroutine interaction_set_matrix_element_all (int, value)
  class(interaction_t), intent(inout) :: int
  complex(default), intent(in) :: value
  call int%state_matrix%set_matrix_element (value)
end subroutine interaction_set_matrix_element_all
```

Set the matrix-element array directly.

(Interactions: procedures)+≡

```
subroutine interaction_set_matrix_element_array (int, value)
  class(interaction_t), intent(inout) :: int
  complex(default), dimension(:), intent(in) :: value
  call int%state_matrix%set_matrix_element (value)
end subroutine interaction_set_matrix_element_array

pure subroutine interaction_set_matrix_element_single (int, i, value)
  class(interaction_t), intent(inout) :: int
  integer, intent(in) :: i
  complex(default), intent(in) :: value
  call int%state_matrix%set_matrix_element (i, value)
end subroutine interaction_set_matrix_element_single
```

Clone from another (matching) interaction.

(Interactions: procedures)+≡

```
subroutine interaction_set_matrix_element_clone (int, int1)
  class(interaction_t), intent(inout) :: int
  class(interaction_t), intent(in) :: int1
  call int%state_matrix%set_matrix_element (int1%state_matrix)
end subroutine interaction_set_matrix_element_clone
```

Get the indices of any diagonal matrix elements.

(Interactions: interaction: TBP)+≡

```
procedure :: get_diagonal_entries => interaction_get_diagonal_entries
```

(Interactions: procedures)+≡

```
subroutine interaction_get_diagonal_entries (int, i)
  class(interaction_t), intent(in) :: int
  integer, dimension(:), allocatable, intent(out) :: i
  call int%state_matrix%get_diagonal_entries (i)
end subroutine interaction_get_diagonal_entries
```

Renormalize the state matrix by its trace, if nonzero. The renormalization is reflected in the state-matrix norm.

(Interactions: interaction: TBP)+≡

```
procedure :: normalize_by_trace => interaction_normalize_by_trace
```

(Interactions: procedures)+≡

```
subroutine interaction_normalize_by_trace (int)
  class(interaction_t), intent(inout) :: int
```

```

        call int%state_matrix%normalize_by_trace ()
    end subroutine interaction_normalize_by_trace

```

Analogous, but renormalize by maximal (absolute) value.

```

<Interactions: interaction: TBP>+≡
    procedure :: normalize_by_max => interaction_normalize_by_max

<Interactions: procedures>+≡
    subroutine interaction_normalize_by_max (int)
        class(interaction_t), intent(inout) :: int
        call int%state_matrix%normalize_by_max ()
    end subroutine interaction_normalize_by_max

```

Explicitly set the norm value (of the state matrix).

```

<Interactions: interaction: TBP>+≡
    procedure :: set_norm => interaction_set_norm

<Interactions: procedures>+≡
    subroutine interaction_set_norm (int, norm)
        class(interaction_t), intent(inout) :: int
        real(default), intent(in) :: norm
        call int%state_matrix%set_norm (norm)
    end subroutine interaction_set_norm

```

Return the maximum absolute value of color indices.

```

<Interactions: interaction: TBP>+≡
    procedure :: get_max_color_value => &
        interaction_get_max_color_value

<Interactions: procedures>+≡
    function interaction_get_max_color_value (int) result (cmax)
        class(interaction_t), intent(in) :: int
        integer :: cmax
        cmax = int%state_matrix%get_max_color_value ()
    end function interaction_get_max_color_value

```

Factorize the state matrix into single-particle state matrices, the branch selection depending on a (random) value between 0 and 1; optionally also return a correlated state matrix.

```

<Interactions: interaction: TBP>+≡
    procedure :: factorize => interaction_factorize

<Interactions: procedures>+≡
    subroutine interaction_factorize &
        (int, mode, x, ok, single_state, correlated_state, qn_in)
        class(interaction_t), intent(in), target :: int
        integer, intent(in) :: mode
        real(default), intent(in) :: x
        logical, intent(out) :: ok
        type(state_matrix_t), &
            dimension(:), allocatable, intent(out) :: single_state
        type(state_matrix_t), intent(out), optional :: correlated_state
        type(quantum_numbers_t), dimension(:), intent(in), optional :: qn_in
    end subroutine interaction_factorize

```

```

        call int%state_matrix%factorize &
            (mode, x, ok, single_state, correlated_state, qn_in)
    end subroutine interaction_factorize

```

Sum all matrix element values

```

<Interactions: interaction: TBP>+≡
    procedure :: sum => interaction_sum

<Interactions: procedures>+≡
    function interaction_sum (int) result (value)
        class(interaction_t), intent(in) :: int
        complex(default) :: value
        value = int%state_matrix%sum ()
    end function interaction_sum

```

Append new states which are color-contracted versions of the existing states. The matrix element index of each color contraction coincides with the index of its origin, so no new matrix elements are generated. After this operation, no `freeze` must be performed anymore.

```

<Interactions: interaction: TBP>+≡
    procedure :: add_color_contractions => &
        interaction_add_color_contractions

<Interactions: procedures>+≡
    subroutine interaction_add_color_contractions (int)
        class(interaction_t), intent(inout) :: int
        call int%state_matrix%add_color_contractions ()
    end subroutine interaction_add_color_contractions

```

Multiply matrix elements from two interactions. Choose the elements as given by the integer index arrays, multiply them and store the sum of products in the indicated matrix element. The suffixes mean: c=conjugate first factor; f=include weighting factor.

```

<Interactions: interaction: TBP>+≡
    procedure :: evaluate_product => interaction_evaluate_product
    procedure :: evaluate_product_cf => interaction_evaluate_product_cf
    procedure :: evaluate_square_c => interaction_evaluate_square_c
    procedure :: evaluate_sum => interaction_evaluate_sum
    procedure :: evaluate_me_sum => interaction_evaluate_me_sum

<Interactions: procedures>+≡
    pure subroutine interaction_evaluate_product &
        (int, i, int1, int2, index1, index2)
        class(interaction_t), intent(inout) :: int
        integer, intent(in) :: i
        type(interaction_t), intent(in) :: int1, int2
        integer, dimension(:), intent(in) :: index1, index2
        call int%state_matrix%evaluate_product &
            (i, int1%state_matrix, int2%state_matrix, &
                index1, index2)
    end subroutine interaction_evaluate_product

    pure subroutine interaction_evaluate_product_cf &

```

```

        (int, i, int1, int2, index1, index2, factor)
class(interaction_t), intent(inout) :: int
integer, intent(in) :: i
type(interaction_t), intent(in) :: int1, int2
integer, dimension(:), intent(in) :: index1, index2
complex(default), dimension(:), intent(in) :: factor
call int%state_matrix%evaluate_product_cf &
    (i, int1%state_matrix, int2%state_matrix, &
    index1, index2, factor)
end subroutine interaction_evaluate_product_cf

pure subroutine interaction_evaluate_square_c (int, i, int1, index1)
class(interaction_t), intent(inout) :: int
integer, intent(in) :: i
type(interaction_t), intent(in) :: int1
integer, dimension(:), intent(in) :: index1
call int%state_matrix%evaluate_square_c (i, int1%state_matrix, index1)
end subroutine interaction_evaluate_square_c

pure subroutine interaction_evaluate_sum (int, i, int1, index1)
class(interaction_t), intent(inout) :: int
integer, intent(in) :: i
type(interaction_t), intent(in) :: int1
integer, dimension(:), intent(in) :: index1
call int%state_matrix%evaluate_sum (i, int1%state_matrix, index1)
end subroutine interaction_evaluate_sum

pure subroutine interaction_evaluate_me_sum (int, i, int1, index1)
class(interaction_t), intent(inout) :: int
integer, intent(in) :: i
type(interaction_t), intent(in) :: int1
integer, dimension(:), intent(in) :: index1
call int%state_matrix%evaluate_me_sum (i, int1%state_matrix, index1)
end subroutine interaction_evaluate_me_sum

```

11.2.5 Accessing contents

Return the integer tag.

```

<Interactions: interaction: TBP>+≡
  procedure :: get_tag => interaction_get_tag

<Interactions: procedures>+≡
  function interaction_get_tag (int) result (tag)
    class(interaction_t), intent(in) :: int
    integer :: tag
    tag = int%tag
  end function interaction_get_tag

```

Return the number of particles.

```

<Interactions: interaction: TBP>+≡
  procedure :: get_n_tot => interaction_get_n_tot
  procedure :: get_n_in => interaction_get_n_in

```



```

procedure :: get_n_vir => interaction_get_n_vir
procedure :: get_n_out => interaction_get_n_out

<Interactions: procedures>+=
function interaction_get_n_tot (object) result (n_tot)
  class(interaction_t), intent(in) :: object
  integer :: n_tot
  n_tot = object%n_tot
end function interaction_get_n_tot

function interaction_get_n_in (object) result (n_in)
  class(interaction_t), intent(in) :: object
  integer :: n_in
  n_in = object%n_in
end function interaction_get_n_in

function interaction_get_n_vir (object) result (n_vir)
  class(interaction_t), intent(in) :: object
  integer :: n_vir
  n_vir = object%n_vir
end function interaction_get_n_vir

function interaction_get_n_out (object) result (n_out)
  class(interaction_t), intent(in) :: object
  integer :: n_out
  n_out = object%n_out
end function interaction_get_n_out

```

Return a momentum index. The flags specify whether to keep/drop incoming, virtual, or outgoing momenta. Check for illegal values.

```

<Interactions: procedures>+=
function idx (int, i, outgoing)
  integer :: idx
  type(interaction_t), intent(in) :: int
  integer, intent(in) :: i
  logical, intent(in), optional :: outgoing
  logical :: in, vir, out
  if (present (outgoing)) then
    in = .not. outgoing
    vir = .false.
    out = outgoing
  else
    in = .true.
    vir = .true.
    out = .true.
  end if
  idx = 0
  if (in) then
    if (vir) then
      if (out) then
        if (i <= int%n_tot) idx = i
      else
        if (i <= int%n_in + int%n_vir) idx = i
      end if
    end if
  end if

```

```

        else if (out) then
            if (i <= int%n_in) then
                idx = i
            else if (i <= int%n_in + int%n_out) then
                idx = int%n_vir + i
            end if
        else
            if (i <= int%n_in) idx = i
        end if
    else if (vir) then
        if (out) then
            if (i <= int%n_vir + int%n_out) idx = int%n_in + i
        else
            if (i <= int%n_vir) idx = int%n_in + i
        end if
    else if (out) then
        if (i <= int%n_out) idx = int%n_in + int%n_vir + i
    end if
    if (idx == 0) then
        call int%basic_write ()
        print *, i, in, vir, out
        call msg_bug (" Momentum index is out of range for this interaction")
    end if
end function idx

```

Return all or just a specific four-momentum.

(Interactions: interaction: TBP)+≡

```

generic :: get_momenta => get_momenta_all, get_momenta_idx
procedure :: get_momentum => interaction_get_momentum
procedure :: get_momenta_all => interaction_get_momenta_all
procedure :: get_momenta_idx => interaction_get_momenta_idx

```

(Interactions: procedures)+≡

```

function interaction_get_momenta_all (int, outgoing) result (p)
    class(interaction_t), intent(in) :: int
    type(vector4_t), dimension(:), allocatable :: p
    logical, intent(in), optional :: outgoing
    integer :: i
    if (present (outgoing)) then
        if (outgoing) then
            allocate (p (int%n_out))
        else
            allocate (p (int%n_in))
        end if
    else
        allocate (p (int%n_tot))
    end if
    do i = 1, size (p)
        p(i) = int%p(idx (int, i, outgoing))
    end do
end function interaction_get_momenta_all

function interaction_get_momenta_idx (int, jj) result (p)
    class(interaction_t), intent(in) :: int

```

```

    type(vector4_t), dimension(:), allocatable :: p
    integer, dimension(:), intent(in) :: jj
    allocate (p (size (jj)))
    p = int%p(jj)
end function interaction_get_momenta_idx

function interaction_get_momentum (int, i, outgoing) result (p)
    class(interaction_t), intent(in) :: int
    type(vector4_t) :: p
    integer, intent(in) :: i
    logical, intent(in), optional :: outgoing
    p = int%p(idx (int, i, outgoing))
end function interaction_get_momentum

```

This is a variant as a subroutine. Redundant, but the function above fails at times for gfortran 4.5.0 (double allocation, compiler bug).

```

<Interactions: interaction: TBP>+≡
    procedure :: get_momenta_sub => interaction_get_momenta_sub

<Interactions: procedures>+≡
    subroutine interaction_get_momenta_sub (int, p, outgoing)
        class(interaction_t), intent(in) :: int
        type(vector4_t), dimension(:), intent(out) :: p
        logical, intent(in), optional :: outgoing
        integer :: i
        do i = 1, size (p)
            p(i) = int%p(idx (int, i, outgoing))
        end do
    end subroutine interaction_get_momenta_sub

```

Return a shallow copy of the state matrix:

```

<Interactions: interaction: TBP>+≡
    procedure :: get_state_matrix_ptr => &
        interaction_get_state_matrix_ptr

<Interactions: procedures>+≡
    function interaction_get_state_matrix_ptr (int) result (state)
        class(interaction_t), intent(in), target :: int
        type(state_matrix_t), pointer :: state
        state => int%state_matrix
    end function interaction_get_state_matrix_ptr

```

Return the array of resonance flags

```

<Interactions: interaction: TBP>+≡
    procedure :: get_resonance_flags => interaction_get_resonance_flags

<Interactions: procedures>+≡
    function interaction_get_resonance_flags (int) result (resonant)
        class(interaction_t), intent(in) :: int
        logical, dimension(size(int%resonant)) :: resonant
        resonant = int%resonant
    end function interaction_get_resonance_flags

```

Return the quantum-numbers mask (or part of it)

```

<Interactions: interaction: TBP>+≡
  generic :: get_mask => get_mask_all, get_mask_slice
  procedure :: get_mask_all => interaction_get_mask_all
  procedure :: get_mask_slice => interaction_get_mask_slice

<Interactions: procedures>+≡
  function interaction_get_mask_all (int) result (mask)
    class(interaction_t), intent(in) :: int
    type(quantum_numbers_mask_t), dimension(size(int%mask)) :: mask
    mask = int%mask
  end function interaction_get_mask_all

  function interaction_get_mask_slice (int, index) result (mask)
    class(interaction_t), intent(in) :: int
    integer, dimension(:), intent(in) :: index
    type(quantum_numbers_mask_t), dimension(size(index)) :: mask
    mask = int%mask(index)
  end function interaction_get_mask_slice

```

Compute the invariant mass squared of the incoming particles (if any, otherwise outgoing).

```

<Interactions: public>+≡
  public :: interaction_get_s

<Interactions: procedures>+≡
  function interaction_get_s (int) result (s)
    real(default) :: s
    type(interaction_t), intent(in) :: int
    if (int%n_in /= 0) then
      s = sum (int%p(:int%n_in)) ** 2
    else
      s = sum (int%p(int%n_vir+1:)) ** 2
    end if
  end function interaction_get_s

```

Compute the Lorentz transformation that transforms the incoming particles from the center-of-mass frame to the lab frame where they are given. If the c.m. mass squared is negative or zero, return the identity.

```

<Interactions: public>+≡
  public :: interaction_get_cm_transformation

<Interactions: procedures>+≡
  function interaction_get_cm_transformation (int) result (lt)
    type(lorentz_transformation_t) :: lt
    type(interaction_t), intent(in) :: int
    type(vector4_t) :: p_cm
    real(default) :: s
    if (int%n_in /= 0) then
      p_cm = sum (int%p(:int%n_in))
    else
      p_cm = sum (int%p(int%n_vir+1:))
    end if
    s = p_cm ** 2
  end function interaction_get_cm_transformation

```

```

    if (s > 0) then
        lt = boost (p_cm, sqrt (s))
    else
        lt = identity
    end if
end function interaction_get_cm_transformation

```

Return flavor, momentum, and position of the first outgoing unstable particle present in the interaction. Note that we need not iterate through the state matrix; if there is an unstable particle, it will be present in all state-matrix entries.

```

<Interactions: public>+=
    public :: interaction_get_unstable_particle

<Interactions: procedures>+=
    subroutine interaction_get_unstable_particle (int, flv, p, i)
        type(interaction_t), intent(in), target :: int
        type(flavor_t), intent(out) :: flv
        type(vector4_t), intent(out) :: p
        integer, intent(out) :: i
        type(state_iterator_t) :: it
        type(flavor_t), dimension(int%n_tot) :: flv_array
        call it%init (int%state_matrix)
        flv_array = it%get_flavor ()
        do i = int%n_in + int%n_vir + 1, int%n_tot
            if (.not. flv_array(i)%is_stable ()) then
                flv = flv_array(i)
                p = int%p(i)
                return
            end if
        end do
    end subroutine interaction_get_unstable_particle

```

Return the complete set of *outgoing* flavors, assuming that the flavor quantum number is not suppressed.

```

<Interactions: public>+=
    public :: interaction_get_flv_out

<Interactions: procedures>+=
    subroutine interaction_get_flv_out (int, flv)
        type(interaction_t), intent(in), target :: int
        type(flavor_t), dimension(:, :), allocatable, intent(out) :: flv
        type(state_iterator_t) :: it
        type(flavor_t), dimension(:), allocatable :: flv_state
        integer :: n_in, n_vir, n_out, n_tot, n_state, i
        n_in = int%get_n_in ()
        n_vir = int%get_n_vir ()
        n_out = int%get_n_out ()
        n_tot = int%get_n_tot ()
        n_state = int%get_n_matrix_elements ()
        allocate (flv (n_out, n_state))
        allocate (flv_state (n_tot))
        i = 1

```

```

call it%init (int%get_state_matrix_ptr ())
do while (it%is_valid ())
  flv_state = it%get_flavor ()
  flv(:,i) = flv_state(n_in+n_vir+1:)
  i = i + 1
  call it%advance ()
end do
end subroutine interaction_get_flv_out

```

Determine the flavor content of the interaction. We analyze the state matrix for this, and we select the outgoing particles of the hard process only for the required mask, which indicates the particles that can appear in any order in a matching event record.

We have to assume that any radiated particles (beam remnants) appear at the beginning of the particles marked as outgoing.

```

<Interactions: public>+≡
  public :: interaction_get_flv_content

<Interactions: procedures>+≡
  subroutine interaction_get_flv_content (int, state_flv, n_out_hard)
    type(interaction_t), intent(in), target :: int
    type(state_flv_content_t), intent(out) :: state_flv
    integer, intent(in) :: n_out_hard
    logical, dimension(:), allocatable :: mask
    integer :: n_tot
    n_tot = int%get_n_tot ()
    allocate (mask (n_tot), source = .false.)
    mask(n_tot-n_out_hard+1:) = .true.
    call state_flv%fill (int%get_state_matrix_ptr (), mask)
  end subroutine interaction_get_flv_content

```

11.2.6 Modifying contents

Set the quantum numbers mask.

```

<Interactions: public>+≡
  public :: interaction_set_mask

<Interactions: procedures>+≡
  subroutine interaction_set_mask (int, mask)
    type(interaction_t), intent(inout) :: int
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
    int%mask = mask
    int%update_state_matrix = .true.
  end subroutine interaction_set_mask

```

Merge a particular mask entry, respecting a possible helicity lock for this entry. We apply an OR relation, which means that quantum numbers are summed over if either of the two masks requires it.

```

<Interactions: procedures>+≡
  subroutine interaction_merge_mask_entry (int, i, mask)
    type(interaction_t), intent(inout) :: int

```

```

integer, intent(in) :: i
type(quantum_numbers_mask_t), intent(in) :: mask
type(quantum_numbers_mask_t) :: mask_tmp
integer :: ii
ii = idx (int, i)
if (int%mask(ii) .neqv. mask) then
  int%mask(ii) = int%mask(ii) .or. mask
  if (int%hel_lock(ii) /= 0) then
    call mask_tmp%assign (mask, helicity=.true.)
    int%mask(int%hel_lock(ii)) = int%mask(int%hel_lock(ii)) .or. mask_tmp
  end if
end if
int%update_state_matrix = .true.
end subroutine interaction_merge_mask_entry

```

Fill the momenta array, do not care about the quantum numbers of particles.

```

<Interactions: interaction: TBP>+≡
  procedure :: reset_momenta => interaction_reset_momenta
  procedure :: set_momenta => interaction_set_momenta
  procedure :: set_momentum => interaction_set_momentum

<Interactions: procedures>+≡
  subroutine interaction_reset_momenta (int)
    class(interaction_t), intent(inout) :: int
    int%p = vector4_null
    int%p_is_known = .true.
  end subroutine interaction_reset_momenta

  subroutine interaction_set_momenta (int, p, outgoing)
    class(interaction_t), intent(inout) :: int
    type(vector4_t), dimension(:), intent(in) :: p
    logical, intent(in), optional :: outgoing
    integer :: i, index
    do i = 1, size (p)
      index = idx (int, i, outgoing)
      int%p(index) = p(i)
      int%p_is_known(index) = .true.
    end do
  end subroutine interaction_set_momenta

  subroutine interaction_set_momentum (int, p, i, outgoing)
    class(interaction_t), intent(inout) :: int
    type(vector4_t), intent(in) :: p
    integer, intent(in) :: i
    logical, intent(in), optional :: outgoing
    integer :: index
    index = idx (int, i, outgoing)
    int%p(index) = p
    int%p_is_known(index) = .true.
  end subroutine interaction_set_momentum

```

This more sophisticated version of setting values is used for structure functions, in particular if nontrivial flavor, color, and helicity may be present: set values selectively for the given flavors. If there is more than one flavor, scan the

interaction and check for a matching flavor at the specified particle location. If it matches, insert the value that corresponds to this flavor.

```

<Interactions: public>+≡
    public :: interaction_set_flavored_values

<Interactions: procedures>+≡
    subroutine interaction_set_flavored_values (int, value, flv_in, pos)
        type(interaction_t), intent(inout) :: int
        complex(default), dimension(:), intent(in) :: value
        type(flavor_t), dimension(:), intent(in) :: flv_in
        integer, intent(in) :: pos
        type(state_iterator_t) :: it
        type(flavor_t) :: flv
        integer :: i
        if (size (value) == 1) then
            call int%set_matrix_element (value(1))
        else
            call it%init (int%state_matrix)
            do while (it%is_valid ())
                flv = it%get_flavor (pos)
                SCAN_FLV: do i = 1, size (value)
                    if (flv == flv_in(i)) then
                        call it%set_matrix_element (value(i))
                        exit SCAN_FLV
                    end if
                end do SCAN_FLV
                call it%advance ()
            end do
        end if
    end subroutine interaction_set_flavored_values

```

11.2.7 Handling Linked interactions

Store relations between corresponding particles within one interaction. The first particle is the parent, the second one the child. Links are established in both directions.

These relations have no effect on the propagation of momenta etc., they are rather used for mother-daughter relations in event output.

```

<Interactions: interaction: TBP>+≡
    procedure :: relate => interaction_relate

<Interactions: procedures>+≡
    subroutine interaction_relate (int, i1, i2)
        class(interaction_t), intent(inout), target :: int
        integer, intent(in) :: i1, i2
        if (i1 /= 0 .and. i2 /= 0) then
            call int%children(i1)%append (i2)
            call int%parents(i2)%append (i1)
        end if
    end subroutine interaction_relate

```


Transfer internal parent-child relations defined within interaction `int1` to a new interaction `int` where the particle indices are mapped to. Some particles in `int1` may have no image in `int`. In that case, a child entry maps to zero, and we skip this relation.

Also transfer resonance flags.

```

<Interactions: interaction: TBP>+≡
  procedure :: transfer_relations => interaction_transfer_relations

<Interactions: procedures>+≡
  subroutine interaction_transfer_relations (int1, int2, map)
    class(interaction_t), intent(in) :: int1
    class(interaction_t), intent(inout), target :: int2
    integer, dimension(:), intent(in) :: map
    integer :: i, j, k
    do i = 1, size (map)
      do j = 1, int1%parents(i)%get_length ()
        k = int1%parents(i)%get_link (j)
        call int2%relate (map(k), map(i))
      end do
      if (map(i) /= 0) then
        int2%resonant(map(i)) = int1%resonant(i)
      end if
    end do
  end subroutine interaction_transfer_relations

```

Make up internal parent-child relations for the particle(s) that are connected to a new interaction `int`.

If `resonant` is defined and true, the connections are marked as resonant in the result interaction

```

<Interactions: interaction: TBP>+≡
  procedure :: relate_connections => interaction_relate_connections

<Interactions: procedures>+≡
  subroutine interaction_relate_connections &
    (int, int_in, connection_index, &
     map, map_connections, resonant)
    class(interaction_t), intent(inout), target :: int
    class(interaction_t), intent(in) :: int_in
    integer, dimension(:), intent(in) :: connection_index
    integer, dimension(:), intent(in) :: map, map_connections
    logical, intent(in), optional :: resonant
    logical :: reson
    integer :: i, j, i2, k2
    reson = .false.; if (present (resonant)) reson = resonant
    do i = 1, size (map_connections)
      k2 = connection_index(i)
      do j = 1, int_in%children(k2)%get_length ()
        i2 = int_in%children(k2)%get_link (j)
        call int%relate (map_connections(i), map(i2))
      end do
      int%resonant(map_connections(i)) = reson
    end do
  end subroutine interaction_relate_connections

```

Return the number of source/target links of the internal connections of particle i.

```

<Interactions: public>+=
    public :: interaction_get_n_children
    public :: interaction_get_n_parents

<Interactions: procedures>+=
    function interaction_get_n_children (int, i) result (n)
        integer :: n
        type(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        n = int%children(i)%get_length ()
    end function interaction_get_n_children

    function interaction_get_n_parents (int, i) result (n)
        integer :: n
        type(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        n = int%parents(i)%get_length ()
    end function interaction_get_n_parents

```

Return the source/target links of the internal connections of particle i as an array.

```

<Interactions: public>+=
    public :: interaction_get_children
    public :: interaction_get_parents

<Interactions: procedures>+=
    function interaction_get_children (int, i) result (idx)
        integer, dimension(:), allocatable :: idx
        type(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        integer :: k, l
        l = int%children(i)%get_length ()
        allocate (idx (l))
        do k = 1, l
            idx(k) = int%children(i)%get_link (k)
        end do
    end function interaction_get_children

    function interaction_get_parents (int, i) result (idx)
        integer, dimension(:), allocatable :: idx
        type(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        integer :: k, l
        l = int%parents(i)%get_length ()
        allocate (idx (l))
        do k = 1, l
            idx(k) = int%parents(i)%get_link (k)
        end do
    end function interaction_get_parents

```

Add a source link from an interaction to a corresponding particle within another interaction. These links affect the propagation of particles: the two linked

particles are considered as the same particle, outgoing and incoming.

```

<Interactions: interaction: TBP>+≡
  procedure :: set_source_link => interaction_set_source_link

<Interactions: procedures>+≡
  subroutine interaction_set_source_link (int, i, int1, i1)
    class(interaction_t), intent(inout) :: int
    integer, intent(in) :: i
    class(interaction_t), intent(in), target :: int1
    integer, intent(in) :: i1
    if (i /= 0) call external_link_set (int%source(i), int1, i1)
  end subroutine interaction_set_source_link

```

Reassign links to a new interaction (which is an image of the current interaction).

```

<Interactions: public>+≡
  public :: interaction_reassign_links

<Interactions: procedures>+≡
  subroutine interaction_reassign_links (int, int_src, int_target)
    type(interaction_t), intent(inout) :: int
    type(interaction_t), intent(in) :: int_src
    type(interaction_t), intent(in), target :: int_target
    integer :: i
    if (allocated (int%source)) then
      do i = 1, size (int%source)
        call external_link_reassign (int%source(i), int_src, int_target)
      end do
    end if
  end subroutine interaction_reassign_links

```

Since links are one-directional, if we want to follow them backwards we have to scan all possibilities. This procedure returns the index of the particle within `int` which points to the particle `i1` within interaction `int1`. If unsuccessful, return zero.

```

<Interactions: public>+≡
  public :: interaction_find_link

<Interactions: procedures>+≡
  function interaction_find_link (int, int1, i1) result (i)
    integer :: i
    type(interaction_t), intent(in) :: int, int1
    integer, intent(in) :: i1
    type(interaction_t), pointer :: int_tmp
    do i = 1, int%n_tot
      int_tmp => external_link_get_ptr (int%source(i))
      if (int_tmp%tag == int1%tag) then
        if (external_link_get_index (int%source(i)) == i1) return
      end if
    end do
    i = 0
  end function interaction_find_link

```

The inverse: return interaction pointer and index for the ultimate source of *i* within *int*.

```

<Interactions: interaction: TBP>+≡
    procedure :: find_source => interaction_find_source

<Interactions: procedures>+≡
    subroutine interaction_find_source (int, i, int1, i1)
        class(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        type(interaction_t), intent(out), pointer :: int1
        integer, intent(out) :: i1
        type(external_link_t) :: link
        link = interaction_get_ultimate_source (int, i)
        int1 => external_link_get_ptr (link)
        i1 = external_link_get_index (link)
    end subroutine interaction_find_source

```

Follow source links recursively to return the ultimate source of a particle.

```

<Interactions: procedures>+≡
    function interaction_get_ultimate_source (int, i) result (link)
        type(external_link_t) :: link
        type(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        type(interaction_t), pointer :: int_src
        integer :: i_src
        link = int%source(i)
        if (external_link_is_set (link)) then
            do
                int_src => external_link_get_ptr (link)
                i_src = external_link_get_index (link)
                if (external_link_is_set (int_src%source(i_src))) then
                    link = int_src%source(i_src)
                else
                    exit
                end if
            end do
        end if
    end function interaction_get_ultimate_source

```

Update mask entries by merging them with corresponding masks in interactions linked to the current one. The mask determines quantum numbers which are summed over.

Note that both the mask of the current interaction and the mask of the linked interaction are updated (side effect!). This ensures that both agree for the linked particle.

```

<Interactions: public>+≡
    public :: interaction_exchange_mask

<Interactions: procedures>+≡
    subroutine interaction_exchange_mask (int)
        type(interaction_t), intent(inout) :: int
        integer :: i, index_link
        type(interaction_t), pointer :: int_link

```

```

do i = 1, int%n_tot
  if (external_link_is_set (int%source(i))) then
    int_link => external_link_get_ptr (int%source(i))
    index_link = external_link_get_index (int%source(i))
    call interaction_merge_mask_entry &
      (int, i, int_link%mask(index_link))
    call interaction_merge_mask_entry &
      (int_link, index_link, int%mask(i))
  end if
end do
call int%freeze ()
end subroutine interaction_exchange_mask

```

Copy momenta from interactions linked to the current one.

```

<Interactions: interaction: TBP>+≡
  procedure :: receive_momenta => interaction_receive_momenta

<Interactions: procedures>+≡
  subroutine interaction_receive_momenta (int)
    class(interaction_t), intent(inout) :: int
    integer :: i, index_link
    type(interaction_t), pointer :: int_link
    do i = 1, int%n_tot
      if (external_link_is_set (int%source(i))) then
        int_link => external_link_get_ptr (int%source(i))
        index_link = external_link_get_index (int%source(i))
        call int%set_momentum (int_link%p(index_link), i)
      end if
    end do
  end subroutine interaction_receive_momenta

```

The inverse operation: Copy momenta back to the interactions linked to the current one.

```

<Interactions: public>+≡
  public :: interaction_send_momenta

<Interactions: procedures>+≡
  subroutine interaction_send_momenta (int)
    type(interaction_t), intent(in) :: int
    integer :: i, index_link
    type(interaction_t), pointer :: int_link
    do i = 1, int%n_tot
      if (external_link_is_set (int%source(i))) then
        int_link => external_link_get_ptr (int%source(i))
        index_link = external_link_get_index (int%source(i))
        call int_link%set_momentum (int%p(i), index_link)
      end if
    end do
  end subroutine interaction_send_momenta

```

For numerical comparisons: pacify all momenta in an interaction.

```

<Interactions: public>+≡
  public :: interaction_pacify_momenta

```

```

<Interactions: procedures>+≡
subroutine interaction_pacify_momenta (int, acc)
  type(interaction_t), intent(inout) :: int
  real(default), intent(in) :: acc
  integer :: i
  do i = 1, int%n_tot
    call pacify (int%p(i), acc)
  end do
end subroutine interaction_pacify_momenta

```

11.2.8 Recovering connections

When creating an evaluator for two interactions, we have to know by which particles they are connected. The connection indices can be determined if we have two linked interactions. We assume that `int1` is the source and `int2` the target, so the connections of interest are stored within `int2`. A connection is found if either the source is `int1`, or the (ultimate) source of a particle within `int2` coincides with the (ultimate) source of a particle within `int1`. The result is an array of index pairs.

To make things simple, we scan the interaction twice, once for counting hits, then allocate the array, then scan again and store the connections.

The connections are scanned for `int2`, which has sources in `int1`. It may happen that the order of connections is interchanged (crossed). We require the indices in `int1` to be sorted, so we reorder both index arrays correspondingly before returning them. (After this, the indices in `int2` may be out of order.)

```

<Interactions: public>+≡
public :: find_connections

<Interactions: procedures>+≡
subroutine find_connections (int1, int2, n, connection_index)
  class(interaction_t), intent(in) :: int1, int2
  integer, intent(out) :: n
  integer, dimension(:,:), intent(out), allocatable :: connection_index
  integer, dimension(:,:), allocatable :: conn_index_tmp
  integer, dimension(:), allocatable :: ordering
  integer :: i, j, k
  type(external_link_t) :: link2, link1
  type(interaction_t), pointer :: int_link, int_link1
  n = 0
  do i = 1, size (int2%source)
    link2 = interaction_get_ultimate_source (int2, i)
    if (external_link_is_set (link2)) then
      int_link => external_link_get_ptr (link2)
      if (int_link%tag == int1%tag) then
        n = n + 1
      else
        k = external_link_get_index (link2)
        do j = 1, size (int1%source)
          link1 = interaction_get_ultimate_source (int1, j)
          if (external_link_is_set (link1)) then
            int_link1 => external_link_get_ptr (link1)
            if (int_link1%tag == int_link%tag) then

```

```

        if (external_link_get_index (link1) == k) then
            n = n + 1
        end if
    end if
end if
end if
end do
end if
end if
end do
allocate (conn_index_tmp (n, 2))
n = 0
do i = 1, size (int2%source)
    link2 = interaction_get_ultimate_source (int2, i)
    if (external_link_is_set (link2)) then
        int_link => external_link_get_ptr (link2)
        if (int_link%tag == int1%tag) then
            n = n + 1
            conn_index_tmp(n,1) = external_link_get_index (int2%source(i))
            conn_index_tmp(n,2) = i
        else
            k = external_link_get_index (link2)
            do j = 1, size (int1%source)
                link1 = interaction_get_ultimate_source (int1, j)
                if (external_link_is_set (link1)) then
                    int_link1 => external_link_get_ptr (link1)
                    if (int_link1%tag == int_link%tag) then
                        if (external_link_get_index (link1) == k) then
                            n = n + 1
                            conn_index_tmp(n,1) = j
                            conn_index_tmp(n,2) = i
                        end if
                    end if
                end if
            end do
        end if
    end if
end do
allocate (connection_index (n, 2))
if (n > 1) then
    allocate (ordering (n))
    ordering = order (conn_index_tmp(:,1))
    connection_index = conn_index_tmp(ordering,:)
else
    connection_index = conn_index_tmp
end if
end subroutine find_connections

```

11.2.9 Unit tests

```

<Interactions: public>+≡
    public :: interaction_test
<Interactions: procedures>+≡

```

```

subroutine interaction_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
  <Interactions: execute tests>
end subroutine interaction_test

```

Generate an interaction of a polarized virtual photon and a colored quark which may be either up or down. Remove the quark polarization. Generate another interaction for the quark radiating a photon and link this to the first interaction. The radiation ignores polarization; transfer this information to the first interaction to simplify it. Then, transfer the momentum to the radiating quark and perform a splitting.

```

<Interactions: execute tests>≡
  call test (interaction_1, "interaction_1", &
    "check interaction setup", &
    u, results)

<Interactions: tests>≡
  subroutine interaction_1 (u)
    integer, intent(in) :: u
    type(interaction_t), target :: int, rad
    type(vector4_t), dimension(3) :: p
    type(quantum_numbers_mask_t), dimension(3) :: mask
    p(2) = vector4_moving (500._default, 500._default, 1)
    p(3) = vector4_moving (500._default, -500._default, 1)
    p(1) = p(2) + p(3)

    write (u, "(A)")  "* Test output: interaction"
    write (u, "(A)")  "* Purpose: check routines for interactions"
    write (u, "(A)")

    call int%basic_init (1, 0, 2, set_relations=.true., &
      store_values = .true. )
    call int_set (int, 1, -1, 1, 1, &
      cmplx (0.3_default, 0.1_default, kind=default))
    call int_set (int, 1, -1, -1, 1, &
      cmplx (0.5_default, -0.7_default, kind=default))
    call int_set (int, 1, 1, 1, 1, &
      cmplx (0.1_default, 0._default, kind=default))
    call int_set (int, -1, 1, -1, 2, &
      cmplx (0.4_default, -0.1_default, kind=default))
    call int_set (int, 1, 1, 1, 2, &
      cmplx (0.2_default, 0._default, kind=default))
    call int%freeze ()
    call int%set_momenta (p)
    mask = quantum_numbers_mask (.false., .false., [.true., .true., .true.])
    call rad%basic_init (1, 0, 2, &
      mask=mask, set_relations=.true., store_values = .true.)
    call rad_set (1)
    call rad_set (2)
    call rad%set_source_link (1, int, 2)
    call interaction_exchange_mask (rad)
    call rad%receive_momenta ()
    p(1) = rad%get_momentum (1)

```



```

p(2) = 0.4_default * p(1)
p(3) = p(1) - p(2)
call rad%set_momenta (p(2:3), outgoing=.true.)
call int%freeze ()
call rad%freeze ()
call rad%set_matrix_element &
    (cmplx (0._default, 0._default, kind=default))
call int%basic_write (u)
write (u, "(A)")
call rad%basic_write (u)
write (u, "(A)")
write (u, "(A)")  "* Cleanup"
call int%final ()
call rad%final ()
write (u, "(A)")
write (u, "(A)")  "* Test interaction_1: successful."
contains
subroutine int_set (int, h1, h2, hq, q, val)
    type(interaction_t), target, intent(inout) :: int
    integer, intent(in) :: h1, h2, hq, q
    type(flavor_t), dimension(3) :: flv
    type(color_t), dimension(3) :: col
    type(helicity_t), dimension(3) :: hel
    type(quantum_numbers_t), dimension(3) :: qn
    complex(default), intent(in) :: val
    call flv%init ([21, q, -q])
    call col(2)%init_col_acl (5, 0)
    call col(3)%init_col_acl (0, 5)
    call hel%init ([h1, hq, -hq], [h2, hq, -hq])
    call qn%init (flv, col, hel)
    call int%add_state (qn)
    call int%set_matrix_element (val)
end subroutine int_set
subroutine rad_set (q)
    integer, intent(in) :: q
    type(flavor_t), dimension(3) :: flv
    type(quantum_numbers_t), dimension(3) :: qn
    call flv%init ([ q, q, 21 ])
    call qn%init (flv)
    call rad%add_state (qn)
end subroutine rad_set
end subroutine interaction_1

```

11.3 Matrix element evaluation

The `evaluator_t` type is an extension of the `interaction_t` type. It represents either a density matrix as the square of a transition matrix element, or the product of two density matrices. Usually, some quantum numbers are summed over in the result.

The `interaction_t` subobject represents a multi-particle interaction with incoming, virtual, and outgoing particles and the associated (not necessarily

diagonal) density matrix of quantum state. When the evaluator is initialized, this interaction is constructed from the input interaction(s).

In addition, the initialization process sets up a multiplication table. For each matrix element of the result, it states which matrix elements are to be taken from the input interaction(s), multiplied (optionally, with an additional weight factor) and summed over.

Eventually, to a processes we associate a chain of evaluators which are to be evaluated sequentially. The physical event and its matrix element value(s) can be extracted from the last evaluator in such a chain.

Evaluators are constructed only once (as long as this is possible) during an initialization step. Then, for each event, momenta are computed and transferred among evaluators using the links within the interaction subobject. The multiplication tables enable fast evaluation of the result without looking at quantum numbers anymore.

`<evaluators.f90>`≡

<File header>

`module evaluators`

<Use kinds>

<Use strings>

`use io_units`

`use format_defs, only: FMT_19`

`use unit_tests`

`use diagnostics`

`use lorentz`

`use model_data`

`use flavors`

`use colors`

`use helicities`

`use quantum_numbers`

`use state_matrices`

`use interactions`

<Standard module head>

<Evaluators: public>

<Evaluators: parameters>

<Evaluators: types>

<Evaluators: interfaces>

`contains`

<Evaluators: procedures>

<Evaluators: tests>

`end module evaluators`

11.3.1 Array of pairings

The evaluator contains an array of `pairing_array` objects. This makes up the multiplication table.

Each pairing array contains two list of matrix element indices and a list of numerical factors. The matrix element indices correspond to the input interactions. The corresponding matrix elements are to be multiplied and optionally multiplied by a factor. The results are summed over to yield one specific matrix element of the result evaluator.

(Evaluators: types)≡

```
type :: pairing_array_t
      integer, dimension(:), allocatable :: i1, i2
      complex(default), dimension(:), allocatable :: factor
end type pairing_array_t
```

(Evaluators: procedures)≡

```
elemental subroutine pairing_array_init (pa, n, has_i2, has_factor)
  type(pairing_array_t), intent(out) :: pa
  integer, intent(in) :: n
  logical, intent(in) :: has_i2, has_factor
  allocate (pa%i1 (n))
  if (has_i2) allocate (pa%i2 (n))
  if (has_factor) allocate (pa%factor (n))
end subroutine pairing_array_init
```

11.3.2 The evaluator type

Possible variants of evaluators:

(Evaluators: parameters)≡

```
integer, parameter :: &
  EVAL_UNDEFINED = 0, &
  EVAL_PRODUCT = 1, &
  EVAL_SQUARED_FLOWS = 2, &
  EVAL_SQUARE_WITH_COLOR_FACTORS = 3, &
  EVAL_COLOR_CONTRACTION = 4, &
  EVAL_IDENTITY = 5, &
  EVAL_QN_SUM = 6
```

The evaluator type contains the result interaction and an array of pairing lists, one for each matrix element in the result interaction.

(Evaluators: public)≡

```
public :: evaluator_t
```

(Evaluators: types)+≡

```
type, extends (interaction_t) :: evaluator_t
  private
  integer :: type = EVAL_UNDEFINED
  class(interaction_t), pointer :: int_in1 => null ()
  class(interaction_t), pointer :: int_in2 => null ()
  type(pairing_array_t), dimension(:), allocatable :: pairing_array
contains
(Evaluators: evaluator: TBP)
```

```
end type evaluator_t
```

Output.

(Evaluators: evaluator: TBP)≡

```
procedure :: write => evaluator_write
```

(Evaluators: procedures)+≡

```
subroutine evaluator_write (eval, unit, &
    verbose, show_momentum_sum, show_mass, show_state, show_table, &
    col_verbose, testflag)
class(evaluator_t), intent(in) :: eval
integer, intent(in), optional :: unit
logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
logical, intent(in), optional :: show_state, show_table, col_verbose
logical, intent(in), optional :: testflag
logical :: conjugate, square, show_tab
integer :: u, i, j
u = given_output_unit (unit); if (u < 0) return
show_tab = .true.; if (present (show_table)) show_tab = .false.
call eval%basic_write &
    (unit, verbose, show_momentum_sum, show_mass, &
    show_state, col_verbose, testflag)
if (show_tab) then
    write (u, "(1x,A)") "Matrix-element multiplication"
    write (u, "(2x,A)", advance="no") "Input interaction 1:"
    if (associated (eval%int_in1)) then
        write (u, "(1x,I0)") eval%int_in1%get_tag ()
    else
        write (u, "(A)") " [undefined]"
    end if
    write (u, "(2x,A)", advance="no") "Input interaction 2:"
    if (associated (eval%int_in2)) then
        write (u, "(1x,I0)") eval%int_in2%get_tag ()
    else
        write (u, "(A)") " [undefined]"
    end if
    select case (eval%type)
    case (EVAL_SQUARED_FLOWS, EVAL_SQUARE_WITH_COLOR_FACTORS)
        conjugate = .true.
        square = .true.
    case default
        conjugate = .false.
        square = .false.
    end select
    if (eval%type == EVAL_IDENTITY) then
        write (u, "(1X,A)") "Identity evaluator, pairing array unused"
        return
    end if
    if (allocated (eval%pairing_array)) then
        do i = 1, size (eval%pairing_array)
            write (u, "(2x,A,I0,A)") "ME(", i, ") = "
            do j = 1, size (eval%pairing_array(i)%i1)
                write (u, "(4x,A)", advance="no") "+"
                if (allocated (eval%pairing_array(i)%i2)) then
```

```

        write (u, "(1x,A,I0,A)", advance="no") &
            "ME1(", eval%pairing_array(i)%i1(j), ")"
        if (conjugate) then
            write (u, "(A)", advance="no")  "*" x"
        else
            write (u, "(A)", advance="no")  " x"
        end if
        write (u, "(1x,A,I0,A)", advance="no") &
            "ME2(", eval%pairing_array(i)%i2(j), ")"
    else if (square) then
        write (u, "(1x,A)", advance="no")  "|"
        write (u, "(A,I0,A)", advance="no") &
            "ME1(", eval%pairing_array(i)%i1(j), ")"
        write (u, "(A)", advance="no")  "|^2"
    else
        write (u, "(1x,A,I0,A)", advance="no") &
            "ME1(", eval%pairing_array(i)%i1(j), ")"
    end if
    if (allocated (eval%pairing_array(i)%factor)) then
        write (u, "(1x,A)", advance="no")  "x"
        write (u, "(1x,'('," // FMT_19 // ",',',',", // FMT_19 // &
            ",')')") eval%pairing_array(i)%factor(j)
    else
        write (u, *)
    end if
end do
end do
end if
! print *, size (eval%pairing_array)      !!! Debugging
end if
end subroutine evaluator_write

```

Assignment: Deep copy of the interaction component.

```

<Evaluators: public>+≡
    public :: assignment(=)

<Evaluators: interfaces>≡
    interface assignment(=)
        module procedure evaluator_assign
    end interface

<Evaluators: procedures>+≡
    subroutine evaluator_assign (eval_out, eval_in)
        type(evaluator_t), intent(out) :: eval_out
        type(evaluator_t), intent(in) :: eval_in
        eval_out%type = eval_in%type
        eval_out%int_in1 => eval_in%int_in1
        eval_out%int_in2 => eval_in%int_in2
        eval_out%interaction_t = eval_in%interaction_t
        if (allocated (eval_in%pairing_array)) then
            allocate (eval_out%pairing_array (size (eval_in%pairing_array)))
            eval_out%pairing_array = eval_in%pairing_array
        end if
    end subroutine evaluator_assign

```

11.3.3 Auxiliary structures for evaluator creation

Creating an evaluator that properly handles all quantum numbers requires some bookkeeping. In this section, we define several auxiliary types and methods that organize and simplify this task. More structures are defined within the specific initializers (as local types and internal subroutines).

These types are currently implemented in a partial object-oriented way: We define some basic methods for initialization etc. here, but the evaluator routines below do access their internals as well. This simplifies some things such as index addressing using array slices, at the expense of losing some clarity.

Index mapping

Index mapping are abundant when constructing an evaluator. To have arrays of index mappings, we define this:

```
<Evaluators: types>+≡
    type :: index_map_t
        integer, dimension(:), allocatable :: entry
    end type index_map_t

<Evaluators: procedures>+≡
    elemental subroutine index_map_init (map, n)
        type(index_map_t), intent(out) :: map
        integer, intent(in) :: n
        allocate (map%entry (n))
    end subroutine index_map_init

<Evaluators: procedures>+≡
    function index_map_exists (map) result (flag)
        logical :: flag
        type(index_map_t), intent(in) :: map
        flag = allocated (map%entry)
    end function index_map_exists

<Evaluators: interfaces>+≡
    interface size
        module procedure index_map_size
    end interface

<Evaluators: procedures>+≡
    function index_map_size (map) result (s)
        integer :: s
        type(index_map_t), intent(in) :: map
        if (allocated (map%entry)) then
            s = size (map%entry)
        else
            s = 0
        end if
    end function index_map_size
```

```

(Evaluators: interfaces)+≡
interface assignment(=)
  module procedure index_map_assign_int
  module procedure index_map_assign_array
end interface

(Evaluators: procedures)+≡
elemental subroutine index_map_assign_int (map, ival)
  type(index_map_t), intent(inout) :: map
  integer, intent(in) :: ival
  map%entry = ival
end subroutine index_map_assign_int

subroutine index_map_assign_array (map, array)
  type(index_map_t), intent(inout) :: map
  integer, dimension(:), intent(in) :: array
  map%entry = array
end subroutine index_map_assign_array

(Evaluators: procedures)+≡
elemental subroutine index_map_set_entry (map, i, ival)
  type(index_map_t), intent(inout) :: map
  integer, intent(in) :: i
  integer, intent(in) :: ival
  map%entry(i) = ival
end subroutine index_map_set_entry

(Evaluators: procedures)+≡
elemental function index_map_get_entry (map, i) result (ival)
  integer :: ival
  type(index_map_t), intent(in) :: map
  integer, intent(in) :: i
  ival = map%entry(i)
end function index_map_get_entry

```

Index mapping (two-dimensional)

This is a variant with a square matrix instead of an array.

```

(Evaluators: types)+≡
type :: index_map2_t
  integer :: s = 0
  integer, dimension(:,:), allocatable :: entry
end type index_map2_t

(Evaluators: procedures)+≡
elemental subroutine index_map2_init (map, n)
  type(index_map2_t), intent(out) :: map
  integer, intent(in) :: n
  map%s = n
  allocate (map%entry (n, n))
end subroutine index_map2_init

```

```

<Evaluators: procedures>+=
function index_map2_exists (map) result (flag)
    logical :: flag
    type(index_map2_t), intent(in) :: map
    flag = allocated (map%entry)
end function index_map2_exists

<Evaluators: interfaces>+=
interface size
    module procedure index_map2_size
end interface

<Evaluators: procedures>+=
function index_map2_size (map) result (s)
    integer :: s
    type(index_map2_t), intent(in) :: map
    s = map%s
end function index_map2_size

<Evaluators: interfaces>+=
interface assignment(=)
    module procedure index_map2_assign_int
end interface

<Evaluators: procedures>+=
elemental subroutine index_map2_assign_int (map, ival)
    type(index_map2_t), intent(inout) :: map
    integer, intent(in) :: ival
    map%entry = ival
end subroutine index_map2_assign_int

<Evaluators: procedures>+=
elemental subroutine index_map2_set_entry (map, i, j, ival)
    type(index_map2_t), intent(inout) :: map
    integer, intent(in) :: i, j
    integer, intent(in) :: ival
    map%entry(i,j) = ival
end subroutine index_map2_set_entry

<Evaluators: procedures>+=
elemental function index_map2_get_entry (map, i, j) result (ival)
    integer :: ival
    type(index_map2_t), intent(in) :: map
    integer, intent(in) :: i, j
    ival = map%entry(i,j)
end function index_map2_get_entry

```


Auxiliary structures: particle mask

This is a simple container of a logical array.

```
<Evaluators: types>+≡
  type :: prt_mask_t
    logical, dimension(:), allocatable :: entry
  end type prt_mask_t

<Evaluators: procedures>+≡
  subroutine prt_mask_init (mask, n)
    type(prt_mask_t), intent(out) :: mask
    integer, intent(in) :: n
    allocate (mask%entry (n))
  end subroutine prt_mask_init

<Evaluators: interfaces>+≡
  interface size
    module procedure prt_mask_size
  end interface

<Evaluators: procedures>+≡
  function prt_mask_size (mask) result (s)
    integer :: s
    type(prt_mask_t), intent(in) :: mask
    s = size (mask%entry)
  end function prt_mask_size
```

Quantum number containers

Trivial transparent containers:

```
<Evaluators: types>+≡
  type :: qn_list_t
    type(quantum_numbers_t), dimension(:,:), allocatable :: qn
  end type qn_list_t

  type :: qn_mask_array_t
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
  end type qn_mask_array_t
```

Auxiliary structures: connection entries

This type is used as intermediate storage when computing the product of two evaluators or the square of an evaluator. The quantum-number array **qn** corresponds to the particles common to both interactions, but irrelevant quantum numbers (color) masked out. The index arrays **index_in** determine the entries in the input interactions that contribute to this connection. **n_index** is the size of these arrays, and **count** is used while filling the entries. Finally, the quantum-number arrays **qn_in_list** are the actual entries in the input interaction that contribute. In the product case, they exclude the connected quantum numbers.

Each evaluator has its own `connection_table` which contains an array of `connection_entry` objects, but also has stuff that specifically applies to the evaluator type. Hence, we do not generalize the `connection_table_t` type.

The filling procedure `connection_entry_add_state` is specific to the various evaluator types.

(Evaluators: types)+≡

```

type :: connection_entry_t
  type(quantum_numbers_t), dimension(:), allocatable :: qn_conn
  integer, dimension(:), allocatable :: n_index
  integer, dimension(:), allocatable :: count
  type(index_map_t), dimension(:), allocatable :: index_in
  type(qn_list_t), dimension(:), allocatable :: qn_in_list
end type connection_entry_t

```

(Evaluators: procedures)+≡

```

subroutine connection_entry_init &
  (entry, n_count, n_map, qn_conn, count, n_rest)
  type(connection_entry_t), intent(out) :: entry
  integer, intent(in) :: n_count, n_map
  type(quantum_numbers_t), dimension(:), intent(in) :: qn_conn
  integer, dimension(n_count), intent(in) :: count
  integer, dimension(n_count), intent(in) :: n_rest
  integer :: i
  allocate (entry%qn_conn (size (qn_conn)))
  allocate (entry%n_index (n_count))
  allocate (entry%count (n_count))
  allocate (entry%index_in (n_map))
  allocate (entry%qn_in_list (n_count))
  entry%qn_conn = qn_conn
  entry%n_index = count
  entry%count = 0
  if (size (entry%index_in) == size (count)) then
    call index_map_init (entry%index_in, count)
  else
    call index_map_init (entry%index_in, count(1))
  end if
  do i = 1, n_count
    allocate (entry%qn_in_list(i)%qn (n_rest(i), count(i)))
  end do
end subroutine connection_entry_init

```

(Evaluators: procedures)+≡

```

subroutine connection_entry_write (entry, unit)
  type(connection_entry_t), intent(in) :: entry
  integer, intent(in), optional :: unit
  integer :: i, j
  integer :: u
  u = given_output_unit (unit)
  call quantum_numbers_write (entry%qn_conn, unit)
  write (u, *)
  do i = 1, size (entry%n_index)
    write (u, *) "Input interaction", i
    do j = 1, entry%n_index(i)

```

```

        if (size (entry%n_index) == size (entry%index_in)) then
            write (u, "(2x,I0,4x,I0,2x)", advance = "no") &
                j, index_map_get_entry (entry%index_in(i), j)
        else
            write (u, "(2x,I0,4x,I0,2x,I0,2x)", advance = "no") &
                j, index_map_get_entry (entry%index_in(1), j), &
                index_map_get_entry (entry%index_in(2), j)
        end if
        call quantum_numbers_write (entry%qn_in_list(i)%qn(:,j), unit)
        write (u, *)
    end do
end do
end subroutine connection_entry_write

```

Color handling

For managing color-factor computation, we introduce this local type. The `index` is the index in the color table that corresponds to a given matrix element index in the input interaction. The `col` array stores the color assignments in rows. The `factor` array associates a complex number with each pair of arrays in the color table. The `factor_is_known` array reveals whether a given factor is known already or still has to be computed.

```

<Evaluators: types>+≡
type :: color_table_t
    integer, dimension(:), allocatable :: index
    type(color_t), dimension(:,,:), allocatable :: col
    logical, dimension(:,,:), allocatable :: factor_is_known
    complex(default), dimension(:,,:), allocatable :: factor
end type color_table_t

```

This is the initializer. We extract the color states from the given state matrices, establish index mappings between the two states (implemented by the array `me_index`), make an array of color states, and initialize the color-factor table. The latter is two-dimensional (includes interference) and not yet filled.

```

<Evaluators: procedures>+≡
subroutine color_table_init (color_table, state, n_tot)
    type(color_table_t), intent(out) :: color_table
    type(state_matrix_t), intent(in) :: state
    integer, intent(in) :: n_tot
    type(state_iterator_t) :: it
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    type(state_matrix_t) :: state_col
    integer :: index, n_col_state
    allocate (color_table%index (state%get_n_matrix_elements ()))
    color_table%index = 0
    allocate (qn (n_tot))
    call state_col%init ()
    call it%init (state)
    do while (it%is_valid ())
        index = it%get_me_index ()
        call qn%init (col = it%get_color ())
    end do
end subroutine color_table_init

```

```

        call state_col%add_state (qn, me_index = color_table%index(index))
        call it%advance ()
    end do
    n_col_state = state_col%get_n_matrix_elements ()
    allocate (color_table%col (n_tot, n_col_state))
    call it%init (state_col)
    do while (it%is_valid ())
        index = it%get_me_index ()
        color_table%col(:,index) = it%get_color ()
        call it%advance ()
    end do
    call state_col%final ()
    allocate (color_table%factor_is_known (n_col_state, n_col_state))
    allocate (color_table%factor (n_col_state, n_col_state))
    color_table%factor_is_known = .false.
end subroutine color_table_init

```

Output (debugging use):

```

<Evaluators: procedures>+≡
subroutine color_table_write (color_table, unit)
    type(color_table_t), intent(in) :: color_table
    integer, intent(in), optional :: unit
    integer :: i, j
    integer :: u
    u = given_output_unit (unit)
    write (u, *) "Color table:"
    if (allocated (color_table%index)) then
        write (u, *) "  Index mapping state => color table:"
        do i = 1, size (color_table%index)
            write (u, "(3x,I0,2x,I0,2x)") i, color_table%index(i)
        end do
        write (u, *) "  Color table:"
        do i = 1, size (color_table%col, 2)
            write (u, "(3x,I0,2x)", advance = "no") i
            call color_write (color_table%col(:,i), unit)
            write (u, *)
        end do
        write (u, *) "  Defined color factors:"
        do i = 1, size (color_table%factor, 1)
            do j = 1, size (color_table%factor, 2)
                if (color_table%factor_is_known(i,j)) then
                    write (u, *) i, j, color_table%factor(i,j)
                end if
            end do
        end do
    end if
end subroutine color_table_write

```

This subroutine sets color factors, based on information from the hard matrix element: the list of pairs of color-flow indices (in the basis of the matrix element code), the list of corresponding factors, and the list of mappings from the matrix element index in the input interaction to the color-flow index in the hard matrix element object.

We first determine the mapping of color-flow indices from the hard matrix element code to the current color table. The mapping could be nontrivial because the latter is derived from iterating over a state matrix, which may return states in non-canonical order. The translation table can be determined because we have, for the complete state matrix, both the mapping to the hard interaction (the input `col_index_hi`) and the mapping to the current color table (the component `color_table%index`).

Once this mapping is known, we scan the list of index pairs `color_flow_index` and translate them to valid color-table index pairs. For this pair, the color factor is set using the corresponding entry in the list `col_factor`.

```
(Evaluators: procedures)+≡
subroutine color_table_set_color_factors (color_table, &
    col_flow_index, col_factor, col_index_hi)
    type(color_table_t), intent(inout) :: color_table
    integer, dimension(:,:), intent(in) :: col_flow_index
    complex(default), dimension(:), intent(in) :: col_factor
    integer, dimension(:), intent(in) :: col_index_hi
    integer, dimension(:), allocatable :: hi_to_ct
    integer :: n_cflow
    integer :: hi_index, me_index, ct_index, cf_index
    integer, dimension(2) :: hi_index_pair, ct_index_pair
    n_cflow = size (col_index_hi)
    if (size (color_table%index) /= n_cflow) &
        call msg_bug ("Mismatch between hard matrix element and color table")
    allocate (hi_to_ct (n_cflow))
    do me_index = 1, size (color_table%index)
        ct_index = color_table%index(me_index)
        hi_index = col_index_hi(me_index)
        hi_to_ct(hi_index) = ct_index
    end do
    do cf_index = 1, size (col_flow_index, 2)
        hi_index_pair = col_flow_index(:,cf_index)
        ct_index_pair = hi_to_ct(hi_index_pair)
        color_table%factor(ct_index_pair(1), ct_index_pair(2)) = &
            col_factor(cf_index)
        color_table%factor_is_known(ct_index_pair(1), ct_index_pair(2)) = .true.
    end do
end subroutine color_table_set_color_factors
```

This function returns a color factor, given two indices which point to the matrix elements of the initial state matrix. Internally, we can map them to the corresponding indices in the color table. As a side effect, we store the color factor in the color table for later lookup. (I.e., this function is impure.)

```
(Evaluators: procedures)+≡
function color_table_get_color_factor (color_table, index1, index2, nc) &
    result (factor)
    real(default) :: factor
    type(color_table_t), intent(inout) :: color_table
    integer, intent(in) :: index1, index2
    integer, intent(in), optional :: nc
    integer :: i1, i2
    ! print *, "compute color factor ", index1, index2    !!! Debugging
```

```

i1 = color_table%index(index1)
i2 = color_table%index(index2)
! print *, " indices = ", i1, i2                !!! Debugging
if (color_table%factor_is_known(i1,i2)) then
    factor = color_table%factor(i1,i2)
    ! print *, " is known : ", factor            !!! Debugging
else
    factor = compute_color_factor &
        (color_table%col(:,i1), color_table%col(:,i2), nc)
    color_table%factor(i1,i2) = factor
    color_table%factor_is_known(i1,i2) = .true.
    ! print *, " computed : ", factor            !!! Debugging
end if
end function color_table_get_color_factor

```

11.3.4 Creating an evaluator: Matrix multiplication

The evaluator for matrix multiplication is the most complicated variant.

The initializer takes two input interactions and constructs the result evaluator, which consists of the interaction and the multiplication table for the product (or convolution) of the two. Normally, the input interactions are connected by one or more common particles (e.g., decay, structure function convolution).

In the result interaction, quantum numbers of the connections can be summed over. This is determined by the `qn_mask_conn` argument. The `qn_mask_rest` argument is its analog for the other particles within the result interaction. (E.g., for the trace of the state matrix, all quantum numbers are summed over.) Finally, the `connections_are_resonant` argument tells whether the connecting particles should be marked as resonant in the final event record. This is useful for decays.

The algorithm consists of the following steps:

1. **find_connections:** Find the particles which are connected, i.e., common to both input interactions. Either they are directly linked, or both are linked to a common source.
2. **compute_index_bounds_and_mappings:** Compute the mappings of particle indices from the input interactions to the result interaction. There is a separate mapping for the connected particles.
3. **accumulate_connected_states:** Create an auxiliary state matrix which lists the possible quantum numbers for the connected particles. When building this matrix, count the number of times each assignment is contained in any of the input states and, for each of the input states, record the index of the matrix element within the new state matrix. For the connected particles, reassign color indices such that no color state is present twice in different color-index assignment. Note that helicity assignments of the connected state can be (and will be) off-diagonal, so no spin correlations are lost in decays.

Do this for both input interactions.

4. **allocate_connection_entries**: Allocate a table of connections. Each table row corresponds to one state in the auxiliary matrix, and to multiple states of the input interactions. It collects all states of the unconnected particles in the two input interactions that are associated with the particular state (quantum-number assignment) of the connected particles.
5. **fill_connection_table**: Fill the table of connections by scanning both input interactions. When copying states, reassign color indices for the unconnected particles such that they match between all involved particle sets (interaction 1, interaction 2, and connected particles).
6. **make_product_interaction**: Scan the table of connections we have just built. For each entry, construct all possible pairs of states of the unconnected particles and combine them with the specific connected-particle state. This is a possible quantum-number assignment of the result interaction. Now mask all quantum numbers that should be summed over, and append this to the result state matrix. Record the matrix element index of the result. We now have the result interaction.
7. **make_pairing_array**: First allocate the pairing array with the number of entries of the result interaction. Then scan the table of connections again. For each entry, record the indices of the matrix elements which have to be multiplied and summed over in order to compute this particular matrix element. This makes up the multiplication table.
8. **record_links**: Transfer all source pointers from the input interactions to the result interaction. Do the same for the internal parent-child relations and resonance assignments. For the connected particles, make up appropriate additional parent-child relations. This allows for fetching momenta from other interactions when a new event is filled, and to reconstruct the event history when the event is analyzed.

After all this is done, for each event, we just have to evaluate the pairing arrays (multiplication tables) in order to compute the result matrix elements in their proper positions. The quantum-number assignments remain fixed from now on.

```

(Evaluators: evaluator: TBP)+≡
  procedure :: init_product => evaluator_init_product

(Evaluators: procedures)+≡
  subroutine evaluator_init_product &
    (eval, int_in1, int_in2, qn_mask_conn, qn_filter_conn, qn_mask_rest, &
     connections_are_resonant)

    class(evaluator_t), intent(out), target :: eval
    class(interaction_t), intent(in), target :: int_in1, int_in2
    type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
    type(quantum_numbers_t), intent(in), optional :: qn_filter_conn
    type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
    logical, intent(in), optional :: connections_are_resonant

    type(qn_mask_array_t), dimension(2) :: qn_mask_in
    type(state_matrix_t), pointer :: state_in1, state_in2

```

```

type :: connection_table_t
  integer :: n_conn = 0
  integer, dimension(2) :: n_rest = 0
  integer :: n_tot = 0
  integer :: n_me_conn = 0
  type(state_matrix_t) :: state
  type(index_map_t), dimension(:), allocatable :: index_conn
  type(connection_entry_t), dimension(:), allocatable :: entry
  type(index_map_t) :: index_result
end type connection_table_t
type(connection_table_t) :: connection_table

integer :: n_in, n_vir, n_out, n_tot
integer, dimension(2) :: n_rest
integer :: n_conn

integer, dimension(:,:), allocatable :: connection_index
type(index_map_t), dimension(2) :: prt_map_in
type(index_map_t) :: prt_map_conn
type(prt_mask_t), dimension(2) :: prt_is_connected
type(quantum_numbers_mask_t), dimension(:), allocatable :: &
  qn_mask_conn_initial

integer :: i

eval%type = EVAL_PRODUCT
eval%int_in1 => int_in1
eval%int_in2 => int_in2
! print *, "Evaluator product"          !!! Debugging
! print *, "First interaction"          !!! Debugging
! call int_in1%basic_write ()           !!! Debugging
! print *                               !!! Debugging
! print *, "Second interaction"         !!! Debugging
! call int_in2%basic_write ()           !!! Debugging
! print *                               !!! Debugging

state_in1 => int_in1%get_state_matrix_ptr ()
state_in2 => int_in2%get_state_matrix_ptr ()

call find_connections (int_in1, int_in2, n_conn, connection_index)
if (n_conn == 0) then
  call msg_message ("First interaction:")
  call int_in1%basic_write (col_verbosity=.true.)
  call msg_message ("Second interaction:")
  call int_in2%basic_write (col_verbosity=.true.)
  call msg_fatal ("Evaluator product: no connections found between factors")
end if
call compute_index_bounds_and_mappings &
  (int_in1, int_in2, n_conn, &
   n_in, n_vir, n_out, n_tot, &
   n_rest, prt_map_in, prt_map_conn)

call prt_mask_init (prt_is_connected(1), int_in1%get_n_tot ())

```



```

call prt_mask_init (prt_is_connected(2), int_in2%get_n_tot ())
do i = 1, 2
  prt_is_connected(i)%entry = .true.
  prt_is_connected(i)%entry(connection_index(:,i)) = .false.
end do
allocate (qn_mask_conn_initial (n_conn))
qn_mask_conn_initial = &
  int_in1%get_mask (connection_index(:,1)) .or. &
  int_in2%get_mask (connection_index(:,2))
allocate (qn_mask_in(1)%mask (int_in1%get_n_tot ()))
allocate (qn_mask_in(2)%mask (int_in2%get_n_tot ()))
qn_mask_in(1)%mask = int_in1%get_mask ()
qn_mask_in(2)%mask = int_in2%get_mask ()

call connection_table_init (connection_table, &
  state_in1, state_in2, &
  qn_mask_conn_initial, &
  n_conn, connection_index, n_rest, &
  qn_filter_conn)
call connection_table_fill (connection_table, &
  state_in1, state_in2, &
  connection_index, prt_is_connected)
call make_product_interaction (eval%interaction_t, &
  n_in, n_vir, n_out, &
  connection_table, &
  prt_map_in, prt_is_connected, &
  qn_mask_in, qn_mask_conn_initial, &
  qn_mask_conn, qn_filter_conn, qn_mask_rest)
! call connection_table_write (connection_table)      !!! Debugging
call make_pairing_array (eval%pairing_array, &
  eval%get_n_matrix_elements (), &
  connection_table)
call record_links (eval%interaction_t, &
  int_in1, int_in2, connection_index, prt_map_in, prt_map_conn, &
  prt_is_connected, connections_are_resonant)
call connection_table_final (connection_table)

! print *, "Result evaluator"                        !!! Debugging
! call eval%write ()                                !!! Debugging

if (eval%get_n_matrix_elements () == 0) then
  print *, "Evaluator product"
  print *, "First interaction"
  call int_in1%basic_write (col_verbose=.true.)
  print *
  print *, "Second interaction"
  call int_in2%basic_write (col_verbose=.true.)
  print *
  call msg_fatal ("Product of density matrices is empty", &
    [var_str ("-----"), &
    var_str ("This happens when two density matrices are convoluted "), &
    var_str ("but the processes they belong to (e.g., production "), &
    var_str ("and decay) do not match. This could happen if the "), &
    var_str ("beam specification does not match the hard "), &

```

```

        var_str ("process. Or it may indicate a WHIZARD bug.")]
    end if

contains

subroutine compute_index_bounds_and_mappings &
    (int1, int2, n_conn, &
     n_in, n_vir, n_out, n_tot, &
     n_rest, prt_map_in, prt_map_conn)
class(interaction_t), intent(in) :: int1, int2
integer, intent(in) :: n_conn
integer, intent(out) :: n_in, n_vir, n_out, n_tot
integer, dimension(2), intent(out) :: n_rest
type(index_map_t), dimension(2), intent(out) :: prt_map_in
type(index_map_t), intent(out) :: prt_map_conn
integer, dimension(:), allocatable :: index
integer :: n_in1, n_vir1, n_out1
integer :: n_in2, n_vir2, n_out2
integer :: k
n_in1 = int1%get_n_in ()
n_vir1 = int1%get_n_vir ()
n_out1 = int1%get_n_out () - n_conn
n_rest(1) = n_in1 + n_vir1 + n_out1
n_in2 = int2%get_n_in () - n_conn
n_vir2 = int2%get_n_vir ()
n_out2 = int2%get_n_out ()
n_rest(2) = n_in2 + n_vir2 + n_out2
n_in = n_in1 + n_in2
n_vir = n_vir1 + n_vir2 + n_conn
n_out = n_out1 + n_out2
n_tot = n_in + n_vir + n_out
call index_map_init (prt_map_in, n_rest)
call index_map_init (prt_map_conn, n_conn)
allocate (index (n_tot))
index = [ (i, i = 1, n_tot) ]
prt_map_in(1)%entry(1 : n_in1) = index( 1 : n_in1)
k = n_in1
prt_map_in(2)%entry(1 : n_in2) = index(k+1 : k+n_in2)
k = k + n_in2
prt_map_in(1)%entry(n_in1+1 : n_in1+n_vir1) = index(k+1 : k+n_vir1)
k = k + n_vir1
prt_map_in(2)%entry(n_in2+1 : n_in2+n_vir2) = index(k+1 : k+n_vir2)
k = k + n_vir2
prt_map_conn%entry = index(k+1 : k+n_conn)
k = k + n_conn
prt_map_in(1)%entry(n_in1+n_vir1+1 : n_rest(1)) = index(k+1 : k+n_out1)
k = k + n_out1
prt_map_in(2)%entry(n_in2+n_vir2+1 : n_rest(2)) = index(k+1 : k+n_out2)
end subroutine compute_index_bounds_and_mappings

subroutine connection_table_init &
    (connection_table, state_in1, state_in2, qn_mask_conn, &
     n_conn, connection_index, n_rest, &
     qn_filter_conn)

```

```

type(connection_table_t), intent(out) :: connection_table
type(state_matrix_t), intent(in), target :: state_in1, state_in2
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_conn
integer, intent(in) :: n_conn
integer, dimension(:,:), intent(in) :: connection_index
integer, dimension(2), intent(in) :: n_rest
type(quantum_numbers_t), intent(in), optional :: qn_filter_conn
integer, dimension(2) :: n_me_in
type(state_iterator_t) :: it
type(quantum_numbers_t), dimension(n_conn) :: qn
integer :: i, me_index_in, me_index_conn, n_me_conn
integer, dimension(2) :: me_count
connection_table%n_conn = n_conn
connection_table%n_rest = n_rest
n_me_in(1) = state_in1%get_n_matrix_elements ()
n_me_in(2) = state_in2%get_n_matrix_elements ()
allocate (connection_table%index_conn (2))
call index_map_init (connection_table%index_conn, n_me_in)
connection_table%index_conn = 0
call connection_table%state%init (n_counters=2)
do i = 1, 2
  select case (i)
    case (1); call it%init (state_in1)
    case (2); call it%init (state_in2)
  end select
  do while (it%is_valid ())
    qn = it%get_quantum_numbers (connection_index(:,i))
    call qn%undefine (qn_mask_conn)
    if (present (qn_filter_conn)) then
      if (.not. all (qn .match. qn_filter_conn)) then
        call it%advance (); cycle
      end if
    end if
    call quantum_numbers_canonicalize_color (qn)
    me_index_in = it%get_me_index ()
    call connection_table%state%add_state (qn, &
      counter_index = i, me_index = me_index_conn)
    call index_map_set_entry (connection_table%index_conn(i), &
      me_index_in, me_index_conn)
    call it%advance ()
  end do
end do
n_me_conn = connection_table%state%get_n_matrix_elements ()
connection_table%n_me_conn = n_me_conn
allocate (connection_table%entry (n_me_conn))
call it%init (connection_table%state)
do while (it%is_valid ())
  i = it%get_me_index ()
  me_count = it%get_me_count ()
  call connection_entry_init (connection_table%entry(i), 2, 2, &
    it%get_quantum_numbers (), me_count, n_rest)
  call it%advance ()
end do
end subroutine connection_table_init

```

```

subroutine connection_table_final (connection_table)
  type(connection_table_t), intent(inout) :: connection_table
  call connection_table%state%final ()
end subroutine connection_table_final

subroutine connection_table_write (connection_table, unit)
  type(connection_table_t), intent(in) :: connection_table
  integer, intent(in), optional :: unit
  integer :: i, j
  integer :: u
  u = given_output_unit (unit)
  write (u, *) "Connection table:"
  call connection_table%state%write (unit)
  if (allocated (connection_table%index_conn)) then
    write (u, *) "  Index mapping input => connection table:"
    do i = 1, size (connection_table%index_conn)
      write (u, *) "    Input state", i
      do j = 1, size (connection_table%index_conn(i))
        write (u, *)      j, &
          index_map_get_entry (connection_table%index_conn(i), j)
      end do
    end do
  end if
  if (allocated (connection_table%entry)) then
    write (u, *) "  Connection table contents:"
    do i = 1, size (connection_table%entry)
      call connection_entry_write (connection_table%entry(i), unit)
    end do
  end if
  if (index_map_exists (connection_table%index_result)) then
    write (u, *) "  Index mapping connection table => output:"
    do i = 1, size (connection_table%index_result)
      write (u, *)    i, &
        index_map_get_entry (connection_table%index_result, i)
    end do
  end if
end subroutine connection_table_write

subroutine connection_table_fill &
  (connection_table, state_in1, state_in2, &
   connection_index, prt_is_connected)
  type(connection_table_t), intent(inout) :: connection_table
  type(state_matrix_t), intent(in), target :: state_in1, state_in2
  integer, dimension(:, :), intent(in) :: connection_index
  type(prt_mask_t), dimension(2), intent(in) :: prt_is_connected
  type(state_iterator_t) :: it
  integer :: index_in, index_conn
  integer :: color_offset
  integer :: n_result_entries
  integer :: i, k
  color_offset = connection_table%state%get_max_color_value ()
  do i = 1, 2
    select case (i)

```

```

case (1); call it%init (state_in1)
case (2); call it%init (state_in2)
end select
do while (it%is_valid ())
  index_in = it%get_me_index ()
  index_conn = index_map_get_entry &
    (connection_table%index_conn(i), index_in)
  if (index_conn /= 0) then
    call connection_entry_add_state &
      (connection_table%entry(index_conn), i, &
        index_in, it%get_quantum_numbers (), &
        connection_index(:,i), prt_is_connected(i), &
        color_offset)
  end if
  call it%advance ()
end do
color_offset = color_offset + state_in1%get_max_color_value ()
end do
n_result_entries = 0
do k = 1, size (connection_table%entry)
  n_result_entries = &
    n_result_entries + product (connection_table%entry(k)%n_index)
end do
call index_map_init (connection_table%index_result, n_result_entries)
end subroutine connection_table_fill

subroutine connection_entry_add_state &
  (entry, i, index_in, qn_in, connection_index, prt_is_connected, &
    color_offset)
type(connection_entry_t), intent(inout) :: entry
integer, intent(in) :: i
integer, intent(in) :: index_in
type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
integer, dimension(:), intent(in) :: connection_index
type(prt_mask_t), intent(in) :: prt_is_connected
integer, intent(in) :: color_offset
integer :: c
integer, dimension(:,:), allocatable :: color_map
entry%count(i) = entry%count(i) + 1
c = entry%count(i)
call make_color_map (color_map, &
  qn_in(connection_index), entry%qn_conn)
call index_map_set_entry (entry%index_in(i), c, index_in)
entry%qn_in_list(i)%qn(:,c) = pack (qn_in, prt_is_connected%entry)
call quantum_numbers_translate_color &
  (entry%qn_in_list(i)%qn(:,c), color_map, color_offset)
end subroutine connection_entry_add_state

subroutine make_product_interaction (int, &
  n_in, n_vir, n_out, &
  connection_table, &
  prt_map_in, prt_is_connected, &
  qn_mask_in, qn_mask_conn_initial, &
  qn_mask_conn, qn_filter_conn, qn_mask_rest)

```

```

type(interaction_t), intent(out), target :: int
integer, intent(in) :: n_in, n_vir, n_out
type(connection_table_t), intent(inout), target :: connection_table
type(index_map_t), dimension(2), intent(in) :: prt_map_in
type(prt_mask_t), dimension(2), intent(in) :: prt_is_connected
type(qn_mask_array_t), dimension(2), intent(in) :: qn_mask_in
type(quantum_numbers_mask_t), dimension(:), intent(in) :: &
    qn_mask_conn_initial
type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
type(quantum_numbers_t), intent(in), optional :: qn_filter_conn
type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
type(index_map_t), dimension(2) :: prt_index_in
type(index_map_t) :: prt_index_conn
integer :: n_tot, n_conn
integer, dimension(2) :: n_rest
integer :: i, j, k, m
type(quantum_numbers_t), dimension(:), allocatable :: qn
type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
type(connection_entry_t), pointer :: entry
integer :: result_index
n_conn = connection_table%n_conn
n_rest = connection_table%n_rest
n_tot = sum (n_rest) + n_conn
allocate (qn (n_tot), qn_mask (n_tot))
do i = 1, 2
    call index_map_init (prt_index_in(i), n_rest(i))
    prt_index_in(i) = &
        prt_map_in(i)%entry ([ (j, j = 1, n_rest(i)) ])
end do
call index_map_init (prt_index_conn, n_conn)
prt_index_conn = prt_map_conn%entry ([ (j, j = 1, n_conn) ])
do i = 1, 2
    if (present (qn_mask_rest)) then
        qn_mask(prt_index_in(i)%entry) = &
            pack (qn_mask_in(i)%mask, prt_is_connected(i)%entry) &
            .or. qn_mask_rest
    else
        qn_mask(prt_index_in(i)%entry) = &
            pack (qn_mask_in(i)%mask, prt_is_connected(i)%entry)
    end if
end do
qn_mask(prt_index_conn%entry) = qn_mask_conn_initial .or. qn_mask_conn
call eval%interaction_t%basic_init (n_in, n_vir, n_out, mask=qn_mask)
m = 1
do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)
    qn(prt_index_conn%entry) = &
        quantum_numbers_undefined (entry%qn_conn, qn_mask_conn)
    if (present (qn_filter_conn)) then
        if (.not. all (qn(prt_index_conn%entry) .match. qn_filter_conn)) &
            cycle
    end if
    do j = 1, entry%n_index(1)
        qn(prt_index_in(1)%entry) = entry%qn_in_list(1)%qn(:,j)
    end do
end do

```

```

        do k = 1, entry%n_index(2)
            qn(prt_index_in(2)%entry) = entry%qn_in_list(2)%qn(:,k)
            call int%add_state (qn, me_index = result_index)
            call index_map_set_entry &
                (connection_table%index_result, m, result_index)
            m = m + 1
        end do
    end do
end do
call int%freeze ()
end subroutine make_product_interaction

subroutine make_pairing_array (pa, n_matrix_elements, connection_table)
    type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
    integer, intent(in) :: n_matrix_elements
    type(connection_table_t), intent(in), target :: connection_table
    type(connection_entry_t), pointer :: entry
    integer, dimension(:), allocatable :: n_entries
    integer :: i, j, k, m, r
    allocate (pa (n_matrix_elements))
    allocate (n_entries (n_matrix_elements))
    n_entries = 0
    do m = 1, size (connection_table%index_result)
        r = index_map_get_entry (connection_table%index_result, m)
        n_entries(r) = n_entries(r) + 1
    end do
    call pairing_array_init &
        (pa, n_entries, has_i2=.true., has_factor=.false.)
    m = 1
    n_entries = 0
    do i = 1, connection_table%n_me_conn
        entry => connection_table%entry(i)
        do j = 1, entry%n_index(1)
            do k = 1, entry%n_index(2)
                r = index_map_get_entry (connection_table%index_result, m)
                n_entries(r) = n_entries(r) + 1
                pa(r)%i1(n_entries(r)) = &
                    index_map_get_entry (entry%index_in(1), j)
                pa(r)%i2(n_entries(r)) = &
                    index_map_get_entry (entry%index_in(2), k)
                m = m + 1
            end do
        end do
    end do
end subroutine make_pairing_array

subroutine record_links (int, &
    int_in1, int_in2, connection_index, prt_map_in, prt_map_conn, &
    prt_is_connected, connections_are_resonant)
    class(interaction_t), intent(inout) :: int
    class(interaction_t), intent(in), target :: int_in1, int_in2
    integer, dimension(:,:), intent(in) :: connection_index
    type(index_map_t), dimension(2), intent(in) :: prt_map_in
    type(index_map_t), intent(in) :: prt_map_conn

```

```

type(prt_mask_t), dimension(2), intent(in) :: prt_is_connected
logical, intent(in), optional :: connections_are_resonant
type(index_map_t), dimension(2) :: prt_map_all
integer :: i, j, k, ival
call index_map_init (prt_map_all(1), size (prt_is_connected(1)))
k = 0
j = 0
do i = 1, size (prt_is_connected(1))
  if (prt_is_connected(1)%entry(i)) then
    j = j + 1
    ival = index_map_get_entry (prt_map_in(1), j)
    call index_map_set_entry (prt_map_all(1), i, ival)
  else
    k = k + 1
    ival = index_map_get_entry (prt_map_conn, k)
    call index_map_set_entry (prt_map_all(1), i, ival)
  end if
  call int%set_source_link (ival, int_in1, i)
end do
call int_in1%transfer_relations (int, prt_map_all(1)%entry)
call index_map_init (prt_map_all(2), size (prt_is_connected(2)))
j = 0
do i = 1, size (prt_is_connected(2))
  if (prt_is_connected(2)%entry(i)) then
    j = j + 1
    ival = index_map_get_entry (prt_map_in(2), j)
    call index_map_set_entry (prt_map_all(2), i, ival)
    call int%set_source_link (ival, int_in2, i)
  else
    call index_map_set_entry (prt_map_all(2), i, 0)
  end if
end do
call int_in2%transfer_relations (int, prt_map_all(2)%entry)
call int%relate_connections &
  (int_in2, connection_index(:,2), prt_map_all(2)%entry, &
   prt_map_conn%entry, connections_are_resonant)
end subroutine record_links

end subroutine evaluator_init_product

```

11.3.5 Creating an evaluator: square

The generic initializer for an evaluator that squares a matrix element. Depending on the provided mask, we select the appropriate specific initializer for either diagonal or non-diagonal helicity density matrices.

(Evaluators: evaluator: TBP)+≡

```
procedure :: init_square => evaluator_init_square
```

(Evaluators: procedures)+≡

```

subroutine evaluator_init_square (eval, int_in, qn_mask, &
  col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)
class(evaluator_t), intent(out), target :: eval
class(interaction_t), intent(in), target :: int_in

```



```

type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
integer, dimension(:,:), intent(in), optional :: col_flow_index
complex(default), dimension(:), intent(in), optional :: col_factor
integer, dimension(:), intent(in), optional :: col_index_hi
logical, intent(in), optional :: expand_color_flows
integer, intent(in), optional :: nc
if (all (qn_mask%diagonal_helicity ())) then
    call eval%init_square_diag (int_in, qn_mask, &
        col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)
else
    call eval%init_square_nondiag (int_in, qn_mask, &
        col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)
end if
end subroutine evaluator_init_square

```

Color-summed squared matrix (diagonal helicities)

The initializer for an evaluator that squares a matrix element, including color factors. The mask must be such that off-diagonal matrix elements are excluded.

If `color_flows` is set, the evaluator keeps color-flow entries separate and drops all interfering color structures. The color factors are set to unity in this case.

There is only one input interaction. The quantum-number mask is an array, one entry for each particle, so they can be treated individually. For academic purposes, we allow for the number of colors being different from three (but 3 is the default).

The algorithm is analogous to multiplication, with a few notable differences:

1. The connected particles are known, the correspondence is one-to-one. All particles are connected, and the mapping of indices is trivial, which simplifies the following steps.
2. `accumulate_connected_states`: The matrix of connected states encompasses all particles, but color indices are removed. However, ghost states are still kept separate from physical color states. No color-index reassignment is necessary.
3. The table of connections contains single index and quantum-number arrays instead of pairs of them. They are paired with themselves in all possible ways.
4. `make_squared_interaction`: Now apply the predefined quantum-numbers mask, which usually collects all color states (physical and ghosts), and possibly a helicity sum.
5. `make_pairing_array`: For each pair of input states, compute the color factor (including a potential ghost-parity sign) and store this in the pairing array together with the matrix-element indices for multiplication.
6. `record_links`: This is again trivial due to the one-to-one correspondence.

(*Evaluators: evaluator: TBP*) +=

```

procedure :: init_square_diag => evaluator_init_square_diag

```

```

(Evaluators: procedures)+≡
subroutine evaluator_init_square_diag (eval, int_in, qn_mask, &
    col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)

class(evaluator_t), intent(out), target :: eval
class(interaction_t), intent(in), target :: int_in
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
integer, dimension(:,:), intent(in), optional :: col_flow_index
complex(default), dimension(:), intent(in), optional :: col_factor
integer, dimension(:), intent(in), optional :: col_index_hi
logical, intent(in), optional :: expand_color_flows
integer, intent(in), optional :: nc

integer :: n_in, n_vir, n_out, n_tot
type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask_initial
type(state_matrix_t), pointer :: state_in

type :: connection_table_t
    integer :: n_tot = 0
    integer :: n_me_conn = 0
    type(state_matrix_t) :: state
    type(index_map_t) :: index_conn
    type(connection_entry_t), dimension(:), allocatable :: entry
    type(index_map_t) :: index_result
end type connection_table_t
type(connection_table_t) :: connection_table

logical :: sum_colors
type(color_table_t) :: color_table

if (present (expand_color_flows)) then
    sum_colors = .not. expand_color_flows
else
    sum_colors = .true.
end if

if (sum_colors) then
    eval%type = EVAL_SQUARE_WITH_COLOR_FACTORS
else
    eval%type = EVAL_SQUARED_FLOWS
end if
eval%int_in1 => int_in

! print *, "Interaction square with color factors (diag)" !!! Debugging
! print *, "Input interaction" !!! Debugging
! call int_in%basic_write () !!! Debugging

n_in = int_in%get_n_in ()
n_vir = int_in%get_n_vir ()
n_out = int_in%get_n_out ()
n_tot = int_in%get_n_tot ()

state_in => int_in%get_state_matrix_ptr ()

```

```

allocate (qn_mask_initial (n_tot))
qn_mask_initial = int_in%get_mask ()
call qn_mask_initial%set_color (sum_colors, mask_cg=.false.)
if (sum_colors) then
  call color_table_init (color_table, state_in, n_tot)
  if (present (col_flow_index) .and. present (col_factor) &
    .and. present (col_index_hi)) then
    call color_table_set_color_factors &
      (color_table, col_flow_index, col_factor, col_index_hi)
  end if
  ! call color_table_write (color_table)      !!! Debugging
end if

call connection_table_init (connection_table, state_in, &
  qn_mask_initial, qn_mask, n_tot)
call connection_table_fill (connection_table, state_in)
call make_squared_interaction (eval%interaction_t, &
  n_in, n_vir, n_out, n_tot, &
  connection_table, sum_colors, qn_mask_initial .or. qn_mask)
call make_pairing_array (eval%pairing_array, &
  eval%get_n_matrix_elements (), &
  connection_table, sum_colors, color_table, n_in, n_tot, nc)
call record_links (eval, int_in, n_tot)
call connection_table_final (connection_table)
! print *, "Result evaluator:"      !!! Debugging
! call eval%write ()                !!! Debugging

```

contains

```

subroutine connection_table_init &
  (connection_table, state_in, qn_mask_in, qn_mask, n_tot)
  type(connection_table_t), intent(out) :: connection_table
  type(state_matrix_t), intent(in), target :: state_in
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
  integer, intent(in) :: n_tot
  type(quantum_numbers_t), dimension(n_tot) :: qn
  type(state_iterator_t) :: it
  integer :: i, n_me_in, me_index_in
  integer :: me_index_conn, n_me_conn
  integer, dimension(1) :: me_count
  logical :: qn_passed
  connection_table%n_tot = n_tot
  n_me_in = state_in%get_n_matrix_elements ()
  call index_map_init (connection_table%index_conn, n_me_in)
  connection_table%index_conn = 0
  call connection_table%state%init (n_counters=1)
  call it%init (state_in)
  do while (it%is_valid ())
    qn = it%get_quantum_numbers ()
    if (all (quantum_numbers_are_physical (qn, qn_mask))) then
      call qn%undefine (qn_mask_in)
      qn_passed = .true.
      if (qn_passed) then

```

```

        me_index_in = it%get_me_index ()
        call connection_table%state%add_state (qn, &
            counter_index = 1, me_index = me_index_conn)
        call index_map_set_entry (connection_table%index_conn, &
            me_index_in, me_index_conn)
    end if
end if
call it%advance ()
end do
n_me_conn = connection_table%state%get_n_matrix_elements ()
connection_table%n_me_conn = n_me_conn
allocate (connection_table%entry (n_me_conn))
call it%init (connection_table%state)
do while (it%is_valid ())
    i = it%get_me_index ()
    me_count = it%get_me_count ()
    call connection_entry_init (connection_table%entry(i), 1, 2, &
        it%get_quantum_numbers (), me_count, [n_tot])
    call it%advance ()
end do
end subroutine connection_table_init

subroutine connection_table_final (connection_table)
    type(connection_table_t), intent(inout) :: connection_table
    call connection_table%state%final ()
end subroutine connection_table_final

subroutine connection_table_write (connection_table, unit)
    type(connection_table_t), intent(in) :: connection_table
    integer, intent(in), optional :: unit
    integer :: i
    integer :: u
    u = given_output_unit (unit)
    write (u, *) "Connection table:"
    call connection_table%state%write (unit)
    if (index_map_exists (connection_table%index_conn)) then
        write (u, *) " Index mapping input => connection table:"
        do i = 1, size (connection_table%index_conn)
            write (u, *) i, &
                index_map_get_entry (connection_table%index_conn, i)
        end do
    end if
    if (allocated (connection_table%entry)) then
        write (u, *) " Connection table contents"
        do i = 1, size (connection_table%entry)
            call connection_entry_write (connection_table%entry(i), unit)
        end do
    end if
    if (index_map_exists (connection_table%index_result)) then
        write (u, *) " Index mapping connection table => output"
        do i = 1, size (connection_table%index_result)
            write (u, *) i, &
                index_map_get_entry (connection_table%index_result, i)
        end do
    end if
end do

```

```

end if
end subroutine connection_table_write

subroutine connection_table_fill (connection_table, state)
  type(connection_table_t), intent(inout) :: connection_table
  type(state_matrix_t), intent(in), target :: state
  integer :: index_in, index_conn, n_result_entries
  type(state_iterator_t) :: it
  integer :: k
  call it%init (state)
  do while (it%is_valid ())
    index_in = it%get_me_index ()
    index_conn = &
      index_map_get_entry (connection_table%index_conn, index_in)
    if (index_conn /= 0) then
      call connection_entry_add_state &
        (connection_table%entry(index_conn), &
          index_in, it%get_quantum_numbers ())
    end if
    call it%advance ()
  end do
  n_result_entries = 0
  do k = 1, size (connection_table%entry)
    n_result_entries = &
      n_result_entries + connection_table%entry(k)%n_index(1) ** 2
  end do
  call index_map_init (connection_table%index_result, n_result_entries)
  connection_table%index_result = 0
end subroutine connection_table_fill

subroutine connection_entry_add_state (entry, index_in, qn_in)
  type(connection_entry_t), intent(inout) :: entry
  integer, intent(in) :: index_in
  type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
  integer :: c
  entry%count = entry%count + 1
  c = entry%count(1)
  call index_map_set_entry (entry%index_in(1), c, index_in)
  entry%qn_in_list(1)%qn(:,c) = qn_in
end subroutine connection_entry_add_state

subroutine make_squared_interaction (int, &
  n_in, n_vir, n_out, n_tot, &
  connection_table, sum_colors, qn_mask)
  type(interaction_t), intent(out), target :: int
  integer, intent(in) :: n_in, n_vir, n_out, n_tot
  type(connection_table_t), intent(inout), target :: connection_table
  logical, intent(in) :: sum_colors
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
  type(connection_entry_t), pointer :: entry
  integer :: result_index, n_contrib
  integer :: i, m
  type(quantum_numbers_t), dimension(n_tot) :: qn
  call eval%interaction_t%basic_init (n_in, n_vir, n_out, mask=qn_mask)

```

```

m = 0
do i = 1, connection_table%n_me_conn
  entry => connection_table%entry(i)
  qn = quantum_numbers_undefined (entry%qn_conn, qn_mask)
  if (.not. sum_colors) call qn(1:n_in)%invert_color ()
  call int%add_state (qn, me_index = result_index)
  n_contrib = entry%n_index(1) ** 2
  connection_table%index_result%entry(m+1:m+n_contrib) = result_index
  m = m + n_contrib
end do
call int%freeze ()
end subroutine make_squared_interaction

subroutine make_pairing_array (pa, &
  n_matrix_elements, connection_table, sum_colors, color_table, &
  n_in, n_tot, nc)
  type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
  integer, intent(in) :: n_matrix_elements
  type(connection_table_t), intent(in), target :: connection_table
  logical, intent(in) :: sum_colors
  type(color_table_t), intent(inout) :: color_table
  type(connection_entry_t), pointer :: entry
  integer, intent(in) :: n_in, n_tot
  integer, intent(in), optional :: nc
  integer, dimension(:), allocatable :: n_entries
  integer :: i, k, l, ks, ls, m, r
  integer :: color_multiplicity_in
  allocate (pa (n_matrix_elements))
  allocate (n_entries (n_matrix_elements))
  n_entries = 0
  do m = 1, size (connection_table%index_result)
    r = index_map_get_entry (connection_table%index_result, m)
    n_entries(r) = n_entries(r) + 1
  end do
  call pairing_array_init &
    (pa, n_entries, has_i2 = sum_colors, has_factor = sum_colors)
  m = 1
  n_entries = 0
  do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)
    do k = 1, entry%n_index(1)
      if (sum_colors) then
        color_multiplicity_in = &
          product (abs (quantum_numbers_get_color_type &
            (entry%qn_in_list(1)%qn(:n_in, k))))
      end if
      do l = 1, entry%n_index(1)
        r = index_map_get_entry (connection_table%index_result, m)
        n_entries(r) = n_entries(r) + 1
        ks = index_map_get_entry (entry%index_in(1), k)
        ls = index_map_get_entry (entry%index_in(1), l)
        pa(r)%i1(n_entries(r)) = ks
        pa(r)%i2(n_entries(r)) = ls
        pa(r)%factor(n_entries(r)) = &
          color_table_get_color_factor (color_table, ks, ls, nc) &

```

```

                                / color_multiplicity_in
                                m = m + 1
                                end do
                                else
                                r = index_map_get_entry (connection_table%index_result, m)
                                n_entries(r) = n_entries(r) + 1
                                ks = index_map_get_entry (entry%index_in(1), k)
                                pa(r)%i1(n_entries(r)) = ks
                                m = m + 1
                                end if
                                end do
                                end do
end subroutine make_pairing_array

subroutine record_links (int, int_in, n_tot)
  class(interaction_t), intent(inout) :: int
  class(interaction_t), intent(in), target :: int_in
  integer, intent(in) :: n_tot
  integer, dimension(n_tot) :: map
  integer :: i
  do i = 1, n_tot
    call int%set_source_link (i, int_in, i)
  end do
  map = [ (i, i = 1, n_tot) ]
  call int_in%transfer_relations (int, map)
end subroutine record_links

end subroutine evaluator_init_square_diag

```

Color-summed squared matrix (support nodiagonal helicities)

The initializer for an evaluator that squares a matrix element, including color factors. Unless requested otherwise by the quantum-number mask, the result contains off-diagonal matrix elements. (The input interaction must be diagonal since it represents an amplitude, not a density matrix.)

There is only one input interaction. The quantum-number mask is an array, one entry for each particle, so they can be treated individually. For academic purposes, we allow for the number of colors being different from three (but 3 is the default).

The algorithm is analogous to the previous one, with some additional complications due to the necessity to loop over two helicity indices.

(Evaluators: evaluator: TBP)+≡

```

  procedure :: init_square_nondiag => evaluator_init_square_nondiag

```

(Evaluators: procedures)+≡

```

  subroutine evaluator_init_square_nondiag (eval, int_in, qn_mask, &
    col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)

```

```

  class(evaluator_t), intent(out), target :: eval
  class(interaction_t), intent(in), target :: int_in
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
  integer, dimension(:, :), intent(in), optional :: col_flow_index

```

```

complex(default), dimension(:), intent(in), optional :: col_factor
integer, dimension(:), intent(in), optional :: col_index_hi
logical, intent(in), optional :: expand_color_flows
integer, intent(in), optional :: nc

integer :: n_in, n_vir, n_out, n_tot
type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask_initial
type(state_matrix_t), pointer :: state_in

type :: connection_table_t
  integer :: n_tot = 0
  integer :: n_me_conn = 0
  type(state_matrix_t) :: state
  type(index_map2_t) :: index_conn
  type(connection_entry_t), dimension(:), allocatable :: entry
  type(index_map_t) :: index_result
end type connection_table_t
type(connection_table_t) :: connection_table

logical :: sum_colors
type(color_table_t) :: color_table

if (present (expand_color_flows)) then
  sum_colors = .not. expand_color_flows
else
  sum_colors = .true.
end if

if (sum_colors) then
  eval%type = EVAL_SQUARE_WITH_COLOR_FACTORS
else
  eval%type = EVAL_SQUARED_FLOWS
end if
eval%int_in1 => int_in

! print *, "Interaction square with color factors (nondiag)" !!! Debugging
! print *, "Input interaction" !!! Debugging
! call int_int%basic_write () !!! Debugging
n_in = int_in%get_n_in ()
n_vir = int_in%get_n_vir ()
n_out = int_in%get_n_out ()
n_tot = int_in%get_n_tot ()

state_in => int_in%get_state_matrix_ptr ()

allocate (qn_mask_initial (n_tot))
qn_mask_initial = int_in%get_mask ()
call qn_mask_initial%set_color (sum_colors, mask_cg=.false.)
if (sum_colors) then
  call color_table_init (color_table, state_in, n_tot)
  if (present (col_flow_index) .and. present (col_factor) &
    .and. present (col_index_hi)) then
    call color_table_set_color_factors &
      (color_table, col_flow_index, col_factor, col_index_hi)
  end if
end if

```



```

        end if
        ! call color_table_write (color_table)      !!! Debugging
    end if

    call connection_table_init (connection_table, state_in, &
        qn_mask_initial, qn_mask, n_tot)
    call connection_table_fill (connection_table, state_in)
    call make_squared_interaction (eval%interaction_t, &
        n_in, n_vir, n_out, n_tot, &
        connection_table, sum_colors, qn_mask_initial .or. qn_mask)
    ! call connection_table_write (connection_table)      !!! Debugging
    call make_pairing_array (eval%pairing_array, &
        eval%get_n_matrix_elements (), &
        connection_table, sum_colors, color_table, n_in, n_tot, nc)
    call record_links (eval, int_in, n_tot)
    call connection_table_final (connection_table)

    ! print *, "Result evaluator:"      !!! Debugging
    ! call eval%write ()                !!! Debugging

contains

subroutine connection_table_init &
    (connection_table, state_in, qn_mask_in, qn_mask, n_tot)
    type(connection_table_t), intent(out) :: connection_table
    type(state_matrix_t), intent(in), target :: state_in
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
    integer, intent(in) :: n_tot
    type(quantum_numbers_t), dimension(n_tot) :: qn1, qn2, qn
    type(state_iterator_t) :: it1, it2, it
    integer :: i, n_me_in, me_index_in1, me_index_in2
    integer :: me_index_conn, n_me_conn
    integer, dimension(1) :: me_count
    logical :: qn_passed
    connection_table%n_tot = n_tot
    n_me_in = state_in%get_n_matrix_elements ()
    call index_map2_init (connection_table%index_conn, n_me_in)
    connection_table%index_conn = 0
    call connection_table%state%init (n_counters=1)
    call it1%init (state_in)
    do while (it1%is_valid ())
        qn1 = it1%get_quantum_numbers ()
        me_index_in1 = it1%get_me_index ()
        call it2%init (state_in)
        do while (it2%is_valid ())
            qn2 = it2%get_quantum_numbers ()
            if (all (quantum_numbers_are_compatible (qn1, qn2, qn_mask))) then
                qn = qn1 .merge. qn2
                call qn%undefine (qn_mask_in)
                qn_passed = .true.
                if (qn_passed) then
                    me_index_in2 = it2%get_me_index ()
                    call connection_table%state%add_state (qn, &

```

```

        counter_index = 1, me_index = me_index_conn)
    call index_map2_set_entry (connection_table%index_conn, &
        me_index_in1, me_index_in2, me_index_conn)
    end if
end if
call it2%advance ()
end do
call it1%advance ()
end do
n_me_conn = connection_table%state%get_n_matrix_elements ()
connection_table%n_me_conn = n_me_conn
allocate (connection_table%entry (n_me_conn))
call it%init (connection_table%state)
do while (it%is_valid ())
    i = it%get_me_index ()
    me_count = it%get_me_count ()
    call connection_entry_init (connection_table%entry(i), 1, 2, &
        it%get_quantum_numbers (), me_count, [n_tot])
    call it%advance ()
end do
end subroutine connection_table_init

subroutine connection_table_final (connection_table)
    type(connection_table_t), intent(inout) :: connection_table
    call connection_table%state%final ()
end subroutine connection_table_final

subroutine connection_table_write (connection_table, unit)
    type(connection_table_t), intent(in) :: connection_table
    integer, intent(in), optional :: unit
    integer :: i, j
    integer :: u
    u = given_output_unit (unit)
    write (u, *) "Connection table:"
    call connection_table%state%write (unit)
    if (index_map2_exists (connection_table%index_conn)) then
        write (u, *) " Index mapping input => connection table:"
        do i = 1, size (connection_table%index_conn)
            do j = 1, size (connection_table%index_conn)
                write (u, *) i, j, &
                    index_map2_get_entry (connection_table%index_conn, i, j)
            end do
        end do
    end if
    if (allocated (connection_table%entry)) then
        write (u, *) " Connection table contents"
        do i = 1, size (connection_table%entry)
            call connection_entry_write (connection_table%entry(i), unit)
        end do
    end if
    if (index_map_exists (connection_table%index_result)) then
        write (u, *) " Index mapping connection table => output"
        do i = 1, size (connection_table%index_result)
            write (u, *) i, &

```

```

        index_map_get_entry (connection_table%index_result, i)
    end do
end if
end subroutine connection_table_write

subroutine connection_table_fill (connection_table, state)
    type(connection_table_t), intent(inout), target :: connection_table
    type(state_matrix_t), intent(in), target :: state
    integer :: index1_in, index2_in, index_conn, n_result_entries
    type(state_iterator_t) :: it1, it2
    integer :: k
    call it1%init (state)
    do while (it1%is_valid ())
        index1_in = it1%get_me_index ()
        call it2%init (state)
        do while (it2%is_valid ())
            index2_in = it2%get_me_index ()
            index_conn = index_map2_get_entry &
                (connection_table%index_conn, index1_in, index2_in)
            if (index_conn /= 0) then
                call connection_entry_add_state &
                    (connection_table%entry(index_conn), &
                     index1_in, index2_in, &
                     it1%get_quantum_numbers () &
                     .merge. &
                     it2%get_quantum_numbers ())
            end if
            call it2%advance ()
        end do
        call it1%advance ()
    end do
    n_result_entries = 0
    do k = 1, size (connection_table%entry)
        n_result_entries = &
            n_result_entries + connection_table%entry(k)%n_index(1)
    end do
    call index_map_init (connection_table%index_result, n_result_entries)
    connection_table%index_result = 0
end subroutine connection_table_fill

subroutine connection_entry_add_state (entry, index1_in, index2_in, qn_in)
    type(connection_entry_t), intent(inout) :: entry
    integer, intent(in) :: index1_in, index2_in
    type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
    integer :: c
    entry%count = entry%count + 1
    c = entry%count(1)
    call index_map_set_entry (entry%index_in(1), c, index1_in)
    call index_map_set_entry (entry%index_in(2), c, index2_in)
    entry%qn_in_list(1)%qn(:,c) = qn_in
end subroutine connection_entry_add_state

subroutine make_squared_interaction (int, &
    n_in, n_vir, n_out, n_tot, &

```

```

        connection_table, sum_colors, qn_mask)
type(interaction_t), intent(out), target :: int
integer, intent(in) :: n_in, n_vir, n_out, n_tot
type(connection_table_t), intent(inout), target :: connection_table
logical, intent(in) :: sum_colors
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
type(connection_entry_t), pointer :: entry
integer :: result_index
integer :: i, k, m
type(quantum_numbers_t), dimension(n_tot) :: qn
call eval%interaction_t%basic_init (n_in, n_vir, n_out, mask=qn_mask)
m = 0
do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)
    do k = 1, size (entry%qn_in_list(1)%qn, 2)
        qn = quantum_numbers_undefined &
            (entry%qn_in_list(1)%qn(:,k), qn_mask)
        if (.not. sum_colors) call qn(1:n_in)%invert_color ()
        call int%add_state (qn, me_index = result_index)
        call index_map_set_entry (connection_table%index_result, m + 1, &
            result_index)
        m = m + 1
    end do
end do
call int%freeze ()
end subroutine make_squared_interaction

subroutine make_pairing_array (pa, &
    n_matrix_elements, connection_table, sum_colors, color_table, &
    n_in, n_tot, nc)
type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
integer, intent(in) :: n_matrix_elements
type(connection_table_t), intent(in), target :: connection_table
logical, intent(in) :: sum_colors
type(color_table_t), intent(inout) :: color_table
type(connection_entry_t), pointer :: entry
integer, intent(in) :: n_in, n_tot
integer, intent(in), optional :: nc
integer, dimension(:), allocatable :: n_entries
integer :: i, k, k1s, k2s, m, r
integer :: color_multiplicity_in
allocate (pa (n_matrix_elements))
allocate (n_entries (n_matrix_elements))
n_entries = 0
do m = 1, size (connection_table%index_result)
    r = index_map_get_entry (connection_table%index_result, m)
    n_entries(r) = n_entries(r) + 1
end do
call pairing_array_init &
    (pa, n_entries, has_i2 = sum_colors, has_factor = sum_colors)
m = 1
n_entries = 0
do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)

```

```

do k = 1, entry%n_index(1)
  r = index_map_get_entry (connection_table%index_result, m)
  n_entries(r) = n_entries(r) + 1
  if (sum_colors) then
    k1s = index_map_get_entry (entry%index_in(1), k)
    k2s = index_map_get_entry (entry%index_in(2), k)
    pa(r)%i1(n_entries(r)) = k1s
    pa(r)%i2(n_entries(r)) = k2s
    color_multiplicity_in = &
      product (abs (quantum_numbers_get_color_type &
        (entry%qn_in_list(1)%qn(:n_in, k))))
    pa(r)%factor(n_entries(r)) = &
      color_table_get_color_factor (color_table, k1s, k2s, nc) &
      / color_multiplicity_in
  else
    k1s = index_map_get_entry (entry%index_in(1), k)
    pa(r)%i1(n_entries(r)) = k1s
  end if
  m = m + 1
end do
end subroutine make_pairing_array

subroutine record_links (int, int_in, n_tot)
  class(interaction_t), intent(inout) :: int
  class(interaction_t), intent(in), target :: int_in
  integer, intent(in) :: n_tot
  integer, dimension(n_tot) :: map
  integer :: i
  do i = 1, n_tot
    call int%set_source_link (i, int_in, i)
  end do
  map = [ (i, i = 1, n_tot) ]
  call int_in%transfer_relations (int, map)
end subroutine record_links

end subroutine evaluator_init_square_nondiag

```

Copy with additional contracted color states

This evaluator involves no square or multiplication, its matrix elements are just copies of the (single) input interaction. However, the state matrix of the interaction contains additional states that have color indices contracted. This is used for copies of the beam or structure-function interactions that need to match the hard interaction also in the case where its color indices coincide.

(Evaluators: evaluator: TBP) +=

```
procedure :: init_color_contractions => evaluator_init_color_contractions
```

(Evaluators: procedures) +=

```

subroutine evaluator_init_color_contractions (eval, int_in)
  class(evaluator_t), intent(out), target :: eval
  type(interaction_t), intent(in), target :: int_in
  integer :: n_in, n_vir, n_out, n_tot

```

```

type(state_matrix_t) :: state_with_contractions
integer, dimension(:), allocatable :: me_index
integer, dimension(:), allocatable :: result_index
eval%type = EVAL_COLOR_CONTRACTION
eval%int_in1 => int_in
! print *, "Interaction with additional color contractions" !!! Debugging
! print *, "Input interaction" !!! Debugging
! call int_in%basic_write () !!! Debugging
n_in = int_in%get_n_in ()
n_vir = int_in%get_n_vir ()
n_out = int_in%get_n_out ()
n_tot = int_in%get_n_tot ()
state_with_contractions = int_in%get_state_matrix_ptr ()
call state_with_contractions%add_color_contractions ()
call make_contracted_interaction (eval%interaction_t, &
    me_index, result_index, &
    n_in, n_vir, n_out, n_tot, &
    state_with_contractions, int_in%get_mask ())
call make_pairing_array (eval%pairing_array, me_index, result_index)
call record_links (eval, int_in, n_tot)
call state_with_contractions%final ()
! print *, "Result evaluator:" !!! Debugging
! call eval%write () !!! Debugging

```

contains

```

subroutine make_contracted_interaction (int, &
    me_index, result_index, &
    n_in, n_vir, n_out, n_tot, state, qn_mask)
type(interaction_t), intent(out), target :: int
integer, dimension(:), intent(out), allocatable :: me_index
integer, dimension(:), intent(out), allocatable :: result_index
integer, intent(in) :: n_in, n_vir, n_out, n_tot
type(state_matrix_t), intent(in) :: state
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
type(state_iterator_t) :: it
integer :: n_me, i
type(quantum_numbers_t), dimension(n_tot) :: qn
call int%basic_init (n_in, n_vir, n_out, mask=qn_mask)
n_me = state%get_n_leaves ()
allocate (me_index (n_me))
allocate (result_index (n_me))
call it%init (state)
i = 0
do while (it%is_valid ())
    i = i + 1
    me_index(i) = it%get_me_index ()
    qn = it%get_quantum_numbers ()
    call int%add_state (qn, me_index = result_index(i))
    call it%advance ()
end do
call int%freeze ()
end subroutine make_contracted_interaction

```

```

subroutine make_pairing_array (pa, me_index, result_index)
  type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
  integer, dimension(:), intent(in) :: me_index, result_index
  integer, dimension(:), allocatable :: n_entries
  integer :: n_matrix_elements, r, i
  n_matrix_elements = size (me_index)
  allocate (pa (n_matrix_elements))
  allocate (n_entries (n_matrix_elements))
  n_entries = 1
  call pairing_array_init &
    (pa, n_entries, has_i2=.false., has_factor=.false.)
  do i = 1, n_matrix_elements
    r = result_index(i)
    pa(r)%i1(1) = me_index(i)
  end do
end subroutine make_pairing_array

subroutine record_links (int, int_in, n_tot)
  class(interaction_t), intent(inout) :: int
  class(interaction_t), intent(in), target :: int_in
  integer, intent(in) :: n_tot
  integer, dimension(n_tot) :: map
  integer :: i
  do i = 1, n_tot
    call int%set_source_link (i, int_in, i)
  end do
  map = [ (i, i = 1, n_tot) ]
  call int_in%transfer_relations (int, map)
end subroutine record_links

end subroutine evaluator_init_color_contractions

```

Auxiliary procedure for initialization

This will become a standard procedure in F2008. The result is true if the number of true values in the mask is odd. We use the function for determining the ghost parity of a quantum-number array.

```

<Evaluators: procedures>+=
function parity (mask)
  logical :: parity
  logical, dimension(:) :: mask
  integer :: i
  parity = .false.
  do i = 1, size (mask)
    if (mask(i)) parity = .not. parity
  end do
end function parity

```

Reassign external source links from one to another.

```

<Evaluators: public>+=
public :: evaluator_reassign_links

```

```

<Evaluators: interfaces>+=
interface evaluator_reassign_links
  module procedure evaluator_reassign_links_eval
  module procedure evaluator_reassign_links_int
end interface

<Evaluators: procedures>+=
subroutine evaluator_reassign_links_eval (eval, eval_src, eval_target)
  type(evaluator_t), intent(inout) :: eval
  type(evaluator_t), intent(in) :: eval_src
  type(evaluator_t), intent(in), target :: eval_target
  if (associated (eval%int_in1)) then
    if (eval%int_in1%get_tag () &
      == eval_src%get_tag ()) then
      eval%int_in1 => eval_target%interaction_t
    end if
  end if
  if (associated (eval%int_in2)) then
    if (eval%int_in2%get_tag () &
      == eval_src%get_tag ()) then
      eval%int_in2 => eval_target%interaction_t
    end if
  end if
  call interaction_reassign_links &
    (eval%interaction_t, eval_src%interaction_t, &
    eval_target%interaction_t)
end subroutine evaluator_reassign_links_eval

subroutine evaluator_reassign_links_int (eval, int_src, int_target)
  type(evaluator_t), intent(inout) :: eval
  type(interaction_t), intent(in) :: int_src
  type(interaction_t), intent(in), target :: int_target
  if (associated (eval%int_in1)) then
    if (eval%int_in1%get_tag () &
      == int_src%get_tag ()) then
      eval%int_in1 => int_target
    end if
  end if
  if (associated (eval%int_in2)) then
    if (eval%int_in2%get_tag () &
      == int_src%get_tag ()) then
      eval%int_in2 => int_target
    end if
  end if
  call interaction_reassign_links (eval%interaction_t, int_src, int_target)
end subroutine evaluator_reassign_links_int

```

Return flavor, momentum, and position of the first unstable particle present in the interaction.

```

<Evaluators: public>+=
public :: evaluator_get_unstable_particle

<Evaluators: procedures>+=
subroutine evaluator_get_unstable_particle (eval, flv, p, i)

```



```

type(evaluator_t), intent(in) :: eval
type(flavor_t), intent(out) :: flv
type(vector4_t), intent(out) :: p
integer, intent(out) :: i
call interaction_get_unstable_particle (eval%interaction_t, flv, p, i)
end subroutine evaluator_get_unstable_particle

```

11.3.6 Creating an evaluator: identity

The identity evaluator creates a copy of the first input evaluator; the second input is not used.

All particles link back to the input evaluator and the internal relations are copied. As evaluation does take a shortcut by cloning the matrix elements, the pairing array is not used and does not have to be set up.

```

(Evaluators: evaluator: TBP)+≡
  procedure :: init_identity => evaluator_init_identity

(Evaluators: procedures)+≡
  subroutine evaluator_init_identity (eval, int)
    class(evaluator_t), intent(out), target :: eval
    class(interaction_t), intent(in), target :: int
    integer :: n_in, n_out, n_vir, n_tot
    integer :: i
    integer, dimension(:), allocatable :: map
    type(state_matrix_t), pointer :: state
    type(state_iterator_t) :: it

    eval%type = EVAL_IDENTITY
    eval%int_in1 => int
    nullify (eval%int_in2)
    n_in = int%get_n_in ()
    n_out = int%get_n_out ()
    n_vir = int%get_n_vir ()
    n_tot = int%get_n_tot ()
    call eval%interaction_t%basic_init (n_in, n_vir, n_out, &
      mask=int%get_mask (), &
      resonant=int%get_resonance_flags ())
    do i = 1, n_tot
      call eval%set_source_link (i, int, i)
    end do
    allocate (map(n_tot))
    map = [(i, i = 1, n_tot)]
    call int%transfer_relations (eval, map)
    state => int%get_state_matrix_ptr ()
    call it%init (state)
    do while (it%is_valid ())
      call eval%add_state (it%get_quantum_numbers (), &
        it%get_me_index ())
      call it%advance ()
    end do
    call eval%freeze ()
  end subroutine evaluator_init_identity

```

```
end subroutine evaluator_init_identity
```

11.3.7 Creating an evaluator: quantum number sum

This evaluator operates on the diagonal of a density matrix and sums over the quantum numbers specified by the mask. The optional argument **drop** allows to drop a particle from the resulting density matrix. The handling of virtuals is not completely sane, especially in connection with dropping particles.

When summing over matrix element entries, we keep the separation into entries and normalization (in the corresponding evaluation routine below).

(Evaluators: evaluator: TBP)+≡

```
procedure :: init_qn_sum => evaluator_init_qn_sum
```

(Evaluators: procedures)+≡

```
subroutine evaluator_init_qn_sum (eval, int, qn_mask, drop)
  class(evaluator_t), intent(out), target :: eval
  class(interaction_t), target, intent(in) :: int
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
  logical, intent(in), optional, dimension(:) :: drop
  type(state_iterator_t) :: it_old, it_new
  integer, dimension(:,:), allocatable :: pairing_proto
  integer, dimension(:), allocatable :: pairing_sizes
  integer, dimension(:), allocatable :: map
  integer :: n_in, n_out, n_vir, n_tot, n_me_old, n_me_new
  integer :: i, j
  type(state_matrix_t), pointer :: state_new, state_old
  type(quantum_numbers_t), dimension(:), allocatable :: qn
  logical :: matched
  logical, dimension(size (qn_mask)) :: dropped
  integer :: ndropped
  integer, dimension(:), allocatable :: inotdropped
  type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
  logical, dimension(:), allocatable :: resonant

  eval%type = EVAL_QN_SUM
  eval%int_in1 => int
  nullify (eval%int_in2)
  if (present (drop)) then
    dropped = drop
  else
    dropped = .false.
  end if
  ndropped = count (dropped)

  n_in = int%get_n_in ()
  n_out = int%get_n_out () - ndropped
  n_vir = int%get_n_vir ()
  n_tot = int%get_n_tot () - ndropped

  allocate (inotdropped (n_tot))
  i = 1
  do j = 1, n_tot + ndropped
```

```

        if (dropped (j)) cycle
        inotdropped(i) = j
        i = i + 1
    end do

    allocate (mask(n_tot + ndropped))
    mask = int%get_mask ()
    allocate (resonant(n_tot + ndropped))
    resonant = int%get_resonance_flags ()
    call eval%interaction_t%basic_init (n_in, n_vir, n_out, &
        mask = mask(inotdropped) .or. qn_mask(inotdropped), &
        resonant = resonant(inotdropped))
    i = 1
    do j = 1, n_tot + ndropped
        if (dropped(j)) cycle
        call eval%set_source_link (i, int, j)
        i = i + 1
    end do
    allocate (map(n_tot + ndropped))
    i = 1
    do j = 1, n_tot + ndropped
        if (dropped (j)) then
            map(j) = 0
        else
            map(j) = i
            i = i + 1
        end if
    end do
    call int%transfer_relations (eval, map)

    n_me_old = int%get_n_matrix_elements ()
    allocate (pairing_proto(n_me_old, n_me_old))
    allocate (pairing_sizes(n_me_old))
    pairing_sizes = 0
    state_old => int%get_state_matrix_ptr ()
    state_new => eval%get_state_matrix_ptr ()
    call it_old%init (state_old)
    allocate (qn(n_tot + ndropped))
    do while (it_old%is_valid ())
        qn = it_old%get_quantum_numbers ()
        if (.not. all (qn%are_diagonal ())) then
            call it_old%advance ()
            cycle
        end if
        matched = .false.
        call it_new%init (state_new)
        if (eval%get_n_matrix_elements () > 0) then
            do while (it_new%is_valid ())
                if (all (qn(inotdropped) .match. &
                    it_new%get_quantum_numbers ())) &
                then
                    matched = .true.
                    i = it_new%get_me_index ()
                    exit
                end if
            end do
        end if
    end do

```

```

        end if
        call it_new%advance ()
    end do
end if
if (.not. matched) then
    call eval%add_state (qn(inotdropped))
    i = eval%get_n_matrix_elements ()
end if
pairing_sizes(i) = pairing_sizes(i) + 1
pairing_proto(pairing_sizes(i), i) = it_old%get_me_index ()
! print *, &                                     !!! Debugging
!      i, pairing_sizes(i), it_old%get_me_index ()
call it_old%advance ()
end do
call eval%freeze ()

n_me_new = eval%get_n_matrix_elements ()
allocate (eval%pairing_array(n_me_new))
do i = 1, n_me_new
    ! print *, i, pairing_sizes(i)                !!! Debugging
    call pairing_array_init (eval%pairing_array(i), &
        pairing_sizes(i), .false., .false.)
    eval%pairing_array(i)%i1 = pairing_proto(:pairing_sizes(i), i)
end do

end subroutine evaluator_init_qn_sum

```

11.3.8 Evaluation

When the input interactions (which are pointed to in the pairings stored within the evaluator) are filled with values, we can activate the evaluator, i.e., calculate the result values which are stored in the interaction.

The evaluation of matrix elements can be done in parallel. A `forall` construct is not appropriate, however. We would need `do concurrent` here. Nevertheless, the evaluation functions are marked as `pure`.

```

<Evaluators: evaluator: TBP>+≡
    procedure :: evaluate => evaluator_evaluate

<Evaluators: procedures>+≡
    subroutine evaluator_evaluate (eval)
        class(evaluator_t), intent(inout), target :: eval
        integer :: i
        select case (eval%type)
        case (EVAL_PRODUCT)
            do i = 1, size(eval%pairing_array)
                call eval%evaluate_product (i, &
                    eval%int_in1, eval%int_in2, &
                    eval%pairing_array(i)%i1, eval%pairing_array(i)%i2)
            end do
        case (EVAL_SQUARE_WITH_COLOR_FACTORS)
            do i = 1, size(eval%pairing_array)
                call eval%evaluate_product_cf (i, &

```

```

        eval%int_in1, eval%int_in1, &
        eval%pairing_array(i)%i1, eval%pairing_array(i)%i2, &
        eval%pairing_array(i)%factor)
    end do
case (EVAL_SQUARED_FLOWS)
    do i = 1, size(eval%pairing_array)
        call eval%evaluate_square_c (i, &
            eval%int_in1, &
            eval%pairing_array(i)%i1)
    end do
case (EVAL_COLOR_CONTRACTION)
    do i = 1, size(eval%pairing_array)
        call eval%evaluate_sum (i, &
            eval%int_in1, &
            eval%pairing_array(i)%i1)
    end do
case (EVAL_IDENTITY)
    call eval%set_matrix_element (eval%int_in1)
case (EVAL_QN_SUM)
    do i = 1, size (eval%pairing_array)
        call eval%evaluate_me_sum (i, &
            eval%int_in1, eval%pairing_array(i)%i1)
        call eval%set_norm (eval%int_in1%get_norm ())
    end do
end select
end subroutine evaluator_evaluate

```

11.3.9 Unit tests

Test: Create two interactions. The interactions are twofold connected. The first connection has a helicity index that is kept, the second connection has a helicity index that is summed over. Concatenate the interactions in an evaluator, which thus contains a result interaction. Fill the input interactions with values, activate the evaluator and print the result.

```

<Evaluators: public>+≡
    public :: evaluator_test

<Evaluators: procedures>+≡
    subroutine evaluator_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Evaluators: execute tests>
    end subroutine evaluator_test

<Evaluators: execute tests>≡
    call test (evaluator_1, "evaluator_1", &
        "check evaluators (1)", &
        u, results)

<Evaluators: tests>≡
    subroutine evaluator_1 (u)
        integer, intent(in) :: u
        type(model_data_t), target :: model

```

```

type(interaction_t), target :: int_qqtt, int_tbw, int1, int2
type(flavor_t), dimension(:), allocatable :: flv
type(color_t), dimension(:), allocatable :: col
type(helicity_t), dimension(:), allocatable :: hel
type(quantum_numbers_t), dimension(:), allocatable :: qn
integer :: f, c, h1, h2, h3
type(vector4_t), dimension(4) :: p
type(vector4_t), dimension(2) :: q
type(quantum_numbers_mask_t) :: qn_mask_conn
type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask2
type(evaluator_t), target :: eval, eval2, eval3

call model%init_sm_test ()

write (u, "(A)")  "*** Evaluator for matrix product"
write (u, "(A)")  "***   Construct interaction for qq -> tt"
write (u, "(A)")
call int_qqtt%basic_init (2, 0, 2, set_relations=.true.)
allocate (flv (4), col (4), hel (4), qn (4))
allocate (qn_mask2 (4))
do c = 1, 2
  select case (c)
  case (1)
    call col%init_col_acl ([1, 0, 1, 0], [0, 2, 0, 2])
  case (2)
    call col%init_col_acl ([1, 0, 2, 0], [0, 1, 0, 2])
  end select
do f = 1, 2
  call flv%init ([f, -f, 6, -6], model)
do h1 = -1, 1, 2
  call hel(3)%init (h1)
do h2 = -1, 1, 2
  call hel(4)%init (h2)
  call qn%init (flv, col, hel)
  call int_qqtt%add_state (qn)
end do
end do
end do
call int_qqtt%freeze ()
deallocate (flv, col, hel, qn)
write (u, "(A)")  "***   Construct interaction for t -> bW"
call int_tbw%basic_init (1, 0, 2, set_relations=.true.)
allocate (flv (3), col (3), hel (3), qn (3))
call flv%init ([6, 5, 24], model)
call col%init_col_acl ([1, 1, 0], [0, 0, 0])
do h1 = -1, 1, 2
  call hel(1)%init (h1)
do h2 = -1, 1, 2
  call hel(2)%init (h2)
do h3 = -1, 1
  call hel(3)%init (h3)
  call qn%init (flv, col, hel)
  call int_tbw%add_state (qn)

```

```

        end do
    end do
end do
call int_tbw%freeze ()
deallocate (flv, col, hel, qn)
write (u, "(A)")  "***  Link interactions"
call int_tbw%set_source_link (1, int_qqtt, 3)
qn_mask_conn = quantum_numbers_mask (.false.,.false.,.true.)
write (u, "(A)")
write (u, "(A)")  "***  Show input"
call int_qqtt%basic_write (unit = u)
write (u, "(A)")
call int_tbw%basic_write (unit = u)
write (u, "(A)")
write (u, "(A)")  "***  Evaluate product"
call eval%init_product (int_qqtt, int_tbw, qn_mask_conn)
call eval%write (unit = u)

call int1%basic_init (2, 0, 2, set_relations=.true.)
call int2%basic_init (1, 0, 2, set_relations=.true.)
p(1) = vector4_moving (1000._default, 1000._default, 3)
p(2) = vector4_moving (200._default, 200._default, 2)
p(3) = vector4_moving (100._default, 200._default, 1)
p(4) = p(1) - p(2) - p(3)
call int1%set_momenta (p)
q(1) = vector4_moving (50._default,-50._default, 3)
q(2) = p(2) + p(4) - q(1)
call int2%set_momenta (q, outgoing=.true.)
call int1%set_matrix_element ([[2._default,0._default), &
    (4._default,1._default), (-3._default,0._default)])
call int2%set_matrix_element ([(-3._default,0._default), &
    (0._default,1._default), (1._default,2._default)])
call eval%receive_momenta ()
call eval%evaluate ()
call int1%basic_write (unit = u)
write (u, "(A)")
call int2%basic_write (unit = u)
write (u, "(A)")
call eval%write (unit = u)
write (u, "(A)")
call int1%final ()
call int2%final ()
call eval%final ()

write (u, "(A)")
write (u, "(A)")  "*** Evaluator for matrix square"
allocate (flv(4), col(4), qn(4))
call int1%basic_init (2, 0, 2, set_relations=.true.)
call flv%init ([1, -1, 21, 21], model)
call col(1)%init ([1])
call col(2)%init ([-2])
call col(3)%init ([2, -3])
call col(4)%init ([3, -1])
call qn%init (flv, col)

```

```

call int1%add_state (qn)
call col(3)%init ([3, -1])
call col(4)%init ([2, -3])
call qn%init (flv, col)
call int1%add_state (qn)
call col(3)%init ([2, -1])
call col(4)%init (.true.)
call qn%init (flv, col)
call int1%add_state (qn)
call int1%freeze ()
! [qn_mask2 not set since default is false]
call eval%init_square (int1, qn_mask2, nc=3)
call eval2%init_square_nondiag (int1, qn_mask2)
qn_mask2 = quantum_numbers_mask (.false., .true., .true.)
call eval3%init_square_diag (eval, qn_mask2)
call int1%set_matrix_element &
    [(2._default,0._default), &
     (4._default,1._default), (-3._default,0._default)])
call int1%set_momenta (p)
call int1%basic_write (unit = u)
write (u, "(A)")
call eval%receive_momenta ()
call eval%evaluate ()
call eval%write (unit = u)
write (u, "(A)")
call eval2%receive_momenta ()
call eval2%evaluate ()
call eval2%write (unit = u)
write (u, "(A)")
call eval3%receive_momenta ()
call eval3%evaluate ()
call eval3%write (unit = u)
call int1%final ()
call eval%final ()
call eval2%final ()
call eval3%final ()

call model%final ()
end subroutine evaluator_1

```

```

<Evaluators: execute tests>+≡
call test (evaluator_2, "evaluator_2", &
    "check evaluators (2)", &
    u, results)

```

```

<Evaluators: tests>+≡
subroutine evaluator_2 (u)
integer, intent(in) :: u
type(model_data_t), target :: model
type(interaction_t), target :: int
integer :: h1, h2, h3, h4
type(helicity_t), dimension(4) :: hel
type(color_t), dimension(4) :: col
type(flavor_t), dimension(4) :: flv

```



```

type(quantum_numbers_t), dimension(4) :: qn
type(vector4_t), dimension(4) :: p
type(evaluator_t) :: eval
integer :: i

call model%init_sm_test ()

write (u, "(A)") "*** Creating interaction for e+ e- -> W+ W-"
write (u, "(A)")

call flv%init ([11, -11, 24, -24], model)
do i = 1, 4
    call col(i)%init ()
end do
call int%basic_init (2, 0, 2, set_relations=.true.)
do h1 = -1, 1, 2
    call hel(1)%init (h1)
    do h2 = -1, 1, 2
        call hel(2)%init (h2)
        do h3 = -1, 1
            call hel(3)%init (h3)
            do h4 = -1, 1
                call hel(4)%init (h4)
                call qn%init (flv, col, hel)
                call int%add_state (qn)
            end do
        end do
    end do
end do
call int%freeze ()
call int%set_matrix_element &
    ([cplx (i, kind=default), i = 1, 36])
p(1) = vector4_moving (1000._default, 1000._default, 3)
p(2) = vector4_moving (1000._default, -1000._default, 3)
p(3) = vector4_moving (1000._default, &
    sqrt (1E6_default - 80._default**2), 3)
p(4) = p(1) + p(2) - p(3)
call int%set_momenta (p)
write (u, "(A)") "*** Setting up evaluator"
write (u, "(A)")

call eval%init_identity (int)
write (u, "(A)") "*** Transferring momenta and evaluating"
write (u, "(A)")

call eval%receive_momenta ()
call eval%evaluate ()
write (u, "(A)") "*****"
write (u, "(A)") "    Interaction dump"
write (u, "(A)") "*****"
call int%basic_write (unit = u)
write (u, "(A)")
write (u, "(A)") "*****"
write (u, "(A)") "    Evaluator dump"

```

```

write (u, "(A)") "*****"
call eval%write (unit = u)
write (u, "(A)")
write (u, "(A)") "*** cleaning up"
call int%final ()
call eval%final ()

call model%final ()
end subroutine evaluator_2

```

```

<Evaluators: execute tests>+≡
call test (evaluator_3, "evaluator_3", &
  "check evaluators (3)", &
  u, results)

```

```

<Evaluators: tests>+≡
subroutine evaluator_3 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(interaction_t), target :: int
  integer :: h1, h2, h3, h4
  type(helicity_t), dimension(4) :: hel
  type(color_t), dimension(4) :: col
  type(flavor_t), dimension(4) :: flv1, flv2
  type(quantum_numbers_t), dimension(4) :: qn
  type(vector4_t), dimension(4) :: p
  type(evaluator_t) :: eval1, eval2, eval3
  type(quantum_numbers_mask_t), dimension(4) :: qn_mask
  integer :: i

  call model%init_sm_test ()

  write (u, "(A)") "*** Creating interaction for e+/mu+ e-/mu- -> W+ W-"
  call flv1%init ([11, -11, 24, -24], model)
  call flv2%init ([13, -13, 24, -24], model)
  do i = 1, 4
    call col (i)%init ()
  end do
  call int%basic_init (2, 0, 2, set_relations=.true.)
  do h1 = -1, 1, 2
    call hel(1)%init (h1)
    do h2 = -1, 1, 2
      call hel(2)%init (h2)
      do h3 = -1, 1
        call hel(3)%init (h3)
        do h4 = -1, 1
          call hel(4)%init (h4)
          call qn%init (flv1, col, hel)
          call int%add_state (qn)
          call qn%init (flv2, col, hel)
          call int%add_state (qn)
        end do
      end do
    end do
  end do
end do
end do

```

```

end do
call int%freeze ()
call int%set_matrix_element &
    ([[cplx (1, kind=default), i = 1, 72]])
p(1) = vector4_moving (1000._default, 1000._default, 3)
p(2) = vector4_moving (1000._default, -1000._default, 3)
p(3) = vector4_moving (1000._default, &
    sqrt (1E6_default - 80._default**2), 3)
p(4) = p(1) + p(2) - p(3)
call int%set_momenta (p)
write (u, "(A)")  "*** Setting up evaluators"
call qn_mask%init (.false., .true., .true.)
call eval1%init_qn_sum (int, qn_mask)
call qn_mask%init (.true., .true., .true.)
call eval2%init_qn_sum (int, qn_mask)
call qn_mask%init (.false., .true., .false.)
call eval3%init_qn_sum (int, qn_mask, &
    [.false., .false., .false., .true.])
write (u, "(A)")  "*** Transferring momenta and evaluating"
call eval1%receive_momenta ()
call eval1%evaluate ()
call eval2%receive_momenta ()
call eval2%evaluate ()
call eval3%receive_momenta ()
call eval3%evaluate ()
write (u, "(A)")  "*****"
write (u, "(A)")  "    Interaction dump"
write (u, "(A)")  "*****"
call int%basic_write (unit = u)
write (u, "(A)")
write (u, "(A)")  "*****"
write (u, "(A)")  "    Evaluator dump --- spin sum"
write (u, "(A)")  "*****"
call eval1%write (unit = u)
call eval1%basic_write (unit = u)
write (u, "(A)")  "*****"
write (u, "(A)")  "    Evaluator dump --- spin / flavor sum"
write (u, "(A)")  "*****"
call eval2%write (unit = u)
call eval2%basic_write (unit = u)
write (u, "(A)")  "*****"
write (u, "(A)")  "    Evaluator dump --- flavor sum, drop last W"
write (u, "(A)")  "*****"
call eval3%write (unit = u)
call eval3%basic_write (unit = u)
write (u, "(A)")
write (u, "(A)")  "*** cleaning up"
call int%final ()
call eval1%final ()
call eval2%final ()
call eval3%final ()

call model%final ()
end subroutine evaluator_3

```

This test evaluates a product with different quantum-number masks and filters for the linked entry.

```

(Evaluators: execute tests)+≡
    call test (evaluator_4, "evaluator_4", &
               "check evaluator product with filter", &
               u, results)

(Evaluators: tests)+≡
    subroutine evaluator_4 (u)
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(interaction_t), target :: int1, int2
        integer :: h1, h2, h3
        type(helicity_t), dimension(3) :: hel
        type(color_t), dimension(3) :: col
        type(flavor_t), dimension(2) :: flv1, flv2
        type(flavor_t), dimension(3) :: flv3, flv4
        type(quantum_numbers_t), dimension(3) :: qn
        type(evaluator_t) :: eval1, eval2, eval3, eval4
        type(quantum_numbers_mask_t) :: qn_mask
        type(flavor_t) :: flv_filter
        type(helicity_t) :: hel_filter
        type(color_t) :: col_filter
        type(quantum_numbers_t) :: qn_filter
        integer :: i

        write (u, "(A)")  "* Test output: evaluator_4"
        write (u, "(A)")  "* Purpose: test evaluator products &
                           &with mask and filter"
        write (u, "(A)")

        call model%init_sm_test ()

        write (u, "(A)")  "* Creating interaction for e- -> W+/Z"
        write (u, "(A)")

        call flv1%init ([11, 24], model)
        call flv2%init ([11, 23], model)
        do i = 1, 3
            call col(i)%init ()
        end do
        call int1%basic_init (1, 0, 1, set_relations=.true.)
        do h1 = -1, 1, 2
            call hel(1)%init (h1)
            do h2 = -1, 1
                call hel(2)%init (h2)
                call qn(:2)%init (flv1, col(:2), hel(:2))
                call int1%add_state (qn(:2))
                call qn(:2)%init (flv2, col(:2), hel(:2))
                call int1%add_state (qn(:2))
            end do
        end do
        call int1%freeze ()
    end subroutine evaluator_4

```

```

call int1%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Creating interaction for W+/Z -> u ubar/dbar"
write (u, "(A)")

call flv3%init ([24, 2, -1], model)
call flv4%init ([23, 2, -2], model)

call int2%basic_init (1, 0, 2, set_relations=.true.)
do h1 = -1, 1
  call hel(1)%init (h1)
  do h2 = -1, 1, 2
    call hel(2)%init (h2)
    do h3 = -1, 1, 2
      call hel(3)%init (h3)
      call qn(:3)%init (flv3, col(:3), hel(:3))
      call int2%add_state (qn(:3))
      call qn(:3)%init (flv4, col(:3), hel(:3))
      call int2%add_state (qn(:3))
    end do
  end do
end do
call int2%freeze ()

call int2%set_source_link (1, int1, 2)
call int2%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Product evaluator"
write (u, "(A)")

call qn_mask%init (.false., .false., .false.)
call eval1%init_product (int1, int2, qn_mask_conn = qn_mask)
call eval1%write (u)

write (u, "(A)")
write (u, "(A)")  "* Product evaluator with helicity mask"
write (u, "(A)")

call qn_mask%init (.false., .false., .true.)
call eval2%init_product (int1, int2, qn_mask_conn = qn_mask)
call eval2%write (u)

write (u, "(A)")
write (u, "(A)")  "* Product with flavor filter and helicity mask"
write (u, "(A)")

call qn_mask%init (.false., .false., .true.)
call flv_filter%init (24, model)
call hel_filter%init ()
call col_filter%init ()
call qn_filter%init (flv_filter, col_filter, hel_filter)
call eval3%init_product (int1, int2, &

```

```

        qn_mask_conn = qn_mask, qn_filter_conn = qn_filter)
call eval3%write (u)

write (u, "(A)")
write (u, "(A)")  "* Product with helicity filter and mask"
write (u, "(A)")

call qn_mask%init (.false., .false., .true.)
call flv_filter%init ()
call hel_filter%init (0)
call col_filter%init ()
call qn_filter%init (flv_filter, col_filter, hel_filter)
call eval4%init_product (int1, int2, &
        qn_mask_conn = qn_mask, qn_filter_conn = qn_filter)
call eval4%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eval1%final ()
call eval2%final ()
call eval3%final ()
call eval4%final ()

call int1%final ()
call int2%final ()

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: evaluator_4"

end subroutine evaluator_4

```

Chapter 12

Sindarin Built-In Types

Here, we define a couple of types and objects which are useful both internally for WHIZARD, and visible to the user, so they correspond to Sindarin types.

particle_specifiers Expressions for particles and particle alternatives, involving particle names.

pdg_arrays Integer (PDG) codes for particles. Useful for particle aliases (e.g., 'quark' for u, d, s etc.).

jets Define (pseudo)jets as objects. Functional only if the **fastjet** library is linked. (This may change in the future.)

subevents Particle collections built from event records, for use in analysis and other Sindarin expressions

analysis Observables, histograms, and plots.

12.1 Particle Specifiers

In this module we introduce a type for specifying a particle or particle alternative. In addition to the particle specifiers (strings separated by colons), the type contains an optional flag **polarized** and a string **decay**. If the **polarized** flag is set, particle polarization information should be kept when generating events for this process. If the **decay** string is set, it is the ID of a decay process which should be applied to this particle when generating events.

In input/output form, the **polarized** flag is indicated by an asterisk (*) in brackets, and the **decay** is indicated by its ID in brackets.

The **read** and **write** procedures in this module are not type-bound but generic procedures which handle scalar and array arguments.

```
<particle_specifiers.f90>≡  
<File header>
```

```
module particle_specifiers
```

```
<Use strings>
```

```
  use io_units
```

```
  use unit_tests
```

```

    use diagnostics

    <Standard module head>

    <Particle specifiers: public>

    <Particle specifiers: types>

    <Particle specifiers: interfaces>

contains

    <Particle specifiers: procedures>

    <Particle specifiers: tests>

end module particle_specifiers

```

12.1.1 Base type

This is an abstract type which can hold a single particle or an expression.

```

<Particle specifiers: types>≡
    type, abstract :: prt_spec_expr_t
    contains
    <Particle specifiers: prt spec expr: TBP>
end type prt_spec_expr_t

```

Output, as a string.

```

<Particle specifiers: prt spec expr: TBP>≡
    procedure (prt_spec_expr_to_string), deferred :: to_string

<Particle specifiers: interfaces>≡
    abstract interface
        function prt_spec_expr_to_string (object) result (string)
            import
            class(prt_spec_expr_t), intent(in) :: object
            type(string_t) :: string
        end function prt_spec_expr_to_string
    end interface

```

Call an `expand` method for all enclosed subexpressions (before handling the current expression).

```

<Particle specifiers: prt spec expr: TBP>+≡
    procedure (prt_spec_expr_expand_sub), deferred :: expand_sub

<Particle specifiers: interfaces>+≡
    abstract interface
        subroutine prt_spec_expr_expand_sub (object)
            import
            class(prt_spec_expr_t), intent(inout) :: object
        end subroutine prt_spec_expr_expand_sub
    end interface

```


12.1.2 Wrapper type

This wrapper can hold a particle expression of any kind. We need it so we can make variadic arrays.

```
<Particle specifiers: public>≡
    public :: prt_expr_t
<Particle specifiers: types>+≡
    type :: prt_expr_t
        class(prt_spec_expr_t), allocatable :: x
        contains
        <Particle specifiers: prt expr: TBP>
    end type prt_expr_t
```

Output as a string: delegate.

```
<Particle specifiers: prt expr: TBP>≡
    procedure :: to_string => prt_expr_to_string
<Particle specifiers: procedures>≡
    recursive function prt_expr_to_string (object) result (string)
        class(prt_expr_t), intent(in) :: object
        type(string_t) :: string
        if (allocated (object%x)) then
            string = object%x%to_string ()
        else
            string = ""
        end if
    end function prt_expr_to_string
```

Allocate the expression as a particle specifier and copy the value.

```
<Particle specifiers: prt expr: TBP>+≡
    procedure :: init_spec => prt_expr_init_spec
<Particle specifiers: procedures>+≡
    subroutine prt_expr_init_spec (object, spec)
        class(prt_expr_t), intent(out) :: object
        type(prt_spec_t), intent(in) :: spec
        allocate (prt_spec_t :: object%x)
        select type (x => object%x)
        type is (prt_spec_t)
            x = spec
        end select
    end subroutine prt_expr_init_spec
```

Allocate as a list/sum and allocate for a given length

```
<Particle specifiers: prt expr: TBP>+≡
    procedure :: init_list => prt_expr_init_list
    procedure :: init_sum => prt_expr_init_sum
<Particle specifiers: procedures>+≡
    subroutine prt_expr_init_list (object, n)
        class(prt_expr_t), intent(out) :: object
        integer, intent(in) :: n
        allocate (prt_spec_list_t :: object%x)
```

```

        select type (x => object%x)
        type is (prt_spec_list_t)
            allocate (x%expr (n))
        end select
    end subroutine prt_expr_init_list

    subroutine prt_expr_init_sum (object, n)
        class(prt_expr_t), intent(out) :: object
        integer, intent(in) :: n
        allocate (prt_spec_sum_t :: object%x)
        select type (x => object%x)
        type is (prt_spec_sum_t)
            allocate (x%expr (n))
        end select
    end subroutine prt_expr_init_sum

```

Return the number of terms. This is unity, except if the expression is a sum.

```

<Particle specifiers: prt expr: TBP>+≡
    procedure :: get_n_terms => prt_expr_get_n_terms

<Particle specifiers: procedures>+≡
    function prt_expr_get_n_terms (object) result (n)
        class(prt_expr_t), intent(in) :: object
        integer :: n
        if (allocated (object%x)) then
            select type (x => object%x)
            type is (prt_spec_sum_t)
                n = size (x%expr)
            class default
                n = 1
            end select
        else
            n = 0
        end if
    end function prt_expr_get_n_terms

```

Transform one of the terms, as returned by the previous method, to an array of particle specifiers. The array has more than one entry if the selected term is a list. This makes sense only if the expression has been completely expanded, so the list contains only atoms.

```

<Particle specifiers: prt expr: TBP>+≡
    procedure :: term_to_array => prt_expr_term_to_array

<Particle specifiers: procedures>+≡
    recursive subroutine prt_expr_term_to_array (object, array, i)
        class(prt_expr_t), intent(in) :: object
        type(prt_spec_t), dimension(:), intent(inout), allocatable :: array
        integer, intent(in) :: i
        integer :: j
        if (allocated (array)) deallocate (array)
        select type (x => object%x)
        type is (prt_spec_t)
            allocate (array (1))
            array(1) = x

```

```

type is (prt_spec_list_t)
  allocate (array (size (x%expr)))
  do j = 1, size (array)
    select type (y => x%expr(j)%x)
      type is (prt_spec_t)
        array(j) = y
      end select
    end do
  type is (prt_spec_sum_t)
    call x%expr(i)%term_to_array (array, 1)
  end select
end subroutine prt_expr_term_to_array

```

12.1.3 The atomic type

The trivial case is a single particle, including optional decay and polarization attributes.

Definition

The particle is unstable if the **decay** array is allocated. The **polarized** flag and decays may not be set simultaneously.

```

<Particle specifiers: public>+≡
  public :: prt_spec_t

<Particle specifiers: types>+≡
  type, extends (prt_spec_expr_t) :: prt_spec_t
    private
    type(string_t) :: name
    logical :: polarized = .false.
    type(string_t), dimension(:), allocatable :: decay
  contains
    <Particle specifiers: prt spec: TBP>
  end type prt_spec_t

```

I/O

Output. Old-style subroutines.

```

<Particle specifiers: public>+≡
  public :: prt_spec_write

<Particle specifiers: interfaces>+≡
  interface prt_spec_write
    module procedure prt_spec_write1
    module procedure prt_spec_write2
  end interface prt_spec_write

<Particle specifiers: procedures>+≡
  subroutine prt_spec_write1 (object, unit, advance)
    type(prt_spec_t), intent(in) :: object
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: advance

```

```

character(3) :: adv
integer :: u
u = given_output_unit (unit)
adv = "yes"; if (present (advance)) adv = advance
write (u, "(A)", advance = adv) char (object%to_string ())
end subroutine prt_spec_write1

```

Write an array as a list of particle specifiers.

```

<Particle specifiers: procedures>+≡
subroutine prt_spec_write2 (prt_spec, unit, advance)
  type(prt_spec_t), dimension(:), intent(in) :: prt_spec
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: advance
  character(3) :: adv
  integer :: u, i
  u = given_output_unit (unit)
  adv = "yes"; if (present (advance)) adv = advance
  do i = 1, size (prt_spec)
    if (i > 1) write (u, "(A)", advance="no") " ", "
    call prt_spec_write (prt_spec(i), u, advance="no")
  end do
  write (u, "(A)", advance = adv)
end subroutine prt_spec_write2

```

Read. Input may be string or array of strings.

```

<Particle specifiers: public>+≡
public :: prt_spec_read

<Particle specifiers: interfaces>+≡
interface prt_spec_read
  module procedure prt_spec_read1
  module procedure prt_spec_read2
end interface prt_spec_read

```

Read a single particle specifier

```

<Particle specifiers: procedures>+≡
pure subroutine prt_spec_read1 (prt_spec, string)
  type(prt_spec_t), intent(out) :: prt_spec
  type(string_t), intent(in) :: string
  type(string_t) :: arg, buffer
  integer :: b1, b2, c, n, i
  b1 = scan (string, "(")
  b2 = scan (string, ")")
  if (b1 == 0) then
    prt_spec%name = trim (adjustl (string))
  else
    prt_spec%name = trim (adjustl (extract (string, 1, b1-1)))
    arg = trim (adjustl (extract (string, b1+1, b2-1)))
    if (arg == "*") then
      prt_spec%polarized = .true.
    else
      n = 0
      buffer = arg
      do

```

```

        if (verify (buffer, " ") == 0) exit
        n = n + 1
        c = scan (buffer, "+")
        if (c == 0) exit
        buffer = extract (buffer, c+1)
    end do
    allocate (prt_spec%decay (n))
    buffer = arg
    do i = 1, n
        c = scan (buffer, "+")
        if (c == 0) c = len (buffer) + 1
        prt_spec%decay(i) = trim (adjustl (extract (buffer, 1, c-1)))
        buffer = extract (buffer, c+1)
    end do
end if
end if
end subroutine prt_spec_read1

```

Read a particle specifier array, given as a single string. The array is allocated to the correct size.

(Particle specifiers: procedures)+≡

```

pure subroutine prt_spec_read2 (prt_spec, string)
    type(prt_spec_t), dimension(:), intent(out), allocatable :: prt_spec
    type(string_t), intent(in) :: string
    type(string_t) :: buffer
    integer :: c, i, n
    n = 0
    buffer = string
    do
        n = n + 1
        c = scan (buffer, ",")
        if (c == 0) exit
        buffer = extract (buffer, c+1)
    end do
    allocate (prt_spec (n))
    buffer = string
    do i = 1, size (prt_spec)
        c = scan (buffer, ",")
        if (c == 0) c = len (buffer) + 1
        call prt_spec_read (prt_spec(i), &
            trim (adjustl (extract (buffer, 1, c-1))))
        buffer = extract (buffer, c+1)
    end do
end subroutine prt_spec_read2

```

Constructor

Initialize a particle specifier.

(Particle specifiers: public)+≡

```
public :: new_prt_spec
```

(Particle specifiers: interfaces)+≡

```

interface new_prt_spec
  module procedure new_prt_spec
  module procedure new_prt_spec_polarized
  module procedure new_prt_spec_unstable
end interface new_prt_spec

<Particle specifiers: procedures>+≡
elemental function new_prt_spec (name) result (prt_spec)
  type(string_t), intent(in) :: name
  type(prt_spec_t) :: prt_spec
  prt_spec%name = name
end function new_prt_spec

elemental function new_prt_spec_polarized (name, polarized) result (prt_spec)
  type(string_t), intent(in) :: name
  logical, intent(in) :: polarized
  type(prt_spec_t) :: prt_spec
  prt_spec%name = name
  prt_spec%polarized = polarized
end function new_prt_spec_polarized

pure function new_prt_spec_unstable (name, decay) result (prt_spec)
  type(string_t), intent(in) :: name
  type(string_t), dimension(:), intent(in) :: decay
  type(prt_spec_t) :: prt_spec
  prt_spec%name = name
  allocate (prt_spec%decay (size (decay)))
  prt_spec%decay = decay
end function new_prt_spec_unstable

```

Access Methods

Return the particle name without qualifiers

```

<Particle specifiers: prt spec: TBP>≡
  procedure :: get_name => prt_spec_get_name

<Particle specifiers: procedures>+≡
  elemental function prt_spec_get_name (prt_spec) result (name)
    class(prt_spec_t), intent(in) :: prt_spec
    type(string_t) :: name
    name = prt_spec%name
  end function prt_spec_get_name

```

Return the name with qualifiers

```

<Particle specifiers: prt spec: TBP>+≡
  procedure :: to_string => prt_spec_to_string

<Particle specifiers: procedures>+≡
  function prt_spec_to_string (object) result (string)
    class(prt_spec_t), intent(in) :: object
    type(string_t) :: string
    integer :: i
    string = object%name
  end function prt_spec_to_string

```

```

if (allocated (object%decay)) then
  string = string // "("
  do i = 1, size (object%decay)
    if (i > 1) string = string // " + "
    string = string // object%decay(i)
  end do
  string = string // ")"
else if (object%polarized) then
  string = string // "(*)"
end if
end function prt_spec_to_string

```

Return the polarization flag

```

⟨Particle specifiers: prt spec: TBP⟩+≡
  procedure :: is_polarized => prt_spec_is_polarized

⟨Particle specifiers: procedures⟩+≡
  elemental function prt_spec_is_polarized (prt_spec) result (flag)
    class(prt_spec_t), intent(in) :: prt_spec
    logical :: flag
    flag = prt_spec%polarized
  end function prt_spec_is_polarized

```

The particle is unstable if there is a decay array.

```

⟨Particle specifiers: prt spec: TBP⟩+≡
  procedure :: is_unstable => prt_spec_is_unstable

⟨Particle specifiers: procedures⟩+≡
  elemental function prt_spec_is_unstable (prt_spec) result (flag)
    class(prt_spec_t), intent(in) :: prt_spec
    logical :: flag
    flag = allocated (prt_spec%decay)
  end function prt_spec_is_unstable

```

Return the number of decay channels

```

⟨Particle specifiers: prt spec: TBP⟩+≡
  procedure :: get_n_decays => prt_spec_get_n_decays

⟨Particle specifiers: procedures⟩+≡
  elemental function prt_spec_get_n_decays (prt_spec) result (n)
    class(prt_spec_t), intent(in) :: prt_spec
    integer :: n
    if (allocated (prt_spec%decay)) then
      n = size (prt_spec%decay)
    else
      n = 0
    end if
  end function prt_spec_get_n_decays

```

Return the decay channels

```

⟨Particle specifiers: prt spec: TBP⟩+≡
  procedure :: get_decays => prt_spec_get_decays

```

```

<Particle specifiers: procedures>+≡
subroutine prt_spec_get_decays (prt_spec, decay)
  class(prt_spec_t), intent(in) :: prt_spec
  type(string_t), dimension(:), allocatable, intent(out) :: decay
  if (allocated (prt_spec%decay)) then
    allocate (decay (size (prt_spec%decay)))
    decay = prt_spec%decay
  else
    allocate (decay (0))
  end if
end subroutine prt_spec_get_decays

```

Miscellaneous

There is nothing to expand here:

```

<Particle specifiers: prt spec: TBP>+≡
  procedure :: expand_sub => prt_spec_expand_sub

<Particle specifiers: procedures>+≡
subroutine prt_spec_expand_sub (object)
  class(prt_spec_t), intent(inout) :: object
end subroutine prt_spec_expand_sub

```

12.1.4 List

A list of particle specifiers, indicating, e.g., the final state of a process.

```

<Particle specifiers: public>+≡
  public :: prt_spec_list_t

<Particle specifiers: types>+≡
  type, extends (prt_spec_expr_t) :: prt_spec_list_t
    type(prt_spec_expr_t), dimension(:), allocatable :: expr
    contains
    <Particle specifiers: prt spec list: TBP>
  end type prt_spec_list_t

```

Output: Concatenate the components. Insert brackets if the component is also a list. The components of the `expr` array, if any, should all be filled.

```

<Particle specifiers: prt spec list: TBP>≡
  procedure :: to_string => prt_spec_list_to_string

<Particle specifiers: procedures>+≡
recursive function prt_spec_list_to_string (object) result (string)
  class(prt_spec_list_t), intent(in) :: object
  type(string_t) :: string
  integer :: i
  string = ""
  if (allocated (object%expr)) then
    do i = 1, size (object%expr)
      if (i > 1) string = string // ", "
      select type (x => object%expr(i)%x)

```



```

        type is (prt_spec_list_t)
        string = string // "(" // x%to_string () // ")"
    class default
        string = string // x%to_string ()
    end select
end do
end if
end function prt_spec_list_to_string

```

Flatten: if there is a subexpression which is also a list, include the components as direct members of the current list.

```

⟨Particle specifiers: prt spec list: TBP⟩+≡
    procedure :: flatten => prt_spec_list_flatten

⟨Particle specifiers: procedures⟩+≡
    subroutine prt_spec_list_flatten (object)
        class(prt_spec_list_t), intent(inout) :: object
        type(prt_expr_t), dimension(:), allocatable :: tmp_expr
        integer :: i, n_flat, i_flat
        n_flat = 0
        do i = 1, size (object%expr)
            select type (y => object%expr(i)%x)
            type is (prt_spec_list_t)
                n_flat = n_flat + size (y%expr)
            class default
                n_flat = n_flat + 1
            end select
        end do
        if (n_flat > size (object%expr)) then
            allocate (tmp_expr (n_flat))
            i_flat = 0
            do i = 1, size (object%expr)
                select type (y => object%expr(i)%x)
                type is (prt_spec_list_t)
                    tmp_expr (i_flat + 1 : i_flat + size (y%expr)) = y%expr
                    i_flat = i_flat + size (y%expr)
                class default
                    tmp_expr (i_flat + 1) = object%expr(i)
                    i_flat = i_flat + 1
                end select
            end do
        end if
        if (allocated (tmp_expr)) &
            call move_alloc (from = tmp_expr, to = object%expr)
    end subroutine prt_spec_list_flatten

```

Convert a list of sums into a sum of lists. (Subexpressions which are not sums are left untouched.)

```

⟨Particle specifiers: procedures⟩+≡
    subroutine distribute_prt_spec_list (object)
        class(prt_spec_expr_t), intent(inout), allocatable :: object
        class(prt_spec_expr_t), allocatable :: new_object
        integer, dimension(:), allocatable :: n, ii

```

```

integer :: k, n_expr, n_terms, i_term
select type (object)
type is (prt_spec_list_t)
  n_expr = size (object%expr)
  allocate (n (n_expr), source = 1)
  allocate (ii (n_expr), source = 1)
  do k = 1, size (object%expr)
    select type (y => object%expr(k)%x)
    type is (prt_spec_sum_t)
      n(k) = size (y%expr)
    end select
  end do
  n_terms = product (n)
  if (n_terms > 1) then
    allocate (prt_spec_sum_t :: new_object)
    select type (new_object)
    type is (prt_spec_sum_t)
      allocate (new_object%expr (n_terms))
      do i_term = 1, n_terms
        allocate (prt_spec_list_t :: new_object%expr(i_term)%x)
        select type (x => new_object%expr(i_term)%x)
        type is (prt_spec_list_t)
          allocate (x%expr (n_expr))
          do k = 1, n_expr
            select type (y => object%expr(k)%x)
            type is (prt_spec_sum_t)
              x%expr(k) = y%expr(ii(k))
            class default
              x%expr(k) = object%expr(k)
            end select
          end do
        end select
        INCR_INDEX: do k = n_expr, 1, -1
          if (ii(k) < n(k)) then
            ii(k) = ii(k) + 1
            exit INCR_INDEX
          else
            ii(k) = 1
          end if
        end do INCR_INDEX
      end do
    end select
  end if
end select
if (allocated (new_object)) call move_alloc (from = new_object, to = object)
end subroutine distribute_prt_spec_list

```

Apply expand to all components of the list.

```

<Particle specifiers: prt spec list: TBP>+≡
  procedure :: expand_sub => prt_spec_list_expand_sub

<Particle specifiers: procedures>+≡
  recursive subroutine prt_spec_list_expand_sub (object)
    class(prt_spec_list_t), intent(inout) :: object

```

```

integer :: i
if (allocated (object%expr)) then
  do i = 1, size (object%expr)
    call object%expr(i)%expand ()
  end do
end if
end subroutine prt_spec_list_expand_sub

```

12.1.5 Sum

A sum of particle specifiers, indicating, e.g., a sum of final states.

```

⟨Particle specifiers: public⟩+≡
  public :: prt_spec_sum_t

⟨Particle specifiers: types⟩+≡
  type, extends (prt_spec_expr_t) :: prt_spec_sum_t
    type(prt_expr_t), dimension(:), allocatable :: expr
  contains
    ⟨Particle specifiers: prt spec sum: TBP⟩
  end type prt_spec_sum_t

```

Output: Concatenate the components. Insert brackets if the component is a list or also a sum. The components of the `expr` array, if any, should all be filled.

```

⟨Particle specifiers: prt spec sum: TBP⟩≡
  procedure :: to_string => prt_spec_sum_to_string

⟨Particle specifiers: procedures⟩+≡
  recursive function prt_spec_sum_to_string (object) result (string)
    class(prt_spec_sum_t), intent(in) :: object
    type(string_t) :: string
    integer :: i
    string = ""
    if (allocated (object%expr)) then
      do i = 1, size (object%expr)
        if (i > 1) string = string // " + "
        select type (x => object%expr(i)%x)
          type is (prt_spec_list_t)
            string = string // "(" // x%to_string () // ")"
          type is (prt_spec_sum_t)
            string = string // "(" // x%to_string () // ")"
          class default
            string = string // x%to_string ()
        end select
      end do
    end if
  end function prt_spec_sum_to_string

```

Flatten: if there is a subexpression which is also a sum, include the components as direct members of the current sum.

This is identical to `prt_spec_list_flatten` above, except for the type.

```

⟨Particle specifiers: prt spec sum: TBP⟩+≡
  procedure :: flatten => prt_spec_sum_flatten

```

<Particle specifiers: procedures>+≡

```

subroutine prt_spec_sum_flatten (object)
  class(prt_spec_sum_t), intent(inout) :: object
  type(prt_expr_t), dimension(:), allocatable :: tmp_expr
  integer :: i, n_flat, i_flat
  n_flat = 0
  do i = 1, size (object%expr)
    select type (y => object%expr(i)%x)
      type is (prt_spec_sum_t)
        n_flat = n_flat + size (y%expr)
      class default
        n_flat = n_flat + 1
    end select
  end do
  if (n_flat > size (object%expr)) then
    allocate (tmp_expr (n_flat))
    i_flat = 0
    do i = 1, size (object%expr)
      select type (y => object%expr(i)%x)
        type is (prt_spec_sum_t)
          tmp_expr (i_flat + 1 : i_flat + size (y%expr)) = y%expr
          i_flat = i_flat + size (y%expr)
        class default
          tmp_expr (i_flat + 1) = object%expr(i)
          i_flat = i_flat + 1
        end select
      end do
    end if
    if (allocated (tmp_expr)) &
      call move_alloc (from = tmp_expr, to = object%expr)
  end subroutine prt_spec_sum_flatten

```

Apply expand to all terms in the sum.

<Particle specifiers: prt spec sum: TBP>+≡

```

procedure :: expand_sub => prt_spec_sum_expand_sub

```

<Particle specifiers: procedures>+≡

```

recursive subroutine prt_spec_sum_expand_sub (object)
  class(prt_spec_sum_t), intent(inout) :: object
  integer :: i
  if (allocated (object%expr)) then
    do i = 1, size (object%expr)
      call object%expr(i)%expand ()
    end do
  end if
end subroutine prt_spec_sum_expand_sub

```

12.1.6 Expression Expansion

The `expand` method transforms each particle specifier expression into a sum of lists, according to the rules

$$a, (b, c) \rightarrow a, b, c \quad (12.1)$$

$$a + (b + c) \rightarrow a + b + c \quad (12.2)$$

$$a, b + c \rightarrow (a, b) + (a, c) \quad (12.3)$$

Note that the precedence of comma and plus are opposite to this expansion, so the parentheses in the final expression are necessary.

We assume that subexpressions are filled, i.e., arrays are allocated.

```

<Particle specifiers: prt expr: TBP>+≡
  procedure :: expand => prt_expr_expand

<Particle specifiers: procedures>+≡
  recursive subroutine prt_expr_expand (expr)
    class(prt_expr_t), intent(inout) :: expr
    if (allocated (expr%x)) then
      call distribute_prt_spec_list (expr%x)
      call expr%x%expand_sub ()
      select type (x => expr%x)
        type is (prt_spec_list_t)
          call x%flatten ()
        type is (prt_spec_sum_t)
          call x%flatten ()
      end select
    end if
  end subroutine prt_expr_expand

```

12.1.7 Test

This is the master for calling self-test procedures.

```

<Particle specifiers: public>+≡
  public :: particle_specifiers_test

<Particle specifiers: tests>≡
  subroutine particle_specifiers_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Particle specifiers: execute tests>
  end subroutine particle_specifiers_test

```

Particle specifier array

Define, read and write an array of particle specifiers.

```

<Particle specifiers: execute tests>≡
  call test (particle_specifiers_1, "particle_specifiers_1", &
    "Handle particle specifiers", &
    u, results)

```

<Particle specifiers: tests>+≡

```

subroutine particle_specifiers_1 (u)
  integer, intent(in) :: u
  type(prt_spec_t), dimension(:), allocatable :: prt_spec
  type(string_t), dimension(:), allocatable :: decay
  type(string_t), dimension(0) :: no_decay
  integer :: i, j

  write (u, "(A)")  "* Test output: particle_specifiers_1"
  write (u, "(A)")  "* Purpose: Read and write a particle specifier array"
  write (u, "(A)")

  allocate (prt_spec (5))
  prt_spec = [ &
    new_prt_spec (var_str ("a")), &
    new_prt_spec (var_str ("b"), .true.), &
    new_prt_spec (var_str ("c"), [var_str ("dec1")]), &
    new_prt_spec (var_str ("d"), [var_str ("dec1"), var_str ("dec2")]), &
    new_prt_spec (var_str ("e"), no_decay) &
  ]
  do i = 1, size (prt_spec)
    write (u, "(A)")  char (prt_spec(i)%to_string ())
  end do
  write (u, "(A)")

  call prt_spec_read (prt_spec, &
    var_str (" a, b( *), c( dec1), d (dec1 + dec2 ), e()"))
  call prt_spec_write (prt_spec, u)

  do i = 1, size (prt_spec)
    write (u, "(A)")
    write (u, "(A,A)")  char (prt_spec(i)%get_name ()), ":"
    write (u, "(A,L1)")  "polarized = ", prt_spec(i)%is_polarized ()
    write (u, "(A,L1)")  "unstable = ", prt_spec(i)%is_unstable ()
    write (u, "(A,I0)")  "n_decays = ", prt_spec(i)%get_n_decays ()
    call prt_spec(i)%get_decays (decay)
    write (u, "(A)", advance="no") "decays   ="
    do j = 1, size (decay)
      write (u, "(ix,A)", advance="no") char (decay(j))
    end do
    write (u, "(A)")
  end do

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: particle_specifiers_1"
end subroutine particle_specifiers_1

```

Particle specifier expressions

Nested expressions (only basic particles, no decay specs).

<Particle specifiers: execute tests>+≡

```

call test (particle_specifiers_2, "particle_specifiers_2", &

```

```

        "Particle specifier expressions", &
        u, results)

(Particle specifiers: tests)+=
subroutine particle_specifiers_2 (u)
    integer, intent(in) :: u
    type(prt_spec_t) :: a, b, c, d, e, f
    type(prt_expr_t) :: pe1, pe2, pe3
    type(prt_expr_t) :: pe4, pe5, pe6, pe7, pe8, pe9
    integer :: i
    type(prt_spec_t), dimension(:), allocatable :: pa

    write (u, "(A)")  "* Test output: particle_specifiers_2"
    write (u, "(A)")  "* Purpose: Create and display particle expressions"
    write (u, "(A)")

    write (u, "(A)")  "* Basic expressions"
    write (u, *)

    a = new_prt_spec (var_str ("a"))
    b = new_prt_spec (var_str ("b"))
    c = new_prt_spec (var_str ("c"))
    d = new_prt_spec (var_str ("d"))
    e = new_prt_spec (var_str ("e"))
    f = new_prt_spec (var_str ("f"))

    call pe1%init_spec (a)
    write (u, "(A)")  char (pe1%to_string ())

    call pe2%init_sum (2)
    select type (x => pe2%x)
    type is (prt_spec_sum_t)
        call x%expr(1)%init_spec (a)
        call x%expr(2)%init_spec (b)
    end select
    write (u, "(A)")  char (pe2%to_string ())

    call pe3%init_list (2)
    select type (x => pe3%x)
    type is (prt_spec_list_t)
        call x%expr(1)%init_spec (a)
        call x%expr(2)%init_spec (b)
    end select
    write (u, "(A)")  char (pe3%to_string ())

    write (u, *)
    write (u, "(A)")  "* Nested expressions"
    write (u, *)

    call pe4%init_list (2)
    select type (x => pe4%x)
    type is (prt_spec_list_t)
        call x%expr(1)%init_sum (2)
        select type (y => x%expr(1)%x)
        type is (prt_spec_sum_t)

```

```

        call y%expr(1)%init_spec (a)
        call y%expr(2)%init_spec (b)
    end select
    call x%expr(2)%init_spec (c)
end select
write (u, "(A)") char (pe4%to_string ())

call pe5%init_list (2)
select type (x => pe5%x)
type is (prt_spec_list_t)
    call x%expr(1)%init_list (2)
    select type (y => x%expr(1)%x)
    type is (prt_spec_list_t)
        call y%expr(1)%init_spec (a)
        call y%expr(2)%init_spec (b)
    end select
    call x%expr(2)%init_spec (c)
end select
write (u, "(A)") char (pe5%to_string ())

call pe6%init_sum (2)
select type (x => pe6%x)
type is (prt_spec_sum_t)
    call x%expr(1)%init_spec (a)
    call x%expr(2)%init_sum (2)
    select type (y => x%expr(2)%x)
    type is (prt_spec_sum_t)
        call y%expr(1)%init_spec (b)
        call y%expr(2)%init_spec (c)
    end select
end select
write (u, "(A)") char (pe6%to_string ())

call pe7%init_list (2)
select type (x => pe7%x)
type is (prt_spec_list_t)
    call x%expr(1)%init_sum (2)
    select type (y => x%expr(1)%x)
    type is (prt_spec_sum_t)
        call y%expr(1)%init_spec (a)
        call y%expr(2)%init_list (2)
        select type (z => y%expr(2)%x)
        type is (prt_spec_list_t)
            call z%expr(1)%init_spec (b)
            call z%expr(2)%init_spec (c)
        end select
    end select
    call x%expr(2)%init_spec (d)
end select
write (u, "(A)") char (pe7%to_string ())

call pe8%init_sum (2)
select type (x => pe8%x)
type is (prt_spec_sum_t)

```



```

    call x%expr(1)%init_list (2)
    select type (y => x%expr(1)%x)
    type is (prt_spec_list_t)
        call y%expr(1)%init_spec (a)
        call y%expr(2)%init_spec (b)
    end select
    call x%expr(2)%init_list (2)
    select type (y => x%expr(2)%x)
    type is (prt_spec_list_t)
        call y%expr(1)%init_spec (c)
        call y%expr(2)%init_spec (d)
    end select
end select
write (u, "(A)") char (pe8%to_string ())

call pe9%init_list (3)
select type (x => pe9%x)
type is (prt_spec_list_t)
    call x%expr(1)%init_sum (2)
    select type (y => x%expr(1)%x)
    type is (prt_spec_sum_t)
        call y%expr(1)%init_spec (a)
        call y%expr(2)%init_spec (b)
    end select
    call x%expr(2)%init_spec (c)
    call x%expr(3)%init_sum (3)
    select type (y => x%expr(3)%x)
    type is (prt_spec_sum_t)
        call y%expr(1)%init_spec (d)
        call y%expr(2)%init_spec (e)
        call y%expr(3)%init_spec (f)
    end select
end select
write (u, "(A)") char (pe9%to_string ())

write (u, *)
write (u, "(A)")  "* Expand as sum"
write (u, *)

call pe1%expand ()
write (u, "(A)") char (pe1%to_string ())

call pe4%expand ()
write (u, "(A)") char (pe4%to_string ())

call pe5%expand ()
write (u, "(A)") char (pe5%to_string ())

call pe6%expand ()
write (u, "(A)") char (pe6%to_string ())

call pe7%expand ()
write (u, "(A)") char (pe7%to_string ())

```

```

call pe8%expand ()
write (u, "(A)") char (pe8%to_string ())

call pe9%expand ()
write (u, "(A)") char (pe9%to_string ())

write (u, *)
write (u, "(A)")  "* Transform to arrays:"

write (u, "(A)")  "* Atomic specifier"
do i = 1, pe1%get_n_terms ()
  call pe1%term_to_array (pa, i)
  call prt_spec_write (pa, u)
end do

write (u, *)
write (u, "(A)")  "* List"
do i = 1, pe5%get_n_terms ()
  call pe5%term_to_array (pa, i)
  call prt_spec_write (pa, u)
end do

write (u, *)
write (u, "(A)")  "* Sum of atoms"
do i = 1, pe6%get_n_terms ()
  call pe6%term_to_array (pa, i)
  call prt_spec_write (pa, u)
end do

write (u, *)
write (u, "(A)")  "* Sum of lists"
do i = 1, pe9%get_n_terms ()
  call pe9%term_to_array (pa, i)
  call prt_spec_write (pa, u)
end do

write (u, "(A)")
write (u, "(A)")  "* Test output end: particle_specifiers_2"
end subroutine particle_specifiers_2

```

12.2 PDG arrays

For defining aliases, we introduce a special type which holds a set of (integer) PDG codes.

`<pdg_arrays.f90>`≡
<File header>

```

module pdg_arrays

  use io_units
  use unit_tests

```

```

    use sorting
    use physics_defs, only: UNDEFINED

    <Standard module head>

    <PDG arrays: public>

    <PDG arrays: types>

    <PDG arrays: interfaces>

    contains

    <PDG arrays: procedures>

    <PDG arrays: tests>

    end module pdg_arrays

```

12.2.1 Type definition

Using an allocatable array eliminates the need for initializer and/or finalizer.

```

<PDG arrays: public>≡
    public :: pdg_array_t

<PDG arrays: types>≡
    type :: pdg_array_t
    private
        integer, dimension(:), allocatable :: pdg
    contains
        <PDG arrays: pdg array: TBP>
    end type pdg_array_t

```

Output

```

<PDG arrays: public>+≡
    public :: pdg_array_write

<PDG arrays: pdg array: TBP>≡
    procedure :: write => pdg_array_write

<PDG arrays: procedures>≡
    subroutine pdg_array_write (aval, unit)
        class(pdg_array_t), intent(in) :: aval
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "PDG("
        if (allocated (aval%pdg)) then
            do i = 1, size (aval%pdg)
                if (i > 1) write (u, "(A)", advance="no") " ", "
                write (u, "(IO)", advance="no") aval%pdg(i)
            end do
        end if
        write (u, "(A)", advance="no") ")"
    end subroutine

```

```
end subroutine pdg_array_write
```

12.2.2 Basic operations

Assignment. We define assignment from and to an integer array. Note that the integer array, if it is the l.h.s., must be declared allocatable by the caller.

```
<PDG arrays: public>+=
  public :: assignment(=)

<PDG arrays: interfaces>=
  interface assignment(=)
    module procedure pdg_array_from_int_array
    module procedure pdg_array_from_int
    module procedure int_array_from_pdg_array
  end interface

<PDG arrays: procedures>+=
  subroutine pdg_array_from_int_array (aval, iarray)
    type(pdg_array_t), intent(out) :: aval
    integer, dimension(:), intent(in) :: iarray
    allocate (aval%pdg (size (iarray)))
    aval%pdg = iarray
  end subroutine pdg_array_from_int_array

  elemental subroutine pdg_array_from_int (aval, int)
    type(pdg_array_t), intent(out) :: aval
    integer, intent(in) :: int
    allocate (aval%pdg (1))
    aval%pdg = int
  end subroutine pdg_array_from_int

  subroutine int_array_from_pdg_array (iarray, aval)
    integer, dimension(:), allocatable, intent(out) :: iarray
    type(pdg_array_t), intent(in) :: aval
    if (allocated (aval%pdg)) then
      allocate (iarray (size (aval%pdg)))
      iarray = aval%pdg
    else
      allocate (iarray (0))
    end if
  end subroutine int_array_from_pdg_array
```

Allocate space for a PDG array

```
<PDG arrays: public>+=
  public :: pdg_array_init

<PDG arrays: procedures>+=
  subroutine pdg_array_init (aval, n_elements)
    type(pdg_array_t), intent(inout) :: aval
    integer, intent(in) :: n_elements
    allocate(aval%pdg(n_elements))
  end subroutine pdg_array_init
```

Deallocate a previously allocated pdg array

```
<PDG arrays: public>+=  
    public :: pdg_array_delete  
  
<PDG arrays: procedures>+=  
    subroutine pdg_array_delete (aval)  
        type(pdg_array_t), intent(inout) :: aval  
        if (allocated (aval%pdg)) deallocate (aval%pdg)  
    end subroutine pdg_array_delete
```

Merge two pdg arrays, i.e. append a particle string to another leaving out doublettes

```
<PDG arrays: public>+=  
    public :: pdg_array_merge  
  
<PDG arrays: procedures>+=  
    subroutine pdg_array_merge (aval1, aval2)  
        type(pdg_array_t), intent(inout) :: aval1  
        type(pdg_array_t), intent(in) :: aval2  
        type(pdg_array_t) :: aval  
        if (allocated (aval1%pdg) .and. allocated (aval2%pdg)) then  
            if (.not. any (aval1%pdg == aval2%pdg)) aval = aval1 // aval2  
        else if (allocated (aval1%pdg)) then  
            aval = aval1  
        else if (allocated (aval2%pdg)) then  
            aval = aval2  
        end if  
        call pdg_array_delete (aval1)  
        aval1 = aval%pdg  
    end subroutine pdg_array_merge
```

Length of the array.

```
<PDG arrays: public>+=  
    public :: pdg_array_get_length  
  
<PDG arrays: pdg array: TBP>+=  
    procedure :: get_length => pdg_array_get_length  
  
<PDG arrays: procedures>+=  
    elemental function pdg_array_get_length (aval) result (n)  
        class(pdg_array_t), intent(in) :: aval  
        integer :: n  
        if (allocated (aval%pdg)) then  
            n = size (aval%pdg)  
        else  
            n = 0  
        end if  
    end function pdg_array_get_length
```

Return the element with index i.

```
<PDG arrays: public>+=  
    public :: pdg_array_get  
  
<PDG arrays: pdg array: TBP>+=  
    procedure :: get => pdg_array_get
```

```

(PDG arrays: procedures)+≡
elemental function pdg_array_get (aval, i) result (pdg)
  class(pdg_array_t), intent(in) :: aval
  integer, intent(in), optional :: i
  integer :: pdg
  if (present (i)) then
    pdg = aval%pdg(i)
  else
    pdg = aval%pdg(1)
  end if
end function pdg_array_get

```

Explicitly set the element with index i.

```

(PDG arrays: pdg array: TBP)+≡
procedure :: set => pdg_array_set

(PDG arrays: procedures)+≡
subroutine pdg_array_set (aval, i, pdg)
  class(pdg_array_t), intent(inout) :: aval
  integer, intent(in) :: i
  integer, intent(in) :: pdg
  aval%pdg(i) = pdg
end subroutine pdg_array_set

```

Replace element with index i by a new array of elements.

```

(PDG arrays: public)+≡
public :: pdg_array_replace

(PDG arrays: pdg array: TBP)+≡
procedure :: replace => pdg_array_replace

(PDG arrays: procedures)+≡
function pdg_array_replace (aval, i, pdg_new) result (aval_new)
  class(pdg_array_t), intent(in) :: aval
  integer, intent(in) :: i
  integer, dimension(:), intent(in) :: pdg_new
  type(pdg_array_t) :: aval_new
  integer :: n, l
  n = size (aval%pdg)
  l = size (pdg_new)
  allocate (aval_new%pdg (n + l - 1))
  aval_new%pdg(:i-1) = aval%pdg(:i-1)
  aval_new%pdg(i:i+l-1) = pdg_new
  aval_new%pdg(i+l:) = aval%pdg(i+1:)
end function pdg_array_replace

```

Concatenate two PDG arrays

```

(PDG arrays: public)+≡
public :: operator(//)

(PDG arrays: interfaces)+≡
interface operator(//)
  module procedure concat_pdg_arrays
end interface

```

```

(PDG arrays: procedures)+≡
function concat_pdg_arrays (aval1, aval2) result (aval)
  type(pdg_array_t) :: aval
  type(pdg_array_t), intent(in) :: aval1, aval2
  integer :: n1, n2
  if (allocated (aval1%pdg) .and. allocated (aval2%pdg)) then
    n1 = size (aval1%pdg)
    n2 = size (aval2%pdg)
    allocate (aval%pdg (n1 + n2))
    aval%pdg(:n1) = aval1%pdg
    aval%pdg(n1+1:) = aval2%pdg
  else if (allocated (aval1%pdg)) then
    aval = aval1
  else if (allocated (aval2%pdg)) then
    aval = aval2
  end if
end function concat_pdg_arrays

```

12.2.3 Matching

A PDG array matches a given PDG code if the code is present within the array. If either one is zero (UNDEFINED), the match also succeeds.

```

(PDG arrays: public)+≡
public :: operator(.match.)

(PDG arrays: interfaces)+≡
interface operator(.match.)
  module procedure pdg_array_match_integer
  module procedure pdg_array_match_pdg_array
end interface

```

Match a single code against the array.

```

(PDG arrays: procedures)+≡
elemental function pdg_array_match_integer (aval, pdg) result (flag)
  logical :: flag
  type(pdg_array_t), intent(in) :: aval
  integer, intent(in) :: pdg
  if (allocated (aval%pdg)) then
    flag = pdg == UNDEFINED &
      .or. any (aval%pdg == UNDEFINED) &
      .or. any (aval%pdg == pdg)
  else
    flag = .false.
  end if
end function pdg_array_match_integer

```

Check if the pdg-number corresponds to a quark

```

(PDG arrays: public)+≡
public :: is_quark

```

```

(PDG arrays: procedures)+≡
function is_quark (pdg_nr) result(res)
  integer, intent(in) :: pdg_nr
  logical :: res
  if (pdg_nr >= 1 .and. pdg_nr <= 6) then
    res = .true.
  else
    res = .false.
  end if
end function is_quark

```

Check if pdg-number corresponds to a gluon

```

(PDG arrays: public)+≡
public :: is_gluon
(PDG arrays: procedures)+≡
function is_gluon (pdg_nr) result(res)
  integer, intent(in) :: pdg_nr
  logical :: res
  if (pdg_nr == 21) then
    res = .true.
  else
    res = .false.
  end if
end function is_gluon

```

```

(PDG arrays: public)+≡
public :: is_lepton
(PDG arrays: procedures)+≡
function is_lepton (pdg_nr) result(res)
  integer, intent(in) :: pdg_nr
  logical :: res
  if (pdg_nr >= 11 .and. pdg_nr <= 16) then
    res = .true.
  else
    res = .false.
  end if
end function is_lepton

```

Check if the pdg-number corresponds to a massless vector boson

```

(PDG arrays: public)+≡
public :: is_massless_vector
(PDG arrays: procedures)+≡
function is_massless_vector (pdg_nr) result (res)
  integer, intent(in) :: pdg_nr
  logical :: res
  if (pdg_nr == 21 .or. pdg_nr == 22) then
    res = .true.
  else
    res = .false.
  end if
end function is_massless_vector

```


Check if pdg-number corresponds to a massive vector boson

```

(PDG arrays: public)+≡
    public :: is_massive_vector

(PDG arrays: procedures)+≡
    function is_massive_vector (pdg_nr) result (res)
        integer, intent(in) :: pdg_nr
        logical :: res
        if (pdg_nr == 23 .or. pdg_nr == 24) then
            res = .true.
        else
            res = .false.
        end if
    end function is_massive_vector

```

Check if particle is strongly interacting

```

(PDG arrays: pdg array: TBP)+≡
    procedure :: has_colored_particles => pdg_array_has_colored_particles

(PDG arrays: procedures)+≡
    function pdg_array_has_colored_particles (pdg) result (colored)
        class(pdg_array_t), intent(in) :: pdg
        logical :: colored
        integer :: i, pdg_nr
        colored = .false.
        do i = 1, size (pdg%pdg)
            pdg_nr = pdg%pdg(i)
            if (is_quark (abs (pdg_nr)) .or. is_gluon (pdg_nr)) then
                colored = .true.
                exit
            end if
        end do
    end function pdg_array_has_colored_particles

```

Match two arrays. Succeeds if any pair of entries matches.

```

(PDG arrays: procedures)+≡
    function pdg_array_match_pdg_array (aval1, aval2) result (flag)
        logical :: flag
        type(pdg_array_t), intent(in) :: aval1, aval2
        if (allocated (aval1%pdg) .and. allocated (aval2%pdg)) then
            flag = any (aval1 .match. aval2%pdg)
        else
            flag = .false.
        end if
    end function pdg_array_match_pdg_array

```

Comparison. Here, we take the PDG arrays as-is, assuming that they are sorted.

The ordering is a bit odd: first, we look only at the absolute values of the PDG codes. If they all match, the particle comes before the antiparticle, scanning from left to right.

```

(PDG arrays: public)+≡
    public :: operator(<)
    public :: operator(>)

```

```

public :: operator(<=)
public :: operator(>=)
public :: operator(==)
public :: operator(/=)

(PDG arrays: interfaces)+≡
interface operator(<)
  module procedure pdg_array_lt
end interface
interface operator(>)
  module procedure pdg_array_gt
end interface
interface operator(<=)
  module procedure pdg_array_le
end interface
interface operator(>=)
  module procedure pdg_array_ge
end interface
interface operator(==)
  module procedure pdg_array_eq
end interface
interface operator(/=)
  module procedure pdg_array_ne
end interface

(PDG arrays: procedures)+≡
elemental function pdg_array_lt (aval1, aval2) result (flag)
  type(pdg_array_t), intent(in) :: aval1, aval2
  logical :: flag
  integer :: i
  if (size (aval1%pdg) /= size (aval2%pdg)) then
    flag = size (aval1%pdg) < size (aval2%pdg)
  else
    do i = 1, size (aval1%pdg)
      if (abs (aval1%pdg(i)) /= abs (aval2%pdg(i))) then
        flag = abs (aval1%pdg(i)) < abs (aval2%pdg(i))
        return
      end if
    end do
    do i = 1, size (aval1%pdg)
      if (aval1%pdg(i) /= aval2%pdg(i)) then
        flag = aval1%pdg(i) > aval2%pdg(i)
        return
      end if
    end do
    flag = .false.
  end if
end function pdg_array_lt

elemental function pdg_array_gt (aval1, aval2) result (flag)
  type(pdg_array_t), intent(in) :: aval1, aval2
  logical :: flag
  flag = .not. (aval1 < aval2 .or. aval1 == aval2)
end function pdg_array_gt

```

```

elemental function pdg_array_le (aval1, aval2) result (flag)
  type(pdg_array_t), intent(in) :: aval1, aval2
  logical :: flag
  flag = aval1 < aval2 .or. aval1 == aval2
end function pdg_array_le

elemental function pdg_array_ge (aval1, aval2) result (flag)
  type(pdg_array_t), intent(in) :: aval1, aval2
  logical :: flag
  flag = .not. (aval1 < aval2)
end function pdg_array_ge

elemental function pdg_array_eq (aval1, aval2) result (flag)
  type(pdg_array_t), intent(in) :: aval1, aval2
  logical :: flag
  if (size (aval1%pdg) /= size (aval2%pdg)) then
    flag = .false.
  else
    flag = all (aval1%pdg == aval2%pdg)
  end if
end function pdg_array_eq

elemental function pdg_array_ne (aval1, aval2) result (flag)
  type(pdg_array_t), intent(in) :: aval1, aval2
  logical :: flag
  flag = .not. (aval1 == aval2)
end function pdg_array_ne

```

Equivalence. Two PDG arrays are equivalent if either one contains UNDEFINED or if each element of array 1 is present in array 2, and vice versa.

```

(PDG arrays: public)+≡
  public :: operator(.eqv.)
  public :: operator(.neqv.)

(PDG arrays: interfaces)+≡
  interface operator(.eqv.)
    module procedure pdg_array_equivalent
  end interface
  interface operator(.neqv.)
    module procedure pdg_array_inequivalent
  end interface

(PDG arrays: procedures)+≡
  elemental function pdg_array_equivalent (aval1, aval2) result (eq)
    logical :: eq
    type(pdg_array_t), intent(in) :: aval1, aval2
    logical, dimension(:), allocatable :: match1, match2
    integer :: i
    if (allocated (aval1%pdg) .and. allocated (aval2%pdg)) then
      eq = any (aval1%pdg == UNDEFINED) &
        .or. any (aval2%pdg == UNDEFINED)
    if (.not. eq) then
      allocate (match1 (size (aval1%pdg)))

```

```

        allocate (match2 (size (aval2%pdg)))
        match1 = .false.
        match2 = .false.
        do i = 1, size (aval1%pdg)
            match2 = match2 .or. aval1%pdg(i) == aval2%pdg
        end do
        do i = 1, size (aval2%pdg)
            match1 = match1 .or. aval2%pdg(i) == aval1%pdg
        end do
        eq = all (match1) .and. all (match2)
    end if
else
    eq = .false.
end if
end function pdg_array_equivalent

elemental function pdg_array_inequivalent (aval1, aval2) result (neq)
    logical :: neq
    type(pdg_array_t), intent(in) :: aval1, aval2
    neq = .not. pdg_array_equivalent (aval1, aval2)
end function pdg_array_inequivalent

```

12.2.4 Sorting

Sort a PDG array by absolute value, particle before antiparticle. After sorting, we eliminate double entries.

```

<PDG arrays: public>+≡
    public :: sort_abs

<PDG arrays: interfaces>+≡
    interface sort_abs
        module procedure pdg_array_sort_abs
    end interface

<PDG arrays: pdg array: TBP>+≡
    procedure :: sort_abs => pdg_array_sort_abs

<PDG arrays: procedures>+≡
    function pdg_array_sort_abs (aval1, unique) result (aval2)
        class(pdg_array_t), intent(in) :: aval1
        logical, intent(in), optional :: unique
        type(pdg_array_t) :: aval2
        integer, dimension(:), allocatable :: tmp
        logical, dimension(:), allocatable :: mask
        integer :: i, n
        logical :: uni
        uni = .false.; if (present (unique)) uni = unique
        n = size (aval1%pdg)
        if (uni) then
            allocate (tmp (n), mask(n))
            tmp = sort_abs (aval1%pdg)
            mask(1) = .true.
            do i = 2, n

```

```

        mask(i) = tmp(i) /= tmp(i-1)
    end do
    allocate (aval2%pdg (count (mask)))
    aval2%pdg = pack (tmp, mask)
else
    allocate (aval2%pdg (n))
    aval2%pdg = sort_abs (aval1%pdg)
end if
end function pdg_array_sort_abs

```

<PDG arrays: pdg array: TBP>+≡

```

procedure :: intersect => pdg_array_intersect

```

<PDG arrays: procedures>+≡

```

function pdg_array_intersect (aval1, match) result (aval2)
class(pdg_array_t), intent(in) :: aval1
integer, dimension(:) :: match
type(pdg_array_t) :: aval2
integer, dimension(:), allocatable :: isec
integer :: i
isec = pack (aval1%pdg, [(any(aval1%pdg(i) == match), i=1,size(aval1%pdg))])
aval2 = isec
end function pdg_array_intersect

```

<PDG arrays: pdg array: TBP>+≡

```

procedure :: search_for_particle => pdg_array_search_for_particle

```

<PDG arrays: procedures>+≡

```

function pdg_array_search_for_particle (pdg, i_part) result (found)
class(pdg_array_t), intent(in) :: pdg
integer, intent(in) :: i_part
logical :: found
found = any (pdg%pdg == i_part)
end function pdg_array_search_for_particle

```

<PDG arrays: pdg array: TBP>+≡

```

procedure :: invert => pdg_array_invert

```

<PDG arrays: procedures>+≡

```

function pdg_array_invert (pdg) result (pdg_inverse)
class(pdg_array_t), intent(in) :: pdg
type(pdg_array_t) :: pdg_inverse
integer :: i, n
n = size (pdg%pdg)
allocate (pdg_inverse%pdg (n))
do i = 1, n
    select case (pdg%pdg(i))
    case (21, 22, 23, 25)
        pdg_inverse%pdg(i) = pdg%pdg(i)
    case default
        pdg_inverse%pdg(i) = -pdg%pdg(i)
    end select
end do
end function pdg_array_invert

```

12.2.5 PDG array list

A PDG array list, or PDG list, is an array of PDG-array objects with some convenience methods.

```

(PDG arrays: public)+≡
    public :: pdg_list_t

(PDG arrays: types)+≡
    type :: pdg_list_t
        type(pdg_array_t), dimension(:), allocatable :: a
        contains
        (PDG arrays: pdg list: TBP)
    end type pdg_list_t

```

Output, as a comma-separated list without advancing I/O.

```

(PDG arrays: pdg list: TBP)≡
    procedure :: write => pdg_list_write

(PDG arrays: procedures)+≡
    subroutine pdg_list_write (object, unit)
        class(pdg_list_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit)
        if (allocated (object%a)) then
            do i = 1, size (object%a)
                if (i > 1) write (u, "(A)", advance="no") ", "
                call object%a(i)%write (u)
            end do
        end if
    end subroutine pdg_list_write

```

Initialize for a certain size. The entries are initially empty PDG arrays.

```

(PDG arrays: pdg list: TBP)+≡
    generic :: init => pdg_list_init_size
    procedure, private :: pdg_list_init_size

(PDG arrays: procedures)+≡
    subroutine pdg_list_init_size (pl, n)
        class(pdg_list_t), intent(out) :: pl
        integer, intent(in) :: n
        allocate (pl%a (n))
    end subroutine pdg_list_init_size

```

Initialize with a definite array of PDG codes. That is, each entry in the list becomes a single-particle PDG array.

```

(PDG arrays: pdg list: TBP)+≡
    generic :: init => pdg_list_init_int_array
    procedure, private :: pdg_list_init_int_array

(PDG arrays: procedures)+≡
    subroutine pdg_list_init_int_array (pl, pdg)
        class(pdg_list_t), intent(out) :: pl
        integer, dimension(:), intent(in) :: pdg

```

```

integer :: i
allocate (pl%a (size (pdg)))
do i = 1, size (pdg)
    pl%a(i) = pdg(i)
end do
end subroutine pdg_list_init_int_array

```

Set one of the entries. No bounds-check.

```

(PDG arrays: pdg list: TBP)+≡
generic :: set => pdg_list_set_int
generic :: set => pdg_list_set_int_array
generic :: set => pdg_list_set_pdg_array
procedure, private :: pdg_list_set_int
procedure, private :: pdg_list_set_int_array
procedure, private :: pdg_list_set_pdg_array

(PDG arrays: procedures)+≡
subroutine pdg_list_set_int (pl, i, pdg)
    class(pdg_list_t), intent(inout) :: pl
    integer, intent(in) :: i
    integer, intent(in) :: pdg
    pl%a(i) = pdg
end subroutine pdg_list_set_int

subroutine pdg_list_set_int_array (pl, i, pdg)
    class(pdg_list_t), intent(inout) :: pl
    integer, intent(in) :: i
    integer, dimension(:), intent(in) :: pdg
    pl%a(i) = pdg
end subroutine pdg_list_set_int_array

subroutine pdg_list_set_pdg_array (pl, i, pa)
    class(pdg_list_t), intent(inout) :: pl
    integer, intent(in) :: i
    type(pdg_array_t), intent(in) :: pa
    pl%a(i) = pa
end subroutine pdg_list_set_pdg_array

```

Array size, not the length of individual entries

```

(PDG arrays: pdg list: TBP)+≡
procedure :: get_size => pdg_list_get_size

(PDG arrays: procedures)+≡
function pdg_list_get_size (pl) result (n)
    class(pdg_list_t), intent(in) :: pl
    integer :: n
    if (allocated (pl%a)) then
        n = size (pl%a)
    else
        n = 0
    end if
end function pdg_list_get_size

```

Return an entry, as a PDG array.

```

(PDG arrays: pdg list: TBP)+≡
  procedure :: get => pdg_list_get

(PDG arrays: procedures)+≡
  function pdg_list_get (pl, i) result (pa)
    class(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: i
    type(pdg_array_t) :: pa
    pa = pl%a(i)
  end function pdg_list_get

```

Check if the list entries are all either mutually disjoint or identical. The individual entries (PDG arrays) should already be sorted, so we can test for equality.

```

(PDG arrays: pdg list: TBP)+≡
  procedure :: is_regular => pdg_list_is_regular

(PDG arrays: procedures)+≡
  function pdg_list_is_regular (pl) result (flag)
    class(pdg_list_t), intent(in) :: pl
    logical :: flag
    integer :: i, j, s
    s = pl%get_size ()
    flag = .true.
    do i = 1, s
      do j = i + 1, s
        if (pl%a(i) .match. pl%a(j)) then
          if (pl%a(i) /= pl%a(j)) then
            flag = .false.
            return
          end if
        end if
      end do
    end do
  end function pdg_list_is_regular

```

Sort the list. First, each entry gets sorted, including elimination of doublers. Then, we sort the list, using the first member of each PDG array as the marker. No removal of doublers at this stage.

If `n_in` is supplied, we do not reorder the first `n_in` particle entries.

```

(PDG arrays: pdg list: TBP)+≡
  procedure :: sort_abs => pdg_list_sort_abs

(PDG arrays: procedures)+≡
  function pdg_list_sort_abs (pl, n_in) result (pl_sorted)
    class(pdg_list_t), intent(in) :: pl
    integer, intent(in), optional :: n_in
    type(pdg_list_t) :: pl_sorted
    type(pdg_array_t), dimension(:), allocatable :: pa
    integer, dimension(:), allocatable :: pdg, map
    integer :: i, n0
    call pl_sorted%init (pl%get_size ())
    if (allocated (pl%a)) then
      allocate (pa (size (pl%a)))

```



```

do i = 1, size (p1%a)
  pa(i) = p1%a(i)%sort_abs (unique = .true.)
end do
allocate (pdg (size (pa)), source = 0)
do i = 1, size (pa)
  if (allocated (pa(i)%pdg)) then
    if (size (pa(i)%pdg) > 0) then
      pdg(i) = pa(i)%pdg(1)
    end if
  end if
end do
if (present (n_in)) then
  n0 = n_in
else
  n0 = 0
end if
allocate (map (size (pdg)))
map(:n0) = [(i, i = 1, n0)]
map(n0+1:) = n0 + order_abs (pdg(n0+1:))
do i = 1, size (pa)
  call p1_sorted%set (i, pa(map(i)))
end do
end if
end function pdg_list_sort_abs

```

Compare sorted lists: equality. The result is undefined if some entries are not allocated.

```

(PDG arrays: pdg list: TBP)+≡
generic :: operator (==) => pdg_list_eq
procedure, private :: pdg_list_eq

(PDG arrays: procedures)+≡
function pdg_list_eq (p1, p2) result (flag)
class(pdg_list_t), intent(in) :: p1, p2
logical :: flag
integer :: i
flag = .false.
if (allocated (p1%a) .and. allocated (p2%a)) then
  if (size (p1%a) == size (p2%a)) then
    do i = 1, size (p1%a)
      associate (a1 => p1%a(i), a2 => p2%a(i))
        if (allocated (a1%pdg) .and. allocated (a2%pdg)) then
          if (size (a1%pdg) == size (a2%pdg)) then
            if (size (a1%pdg) > 0) then
              if (a1%pdg(1) /= a2%pdg(1)) return
            end if
          else
            return
          end if
        else
          return
        end if
      end if
    end do
  end if
end function pdg_list_eq
end function pdg_list_eq

```

```

        flag = .true.
    end if
end if
end function pdg_list_eq

```

Compare sorted lists. The result is undefined if some entries are not allocated.

The ordering is quite complicated. First, a shorter list comes before a longer list. Comparing entry by entry, a shorter entry comes first. Next, we check the first PDG code within corresponding entries. This is compared by absolute value. If equal, particle comes before antiparticle. Finally, if all is equal, the result is false.

```

(PDG arrays: pdg list: TBP)+≡
    generic :: operator (<) => pdg_list_lt
    procedure, private :: pdg_list_lt
(PDG arrays: procedures)+≡
    function pdg_list_lt (p1, p2) result (flag)
        class(pdg_list_t), intent(in) :: p1, p2
        logical :: flag
        integer :: i
        flag = .false.
        if (allocated (p1%a) .and. allocated (p2%a)) then
            if (size (p1%a) < size (p2%a)) then
                flag = .true.; return
            else if (size (p1%a) > size (p2%a)) then
                return
            else
                do i = 1, size (p1%a)
                    associate (a1 => p1%a(i), a2 => p2%a(i))
                        if (allocated (a1%pdg) .and. allocated (a2%pdg)) then
                            if (size (a1%pdg) < size (a2%pdg)) then
                                flag = .true.; return
                            else if (size (a1%pdg) > size (a2%pdg)) then
                                return
                            else
                                if (size (a1%pdg) > 0) then
                                    if (abs (a1%pdg(1)) < abs (a2%pdg(1))) then
                                        flag = .true.; return
                                    else if (abs (a1%pdg(1)) > abs (a2%pdg(1))) then
                                        return
                                    else if (a1%pdg(1) > 0 .and. a2%pdg(1) < 0) then
                                        flag = .true.; return
                                    else if (a1%pdg(1) < 0 .and. a2%pdg(1) > 0) then
                                        return
                                    end if
                                end if
                            end if
                        end if
                    end do
                end do
                flag = .false.
            end if
        end if
    end function pdg_list_lt

```

```

end if
end function pdg_list_lt

```

Replace an entry. In the result, the entry #i is replaced by the contents of the second argument. The result is not sorted.

If n_in is also set and i is less or equal to n_in, replace #i only by the first entry of pl_insert, and insert the remainder after entry n_in.

(PDG arrays: pdg list: TBP)+≡

```

procedure :: replace => pdg_list_replace

```

(PDG arrays: procedures)+≡

```

function pdg_list_replace (pl, i, pl_insert, n_in) result (pl_out)
  class(pdg_list_t), intent(in) :: pl
  integer, intent(in) :: i
  class(pdg_list_t), intent(in) :: pl_insert
  integer, intent(in), optional :: n_in
  type(pdg_list_t) :: pl_out
  integer :: n, n_insert, n_out, k
  n = pl%get_size ()
  n_insert = pl_insert%get_size ()
  n_out = n + n_insert - 1
  call pl_out%init (n_out)
!   if (allocated (pl%a)) then
!       do k = 1, i - 1
!           pl_out%a(k) = pl%a(k)
!       end do
!   end if
  if (present (n_in)) then
    pl_out%a(i) = pl_insert%a(1)
    do k = i + 1, n_in
      pl_out%a(k) = pl%a(k)
    end do
    do k = 1, n_insert - 1
      pl_out%a(n_in+k) = pl_insert%a(1+k)
    end do
    do k = 1, n - n_in
      pl_out%a(n_in+k+n_insert-1) = pl%a(n_in+k)
    end do
  else
!   if (allocated (pl_insert%a)) then
!       do k = 1, n_insert
!           pl_out%a(i-1+k) = pl_insert%a(k)
!       end do
!   end if
!   if (allocated (pl%a)) then
!       do k = 1, n - i
!           pl_out%a(i+n_insert-1+k) = pl%a(i+k)
!       end do
!   end if
!   end if
end function pdg_list_replace

```

Replace the entries of pl by the matching entries of pl_match, one by one. This

is done in-place. If there is no match, return failure.

```

(PDG arrays: pdg list: TBP)+≡
  procedure :: match_replace => pdg_list_match_replace

(PDG arrays: procedures)+≡
  subroutine pdg_list_match_replace (pl, pl_match, success)
    class(pdg_list_t), intent(inout) :: pl
    class(pdg_list_t), intent(in) :: pl_match
    logical, intent(out) :: success
    integer :: i, j
    success = .true.
    SCAN_ENTRIES: do i = 1, size (pl%a)
      do j = 1, size (pl_match%a)
        if (pl%a(i) .match. pl_match%a(j)) then
          pl%a(i) = pl_match%a(j)
          cycle SCAN_ENTRIES
        end if
      end do
      success = .false.
    end do SCAN_ENTRIES
  end subroutine pdg_list_match_replace

```

Just check if a PDG array matches any entry in the PDG list. The second version returns the position of the match within the list. An optional mask indicates the list elements that should be checked.

```

(PDG arrays: pdg list: TBP)+≡
  generic :: operator (.match.) => pdg_list_match_pdg_array
  procedure, private :: pdg_list_match_pdg_array
  procedure :: find_match => pdg_list_find_match_pdg_array

(PDG arrays: procedures)+≡
  function pdg_list_match_pdg_array (pl, pa) result (flag)
    class(pdg_list_t), intent(in) :: pl
    type(pdg_array_t), intent(in) :: pa
    logical :: flag
    flag = pl%find_match (pa) /= 0
  end function pdg_list_match_pdg_array

  function pdg_list_find_match_pdg_array (pl, pa, mask) result (i)
    class(pdg_list_t), intent(in) :: pl
    type(pdg_array_t), intent(in) :: pa
    logical, dimension(:), intent(in), optional :: mask
    integer :: i
    do i = 1, size (pl%a)
      if (present (mask)) then
        if (.not. mask(i)) cycle
      end if
      if (pl%a(i) .match. pa) return
    end do
    i = 0
  end function pdg_list_find_match_pdg_array

```

Some old compilers have problems with allocatable arrays as intent(out) or as function result, so be conservative here:

(PDG arrays: pdg list: TBP)+≡

```
procedure :: create_pdg_array => pdg_list_create_pdg_array
```

(PDG arrays: procedures)+≡

```
subroutine pdg_list_create_pdg_array (pl, pdg)
  class(pdg_list_t), intent(in) :: pl
  type(pdg_array_t), dimension(:), intent(inout), allocatable :: pdg
  integer :: n_elements
  integer :: i
  associate (a => pl%a)
    n_elements = size (a)
    if (allocated (pdg)) deallocate (pdg)
    allocate (pdg (n_elements))
    do i = 1, n_elements
      pdg(i) = a(i)
    end do
  end associate
end subroutine pdg_list_create_pdg_array
```

(PDG arrays: pdg list: TBP)+≡

```
procedure :: create_antiparticles => pdg_list_create_antiparticles
```

(PDG arrays: procedures)+≡

```
subroutine pdg_list_create_antiparticles (pl, pl_anti, n_new_particles)
  class(pdg_list_t), intent(in) :: pl
  type(pdg_list_t), intent(out) :: pl_anti
  integer, intent(out) :: n_new_particles
  type(pdg_list_t) :: pl_inverse
  integer :: i, n
  integer :: n_identical
  logical, dimension(:), allocatable :: collect
  n = pl%get_size (); n_identical = 0
  allocate (collect (n)); collect = .true.
  call pl_inverse%init (n)
  do i = 1, n
    pl_inverse%a(i) = pl%a(i)%invert()
  end do
  do i = 1, n
    if (any (pl_inverse%a(i) == pl%a)) then
      collect(i) = .false.
      n_identical = n_identical + 1
    end if
  end do
  n_new_particles = n - n_identical
  if (n_new_particles > 0) then
    call pl_anti%init (n_new_particles)
    do i = 1, n
      if (collect (i)) pl_anti%a(i) = pl_inverse%a(i)
    end do
  end if
end subroutine pdg_list_create_antiparticles
```

```

(PDG arrays: pdg list: TBP)+≡
  procedure :: search_for_particle => pdg_list_search_for_particle

(PDG arrays: procedures)+≡
  function pdg_list_search_for_particle (pl, i_part) result (found)
    class(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: i_part
    logical :: found
    integer :: i_pl
    do i_pl = 1, size (pl%a)
      found = pl%a(i_pl)%search_for_particle (i_part)
      if (found) return
    end do
  end function pdg_list_search_for_particle

(PDG arrays: pdg list: TBP)+≡
  procedure :: contains_colored_particles => pdg_list_contains_colored_particles

(PDG arrays: procedures)+≡
  function pdg_list_contains_colored_particles (pl) result (colored)
    class(pdg_list_t), intent(in) :: pl
    logical :: colored
    integer :: i
    colored = .false.
    do i = 1, size (pl%a)
      if (pl%a(i)%has_colored_particles()) then
        colored = .true.
        exit
      end if
    end do
  end function pdg_list_contains_colored_particles

```

12.2.6 Unit tests

```

(PDG arrays: public)+≡
  public :: pdg_arrays_test

(PDG arrays: procedures)+≡
  subroutine pdg_arrays_test (u, results)
    integer, intent(in) :: u
    type (test_results_t), intent(inout) :: results
  (PDG arrays: execute tests)
  end subroutine pdg_arrays_test

```

Basic functionality.

```

(PDG arrays: execute tests)≡
  call test (pdg_arrays_1, "pdg_arrays_1", &
    "create and sort PDG array", &
    u, results)

(PDG arrays: tests)≡
  subroutine pdg_arrays_1 (u)
    integer, intent(in) :: u

```

```

type(pdg_array_t) :: pa, pa1, pa2, pa3, pa4, pa5, pa6
integer, dimension(:), allocatable :: pdg

write (u, "(A)")  "* Test output: pdg_arrays_1"
write (u, "(A)")  "*   Purpose: create and sort PDG arrays"
write (u, "(A)")

write (u, "(A)")  "* Assignment"
write (u, "(A)")

call pa%write (u)
write (u, *)
write (u, "(A,I0)")  "length = ", pa%get_length ()
pdg = pa
write (u, "(A,3(1x,I0))")  "contents = ", pdg

write (u, *)
pa = 1
call pa%write (u)
write (u, *)
write (u, "(A,I0)")  "length = ", pa%get_length ()
pdg = pa
write (u, "(A,3(1x,I0))")  "contents = ", pdg

write (u, *)
pa = [1, 2, 3]
call pa%write (u)
write (u, *)
write (u, "(A,I0)")  "length = ", pa%get_length ()
pdg = pa
write (u, "(A,3(1x,I0))")  "contents = ", pdg
write (u, "(A,I0)")  "element #2 = ", pa%get (2)

write (u, *)
write (u, "(A)")  "* Replace"
write (u, *)

pa = pa%replace (2, [-5, 5, -7])
call pa%write (u)
write (u, *)

write (u, *)
write (u, "(A)")  "* Sort"
write (u, *)

pa = [1, -7, 3, -5, 5, 3]
call pa%write (u)
write (u, *)
pa1 = pa%sort_abs ()
pa2 = pa%sort_abs (unique = .true.)
call pa1%write (u)
write (u, *)
call pa2%write (u)

```

```

write (u, *)

write (u, *)
write (u, "(A)")  "* Compare"
write (u, *)

pa1 = [1, 3]
pa2 = [1, 2, -2]
pa3 = [1, 2, 4]
pa4 = [1, 2, 4]
pa5 = [1, 2, -4]
pa6 = [1, 2, -3]

write (u, "(A,6(1x,L1))") "< ", &
    pa1 < pa2, pa2 < pa3, pa3 < pa4, pa4 < pa5, pa5 < pa6, pa6 < pa1
write (u, "(A,6(1x,L1))") "> ", &
    pa1 > pa2, pa2 > pa3, pa3 > pa4, pa4 > pa5, pa5 > pa6, pa6 > pa1
write (u, "(A,6(1x,L1))") "<=", &
    pa1 <= pa2, pa2 <= pa3, pa3 <= pa4, pa4 <= pa5, pa5 <= pa6, pa6 <= pa1
write (u, "(A,6(1x,L1))") ">=", &
    pa1 >= pa2, pa2 >= pa3, pa3 >= pa4, pa4 >= pa5, pa5 >= pa6, pa6 >= pa1
write (u, "(A,6(1x,L1))") "==", &
    pa1 == pa2, pa2 == pa3, pa3 == pa4, pa4 == pa5, pa5 == pa6, pa6 == pa1
write (u, "(A,6(1x,L1))") "/=", &
    pa1 /= pa2, pa2 /= pa3, pa3 /= pa4, pa4 /= pa5, pa5 /= pa6, pa6 /= pa1

write (u, *)
pa1 = [0]
pa2 = [1, 2]
pa3 = [1, -2]

write (u, "(A,6(1x,L1))") ".eqv ", &
    pa1 .eqv. pa1, pa1 .eqv. pa2, &
    pa2 .eqv. pa2, pa2 .eqv. pa3

write (u, "(A,6(1x,L1))") ".neqv", &
    pa1 .neqv. pa1, pa1 .neqv. pa2, &
    pa2 .neqv. pa2, pa2 .neqv. pa3

write (u, *)
write (u, "(A,6(1x,L1))") ".match", &
    pa1 .match. 0, pa1 .match. 1, &
    pa2 .match. 0, pa2 .match. 1, pa2 .match. 3

write (u, "(A)")
write (u, "(A)")  "* Test output end: pdg_arrays_1"

end subroutine pdg_arrays_1

```

PDG array list, i.e., arrays of arrays.

```

(PDG arrays: execute tests)+≡
call test (pdg_arrays_2, "pdg_arrays_2", &

```



```

        "create and sort PDG lists", &
        u, results)
(PDG arrays: tests)+≡
subroutine pdg_arrays_2 (u)
    integer, intent(in) :: u

    type(pdg_array_t) :: pa
    type(pdg_list_t) :: pl, pl1

    write (u, "(A)")  "* Test output: pdg_arrays_2"
    write (u, "(A)")  "* Purpose: create and sort PDG lists"
    write (u, "(A)")

    write (u, "(A)")  "* Assignment"
    write (u, "(A)")

    call pl%init (3)
    call pl%set (1, 42)
    call pl%set (2, [3, 2])
    pa = [5, -5]
    call pl%set (3, pa)
    call pl%write (u)
    write (u, *)
    write (u, "(A,I0)")  "size = ", pl%get_size ()

    write (u, "(A)")
    write (u, "(A)")  "* Sort"
    write (u, "(A)")

    pl = pl%sort_abs ()
    call pl%write (u)
    write (u, *)

    write (u, "(A)")
    write (u, "(A)")  "* Extract item #3"
    write (u, "(A)")

    pa = pl%get (3)
    call pa%write (u)
    write (u, *)

    write (u, "(A)")
    write (u, "(A)")  "* Replace item #3"
    write (u, "(A)")

    call pl1%init (2)
    call pl1%set (1, [2, 4])
    call pl1%set (2, -7)

    pl = pl%replace (3, pl1)
    call pl%write (u)
    write (u, *)

    write (u, "(A)")

```

```

        write (u, "(A)")  "* Test output end: pdg_arrays_2"

    end subroutine pdg_arrays_2

```

Check if a (sorted) PDG array lists is regular. The entries (PDG arrays) must not overlap, unless they are identical.

```

<PDG arrays: execute tests>+≡
    call test (pdg_arrays_3, "pdg_arrays_3", &
        "check PDG lists", &
        u, results)

<PDG arrays: tests>+≡
    subroutine pdg_arrays_3 (u)
        integer, intent(in) :: u

        type(pdg_list_t) :: pl

        write (u, "(A)")  "* Test output: pdg_arrays_3"
        write (u, "(A)")  "* Purpose: check for regular PDG lists"
        write (u, "(A)")

        write (u, "(A)")  "* Regular list"
        write (u, "(A)")

        call pl%init (4)
        call pl%set (1, [1, 2])
        call pl%set (2, [1, 2])
        call pl%set (3, [5, -5])
        call pl%set (4, 42)
        call pl%write (u)
        write (u, *)
        write (u, "(L1)") pl%is_regular ()

        write (u, "(A)")
        write (u, "(A)")  "* Irregular list"
        write (u, "(A)")

        call pl%init (4)
        call pl%set (1, [1, 2])
        call pl%set (2, [1, 2])
        call pl%set (3, [2, 5, -5])
        call pl%set (4, 42)
        call pl%write (u)
        write (u, *)
        write (u, "(L1)") pl%is_regular ()

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: pdg_arrays_3"

    end subroutine pdg_arrays_3

```

Compare PDG array lists. The lists must be regular, i.e., sorted and with non-overlapping (or identical) entries.

```

(PDG arrays: execute tests)+≡
  call test (pdg_arrays_4, "pdg_arrays_4", &
    "compare PDG lists", &
    u, results)

(PDG arrays: tests)+≡
  subroutine pdg_arrays_4 (u)
    integer, intent(in) :: u

    type(pdg_list_t) :: pl1, pl2, pl3

    write (u, "(A)")  "* Test output: pdg_arrays_4"
    write (u, "(A)")  "* Purpose: check for regular PDG lists"
    write (u, "(A)")

    write (u, "(A)")  "* Create lists"
    write (u, "(A)")

    call pl1%init (4)
    call pl1%set (1, [1, 2])
    call pl1%set (2, [1, 2])
    call pl1%set (3, [5, -5])
    call pl1%set (4, 42)
    write (u, "(I1,1x)", advance = "no")  1
    call pl1%write (u)
    write (u, *)

    call pl2%init (2)
    call pl2%set (1, 3)
    call pl2%set (2, [5, -5])
    write (u, "(I1,1x)", advance = "no")  2
    call pl2%write (u)
    write (u, *)

    call pl3%init (2)
    call pl3%set (1, 4)
    call pl3%set (2, [5, -5])
    write (u, "(I1,1x)", advance = "no")  3
    call pl3%write (u)
    write (u, *)

    write (u, "(A)")
    write (u, "(A)")  "* a == b"
    write (u, "(A)")

    write (u, "(2x,A)")  "123"
    write (u, *)
    write (u, "(I1,1x,4L1)")  1, pl1 == pl1, pl1 == pl2, pl1 == pl3
    write (u, "(I1,1x,4L1)")  2, pl2 == pl1, pl2 == pl2, pl2 == pl3
    write (u, "(I1,1x,4L1)")  3, pl3 == pl1, pl3 == pl2, pl3 == pl3

    write (u, "(A)")
    write (u, "(A)")  "* a < b"
    write (u, "(A)")

```

```

write (u, "(2x,A)") "123"
write (u, *)
write (u, "(I1,1x,4L1)") 1, pl1 < pl1, pl1 < pl2, pl1 < pl3
write (u, "(I1,1x,4L1)") 2, pl2 < pl1, pl2 < pl2, pl2 < pl3
write (u, "(I1,1x,4L1)") 3, pl3 < pl1, pl3 < pl2, pl3 < pl3

write (u, "(A)")
write (u, "(A)") "* Test output end: pdg_arrays_4"

end subroutine pdg_arrays_4

```

Match-replace: translate all entries in the first list into the matching entries of the second list, if there is a match.

```

(PDG arrays: execute tests)+≡
call test (pdg_arrays_5, "pdg_arrays_5", &
"match PDG lists", &
u, results)

(PDG arrays: tests)+≡
subroutine pdg_arrays_5 (u)
integer, intent(in) :: u

type(pdg_list_t) :: pl1, pl2, pl3
logical :: success

write (u, "(A)") "* Test output: pdg_arrays_5"
write (u, "(A)") "* Purpose: match-replace"
write (u, "(A)")

write (u, "(A)") "* Create lists"
write (u, "(A)")

call pl1%init (2)
call pl1%set (1, [1, 2])
call pl1%set (2, 42)
call pl1%write (u)
write (u, *)
call pl3%init (2)
call pl3%set (1, [42, -42])
call pl3%set (2, [1, 2, 3, 4])
call pl1%match_replace (pl3, success)
call pl3%write (u)
write (u, "(1x,A,1x,L1,':'',1x)", advance="no") "=>", success
call pl1%write (u)
write (u, *)

write (u, *)

call pl2%init (2)
call pl2%set (1, 9)
call pl2%set (2, 42)
call pl2%write (u)
write (u, *)
call pl2%match_replace (pl3, success)

```

```

call pl3%write (u)
write (u, "(1x,A,1x,L1,':',1x)", advance="no")  "=>", success
call pl2%write (u)
write (u, *)

write (u, "(A)")
write (u, "(A)")  "* Test output end: pdg_arrays_5"

end subroutine pdg_arrays_5

```

12.3 Jets

The FastJet library is linked externally, if available. The wrapper code is also in a separate directory. Here, we define WHIZARD-specific procedures and tests.

```
<jets.f90>≡  
  <File header>  
  
  module jets  
  
    <Use kinds>  
    use unit_tests  
    use fastjet !NODEP!  
  
    <Standard module head>  
  
    <Jets: public>  
  
    contains  
  
    <Jets: procedures>  
  
    <Jets: tests>  
  
  end module jets
```

12.3.1 Re-exported symbols

We use this module as a proxy for the FastJet interface, therefore we re-export some symbols.

```
<Jets: public>≡  
  public :: fastjet_available  
  public :: fastjet_init  
  public :: jet_definition_t  
  public :: pseudojet_t  
  public :: pseudojet_vector_t  
  public :: cluster_sequence_t  
  public :: assignment (=)
```

The initialization routine prints the banner.

```
<Jets: procedures>≡  
  subroutine fastjet_init ()  
    call print_banner ()  
  end subroutine fastjet_init
```

The jet algorithm codes (actually, integers)

```
<Jets: public>+≡  
  public :: kt_algorithm  
  public :: cambridge_algorithm  
  public :: antikt_algorithm  
  public :: genkt_algorithm  
  public :: cambridge_for_passive_algorithm  
  public :: genkt_for_passive_algorithm
```

```

public :: ee_kt_algorithm
public :: ee_genkt_algorithm
public :: plugin_algorithm
public :: undefined_jet_algorithm

```

12.3.2 Unit tests

```

<Jets: public>+≡
    public :: jets_test

<Jets: procedures>+≡
    subroutine jets_test (u, results)
        integer, intent(in) :: u
        type (test_results_t), intent(inout) :: results
    <Jets: execute tests>
    end subroutine jets_test

```

This test is actually the minimal example from the FastJet manual, translated to Fortran.

Note that FastJet creates pseudojet vectors, which we mirror in the `pseudojet_vector_t`, but immediately assign to pseudojet arrays. Without automatic finalization available in the compilers, we should avoid this in actual code and rather introduce intermediate variables for those objects, which we can finalize explicitly.

```

<Jets: execute tests>≡
    call test (jets_1, "jets_1", &
        "basic FastJet functionality", &
        u, results)

<Jets: tests>≡
    subroutine jets_1 (u)
        integer, intent(in) :: u

        type(pseudojet_t), dimension(:), allocatable :: prt, jets, constituents
        type(jet_definition_t) :: jet_def
        type(cluster_sequence_t) :: cs

        integer, parameter :: dp = default
        integer :: i, j

        write (u, "(A)")  "* Test output: jets_1"
        write (u, "(A)")  "* Purpose: test basic FastJet functionality"
        write (u, "(A)")

        write (u, "(A)")  "* Print banner"
        call print_banner ()

        write (u, *)
        write (u, "(A)")  "* Prepare input particles"
        allocate (prt (3))
        call prt(1)%init ( 99._dp, 0.1_dp, 0._dp, 100._dp)
        call prt(2)%init (  4._dp,-0.1_dp, 0._dp,  5._dp)
        call prt(3)%init (-99._dp, 0._dp,  0._dp, 99._dp)

```

```

write (u, *)
write (u, "(A)")  "* Define jet algorithm"
call jet_def%init (antikt_algorithm, 0.7_dp)

write (u, *)
write (u, "(A)")  "* Cluster particles according to jet algorithm"

write (u, *)
write (u, "(A,A)") "Clustering with ", jet_def%description ()
call cs%init (pseudojet_vector (prt), jet_def)

write (u, *)
write (u, "(A)")  "* Sort output jets"
jets = sorted_by_pt (cs%inclusive_jets ())

write (u, *)
write (u, "(A)")  "* Print jet observables and constituents"
write (u, *)
write (u, "(4x,3(7x,A3))") "pt", "y", "phi"
do i = 1, size (jets)
  write (u, "(A,1x,I0,A,3(1x,F9.5))") &
    "jet", i, ":", jets(i)%perp (), jets(i)%rap (), jets(i)%phi ()
  constituents = jets(i)%constituents ()
  do j = 1, size (constituents)
    write (u, "(4x,A,1x,I0,A,F9.5)") &
      "constituent", j, "'s pt:", constituents(j)%perp ()
  end do
  do j = 1, size (constituents)
    call constituents(j)%final ()
  end do
end do

write (u, *)
write (u, "(A)")  "* Cleanup"

do i = 1, size (prt)
  call prt(i)%final ()
end do
do i = 1, size (jets)
  call jets(i)%final ()
end do
call jet_def%final ()
call cs%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: jets_1"

end subroutine jets_1

```


12.4 Subevents

The purpose of subevents is to store the relevant part of the physical event (either partonic or hadronic), and to hold particle selections and combinations which are constructed in cut or analysis expressions.

```
<subevents.f90>≡  
  <File header>  
  
  module subevents  
  
    use, intrinsic :: iso_c_binding !NODEP!  
  
    <Use kinds>  
    use io_units  
    use format_defs, only: FMT_14, FMT_19  
    use format_utils, only: pac_fmt  
    use sorting  
    use c_particles  
    use lorentz  
    use pdg_arrays  
    use jets  
  
    <Standard module head>  
  
    <Subevents: public>  
  
    <Subevents: parameters>  
  
    <Subevents: types>  
  
    <Subevents: interfaces>  
  
    contains  
  
    <Subevents: procedures>  
  
  end module subevents
```

12.4.1 Particles

For the purpose of this module, a particle has a type which can indicate a beam, incoming, outgoing, or composite particle, flavor and helicity codes (integer, undefined for composite), four-momentum and invariant mass squared. (Other particles types are used in extended event types, but also defined here.) Furthermore, each particle has an allocatable array of ancestors – particle indices which indicate the building blocks of a composite particle. For an incoming/outgoing particle, the array contains only the index of the particle itself.

For incoming particles, the momentum is inverted before storing it in the particle object.

```
<Subevents: parameters>≡  
  integer, parameter, public :: PRT_UNDEFINED = 0  
  integer, parameter, public :: PRT_BEAM = -9
```

```

integer, parameter, public :: PRT_INCOMING = 1
integer, parameter, public :: PRT_OUTGOING = 2
integer, parameter, public :: PRT_COMPOSITE = 3
integer, parameter, public :: PRT_VIRTUAL = 4
integer, parameter, public :: PRT_RESONANT = 5
integer, parameter, public :: PRT_BEAM_REMNANT = 9

```

The type

We initialize only the type here and mark as unpolarized. The initializers below do the rest.

```

<Subevents: public>≡
  public :: prt_t

<Subevents: types>≡
  type :: prt_t
    private
    integer :: type = PRT_UNDEFINED
    integer :: pdg
    logical :: polarized = .false.
    integer :: h
    type(vector4_t) :: p
    real(default) :: p2
    integer, dimension(:), allocatable :: src
  end type prt_t

```

Initializers. Polarization is set separately. Finalizers are not needed.

```

<Subevents: procedures>≡
  subroutine prt_init_beam (prt, pdg, p, p2, src)
    type(prt_t), intent(out) :: prt
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_BEAM
    call prt_set (prt, pdg, - p, p2, src)
  end subroutine prt_init_beam

  subroutine prt_init_incoming (prt, pdg, p, p2, src)
    type(prt_t), intent(out) :: prt
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_INCOMING
    call prt_set (prt, pdg, - p, p2, src)
  end subroutine prt_init_incoming

  subroutine prt_init_outgoing (prt, pdg, p, p2, src)
    type(prt_t), intent(out) :: prt
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p

```

```

    real(default), intent(in) :: p2
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_OUTGOING
    call prt_set (prt, pdg, p, p2, src)
end subroutine prt_init_outgoing

subroutine prt_init_composite (prt, p, src)
    type(prt_t), intent(out) :: prt
    type(vector4_t), intent(in) :: p
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_COMPOSITE
    call prt_set (prt, 0, p, p**2, src)
end subroutine prt_init_composite

```

This version is for temporary particle objects, so the `src` array is not set.

```

<Subevents: public>+≡
    public :: prt_init_combine

<Subevents: procedures>+≡
    subroutine prt_init_combine (prt, prt1, prt2)
        type(prt_t), intent(out) :: prt
        type(prt_t), intent(in) :: prt1, prt2
        type(vector4_t) :: p
        integer, dimension(0) :: src
        prt%type = PRT_COMPOSITE
        p = prt1%p + prt2%p
        call prt_set (prt, 0, p, p**2, src)
    end subroutine prt_init_combine

```

Init from a pseudojet object.

```

<Subevents: procedures>+≡
    subroutine prt_init_pseudojet (prt, jet, src)
        type(prt_t), intent(out) :: prt
        type(pseudojet_t), intent(in) :: jet
        integer, dimension(:), intent(in) :: src
        type(vector4_t) :: p
        prt%type = PRT_COMPOSITE
        p = vector4_moving (jet%e(), &
            vector3_moving ([jet%px(), jet%py(), jet%pz()]))
        call prt_set (prt, 0, p, p**2, src)
    end subroutine prt_init_pseudojet

```

Accessing contents

```

<Subevents: public>+≡
    public :: prt_get_pdg

<Subevents: procedures>+≡
    elemental function prt_get_pdg (prt) result (pdg)
        integer :: pdg
        type(prt_t), intent(in) :: prt
        pdg = prt%pdg
    end function prt_get_pdg

```

```

<Subevents: public>+≡
    public :: prt_get_momentum

<Subevents: procedures>+≡
    elemental function prt_get_momentum (prt) result (p)
        type(vector4_t) :: p
        type(prt_t), intent(in) :: prt
        p = prt%p
    end function prt_get_momentum

<Subevents: public>+≡
    public :: prt_get_msq

<Subevents: procedures>+≡
    elemental function prt_get_msq (prt) result (msq)
        real(default) :: msq
        type(prt_t), intent(in) :: prt
        msq = prt%p2
    end function prt_get_msq

<Subevents: public>+≡
    public :: prt_is_polarized

<Subevents: procedures>+≡
    elemental function prt_is_polarized (prt) result (flag)
        logical :: flag
        type(prt_t), intent(in) :: prt
        flag = prt%polarized
    end function prt_is_polarized

<Subevents: public>+≡
    public :: prt_get_helicity

<Subevents: procedures>+≡
    elemental function prt_get_helicity (prt) result (h)
        integer :: h
        type(prt_t), intent(in) :: prt
        h = prt%h
    end function prt_get_helicity

```

Setting data

Set the PDG, momentum and momentum squared, and ancestors. If allocation-assignment is available, this can be simplified.

```

<Subevents: procedures>+≡
    subroutine prt_set (prt, pdg, p, p2, src)
        type(prt_t), intent(inout) :: prt
        integer, intent(in) :: pdg
        type(vector4_t), intent(in) :: p
        real(default), intent(in) :: p2
        integer, dimension(:), intent(in) :: src
        prt%pdg = pdg
    end subroutine prt_set

```

```

prt%p = p
prt%p2 = p2
if (allocated (prt%src)) then
  if (size (src) /= size (prt%src)) then
    deallocate (prt%src)
    allocate (prt%src (size (src)))
  end if
else
  allocate (prt%src (size (src)))
end if
prt%src = src
end subroutine prt_set

```

Set the particle PDG code separately.

```

<Subevents: procedures>+≡
  elemental subroutine prt_set_pdg (prt, pdg)
    type(prt_t), intent(inout) :: prt
    integer, intent(in) :: pdg
    prt%pdg = pdg
  end subroutine prt_set_pdg

```

Set the momentum separately.

```

<Subevents: procedures>+≡
  elemental subroutine prt_set_p (prt, p)
    type(prt_t), intent(inout) :: prt
    type(vector4_t), intent(in) :: p
    prt%p = p
  end subroutine prt_set_p

```

Set the squared invariant mass separately.

```

<Subevents: procedures>+≡
  elemental subroutine prt_set_p2 (prt, p2)
    type(prt_t), intent(inout) :: prt
    real(default), intent(in) :: p2
    prt%p2 = p2
  end subroutine prt_set_p2

```

Set helicity (optional).

```

<Subevents: procedures>+≡
  subroutine prt_polarize (prt, h)
    type(prt_t), intent(inout) :: prt
    integer, intent(in) :: h
    prt%polarized = .true.
    prt%h = h
  end subroutine prt_polarize

```

Conversion

Transform a `prt_t` object into a `c_prt_t` object.

```

<Subevents: public>+≡
  public :: c_prt

```

```

<Subevents: interfaces>≡
  interface c_prt
    module procedure c_prt_from_prt
  end interface

<Subevents: procedures>+≡
  elemental function c_prt_from_prt (prt) result (c_prt)
    type(c_prt_t) :: c_prt
    type(prt_t), intent(in) :: prt
    c_prt = prt%p
    c_prt%type = prt%type
    c_prt%pdg = prt%pdg
    if (prt%polarized) then
      c_prt%polarized = 1
    else
      c_prt%polarized = 0
    end if
    c_prt%h = prt%h
  end function c_prt_from_prt

```

Output

```

<Subevents: public>+≡
  public :: prt_write

<Subevents: procedures>+≡
  subroutine prt_write (prt, unit, testflag)
    type(prt_t), intent(in) :: prt
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    logical :: pacified
    type(prt_t) :: tmp
    character(len=7) :: fmt
    integer :: u, i
    call pac_fmt (fmt, FMT_19, FMT_14, testflag)
    u = given_output_unit (unit); if (u < 0) return
    pacified = .false.; if (present (testflag)) pacified = testflag
    tmp = prt
    if (pacified) call pacify (tmp)
    write (u, "(1x,A)", advance="no") "prt("
    select case (prt%type)
    case (PRT_UNDEFINED); write (u, "('?')", advance="no")
    case (PRT_BEAM); write (u, "('b:')", advance="no")
    case (PRT_INCOMING); write (u, "('i:~')", advance="no")
    case (PRT_OUTGOING); write (u, "('o:~')", advance="no")
    case (PRT_COMPOSITE); write (u, "('c:~')", advance="no")
    end select
    select case (prt%type)
    case (PRT_BEAM, PRT_INCOMING, PRT_OUTGOING)
      if (prt%polarized) then
        write (u, "(I0,'/',I0,'|')", advance="no") prt%pdg, prt%h
      else
        write (u, "(I0,'|')", advance="no") prt%pdg

```

```

        end if
    end select
    select case (prt%type)
    case (PRT_BEAM, PRT_INCOMING, PRT_OUTGOING, PRT_COMPOSITE)
        write (u, "(" // FMT_14 // ",',';" // FMT_14 // ",',';" // &
            FMT_14 // ",',';" // FMT_14 // ") ", advance="no") tmp%p
        write (u, "('|'," // fmt // ") ", advance="no") tmp%p2
    end select
    if (allocated (prt%src)) then
        write (u, "('|'," // fmt // ") ", advance="no")
        do i = 1, size (prt%src)
            write (u, "(1x,I0)", advance="no") prt%src(i)
        end do
    end if
    write (u, "(A)" // " ")
end subroutine prt_write

```

Tools

Two particles match if their `src` arrays are the same.

(Subevents: interfaces)+≡

```

interface operator(.match.)
    module procedure prt_match
end interface

```

(Subevents: procedures)+≡

```

elemental function prt_match (prt1, prt2) result (match)
    logical :: match
    type(prt_t), intent(in) :: prt1, prt2
    if (size (prt1%src) == size (prt2%src)) then
        match = all (prt1%src == prt2%src)
    else
        match = .false.
    end if
end function prt_match

```

The combine operation makes a pseudoparticle whose momentum is the result of adding (the momenta of) the pair of input particles. We trace the particles from which a particle is built by storing a `src` array. Each particle entry in the `src` list contains a list of indices which indicates its building blocks. The indices refer to an original list of particles. Index lists are sorted, and they contain no element more than once.

We thus require that in a given pseudoparticle, each original particle occurs at most once.

The result is `intent(inout)`, so it will not be initialized when the subroutine is entered.

(Subevents: procedures)+≡

```

subroutine prt_combine (prt, prt_in1, prt_in2, ok)
    type(prt_t), intent(inout) :: prt
    type(prt_t), intent(in) :: prt_in1, prt_in2

```



```

        end if
    end do LOOP
end subroutine combine_index_lists

```

This function is similar, but it does not actually merge the list, it just checks whether they are disjoint (no common `src` entry).

```

<Subevents: procedures>+≡
function index_lists_are_disjoint (src1, src2) result (flag)
    logical :: flag
    integer, dimension(:), intent(in) :: src1, src2
    integer :: i1, i2, i
    flag = .true.
    i1 = 1
    i2 = 1
    LOOP: do i = 1, size (src1) + size (src2)
        if (src1(i1) < src2(i2)) then
            i1 = i1 + 1
            if (i1 > size (src1)) then
                exit LOOP
            end if
        else if (src1(i1) > src2(i2)) then
            i2 = i2 + 1
            if (i2 > size (src2)) then
                exit LOOP
            end if
        else
            flag = .false.
            exit LOOP
        end if
    end do LOOP
end function index_lists_are_disjoint

```

12.4.2 subevents

Particles are collected in subevents. This type is implemented as a dynamically allocated array, which need not be completely filled. The value `n_active` determines the number of meaningful entries.

Type definition

```

<Subevents: public>+≡
    public :: subevt_t

<Subevents: types>+≡
    type :: subevt_t
    private
        integer :: n_active = 0
        type(prt_t), dimension(:), allocatable :: prt
    contains
        <Subevents: subevt: TBP>
    end type subevt_t

```

Initialize, allocating with size zero (default) or given size. The number of contained particles is set equal to the size.

```

<Subevents: public>+≡
    public :: subevt_init

<Subevents: procedures>+≡
    subroutine subevt_init (subevt, n_active)
        type(subevt_t), intent(out) :: subevt
        integer, intent(in), optional :: n_active
        if (present (n_active)) subevt%n_active = n_active
        allocate (subevt%prt (subevt%n_active))
    end subroutine subevt_init

```

(Re-)allocate the subevent with some given size. If the size is greater than the previous one, do a real reallocation. Otherwise, just reset the recorded size. Contents are untouched, but become invalid.

```

<Subevents: public>+≡
    public :: subevt_reset

<Subevents: procedures>+≡
    subroutine subevt_reset (subevt, n_active)
        type(subevt_t), intent(inout) :: subevt
        integer, intent(in) :: n_active
        subevt%n_active = n_active
        if (subevt%n_active > size (subevt%prt)) then
            deallocate (subevt%prt)
            allocate (subevt%prt (subevt%n_active))
        end if
    end subroutine subevt_reset

```

Output. No prefix for the headline 'subevt', because this will usually be printed appending to a previous line.

```

<Subevents: public>+≡
    public :: subevt_write

<Subevents: subevt: TBP>≡
    procedure :: write => subevt_write

<Subevents: procedures>+≡
    subroutine subevt_write (object, unit, prefix, pacified)
        class(subevt_t), intent(in) :: object
        integer, intent(in), optional :: unit
        character(*), intent(in), optional :: prefix
        logical, intent(in), optional :: pacified
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,A)") "subevent:"
        do i = 1, object%n_active
            if (present (prefix)) write (u, "(A)", advance="no") prefix
            write (u, "(1x,I0)", advance="no") i
            call prt_write (object%prt(i), unit = unit, testflag = pacified)
        end do
    end subroutine subevt_write

```

Defined assignment: transfer only meaningful entries. This is a deep copy (as would be default assignment).

```

<Subevents: interfaces>+≡
    interface assignment(=)
        module procedure subevt_assign
    end interface

<Subevents: procedures>+≡
    subroutine subevt_assign (subevt, subevt_in)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: subevt_in
        if (.not. allocated (subevt%prt)) then
            call subevt_init (subevt, subevt_in%n_active)
        else
            call subevt_reset (subevt, subevt_in%n_active)
        end if
        subevt%prt(:subevt%n_active) = subevt_in%prt(:subevt%n_active)
    end subroutine subevt_assign

```

Fill contents

Store incoming/outgoing particles which are completely defined.

```

<Subevents: public>+≡
    public :: subevt_set_beam
    public :: subevt_set_incoming
    public :: subevt_set_outgoing
    public :: subevt_set_composite

<Subevents: procedures>+≡
    subroutine subevt_set_beam (subevt, i, pdg, p, p2, src)
        type(subevt_t), intent(inout) :: subevt
        integer, intent(in) :: i
        integer, intent(in) :: pdg
        type(vector4_t), intent(in) :: p
        real(default), intent(in) :: p2
        integer, dimension(:), intent(in), optional :: src
        if (present (src)) then
            call prt_init_beam (subevt%prt(i), pdg, p, p2, src)
        else
            call prt_init_beam (subevt%prt(i), pdg, p, p2, [i])
        end if
    end subroutine subevt_set_beam

    subroutine subevt_set_incoming (subevt, i, pdg, p, p2, src)
        type(subevt_t), intent(inout) :: subevt
        integer, intent(in) :: i
        integer, intent(in) :: pdg
        type(vector4_t), intent(in) :: p
        real(default), intent(in) :: p2
        integer, dimension(:), intent(in), optional :: src
        if (present (src)) then
            call prt_init_incoming (subevt%prt(i), pdg, p, p2, src)

```

```

    else
        call prt_init_incoming (subevt%prt(i), pdg, p, p2, [i])
    end if
end subroutine subevt_set_incoming

subroutine subevt_set_outgoing (subevt, i, pdg, p, p2, src)
    type(subevt_t), intent(inout) :: subevt
    integer, intent(in) :: i
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in), optional :: src
    if (present (src)) then
        call prt_init_outgoing (subevt%prt(i), pdg, p, p2, src)
    else
        call prt_init_outgoing (subevt%prt(i), pdg, p, p2, [i])
    end if
end subroutine subevt_set_outgoing

subroutine subevt_set_composite (subevt, i, p, src)
    type(subevt_t), intent(inout) :: subevt
    integer, intent(in) :: i
    type(vector4_t), intent(in) :: p
    integer, dimension(:), intent(in) :: src
    call prt_init_composite (subevt%prt(i), p, src)
end subroutine subevt_set_composite

```

Separately assign flavors, simultaneously for all incoming/outgoing particles.

<Subevents: public>+≡

```

    public :: subevt_set_pdg_beam
    public :: subevt_set_pdg_incoming
    public :: subevt_set_pdg_outgoing

```

<Subevents: procedures>+≡

```

subroutine subevt_set_pdg_beam (subevt, pdg)
    type(subevt_t), intent(inout) :: subevt
    integer, dimension(:), intent(in) :: pdg
    integer :: i, j
    j = 1
    do i = 1, subevt%n_active
        if (subevt%prt(i)%type == PRT_BEAM) then
            call prt_set_pdg (subevt%prt(i), pdg(j))
            j = j + 1
            if (j > size (pdg)) exit
        end if
    end do
end subroutine subevt_set_pdg_beam

subroutine subevt_set_pdg_incoming (subevt, pdg)
    type(subevt_t), intent(inout) :: subevt
    integer, dimension(:), intent(in) :: pdg
    integer :: i, j
    j = 1
    do i = 1, subevt%n_active

```

```

        if (subevt%prt(i)%type == PRT_INCOMING) then
            call prt_set_pdg (subevt%prt(i), pdg(j))
            j = j + 1
            if (j > size (pdg)) exit
        end if
    end do
end subroutine subevt_set_pdg_incoming

subroutine subevt_set_pdg_outgoing (subevt, pdg)
    type(subevt_t), intent(inout) :: subevt
    integer, dimension(:), intent(in) :: pdg
    integer :: i, j
    j = 1
    do i = 1, subevt%n_active
        if (subevt%prt(i)%type == PRT_OUTGOING) then
            call prt_set_pdg (subevt%prt(i), pdg(j))
            j = j + 1
            if (j > size (pdg)) exit
        end if
    end do
end subroutine subevt_set_pdg_outgoing

```

Separately assign momenta, simultaneously for all incoming/outgoing particles.

<Subevents: public>+≡

```

public :: subevt_set_p_beam
public :: subevt_set_p_incoming
public :: subevt_set_p_outgoing

```

<Subevents: procedures>+≡

```

subroutine subevt_set_p_beam (subevt, p)
    type(subevt_t), intent(inout) :: subevt
    type(vector4_t), dimension(:), intent(in) :: p
    integer :: i, j
    j = 1
    do i = 1, subevt%n_active
        if (subevt%prt(i)%type == PRT_BEAM) then
            call prt_set_p (subevt%prt(i), p(j))
            j = j + 1
            if (j > size (p)) exit
        end if
    end do
end subroutine subevt_set_p_beam

subroutine subevt_set_p_incoming (subevt, p)
    type(subevt_t), intent(inout) :: subevt
    type(vector4_t), dimension(:), intent(in) :: p
    integer :: i, j
    j = 1
    do i = 1, subevt%n_active
        if (subevt%prt(i)%type == PRT_INCOMING) then
            call prt_set_p (subevt%prt(i), p(j))
            j = j + 1
            if (j > size (p)) exit
        end if
    end if
end subroutine subevt_set_p_incoming

```

```

        end do
    end subroutine subevt_set_p_incoming

    subroutine subevt_set_p_outgoing (subevt, p)
        type(subevt_t), intent(inout) :: subevt
        type(vector4_t), dimension(:), intent(in) :: p
        integer :: i, j
        j = 1
        do i = 1, subevt%n_active
            if (subevt%prt(i)%type == PRT_OUTGOING) then
                call prt_set_p (subevt%prt(i), p(j))
                j = j + 1
                if (j > size (p)) exit
            end if
        end do
    end subroutine subevt_set_p_outgoing

```

Separately assign the squared invariant mass, simultaneously for all incoming/outgoing particles.

```

<Subevents: public>+≡
    public :: subevt_set_p2_beam
    public :: subevt_set_p2_incoming
    public :: subevt_set_p2_outgoing

<Subevents: procedures>+≡
    subroutine subevt_set_p2_beam (subevt, p2)
        type(subevt_t), intent(inout) :: subevt
        real(default), dimension(:), intent(in) :: p2
        integer :: i, j
        j = 1
        do i = 1, subevt%n_active
            if (subevt%prt(i)%type == PRT_BEAM) then
                call prt_set_p2 (subevt%prt(i), p2(j))
                j = j + 1
                if (j > size (p2)) exit
            end if
        end do
    end subroutine subevt_set_p2_beam

    subroutine subevt_set_p2_incoming (subevt, p2)
        type(subevt_t), intent(inout) :: subevt
        real(default), dimension(:), intent(in) :: p2
        integer :: i, j
        j = 1
        do i = 1, subevt%n_active
            if (subevt%prt(i)%type == PRT_INCOMING) then
                call prt_set_p2 (subevt%prt(i), p2(j))
                j = j + 1
                if (j > size (p2)) exit
            end if
        end do
    end subroutine subevt_set_p2_incoming

    subroutine subevt_set_p2_outgoing (subevt, p2)

```

```

type(subvt_t), intent(inout) :: subvt
real(default), dimension(:), intent(in) :: p2
integer :: i, j
j = 1
do i = 1, subvt%n_active
  if (subvt%prt(i)%type == PRT_OUTGOING) then
    call prt_set_p2 (subvt%prt(i), p2(j))
    j = j + 1
    if (j > size (p2)) exit
  end if
end do
end subroutine subvt_set_p2_outgoing

```

Set polarization for an entry

```

<Subevents: public>+≡
  public :: subvt_polarize

<Subevents: procedures>+≡
  subroutine subvt_polarize (subvt, i, h)
    type(subvt_t), intent(inout) :: subvt
    integer, intent(in) :: i, h
    call prt_polarize (subvt%prt(i), h)
  end subroutine subvt_polarize

```

Accessing contents

Return true if the subevent has entries.

```

<Subevents: public>+≡
  public :: subvt_is_nonempty

<Subevents: procedures>+≡
  function subvt_is_nonempty (subvt) result (flag)
    logical :: flag
    type(subvt_t), intent(in) :: subvt
    flag = subvt%n_active /= 0
  end function subvt_is_nonempty

```

Return the number of entries

```

<Subevents: public>+≡
  public :: subvt_get_length

<Subevents: procedures>+≡
  function subvt_get_length (subvt) result (length)
    integer :: length
    type(subvt_t), intent(in) :: subvt
    length = subvt%n_active
  end function subvt_get_length

```

Return a specific particle. The index is not checked for validity.

```

<Subevents: public>+≡
  public :: subvt_get_prt

```

```

<Subevents: procedures>+≡
function subevt_get_prt (subevt, i) result (prt)
  type(prt_t) :: prt
  type(subevt_t), intent(in) :: subevt
  integer, intent(in) :: i
  prt = subevt%prt(i)
end function subevt_get_prt

```

Return the partonic energy squared. We take the particles with flag PRT_INCOMING and compute their total invariant mass.

```

<Subevents: public>+≡
public :: subevt_get_sqrts_hat

<Subevents: procedures>+≡
function subevt_get_sqrts_hat (subevt) result (sqrts_hat)
  type(subevt_t), intent(in) :: subevt
  real(default) :: sqrts_hat
  type(vector4_t) :: p
  integer :: i
  do i = 1, subevt%n_active
    if (subevt%prt(i)%type == PRT_INCOMING) then
      p = p + prt_get_momentum (subevt%prt(i))
    end if
  end do
  sqrts_hat = p ** 1
end function subevt_get_sqrts_hat

```

Return the number of incoming (outgoing) particles, respectively. Beam particles or composites are not counted.

```

<Subevents: public>+≡
public :: subevt_get_n_in
public :: subevt_get_n_out

<Subevents: procedures>+≡
function subevt_get_n_in (subevt) result (n_in)
  type(subevt_t), intent(in) :: subevt
  integer :: n_in
  n_in = count (subevt%prt(:subevt%n_active)%type == PRT_INCOMING)
end function subevt_get_n_in

function subevt_get_n_out (subevt) result (n_out)
  type(subevt_t), intent(in) :: subevt
  integer :: n_out
  n_out = count (subevt%prt(:subevt%n_active)%type == PRT_OUTGOING)
end function subevt_get_n_out

```

```

<Subevents: interfaces>+≡
interface c_prt
  module procedure c_prt_from_subevt
  module procedure c_prt_array_from_subevt
end interface

```



```

<Subevents: procedures>+≡
function c_prt_from_subevt (subevt, i) result (c_prt)
  type(c_prt_t) :: c_prt
  type(subevt_t), intent(in) :: subevt
  integer, intent(in) :: i
  c_prt = c_prt_from_prt (subevt%prt(i))
end function c_prt_from_subevt

function c_prt_array_from_subevt (subevt) result (c_prt_array)
  type(subevt_t), intent(in) :: subevt
  type(c_prt_t), dimension(subevt%n_active) :: c_prt_array
  c_prt_array = c_prt_from_prt (subevt%prt(1:subevt%n_active))
end function c_prt_array_from_subevt

```

Operations with subevents

The join operation joins two subevents. When appending the elements of the second list, we check for each particle whether it is already in the first list. If yes, it is discarded. The result list should be initialized already.

If a mask is present, it refers to the second subevent. Particles where the mask is not set are discarded.

```

<Subevents: public>+≡
public :: subevt_join

<Subevents: procedures>+≡
subroutine subevt_join (subevt, pl1, pl2, mask2)
  type(subevt_t), intent(inout) :: subevt
  type(subevt_t), intent(in) :: pl1, pl2
  logical, dimension(:), intent(in), optional :: mask2
  integer :: n1, n2, i, n
  n1 = pl1%n_active
  n2 = pl2%n_active
  call subevt_reset (subevt, n1 + n2)
  subevt%prt(:n1) = pl1%prt(:n1)
  n = n1
  if (present (mask2)) then
    do i = 1, pl2%n_active
      if (mask2(i)) then
        if (disjoint (i)) then
          n = n + 1
          subevt%prt(n) = pl2%prt(i)
        end if
      end if
    end do
  else
    do i = 1, pl2%n_active
      if (disjoint (i)) then
        n = n + 1
        subevt%prt(n) = pl2%prt(i)
      end if
    end do
  end if
  subevt%n_active = n

```

```

contains
  function disjoint (i) result (flag)
    integer, intent(in) :: i
    logical :: flag
    integer :: j
    do j = 1, pl1%n_active
      if (.not. are_disjoint (pl1%prt(j), pl2%prt(i))) then
        flag = .false.
        return
      end if
    end do
    flag = .true.
  end function disjoint
end subroutine subevt_join

```

The combine operation makes a subevent whose entries are the result of adding (the momenta of) each pair of particles in the input lists. We trace the particles from which a particle is built by storing a `src` array. Each particle entry in the `src` list contains a list of indices which indicates its building blocks. The indices refer to an original list of particles. Index lists are sorted, and they contain no element more than once.

We thus require that in a given pseudoparticle, each original particle occurs at most once.

<Subevents: public>+≡

```
public :: subevt_combine
```

<Subevents: procedures>+≡

```

subroutine subevt_combine (subevt, pl1, pl2, mask12)
  type(subevt_t), intent(inout) :: subevt
  type(subevt_t), intent(in) :: pl1, pl2
  logical, dimension(:,,:), intent(in), optional :: mask12
  integer :: n1, n2, i1, i2, n, j
  logical :: ok
  n1 = pl1%n_active
  n2 = pl2%n_active
  call subevt_reset (subevt, n1 * n2)
  n = 1
  do i1 = 1, n1
    do i2 = 1, n2
      if (present (mask12)) then
        ok = mask12(i1,i2)
      else
        ok = .true.
      end if
      if (ok) call prt_combine &
        (subevt%prt(n), pl1%prt(i1), pl2%prt(i2), ok)
      if (ok) then
        CHECK_DOUBLES: do j = 1, n - 1
          if (subevt%prt(n) .match. subevt%prt(j)) then
            ok = .false.; exit CHECK_DOUBLES
          end if
        end do CHECK_DOUBLES
        if (ok) n = n + 1
      end if
    end do
  end do

```

```

        end if
    end do
end do
subevt%n_active = n - 1
end subroutine subevt_combine

```

The collect operation makes a single-entry subevent which results from combining (the momenta of) all particles in the input list. As above, the result does not contain an original particle more than once; this is checked for each particle when it is collected. Furthermore, each entry has a mask; where the mask is false, the entry is dropped.

(Thus, if the input particles are already composite, there is some chance that the result depends on the order of the input list and is not as expected. This situation should be avoided.)

```

<Subevents: public>+≡
    public :: subevt_collect

<Subevents: procedures>+≡
    subroutine subevt_collect (subevt, pl1, mask1)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl1
        logical, dimension(:), intent(in) :: mask1
        type(prt_t) :: prt
        integer :: i
        logical :: ok
        call subevt_reset (subevt, 1)
        subevt%n_active = 0
        do i = 1, pl1%n_active
            if (mask1(i)) then
                if (subevt%n_active == 0) then
                    subevt%n_active = 1
                    subevt%prt(1) = pl1%prt(i)
                else
                    call prt_combine (prt, subevt%prt(1), pl1%prt(i), ok)
                    if (ok) subevt%prt(1) = prt
                end if
            end if
        end do
    end subroutine subevt_collect

```

The cluster operation is similar to `collect`, but applies a jet algorithm. The result is a subevent consisting of jets and, possibly, unclustered extra particles. As above, the result does not contain an original particle more than once; this is checked for each particle when it is collected. Furthermore, each entry has a mask; where the mask is false, the entry is dropped.

The algorithm: first determine the (pseudo)particles that participate in the clustering. They should not overlap, and the mask entry must be set. We then cluster the particles, using the given jet definition. The result particles are retrieved from the cluster sequence. We still have to determine the source indices for each jet: for each input particle, we get the jet index. Accumulating the source entries for all particles that are part of a given jet, we derive the jet

source entries. Finally, we delete the C structures that have been constructed by FastJet and its interface.

```

<Subevents: public>+≡
    public :: subevt_cluster

<Subevents: procedures>+≡
    subroutine subevt_cluster (subevt, pl1, mask1, jet_def)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl1
        logical, dimension(:), intent(in) :: mask1
        type(jet_definition_t), intent(in) :: jet_def
        integer, dimension(:), allocatable :: src, src_tmp
        integer, dimension(:), allocatable :: map, jet_idx
        type(pseudojet_t), dimension(:), allocatable :: jet_in, jet_out
        type(pseudojet_vector_t) :: jv_in, jv_out
        type(cluster_sequence_t) :: cs
        integer :: i, j, k, n_src, n_active
        n_active = 0
        allocate (map (pl1%n_active), source = 0)
        allocate (src (0))
        do i = 1, pl1%n_active
            if (mask1(i)) then
                call combine_index_lists (src_tmp, src, pl1%prt(i)%src)
                if (allocated (src_tmp)) then
                    call move_alloc (from=src_tmp, to=src)
                    n_active = n_active + 1
                    map(n_active) = i
                end if
            end if
        end do
        allocate (jet_in (count (map /= 0)))
        do i = 1, size (jet_in)
            call jet_in(i)%init (prt_get_momentum (pl1%prt(map(i))))
        end do
        call jv_in%init (jet_in)
        call cs%init (jv_in, jet_def)
        jv_out = cs%inclusive_jets ()
        allocate (jet_idx (size (jet_in)))
        call cs%assign_jet_indices (jv_out, jet_idx)
        allocate (jet_out (jv_out%size ()))
        jet_out = jv_out
        call subevt_reset (subevt, size (jet_out))
        do i = 1, size (jet_out)
            src = 0
            n_src = 0
            do j = 1, size (jet_idx)
                if (jet_idx(j) == i) then
                    associate (prt => pl1%prt(map(j)))
                        do k = 1, size (prt%src)
                            src(n_src + k) = prt%src(k)
                        end do
                        n_src = n_src + size (prt%src)
                    end associate
                end if
            end do
        end do
    end subroutine

```

```

        end do
        call prt_init_pseudojet (subevt%prt(i), jet_out(i), src(:n_src))
    end do
    do i = 1, size (jet_out)
        call jet_out(i)%final ()
    end do
    call jv_out%final ()
    call cs%final ()
    call jv_in%final ()
    do i = 1, size (jet_in)
        call jet_in(i)%final ()
    end do
end subroutine subevt_cluster

```

Return a list of all particles for which the mask is true.

```

<Subevents: public>+≡
    public :: subevt_select

<Subevents: procedures>+≡
    subroutine subevt_select (subevt, pl, mask1)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl
        logical, dimension(:), intent(in) :: mask1
        integer :: i, n
        call subevt_reset (subevt, pl%n_active)
        n = 0
        do i = 1, pl%n_active
            if (mask1(i)) then
                n = n + 1
                subevt%prt(n) = pl%prt(i)
            end if
        end do
        subevt%n_active = n
    end subroutine subevt_select

```

Return a subevent which consists of the single particle with specified `index`. If `index` is negative, count from the end. If it is out of bounds, return an empty list.

```

<Subevents: public>+≡
    public :: subevt_extract

<Subevents: procedures>+≡
    subroutine subevt_extract (subevt, pl, index)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl
        integer, intent(in) :: index
        if (index > 0) then
            if (index <= pl%n_active) then
                call subevt_reset (subevt, 1)
                subevt%prt(1) = pl%prt(index)
            else
                call subevt_reset (subevt, 0)
            end if
        else if (index < 0) then

```

```

        if (abs (index) <= pl%n_active) then
            call subevt_reset (subevt, 1)
            subevt%prt(1) = pl%prt(pl%n_active + 1 + index)
        else
            call subevt_reset (subevt, 0)
        end if
    else
        call subevt_reset (subevt, 0)
    end if
end subroutine subevt_extract

```

Return the list of particles sorted according to increasing values of the provided integer or real array. If no array is given, sort by PDG value.

<Subevents: public>+≡

```
public :: subevt_sort
```

<Subevents: interfaces>+≡

```

interface subevt_sort
    module procedure subevt_sort_pdg
    module procedure subevt_sort_int
    module procedure subevt_sort_real
end interface

```

<Subevents: procedures>+≡

```

subroutine subevt_sort_pdg (subevt, pl)
    type(subevt_t), intent(inout) :: subevt
    type(subevt_t), intent(in) :: pl
    integer :: n
    n = subevt%n_active
    call subevt_sort_int (subevt, pl, abs (3 * subevt%prt(:n)%pdg - 1))
end subroutine subevt_sort_pdg

```

```

subroutine subevt_sort_int (subevt, pl, ival)
    type(subevt_t), intent(inout) :: subevt
    type(subevt_t), intent(in) :: pl
    integer, dimension(:), intent(in) :: ival
    call subevt_reset (subevt, pl%n_active)
    subevt%n_active = pl%n_active
    subevt%prt = pl%prt( order (ival) )
end subroutine subevt_sort_int

```

```

subroutine subevt_sort_real (subevt, pl, rval)
    type(subevt_t), intent(inout) :: subevt
    type(subevt_t), intent(in) :: pl
    real(default), dimension(:), intent(in) :: rval
    call subevt_reset (subevt, pl%n_active)
    subevt%n_active = pl%n_active
    subevt%prt = pl%prt( order (rval) )
end subroutine subevt_sort_real

```

Return the list of particles which have any of the specified PDG codes (and optionally particle type: beam, incoming, outgoing).

The `pack` command was buggy in some gfortran versions, therefore it is unrolled. The unrolled version may be more efficient, actually.

```

<Subevents: public>+≡
    public :: subevt_select_pdg_code

<Subevents: procedures>+≡
    subroutine subevt_select_pdg_code (subevt, aval, subevt_in, prt_type)
        type(subevt_t), intent(inout) :: subevt
        type(pdg_array_t), intent(in) :: aval
        type(subevt_t), intent(in) :: subevt_in
        integer, intent(in), optional :: prt_type
        integer :: n_active, n_match
        logical, dimension(:), allocatable :: mask
        integer :: i, j
        n_active = subevt_in%n_active
        allocate (mask (n_active))
        forall (i = 1:n_active) &
            mask(i) = aval .match. subevt_in%prt(i)%pdg
        if (present (prt_type)) &
            mask = mask .and. subevt_in%prt(:n_active)%type == prt_type
        n_match = count (mask)
        call subevt_reset (subevt, n_match)
        !!! !!! !!! Workaround for gfortran compiler bug
        ! subevt%prt(:n_match) = pack (subevt_in%prt(:n_active), mask)
        j = 0
        do i = 1, n_active
            if (mask(i)) then
                j = j + 1
                subevt%prt(j) = subevt_in%prt(i)
            end if
        end do
    end subroutine subevt_select_pdg_code

```

12.4.3 Eliminate numerical noise

This is useful for testing purposes: set entries to zero that are smaller in absolute values than a given tolerance parameter.

Note: instead of setting the tolerance in terms of `EPSILON` (kind-dependent), we fix it to 10^{-16} , which is the typical value for double precision. The reason is that there are situations where intermediate representations (external libraries, files) are limited to double precision, even if the main program uses higher precision.

```

<Subevents: public>+≡
    public :: pacify

<Subevents: interfaces>+≡
    interface pacify
        module procedure pacify_prt
        module procedure pacify_subevt
    end interface pacify

```

```

<Subevents: procedures>+≡
subroutine pacify_prt (prt)
  class(prt_t), intent(inout) :: prt
  real(default) :: e
  e = max (1E-10_default * energy (prt%p), 1E-13_default)
  call pacify (prt%p, e)
  call pacify (prt%p2, 1E3_default * e)
end subroutine pacify_prt

subroutine pacify_subevt (subevt)
  class(subevt_t), intent(inout) :: subevt
  integer :: i
  do i = 1, subevt%n_active
    call pacify (subevt%prt(i))
  end do
end subroutine pacify_subevt

```


12.5 Analysis tools

This module defines structures useful for data analysis. These include observables, histograms, and plots.

Observables are quantities that are calculated and summed up event by event. At the end, one can compute the average and error.

Histograms have their bins in addition to the observable properties. Histograms are usually written out in tables and displayed graphically.

In plots, each record creates its own entry in a table. This can be used for scatter plots if called event by event, or for plotting dependencies on parameters if called once per integration run.

Graphs are container for histograms and plots, which carry their own graphics options.

The type layout is still somewhat obfuscated. This would become much simpler if type extension could be used.

```
<analysis.f90>≡
  <File header>

  module analysis

    <Use kinds>
    <Use strings>
    use io_units
    use format_utils, only: quote_underscore, tex_format
    use format_defs, only: FMT_19
    use system_defs, only: TAB
    use unit_tests
    use diagnostics
    use os_interface
    use ifiles

    <Standard module head>

    <Analysis: public>

    <Analysis: parameters>

    <Analysis: types>

    <Analysis: interfaces>

    <Analysis: variables>

    contains

    <Analysis: procedures>

    <Analysis: tests>

  end module analysis
```

12.5.1 Output formats

These formats share a common field width (alignment).

```
<Analysis: parameters>≡
    character(*), parameter, public :: HISTOGRAM_HEAD_FORMAT = "1x,A15,3x"
    character(*), parameter, public :: HISTOGRAM_INTG_FORMAT = "3x,I9,3x"
    character(*), parameter, public :: HISTOGRAM_DATA_FORMAT = "ES19.12"
```

12.5.2 Graph options

These parameters are used for displaying data. They apply to a whole graph, which may contain more than one plot element.

The GAMELAN code chunks are part of both `graph_options` and `drawing_options`. The `drawing_options` copy is used in histograms and plots, also as graph elements. The `graph_options` copy is used for `graph` objects as a whole. Both copies are usually identical.

```
<Analysis: public>≡
    public :: graph_options_t

<Analysis: types>≡
    type :: graph_options_t
    private
    type(string_t) :: id
    type(string_t) :: title
    type(string_t) :: description
    type(string_t) :: x_label
    type(string_t) :: y_label
    integer :: width_mm = 130
    integer :: height_mm = 90
    logical :: x_log = .false.
    logical :: y_log = .false.
    real(default) :: x_min = 0
    real(default) :: x_max = 1
    real(default) :: y_min = 0
    real(default) :: y_max = 1
    logical :: x_min_set = .false.
    logical :: x_max_set = .false.
    logical :: y_min_set = .false.
    logical :: y_max_set = .false.
    type(string_t) :: gmlcode_bg
    type(string_t) :: gmlcode_fg
end type graph_options_t
```

Initialize the record, all strings are empty. The limits are undefined.

```
<Analysis: public>+≡
    public :: graph_options_init

<Analysis: procedures>≡
    subroutine graph_options_init (graph_options)
        type(graph_options_t), intent(out) :: graph_options
        graph_options%id = ""
        graph_options%title = ""
```

```

graph_options%description = ""
graph_options%x_label = ""
graph_options%y_label = ""
graph_options%gmlcode_bg = ""
graph_options%gmlcode_fg = ""
end subroutine graph_options_init

```

Set individual options.

```

<Analysis: public>+≡
public :: graph_options_set

<Analysis: procedures>+≡
subroutine graph_options_set (graph_options, id, &
    title, description, x_label, y_label, width_mm, height_mm, &
    x_log, y_log, x_min, x_max, y_min, y_max, &
    gmlcode_bg, gmlcode_fg)
    type(graph_options_t), intent(inout) :: graph_options
    type(string_t), intent(in), optional :: id
    type(string_t), intent(in), optional :: title
    type(string_t), intent(in), optional :: description
    type(string_t), intent(in), optional :: x_label, y_label
    integer, intent(in), optional :: width_mm, height_mm
    logical, intent(in), optional :: x_log, y_log
    real(default), intent(in), optional :: x_min, x_max, y_min, y_max
    type(string_t), intent(in), optional :: gmlcode_bg, gmlcode_fg
    if (present (id)) graph_options%id = id
    if (present (title)) graph_options%title = title
    if (present (description)) graph_options%description = description
    if (present (x_label)) graph_options%x_label = x_label
    if (present (y_label)) graph_options%y_label = y_label
    if (present (width_mm)) graph_options%width_mm = width_mm
    if (present (height_mm)) graph_options%height_mm = height_mm
    if (present (x_log)) graph_options%x_log = x_log
    if (present (y_log)) graph_options%y_log = y_log
    if (present (x_min)) graph_options%x_min = x_min
    if (present (x_max)) graph_options%x_max = x_max
    if (present (y_min)) graph_options%y_min = y_min
    if (present (y_max)) graph_options%y_max = y_max
    if (present (x_min)) graph_options%x_min_set = .true.
    if (present (x_max)) graph_options%x_max_set = .true.
    if (present (y_min)) graph_options%y_min_set = .true.
    if (present (y_max)) graph_options%y_max_set = .true.
    if (present (gmlcode_bg)) graph_options%gmlcode_bg = gmlcode_bg
    if (present (gmlcode_fg)) graph_options%gmlcode_fg = gmlcode_fg
end subroutine graph_options_set

```

Write a simple account of all options.

```

<Analysis: public>+≡
public :: graph_options_write

<Analysis: procedures>+≡
subroutine graph_options_write (gro, unit)
    type(graph_options_t), intent(in) :: gro
    integer, intent(in), optional :: unit

```

```

integer :: u
u = given_output_unit (unit)
1 format (A,1x,'"',A,'"')
2 format (A,1x,L1)
3 format (A,1x,ES19.12)
4 format (A,1x,I0)
5 format (A,1x,'[undefined]')
write (u, 1) "title      =", char (gro%title)
write (u, 1) "description =", char (gro%description)
write (u, 1) "x_label    =", char (gro%x_label)
write (u, 1) "y_label    =", char (gro%y_label)
write (u, 2) "x_log      =", gro%x_log
write (u, 2) "y_log      =", gro%y_log
if (gro%x_min_set) then
    write (u, 3) "x_min      =", gro%x_min
else
    write (u, 5) "x_min      ="
end if
if (gro%x_max_set) then
    write (u, 3) "x_max      =", gro%x_max
else
    write (u, 5) "x_max      ="
end if
if (gro%y_min_set) then
    write (u, 3) "y_min      =", gro%y_min
else
    write (u, 5) "y_min      ="
end if
if (gro%y_max_set) then
    write (u, 3) "y_max      =", gro%y_max
else
    write (u, 5) "y_max      ="
end if
write (u, 4) "width_mm   =", gro%width_mm
write (u, 4) "height_mm  =", gro%height_mm
write (u, 1) "gmlcode_bg =", char (gro%gmlcode_bg)
write (u, 1) "gmlcode_fg =", char (gro%gmlcode_fg)
end subroutine graph_options_write

```

Write a L^AT_EX header/footer for the analysis file.

```

<Analysis: procedures>+≡
subroutine graph_options_write_tex_header (gro, unit)
type(graph_options_t), intent(in) :: gro
integer, intent(in), optional :: unit
integer :: u
u = given_output_unit (unit)
if (gro%title /= "") then
    write (u, "(A)")
    write (u, "(A)") "\section{" // char (gro%title) // "}"
else
    write (u, "(A)") "\section{" // char (quote_underscore (gro%id)) // "}"
end if
if (gro%description /= "") then

```

```

        write (u, "(A)") char (gro%description)
        write (u, *)
        write (u, "(A)") "\vspace*{\baselineskip}"
    end if
    write (u, "(A)") "\vspace*{\baselineskip}"
    write (u, "(A)") "\unitlength 1mm"
    write (u, "(A,IO,',',IO,A)") &
        "\begin{gmlgraph*}(", &
        gro%width_mm, gro%height_mm, &
        ")[dat]"
end subroutine graph_options_write_tex_header

subroutine graph_options_write_tex_footer (gro, unit)
    type(graph_options_t), intent(in) :: gro
    integer, intent(in), optional :: unit
    integer :: u, width, height
    width = gro%width_mm - 10
    height = gro%height_mm - 10
    u = given_output_unit (unit)
    write (u, "(A)") " begingmleps " "Whizard-Logo.eps";"
    write (u, "(A,IO,A,IO,A)") &
        " base := (" , width, "*unitlength," , height, "*unitlength);"
    write (u, "(A)") " height := 9.6*unitlength;"
    write (u, "(A)") " width := 11.2*unitlength;"
    write (u, "(A)") " endgmleps;"
    write (u, "(A)") "\end{gmlgraph*}"
end subroutine graph_options_write_tex_footer

```

Return the analysis object ID.

```

<Analysis: procedures>+≡
function graph_options_get_id (gro) result (id)
    type(string_t) :: id
    type(graph_options_t), intent(in) :: gro
    id = gro%id
end function graph_options_get_id

```

Create an appropriate `setup` command (linear/log).

```

<Analysis: procedures>+≡
function graph_options_get_gml_setup (gro) result (cmd)
    type(string_t) :: cmd
    type(graph_options_t), intent(in) :: gro
    type(string_t) :: x_str, y_str
    if (gro%x_log) then
        x_str = "log"
    else
        x_str = "linear"
    end if
    if (gro%y_log) then
        y_str = "log"
    else
        y_str = "linear"
    end if
    cmd = "setup (" // x_str // ", " // y_str // ");"
end function graph_options_get_gml_setup

```

```
end function graph_options_get_gml_setup
```

Return the labels in GAMELAN form.

(Analysis: procedures)+≡

```
function graph_options_get_gml_x_label (gro) result (cmd)
  type(string_t) :: cmd
  type(graph_options_t), intent(in) :: gro
  cmd = 'label.bot (<' // '<' // gro%x_label // '>' // '>', out);'
end function graph_options_get_gml_x_label

function graph_options_get_gml_y_label (gro) result (cmd)
  type(string_t) :: cmd
  type(graph_options_t), intent(in) :: gro
  cmd = 'label.ulft (<' // '<' // gro%y_label // '>' // '>', out);'
end function graph_options_get_gml_y_label
```

Create an appropriate **graphrange** statement for the given graph options. Where the graph options are not set, use the supplied arguments, if any, otherwise set the undefined value.

(Analysis: procedures)+≡

```
function graph_options_get_gml_graphrange &
  (gro, x_min, x_max, y_min, y_max) result (cmd)
  type(string_t) :: cmd
  type(graph_options_t), intent(in) :: gro
  real(default), intent(in), optional :: x_min, x_max, y_min, y_max
  type(string_t) :: x_min_str, x_max_str, y_min_str, y_max_str
  character(*), parameter :: fmt = "(ES15.8)"
  if (gro%x_min_set) then
    x_min_str = "#" // trim (adjustl (real2string (gro%x_min, fmt)))
  else if (present (x_min)) then
    x_min_str = "#" // trim (adjustl (real2string (x_min, fmt)))
  else
    x_min_str = "???"
  end if
  if (gro%x_max_set) then
    x_max_str = "#" // trim (adjustl (real2string (gro%x_max, fmt)))
  else if (present (x_max)) then
    x_max_str = "#" // trim (adjustl (real2string (x_max, fmt)))
  else
    x_max_str = "???"
  end if
  if (gro%y_min_set) then
    y_min_str = "#" // trim (adjustl (real2string (gro%y_min, fmt)))
  else if (present (y_min)) then
    y_min_str = "#" // trim (adjustl (real2string (y_min, fmt)))
  else
    y_min_str = "???"
  end if
  if (gro%y_max_set) then
    y_max_str = "#" // trim (adjustl (real2string (gro%y_max, fmt)))
  else if (present (y_max)) then
    y_max_str = "#" // trim (adjustl (real2string (y_max, fmt)))
  else
    y_max_str = "???"
  end if
```

```

        y_max_str = "??"
    end if
    cmd = "graphrange (" // x_min_str // ", " // y_min_str // "), " &
        // "(" // x_max_str // ", " // y_max_str // ");"
end function graph_options_get_gml_graphrange

```

Get extra GAMELAN code to be executed before and after the usual drawing commands.

```

<Analysis: procedures>+≡
function graph_options_get_gml_bg_command (gro) result (cmd)
    type(string_t) :: cmd
    type(graph_options_t), intent(in) :: gro
    cmd = gro%gmlcode_bg
end function graph_options_get_gml_bg_command

function graph_options_get_gml_fg_command (gro) result (cmd)
    type(string_t) :: cmd
    type(graph_options_t), intent(in) :: gro
    cmd = gro%gmlcode_fg
end function graph_options_get_gml_fg_command

```

Append the header for generic data output in ifile format. We print only labels, not graphics parameters.

```

<Analysis: procedures>+≡
subroutine graph_options_get_header (pl, header, comment)
    type(graph_options_t), intent(in) :: pl
    type(ifile_t), intent(inout) :: header
    type(string_t), intent(in), optional :: comment
    type(string_t) :: c
    if (present (comment)) then
        c = comment
    else
        c = ""
    end if
    call ifile_append (header, &
        c // "ID: " // pl%id)
    call ifile_append (header, &
        c // "title: " // pl%title)
    call ifile_append (header, &
        c // "description: " // pl%description)
    call ifile_append (header, &
        c // "x axis label: " // pl%x_label)
    call ifile_append (header, &
        c // "y axis label: " // pl%y_label)
end subroutine graph_options_get_header

```

12.5.3 Drawing options

These options apply to an individual graph element (histogram or plot).

```

<Analysis: public>+≡
public :: drawing_options_t

```

```

<Analysis: types>+=
type :: drawing_options_t
    type(string_t) :: dataset
    logical :: with_hbars = .false.
    logical :: with_base = .false.
    logical :: piecewise = .false.
    logical :: fill = .false.
    logical :: draw = .false.
    logical :: err = .false.
    logical :: symbols = .false.
    type(string_t) :: fill_options
    type(string_t) :: draw_options
    type(string_t) :: err_options
    type(string_t) :: symbol
    type(string_t) :: gmlcode_bg
    type(string_t) :: gmlcode_fg
end type drawing_options_t

```

Write a simple account of all options.

```

<Analysis: public>+=
public :: drawing_options_write

<Analysis: procedures>+=
subroutine drawing_options_write (dro, unit)
    type(drawing_options_t), intent(in) :: dro
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
1  format (A,1x,'"',A,'"')
2  format (A,1x,L1)
    write (u, 2) "with_hbars =", dro%with_hbars
    write (u, 2) "with_base  =", dro%with_base
    write (u, 2) "piecewise =", dro%piecewise
    write (u, 2) "fill      =", dro%fill
    write (u, 2) "draw      =", dro%draw
    write (u, 2) "err       =", dro%err
    write (u, 2) "symbols   =", dro%symbols
    write (u, 1) "fill_options=", char (dro%fill_options)
    write (u, 1) "draw_options=", char (dro%draw_options)
    write (u, 1) "err_options =", char (dro%err_options)
    write (u, 1) "symbol     =", char (dro%symbol)
    write (u, 1) "gmlcode_bg =", char (dro%gmlcode_bg)
    write (u, 1) "gmlcode_fg =", char (dro%gmlcode_fg)
end subroutine drawing_options_write

```

Init with empty strings and default options, appropriate for either histogram or plot.

```

<Analysis: public>+=
public :: drawing_options_init_histogram
public :: drawing_options_init_plot

<Analysis: procedures>+=
subroutine drawing_options_init_histogram (dro)
    type(drawing_options_t), intent(out) :: dro

```



```

dro%dataset = "dat"
dro%with_hbars = .true.
dro%with_base = .true.
dro%piecewise = .true.
dro%fill = .true.
dro%draw = .true.
dro%fill_options = "withcolor col.default"
dro%draw_options = ""
dro%err_options = ""
dro%symbol = "fshape(circle scaled 1mm())"
dro%gmlcode_bg = ""
dro%gmlcode_fg = ""
end subroutine drawing_options_init_histogram

```

```

subroutine drawing_options_init_plot (dro)
  type(drawing_options_t), intent(out) :: dro
  dro%dataset = "dat"
  dro%draw = .true.
  dro%fill_options = "withcolor col.default"
  dro%draw_options = ""
  dro%err_options = ""
  dro%symbol = "fshape(circle scaled 1mm())"
  dro%gmlcode_bg = ""
  dro%gmlcode_fg = ""
end subroutine drawing_options_init_plot

```

Set individual options.

<Analysis: public>+≡

```
public :: drawing_options_set
```

<Analysis: procedures>+≡

```

subroutine drawing_options_set (dro, dataset, &
  with_hbars, with_base, piecewise, fill, draw, err, symbols, &
  fill_options, draw_options, err_options, symbol, &
  gmlcode_bg, gmlcode_fg)
  type(drawing_options_t), intent(inout) :: dro
  type(string_t), intent(in), optional :: dataset
  logical, intent(in), optional :: with_hbars, with_base, piecewise
  logical, intent(in), optional :: fill, draw, err, symbols
  type(string_t), intent(in), optional :: fill_options, draw_options
  type(string_t), intent(in), optional :: err_options, symbol
  type(string_t), intent(in), optional :: gmlcode_bg, gmlcode_fg
  if (present (dataset)) dro%dataset = dataset
  if (present (with_hbars)) dro%with_hbars = with_hbars
  if (present (with_base)) dro%with_base = with_base
  if (present (piecewise)) dro%piecewise = piecewise
  if (present (fill)) dro%fill = fill
  if (present (draw)) dro%draw = draw
  if (present (err)) dro%err = err
  if (present (symbols)) dro%symbols = symbols
  if (present (fill_options)) dro%fill_options = fill_options
  if (present (draw_options)) dro%draw_options = draw_options
  if (present (err_options)) dro%err_options = err_options
  if (present (symbol)) dro%symbol = symbol

```

```

    if (present (gmlcode_bg)) dro%gmlcode_bg = gmlcode_bg
    if (present (gmlcode_fg)) dro%gmlcode_fg = gmlcode_fg
end subroutine drawing_options_set

```

There are separate commands for drawing the curve and for drawing errors. The symbols are applied to the latter. First of all, we may have to compute a baseline:

(Analysis: procedures)+≡

```

function drawing_options_get_calc_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  if (dro%with_base) then
    cmd = "calculate " // dro%dataset // ".base (" // dro%dataset // ") " &
      // "(x, #0);"
  else
    cmd = ""
  end if
end function drawing_options_get_calc_command

```

Return the drawing command.

(Analysis: procedures)+≡

```

function drawing_options_get_draw_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  if (dro%fill) then
    cmd = "fill"
  else if (dro%draw) then
    cmd = "draw"
  else
    cmd = ""
  end if
  if (dro%fill .or. dro%draw) then
    if (dro%piecewise) cmd = cmd // " piecewise"
    if (dro%draw .and. dro%with_base) cmd = cmd // " cyclic"
    cmd = cmd // " from (" // dro%dataset
    if (dro%with_base) then
      if (dro%piecewise) then
        cmd = cmd // ", " // dro%dataset // ".base\" ! "
      else
        cmd = cmd // " ~ " // dro%dataset // ".base\" ! "
      end if
    end if
    cmd = cmd // ")"
    if (dro%fill) then
      cmd = cmd // " " // dro%fill_options
      if (dro%draw) cmd = cmd // " outlined"
    end if
    if (dro%draw) cmd = cmd // " " // dro%draw_options
    cmd = cmd // ";"
  end if
end function drawing_options_get_draw_command

```

The error command draws error bars, if any.

```

<Analysis: procedures>+≡
function drawing_options_get_err_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  if (dro%err) then
    cmd = "draw piecewise " &
      // "from (" // dro%dataset // ".err)" &
      // " " // dro%err_options // ";"
  else
    cmd = ""
  end if
end function drawing_options_get_err_command

```

The symbol command draws symbols, if any.

```

<Analysis: procedures>+≡
function drawing_options_get_symb_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  if (dro%symbols) then
    cmd = "phantom" &
      // " from (" // dro%dataset // ")" &
      // " withsymbol (" // dro%symbol // ");"
  else
    cmd = ""
  end if
end function drawing_options_get_symb_command

```

Get extra GAMELAN code to be executed before and after the usual drawing commands.

```

<Analysis: procedures>+≡
function drawing_options_get_gml_bg_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  cmd = dro%gmlcode_bg
end function drawing_options_get_gml_bg_command

function drawing_options_get_gml_fg_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  cmd = dro%gmlcode_fg
end function drawing_options_get_gml_fg_command

```

12.5.4 Observables

The observable type holds the accumulated observable values and weight sums which are necessary for proper averaging.

```

<Analysis: types>+≡
type :: observable_t
  private
  real(default) :: sum_values = 0

```

```

    real(default) :: sum_squared_values = 0
    real(default) :: sum_weights = 0
    real(default) :: sum_squared_weights = 0
    integer :: count = 0
    type(string_t) :: obs_label
    type(string_t) :: obs_unit
    type(graph_options_t) :: graph_options
end type observable_t

```

Initialize with defined properties

<Analysis: procedures>+≡

```

subroutine observable_init (obs, obs_label, obs_unit, graph_options)
    type(observable_t), intent(out) :: obs
    type(string_t), intent(in), optional :: obs_label, obs_unit
    type(graph_options_t), intent(in), optional :: graph_options
    if (present (obs_label)) then
        obs%obs_label = obs_label
    else
        obs%obs_label = ""
    end if
    if (present (obs_unit)) then
        obs%obs_unit = obs_unit
    else
        obs%obs_unit = ""
    end if
    if (present (graph_options)) then
        obs%graph_options = graph_options
    else
        call graph_options_init (obs%graph_options)
    end if
end subroutine observable_init

```

Reset all numeric entries.

<Analysis: procedures>+≡

```

subroutine observable_clear (obs)
    type(observable_t), intent(inout) :: obs
    obs%sum_values = 0
    obs%sum_squared_values = 0
    obs%sum_weights = 0
    obs%sum_squared_weights = 0
    obs%count = 0
end subroutine observable_clear

```

Record a a value. Always successful for observables.

<Analysis: interfaces>≡

```

interface observable_record_value
    module procedure observable_record_value_unweighted
    module procedure observable_record_value_weighted
end interface

```

<Analysis: procedures>+≡

```

subroutine observable_record_value_unweighted (obs, value, success)

```

```

type(observable_t), intent(inout) :: obs
real(default), intent(in) :: value
logical, intent(out), optional :: success
obs%sum_values = obs%sum_values + value
obs%sum_squared_values = obs%sum_squared_values + value**2
obs%sum_weights = obs%sum_weights + 1
obs%sum_squared_weights = obs%sum_squared_weights + 1
obs%count = obs%count + 1
if (present (success)) success = .true.
end subroutine observable_record_value_unweighted

subroutine observable_record_value_weighted (obs, value, weight, success)
type(observable_t), intent(inout) :: obs
real(default), intent(in) :: value, weight
logical, intent(out), optional :: success
obs%sum_values = obs%sum_values + value * weight
obs%sum_squared_values = obs%sum_squared_values + value**2 * weight
obs%sum_weights = obs%sum_weights + abs (weight)
obs%sum_squared_weights = obs%sum_squared_weights + weight**2
obs%count = obs%count + 1
if (present (success)) success = .true.
end subroutine observable_record_value_weighted

```

Here are the statistics formulas:

1. Unweighted case: Given a sample of n values x_i , the average is

$$\langle x \rangle = \frac{\sum x_i}{n} \quad (12.4)$$

and the error estimate

$$\Delta x = \sqrt{\frac{1}{n-1} \langle \sum (x_i - \langle x \rangle)^2 \rangle} \quad (12.5)$$

$$= \sqrt{\frac{1}{n-1} \left(\frac{\sum x_i^2}{n} - \frac{(\sum x_i)^2}{n^2} \right)} \quad (12.6)$$

2. Weighted case: Instead of weight 1, each event comes with weight w_i .

$$\langle x \rangle = \frac{\sum x_i w_i}{\sum w_i} \quad (12.7)$$

and

$$\Delta x = \sqrt{\frac{1}{n-1} \left(\frac{\sum x_i^2 w_i}{\sum w_i} - \frac{(\sum x_i w_i)^2}{(\sum w_i)^2} \right)} \quad (12.8)$$

For $w_i = 1$, this specializes to the previous formula.

<Analysis: procedures>+≡

```

function observable_get_n_entries (obs) result (n)
integer :: n
type(observable_t), intent(in) :: obs
n = obs%count

```

```

end function observable_get_n_entries

function observable_get_average (obs) result (avg)
  real(default) :: avg
  type(observable_t), intent(in) :: obs
  if (obs%sum_weights /= 0) then
    avg = obs%sum_values / obs%sum_weights
  else
    avg = 0
  end if
end function observable_get_average

function observable_get_error (obs) result (err)
  real(default) :: err
  type(observable_t), intent(in) :: obs
  real(default) :: var, n
  if (obs%sum_weights /= 0) then
    select case (obs%count)
    case (0:1)
      err = 0
    case default
      n = obs%count
      var = obs%sum_squared_values / obs%sum_weights &
        - (obs%sum_values / obs%sum_weights) ** 2
      err = sqrt (max (var, 0._default) / (n - 1))
    end select
  else
    err = 0
  end if
end function observable_get_error

```

Write label and/or physical unit to a string.

(Analysis: procedures)+≡

```

function observable_get_label (obs, wl, wu) result (string)
  type(string_t) :: string
  type(observable_t), intent(in) :: obs
  logical, intent(in) :: wl, wu
  type(string_t) :: obs_label, obs_unit
  if (wl) then
    if (obs%obs_label /= "") then
      obs_label = obs%obs_label
    else
      obs_label = "\textrm{Observable}"
    end if
  else
    obs_label = ""
  end if
  if (wu) then
    if (obs%obs_unit /= "") then
      if (wl) then
        obs_unit = "\;[" // obs%obs_unit // "]"
      else
        obs_unit = obs%obs_unit
      end if
    end if
  end if
end function observable_get_label

```

```

        end if
    else
        obs_unit = ""
    end if
else
    obs_unit = ""
end if
string = obs_label // obs_unit
end function observable_get_label

```

12.5.5 Output

(Analysis: procedures)+≡

```

subroutine observable_write (obs, unit)
    type(observable_t), intent(in) :: obs
    integer, intent(in), optional :: unit
    real(default) :: avg, err, relerr
    integer :: n
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    avg = observable_get_average (obs)
    err = observable_get_error (obs)
    if (avg /= 0) then
        relerr = err / avg
    else
        relerr = 0
    end if
    n = observable_get_n_entries (obs)
    if (obs%graph_options%title /= "") then
        write (u, "(A,1x,3A)") &
            "title      =", "'", char (obs%graph_options%title), "'"
    end if
    if (obs%graph_options%title /= "") then
        write (u, "(A,1x,3A)") &
            "description =", "'", char (obs%graph_options%description), "'"
    end if
    write (u, "(A,1x," // HISTOGRAM_DATA_FORMAT // ")", advance = "no") &
        "average      =", avg
    call write_unit ()
    write (u, "(A,1x," // HISTOGRAM_DATA_FORMAT // ")", advance = "no") &
        "error[abs]   =", err
    call write_unit ()
    write (u, "(A,1x," // HISTOGRAM_DATA_FORMAT // ")", advance = "no") &
        "error[rel]   =", relerr
    write (u, "(A,1x,I0)") &
        "n_entries    =", n
contains
    subroutine write_unit ()
        if (obs%obs_unit /= "") then
            write (u, "(1x,A)") char (obs%obs_unit)
        else
            write (u, *)
        end if
    end subroutine write_unit
end subroutine observable_write

```

```

end subroutine write_unit
end subroutine observable_write

```

L^AT_EX output.

(Analysis: procedures)+≡

```

subroutine observable_write_driver (obs, unit, write_heading)
  type(observable_t), intent(in) :: obs
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: write_heading
  real(default) :: avg, err
  integer :: n_digits
  logical :: heading
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  heading = .true.; if (present (write_heading)) heading = write_heading
  avg = observable_get_average (obs)
  err = observable_get_error (obs)
  if (avg /= 0 .and. err /= 0) then
    n_digits = max (2, 2 - int (log10 (abs (err / real (avg, default)))))
  else if (avg /= 0) then
    n_digits = 100
  else
    n_digits = 1
  end if
  if (heading) then
    write (u, "(A)")
    if (obs%graph_options%title /= "") then
      write (u, "(A)") "\section{" // char (obs%graph_options%title) &
        // "}"
    else
      write (u, "(A)") "\section{Observable}"
    end if
    if (obs%graph_options%description /= "") then
      write (u, "(A)") char (obs%graph_options%description)
      write (u, *)
    end if
    write (u, "(A)") "\begin{flushleft}"
  end if
  write (u, "(A)", advance="no") "  $\langle$ " ! $ sign
  write (u, "(A)", advance="no") char (observable_get_label (obs, wl=.true., wu=.false.))
  write (u, "(A)", advance="no") "\rangle = "
  write (u, "(A)", advance="no") char (tex_format (avg, n_digits))
  write (u, "(A)", advance="no") "\pm"
  write (u, "(A)", advance="no") char (tex_format (err, 2))
  write (u, "(A)", advance="no") "\;{"
  write (u, "(A)", advance="no") char (observable_get_label (obs, wl=.false., wu=.true.))
  write (u, "(A)") "}"
  write (u, "(A)", advance="no") "  \quad[n_{\text{entries}}] = "
  write (u, "(IO)", advance="no") observable_get_n_entries (obs)
  write (u, "(A)") "]"$ " ! $ fool Emacs' noweb mode
  if (heading) then
    write (u, "(A)") "\end{flushleft}"
  end if
end if

```



```
end subroutine observable_write_driver
```

12.5.6 Histograms

Bins

<Analysis: types>+≡

```
type :: bin_t
  private
  real(default) :: midpoint = 0
  real(default) :: width = 0
  real(default) :: sum_weights = 0
  real(default) :: sum_squared_weights = 0
  real(default) :: sum_excess_weights = 0
  integer :: count = 0
end type bin_t
```

<Analysis: procedures>+≡

```
subroutine bin_init (bin, midpoint, width)
  type(bin_t), intent(out) :: bin
  real(default), intent(in) :: midpoint, width
  bin%midpoint = midpoint
  bin%width = width
end subroutine bin_init
```

<Analysis: procedures>+≡

```
elemental subroutine bin_clear (bin)
  type(bin_t), intent(inout) :: bin
  bin%sum_weights = 0
  bin%sum_squared_weights = 0
  bin%sum_excess_weights = 0
  bin%count = 0
end subroutine bin_clear
```

<Analysis: procedures>+≡

```
subroutine bin_record_value (bin, normalize, weight, excess)
  type(bin_t), intent(inout) :: bin
  logical, intent(in) :: normalize
  real(default), intent(in) :: weight
  real(default), intent(in), optional :: excess
  real(default) :: w, e
  if (normalize) then
    if (bin%width /= 0) then
      w = weight / bin%width
      if (present (excess)) e = excess / bin%width
    else
      w = 0
      if (present (excess)) e = 0
    end if
  else
    w = weight
    if (present (excess)) e = excess
  end if
```

```

end if
bin%sum_weights = bin%sum_weights + abs (w)
bin%sum_squared_weights = bin%sum_squared_weights + w ** 2
if (present (excess)) &
    bin%sum_excess_weights = bin%sum_excess_weights + abs (e)
bin%count = bin%count + 1
end subroutine bin_record_value

```

<Analysis: procedures>+≡

```

function bin_get_midpoint (bin) result (x)
    real(default) :: x
    type(bin_t), intent(in) :: bin
    x = bin%midpoint
end function bin_get_midpoint

```

```

function bin_get_width (bin) result (w)
    real(default) :: w
    type(bin_t), intent(in) :: bin
    w = bin%width
end function bin_get_width

```

```

function bin_get_n_entries (bin) result (n)
    integer :: n
    type(bin_t), intent(in) :: bin
    n = bin%count
end function bin_get_n_entries

```

```

function bin_get_sum (bin) result (s)
    real(default) :: s
    type(bin_t), intent(in) :: bin
    s = bin%sum_weights
end function bin_get_sum

```

```

function bin_get_error (bin) result (err)
    real(default) :: err
    type(bin_t), intent(in) :: bin
    err = sqrt (bin%sum_squared_weights)
end function bin_get_error

```

```

function bin_get_excess (bin) result (excess)
    real(default) :: excess
    type(bin_t), intent(in) :: bin
    excess = bin%sum_excess_weights
end function bin_get_excess

```

<Analysis: procedures>+≡

```

subroutine bin_write_header (unit)
    integer, intent(in), optional :: unit
    character(120) :: buffer
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (buffer, "(A,4(1x," //HISTOGRAM_HEAD_FORMAT // " ),2x,A)") &
        "#", "bin midpoint", "value", "error", "&

```

```

        "excess      ", "n"
        write (u, "(A)") trim (buffer)
    end subroutine bin_write_header

    subroutine bin_write (bin, unit)
        type(bin_t), intent(in) :: bin
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,4(1x," // HISTOGRAM_DATA_FORMAT // "),2x,IO)") &
            bin_get_midpoint (bin), &
            bin_get_sum (bin), &
            bin_get_error (bin), &
            bin_get_excess (bin), &
            bin_get_n_entries (bin)
    end subroutine bin_write

```

Histograms

<Analysis: types>+≡

```

    type :: histogram_t
    private
    real(default) :: lower_bound = 0
    real(default) :: upper_bound = 0
    real(default) :: width = 0
    integer :: n_bins = 0
    logical :: normalize_bins = .false.
    type(observable_t) :: obs
    type(observable_t) :: obs_within_bounds
    type(bin_t) :: underflow
    type(bin_t), dimension(:), allocatable :: bin
    type(bin_t) :: overflow
    type(graph_options_t) :: graph_options
    type(drawing_options_t) :: drawing_options
end type histogram_t

```

Initializer/finalizer

Initialize a histogram. We may provide either the bin width or the number of bins. A finalizer is not needed, since the histogram contains no pointer (sub)components.

<Analysis: interfaces>+≡

```

    interface histogram_init
        module procedure histogram_init_n_bins
        module procedure histogram_init_bin_width
    end interface

```

<Analysis: procedures>+≡

```

    subroutine histogram_init_n_bins (h, id, &
        lower_bound, upper_bound, n_bins, normalize_bins, &

```

```

        obs_label, obs_unit, graph_options, drawing_options)
type(histogram_t), intent(out) :: h
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound
integer, intent(in) :: n_bins
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
real(default) :: bin_width
integer :: i
call observable_init (h%obs_within_bounds, obs_label, obs_unit)
call observable_init (h%obs, obs_label, obs_unit)
h%lower_bound = lower_bound
h%upper_bound = upper_bound
h%n_bins = max (n_bins, 1)
h%width = h%upper_bound - h%lower_bound
h%normalize_bins = normalize_bins
bin_width = h%width / h%n_bins
allocate (h%bin (h%n_bins))
call bin_init (h%underflow, h%lower_bound, 0._default)
do i = 1, h%n_bins
    call bin_init (h%bin(i), &
        h%lower_bound - bin_width/2 + i * bin_width, bin_width)
end do
call bin_init (h%overflow, h%upper_bound, 0._default)
if (present (graph_options)) then
    h%graph_options = graph_options
else
    call graph_options_init (h%graph_options)
end if
call graph_options_set (h%graph_options, id = id)
if (present (drawing_options)) then
    h%drawing_options = drawing_options
else
    call drawing_options_init_histogram (h%drawing_options)
end if
end subroutine histogram_init_n_bins

subroutine histogram_init_bin_width (h, id, &
    lower_bound, upper_bound, bin_width, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
type(histogram_t), intent(out) :: h
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound, bin_width
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
integer :: n_bins
if (bin_width /= 0) then
    n_bins = nint ((upper_bound - lower_bound) / bin_width)
else
    n_bins = 1

```

```

end if
call histogram_init_n_bins (h, id, &
    lower_bound, upper_bound, n_bins, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
end subroutine histogram_init_bin_width

```

Initialize a histogram by copying another one.

Since `h` has no pointer (sub)components, intrinsic assignment is sufficient. Optionally, we replace the drawing options.

<Analysis: procedures>+≡

```

subroutine histogram_init_histogram (h, h_in, drawing_options)
    type(histogram_t), intent(out) :: h
    type(histogram_t), intent(in) :: h_in
    type(drawing_options_t), intent(in), optional :: drawing_options
    h = h_in
    if (present (drawing_options)) then
        h%drawing_options = drawing_options
    end if
end subroutine histogram_init_histogram

```

Fill histograms

Clear the histogram contents, but do not modify the structure.

<Analysis: procedures>+≡

```

subroutine histogram_clear (h)
    type(histogram_t), intent(inout) :: h
    call observable_clear (h%obs)
    call observable_clear (h%obs_within_bounds)
    call bin_clear (h%underflow)
    if (allocated (h%bin)) call bin_clear (h%bin)
    call bin_clear (h%overflow)
end subroutine histogram_clear

```

Record a value. Successful if the value is within bounds, otherwise it is recorded as under-/overflow. Optionally, we may provide an excess weight that could be returned by the unweighting procedure.

<Analysis: procedures>+≡

```

subroutine histogram_record_value_unweighted (h, value, excess, success)
    type(histogram_t), intent(inout) :: h
    real(default), intent(in) :: value
    real(default), intent(in), optional :: excess
    logical, intent(out), optional :: success
    integer :: i_bin
    call observable_record_value (h%obs, value)
    if (h%width /= 0) then
        i_bin = floor (((value - h%lower_bound) / h%width) * h%n_bins) + 1
    else
        i_bin = 0
    end if
    if (i_bin <= 0) then
        call bin_record_value (h%underflow, .false., 1._default, excess)
    end if
end subroutine histogram_record_value_unweighted

```

```

        if (present (success)) success = .false.
    else if (i_bin <= h%n_bins) then
        call observable_record_value (h%obs_within_bounds, value)
        call bin_record_value &
            (h%bin(i_bin), h%normalize_bins, 1._default, excess)
        if (present (success)) success = .true.
    else
        call bin_record_value (h%overflow, .false., 1._default, excess)
        if (present (success)) success = .false.
    end if
end subroutine histogram_record_value_unweighted

```

Weighted events: analogous, but no excess weight.

(Analysis: procedures)+≡

```

subroutine histogram_record_value_weighted (h, value, weight, success)
    type(histogram_t), intent(inout) :: h
    real(default), intent(in) :: value, weight
    logical, intent(out), optional :: success
    integer :: i_bin
    call observable_record_value (h%obs, value, weight)
    if (h%width /= 0) then
        i_bin = floor (((value - h%lower_bound) / h%width) * h%n_bins) + 1
    else
        i_bin = 0
    end if
    if (i_bin <= 0) then
        call bin_record_value (h%underflow, .false., weight)
        if (present (success)) success = .false.
    else if (i_bin <= h%n_bins) then
        call observable_record_value (h%obs_within_bounds, value, weight)
        call bin_record_value (h%bin(i_bin), h%normalize_bins, weight)
        if (present (success)) success = .true.
    else
        call bin_record_value (h%overflow, .false., weight)
        if (present (success)) success = .false.
    end if
end subroutine histogram_record_value_weighted

```

Access contents

Inherited from the observable component (all-over average etc.)

(Analysis: procedures)+≡

```

function histogram_get_n_entries (h) result (n)
    integer :: n
    type(histogram_t), intent(in) :: h
    n = observable_get_n_entries (h%obs)
end function histogram_get_n_entries

function histogram_get_average (h) result (avg)
    real(default) :: avg
    type(histogram_t), intent(in) :: h
    avg = observable_get_average (h%obs)

```

```

end function histogram_get_average

function histogram_get_error (h) result (err)
    real(default) :: err
    type(histogram_t), intent(in) :: h
    err = observable_get_error (h%obs)
end function histogram_get_error

```

Analogous, but applied only to events within bounds.

<Analysis: procedures>+≡

```

function histogram_get_n_entries_within_bounds (h) result (n)
    integer :: n
    type(histogram_t), intent(in) :: h
    n = observable_get_n_entries (h%obs_within_bounds)
end function histogram_get_n_entries_within_bounds

function histogram_get_average_within_bounds (h) result (avg)
    real(default) :: avg
    type(histogram_t), intent(in) :: h
    avg = observable_get_average (h%obs_within_bounds)
end function histogram_get_average_within_bounds

function histogram_get_error_within_bounds (h) result (err)
    real(default) :: err
    type(histogram_t), intent(in) :: h
    err = observable_get_error (h%obs_within_bounds)
end function histogram_get_error_within_bounds

```

Get the number of bins

<Analysis: procedures>+≡

```

function histogram_get_n_bins (h) result (n)
    type(histogram_t), intent(in) :: h
    integer :: n
    n = h%n_bins
end function histogram_get_n_bins

```

Check bins. If the index is zero or above the limit, return the results for underflow or overflow, respectively.

<Analysis: procedures>+≡

```

function histogram_get_n_entries_for_bin (h, i) result (n)
    integer :: n
    type(histogram_t), intent(in) :: h
    integer, intent(in) :: i
    if (i <= 0) then
        n = bin_get_n_entries (h%underflow)
    else if (i <= h%n_bins) then
        n = bin_get_n_entries (h%bin(i))
    else
        n = bin_get_n_entries (h%overflow)
    end if
end function histogram_get_n_entries_for_bin

```

```

function histogram_get_sum_for_bin (h, i) result (avg)
  real(default) :: avg
  type(histogram_t), intent(in) :: h
  integer, intent(in) :: i
  if (i <= 0) then
    avg = bin_get_sum (h%underflow)
  else if (i <= h%n_bins) then
    avg = bin_get_sum (h%bin(i))
  else
    avg = bin_get_sum (h%overflow)
  end if
end function histogram_get_sum_for_bin

function histogram_get_error_for_bin (h, i) result (err)
  real(default) :: err
  type(histogram_t), intent(in) :: h
  integer, intent(in) :: i
  if (i <= 0) then
    err = bin_get_error (h%underflow)
  else if (i <= h%n_bins) then
    err = bin_get_error (h%bin(i))
  else
    err = bin_get_error (h%overflow)
  end if
end function histogram_get_error_for_bin

function histogram_get_excess_for_bin (h, i) result (err)
  real(default) :: err
  type(histogram_t), intent(in) :: h
  integer, intent(in) :: i
  if (i <= 0) then
    err = bin_get_excess (h%underflow)
  else if (i <= h%n_bins) then
    err = bin_get_excess (h%bin(i))
  else
    err = bin_get_excess (h%overflow)
  end if
end function histogram_get_excess_for_bin

```

Return a pointer to the graph options.

<Analysis: procedures>+≡

```

function histogram_get_graph_options_ptr (h) result (ptr)
  type(graph_options_t), pointer :: ptr
  type(histogram_t), intent(in), target :: h
  ptr => h%graph_options
end function histogram_get_graph_options_ptr

```

Return a pointer to the drawing options.

<Analysis: procedures>+≡

```

function histogram_get_drawing_options_ptr (h) result (ptr)
  type(drawing_options_t), pointer :: ptr
  type(histogram_t), intent(in), target :: h
  ptr => h%drawing_options

```



```
end function histogram_get_drawing_options_ptr
```

Output

<Analysis: procedures>+≡

```
subroutine histogram_write (h, unit)
  type(histogram_t), intent(in) :: h
  integer, intent(in), optional :: unit
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  call bin_write_header (u)
  if (allocated (h%bin)) then
    do i = 1, h%n_bins
      call bin_write (h%bin(i), u)
    end do
  end if
  write (u, *)
  write (u, "(A,1x,A)" ) "#", "Underflow:"
  call bin_write (h%underflow, u)
  write (u, *)
  write (u, "(A,1x,A)" ) "#", "Overflow:"
  call bin_write (h%overflow, u)
  write (u, *)
  write (u, "(A,1x,A)" ) "#", "Summary: data within bounds"
  call observable_write (h%obs_within_bounds, u)
  write (u, *)
  write (u, "(A,1x,A)" ) "#", "Summary: all data"
  call observable_write (h%obs, u)
  write (u, *)
end subroutine histogram_write
```

Write the GAMELAN reader for histogram contents.

<Analysis: procedures>+≡

```
subroutine histogram_write_gml_reader (h, filename, unit)
  type(histogram_t), intent(in) :: h
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  character(*), parameter :: fmt = "(ES15.8)"
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(2x,A)" ) 'fromfile "' // char (filename) // '":'
  write (u, "(4x,A)" ) 'key "# Histogram:";'
  write (u, "(4x,A)" ) 'dx := #' &
    // real2char (h%width / h%n_bins / 2, fmt) // ';'
  write (u, "(4x,A)" ) 'for i withinblock:'
  write (u, "(6x,A)" ) 'get x, y, y.d, y.n, y.e;'
  if (h%drawing_options%with_hbars) then
    write (u, "(6x,A)" ) 'plot (' // char (h%drawing_options%dataset) &
      // ')' (x,y) hbar dx;'
  else
    write (u, "(6x,A)" ) 'plot (' // char (h%drawing_options%dataset) &
      // ')' (x,y);'
```

```

end if
if (h%drawing_options%err) then
    write (u, "(6x,A)") 'plot (' // char (h%drawing_options%dataset) &
        // '.err) ' &
        // '(x,y) vbar y.d;'
end if
!!! Future excess options for plots
! write (u, "(6x,A)") 'if show_excess: ' // &
!         & 'plot(dat.e)(x, y plus y.e) hbar dx; fi'
write (u, "(4x,A)") 'endfor'
write (u, "(2x,A)") 'endfrom'
end subroutine histogram_write_gml_reader

```

L^AT_EX and GAMELAN output.

(Analysis: procedures)+≡

```

subroutine histogram_write_gml_driver (h, filename, unit)
    type(histogram_t), intent(in) :: h
    type(string_t), intent(in) :: filename
    integer, intent(in), optional :: unit
    type(string_t) :: calc_cmd, bg_cmd, draw_cmd, err_cmd, symb_cmd, fg_cmd
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call graph_options_write_tex_header (h%graph_options, unit)
    write (u, "(2x,A)") char (graph_options_get_gml_setup (h%graph_options))
    write (u, "(2x,A)") char (graph_options_get_gml_graphrange &
        (h%graph_options, x_min=h%lower_bound, x_max=h%upper_bound))
    call histogram_write_gml_reader (h, filename, unit)
    calc_cmd = drawing_options_get_calc_command (h%drawing_options)
    if (calc_cmd /= "") write (u, "(2x,A)") char (calc_cmd)
    bg_cmd = drawing_options_get_gml_bg_command (h%drawing_options)
    if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
    draw_cmd = drawing_options_get_draw_command (h%drawing_options)
    if (draw_cmd /= "") write (u, "(2x,A)") char (draw_cmd)
    err_cmd = drawing_options_get_err_command (h%drawing_options)
    if (err_cmd /= "") write (u, "(2x,A)") char (err_cmd)
    symb_cmd = drawing_options_get_symb_command (h%drawing_options)
    if (symb_cmd /= "") write (u, "(2x,A)") char (symb_cmd)
    fg_cmd = drawing_options_get_gml_fg_command (h%drawing_options)
    if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
    write (u, "(2x,A)") char (graph_options_get_gml_x_label (h%graph_options))
    write (u, "(2x,A)") char (graph_options_get_gml_y_label (h%graph_options))
    call graph_options_write_tex_footer (h%graph_options, unit)
    write (u, "(A)") "\vspace*{2\baselineskip}"
    write (u, "(A)") "\begin{flushleft}"
    write (u, "(A)") "\textbf{Data within bounds:} \\"
    call observable_write_driver (h%obs_within_bounds, unit, &
        write_heading=.false.)
    write (u, "(A)") "\\[0.5\baselineskip]"
    write (u, "(A)") "\textbf{All data:} \\"
    call observable_write_driver (h%obs, unit, write_heading=.false.)
    write (u, "(A)") "\end{flushleft}"
end subroutine histogram_write_gml_driver

```

Return the header for generic data output as an ifile.

```

<Analysis: procedures>+≡
subroutine histogram_get_header (h, header, comment)
  type(histogram_t), intent(in) :: h
  type(ifile_t), intent(inout) :: header
  type(string_t), intent(in), optional :: comment
  type(string_t) :: c
  if (present (comment)) then
    c = comment
  else
    c = ""
  end if
  call ifile_append (header, c // "WHIZARD histogram data")
  call graph_options_get_header (h%graph_options, header, comment)
  call ifile_append (header, &
    c // "range: " // real2string (h%lower_bound) &
    // " - " // real2string (h%upper_bound))
  call ifile_append (header, &
    c // "counts total: " &
    // int2char (histogram_get_n_entries_within_bounds (h)))
  call ifile_append (header, &
    c // "total average: " &
    // real2string (histogram_get_average_within_bounds (h)) // " +- " &
    // real2string (histogram_get_error_within_bounds (h)))
end subroutine histogram_get_header

```

12.5.7 Plots

Points

```

<Analysis: types>+≡
type :: point_t
  private
  real(default) :: x = 0
  real(default) :: y = 0
  real(default) :: yerr = 0
  real(default) :: xerr = 0
  type(point_t), pointer :: next => null ()
end type point_t

<Analysis: interfaces>+≡
interface point_init
  module procedure point_init_contents
  module procedure point_init_point
end interface

<Analysis: procedures>+≡
subroutine point_init_contents (point, x, y, yerr, xerr)
  type(point_t), intent(out) :: point
  real(default), intent(in) :: x, y
  real(default), intent(in), optional :: yerr, xerr
  point%x = x
  point%y = y

```

```

    if (present (yerr)) point%yerr = yerr
    if (present (xerr)) point%xerr = xerr
end subroutine point_init_contents

subroutine point_init_point (point, point_in)
    type(point_t), intent(out) :: point
    type(point_t), intent(in) :: point_in
    point%x = point_in%x
    point%y = point_in%y
    point%yerr = point_in%yerr
    point%xerr = point_in%xerr
end subroutine point_init_point

```

<Analysis: procedures>+≡

```

function point_get_x (point) result (x)
    real(default) :: x
    type(point_t), intent(in) :: point
    x = point%x
end function point_get_x

function point_get_y (point) result (y)
    real(default) :: y
    type(point_t), intent(in) :: point
    y = point%y
end function point_get_y

function point_get_xerr (point) result (xerr)
    real(default) :: xerr
    type(point_t), intent(in) :: point
    xerr = point%xerr
end function point_get_xerr

function point_get_yerr (point) result (yerr)
    real(default) :: yerr
    type(point_t), intent(in) :: point
    yerr = point%yerr
end function point_get_yerr

```

<Analysis: procedures>+≡

```

subroutine point_write_header (unit)
    integer, intent(in) :: unit
    character(120) :: buffer
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (buffer, "(A,4(1x," // HISTOGRAM_HEAD_FORMAT // "))" &
        "#", "x", "y", "yerr", "xerr"
    write (u, "(A)") trim (buffer)
end subroutine point_write_header

subroutine point_write (point, unit)
    type(point_t), intent(in) :: point
    integer, intent(in), optional :: unit
    integer :: u

```

```

u = given_output_unit (unit); if (u < 0) return
write (u, "(1x,4(1x," // HISTOGRAM_DATA_FORMAT // ")") &
      point_get_x (point), &
      point_get_y (point), &
      point_get_yerr (point), &
      point_get_xerr (point)
end subroutine point_write

```

Plots

<Analysis: types>+≡

```

type :: plot_t
  private
  type(point_t), pointer :: first => null ()
  type(point_t), pointer :: last => null ()
  integer :: count = 0
  type(graph_options_t) :: graph_options
  type(drawing_options_t) :: drawing_options
end type plot_t

```

Initializer/finalizer

Initialize a plot. We provide the lower and upper bound in the x direction.

<Analysis: interfaces>+≡

```

interface plot_init
  module procedure plot_init_empty
  module procedure plot_init_plot
end interface

```

<Analysis: procedures>+≡

```

subroutine plot_init_empty (p, id, graph_options, drawing_options)
  type(plot_t), intent(out) :: p
  type(string_t), intent(in) :: id
  type(graph_options_t), intent(in), optional :: graph_options
  type(drawing_options_t), intent(in), optional :: drawing_options
  if (present (graph_options)) then
    p%graph_options = graph_options
  else
    call graph_options_init (p%graph_options)
  end if
  call graph_options_set (p%graph_options, id = id)
  if (present (drawing_options)) then
    p%drawing_options = drawing_options
  else
    call drawing_options_init_plot (p%drawing_options)
  end if
end subroutine plot_init_empty

```

Initialize a plot by copying another one, optionally merging in a new set of drawing options.

Since `p` has pointer (sub)components, we have to explicitly deep-copy the original.

<Analysis: procedures>+≡

```
subroutine plot_init_plot (p, p_in, drawing_options)
  type(plot_t), intent(out) :: p
  type(plot_t), intent(in) :: p_in
  type(drawing_options_t), intent(in), optional :: drawing_options
  type(point_t), pointer :: current, new
  current => p_in%first
  do while (associated (current))
    allocate (new)
    call point_init (new, current)
    if (associated (p%last)) then
      p%last%next => new
    else
      p%first => new
    end if
    p%last => new
    current => current%next
  end do
  p%count = p_in%count
  p%graph_options = p_in%graph_options
  if (present (drawing_options)) then
    p%drawing_options = drawing_options
  else
    p%drawing_options = p_in%drawing_options
  end if
end subroutine plot_init_plot
```

Finalize the plot by deallocating the list of points.

<Analysis: procedures>+≡

```
subroutine plot_final (plot)
  type(plot_t), intent(inout) :: plot
  type(point_t), pointer :: current
  do while (associated (plot%first))
    current => plot%first
    plot%first => current%next
    deallocate (current)
  end do
  plot%last => null ()
end subroutine plot_final
```

Fill plots

Clear the plot contents, but do not modify the structure.

<Analysis: procedures>+≡

```
subroutine plot_clear (plot)
  type(plot_t), intent(inout) :: plot
  plot%count = 0
  call plot_final (plot)
end subroutine plot_clear
```

Record a value. Successful if the value is within bounds, otherwise it is recorded as under-/overflow.

<Analysis: procedures>+≡

```
subroutine plot_record_value (plot, x, y, yerr, xerr, success)
  type(plot_t), intent(inout) :: plot
  real(default), intent(in) :: x, y
  real(default), intent(in), optional :: yerr, xerr
  logical, intent(out), optional :: success
  type(point_t), pointer :: point
  plot%count = plot%count + 1
  allocate (point)
  call point_init (point, x, y, yerr, xerr)
  if (associated (plot%first)) then
    plot%last%next => point
  else
    plot%first => point
  end if
  plot%last => point
  if (present (success)) success = .true.
end subroutine plot_record_value
```

Access contents

The number of points.

<Analysis: procedures>+≡

```
function plot_get_n_entries (plot) result (n)
  integer :: n
  type(plot_t), intent(in) :: plot
  n = plot%count
end function plot_get_n_entries
```

Return a pointer to the graph options.

<Analysis: procedures>+≡

```
function plot_get_graph_options_ptr (p) result (ptr)
  type(graph_options_t), pointer :: ptr
  type(plot_t), intent(in), target :: p
  ptr => p%graph_options
end function plot_get_graph_options_ptr
```

Return a pointer to the drawing options.

<Analysis: procedures>+≡

```
function plot_get_drawing_options_ptr (p) result (ptr)
  type(drawing_options_t), pointer :: ptr
  type(plot_t), intent(in), target :: p
  ptr => p%drawing_options
end function plot_get_drawing_options_ptr
```

Output

This output format is used by the GAMELAN driver below.

<Analysis: procedures>+≡

```
subroutine plot_write (plot, unit)
  type(plot_t), intent(in) :: plot
  integer, intent(in), optional :: unit
  type(point_t), pointer :: point
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call point_write_header (u)
  point => plot%first
  do while (associated (point))
    call point_write (point, unit)
    point => point%next
  end do
  write (u, *)
  write (u, "(A,1x,A)" ) "#", "Summary:"
  write (u, "(A,1x,I0)" ) &
    "n_entries =", plot_get_n_entries (plot)
  write (u, *)
end subroutine plot_write
```

Write the GAMELAN reader for plot contents.

<Analysis: procedures>+≡

```
subroutine plot_write_gml_reader (p, filename, unit)
  type(plot_t), intent(in) :: p
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(2x,A)" ) 'fromfile "' // char (filename) // '":'
  write (u, "(4x,A)" ) 'key "# Plot:";'
  write (u, "(4x,A)" ) 'for i withinblock:'
  write (u, "(6x,A)" ) 'get x, y, y.err, x.err;'
  write (u, "(6x,A)" ) 'plot (' // char (p%drawing_options%dataset) &
    // ')' (x,y);'
  if (p%drawing_options%err) then
    write (u, "(6x,A)" ) 'plot (' // char (p%drawing_options%dataset) &
      // '.err) (x,y) vbar y.err hbar x.err;'
  end if
  write (u, "(4x,A)" ) 'endfor'
  write (u, "(2x,A)" ) 'endfrom'
end subroutine plot_write_gml_reader
```

L^AT_EX and GAMELAN output. Analogous to histogram output.

<Analysis: procedures>+≡

```
subroutine plot_write_gml_driver (p, filename, unit)
  type(plot_t), intent(in) :: p
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  type(string_t) :: calc_cmd, bg_cmd, draw_cmd, err_cmd, symb_cmd, fg_cmd
  integer :: u
```



```

u = given_output_unit (unit); if (u < 0) return
call graph_options_write_tex_header (p%graph_options, unit)
write (u, "(2x,A)") &
    char (graph_options_get_gml_setup (p%graph_options))
write (u, "(2x,A)") &
    char (graph_options_get_gml_graphrange (p%graph_options))
call plot_write_gml_reader (p, filename, unit)
calc_cmd = drawing_options_get_calc_command (p%drawing_options)
if (calc_cmd /= "") write (u, "(2x,A)") char (calc_cmd)
bg_cmd = drawing_options_get_gml_bg_command (p%drawing_options)
if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
draw_cmd = drawing_options_get_draw_command (p%drawing_options)
if (draw_cmd /= "") write (u, "(2x,A)") char (draw_cmd)
err_cmd = drawing_options_get_err_command (p%drawing_options)
if (err_cmd /= "") write (u, "(2x,A)") char (err_cmd)
symb_cmd = drawing_options_get_symb_command (p%drawing_options)
if (symb_cmd /= "") write (u, "(2x,A)") char (symb_cmd)
fg_cmd = drawing_options_get_gml_fg_command (p%drawing_options)
if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
write (u, "(2x,A)") char (graph_options_get_gml_x_label (p%graph_options))
write (u, "(2x,A)") char (graph_options_get_gml_y_label (p%graph_options))
call graph_options_write_tex_footer (p%graph_options, unit)
end subroutine plot_write_gml_driver

```

Append header for generic data output in ifile format.

(Analysis: procedures)+≡

```

subroutine plot_get_header (plot, header, comment)
    type(plot_t), intent(in) :: plot
    type(ifile_t), intent(inout) :: header
    type(string_t), intent(in), optional :: comment
    type(string_t) :: c
    if (present (comment)) then
        c = comment
    else
        c = ""
    end if
    call ifile_append (header, c // "WHIZARD plot data")
    call graph_options_get_header (plot%graph_options, header, comment)
    call ifile_append (header, &
        c // "number of points: " &
        // int2char (plot_get_n_entries (plot)))
end subroutine plot_get_header

```

12.5.8 Graphs

A graph is a container for several graph elements. Each graph element is either a plot or a histogram. There is an appropriate base type below (the `analysis_object_t`), but to avoid recursion, we define a separate base type here. Note that there is no actual recursion: a graph is an analysis object, but a graph cannot contain graphs.

(If we could use type extension, the implementation would be much more transparent.)

Graph elements

Graph elements cannot be filled by the **record** command directly. The contents are always copied from elementary histograms or plots.

(Analysis: types)+≡

```
type :: graph_element_t
private
integer :: type = AN_UNDEFINED
type(histogram_t), pointer :: h => null ()
type(plot_t), pointer :: p => null ()
end type graph_element_t
```

(Analysis: procedures)+≡

```
subroutine graph_element_final (el)
type(graph_element_t), intent(inout) :: el
select case (el%type)
case (AN_HISTOGRAM)
deallocate (el%h)
case (AN_PLOT)
call plot_final (el%p)
deallocate (el%p)
end select
el%type = AN_UNDEFINED
end subroutine graph_element_final
```

Return the number of entries in the graph element:

(Analysis: procedures)+≡

```
function graph_element_get_n_entries (el) result (n)
integer :: n
type(graph_element_t), intent(in) :: el
select case (el%type)
case (AN_HISTOGRAM); n = histogram_get_n_entries (el%h)
case (AN_PLOT);      n = plot_get_n_entries (el%p)
case default;        n = 0
end select
end function graph_element_get_n_entries
```

Return a pointer to the graph / drawing options.

(Analysis: procedures)+≡

```
function graph_element_get_graph_options_ptr (el) result (ptr)
type(graph_options_t), pointer :: ptr
type(graph_element_t), intent(in) :: el
select case (el%type)
case (AN_HISTOGRAM); ptr => histogram_get_graph_options_ptr (el%h)
case (AN_PLOT);      ptr => plot_get_graph_options_ptr (el%p)
case default;        ptr => null ()
end select
end function graph_element_get_graph_options_ptr

function graph_element_get_drawing_options_ptr (el) result (ptr)
type(drawing_options_t), pointer :: ptr
type(graph_element_t), intent(in) :: el
```

```

        select case (el%type)
        case (AN_HISTOGRAM); ptr => histogram_get_drawing_options_ptr (el%h)
        case (AN_PLOT);      ptr => plot_get_drawing_options_ptr (el%p)
        case default;       ptr => null ()
        end select
    end function graph_element_get_drawing_options_ptr

```

Output, simple wrapper for the plot/histogram writer.

<Analysis: procedures>+≡

```

subroutine graph_element_write (el, unit)
    type(graph_element_t), intent(in) :: el
    integer, intent(in), optional :: unit
    type(graph_options_t), pointer :: gro
    type(string_t) :: id
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    gro => graph_element_get_graph_options_ptr (el)
    id = graph_options_get_id (gro)
    write (u, "(A,A)" ' #', repeat ("-", 78))
    select case (el%type)
    case (AN_HISTOGRAM)
        write (u, "(A)", advance="no")  "# Histogram: "
        write (u, "(1x,A)" char (id)
        call histogram_write (el%h, unit)
    case (AN_PLOT)
        write (u, "(A)", advance="no")  "# Plot: "
        write (u, "(1x,A)" char (id)
        call plot_write (el%p, unit)
    end select
end subroutine graph_element_write

```

<Analysis: procedures>+≡

```

subroutine graph_element_write_gml_reader (el, filename, unit)
    type(graph_element_t), intent(in) :: el
    type(string_t), intent(in) :: filename
    integer, intent(in), optional :: unit
    select case (el%type)
    case (AN_HISTOGRAM); call histogram_write_gml_reader (el%h, filename, unit)
    case (AN_PLOT);      call plot_write_gml_reader (el%p, filename, unit)
    end select
end subroutine graph_element_write_gml_reader

```

The graph type

The actual graph type contains its own `graph_options`, which override the individual settings. The `drawing_options` are set in the graph elements. This distinction motivates the separation of the two types.

<Analysis: types>+≡

```

type :: graph_t
    private
    type(graph_element_t), dimension(:), allocatable :: el

```

```

    type(graph_options_t) :: graph_options
end type graph_t

```

Initializer/finalizer

The graph is created with a definite number of elements. The elements are filled one by one, optionally with modified drawing options.

(Analysis: procedures)+≡

```

subroutine graph_init (g, id, n_elements, graph_options)
    type(graph_t), intent(out) :: g
    type(string_t), intent(in) :: id
    integer, intent(in) :: n_elements
    type(graph_options_t), intent(in), optional :: graph_options
    allocate (g%el (n_elements))
    if (present (graph_options)) then
        g%graph_options = graph_options
    else
        call graph_options_init (g%graph_options)
    end if
    call graph_options_set (g%graph_options, id = id)
end subroutine graph_init

```

(Analysis: procedures)+≡

```

subroutine graph_insert_histogram (g, i, h, drawing_options)
    type(graph_t), intent(inout), target :: g
    integer, intent(in) :: i
    type(histogram_t), intent(in) :: h
    type(drawing_options_t), intent(in), optional :: drawing_options
    type(graph_options_t), pointer :: gro
    type(drawing_options_t), pointer :: dro
    type(string_t) :: id
    g%el(i)%type = AN_HISTOGRAM
    allocate (g%el(i)%h)
    call histogram_init_histogram (g%el(i)%h, h, drawing_options)
    gro => histogram_get_graph_options_ptr (g%el(i)%h)
    dro => histogram_get_drawing_options_ptr (g%el(i)%h)
    id = graph_options_get_id (gro)
    call drawing_options_set (dro, dataset = "dat." // id)
end subroutine graph_insert_histogram

```

(Analysis: procedures)+≡

```

subroutine graph_insert_plot (g, i, p, drawing_options)
    type(graph_t), intent(inout) :: g
    integer, intent(in) :: i
    type(plot_t), intent(in) :: p
    type(drawing_options_t), intent(in), optional :: drawing_options
    type(graph_options_t), pointer :: gro
    type(drawing_options_t), pointer :: dro
    type(string_t) :: id
    g%el(i)%type = AN_PLOT
    allocate (g%el(i)%p)
    call plot_init_plot (g%el(i)%p, p, drawing_options)

```

```

        gro => plot_get_graph_options_ptr (g%el(i)%p)
        dro => plot_get_drawing_options_ptr (g%el(i)%p)
        id = graph_options_get_id (gro)
        call drawing_options_set (dro, dataset = "dat." // id)
    end subroutine graph_insert_plot

```

Finalizer.

```

<Analysis: procedures>+≡
subroutine graph_final (g)
    type(graph_t), intent(inout) :: g
    integer :: i
    do i = 1, size (g%el)
        call graph_element_final (g%el(i))
    end do
    deallocate (g%el)
end subroutine graph_final

```

Access contents

The number of elements.

```

<Analysis: procedures>+≡
function graph_get_n_elements (graph) result (n)
    integer :: n
    type(graph_t), intent(in) :: graph
    n = size (graph%el)
end function graph_get_n_elements

```

Retrieve a pointer to the drawing options of an element, so they can be modified. (The `target` attribute is not actually needed because the components are pointers.)

```

<Analysis: procedures>+≡
function graph_get_drawing_options_ptr (g, i) result (ptr)
    type(drawing_options_t), pointer :: ptr
    type(graph_t), intent(in), target :: g
    integer, intent(in) :: i
    ptr => graph_element_get_drawing_options_ptr (g%el(i))
end function graph_get_drawing_options_ptr

```

Output

The default output format just writes histogram and plot data.

```

<Analysis: procedures>+≡
subroutine graph_write (graph, unit)
    type(graph_t), intent(in) :: graph
    integer, intent(in), optional :: unit
    integer :: i
    do i = 1, size (graph%el)
        call graph_element_write (graph%el(i), unit)
    end do

```

```
end subroutine graph_write
```

The GAMELAN driver is not a simple wrapper, but it writes the plot/histogram contents embedded the complete graph. First, data are read in, global background commands next, then individual elements, then global foreground commands.

<Analysis: procedures>+≡

```
subroutine graph_write_gml_driver (g, filename, unit)
  type(graph_t), intent(in) :: g
  type(string_t), intent(in) :: filename
  type(string_t) :: calc_cmd, bg_cmd, draw_cmd, err_cmd, symb_cmd, fg_cmd
  integer, intent(in), optional :: unit
  type(drawing_options_t), pointer :: dro
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  call graph_options_write_tex_header (g%graph_options, unit)
  write (u, "(2x,A)") &
    char (graph_options_get_gml_setup (g%graph_options))
  write (u, "(2x,A)") &
    char (graph_options_get_gml_graphrange (g%graph_options))
  do i = 1, size (g%el)
    call graph_element_write_gml_reader (g%el(i), filename, unit)
    calc_cmd = drawing_options_get_calc_command &
      (graph_element_get_drawing_options_ptr (g%el(i)))
    if (calc_cmd /= "") write (u, "(2x,A)") char (calc_cmd)
  end do
  bg_cmd = graph_options_get_gml_bg_command (g%graph_options)
  if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
  do i = 1, size (g%el)
    dro => graph_element_get_drawing_options_ptr (g%el(i))
    bg_cmd = drawing_options_get_gml_bg_command (dro)
    if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
    draw_cmd = drawing_options_get_draw_command (dro)
    if (draw_cmd /= "") write (u, "(2x,A)") char (draw_cmd)
    err_cmd = drawing_options_get_err_command (dro)
    if (err_cmd /= "") write (u, "(2x,A)") char (err_cmd)
    symb_cmd = drawing_options_get_symb_command (dro)
    if (symb_cmd /= "") write (u, "(2x,A)") char (symb_cmd)
    fg_cmd = drawing_options_get_gml_fg_command (dro)
    if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
  end do
  fg_cmd = graph_options_get_gml_fg_command (g%graph_options)
  if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
  write (u, "(2x,A)") char (graph_options_get_gml_x_label (g%graph_options))
  write (u, "(2x,A)") char (graph_options_get_gml_y_label (g%graph_options))
  call graph_options_write_tex_footer (g%graph_options, unit)
end subroutine graph_write_gml_driver
```

Append header for generic data output in ifile format.

<Analysis: procedures>+≡

```
subroutine graph_get_header (graph, header, comment)
  type(graph_t), intent(in) :: graph
  type(ifile_t), intent(inout) :: header
```

```

type(string_t), intent(in), optional :: comment
type(string_t) :: c
if (present (comment)) then
    c = comment
else
    c = ""
end if
call ifile_append (header, c // "WHIZARD graph data")
call graph_options_get_header (graph%graph_options, header, comment)
call ifile_append (header, &
    c // "number of graph elements: " &
    // int2char (graph_get_n_elements (graph)))
end subroutine graph_get_header

```

12.5.9 Analysis objects

This data structure holds all observables, histograms and such that are currently active. We have one global store; individual items are identified by their ID strings.

(This should rather be coded by type extension.)

```

<Analysis: parameters>+≡
integer, parameter :: AN_UNDEFINED = 0
integer, parameter :: AN_OBSERVABLE = 1
integer, parameter :: AN_HISTOGRAM = 2
integer, parameter :: AN_PLOT = 3
integer, parameter :: AN_GRAPH = 4

<Analysis: public>+≡
public :: AN_UNDEFINED, AN_HISTOGRAM, AN_OBSERVABLE, AN_PLOT, AN_GRAPH

<Analysis: types>+≡
type :: analysis_object_t
private
type(string_t) :: id
integer :: type = AN_UNDEFINED
type(observable_t), pointer :: obs => null ()
type(histogram_t), pointer :: h => null ()
type(plot_t), pointer :: p => null ()
type(graph_t), pointer :: g => null ()
type(analysis_object_t), pointer :: next => null ()
end type analysis_object_t

```

Initializer/finalizer

Allocate with the correct type but do not fill initial values.

```

<Analysis: procedures>+≡
subroutine analysis_object_init (obj, id, type)
type(analysis_object_t), intent(out) :: obj
type(string_t), intent(in) :: id
integer, intent(in) :: type
obj%id = id

```

```

obj%type = type
select case (obj%type)
case (AN_OBSERVABLE); allocate (obj%obs)
case (AN_HISTOGRAM);  allocate (obj%h)
case (AN_PLOT);       allocate (obj%p)
case (AN_GRAPH);      allocate (obj%g)
end select
end subroutine analysis_object_init

```

(Analysis: procedures)+≡

```

subroutine analysis_object_final (obj)
type(analysis_object_t), intent(inout) :: obj
select case (obj%type)
case (AN_OBSERVABLE)
deallocate (obj%obs)
case (AN_HISTOGRAM)
deallocate (obj%h)
case (AN_PLOT)
call plot_final (obj%p)
deallocate (obj%p)
case (AN_GRAPH)
call graph_final (obj%g)
deallocate (obj%g)
end select
obj%type = AN_UNDEFINED
end subroutine analysis_object_final

```

Clear the analysis object, i.e., reset it to its initial state. Not applicable to graphs, which are always combinations of other existing objects.

(Analysis: procedures)+≡

```

subroutine analysis_object_clear (obj)
type(analysis_object_t), intent(inout) :: obj
select case (obj%type)
case (AN_OBSERVABLE)
call observable_clear (obj%obs)
case (AN_HISTOGRAM)
call histogram_clear (obj%h)
case (AN_PLOT)
call plot_clear (obj%p)
end select
end subroutine analysis_object_clear

```

Fill with data

Record data. The effect depends on the type of analysis object.

(Analysis: procedures)+≡

```

subroutine analysis_object_record_data (obj, &
x, y, yerr, xerr, weight, excess, success)
type(analysis_object_t), intent(inout) :: obj
real(default), intent(in) :: x
real(default), intent(in), optional :: y, yerr, xerr, weight, excess

```



```

logical, intent(out), optional :: success
select case (obj%type)
case (AN_OBSERVABLE)
  if (present (weight)) then
    call observable_record_value_weighted (obj%obs, x, weight, success)
  else
    call observable_record_value_unweighted (obj%obs, x, success)
  end if
case (AN_HISTOGRAM)
  if (present (weight)) then
    call histogram_record_value_weighted (obj%h, x, weight, success)
  else
    call histogram_record_value_unweighted (obj%h, x, excess, success)
  end if
case (AN_PLOT)
  if (present (y)) then
    call plot_record_value (obj%p, x, y, yerr, xerr, success)
  else
    if (present (success)) success = .false.
  end if
case default
  if (present (success)) success = .false.
end select
end subroutine analysis_object_record_data

```

Explicitly set the pointer to the next object in the list.

```

<Analysis: procedures>+≡
subroutine analysis_object_set_next_ptr (obj, next)
  type(analysis_object_t), intent(inout) :: obj
  type(analysis_object_t), pointer :: next
  obj%next => next
end subroutine analysis_object_set_next_ptr

```

Access contents

Return a pointer to the next object in the list.

```

<Analysis: procedures>+≡
function analysis_object_get_next_ptr (obj) result (next)
  type(analysis_object_t), pointer :: next
  type(analysis_object_t), intent(in) :: obj
  next => obj%next
end function analysis_object_get_next_ptr

```

Return data as appropriate for the object type.

```

<Analysis: procedures>+≡
function analysis_object_get_n_elements (obj) result (n)
  integer :: n
  type(analysis_object_t), intent(in) :: obj
  select case (obj%type)
  case (AN_HISTOGRAM)
    n = 1

```

```

    case (AN_PLOT)
        n = 1
    case (AN_GRAPH)
        n = graph_get_n_elements (obj%g)
    case default
        n = 0
    end select
end function analysis_object_get_n_elements

function analysis_object_get_n_entries (obj, within_bounds) result (n)
    integer :: n
    type(analysis_object_t), intent(in) :: obj
    logical, intent(in), optional :: within_bounds
    logical :: wb
    select case (obj%type)
    case (AN_OBSERVABLE)
        n = observable_get_n_entries (obj%obs)
    case (AN_HISTOGRAM)
        wb = .false.; if (present (within_bounds)) wb = within_bounds
        if (wb) then
            n = histogram_get_n_entries_within_bounds (obj%h)
        else
            n = histogram_get_n_entries (obj%h)
        end if
    case (AN_PLOT)
        n = plot_get_n_entries (obj%p)
    case default
        n = 0
    end select
end function analysis_object_get_n_entries

function analysis_object_get_average (obj, within_bounds) result (avg)
    real(default) :: avg
    type(analysis_object_t), intent(in) :: obj
    logical, intent(in), optional :: within_bounds
    logical :: wb
    select case (obj%type)
    case (AN_OBSERVABLE)
        avg = observable_get_average (obj%obs)
    case (AN_HISTOGRAM)
        wb = .false.; if (present (within_bounds)) wb = within_bounds
        if (wb) then
            avg = histogram_get_average_within_bounds (obj%h)
        else
            avg = histogram_get_average (obj%h)
        end if
    case default
        avg = 0
    end select
end function analysis_object_get_average

function analysis_object_get_error (obj, within_bounds) result (err)
    real(default) :: err
    type(analysis_object_t), intent(in) :: obj

```

```

logical, intent(in), optional :: within_bounds
logical :: wb
select case (obj%type)
case (AN_OBSERVABLE)
    err = observable_get_error (obj%obs)
case (AN_HISTOGRAM)
    wb = .false.; if (present (within_bounds)) wb = within_bounds
    if (wb) then
        err = histogram_get_error_within_bounds (obj%h)
    else
        err = histogram_get_error (obj%h)
    end if
case default
    err = 0
end select
end function analysis_object_get_error

```

Return pointers to the actual contents:

(Analysis: procedures)+≡

```

function analysis_object_get_observable_ptr (obj) result (obs)
    type(observable_t), pointer :: obs
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_OBSERVABLE); obs => obj%obs
    case default;         obs => null ()
    end select
end function analysis_object_get_observable_ptr

function analysis_object_get_histogram_ptr (obj) result (h)
    type(histogram_t), pointer :: h
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_HISTOGRAM); h => obj%h
    case default;       h => null ()
    end select
end function analysis_object_get_histogram_ptr

function analysis_object_get_plot_ptr (obj) result (plot)
    type(plot_t), pointer :: plot
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_PLOT); plot => obj%p
    case default;   plot => null ()
    end select
end function analysis_object_get_plot_ptr

function analysis_object_get_graph_ptr (obj) result (g)
    type(graph_t), pointer :: g
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_GRAPH); g => obj%g
    case default;    g => null ()
    end select
end function analysis_object_get_graph_ptr

```

Return true if the object has a graphical representation:

```
<Analysis: procedures>+≡  
function analysis_object_has_plot (obj) result (flag)  
  logical :: flag  
  type(analysis_object_t), intent(in) :: obj  
  select case (obj%type)  
    case (AN_HISTOGRAM); flag = .true.  
    case (AN_PLOT);      flag = .true.  
    case (AN_GRAPH);     flag = .true.  
    case default;        flag = .false.  
  end select  
end function analysis_object_has_plot
```

Output

```
<Analysis: procedures>+≡  
subroutine analysis_object_write (obj, unit, verbose)  
  type(analysis_object_t), intent(in) :: obj  
  integer, intent(in), optional :: unit  
  logical, intent(in), optional :: verbose  
  logical :: verb  
  integer :: u  
  u = given_output_unit (unit); if (u < 0) return  
  verb = .false.; if (present (verbose)) verb = verbose  
  write (u, "(A)") repeat ("#", 79)  
  select case (obj%type)  
    case (AN_OBSERVABLE)  
      write (u, "(A)", advance="no")  "# Observable:"  
    case (AN_HISTOGRAM)  
      write (u, "(A)", advance="no")  "# Histogram: "  
    case (AN_PLOT)  
      write (u, "(A)", advance="no")  "# Plot: "  
    case (AN_GRAPH)  
      write (u, "(A)", advance="no")  "# Graph: "  
    case default  
      write (u, "(A)") "# [undefined analysis object]"  
      return  
  end select  
  write (u, "(1x,A)") char (obj%id)  
  select case (obj%type)  
    case (AN_OBSERVABLE)  
      call observable_write (obj%obs, unit)  
    case (AN_HISTOGRAM)  
      if (verb) then  
        call graph_options_write (obj%h%graph_options, unit)  
        write (u, *)  
        call drawing_options_write (obj%h%drawing_options, unit)  
        write (u, *)  
      end if  
      call histogram_write (obj%h, unit)  
    case (AN_PLOT)
```

```

        if (verb) then
            call graph_options_write (obj%p%graph_options, unit)
            write (u, *)
            call drawing_options_write (obj%p%drawing_options, unit)
            write (u, *)
        end if
        call plot_write (obj%p, unit)
    case (AN_GRAPH)
        call graph_write (obj%g, unit)
    end select
end subroutine analysis_object_write

```

Write the object part of the L^AT_EX driver file.

```

<Analysis: procedures>+≡
subroutine analysis_object_write_driver (obj, filename, unit)
    type(analysis_object_t), intent(in) :: obj
    type(string_t), intent(in) :: filename
    integer, intent(in), optional :: unit
    select case (obj%type)
    case (AN_OBSERVABLE)
        call observable_write_driver (obj%obs, unit)
    case (AN_HISTOGRAM)
        call histogram_write_gml_driver (obj%h, filename, unit)
    case (AN_PLOT)
        call plot_write_gml_driver (obj%p, filename, unit)
    case (AN_GRAPH)
        call graph_write_gml_driver (obj%g, filename, unit)
    end select
end subroutine analysis_object_write_driver

```

Return a data header for external formats, in ifile form.

```

<Analysis: procedures>+≡
subroutine analysis_object_get_header (obj, header, comment)
    type(analysis_object_t), intent(in) :: obj
    type(ifile_t), intent(inout) :: header
    type(string_t), intent(in), optional :: comment
    select case (obj%type)
    case (AN_HISTOGRAM)
        call histogram_get_header (obj%h, header, comment)
    case (AN_PLOT)
        call plot_get_header (obj%p, header, comment)
    end select
end subroutine analysis_object_get_header

```

12.5.10 Analysis object iterator

Analysis objects are containers which have iterable data structures: histograms/bins and plots/points. If they are to be treated on a common basis, it is useful to have an iterator which hides the implementation details.

The iterator is used only for elementary analysis objects that contain plot

data: histograms or plots. It is invalid for meta-objects (graphs) and non-graphical objects (observables).

```

<Analysis: public>+≡
    public :: analysis_iterator_t

<Analysis: types>+≡
    type :: analysis_iterator_t
    private
    integer :: type = AN_UNDEFINED
    type(analysis_object_t), pointer :: object => null ()
    integer :: index = 1
    type(point_t), pointer :: point => null ()
end type

```

The initializer places the iterator at the beginning of the analysis object.

```

<Analysis: procedures>+≡
    subroutine analysis_iterator_init (iterator, object)
    type(analysis_iterator_t), intent(out) :: iterator
    type(analysis_object_t), intent(in), target :: object
    iterator%object => object
    if (associated (iterator%object)) then
        iterator%type = iterator%object%type
        select case (iterator%type)
        case (AN_PLOT)
            iterator%point => iterator%object%p%first
        end select
    end if
end subroutine analysis_iterator_init

```

The iterator is valid as long as it points to an existing entry. An iterator for a data object without array data (observable) is always invalid.

```

<Analysis: public>+≡
    public :: analysis_iterator_is_valid

<Analysis: procedures>+≡
    function analysis_iterator_is_valid (iterator) result (valid)
    logical :: valid
    type(analysis_iterator_t), intent(in) :: iterator
    if (associated (iterator%object)) then
        select case (iterator%type)
        case (AN_HISTOGRAM)
            valid = iterator%index <= histogram_get_n_bins (iterator%object%h)
        case (AN_PLOT)
            valid = associated (iterator%point)
        case default
            valid = .false.
        end select
    else
        valid = .false.
    end if
end function analysis_iterator_is_valid

```

Advance the iterator.

```

<Analysis: public>+≡
    public :: analysis_iterator_advance

<Analysis: procedures>+≡
    subroutine analysis_iterator_advance (iterator)
        type(analysis_iterator_t), intent(inout) :: iterator
        if (associated (iterator%object)) then
            select case (iterator%type)
            case (AN_PLOT)
                iterator%point => iterator%point%next
            end select
            iterator%index = iterator%index + 1
        end if
    end subroutine analysis_iterator_advance

```

Retrieve the object type:

```

<Analysis: public>+≡
    public :: analysis_iterator_get_type

<Analysis: procedures>+≡
    function analysis_iterator_get_type (iterator) result (type)
        integer :: type
        type(analysis_iterator_t), intent(in) :: iterator
        type = iterator%type
    end function analysis_iterator_get_type

```

Use the iterator to retrieve data. We implement a common routine which takes the data descriptors as optional arguments. Data which do not occur in the selected type trigger to an error condition.

The iterator must point to a valid entry.

```

<Analysis: public>+≡
    public :: analysis_iterator_get_data

<Analysis: procedures>+≡
    subroutine analysis_iterator_get_data (iterator, &
        x, y, yerr, xerr, width, excess, index, n_total)
        type(analysis_iterator_t), intent(in) :: iterator
        real(default), intent(out), optional :: x, y, yerr, xerr, width, excess
        integer, intent(out), optional :: index, n_total
        select case (iterator%type)
        case (AN_HISTOGRAM)
            if (present (x)) &
                x = bin_get_midpoint (iterator%object%h%bin(iterator%index))
            if (present (y)) &
                y = bin_get_sum (iterator%object%h%bin(iterator%index))
            if (present (yerr)) &
                yerr = bin_get_error (iterator%object%h%bin(iterator%index))
            if (present (xerr)) &
                call invalid ("histogram", "xerr")
            if (present (width)) &
                width = bin_get_width (iterator%object%h%bin(iterator%index))
            if (present (excess)) &
                excess = bin_get_excess (iterator%object%h%bin(iterator%index))

```

```

        if (present (index)) &
            index = iterator%index
        if (present (n_total)) &
            n_total = histogram_get_n_bins (iterator%object%h)
    case (AN_PLOT)
        if (present (x)) &
            x = point_get_x (iterator%point)
        if (present (y)) &
            y = point_get_y (iterator%point)
        if (present (yerr)) &
            yerr = point_get_yerr (iterator%point)
        if (present (xerr)) &
            xerr = point_get_xerr (iterator%point)
        if (present (width)) &
            call invalid ("plot", "width")
        if (present (excess)) &
            call invalid ("plot", "excess")
        if (present (index)) &
            index = iterator%index
        if (present (n_total)) &
            n_total = plot_get_n_entries (iterator%object%p)
    case default
        call msg_bug ("analysis_iterator_get_data: called " &
            // "for unsupported analysis object type")
    end select
contains
    subroutine invalid (typestr, objstr)
        character(*), intent(in) :: typestr, objstr
        call msg_bug ("analysis_iterator_get_data: attempt to get '" &
            // objstr // "' for type '" // typestr // "'")
    end subroutine invalid
end subroutine analysis_iterator_get_data

```

12.5.11 Analysis store

This data structure holds all observables, histograms and such that are currently active. We have one global store; individual items are identified by their ID strings and types.

```

<Analysis: variables>≡
    type(analysis_store_t), save :: analysis_store

<Analysis: types>+≡
    type :: analysis_store_t
    private
    type(analysis_object_t), pointer :: first => null ()
    type(analysis_object_t), pointer :: last => null ()
    end type analysis_store_t

```

Delete the analysis store

```

<Analysis: public>+≡
    public :: analysis_final

```



```

<Analysis: procedures>+≡
subroutine analysis_final ()
  type(analysis_object_t), pointer :: current
  do while (associated (analysis_store%first))
    current => analysis_store%first
    analysis_store%first => current%next
    call analysis_object_final (current)
  end do
  analysis_store%last => null ()
end subroutine analysis_final

```

Append a new analysis object

```

<Analysis: procedures>+≡
subroutine analysis_store_append_object (id, type)
  type(string_t), intent(in) :: id
  integer, intent(in) :: type
  type(analysis_object_t), pointer :: obj
  allocate (obj)
  call analysis_object_init (obj, id, type)
  if (associated (analysis_store%last)) then
    analysis_store%last%next => obj
  else
    analysis_store%first => obj
  end if
  analysis_store%last => obj
end subroutine analysis_store_append_object

```

Return a pointer to the analysis object with given ID.

```

<Analysis: procedures>+≡
function analysis_store_get_object_ptr (id) result (obj)
  type(string_t), intent(in) :: id
  type(analysis_object_t), pointer :: obj
  obj => analysis_store%first
  do while (associated (obj))
    if (obj%id == id) return
    obj => obj%next
  end do
end function analysis_store_get_object_ptr

```

Initialize an analysis object: either reset it if present, or append a new entry.

```

<Analysis: procedures>+≡
subroutine analysis_store_init_object (id, type, obj)
  type(string_t), intent(in) :: id
  integer, intent(in) :: type
  type(analysis_object_t), pointer :: obj, next
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) then
    next => analysis_object_get_next_ptr (obj)
    call analysis_object_final (obj)
    call analysis_object_init (obj, id, type)
    call analysis_object_set_next_ptr (obj, next)
  else

```

```

        call analysis_store_append_object (id, type)
        obj => analysis_store%last
    end if
end subroutine analysis_store_init_object

```

Get the type of a analysis object

```

<Analysis: public>+≡
    public :: analysis_store_get_object_type

<Analysis: procedures>+≡
    function analysis_store_get_object_type (id) result (type)
        type(string_t), intent(in) :: id
        integer :: type
        type(analysis_object_t), pointer :: object
        object => analysis_store_get_object_ptr (id)
        if (associated (object)) then
            type = object%type
        else
            type = AN_UNDEFINED
        end if
    end function analysis_store_get_object_type

```

Return the number of objects in the store.

```

<Analysis: procedures>+≡
    function analysis_store_get_n_objects () result (n)
        integer :: n
        type(analysis_object_t), pointer :: current
        n = 0
        current => analysis_store%first
        do while (associated (current))
            n = n + 1
            current => current%next
        end do
    end function analysis_store_get_n_objects

```

Allocate an array and fill it with all existing IDs.

```

<Analysis: public>+≡
    public :: analysis_store_get_ids

<Analysis: procedures>+≡
    subroutine analysis_store_get_ids (id)
        type(string_t), dimension(:), allocatable, intent(out) :: id
        type(analysis_object_t), pointer :: current
        integer :: i
        allocate (id (analysis_store_get_n_objects()))
        i = 0
        current => analysis_store%first
        do while (associated (current))
            i = i + 1
            id(i) = current%id
            current => current%next
        end do
    end subroutine analysis_store_get_ids

```

12.5.12 L^AT_EX driver file

Write a driver file for all objects in the store.

```
<Analysis: procedures>+≡
subroutine analysis_store_write_driver_all (filename_data, unit)
  type(string_t), intent(in) :: filename_data
  integer, intent(in), optional :: unit
  type(analysis_object_t), pointer :: obj
  call analysis_store_write_driver_header (unit)
  obj => analysis_store%first
  do while (associated (obj))
    call analysis_object_write_driver (obj, filename_data, unit)
    obj => obj%next
  end do
  call analysis_store_write_driver_footer (unit)
end subroutine analysis_store_write_driver_all
```

Write a driver file for an array of objects.

```
<Analysis: procedures>+≡
subroutine analysis_store_write_driver_obj (filename_data, id, unit)
  type(string_t), intent(in) :: filename_data
  type(string_t), dimension(:), intent(in) :: id
  integer, intent(in), optional :: unit
  type(analysis_object_t), pointer :: obj
  integer :: i
  call analysis_store_write_driver_header (unit)
  do i = 1, size (id)
    obj => analysis_store_get_object_ptr (id(i))
    if (associated (obj)) &
      call analysis_object_write_driver (obj, filename_data, unit)
  end do
  call analysis_store_write_driver_footer (unit)
end subroutine analysis_store_write_driver_obj
```

The beginning of the driver file.

```
<Analysis: procedures>+≡
subroutine analysis_store_write_driver_header (unit)
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  write (u, '(A)') "\documentclass[12pt]{article}"
  write (u, *)
  write (u, '(A)') "\usepackage{gamelan}"
  write (u, '(A)') "\usepackage{amsmath}"
  write (u, '(A)') "\usepackage{ifpdf}"
  write (u, '(A)') "\ifpdf"
  write (u, '(A)') "  \DeclareGraphicsRule{*}{mps}{*}{"
  write (u, '(A)') "\else"
  write (u, '(A)') "  \DeclareGraphicsRule{*}{eps}{*}{"
  write (u, '(A)') "\fi"
  write (u, *)
  write (u, '(A)') "\begin{document}"
  write (u, '(A)') "\begin{gmlfile}"
```

```

write (u, *)
write (u, '(A)') "\begin{gmlcode}"
write (u, '(A)') " color col.default, col.excess;"
write (u, '(A)') " col.default = 0.9white;"
write (u, '(A)') " col.excess = red;"
write (u, '(A)') " boolean show_excess;"
!!! Future excess options for plots
! if (mcs(1)%plot_excess .and. mcs(1)%unweighted) then
!   write (u, '(A)') " show_excess = true;"
! else
write (u, '(A)') " show_excess = false;"
! end if
write (u, '(A)') "\end{gmlcode}"
write (u, *)
end subroutine analysis_store_write_driver_header

```

The end of the driver file.

```

<Analysis: procedures>+≡
subroutine analysis_store_write_driver_footer (unit)
integer, intent(in), optional :: unit
integer :: u
u = given_output_unit (unit); if (u < 0) return
write(u, *)
write(u, '(A)') "\end{gmlfile}"
write(u, '(A)') "\end{document}"
end subroutine analysis_store_write_driver_footer

```

12.5.13 API

Creating new objects

The specific versions below:

```

<Analysis: public>+≡
public :: analysis_init_observable

<Analysis: procedures>+≡
subroutine analysis_init_observable (id, obs_label, obs_unit, graph_options)
type(string_t), intent(in) :: id
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(analysis_object_t), pointer :: obj
type(observable_t), pointer :: obs
call analysis_store_init_object (id, AN_OBSERVABLE, obj)
obs => analysis_object_get_observable_ptr (obj)
call observable_init (obs, obs_label, obs_unit, graph_options)
end subroutine analysis_init_observable

<Analysis: public>+≡
public :: analysis_init_histogram

<Analysis: interfaces>+≡
interface analysis_init_histogram
module procedure analysis_init_histogram_n_bins

```

```

    module procedure analysis_init_histogram_bin_width
end interface

```

<Analysis: procedures>+≡

```

subroutine analysis_init_histogram_n_bins &
    (id, lower_bound, upper_bound, n_bins, normalize_bins, &
     obs_label, obs_unit, graph_options, drawing_options)
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound
integer, intent(in) :: n_bins
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
type(analysis_object_t), pointer :: obj
type(histogram_t), pointer :: h
call analysis_store_init_object (id, AN_HISTOGRAM, obj)
h => analysis_object_get_histogram_ptr (obj)
call histogram_init (h, id, &
    lower_bound, upper_bound, n_bins, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
end subroutine analysis_init_histogram_n_bins

```

```

subroutine analysis_init_histogram_bin_width &
    (id, lower_bound, upper_bound, bin_width, normalize_bins, &
     obs_label, obs_unit, graph_options, drawing_options)
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound, bin_width
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
type(analysis_object_t), pointer :: obj
type(histogram_t), pointer :: h
call analysis_store_init_object (id, AN_HISTOGRAM, obj)
h => analysis_object_get_histogram_ptr (obj)
call histogram_init (h, id, &
    lower_bound, upper_bound, bin_width, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
end subroutine analysis_init_histogram_bin_width

```

<Analysis: public>+≡

```

public :: analysis_init_plot

```

<Analysis: procedures>+≡

```

subroutine analysis_init_plot (id, graph_options, drawing_options)
type(string_t), intent(in) :: id
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
type(analysis_object_t), pointer :: obj
type(plot_t), pointer :: plot
call analysis_store_init_object (id, AN_PLOT, obj)
plot => analysis_object_get_plot_ptr (obj)
call plot_init (plot, id, graph_options, drawing_options)

```

```

end subroutine analysis_init_plot

<Analysis: public>+≡
public :: analysis_init_graph

<Analysis: procedures>+≡
subroutine analysis_init_graph (id, n_elements, graph_options)
  type(string_t), intent(in) :: id
  integer, intent(in) :: n_elements
  type(graph_options_t), intent(in), optional :: graph_options
  type(analysis_object_t), pointer :: obj
  type(graph_t), pointer :: graph
  call analysis_store_init_object (id, AN_GRAPH, obj)
  graph => analysis_object_get_graph_ptr (obj)
  call graph_init (graph, id, n_elements, graph_options)
end subroutine analysis_init_graph

```

Recording data

This procedure resets an object or the whole store to its initial state.

```

<Analysis: public>+≡
public :: analysis_clear

<Analysis: interfaces>+≡
interface analysis_clear
  module procedure analysis_store_clear_obj
  module procedure analysis_store_clear_all
end interface

<Analysis: procedures>+≡
subroutine analysis_store_clear_obj (id)
  type(string_t), intent(in) :: id
  type(analysis_object_t), pointer :: obj
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) then
    call analysis_object_clear (obj)
  end if
end subroutine analysis_store_clear_obj

subroutine analysis_store_clear_all ()
  type(analysis_object_t), pointer :: obj
  obj => analysis_store%first
  do while (associated (obj))
    call analysis_object_clear (obj)
    obj => obj%next
  end do
end subroutine analysis_store_clear_all

```

There is one generic recording function whose behavior depends on the type of analysis object.

```

<Analysis: public>+≡
public :: analysis_record_data

```

<Analysis: procedures>+≡

```

subroutine analysis_record_data (id, x, y, yerr, xerr, &
    weight, excess, success, exist)
    type(string_t), intent(in) :: id
    real(default), intent(in) :: x
    real(default), intent(in), optional :: y, yerr, xerr, weight, excess
    logical, intent(out), optional :: success, exist
    type(analysis_object_t), pointer :: obj
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        call analysis_object_record_data (obj, x, y, yerr, xerr, &
            weight, excess, success)
        if (present (exist)) exist = .true.
    else
        if (present (success)) success = .false.
        if (present (exist)) exist = .false.
    end if
end subroutine analysis_record_data

```

Build a graph

This routine sets up the array of graph elements by copying the graph elements given as input. The object must exist and already be initialized as a graph.

<Analysis: public>+≡

```

public :: analysis_fill_graph

```

<Analysis: procedures>+≡

```

subroutine analysis_fill_graph (id, i, id_in, drawing_options)
    type(string_t), intent(in) :: id
    integer, intent(in) :: i
    type(string_t), intent(in) :: id_in
    type(drawing_options_t), intent(in), optional :: drawing_options
    type(analysis_object_t), pointer :: obj
    type(graph_t), pointer :: g
    type(histogram_t), pointer :: h
    type(plot_t), pointer :: p
    obj => analysis_store_get_object_ptr (id)
    g => analysis_object_get_graph_ptr (obj)
    obj => analysis_store_get_object_ptr (id_in)
    if (associated (obj)) then
        select case (obj%type)
            case (AN_HISTOGRAM)
                h => analysis_object_get_histogram_ptr (obj)
                call graph_insert_histogram (g, i, h, drawing_options)
            case (AN_PLOT)
                p => analysis_object_get_plot_ptr (obj)
                call graph_insert_plot (g, i, p, drawing_options)
            case default
                call msg_error ("Graph '" // char (id) // "': Element '" &
                    // char (id_in) // "' is neither histogram nor plot.")
        end select
    else
        call msg_error ("Graph '" // char (id) // "': Element '" &

```

```

        // char (id_in) // '' is undefined.")
    end if
end subroutine analysis_fill_graph

```

Retrieve generic results

Check if a named object exists.

```

<Analysis: public>+≡
    public :: analysis_exists

<Analysis: procedures>+≡
    function analysis_exists (id) result (flag)
        type(string_t), intent(in) :: id
        logical :: flag
        type(analysis_object_t), pointer :: obj
        flag = .true.
        obj => analysis_store%first
        do while (associated (obj))
            if (obj%id == id) return
            obj => obj%next
        end do
        flag = .false.
    end function analysis_exists

```

The following functions should work for all kinds of analysis object:

```

<Analysis: public>+≡
    public :: analysis_get_n_elements
    public :: analysis_get_n_entries
    public :: analysis_get_average
    public :: analysis_get_error

<Analysis: procedures>+≡
    function analysis_get_n_elements (id) result (n)
        integer :: n
        type(string_t), intent(in) :: id
        type(analysis_object_t), pointer :: obj
        obj => analysis_store_get_object_ptr (id)
        if (associated (obj)) then
            n = analysis_object_get_n_elements (obj)
        else
            n = 0
        end if
    end function analysis_get_n_elements

    function analysis_get_n_entries (id, within_bounds) result (n)
        integer :: n
        type(string_t), intent(in) :: id
        logical, intent(in), optional :: within_bounds
        type(analysis_object_t), pointer :: obj
        obj => analysis_store_get_object_ptr (id)
        if (associated (obj)) then
            n = analysis_object_get_n_entries (obj, within_bounds)
        else

```



```

        n = 0
    end if
end function analysis_get_n_entries

function analysis_get_average (id, within_bounds) result (avg)
    real(default) :: avg
    type(string_t), intent(in) :: id
    type(analysis_object_t), pointer :: obj
    logical, intent(in), optional :: within_bounds
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        avg = analysis_object_get_average (obj, within_bounds)
    else
        avg = 0
    end if
end function analysis_get_average

function analysis_get_error (id, within_bounds) result (err)
    real(default) :: err
    type(string_t), intent(in) :: id
    type(analysis_object_t), pointer :: obj
    logical, intent(in), optional :: within_bounds
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        err = analysis_object_get_error (obj, within_bounds)
    else
        err = 0
    end if
end function analysis_get_error

```

Return true if any analysis object is graphical

```

<Analysis: public>+≡
    public :: analysis_has_plots

<Analysis: interfaces>+≡
    interface analysis_has_plots
        module procedure analysis_has_plots_any
        module procedure analysis_has_plots_obj
    end interface

<Analysis: procedures>+≡
    function analysis_has_plots_any () result (flag)
        logical :: flag
        type(analysis_object_t), pointer :: obj
        flag = .false.
        obj => analysis_store%first
        do while (associated (obj))
            flag = analysis_object_has_plot (obj)
            if (flag) return
        end do
    end function analysis_has_plots_any

    function analysis_has_plots_obj (id) result (flag)
        logical :: flag

```

```

type(string_t), dimension(:), intent(in) :: id
type(analysis_object_t), pointer :: obj
integer :: i
flag = .false.
do i = 1, size (id)
  obj => analysis_store_get_object_ptr (id(i))
  if (associated (obj)) then
    flag = analysis_object_has_plot (obj)
    if (flag) return
  end if
end do
end function analysis_has_plots_obj

```

Iterators

Initialize an iterator for the given object. If the object does not exist or has wrong type, the iterator will be invalid.

```

<Analysis: public>+≡
public :: analysis_init_iterator

<Analysis: procedures>+≡
subroutine analysis_init_iterator (id, iterator)
  type(string_t), intent(in) :: id
  type(analysis_iterator_t), intent(out) :: iterator
  type(analysis_object_t), pointer :: obj
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) call analysis_iterator_init (iterator, obj)
end subroutine analysis_init_iterator

```

Output

```

<Analysis: public>+≡
public :: analysis_write

<Analysis: interfaces>+≡
interface analysis_write
  module procedure analysis_write_object
  module procedure analysis_write_all
end interface

<Analysis: procedures>+≡
subroutine analysis_write_object (id, unit, verbose)
  type(string_t), intent(in) :: id
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  type(analysis_object_t), pointer :: obj
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) then
    call analysis_object_write (obj, unit, verbose)
  else
    call msg_error ("Analysis object '" // char (id) // "' not found")
  end if
end if

```

```

end subroutine analysis_write_object

subroutine analysis_write_all (unit, verbose)
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  type(analysis_object_t), pointer :: obj
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  obj => analysis_store%first
  do while (associated (obj))
    call analysis_object_write (obj, unit, verbose)
    obj => obj%next
  end do
end subroutine analysis_write_all

<Analysis: public>+≡
public :: analysis_write_driver

<Analysis: procedures>+≡
subroutine analysis_write_driver (filename_data, id, unit)
  type(string_t), intent(in) :: filename_data
  type(string_t), dimension(:), intent(in), optional :: id
  integer, intent(in), optional :: unit
  if (present (id)) then
    call analysis_store_write_driver_obj (filename_data, id, unit)
  else
    call analysis_store_write_driver_all (filename_data, unit)
  end if
end subroutine analysis_write_driver

<Analysis: public>+≡
public :: analysis_compile_tex

<Analysis: procedures>+≡
subroutine analysis_compile_tex (file, has_gmlcode, os_data)
  type(string_t), intent(in) :: file
  logical, intent(in) :: has_gmlcode
  type(os_data_t), intent(in) :: os_data
  type(string_t) :: setenv
  integer :: status
  if (os_data%event_analysis_ps) then
    call os_system_call ("make compile " // os_data%makeflags // " -f " // &
      char (file) // "_ana.makefile", status)
    if (status /= 0) then
      call msg_error ("Unable to compile analysis output file")
    end if
  else
    call msg_warning ("Skipping results display because " &
      // "latex/mpost/dvips is not available")
  end if
end subroutine analysis_compile_tex

```

Write header for generic data output to an ifile.

```

<Analysis: public>+≡

```

```

public :: analysis_get_header
<Analysis: procedures>+≡
subroutine analysis_get_header (id, header, comment)
  type(string_t), intent(in) :: id
  type(ifile_t), intent(inout) :: header
  type(string_t), intent(in), optional :: comment
  type(analysis_object_t), pointer :: object
  object => analysis_store_get_object_ptr (id)
  if (associated (object)) then
    call analysis_object_get_header (object, header, comment)
  end if
end subroutine analysis_get_header

```

Write a makefile in order to do the compile steps.

```

<Analysis: public>+≡
public :: analysis_write_makefile
<Analysis: procedures>+≡
subroutine analysis_write_makefile (filename, unit, has_gmlcode, os_data)
  type(string_t), intent(in) :: filename
  integer, intent(in) :: unit
  logical, intent(in) :: has_gmlcode
  type(os_data_t), intent(in) :: os_data
  type(string_t) :: setenv
  write (unit, "(3A)")  "# WHIZARD: Makefile for analysis '", &
    char (filename), "'"
  write (unit, "(A)")  "# Automatically generated file, do not edit"
  write (unit, "(A)")  ""
  write (unit, "(A)")  "# LaTeX setup"
  write (unit, "(A)")  "LATEX = " // char (os_data%latex)
  write (unit, "(A)")  "MPOST = " // char (os_data%mpost)
  write (unit, "(A)")  "GML = " // char (os_data%gml)
  write (unit, "(A)")  "DVIPS = " // char (os_data%dvips)
  write (unit, "(A)")  "PS2PDF = " // char (os_data%ps2pdf)
  write (unit, "(A)")  'TEX_FLAGS = "$$TEXINPUTS:' // &
    char(os_data%whizard_texpath) // ' "'
  write (unit, "(A)")  'MP_FLAGS = "$$MPINPUTS:' // &
    char(os_data%whizard_texpath) // ' "'
  write (unit, "(A)")  ""
  write (unit, "(5A)")  "TEX_SOURCES = ", char (filename), ".tex"
  if (os_data%event_analysis_pdf) then
    write (unit, "(5A)")  "TEX_OBJECTS = ", char (filename), ".pdf"
  else
    write (unit, "(5A)")  "TEX_OBJECTS = ", char (filename), ".ps"
  end if
  if (os_data%event_analysis_ps) then
    if (os_data%event_analysis_pdf) then
      write (unit, "(5A)")  char (filename), ".pdf: ", &
        char (filename), ".tex"
    else
      write (unit, "(5A)")  char (filename), ".ps: ", &
        char (filename), ".tex"
    end if
  end if
  write (unit, "(5A)")  TAB, "-TEXINPUTS=$(TEX_FLAGS) $(LATEX) " // &

```

```

        char (filename) // ".tex"
    if (has_gmlcode) then
        write (unit, "(5A)") TAB, "$(GML) " // char (filename)
        write (unit, "(5A)") TAB, "TEXINPUTS=$(TEX_FLAGS) $(LATEX) " // &
            char (filename) // ".tex"
    end if
    write (unit, "(5A)") TAB, "$(DVIPS) -o " // char (filename) // ".ps " // &
        char (filename) // ".dvi"
    if (os_data%event_analysis_pdf) then
        write (unit, "(5A)") TAB, "$(PS2PDF) " // char (filename) // ".ps"
    end if
end if
write (unit, "(A)")
write (unit, "(A)") "compile: $(TEX_OBJECTS)"
write (unit, "(A)") ".PHONY: compile"
write (unit, "(A)")
write (unit, "(5A)") "CLEAN_OBJECTS = ", char (filename), ".aux"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".log"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".dvi"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".out"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".[1-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".[1-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".[1-9][0-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".t[1-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".t[1-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".t[1-9][0-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".ltp"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".mp"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".mpx"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".dvi"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".ps"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (filename), ".pdf"
write (unit, "(A)")
write (unit, "(A)") "# Generic cleanup targets"
write (unit, "(A)") "clean-objects:"
write (unit, "(A)") TAB // "rm -f $(CLEAN_OBJECTS)"
write (unit, "(A)") ""
write (unit, "(A)") "clean: clean-objects"
write (unit, "(A)") ".PHONY: clean"
end subroutine analysis_write_makefile

```

12.5.14 Unit tests

```

<Analysis: public>+≡
    public :: analysis_test

<Analysis: procedures>+≡
    subroutine analysis_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Analysis: execute tests>
    end subroutine analysis_test

```

```

<Analysis: execute tests>≡
  call test (analysis_1, "analysis_1", &
    "check elementary analysis building blocks", &
    u, results)

<Analysis: tests>≡
  subroutine analysis_1 (u)
    integer, intent(in) :: u
    type(string_t) :: id1, id2, id3, id4
    integer :: i
    id1 = "foo"
    id2 = "bar"
    id3 = "hist"
    id4 = "plot"

    write (u, "(A)")  "* Test output: Analysis"
    write (u, "(A)")  "* Purpose: test the analysis routines"
    write (u, "(A)")

    call analysis_init_observable (id1)
    call analysis_init_observable (id2)
    call analysis_init_histogram_bin_width &
      (id3, 0.5_default, 5.5_default, 1._default, normalize_bins=.false.)
    call analysis_init_plot (id4)
    do i = 1, 3
      write (u, "(A,1x," // FMT_19 // ")") "data = ", real(i,default)
      call analysis_record_data (id1, real(i,default))
      call analysis_record_data (id2, real(i,default), &
        weight=real(i,default))
      call analysis_record_data (id3, real(i,default))
      call analysis_record_data (id4, real(i,default), real(i,default)**2)
    end do
    write (u, "(A,10(1x,I5))") "n_entries = ", &
      analysis_get_n_entries (id1), &
      analysis_get_n_entries (id2), &
      analysis_get_n_entries (id3), &
      analysis_get_n_entries (id3, within_bounds = .true.), &
      analysis_get_n_entries (id4), &
      analysis_get_n_entries (id4, within_bounds = .true.)
    write (u, "(A,10(1x," // FMT_19 // ")") "average = ", &
      analysis_get_average (id1), &
      analysis_get_average (id2), &
      analysis_get_average (id3), &
      analysis_get_average (id3, within_bounds = .true.)
    write (u, "(A,10(1x," // FMT_19 // ")") "error = ", &
      analysis_get_error (id1), &
      analysis_get_error (id2), &
      analysis_get_error (id3), &
      analysis_get_error (id3, within_bounds = .true.)

    write (u, "(A)")
    write (u, "(A)") "* Clear analysis #2"
    write (u, "(A)")

    call analysis_clear (id2)

```

```

do i = 4, 6
  print *, "data = ", real(i,default)
  call analysis_record_data (id1, real(i,default))
  call analysis_record_data (id2, real(i,default), &
                             weight=real(i,default))
  call analysis_record_data (id3, real(i,default))
  call analysis_record_data (id4, real(i,default), real(i,default)**2)
end do
write (u, "(A,10(1x,I5))") "n_entries = ", &
  analysis_get_n_entries (id1), &
  analysis_get_n_entries (id2), &
  analysis_get_n_entries (id3), &
  analysis_get_n_entries (id3, within_bounds = .true.), &
  analysis_get_n_entries (id4), &
  analysis_get_n_entries (id4, within_bounds = .true.)
write (u, "(A,10(1x," // FMT_19 // ")") "average = ", &
  analysis_get_average (id1), &
  analysis_get_average (id2), &
  analysis_get_average (id3), &
  analysis_get_average (id3, within_bounds = .true.)
write (u, "(A,10(1x," // FMT_19 // ")") "error = ", &
  analysis_get_error (id1), &
  analysis_get_error (id2), &
  analysis_get_error (id3), &
  analysis_get_error (id3, within_bounds = .true.)
write (u, "(A)")
call analysis_write (u)

write (u, "(A)")
write (u, "(A)") "* Cleanup"

call analysis_clear ()
call analysis_final ()

write (u, "(A)")
write (u, "(A)") "* Test output end: analysis_1"
end subroutine analysis_1

```

Chapter 13

Matrix Element Handling

In this chapter, we support internal and external matrix elements: initialization, automatic generation where necessary, and numerical evaluation. We provide the interface for code generation and linking. Matrix-element code is organized in processes and process libraries.

process_constants A record of static process properties, for easy transfer between various WHIZARD modules.

prclib_interfaces This module deals with matrix-element code which is accessible via external libraries (Fortran libraries or generic C-compatible libraries) and must either be generated by the program or provided by the user explicitly.

The module defines and uses an abstract type `prc_writer_t` and two abstract extensions, one for a Fortran module and one for a C-compatible library. The implementation provides the specific methods for writing the appropriate parts in external matrix element code.

prc_core_def This module defines the abstract types `prc_core_def_t` and `prc_driver_t`. The implementation of the former provides the configuration for processes of a certain class, while the latter accesses the corresponding matrix element, in particular those generated by the appropriate `prc_writer_t` object.

process_libraries This module combines the functionality of the previous module with the means for holding processes definitions (the internal counterpart of appropriate declarations in the user interface), for handling matrix elements which do not need external code, and for accessing the matrix elements by the procedures for matrix-element evaluation, integration and event generation.

prclib_stacks Collect process libraries.

test_me This module provides a test implementation for the abstract types in the `prc_core_def` module. The implementation is intended for self-tests of several later modules. The implementation is internal, i.e., no external code has is generated.

All data structures which are specific for a particular way of generating code or evaluating matrix element are kept abstract and thus generic. Later modules such as `prc_omega` provide implementations, in the form of type extensions for the various abstract types.

13.1 Process data block

We define a simple transparent type that contains universal constant process data. We will reference objects of this type for the phase-space setup, for interfacing with process libraries, for implementing matrix-element generation, and in the master process-handling module.

```
<process_constants.f90>≡
  <File header>
```

```
  module process_constants
```

```
    <Use kinds>
```

```
    <Use strings>
```

```
    <Standard module head>
```

```
    <Process constants: public>
```

```
    <Process constants: types>
```

```
  contains
```

```
    <Process constants: procedures>
```

```
  end module process_constants
```

The data type is just a block of public objects, only elementary types, no type-bound procedures.

```
<Process constants: public>≡
```

```
  public :: process_constants_t
```

```
<Process constants: types>≡
```

```
  type :: process_constants_t
```

```
    type(string_t) :: id
```

```
    type(string_t) :: model_name
```

```
    character(32) :: md5sum = ""
```

```
    logical :: openmp_supported = .false.
```

```
    integer :: n_in = 0
```

```
    integer :: n_out = 0
```

```
    integer :: n_flv = 0
```

```
    integer :: n_hel = 0
```

```
    integer :: n_col = 0
```

```
    integer :: n_cin = 0
```

```
    integer :: n_cf = 0
```

```
    integer, dimension(:,:), allocatable :: flv_state
```

```
    integer, dimension(:,:), allocatable :: hel_state
```

```
    integer, dimension(:,:), allocatable :: col_state
```

```
    logical, dimension(:,:), allocatable :: ghost_flag
```

```
    complex(default), dimension(:), allocatable :: color_factors
```

```
    integer, dimension(:,:), allocatable :: cf_index
```

```
  contains
```

```
    <Process constants: prc const: TBP>
```

```
  end type process_constants_t
```

```

<Process constants: prc const: TBP>≡
    procedure :: get_flv_state => process_constants_get_flv_state

<Process constants: procedures>≡
    function process_constants_get_flv_state (prc_const) result (flv_state)
        class(process_constants_t), intent(in) :: prc_const
        integer, dimension(:,:), allocatable :: flv_state
        flv_state = prc_const%flv_state
    end function process_constants_get_flv_state

<Process constants: prc const: TBP>+≡
    procedure :: get_hel_state => process_constants_get_hel_state

<Process constants: procedures>+≡
    subroutine process_constants_get_hel_state (prc_const, hel_state)
        class(process_constants_t), intent(in) :: prc_const
        integer, dimension(:,:), allocatable :: hel_state
        hel_state = prc_const%hel_state
    end subroutine process_constants_get_hel_state

<Process constants: prc const: TBP>+≡
    procedure :: get_col_state => process_constants_get_col_state

<Process constants: procedures>+≡
    subroutine process_constants_get_col_state (prc_const, col_state)
        class(process_constants_t), intent(in) :: prc_const
        integer, dimension(:,:,:), allocatable :: col_state
        col_state = prc_const%col_state
    end subroutine process_constants_get_col_state

<Process constants: prc const: TBP>+≡
    procedure :: get_ghost_flag => process_constants_get_ghost_flag

<Process constants: procedures>+≡
    function process_constants_get_ghost_flag (prc_const) result(ghost_flag)
        class(process_constants_t), intent(in) :: prc_const
        logical, dimension(:,:), allocatable :: ghost_flag
        ghost_flag = prc_const%ghost_flag
    end function process_constants_get_ghost_flag

<Process constants: prc const: TBP>+≡
    procedure :: get_color_factors => process_constants_get_color_factors

<Process constants: procedures>+≡
    subroutine process_constants_get_color_factors (prc_const, col_facts)
        class(process_constants_t), intent(in) :: prc_const
        complex(default), intent(inout), dimension(:), allocatable :: col_facts
        col_facts = prc_const%color_factors
    end subroutine process_constants_get_color_factors

<Process constants: prc const: TBP>+≡
    procedure :: get_cf_index => process_constants_get_cf_index

```

```

<Process constants: procedures>+≡
  subroutine process_constants_get_cf_index (prc_const, cf_index)
    class(process_constants_t), intent(in) :: prc_const
    integer, intent(inout), dimension(:,:), allocatable :: cf_index
    cf_index = prc_const%cf_index
  end subroutine process_constants_get_cf_index

<Process constants: prc const: TBP>+≡
  procedure :: set_flv_state => process_constants_set_flv_state

<Process constants: procedures>+≡
  subroutine process_constants_set_flv_state (prc_const, flv_state)
    class(process_constants_t), intent(inout) :: prc_const
    integer, intent(in), dimension(:,:), allocatable :: flv_state
    prc_const%flv_state = flv_state
  end subroutine process_constants_set_flv_state

<Process constants: prc const: TBP>+≡
  procedure :: set_col_state => process_constants_set_col_state

<Process constants: procedures>+≡
  subroutine process_constants_set_col_state (prc_const, col_state)
    class(process_constants_t), intent(inout) :: prc_const
    integer, intent(in), dimension(:,:,:), allocatable :: col_state
    prc_const%col_state = col_state
  end subroutine process_constants_set_col_state

<Process constants: prc const: TBP>+≡
  procedure :: set_cf_index => process_constants_set_cf_index

<Process constants: procedures>+≡
  subroutine process_constants_set_cf_index (prc_const, cf_index)
    class(process_constants_t), intent(inout) :: prc_const
    integer, dimension(:,:), intent(in), allocatable :: cf_index
    prc_const%cf_index = cf_index
  end subroutine process_constants_set_cf_index

<Process constants: prc const: TBP>+≡
  procedure :: set_color_factors => process_constants_set_color_factors

<Process constants: procedures>+≡
  subroutine process_constants_set_color_factors (prc_const, color_factors)
    class(process_constants_t), intent(inout) :: prc_const
    complex(default), dimension(:), intent(in), allocatable :: color_factors
    prc_const%color_factors = color_factors
  end subroutine process_constants_set_color_factors

<Process constants: prc const: TBP>+≡
  procedure :: set_ghost_flag => process_constants_set_ghost_flag

```

```

<Process constants: procedures>+≡
  subroutine process_constants_set_ghost_flag (prc_const, ghost_flag)
    class(process_constants_t), intent(inout) :: prc_const
    logical, intent(in), dimension(:,:), allocatable :: ghost_flag
    prc_const%ghost_flag = ghost_flag
  end subroutine process_constants_set_ghost_flag

```

13.2 Process library interface

The module `prclib_interfaces` handles external matrix-element code.

13.2.1 Overview

The top-level data structure is the `prclib_driver_t` data type. The associated type-bound procedures deal with the generation of external code, compilation and linking, and accessing the active external library.

An object of type `prclib_driver_t` consists of the following parts:

1. Metadata that identify name and status of the library driver, etc.
2. An array of process records (`prclib_driver_record_t`), one for each external matrix element.
3. A record of type `dlaccess_t` which handles the operating-system part of linking a dynamically loadable library.
4. A collection of procedure pointers which have a counterpart in the external library interface. Given the unique identifier of a matrix element, the procedures retrieve generic matrix-element information such as the particle content and helicity combination tables. There is also a procedure which returns pointers to the more specific procedures that a matrix element provides, called *features*.

The process records of type `prclib_driver_record_t` handle the individual matrix elements. Each record identifies a process by name (`id`), names the physics model to be loaded for this process, lists the features that the associated matrix-element code provides, and holds a `writer` object which handles all operations that depend on the process type. The numbering of process records is identical to the numbering of matrix-element codes in the external library.

The writer object is of abstract type `prc_writer_t`. The module defines two basic, also abstract, extensions: `prc_writer_f_module_t` and `prc_writer_c_lib_t`. The first version is for matrix-element code that is available in form of Fortran modules. The writer contains type-bound procedures which create appropriate `use` directives and C-compatible wrapper functions for the given set of Fortran modules and their features. The second version is for matrix-element code that is available in form of a C-compatible library (this includes Fortran libraries with proper C bindings). The writer needs not write wrapper function, but explicit interface blocks for the matrix-element features.

Each matrix-element variant is encoded in an appropriate extension of `prc_writer_t`. For instance, `O'MEGA` matrix elements provide an implementation `omega_writer_t` which extends `prc_writer_f_module_t`.

13.2.2 Workflow

We expect that the functionality provided by this module is called in the following order:

1. The caller initializes the `prclib_driver_t` object and fills the array of `prclib_record_t` entries with the appropriate process data and process-specific writer objects.
2. It calls the `generate_makefile` method to set up an appropriate makefile in the current directory. The makefile will handle source generation, compilation and linking both for the individual matrix elements (unless this has to be done manually) and for the common external driver code which interfaces those matrix element.
3. The `generate_driver_code` writes the common driver as source code to file.
4. The methods `make_source`, `make_compile`, and `make_link` individually perform the corresponding steps in building the library. Wherever possible, they simply use the generated makefile. By calling `make`, we make sure that we can avoid unnecessary recompilation. For the compilation and linking steps, the makefile will employ `libtool`.
5. The `load` method loads the library procedures into the corresponding procedure pointers, using the `dlopen` mechanism via the `dlaccess` subobject.

13.2.3 The module

```
<prclib_interfaces.f90>≡  
<File header>  
  
module prclib_interfaces  
  
    use, intrinsic :: iso_c_binding !NODEP!  
  
    use kinds  
<Use strings>  
    use io_units  
    use unit_tests  
    use system_defs, only: TAB  
    use diagnostics  
    use os_interface  
  
<Standard module head>  
  
<Prclib interfaces: public>  
  
<Prclib interfaces: types>  
  
<Prclib interfaces: interfaces>  
  
<Prclib interfaces: test types>
```

```

contains

<Prclib interfaces: procedures>

<Prclib interfaces: tests>

end module prclib_interfaces

```

13.2.4 Writers

External matrix element code provides externally visible procedures, which we denote as *features*. The features consist of informational subroutines and functions which are mandatory (universal features) and matrix-element specific subroutines and functions (specific features). The driver interfaces the generic features directly, while it returns the specific features in form of `bind(C)` procedure pointers to the caller. For instance, function `n_in` is generic, while the matrix matrix-element value itself is specific.

To implement these tasks, the driver needs `use` directives for Fortran module procedures, interface blocks for other external stuff, wrapper code, and Makefile snippets.

Generic writer

In the `prc_writer_t` data type, we collect the procedures which implement the writing tasks. The type is abstract. The concrete implementations are defined by an extension which is specific for the process type.

The MD5 sum stored here should be the MD5 checksum of the current process component, which can be calculated once the process is configured completely. It can be used by implementations which work with external files, such as O'MEGA.

```

<Prclib interfaces: public>≡
    public :: prc_writer_t

<Prclib interfaces: types>≡
    type, abstract :: prc_writer_t
        character(32) :: md5sum = ""
    contains
    <Prclib interfaces: prc writer: TBP>
    end type prc_writer_t

```

In any case, it is useful to have a string representation of the writer type. This must be implemented by all extensions.

```

<Prclib interfaces: prc writer: TBP>≡
    procedure(get_const_string), nopass, deferred :: type_name

<Prclib interfaces: interfaces>≡
    abstract interface
        function get_const_string () result (string)
            import
            type(string_t) :: string
        end function get_const_string
    end interface

```

Return the name of a procedure that implements a given feature, as it is provided by the external matrix-element code. For a reasonable default, we take the feature name unchanged.

```

<Prclib interfaces: prc writer: TBP>+≡
  procedure, nopass :: get_procname => prc_writer_get_procname

<Prclib interfaces: procedures>≡
  function prc_writer_get_procname (feature) result (name)
    type(string_t) :: name
    type(string_t), intent(in) :: feature
    name = feature
  end function prc_writer_get_procname

```

Return the name of a procedure that implements a given feature with the bind(C) property, so it can be accessed via a C procedure pointer and handled by dlopen. We need this for all special features of a matrix element, since the interface has to return a C function pointer for it. For a default implementation, we prefix the external procedure name by the process ID.

```

<Prclib interfaces: prc writer: TBP>+≡
  procedure :: get_c_procname => prc_writer_get_c_procname

<Prclib interfaces: procedures>+≡
  function prc_writer_get_c_procname (writer, id, feature) result (name)
    class(prc_writer_t), intent(in) :: writer
    type(string_t), intent(in) :: id, feature
    type(string_t) :: name
    name = id // "_" // feature
  end function prc_writer_get_c_procname

```

Common signature of code-writing procedures. The procedure may use the process ID, and the feature name. (Not necessarily all of them.)

```

<Prclib interfaces: interfaces>+≡
  abstract interface
    subroutine write_code_file (writer, id)
      import
      class(prc_writer_t), intent(in) :: writer
      type(string_t), intent(in) :: id
    end subroutine write_code_file
  end interface

  abstract interface
    subroutine write_code (writer, unit, id)
      import
      class(prc_writer_t), intent(in) :: writer
      integer, intent(in) :: unit
      type(string_t), intent(in) :: id
    end subroutine write_code
  end interface

  abstract interface
    subroutine write_code_os (writer, unit, id, os_data, testflag)
      import
      class(prc_writer_t), intent(in) :: writer

```



```

        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: testflag
    end subroutine write_code_os
end interface

abstract interface
    subroutine write_feature_code (writer, unit, id, feature)
        import
        class(prc_writer_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id, feature
    end subroutine write_feature_code
end interface

```

There must be a procedure which writes an interface block for a given feature. If the external matrix element is implemented as a Fortran module, this is required only for the specific features which are returned as procedure pointers.

```

<Prclib interfaces: prc writer: TBP>+≡
    procedure(write_feature_code), deferred :: write_interface

```

There must also be a procedure which writes Makefile code which is specific for the current process, but not the feature.

```

<Prclib interfaces: prc writer: TBP>+≡
    procedure(write_code_os), deferred :: write_makefile_code

```

This procedure writes code process-specific source-code file (which need not be Fortran). It may be a no-op, if the source code is generated by Make instead.

```

<Prclib interfaces: prc writer: TBP>+≡
    procedure(write_code_file), deferred :: write_source_code

```

Writer for Fortran-module matrix elements

If the matrix element is available as a Fortran module, we have specific requirements: (i) the features are imported via `use` directives, (ii) the specific features require `bind(C)` wrappers.

The type is still abstract, all methods must be implemented explicitly for a specific matrix-element variant.

```

<Prclib interfaces: public>+≡
    public :: prc_writer_f_module_t

<Prclib interfaces: types>+≡
    type, extends (prc_writer_t), abstract :: prc_writer_f_module_t
    contains
    <Prclib interfaces: prc writer f module: TBP>
    end type prc_writer_f_module_t

```

Return the name of the Fortran module. As a default implementation, we take the process ID unchanged.

```

<Prclib interfaces: prc writer f module: TBP>≡
    procedure, nopass :: get_module_name => prc_writer_get_module_name

```

```

<Prclib interfaces: procedures>+≡
function prc_writer_get_module_name (id) result (name)
  type(string_t) :: name
  type(string_t), intent(in) :: id
  name = id
end function prc_writer_get_module_name

```

Write a `use` directive that associates the driver reference with the procedure in the matrix element code. By default, we use the C name for this.

```

<Prclib interfaces: prc writer f module: TBP>+≡
  procedure :: write_use_line => prc_writer_write_use_line

<Prclib interfaces: procedures>+≡
subroutine prc_writer_write_use_line (writer, unit, id, feature)
  class(prc_writer_f_module_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t) :: id, feature
  write (unit, "(2x,9A)") "use ", char (writer%get_module_name (id)), &
    ", only: ", char (writer%get_c_procname (id, feature)), &
    " => ", char (writer%get_procname (feature))
end subroutine prc_writer_write_use_line

```

Write a wrapper routine for a feature. This also associates a C name the module procedure. The details depend on the writer variant.

```

<Prclib interfaces: prc writer f module: TBP>+≡
  procedure(prc_write_wrapper), deferred :: write_wrapper

<Prclib interfaces: interfaces>+≡
abstract interface
  subroutine prc_write_wrapper (writer, unit, id, feature)
    import
    class(prc_writer_f_module_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id, feature
  end subroutine prc_write_wrapper
end interface

```

This is used for testing only: initialize the writer with a specific MD5 sum string.

```

<Prclib interfaces: prc writer: TBP>+≡
  procedure :: init_test => prc_writer_init_test

<Prclib interfaces: procedures>+≡
subroutine prc_writer_init_test (writer)
  class(prc_writer_t), intent(out) :: writer
  writer%md5sum = "1234567890abcdef1234567890abcdef"
end subroutine prc_writer_init_test

```

Writer for C-library matrix elements

This applies if the matrix element is available as a C library or a Fortran library with `bind(C)` compatible interface. We can use the basic version.

The type is still abstract, all methods must be implemented explicitly for a specific matrix-element variant.

```

<Prclib interfaces: types>+≡
  type, extends (prc_writer_t), abstract :: prc_writer_c_lib_t
  contains
    <Prclib interfaces: prc writer c lib: TBP>
  end type prc_writer_c_lib_t

```

13.2.5 Process records in the library driver

A process record holds the process (component) ID, the physics `model_name`, and the array of `features` that are implemented by the corresponding matrix element code.

The `writer` component holds procedures. The procedures write source code for the current record, either for the driver or for the Makefile.

```

<Prclib interfaces: types>+≡
  type :: prclib_driver_record_t
    type(string_t) :: id
    type(string_t) :: model_name
    type(string_t), dimension(:), allocatable :: feature
    class(prc_writer_t), pointer :: writer => null ()
  contains
    <Prclib interfaces: prclib driver record: TBP>
  end type prclib_driver_record_t

```

Output routine. We indent the output, so it smoothly integrates into the output routine for the whole driver.

Note: the pointer `writer` is introduced as a workaround for a NAG compiler bug.

```

<Prclib interfaces: prclib driver record: TBP>≡
  procedure :: write => prclib_driver_record_write

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_record_write (object, unit)
    class(prclib_driver_record_t), intent(in) :: object
    integer, intent(in) :: unit
    integer :: j
    class(prc_writer_t), pointer :: writer
    write (unit, "(3x,A,2x,['',A,']')") &
      char (object%id), char (object%model_name)
    if (allocated (object%feature)) then
      writer => object%writer
      write (unit, "(5x,A,A)", advance="no") &
        char (writer%type_name ()), ":"
      do j = 1, size (object%feature)
        write (unit, "(1x,A)", advance="no") &
          char (object%feature(j))
      end do
      write (unit, *)
    end if
  end subroutine prclib_driver_record_write

```

Get the C procedure name for a feature.

```

<Prclib interfaces: prclib driver record: TBP>+≡
  procedure :: get_c_procname => prclib_driver_record_get_c_procname

<Prclib interfaces: procedures>+≡
  function prclib_driver_record_get_c_procname (record, feature) result (name)
    type(string_t) :: name
    class(prclib_driver_record_t), intent(in) :: record
    type(string_t), intent(in) :: feature
    name = record%writer%get_c_procname (record%id, feature)
  end function prclib_driver_record_get_c_procname

```

Write a USE directive for a given feature. Applies only if the record corresponds to a Fortran module.

```

<Prclib interfaces: prclib driver record: TBP>+≡
  procedure :: write_use_line => prclib_driver_record_write_use_line

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_record_write_use_line (record, unit, feature)
    class(prclib_driver_record_t), intent(in) :: record
    integer, intent(in) :: unit
    type(string_t), intent(in) :: feature
    select type (writer => record%writer)
      class is (prc_writer_f_module_t)
        call writer%write_use_line (unit, record%id, feature)
    end select
  end subroutine prclib_driver_record_write_use_line

```

The alternative: write an interface block for a given feature, unless the record corresponds to a Fortran module.

```

<Prclib interfaces: prclib driver record: TBP>+≡
  procedure :: write_interface => prclib_driver_record_write_interface

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_record_write_interface (record, unit, feature)
    class(prclib_driver_record_t), intent(in) :: record
    integer, intent(in) :: unit
    type(string_t), intent(in) :: feature
    select type (writer => record%writer)
      class is (prc_writer_f_module_t)
        class default
          call writer%write_interface (unit, record%id, feature)
        end select
    end select
  end subroutine prclib_driver_record_write_interface

```

Write all special feature interfaces for the current record. Do this for all process variants.

```

<Prclib interfaces: prclib driver record: TBP>+≡
  procedure :: write_interfaces => prclib_driver_record_write_interfaces

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_record_write_interfaces (record, unit)
    class(prclib_driver_record_t), intent(in) :: record
    integer, intent(in) :: unit

```

```

integer :: i
do i = 1, size (record%feature)
    call record%writer%write_interface (unit, record%id, record%feature(i))
end do
end subroutine prclib_driver_record_write_interfaces

```

Write the wrapper routines for this record, if it corresponds to a Fortran module.

```

<Prclib interfaces: prclib driver record: TBP>+≡
    procedure :: write_wrappers => prclib_driver_record_write_wrappers
<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_record_write_wrappers (record, unit)
        class(prclib_driver_record_t), intent(in) :: record
        integer, intent(in) :: unit
        integer :: i
        select type (writer => record%writer)
        class is (prc_writer_f_module_t)
            do i = 1, size (record%feature)
                call writer%write_wrapper (unit, record%id, record%feature(i))
            end do
        end select
    end subroutine prclib_driver_record_write_wrappers

```

Write the Makefile code for this record.

```

<Prclib interfaces: prclib driver record: TBP>+≡
    procedure :: write_makefile_code => prclib_driver_record_write_makefile_code
<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_record_write_makefile_code &
        (record, unit, os_data, testflag)
        class(prclib_driver_record_t), intent(in) :: record
        integer, intent(in) :: unit
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: testflag
        call record%writer%write_makefile_code (unit, record%id, os_data, testflag)
    end subroutine prclib_driver_record_write_makefile_code

```

Write source-code files for this record. (Does nothing if the source code is handled by Makefile rules.)

```

<Prclib interfaces: prclib driver record: TBP>+≡
    procedure :: write_source_code => prclib_driver_record_write_source_code
<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_record_write_source_code (record)
        class(prclib_driver_record_t), intent(in) :: record
        call record%writer%write_source_code (record%id)
    end subroutine prclib_driver_record_write_source_code

```

13.2.6 The process library driver object

A `prclib_driver_t` object provides the interface to external matrix element code. The code is provided by an external library which is either statically or dynamically linked.

The dynamic and static versions of the library are two different implementations of the abstract base type.

The **basename** identifies the library, both by file names and by Fortran variable names.

The **loaded** flag becomes true once all procedure pointers to the matrix element have been assigned.

For a dynamical external library, the communication proceeds via a **dlaccess** object.

n_processes is the number of external process code components that are referenced by this library. The code is addressed by index (**i_lib** in the process library entry above). This number should be equal to the number returned by **get_n_prc**.

For each external process, there is a separate **record** which holds the data that are needed for the driver parts which are specific for a given process component. The actual pointers for the loaded library will be assigned elsewhere.

The remainder is a collection of procedure pointers, which can be assigned once all external code has been compiled and linked. The procedure pointers all take a process component code index as an argument. Most return information about the process component that should match the process definition. The **get_fptr** procedures return a function pointer, which is the actual means to compute matrix elements or retrieve associated data.

Finally, the **unload_hook** and **reload_hook** pointers allow for the insertion of additional code when a library is loaded.

(Prclib interfaces: public)+≡

public :: prclib_driver_t

(Prclib interfaces: types)+≡

```
type, abstract :: prclib_driver_t
  type(string_t) :: basename
  character(32) :: md5sum = ""
  logical :: loaded = .false.
  type(string_t) :: libname
  type(string_t) :: modellibs_ldflags
  integer :: n_processes = 0
  type(prclib_driver_record_t), dimension(:), allocatable :: record
  procedure(prc_get_n_processes), nopass, pointer :: &
    get_n_processes => null ()
  procedure(prc_get_stringptr), nopass, pointer :: &
    get_process_id_ptr => null ()
  procedure(prc_get_stringptr), nopass, pointer :: &
    get_model_name_ptr => null ()
  procedure(prc_get_stringptr), nopass, pointer :: &
    get_md5sum_ptr => null ()
  procedure(prc_get_log), nopass, pointer :: &
    get_omp_status => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_in => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_out => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_flv => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_hel => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_col => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_cin => null ()
  procedure(prc_get_int), nopass, pointer :: get_n_cf => null ()
```

```

    procedure(prc_set_int_tab1), nopass, pointer :: &
        set_flv_state_ptr => null ()
    procedure(prc_set_int_tab1), nopass, pointer :: &
        set_hel_state_ptr => null ()
    procedure(prc_set_col_state), nopass, pointer :: &
        set_col_state_ptr => null ()
    procedure(prc_set_color_factors), nopass, pointer :: &
        set_color_factors_ptr => null ()
    procedure(prc_get_fptr), nopass, pointer :: get_fptr => null ()
contains
    <Prclib interfaces: prclib driver: TBP>
end type prclib_driver_t

```

This is the dynamic version. It contains a `dlaccess` object for communicating with the OS.

```

<Prclib interfaces: types>+≡
type, extends (prclib_driver_t) :: prclib_driver_dynamic_t
    type(dlaccess_t) :: dlaccess
contains
    <Prclib interfaces: prclib driver dynamic: TBP>
end type prclib_driver_dynamic_t

```

Print just the metadata. Procedure pointers cannot be printed.

```

<Prclib interfaces: prclib driver: TBP>≡
    procedure :: write => prclib_driver_write

<Prclib interfaces: procedures>+≡
subroutine prclib_driver_write (object, unit, libpath)
    class(prclib_driver_t), intent(in) :: object
    integer, intent(in) :: unit
    logical, intent(in), optional :: libpath
    logical :: write_lib
    integer :: i
    write_lib = .true.
    if (present (libpath)) write_lib = libpath
    write (unit, "(1x,A,A)") &
        "External matrix-element code library: ", char (object%basename)
    select type (object)
    type is (prclib_driver_dynamic_t)
        write (unit, "(3x,A,L1)") "static      = F"
    class default
        write (unit, "(3x,A,L1)") "static      = T"
    end select
    write (unit, "(3x,A,L1)") "loaded       = ", object%loaded
    write (unit, "(3x,A,A,A)") "MD5 sum     = '", object%md5sum, "'"
    if (write_lib) then
        write (unit, "(3x,A,A,A)") "Mdl flags = '", &
            char (object%modellibs_ldflags), "'"
    end if
    select type (object)
    type is (prclib_driver_dynamic_t)
        write (unit, *)
        call object%dlaccess%write (unit)

```

```

end select
write (unit, *)
if (allocated (object%record)) then
  write (unit, "(1x,A)") "Matrix-element code entries:"
  do i = 1, object%n_processes
    call object%record(i)%write (unit)
  end do
else
  write (unit, "(1x,A)") "Matrix-element code entries: [undefined]"
end if
end subroutine prclib_driver_write

```

Allocate a library as either static or dynamic. For static libraries, the procedure defers control to an external procedure which knows about the available static libraries. By default, this procedure is empty, but when we build a stand-alone executable, we replace the dummy by an actual dispatcher for the available static libraries. If the static dispatcher was not successful, we allocate a dynamic library.

The default version of `dispatch_prclib_static` resides in the `prebuilt` section of the `WHIZARD` tree, in a separate library. It does nothing, but can be replaced by a different procedure that allocates a static library driver if requested by name.

Note: `intent(out)` for the `driver` argument segfaults with gfortran 4.7.

```

<Prclib interfaces: public>+≡
  public :: dispatch_prclib_driver

<Prclib interfaces: procedures>+≡
  subroutine dispatch_prclib_driver &
    (driver, basename, modellibs_ldflags)
    class(prclib_driver_t), intent(inout), allocatable :: driver
    type(string_t), intent(in) :: basename
    type(string_t), intent(in), optional :: modellibs_ldflags
    procedure(dispatch_prclib_driver) :: dispatch_prclib_static
    if (allocated (driver)) deallocate (driver)
    call dispatch_prclib_static (driver, basename)
    if (.not. allocated (driver)) then
      allocate (prclib_driver_dynamic_t :: driver)
    end if
    driver%basename = basename
    driver%modellibs_ldflags = modellibs_ldflags
  end subroutine dispatch_prclib_driver

```

Initialize the ID array and set `n_processes` accordingly.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: init => prclib_driver_init

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_init (driver, n_processes)
    class(prclib_driver_t), intent(inout) :: driver
    integer, intent(in) :: n_processes
    driver%n_processes = n_processes
    allocate (driver%record (n_processes))
  end subroutine prclib_driver_init

```


Set the MD5 sum. This is separate because the MD5 sum may be known only after initialization.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: set_md5sum => prclib_driver_set_md5sum

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_set_md5sum (driver, md5sum)
    class(prclib_driver_t), intent(inout) :: driver
    character(32), intent(in) :: md5sum
    driver%md5sum = md5sum
  end subroutine prclib_driver_set_md5sum

```

Set the process record for a specific library entry. If the index is zero, we do nothing.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: set_record => prclib_driver_set_record

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_set_record (driver, i, &
    id, model_name, features, writer)
    class(prclib_driver_t), intent(inout) :: driver
    integer, intent(in) :: i
    type(string_t), intent(in) :: id
    type(string_t), intent(in) :: model_name
    type(string_t), dimension(:), intent(in) :: features
    class(prc_writer_t), intent(in), pointer :: writer
    if (i > 0) then
      associate (record => driver%record(i))
        record%id = id
        record%model_name = model_name
        allocate (record%feature (size (features)))
        record%feature = features
        record%writer => writer
      end associate
    end if
  end subroutine prclib_driver_set_record

```

Write all USE directives for a given feature, scanning the array of processes. Only Fortran-module processes count. Then, write interface blocks for the remaining processes.

The `implicit none` statement must go in-between.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: write_interfaces => prclib_driver_write_interfaces

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_write_interfaces (driver, unit, feature)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: unit
    type(string_t), intent(in) :: feature
    integer :: i
    do i = 1, driver%n_processes
      call driver%record(i)%write_use_line (unit, feature)
    end do
  end subroutine prclib_driver_write_interfaces

```

```

end do
write (unit, "(2x,9A)") "implicit none"
do i = 1, driver%n_processes
    call driver%record(i)%write_interface (unit, feature)
end do
end subroutine prclib_driver_write_interfaces

```

13.2.7 Write makefile

The makefile contains constant parts, parts that depend on the library name, and parts that depend on the specific processes and their types.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: generate_makefile => prclib_driver_generate_makefile

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_generate_makefile (driver, unit, os_data, testflag)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: unit
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: testflag
        integer :: i
        write (unit, "(A)") "# WHIZARD: Makefile for process library '" &
            // char (driver%basename) // "'"
        write (unit, "(A)") "# Automatically generated file, do not edit"
        write (unit, "(A)") ""
        write (unit, "(A)") "# Integrity check (don't modify the following line!)"
        write (unit, "(A)") "MD5SUM = '" // driver%md5sum // "'"
        write (unit, "(A)") ""
        write (unit, "(A)") "# Library name"
        write (unit, "(A)") "BASE = " // char (driver%basename)
        write (unit, "(A)") ""
        write (unit, "(A)") "# Compiler"
        write (unit, "(A)") "FC = " // char (os_data%fc)
        write (unit, "(A)") "CC = " // char (os_data%cc)
        write (unit, "(A)") ""
        write (unit, "(A)") "# Included libraries"
        write (unit, "(A)") "FCINCL = " // char (os_data%whizard_includes)
        write (unit, "(A)") ""
        write (unit, "(A)") "# Compiler flags"
        write (unit, "(A)") "FCFLAGS = " // char (os_data%fcflags)
        write (unit, "(A)") "FCFLAGS_PIC = " // char (os_data%fcflags_pic)
        write (unit, "(A)") "CFLAGS = " // char (os_data%cflags)
        write (unit, "(A)") "CFLAGS_PIC = " // char (os_data%cflags_pic)
        write (unit, "(A)") "LDFLAGS = " // char (os_data%whizard_ldflags) &
            // " " // char (os_data%ldflags) // " " // &
            char (driver%modellibs_ldflags)
        write (unit, "(A)") ""
        write (unit, "(A)") "# LaTeX setup"
        write (unit, "(A)") "LATEX = " // char (os_data%latex)
        write (unit, "(A)") "MPOST = " // char (os_data%mpost)
        write (unit, "(A)") "DVIPS = " // char (os_data%dvips)
        write (unit, "(A)") "PS2PDF = " // char (os_data%ps2pdf)
        write (unit, "(A)") 'TEX_FLAGS = "$$TEXINPUTS:' // &

```

```

char(os_data%whizard_texpath) // ''
write (unit, "(A)") 'MP_FLAGS = "$$MPINPUTS:' // &
char(os_data%whizard_texpath) // ''
write (unit, "(A)") ""
write (unit, "(A)") "# Libtool"
write (unit, "(A)") "LIBTOOL = " // char (os_data%whizard_libtool)
write (unit, "(A)") "FCOMPILE = $(LIBTOOL) --tag=FC --mode=compile"
write (unit, "(A)") "CCOMPILE = $(LIBTOOL) --tag=CC --mode=compile"
write (unit, "(A)") "LINK = $(LIBTOOL) --tag=FC --mode=link"
write (unit, "(A)") ""
write (unit, "(A)") "# Compile commands (default)"
write (unit, "(A)") "LTF_COMPILE = $(FCOMPILE) $(FC) -c &
&$(FCINCL) $(FCFLAGS) $(FCFLAGS_PIC)"
write (unit, "(A)") "LTCC_COMPILE = $(CCOMPILE) $(CC) -c &
&$(CFLAGS) $(CFLAGS_PIC)"
write (unit, "(A)") ""
write (unit, "(A)") "# Default target"
write (unit, "(A)") "all: link diags"
write (unit, "(A)") ""
write (unit, "(A)") "# Matrix-element code files"
do i = 1, size (driver%record)
call driver%record(i)%write_makefile_code (unit, os_data, testflag)
end do
write (unit, "(A)") ""
write (unit, "(A)") "# Library driver"
write (unit, "(A)") "$$(BASE).lo: $(BASE).f90 $(OBJECTS)"
write (unit, "(A)") TAB // "$$(LTF_COMPILE) $<"
write (unit, "(A)") ""
write (unit, "(A)") "# Library"
write (unit, "(A)") "$$(BASE).la: $(BASE).lo $(OBJECTS)"
write (unit, "(A)") TAB // "$$(LINK) $(FC) -module -rpath /dev/null &
&$(FCFLAGS) $(LD_FLAGS) -o $(BASE).la $~"
write (unit, "(A)") ""
write (unit, "(A)") "# Main targets"
write (unit, "(A)") "link: compile $(BASE).la"
write (unit, "(A)") "compile: source $(OBJECTS) $(TEX_OBJECTS) $(BASE).lo"
write (unit, "(A)") "compile_tex: $(TEX_OBJECTS)"
write (unit, "(A)") "source: $(SOURCES) $(BASE).f90 $(TEX_SOURCES)"
write (unit, "(A)") ".PHONY: link diags compile compile_tex source"
write (unit, "(A)") ""
write (unit, "(A)") "# Specific cleanup targets"
do i = 1, size (driver%record)
write (unit, "(A)") "clean-" // char (driver%record(i)%id) // ":"
write (unit, "(A)") ".PHONY: clean-" // char (driver%record(i)%id)
end do
write (unit, "(A)") ""
write (unit, "(A)") "# Generic cleanup targets"
write (unit, "(A)") "clean-library:"
write (unit, "(A)") TAB // "rm -f $(BASE).la"
write (unit, "(A)") "clean-objects:"
write (unit, "(A)") TAB // "rm -f $(BASE).lo $(BASE)_driver.mod &
&$(CLEAN_OBJECTS)"
write (unit, "(A)") "clean-source:"
write (unit, "(A)") TAB // "rm -f $(CLEAN_SOURCES)"

```

```

write (unit, "(A)") "clean-driver:"
write (unit, "(A)") TAB // "rm -f $(BASE).f90"
write (unit, "(A)") "clean-makefile:"
write (unit, "(A)") TAB // "rm -f $(BASE).makefile"
write (unit, "(A)") ".PHONY: clean-library clean-objects &
      &clean-source clean-driver clean-makefile"
write (unit, "(A)") ""
write (unit, "(A)") "clean: clean-library clean-objects clean-source"
write (unit, "(A)") "distclean: clean clean-driver clean-makefile"
write (unit, "(A)") ".PHONY: clean distclean"
end subroutine prclib_driver_generate_makefile

```

13.2.8 Write driver file

This procedure writes the process library driver source code to the specified output unit. The individual routines for writing source-code procedures are given below.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: generate_driver_code => prclib_driver_generate_code

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_generate_code (driver, unit)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: unit
    type(string_t) :: prefix
    integer :: i

    prefix = driver%basename // "_"

    write (unit, "(A)") "! WHIZARD matrix-element code interface"
    write (unit, "(A)") "!"
    write (unit, "(A)") "! Automatically generated file, do not edit"
    call driver%write_module (unit, prefix)
    call driver%write_lib_md5sum_fun (unit, prefix)
    call driver%write_get_n_processes_fun (unit, prefix)
    call driver%write_get_process_id_fun (unit, prefix)
    call driver%write_get_model_name_fun (unit, prefix)
    call driver%write_get_md5sum_fun (unit, prefix)
    call driver%write_string_to_array_fun (unit, prefix)
    call driver%write_get_openmp_status_fun (unit, prefix)
    call driver%write_get_int_fun (unit, prefix, var_str ("n_in"))
    call driver%write_get_int_fun (unit, prefix, var_str ("n_out"))
    call driver%write_get_int_fun (unit, prefix, var_str ("n_flv"))
    call driver%write_get_int_fun (unit, prefix, var_str ("n_hel"))
    call driver%write_get_int_fun (unit, prefix, var_str ("n_col"))
    call driver%write_get_int_fun (unit, prefix, var_str ("n_cin"))
    call driver%write_get_int_fun (unit, prefix, var_str ("n_cf"))
    call driver%write_set_int_sub (unit, prefix, var_str ("flv_state"))
    call driver%write_set_int_sub (unit, prefix, var_str ("hel_state"))
    call driver%write_set_col_state_sub (unit, prefix)
    call driver%write_set_color_factors_sub (unit, prefix)
    call driver%write_get_fptr_sub (unit, prefix)
    do i = 1, driver%n_processes

```

```

        call driver%record(i)%write_wrappers (unit)
    end do
end subroutine prclib_driver_generate_code

```

The driver module is used and required *only* if we intend to link the library statically. Then, it provides the (static) driver type as a concrete implementation of the abstract library driver. This type contains the internal dispatcher for assigning the library procedures to their appropriate procedure pointers. In the dynamical case, the assignment is done via the base-type dispatcher which invokes the DL mechanism.

However, compiling this together with the rest in any case should not do any harm.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure, nopass :: write_module => prclib_driver_write_module

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_write_module (unit, prefix)
        integer, intent(in) :: unit
        type(string_t), intent(in) :: prefix
        write (unit, "(A)") ""
        write (unit, "(A)") "! Module: define library driver as an extension &
            &of the abstract driver type."
        write (unit, "(A)") "! This is used _only_ by the library dispatcher &
            &of a static executable."
        write (unit, "(A)") "! For a dynamical library, the stand-alone proce&
            &dures are linked via libdl."
        write (unit, "(A)") ""
        write (unit, "(A)") "module " &
            // char (prefix) // "driver"
        write (unit, "(A)") " use iso_c_binding"
        write (unit, "(A)") " use iso_varying_string, string_t => varying_string"
        write (unit, "(A)") " use diagnostics"
        write (unit, "(A)") " use prclib_interfaces"
        write (unit, "(A)") ""
        write (unit, "(A)") " implicit none"
        write (unit, "(A)") ""
        write (unit, "(A)") " type, extends (prclib_driver_t) :: " &
            // char (prefix) // "driver_t"
        write (unit, "(A)") " contains"
        write (unit, "(A)") " procedure :: get_c_funptr => " &
            // char (prefix) // "driver_get_c_funptr"
        write (unit, "(A)") " end type " &
            // char (prefix) // "driver_t"
        write (unit, "(A)") ""
        write (unit, "(A)") "contains"
        write (unit, "(A)") ""
        write (unit, "(A)") " function " &
            // char (prefix) // "driver_get_c_funptr (driver, feature) result &
            &(c_funptr)"
        write (unit, "(A)") " class(" &
            // char (prefix) // "driver_t", intent(inout) :: driver"
        write (unit, "(A)") " type(string_t), intent(in) :: feature"
        write (unit, "(A)") " type(c_funptr) :: c_funptr"
    end subroutine prclib_driver_write_module

```

```

call write_decl ("get_n_processes", "get_n_processes")
call write_decl ("get_stringptr", "get_process_id_ptr")
call write_decl ("get_stringptr", "get_model_name_ptr")
call write_decl ("get_stringptr", "get_md5sum_ptr")
call write_decl ("get_log", "get_openmp_status")
call write_decl ("get_int", "get_n_in")
call write_decl ("get_int", "get_n_out")
call write_decl ("get_int", "get_n_flv")
call write_decl ("get_int", "get_n_hel")
call write_decl ("get_int", "get_n_col")
call write_decl ("get_int", "get_n_cin")
call write_decl ("get_int", "get_n_cf")
call write_decl ("set_int_tab1", "set_flv_state_ptr")
call write_decl ("set_int_tab1", "set_hel_state_ptr")
call write_decl ("set_col_state", "set_col_state_ptr")
call write_decl ("set_color_factors", "set_color_factors_ptr")
call write_decl ("get_fp_ptr", "get_fp_ptr")
write (unit, "(A)") "      select case (char (feature))"
call write_case ("get_n_processes")
call write_case ("get_process_id_ptr")
call write_case ("get_model_name_ptr")
call write_case ("get_md5sum_ptr")
call write_case ("get_openmp_status")
call write_case ("get_n_in")
call write_case ("get_n_out")
call write_case ("get_n_flv")
call write_case ("get_n_hel")
call write_case ("get_n_col")
call write_case ("get_n_cin")
call write_case ("get_n_cf")
call write_case ("set_flv_state_ptr")
call write_case ("set_hel_state_ptr")
call write_case ("set_col_state_ptr")
call write_case ("set_color_factors_ptr")
call write_case ("get_fp_ptr")
write (unit, "(A)") "      case default"
write (unit, "(A)") "          call msg_bug ('prclib2 driver setup: unknown &
&function name')"
write (unit, "(A)") "      end select"
write (unit, "(A)") "  end function " &
// char (prefix) // "driver_get_c_funptr"
write (unit, "(A)") ""
write (unit, "(A)") "end module " &
// char (prefix) // "driver"
write (unit, "(A)") ""
write (unit, "(A)") " ! Stand-alone external procedures: used for both &
&static and dynamic linkage"
contains
subroutine write_decl (template, feature)
character(*), intent(in) :: template, feature
write (unit, "(A)") "      procedure(prc_" // template // ") &"
write (unit, "(A)") "          :: " &
// char (prefix) // feature
end subroutine write_decl

```

```

subroutine write_case (feature)
  character(*), intent(in) :: feature
  write (unit, "(A)") "      case ('" // feature // "' )"
  write (unit, "(A)") "      c_fptr = c_funloc (" &
    // char (prefix) // feature // ")"
end subroutine write_case
end subroutine prclib_driver_write_module

```

This function provides the overall library MD5sum. The function is for internal use (therefore not bind(C)), the external interface is via the `get_md5sum_ptr` procedure with index 0.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: write_lib_md5sum_fun => prclib_driver_write_lib_md5sum_fun

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_write_lib_md5sum_fun (driver, unit, prefix)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: unit
    type(string_t), intent(in) :: prefix
    write (unit, "(A)") ""
    write (unit, "(A)") "! The MD5 sum of the library"
    write (unit, "(A)") "function " // char (prefix) &
      // "md5sum () result (md5sum)"
    write (unit, "(A)") "  implicit none"
    write (unit, "(A)") "  character(32) :: md5sum"
    write (unit, "(A)") "  md5sum = ' " // driver%md5sum // "' "
    write (unit, "(A)") "end function " // char (prefix) // "md5sum"
  end subroutine prclib_driver_write_lib_md5sum_fun

```

13.2.9 Interface bodies for informational functions

These interfaces implement the communication between WHIZARD (the main program) and the process-library driver. The procedures are all BIND(C), so they can safely be exposed by the library and handled by the `dlopen` mechanism, which apparently understands only C calling conventions.

In the sections below, for each procedure, we provide both the interface itself and a procedure that writes the corresponding procedure as source code to the process library driver.

Process count

Return the number of processes contained in the library.

```

<Prclib interfaces: public>+≡
  public :: prc_get_n_processes

<Prclib interfaces: interfaces>+≡
  abstract interface
    function prc_get_n_processes () result (n) bind(C)
      import
      integer(c_int) :: n
    end function prc_get_n_processes
  end interface

```

Here is the code.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: write_get_n_processes_fun

<Prclib interfaces: procedures>+≡
  subroutine write_get_n_processes_fun (driver, unit, prefix)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: unit
    type(string_t), intent(in) :: prefix
    write (unit, "(A)") ""
    write (unit, "(A)") "! Return the number of processes in this library"
    write (unit, "(A)") "function " // char (prefix) &
      // "get_n_processes () result (n) bind(C)"
    write (unit, "(A)") "  use iso_c_binding"
    write (unit, "(A)") "  implicit none"
    write (unit, "(A)") "  integer(c_int) :: n"
    write (unit, "(A,I0)") "  n = ", driver%n_processes
    write (unit, "(A)") "end function " // char (prefix) &
      // "get_n_processes"
  end subroutine write_get_n_processes_fun

```

Informational string functions

These functions return constant information about the matrix-element code.

The following procedures have to return strings. With the BIND(C) constraint, we choose to return the C pointer to a string, and its length, so the procedures implement this interface. They are actually subroutines.

```

<Prclib interfaces: public>+≡
  public :: prc_get_stringptr

<Prclib interfaces: interfaces>+≡
  abstract interface
    subroutine prc_get_stringptr (i, cptr, len) bind(C)
      import
      integer(c_int), intent(in) :: i
      type(c_ptr), intent(out) :: cptr
      integer(c_int), intent(out) :: len
    end subroutine prc_get_stringptr
  end interface

```

To hide this complication, we introduce a subroutine that converts the returned C pointer to a `string_t` object. As a side effect, we deallocate the original after conversion – otherwise, we might have a memory leak.

For the conversion, we first pointer-convert the C pointer to a Fortran character array pointer, length 1 and size `len`. Using argument association and an internal subroutine, we convert this to a character array with length `len` and size 1. Using ordinary assignment, we finally convert this to `string_t`.

The function takes the pointer-returning function as an argument. The index `i` identifies the process in the library.

```

<Prclib interfaces: procedures>+≡
  subroutine get_string_via_cptr (string, i, get_stringptr)
    type(string_t), intent(out) :: string
    integer, intent(in) :: i

```



```

procedure(prc_get_stringptr) :: get_stringptr
type(c_ptr) :: cptr
integer(c_int) :: pid, len
character(kind=c_char), dimension(:), pointer :: c_array
pid = i
call get_stringptr (pid, cptr, len)
if (c_associated (cptr)) then
    call c_f_pointer (cptr, c_array, shape = [len])
    call set_string (c_array)
    call get_stringptr (0_c_int, cptr, len)
else
    string = ""
end if
contains
subroutine set_string (buffer)
    character(len, kind=c_char), dimension(1), intent(in) :: buffer
    string = buffer(1)
end subroutine set_string
end subroutine get_string_via_cptr

```

Since the module procedures return Fortran strings, we have to convert them. This is the necessary auxiliary routine. The routine is not BIND(C), it is not accessed from outside.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure, nopass :: write_string_to_array_fun

<Prclib interfaces: procedures>+≡
subroutine write_string_to_array_fun (unit, prefix)
    integer, intent(in) :: unit
    type(string_t), intent(in) :: prefix
    write (unit, "(A)") ""
    write (unit, "(A)") "! Auxiliary: convert character string &
        &to array pointer"
    write (unit, "(A)") "subroutine " // char (prefix) &
        // "string_to_array (string, a)"
    write (unit, "(A)") " use iso_c_binding"
    write (unit, "(A)") " implicit none"
    write (unit, "(A)") " character(*), intent(in) :: string"
    write (unit, "(A)") " character(kind=c_char), dimension(:), &
        &allocatable, intent(out) :: a"
    write (unit, "(A)") " integer :: i"
    write (unit, "(A)") " allocate (a (len (string)))"
    write (unit, "(A)") " do i = 1, size (a)"
    write (unit, "(A)") "     a(i) = string(i:i)"
    write (unit, "(A)") " end do"
    write (unit, "(A)") "end subroutine " // char (prefix) &
        // "string_to_array"
end subroutine write_string_to_array_fun

```

The above routine is called by other functions. It is not in a module, so they need its interface explicitly.

```

<Prclib interfaces: procedures>+≡
    subroutine write_string_to_array_interface (unit, prefix)

```

```

integer, intent(in) :: unit
type(string_t), intent(in) :: prefix
write (unit, "(2x,A)") "interface"
write (unit, "(2x,A)") "  subroutine " // char (prefix) &
    // "string_to_array (string, a)"
write (unit, "(2x,A)") "    use iso_c_binding"
write (unit, "(2x,A)") "    implicit none"
write (unit, "(2x,A)") "    character(*), intent(in) :: string"
write (unit, "(2x,A)") "    character(kind=c_char), dimension(:), &
    &allocatable, intent(out) :: a"
write (unit, "(2x,A)") "  end subroutine " // char (prefix) &
    // "string_to_array"
write (unit, "(2x,A)") "end interface"
end subroutine write_string_to_array_interface

```

Here are the info functions which return strings, implementing the interface `prc_get_stringptr`.

Return the process ID for each process.

<Prclib interfaces: prclib driver: TBP>+≡

```

procedure :: write_get_process_id_fun

```

<Prclib interfaces: procedures>+≡

```

subroutine write_get_process_id_fun (driver, unit, prefix)
  class(prclib_driver_t), intent(in) :: driver
  integer, intent(in) :: unit
  type(string_t), intent(in) :: prefix
  integer :: i
  write (unit, "(A)") ""
  write (unit, "(A)") "! Return the process ID of process #i &
    &(as a C pointer to a character array)"
  write (unit, "(A)") "subroutine " // char (prefix) &
    // "get_process_id_ptr (i, cptr, len) bind(C)"
  write (unit, "(A)") "  use iso_c_binding"
  write (unit, "(A)") "  implicit none"
  write (unit, "(A)") "  integer(c_int), intent(in) :: i"
  write (unit, "(A)") "  type(c_ptr), intent(out) :: cptr"
  write (unit, "(A)") "  integer(c_int), intent(out) :: len"
  write (unit, "(A)") "  character(kind=c_char), dimension(:), &
    &allocatable, target, save :: a"
  call write_string_to_array_interface (unit, prefix)
  write (unit, "(A)") "  select case (i)"
  write (unit, "(A)") "    case (0); if (allocated (a)) deallocate (a)"
  do i = 1, driver%n_processes
    write (unit, "(A,I0,9A)") "    case (" // i // ", "; " // &
      "call " // char (prefix) // "string_to_array ('" // &
      char (driver%record(i)%id) // "', a)"
  end do
  write (unit, "(A)") "  end select"
  write (unit, "(A)") "  if (allocated (a)) then"
  write (unit, "(A)") "    cptr = c_loc (a)"
  write (unit, "(A)") "    len = size (a)"
  write (unit, "(A)") "  else"
  write (unit, "(A)") "    cptr = c_null_ptr"
  write (unit, "(A)") "    len = 0"

```

```

        write (unit, "(A)") " end if"
        write (unit, "(A)") "end subroutine " // char (prefix) &
        // "get_process_id_ptr"
    end subroutine write_get_process_id_fun

```

Return the model name, given explicitly.

<Prclib interfaces: prclib driver: TBP>+≡

```

    procedure :: write_get_model_name_fun

```

<Prclib interfaces: procedures>+≡

```

subroutine write_get_model_name_fun (driver, unit, prefix)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: unit
    type(string_t), intent(in) :: prefix
    integer :: i
    write (unit, "(A)") ""
    write (unit, "(A)") "! Return the model name for process #i &
        &(as a C pointer to a character array)"
    write (unit, "(A)") "subroutine " // char (prefix) &
        // "get_model_name_ptr (i, cptr, len) bind(C)"
    write (unit, "(A)") " use iso_c_binding"
    write (unit, "(A)") " implicit none"
    write (unit, "(A)") " integer(c_int), intent(in) :: i"
    write (unit, "(A)") " type(c_ptr), intent(out) :: cptr"
    write (unit, "(A)") " integer(c_int), intent(out) :: len"
    write (unit, "(A)") " character(kind=c_char), dimension(:), &
        &allocatable, target, save :: a"
    call write_string_to_array_interface (unit, prefix)
    write (unit, "(A)") " select case (i)"
    write (unit, "(A)") " case (0); if (allocated (a)) deallocate (a)"
    do i = 1, driver%n_processes
        write (unit, "(A,I0,9A)") " case (" , i, ")"; " , &
            "call " , char (prefix), "string_to_array ('" , &
            char (driver%record(i)%model_name), &
            "' , a)"
    end do
    write (unit, "(A)") " end select"
    write (unit, "(A)") " if (allocated (a)) then"
    write (unit, "(A)") "     cptr = c_loc (a)"
    write (unit, "(A)") "     len = size (a)"
    write (unit, "(A)") " else"
    write (unit, "(A)") "     cptr = c_null_ptr"
    write (unit, "(A)") "     len = 0"
    write (unit, "(A)") " end if"
    write (unit, "(A)") "end subroutine " // char (prefix) &
        // "get_model_name_ptr"
end subroutine write_get_model_name_fun

```

Call the MD5 sum function for the process. The function calls the corresponding function of the matrix-element code, and it returns the C address of a character array with length 32.

<Prclib interfaces: prclib driver: TBP>+≡

```

    procedure :: write_get_md5sum_fun

```

<Prclib interfaces: procedures>+≡

```

subroutine write_get_md5sum_fun (driver, unit, prefix)
  class(prclib_driver_t), intent(in) :: driver
  integer, intent(in) :: unit
  type(string_t), intent(in) :: prefix
  integer :: i
  write (unit, "(A)") ""
  write (unit, "(A)") "! Return the MD5 sum for the process configuration &
    &(as a C pointer to a character array)"
  write (unit, "(A)") "subroutine " // char (prefix) &
    // "get_md5sum_ptr (i, cptr, len) bind(C)"
  write (unit, "(A)") " use iso_c_binding"
  call driver%write_interfaces (unit, var_str ("md5sum"))
  write (unit, "(A)") " interface"
  write (unit, "(A)") " function " // char (prefix) &
    // "md5sum () result (md5sum)"
  write (unit, "(A)") " character(32) :: md5sum"
  write (unit, "(A)") " end function " // char (prefix) // "md5sum"
  write (unit, "(A)") " end interface"
  write (unit, "(A)") " integer(c_int), intent(in) :: i"
  write (unit, "(A)") " type(c_ptr), intent(out) :: cptr"
  write (unit, "(A)") " integer(c_int), intent(out) :: len"
  write (unit, "(A)") " character(kind=c_char), dimension(32), &
    &target, save :: md5sum"
  write (unit, "(A)") " select case (i)"
  write (unit, "(A)") " case (0)"
  write (unit, "(A)") " call copy (" // char (prefix) // "md5sum ())"
  write (unit, "(A)") " cptr = c_loc (md5sum)"
  do i = 1, driver%n_processes
    write (unit, "(A,I0,A)") " case (" , i, ")"
    call driver%record(i)%write_md5sum_call (unit)
  end do
  write (unit, "(A)") " case default"
  write (unit, "(A)") " cptr = c_null_ptr"
  write (unit, "(A)") " end select"
  write (unit, "(A)") " len = 32"
  write (unit, "(A)") "contains"
  write (unit, "(A)") " subroutine copy (md5sum_tmp)"
  write (unit, "(A)") " character, dimension(32), intent(in) :: &
    &md5sum_tmp"
  write (unit, "(A)") " md5sum = md5sum_tmp"
  write (unit, "(A)") " end subroutine copy"
  write (unit, "(A)") "end subroutine " // char (prefix) &
    // "get_md5sum_ptr"
end subroutine write_get_md5sum_fun

```

The actual call depends on the type of matrix element.

<Prclib interfaces: prclib driver record: TBP>+≡

```

procedure :: write_md5sum_call => prclib_driver_record_write_md5sum_call

```

<Prclib interfaces: procedures>+≡

```

subroutine prclib_driver_record_write_md5sum_call (record, unit)
  class(prclib_driver_record_t), intent(in) :: record
  integer, intent(in) :: unit

```

```

        call record%writer%write_md5sum_call (unit, record%id)
    end subroutine prclib_driver_record_write_md5sum_call

```

The interface goes into the writer base type:

```

<Prclib interfaces: prc writer: TBP>+≡

```

```

    procedure(write_code), deferred :: write_md5sum_call

```

In the Fortran module case, we take a detour. The string returned by the Fortran function is copied into a fixed-size array. The copy routine is an internal subroutine of `get_md5sum_ptr`. We return the C address of the target array.

```

<Prclib interfaces: prc writer f module: TBP>+≡

```

```

    procedure :: write_md5sum_call => prc_writer_f_module_write_md5sum_call

```

```

<Prclib interfaces: procedures>+≡

```

```

    subroutine prc_writer_f_module_write_md5sum_call (writer, unit, id)
        class(prc_writer_f_module_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        write (unit, "(5x,9A)") "call copy (", &
            char (writer%get_c_procname (id, var_str ("md5sum"))), " ()"
        write (unit, "(5x,9A)") "cptr = c_loc (md5sum)"
    end subroutine prc_writer_f_module_write_md5sum_call

```

In the C library case, the library function returns a C pointer, which we can just copy.

```

<Prclib interfaces: prc writer c lib: TBP>≡

```

```

    procedure :: write_md5sum_call => prc_writer_c_lib_write_md5sum_call

```

```

<Prclib interfaces: procedures>+≡

```

```

    subroutine prc_writer_c_lib_write_md5sum_call (writer, unit, id)
        class(prc_writer_c_lib_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        write (unit, "(5x,9A)") &
            "cptr = ", &
            char (writer%get_c_procname (id, var_str ("get_md5sum"))), " ()"
    end subroutine prc_writer_c_lib_write_md5sum_call

```

Actual references to the info functions

The string-valued info functions return C character arrays. For the API of the library driver, we provide convenience functions which (re)convert those arrays into `string_t` objects.

```

<Prclib interfaces: prclib driver: TBP>+≡

```

```

    procedure :: get_process_id => prclib_driver_get_process_id
    procedure :: get_model_name => prclib_driver_get_model_name
    procedure :: get_md5sum => prclib_driver_get_md5sum

```

```

<Prclib interfaces: procedures>+≡

```

```

    function prclib_driver_get_process_id (driver, i) result (string)
        type(string_t) :: string
        class(prclib_driver_t), intent(in) :: driver

```

```

integer, intent(in) :: i
call get_string_via_cptr (string, i, driver%get_process_id_ptr)
end function prclib_driver_get_process_id

function prclib_driver_get_model_name (driver, i) result (string)
type(string_t) :: string
class(prclib_driver_t), intent(in) :: driver
integer, intent(in) :: i
call get_string_via_cptr (string, i, driver%get_model_name_ptr)
end function prclib_driver_get_model_name

function prclib_driver_get_md5sum (driver, i) result (string)
type(string_t) :: string
class(prclib_driver_t), intent(in) :: driver
integer, intent(in) :: i
call get_string_via_cptr (string, i, driver%get_md5sum_ptr)
end function prclib_driver_get_md5sum

```

Informational logical functions

When returning a logical value, we use the C boolean type, which may differ from Fortran.

```

<Prclib interfaces: public>+≡
public :: prc_get_log

<Prclib interfaces: interfaces>+≡
abstract interface
function prc_get_log (pid) result (l) bind(C)
import
integer(c_int), intent(in) :: pid
logical(c_bool) :: l
end function prc_get_log
end interface

```

Return a logical flag which tells whether OpenMP is supported for a specific process code.

```

<Prclib interfaces: prclib driver: TBP>+≡
procedure :: write_get_openmp_status_fun

<Prclib interfaces: procedures>+≡
subroutine write_get_openmp_status_fun (driver, unit, prefix)
class(prclib_driver_t), intent(in) :: driver
integer, intent(in) :: unit
type(string_t), intent(in) :: prefix
integer :: i
write (unit, "(A)") ""
write (unit, "(A)") "! Return the OpenMP support status"
write (unit, "(A)") "function " // char (prefix) &
// "get_openmp_status (i) result (openmp_status) bind(C)"
write (unit, "(A)") " use iso_c_binding"
call driver%write_interfaces (unit, var_str ("openmp_supported"))
write (unit, "(A)") " integer(c_int), intent(in) :: i"
write (unit, "(A)") " logical(c_bool) :: openmp_status"
write (unit, "(A)") " select case (i)"

```

```

do i = 1, driver%n_processes
  write (unit, "(A,I0,9A)" " case (" , i, " "); " , &
    "openmp_status = " , &
    char (driver%record(i)%get_c_procname &
      (var_str ("openmp_supported"))), " ()"
end do
write (unit, "(A)" " end select"
write (unit, "(A)" "end function " // char (prefix) &
  // "get_openmp_status"
end subroutine write_get_openmp_status_fun

```

Informational integer functions

Various process metadata are integer values. We can use a single interface for all of them.

```

<Prclib interfaces: public>+≡
  public :: prc_get_int

<Prclib interfaces: interfaces>+≡
  abstract interface
    function prc_get_int (pid) result (n) bind(C)
      import
      integer(c_int), intent(in) :: pid
      integer(c_int) :: n
    end function prc_get_int
  end interface

```

This function returns any data of type integer, for each process.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: write_get_int_fun

<Prclib interfaces: procedures>+≡
  subroutine write_get_int_fun (driver, unit, prefix, feature)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: unit
    type(string_t), intent(in) :: prefix
    type(string_t), intent(in) :: feature
    integer :: i
    write (unit, "(A)" " "
    write (unit, "(9A)" " ! Return the value of " , char (feature)
    write (unit, "(9A)" "function " , char (prefix), &
      "get_" , char (feature), " (pid)", &
      " result (" , char (feature), ") bind(C)"
    write (unit, "(9A)" " use iso_c_binding"
    call driver%write_interfaces (unit, feature)
    write (unit, "(9A)" " integer(c_int), intent(in) :: pid"
    write (unit, "(9A)" " integer(c_int) :: " , char (feature)
    write (unit, "(9A)" " select case (pid)"
    do i = 1, driver%n_processes
      write (unit, "(2x,A,I0,9A)" "case (" , i, " "); " , &
        char (feature), " = " , &
        char (driver%record(i)%get_c_procname (feature)), &
        " ()"
    end do

```

```

        write (unit, "(9A)") " end select"
        write (unit, "(9A)") "end function ", char (prefix), &
            "get_", char (feature)
    end subroutine write_get_int_fun

```

Write a case line that assigns the value of the external function to the current return value.

```

<Prclib interfaces: procedures>+≡
    subroutine write_case_int_fun (record, unit, i, feature)
        class(prclib_driver_record_t), intent(in) :: record
        integer, intent(in) :: unit
        integer, intent(in) :: i
        type(string_t), intent(in) :: feature
        write (unit, "(5x,A,I0,9A)") "case (" , i, ")"; " , &
            char (feature), " = ", char (record%get_c_procname (feature))
    end subroutine write_case_int_fun

```

Flavor and helicity tables

Transferring tables is more complicated. First, a two-dimensional array.

```

<Prclib interfaces: public>+≡
    public :: prc_set_int_tab1

<Prclib interfaces: interfaces>+≡
    abstract interface
        subroutine prc_set_int_tab1 (pid, tab, shape) bind(C)
            import
            integer(c_int), intent(in) :: pid
            integer(c_int), dimension(*), intent(out) :: tab
            integer(c_int), dimension(2), intent(in) :: shape
        end subroutine prc_set_int_tab1
    end interface

```

This subroutine returns a table of integers.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: write_set_int_sub

<Prclib interfaces: procedures>+≡
    subroutine write_set_int_sub (driver, unit, prefix, feature)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: unit
        type(string_t), intent(in) :: prefix
        type(string_t), intent(in) :: feature
        integer :: i
        write (unit, "(A)") ""
        write (unit, "(9A)") "! Set table: ", char (feature)
        write (unit, "(9A)") "subroutine ", char (prefix), &
            "set_", char (feature), "_ptr (pid, ", char (feature), &
            ", shape) bind(C)"
        write (unit, "(9A)") " use iso_c_binding"
        call driver%write_interfaces (unit, feature)
        write (unit, "(9A)") " integer(c_int), intent(in) :: pid"
        write (unit, "(9A)") " integer(c_int), dimension(*), intent(out) :: ", &

```



```

        char (feature)
write (unit, "(9A)") " integer(c_int), dimension(2), intent(in) :: shape"
write (unit, "(9A)") " integer, dimension(:,:), allocatable :: ", &
        char (feature), "_tmp"
write (unit, "(9A)") " integer :: i, j"
write (unit, "(9A)") " select case (pid)"
do i = 1, driver%n_processes
    write (unit, "(2x,A,IO,A)") "case (" , i, ")"
    call driver%record(i)%write_int_sub_call (unit, feature)
end do
write (unit, "(9A)") " end select"
write (unit, "(9A)") "end subroutine ", char (prefix), &
        "set_", char (feature), "_ptr"
end subroutine write_set_int_sub

```

The actual call depends on the type of matrix element.

```

<Prclib interfaces: prclib driver record: TBP>+≡
    procedure :: write_int_sub_call => prclib_driver_record_write_int_sub_call

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_record_write_int_sub_call (record, unit, feature)
        class(prclib_driver_record_t), intent(in) :: record
        integer, intent(in) :: unit
        type(string_t), intent(in) :: feature
        call record%writer%write_int_sub_call (unit, record%id, feature)
    end subroutine prclib_driver_record_write_int_sub_call

```

The interface goes into the writer base type:

```

<Prclib interfaces: prc writer: TBP>+≡
    procedure(write_feature_code), deferred :: write_int_sub_call

```

In the Fortran module case, we need an extra copy in the (academical) situation where default integer and `c_int` differ. Otherwise, we just associate a Fortran array with the C pointer and let the matrix-element subroutine fill the array.

```

<Prclib interfaces: prc writer f module: TBP>+≡
    procedure :: write_int_sub_call => prc_writer_f_module_write_int_sub_call

<Prclib interfaces: procedures>+≡
    subroutine prc_writer_f_module_write_int_sub_call (writer, unit, id, feature)
        class(prc_writer_f_module_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id, feature
        write (unit, "(5x,9A)") "allocate (" , char (feature), "_tmp ", &
            "(shape(1), shape(2)))"
        write (unit, "(5x,9A)") "call ", &
            char (writer%get_c_procname (id, feature)), &
            " (" , char (feature), "_tmp)"
        write (unit, "(5x,9A)") "forall (i=1:shape(1), j=1:shape(2)) "
        write (unit, "(8x,9A)") char (feature), "(i + shape(1)*(j-1)) = ", &
            char (feature), "_tmp", "(i,j)"
        write (unit, "(5x,9A)") "end forall"
    end subroutine prc_writer_f_module_write_int_sub_call

```

In the C library case, we just transfer the C pointer to the library function.

```

<Prclib interfaces: prc writer c lib: TBP>+≡
    procedure :: write_int_sub_call => prc_writer_c_lib_write_int_sub_call

<Prclib interfaces: procedures>+≡
    subroutine prc_writer_c_lib_write_int_sub_call (writer, unit, id, feature)
        class(prc_writer_c_lib_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id, feature
        write (unit, "(5x,9A)") "call ", &
            char (writer%get_c_procname (id, feature)), " (", char (feature), ")"
    end subroutine prc_writer_c_lib_write_int_sub_call

```

Color state table

The color-state specification needs a table of integers (one array per color flow) and a corresponding array of color-ghost flags.

```

<Prclib interfaces: public>+≡
    public :: prc_set_col_state

<Prclib interfaces: interfaces>+≡
    abstract interface
        subroutine prc_set_col_state (pid, col_state, ghost_flag, shape) bind(C)
            import
            integer(c_int), intent(in) :: pid
            integer(c_int), dimension(*), intent(out) :: col_state
            logical(c_bool), dimension(*), intent(out) :: ghost_flag
            integer(c_int), dimension(3), intent(in) :: shape
        end subroutine prc_set_col_state
    end interface

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: write_set_col_state_sub

<Prclib interfaces: procedures>+≡
    subroutine write_set_col_state_sub (driver, unit, prefix)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: unit
        type(string_t), intent(in) :: prefix
        integer :: i
        type(string_t) :: feature
        feature = "col_state"
        write (unit, "(A)") ""
        write (unit, "(9A)") "! Set tables: col_state, ghost_flag"
        write (unit, "(9A)") "subroutine ", char (prefix), &
            "set_col_state_ptr (pid, col_state, ghost_flag, shape) bind(C)"
        write (unit, "(9A)") " use iso_c_binding"
        call driver%write_interfaces (unit, feature)
        write (unit, "(9A)") " integer(c_int), intent(in) :: pid"
        write (unit, "(9A)") &
            " integer(c_int), dimension(*), intent(out) :: col_state"
        write (unit, "(9A)") &
            " logical(c_bool), dimension(*), intent(out) :: ghost_flag"
        write (unit, "(9A)") &

```

```

        " integer(c_int), dimension(3), intent(in) :: shape"
write (unit, "(9A)") &
        " integer, dimension(:, :, :), allocatable :: col_state_tmp"
write (unit, "(9A)") &
        " logical, dimension(:, :), allocatable :: ghost_flag_tmp"
write (unit, "(9A)") " integer :: i, j, k"
write (unit, "(A)") " select case (pid)"
do i = 1, driver%n_processes
    write (unit, "(A,I0,A)") " case (" , i, ")"
    call driver%record(i)%write_col_state_call (unit)
end do
write (unit, "(A)") " end select"
write (unit, "(9A)") "end subroutine ", char (prefix), &
        "set_col_state_ptr"
end subroutine write_set_col_state_sub

```

The actual call depends on the type of matrix element.

```

<Prclib interfaces: prclib driver record: TBP>+≡
    procedure :: write_col_state_call => prclib_driver_record_write_col_state_call

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_record_write_col_state_call (record, unit)
        class(prclib_driver_record_t), intent(in) :: record
        integer, intent(in) :: unit
        call record%writer%write_col_state_call (unit, record%id)
    end subroutine prclib_driver_record_write_col_state_call

```

The interface goes into the writer base type:

```

<Prclib interfaces: prc writer: TBP>+≡
    procedure(write_code), deferred :: write_col_state_call

```

In the Fortran module case, we need an extra copy in the (academical) situation where default integer and `c_int` differ. Otherwise, we just associate a Fortran array with the C pointer and let the matrix-element subroutine fill the array.

```

<Prclib interfaces: prc writer f module: TBP>+≡
    procedure :: write_col_state_call => prc_writer_f_module_write_col_state_call

<Prclib interfaces: procedures>+≡
    subroutine prc_writer_f_module_write_col_state_call (writer, unit, id)
        class(prc_writer_f_module_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        write (unit, "(9A)") " allocate (col_state_tmp ", &
            "(shape(1), shape(2), shape(3)))"
        write (unit, "(5x,9A)") "allocate (ghost_flag_tmp ", &
            "(shape(2), shape(3)))"
        write (unit, "(5x,9A)") "call ", &
            char (writer%get_c_procname (id, var_str ("col_state"))), &
            " (col_state_tmp, ghost_flag_tmp)"
        write (unit, "(5x,9A)") "forall (i = 1:shape(2), j = 1:shape(3))"
        write (unit, "(8x,9A)") "forall (k = 1:shape(1))"
        write (unit, "(11x,9A)") &
            "col_state(k + shape(1) * (i + shape(2)*(j-1) - 1)) ", &
            "= col_state_tmp(k,i,j)"
    end subroutine prc_writer_f_module_write_col_state_call

```

```

        write (unit, "(8x,9A)") "end forall"
        write (unit, "(8x,9A)") &
            "ghost_flag(i + shape(2)*(j-1)) = ghost_flag_tmp(i,j)"
        write (unit, "(5x,9A)") "end forall"
    end subroutine prc_writer_f_module_write_col_state_call

```

In the C library case, we just transfer the C pointer to the library function.

```

<Prclib interfaces: prc writer c lib: TBP>+≡
    procedure :: write_col_state_call => prc_writer_c_lib_write_col_state_call

<Prclib interfaces: procedures>+≡
    subroutine prc_writer_c_lib_write_col_state_call (writer, unit, id)
        class(prc_writer_c_lib_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        write (unit, "(5x,9A)") "call ", &
            char (writer%get_c_procname (id, var_str ("col_state"))), &
            " (col_state, ghost_flag)"
    end subroutine prc_writer_c_lib_write_col_state_call

```

Color factors

For the color-factor information, we return two integer arrays and a complex array.

```

<Prclib interfaces: public>+≡
    public :: prc_set_color_factors

<Prclib interfaces: interfaces>+≡
    abstract interface
        subroutine prc_set_color_factors &
            (pid, cf_index1, cf_index2, color_factors, shape) bind(C)
        import
        integer(c_int), intent(in) :: pid
        integer(c_int), dimension(*), intent(out) :: cf_index1, cf_index2
        complex(c_default_complex), dimension(*), intent(out) :: color_factors
        integer(c_int), dimension(1), intent(in) :: shape
    end subroutine prc_set_color_factors
    end interface

```

This subroutine returns the color-flavor factor table.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: write_set_color_factors_sub

<Prclib interfaces: procedures>+≡
    subroutine write_set_color_factors_sub (driver, unit, prefix)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: unit
        type(string_t), intent(in) :: prefix
        integer :: i
        type(string_t) :: feature
        feature = "color_factors"
        write (unit, "(A)") ""
    end subroutine

```

```

write (unit, "(A)")  "! Set tables: color factors"
write (unit, "(9A)") "subroutine ", char (prefix), &
    "set_color_factors_ptr (pid, cf_index1, cf_index2, color_factors, ", &
    "shape) bind(C)"
write (unit, "(A)")  " use iso_c_binding"
write (unit, "(A)")  " use kinds"
write (unit, "(A)")  " use omega_color"
call driver%write_interfaces (unit, feature)
write (unit, "(A)")  " integer(c_int), intent(in) :: pid"
write (unit, "(A)")  " integer(c_int), dimension(1), intent(in) :: shape"
write (unit, "(A)")  " integer(c_int), dimension(*), intent(out) :: &
    &cf_index1, cf_index2"
write (unit, "(A)")  " complex(c_default_complex), dimension(*), &
    &intent(out) :: color_factors"
write (unit, "(A)")  " type(omega_color_factor), dimension(:), &
    &allocatable :: cf"
write (unit, "(A)")  " select case (pid)"
do i = 1, driver%n_processes
    write (unit, "(2x,A,IO,A)") "case (", i, ")"
    call driver%record(i)%write_color_factors_call (unit)
end do
write (unit, "(A)")  " end select"
write (unit, "(A)")  "end subroutine " // char (prefix) &
    // "set_color_factors_ptr"
end subroutine write_set_color_factors_sub

```

The actual call depends on the type of matrix element.

```

<Prclib interfaces: prclib driver record: TBP>+≡
    procedure :: write_color_factors_call => prclib_driver_record_write_color_factors_call

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_record_write_color_factors_call (record, unit)
        class(prclib_driver_record_t), intent(in) :: record
        integer, intent(in) :: unit
        call record%writer%write_color_factors_call (unit, record%id)
    end subroutine prclib_driver_record_write_color_factors_call

```

The interface goes into the writer base type:

```

<Prclib interfaces: prc writer: TBP>+≡
    procedure(write_code), deferred :: write_color_factors_call

In the Fortran module case, the matrix-element procedure fills an array of
omega_color_factor elements. We distribute this array among two integer
arrays and one complex-valued array, for which we have the C pointers.

<Prclib interfaces: prc writer f module: TBP>+≡
    procedure :: write_color_factors_call => prc_writer_f_module_write_color_factors_call

<Prclib interfaces: procedures>+≡
    subroutine prc_writer_f_module_write_color_factors_call (writer, unit, id)
        class(prc_writer_f_module_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        write (unit, "(5x,A)") "allocate (cf (shape(1)))"
        write (unit, "(5x,9A)") "call ", &

```

```

        char (writer%get_c_procname (id, var_str ("color_factors"))), " (cf)"
write (unit, "(5x,9A)") "cf_index1(1:shape(1)) = cf%i1"
write (unit, "(5x,9A)") "cf_index2(1:shape(1)) = cf%i2"
write (unit, "(5x,9A)") "color_factors(1:shape(1)) = cf%factor"
end subroutine prc_writer_f_module_write_color_factors_call

```

In the C library case, we just transfer the C pointers to the library function. There are three arrays.

```

<Prclib interfaces: prc_writer c lib: TBP>+≡
  procedure :: write_color_factors_call => &
    prc_writer_c_lib_write_color_factors_call

<Prclib interfaces: procedures>+≡
  subroutine prc_writer_c_lib_write_color_factors_call (writer, unit, id)
    class(prc_writer_c_lib_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id
    write (unit, "(5x,9A)") "call ", &
      char (writer%get_c_procname (id, var_str ("color_factors"))), &
      " (cf_index1, cf_index2, color_factors)"
  end subroutine prc_writer_c_lib_write_color_factors_call

```

13.2.10 Interfaces for C-library matrix element

If the matrix element code is not provided as a Fortran module but as a C or bind(C) Fortran library, we need explicit interfaces for the library functions. They are not identical to the Fortran module versions. They transfer pointers directly.

The implementation is part of the `prc_writer_c_lib` type, which serves as base type for all C-library writers. It writes specific interfaces depending on the feature.

We bind this as the method `write_standard_interface` instead of `write_interface`, because we have to override the latter. Otherwise we could not call the method because the writer type is abstract.

```

<Prclib interfaces: prc_writer c lib: TBP>+≡
  procedure :: write_standard_interface => prc_writer_c_lib_write_interface

<Prclib interfaces: procedures>+≡
  subroutine prc_writer_c_lib_write_interface (writer, unit, id, feature)
    class(prc_writer_c_lib_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id, feature
    select case (char (feature))
    case ("md5sum")
      write (unit, "(2x,9A)") "interface"
      write (unit, "(5x,9A)") "function ", &
        char (writer%get_c_procname (id, var_str ("get_md5sum"))), &
        " () result (cptr) bind(C)"
      write (unit, "(7x,9A)") "import"
      write (unit, "(7x,9A)") "implicit none"
      write (unit, "(7x,9A)") "type(c_ptr) :: cptr"
      write (unit, "(5x,9A)") "end function ", &

```

```

        char (writer%get_c_procname (id, var_str ("get_md5sum")))
        write (unit, "(2x,9A)") "end interface"
case ("openmp_supported")
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "function ", &
        char (writer%get_c_procname (id, feature)), &
        " () result (status) bind(C)"
    write (unit, "(7x,9A)") "import"
    write (unit, "(7x,9A)") "implicit none"
    write (unit, "(7x,9A)") "logical(c_bool) :: status"
    write (unit, "(5x,9A)") "end function ", &
        char (writer%get_c_procname (id, feature))
    write (unit, "(2x,9A)") "end interface"
case ("n_in", "n_out", "n_flv", "n_hel", "n_col", "n_cin", "n_cf")
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "function ", &
        char (writer%get_c_procname (id, feature)), &
        " () result (n) bind(C)"
    write (unit, "(7x,9A)") "import"
    write (unit, "(7x,9A)") "implicit none"
    write (unit, "(7x,9A)") "integer(c_int) :: n"
    write (unit, "(5x,9A)") "end function ", &
        char (writer%get_c_procname (id, feature))
    write (unit, "(2x,9A)") "end interface"
case ("flv_state", "hel_state")
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "subroutine ", &
        char (writer%get_c_procname (id, feature)), &
        " (", char (feature), ") bind(C)"
    write (unit, "(7x,9A)") "import"
    write (unit, "(7x,9A)") "implicit none"
    write (unit, "(7x,9A)") "integer(c_int), dimension(*), intent(out) ", &
        ":", char (feature)
    write (unit, "(5x,9A)") "end subroutine ", &
        char (writer%get_c_procname (id, feature))
    write (unit, "(2x,9A)") "end interface"
case ("col_state")
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "subroutine ", &
        char (writer%get_c_procname (id, feature)), &
        " (col_state, ghost_flag) bind(C)"
    write (unit, "(7x,9A)") "import"
    write (unit, "(7x,9A)") "implicit none"
    write (unit, "(7x,9A)") "integer(c_int), dimension(*), intent(out) ", &
        ":", col_state"
    write (unit, "(7x,9A)") "logical(c_bool), dimension(*), intent(out) ", &
        ":", ghost_flag"
    write (unit, "(5x,9A)") "end subroutine ", &
        char (writer%get_c_procname (id, feature))
    write (unit, "(2x,9A)") "end interface"
case ("color_factors")
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "subroutine ", &
        char (writer%get_c_procname (id, feature)), &

```

```

      " (cf_index1, cf_index2, color_factors) bind(C)"
write (unit, "(7x,9A)") "import"
write (unit, "(7x,9A)") "implicit none"
write (unit, "(7x,9A)") "integer(c_int), dimension(*), &
&intent(out) :: cf_index1"
write (unit, "(7x,9A)") "integer(c_int), dimension(*), &
&intent(out) :: cf_index2"
write (unit, "(7x,9A)") "complex(c_default_complex), dimension(*), &
&intent(out) :: color_factors"
write (unit, "(5x,9A)") "end subroutine ", &
char (writer%get_c_procname (id, feature))
write (unit, "(2x,9A)") "end interface"
end select
end subroutine prc_writer_c_lib_write_interface

```

13.2.11 Retrieving the tables

In the previous section we had the writer routines for procedures that return tables, actually C pointers to tables. Here, we write convenience routines that unpack them and move the contents to suitable Fortran arrays.

The flavor and helicity tables are two-dimensional integer arrays. We use intermediate storage for correctly transforming C to Fortran data types.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: set_flv_state => prclib_driver_set_flv_state
  procedure :: set_hel_state => prclib_driver_set_hel_state

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_set_flv_state (driver, i, flv_state)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: i
    integer, dimension(:,:), allocatable, intent(out) :: flv_state
    integer :: n_tot, n_flv
    integer(c_int) :: pid
    integer(c_int), dimension(:,:), allocatable :: c_flv_state
    pid = i
    n_tot = driver%get_n_in (pid) + driver%get_n_out (pid)
    n_flv = driver%get_n_flv (pid)
    allocate (flv_state (n_tot, n_flv))
    allocate (c_flv_state (n_tot, n_flv))
    call driver%set_flv_state_ptr &
      (pid, c_flv_state, int ([n_tot, n_flv], kind=c_int))
    flv_state = c_flv_state
  end subroutine prclib_driver_set_flv_state

  subroutine prclib_driver_set_hel_state (driver, i, hel_state)
    class(prclib_driver_t), intent(in) :: driver
    integer, intent(in) :: i
    integer, dimension(:,:), allocatable, intent(out) :: hel_state
    integer :: n_tot, n_hel
    integer(c_int) :: pid
    integer(c_int), dimension(:,:), allocatable, target :: c_hel_state
    pid = i

```



```

n_tot = driver%get_n_in (pid) + driver%get_n_out (pid)
n_hel = driver%get_n_hel (pid)
allocate (hel_state (n_tot, n_hel))
allocate (c_hel_state (n_tot, n_hel))
call driver%set_hel_state_ptr &
    (pid, c_hel_state, int ([n_tot, n_hel], kind=c_int))
hel_state = c_hel_state
end subroutine prclib_driver_set_hel_state

```

The color-flow table is three-dimensional, otherwise similar. We simultaneously set the ghost-flag table, which consists of logical entries.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: set_col_state => prclib_driver_set_col_state

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_set_col_state (driver, i, col_state, ghost_flag)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: i
        integer, dimension(:, :, :), allocatable, intent(out) :: col_state
        logical, dimension(:, :, :), allocatable, intent(out) :: ghost_flag
        integer :: n_cin, n_tot, n_col
        integer(c_int) :: pid
        integer(c_int), dimension(:, :, :), allocatable :: c_col_state
        logical(c_bool), dimension(:, :, :), allocatable :: c_ghost_flag
        pid = i
        n_cin = driver%get_n_cin (pid)
        n_tot = driver%get_n_in (pid) + driver%get_n_out (pid)
        n_col = driver%get_n_col (pid)
        allocate (col_state (n_cin, n_tot, n_col))
        allocate (c_col_state (n_cin, n_tot, n_col))
        allocate (ghost_flag (n_tot, n_col))
        allocate (c_ghost_flag (n_tot, n_col))
        call driver%set_col_state_ptr (pid, &
            c_col_state, c_ghost_flag, int ([n_cin, n_tot, n_col], kind=c_int))
        col_state = c_col_state
        ghost_flag = c_ghost_flag
    end subroutine prclib_driver_set_col_state

```

The color-factor table is a sparse matrix: a two-column array of indices and one array which contains the corresponding factors.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: set_color_factors => prclib_driver_set_color_factors

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_set_color_factors (driver, i, color_factors, cf_index)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: i
        complex(default), dimension(:), allocatable, intent(out) :: color_factors
        integer, dimension(:, :), allocatable, intent(out) :: cf_index
        integer :: n_cf
        integer(c_int) :: pid
        complex(c_default_complex), dimension(:), allocatable, target :: c_color_factors
        integer(c_int), dimension(:), allocatable, target :: c_cf_index1
        integer(c_int), dimension(:), allocatable, target :: c_cf_index2

```

```

pid = i
n_cf = driver%get_n_cf (pid)
allocate (color_factors (n_cf))
allocate (c_color_factors (n_cf))
allocate (c_cf_index1 (n_cf))
allocate (c_cf_index2 (n_cf))
call driver%set_color_factors_ptr (pid, &
    c_cf_index1, c_cf_index2, &
    c_color_factors, int ([n_cf], kind=c_int))
color_factors = c_color_factors
allocate (cf_index (2, n_cf))
cf_index(1,:) = c_cf_index1
cf_index(2,:) = c_cf_index2
end subroutine prclib_driver_set_color_factors

```

13.2.12 Returning a procedure pointer

The functions that directly access the matrix element, event by event, are assigned to a process-specific driver object as procedure pointers. For the `dlopen` interface, we use C function pointers. This subroutine returns such a pointer:

```

<Prclib interfaces: public>+≡
public :: prc_get_fptr

<Prclib interfaces: interfaces>+≡
abstract interface
  subroutine prc_get_fptr (pid, fid, fptr) bind(C)
    import
    integer(c_int), intent(in) :: pid
    integer(c_int), intent(in) :: fid
    type(c_funptr), intent(out) :: fptr
  end subroutine prc_get_fptr
end interface

```

This procedure writes the source code for the procedure pointer returning subroutine.

All C functions that are provided by the matrix element code of a specific process are handled here. The selection consists of a double layered `select case` construct.

```

<Prclib interfaces: prclib driver: TBP>+≡
procedure :: write_get_fptr_sub

<Prclib interfaces: procedures>+≡
subroutine write_get_fptr_sub (driver, unit, prefix)
  class(prclib_driver_t), intent(in) :: driver
  integer, intent(in) :: unit
  type(string_t), intent(in) :: prefix
  integer :: i, j
  write (unit, "(A)") ""
  write (unit, "(A)") "! Return C pointer to a procedure:"
  write (unit, "(A)") "! pid = process index; fid = function index"
  write (unit, "(4A)") "subroutine ", char (prefix), "get_fptr ", &
    "(pid, fid, fptr) bind(C)"

```

```

write (unit, "(A)") " use iso_c_binding"
write (unit, "(A)") " use kinds"
write (unit, "(A)") " implicit none"
write (unit, "(A)") " integer(c_int), intent(in) :: pid"
write (unit, "(A)") " integer(c_int), intent(in) :: fid"
write (unit, "(A)") " type(c_funptr), intent(out) :: fptr"
do i = 1, driver%n_processes
  call driver%record(i)%write_interfaces (unit)
end do
write (unit, "(A)") " select case (pid)"
do i = 1, driver%n_processes
  write (unit, "(2x,A,IO,A)") "case (" , i, ")"
  write (unit, "(5x,A)") "select case (fid)"
  associate (record => driver%record(i))
    do j = 1, size (record%feature)
      write (unit, "(5x,A,IO,9A)") "case (" , j, "); " , &
        "fptr = c_funloc (" , &
        char (record%get_c_procname (record%feature(j))), &
        ")"
    end do
  end associate
  write (unit, "(5x,A)") "end select"
end do
write (unit, "(A)") " end select"
write (unit, "(3A)") "end subroutine " , char (prefix), "get_fptr"
end subroutine write_get_fptr_sub

```

The procedures for which we want to return a pointer (the 'features' of the matrix element code) are actually Fortran module procedures. If we want to have a C signature, we must write wrapper functions for all of them. The procedures, their signatures, and the appropriate writer routines are specific for the process type.

To keep this generic, we do not provide the writer routines here, but just the interface for a writer routine. The actual routines are stored in the process record.

The **prefix** indicates the library, the **id** indicates the process, and **procname** is the bare name of the procedure to be written.

```

<Prclib interfaces: public>+≡
  public :: write_driver_code

<Prclib interfaces: interfaces>+≡
  abstract interface
    subroutine write_driver_code (unit, prefix, id, procname)
      import
      integer, intent(in) :: unit
      type(string_t), intent(in) :: prefix
      type(string_t), intent(in) :: id
      type(string_t), intent(in) :: procname
    end subroutine write_driver_code
  end interface

```

13.2.13 Hooks

Interface for additional library unload / reload hooks (currently unused!)

```
<Prclib interfaces: public>+≡
  public :: prclib_unload_hook
  public :: prclib_reload_hook
<Prclib interfaces: interfaces>+≡
  abstract interface
    subroutine prclib_unload_hook (libname)
      import
      type(string_t), intent(in) :: libname
    end subroutine prclib_unload_hook

    subroutine prclib_reload_hook (libname)
      import
      type(string_t), intent(in) :: libname
    end subroutine prclib_reload_hook
  end interface
```

13.2.14 Make source, compile, link

Since we should have written a Makefile, these tasks amount to simple make calls. Note that the Makefile targets depend on each other, so calling link executes also the source and compile steps, when necessary.

The first routine writes source-code files for the individual processes. First it calls the writer routines directly for each process, then it calls `make source`. The make command may either post-process the files, or it may do the complete work, e.g., calling an external program the generates the files.

```
<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: make_source => prclib_driver_make_source
<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_make_source (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    integer :: i
    do i = 1, driver%n_processes
      call driver%record(i)%write_source_code ()
    end do
    call os_system_call ("make source " // os_data%makeflags &
      // " -f " // driver%basename // ".makefile")
  end subroutine prclib_driver_make_source
```

Compile matrix element source code and the driver source code.

```
<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: make_compile => prclib_driver_make_compile
<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_make_compile (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    call os_system_call ("make compile " // os_data%makeflags &
      // " -f " // driver%basename // ".makefile")
```

```
end subroutine prclib_driver_make_compile
```

Combine all matrix-element code together with the driver in a process library on disk.

```
<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: make_link => prclib_driver_make_link

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_make_link (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    call os_system_call ("make link " // os_data%makeflags &
      // " -f " // driver%basename // ".makefile")
  end subroutine prclib_driver_make_link
```

13.2.15 Clean up generated files

The task of cleaning any generated files should also be deferred to Makefile targets. Apart from removing everything, removing specific files may be useful for partial rebuilds. (Note that removing the makefile itself can only be done once, for obvious reasons.)

If there is no makefile, do nothing.

```
<Prclib interfaces: prclib driver: TBP>+≡
  procedure :: clean_library => prclib_driver_clean_library
  procedure :: clean_objects => prclib_driver_clean_objects
  procedure :: clean_source => prclib_driver_clean_source
  procedure :: clean_driver => prclib_driver_clean_driver
  procedure :: clean_makefile => prclib_driver_clean_makefile
  procedure :: clean => prclib_driver_clean
  procedure :: distclean => prclib_driver_distclean

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_clean_library (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
      call os_system_call ("make clean-library " // os_data%makeflags &
        // " -f " // driver%basename // ".makefile")
    end if
  end subroutine prclib_driver_clean_library

  subroutine prclib_driver_clean_objects (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
      call os_system_call ("make clean-objects " // os_data%makeflags &
        // " -f " // driver%basename // ".makefile")
    end if
  end subroutine prclib_driver_clean_objects

  subroutine prclib_driver_clean_source (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
```

```

    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
        call os_system_call ("make clean-source " // os_data%makeflags &
            // " -f " // driver%basename // ".makefile")
    end if
end subroutine prclib_driver_clean_source

subroutine prclib_driver_clean_driver (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
        call os_system_call ("make clean-driver " // os_data%makeflags &
            // " -f " // driver%basename // ".makefile")
    end if
end subroutine prclib_driver_clean_driver

subroutine prclib_driver_clean_makefile (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
        call os_system_call ("make clean-makefile " // os_data%makeflags &
            // " -f " // driver%basename // ".makefile")
    end if
end subroutine prclib_driver_clean_makefile

subroutine prclib_driver_clean (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
        call os_system_call ("make clean " // os_data%makeflags &
            // " -f " // driver%basename // ".makefile")
    end if
end subroutine prclib_driver_clean

subroutine prclib_driver_distclean (driver, os_data)
    class(prclib_driver_t), intent(in) :: driver
    type(os_data_t), intent(in) :: os_data
    if (driver%makefile_exists ()) then
        call os_system_call ("make distclean " // os_data%makeflags &
            // " -f " // driver%basename // ".makefile")
    end if
end subroutine prclib_driver_distclean

```

This Make target should remove all files that apply to a specific process. We execute this when we want to force remaking source code. Note that source targets need not have prerequisites, so just calling `make_source` would not do anything if the files exist.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: clean_proc => prclib_driver_clean_proc

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_clean_proc (driver, i, os_data)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: i

```

```

type(os_data_t), intent(in) :: os_data
type(string_t) :: id
if (driver%makefile_exists ()) then
    id = driver%record(i)%id
    call os_system_call ("make clean-" // driver%record(i)%id // " " &
        // os_data%makeflags &
        // " -f " // driver%basename // ".makefile")
end if
end subroutine prclib_driver_clean_proc

```

13.2.16 Further Tools

Check for the appropriate makefile.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: makefile_exists => prclib_driver_makefile_exists

<Prclib interfaces: procedures>+≡
    function prclib_driver_makefile_exists (driver) result (flag)
        class(prclib_driver_t), intent(in) :: driver
        logical :: flag
        inquire (file = char (driver%basename) // ".makefile", exist = flag)
    end function prclib_driver_makefile_exists

```

13.2.17 Load the library

Once the library has been linked, we can dlopen it and assign all procedure pointers to their proper places in the library driver object. The loaded flag is set only if all required pointers have become assigned.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: load => prclib_driver_load

<Prclib interfaces: procedures>+≡
    subroutine prclib_driver_load (driver, os_data, noerror)
        class(prclib_driver_t), intent(inout) :: driver
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: noerror
        type(c_funptr) :: c_fptr
        logical :: ignore

        ignore = .false.; if (present (noerror)) ignore = noerror

        driver%libname = os_get_dlname (driver%basename, os_data, noerror, noerror)
        if (driver%libname == "") return
        select type (driver)
        type is (prclib_driver_dynamic_t)
            if (.not. dlaccess_is_open (driver%dlaccess)) then
                call dlaccess_init &
                    (driver%dlaccess, var_str ("."), driver%libname, os_data)
                if (.not. ignore) call driver%check_dlerror ()
            end if
            driver%loaded = dlaccess_is_open (driver%dlaccess)

```

```

class default
    driver%loaded = .true.
end select
if (.not. driver%loaded) return

c_fptr = driver%get_c_funptr (var_str ("get_n_processes"))
call c_f_procpointer (c_fptr, driver%get_n_processes)
driver%loaded = driver%loaded .and. associated (driver%get_n_processes)

c_fptr = driver%get_c_funptr (var_str ("get_process_id_ptr"))
call c_f_procpointer (c_fptr, driver%get_process_id_ptr)
driver%loaded = driver%loaded .and. associated (driver%get_process_id_ptr)

c_fptr = driver%get_c_funptr (var_str ("get_model_name_ptr"))
call c_f_procpointer (c_fptr, driver%get_model_name_ptr)
driver%loaded = driver%loaded .and. associated (driver%get_model_name_ptr)

c_fptr = driver%get_c_funptr (var_str ("get_md5sum_ptr"))
call c_f_procpointer (c_fptr, driver%get_md5sum_ptr)
driver%loaded = driver%loaded .and. associated (driver%get_md5sum_ptr)

c_fptr = driver%get_c_funptr (var_str ("get_openmp_status"))
call c_f_procpointer (c_fptr, driver%get_openmp_status)
driver%loaded = driver%loaded .and. associated (driver%get_openmp_status)

c_fptr = driver%get_c_funptr (var_str ("get_n_in"))
call c_f_procpointer (c_fptr, driver%get_n_in)
driver%loaded = driver%loaded .and. associated (driver%get_n_in)

c_fptr = driver%get_c_funptr (var_str ("get_n_out"))
call c_f_procpointer (c_fptr, driver%get_n_out)
driver%loaded = driver%loaded .and. associated (driver%get_n_out)

c_fptr = driver%get_c_funptr (var_str ("get_n_flv"))
call c_f_procpointer (c_fptr, driver%get_n_flv)
driver%loaded = driver%loaded .and. associated (driver%get_n_flv)

c_fptr = driver%get_c_funptr (var_str ("get_n_hel"))
call c_f_procpointer (c_fptr, driver%get_n_hel)
driver%loaded = driver%loaded .and. associated (driver%get_n_hel)

c_fptr = driver%get_c_funptr (var_str ("get_n_col"))
call c_f_procpointer (c_fptr, driver%get_n_col)
driver%loaded = driver%loaded .and. associated (driver%get_n_col)

c_fptr = driver%get_c_funptr (var_str ("get_n_cin"))
call c_f_procpointer (c_fptr, driver%get_n_cin)
driver%loaded = driver%loaded .and. associated (driver%get_n_cin)

c_fptr = driver%get_c_funptr (var_str ("get_n_cf"))
call c_f_procpointer (c_fptr, driver%get_n_cf)
driver%loaded = driver%loaded .and. associated (driver%get_n_cf)

c_fptr = driver%get_c_funptr (var_str ("set_flv_state_ptr"))

```



```

call c_f_procpointer (c_fptr, driver%set_flv_state_ptr)
driver%loaded = driver%loaded .and. associated (driver%set_flv_state_ptr)

c_fptr = driver%get_c_funptr (var_str ("set_hel_state_ptr"))
call c_f_procpointer (c_fptr, driver%set_hel_state_ptr)
driver%loaded = driver%loaded .and. associated (driver%set_hel_state_ptr)

c_fptr = driver%get_c_funptr (var_str ("set_col_state_ptr"))
call c_f_procpointer (c_fptr, driver%set_col_state_ptr)
driver%loaded = driver%loaded .and. associated (driver%set_col_state_ptr)

c_fptr = driver%get_c_funptr (var_str ("set_color_factors_ptr"))
call c_f_procpointer (c_fptr, driver%set_color_factors_ptr)
driver%loaded = driver%loaded .and. associated (driver%set_color_factors_ptr)

c_fptr = driver%get_c_funptr (var_str ("get_fptr"))
call c_f_procpointer (c_fptr, driver%get_fptr)
driver%loaded = driver%loaded .and. associated (driver%get_fptr)

end subroutine prclib_driver_load

```

Unload. To be sure, nullify the procedure pointers.

```

<Prclib interfaces: prclib_driver: TBP>+≡
  procedure :: unload => prclib_driver_unload

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_unload (driver)
    class(prclib_driver_t), intent(inout) :: driver
    select type (driver)
    type is (prclib_driver_dynamic_t)
      if (dlaccess_is_open (driver%dlaccess)) then
        call dlaccess_final (driver%dlaccess)
        call driver%check_dlerror ()
      end if
    end select
    driver%loaded = .false.
    nullify (driver%get_n_processes)
    nullify (driver%get_process_id_ptr)
    nullify (driver%get_model_name_ptr)
    nullify (driver%get_md5sum_ptr)
    nullify (driver%get_openmp_status)
    nullify (driver%get_n_in)
    nullify (driver%get_n_out)
    nullify (driver%get_n_flv)
    nullify (driver%get_n_hel)
    nullify (driver%get_n_col)
    nullify (driver%get_n_cin)
    nullify (driver%get_n_cf)
    nullify (driver%set_flv_state_ptr)
    nullify (driver%set_hel_state_ptr)
    nullify (driver%set_col_state_ptr)
    nullify (driver%set_color_factors_ptr)
    nullify (driver%get_fptr)
  end subroutine prclib_driver_unload

```

This subroutine checks the `dlerror` content and issues a fatal error if it finds an error there.

```

<Prclib interfaces: prclib driver dynamic: TBP>≡
  procedure :: check_dlerror => prclib_driver_check_dlerror

<Prclib interfaces: procedures>+≡
  subroutine prclib_driver_check_dlerror (driver)
    class(prclib_driver_dynamic_t), intent(in) :: driver
    if (dlaccess_has_error (driver%dlaccess)) then
      call msg_fatal (char (dlaccess_get_error (driver%dlaccess)))
    end if
  end subroutine prclib_driver_check_dlerror

```

Get the handle (C function pointer) for a given “feature” of the matrix element code, so it can be assigned to the appropriate procedure pointer slot. In the static case, this is a trivial pointer assignment, hard-coded into the driver type implementation.

```

<Prclib interfaces: prclib driver: TBP>+≡
  procedure (prclib_driver_get_c_funptr), deferred :: get_c_funptr

<Prclib interfaces: interfaces>+≡
  abstract interface
    function prclib_driver_get_c_funptr (driver, feature) result (c_fptr)
      import
      class(prclib_driver_t), intent(inout) :: driver
      type(string_t), intent(in) :: feature
      type(c_funptr) :: c_fptr
    end function prclib_driver_get_c_funptr
  end interface

```

In the dynamic-library case, we call the DL interface to retrieve the C pointer to a named procedure.

```

<Prclib interfaces: prclib driver dynamic: TBP>+≡
  procedure :: get_c_funptr => prclib_driver_dynamic_get_c_funptr

<Prclib interfaces: procedures>+≡
  function prclib_driver_dynamic_get_c_funptr (driver, feature) result (c_fptr)
    class(prclib_driver_dynamic_t), intent(inout) :: driver
    type(string_t), intent(in) :: feature
    type(c_funptr) :: c_fptr
    type(string_t) :: prefix, full_name
    prefix = driver%basename // "_"
    full_name = prefix // feature
    c_fptr = dlaccess_get_c_funptr (driver%dlaccess, full_name)
    call driver%check_dlerror ()
  end function prclib_driver_dynamic_get_c_funptr

```

13.2.18 MD5 sums

Recall the MD5 sum written in the Makefile

```

<Prclib interfaces: prclib driver: TBP>+≡

```

```

procedure :: get_md5sum_makefile => prclib_driver_get_md5sum_makefile
<Prclib interfaces: procedures>+≡
function prclib_driver_get_md5sum_makefile (driver) result (md5sum)
  class(prclib_driver_t), intent(in) :: driver
  character(32) :: md5sum
  type(string_t) :: filename
  character(80) :: buffer
  logical :: exist
  integer :: u, iostat
  md5sum = ""
  filename = driver%basename // ".makefile"
  inquire (file = char (filename), exist = exist)
  if (exist) then
    u = free_unit ()
    open (u, file = char (filename), action = "read", status = "old")
    iostat = 0
    do
      read (u, "(A)", iostat = iostat) buffer
      if (iostat /= 0) exit
      buffer = adjustl (buffer)
      select case (buffer(1:9))
      case ("MD5SUM = ")
        read (buffer(11:), "(A32)") md5sum
        exit
      end select
    end do
    close (u)
  end if
end function prclib_driver_get_md5sum_makefile

```

Recall the MD5 sum written in the driver source code.

```

<Prclib interfaces: prclib driver: TBP>+≡
procedure :: get_md5sum_driver => prclib_driver_get_md5sum_driver
<Prclib interfaces: procedures>+≡
function prclib_driver_get_md5sum_driver (driver) result (md5sum)
  class(prclib_driver_t), intent(in) :: driver
  character(32) :: md5sum
  type(string_t) :: filename
  character(80) :: buffer
  logical :: exist
  integer :: u, iostat
  md5sum = ""
  filename = driver%basename // ".f90"
  inquire (file = char (filename), exist = exist)
  if (exist) then
    u = free_unit ()
    open (u, file = char (filename), action = "read", status = "old")
    iostat = 0
    do
      read (u, "(A)", iostat = iostat) buffer
      if (iostat /= 0) exit
      buffer = adjustl (buffer)
      select case (buffer(1:9))

```

```

        case ("md5sum = ")
            read (buffer(11:), "(A32)") md5sum
            exit
        end select
    end do
    close (u)
end if
end function prclib_driver_get_md5sum_driver

```

Recall the MD5 sum written in the matrix element source code.

```

<Prclib interfaces: prclib driver: TBP>+≡
    procedure :: get_md5sum_source => prclib_driver_get_md5sum_source

<Prclib interfaces: procedures>+≡
    function prclib_driver_get_md5sum_source (driver, i) result (md5sum)
        class(prclib_driver_t), intent(in) :: driver
        integer, intent(in) :: i
        character(32) :: md5sum
        type(string_t) :: filename
        character(80) :: buffer
        logical :: exist
        integer :: u, iostat
        md5sum = ""

        filename = driver%record(i)%id // ".f90"
        inquire (file = char (filename), exist = exist)
        if (exist) then
            u = free_unit ()
            open (u, file = char (filename), action = "read", status = "old")
            iostat = 0
            do
                read (u, "(A)", iostat = iostat) buffer
                if (iostat /= 0) exit
                buffer = adjustl (buffer)
                select case (buffer(1:9))
                    case ("md5sum = ")
                        read (buffer(11:), "(A32)") md5sum
                        exit
                end select
            end do
            close (u)
        end if
    end function prclib_driver_get_md5sum_source

```

13.2.19 Test

This is the master for calling self-test procedures.

```

<Prclib interfaces: public>+≡
    public :: prclib_interfaces_test

<Prclib interfaces: tests>≡
    subroutine prclib_interfaces_test (u, results)
        integer, intent(in) :: u

```

```

    type(test_results_t), intent(inout) :: results
    <Prclib interfaces: execute tests>
end subroutine prclib_interfaces_test

```

Empty process list

Test 1: Create a driver object and display its contents. One of the feature lists references a writer procedure; this is just a dummy that does nothing useful.

```

<Prclib interfaces: execute tests>≡
    call test (prclib_interfaces_1, "prclib_interfaces_1", &
        "create driver object", &
        u, results)
<Prclib interfaces: tests>+≡
subroutine prclib_interfaces_1 (u)
    integer, intent(in) :: u
    class(prclib_driver_t), allocatable :: driver
    character(32), parameter :: md5sum = "prclib_interfaces_1_md5sum"
    class(prc_writer_t), pointer :: test_writer_1

    write (u, "(A)")  "* Test output: prclib_interfaces_1"
    write (u, "(A)")  "* Purpose: display the driver object contents"
    write (u, *)
    write (u, "(A)")  "* Create a prclib driver object"
    write (u, "(A)")

    call dispatch_prclib_driver (driver, var_str ("prclib"), var_str (""))
    call driver%init (3)
    call driver%set_md5sum (md5sum)

    allocate (test_writer_1_t :: test_writer_1)

    call driver%set_record (1, var_str ("test1"), var_str ("test_model"), &
        [var_str ("init")], test_writer_1)

    call driver%set_record (2, var_str ("test2"), var_str ("foo_model"), &
        [var_str ("another_proc")], test_writer_1)

    call driver%set_record (3, var_str ("test3"), var_str ("test_model"), &
        [var_str ("init"), var_str ("some_proc")], test_writer_1)

    call driver%write (u)

    deallocate (test_writer_1)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: prclib_interfaces_1"
end subroutine prclib_interfaces_1

```

The writer: the procedures write just comment lines. We can fix an instance of this as a parameter (since it has no mutable content) and just reference the fixed parameter.

NOTE: temporarily made public.

(Prclib interfaces: test types)≡

```
type, extends (prc_writer_t) :: test_writer_1_t
contains
  procedure, nopass :: type_name => test_writer_1_type_name
  procedure :: write_makefile_code => test_writer_1_mk
  procedure :: write_source_code => test_writer_1_src
  procedure :: write_interface => test_writer_1_if
  procedure :: write_md5sum_call => test_writer_1_md5sum
  procedure :: write_int_sub_call => test_writer_1_int_sub
  procedure :: write_col_state_call => test_writer_1_col_state
  procedure :: write_color_factors_call => test_writer_1_col_factors
end type test_writer_1_t
```

(Prclib interfaces: tests)+≡

```
function test_writer_1_type_name () result (string)
  type(string_t) :: string
  string = "test_1"
end function test_writer_1_type_name

subroutine test_writer_1_mk (writer, unit, id, os_data, testflag)
  class(test_writer_1_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id
  type(os_data_t), intent(in) :: os_data
  logical, intent(in), optional :: testflag
  write (unit, "(5A)")  "# Makefile code for process ", char (id), &
    " goes here."
end subroutine test_writer_1_mk

subroutine test_writer_1_src (writer, id)
  class(test_writer_1_t), intent(in) :: writer
  type(string_t), intent(in) :: id
end subroutine test_writer_1_src

subroutine test_writer_1_if (writer, unit, id, feature)
  class(test_writer_1_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id, feature
  write (unit, "(2x,9A)")  "! Interface code for ", &
    char (id), "_", char (writer%get_procname (feature)), &
    " goes here."
end subroutine test_writer_1_if

subroutine test_writer_1_md5sum (writer, unit, id)
  class(test_writer_1_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id
  write (unit, "(5x,9A)")  "! MD5sum call for ", char (id), " goes here."
end subroutine test_writer_1_md5sum

subroutine test_writer_1_int_sub (writer, unit, id, feature)
  class(test_writer_1_t), intent(in) :: writer
```

```

integer, intent(in) :: unit
type(string_t), intent(in) :: id, feature
write (unit, "(5x,9A)") "! ", char (feature), " call for ", &
char (id), " goes here."
end subroutine test_writer_1_int_sub

subroutine test_writer_1_col_state (writer, unit, id)
class(test_writer_1_t), intent(in) :: writer
integer, intent(in) :: unit
type(string_t), intent(in) :: id
write (unit, "(5x,9A)") "! col_state call for ", &
char (id), " goes here."
end subroutine test_writer_1_col_state

subroutine test_writer_1_col_factors (writer, unit, id)
class(test_writer_1_t), intent(in) :: writer
integer, intent(in) :: unit
type(string_t), intent(in) :: id
write (unit, "(5x,9A)") "! color_factors call for ", &
char (id), " goes here."
end subroutine test_writer_1_col_factors

```

Process library driver file

Test 2: Write the driver file for a test case with two processes. The first process needs no wrapper (C library), the second one needs wrappers (Fortran module library).

```

<Prclib interfaces: execute tests>+≡
call test (prclib_interfaces_2, "prclib_interfaces_2", &
"write driver file", &
u, results)

<Prclib interfaces: tests>+≡
subroutine prclib_interfaces_2 (u)
integer, intent(in) :: u
class(prclib_driver_t), allocatable :: driver
character(32), parameter :: md5sum = "prclib_interfaces_2_md5sum"
class(prc_writer_t), pointer :: test_writer_1, test_writer_2

write (u, "(A)") "* Test output: prclib_interfaces_2"
write (u, "(A)") "* Purpose: check the generated driver source code"
write (u, "(A)")
write (u, "(A)") "* Create a prclib driver object (2 processes)"
write (u, "(A)")

call dispatch_prclib_driver (driver, var_str ("prclib2"), var_str (""))
call driver%init (2)
call driver%set_md5sum (md5sum)

allocate (test_writer_1_t :: test_writer_1)
allocate (test_writer_2_t :: test_writer_2)

call driver%set_record (1, var_str ("test1"), var_str ("Test_model"), &

```

```

[var_str ("proc1")], test_writer_1)

call driver%set_record (2, var_str ("test2"), var_str ("Test_model"), &
[var_str ("proc1"), var_str ("proc2")], test_writer_2)

call driver%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write the driver file"
write (u, "(A)")  "* File contents:"
write (u, "(A)")

call driver%generate_driver_code (u)

deallocate (test_writer_1)
deallocate (test_writer_2)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prclib_interfaces_2"
end subroutine prclib_interfaces_2

```

A writer with wrapper code: the procedures again write just comment lines. Since all procedures are NOPASS, we can reuse two of the TBP.

(Prclib interfaces: test types)+≡

```

type, extends (prc_writer_f_module_t) :: test_writer_2_t
contains
  procedure, nopass :: type_name => test_writer_2_type_name
  procedure :: write_makefile_code => test_writer_2_mk
  procedure :: write_source_code => test_writer_2_src
  procedure :: write_interface => test_writer_2_if
  procedure :: write_wrapper => test_writer_2_wr
end type test_writer_2_t

```

(Prclib interfaces: tests)+≡

```

function test_writer_2_type_name () result (string)
  type(string_t) :: string
  string = "test_2"
end function test_writer_2_type_name

subroutine test_writer_2_mk (writer, unit, id, os_data, testflag)
  class(test_writer_2_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id
  type(os_data_t), intent(in) :: os_data
  logical, intent(in), optional :: testflag
  write (unit, "(5A)")  "# Makefile code for process ", char (id), &
    " goes here."
end subroutine test_writer_2_mk

subroutine test_writer_2_src (writer, id)
  class(test_writer_2_t), intent(in) :: writer
  type(string_t), intent(in) :: id
end subroutine test_writer_2_src

```



```

subroutine test_writer_2_if (writer, unit, id, feature)
  class(test_writer_2_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id, feature
  write (unit, "(2x,9A)")  "! Interface code for ", &
    char (writer%get_module_name (id)), "_", &
    char (writer%get_procname (feature)), " goes here."
end subroutine test_writer_2_if

subroutine test_writer_2_wr (writer, unit, id, feature)
  class(test_writer_2_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id, feature
  write (unit, *)
  write (unit, "(9A)")  "! Wrapper code for ", &
    char (writer%get_c_procname (id, feature)), " goes here."
end subroutine test_writer_2_wr

```

Process library makefile

Test 3: Write the makefile for compiling and linking the process library (processes and driver code). There are two processes, one with one method, one with two methods.

To have predictable output, we reset the system-dependent initial components of `os_data` to known values.

```

<Prclib interfaces: execute tests>+≡
  call test (prclib_interfaces_3, "prclib_interfaces_3", &
    "write makefile", &
    u, results)

<Prclib interfaces: tests>+≡
subroutine prclib_interfaces_3 (u)
  integer, intent(in) :: u
  class(prclib_driver_t), allocatable :: driver
  type(os_data_t) :: os_data
  character(32), parameter :: md5sum = "prclib_interfaces_3_md5sum"
  class(prc_writer_t), pointer :: test_writer_1, test_writer_2

  call os_data_init (os_data)
  os_data%fc = "fortran-compiler"
  os_data%whizard_includes = "-I module-dir"
  os_data%fcflags = "-C=all"
  os_data%fcflags_pic = "-PIC"
  os_data%cc = "c-compiler"
  os_data%cflags = "-I include-dir"
  os_data%cflags_pic = "-PIC"
  os_data%whizard_ldflags = ""
  os_data%ldflags = ""
  os_data%whizard_libtool = "my-libtool"
  os_data%latex = "latex -halt-on-error"
  os_data%mpost = "mpost --math=scaled -halt-on-error"
  os_data%dvips = "dvips"

```

```

os_data%ps2pdf = "ps2pdf14"
os_data%whizard_texpath = ""

write (u, "(A)")  "* Test output: prclib_interfaces_3"
write (u, "(A)")  "* Purpose: check the generated Makefile"
write (u, *)
write (u, "(A)")  "* Create a prclib driver object (2 processes)"
write (u, "(A)")

call dispatch_prclib_driver (driver, var_str ("prclib3"), var_str (""))
call driver%init (2)
call driver%set_md5sum (md5sum)

allocate (test_writer_1_t :: test_writer_1)
allocate (test_writer_2_t :: test_writer_2)

call driver%set_record (1, var_str ("test1"), var_str ("Test_model"), &
    [var_str ("proc1")], test_writer_1)

call driver%set_record (2, var_str ("test2"), var_str ("Test_model"), &
    [var_str ("proc1"), var_str ("proc2")], test_writer_2)

call driver%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write Makefile"
write (u, "(A)")  "* File contents:"
write (u, "(A)")

call driver%generate_makefile (u, os_data)

deallocate (test_writer_1)
deallocate (test_writer_2)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prclib_interfaces_3"
end subroutine prclib_interfaces_3

```

Compile test with Fortran module

Test 4: Write driver and makefile and try to compile and link the library driver.

There is a single test process with a single feature. The process code is provided as a Fortran module, therefore we need a wrapper for the featured procedure.

```

<Prclib interfaces: execute tests>+≡
    call test (prclib_interfaces_4, "prclib_interfaces_4", &
        "compile and link (Fortran module)", &
        u, results)

<Prclib interfaces: tests>+≡
    subroutine prclib_interfaces_4 (u)
        integer, intent(in) :: u
        class(prclib_driver_t), allocatable :: driver

```

```

class(prc_writer_t), pointer :: test_writer_4
type(os_data_t) :: os_data
integer :: u_file

integer, dimension(:,:), allocatable :: flv_state
integer, dimension(:,:), allocatable :: hel_state
integer, dimension(:,:,:), allocatable :: col_state
logical, dimension(:,:), allocatable :: ghost_flag
integer, dimension(:,:), allocatable :: cf_index
complex(default), dimension(:), allocatable :: color_factors
character(32), parameter :: md5sum = "prclib_interfaces_4_md5sum      "
character(32) :: md5sum_file

type(c_funptr) :: proc1_ptr
interface
    subroutine proc1_t (n) bind(C)
        import
        integer(c_int), intent(out) :: n
    end subroutine proc1_t
end interface
procedure(proc1_t), pointer :: proc1
integer(c_int) :: n

write (u, "(A)")  "* Test output: prclib_interfaces_4"
write (u, "(A)")  "* Purpose: compile, link, and load process library"
write (u, "(A)")  "*           with (fake) matrix-element code &
                &as a Fortran module"
write (u, *)
write (u, "(A)")  "* Create a prclib driver object (1 process)"
write (u, "(A)")

call os_data_init (os_data)

allocate (test_writer_4_t :: test_writer_4)
call test_writer_4%init_test ()

call dispatch_prclib_driver (driver, var_str ("prclib4"), var_str (""))
call driver%init (1)
call driver%set_md5sum (md5sum)

call driver%set_record (1, var_str ("test4"), var_str ("Test_model"), &
    [var_str ("proc1")], test_writer_4)

call driver%write (u)

write (u, *)
write (u, "(A)")  "* Write Makefile"
u_file = free_unit ()
open (u_file, file="prclib4.makefile", status="replace", action="write")
call driver%generate_makefile (u_file, os_data)
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Recall MD5 sum from Makefile"

```

```

write (u, "(A)")

md5sum_file = driver%get_md5sum_makefile ()
write (u, "(1x,A,A,A)") "MD5 sum = '", md5sum_file, "'"

write (u, "(A)")
write (u, "(A)")  "* Write driver source code"

u_file = free_unit ()
open (u_file, file="prclib4.f90", status="replace", action="write")
call driver%generate_driver_code (u_file)
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Recall MD5 sum from driver source"
write (u, "(A)")

md5sum_file = driver%get_md5sum_driver ()
write (u, "(1x,A,A,A)") "MD5 sum = '", md5sum_file, "'"

write (u, "(A)")
write (u, "(A)")  "* Write matrix-element source code"
call driver%make_source (os_data)

write (u, "(A)")
write (u, "(A)")  "* Recall MD5 sum from matrix-element source"
write (u, "(A)")

md5sum_file = driver%get_md5sum_source (1)
write (u, "(1x,A,A,A)") "MD5 sum = '", md5sum_file, "'"

write (u, "(A)")
write (u, "(A)")  "* Compile source code"
call driver%make_compile (os_data)

write (u, "(A)")  "* Link library"
call driver%make_link (os_data)

write (u, "(A)")  "* Load library"
call driver%load (os_data)

write (u, *)
call driver%write (u)
write (u, *)

if (driver%loaded) then
  write (u, "(A)")  "* Call library functions:"
  write (u, *)
  write (u, "(1x,A,I0)") "n_processes   = ", driver%get_n_processes ()
  write (u, "(1x,A,A,A)") "process_id   = '", &
    char (driver%get_process_id (1)), "'"
  write (u, "(1x,A,A,A)") "model_name   = '", &
    char (driver%get_model_name (1)), "'"
  write (u, "(1x,A,A,A)") "md5sum (lib) = '", &

```

```

        char (driver%get_md5sum (0)), "' "
write (u, "(1x,A,A,A)") "md5sum (proc) = '", &
        char (driver%get_md5sum (1)), "' "
write (u, "(1x,A,L1)") "openmp_status = ", driver%get_openmp_status (1)
write (u, "(1x,A,I0)") "n_in = ", driver%get_n_in (1)
write (u, "(1x,A,I0)") "n_out = ", driver%get_n_out (1)
write (u, "(1x,A,I0)") "n_flv = ", driver%get_n_flv (1)
write (u, "(1x,A,I0)") "n_hel = ", driver%get_n_hel (1)
write (u, "(1x,A,I0)") "n_col = ", driver%get_n_col (1)
write (u, "(1x,A,I0)") "n_cin = ", driver%get_n_cin (1)
write (u, "(1x,A,I0)") "n_cf = ", driver%get_n_cf (1)

call driver%set_flv_state (1, flv_state)
write (u, "(1x,A,10(1x,I0))") "flv_state =", flv_state

call driver%set_hel_state (1, hel_state)
write (u, "(1x,A,10(1x,I0))") "hel_state =", hel_state

call driver%set_col_state (1, col_state, ghost_flag)
write (u, "(1x,A,10(1x,I0))") "col_state =", col_state
write (u, "(1x,A,10(1x,L1))") "ghost_flag =", ghost_flag

call driver%set_color_factors (1, color_factors, cf_index)
write (u, "(1x,A,10(1x,F5.3))") "color_factors =", color_factors
write (u, "(1x,A,10(1x,I0))") "cf_index =", cf_index

call driver%get_fptr (1, 1, proc1_ptr)
call c_f_procpointer (proc1_ptr, proc1)
if (associated (proc1)) then
    write (u, *)
    call proc1 (n)
    write (u, "(1x,A,I0)") "proc1(1) = ", n
end if

end if

deallocate (test_writer_4)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prclib_interfaces_4"
end subroutine prclib_interfaces_4

```

This version of test-code writer actually writes an interface and wrapper code.

The wrapped function is a no-parameter function with integer result.

The stored MD5 sum may be modified.

We will reuse this later, therefore public.

<Prclib interfaces: public>+≡

public :: test_writer_4_t

<Prclib interfaces: test types>+≡

type, extends (prc_writer_f_module_t) :: test_writer_4_t

contains

procedure, nopass :: type_name => test_writer_4_type_name

procedure, nopass :: get_module_name => &

```

        test_writer_4_get_module_name
    procedure :: write_makefile_code => test_writer_4_mk
    procedure :: write_source_code => test_writer_4_src
    procedure :: write_interface => test_writer_4_if
    procedure :: write_wrapper => test_writer_4_wr
end type test_writer_4_t

```

(Prclib interfaces: tests)+≡

```

function test_writer_4_type_name () result (string)
    type(string_t) :: string
    string = "test_4"
end function test_writer_4_type_name

```

```

function test_writer_4_get_module_name (id) result (name)
    type(string_t), intent(in) :: id
    type(string_t) :: name
    name = "tpr_" // id
end function test_writer_4_get_module_name

```

```

subroutine test_writer_4_mk (writer, unit, id, os_data, testflag)
    class(test_writer_4_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: testflag
    write (unit, "(5A)") "SOURCES += ", char (id), ".f90"
    write (unit, "(5A)") "OBJECTS += ", char (id), ".lo"
    write (unit, "(5A)") "CLEAN_SOURCES += ", char (id), ".f90"
    write (unit, "(5A)") "CLEAN_OBJECTS += tpr_", char (id), ".mod"
    write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), ".lo"
    write (unit, "(5A)") char (id), ".lo: ", char (id), ".f90"
    write (unit, "(5A)") TAB, "$(LTF_COMPILE) $<"
end subroutine test_writer_4_mk

```

```

subroutine test_writer_4_src (writer, id)
    class(test_writer_4_t), intent(in) :: writer
    type(string_t), intent(in) :: id
    call write_test_module_file (id, var_str ("proc1"), writer%md5sum)
end subroutine test_writer_4_src

```

```

subroutine test_writer_4_if (writer, unit, id, feature)
    class(test_writer_4_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id, feature
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "subroutine ", &
        char (writer%get_c_procname (id, feature)), &
        " (n) bind(C)"
    write (unit, "(7x,9A)") "import"
    write (unit, "(7x,9A)") "implicit none"
    write (unit, "(7x,9A)") "integer(c_int), intent(out) :: n"
    write (unit, "(5x,9A)") "end subroutine ", &
        char (writer%get_c_procname (id, feature))
    write (unit, "(2x,9A)") "end interface"

```

```

end subroutine test_writer_4_if

subroutine test_writer_4_wr (writer, unit, id, feature)
  class(test_writer_4_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id, feature
  write (unit, *)
  write (unit, "(9A)") "subroutine ", &
    char (writer%get_c_procname (id, feature)), &
    " (n) bind(C)"
  write (unit, "(2x,9A)") "use iso_c_binding"
  write (unit, "(2x,9A)") "use tpr_", char (id), ", only: ", &
    char (writer%get_c_procname (feature))
  write (unit, "(2x,9A)") "implicit none"
  write (unit, "(2x,9A)") "integer(c_int), intent(out) :: n"
  write (unit, "(2x,9A)") "call ", char (feature), " (n)"
  write (unit, "(9A)") "end subroutine ", &
    char (writer%get_c_procname (id, feature))
end subroutine test_writer_4_wr

```

We need a test module file (actually, one for each process in the test above) that allows us to check compilation and linking. The test module implements a colorless $1 \rightarrow 2$ process, and it implements one additional function (feature), the name given as an argument.

(*Prclib interfaces: tests*) +=

```

subroutine write_test_module_file (basename, feature, md5sum)
  type(string_t), intent(in) :: basename
  type(string_t), intent(in) :: feature
  character(32), intent(in) :: md5sum
  integer :: u
  u = free_unit ()
  open (u, file = char (basename) // ".f90", &
    status = "replace", action = "write")
  write (u, "(A)") "!(Pseudo) matrix element code file &
    &for WHIZARD self-test"
  write (u, *)
  write (u, "(A)") "module tpr_" // char (basename)
  write (u, *)
  write (u, "(2x,A)") "use kinds"
  write (u, "(2x,A)") "use omega_color, OCF => omega_color_factor"
  write (u, *)
  write (u, "(2x,A)") "implicit none"
  write (u, "(2x,A)") "private"
  write (u, *)
  call write_test_me_code_1 (u)
  write (u, *)
  write (u, "(2x,A)") "public :: " // char (feature)
  write (u, *)
  write (u, "(A)") "contains"
  write (u, *)
  call write_test_me_code_2 (u, md5sum)
  write (u, *)
  write (u, "(2x,A)") "subroutine " // char (feature) // " (n)"

```

```

write (u, "(2x,A)") " integer, intent(out) :: n"
write (u, "(2x,A)") " n = 42"
write (u, "(2x,A)") "end subroutine " // char (feature)
write (u, *)
write (u, "(A)") "end module tpr_" // char (basename)
close (u)
end subroutine write_test_module_file

```

The following two subroutines provide building blocks for a matrix-element source code file, useful only for testing the workflow. The first routine writes the header part, the other routine the implementation of the procedures listed in the header.

(Prclib interfaces: tests)+≡

```

subroutine write_test_me_code_1 (u)
  integer, intent(in) :: u
  write (u, "(2x,A)") "public :: md5sum"
  write (u, "(2x,A)") "public :: openmp_supported"
  write (u, *)
  write (u, "(2x,A)") "public :: n_in"
  write (u, "(2x,A)") "public :: n_out"
  write (u, "(2x,A)") "public :: n_flv"
  write (u, "(2x,A)") "public :: n_hel"
  write (u, "(2x,A)") "public :: n_cin"
  write (u, "(2x,A)") "public :: n_col"
  write (u, "(2x,A)") "public :: n_cf"
  write (u, *)
  write (u, "(2x,A)") "public :: flv_state"
  write (u, "(2x,A)") "public :: hel_state"
  write (u, "(2x,A)") "public :: col_state"
  write (u, "(2x,A)") "public :: color_factors"
end subroutine write_test_me_code_1

subroutine write_test_me_code_2 (u, md5sum)
  integer, intent(in) :: u
  character(32), intent(in) :: md5sum
  write (u, "(2x,A)") "pure function md5sum ()"
  write (u, "(2x,A)") " character(len=32) :: md5sum"
  write (u, "(2x,A)") " md5sum = ' ' // md5sum // '"
  write (u, "(2x,A)") "end function md5sum"
  write (u, *)
  write (u, "(2x,A)") "pure function openmp_supported () result (status)"
  write (u, "(2x,A)") " logical :: status"
  write (u, "(2x,A)") " status = .false."
  write (u, "(2x,A)") "end function openmp_supported"
  write (u, *)
  write (u, "(2x,A)") "pure function n_in () result (n)"
  write (u, "(2x,A)") " integer :: n"
  write (u, "(2x,A)") " n = 1"
  write (u, "(2x,A)") "end function n_in"
  write (u, *)
  write (u, "(2x,A)") "pure function n_out () result (n)"
  write (u, "(2x,A)") " integer :: n"
  write (u, "(2x,A)") " n = 2"

```



```

write (u, "(2x,A)") "end function n_out"
write (u, *)
write (u, "(2x,A)") "pure function n_flv () result (n)"
write (u, "(2x,A)") "  integer :: n"
write (u, "(2x,A)") "  n = 1"
write (u, "(2x,A)") "end function n_flv"
write (u, *)
write (u, "(2x,A)") "pure function n_hel () result (n)"
write (u, "(2x,A)") "  integer :: n"
write (u, "(2x,A)") "  n = 1"
write (u, "(2x,A)") "end function n_hel"
write (u, *)
write (u, "(2x,A)") "pure function n_cin () result (n)"
write (u, "(2x,A)") "  integer :: n"
write (u, "(2x,A)") "  n = 2"
write (u, "(2x,A)") "end function n_cin"
write (u, *)
write (u, "(2x,A)") "pure function n_col () result (n)"
write (u, "(2x,A)") "  integer :: n"
write (u, "(2x,A)") "  n = 1"
write (u, "(2x,A)") "end function n_col"
write (u, *)
write (u, "(2x,A)") "pure function n_cf () result (n)"
write (u, "(2x,A)") "  integer :: n"
write (u, "(2x,A)") "  n = 1"
write (u, "(2x,A)") "end function n_cf"
write (u, *)
write (u, "(2x,A)") "pure subroutine flv_state (a)"
write (u, "(2x,A)") "  integer, dimension(:,,:), intent(out) :: a"
write (u, "(2x,A)") "  a = reshape ([1,2,3], [3,1])"
write (u, "(2x,A)") "end subroutine flv_state"
write (u, *)
write (u, "(2x,A)") "pure subroutine hel_state (a)"
write (u, "(2x,A)") "  integer, dimension(:,,:), intent(out) :: a"
write (u, "(2x,A)") "  a = reshape ([0,0,0], [3,1])"
write (u, "(2x,A)") "end subroutine hel_state"
write (u, *)
write (u, "(2x,A)") "pure subroutine col_state (a, g)"
write (u, "(2x,A)") "  integer, dimension(:,,:), intent(out) :: a"
write (u, "(2x,A)") "  logical, dimension(:,,:), intent(out) :: g"
write (u, "(2x,A)") "  a = reshape ([0,0, 0,0, 0,0], [2,3,1])"
write (u, "(2x,A)") "  g = reshape ([.false., .false., .false.], [3,1])"
write (u, "(2x,A)") "end subroutine col_state"
write (u, *)
write (u, "(2x,A)") "pure subroutine color_factors (cf)"
write (u, "(2x,A)") "  type(OCF), dimension(:), intent(out) :: cf"
write (u, "(2x,A)") "  cf = [ OCF(1,1,+1._default) ]"
write (u, "(2x,A)") "end subroutine color_factors"
end subroutine write_test_me_code_2

```

Compile test with Fortran bind(C) library

Test 5: Write driver and makefile and try to compile and link the library driver.

There is a single test process with a single feature. The process code is provided as a Fortran library of independent procedures. These procedures are bind(C).

```

<Prclib interfaces: execute tests>+=
  call test (prclib_interfaces_5, "prclib_interfaces_5", &
    "compile and link (Fortran library)", &
    u, results)

<Prclib interfaces: tests>+=
  subroutine prclib_interfaces_5 (u)
    integer, intent(in) :: u
    class(prclib_driver_t), allocatable :: driver
    class(prc_writer_t), pointer :: test_writer_5
    type(os_data_t) :: os_data
    integer :: u_file

    integer, dimension(:,:), allocatable :: flv_state
    integer, dimension(:,:), allocatable :: hel_state
    integer, dimension(:,:,:), allocatable :: col_state
    logical, dimension(:,:), allocatable :: ghost_flag
    integer, dimension(:,:), allocatable :: cf_index
    complex(default), dimension(:), allocatable :: color_factors
    character(32), parameter :: md5sum = "prclib_interfaces_5_md5sum"

    type(c_funptr) :: proc1_ptr
    interface
      subroutine proc1_t (n) bind(C)
        import
        integer(c_int), intent(out) :: n
      end subroutine proc1_t
    end interface
    procedure(proc1_t), pointer :: proc1
    integer(c_int) :: n

    write (u, "(A)")  "* Test output: prclib_interfaces_5"
    write (u, "(A)")  "* Purpose: compile, link, and load process library"
    write (u, "(A)")  "*           with (fake) matrix-element code &
      &as a Fortran bind(C) library"
    write (u, *)
    write (u, "(A)")  "* Create a prclib driver object (1 process)"
    write (u, "(A)")

    call os_data_init (os_data)
    allocate (test_writer_5_t :: test_writer_5)

    call dispatch_prclib_driver (driver, var_str ("prclib5"), var_str (""))
    call driver%init (1)
    call driver%set_md5sum (md5sum)

    call driver%set_record (1, var_str ("test5"), var_str ("Test_model"), &
      [var_str ("proc1")], test_writer_5)

    call driver%write (u)

```

```

write (u, *)
write (u, "(A)")  "* Write makefile"
u_file = free_unit ()
open (u_file, file="prclib5.makefile", status="replace", action="write")
call driver%generate_makefile (u_file, os_data)
close (u_file)

write (u, "(A)")  "* Write driver source code"
u_file = free_unit ()
open (u_file, file="prclib5.f90", status="replace", action="write")
call driver%generate_driver_code (u_file)
close (u_file)

write (u, "(A)")  "* Write matrix-element source code"
call driver%make_source (os_data)

write (u, "(A)")  "* Compile source code"
call driver%make_compile (os_data)

write (u, "(A)")  "* Link library"
call driver%make_link (os_data)

write (u, "(A)")  "* Load library"
call driver%load (os_data)

write (u, *)
call driver%write (u)
write (u, *)

if (driver%loaded) then
  write (u, "(A)")  "* Call library functions:"
  write (u, *)
  write (u, "(1x,A,I0)")  "n_processes   = ", driver%get_n_processes ()
  write (u, "(1x,A,A)")  "process_id    = ", &
    char (driver%get_process_id (1))
  write (u, "(1x,A,A)")  "model_name   = ", &
    char (driver%get_model_name (1))
  write (u, "(1x,A,A)")  "md5sum       = ", &
    char (driver%get_md5sum (1))
  write (u, "(1x,A,L1)")  "openmp_status = ", driver%get_openmp_status (1)
  write (u, "(1x,A,I0)")  "n_in         = ", driver%get_n_in (1)
  write (u, "(1x,A,I0)")  "n_out        = ", driver%get_n_out (1)
  write (u, "(1x,A,I0)")  "n_flv        = ", driver%get_n_flv (1)
  write (u, "(1x,A,I0)")  "n_hel        = ", driver%get_n_hel (1)
  write (u, "(1x,A,I0)")  "n_col        = ", driver%get_n_col (1)
  write (u, "(1x,A,I0)")  "n_cin        = ", driver%get_n_cin (1)
  write (u, "(1x,A,I0)")  "n_cf         = ", driver%get_n_cf (1)

  call driver%set_flv_state (1, flv_state)
  write (u, "(1x,A,10(1x,I0))")  "flv_state =", flv_state

  call driver%set_hel_state (1, hel_state)
  write (u, "(1x,A,10(1x,I0))")  "hel_state =", hel_state

```

```

call driver%set_col_state (1, col_state, ghost_flag)
write (u, "(1x,A,10(1x,I0))") "col_state =", col_state
write (u, "(1x,A,10(1x,L1))") "ghost_flag =", ghost_flag

call driver%set_color_factors (1, color_factors, cf_index)
write (u, "(1x,A,10(1x,F5.3))") "color_factors =", color_factors
write (u, "(1x,A,10(1x,I0))") "cf_index =", cf_index

call driver%get_fptr (1, 1, proc1_ptr)
call c_f_procpointer (proc1_ptr, proc1)
if (associated (proc1)) then
  write (u, *)
  call proc1 (n)
  write (u, "(1x,A,I0)") "proc1(1) = ", n
end if

end if

deallocate (test_writer_5)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prclib_interfaces_5"
end subroutine prclib_interfaces_5

```

This version of test-code writer writes interfaces for all standard features plus one specific feature. The interfaces are all `bind(C)`, so no wrapper is needed.

```

<Prclib interfaces: test types>+=
type, extends (prc_writer_c_lib_t) :: test_writer_5_t
contains
  procedure, nopass :: type_name => test_writer_5_type_name
  procedure :: write_makefile_code => test_writer_5_mk
  procedure :: write_source_code => test_writer_5_src
  procedure :: write_interface => test_writer_5_if
end type test_writer_5_t

```

The

```

<Prclib interfaces: tests>+=
function test_writer_5_type_name () result (string)
  type(string_t) :: string
  string = "test_5"
end function test_writer_5_type_name

subroutine test_writer_5_mk (writer, unit, id, os_data, testflag)
  class(test_writer_5_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id
  type(os_data_t), intent(in) :: os_data
  logical, intent(in), optional :: testflag
  write (unit, "(5A)") "SOURCES += ", char (id), ".f90"
  write (unit, "(5A)") "OBJECTS += ", char (id), ".lo"
  write (unit, "(5A)") char (id), ".lo: ", char (id), ".f90"
  write (unit, "(5A)") TAB, "$(LTF_COMPILE) $<"
end subroutine test_writer_5_mk

```

```

subroutine test_writer_5_src (writer, id)
  class(test_writer_5_t), intent(in) :: writer
  type(string_t), intent(in) :: id
  call write_test_f_lib_file (id, var_str ("proc1"))
end subroutine test_writer_5_src

subroutine test_writer_5_if (writer, unit, id, feature)
  class(test_writer_5_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id, feature
  select case (char (feature))
  case ("proc1")
    write (unit, "(2x,9A)") "interface"
    write (unit, "(5x,9A)") "subroutine ", &
      char (writer%get_c_procname (id, feature)), &
      " (n) bind(C)"
    write (unit, "(7x,9A)") "import"
    write (unit, "(7x,9A)") "implicit none"
    write (unit, "(7x,9A)") "integer(c_int), intent(out) :: n"
    write (unit, "(5x,9A)") "end subroutine ", &
      char (writer%get_c_procname (id, feature))
    write (unit, "(2x,9A)") "end interface"
  case default
    call writer%write_standard_interface (unit, id, feature)
  end select
end subroutine test_writer_5_if

```

We need a test module file (actually, one for each process in the test above) that allows us to check compilation and linking. The test module implements a colorless $1 \rightarrow 2$ process, and it implements one additional function (feature), the name given as an argument.

(Prclib interfaces: tests) $\vdash \equiv$

```

subroutine write_test_f_lib_file (basename, feature)
  type(string_t), intent(in) :: basename
  type(string_t), intent(in) :: feature
  integer :: u
  u = free_unit ()
  open (u, file = char (basename) // ".f90", &
    status = "replace", action = "write")
  write (u, "(A)") "!(Pseudo) matrix element code file &
    &for WHIZARD self-test"
  call write_test_me_code_3 (u, char (basename))
  write (u, *)
  write (u, "(A)") "subroutine " // char (basename) // "_" &
    // char (feature) // " (n) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " implicit none"
  write (u, "(A)") " integer(c_int), intent(out) :: n"
  write (u, "(A)") " n = 42"
  write (u, "(A)") "end subroutine " // char (basename) // "_" &
    // char (feature)
  close (u)

```

```
end subroutine write_test_f_lib_file
```

The following matrix-element source code is identical to the previous one, but modified such as to provide independent procedures without a module envelope.

(Prclib interfaces: tests)+≡

```
subroutine write_test_me_code_3 (u, id)
  integer, intent(in) :: u
  character(*), intent(in) :: id
  write (u, "(A)") "function " // id // "_get_md5sum () &
    &result (cptr) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " implicit none"
  write (u, "(A)") " type(c_ptr) :: cptr"
  write (u, "(A)") " character(c_char), dimension(32), &
    &target, save :: md5sum"
  write (u, "(A)") " md5sum = copy (c_char_&
    &'1234567890abcdef1234567890abcdef')"
  write (u, "(A)") " cptr = c_loc (md5sum)"
  write (u, "(A)") "contains"
  write (u, "(A)") " function copy (md5sum)"
  write (u, "(A)") " character(c_char), dimension(32) :: copy"
  write (u, "(A)") " character(c_char), dimension(32), intent(in) :: &
    &md5sum"
  write (u, "(A)") " copy = md5sum"
  write (u, "(A)") " end function copy"
  write (u, "(A)") "end function " // id // "_get_md5sum"
  write (u, *)
  write (u, "(A)") "function " // id // "_openmp_supported () &
    &result (status) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " implicit none"
  write (u, "(A)") " logical(c_bool) :: status"
  write (u, "(A)") " status = .false."
  write (u, "(A)") "end function " // id // "_openmp_supported"
  write (u, *)
  write (u, "(A)") "function " // id // "_n_in () result (n) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " implicit none"
  write (u, "(A)") " integer(c_int) :: n"
  write (u, "(A)") " n = 1"
  write (u, "(A)") "end function " // id // "_n_in"
  write (u, *)
  write (u, "(A)") "function " // id // "_n_out () result (n) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " implicit none"
  write (u, "(A)") " integer(c_int) :: n"
  write (u, "(A)") " n = 2"
  write (u, "(A)") "end function " // id // "_n_out"
  write (u, *)
  write (u, "(A)") "function " // id // "_n_flv () result (n) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " implicit none"
  write (u, "(A)") " integer(c_int) :: n"
```

```

write (u, "(A)") " n = 1"
write (u, "(A)") "end function " // id // "_n_flv"
write (u, *)
write (u, "(A)") "function " // id // "_n_hel () result (n) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int) :: n"
write (u, "(A)") " n = 1"
write (u, "(A)") "end function " // id // "_n_hel"
write (u, *)
write (u, "(A)") "function " // id // "_n_cin () result (n) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int) :: n"
write (u, "(A)") " n = 2"
write (u, "(A)") "end function " // id // "_n_cin"
write (u, *)
write (u, "(A)") "function " // id // "_n_col () result (n) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int) :: n"
write (u, "(A)") " n = 1"
write (u, "(A)") "end function " // id // "_n_col"
write (u, *)
write (u, "(A)") "function " // id // "_n_cf () result (n) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int) :: n"
write (u, "(A)") " n = 1"
write (u, "(A)") "end function " // id // "_n_cf"
write (u, *)
write (u, "(A)") "subroutine " // id // "_flv_state (flv_state) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int), dimension(*), intent(out) :: flv_state"
write (u, "(A)") " flv_state(1:3) = [1,2,3]"
write (u, "(A)") "end subroutine " // id // "_flv_state"
write (u, *)
write (u, "(A)") "subroutine " // id // "_hel_state (hel_state) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int), dimension(*), intent(out) :: hel_state"
write (u, "(A)") " hel_state(1:3) = [0,0,0]"
write (u, "(A)") "end subroutine " // id // "_hel_state"
write (u, *)
write (u, "(A)") "subroutine " // id // "_col_state &"
write (u, "(A)") " &(col_state, ghost_flag) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int), dimension(*), intent(out) &"
write (u, "(A)") " &:: col_state"
write (u, "(A)") " logical(c_bool), dimension(*), intent(out) &"
write (u, "(A)") " &:: ghost_flag"
write (u, "(A)") " col_state(1:6) = [0,0, 0,0, 0,0]"

```

```

write (u, "(A)") " ghost_flag(1:3) = [.false., .false., .false.]"
write (u, "(A)") "end subroutine " // id // "_col_state"
write (u, *)
write (u, "(A)") "subroutine " // id // "_color_factors &
    &(cf_index1, cf_index2, color_factors) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " use kinds"
write (u, "(A)") " implicit none"
write (u, "(A)") " integer(c_int), dimension(*), intent(out) :: cf_index1"
write (u, "(A)") " integer(c_int), dimension(*), intent(out) :: cf_index2"
write (u, "(A)") " complex(c_default_complex), dimension(*), &
    &intent(out) :: color_factors"
write (u, "(A)") " cf_index1(1:1) = [1]"
write (u, "(A)") " cf_index2(1:1) = [1]"
write (u, "(A)") " color_factors(1:1) = [1]"
write (u, "(A)") "end subroutine " // id // "_color_factors"
end subroutine write_test_me_code_3

```

Compile test with genuine C library

Test 6: Write driver and makefile and try to compile and link the library driver.

There is a single test process with a single feature. The process code is provided as a C library of independent procedures. These procedures should match the Fortran bind(C) interface.

```

<Prclib interfaces: execute tests>+=
    call test (prclib_interfaces_6, "prclib_interfaces_6", &
        "compile and link (C library)", &
        u, results)

<Prclib interfaces: tests>+=
subroutine prclib_interfaces_6 (u)
    integer, intent(in) :: u
    class(prclib_driver_t), allocatable :: driver
    class(prc_writer_t), pointer :: test_writer_6
    type(os_data_t) :: os_data
    integer :: u_file

    integer, dimension(:,:), allocatable :: flv_state
    integer, dimension(:,:), allocatable :: hel_state
    integer, dimension(:,:), allocatable :: col_state
    logical, dimension(:,:), allocatable :: ghost_flag
    integer, dimension(:,:), allocatable :: cf_index
    complex(default), dimension(:), allocatable :: color_factors
    character(32), parameter :: md5sum = "prclib_interfaces_6_md5sum"

    type(c_funptr) :: proc1_ptr
    interface
        subroutine proc1_t (n) bind(C)
            import
            integer(c_int), intent(out) :: n
        end subroutine proc1_t
    end interface
    procedure(proc1_t), pointer :: proc1

```



```

integer(c_int) :: n

write (u, "(A)")  "* Test output: prclib_interfaces_6"
write (u, "(A)")  "* Purpose: compile, link, and load process library"
write (u, "(A)")  "*           with (fake) matrix-element code &
                    &as a C library"
write (u, *)
write (u, "(A)")  "* Create a prclib driver object (1 process)"
write (u, "(A)")

call os_data_init (os_data)
allocate (test_writer_6_t :: test_writer_6)

call dispatch_prclib_driver (driver, var_str ("prclib6"), var_str (""))
call driver%init (1)
call driver%set_md5sum (md5sum)

call driver%set_record (1, var_str ("test6"), var_str ("Test_model"), &
    [var_str ("proc1")], test_writer_6)

call driver%write (u)

write (u, *)
write (u, "(A)")  "* Write makefile"
u_file = free_unit ()
open (u_file, file="prclib6.makefile", status="replace", action="write")
call driver%generate_makefile (u_file, os_data)
close (u_file)

write (u, "(A)")  "* Write driver source code"
u_file = free_unit ()
open (u_file, file="prclib6.f90", status="replace", action="write")
call driver%generate_driver_code (u_file)
close (u_file)

write (u, "(A)")  "* Write matrix-element source code"
call driver%make_source (os_data)

write (u, "(A)")  "* Compile source code"
call driver%make_compile (os_data)

write (u, "(A)")  "* Link library"
call driver%make_link (os_data)

write (u, "(A)")  "* Load library"
call driver%load (os_data)

write (u, *)
call driver%write (u)
write (u, *)

if (driver%loaded) then
    write (u, "(A)")  "* Call library functions:"
    write (u, *)

```

```

write (u, "(1x,A,I0)") "n_processes = ", driver%get_n_processes ()
write (u, "(1x,A,A)") "process_id = ", &
    char (driver%get_process_id (1))
write (u, "(1x,A,A)") "model_name = ", &
    char (driver%get_model_name (1))
write (u, "(1x,A,A)") "md5sum = ", &
    char (driver%get_md5sum (1))
write (u, "(1x,A,L1)") "openmp_status = ", driver%get_openmp_status (1)
write (u, "(1x,A,I0)") "n_in = ", driver%get_n_in (1)
write (u, "(1x,A,I0)") "n_out = ", driver%get_n_out (1)
write (u, "(1x,A,I0)") "n_flv = ", driver%get_n_flv (1)
write (u, "(1x,A,I0)") "n_hel = ", driver%get_n_hel (1)
write (u, "(1x,A,I0)") "n_col = ", driver%get_n_col (1)
write (u, "(1x,A,I0)") "n_cin = ", driver%get_n_cin (1)
write (u, "(1x,A,I0)") "n_cf = ", driver%get_n_cf (1)

call driver%set_flv_state (1, flv_state)
write (u, "(1x,A,10(1x,I0))") "flv_state =", flv_state

call driver%set_hel_state (1, hel_state)
write (u, "(1x,A,10(1x,I0))") "hel_state =", hel_state

call driver%set_col_state (1, col_state, ghost_flag)
write (u, "(1x,A,10(1x,I0))") "col_state =", col_state
write (u, "(1x,A,10(1x,L1))") "ghost_flag =", ghost_flag

call driver%set_color_factors (1, color_factors, cf_index)
write (u, "(1x,A,10(1x,F5.3))") "color_factors =", color_factors
write (u, "(1x,A,10(1x,I0))") "cf_index =", cf_index

call driver%get_fptr (1, 1, proc1_ptr)
call c_f_procpointer (proc1_ptr, proc1)
if (associated (proc1)) then
    write (u, *)
    call proc1 (n)
    write (u, "(1x,A,I0)") "proc1(1) = ", n
end if

end if

deallocate (test_writer_6)

write (u, "(A)")
write (u, "(A)") "* Test output end: prclib_interfaces_6"
end subroutine prclib_interfaces_6

```

This version of test-code writer writes interfaces for all standard features plus one specific feature. The interfaces are all `bind(C)`, so no wrapper is needed.

The driver part is identical to the Fortran case, so we simply extend the previous `test_writer_5` type. We only have to override the Makefile writer.

```

(Prclib interfaces: test types) +=
type, extends (test_writer_5_t) :: test_writer_6_t
contains

```

```

        procedure, nopass :: type_name => test_writer_6_type_name
        procedure :: write_makefile_code => test_writer_6_mk
        procedure :: write_source_code => test_writer_6_src
    end type test_writer_6_t

```

(Prclib interfaces: tests)+≡

```

function test_writer_6_type_name () result (string)
    type(string_t) :: string
    string = "test_6"
end function test_writer_6_type_name

subroutine test_writer_6_mk (writer, unit, id, os_data, testflag)
    class(test_writer_6_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: testflag
    write (unit, "(5A)") "SOURCES += ", char (id), ".c"
    write (unit, "(5A)") "OBJECTS += ", char (id), ".lo"
    write (unit, "(5A)") char (id), ".lo: ", char (id), ".c"
    write (unit, "(5A)") TAB, "$(LTCCOMPILE) $<"
end subroutine test_writer_6_mk

subroutine test_writer_6_src (writer, id)
    class(test_writer_6_t), intent(in) :: writer
    type(string_t), intent(in) :: id
    call write_test_c_lib_file (id, var_str ("proc1"))
end subroutine test_writer_6_src

```

We need a test module file (actually, one for each process in the test above) that allows us to check compilation and linking. The test module implements a colorless $1 \rightarrow 2$ process, and it implements one additional function (feature), the name given as an argument.

(Prclib interfaces: tests)+≡

```

subroutine write_test_c_lib_file (basename, feature)
    type(string_t), intent(in) :: basename
    type(string_t), intent(in) :: feature
    integer :: u
    u = free_unit ()
    open (u, file = char (basename) // ".c", &
        status = "replace", action = "write")
    write (u, "(A)") "/* (Pseudo) matrix element code file &
        &for WHIZARD self-test */"
    write (u, "(A)") "#include <stdbool.h>"
    write (u, *)
    call write_test_me_code_4 (u, char (basename))
    write (u, *)
    write (u, "(A)") "void " // char (basename) // "_" &
        // char (feature) // "(int* n) {"
    write (u, "(A)") "    *n = 42;"
    write (u, "(A)") "}"
    close (u)
end subroutine write_test_c_lib_file

```

The following matrix-element source code is equivalent to the code in the previous example, but coded in C.

(Prelib interfaces: tests)+≡

```

subroutine write_test_me_code_4 (u, id)
  integer, intent(in) :: u
  character(*), intent(in) :: id
  write (u, "(A)") "char* " // id // "_get_md5sum() {"
  write (u, "(A)") "  return ""1234567890abcdef1234567890abcdef"";"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "bool " // id // "_openmp_supported() {"
  write (u, "(A)") "  return false;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_in() {"
  write (u, "(A)") "  return 1;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_out() {"
  write (u, "(A)") "  return 2;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_flv() {"
  write (u, "(A)") "  return 1;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_hel() {"
  write (u, "(A)") "  return 1;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_cin() {"
  write (u, "(A)") "  return 2;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_col() {"
  write (u, "(A)") "  return 1;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "int " // id // "_n_cf() {"
  write (u, "(A)") "  return 1;"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "void " // id // "_flv_state( int (*a)[] ) {"
  write (u, "(A)") "  static int flv_state[1][3] = { { 1, 2, 3 } };"
  write (u, "(A)") "  int j;"
  write (u, "(A)") "  for (j = 0; j < 3; j++) { (*a)[j] &
    &= flv_state[0][j]; }"
  write (u, "(A)") "}"
  write (u, *)
  write (u, "(A)") "void " // id // "_hel_state( int (*a)[] ) {"
  write (u, "(A)") "  static int hel_state[1][3] = { { 0, 0, 0 } };"
  write (u, "(A)") "  int j;"

```

```

write (u, "(A)") " for (j = 0; j < 3; j++) { (*a)[j] &
&= hel_state[0][j]; }"
write (u, "(A)") "}"
write (u, *)
write (u, "(A)") "void " // id // "_col_state&
&( int (*a)[], bool (*g)[] ) {"
write (u, "(A)") " static int col_state[1][3][2] = &
&{ { {0, 0}, {0, 0}, {0, 0} } };"
write (u, "(A)") " static bool ghost_flag[1][3] = &
&{ { false, false, false } };"
write (u, "(A)") " int j,k;"
write (u, "(A)") " for (j = 0; j < 3; j++) {"
write (u, "(A)") " for (k = 0; k < 2; k++) {"
write (u, "(A)") " (*a)[j*2+k] = col_state[0][j][k];"
write (u, "(A)") " }"
write (u, "(A)") " (*g)[j] = ghost_flag[0][j];"
write (u, "(A)") " }"
write (u, "(A)") "}"
write (u, *)
if (c_default_complex == c_long_double_complex) then
write (u, "(A)") "void " // id // "_color_factors&
&( int (*cf_index1)[], int (*cf_index2)[], &
&long double _Complex (*color_factors)[] ) {"
else
write (u, "(A)") "void " // id // "_color_factors&
&( int (*cf_index1)[], int (*cf_index2)[], &
&double _Complex (*color_factors)[] ) {"
end if
write (u, "(A)") " (*color_factors)[0] = 1;"
write (u, "(A)") " (*cf_index1)[0] = 1;"
write (u, "(A)") " (*cf_index2)[0] = 1;"
write (u, "(A)") "}"
end subroutine write_test_me_code_4

```

Test cleanup targets

Test 7: Repeat test 4 (create, compile, link Fortran module and driver) and properly clean up all generated files.

```

<Prclib interfaces: execute tests>+≡
call test (prclib_interfaces_7, "prclib_interfaces_7", &
"cleanup", &
u, results)

<Prclib interfaces: tests>+≡
subroutine prclib_interfaces_7 (u)
integer, intent(in) :: u
class(prclib_driver_t), allocatable :: driver
class(prc_writer_t), pointer :: test_writer_4
type(os_data_t) :: os_data
integer :: u_file
character(32), parameter :: md5sum = "1234567890abcdef1234567890abcdef"

write (u, "(A)") "* Test output: prclib_interfaces_7"

```

```

write (u, "(A)")  "*"   Purpose: compile and link process library"
write (u, "(A)")  "*"           with (fake) matrix-element code &
                                &as a Fortran module"
write (u, "(A)")  "*"           then clean up generated files"
write (u, *)
write (u, "(A)")  "*" Create a prclib driver object (1 process)"

allocate (test_writer_4_t :: test_writer_4)

call os_data_init (os_data)
call dispatch_prclib_driver (driver, var_str ("prclib7"), var_str (""))
call driver%init (1)
call driver%set_md5sum (md5sum)
call driver%set_record (1, var_str ("test7"), var_str ("Test_model"), &
    [var_str ("proc1")], test_writer_4)

write (u, "(A)")  "*" Write makefile"
u_file = free_unit ()
open (u_file, file="prclib7.makefile", status="replace", action="write")
call driver%generate_makefile (u_file, os_data)
close (u_file)

write (u, "(A)")  "*" Write driver source code"
u_file = free_unit ()
open (u_file, file="prclib7.f90", status="replace", action="write")
call driver%generate_driver_code (u_file)
close (u_file)

write (u, "(A)")  "*" Write matrix-element source code"
call driver%make_source (os_data)

write (u, "(A)")  "*" Compile source code"
call driver%make_compile (os_data)

write (u, "(A)")  "*" Link library"
call driver%make_link (os_data)

write (u, "(A)")  "*" File check"
write (u, *)
call check_file (u, "test7.f90")
call check_file (u, "tpr_test7.mod")
call check_file (u, "test7.lo")
call check_file (u, "prclib7.makefile")
call check_file (u, "prclib7.f90")
call check_file (u, "prclib7.lo")
call check_file (u, "prclib7.la")

write (u, *)
write (u, "(A)")  "*" Delete library"
write (u, *)
call driver%clean_library (os_data)
call check_file (u, "prclib7.la")

```

```

write (u, *)
write (u, "(A)")  "* Delete object code"
write (u, *)
call driver%clean_objects (os_data)
call check_file (u, "test7.lo")
call check_file (u, "tpr_test7.mod")
call check_file (u, "prclib7.lo")

write (u, *)
write (u, "(A)")  "* Delete source code"
write (u, *)
call driver%clean_source (os_data)
call check_file (u, "test7.f90")

write (u, *)
write (u, "(A)")  "* Delete driver source code"
write (u, *)
call driver%clean_driver (os_data)
call check_file (u, "prclib7.f90")

write (u, *)
write (u, "(A)")  "* Delete makefile"
write (u, *)
call driver%clean_makefile (os_data)
call check_file (u, "prclib7.makefile")

deallocate (test_writer_4)

write (u, *)
write (u, "(A)")  "* Test output end: prclib_interfaces_7"
end subroutine prclib_interfaces_7

```

Auxiliary routine: check and report existence of a file

```

<Prclib interfaces: tests>+≡
subroutine check_file (u, file)
integer, intent(in) :: u
character(*), intent(in) :: file
logical :: exist
inquire (file=file, exist=exist)
write (u, "(2x,A,A,L1)") file, " = ", exist
end subroutine check_file

```

13.3 Abstract process core configuration

In this module, we define abstract data types that handle the method-specific part of defining a process (including all of its options) and accessing an external matrix element.

There are no unit tests, these are deferred to the `process_libraries` module below.

```

<prc_core_def.f90>≡

```

```

<File header>

module prc_core_def

  <Use strings>
  use io_units
  use diagnostics

  use process_constants
  use prclib_interfaces

  <Standard module head>

  <Prc core def: public>

  <Prc core def: types>

  <Prc core def: interfaces>

  contains

  <Prc core def: procedures>

end module prc_core_def

```

13.3.1 Process core definition type

For storing configuration data that depend on the specific process variant, we introduce a polymorphic type. At this point, we just declare an abstract base type. This allows us to defer the implementation to later modules.

There should be no components that need explicit finalization, otherwise we would have to call a finalizer from the `process_component_def_t` wrapper.

```

<Prc core def: public>≡
  public :: prc_core_def_t

<Prc core def: types>≡
  type, abstract :: prc_core_def_t
  class(prc_writer_t), allocatable :: writer
  contains
  <Prc core def: process core def: TBP>
  end type prc_core_def_t

```

Interfaces for the deferred methods.

This returns a string. No passed argument; the string is constant and depends just on the type.

```

<Prc core def: process core def: TBP>≡
  procedure (prc_core_def_get_string), nopass, deferred :: type_string

<Prc core def: interfaces>≡
  abstract interface
    function prc_core_def_get_string () result (string)
      import
      type(string_t) :: string

```



```

        end function prc_core_def_get_string
    end interface

```

The `write` method should display the content completely.

```

<Prc core def: process core def: TBP>+≡
    procedure (prc_core_def_write), deferred :: write

<Prc core def: interfaces>+≡
    abstract interface
        subroutine prc_core_def_write (object, unit)
            import
            class(prc_core_def_t), intent(in) :: object
            integer, intent(in) :: unit
        end subroutine prc_core_def_write
    end interface

```

The `read` method should fill the content completely.

```

<Prc core def: process core def: TBP>+≡
    procedure (prc_core_def_read), deferred :: read

<Prc core def: interfaces>+≡
    abstract interface
        subroutine prc_core_def_read (object, unit)
            import
            class(prc_core_def_t), intent(out) :: object
            integer, intent(in) :: unit
        end subroutine prc_core_def_read
    end interface

```

This communicates a MD5 checksum to the writer inside the `core_def` object, if there is any. Usually, this checksum is not yet known at the time when the writer is initialized.

```

<Prc core def: process core def: TBP>+≡
    procedure :: set_md5sum => prc_core_def_set_md5sum

<Prc core def: procedures>≡
    subroutine prc_core_def_set_md5sum (core_def, md5sum)
        class(prc_core_def_t), intent(inout) :: core_def
        character(32) :: md5sum
        if (allocated (core_def%writer)) core_def%writer%md5sum = md5sum
    end subroutine prc_core_def_set_md5sum

```

Allocate an appropriate driver object which corresponds to the chosen process core definition.

For internal matrix element (i.e., those which do not need external code), the driver should have access to all matrix element information from the beginning. In short, it is the matrix-element code.

For external matrix elements, the driver will get access to the external matrix element code.

```

<Prc core def: process core def: TBP>+≡
    procedure(prc_core_def_allocate_driver), deferred :: allocate_driver

```

```

<Prc core def: interfaces>+≡
  abstract interface
    subroutine prc_core_def_allocate_driver (object, driver, basename)
      import
      class(prc_core_def_t), intent(in) :: object
      class(prc_core_driver_t), intent(out), allocatable :: driver
      type(string_t), intent(in) :: basename
    end subroutine prc_core_def_allocate_driver
  end interface

```

This flag tells whether the particular variant needs external code. We implement a default function which returns false. The flag depends only on the type, therefore we implement it as `nopass`.

```

<Prc core def: process core def: TBP>+≡
  procedure, nopass :: needs_code => prc_core_def_needs_code

<Prc core def: procedures>+≡
  function prc_core_def_needs_code () result (flag)
    logical :: flag
    flag = .false.
  end function prc_core_def_needs_code

```

This subroutine allocates an array which holds the name of all features that this process core implements. This feature applies to matrix element code that is not coded as a Fortran module but communicates via independent library functions, which follow the C calling conventions. The addresses of those functions are returned as C function pointers, which can be converted into Fortran procedure pointers. The conversion is done in code specific for the process variant; here we just retrieve the C function pointer.

The array returned here serves the purpose of writing specific driver code. The driver interfaces only those C functions which are supported for the given process core.

If the process core does not require external code, this array is meaningless.

```

<Prc core def: process core def: TBP>+≡
  procedure(prc_core_def_get_features), nopass, deferred &
    :: get_features

<Prc core def: interfaces>+≡
  abstract interface
    subroutine prc_core_def_get_features (features)
      import
      type(string_t), dimension(:), allocatable, intent(out) :: features
    end subroutine prc_core_def_get_features
  end interface

```

Assign pointers to the process-specific procedures to the driver, if the process is external.

```

<Prc core def: process core def: TBP>+≡
  procedure(prc_core_def_connect), deferred :: connect

```

```

<Prc core def: interfaces>+≡
  abstract interface
    subroutine prc_core_def_connect (def, lib_driver, i, proc_driver)
      import
      class(prc_core_def_t), intent(in) :: def
      class(prclib_driver_t), intent(in) :: lib_driver
      integer, intent(in) :: i
      class(prc_core_driver_t), intent(inout) :: proc_driver
    end subroutine prc_core_def_connect
  end interface

```

13.3.2 Process core template

We must be able to automatically allocate a process core definition object with the appropriate type, given only the type name.

To this end, we introduce a `prc_template_t` type which is simply a wrapper for an empty `prc_core_def_t` object. Choosing one of the templates from an array, we can allocate the target object.

```

<Prc core def: public>+≡
  public :: prc_template_t

<Prc core def: types>+≡
  type :: prc_template_t
    class(prc_core_def_t), allocatable :: core_def
  end type prc_template_t

```

The allocation routine. We use the `source` option of the `allocate` statement. The `mold` option would probably more appropriate, but is a F2008 feature.

```

<Prc core def: public>+≡
  public :: allocate_core_def

<Prc core def: procedures>+≡
  subroutine allocate_core_def (template, name, core_def)
    type(prc_template_t), dimension(:), intent(in) :: template
    type(string_t), intent(in) :: name
    class(prc_core_def_t), allocatable :: core_def
    integer :: i
    do i = 1, size (template)
      if (template(i)%core_def%type_string () == name) then
        allocate (core_def, source = template(i)%core_def)
        return
      end if
    end do
  end subroutine allocate_core_def

```

13.3.3 Process driver

For each process component, we implement a driver object which holds the calls to the matrix element and various auxiliary routines as procedure pointers. Any actual calculation will use this object to communicate with the process.

Depending on the type of process (as described by a corresponding `prc_core_def` object), the procedure pointers may refer to external or internal code, and there may be additional procedures for certain types. The base type defined here is abstract.

```

<Prc core def: public>+≡
  public :: prc_core_driver_t

<Prc core def: types>+≡
  type, abstract :: prc_core_driver_t
  contains
    <Prc core def: process driver: TBP>
  end type prc_core_driver_t

```

This returns the process type. No reference to contents.

```

<Prc core def: process driver: TBP>≡
  procedure(prc_core_driver_type_name), nopass, deferred :: type_name

<Prc core def: interfaces>+≡
  abstract interface
    function prc_core_driver_type_name () result (type)
      import
      type(string_t) :: type
    end function prc_core_driver_type_name
  end interface

```

13.3.4 Process driver for intrinsic process

This is an abstract extension for the driver type. It has one additional method, namely a subroutine that fills the record of constant process data. For an external process, this task is performed by the external library driver instead.

```

<Prc core def: public>+≡
  public :: process_driver_internal_t

<Prc core def: types>+≡
  type, extends (prc_core_driver_t), abstract :: process_driver_internal_t
  contains
    <Prc core def: process driver internal: TBP>
  end type process_driver_internal_t

<Prc core def: process driver internal: TBP>≡
  procedure(process_driver_fill_constants), deferred :: fill_constants

<Prc core def: interfaces>+≡
  abstract interface
    subroutine process_driver_fill_constants (driver, data)
      import
      class(process_driver_internal_t), intent(in) :: driver
      type(process_constants_t), intent(out) :: data
    end subroutine process_driver_fill_constants
  end interface

```

13.4 Process library access

Processes (the code and data that are necessary for evaluating matrix elements of a particular process or process component) are organized in process libraries. In full form, process libraries contain generated and dynamically compiled and linked code, so they are actual libraries on the OS level. Alternatively, there may be simple processes that can be generated without referring to external libraries, and external libraries that are just linked in.

This module interfaces the OS to create, build, and use process libraries.

We work with two related data structures. There is the list of process configurations that stores the user input and data derived from it. A given process configuration list is scanned for creating a process library, which consists of both data and code. The creation step involves calling external programs and incorporating external code.

For the subsequent integration and event generation steps, we read the process library. We also support partial (re)creation of the process library. To this end, we should be able to reconstruct the configuration data records from the process library.

```
<process_libraries.f90>≡
  <File header>

  module process_libraries

    use iso_c_binding !NODEP!
    use kinds
    <Use strings>
    use io_units
    use unit_tests
    use diagnostics
    use md5
    use physics_defs
    use os_interface
    use lexers
    use model_data
    use particle_specifiers
    use process_constants
    use prclib_interfaces
    use prc_core_def

    <Standard module head>

    <Process libraries: public>

    <Process libraries: parameters>

    <Process libraries: types>

    <Process libraries: interfaces>

    <Process libraries: test declarations>

    contains
```

⟨Process libraries: procedures⟩

⟨Process libraries: tests⟩

`end module process_libraries`

13.4.1 Auxiliary stuff

Here is a small subroutine that strips the left-hand side and the equals sign off an equation.

```
⟨Process libraries: procedures⟩≡
subroutine strip_prefix (buffer)
  character(*), intent(inout) :: buffer
  type(string_t) :: string, prefix
  string = buffer
  call split (string, prefix, "=")
  buffer = string
end subroutine strip_prefix
```

13.4.2 Process definition objects

We collect process configuration data in a derived type, `process_def_t`. A process can be a collection of several components which are treated as a single entity for the purpose of observables and event generation. Multiple process components may initially be defined by the user. The system may add additional components, e.g., subtraction terms. The common data type is `process_component_def_t`. Within each component, there are several universal data items, and a part which depend on the particular process variant. The latter is covered by an abstract type `prc_core_def_t` and its extensions.

Wrapper for components

We define a wrapper type for the configuration of individual components.

The string `basename` is used for building file, module, and function names for the current process component. Initially, it will be built from the corresponding process `basename` by appending an alphanumeric suffix.

The logical `initial` tells whether this is a user-defined (true) or system-generated (false) configuration.

The numbers `n_in`, `n_out`, and `n_tot` denote the incoming, outgoing and total number of particles (partons) participating in the process component, respectively. These are the nominal particles, as input by the user (recombination may change the particle content, for the output events).

The string arrays `prt_in` and `prt_out` hold the particle specifications as provided by the user. For a system-generated process component, they remain deallocated.

The `method` string is used to determine the type of process matrix element and how it is obtained.

The `description` string collects the information about particle content and method in a single human-readable string.

The pointer object `core_def` is allocated according to the actual process variant, which depends on the method. The subobject holds any additional configuration data that is relevant for the process component.

We assume that no finalizer is needed.

```

<Process libraries: public>≡
    public :: process_component_def_t

<Process libraries: types>≡
    type :: process_component_def_t
    private
    type(string_t) :: basename
    logical :: initial = .false.
    integer :: n_in = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    type(prt_spec_t), dimension(:), allocatable :: prt_in
    type(prt_spec_t), dimension(:), allocatable :: prt_out
    type(string_t) :: method
    type(string_t) :: description
    class(prc_core_def_t), allocatable :: core_def
    character(32) :: md5sum = ""
    integer :: nlo_type = BORN
    integer :: associated_born = 0
    integer :: associated_real = 0
    integer :: associated_virt = 0
    integer :: associated_sub = 0
    logical :: active_nlo_component
contains
    <Process libraries: process component def: TBP>
end type process_component_def_t

```

Display the complete content.

```

<Process libraries: process component def: TBP>≡
    procedure :: write => process_component_def_write

<Process libraries: procedures>+≡
    subroutine process_component_def_write (object, unit)
    class(process_component_def_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(3x,A,A)") "Component ID      = ", char (object%basename)
    write (u, "(3x,A,L1)") "Initial component = ", object%initial
    write (u, "(3x,A,I0,1x,I0,1x,I0)") "N (in, out, tot)   = ", &
        object%n_in, object%n_out, object%n_tot
    write (u, "(3x,A)", advance="no") "Particle content   = "
    if (allocated (object%prt_in)) then
        call prt_spec_write (object%prt_in, u, advance="no")
    else
        write (u, "(A)", advance="no") "[undefined]"
    end if
    write (u, "(A)", advance="no") " => "
    if (allocated (object%prt_out)) then
        call prt_spec_write (object%prt_out, u, advance="no")
    end if
end subroutine process_component_def_write

```

```

else
  write (u, "(A)", advance="no") "[undefined]"
end if
write (u, "(A)")
if (object%method /= "") then
  write (u, "(3x,A,A)") "Method          = ", &
    char (object%method)
else
  write (u, "(3x,A)") "Method          = [undefined]"
end if
if (allocated (object%core_def)) then
  write (u, "(3x,A,A)") "Process variant = ", &
    char (object%core_def%type_string ())
  call object%core_def%write (u)
else
  write (u, "(3x,A)") "Process variant = [undefined]"
end if
write (u, "(3x,A,A,A)") "MD5 sum (def)    = '", object%md5sum, "'"
end subroutine process_component_def_write

```

Read the process component definition. Allocate the process variant definition with appropriate type, matching the type name on file with the provided templates.

```

<Process libraries: process component def: TBP>+≡
  procedure :: read => process_component_def_read

<Process libraries: procedures>+≡
  subroutine process_component_def_read (component, unit, core_def_templates)
    class(process_component_def_t), intent(out) :: component
    integer, intent(in) :: unit
    type(prc_template_t), dimension(:), intent(in) :: core_def_templates
    character(80) :: buffer
    type(string_t) :: var_buffer, prefix, in_state, out_state
    type(string_t) :: variant_type

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    component%basename = trim (adjustl (buffer))

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    read (buffer, *) component%initial

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    read (buffer, *) component%n_in, component%n_out, component%n_tot

    call get (unit, var_buffer)
    call split (var_buffer, prefix, "=") ! keeps 'in => out'
    call split (var_buffer, prefix, "=") ! actually: separator is '=>'

    in_state = prefix
    if (component%n_in > 0) then
      call prt_spec_read (component%prt_in, in_state)
    end if
  end subroutine

```



```

end if

out_state = extract (var_buffer, 2)
if (component%n_out > 0) then
    call prt_spec_read (component%prt_out, out_state)
end if

read (unit, "(A)") buffer
call strip_prefix (buffer)
component%method = trim (adjustl (buffer))
if (component%method == "[undefined]") &
    component%method = ""

read (unit, "(A)") buffer
call strip_prefix (buffer)
variant_type = trim (adjustl (buffer))
call allocate_core_def &
    (core_def_templates, variant_type, component%core_def)
if (allocated (component%core_def)) then
    call component%core_def%read (unit)
end if

read (unit, "(A)") buffer
call strip_prefix (buffer)
read (buffer(3:34), "(A32)") component%md5sum

end subroutine process_component_def_read

```

Short account.

```

<Process libraries: process component def: TBP>+≡
    procedure :: show => process_component_def_show

<Process libraries: procedures>+≡
    subroutine process_component_def_show (object, unit)
        class(process_component_def_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(6x,A)", advance="no") char (object%basename)
        if (.not. object%initial) &
            write (u, "('*')", advance="no")
        write (u, "(:',1x)", advance="no")
        if (allocated (object%prt_in)) then
            call prt_spec_write (object%prt_in, u, advance="no")
        else
            write (u, "(A)", advance="no") "[undefined]"
        end if
        write (u, "(A)", advance="no") " => "
        if (allocated (object%prt_out)) then
            call prt_spec_write (object%prt_out, u, advance="no")
        else
            write (u, "(A)", advance="no") "[undefined]"
        end if
        if (object%method /= "") then

```

```

        write (u, "(2x,['',A,'])") char (object%method)
    else
        write (u, *)
    end if
end subroutine process_component_def_show

```

Compute the MD5 sum of a process component. We reset the stored MD5 sum to the empty string (so a previous value is not included in the calculation), the write a temporary file and calculate the MD5 sum of that file.

This implies that all data that are displayed by the `write` method become part of the MD5 sum calculation.

The `model` is not part of the object, but must be included in the MD5 sum. Otherwise, modifying the model and nothing else would not trigger remaking the process-component source. Note that the model parameters may change later and therefore are not incorporated.

After the MD5 sum of the component has been computed, we communicate it to the `writer` subobject of the specific `core_def` component. Although these types are abstract, the MD5-related features are valid for the abstract types.

```

<Process libraries: process component def: TBP>+≡
    procedure :: compute_md5sum => process_component_def_compute_md5sum

<Process libraries: procedures>+≡
    subroutine process_component_def_compute_md5sum (component, model)
        class(process_component_def_t), intent(inout) :: component
        class(model_data_t), intent(in), optional, target :: model
        integer :: u
        component%md5sum = ""
        u = free_unit ()
        open (u, status = "scratch", action = "readwrite")
        if (present (model)) write (u, "(A32)") model%get_md5sum ()
        call component%write (u)
        rewind (u)
        component%md5sum = md5sum (u)
        close (u)
        if (allocated (component%core_def)) then
            call component%core_def%set_md5sum (component%md5sum)
        end if
    end subroutine process_component_def_compute_md5sum

```

Allocate the process driver (with a suitable type) for a process component. For internal processes, we may set all data already at this stage.

```

<Process libraries: process component def: TBP>+≡
    procedure :: allocate_driver => process_component_def_allocate_driver

<Process libraries: procedures>+≡
    subroutine process_component_def_allocate_driver (component, driver)
        class(process_component_def_t), intent(in) :: component
        class(prc_core_driver_t), intent(out), allocatable :: driver
        if (allocated (component%core_def)) then
            call component%core_def%allocate_driver (driver, component%basename)
        end if
    end subroutine process_component_def_allocate_driver

```

Tell whether the process core needs external code.

```

(Process libraries: process component def: TBP)+≡
    procedure :: needs_code => process_component_def_needs_code

(Process libraries: procedures)+≡
    function process_component_def_needs_code (component) result (flag)
        class(process_component_def_t), intent(in) :: component
        logical :: flag
        flag = component%core_def%needs_code ()
    end function process_component_def_needs_code

```

If there is external code, the `core_def` subobject should provide a writer object. This method returns a pointer to the writer.

```

(Process libraries: process component def: TBP)+≡
    procedure :: get_writer_ptr => process_component_def_get_writer_ptr

(Process libraries: procedures)+≡
    function process_component_def_get_writer_ptr (component) result (writer)
        class(process_component_def_t), intent(in), target :: component
        class(prc_writer_t), pointer :: writer
        writer => component%core_def%writer
    end function process_component_def_get_writer_ptr

```

Return an array which holds the names of all C functions that this process component implements.

```

(Process libraries: process component def: TBP)+≡
    procedure :: get_features => process_component_def_get_features

(Process libraries: procedures)+≡
    function process_component_def_get_features (component) result (features)
        class(process_component_def_t), intent(in) :: component
        type(string_t), dimension(:), allocatable :: features
        call component%core_def%get_features (features)
    end function process_component_def_get_features

```

Assign procedure pointers in the `driver` component (external processes). For internal processes, this is meaningless.

```

(Process libraries: process component def: TBP)+≡
    procedure :: connect => process_component_def_connect

(Process libraries: procedures)+≡
    subroutine process_component_def_connect &
        (component, lib_driver, i, proc_driver)
        class(process_component_def_t), intent(in) :: component
        class(prclib_driver_t), intent(in) :: lib_driver
        integer, intent(in) :: i
        class(prc_core_driver_t), intent(inout) :: proc_driver
        select type (proc_driver)
            class is (process_driver_internal_t)
                ! nothing to do
            class default
                call component%core_def%connect (lib_driver, i, proc_driver)
            end select
    end subroutine process_component_def_connect

```

Return a pointer to the process core definition, which is of abstract type.

```

(Process libraries: process component def: TBP)+≡
  procedure :: get_core_def_ptr => process_component_get_core_def_ptr

(Process libraries: procedures)+≡
  function process_component_get_core_def_ptr (component) result (ptr)
    class(process_component_def_t), intent(in), target :: component
    class(prc_core_def_t), pointer :: ptr
    ptr => component%core_def
  end function process_component_get_core_def_ptr

```

Return nominal particle counts, as input by the user.

```

(Process libraries: process component def: TBP)+≡
  procedure :: get_n_in  => process_component_def_get_n_in
  procedure :: get_n_out => process_component_def_get_n_out
  procedure :: get_n_tot => process_component_def_get_n_tot

(Process libraries: procedures)+≡
  function process_component_def_get_n_in (component) result (n_in)
    class(process_component_def_t), intent(in) :: component
    integer :: n_in
    n_in = component%n_in
  end function process_component_def_get_n_in

  function process_component_def_get_n_out (component) result (n_out)
    class(process_component_def_t), intent(in) :: component
    integer :: n_out
    n_out = component%n_out
  end function process_component_def_get_n_out

  function process_component_def_get_n_tot (component) result (n_tot)
    class(process_component_def_t), intent(in) :: component
    integer :: n_tot
    n_tot = component%n_tot
  end function process_component_def_get_n_tot

```

Allocate and return string arrays for the incoming and outgoing particles.

```

(Process libraries: process component def: TBP)+≡
  procedure :: get_prt_in => process_component_def_get_prt_in
  procedure :: get_prt_out => process_component_def_get_prt_out

(Process libraries: procedures)+≡
  subroutine process_component_def_get_prt_in (component, prt)
    class(process_component_def_t), intent(in) :: component
    type(string_t), dimension(:), intent(out), allocatable :: prt
    integer :: i
    allocate (prt (component%n_in))
    do i = 1, component%n_in
      prt(i) = component%prt_in(i)%to_string ()
    end do
  end subroutine process_component_def_get_prt_in

  subroutine process_component_def_get_prt_out (component, prt)
    class(process_component_def_t), intent(in) :: component

```

```

type(string_t), dimension(:), intent(out), allocatable :: prt
integer :: i
allocate (prt (component%n_out))
do i = 1, component%n_out
    prt(i) = component%prt_out(i)%to_string ()
end do
end subroutine process_component_def_get_prt_out

```

Return the MD5 sum.

```

(Process libraries: process component def: TBP)+≡
    procedure :: get_md5sum => process_component_def_get_md5sum

(Process libraries: procedures)+≡
    function process_component_def_get_md5sum (component) result (md5sum)
        class(process_component_def_t), intent(in) :: component
        character(32) :: md5sum
        md5sum = component%md5sum
    end function process_component_def_get_md5sum

```

Get NLO data

```

(Process libraries: process component def: TBP)+≡
    procedure :: get_nlo_type => process_component_def_get_nlo_type
    procedure :: get_associated_born &
        => process_component_def_get_associated_born
    procedure :: get_association_list &
        => process_component_def_get_association_list
    procedure :: is_active_nlo_component &
        => process_component_def_is_active_nlo_component
    procedure :: get_associated_real => process_component_def_get_associated_real

(Process libraries: procedures)+≡
    function process_component_def_get_nlo_type (component) result (nlo_type)
        class(process_component_def_t), intent(in) :: component
        integer :: nlo_type
        nlo_type = component%nlo_type
    end function process_component_def_get_nlo_type

    function process_component_def_get_associated_born (component) result (i_born)
        class(process_component_def_t), intent(in) :: component
        integer :: i_born
        i_born = component%associated_born
    end function process_component_def_get_associated_born

    function process_component_def_is_active_nlo_component (component) result (active)
        class(process_component_def_t), intent(in) :: component
        logical :: active
        active = component%active_nlo_component
    end function process_component_def_is_active_nlo_component

    function process_component_def_get_association_list (component) result (list)
        class(process_component_def_t), intent(in) :: component
        integer, dimension(4) :: list
        list(1) = component%associated_born
        list(2) = component%associated_real

```

```

list(3) = component%associated_virt
list(4) = component%associated_sub
end function process_component_def_get_association_list

function process_component_def_get_associated_real (component) result (i_real)
  class(process_component_def_t), intent(in) :: component
  integer :: i_real
  i_real = component%associated_real
end function process_component_def_get_associated_real

```

Process definition

The process component definitions are collected in a common process definition object.

The `id` is the ID string that the user has provided for identifying this process. It must be a string that is allowed as part of a Fortran variable name, since it may be used for generating code.

The number `n_in` is 1 or 2 for a decay or scattering process, respectively. This must be identical to `n_in` for all components.

The initial and extra component definitions (see above) are allocated as the `initial` and `extra` arrays, respectively. The latter are determined from the former.

The `md5sum` is used to verify the integrity of the configuration.

```

<Process libraries: public>+≡
  public :: process_def_t

<Process libraries: types>+≡
  type :: process_def_t
    private
    type(string_t) :: id
    integer :: num_id = 0
    class(model_data_t), pointer :: model => null ()
    type(string_t) :: model_name
    integer :: n_in = 0
    integer :: n_initial = 0
    integer :: n_extra = 0
    type(process_component_def_t), dimension(:), allocatable :: initial
    type(process_component_def_t), dimension(:), allocatable :: extra
    character(32) :: md5sum = ""
    logical :: nlo_process = .false.
    logical :: combined_nlo_integration = .false.
  contains
    <Process libraries: process def: TBP>
  end type process_def_t

```

Write the process definition including components:

```

<Process libraries: process def: TBP>≡
  procedure :: write => process_def_write

<Process libraries: procedures>+≡
  subroutine process_def_write (object, unit)
    class(process_def_t), intent(in) :: object

```

```

integer, intent(in) :: unit
integer :: i
write (unit, "(1x,A,A,A)") "ID = ', char (object%id), '"
if (object%num_id /= 0) &
    write (unit, "(1x,A,I0)") "ID(num) = ", object%num_id
select case (object%n_in)
case (1); write (unit, "(1x,A)") "Decay"
case (2); write (unit, "(1x,A)") "Scattering"
case default
    write (unit, "(1x,A)") "[Undefined process]"
    return
end select
if (object%model_name /= "") then
    write (unit, "(1x,A,A)") "Model = ", char (object%model_name)
else
    write (unit, "(1x,A)") "Model = [undefined]"
end if
write (unit, "(1x,A,I0)") "Initially defined component(s) = ", &
    object%n_initial
write (unit, "(1x,A,I0)") "Extra generated component(s) = ", &
    object%n_extra
write (unit, "(1x,A,A,A)") "MD5 sum = ', object%md5sum, '"
if (allocated (object%initial)) then
    do i = 1, size (object%initial)
        write (unit, "(1x,A,I0)") "Component #", i
        call object%initial(i)%write (unit)
    end do
end if
if (allocated (object%extra)) then
    do i = 1, size (object%extra)
        write (unit, "(1x,A,I0)") "Component #", object%n_initial + i
        call object%extra(i)%write (unit)
    end do
end if
end subroutine process_def_write

```

Read the process definition including components.

(Process libraries: process def: TBP)+≡

```

procedure :: read => process_def_read

```

(Process libraries: procedures)+≡

```

subroutine process_def_read (object, unit, core_def_templates)
class(process_def_t), intent(out) :: object
integer, intent(in) :: unit
type(prc_template_t), dimension(:), intent(in) :: core_def_templates
integer :: i, i1, i2
character(80) :: buffer, ref
read (unit, "(A)") buffer
call strip_prefix (buffer)
i1 = scan (buffer, "'")
i2 = scan (buffer, '"', back=.true.)
if (i2 > i1) then
    object%id = buffer(i1+1:i2-1)
else

```

```

        object%id = ""
    end if

    read (unit, "(A)") buffer
    select case (buffer(2:11))
    case ("Decay      "); object%n_in = 1
    case ("Scattering"); object%n_in = 2
    case default
        return
    end select

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    object%model_name = trim (adjustl (buffer))
    if (object%model_name == "[undefined]") object%model_name = ""

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    read (buffer, *) object%n_initial

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    read (buffer, *) object%n_extra

    read (unit, "(A)") buffer
    call strip_prefix (buffer)
    read (buffer(3:34), "(A32)") object%md5sum

    if (object%n_initial > 0) then
        allocate (object%initial (object%n_initial))
        do i = 1, object%n_initial
            read (unit, "(A)") buffer
            write (ref, "(1x,A,I0)") "Component #", i
            if (buffer /= ref) return ! Wrong component header
            call object%initial(i)%read (unit, core_def_templates)
        end do
    end if

end subroutine process_def_read

```

Short account.

```

<Process libraries: process def: TBP>+≡
    procedure :: show => process_def_show

<Process libraries: procedures>+≡
    subroutine process_def_show (object, unit)
        class(process_def_t), intent(in) :: object
        integer, intent(in) :: unit
        integer :: i
        write (unit, "(4x,A)", advance="no") char (object%id)
        if (object%num_id /= 0) &
            write (unit, "(1x,'( ',I0,')')", advance="no") object%num_id
        if (object%model_name /= "") &
            write (unit, "(1x,'[ ',A,']')", advance="no") char (object%model_name)
    end subroutine

```



```

    if (allocated (object%initial)) then
        do i = 1, size (object%initial)
            call object%initial(i)%show (unit)
        end do
    end if
    if (allocated (object%extra)) then
        do i = 1, size (object%extra)
            call object%extra(i)%show (unit)
        end do
    end if
end subroutine process_def_show

```

Initialize an entry (initialize the process definition inside). We allocate the 'initial' set of components. Extra components remain unallocated.

The model should be present as a pointer. This allows us to retrieve the model's MD5 sum. However, for various tests it is sufficient to have the name.

We create the basenames for the process components by appending a suffix which we increment for each component.

```

<Process libraries: process def: TBP>+≡
    procedure :: init => process_def_init

<Process libraries: procedures>+≡
    subroutine process_def_init (def, id, &
        model, model_name, n_in, n_components, num_id, nlo_process)
        class(process_def_t), intent(out) :: def
        type(string_t), intent(in), optional :: id
        class(model_data_t), intent(in), optional, target :: model
        type(string_t), intent(in), optional :: model_name
        integer, intent(in), optional :: n_in
        integer, intent(in), optional :: n_components
        integer, intent(in), optional :: num_id
        logical, intent(in), optional :: nlo_process
        character(16) :: suffix
        integer :: i
        if (present (id)) then
            def%id = id
        else
            def%id = ""
        end if
        if (present (num_id)) then
            def%num_id = num_id
        end if
        if (present (model)) then
            def%model => model
            def%model_name = model%get_name ()
        else
            def%model => null ()
            if (present (model_name)) then
                def%model_name = model_name
            else
                def%model_name = ""
            end if
        end if
        if (present (n_in)) def%n_in = n_in

```

```

if (present (n_components)) then
  def%n_initial = n_components
  allocate (def%initial (n_components))
end if
if (present (nlo_process)) def%nlo_process = nlo_process
def%initial%initial = .true.
def%initial%method = ""
do i = 1, def%n_initial
  write (suffix, "(A,I0)") "_i", i
  def%initial(i)%basename = def%id // trim (suffix)
end do
def%initial%description = ""
end subroutine process_def_init

```

Initialize an initial component. The particle content must be specified. The process core block is not (yet) allocated.

We assume that the particle arrays match the `n_in` and `n_out` values in size. The model is referred to by name; it is identified as an existing model later. The index `i` must refer to an existing element of the component array.

Data specific for the process core of a component are imported as the `core_def` argument. We should allocate an object of class `prc_core_def_t` with the appropriate specific type, fill it, and transfer it to the process component definition here. The allocation is moved, so the original allocated object is returned empty.

(Process libraries: process def: TBP)+≡

```

procedure :: import_component => process_def_import_component

```

(Process libraries: procedures)+≡

```

subroutine process_def_import_component (def, &
  i, n_out, prt_in, prt_out, method, variant, &
  nlo_type, active)
class(process_def_t), intent(inout) :: def
integer, intent(in) :: i
integer, intent(in), optional :: n_out
type(prt_spec_t), dimension(:), intent(in), optional :: prt_in
type(prt_spec_t), dimension(:), intent(in), optional :: prt_out
type(string_t), intent(in), optional :: method
integer, intent(in), optional :: nlo_type
logical, intent(in), optional :: active
type(string_t) :: nlo_type_string
class(prc_core_def_t), &
  intent(inout), allocatable, optional :: variant
integer :: p
associate (comp => def%initial(i))
  if (present (n_out)) then
    comp%n_in = def%n_in
    comp%n_out = n_out
    comp%n_tot = def%n_in + n_out
  end if
  if (present (prt_in)) then
    allocate (comp%prt_in (size (prt_in)))
    comp%prt_in = prt_in
  end if
end if

```

```

if (present (prt_out)) then
  allocate (comp%prt_out (size (prt_out)))
  comp%prt_out = prt_out
end if
if (present (method)) comp%method = method
if (present (variant)) then
  call move_alloc (variant, comp%core_def)
end if
if (present (nlo_type)) then
  comp%nlo_type = nlo_type
end if
if (present (active)) then
  comp%active_nlo_component = active
else
  comp%active_nlo_component = .true.
end if
if (allocated (comp%prt_in) .and. allocated (comp%prt_out)) then
  associate (d => comp%description)
    d = ""
    do p = 1, size (prt_in)
      if (p > 1) d = d // ", "
      d = d // comp%prt_in(p)%to_string ()
    end do
    d = d // " => "
    do p = 1, size (prt_out)
      if (p > 1) d = d // ", "
      d = d // comp%prt_out(p)%to_string ()
    end do
    if (comp%method /= "") then
      d = d // " [" // comp%method // "]"
    end if
    nlo_type_string = get_nlo_type_string (comp%nlo_type)
    if (nlo_type_string /= "Born") then
      d = d // ", [" // nlo_type_string // "]"
    end if
  end associate
end if
end associate
contains
function get_nlo_type_string (nlo_type) result (nlo_type_string)
  integer, intent(in) :: nlo_type
  type(string_t) :: nlo_type_string
  select case (nlo_type)
  case (BORN)
    nlo_type_string = 'Born'
  case (NLO_REAL)
    nlo_type_string = 'Real'
  case (NLO_VIRTUAL)
    nlo_type_string = 'Virtual'
  case (NLO_PDF)
    nlo_type_string = 'Pdf'
  case (NLO_SUBTRACTION)
    nlo_type_string = 'Subtraction'
  end select

```

```

    end function get_nlo_type_string
end subroutine process_def_import_component

```

```

<Process libraries: process def: TBP>+≡
    procedure :: get_n_components => process_def_get_n_components

<Process libraries: procedures>+≡
    function process_def_get_n_components (def) result (n)
        class(process_def_t), intent(in) :: def
        integer :: n
        n = size (def%initial)
    end function process_def_get_n_components

```

```

<Process libraries: process def: TBP>+≡
    procedure :: set_associated_components => &
        process_def_set_associated_components

<Process libraries: procedures>+≡
    subroutine process_def_set_associated_components (def, i, &
        i_born, i_real, i_virt, i_sub)
        class(process_def_t), intent(inout) :: def
        integer, intent(in) :: i
        integer, intent(in) :: i_born, i_real
        integer, intent(in) :: i_virt, i_sub
        associate (comp => def%initial(i))
            comp%associated_born = i_born
            comp%associated_real = i_real
            comp%associated_virt = i_virt
            comp%associated_sub = i_sub
        end associate
    end subroutine process_def_set_associated_components

```

Compute the MD5 sum for this process definition. We compute the MD5 sums for all components individually, than concatenate a string of those and compute the MD5 sum of this string. We also include the model name. All other data part of the component definitions.

```

<Process libraries: process def: TBP>+≡
    procedure :: compute_md5sum => process_def_compute_md5sum

<Process libraries: procedures>+≡
    subroutine process_def_compute_md5sum (def, model)
        class(process_def_t), intent(inout) :: def
        class(model_data_t), intent(in), optional, target :: model
        integer :: i
        type(string_t) :: buffer
        buffer = def%model_name
        do i = 1, def%n_initial
            call def%initial(i)%compute_md5sum (model)
            buffer = buffer // def%initial(i)%md5sum
        end do
        do i = 1, def%n_extra
            call def%extra(i)%compute_md5sum (model)
            buffer = buffer // def%initial(i)%md5sum
        end do
    end subroutine process_def_compute_md5sum

```

```

end do
def%md5sum = md5sum (char (buffer))
end subroutine process_def_compute_md5sum

```

Return the MD5 sum of the process or of a process component.

```

<Process libraries: process def: TBP>+≡
  procedure :: get_md5sum => process_def_get_md5sum
<Process libraries: procedures>+≡
  function process_def_get_md5sum (def, i_component) result (md5sum)
    class(process_def_t), intent(in) :: def
    integer, intent(in), optional :: i_component
    character(32) :: md5sum
    if (present (i_component)) then
      md5sum = def%initial(i_component)%md5sum
    else
      md5sum = def%md5sum
    end if
  end function process_def_get_md5sum

```

This query tells whether a specific process component relies on external code. This includes all traditional WHIZARD matrix elements which rely on O’MEGA for code generation. Other process components (trivial decays, subtraction terms) do not require external code.

NOTE: Implemented only for initial component.

The query is passed to the process component.

```

<Process libraries: process def: TBP>+≡
  procedure :: needs_code => process_def_needs_code
<Process libraries: procedures>+≡
  function process_def_needs_code (def, i_component) result (flag)
    class(process_def_t), intent(in) :: def
    integer, intent(in) :: i_component
    logical :: flag
    flag = def%initial(i_component)%needs_code ()
  end function process_def_needs_code

```

Process definition list

A list of process definitions is the starting point for creating a process library. The list is built when reading the user input. When reading an existing process library, the list is used for cross-checking and updating the configuration.

We need a type for the list entry. The simplest way is to extend the process definition type, so all methods apply to the process definition directly.

```

<Process libraries: public>+≡
  public :: process_def_entry_t
<Process libraries: types>+≡
  type, extends (process_def_t) :: process_def_entry_t
    private
    type(process_def_entry_t), pointer :: next => null ()
  end type process_def_entry_t

```

This is the type for the list itself.

```

<Process libraries: types>+≡
  type :: process_def_list_t
  private
    type(process_def_entry_t), pointer :: first => null ()
    type(process_def_entry_t), pointer :: last => null ()
  contains
    <Process libraries: process def list: TBP>
  end type process_def_list_t

```

The deallocates the list iteratively. We assume that the list entries do not need finalization themselves.

```

<Process libraries: process def list: TBP>≡
  procedure :: final => process_def_list_final

<Process libraries: procedures>+≡
  subroutine process_def_list_final (list)
    class(process_def_list_t), intent(inout) :: list
    type(process_def_entry_t), pointer :: current
    nullify (list%last)
    do while (associated (list%first))
      current => list%first
      list%first => current%next
      deallocate (current)
    end do
  end subroutine process_def_list_final

```

Write the complete list.

```

<Process libraries: process def list: TBP>+≡
  procedure :: write => process_def_list_write

<Process libraries: procedures>+≡
  subroutine process_def_list_write (object, unit, libpath)
    class(process_def_list_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: libpath
    type(process_def_entry_t), pointer :: entry
    integer :: i, u
    u = given_output_unit (unit)
    if (associated (object%first)) then
      i = 1
      entry => object%first
      do while (associated (entry))
        write (u, "(1x,A,I0,A)") "Process #", i, ":"
        call entry%write (u)
        i = i + 1
        entry => entry%next
        if (associated (entry)) write (u, *)
      end do
    else
      write (u, "(1x,A)") "Process definition list: [empty]"
    end if
  end subroutine process_def_list_write

```

Short account.

```

<Process libraries: process def list: TBP>+=
  procedure :: show => process_def_list_show

<Process libraries: procedures>+=
  subroutine process_def_list_show (object, unit)
    class(process_def_list_t), intent(in) :: object
    integer, intent(in), optional :: unit
    type(process_def_entry_t), pointer :: entry
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%first)) then
      write (u, "(2x,A)") "Processes:"
      entry => object%first
      do while (associated (entry))
        call entry%show (u)
        entry => entry%next
      end do
    else
      write (u, "(2x,A)") "Processes: [empty]"
    end if
  end subroutine process_def_list_show

```

Read the complete list. We need an array of templates for the component sub-objects of abstract `prc_core_t` type, to allocate them with the correct specific type.

NOTE: Error handling is missing. Reading will just be aborted on error, or an I/O error occurs.

```

<Process libraries: process def list: TBP>+=
  procedure :: read => process_def_list_read

<Process libraries: procedures>+=
  subroutine process_def_list_read (object, unit, core_def_templates)
    class(process_def_list_t), intent(out) :: object
    integer, intent(in) :: unit
    type(prc_template_t), dimension(:), intent(in) :: core_def_templates
    type(process_def_entry_t), pointer :: entry
    character(80) :: buffer, ref
    integer :: i
    read (unit, "(A)") buffer
    write (ref, "(1x,A)") "Process definition list: [empty]"
    if (buffer == ref) return ! OK: empty library
    backspace (unit)
    READ_ENTRIES: do i = 1, huge (0)
      if (i > 1) read (unit, *, end=1)
      read (unit, "(A)") buffer

      write (ref, "(1x,A,I0,A)") "Process #", i, ":"
      if (buffer /= ref) return ! Wrong process header: done.
      allocate (entry)
      call entry%read (unit, core_def_templates)
      call object%append (entry)
    end do READ_ENTRIES
1  continue ! EOF: done

```

```
end subroutine process_def_list_read
```

Append an entry to the list. The entry should be allocated as a pointer, and the pointer allocation is transferred. The original pointer is returned null.

```
<Process libraries: process def list: TBP>+≡
  procedure :: append => process_def_list_append

<Process libraries: procedures>+≡
  subroutine process_def_list_append (list, entry)
    class(process_def_list_t), intent(inout) :: list
    type(process_def_entry_t), intent(inout), pointer :: entry
    if (list%contains (entry%id)) then
      call msg_fatal ("Recording process: '" // char (entry%id) &
        // "' has already been defined")
    end if
    if (associated (list%first)) then
      list%last%next => entry
    else
      list%first => entry
    end if
    list%last => entry
    entry => null ()
  end subroutine process_def_list_append
```

Probe the process definition list

Return the number of processes supported by the library.

```
<Process libraries: process def list: TBP>+≡
  procedure :: get_n_processes => process_def_list_get_n_processes

<Process libraries: procedures>+≡
  function process_def_list_get_n_processes (list) result (n)
    integer :: n
    class(process_def_list_t), intent(in) :: list
    type(process_def_entry_t), pointer :: current
    n = 0
    current => list%first
    do while (associated (current))
      n = n + 1
      current => current%next
    end do
  end function process_def_list_get_n_processes
```

Allocate an array with the process IDs supported by the library.

```
<Process libraries: process def list: TBP>+≡
  procedure :: get_process_id_list => process_def_list_get_process_id_list

<Process libraries: procedures>+≡
  subroutine process_def_list_get_process_id_list (list, id)
    class(process_def_list_t), intent(in) :: list
    type(string_t), dimension(:), allocatable, intent(out) :: id
    type(process_def_entry_t), pointer :: current
```



```

integer :: i
allocate (id (list%get_n_processes ()))
i = 0
current => list%first
do while (associated (current))
    i = i + 1
    id(i) = current%id
    current => current%next
end do
end subroutine process_def_list_get_process_id_list

```

Return true if a given process is in the library.

(Process libraries: process def list: TBP)+≡

```

procedure :: contains => process_def_list_contains

```

(Procedures: procedures)+≡

```

function process_def_list_contains (list, id) result (flag)
    logical :: flag
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(process_def_entry_t), pointer :: current
    current => list%first
    do while (associated (current))
        if (id == current%id) then
            flag = .true.; return
        end if
        current => current%next
    end do
    flag = .false.
end function process_def_list_contains

```

Return the index of the entry that corresponds to a given process.

(Process libraries: process def list: TBP)+≡

```

procedure :: get_entry_index => process_def_list_get_entry_index

```

(Procedures: procedures)+≡

```

function process_def_list_get_entry_index (list, id) result (n)
    integer :: n
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(process_def_entry_t), pointer :: current
    n = 0
    current => list%first
    do while (associated (current))
        n = n + 1
        if (id == current%id) then
            return
        end if
        current => current%next
    end do
    n = 0
end function process_def_list_get_entry_index

```

Return the numerical ID for a process.

```

(Process libraries: process def list: TBP)+≡
  procedure :: get_num_id => process_def_list_get_num_id

(Process libraries: procedures)+≡
  function process_def_list_get_num_id (list, id) result (num_id)
    integer :: num_id
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(process_def_entry_t), pointer :: current
    current => list%first
    do while (associated (current))
      if (id == current%id) then
        num_id = current%num_id
        return
      end if
      current => current%next
    end do
    num_id = 0
  end function process_def_list_get_num_id

```

Return the model name for a given process in the library.

```

(Process libraries: process def list: TBP)+≡
  procedure :: get_model_name => process_def_list_get_model_name

(Process libraries: procedures)+≡
  function process_def_list_get_model_name (list, id) result (model_name)
    type(string_t) :: model_name
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(process_def_entry_t), pointer :: current
    current => list%first
    do while (associated (current))
      if (id == current%id) then
        model_name = current%model_name
        return
      end if
      current => current%next
    end do
    model_name = ""
  end function process_def_list_get_model_name

```

Return the number of incoming particles of a given process in the library. This tells us whether the process is a decay or a scattering.

```

(Process libraries: process def list: TBP)+≡
  procedure :: get_n_in => process_def_list_get_n_in

(Process libraries: procedures)+≡
  function process_def_list_get_n_in (list, id) result (n)
    integer :: n
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(process_def_entry_t), pointer :: current
    current => list%first

```

```

do while (associated (current))
  if (id == current%id) then
    n = current%n_in
    return
  end if
  current => current%next
end do
end function process_def_list_get_n_in

```

Return the number of components of a given process in the library.

```

<Process libraries: process def list: TBP>+≡
  procedure :: get_n_components => process_def_list_get_n_components

<Process libraries: procedures>+≡
  function process_def_list_get_n_components (list, id) result (n)
    integer :: n
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(process_def_entry_t), pointer :: current
    current => list%first
    do while (associated (current))
      if (id == current%id) then
        n = current%n_initial + current%n_extra
        return
      end if
      current => current%next
    end do
  end function process_def_list_get_n_components

```

Return a pointer to a specific process component definition.

```

<Process libraries: process def list: TBP>+≡
  procedure :: get_component_def_ptr => process_def_list_get_component_def_ptr

<Process libraries: procedures>+≡
  function process_def_list_get_component_def_ptr (list, id, i) result (ptr)
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    integer, intent(in) :: i
    type(process_component_def_t), pointer :: ptr
    type(process_def_entry_t), pointer :: current
    ptr => null ()
    current => list%first
    do while (associated (current))
      if (id == current%id) then
        if (i <= current%n_initial) then
          ptr => current%initial(i)
        else if (i <= current%n_initial + current%n_extra) then
          ptr => current%extra(i-current%n_initial)
        end if
        return
      end if
      current => current%next
    end do
  end function process_def_list_get_component_def_ptr

```

Return the list of component IDs of a given process in the library.

```

(Process libraries: process def list: TBP)+≡
  procedure :: get_component_list => process_def_list_get_component_list

(Process libraries: procedures)+≡
  subroutine process_def_list_get_component_list (list, id, cid)
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(string_t), dimension(:), allocatable, intent(out) :: cid
    type(process_def_entry_t), pointer :: current
    integer :: i, n
    current => list%first
    do while (associated (current))
      if (id == current%id) then
        allocate (cid (current%n_initial + current%n_extra))
        do i = 1, current%n_initial
          cid(i) = current%initial(i)%basename
        end do
        n = current%n_initial
        do i = 1, current%n_extra
          cid(n + i) = current%extra(i)%basename
        end do
        return
      end if
      current => current%next
    end do
  end subroutine process_def_list_get_component_list

```

Return the list of component description strings for a given process in the library.

```

(Process libraries: process def list: TBP)+≡
  procedure :: get_component_description_list => &
    process_def_list_get_component_description_list

(Process libraries: procedures)+≡
  subroutine process_def_list_get_component_description_list &
    (list, id, description)
    class(process_def_list_t), intent(in) :: list
    type(string_t), intent(in) :: id
    type(string_t), dimension(:), allocatable, intent(out) :: description
    type(process_def_entry_t), pointer :: current
    integer :: i, n
    current => list%first
    do while (associated (current))
      if (id == current%id) then
        allocate (description (current%n_initial + current%n_extra))
        do i = 1, current%n_initial
          description(i) = current%initial(i)%description
        end do
        n = current%n_initial
        do i = 1, current%n_extra
          description(n + i) = current%extra(i)%description
        end do
        return
      end if
      current => current%next
    end do
  end subroutine process_def_list_get_component_description_list

```

```

        end if
        current => current%next
    end do
end subroutine process_def_list_get_component_description_list

```

Return whether the entry corresponds to an NLO-process

```

<Process libraries: process def list: TBP>+≡
    procedure :: get_nlo_process => process_def_list_get_nlo_process

<Process libraries: procedures>+≡
    function process_def_list_get_nlo_process (list, id) result (nlo)
        class(process_def_list_t), intent(in) :: list
        type(string_t), intent(in) :: id
        logical :: nlo
        type(process_def_entry_t), pointer :: current
        current => list%first
        do while (associated (current))
            if (id == current%id) then
                nlo = current%nlo_process
                return
            end if
            current => current%next
        end do
    end function process_def_list_get_nlo_process

```

13.4.3 Process library

The process library object is the interface between the process definition data, as provided by the user, generated or linked process code on file, and the process run data that reference the process code.

Process library entry

For each process component that is part of the library, there is a separate library entry (**process_library_entry_t**). The library entry connects a process definition with the specific code (if any) in the compiled driver library.

The **status** indicates how far the process has been processed by the system (definition, code generation, compilation, linking). A process with status **STAT_LOADED** is accessible for computing matrix elements.

The **def** pointer identifies the corresponding process definition. The process component within that definition is identified by the **i_component** index.

The **i_external** index refers to the compiled library driver. If it is zero, there is no associated matrix-element code.

The **driver** component holds the pointers to the matrix-element specific functions, in particular the matrix element function itself.

```

<Process libraries: types>+≡
    type :: process_library_entry_t
        private
        integer :: status = STAT_UNKNOWN
        type(process_def_t), pointer :: def => null ()
        integer :: i_component = 0

```

```

integer :: i_external = 0
class(prc_core_driver_t), allocatable :: driver
contains
  <Process libraries: process library entry: TBP>
end type process_library_entry_t

```

Here are the available status codes. An entry starts with UNKNOWN status. Once the association with a valid process definition is established, the status becomes CONFIGURED. If matrix element source code is to be generated by the system or provided from elsewhere, CODE_GENERATED indicates that this is done. The COMPILED status is next, it also applies to processes which are accessed as pre-compiled binaries. Finally, the library is linked and process pointers are set; this is marked as LOADED.

For a process library, the initial status is OPEN, since process definitions may be added. After configuration, the process content is fixed and the status becomes CONFIGURED. The further states are as above, always referring to the lowest status among the process entries.

```

<Process libraries: parameters>≡
integer, parameter :: STAT_UNKNOWN = 0
integer, parameter :: STAT_OPEN = 1
integer, parameter :: STAT_CONFIGURED = 2
integer, parameter :: STAT_SOURCE = 3
integer, parameter :: STAT_COMPILED = 4
integer, parameter :: STAT_LINKED = 5
integer, parameter :: STAT_ACTIVE = 6

```

These are the associated code letters, for output:

```

<Process libraries: parameters>+≡
character, dimension(0:6), parameter :: STATUS_LETTER = &
  ["?", "o", "f", "s", "c", "l", "a"]

```

This produces a condensed account of the library entry. The status is indicated by a letter in brackets, then the ID and component index of the associated process definition, finally the library index, if available.

```

<Process libraries: process library entry: TBP>≡
procedure :: to_string => process_library_entry_to_string

<Procedures: procedures>+≡
function process_library_entry_to_string (object) result (string)
  type(string_t) :: string
  class(process_library_entry_t), intent(in) :: object
  character(32) :: buffer
  string = "[" // STATUS_LETTER(object%status) // "]"
  select case (object%status)
  case (STAT_UNKNOWN)
  case default
    if (associated (object%def)) then
      write (buffer, "(IO)") object%i_component
      string = string // " " // object%def%id // "." // trim (buffer)
    end if
    if (object%i_external /= 0) then
      write (buffer, "(IO)") object%i_external

```

```

        string = string // " = ext:" // trim (buffer)
    else
        string = string // " = int"
    end if
    if (allocated (object%driver)) then
        string = string // " (" // object%driver%type_name () // ")"
    end if
end select
end function process_library_entry_to_string

```

Initialize with data. Used for the unit tests.

```

<Process libraries: process library entry: TBP>+≡
    procedure :: init => process_library_entry_init

<Process libraries: procedures>+≡
    subroutine process_library_entry_init (object, &
        status, def, i_component, i_external)
        class(process_library_entry_t), intent(out) :: object
        integer, intent(in) :: status
        type(process_def_t), target, intent(in) :: def
        integer, intent(in) :: i_component
        integer, intent(in) :: i_external
        object%status = status
        object%def => def
        object%i_component = i_component
        object%i_external = i_external
    end subroutine process_library_entry_init

```

Assign pointers for all process-specific features. We have to combine the method from the `core_def` specification, the assigned pointers within the library driver, the index within that driver, and the process driver which should receive the links.

```

<Process libraries: process library entry: TBP>+≡
    procedure :: connect => process_library_entry_connect

<Process libraries: procedures>+≡
    subroutine process_library_entry_connect (entry, lib_driver, i)
        class(process_library_entry_t), intent(inout) :: entry
        class(prclib_driver_t), intent(in) :: lib_driver
        integer, intent(in) :: i
        call entry%def%initial(entry%i_component)%connect &
            (lib_driver, i, entry%driver)
    end subroutine process_library_entry_connect

```

The process library object

The `process_library_t` type is an extension of the `process_def_list_t` type. Thus, it automatically contains the process definition list.

The `basename` identifies the library generically.

The `external` flag is true if any process within the library needs external code, so the library must correspond to an actual code library (statically or dynamically linked).

The **entry** array contains all process components that can be handled by this library. Each entry refers to the process (component) definition and to the associated external matrix element code, if there is any.

The **driver** object is needed only if **external** is true. This object handles all interactions with external matrix-element code.

The **md5sum** summarizes the complete **process_def_list_t** base object. It can be used to check if the library configuration has changed.

```

(Process libraries: public)+≡
    public :: process_library_t

(Process libraries: types)+≡
    type, extends (process_def_list_t) :: process_library_t
        private
            type(string_t) :: basename
            integer :: n_entries = 0
            logical :: external = .false.
            integer :: status = STAT_UNKNOWN
            logical :: static = .false.
            logical :: driver_exists = .false.
            logical :: makefile_exists = .false.
            type(process_library_entry_t), dimension(:), allocatable :: entry
            class(prclib_driver_t), allocatable :: driver
            character(32) :: md5sum = ""
        contains
            (Process libraries: process library: TBP)
        end type process_library_t

```

For the output, we write first the metadata and the DL access record, then the library entries in short form, and finally the process definition list which is the base object.

Don't write the MD5 sum since this is used to generate it.

```

(Process libraries: process library: TBP)≡
    procedure :: write => process_library_write

(Process libraries: procedures)+≡
    subroutine process_library_write (object, unit, libpath)
        class(process_library_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: libpath
        integer :: i, u
        u = given_output_unit (unit)
        write (u, "(1x,A,A)") "Process library: ", char (object%basename)
        write (u, "(3x,A,L1)") "external      = ", object%external
        write (u, "(3x,A,L1)") "makefile exists = ", object%makefile_exists
        write (u, "(3x,A,L1)") "driver exists  = ", object%driver_exists
        write (u, "(3x,A,A1)") "code status    = ", &
            STATUS_LETTER (object%status)
        write (u, *)
        if (allocated (object%entry)) then
            write (u, "(1x,A)", advance="no") "Process library entries:"
            write (u, "(1x,I0)") object%n_entries
            do i = 1, size (object%entry)
                write (u, "(1x,A,I0,A,A)") "Entry #", i, ": ", &

```



```

        char (object%entry(i)%to_string ())
    end do
    write (u, *)
end if
if (object%external) then
    call object%driver%write (u, libpath)
    write (u, *)
end if
call object%process_def_list_t%write (u)
end subroutine process_library_write

```

Condensed version for screen output.

```

<Process libraries: process library: TBP>+≡
    procedure :: show => process_library_show

<Process libraries: procedures>+≡
    subroutine process_library_show (object, unit)
        class(process_library_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(A,A)") "Process library: ", char (object%basename)
        write (u, "(2x,A,L1)") "external      = ", object%external
        if (object%static) then
            write (u, "(2x,A,L1)") "static      = ", .true.
        else
            write (u, "(2x,A,L1)") "makefile exists = ", object%makefile_exists
            write (u, "(2x,A,L1)") "driver exists  = ", object%driver_exists
        end if
        write (u, "(2x,A,A1)", advance="no") "code status    = "
        select case (object%status)
        case (STAT_UNKNOWN);   write (u, "(A)") "[unknown]"
        case (STAT_OPEN);      write (u, "(A)") "open"
        case (STAT_CONFIGURED); write (u, "(A)") "configured"
        case (STAT_SOURCE);    write (u, "(A)") "source code exists"
        case (STAT_COMPILED);  write (u, "(A)") "compiled"
        case (STAT_LINKED);    write (u, "(A)") "linked"
        case (STAT_ACTIVE);    write (u, "(A)") "active"
        end select
        call object%process_def_list_t%show (u)
    end subroutine process_library_show

```

The initializer defines just the basename. We may now add process definitions to the library.

```

<Process libraries: process library: TBP>+≡
    procedure :: init => process_library_init

<Process libraries: procedures>+≡
    subroutine process_library_init (lib, basename)
        class(process_library_t), intent(out) :: lib
        type(string_t), intent(in) :: basename
        lib%basename = basename
        lib%status = STAT_OPEN
        call msg_message ("Process library '" // char (basename) &

```

```

        // "': initialized")
    end subroutine process_library_init

```

This alternative initializer declares the library as static. We should now add process definitions to the library, but all external process code exists already. We need the driver object, and we should check the defined processes against the stored ones.

```

<Process libraries: process library: TBP>+≡
    procedure :: init_static => process_library_init_static

<Process libraries: procedures>+≡
    subroutine process_library_init_static (lib, basename)
        class(process_library_t), intent(out) :: lib
        type(string_t), intent(in) :: basename
        lib%basename = basename
        lib%status = STAT_OPEN
        lib%static = .true.
        call msg_message ("Static process library '" // char (basename) &
            // "': initialized")
    end subroutine process_library_init_static

```

The `configure` procedure scans the allocated entries in the process definition list. The configuration proceeds in three passes.

In the first pass, we scan the process definition list and count the number of process components and the number of components which need external code. This is used to allocate the `entry` array.

In the second pass, we initialize the `entry` elements which connect process definitions, process driver objects, and external code.

In the third pass, we initialize the library driver object, allocating an entry for each external matrix element.

NOTE: Currently we handle only `initial` process components; `extra` components are ignored.

```

<Process libraries: process library: TBP>+≡
    procedure :: configure => process_library_configure

<Process libraries: procedures>+≡
    subroutine process_library_configure (lib, os_data)
        class(process_library_t), intent(inout) :: lib
        type(os_data_t), intent(in) :: os_data
        type(process_def_entry_t), pointer :: def_entry
        integer :: n_entries, n_external, i_entry, i_external
        type(string_t) :: model_name
        integer :: i_component

        n_entries = 0
        n_external = 0
        if (allocated (lib%entry)) deallocate (lib%entry)

        def_entry => lib%first
        do while (associated (def_entry))
            do i_component = 1, def_entry%n_initial
                n_entries = n_entries + 1
                if (def_entry%initial(i_component)%needs_code ()) then

```

```

        n_external = n_external + 1
        lib%external = .true.
    end if
end do
def_entry => def_entry%next
end do
lib%n_entries = n_entries

allocate (lib%entry (n_entries))
i_entry = 0
i_external = 0
def_entry => lib%first
do while (associated (def_entry))
    do i_component = 1, def_entry%n_initial
        i_entry = i_entry + 1
        associate (lib_entry => lib%entry(i_entry))
            lib_entry%status = STAT_CONFIGURED
            lib_entry%def => def_entry%process_def_t
            lib_entry%i_component = i_component
            if (def_entry%initial(i_component)%needs_code ()) then
                i_external = i_external + 1
                lib_entry%i_external = i_external
            end if
            call def_entry%initial(i_component)%allocate_driver &
                (lib_entry%driver)
        end associate
    end do
    def_entry => def_entry%next
end do

call dispatch_prclib_driver (lib%driver, &
    lib%basename, lib%get_modellibs_ldflags (os_data))
call lib%driver%init (n_external)
do i_entry = 1, n_entries
    associate (lib_entry => lib%entry(i_entry))
        i_component = lib_entry%i_component
        model_name = lib_entry%def%model_name
        associate (def => lib_entry%def%initial(i_component))
            if (def%needs_code ()) then
                call lib%driver%set_record (lib_entry%i_external, &
                    def%basename, &
                    model_name, &
                    def%get_features (), def%get_writer_ptr ())
            end if
        end associate
    end associate
end do

if (lib%static) then
    if (lib%n_entries /= 0) lib%entry%status = STAT_LINKED
    lib%status = STAT_LINKED
else if (lib%external) then
    where (lib%entry%i_external == 0) lib%entry%status = STAT_LINKED
    lib%status = STAT_CONFIGURED

```

```

        lib%makefile_exists = .false.
        lib%driver_exists = .false.
    else
        if (lib%n_entries /= 0) lib%entry%status = STAT_LINKED
        lib%status = STAT_LINKED
    end if
end subroutine process_library_configure

```

Compute the MD5 sum. We concatenate the individual MD5 sums of all processes (which, in turn, are derived from the MD5 sums of their components) and compute the MD5 sum of that.

This should be executed *after* configuration, where the driver was initialized, since otherwise the MD5 sum stored in the driver would be overwritten.

```

(Process libraries: process library: TBP)+≡
    procedure :: compute_md5sum => process_library_compute_md5sum

(Process libraries: procedures)+≡
    subroutine process_library_compute_md5sum (lib, model)
        class(process_library_t), intent(inout) :: lib
        class(model_data_t), intent(in), optional, target :: model
        type(process_def_entry_t), pointer :: def_entry
        type(string_t) :: buffer
        buffer = lib%basename
        def_entry => lib%first
        do while (associated (def_entry))
            call def_entry%compute_md5sum (model)
            buffer = buffer // def_entry%md5sum
            def_entry => def_entry%next
        end do
        lib%md5sum = md5sum (char (buffer))
        call lib%driver%set_md5sum (lib%md5sum)
    end subroutine process_library_compute_md5sum

```

Write an appropriate makefile, if there are external processes. Unless **force** is in effect, first check if there is already a makefile with the correct MD5 sum. If yes, do nothing.

```

(Process libraries: process library: TBP)+≡
    procedure :: write_makefile => process_library_write_makefile

(Process libraries: procedures)+≡
    subroutine process_library_write_makefile (lib, os_data, force, testflag)
        class(process_library_t), intent(inout) :: lib
        type(os_data_t), intent(in) :: os_data
        logical, intent(in) :: force
        logical, intent(in), optional :: testflag
        character(32) :: md5sum_file
        logical :: generate
        integer :: unit
        if (lib%external .and. .not. lib%static) then
            generate = .true.
            if (.not. force) then
                md5sum_file = lib%driver%get_md5sum_makefile ()
                if (lib%md5sum == md5sum_file) then

```

```

        call msg_message ("Process library '" // char (lib%basename) &
            // "': keeping makefile")
        generate = .false.
    end if
end if
if (generate) then
    call msg_message ("Process library '" // char (lib%basename) &
        // "': writing makefile")
    unit = free_unit ()
    open (unit, file = char (lib%driver%basename // ".makefile"), &
        status="replace", action="write")
    call lib%driver%generate_makefile (unit, os_data, testflag)
    close (unit)
end if
lib%makefile_exists = .true.
end if
end subroutine process_library_write_makefile

```

Write the driver source code for the library to file, if there are external processes.

```

<Process libraries: process library: TBP>+≡
    procedure :: write_driver => process_library_write_driver

<Process libraries: procedures>+≡
    subroutine process_library_write_driver (lib, force)
        class(process_library_t), intent(inout) :: lib
        logical, intent(in) :: force
        character(32) :: md5sum_file
        logical :: generate
        integer :: unit
        if (lib%external .and. .not. lib%static) then
            generate = .true.
            if (.not. force) then
                md5sum_file = lib%driver%get_md5sum_driver ()
                if (lib%md5sum == md5sum_file) then
                    call msg_message ("Process library '" // char (lib%basename) &
                        // "': keeping driver")
                    generate = .false.
                end if
            end if
            if (generate) then
                call msg_message ("Process library '" // char (lib%basename) &
                    // "': writing driver")
                unit = free_unit ()
                open (unit, file = char (lib%driver%basename // ".f90"), &
                    status="replace", action="write")
                call lib%driver%generate_driver_code (unit)
                close (unit)
            end if
            lib%driver_exists = .true.
        end if
    end subroutine process_library_write_driver

```

Update the compilation status of an external library.

Strictly speaking, this is not necessary for a one-time run, since the individual library methods will update the status themselves. However, it allows us to identify compilation steps that we can skip because the file exists or is already loaded, for the whole library or for particular entries.

Independently, the building process is controlled by a makefile. Thus, previous files are reused if they are not modified by the current compilation.

1. If it is not already loaded, attempt to load the library. If successful, check the overall MD5 sum. If it matches, just keep it loaded and mark as ACTIVE. If not, check the MD5 sum for all linked process components. Where it matches, mark the entry as COMPILED. Then, unload the library and mark as CONFIGURED.

Thus, we can identify compiled files for all matrix elements which are accessible via the previous compiled library, even if it is no longer up to date.

2. If the library is now in CONFIGURED state, look for valid source files. Each entry that is just in CONFIGURED state will advance to SOURCE if the MD5 sum matches. Finally, advance the whole library to SOURCE if all entries are at least in this condition.

```

(Process libraries: process library: TBP)+≡
  procedure :: update_status => process_library_update_status

(Process libraries: procedures)+≡
  subroutine process_library_update_status (lib, os_data)
    class(process_library_t), intent(inout) :: lib
    type(os_data_t), intent(in) :: os_data
    character(32) :: md5sum_file
    integer :: i, i_external, i_component
    if (lib%external) then
      select case (lib%status)
      case (STAT_CONFIGURED:STAT_LINKED)
        call lib%driver%load (os_data, noerror=.true.)
      end select
    if (lib%driver%loaded) then
      md5sum_file = lib%driver%get_md5sum (0)
      if (lib%md5sum == md5sum_file) then
        call lib%load_entries ()
        lib%entry%status = STAT_ACTIVE
        lib%status = STAT_ACTIVE
        call msg_message ("Process library '" // char (lib%basename) &
          // "': active")
      else
        do i = 1, lib%n_entries
          associate (entry => lib%entry(i))
            i_external = entry%i_external
            i_component = entry%i_component
            if (i_external /= 0) then
              md5sum_file = lib%driver%get_md5sum (i_external)
              if (entry%def%get_md5sum (i_component) == md5sum_file) then
                entry%status = STAT_COMPILED
              else
                entry%status = STAT_CONFIGURED
              end if
            end if
          end associate
        end do
      end if
    end if
  end subroutine

```

```

        end if
    end if
    end associate
end do
call lib%driver%unload ()
lib%status = STAT_CONFIGURED
end if
end if
select case (lib%status)
case (STAT_CONFIGURED)
do i = 1, lib%n_entries
associate (entry => lib%entry(i))
i_external = entry%i_external
i_component = entry%i_component
if (i_external /= 0) then
select case (entry%status)
case (STAT_CONFIGURED)
md5sum_file = lib%driver%get_md5sum_source (i_external)
if (entry%def%get_md5sum (i_component) == md5sum_file) then
entry%status = STAT_SOURCE
end if
end select
end if
end associate
end do
if (all (lib%entry%status >= STAT_SOURCE)) then
md5sum_file = lib%driver%get_md5sum_driver ()
if (lib%md5sum == md5sum_file) then
lib%status = STAT_SOURCE
end if
end if
end select
end if
end subroutine process_library_update_status

```

This procedure triggers code generation for all processes where this is possible.

We generate code only for external processes of status `STAT_CONFIGURED`, which then advance to `STAT_SOURCE`. If, for a particular process, the status is already advanced, we do not remove previous files, so `make` will consider them as up to date if they exist. Otherwise, we remove those files to force a fresh `make`.

Finally, if any source code has been generated, we need a driver file.

(Process libraries: process library: TBP)+≡

```

procedure :: make_source => process_library_make_source

```

(Process libraries: procedures)+≡

```

subroutine process_library_make_source (lib, os_data, keep_old_source)
class(process_library_t), intent(inout) :: lib
type(os_data_t), intent(in) :: os_data
logical, intent(in), optional :: keep_old_source
logical :: keep_old
integer :: i, i_external
keep_old = .false.

```

```

if (present (keep_old_source)) keep_old = keep_old_source
if (lib%external .and. .not. lib%static) then
  select case (lib%status)
  case (STAT_CONFIGURED)
    if (keep_old) then
      call msg_message ("Process library '" // char (lib%basename) &
        // "' : keeping source code")
    else
      call msg_message ("Process library '" // char (lib%basename) &
        // "' : creating source code")
    do i = 1, size (lib%entry)
      associate (entry => lib%entry(i))
        i_external = entry%i_external
        if (i_external /= 0 &
          .and. lib%entry(i)%status == STAT_CONFIGURED) then
          call lib%driver%clean_proc (i_external, os_data)
        end if
      end associate
    end do
    call lib%driver%make_source (os_data)
  end if
  lib%status = STAT_SOURCE
  where (lib%entry%i_external /= 0 &
    .and. lib%entry%status == STAT_CONFIGURED)
    lib%entry%status = STAT_SOURCE
  end where
  lib%status = STAT_SOURCE
end select
end if
end subroutine process_library_make_source

```

Compile the generated code and update the status codes. Try to make the sources first, just in case. This includes compiling possible L^AT_EX Feynman diagram files.

(Process libraries: process library: TBP)+≡

```

procedure :: make_compile => process_library_make_compile

```

(Process libraries: procedures)+≡

```

subroutine process_library_make_compile (lib, os_data, keep_old_source)
  class(process_library_t), intent(inout) :: lib
  type(os_data_t), intent(in) :: os_data
  logical, intent(in), optional :: keep_old_source
  if (lib%external .and. .not. lib%static) then
    select case (lib%status)
    case (STAT_CONFIGURED)
      call lib%make_source (os_data, keep_old_source)
    end select
  if (signal_is_pending ()) return
  select case (lib%status)
  case (STAT_SOURCE)
    call msg_message ("Process library '" // char (lib%basename) &
      // "' : compiling sources")
    call lib%driver%make_compile (os_data)
  end case
end subroutine

```



```

        where (lib%entry%i_external /= 0 &
              .and. lib%entry%status == STAT_SOURCE)
              lib%entry%status = STAT_COMPILED
        end where
        lib%status = STAT_COMPILED
    end select
end if
end subroutine process_library_make_compile

```

Link the process library. Try to compile first, just in case.

```

<Process libraries: process library: TBP>+≡
    procedure :: make_link => process_library_make_link

<Process libraries: procedures>+≡
    subroutine process_library_make_link (lib, os_data, keep_old_source)
    class(process_library_t), intent(inout) :: lib
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: keep_old_source
    if (lib%external .and. .not. lib%static) then
        select case (lib%status)
        case (STAT_CONFIGURED:STAT_SOURCE)
            call lib%make_compile (os_data, keep_old_source)
        end select
        if (signal_is_pending ()) return
        select case (lib%status)
        case (STAT_COMPILED)
            call msg_message ("Process library '" // char (lib%basename) &
                             // "': linking")
            call lib%driver%make_link (os_data)
            lib%entry%status = STAT_LINKED
            lib%status = STAT_LINKED
        end select
    end if
end subroutine process_library_make_link

```

Load the process library, i.e., assign pointers to the library functions.

```

<Process libraries: process library: TBP>+≡
    procedure :: load => process_library_load

<Process libraries: procedures>+≡
    subroutine process_library_load (lib, os_data, keep_old_source)
    class(process_library_t), intent(inout) :: lib
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: keep_old_source
    select case (lib%status)
    case (STAT_CONFIGURED:STAT_COMPILED)
        call lib%make_link (os_data, keep_old_source)
    end select
    if (signal_is_pending ()) return
    select case (lib%status)
    case (STAT_LINKED)
        if (lib%external) then
            call msg_message ("Process library '" // char (lib%basename) &
                             // "': loading")
        end if
    end case
end subroutine process_library_load

```

```

        call lib%driver%load (os_data)
        call lib%load_entries ()
    end if
    lib%entry%status = STAT_ACTIVE
    lib%status = STAT_ACTIVE
end select
end subroutine process_library_load

```

This is the actual loading part for the process methods.

```

(Process libraries: process library: TBP)+≡
    procedure :: load_entries => process_library_load_entries

(Process libraries: procedures)+≡
    subroutine process_library_load_entries (lib)
        class(process_library_t), intent(inout) :: lib
        integer :: i
        do i = 1, size (lib%entry)
            associate (entry => lib%entry(i))
                if (entry%i_external /= 0) then
                    call entry%connect (lib%driver, entry%i_external)
                end if
            end associate
        end do
    end subroutine process_library_load_entries

```

Unload the library, if possible. This reverts the status to “linked”.

```

(Process libraries: process library: TBP)+≡
    procedure :: unload => process_library_unload

(Process libraries: procedures)+≡
    subroutine process_library_unload (lib)
        class(process_library_t), intent(inout) :: lib
        select case (lib%status)
        case (STAT_ACTIVE)
            if (lib%external) then
                call msg_message ("Process library '" // char (lib%basename) &
                    // "': unloading")
                call lib%driver%unload ()
            end if
            lib%entry%status = STAT_LINKED
            lib%status = STAT_LINKED
        end select
    end subroutine process_library_unload

```

Unload, clean all generated files and revert the library status. If distclean is set, also remove the makefile and the driver source.

```

(Process libraries: process library: TBP)+≡
    procedure :: clean => process_library_clean

(Process libraries: procedures)+≡
    subroutine process_library_clean (lib, os_data, distclean)
        class(process_library_t), intent(inout) :: lib
        type(os_data_t), intent(in) :: os_data

```

```

logical, intent(in) :: distclean
call lib%unload ()
if (lib%external .and. .not. lib%static) then
  call msg_message ("Process library '" // char (lib%basename) &
    // "': removing old files")
  if (distclean) then
    call lib%driver%distclean (os_data)
  else
    call lib%driver%clean (os_data)
  end if
end if
where (lib%entry%i_external /= 0)
  lib%entry%status = STAT_CONFIGURED
elsewhere
  lib%entry%status = STAT_LINKED
end where
if (lib%external) then
  lib%status = STAT_CONFIGURED
else
  lib%status = STAT_LINKED
end if
end subroutine process_library_clean

```

Unload and clean the compiled library and all generated object files, so force a recompilation.

<XXX Process libraries: process library: TBP>≡

```

  procedure :: clean_objects => process_library_clean_objects

```

<XXX Process libraries: procedures>≡

```

subroutine process_library_clean_objects (lib, os_data)
  class(process_library_t), intent(inout) :: lib
  type(os_data_t), intent(in) :: os_data
  call lib%unload ()
  if (lib%external .and. .not. lib%static) then
    call msg_message ("Process library '" // char (lib%basename) &
      // "': removing compiled objects")
    call lib%driver%clean_library (os_data)
    call lib%driver%clean_objects (os_data)
  end if
  where (lib%entry%i_external /= 0)
    lib%entry%status = STAT_CONFIGURED
  elsewhere
    lib%entry%status = STAT_LINKED
  end where
  if (lib%external) then
    lib%status = STAT_CONFIGURED
  else
    lib%status = STAT_LINKED
  end if
end subroutine process_library_clean_objects

```

Unload and revert the library status to INITIAL. This allows for appending new processes. No files are deleted.

```

<Process libraries: process library: TBP>+≡
  procedure :: open => process_library_open

<Process libraries: procedures>+≡
  subroutine process_library_open (lib)
    class(process_library_t), intent(inout) :: lib
    select case (lib%status)
    case (STAT_OPEN)
    case default
      call lib%unload ()
      if (.not. lib%static) then
        lib%entry%status = STAT_OPEN
        lib%status = STAT_OPEN
        call msg_message ("Process library '" // char (lib%basename) &
          // "': open")
      else
        call msg_error ("Static process library '" // char (lib%basename) &
          // "': processes can't be appended")
      end if
    end select
  end subroutine process_library_open

```

13.4.4 Use the library

Return the base name of the library

```

<Process libraries: process library: TBP>+≡
  procedure :: get_name => process_library_get_name

<Process libraries: procedures>+≡
  function process_library_get_name (lib) result (name)
    class(process_library_t), intent(in) :: lib
    type(string_t) :: name
    name = lib%basename
  end function process_library_get_name

```

Once activated, we view the process library object as an interface for accessing the matrix elements.

```

<Process libraries: process library: TBP>+≡
  procedure :: is_active => process_library_is_active

<Process libraries: procedures>+≡
  function process_library_is_active (lib) result (flag)
    logical :: flag
    class(process_library_t), intent(in) :: lib
    flag = lib%status == STAT_ACTIVE
  end function process_library_is_active

```

Retrieve constants using the process library driver. We assume that the process code has been loaded, if external.

```

<Process libraries: process library entry: TBP>+≡
  procedure :: fill_constants => process_library_entry_fill_constants

```

(Process libraries: procedures)+≡

```

subroutine process_library_entry_fill_constants (entry, driver, data)
  class(process_library_entry_t), intent(in) :: entry
  class(prclib_driver_t), intent(in) :: driver
  type(process_constants_t), intent(out) :: data
  integer :: i
  if (entry%i_external /= 0) then
    i = entry%i_external
    data%id = driver%get_process_id (i)
    data%model_name = driver%get_model_name (i)
    data%md5sum = driver%get_md5sum (i)
    data%openmp_supported = driver%get_openmp_status (i)
    data%n_in = driver%get_n_in (i)
    data%n_out = driver%get_n_out (i)
    data%n_flv = driver%get_n_flv (i)
    data%n_hel = driver%get_n_hel (i)
    data%n_col = driver%get_n_col (i)
    data%n_cin = driver%get_n_cin (i)
    data%n_cf = driver%get_n_cf (i)
    call driver%set_flv_state (i, data%flv_state)
    call driver%set_hel_state (i, data%hel_state)
    call driver%set_col_state (i, data%col_state, data%ghost_flag)
    call driver%set_color_factors (i, data%color_factors, data%cf_index)
  else
    select type (proc_driver => entry%driver)
    class is (process_driver_internal_t)
      call proc_driver%fill_constants (data)
    end select
  end if
end subroutine process_library_entry_fill_constants

```

Retrieve the constants and a connected driver for a process, identified by a process ID and a subprocess index. We scan the process entries until we have found a match.

(Process libraries: process library: TBP)+≡

```

procedure :: connect_process => process_library_connect_process

```

(Process libraries: procedures)+≡

```

subroutine process_library_connect_process &
  (lib, id, i_component, data, proc_driver)
  class(process_library_t), intent(in) :: Lib
  type(string_t), intent(in) :: id
  integer, intent(in) :: i_component
  type(process_constants_t), intent(out) :: data
  class(prc_core_driver_t), allocatable, intent(out) :: proc_driver
  integer :: i
  do i = 1, size (lib%entry)
    associate (entry => lib%entry(i))
      if (entry%def%id == id .and. entry%i_component == i_component) then
        call entry%fill_constants (lib%driver, data)
        allocate (proc_driver, source=entry%driver)
        return
      end if
    end associate
  end do
end subroutine process_library_connect_process

```

```

end do
call msg_fatal ("Process library '" // char (lib%basename) &
               // "': process '" // char (id) // "' not found")
end subroutine process_library_connect_process

```

13.4.5 Collect model-specific libraries

This returns appropriate linker flags for the model parameter libraries that are used by the generated matrix element. At the end, the main libwhizard is appended (again), because functions from that may be required.

Extra models in the local user space need to be treated individually.

```

(Process libraries: process library: TBP)+≡
  procedure :: get_modellibs_ldflags => process_library_get_modellibs_ldflags

(Process libraries: procedures)+≡
  function process_library_get_modellibs_ldflags (prc_lib, os_data) result (flags)
    class(process_library_t), intent(in) :: prc_lib
    type(os_data_t), intent(in) :: os_data
    type(string_t) :: flags
    type(string_t), dimension(:), allocatable :: models
    type(string_t) :: modelname, modellib, modellib_full
    logical :: exist
    integer :: i, j, mi
    flags = "-lomega"
    if ((.not. os_data%use_testfiles) .and. &
        os_dir_exist (os_data%whizard_models_libpath_local)) &
        flags = flags // " -L" // os_data%whizard_models_libpath_local
    flags = flags // " -L" // os_data%whizard_models_libpath
    allocate(models(prc_lib%n_entries + 1))
    models = ""
    mi = 1
    if (allocated (prc_lib%entry)) then
      SCAN: do i = 1, prc_lib%n_entries
        if (associated (prc_lib%entry(i)%def)) then
          if (prc_lib%entry(i)%def%model_name /= "") then
            modelname = prc_lib%entry(i)%def%model_name
          else
            cycle SCAN
          end if
        else
          cycle SCAN
        end if
      do j = 1, mi
        if (models(mi) == modelname) cycle SCAN
      end do
      models(mi) = modelname
      mi = mi + 1
    if (os_data%use_libtool) then
      modellib = "libparameters_" // modelname // ".la"
    else
      modellib = "libparameters_" // modelname // ".a"
    end if
    exist = .false.
  end function

```

```

        if (.not. os_data%use_testfiles) then
            modellib_full = os_data%whizard_models_libpath_local &
                // "/" // modellib
            inquire (file=char (modellib_full), exist=exist)
        end if
        if (.not. exist) then
            modellib_full = os_data%whizard_models_libpath &
                // "/" // modellib
            inquire (file=char (modellib_full), exist=exist)
        end if
        if (exist) flags = flags // " -lparameters_" // modelname
    end do SCAN
end if
deallocate (models)
flags = flags // " -lwhizard"
end function process_library_get_modellibs_ldflags

```

(Process libraries: process library: TBP)+≡

```

    procedure :: get_static_modelname => process_library_get_static_modelname

```

(Process libraries: procedures)+≡

```

function process_library_get_static_modelname (prc_lib, os_data) result (name)
    class(process_library_t), intent(in) :: prc_lib
    type(os_data_t), intent(in) :: os_data
    type(string_t) :: name
    type(string_t), dimension(:), allocatable :: models
    type(string_t) :: modelname, modellib, modellib_full
    logical :: exist
    integer :: i, j, mi
    name = ""
    allocate (models(prc_lib%n_entries + 1))
    models = ""
    mi = 1
    if (allocated (prc_lib%entry)) then
        SCAN: do i = 1, prc_lib%n_entries
            if (associated (prc_lib%entry(i)%def)) then
                if (prc_lib%entry(i)%def%model_name /= "") then
                    modelname = prc_lib%entry(i)%def%model_name
                else
                    cycle SCAN
                end if
            else
                cycle SCAN
            end if
            do j = 1, mi
                if (models(mi) == modelname) cycle SCAN
            end do
            models(mi) = modelname
            mi = mi + 1
            modellib = "libparameters_" // modelname // ".a"
            exist = .false.
        end do
        if (.not. os_data%use_testfiles) then
            modellib_full = os_data%whizard_models_libpath_local &
                // "/" // modellib
        end if
    end if
end function process_library_get_static_modelname

```

```

        inquire (file=char (modellib_full), exist=exist)
    end if
    if (.not. exist) then
        modellib_full = os_data%whizard_models_libpath &
            // "/" // modellib
        inquire (file=char (modellib_full), exist=exist)
    end if
    if (exist) name = name // " " // modellib_full
end do SCAN
end if
deallocate (models)
end function process_library_get_static_modelname

```

13.4.6 Test

This is the master for calling self-test procedures.

```

<Process libraries: public>+≡
    public :: process_libraries_test

<Process libraries: tests>≡
    subroutine process_libraries_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Process libraries: execute tests>
    end subroutine process_libraries_test

```

Empty process list

Test 1: Write an empty process list.

```

<Process libraries: execute tests>≡
    call test (process_libraries_1, "process_libraries_1", &
        "empty process list", &
        u, results)

<Process libraries: tests>+≡
    subroutine process_libraries_1 (u)
        integer, intent(in) :: u
        type(process_def_list_t) :: process_def_list

        write (u, "(A)")  "* Test output: process_libraries_1"
        write (u, "(A)")  "* Purpose: Display an empty process definition list"
        write (u, "(A)")

        call process_def_list%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: process_libraries_1"
    end subroutine process_libraries_1

```


Process definition list

Test 2: Process definition list with processes and components. Construct the list, write to file, read it in again, and display. Finalize and delete the list after use.

We define a trivial 'test' type for the process variant. The test type contains just one (meaningless) data item, which is an integer.

```
<Process libraries: test declarations>≡
    type, extends (prc_core_def_t) :: prcdef_2_t
        integer :: data = 0
        logical :: file = .false.
    contains
        <Process libraries: prcdef 2: TBP>
    end type prcdef_2_t
```

The process variant is named 'test'.

```
<Process libraries: prcdef 2: TBP>≡
    procedure, nopass :: type_string => prcdef_2_type_string

<Process libraries: tests>+≡
    function prcdef_2_type_string () result (string)
        type(string_t) :: string
        string = "test"
    end function prcdef_2_type_string
```

Write the contents (the integer value).

```
<Process libraries: prcdef 2: TBP>+≡
    procedure :: write => prcdef_2_write

<Process libraries: tests>+≡
    subroutine prcdef_2_write (object, unit)
        class(prcdef_2_t), intent(in) :: object
        integer, intent(in) :: unit
        write (unit, "(3x,A,I0)") "Test data" = ", object%data"
    end subroutine prcdef_2_write
```

Recover the integer value.

```
<Process libraries: prcdef 2: TBP>+≡
    procedure :: read => prcdef_2_read

<Process libraries: tests>+≡
    subroutine prcdef_2_read (object, unit)
        class(prcdef_2_t), intent(out) :: object
        integer, intent(in) :: unit
        character(80) :: buffer
        read (unit, "(A)") buffer
        call strip_prefix (buffer)
        read (buffer, *) object%data
    end subroutine prcdef_2_read
```

No external procedures.

```
<Process libraries: prcdef 2: TBP>+≡
    procedure, nopass :: get_features => prcdef_2_get_features
```

```

<Process libraries: tests>+≡
  subroutine prcdef_2_get_features (features)
    type(string_t), dimension(:), allocatable, intent(out) :: features
    allocate (features (0))
  end subroutine prcdef_2_get_features

```

No code generated.

```

<Process libraries: prcdef 2: TBP>+≡
  procedure :: generate_code => prcdef_2_generate_code

```

```

<Process libraries: tests>+≡
  subroutine prcdef_2_generate_code (object, &
    basename, model_name, prt_in, prt_out)
    class(prcdef_2_t), intent(in) :: object
    type(string_t), intent(in) :: basename
    type(string_t), intent(in) :: model_name
    type(string_t), dimension(:), intent(in) :: prt_in
    type(string_t), dimension(:), intent(in) :: prt_out
  end subroutine prcdef_2_generate_code

```

Allocate the driver with the appropriate type.

```

<Process libraries: prcdef 2: TBP>+≡
  procedure :: allocate_driver => prcdef_2_allocate_driver

<Process libraries: tests>+≡
  subroutine prcdef_2_allocate_driver (object, driver, basename)
    class(prcdef_2_t), intent(in) :: object
    class(prc_core_driver_t), intent(out), allocatable :: driver
    type(string_t), intent(in) :: basename
    allocate (prctest_2_t :: driver)
  end subroutine prcdef_2_allocate_driver

```

Nothing to connect.

```

<Process libraries: prcdef 2: TBP>+≡
  procedure :: connect => prcdef_2_connect

<Process libraries: tests>+≡
  subroutine prcdef_2_connect (def, lib_driver, i, proc_driver)
    class(prcdef_2_t), intent(in) :: def
    class(prclib_driver_t), intent(in) :: lib_driver
    integer, intent(in) :: i
    class(prc_core_driver_t), intent(inout) :: proc_driver
  end subroutine prcdef_2_connect

```

The associated driver type.

```

<Process libraries: types>+≡
  type, extends (process_driver_internal_t) :: prctest_2_t
    contains
    <Process libraries: prctest 2: TBP>
  end type prctest_2_t

```

Return the type name.

```

(Process libraries: prctest 2: TBP)≡
  procedure, nopass :: type_name => prctest_2_type_name

(Process libraries: procedures)+≡
  function prctest_2_type_name () result (type)
    type(string_t) :: type
    type = "test"
  end function prctest_2_type_name

```

This should fill constant process data. We do not check those here, however, therefore nothing done.

```

(Process libraries: prctest 2: TBP)+≡
  procedure :: fill_constants => prctest_2_fill_constants

(Process libraries: procedures)+≡
  subroutine prctest_2_fill_constants (driver, data)
    class(prctest_2_t), intent(in) :: driver
    type(process_constants_t), intent(out) :: data
  end subroutine prctest_2_fill_constants

```

Here is the actual test.

For reading, we need a list of templates, i.e., an array containing allocated objects for all available process variants. This is the purpose of `process_core_templates`. Here, we have only a single template for the 'test' variant.

```

(Process libraries: execute tests)+≡
  call test (process_libraries_2, "process_libraries_2", &
    "process definition list", &
    u, results)

(Process libraries: tests)+≡
  subroutine process_libraries_2 (u)
    integer, intent(in) :: u
    type(prc_template_t), dimension(:), allocatable :: process_core_templates
    type(process_def_list_t) :: process_def_list
    type(process_def_entry_t), pointer :: entry => null ()
    class(prc_core_def_t), allocatable :: test_def
    integer :: scratch_unit

    write (u, "(A)")  "* Test output: process_libraries_2"
    write (u, "(A)")  "* Purpose: Construct a process definition list,"
    write (u, "(A)")  "*           write it to file and reread it"
    write (u, "(A)")  ""
    write (u, "(A)")  "* Construct a process definition list"
    write (u, "(A)")  "*   First process definition: empty"
    write (u, "(A)")  "*   Second process definition: two components"
    write (u, "(A)")  "*       First component: empty"
    write (u, "(A)")  "*       Second component: test data"
    write (u, "(A)")  "*   Third process definition:"
    write (u, "(A)")  "*       Embedded decays and polarization"
    write (u, "(A)")

    allocate (process_core_templates (1))
    allocate (prcdef_2_t :: process_core_templates(1)%core_def)

```

```

allocate (entry)
call entry%init (var_str ("first"), n_in = 0, n_components = 0)
call entry%compute_md5sum ()
call process_def_list%append (entry)

allocate (entry)
call entry%init (var_str ("second"), model_name = var_str ("Test"), &
    n_in = 1, n_components = 2)
allocate (prcdef_2_t :: test_def)
select type (test_def)
type is (prcdef_2_t); test_def%data = 42
end select
call entry%import_component (2, n_out = 2, &
    prt_in = new_prt_spec ([var_str ("a")]), &
    prt_out = new_prt_spec ([var_str ("b"), var_str ("c")]), &
    method = var_str ("test"), &
    variant = test_def)
call entry%compute_md5sum ()
call process_def_list%append (entry)

allocate (entry)
call entry%init (var_str ("third"), model_name = var_str ("Test"), &
    n_in = 2, n_components = 1)
allocate (prcdef_2_t :: test_def)
call entry%import_component (1, n_out = 3, &
    prt_in = &
        new_prt_spec ([var_str ("a"), var_str ("b")]), &
    prt_out = &
        [new_prt_spec (var_str ("c")), &
        new_prt_spec (var_str ("d"), .true.), &
        new_prt_spec (var_str ("e"), [var_str ("e_decay")])], &
    method = var_str ("test"), &
    variant = test_def)
call entry%compute_md5sum ()
call process_def_list%append (entry)
call process_def_list%write (u)

write (u, "(A)") ""
write (u, "(A)") "* Write the process definition list to (scratch) file"

scratch_unit = free_unit ()
open (unit = scratch_unit, status="scratch", action = "readwrite")
call process_def_list%write (scratch_unit)
call process_def_list%final ()

write (u, "(A)") "* Reread it"
write (u, "(A)") ""

rewind (scratch_unit)
call process_def_list%read (scratch_unit, process_core_templates)
close (scratch_unit)

call process_def_list%write (u)

```

```

call process_def_list%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_2"
end subroutine process_libraries_2

```

Process library object

Test 3: Process library object with several process definitions and library entries. Just construct the object, modify some initial content, and write the result. The modifications are mostly applied directly, so we do not test anything but the contents and the output routine.

```

<Process libraries: execute tests>+≡
call test (process_libraries_3, "process_libraries_3", &
  "recover process definition list from file", &
  u, results)

<Process libraries: tests>+≡
subroutine process_libraries_3 (u)
  integer, intent(in) :: u
  type(process_library_t) :: lib
  type(process_def_entry_t), pointer :: entry

  write (u, "(A)")  "* Test output: process_libraries_3"
  write (u, "(A)")  "* Purpose: Construct a process library object &
    &with entries"
  write (u, "(A)")  ""
  write (u, "(A)")  "* Construct and display a process library object"
  write (u, "(A)")  "*   with 5 entries"
  write (u, "(A)")  "*   associated with 3 matrix element codes"
  write (u, "(A)")  "*   corresponding to 3 process definitions"
  write (u, "(A)")  "*   with 2, 1, 1 components, respectively"
  write (u, "(A)")

  call lib%init (var_str ("testlib"))

  lib%status = STAT_ACTIVE
  lib%n_entries = 5
  allocate (lib%entry (lib%n_entries))

  allocate (entry)
  call entry%init (var_str ("test_a"), n_in = 2, n_components = 2)
  call lib%entry(3)%init (STAT_SOURCE, entry%process_def_t, 2, 2)
  allocate (prctest_2_t :: lib%entry(3)%driver)
  call lib%entry(4)%init (STAT_COMPILED, entry%process_def_t, 1, 0)
  call lib%append (entry)

  allocate (entry)
  call entry%init (var_str ("test_b"), n_in = 2, n_components = 1)
  call lib%entry(2)%init (STAT_CONFIGURED, entry%process_def_t, 1, 1)
  call lib%append (entry)

  allocate (entry)

```

```

call entry%init (var_str ("test_c"), n_in = 2, n_components = 1)
call lib%entry(5)%init (STAT_LINKED, entry%process_def_t, 1, 3)
allocate (prctest_2_t :: lib%entry(5)%driver)
call lib%append (entry)

call lib%write (u)
call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_3"
end subroutine process_libraries_3

```

Process library for test matrix element (no file)

Test 4: We proceed through the library generation and loading phases with a test matrix element type that needs no code written on file.

```

<Process libraries: execute tests>+≡
call test (process_libraries_4, "process_libraries_4", &
  "build and load internal process library", &
  u, results)

<Process libraries: tests>+≡
subroutine process_libraries_4 (u)
  integer, intent(in) :: u
  type(process_library_t) :: lib
  type(process_def_entry_t), pointer :: entry
  class(prc_core_def_t), allocatable :: core_def
  type(os_data_t) :: os_data

  write (u, "(A)")  "* Test output: process_libraries_4"
  write (u, "(A)")  "* Purpose: build a process library with an &
    &internal (pseudo) matrix element"
  write (u, "(A)")  "*           No Makefile or code should be generated"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize a process library with one entry &
    &(no external code)"
  write (u, "(A)")
  call os_data_init (os_data)
  call lib%init (var_str ("proclibs4"))

  allocate (prcdef_2_t :: core_def)

  allocate (entry)
  call entry%init (var_str ("proclibs4_a"), n_in = 1, n_components = 1)
  call entry%import_component (1, n_out = 2, variant = core_def)
  call lib%append (entry)

  write (u, "(A)")  "* Configure library"
  write (u, "(A)")
  call lib%configure (os_data)

  write (u, "(A)")  "* Compute MD5 sum"

```

```

write (u, "(A)")
call lib%compute_md5sum ()

write (u, "(A)")  "* Write makefile (no-op)"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Write driver source code (no-op)"
write (u, "(A)")
call lib%write_driver (force = .true.)

write (u, "(A)")  "* Write process source code (no-op)"
write (u, "(A)")
call lib%make_source (os_data)

write (u, "(A)")  "* Compile (no-op)"
write (u, "(A)")
call lib%make_compile (os_data)

write (u, "(A)")  "* Link (no-op)"
write (u, "(A)")
call lib%make_link (os_data)

write (u, "(A)")  "* Load (no-op)"
write (u, "(A)")
call lib%load (os_data)

call lib%write (u)
call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_4"
end subroutine process_libraries_4

```

Build workflow for test matrix element

Test 5: We write source code for a dummy process.

We define another trivial type for the process variant. The test type contains just no variable data, but produces code on file.

```

<Process libraries: test declarations>+≡
  type, extends (prc_core_def_t) :: prcdef_5_t
  contains
  <Process libraries: prcdef 5: TBP>
end type prcdef_5_t

```

The process variant is named `test_file`.

```

<Process libraries: prcdef 5: TBP>≡
  procedure, nopass :: type_string => prcdef_5_type_string

<Process libraries: tests>+≡
  function prcdef_5_type_string () result (string)
    type(string_t) :: string

```

```

        string = "test_file"
    end function prcdef_5_type_string

```

We reuse the writer `test_writer_4` from the previous module.

```

<Process libraries: prcdef 5: TBP>+≡
    procedure :: init => prcdef_5_init
<Process libraries: tests>+≡
    subroutine prcdef_5_init (object)
        class(prcdef_5_t), intent(out) :: object
        allocate (test_writer_4_t :: object%writer)
    end subroutine prcdef_5_init

```

Nothing to write.

```

<Process libraries: prcdef 5: TBP>+≡
    procedure :: write => prcdef_5_write
<Process libraries: tests>+≡
    subroutine prcdef_5_write (object, unit)
        class(prcdef_5_t), intent(in) :: object
        integer, intent(in) :: unit
    end subroutine prcdef_5_write

```

Nothing to read.

```

<Process libraries: prcdef 5: TBP>+≡
    procedure :: read => prcdef_5_read
<Process libraries: tests>+≡
    subroutine prcdef_5_read (object, unit)
        class(prcdef_5_t), intent(out) :: object
        integer, intent(in) :: unit
    end subroutine prcdef_5_read

```

Allocate the driver with the appropriate type.

```

<Process libraries: prcdef 5: TBP>+≡
    procedure :: allocate_driver => prcdef_5_allocate_driver
<Process libraries: tests>+≡
    subroutine prcdef_5_allocate_driver (object, driver, basename)
        class(prcdef_5_t), intent(in) :: object
        class(prc_core_driver_t), intent(out), allocatable :: driver
        type(string_t), intent(in) :: basename
        allocate (prctest_5_t :: driver)
    end subroutine prcdef_5_allocate_driver

```

This time we need code:

```

<Process libraries: prcdef 5: TBP>+≡
    procedure, nopass :: needs_code => prcdef_5_needs_code
<Process libraries: tests>+≡
    function prcdef_5_needs_code () result (flag)
        logical :: flag
        flag = .true.
    end function prcdef_5_needs_code

```


For the test case, we implement a single feature `proc1`.

```

<Process libraries: prcdef 5: TBP>+≡
    procedure, nopass :: get_features => prcdef_5_get_features

<Process libraries: tests>+≡
    subroutine prcdef_5_get_features (features)
        type(string_t), dimension(:), allocatable, intent(out) :: features
        allocate (features (1))
        features = [ var_str ("proc1") ]
    end subroutine prcdef_5_get_features

```

Nothing to connect.

```

<Process libraries: prcdef 5: TBP>+≡
    procedure :: connect => prcdef_5_connect

<Process libraries: tests>+≡
    subroutine prcdef_5_connect (def, lib_driver, i, proc_driver)
        class(prcdef_5_t), intent(in) :: def
        class(prclib_driver_t), intent(in) :: lib_driver
        integer, intent(in) :: i
        class(prc_core_driver_t), intent(inout) :: proc_driver
    end subroutine prcdef_5_connect

```

The driver type.

```

<Process libraries: types>+≡
    type, extends (prc_core_driver_t) :: prctest_5_t
    contains
    <Process libraries: prctest 5: TBP>
    end type prctest_5_t

```

Return the type name.

```

<Process libraries: prctest 5: TBP>≡
    procedure, nopass :: type_name => prctest_5_type_name

<Process libraries: tests>+≡
    function prctest_5_type_name () result (type)
        type(string_t) :: type
        type = "test_file"
    end function prctest_5_type_name

```

Here is the actual test:

```

<Process libraries: execute tests>+≡
    call test (process_libraries_5, "process_libraries_5", &
        "build external process library", &
        u, results)

<Process libraries: tests>+≡
    subroutine process_libraries_5 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        type(process_def_entry_t), pointer :: entry
        class(prc_core_def_t), allocatable :: core_def
        type(os_data_t) :: os_data

```

```

write (u, "(A)")  "* Test output: process_libraries_5"
write (u, "(A)")  "* Purpose: build a process library with an &
                    &external (pseudo) matrix element"
write (u, "(A)")

write (u, "(A)")  "* Initialize a process library with one entry"
write (u, "(A)")
call lib%init (var_str ("proclibs5"))
call os_data_init (os_data)

allocate (prcdef_5_t :: core_def)
select type (core_def)
type is (prcdef_5_t)
    call core_def%init ()
end select

allocate (entry)
call entry%init (var_str ("proclibs5_a"), &
    model_name = var_str ("Test_Model"), &
    n_in = 1, n_components = 1)
call entry%import_component (1, n_out = 2, &
    prt_in = new_prt_spec ([var_str ("a")]), &
    prt_out = new_prt_spec ([var_str ("b"), var_str ("c")]), &
    method = var_str ("test"), &
    variant = core_def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Compute MD5 sum"
write (u, "(A)")
call lib%compute_md5sum ()

write (u, "(A)")  "* Write makefile"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Write driver source code"
write (u, "(A)")
call lib%write_driver (force = .true.)

write (u, "(A)")  "* Write process source code"
write (u, "(A)")
call lib%make_source (os_data)

write (u, "(A)")  "* Compile"
write (u, "(A)")
call lib%make_compile (os_data)

write (u, "(A)")  "* Link"
write (u, "(A)")

```

```

call lib%make_link (os_data)

call lib%write (u, libpath = .false.)

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_5"
end subroutine process_libraries_5

```

Build and load library with test matrix element

Test 6: We write source code for a dummy process.

This process variant is identical to the previous case, but it supports a driver for the test procedure 'proc1'.

```

<Process libraries: test declarations>+≡
type, extends (prc_core_def_t) :: prcdef_6_t
contains
  <Process libraries: prcdef 6: TBP>
end type prcdef_6_t

```

The process variant is named `test_file`.

```

<Process libraries: prcdef 6: TBP>≡
procedure, nopass :: type_string => prcdef_6_type_string

<Process libraries: tests>+≡
function prcdef_6_type_string () result (string)
  type(string_t) :: string
  string = "test_file"
end function prcdef_6_type_string

```

We reuse the writer `test_writer_4` from the previous module.

```

<Process libraries: prcdef 6: TBP>+≡
procedure :: init => prcdef_6_init

<Process libraries: tests>+≡
subroutine prcdef_6_init (object)
  class(prcdef_6_t), intent(out) :: object
  allocate (test_writer_4_t :: object%writer)
  call object%writer%init_test ()
end subroutine prcdef_6_init

```

Nothing to write.

```

<Process libraries: prcdef 6: TBP>+≡
procedure :: write => prcdef_6_write

<Process libraries: tests>+≡
subroutine prcdef_6_write (object, unit)
  class(prcdef_6_t), intent(in) :: object
  integer, intent(in) :: unit
end subroutine prcdef_6_write

```

Nothing to read.

```
<Process libraries: prcdef 6: TBP>+≡  
  procedure :: read => prcdef_6_read  
  
<Process libraries: tests>+≡  
  subroutine prcdef_6_read (object, unit)  
    class(prcdef_6_t), intent(out) :: object  
    integer, intent(in) :: unit  
  end subroutine prcdef_6_read
```

Allocate the driver with the appropriate type.

```
<Process libraries: prcdef 6: TBP>+≡  
  procedure :: allocate_driver => prcdef_6_allocate_driver  
  
<Process libraries: tests>+≡  
  subroutine prcdef_6_allocate_driver (object, driver, basename)  
    class(prcdef_6_t), intent(in) :: object  
    class(prc_core_driver_t), intent(out), allocatable :: driver  
    type(string_t), intent(in) :: basename  
    allocate (prctest_6_t :: driver)  
  end subroutine prcdef_6_allocate_driver
```

This time we need code:

```
<Process libraries: prcdef 6: TBP>+≡  
  procedure, nopass :: needs_code => prcdef_6_needs_code  
  
<Process libraries: tests>+≡  
  function prcdef_6_needs_code () result (flag)  
    logical :: flag  
    flag = .true.  
  end function prcdef_6_needs_code
```

For the test case, we implement a single feature proc1.

```
<Process libraries: prcdef 6: TBP>+≡  
  procedure, nopass :: get_features => prcdef_6_get_features  
  
<Process libraries: tests>+≡  
  subroutine prcdef_6_get_features (features)  
    type(string_t), dimension(:), allocatable, intent(out) :: features  
    allocate (features (1))  
    features = [ var_str ("proc1") ]  
  end subroutine prcdef_6_get_features
```

The interface of the only specific feature.

```
<Process libraries: interfaces>≡  
  abstract interface  
    subroutine proc1_t (n) bind(C)  
      import  
      integer(c_int), intent(out) :: n  
    end subroutine proc1_t  
  end interface
```

Connect the feature `proc1` with the process driver.

```

<Process libraries: prcdef 6: TBP>+≡
  procedure :: connect => prcdef_6_connect

<Process libraries: tests>+≡
  subroutine prcdef_6_connect (def, lib_driver, i, proc_driver)
    class(prcdef_6_t), intent(in) :: def
    class(prclib_driver_t), intent(in) :: lib_driver
    integer, intent(in) :: i
    class(prc_core_driver_t), intent(inout) :: proc_driver
    integer(c_int) :: pid, fid
    type(c_funptr) :: fptr
    select type (proc_driver)
    type is (prctest_6_t)
      pid = i
      fid = 1
      call lib_driver%get_fptr (pid, fid, fptr)
      call c_f_procpointer (fptr, proc_driver%proc1)
    end select
  end subroutine prcdef_6_connect

```

The driver type.

```

<Process libraries: types>+≡
  type, extends (prc_core_driver_t) :: prctest_6_t
    procedure(proc1_t), nopass, pointer :: proc1 => null ()
    contains
    <Process libraries: prctest 6: TBP>
  end type prctest_6_t

```

Return the type name.

```

<Process libraries: prctest 6: TBP>≡
  procedure, nopass :: type_name => prctest_6_type_name

<Process libraries: tests>+≡
  function prctest_6_type_name () result (type)
    type(string_t) :: type
    type = "test_file"
  end function prctest_6_type_name

```

Here is the actual test:

```

<Process libraries: execute tests>+≡
  call test (process_libraries_6, "process_libraries_6", &
    "build and load external process library", &
    u, results)

<Process libraries: tests>+≡
  subroutine process_libraries_6 (u)
    integer, intent(in) :: u
    type(process_library_t) :: lib
    type(process_def_entry_t), pointer :: entry
    class(prc_core_def_t), allocatable :: core_def
    type(os_data_t) :: os_data
    type(string_t), dimension(:), allocatable :: name_list

```

```

type(process_constants_t) :: data
class(prc_core_driver_t), allocatable :: proc_driver
integer :: i
integer(c_int) :: n

write (u, "(A)")  "* Test output: process_libraries_6"
write (u, "(A)")  "* Purpose: build and load a process library"
write (u, "(A)")  "*           with an external (pseudo) matrix element"
write (u, "(A)")  "*           Check single-call linking"
write (u, "(A)")

write (u, "(A)")  "* Initialize a process library with one entry"
write (u, "(A)")
call lib%init (var_str ("proclibs6"))
call os_data_init (os_data)

allocate (prcdef_6_t :: core_def)
select type (core_def)
type is (prcdef_6_t)
    call core_def%init ()
end select

allocate (entry)
call entry%init (var_str ("proclibs6_a"), &
    model_name = var_str ("Test_model"), &
    n_in = 1, n_components = 1)
call entry%import_component (1, n_out = 2, &
    prt_in  = new_prt_spec ([var_str ("a")]), &
    prt_out = new_prt_spec ([var_str ("b"), var_str ("c")]), &
    method  = var_str ("test"), &
    variant = core_def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Write makefile"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Write driver source code"
write (u, "(A)")
call lib%write_driver (force = .true.)

write (u, "(A)")  "* Write process source code, compile, link, load"
write (u, "(A)")
call lib%load (os_data)

call lib%write (u, libpath = .false.)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

```

```

write (u, "(1x,A,A,A)") "name" = ', ' , &
char (lib%get_name ()), "' "
write (u, "(1x,A,L1)") "is active" = ", &
lib%is_active ()
write (u, "(1x,A,I0)") "n_processes" = ", &
lib%get_n_processes ()
write (u, "(1x,A)", advance="no") "processes" = "
call lib%get_process_id_list (name_list)
do i = 1, size (name_list)
write (u, "(1x,A)", advance="no") char (name_list(i))
end do
write (u, *)
write (u, "(1x,A,L1)") "proclibs6_a is process" = ", &
lib%contains (var_str ("proclibs6_a"))
write (u, "(1x,A,I0)") "proclibs6_a has index" = ", &
lib%get_entry_index (var_str ("proclibs6_a"))
write (u, "(1x,A,L1)") "foobar is process" = ", &
lib%contains (var_str ("foobar"))
write (u, "(1x,A,I0)") "foobar has index" = ", &
lib%get_entry_index (var_str ("foobar"))
write (u, "(1x,A,I0)") "n_in(proclibs6_a)" = ", &
lib%get_n_in (var_str ("proclibs6_a"))
write (u, "(1x,A,A)") "model_name(proclibs6_a)" = ", &
char (lib%get_model_name (var_str ("proclibs6_a")))
write (u, "(1x,A,I0)") "n_components(proclibs6_a)" = ", &
lib%get_n_components (var_str ("proclibs6_a"))
write (u, "(1x,A)", advance="no") "components(proclibs6_a)" = "
call lib%get_component_list (var_str ("proclibs6_a"), name_list)
do i = 1, size (name_list)
write (u, "(1x,A)", advance="no") char (name_list(i))
end do
write (u, *)

write (u, "(A)")
write (u, "(A)") "* Constants of proclibs6_a_i1:"
write (u, "(A)")

call lib%connect_process (var_str ("proclibs6_a"), 1, data, proc_driver)

write (u, "(1x,A,A)") "component ID" = ", char (data%id)
write (u, "(1x,A,A)") "model name" = ", char (data%model_name)
write (u, "(1x,A,A,A)") "md5sum" = ', ' , data%md5sum, "' "
write (u, "(1x,A,L1)") "openmp supported" = ", data%openmp_supported
write (u, "(1x,A,I0)") "n_in" = ", data%n_in
write (u, "(1x,A,I0)") "n_out" = ", data%n_out
write (u, "(1x,A,I0)") "n_flv" = ", data%n_flv
write (u, "(1x,A,I0)") "n_hel" = ", data%n_hel
write (u, "(1x,A,I0)") "n_col" = ", data%n_col
write (u, "(1x,A,I0)") "n_cin" = ", data%n_cin
write (u, "(1x,A,I0)") "n_cf" = ", data%n_cf
write (u, "(1x,A,10(1x,I0))") "flv state" = ", data%flv_state
write (u, "(1x,A,10(1x,I0))") "hel state" = ", data%hel_state
write (u, "(1x,A,10(1x,I0))") "col state" = ", data%col_state

```

```

write (u, "(1x,A,10(1x,L1))") "ghost flag =", data%ghost_flag
write (u, "(1x,A,10(1x,F5.3))") "color factors =", data%color_factors
write (u, "(1x,A,10(1x,I0))") "cf index =", data%cf_index

write (u, "(A)")
write (u, "(A)")  "* Call feature of proclibs6_a:"
write (u, "(A)")

select type (proc_driver)
type is (prctest_6_t)
  call proc_driver%proc1 (n)
  write (u, "(1x,A,I0)") "proc1 = ", n
end select

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_6"
end subroutine process_libraries_6

```

MD5 sums

Check MD5 sum calculation.

```

(Process libraries: execute tests)+≡
  call test (process_libraries_7, "process_libraries_7", &
    "process definition list", &
    u, results)

(Process libraries: tests)+≡
  subroutine process_libraries_7 (u)
    integer, intent(in) :: u
    type(prc_template_t), dimension(:), allocatable :: process_core_templates
    type(process_def_entry_t) :: entry
    class(prc_core_def_t), allocatable :: test_def

    write (u, "(A)")  "* Test output: process_libraries_7"
    write (u, "(A)")  "* Purpose: Construct a process definition list &
      &and check MD5 sums"
    write (u, "(A)")
    write (u, "(A)")  "* Construct a process definition list"
    write (u, "(A)")  "* Process: two components"
    write (u, "(A)")

    allocate (process_core_templates (1))
    allocate (prcdef_2_t :: process_core_templates(1)%core_def)

    call entry%init (var_str ("first"), model_name = var_str ("Test"), &
      n_in = 1, n_components = 2)
    allocate (prcdef_2_t :: test_def)
    select type (test_def)
    type is (prcdef_2_t); test_def%data = 31
    end select
    call entry%import_component (1, n_out = 3, &

```



```

        prt_in = new_prt_spec ([var_str ("a")]), &
        prt_out = new_prt_spec ([var_str ("b"), var_str ("c"), &
                                var_str ("e")]), &
        method = var_str ("test"), &
        variant = test_def)
allocate (prcdef_2_t :: test_def)
select type (test_def)
type is (prcdef_2_t); test_def%data = 42
end select
call entry%import_component (2, n_out = 2, &
        prt_in = new_prt_spec ([var_str ("a")]), &
        prt_out = new_prt_spec ([var_str ("b"), var_str ("c")]), &
        method = var_str ("test"), &
        variant = test_def)
call entry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute MD5 sums"
write (u, "(A)")

call entry%compute_md5sum ()
call entry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recalculate MD5 sums (should be identical)"
write (u, "(A)")

call entry%compute_md5sum ()
call entry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Modify a component and recalculate MD5 sums"
write (u, "(A)")

select type (test_def => entry%initial(2)%core_def)
type is (prcdef_2_t)
    test_def%data = 54
end select
call entry%compute_md5sum ()
call entry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Modify the model and recalculate MD5 sums"
write (u, "(A)")

entry%model_name = "foo"
call entry%compute_md5sum ()
call entry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_7"
end subroutine process_libraries_7

```

Here is the actual test:

```

<Process libraries: execute tests>+≡
    call test (process_libraries_8, "process_libraries_8", &
        "library status checks", &
        u, results)

<Process libraries: tests>+≡
    subroutine process_libraries_8 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        type(process_def_entry_t), pointer :: entry
        class(prc_core_def_t), allocatable :: core_def
        type(os_data_t) :: os_data

        write (u, "(A)")  "* Test output: process_libraries_8"
        write (u, "(A)")  "* Purpose: build and load a process library"
        write (u, "(A)")  "*           with an external (pseudo) matrix element"
        write (u, "(A)")  "*           Check status updates"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize a process library with one entry"
        write (u, "(A)")
        call lib%init (var_str ("proclibs8"))
        call os_data_init (os_data)

        allocate (prcdef_6_t :: core_def)
        select type (core_def)
        type is (prcdef_6_t)
            call core_def%init ()
        end select

        allocate (entry)
        call entry%init (var_str ("proclibs8_a"), &
            model_name = var_str ("Test_model"), &
            n_in = 1, n_components = 1)
        call entry%import_component (1, n_out = 2, &
            prt_in = new_prt_spec ([var_str ("a")]), &
            prt_out = new_prt_spec ([var_str ("b"), var_str ("c")]), &
            method = var_str ("test"), &
            variant = core_def)
        call lib%append (entry)

        write (u, "(A)")  "* Configure library"
        write (u, "(A)")

        call lib%configure (os_data)
        call lib%compute_md5sum ()

        associate (def => lib%entry(1)%def%initial(1))
            select type (writer => lib%driver%record(1)%writer)
            type is (test_writer_4_t)
                writer%md5sum = def%md5sum
            end select
        end associate

        write (u, "(1x,A,L1)")  "library loaded = ", lib%driver%loaded

```

```

write (u, "(1x,A,I0)") "lib status  = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status

write (u, "(A)")
write (u, "(A)")  "* Write makefile"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Update status"
write (u, "(A)")

call lib%update_status (os_data)
write (u, "(1x,A,L1)") "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)") "lib status  = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status

write (u, "(A)")
write (u, "(A)")  "* Write driver source code"
write (u, "(A)")
call lib%write_driver (force = .false.)

write (u, "(A)")  "* Write process source code"
write (u, "(A)")
call lib%make_source (os_data)

write (u, "(1x,A,L1)") "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)") "lib status  = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status

write (u, "(A)")
write (u, "(A)")  "* Compile and load"
write (u, "(A)")

call lib%load (os_data)
write (u, "(1x,A,L1)") "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)") "lib status  = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status

write (u, "(A)")
write (u, "(A)")  "* Append process and reconfigure"
write (u, "(A)")

allocate (prcdef_6_t :: core_def)
select type (core_def)
type is (prcdef_6_t)
    call core_def%init ()
end select

allocate (entry)
call entry%init (var_str ("proclibs8_b"), &
    model_name = var_str ("Test_model"), &
    n_in = 1, n_components = 1)
call entry%import_component (1, n_out = 2, &
    prt_in  = new_prt_spec ([var_str ("a")]), &

```

```

        prt_out = new_prt_spec ([var_str ("b"), var_str ("d")], &
        method = var_str ("test"), &
        variant = core_def)
call lib%append (entry)

call lib%configure (os_data)
call lib%compute_md5sum ()
associate (def => lib%entry(2)%def%initial(1))
    select type (writer => lib%driver%record(2)%writer)
    type is (test_writer_4_t)
        writer%md5sum = def%md5sum
    end select
end associate
call lib%write_makefile (os_data, force = .false.)
call lib%write_driver (force = .false.)

write (u, "(1x,A,L1)" "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)" "lib status = ", lib%status
write (u, "(1x,A,I0)" "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)" "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Update status"
write (u, "(A)")

call lib%update_status (os_data)
write (u, "(1x,A,L1)" "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)" "lib status = ", lib%status
write (u, "(1x,A,I0)" "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)" "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Write source code"
write (u, "(A)")

call lib%make_source (os_data)
write (u, "(1x,A,L1)" "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)" "lib status = ", lib%status
write (u, "(1x,A,I0)" "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)" "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Reset status"
write (u, "(A)")

lib%status = STAT_CONFIGURED
lib%entry%status = STAT_CONFIGURED
write (u, "(1x,A,L1)" "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)" "lib status = ", lib%status
write (u, "(1x,A,I0)" "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)" "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Update status"

```

```

write (u, "(A)")

call lib%update_status (os_data)
write (u, "(1x,A,L1)") "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)") "lib status   = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)") "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Partial cleanup"
write (u, "(A)")

call lib%clean (os_data, distclean = .false.)
write (u, "(1x,A,L1)") "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)") "lib status   = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)") "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Update status"
write (u, "(A)")

call lib%update_status (os_data)
write (u, "(1x,A,L1)") "library loaded = ", lib%driver%loaded
write (u, "(1x,A,I0)") "lib status   = ", lib%status
write (u, "(1x,A,I0)") "proc1 status = ", lib%entry(1)%status
write (u, "(1x,A,I0)") "proc2 status = ", lib%entry(2)%status

write (u, "(A)")
write (u, "(A)")  "* Complete cleanup"

call lib%clean (os_data, distclean = .true.)
call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_libraries_8"
end subroutine process_libraries_8

```

13.5 Process Library Stacks

For storing and handling multiple libraries, we define process library stacks. These are ordinary stacks where new entries are pushed onto the top.

```

<prclib_stacks.f90>≡
  <File header>

  module prclib_stacks

    <Use strings>
    use io_units
    use format_utils, only: write_separator

```

```

    use unit_tests
    use os_interface
    use process_libraries

    <Standard module head>

    <Prclib stacks: public>

    <Prclib stacks: types>

    contains

    <Prclib stacks: procedures>

    <Prclib stacks: tests>

    end module prclib_stacks

```

13.5.1 The stack entry type

A stack entry is a process library object, augmented by a pointer to the next entry. We do not need specific methods, all relevant methods are inherited.

On higher level, process libraries should be prepared as process entry objects.

```

<Prclib stacks: public>≡
    public :: prclib_entry_t

<Prclib stacks: types>≡
    type, extends (process_library_t) :: prclib_entry_t
        type(prclib_entry_t), pointer :: next => null ()
    end type prclib_entry_t

```

13.5.2 The prclib stack type

For easy conversion and lookup it is useful to store the filling number in the object. The content is stored as a linked list.

```

<Prclib stacks: public>+≡
    public :: prclib_stack_t

<Prclib stacks: types>+≡
    type :: prclib_stack_t
        integer :: n = 0
        type(prclib_entry_t), pointer :: first => null ()
    contains
        <Prclib stacks: prclib stack: TBP>
    end type prclib_stack_t

```

Finalizer. Iteratively deallocate the stack entries. The resulting empty stack can be immediately recycled, if necessary.

```

<Prclib stacks: prclib stack: TBP>≡
    procedure :: final => prclib_stack_final

```

```

<Prclib stacks: procedures>+=
  subroutine prclib_stack_final (object)
    class(prclib_stack_t), intent(inout) :: object
    type(prclib_entry_t), pointer :: lib
    do while (associated (object%first))
      lib => object%first
      object%first => lib%next
      call lib%final ()
      deallocate (lib)
    end do
    object%n = 0
  end subroutine prclib_stack_final

```

Output. The entries on the stack will be ordered LIFO, i.e., backwards.

```

<Prclib stacks: prclib stack: TBP>+=
  procedure :: write => prclib_stack_write

<Prclib stacks: procedures>+=
  subroutine prclib_stack_write (object, unit, libpath)
    class(prclib_stack_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: libpath
    type(prclib_entry_t), pointer :: lib
    integer :: u
    u = given_output_unit (unit)
    call write_separator (u, 2)
    select case (object%n)
    case (0)
      write (u, "(1x,A)") "Process library stack: [empty]"
    case default
      write (u, "(1x,A)") "Process library stack:"
      lib => object%first
      do while (associated (lib))
        call write_separator (u)
        call lib%write (u, libpath)
        lib => lib%next
      end do
    end select
    call write_separator (u, 2)
  end subroutine prclib_stack_write

```

13.5.3 Operating on Stacks

We take a library entry pointer and push it onto the stack. The previous pointer is nullified. Subsequently, the library entry is ‘owned’ by the stack and will be finalized when the stack is deleted.

```

<Prclib stacks: prclib stack: TBP>+=
  procedure :: push => prclib_stack_push

<Prclib stacks: procedures>+=
  subroutine prclib_stack_push (stack, lib)
    class(prclib_stack_t), intent(inout) :: stack

```

```

    type(prclib_entry_t), intent(inout), pointer :: lib
    lib%next => stack%first
    stack%first => lib
    lib => null ()
    stack%n = stack%n + 1
end subroutine prclib_stack_push

```

13.5.4 Accessing Contents

Return a pointer to the topmost stack element. The result type is just the bare `process_library_t`. There is no `target` attribute required since the stack elements are allocated via pointers.

```

<Prclib stacks: prclib stack: TBP>+≡
    procedure :: get_first_ptr => prclib_stack_get_first_ptr

<Prclib stacks: procedures>+≡
    function prclib_stack_get_first_ptr (stack) result (ptr)
        class(prclib_stack_t), intent(in) :: stack
        type(process_library_t), pointer :: ptr
        if (associated (stack%first)) then
            ptr => stack%first%process_library_t
        else
            ptr => null ()
        end if
    end function prclib_stack_get_first_ptr

```

Return a complete list of the libraries (names) in the stack. The list is in the order in which the elements got pushed onto the stack, so the 'first' entry is listed last.

```

<Prclib stacks: prclib stack: TBP>+≡
    procedure :: get_names => prclib_stack_get_names

<Prclib stacks: procedures>+≡
    subroutine prclib_stack_get_names (stack, libname)
        class(prclib_stack_t), intent(in) :: stack
        type(string_t), dimension(:), allocatable, intent(out) :: libname
        type(prclib_entry_t), pointer :: lib
        integer :: i
        allocate (libname (stack%n))
        i = stack%n
        lib => stack%first
        do while (associated (lib))
            libname(i) = lib%get_name ()
            i = i - 1
            lib => lib%next
        end do
    end subroutine prclib_stack_get_names

```

Return a pointer to the library with given name.

```

<Prclib stacks: prclib stack: TBP>+≡
    procedure :: get_library_ptr => prclib_stack_get_library_ptr

```



```

<Prclib stacks: procedures>+≡
function prclib_stack_get_library_ptr (stack, libname) result (ptr)
  class(prclib_stack_t), intent(in) :: stack
  type(string_t), intent(in) :: libname
  type(process_library_t), pointer :: ptr
  type(prclib_entry_t), pointer :: current
  current => stack%first
  do while (associated (current))
    if (current%get_name () == libname) then
      ptr => current%process_library_t
      return
    end if
    current => current%next
  end do
  ptr => null ()
end function prclib_stack_get_library_ptr

```

13.5.5 Unit tests

```

<Prclib stacks: public>+≡
public :: prclib_stacks_test
<Prclib stacks: tests>≡
subroutine prclib_stacks_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
<Prclib stacks: execute tests>
end subroutine prclib_stacks_test

```

Write an empty process library stack

The most trivial test is to write an uninitialized process library stack.

```

<Prclib stacks: execute tests>≡
call test (prclib_stacks_1, "prclib_stacks_1", &
  "write an empty process library stack", &
  u, results)
<Prclib stacks: tests>+≡
subroutine prclib_stacks_1 (u)
  integer, intent(in) :: u
  type(prclib_stack_t) :: stack

  write (u, "(A)")  "* Test output: prclib_stacks_1"
  write (u, "(A)")  "* Purpose: display an empty process library stack"
  write (u, "(A)")

  call stack%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: prclib_stacks_1"

end subroutine prclib_stacks_1

```

Fill a process library stack

Fill a process library stack with two (identical) processes.

```
(Prclib_stacks: execute tests)+≡
    call test (prclib_stacks_2, "prclib_stacks_2", &
              "fill a process library stack", &
              u, results)

(Prclib_stacks: tests)+≡
    subroutine prclib_stacks_2 (u)
        integer, intent(in) :: u
        type(prclib_stack_t) :: stack
        type(prclib_entry_t), pointer :: lib

        write (u, "(A)")  "* Test output: prclib_stacks_2"
        write (u, "(A)")  "*   Purpose: fill a process library stack"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize two (empty) libraries &
                           &and push them on the stack"
        write (u, "(A)")

        allocate (lib)
        call lib%init (var_str ("lib1"))
        call stack%push (lib)

        allocate (lib)
        call lib%init (var_str ("lib2"))
        call stack%push (lib)

        call stack%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Cleanup"

        call stack%final ()

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: prclib_stacks_2"

    end subroutine prclib_stacks_2
```

13.6 Trivial matrix element for tests

For the purpose of testing the workflow, we implement here two matrix elements with the simplest possible structure.

This matrix element generator can only generate a single scattering process and a single decay process. The scattering process is a quartic interaction of a massless, neutral and colorless scalar s with unit coupling results in a trivial $2 \rightarrow 2$ scattering process. The matrix element is implemented internally, so we do not need the machinery of external process libraries. The decay process is a

decay of **s** into a pair of colored fermions **f**.

$\langle \text{prc_test.f90} \rangle \equiv$

$\langle \text{File header} \rangle$

`module prc_test`

`use iso_c_binding !NODEP!`

`use kinds`

$\langle \text{Use strings} \rangle$

`use unit_tests`

`use os_interface`

`use process_constants`

`use prclib_interfaces`

`use prc_core_def`

`use particle_specifiers`

`use process_libraries`

$\langle \text{Standard module head} \rangle$

$\langle \text{Test ME: public} \rangle$

$\langle \text{Test ME: types} \rangle$

`contains`

$\langle \text{Test ME: procedures} \rangle$

$\langle \text{Test ME: tests} \rangle$

`end module prc_test`

13.6.1 Process definition

For the process definition we implement an extension of the `prc_core_def_t` abstract type.

$\langle \text{Test ME: public} \rangle \equiv$

`public :: prc_test_def_t`

$\langle \text{Test ME: types} \rangle \equiv$

`type, extends (prc_core_def_t) :: prc_test_def_t`

`type(string_t) :: model_name`

`type(string_t), dimension(:), allocatable :: prt_in`

`type(string_t), dimension(:), allocatable :: prt_out`

`contains`

$\langle \text{Test ME: test me def: TBP} \rangle$

`end type prc_test_def_t`

$\langle \text{Test ME: test me def: TBP} \rangle \equiv$

`procedure, nopass :: type_string => prc_test_def_type_string`

$\langle \text{Test ME: procedures} \rangle \equiv$

`function prc_test_def_type_string () result (string)`

```

        type(string_t) :: string
        string = "test_me"
    end function prc_test_def_type_string

```

There is no 'feature' here since there is no external code.

```

<Test ME: test me def: TBP>+≡
    procedure, nopass :: get_features => prc_test_def_get_features

<Test ME: procedures>+≡
    subroutine prc_test_def_get_features (features)
        type(string_t), dimension(:), allocatable, intent(out) :: features
        allocate (features (0))
    end subroutine prc_test_def_get_features

```

Initialization: set some data (not really useful).

```

<Test ME: test me def: TBP>+≡
    procedure :: init => prc_test_def_init

<Test ME: procedures>+≡
    subroutine prc_test_def_init (object, model_name, prt_in, prt_out)
        class(prc_test_def_t), intent(out) :: object
        type(string_t), intent(in) :: model_name
        type(string_t), dimension(:), intent(in) :: prt_in
        type(string_t), dimension(:), intent(in) :: prt_out
        object%model_name = model_name
        allocate (object%prt_in (size (prt_in)))
        object%prt_in = prt_in
        allocate (object%prt_out (size (prt_out)))
        object%prt_out = prt_out
    end subroutine prc_test_def_init

```

Write/read process- and method-specific data. (No-op)

```

<Test ME: test me def: TBP>+≡
    procedure :: write => prc_test_def_write

<Test ME: procedures>+≡
    subroutine prc_test_def_write (object, unit)
        class(prc_test_def_t), intent(in) :: object
        integer, intent(in) :: unit
    end subroutine prc_test_def_write

<Test ME: test me def: TBP>+≡
    procedure :: read => prc_test_def_read

<Test ME: procedures>+≡
    subroutine prc_test_def_read (object, unit)
        class(prc_test_def_t), intent(out) :: object
        integer, intent(in) :: unit
    end subroutine prc_test_def_read

```

Allocate the driver for test ME matrix elements. We get the actual component ID (basename), and we can transfer all process-specific data from the process definition.

```

<Test ME: test me def: TBP>+≡
  procedure :: allocate_driver => prc_test_def_allocate_driver

<Test ME: procedures>+≡
  subroutine prc_test_def_allocate_driver (object, driver, basename)
    class(prc_test_def_t), intent(in) :: object
    class(prc_core_driver_t), intent(out), allocatable :: driver
    type(string_t), intent(in) :: basename
    allocate (prc_test_t :: driver)
    select type (driver)
    type is (prc_test_t)
      driver%id = basename
      driver%model_name = object%model_name
      select case (size (object%prt_in))
      case (1); driver%scattering = .false.
      case (2); driver%scattering = .true.
      end select
    end select
  end subroutine prc_test_def_allocate_driver

```

Nothing to connect. This subroutine will not be called.

```

<Test ME: test me def: TBP>+≡
  procedure :: connect => prc_test_def_connect

<Test ME: procedures>+≡
  subroutine prc_test_def_connect (def, lib_driver, i, proc_driver)
    class(prc_test_def_t), intent(in) :: def
    class(prclib_driver_t), intent(in) :: lib_driver
    integer, intent(in) :: i
    class(prc_core_driver_t), intent(inout) :: proc_driver
  end subroutine prc_test_def_connect

```

13.6.2 Driver

```

<Test ME: public>+≡
  public :: prc_test_t

<Test ME: types>+≡
  type, extends (process_driver_internal_t) :: prc_test_t
    type(string_t) :: id
    type(string_t) :: model_name
    logical :: scattering = .true.
  contains
    <Test ME: test me driver: TBP>
  end type prc_test_t

```

In contrast to generic matrix-element implementations, we can hard-wire the amplitude method as a type-bound procedure.

```

<Test ME: test me driver: TBP>≡
  procedure, nopass :: get_amplitude => prc_test_get_amplitude

```

```

<Test ME: procedures>+≡
function prc_test_get_amplitude (p) result (amp)
  complex(default) :: amp
  real(default), dimension(:,:), intent(in) :: p
  amp = 1
end function prc_test_get_amplitude

```

The reported type is the same as for the `prc_test_def_t` type.

```

<Test ME: test me driver: TBP>+≡
procedure, nopass :: type_name => prc_test_type_name

<Test ME: procedures>+≡
function prc_test_type_name () result (string)
  type(string_t) :: string
  string = "test_me"
end function prc_test_type_name

```

Fill process constants.

```

<Test ME: test me driver: TBP>+≡
procedure :: fill_constants => prc_test_fill_constants

<Test ME: procedures>+≡
subroutine prc_test_fill_constants (driver, data)
  class(prc_test_t), intent(in) :: driver
  type(process_constants_t), intent(out) :: data
  data%id = driver%id
  data%model_name = driver%model_name
  if (driver%scattering) then
    data%n_in = 2
    data%n_out = 2
    data%n_flv = 1
    data%n_hel = 1
    data%n_col = 1
    data%n_cin = 2
    data%n_cf = 1
    allocate (data%flv_state (4, 1))
    data%flv_state = 25
    allocate (data%hel_state (4, 1))
    data%hel_state = 0
    allocate (data%col_state (2, 4, 1))
    data%col_state = 0
    allocate (data%ghost_flag (4, 1))
    data%ghost_flag = .false.
    allocate (data%color_factors (1))
    data%color_factors = 1
    allocate (data%cf_index (2, 1))
    data%cf_index = 1
  else
    data%n_in = 1
    data%n_out = 2
    data%n_flv = 1
    data%n_hel = 2
    data%n_col = 1
    data%n_cin = 2
  end if
end subroutine prc_test_fill_constants

```

```

data%n_cf = 1
allocate (data%flv_state (3, 1))
data%flv_state(:,1) = [25, 6, -6]
allocate (data%hel_state (3, 2))
data%hel_state(:,1) = [0, 1,-1]
data%hel_state(:,2) = [0,-1, 1]
allocate (data%col_state (2, 3, 1))
data%col_state = reshape ([0,0, 1,0, 0,-1], [2,3,1])
allocate (data%ghost_flag (3, 1))
data%ghost_flag = .false.
allocate (data%color_factors (1))
data%color_factors = 3
allocate (data%cf_index (2, 1))
data%cf_index = 1
end if
end subroutine prc_test_fill_constants

```

13.6.3 Shortcut

Since this module is there for testing purposes, we set up a subroutine that does all the work at once: create a library with the two processes (scattering and decay), configure and load, and set up the driver.

```

<Test ME: public>+≡
public :: prc_test_create_library

<Test ME: procedures>+≡
subroutine prc_test_create_library &
  (libname, lib, scattering, decay, procname1, procname2)
  type(string_t), intent(in) :: libname
  type(process_library_t), intent(out) :: lib
  logical, intent(in), optional :: scattering, decay
  type(string_t), intent(in), optional :: procname1, procname2
  type(string_t) :: model_name, procname
  type(string_t), dimension(:), allocatable :: prt_in, prt_out
  class(prc_core_def_t), allocatable :: def
  type(process_def_entry_t), pointer :: entry
  type(os_data_t) :: os_data
  logical :: sca, dec
  sca = .true.; if (present (scattering)) sca = scattering
  dec = .false.; if (present (decay)) dec = decay

  call os_data_init (os_data)
  call lib%init (libname)
  model_name = "Test"

  if (sca) then
    if (present (procname1)) then
      procname = procname1
    else
      procname = libname
    end if
  end if
  allocate (prt_in (2), prt_out (2))
  prt_in = [var_str ("s"), var_str ("s")]

```

```

    prt_out = [var_str ("s"), var_str ("s")]
    allocate (prc_test_def_t :: def)
    select type (def)
    type is (prc_test_def_t)
        call def%init (model_name, prt_in, prt_out)
    end select
    allocate (entry)
    call entry%init (procname, model_name = model_name, &
        n_in = 2, n_components = 1)
    call entry%import_component (1, n_out = size (prt_out), &
        prt_in = new_prt_spec (prt_in), &
        prt_out = new_prt_spec (prt_out), &
        method = var_str ("test_me"), &
        variant = def)
    call lib%append (entry)
end if

if (dec) then
    if (present (procname2)) then
        procname = procname2
    else
        procname = libname
    end if
    if (allocated (prt_in)) deallocate (prt_in, prt_out)
    allocate (prt_in (1), prt_out (2))
    prt_in = [var_str ("s")]
    prt_out = [var_str ("f"), var_str ("fbar")]
    allocate (prc_test_def_t :: def)
    select type (def)
    type is (prc_test_def_t)
        call def%init (model_name, prt_in, prt_out)
    end select
    allocate (entry)
    call entry%init (procname, model_name = model_name, &
        n_in = 1, n_components = 1)
    call entry%import_component (1, n_out = size (prt_out), &
        prt_in = new_prt_spec (prt_in), &
        prt_out = new_prt_spec (prt_out), &
        method = var_str ("test_decay"), &
        variant = def)
    call lib%append (entry)
end if

call lib%configure (os_data)
call lib%load (os_data)
end subroutine prc_test_create_library

```

13.6.4 Test

This is the master for calling self-test procedures.

```

<Test ME: public>+≡
public :: prc_test_test

```



```

<Test ME: tests>≡
  subroutine prc_test_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    <Test ME: execute tests>
  end subroutine prc_test_test

```

Generate and load the scattering process

The process is $ss \rightarrow ss$, where s is a trivial scalar particle, for vanishing mass and unit coupling. We initialize the process, build the library, and compute the particular matrix element for momenta of unit energy and right-angle scattering. (The scattering is independent of angle.) The matrix element is equal to unity.

```

<Test ME: execute tests>≡
  call test (prc_test_1, "prc_test_1", &
    "build and load trivial process", &
    u, results)

<Test ME: tests>+≡
  subroutine prc_test_1 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(process_library_t) :: lib
    class(prc_core_def_t), allocatable :: def
    type(process_def_entry_t), pointer :: entry
    type(string_t) :: model_name
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    type(process_constants_t) :: data
    class(prc_core_driver_t), allocatable :: driver
    real(default), dimension(0:3,4) :: p
    integer :: i

    write (u, "(A)")  "* Test output: prc_test_1"
    write (u, "(A)")  "*   Purpose: create a trivial process"
    write (u, "(A)")  "*               build a library and &
      &access the matrix element"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize a process library with one entry"
    write (u, "(A)")
    call os_data_init (os_data)
    call lib%init (var_str ("prc_test1"))

    model_name = "Test"
    allocate (prt_in (2), prt_out (2))
    prt_in = [var_str ("s"), var_str ("s")]
    prt_out = [var_str ("s"), var_str ("s")]

    allocate (prc_test_def_t :: def)
    select type (def)
    type is (prc_test_def_t)
      call def%init (model_name, prt_in, prt_out)
    end select

```

```

allocate (entry)
call entry%init (var_str ("prc_test1_a"), model_name = model_name, &
    n_in = 2, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
    prt_in = new_prt_spec (prt_in), &
    prt_out = new_prt_spec (prt_out), &
    method = var_str ("test_me"), &
    variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Load library"
write (u, "(A)")
call lib%load (os_data)

call lib%write (u)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active" = ", &
    lib%is_active ()
write (u, "(1x,A,I0)")  "n_processes" = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Constants of prc_test1_a_i1:"
write (u, "(A)")

call lib%connect_process (var_str ("prc_test1_a"), 1, data, driver)

write (u, "(1x,A,A)")  "component ID" = ", char (data%id)
write (u, "(1x,A,A)")  "model name" = ", char (data%model_name)
write (u, "(1x,A,A,A)")  "md5sum" = ', ", data%md5sum, "'
write (u, "(1x,A,L1)")  "openmp supported = ", data%openmp_supported
write (u, "(1x,A,I0)")  "n_in = ", data%n_in
write (u, "(1x,A,I0)")  "n_out = ", data%n_out
write (u, "(1x,A,I0)")  "n_flv = ", data%n_flv
write (u, "(1x,A,I0)")  "n_hel = ", data%n_hel
write (u, "(1x,A,I0)")  "n_col = ", data%n_col
write (u, "(1x,A,I0)")  "n_cin = ", data%n_cin
write (u, "(1x,A,I0)")  "n_cf = ", data%n_cf
write (u, "(1x,A,10(1x,I0))")  "flv state =", data%flv_state
write (u, "(1x,A,10(1x,I2))")  "hel state =", data%hel_state(:,1)
write (u, "(1x,A,10(1x,I0))")  "col state =", data%col_state
write (u, "(1x,A,10(1x,L1))")  "ghost flag =", data%ghost_flag
write (u, "(1x,A,10(1x,F5.3))")  "color factors =", data%color_factors
write (u, "(1x,A,10(1x,I0))")  "cf index =", data%cf_index

write (u, "(A)")

```

```

write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    1.0_default, 0.0_default, 0.0_default, 1.0_default, &
    1.0_default, 0.0_default, 0.0_default,-1.0_default, &
    1.0_default, 1.0_default, 0.0_default, 0.0_default, &
    1.0_default,-1.0_default, 0.0_default, 0.0_default &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.4))")  "p", i, " =", p(:,i)
end do

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element:"
write (u, "(A)")

select type (driver)
type is (prc_test_t)
    write (u, "(1x,A,1x,E11.4)") "|amp| =", abs (driver%get_amplitude (p))
end select

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_test_1"

end subroutine prc_test_1

```

Shortcut

This is identical to the previous test, but we create the library be a single command. This is handy for other modules which use the test process.

```

<Test ME: execute tests>+≡
    call test (prc_test_2, "prc_test_2", &
        "build and load trivial process using shortcut", &
        u, results)

<Test ME: tests>+≡
    subroutine prc_test_2 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        class(prc_core_driver_t), allocatable :: driver
        type(process_constants_t) :: data
        real(default), dimension(0:3,4) :: p

        write (u, "(A)")  "* Test output: prc_test_2"
        write (u, "(A)")  "*   Purpose: create a trivial process"
        write (u, "(A)")  "*           build a library and &
            &access the matrix element"
        write (u, "(A)")

        write (u, "(A)")  "* Build and load a process library with one entry"

```

```

call prc_test_create_library (var_str ("prc_test2"), lib)
call lib%connect_process (var_str ("prc_test2"), 1, data, driver)

p = reshape ([ &
    1.0_default, 0.0_default, 0.0_default, 1.0_default, &
    1.0_default, 0.0_default, 0.0_default,-1.0_default, &
    1.0_default, 1.0_default, 0.0_default, 0.0_default, &
    1.0_default,-1.0_default, 0.0_default, 0.0_default &
    ], [4,4])

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element:"
write (u, "(A)")

select type (driver)
type is (prc_test_t)
    write (u, "(1x,A,1x,E11.4)") "|amp| =", abs (driver%get_amplitude (p))
end select

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_test_2"

end subroutine prc_test_2

```

Generate and load the decay process

The process is $s \rightarrow f\bar{f}$, where s is a trivial scalar particle and f is a colored fermion. We initialize the process, build the library, and compute the particular matrix element for a fixed momentum configuration. (The decay is independent of angle.) The matrix element is equal to unity.

```

<Test ME: execute tests>+≡
    call test (prc_test_3, "prc_test_3", &
        "build and load trivial decay", &
        u, results)

<Test ME: tests>+≡
subroutine prc_test_3 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(process_library_t) :: lib
    class(prc_core_def_t), allocatable :: def
    type(process_def_entry_t), pointer :: entry
    type(string_t) :: model_name
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    type(process_constants_t) :: data
    class(prc_core_driver_t), allocatable :: driver
    real(default), dimension(0:3,3) :: p
    integer :: i

    write (u, "(A)")  "* Test output: prc_test_3"

```

```

write (u, "(A)")  "* Purpose: create a trivial decay process"
write (u, "(A)")  "* build a library and &
    &access the matrix element"
write (u, "(A)")

write (u, "(A)")  "* Initialize a process library with one entry"
write (u, "(A)")
call os_data_init (os_data)
call lib%init (var_str ("prc_test3"))

model_name = "Test"
allocate (prt_in (2), prt_out (2))
prt_in = [var_str ("s")]
prt_out = [var_str ("f"), var_str ("F")]

allocate (prc_test_def_t :: def)
select type (def)
type is (prc_test_def_t)
    call def%init (model_name, prt_in, prt_out)
end select
allocate (entry)
call entry%init (var_str ("prc_test3_a"), model_name = model_name, &
    n_in = 1, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
    prt_in = new_prt_spec (prt_in), &
    prt_out = new_prt_spec (prt_out), &
    method = var_str ("test_me"), &
    variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Load library"
write (u, "(A)")
call lib%load (os_data)

call lib%write (u)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)") "is active" = ", &
    lib%is_active ()
write (u, "(1x,A,I0)") "n_processes" = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Constants of prc_test3_a_i1:"
write (u, "(A)")

call lib%connect_process (var_str ("prc_test3_a"), 1, data, driver)

```

```

write (u, "(1x,A,A)") "component ID      = ", char (data%id)
write (u, "(1x,A,A)") "model name       = ", char (data%model_name)
write (u, "(1x,A,A,A)") "md5sum          = ', data%md5sum, '"
write (u, "(1x,A,L1)") "openmp supported = ", data%openmp_supported
write (u, "(1x,A,I0)") "n_in      = ", data%n_in
write (u, "(1x,A,I0)") "n_out     = ", data%n_out
write (u, "(1x,A,I0)") "n_flv    = ", data%n_flv
write (u, "(1x,A,I0)") "n_hel    = ", data%n_hel
write (u, "(1x,A,I0)") "n_col    = ", data%n_col
write (u, "(1x,A,I0)") "n_cin    = ", data%n_cin
write (u, "(1x,A,I0)") "n_cf     = ", data%n_cf
write (u, "(1x,A,10(1x,I0))") "flv state =", data%flv_state
write (u, "(1x,A,10(1x,I2))") "hel state =", data%hel_state(:,1)
write (u, "(1x,A,10(1x,I2))") "hel state =", data%hel_state(:,2)
write (u, "(1x,A,10(1x,I0))") "col state =", data%col_state
write (u, "(1x,A,10(1x,L1))") "ghost flag =", data%ghost_flag
write (u, "(1x,A,10(1x,F5.3))") "color factors =", data%color_factors
write (u, "(1x,A,10(1x,I0))") "cf index =", data%cf_index

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    125._default, 0.0_default, 0.0_default, 0.0_default, &
    62.5_default, 0.0_default, 0.0_default, 62.5_default, &
    62.5_default, 0.0_default, 0.0_default, -62.5_default &
    ], [4,3])
do i = 1, 3
    write (u, "(2x,A,I0,A,4(1x,F8.4))") "p", i, " =", p(:,i)
end do

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element:"
write (u, "(A)")

select type (driver)
type is (prc_test_t)
    write (u, "(1x,A,1x,E11.4)") "|amp| =", abs (driver%get_amplitude (p))
end select

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_test_3"

end subroutine prc_test_3

```

Shortcut

This is identical to the previous test, but we create the library be a single command. This is handy for other modules which use the test process.

```

<Test ME: execute tests>+≡
    call test (prc_test_4, "prc_test_4", &
        "build and load trivial decay using shortcut", &
        u, results)

<Test ME: tests>+≡
    subroutine prc_test_4 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        class(prc_core_driver_t), allocatable :: driver
        type(process_constants_t) :: data
        real(default), dimension(0:3,3) :: p

        write (u, "(A)")  "* Test output: prc_test_4"
        write (u, "(A)")  "* Purpose: create a trivial decay process"
        write (u, "(A)")  "* build a library and &
            &access the matrix element"
        write (u, "(A)")

        write (u, "(A)")  "* Build and load a process library with one entry"

        call prc_test_create_library (var_str ("prc_test4"), lib, &
            scattering=.false., decay=.true.)
        call lib%connect_process (var_str ("prc_test4"), 1, data, driver)

        p = reshape ([ &
            125._default, 0.0_default, 0.0_default, 0.0_default, &
            62.5_default, 0.0_default, 0.0_default, 62.5_default, &
            62.5_default, 0.0_default, 0.0_default, -62.5_default &
            ], [4,3])

        write (u, "(A)")
        write (u, "(A)")  "* Compute matrix element:"
        write (u, "(A)")

        select type (driver)
        type is (prc_test_t)
            write (u, "(1x,A,1x,E11.4)") "|amp| =", abs (driver%get_amplitude (p))
        end select

        call lib%final ()

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: prc_test_4"

    end subroutine prc_test_4

```

Chapter 14

Particles

This chapter collects modules that implement particle objects, for use in event records.

While within interactions, all correlations are manifest, a particle array is derived by selecting a particular quantum number set. This involves tracing over all other particles, as far as polarization is concerned. Thus, a particle has definite flavor, color, and a single-particle density matrix for polarization.

polarizations The polarization object is based on a `state_matrix_t` object. It describes the spin density matrix of a particle.

particles Particle objects and particle lists, as the base of event records.

14.1 Polarization

Particle polarization is determined by a particular quantum state which has just helicity information. For defining polarizations, we adopt the phase convention for a spin-1/2 particle that

$$\rho = \frac{1}{2}(1 + \vec{\alpha} \cdot \vec{\sigma}) \quad (14.1)$$

with the polarization axis $\vec{\alpha}$. Using this, we define

1. Trivial polarization: $\vec{\alpha} = 0$. [This is unpolarized, but distinct from the particular undefined polarization matrix which has the same meaning.]
2. Circular polarization: $\vec{\alpha}$ points in $\pm z$ direction.
3. Transversal polarization: $\vec{\alpha}$ points orthogonal to the z direction, with a phase ϕ that is 0 for the x axis, and $\pi/2 = 90^\circ$ for the y axis. For antiparticles, the phase switches sign, corresponding to complex conjugation.
4. Axis polarization, where we explicitly give $\vec{\alpha}$.

For higher spin, we retain this definition, but apply it to the two components with maximum and minimum weight. For massless particles, this is sufficient. For massive particles, we add the possibilities:

5. Longitudinal polarization: Only the 0-component is set. This is possible only for bosons.
6. Diagonal polarization: Explicitly specify all components in the helicity basis.

Obviously, this does not exhaust the possible density matrices for higher spin, but it should cover all practical applications.

`<polarizations.f90>`≡
<File header>

`module polarizations`

<Use kinds>
<Use strings>
`use constants, only: imago`
`use io_units`
`use format_defs, only: FMT_12, FMT_19`
`use unit_tests`
`use diagnostics`
`use physics_defs, only: SCALAR`
`use lorentz`
`use model_data`
`use flavors`
`use colors`
`use helicities`
`use quantum_numbers`
`use state_matrices`

<Standard module head>

```

    <Polarizations: public>

    <Polarizations: types>

    <Polarizations: interfaces>

contains

    <Polarizations: procedures>

    <Polarizations: tests>

end module polarizations

```

14.1.1 The polarization type

This is not an extension, but rather a restriction of the quantum state. Flavor and color are ignored, there is just a one-particle helicity density matrix.

```

<Polarizations: public>≡
    public :: polarization_t
<Polarizations: types>≡
    type :: polarization_t
        logical :: polarized = .false.
        integer :: spin_type = 0
        integer :: multiplicity = 0
        type(state_matrix_t) :: state
    end type polarization_t

```

14.1.2 Basic initializer and finalizer

We need the particle flavor for determining the allowed helicity values. The density matrix is not set, but prepared to be filled later. This is private.

```

<Polarizations: procedures>≡
    subroutine polarization_init (pol, flv)
        type(polarization_t), intent(out) :: pol
        type(flavor_t), intent(in) :: flv
        pol%spin_type = flv%get_spin_type ()
        pol%multiplicity = flv%get_multiplicity ()
        call pol%state%init (store_values = .true.)
    end subroutine polarization_init

```

The finalizer has to be public. The quantum state contains memory allocated to pointers.

```

<Polarizations: public>+≡
    public :: polarization_final
<Polarizations: procedures>+≡
    subroutine polarization_final (pol)
        type(polarization_t), intent(inout) :: pol
        call pol%state%final ()
    end subroutine polarization_final

```

14.1.3 I/O

<Polarizations: public>+≡

```
public :: polarization_write
```

<Polarizations: procedures>+≡

```
subroutine polarization_write (pol, unit)
  type(polarization_t), intent(in) :: pol
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(1x,A,I1,A,I1,A)") &
    "Polarization: [spin_type = ", pol%spin_type, &
    ", mult = ", pol%multiplicity, "]"
  call pol%state%write (unit=unit)
end subroutine polarization_write
```

Defined assignment: deep copy

<Polarizations: public>+≡

```
public :: assignment(=)
```

<Polarizations: interfaces>≡

```
interface assignment(=)
  module procedure polarization_assign
end interface
```

<Polarizations: procedures>+≡

```
subroutine polarization_assign (pol_out, pol_in)
  type(polarization_t), intent(out) :: pol_out
  type(polarization_t), intent(in) :: pol_in
  pol_out%polarized = pol_in%polarized
  pol_out%spin_type = pol_in%spin_type
  pol_out%multiplicity = pol_in%multiplicity
  pol_out%state = pol_in%state
end subroutine polarization_assign
```

Binary I/O.

<Polarizations: public>+≡

```
public :: polarization_write_raw
public :: polarization_read_raw
```

<Polarizations: procedures>+≡

```
subroutine polarization_write_raw (pol, u)
  type(polarization_t), intent(in) :: pol
  integer, intent(in) :: u
  write (u) pol%polarized
  write (u) pol%spin_type
  write (u) pol%multiplicity
  call pol%state%write_raw (u)
end subroutine polarization_write_raw

subroutine polarization_read_raw (pol, u, iostat)
  type(polarization_t), intent(out) :: pol
  integer, intent(in) :: u
```

```

integer, intent(out), optional :: iostat
read (u, iostat=iostat) pol%polarized
read (u, iostat=iostat) pol%spin_type
read (u, iostat=iostat) pol%multiplicity
call pol%state%read_raw (u, iostat=iostat)
end subroutine polarization_read_raw

```

14.1.4 Accessing contents

Return true if the particle is polarized. This is the case if the first (and only) entry in the quantum state has undefined helicity.

```

(Polarizations: public)+≡
  public :: polarization_is_polarized

(Polarizations: procedures)+≡
  elemental function polarization_is_polarized (pol) result (polarized)
    logical :: polarized
    type(polarization_t), intent(in) :: pol
    polarized = pol%polarized
  end function polarization_is_polarized

```

Return true if the polarization is diagonal, i.e., all entries in the density matrix are diagonal.

```

(Polarizations: public)+≡
  public :: polarization_is_diagonal

(Polarizations: interfaces)+≡
  interface polarization_is_diagonal
    module procedure polarization_is_diagonal0
    module procedure polarization_is_diagonal1
  end interface

(Polarizations: procedures)+≡
  function polarization_is_diagonal0 (pol) result (diagonal)
    logical :: diagonal
    type(polarization_t), intent(in) :: pol
    type(state_iterator_t) :: it
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    diagonal = .true.
    allocate (qn (pol%state%get_depth ()))
    call it%init (pol%state)
    do while (it%is_valid ())
      qn = it%get_quantum_numbers ()
      diagonal = all (qn%are_diagonal ())
      if (.not. diagonal) exit
      call it%advance ()
    end do
  end function polarization_is_diagonal0

  function polarization_is_diagonal1 (pol) result (diagonal)
    type(polarization_t), dimension(:), intent(in) :: pol
    logical, dimension(size(pol)) :: diagonal

```

```

integer :: i
do i = 1, size (pol)
    diagonal(i) = polarization_is_diagonal0 (pol(i))
end do
end function polarization_is_diagonal1

```

14.1.5 Initialization from state matrix

Here, the state matrix is already known (but not necessarily normalized). The result will be either unpolarized, or a normalized spin density matrix.

```

(Polarizations: public)+≡
    public :: polarization_init_state_matrix

(Polarizations: procedures)+≡
    subroutine polarization_init_state_matrix (pol, state)
        type(polarization_t), intent(out) :: pol
        type(state_matrix_t), intent(in), target :: state
        type(state_iterator_t) :: it
        type(flavor_t) :: flv
        type(helicity_t) :: hel
        type(quantum_numbers_t), dimension(1) :: qn
        complex(default) :: value, t
        call it%init (state)
        flv = it%get_flavor (1)
        hel = it%get_helicity (1)
        if (hel%is_defined ()) then
            call polarization_init (pol, flv)
            pol%polarized = .true.
            t = 0
            do while (it%is_valid ())
                hel = it%get_helicity (1)
                call qn(1)%init (hel)
                value = it%get_matrix_element ()
                call pol%state%add_state (qn, value=value)
                if (hel%is_diagonal ()) t = t + value
                call it%advance ()
            end do
            call pol%state%freeze ()
            if (t /= 0) call pol%state%renormalize (1._default / t)
        else
            call polarization_init_unpolarized (pol, flv)
        end if
    end subroutine polarization_init_state_matrix

```

14.1.6 Specific initializers

Unpolarized particle, no helicity labels in the density matrix. The value is specified as $1/N$, where N is the multiplicity.

Exception: for left-handed or right-handed particles (neutrinos), polarization is always circular with fraction unity.

```

(Polarizations: public)+≡

```

```

public :: polarization_init_unpolarized
<Polarizations: procedures>+≡
subroutine polarization_init_unpolarized (pol, flv)
  type(polarization_t), intent(inout) :: pol
  type(flavor_t), intent(in) :: flv
  type(quantum_numbers_t), dimension(1) :: qn
  complex(default) :: value
  if (flv%is_left_handed ()) then
    call polarization_init_circular (pol, flv, -1._default)
  else if (flv%is_right_handed ()) then
    call polarization_init_circular (pol, flv, 1._default)
  else
    call polarization_init (pol, flv)
    value = 1._default / flv%get_multiplicity ()
    call pol%state%add_state (qn)
    call pol%state%freeze ()
    call pol%state%set_matrix_element (value)
  end if
end subroutine polarization_init_unpolarized

```

Unpolarized particle, but explicit density matrix with helicity states allocated according to given flavor. Note that fermions have even spin type, bosons odd. The spin density matrix entries are scaled by `fraction`. This is used for initializing other polarizations:

$$\rho(f) = \frac{|f|}{N} \mathbf{1}.$$

```

<Polarizations: public>+≡
public :: polarization_init_trivial
<Polarizations: procedures>+≡
subroutine polarization_init_trivial (pol, flv, fraction)
  type(polarization_t), intent(out) :: pol
  type(flavor_t), intent(in) :: flv
  real(default), intent(in), optional :: fraction
  type(helicity_t) :: hel
  type(quantum_numbers_t), dimension(1) :: qn
  integer :: h, hmax
  logical :: fermion
  complex(default) :: value
  call polarization_init (pol, flv)
  pol%polarized = .true.
  if (present (fraction)) then
    value = fraction / pol%multiplicity
  else
    value = 1._default / pol%multiplicity
  end if
  fermion = mod (pol%spin_type, 2) == 0
  hmax = pol%spin_type / 2
  select case (pol%multiplicity)
  case (1)
    if (flv%is_left_handed ()) then
      call hel%init (-hmax)
    else if (flv%is_right_handed ()) then

```

```

        call hel%init (hmax)
    else
        call hel%init (0)
    end if
    call qn(1)%init (hel)
    call pol%state%add_state (qn)
case (2)
    do h = -hmax, hmax, 2*hmax
        call hel%init (h)
        call qn(1)%init (hel)
        call pol%state%add_state (qn)
    end do
case default
    do h = -hmax, hmax
        if (fermion .and. h == 0) cycle
        call hel%init (h)
        call qn(1)%init (hel)
        call pol%state%add_state (qn)
    end do
end select
call pol%state%freeze ()
call pol%state%set_matrix_element (value)
end subroutine polarization_init_trivial

```

The following three modes are useful mainly for spin-1/2 particle and massless particles of any nonzero spin. Only the highest-weight components are filled.

Circular polarization: The density matrix of the two highest-weight states is

$$\rho(f) = \frac{1 - |f|}{2} \mathbf{1} + |f| \times \begin{cases} \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}, & f > 0; \\ \begin{pmatrix} 0 & 0 \\ 0 & 1 \end{pmatrix}, & f < 0, \end{cases}$$

If the polarization fraction $|f|$ is unity, we need only one entry in the density matrix.

<Polarizations: public>+≡

```
public :: polarization_init_circular
```

<Polarizations: procedures>+≡

```

subroutine polarization_init_circular (pol, flv, fraction)
    type(polarization_t), intent(out) :: pol
    type(flavor_t), intent(in) :: flv
    real(default), intent(in) :: fraction
    type(helicity_t), dimension(2) :: hel
    type(quantum_numbers_t), dimension(1) :: qn
    complex(default) :: value
    integer :: hmax
    call polarization_init (pol, flv)
    pol%polarized = .true.
    hmax = pol%spin_type / 2
    call hel(1)%init ( hmax)
    call hel(2)%init (-hmax)
    if (abs (fraction) /= 1) then

```

```

        value = (1 + fraction) / 2
        call qn(1)%init (hel(1))
        call pol%state%add_state (qn, value=value)
        value = (1 - fraction) / 2
        call qn(1)%init (hel(2))
        call pol%state%add_state (qn, value=value)
    else
        value = abs (fraction)
        if (fraction > 0) then
            call qn(1)%init (hel(1))
        else
            call qn(1)%init (hel(2))
        end if
        call pol%state%add_state (qn, value=value)
    end if
    call pol%state%freeze ()
end subroutine polarization_init_circular

```

Transversal polarization is analogous to circular, but we get a density matrix

$$\rho(f, \phi) = \frac{1 - |f|}{2} \mathbf{1} + \frac{|f|}{2} \begin{pmatrix} 1 & e^{-i\phi} \\ e^{i\phi} & 1 \end{pmatrix}.$$

The phase is $\phi = 0$ for the x -axis, $\phi = 90^\circ$ for the y axis as polarization vector. For an antiparticle, the phase switches sign, and for $f < 0$, the off-diagonal elements switch sign.

```

<Polarizations: public>+≡
    public :: polarization_init_transversal

<Polarizations: procedures>+≡
    subroutine polarization_init_transversal (pol, flv, phi, fraction)
        type(polarization_t), intent(inout) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: phi, fraction
        call polarization_init_axis &
            (pol, flv, fraction * [ cos (phi), sin (phi), 0._default])
    end subroutine polarization_init_transversal

```

For axis polarization, we again set only the entries with maximum weight.

$$\rho(f, \phi) = \frac{1}{2} \begin{pmatrix} 1 + \alpha_3 & \alpha_1 - i\alpha_2 \\ \alpha_1 + i\alpha_2 & 1 - \alpha_3 \end{pmatrix}.$$

For an antiparticle, α_2 switches sign (complex conjugate).

```

<Polarizations: public>+≡
    public :: polarization_init_axis

<Polarizations: procedures>+≡
    subroutine polarization_init_axis (pol, flv, alpha)
        type(polarization_t), intent(out) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), dimension(3), intent(in) :: alpha
        type(quantum_numbers_t), dimension(1) :: qn
        type(helicity_t), dimension(2,2) :: hel

```



```

complex(default), dimension(2,2) :: value
integer :: hmax
call polarization_init (pol, flv)
pol%polarized = .true.
hmax = pol%spin_type / 2
call hel(1,1)%init ( hmax, hmax)
call hel(1,2)%init ( hmax,-hmax)
call hel(2,1)%init (-hmax, hmax)
call hel(2,2)%init (-hmax,-hmax)
value(1,1) = (1 + alpha(3)) / 2
value(2,2) = (1 - alpha(3)) / 2
if (flv%is_antiparticle ()) then
    value(1,2) = (alpha(1) + imago * alpha(2)) / 2
else
    value(1,2) = (alpha(1) - imago * alpha(2)) / 2
end if
value(2,1) = conjg (value(1,2))
if (value(1,1) /= 0) then
    call qn(1)%init (hel(1,1))
    call pol%state%add_state (qn, value=value(1,1))
end if
if (value(2,2) /= 0) then
    call qn(1)%init (hel(2,2))
    call pol%state%add_state (qn, value=value(2,2))
end if
if (value(1,2) /= 0) then
    call qn(1)%init (hel(1,2))
    call pol%state%add_state (qn, value=value(1,2))
    call qn(1)%init (hel(2,1))
    call pol%state%add_state (qn, value=value(2,1))
end if
call pol%state%freeze ()
end subroutine polarization_init_axis

```

This version specifies the polarization axis in terms of r (polarization degree) and θ, ϕ (polar and azimuthal angles).

If one of the angles is a nonzero multiple of π , roundoff errors typically will result in tiny contributions to unwanted components. Therefore, include a catch for small numbers.

```

<Polarizations: public>+≡
    public :: polarization_init_angles

<Polarizations: procedures>+≡
    subroutine polarization_init_angles (pol, flv, r, theta, phi)
        type(polarization_t), intent(out) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: r, theta, phi
        real(default), dimension(3) :: alpha
        real(default), parameter :: eps = 10 * epsilon (1._default)
        alpha(1) = r * sin (theta) * cos (phi)
        alpha(2) = r * sin (theta) * sin (phi)
        alpha(3) = r * cos (theta)
        where (abs (alpha) < eps) alpha = 0
        call polarization_init_axis (pol, flv, alpha)
    end subroutine polarization_init_angles

```

```
end subroutine polarization_init_angles
```

Longitudinal polarization is defined only for massive bosons. Only the zero component is filled. Otherwise, unpolarized.

<Polarizations: public>+≡

```
public :: polarization_init_longitudinal
```

<Polarizations: procedures>+≡

```
subroutine polarization_init_longitudinal (pol, flv, fraction)
  type(polarization_t), intent(out) :: pol
  type(flavor_t), intent(in) :: flv
  real(default), intent(in) :: fraction
  integer :: spin_type, multiplicity
  type(helicity_t) :: hel
  type(quantum_numbers_t), dimension(1) :: qn
  complex(default) :: value
  integer :: n_values
  value = abs (fraction)
  spin_type = flv%get_spin_type ()
  multiplicity = flv%get_multiplicity ()
  if (mod (spin_type, 2) == 1 .and. multiplicity > 2) then
    if (fraction /= 1) then
      call polarization_init_trivial (pol, flv, 1 - fraction)
      n_values = pol%state%get_n_matrix_elements ()
      call pol%state%add_to_matrix_element (n_values/2 + 1, value)
    else
      call polarization_init (pol, flv)
      pol%polarized = .true.
      call hel%init (0)
      call qn(1)%init (hel)
      call pol%state%add_state (qn)
      call pol%state%freeze ()
      call pol%state%set_matrix_element (value)
    end if
  else
    call polarization_init_unpolarized (pol, flv)
  end if
end subroutine polarization_init_longitudinal
```

This is diagonal polarization: we specify all components explicitly. We use only the positive components. The sum is normalized to unity. We assume that the length of `alpha` is equal to the particle multiplicity.

<Polarizations: public>+≡

```
public :: polarization_init_diagonal
```

<Polarizations: procedures>+≡

```
subroutine polarization_init_diagonal (pol, flv, alpha)
  type(polarization_t), intent(inout) :: pol
  type(flavor_t), intent(in) :: flv
  real(default), dimension(:), intent(in) :: alpha
  type(helicity_t) :: hel
  type(quantum_numbers_t), dimension(1) :: qn
  logical, dimension(size(alpha)) :: mask
  real(default) :: norm
```

```

complex(default), dimension(:), allocatable :: value
logical :: fermion
integer :: h, hmax, i
mask = alpha > 0
norm = sum (alpha, mask); if (norm == 0) norm = 1
allocate (value (count (mask)))
value = pack (alpha / norm, mask)
call polarization_init (pol, flv)
pol%polarized = .true.
fermion = mod (pol%spin_type, 2) == 0
hmax = pol%spin_type / 2
i = 0
select case (pol%multiplicity)
case (1)
  if (flv%is_left_handed ()) then
    call hel%init (-hmax)
  else if (flv%is_right_handed ()) then
    call hel%init ( hmax)
  else
    call hel%init (0)
  end if
  call qn(1)%init (hel)
  call pol%state%add_state (qn)
case (2)
  do h = -hmax, hmax, 2*hmax
    i = i + 1
    if (mask(i)) then
      call hel%init (h)
      call qn(1)%init (hel)
      call pol%state%add_state (qn)
    end if
  end do
case default
  do h = -hmax, hmax
    if (fermion .and. h == 0) cycle
    i = i + 1
    if (mask(i)) then
      call hel%init (h)
      call qn(1)%init (hel)
      call pol%state%add_state (qn)
    end if
  end do
end select
call pol%state%freeze ()
call pol%state%set_matrix_element (value)
end subroutine polarization_init_diagonal

```

Generic polarization: we generate all possible density matrix entries, but the values are left zero.

```

<Polarizations: public>+≡
  public :: polarization_init_generic

<Polarizations: procedures>+≡
  subroutine polarization_init_generic (pol, flv)

```

```

type(polarization_t), intent(out) :: pol
type(flavor_t), intent(in) :: flv
type(helicity_t) :: hel
type(quantum_numbers_t), dimension(1) :: qn
logical :: fermion
integer :: hmax, h1, h2
call polarization_init (pol, flv)
pol%polarized = .true.
fermion = mod (pol%spin_type, 2) == 0
hmax = pol%spin_type / 2
select case (pol%multiplicity)
case (1)
  if (flv%is_left_handed ()) then
    call hel%init (-hmax)
  else if (flv%is_right_handed ()) then
    call hel%init ( hmax)
  else
    call hel%init (0)
  end if
  call qn(1)%init (hel)
  call pol%state%add_state (qn)
case (2)
  do h1 = -hmax, hmax, 2*hmax
    do h2 = -hmax, hmax, 2*hmax
      call hel%init (h1, h2)
      call qn(1)%init (hel)
      call pol%state%add_state (qn)
    end do
  end do
case default
  do h1 = -hmax, hmax
    if (fermion .and. h1 == 0) cycle
    do h2 = -hmax, hmax
      if (fermion .and. h2 == 0) cycle
      call hel%init (h1, h2)
      call qn(1)%init (hel)
      call pol%state%add_state (qn)
    end do
  end do
end select
call pol%state%freeze ()
end subroutine polarization_init_generic

```

14.1.7 Operations

Combine polarization states by computing the outer product of the state matrices.

```

(Polarizations: public)+≡
  public :: combine_polarization_states

(Polarizations: procedures)+≡
  subroutine combine_polarization_states (pol, state)
    type(polarization_t), dimension(:), intent(in), target :: pol

```

```

    type(state_matrix_t), intent(out) :: state
    call outer_multiply (pol%state, state)
end subroutine combine_polarization_states

```

Transform a polarization density matrix into a polarization vector. This is possible without information loss only for spin-1/2 and for massless particles. To get a unique answer in all cases, we consider only the components with highest weight. Obviously, this loses the longitudinal component of a massive vector, for instance.

This is the inverse operation of `polarization_init_axis` above, where the polarization fraction is set to unity.

```

<Polarizations: public>+≡
    public :: polarization_get_axis

<Polarizations: procedures>+≡
    function polarization_get_axis (pol) result (alpha)
        real(default), dimension(3) :: alpha
        type(polarization_t), intent(in), target :: pol
        type(state_iterator_t) :: it
        complex(default), dimension(2,2) :: value
        type(helicity_t), dimension(2,2) :: hel
        type(helicity_t), dimension(1) :: hel1
        integer :: hmax, i, j
        if (pol%polarized) then
            hmax = pol%spin_type / 2
            call hel(1,1)%init ( hmax, hmax)
            call hel(1,2)%init ( hmax,-hmax)
            call hel(2,1)%init (-hmax, hmax)
            call hel(2,2)%init (-hmax,-hmax)
            value = 0
            call it%init (pol%state)
            do while (it%is_valid ())
                hel1 = it%get_helicity ()
                SCAN_HEL: do i = 1, 2
                    do j = 1, 2
                        if (hel1(1) == hel(i,j)) then
                            value(i,j) = it%get_matrix_element ()
                            exit SCAN_HEL
                        end if
                    end do
                end do SCAN_HEL
                call it%advance ()
            end do
            alpha(1) = real(value(1,2) + value(2,1))
            alpha(2) = - aimag(value(1,2) - value(2,1))
            alpha(3) = real(value(1,1) - value(2,2))
        else
            alpha = 0
        end if
    end function polarization_get_axis

```

This function returns polarization degree and polar and azimuthal angles (θ, ϕ) of the polarization axis.

```

<Polarizations: public>+≡
    public :: polarization_to_angles

<Polarizations: procedures>+≡
    subroutine polarization_to_angles (pol, r, theta, phi)
        type(polarization_t), intent(in) :: pol
        real(default), intent(out) :: r, theta, phi
        real(default), dimension(3) :: alpha
        real(default) :: r12
        if (pol%polarized) then
            alpha = polarization_get_axis (pol)
            r = sqrt (sum (alpha**2))
            if (any (alpha /= 0)) then
                r12 = sqrt (alpha(1)**2 + alpha(2)**2)
                theta = atan2 (r12, alpha(3))
                if (any (alpha(1:2) /= 0)) then
                    phi = atan2 (alpha(2), alpha(1))
                else
                    phi = 0
                end if
            else
                theta = 0
            end if
        else
            r = 0
            theta = 0
            phi = 0
        end if
    end subroutine polarization_to_angles

```

14.1.8 Sparse Matrix

We introduce a simpler implementation of a sparse matrix that should represent polarization. It consists of an integer array that represents the index values, and a complex array that represents the nonvanishing entries. The number of nonvanishing entries must be known for initialization, but the entries are filled one at a time.

This should eventually replace the more baroque polarization definition above, but in the first stage we introduce it just as an intermedial storage container.

Here is a base type without the special properties of a spin-density matrix.

```

<Polarizations: public>+≡
    public :: smatrix_t

<Polarizations: types>+≡
    type :: smatrix_t
        private
        integer :: dim = 0
        integer :: n_entry = 0
        integer, dimension(:,:), allocatable :: index
        complex(default), dimension(:), allocatable :: value
    contains
    <Polarizations: smatrix: TBP>

```

```
end type smatrix_t
```

Output.

```
<Polarizations: smatrix: TBP>≡
  procedure :: write => smatrix_write

<Polarizations: procedures>+≡
  subroutine smatrix_write (object, unit, indent)
    class(smatrix_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    integer :: u, i, ind
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    if (allocated (object%value)) then
      if (size (object%value) > 0) then
        do i = 1, object%n_entry
          write (u, "(1x,A,'@(')", advance="no") repeat (" ", ind)
          write (u, "(SP,9999(I2.1,':',1x))", advance="no") &
            object%index(:,i)
          write (u, "('(', " // FMT_19 // ",','," // FMT_19 // &
            ",')')'") object%value(i)
        end do
      else
        write (u, "(1x,A)", advance="no") repeat (" ", ind)
        write (u, "(A)" " [empty matrix]"
      end if
    else
      write (u, "(1x,A)", advance="no") repeat (" ", ind)
      write (u, "(A)" " [undefined matrix]"
    end if
  end subroutine smatrix_write
```

Initialization: allocate arrays to the correct size. We specify both the dimension of the matrix (if different from two, this is rather a generic tensor) and the number of nonvanishing entries.

```
<Polarizations: smatrix: TBP>+≡
  procedure :: init => smatrix_init

<Polarizations: procedures>+≡
  subroutine smatrix_init (smatrix, dim, n_entry)
    class(smatrix_t), intent(out) :: smatrix
    integer, intent(in) :: dim
    integer, intent(in) :: n_entry
    smatrix%dim = dim
    smatrix%n_entry = n_entry
    allocate (smatrix%index (dim, n_entry))
    allocate (smatrix%value (n_entry))
  end subroutine smatrix_init
```

Fill: one entry at a time.

```
<Polarizations: smatrix: TBP>+≡
  procedure :: set_entry => smatrix_set_entry
```

```

<Polarizations: procedures>+≡
subroutine smatrix_set_entry (smatrix, i, index, value)
  class(smatrix_t), intent(inout) :: smatrix
  integer, intent(in) :: i
  integer, dimension(:), intent(in) :: index
  complex(default), intent(in) :: value
  smatrix%index(:,i) = index
  smatrix%value(i) = value
end subroutine smatrix_set_entry

```

14.1.9 Polarization Matrix

As an extension of the more generic `smatrix` type, we implement a proper spin-density matrix. After the matrix has been filled, we can fix spin type and multiplicity for a particle, check the matrix for consistency, and normalize it if necessary.

```

<Polarizations: public>+≡
public :: pmatrix_t

<Polarizations: types>+≡
type, extends (smatrix_t) :: pmatrix_t
  private
  integer :: spin_type = 0
  integer :: multiplicity = 0
  logical :: massive = .true.
  integer :: chirality = 0
  real(default) :: degree = 1
  logical :: pure = .false.
  contains
  <Polarizations: pmatrix: TBP>
end type pmatrix_t

```

Output, including extra data. (The `indent` argument is ignored.)

```

<Polarizations: pmatrix: TBP>≡
procedure :: write => pmatrix_write

<Polarizations: procedures>+≡
subroutine pmatrix_write (object, unit, indent)
  class(pmatrix_t), intent(in) :: object
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)") "Polarization: spin density matrix"
  write (u, "(3x,A,I0)") "spin type      = ", object%spin_type
  write (u, "(3x,A,I0)") "multiplicity = ", object%multiplicity
  write (u, "(3x,A,L1)") "massive     = ", object%massive
  write (u, "(3x,A,I0)") "chirality   = ", object%chirality
  write (u, "(3x,A,F10.7)") "pol.degree  = ", object%degree
  write (u, "(3x,A,L1)") "pure state  = ", object%pure
  call object%smatrix_t%write (u, 1)
end subroutine pmatrix_write

```


This assignment is trivial, but must be coded explicitly.

```

(Polarizations: pmatrix: TBP)+≡
  generic :: assignment(=) => pmatrix_assign_from_smatrix
  procedure, private :: pmatrix_assign_from_smatrix

(Polarizations: procedures)+≡
  subroutine pmatrix_assign_from_smatrix (pmatrix, smatrix)
    class(pmatrix_t), intent(out) :: pmatrix
    type(smatrix_t), intent(in) :: smatrix
    pmatrix%smatrix_t = smatrix
  end subroutine pmatrix_assign_from_smatrix

```

Declare spin, multiplicity, and polarization degree. Check whether all entries fit, and whether this is a valid matrix.

The required properties are:

1. all entries apply to the given spin and mass type
2. the diagonal is real
3. only the upper of corresponding off-diagonal elements is specified, i.e., the row index is less than the column index
4. the trace is nonnegative and equal to the polarization degree (the remainder, proportional to the unit matrix, is understood to be present)
5. the trace of the matrix square is positive and less or equal to the trace of the matrix itself, which is the polarization degree. (If it is equal, we are dealing with a pure state).

```

(Polarizations: pmatrix: TBP)+≡
  procedure :: normalize => pmatrix_normalize

(Polarizations: procedures)+≡
  subroutine pmatrix_normalize (pmatrix, flv, degree, tolerance)
    class(pmatrix_t), intent(inout) :: pmatrix
    type(flavor_t), intent(in) :: flv
    real(default), intent(in), optional :: degree
    real(default), intent(in), optional :: tolerance
    integer :: i, hmax
    logical :: fermion, ok
    real(default) :: trace, trace_sq
    real(default) :: tol
    tol = 0; if (present (tolerance)) tol = tolerance
    pmatrix%spin_type = flv%get_spin_type ()
    pmatrix%massive = flv%get_mass () /= 0
    if (.not. pmatrix%massive) then
      if (flv%is_left_handed ()) then
        pmatrix%chirality = -1
      else if (flv%is_right_handed ()) then
        pmatrix%chirality = +1
      end if
    end if
    if (pmatrix%spin_type == SCALAR) then
      pmatrix%multiplicity = 1
    end if
  end subroutine pmatrix_normalize

```

```

else if (pmatrx%massive) then
    pmatrx%multiplicity = pmatrx%spin_type
else if (pmatrx%chirality == 0) then
    pmatrx%multiplicity = 2
else
    pmatrx%multiplicity = 1
end if
if (present (degree)) then
    if (degree < 0 .or. degree > 1) &
        call msg_error ("polarization degree must be between 0 and 1")
    pmatrx%degree = degree
end if
if (size (pmatrx%index, 1) /= 2) call error ("wrong array rank")
fermion = mod (pmatrx%spin_type, 2) == 0
hmax = pmatrx%spin_type / 2
if (pmatrx%n_entry > 0) then
    if (fermion) then
        if (pmatrx%massive) then
            ok = all (pmatrx%index /= 0) &
                .and. all (abs (pmatrx%index) <= hmax)
        else if (pmatrx%chirality == -1) then
            ok = all (pmatrx%index == -hmax)
        else if (pmatrx%chirality == +1) then
            ok = all (pmatrx%index == +hmax)
        else
            ok = all (abs (pmatrx%index) == hmax)
        end if
    else
        if (pmatrx%massive) then
            ok = all (abs (pmatrx%index) <= hmax)
        else
            ok = all (abs (pmatrx%index) == hmax)
        end if
    end if
    if (.not. ok) call error ("illegal index value")
else
    pmatrx%degree = 0
    pmatrx%pure = pmatrx%multiplicity == 1
    return
end if
trace = 0
do i = 1, pmatrx%n_entry
    associate (index => pmatrx%index(:,i), value => pmatrx%value(i))
        if (index(1) == index(2)) then
            if (abs (aimag (value)) > tol) call error ("diagonal must be real")
            value = real (value, kind=default)
            trace = trace + value

            else if (any (pmatrx%index(1,:) == index(2) &
                .and. pmatrx%index(2,:) == index(1))) then
                call error ("redundant off-diagonal entry")
            else if (index(2) < index (1)) then
                index = index([2,1])
                value = conjg (value)
            end if
        end associate
    end do

```

```

        end if
    end associate
end do
if (abs (trace) <= tol) call error ("trace must not vanish")
trace = real (trace, kind=default)
pmatrx%value = pmatrx%value / trace * pmatrx%degree
trace_sq = (1 - pmatrx%degree ** 2) / pmatrx%multiplicity
do i = 1, pmatrx%n_entry
    associate (index => pmatrx%index(:,i), value => pmatrx%value(i))
        if (index(1) == index(2)) then
            trace_sq = trace_sq + abs (value) ** 2
        else
            trace_sq = trace_sq + 2 * abs (value) ** 2
        end if
    end associate
end do
if (pmatrx%multiplicity == 1) then
    pmatrx%pure = .true.
else if (abs (trace_sq - 1) <= tol) then
    pmatrx%pure = .true.
else if (trace_sq - 1 > tol .or. trace_sq < -tol) then
    print *, "Trace of matrix square = ", trace_sq
    call error ("not permissible as density matrix")
end if
contains
subroutine error (msg)
    character(*), intent(in) :: msg
    call pmatrx%write ()
    call msg_fatal ("Spin density matrix: " // msg)
end subroutine error
end subroutine pmatrx_normalize

```

A polarized matrix is defined as one with a positive polarization degree, even if the actual matrix is trivial.

```

<Polarizations: pmatrx: TBP>+≡
    procedure :: is_polarized => pmatrx_is_polarized

<Polarizations: procedures>+≡
    elemental function pmatrx_is_polarized (pmatrx) result (flag)
        class(pmatrx_t), intent(in) :: pmatrx
        logical :: flag
        flag = pmatrx%degree > 0
    end function pmatrx_is_polarized

```

Check if there are only diagonal entries.

```

<Polarizations: pmatrx: TBP>+≡
    procedure :: is_diagonal => pmatrx_is_diagonal

<Polarizations: procedures>+≡
    elemental function pmatrx_is_diagonal (pmatrx) result (flag)
        class(pmatrx_t), intent(in) :: pmatrx
        logical :: flag
        flag = all (pmatrx%index(1,:) == pmatrx%index(2,:))
    end function pmatrx_is_diagonal

```

14.1.10 Data Translation

Create a `polarization_t` object from the contents of a normalized `pmatrix_t` object.

Note for off diagonal entries: the convention for the arguments of `helicity_init` is (h2,h1), so the helicity of the conjugate state is inserted first.

```

(Polarizations: public)+≡
    public :: polarization_init_pmatrix

(Polarizations: procedures)+≡
    subroutine polarization_init_pmatrix (pol, pmatrix)
        type(polarization_t), intent(out) :: pol
        type(pmatrix_t), intent(in) :: pmatrix
        type(quantum_numbers_t), dimension(1) :: qn
        type(helicity_t) :: hel
        integer :: i, h, h1, h2, hmin, hmax, dh
        logical :: fermion
        complex(default) :: value
        pol%polarized = .true.
        pol%spin_type = pmatrix%spin_type
        pol%multiplicity = pmatrix%multiplicity
        call pol%state%init (store_values = .true.)
        fermion = mod (pol%spin_type, 2) == 0
        h = pol%spin_type / 2
        select case (pmatrix%chirality)
        case (-1)
            hmin = -h
            hmax = -h
        case (0)
            hmin = -h
            hmax = h
        case (1)
            hmin = h
            hmax = h
        end select
        if (pol%multiplicity == 1) then
            dh = 1
        else if (pol%multiplicity == 2) then
            dh = hmax - hmin
        else
            dh = 1
        end if
        if (pmatrix%degree < 1) then
            value = (1 - pmatrix%degree) / pol%multiplicity
            do h = hmin, hmax, dh
                if (h == 0 .and. fermion) cycle
                call hel%init (h)
                call qn(1)%init (hel)
                call pol%state%add_state (qn, value = value)
            end do
        end if
        do i = 1, pmatrix%n_entry

```

```

associate (index => pmatrix%index(:,i), value => pmatrix%value(i))
  h1 = index(1)
  h2 = index(2)
  if (h1 == h2) then
    call hel%init (h1)
    call qn(1)%init (hel)
    call pol%state%add_state (qn, value = value, &
      sum_values = .true.)
  else
    call hel%init (h2, h1)
    call qn(1)%init (hel)
    call pol%state%add_state (qn, value = value)
    call hel%init (h1, h2)
    call qn(1)%init (hel)
    call pol%state%add_state (qn, value = conjg (value))
  end if
end associate
end do
call pol%state%freeze ()
end subroutine polarization_init_pmatrix

```

14.1.11 Unit tests

```

<Polarizations: public>+≡
  public :: polarization_test

<Polarizations: procedures>+≡
  subroutine polarization_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Polarizations: execute tests>
  end subroutine polarization_test

```

Polarization type

Checking the setup for polarization.

```

<Polarizations: execute tests>≡
  call test (polarization_1, "polarization_1", &
    "check polarization setup", &
    u, results)

<Polarizations: tests>≡
  subroutine polarization_1 (u)
    use os_interface
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(polarization_t) :: pol
    type(flavor_t) :: flv
    real(default), dimension(3) :: alpha
    real(default) :: r, theta, phi

```

```

write (u, "(A)")  "* Test output: polarization_1"
write (u, "(A)")  "* Purpose: test polarization setup"
write (u, "(A)")

write (u, "(A)")  "* Reading model file"
write (u, "(A)")

call model%init_sm_test ()

write (u, "(A)")  "* Unpolarized fermion"
write (u, "(A)")

call flv%init (1, model)
call polarization_init_unpolarized (pol, flv)
call polarization_write (pol, u)
write (u, "(A,L1)")  " diagonal =", polarization_is_diagonal (pol)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Unpolarized fermion"
write (u, "(A)")

call polarization_init_circular (pol, flv, 0._default)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Transversally polarized fermion, phi=0"
write (u, "(A)")

call polarization_init_transversal (pol, flv, 0._default, 1._default)
call polarization_write (pol, u)
write (u, "(A,L1)")  " diagonal =", polarization_is_diagonal (pol)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Transversally polarized fermion, phi=0.9, frac=0.8"
write (u, "(A)")

call polarization_init_transversal (pol, flv, 0.9_default, 0.8_default)
call polarization_write (pol, u)
write (u, "(A,L1)")  " diagonal =", polarization_is_diagonal (pol)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* All polarization directions of a fermion"
write (u, "(A)")

call polarization_init_generic (pol, flv)
call polarization_write (pol, u)
call polarization_final (pol)
call flv%init (21, model)

write (u, "(A)")

```

```

write (u, "(A)")  "* Circularly polarized gluon, frac=0.3"
write (u, "(A)")

call polarization_init_circular (pol, flv, 0.3_default)
call polarization_write (pol, u)
call polarization_final (pol)
call flv%init (23, model)

write (u, "(A)")
write (u, "(A)")  "* Circularly polarized massive vector, frac=-0.7"
write (u, "(A)")

call polarization_init_circular (pol, flv, -0.7_default)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Circularly polarized massive vector"
write (u, "(A)")

call polarization_init_circular (pol, flv, 1._default)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Longitudinally polarized massive vector, frac=0.4"
write (u, "(A)")

call polarization_init_longitudinal (pol, flv, 0.4_default)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Longitudinally polarized massive vector"
write (u, "(A)")

call polarization_init_longitudinal (pol, flv, 1._default)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Diagonally polarized massive vector"
write (u, "(A)")

call polarization_init_diagonal &
    (pol, flv, [0._default, 1._default, 2._default])
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* All polarization directions of a massive vector"
write (u, "(A)")

call polarization_init_generic (pol, flv)

```

```

call polarization_write (pol, u)
call polarization_final (pol)
call flv%init (21, model)

write (u, "(A)")
write (u, "(A)")  "* Axis polarization (0.2, 0.4, 0.6)"
write (u, "(A)")

alpha = [0.2_default, 0.4_default, 0.6_default]
call polarization_init_axis (pol, flv, alpha)
call polarization_write (pol, u)

write (u, "(A)")  "   Recovered axis:"
alpha = polarization_get_axis (pol)
write (u, "(A)")  "   Angle polarization (0.5, 0.6, -1)"
r = 0.5_default
theta = 0.6_default
phi = -1._default
call polarization_init_angles (pol, flv, r, theta, phi)
call polarization_write (pol, u)
write (u, "(A)")  "   Recovered parameters (r, theta, phi):"
call polarization_to_angles (pol, r, theta, phi)
write (u, "(A,3(1x," // FMT_12 // "))")  "   ", r, theta, phi
call polarization_final (pol)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: polarization_1"

end subroutine polarization_1

```

Sparse-Matrix type

Use a sparse density matrix universally as the input for setting up polarization.

```

<Polarizations: execute tests>+≡
call test (polarization_2, "polarization_2", &
  "matrix polarization setup", &
  u, results)

<Polarizations: tests>+≡
subroutine polarization_2 (u)
  use os_interface
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(flavor_t) :: flv
  type(polarization_t) :: pol
  real(default), dimension(3) :: alpha
  type(pmatrix_t) :: pmatrix
  real(default), parameter :: tolerance = 1e-8_default

  write (u, "(A)")  "* Test output: polarization_2"
  write (u, "(A)")  "*   Purpose: matrix polarization setup"

```



```

write (u, "(A)")

write (u, "(A)")  "* Reading model file"
write (u, "(A)")

call model%init_sm_test ()

write (u, "(A)")  "* Unpolarized fermion"
write (u, "(A)")

call flv%init (1, model)
call pmatrix%init (2, 0)
call pmatrix%normalize (flv, 0._default, tolerance)
call pmatrix%write (u)
write (u, *)
write (u, "(1x,A,L1)")  "polarized = ", pmatrix%is_polarized ()
write (u, "(1x,A,L1)")  "diagonal = ", pmatrix%is_diagonal ()
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Transversally polarized fermion, phi=0"
write (u, "(A)")

call pmatrix%init (2, 3)
call pmatrix%set_entry (1, [-1,-1], (1._default, 0._default))
call pmatrix%set_entry (2, [+1,+1], (1._default, 0._default))
call pmatrix%set_entry (3, [-1,+1], (1._default, 0._default))
call pmatrix%normalize (flv, 1._default, tolerance)
call pmatrix%write (u)
write (u, *)
write (u, "(1x,A,L1)")  "polarized = ", pmatrix%is_polarized ()
write (u, "(1x,A,L1)")  "diagonal = ", pmatrix%is_diagonal ()
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Transversally polarized fermion, phi=0.9, frac=0.8"
write (u, "(A)")

call pmatrix%init (2, 3)
call pmatrix%set_entry (1, [-1,-1], (1._default, 0._default))
call pmatrix%set_entry (2, [+1,+1], (1._default, 0._default))
call pmatrix%set_entry (3, [-1,+1], exp ((0._default, -0.9_default)))
call pmatrix%normalize (flv, 0.8_default, tolerance)
call pmatrix%write (u)
write (u, *)

```

```

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Left-handed massive fermion, frac=1"
write (u, "(A)")

call flv%init (11, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [-1,-1], (1._default, 0._default))
call pmatrix%normalize (flv, 1._default, tolerance)
call pmatrix%write (u)
write (u, *)
write (u, "(1x,A,L1)")  "polarized = ", pmatrix%is_polarized ()
write (u, "(1x,A,L1)")  "diagonal = ", pmatrix%is_diagonal ()
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Left-handed massive fermion, frac=0.8"
write (u, "(A)")

call flv%init (11, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [-1,-1], (1._default, 0._default))
call pmatrix%normalize (flv, 0.8_default, tolerance)
call pmatrix%write (u)
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Left-handed massless fermion"
write (u, "(A)")

call flv%init (12, model)
call pmatrix%init (2, 0)
call pmatrix%normalize (flv, 1._default, tolerance)
call pmatrix%write (u)
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Right-handed massless fermion, frac=0.5"
write (u, "(A)")

```

```

call flv%init (-12, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [1,1], (1._default, 0._default))
call pmatrix%normalize (flv, 0.5_default, tolerance)
call pmatrix%write (u)
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Circularly polarized gluon, frac=0.3"
write (u, "(A)")

call flv%init (21, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [1,1], (1._default, 0._default))
call pmatrix%normalize (flv, 0.3_default, tolerance)
call pmatrix%write (u)
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Circularly polarized massive vector, frac=0.7"
write (u, "(A)")

call flv%init (23, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [1,1], (1._default, 0._default))
call pmatrix%normalize (flv, 0.7_default, tolerance)
call pmatrix%write (u)
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Circularly polarized massive vector"
write (u, "(A)")

call flv%init (23, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [1,1], (1._default, 0._default))
call pmatrix%normalize (flv, 1._default, tolerance)
call pmatrix%write (u)
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)

```

```

call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Longitudinally polarized massive vector, frac=0.4"
write (u, "(A)")

call flv%init (23, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [0,0], (1._default, 0._default))
call pmatrix%normalize (flv, 0.4_default, tolerance)
call pmatrix%write (u)
write (u, *)
write (u, "(1x,A,L1)")  "polarized = ", pmatrix%is_polarized ()
write (u, "(1x,A,L1)")  "diagonal = ", pmatrix%is_diagonal ()
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Longitudinally polarized massive vector"
write (u, "(A)")

call flv%init (23, model)
call pmatrix%init (2, 1)
call pmatrix%set_entry (1, [0,0], (1._default, 0._default))
call pmatrix%normalize (flv, 1._default, tolerance)
call pmatrix%write (u)
write (u, *)
write (u, "(1x,A,L1)")  "polarized = ", pmatrix%is_polarized ()
write (u, "(1x,A,L1)")  "diagonal = ", pmatrix%is_diagonal ()
write (u, *)

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

write (u, "(A)")
write (u, "(A)")  "* Axis polarization (0.2, 0.4, 0.6)"
write (u, "(A)")

call flv%init (11, model)
alpha = [0.2_default, 0.4_default, 0.6_default]
alpha = alpha / sqrt (sum (alpha**2))
call pmatrix%init (2, 3)
call pmatrix%set_entry (1, [-1,-1], cmplx (1 - alpha(3), kind=default))
call pmatrix%set_entry (2, [1,-1], &
    cmplx (alpha(1), -alpha(2), kind=default))
call pmatrix%set_entry (3, [1,1], cmplx (1 + alpha(3), kind=default))
call pmatrix%normalize (flv, 1._default, tolerance)
call pmatrix%write (u)
write (u, *)

```

```

call polarization_init_pmatrix (pol, pmatrix)
call polarization_write (pol, u)
call polarization_final (pol)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: polarization_2"

end subroutine polarization_2

```

14.2 Particles

This module defines the `particle_t` object type, and the methods and operations that deal with it.

`<particles.f90>`≡
<File header>

`module particles`

<Use kinds>

<Use strings>

`use io_units`

`use format_utils`

`use format_defs, only: FMT_16, FMT_17, FMT_19`

`use constants, only: one, tiny_07`

`use unit_tests`

`use diagnostics`

`use lorentz`

`use model_data`

`use flavors`

`use colors`

`use helicities`

`use quantum_numbers`

`use state_matrices`

`use interactions`

`use evaluators`

`use subevents`

`use polarizations`

<Standard module head>

<Particles: public>

<Particles: parameters>

<Particles: types>

<Particles: interfaces>

```

contains

⟨Particles: procedures⟩

⟨Particles: tests⟩

end module particles

```

14.2.1 The particle type

Particle status codes

The overall status codes (incoming/outgoing etc.) are inherited from the module `subevents`.

Polarization status:

```

⟨Particles: parameters⟩≡
    integer, parameter, public :: PRT_UNPOLARIZED = 0
    integer, parameter, public :: PRT_DEFINITE_HELICITY = 1
    integer, parameter, public :: PRT_GENERIC_POLARIZATION = 2

```

Definition

The quantum numbers are flavor (from which invariant particle properties can be derived), color, and polarization. The particle may be unpolarized. In this case, `hel` and `pol` are unspecified. If it has a definite helicity, the `hel` component is defined. If it has a generic polarization, the `pol` component is defined. For each particle we store the four-momentum and the invariant mass squared, i.e., the squared norm of the four-momentum. There is also an optional list of parent and child particles, for bookkeeping in physical events. The vertex is an optional component that consists of a Lorentz 4-vector, denoting the position and time of the vertex (displaced vertex/time).

```

⟨Particles: public⟩≡
    public :: particle_t

⟨Particles: types⟩≡
    type :: particle_t
        !private
        integer :: status = PRT_UNDEFINED
        integer :: polarization = PRT_UNPOLARIZED
        type(flavor_t) :: flv
        type(color_t) :: col
        type(helicity_t) :: hel
        type(polarization_t) :: pol
        type(vector4_t) :: p = vector4_null
        real(default) :: p2 = 0
        type(vector4_t), allocatable :: vertex
        integer, dimension(:), allocatable :: parent
        integer, dimension(:), allocatable :: child
    contains
    ⟨Particles: particle: TBP⟩
end type particle_t

```

Copy a particle. (Deep copy) This excludes the parent-child relations.

```

(Particles: particle)≡
  generic :: init => init_particle
  procedure :: init_particle => particle_init_particle

(Particles: procedures)≡
  subroutine particle_init_particle (prt_out, prt_in)
    type(particle_t), intent(in) :: prt_in
    class(particle_t), intent(out) :: prt_out
    prt_out%status = prt_in%status
    prt_out%polarization = prt_in%polarization
    prt_out%flv = prt_in%flv
    prt_out%col = prt_in%col
    prt_out%hel = prt_in%hel
    prt_out%pol = prt_in%pol
    prt_out%p = prt_in%p
    prt_out%p2 = prt_in%p2
    if (allocated (prt_in%vertex)) &
      allocate (prt_out%vertex, source=prt_in%vertex)
  end subroutine particle_init_particle

```

Initialize a particle using external information.

```

(Particles: particle: TBP)≡
  generic :: init => init_external
  procedure :: init_external => particle_init_external

(Particles: procedures)+≡
  subroutine particle_init_external &
    (particle, status, pdg, model, col, anti_col, mom)
    class(particle_t), intent(out) :: particle
    integer, intent(in) :: status, pdg, col, anti_col
    class(model_data_t), pointer, intent(in) :: model
    type(vector4_t) :: mom
    type(flavor_t) :: flavor
    type(color_t) :: color
    call flavor%init (pdg, model)
    call particle%set_flavor (flavor)
    call color%init_col_acl (col, anti_col)
    call particle%set_color (color)
    call particle%set_status (status)
    call particle%set_momentum (mom)
  end subroutine particle_init_external

```

Initialize a particle using a single-particle state matrix which determines flavor, color, and polarization. The state matrix must have unique flavor and color. The factorization mode determines whether the particle is unpolarized, has definite helicity, or generic polarization. This mode is translated into the polarization status.

```

(Particles: particle: TBP)+≡
  generic :: init => init_state
  procedure :: init_state => particle_init_state

```

<Particles: procedures>+≡

```

subroutine particle_init_state (prt, state, status, mode)
  class(particle_t), intent(out) :: prt
  type(state_matrix_t), intent(in) :: state
  integer, intent(in) :: status, mode
  type(state_iterator_t) :: it
  prt%status = status
  call it%init (state)
  prt%flv = it%get_flavor (1)
  if (prt%flv%is_radiated ()) prt%status = PRT_BEAM_REMNANT
  prt%col = it%get_color (1)
  select case (mode)
    case (FM_SELECT_HELICITY)
      prt%hel = it%get_helicity (1)
      if (prt%hel%is_defined ()) then
        prt%polarization = PRT_DEFINITE_HELICITY
      end if
    case (FM_FACTOR_HELICITY)
      call polarization_init_state_matrix (prt%pol, state)
      prt%polarization = PRT_GENERIC_POLARIZATION
  end select
end subroutine particle_init_state

```

Finalizer. The polarization component has pointers allocated.

<Particles: particle: TBP>+≡

```

procedure :: final => particle_final

```

<Particles: procedures>+≡

```

subroutine particle_final (prt)
  class(particle_t), intent(inout) :: prt
  call polarization_final (prt%pol)
  if (allocated (prt%vertex)) deallocate (prt%vertex)
end subroutine particle_final

```

I/O

<Particles: particle: TBP>+≡

```

procedure :: write => particle_write

```

<Particles: procedures>+≡

```

subroutine particle_write (prt, unit, testflag, compressed)
  class(particle_t), intent(in) :: prt
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag, compressed
  logical :: comp, pacified
  integer :: u
  real(default) :: pp2
  character(len=7) :: fmt
  character(len=20) :: buffer
  comp = .false.; if (present (compressed)) comp = compressed
  pacified = .false.; if (present (testflag)) pacified = testflag
  call pac_fmt (fmt, FMT_19, FMT_16, testflag)
  u = given_output_unit (unit); if (u < 0) return

```



```

pp2 = prt%p2
if (pacified) call pacify (pp2, tolerance = 1E-10_default)
select case (prt%status)
case (PRT_UNDEFINED); write (u, "(1x, A)", advance="no") "[~]"
case (PRT_BEAM); write (u, "(1x, A)", advance="no") "[b]"
case (PRT_INCOMING); write (u, "(1x, A)", advance="no") "[i]"
case (PRT_OUTGOING); write (u, "(1x, A)", advance="no") "[o]"
case (PRT_VIRTUAL); write (u, "(1x, A)", advance="no") "[v]"
case (PRT_RESONANT); write (u, "(1x, A)", advance="no") "[r]"
case (PRT_BEAM_REMNANT); write (u, "(1x, A)", advance="no") "[x]"
end select
write (u, "(1x)", advance="no")
if (comp) then
write (u, "(A7,1X)", advance="no") char (prt%flv%get_name ())
write (u, "(2(I4,1X))", advance="no") &
prt%col%get_col (), prt%col%get_acl ()
call write_compressed_integer_array (buffer, prt%parent)
write (u, "(A,1X)", advance="no") buffer
call write_compressed_integer_array (buffer, prt%child)
write (u, "(A,1X)", advance="no") buffer
call prt%p%write(u, testflag = testflag, compressed = comp)
write (u, "(F12.3)") pp2
else
call prt%flv%write (unit)
if (prt%col%is_nonzero ()) then
call color_write (prt%col, unit)
end if
select case (prt%polarization)
case (PRT_DEFINITE_HELICITY)
call prt%hel%write (unit)
write (u, *)
case (PRT_GENERIC_POLARIZATION)
write (u, *)
call polarization_write (prt%pol, unit)
case default
write (u, *)
end select
call prt%p%write (unit, testflag = testflag)
write (u, "(1x,A,1x," // fmt // ")") "T = ", pp2
if (allocated (prt%parent)) then
if (size (prt%parent) /= 0) then
write (u, "(1x,A,40(1x,I0))") "Parents: ", prt%parent
end if
end if
if (allocated (prt%child)) then
if (size (prt%child) /= 0) then
write (u, "(1x,A,40(1x,I0))") "Children:", prt%child
end if
end if
if (allocated (prt%vertex)) then
write (u, "(1x,A,1x," // fmt // ")") "Vtx t = ", prt%vertex%p(0)
write (u, "(1x,A,1x," // fmt // ")") "Vtx x = ", prt%vertex%p(1)
write (u, "(1x,A,1x," // fmt // ")") "Vtx y = ", prt%vertex%p(2)
write (u, "(1x,A,1x," // fmt // ")") "Vtx z = ", prt%vertex%p(3)

```

```

        end if
    end if
end subroutine particle_write

```

Binary I/O:

$\langle \text{Particles: particle: TBP} \rangle + \equiv$

```

    procedure :: write_raw => particle_write_raw
    procedure :: read_raw => particle_read_raw

```

$\langle \text{Particles: procedures} \rangle + \equiv$

```

subroutine particle_write_raw (prt, u)
    class(particle_t), intent(in) :: prt
    integer, intent(in) :: u
    write (u) prt%status, prt%polarization
    call prt%flv%write_raw (u)
    call prt%col%write_raw (u)
    select case (prt%polarization)
    case (PRT_DEFINITE_HELICITY)
        call prt%hel%write_raw (u)
    case (PRT_GENERIC_POLARIZATION)
        call polarization_write_raw (prt%pol, u)
    end select
    call vector4_write_raw (prt%p, u)
    write (u) prt%p2
    write (u) allocated (prt%parent)
    if (allocated (prt%parent)) then
        write (u) size (prt%parent)
        write (u) prt%parent
    end if
    write (u) allocated (prt%child)
    if (allocated (prt%child)) then
        write (u) size (prt%child)
        write (u) prt%child
    end if
    write (u) allocated (prt%vertex)
    if (allocated (prt%vertex)) then
        call vector4_write_raw (prt%vertex, u)
    end if
end subroutine particle_write_raw

subroutine particle_read_raw (prt, u, iostat)
    class(particle_t), intent(out) :: prt
    integer, intent(in) :: u
    integer, intent(out) :: iostat
    logical :: allocated_parent, allocated_child, allocated_vertex
    integer :: size_parent, size_child
    read (u, iostat=iostat) prt%status, prt%polarization
    call prt%flv%read_raw (u, iostat=iostat)
    call prt%col%read_raw (u, iostat=iostat)
    select case (prt%polarization)
    case (PRT_DEFINITE_HELICITY)
        call prt%hel%read_raw (u, iostat=iostat)
    case (PRT_GENERIC_POLARIZATION)
        call polarization_read_raw (prt%pol, u, iostat=iostat)
    end select
end subroutine particle_read_raw

```

```

end select
call vector4_read_raw (prt%p, u, iostat=iostat)
read (u, iostat=iostat) prt%p2
read (u, iostat=iostat) allocated_parent
if (allocated_parent) then
    read (u, iostat=iostat) size_parent
    allocate (prt%parent (size_parent))
    read (u, iostat=iostat) prt%parent
end if
read (u, iostat=iostat) allocated_child
if (allocated_child) then
    read (u, iostat=iostat) size_child
    allocate (prt%child (size_child))
    read (u, iostat=iostat) prt%child
end if
read (u, iostat=iostat) allocated_vertex
if (allocated_vertex) then
    allocate (prt%vertex)
    read (u, iostat=iostat) prt%vertex%p
end if
end subroutine particle_read_raw

```

Setting contents

Reset the status code. Where applicable, set p^2 assuming that the particle is on-shell.

```

⟨Particles: particle: TBP⟩+≡
    procedure :: reset_status => particle_reset_status

⟨Particles: procedures⟩+≡
    elemental subroutine particle_reset_status (prt, status)
        class(particle_t), intent(inout) :: prt
        integer, intent(in) :: status
        prt%status = status
        select case (status)
        case (PRT_BEAM, PRT_INCOMING, PRT_OUTGOING)
            prt%p2 = prt%flv%get_mass () ** 2
        end select
    end subroutine particle_reset_status

```

The color can be given explicitly.

```

⟨Particles: particle: TBP⟩+≡
    procedure :: set_color => particle_set_color

⟨Particles: procedures⟩+≡
    elemental subroutine particle_set_color (prt, col)
        class(particle_t), intent(inout) :: prt
        type(color_t), intent(in) :: col
        prt%col = col
    end subroutine particle_set_color

```

The flavor can be given explicitly.

```

(Particles: particle: TBP)+≡
  procedure :: set_flavor => particle_set_flavor

(Particles: procedures)+≡
  subroutine particle_set_flavor (prt, flv)
    class(particle_t), intent(inout) :: prt
    type(flavor_t), intent(in) :: flv
    prt%flv = flv
  end subroutine particle_set_flavor

```

As can the helicity.

```

(Particles: particle: TBP)+≡
  procedure :: set_helicity => particle_set_helicity

(Particles: procedures)+≡
  subroutine particle_set_helicity (prt, hel)
    class(particle_t), intent(inout) :: prt
    type(helicity_t), intent(in) :: hel
    prt%hel = hel
  end subroutine particle_set_helicity

```

And the polarization.

```

(Particles: particle: TBP)+≡
  procedure :: set_pol => particle_set_pol

(Particles: procedures)+≡
  subroutine particle_set_pol (prt, pol)
    class(particle_t), intent(inout) :: prt
    type(polarization_t), intent(in) :: pol
    prt%pol = pol
  end subroutine particle_set_pol

```

Manually set the model for the particle flavor. This is required, e.g., if the particle has been read from file.

```

(Particles: particle: TBP)+≡
  procedure :: set_model => particle_set_model

(Particles: procedures)+≡
  subroutine particle_set_model (prt, model)
    class(particle_t), intent(inout) :: prt
    class(model_data_t), intent(in), target :: model
    call prt%flv%set_model (model)
  end subroutine particle_set_model

```

The momentum is set independent of the quantum numbers.

```

(Particles: particle: TBP)+≡
  procedure :: set_momentum => particle_set_momentum

(Particles: procedures)+≡
  elemental subroutine particle_set_momentum (prt, p, p2, on_shell)
    class(particle_t), intent(inout) :: prt
    type(vector4_t), intent(in) :: p

```

```

real(default), intent(in), optional :: p2
logical, intent(in), optional :: on_shell
prt%p = p
if (present (on_shell)) then
  if (on_shell) then
    if (prt%flv%is_associated ()) then
      prt%p2 = prt%flv%get_mass () ** 2
      return
    end if
  end if
end if
if (present (p2)) then
  prt%p2 = p2
else
  prt%p2 = p ** 2
end if
end subroutine particle_set_momentum

```

Set resonance information. This should be done after momentum assignment, because we need to know whether the particle is spacelike or timelike. The resonance flag is defined only for virtual particles.

```

<Particle: particle: TBP>≡
  procedure :: set_resonance_flag => particle_set_resonance_flag

<Particles: procedures>+≡
  elemental subroutine particle_set_resonance_flag (prt, resonant)
    class(particle_t), intent(inout) :: prt
    logical, intent(in) :: resonant
    select case (prt%status)
    case (PRT_VIRTUAL)
      if (resonant) prt%status = PRT_RESONANT
    end select
  end subroutine particle_set_resonance_flag

```

Set children and parents information.

```

<Particles: particle: TBP>+≡
  procedure :: set_children => particle_set_children
  procedure :: set_parents => particle_set_parents

<Particles: procedures>+≡
  subroutine particle_set_children (prt, idx)
    class(particle_t), intent(inout) :: prt
    integer, dimension(:), intent(in) :: idx
    if (allocated (prt%child)) deallocate (prt%child)
    allocate (prt%child (count (idx /= 0)))
    prt%child = pack (idx, idx /= 0)
  end subroutine particle_set_children

  subroutine particle_set_parents (prt, idx)
    class(particle_t), intent(inout) :: prt
    integer, dimension(:), intent(in) :: idx
    if (allocated (prt%parent)) deallocate (prt%parent)
    allocate (prt%parent (count (idx /= 0)))
    prt%parent = pack (idx, idx /= 0)
  end subroutine particle_set_parents

```

```

end subroutine particle_set_parents

<Particles: particle: TBP>+≡
  procedure :: add_child => particle_add_child

<Particles: procedures>+≡
  subroutine particle_add_child (prt, new_child)
    class(particle_t), intent(inout) :: prt
    integer, intent(in) :: new_child
    integer, dimension(:), allocatable :: idx
    integer :: n, i
    n = prt%get_n_children()
    if (n == 0) then
      call prt%set_children ([new_child])
    else
      do i = 1, n
        if (prt%child(i) == new_child) then
          return
        end if
      end do
      allocate (idx (1:n+1))
      idx(1:n) = prt%get_children ()
      idx(n+1) = new_child
      call prt%set_children (idx)
    end if
  end subroutine particle_add_child

<Particles: particle: TBP>+≡
  procedure :: add_children => particle_add_children

<Particles: procedures>+≡
  subroutine particle_add_children (prt, new_child)
    class(particle_t), intent(inout) :: prt
    integer, dimension(:), intent(in) :: new_child
    integer, dimension(:), allocatable :: idx
    integer :: n
    n = prt%get_n_children()
    if (n == 0) then
      call prt%set_children (new_child)
    else
      allocate (idx (1:n+size(new_child)))
      idx(1:n) = prt%get_children ()
      idx(n+1:n+size(new_child)) = new_child
      call prt%set_children (idx)
    end if
  end subroutine particle_add_children

<Particles: particle: TBP>+≡
  procedure :: set_status => particle_set_status

<Particles: procedures>+≡
  elemental subroutine particle_set_status (prt, status)
    class(particle_t), intent(inout) :: prt
    integer, intent(in) :: status

```

```

    prt%status = status
end subroutine particle_set_status

```

<Particles: particle: TBP>+≡

```

    procedure :: set_polarization => particle_set_polarization

```

<Particles: procedures>+≡

```

subroutine particle_set_polarization (prt, polarization)
    class(particle_t), intent(inout) :: prt
    integer, intent(in) :: polarization
    prt%polarization = polarization
end subroutine particle_set_polarization

```

<Particles: particle: TBP>+≡

```

generic :: set_vertex => set_vertex_from_vector3, set_vertex_from_xyz, &
    set_vertex_from_vector4, set_vertex_from_xyzt
procedure :: set_vertex_from_vector4 => particle_set_vertex_from_vector4
procedure :: set_vertex_from_vector3 => particle_set_vertex_from_vector3
procedure :: set_vertex_from_xyzt => particle_set_vertex_from_xyzt
procedure :: set_vertex_from_xyz => particle_set_vertex_from_xyz

```

<Particles: procedures>+≡

```

subroutine particle_set_vertex_from_vector4 (prt, vertex)
    class(particle_t), intent(inout) :: prt
    type(vector4_t), intent(in) :: vertex
    if (allocated (prt%vertex)) deallocate (prt%vertex)
    allocate (prt%vertex, source=vertex)
end subroutine particle_set_vertex_from_vector4

```

```

subroutine particle_set_vertex_from_vector3 (prt, vertex)
    class(particle_t), intent(inout) :: prt
    type(vector3_t), intent(in) :: vertex
    type(vector4_t) :: vtx
    vtx = vector4_moving (0._default, vertex)
    if (allocated (prt%vertex)) deallocate (prt%vertex)
    allocate (prt%vertex, source=vtx)
end subroutine particle_set_vertex_from_vector3

```

```

subroutine particle_set_vertex_from_xyzt (prt, vx, vy, vz, t)
    class(particle_t), intent(inout) :: prt
    real(default), intent(in) :: vx, vy, vz, t
    type(vector4_t) :: vertex
    if (allocated (prt%vertex)) deallocate (prt%vertex)
    vertex = vector4_moving (t, vector3_moving ([vx, vy, vz]))
    allocate (prt%vertex, source=vertex)
end subroutine particle_set_vertex_from_xyzt

```

```

subroutine particle_set_vertex_from_xyz (prt, vx, vy, vz)
    class(particle_t), intent(inout) :: prt
    real(default), intent(in) :: vx, vy, vz
    type(vector4_t) :: vertex
    if (allocated (prt%vertex)) deallocate (prt%vertex)
    vertex = vector4_moving (0._default, vector3_moving ([vx, vy, vz]))
    allocate (prt%vertex, source=vertex)

```

```
end subroutine particle_set_vertex_from_xyz
```

Accessing contents

The status code.

```
<Particles: particle: TBP>+≡
  procedure :: get_status => particle_get_status

<Particles: procedures>+≡
  elemental function particle_get_status (prt) result (status)
    integer :: status
    class(particle_t), intent(in) :: prt
    status = prt%status
  end function particle_get_status
```

Return true if the status is either INCOMING, OUTGOING or RESONANT. BEAM is kept, if keep_beams is set true.

```
<Particles: particle: TBP>+≡
  procedure :: is_real => particle_is_real

<Particles: procedures>+≡
  elemental function particle_is_real (prt, keep_beams) result (flag)
    logical :: flag, kb
    class(particle_t), intent(in) :: prt
    logical, intent(in), optional :: keep_beams
    kb = .false.
    if (present (keep_beams)) kb = keep_beams
    select case (prt%status)
    case (PRT_INCOMING, PRT_OUTGOING, PRT_RESONANT)
      flag = .true.
    case (PRT_BEAM)
      flag = kb
    case default
      flag = .false.
    end select
  end function particle_is_real
```

```
<Particles: particle: TBP>+≡
  procedure :: is_colored => particle_is_colored

<Particles: procedures>+≡
  elemental function particle_is_colored (particle) result (flag)
    logical :: flag
    class(particle_t), intent(in) :: particle
    flag = particle%col%is_nonzero ()
  end function particle_is_colored
```

[90,100] hopefully catches all of them and not too many.

```
<Particles: particle: TBP>+≡
  procedure :: is_hadronic_beam_remnant => particle_is_hadronic_beam_remnant
```



```

⟨Particles: procedures⟩+=
  elemental function particle_is_hadronic_beam_remnant (particle) result (flag)
    class(particle_t), intent(in) :: particle
    logical :: flag
    integer :: pdg
    pdg = particle%flv%get_pdg ()
    flag = particle%status == PRT_BEAM_REMNANT .and. &
      abs(pdg) >= 90 .and. abs(pdg) <= 100
  end function particle_is_hadronic_beam_remnant

```

```

⟨Particles: particle: TBP⟩+=
  procedure :: is_beam_remnant => particle_is_beam_remnant

```

```

⟨Particles: procedures⟩+=
  elemental function particle_is_beam_remnant (particle) result (flag)
    class(particle_t), intent(in) :: particle
    logical :: flag
    flag = particle%status == PRT_BEAM_REMNANT
  end function particle_is_beam_remnant

```

Polarization status.

```

⟨Particles: particle: TBP⟩+=
  procedure :: get_polarization_status => particle_get_polarization_status

⟨Particles: procedures⟩+=
  elemental function particle_get_polarization_status (prt) result (status)
    integer :: status
    class(particle_t), intent(in) :: prt
    status = prt%polarization
  end function particle_get_polarization_status

```

Return the PDG code from the flavor component directly.

```

⟨Particles: particle: TBP⟩+=
  procedure :: get_pdg => particle_get_pdg

⟨Particles: procedures⟩+=
  elemental function particle_get_pdg (prt) result (pdg)
    integer :: pdg
    class(particle_t), intent(in) :: prt
    pdg = prt%flv%get_pdg ()
  end function particle_get_pdg

```

Return the color and anticolor quantum numbers.

```

⟨Particles: particle: TBP⟩+=
  procedure :: get_color => particle_get_color

⟨Particles: procedures⟩+=
  pure function particle_get_color (prt) result (col)
    integer, dimension(2) :: col
    class(particle_t), intent(in) :: prt
    col(1) = prt%col%get_col ()
    col(2) = prt%col%get_acl ()
  end function particle_get_color

```

Return the polarization density matrix (as a shallow copy).

```
<Particles: particle: TBP>+≡  
  procedure :: get_polarization => particle_get_polarization  
  
<Particles: procedures>+≡  
  function particle_get_polarization (prt) result (pol)  
    class(particle_t), intent(in) :: prt  
    class(polarization_t), allocatable :: pol  
    pol = prt%pol  
  end function particle_get_polarization
```

Return the flavor, color and helicity.

```
<Particles: particle: TBP>+≡  
  procedure :: get_flv => particle_get_flv  
  procedure :: get_col => particle_get_col  
  procedure :: get_hel => particle_get_hel  
  
<Particles: procedures>+≡  
  function particle_get_flv (prt) result (flv)  
    class(particle_t), intent(in) :: prt  
    type(flavor_t) :: flv  
    flv = prt%flv  
  end function particle_get_flv  
  
  function particle_get_col (prt) result (col)  
    class(particle_t), intent(in) :: prt  
    type(color_t) :: col  
    col = prt%col  
  end function particle_get_col  
  
  function particle_get_hel (prt) result (hel)  
    class(particle_t), intent(in) :: prt  
    type(helicity_t) :: hel  
    hel = prt%hel  
  end function particle_get_hel
```

Return the helicity (if defined and diagonal).

```
<Particles: particle: TBP>+≡  
  procedure :: get_helicity => particle_get_helicity  
  
<Particles: procedures>+≡  
  elemental function particle_get_helicity (prt) result (hel)  
    integer :: hel  
    integer, dimension(2) :: hel_arr  
    class(particle_t), intent(in) :: prt  
    hel = 0  
    if (prt%hel%is_defined () .and. prt%hel%is_diagonal ()) then  
      hel_arr = prt%hel%to_pair ()  
      hel = hel_arr (1)  
    end if  
  end function particle_get_helicity
```

Return the number of children/parents

```
(Particles: particle: TBP)+≡  
  procedure :: get_n_parents => particle_get_n_parents  
  procedure :: get_n_children => particle_get_n_children  
  
(Particles: procedures)+≡  
  elemental function particle_get_n_parents (prt) result (n)  
    integer :: n  
    class(particle_t), intent(in) :: prt  
    if (allocated (prt%parent)) then  
      n = size (prt%parent)  
    else  
      n = 0  
    end if  
  end function particle_get_n_parents  
  
  elemental function particle_get_n_children (prt) result (n)  
    integer :: n  
    class(particle_t), intent(in) :: prt  
    if (allocated (prt%child)) then  
      n = size (prt%child)  
    else  
      n = 0  
    end if  
  end function particle_get_n_children
```

Return the array of parents/children.

```
(Particles: particle: TBP)+≡  
  procedure :: get_parents => particle_get_parents  
  procedure :: get_children => particle_get_children  
  
(Particles: procedures)+≡  
  function particle_get_parents (prt) result (parent)  
    class(particle_t), intent(in) :: prt  
    integer, dimension(:), allocatable :: parent  
    if (allocated (prt%parent)) then  
      allocate (parent (size (prt%parent)))  
      parent = prt%parent  
    else  
      allocate (parent (0))  
    end if  
  end function particle_get_parents  
  
  function particle_get_children (prt) result (child)  
    class(particle_t), intent(in) :: prt  
    integer, dimension(:), allocatable :: child  
    if (allocated (prt%child)) then  
      allocate (child (size (prt%child)))  
      child = prt%child  
    else  
      allocate (child (0))  
    end if  
  end function particle_get_children
```

```

<Particles: particle: TBP>+=
  procedure :: has_children => particle_has_children

<Particles: procedures>+=
  elemental function particle_has_children (prt) result (has_children)
    logical :: has_children
    class(particle_t), intent(in) :: prt
    has_children = .false.
    if (allocated (prt%child)) then
      has_children = size (prt%child) > 0
    end if
  end function particle_has_children

```

```

<Particles: particle: TBP>+=
  procedure :: has_parents => particle_has_parents

<Particles: procedures>+=
  elemental function particle_has_parents (prt) result (has_parents)
    logical :: has_parents
    class(particle_t), intent(in) :: prt
    has_parents = .false.
    if (allocated (prt%parent)) then
      has_parents = size (prt%parent) > 0
    end if
  end function particle_has_parents

```

Return momentum and momentum squared.

```

<Particles: particle: TBP>+=
  procedure :: get_momentum => particle_get_momentum
  procedure :: get_p2 => particle_get_p2

<Particles: procedures>+=
  elemental function particle_get_momentum (prt) result (p)
    type(vector4_t) :: p
    class(particle_t), intent(in) :: prt
    p = prt%p
  end function particle_get_momentum

  elemental function particle_get_p2 (prt) result (p2)
    real(default) :: p2
    class(particle_t), intent(in) :: prt
    p2 = prt%p2
  end function particle_get_p2

```

Return the particle vertex, if allocated.

```

<Particles: particle: TBP>+=
  procedure :: get_vertex => particle_get_vertex

<Particles: procedures>+=
  elemental function particle_get_vertex (prt) result (vtx)
    type(vector4_t) :: vtx
    class(particle_t), intent(in) :: prt
    if (allocated (prt%vertex)) then
      vtx = prt%vertex
    end if
  end function particle_get_vertex

```

```

else
    vtx = vector4_null
end if
end function particle_get_vertex

```

14.2.2 Particle sets

A particle set is what is usually called an event: an array of particles. The individual particle entries carry momentum, quantum numbers, polarization, and optionally connections. There is (also optionally) a correlated state-density matrix that maintains spin correlations that are lost in the individual particle entries.

```

⟨Particles: public⟩+≡
    public :: particle_set_t

⟨Particles: types⟩+≡
    type :: particle_set_t
        integer :: n_beam = 0
        integer :: n_in  = 0
        integer :: n_vir = 0
        integer :: n_out = 0
        integer :: n_tot = 0
        type(particle_t), dimension(:), allocatable :: prt
        type(state_matrix_t) :: correlated_state
    contains
        ⟨Particles: particle set: TBP⟩
    end type particle_set_t

```

A particle set can be initialized from an interaction or from a HepMC event record.

```

⟨Particles: particle set: TBP⟩≡
    generic :: init => init_interaction
    procedure :: init_interaction => particle_set_init_interaction

```

When a particle set is initialized from a given interaction, we have to determine the branch within the original state matrix that fixes the particle quantum numbers. This is done with the appropriate probabilities, based on a random number `x`. The `mode` determines whether the individual particles become unpolarized, or take a definite (diagonal) helicity, or acquire single-particle polarization matrices. The flag `keep_correlations` tells whether the spin-correlation matrix is to be calculated and stored in addition to the particles. The flag `keep_virtual` tells whether virtual particles should be dropped. Note that if virtual particles are dropped, the spin-correlation matrix makes no sense, and parent-child relations are not set.

For a correct disentangling of color and flavor (in the presence of helicity), we consider two interactions. `int` has no color information, and is used to select a flavor state. Consequently, we trace over helicities here. `int_flows` contains color-flow and potentially helicity information, but is useful only after the flavor combination has been chosen. So this interaction is used to select helicity and color, but restricted to the selected flavor combination.

`int` and `int_flows` may be identical if there is only a single (or no) color flow. If there is just a single flavor combination, `x(1)` can be set to zero.

The current algorithm of evaluator convolution requires that the beam particles are assumed outgoing (in the beam interaction) and become virtual in all derived interactions. In the particle set they should be re-identified as incoming. The optional integer `n_incoming` can be used to perform this correction.

The flag `is_valid` is false if factorization of the state is not possible, in particular if the squared matrix element is zero.

(Particles: procedures)+≡

```

subroutine particle_set_init_interaction &
  (particle_set, is_valid, int, int_flows, mode, x, &
   keep_correlations, keep_virtual, n_incoming)
class(particle_set_t), intent(out) :: particle_set
logical, intent(out) :: is_valid
type(interaction_t), intent(in), target :: int, int_flows
integer, intent(in) :: mode
real(default), dimension(2), intent(in) :: x
logical, intent(in) :: keep_correlations, keep_virtual
integer, intent(in), optional :: n_incoming
type(state_matrix_t), dimension(:), allocatable, target :: flavor_state
type(state_matrix_t), dimension(:), allocatable, target :: single_state
integer :: n_in, n_vir, n_out, n_tot
type(quantum_numbers_t), dimension(:,:), allocatable :: qn
logical :: ok
integer :: i, j
if (present (n_incoming)) then
  n_in = n_incoming
  n_vir = int%get_n_vir () - n_incoming
else
  n_in = int%get_n_in ()
  n_vir = int%get_n_vir ()
end if
n_out = int%get_n_out ()
n_tot = int%get_n_tot ()
particle_set%n_in = n_in
particle_set%n_out = n_out
if (keep_virtual) then
  particle_set%n_vir = n_vir
  particle_set%n_tot = n_tot
else
  particle_set%n_vir = 0
  particle_set%n_tot = n_in + n_out
end if
call int%factorize &
  (FM_IGNORE_HELICITY, x(1), is_valid, flavor_state)
allocate (qn (n_tot,1))
do i = 1, n_tot
  qn(i,:) = flavor_state(i)%get_quantum_numbers (1)
end do
if (keep_correlations .and. keep_virtual) then
  call int_flows%factorize (mode, x(2), ok, &
    single_state, particle_set%correlated_state, qn(:,1))
else

```

```

        call int_flows%factorize (mode, x(2), ok, &
            single_state, qn_in=qn(:,1))
    end if
    is_valid = is_valid .and. ok
    allocate (particle_set%prt (particle_set%n_tot))
    j = 1
    do i = 1, n_tot
        if (i <= n_in) then
            call particle_set%prt(j)%init (single_state(i), PRT_INCOMING, mode)
            call particle_set%prt(j)%set_momentum (int%get_momentum (i))
        else if (i <= n_in + n_vir) then
            if (.not. keep_virtual) cycle
            call particle_set%prt(j)%init &
                (single_state(i), PRT_VIRTUAL, mode)
            call particle_set%prt(j)%set_momentum (int%get_momentum (i))
        else
            call particle_set%prt(j)%init (single_state(i), PRT_OUTGOING, mode)
            call particle_set%prt(j)%set_momentum &
                (int%get_momentum (i), on_shell = .true.)
        end if
        if (keep_virtual) then
            call particle_set%prt(j)%set_children &
                (interaction_get_children (int, i))
            call particle_set%prt(j)%set_parents &
                (interaction_get_parents (int, i))
        end if
        j = j + 1
    end do
    if (keep_virtual) then
        call particle_set_resonance_flag &
            (particle_set%prt, int%get_resonance_flags ())
    end if
    do i = 1, size(flavor_state)
        call flavor_state(i)%final ()
    end do
    do i = 1, size(single_state)
        call single_state(i)%final ()
    end do
end subroutine particle_set_init_interaction

```

Manually set the model for the stored particles.

```

<Particles: particle set: TBP>+≡
    procedure :: set_model => particle_set_set_model

<Particles: procedures>+≡
    subroutine particle_set_set_model (particle_set, model)
        class(particle_set_t), intent(inout) :: particle_set
        class(model_data_t), intent(in), target :: model
        integer :: i
        do i = 1, particle_set%n_tot
            call particle_set%prt(i)%set_model (model)
        end do
        call particle_set%correlated_state%set_model (model)
    end subroutine particle_set_set_model

```

Pointer components are hidden inside the particle polarization, and in the correlated state matrix.

```

<Particles: particle set: TBP>+≡
  procedure :: final => particle_set_final

<Particles: procedures>+≡
  subroutine particle_set_final (particle_set)
    class(particle_set_t), intent(inout) :: particle_set
    integer :: i
    if (allocated (particle_set%prt)) then
      do i = 1, size(particle_set%prt)
        call particle_set%prt(i)%final ()
      end do
      deallocate (particle_set%prt)
    end if
    call particle_set%correlated_state%final ()
  end subroutine particle_set_final

<Particles: particle set: TBP>+≡
  procedure :: get_momenta => particle_set_get_momenta

<Particles: procedures>+≡
  function particle_set_get_momenta (particle_set) result (p)
    class(particle_set_t), intent(in) :: particle_set
    type(vector4_t), dimension(:), allocatable :: p
    p = particle_set%prt%p
  end function particle_set_get_momenta

<Particles: particle set: TBP>+≡
  procedure :: set_momenta => particle_set_set_momenta

<Particles: procedures>+≡
  pure subroutine particle_set_set_momenta (particle_set, p)
    class(particle_set_t), intent(inout) :: particle_set
    type(vector4_t), dimension(:), intent(in) :: p
    if (.not. allocated (particle_set%prt)) then
      allocate (particle_set%prt (size (p)))
    end if
    particle_set%prt%p = p
  end subroutine particle_set_set_momenta

<Particles: particle set: TBP>+≡
  procedure :: parent_add_child => particle_set_parent_add_child

<Particles: procedures>+≡
  subroutine particle_set_parent_add_child (particle_set, parent, child)
    class(particle_set_t), intent(inout) :: particle_set
    integer, intent(in) :: parent, child
    call particle_set%prt(child)%set_parents ([parent])
    call particle_set%prt(parent)%add_child (child)
  end subroutine particle_set_parent_add_child

```


Output (default format)

(Particles: particle set: TBP)+≡

```
procedure :: write => particle_set_write
```

(Particles: procedures)+≡

```
subroutine particle_set_write &
  (particle_set, unit, testflag, summary, compressed)
  class(particle_set_t), intent(in) :: particle_set
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag, summary, compressed
  logical :: summ, comp
  type(vector4_t) :: sum_vec
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  summ = .false.; if (present (summary)) summ = summary
  comp = .false.; if (present (compressed)) comp = compressed
  write (u, "(1x,A)") "Particle set:"
  call write_separator (u)
  if (comp) write (u, &
    "((A4,1X),(A6,1X),(A7,1X),2(A4,1X),2(A20,1X),5(A12,1X)))" &
    "Nr", "Status", "Flavor", "Col", "ACol", "Parents", "Children", &
    "P(0)", "P(1)", "P(2)", "P(3)", "P^2"
  if (particle_set%n_tot /= 0) then
    do i = 1, particle_set%n_tot
      if (comp) then
        write (u, "(I4,1X,2X)", advance="no") i
      else
        write (u, "(1x,A,1x,I0)", advance="no") "Particle", i
      end if
      call particle_set%prt(i)%write (u, testflag = testflag, &
        compressed = comp)
    end do
    if (particle_set%correlated_state%is_defined ()) then
      call write_separator (u)
      write (u, *) "Correlated state density matrix:"
      call particle_set%correlated_state%write (u)
    end if
    if (summ) then
      call write_separator (u)
      write (u, "(A)", advance="no") &
        "Sum of incoming momenta: p(0:3) = "
      sum_vec = sum (particle_set%prt%p, &
        mask=particle_set%prt%get_status () == PRT_INCOMING)
      call pacify (sum_vec, tolerance = 1E-3_default)
      call sum_vec%write (u, compressed=.true.)
      write (u, *)
      write (u, "(A)", advance="no") &
        "Sum of beam remnant momenta: p(0:3) = "
      sum_vec = sum (particle_set%prt%p, &
        mask=particle_set%prt%get_status () == PRT_BEAM_REMNANT)
      call pacify (sum_vec, tolerance = 1E-3_default)
      call sum_vec%write (u, compressed=.true.)
      write (u, *)
      write (u, "(A)", advance="no") &
        "Sum of outgoing momenta: p(0:3) = "
```

```

        sum_vec = sum (particle_set%prt%p, &
            mask=particle_set%prt%get_status () == PRT_OUTGOING)
        call pacify (sum_vec, tolerance = 1E-3_default)
        call sum_vec%write (u, compressed=.true.)
        write (u, "(A)") ""
    end if
else
    write (u, "(3x,A)") "[empty]"
end if
end subroutine particle_set_write

```

14.2.3 I/O formats

Here, we define input/output of particle sets in various formats. This is the right place since particle sets contain most of the event information.

All write/read routines take as first argument the object, as second argument the I/O unit which in this case is a mandatory argument. Then follow further event data.

Internal binary format

This format is supposed to contain the complete information, so the particle data set can be fully reconstructed. The exception is the model part of the particle flavors; this is unassigned for the flavor values read from file.

(Particles: particle set: TBP)+≡

```

    procedure :: write_raw => particle_set_write_raw
    procedure :: read_raw => particle_set_read_raw

```

(Particles: procedures)+≡

```

subroutine particle_set_write_raw (particle_set, u)
    class(particle_set_t), intent(in) :: particle_set
    integer, intent(in) :: u
    integer :: i
    write (u) &
        particle_set%n_beam, particle_set%n_in, &
        particle_set%n_vir, particle_set%n_out
    write (u) particle_set%n_tot
    do i = 1, particle_set%n_tot
        call particle_set%prt(i)%write_raw (u)
    end do
    call particle_set%correlated_state%write_raw (u)
end subroutine particle_set_write_raw

```

```

subroutine particle_set_read_raw (particle_set, u, iostat)
    class(particle_set_t), intent(out) :: particle_set
    integer, intent(in) :: u
    integer, intent(out) :: iostat
    integer :: i
    read (u, iostat=iostat) &
        particle_set%n_beam, particle_set%n_in, &
        particle_set%n_vir, particle_set%n_out
    read (u, iostat=iostat) particle_set%n_tot

```

```

allocate (particle_set%prt (particle_set%n_tot))
do i = 1, size (particle_set%prt)
    call particle_set%prt(i)%read_raw (u, iostat=iostat)
end do
call particle_set%correlated_state%read_raw (u, iostat=iostat)
end subroutine particle_set_read_raw

```

Get contents

Find parents/children of a particular particle recursively; the search terminates if a parent/child has status BEAM, INCOMING, OUTGOING or RESONANT.

(Particles: particle set: TBP)+≡

```

procedure :: get_real_parents => particle_set_get_real_parents
procedure :: get_real_children => particle_set_get_real_children

```

(Particles: procedures)+≡

```

function particle_set_get_real_parents (pset, i, keep_beams) result (parent)
    integer, dimension(:), allocatable :: parent
    class(particle_set_t), intent(in) :: pset
    integer, intent(in) :: i
    logical, intent(in), optional :: keep_beams
    logical, dimension(:), allocatable :: is_real
    logical, dimension(:), allocatable :: is_parent, is_real_parent
    logical :: kb
    integer :: j, k
    kb = .false.
    if (present (keep_beams)) kb = keep_beams
    allocate (is_real (pset%n_tot))
    is_real = pset%prt%is_real (kb)
    allocate (is_parent (pset%n_tot), is_real_parent (pset%n_tot))
    is_real_parent = .false.
    is_parent = .false.
    is_parent(pset%prt(i)%get_parents()) = .true.
    do while (any (is_parent))
        where (is_real .and. is_parent)
            is_real_parent = .true.
            is_parent = .false.
        end where
        mark_next_parent: do j = size (is_parent), 1, -1
            if (is_parent(j)) then
                is_parent(pset%prt(j)%get_parents()) = .true.
                is_parent(j) = .false.
                exit mark_next_parent
            end if
        end do mark_next_parent
    end do
    allocate (parent (count (is_real_parent)))
    j = 0
    do k = 1, size (is_parent)
        if (is_real_parent(k)) then
            j = j + 1
            parent(j) = k
        end if
    end do

```

```

end do
end function particle_set_get_real_parents

function particle_set_get_real_children (pset, i, keep_beams) result (child)
  integer, dimension(:), allocatable :: child
  class(particle_set_t), intent(in) :: pset
  integer, intent(in) :: i
  logical, dimension(:), allocatable :: is_real
  logical, dimension(:), allocatable :: is_child, is_real_child
  logical, intent(in), optional :: keep_beams
  integer :: j, k
  logical :: kb
  kb = .false.
  if (present (keep_beams)) kb = keep_beams
  allocate (is_real (pset%n_tot))
  is_real = pset%prt%is_real (kb)
  allocate (is_child (pset%n_tot), is_real_child (pset%n_tot))
  is_real_child = .false.
  is_child = .false.
  is_child(pset%prt(i)%get_children()) = .true.
  do while (any (is_child))
    where (is_real .and. is_child)
      is_real_child = .true.
      is_child = .false.
    end where
    mark_next_child: do j = 1, size (is_child)
      if (is_child(j)) then
        is_child(pset%prt(j)%get_children()) = .true.
        is_child(j) = .false.
        exit mark_next_child
      end if
    end do mark_next_child
  end do
  allocate (child (count (is_real_child)))
  j = 0
  do k = 1, size (is_child)
    if (is_real_child(k)) then
      j = j + 1
      child(j) = k
    end if
  end do
end function particle_set_get_real_children

```

Get the `n_tot`, `n_in`, and `n_out` values out of the particle set.

(Particles: particle set: TBP)+≡

```

procedure :: get_n_beam => particle_set_get_n_beam
procedure :: get_n_in => particle_set_get_n_in
procedure :: get_n_vir => particle_set_get_n_vir
procedure :: get_n_out => particle_set_get_n_out
procedure :: get_n_tot => particle_set_get_n_tot
procedure :: get_n_remnants => particle_set_get_n_remnants

```

(Particles: procedures)+≡

```

function particle_set_get_n_beam (pset) result (n_beam)

```

```

        class(particle_set_t), intent(in) :: pset
        integer :: n_beam
        n_beam = pset%n_beam
    end function particle_set_get_n_beam

function particle_set_get_n_in (pset) result (n_in)
    class(particle_set_t), intent(in) :: pset
    integer :: n_in
    n_in = pset%n_in
end function particle_set_get_n_in

function particle_set_get_n_vir (pset) result (n_vir)
    class(particle_set_t), intent(in) :: pset
    integer :: n_vir
    n_vir = pset%n_vir
end function particle_set_get_n_vir

function particle_set_get_n_out (pset) result (n_out)
    class(particle_set_t), intent(in) :: pset
    integer :: n_out
    n_out = pset%n_out
end function particle_set_get_n_out

function particle_set_get_n_tot (pset) result (n_tot)
    class(particle_set_t), intent(in) :: pset
    integer :: n_tot
    n_tot = pset%n_tot
end function particle_set_get_n_tot

function particle_set_get_n_remnants (pset) result (n_rad)
    class(particle_set_t), intent(in) :: pset
    integer :: n_rad
    n_rad = count (pset%prt%get_status () == PRT_BEAM_REMNANT)
end function particle_set_get_n_remnants

```

Return a pointer to the particle corresponding to the number

(Particles: particle set: TBP)+≡

```

    procedure :: get_particle => particle_set_get_particle

```

(Particles: procedures)+≡

```

    function particle_set_get_particle (pset, index) result (particle)
        class(particle_set_t), intent(in) :: pset
        integer, intent(in) :: index
        type(particle_t) :: particle
        particle = pset%prt(index)
    end function particle_set_get_particle

```

(Particles: particle set: TBP)+≡

```

    procedure :: get_indices => particle_set_get_indices

```

(Particles: procedures)+≡

```

    pure function particle_set_get_indices (pset, mask) result (finals)
        integer, dimension(:), allocatable :: finals
        class(particle_set_t), intent(in) :: pset

```

```

logical, dimension(:), intent(in) :: mask
integer, dimension(size(mask)) :: indices
integer :: i
allocate (finals (count (mask)))
indices = [(i, i=1, pset%n_tot)]
finals = pack (indices, mask)
end function particle_set_get_indices

```

Tools

Build a new particles array without hadronic remnants but with `n_extra` additional spots. We also update the mother-daughter relations assuming the ordering `b, i, r, x, o`.

```

⟨Particles: particle set: TBP⟩+≡
  procedure :: without_hadronic_remnants => particle_set_without_hadronic_remnants

⟨Particles: procedures⟩+≡
  subroutine particle_set_without_hadronic_remnants &
    (particle_set, particles, n_particles, n_extra)
    class(particle_set_t), intent(inout) :: particle_set
    type(particle_t), allocatable, dimension(:), intent(out) :: particles
    integer, intent(out) :: n_particles
    integer, intent(in) :: n_extra
    logical, allocatable, dimension(:) :: no_hadronic_remnants
    integer, allocatable, dimension(:) :: children, new_children
    integer :: i, j, first_remnant
    first_remnant = particle_set%n_tot
    do i = 1, particle_set%n_tot
      if (particle_set%prt(i)%is_hadronic_beam_remnant ()) then
        first_remnant = i
        exit
      end if
    end do
    no_hadronic_remnants = .not. (particle_set%prt%is_hadronic_beam_remnant ())
    n_particles = count (no_hadronic_remnants)
    allocate (particles (n_particles + n_extra))
    particles (1:n_particles) = pack (particle_set%prt, no_hadronic_remnants)
    if (n_particles /= particle_set%n_tot) then
      do i = 1, n_particles
        select case (particles(i)%get_status ())
          case (PRT_BEAM)
            children = particles(i)%get_children ()
            no_hadronic_remnants = .not. &
              (particle_set%prt(children)%is_hadronic_beam_remnant ())
            new_children = pack (children, no_hadronic_remnants)
            call particles(i)%set_children (new_children)
          case (PRT_INCOMING, PRT_RESONANT)
            ⟨update children after remnant⟩
          case (PRT_OUTGOING, PRT_BEAM_REMNANT)
          case default
          end select
        end do
      end if
    end if
  end subroutine

```

```

end subroutine particle_set_without_hadronic_remnants

<update children after remnant>≡
  children = particles(i)%get_children ()
  do j = 1, size (children)
    if (children(j) > first_remnant) then
      children(j) = children (j) - (particle_set%n_tot - n_particles)
    end if
  end do
  call particles(i)%set_children (children)

Build a new particles array without remnants but with n_extra additional spots.
We also update the mother-daughter relations assuming the ordering b, i, r, x,
o.

<Particles: particle set: TBP>+≡
  procedure :: without_remnants => particle_set_without_remnants

<Particles: procedures>+≡
  subroutine particle_set_without_remnants &
    (particle_set, particles, n_particles, n_extra)
    class(particle_set_t), intent(inout) :: particle_set
    type(particle_t), allocatable, dimension(:), intent(out) :: particles
    integer, intent(in) :: n_extra
    integer, intent(out) :: n_particles
    logical, allocatable, dimension(:) :: no_remnants
    integer, allocatable, dimension(:) :: children, new_children
    integer :: i,j, first_remnant
    first_remnant = particle_set%n_tot
    do i = 1, particle_set%n_tot
      if (particle_set%prt(i)%is_beam_remnant ()) then
        first_remnant = i
        exit
      end if
    end do
    no_remnants = .not. (particle_set%prt%is_beam_remnant ())
    n_particles = count (no_remnants)
    allocate (particles (n_particles + n_extra))
    particles (1:n_particles) = pack (particle_set%prt, no_remnants)
    if (n_particles /= particle_set%n_tot) then
      do i = 1, n_particles
        select case (particles(i)%get_status ())
        case (PRT_BEAM)
          children = particles(i)%get_children ()
          no_remnants = .not. (particle_set%prt(children)%is_beam_remnant ())
          new_children = pack (children, no_remnants)
          call particles(i)%set_children (new_children)
        case (PRT_INCOMING, PRT_RESONANT)
          <update children after remnant>
        case (PRT_OUTGOING, PRT_BEAM_REMNANT)
        case default
        end select
      end do
    end if
  end subroutine particle_set_without_remnants

```

```

<Particles: particle set: TBP>+≡
  procedure :: find_particle => particle_set_find_particle

<Particles: procedures>+≡
  !pure
  function particle_set_find_particle &
    (particle_set, pdg, momentum, abs_smallness, rel_smallness) result (idx)
    integer :: idx
    class(particle_set_t), intent(in) :: particle_set
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: momentum
    real(default), intent(in), optional :: abs_smallness, rel_smallness
    integer :: i
    idx = 0
    do i = 1, size (particle_set%prt)
      if (particle_set%prt(i)%flv%get_pdg () == pdg) then
        if (all (nearly_equal (particle_set%prt(i)%p%p, momentum%p, &
                               abs_smallness, rel_smallness))) then
          idx = i
          return
        end if
      end if
    end do
  end function particle_set_find_particle

```

Given a subevent, reset status codes. If the new status is beam, incoming, or outgoing, we also make sure that the stored p^2 value is equal to the on-shell mass squared.

```

<Particles: particle set: TBP>+≡
  procedure :: reset_status => particle_set_reset_status

<Particles: procedures>+≡
  subroutine particle_set_reset_status (particle_set, index, status)
    class(particle_set_t), intent(inout) :: particle_set
    integer, dimension(:), intent(in) :: index
    integer, intent(in) :: status
    integer :: i
    if (allocated (particle_set%prt)) then
      do i = 1, size (index)
        call particle_set%prt(index(i))%reset_status (status)
      end do
    end if
    particle_set%n_beam = &
      count (particle_set%prt%get_status () == PRT_BEAM)
    particle_set%n_in = &
      count (particle_set%prt%get_status () == PRT_INCOMING)
    particle_set%n_out = &
      count (particle_set%prt%get_status () == PRT_OUTGOING)
    particle_set%n_vir = particle_set%n_tot &
      - particle_set%n_beam - particle_set%n_in - particle_set%n_out
  end subroutine particle_set_reset_status

```

Reduce a particle set to the essential entries. The entries kept are those with status INCOMING, OUTGOING or RESONANT. BEAM is kept if `keep_beams` is true.

Other entries are skipped. The correlated state matrix, if any, is also ignored.

```

(Particles: particle set: TBP)+≡
  procedure :: reduce => particle_set_reduce
(Particles: procedures)+≡
  subroutine particle_set_reduce (pset_in, pset_out, keep_beams)
    class(particle_set_t), intent(in) :: pset_in
    type(particle_set_t), intent(out) :: pset_out
    logical, intent(in), optional :: keep_beams
    integer, dimension(:), allocatable :: status, map
    integer :: i, j
    logical :: kb
    kb = .false.; if (present (keep_beams)) kb = keep_beams
    allocate (status (pset_in%n_tot))
    status = pset_in%prt%get_status ()
    if (kb) pset_out%n_beam = count (status == PRT_BEAM)
    pset_out%n_in = count (status == PRT_INCOMING)
    pset_out%n_vir = count (status == PRT_RESONANT)
    pset_out%n_out = count (status == PRT_OUTGOING)
    pset_out%n_tot = &
      pset_out%n_beam + pset_out%n_in + pset_out%n_vir + pset_out%n_out
    allocate (pset_out%prt (pset_out%n_tot))
    allocate (map (pset_in%n_tot))
    map = 0
    j = 0
    if (kb) call copy_particles (PRT_BEAM)
    call copy_particles (PRT_INCOMING)
    call copy_particles (PRT_RESONANT)
    call copy_particles (PRT_OUTGOING)
    do i = 1, pset_in%n_tot
      if (map(i) == 0) cycle
      !!! !!! triggers nagfor bug!
      !!! call particle_set_parents (pset_out%prt(map(i)), &
      !!!   map (particle_set_get_real_parents (pset_in, i)))
      !!! call particle_set_children (pset_out%prt(map(i)), &
      !!!   map (particle_set_get_real_children (pset_in, i)))
      !!! !!! workaround:
      call pset_out%prt(map(i))%set_parents &
        (pset_in%get_real_parents (i, kb))
      call pset_out%prt(map(i))%set_parents &
        (map (pset_out%prt(map(i))%parent))
      call pset_out%prt(map(i))%set_children &
        (pset_in%get_real_children (i, kb))
      call pset_out%prt(map(i))%set_children &
        (map (pset_out%prt(map(i))%child))
    end do
  contains
    subroutine copy_particles (stat)
      integer, intent(in) :: stat
      integer :: i
      do i = 1, pset_in%n_tot
        if (status(i) == stat) then
          j = j + 1
          map(i) = j
          call particle_init_particle (pset_out%prt(j), pset_in%prt(i))
        end if
      end do
    end subroutine
  end subroutine

```

```

        end if
    end do
end subroutine copy_particles
end subroutine particle_set_reduce

```

Remove the beam particles and beam remnants from the particle set if the keep beams flag is false. If keep beams is not given, the beam particles and the beam remnants are removed. The correlated state matrix, if any, is also ignored.

```

(Particles: particle set: TBP) +=
    procedure :: apply_keep_beams => particle_set_apply_keep_beams

(Particles: procedures) +=
    subroutine particle_set_apply_keep_beams &
        (pset_in, pset_out, keep_beams, real_parents)
    class(particle_set_t), intent(in) :: pset_in
    type(particle_set_t), intent(out) :: pset_out
    logical, intent(in), optional :: keep_beams, real_parents
    integer, dimension(:), allocatable :: status, map
    integer :: i, j
    logical :: kb, rp
    kb = .false.; if (present (keep_beams)) kb = keep_beams
    rp = .false.; if (present (real_parents)) rp = real_parents
    allocate (status (pset_in%n_tot))
    status = particle_get_status (pset_in%prt)
    if (kb) pset_out%n_beam = count (status == PRT_BEAM)
    pset_out%n_in = count (status == PRT_INCOMING)
    if (kb) then
        pset_out%n_vir = count (status == PRT_VIRTUAL) + &
            count (status == PRT_RESONANT) + &
            count (status == PRT_BEAM_REMNANT)
    else
        pset_out%n_vir = count (status == PRT_VIRTUAL) + &
            count (status == PRT_RESONANT)
    end if
    pset_out%n_out = count (status == PRT_OUTGOING)
    pset_out%n_tot = &
        pset_out%n_beam + pset_out%n_in + pset_out%n_vir + pset_out%n_out
    allocate (pset_out%prt (pset_out%n_tot))
    allocate (map (pset_in%n_tot))
    map = 0
    j = 0
    if (kb) call copy_particles (PRT_BEAM)
    call copy_particles (PRT_INCOMING)
    if (kb) call copy_particles (PRT_BEAM_REMNANT)
    call copy_particles (PRT_RESONANT)
    call copy_particles (PRT_VIRTUAL)
    call copy_particles (PRT_OUTGOING)
    do i = 1, pset_in%n_tot
        if (map(i) == 0) cycle
        if (rp) then
            call pset_out%prt(map(i))%set_parents &
                (map (pset_in%get_real_parents (i, kb)))
            call pset_out%prt(map(i))%set_children &
                (map (pset_in%get_real_children (i, kb)))

```

```

        else
            call pset_out%prt(map(i))%set_parents &
                (map (pset_in%prt(i)%get_parents ()))
            call pset_out%prt(map(i))%set_children &
                (map (pset_in%prt(i)%get_children ()))
        end if
    end do
contains
    subroutine copy_particles (stat)
        integer, intent(in) :: stat
        integer :: i
        do i = 1, pset_in%n_tot
            if (status(i) == stat) then
                j = j + 1
                map(i) = j
                call particle_init_particle (pset_out%prt(j), pset_in%prt(i))
            end if
        end do
    end subroutine copy_particles
end subroutine particle_set_apply_keep_beams

```

Transform a particle set into HEPEVT-compatible form. In this form, for each particle, the parents and the children are contiguous in the particle array. Usually, this requires to clone some particles.

We do not know in advance how many particles the canonical form will have. To be on the safe side, allocate four times the original size.

(Particles: particle set: TBP)+≡

```

    procedure :: to_hepevt_form => particle_set_to_hepevt_form

```

(Particles: procedures)+≡

```

    subroutine particle_set_to_hepevt_form (pset_in, pset_out, keep_beams)
        class(particle_set_t), intent(in) :: pset_in
        type(particle_set_t), intent(out) :: pset_out
        logical, intent(in), optional :: keep_beams
        type(particle_set_t) :: pset
        type :: particle_entry_t
        integer :: src = 0
        integer :: status = 0
        integer :: orig = 0
        integer :: copy = 0
    end type particle_entry_t
    type(particle_entry_t), dimension(:), allocatable :: prt
    integer, dimension(:), allocatable :: map1, map2
    integer, dimension(:), allocatable :: parent, child
    integer :: n_tot, n_parents, n_children, i, j, c, n

    call pset_in%apply_keep_beams (pset, keep_beams = keep_beams)
    n_tot = pset%n_tot
    allocate (prt (4 * n_tot))
    allocate (map1(4 * n_tot))
    allocate (map2(4 * n_tot))
    map1 = 0
    map2 = 0
    allocate (child (n_tot))

```

```

allocate (parent (n_tot))
n = 0
do i = 1, n_tot
  if (pset%prt(i)%get_n_parents () == 0) then
    call append (i)
  end if
end do
do i = 1, n_tot
  n_children = pset%prt(i)%get_n_children ()
  if (n_children > 0) then
    child(1:n_children) = pset%prt(i)%get_children ()
    c = child(1)
    if (map1(c) == 0) then
      n_parents = pset%prt(c)%get_n_parents ()
      if (n_parents > 1) then
        parent(1:n_parents) = pset%prt(c)%get_parents ()
        if (i == parent(1) .and. &
            any( [(map1(i)+j-1, j=1,n_parents)] /= &
                map1(parent(1:n_parents))))) &
          then
            do j = 1, n_parents
              call append (parent(j))
            end do
          end if
        else if (map1(i) == 0) then
          call append (i)
        end if
        do j = 1, n_children
          call append (child(j))
        end do
      end if
    else if (map1(i) == 0) then
      call append (i)
    end if
  end do
do i = n, 1, -1
  if (prt(i)%status /= PRT_OUTGOING) then
    do j = 1, i-1
      if (prt(j)%status == PRT_OUTGOING) then
        call append(prt(j)%src)
      end if
    end do
    exit
  end if
end do
pset_out%n_beam = count (prt(1:n)%status == PRT_BEAM)
pset_out%n_in   = count (prt(1:n)%status == PRT_INCOMING)
pset_out%n_vir  = count (prt(1:n)%status == PRT_RESONANT)
pset_out%n_out  = count (prt(1:n)%status == PRT_OUTGOING)
pset_out%n_tot = n
allocate (pset_out%prt (n))
do i = 1, n
  call particle_init_particle (pset_out%prt(i), pset%prt(prt(i)%src))
  call particle_reset_status (pset_out%prt(i), prt(i)%status)

```

```

    if (prt(i)%orig == 0) then
        call pset_out%prt(i)%set_parents &
            (map2 (pset%prt(prt(i)%src)%get_parents ()))
    else
        call pset_out%prt(i)%set_parents ([ prt(i)%orig ])
    end if
    if (prt(i)%copy == 0) then
        call pset_out%prt(i)%set_children &
            (map1 (pset%prt(prt(i)%src)%get_children ()))
    else
        call pset_out%prt(i)%set_children ([ prt(i)%copy ])
    end if
end do
contains
subroutine append (i)
    integer, intent(in) :: i
    n = n + 1
    if (n > size (prt)) &
        call msg_bug ("Particle set transform to HEPEVT: insufficient space")
    prt(n)%src = i
    prt(n)%status = pset%prt(i)%get_status ()
    if (map1(i) == 0) then
        map1(i) = n
    else
        prt(map2(i))%status = PRT_VIRTUAL
        prt(map2(i))%copy = n
        prt(n)%orig = map2(i)
    end if
    map2(i) = n
end subroutine append
end subroutine particle_set_to_hepevt_form

```

This procedure aims at reconstructing the momenta of an interaction, given a particle set. Since the particle orderings

$\langle \text{Particles: particle set: TBP} \rangle + \equiv$

```

    procedure :: fill_interaction => particle_set_fill_interaction

```

$\langle \text{Particles: procedures} \rangle + \equiv$

```

subroutine particle_set_fill_interaction &
    (pset, int, n_in, recover_beams, check_match, state_flg)
class(particle_set_t), intent(in) :: pset
type(interaction_t), intent(inout) :: int
integer, intent(in) :: n_in
logical, intent(in), optional :: recover_beams, check_match
type(state_flg_content_t), intent(in), optional :: state_flg
integer, dimension(:), allocatable :: map, pdg
integer, dimension(:), allocatable :: i_in, i_out, p_in, p_out
logical, dimension(:), allocatable :: i_set
integer :: n_out, i, p
logical :: r_beams, check
r_beams = .false.; if (present (recover_beams)) r_beams = recover_beams
check = .true.; if (present (check_match)) check = check_match
if (check) then
    call find_hard_process_in_int (i_in, i_out)

```

```

call find_hard_process_in_pset (p_in, p_out)
n_out = size (i_out)
if (size (i_in) /= n_in) call err_int_n_in
if (size (p_in) /= n_in) call err_pset_n_in
if (size (p_out) /= n_out) call err_pset_n_out
call extract_hard_process_from_pset (pdg)
call determine_map_for_hard_process (map, state_flg)
if (.not. r_beams) then
  select case (n_in)
  case (1)
    call recover_parents (p_in(1), map)
  case (2)
    do i = 1, 2
      call recover_parents (p_in(i), map)
    end do
    do p = 1, 2
      call recover_radiation (p, map)
    end do
  end select
end if
else
  allocate (map (int%get_n_tot ()))
  map = [(i, i = 1, size (map))]
  r_beams = .false.
end if
allocate (i_set (int%get_n_tot ()), source = .false.)
do p = 1, size (map)
  if (map(p) /= 0) then
    i_set(map(p)) = .true.
    call int%set_momentum &
      (pset%prt(p)%get_momentum (), map(p))
  end if
end do
if (r_beams) then
  do i = 1, n_in
    call reconstruct_beam_and_radiation (i, i_set)
  end do
end if
if (any (.not. i_set)) call err_map
contains
subroutine find_hard_process_in_pset (p_in, p_out)
  integer, dimension(:), allocatable, intent(out) :: p_in, p_out
  integer, dimension(:), allocatable :: p_status, p_idx
  integer :: n_in_p, n_out_p
  integer :: i
  allocate (p_status (pset%n_tot), p_idx (pset%n_tot))
  p_status = particle_get_status (pset%prt)
  p_idx = [(i, i = 1, pset%n_tot)]
  n_in_p = count (p_status == PRT_INCOMING)
  allocate (p_in (n_in_p))
  p_in = pack (p_idx, p_status == PRT_INCOMING)
  if (size (p_in) == 0) call err_pset_hard
  i = p_in(1)
  n_out_p = particle_get_n_children (pset%prt(i))

```

```

        allocate (p_out (n_out_p))
        p_out = particle_get_children (pset%prt(i))
    end subroutine find_hard_process_in_pset
    subroutine find_hard_process_in_int (i_in, i_out)
        integer, dimension(:), allocatable, intent(out) :: i_in, i_out
        integer :: n_in_i
        integer :: i
        i = int%get_n_tot ()
        n_in_i = interaction_get_n_parents (int, i)
        if (n_in_i /= n_in) call err_int_n_in
        allocate (i_in (n_in))
        i_in = interaction_get_parents (int, i)
        i = i_in(1)
        n_out = interaction_get_n_children (int, i)
        allocate (i_out (n_out))
        i_out = interaction_get_children (int, i)
    end subroutine find_hard_process_in_int
    subroutine extract_hard_process_from_pset (pdg)
        integer, dimension(:), allocatable, intent(out) :: pdg
        integer, dimension(:), allocatable :: pdg_p
        logical, dimension(:), allocatable :: mask_p
        allocate (pdg_p (pset%n_tot))
        pdg_p = particle_get_pdg (pset%prt)
        allocate (mask_p (pset%n_tot), source = .false.)
        mask_p (p_in) = .true.
        mask_p (p_out) = .true.
        allocate (pdg (n_in + n_out))
        pdg = pack (pdg_p, mask_p)
    end subroutine extract_hard_process_from_pset
    subroutine determine_map_for_hard_process (map, state_flg)
        integer, dimension(:), allocatable, intent(out) :: map
        type(state_flg_content_t), intent(in), optional :: state_flg
        integer, dimension(:), allocatable :: pdg_i, map_i
        integer :: n_tot
        logical, dimension(:), allocatable :: mask_i, mask_p
        logical :: success
        n_tot = int%get_n_tot ()
        allocate (map (n_tot), source = 0)
        if (present (state_flg)) then
            allocate (mask_i (n_tot), source = .false.)
            mask_i (i_in) = .true.
            mask_i (i_out) = .true.
            allocate (pdg_i (n_tot), map_i (n_tot))
            pdg_i = unpack (pdg, mask_i, 0)
            call state_flg%match (pdg_i, success, map_i)
            allocate (mask_p (pset%n_tot), source = .false.)
            mask_p (p_in) = .true.
            mask_p (p_out) = .true.
            map = unpack (pack (map_i, mask_i), mask_p, 0)
            if (.not. success) call err_mismatch
        else
            map(p_in) = i_in
            map(p_out) = i_out
        end if
    end if

```

```

end subroutine determine_map_for_hard_process
recursive subroutine recover_parents (p, map)
  integer, intent(in) :: p
  integer, dimension(:), intent(inout) :: map
  integer :: i, n, n_p, q, k
  integer, dimension(:), allocatable :: i_parents, p_parents
  integer, dimension(1) :: pp
  i = map(p)
  n = interaction_get_n_parents (int, i)
  q = p
  n_p = particle_get_n_parents (pset%prt(q))
  do while (n_p == 1)
    pp = particle_get_parents (pset%prt(q))
    if (pset%prt(pp(1))%get_n_children () > 1) exit
    q = pp(1)
    n_p = pset%prt(q)%get_n_parents ()
  end do
  if (n_p /= n) call err_map
  allocate (i_parents (n), p_parents (n))
  i_parents = interaction_get_parents (int, i)
  p_parents = pset%prt(q)%get_parents ()
  do k = 1, n
    q = p_parents(k)
    if (map(q) == 0) then
      map(q) = i_parents(k)
      call recover_parents (q, map)
    end if
  end do
end subroutine recover_parents
recursive subroutine recover_radiation (p, map)
  integer, intent(in) :: p
  integer, dimension(:), intent(inout) :: map
  integer :: i, n, n_p, q, k
  integer, dimension(:), allocatable :: i_children, p_children
  if (particle_get_status (pset%prt(p)) == PRT_INCOMING) return
  i = map(p)
  n = interaction_get_n_children (int, i)
  n_p = pset%prt(p)%get_n_children ()
  if (n_p /= n) call err_map
  allocate (i_children (n), p_children (n))
  i_children = interaction_get_children (int, i)
  p_children = pset%prt(p)%get_children ()
  do k = 1, n
    q = p_children(k)
    if (map(q) == 0) then
      i = i_children(k)
      if (interaction_get_n_children (int, i) == 0) then
        map(q) = i
      else
        select case (n)
        case (2)
          select case (k)
          case (1); map(q) = i_children(2)
          case (2); map(q) = i_children(1)
        end select
      end if
    end if
  end do
end subroutine recover_radiation

```



```

        end select
    case (4)
        select case (k)
            case (1); map(q) = i_children(3)
            case (2); map(q) = i_children(4)
            case (3); map(q) = i_children(1)
            case (4); map(q) = i_children(2)
        end select
    case default
        call err_radiation
    end select
end if
else
    call recover_radiation (q, map)
end if
end do
end subroutine recover_radiation
subroutine reconstruct_beam_and_radiation (k, i_set)
    integer, intent(in) :: k
    logical, dimension(:), intent(inout) :: i_set
    integer :: k_src, k_in, k_rad
    type(interaction_t), pointer :: int_src
    integer, dimension(2) :: i_child
    call int%find_source (k, int_src, k_src)
    call int%set_momentum (int_src%get_momentum (k_src), k)
    i_set(k) = .true.
    if (n_in == 2) then
        i_child = interaction_get_children (int, k)
        if (interaction_get_n_children (int, i_child(1)) > 0) then
            k_in = i_child(1); k_rad = i_child(2)
        else
            k_in = i_child(2); k_rad = i_child(1)
        end if
        if (.not. i_set(k_in)) call err_beams
        call int%set_momentum &
            (int%get_momentum (k) - int%get_momentum (k_in), k_rad)
        i_set(k_rad) = .true.
    end if
end subroutine reconstruct_beam_and_radiation
subroutine err_pset_hard
    call msg_fatal ("Reading particle set: no particles marked as incoming")
end subroutine err_pset_hard
subroutine err_int_n_in
    integer :: n
    if (allocated (i_in)) then
        n = size (i_in)
    else
        n = 0
    end if
    write (msg_buffer, "(A,I0,A,I0)") &
        "Filling hard process from particle set: expect ", n_in, &
        " incoming particle(s), found ", n
    call msg_bug
end subroutine err_int_n_in

```

```

subroutine err_pset_n_in
  write (msg_buffer, "(A,I0,A,I0)") &
    "Reading hard-process particle set: should contain ", n_in, &
    " incoming particle(s), found ", size (p_in)
  call msg_fatal
end subroutine err_pset_n_in
subroutine err_pset_n_out
  write (msg_buffer, "(A,I0,A,I0)") &
    "Reading hard-process particle set: should contain ", n_out, &
    " outgoing particle(s), found ", size (p_out)
  call msg_fatal
end subroutine err_pset_n_out
subroutine err_mismatch
  call pset%write ()
  call state_flv%write ()
  call msg_fatal ("Reading particle set: Flavor combination " &
    // "does not match requested process")
end subroutine err_mismatch
subroutine err_map
  call pset%write ()
  call int%basic_write ()
  call msg_fatal ("Reading hard-process particle set: " &
    // "Incomplete mapping from particle set to interaction")
end subroutine err_map
subroutine err_beams
  call pset%write ()
  call int%basic_write ()
  call msg_fatal ("Reading particle set: Beam structure " &
    // "does not match requested process")
end subroutine err_beams
subroutine err_radiation
  call int%basic_write ()
  call msg_bug ("Reading particle set: Interaction " &
    // "contains inconsistent radiation pattern.")
end subroutine err_radiation
end subroutine particle_set_fill_interaction

```

This procedure reconstructs an array of vertex indices from the parent-child information in the particle entries, according to the HepMC scheme. For each particle, we determine which vertex it comes from and which vertex it goes to. We return the two arrays and the maximum vertex index.

For each particle in the list, we first check its parents. If for any parent the vertex where it goes to is already known, this vertex index is assigned as the current 'from' vertex. Otherwise, a new index is created, assigned as the current 'from' vertex, and as the 'to' vertex for all parents.

Then, the analogous procedure is done for the children.

Furthermore, we assign to each vertex the vertex position from the parent(s). We check that these vertex positions coincide, and if not return a null vector.

```

<Particles: particle set: TBP>+=
  procedure :: assign_vertices => particle_set_assign_vertices

<Particles: procedures>+=
  subroutine particle_set_assign_vertices &

```

```

      (particle_set, v_from, v_to, n_vertices)
class(particle_set_t), intent(in) :: particle_set
integer, dimension(:), intent(out) :: v_from, v_to
integer, intent(out) :: n_vertices
integer, dimension(:), allocatable :: parent, child
integer :: n_parents, n_children, vf, vt
integer :: i, j, v
v_from = 0
v_to = 0
vf = 0
vt = 0
do i = 1, particle_set%n_tot
  n_parents = particle_set%prt(i)%get_n_parents ()
  if (n_parents /= 0) then
    allocate (parent (n_parents))
    parent = particle_set%prt(i)%get_parents ()
    SCAN_PARENTS: do j = 1, size (parent)
      v = v_to(parent(j))
      if (v /= 0) then
        v_from(i) = v; exit SCAN_PARENTS
      end if
    end do SCAN_PARENTS
    if (v_from(i) == 0) then
      vf = vf + 1; v_from(i) = vf
      v_to(parent) = vf
    end if
    deallocate (parent)
  end if
  n_children = particle_set%prt(i)%get_n_children ()
  if (n_children /= 0) then
    allocate (child (n_children))
    child = particle_set%prt(i)%get_children ()
    SCAN_CHILDREN: do j = 1, size (child)
      v = v_from(child(j))
      if (v /= 0) then
        v_to(i) = v; exit SCAN_CHILDREN
      end if
    end do SCAN_CHILDREN
    if (v_to(i) == 0) then
      vt = vt + 1; v_to(i) = vt
      v_from(child) = vt
    end if
    deallocate (child)
  end if
end do
n_vertices = max (vf, vt)
end subroutine particle_set_assign_vertices

```

14.2.4 Expression interface

This converts a `particle_set` object as defined here to a more concise `subevt` object that can be used as the event root of an expression. In particular, the

latter lacks virtual particles, spin correlations and parent-child relations.

We keep beam particles, incoming partons, and outgoing partons. Furthermore, we keep radiated particles (a.k.a. beam remnants) if they have no children in the current particle set, and mark them as outgoing particles.

(Particles: particle set: TBP)+≡

```
procedure :: to_subevt => particle_set_to_subevt
```

(Particles: procedures)+≡

```
subroutine particle_set_to_subevt (particle_set, subevt)
  class(particle_set_t), intent(in) :: particle_set
  type(subevt_t), intent(out) :: subevt
  integer :: n_tot, n_beam, n_in, n_out, n_rad
  integer :: i, k, n_active
  integer, dimension(2) :: hel
  logical :: keep
  n_tot = particle_set_get_n_tot      (particle_set)
  n_beam = particle_set_get_n_beam    (particle_set)
  n_in  = particle_set_get_n_in      (particle_set)
  n_out  = particle_set_get_n_out     (particle_set)
  n_rad  = particle_set_get_n_remnants (particle_set)
  call subevt_init (subevt, n_beam + n_rad + n_in + n_out)
  k = 0
  do i = 1, n_tot
    associate (prt => particle_set%prt(i))
      keep = .false.
      select case (particle_get_status (prt))
        case (PRT_BEAM)
          k = k + 1
          call subevt_set_beam (subevt, k, &
            particle_get_pdg (prt), &
            particle_get_momentum (prt), &
            particle_get_p2 (prt))
          keep = .true.
        case (PRT_INCOMING)
          k = k + 1
          call subevt_set_incoming (subevt, k, &
            particle_get_pdg (prt), &
            particle_get_momentum (prt), &
            particle_get_p2 (prt))
          keep = .true.
        case (PRT_OUTGOING)
          k = k + 1
          call subevt_set_outgoing (subevt, k, &
            particle_get_pdg (prt), &
            particle_get_momentum (prt), &
            particle_get_p2 (prt))
          keep = .true.
        case (PRT_BEAM_REMNANT)
          if (particle_get_n_children (prt) == 0) then
            k = k + 1
            call subevt_set_outgoing (subevt, k, &
              particle_get_pdg (prt), &
              particle_get_momentum (prt), &
              particle_get_p2 (prt))
```

```

        keep = .true.
    end if
end select
if (keep) then
    if (prt%polarization == PRT_DEFINITE_HELICITY) then
        if (prt%hel%is_diagonal ()) then
            hel = prt%hel%to_pair ()
            call subvt_polarize (subvt, k, hel(1))
        end if
    end if
end if
end associate
n_active = k
end do
call subvt_reset (subvt, n_active)
end subroutine particle_set_to_subvt

```

This replaces the `particle_set\%prt` array with a given array of particles

```

<Particles: particle set: TBP>+≡
    procedure :: replace => particle_set_replace

<Particles: procedures>+≡
    subroutine particle_set_replace (particle_set, newprt)
        class(particle_set_t), intent(inout) :: particle_set
        type(particle_t), intent(in), dimension(:), allocatable :: newprt
        if (allocated (particle_set%prt)) deallocate (particle_set%prt)
        allocate (particle_set%prt(size (newprt)))
        particle_set%prt = newprt
        particle_set%n_tot = size (newprt)
        particle_set%n_beam = count (particle_get_status (newprt) == PRT_BEAM)
        particle_set%n_in = count (particle_get_status (newprt) == PRT_INCOMING)
        particle_set%n_out = count (particle_get_status (newprt) == PRT_OUTGOING)
        particle_set%n_vir = particle_set%n_tot &
            - particle_set%n_beam - particle_set%n_in - particle_set%n_out
    end subroutine particle_set_replace

```

Eliminate numerical noise

```

<Particles: public>+≡
    public :: pacify

<Particles: interfaces>≡
    interface pacify
        module procedure pacify_particle
        module procedure pacify_particle_set
    end interface pacify

<Particles: procedures>+≡
    subroutine pacify_particle (prt)
        class(particle_t), intent(inout) :: prt
        real(default) :: e
        e = epsilon (1._default) * energy (prt%p)
        call pacify (prt%p, 10 * e)
        call pacify (prt%p2, 1e4 * e)
    end subroutine pacify_particle

```

```

end subroutine pacify_particle

subroutine pacify_particle_set (pset)
  class(particle_set_t), intent(inout) :: pset
  integer :: i
  do i = 1, pset%n_tot
    call pacify (pset%prt(i))
  end do
end subroutine pacify_particle_set

```

14.2.5 Unit tests

Set up a chain of production and decay and factorize the result into particles.
The process is $d\bar{d} \rightarrow Z \rightarrow q\bar{q}$.

```

⟨Particles: public⟩+=
  public :: particles_test

⟨Particles: procedures⟩+=
  subroutine particles_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  ⟨Particles: execute tests⟩
  end subroutine particles_test

```

Check the basic setup of the particle_set_t type.

```

⟨Particles: execute tests⟩=
  call test (particles_1, "particles_1", &
    "check particle_set routines", &
    u, results)

⟨Particles: tests⟩=
  subroutine particles_1 (u)
    use os_interface
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t), dimension(3) :: flv
    type(color_t), dimension(3) :: col
    type(helicity_t), dimension(3) :: hel
    type(quantum_numbers_t), dimension(3) :: qn
    type(vector4_t), dimension(3) :: p
    type(interaction_t), target :: int1, int2
    type(quantum_numbers_mask_t) :: qn_mask_conn
    type(evaluator_t), target :: eval
    type(interaction_t) :: int
    type(particle_set_t) :: particle_set1, particle_set2
    type(particle_set_t) :: particle_set3, particle_set4
    type(subevt_t) :: subevt
    logical :: ok
    integer :: unit, iostat

    write (u, "(A)")  "* Test output: Particles"
    write (u, "(A)")  "* Purpose: test particle_set routines"
    write (u, "(A)")

```

```

write (u, "(A)")  "** Reading model file"

call model%init_sm_test ()

write (u, "(A)")
write (u, "(A)")  "** Initializing production process"

call int1%basic_init (2, 0, 1, set_relations=.true.)
call flv%init ([1, -1, 23], model)
call col%init_col_acl ([0, 0, 0], [0, 0, 0])
call hel(3)%init (1, 1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0.25_default, 0._default))
call hel(3)%init (1,-1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0._default, 0.25_default))
call hel(3)%init (-1, 1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0._default,-0.25_default))
call hel(3)%init (-1,-1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0.25_default, 0._default))
call hel(3)%init (0, 0)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0.5_default, 0._default))
call int1%freeze ()
p(1) = vector4_moving (45._default, 45._default, 3)
p(2) = vector4_moving (45._default,-45._default, 3)
p(3) = p(1) + p(2)
call int1%set_momenta (p)

write (u, "(A)")
write (u, "(A)")  "** Setup decay process"

call int2%basic_init (1, 0, 2, set_relations=.true.)
call flv%init ([23, 1, -1], model)
call col%init_col_acl ([0, 501, 0], [0, 0, 501])
call hel%init ([1, 1, 1], [1, 1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(1._default, 0._default))
call hel%init ([1, 1, 1], [-1,-1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0._default, 0.1_default))
call hel%init ([-1,-1,-1], [1, 1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0._default,-0.1_default))
call hel%init ([-1,-1,-1], [-1,-1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(1._default, 0._default))
call hel%init ([0, 1,-1], [0, 1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(4._default, 0._default))
call hel%init ([0,-1, 1], [0, 1,-1])

```

```

call qn%init (flv, col, hel)
call int2%add_state (qn, value=(2._default, 0._default))
call hel%init ([0, 1,-1], [0,-1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(2._default, 0._default))
call hel%init ([0,-1, 1], [0,-1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(4._default, 0._default))
call flv%init ([23, 2, -2], model)
call hel%init ([0, 1,-1], [0, 1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0.5_default, 0._default))
call hel%init ([0,-1, 1], [0,-1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0.5_default, 0._default))
call int2%freeze ()
p(2) = vector4_moving (45._default, 45._default, 2)
p(3) = vector4_moving (45._default,-45._default, 2)
call int2%set_momenta (p)
call int2%set_source_link (1, int1, 3)
call int1%basic_write (u)
call int2%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Concatenate production and decay"

call eval%init_product (int1, int2, qn_mask_conn, &
    connections_are_resonant=.true.)
call eval%receive_momenta ()
call eval%evaluate ()
call eval%write (u)

write (u, "(A)")
write (u, "(A)")  "* Factorize as subevent (complete, polarized)"
write (u, "(A)")

int = eval%interaction_t
call particle_set1%init &
    (ok, int, int, FM_FACTOR_HELICITY, &
    [0.2_default, 0.2_default], .false., .true.)
call particle_set1%write (u)

write (u, "(A)")
write (u, "(A)")  "* Factorize as subevent (in/out only, selected helicity)"
write (u, "(A)")

int = eval%interaction_t
call particle_set2%init &
    (ok, int, int, FM_SELECT_HELICITY, &
    [0.9_default, 0.9_default], .false., .false.)
call particle_set2%write (u)
call particle_set2%final ()

write (u, "(A)")

```



```

write (u, "(A)")  "* Factorize as subevent (complete, selected helicity)"
write (u, "(A)")

int = eval%interaction_t
call particle_set2%init &
      (ok, int, int, FM_SELECT_HELICITY, &
       [0.7_default, 0.7_default], .false., .true.)
call particle_set2%write (u)

write (u, "(A)")
write (u, "(A)")  &
      "* Factorize (complete, polarized, correlated); write and read again"
write (u, "(A)")

int = eval%interaction_t
call particle_set3%init &
      (ok, int, int, FM_FACTOR_HELICITY, &
       [0.7_default, 0.7_default], .true., .true.)
call particle_set3%write (u)

unit = free_unit ()
open (unit, action="readwrite", form="unformatted", status="scratch")
call particle_set3%write_raw (unit)
rewind (unit)
call particle_set4%read_raw (unit, iostat=iostat)
call particle_set4%set_model (model)
close (unit)

write (u, "(A)")
write (u, "(A)")  "* Result from reading"
write (u, "(A)")

call particle_set4%write (u)

write (u, "(A)")
write (u, "(A)")  "* Transform to a subevt object"
write (u, "(A)")

call particle_set4%to_subevt (subevt)
call subevt_write (subevt, u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call particle_set1%final ()
call particle_set2%final ()
call particle_set3%final ()
call particle_set4%final ()
call eval%final ()
call int1%final ()
call int2%final ()

call model%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Test output end: particles_1"

end subroutine particles_1

```

Reconstruct a hard interaction from a particle set.

```

<Particles: execute tests>+≡
  call test (particles_2, "particles_2", &
    "reconstruct hard interaction", &
    u, results)

<Particles: tests>+≡
  subroutine particles_2 (u)

    integer, intent(in) :: u
    type(interaction_t) :: int
    type(state_flv_content_t) :: state_flv
    type(particle_set_t) :: pset
    type(flavor_t), dimension(:), allocatable :: flv
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: i, j

    write (u, "(A)")  "* Test output: Particles"
    write (u, "(A)")  "* Purpose: reconstruct simple interaction"
    write (u, "(A)")

    write (u, "(A)")  "* Set up a 2 -> 3 interaction"
    write (u, "(A)")  "    + incoming partons marked as virtual"
    write (u, "(A)")  "    + no quantum numbers"
    write (u, "(A)")

    call reset_interaction_counter ()
    call int%basic_init (0, 2, 3)
    do i = 1, 2
      do j = 3, 5
        call int%relate (i, j)
      end do
    end do

    allocate (qn (5))
    call int%add_state(qn)
    call int%freeze ()

    call int%basic_write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Manually set up a flavor-content record"
    write (u, "(A)")

    call state_flv%init (1, &
      mask = [.false., .false., .true., .true., .true.])
    call state_flv%set_entry (1, &
      pdg = [11, 12, 3, 4, 5], &
      map = [1, 2, 3, 4, 5])

```

```

call state_flv%write (u)

write (u, "(A)")
write (u, "(A)")  "* Manually create a matching particle set"
write (u, "(A)")

pset%n_beam = 0
pset%n_in   = 2
pset%n_vir  = 0
pset%n_out  = 3
pset%n_tot  = 5
allocate (pset%prt (pset%n_tot))
do i = 1, 2
    call pset%prt(i)%reset_status (PRT_INCOMING)
    call pset%prt(i)%set_children ([3,4,5])
end do
do i = 3, 5
    call particle_reset_status (pset%prt(i), PRT_OUTGOING)
    call particle_set_parents (pset%prt(i), [1,2])
end do
call pset%prt(1)%set_momentum (vector4_at_rest (1._default))
call pset%prt(2)%set_momentum (vector4_at_rest (2._default))
call pset%prt(3)%set_momentum (vector4_at_rest (5._default))
call pset%prt(4)%set_momentum (vector4_at_rest (4._default))
call pset%prt(5)%set_momentum (vector4_at_rest (3._default))

allocate (flv (5))
call flv%init ([11,12,5,4,3])
do i = 1, 5
    call pset%prt(i)%set_flavor (flv(i))
end do

call pset%write (u)

write (u, "(A)")
write (u, "(A)")  "* Fill interaction from particle set"
write (u, "(A)")

call pset%fill_interaction (int, 2, state_flv=state_flv)
call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call int%final ()
call pset%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: particles_2"

end subroutine particles_2

```

Reconstruct an interaction with beam structure, e.g., a hadronic interaction,

from a particle set.

```

<Particles: execute tests>+≡
  call test (particles_3, "particles_3", &
    "reconstruct interaction with beam structure", &
    u, results)
<Particles: tests>+≡
  subroutine particles_3 (u)

    integer, intent(in) :: u
    type(interaction_t) :: int
    type(state_flv_content_t) :: state_flv
    type(particle_set_t) :: pset
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: i, j

    write (u, "(A)")  "* Test output: Particles"
    write (u, "(A)")  "*   Purpose: reconstruct simple interaction"
    write (u, "(A)")

    write (u, "(A)")  "* Set up a 2 -> 2 -> 3 interaction with radiation"
    write (u, "(A)")  "      + no quantum numbers"
    write (u, "(A)")

    call reset_interaction_counter ()
    call int%basic_init (0, 6, 3)
    call int%relate (1, 3)
    call int%relate (1, 4)
    call int%relate (2, 5)
    call int%relate (2, 6)
    do i = 4, 6, 2
      do j = 7, 9
        call int%relate (i, j)
      end do
    end do

    allocate (qn (9))
    call int%add_state (qn)
    call int%freeze ()

    call int%basic_write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Manually set up a flavor-content record"
    write (u, "(A)")

    call state_flv%init (1, &
      mask = [.false., .false., .false., .false., .false., .false., &
        .true., .true., .true.])
    call state_flv%set_entry (1, &
      pdg = [2011, 2012, 91, 11, 92, 12, 3, 4, 5], &
      map = [1, 2, 3, 4, 5, 6, 7, 8, 9])

    call state_flv%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Manually create a matching particle set"
write (u, "(A)")

call create_test_particle_set_1 (pset)

call pset%write (u)

write (u, "(A)")
write (u, "(A)")  "* Fill interaction from particle set"
write (u, "(A)")

call pset%fill_interaction (int, 2, state_flg=state_flg)
call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call int%final ()
call pset%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: particles_3"

end subroutine particles_3

```

(Particles: procedures)+≡

```

subroutine create_test_particle_set_1 (pset)
  type(particle_set_t), intent(out) :: pset
  type(flavor_t), dimension(:), allocatable :: flv
  integer :: i
  pset%n_beam = 2
  pset%n_in   = 2
  pset%n_vir  = 2
  pset%n_out  = 3
  pset%n_tot  = 9

  allocate (pset%prt (pset%n_tot))
  call pset%prt(1)%reset_status (PRT_BEAM)
  call pset%prt(2)%reset_status (PRT_BEAM)
  call pset%prt(3)%reset_status (PRT_INCOMING)
  call pset%prt(4)%reset_status (PRT_INCOMING)
  call pset%prt(5)%reset_status (PRT_BEAM_REMNANT)
  call pset%prt(6)%reset_status (PRT_BEAM_REMNANT)
  call pset%prt(7)%reset_status (PRT_OUTGOING)
  call pset%prt(8)%reset_status (PRT_OUTGOING)
  call pset%prt(9)%reset_status (PRT_OUTGOING)

  call pset%prt(1)%set_children ([3,5])
  call pset%prt(2)%set_children ([4,6])
  call pset%prt(3)%set_children ([7,8,9])
  call pset%prt(4)%set_children ([7,8,9])

  call pset%prt(3)%set_parents ([1])

```

```

call pset%prt(4)%set_parents ([2])
call pset%prt(5)%set_parents ([1])
call pset%prt(6)%set_parents ([2])
call pset%prt(7)%set_parents ([3,4])
call pset%prt(8)%set_parents ([3,4])
call pset%prt(9)%set_parents ([3,4])

call pset%prt(1)%set_momentum (vector4_at_rest (1._default))
call pset%prt(2)%set_momentum (vector4_at_rest (2._default))
call pset%prt(3)%set_momentum (vector4_at_rest (4._default))
call pset%prt(4)%set_momentum (vector4_at_rest (6._default))
call pset%prt(5)%set_momentum (vector4_at_rest (3._default))
call pset%prt(6)%set_momentum (vector4_at_rest (5._default))
call pset%prt(7)%set_momentum (vector4_at_rest (7._default))
call pset%prt(8)%set_momentum (vector4_at_rest (8._default))
call pset%prt(9)%set_momentum (vector4_at_rest (9._default))

allocate (flv (9))
call flv%init ([2011, 2012, 11, 12, 91, 92, 3, 4, 5])
do i = 1, 9
    call pset%prt(i)%set_flavor (flv(i))
end do
end subroutine create_test_particle_set_1

```

Reconstruct an interaction with beam structure, e.g., a hadronic interaction, from a particle set that is missing the beam information.

```

<Particles: execute tests>+≡
    call test (particles_4, "particles_4", &
        "reconstruct interaction with missing beams", &
        u, results)

<Particles: tests>+≡
    subroutine particles_4 (u)

        integer, intent(in) :: u
        type(interaction_t) :: int
        type(interaction_t), target :: int_beams
        type(state_flv_content_t) :: state_flv
        type(particle_set_t) :: pset
        type(flavor_t), dimension(:), allocatable :: flv
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        integer :: i, j

        write (u, "(A)")  "* Test output: Particles"
        write (u, "(A)")  "* Purpose: reconstruct beams"
        write (u, "(A)")

        call reset_interaction_counter ()

        write (u, "(A)")  "* Set up an interaction that contains beams only"
        write (u, "(A)")

        call int_beams%basic_init (0, 0, 2)
        call int_beams%set_momentum (vector4_at_rest (1._default), 1)

```

```

call int_beams%set_momentum (vector4_at_rest (2._default), 2)
allocate (qn (2))
call int_beams%add_state (qn)
call int_beams%freeze ()

call int_beams%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Set up a 2 -> 2 -> 3 interaction with radiation"
write (u, "(A)")  "    + no quantum numbers"
write (u, "(A)")

call int%basic_init (0, 6, 3)
call int%relate (1, 3)
call int%relate (1, 4)
call int%relate (2, 5)
call int%relate (2, 6)
do i = 4, 6, 2
  do j = 7, 9
    call int%relate (i, j)
  end do
end do
do i = 1, 2
  call int%set_source_link (i, int_beams, i)
end do

deallocate (qn)
allocate (qn (9))
call int%add_state (qn)
call int%freeze ()

call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Manually set up a flavor-content record"
write (u, "(A)")

call state_flv%init (1, &
  mask = [.false., .false., .false., .false., .false., .false., &
    .true., .true., .true.])
call state_flv%set_entry (1, &
  pdg = [2011, 2012, 91, 11, 92, 12, 3, 4, 5], &
  map = [1, 2, 3, 4, 5, 6, 7, 8, 9])

call state_flv%write (u)

write (u, "(A)")
write (u, "(A)")  "* Manually create a matching particle set"
write (u, "(A)")

pset%n_beam = 0
pset%n_in   = 2
pset%n_vir  = 0
pset%n_out  = 3

```

```

pset%n_tot = 5

allocate (pset%prt (pset%n_tot))
call pset%prt(1)%reset_status (PRT_INCOMING)
call pset%prt(2)%reset_status (PRT_INCOMING)
call pset%prt(3)%reset_status (PRT_OUTGOING)
call pset%prt(4)%reset_status (PRT_OUTGOING)
call pset%prt(5)%reset_status (PRT_OUTGOING)

call pset%prt(1)%set_children ([3,4,5])
call pset%prt(2)%set_children ([3,4,5])

call pset%prt(3)%set_parents ([1,2])
call pset%prt(4)%set_parents ([1,2])
call pset%prt(5)%set_parents ([1,2])

call pset%prt(1)%set_momentum (vector4_at_rest (6._default))
call pset%prt(2)%set_momentum (vector4_at_rest (6._default))
call pset%prt(3)%set_momentum (vector4_at_rest (3._default))
call pset%prt(4)%set_momentum (vector4_at_rest (4._default))
call pset%prt(5)%set_momentum (vector4_at_rest (5._default))

allocate (flv (5))
call flv%init ([11, 12, 3, 4, 5])
do i = 1, 5
    call pset%prt(i)%set_flavor (flv(i))
end do

call pset%write (u)

write (u, "(A)")
write (u, "(A)")  "*"   Fill interaction from particle set"
write (u, "(A)")

call pset%fill_interaction (int, 2, state_flv=state_flv, &
    recover_beams = .true.)
call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "*" Cleanup"

call int%final ()
call pset%final ()

write (u, "(A)")
write (u, "(A)")  "*" Test output end: particles_4"

end subroutine particles_4

```

Reconstruct an interaction with beam structure and cloned particles (radiated particles repeated in the event record, to maintain some canonical ordering).

(Particles: execute tests)+≡

```
call test (particles_5, "particles_5", &
```



```

        "reconstruct interaction with beams and duplicate entries", &
        u, results)
(Particles: tests)+=
subroutine particles_5 (u)

    integer, intent(in) :: u
    type(interaction_t) :: int
    type(state_flv_content_t) :: state_flv
    type(particle_set_t) :: pset
    type(flavor_t), dimension(:), allocatable :: flv
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: i, j

    write (u, "(A)")  "* Test output: Particles"
    write (u, "(A)")  "*   Purpose: reconstruct event with duplicate entries"
    write (u, "(A)")

    write (u, "(A)")  "* Set up a 2 -> 2 -> 3 interaction with radiation"
    write (u, "(A)")  "      + no quantum numbers"
    write (u, "(A)")

    call reset_interaction_counter ()
    call int%basic_init (0, 6, 3)
    call int%relate (1, 3)
    call int%relate (1, 4)
    call int%relate (2, 5)
    call int%relate (2, 6)
    do i = 4, 6, 2
        do j = 7, 9
            call int%relate (i, j)
        end do
    end do

    allocate (qn (9))
    call int%add_state (qn)
    call int%freeze ()

    call int%basic_write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Manually set up a flavor-content record"
    write (u, "(A)")

    call state_flv%init (1, &
        mask = [.false., .false., .false., .false., .false., .false., &
        .true., .true., .true.])
    call state_flv%set_entry (1, &
        pdg = [2011, 2012, 91, 11, 92, 12, 3, 4, 5], &
        map = [1, 2, 3, 4, 5, 6, 7, 8, 9])

    call state_flv%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Manually create a matching particle set"

```

```

write (u, "(A)")

pset%n_beam = 2
pset%n_in   = 2
pset%n_vir  = 4
pset%n_out  = 5
pset%n_tot  = 13

allocate (pset%prt (pset%n_tot))
call pset%prt(1)%reset_status (PRT_BEAM)
call pset%prt(2)%reset_status (PRT_BEAM)
call pset%prt(3)%reset_status (PRT_VIRTUAL)
call pset%prt(4)%reset_status (PRT_VIRTUAL)
call pset%prt(5)%reset_status (PRT_VIRTUAL)
call pset%prt(6)%reset_status (PRT_VIRTUAL)
call pset%prt(7)%reset_status (PRT_INCOMING)
call pset%prt(8)%reset_status (PRT_INCOMING)
call pset%prt( 9)%reset_status (PRT_OUTGOING)
call pset%prt(10)%reset_status (PRT_OUTGOING)
call pset%prt(11)%reset_status (PRT_OUTGOING)
call pset%prt(12)%reset_status (PRT_OUTGOING)
call pset%prt(13)%reset_status (PRT_OUTGOING)

call pset%prt(1)%set_children ([3,4])
call pset%prt(2)%set_children ([5,6])
call pset%prt(3)%set_children ([ 7])
call pset%prt(4)%set_children ([ 9])
call pset%prt(5)%set_children ([ 8])
call pset%prt(6)%set_children ([10])
call pset%prt(7)%set_children ([11,12,13])
call pset%prt(8)%set_children ([11,12,13])

call pset%prt(3)%set_parents ([1])
call pset%prt(4)%set_parents ([1])
call pset%prt(5)%set_parents ([2])
call pset%prt(6)%set_parents ([2])
call pset%prt( 7)%set_parents ([3])
call pset%prt( 8)%set_parents ([5])
call pset%prt( 9)%set_parents ([4])
call pset%prt(10)%set_parents ([6])
call pset%prt(11)%set_parents ([7,8])
call pset%prt(12)%set_parents ([7,8])
call pset%prt(13)%set_parents ([7,8])

call pset%prt(1)%set_momentum (vector4_at_rest (1._default))
call pset%prt(2)%set_momentum (vector4_at_rest (2._default))
call pset%prt(3)%set_momentum (vector4_at_rest (4._default))
call pset%prt(4)%set_momentum (vector4_at_rest (3._default))
call pset%prt(5)%set_momentum (vector4_at_rest (6._default))
call pset%prt(6)%set_momentum (vector4_at_rest (5._default))
call pset%prt(7)%set_momentum (vector4_at_rest (4._default))
call pset%prt(8)%set_momentum (vector4_at_rest (6._default))
call pset%prt( 9)%set_momentum (vector4_at_rest (3._default))
call pset%prt(10)%set_momentum (vector4_at_rest (5._default))

```

```

call pset%prt(11)%set_momentum (vector4_at_rest (7._default))
call pset%prt(12)%set_momentum (vector4_at_rest (8._default))
call pset%prt(13)%set_momentum (vector4_at_rest (9._default))

allocate (flv (13))
call flv%init ([2011, 2012, 11, 91, 12, 92, 11, 12, 91, 92, 3, 4, 5])
do i = 1, 13
    call pset%prt(i)%set_flavor (flv(i))
end do

call pset%write (u)

write (u, "(A)")
write (u, "(A)")  "*   Fill interaction from particle set"
write (u, "(A)")

call pset%fill_interaction (int, 2, state_flv=state_flv)
call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call int%final ()
call pset%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: particles_5"

end subroutine particles_5

```

Reconstruct an interaction with pair spectrum, e.g., beamstrahlung from a particle set.

```

<Particles: execute tests>+≡
    call test (particles_6, "particles_6", &
        "reconstruct interaction with pair spectrum", &
        u, results)

<Particles: tests>+≡
    subroutine particles_6 (u)

        integer, intent(in) :: u
        type(interaction_t) :: int
        type(state_flv_content_t) :: state_flv
        type(particle_set_t) :: pset
        type(flavor_t), dimension(:), allocatable :: flv
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        integer :: i, j

        write (u, "(A)")  "* Test output: Particles"
        write (u, "(A)")  "*   Purpose: reconstruct interaction with pair spectrum"
        write (u, "(A)")

        write (u, "(A)")  "* Set up a 2 -> 2 -> 3 interaction with radiation"
        write (u, "(A)")  "    + no quantum numbers"
    end subroutine particles_6

```

```

write (u, "(A)")

call reset_interaction_counter ()
call int%basic_init (0, 6, 3)
do i = 1, 2
  do j = 3, 6
    call int%relate (i, j)
  end do
end do
do i = 5, 6
  do j = 7, 9
    call int%relate (i, j)
  end do
end do

allocate (qn (9))
call int%add_state (qn)
call int%freeze ()

call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Manually set up a flavor-content record"
write (u, "(A)")

call state_flv%init (1, &
  mask = [.false., .false., .false., .false., .false., .false., &
    .true., .true., .true.])
call state_flv%set_entry (1, &
  pdg = [1011, 1012, 21, 22, 11, 12, 3, 4, 5], &
  map = [1, 2, 3, 4, 5, 6, 7, 8, 9])

call state_flv%write (u)

write (u, "(A)")
write (u, "(A)")  "* Manually create a matching particle set"
write (u, "(A)")

pset%n_beam = 2
pset%n_in   = 2
pset%n_vir  = 2
pset%n_out  = 3
pset%n_tot  = 9

allocate (pset%prt (pset%n_tot))
call pset%prt(1)%reset_status (PRT_BEAM)
call pset%prt(2)%reset_status (PRT_BEAM)
call pset%prt(3)%reset_status (PRT_INCOMING)
call pset%prt(4)%reset_status (PRT_INCOMING)
call pset%prt(5)%reset_status (PRT_OUTGOING)
call pset%prt(6)%reset_status (PRT_OUTGOING)
call pset%prt(7)%reset_status (PRT_OUTGOING)
call pset%prt(8)%reset_status (PRT_OUTGOING)
call pset%prt(9)%reset_status (PRT_OUTGOING)

```

```

call pset%prt(1)%set_children ([3,4,5,6])
call pset%prt(2)%set_children ([3,4,5,6])
call pset%prt(3)%set_children ([7,8,9])
call pset%prt(4)%set_children ([7,8,9])

call pset%prt(3)%set_parents ([1,2])
call pset%prt(4)%set_parents ([1,2])
call pset%prt(5)%set_parents ([1,2])
call pset%prt(6)%set_parents ([1,2])
call pset%prt(7)%set_parents ([3,4])
call pset%prt(8)%set_parents ([3,4])
call pset%prt(9)%set_parents ([3,4])

call pset%prt(1)%set_momentum (vector4_at_rest (1._default))
call pset%prt(2)%set_momentum (vector4_at_rest (2._default))
call pset%prt(3)%set_momentum (vector4_at_rest (5._default))
call pset%prt(4)%set_momentum (vector4_at_rest (6._default))
call pset%prt(5)%set_momentum (vector4_at_rest (3._default))
call pset%prt(6)%set_momentum (vector4_at_rest (4._default))
call pset%prt(7)%set_momentum (vector4_at_rest (7._default))
call pset%prt(8)%set_momentum (vector4_at_rest (8._default))
call pset%prt(9)%set_momentum (vector4_at_rest (9._default))

allocate (flv (9))
call flv%init ([1011, 1012, 11, 12, 21, 22, 3, 4, 5])
do i = 1, 9
    call pset%prt(i)%set_flavor (flv(i))
end do

call pset%write (u)

write (u, "(A)")
write (u, "(A)")  "*"   Fill interaction from particle set"
write (u, "(A)")

call pset%fill_interaction (int, 2, state_flv=state_flv)
call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "*" Cleanup"

call int%final ()
call pset%final ()

write (u, "(A)")
write (u, "(A)")  "*" Test output end: particles_6"

end subroutine particles_6

```

Reconstruct a hard decay interaction from a shuffled particle set.

```

<Particles: execute tests>+≡
    call test (particles_7, "particles_7", &

```

```

        "reconstruct decay interaction with reordering", &
        u, results)
(Particles: tests)+≡
subroutine particles_7 (u)

    integer, intent(in) :: u
    type(interaction_t) :: int
    type(state_flv_content_t) :: state_flv
    type(particle_set_t) :: pset
    type(flavor_t), dimension(:), allocatable :: flv
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: i, j

    write (u, "(A)")  "* Test output: Particles"
    write (u, "(A)")  "* Purpose: reconstruct decay interaction with reordering"
    write (u, "(A)")

    write (u, "(A)")  "* Set up a 1 -> 3 interaction"
    write (u, "(A)")  "    + no quantum numbers"
    write (u, "(A)")

    call reset_interaction_counter ()
    call int%basic_init (0, 1, 3)
    do j = 2, 4
        call int%relate (1, j)
    end do

    allocate (qn (4))
    call int%add_state (qn)
    call int%freeze ()

    call int%basic_write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Manually set up a flavor-content record"
    write (u, "(A)")  "* assumed interaction: 6 12 5 -11"
    write (u, "(A)")

    call state_flv%init (1, &
        mask = [.false., .true., .true., .true.])
    call state_flv%set_entry (1, &
        pdg = [6, 5, -11, 12], &
        map = [1, 4, 2, 3])

    call state_flv%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Manually create a matching particle set"
    write (u, "(A)")

    pset%n_beam = 0
    pset%n_in   = 1
    pset%n_vir  = 0
    pset%n_out  = 3

```

```

pset%n_tot = 4
allocate (pset%prt (pset%n_tot))
do i = 1, 1
    call pset%prt(i)%reset_status (PRT_INCOMING)
    call pset%prt(i)%set_children ([2,3,4])
end do
do i = 2, 4
    call pset%prt(i)%reset_status (PRT_OUTGOING)
    call pset%prt(i)%set_parents ([1])
end do
call pset%prt(1)%set_momentum (vector4_at_rest (1._default))
call pset%prt(2)%set_momentum (vector4_at_rest (3._default))
call pset%prt(3)%set_momentum (vector4_at_rest (2._default))
call pset%prt(4)%set_momentum (vector4_at_rest (4._default))

allocate (flv (5))
call flv%init ([6,5,12,-11])
do i = 1, 4
    call pset%prt(i)%set_flavor (flv(i))
end do

call pset%write (u)

write (u, "(A)")
write (u, "(A)")  "*   Fill interaction from particle set"
write (u, "(A)")

call pset%fill_interaction (int, 1, state_flv=state_flv)
call int%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call int%final ()
call pset%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: particles_7"

end subroutine particles_7

<Particles: execute tests>+≡
call test(particles_8, "particles_8", &
    "Test functions on particle sets", u, results)

<Particles: procedures>+≡
subroutine particles_8 (u)
    integer, intent(in) :: u
    type(particle_set_t) :: particle_set
    type(particle_t), dimension(:), allocatable :: particles
    integer, allocatable, dimension(:) :: children, parents
    integer :: n_particles, i
    write (u, "(A)")  "* Test output: particles_8"
    write (u, "(A)")  "*   Purpose: Test functions on particle sets"

```

```

write (u, "(A)")

call create_test_particle_set_1 (particle_set)
call particle_set%write (u)
call assert_equal (u, particle_set%n_tot, 9)
call assert_equal (u, particle_set%n_beam, 2)
children = particle_set%prt(3)%get_children()
call assert_equal (u, particle_set%prt(children(1))%get_pdg (), 3)
call assert_equal (u, size (particle_set%prt(1)%get_children ()), 2)
call assert_equal (u, size (particle_set%prt(2)%get_children ()), 2)

call particle_set%without_hadronic_remnants &
    (particles, n_particles, 3)
call particle_set%replace (particles)
write (u, "(A)")
call particle_set%write (u)

call assert_equal (u, n_particles, 7)
call assert_equal (u, size(particles), 10)
call assert_equal (u, particle_set%n_tot, 10)
call assert_equal (u, particle_set%n_beam, 2)
do i = 3, 4
    children = particle_set%prt(i)%get_children()
    call assert_equal (u, particle_set%prt(children(1))%get_pdg (), 3)
    children = particle_set%prt(i)%get_children()
    call assert_equal (u, particle_set%prt(children(2))%get_pdg (), 4)
    children = particle_set%prt(i)%get_children()
    call assert_equal (u, particle_set%prt(children(3))%get_pdg (), 5)
end do
do i = 5, 7
    parents = particle_set%prt(i)%get_parents()
    call assert_equal (u, particle_set%prt(parents(1))%get_pdg (), 11)
    call assert_equal (u, particle_set%prt(parents(2))%get_pdg (), 12)
end do
call assert_equal (u, size (particle_set%prt(1)%get_children ()), &
    1, "get children of 1")
call assert_equal (u, size (particle_set%prt(2)%get_children ()), &
    1, "get children of 2")

call assert_equal(u, particle_set%find_particle &
    (particle_set%prt(1)%get_pdg (), particle_set%prt(1)%p), &
    1, "find 1st particle")
call assert_equal(u, particle_set%find_particle &
    (particle_set%prt(2)%get_pdg (), particle_set%prt(2)%p * &
    (one + tiny_07), rel_smallness=1.0E-6_default), &
    2, "find 2nd particle fuzzy")

write (u, "(A)")
write (u, "(A)")  "* Test output end: particles_8"
end subroutine particles_8

```


Chapter 15

Beams

These modules implement beam configuration and beam structure, the latter in abstract terms.

beam_structures The `beam_structure_t` type is a messenger type that communicates the user settings to the **WHIZARD** core.

beams Beam configuration.

sf_aux Tools for handling structure functions and splitting

sf_mappings Mapping functions, useful for structure function implementation

sf_base The abstract structure-function interaction and structure-function chain types.

These are the implementation modules, the concrete counterparts of **sf_base**:

sf_isr ISR structure function (photon radiation inclusive and resummed in collinear and IR regions).

sf_epa Effective Photon Approximation.

sf_ewa Effective W (and Z) approximation.

sf_escan Energy spectrum that emulates a uniform energy scan.

sf_beam_events Beam-event generator that reads its input from an external file.

sf_circe1 CIRCE1 beam spectra for electrons and photons.

sf_circe2 CIRCE2 beam spectra for electrons and photons.

hoppet_interface Support for b -quark matching, add-on to PDF modules.

sf_pdf_builtin Direct support for selected hadron PDFs.

sf_lhapdf LHAPDF library support.

15.1 Beam structure

This module stores the beam structure definition as it is declared in the SINDARIN script. The structure definition is not analyzed, just recorded for later use.

We do not capture any numerical parameters, just names of particles and structure functions.

```
(beam_structures.f90)≡  
  <File header>  
  
  module beam_structures  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use format_defs, only: FMT_19  
    use unit_tests  
    use diagnostics  
    use lorentz  
    use polarizations  
  
    <Standard module head>  
  
    <Beam structures: public>  
  
    <Beam structures: types>  
  
    <Beam structures: interfaces>  
  
    contains  
  
    <Beam structures: procedures>  
  
    <Beam structures: tests>  
  
  end module beam_structures
```

15.1.1 Beam structure elements

An entry in a beam-structure record consists of a string that denotes a type of structure function.

```
<Beam structures: types>≡  
  type :: beam_structure_entry_t  
    logical :: is_valid = .false.  
    type(string_t) :: name  
    contains  
    <Beam structures: beam structure entry: TBP>  
  end type beam_structure_entry_t
```

Output.

```
<Beam structures: beam structure entry: TBP>≡  
  procedure :: to_string => beam_structure_entry_to_string
```

```

<Beam structures: procedures>≡
  function beam_structure_entry_to_string (object) result (string)
    class (beam_structure_entry_t), intent(in) :: object
    type(string_t) :: string
    if (object%is_valid) then
      string = object%name
    else
      string = "none"
    end if
  end function beam_structure_entry_to_string

```

A record in the beam-structure sequence denotes either a structure-function entry, a pair of such entries, or a pair spectrum.

```

<Beam structures: types>+≡
  type :: beam_structure_record_t
    type (beam_structure_entry_t), dimension(:), allocatable :: entry
  end type beam_structure_record_t

```

15.1.2 Beam structure type

The beam-structure object contains the beam particle(s) as simple strings. The sequence of records indicates the structure functions by name. No numerical parameters are stored.

```

<Beam structures: public>≡
  public :: beam_structure_t

<Beam structures: types>+≡
  type :: beam_structure_t
    private
    integer :: n_beam = 0
    type(string_t), dimension(:), allocatable :: prt
    type (beam_structure_record_t), dimension(:), allocatable :: record
    type (smatrix_t), dimension(:), allocatable :: smatrix
    real(default), dimension(:), allocatable :: pol_f
    real(default), dimension(:), allocatable :: p
    real(default), dimension(:), allocatable :: theta
    real(default), dimension(:), allocatable :: phi
  contains
    <Beam structures: beam structure: TBP>
  end type beam_structure_t

```

The finalizer deletes all contents explicitly, so we can continue with an empty beam record. (It is not needed for deallocation.) We have distinct finalizers for the independent parts of the beam structure.

```

<Beam structures: beam structure: TBP>≡
  procedure :: final_sf => beam_structure_final_sf

<Beam structures: procedures>+≡
  subroutine beam_structure_final_sf (object)
    class (beam_structure_t), intent(inout) :: object
    if (allocated (object%prt)) deallocate (object%prt)
    if (allocated (object%record)) deallocate (object%record)
  end subroutine beam_structure_final_sf

```

```

    object%n_beam = 0
end subroutine beam_structure_final_sf

```

Output. The actual information fits in a single line, therefore we can provide a `to_string` method. The `show` method also lists the current values of relevant global variables.

```

(Beam structures: beam structure: TBP)+≡
    procedure :: write => beam_structure_write
    procedure :: to_string => beam_structure_to_string

(Beam structures: procedures)+≡
    subroutine beam_structure_write (object, unit)
        class(beam_structure_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit)
        write (u, "(1x,A,A)") "Beam structure: ", char (object%to_string ())
        if (allocated (object%smatrix)) then
            do i = 1, size (object%smatrix)
                write (u, "(3x,A,I0,A)") "polarization (beam ", i, "):"
                call object%smatrix(i)%write (u, indent=2)
            end do
        end if
        if (allocated (object%pol_f)) then
            write (u, "(3x,A,F10.7,:',',F10.7)") "polarization degree =", &
                object%pol_f
        end if
        if (allocated (object%p)) then
            write (u, "(3x,A," // FMT_19 // ",:',','," // FMT_19 // &
                ")") "momentum =", object%p
        end if
        if (allocated (object%theta)) then
            write (u, "(3x,A," // FMT_19 // ",:',','," // FMT_19 // &
                ")") "angle th =", object%theta
        end if
        if (allocated (object%phi)) then
            write (u, "(3x,A," // FMT_19 // ",:',','," // FMT_19 // &
                ")") "angle ph =", object%phi
        end if
    end subroutine beam_structure_write

    function beam_structure_to_string (object, sf_only) result (string)
        class(beam_structure_t), intent(in) :: object
        logical, intent(in), optional :: sf_only
        type(string_t) :: string
        integer :: i, j
        logical :: with_beams
        with_beams = .true.; if (present (sf_only)) with_beams = .not. sf_only
        select case (object%n_beam)
        case (1)
            if (with_beams) then
                string = object%prt(1)
            else
                string = ""
            end if
        end select
    end function beam_structure_to_string

```

```

        end if
    case (2)
        if (with_beams) then
            string = object%prt(1) // ", " // object%prt(2)
        else
            string = ""
        end if
        if (allocated (object%record)) then
            if (size (object%record) > 0) then
                if (with_beams) string = string // " => "
                do i = 1, size (object%record)
                    if (i > 1) string = string // " => "
                    do j = 1, size (object%record(i)%entry)
                        if (j > 1) string = string // ", "
                        string = string // object%record(i)%entry(j)%to_string ()
                    end do
                end do
            end if
        end if
    case default
        string = "[any particles]"
    end select
end function beam_structure_to_string

```

Initializer: dimension the beam structure record. Each array element denotes the number of entries for a record within the beam-structure sequence. The number of entries is either one or two, while the number of records is unlimited.

(Beam structures: beam structure: TBP)+≡

```

    procedure :: init_sf => beam_structure_init_sf

```

(Beam structures: procedures)+≡

```

    subroutine beam_structure_init_sf (beam_structure, prt, dim_array)
        class(beam_structure_t), intent(inout) :: beam_structure
        type(string_t), dimension(:), intent(in) :: prt
        integer, dimension(:), intent(in), optional :: dim_array
        integer :: i
        call beam_structure%final_sf ()
        beam_structure%n_beam = size (prt)
        allocate (beam_structure%prt (size (prt)))
        beam_structure%prt = prt
        if (present (dim_array)) then
            allocate (beam_structure%record (size (dim_array)))
            do i = 1, size (dim_array)
                allocate (beam_structure%record(i)%entry (dim_array(i)))
            end do
        else
            allocate (beam_structure%record (0))
        end if
    end subroutine beam_structure_init_sf

```

Set an entry, specified by record number and entry number.

(Beam structures: beam structure: TBP)+≡

```

    procedure :: set_sf => beam_structure_set_sf

```

```

<Beam structures: procedures>+≡
subroutine beam_structure_set_sf (beam_structure, i, j, name)
  class(beam_structure_t), intent(inout) :: beam_structure
  integer, intent(in) :: i, j
  type(string_t), intent(in) :: name
  associate (entry => beam_structure%record(i)%entry(j))
    entry%name = name
    entry%is_valid = .true.
  end associate
end subroutine beam_structure_set_sf

```

Expand the beam-structure object. (i) For a pair spectrum, keep the entry. (ii) For a single-particle structure function written as a single entry, replace this by a record with two entries. (ii) For a record with two nontrivial entries, separate this into two records with one trivial entry each.

To achieve this, we need a function that tells us whether an entry is a spectrum or a structure function. It returns 0 for a trivial entry, 1 for a single-particle structure function, and 2 for a two-particle spectrum.

```

<Beam structures: interfaces>≡
abstract interface
  function strfun_mode_fun (name) result (n)
  import
  type(string_t), intent(in) :: name
  integer :: n
end function strfun_mode_fun
end interface

```

Algorithm: (1) Mark entries as invalid where necessary. (2) Count the number of entries that we will need. (3) Expand and copy entries to a new record array. (4) Replace the old array by the new one.

```

<Beam structures: beam structure: TBP>+≡
procedure :: expand => beam_structure_expand

<Beam structures: procedures>+≡
subroutine beam_structure_expand (beam_structure, strfun_mode)
  class(beam_structure_t), intent(inout) :: beam_structure
  procedure(strfun_mode_fun) :: strfun_mode
  type(beam_structure_record_t), dimension(:), allocatable :: new
  integer :: n_record, i, j
  if (.not. allocated (beam_structure%record)) return
  do i = 1, size (beam_structure%record)
    associate (entry => beam_structure%record(i)%entry)
      do j = 1, size (entry)
        select case (strfun_mode (entry(j)%name))
          case (0); entry(j)%is_valid = .false.
        end select
      end do
    end associate
  end do
  n_record = 0
  do i = 1, size (beam_structure%record)
    associate (entry => beam_structure%record(i)%entry)
      select case (size (entry))

```

```

case (1)
  if (entry(1)%is_valid) then
    select case (strfun_mode (entry(1)%name))
      case (1); n_record = n_record + 2
      case (2); n_record = n_record + 1
    end select
  end if
case (2)
  do j = 1, 2
    if (entry(j)%is_valid) then
      select case (strfun_mode (entry(j)%name))
        case (1); n_record = n_record + 1
        case (2)
          call beam_structure%write ()
          call msg_fatal ("Pair spectrum used as &
            &single-particle structure function")
        end select
      end if
    end do
  end select
end associate
end do
allocate (new (n_record))
n_record = 0
do i = 1, size (beam_structure%record)
  associate (entry => beam_structure%record(i)%entry)
    select case (size (entry))
      case (1)
        if (entry(1)%is_valid) then
          select case (strfun_mode (entry(1)%name))
            case (1)
              n_record = n_record + 1
              allocate (new(n_record)%entry (2))
              new(n_record)%entry(1) = entry(1)
              n_record = n_record + 1
              allocate (new(n_record)%entry (2))
              new(n_record)%entry(2) = entry(1)
            case (2)
              n_record = n_record + 1
              allocate (new(n_record)%entry (1))
              new(n_record)%entry(1) = entry(1)
            end select
          end if
        case (2)
          do j = 1, 2
            if (entry(j)%is_valid) then
              n_record = n_record + 1
              allocate (new(n_record)%entry (2))
              new(n_record)%entry(j) = entry(j)
            end if
          end do
        end select
      end associate
    end do
  end do

```

```

    call move_alloc (from = new, to = beam_structure%record)
end subroutine beam_structure_expand

```

15.1.3 Polarization

To record polarization, we provide an allocatable array of `smatrix` objects, sparse matrices. The polarization structure is independent of the structure-function setup, they are combined only when an actual beam object is constructed.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: final_pol => beam_structure_final_pol
  procedure :: init_pol => beam_structure_init_pol

<Beam structures: procedures>+≡
  subroutine beam_structure_final_pol (beam_structure)
    class(beam_structure_t), intent(inout) :: beam_structure
    if (allocated (beam_structure%smatrix)) deallocate (beam_structure%smatrix)
    if (allocated (beam_structure%pol_f)) deallocate (beam_structure%pol_f)
  end subroutine beam_structure_final_pol

  subroutine beam_structure_init_pol (beam_structure, n)
    class(beam_structure_t), intent(inout) :: beam_structure
    integer, intent(in) :: n
    if (allocated (beam_structure%smatrix)) deallocate (beam_structure%smatrix)
    allocate (beam_structure%smatrix (n))
    if (.not. allocated (beam_structure%pol_f)) &
      allocate (beam_structure%pol_f (n), source = 1._default)
  end subroutine beam_structure_init_pol

```

Directly copy the spin density matrices.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: set_smatrix => beam_structure_set_smatrix

<Beam structures: procedures>+≡
  subroutine beam_structure_set_smatrix (beam_structure, i, smatrix)
    class(beam_structure_t), intent(inout) :: beam_structure
    integer, intent(in) :: i
    type(smatrix_t), intent(in) :: smatrix
    beam_structure%smatrix(i) = smatrix
  end subroutine beam_structure_set_smatrix

```

Initialize one of the spin density matrices manually.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: init_smatrix => beam_structure_init_smatrix

<Beam structures: procedures>+≡
  subroutine beam_structure_init_smatrix (beam_structure, i, n_entry)
    class(beam_structure_t), intent(inout) :: beam_structure
    integer, intent(in) :: i
    integer, intent(in) :: n_entry
    call beam_structure%smatrix(i)%init (2, n_entry)
  end subroutine beam_structure_init_smatrix

```


Set a polarization entry.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: set_sentry => beam_structure_set_sentry

<Beam structures: procedures>+≡
  subroutine beam_structure_set_sentry &
    (beam_structure, i, i_entry, index, value)
    class(beam_structure_t), intent(inout) :: beam_structure
    integer, intent(in) :: i
    integer, intent(in) :: i_entry
    integer, dimension(:), intent(in) :: index
    complex(default), intent(in) :: value
    call beam_structure%smatrix(i)%set_entry (i_entry, index, value)
  end subroutine beam_structure_set_sentry

```

Set the array of polarization fractions.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: set_pol_f => beam_structure_set_pol_f

<Beam structures: procedures>+≡
  subroutine beam_structure_set_pol_f (beam_structure, f)
    class(beam_structure_t), intent(inout) :: beam_structure
    real(default), dimension(:), intent(in) :: f
    if (allocated (beam_structure%pol_f)) deallocate (beam_structure%pol_f)
    allocate (beam_structure%pol_f (size (f)), source = f)
  end subroutine beam_structure_set_pol_f

```

15.1.4 Beam momenta

By default, beam momenta are deduced from the `sqrts` value or from the mass of the decaying particle, assuming a c.m. setup. Here we set them explicitly.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: final_mom => beam_structure_final_mom

<Beam structures: procedures>+≡
  subroutine beam_structure_final_mom (beam_structure)
    class(beam_structure_t), intent(inout) :: beam_structure
    if (allocated (beam_structure%p)) deallocate (beam_structure%p)
    if (allocated (beam_structure%theta)) deallocate (beam_structure%theta)
    if (allocated (beam_structure%phi)) deallocate (beam_structure%phi)
  end subroutine beam_structure_final_mom

<Beam structures: beam structure: TBP>+≡
  procedure :: set_momentum => beam_structure_set_momentum
  procedure :: set_theta => beam_structure_set_theta
  procedure :: set_phi => beam_structure_set_phi

<Beam structures: procedures>+≡
  subroutine beam_structure_set_momentum (beam_structure, p)
    class(beam_structure_t), intent(inout) :: beam_structure
    real(default), dimension(:), intent(in) :: p
    if (allocated (beam_structure%p)) deallocate (beam_structure%p)
    allocate (beam_structure%p (size (p)), source = p)

```

```

end subroutine beam_structure_set_momentum

subroutine beam_structure_set_theta (beam_structure, theta)
  class(beam_structure_t), intent(inout) :: beam_structure
  real(default), dimension(:), intent(in) :: theta
  if (allocated (beam_structure%theta)) deallocate (beam_structure%theta)
  allocate (beam_structure%theta (size (theta)), source = theta)
end subroutine beam_structure_set_theta

subroutine beam_structure_set_phi (beam_structure, phi)
  class(beam_structure_t), intent(inout) :: beam_structure
  real(default), dimension(:), intent(in) :: phi
  if (allocated (beam_structure%phi)) deallocate (beam_structure%phi)
  allocate (beam_structure%phi (size (phi)), source = phi)
end subroutine beam_structure_set_phi

```

15.1.5 Get contents

Look at the incoming particles. We may also have the case that beam particles are not specified, but polarization.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: is_set => beam_structure_is_set
  procedure :: get_n_beam => beam_structure_get_n_beam
  procedure :: get_prt => beam_structure_get_prt

<Beam structures: procedures>+≡
  function beam_structure_is_set (beam_structure) result (flag)
    class(beam_structure_t), intent(in) :: beam_structure
    logical :: flag
    flag = beam_structure%n_beam > 0 .or. beam_structure%asymmetric ()
  end function beam_structure_is_set

  function beam_structure_get_n_beam (beam_structure) result (n)
    class(beam_structure_t), intent(in) :: beam_structure
    integer :: n
    n = beam_structure%n_beam
  end function beam_structure_get_n_beam

  function beam_structure_get_prt (beam_structure) result (prt)
    class(beam_structure_t), intent(in) :: beam_structure
    type(string_t), dimension(:), allocatable :: prt
    allocate (prt (size (beam_structure%prt)))
    prt = beam_structure%prt
  end function beam_structure_get_prt

```

Return the number of records.

```

<Beam structures: beam structure: TBP>+≡
  procedure :: get_n_record => beam_structure_get_n_record

<Beam structures: procedures>+≡
  function beam_structure_get_n_record (beam_structure) result (n)
    class(beam_structure_t), intent(in) :: beam_structure
    integer :: n

```

```

    if (allocated (beam_structure%record)) then
        n = size (beam_structure%record)
    else
        n = 0
    end if
end function beam_structure_get_n_record

```

Return an array consisting of the beam indices affected by the valid entries within a record. After expansion, there should be exactly one valid entry per record.

```

⟨Beam structures: beam structure: TBP⟩+≡
    procedure :: get_i_entry => beam_structure_get_i_entry
⟨Beam structures: procedures⟩+≡
    function beam_structure_get_i_entry (beam_structure, i) result (i_entry)
        class(beam_structure_t), intent(in) :: beam_structure
        integer, intent(in) :: i
        integer, dimension(:), allocatable :: i_entry
        associate (record => beam_structure%record(i))
            select case (size (record%entry))
            case (1)
                if (record%entry(1)%is_valid) then
                    allocate (i_entry (2), source = [1, 2])
                else
                    allocate (i_entry (0))
                end if
            case (2)
                if (all (record%entry%is_valid)) then
                    allocate (i_entry (2), source = [1, 2])
                else if (record%entry(1)%is_valid) then
                    allocate (i_entry (1), source = [1])
                else if (record%entry(2)%is_valid) then
                    allocate (i_entry (1), source = [2])
                else
                    allocate (i_entry (0))
                end if
            end select
        end associate
    end function beam_structure_get_i_entry

```

Return the name of the first valid entry within a record. After expansion, there should be exactly one valid entry per record.

```

⟨Beam structures: beam structure: TBP⟩+≡
    procedure :: get_name => beam_structure_get_name
⟨Beam structures: procedures⟩+≡
    function beam_structure_get_name (beam_structure, i) result (name)
        class(beam_structure_t), intent(in) :: beam_structure
        integer, intent(in) :: i
        type(string_t) :: name
        associate (record => beam_structure%record(i))
            if (record%entry(1)%is_valid) then
                name = record%entry(1)%name
            else if (size (record%entry) == 2) then

```

```

        name = record%entry(2)%name
    end if
end associate
end function beam_structure_get_name

```

Return true if the beam structure contains a particular structure function identifier (such as `lhpdf`, `isr`, etc.)

```

<Beam structures: beam structure: TBP>+=
    procedure :: contains => beam_structure_contains

<Beam structures: procedures>+=
    function beam_structure_contains (beam_structure, name) result (flag)
        class(beam_structure_t), intent(in) :: beam_structure
        character(*), intent(in) :: name
        logical :: flag
        integer :: i, j
        flag = .false.
        if (allocated (beam_structure%record)) then
            do i = 1, size (beam_structure%record)
                do j = 1, size (beam_structure%record(i)%entry)
                    flag = beam_structure%record(i)%entry(j)%name == name
                    if (flag) return
                end do
            end do
        end if
    end function beam_structure_contains

```

Return polarization data.

```

<Beam structures: beam structure: TBP>+=
    procedure :: polarized => beam_structure_polarized
    procedure :: get_smatrix => beam_structure_get_smatrix
    procedure :: get_pol_f => beam_structure_get_pol_f
    procedure :: asymmetric => beam_structure_asymmetric

<Beam structures: procedures>+=
    function beam_structure_polarized (beam_structure) result (flag)
        class(beam_structure_t), intent(in) :: beam_structure
        logical :: flag
        flag = allocated (beam_structure%smatrix)
    end function beam_structure_polarized

    function beam_structure_get_smatrix (beam_structure) result (smatrix)
        class(beam_structure_t), intent(in) :: beam_structure
        type(smatrix_t), dimension(:), allocatable :: smatrix
        allocate (smatrix (size (beam_structure%smatrix)), &
            source = beam_structure%smatrix)
    end function beam_structure_get_smatrix

    function beam_structure_get_pol_f (beam_structure) result (pol_f)
        class(beam_structure_t), intent(in) :: beam_structure
        real(default), dimension(:), allocatable :: pol_f
        allocate (pol_f (size (beam_structure%pol_f)), &
            source = beam_structure%pol_f)
    end function beam_structure_get_pol_f

```

```

function beam_structure_asymmetric (beam_structure) result (flag)
  class(beam_structure_t), intent(in) :: beam_structure
  logical :: flag
  flag = allocated (beam_structure%p) &
    .or. allocated (beam_structure%theta) &
    .or. allocated (beam_structure%phi)
end function beam_structure_asymmetric

```

Return the beam momenta (the space part, i.e., three-momenta). This is meaningful only if momenta and, optionally, angles have been set.

(Beam structures: beam structure: TBP)+≡

```

procedure :: get_momenta => beam_structure_get_momenta

```

(Beam structures: procedures)+≡

```

function beam_structure_get_momenta (beam_structure) result (p)
  class(beam_structure_t), intent(in) :: beam_structure
  type(vector3_t), dimension(:), allocatable :: p
  real(default), dimension(:), allocatable :: theta, phi
  integer :: n, i
  if (allocated (beam_structure%p)) then
    n = size (beam_structure%p)
    if (allocated (beam_structure%theta)) then
      if (size (beam_structure%theta) == n) then
        allocate (theta (n), source = beam_structure%theta)
      else
        call msg_fatal ("Beam structure: mismatch in momentum vs. &
          &angle theta specification")
      end if
    else
      allocate (theta (n), source = 0._default)
    end if
    if (allocated (beam_structure%phi)) then
      if (size (beam_structure%phi) == n) then
        allocate (phi (n), source = beam_structure%phi)
      else
        call msg_fatal ("Beam structure: mismatch in momentum vs. &
          &angle phi specification")
      end if
    else
      allocate (phi (n), source = 0._default)
    end if
    allocate (p (n))
    do i = 1, n
      p(i) = beam_structure%p(i) * vector3_moving ([ &
        sin (theta(i)) * cos (phi(i)), &
        sin (theta(i)) * sin (phi(i)), &
        cos (theta(i))] )
    end do
    if (n == 2) p(2) = - p(2)
  else
    call msg_fatal ("Beam structure: angle theta/phi specified but &
      &momentum/a p undefined")
  end if

```

```
end function beam_structure_get_momenta
```

15.1.6 Unit Tests

```
<Beam structures: public>+≡
  public :: beam_structures_test

<Beam structures: tests>≡
  subroutine beam_structures_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    <Beam structures: execute tests>
  end subroutine beam_structures_test
```

Empty structure

```
<Beam structures: execute tests>≡
  call test (beam_structures_1, "beam_structures_1", &
    "empty beam structure record", &
    u, results)

<Beam structures: tests>+≡
  subroutine beam_structures_1 (u)
    integer, intent(in) :: u
    type(beam_structure_t) :: beam_structure

    write (u, "(A)")  "* Test output: beam_structures_1"
    write (u, "(A)")  "* Purpose: display empty beam structure record"
    write (u, "(A)")

    call beam_structure%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: beam_structures_1"

  end subroutine beam_structures_1
```

Nontrivial configurations

```
<Beam structures: execute tests>+≡
  call test (beam_structures_2, "beam_structures_2", &
    "beam structure records", &
    u, results)

<Beam structures: tests>+≡
  subroutine beam_structures_2 (u)
    integer, intent(in) :: u
    type(beam_structure_t) :: beam_structure
    integer, dimension(0) :: empty_array
    type(string_t) :: s

    write (u, "(A)")  "* Test output: beam_structures_2"
```

```

write (u, "(A)")  "*"   Purpose: setup beam structure records"
write (u, "(A)")

s = "s"

call beam_structure%init_sf ([s], empty_array)
call beam_structure%write (u)

write (u, "(A)")

call beam_structure%init_sf ([s, s], [1])
call beam_structure%set_sf (1, 1, var_str ("a"))
call beam_structure%write (u)

write (u, "(A)")

call beam_structure%init_sf ([s, s], [2])
call beam_structure%set_sf (1, 1, var_str ("a"))
call beam_structure%set_sf (1, 2, var_str ("b"))
call beam_structure%write (u)

write (u, "(A)")

call beam_structure%init_sf ([s, s], [2, 1])
call beam_structure%set_sf (1, 1, var_str ("a"))
call beam_structure%set_sf (1, 2, var_str ("b"))
call beam_structure%set_sf (2, 1, var_str ("c"))
call beam_structure%write (u)

write (u, "(A)")
write (u, "(A)")  "*" Test output end: beam_structures_2"

end subroutine beam_structures_2

```

Expansion

Provide a function that tells, for the dummy structure function names used here, whether they are considered a two-particle spectrum or a single-particle structure function:

```

<Beam structures: tests>+≡
function test_strfun_mode (name) result (n)
  type(string_t), intent(in) :: name
  integer :: n
  select case (char (name))
    case ("a");  n = 2
    case ("b");  n = 1
    case default; n = 0
  end select
end function test_strfun_mode

<Beam structures: execute tests>+≡
call test (beam_structures_3, "beam_structures_3", &

```

```

        "beam structure expansion", &
        u, results)
(Beam structures: tests)+=
subroutine beam_structures_3 (u)
    integer, intent(in) :: u
    type(beam_structure_t) :: beam_structure
    type(string_t) :: s

    write (u, "(A)")  "* Test output: beam_structures_3"
    write (u, "(A)")  "*   Purpose: expand beam structure records"
    write (u, "(A)")

    s = "s"

    write (u, "(A)")  "* Pair spectrum (keep as-is)"
    write (u, "(A)")

    call beam_structure%init_sf ([s, s], [1])
    call beam_structure%set_sf (1, 1, var_str ("a"))
    call beam_structure%write (u)

    write (u, "(A)")

    call beam_structure%expand (test_strfun_mode)
    call beam_structure%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Structure function pair (expand)"
    write (u, "(A)")

    call beam_structure%init_sf ([s, s], [2])
    call beam_structure%set_sf (1, 1, var_str ("b"))
    call beam_structure%set_sf (1, 2, var_str ("b"))
    call beam_structure%write (u)

    write (u, "(A)")

    call beam_structure%expand (test_strfun_mode)
    call beam_structure%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Structure function (separate and expand)"
    write (u, "(A)")

    call beam_structure%init_sf ([s, s], [1])
    call beam_structure%set_sf (1, 1, var_str ("b"))
    call beam_structure%write (u)

    write (u, "(A)")

    call beam_structure%expand (test_strfun_mode)
    call beam_structure%write (u)

    write (u, "(A)")

```



```

write (u, "(A)")  "* Combination"
write (u, "(A)")

call beam_structure%init_sf ([s, s], [1, 1])
call beam_structure%set_sf (1, 1, var_str ("a"))
call beam_structure%set_sf (2, 1, var_str ("b"))
call beam_structure%write (u)

write (u, "(A)")

call beam_structure%expand (test_strfun_mode)
call beam_structure%write (u)

write (u, "(A)")
write (u, "(A)")  "* Test output end: beam_structures_3"

end subroutine beam_structures_3

```

Public methods

Check the methods that can be called to get the beam-structure contents.

```

<Beam structures: execute tests>+≡
  call test (beam_structures_4, "beam_structures_4", &
    "beam structure contents", &
    u, results)

<Beam structures: tests>+≡
  subroutine beam_structures_4 (u)
    integer, intent(in) :: u
    type(beam_structure_t) :: beam_structure
    type(string_t) :: s
    type(string_t), dimension(2) :: prt
    integer :: i

    write (u, "(A)")  "* Test output: beam_structures_4"
    write (u, "(A)")  "* Purpose: check the API"
    write (u, "(A)")

    s = "s"

    write (u, "(A)")  "* Structure-function combination"
    write (u, "(A)")

    call beam_structure%init_sf ([s, s], [1, 2, 2])
    call beam_structure%set_sf (1, 1, var_str ("a"))
    call beam_structure%set_sf (2, 1, var_str ("b"))
    call beam_structure%set_sf (3, 2, var_str ("c"))
    call beam_structure%write (u)

    write (u, *)
    write (u, "(1x,A,I0)")  "n_beam = ", beam_structure%get_n_beam ()
    prt = beam_structure%get_prt ()
    write (u, "(1x,A,2(1x,A))")  "prt =", char (prt(1)), char (prt(2))

```

```

write (u, *)
write (u, "(1x,A,I0)") "n_record = ", beam_structure%get_n_record ()

do i = 1, 3
  write (u, "(A)")
  write (u, "(1x,A,I0,A,A)") "name(", i, ") = ", &
    char (beam_structure%get_name (i))
  write (u, "(1x,A,I0,A,2(1x,I0))") "i_entry(", i, ") = ", &
    beam_structure%get_i_entry (i)
end do

write (u, "(A)")
write (u, "(A)")  "* Test output end: beam_structures_4"

end subroutine beam_structures_4

```

Polarization

The polarization properties are independent from the structure-function setup.

(Beam structures: execute tests)+≡

```

call test (beam_structures_5, "beam_structures_5", &
  "polarization", &
  u, results)

```

(Beam structures: tests)+≡

```

subroutine beam_structures_5 (u)
  integer, intent(in) :: u
  type(beam_structure_t) :: beam_structure
  integer, dimension(0) :: empty_array
  type(string_t) :: s

  write (u, "(A)")  "* Test output: beam_structures_5"
  write (u, "(A)")  "* Purpose: setup polarization in beam structure records"
  write (u, "(A)")

  s = "s"

  call beam_structure%init_sf ([s], empty_array)
  call beam_structure%init_pol (1)
  call beam_structure%init_smatrix (1, 1)
  call beam_structure%set_sentry (1, 1, [0,0], (1._default, 0._default))
  call beam_structure%set_pol_f ([0.5_default])
  call beam_structure%write (u)

  write (u, "(A)")
  call beam_structure%final_sf ()
  call beam_structure%final_pol ()

  call beam_structure%init_sf ([s, s], [1])
  call beam_structure%set_sf (1, 1, var_str ("a"))
  call beam_structure%init_pol (2)

```

```

call beam_structure%init_smatrix (1, 2)
call beam_structure%set_sentry (1, 1, [-1,1], (0.5_default,-0.5_default))
call beam_structure%set_sentry (1, 2, [ 1,1], (1._default, 0._default))
call beam_structure%init_smatrix (2, 0)
call beam_structure%write (u)

write (u, "(A)")
write (u, "(A)")  "* Test output end: beam_structures_5"

end subroutine beam_structures_5

```

Momenta

The momenta are independent from the structure-function setup.

```

<Beam structures: execute tests>+≡
call test (beam_structures_6, "beam_structures_6", &
  "momenta", &
  u, results)

<Beam structures: tests>+≡
subroutine beam_structures_6 (u)
  integer, intent(in) :: u
  type(beam_structure_t) :: beam_structure
  integer, dimension(0) :: empty_array
  type(string_t) :: s

  write (u, "(A)")  "* Test output: beam_structures_6"
  write (u, "(A)")  "* Purpose: setup momenta in beam structure records"
  write (u, "(A)")

  s = "s"

  call beam_structure%init_sf ([s], empty_array)
  call beam_structure%set_momentum ([500._default])
  call beam_structure%write (u)

  write (u, "(A)")
  call beam_structure%final_sf ()
  call beam_structure%final_mom ()

  call beam_structure%init_sf ([s, s], [1])
  call beam_structure%set_momentum ([500._default, 700._default])
  call beam_structure%set_theta ([0._default, 0.1_default])
  call beam_structure%set_phi ([0._default, 1.51_default])
  call beam_structure%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: beam_structures_6"

end subroutine beam_structures_6

```

15.2 Beams for collisions and decays

```
(beams.f90)≡
  <File header>

  module beams

    <Use kinds>
    <Use strings>
    use io_units
    use constants
    use format_defs, only: FMT_19
    use unit_tests
    use diagnostics
    use md5
    use lorentz
    use model_data
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use interactions
    use polarizations
    use beam_structures

    <Standard module head>

    <Beams: public>

    <Beams: types>

    <Beams: interfaces>

    contains

    <Beams: procedures>

    <Beams: tests>

  end module beams
```

15.2.1 Beam data

The beam data type contains beam data for one or two beams, depending on whether we are dealing with beam collisions or particle decay. In addition, it holds the c.m. energy `sqrts`, the Lorentz transformation `L` that transforms the c.m. system into the lab system, and the pair of c.m. momenta.

```
<Beams: public>≡
  public :: beam_data_t

<Beams: types>≡
  type :: beam_data_t
    logical :: initialized = .false.
    integer :: n = 0
```

```

    type(flavor_t), dimension(:), allocatable :: flv
    real(default), dimension(:), allocatable :: mass
    type(pmatrix_t), dimension(:), allocatable :: pmatrix
    logical :: lab_is_cm_frame = .true.
    type(vector4_t), dimension(:), allocatable :: p_cm
    type(vector4_t), dimension(:), allocatable :: p
    type(lorentz_transformation_t), allocatable :: L_cm_to_lab
    real(default) :: sqrts = 0
    character(32) :: md5sum = ""
contains
    <Beams: beam data: TBP>
end type beam_data_t

```

Generic initializer. This is called by the specific initializers below. Initialize either for decay or for collision.

```

<Beams: procedures>≡
    subroutine beam_data_init (beam_data, n)
        type(beam_data_t), intent(out) :: beam_data
        integer, intent(in) :: n
        beam_data%n = n
        allocate (beam_data%flv (n))
        allocate (beam_data%mass (n))
        allocate (beam_data%pmatrix (n))
        allocate (beam_data%p_cm (n))
        allocate (beam_data%p (n))
        beam_data%initialized = .true.
    end subroutine beam_data_init

```

Finalizer: needed for the polarization components of the beams.

```

<Beams: public>+≡
    public :: beam_data_final

<Beams: procedures>+≡
    subroutine beam_data_final (beam_data)
        type(beam_data_t), intent(inout) :: beam_data
        beam_data%initialized = .false.
    end subroutine beam_data_final

```

The verbose (default) version is for debugging. The short version is for screen output in the UI.

```

<Beams: public>+≡
    public :: beam_data_write

<Beams: beam data: TBP>≡
    procedure :: write => beam_data_write

<Beams: procedures>+≡
    subroutine beam_data_write (beam_data, unit, verbose, write_md5sum)
        class(beam_data_t), intent(in) :: beam_data
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose, write_md5sum
        integer :: prt_name_len
        logical :: verb, write_md5
        integer :: u

```

```

u = given_output_unit (unit); if (u < 0) return
verb = .false.; if (present (verbose)) verb = verbose
write_md5 = verb; if (present (write_md5sum)) write_md5 = write_md5sum
if (.not. beam_data%initialized) then
    write (u, "(1x,A)") "Beam data: [undefined]"
    return
end if
prt_name_len = maxval (len (beam_data%flv%get_name ()))
select case (beam_data%n)
case (1)
    write (u, "(1x,A)") "Beam data (decay):"
    if (verb) then
        call write_prt (1)
        call beam_data%pmatrix(1)%write (u)
        write (u, *) "R.f. momentum:"
        call vector4_write (beam_data%p_cm(1), u)
        write (u, *) "Lab momentum:"
        call vector4_write (beam_data%p(1), u)
    else
        call write_prt (1)
    end if
case (2)
    write (u, "(1x,A)") "Beam data (collision):"
    if (verb) then
        call write_prt (1)
        call beam_data%pmatrix(1)%write (u)
        call write_prt (2)
        call beam_data%pmatrix(2)%write (u)
        call write_sqrts
        write (u, *) "C.m. momenta:"
        call vector4_write (beam_data%p_cm(1), u)
        call vector4_write (beam_data%p_cm(2), u)
        write (u, *) "Lab momenta:"
        call vector4_write (beam_data%p(1), u)
        call vector4_write (beam_data%p(2), u)
    else
        call write_prt (1)
        call write_prt (2)
        call write_sqrts
    end if
end select
if (allocated (beam_data%L_cm_to_lab)) then
    if (verb) then
        call lorentz_transformation_write (beam_data%L_cm_to_lab, u)
    else
        write (u, "(1x,A)") "Beam structure: lab and c.m. frame differ"
    end if
end if
if (write_md5) then
    write (u, *) "MD5 sum: ", beam_data%md5sum
end if
contains
subroutine write_sqrts
character(80) :: sqrts_str

```

```

        write (sqrts_str, "(" // FMT_19 // ")") beam_data%sqrts
        write (u, "(3x,A)") "sqrts = " // trim (adjustl (sqrts_str)) // " GeV"
    end subroutine write_sqrts
    subroutine write_prt (i)
        integer, intent(in) :: i
        character(80) :: name_str, mass_str
        write (name_str, "(A)") char (beam_data%flv(i)%get_name ())
        write (mass_str, "(ES13.7)") beam_data%mass(i)
        write (u, "(3x,A)", advance="no") &
            name_str(:prt_name_len) // " (mass = " &
            // trim (adjustl (mass_str)) // " GeV)"
        if (beam_data%pmatrix(i)%is_polarized ()) then
            write (u, "(2x,A)") "polarized"
        else
            write (u, *)
        end if
    end subroutine write_prt
end subroutine beam_data_write

```

Return initialization status:

```

(Beams: public)+≡
    public :: beam_data_are_valid

(Beams: procedures)+≡
    function beam_data_are_valid (beam_data) result (flag)
        logical :: flag
        type(beam_data_t), intent(in) :: beam_data
        flag = beam_data%initialized
    end function beam_data_are_valid

```

Check whether beam data agree with the current values of relevant parameters.

```

(Beams: public)+≡
    public :: beam_data_check_scattering

(Beams: procedures)+≡
    subroutine beam_data_check_scattering (beam_data, sqrts)
        type(beam_data_t), intent(in) :: beam_data
        real(default), intent(in), optional :: sqrts
        if (beam_data_are_valid (beam_data)) then
            if (present (sqrts)) then
                if (sqrts /= beam_data%sqrts) then
                    call msg_error ("Current setting of sqrts is inconsistent " &
                        // "with beam setup (ignored).")
                end if
            end if
        else
            call msg_bug ("Beam setup: invalid beam data")
        end if
    end subroutine beam_data_check_scattering

```

Return the number of beams (1 for decays, 2 for collisions).

```

(Beams: public)+≡
    public :: beam_data_get_n_in

```

```

<Beams: procedures>+≡
function beam_data_get_n_in (beam_data) result (n_in)
integer :: n_in
type(beam_data_t), intent(in) :: beam_data
n_in = beam_data%n
end function beam_data_get_n_in

```

Return the beam flavor

```

<Beams: public>+≡
public :: beam_data_get_flavor

<Beams: procedures>+≡
function beam_data_get_flavor (beam_data) result (flv)
type(flavor_t), dimension(:), allocatable :: flv
type(beam_data_t), intent(in) :: beam_data
allocate (flv (beam_data%n))
flv = beam_data%flv
end function beam_data_get_flavor

```

Return the beam energies

```

<Beams: public>+≡
public :: beam_data_get_energy

<Beams: procedures>+≡
function beam_data_get_energy (beam_data) result (e)
real(default), dimension(:), allocatable :: e
type(beam_data_t), intent(in) :: beam_data
allocate (e (beam_data%n))
if (beam_data%initialized) then
e = energy (beam_data%p)
else
e = 0
end if
end function beam_data_get_energy

```

Return the c.m. energy.

```

<Beams: public>+≡
public :: beam_data_get_sqrts

<Beams: procedures>+≡
function beam_data_get_sqrts (beam_data) result (sqrts)
real(default) :: sqrts
type(beam_data_t), intent(in) :: beam_data
sqrts = beam_data%sqrts
end function beam_data_get_sqrts

```

Return true if the lab and c.m. frame are specified as identical.

```

<Beams: public>+≡
public :: beam_data_cm_frame

```



```

(Beams: procedures)+≡
function beam_data_cm_frame (beam_data) result (flag)
  type(beam_data_t), intent(in) :: beam_data
  logical :: flag
  flag = beam_data%lab_is_cm_frame
end function beam_data_cm_frame

```

Return a MD5 checksum for beam data. If no checksum is present (because beams have not been initialized), compute the checksum of the sqrts value.

```

(Beams: public)+≡
public :: beam_data_get_md5sum

(Beams: procedures)+≡
function beam_data_get_md5sum (beam_data, sqrts) result (md5sum_beams)
  type(beam_data_t), intent(in) :: beam_data
  real(default), intent(in) :: sqrts
  character(32) :: md5sum_beams
  character(80) :: buffer
  if (beam_data%md5sum /= "") then
    md5sum_beams = beam_data%md5sum
  else
    write (buffer, *) sqrts
    md5sum_beams = md5sum (buffer)
  end if
end function beam_data_get_md5sum

```

15.2.2 Initializers: beam structure

Initialize the beam data object from a beam structure object, given energy and model.

```

(Beams: public)+≡
public :: beam_data_init_structure

(Beams: procedures)+≡
subroutine beam_data_init_structure &
  (beam_data, structure, sqrts, model, decay_rest_frame)
  type(beam_data_t), intent(out) :: beam_data
  type(beam_structure_t), intent(in) :: structure
  integer :: n_beam
  real(default), intent(in) :: sqrts
  class(model_data_t), intent(in), target :: model
  logical, intent(in), optional :: decay_rest_frame
  type(flavor_t), dimension(:), allocatable :: flv
  n_beam = structure%get_n_beam ()
  allocate (flv (n_beam))
  call flv%init (structure%get_prt (), model)
  if (structure%asymmetric ()) then
    if (structure%polarized ()) then
      call beam_data_init_momenta (beam_data, &
        structure%get_momenta (), flv, &
        structure%get_smatrix (), structure%get_pol_f ())
    else

```

```

        call beam_data_init_momenta (beam_data, &
            structure%get_momenta (), flv)
    end if
else
    select case (n_beam)
    case (1)
        if (structure%polarized ()) then
            call beam_data_init_decay (beam_data, flv, &
                structure%get_smatrix (), structure%get_pol_f (), &
                rest_frame = decay_rest_frame)
        else
            call beam_data_init_decay (beam_data, flv, &
                rest_frame = decay_rest_frame)
        end if
    case (2)
        if (structure%polarized ()) then
            call beam_data_init_sqrts (beam_data, sqrts, flv, &
                structure%get_smatrix (), structure%get_pol_f ())
        else
            call beam_data_init_sqrts (beam_data, sqrts, flv)
        end if
    case default
        call msg_bug ("Beam data: invalid beam structure object")
    end select
end if
end subroutine beam_data_init_structure

```

15.2.3 Initializers: collisions

This is the simplest one: just the two flavors, c.m. energy, polarization. Color is inferred from flavor. Beam momenta and c.m. momenta coincide.

```

(Beams: public)+≡
    public :: beam_data_init_sqrts

(Beams: procedures)+≡
    subroutine beam_data_init_sqrts (beam_data, sqrts, flv, smatrix, pol_f)
        type(beam_data_t), intent(out) :: beam_data
        real(default), intent(in) :: sqrts
        type(flavor_t), dimension(:), intent(in) :: flv
        type(smatrix_t), dimension(:), intent(in), optional :: smatrix
        real(default), dimension(:), intent(in), optional :: pol_f
        real(default), dimension(size(flv)) :: E, p
        call beam_data_init (beam_data, size (flv))
        beam_data%sqrts = sqrts
        beam_data%lab_is_cm_frame = .true.
        select case (beam_data%n)
        case (1)
            E = sqrts; p = 0
            beam_data%p_cm = vector4_moving (E, p, 3)
            beam_data%p = beam_data%p_cm
        case (2)
            beam_data%p_cm = colliding_momenta (sqrts, flv%get_mass ())
            beam_data%p = colliding_momenta (sqrts, flv%get_mass ())

```

```

end select
call beam_data_finish_initialization (beam_data, flv, smatrix, pol_f)
end subroutine beam_data_init_sqrts

```

This version sets beam momenta directly, assuming that they are asymmetric, i.e., lab frame and c.m. frame do not coincide. Polarization info is deferred to a common initializer.

The Lorentz transformation that we compute here is not actually used in the calculation; instead, it will be recomputed for each event in the subroutine `phs_set_incoming_momenta`. We compute it here for the nominal beam setup nevertheless, so we can print it and, in particular, include it in the MD5 sum.

<Beams: public>+≡

```
public :: beam_data_init_momenta
```

<Beams: procedures>+≡

```

subroutine beam_data_init_momenta (beam_data, p3, flv, smatrix, pol_f)
  type(beam_data_t), intent(out) :: beam_data
  type(vector3_t), dimension(:), intent(in) :: p3
  type(flavor_t), dimension(:), intent(in) :: flv
  type(smatrix_t), dimension(:), intent(in), optional :: smatrix
  real(default), dimension(:), intent(in), optional :: pol_f
  type(vector4_t) :: p0
  type(vector4_t), dimension(:), allocatable :: p, p_cm_rot
  real(default), dimension(size(p3)) :: e
  real(default), dimension(size(flv)) :: m
  type(lorentz_transformation_t) :: L_boost, L_rot
  call beam_data_init (beam_data, size (flv))
  m = flv%get_mass ()
  e = sqrt (p3 ** 2 + m ** 2)
  allocate (p (beam_data%n))
  p = vector4_moving (e, p3)
  p0 = sum (p)
  beam_data%p = p
  beam_data%lab_is_cm_frame = .false.
  beam_data%sqrts = p0 ** 1
  L_boost = boost (p0, beam_data%sqrts)
  allocate (p_cm_rot (beam_data%n))
  p_cm_rot = inverse (L_boost) * p
  allocate (beam_data%L_cm_to_lab)
  select case (beam_data%n)
  case (1)
    beam_data%L_cm_to_lab = L_boost
    beam_data%p_cm = vector4_at_rest (beam_data%sqrts)
  case (2)
    L_rot = rotation_to_2nd (3, space_part (p_cm_rot(1)))
    beam_data%L_cm_to_lab = L_boost * L_rot
    beam_data%p_cm = &
      colliding_momenta (beam_data%sqrts, flv%get_mass ())
  end select
  call beam_data_finish_initialization (beam_data, flv, smatrix, pol_f)
end subroutine beam_data_init_momenta

```

Final steps: If requested, rotate the beams in the lab frame, and set the beam-data components.

```

(Beams: procedures)+≡
subroutine beam_data_finish_initialization (beam_data, flv, smatrix, pol_f)
  type(beam_data_t), intent(inout) :: beam_data
  type(flavor_t), dimension(:), intent(in) :: flv
  type(smatrix_t), dimension(:), intent(in), optional :: smatrix
  real(default), dimension(:), intent(in), optional :: pol_f
  integer :: i
do i = 1, beam_data%n
  beam_data%flv(i) = flv(i)
  beam_data%mass(i) = flv(i)%get_mass ()
  if (present (smatrix)) then
    if (size (smatrix) /= beam_data%n) &
      call msg_fatal ("Beam data: &
        &polarization density array has wrong dimension")
    beam_data%pmatrix(i) = smatrix(i)
    if (present (pol_f)) then
      if (size (pol_f) /= size (smatrix)) &
        call msg_fatal ("Beam data: &
          &polarization fraction array has wrong dimension")
      call beam_data%pmatrix(i)%normalize (flv(i), pol_f(i))
    else
      call beam_data%pmatrix(i)%normalize (flv(i), 1._default)
    end if
  else
    call beam_data%pmatrix(i)%init (2, 0)
    call beam_data%pmatrix(i)%normalize (flv(i), 0._default)
  end if
end do
call beam_data_compute_md5sum (beam_data)
end subroutine beam_data_finish_initialization

```

The MD5 sum is stored within the beam-data record, so it can be checked for integrity in subsequent runs.

```

(Beams: procedures)+≡
subroutine beam_data_compute_md5sum (beam_data)
  type(beam_data_t), intent(inout) :: beam_data
  integer :: unit
  unit = free_unit ()
  open (unit = unit, status = "scratch", action = "readwrite")
  call beam_data_write (beam_data, unit, write_md5sum = .false., &
    verbose = .true.)
  rewind (unit)
  beam_data%md5sum = md5sum (unit)
  close (unit)
end subroutine beam_data_compute_md5sum

```

15.2.4 Initializers: decays

This is the simplest one: decay in rest frame. We need just flavor and polarization. Color is inferred from flavor. Beam momentum and c.m. momentum

coincide.

```

(Beams: public)+≡
    public :: beam_data_init_decay

(Beams: procedures)+≡
    subroutine beam_data_init_decay (beam_data, flv, smatrix, pol_f, rest_frame)
        type(beam_data_t), intent(out) :: beam_data
        type(flavor_t), dimension(1), intent(in) :: flv
        type(smatrix_t), dimension(1), intent(in), optional :: smatrix
        real(default), dimension(:), intent(in), optional :: pol_f
        logical, intent(in), optional :: rest_frame
        real(default), dimension(1) :: m
        m = flv%get_mass ()
        if (present (smatrix)) then
            call beam_data_init_sqrts (beam_data, m(1), flv, smatrix, pol_f)
        else
            call beam_data_init_sqrts (beam_data, m(1), flv, smatrix, pol_f)
        end if
        if (present (rest_frame)) beam_data%lab_is_cm_frame = rest_frame
    end subroutine beam_data_init_decay

```

15.2.5 Sanity check

After the beams have been set, the initial-particle masses may have been modified. This can be checked here.

```

(Beams: public)+≡
    public :: beam_data_masses_are_consistent

(Beams: procedures)+≡
    function beam_data_masses_are_consistent (beam_data) result (flag)
        logical :: flag
        type(beam_data_t), intent(in) :: beam_data
        flag = all (beam_data%mass == beam_data%flv%get_mass ())
    end function beam_data_masses_are_consistent

```

15.2.6 The beams type

Beam objects are interaction objects that contain the actual beam data including polarization and density matrix. For collisions, the beam object actually contains two beams.

```

(Beams: public)+≡
    public :: beam_t

(Beams: types)+≡
    type :: beam_t
        private
        type(interaction_t) :: int
    end type beam_t

```

The constructor contains code that converts beam data into the (entangled) particle-pair quantum state. First, we set the number of particles and polarization mask. (The polarization mask is handed over to all later interactions, so if helicity is diagonal or absent, this fact is used when constructing the hard-interaction events.) Then, we construct the entangled state that combines helicity, flavor and color of the two particles (where flavor and color are unique, while several helicity states are possible). Then, we transfer this state together with the associated values from the spin density matrix into the `interaction_t` object.

```

(Beams: public)+≡
    public :: beam_init

(Beams: procedures)+≡
    subroutine beam_init (beam, beam_data)
        type(beam_t), intent(out) :: beam
        type(beam_data_t), intent(in), target :: beam_data
        type(quantum_numbers_mask_t), dimension(beam_data%n) :: mask
        type(state_matrix_t), target :: state_hel, state_fc, state_tmp
        type(state_iterator_t) :: it_hel, it_tmp
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        type(polarization_t), dimension(:), allocatable :: pol
        integer :: i
        mask = quantum_numbers_mask (.false., .false., &
            .not. beam_data%pmatrix%is_polarized (), &
            mask_hd = beam_data%pmatrix%is_diagonal ())
        call beam%int%basic_init &
            (0, 0, beam_data%n, mask=mask, store_values=.true.)
        allocate (pol (beam_data%n))
        do i = 1, size (pol)
            call polarization_init_pmatrix (pol(i), beam_data%pmatrix(i))
        end do
        call combine_polarization_states (pol, state_hel)
        do i = 1, size (pol)
            call polarization_final (pol(i))
        end do
        allocate (qn (beam_data%n))
        call qn%init (beam_data%flv, color_from_flavor (beam_data%flv, 1))
        call state_fc%init ()
        call state_fc%add_state (qn)
        call merge_state_matrices (state_hel, state_fc, state_tmp)
        call it_hel%init (state_hel)
        call it_tmp%init (state_tmp)
        do while (it_hel%is_valid ())
            call beam%int%add_state (it_tmp%get_quantum_numbers (), &
                value=it_hel%get_matrix_element ())
            call it_hel%advance ()
            call it_tmp%advance ()
        end do
        call beam%int%freeze ()
        call beam%int%set_momenta (beam_data%p, outgoing = .true.)
        call state_hel%final ()
        call state_fc%final ()
        call state_tmp%final ()
    end subroutine beam_init

```

Finalizer:

```
<Beams: public>+≡
    public :: beam_final

<Beams: procedures>+≡
    subroutine beam_final (beam)
        type(beam_t), intent(inout) :: beam
        call beam%int%final ()
    end subroutine beam_final
```

I/O:

```
<Beams: public>+≡
    public :: beam_write

<Beams: procedures>+≡
    subroutine beam_write (beam, unit, verbose, show_momentum_sum, show_mass)
        type(beam_t), intent(in) :: beam
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        select case (beam%int%get_n_out ())
            case (1); write (u, *) "Decaying particle:"
            case (2); write (u, *) "Colliding beams:"
        end select
        call beam%int%basic_write &
            (unit, verbose = verbose, show_momentum_sum = &
                show_momentum_sum, show_mass = show_mass)
    end subroutine beam_write
```

Defined assignment: deep copy

```
<Beams: public>+≡
    public :: assignment(=)

<Beams: interfaces>≡
    interface assignment(=)
        module procedure beam_assign
    end interface

<Beams: procedures>+≡
    subroutine beam_assign (beam_out, beam_in)
        type(beam_t), intent(out) :: beam_out
        type(beam_t), intent(in) :: beam_in
        beam_out%int = beam_in%int
    end subroutine beam_assign
```

15.2.7 Inherited procedures

```
<Beams: public>+≡
    public :: interaction_set_source_link
```

```

<Beams: interfaces>+≡
  interface interaction_set_source_link
    module procedure interaction_set_source_link_beam
  end interface

<Beams: procedures>+≡
  subroutine interaction_set_source_link_beam (int, i, beam1, i1)
    type(interaction_t), intent(inout) :: int
    type(beam_t), intent(in), target :: beam1
    integer, intent(in) :: i, i1
    call int%set_source_link (i, beam1%i1, i1)
  end subroutine interaction_set_source_link_beam

```

15.2.8 Accessing contents

Return the interaction component – as a pointer, to avoid any copying.

```

<Beams: public>+≡
  public :: beam_get_int_ptr

<Beams: procedures>+≡
  function beam_get_int_ptr (beam) result (int)
    type(interaction_t), pointer :: int
    type(beam_t), intent(in), target :: beam
    int => beam%int
  end function beam_get_int_ptr

```

Set beam momenta directly. (Used for cascade decays.)

```

<Beams: public>+≡
  public :: beam_set_momenta

<Beams: procedures>+≡
  subroutine beam_set_momenta (beam, p)
    type(beam_t), intent(inout) :: beam
    type(vector4_t), dimension(:), intent(in) :: p
    call beam%int%set_momenta (p)
  end subroutine beam_set_momenta

```

15.2.9 Unit tests

```

<Beams: public>+≡
  public :: beam_test

<Beams: procedures>+≡
  subroutine beam_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Beams: execute tests>
  end subroutine beam_test

```


Test the basic beam setup.

```

<Beams: execute tests>≡
    call test (beam_1, "beam_1", &
        "check basic beam setup", &
        u, results)

<Beams: tests>≡
    subroutine beam_1 (u)
        integer, intent(in) :: u
        type(beam_data_t), target :: beam_data
        type(beam_t) :: beam
        real(default) :: sqrts
        type(flavor_t), dimension(2) :: flv
        type(smatrix_t), dimension(2) :: smatrix
        real(default), dimension(2) :: pol_f
        type(model_data_t), target :: model

        write (u, "(A)")  "* Test output: beam_1"
        write (u, "(A)")  "* Purpose: test basic beam setup"
        write (u, "(A)")

        write (u, "(A)")  "* Reading model file"
        write (u, "(A)")

        call reset_interaction_counter ()

        call model%init_sm_test ()

        write (u, "(A)")  "* 1: Scattering process"
        write (u, "(A)")

        sqrts = 500
        call flv%init ([1,-1], model)

        call smatrix(1)%init (2, 1)
        call smatrix(1)%set_entry (1, [1,1], (1._default, 0._default))
        pol_f(1) = 0.5_default

        !!! 2.1 version:
        ! call polarization_init_circular (pol(1), flv(1), 0.5_default)

        call smatrix(2)%init (2, 3)
        call smatrix(2)%set_entry (1, [1,1], (1._default, 0._default))
        call smatrix(2)%set_entry (2, [-1,-1], (1._default, 0._default))
        call smatrix(2)%set_entry (3, [-1,1], (1._default, 0._default))
        pol_f(2) = 1._default

        !!! 2.1 version:
        ! call polarization_init_transversal (pol(2), flv(2), 0._default, 1._default)
        call beam_data_init_sqrts (beam_data, sqrts, flv, smatrix, pol_f)
        call beam_data_write (beam_data, u)
        write (u, "(A)")
        call beam_init (beam, beam_data)
        call beam_write (beam, u)
        call beam_final (beam)

```

```

call beam_data_final (beam_data)

write (u, "(A)")
write (u, "(A)")  "* 2: Decay"
write (u, "(A)")
call flv(1)%init (23, model)
call smatrix(1)%init (2, 1)
call smatrix(1)%set_entry (1, [0,0], (1._default, 0._default))
pol_f(1) = 0.4_default

!!! 2.1 version:
! call polarization_init_longitudinal (pol(1), flv(1), 0.4_default)
call beam_data_init_decay (beam_data, flv(1:1), smatrix(1:1), pol_f(1:1))
call beam_data_write (beam_data, u)
write (u, "(A)")
call beam_init (beam, beam_data)
call beam_write (beam, u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call beam_final (beam)
call beam_data_final (beam_data)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: beam_1"

end subroutine beam_1

```

Test advanced beam setup.

(Beams: execute tests)+≡

```

call test (beam_2, "beam_2", &
  "beam initialization", &
  u, results)

```

(Beams: tests)+≡

```

subroutine beam_2 (u)
  integer, intent(in) :: u
  type(beam_data_t), target :: beam_data
  type(beam_t) :: beam
  real(default) :: sqrts
  type(flavor_t), dimension(2) :: flv
  integer, dimension(0) :: no_records
  type(beam_structure_t) :: beam_structure
  type(model_data_t), target :: model

  write (u, "(A)")  "* Test output: beam_2"
  write (u, "(A)")  "* Purpose: transfer beam polarization using &
    &beam structure"
  write (u, "(A)")

  write (u, "(A)")  "* Reading model file"

```

```

write (u, "(A)")

call reset_interaction_counter ()

call model%init_sm_test ()

write (u, "(A)")  "* 1: Scattering process"
write (u, "(A)")

sqrt_s = 500
call flv%init ([1,-1], model)
call beam_structure%init_sf (flv%get_name (), no_records)

call beam_structure%init_pol (2)

call beam_structure%init_smatrix (1, 1)
call beam_structure%set_sentry (1, 1, [1,1], (1._default, 0._default))

call beam_structure%init_smatrix (2, 3)
call beam_structure%set_sentry (2, 1, [1,1], (1._default, 0._default))
call beam_structure%set_sentry (2, 2, [-1,-1], (1._default, 0._default))
call beam_structure%set_sentry (2, 3, [-1,1], (1._default, 0._default))

call beam_structure%set_pol_f ([0.5_default, 1._default])
call beam_structure%write (u)
write (u, *)

call beam_data_init_structure (beam_data, beam_structure, sqrt_s, model)
call beam_data_write (beam_data, u)
write (u, *)

call beam_init (beam, beam_data)
call beam_write (beam, u)

call beam_final (beam)
call beam_data_final (beam_data)
call beam_structure%final_pol ()
call beam_structure%final_sf ()

write (u, "(A)")
write (u, "(A)")  "* 2: Decay"
write (u, "(A)")

call flv(1)%init (23, model)
call beam_structure%init_sf ([flv(1)%get_name ()], no_records)

call beam_structure%init_pol (1)

call beam_structure%init_smatrix (1, 1)
call beam_structure%set_sentry (1, 1, [0,0], (1._default, 0._default))
call beam_structure%set_pol_f ([0.4_default])
call beam_structure%write (u)
write (u, *)

```

```

call beam_data_init_structure (beam_data, beam_structure, sqrts, model)
call beam_data_write (beam_data, u)
write (u, "(A)")
call beam_init (beam, beam_data)
call beam_write (beam, u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call beam_final (beam)
call beam_data_final (beam_data)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: beam_2"

end subroutine beam_2

```

Test advanced beam setup, completely arbitrary momenta.

<Beams: execute tests>+≡

```

call test (beam_3, "beam_3", &
  "generic beam momenta", &
  u, results)

```

<Beams: tests>+≡

```

subroutine beam_3 (u)
  integer, intent(in) :: u
  type(beam_data_t), target :: beam_data
  type(beam_t) :: beam
  type(flavor_t), dimension(2) :: flv
  integer, dimension(0) :: no_records
  type(model_data_t), target :: model
  type(beam_structure_t) :: beam_structure
  type(vector3_t), dimension(2) :: p3
  type(vector4_t), dimension(2) :: p

  write (u, "(A)")  "* Test output: beam_3"
  write (u, "(A)")  "* Purpose: set up beams with generic momenta"
  write (u, "(A)")

  write (u, "(A)")  "* Reading model file"
  write (u, "(A)")

  call reset_interaction_counter ()

  call model%init_sm_test ()

  write (u, "(A)")  "* 1: Scattering process"
  write (u, "(A)")

  call flv%init ([2212,2212], model)

  p3(1) = vector3_moving ([5._default, 0._default, 10._default])

```

```

p3(2) = -vector3_moving ([1._default, 1._default, -10._default])

call beam_structure%init_sf (flv%get_name (), no_records)
call beam_structure%set_momentum (p3 ** 1)
call beam_structure%set_theta (polar_angle (p3))
call beam_structure%set_phi (azimuthal_angle (p3))
call beam_structure%write (u)
write (u, *)

call beam_data_init_structure (beam_data, beam_structure, 0._default, model)
call beam_data_write (beam_data, u, verbose = .true.)
write (u, *)

write (u, "(1x,A)") "Beam momenta reconstructed from LT:"
p = beam_data%L_cm_to_lab * beam_data%p_cm
call pacify (p, 1e-12_default)
call vector4_write (p(1), u)
call vector4_write (p(2), u)
write (u, "(A)")

call beam_init (beam, beam_data)
call beam_write (beam, u)

call beam_final (beam)
call beam_data_final (beam_data)
call beam_structure%final_sf ()
call beam_structure%final_mom ()

write (u, "(A)")
write (u, "(A)") "* 2: Decay"
write (u, "(A)")

call flv(1)%init (23, model)
p3(1) = vector3_moving ([10._default, 5._default, 50._default])

call beam_structure%init_sf ([flv(1)%get_name ()], no_records)
call beam_structure%set_momentum ([p3(1) ** 1])
call beam_structure%set_theta ([polar_angle (p3(1))])
call beam_structure%set_phi ([azimuthal_angle (p3(1))])
call beam_structure%write (u)
write (u, *)

call beam_data_init_structure (beam_data, beam_structure, 0._default, model)
call beam_data_write (beam_data, u, verbose = .true.)
write (u, "(A)")

write (u, "(1x,A)") "Beam momentum reconstructed from LT:"
p(1) = beam_data%L_cm_to_lab * beam_data%p_cm(1)
call pacify (p(1), 1e-12_default)
call vector4_write (p(1), u)
write (u, "(A)")

call beam_init (beam, beam_data)
call beam_write (beam, u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call beam_final (beam)
call beam_data_final (beam_data)
call beam_structure%final_sf ()
call beam_structure%final_mom ()

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: beam_3"

end subroutine beam_3

```

15.3 Tools

This module contains auxiliary procedures that can be accessed by the structure function code.

```

⟨sf_aux.f90⟩≡
  ⟨File header⟩

  module sf_aux

    ⟨Use kinds⟩
    use io_units
    use constants, only: twopi
    use unit_tests

    use lorentz

    ⟨Standard module head⟩

    ⟨SF aux: public⟩

    ⟨SF aux: parameters⟩

    ⟨SF aux: types⟩

    contains

    ⟨SF aux: procedures⟩

    ⟨SF aux: tests⟩

  end module sf_aux

```

15.3.1 Momentum splitting

Let us consider first an incoming parton with momentum k and invariant mass squared $s = k^2$ that splits into two partons with momenta q, p and invariant masses $t = q^2$ and $u = p^2$. (This is an abuse of the Mandelstam notation. t is actually the momentum transfer, assuming that p is radiated and q initiates the hard process.) The energy is split among the partons such that if $E = k^0$, we have $q^0 = xE$ and $p^0 = \bar{x}E$, where $\bar{x} \equiv 1 - x$.

We define the angle θ as the polar angle of p w.r.t. the momentum axis of the incoming momentum k . Ignoring azimuthal angle, we can write the four-momenta in the basis (E, p_T, p_L) as

$$k = \begin{pmatrix} E \\ 0 \\ p \end{pmatrix}, \quad p = \begin{pmatrix} \bar{x}E \\ \bar{x}\bar{p}\sin\theta \\ \bar{x}\bar{p}\cos\theta \end{pmatrix}, \quad q = \begin{pmatrix} xE \\ -\bar{x}\bar{p}\sin\theta \\ p - \bar{x}\bar{p}\cos\theta \end{pmatrix}, \quad (15.1)$$

where the first two mass-shell conditions are

$$p^2 = E^2 - s, \quad \bar{p}^2 = E^2 - \frac{u}{\bar{x}^2}. \quad (15.2)$$

The second condition implies that, for positive u , $\bar{x}^2 > u/E^2$, or equivalently

$$x < 1 - \sqrt{u}/E. \quad (15.3)$$

We are interested in the third mass-shell conditions: s and u are fixed, so we need t as a function of $\cos\theta$:

$$t = -2\bar{x}(E^2 - p\bar{p}\cos\theta) + s + u. \quad (15.4)$$

Solving for $\cos\theta$, we get

$$\cos\theta = \frac{2\bar{x}E^2 + t - s - u}{2\bar{x}p\bar{p}}. \quad (15.5)$$

We can compute $\sin^2\theta$ numerically as $\sin^2\theta = 1 - \cos^2\theta$, but it is important to reexpress this in view of numerical stability. To this end, we first determine the bounds for t . The cosine must be between -1 and 1 , so the bounds are

$$t_0 = -2\bar{x}(E^2 + p\bar{p}) + s + u, \quad (15.6)$$

$$t_1 = -2\bar{x}(E^2 - p\bar{p}) + s + u. \quad (15.7)$$

Computing $\sin^2\theta$ from $\cos\theta$ above, we observe that the numerator is a quadratic polynomial in t which has the zeros t_0 and t_1 , while the common denominator is given by $(2\bar{x}p\bar{p})^2$. Hence, we can write

$$\sin^2\theta = -\frac{(t - t_0)(t - t_1)}{(2\bar{x}p\bar{p})^2} \quad \text{and} \quad \cos\theta = \frac{(t - t_0) + (t - t_1)}{4\bar{x}p\bar{p}}, \quad (15.8)$$

which is free of large cancellations near $t = t_0$ or $t = t_1$.

If all is massless, i.e., $s = u = 0$, this simplifies to

$$t_0 = -4\bar{x}E^2, \quad t_1 = 0, \quad (15.9)$$

$$\sin^2\theta = -\frac{t}{\bar{x}E^2} \left(1 + \frac{t}{4\bar{x}E^2}\right), \quad \cos\theta = 1 + \frac{t}{2\bar{x}E^2}. \quad (15.10)$$

Here is the implementation. First, we define a container for the kinematical integration limits and some further data.

```

<SF aux: public>≡
  public :: splitting_data_t

<SF aux: types>≡
  type :: splitting_data_t
    private
    logical :: collinear = .false.
    real(default) :: x0 = 0
    real(default) :: x1
    real(default) :: t0
    real(default) :: t1
    real(default) :: phi0 = 0
    real(default) :: phi1 = twopi
    real(default) :: E, p, s, u, m2
    real(default) :: x, xb, pb
    real(default) :: t = 0
    real(default) :: phi = 0
    contains
    <SF aux: splitting data: TBP>
  end type splitting_data_t

```

I/O for debugging:

```

<SF aux: splitting data: TBP>≡
  procedure :: write => splitting_data_write

<SF aux: procedures>≡
  subroutine splitting_data_write (d, unit)
    class(splitting_data_t), intent(in) :: d
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A)") "Splitting data:"
    write (u, "(2x,A,L1)") "collinear = ", d%collinear
1   format (2x,A,1x,ES15.8)
    write (u, 1) "x0  =", d%x0
    write (u, 1) "x   =", d%x
    write (u, 1) "xb  =", d%xb
    write (u, 1) "x1  =", d%x1
    write (u, 1) "t0  =", d%t0
    write (u, 1) "t   =", d%t
    write (u, 1) "t1  =", d%t1
    write (u, 1) "phi0 =", d%phi0
    write (u, 1) "phi  =", d%phi
    write (u, 1) "phi1 =", d%phi1
    write (u, 1) "E    =", d%E
    write (u, 1) "p    =", d%p
    write (u, 1) "pb   =", d%pb
    write (u, 1) "s    =", d%s
    write (u, 1) "u    =", d%u
    write (u, 1) "m2   =", d%m2
  end subroutine splitting_data_write

```


15.3.2 Constant data

This is the initializer for the data. The input consists of the incoming momentum, its invariant mass squared, and the invariant mass squared of the radiated particle. m_2 is the *physical* mass squared of the outgoing particle. The t bounds depend on the chosen x value and cannot be determined yet.

```

(SF aux: splitting data: TBP)+≡
  procedure :: init => splitting_data_init

(SF aux: procedures)+≡
  subroutine splitting_data_init (d, k, mk2, mr2, mo2, collinear)
    class(splitting_data_t), intent(out) :: d
    type(vector4_t), intent(in) :: k
    real(default), intent(in) :: mk2, mr2, mo2
    logical, intent(in), optional :: collinear
    if (present (collinear)) d%collinear = collinear
    d%E = energy (k)
    d%x1 = 1 - sqrt (max (mr2, 0._default)) / d%E
    d%p = sqrt (d%E**2 - mk2)
    d%s = mk2
    d%u = mr2
    d%m2 = mo2
  end subroutine splitting_data_init

```

Retrieve the x bounds, if needed for x sampling. Generating an x value is done by the caller, since this is the part that depends on the nature of the structure function.

```

(SF aux: splitting data: TBP)+≡
  procedure :: get_x_bounds => splitting_get_x_bounds

(SF aux: procedures)+≡
  function splitting_get_x_bounds (d) result (x)
    class(splitting_data_t), intent(in) :: d
    real(default), dimension(2) :: x
    x = [ d%x0, d%x1 ]
  end function splitting_get_x_bounds

```

Now set the momentum fraction and compute t_0 and t_1 .

[The calculation of t_1 is subject to numerical problems. The exact formula is ($s = m_i^2$, $u = m_r^2$)

$$t_1 = -2\bar{x}E^2 + m_i^2 + m_r^2 + 2\bar{x}\sqrt{E^2 - m_i^2}\sqrt{E^2 - m_r^2/\bar{x}^2}. \quad (15.11)$$

The structure-function paradigm is useful only if $E \gg m_i, m_r$. In a Taylor expansion for large E , the leading term cancels. The expansion of the square roots (to subleading order) yields

$$t_1 = xm_i^2 - \frac{x}{\bar{x}}m_r^2. \quad (15.12)$$

There are two cases of interest: $m_i = m_o$ and $m_r = 0$,

$$t_1 = xm_o^2 \quad (15.13)$$

and $m_i = m_r$ and $m_o = 0$,

$$t_1 = -\frac{x^2}{\bar{x}} m_i^2. \quad (15.14)$$

In both cases, $t_1 \leq m_o^2$.]

That said, it turns out that taking the t_1 evaluation at face value leads to less problems than the approximation. We express the angles in terms of $t - t_0$ and $t - t_1$. Numerical noise in t_1 can then be tolerated.

```

<SF aux: splitting data: TBP>+≡
  procedure :: set_t_bounds => splitting_set_t_bounds

<SF aux: procedures>+≡
  elemental subroutine splitting_set_t_bounds (d, x, xb)
    class(splitting_data_t), intent(inout) :: d
    real(default), intent(in), optional :: x, xb
    real(default) :: tp, tm
    if (present (x)) d%x = x
    if (present (xb)) d%xb = xb
    if (.not. vanishes (d%xb)) then
      d%pb = sqrt (max (d%E**2 - d%u / d%xb**2, 0._default))
    else
      d%pb = 0
    end if
    tp = -2 * d%xb * d%E**2 + d%s + d%u
    tm = -2 * d%xb * d%p * d%pb
    d%t0 = tp + tm
    d%t1 = tp - tm
    d%t = d%t1
  end subroutine splitting_set_t_bounds

```

15.3.3 Sampling recoil

Compute a value for the momentum transfer t , using a random number r . We assume a logarithmic distribution for $t - m^2$, corresponding to the propagator $1/(t - m^2)$ with the physical mass m for the outgoing particle. Optionally, we can narrow the kinematical bounds.

If all three masses in the splitting vanish, the upper limit for t is zero. In that case, the t value is set to zero and the splitting will be collinear.

```

<SF aux: splitting data: TBP>+≡
  procedure :: sample_t => splitting_sample_t

<SF aux: procedures>+≡
  subroutine splitting_sample_t (d, r, t0, t1)
    class(splitting_data_t), intent(inout) :: d
    real(default), intent(in) :: r
    real(default), intent(in), optional :: t0, t1
    real(default) :: tt0, tt1, tt0m, tt1m
    if (d%collinear) then
      d%t = d%t1
    else
      tt0 = d%t0; if (present (t0)) tt0 = max (t0, tt0)
      tt1 = d%t1; if (present (t1)) tt1 = min (t1, tt1)
      tt0m = tt0 - d%m2

```

```

        tt1m = tt1 - d%m2
        if (tt0m < 0 .and. tt1m < 0 .and. abs(tt0m) > &
            epsilon(tt0m) .and. abs(tt1m) > epsilon(tt0m)) then
            d%t = d%m2 + tt0m * exp (r * log (tt1m / tt0m))
        else
            d%t = tt1
        end if
    end if
end subroutine splitting_sample_t

```

The inverse operation: Given t , we recover the value of r that would have produced this value.

```

<SF aux: splitting data: TBP>+≡
    procedure :: inverse_t => splitting_inverse_t
<SF aux: procedures>+≡
    subroutine splitting_inverse_t (d, r, t0, t1)
        class(splitting_data_t), intent(in) :: d
        real(default), intent(out) :: r
        real(default), intent(in), optional :: t0, t1
        real(default) :: tt0, tt1, tt0m, tt1m
        if (d%collinear) then
            r = 0
        else
            tt0 = d%t0; if (present (t0)) tt0 = max (t0, tt0)
            tt1 = d%t1; if (present (t1)) tt1 = min (t1, tt1)
            tt0m = tt0 - d%m2
            tt1m = tt1 - d%m2
            if (tt0m < 0 .and. tt1m < 0) then
                r = log ((d%t - d%m2) / tt0m) / log (tt1m / tt0m)
            else
                r = 0
            end if
        end if
    end subroutine splitting_inverse_t

```

This is trivial, but provided for convenience:

```

<SF aux: splitting data: TBP>+≡
    procedure :: sample_phi => splitting_sample_phi
<SF aux: procedures>+≡
    subroutine splitting_sample_phi (d, r)
        class(splitting_data_t), intent(inout) :: d
        real(default), intent(in) :: r
        if (d%collinear) then
            d%phi = 0
        else
            d%phi = (1-r) * d%phi0 + r * d%phi1
        end if
    end subroutine splitting_sample_phi

```

Inverse:

```

<SF aux: splitting data: TBP>+≡
    procedure :: inverse_phi => splitting_inverse_phi

```

```

<SF aux: procedures>+≡
subroutine splitting_inverse_phi (d, r)
  class(splitting_data_t), intent(in) :: d
  real(default), intent(out) :: r
  if (d%collinear) then
    r = 0
  else
    r = (d%phi - d%phi0) / (d%phi1 - d%phi0)
  end if
end subroutine splitting_inverse_phi

```

15.3.4 Splitting

In this function, we actually perform the splitting. The incoming momentum k is split into (if no recoil) $q_1 = (1 - x)k$ and $q_2 = xk$.

Apart from the splitting data, we need the incoming momentum k , the momentum transfer t , and the azimuthal angle ϕ . The momentum fraction x is already known here.

Alternatively, we can split without recoil. The azimuthal angle is irrelevant, and the momentum transfer is always equal to the upper limit t_1 , so the polar angle is zero. Obviously, if there are nonzero masses it is not possible to keep both energy-momentum conservation and at the same time all particles on shell. We choose for dropping the on-shell condition here.

```

<SF aux: splitting data: TBP>+≡
procedure :: split_momentum => splitting_split_momentum

<SF aux: procedures>+≡
function splitting_split_momentum (d, k) result (q)
  class(splitting_data_t), intent(in) :: d
  type(vector4_t), dimension(2) :: q
  type(vector4_t), intent(in) :: k
  real(default) :: st2, ct2, st, ct, cp, sp
  type(lorentz_transformation_t) :: rot
  real(default) :: tt0, tt1, den
  type(vector3_t) :: kk, q1, q2
  if (d%collinear) then
    if (d%s == 0 .and. d%u == 0) then
      q(1) = d%xb * k
      q(2) = d%x * k
    else
      kk = space_part (k)
      q1 = d%xb * (d%pb / d%p) * kk
      q2 = kk - q1
      q(1) = vector4_moving (d%xb * d%E, q1)
      q(2) = vector4_moving (d%x * d%E, q2)
    end if
  else
    den = 2 * d%xb * d%p * d%pb
    tt0 = max (d%t - d%t0, 0._default)
    tt1 = min (d%t - d%t1, 0._default)
    if (den**2 <= epsilon(den)) then
      st2 = 1
    end if
  end if
end function splitting_split_momentum

```

```

else
  st2 = - (tt0 * tt1) / den ** 2
end if
if (st2 > 1) then
  st2 = 1
end if
ct2 = 1 - st2
st = sqrt (max (st2, 0._default))
ct = sqrt (max (ct2, 0._default))
sp = sin (d%phi)
cp = cos (d%phi)
rot = rotation_to_2nd (3, space_part (k))
q1 = vector3_moving (d%xb * d%pb * [st * cp, st * sp, ct])
q2 = vector3_moving (d%p, 3) - q1
q(1) = rot * vector4_moving (d%xb * d%E, q1)
q(2) = rot * vector4_moving (d%x * d%E, q2)
end if
end function splitting_split_momentum

```

Momenta generated by splitting will in general be off-shell. They are on-shell only if they are collinear and massless. This subroutine puts them on shell by brute force, violating either momentum or energy conservation. The direction of three-momentum is always retained.

If the energy is below mass shell, we return a zero momentum.

```

<SF aux: parameters>≡
  integer, parameter, public :: KEEP_ENERGY = 0, KEEP_MOMENTUM = 1

<SF aux: public>+≡
  public :: on_shell

<SF aux: procedures>+≡
  elemental subroutine on_shell (p, m2, keep)
    type(vector4_t), intent(inout) :: p
    real(default), intent(in) :: m2
    integer, intent(in) :: keep
    real(default) :: E, E2, pn
    select case (keep)
    case (KEEP_ENERGY)
      E = energy (p)
      E2 = E ** 2
      if (E2 >= m2) then
        pn = sqrt (E2 - m2)
        p = vector4_moving (E, pn * direction (space_part (p)))
      else
        p = vector4_null
      end if
    case (KEEP_MOMENTUM)
      E = sqrt (space_part (p) ** 2 + m2)
      p = vector4_moving (E, space_part (p))
    end select
  end subroutine on_shell

```

15.3.5 Recovering the splitting

This is the inverse problem. We have on-shell momenta and want to deduce the splitting parameters x , t , and ϕ .

```

(SF aux: splitting data: TBP)+≡
  procedure :: recover => splitting_recover

(SF aux: procedures)+≡
  subroutine splitting_recover (d, k, q, keep)
    class(splitting_data_t), intent(inout) :: d
    type(vector4_t), intent(in) :: k, q
    integer, intent(in) :: keep
    type(lorentz_transformation_t) :: rot
    type(vector4_t) :: q0, k0
    real(default) :: p1, p2, p3, pt2, pp2, pl
    real(default) :: aux, den, norm
    real(default) :: st2, ct2, ct
    rot = inverse (rotation_to_2nd (3, space_part (k)))
    q0 = rot * q
    p1 = vector4_get_component (q0, 1)
    p2 = vector4_get_component (q0, 2)
    p3 = vector4_get_component (q0, 3)
    pt2 = p1 ** 2 + p2 ** 2
    pp2 = p1 ** 2 + p2 ** 2 + p3 ** 2
    pl = abs (p3)
    k0 = vector4_moving (d%E, d%p, 3)
    select case (keep)
    case (KEEP_ENERGY)
      d%x = energy (q0) / d%E
      d%xb = 1 - d%x
      call d%set_t_bounds ()
      if (.not. d%collinear) then
        aux = (d%xb * d%pb) ** 2 * pp2 - d%p ** 2 * pt2
        den = d%p ** 2 - (d%xb * d%pb) ** 2
        if (aux >= 0 .and. den > 0) then
          norm = (d%p * pl + sqrt (aux)) / den
        else
          norm = 1
        end if
      end if
    case (KEEP_MOMENTUM)
      d%xb = sqrt (space_part (k0 - q0) ** 2 + d%u) / d%E
      d%x = 1 - d%xb
      call d%set_t_bounds ()
      norm = 1
    end select
    if (d%collinear) then
      d%t = d%t1
      d%phi = 0
    else
      if ((d%xb * d%pb * norm)**2 < epsilon(d%xb)) then
        st2 = 1
      else
        st2 = pt2 / (d%xb * d%pb * norm) ** 2
      end if
    end if
  end subroutine

```

```

      if (st2 > 1) then
        st2 = 1
      end if
      ct2 = 1 - st2
      ct = sqrt (max (ct2, 0._default))
      if (ct /= -1) then
        d%t = d%t1 - 2 * d%xb * d%p * d%pb * st2 / (1 + ct)
      else
        d%t = d%t0
      end if
      if (p1 /= 0 .or. p2 /= 0) then
        d%phi = atan2 (-p2, -p1)
      else
        d%phi = 0
      end if
    end if
  end subroutine splitting_recover

```

15.3.6 Extract data

```

<SF aux: splitting data: TBP>+≡
  procedure :: get_x => splitting_get_x

<SF aux: procedures>+≡
  function splitting_get_x (sd) result (x)
    class(splitting_data_t), intent(in) :: sd
    real(default) :: x
    x = sd%x
  end function splitting_get_x

```

15.3.7 Unit tests

```

<SF aux: public>+≡
  public :: sf_aux_test

<SF aux: tests>≡
  subroutine sf_aux_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <SF aux: execute tests>
  end subroutine sf_aux_test

```

Momentum splitting: massless radiation

Compute momentum splitting for generic kinematics. It turns out that for $x = 0.5$, where $t - m^2$ is the geometric mean between its upper and lower bounds (this can be directly seen from the logarithmic distribution in the function `sample_t` for $r \equiv x = 1 - x = 0.5$), we arrive at an exact number $t = -0.15$ for the given input values.

```

<SF aux: execute tests>≡

```

```

call test (sf_aux_1, "sf_aux_1", &
          "massless radiation", &
          u, results)
<SF aux: tests>+≡
subroutine sf_aux_1 (u)
  integer, intent(in) :: u
  type(splitting_data_t) :: sd
  type(vector4_t) :: k
  type(vector4_t), dimension(2) :: q, q0
  real(default) :: E, mk, mp, mq
  real(default) :: x, r1, r2, r1o, r2o
  real(default) :: k2, q0_2, q1_2, q2_2

  write (u, "(A)")  "** Test output: sf_aux_1"
  write (u, "(A)")  "** Purpose: compute momentum splitting"
  write (u, "(A)")  "          (massless radiated particle)"
  write (u, "(A)")

  E = 1
  mk = 0.3_default
  mp = 0
  mq = mk

  k = vector4_moving (E, sqrt (E**2 - mk**2), 3)
  k2 = k ** 2; call pacify (k2, 1e-10_default)

  x = 0.6_default
  r1 = 0.5_default
  r2 = 0.125_default

  write (u, "(A)")  "** (1) Non-collinear setup"
  write (u, "(A)")

  call sd%init (k, mk**2, mp**2, mq**2)
  call sd%set_t_bounds (x, 1 - x)
  call sd%sample_t (r1)
  call sd%sample_phi (r2)

  call sd%write (u)

  q = sd%split_momentum (k)
  q1_2 = q(1) ** 2; call pacify (q1_2, 1e-10_default)
  q2_2 = q(2) ** 2; call pacify (q2_2, 1e-10_default)

  write (u, "(A)")
  write (u, "(A)")  "Incoming momentum k ="
  call vector4_write (k, u)
  write (u, "(A)")
  write (u, "(A)")  "Outgoing momentum sum p + q ="
  call vector4_write (sum (q), u)
  write (u, "(A)")
  write (u, "(A)")  "Radiated momentum p ="
  call vector4_write (q(1), u)
  write (u, "(A)")

```



```

write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: s"
write (u, "(2(1x,F11.8))") sd%s, k2

write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") sd%t, q2_2

write (u, "(A)") "Compare: u"
write (u, "(2(1x,F11.8))") sd%u, q1_2

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") sd%x, energy (q(2)) / energy (k)

write (u, "(A)") "Compare: 1-x"
write (u, "(2(1x,F11.8))") sd%xb, energy (q(1)) / energy (k)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep energy)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_ENERGY)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q0_2 = q0(2) ** 2; call pacify (q0_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q0_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%recover (k, q0(2), KEEP_ENERGY)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

```

```

call sd%inverse_t (r1o)

write (u, "(A)") "Compare: r1"
write (u, "(2(1x,F11.8))") r1, r1o

call sd%inverse_phi (r2o)

write (u, "(A)") "Compare: r2"
write (u, "(2(1x,F11.8))") r2, r2o

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep momentum)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_MOMENTUM)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q0_2 = q0(2) ** 2; call pacify (q0_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q0_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%recover (k, q0(2), KEEP_MOMENTUM)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

call sd%inverse_t (r1o)

write (u, "(A)") "Compare: r1"

```

```

write (u, "(2(1x,F11.8))") r1, r1o

call sd%inverse_phi (r2o)

write (u, "(A)") "Compare: r2"
write (u, "(2(1x,F11.8))") r2, r2o

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* (2) Collinear setup"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2, collinear = .true.)
call sd%set_t_bounds (x, 1 - x)

call sd%write (u)

q = sd%split_momentum (k)
q1_2 = q(1) ** 2; call pacify (q1_2, 1e-10_default)
q2_2 = q(2) ** 2; call pacify (q2_2, 1e-10_default)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: s"
write (u, "(2(1x,F11.8))") sd%s, k2

write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") sd%t, q2_2

write (u, "(A)") "Compare: u"
write (u, "(2(1x,F11.8))") sd%u, q1_2

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") sd%x, energy (q(2)) / energy (k)

write (u, "(A)") "Compare: 1-x"
write (u, "(2(1x,F11.8))") sd%xb, energy (q(1)) / energy (k)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep energy)"

```

```

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_ENERGY)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q0_2 = q0(2) ** 2; call pacify (q0_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q0_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%recover (k, q0(2), KEEP_ENERGY)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep momentum)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_MOMENTUM)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="

```

```

call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q0_2 = q0(2) ** 2; call pacify (q0_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q0_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%recover (k, q0(2), KEEP_MOMENTUM)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_aux_1"

end subroutine sf_aux_1

```

Momentum splitting: massless parton

Compute momentum splitting for generic kinematics. It turns out that for $x = 0.5$, where $t - m^2$ is the geometric mean between its upper and lower bounds, we arrive at an exact number $t = -0.36$ for the given input values.

```

<SF aux: execute tests>+≡
  call test (sf_aux_2, "sf_aux_2", &
    "massless parton", &
    u, results)

<SF aux: tests>+≡
  subroutine sf_aux_2 (u)
    integer, intent(in) :: u
    type(splitting_data_t) :: sd
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q, q0
    real(default) :: E, mk, mp, mq
    real(default) :: x, r1, r2, r1o, r2o
    real(default) :: k2, q02_2, q1_2, q2_2

    write (u, "(A)") "* Test output: sf_aux_2"
    write (u, "(A)") "* Purpose: compute momentum splitting"
    write (u, "(A)") " (massless outgoing particle)"
    write (u, "(A)")

    E = 1

```

```

mk = 0.3_default
mp = mk
mq = 0

k = vector4_moving (E, sqrt (E**2 - mk**2), 3)
k2 = k ** 2; call pacify (k2, 1e-10_default)

x = 0.6_default
r1 = 0.5_default
r2 = 0.125_default

write (u, "(A)")  "* (1) Non-collinear setup"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%sample_t (r1)
call sd%sample_phi (r2)

call sd%write (u)

q = sd%split_momentum (k)
q1_2 = q(1) ** 2; call pacify (q1_2, 1e-10_default)
q2_2 = q(2) ** 2; call pacify (q2_2, 1e-10_default)

write (u, "(A)")
write (u, "(A)")  "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)")  "Outgoing momentum sum p + q ="
call vector4_write (sum (q), u)
write (u, "(A)")
write (u, "(A)")  "Radiated momentum p ="
call vector4_write (q(1), u)
write (u, "(A)")
write (u, "(A)")  "Outgoing momentum q ="
call vector4_write (q(2), u)
write (u, "(A)")

write (u, "(A)")  "Compare: s"
write (u, "(2(1x,F11.8))")  sd%s, k2

write (u, "(A)")  "Compare: t"
write (u, "(2(1x,F11.8))")  sd%t, q2_2

write (u, "(A)")  "Compare: u"
write (u, "(2(1x,F11.8))")  sd%u, q1_2

write (u, "(A)")  "Compare: x"
write (u, "(2(1x,F11.8))")  sd%x, energy (q(2)) / energy (k)

write (u, "(A)")  "Compare: 1-x"
write (u, "(2(1x,F11.8))")  sd%xb, energy (q(1)) / energy (k)

```

```

write (u, "(A)")
write (u, "(A)")  "* Project on-shell (keep energy)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_ENERGY)

write (u, "(A)")
write (u, "(A)")  "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)")  "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)")  "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)")  "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)")  "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))")  sd%m2, q02_2
write (u, "(A)")

write (u, "(A)")  "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_ENERGY)

write (u, "(A)")  "Compare: x"
write (u, "(2(1x,F11.8))")  x, sd%x
write (u, "(A)")  "Compare: t"
write (u, "(2(1x,F11.8))")  q2_2, sd%t

call sd%inverse_t (r1o)

write (u, "(A)")  "Compare: r1"
write (u, "(2(1x,F11.8))")  r1, r1o

call sd%inverse_phi (r2o)

write (u, "(A)")  "Compare: r2"
write (u, "(2(1x,F11.8))")  r2, r2o

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)")  "* Project on-shell (keep momentum)"

```

```

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_MOMENTUM)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_MOMENTUM)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

call sd%inverse_t (r1o)

write (u, "(A)") "Compare: r1"
write (u, "(2(1x,F11.8))") r1, r1o

call sd%inverse_phi (r2o)

write (u, "(A)") "Compare: r2"
write (u, "(2(1x,F11.8))") r2, r2o

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* (2) Collinear setup"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2, collinear = .true.)
call sd%set_t_bounds (x, 1 - x)

```



```

call sd%write (u)

q = sd%split_momentum (k)
q1_2 = q(1) ** 2; call pacify (q1_2, 1e-10_default)
q2_2 = q(2) ** 2; call pacify (q2_2, 1e-10_default)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: s"
write (u, "(2(1x,F11.8))") sd%s, k2

write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") sd%t, q2_2

write (u, "(A)") "Compare: u"
write (u, "(2(1x,F11.8))") sd%u, q1_2

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") sd%x, energy (q(2)) / energy (k)

write (u, "(A)") "Compare: 1-x"
write (u, "(2(1x,F11.8))") sd%xb, energy (q(1)) / energy (k)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep energy)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_ENERGY)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

```

```

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_ENERGY)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep momentum)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_MOMENTUM)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_MOMENTUM)

write (u, "(A)") "Compare: x"

```

```

write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_aux_2"

end subroutine sf_aux_2

```

Momentum splitting: all massless

Compute momentum splitting for massless kinematics. In the non-collinear case, we need a lower cutoff for $|t|$, otherwise a logarithmic distribution is not possible.

```

<SF aux: execute tests>+≡
call test (sf_aux_3, "sf_aux_3", &
  "massless parton", &
  u, results)

<SF aux: tests>+≡
subroutine sf_aux_3 (u)
  integer, intent(in) :: u
  type(splitting_data_t) :: sd
  type(vector4_t) :: k
  type(vector4_t), dimension(2) :: q, q0
  real(default) :: E, mk, mp, mq, qmin, qmax
  real(default) :: x, r1, r2, r1o, r2o
  real(default) :: k2, q02_2, q1_2, q2_2

  write (u, "(A)") "* Test output: sf_aux_3"
  write (u, "(A)") "* Purpose: compute momentum splitting"
  write (u, "(A)") " (all massless, q cuts)"
  write (u, "(A)")

  E = 1
  mk = 0
  mp = 0
  mq = 0
  qmin = 1e-2_default
  qmax = 1e0_default

  k = vector4_moving (E, sqrt (E**2 - mk**2), 3)
  k2 = k ** 2; call pacify (k2, 1e-10_default)

  x = 0.6_default
  r1 = 0.5_default
  r2 = 0.125_default

  write (u, "(A)") "* (1) Non-collinear setup"
  write (u, "(A)")

```

```

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%sample_t (r1, t1 = - qmin ** 2, t0 = - qmax **2)
call sd%sample_phi (r2)

call sd%write (u)

q = sd%split_momentum (k)
q1_2 = q(1) ** 2; call pacify (q1_2, 1e-10_default)
q2_2 = q(2) ** 2; call pacify (q2_2, 1e-10_default)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: s"
write (u, "(2(1x,F11.8))") sd%s, k2

write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") sd%t, q2_2

write (u, "(A)") "Compare: u"
write (u, "(2(1x,F11.8))") sd%u, q1_2

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") sd%x, energy (q(2)) / energy (k)

write (u, "(A)") "Compare: 1-x"
write (u, "(2(1x,F11.8))") sd%xb, energy (q(1)) / energy (k)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep energy)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_ENERGY)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")

```

```

write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_ENERGY)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

call sd%inverse_t (r1o, t1 = - qmin ** 2, t0 = - qmax **2)

write (u, "(A)") "Compare: r1"
write (u, "(2(1x,F11.8))") r1, r1o

call sd%inverse_phi (r2o)

write (u, "(A)") "Compare: r2"
write (u, "(2(1x,F11.8))") r2, r2o

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep momentum)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_MOMENTUM)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")

```

```

write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_MOMENTUM)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

call sd%inverse_t (r1o, t1 = - qmin ** 2, t0 = - qmax **2)

write (u, "(A)") "Compare: r1"
write (u, "(2(1x,F11.8))") r1, r1o

call sd%inverse_phi (r2o)

write (u, "(A)") "Compare: r2"
write (u, "(2(1x,F11.8))") r2, r2o

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* (2) Collinear setup"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2, collinear = .true.)
call sd%set_t_bounds (x, 1 - x)

call sd%write (u)

q = sd%split_momentum (k)
q1_2 = q(1) ** 2; call pacify (q1_2, 1e-10_default)
q2_2 = q(2) ** 2; call pacify (q2_2, 1e-10_default)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q), u)
write (u, "(A)")

```

```

write (u, "(A)") "Radiated momentum p ="
call vector4_write (q(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: s"
write (u, "(2(1x,F11.8))") sd%s, k2

write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") sd%t, q2_2

write (u, "(A)") "Compare: u"
write (u, "(2(1x,F11.8))") sd%u, q1_2

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") sd%x, energy (q(2)) / energy (k)

write (u, "(A)") "Compare: 1-x"
write (u, "(2(1x,F11.8))") sd%xb, energy (q(1)) / energy (k)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep energy)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_ENERGY)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_ENERGY)

```

```

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Project on-shell (keep momentum)"

q0 = q
call on_shell (q0, [mp**2, mq**2], KEEP_MOMENTUM)

write (u, "(A)")
write (u, "(A)") "Incoming momentum k ="
call vector4_write (k, u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum sum p + q ="
call vector4_write (sum (q0), u)
write (u, "(A)")
write (u, "(A)") "Radiated momentum p ="
call vector4_write (q0(1), u)
write (u, "(A)")
write (u, "(A)") "Outgoing momentum q ="
call vector4_write (q0(2), u)
write (u, "(A)")

write (u, "(A)") "Compare: mo^2"
q02_2 = q0(2) ** 2; call pacify (q02_2, 1e-10_default)
write (u, "(2(1x,F11.8))") sd%m2, q02_2
write (u, "(A)")

write (u, "(A)") "* Recover parameters from outgoing momentum"
write (u, "(A)")

call sd%init (k, mk**2, mp**2, mq**2)
call sd%set_t_bounds (x, 1 - x)
call sd%recover (k, q0(2), KEEP_MOMENTUM)

write (u, "(A)") "Compare: x"
write (u, "(2(1x,F11.8))") x, sd%x
write (u, "(A)") "Compare: t"
write (u, "(2(1x,F11.8))") q2_2, sd%t

write (u, "(A)")
call sd%write (u)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_aux_3"

end subroutine sf_aux_3

```


15.4 Mappings for structure functions

In this module, we provide a wrapper for useful mappings of the unit (hyper-)square that we can apply to a set of structure functions.

In some cases it is useful, or even mandatory, to map the MC input parameters nontrivially onto a set of structure functions for the two beams. In all cases considered here, instead of x_1, x_2, \dots as parameters for the beams, we generate one parameter that is equal, or related to, the product $x_1 x_2 \dots$ (so it directly corresponds to \sqrt{s}). The other parameters describe the distribution of energy (loss) between beams and radiations.

```
<sf_mappings.f90>≡  
  <File header>  
  
  module sf_mappings  
  
    <Use kinds>  
    use kinds, only: double  
    use io_units  
    use constants, only: pi, zero, one  
    use format_defs, only: FMT_12, FMT_13, FMT_14, FMT_15, FMT_16  
    use unit_tests  
    use diagnostics  
  
    <Standard module head>  
  
    <SF mappings: public>  
  
    <SF mappings: parameters>  
  
    <SF mappings: types>  
  
    <SF mappings: interfaces>  
  
    contains  
  
    <SF mappings: procedures>  
  
    <SF mappings: tests>  
  
  end module sf_mappings
```

15.4.1 Base type

First, we define an abstract base type for the mapping. In all cases we need to store the indices of the parameters on which the mapping applies. Additional parameters can be stored in the extensions of this type.

```
<SF mappings: public>≡  
  public :: sf_mapping_t  
  
<SF mappings: types>≡  
  type, abstract :: sf_mapping_t  
    integer, dimension(:), allocatable :: i  
  contains
```

```

    <SF mappings: sf mapping: TBP>
end type sf_mapping_t

```

The output routine is deferred:

```

<SF mappings: sf mapping: TBP>≡
    procedure (sf_mapping_write), deferred :: write

<SF mappings: interfaces>≡
    abstract interface
        subroutine sf_mapping_write (object, unit)
            import
            class(sf_mapping_t), intent(in) :: object
            integer, intent(in), optional :: unit
        end subroutine sf_mapping_write
    end interface

```

Initializer for the base type. The array of parameter indices is allocated but initialized to zero.

```

<SF mappings: sf mapping: TBP>+≡
    procedure :: base_init => sf_mapping_base_init

<SF mappings: procedures>≡
    subroutine sf_mapping_base_init (mapping, n_par)
        class(sf_mapping_t), intent(out) :: mapping
        integer, intent(in) :: n_par
        allocate (mapping%i (n_par))
        mapping%i = 0
    end subroutine sf_mapping_base_init

```

Set an index value.

```

<SF mappings: sf mapping: TBP>+≡
    procedure :: set_index => sf_mapping_set_index

<SF mappings: procedures>+≡
    subroutine sf_mapping_set_index (mapping, j, i)
        class(sf_mapping_t), intent(inout) :: mapping
        integer, intent(in) :: j, i
        mapping%i(j) = i
    end subroutine sf_mapping_set_index

```

Return the dimensionality, i.e., the number of parameters.

```

<SF mappings: sf mapping: TBP>+≡
    procedure :: get_n_dim => sf_mapping_get_n_dim

<SF mappings: procedures>+≡
    function sf_mapping_get_n_dim (mapping) result (n)
        class(sf_mapping_t), intent(in) :: mapping
        integer :: n
        n = size (mapping%i)
    end function sf_mapping_get_n_dim

```

Computation: the values **p** are the input parameters, the values **r** are the output parameters. The values **rb** are defined as $\bar{r} = 1 - r$, but provided explicitly. They allow us to avoid numerical problems near $r = 1$.

The extra parameter **x_free** indicates that the total energy has already been renormalized by this factor. We have to take such a factor into account in a resonance or on-shell mapping.

The Jacobian is **f**. We modify only the two parameters indicated by the indices **i**.

```

<SF mappings: sf mapping: TBP>+≡
  procedure (sf_mapping_compute), deferred :: compute

<SF mappings: interfaces>+≡
  abstract interface
    subroutine sf_mapping_compute (mapping, r, rb, f, p, pb, x_free)
      import
      class(sf_mapping_t), intent(inout) :: mapping
      real(default), dimension(:), intent(out) :: r, rb
      real(default), intent(out) :: f
      real(default), dimension(:), intent(in) :: p, pb
      real(default), intent(inout), optional :: x_free
    end subroutine sf_mapping_compute
  end interface

```

The inverse mapping. Use **r** and/or **rb** to reconstruct **p** and also compute **f**.

```

<SF mappings: sf mapping: TBP>+≡
  procedure (sf_mapping_inverse), deferred :: inverse

<SF mappings: interfaces>+≡
  abstract interface
    subroutine sf_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
      import
      class(sf_mapping_t), intent(inout) :: mapping
      real(default), dimension(:), intent(in) :: r, rb
      real(default), intent(out) :: f
      real(default), dimension(:), intent(out) :: p, pb
      real(default), intent(inout), optional :: x_free
    end subroutine sf_mapping_inverse
  end interface

```

15.4.2 Methods for self-tests

This is a shorthand for: inject parameters, compute the mapping, display results, compute the inverse, display again. We provide an output format for the parameters and, optionally, a different output format for the Jacobians.

```

<SF mappings: sf mapping: TBP>+≡
  procedure :: check => sf_mapping_check

<SF mappings: procedures>+≡
  subroutine sf_mapping_check (mapping, u, p_in, pb_in, fmt_p, fmt_f)
    class(sf_mapping_t), intent(inout) :: mapping
    integer, intent(in) :: u
    real(default), dimension(:), intent(in) :: p_in, pb_in

```

```

character(*), intent(in) :: fmt_p
character(*), intent(in), optional :: fmt_f
real(default), dimension(size(p_in)) :: p, pb, r, rb
real(default) :: f, tolerance
tolerance = 1.5E-17
p = p_in
pb= pb_in
call mapping%compute (r, rb, f, p, pb)
call pacify (p, tolerance)
call pacify (pb, tolerance)
call pacify (r, tolerance)
call pacify (rb, tolerance)
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "p =", p
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "pb=", pb
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "r =", r
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "rb=", rb
if (present (fmt_f)) then
  write (u, "(3x,A,9(1x," // fmt_f // "))" ) "f =", f
else
  write (u, "(3x,A,9(1x," // fmt_p // "))" ) "f =", f
end if
write (u, *)
call mapping%inverse (r, rb, f, p, pb)
call pacify (p, tolerance)
call pacify (pb, tolerance)
call pacify (r, tolerance)
call pacify (rb, tolerance)
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "p =", p
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "pb=", pb
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "r =", r
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "rb=", rb
if (present (fmt_f)) then
  write (u, "(3x,A,9(1x," // fmt_f // "))" ) "f =", f
else
  write (u, "(3x,A,9(1x," // fmt_p // "))" ) "f =", f
end if
write (u, *)
write (u, "(3x,A,9(1x," // fmt_p // "))" ) "*r=", product (r)
end subroutine sf_mapping_check

```

This is a consistency check for the self-tests: the integral over the unit square should be unity. We estimate this by a simple binning and adding up the values; this should be sufficient for a self-test.

The argument is the requested number of sampling points. We take the square root for binning in both dimensions, so the precise number might be different.

```

<SF mappings: sf mapping: TBP>+≡
  procedure :: integral => sf_mapping_integral

<SF mappings: procedures>+≡
function sf_mapping_integral (mapping, n_calls) result (integral)
  class(sf_mapping_t), intent(inout) :: mapping
  integer, intent(in) :: n_calls
  real(default) :: integral

```

```

integer :: n_dim, n_bin, k
real(default), dimension(:), allocatable :: p, pb, r, rb
integer, dimension(:), allocatable :: ii
real(default) :: dx, f, s

n_dim = mapping%get_n_dim ()
allocate (p (n_dim))
allocate (pb(n_dim))
allocate (r (n_dim))
allocate (rb(n_dim))
allocate (ii(n_dim))
n_bin = nint (real (n_calls, default) ** (1._default / n_dim))
dx = 1._default / n_bin
s = 0
ii = 1

SAMPLE: do
  do k = 1, n_dim
    p(k) = ii(k) * dx - dx/2
    pb(k) = (n_bin - ii(k)) * dx + dx/2
  end do
  call mapping%compute (r, rb, f, p, pb)
  s = s + f
INCR: do k = 1, n_dim
  ii(k) = ii(k) + 1
  if (ii(k) <= n_bin) then
    exit INCR
  else if (k < n_dim) then
    ii(k) = 1
  else
    exit SAMPLE
  end if
end do INCR
end do SAMPLE

integral = s / real (n_bin, default) ** n_dim

end function sf_mapping_integral

```

15.4.3 Implementation: standard mapping

This maps the unit square (r_1, r_2) such that p_1 is the product $r_1 r_2$, while p_2 is related to the ratio.

```

<SF mappings: public>+≡
  public :: sf_s_mapping_t

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_s_mapping_t
    logical :: power_set = .false.
    real(default) :: power = 1
  contains
    <SF mappings: sf standard mapping: TBP>
  end type sf_s_mapping_t

```

Output.

```

<SF mappings: sf standard mapping: TBP>≡
  procedure :: write => sf_s_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_s_mapping_write (object, unit)
    class(sf_s_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "map"
    if (any (object%i /= 0)) then
      write (u, "('(',IO,',',IO,')')", advance="no") object%i
    end if
    write (u, "(A,F7.5,A)" ": standard (", object%power, ")")
  end subroutine sf_s_mapping_write

```

Initialize: index pair and power parameter.

```

<SF mappings: sf standard mapping: TBP>+≡
  procedure :: init => sf_s_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_s_mapping_init (mapping, power)
    class(sf_s_mapping_t), intent(out) :: mapping
    real(default), intent(in), optional :: power
    call mapping%base_init (2)
    if (present (power)) then
      mapping%power_set = .true.
      mapping%power = power
    end if
  end subroutine sf_s_mapping_init

```

Apply mapping.

```

<SF mappings: sf standard mapping: TBP>+≡
  procedure :: compute => sf_s_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_s_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_s_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: r2
    integer :: j
    if (mapping%power_set) then
      call map_unit_square (r2, f, p(mapping%i), mapping%power)
    else
      call map_unit_square (r2, f, p(mapping%i))
    end if
    r = p
    rb= pb
    do j = 1, 2

```

```

        r(mapping%i(j)) = r2(j)
        rb(mapping%i(j)) = 1 - r2(j)
    end do
end subroutine sf_s_mapping_compute

```

Apply inverse.

```

<SF mappings: sf standard mapping: TBP>+≡
    procedure :: inverse => sf_s_mapping_inverse

<SF mappings: procedures>+≡
subroutine sf_s_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_s_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: p2
    integer :: j
    if (mapping%power_set) then
        call map_unit_square_inverse (r(mapping%i), f, p2, mapping%power)
    else
        call map_unit_square_inverse (r(mapping%i), f, p2)
    end if
    p = r
    pb = rb
    do j = 1, 2
        p(mapping%i(j)) = p2(j)
        pb(mapping%i(j)) = 1 - p2(j)
    end do
end subroutine sf_s_mapping_inverse

```

15.4.4 Implementation: resonance pair mapping

This maps the unit square (r_1, r_2) such that p_1 is the product $r_1 r_2$, while p_2 is related to the ratio, then it maps p_1 to itself according to a Breit-Wigner shape, i.e., a flat prior distribution in p_1 results in a Breit-Wigner distribution. Mass and width of the BW are rescaled by the energy, thus dimensionless fractions.

```

<SF mappings: public>+≡
    public :: sf_res_mapping_t

<SF mappings: types>+≡
    type, extends (sf_mapping_t) :: sf_res_mapping_t
        real(default) :: m = 0
        real(default) :: w = 0
    contains
        <SF mappings: sf resonance mapping: TBP>
    end type sf_res_mapping_t

```

Output.

```

<SF mappings: sf resonance mapping: TBP>≡
    procedure :: write => sf_res_mapping_write

```

```

<SF mappings: procedures>+≡
subroutine sf_res_mapping_write (object, unit)
  class(sf_res_mapping_t), intent(in) :: object
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)", advance="no") "map"
  if (any (object%i /= 0)) then
    write (u, "('(',I0,',',',I0,')')", advance="no") object%i
  end if
  write (u, "(A,F7.5,', ',F7.5,A)" ": resonance (" , object%m, object%w, ")")
end subroutine sf_res_mapping_write

```

Initialize: index pair and dimensionless mass and width parameters.

```

<SF mappings: sf resonance mapping: TBP>+≡
procedure :: init => sf_res_mapping_init

<SF mappings: procedures>+≡
subroutine sf_res_mapping_init (mapping, m, w)
  class(sf_res_mapping_t), intent(out) :: mapping
  real(default), intent(in) :: m, w
  call mapping%base_init (2)
  mapping%m = m
  mapping%w = w
end subroutine sf_res_mapping_init

```

Apply mapping.

```

<SF mappings: sf resonance mapping: TBP>+≡
procedure :: compute => sf_res_mapping_compute

<SF mappings: procedures>+≡
subroutine sf_res_mapping_compute (mapping, r, rb, f, p, pb, x_free)
  class(sf_res_mapping_t), intent(inout) :: mapping
  real(default), dimension(:), intent(out) :: r, rb
  real(default), intent(out) :: f
  real(default), dimension(:), intent(in) :: p, pb
  real(default), intent(inout), optional :: x_free
  real(default), dimension(2) :: r2, p2
  real(default) :: fbw, f2, p1m
  integer :: j
  p2 = p(mapping%i)
  call map_breit_wigner &
    (p1m, fbw, p2(1), mapping%m, mapping%w, x_free)
  call map_unit_square (r2, f2, [p1m, p2(2)])
  f = fbw * f2
  r = p
  rb = pb
  do j = 1, 2
    r (mapping%i(j)) = r2(j)
    rb(mapping%i(j)) = 1 - r2(j)
  end do
end subroutine sf_res_mapping_compute

```


Apply inverse.

```

<SF mappings: sf resonance mapping: TBP>+≡
  procedure :: inverse => sf_res_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_res_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_res_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: p2
    real(default) :: fbw, f2, p1m
    call map_unit_square_inverse (r(mapping%i), f2, p2)
    call map_breit_wigner_inverse &
      (p2(1), fbw, p1m, mapping%m, mapping%w, x_free)
    p = r
    pb = rb
    p (mapping%i(1)) = p1m
    pb(mapping%i(1)) = 1 - p1m
    p (mapping%i(2)) = p2(2)
    pb(mapping%i(2)) = 1 - p2(2)
    f = fbw * f2
  end subroutine sf_res_mapping_inverse

```

15.4.5 Implementation: on-shell mapping

This is a degenerate version of the unit-square mapping where the product $r_1 r_2$ is constant. This product is given by the rescaled squared mass. We introduce an artificial first parameter p_1 to keep the counting, but nothing depends on it. The second parameter is the same p_2 as for the standard unit-square mapping for $\alpha = 1$, it parameterizes the ratio of r_1 and r_2 .

```

<SF mappings: public>+≡
  public :: sf_os_mapping_t

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_os_mapping_t
    real(default) :: m = 0
    real(default) :: lm2 = 0
  contains
    <SF mappings: sf on-shell mapping: TBP>
  end type sf_os_mapping_t

```

Output.

```

<SF mappings: sf on-shell mapping: TBP>≡
  procedure :: write => sf_os_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_os_mapping_write (object, unit)
    class(sf_os_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
  end subroutine sf_os_mapping_write

```

```

write (u, "(1x,A)", advance="no") "map"
if (any (object%i /= 0)) then
  write (u, "('(',I0,',',I0,')')", advance="no") object%i
end if
write (u, "(A,F7.5,A)" ": on-shell (" , object%m, ")")
end subroutine sf_os_mapping_write

```

Initialize: index pair and dimensionless mass parameter.

```

<SF mappings: sf on-shell mapping: TBP>+≡
  procedure :: init => sf_os_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_os_mapping_init (mapping, m)
    class(sf_os_mapping_t), intent(out) :: mapping
    real(default), intent(in) :: m
    call mapping%base_init (2)
    mapping%m = m
    mapping%lm2 = abs (2 * log (mapping%m))
  end subroutine sf_os_mapping_init

```

Apply mapping. The `x_free` parameter rescales the total energy, which must be accounted for in the enclosed mapping.

```

<SF mappings: sf on-shell mapping: TBP>+≡
  procedure :: compute => sf_os_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_os_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_os_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: r2, p2
    integer :: j
    p2 = p(mapping%i)
    call map_on_shell (r2, f, p2, mapping%lm2, x_free)
    r = p
    rb = pb
    do j = 1, 2
      r (mapping%i(j)) = r2(j)
      rb(mapping%i(j)) = 1 - r2(j)
    end do
  end subroutine sf_os_mapping_compute

```

Apply inverse. The irrelevant parameter p_1 is always set zero.

```

<SF mappings: sf on-shell mapping: TBP>+≡
  procedure :: inverse => sf_os_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_os_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_os_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f

```

```

real(default), dimension(:), intent(out) :: p, pb
real(default), intent(inout), optional :: x_free
real(default), dimension(2) :: p2, r2
r2 = r(mapping%i)
call map_on_shell_inverse (r2, f, p2, mapping%lm2, x_free)
p = r
pb= rb
p (mapping%i(1)) = p2(1)
pb(mapping%i(1)) = 1 - p2(1)
p (mapping%i(2)) = p2(2)
pb(mapping%i(2)) = 1 - p2(2)
end subroutine sf_os_mapping_inverse

```

15.4.6 Implementation: endpoint mapping

This maps the unit square (r_1, r_2) such that p_1 is the product $r_1 r_2$, while p_2 is related to the ratio. Furthermore, we enhance the region at $r_1 = 1$ and $r_2 = 1$, which translates into $p_1 = 1$ and $p_2 = 0, 1$. The enhancement is such that any power-like singularity is caught. This is useful for beamstrahlung spectra.

In addition, we allow for a delta-function singularity in r_1 and/or r_2 . The singularity is smeared to an interval of width ϵ . If nonzero, we distinguish the kinematical momentum fractions r_i from effective values x_i , which should go into the structure-function evaluation. A bin of width ϵ in r is mapped to $x = 1$ exactly, while the interval $(0, 1 - \epsilon)$ is mapped to $(0, 1)$ in x . The Jacobian reflects this distinction, and the logical `in_peak` allows for an unambiguous distinction.

The delta-peak fraction is used only for the integration self-test.

```

<SF mappings: public>+≡
  public :: sf_ep_mapping_t

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_ep_mapping_t
    real(default) :: a = 1
  contains
    <SF mappings: sf endpoint mapping: TBP>
  end type sf_ep_mapping_t

```

Output.

```

<SF mappings: sf endpoint mapping: TBP>≡
  procedure :: write => sf_ep_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_ep_mapping_write (object, unit)
    class(sf_ep_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "map"
    if (any (object%i /= 0)) then
      write (u, "('(',I0,',',I0,')')", advance="no") object%i
    end if
    write (u, "(A,ES12.5,A)") ": endpoint (a =", object%a, ")"
  end subroutine sf_ep_mapping_write

```

Initialize: no extra parameters.

```

<SF mappings: sf endpoint mapping: TBP>+≡
  procedure :: init => sf_ep_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_ep_mapping_init (mapping, a)
    class(sf_ep_mapping_t), intent(out) :: mapping
    real(default), intent(in), optional :: a
    call mapping%base_init (2)
    if (present (a)) mapping%a = a
  end subroutine sf_ep_mapping_init

```

Apply mapping.

```

<SF mappings: sf endpoint mapping: TBP>+≡
  procedure :: compute => sf_ep_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_ep_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_ep_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: px, r2
    real(default) :: f1, f2
    integer :: j
    call map_endpoint_1 (px(1), f1, p(mapping%i(1)), mapping%a)
    call map_endpoint_01 (px(2), f2, p(mapping%i(2)), mapping%a)
    call map_unit_square (r2, f, px)
    f = f * f1 * f2
    r = p
    rb= pb
    do j = 1, 2
      r (mapping%i(j)) = r2(j)
      rb(mapping%i(j)) = 1 - r2(j)
    end do
  end subroutine sf_ep_mapping_compute

```

Apply inverse.

```

<SF mappings: sf endpoint mapping: TBP>+≡
  procedure :: inverse => sf_ep_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_ep_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_ep_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: r2, px, p2
    real(default) :: f1, f2
    integer :: j
    do j = 1, 2

```

```

        r2(j) = r(mapping%i(j))
    end do
    call map_unit_square_inverse (r2, f, px)
    call map_endpoint_inverse_1 (px(1), f1, p2(1), mapping%a)
    call map_endpoint_inverse_01 (px(2), f2, p2(2), mapping%a)
    f = f * f1 * f2
    p = r
    pb= rb
    do j = 1, 2
        p (mapping%i(j)) = p2(j)
        pb(mapping%i(j)) = 1 - p2(j)
    end do
end subroutine sf_ep_mapping_inverse

```

15.4.7 Implementation: endpoint mapping with resonance

Like the endpoint mapping for p_2 , but replace the endpoint mapping by a Breit-Wigner mapping for p_1 . This covers resonance production in the presence of beamstrahlung.

If the flag `resonance` is unset, we skip the resonance mapping, so the parameter p_1 remains equal to $r_1 r_2$, as in the standard s-channel mapping.

```

<SF mappings: public>+≡
    public :: sf_epr_mapping_t

<SF mappings: types>+≡
    type, extends (sf_mapping_t) :: sf_epr_mapping_t
        real(default) :: a = 1
        real(default) :: m = 0
        real(default) :: w = 0
        logical :: resonance = .true.
    contains
    <SF mappings: sf endpoint/res mapping: TBP>
    end type sf_epr_mapping_t

```

Output.

```

<SF mappings: sf endpoint/res mapping: TBP>≡
    procedure :: write => sf_epr_mapping_write

<SF mappings: procedures>+≡
    subroutine sf_epr_mapping_write (object, unit)
        class(sf_epr_mapping_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)", advance="no") "map"
        if (any (object%i /= 0)) then
            write (u, "('(',I0,',',',I0,')')", advance="no") object%i
        end if
        if (object%resonance) then
            write (u, "(A,F7.5,A,F7.5,',',',F7.5,A)") ": ep/res (a = ", object%a, &
                " | ", object%m, object%w, ") "
        else

```

```

        write (u, "(A,F7.5,A)" ) ": ep/nores (a = ", object%a, ") "
    end if
end subroutine sf_epr_mapping_write

```

Initialize: if mass and width are not given, we initialize a non-resonant version of the mapping.

```

<SF mappings: sf endpoint/res mapping: TBP>+≡
    procedure :: init => sf_epr_mapping_init

<SF mappings: procedures>+≡
    subroutine sf_epr_mapping_init (mapping, a, m, w)
        class(sf_epr_mapping_t), intent(out) :: mapping
        real(default), intent(in) :: a
        real(default), intent(in), optional :: m, w
        call mapping%base_init (2)
        mapping%a = a
        if (present (m) .and. present (w)) then
            mapping%m = m
            mapping%w = w
        else
            mapping%resonance = .false.
        end if
    end subroutine sf_epr_mapping_init

```

Apply mapping.

```

<SF mappings: sf endpoint/res mapping: TBP>+≡
    procedure :: compute => sf_epr_mapping_compute

<SF mappings: procedures>+≡
    subroutine sf_epr_mapping_compute (mapping, r, rb, f, p, pb, x_free)
        class(sf_epr_mapping_t), intent(inout) :: mapping
        real(default), dimension(:), intent(out) :: r, rb
        real(default), intent(out) :: f
        real(default), dimension(:), intent(in) :: p, pb
        real(default), intent(inout), optional :: x_free
        real(default), dimension(2) :: px, r2
        real(default) :: f1, f2
        integer :: j
        if (mapping%resonance) then
            call map_breit_wigner &
                (px(1), f1, p(mapping%i(1)), mapping%m, mapping%w, x_free)
        else
            px(1) = p(mapping%i(1))
            f1 = 1
        end if
        call map_endpoint_01 (px(2), f2, p(mapping%i(2)), mapping%a)
        call map_unit_square (r2, f, px)
        f = f * f1 * f2
        r = p
        rb= pb
        do j = 1, 2
            r (mapping%i(j)) = r2(j)
            rb(mapping%i(j)) = 1 - r2(j)
        end do
    end subroutine sf_epr_mapping_compute

```

```
end subroutine sf_epr_mapping_compute
```

Apply inverse.

```
<SF mappings: sf endpoint/res mapping: TBP>+≡
  procedure :: inverse => sf_epr_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_epr_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_epr_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: px, p2
    real(default) :: f1, f2
    integer :: j
    call map_unit_square_inverse (r(mapping%i), f, px)
    if (mapping%resonance) then
      call map_breit_wigner_inverse &
        (px(1), f1, p2(1), mapping%m, mapping%w, x_free)
    else
      p2(1) = px(1)
      f1 = 1
    end if
    call map_endpoint_inverse_01 (px(2), f2, p2(2), mapping%a)
    f = f * f1 * f2
    p = r
    pb = rb
    do j = 1, 2
      p (mapping%i(j)) = p2(j)
      pb(mapping%i(j)) = 1 - p2(j)
    end do
  end subroutine sf_epr_mapping_inverse
```

15.4.8 Implementation: endpoint mapping for on-shell particle

Analogous to the resonance mapping, but the p_1 input is ignored altogether. This covers on-shell particle production in the presence of beamstrahlung.

```
<SF mappings: public>+≡
  public :: sf_epo_mapping_t

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_epo_mapping_t
    real(default) :: a = 1
    real(default) :: m = 0
    real(default) :: lm2 = 0
  contains
    <SF mappings: sf endpoint/os mapping: TBP>
  end type sf_epo_mapping_t
```

Output.

```
<SF mappings: sf endpoint/os mapping: TBP>≡
  procedure :: write => sf_epo_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_epo_mapping_write (object, unit)
    class(sf_epo_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "map"
    if (any (object%i /= 0)) then
      write (u, "('(',IO,',',IO,')')", advance="no") object%i
    end if
    write (u, "(A,F7.5,A,F7.5,A)") ": ep/on-shell (a = ", object%a, &
      " | ", object%m, ") "
  end subroutine sf_epo_mapping_write
```

Initialize: no extra parameters.

```
<SF mappings: sf endpoint/os mapping: TBP>+≡
  procedure :: init => sf_epo_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_epo_mapping_init (mapping, a, m)
    class(sf_epo_mapping_t), intent(out) :: mapping
    real(default), intent(in) :: a, m
    call mapping%base_init (2)
    mapping%a = a
    mapping%m = m
    mapping%lm2 = abs (2 * log (mapping%m))
  end subroutine sf_epo_mapping_init
```

Apply mapping.

```
<SF mappings: sf endpoint/os mapping: TBP>+≡
  procedure :: compute => sf_epo_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_epo_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_epo_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: px, r2
    real(default) :: f2
    integer :: j
    px(1) = 0
    call map_endpoint_01 (px(2), f2, p(mapping%i(2)), mapping%a)
    call map_on_shell (r2, f, px, mapping%lm2)
    f = f * f2
    r = p
    rb = pb
    do j = 1, 2
      r (mapping%i(j)) = r2(j)
    end do
```



```

        rb(mapping%i(j)) = 1 - r2(j)
    end do
end subroutine sf_epo_mapping_compute

```

Apply inverse.

```

<SF mappings: sf endpoint/os mapping: TBP>+≡
    procedure :: inverse => sf_epo_mapping_inverse

<SF mappings: procedures>+≡
    subroutine sf_epo_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
        class(sf_epo_mapping_t), intent(inout) :: mapping
        real(default), dimension(:), intent(in) :: r, rb
        real(default), intent(out) :: f
        real(default), dimension(:), intent(out) :: p, pb
        real(default), intent(inout), optional :: x_free
        real(default), dimension(2) :: px, p2
        real(default) :: f2
        integer :: j
        call map_on_shell_inverse (r(mapping%i), f, px, mapping%lm2)
        p2(1) = 0
        call map_endpoint_inverse_01 (px(2), f2, p2(2), mapping%a)
        f = f * f2
        p = r
        pb = rb
        do j = 1, 2
            p (mapping%i(j)) = p2(j)
            pb(mapping%i(j)) = 1 - p2(j)
        end do
    end subroutine sf_epo_mapping_inverse

```

15.4.9 Implementation: ISR endpoint mapping

Similar to the endpoint mapping above: This maps the unit square (r_1, r_2) such that p_1 is the product $r_1 r_2$, while p_2 is related to the ratio. Furthermore, we enhance the region at $r_1 = 1$ and $r_2 = 1$, which translates into $p_1 = 1$ and $p_2 = 0, 1$.

The enhancement is such that ISR singularity $(1 - x)^{-1+\epsilon}$ is flattened. This would be easy in one dimension, but becomes nontrivial in two dimensions.

```

<SF mappings: public>+≡
    public :: sf_ip_mapping_t

<SF mappings: types>+≡
    type, extends (sf_mapping_t) :: sf_ip_mapping_t
        real(default) :: eps = 0
        contains
        <SF mappings: sf power mapping: TBP>
    end type sf_ip_mapping_t

```

Output.

```

<SF mappings: sf power mapping: TBP>≡
    procedure :: write => sf_ip_mapping_write

```

```

<SF mappings: procedures>+≡
subroutine sf_ip_mapping_write (object, unit)
  class(sf_ip_mapping_t), intent(in) :: object
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)", advance="no") "map"
  if (any (object%i /= 0)) then
    write (u, "('(',I0,',',I0,')')", advance="no") object%i
  end if
  write (u, "(A,ES12.5,A)") ": isr (eps =", object%eps, ")"
end subroutine sf_ip_mapping_write

```

Initialize: no extra parameters.

```

<SF mappings: sf power mapping: TBP>+≡
procedure :: init => sf_ip_mapping_init

<SF mappings: procedures>+≡
subroutine sf_ip_mapping_init (mapping, eps)
  class(sf_ip_mapping_t), intent(out) :: mapping
  real(default), intent(in), optional :: eps
  call mapping%base_init (2)
  if (present (eps)) mapping%eps = eps
  if (mapping%eps <= 0) &
    call msg_fatal ("ISR mapping: regulator epsilon must not be zero")
end subroutine sf_ip_mapping_init

```

Apply mapping.

```

<SF mappings: sf power mapping: TBP>+≡
procedure :: compute => sf_ip_mapping_compute

<SF mappings: procedures>+≡
subroutine sf_ip_mapping_compute (mapping, r, rb, f, p, pb, x_free)
  class(sf_ip_mapping_t), intent(inout) :: mapping
  real(default), dimension(:), intent(out) :: r, rb
  real(default), intent(out) :: f
  real(default), dimension(:), intent(in) :: p, pb
  real(default), intent(inout), optional :: x_free
  real(default), dimension(2) :: px, pxb, r2, r2b
  real(default) :: f1, f2, xb, y, yb
  integer :: j
  call map_power_1 (xb, f1, pb(mapping%i(1)), 2 * mapping%eps)
  call map_power_01 (y, yb, f2, pb(mapping%i(2)), mapping%eps)
  px(1) = 1 - xb
  pxb(1) = xb
  px(2) = y
  pxb(2) = yb
  call map_unit_square_prec (r2, r2b, f, px, pxb)
  f = f * f1 * f2
  r = p
  rb = pb
  do j = 1, 2
    r (mapping%i(j)) = r2 (j)
    rb(mapping%i(j)) = r2b(j)
  end do

```

```

        end do
    end subroutine sf_ip_mapping_compute

```

Apply inverse.

```

<SF mappings: sf power mapping: TBP>+≡
    procedure :: inverse => sf_ip_mapping_inverse

<SF mappings: procedures>+≡
    subroutine sf_ip_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
        class(sf_ip_mapping_t), intent(inout) :: mapping
        real(default), dimension(:), intent(in) :: r, rb
        real(default), intent(out) :: f
        real(default), dimension(:), intent(out) :: p, pb
        real(default), intent(inout), optional :: x_free
        real(default), dimension(2) :: r2, r2b, px, pxb, p2, p2b
        real(default) :: f1, f2, xb, y, yb
        integer :: j
        do j = 1, 2
            r2(j) = r(mapping%i(j))
            r2b(j) = rb(mapping%i(j))
        end do
        call map_unit_square_inverse_prec (r2, r2b, f, px, pxb)
        xb = pxb(1)
        if (px(1) > 0) then
            y = px(2)
            yb = pxb(2)
        else
            y = 0.5_default
            yb = 0.5_default
        end if
        call map_power_inverse_1 (xb, f1, p2b(1), 2 * mapping%eps)
        call map_power_inverse_01 (y, yb, f2, p2b(2), mapping%eps)
        p2 = 1 - p2b
        f = f * f1 * f2
        p = r
        pb = rb
        do j = 1, 2
            p(mapping%i(j)) = p2(j)
            pb(mapping%i(j)) = p2b(j)
        end do
    end subroutine sf_ip_mapping_inverse

```

15.4.10 Implementation: ISR endpoint mapping, resonant

Similar to the endpoint mapping above: This maps the unit square (r_1, r_2) such that p_1 is the product $r_1 r_2$, while p_2 is related to the ratio. Furthermore, we enhance the region at $r_1 = 1$ and $r_2 = 1$, which translates into $p_1 = 1$ and $p_2 = 0, 1$.

The enhancement is such that ISR singularity $(1 - x)^{-1+\epsilon}$ is flattened. This would be easy in one dimension, but becomes nontrivial in two dimensions.

The resonance can be turned off by the flag **resonance**.

```

<SF mappings: public>+≡

```

```

public :: sf_ipr_mapping_t
<SF mappings: types>+≡
type, extends (sf_mapping_t) :: sf_ipr_mapping_t
  real(default) :: eps = 0
  real(default) :: m = 0
  real(default) :: w = 0
  logical :: resonance = .true.
contains
  <SF mappings: sf power/res mapping: TBP>
end type sf_ipr_mapping_t

```

Output.

```

<SF mappings: sf power/res mapping: TBP>≡
procedure :: write => sf_ipr_mapping_write

<SF mappings: procedures>+≡
subroutine sf_ipr_mapping_write (object, unit)
  class(sf_ipr_mapping_t), intent(in) :: object
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)", advance="no") "map"
  if (any (object%i /= 0)) then
    write (u, "('(',I0,',',I0,')')", advance="no") object%i
  end if
  if (object%resonance) then
    write (u, "(A,F7.5,A,F7.5,', ',F7.5,A)") ": isr/res (eps = ", &
      object%eps, " | ", object%m, object%w, ") "
  else
    write (u, "(A,F7.5,A)") ": isr/res (eps = ", object%eps, ") "
  end if
end subroutine sf_ipr_mapping_write

```

Initialize:

```

<SF mappings: sf power/res mapping: TBP>+≡
procedure :: init => sf_ipr_mapping_init

<SF mappings: procedures>+≡
subroutine sf_ipr_mapping_init (mapping, eps, m, w)
  class(sf_ipr_mapping_t), intent(out) :: mapping
  real(default), intent(in), optional :: eps, m, w
  call mapping%base_init (2)
  if (present (eps)) mapping%eps = eps
  if (mapping%eps <= 0) &
    call msg_fatal ("ISR mapping: regulator epsilon must not be zero")
  if (present (m) .and. present (w)) then
    mapping%m = m
    mapping%w = w
  else
    mapping%resonance = .false.
  end if
end subroutine sf_ipr_mapping_init

```

Apply mapping.

```

<SF mappings: sf power/res mapping: TBP>+≡
  procedure :: compute => sf_ipr_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_ipr_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_ipr_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: px, pxb, r2, r2b
    real(default) :: f1, f2, y, yb
    integer :: j
    if (mapping%resonance) then
      call map_breit_wigner &
        (px(1), f1, p(mapping%i(1)), mapping%m, mapping%w, x_free)
    else
      px(1) = p(mapping%i(1))
      f1 = 1
    end if
    call map_power_01 (y, yb, f2, pb(mapping%i(2)), mapping%eps)
    pxb(1) = 1 - px(1)
    px(2) = y
    pxb(2) = yb
    call map_unit_square_prec (r2, r2b, f, px, pxb)
    f = f * f1 * f2
    r = p
    rb = pb
    do j = 1, 2
      r (mapping%i(j)) = r2 (j)
      rb(mapping%i(j)) = r2b(j)
    end do
  end subroutine sf_ipr_mapping_compute

```

Apply inverse.

```

<SF mappings: sf power/res mapping: TBP>+≡
  procedure :: inverse => sf_ipr_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_ipr_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_ipr_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: r2, r2b, px, pxb, p2, p2b
    real(default) :: f1, f2, y, yb
    integer :: j
    do j = 1, 2
      r2 (j) = r (mapping%i(j))
      r2b(j) = rb(mapping%i(j))
    end do
    call map_unit_square_inverse_prec (r2, r2b, f, px, pxb)

```

```

if (px(1) > 0) then
  y = px(2)
  yb = pxb(2)
else
  y = 0.5_default
  yb = 0.5_default
end if
if (mapping%resonance) then
  call map_breit_wigner_inverse &
    (px(1), f1, p2(1), mapping%m, mapping%w, x_free)
else
  p2(1) = px(1)
  f1 = 1
end if
call map_power_inverse_01 (y, yb, f2, p2b(2), mapping%eps)
p2b(1) = 1 - p2(1)
p2 (2) = 1 - p2b(2)
f = f * f1 * f2
p = r
pb= rb
do j = 1, 2
  p (mapping%i(j)) = p2(j)
  pb(mapping%i(j)) = p2b(j)
end do
end subroutine sf_ipr_mapping_inverse

```

15.4.11 Implementation: ISR on-shell mapping

Similar to the endpoint mapping above: This maps the unit square (r_1, r_2) such that p_1 is ignored while the product $r_1 r_2$ is constant. p_2 is related to the ratio. Furthermore, we enhance the region at $r_1 = 1$ and $r_2 = 1$, which translates into $p_1 = 1$ and $p_2 = 0, 1$.

The enhancement is such that ISR singularity $(1 - x)^{-1+\epsilon}$ is flattened. This would be easy in one dimension, but becomes nontrivial in two dimensions.

```

<SF mappings: public>+≡
  public :: sf_ipo_mapping_t

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_ipo_mapping_t
    real(default) :: eps = 0
    real(default) :: m = 0
  contains
    <SF mappings: sf power/os mapping: TBP>
  end type sf_ipo_mapping_t

```

Output.

```

<SF mappings: sf power/os mapping: TBP>≡
  procedure :: write => sf_ipo_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_ipo_mapping_write (object, unit)
    class(sf_ipo_mapping_t), intent(in) :: object

```

```

integer, intent(in), optional :: unit
integer :: u
u = given_output_unit (unit)
write (u, "(1x,A)", advance="no") "map"
if (any (object%i /= 0)) then
    write (u, "('(',IO,',',IO,')')", advance="no") object%i
end if
write (u, "(A,F7.5,A,F7.5,A)" " : isr/os (eps = ", object%eps, &
" | ", object%m, ")")
end subroutine sf_ipo_mapping_write

```

Initialize: no extra parameters.

(SF mappings: sf power/os mapping: TBP)+≡

```

procedure :: init => sf_ipo_mapping_init

```

(SF mappings: procedures)+≡

```

subroutine sf_ipo_mapping_init (mapping, eps, m)
class(sf_ipo_mapping_t), intent(out) :: mapping
real(default), intent(in), optional :: eps, m
call mapping%base_init (2)
if (present (eps)) mapping%eps = eps
if (mapping%eps <= 0) &
    call msg_fatal ("ISR mapping: regulator epsilon must not be zero")
mapping%m = m
end subroutine sf_ipo_mapping_init

```

Apply mapping.

(SF mappings: sf power/os mapping: TBP)+≡

```

procedure :: compute => sf_ipo_mapping_compute

```

(SF mappings: procedures)+≡

```

subroutine sf_ipo_mapping_compute (mapping, r, rb, f, p, pb, x_free)
class(sf_ipo_mapping_t), intent(inout) :: mapping
real(default), dimension(:), intent(out) :: r, rb
real(default), intent(out) :: f
real(default), dimension(:), intent(in) :: p, pb
real(default), intent(inout), optional :: x_free
real(default), dimension(2) :: px, pxb, r2, r2b
real(default) :: f1, f2, y, yb
integer :: j
call map_power_01 (y, yb, f2, pb(mapping%i(2)), mapping%eps)
px(1) = mapping%m ** 2
if (present (x_free)) px(1) = px(1) / x_free
pxb(1) = 1 - px(1)
px(2) = y
pxb(2) = yb
call map_unit_square_prec (r2, r2b, f1, px, pxb)
f = f1 * f2
r = p
rb= pb
do j = 1, 2
    r (mapping%i(j)) = r2 (j)
    rb(mapping%i(j)) = r2b(j)
end do

```

```
end subroutine sf_ipo_mapping_compute
```

Apply inverse.

```

<SF mappings: sf power/os mapping: TBP>+≡
  procedure :: inverse => sf_ipo_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_ipo_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_ipo_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: r2, r2b, px, pxb, p2, p2b
    real(default) :: f1, f2, y, yb
    integer :: j
    do j = 1, 2
      r2(j) = r(mapping%i(j))
      r2b(j) = rb(mapping%i(j))
    end do
    call map_unit_square_inverse_prec (r2, r2b, f1, px, pxb)
    y = px(2)
    yb = pxb(2)
    call map_power_inverse_01 (y, yb, f2, p2b(2), mapping%eps)
    p2(1) = 0
    p2b(1) = 1
    p2(2) = 1 - p2b(2)
    f = f1 * f2
    p = r
    pb = rb
    do j = 1, 2
      p(mapping%i(j)) = p2(j)
      pb(mapping%i(j)) = p2b(j)
    end do
  end subroutine sf_ipo_mapping_inverse

```

15.4.12 Implementation: Endpoint + ISR power mapping

This is a combination of endpoint (i.e., beamstrahlung) and ISR power mapping. The first two parameters apply to the beamstrahlung spectrum, the last two to the ISR function for the first and second beam, respectively.

```

<SF mappings: public>+≡
  public :: sf_ei_mapping_t

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_ei_mapping_t
    type(sf_ep_mapping_t) :: ep
    type(sf_ip_mapping_t) :: ip
  contains
    <SF mappings: sf ep-ip mapping: TBP>
  end type sf_ei_mapping_t

```


Output.

```

<SF mappings: sf ep-ip mapping: TBP>≡
  procedure :: write => sf_ei_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_ei_mapping_write (object, unit)
    class(sf_ei_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "map"
    if (any (object%i /= 0)) then
      write (u, "('(',IO,3(' ',IO),')')", advance="no") object%i
    end if
    write (u, "(A,ES12.5,A,ES12.5,A)") ": ep/isr (a =", object%ep%a, &
      ", eps =", object%ip%eps, ")"
  end subroutine sf_ei_mapping_write

```

Initialize: no extra parameters.

```

<SF mappings: sf ep-ip mapping: TBP>+≡
  procedure :: init => sf_ei_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_ei_mapping_init (mapping, a, eps)
    class(sf_ei_mapping_t), intent(out) :: mapping
    real(default), intent(in), optional :: a, eps
    call mapping%base_init (4)
    call mapping%ep%init (a)
    call mapping%ip%init (eps)
  end subroutine sf_ei_mapping_init

```

Set an index value. We should communicate the appropriate indices to the enclosed sub-mappings, therefore override the method.

```

<SF mappings: sf ep-ip mapping: TBP>+≡
  procedure :: set_index => sf_ei_mapping_set_index

<SF mappings: procedures>+≡
  subroutine sf_ei_mapping_set_index (mapping, j, i)
    class(sf_ei_mapping_t), intent(inout) :: mapping
    integer, intent(in) :: j, i
    mapping%i(j) = i
    select case (j)
    case (1:2); call mapping%ep%set_index (j, i)
    case (3:4); call mapping%ip%set_index (j-2, i)
    end select
  end subroutine sf_ei_mapping_set_index

```

Apply mapping. Now, the beamstrahlung and ISR mappings are independent of each other. The parameter subsets that are actually used should not overlap. The Jacobians are multiplied.

```

<SF mappings: sf ep-ip mapping: TBP>+≡
  procedure :: compute => sf_ei_mapping_compute

```

```

⟨SF mappings: procedures⟩+=
  subroutine sf_ei_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_ei_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(size(p)) :: q, qb
    real(default) :: f1, f2
    call mapping%ep%compute (q, qb, f1, p, pb, x_free)
    call mapping%ip%compute (r, rb, f2, q, qb, x_free)
    f = f1 * f2
  end subroutine sf_ei_mapping_compute

```

Apply inverse.

```

⟨SF mappings: sf ep-ip mapping: TBP⟩+=
  procedure :: inverse => sf_ei_mapping_inverse

⟨SF mappings: procedures⟩+=
  subroutine sf_ei_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_ei_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(size(p)) :: q, qb
    real(default) :: f1, f2
    call mapping%ip%inverse (r, rb, f2, q, qb, x_free)
    call mapping%ep%inverse (q, qb, f1, p, pb, x_free)
    f = f1 * f2
  end subroutine sf_ei_mapping_inverse

```

15.4.13 Implementation: Endpoint + ISR + resonance

This is a combination of endpoint (i.e., beamstrahlung) and ISR power mapping, adapted for an s-channel resonance. The first two internal parameters apply to the beamstrahlung spectrum, the last two to the ISR function for the first and second beam, respectively. The first and third parameters are the result of an overall resonance mapping, so on the outside, the first parameter is the total momentum fraction, the third one describes the distribution between beamstrahlung and ISR.

```

⟨SF mappings: public⟩+=
  public :: sf_eir_mapping_t

⟨SF mappings: types⟩+=
  type, extends (sf_mapping_t) :: sf_eir_mapping_t
    type(sf_res_mapping_t) :: res
    type(sf_epr_mapping_t) :: ep
    type(sf_ipr_mapping_t) :: ip
  contains
    ⟨SF mappings: sf ep-ip-res mapping: TBP⟩
  end type sf_eir_mapping_t

```

Output.

```

<SF mappings: sf ep-ip-res mapping: TBP>≡
  procedure :: write => sf_eir_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_eir_mapping_write (object, unit)
    class(sf_eir_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "map"
    if (any (object%i /= 0)) then
      write (u, "('(',IO,3(' ',IO),')')", advance="no") object%i
    end if
    write (u, "(A,F7.5,A,F7.5,A,F7.5,', ',F7.5,A)" &
      ": ep/isr/res (a =", object%ep%a, &
      ", eps =", object%ip%eps, " | ", object%res%m, object%res%w, ")")
  end subroutine sf_eir_mapping_write

```

Initialize: no extra parameters.

```

<SF mappings: sf ep-ip-res mapping: TBP>+≡
  procedure :: init => sf_eir_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_eir_mapping_init (mapping, a, eps, m, w)
    class(sf_eir_mapping_t), intent(out) :: mapping
    real(default), intent(in) :: a, eps, m, w
    call mapping%base_init (4)
    call mapping%res%init (m, w)
    call mapping%ep%init (a)
    call mapping%ip%init (eps)
  end subroutine sf_eir_mapping_init

```

Set an index value. We should communicate the appropriate indices to the enclosed sub-mappings, therefore override the method.

```

<SF mappings: sf ep-ip-res mapping: TBP>+≡
  procedure :: set_index => sf_eir_mapping_set_index

<SF mappings: procedures>+≡
  subroutine sf_eir_mapping_set_index (mapping, j, i)
    class(sf_eir_mapping_t), intent(inout) :: mapping
    integer, intent(in) :: j, i
    mapping%i(j) = i
    select case (j)
      case (1); call mapping%res%set_index (1, i)
      case (3); call mapping%res%set_index (2, i)
    end select
    select case (j)
      case (1:2); call mapping%ep%set_index (j, i)
      case (3:4); call mapping%ip%set_index (j-2, i)
    end select
  end subroutine sf_eir_mapping_set_index

```

Apply mapping. Now, the beamstrahlung and ISR mappings are independent of each other. The parameter subsets that are actually used should not overlap. The Jacobians are multiplied.

```

<SF mappings: sf ep-ip-res mapping: TBP>+≡
  procedure :: compute => sf_eir_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_eir_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_eir_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(size(p)) :: px, pxb, q, qb
    real(default) :: f0, f1, f2
    call mapping%res%compute (px, pxb, f0, p, pb, x_free)
    call mapping%ep%compute (q, qb, f1, px, pxb, x_free)
    call mapping%ip%compute (r, rb, f2, q, qb, x_free)
    f = f0 * f1 * f2
  end subroutine sf_eir_mapping_compute

```

Apply inverse.

```

<SF mappings: sf ep-ip-res mapping: TBP>+≡
  procedure :: inverse => sf_eir_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_eir_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_eir_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(size(p)) :: px, pxb, q, qb
    real(default) :: f0, f1, f2
    call mapping%ip%inverse (r, rb, f2, q, qb, x_free)
    call mapping%ep%inverse (q, qb, f1, px, pxb, x_free)
    call mapping%res%inverse (px, pxb, f0, p, pb, x_free)
    f = f0 * f1 * f2
  end subroutine sf_eir_mapping_inverse

```

15.4.14 Implementation: Endpoint + ISR power mapping, on-shell

This is a combination of endpoint (i.e., beamstrahlung) and ISR power mapping. The first two parameters apply to the beamstrahlung spectrum, the last two to the ISR function for the first and second beam, respectively. On top of that, we map the first and third parameter such that the product is constant. From the outside, the first parameter is irrelevant while the third parameter describes the distribution of energy (loss) among beamstrahlung and ISR.

```

<SF mappings: public>+≡
  public :: sf_eio_mapping_t

```

```

<SF mappings: types>+≡
  type, extends (sf_mapping_t) :: sf_eio_mapping_t
    type(sf_os_mapping_t) :: os
    type(sf_epr_mapping_t) :: ep
    type(sf_ipr_mapping_t) :: ip
  contains
    <SF mappings: sf ep-ip-os mapping: TBP>
  end type sf_eio_mapping_t

```

Output.

```

<SF mappings: sf ep-ip-os mapping: TBP>≡
  procedure :: write => sf_eio_mapping_write

<SF mappings: procedures>+≡
  subroutine sf_eio_mapping_write (object, unit)
    class(sf_eio_mapping_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "map"
    if (any (object%i /= 0)) then
      write (u, "('(',I0,3(' ',I0),')')", advance="no") object%i
    end if
    write (u, "(A,F7.5,A,F7.5,A,F7.5,A)") ": ep/isr/os (a =", object%ep%a, &
      ", eps =", object%ip%eps, " | ", object%os%m, ")"
  end subroutine sf_eio_mapping_write

```

Initialize: no extra parameters.

```

<SF mappings: sf ep-ip-os mapping: TBP>+≡
  procedure :: init => sf_eio_mapping_init

<SF mappings: procedures>+≡
  subroutine sf_eio_mapping_init (mapping, a, eps, m)
    class(sf_eio_mapping_t), intent(out) :: mapping
    real(default), intent(in), optional :: a, eps, m
    call mapping%base_init (4)
    call mapping%os%init (m)
    call mapping%ep%init (a)
    call mapping%ip%init (eps)
  end subroutine sf_eio_mapping_init

```

Set an index value. We should communicate the appropriate indices to the enclosed sub-mappings, therefore override the method.

```

<SF mappings: sf ep-ip-os mapping: TBP>+≡
  procedure :: set_index => sf_eio_mapping_set_index

<SF mappings: procedures>+≡
  subroutine sf_eio_mapping_set_index (mapping, j, i)
    class(sf_eio_mapping_t), intent(inout) :: mapping
    integer, intent(in) :: j, i
    mapping%i(j) = i
    select case (j)
      case (1); call mapping%os%set_index (1, i)

```

```

    case (3); call mapping%os%set_index (2, i)
  end select
  select case (j)
    case (1:2); call mapping%ep%set_index (j, i)
    case (3:4); call mapping%ip%set_index (j-2, i)
  end select
end subroutine sf_eio_mapping_set_index

```

Apply mapping. Now, the beamstrahlung and ISR mappings are independent of each other. The parameter subsets that are actually used should not overlap. The Jacobians are multiplied.

```

<SF mappings: sf ep-ip-os mapping: TBP>+≡
  procedure :: compute => sf_eio_mapping_compute

<SF mappings: procedures>+≡
  subroutine sf_eio_mapping_compute (mapping, r, rb, f, p, pb, x_free)
    class(sf_eio_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(size(p)) :: px, pxb, q, qb
    real(default) :: f0, f1, f2
    call mapping%os%compute (px, pxb, f0, p, pb, x_free)
    call mapping%ep%compute (q, qb, f1, px, pxb, x_free)
    call mapping%ip%compute (r, rb, f2, q, qb, x_free)
    f = f0 * f1 * f2
  end subroutine sf_eio_mapping_compute

```

Apply inverse.

```

<SF mappings: sf ep-ip-os mapping: TBP>+≡
  procedure :: inverse => sf_eio_mapping_inverse

<SF mappings: procedures>+≡
  subroutine sf_eio_mapping_inverse (mapping, r, rb, f, p, pb, x_free)
    class(sf_eio_mapping_t), intent(inout) :: mapping
    real(default), dimension(:), intent(in) :: r, rb
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: p, pb
    real(default), intent(inout), optional :: x_free
    real(default), dimension(size(p)) :: px, pxb, q, qb
    real(default) :: f0, f1, f2
    call mapping%ip%inverse (r, rb, f2, q, qb, x_free)
    call mapping%ep%inverse (q, qb, f1, px, pxb, x_free)
    call mapping%os%inverse (px, pxb, f0, p, pb, x_free)
    f = f0 * f1 * f2
  end subroutine sf_eio_mapping_inverse

```

15.4.15 Basic formulas

Standard mapping of the unit square

This mapping of the unit square is appropriate in particular for structure functions which are concentrated at the lower end. Instead of a rectangular grid, one set of grid lines corresponds to constant parton c.m. energy. The other set is chosen such that the jacobian is only mildly singular ($\ln x$ which is zero at $x = 1$), corresponding to an initial concentration of sampling points at the maximum energy. If **power** is greater than one (the default), points are also concentrated at the lower end.

The formula is (**power**= α):

$$r_1 = (p_1^{p_2})^\alpha \quad (15.15)$$

$$r_2 = (p_1^{1-p_2})^\alpha \quad (15.16)$$

$$f = \alpha^2 p_1^{\alpha-1} |\log p_1| \quad (15.17)$$

and for the default case $\alpha = 1$:

$$r_1 = p_1^{p_2} \quad (15.18)$$

$$r_2 = p_1^{1-p_2} \quad (15.19)$$

$$f = |\log p_1| \quad (15.20)$$

(SF mappings: procedures) +=

```
subroutine map_unit_square (r, factor, p, power)
  real(default), dimension(2), intent(out) :: r
  real(default), intent(out) :: factor
  real(default), dimension(2), intent(in) :: p
  real(default), intent(in), optional :: power
  real(default) :: xx, yy
  factor = 1
  xx = p(1)
  yy = p(2)
  if (present(power)) then
    if (p(1) > 0 .and. power > 1) then
      xx = p(1)**power
      factor = factor * power * xx / p(1)
    end if
  end if
  if (xx /= 0) then
    r(1) = xx ** yy
    r(2) = xx / r(1)
    factor = factor * abs (log (xx))
  else
    r = 0
  end if
end subroutine map_unit_square
```

This is the inverse mapping.

(SF mappings: procedures) +=

```
subroutine map_unit_square_inverse (r, factor, p, power)
  real(kind=default), dimension(2), intent(in) :: r
```

```

real(kind=default), intent(out) :: factor
real(kind=default), dimension(2), intent(out) :: p
real(kind=default), intent(in), optional :: power
real(kind=default) :: lg, xx, yy
factor = 1
xx = r(1) * r(2)
if (xx /= 0) then
  lg = log (xx)
  if (lg /= 0) then
    yy = log (r(1)) / lg
  else
    yy = 0
  end if
  p(2) = yy
  factor = factor * abs (lg)
  if (present(power)) then
    p(1) = xx*(1._default/power)
    factor = factor * power * xx / p(1)
  else
    p(1) = xx
  end if
else
  p = 0
end if
end subroutine map_unit_square_inverse

```

Precise mapping of the unit square

A more precise version (with unit power parameter). This version should be numerically stable near $x = 1$ and $y = 0, 1$. The formulas are again

$$r_1 = p_1^{p_2}, \quad r_2 = p_1^{\bar{p}_2}, \quad f = -\log p_1 \quad (15.21)$$

but we compute both r_i and \bar{r}_i simultaneously and make direct use of both p_i and \bar{p}_i as appropriate.

(SF mappings: procedures)+≡

```

subroutine map_unit_square_prec (r, rb, factor, p, pb)
  real(default), dimension(2), intent(out) :: r
  real(default), dimension(2), intent(out) :: rb
  real(default), intent(out) :: factor
  real(default), dimension(2), intent(in) :: p
  real(default), dimension(2), intent(in) :: pb
  if (p(1) > 0.5_default) then
    call compute_prec_xy_1 (r(1), rb(1), p(1), pb(1), p (2))
    call compute_prec_xy_1 (r(2), rb(2), p(1), pb(1), pb(2))
    factor = - log_prec (p(1), pb(1))
  else if (p(1) > 0) then
    call compute_prec_xy_0 (r(1), rb(1), p(1), pb(1), p (2))
    call compute_prec_xy_0 (r(2), rb(2), p(1), pb(1), pb(2))
    factor = - log_prec (p(1), pb(1))
  else
    r = 0
    rb = 1
  end if
end subroutine

```



```

        factor = 0
    end if
end subroutine map_unit_square_prec

```

This is the inverse mapping.

(SF mappings: procedures)+≡

```

subroutine map_unit_square_inverse_prec (r, rb, factor, p, pb)
    real(default), dimension(2), intent(in) :: r
    real(default), dimension(2), intent(in) :: rb
    real(default), intent(out) :: factor
    real(default), dimension(2), intent(out) :: p
    real(default), dimension(2), intent(out) :: pb
    call inverse_prec_x (r, rb, p(1), pb(1))
    if (all (r > 0)) then
        if (rb(1) < rb(2)) then
            call inverse_prec_y (r, rb, p(2), pb(2))
        else
            call inverse_prec_y ([r(2),r(1)], [rb(2),rb(1)], pb(2), p(2))
        end if
        factor = - log_prec (p(1), pb(1))
    else
        p(1) = 0
        pb(1) = 1
        p(2) = 0.5_default
        pb(2) = 0.5_default
        factor = 0
    end if
end subroutine map_unit_square_inverse_prec

```

This is an auxiliary function: evaluate the expression $\bar{z} = 1 - x^y$ in a numerically stable way. Instabilities occur for $y = 0$ and $x = 1$. The idea is to replace the bracket by the first terms of its Taylor expansion around $x = 1$ (read $\bar{x} \equiv 1 - x$)

$$1 - x^y = y\bar{x} \left(1 + \frac{1}{2}(1 - y)\bar{x} + \frac{1}{6}(2 - y)(1 - y)\bar{x}^2 \right) \quad (15.22)$$

whenever this is the better approximation. Actually, the relative numerical error of the exact formula is about $\eta/(y\bar{x})$ where η is given by `epsilon(KIND)` in Fortran. The relative error of the approximation is better than the last included term divided by $(y\bar{x})$.

The first subroutine computes z and \bar{z} near $x = 1$ where $\log x$ should be expanded, the second one near $x = 0$ where $\log x$ can be kept.

(SF mappings: procedures)+≡

```

subroutine compute_prec_xy_1 (z, zb, x, xb, y)
    real(default), intent(out) :: z, zb
    real(default), intent(in) :: x, xb, y
    real(default) :: a1, a2, a3
    a1 = y * xb
    a2 = a1 * (1 - y) * xb / 2
    a3 = a2 * (2 - y) * xb / 3
    if (abs (a3) < epsilon (a3)) then
        zb = a1 + a2 + a3
        z = 1 - zb
    end if
end subroutine compute_prec_xy_1

```

```

else
  z = x ** y
  zb = 1 - z
end if
end subroutine compute_prec_xy_1

subroutine compute_prec_xy_0 (z, zb, x, xb, y)
  real(default), intent(out) :: z, zb
  real(default), intent(in) :: x, xb, y
  real(default) :: a1, a2, a3, lx
  lx = -log (x)
  a1 = y * lx
  a2 = a1 * y * lx / 2
  a3 = a2 * y * lx / 3
  if (abs (a3) < epsilon (a3)) then
    zb = a1 + a2 + a3
    z = 1 - zb
  else
    z = x ** y
    zb = 1 - z
  end if
end subroutine compute_prec_xy_0

```

For the inverse calculation, we evaluate $x = r_1 r_2$ in a stable way. Since it is just a polynomial, the expansion near $x = 1$ is analytically exact, and we don't need to choose based on precision.

(SF mappings: procedures) +≡

```

subroutine inverse_prec_x (r, rb, x, xb)
  real(default), dimension(2), intent(in) :: r, rb
  real(default), intent(out) :: x, xb
  real(default) :: a0, a1
  a0 = rb(1) + rb(2)
  a1 = rb(1) * rb(2)
  if (a0 > 0.5_default) then
    xb = a0 - a1
    x = 1 - xb
  else
    x = r(1) * r(2)
    xb = 1 - x
  end if
end subroutine inverse_prec_x

```

The inverse calculation for the relative momentum fraction

$$y = \frac{1}{1 + \frac{\log r_2}{\log r_1}} \quad (15.23)$$

is slightly more complicated. We should take the precise form of the logarithm, so we are safe near $r_i = 1$. A series expansion is required if $r_1 \ll r_2$, since then y becomes small. (We assume $r_1 < r_2$ here; for the opposite case, the arguments can be exchanged.)

(SF mappings: procedures) +≡

```

subroutine inverse_prec_y (r, rb, y, yb)

```

```

real(default), dimension(2), intent(in) :: r, rb
real(default), intent(out) :: y, yb
real(default) :: log1, log2, a1, a2, a3
log1 = log_prec (r(1), rb(1))
log2 = log_prec (r(2), rb(2))
a1 = - rb(1) / log2
a2 = - rb(1) ** 2 * (one / log2**2 + one/(2*log2))
if (abs (log2**3) < epsilon (one)) then
  if (abs(log1) < epsilon (one)) then
    y = zero
  else
    y = one / (one+log2/log1)
  end if
  if (abs(log2) < epsilon (one)) then
    yb = zero
  else
    yb = one / (one+log1/log2)
  end if
  return
else
  a3 = - rb(1) ** 3 * (one / log2**3 + one/log2**2 + one/(3 * log2))
end if
if (abs (a3) < epsilon (a3)) then
  y = a1 + a2 + a3
  yb = one - y
else
  y = one / (one+log2/log1)
  yb = one / (one+log1/log2)
end if
end subroutine inverse_prec_y

```

We also need an evaluation of $\log x$ which is stable near $x = 1$.

```

<SF mappings: public>+≡
public :: log_prec

<SF mappings: procedures>+≡
function log_prec (x, xb) result (lx)
  real(default), intent(in) :: x, xb
  real(default) :: a1, a2, a3, lx
  a1 = xb
  a2 = a1 * xb / 2
  a3 = a2 * xb * 2 / 3
  if (abs (a3) < epsilon (a3)) then
    lx = - a1 - a2 - a3
  else
    lx = log (x)
  end if
end function log_prec

```

Mapping for on-shell s-channel

The limiting case, if the product $r_1 r_2$ is fixed for on-shell production. The parameter p_1 is ignored. In the inverse mapping, it is returned zero.

The parameter `x_free`, if present, rescales the total energy. If it is less than one, the rescaled mass parameter m^2 should be increased accordingly.

(SF mappings: procedures)+≡

```

subroutine map_on_shell (r, factor, p, lm2, x_free)
  real(default), dimension(2), intent(out) :: r
  real(default), intent(out) :: factor
  real(default), dimension(2), intent(in) :: p
  real(default), intent(in) :: lm2
  real(default), intent(in), optional :: x_free
  real(default) :: lx
  lx = lm2; if (present (x_free)) lx = lx + log (x_free)
  r(1) = exp (- p(2) * lx)
  r(2) = exp (- (1 - p(2)) * lx)
  factor = lx
end subroutine map_on_shell

subroutine map_on_shell_inverse (r, factor, p, lm2, x_free)
  real(default), dimension(2), intent(in) :: r
  real(default), intent(out) :: factor
  real(default), dimension(2), intent(out) :: p
  real(default), intent(in) :: lm2
  real(default), intent(in), optional :: x_free
  real(default) :: lx
  lx = lm2; if (present (x_free)) lx = lx + log (x_free)
  p(1) = 0
  p(2) = abs (log (r(1))) / lx
  factor = lx
end subroutine map_on_shell_inverse

```

This is the standard Breit-Wigner mapping. We apply it to a single variable, independently of or in addition to a unit-square mapping. We assume here that the limits for the variable are 0 and 1, and that the mass m and width w are rescaled appropriately, so they are dimensionless and usually between 0 and 1.

If `x_free` is set, it rescales the total energy and thus mass and width, since these are defined with respect to the total energy.

(SF mappings: procedures)+≡

```

subroutine map_breit_wigner (r, factor, p, m, w, x_free)
  real(default), intent(out) :: r
  real(default), intent(out) :: factor
  real(default), intent(in) :: p
  real(default), intent(in) :: m
  real(default), intent(in) :: w
  real(default), intent(in), optional :: x_free
  real(default) :: m2, mw, a1, a2, a3, z, tmp
  m2 = m ** 2
  mw = m * w
  if (present (x_free)) then
    m2 = m2 / x_free
    mw = mw / x_free
  end if
  a1 = atan (- m2 / mw)
  a2 = atan ((1 - m2) / mw)
  a3 = (a2 - a1) * mw

```

```

z = (1-p) * a1 + p * a2
if (-pi/2 < z .and. z < pi/2) then
    tmp = tan (z)
    r = max (m2 + mw * tmp, 0._default)
    factor = a3 * (1 + tmp ** 2)
else
    r = 0
    factor = 0
end if
end subroutine map_breit_wigner

subroutine map_breit_wigner_inverse (r, factor, p, m, w, x_free)
    real(default), intent(in) :: r
    real(default), intent(out) :: factor
    real(default), intent(out) :: p
    real(default), intent(in) :: m
    real(default), intent(in) :: w
    real(default) :: m2, mw, a1, a2, a3, tmp
    real(default), intent(in), optional :: x_free
    m2 = m ** 2
    mw = m * w
    if (present (x_free)) then
        m2 = m2 / x_free
        mw = mw / x_free
    end if
    a1 = atan (- m2 / mw)
    a2 = atan ((1 - m2) / mw)
    a3 = (a2 - a1) * mw
    tmp = (r - m2) / mw
    p = (atan (tmp) - a1) / (a2 - a1)
    factor = a3 * (1 + tmp ** 2)
end subroutine map_breit_wigner_inverse

```

Mapping with endpoint enhancement

This is a mapping which is close to the unit mapping, except that at the endpoint(s), the output values are exponentially enhanced.

$$y = \tanh(a \tan(\frac{\pi}{2}x)) \quad (15.24)$$

We have two variants: one covers endpoints at 0 and 1 symmetrically, while the other one (which essentially maps one-half of the range), covers only the endpoint at 1.

(SF mappings: procedures)+≡

```

subroutine map_endpoint_1 (x3, factor, x1, a)
    real(default), intent(out) :: x3, factor
    real(default), intent(in) :: x1
    real(default), intent(in) :: a
    real(default) :: x2
    if (abs (x1) < 1) then
        x2 = tan (x1 * pi / 2)
        x3 = tanh (a * x2)
    end if
end subroutine map_endpoint_1

```

```

        factor = a * pi/2 * (1 + x2 ** 2) * (1 - x3 ** 2)
    else
        x3 = x1
        factor = 0
    end if
end subroutine map_endpoint_1

subroutine map_endpoint_inverse_1 (x3, factor, x1, a)
    real(default), intent(in) :: x3
    real(default), intent(out) :: x1, factor
    real(default), intent(in) :: a
    real(default) :: x2
    if (abs (x3) < 1) then
        x2 = atanh (x3) / a
        x1 = 2 / pi * atan (x2)
        factor = a * pi/2 * (1 + x2 ** 2) * (1 - x3 ** 2)
    else
        x1 = x3
        factor = 0
    end if
end subroutine map_endpoint_inverse_1

subroutine map_endpoint_01 (x4, factor, x0, a)
    real(default), intent(out) :: x4, factor
    real(default), intent(in) :: x0
    real(default), intent(in) :: a
    real(default) :: x1, x3
    x1 = 2 * x0 - 1
    call map_endpoint_1 (x3, factor, x1, a)
    x4 = (x3 + 1) / 2
end subroutine map_endpoint_01

subroutine map_endpoint_inverse_01 (x4, factor, x0, a)
    real(default), intent(in) :: x4
    real(default), intent(out) :: x0, factor
    real(default), intent(in) :: a
    real(default) :: x1, x3
    x3 = 2 * x4 - 1
    call map_endpoint_inverse_1 (x3, factor, x1, a)
    x0 = (x1 + 1) / 2
end subroutine map_endpoint_inverse_01

```

Mapping with endpoint enhancement (ISR)

This is another endpoint mapping. It is designed to flatten the ISR singularity which is of power type at $x = 1$, i.e., if

$$\sigma = \int_0^1 dx f(x) G(x) = \int_0^1 dx \epsilon (1-x)^{-1+\epsilon} G(x), \quad (15.25)$$

we replace this by

$$r = x^\epsilon \implies \sigma = \int_0^1 dr G(1 - (1-r)^{1/\epsilon}). \quad (15.26)$$

We expect that ϵ is small.

The actual mapping is $r \rightarrow x$ (so x emerges closer to 1). The Jacobian that we return is thus $1/f(x)$. We compute the mapping in terms of $\bar{x} \equiv 1 - x$, so we can achieve the required precision. Because some compilers show quite wild numeric fluctuations, we internally convert numeric types to explicit double precision.

```

<SF mappings: public>+≡
  public :: map_power_1
  public :: map_power_inverse_1

<SF mappings: procedures>+≡
  subroutine map_power_1 (xb, factor, rb, eps)
    real(default), intent(out) :: xb, factor
    real(default), intent(in) :: rb
    real(double) :: rb_db, factor_db, eps_db, xb_db
    real(default), intent(in) :: eps
    rb_db = real (rb, kind=double)
    eps_db = real (eps, kind=double)
    xb_db = rb_db ** (1 / eps_db)
    if (rb_db > 0) then
      factor_db = xb_db / rb_db / eps_db
      factor = real (factor_db, kind=default)
    else
      factor = 0
    end if
    xb = real (xb_db, kind=default)
  end subroutine map_power_1

  subroutine map_power_inverse_1 (xb, factor, rb, eps)
    real(default), intent(in) :: xb
    real(default), intent(out) :: rb, factor
    real(double) :: xb_db, factor_db, eps_db, rb_db
    real(default), intent(in) :: eps
    xb_db = real (xb, kind=double)
    eps_db = real (eps, kind=double)
    rb_db = xb_db ** eps_db
    if (xb_db > 0) then
      factor_db = xb_db / rb_db / eps_db
      factor = real (factor_db, kind=default)
    else
      factor = 0
    end if
    rb = real (rb_db, kind=default)
  end subroutine map_power_inverse_1

```

Here we apply a power mapping to both endpoints. We divide the interval in two equal halves and apply the power mapping for the nearest endpoint, either 0 or 1.

```

<SF mappings: procedures>+≡
  subroutine map_power_01 (y, yb, factor, r, eps)
    real(default), intent(out) :: y, yb, factor
    real(default), intent(in) :: r
    real(default), intent(in) :: eps

```

```

real(default) :: u, ub, zp, zm
u = 2 * r - 1
if (u > 0) then
    ub = 2 * (1 - r)
    call map_power_1 (zm, factor, ub, eps)
    zp = 2 - zm
else if (u < 0) then
    ub = 2 * r
    call map_power_1 (zp, factor, ub, eps)
    zm = 2 - zp
else
    factor = 1 / eps
    zp = 1
    zm = 1
end if
y = zp / 2
yb = zm / 2
end subroutine map_power_01

subroutine map_power_inverse_01 (y, yb, factor, r, eps)
real(default), intent(in) :: y, yb
real(default), intent(out) :: r, factor
real(default), intent(in) :: eps
real(default) :: ub, zp, zm
zp = 2 * y
zm = 2 * yb
if (zm < zp) then
    call map_power_inverse_1 (zm, factor, ub, eps)
    r = 1 - ub / 2
else if (zp < zm) then
    call map_power_inverse_1 (zp, factor, ub, eps)
    r = ub / 2
else
    factor = 1 / eps
    ub = 1
    r = ub / 2
end if
end subroutine map_power_inverse_01

```

Structure-function channels

A structure-function chain parameterization (channel) may contain a mapping that applies to multiple structure functions. This is described by an extension of the `sf_mapping_t` type. In addition, it may contain mappings that apply to (other) individual structure functions. The details of these mappings are implementation-specific.

The `sf_channel_t` type combines this information. It contains an array of map codes, one for each structure-function entry. The code values are:

none MC input parameters r directly become energy fractions x

single default mapping for a single structure-function entry

multi/s map $r \rightarrow x$ such that one MC input parameter is \hat{s}/s

multi/resonance as before, adapted to s-channel resonance

multi/on-shell as before, adapted to an on-shell particle in the s channel

multi/endpoint like multi/s, but enhance the region near $r_i = 1$

multi/endpoint/res endpoint mapping with resonance

multi/endpoint/os endpoint mapping for on-shell

multi/power/os like multi/endpoint, regulating a power singularity

```
<SF mappings: parameters>≡
  integer, parameter :: SFMAP_NONE = 0
  integer, parameter :: SFMAP_SINGLE = 1
  integer, parameter :: SFMAP_MULTI_S = 2
  integer, parameter :: SFMAP_MULTI_RES = 3
  integer, parameter :: SFMAP_MULTI_ONS = 4
  integer, parameter :: SFMAP_MULTI_EP = 5
  integer, parameter :: SFMAP_MULTI_EPR = 6
  integer, parameter :: SFMAP_MULTI_EPO = 7
  integer, parameter :: SFMAP_MULTI_IP = 8
  integer, parameter :: SFMAP_MULTI_IPR = 9
  integer, parameter :: SFMAP_MULTI_IPO = 10
  integer, parameter :: SFMAP_MULTI_EI = 11
```

Then, it contains an allocatable entry for the multi mapping. This entry holds the MC-parameter indices on which the mapping applies (there may be more than one MC parameter per structure-function entry) and any parameters associated with the mapping.

There can be only one multi-mapping per channel.

```
<SF mappings: public>+≡
  public :: sf_channel_t

<SF mappings: types>+≡
  type :: sf_channel_t
    integer, dimension(:), allocatable :: map_code
    class(sf_mapping_t), allocatable :: multi_mapping
    contains
      <SF mappings: sf channel: TBP>
    end type sf_channel_t
```

The output format prints a single character for each structure-function entry and, if applicable, an account of the mapping parameters.

```
<SF mappings: sf channel: TBP>≡
  procedure :: write => sf_channel_write

<SF mappings: procedures>+≡
  subroutine sf_channel_write (object, unit)
    class(sf_channel_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
```

```

if (allocated (object%map_code)) then
  do i = 1, size (object%map_code)
    select case (object%map_code (i))
      case (SFMAP_NONE)
        write (u, "(1x,A)", advance="no") "-"
      case (SFMAP_SINGLE)
        write (u, "(1x,A)", advance="no") "+"
      case (SFMAP_MULTI_S)
        write (u, "(1x,A)", advance="no") "s"
      case (SFMAP_MULTI_RES)
        write (u, "(1x,A)", advance="no") "r"
      case (SFMAP_MULTI_ONS)
        write (u, "(1x,A)", advance="no") "o"
      case (SFMAP_MULTI_EP)
        write (u, "(1x,A)", advance="no") "e"
      case (SFMAP_MULTI_EPR)
        write (u, "(1x,A)", advance="no") "p"
      case (SFMAP_MULTI_EPO)
        write (u, "(1x,A)", advance="no") "q"
      case (SFMAP_MULTI_IP)
        write (u, "(1x,A)", advance="no") "i"
      case (SFMAP_MULTI_IPR)
        write (u, "(1x,A)", advance="no") "i"
      case (SFMAP_MULTI_IPO)
        write (u, "(1x,A)", advance="no") "i"
      case (SFMAP_MULTI_EI)
        write (u, "(1x,A)", advance="no") "i"
    end select
  end do
else
  write (u, "(1x,A)", advance="no") "-"
end if
if (allocated (object%multi_mapping)) then
  write (u, "(1x,'/ ')", advance="no")
  call object%multi_mapping%write (u)
else
  write (u, *)
end if
end subroutine sf_channel_write

```

Initializer for a single `sf_channel` object.

```

<SF mappings: sf channel: TBP>+≡
  procedure :: init => sf_channel_init

<SF mappings: procedures>+≡
  subroutine sf_channel_init (channel, n_strfun)
    class(sf_channel_t), intent(out) :: channel
    integer, intent(in) :: n_strfun
    allocate (channel%map_code (n_strfun))
    channel%map_code = SFMAP_NONE
  end subroutine sf_channel_init

```

Assignment. This merely copies intrinsic assignment, but apparently the latter

is bugged in gfortran 4.6.3, causing memory corruption.

```

<SF mappings: sf channel: TBP>+≡
  generic :: assignment (=) => sf_channel_assign
  procedure :: sf_channel_assign

<SF mappings: procedures>+≡
  subroutine sf_channel_assign (copy, original)
    class(sf_channel_t), intent(out) :: copy
    type(sf_channel_t), intent(in) :: original
    allocate (copy%map_code (size (original%map_code)))
    copy%map_code = original%map_code
    if (allocated (original%multi_mapping)) then
      allocate (copy%multi_mapping, source = original%multi_mapping)
    end if
  end subroutine sf_channel_assign

```

This initializer allocates an array of channels with common number of structure-function entries, therefore it is not a type-bound procedure.

```

<SF mappings: public>+≡
  public :: allocate_sf_channels

<SF mappings: procedures>+≡
  subroutine allocate_sf_channels (channel, n_channel, n_strfun)
    type(sf_channel_t), dimension(:), intent(out), allocatable :: channel
    integer, intent(in) :: n_channel
    integer, intent(in) :: n_strfun
    integer :: c
    allocate (channel (n_channel))
    do c = 1, n_channel
      call channel(c)%init (n_strfun)
    end do
  end subroutine allocate_sf_channels

```

This marks a given subset of indices as single-mapping.

```

<SF mappings: sf channel: TBP>+≡
  procedure :: activate_mapping => sf_channel_activate_mapping

<SF mappings: procedures>+≡
  subroutine sf_channel_activate_mapping (channel, i_sf)
    class(sf_channel_t), intent(inout) :: channel
    integer, dimension(:), intent(in) :: i_sf
    channel%map_code(i_sf) = SFMAP_SINGLE
  end subroutine sf_channel_activate_mapping

```

This sets an s-channel multichannel mapping. The length of the `i_sf` array must be 2. The parameter indices are not yet set.

```

<SF mappings: sf channel: TBP>+≡
  procedure :: set_s_mapping => sf_channel_set_s_mapping

<SF mappings: procedures>+≡
  subroutine sf_channel_set_s_mapping (channel, i_sf, power)
    class(sf_channel_t), intent(inout) :: channel
    integer, dimension(:), intent(in) :: i_sf
    real(default), intent(in), optional :: power

```

```

channel%map_code(i_sf) = SFMAP_MULTI_S
allocate (sf_s_mapping_t :: channel%multi_mapping)
select type (mapping => channel%multi_mapping)
type is (sf_s_mapping_t)
    call mapping%init (power)
end select
end subroutine sf_channel_set_s_mapping

```

This sets an s-channel resonance multichannel mapping.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_res_mapping => sf_channel_set_res_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_res_mapping (channel, i_sf, m, w)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in) :: m, w
        channel%map_code(i_sf) = SFMAP_MULTI_RES
        allocate (sf_res_mapping_t :: channel%multi_mapping)
        select type (mapping => channel%multi_mapping)
        type is (sf_res_mapping_t)
            call mapping%init (m, w)
        end select
    end subroutine sf_channel_set_res_mapping

```

This sets an s-channel on-shell multichannel mapping. The length of the `i_sf` array must be 2. (The first parameter actually becomes an irrelevant dummy.)

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_os_mapping => sf_channel_set_os_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_os_mapping (channel, i_sf, m)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in) :: m
        channel%map_code(i_sf) = SFMAP_MULTI_ONS
        allocate (sf_os_mapping_t :: channel%multi_mapping)
        select type (mapping => channel%multi_mapping)
        type is (sf_os_mapping_t)
            call mapping%init (m)
        end select
    end subroutine sf_channel_set_os_mapping

```

This sets an s-channel endpoint mapping. The parameter a is the slope parameter (default 1); increasing it moves the endpoint region (at $x = 1$ to lower values in the input parameter. region even more.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_ep_mapping => sf_channel_set_ep_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_ep_mapping (channel, i_sf, a)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf

```

```

    real(default), intent(in), optional :: a
    channel%map_code(i_sf) = SFMAP_MULTI_EP
    allocate (sf_ep_mapping_t :: channel%multi_mapping)
    select type (mapping => channel%multi_mapping)
    type is (sf_ep_mapping_t)
        call mapping%init (a = a)
    end select
end subroutine sf_channel_set_ep_mapping

```

This sets a resonant endpoint mapping.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_epr_mapping => sf_channel_set_epr_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_epr_mapping (channel, i_sf, a, m, w)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in) :: a, m, w
        channel%map_code(i_sf) = SFMAP_MULTI_EPR
        allocate (sf_epr_mapping_t :: channel%multi_mapping)
        select type (mapping => channel%multi_mapping)
        type is (sf_epr_mapping_t)
            call mapping%init (a, m, w)
        end select
    end subroutine sf_channel_set_epr_mapping

```

This sets an on-shell endpoint mapping.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_epo_mapping => sf_channel_set_epo_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_epo_mapping (channel, i_sf, a, m)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in) :: a, m
        channel%map_code(i_sf) = SFMAP_MULTI_EPO
        allocate (sf_epo_mapping_t :: channel%multi_mapping)
        select type (mapping => channel%multi_mapping)
        type is (sf_epo_mapping_t)
            call mapping%init (a, m)
        end select
    end subroutine sf_channel_set_epo_mapping

```

This sets an s-channel power mapping, regulating a singularity of type $(1 - x)^{-1+\epsilon}$. The parameter ϵ depends on the structure function.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_ip_mapping => sf_channel_set_ip_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_ip_mapping (channel, i_sf, eps)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in), optional :: eps

```

```

channel%map_code(i_sf) = SFMAP_MULTI_IP
allocate (sf_ip_mapping_t :: channel%multi_mapping)
select type (mapping => channel%multi_mapping)
type is (sf_ip_mapping_t)
    call mapping%init (eps)
end select
end subroutine sf_channel_set_ip_mapping

```

This sets an s-channel resonant power mapping, regulating a singularity of type $(1-x)^{-1+\epsilon}$ in the presence of an s-channel resonance. The parameter ϵ depends on the structure function.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_ipr_mapping => sf_channel_set_ipr_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_ipr_mapping (channel, i_sf, eps, m, w)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in), optional :: eps, m, w
        channel%map_code(i_sf) = SFMAP_MULTI_IPR
        allocate (sf_ipr_mapping_t :: channel%multi_mapping)
        select type (mapping => channel%multi_mapping)
        type is (sf_ipr_mapping_t)
            call mapping%init (eps, m, w)
        end select
    end subroutine sf_channel_set_ipr_mapping

```

This sets an on-shell power mapping, regulating a singularity of type $(1-x)^{-1+\epsilon}$ for the production of a single on-shell particle.. The parameter ϵ depends on the structure function.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_ipo_mapping => sf_channel_set_ipo_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_ipo_mapping (channel, i_sf, eps, m)
        class(sf_channel_t), intent(inout) :: channel
        integer, dimension(:), intent(in) :: i_sf
        real(default), intent(in), optional :: eps, m
        channel%map_code(i_sf) = SFMAP_MULTI_IPO
        allocate (sf_ipo_mapping_t :: channel%multi_mapping)
        select type (mapping => channel%multi_mapping)
        type is (sf_ipo_mapping_t)
            call mapping%init (eps, m)
        end select
    end subroutine sf_channel_set_ipo_mapping

```

This sets a combined endpoint/ISR mapping.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_ei_mapping => sf_channel_set_ei_mapping

<SF mappings: procedures>+≡
    subroutine sf_channel_set_ei_mapping (channel, i_sf, a, eps)
        class(sf_channel_t), intent(inout) :: channel

```

```

integer, dimension(:), intent(in) :: i_sf
real(default), intent(in), optional :: a, eps
channel%map_code(i_sf) = SFMAP_MULTI_EI
allocate (sf_ei_mapping_t :: channel%multi_mapping)
select type (mapping => channel%multi_mapping)
type is (sf_ei_mapping_t)
    call mapping%init (a, eps)
end select
end subroutine sf_channel_set_ei_mapping

```

This sets a combined endpoint/ISR mapping with resonance.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_eir_mapping => sf_channel_set_eir_mapping

<SF mappings: procedures>+≡
subroutine sf_channel_set_eir_mapping (channel, i_sf, a, eps, m, w)
    class(sf_channel_t), intent(inout) :: channel
    integer, dimension(:), intent(in) :: i_sf
    real(default), intent(in), optional :: a, eps, m, w
    channel%map_code(i_sf) = SFMAP_MULTI_EI
    allocate (sf_eir_mapping_t :: channel%multi_mapping)
    select type (mapping => channel%multi_mapping)
    type is (sf_eir_mapping_t)
        call mapping%init (a, eps, m, w)
    end select
end subroutine sf_channel_set_eir_mapping

```

This sets a combined endpoint/ISR mapping, on-shell.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: set_eio_mapping => sf_channel_set_eio_mapping

<SF mappings: procedures>+≡
subroutine sf_channel_set_eio_mapping (channel, i_sf, a, eps, m)
    class(sf_channel_t), intent(inout) :: channel
    integer, dimension(:), intent(in) :: i_sf
    real(default), intent(in), optional :: a, eps, m
    channel%map_code(i_sf) = SFMAP_MULTI_EI
    allocate (sf_eio_mapping_t :: channel%multi_mapping)
    select type (mapping => channel%multi_mapping)
    type is (sf_eio_mapping_t)
        call mapping%init (a, eps, m)
    end select
end subroutine sf_channel_set_eio_mapping

```

Return true if the mapping code at position i_sf is SFMAP_SINGLE.

```

<SF mappings: sf channel: TBP>+≡
    procedure :: is_single_mapping => sf_channel_is_single_mapping

<SF mappings: procedures>+≡
function sf_channel_is_single_mapping (channel, i_sf) result (flag)
    class(sf_channel_t), intent(in) :: channel
    integer, intent(in) :: i_sf
    logical :: flag
    flag = channel%map_code(i_sf) == SFMAP_SINGLE

```

```
end function sf_channel_is_single_mapping
```

Return true if the mapping code at position `i_sf` is any of the `SFMAP_MULTI` mappings.

```
<SF mappings: sf channel: TBP>+≡
  procedure :: is_multi_mapping => sf_channel_is_multi_mapping

<SF mappings: procedures>+≡
  function sf_channel_is_multi_mapping (channel, i_sf) result (flag)
    class(sf_channel_t), intent(in) :: channel
    integer, intent(in) :: i_sf
    logical :: flag
    select case (channel%map_code(i_sf))
    case (SFMAP_NONE, SFMAP_SINGLE)
      flag = .false.
    case default
      flag = .true.
    end select
  end function sf_channel_is_multi_mapping
```

Return true if there is any nontrivial mapping in any of the channels.

Note: we provide an explicit public function. gfortran 4.6.3 has problems with the alternative implementation as a type-bound procedure for an array base object.

```
<SF mappings: public>+≡
  public :: any_sf_channel_has_mapping

<SF mappings: procedures>+≡
  function any_sf_channel_has_mapping (channel) result (flag)
    type(sf_channel_t), dimension(:), intent(in) :: channel
    logical :: flag
    integer :: c
    flag = .false.
    do c = 1, size (channel)
      flag = flag .or. any (channel(c)%map_code /= SFMAP_NONE)
    end do
  end function any_sf_channel_has_mapping
```

Set a parameter index for an active multi mapping. We assume that the index array is allocated properly.

```
<SF mappings: sf channel: TBP>+≡
  procedure :: set_par_index => sf_channel_set_par_index

<SF mappings: procedures>+≡
  subroutine sf_channel_set_par_index (channel, j, i_par)
    class(sf_channel_t), intent(inout) :: channel
    integer, intent(in) :: j
    integer, intent(in) :: i_par
    call channel%multi_mapping%set_index (j, i_par)
  end subroutine sf_channel_set_par_index
```


15.4.16 Unit tests

```
<SF mappings: public>+≡
  public :: sf_mappings_test
<SF mappings: tests>≡
  subroutine sf_mappings_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    <SF mappings: execute tests>
  end subroutine sf_mappings_test
```

Check standard mapping

Probe the standard mapping of the unit square for different parameter values. Also calculates integrals. For a finite number of bins, they differ slightly from 1, but the result is well-defined because we are not using random points.

```
<SF mappings: execute tests>≡
  call test (sf_mappings_1, "sf_mappings_1", &
    "standard pair mapping", &
    u, results)
<SF mappings: tests>+≡
  subroutine sf_mappings_1 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(2) :: p

    write (u, "(A)")  "* Test output: sf_mappings_1"
    write (u, "(A)")  "* Purpose: probe standard mapping"
    write (u, "(A)")

    allocate (sf_s_mapping_t :: mapping)
    select type (mapping)
    type is (sf_s_mapping_t)
      call mapping%init ()
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)
    end select

    call mapping%write (u)

    write (u, *)
    write (u, "(A)")  "Probe at (0,0):"
    p = [0._default, 0._default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0.5,0.5):"
    p = [0.5_default, 0.5_default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0.1,0.5):"
```

```

p = [0.1_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.1,0.1):"
p = [0.1_default, 0.1_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)
allocate (sf_s_mapping_t :: mapping)
select type (mapping)
type is (sf_s_mapping_t)
    call mapping%init (power=2._default)
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
end select

write (u, *)
call mapping%write (u)

write (u, *)
write (u, "(A)") "Probe at (0,0):"
p = [0._default, 0._default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.5,0.5):"
p = [0.5_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.1,0.5):"
p = [0.1_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.1,0.1):"
p = [0.1_default, 0.1_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_1"

end subroutine sf_mappings_1

```

Channel entries

Construct channel entries and print them.

```
<SF mappings: execute tests>+≡
    call test (sf_mappings_2, "sf_mappings_2", &
               "structure-function mapping channels", &
               u, results)

<SF mappings: tests>+≡
    subroutine sf_mappings_2 (u)
        integer, intent(in) :: u
        type(sf_channel_t), dimension(:), allocatable :: channel
        integer :: c

        write (u, "(A)")  "* Test output: sf_mappings_2"
        write (u, "(A)")  "* Purpose: construct and display &
                           &mapping-channel objects"
        write (u, "(A)")

        call allocate_sf_channels (channel, n_channel = 6, n_strfun = 2)
        call channel(2)%activate_mapping ([1])
        call channel(3)%set_s_mapping ([1,2])
        call channel(4)%set_s_mapping ([1,2], power=2._default)
        call channel(5)%set_res_mapping ([1,2], m = 0.5_default, w = 0.1_default)
        call channel(6)%set_os_mapping ([1,2], m = 0.5_default)

        call channel(3)%set_par_index (1, 1)
        call channel(3)%set_par_index (2, 4)

        call channel(4)%set_par_index (1, 1)
        call channel(4)%set_par_index (2, 4)

        call channel(5)%set_par_index (1, 1)
        call channel(5)%set_par_index (2, 3)

        call channel(6)%set_par_index (1, 1)
        call channel(6)%set_par_index (2, 2)

        do c = 1, size (channel)
            write (u, "(I0,':')", advance="no") c
            call channel(c)%write (u)
        end do

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: sf_mappings_2"

    end subroutine sf_mappings_2
```

Check resonance mapping

Probe the resonance mapping of the unit square for different parameter values. Also calculates integrals. For a finite number of bins, they differ slightly from 1, but the result is well-defined because we are not using random points.

The resonance mass is at $1/2$ the energy, the width is $1/10$.

```

<SF mappings: execute tests>+≡
  call test (sf_mappings_3, "sf_mappings_3", &
    "resonant pair mapping", &
    u, results)
<SF mappings: tests>+≡
  subroutine sf_mappings_3 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(2) :: p

    write (u, "(A)")  "* Test output: sf_mappings_3"
    write (u, "(A)")  "*   Purpose: probe resonance pair mapping"
    write (u, "(A)")

    allocate (sf_res_mapping_t :: mapping)
    select type (mapping)
    type is (sf_res_mapping_t)
      call mapping%init (0.5_default, 0.1_default)
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)
    end select

    call mapping%write (u)

    write (u, *)
    write (u, "(A)")  "Probe at (0,0):"
    p = [0._default, 0._default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0.5,0.5):"
    p = [0.5_default, 0.5_default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0.1,0.5):"
    p = [0.1_default, 0.5_default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0.1,0.1):"
    p = [0.1_default, 0.1_default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Compute integral:"
    write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

    deallocate (mapping)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: sf_mappings_3"

```

```
end subroutine sf_mappings_3
```

Check on-shell mapping

Probe the on-shell mapping of the unit square for different parameter values. Also calculates integrals. In this case, the Jacobian is constant and given by $|\log m^2|$, so this is also the value of the integral. The factor results from the variable change in the $\delta(m^2 - x_1 x_2)$ which multiplies the cross section for the case at hand.

For the test, the (rescaled) resonance mass is set at 1/2 the energy.

```
<SF mappings: execute tests>+≡
  call test (sf_mappings_4, "sf_mappings_4", &
    "on-shell pair mapping", &
    u, results)
```

```
<SF mappings: tests>+≡
  subroutine sf_mappings_4 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(2) :: p

    write (u, "(A)")  "* Test output: sf_mappings_4"
    write (u, "(A)")  "* Purpose: probe on-shell pair mapping"
    write (u, "(A)")

    allocate (sf_os_mapping_t :: mapping)
    select type (mapping)
    type is (sf_os_mapping_t)
      call mapping%init (0.5_default)
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)
    end select

    call mapping%write (u)

    write (u, *)
    write (u, "(A)")  "Probe at (0,0):"
    p = [0._default, 0._default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0.5,0.5):"
    p = [0.5_default, 0.5_default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0,0.1):"
    p = [0._default, 0.1_default]
    call mapping%check (u, p, 1-p, "F7.5")

    write (u, *)
    write (u, "(A)")  "Probe at (0,1.0):"
    p = [0._default, 1.0_default]
```

```

call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_4"

end subroutine sf_mappings_4

```

Check endpoint mapping

Probe the endpoint mapping of the unit square for different parameter values. Also calculates integrals. For a finite number of bins, they differ slightly from 1, but the result is well-defined because we are not using random points.

```

<SF mappings: execute tests>+≡
call test (sf_mappings_5, "sf_mappings_5", &
  "endpoint pair mapping", &
  u, results)

<SF mappings: tests>+≡
subroutine sf_mappings_5 (u)
  integer, intent(in) :: u
  class(sf_mapping_t), allocatable :: mapping
  real(default), dimension(2) :: p

  write (u, "(A)") "* Test output: sf_mappings_5"
  write (u, "(A)") "* Purpose: probe endpoint pair mapping"
  write (u, "(A)")

  allocate (sf_ep_mapping_t :: mapping)
  select type (mapping)
  type is (sf_ep_mapping_t)
    call mapping%init ()
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
  end select

  call mapping%write (u)

  write (u, *)
  write (u, "(A)") "Probe at (0,0):"
  p = [0._default, 0._default]
  call mapping%check (u, p, 1-p, "F7.5")

  write (u, *)
  write (u, "(A)") "Probe at (0.5,0.5):"
  p = [0.5_default, 0.5_default]
  call mapping%check (u, p, 1-p, "F7.5")

```

```

write (u, *)
write (u, "(A)") "Probe at (0.1,0.5):"
p = [0.1_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.7,0.2):"
p = [0.7_default, 0.2_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_5"

end subroutine sf_mappings_5

```

Check endpoint resonant mapping

Probe the endpoint mapping with resonance. Also calculates integrals.

```

<SF mappings: execute tests>+≡
call test (sf_mappings_6, "sf_mappings_6", &
  "endpoint resonant mapping", &
  u, results)

<SF mappings: tests>+≡
subroutine sf_mappings_6 (u)
  integer, intent(in) :: u
  class(sf_mapping_t), allocatable :: mapping
  real(default), dimension(2) :: p

  write (u, "(A)") "* Test output: sf_mappings_6"
  write (u, "(A)") "* Purpose: probe endpoint resonant mapping"
  write (u, "(A)")

  allocate (sf_epr_mapping_t :: mapping)
  select type (mapping)
  type is (sf_epr_mapping_t)
    call mapping%init (a = 1._default, m = 0.5_default, w = 0.1_default)
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
  end select

  call mapping%write (u)

  write (u, *)
  write (u, "(A)") "Probe at (0,0):"
  p = [0._default, 0._default]
  call mapping%check (u, p, 1-p, "F7.5")

```

```

write (u, *)
write (u, "(A)") "Probe at (0.5,0.5):"
p = [0.5_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.1,0.5):"
p = [0.1_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.7,0.2):"
p = [0.7_default, 0.2_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Same mapping without resonance:"
write (u, "(A)")

allocate (sf_epr_mapping_t :: mapping)
select type (mapping)
type is (sf_epr_mapping_t)
    call mapping%init (a = 1._default)
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
end select

call mapping%write (u)

write (u, *)
write (u, "(A)") "Probe at (0,0):"
p = [0._default, 0._default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.5,0.5):"
p = [0.5_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.1,0.5):"
p = [0.1_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.7,0.2):"
p = [0.7_default, 0.2_default]

```



```

call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_6"

end subroutine sf_mappings_6

```

Check endpoint on-shell mapping

Probe the endpoint mapping with an on-shell particle. Also calculates integrals.

```

<SF mappings: execute tests>+≡
call test (sf_mappings_7, "sf_mappings_7", &
  "endpoint on-shell mapping", &
  u, results)

<SF mappings: tests>+≡
subroutine sf_mappings_7 (u)
  integer, intent(in) :: u
  class(sf_mapping_t), allocatable :: mapping
  real(default), dimension(2) :: p

  write (u, "(A)") "* Test output: sf_mappings_7"
  write (u, "(A)") "* Purpose: probe endpoint on-shell mapping"
  write (u, "(A)")

  allocate (sf_epo_mapping_t :: mapping)
  select type (mapping)
  type is (sf_epo_mapping_t)
    call mapping%init (a = 1._default, m = 0.5_default)
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
  end select

  call mapping%write(u)

  write (u, *)
  write (u, "(A)") "Probe at (0,0):"
  p = [0._default, 0._default]
  call mapping%check (u, p, 1-p, "F7.5")

  write (u, *)
  write (u, "(A)") "Probe at (0.5,0.5):"
  p = [0.5_default, 0.5_default]
  call mapping%check (u, p, 1-p, "F7.5")

  write (u, *)
  write (u, "(A)") "Probe at (0.1,0.5):"

```

```

p = [0.1_default, 0.5_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Probe at (0.7,0.2):"
p = [0.7_default, 0.2_default]
call mapping%check (u, p, 1-p, "F7.5")

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_7"

end subroutine sf_mappings_7

```

Check power mapping

Probe the power mapping of the unit square for different parameter values. Also calculates integrals. For a finite number of bins, they differ slightly from 1, but the result is well-defined because we are not using random points.

```

<SF mappings: execute tests> +=
  call test (sf_mappings_8, "sf_mappings_8", &
    "power pair mapping", &
    u, results)

<SF mappings: tests> +=
  subroutine sf_mappings_8 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(2) :: p, pb

    write (u, "(A)") "* Test output: sf_mappings_8"
    write (u, "(A)") "* Purpose: probe power pair mapping"
    write (u, "(A)")

    allocate (sf_ip_mapping_t :: mapping)
    select type (mapping)
    type is (sf_ip_mapping_t)
      call mapping%init (eps = 0.1_default)
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)
    end select

    call mapping%write (u)

    write (u, *)
    write (u, "(A)") "Probe at (0,0.5):"
    p = [0._default, 0.5_default]
    pb= [1._default, 0.5_default]

```

```

call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.5,0.5):"
p = [0.5_default, 0.5_default]
pb= [0.5_default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.9,0.5):"
p = [0.9_default, 0.5_default]
pb= [0.1_default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.7,0.2):"
p = [0.7_default, 0.2_default]
pb= [0.3_default, 0.8_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.7,0.8):"
p = [0.7_default, 0.8_default]
pb= [0.3_default, 0.2_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.99,0.02):"
p = [0.99_default, 0.02_default]
pb= [0.01_default, 0.98_default]
call mapping%check (u, p, pb, FMT_14, FMT_12)

write (u, *)
write (u, "(A)") "Probe at (0.99,0.98):"
p = [0.99_default, 0.98_default]
pb= [0.01_default, 0.02_default]
call mapping%check (u, p, pb, FMT_14, FMT_12)

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_8"

end subroutine sf_mappings_8

```

Check resonant power mapping

Probe the power mapping of the unit square, adapted for an s-channel resonance, for different parameter values. Also calculates integrals. For a finite number of

bins, they differ slightly from 1, but the result is well-defined because we are not using random points.

```

<SF mappings: execute tests>+≡
  call test (sf_mappings_9, "sf_mappings_9", &
    "power resonance mapping", &
    u, results)

<SF mappings: tests>+≡
  subroutine sf_mappings_9 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(2) :: p, pb

    write (u, "(A)")  "* Test output: sf_mappings_9"
    write (u, "(A)")  "* Purpose: probe power resonant pair mapping"
    write (u, "(A)")

    allocate (sf_ipr_mapping_t :: mapping)
    select type (mapping)
    type is (sf_ipr_mapping_t)
      call mapping%init (eps = 0.1_default, m = 0.5_default, w = 0.1_default)
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)
    end select

    call mapping%write (u)

    write (u, *)
    write (u, "(A)")  "Probe at (0,0.5):"
    p = [0._default, 0.5_default]
    pb= [1._default, 0.5_default]
    call mapping%check (u, p, pb, FMT_16)

    write (u, *)
    write (u, "(A)")  "Probe at (0.5,0.5):"
    p = [0.5_default, 0.5_default]
    pb= [0.5_default, 0.5_default]
    call mapping%check (u, p, pb, FMT_16)

    write (u, *)
    write (u, "(A)")  "Probe at (0.9,0.5):"
    p = [0.9_default, 0.5_default]
    pb= [0.1_default, 0.5_default]
    call mapping%check (u, p, pb, FMT_16)

    write (u, *)
    write (u, "(A)")  "Probe at (0.7,0.2):"
    p = [0.7_default, 0.2_default]
    pb= [0.3_default, 0.8_default]
    call mapping%check (u, p, pb, FMT_16)

    write (u, *)
    write (u, "(A)")  "Probe at (0.7,0.8):"
    p = [0.7_default, 0.8_default]

```

```

pb= [0.3_default, 0.2_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.9999,0.02):"
p = [0.9999_default, 0.02_default]
pb= [0.0001_default, 0.98_default]
call mapping%check (u, p, pb, FMT_15, FMT_12)

write (u, *)
write (u, "(A)") "Probe at (0.9999,0.98):"
p = [0.9999_default, 0.98_default]
pb= [0.0001_default, 0.02_default]
call mapping%check (u, p, pb, FMT_15, FMT_12)

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Same mapping without resonance:"
write (u, "(A)")

allocate (sf_ipr_mapping_t :: mapping)
select type (mapping)
type is (sf_ipr_mapping_t)
  call mapping%init (eps = 0.1_default)
  call mapping%set_index (1, 1)
  call mapping%set_index (2, 2)
end select

call mapping%write (u)

write (u, *)
write (u, "(A)") "Probe at (0,0.5):"
p = [0._default, 0.5_default]
pb= [1._default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.5,0.5):"
p = [0.5_default, 0.5_default]
pb= [0.5_default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.9,0.5):"
p = [0.9_default, 0.5_default]
pb= [0.1_default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)

```

```

write (u, "(A)") "Probe at (0.7,0.2):"
p = [0.7_default, 0.2_default]
pb= [0.3_default, 0.8_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.7,0.8):"
p = [0.7_default, 0.8_default]
pb= [0.3_default, 0.2_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_9"

end subroutine sf_mappings_9

```

Check on-shell power mapping

Probe the power mapping of the unit square, adapted for single-particle production, for different parameter values. Also calculates integrals. For a finite number of bins, they differ slightly from 1, but the result is well-defined because we are not using random points.

```

<SF mappings: execute tests>+=
  call test (sf_mappings_10, "sf_mappings_10", &
    "power on-shell mapping", &
    u, results)

<SF mappings: tests>+=
  subroutine sf_mappings_10 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(2) :: p, pb

    write (u, "(A)") "* Test output: sf_mappings_10"
    write (u, "(A)") "* Purpose: probe power on-shell mapping"
    write (u, "(A)")

    allocate (sf_ipo_mapping_t :: mapping)
    select type (mapping)
    type is (sf_ipo_mapping_t)
      call mapping%init (eps = 0.1_default, m = 0.5_default)
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)
    end select

    call mapping%write (u)

```

```

write (u, *)
write (u, "(A)") "Probe at (0,0.5):"
p = [0._default, 0.5_default]
pb= [1._default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0,0.02):"
p = [0._default, 0.02_default]
pb= [1._default, 0.98_default]
call mapping%check (u, p, pb, FMT_15, FMT_12)

write (u, *)
write (u, "(A)") "Probe at (0,0.98):"
p = [0._default, 0.98_default]
pb= [1._default, 0.02_default]
call mapping%check (u, p, pb, FMT_15, FMT_12)

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "** Test output end: sf_mappings_10"

end subroutine sf_mappings_10

```

Check combined endpoint-power mapping

Probe the mapping for the beamstrahlung/ISR combination.

```

<SF mappings: execute tests>+=
  call test (sf_mappings_11, "sf_mappings_11", &
    "endpoint/power combined mapping", &
    u, results)

<SF mappings: tests>+=
  subroutine sf_mappings_11 (u)
    integer, intent(in) :: u
    class(sf_mapping_t), allocatable :: mapping
    real(default), dimension(4) :: p, pb

    write (u, "(A)") "** Test output: sf_mappings_11"
    write (u, "(A)") "** Purpose: probe power pair mapping"
    write (u, "(A)")

    allocate (sf_ei_mapping_t :: mapping)
    select type (mapping)
    type is (sf_ei_mapping_t)
      call mapping%init (eps = 0.1_default)
      call mapping%set_index (1, 1)
      call mapping%set_index (2, 2)

```

```

        call mapping%set_index (3, 3)
        call mapping%set_index (4, 4)
    end select

    call mapping%write (u)

    write (u, *)
    write (u, "(A)") "Probe at (0.5, 0.5, 0.5, 0.5):"
    p = [0.5_default, 0.5_default, 0.5_default, 0.5_default]
    pb= [0.5_default, 0.5_default, 0.5_default, 0.5_default]
    call mapping%check (u, p, pb, FMT_16)

    write (u, *)
    write (u, "(A)") "Probe at (0.7, 0.2, 0.4, 0.8):"
    p = [0.7_default, 0.2_default, 0.4_default, 0.8_default]
    pb= [0.3_default, 0.8_default, 0.6_default, 0.2_default]
    call mapping%check (u, p, pb, FMT_16)

    write (u, *)
    write (u, "(A)") "Probe at (0.9, 0.06, 0.95, 0.1):"
    p = [0.9_default, 0.06_default, 0.95_default, 0.1_default]
    pb= [0.1_default, 0.94_default, 0.05_default, 0.9_default]
    call mapping%check (u, p, pb, FMT_13, FMT_12)

    write (u, *)
    write (u, "(A)") "Compute integral:"
    write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

    deallocate (mapping)

    write (u, "(A)")
    write (u, "(A)") "* Test output end: sf_mappings_11"

end subroutine sf_mappings_11

```

Check resonant endpoint-power mapping

Probe the mapping for the beamstrahlung/ISR combination.

```

<SF mappings: execute tests>+=
    call test (sf_mappings_12, "sf_mappings_12", &
        "endpoint/power resonant combined mapping", &
        u, results)

<SF mappings: tests>+=
    subroutine sf_mappings_12 (u)
        integer, intent(in) :: u
        class(sf_mapping_t), allocatable :: mapping
        real(default), dimension(4) :: p, pb

        write (u, "(A)") "* Test output: sf_mappings_12"
        write (u, "(A)") "* Purpose: probe resonant combined mapping"
        write (u, "(A)")
    end subroutine sf_mappings_12

```



```

allocate (sf_eir_mapping_t :: mapping)
select type (mapping)
type is (sf_eir_mapping_t)
    call mapping%init (a = 1._default, &
        eps = 0.1_default, m = 0.5_default, w = 0.1_default)
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
    call mapping%set_index (3, 3)
    call mapping%set_index (4, 4)
end select

call mapping%write (u)

write (u, *)
write (u, "(A)") "Probe at (0.5, 0.5, 0.5, 0.5):"
p = [0.5_default, 0.5_default, 0.5_default, 0.5_default]
pb= [0.5_default, 0.5_default, 0.5_default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.7, 0.2, 0.4, 0.8):"
p = [0.7_default, 0.2_default, 0.4_default, 0.8_default]
pb= [0.3_default, 0.8_default, 0.6_default, 0.2_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)") "Probe at (0.9, 0.06, 0.95, 0.1):"
p = [0.9_default, 0.06_default, 0.95_default, 0.1_default]
pb= [0.1_default, 0.94_default, 0.05_default, 0.9_default]
call mapping%check (u, p, pb, FMT_15, FMT_12)

write (u, *)
write (u, "(A)") "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)") "* Test output end: sf_mappings_12"

end subroutine sf_mappings_12

```

Check on-shell endpoint-power mapping

Probe the mapping for the beamstrahlung/ISR combination.

```

<SF mappings: execute tests>+≡
    call test (sf_mappings_13, "sf_mappings_13", &
        "endpoint/power on-shell combined mapping", &
        u, results)

<SF mappings: tests>+≡
    subroutine sf_mappings_13 (u)
        integer, intent(in) :: u

```

```

class(sf_mapping_t), allocatable :: mapping
real(default), dimension(4) :: p, pb

write (u, "(A)")  "* Test output: sf_mappings_13"
write (u, "(A)")  "*   Purpose: probe on-shell combined mapping"
write (u, "(A)")

allocate (sf_eio_mapping_t :: mapping)
select type (mapping)
type is (sf_eio_mapping_t)
    call mapping%init (a = 1._default, eps = 0.1_default, m = 0.5_default)
    call mapping%set_index (1, 1)
    call mapping%set_index (2, 2)
    call mapping%set_index (3, 3)
    call mapping%set_index (4, 4)
end select

call mapping%write (u)

write (u, *)
write (u, "(A)")  "Probe at (0.5, 0.5, 0.5, 0.5):"
p = [0.5_default, 0.5_default, 0.5_default, 0.5_default]
pb= [0.5_default, 0.5_default, 0.5_default, 0.5_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)")  "Probe at (0.7, 0.2, 0.4, 0.8):"
p = [0.7_default, 0.2_default, 0.4_default, 0.8_default]
pb= [0.3_default, 0.8_default, 0.6_default, 0.2_default]
call mapping%check (u, p, pb, FMT_16)

write (u, *)
write (u, "(A)")  "Probe at (0.9, 0.06, 0.95, 0.1):"
p = [0.9_default, 0.06_default, 0.95_default, 0.1_default]
pb= [0.1_default, 0.94_default, 0.05_default, 0.9_default]
call mapping%check (u, p, pb, FMT_14, FMT_12)

write (u, *)
write (u, "(A)")  "Compute integral:"
write (u, "(3x,A,1x,F7.5)") "I =", mapping%integral (100000)

deallocate (mapping)

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_mappings_13"

end subroutine sf_mappings_13

```

Check rescaling

Check the rescaling factor in on-shell basic mapping.

<SF mappings: execute tests>+≡

```

call test (sf_mappings_14, "sf_mappings_14", &
  "rescaled on-shell mapping", &
  u, results)
<SF mappings: tests>+≡
subroutine sf_mappings_14 (u)
  integer, intent(in) :: u
  real(default), dimension(2) :: p, r
  real(default) :: f, x_free, m2

  write (u, "(A)")  "* Test output: sf_mappings_14"
  write (u, "(A)")  "* Purpose: probe rescaling in os mapping"
  write (u, "(A)")

  p = [0.1_default, 0.2_default]
  x_free = 0.9_default
  m2 = 0.5_default

  call map_on_shell (r, f, p, -log (m2), x_free)

  write (u, "(A,9(1x," // FMT_14 // ")") "p =", p
  write (u, "(A,9(1x," // FMT_14 // ")") "r =", r
  write (u, "(A,9(1x," // FMT_14 // ")") "f =", f
  write (u, "(A,9(1x," // FMT_14 // ")") "*r=", x_free * product (r)

  write (u, *)

  call map_on_shell_inverse (r, f, p, -log (m2), x_free)

  write (u, "(A,9(1x," // FMT_14 // ")") "p =", p
  write (u, "(A,9(1x," // FMT_14 // ")") "r =", r
  write (u, "(A,9(1x," // FMT_14 // ")") "f =", f
  write (u, "(A,9(1x," // FMT_14 // ")") "*r=", x_free * product (r)

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: sf_mappings_14"

end subroutine sf_mappings_14

```

15.5 Structure function base

```

<sf_base.f90>≡
<File header>

module sf_base

  <Use kinds>
  <Use strings>
  use io_units
  use format_utils, only: write_separator
  use format_defs, only: FMT_17, FMT_19
  use unit_tests

```

```

    use diagnostics
    use lorentz
    use model_data
    use flavors
    use colors
    use helicities
    use quantum_numbers
    use state_matrices
    use interactions
    use evaluators
    use pdg_arrays
    use particles
    use beams
    use sf_aux
    use sf_mappings

```

⟨Standard module head⟩

⟨SF base: public⟩

⟨SF base: parameters⟩

⟨SF base: types⟩

⟨SF base: interfaces⟩

⟨SF base: test types⟩

contains

⟨SF base: procedures⟩

⟨SF base: tests⟩

end module sf_base

15.5.1 Abstract structure-function data type

This type should hold all configuration data for a specific type of structure function. The base object is empty; the implementations will fill it.

⟨SF base: public⟩≡

```
public :: sf_data_t
```

⟨SF base: types⟩≡

```
type, abstract :: sf_data_t
```

```
contains
```

⟨SF base: sf data: TBP⟩

```
end type sf_data_t
```

Output.

⟨SF base: sf data: TBP⟩≡

```
procedure (sf_data_write), deferred :: write
```

```

<SF base: interfaces>+=
  abstract interface
    subroutine sf_data_write (data, unit, verbose)
      import
      class(sf_data_t), intent(in) :: data
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: verbose
    end subroutine sf_data_write
  end interface

```

Return true if this structure function is in generator mode. In that case, all parameters are free, otherwise bound. (We do not support mixed cases.) Default is: no generator.

```

<SF base: sf data: TBP>+=
  procedure :: is_generator => sf_data_is_generator

<SF base: procedures>+=
  function sf_data_is_generator (data) result (flag)
    class(sf_data_t), intent(in) :: data
    logical :: flag
    flag = .false.
  end function sf_data_is_generator

```

Return the number of input parameters that determine the structure function.

```

<SF base: sf data: TBP>+=
  procedure (sf_data_get_int), deferred :: get_n_par

<SF base: interfaces>+=
  abstract interface
    function sf_data_get_int (data) result (n)
      import
      class(sf_data_t), intent(in) :: data
      integer :: n
    end function sf_data_get_int
  end interface

```

Return the outgoing particle PDG codes for the current setup. The codes can be an array of particles, for each beam.

```

<SF base: sf data: TBP>+=
  procedure (sf_data_get_pdg_out), deferred :: get_pdg_out

<SF base: interfaces>+=
  abstract interface
    subroutine sf_data_get_pdg_out (data, pdg_out)
      import
      class(sf_data_t), intent(in) :: data
      type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
    end subroutine sf_data_get_pdg_out
  end interface

```

Allocate a matching structure function interaction object and properly initialize it.

```

<SF base: sf data: TBP>+=
  procedure (sf_data_allocate_sf_int), deferred :: allocate_sf_int

```

```

<SF base: interfaces>+=
  abstract interface
    subroutine sf_data_allocate_sf_int (data, sf_int)
      import
      class(sf_data_t), intent(in) :: data
      class(sf_int_t), intent(inout), allocatable :: sf_int
    end subroutine sf_data_allocate_sf_int
  end interface

```

Return the PDF set index, if applicable. We implement a default method which returns zero. The PDF (builtin and LHA) implementations will override this.

```

<SF base: sf data: TBP>+=
  procedure :: get_pdf_set => sf_data_get_pdf_set

<SF base: procedures>+=
  function sf_data_get_pdf_set (data) result (pdf_set)
    class(sf_data_t), intent(in) :: data
    integer :: pdf_set
    pdf_set = 0
  end function sf_data_get_pdf_set

```

15.5.2 Structure-function chain configuration

This is the data type that the `processes` module uses for setting up its structure-function chain. For each structure function described by the beam data, there is an entry. The `i` array indicates the beam(s) to which this structure function applies, and the `data` object contains the actual configuration data.

```

<SF base: public>+=
  public :: sf_config_t

<SF base: types>+=
  type :: sf_config_t
    integer, dimension(:), allocatable :: i
    class(sf_data_t), allocatable :: data
  contains
    <SF base: sf config: TBP>
  end type sf_config_t

```

Output:

```

<SF base: sf config: TBP>=
  procedure :: write => sf_config_write

<SF base: procedures>+=
  subroutine sf_config_write (object, unit)
    class(sf_config_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    if (allocated (object%i)) then
      write (u, "(1x,A,2(1x,I0))") "Structure-function configuration: &
        &beam(s)", object%i
      if (allocated (object%data)) call object%data%write (u)
    end if
  end subroutine sf_config_write

```

```

    else
      write (u, "(1x,A)") "Structure-function configuration: [undefined]"
    end if
  end subroutine sf_config_write

```

Initialize.

```

<SF base: sf config: TBP>+≡
  procedure :: init => sf_config_init

<SF base: procedures>+≡
  subroutine sf_config_init (sf_config, i_beam, sf_data)
    class(sf_config_t), intent(out) :: sf_config
    integer, dimension(:), intent(in) :: i_beam
    class(sf_data_t), intent(in) :: sf_data
    allocate (sf_config%i (size (i_beam)), source = i_beam)
    allocate (sf_config%data, source = sf_data)
  end subroutine sf_config_init

```

Return the PDF set, if any.

```

<SF base: sf config: TBP>+≡
  procedure :: get_pdf_set => sf_config_get_pdf_set

<SF base: procedures>+≡
  function sf_config_get_pdf_set (sf_config) result (pdf_set)
    class(sf_config_t), intent(in) :: sf_config
    integer :: pdf_set
    pdf_set = sf_config%data%get_pdf_set ()
  end function sf_config_get_pdf_set

```

15.5.3 Structure-function instance

The `sf_int_t` data type contains an `interaction_t` object (it is an extension of this type) and a pointer to the `sf_data_t` configuration data. This interaction, or copies of it, is used to implement structure-function kinematics and dynamics in the context of process evaluation.

The status code `status` tells whether the interaction is undefined, has defined kinematics (but matrix elements invalid), or is completely defined. There is also a status code for failure. The implementation is responsible for updating the status.

The entries `mi2`, `mr2`, and `mo2` hold the squared invariant masses of the incoming, radiated, and outgoing particle, respectively. They are supposed to be set upon initialization, but could also be varied event by event.

If the radiated or outgoing mass is nonzero, we may need to apply an on-shell projection. The projection mode is stored as `on_shell_mode`.

The array `beam_index` is the list of beams on which this structure function applies (1, 2, or both). The arrays `incoming`, `radiated`, and `outgoing` contain the indices of the respective particle sets within the interaction, for convenient lookup. The array `par_index` indicates the MC input parameters that this entry will use up in the structure-function chain. The first parameter (or the first two, for a spectrum) in this array determines the momentum fraction and is thus subject to global mappings.

In the abstract base type, we do not implement the data pointer. This allows us to restrict its type in the implementations.

```

<SF base: public>+≡
    public :: sf_int_t

<SF base: types>+≡
    type, abstract, extends (interaction_t) :: sf_int_t
        integer :: status = SF_UNDEFINED
        real(default), dimension(:), allocatable :: mi2
        real(default), dimension(:), allocatable :: mr2
        real(default), dimension(:), allocatable :: mo2
        integer :: on_shell_mode = KEEP_ENERGY
        logical :: qmin_defined = .false.
        logical :: qmax_defined = .false.
        real(default), dimension(:), allocatable :: qmin
        real(default), dimension(:), allocatable :: qmax
        integer, dimension(:), allocatable :: beam_index
        integer, dimension(:), allocatable :: incoming
        integer, dimension(:), allocatable :: radiated
        integer, dimension(:), allocatable :: outgoing
        integer, dimension(:), allocatable :: par_index
        integer, dimension(:), allocatable :: par_primary
    contains
        <SF base: sf_int: TBP>
    end type sf_int_t

```

Status codes. The codes that refer to links, masks, and connections, apply to structure-function chains only.

The status codes are public.

```

<SF base: parameters>≡
    integer, parameter, public :: SF_UNDEFINED = 0
    integer, parameter, public :: SF_INITIAL = 1
    integer, parameter, public :: SF_DONE_LINKS = 2
    integer, parameter, public :: SF_FAILED_MASK = 3
    integer, parameter, public :: SF_DONE_MASK = 4
    integer, parameter, public :: SF_FAILED_CONNECTIONS = 5
    integer, parameter, public :: SF_DONE_CONNECTIONS = 6
    integer, parameter, public :: SF_SEED_KINEMATICS = 10
    integer, parameter, public :: SF_FAILED_KINEMATICS = 11
    integer, parameter, public :: SF_DONE_KINEMATICS = 12
    integer, parameter, public :: SF_FAILED_EVALUATION = 13
    integer, parameter, public :: SF_EVALUATED = 20

```

Write a string version of the status code:

```

<SF base: procedures>+≡
    subroutine write_sf_status (status, u)
        integer, intent(in) :: status
        integer, intent(in) :: u
        select case (status)
        case (SF_UNDEFINED)
            write (u, "(1x,'[',A,']')") "undefined"
        case (SF_INITIAL)
            write (u, "(1x,'[',A,']')") "initialized"

```



```

case (SF_DONE_LINKS)
  write (u, "(1x,['',A,'])") "links set"
case (SF_FAILED_MASK)
  write (u, "(1x,['',A,'])") "mask mismatch"
case (SF_DONE_MASK)
  write (u, "(1x,['',A,'])") "mask set"
case (SF_FAILED_CONNECTIONS)
  write (u, "(1x,['',A,'])") "connections failed"
case (SF_DONE_CONNECTIONS)
  write (u, "(1x,['',A,'])") "connections set"
case (SF_SEED_KINEMATICS)
  write (u, "(1x,['',A,'])") "incoming momenta set"
case (SF_FAILED_KINEMATICS)
  write (u, "(1x,['',A,'])") "kinematics failed"
case (SF_DONE_KINEMATICS)
  write (u, "(1x,['',A,'])") "kinematics set"
case (SF_FAILED_EVALUATION)
  write (u, "(1x,['',A,'])") "evaluation failed"
case (SF_EVALUATED)
  write (u, "(1x,['',A,'])") "evaluated"
end select
end subroutine write_sf_status

```

This is the basic output routine. Display status and interaction.

(SF base: sf_int: TBP)≡

```
procedure :: base_write => sf_int_base_write
```

(SF base: procedures)+≡

```

subroutine sf_int_base_write (object, unit, testflag)
  class(sf_int_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)", advance="no") "SF instance:"
  call write_sf_status (object%status, u)
  if (allocated (object%beam_index)) &
    write (u, "(3x,A,2(1x,I0))") "beam      =", object%beam_index
  if (allocated (object%incoming)) &
    write (u, "(3x,A,2(1x,I0))") "incoming =", object%incoming
  if (allocated (object%radiated)) &
    write (u, "(3x,A,2(1x,I0))") "radiated  =", object%radiated
  if (allocated (object%outgoing)) &
    write (u, "(3x,A,2(1x,I0))") "outgoing  =", object%outgoing
  if (allocated (object%par_index)) &
    write (u, "(3x,A,2(1x,I0))") "parameter =", object%par_index
  if (object%qmin_defined) &
    write (u, "(3x,A,1x," // FMT_19 // ")") "q_min     =", object%qmin
  if (object%qmax_defined) &
    write (u, "(3x,A,1x," // FMT_19 // ")") "q_max     =", object%qmax
  call object%interaction_t%basic_write (u, testflag = testflag)
end subroutine sf_int_base_write

```

The type string identifies the structure function class, and possibly more details

about the structure function.

```

<SF base: sf_int: TBP>+=
  procedure (sf_int_type_string), deferred :: type_string

<SF base: interfaces>+=
  abstract interface
    function sf_int_type_string (object) result (string)
      import
      class(sf_int_t), intent(in) :: object
      type(string_t) :: string
    end function sf_int_type_string
  end interface

```

Output of the concrete object. We should not forget to call the output routine for the base type.

```

<SF base: sf_int: TBP>+=
  procedure (sf_int_write), deferred :: write

<SF base: interfaces>+=
  abstract interface
    subroutine sf_int_write (object, unit, testflag)
      import
      class(sf_int_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: testflag
    end subroutine sf_int_write
  end interface

```

Basic initialization: set the invariant masses for the particles and initialize the interaction. The caller should then add states to the interaction and freeze it.

The dimension of the mask should be equal to the sum of the dimensions of the mass-squared arrays, which determine incoming, radiated, and outgoing particles, respectively.

Optionally, we can define minimum and maximum values for the momentum transfer to the outgoing particle(s). If all masses are zero, this is actually required for non-collinear splitting.

```

<SF base: sf_int: TBP>+=
  procedure :: base_init => sf_int_base_init

<SF base: procedures>+=
  subroutine sf_int_base_init &
    (sf_int, mask, mi2, mr2, mo2, qmin, qmax, hel_lock)
    class(sf_int_t), intent(out) :: sf_int
    type (quantum_numbers_mask_t), dimension(:), intent(in) :: mask
    real(default), dimension(:), intent(in) :: mi2, mr2, mo2
    real(default), dimension(:), intent(in), optional :: qmin, qmax
    integer, dimension(:), intent(in), optional :: hel_lock
    allocate (sf_int%mi2 (size (mi2)))
    sf_int%mi2 = mi2
    allocate (sf_int%mr2 (size (mr2)))
    sf_int%mr2 = mr2
    allocate (sf_int%mo2 (size (mo2)))
    sf_int%mo2 = mo2
  end subroutine

```

```

    if (present (qmin)) then
        sf_int%qmin_defined = .true.
        allocate (sf_int%qmin (size (qmin)))
        sf_int%qmin = qmin
    end if
    if (present (qmax)) then
        sf_int%qmax_defined = .true.
        allocate (sf_int%qmax (size (qmax)))
        sf_int%qmax = qmax
    end if
    call sf_int%interaction_t%basic_init &
        (size (mi2), 0, size (mr2) + size (mo2), &
         mask = mask, hel_lock = hel_lock, set_relations = .true.)
end subroutine sf_int_base_init

```

Set the indices of the incoming, radiated, and outgoing particles, respectively.

```

⟨SF base: sf_int: TBP⟩+=
    procedure :: set_incoming => sf_int_set_incoming
    procedure :: set_radiated => sf_int_set_radiated
    procedure :: set_outgoing => sf_int_set_outgoing

⟨SF base: procedures⟩+=
    subroutine sf_int_set_incoming (sf_int, incoming)
        class(sf_int_t), intent(inout) :: sf_int
        integer, dimension(:), intent(in) :: incoming
        allocate (sf_int%incoming (size (incoming)))
        sf_int%incoming = incoming
    end subroutine sf_int_set_incoming

    subroutine sf_int_set_radiated (sf_int, radiated)
        class(sf_int_t), intent(inout) :: sf_int
        integer, dimension(:), intent(in) :: radiated
        allocate (sf_int%radiated (size (radiated)))
        sf_int%radiated = radiated
    end subroutine sf_int_set_radiated

    subroutine sf_int_set_outgoing (sf_int, outgoing)
        class(sf_int_t), intent(inout) :: sf_int
        integer, dimension(:), intent(in) :: outgoing
        allocate (sf_int%outgoing (size (outgoing)))
        sf_int%outgoing = outgoing
    end subroutine sf_int_set_outgoing

```

Initialization. This proceeds via an abstract data object, which for the actual implementation should have the matching concrete type. Since all implementations have the same signature, we can prepare a deferred procedure. The data object will become the target of a corresponding pointer within the `sf_int_t` implementation.

This should call the previous procedure.

```

⟨SF base: sf_int: TBP⟩+=
    procedure (sf_int_init), deferred :: init

```

```

<SF base: interfaces>+≡
  abstract interface
    subroutine sf_int_init (sf_int, data)
      import
      class(sf_int_t), intent(out) :: sf_int
      class(sf_data_t), intent(in), target :: data
    end subroutine sf_int_init
  end interface

```

Complete initialization. This routine contains initializations that can only be performed after the interaction object got its final shape, i.e., redundant helicities have been eliminated by matching with beams and process.

The default implementation does nothing.

```

<SF base: sf_int: TBP>+≡
  procedure :: setup_constants => sf_int_setup_constants

<SF base: procedures>+≡
  subroutine sf_int_setup_constants (sf_int)
    class(sf_int_t), intent(inout) :: sf_int
  end subroutine sf_int_setup_constants

```

Set beam indices, i.e., the beam(s) on which this structure function applies.

```

<SF base: sf_int: TBP>+≡
  procedure :: set_beam_index => sf_int_set_beam_index

<SF base: procedures>+≡
  subroutine sf_int_set_beam_index (sf_int, beam_index)
    class(sf_int_t), intent(inout) :: sf_int
    integer, dimension(:), intent(in) :: beam_index
    allocate (sf_int%beam_index (size (beam_index)))
    sf_int%beam_index = beam_index
  end subroutine sf_int_set_beam_index

```

Set parameter indices, indicating which MC input parameters are to be used for evaluating this structure function.

```

<SF base: sf_int: TBP>+≡
  procedure :: set_par_index => sf_int_set_par_index

<SF base: procedures>+≡
  subroutine sf_int_set_par_index (sf_int, par_index)
    class(sf_int_t), intent(inout) :: sf_int
    integer, dimension(:), intent(in) :: par_index
    allocate (sf_int%par_index (size (par_index)))
    sf_int%par_index = par_index
  end subroutine sf_int_set_par_index

```

Initialize the structure-function kinematics, setting incoming momenta. We assume that array shapes match.

Three versions. The first version relies on the momenta being linked to another interaction. The second version sets the momenta explicitly. In the third version, we first compute momenta for the specified energies and store those.

```

<SF base: sf_int: TBP>+≡

```

```

generic :: seed_kinematics => sf_int_receive_momenta
generic :: seed_kinematics => sf_int_seed_momenta
generic :: seed_kinematics => sf_int_seed_energies
procedure :: sf_int_receive_momenta
procedure :: sf_int_seed_momenta
procedure :: sf_int_seed_energies
<SF base: procedures>+≡
subroutine sf_int_receive_momenta (sf_int)
  class(sf_int_t), intent(inout) :: sf_int
  if (sf_int%status >= SF_INITIAL) then
    call sf_int%receive_momenta ()
    sf_int%status = SF_SEED_KINEMATICS
  end if
end subroutine sf_int_receive_momenta

subroutine sf_int_seed_momenta (sf_int, k)
  class(sf_int_t), intent(inout) :: sf_int
  type(vector4_t), dimension(:), intent(in) :: k
  if (sf_int%status >= SF_INITIAL) then
    call sf_int%set_momenta (k, outgoing=.false.)
    sf_int%status = SF_SEED_KINEMATICS
  end if
end subroutine sf_int_seed_momenta

subroutine sf_int_seed_energies (sf_int, E)
  class(sf_int_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(in) :: E
  type(vector4_t), dimension(:), allocatable :: k
  integer :: j
  if (sf_int%status >= SF_INITIAL) then
    allocate (k (size (E)))
    if (all (E**2 >= sf_int%mi2)) then
      do j = 1, size (E)
        k(j) = vector4_moving (E(j), &
          (3-2*j) * sqrt (E(j)**2 - sf_int%mi2(j)), 3)
      end do
      call sf_int%seed_kinematics (k)
    end if
  end if
end subroutine sf_int_seed_energies

```

Tell if in generator mode. By default, this is false. To be overridden where appropriate; we may refer to the `is_generator` method of the `data` component in the concrete type.

```

<SF base: sf_int: TBP>+≡
  procedure :: is_generator => sf_int_is_generator
<SF base: procedures>+≡
function sf_int_is_generator (sf_int) result (flag)
  class(sf_int_t), intent(in) :: sf_int
  logical :: flag
  flag = .false.
end function sf_int_is_generator

```

Generate free parameters **r**. Parameters are free if they do not correspond to integration parameters (i.e., are bound), but are generated by the structure function object itself. By default, all parameters are bound, and the output values of this procedure will be discarded. With free parameters, we have to override this procedure.

The value **x_free** is the renormalization factor of the total energy that corresponds to the free parameters. If there are no free parameters, the procedure will not change its value, which starts as unity. Otherwise, the fraction is typically decreased, but may also be increased in some cases.

```

(SF base: sf_int: TBP)+≡
  procedure :: generate_free => sf_int_generate_free

(SF base: procedures)+≡
  subroutine sf_int_generate_free (sf_int, r, rb, x_free)
    class(sf_int_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: r, rb
    real(default), intent(inout) :: x_free
    r = 0
    rb= 1
  end subroutine sf_int_generate_free

```

Complete the structure-function kinematics, derived from an input parameter (array) *r* between 0 and 1. The interaction momenta are calculated, and we return *x* (the momentum fraction), and *f* (the Jacobian factor for the map $r \rightarrow x$), if **map** is set.

If the **map** flag is unset, *r* and *x* values will coincide, and *f* will become unity. If it is set, the structure-function implementation chooses a convenient mapping from *r* to *x* with Jacobian *f*.

In the **inverse_kinematics** variant, we exchange the intent of **x** and **r**. The momenta are calculated only if the optional flag **set_momenta** is present and set.

```

(SF base: sf_int: TBP)+≡
  procedure (sf_int_complete_kinematics), deferred :: complete_kinematics
  procedure (sf_int_inverse_kinematics), deferred :: inverse_kinematics

(SF base: interfaces)+≡
  abstract interface
    subroutine sf_int_complete_kinematics (sf_int, x, f, r, rb, map)
      import
      class(sf_int_t), intent(inout) :: sf_int
      real(default), dimension(:), intent(out) :: x
      real(default), intent(out) :: f
      real(default), dimension(:), intent(in) :: r
      real(default), dimension(:), intent(in) :: rb
      logical, intent(in) :: map
    end subroutine sf_int_complete_kinematics
  end interface

  abstract interface
    subroutine sf_int_inverse_kinematics (sf_int, x, f, r, rb, map, &
      set_momenta)
      import
      class(sf_int_t), intent(inout) :: sf_int
      real(default), dimension(:), intent(in) :: x

```

```

        real(default), intent(out) :: f
        real(default), dimension(:), intent(out) :: r
        real(default), dimension(:), intent(out) :: rb
        logical, intent(in) :: map
        logical, intent(in), optional :: set_momenta
    end subroutine sf_int_inverse_kinematics
end interface

```

Single splitting: compute momenta, given x input parameters. We assume that the incoming momentum is set. The status code is set to `SF_FAILED_KINEMATICS` if the x array does not correspond to a valid momentum configuration. Otherwise, it is updated to `SF_DONE_KINEMATICS`.

We force the outgoing particle on-shell. The on-shell projection is determined by the `on_shell_mode`. The radiated particle should already be on shell.

(SF base: sf_int: TBP)+≡

```

    procedure :: split_momentum => sf_int_split_momentum

```

(SF base: procedures)+≡

```

subroutine sf_int_split_momentum (sf_int, x, xb1)
    class(sf_int_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(in) :: xb1
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    type(splitting_data_t) :: sd
    real(default) :: E1, E2
    logical :: fail
    if (sf_int%status >= SF_SEED_KINEMATICS) then
        k = sf_int%get_momentum (1)
        call sd%init (k, &
            sf_int%mi2(1), sf_int%mr2(1), sf_int%mo2(1), &
            collinear = size (x) == 1)
        call sd%set_t_bounds (x(1), xb1)
        select case (size (x))
        case (1)
        case (3)
            if (sf_int%qmax_defined) then
                if (sf_int%qmin_defined) then
                    call sd%sample_t (x(2), &
                        t0 = - sf_int%qmax(1) ** 2, t1 = - sf_int%qmin(1) ** 2)
                else
                    call sd%sample_t (x(2), &
                        t0 = - sf_int%qmax(1) ** 2)
                end if
            else
                if (sf_int%qmin_defined) then
                    call sd%sample_t (x(2), t1 = - sf_int%qmin(1) ** 2)
                else
                    call sd%sample_t (x(2))
                end if
            end if
            call sd%sample_phi (x(3))
        case default
            call msg_bug ("Structure function: impossible number of parameters")
        end select
    end if
end subroutine sf_int_split_momentum

```

```

end select
q = sd%split_momentum (k)
call on_shell (q, [sf_int%mr2, sf_int%mo2], &
  sf_int%on_shell_mode)
call sf_int%set_momenta (q, outgoing=.true.)
E1 = energy (q(1))
E2 = energy (q(2))
fail = E1 < 0 .or. E2 < 0 &
  .or. E1 ** 2 < sf_int%mr2(1) &
  .or. E2 ** 2 < sf_int%mo2(1)
if (fail) then
  sf_int%status = SF_FAILED_KINEMATICS
else
  sf_int%status = SF_DONE_KINEMATICS
end if
end if
end subroutine sf_int_split_momentum

```

Pair splitting: two incoming momenta, two radiated, two outgoing. This is simple because we insist on all momenta being collinear.

<SF base: sf_int: TBP>+≡

```

procedure :: split_momenta => sf_int_split_momenta

```

<SF base: procedures>+≡

```

subroutine sf_int_split_momenta (sf_int, x, xb1)
  class(sf_int_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(in) :: x
  real(default), dimension(:), intent(in) :: xb1
  type(vector4_t), dimension(2) :: k
  type(vector4_t), dimension(4) :: q
  real(default), dimension(4) :: E
  logical :: fail
  if (sf_int%status >= SF_SEED_KINEMATICS) then
    select case (size (x))
    case (2)
    case default
      call msg_bug ("Pair structure function: recoil requested &
        &but not implemented yet")
    end select
    k(1) = sf_int%get_momentum (1)
    k(2) = sf_int%get_momentum (2)
    q(1:2) = xb1 * k
    q(3:4) = x * k
    select case (size (sf_int%mr2))
    case (2)
      call on_shell (q, &
        [sf_int%mr2(1), sf_int%mr2(2), &
        sf_int%mo2(1), sf_int%mo2(2)], &
        sf_int%on_shell_mode)
      call sf_int%set_momenta (q, outgoing=.true.)
      E = energy (q)
      fail = any (E < 0) &
        .or. any (E(1:2) ** 2 < sf_int%mr2) &
        .or. any (E(3:4) ** 2 < sf_int%mo2)
    end select
  end if
end subroutine sf_int_split_momenta

```



```

        case default; call msg_bug ("split momenta: incorrect use")
    end select
    if (fail) then
        sf_int%status = SF_FAILED_KINEMATICS
    else
        sf_int%status = SF_DONE_KINEMATICS
    end if
end if
end if
end subroutine sf_int_split_momenta

```

Pair spectrum: the reduced version of the previous splitting, without radiated momenta.

```

<SF base: sf_int: TBP>+=
    procedure :: reduce_momenta => sf_int_reduce_momenta

<SF base: procedures>+=
    subroutine sf_int_reduce_momenta (sf_int, x)
        class(sf_int_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(in) :: x
        type(vector4_t), dimension(2) :: k
        type(vector4_t), dimension(2) :: q
        real(default), dimension(2) :: E
        logical :: fail
        if (sf_int%status >= SF_SEED_KINEMATICS) then
            select case (size(x))
            case (2)
            case default
                call msg_bug ("Pair spectrum: recoil requested &
                    &but not implemented yet")
            end select
            k(1) = sf_int%get_momentum (1)
            k(2) = sf_int%get_momentum (2)
            q = x * k
            call on_shell (q, &
                [sf_int%mo2(1), sf_int%mo2(2)], &
                sf_int%on_shell_mode)
            call sf_int%set_momenta (q, outgoing=.true.)
            E = energy (q)
            fail = any (E < 0) &
                .or. any (E ** 2 < sf_int%mo2)
            if (fail) then
                sf_int%status = SF_FAILED_KINEMATICS
            else
                sf_int%status = SF_DONE_KINEMATICS
            end if
        end if
    end subroutine sf_int_reduce_momenta

```

The inverse procedure: we compute the x array from the momentum configuration. In an overriding TBP, we may also set internal data that depend on this, for convenience.

NOTE: Here and above, the single-particle case is treated in detail, allowing for non-collinearity and non-vanishing masses and nontrivial momentum-

transfer bounds. For the pair case, we currently implement only collinear splitting and assume massless particles. This should be improved.

NOTE: We should also improve this in the sense of extracting both x and \bar{x} , where for the latter we may consult the beam remnant. The current implementation is not sensitive to small \bar{x} values.

```

(SF base: sf_int: TBP)+≡
  procedure :: recover_x => sf_int_recover_x
  procedure :: base_recover_x => sf_int_recover_x

(SF base: procedures)+≡
  subroutine sf_int_recover_x (sf_int, x, x_free)
    class(sf_int_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(inout), optional :: x_free
    type(vector4_t), dimension(:), allocatable :: k
    type(vector4_t), dimension(:), allocatable :: q
    type(splitting_data_t) :: sd
    if (sf_int%status >= SF_SEED_KINEMATICS) then
      allocate (k (sf_int%interaction_t%get_n_in ()))
      allocate (q (sf_int%interaction_t%get_n_out ()))
      k = sf_int%get_momenta (outgoing=.false.)
      q = sf_int%get_momenta (outgoing=.true.)
      select case (size (k))
      case (1)
        call sd%init (k(1), &
          sf_int%mi2(1), sf_int%mr2(1), sf_int%mo2(1), &
          collinear = size (x) == 1)
        call sd%recover (k(1), q(2), sf_int%on_shell_mode)
        x(1) = sd%get_x ()
        select case (size (x))
        case (1)
        case (3)
          if (sf_int%qmax_defined) then
            if (sf_int%qmin_defined) then
              call sd%inverse_t (x(2), &
                t0 = - sf_int%qmax(1) ** 2, t1 = - sf_int%qmin(1) ** 2)
            else
              call sd%inverse_t (x(2), &
                t0 = - sf_int%qmax(1) ** 2)
            end if
          else
            if (sf_int%qmin_defined) then
              call sd%inverse_t (x(2), t1 = - sf_int%qmin(1) ** 2)
            else
              call sd%inverse_t (x(2))
            end if
          end if
          call sd%inverse_phi (x(3))
        case default
          call msg_bug ("Structure function: impossible number &
            &of parameters")
        end select
      case (2)
        select case (size (x))

```

```

        case (2)
        case default
            call msg_bug ("Pair structure function: recoil requested &
                &but not implemented yet")
        end select
        select case (sf_int%on_shell_mode)
        case (KEEP_ENERGY)
            select case (size (q))
            case (4)
                x = energy (q(3:4)) / energy (k)
            case (2)
                x = energy (q) / energy (k)
            end select
        case (KEEP_MOMENTUM)
            select case (size (q))
            case (4)
                x = longitudinal_part (q(3:4)) / longitudinal_part (k)
            case (2)
                x = longitudinal_part (q) / longitudinal_part (k)
            end select
        end select
    end select
end if
end subroutine sf_int_recover_x

```

Apply the structure function, i.e., evaluate the interaction. For the calculation, we may use the stored momenta, any further information stored inside the `sf_int` implementation during kinematics setup, and the given energy scale. It may happen that for the given kinematics the value is not defined. This should be indicated by the status code.

```

<SF base: sf_int: TBP>+≡
    procedure (sf_int_apply), deferred :: apply

<SF base: interfaces>+≡
    abstract interface
        subroutine sf_int_apply (sf_int, scale)
            import
            class(sf_int_t), intent(inout) :: sf_int
            real(default), intent(in) :: scale
        end subroutine sf_int_apply
    end interface

```

15.5.4 Accessing the structure function

Return metadata. Once `interaction_t` is rewritten in OO, some of this will be inherited.

The number of outgoing is equal to the number of incoming particles. The radiated particles are the difference.

```

<SF base: sf_int: TBP>+≡
    procedure :: get_n_in => sf_int_get_n_in
    procedure :: get_n_rad => sf_int_get_n_rad
    procedure :: get_n_out => sf_int_get_n_out

```

```

<SF base: procedures>+=
function sf_int_get_n_in (object) result (n_in)
  class(sf_int_t), intent(in) :: object
  integer :: n_in
  n_in = object%interaction_t%get_n_in ()
end function sf_int_get_n_in

function sf_int_get_n_rad (object) result (n_rad)
  class(sf_int_t), intent(in) :: object
  integer :: n_rad
  n_rad = object%interaction_t%get_n_out () &
    - object%interaction_t%get_n_in ()
end function sf_int_get_n_rad

function sf_int_get_n_out (object) result (n_out)
  class(sf_int_t), intent(in) :: object
  integer :: n_out
  n_out = object%interaction_t%get_n_in ()
end function sf_int_get_n_out

```

Number of matrix element entries in the interaction:

```

<SF base: sf_int: TBP>+=
procedure :: get_n_states => sf_int_get_n_states

<SF base: procedures>+=
function sf_int_get_n_states (sf_int) result (n_states)
  class(sf_int_t), intent(in) :: sf_int
  integer :: n_states
  n_states = sf_int%get_n_matrix_elements ()
end function sf_int_get_n_states

```

Return a specific state as a quantum-number array.

```

<SF base: sf_int: TBP>+=
procedure :: get_state => sf_int_get_state

<SF base: procedures>+=
function sf_int_get_state (sf_int, i) result (qn)
  class(sf_int_t), intent(in) :: sf_int
  type(quantum_numbers_t), dimension(:), allocatable :: qn
  integer, intent(in) :: i
  allocate (qn (sf_int%get_n_tot ()))
  qn = sf_int%get_quantum_numbers (i)
end function sf_int_get_state

```

Return the matrix-element values for all states. We can assume that the matrix elements are real, so we take the real part.

```

<SF base: sf_int: TBP>+=
procedure :: get_values => sf_int_get_values

<SF base: procedures>+=
subroutine sf_int_get_values (sf_int, value)
  class(sf_int_t), intent(in) :: sf_int
  real(default), dimension(:), intent(out) :: value

```

```

integer :: i
if (sf_int%status >= SF_EVALUATED) then
  do i = 1, size (value)
    value(i) = sf_int%get_matrix_element (i)
  end do
else
  value = 0
end if
end subroutine sf_int_get_values

```

15.5.5 Direct calculations

Compute a structure function value (array) directly, given an array of x values and a scale. If the energy is also given, we initialize the kinematics for that energy, otherwise take it from a previous run.

We assume that the E array has dimension n_in , and the x array has n_par .

```

<SF base: sf_int: TBP>+≡
  procedure :: compute_values => sf_int_compute_values

<SF base: procedures>+≡
  subroutine sf_int_compute_values (sf_int, value, x, xb, scale, E)
    class(sf_int_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: value
    real(default), dimension(:), intent(in) :: x
    real(default), dimension(:), intent(in) :: xb
    real(default), intent(in) :: scale
    real(default), dimension(:), intent(in), optional :: E
    real(default), dimension(size (x)) :: xx
    real(default) :: f
    if (present (E)) call sf_int%seed_kinematics (E)
    if (sf_int%status >= SF_SEED_KINEMATICS) then
      call sf_int%complete_kinematics (xx, f, x, xb, map=.false.)
      call sf_int%apply (scale)
      call sf_int%get_values (value)
      value = value * f
    else
      value = 0
    end if
  end subroutine sf_int_compute_values

```

Compute just a single value for one of the states, i.e., throw the others away.

```

<SF base: sf_int: TBP>+≡
  procedure :: compute_value => sf_int_compute_value

<SF base: procedures>+≡
  subroutine sf_int_compute_value &
    (sf_int, i_state, value, x, xb, scale, E)
    class(sf_int_t), intent(inout) :: sf_int
    integer, intent(in) :: i_state
    real(default), intent(out) :: value
    real(default), dimension(:), intent(in) :: x
    real(default), dimension(:), intent(in) :: xb

```

```

real(default), intent(in) :: scale
real(default), dimension(:), intent(in), optional :: E
real(default), dimension(:), allocatable :: value_array
if (sf_int%status >= SF_INITIAL) then
    allocate (value_array (sf_int%get_n_states ()))
    call sf_int%compute_values (value_array, x, xb, scale, E)
    value = value_array(i_state)
else
    value = 0
end if
end subroutine sf_int_compute_value

```

15.5.6 Structure-function instance

This is a wrapper for `sf_int_t` objects, such that we can build an array with different structure-function types. The structure-function contains an array (a sequence) of `sf_int_t` objects.

The object, it holds the evaluator that connects the preceding part of the structure-function chain to the current interaction.

It also stores the input and output parameter values for the contained structure function. The `r` array has a second dimension, corresponding to the mapping channels in a multi-channel configuration. There is a Jacobian entry `f` for each channel. The corresponding logical array `mapping` tells whether we apply the mapping appropriate for the current structure function in this channel. The `x` parameter values (energy fractions) are common to all channels.

(SF base: types)+≡

```

type :: sf_instance_t
    class(sf_int_t), allocatable :: int
    type(evaluator_t) :: eval
    real(default), dimension(:, :), allocatable :: r
    real(default), dimension(:, :), allocatable :: rb
    real(default), dimension(:), allocatable :: f
    logical, dimension(:), allocatable :: m
    real(default), dimension(:), allocatable :: x
end type sf_instance_t

```

15.5.7 Structure-function chain

A chain is an array of structure functions `sf`, initiated by a beam setup. We do not use this directly for evaluation, but create instances with copies of the contained interactions.

`n_par` is the total number of parameters that is necessary for completely determining the structure-function chain. `n_bound` is the number of MC input parameters that are requested from the integrator. The difference of `n_par` and `n_bound` is the number of free parameters, which are generated by a structure-function object in generator mode.

(SF base: public)+≡

```

public :: sf_chain_t

```

```

<SF base: types>+≡
type, extends (beam_t) :: sf_chain_t
  type(beam_data_t), pointer :: beam_data => null ()
  integer :: n_in = 0
  integer :: n_strfun = 0
  integer :: n_par = 0
  integer :: n_bound = 0
  type(sf_instance_t), dimension(:), allocatable :: sf
  logical :: trace_enable = .false.
  integer :: trace_unit = 0
contains
  <SF base: sf chain: TBP>
end type sf_chain_t

```

Finalizer.

```

<SF base: sf chain: TBP>≡
  procedure :: final => sf_chain_final

<SF base: procedures>+≡
  subroutine sf_chain_final (object)
    class(sf_chain_t), intent(inout) :: object
    integer :: i
    call object%final_tracing ()
    if (allocated (object%sf)) then
      do i = 1, size (object%sf, 1)
        associate (sf => object%sf(i))
          if (allocated (sf%int)) then
            call sf%int%final ()
          end if
        end associate
      end do
    end if
    call beam_final (object%beam_t)
  end subroutine sf_chain_final

```

Output.

```

<SF base: sf chain: TBP>+≡
  procedure :: write => sf_chain_write

<SF base: procedures>+≡
  subroutine sf_chain_write (object, unit)
    class(sf_chain_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Incoming particles / structure-function chain:"
    if (associated (object%beam_data)) then
      write (u, "(3x,A,I0)") "n_in      = ", object%n_in
      write (u, "(3x,A,I0)") "n_strfun = ", object%n_strfun
      write (u, "(3x,A,I0)") "n_par     = ", object%n_par
      if (object%n_par /= object%n_bound) then
        write (u, "(3x,A,I0)") "n_bound  = ", object%n_bound
      end if
      call beam_data_write (object%beam_data, u)
    end if
  end subroutine sf_chain_write

```

```

call write_separator (u)
call beam_write (object%beam_t, u)
if (allocated (object%sf)) then
  do i = 1, object%n_strfun
    associate (sf => object%sf(i))
      call write_separator (u)
      if (allocated (sf%int)) then
        call sf%int%write (u)
      else
        write (u, "(1x,A)") "SF instance: [undefined]"
      end if
    end associate
  end do
end if
else
  write (u, "(3x,A)") "[undefined]"
end if
end subroutine sf_chain_write

```

Initialize: setup beams. The `beam_data` target must remain valid for the lifetime of the chain, since we just establish a pointer. The structure-function configuration array is used to initialize the individual structure-function entries. The target attribute is needed because the `sf_int` entries establish pointers to the configuration data.

```

<SF base: sf chain: TBP>+≡
  procedure :: init => sf_chain_init

<SF base: procedures>+≡
  subroutine sf_chain_init (sf_chain, beam_data, sf_config)
    class(sf_chain_t), intent(out) :: sf_chain
    type(beam_data_t), intent(in), target :: beam_data
    type(sf_config_t), dimension(:), intent(in), optional, target :: sf_config
    integer :: i
    sf_chain%beam_data => beam_data
    sf_chain%n_in = beam_data_get_n_in (beam_data)
    call beam_init (sf_chain%beam_t, beam_data)
    if (present (sf_config)) then
      sf_chain%n_strfun = size (sf_config)
      allocate (sf_chain%sf (sf_chain%n_strfun))
      do i = 1, sf_chain%n_strfun
        call sf_chain%set_strfun (i, sf_config(i)%i, sf_config(i)%data)
      end do
    end if
  end subroutine sf_chain_init

```

Receive the beam momenta from a source to which the beam interaction is linked.

```

<SF base: sf chain: TBP>+≡
  procedure :: receive_beam_momenta => sf_chain_receive_beam_momenta

<SF base: procedures>+≡
  subroutine sf_chain_receive_beam_momenta (sf_chain)
    class(sf_chain_t), intent(inout), target :: sf_chain

```



```

    type(interaction_t), pointer :: beam_int
    beam_int => sf_chain%get_beam_int_ptr ()
    call beam_int%receive_momenta ()
end subroutine sf_chain_receive_beam_momenta

```

Explicitly set the beam momenta.

```

<SF base: sf chain: TBP>+≡
    procedure :: set_beam_momenta => sf_chain_set_beam_momenta

<SF base: procedures>+≡
    subroutine sf_chain_set_beam_momenta (sf_chain, p)
        class(sf_chain_t), intent(inout) :: sf_chain
        type(vector4_t), dimension(:), intent(in) :: p
        call beam_set_momenta (sf_chain%beam_t, p)
    end subroutine sf_chain_set_beam_momenta

```

Set a structure-function entry. We use the `data` input to allocate the `int` structure-function instance with appropriate type, then initialize the entry. The entry establishes a pointer to `data`.

The index `i` is the structure-function index in the chain.

```

<SF base: sf chain: TBP>+≡
    procedure :: set_strfun => sf_chain_set_strfun

<SF base: procedures>+≡
    subroutine sf_chain_set_strfun (sf_chain, i, beam_index, data)
        class(sf_chain_t), intent(inout) :: sf_chain
        integer, intent(in) :: i
        integer, dimension(:), intent(in) :: beam_index
        class(sf_data_t), intent(in), target :: data
        integer :: n_par, j
        n_par = data%get_n_par ()
        call data%allocate_sf_int (sf_chain%sf(i)%int)
        associate (sf_int => sf_chain%sf(i)%int)
            call sf_int%init (data)
            call sf_int%set_beam_index (beam_index)
            call sf_int%set_par_index &
                ([ (j, j = sf_chain%n_par + 1, sf_chain%n_par + n_par)])
            sf_chain%n_par = sf_chain%n_par + n_par
            if (.not. data%is_generator ()) then
                sf_chain%n_bound = sf_chain%n_bound + n_par
            end if
        end associate
    end subroutine sf_chain_set_strfun

```

Return the number of structure-function parameters.

```

<SF base: sf chain: TBP>+≡
    procedure :: get_n_par => sf_chain_get_n_par
    procedure :: get_n_bound => sf_chain_get_n_bound

<SF base: procedures>+≡
    function sf_chain_get_n_par (sf_chain) result (n)
        class(sf_chain_t), intent(in) :: sf_chain
        integer :: n

```

```

    n = sf_chain%n_par
end function sf_chain_get_n_par

function sf_chain_get_n_bound (sf_chain) result (n)
    class(sf_chain_t), intent(in) :: sf_chain
    integer :: n
    n = sf_chain%n_bound
end function sf_chain_get_n_bound

```

Return a pointer to the beam interaction.

```

<SF base: sf chain: TBP>+≡
    procedure :: get_beam_int_ptr => sf_chain_get_beam_int_ptr

<SF base: procedures>+≡
    function sf_chain_get_beam_int_ptr (sf_chain) result (int)
        class(sf_chain_t), intent(in), target :: sf_chain
        type(interaction_t), pointer :: int
        int => beam_get_int_ptr (sf_chain%beam_t)
    end function sf_chain_get_beam_int_ptr

```

Enable the trace feature: record structure function data (input parameters, x values, evaluation result) to an external file.

```

<SF base: sf chain: TBP>+≡
    procedure :: setup_tracing => sf_chain_setup_tracing
    procedure :: final_tracing => sf_chain_final_tracing

<SF base: procedures>+≡
    subroutine sf_chain_setup_tracing (sf_chain, file)
        class(sf_chain_t), intent(inout) :: sf_chain
        type(string_t), intent(in) :: file
        if (sf_chain%n_strfun > 0) then
            sf_chain%trace_enable = .true.
            sf_chain%trace_unit = free_unit ()
            open (sf_chain%trace_unit, file = char (file), action = "write", &
                status = "replace")
            call sf_chain%write_trace_header ()
        else
            call msg_error ("Beam structure: no structure functions, tracing &
                &disabled")
        end if
    end subroutine sf_chain_setup_tracing

    subroutine sf_chain_final_tracing (sf_chain)
        class(sf_chain_t), intent(inout) :: sf_chain
        if (sf_chain%trace_enable) then
            close (sf_chain%trace_unit)
            sf_chain%trace_enable = .false.
        end if
    end subroutine sf_chain_final_tracing

```

Write the header for the tracing file.

```

<SF base: sf chain: TBP>+≡
    procedure :: write_trace_header => sf_chain_write_trace_header

```

```

<SF base: procedures>+=
subroutine sf_chain_write_trace_header (sf_chain)
  class(sf_chain_t), intent(in) :: sf_chain
  integer :: u
  if (sf_chain%trace_enable) then
    u = sf_chain%trace_unit
    write (u, "('# ',A)") "WHIZARD output: &
      &structure-function sampling data"
    write (u, "('# ',A,1x,I0)") "Number of sf records:", sf_chain%n_strfun
    write (u, "('# ',A,1x,I0)") "Number of parameters:", sf_chain%n_par
    write (u, "('# ',A)") "Columns: channel, p(n_par), x(n_par), f, Jac * f"
  end if
end subroutine sf_chain_write_trace_header

```

Write a record which collects the structure function data for the current data point. For the selected channel, we print first the input integration parameters, then the x values, then the structure-function value summed over all quantum numbers, then the structure function value times the mapping Jacobian.

```

<SF base: sf chain: TBP>+=
  procedure :: trace => sf_chain_trace

<SF base: procedures>+=
subroutine sf_chain_trace (sf_chain, c_sel, p, x, f, sf_sum)
  class(sf_chain_t), intent(in) :: sf_chain
  integer, intent(in) :: c_sel
  real(default), dimension(:,:), intent(in) :: p
  real(default), dimension(:), intent(in) :: x
  real(default), dimension(:), intent(in) :: f
  real(default), intent(in) :: sf_sum
  integer :: u, i
  if (sf_chain%trace_enable) then
    u = sf_chain%trace_unit
    write (u, "(1x,I0)", advance="no") c_sel
    write (u, "(2x)", advance="no")
    do i = 1, sf_chain%n_par
      write (u, "(1x," // FMT_17 // ")", advance="no") p(i,c_sel)
    end do
    write (u, "(2x)", advance="no")
    do i = 1, sf_chain%n_par
      write (u, "(1x," // FMT_17 // ")", advance="no") x(i)
    end do
    write (u, "(2x)", advance="no")
    write (u, "(2(1x," // FMT_17 // "))" sf_sum, f(c_sel) * sf_sum)
  end if
end subroutine sf_chain_trace

```

15.5.8 Chain instances

A structure-function chain instance contains copies of the interactions in the configuration chain, suitably linked to each other and connected by evaluators.

After initialization, `out_sf` should point, for each beam, to the last structure function that affects this beam. `out_sf_i` should indicate the index of the

corresponding outgoing particle within that structure-function interaction.

Analogously, `out_eval` is the last evaluator in the structure-function chain, which contains the complete set of outgoing particles. `out_eval_i` should indicate the index of the outgoing particles, within that evaluator, which will initiate the collision.

When calculating actual kinematics, we fill the `p`, `r`, and `x` arrays and the `f` factor. The `p` array denotes the MC input parameters as they come from the random-number generator. The `r` array results from applying global mappings. The `x` array results from applying structure-function local mappings. The `x` values can be interpreted directly as momentum fractions (or angle fractions, where recoil is involved). The `f` factor is the Jacobian that results from applying all mappings.

The `mapping` entry may store a global mapping that is applied to a combination of `x` values and structure functions, as opposed to mappings that affect only a single structure function. It is applied before the latter mappings, in the transformation from the `p` array to the `r` array. For parameters affected by this mapping, we should ensure that they are not involved in a local mapping.

```

<SF base: public>+≡
    public :: sf_chain_instance_t

<SF base: types>+≡
    type, extends (beam_t) :: sf_chain_instance_t
        type(sf_chain_t), pointer :: config => null ()
        integer :: status = SF_UNDEFINED
        type(sf_instance_t), dimension(:), allocatable :: sf
        integer, dimension(:), allocatable :: out_sf
        integer, dimension(:), allocatable :: out_sf_i
        integer :: out_eval = 0
        integer, dimension(:), allocatable :: out_eval_i
        integer :: selected_channel = 0
        real(default), dimension(:,:), allocatable :: p, pb
        real(default), dimension(:,:), allocatable :: r, rb
        real(default), dimension(:), allocatable :: f
        real(default), dimension(:), allocatable :: x
        logical, dimension(:), allocatable :: bound
        real(default) :: x_free = 1
        type(sf_channel_t), dimension(:), allocatable :: channel
    contains
        <SF base: sf chain instance: TBP>
    end type sf_chain_instance_t

```

Finalizer.

```

<SF base: sf chain instance: TBP>≡
    procedure :: final => sf_chain_instance_final

<SF base: procedures>+≡
    subroutine sf_chain_instance_final (object)
        class(sf_chain_instance_t), intent(inout) :: object
        integer :: i
        if (allocated (object%sf)) then
            do i = 1, size (object%sf, 1)
                associate (sf => object%sf(i))
                    if (allocated (sf%int)) then

```

```

        call sf%eval%final ()
        call sf%int%final ()
    end if
end associate
end do
end if
call beam_final (object%beam_t)
end subroutine sf_chain_instance_final

```

Output.

Note: nagfor 5.3.1 appears to be slightly confused with the allocation status.
We check both for allocation and nonzero size.

```

<SF base: sf chain instance: TBP>+≡
    procedure :: write => sf_chain_instance_write

<SF base: procedures>+≡
    subroutine sf_chain_instance_write (object, unit)
        class(sf_chain_instance_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, i, c
        u = given_output_unit (unit)
        write (u, "(1x,A)", advance="no") "Structure-function chain instance:"
        call write_sf_status (object%status, u)
        if (allocated (object%out_sf)) then
            write (u, "(3x,A)", advance="no") "outgoing (interactions) ="
            do i = 1, size (object%out_sf)
                write (u, "(1x,I0,':',I0)", advance="no") &
                    object%out_sf(i), object%out_sf_i(i)
            end do
            write (u, *)
        end if
        if (object%out_eval /= 0) then
            write (u, "(3x,A)", advance="no") "outgoing (evaluators) ="
            do i = 1, size (object%out_sf)
                write (u, "(1x,I0,':',I0)", advance="no") &
                    object%out_eval, object%out_eval_i(i)
            end do
            write (u, *)
        end if
        if (allocated (object%sf)) then
            if (size (object%sf) /= 0) then
                write (u, "(1x,A)") "Structure-function parameters:"
                do c = 1, size (object%f)
                    write (u, "(1x,A,I0,A)", advance="no") "Channel #", c, ":"
                    if (c == object%selected_channel) then
                        write (u, "(1x,A)") "[selected]"
                    else
                        write (u, *)
                    end if
                    write (u, "(3x,A,9(1x,F9.7))") "p =", object%p(:,c)
                    write (u, "(3x,A,9(1x,F9.7))") "r =", object%r(:,c)
                    write (u, "(3x,A,9(1x,ES13.7))") "f =", object%f(c)
                    write (u, "(3x,A)", advance="no") "m ="
                    call object%channel(c)%write (u)
                end do
            end if
        end if
    end subroutine sf_chain_instance_write

```

```

        end do
        write (u, "(3x,A,9(1x,F9.7))") "x =", object%x
        if (.not. all (object%bound)) then
            write (u, "(3x,A,9(1x,L1))") "bound =", object%bound
        end if
    end if
end if
call write_separator (u)
call beam_write (object%beam_t, u)
if (allocated (object%sf)) then
    do i = 1, size (object%sf)
        associate (sf => object%sf(i))
            call write_separator (u)
            if (allocated (sf%int)) then
                if (allocated (sf%x)) then
                    write (u, "(1x,A)") "Structure-function parameters:"
                    do c = 1, size (sf%f)
                        write (u, "(1x,A,I0,A)", advance="no") "Channel #", c, ":"
                        if (c == object%selected_channel) then
                            write (u, "(1x,A)") "[selected]"
                        else
                            write (u, *)
                        end if
                        write (u, "(3x,A,9(1x,F9.7))") "r =", sf%x(:,c)
                        write (u, "(3x,A,9(1x,ES13.7))") "f =", sf%f(c)
                        write (u, "(3x,A,9(1x,L1,7x))") "m =", sf%m(c)
                    end do
                    write (u, "(3x,A,9(1x,F9.7))") "x =", sf%x
                end if
                call sf%int%write (u)
                if (.not. sf%eval%is_empty ()) then
                    call sf%eval%write (u)
                end if
            end if
        end associate
    end do
end if
end subroutine sf_chain_instance_write

```

Initialize. This creates a copy of the interactions in the configuration chain, assumed to be properly initialized. In the copy, we allocate the `p` etc. arrays.

The brute-force assignment of the `sf` component would be straightforward, but at least gfortran 4.6.3 would like a more fine-grained copy. In any case, the copy is deep as far as allocatables are concerned, but for the contained `interaction_t` objects the copy is shallow, as long as we do not bind defined assignment to the type. Therefore, we have to re-assign the `interaction_t` components explicitly, this time calling the proper defined assignment. Furthermore, we allocate the parameter arrays for each structure function.

(SF base: sf chain instance: TBP)+≡

```
procedure :: init => sf_chain_instance_init
```

(SF base: procedures)+≡

```
subroutine sf_chain_instance_init (chain, config, n_channel)
```

```

class(sf_chain_instance_t), intent(out), target :: chain
type(sf_chain_t), intent(in), target :: config
integer, intent(in) :: n_channel
integer :: i, j
integer :: n_par_tot, n_par, n_strfun
chain%config => config
n_strfun = config%n_strfun
chain%beam_t = config%beam_t
allocate (chain%out_sf (config%n_in), chain%out_sf_i (config%n_in))
allocate (chain%out_eval_i (config%n_in))
chain%out_sf = 0
chain%out_sf_i = [(i, i = 1, config%n_in)]
chain%out_eval_i = chain%out_sf_i
n_par_tot = 0
if (n_strfun /= 0) then
  allocate (chain%sf (n_strfun))
  do i = 1, n_strfun
    associate (sf => chain%sf(i))
      allocate (sf%int, source=config%sf(i)%int)
      sf%int%interaction_t = config%sf(i)%int%interaction_t
      n_par = size (sf%int%par_index)
      allocate (sf%r (n_par, n_channel)); sf%r = 0
      allocate (sf%rb(n_par, n_channel)); sf%rb= 0
      allocate (sf%f (n_channel)); sf%f = 0
      allocate (sf%m (n_channel)); sf%m = .false.
      allocate (sf%x (n_par)); sf%x = 0
      n_par_tot = n_par_tot + n_par
    end associate
  end do
  allocate (chain%p (n_par_tot, n_channel)); chain%p = 0
  allocate (chain%pb(n_par_tot, n_channel)); chain%pb= 0
  allocate (chain%r (n_par_tot, n_channel)); chain%r = 0
  allocate (chain%rb(n_par_tot, n_channel)); chain%rb= 0
  allocate (chain%f (n_channel)); chain%f = 0
  allocate (chain%x (n_par_tot)); chain%x = 0
  call allocate_sf_channels &
    (chain%channel, n_channel=n_channel, n_strfun=n_strfun)
end if
allocate (chain%bound (n_par_tot), source = .true.)
do i = 1, n_strfun
  associate (sf => chain%sf(i))
    if (sf%int%is_generator ()) then
      do j = 1, size (sf%int%par_index)
        chain%bound(sf%int%par_index(j)) = .false.
      end do
    end if
  end associate
end do
chain%status = SF_INITIAL
end subroutine sf_chain_instance_init

```

Manually select a channel.

$\langle SF \text{ base: } sf \text{ chain instance: } TBP \rangle + \equiv$

```

    procedure :: select_channel => sf_chain_instance_select_channel
  (SF base: procedures)+≡
    subroutine sf_chain_instance_select_channel (chain, channel)
      class(sf_chain_instance_t), intent(inout) :: chain
      integer, intent(in), optional :: channel
      if (present (channel)) then
        chain%selected_channel = channel
      else
        chain%selected_channel = 0
      end if
    end subroutine sf_chain_instance_select_channel

```

Copy a channel-mapping object to the structure-function chain instance. We assume that assignment is sufficient, i.e., any non-static components of the **channel** object are allocatable and thus recursively copied.

After the copy, we extract the single-entry mappings and activate them for the individual structure functions. If there is a multi-entry mapping, we obtain the corresponding MC parameter indices and set them in the copy of the channel object.

```

  (SF base: sf chain instance: TBP)+≡
    procedure :: set_channel => sf_chain_instance_set_channel
  (SF base: procedures)+≡
    subroutine sf_chain_instance_set_channel (chain, c, channel)
      class(sf_chain_instance_t), intent(inout) :: chain
      integer, intent(in) :: c
      type(sf_channel_t), intent(in) :: channel
      integer :: i, j, k
      if (chain%status >= SF_INITIAL) then
        chain%channel(c) = channel
        j = 0
        do i = 1, chain%config%n_strfun
          associate (sf => chain%sf(i))
            sf%m(c) = channel%is_single_mapping (i)
            if (channel%is_multi_mapping (i)) then
              do k = 1, size (sf%int%beam_index)
                j = j + 1
                call chain%channel(c)%set_par_index (j, sf%int%par_index(k))
              end do
            end if
          end associate
        end do
        chain%status = SF_INITIAL
      end if
    end subroutine sf_chain_instance_set_channel

```

Link the interactions in the chain. First, link the beam instance to its template in the configuration chain, which should have the appropriate momenta fixed.

Then, we follow the chain via the arrays `out_sf` and `out_sf_i`. The arrays are (up to) two-dimensional, the entries correspond to the beam particle(s). For each beam, the entry `out_sf` points to the last interaction that affected this

beam, and `out_sf_i` is the out-particle index within that interaction. For the initial beam, `out_sf` is zero by definition.

For each entry in the chain, we scan the affected beams (one or two). We look for `out_sf` and link the out-particle there to the corresponding in-particle in the current interaction. Then, we update the entry in `out_sf` and `out_sf_i` to point to the current interaction.

```

(SF base: sf chain instance: TBP)+≡
  procedure :: link_interactions => sf_chain_instance_link_interactions

(SF base: procedures)+≡
  subroutine sf_chain_instance_link_interactions (chain)
    class(sf_chain_instance_t), intent(inout), target :: chain
    type(interaction_t), pointer :: int
    integer :: i, j, b
    if (chain%status >= SF_INITIAL) then
      do b = 1, chain%config%n_in
        int => beam_get_int_ptr (chain%beam_t)
        call interaction_set_source_link (int, b, &
          chain%config%beam_t, b)
      end do
      if (allocated (chain%sf)) then
        do i = 1, size (chain%sf)
          associate (sf_int => chain%sf(i)%int)
            do j = 1, size (sf_int%beam_index)
              b = sf_int%beam_index(j)
              call link (sf_int%interaction_t, b, sf_int%incoming(j))
              chain%out_sf(b) = i
              chain%out_sf_i(b) = sf_int%outgoing(j)
            end do
          end associate
        end do
      end if
      chain%status = SF_DONE_LINKS
    end if
  contains
    subroutine link (int, b, in_index)
      type(interaction_t), intent(inout) :: int
      integer, intent(in) :: b, in_index
      integer :: i
      i = chain%out_sf(b)
      select case (i)
      case (0)
        call interaction_set_source_link (int, in_index, &
          chain%beam_t, chain%out_sf_i(b))
      case default
        call int%set_source_link (in_index, &
          chain%sf(i)%int, chain%out_sf_i(b))
      end select
    end subroutine link
  end subroutine sf_chain_instance_link_interactions

```

Exchange the quantum-number masks between the interactions in the chain, so we can combine redundant entries and detect any obvious mismatch.

We proceed first in the forward direction and then backwards again.

After this is finished, we finalize initialization by calling the `setup_constants` method, which prepares constant data that depend on the matrix element structure.

```

(SF base: sf chain instance: TBP)+≡
  procedure :: exchange_mask => sf_chain_exchange_mask

(SF base: procedures)+≡
  subroutine sf_chain_exchange_mask (chain)
    class(sf_chain_instance_t), intent(inout), target :: chain
    type(interaction_t), pointer :: int
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
    integer :: i
    if (chain%status >= SF_DONE_LINKS) then
      if (allocated (chain%sf)) then
        int => beam_get_int_ptr (chain%beam_t)
        allocate (mask (int%get_n_out ()))
        mask = int%get_mask ()
        if (size (chain%sf) /= 0) then
          do i = 1, size (chain%sf) - 1
            call interaction_exchange_mask (chain%sf(i)%int%interaction_t)
          end do
          do i = size (chain%sf), 1, -1
            call interaction_exchange_mask (chain%sf(i)%int%interaction_t)
          end do
          if (any (mask .neqv. int%get_mask ())) then
            chain%status = SF_FAILED_MASK
            return
          end if
          do i = 1, size (chain%sf)
            call chain%sf(i)%int%setup_constants ()
          end do
        end if
      end if
      chain%status = SF_DONE_MASK
    end if
  end subroutine sf_chain_exchange_mask

```

Initialize the evaluators that connect the interactions in the chain.

```

(SF base: sf chain instance: TBP)+≡
  procedure :: init_evaluators => sf_chain_instance_init_evaluators

(SF base: procedures)+≡
  subroutine sf_chain_instance_init_evaluators (chain)
    class(sf_chain_instance_t), intent(inout), target :: chain
    type(interaction_t), pointer :: int
    type(quantum_numbers_mask_t) :: mask
    integer :: i
    if (chain%status >= SF_DONE_MASK) then
      if (allocated (chain%sf)) then
        if (size (chain%sf) /= 0) then
          mask = quantum_numbers_mask (.false., .false., .true.)
          int => beam_get_int_ptr (chain%beam_t)
          do i = 1, size (chain%sf)

```

```

        associate (sf => chain%sf(i))
        call sf%eval%init_product &
            (int, sf%int%interaction_t, mask)
        if (sf%eval%is_empty ()) then
            chain%status = SF_FAILED_CONNECTIONS
            return
        end if
        int => sf%eval%interaction_t
    end associate
end do
call find_outgoing_particles ()
end if
end if
chain%status = SF_DONE_CONNECTIONS
end if
contains
<SF base: init evaluators: find outgoing particles>
end subroutine sf_chain_instance_init_evaluators

```

This is an internal subroutine of the previous one: After evaluators are set, trace the outgoing particles to the last evaluator. We only need the first channel, all channels are equivalent for this purpose.

For each beam, the outgoing particle is located by `out_sf` (the structure-function object where it originates) and `out_sf_i` (the index within that object). This particle is referenced by the corresponding evaluator, which in turn is referenced by the next evaluator, until we are at the end of the chain. We can trace back references by `interaction_find_link`. Knowing that `out_eval` is the index of the last evaluator, we thus determine `out_eval_i`, the index of the outgoing particle within that evaluator.

```

<SF base: init evaluators: find outgoing particles>≡
subroutine find_outgoing_particles ()
    type(interaction_t), pointer :: int, int_next
    integer :: i, j, out_sf, out_i
    chain%out_eval = size (chain%sf)
    do j = 1, size (chain%out_eval_i)
        out_sf = chain%out_sf(j)
        out_i = chain%out_sf_i(j)
        if (out_sf == 0) then
            int => beam_get_int_ptr (chain%beam_t)
            out_sf = 1
        else
            int => chain%sf(out_sf)%int%interaction_t
        end if
        do i = out_sf, chain%out_eval
            int_next => chain%sf(i)%eval%interaction_t
            out_i = interaction_find_link (int_next, int, out_i)
            int => int_next
        end do
        chain%out_eval_i(j) = out_i
    end do
end subroutine find_outgoing_particles

```

Compute the kinematics in the chain instance. We can assume that the seed

momenta are set in the configuration beams. Scanning the chain, we first transfer the incoming momenta. Then, we use up the MC input parameter array **p** to compute the radiated and outgoing momenta.

In the multi-channel case, **c_sel** is the channel which we use for computing the kinematics and the **x** values. In the other channels, we invert the kinematics in order to recover the corresponding rows in the **r** array, and the Jacobian **f**.

We first apply any global mapping to transform the input **p** into the array **r**. This is then given to the structure functions which compute the final array **x** and Jacobian factors **f**, which we multiply to obtain the overall Jacobian.

```

<SF base: sf chain instance: TBP>+=
  procedure :: compute_kinematics => sf_chain_instance_compute_kinematics

<SF base: procedures>+=
  subroutine sf_chain_instance_compute_kinematics (chain, c_sel, p_in)
    class(sf_chain_instance_t), intent(inout), target :: chain
    integer, intent(in) :: c_sel
    real(default), dimension(:), intent(in) :: p_in
    type(interaction_t), pointer :: int
    real(default) :: f_mapping
    logical, dimension(size (chain%bound)) :: bound
    integer :: i, j, c
    if (chain%status >= SF_DONE_CONNECTIONS) then
      call chain%select_channel (c_sel)
      int => beam_get_int_ptr (chain%beam_t)
      call int%receive_momenta ()
      if (allocated (chain%sf)) then
        if (size (chain%sf) /= 0) then
          forall (i = 1:size (chain%sf)) chain%sf(i)%int%status = SF_INITIAL
          !!! Bug in nagfor 5.3.1(907), fixed in 5.3.1(982)
          ! chain%p (:,c_sel) = unpack (p_in, chain%bound, 0._default)
          !!! Workaround:
          bound = chain%bound
          chain%p (:,c_sel) = unpack (p_in, bound, 0._default)
          chain%pb(:,c_sel) = 1 - chain%p(:,c_sel)
          chain%f = 1
          chain%x_free = 1
          do i = 1, size (chain%sf)
            associate (sf => chain%sf(i))
              call sf%int%generate_free (sf%r(:,c_sel), sf%rb(:,c_sel), &
                chain%x_free)
              do j = 1, size (sf%x)
                if (.not. chain%bound(sf%int%par_index(j))) then
                  chain%p (sf%int%par_index(j),c_sel) = sf%r (j,c_sel)
                  chain%pb(sf%int%par_index(j),c_sel) = sf%rb(j,c_sel)
                end if
              end do
            end associate
          end do
          end do
          if (allocated (chain%channel(c_sel)%multi_mapping)) then
            call chain%channel(c_sel)%multi_mapping%compute &
              (chain%r(:,c_sel), chain%rb(:,c_sel), &
                f_mapping, &
                chain%p(:,c_sel), chain%pb(:,c_sel), &
                chain%x_free)
          end if
        end if
      end if
    end if
  end subroutine

```

```

        chain%f(c_sel) = f_mapping
    else
        chain%r(:,c_sel) = chain%p(:,c_sel)
        chain%rb(:,c_sel) = chain%pb(:,c_sel)
        chain%f(c_sel) = 1
    end if
do i = 1, size(chain%sf)
    associate(sf => chain%sf(i))
        call sf%int%seed_kinematics()
        do j = 1, size(sf%x)
            sf%r(j,c_sel) = chain%r(sf%int%par_index(j),c_sel)
            sf%rb(j,c_sel) = chain%rb(sf%int%par_index(j),c_sel)
        end do
        call sf%int%complete_kinematics &
            (sf%x, sf%f(c_sel), sf%r(:,c_sel), sf%rb(:,c_sel), &
             sf%m(c_sel))
        do j = 1, size(sf%x)
            chain%x(sf%int%par_index(j)) = sf%x(j)
        end do
        if (sf%int%status <= SF_FAILED_KINEMATICS) then
            chain%status = SF_FAILED_KINEMATICS
            return
        end if
        do c = 1, size(sf%f)
            if (c /= c_sel) then
                call sf%int%inverse_kinematics &
                    (sf%x, sf%f(c), sf%r(:,c), sf%rb(:,c), sf%m(c))
                do j = 1, size(sf%x)
                    chain%r(sf%int%par_index(j),c) = sf%r(j,c)
                    chain%rb(sf%int%par_index(j),c) = sf%rb(j,c)
                end do
            end if
            chain%f(c) = chain%f(c) * sf%f(c)
        end do
        if (.not. sf%eval%is_empty()) then
            call sf%eval%receive_momenta()
        end if
    end associate
end do
do c = 1, size(chain%f)
    if (c /= c_sel) then
        if (allocated(chain%channel(c)%multi_mapping)) then
            call chain%channel(c)%multi_mapping%inverse &
                (chain%r(:,c), chain%rb(:,c), &
                 f_mapping, &
                 chain%p(:,c), chain%pb(:,c), &
                 chain%x_free)
            chain%f(c) = chain%f(c) * f_mapping
        else
            chain%p(:,c) = chain%r(:,c)
            chain%pb(:,c) = chain%rb(:,c)
        end if
    end if
end do
end do

```

```

        end if
    end if
    chain%status = SF_DONE_KINEMATICS
end if
end subroutine sf_chain_instance_compute_kinematics

```

This is a variant of the previous procedure. We know the x parameters and reconstruct the momenta and the MC input parameters p . We do not need to select a channel.

Note: this is probably redundant, since the method we actually want starts from the momenta, recovers all x parameters, and then inverts mappings. See below `recover_kinematics`.

```

<SF base: sf chain instance: TBP>+≡
    procedure :: inverse_kinematics => sf_chain_instance_inverse_kinematics
<SF base: procedures>+≡
    subroutine sf_chain_instance_inverse_kinematics (chain, x)
        class(sf_chain_instance_t), intent(inout), target :: chain
        real(default), dimension(:), intent(in) :: x
        type(interaction_t), pointer :: int
        real(default) :: f_mapping
        integer :: i, j, c
        if (chain%status >= SF_DONE_CONNECTIONS) then
            call chain%select_channel ()
            int => beam_get_int_ptr (chain%beam_t)
            call int%receive_momenta ()
            if (allocated (chain%sf)) then
                chain%f = 1
                if (size (chain%sf) /= 0) then
                    forall (i = 1:size (chain%sf)) chain%sf(i)%int%status = SF_INITIAL
                    chain%x = x
                    do i = 1, size (chain%sf)
                        associate (sf => chain%sf(i))
                            call sf%int%seed_kinematics ()
                            do j = 1, size (sf%x)
                                sf%x(j) = chain%x(sf%int%par_index(j))
                            end do
                            do c = 1, size (sf%f)
                                call sf%int%inverse_kinematics &
                                    (sf%x, sf%f(c), sf%r(:,c), sf%rb(:,c), sf%m(c), c==1)
                                chain%f(c) = chain%f(c) * sf%f(c)
                                do j = 1, size (sf%x)
                                    chain%r (sf%int%par_index(j),c) = sf%r (j,c)
                                    chain%rb(sf%int%par_index(j),c) = sf%rb(j,c)
                                end do
                            end do
                            if (.not. sf%eval%is_empty ()) then
                                call sf%eval%receive_momenta ()
                            end if
                        end associate
                    end do
                    do c = 1, size (chain%f)
                        if (allocated (chain%channel(c)%multi_mapping)) then
                            call chain%channel(c)%multi_mapping%inverse &

```

```

        (chain%r(:,c), chain%rb(:,c), &
        f_mapping, &
        chain%p(:,c), chain%pb(:,c), &
        chain%x_free)
        chain%f(c) = chain%f(c) * f_mapping
    else
        chain%p(:,c) = chain%r(:,c)
        chain%pb(:,c) = chain%rb(:,c)
    end if
end do
end if
end if
chain%status = SF_DONE_KINEMATICS
end if
end subroutine sf_chain_instance_inverse_kinematics

```

Recover the kinematics: assuming that the last evaluator has been filled with a valid set of momenta, we travel the momentum links backwards and fill the preceding evaluators and, as a side effect, interactions. We stop at the beam interaction.

After all momenta are set, apply the `inverse_kinematics` procedure above, suitably modified, to recover the x and p parameters and the Jacobian factors.

The `c_sel` (channel) argument is just used to mark a selected channel for the records, otherwise the recovery procedure is independent of this.

(SF base: sf chain instance: TBP)+≡

```

procedure :: recover_kinematics => sf_chain_instance_recover_kinematics

```

(SF base: procedures)+≡

```

subroutine sf_chain_instance_recover_kinematics (chain, c_sel)
    class(sf_chain_instance_t), intent(inout), target :: chain
    integer, intent(in) :: c_sel
    real(default) :: f_mapping
    integer :: i, j, c
    if (chain%status >= SF_DONE_CONNECTIONS) then
        call chain%select_channel (c_sel)
        if (allocated (chain%sf)) then
            do i = size (chain%sf), 1, -1
                associate (sf => chain%sf(i))
                    if (.not. sf%eval%is_empty ()) then
                        call interaction_send_momenta (sf%eval%interaction_t)
                    end if
                end associate
            end do
            chain%f = 1
            if (size (chain%sf) /= 0) then
                forall (i = 1:size (chain%sf)) chain%sf(i)%int%status = SF_INITIAL
                chain%x_free = 1
                do i = 1, size (chain%sf)
                    associate (sf => chain%sf(i))
                        call sf%int%seed_kinematics ()
                        call sf%int%recover_x (sf%x, chain%x_free)
                        do j = 1, size (sf%x)
                            chain%x(sf%int%par_index(j)) = sf%x(j)
                        end do
                    end associate
                end do
            end if
        end if
    end if
end subroutine sf_chain_instance_recover_kinematics

```

```

        end do
        do c = 1, size (sf%f)
            call sf%int%inverse_kinematics &
                (sf%x, sf%f(c), sf%r(:,c), sf%rb(:,c), sf%m(c), c==1)
            chain%f(c) = chain%f(c) * sf%f(c)
            do j = 1, size (sf%x)
                chain%r (sf%int%par_index(j),c) = sf%r (j,c)
                chain%rb(sf%int%par_index(j),c) = sf%rb(j,c)
            end do
        end do
    end associate
end do
do c = 1, size (chain%f)
    if (allocated (chain%channel(c)%multi_mapping)) then
        call chain%channel(c)%multi_mapping%inverse &
            (chain%r(:,c), chain%rb(:,c), &
            f_mapping, &
            chain%p(:,c), chain%pb(:,c), &
            chain%x_free)
        chain%f(c) = chain%f(c) * f_mapping
    else
        chain%p(:,c) = chain%r(:,c)
        chain%pb(:,c) = chain%rb(:,c)
    end if
end do
end if
chain%status = SF_DONE_KINEMATICS
end if
end subroutine sf_chain_instance_recover_kinematics

```

Return the initial beam momenta to their source, thus completing kinematics recovery. Obviously, this works as a side effect.

```

<SF base: sf chain instance: TBP>+≡
    procedure :: return_beam_momenta => sf_chain_instance_return_beam_momenta

<SF base: procedures>+≡
    subroutine sf_chain_instance_return_beam_momenta (chain)
        class(sf_chain_instance_t), intent(in), target :: chain
        type(interaction_t), pointer :: int
        if (chain%status >= SF_DONE_KINEMATICS) then
            int => beam_get_int_ptr (chain%beam_t)
            call interaction_send_momenta (int)
        end if
    end subroutine sf_chain_instance_return_beam_momenta

```

Evaluate all interactions in the chain and the product evaluators. We provide a `scale` argument that is given to all structure functions in the chain.

```

<SF base: sf chain instance: TBP>+≡
    procedure :: evaluate => sf_chain_instance_evaluate

<SF base: procedures>+≡
    subroutine sf_chain_instance_evaluate (chain, scale)
        class(sf_chain_instance_t), intent(inout), target :: chain

```



```

real(default), intent(in) :: scale
type(interaction_t), pointer :: out_int
real(default) :: sf_sum
integer :: i
if (chain%status >= SF_DONE_KINEMATICS) then
  if (allocated (chain%sf)) then
    if (size (chain%sf) /= 0) then
      do i = 1, size (chain%sf)
        associate (sf => chain%sf(i))
          call sf%int%apply (scale)
          if (sf%int%status <= SF_FAILED_EVALUATION) then
            chain%status = SF_FAILED_EVALUATION
            return
          end if
          if (.not. sf%eval%is_empty ()) then
            call sf%eval%evaluate ()
          end if
        end associate
      end do
      out_int => chain%get_out_int_ptr ()
      sf_sum = out_int%sum ()
      call chain%config%trace &
        (chain%selected_channel, chain%p, chain%x, chain%f, sf_sum)
    end if
  end if
  chain%status = SF_EVALUATED
end if
end subroutine sf_chain_instance_evaluate

```

15.5.9 Access to the chain instance

Transfer the outgoing momenta to the array p. We assume that array sizes match.

```

<SF base: sf chain instance: TBP>+≡
  procedure :: get_out_momenta => sf_chain_instance_get_out_momenta

<SF base: procedures>+≡
  subroutine sf_chain_instance_get_out_momenta (chain, p)
    class(sf_chain_instance_t), intent(in), target :: chain
    type(vector4_t), dimension(:), intent(out) :: p
    type(interaction_t), pointer :: int
    integer :: i, j
    if (chain%status >= SF_DONE_KINEMATICS) then
      do j = 1, size (chain%out_sf)
        i = chain%out_sf(j)
        select case (i)
          case (0)
            int => beam_get_int_ptr (chain%beam_t)
          case default
            int => chain%sf(i)%int%interaction_t
        end select
        p(j) = int%get_momentum (chain%out_sf_i(j))
      end do
    end if
  end subroutine

```

```

        end if
    end subroutine sf_chain_instance_get_out_momenta

```

Return a pointer to the last evaluator in the chain (to the interaction).

```

⟨SF base: sf chain instance: TBP⟩+≡
    procedure :: get_out_int_ptr => sf_chain_instance_get_out_int_ptr

⟨SF base: procedures⟩+≡
    function sf_chain_instance_get_out_int_ptr (chain) result (int)
        class(sf_chain_instance_t), intent(in), target :: chain
        type(interaction_t), pointer :: int
        if (chain%out_eval == 0) then
            int => beam_get_int_ptr (chain%beam_t)
        else
            int => chain%sf(chain%out_eval)%eval%interaction_t
        end if
    end function sf_chain_instance_get_out_int_ptr

```

Return the index of the j-th outgoing particle, within the last evaluator.

```

⟨SF base: sf chain instance: TBP⟩+≡
    procedure :: get_out_i => sf_chain_instance_get_out_i

⟨SF base: procedures⟩+≡
    function sf_chain_instance_get_out_i (chain, j) result (i)
        class(sf_chain_instance_t), intent(in) :: chain
        integer, intent(in) :: j
        integer :: i
        i = chain%out_eval_i(j)
    end function sf_chain_instance_get_out_i

```

Return the mask for the outgoing particle(s), within the last evaluator.

```

⟨SF base: sf chain instance: TBP⟩+≡
    procedure :: get_out_mask => sf_chain_instance_get_out_mask

⟨SF base: procedures⟩+≡
    function sf_chain_instance_get_out_mask (chain) result (mask)
        class(sf_chain_instance_t), intent(in), target :: chain
        type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
        type(interaction_t), pointer :: int
        allocate (mask (chain%config%n_in))
        int => chain%get_out_int_ptr ()
        mask = int%get_mask (chain%out_eval_i)
    end function sf_chain_instance_get_out_mask

```

Return the array of MC input parameters that corresponds to channel c. This is the p array, the parameters before all mappings.

The p array may be deallocated. This should correspond to a zero-size r argument, so nothing to do then.

```

⟨SF base: sf chain instance: TBP⟩+≡
    procedure :: get_mcpair => sf_chain_instance_get_mcpair

```

```

<SF base: procedures>+=
  subroutine sf_chain_instance_get_mcpair (chain, c, r)
    class(sf_chain_instance_t), intent(in) :: chain
    integer, intent(in) :: c
    real(default), dimension(:), intent(out) :: r
    if (allocated (chain%p)) r = pack (chain%p(:,c), chain%bound)
  end subroutine sf_chain_instance_get_mcpair

```

Return the Jacobian factor that corresponds to channel c.

```

<SF base: sf chain instance: TBP>+=
  procedure :: get_f => sf_chain_instance_get_f

<SF base: procedures>+=
  function sf_chain_instance_get_f (chain, c) result (f)
    class(sf_chain_instance_t), intent(in) :: chain
    integer, intent(in) :: c
    real(default) :: f
    if (allocated (chain%f)) then
      f = chain%f(c)
    else
      f = 1
    end if
  end function sf_chain_instance_get_f

```

Return the evaluation status.

```

<SF base: sf chain instance: TBP>+=
  procedure :: get_status => sf_chain_instance_get_status

<SF base: procedures>+=
  function sf_chain_instance_get_status (chain) result (status)
    class(sf_chain_instance_t), intent(in) :: chain
    integer :: status
    status = chain%status
  end function sf_chain_instance_get_status

```

15.5.10 Unit tests

```

<SF base: public>+=
  public :: sf_base_test

<SF base: tests>=
  subroutine sf_base_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <SF base: execute tests>
  end subroutine sf_base_test

```

15.5.11 Test implementation: structure function

This is a template for the actual structure-function implementation which will be defined in separate modules.

Configuration data

The test structure function uses the `Test` model. It describes a scalar within an arbitrary initial particle, which is given in the initialization. The radiated particle is also a scalar, the same one, but we set its mass artificially to zero.

```
<SF base: public>+=  
    public :: sf_test_data_t  
  
<SF base: test types>=  
    type, extends (sf_data_t) :: sf_test_data_t  
        class(model_data_t), pointer :: model => null ()  
        integer :: mode = 0  
        type(flavor_t) :: flv_in  
        type(flavor_t) :: flv_out  
        type(flavor_t) :: flv_rad  
        real(default) :: m = 0  
        logical :: collinear = .true.  
        real(default), dimension(:), allocatable :: qbounds  
        contains  
        <SF base: sf test data: TBP>  
    end type sf_test_data_t
```

Output.

```
<SF base: sf test data: TBP>=  
    procedure :: write => sf_test_data_write  
  
<SF base: procedures>+=  
    subroutine sf_test_data_write (data, unit, verbose)  
        class(sf_test_data_t), intent(in) :: data  
        integer, intent(in), optional :: unit  
        logical, intent(in), optional :: verbose  
        integer :: u  
        u = given_output_unit (unit)  
        write (u, "(1x,A)") "SF test data:"  
        write (u, "(3x,A,A)") "model      = ", char (data%model%get_name ())  
        write (u, "(3x,A)", advance="no") "incoming  = "  
        call data%flv_in%write (u); write (u, *)  
        write (u, "(3x,A)", advance="no") "outgoing  = "  
        call data%flv_out%write (u); write (u, *)  
        write (u, "(3x,A)", advance="no") "radiated  = "  
        call data%flv_rad%write (u); write (u, *)  
        write (u, "(3x,A," // FMT_19 // ")") "mass      = ", data%m  
        write (u, "(3x,A,L1)") "collinear = ", data%collinear  
        if (.not. data%collinear .and. allocated (data%qbounds)) then  
            write (u, "(3x,A," // FMT_19 // ")") "qmin      = ", data%qbounds(1)  
            write (u, "(3x,A," // FMT_19 // ")") "qmax      = ", data%qbounds(2)  
        end if  
    end subroutine sf_test_data_write
```

Initialization.

```
<SF base: sf test data: TBP>+=  
    procedure :: init => sf_test_data_init
```

<SF base: procedures>+≡

```

subroutine sf_test_data_init (data, model, pdg_in, collinear, qbounds, mode)
  class(sf_test_data_t), intent(out) :: data
  class(model_data_t), intent(in), target :: model
  type(pdg_array_t), intent(in) :: pdg_in
  logical, intent(in), optional :: collinear
  real(default), dimension(2), intent(in), optional :: qbounds
  integer, intent(in), optional :: mode
  data%model => model
  if (present (mode)) data%mode = mode
  if (pdg_array_get (pdg_in, 1) /= 25) then
    call msg_fatal ("Test spectrum function: input flavor must be 's'")
  end if
  call data%flv_in%init (25, model)
  data%m = data%flv_in%get_mass ()
  if (present (collinear)) data%collinear = collinear
  call data%flv_out%init (25, model)
  call data%flv_rad%init (25, model)
  if (present (qbounds)) then
    allocate (data%qbounds (2))
    data%qbounds = qbounds
  end if
end subroutine sf_test_data_init

```

Return the number of parameters: 1 if only consider collinear splitting, 3 otherwise.

<SF base: sf test data: TBP>+≡

```

procedure :: get_n_par => sf_test_data_get_n_par

```

<SF base: procedures>+≡

```

function sf_test_data_get_n_par (data) result (n)
  class(sf_test_data_t), intent(in) :: data
  integer :: n
  if (data%collinear) then
    n = 1
  else
    n = 3
  end if
end function sf_test_data_get_n_par

```

Return the outgoing particle PDG code: 25

<SF base: sf test data: TBP>+≡

```

procedure :: get_pdg_out => sf_test_data_get_pdg_out

```

<SF base: procedures>+≡

```

subroutine sf_test_data_get_pdg_out (data, pdg_out)
  class(sf_test_data_t), intent(in) :: data
  type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
  pdg_out(1) = 25
end subroutine sf_test_data_get_pdg_out

```

Allocate the matching interaction.

<SF base: sf test data: TBP>+≡

```

procedure :: allocate_sf_int => sf_test_data_allocate_sf_int

```

```

<SF base: procedures>+=
  subroutine sf_test_data_allocate_sf_int (data, sf_int)
    class(sf_test_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (sf_test_t :: sf_int)
  end subroutine sf_test_data_allocate_sf_int

```

Interaction

```

<SF base: test types>+=
  type, extends (sf_int_t) :: sf_test_t
    type(sf_test_data_t), pointer :: data => null ()
    real(default) :: x = 0
  contains
    <SF base: sf test int: TBP>
  end type sf_test_t

```

Type string: constant

```

<SF base: sf test int: TBP>=
  procedure :: type_string => sf_test_type_string

```

```

<SF base: procedures>+=
  function sf_test_type_string (object) result (string)
    class(sf_test_t), intent(in) :: object
    type(string_t) :: string
    string = "Test"
  end function sf_test_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF base: sf test int: TBP>+=
  procedure :: write => sf_test_write

<SF base: procedures>+=
  subroutine sf_test_write (object, unit, testflag)
    class(sf_test_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      call object%base_write (u, testflag)
    else
      write (u, "(1x,A)") "SF test data: [undefined]"
    end if
  end subroutine sf_test_write

```

Initialize. We know that `data` will be of concrete type `sf_test_data_t`, but we have to cast this explicitly.

For this implementation, we set the incoming and outgoing masses equal to the physical particle mass, but keep the radiated mass zero.

Optionally, we can provide minimum and maximum values for the momentum transfer.

```

<SF base: sf test int: TBP>+=
  procedure :: init => sf_test_init

<SF base: procedures>+=
  subroutine sf_test_init (sf_int, data)
    class(sf_test_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(3) :: mask
    type(helicity_t) :: hel0
    type(color_t) :: col0
    type(quantum_numbers_t), dimension(3) :: qn
    mask = quantum_numbers_mask (.false., .false., .false.)
    select type (data)
    type is (sf_test_data_t)
      if (allocated (data%qbounds)) then
        call sf_int%base_init (mask, &
          [data%m**2], [0._default], [data%m**2], &
          [data%qbounds(1)], [data%qbounds(2)])
      else
        call sf_int%base_init (mask, &
          [data%m**2], [0._default], [data%m**2])
      end if
      sf_int%data => data
      call hel0%init (0)
      call col0%init ()
      call qn(1)%init (data%flv_in, col0, hel0)
      call qn(2)%init (data%flv_rad, col0, hel0)
      call qn(3)%init (data%flv_out, col0, hel0)
      call sf_int%add_state (qn)
      call sf_int%freeze ()
      call sf_int%set_incoming ([1])
      call sf_int%set_radiated ([2])
      call sf_int%set_outgoing ([3])
    end select
    sf_int%status = SF_INITIAL
  end subroutine sf_test_init

```

Set kinematics. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ is trivial.

If `map` is set, we are asked to provide an efficient mapping. For the test case, we set $x = r^2$ and consequently $f(r) = 2r$.

```

<SF base: sf test int: TBP>+=
  procedure :: complete_kinematics => sf_test_complete_kinematics

<SF base: procedures>+=
  subroutine sf_test_complete_kinematics (sf_int, x, f, r, rb, map)
    class(sf_test_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: r
    real(default), dimension(:), intent(in) :: rb
    logical, intent(in) :: map

```

```

real(default) :: xb1
if (map) then
  x(1) = r(1)**2
  f = 2 * r(1)
else
  x(1) = r(1)
  f = 1
end if
xb1 = 1 - x(1)
if (size (x) == 3) x(2:3) = r(2:3)
call sf_int%split_momentum (x, xb1)
sf_int%x = x(1)
select case (sf_int%status)
case (SF_FAILED_KINEMATICS); f = 0
end select
end subroutine sf_test_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

<SF base: sf test int: TBP>+≡
  procedure :: inverse_kinematics => sf_test_inverse_kinematics

<SF base: procedures>+≡
subroutine sf_test_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
  class(sf_test_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(in) :: x
  real(default), intent(out) :: f
  real(default), dimension(:), intent(out) :: r
  real(default), dimension(:), intent(out) :: rb
  logical, intent(in) :: map
  logical, intent(in), optional :: set_momenta
  real(default) :: xb1
  logical :: set_mom
  set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
  if (map) then
    r(1) = sqrt (x(1))
    f = 2 * r(1)
  else
    r(1) = x(1)
    f = 1
  end if
  xb1 = 1 - x(1)
  if (size (x) == 3) r(2:3) = x(2:3)
  rb = 1 - r
  sf_int%x = x(1)
  if (set_mom) then
    call sf_int%split_momentum (x, xb1)
    select case (sf_int%status)
    case (SF_FAILED_KINEMATICS); f = 0
    end select
  end if
end subroutine sf_test_inverse_kinematics

```


Apply the structure function. The matrix element becomes unity and the application always succeeds.

If the `mode` indicator is one, the matrix element is equal to the parameter x .

```

<SF base: sf test int: TBP>+≡
  procedure :: apply => sf_test_apply

<SF base: procedures>+≡
  subroutine sf_test_apply (sf_int, scale)
    class(sf_test_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    select case (sf_int%data%mode)
    case (0)
      call sf_int%set_matrix_element &
        (cmplx (1._default, kind=default))
    case (1)
      call sf_int%set_matrix_element &
        (cmplx (sf_int%x, kind=default))
    end select
    sf_int%status = SF_EVALUATED
  end subroutine sf_test_apply

```

15.5.12 Test implementation: pair spectrum

Another template, this time for a incoming particle pair, splitting into two radiated and two outgoing particles.

Configuration data

For simplicity, the spectrum contains two mirror images of the previous structure-function configuration: the incoming and all outgoing particles are test scalars.

We have two versions, one with radiated particles, one without.

```

<SF base: test types>+≡
  type, extends (sf_data_t) :: sf_test_spectrum_data_t
    class(model_data_t), pointer :: model => null ()
    type(flavor_t) :: flv_in
    type(flavor_t) :: flv_out
    type(flavor_t) :: flv_rad
    logical :: with_radiation = .true.
    real(default) :: m = 0
  contains
    <SF base: sf test spectrum data: TBP>
  end type sf_test_spectrum_data_t

```

Output.

```

<SF base: sf test spectrum data: TBP>≡
  procedure :: write => sf_test_spectrum_data_write

<SF base: procedures>+≡
  subroutine sf_test_spectrum_data_write (data, unit, verbose)
    class(sf_test_spectrum_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose

```

```

integer :: u
u = given_output_unit (unit)
write (u, "(1x,A)") "SF test spectrum data:"
write (u, "(3x,A,A)") "model      = ", char (data%model%get_name ())
write (u, "(3x,A)", advance="no") "incoming  = "
call data%flv_in%write (u); write (u, *)
write (u, "(3x,A)", advance="no") "outgoing  = "
call data%flv_out%write (u); write (u, *)
write (u, "(3x,A)", advance="no") "radiated  = "
call data%flv_rad%write (u); write (u, *)
write (u, "(3x,A," // FMT_19 // ")") "mass      = ", data%m
end subroutine sf_test_spectrum_data_write

```

Initialization.

```

<SF base: sf test spectrum data: TBP>+≡
  procedure :: init => sf_test_spectrum_data_init

<SF base: procedures>+≡
  subroutine sf_test_spectrum_data_init (data, model, pdg_in, with_radiation)
    class(sf_test_spectrum_data_t), intent(out) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), intent(in) :: pdg_in
    logical, intent(in) :: with_radiation
    data%model => model
    data%with_radiation = with_radiation
    if (pdg_array_get (pdg_in, 1) /= 25) then
      call msg_fatal ("Test structure function: input flavor must be 's'")
    end if
    call data%flv_in%init (25, model)
    data%m = data%flv_in%get_mass ()
    call data%flv_out%init (25, model)
    if (with_radiation) then
      call data%flv_rad%init (25, model)
    end if
  end subroutine sf_test_spectrum_data_init

```

Return the number of parameters: 2, since we have only collinear splitting here.

```

<SF base: sf test spectrum data: TBP>+≡
  procedure :: get_n_par => sf_test_spectrum_data_get_n_par

<SF base: procedures>+≡
  function sf_test_spectrum_data_get_n_par (data) result (n)
    class(sf_test_spectrum_data_t), intent(in) :: data
    integer :: n
    n = 2
  end function sf_test_spectrum_data_get_n_par

```

Return the outgoing particle PDG codes: 25

```

<SF base: sf test spectrum data: TBP>+≡
  procedure :: get_pdg_out => sf_test_spectrum_data_get_pdg_out

<SF base: procedures>+≡
  subroutine sf_test_spectrum_data_get_pdg_out (data, pdg_out)
    class(sf_test_spectrum_data_t), intent(in) :: data

```

```

        type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
        pdg_out(1) = 25
        pdg_out(2) = 25
    end subroutine sf_test_spectrum_data_get_pdg_out

```

Allocate the matching interaction.

```

<SF base: sf test spectrum data: TBP>+≡
    procedure :: allocate_sf_int => &
        sf_test_spectrum_data_allocate_sf_int

<SF base: procedures>+≡
    subroutine sf_test_spectrum_data_allocate_sf_int (data, sf_int)
        class(sf_test_spectrum_data_t), intent(in) :: data
        class(sf_int_t), intent(inout), allocatable :: sf_int
        allocate (sf_test_spectrum_t :: sf_int)
    end subroutine sf_test_spectrum_data_allocate_sf_int

```

Interaction

```

<SF base: test types>+≡
    type, extends (sf_int_t) :: sf_test_spectrum_t
        type(sf_test_spectrum_data_t), pointer :: data => null ()
        contains
        <SF base: sf test spectrum: TBP>
    end type sf_test_spectrum_t

<SF base: sf test spectrum: TBP>≡
    procedure :: type_string => sf_test_spectrum_type_string

<SF base: procedures>+≡
    function sf_test_spectrum_type_string (object) result (string)
        class(sf_test_spectrum_t), intent(in) :: object
        type(string_t) :: string
        string = "Test Spectrum"
    end function sf_test_spectrum_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF base: sf test spectrum: TBP>+≡
    procedure :: write => sf_test_spectrum_write

<SF base: procedures>+≡
    subroutine sf_test_spectrum_write (object, unit, testflag)
        class(sf_test_spectrum_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: testflag
        integer :: u
        u = given_output_unit (unit)
        if (associated (object%data)) then
            call object%data%write (u)
            call object%base_write (u, testflag)
        else
            write (u, "(1x,A)") "SF test spectrum data: [undefined]"
        end if
    end subroutine sf_test_spectrum_write

```

```

end if
end subroutine sf_test_spectrum_write

```

Initialize. We know that `data` will be of concrete type `sf_test_spectrum_data_t`, but we have to cast this explicitly.

For this implementation, we set the incoming and outgoing masses equal to the physical particle mass, but keep the radiated mass zero.

Optionally, we can provide minimum and maximum values for the momentum transfer.

```

⟨SF base: sf test spectrum: TBP⟩+=
  procedure :: init => sf_test_spectrum_init

⟨SF base: procedures⟩+=
  subroutine sf_test_spectrum_init (sf_int, data)
    class(sf_test_spectrum_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(6) :: mask
    type(helicity_t) :: hel0
    type(color_t) :: col0
    type(quantum_numbers_t), dimension(6) :: qn
    mask = quantum_numbers_mask (.false., .false., .false.)
    select type (data)
    type is (sf_test_spectrum_data_t)
      if (data%with_radiation) then
        call sf_int%base_init (mask(1:6), &
          [data%m**2, data%m**2], &
          [0._default, 0._default], &
          [data%m**2, data%m**2])
        sf_int%data => data
        call hel0%init (0)
        call col0%init ()
        call qn(1)%init (data%flv_in, col0, hel0)
        call qn(2)%init (data%flv_in, col0, hel0)
        call qn(3)%init (data%flv_rad, col0, hel0)
        call qn(4)%init (data%flv_rad, col0, hel0)
        call qn(5)%init (data%flv_out, col0, hel0)
        call qn(6)%init (data%flv_out, col0, hel0)
        call sf_int%add_state (qn(1:6))
        call sf_int%set_incoming ([1,2])
        call sf_int%set_radiated ([3,4])
        call sf_int%set_outgoing ([5,6])
      else
        call sf_int%base_init (mask(1:4), &
          [data%m**2, data%m**2], &
          [real(default) :: ], &
          [data%m**2, data%m**2])
        sf_int%data => data
        call hel0%init (0)
        call col0%init ()
        call qn(1)%init (data%flv_in, col0, hel0)
        call qn(2)%init (data%flv_in, col0, hel0)
        call qn(3)%init (data%flv_out, col0, hel0)
        call qn(4)%init (data%flv_out, col0, hel0)
        call sf_int%add_state (qn(1:4))
      end if
    end select
  end subroutine

```

```

        call sf_int%set_incoming ([1,2])
        call sf_int%set_outgoing ([3,4])
    end if
    call sf_int%freeze ()
end select
sf_int%status = SF_INITIAL
end subroutine sf_test_spectrum_init

```

Set kinematics. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ is trivial.

If `map` is set, we are asked to provide an efficient mapping. For the test case, we set $x = r^2$ (as above) for both x parameters and consequently $f(r) = 4r_1r_2$.

```

<SF base: sf test spectrum: TBP>+≡
    procedure :: complete_kinematics => sf_test_spectrum_complete_kinematics

<SF base: procedures>+≡
    subroutine sf_test_spectrum_complete_kinematics (sf_int, x, f, r, rb, map)
        class(sf_test_spectrum_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: x
        real(default), intent(out) :: f
        real(default), dimension(:), intent(in) :: r
        real(default), dimension(:), intent(in) :: rb
        logical, intent(in) :: map
        real(default), dimension(2) :: xb1
        if (map) then
            x = r**2
            f = 4 * r(1) * r(2)
        else
            x = r
            f = 1
        end if
        if (sf_int%data%with_radiation) then
            xb1 = 1 - x
            call sf_int%split_momenta (x, xb1)
        else
            call sf_int%reduce_momenta (x)
        end if
        select case (sf_int%status)
        case (SF_FAILED_KINEMATICS); f = 0
        end select
    end subroutine sf_test_spectrum_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

<SF base: sf test spectrum: TBP>+≡
    procedure :: inverse_kinematics => sf_test_spectrum_inverse_kinematics

<SF base: procedures>+≡
    subroutine sf_test_spectrum_inverse_kinematics &
        (sf_int, x, f, r, rb, map, set_momenta)
        class(sf_test_spectrum_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(in) :: x

```

```

real(default), intent(out) :: f
real(default), dimension(:), intent(out) :: r
real(default), dimension(:), intent(out) :: rb
logical, intent(in) :: map
logical, intent(in), optional :: set_momenta
real(default), dimension(2) :: xb1
logical :: set_mom
set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
if (map) then
  r = sqrt (x)
  f = 4 * r(1) * r(2)
else
  r = x
  f = 1
end if
rb = 1 - r
if (set_mom) then
  if (sf_int%data%with_radiation) then
    xb1 = 1 - x
    call sf_int%split_momenta (x, xb1)
  else
    call sf_int%reduce_momenta (x)
  end if
  select case (sf_int%status)
  case (SF_FAILED_KINEMATICS); f = 0
  end select
end if
end subroutine sf_test_spectrum_inverse_kinematics

```

Apply the structure function. The matrix element becomes unity and the application always succeeds.

```

<SF base: sf test spectrum: TBP>+≡
  procedure :: apply => sf_test_spectrum_apply

<SF base: procedures>+≡
  subroutine sf_test_spectrum_apply (sf_int, scale)
    class(sf_test_spectrum_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    call sf_int%set_matrix_element &
      (cmplx (1._default, kind=default))
    sf_int%status = SF_EVALUATED
  end subroutine sf_test_spectrum_apply

```

15.5.13 Test implementation: generator spectrum

A generator for two beams, no radiation (for simplicity).

Configuration data

For simplicity, the spectrum contains two mirror images of the previous structure-function configuration: the incoming and all outgoing particles are test scalars.

We have two versions, one with radiated particles, one without.

```

<SF base: test types>+≡
type, extends (sf_data_t) :: sf_test_generator_data_t
  class(model_data_t), pointer :: model => null ()
  type(flavor_t) :: flv_in
  type(flavor_t) :: flv_out
  type(flavor_t) :: flv_rad
  real(default) :: m = 0
contains
  <SF base: sf test generator data: TBP>
end type sf_test_generator_data_t

```

Output.

```

<SF base: sf test generator data: TBP>≡
  procedure :: write => sf_test_generator_data_write

<SF base: procedures>+≡
  subroutine sf_test_generator_data_write (data, unit, verbose)
    class(sf_test_generator_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "SF test generator data:"
    write (u, "(3x,A,A)") "model      = ", char (data%model%get_name ())
    write (u, "(3x,A)", advance="no") "incoming  = "
    call data%flv_in%write (u); write (u, *)
    write (u, "(3x,A)", advance="no") "outgoing  = "
    call data%flv_out%write (u); write (u, *)
    write (u, "(3x,A," // FMT_19 // ")") "mass      = ", data%m
  end subroutine sf_test_generator_data_write

```

Initialization.

```

<SF base: sf test generator data: TBP>+≡
  procedure :: init => sf_test_generator_data_init

<SF base: procedures>+≡
  subroutine sf_test_generator_data_init (data, model, pdg_in)
    class(sf_test_generator_data_t), intent(out) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), intent(in) :: pdg_in
    data%model => model
    if (pdg_array_get (pdg_in, 1) /= 25) then
      call msg_fatal ("Test generator: input flavor must be 's'")
    end if
    call data%flv_in%init (25, model)
    data%m = data%flv_in%get_mass ()
    call data%flv_out%init (25, model)
  end subroutine sf_test_generator_data_init

```

This structure function is a generator.

```

<SF base: sf test generator data: TBP>+≡
  procedure :: is_generator => sf_test_generator_data_is_generator

```

```

<SF base: procedures>+≡
function sf_test_generator_data_is_generator (data) result (flag)
  class(sf_test_generator_data_t), intent(in) :: data
  logical :: flag
  flag = .true.
end function sf_test_generator_data_is_generator

```

Return the number of parameters: 2, since we have only collinear splitting here.

```

<SF base: sf test generator data: TBP>+≡
procedure :: get_n_par => sf_test_generator_data_get_n_par

<SF base: procedures>+≡
function sf_test_generator_data_get_n_par (data) result (n)
  class(sf_test_generator_data_t), intent(in) :: data
  integer :: n
  n = 2
end function sf_test_generator_data_get_n_par

```

Return the outgoing particle PDG codes: 25

```

<SF base: sf test generator data: TBP>+≡
procedure :: get_pdg_out => sf_test_generator_data_get_pdg_out

<SF base: procedures>+≡
subroutine sf_test_generator_data_get_pdg_out (data, pdg_out)
  class(sf_test_generator_data_t), intent(in) :: data
  type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
  pdg_out(1) = 25
  pdg_out(2) = 25
end subroutine sf_test_generator_data_get_pdg_out

```

Allocate the matching interaction.

```

<SF base: sf test generator data: TBP>+≡
procedure :: allocate_sf_int => &
  sf_test_generator_data_allocate_sf_int

<SF base: procedures>+≡
subroutine sf_test_generator_data_allocate_sf_int (data, sf_int)
  class(sf_test_generator_data_t), intent(in) :: data
  class(sf_int_t), intent(inout), allocatable :: sf_int
  allocate (sf_test_generator_t :: sf_int)
end subroutine sf_test_generator_data_allocate_sf_int

```

Interaction

```

<SF base: test types>+≡
type, extends (sf_int_t) :: sf_test_generator_t
  type(sf_test_generator_data_t), pointer :: data => null ()
  contains
  <SF base: sf test generator: TBP>
end type sf_test_generator_t

```



```

<SF base: sf test generator: TBP>+=
  procedure :: type_string => sf_test_generator_type_string

<SF base: procedures>+=
  function sf_test_generator_type_string (object) result (string)
    class(sf_test_generator_t), intent(in) :: object
    type(string_t) :: string
    string = "Test Generator"
  end function sf_test_generator_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF base: sf test generator: TBP>+=
  procedure :: write => sf_test_generator_write

<SF base: procedures>+=
  subroutine sf_test_generator_write (object, unit, testflag)
    class(sf_test_generator_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      call object%base_write (u, testflag)
    else
      write (u, "(1x,A)") "SF test generator data: [undefined]"
    end if
  end subroutine sf_test_generator_write

```

Initialize. We know that data will be of concrete type `sf_test_generator_data_t`, but we have to cast this explicitly.

For this implementation, we set the incoming and outgoing masses equal to the physical particle mass. No radiation.

```

<SF base: sf test generator: TBP>+=
  procedure :: init => sf_test_generator_init

<SF base: procedures>+=
  subroutine sf_test_generator_init (sf_int, data)
    class(sf_test_generator_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(4) :: mask
    type(helicity_t) :: hel0
    type(color_t) :: col0
    type(quantum_numbers_t), dimension(4) :: qn
    mask = quantum_numbers_mask (.false., .false., .false.)
    select type (data)
    type is (sf_test_generator_data_t)
      call sf_int%base_init (mask(1:4), &
        [data%m**2, data%m**2], &
        [real(default) :: ], &
        [data%m**2, data%m**2])
      sf_int%data => data
      call hel0%init (0)
      call col0%init ()
    end select
  end subroutine sf_test_generator_init

```

```

        call qn(1)%init (data%flv_in, col0, hel0)
        call qn(2)%init (data%flv_in, col0, hel0)
        call qn(3)%init (data%flv_out, col0, hel0)
        call qn(4)%init (data%flv_out, col0, hel0)
        call sf_int%add_state (qn(1:4))
        call sf_int%set_incoming ([1,2])
        call sf_int%set_outgoing ([3,4])
        call sf_int%freeze ()
    end select
    sf_int%status = SF_INITIAL
end subroutine sf_test_generator_init

```

This structure function is a generator.

```

<SF base: sf test generator: TBP>+≡
    procedure :: is_generator => sf_test_generator_is_generator

<SF base: procedures>+≡
    function sf_test_generator_is_generator (sf_int) result (flag)
        class(sf_test_generator_t), intent(in) :: sf_int
        logical :: flag
        flag = sf_int%data%is_generator ()
    end function sf_test_generator_is_generator

```

Generate free parameters. This mock generator always produces the nubmers 0.8 and 0.5.

```

<SF base: sf test generator: TBP>+≡
    procedure :: generate_free => sf_test_generator_generate_free

<SF base: procedures>+≡
    subroutine sf_test_generator_generate_free (sf_int, r, rb, x_free)
        class(sf_test_generator_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: r, rb
        real(default), intent(inout) :: x_free
        r = [0.8, 0.5]
        rb= 1 - r
        x_free = x_free * product (r)
    end subroutine sf_test_generator_generate_free

```

Recover momentum fractions. Since the x values are free, we also set the **x_free** parameter.

```

<SF base: sf test generator: TBP>+≡
    procedure :: recover_x => sf_test_generator_recover_x

<SF base: procedures>+≡
    subroutine sf_test_generator_recover_x (sf_int, x, x_free)
        class(sf_test_generator_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: x
        real(default), intent(inout), optional :: x_free
        call sf_int%base_recover_x (x)
        if (present (x_free)) x_free = x_free * product (x)
    end subroutine sf_test_generator_recover_x

```

Set kinematics. Since this is a generator, just transfer input to output.

```

(SF base: sf test generator: TBP)+≡
  procedure :: complete_kinematics => sf_test_generator_complete_kinematics

(SF base: procedures)+≡
  subroutine sf_test_generator_complete_kinematics (sf_int, x, f, r, rb, map)
    class(sf_test_generator_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: r
    real(default), dimension(:), intent(in) :: rb
    logical, intent(in) :: map
    x = r
    f = 1
    call sf_int%reduce_momenta (x)
  end subroutine sf_test_generator_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

(SF base: sf test generator: TBP)+≡
  procedure :: inverse_kinematics => sf_test_generator_inverse_kinematics

(SF base: procedures)+≡
  subroutine sf_test_generator_inverse_kinematics &
    (sf_int, x, f, r, rb, map, set_momenta)
    class(sf_test_generator_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    r = x
    rb = 1 - x
    f = 1
    if (set_mom) call sf_int%reduce_momenta (x)
  end subroutine sf_test_generator_inverse_kinematics

```

Apply the structure function. The matrix element becomes unity and the application always succeeds.

```

(SF base: sf test generator: TBP)+≡
  procedure :: apply => sf_test_generator_apply

(SF base: procedures)+≡
  subroutine sf_test_generator_apply (sf_int, scale)
    class(sf_test_generator_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    call sf_int%set_matrix_element &
      (cmplx (1._default, kind=default))
    sf_int%status = SF_EVALUATED
  end subroutine sf_test_generator_apply

```

Test structure function data

Construct and display a test structure function data object.

```
<SF base: execute tests>≡
  call test (sf_base_1, "sf_base_1", &
    "structure function configuration", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_1 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(pdg_array_t), dimension(1) :: pdg_out
    integer, dimension(:), allocatable :: pdg1
    class(sf_data_t), allocatable :: data

    write (u, "(A)")  "* Test output: sf_base_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &test structure function data"
    write (u, "(A)")

    call model%init_test ()
    pdg_in = 25

    allocate (sf_test_data_t :: data)
    select type (data)
    type is (sf_test_data_t)
      call data%init (model, pdg_in)
    end select

    call data%write (u)

    write (u, "(A)")

    write (u, "(1x,A)") "Outgoing particle code:"
    call data%get_pdg_out (pdg_out)
    pdg1 = pdg_out(1)
    write (u, "(2x,99(1x,I0))")  pdg1

    call model%final ()

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: sf_base_1"

  end subroutine sf_base_1
```

Test and probe structure function

Construct and display a structure function object based on the test structure function.

```
<SF base: execute tests>+≡
  call test (sf_base_2, "sf_base_2", &
```

```

        "structure function instance", &
        u, results)
<SF base: tests>+≡
subroutine sf_base_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_base_2"
    write (u, "(A)")  "* Purpose: initialize and fill &
        &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_test ()
    pdg_in = 25
    call flv%init (25, model)

    call reset_interaction_counter ()

    allocate (sf_test_data_t :: data)
    select type (data)
    type is (sf_test_data_t)
        call data%init (model, pdg_in)
    end select

    write (u, "(A)")  "* Initialize structure-function object"
    write (u, "(A)")

    call data%allocate_sf_int (sf_int)
    call sf_int%init (data)
    call sf_int%set_beam_index ([1])

    call sf_int%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize incoming momentum with E=500"
    write (u, "(A)")
    E = 500
    k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
    call vector4_write (k, u)
    call sf_int%seed_kinematics ([k])

    write (u, "(A)")

```

```

write (u, "(A)")  "* Set kinematics for x=0"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=1"
write (u, "(A)")

r = 1
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Set kinematics with mapping for r=0.8"
write (u, "(A)")

r = 0.8_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

```

```

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)

write (u, "(A,9(1x,F10.7))")  "x =", x

write (u, "(A)")
write (u, "(A)")  "* Compute inverse kinematics for x=0.64 and evaluate"
write (u, "(A)")

x = 0.64_default
call sf_int%inverse_kinematics (x, f, r, rb, map=.true.)
call sf_int%apply (scale=0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_2"

end subroutine sf_base_2

```

Collinear kinematics

Scan over the possibilities for mass assignment and on-shell projections, collinear case.

```

<SF base: execute tests>+≡
call test (sf_base_3, "sf_base_3", &
  "alternatives for collinear kinematics", &
  u, results)

```

```

<SF base: tests>+≡
subroutine sf_base_3 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(pdg_array_t) :: pdg_in
  type(flavor_t) :: flv
  class(sf_data_t), allocatable, target :: data
  class(sf_int_t), allocatable :: sf_int
  type(vector4_t) :: k
  real(default) :: E
  real(default), dimension(:), allocatable :: r, rb, x
  real(default) :: f

  write (u, "(A)")  "* Test output: sf_base_3"
  write (u, "(A)")  "*   Purpose: check various kinematical setups"
  write (u, "(A)")  "*               for collinear structure-function splitting."
  write (u, "(A)")  "               (two masses equal, one zero)"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize configuration data"
  write (u, "(A)")

  call model%init_test ()
  pdg_in = 25
  call flv%init (25, model)

  call reset_interaction_counter ()

  allocate (sf_test_data_t :: data)
  select type (data)
  type is (sf_test_data_t)
    call data%init (model, pdg_in)
  end select

  write (u, "(A)")  "* Initialize structure-function object"
  write (u, "(A)")

  call data%allocate_sf_int (sf_int)
  call sf_int%init (data)

  call sf_int%write (u)

  allocate (r (data%get_n_par ()))
  allocate (rb(size (r)))
  allocate (x (size (r)))

  write (u, "(A)")
  write (u, "(A)")  "* Initialize incoming momentum with E=500"

  E = 500
  k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
  call sf_int%seed_kinematics ([k])

  write (u, "(A)")

```



```

write (u, "(A)")  "* Set radiated mass to zero"

sf_int%mr2 = 0
sf_int%mo2 = sf_int%mi2

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping energy"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping momentum"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set outgoing mass to zero"

sf_int%mr2 = sf_int%mi2
sf_int%mo2 = 0

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping energy"
write (u, "(A)")

r = 0.5_default

```

```

rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping momentum"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set incoming mass to zero"

k = vector4_moving (E, E, 3)
call sf_int%seed_kinematics ([k])

sf_int%mr2 = sf_int%mi2
sf_int%mo2 = sf_int%mi2
sf_int%mi2 = 0

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping energy"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")

```

```

write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping momentum"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set all masses to zero"

sf_int%mr2 = 0
sf_int%mo2 = 0
sf_int%mi2 = 0

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5, keeping energy"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")

```

```

write (u, "(A)")  "* Set kinematics for x=0.5, keeping momentum"
write (u, "(A)")

r = 0.5_default
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_3"

end subroutine sf_base_3

```

Non-collinear kinematics

Scan over the possibilities for mass assignment and on-shell projections, non-collinear case.

```

<SF base: execute tests>+≡
  call test (sf_base_4, "sf_base_4", &
    "alternatives for non-collinear kinematics", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_4(u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(flavor_t) :: flv
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_base_4"
    write (u, "(A)")  "* Purpose: check various kinematical setups"

```

```

write (u, "(A)")  "*"          for free structure-function splitting."
write (u, "(A)")  "          (two masses equal, one zero)"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_test ()
pdg_in = 25
call flv%init (25, model)

call reset_interaction_counter ()

allocate (sf_test_data_t :: data)
select type (data)
type is (sf_test_data_t)
    call data%init (model, pdg_in, collinear=.false.)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)

call sf_int%write (u)

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=500"

E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set radiated mass to zero"

sf_int%mr2 = 0
sf_int%mo2 = sf_int%mi2

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping energy"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping momentum"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set outgoing mass to zero"

sf_int%mr2 = sf_int%mi2
sf_int%mo2 = 0

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping energy"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")

```

```

write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping momentum"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set incoming mass to zero"

k = vector4_moving (E, E, 3)
call sf_int%seed_kinematics ([k])

sf_int%mr2 = sf_int%mi2
sf_int%mo2 = sf_int%mi2
sf_int%mi2 = 0

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping energy"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping momentum"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM

```

```

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set all masses to zero"

sf_int%mr2 = 0
sf_int%mo2 = 0
sf_int%mi2 = 0

write (u, "(A)")
write (u, "(A)")  "* Re-Initialize structure-function object with Q bounds"

call reset_interaction_counter ()

select type (data)
type is (sf_test_data_t)
    call data%init (model, pdg_in, collinear=.false., &
        qbounds = [1._default, 100._default])
end select

call sf_int%init (data)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping energy"
write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.125, keeping momentum"

```



```

write (u, "(A)")

r = [0.5_default, 0.5_default, 0.125_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_MOMENTUM
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recover x and r"
write (u, "(A)")

call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "r =", r

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_4"

end subroutine sf_base_4

```

Pair spectrum

Construct and display a structure function object for a pair spectrum (a structure function involving two particles simultaneously).

```

<SF base: execute tests>+≡
  call test (sf_base_5, "sf_base_5", &
    "pair spectrum with radiation", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_5 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(pdg_array_t), dimension(2) :: pdg_out
    integer, dimension(:), allocatable :: pdg1, pdg2
    type(flavor_t) :: flv
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t), dimension(2) :: k
    type(vector4_t), dimension(4) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

```

```

write (u, "(A)")  "* Test output: sf_base_5"
write (u, "(A)")  "* Purpose: initialize and fill &
    &a pair spectrum object"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_test ()
call flv%init (25, model)
pdg_in = 25

call reset_interaction_counter ()

allocate (sf_test_spectrum_data_t :: data)
select type (data)
type is (sf_test_spectrum_data_t)
    call data%init (model, pdg_in, with_radiation=.true.)
end select

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
pdg2 = pdg_out(2)
write (u, "(2x,99(1x,I0))") pdg1, pdg2

write (u, "(A)")
write (u, "(A)")  "* Initialize spectrum object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)

call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momenta with sqrt_s=1000"

E = 500
k(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
k(2) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call sf_int%seed_kinematics (k)

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.4,0.8"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = [0.4_default, 0.8_default]
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

```

```

call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Set kinematics with mapping for r=0.6,0.8"
write (u, "(A)")

r = [0.6_default, 0.8_default]
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call reset_interaction_counter ()
call data%allocate_sf_int (sf_int)
call sf_int%init (data)

call sf_int%seed_kinematics (k)
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
write (u, "(A,9(1x,F10.7))") "x =", x

write (u, "(A)")
write (u, "(A)")  "* Compute inverse kinematics for x=0.36,0.64 &
    &and evaluate"
write (u, "(A)")

x = [0.36_default, 0.64_default]
call sf_int%inverse_kinematics (x, f, r, rb, map=.true.)
call sf_int%apply (scale=0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()

```

```

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_5"

end subroutine sf_base_5

```

Pair spectrum without radiation

Construct and display a structure function object for a pair spectrum (a structure function involving two particles simultaneously).

```

<SF base: execute tests>+≡
  call test (sf_base_6, "sf_base_6", &
    "pair spectrum without radiation", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_6 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(flavor_t) :: flv
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t), dimension(2) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_base_6"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &a pair spectrum object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_test ()
    call flv%init (25, model)
    pdg_in = 25

    call reset_interaction_counter ()

    allocate (sf_test_spectrum_data_t :: data)
    select type (data)
    type is (sf_test_spectrum_data_t)
      call data%init (model, pdg_in, with_radiation=.false.)
    end select

    write (u, "(A)")  "* Initialize spectrum object"
    write (u, "(A)")

```

```

call data%allocate_sf_int (sf_int)
call sf_int%init (data)

write (u, "(A)")  "* Initialize incoming momenta with sqrts=1000"

E = 500
k(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
k(2) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call sf_int%seed_kinematics (k)

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.4,0.8"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = [0.4_default, 0.8_default]
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call reset_interaction_counter ()
call data%allocate_sf_int (sf_int)
call sf_int%init (data)

call sf_int%seed_kinematics (k)
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
write (u, "(A,9(1x,F10.7))")  "x =", x

write (u, "(A)")
write (u, "(A)")  "* Compute inverse kinematics for x=0.4,0.8 &
&and evaluate"
write (u, "(A)")

x = [0.4_default, 0.8_default]
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
call sf_int%apply (scale=0._default)
call sf_int%write (u)

```

```

write (u, "(A)")
write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_6"

end subroutine sf_base_6

```

Direct access to structure function

Probe a structure function directly.

```

<SF base: execute tests>+≡
  call test (sf_base_7, "sf_base_7", &
    "direct access", &
    u, results)

<SF base: tests>+≡
subroutine sf_base_7 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(pdg_array_t) :: pdg_in
  type(flavor_t) :: flv
  class(sf_data_t), allocatable, target :: data
  class(sf_int_t), allocatable :: sf_int
  real(default), dimension(:), allocatable :: value

  write (u, "(A)")  "* Test output: sf_base_7"
  write (u, "(A)")  "* Purpose: check direct access method"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize configuration data"
  write (u, "(A)")

  call model%init_test ()
  call flv%init (25, model)
  pdg_in = 25

  call reset_interaction_counter ()

  write (u, "(A)")  "* Initialize structure-function object"
  write (u, "(A)")

  allocate (sf_test_data_t :: data)
  select type (data)
  type is (sf_test_data_t)
    call data%init (model, pdg_in)

```

```

end select

call data%allocate_sf_int (sf_int)
call sf_int%init (data)

write (u, "(A)")  "* Probe structure function: states"
write (u, "(A)")

write (u, "(A,IO)")  "n_states = ", sf_int%get_n_states ()
write (u, "(A,IO)")  "n_in      = ", sf_int%get_n_in ()
write (u, "(A,IO)")  "n_rad      = ", sf_int%get_n_rad ()
write (u, "(A,IO)")  "n_out      = ", sf_int%get_n_out ()
write (u, "(A)")
write (u, "(A)", advance="no")  "state(1) = "
call quantum_numbers_write (sf_int%get_state (1), u)
write (u, *)

allocate (value (sf_int%get_n_states ()))
call sf_int%compute_values (value, &
    E=[500._default], x=[0.5_default], xb=[0.5_default], scale=0._default)

write (u, "(A)")
write (u, "(A)", advance="no")  "value (E=500, x=0.5) ="
write (u, "(9(1x," // FMT_19 // "))" value

call sf_int%compute_values (value, &
    x=[0.1_default], xb=[0.9_default], scale=0._default)

write (u, "(A)")
write (u, "(A)", advance="no")  "value (E=500, x=0.1) ="
write (u, "(9(1x," // FMT_19 // "))" value

write (u, "(A)")
write (u, "(A)")  "* Initialize spectrum object"
write (u, "(A)")

deallocate (value)
call sf_int%final ()
deallocate (sf_int)
deallocate (data)

allocate (sf_test_spectrum_data_t :: data)
select type (data)
type is (sf_test_spectrum_data_t)
    call data%init (model, pdg_in, with_radiation=.false.)
end select

call data%allocate_sf_int (sf_int)
call sf_int%init (data)

write (u, "(A)")  "* Probe spectrum: states"
write (u, "(A)")

```

```

write (u, "(A,I0)") "n_states = ", sf_int%get_n_states ()
write (u, "(A,I0)") "n_in      = ", sf_int%get_n_in ()
write (u, "(A,I0)") "n_rad     = ", sf_int%get_n_rad ()
write (u, "(A,I0)") "n_out     = ", sf_int%get_n_out ()
write (u, "(A)")
write (u, "(A)", advance="no") "state(1) = "
call quantum_numbers_write (sf_int%get_state (1), u)
write (u, *)

allocate (value (sf_int%get_n_states ()))
call sf_int%compute_value (1, value(1), &
    E = [500._default, 500._default], &
    x = [0.5_default, 0.6_default], &
    xb= [0.5_default, 0.4_default], &
    scale = 0._default)

write (u, "(A)")
write (u, "(A)", advance="no") "value (E=500,500, x=0.5,0.6) ="
write (u, "(9(1x," // FMT_19 // "))" value

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_7"

end subroutine sf_base_7

```

Structure function chain configuration

```

<SF base: execute tests>+≡
call test (sf_base_8, "sf_base_8", &
    "structure function chain configuration", &
    u, results)

<SF base: tests>+≡
subroutine sf_base_8(u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    type(beam_data_t), target :: beam_data
    class(sf_data_t), allocatable, target :: data_strfun
    class(sf_data_t), allocatable, target :: data_spectrum
    type(sf_config_t), dimension(:), allocatable :: sf_config
    type(sf_chain_t) :: sf_chain

write (u, "(A)")  "* Test output: sf_base_8"
write (u, "(A)")  "* Purpose: set up a structure-function chain"
write (u, "(A)")

```



```

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_test ()
call flv%init (25, model)
pdg_in = 25

call reset_interaction_counter ()

call beam_data_init_sqrts (beam_data, &
    1000._default, [flv, flv])

allocate (sf_test_data_t :: data_strfun)
select type (data_strfun)
type is (sf_test_data_t)
    call data_strfun%init (model, pdg_in)
end select

allocate (sf_test_spectrum_data_t :: data_spectrum)
select type (data_spectrum)
type is (sf_test_spectrum_data_t)
    call data_spectrum%init (model, pdg_in, with_radiation=.true.)
end select

write (u, "(A)")  "* Set up chain with beams only"
write (u, "(A)")

call sf_chain%init (beam_data)
call write_separator (u, 2)
call sf_chain%write (u)
call write_separator (u, 2)
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Set up chain with structure function"
write (u, "(A)")

allocate (sf_config (1))
call sf_config(1)%init ([1], data_strfun)
call sf_chain%init(beam_data, sf_config)

call write_separator (u, 2)
call sf_chain%write (u)
call write_separator (u, 2)
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Set up chain with spectrum and structure function"
write (u, "(A)")

deallocate (sf_config)
allocate (sf_config (2))
call sf_config(1)%init ([1,2], data_spectrum)

```

```

call sf_config(2)%init ([2], data_strfun)
call sf_chain%init (beam_data, sf_config)

call write_separator (u, 2)
call sf_chain%write (u)
call write_separator (u, 2)
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_8"

end subroutine sf_base_8

```

Structure function instance configuration

We create a structure-function chain instance which implements a configured structure-function chain. We link the momentum entries in the interactions and compute kinematics.

We do not actually connect the interactions and create evaluators. We skip this step and manually advance the status of the chain instead.

```

<SF base: execute tests>+≡
call test (sf_base_9, "sf_base_9", &
    "structure function chain instance", &
    u, results)

<SF base: tests>+≡
subroutine sf_base_9 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    type(beam_data_t), target :: beam_data
    class(sf_data_t), allocatable, target :: data_strfun
    class(sf_data_t), allocatable, target :: data_spectrum
    type(sf_config_t), dimension(:), allocatable, target :: sf_config
    type(sf_chain_t), target :: sf_chain
    type(sf_chain_instance_t), target :: sf_chain_instance
    type(sf_channel_t), dimension(2) :: sf_channel
    type(vector4_t), dimension(2) :: p
    integer :: j

    write (u, "(A)")  "* Test output: sf_base_9"
    write (u, "(A)")  "* Purpose: set up a structure-function chain &
        &and create an instance"
    write (u, "(A)")  "* compute kinematics"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"

```

```

write (u, "(A)")

call model%init_test ()
call flv%init (25, model)
pdg_in = 25

call reset_interaction_counter ()

call beam_data_init_sqrts (beam_data, &
    1000._default, [flv, flv])

allocate (sf_test_data_t :: data_strfun)
select type (data_strfun)
type is (sf_test_data_t)
    call data_strfun%init (model, pdg_in)
end select

allocate (sf_test_spectrum_data_t :: data_spectrum)
select type (data_spectrum)
type is (sf_test_spectrum_data_t)
    call data_spectrum%init (model, pdg_in, with_radiation=.true.)
end select

write (u, "(A)")  "* Set up chain with beams only"
write (u, "(A)")

call sf_chain%init (beam_data)

call sf_chain_instance%init (sf_chain, n_channel = 1)

call sf_chain_instance%link_interactions ()
sf_chain_instance%status = SF_DONE_CONNECTIONS
call sf_chain_instance%compute_kinematics (1, [real(default) ::])

call write_separator (u, 2)
call sf_chain%write (u)
call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call sf_chain_instance%get_out_momenta (p)

write (u, "(A)")
write (u, "(A)")  "* Outgoing momenta:"

do j = 1, 2
    write (u, "(A)")
    call vector4_write (p(j), u)
end do

call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")

```

```

write (u, "(A)")  "* Set up chain with structure function"
write (u, "(A)")

allocate (sf_config (1))
call sf_config(1)%init ([1], data_strfun)
call sf_chain%init (beam_data, sf_config)

call sf_chain_instance%init (sf_chain, n_channel = 1)

call sf_channel(1)%init (1)
call sf_channel(1)%activate_mapping ([1])
call sf_chain_instance%set_channel (1, sf_channel(1))

call sf_chain_instance%link_interactions ()
sf_chain_instance%status = SF_DONE_CONNECTIONS
call sf_chain_instance%compute_kinematics (1, [0.8_default])

call write_separator (u, 2)
call sf_chain%write (u)
call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call sf_chain_instance%get_out_momenta (p)

write (u, "(A)")
write (u, "(A)")  "* Outgoing momenta:"

do j = 1, 2
    write (u, "(A)")
    call vector4_write (p(j), u)
end do

call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Set up chain with spectrum and structure function"
write (u, "(A)")

deallocate (sf_config)
allocate (sf_config (2))
call sf_config(1)%init ([1,2], data_spectrum)
call sf_config(2)%init ([2], data_strfun)
call sf_chain%init (beam_data, sf_config)

call sf_chain_instance%init (sf_chain, n_channel = 1)

call sf_channel(2)%init (2)
call sf_channel(2)%activate_mapping ([2])
call sf_chain_instance%set_channel (1, sf_channel(2))

call sf_chain_instance%link_interactions ()
sf_chain_instance%status = SF_DONE_CONNECTIONS

```

```

call sf_chain_instance%compute_kinematics &
    (1, [0.5_default, 0.6_default, 0.8_default])

call write_separator (u, 2)
call sf_chain%write (u)
call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call sf_chain_instance%get_out_momenta (p)

write (u, "(A)")
write (u, "(A)")  "* Outgoing momenta:"

do j = 1, 2
    write (u, "(A)")
    call vector4_write (p(j), u)
end do

call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_9"

end subroutine sf_base_9

```

Structure function chain mappings

Set up a structure function chain instance with a pair of single-particle structure functions. We test different global mappings for this setup.

Again, we skip evaluators.

```

<SF base: execute tests>+≡
call test (sf_base_10, "sf_base_10", &
    "structure function chain mapping", &
    u, results)

<SF base: tests>+≡
subroutine sf_base_10 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    type(beam_data_t), target :: beam_data
    class(sf_data_t), allocatable, target :: data_strfun
    type(sf_config_t), dimension(:), allocatable, target :: sf_config
    type(sf_chain_t), target :: sf_chain
    type(sf_chain_instance_t), target :: sf_chain_instance

```

```

type(sf_channel_t), dimension(2) :: sf_channel
real(default), dimension(2) :: x_saved

write (u, "(A)")  "* Test output: sf_base_10"
write (u, "(A)")  "*   Purpose: set up a structure-function chain"
write (u, "(A)")  "*               and check mappings"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_test ()
call flv%init (25, model)
pdg_in = 25

call reset_interaction_counter ()

call beam_data_init_sqrts (beam_data, &
    1000._default, [flv, flv])

allocate (sf_test_data_t :: data_strfun)
select type (data_strfun)
type is (sf_test_data_t)
    call data_strfun%init (model, pdg_in)
end select

write (u, "(A)")  "* Set up chain with structure function pair &
    &and standard mapping"
write (u, "(A)")

allocate (sf_config (2))
call sf_config(1)%init ([1], data_strfun)
call sf_config(2)%init ([2], data_strfun)
call sf_chain%init (beam_data, sf_config)

call sf_chain_instance%init (sf_chain, n_channel = 1)

call sf_channel(1)%init (2)
call sf_channel(1)%set_s_mapping ([1,2])
call sf_chain_instance%set_channel (1, sf_channel(1))

call sf_chain_instance%link_interactions ()
sf_chain_instance%status = SF_DONE_CONNECTIONS
call sf_chain_instance%compute_kinematics (1, [0.8_default, 0.6_default])

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Invert the kinematics calculation"
write (u, "(A)")

x_saved = sf_chain_instance%x

```

```

call sf_chain_instance%init (sf_chain, n_channel = 1)

call sf_channel(2)%init (2)
call sf_channel(2)%set_s_mapping ([1, 2])
call sf_chain_instance%set_channel (1, sf_channel(2))

call sf_chain_instance%link_interactions ()
sf_chain_instance%status = SF_DONE_CONNECTIONS
call sf_chain_instance%inverse_kinematics (x_saved)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_10"

end subroutine sf_base_10

```

Structure function chain evaluation

Here, we test the complete workflow for structure-function chains. First, we create the template chain, then initialize an instance. We set up links, mask, and evaluators. Finally, we set kinematics and evaluate the matrix elements and their products.

```

<SF base: execute tests>+≡
  call test (sf_base_11, "sf_base_11", &
    "structure function chain evaluation", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_11 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    type(beam_data_t), target :: beam_data
    class(sf_data_t), allocatable, target :: data_strfun
    class(sf_data_t), allocatable, target :: data_spectrum
    type(sf_config_t), dimension(:), allocatable, target :: sf_config
    type(sf_chain_t), target :: sf_chain
    type(sf_chain_instance_t), target :: sf_chain_instance
    type(sf_channel_t), dimension(2) :: sf_channel

```

```

type(particle_set_t) :: pset
type(interaction_t), pointer :: int
logical :: ok

write (u, "(A)")  "* Test output: sf_base_11"
write (u, "(A)")  "* Purpose: set up a structure-function chain"
write (u, "(A)")  "*           create an instance and evaluate"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_test ()
call flv%init (25, model)
pdg_in = 25

call reset_interaction_counter ()

call beam_data_init_sqrts (beam_data, &
    1000._default, [flv, flv])

allocate (sf_test_data_t :: data_strfun)
select type (data_strfun)
type is (sf_test_data_t)
    call data_strfun%init (model, pdg_in)
end select

allocate (sf_test_spectrum_data_t :: data_spectrum)
select type (data_spectrum)
type is (sf_test_spectrum_data_t)
    call data_spectrum%init (model, pdg_in, with_radiation=.true.)
end select

write (u, "(A)")  "* Set up chain with beams only"
write (u, "(A)")

call sf_chain%init (beam_data)

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

call sf_chain_instance%compute_kinematics (1, [real(default) ::])
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

int => sf_chain_instance%get_out_int_ptr ()
call pset%init (ok, int, int, FM_IGNORE_HELICITY, &
    [0._default, 0._default], .false., .true.)
call sf_chain_instance%final ()

```



```

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover chain:"
write (u, "(A)")

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

int => sf_chain_instance%get_out_int_ptr ()
call pset%fill_interaction (int, 2, check_match=.false.)

call sf_chain_instance%recover_kinematics (1)
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call pset%final ()
call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")
write (u, "(A)")
write (u, "(A)")  "* Set up chain with structure function"
write (u, "(A)")

allocate (sf_config (1))
call sf_config(1)%init ([1], data_strfun)
call sf_chain%init (beam_data, sf_config)

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_channel(1)%init (1)
call sf_channel(1)%activate_mapping ([1])
call sf_chain_instance%set_channel (1, sf_channel(1))
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

call sf_chain_instance%compute_kinematics (1, [0.8_default])
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)

```

```

call sf_chain_instance%write (u)
call write_separator (u, 2)

int => sf_chain_instance%get_out_int_ptr ()
call pset%init (ok, int, int, FM_IGNORE_HELICITY, &
    [0._default, 0._default], .false., .true.)
call sf_chain_instance%final ()

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover chain:"
write (u, "(A)")

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_channel(1)%init (1)
call sf_channel(1)%activate_mapping ([1])
call sf_chain_instance%set_channel (1, sf_channel(1))
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

int => sf_chain_instance%get_out_int_ptr ()
call pset%fill_interaction (int, 2, check_match=.false.)

call sf_chain_instance%recover_kinematics (1)
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call pset%final ()
call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")
write (u, "(A)")
write (u, "(A)")  "* Set up chain with spectrum and structure function"
write (u, "(A)")

deallocate (sf_config)
allocate (sf_config (2))
call sf_config(1)%init ([1,2], data_spectrum)
call sf_config(2)%init ([2], data_strfun)
call sf_chain%init (beam_data, sf_config)

```

```

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_channel(2)%init (2)
call sf_channel(2)%activate_mapping ([2])
call sf_chain_instance%set_channel (1, sf_channel(2))
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

call sf_chain_instance%compute_kinematics &
      (1, [0.5_default, 0.6_default, 0.8_default])
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

int => sf_chain_instance%get_out_int_ptr ()
call pset%init (ok, int, int, FM_IGNORE_HELICITY, &
      [0._default, 0._default], .false., .true.)
call sf_chain_instance%final ()

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover chain:"
write (u, "(A)")

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_channel(2)%init (2)
call sf_channel(2)%activate_mapping ([2])
call sf_chain_instance%set_channel (1, sf_channel(2))
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

int => sf_chain_instance%get_out_int_ptr ()
call pset%fill_interaction (int, 2, check_match=.false.)

call sf_chain_instance%recover_kinematics (1)
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

call pset%final ()
call sf_chain_instance%final ()
call sf_chain%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_11"

end subroutine sf_base_11

```

Multichannel case

We set up a structure-function chain as before, but with three different parameterizations. The first instance is without mappings, the second one with single-particle mappings, and the third one with two-particle mappings.

```

<SF base: execute tests>+≡
  call test (sf_base_12, "sf_base_12", &
    "multi-channel structure function chain", &
    u, results)

<SF base: tests>+≡
subroutine sf_base_12 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(flavor_t) :: flv
  type(pdg_array_t) :: pdg_in
  type(beam_data_t), target :: beam_data
  class(sf_data_t), allocatable, target :: data
  type(sf_config_t), dimension(:), allocatable, target :: sf_config
  type(sf_chain_t), target :: sf_chain
  type(sf_chain_instance_t), target :: sf_chain_instance
  real(default), dimension(2) :: x_saved
  real(default), dimension(2,3) :: p_saved
  type(sf_channel_t), dimension(:), allocatable :: sf_channel

  write (u, "(A)")  "* Test output: sf_base_12"
  write (u, "(A)")  "* Purpose: set up and evaluate a multi-channel &
    &structure-function chain"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize configuration data"
  write (u, "(A)")

  call model%init_test ()
  call flv%init (25, model)
  pdg_in = 25

  call reset_interaction_counter ()

  call beam_data_init_sqrts (beam_data, &
    1000._default, [flv, flv])

```

```

allocate (sf_test_data_t :: data)
select type (data)
type is (sf_test_data_t)
    call data%init (model, pdg_in)
end select

write (u, "(A)")  "* Set up chain with structure function pair &
    &and three different mappings"
write (u, "(A)")

allocate (sf_config (2))
call sf_config(1)%init ([1], data)
call sf_config(2)%init ([2], data)
call sf_chain%init (beam_data, sf_config)

call sf_chain_instance%init (sf_chain, n_channel = 3)

call allocate_sf_channels (sf_channel, n_channel = 3, n_strfun = 2)

! channel 1: no mapping
call sf_chain_instance%set_channel (1, sf_channel(1))

! channel 2: single-particle mappings
call sf_channel(2)%activate_mapping ([1,2])
! call sf_chain_instance%activate_mapping (2, [1,2])
call sf_chain_instance%set_channel (2, sf_channel(2))

! channel 3: two-particle mapping
call sf_channel(3)%set_s_mapping ([1,2])
! call sf_chain_instance%set_s_mapping (3, [1, 2])
call sf_chain_instance%set_channel (3, sf_channel(3))

call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

write (u, "(A)")  "* Compute kinematics in channel 1 and evaluate"
write (u, "(A)")

call sf_chain_instance%compute_kinematics (1, [0.8_default, 0.6_default])
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Invert the kinematics calculation"
write (u, "(A)")

x_saved = sf_chain_instance%x

call sf_chain_instance%inverse_kinematics (x_saved)
call sf_chain_instance%evaluate (scale=0._default)

```

```

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Compute kinematics in channel 2 and evaluate"
write (u, "(A)")

p_saved = sf_chain_instance%p

call sf_chain_instance%compute_kinematics (2, p_saved(:,2))
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Compute kinematics in channel 3 and evaluate"
write (u, "(A)")

call sf_chain_instance%compute_kinematics (3, p_saved(:,3))
call sf_chain_instance%evaluate (scale=0._default)

call write_separator (u, 2)
call sf_chain_instance%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_chain_instance%final ()
call sf_chain%final ()

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_12"

end subroutine sf_base_12

```

Generated spectrum

Construct and evaluate a structure function object for a pair spectrum which is evaluated as a beam-event generator.

```

<SF base: execute tests>+≡
  call test (sf_base_13, "sf_base_13", &
    "pair spectrum generator", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_13 (u)

```

```

integer, intent(in) :: u
type(model_data_t), target :: model
type(flavor_t) :: flv
type(pdg_array_t) :: pdg_in
class(sf_data_t), allocatable, target :: data
class(sf_int_t), allocatable :: sf_int
type(vector4_t), dimension(2) :: k
type(vector4_t), dimension(2) :: q
real(default) :: E
real(default), dimension(:), allocatable :: r, rb, x
real(default) :: f, x_free

write (u, "(A)")  "* Test output: sf_base_13"
write (u, "(A)")  "* Purpose: initialize and fill &
                  &a pair generator object"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_test ()
call flv%init (25, model)
pdg_in = 25

call reset_interaction_counter ()

allocate (sf_test_generator_data_t :: data)
select type (data)
type is (sf_test_generator_data_t)
    call data%init (model, pdg_in)
end select

write (u, "(A)")  "* Initialize generator object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

write (u, "(A)")  "* Generate free r values"
write (u, "(A)")

x_free = 1
call sf_int%generate_free (r, rb, x_free)

write (u, "(A)")  "* Initialize incoming momenta with sqrts=1000"

E = 500
k(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
k(2) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call sf_int%seed_kinematics (k)

```

```

write (u, "(A)")
write (u, "(A)")  "* Complete kinematics"
write (u, "(A)")

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call reset_interaction_counter ()
call data%allocate_sf_int (sf_int)
call sf_int%init (data)

call sf_int%seed_kinematics (k)
call sf_int%set_momenta (q, outgoing=.true.)
x_free = 1
call sf_int%recover_x (x, x_free)
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Compute inverse kinematics &
&and evaluate"
write (u, "(A)")

call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
call sf_int%apply (scale=0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_13"

```



```
end subroutine sf_base_13
```

Structure function chain evaluation

Here, we test the complete workflow for a structure-function chain with generator. First, we create the template chain, then initialize an instance. We set up links, mask, and evaluators. Finally, we set kinematics and evaluate the matrix elements and their products.

```
<SF base: execute tests>+≡
  call test (sf_base_14, "sf_base_14", &
    "structure function generator evaluation", &
    u, results)

<SF base: tests>+≡
  subroutine sf_base_14 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    type(beam_data_t), target :: beam_data
    class(sf_data_t), allocatable, target :: data_strfun
    class(sf_data_t), allocatable, target :: data_generator
    type(sf_config_t), dimension(:), allocatable, target :: sf_config
    real(default), dimension(:), allocatable :: p_in
    type(sf_chain_t), target :: sf_chain
    type(sf_chain_instance_t), target :: sf_chain_instance

    write (u, "(A)")  "* Test output: sf_base_14"
    write (u, "(A)")  "* Purpose: set up a structure-function chain"
    write (u, "(A)")  "*           create an instance and evaluate"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_test ()
    call flv%init (25, model)
    pdg_in = 25

    call reset_interaction_counter ()

    call beam_data_init_sqrts (beam_data, &
      1000._default, [flv, flv])

    allocate (sf_test_data_t :: data_strfun)
    select type (data_strfun)
    type is (sf_test_data_t)
      call data_strfun%init (model, pdg_in)
    end select

    allocate (sf_test_generator_data_t :: data_generator)
    select type (data_generator)
    type is (sf_test_generator_data_t)
```

```

        call data_generator%init (model, pdg_in)
end select

write (u, "(A)")  "* Set up chain with generator and structure function"
write (u, "(A)")

allocate (sf_config (2))
call sf_config(1)%init ([1,2], data_generator)
call sf_config(2)%init ([2], data_strfun)
call sf_chain%init (beam_data, sf_config)

call sf_chain_instance%init (sf_chain, n_channel = 1)
call sf_chain_instance%link_interactions ()
call sf_chain_instance%exchange_mask ()
call sf_chain_instance%init_evaluators ()

write (u, "(A)")  "* Inject integration parameter"
write (u, "(A)")

allocate (p_in (sf_chain%get_n_bound ()), source = 0.9_default)
write (u, "(A,9(1x,F10.7))")  "p_in =", p_in

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_chain_instance%compute_kinematics (1, p_in)
call sf_chain_instance%evaluate (scale=0._default)

call sf_chain_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Extract integration parameter"
write (u, "(A)")

call sf_chain_instance%get_mcpair (1, p_in)
write (u, "(A,9(1x,F10.7))")  "p_in =", p_in

call sf_chain_instance%final ()
call sf_chain%final ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_base_14"

end subroutine sf_base_14

```

15.6 Photon radiation: ISR

```

⟨sf_isr.f90⟩≡
  ⟨File header⟩

  module sf_isr

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use io_units
    use constants, only: pi
    use format_defs, only: FMT_12, FMT_17, FMT_19
    use unit_tests
    use diagnostics
    use physics_defs, only: ELECTRON, PHOTON
    use lorentz
    use sm_physics, only: Li2
    use pdg_arrays
    use model_data
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use interactions
    use polarizations
    use sf_mappings
    use sf_aux
    use sf_base

    ⟨Standard module head⟩

    ⟨SF_isr: public⟩

    ⟨SF_isr: parameters⟩

    ⟨SF_isr: types⟩

    contains

    ⟨SF_isr: procedures⟩

    ⟨SF_isr: tests⟩

  end module sf_isr

```

15.6.1 Physics

The ISR structure function is in the most crude approximation (LLA without α corrections, i.e. ϵ^0)

$$f_0(x) = \epsilon(1-x)^{-1+\epsilon} \quad \text{with} \quad \epsilon = \frac{\alpha}{\pi} q_e^2 \ln \frac{s}{m^2}, \quad (15.27)$$

where m is the mass of the incoming (and outgoing) particle, which is initially assumed on-shell.

Here, the form of ϵ results from the kinematical bounds for the momentum squared of the outgoing particle, which in the limit $m^2 \ll s$ are given by

$$t_0 = -2\bar{x}E(E+p) + m^2 \approx -\bar{x}s, \quad (15.28)$$

$$t_1 = -2\bar{x}E(E-p) + m^2 \approx xm^2, \quad (15.29)$$

so the integration over the propagator $1/(t - m^2)$ yields

$$\ln \frac{t_0 - m^2}{t_1 - m^2} = \ln \frac{s}{m^2}. \quad (15.30)$$

In $f_0(x)$, there is an integrable singularity at $x = 1$ which does not spoil the integration, but would lead to an unbounded f_{\max} . Therefore, we map this singularity like

$$x = 1 - (1 - x')^{1/\epsilon} \quad (15.31)$$

such that

$$\int dx f_0(x) = \int dx' \quad (15.32)$$

The structure function has three parameters: α , m_{in} of the incoming particle and s , the hard scale. Internally, we store the exponent ϵ which is the relevant parameter. (In conventional notation, $\epsilon = \beta/2$.) As defaults, we take the actual values of α (which is probably $\alpha(s)$), the actual mass m_{in} and the squared total c.m. energy s .

Including ϵ , ϵ^2 , and ϵ^3 corrections, the successive approximation of the ISR structure function read

$$f_0(x) = \epsilon(1-x)^{-1+\epsilon} \quad (15.33)$$

$$f_1(x) = g_1(\epsilon) f_0(x) - \frac{\epsilon}{2}(1+x) \quad (15.34)$$

$$f_2(x) = g_2(\epsilon) f_0(x) - \frac{\epsilon}{2}(1+x) - \frac{\epsilon^2}{8} \left(\frac{1+3x^2}{1-x} \ln x + 4(1+x) \ln(1-x) + 5+x \right) \quad (15.35)$$

$$\begin{aligned} f_3(x) = & g_3(\epsilon) f_0(x) - \frac{\epsilon}{2}(1+x) \\ & - \frac{\epsilon^2}{8} \left(\frac{1+3x^2}{1-x} \ln x + 4(1+x) \ln(1-x) + 5+x \right) \\ & - \frac{\epsilon^3}{48} \left((1+x) [6 \text{Li}_2(x) + 12 \ln^2(1-x) - 3\pi^2] + 6(x+5) \ln(1-x) \right. \\ & \quad \left. + \frac{1}{1-x} \left[\frac{3}{2}(1+8x+3x^2) \ln x + 12(1+x^2) \ln x \ln(1-x) \right. \right. \\ & \quad \left. \left. - \frac{1}{2}(1+7x^2) \ln^2 x + \frac{1}{4}(39-24x-15x^2) \right] \right) \end{aligned} \quad (15.36)$$

where the successive approximations to the prefactor of the leading singularity

$$g(\epsilon) = \frac{\exp\left(\epsilon(-\gamma_E + \frac{3}{4})\right)}{\Gamma(1+\epsilon)}, \quad (15.37)$$

are given by

$$g_0(\epsilon) = 1 \quad (15.38)$$

$$g_1(\epsilon) = 1 + \frac{3}{4}\epsilon \quad (15.39)$$

$$g_2(\epsilon) = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 \quad (15.40)$$

$$g_3(\epsilon) = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 + \frac{27 - 24\pi^2 + 128\zeta(3)}{384}\epsilon^3, \quad (15.41)$$

where, numerically

$$\zeta(3) = 1.20205690315959428539973816151 \dots \quad (15.42)$$

Although one could calculate the function $g(\epsilon)$ exactly, truncating its Taylor expansion ensures the exact normalization of the truncated structure function at each given order:

$$\int_0^1 dx f_i(x) = 1 \quad \text{for all } i. \quad (15.43)$$

Effectively, the $O(\epsilon)$ correction reduces the low- x tail of the structure function by 50% while increasing the coefficient of the singularity by $O(\epsilon)$. Relative to this, the $O(\epsilon^2)$ correction slightly enhances $x > \frac{1}{2}$ compared to $x < \frac{1}{2}$. At $x = 0$, $f_2(x)$ introduces a logarithmic singularity which should be cut off at $x_0 = O(e^{-1/\epsilon})$: for lower x the perturbative series breaks down. The f_3 correction is slightly positive for low x values and negative near $x = 1$, where the Li₂ piece slightly softens the singularity at $x = 1$.

Instead of the definition for ϵ given above, it is customary to include a universal nonlogarithmic piece:

$$\epsilon = \frac{\alpha}{\pi} q_e^2 \left(\ln \frac{s}{m^2} - 1 \right) \quad (15.44)$$

15.6.2 Implementation

In the concrete implementation, the zeroth order mapping (15.31) is implemented, and the Jacobian is equal to $f_i(x)/f_0(x)$. This can be written as

$$\frac{f_0(x)}{f_0(x)} = 1 \quad (15.45)$$

$$\frac{f_1(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon - \frac{1 - x^2}{2(1 - x')} \quad (15.46)$$

$$\begin{aligned} \frac{f_2(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 - \frac{1 - x^2}{2(1 - x')} \\ - \frac{(1 + 3x^2) \ln x + (1 - x)(4(1 + x) \ln(1 - x) + 5 + x)}{8(1 - x')} \epsilon \end{aligned} \quad (15.47)$$

For $x = 1$ (i.e., numerically indistinguishable from 1), this reduces to

$$\frac{f_0(x)}{f_0(x)} = 1 \quad (15.48)$$

$$\frac{f_1(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon \quad (15.49)$$

$$\frac{f_2(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 \quad (15.50)$$

The last line in (15.47) is zero for

$$x_{\min} = 0.00714053329734592839549879772019 \quad (15.51)$$

(Mathematica result), independent of ϵ . For x values less than this we ignore this correction because of the logarithmic singularity which should in principle be resummed.

15.6.3 The ISR data block

```

<SF isr: public>≡
  public :: isr_data_t
<SF isr: types>≡
  type, extends (sf_data_t) :: isr_data_t
  private
  class(model_data_t), pointer :: model => null ()
  type(flavor_t), dimension(:), allocatable :: flv_in
  real(default) :: alpha = 0
  real(default) :: q_max = 0
  real(default) :: real_mass = 0
  real(default) :: mass = 0
  real(default) :: eps = 0
  real(default) :: log = 0
  logical :: recoil = .false.
  integer :: order = 3
  integer :: error = NONE
  contains
  <SF isr: isr data: TBP>
end type isr_data_t

```

Error codes

```

<SF isr: parameters>≡
  integer, parameter :: NONE = 0
  integer, parameter :: ZERO_MASS = 1
  integer, parameter :: Q_MAX_TOO_SMALL = 2
  integer, parameter :: EPS_TOO_LARGE = 3
  integer, parameter :: INVALID_ORDER = 4
  integer, parameter :: CHARGE_MIX = 5
  integer, parameter :: CHARGE_ZERO = 6
  integer, parameter :: MASS_MIX = 7

```

Generate flavor-dependent ISR data:

```

<SF isr: isr data: TBP>≡
  procedure :: init => isr_data_init

```

$\langle SF \text{ isr: procedures} \rangle \equiv$

```

subroutine isr_data_init &
  (data, model, pdg_in, alpha, q_max, mass, order, recoil)
  class(isr_data_t), intent(out) :: data
  class(model_data_t), intent(in), target :: model
  type(pdg_array_t), intent(in) :: pdg_in
  real(default), intent(in) :: alpha
  real(default), intent(in) :: q_max
  real(default), intent(in), optional :: mass
  integer, intent(in), optional :: order
  logical, intent(in), optional :: recoil
  integer :: i, n_flv
  real(default) :: charge
  data%model => model
  n_flv = pdg_array_get_length (pdg_in)
  allocate (data%flv_in (n_flv))
  do i = 1, n_flv
    call data%flv_in(i)%init (pdg_array_get (pdg_in, i), model)
  end do
  data%alpha = alpha
  data%q_max = q_max
  if (present (order)) then
    call data%set_order (order)
  end if
  if (present (recoil)) then
    data%recoil = recoil
  end if
  data%real_mass = data%flv_in(1)%get_mass ()
  if (present (mass)) then
    if (mass > 0) then
      data%mass = mass
    else
      data%mass = data%real_mass
      if (any (data%flv_in%get_mass () /= data%mass)) then
        data%error = MASS_MIX; return
      end if
    end if
  end if
  else
    data%mass = data%real_mass
    if (any (data%flv_in%get_mass () /= data%mass)) then
      data%error = MASS_MIX; return
    end if
  end if
  if (data%mass == 0) then
    data%error = ZERO_MASS; return
  else if (data%mass >= data%q_max) then
    data%error = Q_MAX_TOO_SMALL; return
  end if
  data%log = log (1 + (data%q_max / data%mass)**2)
  charge = data%flv_in(1)%get_charge ()
  if (any (abs (data%flv_in%get_charge ()) /= abs (charge))) then
    data%error = CHARGE_MIX; return
  else if (charge == 0) then
    data%error = CHARGE_ZERO; return

```

```

end if
data%eps = data%alpha / pi * charge ** 2 &
          * (2 * log (data%q_max / data%mass) - 1)
if (data%eps > 1) then
  data%error = EPS_TOO_LARGE; return
end if
end subroutine isr_data_init

```

Explicitly set ISR order

```

<SF isr: isr data: TBP>+≡
  procedure :: set_order => isr_data_set_order

<SF isr: procedures>+≡
  elemental subroutine isr_data_set_order (data, order)
    class(isr_data_t), intent(inout) :: data
    integer, intent(in) :: order
    if (order < 0 .or. order > 3) then
      data%error = INVALID_ORDER
    else
      data%order = order
    end if
  end if
end subroutine isr_data_set_order

```

Handle error conditions. Should always be done after initialization, unless we are sure everything is ok.

```

<SF isr: isr data: TBP>+≡
  procedure :: check => isr_data_check

<SF isr: procedures>+≡
  subroutine isr_data_check (data)
    class(isr_data_t), intent(in) :: data
    select case (data%error)
    case (ZERO_MASS)
      call msg_fatal ("ISR: Particle mass is zero")
    case (Q_MAX_TOO_SMALL)
      call msg_fatal ("ISR: Particle mass exceeds Qmax")
    case (EPS_TOO_LARGE)
      call msg_fatal ("ISR: Expansion parameter too large, " // &
                     "perturbative expansion breaks down")
    case (INVALID_ORDER)
      call msg_error ("ISR: LLA order invalid (valid values are 0,1,2,3)")
    case (MASS_MIX)
      call msg_fatal ("ISR: Incoming particle masses must be uniform")
    case (CHARGE_MIX)
      call msg_fatal ("ISR: Incoming particle charges must be uniform")
    case (CHARGE_ZERO)
      call msg_fatal ("ISR: Incoming particle must be charged")
    end select
  end subroutine isr_data_check

```

Output

```

<SF isr: isr data: TBP>+≡
  procedure :: write => isr_data_write

```



```

<SF isr: procedures>+≡
subroutine isr_data_write (data, unit, verbose)
  class(isr_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(1x,A)") "ISR data:"
  if (allocated (data%flv_in)) then
    write (u, "(3x,A)", advance="no") " flavor = "
    do i = 1, size (data%flv_in)
      if (i > 1) write (u, "(',','1x)", advance="no")
      call data%flv_in(i)%write (u)
    end do
    write (u, *)
    write (u, "(3x,A," // FMT_19 // ")") " alpha = ", data%alpha
    write (u, "(3x,A," // FMT_19 // ")") " q_max = ", data%q_max
    write (u, "(3x,A," // FMT_19 // ")") " mass = ", data%mass
    write (u, "(3x,A," // FMT_19 // ")") " eps = ", data%eps
    write (u, "(3x,A," // FMT_19 // ")") " log = ", data%log
    write (u, "(3x,A,I2)") " order = ", data%order
    write (u, "(3x,A,L2)") " recoil = ", data%recoil
  else
    write (u, "(3x,A)") "[undefined]"
  end if
end subroutine isr_data_write

```

For ISR, there is the option to generate transverse momentum is generated. Hence, there can be up to three parameters, x , and two angles.

```

<SF isr: isr data: TBP>+≡
procedure :: get_n_par => isr_data_get_n_par

<SF isr: procedures>+≡
function isr_data_get_n_par (data) result (n)
  class(isr_data_t), intent(in) :: data
  integer :: n
  if (data%recoil) then
    n = 3
  else
    n = 1
  end if
end function isr_data_get_n_par

```

Return the outgoing particles PDG codes. For ISR, these are identical to the incoming particles.

```

<SF isr: isr data: TBP>+≡
procedure :: get_pdg_out => isr_data_get_pdg_out

<SF isr: procedures>+≡
subroutine isr_data_get_pdg_out (data, pdg_out)
  class(isr_data_t), intent(in) :: data
  type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
  pdg_out(1) = data%flv_in%get_pdg ()
end subroutine isr_data_get_pdg_out

```

Return the `eps` value. We need it for an appropriate mapping of structure-function parameters.

```

<SF isr: isr data: TBP>+≡
  procedure :: get_eps => isr_data_get_eps
<SF isr: procedures>+≡
  function isr_data_get_eps (data) result (eps)
    class(isr_data_t), intent(in) :: data
    real(default) :: eps
    eps = data%eps
  end function isr_data_get_eps

```

Allocate the interaction record.

```

<SF isr: isr data: TBP>+≡
  procedure :: allocate_sf_int => isr_data_allocate_sf_int
<SF isr: procedures>+≡
  subroutine isr_data_allocate_sf_int (data, sf_int)
    class(isr_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (isr_t :: sf_int)
  end subroutine isr_data_allocate_sf_int

```

15.6.4 The ISR object

The `isr_t` data type is a $1 \rightarrow 2$ interaction, i.e., we allow for single-photon emission only (but use the multi-photon resummed radiator function). The particles are ordered as (incoming, photon, outgoing).

There is no need to handle several flavors (and data blocks) in parallel, since ISR is always applied immediately after beam collision. (ISR for partons is accounted for by the PDFs themselves.) Polarization is carried through, i.e., we retain the polarization of the incoming particle and treat the emitted photon as unpolarized. Color is trivially carried through. This implies that particles 1 and 3 should be locked together. For ISR we don't need the `q` variable.

```

<SF isr: types>+≡
  type, extends (sf_int_t) :: isr_t
    type(isr_data_t), pointer :: data => null ()
    real(default) :: x = 0
    real(default) :: xb= 0
  contains
    <SF isr: isr: TBP>
  end type isr_t

```

Type string: has to be here, but there is no string variable on which ISR depends. Hence, a dummy routine.

```

<SF isr: isr: TBP>≡
  procedure :: type_string => isr_type_string

```

```

<SF isr: procedures>+=
function isr_type_string (object) result (string)
  class(isr_t), intent(in) :: object
  type(string_t) :: string
  if (associated (object%data)) then
    string = "ISR: e+ e- ISR spectrum"
  else
    string = "ISR: [undefined]"
  end if
end function isr_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF isr: isr: TBP>+=
  procedure :: write => isr_write

<SF isr: procedures>+=
subroutine isr_write (object, unit, testflag)
  class(isr_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag
  integer :: u
  u = given_output_unit (unit)
  if (associated (object%data)) then
    call object%data%write (u)
    if (object%status >= SF_DONE_KINEMATICS) then
      write (u, "(1x,A)") "SF parameters:"
      write (u, "(3x,A," // FMT_17 // ")") "x =", object%x
      write (u, "(3x,A," // FMT_17 // ")") "xb=", object%xb
    end if
    call object%base_write (u, testflag)
  else
    write (u, "(1x,A)") "ISR data: [undefined]"
  end if
end subroutine isr_write

```

15.6.5 Kinematics

Set kinematics. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ were trivial. The ISR structure function allows for a straightforward mapping of the unit interval. So, to leading order, the structure function value is unity, but the x value is transformed. Higher orders affect the function value.

The structure function implementation applies the above mapping to the input (random) number r to generate the momentum fraction x and the function value f . For numerical stability reasons, we also output xb , which is $\bar{x} = 1 - x$.

For the ISR structure function, the mapping Jacobian cancels the structure function (to order zero). We apply the cancellation explicitly, therefore both the Jacobian f and the zeroth-order value (see the `apply` method) are unity if mapping is turned on. If mapping is turned off, the Jacobian f includes the value of the (zeroth-order) structure function, and strongly peaked.

```

<SF isr: isr: TBP>+=
  procedure :: complete_kinematics => isr_complete_kinematics

```

```

<SF isr: procedures>+≡
subroutine isr_complete_kinematics (sf_int, x, f, r, rb, map)
  class(isr_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(out) :: x
  real(default), intent(out) :: f
  real(default), dimension(:), intent(in) :: r
  real(default), dimension(:), intent(in) :: rb
  logical, intent(in) :: map
  real(default) :: eps
  eps = sf_int%data%eps
  if (map) then
    call map_power_1 (sf_int%xb, f, rb(1), eps)
  else
    sf_int%xb = rb(1)
    if (rb(1) > 0) then
      f = 1
    else
      f = 0
    end if
  end if
  sf_int%x = 1 - sf_int%xb
  x(1) = sf_int%x
  if (size (x) == 3) x(2:3) = r(2:3)
  call sf_int%split_momentum (x, sf_int%xb)
  select case (sf_int%status)
  case (SF_FAILED_KINEMATICS)
    sf_int%x = 0
    sf_int%xb = 0
    f = 0
  end select
end subroutine isr_complete_kinematics

```

Overriding the default method: we compute the x array from the momentum configuration. In the specific case of ISR, we also set the internally stored x and \bar{x} values, so they can be used in the following routine.

Note: the extraction of \bar{x} is not numerically safe, but it can't be as long as the base `recover_x` isn't.

```

<SF isr: isr: TBP>+≡
  procedure :: recover_x => sf_isr_recover_x

<SF isr: procedures>+≡
subroutine sf_isr_recover_x (sf_int, x, x_free)
  class(isr_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(out) :: x
  real(default), intent(inout), optional :: x_free
  call sf_int%base_recover_x (x, x_free)
  sf_int%x = x(1)
  sf_int%xb = 1 - x(1)
end subroutine sf_isr_recover_x

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

For extracting x , we rely on the stored \bar{x} value, since the x value in the argument is likely imprecise. This means that either `complete_kinematics` or `recover_x` must be called first, for the current sampling point (but maybe another channel).

```

<SF isr: isr: TBP>+≡
  procedure :: inverse_kinematics => isr_inverse_kinematics

<SF isr: procedures>+≡
  subroutine isr_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
    class(isr_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    real(default) :: eps
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    eps = sf_int%data%eps
    if (map) then
      call map_power_inverse_1 (sf_int%xb, f, rb(1), eps)
    else
      rb(1) = sf_int%xb
      if (rb(1) > 0) then
        f = 1
      else
        f = 0
      end if
    end if
    r(1) = 1 - rb(1)
    if (size(r) == 3) then
      r(2:3) = x(2:3)
      rb(2:3) = 1 - r(2:3)
    end if
    if (set_mom) then
      call sf_int%split_momentum (x, sf_int%xb)
      select case (sf_int%status)
      case (SF_FAILED_KINEMATICS)
        r = 0
        rb = 0
        f = 0
      end select
    end if
  end subroutine isr_inverse_kinematics

<SF isr: isr: TBP>+≡
  procedure :: init => isr_init

<SF isr: procedures>+≡
  subroutine isr_init (sf_int, data)
    class(isr_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(3) :: mask

```

```

integer, dimension(3) :: hel_lock
type(polarization_t) :: pol
type(quantum_numbers_t), dimension(1) :: qn_fc, qn_hel
type(flavor_t) :: flv_photon
type(color_t) :: col_photon
type(quantum_numbers_t) :: qn_photon, qn
type(state_iterator_t) :: it_hel
real(default) :: m2
integer :: i
mask = quantum_numbers_mask (.false., .false., &
    mask_h = [.false., .true., .false.])
hel_lock = [3, 0, 1]
select type (data)
type is (isr_data_t)
    m2 = data%mass**2
    call sf_int%base_init (mask, [m2], [0._default], [m2], &
        hel_lock = hel_lock)
    sf_int%data => data
    call flv_photon%init (PHOTON, data%model)
    call col_photon%init ()
    call qn_photon%init (flv_photon, col_photon)
    call qn_photon%tag_radiated ()
    do i = 1, size (data%flv_in)
        call polarization_init_generic (pol, data%flv_in(i))
        call qn_fc(1)%init (&
            flv = data%flv_in(i), &
            col = color_from_flavor (data%flv_in(i), 1))
        call it_hel%init (pol%state)
        do while (it_hel%is_valid ())
            qn_hel = it_hel%get_quantum_numbers ()
            qn = qn_hel(1) .merge. qn_fc(1)
            call sf_int%add_state ([qn, qn_photon, qn])
            call it_hel%advance ()
        end do
        call polarization_final (pol)
    end do
    call sf_int%freeze ()
    call sf_int%set_incoming ([1])
    call sf_int%set_radiated ([2])
    call sf_int%set_outgoing ([3])
    sf_int%status = SF_INITIAL
end select
end subroutine isr_init

```

15.6.6 ISR application

For ISR, we could in principle compute kinematics and function value in a single step. In order to be able to reweight matrix elements including structure functions we split kinematics and structure function calculation. The structure function works on a single beam, assuming that the input momentum has been set.

For the structure-function evaluation, we rely on the fact that the power

mapping, which we apply in the kinematics method (if the `map` flag is set), has a Jacobian which is just the inverse lowest-order structure function. With mapping active, the two should cancel exactly.

After splitting momenta, we set the outgoing momenta on-shell. We choose to conserve momentum, so energy conservation may be violated.

```

<SF isr: isr: TBP>+=
  procedure :: apply => isr_apply

<SF isr: procedures>+=
  subroutine isr_apply (sf_int, scale)
    class(isr_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    real(default) :: f, finv, x, xb, eps, rb
    real(default) :: log_x, log_xb, x_2
    real(default), parameter :: &
      & xmin = 0.00714053329734592839549879772019_default
    real(default), parameter :: &
      & zeta3 = 1.20205690315959428539973816151_default
    real(default), parameter :: &
      & g1 = 3._default / 4._default, &
      & g2 = (27 - 8*pi**2) / 96._default, &
      & g3 = (27 - 24*pi**2 + 128*zeta3) / 384._default
    associate (data => sf_int%data)
      eps = sf_int%data%eps
      x = sf_int%x
      xb = sf_int%xb
      call map_power_inverse_1 (xb, finv, rb, eps)
      if (finv > 0) then
        f = 1 / finv
      else
        f = 0
      end if
      if (f > 0 .and. data%order > 0) then
        f = f * (1 + g1 * eps)
        x_2 = x*x
        if (rb>0) f = f * (1 - (1-x_2) / (2 * rb))
        if (data%order > 1) then
          f = f * (1 + g2 * eps**2)
          if (rb>0 .and. xb>0 .and. x>xmin) then
            log_x = log_prec (x, xb)
            log_xb = log_prec (xb, x)
            f = f * (1 - ((1+3*x_2)*log_x + xb * (4*(1+x)*log_xb + 5 + x)) &
              / ( 8 * rb) * eps)
          end if
          if (data%order > 2) then
            f = f * (1 + g3 * eps**3)
            if (rb > 0 .and. xb > 0 .and. x > xmin) then
              f = f * (1 - ((1+x) * xb &
                * (6 * Li2(x) + 12 * log_xb**2 - 3 * pi**2) &
                + 1.5_default * (1 + 8*x + 3*x_2) * log_x &
                + 6 * (x+5) * xb * log_xb &
                + 12 * (1+x_2) * log_x * log_xb &
                - (1 + 7*x_2) * log_x**2 / 2 &
                + (39 - 24*x - 15*x_2) / 4) &

```

```

                                / ( 48 * rb) * eps**2)
        end if
    end if
end if
end associate
call sf_int%set_matrix_element (cmplx (f, kind=default))
sf_int%status = SF_EVALUATED
end subroutine isr_apply

```

15.6.7 Unit tests

```

<SF isr: public>+≡
    public :: sf_isr_test

<SF isr: tests>≡
    subroutine sf_isr_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <SF isr: execute tests>
    end subroutine sf_isr_test

```

Test structure function data

Construct and display a test structure function data object.

```

<SF isr: execute tests>≡
    call test (sf_isr_1, "sf_isr_1", &
        "structure function configuration", &
        u, results)

<SF isr: tests>+≡
    subroutine sf_isr_1 (u)
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(pdg_array_t) :: pdg_in
        type(pdg_array_t), dimension(1) :: pdg_out
        integer, dimension(:), allocatable :: pdg1
        class(sf_data_t), allocatable :: data

        write (u, "(A)")  "* Test output: sf_isr_1"
        write (u, "(A)")  "* Purpose: initialize and display &
            &test structure function data"
        write (u, "(A)")

        write (u, "(A)")  "* Create empty data object"
        write (u, "(A)")

        call model%init_qed_test ()
        pdg_in = ELECTRON

        allocate (isr_data_t :: data)
        call data%write (u)
    end subroutine sf_isr_1

```



```

write (u, "(A)")
write (u, "(A)")  "* Initialize"
write (u, "(A)")

select type (data)
type is (isr_data_t)
  call data%init (model, pdg_in, 1./137._default, 10._default, &
    0.000511_default, order = 3, recoil = .false.)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(2x,99(1x,I0))") pdg1

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_isr_1"

end subroutine sf_isr_1

```

Structure function without mapping

Direct ISR evaluation. This is the use case for a double-beam structure function. The parameter pair is mapped in the calling program.

```

<SF isr: execute tests>+≡
  call test (sf_isr_2, "sf_isr_2", &
    "no ISR mapping", &
    u, results)

<SF isr: tests>+≡
  subroutine sf_isr_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(flavor_t) :: flv
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f, f_isr

    write (u, "(A)")  "* Test output: sf_isr_2"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_qed_test ()
pdg_in = ELECTRON
call flv%init (ELECTRON, model)

call reset_interaction_counter ()

allocate (isr_data_t :: data)
select type (data)
type is (isr_data_t)
    call data%init (model, pdg_in, 1./137._default, 500._default, &
        0.000511_default, order = 3, recoil = .false.)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.9, no ISR mapping, &
    &collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.9_default
rb = 1 - r
write (u, "(A,9(1x," // FMT_12 // "))")  "r =", r
write (u, "(A,9(1x," // FMT_12 // "))")  "rb=", rb

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A)")
write (u, "(A,9(1x," // FMT_12 // "))")  "x =", x
write (u, "(A,9(1x," // FMT_12 // "))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Invert kinematics"

```

```

write (u, "(A)")

call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)
write (u, "(A,9(1x," // FMT_12 // "))") "r =", r
write (u, "(A,9(1x," // FMT_12 // "))") "rb=", rb
write (u, "(A,9(1x," // FMT_12 // "))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate ISR structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Structure-function value, default order"
write (u, "(A)")

f_isr = sf_int%get_matrix_element (1)

write (u, "(A,9(1x," // FMT_12 // "))") "f_isr          =", f_isr
write (u, "(A,9(1x," // FMT_12 // "))") "f_isr * f_map =", f_isr * f

write (u, "(A)")
write (u, "(A)")  "* Re-evaluate structure function, leading order"
write (u, "(A)")

select type (sf_int)
type is (isr_t)
  sf_int%data%order = 0
end select
call sf_int%apply (scale = 100._default)
f_isr = sf_int%get_matrix_element (1)

write (u, "(A,9(1x," // FMT_12 // "))") "f_isr          =", f_isr
write (u, "(A,9(1x," // FMT_12 // "))") "f_isr * f_map =", f_isr * f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_isr_2"

end subroutine sf_isr_2

```

Structure function with mapping

Apply the optimal ISR mapping. This is the use case for a single-beam structure function.

```

<SF isr: execute tests>+≡
  call test (sf_isr_3, "sf_isr_3", &
    "ISR mapping", &
    u, results)

<SF isr: tests>+≡
  subroutine sf_isr_3 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f, f_isr

    write (u, "(A)")  "* Test output: sf_isr_3"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_qed_test ()
    call flv%init (ELECTRON, model)
    pdg_in = ELECTRON

    call reset_interaction_counter ()

    allocate (isr_data_t :: data)
    select type (data)
    type is (isr_data_t)
      call data%init (model, pdg_in, 1./137._default, 500._default, &
        0.000511_default, order = 3, recoil = .false.)
    end select

    write (u, "(A)")  "* Initialize structure-function object"
    write (u, "(A)")

    call data%allocate_sf_int (sf_int)
    call sf_int%init (data)
    call sf_int%set_beam_index ([1])

    write (u, "(A)")  "* Initialize incoming momentum with E=500"
    write (u, "(A)")
    E = 500
    k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
    call pacify (k, 1e-10_default)
    call vector4_write (k, u)
    call sf_int%seed_kinematics ([k])

    write (u, "(A)")

```

```

write (u, "(A)")  "* Set kinematics for r=0.7, with ISR mapping, &
                  &collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.7_default
rb = 1 - r
write (u, "(A,9(1x," // FMT_12 // "))") "r =", r
write (u, "(A,9(1x," // FMT_12 // "))") "rb=", rb

call sf_int%complete_kinematics (x, f, r, rb, map=.true.)

write (u, "(A)")
write (u, "(A,9(1x," // FMT_12 // "))") "x =", x
write (u, "(A,9(1x," // FMT_12 // "))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Invert kinematics"
write (u, "(A)")

call sf_int%inverse_kinematics (x, f, r, rb, map=.true.)
write (u, "(A,9(1x," // FMT_12 // "))") "r =", r
write (u, "(A,9(1x," // FMT_12 // "))") "rb=", rb
write (u, "(A,9(1x," // FMT_12 // "))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate ISR structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Structure-function value, default order"
write (u, "(A)")

f_isr = sf_int%get_matrix_element (1)

write (u, "(A,9(1x," // FMT_12 // "))") "f_isr          =", f_isr
write (u, "(A,9(1x," // FMT_12 // "))") "f_isr * f_map =", f_isr * f

write (u, "(A)")
write (u, "(A)")  "* Re-evaluate structure function, leading order"
write (u, "(A)")

select type (sf_int)
type is (isr_t)
    sf_int%data%order = 0
end select
call sf_int%apply (scale = 100._default)
f_isr = sf_int%get_matrix_element (1)

```

```

write (u, "(A,9(1x," // FMT_12 // "))") "f_isr          =", f_isr
write (u, "(A,9(1x," // FMT_12 // "))") "f_isr * f_map =", f_isr * f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_isr_3"

end subroutine sf_isr_3

```

Non-collinear ISR splitting

Construct and display a structure function object based on the ISR structure function. We blank out numerical fluctuations for 32bit.

```

<SF isr: execute tests>+≡
  call test (sf_isr_4, "sf_isr_4", &
    "ISR non-collinear", &
    u, results)

<SF isr: tests>+≡
  subroutine sf_isr_4 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f, f_isr
    character(len=80) :: buffer
    integer :: u_scratch, iostat

    write (u, "(A)")  "* Test output: sf_isr_4"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_qed_test ()
    call flv%init (ELECTRON, model)
    pdg_in = ELECTRON

    call reset_interaction_counter ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

allocate (isr_data_t :: data)
select type (data)
type is (isr_data_t)
    call data%init (model, pdg_in, 1./137._default, 500._default, &
        0.000511_default, order = 3, recoil = .true.)
end select

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5/0.5/0.25, with ISR mapping, "
write (u, "(A)")  "          non-coll., keeping energy"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = [0.5_default, 0.5_default, 0.25_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)
call interaction_pacify_momenta (sf_int%interaction_t, 1e-10_default)

write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x and r from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

```

```

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.true.)

write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "r =", r

write (u, "(A)")
write (u, "(A)")  "* Evaluate ISR structure function"
write (u, "(A)")

call sf_int%complete_kinematics (x, f, r, rb, map=.true.)
call interaction_pacify_momenta (sf_int%interaction_t, 1e-10_default)
call sf_int%apply (scale = 10._default)
u_scratch = free_unit ()
open (u_scratch, status="scratch", action = "readwrite")
call sf_int%write (u_scratch, testflag = .true.)
rewind (u_scratch)
do
  read (u_scratch, "(A)", iostat=iostat) buffer
  if (iostat /= 0) exit
  if (buffer(1:25) == " P =  0.000000E+00  9.57") then
    buffer = replace (buffer, 26, "XXXX")
  end if
  if (buffer(1:25) == " P =  0.000000E+00 -9.57") then
    buffer = replace (buffer, 26, "XXXX")
  end if
  write (u, "(A)") buffer
end do
close (u_scratch)

write (u, "(A)")
write (u, "(A)")  "* Structure-function value"
write (u, "(A)")

f_isr = sf_int%get_matrix_element (1)

write (u, "(A,9(1x," // FMT_12 // "))") "f_isr      =", f_isr
write (u, "(A,9(1x," // FMT_12 // "))") "f_isr * f_map =", f_isr * f

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_isr_4"

end subroutine sf_isr_4

```


Structure function pair with mapping

Apply the ISR mapping for a ISR pair. structure function.

```
<SF_isr: execute tests>+≡
    call test (sf_isr_5, "sf_isr_5", &
               "ISR pair mapping", &
               u, results)

<SF_isr: tests>+≡
    subroutine sf_isr_5 (u)
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(flavor_t) :: flv
        type(pdg_array_t) :: pdg_in
        class(sf_data_t), allocatable, target :: data
        class(sf_mapping_t), allocatable :: mapping
        class(sf_int_t), dimension(:), allocatable :: sf_int
        type(vector4_t), dimension(2) :: k
        real(default) :: E, f_map
        real(default), dimension(:), allocatable :: p, pb, r, rb, x
        real(default), dimension(2) :: f, f_isr
        integer :: i

        write (u, "(A)")  "* Test output: sf_isr_5"
        write (u, "(A)")  "* Purpose: initialize and fill &
                           &test structure function object"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize configuration data"
        write (u, "(A)")

        call model%init_qed_test ()
        call flv%init (ELECTRON, model)
        pdg_in = ELECTRON

        call reset_interaction_counter ()

        allocate (isr_data_t :: data)
        select type (data)
        type is (isr_data_t)
            call data%init (model, pdg_in, 1./137._default, 500._default, &
                           0.000511_default, order = 3, recoil = .false.)
        end select

        allocate (sf_ip_mapping_t :: mapping)
        select type (mapping)
        type is (sf_ip_mapping_t)
            select type (data)
            type is (isr_data_t)
                call mapping%init (eps = data%eps)
            end select
            call mapping%set_index (1, 1)
            call mapping%set_index (2, 2)
        end select
```

```

call mapping%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

allocate (isr_t :: sf_int (2))

do i = 1, 2
    call sf_int(i)%init (data)
    call sf_int(i)%set_beam_index ([i])
end do

write (u, "(A)")  "* Initialize incoming momenta with E=500"
write (u, "(A)")
E = 500
k(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
k(2) = vector4_moving (E, - sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
do i = 1, 2
    call vector4_write (k(i), u)
    call sf_int(i)%seed_kinematics (k(i:i))
end do

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for p=[0.7,0.4], collinear"
write (u, "(A)")

allocate (p (2 * data%get_n_par ()))
allocate (pb(size (p)))
allocate (r (size (p)))
allocate (rb(size (p)))
allocate (x (size (p)))

p = [0.7_default, 0.4_default]
pb= 1 - p
call mapping%compute (r, rb, f_map, p, pb)

write (u, "(A,9(1x," // FMT_12 // "))")  "p =", p
write (u, "(A,9(1x," // FMT_12 // "))")  "pb=", pb
write (u, "(A,9(1x," // FMT_12 // "))")  "r =", r
write (u, "(A,9(1x," // FMT_12 // "))")  "rb=", rb
write (u, "(A,9(1x," // FMT_12 // "))")  "fm=", f_map

do i = 1, 2
    call sf_int(i)%complete_kinematics (x(i:i), f(i), r(i:i), rb(i:i), &
        map=.false.)
end do

write (u, "(A)")
write (u, "(A,9(1x," // FMT_12 // "))")  "x =", x
write (u, "(A,9(1x," // FMT_12 // "))")  "f =", f

write (u, "(A)")

```

```

write (u, "(A)")  "* Invert kinematics"
write (u, "(A)")

do i = 1, 2
    call sf_int(i)%inverse_kinematics (x(i:i), f(i), r(i:i), rb(i:i), &
        map=.false.)
end do
call mapping%inverse (r, rb, f_map, p, pb)

write (u, "(A,9(1x," // FMT_12 // "))") "p =", p
write (u, "(A,9(1x," // FMT_12 // "))") "pb=", pb
write (u, "(A,9(1x," // FMT_12 // "))") "r =", r
write (u, "(A,9(1x," // FMT_12 // "))") "rb=", rb
write (u, "(A,9(1x," // FMT_12 // "))") "fm=", f_map

write (u, "(A)")
write (u, "(A)")  "* Evaluate ISR structure function"

call sf_int(1)%apply (scale = 100._default)
call sf_int(2)%apply (scale = 100._default)

write (u, "(A)")
write (u, "(A)")  "* Structure function #1"
write (u, "(A)")
call sf_int(1)%write (u)

write (u, "(A)")
write (u, "(A)")  "* Structure function #2"
write (u, "(A)")
call sf_int(2)%write (u)

write (u, "(A)")
write (u, "(A)")  "* Structure-function value, default order"
write (u, "(A)")

do i = 1, 2
    f_isr(i) = sf_int(i)%get_matrix_element (1)
end do

write (u, "(A,9(1x," // FMT_12 // "))") "f_isr          =", &
    product (f_isr)
write (u, "(A,9(1x," // FMT_12 // "))") "f_isr * f_map =", &
    product (f_isr * f) * f_map

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

do i = 1, 2
    call sf_int(i)%final ()
end do
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_isr_5"

```

```
end subroutine sf_isr_5
```

15.7 EPA

```

⟨sf_epa.f90⟩≡
  ⟨File header⟩

  module sf_epa

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use io_units
    use constants, only: pi
    use format_defs, only: FMT_17, FMT_19
    use unit_tests
    use diagnostics
    use physics_defs, only: ELECTRON, PHOTON
    use lorentz
    use pdg_arrays
    use model_data
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux
    use sf_base

    ⟨Standard module head⟩

    ⟨SF epa: public⟩

    ⟨SF epa: parameters⟩

    ⟨SF epa: types⟩

    contains

    ⟨SF epa: procedures⟩

    ⟨SF epa: tests⟩

  end module sf_epa

```

15.7.1 Physics

The EPA structure function for a photon inside an (elementary) particle p with energy E , mass m and charge q_p (e.g., electron) is given by ($\bar{x} \equiv 1 - x$)

$$\begin{aligned}
 f(x) = \frac{\alpha}{\pi} q_p^2 \frac{1}{x} & \left[\left(\bar{x} + \frac{x^2}{2} \right) \ln \frac{Q_{\max}^2}{Q_{\min}^2} \right. \\
 & \left. - \left(1 - \frac{x}{2} \right)^2 \ln \frac{x^2 + \frac{Q_{\max}^2}{E^2}}{x^2 + \frac{Q_{\min}^2}{E^2}} - x^2 \frac{m^2}{Q_{\min}^2} \left(1 - \frac{Q_{\min}^2}{Q_{\max}^2} \right) \right]. \quad (15.52)
 \end{aligned}$$

If no explicit Q bounds are provided, the kinematical bounds are

$$-Q_{\max}^2 = t_0 = -2\bar{x}(E^2 + p\bar{p}) + 2m^2 \approx -4\bar{x}E^2, \quad (15.53)$$

$$-Q_{\min}^2 = t_1 = -2\bar{x}(E^2 - p\bar{p}) + 2m^2 \approx -\frac{x^2}{\bar{x}}m^2. \quad (15.54)$$

The second and third terms in (15.52) are negative definite (and subleading). Noting that $\bar{x} + x^2/2$ is bounded between $1/2$ and 1 , we derive that $f(x)$ is always smaller than

$$\bar{f}(x) = \frac{\alpha}{\pi} q_p^2 \frac{L - 2 \ln x}{x} \quad \text{where} \quad L = \ln \frac{\min(4E_{\max}^2, Q_{\max}^2)}{\max(m^2, Q_{\min}^2)}, \quad (15.55)$$

where we allow for explicit Q bounds that narrow the kinematical range. Therefore, we generate this distribution:

$$\int_{x_0}^{x_1} dx \bar{f}(x) = C(x_0, x_1) \int_0^1 dx' \quad (15.56)$$

We set

$$\ln x = \frac{1}{2} \left\{ L - \sqrt{L^2 - 4 [x' \ln x_1 (L - \ln x_1) + \bar{x}' \ln x_0 (L - \ln x_0)]} \right\} \quad (15.57)$$

such that $x(0) = x_0$ and $x(1) = x_1$ and

$$\frac{dx}{dx'} = \left(\frac{\alpha}{\pi} q_p^2 \right)^{-1} x \frac{C(x_0, x_1)}{L - 2 \ln x} \quad (15.58)$$

with

$$C(x_0, x_1) = \frac{\alpha}{\pi} q_p^2 [\ln x_1 (L - \ln x_1) - \ln x_0 (L - \ln x_0)] \quad (15.59)$$

such that (15.56) is satisfied. Finally, we have

$$\int_{x_0}^{x_1} dx f(x) = C(x_0, x_1) \int_0^1 dx' \frac{f(x(x'))}{\bar{f}(x(x'))} \quad (15.60)$$

where x' is calculated from x via (15.57).

The structure of the mapping is most obvious from:

$$x'(x) = \frac{\log x (L - \log x) - \log x_0 (L - \log x_0)}{\log x_1 (L - \log x_1) - \log x_0 (L - \log x_0)}. \quad (15.61)$$

15.7.2 The EPA data block

The EPA parameters are: α , E_{\max} , m , Q_{\min} , and x_{\min} . Instead of m we can use the incoming particle PDG code as input; from this we can deduce the mass and charge.

Internally we store in addition $C_{0/1} = \frac{\alpha}{\pi} q_e^2 \ln x_{0/1} (L - \ln x_{0/1})$, the c.m. energy squared and the incoming particle mass.

```
<SF epa: public>≡
public :: epa_data_t
```

```

<SF epa: types>≡
  type, extends(sf_data_t) :: epa_data_t
  private
    class(model_data_t), pointer :: model => null ()
    type(flavor_t), dimension(:), allocatable :: flv_in
    real(default) :: alpha
    real(default) :: x_min
    real(default) :: x_max
    real(default) :: q_min
    real(default) :: q_max
    real(default) :: E_max
    real(default) :: mass
    real(default) :: log
    real(default) :: a
    real(default) :: c0
    real(default) :: c1
    real(default) :: dc
    integer :: error = NONE
    logical :: recoil = .false.
  contains
    <SF epa: epa_data: TBP>
  end type epa_data_t

```

Error codes

```

<SF epa: parameters>≡
  integer, parameter :: NONE = 0
  integer, parameter :: ZERO_QMIN = 1
  integer, parameter :: Q_MAX_TOO_SMALL = 2
  integer, parameter :: ZERO_XMIN = 3
  integer, parameter :: MASS_MIX = 4
  integer, parameter :: NO_EPA = 5

<SF epa: epa_data: TBP>≡
  procedure :: init => epa_data_init

<SF epa: procedures>≡
  subroutine epa_data_init &
    (data, model, pdg_in, alpha, x_min, q_min, E_max, mass, recoil)
    class(epa_data_t), intent(inout) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), intent(in) :: pdg_in
    real(default), intent(in) :: alpha, x_min, q_min, E_max
    real(default), intent(in), optional :: mass
    logical, intent(in), optional :: recoil
    integer :: n_flv, i
    data%model => model
    n_flv = pdg_array_get_length (pdg_in)
    allocate (data%flv_in (n_flv))
    do i = 1, n_flv
      call data%flv_in(i)%init (pdg_array_get (pdg_in, i), model)
    end do
    data%alpha = alpha
    data%E_max = E_max
    data%x_min = x_min
    data%x_max = 1
  end subroutine epa_data_init

```

```

if (data%x_min == 0) then
  data%error = ZERO_XMIN; return
end if
data%q_min = q_min
data%q_max = 2 * data%E_max
select case (char (data%model%get_name ()))
case ("QCD","Test")
  data%error = NO_EPA; return
end select
if (present (recoil)) then
  data%recoil = recoil
end if
if (present (mass)) then
  data%mass = mass
else
  data%mass = data%flv_in(1)%get_mass ()
  if (any (data%flv_in%get_mass () /= data%mass)) then
    data%error = MASS_MIX; return
  end if
end if
if (max (data%mass, data%q_min) == 0) then
  data%error = ZERO_QMIN; return
else if (max (data%mass, data%q_min) >= data%E_max) then
  data%error = Q_MAX_TOO_SMALL; return
end if
data%log = log (4 * (data%E_max / max (data%mass, data%q_min)) ** 2 )
data%a = data%alpha / pi
data%c0 = log (data%x_min) * (data%log - log (data%x_min))
data%c1 = log (data%x_max) * (data%log - log (data%x_max))
data%dc = data%c1 - data%c0
end subroutine epa_data_init

```

Handle error conditions. Should always be done after initialization, unless we are sure everything is ok.

```

<SF epa: epa data: TBP>+≡
  procedure :: check => epa_data_check

<SF epa: procedures>+≡
  subroutine epa_data_check (data)
    class(epa_data_t), intent(in) :: data
    select case (data%error)
    case (NO_EPA)
      call msg_fatal ("EPA structure function not available for model " &
        // char (data%model%get_name ()) // ".")
    case (ZERO_QMIN)
      call msg_fatal ("EPA: Particle mass is zero")
    case (Q_MAX_TOO_SMALL)
      call msg_fatal ("EPA: Particle mass exceeds Qmax")
    case (ZERO_XMIN)
      call msg_fatal ("EPA: x_min must be larger than zero")
    case (MASS_MIX)
      call msg_fatal ("EPA: incoming particle masses must be uniform")
    end select
  end subroutine epa_data_check

```


Output

```

<SF epa: epa data: TBP>+≡
  procedure :: write => epa_data_write

<SF epa: procedures>+≡
  subroutine epa_data_write (data, unit, verbose)
    class(epa_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1x,A)") "EPA data:"
    if (allocated (data%flv_in)) then
      write (u, "(3x,A)", advance="no") " flavor = "
      do i = 1, size (data%flv_in)
        if (i > 1) write (u, "(',',1x)", advance="no")
        call data%flv_in(i)%write (u)
      end do
      write (u, *)
      write (u, "(3x,A," // FMT_19 // ")") " alpha = ", data%alpha
      write (u, "(3x,A," // FMT_19 // ")") " x_min = ", data%x_min
      write (u, "(3x,A," // FMT_19 // ")") " x_max = ", data%x_max
      write (u, "(3x,A," // FMT_19 // ")") " q_min = ", data%q_min
      write (u, "(3x,A," // FMT_19 // ")") " q_max = ", data%q_max
      write (u, "(3x,A," // FMT_19 // ")") " E_max = ", data%e_max
      write (u, "(3x,A," // FMT_19 // ")") " mass = ", data%mass
      write (u, "(3x,A," // FMT_19 // ")") " a = ", data%a
      write (u, "(3x,A," // FMT_19 // ")") " c0 = ", data%c0
      write (u, "(3x,A," // FMT_19 // ")") " c1 = ", data%c1
      write (u, "(3x,A," // FMT_19 // ")") " log = ", data%log
      write (u, "(3x,A,L2)") " recoil = ", data%recoil
    else
      write (u, "(3x,A)") "[undefined]"
    end if
  end subroutine epa_data_write

```

The number of kinematic parameters.

```

<SF epa: epa data: TBP>+≡
  procedure :: get_n_par => epa_data_get_n_par

<SF epa: procedures>+≡
  function epa_data_get_n_par (data) result (n)
    class(epa_data_t), intent(in) :: data
    integer :: n
    if (data%recoil) then
      n = 3
    else
      n = 1
    end if
  end function epa_data_get_n_par

```

Return the outgoing particles PDG codes. The outgoing particle is always the photon while the radiated particle is identical to the incoming one.

```

<SF epa: epa_data: TBP>+≡
  procedure :: get_pdg_out => epa_data_get_pdg_out

<SF epa: procedures>+≡
  subroutine epa_data_get_pdg_out (data, pdg_out)
    class(epa_data_t), intent(in) :: data
    type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
    pdg_out(1) = PHOTON
  end subroutine epa_data_get_pdg_out

```

Allocate the interaction record.

```

<SF epa: epa_data: TBP>+≡
  procedure :: allocate_sf_int => epa_data_allocate_sf_int

<SF epa: procedures>+≡
  subroutine epa_data_allocate_sf_int (data, sf_int)
    class(epa_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (epa_t :: sf_int)
  end subroutine epa_data_allocate_sf_int

```

15.7.3 The EPA object

The `epa_t` data type is a $1 \rightarrow 2$ interaction. We should be able to handle several flavors in parallel, since EPA is not necessarily applied immediately after beam collision: Photons may be radiated from quarks. In that case, the partons are massless and q_{\min} applies instead, so we do not need to generate several kinematical configurations in parallel.

The squared charge values multiply the matrix elements, depending on the flavour. We scan the interaction after building it, so we have the correct assignments.

The particles are ordered as (incoming, radiated, photon), where the photon initiates the hard interaction.

We generate an unpolarized photon and transfer initial polarization to the radiated parton. Color is transferred in the same way.

```

<SF epa: types>+≡
  type, extends (sf_int_t) :: epa_t
    type(epa_data_t), pointer :: data => null ()
    real(default) :: x = 0
    real(default) :: xb = 0
    real(default) :: E = 0
    real(default), dimension(:), allocatable :: charge2
  contains
    <SF epa: epa: TBP>
  end type epa_t

```

Type string: has to be here, but there is no string variable on which EPA depends. Hence, a dummy routine.

```

<SF epa: epa: TBP>≡
  procedure :: type_string => epa_type_string

<SF epa: procedures>+≡
  function epa_type_string (object) result (string)
    class(epa_t), intent(in) :: object
    type(string_t) :: string
    if (associated (object%data)) then
      string = "EPA: equivalent photon approx."
    else
      string = "EPA: [undefined]"
    end if
  end function epa_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF epa: epa: TBP>+≡
  procedure :: write => epa_write

<SF epa: procedures>+≡
  subroutine epa_write (object, unit, testflag)
    class(epa_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      if (object%status >= SF_DONE_KINEMATICS) then
        write (u, "(1x,A)") "SF parameters:"
        write (u, "(3x,A," // FMT_17 // ")") "x =", object%x
        if (object%status >= SF_FAILED_EVALUATION) then
          write (u, "(3x,A," // FMT_17 // ")") "E =", object%E
        end if
      end if
      call object%base_write (u, testflag)
    else
      write (u, "(1x,A)") "EPA data: [undefined]"
    end if
  end subroutine epa_write

```

Prepare the interaction object. We have to construct transition matrix elements for all flavor and helicity combinations.

```

<SF epa: epa: TBP>+≡
  procedure :: init => epa_init

<SF epa: procedures>+≡
  subroutine epa_init (sf_int, data)
    class(epa_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(3) :: mask
    integer, dimension(3) :: hel_lock
    type(polarization_t) :: pol

```

```

type(quantum_numbers_t), dimension(1) :: qn_fc, qn_hel
type(flavor_t) :: flv_photon
type(color_t) :: col_photon
type(quantum_numbers_t) :: qn_photon, qn, qn_rad
type(state_iterator_t) :: it_hel
integer :: i
mask = quantum_numbers_mask (.false., .false., &
    mask_h = [.false., .false., .true.])
hel_lock = [2, 1, 0]
select type (data)
type is (epa_data_t)
    call sf_int%base_init (mask, [data%mass**2], &
        [data%mass**2], [0._default], hel_lock = hel_lock)
    sf_int%data => data
    call flv_photon%init (PHOTON, data%model)
    call col_photon%init ()
    call qn_photon%init (flv_photon, col_photon)
    do i = 1, size (data%flv_in)
        call polarization_init_generic (pol, data%flv_in(i))
        call qn_fc(1)%init ( &
            flv = data%flv_in(i), &
            col = color_from_flavor (data%flv_in(i), 1))
        call it_hel%init (pol%state)
        do while (it_hel%is_valid ())
            qn_hel = it_hel%get_quantum_numbers ()
            qn = qn_hel(1) .merge. qn_fc(1)
            qn_rad = qn
            call qn_rad%tag_radiated ()
            call sf_int%add_state ([qn, qn_rad, qn_photon])
            call it_hel%advance ()
        end do
        call polarization_final (pol)
    end do
    call sf_int%freeze ()
    call sf_int%set_incoming ([1])
    call sf_int%set_radiated ([2])
    call sf_int%set_outgoing ([3])
end select
end subroutine epa_init

```

Prepare the charge array. This is separate from the previous routine since the state matrix may be helicity-contracted.

```

<SF epa: epa: TBP>+≡
    procedure :: setup_constants => epa_setup_constants

<SF epa: procedures>+≡
    subroutine epa_setup_constants (sf_int)
        class(epa_t), intent(inout) :: sf_int
        type(state_iterator_t) :: it
        type(flavor_t) :: flv
        integer :: i, n_me
        n_me = sf_int%get_n_matrix_elements ()
        allocate (sf_int%charge2 (n_me))
        call it%init (sf_int%interaction_t%get_state_matrix_ptr ())
    end subroutine

```

```

do while (it%is_valid ())
  i = it%get_me_index ()
  flv = it%get_flavor (1)
  sf_int%charge2(i) = flv%get_charge () ** 2
  call it%advance ()
end do
sf_int%status = SF_INITIAL
end subroutine epa_setup_constants

```

15.7.4 Kinematics

Set kinematics. If *map* is unset, the *r* and *x* values coincide, and the Jacobian $f(r)$ is trivial.

The EPA structure function allows for a straightforward mapping of the unit interval. The *x* value is transformed, and the mapped structure function becomes unity at its upper boundary.

The structure function implementation applies the above mapping to the input (random) number *r* to generate the momentum fraction *x* and the function value *f*. For numerical stability reasons, we also output *xb*, which is $\bar{x} = 1 - x$.

(SF epa: epa: TBP)+≡

```

procedure :: complete_kinematics => epa_complete_kinematics

```

(SF epa: procedures)+≡

```

subroutine epa_complete_kinematics (sf_int, x, f, r, rb, map)
  class(epa_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(out) :: x
  real(default), intent(out) :: f
  real(default), dimension(:), intent(in) :: r
  real(default), dimension(:), intent(in) :: rb
  logical, intent(in) :: map
  real(default) :: xb1
  real(default) :: delta, sqrt_delta, lx
  if (map) then
    associate (data => sf_int%data)
      delta = data%log ** 2 - 4 * (r(1) * data%c1 + rb(1) * data%c0)
      if (delta > 0) then
        sqrt_delta = sqrt (delta)
        lx = (data%log - sqrt_delta) / 2
      else
        sf_int%status = SF_FAILED_KINEMATICS
        f = 0
        return
      end if
      x(1) = exp (lx)
      f = x(1) * data%dc / sqrt_delta
    end associate
  else
    x(1) = r(1)
    if (sf_int%data%x_min < x(1) .and. x(1) < sf_int%data%x_max) then
      f = 1
    else
      sf_int%status = SF_FAILED_KINEMATICS
    end if
  end if
end subroutine

```

```

        f = 0
        return
    end if
end if
xb1 = 1 - x(1)
if (size(x) == 3) x(2:3) = r(2:3)
call sf_int%split_momentum (x, xb1)
select case (sf_int%status)
case (SF_DONE_KINEMATICS)
    sf_int%x = x(1)
    sf_int%xb= xb1
    sf_int%E = energy (sf_int%get_momentum (1))
case (SF_FAILED_KINEMATICS)
    sf_int%x = 0
    sf_int%xb= 0
    f = 0
end select
end subroutine epa_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

<SF epa: epa: TBP>+≡
    procedure :: inverse_kinematics => epa_inverse_kinematics

<SF epa: procedures>+≡
    subroutine epa_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
        class(epa_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(in) :: x
        real(default), intent(out) :: f
        real(default), dimension(:), intent(out) :: r
        real(default), dimension(:), intent(out) :: rb
        logical, intent(in) :: map
        logical, intent(in), optional :: set_momenta
        real(default) :: lx, delta, sqrt_delta, c
        logical :: set_mom
        set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
        if (map) then
            associate (data => sf_int%data)
                lx = log (x(1))
                sqrt_delta = data%log - 2 * lx
                delta = sqrt_delta ** 2
                c = (data%log ** 2 - delta) / 4
                r (1) = (c - data%c0) / data%dc
                rb(1) = (data%c1 - c) / data%dc
                f = x(1) * data%dc / sqrt_delta
            end associate
        else
            r (1) = x(1)
            rb(1) = 1 - x(1)
            if (sf_int%data%x_min < x(1) .and. x(1) < sf_int%data%x_max) then
                f = 1
            else
                f = 0
            end if
        end if
    end subroutine

```

```

        end if
    end if
    if (size(r) == 3) then
        r (2:3) = x(2:3)
        rb(2:3) = 1 - x(2:3)
    end if
    if (set_mom) then
        call sf_int%split_momentum (x, sf_int%xb)
        select case (sf_int%status)
        case (SF_DONE_KINEMATICS)
            sf_int%x = x(1)
            sf_int%xb = 1 - x(1)
            sf_int%E = energy (sf_int%get_momentum (1))
        case (SF_FAILED_KINEMATICS)
            sf_int%x = 0
            f = 0
        end select
    end if
end subroutine epa_inverse_kinematics

```

Overriding the default method: we compute the x array from the momentum configuration. In the specific case of EPA, we also set the internally stored x and \bar{x} values, so they can be used in the following routine.

Note: the extraction of \bar{x} is not numerically safe, but it can't be as long as the base `recover_x` isn't.

```

⟨SF epa: epa: TBP⟩+=
    procedure :: recover_x => sf_epa_recover_x

⟨SF epa: procedures⟩+=
    subroutine sf_epa_recover_x (sf_int, x, x_free)
        class(epa_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: x
        real(default), intent(inout), optional :: x_free
        call sf_int%base_recover_x (x, x_free)
        sf_int%x = x(1)
        sf_int%xb = 1 - x(1)
    end subroutine sf_epa_recover_x

```

15.7.5 EPA application

For EPA, we can in principle compute kinematics and function value in a single step. In order to be able to reweight events, kinematics and structure function application are separated. This function works on a single beam, assuming that the input momentum has been set. We need three random numbers as input: one for x , and two for the polar and azimuthal angles. Alternatively, for the no-recoil case, we can skip p_T generation; in this case, we only need one.

For obtaining splitting kinematics, we rely on the assumption that all in-particles are mass-degenerate (or there is only one), so the generated x values are identical.

```

⟨SF epa: epa: TBP⟩+=
    procedure :: apply => epa_apply

```

```

<SF epa: procedures>+≡
subroutine epa_apply (sf_int, scale)
  class(epa_t), intent(inout) :: sf_int
  real(default), intent(in) :: scale
  real(default) :: x, xb, qminsq, qmaxsq, f, E
  associate (data => sf_int%data)
    x = sf_int%x
    xb= sf_int%xb
    E = sf_int%E
    qminsq = max (x ** 2 / xb * data%mass ** 2, data%q_min ** 2)
    qmaxsq = min (4 * xb * E ** 2, data%q_max ** 2)
    if (qminsq < qmaxsq) then
      f = data%a / x &
        * ((xb + x ** 2 / 2) * log (qmaxsq / qminsq) &
          - (1 - x / 2) ** 2 &
          * log ((x**2 + qmaxsq / E ** 2) / (x**2 + qminsq / E ** 2)) &
          - x ** 2 * data%mass ** 2 / qminsq * (1 - qminsq / qmaxsq))
    else
      f = 0
    end if
    call sf_int%set_matrix_element &
      (cplx (f, kind=default) * sf_int%charge2)
  end associate
  sf_int%status = SF_EVALUATED
end subroutine epa_apply

```

15.7.6 Unit tests

```

<SF epa: public>+≡
public :: sf_epa_test

<SF epa: tests>≡
subroutine sf_epa_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
  <SF epa: execute tests>
end subroutine sf_epa_test

```

Test structure function data

Construct and display a test structure function data object.

```

<SF epa: execute tests>≡
call test (sf_epa_1, "sf_epa_1", &
  "structure function configuration", &
  u, results)

<SF epa: tests>+≡
subroutine sf_epa_1 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(pdg_array_t) :: pdg_in
  type(pdg_array_t), dimension(1) :: pdg_out

```



```

integer, dimension(:), allocatable :: pdg1
class(sf_data_t), allocatable :: data

write (u, "(A)")  "* Test output: sf_epa_1"
write (u, "(A)")  "*   Purpose: initialize and display &
                    &test structure function data"
write (u, "(A)")

write (u, "(A)")  "* Create empty data object"
write (u, "(A)")

call model%init_qed_test ()
pdg_in = ELECTRON

allocate (epa_data_t :: data)
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize"
write (u, "(A)")

select type (data)
type is (epa_data_t)
    call data%init (model, pdg_in, 1./137._default, 0.01_default, &
                    10._default, 50._default, 0.000511_default, recoil = .false.)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(2x,99(1x,I0))") pdg1

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_epa_1"

end subroutine sf_epa_1

```

Test and probe structure function

Construct and display a structure function object based on the EPA structure function.

```

<SF epa: execute tests>+≡
call test (sf_epa_2, "sf_epa_2", &
           "structure function instance", &
           u, results)

```

$\langle SF \text{ epa: tests} \rangle + \equiv$

```

subroutine sf_epa_2 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(flavor_t) :: flv
  type(pdg_array_t) :: pdg_in
  class(sf_data_t), allocatable, target :: data
  class(sf_int_t), allocatable :: sf_int
  type(vector4_t) :: k
  type(vector4_t), dimension(2) :: q
  real(default) :: E
  real(default), dimension(:), allocatable :: r, rb, x
  real(default) :: f

  write (u, "(A)")  "* Test output: sf_epa_2"
  write (u, "(A)")  "* Purpose: initialize and fill &
    &test structure function object"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize configuration data"
  write (u, "(A)")

  call model%init_qed_test ()
  call flv%init (ELECTRON, model)
  pdg_in = ELECTRON

  call reset_interaction_counter ()

  allocate (epa_data_t :: data)
  select type (data)
  type is (epa_data_t)
    call data%init (model, pdg_in, 1./137._default, 0.01_default, &
      10._default, 50._default, 0.000511_default, recoil = .false.)
  end select

  write (u, "(A)")  "* Initialize structure-function object"
  write (u, "(A)")

  call data%allocate_sf_int (sf_int)
  call sf_int%init (data)
  call sf_int%set_beam_index ([1])
  call sf_int%setup_constants ()

  write (u, "(A)")  "* Initialize incoming momentum with E=500"
  write (u, "(A)")
  E = 500
  k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
  call pacify (k, 1e-10_default)
  call vector4_write (k, u)
  call sf_int%seed_kinematics ([k])

  write (u, "(A)")
  write (u, "(A)")  "* Set kinematics for r=0.4, no EPA mapping, collinear"
  write (u, "(A)")

```

```

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.4_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "rb=", rb
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false., &
    set_momenta=.true.)

write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "rb=", rb
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EPA structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_epa_2"

```

```
end subroutine sf_epa_2
```

Standard mapping

Construct and display a structure function object based on the EPA structure function, applying the standard single-particle mapping.

```
<SF epa: execute tests>+≡
  call test (sf_epa_3, "sf_epa_3", &
    "apply mapping", &
    u, results)

<SF epa: tests>+≡
  subroutine sf_epa_3 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_epa_3"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_qed_test ()
    call flv%init (ELECTRON, model)
    pdg_in = ELECTRON

    call reset_interaction_counter ()

    allocate (epa_data_t :: data)
    select type (data)
    type is (epa_data_t)
      call data%init (model, pdg_in, 1./137._default, 0.01_default, &
        10._default, 50._default, 0.000511_default, recoil = .false.)
    end select

    write (u, "(A)")  "* Initialize structure-function"
    write (u, "(A)")

    call data%allocate_sf_int (sf_int)
    call sf_int%init (data)
    call sf_int%set_beam_index ([1])
    call sf_int%setup_constants ()
```

```

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.4, with EPA mapping, collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.4_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.true., &
    set_momenta=.true.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EPA structure function"
write (u, "(A)")

```

```

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_epa_3"

end subroutine sf_epa_3

```

Non-collinear case

Construct and display a structure function object based on the EPA structure function.

```

<SF epa: execute tests>+≡
  call test (sf_epa_4, "sf_epa_4", &
    "non-collinear", &
    u, results)

<SF epa: tests>+≡
  subroutine sf_epa_4 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E, m
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_epa_4"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_qed_test ()
    call flv%init (ELECTRON, model)
    pdg_in = ELECTRON

    call reset_interaction_counter ()

    allocate (epa_data_t :: data)
    select type (data)

```

```

type is (epa_data_t)
  call data%init (model, pdg_in, 1./137._default, 0.01_default, &
    10._default, 50._default, 5.0_default, recoil = .true.)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

write (u, "(A)")  "* Initialize incoming momentum with E=500, me = 5 GeV"
write (u, "(A)")
E = 500
m = 5
k = vector4_moving (E, sqrt (E**2 - m**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.5/0.5/0.25, with EPA mapping, "
write (u, "(A)")  "          non-coll., keeping energy, me = 5 GeV"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = [0.5_default, 0.5_default, 0.25_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)
call interaction_pacify_momenta (sf_int%interaction_t, 1e-10_default)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x and r from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

```

```

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.true., &
    set_momenta=.true.)
call interaction_pacify_momenta (sf_int%interaction_t, 1e-10_default)

write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "rb=", rb
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EPA structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u, testflag = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_epa_4"

end subroutine sf_epa_4

```

Structure function for multiple flavors

Construct and display a structure function object based on the EPA structure function. The incoming state has multiple particles with non-uniform charge.

```

<SF epa: execute tests>+≡
    call test (sf_epa_5, "sf_epa_5", &
        "multiple flavors", &
        u, results)

<SF epa: tests>+≡
subroutine sf_epa_5 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

```



```

write (u, "(A)")  "* Test output: sf_epa_5"
write (u, "(A)")  "* Purpose: initialize and fill &
                  &test structure function object"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_sm_test ()
call flv%init (1, model)
pdg_in = [1, 2, -1, -2]

call reset_interaction_counter ()

allocate (epa_data_t :: data)
select type (data)
type is (epa_data_t)
    call data%init (model, pdg_in, 1./137._default, 0.01_default, &
                  10._default, 50._default, 0.000511_default, recoil = .false.)
    call data%check ()
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.4, no EPA mapping, collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb (size (r)))
allocate (x (size (r)))

r = 0.4_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

```

```

write (u, "(A)")
write (u, "(A)")  "* Evaluate EPA structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_epa_5"

end subroutine sf_epa_5

```

15.8 EWA

```
(sf_ewa.f90)≡  
  <File header>  
  
  module sf_ewa  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use constants, only: pi  
    use format_defs, only: FMT_17, FMT_19  
    use unit_tests  
    use diagnostics  
    use physics_defs, only: W_BOSON, Z_BOSON  
    use lorentz  
    use pdg_arrays  
    use model_data  
    use flavors  
    use colors  
    use quantum_numbers  
    use state_matrices  
    use polarizations  
    use interactions  
    use sf_aux  
    use sf_base  
  
    <Standard module head>  
  
    <SF ewa: public>  
  
    <SF ewa: parameters>  
  
    <SF ewa: types>  
  
    contains  
  
    <SF ewa: procedures>  
  
    <SF ewa: tests>  
  
  end module sf_ewa
```

15.8.1 Physics

The EWA structure function for a Z or W inside a fermion (lepton or quark) depends on the vector-boson polarization. We distinguish transversal (\pm) and

longitudinal (0) polarization.

$$F_+(x) = \frac{1}{16\pi^2} \frac{(v-a)^2 + (v+a)^2 \bar{x}^2}{x} \left[\ln \left(\frac{p_{\perp,\max}^2 + \bar{x}M^2}{\bar{x}M^2} \right) - \frac{p_{\perp,\max}^2}{p_{\perp,\max}^2 + \bar{x}M^2} \right] \quad (15.62)$$

$$F_-(x) = \frac{1}{16\pi^2} \frac{(v+a)^2 + (v-a)^2 \bar{x}^2}{x} \left[\ln \left(\frac{p_{\perp,\max}^2 + \bar{x}M^2}{\bar{x}M^2} \right) - \frac{p_{\perp,\max}^2}{p_{\perp,\max}^2 + \bar{x}M^2} \right] \quad (15.63)$$

$$F_0(x) = \frac{v^2 + a^2}{8\pi^2} \frac{2\bar{x}}{x} \frac{p_{\perp,\max}^2}{p_{\perp,\max}^2 + \bar{x}M^2} \quad (15.64)$$

where $p_{\perp,\max}$ is the cutoff in transversal momentum, M is the vector-boson mass, v and a are the vector and axial-vector couplings, and $\bar{x} \equiv 1-x$. Note that the longitudinal structure function is finite for large cutoff, while the transversal structure function is logarithmically divergent.

The maximal transverse momentum is given by the kinematical limit, it is

$$p_{\perp,\max} = \bar{x}\sqrt{s}/2. \quad (15.65)$$

The vector and axial couplings for a fermion branching into a W are

$$v_W = \frac{g}{2\sqrt{2}}, \quad a_W = \frac{g}{2\sqrt{2}}. \quad (15.66)$$

For Z emission, this is replaced by

$$v_Z = \frac{g}{2\cos\theta_w} (t_3 - 2q\sin^2\theta_w), \quad a_Z = \frac{g}{2\cos\theta_w} t_3, \quad (15.67)$$

where $t_3 = \pm\frac{1}{2}$ is the fermion isospin, and q its charge.

For an initial antifermion, the signs of the axial couplings are inverted. Note that a common sign change of v and a is irrelevant.

The EWA depends on the parameters g , $\sin^2\theta_w$, M_W , and M_Z . These can all be taken from the SM input, and the prefactors are calculated from those and the incoming particle type.

Since these structure functions have a $1/x$ singularity (which is not really relevant in practice, however, since the vector boson mass is finite), we map this singularity allowing for nontrivial x bounds:

$$x = \exp(\bar{r} \ln x_0 + r \ln x_1) \quad (15.68)$$

such that

$$\int_{x_0}^{x_1} \frac{dx}{x} = (\ln x_1 - \ln x_0) \int_0^1 dr. \quad (15.69)$$

As a user parameter, we have the cutoff $p_{\perp,\max}$. The divergence $1/x$ also requires a x_0 cutoff; and for completeness we introduce a corresponding x_1 . Physically, the minimal sensible value of x is M^2/s , although the approximation loses its value already at higher x values.

15.8.2 The EWA data block

The EWA parameters are: $p_{T,\max}$, c_V , c_A , and m . Instead of m we can use the incoming particle PDG code as input; from this we can deduce the mass and charges. In the initialization phase it is not yet determined whether a W or a Z is radiated, hence we set the vector and axial-vector couplings equal to the common prefactors $g/2 = e/2/\sin\theta_W$.

In principle, for EWA it would make sense to allow the user to also set the upper bound for x , x_{\max} , but we fix it to one here.

```

<SF ewa: public>≡
    public :: ewa_data_t

<SF ewa: types>≡
    type, extends(sf_data_t) :: ewa_data_t
        private
        class(model_data_t), pointer :: model => null ()
        type(flavor_t), dimension(:), allocatable :: flv_in
        type(flavor_t), dimension(:), allocatable :: flv_out
        real(default) :: pt_max
        real(default) :: sqrts
        real(default) :: x_min
        real(default) :: x_max
        real(default) :: mass
        real(default) :: m_out
        real(default) :: q_min
        real(default) :: cv
        real(default) :: ca
        real(default) :: costhw
        real(default) :: sinthw
        real(default) :: mW
        real(default) :: mZ
        real(default) :: coeff
        logical :: mass_set = .false.
        logical :: keep_momentum
        logical :: keep_energy
        integer :: id = 0
        integer :: error = NONE
    contains
        <SF ewa: ewa data: TBP>
    end type ewa_data_t

```

Error codes

```

<SF ewa: parameters>≡
    integer, parameter :: NONE = 0
    integer, parameter :: ZERO_QMIN = 1
    integer, parameter :: Q_MAX_TOO_SMALL = 2
    integer, parameter :: ZERO_XMIN = 3
    integer, parameter :: MASS_MIX = 4
    integer, parameter :: ZERO_SW = 5
    integer, parameter :: ISOSPIN_MIX = 6
    integer, parameter :: WRONG_PRT = 7
    integer, parameter :: MASS_MIX_OUT = 8
    integer, parameter :: NO_EWA = 9

```

```

<SF ewa: ewa data: TBP>≡
  procedure :: init => ewa_data_init

<SF ewa: procedures>≡
  subroutine ewa_data_init (data, model, pdg_in, x_min, pt_max, &
    sqrts, keep_momentum, keep_energy, mass)
    class(ewa_data_t), intent(inout) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), intent(in) :: pdg_in
    real(default), intent(in) :: x_min, pt_max, sqrts
    logical, intent(in) :: keep_momentum, keep_energy
    real(default), intent(in), optional :: mass
    real(default) :: g, ee
    integer :: n_flv, i
    data%model => model
    if (.not. any (pdg_in .match. &
      [1,2,3,4,5,6,11,13,15,-1,-2,-3,-4,-5,-6,-11,-13,-15])) then
      data%error = WRONG_PRT; return
    end if
    n_flv = pdg_array_get_length (pdg_in)
    allocate (data%flv_in (n_flv))
    allocate (data%flv_out(n_flv))
    do i = 1, n_flv
      call data%flv_in(i)%init (pdg_array_get (pdg_in, i), model)
    end do
    data%pt_max = pt_max
    data%sqrts = sqrts
    data%x_min = x_min
    data%x_max = 1
    if (data%x_min == 0) then
      data%error = ZERO_XMIN; return
    end if
    select case (char (data%model%get_name ()))
    case ("QCD","QED","Test")
      data%error = NO_EWA; return
    end select
    ee = data%model%get_real (var_str ("ee"))
    data%sinhw = data%model%get_real (var_str ("sw"))
    data%costhw = data%model%get_real (var_str ("cw"))
    data%mZ = data%model%get_real (var_str ("mZ"))
    data%mW = data%model%get_real (var_str ("mW"))
    if (data%sinhw /= 0) then
      g = ee / data%sinhw
    else
      data%error = ZERO_SW; return
    end if
    data%cv = g / 2._default
    data%ca = g / 2._default
    data%coeff = 1._default / (8._default * PI**2)
    data%keep_momentum = keep_momentum
    data%keep_energy = keep_energy
    if (present (mass)) then
      data%mass = mass
      data%m_out = mass
      data%mass_set = .true.

```

```

else
  data%mass = data%flv_in(1)%get_mass ()
  if (any (data%flv_in%get_mass () /= data%mass)) then
    data%error = MASS_MIX; return
  end if
end if
end if
end subroutine ewa_data_init

```

Set the vector boson ID for distinguishing W and Z bosons.

```

<SF ewa: ewa data: TBP>+=
  procedure :: set_id => ewa_set_id

<SF ewa: procedures>+=
  subroutine ewa_set_id (data, id)
    class(ewa_data_t), intent(inout) :: data
    integer, intent(in) :: id
    integer :: i, isospin, pdg
    if (.not. allocated (data%flv_in)) &
      call msg_bug ("EWA: incoming particles not set")
    data%id = id
    select case (data%id)
    case (23)
      data%m_out = data%mass
      data%flv_out = data%flv_in
    case (24)
      do i = 1, size (data%flv_in)
        pdg = data%flv_in(i)%get_pdg ()
        isospin = data%flv_in(i)%get_isospin_type ()
        if (isospin > 0) then
          !!! up-type quark or neutrinos
          if (data%flv_in(i)%is_antiparticle ()) then
            call data%flv_out(i)%init (pdg + 1, data%model)
          else
            call data%flv_out(i)%init (pdg - 1, data%model)
          end if
        else
          !!! down-type quark or lepton
          if (data%flv_in(i)%is_antiparticle ()) then
            call data%flv_out(i)%init (pdg - 1, data%model)
          else
            call data%flv_out(i)%init (pdg + 1, data%model)
          end if
        end if
      end do
      if (.not. data%mass_set) then
        data%m_out = data%flv_out(1)%get_mass ()
        if (any (data%flv_out%get_mass () /= data%m_out)) then
          data%error = MASS_MIX_OUT; return
        end if
      end if
    end select
  end subroutine ewa_set_id

```

Handle error conditions. Should always be done after initialization, unless we are sure everything is ok.

```

<SF ewa: ewa data: TBP>+≡
  procedure :: check => ewa_data_check

<SF ewa: procedures>+≡
  subroutine ewa_data_check (data)
    class(ewa_data_t), intent(in) :: data
    select case (data%error)
    case (WRONG_PRT)
      call msg_fatal ("EWA structure function only accessible for " &
        // "SM quarks and leptons.")
    case (NO_EWA)
      call msg_fatal ("EWA structure function not available for model " &
        // char (data%model%get_name ()))
    case (ZERO_SW)
      call msg_fatal ("EWA: Vanishing value of sin(theta_w)")
    case (ZERO_QMIN)
      call msg_fatal ("EWA: Particle mass is zero")
    case (Q_MAX_TOO_SMALL)
      call msg_fatal ("EWA: Particle mass exceeds Qmax")
    case (ZERO_XMIN)
      call msg_fatal ("EWA: x_min must be larger than zero")
    case (MASS_MIX)
      call msg_fatal ("EWA: incoming particle masses must be uniform")
    case (MASS_MIX_OUT)
      call msg_fatal ("EWA: outgoing particle masses must be uniform")
    case (ISOSPIN_MIX)
      call msg_fatal ("EWA: incoming particle isospins must be uniform")
    end select
  end subroutine ewa_data_check

```

Output

```

<SF ewa: ewa data: TBP>+≡
  procedure :: write => ewa_data_write

<SF ewa: procedures>+≡
  subroutine ewa_data_write (data, unit, verbose)
    class(ewa_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1x,A)") "EWA data:"
    if (allocated (data%flv_in) .and. allocated (data%flv_out)) then
      write (u, "(3x,A)", advance="no") " flavor(in) = "
      do i = 1, size (data%flv_in)
        if (i > 1) write (u, "(',',1x)", advance="no")
        call data%flv_in(i)%write (u)
      end do
    end if
    write (u, *)
    write (u, "(3x,A)", advance="no") " flavor(out) = "
    do i = 1, size (data%flv_out)
      if (i > 1) write (u, "(',',1x)", advance="no")
    end do
  end subroutine ewa_data_write

```



```

        call data%flv_out(i)%write (u)
    end do
    write (u, *)
    write (u, "(3x,A," // FMT_19 // ")") " x_min      = ", data%x_min
    write (u, "(3x,A," // FMT_19 // ")") " x_max      = ", data%x_max
    write (u, "(3x,A," // FMT_19 // ")") " pt_max     = ", data%pt_max
    write (u, "(3x,A," // FMT_19 // ")") " sqrts      = ", data%sqrts
    write (u, "(3x,A," // FMT_19 // ")") " mass       = ", data%mass
    write (u, "(3x,A," // FMT_19 // ")") " cv         = ", data%cv
    write (u, "(3x,A," // FMT_19 // ")") " ca         = ", data%ca
    write (u, "(3x,A," // FMT_19 // ")") " coeff      = ", data%coeff
    write (u, "(3x,A," // FMT_19 // ")") " costhw     = ", data%costhw
    write (u, "(3x,A," // FMT_19 // ")") " sinthw     = ", data%sinhw
    write (u, "(3x,A," // FMT_19 // ")") " mZ         = ", data%mZ
    write (u, "(3x,A," // FMT_19 // ")") " mW         = ", data%mW
    write (u, "(3x,A,L2)") " keep_mom. = ", data%keep_momentum
    write (u, "(3x,A,L2)") " keep_en.  = ", data%keep_energy
    write (u, "(3x,A,I2)") " PDG (VB) = ", data%id
else
    write (u, "(3x,A)") "[undefined]"
end if
end subroutine ewa_data_write

```

The number of parameters is one for collinear splitting, in case one of the options `keep_energy` or `keep_momentum` is set, we take the recoil into account.

```

<SF ewa: ewa data: TBP>+≡
    procedure :: get_n_par => ewa_data_get_n_par

<SF ewa: procedures>+≡
    function ewa_data_get_n_par (data) result (n)
        class(ewa_data_t), intent(in) :: data
        integer :: n
        if (data%keep_energy .or. data%keep_momentum) then
            n = 3
        else
            n = 1
        end if
    end function ewa_data_get_n_par

```

Return the outgoing particles PDG codes. This depends, whether this is a charged-current or neutral-current interaction.

```

<SF ewa: ewa data: TBP>+≡
    procedure :: get_pdg_out => ewa_data_get_pdg_out

<SF ewa: procedures>+≡
    subroutine ewa_data_get_pdg_out (data, pdg_out)
        class(ewa_data_t), intent(in) :: data
        type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
        integer, dimension(:), allocatable :: pdg1
        integer :: i, n_flv
        if (allocated (data%flv_out)) then
            n_flv = size (data%flv_out)
        else
            n_flv = 0
        end if
    end subroutine ewa_data_get_pdg_out

```

```

end if
allocate (pdg1 (n_flv))
do i = 1, n_flv
    pdg1(i) = data%flv_out(i)%get_pdg ()
end do
pdg_out(1) = pdg1
end subroutine ewa_data_get_pdg_out

```

Allocate the interaction record.

```

<SF ewa: ewa data: TBP>+≡
    procedure :: allocate_sf_int => ewa_data_allocate_sf_int

<SF ewa: procedures>+≡
    subroutine ewa_data_allocate_sf_int (data, sf_int)
        class(ewa_data_t), intent(in) :: data
        class(sf_int_t), intent(inout), allocatable :: sf_int
        allocate (ewa_t :: sf_int)
    end subroutine ewa_data_allocate_sf_int

```

15.8.3 The EWA object

The `ewa_t` data type is a $1 \rightarrow 2$ interaction. We should be able to handle several flavors in parallel, since EWA is not necessarily applied immediately after beam collision: W/Z bosons may be radiated from quarks. In that case, the partons are massless and q_{\min} applies instead, so we do not need to generate several kinematical configurations in parallel.

The particles are ordered as (incoming, radiated, W/Z), where the W/Z initiates the hard interaction.

In the case of EPA, we generated an unpolarized photon and transferred initial polarization to the radiated parton. Color is transferred in the same way. I do not know whether the same can/should be done for EWA, as the structure functions depend on the W/Z polarization. If we are having Z bosons, both up- and down-type fermions can participate. Otherwise, with a W^+ an up-type fermion is transferred to a down-type fermion, and the other way round.

```

<SF ewa: types>+≡
    type, extends (sf_int_t) :: ewa_t
        type(ewa_data_t), pointer :: data => null ()
        real(default) :: x = 0
        real(default) :: xb = 0
        integer :: n_me = 0
        real(default), dimension(:), allocatable :: cv
        real(default), dimension(:), allocatable :: ca
    contains
        <SF ewa: ewa: TBP>
    end type ewa_t

```

Type string: has to be here, but there is no string variable on which EWA depends. Hence, a dummy routine.

```

<SF ewa: ewa: TBP>≡
    procedure :: type_string => ewa_type_string

```

```

<SF ewa: procedures>+≡
function ewa_type_string (object) result (string)
  class(ewa_t), intent(in) :: object
  type(string_t) :: string
  if (associated (object%data)) then
    string = "EWA: equivalent W/Z approx."
  else
    string = "EWA: [undefined]"
  end if
end function ewa_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF ewa: ewa: TBP>+≡
  procedure :: write => ewa_write

<SF ewa: procedures>+≡
  subroutine ewa_write (object, unit, testflag)
    class(ewa_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      if (object%status >= SF_DONE_KINEMATICS) then
        write (u, "(1x,A)") "SF parameters:"
        write (u, "(3x,A," // FMT_17 // ")") "x =", object%x
      end if
      call object%base_write (u, testflag)
    else
      write (u, "(1x,A)") "EWA data: [undefined]"
    end if
  end subroutine ewa_write

```

The current implementation requires uniform isospin for all incoming particles, therefore we need to probe only the first one.

```

<SF ewa: ewa: TBP>+≡
  procedure :: init => ewa_init

<SF ewa: procedures>+≡
  subroutine ewa_init (sf_int, data)
    class(ewa_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(3) :: mask
    integer, dimension(3) :: hel_lock
    type(polarization_t) :: pol
    type(quantum_numbers_t), dimension(1) :: qn_fc, qn_hel, qn_fc_fin
    type(flavor_t) :: flv_z, flv_wp, flv_wm
    type(color_t) :: col0
    type(quantum_numbers_t) :: qn_z, qn_wp, qn_wm, qn, qn_rad, qn_w
    type(state_iterator_t) :: it_hel
    integer :: i, isospin
    select type (data)
      type is (ewa_data_t)

```

```

mask = quantum_numbers_mask (.false., .false., &
    mask_h = [.false., .false., .true.])
hel_lock = [2, 1, 0]
call col0%init ()
select case (data%id)
case (23)
    !!! Z boson, flavor is not changing
    call sf_int%base_init (mask, [data%mass**2], [data%mass**2], &
        [data%mZ**2], hel_lock = hel_lock)
    sf_int%data => data
    call flv_z%init (Z_BOSON, data%model)
    call qn_z%init (flv_z, col0)
    do i = 1, size (data%flv_in)
        call polarization_init_generic (pol, data%flv_in(i))
        call qn_fc(1)%init ( &
            flv = data%flv_in(i), &
            col = color_from_flavor (data%flv_in(i), 1))
        call it_hel%init (pol%state)
        do while (it_hel%is_valid ())
            qn_hel = it_hel%get_quantum_numbers ()
            qn = qn_hel(1) .merge. qn_fc(1)
            qn_rad = qn
            call qn_rad%tag_radiated ()
            call sf_int%add_state ([qn, qn_rad, qn_z])
            call it_hel%advance ()
        end do
        call polarization_final (pol)
    end do
case (24)
    call sf_int%base_init (mask, [data%mass**2], [data%m_out**2], &
        [data%mW**2], hel_lock = hel_lock)
    sf_int%data => data
    call flv_wp%init (W_BOSON, data%model)
    call flv_wm%init (- W_BOSON, data%model)
    call qn_wp%init (flv_wp, col0)
    call qn_wm%init (flv_wm, col0)
    do i = 1, size (data%flv_in)
        isospin = data%flv_in(i)%get_isospin_type ()
        if (isospin > 0) then
            !!! up-type quark or neutrinos
            if (data%flv_in(i)%is_antiparticle ()) then
                qn_w = qn_wm
            else
                qn_w = qn_wp
            end if
        else
            !!! down-type quark or lepton
            if (data%flv_in(i)%is_antiparticle ()) then
                qn_w = qn_wp
            else
                qn_w = qn_wm
            end if
        end if
        call polarization_init_generic (pol, data%flv_in(i))
    end do
end select

```

```

        call qn_fc(1)%init ( &
            flv = data%flv_in(i), &
            col = color_from_flavor (data%flv_in(i), 1))
        call qn_fc_fin(1)%init ( &
            flv = data%flv_out(i), &
            col = color_from_flavor (data%flv_out(i), 1))
        call it_hel%init (pol%state)
        do while (it_hel%is_valid ())
            qn_hel = it_hel%get_quantum_numbers ()
            qn = qn_hel(1) .merge. qn_fc(1)
            qn_rad = qn_hel(1) .merge. qn_fc_fin(1)
            call qn_rad%tag_radiated ()
            call sf_int%add_state ([qn, qn_rad, qn_w])
            call it_hel%advance ()
        end do
        call polarization_final (pol)
    end do
case default
    call msg_fatal ("EWA initialization failed: wrong particle type.")
end select
call sf_int%freeze ()
if (data%keep_momentum) then
    if (data%keep_energy) then
        call msg_fatal ("EWA: momentum and energy" // &
            "cannot be simultaneously conserved.")
    else
        sf_int%on_shell_mode = KEEP_MOMENTUM
    end if
else
    if (data%keep_energy) then
        sf_int%on_shell_mode = KEEP_ENERGY
    end if
end if
call sf_int%set_incoming ([1])
call sf_int%set_radiated ([2])
call sf_int%set_outgoing ([3])
end select
end subroutine ewa_init

```

Prepare the coupling arrays. This is separate from the previous routine since the state matrix may be helicity-contracted.

```

<SF ewa: ewa: TBP>+≡
    procedure :: setup_constants => ewa_setup_constants

<SF ewa: procedures>+≡
    subroutine ewa_setup_constants (sf_int)
        class(ewa_t), intent(inout) :: sf_int
        type(state_iterator_t) :: it
        type(flavor_t) :: flv
        real(default) :: q, t3
        integer :: i
        sf_int%n_me = sf_int%get_n_matrix_elements ()
        allocate (sf_int%cv (sf_int%n_me))
        allocate (sf_int%ca (sf_int%n_me))
    end subroutine

```

```

associate (data => sf_int%data)
  select case (data%id)
  case (23)
    call it%init (sf_int%interaction_t%get_state_matrix_ptr ())
    do while (it%is_valid ())
      i = it%get_me_index ()
      flv = it%get_flavor (1)
      q = flv%get_charge ()
      t3 = flv%get_isospin ()
      if (flv%is_antiparticle ()) then
        sf_int%cv(i) = - data%cv &
          * (t3 - 2._default * q * data%sinthw**2) / data%costhw
        sf_int%ca(i) = data%ca * t3 / data%costhw
      else
        sf_int%cv(i) = data%cv &
          * (t3 - 2._default * q * data%sinthw**2) / data%costhw
        sf_int%ca(i) = data%ca * t3 / data%costhw
      end if
      call it%advance ()
    end do
  case (24)
    call it%init (sf_int%interaction_t%get_state_matrix_ptr ())
    do while (it%is_valid ())
      i = it%get_me_index ()
      flv = it%get_flavor (1)
      if (flv%is_antiparticle ()) then
        sf_int%cv(i) = data%cv / sqrt(2._default)
        sf_int%ca(i) = - data%ca / sqrt(2._default)
      else
        sf_int%cv(i) = data%cv / sqrt(2._default)
        sf_int%ca(i) = data%ca / sqrt(2._default)
      end if
      call it%advance ()
    end do
  end select
end associate
sf_int%status = SF_INITIAL
end subroutine ewa_setup_constants

```

15.8.4 Kinematics

Set kinematics. The EWA structure function allows for a straightforward mapping of the unit interval. So, to leading order, the structure function value is unity, but the x value is transformed. Higher orders affect the function value. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ is trivial.

If `map` is set, the exponential mapping for the $1/x$ singularity discussed above is applied.

```

<SF ewa: ewa: TBP>+≡
  procedure :: complete_kinematics => ewa_complete_kinematics

<SF ewa: procedures>+≡
  subroutine ewa_complete_kinematics (sf_int, x, f, r, rb, map)

```

```

class(ewa_t), intent(inout) :: sf_int
real(default), dimension(:), intent(out) :: x
real(default), intent(out) :: f
real(default), dimension(:), intent(in) :: r
real(default), dimension(:), intent(in) :: rb
logical, intent(in) :: map
real(default) :: xb1, e_1
real(default) :: x0, x1, lx0, lx1, lx
e_1 = energy (sf_int%get_momentum (1))
if (sf_int%data%keep_momentum .or. sf_int%data%keep_energy) then
  select case (sf_int%data%id)
    case (23)
      x0 = max (sf_int%data%x_min, sf_int%data%mz / e_1)
    case (24)
      x0 = max (sf_int%data%x_min, sf_int%data%mw / e_1)
  end select
else
  x0 = sf_int%data%x_min
end if
x1 = sf_int%data%x_max
if ( x0 >= x1) then
  f = 0
  sf_int%status = SF_FAILED_KINEMATICS
  return
end if
if (map) then
  lx0 = log (x0)
  lx1 = log (x1)
  lx = lx1 * r(1) + lx0 * rb(1)
  x(1) = exp(lx)
  f = x(1) * (lx1 - lx0)
else
  x(1) = r(1)
  if (x0 < x(1) .and. x(1) < x1) then
    f = 1
  else
    sf_int%status = SF_FAILED_KINEMATICS
    f = 0
    return
  end if
end if
xb1 = 1 - x(1)
if (size(x) == 3) x(2:3) = r(2:3)
call sf_int%split_momentum (x, xb1)
select case (sf_int%status)
case (SF_DONE_KINEMATICS)
  sf_int%x = x(1)
  sf_int%xb = xb1
case (SF_FAILED_KINEMATICS)
  sf_int%x = 0
  sf_int%xb = 0
  f = 0
end select
end subroutine ewa_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

<SF ewa: ewa: TBP>+≡
  procedure :: inverse_kinematics => ewa_inverse_kinematics

<SF ewa: procedures>+≡
  subroutine ewa_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
    class(ewa_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    real(default) :: x0, x1, lx0, lx1, lx, e_1
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    e_1 = energy (sf_int%get_momentum (1))
    if (sf_int%data%keep_momentum .or. sf_int%data%keep_energy) then
      select case (sf_int%data%id)
        case (23)
          x0 = max (sf_int%data%x_min, sf_int%data%mz / e_1)
        case (24)
          x0 = max (sf_int%data%x_min, sf_int%data%mw / e_1)
        end select
    else
      x0 = sf_int%data%x_min
    end if
    x1 = sf_int%data%x_max
    if (map) then
      lx0 = log (x0)
      lx1 = log (x1)
      lx = log (x(1))
      r(1) = (lx - lx0) / (lx1 - lx0)
      rb(1) = (lx1 - lx) / (lx1 - lx0)
      f = x(1) * (lx1 - lx0)
    else
      r (1) = x(1)
      rb(1) = 1 - x(1)
      if (x0 < x(1) .and. x(1) < x1) then
        f = 1
      else
        f = 0
      end if
    end if
    if (size(r) == 3) then
      r (2:3) = x(2:3)
      rb(2:3) = 1 - x(2:3)
    end if
    if (set_mom) then
      call sf_int%split_momentum (x, sf_int%xb)
      select case (sf_int%status)

```



```

      case (SF_DONE_KINEMATICS)
        sf_int%x = x(1)
        sf_int%xb = 1 - x(1)
      case (SF_FAILED_KINEMATICS)
        sf_int%x = 0
        f = 0
      end select
    end if
  end subroutine ewa_inverse_kinematics

```

15.8.5 EWA application

For EWA, we can compute kinematics and function value in a single step. This function works on a single beam, assuming that the input momentum has been set. We need four random numbers as input: one for x , one for Q^2 , and two for the polar and azimuthal angles. Alternatively, we can skip p_T generation; in this case, we only need one.

For obtaining splitting kinematics, we rely on the assumption that all in-particles are mass-degenerate (or there is only one), so the generated x values are identical.

```

<SF ewa: ewa: TBP>+≡
  procedure :: apply => ewa_apply

<SF ewa: procedures>+≡
  subroutine ewa_apply (sf_int, scale)
    class(ewa_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    real(default) :: x, xb, pt2, c1, c2
    real(default) :: cv, ca
    real(default) :: f, fm, fp, fL
    integer :: i
    associate (data => sf_int%data)
      x = sf_int%x
      xb = sf_int%xb
      pt2 = min ((data%pt_max)**2, (xb * data%sqrts / 2)**2)
      select case (data%id)
        case (23)
          !!! Z boson structure function
          c1 = log (1 + pt2 / (xb * (data%mZ)**2))
          c2 = 1 / (1 + (xb * (data%mZ)**2) / pt2)
        case (24)
          !!! W boson structure function
          c1 = log (1 + pt2 / (xb * (data%mW)**2))
          c2 = 1 / (1 + (xb * (data%mW)**2) / pt2)
      end select
      do i = 1, sf_int%n_me
        cv = sf_int%cv(i)
        ca = sf_int%ca(i)
        fm = data%coeff * &
          ((cv + ca)**2 + ((cv - ca) * xb)**2) * (c1 - c2) / (2 * x)
        fp = data%coeff * &
          ((cv - ca)**2 + ((cv + ca) * xb)**2) * (c1 - c2) / (2 * x)
      end do
    end associate
  end subroutine ewa_apply

```

```

        fL = data%coeff * &
            (cv**2 + ca**2) * (2 * xb / x) * c2
        f = fp + fm + fL
        if (f /= 0) then
            fp = fp / f
            fm = fm / f
            fL = fL / f
        end if
        call sf_int%set_matrix_element (i, cmplx (f, kind=default))
    end do
end associate
sf_int%status = SF_EVALUATED
end subroutine ewa_apply

```

15.8.6 Unit tests

```

<SF ewa: public>+≡
    public :: sf_ewa_test

<SF ewa: tests>≡
    subroutine sf_ewa_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <SF ewa: execute tests>
    end subroutine sf_ewa_test

```

Test structure function data

Construct and display a test structure function data object.

```

<SF ewa: execute tests>≡
    call test (sf_ewa_1, "sf_ewa_1", &
        "structure function configuration", &
        u, results)

<SF ewa: tests>+≡
    subroutine sf_ewa_1 (u)
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(pdg_array_t) :: pdg_in
        type(pdg_array_t), dimension(1) :: pdg_out
        integer, dimension(:), allocatable :: pdg1
        class(sf_data_t), allocatable :: data

        write (u, "(A)")  "* Test output: sf_ewa_1"
        write (u, "(A)")  "*   Purpose: initialize and display &
            &test structure function data"
        write (u, "(A)")

        write (u, "(A)")  "* Create empty data object"
        write (u, "(A)")

        call model%init_sm_test ()
    end subroutine sf_ewa_1

```

```

pdg_in = 2

allocate (ewa_data_t :: data)
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize for Z boson"
write (u, "(A)")

select type (data)
type is (ewa_data_t)
    call data%init (model, pdg_in, 0.01_default, &
        500._default, 5000._default, .false., .false.)
    call data%set_id (23)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(2x,99(1x,I0))") pdg1

write (u, "(A)")
write (u, "(A)")  "* Initialize for W boson"
write (u, "(A)")

deallocate (data)
allocate (ewa_data_t :: data)
select type (data)
type is (ewa_data_t)
    call data%init (model, pdg_in, 0.01_default, &
        500._default, 5000._default, .false., .false.)
    call data%set_id (24)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(2x,99(1x,I0))") pdg1

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_ewa_1"

end subroutine sf_ewa_1

```

Test and probe structure function

Construct and display a structure function object based on the EWA structure function.

```
(SF ewa: execute tests)+≡
  call test (sf_ewa_2, "sf_ewa_2", &
    "structure function instance", &
    u, results)

(SF ewa: tests)+≡
  subroutine sf_ewa_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_ewa_2"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_sm_test ()
    call flv%init (2, model)
    pdg_in = 2

    call reset_interaction_counter ()

    allocate (ewa_data_t :: data)
    select type (data)
    type is (ewa_data_t)
      call data%init (model, pdg_in, 0.01_default, &
        500._default, 3000._default, .false., .false.)
      call data%set_id (24)
    end select

    write (u, "(A)")  "* Initialize structure-function object"
    write (u, "(A)")

    call data%allocate_sf_int (sf_int)
    call sf_int%init (data)
    call sf_int%set_beam_index ([1])
    call sf_int%setup_constants ()

    call sf_int%write (u)
```

```

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=1500"
write (u, "(A)")
E = 1500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.4, no EWA mapping, collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.4_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false., &
    set_momenta=.true.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EWA structure function"
write (u, "(A)")

```

```

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_ewa_2"

end subroutine sf_ewa_2

```

Standard mapping

Construct and display a structure function object based on the EWA structure function, applying the standard single-particle mapping.

```

<SF ewa: execute tests>+≡
call test (sf_ewa_3, "sf_ewa_3", &
  "apply mapping", &
  u, results)

<SF ewa: tests>+≡
subroutine sf_ewa_3 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(flavor_t) :: flv
  type(pdg_array_t) :: pdg_in
  class(sf_data_t), allocatable, target :: data
  class(sf_int_t), allocatable :: sf_int
  type(vector4_t) :: k
  type(vector4_t), dimension(2) :: q
  real(default) :: E
  real(default), dimension(:), allocatable :: r, rb, x
  real(default) :: f

  write (u, "(A)")  "* Test output: sf_ewa_3"
  write (u, "(A)")  "* Purpose: initialize and fill &
    &test structure function object"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize configuration data"
  write (u, "(A)")

  call model%init_sm_test ()
  call flv%init (2, model)
  pdg_in = 2

  call reset_interaction_counter ()

  allocate (ewa_data_t :: data)
  select type (data)

```

```

type is (ewa_data_t)
  call data%init (model, pdg_in, 0.01_default, &
    500._default, 3000._default, .false., .false.)
  call data%set_id (24)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=1500"
write (u, "(A)")
E = 1500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.4, with EWA mapping, collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.4_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

```

```

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.true., &
    set_momenta=.true.)

write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "rb=", rb
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EWA structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_ewa_3"

end subroutine sf_ewa_3

```

Non-collinear case

Construct and display a structure function object based on the EPA structure function.

```

<SF ewa: execute tests>+=
  call test (sf_ewa_4, "sf_ewa_4", &
    "non-collinear", &
    u, results)

<SF ewa: tests>+=
  subroutine sf_ewa_4 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

```



```

write (u, "(A)")  "* Test output: sf_ewa_4"
write (u, "(A)")  "* Purpose: initialize and fill &
                  &test structure function object"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_sm_test ()
call flv%init (2, model)
pdg_in = 2

call reset_interaction_counter ()

allocate (ewa_data_t :: data)
select type (data)
type is (ewa_data_t)
    call data%init (model, pdg_in, 0.01_default, &
                  500._default, 3000.0_default, .false., .true.)
    call data%set_id (24)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

write (u, "(A)")  "* Initialize incoming momentum with E=1500"
write (u, "(A)")
E = 1500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.5/0.5/0.25, with EWA mapping, "
write (u, "(A)")  "          non-coll., keeping energy"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = [0.5_default, 0.5_default, 0.25_default]
rb = 1 - r
sf_int%on_shell_mode = KEEP_ENERGY
call sf_int%complete_kinematics (x, f, r, rb, map=.true.)
call interaction_pacify_momenta (sf_int%interaction_t, 1e-10_default)

write (u, "(A,9(1x,F10.7))")  "r =", r

```

```

write (u, "(A,9(1x,F10.7))") "rb=", rb
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x and r from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])
call sf_int%setup_constants ()

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)
call sf_int%inverse_kinematics (x, f, r, rb, map=.true., &
    set_momenta=.true.)
call interaction_pacify_momenta (sf_int%interaction_t, 1e-10_default)

write (u, "(A,9(1x,F10.7))") "r =", r
write (u, "(A,9(1x,F10.7))") "rb=", rb
write (u, "(A,9(1x,F10.7))") "x =", x
write (u, "(A,9(1x,F10.7))") "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EWA structure function"
write (u, "(A)")

call sf_int%apply (scale = 1500._default)
call sf_int%write (u, testflag = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_ewa_4"

end subroutine sf_ewa_4

```

Structure function for multiple flavors

Construct and display a structure function object based on the EWA structure function. The incoming state has multiple particles with non-uniform quantum numbers.

```

<SF ewa: execute tests>+=
  call test (sf_ewa_5, "sf_ewa_5", &
    "structure function instance", &
    u, results)

<SF ewa: tests>+=
  subroutine sf_ewa_5 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_ewa_5"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_sm_test ()
    call flv%init (2, model)
    pdg_in = [1, 2, -1, -2]

    call reset_interaction_counter ()

    allocate (ewa_data_t :: data)
    select type (data)
    type is (ewa_data_t)
      call data%init (model, pdg_in, 0.01_default, &
        500._default, 3000._default, .false., .false.)
      call data%set_id (24)
    end select

    write (u, "(A)")  "* Initialize structure-function object"
    write (u, "(A)")

    call data%allocate_sf_int (sf_int)
    call sf_int%init (data)
    call sf_int%set_beam_index ([1])
    call sf_int%setup_constants ()

    call sf_int%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize incoming momentum with E=1500"
    write (u, "(A)")
    E = 1500
    k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)

```

```

call pacify (k, 1e-10_default)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for r=0.4, no EWA mapping, collinear"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.4_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Evaluate EWA structure function"
write (u, "(A)")

call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_ewa_5"

end subroutine sf_ewa_5

```

15.9 Energy-scan spectrum

This spectrum is actually a trick that allows us to plot the c.m. energy dependence of a cross section without scanning the input energy. We start with the observation that a spectrum $f(x)$, applied to one of the incoming beams only, results in a cross section

$$\sigma = \int dx f(x) \hat{\sigma}(xs). \quad (15.70)$$

We want to compute the distribution of $E = \sqrt{\hat{s}} = \sqrt{xs}$, i.e.,

$$\frac{d\sigma}{dE} = \frac{2\sqrt{x}}{\sqrt{s}} \frac{d\sigma}{dx} = \frac{2\sqrt{x}}{\sqrt{s}} f(x) \hat{\sigma}(xs), \quad (15.71)$$

so if we set

$$f(x) = \frac{\sqrt{s}}{2\sqrt{x}}, \quad (15.72)$$

we get the distribution

$$\frac{d\sigma}{dE} = \hat{\sigma}(\hat{s} = E^2). \quad (15.73)$$

We implement this as a spectrum with a single parameter x . The parameters for the individual beams are computed as $x_i = \sqrt{x}$, so they are equal and the kinematics is always symmetric.

`<sf_escan.f90>`≡
<File header>

`module sf_escan`

<Use kinds>

<Use strings>

`use io_units`

`use format_defs, only: FMT_12`

`use unit_tests`

`use diagnostics`

`use lorentz`

`use physics_defs, only: ELECTRON`

`use pdg_arrays`

`use model_data`

`use flavors`

`use helicities`

`use colors`

`use quantum_numbers`

`use state_matrices`

`use polarizations`

`use interactions`

`use sf_aux`

`use sf_base`

<Standard module head>

<SF escan: public>

<SF escan: types>

```

contains

<SF escan: procedures>

<SF escan: tests>

end module sf_escan

```

15.9.1 Data type

The `norm` is unity if the total cross section should be normalized to one, and \sqrt{s} if it should be normalized to the total energy. In the latter case, the differential distribution $d\sigma/d\sqrt{\hat{s}}$ coincides with the partonic cross section $\hat{\sigma}$ as a function of $\sqrt{\hat{s}}$.

```

<SF escan: public>≡
    public :: escan_data_t

<SF escan: types>≡
    type, extends(sf_data_t) :: escan_data_t
        private
            type(flavor_t), dimension(:, :), allocatable :: flv_in
            integer, dimension(2) :: n_flv = 0
            real(default) :: norm = 1
        contains
            <SF escan: escan data: TBP>
        end type escan_data_t

<SF escan: escan data: TBP>≡
    procedure :: init => escan_data_init

<SF escan: procedures>≡
    subroutine escan_data_init (data, model, pdg_in, norm)
        class(escan_data_t), intent(out) :: data
        class(model_data_t), intent(in), target :: model
        type(pdg_array_t), dimension(2), intent(in) :: pdg_in
        real(default), intent(in), optional :: norm
        real(default), dimension(2) :: m2
        integer :: i, j
        data%n_flv = pdg_array_get_length (pdg_in)
        allocate (data%flv_in (maxval (data%n_flv), 2))
        do i = 1, 2
            do j = 1, data%n_flv(i)
                call data%flv_in(j, i)%init (pdg_array_get (pdg_in(i), j), model)
            end do
        end do
        m2 = data%flv_in(1, :)%get_mass ()
        do i = 1, 2
            if (any (data%flv_in(1:data%n_flv(i), i)%get_mass () /= m2(i))) then
                call msg_fatal ("Energy scan: incoming particle mass must be uniform")
            end if
        end do
        if (present (norm)) data%norm = norm
    end subroutine escan_data_init

```

Output

```

<SF escan: escan data: TBP>+≡
  procedure :: write => escan_data_write

<SF escan: procedures>+≡
  subroutine escan_data_write (data, unit, verbose)
    class(escan_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u, i, j
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1x,A)") "Energy-scan data:"
    write (u, "(3x,A)", advance="no") "prt_in = "
    do i = 1, 2
      if (i > 1) write (u, "(',',1x)", advance="no")
      do j = 1, data%n_flv(i)
        if (j > 1) write (u, "(:',)", advance="no")
        write (u, "(A)", advance="no") char (data%flv_in(j,i)%get_name ())
      end do
    end do
    write (u, *)
    write (u, "(3x,A," // FMT_12 // ")") "norm   =", data%norm
  end subroutine escan_data_write

```

Kinematics is completely collinear, hence there is only one parameter for a pair spectrum.

```

<SF escan: escan data: TBP>+≡
  procedure :: get_n_par => escan_data_get_n_par

<SF escan: procedures>+≡
  function escan_data_get_n_par (data) result (n)
    class(escan_data_t), intent(in) :: data
    integer :: n
    n = 1
  end function escan_data_get_n_par

```

Return the outgoing particles PDG codes. This is always the same as the incoming particle, where we use two indices for the two beams.

```

<SF escan: escan data: TBP>+≡
  procedure :: get_pdg_out => escan_data_get_pdg_out

<SF escan: procedures>+≡
  subroutine escan_data_get_pdg_out (data, pdg_out)
    class(escan_data_t), intent(in) :: data
    type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
    integer :: i, n
    n = 2
    do i = 1, n
      pdg_out(i) = data%flv_in(1:data%n_flv(i),i)%get_pdg ()
    end do
  end subroutine escan_data_get_pdg_out

```

Allocate the interaction record.

```

<SF escan: escan data: TBP>+≡
  procedure :: allocate_sf_int => escan_data_allocate_sf_int

<SF escan: procedures>+≡
  subroutine escan_data_allocate_sf_int (data, sf_int)
    class(escan_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (escan_t :: sf_int)
  end subroutine escan_data_allocate_sf_int

```

15.9.2 The Energy-scan object

This is a spectrum, not a radiation. We create an interaction with two incoming and two outgoing particles, flavor, color, and helicity being carried through. x nevertheless is only one-dimensional, as we are always using only one beam parameter.

```

<SF escan: types>+≡
  type, extends (sf_int_t) :: escan_t
    type(escan_data_t), pointer :: data => null ()
    contains
    <SF escan: escan: TBP>
  end type escan_t

```

Type string: for the energy scan this is just a dummy function.

```

<SF escan: escan: TBP>≡
  procedure :: type_string => escan_type_string

<SF escan: procedures>+≡
  function escan_type_string (object) result (string)
    class(escan_t), intent(in) :: object
    type(string_t) :: string
    if (associated (object%data)) then
      string = "Escan: energy scan"
    else
      string = "Escan: [undefined]"
    end if
  end function escan_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF escan: escan: TBP>+≡
  procedure :: write => escan_write

<SF escan: procedures>+≡
  subroutine escan_write (object, unit, testflag)
    class(escan_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
    end if
  end subroutine escan_write

```



```

        call object%base_write (u, testflag)
    else
        write (u, "(1x,A)") "Energy scan data: [undefined]"
    end if
end subroutine escan_write

```

(SF escan: escan: TBP)+≡

```

procedure :: init => escan_init

```

(SF escan: procedures)+≡

```

subroutine escan_init (sf_int, data)
    class(escan_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(4) :: mask
    integer, dimension(4) :: hel_lock
    real(default), dimension(2) :: m2
    real(default), dimension(0) :: mr2
    type(quantum_numbers_t), dimension(4) :: qn_fc, qn_hel, qn
    type(polarization_t) :: pol1, pol2
    type(state_iterator_t) :: it_hel1, it_hel2
    integer :: j1, j2
    select type (data)
    type is (escan_data_t)
        hel_lock = [3, 4, 1, 2]
        m2 = data%flv_in(1,:)%get_mass ()
        call sf_int%base_init (mask, m2, mr2, m2, hel_lock = hel_lock)
        sf_int%data => data
        do j1 = 1, data%n_flv(1)
            call qn_fc(1)%init ( &
                flv = data%flv_in(j1,1), &
                col = color_from_flavor (data%flv_in(j1,1)))
            call qn_fc(3)%init ( &
                flv = data%flv_in(j1,1), &
                col = color_from_flavor (data%flv_in(j1,1)))
            call polarization_init_generic (pol1, data%flv_in(j1,1))
        do j2 = 1, data%n_flv(2)
            call qn_fc(2)%init ( &
                flv = data%flv_in(j2,2), &
                col = color_from_flavor (data%flv_in(j2,2)))
            call qn_fc(4)%init ( &
                flv = data%flv_in(j2,2), &
                col = color_from_flavor (data%flv_in(j2,2)))
            call polarization_init_generic (pol2, data%flv_in(j2,2))
            call it_hel1%init (pol1%state)
            do while (it_hel1%is_valid ())
                qn_hel(1:1) = it_hel1%get_quantum_numbers ()
                qn_hel(3:3) = it_hel1%get_quantum_numbers ()
                call it_hel2%init (pol2%state)
            do while (it_hel2%is_valid ())
                qn_hel(2:2) = it_hel2%get_quantum_numbers ()
                qn_hel(4:4) = it_hel2%get_quantum_numbers ()
                qn = qn_hel .merge. qn_fc
                call sf_int%add_state (qn)
                call it_hel2%advance ()
            end do
            end do
        end do
    end select
end subroutine escan_init

```

```

        end do
        call it_hell1%advance ()
    end do
    call polarization_final (pol2)
end do
call polarization_final (pol1)
end do
call sf_int%set_incoming ([1,2])
call sf_int%set_outgoing ([3,4])
call sf_int%freeze ()
sf_int%status = SF_INITIAL
end select
end subroutine escan_init

```

15.9.3 Kinematics

Set kinematics. We have a single parameter, but reduce both beams. The map flag is ignored.

```

<SF escan: escan: TBP>+≡
    procedure :: complete_kinematics => escan_complete_kinematics

<SF escan: procedures>+≡
    subroutine escan_complete_kinematics (sf_int, x, f, r, rb, map)
        class(escan_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: x
        real(default), intent(out) :: f
        real(default) :: sqrt_x
        real(default), dimension(:), intent(in) :: r
        real(default), dimension(:), intent(in) :: rb
        logical, intent(in) :: map
        x = r
        sqrt_x = sqrt (x(1))
        if (sqrt_x > 0) then
            f = 1 / (2 * sqrt_x)
        else
            f = 0
            sf_int%status = SF_FAILED_KINEMATICS
            return
        end if
        call sf_int%reduce_momenta ([sqrt_x, sqrt_x])
    end subroutine escan_complete_kinematics

```

Recover x . The base procedure should return two momentum fractions for the two beams, while we have only one parameter. This is the product of the extracted momentum fractions.

```

<SF escan: escan: TBP>+≡
    procedure :: recover_x => escan_recover_x

<SF escan: procedures>+≡
    subroutine escan_recover_x (sf_int, x, x_free)
        class(escan_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: x

```

```

    real(default), intent(inout), optional :: x_free
    real(default), dimension(2) :: xi
    call sf_int%base_recover_x (xi, x_free)
    x = product (xi)
end subroutine escan_recover_x

```

Compute inverse kinematics.

```

<SF escan: escan: TBP>+≡
    procedure :: inverse_kinematics => escan_inverse_kinematics

<SF escan: procedures>+≡
    subroutine escan_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
        class(escan_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(in) :: x
        real(default), intent(out) :: f
        real(default), dimension(:), intent(out) :: r
        real(default), dimension(:), intent(out) :: rb
        logical, intent(in) :: map
        logical, intent(in), optional :: set_momenta
        real(default) :: sqrt_x
        logical :: set_mom
        set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
        sqrt_x = sqrt (x(1))
        if (sqrt_x > 0) then
            f = 1 / (2 * sqrt_x)
        else
            f = 0
            sf_int%status = SF_FAILED_KINEMATICS
            return
        end if
        r = x
        rb = 1 - r
        if (set_mom) then
            call sf_int%reduce_momenta ([sqrt_x, sqrt_x])
        end if
    end subroutine escan_inverse_kinematics

```

15.9.4 Energy scan application

Here, we insert the predefined norm.

```

<SF escan: escan: TBP>+≡
    procedure :: apply => escan_apply

<SF escan: procedures>+≡
    subroutine escan_apply (sf_int, scale)
        class(escan_t), intent(inout) :: sf_int
        real(default), intent(in) :: scale
        real(default) :: f
        associate (data => sf_int%data)
            f = data%norm
        end associate
        call sf_int%set_matrix_element (cmplx (f, kind=default))
        sf_int%status = SF_EVALUATED
    end subroutine

```

```
end subroutine escan_apply
```

15.9.5 Unit tests

```
<SF escan: public>+=
  public :: sf_escan_test

<SF escan: tests>=
  subroutine sf_escan_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <SF escan: execute tests>
  end subroutine sf_escan_test
```

Test structure function data

Construct and display a test structure function data object.

```
<SF escan: execute tests>=
  call test (sf_escan_1, "sf_escan_1", &
    "structure function configuration", &
    u, results)

<SF escan: tests>+=
  subroutine sf_escan_1 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t), dimension(2) :: pdg_in
    type(pdg_array_t), dimension(2) :: pdg_out
    integer, dimension(:), allocatable :: pdg1, pdg2
    class(sf_data_t), allocatable :: data

    write (u, "(A)")  "* Test output: sf_escan_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &energy-scan structure function data"
    write (u, "(A)")

    call model%init_qed_test ()
    pdg_in(1) = ELECTRON
    pdg_in(2) = -ELECTRON

    allocate (escan_data_t :: data)
    select type (data)
    type is (escan_data_t)
      call data%init (model, pdg_in, norm = 2._default)
    end select

    call data%write (u)

    write (u, "(A)")

    write (u, "(1x,A)") "Outgoing particle codes:"
    call data%get_pdg_out (pdg_out)
```

```

pdg1 = pdg_out(1)
pdg2 = pdg_out(2)
write (u, "(2x,99(1x,I0))") pdg1, pdg2

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_escan_1"

end subroutine sf_escan_1

```

g@

Probe the structure-function object

Active the beam event reader, generate an event.

```

<SF escan: execute tests>+≡
  call test (sf_escan_2, "sf_escan_2", &
    "generate event", &
    u, results)

<SF escan: tests>+≡
  subroutine sf_escan_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t), dimension(2) :: flv
    type(pdg_array_t), dimension(2) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k1, k2
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: x_free, f

    write (u, "(A)")  "* Test output: sf_escan_2"
    write (u, "(A)")  "* Purpose: initialize and display &
      &beam-events structure function data"
    write (u, "(A)")

    call model%init_qed_test ()
    call flv(1)%init (ELECTRON, model)
    call flv(2)%init (-ELECTRON, model)
    pdg_in(1) = ELECTRON
    pdg_in(2) = -ELECTRON

    call reset_interaction_counter ()

    allocate (escan_data_t :: data)
    select type (data)
    type is (escan_data_t)
      call data%init (model, pdg_in)
    end select

    write (u, "(A)")  "* Initialize structure-function object"

```

```

write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1,2])

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 250
k1 = vector4_moving (E, sqrt (E**2 - flv(1)%get_mass ()**2), 3)
k2 = vector4_moving (E,-sqrt (E**2 - flv(2)%get_mass ()**2), 3)
call vector4_write (k1, u)
call vector4_write (k2, u)
call sf_int%seed_kinematics ([k1, k2])

write (u, "(A)")
write (u, "(A)")  "* Set dummy parameters and generate x"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.8
rb = 1 - r
x_free = 1

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"
write (u, "(A)")

call sf_int%recover_x (x, x_free)
call sf_int%inverse_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_int%apply (scale = 0._default)
call sf_int%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_escan_2"

end subroutine sf_escan_2

```

15.10 Using beam event data

Instead of an analytic beam description, beam data may be provided in form of an event file. In its most simple form, the event file contains pairs of x values, relative to nominal beam energies. More advanced formats may include polarization, etc. The current implementation carries beam polarization through, if specified.

The code is very similar to the energy scan described above.

However, we must include a file-handle manager for the beam-event files. Two different processes may access a given beam-event file at the same time (i.e., serially but alternating). Accessing an open file from two different units is non-standard and not supported by all compilers. Therefore, we keep a global registry of open files, associated units, and reference counts. The `beam_events_t` objects act as proxies to this registry.

```

⟨sf_beam_events.f90⟩≡
  ⟨File header⟩

module sf_beam_events

  ⟨Use kinds⟩
  ⟨Use strings⟩
  use io_units
  use file_registries
  use unit_tests
  use diagnostics
  use physics_defs, only: ELECTRON
  use lorentz
  use pdg_arrays
  use model_data
  use flavors
  use helicities
  use colors
  use quantum_numbers
  use state_matrices
  use polarizations
  use interactions
  use sf_aux
  use sf_base

```

```

    <Standard module head>

    <SF beam events: public>

    <SF beam events: types>

    <SF beam events: variables>

contains

    <SF beam events: procedures>

    <SF beam events: tests>

end module sf_beam_events

```

15.10.1 The beam-data file registry

We manage data files via the `file_registries` module. To this end, we keep the registry as a private module variable here.

```

<SF beam events: variables>≡
    type(file_registry_t), save :: beam_file_registry

```

15.10.2 Data type

```

<SF beam events: public>≡
    public :: beam_events_data_t

<SF beam events: types>≡
    type, extends(sf_data_t) :: beam_events_data_t
        private
            type(flavor_t), dimension(2) :: flv_in
            type(string_t) :: dir
            type(string_t) :: file
            type(string_t) :: fq
            integer :: unit = 0
            logical :: warn_eof = .true.
        contains
            <SF beam events: beam events data: TBP>
        end type beam_events_data_t

<SF beam events: beam events data: TBP>≡
    procedure :: init => beam_events_data_init

<SF beam events: procedures>≡
    subroutine beam_events_data_init (data, model, pdg_in, dir, file, warn_eof)
        class(beam_events_data_t), intent(out) :: data
        class(model_data_t), intent(in), target :: model
        type(pdg_array_t), dimension(2), intent(in) :: pdg_in
        type(string_t), intent(in) :: dir
        type(string_t), intent(in) :: file
    end subroutine

```



```

logical, intent(in), optional :: warn_eof
if (any (pdg_array_get_length (pdg_in) /= 1)) then
  call msg_fatal ("Beam events: incoming beam particles must be unique")
end if
call data%flv_in(1)%init (pdg_array_get (pdg_in(1), 1), model)
call data%flv_in(2)%init (pdg_array_get (pdg_in(2), 1), model)
data%dir = dir
data%file = file
if (present (warn_eof)) data%warn_eof = warn_eof
end subroutine beam_events_data_init

```

Return true since this spectrum is always in generator mode.

```

<SF beam events: beam events data: TBP>+≡
  procedure :: is_generator => beam_events_data_is_generator

<SF beam events: procedures>+≡
  function beam_events_data_is_generator (data) result (flag)
    class(beam_events_data_t), intent(in) :: data
    logical :: flag
    flag = .true.
  end function beam_events_data_is_generator

```

The number of parameters is two. They are free parameters.

```

<SF beam events: beam events data: TBP>+≡
  procedure :: get_n_par => beam_events_data_get_n_par

<SF beam events: procedures>+≡
  function beam_events_data_get_n_par (data) result (n)
    class(beam_events_data_t), intent(in) :: data
    integer :: n
    n = 2
  end function beam_events_data_get_n_par

<SF beam events: beam events data: TBP>+≡
  procedure :: get_pdg_out => beam_events_data_get_pdg_out

<SF beam events: procedures>+≡
  subroutine beam_events_data_get_pdg_out (data, pdg_out)
    class(beam_events_data_t), intent(in) :: data
    type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
    integer :: i, n
    n = 2
    do i = 1, n
      pdg_out(i) = data%flv_in(i)%get_pdg ()
    end do
  end subroutine beam_events_data_get_pdg_out

```

Allocate the interaction record.

```

<SF beam events: beam events data: TBP>+≡
  procedure :: allocate_sf_int => beam_events_data_allocate_sf_int

```

```

<SF beam events: procedures>+≡
subroutine beam_events_data_allocate_sf_int (data, sf_int)
  class(beam_events_data_t), intent(in) :: data
  class(sf_int_t), intent(inout), allocatable :: sf_int
  allocate (beam_events_t :: sf_int)
end subroutine beam_events_data_allocate_sf_int

```

Output

```

<SF beam events: beam events data: TBP>+≡
  procedure :: write => beam_events_data_write

<SF beam events: procedures>+≡
subroutine beam_events_data_write (data, unit, verbose)
  class(beam_events_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(1x,A)") "Beam-event file data:"
  write (u, "(3x,A,A,A,A)") "prt_in = ", &
    char (data%flv_in(1)%get_name ()), &
    ", ", char (data%flv_in(2)%get_name ())
  write (u, "(3x,A,A,A)") "file   = '", char (data%file), "'"
  write (u, "(3x,A,I0)") "unit   = ", data%unit
  write (u, "(3x,A,L1)") "warn   = ", data%warn_eof
end subroutine beam_events_data_write

```

The data file needs to be opened and closed explicitly. The open/close message is communicated to the file handle registry, which does the actual work.

We determine first whether to look in the local directory or in the given system directory.

```

<SF beam events: beam events data: TBP>+≡
  procedure :: open => beam_events_data_open
  procedure :: close => beam_events_data_close

<SF beam events: procedures>+≡
subroutine beam_events_data_open (data)
  class(beam_events_data_t), intent(inout) :: data
  logical :: exist
  if (data%unit == 0) then
    data%fqn = data%file
    if (data%fqn == "") &
      call msg_fatal ("Beam events: $beam_events_file is not set")
    inquire (file = char (data%fqn), exist = exist)
    if (.not. exist) then
      data%fqn = data%dir // "/" // data%file
      inquire (file = char (data%fqn), exist = exist)
      if (.not. exist) then
        data%fqn = ""
        call msg_fatal ("Beam events: file '" &
          // char (data%file) // "' not found")
      return
    end if
  end if
end if

```

```

        call msg_message ("Beam events: reading from file '" &
            // char (data%file) // "'")
        call beam_file_registry%open (data%fqn, data%unit)
    else
        call msg_bug ("Beam events: file '" &
            // char (data%file) // "' is already open")
    end if
end subroutine beam_events_data_open

subroutine beam_events_data_close (data)
    class(beam_events_data_t), intent(inout) :: data
    if (data%unit /= 0) then
        call beam_file_registry%close (data%fqn)
        call msg_message ("Beam events: closed file '" &
            // char (data%file) // "'")
        data%unit = 0
    end if
end subroutine beam_events_data_close

```

15.10.3 The beam events object

Flavor and polarization carried through, no radiated particles.

```

<SF beam events: types>+≡
    type, extends (sf_int_t) :: beam_events_t
        type(beam_events_data_t), pointer :: data => null ()
        integer :: count = 0
    contains
        <SF beam events: beam events: TBP>
    end type beam_events_t

```

Type string: show beam events file.

```

<SF beam events: beam events: TBP>≡
    procedure :: type_string => beam_events_type_string

<SF beam events: procedures>+≡
    function beam_events_type_string (object) result (string)
        class(beam_events_t), intent(in) :: object
        type(string_t) :: string
        if (associated (object%data)) then
            string = "Beam events: " // object%data%file
        else
            string = "Beam events: [undefined]"
        end if
    end function beam_events_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF beam events: beam events: TBP>+≡
    procedure :: write => beam_events_write

<SF beam events: procedures>+≡
    subroutine beam_events_write (object, unit, testflag)
        class(beam_events_t), intent(in) :: object

```

```

integer, intent(in), optional :: unit
logical, intent(in), optional :: testflag
integer :: u
u = given_output_unit (unit)
if (associated (object%data)) then
    call object%data%write (u)
    call object%base_write (u, testflag)
else
    write (u, "(1x,A)" "Beam events data: [undefined]"
end if
end subroutine beam_events_write

```

$\langle SF \text{ beam events: beam events: TBP} \rangle + \equiv$

```

procedure :: init => beam_events_init

```

$\langle SF \text{ beam events: procedures} \rangle + \equiv$

```

subroutine beam_events_init (sf_int, data)
    class(beam_events_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    real(default), dimension(2) :: m2
    real(default), dimension(0) :: mr2
    type(quantum_numbers_mask_t), dimension(4) :: mask
    integer, dimension(4) :: hel_lock
    type(quantum_numbers_t), dimension(4) :: qn_fc, qn_hel, qn
    type(polarization_t) :: pol1, pol2
    type(state_iterator_t) :: it_hel1, it_hel2
    integer :: i
    select type (data)
    type is (beam_events_data_t)
        m2 = data%flv_in%get_mass () ** 2
        hel_lock = [3, 4, 1, 2]
        mask = quantum_numbers_mask (.false., .false., .false.)
        call sf_int%base_init (mask, m2, mr2, m2, hel_lock = hel_lock)
        sf_int%data => data
        do i = 1, 2
            call qn_fc(i)%init ( &
                flv = data%flv_in(i), &
                col = color_from_flavor (data%flv_in(i)))
            call qn_fc(i+2)%init ( &
                flv = data%flv_in(i), &
                col = color_from_flavor (data%flv_in(i)))
        end do
        call polarization_init_generic (pol1, data%flv_in(1))
        call it_hel1%init (pol1%state)
        do while (it_hel1%is_valid ())
            qn_hel(1:1) = it_hel1%get_quantum_numbers ()
            qn_hel(3:3) = it_hel1%get_quantum_numbers ()
            call polarization_init_generic (pol2, data%flv_in(2))
            call it_hel2%init (pol2%state)
            do while (it_hel2%is_valid ())
                qn_hel(2:2) = it_hel2%get_quantum_numbers ()
                qn_hel(4:4) = it_hel2%get_quantum_numbers ()
                qn = qn_hel .merge. qn_fc
                call sf_int%add_state (qn)
            end do
        end do
    end select
end subroutine beam_events_init

```

```

        call it_hel2%advance ()
    end do
    call polarization_final (pol2)
    call it_hel1%advance ()
end do
call polarization_final (pol2)
call sf_int%freeze ()
call sf_int%set_incoming ([1,2])
call sf_int%set_outgoing ([3,4])
call sf_int%data%open ()
sf_int%status = SF_INITIAL
end select
end subroutine beam_events_init

```

This spectrum type needs a finalizer, which closes the data file.

```

<SF beam events: beam events: TBP>+≡
    procedure :: final => sf_beam_events_final

<SF beam events: procedures>+≡
    subroutine sf_beam_events_final (object)
        class(beam_events_t), intent(inout) :: object
        call object%data%close ()
        call object%interaction_t%final ()
    end subroutine sf_beam_events_final

```

15.10.4 Kinematics

Refer to the data component.

```

<SF beam events: beam events: TBP>+≡
    procedure :: is_generator => beam_events_is_generator

<SF beam events: procedures>+≡
    function beam_events_is_generator (sf_int) result (flag)
        class(beam_events_t), intent(in) :: sf_int
        logical :: flag
        flag = sf_int%data%is_generator ()
    end function beam_events_is_generator

```

Generate free parameters. We read them from file.

```

<SF beam events: beam events: TBP>+≡
    procedure :: generate_free => beam_events_generate_free

<SF beam events: procedures>+≡
    recursive subroutine beam_events_generate_free (sf_int, r, rb, x_free)
        class(beam_events_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: r, rb
        real(default), intent(inout) :: x_free
        integer :: iostat
        associate (data => sf_int%data)
            if (data%unit /= 0) then
                read (data%unit, fmt=*, iostat=iostat) r
                if (iostat > 0) then

```

```

        write (msg_buffer, "(A,I0,A)") &
            "Beam events: I/O error after reading ", sf_int%count, &
            " events"
        call msg_fatal ()
    else if (iostat < 0) then
        if (sf_int%count == 0) then
            call msg_fatal ("Beam events: file is empty")
        else if (sf_int%data%warn_eof) then
            write (msg_buffer, "(A,I0,A)") &
                "Beam events: End of file after reading ", sf_int%count, &
                " events, rewinding"
            call msg_warning ()
        end if
        rewind (data%unit)
        sf_int%count = 0
        call sf_int%generate_free (r, rb, x_free)
    else
        sf_int%count = sf_int%count + 1
        rb = 1 - r
        x_free = x_free * product (r)
    end if
else
    call msg_bug ("Beam events: file is not open for reading")
end if
end associate
end subroutine beam_events_generate_free

```

Set kinematics. Trivial transfer since this is a pure generator.

If `map` is set, we are asked to provide an efficient mapping. For the test case, we set $x = r^2$ and consequently $f(r) = 2r$.

```

<SF beam events: beam events: TBP>+≡
    procedure :: complete_kinematics => beam_events_complete_kinematics

<SF beam events: procedures>+≡
    subroutine beam_events_complete_kinematics (sf_int, x, f, r, rb, map)
        class(beam_events_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(out) :: x
        real(default), intent(out) :: f
        real(default), dimension(:), intent(in) :: r
        real(default), dimension(:), intent(in) :: rb
        logical, intent(in) :: map
        if (map) then
            call msg_fatal ("Beam events: map flag not supported")
        else
            x = r
            f = 1
        end if
        call sf_int%reduce_momenta (x)
    end subroutine beam_events_complete_kinematics

```

Compute inverse kinematics. Trivial in this case.

```

<SF beam events: beam events: TBP>+≡
    procedure :: inverse_kinematics => beam_events_inverse_kinematics

```

```

<SF beam events: procedures>+≡
subroutine beam_events_inverse_kinematics &
  (sf_int, x, f, r, rb, map, set_momenta)
  class(beam_events_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(in) :: x
  real(default), intent(out) :: f
  real(default), dimension(:), intent(out) :: r
  real(default), dimension(:), intent(out) :: rb
  logical, intent(in) :: map
  logical, intent(in), optional :: set_momenta
  logical :: set_mom
  set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
  if (map) then
    call msg_fatal ("Beam events: map flag not supported")
  else
    r = x
    f = 1
  end if
  rb = 1 - r
  if (set_mom) then
    call sf_int%reduce_momenta (x)
  end if
end subroutine beam_events_inverse_kinematics

```

15.10.5 Beam events application

Trivial, just set the unit weight.

```

<SF beam events: beam events: TBP>+≡
procedure :: apply => beam_events_apply

<SF beam events: procedures>+≡
subroutine beam_events_apply (sf_int, scale)
  class(beam_events_t), intent(inout) :: sf_int
  real(default), intent(in) :: scale
  real(default) :: f
  f = 1
  call sf_int%set_matrix_element (cmplx (f, kind=default))
  sf_int%status = SF_EVALUATED
end subroutine beam_events_apply

```

15.10.6 Unit tests

```

<SF beam events: public>+≡
public :: sf_beam_events_test

<SF beam events: tests>≡
subroutine sf_beam_events_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
  <SF beam events: execute tests>
end subroutine sf_beam_events_test

```

Test structure function data

Construct and display a test structure function data object.

```
<SF beam events: execute tests>≡
    call test (sf_beam_events_1, "sf_beam_events_1", &
               "structure function configuration", &
               u, results)

<SF beam events: tests>+≡
    subroutine sf_beam_events_1 (u)
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(pdg_array_t), dimension(2) :: pdg_in
        type(pdg_array_t), dimension(2) :: pdg_out
        integer, dimension(:), allocatable :: pdg1, pdg2
        class(sf_data_t), allocatable :: data

        write (u, "(A)")  "* Test output: sf_beam_events_1"
        write (u, "(A)")  "* Purpose: initialize and display &
                           &beam-events structure function data"
        write (u, "(A)")

        call model%init_qed_test ()
        pdg_in(1) = ELECTRON
        pdg_in(2) = -ELECTRON

        allocate (beam_events_data_t :: data)
        select type (data)
        type is (beam_events_data_t)
            call data%init (model, pdg_in, var_str (""), var_str ("beam_events.dat"))
        end select

        call data%write (u)

        write (u, "(A)")

        write (u, "(1x,A)") "Outgoing particle codes:"
        call data%get_pdg_out (pdg_out)
        pdg1 = pdg_out(1)
        pdg2 = pdg_out(2)
        write (u, "(2x,99(1x,I0))") pdg1, pdg2

        call model%final ()

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: sf_beam_events_1"

    end subroutine sf_beam_events_1
```

Probe the structure-function object

Active the beam event reader, generate an event.

```
<SF beam events: execute tests>+≡
```



```

call test (sf_beam_events_2, "sf_beam_events_2", &
  "generate event", &
  u, results)
<SF beam events: tests>+≡
subroutine sf_beam_events_2 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(flavor_t), dimension(2) :: flv
  type(pdg_array_t), dimension(2) :: pdg_in
  class(sf_data_t), allocatable, target :: data
  class(sf_int_t), allocatable :: sf_int
  type(vector4_t) :: k1, k2
  real(default) :: E
  real(default), dimension(:), allocatable :: r, rb, x
  real(default) :: x_free, f
  integer :: i

  write (u, "(A)")  "* Test output: sf_beam_events_2"
  write (u, "(A)")  "* Purpose: initialize and display &
    &beam-events structure function data"
  write (u, "(A)")

  call model%init_qed_test ()
  call flv(1)%init (ELECTRON, model)
  call flv(2)%init (-ELECTRON, model)
  pdg_in(1) = ELECTRON
  pdg_in(2) = -ELECTRON

  call reset_interaction_counter ()

  allocate (beam_events_data_t :: data)
  select type (data)
  type is (beam_events_data_t)
    call data%init (model, pdg_in, &
      var_str (""), var_str ("test_beam_events.dat"))
  end select

  write (u, "(A)")  "* Initialize structure-function object"
  write (u, "(A)")

  call data%allocate_sf_int (sf_int)
  call sf_int%init (data)
  call sf_int%set_beam_index ([1,2])

  write (u, "(A)")  "* Initialize incoming momentum with E=500"
  write (u, "(A)")
  E = 250
  k1 = vector4_moving (E, sqrt (E**2 - flv(1)%get_mass ()**2), 3)
  k2 = vector4_moving (E, -sqrt (E**2 - flv(2)%get_mass ()**2), 3)
  call vector4_write (k1, u)
  call vector4_write (k2, u)
  call sf_int%seed_kinematics ([k1, k2])

  write (u, "(A)")

```

```

write (u, "(A)")  "* Set dummy parameters and generate x."
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0
rb = 0
x_free = 1
call sf_int%generate_free (r, rb, x_free)
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "r =", r
write (u, "(A,9(1x,F10.7))")  "rb=", rb
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free
select type (sf_int)
type is (beam_events_t)
    write (u, "(A,1x,I0)")  "count =", sf_int%count
end select

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_int%apply (scale = 0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate more events, rewind"
write (u, "(A)")

select type (sf_int)
type is (beam_events_t)
    do i = 1, 3
        call sf_int%generate_free (r, rb, x_free)
        write (u, "(A,9(1x,F10.7))")  "r =", r
        write (u, "(A,1x,I0)")  "count =", sf_int%count
    end do
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_beam_events_2"

end subroutine sf_beam_events_2

```

Check the file handle registry

Open and close some files, checking the registry contents.

```
<SF beam events: execute tests>+≡
    call test (sf_beam_events_3, "sf_beam_events_3", &
        "check registry", &
        u, results)

<SF beam events: tests>+≡
    subroutine sf_beam_events_3 (u)
        integer, intent(in) :: u
        integer :: u1

        write (u, "(A)")  "* Test output: sf_beam_events_2"
        write (u, "(A)")  "* Purpose: check file handle registry"
        write (u, "(A)")

        write (u, "(A)")  "* Create some empty files"
        write (u, "(A)")

        u1 = free_unit ()
        open (u1, file = "sf_beam_events_f1.tmp", action="write", status="new")
        close (u1)
        open (u1, file = "sf_beam_events_f2.tmp", action="write", status="new")
        close (u1)
        open (u1, file = "sf_beam_events_f3.tmp", action="write", status="new")
        close (u1)

        write (u, "(A)")  "* Empty registry"
        write (u, "(A)")

        call beam_file_registry%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Insert three entries"
        write (u, "(A)")

        call beam_file_registry%open (var_str ("sf_beam_events_f3.tmp"))
        call beam_file_registry%open (var_str ("sf_beam_events_f2.tmp"))
        call beam_file_registry%open (var_str ("sf_beam_events_f1.tmp"))
        call beam_file_registry%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Open a second channel"
        write (u, "(A)")

        call beam_file_registry%open (var_str ("sf_beam_events_f2.tmp"))
        call beam_file_registry%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Close second entry twice"
        write (u, "(A)")

        call beam_file_registry%close (var_str ("sf_beam_events_f2.tmp"))
        call beam_file_registry%close (var_str ("sf_beam_events_f2.tmp"))
```

```

call beam_file_registry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Close last entry"
write (u, "(A)")

call beam_file_registry%close (var_str ("sf_beam_events_f3.tmp"))
call beam_file_registry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Close remaining entry"
write (u, "(A)")

call beam_file_registry%close (var_str ("sf_beam_events_f1.tmp"))
call beam_file_registry%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

open (u1, file = "sf_beam_events_f1.tmp", action="write")
close (u1, status = "delete")
open (u1, file = "sf_beam_events_f2.tmp", action="write")
close (u1, status = "delete")
open (u1, file = "sf_beam_events_f3.tmp", action="write")
close (u1, status = "delete")

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_beam_events_3"

end subroutine sf_beam_events_3

```

15.11 Lepton collider beamstrahlung: CIRCE1

```
<sf_circe1.f90>≡  
<File header>  
  
module sf_circe1  
  
  <Use kinds>  
  use kinds, only: double  
  <Use strings>  
  use io_units  
  use format_defs, only: FMT_17, FMT_19  
  use unit_tests  
  use diagnostics  
  use physics_defs, only: UNDEFINED, ELECTRON, PHOTON  
  use lorentz  
  use rng_base  
  use pdg_arrays  
  use model_data  
  use flavors  
  use colors  
  use quantum_numbers  
  use state_matrices  
  use polarizations  
  use interactions  
  use sf_mappings  
  use sf_aux  
  use sf_base  
  use circe1, circe1_rng_t => rng_type !NODEP!  
  
  <Standard module head>  
  
  <SF circe1: public>  
  
  <SF circe1: types>  
  
  contains  
  
  <SF circe1: procedures>  
  
  <SF circe1: tests>  
  
end module sf_circe1
```

15.11.1 Physics

Beamstrahlung is applied before ISR. The CIRCE1 implementation has a single structure function for both beams (which makes sense since it has to be switched on or off for both beams simultaneously). Nevertheless it is factorized:

The functional form in the CIRCE1 parameterization is defined for electrons or photons

$$f(x) = \alpha x^\beta (1-x)^\gamma \quad (15.74)$$

for $x < 1 - \epsilon$ (resp. $x > \epsilon$ in the photon case). In the remaining interval, the standard form is zero, with a delta singularity at $x = 1$ (resp. $x = 0$). Equivalently, the delta part may be distributed uniformly among this interval. This latter form is implemented in the `kirke` version of the `CIRCE1` subroutines, and is used here.

The parameter `circe1_eps` sets the peak mapping of the `CIRCE1` structure function. Its default value is 10^{-5} . The other parameters are the parameterization version and revision number, the accelerator type, and the \sqrt{s} value used by `CIRCE1`. The chattiness can also be set.

Since the energy is distributed in a narrow region around unity (for electrons) or zero (for photons), it is advantageous to map the interval first. The mapping is controlled by the parameter `circe1_epsilon` which is taken from the `CIRCE1` internal data structure.

The \sqrt{s} value, if not explicitly set, is taken from the process data. Note that interpolating \sqrt{s} is not recommended; one should rather choose one of the distinct values known to `CIRCE1`.

15.11.2 The CIRCE1 data block

The `CIRCE1` parameters are: The incoming flavors, the flags whether the photon or the lepton is the parton in the hard interaction, the flags for the generation mode (generator/mapping/no mapping), the mapping parameter ϵ , \sqrt{s} and several steering parameters: `ver`, `rev`, `acc`, `chat`.

In generator mode, the x values are actually discarded and a random number generator is used instead.

```

<SF circe1: public>≡
  public :: circe1_data_t

<SF circe1: types>≡
  type, extends (sf_data_t) :: circe1_data_t
  private
  class(model_data_t), pointer :: model => null ()
  type(flavor_t), dimension(2) :: flv_in
  integer, dimension(2) :: pdg_in
  real(default), dimension(2) :: m_in = 0
  logical, dimension(2) :: photon = .false.
  logical :: generate = .false.
  class(rng_factory_t), allocatable :: rng_factory
  real(default) :: sqrts = 0
  real(default) :: eps = 0
  integer :: ver = 0
  integer :: rev = 0
  character(6) :: acc = "?"
  integer :: chat = 0
  logical :: with_radiation = .false.
  contains
    <SF circe1: circe1 data: TBP>
  end type circe1_data_t

<SF circe1: circe1 data: TBP>≡
  procedure :: init => circe1_data_init

```

```

<SF circe1: procedures>+=
  subroutine circe1_data_init &
    (data, model, pdg_in, sqrts, eps, out_photon, &
     ver, rev, acc, chat, with_radiation)
    class(circe1_data_t), intent(out) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), dimension(2), intent(in) :: pdg_in
    real(default), intent(in) :: sqrts
    real(default), intent(in) :: eps
    logical, dimension(2), intent(in) :: out_photon
    character(*), intent(in) :: acc
    integer, intent(in) :: ver, rev, chat
    logical, intent(in) :: with_radiation
    data%model => model
    if (any (pdg_array_get_length (pdg_in) /= 1)) then
      call msg_fatal ("CIRCE1: incoming beam particles must be unique")
    end if
    call data%flv_in(1)%init (pdg_array_get (pdg_in(1), 1), model)
    call data%flv_in(2)%init (pdg_array_get (pdg_in(2), 1), model)
    data%pdg_in = data%flv_in%get_pdg ()
    data%m_in = data%flv_in%get_mass ()
    data%sqrts = sqrts
    data%eps = eps
    data%photon = out_photon
    data%ver = ver
    data%rev = rev
    data%acc = acc
    data%chat = chat
    data%with_radiation = with_radiation
    call data%check ()
    call circex (0.d0, 0.d0, dble (data%sqrts), &
      data%acc, data%ver, data%rev, data%chat)
  end subroutine circe1_data_init

```

Activate the generator mode. We import a RNG factory into the data type, which can then spawn RNG generator objects.

```

<SF circe1: circe1 data: TBP>+=
  procedure :: set_generator_mode => circe1_data_set_generator_mode

<SF circe1: procedures>+=
  subroutine circe1_data_set_generator_mode (data, rng_factory)
    class(circe1_data_t), intent(inout) :: data
    class(rng_factory_t), intent(inout), allocatable :: rng_factory
    data%generate = .true.
    call move_alloc (from = rng_factory, to = data%rng_factory)
  end subroutine circe1_data_set_generator_mode

```

Handle error conditions.

```

<SF circe1: circe1 data: TBP>+=
  procedure :: check => circe1_data_check

<SF circe1: procedures>+=
  subroutine circe1_data_check (data)
    class(circe1_data_t), intent(in) :: data

```

```

type(flavor_t) :: flv_electron, flv_photon
call flv_electron%init (ELECTRON, data%model)
call flv_photon%init (PHOTON, data%model)
if (.not. flv_electron%is_defined () &
    .or. .not. flv_photon%is_defined ()) then
    call msg_fatal ("CIRCE1: model must contain photon and electron")
end if
if (any (abs (data%pdg_in) /= ELECTRON) &
    .or. (data%pdg_in(1) /= - data%pdg_in(2))) then
    call msg_fatal ("CIRCE1: applicable only for e+e- or e-e+ collisions")
end if
if (data%eps <= 0) then
    call msg_error ("CIRCE1: circe1_eps = 0: integration will &
        &miss x=1 peak")
end if
end subroutine circe1_data_check

```

Output

```

<SF circe1: circe1 data: TBP>+≡
    procedure :: write => circe1_data_write

<SF circe1: procedures>+≡
    subroutine circe1_data_write (data, unit, verbose)
        class(circe1_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,A)") "CIRCE1 data:"
        write (u, "(3x,A,2(1x,A))") "prt_in   =", &
            char (data%flv_in(1)%get_name ()), &
            char (data%flv_in(2)%get_name ())
        write (u, "(3x,A,2(1x,L1))") "photon   =", data%photon
        write (u, "(3x,A,L1)")      "generate = ", data%generate
        write (u, "(3x,A,2(1x," // FMT_19 // ")") "m_in     =", data%m_in
        write (u, "(3x,A," // FMT_19 // ")") "sqrts    = ", data%sqrts
        write (u, "(3x,A," // FMT_19 // ")") "eps      = ", data%eps
        write (u, "(3x,A,I0)") "ver       = ", data%ver
        write (u, "(3x,A,I0)") "rev       = ", data%rev
        write (u, "(3x,A,A)")  "acc       = ", data%acc
        write (u, "(3x,A,I0)") "chat      = ", data%chat
        write (u, "(3x,A,L1)") "with rad.= ", data%with_radiation
        if (data%generate) call data%rng_factory%write (u)
    end subroutine circe1_data_write

```

Return true if this structure function is in generator mode. In that case, all parameters are free, otherwise bound. (We do not support mixed cases.) Default is: no generator.

```

<SF circe1: circe1 data: TBP>+≡
    procedure :: is_generator => circe1_data_is_generator

<SF circe1: procedures>+≡
    function circe1_data_is_generator (data) result (flag)
        class(circe1_data_t), intent(in) :: data

```



```

    logical :: flag
    flag = data%generate
end function circe1_data_is_generator

```

The number of parameters is two, collinear splitting for the two beams.

```

<SF circe1: circe1 data: TBP>+≡
  procedure :: get_n_par => circe1_data_get_n_par

<SF circe1: procedures>+≡
  function circe1_data_get_n_par (data) result (n)
    class(circe1_data_t), intent(in) :: data
    integer :: n
    n = 2
  end function circe1_data_get_n_par

```

Return the outgoing particles PDG codes. This is either the incoming particle (if a photon is radiated), or the photon if that is the particle of the hard interaction. The latter is determined via the photon flag. There are two entries for the two beams.

```

<SF circe1: circe1 data: TBP>+≡
  procedure :: get_pdg_out => circe1_data_get_pdg_out

<SF circe1: procedures>+≡
  subroutine circe1_data_get_pdg_out (data, pdg_out)
    class(circe1_data_t), intent(in) :: data
    type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
    integer :: i, n
    n = 2
    do i = 1, n
      if (data%photon(i)) then
        pdg_out(i) = PHOTON
      else
        pdg_out(i) = data%pdg_in(i)
      end if
    end do
  end subroutine circe1_data_get_pdg_out

```

This variant is not inherited, it returns integers.

```

<SF circe1: circe1 data: TBP>+≡
  procedure :: get_pdg_int => circe1_data_get_pdg_int

<SF circe1: procedures>+≡
  function circe1_data_get_pdg_int (data) result (pdg)
    class(circe1_data_t), intent(in) :: data
    integer, dimension(2) :: pdg
    integer :: i
    do i = 1, 2
      if (data%photon(i)) then
        pdg(i) = PHOTON
      else
        pdg(i) = data%pdg_in(i)
      end if
    end do
  end function

```

```
end function circe1_data_get_pdg_int
```

Allocate the interaction record.

```
<SF circe1: data: TBP>+≡
  procedure :: allocate_sf_int => circe1_data_allocate_sf_int

<SF circe1: procedures>+≡
  subroutine circe1_data_allocate_sf_int (data, sf_int)
    class(circe1_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (circe1_t :: sf_int)
  end subroutine circe1_data_allocate_sf_int
```

15.11.3 Random Number Generator for CIRCE

The CIRCE implementation now supports a generic random-number generator object that allows for a local state as a component. To support this, we must extend the abstract type provided by CIRCE and delegate the generator call to the (also abstract) RNG used by WHIZARD.

```
<SF circe1: types>+≡
  type, extends (circe1_rng_t) :: rng_obj_t
    class(rng_t), allocatable :: rng
  contains
    procedure :: generate => rng_obj_generate
  end type rng_obj_t

<SF circe1: procedures>+≡
  subroutine rng_obj_generate (rng_obj, u)
    class(rng_obj_t), intent(inout) :: rng_obj
    real(double), intent(out) :: u
    real(default) :: x
    call rng_obj%rng%generate (x)
    u = x
  end subroutine rng_obj_generate
```

15.11.4 The CIRCE1 object

This is a $2 \rightarrow 4$ interaction, where, depending on the parameters, any two of the four outgoing particles are connected to the hard interactions, the others are radiated. Knowing that all particles are colorless, we do not have to deal with color.

The flavors are sorted such that the first two particles are the incoming leptons, the next two are the radiated particles, and the last two are the partons initiating the hard interaction.

CIRCE1 does not support polarized beams explicitly. For simplicity, we nevertheless carry beam polarization through to the outgoing electrons and make the photons unpolarized.

In the case that no radiated particle is kept (which actually is the default), polarization is always transferred to the electrons, too. If there is a recoil photon

in the event, the radiated particles are 3 and 4, respectively, and 5 and 6 are the outgoing ones (triggering the hard scattering process), while in the case of no radiation, the outgoing particles are 3 and 4, respectively. In the case of the electron being the radiated particle, helicity is not kept.

```

<SF circe1: types>+≡
  type, extends (sf_int_t) :: circe1_t
    type(circe1_data_t), pointer :: data => null ()
    real(default), dimension(2) :: x = 0
    real(default) :: f = 0
    logical, dimension(2) :: continuum = .true.
    logical, dimension(2) :: peak = .true.
    type(rng_obj_t) :: rng_obj
  contains
    <SF circe1: circe1: TBP>
  end type circe1_t

```

Type string: has to be here, but there is no string variable on which CIRCE1 depends. Hence, a dummy routine.

```

<SF circe1: circe1: TBP>≡
  procedure :: type_string => circe1_type_string

<SF circe1: procedures>+≡
  function circe1_type_string (object) result (string)
    class(circe1_t), intent(in) :: object
    type(string_t) :: string
    if (associated (object%data)) then
      string = "CIRCE1: beamstrahlung"
    else
      string = "CIRCE1: [undefined]"
    end if
  end function circe1_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF circe1: circe1: TBP>+≡
  procedure :: write => circe1_write

<SF circe1: procedures>+≡
  subroutine circe1_write (object, unit, testflag)
    class(circe1_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      if (object%data%generate) call object%rng_obj%rng%write (u)
      if (object%status >= SF_DONE_KINEMATICS) then
        write (u, "(3x,A,2(1x," // FMT_17 // ")") "x =", object%x
        if (object%status >= SF_FAILED_EVALUATION) then
          write (u, "(3x,A,1x," // FMT_17 // ")") "f =", object%f
        end if
      end if
    end if
    call object%base_write (u, testflag)
  end subroutine circe1_write

```

```

else
  write (u, "(1x,A)") "CIRCE1 data: [undefined]"
end if
end subroutine circe1_write

```

$\langle SF \text{ circe1: circe1: TBP} \rangle + \equiv$

```

procedure :: init => circe1_init

```

$\langle SF \text{ circe1: procedures} \rangle + \equiv$

```

subroutine circe1_init (sf_int, data)
  class(circe1_t), intent(out) :: sf_int
  class(sf_data_t), intent(in), target :: data
  logical, dimension(6) :: mask_h
  type(quantum_numbers_mask_t), dimension(6) :: mask
  integer, dimension(6) :: hel_lock
  type(polarization_t) :: pol1, pol2
  type(quantum_numbers_t), dimension(1) :: qn_fc1, qn_hel1, qn_fc2, qn_hel2
  type(flavor_t) :: flv_photon
  type(color_t) :: col0
  real(default), dimension(2) :: mi2, mr2, mo2
  type(quantum_numbers_t) :: qn_photon, qn1, qn2
  type(quantum_numbers_t), dimension(6) :: qn
  type(state_iterator_t) :: it_hel1, it_hel2
  hel_lock = 0
  mask_h = .false.
  select type (data)
  type is (circe1_data_t)
    mi2 = data%m_in**2
    if (data%with_radiation) then
      if (data%photon(1)) then
        hel_lock(1) = 3; hel_lock(3) = 1; mask_h(5) = .true.
        mr2(1) = mi2(1)
        mo2(1) = 0._default
      else
        hel_lock(1) = 5; hel_lock(5) = 1; mask_h(3) = .true.
        mr2(1) = 0._default
        mo2(1) = mi2(1)
      end if
      if (data%photon(2)) then
        hel_lock(2) = 4; hel_lock(4) = 2; mask_h(6) = .true.
        mr2(2) = mi2(2)
        mo2(2) = 0._default
      else
        hel_lock(2) = 6; hel_lock(6) = 2; mask_h(4) = .true.
        mr2(2) = 0._default
        mo2(2) = mi2(2)
      end if
      mask = quantum_numbers_mask (.false., .false., mask_h)
      call sf_int%base_init (mask, mi2, mr2, mo2, &
        hel_lock = hel_lock)
      sf_int%data => data
      call flv_photon%init (PHOTON, data%model)
      call col0%init ()
      call qn_photon%init (flv_photon, col0)
    end type
  end select
end subroutine circe1_init

```

```

call polarization_init_generic (pol1, data%flv_in(1))
call qn_fc1(1)%init (flv = data%flv_in(1), col = col0)
call polarization_init_generic (pol2, data%flv_in(2))
call qn_fc2(1)%init (flv = data%flv_in(2), col = col0)
call it_hel1%init (pol1%state)

do while (it_hel1%is_valid ())
  qn_hel1 = it_hel1%get_quantum_numbers ()
  qn1 = qn_hel1(1) .merge. qn_fc1(1)
  qn(1) = qn1
  if (data%photon(1)) then
    qn(3) = qn1; qn(5) = qn_photon
  else
    qn(3) = qn_photon; qn(5) = qn1
  end if
  call it_hel2%init (pol2%state)
  do while (it_hel2%is_valid ())
    qn_hel2 = it_hel2%get_quantum_numbers ()
    qn2 = qn_hel2(1) .merge. qn_fc2(1)
    qn(2) = qn2
    if (data%photon(2)) then
      qn(4) = qn2; qn(6) = qn_photon
    else
      qn(4) = qn_photon; qn(6) = qn2
    end if
    call qn(3:4)%tag_radiated ()
    call sf_int%add_state (qn)
    call it_hel2%advance ()
  end do
  call it_hel1%advance ()
end do
call polarization_final (pol1)
call polarization_final (pol2)
call sf_int%freeze ()
call sf_int%set_incoming ([1,2])
call sf_int%set_radiated ([3,4])
call sf_int%set_outgoing ([5,6])
else
  if (data%photon(1)) then
    mask_h(3) = .true.
    mo2(1) = 0._default
  else
    hel_lock(1) = 3; hel_lock(3) = 1
    mo2(1) = mi2(1)
  end if
  if (data%photon(2)) then
    mask_h(4) = .true.
    mo2(2) = 0._default
  else
    hel_lock(2) = 4; hel_lock(4) = 2
    mo2(2) = mi2(2)
  end if
  mask = quantum_numbers_mask (.false., .false., mask_h)
  call sf_int%base_init (mask(1:4), mi2, [real(default) :: ], mo2, &

```

```

        hel_lock = hel_lock(1:4))
sf_int%data => data
call flv_photon%init (PHOTON, data%model)
call col0%init ()
call qn_photon%init (flv_photon, col0)
call polarization_init_generic (pol1, data%flv_in(1))
call qn_fc1(1)%init (flv = data%flv_in(1), col = col0)
call polarization_init_generic (pol2, data%flv_in(2))
call qn_fc2(1)%init (flv = data%flv_in(2), col = col0)
call it_hel1%init (pol1%state)

do while (it_hel1%is_valid ())
    qn_hel1 = it_hel1%get_quantum_numbers ()
    qn1 = qn_hel1(1) .merge. qn_fc1(1)
    qn(1) = qn1
    if (data%photon(1)) then
        qn(3) = qn_photon
    else
        qn(3) = qn1
    end if
    call it_hel2%init (pol2%state)
    do while (it_hel2%is_valid ())
        qn_hel2 = it_hel2%get_quantum_numbers ()
        qn2 = qn_hel2(1) .merge. qn_fc2(1)
        qn(2) = qn2
        if (data%photon(2)) then
            qn(4) = qn_photon
        else
            qn(4) = qn2
        end if
        call sf_int%add_state (qn(1:4))
        call it_hel2%advance ()
    end do
    call it_hel1%advance ()
end do
call polarization_final (pol1)
call polarization_final (pol2)
call sf_int%freeze ()
call sf_int%set_incoming ([1,2])
call sf_int%set_outgoing ([3,4])
end if
sf_int%status = SF_INITIAL
end select
if (sf_int%data%generate) then
    call sf_int%data%rng_factory%make (sf_int%rng_obj%rng)
end if
end subroutine circe1_init

```

15.11.5 Kinematics

Refer to the data component.

$\langle SF\ circe1: circe1: TBP \rangle + \equiv$

```

    procedure :: is_generator => circe1_is_generator
  <SF circe1: procedures>+≡
    function circe1_is_generator (sf_int) result (flag)
      class(circe1_t), intent(in) :: sf_int
      logical :: flag
      flag = sf_int%data%is_generator ()
    end function circe1_is_generator

```

Generate free parameters, if generator mode is on. Otherwise, the parameters will be discarded.

```

  <SF circe1: circe1: TBP>+≡
    procedure :: generate_free => circe1_generate_free
  <SF circe1: procedures>+≡
    subroutine circe1_generate_free (sf_int, r, rb, x_free)
      class(circe1_t), intent(inout) :: sf_int
      real(default), dimension(:), intent(out) :: r, rb
      real(default), intent(inout) :: x_free

      if (sf_int%data%generate) then
        call circe_generate (r, sf_int%data%get_pdg_int (), sf_int%rng_obj)
        rb = 1 - r
        x_free = x_free * product (r)
      else
        r = 0
        rb = 1
      end if
    end subroutine circe1_generate_free

```

Generator mode: depending on the particle codes, call one of the available `girce` generators. Illegal particle code combinations should have been caught during data initialization.

```

  <SF circe1: procedures>+≡
    subroutine circe_generate (x, pdg, rng_obj)
      real(default), dimension(2), intent(out) :: x
      integer, dimension(2), intent(in) :: pdg
      class(rng_obj_t), intent(inout) :: rng_obj
      real(double) :: xc1, xc2
      select case (abs (pdg(1)))
      case (ELECTRON)
        select case (abs (pdg(2)))
        case (ELECTRON)
          call gircee (xc1, xc2, rng_obj = rng_obj)
        case (PHOTON)
          call girceg (xc1, xc2, rng_obj = rng_obj)
        end select
      case (PHOTON)
        select case (abs (pdg(2)))
        case (ELECTRON)
          call girceg (xc2, xc1, rng_obj = rng_obj)
        case (PHOTON)
          call gircgg (xc1, xc2, rng_obj = rng_obj)
        end select
      end select
    end subroutine

```

```

end select
x = [xc1, xc2]
end subroutine circe_generate

```

Set kinematics. The r values (either from integration or from the generator call above) are copied to x unchanged, and f is unity. We store the x values, so we can use them for the evaluation later.

```

<SF circe1: circe1: TBP>+≡
  procedure :: complete_kinematics => circe1_complete_kinematics
<SF circe1: procedures>+≡
  subroutine circe1_complete_kinematics (sf_int, x, f, r, rb, map)
    class(circe1_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: r
    real(default), dimension(:), intent(in) :: rb
    logical, intent(in) :: map
    real(default), dimension(2) :: xb1
    x = r
    sf_int%x = x
    f = 1
    if (sf_int%data%with_radiation) then
      xb1 = 1 - x
      call sf_int%split_momenta (x, xb1)
    else
      call sf_int%reduce_momenta (x)
    end if
    select case (sf_int%status)
    case (SF_FAILED_KINEMATICS); f = 0
    end select
  end subroutine circe1_complete_kinematics

```

Compute inverse kinematics. In generator mode, the r values are meaningless, but we copy them anyway.

```

<SF circe1: circe1: TBP>+≡
  procedure :: inverse_kinematics => circe1_inverse_kinematics
<SF circe1: procedures>+≡
  subroutine circe1_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
    class(circe1_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    real(default), dimension(2) :: xb1
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    r = x
    rb = 1 - x
    sf_int%x = x
    f = 1

```



```

if (set_mom) then
  xb1 = 1 - x
  call sf_int%split_momenta (x, xb1)
  select case (sf_int%status)
    case (SF_FAILED_KINEMATICS); f = 0
  end select
end if
end subroutine circe1_inverse_kinematics

```

15.11.6 CIRCE1 application

CIRCE is applied for the two beams at once. We can safely assume that no structure functions are applied before this, so the incoming particles are on-shell electrons/positrons.

The scale is ignored.

```

<SF circe1: circe1: TBP>+≡
  procedure :: apply => circe1_apply

<SF circe1: procedures>+≡
  subroutine circe1_apply (sf_int, scale)
    class(circe1_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    real(default), dimension(2) :: xb
    real(double), dimension(2) :: xc
    real(double), parameter :: one = 1
    associate (data => sf_int%data)
      xc = sf_int%x
      xb = 1 - sf_int%x
      if (data%generate) then
        sf_int%f = 1
      else
        sf_int%f = 0
        if (all (sf_int%continuum)) then
          sf_int%f = circe (xc(1), xc(2), data%pdg_in(1), data%pdg_in(2))
        end if
        if (sf_int%continuum(2) .and. sf_int%peak(1)) then
          sf_int%f = sf_int%f &
            + circe (one, xc(2), data%pdg_in(1), data%pdg_in(2)) &
            * peak (xb(1), data%eps)
        end if
        if (sf_int%continuum(1) .and. sf_int%peak(2)) then
          sf_int%f = sf_int%f &
            + circe (xc(1), one, data%pdg_in(1), data%pdg_in(2)) &
            * peak (xb(2), data%eps)
        end if
        if (all (sf_int%peak)) then
          sf_int%f = sf_int%f &
            + circe (one, one, data%pdg_in(1), data%pdg_in(2)) &
            * peak (xb(1), data%eps) * peak (xb(2), data%eps)
        end if
      end if
    end if
  end subroutine circe1_apply

```

```

end associate
call sf_int%set_matrix_element (cmplx (sf_int%f, kind=default))
sf_int%status = SF_EVALUATED
end subroutine circe1_apply

```

This is a smeared delta peak at zero, as an endpoint singularity. We choose an exponentially decreasing function, starting at zero, with integral (from 0 to 1) $1 - e^{-1/\epsilon}$. For small ϵ , this reduces to one.

```

<SF circe1: procedures>+≡
function peak (x, eps) result (f)
  real(default), intent(in) :: x, eps
  real(default) :: f
  f = exp (-x / eps) / eps
end function peak

```

15.11.7 Unit tests

```

<SF circe1: public>+≡
public :: sf_circe1_test

<SF circe1: tests>≡
subroutine sf_circe1_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
<SF circe1: execute tests>
end subroutine sf_circe1_test

```

Test structure function data

Construct and display a test structure function data object.

```

<SF circe1: execute tests>≡
call test (sf_circe1_1, "sf_circe1_1", &
  "structure function configuration", &
  u, results)

<SF circe1: tests>+≡
subroutine sf_circe1_1 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(pdg_array_t), dimension(2) :: pdg_in
  type(pdg_array_t), dimension(2) :: pdg_out
  integer, dimension(:), allocatable :: pdg1, pdg2
  class(sf_data_t), allocatable :: data

  write (u, "(A)")  "* Test output: sf_circe1_1"
  write (u, "(A)")  "* Purpose: initialize and display &
    &CIRCE structure function data"
  write (u, "(A)")

  write (u, "(A)")  "* Create empty data object"
  write (u, "(A)")

```

```

call model%init_qed_test ()
pdg_in(1) = ELECTRON
pdg_in(2) = -ELECTRON

allocate (circe1_data_t :: data)
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize"
write (u, "(A)")

select type (data)
type is (circe1_data_t)
  call data%init (model, pdg_in, &
    sqrts = 500._default, &
    eps = 1e-6_default, &
    out_photon = [.false., .false.], &
    ver = 0, &
    rev = 0, &
    acc = "SBAND", &
    chat = 0, &
    with_radiation = .true.)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
pdg2 = pdg_out(2)
write (u, "(2x,99(1x,I0))") pdg1, pdg2

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_circe1_1"

end subroutine sf_circe1_1

```

Test and probe structure function

Construct and display a structure function object based on the PDF builtin structure function.

```

<SF circe1: execute tests>+≡
  call test (sf_circe1_2, "sf_circe1_2", &
    "structure function instance", &
    u, results)

<SF circe1: tests>+≡
  subroutine sf_circe1_2 (u)

```

```

integer, intent(in) :: u
type(model_data_t), target :: model
type(flavor_t), dimension(2) :: flv
type(pdg_array_t), dimension(2) :: pdg_in
class(sf_data_t), allocatable, target :: data
class(sf_int_t), allocatable :: sf_int
type(vector4_t) :: k1, k2
type(vector4_t), dimension(4) :: q
real(default) :: E
real(default), dimension(:), allocatable :: r, rb, x
real(default) :: f

write (u, "(A)")  "* Test output: sf_circe1_2"
write (u, "(A)")  "* Purpose: initialize and fill &
                  &circe1 structure function object"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call model%init_qed_test ()
call flv(1)%init (ELECTRON, model)
call flv(2)%init (-ELECTRON, model)
pdg_in(1) = ELECTRON
pdg_in(2) = -ELECTRON

call reset_interaction_counter ()

allocate (circe1_data_t :: data)
select type (data)
type is (circe1_data_t)
    call data%init (model, pdg_in, &
        sqrts = 500._default, &
        eps = 1e-6_default, &
        out_photon = [.false., .false.], &
        ver = 0, &
        rev = 0, &
        acc = "SBAND", &
        chat = 0, &
        with_radiation = .true.)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1,2])

call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")

```

```

E = 250
k1 = vector4_moving (E, sqrt (E**2 - flv(1)%get_mass ()**2), 3)
k2 = vector4_moving (E,-sqrt (E**2 - flv(2)%get_mass ()**2), 3)
call vector4_write (k1, u)
call vector4_write (k2, u)
call sf_int%seed_kinematics ([k1, k2])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.95,0.85."
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = [0.9_default, 0.8_default]
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1, 2])

call sf_int%seed_kinematics ([k1, k2])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)

write (u, "(A,9(1x,F10.7))")  "x =", x

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%apply (scale = 0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_circe1_2"

end subroutine sf_circe1_2

```

Generator mode

Construct and evaluate a structure function object in generator mode.

```

<SF circe1: execute tests>+≡
  call test (sf_circe1_3, "sf_circe1_3", &
    "generator mode", &
    u, results)

<SF circe1: tests>+≡
  subroutine sf_circe1_3 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t), dimension(2) :: flv
    type(pdg_array_t), dimension(2) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(rng_factory_t), allocatable :: rng_factory
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k1, k2
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f, x_free

    write (u, "(A)")  "* Test output: sf_circe1_3"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &circe1 structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_qed_test ()
    call flv(1)%init (ELECTRON, model)
    call flv(2)%init (-ELECTRON, model)
    pdg_in(1) = ELECTRON
    pdg_in(2) = -ELECTRON

    call reset_interaction_counter ()

    allocate (circe1_data_t :: data)
    allocate (rng_test_factory_t :: rng_factory)
    select type (data)
    type is (circe1_data_t)
      call data%init (model, pdg_in, &
        sqrts = 500._default, &
        eps = 1e-6_default, &
        out_photon = [.false., .false.], &
        ver = 0, &

```

```

        rev = 0, &
        acc = "SBAND", &
        chat = 0, &
        with_radiation = .true.)
    call data%set_generator_mode (rng_factory)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1,2])
select type (sf_int)
type is (circe1_t)
    call sf_int%rng_obj%rng%init (3)
end select

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 250
k1 = vector4_moving (E, sqrt (E**2 - flv(1)%get_mass ()**2), 3)
k2 = vector4_moving (E, -sqrt (E**2 - flv(2)%get_mass ()**2), 3)
call vector4_write (k1, u)
call vector4_write (k2, u)
call sf_int%seed_kinematics ([k1, k2])

write (u, "(A)")
write (u, "(A)")  "* Generate x"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0
rb = 0
x_free = 1
call sf_int%generate_free (r, rb, x_free)
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_int%apply (scale = 0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```

```
call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_circe1_3"

end subroutine sf_circe1_3
```


15.12 Lepton Collider Beamstrahlung and Photon collider: CIRCE2

```
<sf_circe2.f90>≡  
<File header>  
  
module sf_circe2  
  
  <Use kinds>  
    use kinds, only: double  
  <Use strings>  
    use io_units  
    use format_defs, only: FMT_19  
    use unit_tests  
    use diagnostics  
    use os_interface  
    use physics_defs, only: UNDEFINED, PHOTON, ELECTRON  
    use lorentz  
    use rng_base  
    use selectors  
    use pdg_arrays  
    use model_data  
    use flavors  
    use colors  
    use helicities  
    use quantum_numbers  
    use state_matrices  
    use polarizations  
    use interactions  
    use sf_aux  
    use sf_base  
    use circe2, circe2_rng_t => rng_type !NODEP!  
  
  <Standard module head>  
  
  <SF circe2: public>  
  
  <SF circe2: types>  
  
contains  
  
  <SF circe2: procedures>  
  
  <SF circe2: tests>  
  
end module sf_circe2
```

15.12.1 Physics

CIRCE2 describes photon spectra Beamstrahlung is applied before ISR. The CIRCE2 implementation has a single structure function for both beams (which makes sense since it has to be switched on or off for both beams simultaneously).

15.12.2 The CIRCE2 data block

The CIRCE2 parameters are: file and collider specification, incoming (= outgoing) particles. The luminosity is returned by `circe2_luminosity`.

(SF circe2: public)≡

```
public :: circe2_data_t
```

(SF circe2: types)≡

```
type, extends (sf_data_t) :: circe2_data_t
  private
    class(model_data_t), pointer :: model => null ()
    type(flavor_t), dimension(2) :: flv_in
    integer, dimension(2) :: pdg_in
    real(default) :: sqrts = 0
    logical :: polarized = .false.
    class(rng_factory_t), allocatable :: rng_factory
    type(string_t) :: filename
    type(string_t) :: file
    type(string_t) :: design
    real(default) :: lumi = 0
    real(default), dimension(4) :: lumi_hel_frac = 0
    integer, dimension(0:4) :: h1 = [0, -1, -1, 1, 1]
    integer, dimension(0:4) :: h2 = [0, -1, 1, -1, 1]
    integer :: error = 1
  contains
    (SF circe2: circe2 data: TBP)
  end type circe2_data_t
```

(SF circe2: types)+≡

```
type(circe2_state) :: circe2_global_state
```

(SF circe2: circe2 data: TBP)≡

```
procedure :: init => circe2_data_init
```

(SF circe2: procedures)≡

```
subroutine circe2_data_init (data, os_data, model, pdg_in, &
  sqrts, polarized, file, design)
  class(circe2_data_t), intent(out) :: data
  type(os_data_t), intent(in) :: os_data
  class(model_data_t), intent(in), target :: model
  type(pdg_array_t), dimension(2), intent(in) :: pdg_in
  real(default), intent(in) :: sqrts
  logical, intent(in) :: polarized
  type(string_t), intent(in) :: file, design
  integer :: h
  data%model => model
  if (any (pdg_array_get_length (pdg_in) /= 1)) then
    call msg_fatal ("CIRCE2: incoming beam particles must be unique")
  end if
  call data%flv_in(1)%init (pdg_array_get (pdg_in(1), 1), model)
  call data%flv_in(2)%init (pdg_array_get (pdg_in(2), 1), model)
  data%pdg_in = data%flv_in%get_pdg ()
  data%sqrts = sqrts
  data%polarized = polarized
```

```

data%filename = file
data%design = design
call data%check_file (os_data)
call circe2_load (circe2_global_state, trim (char(data%file)), &
    trim (char(data%design)), data%sqrts, data%error)
data%lumi = circe2_luminosity (circe2_global_state, data%pdg_in, [0, 0])
call data%check ()
if (data%polarized) then
    do h = 1, 4
        data%lumi_hel_frac(h) = &
            circe2_luminosity (circe2_global_state, data%pdg_in, &
                [data%h1(h), data%h2(h)]) &
            / data%lumi
    end do
end if
end subroutine circe2_data_init

```

Activate the generator mode. We import a RNG factory into the data type, which can then spawn RNG generator objects.

```

<SF circe2: circe2 data: TBP>+=
    procedure :: set_generator_mode => circe2_data_set_generator_mode

<SF circe2: procedures>+=
    subroutine circe2_data_set_generator_mode (data, rng_factory)
        class(circe2_data_t), intent(inout) :: data
        class(rng_factory_t), intent(inout), allocatable :: rng_factory
        call move_alloc (from = rng_factory, to = data%rng_factory)
    end subroutine circe2_data_set_generator_mode

```

Check whether the requested data file is in the system directory or in the current directory.

```

<SF circe2: circe2 data: TBP>+=
    procedure :: check_file => circe2_check_file

<SF circe2: procedures>+=
    subroutine circe2_check_file (data, os_data)
        class(circe2_data_t), intent(inout) :: data
        type(os_data_t), intent(in) :: os_data
        logical :: exist
        type(string_t) :: file
        file = data%filename
        if (file == "") &
            call msg_fatal ("CIRCE2: $circe2_file is not set")
        inquire (file = char (file), exist = exist)
        if (exist) then
            data%file = file
        else
            file = os_data%whizard_circe2path // "/" // data%filename
            inquire (file = char (file), exist = exist)
            if (exist) then
                data%file = file
            else
                call msg_fatal ("CIRCE2: data file '" // char (data%filename) &
                    // "' not found")
            end if
        end if
    end subroutine circe2_check_file

```

```

        end if
    end if
end subroutine circe2_check_file

```

Handle error conditions.

```

<SF circe2: circe2 data: TBP>+≡
    procedure :: check => circe2_data_check

<SF circe2: procedures>+≡
    subroutine circe2_data_check (data)
        class(circe2_data_t), intent(in) :: data
        type(flavor_t) :: flv_photon, flv_electron
        call flv_photon%init (PHOTON, data%model)
        if (.not. flv_photon%is_defined ()) then
            call msg_fatal ("CIRCE2: model must contain photon")
        end if
        call flv_electron%init (ELECTRON, data%model)
        if (.not. flv_electron%is_defined ()) then
            call msg_fatal ("CIRCE2: model must contain electron")
        end if
        if (any (abs (data%pdg_in) /= PHOTON .and. abs (data%pdg_in) /= ELECTRON)) &
            then
                call msg_fatal ("CIRCE2: applicable only for e+e- or photon collisions")
            end if
        select case (data%error)
        case (-1)
            call msg_fatal ("CIRCE2: data file not found.")
        case (-2)
            call msg_fatal ("CIRCE2: beam parameters do not match data file.")
        case (-3)
            call msg_fatal ("CIRCE2: invalid format of data file.")
        case (-4)
            call msg_fatal ("CIRCE2: data file too large.")
        end select
        if (data%lumi == 0) then
            call msg_fatal ("CIRCE2: luminosity vanishes for specified beams.")
        end if
    end subroutine circe2_data_check

```

Output

```

<SF circe2: circe2 data: TBP>+≡
    procedure :: write => circe2_data_write

<SF circe2: procedures>+≡
    subroutine circe2_data_write (data, unit, verbose)
        class(circe2_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        integer :: u, h
        u = given_output_unit (unit)
        write (u, "(1x,A)") "CIRCE2 data:"
        write (u, "(3x,A,A)")          "file  = ", char(data%filename)
        write (u, "(3x,A,A)")          "design = ", char(data%design)
        write (u, "(3x,A," // FMT_19 // ")") "sqrts = ", data%sqrts
    end subroutine circe2_data_write

```

```

write (u, "(3x,A,A,A,A)")    "prt_in = ", &
char (data%flv_in(1)%get_name ()), &
", ", char (data%flv_in(2)%get_name ())
write (u, "(3x,A,L1)")        "polarized = ", data%polarized
write (u, "(3x,A," // FMT_19 // ")") "luminosity = ", data%lumi
if (data%polarized) then
do h = 1, 4
write (u, "(6x,'(',I2,1x,I2,')',1x,'=',1x)", advance="no") &
data%h1(h), data%h2(h)
write (u, "(6x, " // FMT_19 // ")") data%lumi_hel_frac(h)
end do
end if
call data%rng_factory%write (u)
end subroutine circe2_data_write

```

This is always in generator mode.

```

<SF circe2: circe2 data: TBP>+≡
procedure :: is_generator => circe2_data_is_generator

<SF circe2: procedures>+≡
function circe2_data_is_generator (data) result (flag)
class(circe2_data_t), intent(in) :: data
logical :: flag
flag = .true.
end function circe2_data_is_generator

```

The number of parameters is two, collinear splitting for the two beams.

```

<SF circe2: circe2 data: TBP>+≡
procedure :: get_n_par => circe2_data_get_n_par

<SF circe2: procedures>+≡
function circe2_data_get_n_par (data) result (n)
class(circe2_data_t), intent(in) :: data
integer :: n
n = 2
end function circe2_data_get_n_par

```

Return the outgoing particles PDG codes. They are equal to the incoming ones.

```

<SF circe2: circe2 data: TBP>+≡
procedure :: get_pdg_out => circe2_data_get_pdg_out

<SF circe2: procedures>+≡
subroutine circe2_data_get_pdg_out (data, pdg_out)
class(circe2_data_t), intent(in) :: data
type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
integer :: i, n
n = 2
do i = 1, n
pdg_out(i) = data%pdg_in(i)
end do
end subroutine circe2_data_get_pdg_out

```

Allocate the interaction record.

```

<SF circe2: circe2 data: TBP>+=
  procedure :: allocate_sf_int => circe2_data_allocate_sf_int

<SF circe2: procedures>+=
  subroutine circe2_data_allocate_sf_int (data, sf_int)
    class(circe2_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (circe2_t :: sf_int)
  end subroutine circe2_data_allocate_sf_int

```

15.12.3 Random Number Generator for CIRCE

The CIRCE implementation now supports a generic random-number generator object that allows for a local state as a component. To support this, we must extend the abstract type provided by CIRCE and delegate the generator call to the (also abstract) RNG used by WHIZARD.

```

<SF circe2: types>+=
  type, extends (circe2_rng_t) :: rng_obj_t
    class(rng_t), allocatable :: rng
  contains
    procedure :: generate => rng_obj_generate
  end type rng_obj_t

```

```

<SF circe2: procedures>+=
  subroutine rng_obj_generate (rng_obj, u)
    class(rng_obj_t), intent(inout) :: rng_obj
    real(default), intent(out) :: u
    real(default) :: x
    call rng_obj%rng%generate (x)
    u = x
  end subroutine rng_obj_generate

```

15.12.4 The CIRCE2 object

For CIRCE2 spectra it does not make sense to describe the state matrix as a radiation interaction, even if photons originate from laser backscattering. Instead, it is a $2 \rightarrow 2$ interaction where the incoming particles are identical to the outgoing ones.

The current implementation of CIRCE2 does support polarization and classical correlations, but no entanglement, so the density matrix of the outgoing particles is diagonal. The incoming particles are unpolarized (user-defined polarization for beams is meaningless, since polarization is described by the data file). The outgoing particles are polarized or polarization-averaged, depending on user request.

When assigning matrix elements, we scan the previously initialized state matrix. For each entry, we extract helicity and call the structure function. In the unpolarized case, the helicity is undefined and replaced by value zero. In the polarized case, there are four entries. If the generator is used, only one entry is

nonzero in each call. Which one, is determined by comparing with a previously (randomly, distributed by relative luminosity) selected pair of helicities.

```

<SF circe2: types>+≡
  type, extends (sf_int_t) :: circe2_t
    type(circe2_data_t), pointer :: data => null ()
    type(rng_obj_t) :: rng_obj
    type(selector_t) :: selector
    integer :: h_sel = 0
  contains
    <SF circe2: circe2: TBP>
  end type circe2_t

```

Type string: show file and design of CIRCE2 structure function.

```

<SF circe2: circe2: TBP>≡
  procedure :: type_string => circe2_type_string

<SF circe2: procedures>+≡
  function circe2_type_string (object) result (string)
    class(circe2_t), intent(in) :: object
    type(string_t) :: string
    if (associated (object%data)) then
      string = "CIRCE2: " // object%data%design
    else
      string = "CIRCE2: [undefined]"
    end if
  end function circe2_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF circe2: circe2: TBP>+≡
  procedure :: write => circe2_write

<SF circe2: procedures>+≡
  subroutine circe2_write (object, unit, testflag)
    class(circe2_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      call object%base_write (u, testflag)
    else
      write (u, "(1x,A)") "CIRCE2 data: [undefined]"
    end if
  end subroutine circe2_write

```

```

<SF circe2: circe2: TBP>+≡
  procedure :: init => circe2_init

<SF circe2: procedures>+≡
  subroutine circe2_init (sf_int, data)
    class(circe2_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data

```

```

logical, dimension(4) :: mask_h
real(default), dimension(0) :: null_array
type(quantum_numbers_mask_t), dimension(4) :: mask
type(quantum_numbers_t), dimension(4) :: qn
type(helicity_t) :: hel
type(color_t) :: col0
integer :: h
select type (data)
type is (circe2_data_t)
  mask_h(1:2) = .true.
  mask_h(3:4) = .not. data%polarized
  mask = quantum_numbers_mask (.false., .false., mask_h)
  call sf_int%base_init (mask, [0._default, 0._default], &
    null_array, [0._default, 0._default])
  sf_int%data => data
  if (data%polarized) then
    if (sum (data%lumi_hel_frac) == 0 .or. &
      any (data%lumi_hel_frac < 0)) then
      call msg_fatal ("Circe2: Helicity-dependent lumi " &
        // "fractions all vanish or", &
        [var_str ("are negative: Please inspect the " &
          // "CIRCE2 file or "), &
          var_str ("switch off the polarized" // &
            " option for Circe2.")])
    else
      call sf_int%selector%init (data%lumi_hel_frac)
    end if
  end if
  call col0%init ()
  call qn(1)%init (flv = data%flv_in(1), col = col0)
  call qn(2)%init (flv = data%flv_in(2), col = col0)
  if (data%polarized) then
    do h = 1, 4
      call hel%init (data%h1(h))
      call qn(3)%init &
        (flv = data%flv_in(1), col = col0, hel = hel)
      call hel%init (data%h2(h))
      call qn(4)%init &
        (flv = data%flv_in(2), col = col0, hel = hel)
      call sf_int%add_state (qn)
    end do
  else
    call qn(3)%init (flv = data%flv_in(1), col = col0)
    call qn(4)%init (flv = data%flv_in(2), col = col0)
    call qn(3:4)%tag_radiated ()
    call sf_int%add_state (qn)
  end if
  call sf_int%freeze ()
  call sf_int%set_incoming ([1,2])
  call sf_int%set_outgoing ([3,4])
  call sf_int%data%rng_factory%make (sf_int%rng_obj%rng)
  sf_int%status = SF_INITIAL
end select
end subroutine circe2_init

```


15.12.5 Kinematics

Refer to the data component.

```
<SF circe2: circe2: TBP>+≡  
  procedure :: is_generator => circe2_is_generator  
  
<SF circe2: procedures>+≡  
  function circe2_is_generator (sf_int) result (flag)  
    class(circe2_t), intent(in) :: sf_int  
    logical :: flag  
    flag = sf_int%data%is_generator ()  
  end function circe2_is_generator
```

Generate free parameters. We first select a helicity, which we have to store, then generate x values for that helicity.

```
<SF circe2: circe2: TBP>+≡  
  procedure :: generate_free => circe2_generate_whizard_free  
  
<SF circe2: procedures>+≡  
  subroutine circe2_generate_whizard_free (sf_int, r, rb, x_free)  
    class(circe2_t), intent(inout) :: sf_int  
    real(default), dimension(:), intent(out) :: r, rb  
    real(default), intent(inout) :: x_free  
    integer :: h_sel  
    if (sf_int%data%polarized) then  
      call sf_int%selector%generate (sf_int%rng_obj%rng, h_sel)  
    else  
      h_sel = 0  
    end if  
    sf_int%h_sel = h_sel  
    call circe2_generate_whizard (r, sf_int%data%pdg_in, &  
      [sf_int%data%h1(h_sel), sf_int%data%h2(h_sel)], &  
      sf_int%rng_obj)  
    rb = 1 - r  
    x_free = x_free * product (r)  
  end subroutine circe2_generate_whizard_free
```

Generator mode: call the CIRCE2 generator for the given particles and helicities. (For unpolarized generation, helicities are zero.)

```
<SF circe2: procedures>+≡  
  subroutine circe2_generate_whizard (x, pdg, hel, rng_obj)  
    real(default), dimension(2), intent(out) :: x  
    integer, dimension(2), intent(in) :: pdg  
    integer, dimension(2), intent(in) :: hel  
    class(rng_obj_t), intent(inout) :: rng_obj  
    call circe2_generate (circe2_global_state, rng_obj, x, pdg, hel)  
  end subroutine circe2_generate_whizard
```

Set kinematics. Trivial here.

```
<SF circe2: circe2: TBP>+≡  
  procedure :: complete_kinematics => circe2_complete_kinematics
```

```

<SF circe2: procedures>+≡
  subroutine circe2_complete_kinematics (sf_int, x, f, r, rb, map)
    class(circe2_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: r
    real(default), dimension(:), intent(in) :: rb
    logical, intent(in) :: map
    if (map) then
      call msg_fatal ("CIRCE2: map flag not supported")
    else
      x = r
      f = 1
    end if
    call sf_int%reduce_momenta (x)
  end subroutine circe2_complete_kinematics

```

Compute inverse kinematics.

```

<SF circe2: circe2: TBP>+≡
  procedure :: inverse_kinematics => circe2_inverse_kinematics

<SF circe2: procedures>+≡
  subroutine circe2_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
    class(circe2_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    if (map) then
      call msg_fatal ("CIRCE2: map flag not supported")
    else
      r = x
      rb = 1 - r
      f = 1
    end if
    if (set_mom) then
      call sf_int%reduce_momenta (x)
    end if
  end subroutine circe2_inverse_kinematics

```

15.12.6 CIRCE2 application

This function works on both beams. In polarized mode, we set only the selected helicity. In unpolarized mode, the interaction has only one entry, and the factor is unity.

```

<SF circe2: circe2: TBP>+≡
  procedure :: apply => circe2_apply

```

```

<SF circe2: procedures>+≡
  subroutine circe2_apply (sf_int, scale)
    class(circe2_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    complex(default) :: f
    integer :: h
    associate (data => sf_int%data)
      f = 1
      if (data%polarized) then
        h = sf_int%h_sel
      else
        h = 1
      end if
      call sf_int%set_matrix_element (h, f)
    end associate
    sf_int%status = SF_EVALUATED
  end subroutine circe2_apply

```

15.12.7 Unit tests

```

<SF circe2: public>+≡
  public :: sf_circe2_test

<SF circe2: tests>≡
  subroutine sf_circe2_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <SF circe2: execute tests>
  end subroutine sf_circe2_test

```

Test structure function data

Construct and display a test structure function data object.

```

<SF circe2: execute tests>≡
  call test (sf_circe2_1, "sf_circe2_1", &
    "structure function configuration", &
    u, results)

<SF circe2: tests>+≡
  subroutine sf_circe2_1 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(model_data_t), target :: model
    type(pdg_array_t), dimension(2) :: pdg_in
    type(pdg_array_t), dimension(2) :: pdg_out
    integer, dimension(:), allocatable :: pdg1, pdg2
    class(sf_data_t), allocatable :: data
    class(rng_factory_t), allocatable :: rng_factory

    write (u, "(A)")  "* Test output: sf_circe2_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &CIRCE structure function data"

```

```

write (u, "(A)")

write (u, "(A)")  "* Create empty data object"
write (u, "(A)")

call os_data_init (os_data)
call model%init_qed_test ()
pdg_in(1) = PHOTON
pdg_in(2) = PHOTON

allocate (circe2_data_t :: data)
allocate (rng_test_factory_t :: rng_factory)

write (u, "(A)")
write (u, "(A)")  "* Initialize (unpolarized)"
write (u, "(A)")

select type (data)
type is (circe2_data_t)
  call data%init (os_data, model, pdg_in, &
    sqrts = 500._default, &
    polarized = .false., &
    file = var_str ("teslagg_500_polavg.circe"), &
    design = var_str ("TESLA/GG"))
  call data%set_generator_mode (rng_factory)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)")  "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
pdg2 = pdg_out(2)
write (u, "(2x,99(1x,I0))")  pdg1, pdg2

write (u, "(A)")
write (u, "(A)")  "* Initialize (polarized)"
write (u, "(A)")

allocate (rng_test_factory_t :: rng_factory)

select type (data)
type is (circe2_data_t)
  call data%init (os_data, model, pdg_in, &
    sqrts = 500._default, &
    polarized = .true., &
    file = var_str ("teslagg_500.circe"), &
    design = var_str ("TESLA/GG"))
  call data%set_generator_mode (rng_factory)
end select

call data%write (u)

```

```

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_circe2_1"

end subroutine sf_circe2_1

```

Generator mode, unpolarized

Construct and evaluate a structure function object in generator mode.

```

<SF circe2: execute tests>+≡
  call test (sf_circe2_2, "sf_circe2_2", &
    "generator, unpolarized", &
    u, results)

<SF circe2: tests>+≡
  subroutine sf_circe2_2 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(model_data_t), target :: model
    type(flavor_t), dimension(2) :: flv
    type(pdg_array_t), dimension(2) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(rng_factory_t), allocatable :: rng_factory
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k1, k2
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f, x_free

    write (u, "(A)")  "* Test output: sf_circe2_2"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &circe2 structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call os_data_init (os_data)
    call model%init_qed_test ()
    call flv(1)%init (PHOTON, model)
    call flv(2)%init (PHOTON, model)
    pdg_in(1) = PHOTON
    pdg_in(2) = PHOTON

    call reset_interaction_counter ()

    allocate (circe2_data_t :: data)
    allocate (rng_test_factory_t :: rng_factory)
    select type (data)
    type is (circe2_data_t)
      call data%init (os_data, model, pdg_in, &

```

```

        sqrts = 500._default, &
        polarized = .false., &
        file = var_str ("teslagg_500_polavg.circe"), &
        design = var_str ("TESLA/GG"))
    call data%set_generator_mode (rng_factory)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1,2])
select type (sf_int)
type is (circe2_t)
    call sf_int%rng_obj%rng%init (3)
end select

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 250
k1 = vector4_moving (E, sqrt (E**2 - flv(1)%get_mass ()**2), 3)
k2 = vector4_moving (E, -sqrt (E**2 - flv(2)%get_mass ()**2), 3)
call vector4_write (k1, u)
call vector4_write (k2, u)
call sf_int%seed_kinematics ([k1, k2])

write (u, "(A)")
write (u, "(A)")  "* Generate x"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0
rb = 0
x_free = 1
call sf_int%generate_free (r, rb, x_free)
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_int%apply (scale = 0._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```

```

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_circe2_2"

end subroutine sf_circe2_2

```

Generator mode, polarized

Construct and evaluate a structure function object in generator mode.

```

<SF circe2: execute tests>+≡
  call test (sf_circe2_3, "sf_circe2_3", &
    "generator, polarized", &
    u, results)

<SF circe2: tests>+≡
  subroutine sf_circe2_3 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(model_data_t), target :: model
    type(flavor_t), dimension(2) :: flv
    type(pdg_array_t), dimension(2) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(rng_factory_t), allocatable :: rng_factory
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k1, k2
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f, x_free

    write (u, "(A)")  "* Test output: sf_circe2_3"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &circe2 structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call os_data_init (os_data)
    call model%init_qed_test ()
    call flv(1)%init (PHOTON, model)
    call flv(2)%init (PHOTON, model)
    pdg_in(1) = PHOTON
    pdg_in(2) = PHOTON

    call reset_interaction_counter ()

    allocate (circe2_data_t :: data)
    allocate (rng_test_factory_t :: rng_factory)
    select type (data)
    type is (circe2_data_t)

```

```

        call data%init (os_data, model, pdg_in, &
            sqrts = 500._default, &
            polarized = .true., &
            file = var_str ("teslagg_500.circe"), &
            design = var_str ("TESLA/GG"))
        call data%set_generator_mode (rng_factory)
    end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1,2])
select type (sf_int)
type is (circe2_t)
    call sf_int%rng_obj%rng%init (3)
end select

write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 250
k1 = vector4_moving (E, sqrt (E**2 - flv(1)%get_mass ()**2), 3)
k2 = vector4_moving (E, -sqrt (E**2 - flv(2)%get_mass ()**2), 3)
call vector4_write (k1, u)
call vector4_write (k2, u)
call sf_int%seed_kinematics ([k1, k2])

write (u, "(A)")
write (u, "(A)")  "* Generate x"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0
rb = 0
x_free = 1
call sf_int%generate_free (r, rb, x_free)
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)

write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f
write (u, "(A,9(1x,F10.7))")  "xf=", x_free

write (u, "(A)")
write (u, "(A)")  "* Evaluate"
write (u, "(A)")

call sf_int%apply (scale = 0._default)
call sf_int%write (u)

write (u, "(A)")

```



```
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_circe2_3"

end subroutine sf_circe2_3
```

15.13 HOPPET interface

Interface to the HOPPET wrapper necessary to perform the LO vs. NLO matching of processes containing an initial b quark.

```
<hoppet_interface.f90>≡  
  <File header>  
  
  module hoppet_interface  
    use lhapdf !NODEP!  
  
    <Standard module head>  
  
    public :: hoppet_init, hoppet_eval  
  
  contains  
  
    subroutine hoppet_init (pdf_builtin, pdf, pdf_id)  
      logical, intent(in) :: pdf_builtin  
      type(lhapdf_pdf_t), intent(inout), optional :: pdf  
      integer, intent(in), optional :: pdf_id  
      external InitForWhizard  
      call InitForWhizard (pdf_builtin, pdf, pdf_id)  
    end subroutine hoppet_init  
  
    subroutine hoppet_eval (x, q, f)  
      double precision, intent(in) :: x, q  
      double precision, intent(out) :: f(-6:6)  
      external EvalForWhizard  
      call EvalForWhizard (x, q, f)  
    end subroutine hoppet_eval  
  
  end module hoppet_interface
```

15.14 Builtin PDF sets

For convenience in order not to depend on the external package LHAPDF, we ship some PDFs with WHIZARD.

15.14.1 The module

```
<sf_pdf_builtin.f90>≡  
<File header>  
  
module sf_pdf_builtin  
  
  <Use kinds>  
    use kinds, only: double  
  <Use strings>  
    use io_units  
    use format_defs, only: FMT_17  
    use unit_tests  
    use diagnostics  
    use os_interface  
    use physics_defs, only: PROTON, PHOTON, GLUON  
    use physics_defs, only: HADRON_REMNANT_SINGLET  
    use physics_defs, only: HADRON_REMNANT_TRIPLET  
    use physics_defs, only: HADRON_REMNANT_OCTET  
    use sm_qcd  
    use lorentz  
    use pdg_arrays  
    use model_data  
    use flavors  
    use colors  
    use quantum_numbers  
    use state_matrices  
    use polarizations  
    use interactions  
    use sf_aux  
    use sf_base  
    use pdf_builtin !NODEP!  
    use hoppet_interface  
  
  <Standard module head>  
  
  <SF pdf builtin: public>  
  
  <SF pdf builtin: types>  
  
  <SF pdf builtin: parameters>  
  
contains  
  
  <SF pdf builtin: procedures>  
  
  <SF pdf builtin: tests>  
  
end module sf_pdf_builtin
```

15.14.2 Codes for default PDF sets

```
<SF pdf builtin: parameters>≡
  character(*), parameter :: PDF_BUILTIN_DEFAULT_PROTON = "CTEQ6L"
  character(*), parameter :: PDF_BUILTIN_DEFAULT_PION   = "NONE"
  character(*), parameter :: PDF_BUILTIN_DEFAULT_PHOTON = "MRST2004QEDp"
```

15.14.3 The PDF builtin data block

The data block holds the incoming flavor (which has to be proton, pion, or photon), the corresponding pointer to the global access data (1, 2, or 3), the flag `invert` which is set for an antiproton, the bounds as returned by LHAPDF for the specified set, and a mask that determines which partons will be actually in use.

```
<SF pdf builtin: public>≡
  public :: pdf_builtin_data_t

<SF pdf builtin: types>≡
  type, extends (sf_data_t) :: pdf_builtin_data_t
  private
  integer :: id = -1
  type (string_t) :: name
  class(model_data_t), pointer :: model => null ()
  type(flavor_t) :: flv_in
  logical :: invert
  logical :: has_photon
  logical :: photon
  logical, dimension(-6:6) :: mask
  logical :: mask_photon
  logical :: hoppet_b_matching = .false.
  contains
  <SF pdf builtin: pdf builtin data: TBP>
  end type pdf_builtin_data_t
```

Generate PDF data and initialize the requested set. Pion and photon PDFs are disabled at the moment until we ship appropriate structure functions. needed.

```
<SF pdf builtin: pdf builtin data: TBP>≡
  procedure :: init => pdf_builtin_data_init

<SF pdf builtin: procedures>≡
  subroutine pdf_builtin_data_init (data, &
    model, pdg_in, name, path, hoppet_b_matching)
    class(pdf_builtin_data_t), intent(out) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), intent(in) :: pdg_in
    type(string_t), intent(in) :: name
    type(string_t), intent(in) :: path
    logical, intent(in), optional :: hoppet_b_matching
    data%model => model
    if (pdg_array_get_length (pdg_in) /= 1) &
      call msg_fatal ("PDF: incoming particle must be unique")
    call data%flv_in%init (pdg_array_get (pdg_in, 1), model)
    data%mask = .true.
    data%mask_photon = .true.
```

```

select case (pdg_array_get (pdg_in, 1))
case (PROTON)
  data%name = var_str (PDF_BUILTIN_DEFAULT_PROTON)
  data%invert = .false.
  data%photon = .false.
case (-PROTON)
  data%name = var_str (PDF_BUILTIN_DEFAULT_PROTON)
  data%invert = .true.
  data%photon = .false.
  ! case (PIPLUS)
  !   data%name = var_str (PDF_BUILTIN_DEFAULT_PION)
  !   data%invert = .false.
  !   data%photon = .false.
  ! case (-PIPLUS)
  !   data%name = var_str (PDF_BUILTIN_DEFAULT_PION)
  !   data%invert = .true.
  !   data%photon = .false.
  ! case (PHOTON)
  !   data%name = var_str (PDF_BUILTIN_DEFAULT_PHOTON)
  !   data%invert = .false.
  !   data%photon = .true.
case default
  call msg_fatal ("PDF: " &
    // "incoming particle must either proton or antiproton.")
  return
end select
data%name = name
data%id = pdf_get_id (data%name)
if (data%id < 0) call msg_fatal ("unknown PDF set " // char (data%name))
data%has_photon = pdf_provides_photon (data%id)
if (present (hoppet_b_matching)) data%hoppet_b_matching = hoppet_b_matching
call pdf_init (data%id, path)
if (data%hoppet_b_matching) call hoppet_init (.true., pdf_id = data%id)
end subroutine pdf_builtin_data_init

```

Enable/disable partons explicitly. If a mask entry is true, applying the PDF will generate the corresponding flavor on output.

```

<SF pdf builtin: pdf builtin data: TBP>+≡
  procedure :: set_mask => pdf_builtin_data_set_mask

<SF pdf builtin: procedures>+≡
  subroutine pdf_builtin_data_set_mask (data, mask)
    class(pdf_builtin_data_t), intent(inout) :: data
    logical, dimension(-6:6), intent(in) :: mask
    data%mask = mask
  end subroutine pdf_builtin_data_set_mask

```

Output.

```

<SF pdf builtin: pdf builtin data: TBP>+≡
  procedure :: write => pdf_builtin_data_write

<SF pdf builtin: procedures>+≡
  subroutine pdf_builtin_data_write (data, unit, verbose)
    class(pdf_builtin_data_t), intent(in) :: data

```

```

integer, intent(in), optional :: unit
logical, intent(in), optional :: verbose
integer :: u
u = given_output_unit (unit); if (u < 0) return
write (u, "(1x,A)") "PDF builtin data:"
if (data%id < 0) then
  write (u, "(3x,A)") "[undefined]"
  return
end if
write (u, "(3x,A)", advance="no") "flavor      = "
call data%flv_in%write (u); write (u, *)
write (u, "(3x,A,A)") "name      = ", char (data%name)
write (u, "(3x,A,L1)") "invert    = ", data%invert
write (u, "(3x,A,L1)") "has photon = ", data%has_photon
write (u, "(3x,A,6(1x,L1),1x,A,1x,L1,1x,A,6(1x,L1))") &
  "mask      = ", &
  data%mask(-6:-1), " ", data%mask(0), " ", data%mask(1:6)
write (u, "(3x,A,L1)") "photon mask = ", data%mask_photon
write (u, "(3x,A,L1)") "hoppet_b    = ", data%hoppet_b_matching
end subroutine pdf_builtin_data_write

```

The number of parameters is one. We do not generate transverse momentum.

```

<SF pdf builtin: pdf builtin data: TBP>+≡
  procedure :: get_n_par => pdf_builtin_data_get_n_par

<SF pdf builtin: procedures>+≡
  function pdf_builtin_data_get_n_par (data) result (n)
    class(pdf_builtin_data_t), intent(in) :: data
    integer :: n
    n = 1
  end function pdf_builtin_data_get_n_par

```

Return the outgoing particle PDG codes. This is based on the mask.

```

<SF pdf builtin: pdf builtin data: TBP>+≡
  procedure :: get_pdg_out => pdf_builtin_data_get_pdg_out

<SF pdf builtin: procedures>+≡
  subroutine pdf_builtin_data_get_pdg_out (data, pdg_out)
    class(pdf_builtin_data_t), intent(in) :: data
    type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
    integer, dimension(:), allocatable :: pdg1
    integer :: n, np, i
    n = count (data%mask)
    np = 0; if (data%has_photon .and. data%mask_photon) np = 1
    allocate (pdg1 (n + np))
    pdg1(1:n) = pack ([i, i = -6, 6], data%mask)
    if (np == 1) pdg1(n+np) = PHOTON
    pdg_out(1) = pdg1
  end subroutine pdf_builtin_data_get_pdg_out

```

Allocate the interaction record.

```

<SF pdf builtin: pdf builtin data: TBP>+≡
  procedure :: allocate_sf_int => pdf_builtin_data_allocate_sf_int

```

```

<SF pdf builtin: procedures>+=
  subroutine pdf_builtin_data_allocate_sf_int (data, sf_int)
    class(pdf_builtin_data_t), intent(in) :: data
    class(sf_int_t), intent(inout), allocatable :: sf_int
    allocate (pdf_builtin_t :: sf_int)
  end subroutine pdf_builtin_data_allocate_sf_int

```

Return the numerical PDF set index.

```

<SF pdf builtin: pdf builtin data: TBP>+=
  procedure :: get_pdf_set => pdf_builtin_data_get_pdf_set

<SF pdf builtin: procedures>+=
  function pdf_builtin_data_get_pdf_set (data) result (pdf_set)
    class(pdf_builtin_data_t), intent(in) :: data
    integer :: pdf_set
    pdf_set = data%id
  end function pdf_builtin_data_get_pdf_set

```

15.14.4 The PDF object

The PDF $1 \rightarrow 2$ interaction which describes the splitting of an (anti)proton into a parton and a beam remnant. We stay in the strict forward-splitting limit, but allow some invariant mass for the beam remnant such that the outgoing parton is exactly massless. For a real event, we would replace this by a parton cascade, where the outgoing partons have virtuality as dictated by parton-shower kinematics, and transverse momentum is generated.

The PDF application is a $1 \rightarrow 2$ splitting process, where the particles are ordered as (hadron, remnant, parton).

Polarization is ignored completely. The beam particle is colorless, while partons and beam remnant carry color. The remnant gets a special flavor code.

```

<SF pdf builtin: types>+=
  type, extends (sf_int_t) :: pdf_builtin_t
    type(pdf_builtin_data_t), pointer :: data => null ()
    real(default) :: x = 0
    real(default) :: q = 0
  contains
    <SF pdf builtin: pdf builtin: TBP>
  end type pdf_builtin_t

```

Type string: display the chosen PDF set.

```

<SF pdf builtin: pdf builtin: TBP>=
  procedure :: type_string => pdf_builtin_type_string

<SF pdf builtin: procedures>+=
  function pdf_builtin_type_string (object) result (string)
    class(pdf_builtin_t), intent(in) :: object
    type(string_t) :: string
    if (associated (object%data)) then
      string = "PDF builtin: " // object%data%name
    else
      string = "PDF builtin: [undefined]"
    end if
  end function pdf_builtin_type_string

```

```

end if
end function pdf_builtin_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

⟨SF pdf builtin: pdf builtin: TBP⟩+≡
  procedure :: write => pdf_builtin_write

⟨SF pdf builtin: procedures⟩+≡
  subroutine pdf_builtin_write (object, unit, testflag)
    class(pdf_builtin_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    if (associated (object%data)) then
      call object%data%write (u)
      if (object%status >= SF_DONE_KINEMATICS) then
        write (u, "(1x,A)") "SF parameters:"
        write (u, "(3x,A," // FMT_17 // ")") "x =", object%x
        if (object%status >= SF_FAILED_EVALUATION) then
          write (u, "(3x,A," // FMT_17 // ")") "Q =", object%q
        end if
      end if
    end if
    call object%base_write (u, testflag)
  else
    write (u, "(1x,A)") "PDF builtin data: [undefined]"
  end if
end subroutine pdf_builtin_write

```

Initialize. We know that `data` will be of concrete type `sf_test_data_t`, but we have to cast this explicitly.

For this implementation, we set the incoming and outgoing masses equal to the physical particle mass, but keep the radiated mass zero.

Optionally, we can provide minimum and maximum values for the momentum transfer.

```

⟨SF pdf builtin: pdf builtin: TBP⟩+≡
  procedure :: init => pdf_builtin_init

⟨SF pdf builtin: procedures⟩+≡
  subroutine pdf_builtin_init (sf_int, data)
    class(pdf_builtin_t), intent(out) :: sf_int
    class(sf_data_t), intent(in), target :: data
    type(quantum_numbers_mask_t), dimension(3) :: mask
    type(flavor_t) :: flv, flv_remnant
    type(color_t) :: col0
    type(quantum_numbers_t), dimension(3) :: qn
    integer :: i
    select type (data)
    type is (pdf_builtin_data_t)
      mask = quantum_numbers_mask (.false., .false., .true.)
      call col0%init ()
      call sf_int%base_init (mask, [0._default], [0._default], [0._default])
      sf_int%data => data
    end select
  end subroutine pdf_builtin_init

```



```

do i = -6, 6
  if (data%mask(i)) then
    call qn(1)%init (data%flv_in, col = col0)
    if (i == 0) then
      call flv%init (GLUON, data%model)
      call flv_remnant%init (HADRON_REMNANT_OCTET, data%model)
    else
      call flv%init (i, data%model)
      call flv_remnant%init &
        (sign (HADRON_REMNANT_TRIPLET, -i), data%model)
    end if
    call qn(2)%init ( &
      flv = flv_remnant, col = color_from_flavor (flv_remnant, 1))
    call qn(2)%tag_radiated ()
    call qn(3)%init ( &
      flv = flv, col = color_from_flavor (flv, 1, reverse=.true.))
    call sf_int%add_state (qn)
  end if
end do
if (data%has_photon .and. data%mask_photon) then
  call flv%init (PHOTON, data%model)
  call flv_remnant%init (HADRON_REMNANT_SINGLET, data%model)
  call qn(2)%init (flv = flv_remnant, &
    col = color_from_flavor (flv_remnant, 1))
  call qn(2)%tag_radiated ()
  call qn(3)%init (flv = flv, &
    col = color_from_flavor (flv, 1, reverse = .true.))
  call sf_int%add_state (qn)
end if
call sf_int%freeze ()
call sf_int%set_incoming ([1])
call sf_int%set_radiated ([2])
call sf_int%set_outgoing ([3])
sf_int%status = SF_INITIAL
end select
end subroutine pdf_builtin_init

```

15.14.5 Kinematics

Set kinematics. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ is trivial.

If `map` is set, we are asked to provide an efficient mapping. For the test case, we set $x = r^2$ and consequently $f(r) = 2r$.

<SF pdf builtin: pdf builtin: TBP>+≡

```
procedure :: complete_kinematics => pdf_builtin_complete_kinematics
```

<SF pdf builtin: procedures>+≡

```

subroutine pdf_builtin_complete_kinematics (sf_int, x, f, r, rb, map)
  class(pdf_builtin_t), intent(inout) :: sf_int
  real(default), dimension(:), intent(out) :: x
  real(default), intent(out) :: f
  real(default), dimension(:), intent(in) :: r
  real(default), dimension(:), intent(in) :: rb

```

```

logical, intent(in) :: map
real(default) :: xb1
if (map) then
    call msg_fatal ("PDF builtin: map flag not supported")
else
    x(1) = r(1)
    f = 1
end if
xb1 = 1 - x(1)
call sf_int%split_momentum (x, xb1)
select case (sf_int%status)
case (SF_DONE_KINEMATICS)
    sf_int%x = x(1)
case (SF_FAILED_KINEMATICS)
    sf_int%x = 0
    f = 0
end select
end subroutine pdf_builtin_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

<SF pdf builtin: pdf builtin: TBP>+≡
    procedure :: inverse_kinematics => pdf_builtin_inverse_kinematics

<SF pdf builtin: procedures>+≡
    subroutine pdf_builtin_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
        class(pdf_builtin_t), intent(inout) :: sf_int
        real(default), dimension(:), intent(in) :: x
        real(default), intent(out) :: f
        real(default), dimension(:), intent(out) :: r
        real(default), dimension(:), intent(out) :: rb
        logical, intent(in) :: map
        logical, intent(in), optional :: set_momenta
        real(default) :: xb1
        logical :: set_mom
        set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
        if (map) then
            call msg_fatal ("PDF builtin: map flag not supported")
        else
            r(1) = x(1)
            f = 1
        end if
        xb1 = 1 - x(1)
        rb = 1 - r
        if (set_mom) then
            call sf_int%split_momentum (x, xb1)
            select case (sf_int%status)
            case (SF_DONE_KINEMATICS)
                sf_int%x = x(1)
            case (SF_FAILED_KINEMATICS)
                sf_int%x = 0
                f = 0
            end select
        end if
    end subroutine pdf_builtin_inverse_kinematics

```

```

end if
end subroutine pdf_builtin_inverse_kinematics

```

15.14.6 Structure function

Once the scale is also known, we can actually call the PDF and set the values. Contrary to LHAPDF, the wrapper already takes care of adjusting to the x and Q bounds. Account for the Jacobian.

```

<SF pdf_builtin: pdf_builtin: TBP>+≡
  procedure :: apply => pdf_builtin_apply

<SF pdf_builtin: procedures>+≡
  subroutine pdf_builtin_apply (sf_int, scale)
    class(pdf_builtin_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    real(default), dimension(-6:6) :: ff
    real(double), dimension(-6:6) :: ff_dbl
    real(default) :: x, fph
    real(double) :: xx, qq
    complex(default), dimension(:), allocatable :: fc
    associate (data => sf_int%data)
      sf_int%q = scale
      x = sf_int%x
      xx = x
      qq = scale
      if (data%invert) then
        if (data%has_photon) then
          call pdf_evolve (data%id, x, scale, ff(6:-6:-1), fph)
        else
          if (data%hoppet_b_matching) then
            call hoppet_eval (xx, qq, ff_dbl(6:-6:-1))
            ff = ff_dbl
          else
            call pdf_evolve (data%id, x, scale, ff(6:-6:-1))
          end if
        end if
      else
        if (data%has_photon) then
          call pdf_evolve (data%id, x, scale, ff, fph)
        else
          if (data%hoppet_b_matching) then
            call hoppet_eval (xx, qq, ff_dbl)
            ff = ff_dbl
          else
            call pdf_evolve (data%id, x, scale, ff)
          end if
        end if
      end if
      if (data%has_photon) then
        allocate (fc (count ([data%mask, data%mask_photon])))
        fc = max (pack ([ff, fph], &
          [data%mask, data%mask_photon]), 0._default)
      else

```

```

        allocate (fc (count (data%mask)))
        fc = max (pack (ff, data%mask), 0._default)
    end if
end associate
call sf_int%set_matrix_element (fc)
sf_int%status = SF_EVALUATED
end subroutine pdf_builtin_apply

```

15.14.7 Strong Coupling

Since the PDF codes provide a function for computing the running α_s value, we make this available as an implementation of the abstract `alpha_qcd_t` type, which is used for matrix element evaluation.

```

⟨SF pdf builtin: public⟩+≡
    public :: alpha_qcd_pdf_builtin_t

⟨SF pdf builtin: types⟩+≡
    type, extends (alpha_qcd_t) :: alpha_qcd_pdf_builtin_t
        type(string_t) :: pdfset_name
        integer :: pdfset_id = -1
    contains
        ⟨SF pdf builtin: alpha qcd: TBP⟩
    end type alpha_qcd_pdf_builtin_t

```

Output.

```

⟨SF pdf builtin: alpha qcd: TBP⟩≡
    procedure :: write => alpha_qcd_pdf_builtin_write

⟨SF pdf builtin: procedures⟩+≡
    subroutine alpha_qcd_pdf_builtin_write (object, unit)
        class(alpha_qcd_pdf_builtin_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A)") "QCD parameters (pdf_builtin):"
        write (u, "(5x,A,A)") "PDF set = ", char (object%pdfset_name)
        write (u, "(5x,A,I0)") "PDF ID = ", object%pdfset_id
    end subroutine alpha_qcd_pdf_builtin_write

```

Calculation: the numeric ID selects the correct PDF set, which must be properly initialized.

```

⟨SF pdf builtin: alpha qcd: TBP⟩+≡
    procedure :: get => alpha_qcd_pdf_builtin_get

⟨SF pdf builtin: procedures⟩+≡
    function alpha_qcd_pdf_builtin_get (alpha_qcd, scale) result (alpha)
        class(alpha_qcd_pdf_builtin_t), intent(in) :: alpha_qcd
        real(default), intent(in) :: scale
        real(default) :: alpha
        alpha = pdf_alphas (alpha_qcd%pdfset_id, scale)
    end function alpha_qcd_pdf_builtin_get

```

Initialization. We need to access the global initialization status.

```

<SF pdf builtin: alpha qcd: TBP>+=
  procedure :: init => alpha_qcd_pdf_builtin_init

<SF pdf builtin: procedures>+=
  subroutine alpha_qcd_pdf_builtin_init (alpha_qcd, name, path)
    class(alpha_qcd_pdf_builtin_t), intent(out) :: alpha_qcd
    type(string_t), intent(in) :: name
    type(string_t), intent(in) :: path
    alpha_qcd%pdfset_name = name
    alpha_qcd%pdfset_id = pdf_get_id (name)
    if (alpha_qcd%pdfset_id < 0) &
      call msg_fatal ("QCD parameter initialization: PDF set " &
        // char (name) // " is unknown")
    call pdf_init (alpha_qcd%pdfset_id, path)
  end subroutine alpha_qcd_pdf_builtin_init

```

15.14.8 Unit tests

```

<SF pdf builtin: public>+=
  public :: sf_pdf_builtin_test

<SF pdf builtin: tests>=
  subroutine sf_pdf_builtin_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <SF pdf builtin: execute tests>
  end subroutine sf_pdf_builtin_test

```

Test structure function data

Construct and display a test structure function data object.

```

<SF pdf builtin: execute tests>=
  call test (sf_pdf_builtin_1, "sf_pdf_builtin_1", &
    "structure function configuration", &
    u, results)

<SF pdf builtin: tests>+=
  subroutine sf_pdf_builtin_1 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(pdg_array_t), dimension(1) :: pdg_out
    integer, dimension(:), allocatable :: pdg1
    class(sf_data_t), allocatable :: data
    type(string_t) :: name

    write (u, "(A)")  "* Test output: sf_pdf_builtin_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &test structure function data"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Create empty data object"
write (u, "(A)")

call os_data_init (os_data)

call model%init_sm_test ()
pdg_in = PROTON

allocate (pdf_builtin_data_t :: data)
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize"
write (u, "(A)")

name = "CTEQ6L"

select type (data)
type is (pdf_builtin_data_t)
  call data%init (model, pdg_in, name, &
    os_data%pdf_builtin_datapath)
end select

call data%write (u)

write (u, "(A)")

write (u, "(1x,A)") "Outgoing particle codes:"
call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(2x,99(1x,I0))") pdg1

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_pdf_builtin_1"

end subroutine sf_pdf_builtin_1

```

Test and probe structure function

Construct and display a structure function object based on the PDF builtin structure function.

```

<SF pdf builtin: execute tests>+≡
  call test (sf_pdf_builtin_2, "sf_pdf_builtin_2", &
    "structure function instance", &
    u, results)

<SF pdf builtin: tests>+≡
  subroutine sf_pdf_builtin_2 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data

```

```

type(model_data_t), target :: model
type(flavor_t) :: flv
type(pdg_array_t) :: pdg_in
class(sf_data_t), allocatable, target :: data
class(sf_int_t), allocatable :: sf_int
type(string_t) :: name
type(vector4_t) :: k
type(vector4_t), dimension(2) :: q
real(default) :: E
real(default), dimension(:), allocatable :: r, rb, x
real(default) :: f

write (u, "(A)")  "* Test output: sf_pdf_builtin_2"
write (u, "(A)")  "* Purpose: initialize and fill &
                  &test structure function object"
write (u, "(A)")

write (u, "(A)")  "* Initialize configuration data"
write (u, "(A)")

call os_data_init (os_data)
call model%init_sm_test ()
call flv%init (PROTON, model)
pdg_in = PROTON

call reset_interaction_counter ()

name = "CTEQ6L"

allocate (pdf_builtin_data_t :: data)
select type (data)
type is (pdf_builtin_data_t)
    call data%init (model, pdg_in, name, &
                   os_data%pdf_builtin_datapath)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")

```

```

write (u, "(A)")  "* Set kinematics for x=0.5"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.5_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)

write (u, "(A,9(1x,F10.7))")  "x =", x

write (u, "(A)")
write (u, "(A)")  "* Evaluate for Q = 100 GeV"
write (u, "(A)")

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%apply (scale = 100._default)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_pdf_builtin_2"

end subroutine sf_pdf_builtin_2

```


Strong Coupling

Test α_s as an implementation of the `alpha_qcd_t` abstract type.

```
<SF pdf builtin: execute tests>+≡
  call test (sf_pdf_builtin_3, "sf_pdf_builtin_3", &
    "running alpha_s", &
    u, results)

<SF pdf builtin: tests>+≡
  subroutine sf_pdf_builtin_3 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    type(string_t) :: name

    write (u, "(A)")  "* Test output: sf_pdf_builtin_3"
    write (u, "(A)")  "* Purpose: initialize and evaluate alpha_s"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call os_data_init (os_data)

    name = "CTEQ6L"

    write (u, "(A)")  "* Initialize qcd object"
    write (u, "(A)")

    allocate (alpha_qcd_pdf_builtin_t :: qcd%alpha)
    select type (alpha => qcd%alpha)
    type is (alpha_qcd_pdf_builtin_t)
      call alpha%init (name, os_data%pdf_builtin_datapath)
    end select
    call qcd%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Evaluate for Q = 100"
    write (u, "(A)")

    write (u, "(1x,A,F8.5)")  "alpha = ", qcd%alpha%get (100._default)

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: sf_pdf_builtin_3"

  end subroutine sf_pdf_builtin_3
```

15.15 LHAPDF

Parton distribution functions (PDFs) are available via an interface to the LHAPDF standard library.

15.15.1 The module

```
<sf_lhapdf.f90>≡  
<File header>  
  
module sf_lhapdf  
  
  <Use kinds>  
  <Use strings>  
  use format_defs, only: FMT_17, FMT_19  
  use io_units  
  use unit_tests  
  use system_dependencies, only: LHAPDF_PDFSETS_PATH  
  use system_dependencies, only: LHAPDF5_AVAILABLE  
  use system_dependencies, only: LHAPDF6_AVAILABLE  
  use diagnostics  
  use physics_defs, only: PROTON, PHOTON, PIPLUS, GLUON  
  use physics_defs, only: HADRON_REMNANT_SINGLET  
  use physics_defs, only: HADRON_REMNANT_TRIPLET  
  use physics_defs, only: HADRON_REMNANT_OCTET  
  use lorentz  
  use sm_qcd  
  use pdg_arrays  
  use model_data  
  use flavors  
  use colors  
  use quantum_numbers  
  use state_matrices  
  use polarizations  
  use interactions  
  use sf_aux  
  use sf_base  
  use lhpdf !NODEP!  
  use hoppet_interface  
  
  <Standard module head>  
  
  <SF lhpdf: public>  
  
  <SF lhpdf: types>  
  
  <SF lhpdf: parameters>  
  
  <SF lhpdf: variables>  
  
  <SF lhpdf: interfaces>  
  
contains
```

```
<SF lhpdf: procedures>
```

```
<SF lhpdf: tests>
```

```
end module sf_lhpdf
```

15.15.2 Codes for default PDF sets

The default PDF for protons set is chosen to be CTEQ6ll (LO fit with LO α_s).

```
<SF lhpdf: parameters>≡
```

```
character(*), parameter :: LHAPDF5_DEFAULT_PROTON = "cteq6ll.LHpdf"
character(*), parameter :: LHAPDF5_DEFAULT_PION   = "ABFKWPI.LHgrid"
character(*), parameter :: LHAPDF5_DEFAULT_PHOTON = "GSG960.LHgrid"
character(*), parameter :: LHAPDF6_DEFAULT_PROTON = "CT10"
```

15.15.3 LHAPDF library interface

Here we specify explicit interfaces for all LHAPDF routines that we use below.

```
<SF lhpdf: interfaces>≡
```

```
interface
  subroutine InitPDFsetM (set, file)
    integer, intent(in) :: set
    character(*), intent(in) :: file
  end subroutine InitPDFsetM
end interface
```

```
<SF lhpdf: interfaces>+≡
```

```
interface
  subroutine InitPDFM (set, mem)
    integer, intent(in) :: set, mem
  end subroutine InitPDFM
end interface
```

```
<SF lhpdf: interfaces>+≡
```

```
interface
  subroutine numberPDFM (set, n_members)
    integer, intent(in) :: set
    integer, intent(out) :: n_members
  end subroutine numberPDFM
end interface
```

```
<SF lhpdf: interfaces>+≡
```

```
interface
  subroutine evolvePDFM (set, x, q, ff)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q
    double precision, dimension(-6:6), intent(out) :: ff
  end subroutine evolvePDFM
end interface
```

```

<SF lhpdf: interfaces>+≡
interface
  subroutine evolvePDFphotonM (set, x, q, ff, fphot)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q
    double precision, dimension(-6:6), intent(out) :: ff
    double precision, intent(out) :: fphot
  end subroutine evolvePDFphotonM
end interface

```

```

<SF lhpdf: interfaces>+≡
interface
  subroutine evolvePDFpM (set, x, q, s, scheme, ff)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q, s
    integer, intent(in) :: scheme
    double precision, dimension(-6:6), intent(out) :: ff
  end subroutine evolvePDFpM
end interface

```

```

<SF lhpdf: interfaces>+≡
interface
  subroutine GetXminM (set, mem, xmin)
    integer, intent(in) :: set, mem
    double precision, intent(out) :: xmin
  end subroutine GetXminM
end interface

```

```

<SF lhpdf: interfaces>+≡
interface
  subroutine GetXmaxM (set, mem, xmax)
    integer, intent(in) :: set, mem
    double precision, intent(out) :: xmax
  end subroutine GetXmaxM
end interface

```

```

<SF lhpdf: interfaces>+≡
interface
  subroutine GetQ2minM (set, mem, q2min)
    integer, intent(in) :: set, mem
    double precision, intent(out) :: q2min
  end subroutine GetQ2minM
end interface

```

```

<SF lhpdf: interfaces>+≡
interface
  subroutine GetQ2maxM (set, mem, q2max)
    integer, intent(in) :: set, mem
    double precision, intent(out) :: q2max
  end subroutine GetQ2maxM
end interface

```

```

<SF lhpdf: interfaces>+=
  interface
    function has_photon () result(flag)
      logical :: flag
    end function has_photon
  end interface

```

15.15.4 The LHAPDF status

This type holds the initialization status of the LHAPDF system. Entry 1 is for proton PDFs, entry 2 for pion PDFs, entry 3 for photon PDFs.

Since it is connected to the external LHAPDF library, this is a truly global object. We implement it as a private module variable. To access it from elsewhere, the caller has to create and initialize an object of type `lhpdf_status_t`, which acts as a proxy.

```

<SF lhpdf: types>=
  type :: lhpdf_global_status_t
    private
      logical, dimension(3) :: initialized = .false.
    end type lhpdf_global_status_t

<SF lhpdf: variables>=
  type(lhpdf_global_status_t) :: lhpdf_global_status

<SF lhpdf: procedures>=
  function lhpdf_global_status_is_initialized (set) result (flag)
    logical :: flag
    integer, intent(in), optional :: set
    if (present (set)) then
      select case (set)
        case (1:3);   flag = lhpdf_global_status%initialized(set)
        case default; flag = .false.
      end select
    else
      flag = any (lhpdf_global_status%initialized)
    end if
  end function lhpdf_global_status_is_initialized

<SF lhpdf: procedures>+=
  subroutine lhpdf_global_status_set_initialized (set)
    integer, intent(in) :: set
    lhpdf_global_status%initialized(set) = .true.
  end subroutine lhpdf_global_status_set_initialized

```

This is the only public procedure, it tells the system to forget about previous initialization, allowing for changing the chosen PDF set. Note that such a feature works only if the global program flow is serial, so no two distinct sets are accessed simultaneously. But this applies to LHAPDF anyway.

```

<SF lhpdf: public>=
  public :: lhpdf_global_reset

```

```

<SF lhpdf: procedures>+=
  subroutine lhpdf_global_reset ()
    lhpdf_global_status%initialized = .false.
  end subroutine lhpdf_global_reset

```

15.15.5 LHAPDF initialization

Before using LHAPDF, we have to initialize it with a particular data set and member. This applies not just if we use structure functions, but also if we just use an α_s formula. The integer `set` should be 1 for proton, 2 for pion, and 3 for photon, but this is just convention.

It appears as if LHAPDF does not allow for multiple data sets being used concurrently (?), so multi-threaded usage with different sets (e.g., a scan) is excluded. The current setup with a global flag that indicates initialization is fine as long as Whizard itself is run in serial mode at the Sindarin level. If we introduce multithreading in any form from Sindarin, we have to rethink the implementation of the LHAPDF interface. (The same considerations apply to builtin PDFs.)

If the particular set has already been initialized, do nothing. This implies that whenever we want to change the setup for a particular set, we have to reset the LHAPDF status. `lhpdf_initialize` has an obvious name clash with `lhpdf_init`, the reason it works for `pdf_builtin` is that there things are outsourced to a separate module (inc. `lhpdf_status` etc.).

```

<SF lhpdf: public>+=
  public :: lhpdf_initialize

<SF lhpdf: procedures>+=
  subroutine lhpdf_initialize (set, prefix, file, member, pdf, b_match)
    integer, intent(in) :: set
    type(string_t), intent(inout) :: prefix
    type(string_t), intent(inout) :: file
    type(lhpdf_pdf_t), intent(inout), optional :: pdf
    integer, intent(inout) :: member
    logical, intent(in), optional :: b_match
    if (prefix == "") prefix = LHAPDF_PDFSETS_PATH
    if (LHAPDF5_AVAILABLE) then
      if (lhpdf_global_status_is_initialized (set)) return
      if (file == "") then
        select case (set)
          case (1); file = LHAPDF5_DEFAULT_PROTON
          case (2); file = LHAPDF5_DEFAULT_PION
          case (3); file = LHAPDF5_DEFAULT_PHOTON
        end select
      end if
      if (data_file_exists (prefix // "/" // file)) then
        call InitPDFsetM (set, char (prefix // "/" // file))
      else
        call msg_fatal ("LHAPDF: Data file '" &
          // char (file) // "' not found in '" // char (prefix) // "'.")
        return
      end if
    end if
  end subroutine lhpdf_initialize

```

```

        if (.not. dataset_member_exists (set, member)) then
            call msg_error (" LHAPDF: Chosen member does not exist for set '" &
                // char (file) // "'", using default.")
            member = 0
        end if
        call InitPDFM (set, member)
    else if (LHAPDF6_AVAILABLE) then
!       if (lhpdf_global_status_is_initialized (set) .and. &
!           pdf%is_associated ()) return
        if (file == "") then
            select case (set)
            case (1); file = LHAPDF6_DEFAULT_PROTON
            case (2);
                call msg_fatal ("LHAPDF6: no pion PDFs supported")
            case (3);
                call msg_fatal ("LHAPDF6: no photon PDFs supported")
            end select
        end if
        if (data_file_exists (prefix // "/" // file // "/" // file // ".info")) then
            call pdf%init (char (file), member)
        else
            call msg_fatal ("LHAPDF: Data file '" &
                // char (file) // "' not found in '" // char (prefix) // "'.")
            return
        end if
    end if
    if (present (b_match)) then
        if (b_match) then
            if (LHAPDF5_AVAILABLE) then
                call hoppet_init (.false.)
            else if (LHAPDF6_AVAILABLE) then
                call hoppet_init (.false., pdf)
            end if
        end if
    end if
    call lhpdf_global_status_set_initialized (set)
contains
    function data_file_exists (fq_name) result (exist)
        type(string_t), intent(in) :: fq_name
        logical :: exist
        inquire (file = char(fq_name), exist = exist)
    end function data_file_exists
    function dataset_member_exists (set, member) result (exist)
        integer, intent(in) :: set, member
        logical :: exist
        integer :: n_members
        call numberPDFM (set, n_members)
        exist = member >= 0 .and. member <= n_members
    end function dataset_member_exists
end subroutine lhpdf_initialize

```

15.15.6 Kinematics

Set kinematics. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ is trivial.

If `map` is set, we are asked to provide an efficient mapping. For the test case, we set $x = r^2$ and consequently $f(r) = 2r$.

```

<SF lhpdf: lhpdf: TBP>≡
  procedure :: complete_kinematics => lhpdf_complete_kinematics

<SF lhpdf: procedures>+≡
  subroutine lhpdf_complete_kinematics (sf_int, x, f, r, rb, map)
    class(lhpdf_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: r
    real(default), dimension(:), intent(in) :: rb
    logical, intent(in) :: map
    real(default) :: xb1
    if (map) then
      call msg_fatal ("LHAPDF: map flag not supported")
    else
      x(1) = r(1)
      f = 1
    end if
    xb1 = 1 - x(1)
    call sf_int%split_momentum (x, xb1)
    select case (sf_int%status)
    case (SF_DONE_KINEMATICS)
      sf_int%x = x(1)
    case (SF_FAILED_KINEMATICS)
      sf_int%x = 0
      f = 0
    end select
  end subroutine lhpdf_complete_kinematics

```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```

<SF lhpdf: lhpdf: TBP>+≡
  procedure :: inverse_kinematics => lhpdf_inverse_kinematics

<SF lhpdf: procedures>+≡
  subroutine lhpdf_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
    class(lhpdf_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    real(default) :: xb1
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    if (map) then

```



```

        call msg_fatal ("LHAPDF: map flag not supported")
    else
        r(1) = x(1)
        f = 1
    end if
    xb1 = 1 - x(1)
    rb = 1 - r
    if (set_mom) then
        call sf_int%split_momentum (x, xb1)
        select case (sf_int%status)
        case (SF_DONE_KINEMATICS)
            sf_int%x = x(1)
        case (SF_FAILED_KINEMATICS)
            sf_int%x = 0
            f = 0
        end select
    end if
end subroutine lhpdf_inverse_kinematics

```

15.15.7 The LHAPDF data block

The data block holds the incoming flavor (which has to be proton, pion, or photon), the corresponding pointer to the global access data (1, 2, or 3), the flag `invert` which is set for an antiproton, the bounds as returned by LHAPDF for the specified set, and a mask that determines which partons will be actually in use.

```

<SF lhpdf: public>+≡
    public :: lhpdf_data_t

<SF lhpdf: types>+≡
    type, extends (sf_data_t) :: lhpdf_data_t
    private
    type(string_t) :: prefix
    type(string_t) :: file
    type(lhpdf_pdf_t) :: pdf
    integer :: member = 0
    class(model_data_t), pointer :: model => null ()
    type(flavor_t) :: flv_in
    integer :: set = 0
    logical :: invert = .false.
    logical :: photon = .false.
    logical :: has_photon = .false.
    integer :: photon_scheme = 0
    real(default) :: xmin = 0, xmax = 0
    real(default) :: qmin = 0, qmax = 0
    logical, dimension(-6:6) :: mask = .true.
    logical :: mask_photon = .true.
    logical :: hoppet_b_matching = .false.
    contains
    <SF lhpdf: lhpdf data: TBP>
end type lhpdf_data_t

```

Generate PDF data. This is provided as a function, but it has the side-effect of initializing the requested PDF set. A finalizer is not needed.

The library uses double precision, so since the default precision may be extended or quadruple, we use auxiliary variables for type casting.

```

<SF lhpdf: lhpdf data: TBP>≡
  procedure :: init => lhpdf_data_init

<SF lhpdf: procedures>+≡
  subroutine lhpdf_data_init &
    (data, model, pdg_in, prefix, file, member, photon_scheme, &
     hoppet_b_matching)
    class(lhpdf_data_t), intent(out) :: data
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t), intent(in) :: pdg_in
    type(string_t), intent(in), optional :: prefix, file
    integer, intent(in), optional :: member
    integer, intent(in), optional :: photon_scheme
    logical, intent(in), optional :: hoppet_b_matching
    double precision :: xmin, xmax, q2min, q2max
    external :: InitPDFsetM, InitPDFM, numberPDFM
    external :: GetXminM, GetXmaxM, GetQ2minM, GetQ2maxM
    if (.not. LHAPDF5_AVAILABLE .and. .not. LHAPDF6_AVAILABLE) then
      call msg_fatal ("LHAPDF requested but library is not linked")
      return
    end if
    data%model => model
    if (pdg_array_get_length (pdg_in) /= 1) &
      call msg_fatal ("PDF: incoming particle must be unique")
    call data%flv_in%init (pdg_array_get (pdg_in, 1), model)
    select case (pdg_array_get (pdg_in, 1))
    case (PROTON)
      data%set = 1
    case (-PROTON)
      data%set = 1
      data%invert = .true.
    case (PIPLUS)
      data%set = 2
    case (-PIPLUS)
      data%set = 2
      data%invert = .true.
    case (PHOTON)
      data%set = 3
      data%photon = .true.
      if (present (photon_scheme)) data%photon_scheme = photon_scheme
    case default
      call msg_fatal (" LHAPDF: " &
        // "incoming particle must be (anti)proton, pion, or photon.")
      return
    end select
    if (present (prefix)) then
      data%prefix = prefix
    else
      data%prefix = ""
    end if
  end subroutine

```

```

if (present (file)) then
  data%file = file
else
  data%file = ""
end if
if (present (hoppet_b_matching)) data%hoppet_b_matching = hoppet_b_matching
if (LHAPDF5_AVAILABLE) then
  call lhpdf_initialize &
    (data%set, data%prefix, data%file, data%member, &
     b_match = data%hoppet_b_matching)
  call GetXminM (data%set, data%member, xmin)
  call GetXmaxM (data%set, data%member, xmax)
  call GetQ2minM (data%set, data%member, q2min)
  call GetQ2maxM (data%set, data%member, q2max)
  data%xmin = xmin
  data%xmax = xmax
  data%qmin = sqrt (q2min)
  data%qmax = sqrt (q2max)
  data%has_photon = has_photon ()
else if (LHAPDF6_AVAILABLE) then
  call lhpdf_initialize &
    (data%set, data%prefix, data%file, data%member, &
     data%pdf, data%hoppet_b_matching)
  data%xmin = data%pdf%getxmin ()
  data%xmax = data%pdf%getxmax ()
  data%qmin = sqrt(data%pdf%getq2min ())
  data%qmax = sqrt(data%pdf%getq2max ())
  data%has_photon = data%pdf%has_photon ()
end if
end subroutine lhpdf_data_init

```

Enable/disable partons explicitly. If a mask entry is true, applying the PDF will generate the corresponding flavor on output.

```

<LHAPDF: lhpdf data: TBP>≡
  procedure :: set_mask => lhpdf_data_set_mask

<LHAPDF: procedures>≡
  subroutine lhpdf_data_set_mask (data, mask)
    class(lhpdf_data_t), intent(inout) :: data
    logical, dimension(-6:6), intent(in) :: mask
    data%mask = mask
  end subroutine lhpdf_data_set_mask

```

Return the public part of the data set.

```

<LHAPDF: public>≡
  public :: lhpdf_data_get_public_info

<LHAPDF: procedures>+≡
  subroutine lhpdf_data_get_public_info &
    (data, lhpdf_dir, lhpdf_file, lhpdf_member)
    type(lhpdf_data_t), intent(in) :: data
    type(string_t), intent(out) :: lhpdf_dir, lhpdf_file
    integer, intent(out) :: lhpdf_member
    lhpdf_dir = data%prefix

```

```

    lhapdf_file = data%file
    lhapdf_member = data%member
end subroutine lhapdf_data_get_public_info

```

Return the number of the member of the data set.

```

<LHAPDF: public>+≡
    public :: lhapdf_data_get_set

<LHAPDF: procedures>+≡
    function lhapdf_data_get_set(data) result(set)
        type(lhapdf_data_t), intent(in) :: data
        integer :: set
        set = data%set
    end function lhapdf_data_get_set

```

Output

```

<SF lhapdf: lhapdf data: TBP>+≡
    procedure :: write => lhapdf_data_write

<SF lhapdf: procedures>+≡
    subroutine lhapdf_data_write (data, unit, verbose)
        class(lhapdf_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        logical :: verb
        integer :: u
        if (present (verbose)) then
            verb = verbose
        else
            verb = .false.
        end if
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,A)") "LHAPDF data:"
        if (data%set /= 0) then
            write (u, "(3x,A)", advance="no") "flavor          = "
            call data%flv_in%write (u); write (u, *)
            if (verb) then
                write (u, "(3x,A,A)")          " prefix          = ", char (data%prefix)
            else
                write (u, "(3x,A,A)")          " prefix          = ", &
                    " <empty (non-verbose version)>"
            end if
            write (u, "(3x,A,A)")          " file              = ", char (data%file)
            write (u, "(3x,A,I3)")          " member             = ", data%member
            write (u, "(3x,A," // FMT_19 // ")") " x(min)             = ", data%xmin
            write (u, "(3x,A," // FMT_19 // ")") " x(max)             = ", data%xmax
            write (u, "(3x,A," // FMT_19 // ")") " Q(min)             = ", data%qmin
            write (u, "(3x,A," // FMT_19 // ")") " Q(max)             = ", data%qmax
            write (u, "(3x,A,L1)")          " invert             = ", data%invert
            if (data%photon) write (u, "(3x,A,I3)") &
                " IP2 (scheme) = ", data%photon_scheme
            write (u, "(3x,A,6(1x,L1),1x,A,1x,L1,1x,A,6(1x,L1))") &
                " mask              = ", &
                data%mask(-6:-1), " ", data%mask(0), " ", data%mask(1:6)
        end if
    end subroutine lhapdf_data_write

```

```

        write (u, "(3x,A,L1)" " photon mask = ", data%mask_photon
    if (data%set == 1) write (u, "(3x,A,L1)" &
        " hoppet_b      = ", data%hoppet_b_matching
    else
        write (u, "(3x,A)" "[undefined]"
    end if
end subroutine lhpdf_data_write

```

The number of parameters is one. We do not generate transverse momentum.

```

<SF lhpdf: lhpdf data: TBP>+≡
    procedure :: get_n_par => lhpdf_data_get_n_par

<SF lhpdf: procedures>+≡
    function lhpdf_data_get_n_par (data) result (n)
        class(lhpdf_data_t), intent(in) :: data
        integer :: n
        n = 1
    end function lhpdf_data_get_n_par

```

Return the outgoing particle PDG codes. This is based on the mask.

```

<SF lhpdf: lhpdf data: TBP>+≡
    procedure :: get_pdg_out => lhpdf_data_get_pdg_out

<SF lhpdf: procedures>+≡
    subroutine lhpdf_data_get_pdg_out (data, pdg_out)
        class(lhpdf_data_t), intent(in) :: data
        type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
        integer, dimension(:), allocatable :: pdg1
        integer :: n, np, i
        n = count (data%mask)
        np = 0; if (data%has_photon .and. data%mask_photon) np = 1
        allocate (pdg1 (n + np))
        pdg1(1:n) = pack ([i, i = -6, 6], data%mask)
        if (np == 1) pdg1(n+np) = PHOTON
        pdg_out(1) = pdg1
    end subroutine lhpdf_data_get_pdg_out

```

Allocate the interaction record.

```

<SF lhpdf: lhpdf data: TBP>+≡
    procedure :: allocate_sf_int => lhpdf_data_allocate_sf_int

<SF lhpdf: procedures>+≡
    subroutine lhpdf_data_allocate_sf_int (data, sf_int)
        class(lhpdf_data_t), intent(in) :: data
        class(sf_int_t), intent(inout), allocatable :: sf_int
        allocate (lhpdf_t :: sf_int)
    end subroutine lhpdf_data_allocate_sf_int

```

Return the numerical PDF set index.

```

<SF lhpdf: lhpdf data: TBP>+≡
    procedure :: get_pdf_set => lhpdf_data_get_pdf_set

```

```

<SF lhpdf: procedures>+≡
function lhpdf_data_get_pdf_set (data) result (pdf_set)
  class(lhpdf_data_t), intent(in) :: data
  integer :: pdf_set
  pdf_set = data%set
end function lhpdf_data_get_pdf_set

```

15.15.8 The LHAPDF object

The `lhpdf_t` data type is a $1 \rightarrow 2$ interaction which describes the splitting of an (anti)proton into a parton and a beam remnant. We stay in the strict forward-splitting limit, but allow some invariant mass for the beam remnant such that the outgoing parton is exactly massless. For a real event, we would replace this by a parton cascade, where the outgoing partons have virtuality as dictated by parton-shower kinematics, and transverse momentum is generated.

This is the LHAPDF object which holds input data together with the interaction. We also store the x momentum fraction and the scale, since kinematics and function value are requested at different times.

The PDF application is a $1 \rightarrow 2$ splitting process, where the particles are ordered as (hadron, remnant, parton).

Polarization is ignored completely. The beam particle is colorless, while partons and beam remnant carry color. The remnant gets a special flavor code.

```

<SF lhpdf: types>+≡
type, extends (sf_int_t) :: lhpdf_t
  type(lhpdf_data_t), pointer :: data => null ()
  real(default) :: x = 0
  real(default) :: q = 0
  real(default) :: s = 0
  contains
  <SF lhpdf: lhpdf: TBP>
end type lhpdf_t

```

Type string: display the chosen PDF set.

```

<SF lhpdf: lhpdf: TBP>+≡
procedure :: type_string => lhpdf_type_string

<SF lhpdf: procedures>+≡
function lhpdf_type_string (object) result (string)
  class(lhpdf_t), intent(in) :: object
  type(string_t) :: string
  if (associated (object%data)) then
    string = "LHAPDF: " // object%data%file
  else
    string = "LHAPDF: [undefined]"
  end if
end function lhpdf_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF lhpdf: lhpdf: TBP>+≡
procedure :: write => lhpdf_write

```

```

<SF lhpdf: procedures>+=
subroutine lhpdf_write (object, unit, testflag)
  class(lhpdf_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag
  integer :: u
  u = given_output_unit (unit)
  if (associated (object%data)) then
    call object%data%write (u)
    if (object%status >= SF_DONE_KINEMATICS) then
      write (u, "(1x,A)") "SF parameters:"
      write (u, "(3x,A," // FMT_17 // ")") "x =", object%x
      if (object%status >= SF_FAILED_EVALUATION) then
        write (u, "(3x,A," // FMT_17 // ")") "Q =", object%q
      end if
    end if
    call object%base_write (u, testflag)
  else
    write (u, "(1x,A)") "LHAPDF data: [undefined]"
  end if
end subroutine lhpdf_write

```

Initialize. We know that `data` will be of concrete type `sf_lhpdf_data_t`, but we have to cast this explicitly.

For this implementation, we set the incoming and outgoing masses equal to the physical particle mass, but keep the radiated mass zero.

```

<SF lhpdf: lhpdf: TBP>+=
  procedure :: init => lhpdf_init

<SF lhpdf: procedures>+=
subroutine lhpdf_init (sf_int, data)
  class(lhpdf_t), intent(out) :: sf_int
  class(sf_data_t), intent(in), target :: data
  type(quantum_numbers_mask_t), dimension(3) :: mask
  type(flavor_t) :: flv, flv_remnant
  type(color_t) :: col0
  type(quantum_numbers_t), dimension(3) :: qn
  integer :: i
  select type (data)
  type is (lhpdf_data_t)
    mask = quantum_numbers_mask (.false., .false., .true.)
    call col0%init ()
    call sf_int%base_init (mask, [0._default], [0._default], [0._default])
    sf_int%data => data
    do i = -6, 6
      if (data%mask(i)) then
        call qn(1)%init (data%flv_in, col = col0)
        if (i == 0) then
          call flv%init (GLUON, data%model)
          call flv_remnant%init (HADRON_REMNANT_OCTET, data%model)
        else
          call flv%init (i, data%model)
          call flv_remnant%init &
            (sign (HADRON_REMNANT_TRIPLET, -i), data%model)
        end if
      end if
    end do
  end select
end subroutine lhpdf_init

```

```

        end if
        call qn(2)%init ( &
            flv = flv_remnant, col = color_from_flavor (flv_remnant, 1))
        call qn(2)%tag_radiated ()
        call qn(3)%init ( &
            flv = flv, col = color_from_flavor (flv, 1, reverse=.true.))
        call sf_int%add_state (qn)
    end if
end do
if (data%has_photon .and. data%mask_photon) then
    call flv%init (PHOTON, data%model)
    call flv_remnant%init (HADRON_REMNANT_SINGLET, data%model)
    call qn(2)%init (flv = flv_remnant, &
        col = color_from_flavor (flv_remnant, 1))
    call qn(2)%tag_radiated ()
    call qn(3)%init (flv = flv, &
        col = color_from_flavor (flv, 1, reverse=.true.))
    call sf_int%add_state (qn)
end if
call sf_int%freeze ()
call sf_int%set_incoming ([1])
call sf_int%set_radiated ([2])
call sf_int%set_outgoing ([3])
sf_int%status = SF_INITIAL
end select
end subroutine lhpdf_init

```

15.15.9 Structure function

We have to cast the LHAPDF arguments to/from double precision (possibly from/to extended/quadruple precision), if necessary. Furthermore, some structure functions can yield negative results (sea quarks close to $x = 1$). We set these unphysical values to zero.

```

<SF lhpdf: lhpdf: TBP>+=
    procedure :: apply => lhpdf_apply

<SF lhpdf: procedures>+=
    subroutine lhpdf_apply (sf_int, scale)
        class(lhpdf_t), intent(inout) :: sf_int
        real(default), intent(in) :: scale
        real(default) :: x, s
        double precision :: xx, qq, ss
        double precision, dimension(-6:6) :: ff
        double precision :: fphot
        complex(default), dimension(:), allocatable :: fc
        external :: evolvePDFM, evolvePDFpM
        associate (data => sf_int%data)
            sf_int%q = scale
            x = sf_int%x
            s = sf_int%s
            qq = min (data% qmax, scale)
            qq = max (data% qmin, qq)
            if (.not. data% photon) then

```



```

xx = x
if (data% invert) then
  if (data%has_photon) then
    if (LHAPDF5_AVAILABLE) then
      call evolvePDFphotonM &
        (data% set, xx, qq, ff(6:-6:-1), fphot)
    else if (LHAPDF6_AVAILABLE) then
      call data%pdf%evolve_pdfphotonm &
        (xx, qq, ff(6:-6:-1), fphot)
    end if
  else
    if (data%hoppet_b_matching) then
      call hoppet_eval (xx, qq, ff(6:-6:-1))
    else
      if (LHAPDF5_AVAILABLE) then
        call evolvePDFM (data% set, xx, qq, ff(6:-6:-1))
      else if (LHAPDF6_AVAILABLE) then
        call data%pdf%evolve_pdfm (xx, qq, ff(6:-6:-1))
      end if
    end if
  end if
else
  if (data%has_photon) then
    if (LHAPDF5_AVAILABLE) then
      call evolvePDFphotonM (data% set, xx, qq, ff, fphot)
    else if (LHAPDF6_AVAILABLE) then
      call data%pdf%evolve_pdfphotonm (xx, qq, ff, fphot)
    end if
  else
    if (data%hoppet_b_matching) then
      call hoppet_eval (xx, qq, ff)
    else
      if (LHAPDF5_AVAILABLE) then
        call evolvePDFM (data% set, xx, qq, ff)
      else if (LHAPDF6_AVAILABLE) then
        call data%pdf%evolve_pdfm (xx, qq, ff)
      end if
    end if
  end if
end if
else
  ss = s
  if (LHAPDF5_AVAILABLE) then
    call evolvePDFpM (data% set, xx, qq, &
      ss, data% photon_scheme, ff)
  else if (LHAPDF6_AVAILABLE) then
    call data%pdf%evolve_pdfpm (xx, qq, ss, &
      data%photon_scheme, ff)
  end if
end if
if (data%has_photon) then
  allocate (fc (count ([data%mask, data%mask_photon])))
  fc = max (pack ([ff, fphot] / x, &
    [data% mask, data%mask_photon]), 0._default)

```

```

        else
            allocate (fc (count (data%mask)))
            fc = max (pack (ff / x, data%mask), 0._default)
        end if
    end associate
    call sf_int%set_matrix_element (fc)
    sf_int%status = SF_EVALUATED
end subroutine lhpdf_apply

```

15.15.10 Strong Coupling

Since the PDF codes provide a function for computing the running α_s value, we make this available as an implementation of the abstract `alpha_qcd_t` type, which is used for matrix element evaluation.

```

<SF lhpdf: public>+≡
    public :: alpha_qcd_lhpdf_t

<SF lhpdf: types>+≡
    type, extends (alpha_qcd_t) :: alpha_qcd_lhpdf_t
        type(string_t) :: pdfset_dir
        type(string_t) :: pdfset_file
        integer :: pdfset_member = -1
        type(lhpdf_pdf_t) :: pdf
    contains
        <SF lhpdf: alpha_qcd: TBP>
    end type alpha_qcd_lhpdf_t

```

Output. As in earlier versions we leave the LHAPDF path out.

```

<SF lhpdf: alpha_qcd: TBP>≡
    procedure :: write => alpha_qcd_lhpdf_write

<SF lhpdf: procedures>+≡
    subroutine alpha_qcd_lhpdf_write (object, unit)
        class(alpha_qcd_lhpdf_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A)") "QCD parameters (lhpdf):"
        write (u, "(5x,A,A)") "PDF set      = ", char (object%pdfset_file)
        write (u, "(5x,A,I0)") "PDF member = ", object%pdfset_member
    end subroutine alpha_qcd_lhpdf_write

```

Calculation: the numeric member ID selects the correct PDF set, which must be properly initialized.

```

<SF lhpdf: interfaces>+≡
    interface
        double precision function alphasPDF (Q)
            double precision, intent(in) :: Q
        end function alphasPDF
    end interface

```

```

<SF lhpdf: alpha_qcd: TBP>+=
  procedure :: get => alpha_qcd_lhapdf_get

<SF lhpdf: procedures>+=
  function alpha_qcd_lhapdf_get (alpha_qcd, scale) result (alpha)
    class(alpha_qcd_lhapdf_t), intent(in) :: alpha_qcd
    real(default), intent(in) :: scale
    real(default) :: alpha
    if (LHAPDF5_AVAILABLE) then
      alpha = alphasPDF (dble (scale))
    else if (LHAPDF6_AVAILABLE) then
      alpha = alpha_qcd%pdf%alphas_pdf (dble (scale))
    end if
  end function alpha_qcd_lhapdf_get

```

Initialization. We need to access the (quasi-global) initialization status.

```

<SF lhpdf: alpha_qcd: TBP>+=
  procedure :: init => alpha_qcd_lhapdf_init

<SF lhpdf: procedures>+=
  subroutine alpha_qcd_lhapdf_init (alpha_qcd, file, member, path)
    class(alpha_qcd_lhapdf_t), intent(out) :: alpha_qcd
    type(string_t), intent(inout) :: file
    integer, intent(inout) :: member
    type(string_t), intent(inout) :: path
    alpha_qcd%pdfset_file = file
    alpha_qcd%pdfset_member = member
    if (alpha_qcd%pdfset_member < 0) &
      call msg_fatal ("QCD parameter initialization: PDF set " &
        // char (file) // " is unknown")
    if (LHAPDF5_AVAILABLE) then
      call lhpdf_initialize (1, path, file, member)
    else if (LHAPDF6_AVAILABLE) then
      call lhpdf_initialize &
        (1, path, file, member, alpha_qcd%pdf)
    end if
  end subroutine alpha_qcd_lhapdf_init

```

15.15.11 Unit tests

```

<SF lhpdf: public>+=
  public :: sf_lhapdf_test

<SF lhpdf: tests>=
  subroutine sf_lhapdf_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <SF lhpdf: execute tests>
  end subroutine sf_lhapdf_test

```

Test structure function data

Construct and display a test structure function data object.

```
<SF lhpdf: execute tests>≡
  if (LHAPDF5_AVAILABLE) then
    call test (sf_lhapdf_1, "sf_lhapdf5_1", &
      "structure function configuration", &
      u, results)
  else if (LHAPDF6_AVAILABLE) then
    call test (sf_lhapdf_1, "sf_lhapdf6_1", &
      "structure function configuration", &
      u, results)
  end if

<SF lhpdf: tests>+≡
  subroutine sf_lhapdf_1 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(pdg_array_t) :: pdg_in
    type(pdg_array_t), dimension(1) :: pdg_out
    integer, dimension(:), allocatable :: pdg1
    class(sf_data_t), allocatable :: data

    write (u, "(A)")  "* Test output: sf_lhapdf_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &test structure function data"
    write (u, "(A)")

    write (u, "(A)")  "* Create empty data object"
    write (u, "(A)")

    call model%init_sm_test ()
    pdg_in = PROTON

    allocate (lhpdf_data_t :: data)
    call data%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize"
    write (u, "(A)")

    select type (data)
    type is (lhpdf_data_t)
      call data%init (model, pdg_in)
    end select

    call data%write (u)

    write (u, "(A)")

    write (u, "(1x,A)") "Outgoing particle codes:"
    call data%get_pdg_out (pdg_out)
    pdg1 = pdg_out(1)
    write (u, "(2x,99(1x,I0))") pdg1
```

```

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_lhapdf_1"

end subroutine sf_lhapdf_1

```

Test and probe structure function

Construct and display a structure function object based on the PDF builtin structure function.

```

<SF lhpdf: execute tests>+≡
  if (LHAPDF5_AVAILABLE) then
    call test (sf_lhapdf_2, "sf_lhapdf5_2", &
      "structure function instance", &
      u, results)
  else if (LHAPDF6_AVAILABLE) then
    call test (sf_lhapdf_2, "sf_lhapdf6_2", &
      "structure function instance", &
      u, results)
  end if

<SF lhpdf: tests>+≡
  subroutine sf_lhapdf_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(pdg_array_t) :: pdg_in
    class(sf_data_t), allocatable, target :: data
    class(sf_int_t), allocatable :: sf_int
    type(vector4_t) :: k
    type(vector4_t), dimension(2) :: q
    real(default) :: E
    real(default), dimension(:), allocatable :: r, rb, x
    real(default) :: f

    write (u, "(A)")  "* Test output: sf_lhapdf_2"
    write (u, "(A)")  "* Purpose: initialize and fill &
      &test structure function object"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call model%init_sm_test ()
    call flv%init (PROTON, model)
    pdg_in = PROTON
    call lhpdf_global_reset ()

    call reset_interaction_counter ()

    allocate (lhpdf_data_t :: data)
    select type (data)

```

```

type is (lhpdf_data_t)
    call data%init (model, pdg_in)
end select

write (u, "(A)")  "* Initialize structure-function object"
write (u, "(A)")

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

call sf_int%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize incoming momentum with E=500"
write (u, "(A)")
E = 500
k = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
call vector4_write (k, u)
call sf_int%seed_kinematics ([k])

write (u, "(A)")
write (u, "(A)")  "* Set kinematics for x=0.5"
write (u, "(A)")

allocate (r (data%get_n_par ()))
allocate (rb(size (r)))
allocate (x (size (r)))

r = 0.5_default
rb = 1 - r
call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%write (u)

write (u, "(A)")
write (u, "(A,9(1x,F10.7))")  "x =", x
write (u, "(A,9(1x,F10.7))")  "f =", f

write (u, "(A)")
write (u, "(A)")  "* Recover x from momenta"
write (u, "(A)")

q = sf_int%get_momenta (outgoing=.true.)
call sf_int%final ()
deallocate (sf_int)

call data%allocate_sf_int (sf_int)
call sf_int%init (data)
call sf_int%set_beam_index ([1])

call sf_int%seed_kinematics ([k])
call sf_int%set_momenta (q, outgoing=.true.)
call sf_int%recover_x (x)

```

```

write (u, "(A,9(1x,F10.7))") "x =", x

write (u, "(A)")
write (u, "(A)")  "* Evaluate for Q = 100 GeV"
write (u, "(A)")

call sf_int%complete_kinematics (x, f, r, rb, map=.false.)
call sf_int%apply (scale = 100._default)
call sf_int%write (u, testflag = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call sf_int%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: sf_lhapdf_2"

end subroutine sf_lhapdf_2

```

Strong Coupling

Test α_s as an implementation of the `alpha_qcd_t` abstract type.

```

<SF lhpdf: execute tests>+≡
  if (LHAPDF5_AVAILABLE) then
    call test (sf_lhapdf_3, "sf_lhapdf5_3", &
      "running alpha_s", &
      u, results)
  else if (LHAPDF6_AVAILABLE) then
    call test (sf_lhapdf_3, "sf_lhapdf6_3", &
      "running alpha_s", &
      u, results)
  end if

<SF lhpdf: tests>+≡
  subroutine sf_lhapdf_3 (u)
    integer, intent(in) :: u
    type(qcd_t) :: qcd
    type(string_t) :: name, path
    integer :: member

    write (u, "(A)")  "* Test output: sf_lhapdf_3"
    write (u, "(A)")  "* Purpose: initialize and evaluate alpha_s"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize configuration data"
    write (u, "(A)")

    call lhpdf_global_reset ()

    if (LHAPDF5_AVAILABLE) then

```

```

        name = "cteq6l1.LHpdf"
        member = 1
        path = ""
    else if (LHAPDF6_AVAILABLE) then
        name = "CT10"
        member = 1
        path = ""
    end if

    write (u, "(A)")  "* Initialize qcd object"
    write (u, "(A)")

    allocate (alpha_qcd_lhapdf_t :: qcd%alpha)
    select type (alpha => qcd%alpha)
    type is (alpha_qcd_lhapdf_t)
        call alpha%init (name, member, path)
    end select
    call qcd%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Evaluate for Q = 100"
    write (u, "(A)")

    write (u, "(1x,A,F8.5)")  "alpha = ", qcd%alpha%get (100._default)

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: sf_lhapdf_3"

end subroutine sf_lhapdf_3

```


Chapter 16

Interface for Matrix Element Objects

These modules manage internal and, in particular, external matrix-element code.

prc_core We define the abstract `prc_core_t` type which handles all specific features of kinematics matrix-element evaluation that depend on a particular class of processes. This abstract type supplements the `prc_core_def_t` type and related types in another module. Together, they provide a complete set of matrix-element handlers that are implemented in the concrete types below.

These are the implementations:

prc_template_me Implements matrix-element code without actual content (trivial value), but full-fledged interface. This can be used for injecting user-defined matrix-element code.

prc_omega Matrix elements calculated by `O'MEGA` are the default for WHIZARD. Here, we provide all necessary support.

16.1 Abstract process core

In this module we provide abstract data types for process classes. Each process class represents a set of processes which are handled by a common “method”, e.g., by the `O'MEGA` matrix-element generator. The process class is also able to select a particular implementation for the phase-space and integration modules.

For a complete implementation of a process class, we have to provide extensions of the following abstract types:

prc_core_def_t process and matrix-element configuration

prc_writer_t (optional) writing external matrix-element code

prc_driver_t accessing the matrix element (internal or external)

prc_core_t evaluating kinematics and matrix element. The process core also selects phase-space and integrator implementations as appropriate for the process class and configuration.

In the actual process-handling data structures, each process component contains an instance of such a process class as its core. This allows us to keep the **processes** module below, which supervises matrix-element evaluation, integration, and event generation, free of any reference to concrete implementations (for the process class, phase space, and integrator).

There are no unit tests, these are deferred to the **processes** module.

```

<prc_core.f90>≡
  <File header>
  module prc_core

    <Use kinds>
    <Use strings>
    use io_units
    use diagnostics
    use os_interface
    use lorentz
    use model_data
    use model_testbed
    use interactions

    use process_constants
    use prc_core_def
    use process_libraries
    use sf_base

    <Standard module head>

    <Prc core: public>

    <Prc core: types>

    <Prc core: variables>

    <Prc core: interfaces>

    contains

    <Prc core: procedures>

  end module prc_core

```

16.1.1 The process core

The process core is of abstract data type. Different types of matrix element will be represented by different implementations.

```

<Prc core: public>≡
  public :: prc_core_t

```

```

<Prc core: types>≡
  type, abstract :: prc_core_t
    class(prc_core_def_t), pointer :: def => null ()
    logical :: data_known = .false.
    type(process_constants_t) :: data
    class(prc_core_driver_t), allocatable :: driver
    logical :: use_color_factors = .false.
    integer :: nc = 3
  contains
    <Prc core: process core: TBP>
  end type prc_core_t

```

In any case there must be an output routine.

```

<Prc core: process core: TBP>≡
  procedure(prc_core_write), deferred :: write

<Prc core: interfaces>≡
  abstract interface
    subroutine prc_core_write (object, unit)
      import
      class(prc_core_t), intent(in) :: object
      integer, intent(in), optional :: unit
    end subroutine prc_core_write
  end interface

```

For initialization, we assign a pointer to the process entry in the relevant library. This allows us to access all process functions via the implementation of `prc_core_t`.

We declare the `object` as `intent(inout)`, since just after allocation it may be useful to store some extra data in the object, which we can then use in the actual initialization. This applies to extensions of `prc_core` which override the `init` method.

```

<Prc core: process core: TBP>+≡
  procedure :: init => prc_core_init
  procedure :: base_init => prc_core_init

<Prc core: procedures>≡
  subroutine prc_core_init (object, def, lib, id, i_component)
    class(prc_core_t), intent(inout) :: object
    class(prc_core_def_t), intent(in), target :: def
    type(process_library_t), intent(in), target :: lib
    type(string_t), intent(in) :: id
    integer, intent(in) :: i_component
    object%def => def
    call lib%connect_process (id, i_component, object%data, object%driver)
    object%data_known = .true.
  end subroutine prc_core_init

```

Return true if the matrix element generation was successful. This can be tested by looking at the number of generated flavor states, which should be nonzero.

```

<Prc core: process core: TBP>+≡
  procedure :: has_matrix_element => prc_core_has_matrix_element

```

```

<Prc core: procedures>+≡
function prc_core_has_matrix_element (object) result (flag)
  class(prc_core_t), intent(in) :: object
  logical :: flag
  flag = object%data%n_flg /= 0
end function prc_core_has_matrix_element

```

Return true if a MC dataset should be attached to this process component.
False if it shares the dataset with another component.

```

<Prc core: process core: TBP>+≡
  procedure(prc_core_get_flag), deferred :: needs_mcset

```

```

<Prc core: interfaces>+≡
abstract interface
  function prc_core_get_flag (object) result (flag)
    import
    class(prc_core_t), intent(in) :: object
    logical :: flag
  end function prc_core_get_flag
end interface

```

Return an integer number

```

<Prc core: interfaces>+≡
abstract interface
  function prc_core_get_integer (object) result (i)
    import
    class(prc_core_t), intent(in) :: object
    integer :: i
  end function prc_core_get_integer
end interface

```

Return the number of distinct terms requested by this process component.

```

<Prc core: process core: TBP>+≡
  procedure(prc_core_get_integer), deferred :: get_n_terms

```

Tell whether a particular combination of flavor/helicity/color state is allowed for the matrix element.

```

<Prc core: process core: TBP>+≡
  procedure(prc_core_is_allowed), deferred :: is_allowed

```

```

<Prc core: interfaces>+≡
abstract interface
  function prc_core_is_allowed (object, i_term, f, h, c) result (flag)
    import
    class(prc_core_t), intent(in) :: object
    integer, intent(in) :: i_term, f, h, c
    logical :: flag
  end function prc_core_is_allowed
end interface

```

Set the constant process data for a specific term. By default, these are the constants stored inside the object, ignoring the term index. Type extensions may override this and provide term-specific data.

```

<Prc core: process core: TBP>+≡
  procedure :: get_constants => prc_core_get_constants

<Prc core: procedures>+≡
  subroutine prc_core_get_constants (object, data, i_term)
    class(prc_core_t), intent(in) :: object
    type(process_constants_t), intent(out) :: data
    integer, intent(in) :: i_term
    data = object%data
  end subroutine prc_core_get_constants

```

The strong coupling is not among the process constants. The default implementation is to return a negative number, which indicates that α_s is not available. This may be overridden by an implementation that provides an (event-specific) value. The value can be stored in the process-specific workspace.

```

<Prc core: process core: TBP>+≡
  procedure :: get_alpha_s => prc_core_get_alpha_s

<Prc core: procedures>+≡
  function prc_core_get_alpha_s (object, core_state) result (alpha)
    class(prc_core_t), intent(in) :: object
    class(prc_core_state_t), intent(in), allocatable :: core_state
    real(default) :: alpha
    alpha = -1
  end function prc_core_get_alpha_s

```

Allocate the workspace associated to a process component. The default is that there is no workspace, so we do nothing. A type extension may override this and allocate a workspace object of appropriate type, which can be used in further calculations.

In any case, the `intent(out)` attribute deletes any previously allocated workspace.

```

<Prc core: process core: TBP>+≡
  procedure :: allocate_workspace => prc_core_ignore_workspace

<Prc core: procedures>+≡
  subroutine prc_core_ignore_workspace (object, core_state)
    class(prc_core_t), intent(in) :: object
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_core_ignore_workspace

```

Initialize the structure-function instance that corresponds to a process component. In ordinary cases, this amounts to a straightforward copy of the given template, but the process core may also choose to modify the setup, and it may access its own workspace.

The `sf_chain_instance` is the object that we want to prepare. The `sf_chain` argument is a template for its structure. For the initialization, we also need the number of channels `n_channel`.

Note: crash with nagfor 5.3.1 if `sf_chain_instance` is declared `intent(out)`, as would be more appropriate.

```

<Prc core: process core: TBP>+≡
  procedure :: init_sf_chain => prc_core_init_sf_chain

<Prc core: procedures>+≡
  subroutine prc_core_init_sf_chain &
    (object, sf_chain_instance, sf_chain, n_channel, core_state)
    class(prc_core_t), intent(in) :: object
    type(sf_chain_instance_t), intent(inout), target :: sf_chain_instance
    type(sf_chain_t), intent(in), target :: sf_chain
    integer, intent(in) :: n_channel
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    call sf_chain_instance%init (sf_chain, n_channel)
  end subroutine prc_core_init_sf_chain

```

Compute the momenta in the hard interaction, taking the seed kinematics as input. The `i_term` index tells us which term we want to compute. (The standard method is to just transfer the momenta to the hard interaction.)

```

<Prc core: process core: TBP>+≡
  procedure(prc_core_compute_hard_kinematics), deferred :: &
    compute_hard_kinematics

<Prc core: interfaces>+≡
  abstract interface
    subroutine prc_core_compute_hard_kinematics &
      (object, p_seed, i_term, int_hard, core_state)
    import
    class(prc_core_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(in) :: p_seed
    integer, intent(in) :: i_term
    type(interaction_t), intent(inout) :: int_hard
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_core_compute_hard_kinematics
  end interface

```

Compute the momenta in the effective interaction, taking the hard kinematics as input. (This is called only if parton recombination is to be applied for the process variant.)

```

<Prc core: process core: TBP>+≡
  procedure(prc_core_compute_eff_kinematics), deferred :: &
    compute_eff_kinematics

<Prc core: interfaces>+≡
  abstract interface
    subroutine prc_core_compute_eff_kinematics &
      (object, i_term, int_hard, int_eff, core_state)
    import
    class(prc_core_t), intent(in) :: object
    integer, intent(in) :: i_term
    type(interaction_t), intent(in) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_core_compute_eff_kinematics

```

```
end interface
```

Recover the missing pieces. We know the incoming momenta of the `p_seed` array and the outgoing momenta of the `int_eff` interaction. We have to recover the outgoing momenta of `p_seed` and the incoming momenta of `int_eff`.

(The trivial case is that these are identical.)

Furthermore, if `int_hard` and `int_eff` are not aliased, we have to set the momenta there. In the trivial case, `int_eff` is a pointer to `int_hard`, so `int_hard` should not be touched at all.

```
<Prc core: process core: TBP>+≡
  procedure(prc_core_recover_kinematics), deferred :: &
    recover_kinematics

<Prc core: interfaces>+≡
  abstract interface
    subroutine prc_core_recover_kinematics &
      (object, p_seed, int_hard, int_eff, core_state)
    import
    class(prc_core_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(inout) :: p_seed
    type(interaction_t), intent(inout) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_core_recover_kinematics
end interface
```

The process core must implement this function. Here, `j` is the index of the particular term we want to compute. The amplitude may depend on the factorization and renormalization scales.

The `core_state` (workspace) argument may be used if it is provided by the caller. Otherwise, the routine should compute the result directly.

```
<Prc core: process core: TBP>+≡
  procedure(prc_core_compute_amplitude), deferred :: compute_amplitude

<Prc core: interfaces>+≡
  abstract interface
    function prc_core_compute_amplitude &
      (object, j, p, f, h, c, fac_scale, ren_scale, alpha_qcd_forced, &
       core_state) result (amp)
    import
    class(prc_core_t), intent(in) :: object
    integer, intent(in) :: j
    type(vector4_t), dimension(:), intent(in) :: p
    integer, intent(in) :: f, h, c
    real(default), intent(in) :: fac_scale, ren_scale
    real(default), intent(in), allocatable :: alpha_qcd_forced
    class(prc_core_state_t), intent(inout), allocatable, optional :: &
      core_state
    complex(default) :: amp
  end function prc_core_compute_amplitude
end interface
```

16.1.2 Storage for intermediate results

The abstract `prc_core_state_t` type allows process cores to set up temporary workspace. The object is an extra argument for each of the individual calculations between kinematics setup and matrix-element evaluation.

```
<Prc core: public>+≡
    public :: prc_core_state_t

<Prc core: types>+≡
    type, abstract :: prc_core_state_t
    contains
        procedure(workspace_write), deferred :: write
        procedure(workspace_reset_new_kinematics), deferred :: reset_new_kinematics
    end type prc_core_state_t
```

For debugging, we should at least have an output routine.

```
<Prc core: interfaces>+≡
    abstract interface
        subroutine workspace_write (object, unit)
            import
                class(prc_core_state_t), intent(in) :: object
                integer, intent(in), optional :: unit
            end subroutine workspace_write
        end interface
```

This is used during the NLO calculation, see there for more information.

```
<Prc core: interfaces>+≡
    abstract interface
        subroutine workspace_reset_new_kinematics (object)
            import
                class(prc_core_state_t), intent(inout) :: object
            end subroutine workspace_reset_new_kinematics
        end interface
```

16.1.3 Helicity selection data

This is intended for use with O'MEGA, but may also be made available to other process methods. We set thresholds for counting the times a specific helicity amplitude is zero. When the threshold is reached, we skip this amplitude in subsequent calls.

For initializing the helicity counters, we need an object that holds the two parameters, the threshold (large real number) and the cutoff (integer).

A helicity value suppressed by more than `threshold` (a value which multiplies `epsilon`, to be compared with the average of the current amplitude, default is 10^{10}) is treated as zero. A matrix element is assumed to be zero and not called again if it has been zero `cutoff` times.

```
<Prc core: public>+≡
    public :: helicity_selection_t
```



```

<Prc core: types>+≡
  type :: helicity_selection_t
    logical :: active = .false.
    real(default) :: threshold = 0
    integer :: cutoff = 0
  contains
    <Prc core: helicity selection: TBP>
  end type helicity_selection_t

```

Output. If the selection is inactive, print nothing.

```

<Prc core: helicity selection: TBP>≡
  procedure :: write => helicity_selection_write

<Prc core: procedures>+≡
  subroutine helicity_selection_write (object, unit)
    class(helicity_selection_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    if (object%active) then
      write (u, "(3x,A)") "Helicity selection data:"
      write (u, "(5x,A,ES17.10)") &
        "threshold =", object%threshold
      write (u, "(5x,A,I0)") &
        "cutoff    =", object%cutoff
    end if
  end subroutine helicity_selection_write

```

16.2 Template matrix elements

Here, we provide template matrix elements that are in structure very similar to O'MEGA matrix elements, but do not need its infrastructure. Per default, the matrix elements are flat, i.e. they have the constant value one. Analogous to the O'MEGA implementation, this section implements the interface to the templates (via the makefile) and the driver.

```

<prc_template_me.f90>≡
  <File header>

  module prc_template_me

    use iso_c_binding !NODEP!
    use kinds
    use io_units
  <Use strings>
    use unit_tests
    use system_defs, only: TAB
    use diagnostics
    use os_interface
    use lorentz
    use flavors
    use sm_qcd

```

```

    use interactions
    use model_data
    use model_testbed

    use process_constants
    use prclib_interfaces
    use prc_core_def
    use particle_specifiers
    use process_libraries
    use prc_core

    <Standard module head>

    <Template matrix elements: public>

    <Template matrix elements: types>

    <Template matrix elements: interfaces>

    contains

    <Template matrix elements: procedures>

    <Template matrix elements: tests>

    end module prc_template_me

```

16.2.1 Process definition

For the process definition we implement an extension of the `prc_core_def_t` abstract type.

```

<Template matrix elements: public>≡
    public :: template_me_def_t

<Template matrix elements: types>≡
    type, extends (prc_core_def_t) :: template_me_def_t
    contains
    <Template matrix elements: template ME def: TBP>
    end type template_me_def_t

<Template matrix elements: template ME def: TBP>≡
    procedure, nopass :: type_string => template_me_def_type_string

<Template matrix elements: procedures>≡
    function template_me_def_type_string () result (string)
        type(string_t) :: string
        string = "template"
    end function template_me_def_type_string

```

Initialization: allocate the writer for the template matrix element. Also set any data for this process that the writer needs.

```

<Template matrix elements: template ME def: TBP>+≡
    procedure :: init => template_me_def_init

```

```

<Template matrix elements: procedures>+≡
  subroutine template_me_def_init &
    (object, model, prt_in, prt_out, unity)
    class(template_me_def_t), intent(out) :: object
    class(model_data_t), intent(in), target :: model
    type(string_t), dimension(:), intent(in) :: prt_in
    type(string_t), dimension(:), intent(in) :: prt_out
    logical, intent(in) :: unity
    allocate (template_me_writer_t :: object%writer)
    select type (writer => object%writer)
    type is (template_me_writer_t)
      call writer%init (model, prt_in, prt_out, unity)
    end select
  end subroutine template_me_def_init

```

Write/read process- and method-specific data.

```

<Template matrix elements: template ME def: TBP>+≡
  procedure :: write => template_me_def_write

```

```

<Template matrix elements: procedures>+≡
  subroutine template_me_def_write (object, unit)
    class(template_me_def_t), intent(in) :: object
    integer, intent(in) :: unit
    select type (writer => object%writer)
    type is (template_me_writer_t)
      call writer%write (unit)
    end select
  end subroutine template_me_def_write

```

```

<Template matrix elements: template ME def: TBP>+≡
  procedure :: read => template_me_def_read

```

```

<Template matrix elements: procedures>+≡
  subroutine template_me_def_read (object, unit)
    class(template_me_def_t), intent(out) :: object
    integer, intent(in) :: unit
    call msg_bug &
      ("WHIZARD template process definition: input not supported (yet)")
  end subroutine template_me_def_read

```

Allocate the driver for template matrix elements.

```

<Template matrix elements: template ME def: TBP>+≡
  procedure :: allocate_driver => template_me_def_allocate_driver

<Template matrix elements: procedures>+≡
  subroutine template_me_def_allocate_driver (object, driver, basename)
    class(template_me_def_t), intent(in) :: object
    class(prc_core_driver_t), intent(out), allocatable :: driver
    type(string_t), intent(in) :: basename
    allocate (template_me_driver_t :: driver)
  end subroutine template_me_def_allocate_driver

```

We need code:

```

<Template matrix elements: template ME def: TBP>+=
  procedure, nopass :: needs_code => template_me_def_needs_code

<Template matrix elements: procedures>+=
  function template_me_def_needs_code () result (flag)
    logical :: flag
    flag = .true.
  end function template_me_def_needs_code

```

These are the features that a template matrix element provides.

```

<Template matrix elements: template ME def: TBP>+=
  procedure, nopass :: get_features => template_me_def_get_features

<Template matrix elements: procedures>+=
  subroutine template_me_def_get_features (features)
    type(string_t), dimension(:), allocatable, intent(out) :: features
    allocate (features (6))
    features = [ &
      var_str ("init"), &
      var_str ("update_alpha_s"), &
      var_str ("is_allowed"), &
      var_str ("new_event"), &
      var_str ("get_amplitude")]
  end subroutine template_me_def_get_features

```

The interface of the specific features.

```

<Template matrix elements: interfaces>=
  abstract interface
    subroutine init_t (par) bind(C)
      import
      real(c_default_float), dimension(*), intent(in) :: par
    end subroutine init_t
  end interface

  abstract interface
    subroutine update_alpha_s_t (alpha_s) bind(C)
      import
      real(c_default_float), intent(in) :: alpha_s
    end subroutine update_alpha_s_t
  end interface

  abstract interface
    subroutine is_allowed_t (flv, hel, col, flag) bind(C)
      import
      integer(c_int), intent(in) :: flv, hel, col
      logical(c_bool), intent(out) :: flag
    end subroutine is_allowed_t
  end interface

  abstract interface
    subroutine new_event_t (p) bind(C)
      import
      real(c_default_float), dimension(0:3,*), intent(in) :: p

```

```

        end subroutine new_event_t
    end interface

    abstract interface
        subroutine get_amplitude_t (flv, hel, col, amp) bind(C)
            import
            integer(c_int), intent(in) :: flv, hel, col
            complex(c_default_complex), intent(out):: amp
        end subroutine get_amplitude_t
    end interface

```

Connect the template matrix element features with the process driver.

```

<Template matrix elements: template ME def: TBP>+≡
    procedure :: connect => template_me_def_connect

<Template matrix elements: procedures>+≡
    subroutine template_me_def_connect (def, lib_driver, i, proc_driver)
        class(template_me_def_t), intent(in) :: def
        class(prclib_driver_t), intent(in) :: lib_driver
        integer, intent(in) :: i
        class(prc_core_driver_t), intent(inout) :: proc_driver
        integer(c_int) :: pid, fid
        type(c_funptr) :: fptr
        select type (proc_driver)
            type is (template_me_driver_t)
                pid = i
                fid = 1
                call lib_driver%get_fptr (pid, fid, fptr)
                call c_f_procpointer (fptr, proc_driver%init)
                fid = 2
                call lib_driver%get_fptr (pid, fid, fptr)
                call c_f_procpointer (fptr, proc_driver%update_alpha_s)
                fid = 3
                call lib_driver%get_fptr (pid, fid, fptr)
                call c_f_procpointer (fptr, proc_driver%is_allowed)
                fid = 4
                call lib_driver%get_fptr (pid, fid, fptr)
                call c_f_procpointer (fptr, proc_driver%new_event)
                fid = 5
                call lib_driver%get_fptr (pid, fid, fptr)
                call c_f_procpointer (fptr, proc_driver%get_amplitude)
            end select
        end subroutine template_me_def_connect

```

16.2.2 The Template Matrix element writer

Unlike O'MEGA, the template matrix element is directly written by the main WHIZARD program, so there will be no entry in the makefile for calling an external program. The template matrix element writer is responsible for writing interfaces and wrappers.

```

<Template matrix elements: types>+≡
    type, extends (prc_writer_f_module_t) :: template_me_writer_t

```

```

class(model_data_t), pointer :: model => null ()
type(string_t) :: model_name
logical :: unity
type(string_t), dimension(:), allocatable :: prt_in
type(string_t), dimension(:), allocatable :: prt_out
integer :: n_in
integer :: n_out
integer :: n_tot
contains
  <Template matrix elements: template ME writer: TBP>
end type template_me_writer_t

```

The reported type is the same as for the `template_me_def_t` type.

```

<Template matrix elements: template ME writer: TBP>≡
  procedure, nopass :: type_name => template_me_writer_type_name
<Template matrix elements: procedures>+≡
  function template_me_writer_type_name () result (string)
    type(string_t) :: string
    string = "template"
  end function template_me_writer_type_name

```

Taking into account the prefix for template ME module names.

```

<Template matrix elements: template ME writer: TBP>+≡
  procedure, nopass :: get_module_name => template_me_writer_get_module_name
<Template matrix elements: procedures>+≡
  function template_me_writer_get_module_name (id) result (name)
    type(string_t) :: name
    type(string_t), intent(in) :: id
    name = "tpr_" // id
  end function template_me_writer_get_module_name

```

Output. This is called by `template_me_def_write`.

```

<Template matrix elements: template ME writer: TBP>+≡
  procedure :: write => template_me_writer_write
<Template matrix elements: procedures>+≡
  subroutine template_me_writer_write (object, unit)
    class(template_me_writer_t), intent(in) :: object
    integer, intent(in) :: unit
    integer :: i, j
    write (unit, "(5x,A,I0)") "# incoming part. = ", object%n_in
    write (unit, "(7x,A)", advance="no") &
      "    Initial state: "
    do i = 1, object%n_in - 1
      write (unit, "(1x,A)", advance="no") char (object%prt_in(i))
    end do
    write (unit, "(1x,A)") char (object%prt_in(object%n_in))
    write (unit, "(5x,A,I0)") "# outgoing part. = ", object%n_out
    write (unit, "(7x,A)", advance="no") &
      "    Final state:  "
    do j = 1, object%n_out - 1
      write (unit, "(1x,A)", advance="no") char (object%prt_out(i))
    end do
  end subroutine

```

```

end do
write (unit, "(1x,A)") char (object%prt_out(object%n_out))
write (unit, "(5x,A,I0)") "# part. (total) = ", object%n_tot
end subroutine template_me_writer_write

```

Initialize with process data.

```

<Template matrix elements: template ME writer: TBP>+=
  procedure :: init => template_me_writer_init

<Template matrix elements: procedures>+=
  subroutine template_me_writer_init (writer, model, &
    prt_in, prt_out, unity)
    class(template_me_writer_t), intent(out) :: writer
    class(model_data_t), intent(in), target :: model
    type(string_t), dimension(:), intent(in) :: prt_in
    type(string_t), dimension(:), intent(in) :: prt_out
    logical, intent(in) :: unity
    writer%model => model
    writer%model_name = model%get_name ()
    writer%n_in = size (prt_in)
    writer%n_out = size (prt_out)
    writer%n_tot = size (prt_in) + size (prt_out)
    allocate (writer%prt_in (size (prt_in)), source = prt_in)
    allocate (writer%prt_out (size (prt_out)), source = prt_out)
    writer%unity = unity
  end subroutine template_me_writer_init

```

The makefile is the driver file for the test matrix elements.

```

<Template matrix elements: template ME writer: TBP>+=
  procedure :: write_makefile_code => template_me_write_makefile_code

<Template matrix elements: procedures>+=
  subroutine template_me_write_makefile_code (writer, unit, id, os_data, testflag)
    class(template_me_writer_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: testflag
    write (unit, "(5A)") "SOURCES += ", char (id), ".f90"
    write (unit, "(5A)") "OBJECTS += ", char (id), ".lo"
    write (unit, "(5A)") "clean-", char (id), ":"
    write (unit, "(5A)") TAB, "rm -f tpr_", char (id), ".mod"
    write (unit, "(5A)") TAB, "rm -f ", char (id), ".lo"
    write (unit, "(5A)") "CLEAN_SOURCES += ", char (id), ".f90"
    write (unit, "(5A)") "CLEAN_OBJECTS += tpr_", char (id), ".mod"
    write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), ".lo"
    write (unit, "(5A)") char (id), ".lo: ", char (id), ".f90"
    write (unit, "(5A)") TAB, "$(LTF_COMPILE) $<"
  end subroutine template_me_write_makefile_code

```

The source is written by this routine.

```

<Template matrix elements: template ME writer: TBP>+=
  procedure :: write_source_code => template_me_write_source_code

```

<Template matrix elements: procedures>+≡

```

subroutine template_me_write_source_code (writer, id)
  class(template_me_writer_t), intent(in) :: writer
  type(string_t), intent(in) :: id
  integer, dimension(writer%n_in) :: prt_in, mult_in, col_in
  type(flavor_t), dimension(1:writer%n_in) :: flv_in
  integer, dimension(writer%n_out) :: prt_out, mult_out
  integer, dimension(writer%n_tot) :: prt, mult
  integer, dimension(:, :), allocatable :: sxxx
  integer :: dummy, status
  type(flavor_t), dimension(1:writer%n_out) :: flv_out
  type(string_t) :: proc_str, comment_str
  integer :: u, i, j
  integer :: hel, hel_in, hel_out, fac, factor, col_fac
  type(string_t) :: filename
  comment_str = ""
  do i = 1, writer%n_in
    comment_str = comment_str // writer%prt_in(i) // " "
  end do
  do j = 1, writer%n_out
    comment_str = comment_str // writer%prt_out(j) // " "
  end do
  do i = 1, writer%n_in
    prt_in(i) = writer%model%get_pdg (writer%prt_in(i))
    call flv_in(i)%init (prt_in(i), writer%model)
    mult_in(i) = flv_in(i)%get_multiplicity ()
    col_in(i) = abs (flv_in(i)%get_color_type ())
    mult(i) = mult_in(i)
  end do
  do j = 1, writer%n_out
    prt_out(j) = writer%model%get_pdg (writer%prt_out(j))
    call flv_out(j)%init (prt_out(j), writer%model)
    mult_out(j) = flv_out(j)%get_multiplicity ()
    mult(writer%n_in + j) = mult_out(j)
  end do
  prt(1:writer%n_in) = prt_in(1:writer%n_in)
  prt(writer%n_in+1:writer%n_tot) = prt_out(1:writer%n_out)
  proc_str = converter (prt)
  hel_in = product (mult_in)
  hel_out = product (mult_out)
  col_fac = product (col_in)
  hel = hel_in * hel_out
  fac = hel
  dummy = 1
  factor = 1
  if (writer%n_out >= 3) then
    do i = 3, writer%n_out
      factor = factor * (i - 2) * (i - 1)
    end do
  end if
  factor = factor * col_fac
  allocate (sxxx(1:hel, 1:writer%n_tot))
  call create_spin_table (dummy, hel, fac, mult, sxxx)
  call msg_message ("Writing test matrix element for process '" &

```



```

        // char (id) // "")
filename = id // ".f90"
u = free_unit ()
open (unit=u, file=char(filename), action="write")
write (u, "(A)") "! File generated automatically by WHIZARD"
write (u, "(A)") "!"
write (u, "(A)") "! Note that irresp. of what you demanded WHIZARD"
write (u, "(A)") "! treats this as colorless process"
write (u, "(A)") "!"
write (u, "(A)") "module tpr_" // char(id)
write (u, "(A)") "
write (u, "(A)") "  use kinds"
write (u, "(A)") "  use omega_color, OCF => omega_color_factor"
write (u, "(A)") "
write (u, "(A)") "  implicit none"
write (u, "(A)") "  private"
write (u, "(A)") "
write (u, "(A)") "  public :: md5sum"
write (u, "(A)") "  public :: number_particles_in, number_particles_out"
write (u, "(A)") "  public :: number_spin_states, spin_states"
write (u, "(A)") "  public :: number_flavor_states, flavor_states"
write (u, "(A)") "  public :: number_color_flows, color_flows"
write (u, "(A)") "  public :: number_color_indices, number_color_factors, &"
write (u, "(A)") "    color_factors, color_sum, openmp_supported"
write (u, "(A)") "  public :: init, final, update_alpha_s"
write (u, "(A)") "
write (u, "(A)") "  public :: new_event, is_allowed, get_amplitude"
write (u, "(A)") "
write (u, "(A)") "  real(default), parameter :: &"
write (u, "(A)") "    & conv = 0.38937966e12_default"
write (u, "(A)") "
write (u, "(A)") "  real(default), parameter :: &"
write (u, "(A)") "    & pi = 3.1415926535897932384626433832795028841972_default"
write (u, "(A)") "
write (u, "(A)") "  real(default), parameter :: &"
if (writer%unity) then
  write (u, "(A)") "    & const = 1"
else
  write (u, "(A,1x,I0,A)") "    & const = (16 * pi / conv) * " &
    // "(16 * pi**2)**(", writer%n_out, "-2) "
end if
write (u, "(A)") "
write (u, "(A,1x,I0)") "  integer, parameter, private :: n_prt = ", &
  writer%n_tot
write (u, "(A,1x,I0)") "  integer, parameter, private :: n_in = ", &
  writer%n_in
write (u, "(A,1x,I0)") "  integer, parameter, private :: n_out = ", &
  writer%n_out
write (u, "(A)") "  integer, parameter, private :: n_cflow = 1"
write (u, "(A)") "  integer, parameter, private :: n_cindex = 2"
write (u, "(A)") "  !!! We ignore tensor products and take only one flavor state."
write (u, "(A)") "  integer, parameter, private :: n_flg = 1"
write (u, "(A,1x,I0)") "  integer, parameter, private :: n_hel = ", hel
write (u, "(A)") "

```

```

write (u, "(A)") " logical, parameter, private :: T = .true."
write (u, "(A)") " logical, parameter, private :: F = .false."
write (u, "(A)") "
do i = 1, hel
  write (u, "(A)") " integer, dimension(n_prt), parameter, private :: &"
  write (u, "(A)") "      // s_conv(i) // " = [ // &
    char(converter(sxxx(i,1:writer%n_tot))) // " ]"
end do
write (u, "(A)") " integer, dimension(n_prt,n_hel), parameter, private :: table_spin_states =
write (u, "(A)") "      reshape ( [ & "
do i = 1, hel-1
  write (u, "(A)") "      // s_conv(i) // ", & "
end do
write (u, "(A)") "      // s_conv(hel) // " & "
write (u, "(A)") "      ], [ n_prt, n_hel ] )"
write (u, "(A)") "
write (u, "(A)") " integer, dimension(n_prt), parameter, private :: &"
write (u, "(A)") "      f0001 = [ // char(proc_str) // " ] ! // char(comment_str)
write (u, "(A)") " integer, dimension(n_prt,n_flv), parameter, private :: table_flavor_states
write (u, "(A)") "      reshape ( [ f0001 ], [ n_prt, n_flv ] )"
write (u, "(A)") "
write (u, "(A)") " integer, dimension(n_cindex, n_prt), parameter, private :: &"
write (u, "(A)") "      c0001 = reshape ( [ // char (dummy_colorizer (flv_in)) // " " // &
  (repeat ("0,0, ", writer%n_out-1)) // "0,0 ], " // " [ n_cindex, n_prt ] )"
write (u, "(A)") " integer, dimension(n_cindex, n_prt, n_cflow), parameter, private :: &"
write (u, "(A)") "      table_color_flows = reshape ( [ c0001 ], [ n_cindex, n_prt, n_cflow ] )"
write (u, "(A)") "
write (u, "(A)") " logical, dimension(n_prt), parameter, private :: & "
write (u, "(A)") "      g0001 = [ // (repeat ("F, ", writer%n_tot-1)) // "F ] "
write (u, "(A)") " logical, dimension(n_prt, n_cflow), parameter, private " &
  // ":: table_ghost_flags = &"
write (u, "(A)") "      reshape ( [ g0001 ], [ n_prt, n_cflow ] )"
write (u, "(A)") "
write (u, "(A)") " integer, parameter, private :: n_cfactors = 1"
write (u, "(A)") " type(OCF), dimension(n_cfactors), parameter, private :: &"
write (u, "(A)") "      table_color_factors = [ OCF(1,1,+1._default) ]"
write (u, "(A)") "
write (u, "(A)") " logical, dimension(n_flv), parameter, private :: a0001 = [ T ]"
write (u, "(A)") " logical, dimension(n_flv, n_cflow), parameter, private :: &"
write (u, "(A)") "      flv_col_is_allowed = reshape ( [ a0001 ], [ n_flv, n_cflow ] )"
write (u, "(A)") "
write (u, "(A)") " complex(default), dimension (n_flv, n_hel, n_cflow), private, save :: amp"
write (u, "(A)") "
write (u, "(A)") " logical, dimension(n_hel), private, save :: hel_is_allowed = T"
write (u, "(A)") "
write (u, "(A)") "contains"
write (u, "(A)") "
write (u, "(A)") " pure function md5sum ()"
write (u, "(A)") "      character(len=32) :: md5sum"
write (u, "(A)") "      ! DON'T EVEN THINK of modifying the following line!"
write (u, "(A)") "      md5sum = "" // writer%md5sum // ""
write (u, "(A)") " end function md5sum"
write (u, "(A)") "
write (u, "(A)") " subroutine init (par)"

```

```

write (u, "(A)") "    real(default), dimension(*), intent(in) :: par"
write (u, "(A)") "end subroutine init"
write (u, "(A)") "
write (u, "(A)") "    subroutine final ()"
write (u, "(A)") "end subroutine final"
write (u, "(A)") "
write (u, "(A)") "    subroutine update_alpha_s (alpha_s)"
write (u, "(A)") "        real(default), intent(in) :: alpha_s"
write (u, "(A)") "end subroutine update_alpha_s"
write (u, "(A)") "
write (u, "(A)") "    pure function number_particles_in () result (n)"
write (u, "(A)") "        integer :: n"
write (u, "(A)") "        n = n_in"
write (u, "(A)") "end function number_particles_in"
write (u, "(A)") "
write (u, "(A)") "    pure function number_particles_out () result (n)"
write (u, "(A)") "        integer :: n"
write (u, "(A)") "        n = n_out"
write (u, "(A)") "end function number_particles_out"
write (u, "(A)") "
write (u, "(A)") "    pure function number_spin_states () result (n)"
write (u, "(A)") "        integer :: n"
write (u, "(A)") "        n = size (table_spin_states, dim=2)"
write (u, "(A)") "end function number_spin_states"
write (u, "(A)") "
write (u, "(A)") "    pure subroutine spin_states (a)"
write (u, "(A)") "        integer, dimension(:,,:), intent(out) :: a"
write (u, "(A)") "        a = table_spin_states"
write (u, "(A)") "end subroutine spin_states"
write (u, "(A)") "
write (u, "(A)") "    pure function number_flavor_states () result (n)"
write (u, "(A)") "        integer :: n"
write (u, "(A)") "        n = 1"
write (u, "(A)") "end function number_flavor_states"
write (u, "(A)") "
write (u, "(A)") "    pure subroutine flavor_states (a)"
write (u, "(A)") "        integer, dimension(:,,:), intent(out) :: a"
write (u, "(A)") "        a = table_flavor_states"
write (u, "(A)") "end subroutine flavor_states"
write (u, "(A)") "
write (u, "(A)") "    pure function number_color_indices () result (n)"
write (u, "(A)") "        integer :: n"
write (u, "(A)") "        n = size(table_color_flows, dim=1)"
write (u, "(A)") "end function number_color_indices"
write (u, "(A)") "
write (u, "(A)") "    pure subroutine color_factors (cf)"
write (u, "(A)") "        type(OCF), dimension(:,), intent(out) :: cf"
write (u, "(A)") "        cf = table_color_factors"
write (u, "(A)") "end subroutine color_factors"
write (u, "(A)") "
!pure unless OpenMP
!write (u, "(A)") "    pure function color_sum (flv, hel) result (amp2)"
write (u, "(A)") "    function color_sum (flv, hel) result (amp2)"
write (u, "(A)") "        integer, intent(in) :: flv, hel"

```

```

write (u, "(A)") "      real(kind=default) :: amp2"
write (u, "(A)") "      amp2 = real (omega_color_sum (flv, hel, amp, table_color_factors))"
write (u, "(A)") "    end function color_sum"
write (u, "(A)") "      "
write (u, "(A)") "    pure function number_color_flows () result (n)"
write (u, "(A)") "      integer :: n"
write (u, "(A)") "      n = size (table_color_flows, dim=3)"
write (u, "(A)") "    end function number_color_flows"
write (u, "(A)") "      "
write (u, "(A)") "    pure subroutine color_flows (a, g)"
write (u, "(A)") "      integer, dimension(:, :, :), intent(out) :: a"
write (u, "(A)") "      logical, dimension(:, :), intent(out) :: g"
write (u, "(A)") "      a = table_color_flows"
write (u, "(A)") "      g = table_ghost_flags"
write (u, "(A)") "    end subroutine color_flows"
write (u, "(A)") "      "
write (u, "(A)") "    pure function number_color_factors () result (n)"
write (u, "(A)") "      integer :: n"
write (u, "(A)") "      n = size (table_color_factors)"
write (u, "(A)") "    end function number_color_factors"
write (u, "(A)") "      "
write (u, "(A)") "    pure function openmp_supported () result (status)"
write (u, "(A)") "      logical :: status"
write (u, "(A)") "      status = .false."
write (u, "(A)") "    end function openmp_supported"
write (u, "(A)") "      "
write (u, "(A)") "    subroutine new_event (p)"
write (u, "(A)") "      real(default), dimension(0:3,*), intent(in) :: p"
write (u, "(A)") "      call calculate_amplitudes (amp, p)"
write (u, "(A)") "    end subroutine new_event"
write (u, "(A)") "      "
write (u, "(A)") "    pure function is_allowed (flv, hel, col) result (yorn)"
write (u, "(A)") "      logical :: yorn"
write (u, "(A)") "      integer, intent(in) :: flv, hel, col"
write (u, "(A)") "      yorn = hel_is_allowed(hel) .and. flv_col_is_allowed(fl, col)"
write (u, "(A)") "    end function is_allowed"
write (u, "(A)") "      "
write (u, "(A)") "    pure function get_amplitude (flv, hel, col) result (amp_result)"
write (u, "(A)") "      complex(default) :: amp_result"
write (u, "(A)") "      integer, intent(in) :: flv, hel, col"
write (u, "(A)") "      amp_result = amp (flv, hel, col)"
write (u, "(A)") "    end function get_amplitude"
write (u, "(A)") "      "
write (u, "(A)") "    pure subroutine calculate_amplitudes (amp, k)"
write (u, "(A)") "      complex(default), dimension(:, :, :), intent(out) :: amp"
write (u, "(A)") "      real(default), dimension(0:3,*), intent(in) :: k"
write (u, "(A)") "      real(default) :: fac"
write (u, "(A)") "      integer :: i"
write (u, "(A)") "      ! We give all helicities the same weight!"
if (writer%unity) then
  write (u, "(A,1x,I0,1x,A)") "      fac = ", col_fac
  write (u, "(A)") "      amp = const * sqrt(fac)"
else
  write (u, "(A,1x,I0,1x,A)") "      fac = ", factor

```

```

        write (u, "(A)") "      amp = sqrt((2 * (k(0,1)*k(0,2) &"
        write (u, "(A,1x,I0,A)") "      - dot_product (k(1:,1), k(1:,2))) ** (3-", &
                                          writer%n_out, ")) * sqrt(const * fac)"
    end if
    write (u, "(A,1x,I0,A)") "      amp = amp / sqrt(", hel_out, "._default)"
    write (u, "(A)") "      end subroutine calculate_amplitudes"
    write (u, "(A)") "
    write (u, "(A)") "end module tpr_" // char(id)
    close (u, iostat=status)
    deallocate (sxxx)
contains
function s_conv (num) result (chrt)
    integer, intent(in) :: num
    character(len=10) :: chrt
    write (chrt, "(I10)") num
    chrt = trim(adjustl(chrt))
    if (num < 10) then
        chrt = "s000" // chrt
    else if (num < 100) then
        chrt = "s00" // chrt
    else if (num < 1000) then
        chrt = "s0" // chrt
    else
        chrt = "s" // chrt
    end if
end function s_conv
function converter (flv) result (str)
    integer, dimension(:), intent(in) :: flv
    type(string_t) :: str
    character(len=150), dimension(size(flv)) :: chrt
    integer :: i
    str = ""
    do i = 1, size(flv) - 1
        write (chrt(i), "(I10)") flv(i)
        str = str // var_str(trim(adjustl(chrt(i)))) // ", "
    end do
    write (chrt(size(flv)), "(I10)") flv(size(flv))
    str = str // trim(adjustl(chrt(size(flv))))
end function converter
integer function sj (j,m)
    integer, intent(in) :: j, m
    if (((j == 1) .and. (m == 1)) .or. &
        ((j == 2) .and. (m == 2)) .or. &
        ((j == 3) .and. (m == 3)) .or. &
        ((j == 4) .and. (m == 3)) .or. &
        ((j == 5) .and. (m == 4))) then
        sj = 1
    else if (((j == 2) .and. (m == 1)) .or. &
        ((j == 3) .and. (m == 1)) .or. &
        ((j == 4) .and. (m == 2)) .or. &
        ((j == 5) .and. (m == 2))) then
        sj = -1
    else if (((j == 3) .and. (m == 2)) .or. &
        ((j == 5) .and. (m == 3))) then

```

```

        sj = 0
    else if (((j == 4) .and. (m == 1)) .or. &
            ((j == 5) .and. (m == 1))) then
        sj = -2
    else if (((j == 4) .and. (m == 4)) .or. &
            ((j == 5) .and. (m == 5))) then
        sj = 2
    else
        call msg_fatal ("template_me_write_source_code: Wrong spin type")
    end if
end function sj
recursive subroutine create_spin_table (index, nhel, fac, mult, inta)
    integer, intent(inout) :: index, fac
    integer, intent(in) :: nhel
    integer, dimension(:), intent(in) :: mult
    integer, dimension(nhel,size(mult)), intent(out) :: inta
    integer :: j
    if (index > size(mult)) return
    fac = fac / mult(index)
    do j = 1, nhel
        inta(j,index) = sj (mult(index),mod(((j-1)/fac),mult(index))+1)
    end do
    index = index + 1
    call create_spin_table (index, nhel, fac, mult, inta)
end subroutine create_spin_table
function dummy_colorizer (flv) result (str)
    type(flavor_t), dimension(:), intent(in) :: flv
    type(string_t) :: str
    integer :: i, k
    str = ""
    k = 0
    do i = 1, size(flvs)
        k = k + 1
        select case (flv(i)%get_color_type ())
            case (1,-1)
                str = str // "0,0, "
            case (3)
                str = str // int2string(k) // ",0, "
            case (-3)
                str = str // "0," // int2string(-k) // ", "
            case (8)
                str = str // int2string(k) // "," // int2string(-k-1) // ", "
                k = k + 1
            case default
                call msg_error ("Color type not supported.")
        end select
    end do
    str = adjustl(trim(str))
end function dummy_colorizer
end subroutine template_me_write_source_code

```

Return the name of a procedure that implements a given feature, as it is provided by the template matrix-element code. Template ME names are chosen

completely in analogy to the O'MEGA matrix element conventions.

```

<Template matrix elements: template ME writer: TBP>+=
  procedure, nopass :: get_procname => template_me_writer_get_procname

<Template matrix elements: procedures>+=
  function template_me_writer_get_procname (feature) result (name)
    type(string_t) :: name
    type(string_t), intent(in) :: feature
    select case (char (feature))
    case ("n_in");   name = "number_particles_in"
    case ("n_out");  name = "number_particles_out"
    case ("n_flv");  name = "number_flavor_states"
    case ("n_hel");  name = "number_spin_states"
    case ("n_col");  name = "number_color_flows"
    case ("n_cin");  name = "number_color_indices"
    case ("n_cf");   name = "number_color_factors"
    case ("flv_state"); name = "flavor_states"
    case ("hel_state"); name = "spin_states"
    case ("col_state"); name = "color_flows"
    case default
      name = feature
    end select
  end function template_me_writer_get_procname

```

The interfaces for the template-specific features.

```

<Template matrix elements: template ME writer: TBP>+=
  procedure :: write_interface => template_me_write_interface

<Template matrix elements: procedures>+=
  subroutine template_me_write_interface (writer, unit, id, feature)
    class(template_me_writer_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id
    type(string_t), intent(in) :: feature
    type(string_t) :: name
    name = writer%get_c_procname (id, feature)
    write (unit, "(2x,9A)") "interface"
    select case (char (feature))
    case ("init")
      write (unit, "(5x,9A)") "subroutine ", char (name), " (par) bind(C)"
      write (unit, "(7x,9A)") "import"
      write (unit, "(7x,9A)") "real(c_default_float), dimension(*), &
        &intent(in) :: par"
      write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("update_alpha_s")
      write (unit, "(5x,9A)") "subroutine ", char (name), " (alpha_s) bind(C)"
      write (unit, "(7x,9A)") "import"
      write (unit, "(7x,9A)") "real(c_default_float), intent(in) :: alpha_s"
      write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("is_allowed")
      write (unit, "(5x,9A)") "subroutine ", char (name), " &
        &(flv, hel, col, flag) bind(C)"
      write (unit, "(7x,9A)") "import"
      write (unit, "(7x,9A)") "integer(c_int), intent(in) :: flv, hel, col"

```

```

        write (unit, "(7x,9A)") "logical(c_bool), intent(out) :: flag"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("new_event")
        write (unit, "(5x,9A)") "subroutine ", char (name), " (p) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "real(c_default_float), dimension(0:3,*), &
            &intent(in) :: p"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("get_amplitude")
        write (unit, "(5x,9A)") "subroutine ", char (name), " &
            &(flv, hel, col, amp) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
        write (unit, "(7x,9A)") "complex(c_default_complex), intent(out) &
            &:: amp"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    end select
    write (unit, "(2x,9A)") "end interface"
end subroutine template_me_write_interface

```

The wrappers have to take into account conversion between C and Fortran data types.

NOTE: The case `c_default_float` \neq default is not yet covered.

<Template matrix elements: template ME writer: TBP>+≡

```

    procedure :: write_wrapper => template_me_write_wrapper

```

<Template matrix elements: procedures>+≡

```

subroutine template_me_write_wrapper (writer, unit, id, feature)
    class(template_me_writer_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id, feature
    type(string_t) :: name
    name = writer%get_c_procname (id, feature)
    write (unit, *)
    select case (char (feature))
    case ("init")
        write (unit, "(9A)") "subroutine ", char (name), " (par) bind(C)"
        write (unit, "(2x,9A)") "use iso_c_binding"
        write (unit, "(2x,9A)") "use kinds"
        write (unit, "(2x,9A)") "use tpr_", char (id)
        write (unit, "(2x,9A)") "real(c_default_float), dimension(*), &
            &intent(in) :: par"
        if (c_default_float == default) then
            write (unit, "(2x,9A)") "call ", char (feature), " (par)"
        end if
        write (unit, "(9A)") "end subroutine ", char (name)
    case ("update_alpha_s")
        write (unit, "(9A)") "subroutine ", char (name), " (alpha_s) bind(C)"
        write (unit, "(2x,9A)") "use iso_c_binding"
        write (unit, "(2x,9A)") "use kinds"
        write (unit, "(2x,9A)") "use tpr_", char (id)
        if (c_default_float == default) then
            write (unit, "(2x,9A)") "real(c_default_float), intent(in) &
                &:: alpha_s"

```



```

        write (unit, "(2x,9A)") "call ", char (feature), " (alpha_s)"
    end if
    write (unit, "(9A)") "end subroutine ", char (name)
case ("is_allowed")
    write (unit, "(9A)") "subroutine ", char (name), &
        " (flv, hel, col, flag) bind(C)"
    write (unit, "(2x,9A)") "use iso_c_binding"
    write (unit, "(2x,9A)") "use kinds"
    write (unit, "(2x,9A)") "use tpr_", char (id)
    write (unit, "(2x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
    write (unit, "(2x,9A)") "logical(c_bool), intent(out) :: flag"
    write (unit, "(2x,9A)") "flag = ", char (feature), &
        " (int (flv), int (hel), int (col))"
    write (unit, "(9A)") "end subroutine ", char (name)
case ("new_event")
    write (unit, "(9A)") "subroutine ", char (name), " (p) bind(C)"
    write (unit, "(2x,9A)") "use iso_c_binding"
    write (unit, "(2x,9A)") "use kinds"
    write (unit, "(2x,9A)") "use tpr_", char (id)
    if (c_default_float == default) then
        write (unit, "(2x,9A)") "real(c_default_float), dimension(0:3,*), &
            &intent(in) :: p"
        write (unit, "(2x,9A)") "call ", char (feature), " (p)"
    end if
    write (unit, "(9A)") "end subroutine ", char (name)
case ("get_amplitude")
    write (unit, "(9A)") "subroutine ", char (name), &
        " (flv, hel, col, amp) bind(C)"
    write (unit, "(2x,9A)") "use iso_c_binding"
    write (unit, "(2x,9A)") "use kinds"
    write (unit, "(2x,9A)") "use tpr_", char (id)
    write (unit, "(2x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
    write (unit, "(2x,9A)") "complex(c_default_complex), intent(out) &
        &:: amp"
    write (unit, "(2x,9A)") "amp = ", char (feature), &
        " (int (flv), int (hel), int (col))"
    write (unit, "(9A)") "end subroutine ", char (name)
end select
end subroutine template_me_write_wrapper

```

16.2.3 Driver

```

<Template matrix elements: types>+≡
type, extends (prc_core_driver_t) :: template_me_driver_t
    procedure(init_t), nopass, pointer :: &
        init => null ()
    procedure(update_alpha_s_t), nopass, pointer :: &
        update_alpha_s => null ()
    procedure(is_allowed_t), nopass, pointer :: &
        is_allowed => null ()
    procedure(new_event_t), nopass, pointer :: &
        new_event => null ()
    procedure(get_amplitude_t), nopass, pointer :: &

```

```

        get_amplitude => null ()
contains
  <Template matrix elements: template ME driver: TBP>
end type template_me_driver_t

```

The reported type is the same as for the `template_me_def_t` type.

```

<Template matrix elements: template ME driver: TBP>≡
  procedure, nopass :: type_name => template_me_driver_type_name

<Template matrix elements: procedures>+≡
  function template_me_driver_type_name () result (string)
    type(string_t) :: string
    string = "template"
  end function template_me_driver_type_name

```

16.2.4 High-level process definition

This procedure wraps the details filling a process-component definition entry as appropriate for an template matrix element.

NOTE: For calling the `import_component` method, we must explicitly address the `process_def_t` parent object. The natural way to call the method of the extended type triggers a bug in gfortran 4.6. The string array arguments `prt_in` and `prt_out` become corrupted and cause a segfault.

```

<Template matrix elements: public>+≡
  public :: template_me_make_process_component

<Template matrix elements: procedures>+≡
  subroutine template_me_make_process_component (entry, component_index, &
    model, model_name, prt_in, prt_out, unity)
    class(process_def_entry_t), intent(inout) :: entry
    integer, intent(in) :: component_index
    type(string_t), intent(in) :: model_name
    class(model_data_t), intent(in), target :: model
    type(string_t), dimension(:), intent(in) :: prt_in
    type(string_t), dimension(:), intent(in) :: prt_out
    logical, intent(in) :: unity
    class(prc_core_def_t), allocatable :: def
    allocate (template_me_def_t :: def)
    select type (def)
    type is (template_me_def_t)
      call def%init (model, prt_in, prt_out, unity)
    end select
    call entry%process_def_t%import_component (component_index, &
      n_out = size (prt_out), &
      prt_in = new_prt_spec (prt_in), &
      prt_out = new_prt_spec (prt_out), &
      method = var_str ("template"), &
      variant = def)
  end subroutine template_me_make_process_component

```

16.2.5 The prc_template_me_t wrapper

This is an instance of the generic `prc_core_t` object. It contains a pointer to the process definition (`template_me_def_t`), a data component (`process_constants_t`), and the matrix-element driver (`template_me_driver_t`).

```

<Template matrix elements: public>+≡
    public :: prc_template_me_t

<Template matrix elements: types>+≡
    type, extends (prc_core_t) :: prc_template_me_t
        real(default), dimension(:), allocatable :: par
    contains
        <Template matrix elements: prc template ME: TBP>
    end type prc_template_me_t

```

The workspace associated to a `prc_template_me_t` object contains a single flag. The flag is used to suppress re-evaluating the matrix element for each quantum-number combination, after the first amplitude belonging to a given kinematics has been computed.

We can also store the value of a running coupling once it has been calculated for an event. The default value is negative, which indicates an undefined value in this context.

```

<Template matrix elements: types>+≡
    type, extends (prc_core_state_t) :: template_me_state_t
        logical :: new_kinematics = .true.
        real(default) :: alpha_qcd = -1
    contains
        procedure :: write => template_me_state_write
        procedure :: reset_new_kinematics => template_me_state_reset_new_kinematics
    end type template_me_state_t

<Template matrix elements: procedures>+≡
    subroutine template_me_state_write (object, unit)
        class(template_me_state_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A,L1)") "Template ME state: new kinematics = ", &
            object%new_kinematics
    end subroutine template_me_state_write

<Template matrix elements: procedures>+≡
    subroutine template_me_state_reset_new_kinematics (object)
        class(template_me_state_t), intent(inout) :: object
    end subroutine template_me_state_reset_new_kinematics

```

Allocate the workspace with the above specific type.

```

<Template matrix elements: prc template ME: TBP>≡
    procedure :: allocate_workspace => prc_template_me_allocate_workspace

```

```

<Template matrix elements: procedures>+≡
  subroutine prc_template_me_allocate_workspace (object, core_state)
    class(prc_template_me_t), intent(in) :: object
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    allocate (template_me_state_t :: core_state)
  end subroutine prc_template_me_allocate_workspace

```

The following procedures are inherited from the base type as deferred, thus must be implemented. The corresponding unit tests are skipped here; the procedures are tested when called from the `processes` module.

Output: print just the ID of the associated matrix element. Then display any stored parameters.

```

<Template matrix elements: prc template ME: TBP>+≡
  procedure :: write => prc_template_me_write

<Template matrix elements: procedures>+≡
  subroutine prc_template_me_write (object, unit)
    class(prc_template_me_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(3x,A)", advance="no") "Template process core:"
    if (object%data_known) then
      write (u, "(1x,A)") char (object%data%id)
    else
      write (u, "(1x,A)") "[undefined]"
    end if
    if (allocated (object%par)) then
      write (u, "(3x,A)") "Parameter array:"
      do i = 1, size (object%par)
        write (u, "(5x,I0,1x,ES17.10)") i, object%par(i)
      end do
    end if
  end subroutine prc_template_me_write

```

Temporarily store the parameter array inside the `prc_template_me` object, so we can use it later during the actual initialization.

```

<Template matrix elements: prc template ME: TBP>+≡
  procedure :: set_parameters => prc_template_me_set_parameters

<Template matrix elements: procedures>+≡
  subroutine prc_template_me_set_parameters (prc_template_me, model)
    class(prc_template_me_t), intent(inout) :: prc_template_me
    class(model_data_t), intent(in), target, optional :: model
    if (present (model)) then
      if (.not. allocated (prc_template_me%par)) &
        allocate (prc_template_me%par (model%get_n_real ()))
      call model%real_parameters_to_c_array (prc_template_me%par)
    end if
  end subroutine prc_template_me_set_parameters

```

To fully initialize the process core, we perform base initialization, then initialize the external matrix element code.

This procedure overrides the `init` method of the base type, which we nevertheless can access via its binding `base_init`. When done, we have an allocated driver. The driver will call the `init` procedure for the external matrix element, and thus transfer the parameter set to where it finally belongs.

```

<Template matrix elements: prc template ME: TBP>+≡
  procedure :: init => prc_template_me_init

<Template matrix elements: procedures>+≡
  subroutine prc_template_me_init (object, def, lib, id, i_component)
    class(prc_template_me_t), intent(inout) :: object
    class(prc_core_def_t), intent(in), target :: def
    type(process_library_t), intent(in), target :: lib
    type(string_t), intent(in) :: id
    integer, intent(in) :: i_component
    call object%base_init (def, lib, id, i_component)
    call object%activate_parameters ()
  end subroutine prc_template_me_init

```

Activate the stored parameters by transferring them to the external matrix element.

```

<Template matrix elements: prc template ME: TBP>+≡
  procedure :: activate_parameters => prc_template_me_activate_parameters

<Template matrix elements: procedures>+≡
  subroutine prc_template_me_activate_parameters (object)
    class (prc_template_me_t), intent(inout) :: object
    if (allocated (object%driver)) then
      if (allocated (object%par)) then
        select type (driver => object%driver)
          type is (template_me_driver_t)
            if (associated (driver%init)) call driver%init (object%par)
          end select
      else
        call msg_bug ("prc_template_me_activate: parameter set is not allocated")
      end if
    else
      call msg_bug ("prc_template_me_activate: driver is not allocated")
    end if
  end subroutine prc_template_me_activate_parameters

```

The template ME process is an independent process which needs its own Monte Carlo parameter set for integration.

```

<Template matrix elements: prc template ME: TBP>+≡
  procedure :: needs_mcset => prc_template_me_needs_mcset

<Template matrix elements: procedures>+≡
  function prc_template_me_needs_mcset (object) result (flag)
    class(prc_template_me_t), intent(in) :: object
    logical :: flag
    flag = .true.
  end function prc_template_me_needs_mcset

```

There is only one term for this tree-level process.

```

<Template matrix elements: prc template ME: TBP>+=
  procedure :: get_n_terms => prc_template_me_get_n_terms

<Template matrix elements: procedures>+=
  function prc_template_me_get_n_terms (object) result (n)
    class(prc_template_me_t), intent(in) :: object
    integer :: n
    n = 1
  end function prc_template_me_get_n_terms

```

Tell whether a particular combination of flavor, helicity, color is allowed. Here we have to consult the matrix-element driver.

```

<Template matrix elements: prc template ME: TBP>+=
  procedure :: is_allowed => prc_template_me_is_allowed

<Template matrix elements: procedures>+=
  function prc_template_me_is_allowed (object, i_term, f, h, c) result (flag)
    class(prc_template_me_t), intent(in) :: object
    integer, intent(in) :: i_term, f, h, c
    logical :: flag
    logical(c_bool) :: cflag
    select type (driver => object%driver)
    type is (template_me_driver_t)
      call driver%is_allowed (f, h, c, cflag)
      flag = cflag
    end select
  end function prc_template_me_is_allowed

```

Transfer the generated momenta directly to the hard interaction in the (only) term. We assume that everything has been set up correctly, so the array fits.

```

<Template matrix elements: prc template ME: TBP>+=
  procedure :: compute_hard_kinematics => &
    prc_template_me_compute_hard_kinematics

<Template matrix elements: procedures>+=
  subroutine prc_template_me_compute_hard_kinematics &
    (object, p_seed, i_term, int_hard, core_state)
    class(prc_template_me_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(in) :: p_seed
    integer, intent(in) :: i_term
    type(interaction_t), intent(inout) :: int_hard
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    call int_hard%set_momenta (p_seed)
    !   if (allocated (core_state)) then
    !     select type (core_state)
    !       type is (template_me_state_t); core_state%new_kinematics = .true.
    !     end select
    !   end if
  end subroutine prc_template_me_compute_hard_kinematics

```

This procedure is not called for `prc_template_me_t`, just a placeholder.

```

<Template matrix elements: prc template ME: TBP>+=
  procedure :: compute_eff_kinematics => &
    prc_template_me_compute_eff_kinematics

<Template matrix elements: procedures>+=
  subroutine prc_template_me_compute_eff_kinematics &
    (object, i_term, int_hard, int_eff, core_state)
    class(prc_template_me_t), intent(in) :: object
    integer, intent(in) :: i_term
    type(interaction_t), intent(in) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_template_me_compute_eff_kinematics

```

Recover the momenta within the hard interaction. For tree-level processes, this is a trivial copy of the incoming seed and outgoing effective momenta. The effective interaction is a pointer to the hard interaction, so the latter is ignored.

```

<Template matrix elements: prc template ME: TBP>+=
  procedure :: recover_kinematics => prc_template_me_recover_kinematics

<Template matrix elements: tests>=
  subroutine prc_template_me_recover_kinematics &
    (object, p_seed, int_hard, int_eff, core_state)
    class(prc_template_me_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(inout) :: p_seed
    type(interaction_t), intent(inout) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    integer :: n_in
    n_in = int_eff%get_n_in ()
    call int_eff%set_momenta (p_seed(1:n_in), outgoing = .false.)
    p_seed(n_in+1:) = int_eff%get_momenta (outgoing = .true.)
  end subroutine prc_template_me_recover_kinematics

```

Compute the amplitude. For the tree-level process, we can ignore the scale settings. The term index `j` is also irrelevant.

We first call `new_event` for the given momenta (which we must unpack), then retrieve the amplitude value for the given quantum numbers.

If the `core_state` status flag is present, we can make sure that we call `new_event` only once for a given kinematics. After the first call, we unset the `new_kinematics` flag.

```

<Template matrix elements: prc template ME: TBP>+=
  procedure :: compute_amplitude => prc_template_me_compute_amplitude

<Template matrix elements: procedures>+=
  function prc_template_me_compute_amplitude &
    (object, j, p, f, h, c, fac_scale, ren_scale, alpha_qcd_forced, &
     core_state) result (amp)
    class(prc_template_me_t), intent(in) :: object
    integer, intent(in) :: j
    type(vector4_t), dimension(:), intent(in) :: p
    integer, intent(in) :: f, h, c

```

```

real(default), intent(in) :: fac_scale, ren_scale
real(default), intent(in), allocatable :: alpha_qcd_forced
class(prc_core_state_t), intent(inout), allocatable, optional :: core_state
complex(default) :: amp
integer :: n_tot, i
real(c_default_float), dimension(:,:), allocatable :: parray
complex(c_default_complex) :: camp
logical :: new_event
select type (driver => object%driver)
type is (template_me_driver_t)
    new_event = .true.
    if (present (core_state)) then
        if (allocated (core_state)) then
            select type (core_state)
            type is (template_me_state_t)
                new_event = core_state%new_kinematics
                core_state%new_kinematics = .false.
            end select
        end if
    end if
    if (new_event) then
        n_tot = object%data%n_in + object%data%n_out
        allocate (parray (0:3, n_tot))
        forall (i = 1:n_tot) parray(:,i) = vector4_get_components (p(i))
        call driver%new_event (parray)
    end if
    if (object%is_allowed (1, f, h, c)) then
        call driver%get_amplitude &
            (int (f, c_int), int (h, c_int), int (c, c_int), camp)
        amp = camp
    else
        amp = 0
    end if
end select
end function prc_template_me_compute_amplitude

```

We do not overwrite the `prc_core_t` routine for α_s .

16.2.6 Test

This is the master for calling self-test procedures. There is a separate test for testing O'MEGA diagram generation as this depends on a working analysis setup.

```

<Template matrix elements: public>+≡
    public :: prc_template_me_test

<Template matrix elements: tests>+≡
    subroutine prc_template_me_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Template matrix elements: execute tests>
end subroutine prc_template_me_test

```


Generate, compile and load a simple process matrix element

The process is $e^+e^- \rightarrow \mu^+\mu^-$ for vanishing masses and $e = 0.3$. We initialize the process, build the library, and compute a particular matrix element for momenta of unit energy and right-angle scattering. The matrix element, as it happens, is equal to e^2 . (Note that are no conversion factors applied, so this result is exact.)

For GNU make, makeflags is set to -j1. This eliminates a potential clash with a -j<n> flag if this test is called from a parallel make.

```

<Template matrix elements: execute tests>≡
    call test (prc_template_me_1, "prc_template_me_1", &
        "build and load simple template process", &
        u, results)

<Template matrix elements: tests>+≡
    subroutine prc_template_me_1 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        class(prc_core_def_t), allocatable :: def
        type(process_def_entry_t), pointer :: entry
        type(os_data_t) :: os_data
        class(model_data_t), pointer :: model
        type(string_t) :: model_name
        type(string_t), dimension(:), allocatable :: prt_in, prt_out
        type(process_constants_t) :: data
        class(prc_core_driver_t), allocatable :: driver
        integer, parameter :: cdf = c_default_float
        integer, parameter :: ci = c_int
        real(cdf), dimension(4) :: par
        real(cdf), dimension(0:3,4) :: p
        logical(c_bool) :: flag
        complex(c_default_complex) :: amp
        integer :: i

        write (u, "(A)")  "* Test output: prc_template_me_1"
        write (u, "(A)")  "* Purpose: create a template matrix element,"
        write (u, "(A)")  "*           normalized to give unit integral,"
        write (u, "(A)")  "*           build a library, link, load, and &
            &access the matrix element"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize a process library with one entry"
        write (u, "(A)")
        call lib%init (var_str ("template_me1"))
        call os_data_init (os_data)

        model_name = "QED"
        call prepare_model (model, model_name)

        allocate (prt_in (2), prt_out (2))
        prt_in = [var_str ("e+"), var_str ("e-")]
        prt_out = [var_str ("m+"), var_str ("m-")]

        allocate (template_me_def_t :: def)

```

```

select type (def)
type is (template_me_def_t)
    call def%init (model, prt_in, prt_out, unity = .false.)
end select
allocate (entry)
call entry%init (var_str ("template_me1_a"), model_name = model_name, &
    n_in = 2, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
    prt_in = new_prt_spec (prt_in), &
    prt_out = new_prt_spec (prt_out), &
    method = var_str ("template"), &
    variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Write makefile"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Clean any left-over files"
write (u, "(A)")
call lib%clean (os_data, distclean = .false.)

write (u, "(A)")  "* Write driver"
write (u, "(A)")
call lib%write_driver (force = .true.)

write (u, "(A)")  "* Write process source code, compile, link, load"
write (u, "(A)")
call lib%load (os_data)

call lib%write (u, libpath = .false.)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active" = ", &
    lib%is_active ()
write (u, "(1x,A,I0)")  "n_processes" = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Constants of template_me1_a_i1:"
write (u, "(A)")

call lib%connect_process (var_str ("template_me1_a"), 1, data, driver)

write (u, "(1x,A,A)")  "component ID" = ", char (data%id)
write (u, "(1x,A,A)")  "model name" = ", char (data%model_name)
write (u, "(1x,A,A,A)")  "md5sum" = ', ', data%md5sum, "'

```

```

write (u, "(1x,A,I0)") "n_in = ", data%n_in
write (u, "(1x,A,I0)") "n_out = ", data%n_out
write (u, "(1x,A,I0)") "n_flv = ", data%n_flv
write (u, "(1x,A,I0)") "n_hel = ", data%n_hel
write (u, "(1x,A,I0)") "n_col = ", data%n_col
write (u, "(1x,A,I0)") "n_cin = ", data%n_cin
write (u, "(1x,A,I0)") "n_cf = ", data%n_cf
write (u, "(1x,A,10(1x,I0))") "flv state =", data%flv_state
write (u, "(1x,A,10(1x,I2))") "hel state =", data%hel_state(:,1)
do i = 2, 16
    write (u, "(12x,4(1x,I2))") data%hel_state(:,i)
end do
write (u, "(1x,A,10(1x,I0))") "col state =", data%col_state
write (u, "(1x,A,10(1x,L1))") "ghost flag =", data%ghost_flag
write (u, "(1x,A,10(1x,F5.3))") "color factors =", data%color_factors
write (u, "(1x,A,10(1x,I0))") "cf index =", data%cf_index

write (u, "(A)")
write (u, "(A)")  "* Set parameters for template_me1_a and initialize:"
write (u, "(A)")

par = [0.3_cdf, 0.0_cdf, 0.0_cdf, 0.0_cdf]
write (u, "(2x,A,F6.4)") "ee = ", par(1)
write (u, "(2x,A,F6.4)") "me = ", par(2)
write (u, "(2x,A,F6.4)") "mmu = ", par(3)
write (u, "(2x,A,F6.4)") "mtau = ", par(4)

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    1.0_cdf, 0.0_cdf, 0.0_cdf, 1.0_cdf, &
    1.0_cdf, 0.0_cdf, 0.0_cdf, -1.0_cdf, &
    1.0_cdf, 1.0_cdf, 0.0_cdf, 0.0_cdf, &
    1.0_cdf, -1.0_cdf, 0.0_cdf, 0.0_cdf &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.4))") "p", i, " =", p(:,i)
end do

select type (driver)
type is (template_me_driver_t)
    call driver%init (par)

    call driver%new_event (p)

    write (u, "(A)")
    write (u, "(A)")  "* Compute matrix element:"
    write (u, "(A)")

    call driver%is_allowed (1_ci, 6_ci, 1_ci, flag)
    write (u, "(1x,A,L1)") "is_allowed (1, 6, 1) = ", flag

```

```

        call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
        write (u, "(1x,A,1x,E11.4)") "|amp (1, 6, 1)| =", abs (amp)
    end select

    call lib%final ()
    call cleanup_model (model)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: prc_template_me_1"

end subroutine prc_template_me_1

<Template matrix elements: execute tests>+≡
    call test (prc_template_me_2, "prc_template_me_2", &
        "build and load simple template_unity process", &
        u, results)

<Template matrix elements: tests>+≡
    subroutine prc_template_me_2 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        class(prc_core_def_t), allocatable :: def
        type(process_def_entry_t), pointer :: entry
        type(os_data_t) :: os_data
        class(model_data_t), pointer :: model
        type(string_t) :: model_name
        type(string_t), dimension(:), allocatable :: prt_in, prt_out
        type(process_constants_t) :: data
        class(prc_core_driver_t), allocatable :: driver
        integer, parameter :: cdf = c_default_float
        integer, parameter :: ci = c_int
        real(cdf), dimension(4) :: par
        real(cdf), dimension(0:3,4) :: p
        logical(c_bool) :: flag
        complex(c_default_complex) :: amp
        integer :: i

        write (u, "(A)")  "* Test output: prc_template_me_1"
        write (u, "(A)")  "* Purpose: create a template matrix element,"
        write (u, "(A)")  "*           being identical to unity,"
        write (u, "(A)")  "*           build a library, link, load, and &
            &access the matrix element"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize a process library with one entry"
        write (u, "(A)")
        call lib%init (var_str ("template_me2"))
        call os_data_init (os_data)

        model_name = "QED"
        call prepare_model (model, model_name)

        allocate (prt_in (2), prt_out (2))
        prt_in = [var_str ("e+"), var_str ("e-")]

```

```

prt_out = [var_str ("m+"), var_str ("m-")]

allocate (template_me_def_t :: def)
select type (def)
type is (template_me_def_t)
    call def%init (model, prt_in, prt_out, unity = .true.)
end select
allocate (entry)
call entry%init (var_str ("template_me2_a"), model_name = model_name, &
    n_in = 2, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
    prt_in = new_prt_spec (prt_in), &
    prt_out = new_prt_spec (prt_out), &
    method = var_str ("template_unity"), &
    variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Write makefile"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Clean any left-over files"
write (u, "(A)")
call lib%clean (os_data, distclean = .false.)

write (u, "(A)")  "* Write driver"
write (u, "(A)")
call lib%write_driver (force = .true.)

write (u, "(A)")  "* Write process source code, compile, link, load"
write (u, "(A)")
call lib%load (os_data)

call lib%write (u, libpath = .false.)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active" = ", &
    lib%is_active ()
write (u, "(1x,A,I0)")  "n_processes" = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Constants of template_me2_a_i1:"
write (u, "(A)")

call lib%connect_process (var_str ("template_me2_a"), 1, data, driver)

```

```

write (u, "(1x,A,A)") "component ID      = ", char (data%id)
write (u, "(1x,A,A)") "model name        = ", char (data%model_name)
write (u, "(1x,A,A,A)") "md5sum          = ', data%md5sum, '"
write (u, "(1x,A,I0)") "n_in      = ", data%n_in
write (u, "(1x,A,I0)") "n_out     = ", data%n_out
write (u, "(1x,A,I0)") "n_flv    = ", data%n_flv
write (u, "(1x,A,I0)") "n_hel    = ", data%n_hel
write (u, "(1x,A,I0)") "n_col    = ", data%n_col
write (u, "(1x,A,I0)") "n_cin    = ", data%n_cin
write (u, "(1x,A,I0)") "n_cf     = ", data%n_cf
write (u, "(1x,A,10(1x,I0))") "flv state =", data%flv_state
write (u, "(1x,A,10(1x,I2))") "hel state =", data%hel_state(:,1)
do i = 2, 16
    write (u, "(12x,4(1x,I2))") data%hel_state(:,i)
end do
write (u, "(1x,A,10(1x,I0))") "col state =", data%col_state
write (u, "(1x,A,10(1x,L1))") "ghost flag =", data%ghost_flag
write (u, "(1x,A,10(1x,F5.3))") "color factors =", data%color_factors
write (u, "(1x,A,10(1x,I0))") "cf index =", data%cf_index

write (u, "(A)")
write (u, "(A)")  "* Set parameters for template_me2_a and initialize:"
write (u, "(A)")

par = [0.3_cdf, 0.0_cdf, 0.0_cdf, 0.0_cdf]
write (u, "(2x,A,F6.4)") "ee  = ", par(1)
write (u, "(2x,A,F6.4)") "me  = ", par(2)
write (u, "(2x,A,F6.4)") "mmu = ", par(3)
write (u, "(2x,A,F6.4)") "mtau = ", par(4)

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    1.0_cdf, 0.0_cdf, 0.0_cdf, 1.0_cdf, &
    1.0_cdf, 0.0_cdf, 0.0_cdf, -1.0_cdf, &
    1.0_cdf, 1.0_cdf, 0.0_cdf, 0.0_cdf, &
    1.0_cdf, -1.0_cdf, 0.0_cdf, 0.0_cdf &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.4))") "p", i, " =", p(:,i)
end do

select type (driver)
type is (template_me_driver_t)
    call driver%init (par)

    call driver%new_event (p)

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element:"
write (u, "(A)")

```

```

        call driver%is_allowed (1_ci, 6_ci, 1_ci, flag)
        write (u, "(1x,A,L1)") "is_allowed (1, 6, 1) = ", flag

        call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
        write (u, "(1x,A,1x,E11.4)") "|amp (1, 6, 1)| =", abs (amp)
    end select

    call lib%final ()
    call cleanup_model (model)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: prc_template_me_2"

end subroutine prc_template_me_2

```

16.3 O'MEGA Interface

The standard method for process computation with WHIZARD is the O'MEGA matrix element generator.

This section implements the interface to the code generator (via the makefile) and the driver for the features provided by the O'MEGA matrix element.

There are actually two different methods steered by this interface, the traditional one which delivers compiled Fortran code, while the O'MEGA virtual machine (OVM) produces bytecode with look-up tables.

`<prc_omega.f90>`≡
<File header>

```

module prc_omega

    use, intrinsic :: iso_c_binding !NODEP!

    use kinds
    <Use strings>
    use io_units
    use file_utils, only: delete_file
    use unit_tests
    use system_defs, only: TAB
    use diagnostics
    use os_interface
    use lorentz
    use sm_qcd
    use interactions
    use model_data
    use var_base
    use model_testbed

    use process_constants
    use prclib_interfaces
    use prc_core_def
    use particle_specifiers
    use process_libraries

```

```

    use prc_core

    <Standard module head>

    <Omega interface: public>

    <Omega interface: types>

    <Omega interface: interfaces>

    contains

    <Omega interface: procedures>

    <Omega interface: tests>

    end module prc_omega

```

16.3.1 Process definition

For the process definition we implement an extension of the `prc_core_def_t` abstract type.

```

<Omega interface: public>≡
    public :: omega_def_t

<Omega interface: types>≡
    type, abstract, extends (prc_core_def_t) :: omega_def_t
    contains
    <Omega interface: omega def: TBP>
    end type omega_def_t

<Omega interface: public>+≡
    public :: omega_omega_def_t

<Omega interface: types>+≡
    type, extends (omega_def_t) :: omega_omega_def_t
    contains
    <Omega interface: omega omega def: TBP>
    end type omega_omega_def_t

<Omega interface: public>+≡
    public :: omega_ovm_def_t

<Omega interface: types>+≡
    type, extends (omega_def_t) :: omega_ovm_def_t
    contains
    <Omega interface: omega ovm def: TBP>
    end type omega_ovm_def_t

<Omega interface: omega omega def: TBP>≡
    procedure, nopass :: type_string => omega_omega_def_type_string

```



```

<Omega interface: procedures>≡
    function omega_omega_def_type_string () result (string)
        type(string_t) :: string
        string = "omega"
    end function omega_omega_def_type_string

<Omega interface: omega ovm def: TBP>≡
    procedure, nopass :: type_string => omega_ovm_def_type_string

<Omega interface: procedures>+≡
    function omega_ovm_def_type_string () result (string)
        type(string_t) :: string
        string = "ovm"
    end function omega_ovm_def_type_string

```

Initialization: allocate the writer for the O'MEGA matrix element. Also set any data for this process that the writer needs.

```

<Omega interface: omega def: TBP>≡
    procedure :: init => omega_def_init

<Omega interface: procedures>+≡
    subroutine omega_def_init (object, model_name, prt_in, prt_out, &
        restrictions, openmp_support, report_progress, extra_options, &
        diags, diags_color)
        class(omega_def_t), intent(out) :: object
        type(string_t), intent(in) :: model_name
        type(string_t), dimension(:), intent(in) :: prt_in
        type(string_t), dimension(:), intent(in) :: prt_out
        type(string_t), intent(in), optional :: restrictions
        logical, intent(in), optional :: openmp_support
        logical, intent(in), optional :: report_progress
        logical, intent(in), optional :: diags, diags_color
        type(string_t), intent(in), optional :: extra_options
        select type (object)
            type is (omega_omega_def_t)
                allocate (omega_omega_writer_t :: object%writer)
                select type (writer => object%writer)
                    type is (omega_omega_writer_t)
                        call writer%init (model_name, prt_in, prt_out, &
                            restrictions, openmp_support, report_progress, &
                            extra_options, diags, diags_color)
                end select
            type is (omega_ovm_def_t)
                allocate (omega_ovm_writer_t :: object%writer)
                select type (writer => object%writer)
                    type is (omega_ovm_writer_t)
                        call writer%init (model_name, prt_in, prt_out, &
                            restrictions, openmp_support, report_progress, &
                            extra_options, diags, diags_color)
                end select
        end select
    end subroutine omega_def_init

```

Write/read process- and method-specific data.

```
<Omega interface: omega def: TBP>+≡  
  procedure :: write => omega_def_write
```

```
<Omega interface: procedures>+≡  
  subroutine omega_def_write (object, unit)  
    class(omega_def_t), intent(in) :: object  
    integer, intent(in) :: unit  
    select type (writer => object%writer)  
    type is (omega_omega_writer_t)  
      call writer%write (unit)  
    type is (omega_ovm_writer_t)  
      call writer%write (unit)  
    end select  
  end subroutine omega_def_write
```

```
<Omega interface: omega def: TBP>+≡  
  procedure :: read => omega_def_read
```

```
<Omega interface: procedures>+≡  
  subroutine omega_def_read (object, unit)  
    class(omega_def_t), intent(out) :: object  
    integer, intent(in) :: unit  
    call msg_bug ("O'Mega process definition: input not supported yet")  
  end subroutine omega_def_read
```

Allocate the driver for O'MEGAmatrix elements.

```
<Omega interface: omega def: TBP>+≡  
  procedure :: allocate_driver => omega_def_allocate_driver
```

```
<Omega interface: procedures>+≡  
  subroutine omega_def_allocate_driver (object, driver, basename)  
    class(omega_def_t), intent(in) :: object  
    class(prc_core_driver_t), intent(out), allocatable :: driver  
    type(string_t), intent(in) :: basename  
    allocate (omega_driver_t :: driver)  
  end subroutine omega_def_allocate_driver
```

We need code:

```
<Omega interface: omega def: TBP>+≡  
  procedure, nopass :: needs_code => omega_def_needs_code
```

```
<Omega interface: procedures>+≡  
  function omega_def_needs_code () result (flag)  
    logical :: flag  
    flag = .true.  
  end function omega_def_needs_code
```

These are the features that an O'MEGA matrix element provides.

```
<Omega interface: omega def: TBP>+≡  
  procedure, nopass :: get_features => omega_def_get_features
```

```

<Omega interface: procedures>+≡
subroutine omega_def_get_features (features)
  type(string_t), dimension(:), allocatable, intent(out) :: features
  allocate (features (6))
  features = [ &
    var_str ("init"), &
    var_str ("update_alpha_s"), &
    var_str ("reset_helicity_selection"), &
    var_str ("is_allowed"), &
    var_str ("new_event"), &
    var_str ("get_amplitude")]
end subroutine omega_def_get_features

```

The interface of the specific features.

```

<Omega interface: interfaces>≡
abstract interface
  subroutine init_t (par) bind(C)
    import
    real(c_default_float), dimension(*), intent(in) :: par
  end subroutine init_t
end interface

abstract interface
  subroutine update_alpha_s_t (alpha_s) bind(C)
    import
    real(c_default_float), intent(in) :: alpha_s
  end subroutine update_alpha_s_t
end interface

abstract interface
  subroutine reset_helicity_selection_t (threshold, cutoff) bind(C)
    import
    real(c_default_float), intent(in) :: threshold
    integer(c_int), intent(in) :: cutoff
  end subroutine reset_helicity_selection_t
end interface

abstract interface
  subroutine is_allowed_t (flv, hel, col, flag) bind(C)
    import
    integer(c_int), intent(in) :: flv, hel, col
    logical(c_bool), intent(out) :: flag
  end subroutine is_allowed_t
end interface

abstract interface
  subroutine new_event_t (p) bind(C)
    import
    real(c_default_float), dimension(0:3,*), intent(in) :: p
  end subroutine new_event_t
end interface

abstract interface

```

```

subroutine get_amplitude_t (flv, hel, col, amp) bind(C)
import
integer(c_int), intent(in) :: flv, hel, col
complex(c_default_complex), intent(out):: amp
end subroutine get_amplitude_t
end interface

```

Connect the O'MEGA features with the process driver.

(Omega interface: omega def: TBP)+≡

```

procedure :: connect => omega_def_connect

```

(Omega interface: procedures)+≡

```

subroutine omega_def_connect (def, lib_driver, i, proc_driver)
class(omega_def_t), intent(in) :: def
class(prclib_driver_t), intent(in) :: lib_driver
integer, intent(in) :: i
class(prc_core_driver_t), intent(inout) :: proc_driver
integer(c_int) :: pid, fid
type(c_funptr) :: fptr
select type (proc_driver)
type is (omega_driver_t)
  pid = i
  fid = 1
  call lib_driver%get_fptr (pid, fid, fptr)
  call c_f_procpointer (fptr, proc_driver%init)
  fid = 2
  call lib_driver%get_fptr (pid, fid, fptr)
  call c_f_procpointer (fptr, proc_driver%update_alpha_s)
  fid = 3
  call lib_driver%get_fptr (pid, fid, fptr)
  call c_f_procpointer (fptr, proc_driver%reset_helicity_selection)
  fid = 4
  call lib_driver%get_fptr (pid, fid, fptr)
  call c_f_procpointer (fptr, proc_driver%is_allowed)
  fid = 5
  call lib_driver%get_fptr (pid, fid, fptr)
  call c_f_procpointer (fptr, proc_driver%new_event)
  fid = 6
  call lib_driver%get_fptr (pid, fid, fptr)
  call c_f_procpointer (fptr, proc_driver%get_amplitude)
end select
end subroutine omega_def_connect

```

16.3.2 The O'MEGA writer

The O'MEGA writer is responsible for inserting the appropriate lines in the make-file that call O'MEGA, and for writing interfaces and wrappers.

(Omega interface: types)+≡

```

type, extends (prc_writer_f_module_t), abstract :: omega_writer_t
type(string_t) :: model_name
type(string_t) :: process_mode
type(string_t) :: process_string

```

```

        type(string_t) :: restrictions
        logical :: openmp_support = .false.
        logical :: report_progress = .false.
        logical :: diags = .false.
        logical :: diags_color = .false.
        type(string_t) :: extra_options
    contains
        <Omega interface: omega writer: TBP>
    end type omega_writer_t

<Omega interface: types>+≡
    type, extends (omega_writer_t) :: omega_omega_writer_t
    contains
        <Omega interface: omega omega writer: TBP>
    end type omega_omega_writer_t

<Omega interface: types>+≡
    type, extends (omega_writer_t) :: omega_ovm_writer_t
    contains
        <Omega interface: omega ovms writer: TBP>
    end type omega_ovm_writer_t

<Omega interface: omega omega writer: TBP>≡
    procedure, nopass :: type_name => omega_omega_writer_type_name

<Omega interface: procedures>+≡
    function omega_omega_writer_type_name () result (string)
        type(string_t) :: string
        string = "omega"
    end function omega_omega_writer_type_name

<Omega interface: omega ovms writer: TBP>≡
    procedure, nopass :: type_name => omega_ovm_writer_type_name

<Omega interface: procedures>+≡
    function omega_ovm_writer_type_name () result (string)
        type(string_t) :: string
        string = "ovm"
    end function omega_ovm_writer_type_name

```

Taking into account the prefix for O'MEGA module names.

```

<Omega interface: omega writer: TBP>≡
    procedure, nopass :: get_module_name => omega_writer_get_module_name

<Omega interface: procedures>+≡
    function omega_writer_get_module_name (id) result (name)
        type(string_t) :: name
        type(string_t), intent(in) :: id
        name = "opr_" // id
    end function omega_writer_get_module_name

```

Output. This is called by omega_def_write.

(Omega interface: omega writer: TBP)+≡

```
procedure :: write => omega_writer_write
```

(Omega interface: procedures)+≡

```
subroutine omega_writer_write (object, unit)
  class(omega_writer_t), intent(in) :: object
  integer, intent(in) :: unit
  write (unit, "(5x,A,A)") "Model name      = ", &
    ''' // char (object%model_name) // '''
  write (unit, "(5x,A,A)") "Mode string    = ", &
    ''' // char (object%process_mode) // '''
  write (unit, "(5x,A,A)") "Process string = ", &
    ''' // char (object%process_string) // '''
  write (unit, "(5x,A,A)") "Restrictions  = ", &
    ''' // char (object%restrictions) // '''
  write (unit, "(5x,A,L1)") "OpenMP support = ", object%openmp_support
  write (unit, "(5x,A,L1)") "Report progress = ", object%report_progress
  write (unit, "(5x,A,A)") "Extra options  = ", &
    ''' // char (object%extra_options) // '''
  write (unit, "(5x,A,L1)") "Write diagrams  = ", object%diags
  write (unit, "(5x,A,L1)") "Write color diag. = ", object%diags_color
end subroutine omega_writer_write
```

Initialize with process data.

(Omega interface: omega writer: TBP)+≡

```
procedure :: init => omega_writer_init
```

(Omega interface: procedures)+≡

```
subroutine omega_writer_init (writer, model_name, prt_in, prt_out, &
  restrictions, openmp_support, report_progress, extra_options, &
  diags, diags_color)
  class(omega_writer_t), intent(out) :: writer
  type(string_t), intent(in) :: model_name
  type(string_t), dimension(:), intent(in) :: prt_in
  type(string_t), dimension(:), intent(in) :: prt_out
  type(string_t), intent(in), optional :: restrictions
  logical, intent(in), optional :: openmp_support
  logical, intent(in), optional :: report_progress
  logical, intent(in), optional :: diags, diags_color
  type(string_t), intent(in), optional :: extra_options
  integer :: i
  writer%model_name = model_name
  if (present (restrictions)) then
    writer%restrictions = restrictions
  else
    writer%restrictions = ""
  end if
  if (present (openmp_support)) writer%openmp_support = openmp_support
  if (present (report_progress)) writer%report_progress = report_progress
  if (present (diags)) writer%diags = diags
  if (present (diags_color)) writer%diags_color = diags_color
  if (present (extra_options)) then
    writer%extra_options = " " // extra_options
  end if
end subroutine omega_writer_init
```

```

else
    writer%extra_options = ""
end if
select case (size (prt_in))
case (1); writer%process_mode = " -decay"
case (2); writer%process_mode = " -scatter"
end select
associate (s => writer%process_string)
    s = " '"
    do i = 1, size (prt_in)
        if (i > 1) s = s // " "
        s = s // prt_in(i)
    end do
    s = s // " ->"
    do i = 1, size (prt_out)
        s = s // " " // prt_out(i)
    end do
    s = s // "' "
end associate
end subroutine omega_writer_init

```

The makefile implements the actual O'MEGA call. For old L^AT_EX distributions, we filter out the hyperref options for O'MEGA diagrams, at least in the testsuite.

```

<Omega interface: omega writer: TBP>+≡
    procedure :: write_makefile_code => omega_write_makefile_code

<Omega interface: procedures>+≡
    subroutine omega_write_makefile_code (writer, unit, id, os_data, testflag)
        class(omega_writer_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: testflag
        type(string_t) :: omega_binary, omega_path
        type(string_t) :: restrictions_string
        type(string_t) :: openmp_string
        type(string_t) :: kmatrix_string
        type(string_t) :: progress_string
        type(string_t) :: diagrams_string
        logical :: escape_hyperref
        escape_hyperref = .false.
        if (present (testflag)) escape_hyperref = testflag
        select type (writer)
        type is (omega_omega_writer_t)
            omega_binary = "omega_" // writer%model_name // ".opt"
        type is (omega_ovm_writer_t)
            select case (char (writer%model_name))
            case ("SM", "SM_CKM", "SM_Higgs", "2HDM", "2HDM_CKM", &
                "HSExt", "QED", "QCD", "Zprime")
            case default
                call msg_fatal ("The model " // char (writer%model_name) &
                    // " is not available for the O'Mega VM.")
            end select
            omega_binary = "omega_" // writer%model_name // "_VM.opt"
        end select
    end subroutine

```

```

end select
omega_path = os_data%whizard_omega_binpath // "/" // omega_binary
if (writer%restrictions /= "") then
    restrictions_string = " -cascade '" // writer%restrictions // "'"
else
    restrictions_string = ""
end if
if (writer%openmp_support) then
    openmp_string = " -target:openmp"
else
    openmp_string = ""
end if
if (writer%report_progress) then
    progress_string = " -fusion:progress"
else
    progress_string = ""
end if
if (writer%diags) then
    if (writer%diags_color) then
        diagrams_string = " -diagrams:C " // char(id) // &
        "_diags -diagrams_LaTeX"
    else
        diagrams_string = " -diagrams " // char(id) // &
        "_diags -diagrams_LaTeX"
    end if
else
    if (writer%diags_color) then
        diagrams_string = " -diagrams:c " // char(id) // &
        "_diags -diagrams_LaTeX"
    else
        diagrams_string = ""
    end if
end if
select case (char (writer%model_name))
case ("SM_rx", "SSC", "NoH_rx", "AltH")
    kmatrix_string = " -target:kmatrix_write"
case default
    kmatrix_string = ""
end select
write (unit, "(5A)") "SOURCES += ", char (id), ".f90"
select type (writer)
type is (omega_ovm_writer_t)
    write (unit, "(5A)") "SOURCES += ", char (id), ".hbc"
end select
if (writer%diags .or. writer%diags_color) then
    write (unit, "(5A)") "TEX_SOURCES += ", char (id), "_diags.tex"
    if (os_data%event_analysis_pdf) then
        write (unit, "(5A)") "TEX_OBJECTS += ", char (id), "_diags.pdf"
    else
        write (unit, "(5A)") "TEX_OBJECTS += ", char (id), "_diags.ps"
    end if
end if
write (unit, "(5A)") "OBJECTS += ", char (id), ".lo"
select type (writer)

```



```

type is (omega_omega_writer_t)
  write (unit, "(5A)") char (id), ".f90:"
  write (unit, "(99A)") TAB, char (omega_path), &
    " -o ", char (id), ".f90", &
    " -target:whizard", &
    " -target:parameter_module parameters_", char (writer%model_name), &
    " -target:module opr_", char (id), &
    " -target:md5sum '", writer%md5sum, "'", &
    char (openmp_string), &
    char (progress_string), &
    char (kmatrix_string), &
    char (writer%process_mode), char (writer%process_string), &
    char (restrictions_string), char (diagrams_string), &
    char (writer%extra_options)
type is (omega_ovm_writer_t)
  write (unit, "(5A)") char (id), ".hbc:"
  write (unit, "(99A)") TAB, char (omega_path), &
    " -o ", char (id), ".hbc", &
    char (progress_string), &
    char (writer%process_mode), char (writer%process_string), &
    char (restrictions_string), char (diagrams_string), &
    char (writer%extra_options)
  write (unit, "(5A)") char (id), ".f90:"
  write (unit, "(99A)") TAB, char (omega_path), &
    " -o ", char (id), ".f90 -params", &
    " -target:whizard ", &
    " -target:bytecode_file ", char (id), ".hbc", &
    " -target:wrapper_module opr_", char (id), &
    " -target:parameter_module_external parameters_", &
    char (writer%model_name), &
    " -target:md5sum '", writer%md5sum, "'", &
    char (openmp_string)
end select
if (writer%diags .or. writer%diags_color) &
  write (unit, "(5A)") char (id), "_diags.tex: ", char (id), ".f90"
write (unit, "(5A)") "clean-", char (id), ":"
write (unit, "(5A)") TAB, "rm -f ", char (id), ".f90"
write (unit, "(5A)") TAB, "rm -f opr_", char (id), ".mod"
write (unit, "(5A)") TAB, "rm -f ", char (id), ".lo"
write (unit, "(5A)") "CLEAN_SOURCES += ", char (id), ".f90"
select type (writer)
type is (omega_ovm_writer_t)
  write (unit, "(5A)") "CLEAN_SOURCES += ", char (id), ".hbc"
end select
if (writer%diags .or. writer%diags_color) then
  write (unit, "(5A)") "CLEAN_SOURCES += ", char (id), "_diags.tex"
end if
write (unit, "(5A)") "CLEAN_OBJECTS += opr_", char (id), ".mod"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), ".lo"
if (writer%diags .or. writer%diags_color) then
  write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.aux"
  write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.log"
  write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.dvi"
  write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.toc"

```

```

write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.out"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.[1-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.[1-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.[1-9][0-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.t[1-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.t[1-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.t[1-9][0-9][0-9]"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.mp"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags-fmf.log"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.dvi"
write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.ps"
if (os_data%event_analysis_pdf) &
  write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), "_diags.pdf"
end if
write (unit, "(5A)") char (id), ".lo: ", char (id), ".f90"
write (unit, "(5A)") TAB, "$(LTF_COMPILE) $<"
if (writer%diags .or. writer%diags_color) then
  if (os_data%event_analysis_ps) then
    if (os_data%event_analysis_pdf) then
      write (unit, "(5A)") char (id), "_diags.pdf: ", char (id), "_diags.tex"
    else
      write (unit, "(5A)") char (id), "_diags.ps: ", char (id), "_diags.tex"
    end if
  if (escape_hyperref) then
    write (unit, "(5A)") TAB, "-cat ", char (id), "_diags.tex | \"
    write (unit, "(5A)") TAB, "    sed -e\" // &
      \"s/\\usepackage\\[colorlinks\\]{hyperref}.*/%\\usepackage\" // &
      \"\\[colorlinks\\]{hyperref}/\" > \"
    write (unit, "(5A)") TAB, "    ", char (id), "_diags.tex.tmp"
    write (unit, "(5A)") TAB, "mv -f ", char (id), "_diags.tex.tmp \"
    write (unit, "(5A)") TAB, "    ", char (id), "_diags.tex"
  end if
  write (unit, "(5A)") TAB, "-TEXINPUTS=$(TEX_FLAGS) $(LATEX) \" // &
    char (id) // "_diags.tex"
  write (unit, "(5A)") TAB, "MPINPUTS=$(MP_FLAGS) $(MPOST) \" // &
    char (id) // "_diags-fmf.mp"
  write (unit, "(5A)") TAB, "TEXINPUTS=$(TEX_FLAGS) $(LATEX) \" // &
    char (id) // "_diags.tex"
  write (unit, "(5A)") TAB, "$(DVIPS) -o \" // char (id) // "_diags.ps \" // &
    char (id) // "_diags.dvi"
  if (os_data%event_analysis_pdf) then
    write (unit, "(5A)") TAB, "$(PS2PDF) \" // char (id) // "_diags.ps"
  end if
end if
end if
end if
end subroutine omega_write_makefile_code

```

The source is written by the makefile, so nothing to do here.

```

<Omega interface: omega_writer: TBP>+≡
  procedure :: write_source_code => omega_write_source_code

<Omega interface: procedures>+≡
  subroutine omega_write_source_code (writer, id)
    class(omega_writer_t), intent(in) :: writer

```

```

    type(string_t), intent(in) :: id
end subroutine omega_write_source_code

```

Return the name of a procedure that implements a given feature, as it is provided by the external matrix-element code. O'MEGA names some procedures differently, therefore we translate here and override the binding of the base type.

```

<Omega interface: omega writer: TBP>+≡
    procedure, nopass :: get_procname => omega_writer_get_procname

<Omega interface: procedures>+≡
    function omega_writer_get_procname (feature) result (name)
        type(string_t) :: name
        type(string_t), intent(in) :: feature
        select case (char (feature))
        case ("n_in");   name = "number_particles_in"
        case ("n_out");  name = "number_particles_out"
        case ("n_flv");  name = "number_flavor_states"
        case ("n_hel");  name = "number_spin_states"
        case ("n_col");  name = "number_color_flows"
        case ("n_cin");  name = "number_color_indices"
        case ("n_cf");   name = "number_color_factors"
        case ("flv_state"); name = "flavor_states"
        case ("hel_state"); name = "spin_states"
        case ("col_state"); name = "color_flows"
        case default
            name = feature
        end select
    end function omega_writer_get_procname

```

The interfaces for the O'MEGA-specific features.

```

<Omega interface: omega writer: TBP>+≡
    procedure :: write_interface => omega_write_interface

<Omega interface: procedures>+≡
    subroutine omega_write_interface (writer, unit, id, feature)
        class(omega_writer_t), intent(in) :: writer
        integer, intent(in) :: unit
        type(string_t), intent(in) :: id
        type(string_t), intent(in) :: feature
        type(string_t) :: name
        name = writer%get_c_procname (id, feature)
        write (unit, "(2x,9A)") "interface"
        select case (char (feature))
        case ("init")
            write (unit, "(5x,9A)") "subroutine ", char (name), " (par) bind(C)"
            write (unit, "(7x,9A)") "import"
            write (unit, "(7x,9A)") "real(c_default_float), dimension(*), &
                &intent(in) :: par"
            write (unit, "(5x,9A)") "end subroutine ", char (name)
        case ("update_alpha_s")
            write (unit, "(5x,9A)") "subroutine ", char (name), " (alpha_s) bind(C)"
            write (unit, "(7x,9A)") "import"
            write (unit, "(7x,9A)") "real(c_default_float), intent(in) :: alpha_s"
            write (unit, "(5x,9A)") "end subroutine ", char (name)

```

```

case ("reset_helicity_selection")
  write (unit, "(5x,9A)") "subroutine ", char (name), " &
    &(threshold, cutoff) bind(C)"
  write (unit, "(7x,9A)") "import"
  write (unit, "(7x,9A)") "real(c_default_float), intent(in) :: threshold"
  write (unit, "(7x,9A)") "integer(c_int), intent(in) :: cutoff"
  write (unit, "(5x,9A)") "end subroutine ", char (name)
case ("is_allowed")
  write (unit, "(5x,9A)") "subroutine ", char (name), " &
    &(flv, hel, col, flag) bind(C)"
  write (unit, "(7x,9A)") "import"
  write (unit, "(7x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
  write (unit, "(7x,9A)") "logical(c_bool), intent(out) :: flag"
  write (unit, "(5x,9A)") "end subroutine ", char (name)
case ("new_event")
  write (unit, "(5x,9A)") "subroutine ", char (name), " (p) bind(C)"
  write (unit, "(7x,9A)") "import"
  write (unit, "(7x,9A)") "real(c_default_float), dimension(0:3,*), &
    &intent(in) :: p"
  write (unit, "(5x,9A)") "end subroutine ", char (name)
case ("get_amplitude")
  write (unit, "(5x,9A)") "subroutine ", char (name), " &
    &(flv, hel, col, amp) bind(C)"
  write (unit, "(7x,9A)") "import"
  write (unit, "(7x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
  write (unit, "(7x,9A)") "complex(c_default_complex), intent(out) &
    &:: amp"
  write (unit, "(5x,9A)") "end subroutine ", char (name)
end select
write (unit, "(2x,9A)") "end interface"
end subroutine omega_write_interface

```

The wrappers have to take into account conversion between C and Fortran data types.

NOTE: The case `c_default_float` \neq default is not yet covered.

<Omega interface: omega writer: TBP>+≡

```

procedure :: write_wrapper => omega_write_wrapper

```

<Omega interface: procedures>+≡

```

subroutine omega_write_wrapper (writer, unit, id, feature)
  class(omega_writer_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id, feature
  type(string_t) :: name
  name = writer%get_c_procname (id, feature)
  write (unit, *)
  select case (char (feature))
  case ("init")
    write (unit, "(9A)") "subroutine ", char (name), " (par) bind(C)"
    write (unit, "(2x,9A)") "use iso_c_binding"
    write (unit, "(2x,9A)") "use kinds"
    write (unit, "(2x,9A)") "use opr_", char (id)
    write (unit, "(2x,9A)") "real(c_default_float), dimension(*), &
      &intent(in) :: par"

```

```

        if (c_default_float == default) then
            write (unit, "(2x,9A)") "call ", char (feature), " (par)"
        end if
        write (unit, "(9A)") "end subroutine ", char (name)
    case ("update_alpha_s")
        write (unit, "(9A)") "subroutine ", char (name), " (alpha_s) bind(C)"
        write (unit, "(2x,9A)") "use iso_c_binding"
        write (unit, "(2x,9A)") "use kinds"
        write (unit, "(2x,9A)") "use opr_", char (id)
        if (c_default_float == default) then
            write (unit, "(2x,9A)") "real(c_default_float), intent(in) &
                &:: alpha_s"
            write (unit, "(2x,9A)") "call ", char (feature), " (alpha_s)"
        end if
        write (unit, "(9A)") "end subroutine ", char (name)
    case ("reset_helicity_selection")
        write (unit, "(9A)") "subroutine ", char (name), &
            " (threshold, cutoff) bind(C)"
        write (unit, "(2x,9A)") "use iso_c_binding"
        write (unit, "(2x,9A)") "use kinds"
        write (unit, "(2x,9A)") "use opr_", char (id)
        if (c_default_float == default) then
            write (unit, "(2x,9A)") "real(c_default_float), intent(in) &
                &:: threshold"
            write (unit, "(2x,9A)") "integer(c_int), intent(in) :: cutoff"
            write (unit, "(2x,9A)") "call ", char (feature), &
                " (threshold, int (cutoff))"
        end if
        write (unit, "(9A)") "end subroutine ", char (name)
    case ("is_allowed")
        write (unit, "(9A)") "subroutine ", char (name), &
            " (flv, hel, col, flag) bind(C)"
        write (unit, "(2x,9A)") "use iso_c_binding"
        write (unit, "(2x,9A)") "use kinds"
        write (unit, "(2x,9A)") "use opr_", char (id)
        write (unit, "(2x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
        write (unit, "(2x,9A)") "logical(c_bool), intent(out) :: flag"
        write (unit, "(2x,9A)") "flag = ", char (feature), &
            " (int (flv), int (hel), int (col))"
        write (unit, "(9A)") "end subroutine ", char (name)
    case ("new_event")
        write (unit, "(9A)") "subroutine ", char (name), " (p) bind(C)"
        write (unit, "(2x,9A)") "use iso_c_binding"
        write (unit, "(2x,9A)") "use kinds"
        write (unit, "(2x,9A)") "use opr_", char (id)
        if (c_default_float == default) then
            write (unit, "(2x,9A)") "real(c_default_float), dimension(0:3,*), &
                &intent(in) :: p"
            write (unit, "(2x,9A)") "call ", char (feature), " (p)"
        end if
        write (unit, "(9A)") "end subroutine ", char (name)
    case ("get_amplitude")
        write (unit, "(9A)") "subroutine ", char (name), &
            " (flv, hel, col, amp) bind(C)"

```

```

write (unit, "(2x,9A)") "use iso_c_binding"
write (unit, "(2x,9A)") "use kinds"
write (unit, "(2x,9A)") "use opr_", char (id)
write (unit, "(2x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
write (unit, "(2x,9A)") "complex(c_default_complex), intent(out) &
&:: amp"
write (unit, "(2x,9A)") "amp = ", char (feature), &
" (int (flv), int (hel), int (col))"
write (unit, "(9A)") "end subroutine ", char (name)
end select
end subroutine omega_write_wrapper

```

16.3.3 Driver

```

<Omega interface: types>+≡
type, extends (prc_core_driver_t) :: omega_driver_t
  procedure(init_t), nopass, pointer :: &
    init => null ()
  procedure(update_alpha_s_t), nopass, pointer :: &
    update_alpha_s => null ()
  procedure(reset_helicity_selection_t), nopass, pointer :: &
    reset_helicity_selection => null ()
  procedure(is_allowed_t), nopass, pointer :: &
    is_allowed => null ()
  procedure(new_event_t), nopass, pointer :: &
    new_event => null ()
  procedure(get_amplitude_t), nopass, pointer :: &
    get_amplitude => null ()
contains
  <Omega interface: omega driver: TBP>
end type omega_driver_t

```

The reported type is the same as for the `omega_def_t` type.

```

<Omega interface: omega driver: TBP>≡
  procedure, nopass :: type_name => omega_driver_type_name
<Omega interface: procedures>+≡
  function omega_driver_type_name () result (string)
    type(string_t) :: string
    string = "omega"
  end function omega_driver_type_name

```

16.3.4 High-level process definition

This procedure wraps the details filling a process-component definition entry as appropriate for an O'MEGA matrix element.

NOTE: For calling the `import_component` method, we must explicitly address the `process_def_t` parent object. The natural way to call the method of the extended type triggers a bug in gfortran 4.6. The string array arguments `prt_in` and `prt_out` become corrupted and cause a segfault.

```

<Omega interface: public>+≡

```

```

public :: omega_make_process_component
<Omega interface: procedures>+≡
  subroutine omega_make_process_component (entry, component_index, &
    model_name, prt_in, prt_out, restrictions, openmp_support, &
    report_progress, extra_options, diags, diags_color)
    class(process_def_entry_t), intent(inout) :: entry
    integer, intent(in) :: component_index
    type(string_t), intent(in) :: model_name
    type(string_t), dimension(:), intent(in) :: prt_in
    type(string_t), dimension(:), intent(in) :: prt_out
    type(string_t), intent(in), optional :: restrictions
    logical, intent(in), optional :: openmp_support
    logical, intent(in), optional :: report_progress
    logical, intent(in), optional :: diags, diags_color
    type(string_t), intent(in), optional :: extra_options
    class(prc_core_def_t), allocatable :: def
    allocate (omega_omega_def_t :: def)
    select type (def)
    type is (omega_omega_def_t)
      call def%init (model_name, prt_in, prt_out, &
        restrictions, openmp_support, report_progress, &
        extra_options, diags, diags_color)
    end select
    call entry%process_def_t%import_component (component_index, &
      n_out = size (prt_out), &
      prt_in = new_prt_spec (prt_in), &
      prt_out = new_prt_spec (prt_out), &
      method = var_str ("omega"), &
      variant = def)
  end subroutine omega_make_process_component

```

16.3.5 The prc_omega_t wrapper

This is an instance of the generic `prc_core_t` object. It contains a pointer to the process definition (`omega_def_t`), a data component (`process_constants_t`), and the matrix-element driver (`omega_driver_t`).

```

<Omega interface: public>+≡
  public :: prc_omega_t
<Omega interface: types>+≡
  type, extends (prc_core_t) :: prc_omega_t
    real(default), dimension(:), allocatable :: par
    type(helicity_selection_t) :: helicity_selection
    type(qcd_t) :: qcd
  contains
    <Omega interface: prc omega: TBP>
  end type prc_omega_t

```

The workspace associated to a `prc_omega_t` object contains a single flag. The flag is used to suppress re-evaluating the matrix element for each quantum-number combination, after the first amplitude belonging to a given kinematics has been computed.

We can also store the value of a running coupling once it has been calculated for an event. The default value is negative, which indicates an undefined value in this context.

```
<Omega interface: types>+≡
type, extends (prc_core_state_t) :: omega_state_t
  logical :: new_kinematics = .true.
  real(default) :: alpha_qcd = -1
contains
  procedure :: write => omega_state_write
  procedure :: reset_new_kinematics => omega_state_reset_new_kinematics
end type omega_state_t
```

```
<Omega interface: procedures>+≡
subroutine omega_state_write (object, unit)
  class(omega_state_t), intent(in) :: object
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, "(3x,A,L1)") "O'Mega state: new kinematics = ", &
    object%new_kinematics
end subroutine omega_state_write
```

```
<Omega interface: procedures>+≡
subroutine omega_state_reset_new_kinematics (object)
  class(omega_state_t), intent(inout) :: object
  object%new_kinematics = .true.
end subroutine omega_state_reset_new_kinematics
```

Allocate the workspace with the above specific type.

```
<Omega interface: prc omega: TBP>≡
procedure :: allocate_workspace => prc_omega_allocate_workspace

<Omega interface: procedures>+≡
subroutine prc_omega_allocate_workspace (object, core_state)
  class(prc_omega_t), intent(in) :: object
  class(prc_core_state_t), intent(inout), allocatable :: core_state
  allocate (omega_state_t :: core_state)
end subroutine prc_omega_allocate_workspace
```

The following procedures are inherited from the base type as deferred, thus must be implemented. The corresponding unit tests are skipped here; the procedures are tested when called from the `processes` module.

Output: print just the ID of the associated matrix element. Then display any stored parameters and the helicity selection data. (The latter are printed only if active.)

```
<Omega interface: prc omega: TBP>+≡
procedure :: write => prc_omega_write

<Omega interface: procedures>+≡
subroutine prc_omega_write (object, unit)
  class(prc_omega_t), intent(in) :: object
  integer, intent(in), optional :: unit
```



```

integer :: u, i
u = given_output_unit (unit)
write (u, "(3x,A)", advance="no") "0'Mega process core:"
if (object%data_known) then
  write (u, "(1x,A)") char (object%data%id)
else
  write (u, "(1x,A)") "[undefined]"
end if
if (allocated (object%par)) then
  write (u, "(3x,A)") "Parameter array:"
  do i = 1, size (object%par)
    write (u, "(5x,I0,1x,ES17.10)") i, object%par(i)
  end do
end if
call object%helicity_selection%write (u)
call object%qcd%write (u)
end subroutine prc_omega_write

```

Temporarily store the parameter array inside the `prc_omega` object, so we can use it later during the actual initialization. Also store threshold and cutoff for helicity selection.

```

<Omega interface: prc_omega: TBP>+≡
  procedure :: set_parameters => prc_omega_set_parameters

<Omega interface: procedures>+≡
  subroutine prc_omega_set_parameters (prc_omega, model, &
    helicity_selection, qcd, use_color_factors)
    class(prc_omega_t), intent(inout) :: prc_omega
    class(model_data_t), intent(in), target, optional :: model
    type(helicity_selection_t), intent(in), optional :: helicity_selection
    type(qcd_t), intent(in), optional :: qcd
    logical, intent(in), optional :: use_color_factors
    if (present (model)) then
      if (.not. allocated (prc_omega%par)) &
        allocate (prc_omega%par (model%get_n_real ()))
      call model%real_parameters_to_c_array (prc_omega%par)
    end if
    if (present (helicity_selection)) then
      prc_omega%helicity_selection = helicity_selection
    end if
    if (present (qcd)) then
      prc_omega%qcd = qcd
    end if
    if (present (use_color_factors)) then
      prc_omega%use_color_factors = use_color_factors
    end if
  end subroutine prc_omega_set_parameters

```

To fully initialize the process core, we perform base initialization, then initialize the external matrix element code.

This procedure overrides the `init` method of the base type, which we nevertheless can access via its binding `base_init`. When done, we have an allocated

driver. The driver will call the `init` procedure for the external matrix element, and thus transfer the parameter set to where it finally belongs.

If requested, we initialize the helicity selection counter.

```

<Omega interface: prc omega: TBP>+≡
  procedure :: init => prc_omega_init

<Omega interface: procedures>+≡
  subroutine prc_omega_init (object, def, lib, id, i_component)
    class(prc_omega_t), intent(inout) :: object
    class(prc_core_def_t), intent(in), target :: def
    type(process_library_t), intent(in), target :: lib
    type(string_t), intent(in) :: id
    integer, intent(in) :: i_component
    call object%base_init (def, lib, id, i_component)
    call object%activate_parameters ()
  end subroutine prc_omega_init

```

Activate the stored parameters by transferring them to the external matrix element. Also reset the helicity selection, if requested.

```

<Omega interface: prc omega: TBP>+≡
  procedure :: activate_parameters => prc_omega_activate_parameters

<Omega interface: procedures>+≡
  subroutine prc_omega_activate_parameters (object)
    class (prc_omega_t), intent(inout) :: object
    if (allocated (object%driver)) then
      if (allocated (object%par)) then
        select type (driver => object%driver)
          type is (omega_driver_t)
            if (associated (driver%init)) call driver%init (object%par)
          end select
      else
        call msg_bug ("prc_omega_activate: parameter set is not allocated")
      end if
      call object%reset_helicity_selection ()
    else
      call msg_bug ("prc_omega_activate: driver is not allocated")
    end if
  end subroutine prc_omega_activate_parameters

```

The O'MEGA process is an independent process which needs its own Monte Carlo parameter set for integration.

```

<Omega interface: prc omega: TBP>+≡
  procedure :: needs_mcset => prc_omega_needs_mcset

<Omega interface: procedures>+≡
  function prc_omega_needs_mcset (object) result (flag)
    class(prc_omega_t), intent(in) :: object
    logical :: flag
    flag = .true.
  end function prc_omega_needs_mcset

```

There is only one term for this tree-level process.

```

<Omega interface: prc omega: TBP>+=
  procedure :: get_n_terms => prc_omega_get_n_terms

<Omega interface: procedures>+=
  function prc_omega_get_n_terms (object) result (n)
    class(prc_omega_t), intent(in) :: object
    integer :: n
    n = 1
  end function prc_omega_get_n_terms

```

Tell whether a particular combination of flavor, helicity, color is allowed. Here we have to consult the matrix-element driver.

```

<Omega interface: prc omega: TBP>+=
  procedure :: is_allowed => prc_omega_is_allowed

<Omega interface: procedures>+=
  function prc_omega_is_allowed (object, i_term, f, h, c) result (flag)
    class(prc_omega_t), intent(in) :: object
    integer, intent(in) :: i_term, f, h, c
    logical :: flag
    logical(c_bool) :: cflag
    select type (driver => object%driver)
      type is (omega_driver_t)
        call driver%is_allowed (f, h, c, cflag)
        flag = cflag
    end select
  end function prc_omega_is_allowed

```

Transfer the generated momenta directly to the hard interaction in the (only) term. We assume that everything has been set up correctly, so the array fits.

We don't reset the `new_kinematics` flag here. This has to be done explicitly by the caller (`reset_new_kinematics`) when a new kinematics configuration is to be considered.

```

<Omega interface: prc omega: TBP>+=
  procedure :: compute_hard_kinematics => prc_omega_compute_hard_kinematics

<Omega interface: procedures>+=
  subroutine prc_omega_compute_hard_kinematics &
    (object, p_seed, i_term, int_hard, core_state)
    class(prc_omega_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(in) :: p_seed
    integer, intent(in) :: i_term
    type(interaction_t), intent(inout) :: int_hard
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    call int_hard%set_momenta (p_seed)
  end subroutine prc_omega_compute_hard_kinematics

```

This procedure is not called for `prc_omega_t`, just a placeholder.

```

<Omega interface: prc omega: TBP>+=
  procedure :: compute_eff_kinematics => prc_omega_compute_eff_kinematics

```

```

<Omega interface: procedures>+≡
  subroutine prc_omega_compute_eff_kinematics &
    (object, i_term, int_hard, int_eff, core_state)
    class(prc_omega_t), intent(in) :: object
    integer, intent(in) :: i_term
    type(interaction_t), intent(in) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_omega_compute_eff_kinematics

```

Recover the momenta within the hard interaction. For tree-level processes, this is a trivial copy of the incoming seed and outgoing effective momenta. The effective interaction is a pointer to the hard interaction, so the latter is ignored.

```

<Omega interface: prc omega: TBP>+≡
  procedure :: recover_kinematics => prc_omega_recover_kinematics

<Omega interface: tests>≡
  subroutine prc_omega_recover_kinematics &
    (object, p_seed, int_hard, int_eff, core_state)
    class(prc_omega_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(inout) :: p_seed
    type(interaction_t), intent(inout) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    integer :: n_in
    n_in = int_eff%get_n_in ()
    call int_eff%set_momenta (p_seed(1:n_in), outgoing = .false.)
    p_seed(n_in+1:) = int_eff%get_momenta (outgoing = .true.)
  end subroutine prc_omega_recover_kinematics

```

Reset the helicity selection counters and start counting zero helicities. We assume that the `helicity_selection` object is allocated. Otherwise, reset and switch off helicity counting.

In the test routine, the driver is allocated but the driver methods are not. Therefore, guard against a disassociated method.

```

<Omega interface: prc omega: TBP>+≡
  procedure :: reset_helicity_selection => prc_omega_reset_helicity_selection

<Omega interface: procedures>+≡
  subroutine prc_omega_reset_helicity_selection (object)
    class(prc_omega_t), intent(inout) :: object
    select type (driver => object%driver)
    type is (omega_driver_t)
      if (associated (driver%reset_helicity_selection)) then
        if (object%helicity_selection%active) then
          call driver%reset_helicity_selection &
            (real (object%helicity_selection%threshold, &
              c_default_float), &
              int (object%helicity_selection%cutoff, c_int))
        else
          call driver%reset_helicity_selection &
            (0._c_default_float, 0_c_int)
        end if
      end if
    end select
  end subroutine prc_omega_reset_helicity_selection

```

```

        end if
    end select
end subroutine prc_omega_reset_helicity_selection

```

Compute the amplitude. For the tree-level process, we can ignore the scale settings. The term index j is also irrelevant.

We first call `new_event` for the given momenta (which we must unpack), then retrieve the amplitude value for the given quantum numbers.

If the `core_state` status flag is present, we can make sure that we call `new_event` only once for a given kinematics. After the first call, we unset the `new_kinematics` flag.

The core objects computes the appropriate α_s value via the `qcd` subobject, taking into account the provided `fac_scale` value. However, if the extra parameter `alpha_qcd_forced` is allocated, it overrides this setting.

The `is_allowed` query is not redundant, since the status may change during the run if helicities are switched off.

```

<Omega interface: prc omega: TBP>+≡
  procedure :: compute_amplitude => prc_omega_compute_amplitude

<Omega interface: procedures>+≡
  function prc_omega_compute_amplitude &
    (object, j, p, f, h, c, fac_scale, ren_scale, alpha_qcd_forced, &
     core_state) result (amp)
    class(prc_omega_t), intent(in) :: object
    integer, intent(in) :: j
    type(vector4_t), dimension(:), intent(in) :: p
    integer, intent(in) :: f, h, c
    real(default), intent(in) :: fac_scale, ren_scale
    real(default), intent(in), allocatable :: alpha_qcd_forced
    class(prc_core_state_t), intent(inout), allocatable, optional :: core_state
    real(default) :: alpha_qcd
    complex(default) :: amp
    integer :: n_tot, i
    real(c_default_float), dimension(:, :), allocatable :: parray
    complex(c_default_complex) :: camp
    logical :: new_event
    select type (driver => object%driver)
    type is (omega_driver_t)
      new_event = .true.
      if (present (core_state)) then
        if (allocated (core_state)) then
          select type (core_state)
          type is (omega_state_t)
            new_event = core_state%new_kinematics
            core_state%new_kinematics = .false.
          end select
        end if
      end if
    end if
    if (new_event) then
      if (allocated (object%qcd%alpha)) then
        if (allocated (alpha_qcd_forced)) then
          alpha_qcd = alpha_qcd_forced
        else

```

```

        alpha_qcd = object%qcd%alpha%get (fac_scale)
    end if
    call driver%update_alpha_s (alpha_qcd)
    if (present (core_state)) then
        if (allocated (core_state)) then
            select type (core_state)
            type is (omega_state_t)
                core_state%alpha_qcd = alpha_qcd
            end select
        end if
    end if
    end if
    end if
    n_tot = object%data%n_in + object%data%n_out
    allocate (parray (0:3, n_tot))
    do i = 1, n_tot
        parray(:,i) = vector4_get_components (p(i))
    end do
    call driver%new_event (parray)
end if
if (object%is_allowed (1, f, h, c)) then
    call driver%get_amplitude &
        (int (f, c_int), int (h, c_int), int (c, c_int), camp)
    amp = camp
else
    amp = 0
end if
end select
end function prc_omega_compute_amplitude

```

After the amplitude has been computed, we may read off the current value of α_s . This works only if α_s varies, and if the workspace `core_state` is present which stores this value.

```

<Omega interface: prc omega: TBP>+≡
    procedure :: get_alpha_s => prc_omega_get_alpha_s

<Omega interface: procedures>+≡
    function prc_omega_get_alpha_s (object, core_state) result (alpha)
        class(prc_omega_t), intent(in) :: object
        class(prc_core_state_t), intent(in), allocatable :: core_state
        real(default) :: alpha
        alpha = -1
        if (allocated (object%qcd%alpha) .and. allocated (core_state)) then
            select type (core_state)
            type is (omega_state_t)
                alpha = core_state%alpha_qcd
            end select
        end if
    end function prc_omega_get_alpha_s

```

16.3.6 Test

This is the master for calling self-test procedures. There is a separate test for testing O'MEGA diagram generation as this depends on a working analysis setup.

```

<Omega interface: public>+≡
    public :: prc_omega_test

<Omega interface: tests>+≡
    subroutine prc_omega_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Omega interface: execute tests>
    end subroutine prc_omega_test

<Omega interface: public>+≡
    public :: prc_omega_diags_test

<Omega interface: tests>+≡
    subroutine prc_omega_diags_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Omega interface: execute diags tests>
    end subroutine prc_omega_diags_test

```

Generate, compile and load a simple process matrix element

The process is $e^+e^- \rightarrow \mu^+\mu^-$ for vanishing masses and $e = 0.3$. We initialize the process, build the library, and compute a particular matrix element for momenta of unit energy and right-angle scattering. The matrix element, as it happens, is equal to e^2 . (Note that are no conversion factors applied, so this result is exact.)

For GNU make, makeflags is set to -j1. This eliminates a potential clash with a -j<n> flag if this test is called from a parallel make.

```

<Omega interface: execute tests>≡
    call test (prc_omega_1, "prc_omega_1", &
        "build and load simple OMEGA process", &
        u, results)

<Omega interface: tests>+≡
    subroutine prc_omega_1 (u)
        integer, intent(in) :: u
        type(process_library_t) :: lib
        class(prc_core_def_t), allocatable :: def
        type(process_def_entry_t), pointer :: entry
        type(os_data_t) :: os_data
        type(string_t) :: model_name
        type(string_t), dimension(:), allocatable :: prt_in, prt_out
        type(process_constants_t) :: data
        class(prc_core_driver_t), allocatable :: driver
        integer, parameter :: cdf = c_default_float
        integer, parameter :: ci = c_int
        real(cdf), dimension(4) :: par
        real(cdf), dimension(0:3,4) :: p

```

```

logical(c_bool) :: flag
complex(c_default_complex) :: amp
integer :: i

write (u, "(A)")  "* Test output: prc_omega_1"
write (u, "(A)")  "* Purpose: create a simple process with OMega"
write (u, "(A)")  "*           build a library, link, load, and &
                        &access the matrix element"
write (u, "(A)")

write (u, "(A)")  "* Initialize a process library with one entry"
write (u, "(A)")
call lib%init (var_str ("omega1"))
call os_data_init (os_data)

model_name = "QED"
allocate (prt_in (2), prt_out (2))
prt_in = [var_str ("e+"), var_str ("e-")]
prt_out = [var_str ("m+"), var_str ("m-")]

allocate (omega_omega_def_t :: def)
select type (def)
type is (omega_omega_def_t)
    call def%init (model_name, prt_in, prt_out)
end select
allocate (entry)
call entry%init (var_str ("omega1_a"), model_name = model_name, &
    n_in = 2, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
    prt_in = new_prt_spec (prt_in), &
    prt_out = new_prt_spec (prt_out), &
    method = var_str ("omega"), &
    variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure library"
write (u, "(A)")
call lib%configure (os_data)

write (u, "(A)")  "* Write makefile"
write (u, "(A)")
call lib%write_makefile (os_data, force = .true.)

write (u, "(A)")  "* Clean any left-over files"
write (u, "(A)")
call lib%clean (os_data, distclean = .false.)

write (u, "(A)")  "* Write driver"
write (u, "(A)")
call lib%write_driver (force = .true.)

write (u, "(A)")  "* Write process source code, compile, link, load"
write (u, "(A)")
call lib%load (os_data)

```



```

call lib%write (u, libpath = .false.)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active          = ", &
    lib%is_active ()
write (u, "(1x,A,I0)")  "n_processes        = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Constants of omega1_a_i1:"
write (u, "(A)")

call lib%connect_process (var_str ("omega1_a"), 1, data, driver)

write (u, "(1x,A,A)")  "component ID      = ", char (data%id)
write (u, "(1x,A,A)")  "model name        = ", char (data%model_name)
write (u, "(1x,A,A,A)")  "md5sum          = '", data%md5sum, "'"
write (u, "(1x,A,L1)")  "openmp supported = ", data%openmp_supported
write (u, "(1x,A,I0)")  "n_in = ", data%n_in
write (u, "(1x,A,I0)")  "n_out = ", data%n_out
write (u, "(1x,A,I0)")  "n_flv = ", data%n_flv
write (u, "(1x,A,I0)")  "n_hel = ", data%n_hel
write (u, "(1x,A,I0)")  "n_col = ", data%n_col
write (u, "(1x,A,I0)")  "n_cin = ", data%n_cin
write (u, "(1x,A,I0)")  "n_cf = ", data%n_cf
write (u, "(1x,A,10(1x,I0))")  "flv state =", data%flv_state
write (u, "(1x,A,10(1x,I2))")  "hel state =", data%hel_state(:,1)
do i = 2, 16
    write (u, "(12x,4(1x,I2))")  data%hel_state(:,i)
end do
write (u, "(1x,A,10(1x,I0))")  "col state =", data%col_state
write (u, "(1x,A,10(1x,L1))")  "ghost flag =", data%ghost_flag
write (u, "(1x,A,10(1x,F5.3))")  "color factors =", data%color_factors
write (u, "(1x,A,10(1x,I0))")  "cf index =", data%cf_index

write (u, "(A)")
write (u, "(A)")  "* Set parameters for omega1_a and initialize:"
write (u, "(A)")

par = [0.3_cdf, 0.0_cdf, 0.0_cdf, 0.0_cdf]
write (u, "(2x,A,F6.4)")  "ee = ", par(1)
write (u, "(2x,A,F6.4)")  "me = ", par(2)
write (u, "(2x,A,F6.4)")  "mmu = ", par(3)
write (u, "(2x,A,F6.4)")  "mtau = ", par(4)

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &

```

```

        1.0_cdf, 0.0_cdf, 0.0_cdf, 1.0_cdf, &
        1.0_cdf, 0.0_cdf, 0.0_cdf, -1.0_cdf, &
        1.0_cdf, 1.0_cdf, 0.0_cdf, 0.0_cdf, &
        1.0_cdf, -1.0_cdf, 0.0_cdf, 0.0_cdf &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.4))") "p", i, " =", p(:,i)
end do

select type (driver)
type is (omega_driver_t)
    call driver%init (par)

    call driver%new_event (p)

    write (u, "(A)")
    write (u, "(A)")  "* Compute matrix element:"
    write (u, "(A)")

    call driver%is_allowed (1_ci, 6_ci, 1_ci, flag)
    write (u, "(1x,A,L1)") "is_allowed (1, 6, 1) = ", flag

    call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
    write (u, "(1x,A,1x,E11.4)") "|amp (1, 6, 1)| =", abs (amp)
end select

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_omega_1"

end subroutine prc_omega_1

```

Check prc_omega_t wrapper and options

The process is $e^-e^+ \rightarrow e^-e^+$ for vanishing masses and $e = 0.3$. We build the library using the high-level procedure `omega_make_process_component` and the “black box” `prc_omega_t` object. Two variants with different settings for restrictions and OpenMP.

For GNU make, `makeflags` is set to `-j1`. This eliminates a potential clash with a `-j<n>` flag if this test is called from a parallel make.

<Omega interface: execute tests>+≡

```

call test (prc_omega_2, "prc_omega_2", &
    "OMega option passing", &
    u, results)

```

<Omega interface: tests>+≡

```

subroutine prc_omega_2 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(process_def_entry_t), pointer :: entry
    type(os_data_t) :: os_data
    type(string_t) :: model_name

```

```

class(model_data_t), pointer :: model
class(vars_t), pointer :: vars
type(string_t), dimension(:), allocatable :: prt_in, prt_out
type(string_t) :: restrictions
type(process_component_def_t), pointer :: config
type(prc_omega_t) :: prc1, prc2
type(process_constants_t) :: data
integer, parameter :: cdf = c_default_float
integer, parameter :: ci = c_int
real(cdf), dimension(:), allocatable :: par
real(cdf), dimension(0:3,4) :: p
complex(c_default_complex) :: amp
integer :: i
logical :: exist

write (u, "(A)")  "* Test output: prc_omega_2"
write (u, "(A)")  "*   Purpose: create simple processes with OMega"
write (u, "(A)")  "*               use the prc_omega wrapper for this"
write (u, "(A)")  "*               and check OMega options"
write (u, "(A)")

write (u, "(A)")  "* Initialize a process library with two entries, &
&different options."
write (u, "(A)")  "* (1) e- e+ -> e- e+  &
&(all diagrams, no OpenMP, report progress)"
write (u, "(A)")  "* (2) e- e+ -> e- e+  &
&(s-channel only, with OpenMP, report progress to file)"

call lib%init (var_str ("omega2"))
call os_data_init (os_data)

model_name = "QED"
call prepare_model (model, model_name, vars)

allocate (prt_in (2), prt_out (2))
prt_in = [var_str ("e-"), var_str ("e+")]
prt_out = prt_in
restrictions = "3+4~A"

allocate (entry)
call entry%init (var_str ("omega2_a"), &
model, n_in = 2, n_components = 2)

call omega_make_process_component (entry, 1, &
model_name, prt_in, prt_out, &
report_progress=.true.)
call omega_make_process_component (entry, 2, &
model_name, prt_in, prt_out, &
restrictions=restrictions, openmp_support=.true., &
extra_options=var_str ("-fusion:progress_file omega2.log"))

call lib%append (entry)

write (u, "(A)")

```

```

write (u, "(A)")  "* Remove left-over file"
write (u, "(A)")

call delete_file ("omega2.log")
inquire (file="omega2.log", exist=exist)
write (u, "(1x,A,L1)")  "omega2.log exists = ", exist

write (u, "(A)")
write (u, "(A)")  "* Build and load library"

call lib%configure (os_data)
call lib%write_makefile (os_data, force = .true.)
call lib%clean (os_data, distclean = .false.)
call lib%write_driver (force = .true.)
call lib%load (os_data)

write (u, "(A)")
write (u, "(A)")  "* Check extra output of OMega"
write (u, "(A)")

inquire (file="omega2.log", exist=exist)
write (u, "(1x,A,L1)")  "omega2.log exists = ", exist

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active          = ", &
    lib%is_active ()
write (u, "(1x,A,I0)")  "n_processes        = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Set parameters for omega2_a and initialize:"
write (u, "(A)")

call vars%set_rval (var_str ("ee"), 0.3_default)
call vars%set_rval (var_str ("me"), 0._default)
call vars%set_rval (var_str ("mmu"), 0._default)
call vars%set_rval (var_str ("mtau"), 0._default)
allocate (par (model%get_n_real ()))
call model%real_parameters_to_c_array (par)

write (u, "(2x,A,F6.4)")  "ee   = ", par(1)
write (u, "(2x,A,F6.4)")  "me   = ", par(2)
write (u, "(2x,A,F6.4)")  "mmu  = ", par(3)
write (u, "(2x,A,F6.4)")  "mtau = ", par(4)

call prc1%set_parameters (model)
call prc2%set_parameters (model)

write (u, "(A)")
write (u, "(A)")  "* Constants of omega2_a_i1:"
write (u, "(A)")

```

```

config => lib%get_component_def_ptr (var_str ("omega2_a"), 1)
call prc1%init (config%get_core_def_ptr (), &
    lib, var_str ("omega2_a"), 1)
call prc1%get_constants (data, 1)

write (u, "(1x,A,A)") "component ID      = ", &
    char (data%id)
write (u, "(1x,A,L1)") "openmp supported = ", &
    data%openmp_supported
write (u, "(1x,A,A,A)") "model name      = ', &
    char (data%model_name), "' "

write (u, "(A)")
write (u, "(A)")  "* Constants of omega2_a_i2:"
write (u, "(A)")

config => lib%get_component_def_ptr (var_str ("omega2_a"), 2)
call prc2%init (config%get_core_def_ptr (), &
    lib, var_str ("omega2_a"), 2)
call prc2%get_constants (data, 1)

write (u, "(1x,A,A)") "component ID      = ", &
    char (data%id)
write (u, "(1x,A,L1)") "openmp supported = ", &
    data%openmp_supported
write (u, "(1x,A,A,A)") "model name      = ', &
    char (data%model_name), "' "

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    1.0_cdf, 0.0_cdf, 0.0_cdf, 1.0_cdf, &
    1.0_cdf, 0.0_cdf, 0.0_cdf, -1.0_cdf, &
    1.0_cdf, 1.0_cdf, 0.0_cdf, 0.0_cdf, &
    1.0_cdf, -1.0_cdf, 0.0_cdf, 0.0_cdf &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.4))") "p", i, " =", p(:,i)
end do

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element:"
write (u, "(A)")

select type (driver => prc1%driver)
type is (omega_driver_t)
    call driver%new_event (p)
    call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
    write (u, "(2x,A,1x,E11.4)") "(1) |amp (1, 6, 1)| =", abs (amp)
end select

```

```

select type (driver => prc2%driver)
type is (omega_driver_t)
  call driver%new_event (p)
  call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
  write (u, "(2x,A,1x,E11.4)") "(2) |amp (1, 6, 1)| =", abs (amp)
end select

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
  1.0_cdf, 0.0_cdf, 0.0_cdf, 1.0_cdf, &
  1.0_cdf, 0.0_cdf, 0.0_cdf, -1.0_cdf, &
  1.0_cdf, sqrt(0.5_cdf), 0.0_cdf, sqrt(0.5_cdf), &
  1.0_cdf, -sqrt(0.5_cdf), 0.0_cdf, -sqrt(0.5_cdf) &
], [4,4])
do i = 1, 4
  write (u, "(2x,A,I0,A,4(1x,F7.4))") "p", i, " =", p(:,i)
end do

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element:"
write (u, "(A)")

select type (driver => prc1%driver)
type is (omega_driver_t)
  call driver%new_event (p)
  call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
  write (u, "(2x,A,1x,E11.4)") "(1) |amp (1, 6, 1)| =", abs (amp)
end select

select type (driver => prc2%driver)
type is (omega_driver_t)
  call driver%new_event (p)
  call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
  write (u, "(2x,A,1x,E11.4)") "(2) |amp (1, 6, 1)| =", abs (amp)
end select

call lib%final ()
call cleanup_model(model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_omega_2"

end subroutine prc_omega_2

```

Check helicity selection

The process is $e^-e^+ \rightarrow e^-e^+$ for vanishing masses. We call the matrix element several times to verify the switching off of irrelevant helicities.

(Omega interface: execute tests)+≡

```

call test (prc_omega_3, "prc_omega_3", &
          "helicity selection", &
          u, results)
(Omega interface: tests)+≡
subroutine prc_omega_3 (u)
  integer, intent(in) :: u
  type(process_library_t), target :: lib
  type(process_def_entry_t), pointer :: entry
  type(os_data_t) :: os_data
  type(string_t) :: model_name
  class(model_data_t), pointer :: model
  class(vars_t), pointer :: vars => null ()
  type(string_t), dimension(:), allocatable :: prt_in, prt_out
  type(process_component_def_t), pointer :: config
  type(prc_omega_t) :: prc1
  type(process_constants_t) :: data
  integer, parameter :: cdf = c_default_float
  real(cdf), dimension(:), allocatable :: par
  real(cdf), dimension(0:3,4) :: p
  type(helicity_selection_t) :: helicity_selection
  integer :: i, h

  write (u, "(A)")  "* Test output: prc_omega_3"
  write (u, "(A)")  "*   Purpose: create simple process with OMega"
  write (u, "(A)")  "*               and check helicity selection"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize a process library."
  write (u, "(A)")  "* (1) e- e+ -> e- e+   (all diagrams, no OpenMP)"

  call lib%init (var_str ("omega3"))
  call os_data_init (os_data)

  model_name = "QED"
  call prepare_model (model, model_name, vars)

  allocate (prt_in (2), prt_out (2))
  prt_in = [var_str ("e-"), var_str ("e+")]
  prt_out = prt_in

  allocate (entry)
  call entry%init (var_str ("omega3_a"), &
                  model, n_in = 2, n_components = 1)

  call omega_make_process_component (entry, 1, &
                                    model_name, prt_in, prt_out)
  call lib%append (entry)

  write (u, "(A)")
  write (u, "(A)")  "* Build and load library"

  call lib%configure (os_data)
  call lib%write_makefile (os_data, force = .true.)
  call lib%clean (os_data, distclean = .false.)

```

```

call lib%write_driver (force = .true.)
call lib%load (os_data)

write (u, "(A)")
write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active           = ", &
    lib%is_active ()
write (u, "(1x,A,I0)")  "n_processes         = ", &
    lib%get_n_processes ()

write (u, "(A)")
write (u, "(A)")  "* Set parameters for omega3_a and initialize:"
write (u, "(A)")

call vars%set_rval (var_str ("ee"), 0.3_default)
call vars%set_rval (var_str ("me"), 0._default)
call vars%set_rval (var_str ("mmu"), 0._default)
call vars%set_rval (var_str ("mtau"), 0._default)
allocate (par (model%get_n_real ()))
call model%real_parameters_to_c_array (par)

write (u, "(2x,A,F6.4)")  "ee   = ", par(1)
write (u, "(2x,A,F6.4)")  "me   = ", par(2)
write (u, "(2x,A,F6.4)")  "mmu  = ", par(3)
write (u, "(2x,A,F6.4)")  "mtau = ", par(4)

call prc1%set_parameters (model, helicity_selection)

write (u, "(A)")
write (u, "(A)")  "* Helicity states of omega3_a_i1:"
write (u, "(A)")

config => lib%get_component_def_ptr (var_str ("omega3_a"), 1)
call prc1%init (config%get_core_def_ptr (), &
    lib, var_str ("omega3_a"), 1)
call prc1%get_constants (data, 1)

do i = 1, data%n_hel
    write (u, "(3x,I2,':',4(1x,I2))") i, data%hel_state(:,i)
end do

write (u, "(A)")
write (u, "(A)")  "* Initially allowed helicities:"
write (u, "(A)")

write (u, "(4x,16(1x,I2))") [(h, h = 1, data%n_hel)]
write (u, "(4x)", advance = "no")
do h = 1, data%n_hel
    write (u, "(2x,L1)", advance = "no") prc1%is_allowed (1, 1, h, 1)
end do
write (u, "(A)")

```



```

write (u, "(A)")
write (u, "(A)")  "* Reset helicity selection (cutoff = 4)"
write (u, "(A)")

helicity_selection%active = .true.
helicity_selection%threshold = 1e10_default
helicity_selection%cutoff = 4
call helicity_selection%write (u)

call prc1%set_parameters (model, helicity_selection)
call prc1%reset_helicity_selection ()

write (u, "(A)")
write (u, "(A)")  "* Allowed helicities:"
write (u, "(A)")

write (u, "(4x,16(1x,I2))") [(h, h = 1, data%n_hel)]
write (u, "(4x)", advance = "no")
do h = 1, data%n_hel
    write (u, "(2x,L1)", advance = "no") prc1%is_allowed (1, 1, h, 1)
end do
write (u, "(A)")

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    1.0_cdf, 0.0_cdf, 0.0_cdf, 1.0_cdf, &
    1.0_cdf, 0.0_cdf, 0.0_cdf, -1.0_cdf, &
    1.0_cdf, 1.0_cdf, 0.0_cdf, 0.0_cdf, &
    1.0_cdf, -1.0_cdf, 0.0_cdf, 0.0_cdf &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.4))") "p", i, " =", p(:,i)
end do

write (u, "(A)")
write (u, "(A)")  "* Compute scattering matrix 5 times"
write (u, "(A)")

write (u, "(4x,16(1x,I2))") [(h, h = 1, data%n_hel)]

select type (driver => prc1%driver)
type is (omega_driver_t)
    do i = 1, 5
        call driver%new_event (p)
        write (u, "(2x,I2)", advance = "no") i
        do h = 1, data%n_hel
            write (u, "(2x,L1)", advance = "no") prc1%is_allowed (1, 1, h, 1)
        end do
        write (u, "(A)")
    end do
end select

```

```

write (u, "(A)")
write (u, "(A)")  "* Reset helicity selection again"
write (u, "(A)")

call prc1%activate_parameters ()

write (u, "(A)")  "* Allowed helicities:"
write (u, "(A)")

write (u, "(4x,16(1x,I2))") [(h, h = 1, data%n_hel)]
write (u, "(4x)", advance = "no")
do h = 1, data%n_hel
  write (u, "(2x,L1)", advance = "no") prc1%is_allowed (1, 1, h, 1)
end do
write (u, "(A)")

call lib%final ()
call cleanup_model (model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_omega_3"

end subroutine prc_omega_3

```

QCD coupling

The process is $u\bar{u} \rightarrow d\bar{d}$ for vanishing masses. We compute the amplitude for a fixed configuration once, then reset α_s , then compute again.

For GNU make, makeflags is set to -j1. This eliminates a potential clash with a -j<n> flag if this test is called from a parallel make.

```

<Omega interface: execute tests>+=
  call test (prc_omega_4, "prc_omega_4", &
    "update QCD alpha", &
    u, results)

<Omega interface: tests>+=
  subroutine prc_omega_4 (u)
    integer, intent(in) :: u
    type(process_library_t) :: lib
    class(prc_core_def_t), allocatable :: def
    type(process_def_entry_t), pointer :: entry
    type(os_data_t) :: os_data
    type(string_t) :: model_name
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    type(process_constants_t) :: data
    class(prc_core_driver_t), allocatable :: driver
    integer, parameter :: cdf = c_default_float
    integer, parameter :: ci = c_int
    real(cdf), dimension(6) :: par
    real(cdf), dimension(0:3,4) :: p
    logical(c_bool) :: flag
    complex(c_default_complex) :: amp

```

```

integer :: i
real(cdf) :: alpha_s

write (u, "(A)")  "* Test output: prc_omega_4"
write (u, "(A)")  "*   Purpose: create a QCD process with OMega"
write (u, "(A)")  "*               and check alpha_s dependence"
write (u, "(A)")

write (u, "(A)")  "* Initialize a process library with one entry"
write (u, "(A)")
call lib%init (var_str ("prc_omega_4_lib"))
call os_data_init (os_data)

model_name = "QCD"
allocate (prt_in (2), prt_out (2))
prt_in = [var_str ("u"), var_str ("ubar")]
prt_out = [var_str ("d"), var_str ("dbar")]

allocate (omega_omega_def_t :: def)
select type (def)
type is (omega_omega_def_t)
    call def%init (model_name, prt_in, prt_out)
end select
allocate (entry)
call entry%init (var_str ("prc_omega_4_p"), model_name = model_name, &
    n_in = 2, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
    prt_in  = new_prt_spec (prt_in), &
    prt_out = new_prt_spec (prt_out), &
    method  = var_str ("omega"), &
    variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure and compile process"
write (u, "(A)")
call lib%configure (os_data)
call lib%write_makefile (os_data, force = .true.)
call lib%clean (os_data, distclean = .false.)
call lib%write_driver (force = .true.)
call lib%load (os_data)

write (u, "(A)")  "* Probe library API:"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active = ", lib%is_active ()

write (u, "(A)")
write (u, "(A)")  "* Set parameters:"
write (u, "(A)")

alpha_s = 0.1178_cdf

par = [alpha_s, 0._cdf, 0._cdf, 0._cdf, 173.1_cdf, 1.523_cdf]
write (u, "(2x,A,F8.4)")  "alpha_s = ", par(1)

```

```

write (u, "(2x,A,F8.4)") "ms      = ", par(2)
write (u, "(2x,A,F8.4)") "mc      = ", par(3)
write (u, "(2x,A,F8.4)") "mb      = ", par(4)
write (u, "(2x,A,F8.4)") "mtop    = ", par(5)
write (u, "(2x,A,F8.4)") "wtop    = ", par(6)

write (u, "(A)")
write (u, "(A)")  "* Set kinematics:"
write (u, "(A)")

p = reshape ([ &
    100.0_cdf, 0.0_cdf, 0.0_cdf, 100.0_cdf, &
    100.0_cdf, 0.0_cdf, 0.0_cdf,-100.0_cdf, &
    100.0_cdf, 100.0_cdf, 0.0_cdf, 0.0_cdf, &
    100.0_cdf,-100.0_cdf, 0.0_cdf, 0.0_cdf &
    ], [4,4])
do i = 1, 4
    write (u, "(2x,A,I0,A,4(1x,F7.1))") "p", i, " =", p(:,i)
end do

call lib%connect_process (var_str ("prc_omega_4_p"), 1, data, driver)

select type (driver)
type is (omega_driver_t)
    call driver%init (par)

    write (u, "(A)")
    write (u, "(A)")  "* Compute matrix element:"
    write (u, "(A)")

    call driver%new_event (p)

    call driver%is_allowed (1_ci, 6_ci, 1_ci, flag)
    write (u, "(1x,A,L1)") "is_allowed (1, 6, 1) = ", flag

    call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
    write (u, "(1x,A,1x,E11.4)") "|amp (1, 6, 1)| =", abs (amp)

    write (u, "(A)")
    write (u, "(A)")  "* Double alpha_s and compute matrix element again:"
    write (u, "(A)")

    call driver%update_alpha_s (2 * alpha_s)
    call driver%new_event (p)

    call driver%is_allowed (1_ci, 6_ci, 1_ci, flag)
    write (u, "(1x,A,L1)") "is_allowed (1, 6, 1) = ", flag

    call driver%get_amplitude (1_ci, 6_ci, 1_ci, amp)
    write (u, "(1x,A,1x,E11.4)") "|amp (1, 6, 1)| =", abs (amp)
end select

call lib%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_omega_4"

end subroutine prc_omega_4

```

Amplitude and QCD coupling

The same process as before. Here, we initialize with a running α_s coupling and compute twice with different scales. We use the high-level method `compute_amplitude`.

```

<Omega interface: execute tests>+≡
  call test (prc_omega_5, "prc_omega_5", &
    "running QCD alpha", &
    u, results)

<Omega interface: tests>+≡
  subroutine prc_omega_5 (u)
    integer, intent(in) :: u
    type(process_library_t) :: lib
    class(prc_core_def_t), allocatable :: def
    type(process_component_def_t), pointer :: cdef_ptr
    class(prc_core_def_t), pointer :: def_ptr
    type(process_def_entry_t), pointer :: entry
    type(os_data_t) :: os_data
    class(model_data_t), pointer :: model
    type(string_t) :: model_name
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    type(qcd_t) :: qcd
    class(prc_core_t), allocatable :: core
    class(prc_core_state_t), allocatable :: core_state
    type(vector4_t), dimension(4) :: p
    complex(default) :: amp
    real(default) :: fac_scale
    real(default), allocatable :: alpha_qcd_forced
    integer :: i

    write (u, "(A)")  "* Test output: prc_omega_5"
    write (u, "(A)")  "* Purpose: create a QCD process with OMega"
    write (u, "(A)")  "*           and check alpha_s dependence"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize a process library with one entry"
    write (u, "(A)")
    call lib%init (var_str ("prc_omega_5_lib"))
    call os_data_init (os_data)

    model_name = "QCD"
    call prepare_model (model, model_name)

    allocate (prt_in (2), prt_out (2))
    prt_in = [var_str ("u"), var_str ("ubar")]
    prt_out = [var_str ("d"), var_str ("dbar")]

    allocate (omega_omega_def_t :: def)

```

```

select type (def)
type is (omega_omega_def_t)
  call def%init (model_name, prt_in, prt_out)
end select
allocate (entry)
call entry%init (var_str ("prc_omega_5_p"), model_name = model_name, &
  n_in = 2, n_components = 1)
call entry%import_component (1, n_out = size (prt_out), &
  prt_in = new_prt_spec (prt_in), &
  prt_out = new_prt_spec (prt_out), &
  method = var_str ("omega"), &
  variant = def)
call lib%append (entry)

write (u, "(A)")  "* Configure and compile process"
write (u, "(A)")
call lib%configure (os_data)
call lib%write_makefile (os_data, force = .true.)
call lib%clean (os_data, distclean = .false.)
call lib%write_driver (force = .true.)
call lib%load (os_data)

write (u, "(A)")  "* Probe library API"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active = ", lib%is_active ()

write (u, "(A)")
write (u, "(A)")  "* Set kinematics"
write (u, "(A)")

p(1) = vector4_moving (100._default, 100._default, 3)
p(2) = vector4_moving (100._default,-100._default, 3)
p(3) = vector4_moving (100._default, 100._default, 1)
p(4) = vector4_moving (100._default,-100._default, 1)
do i = 1, 4
  call vector4_write (p(i), u)
end do

write (u, "(A)")
write (u, "(A)")  "* Setup QCD data"
write (u, "(A)")

allocate (alpha_qcd_from_scale_t :: qcd%alpha)

write (u, "(A)")  "* Setup process core"
write (u, "(A)")

allocate (prc_omega_t :: core)
cdef_ptr => lib%get_component_def_ptr (var_str ("prc_omega_5_p"), 1)
def_ptr => cdef_ptr%get_core_def_ptr ()

select type (core)
type is (prc_omega_t)

```

```

call core%allocate_workspace (core_state)
call core%set_parameters (model, qcd = qcd)
call core%init (def_ptr, lib, var_str ("prc_omega_5_p"), 1)
call core%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute matrix element"
write (u, "(A)")

fac_scale = 100
write (u, "(1x,A,F4.0)")  "factorization scale = ", fac_scale

amp = core%compute_amplitude &
      (1, p, 1, 6, 1, fac_scale, 100._default, alpha_qcd_forced)

write (u, "(1x,A,1x,E11.4)")  "|amp (1, 6, 1)| =", abs (amp)

write (u, "(A)")
write (u, "(A)")  "* Modify factorization scale and &
                  &compute matrix element again"
write (u, "(A)")

fac_scale = 200
write (u, "(1x,A,F4.0)")  "factorization scale = ", fac_scale

amp = core%compute_amplitude &
      (1, p, 1, 6, 1, fac_scale, 100._default, alpha_qcd_forced)

write (u, "(1x,A,1x,E11.4)")  "|amp (1, 6, 1)| =", abs (amp)

write (u, "(A)")
write (u, "(A)")  "* Set alpha(QCD) directly and &
                  &compute matrix element again"
write (u, "(A)")

allocate (alpha_qcd_forced, source = 0.1_default)
write (u, "(1x,A,F6.4)")  "alpha_qcd = ", alpha_qcd_forced

amp = core%compute_amplitude &
      (1, p, 1, 6, 1, fac_scale, 100._default, alpha_qcd_forced)

write (u, "(1x,A,1x,E11.4)")  "|amp (1, 6, 1)| =", abs (amp)

end select

call lib%final ()
call cleanup_model (model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_omega_5"

end subroutine prc_omega_5

```

Generate matrix element diagrams

The same process as before. No amplitude is computed here, instead we just generate Feynman (and color flow) diagrams, and check whether PS and PDF files have been generated. This test is only run if event analysis is possible.

```
(Omega interface: execute diags tests)≡
  call test (prc_omega_diags_1, "prc_omega_diags_1", &
    "generate Feynman diagrams", &
    u, results)

(Omega interface: tests)+≡
  subroutine prc_omega_diags_1 (u)
    integer, intent(in) :: u
    type(process_library_t) :: lib
    class(prc_core_def_t), allocatable :: def
    type(process_def_entry_t), pointer :: entry
    type(os_data_t) :: os_data
    type(string_t) :: model_name
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    type(string_t) :: diags_file, pdf_file, ps_file
    logical :: exist, exist_pdf, exist_ps
    integer :: iostat, u_diags
    character(128) :: buffer

    write (u, "(A)")  "* Test output: prc_omega_diags_1"
    write (u, "(A)")  "* Purpose: generate Feynman diagrams"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize a process library with one entry"
    write (u, "(A)")
    call lib%init (var_str ("prc_omega_diags_1_lib"))
    call os_data_init (os_data)

    model_name = "SM"

    allocate (prt_in (2), prt_out (2))
    prt_in = [var_str ("u"), var_str ("ubar")]
    prt_out = [var_str ("d"), var_str ("dbar")]

    allocate (omega_omega_def_t :: def)
    select type (def)
    type is (omega_omega_def_t)
      call def%init (model_name, prt_in, prt_out, &
        diags = .true., diags_color = .true.)
    end select
    allocate (entry)
    call entry%init (var_str ("prc_omega_diags_1_p"), model_name = model_name, &
      n_in = 2, n_components = 1)
    call entry%import_component (1, n_out = size (prt_out), &
      prt_in = new_prt_spec (prt_in), &
      prt_out = new_prt_spec (prt_out), &
      method = var_str ("omega"), &
      variant = def)
    call lib%append (entry)
```



```

write (u, "(A)")  "* Configure and compile process"
write (u, "(A)")  "    and generate diagrams"
write (u, "(A)")
call lib%configure (os_data)
call lib%write_makefile (os_data, force = .true., testflag = .true.)
call lib%clean (os_data, distclean = .false.)
call lib%write_driver (force = .true.)
call lib%load (os_data)

write (u, "(A)")  "* Probe library API"
write (u, "(A)")

write (u, "(1x,A,L1)")  "is active = ", lib%is_active ()

write (u, "(A)")  "* Check produced diagram files"
write (u, "(A)")

diags_file = "prc_omega_diags_1_p_i1_diags.tex"
ps_file    = "prc_omega_diags_1_p_i1_diags.ps"
pdf_file   = "prc_omega_diags_1_p_i1_diags.pdf"
inquire (file = char (diags_file), exist = exist)
if (exist) then
    u_diags = free_unit ()
    open (u_diags, file = char (diags_file), action = "read", status = "old")
    iostat = 0
    do while (iostat == 0)
        read (u_diags, "(A)", iostat = iostat)  buffer
        if (iostat == 0) write (u, "(A)")  trim (buffer)
    end do
    close (u_diags)
else
    write (u, "(A)")  "[Feynman diagrams LaTeX file is missing]"
end if
inquire (file = char (ps_file), exist = exist_ps)
if (exist_ps) then
    write (u, "(A)")  "[Feynman diagrams Postscript file exists and is nonempty]"
else
    write (u, "(A)")  "[Feynman diagrams Postscript file is missing/non-regular]"
end if
inquire (file = char (pdf_file), exist = exist_pdf)
if (exist_pdf) then
    write (u, "(A)")  "[Feynman diagrams PDF file exists and is nonempty]"
else
    write (u, "(A)")  "[Feynman diagrams PDF file is missing/non-regular]"
end if

write (u, "(A)")
write (u, "(A)")  "* Cleanup"
write (u, "(A)")

call lib%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: prc_omega_diags_1"

```

```
end subroutine prc_omega_diags_1
```

Chapter 17

Generic Event Handling

Event records allow the MC to communicate with the outside world. The event record should exhibit the observable contents of a physical event. We should be able to read and write events. The actual implementation of the event need not be defined yet, for that purpose.

We have the following basic modules:

event_base Abstract base type for event records. The base type contains a reference to a **particle_set_t** object as the event core, and it holds some data that we should always expect, such as the squared matrix element and event weight.

eio_data Transparent container for the metadata of an event sample.

eio_base Abstract base type for event-record input and output. The implementations of this base type represent specific event I/O formats.

These are the implementation modules:

eio_checkpoints Auxiliary output format. The only purpose is to provide screen diagnostics during event output.

eio_weights Print some event summary data, no details. The main use if for testing purposes.

hep_common Implements traditional HEP common blocks that are (still) used by some of the event I/O formats below.

hepmc_interface Access particle objects of the HepMC package. Functional only if this package is linked.

lcio_interface Access objects of the LCIO package. Functional only if this package is linked.

hep_events Interface between the event record and the common blocks.

eio_ascii Collection of event output formats that write ASCII files.

eio_lhef LHEF for input and output.

eio_stdhep Support for the StdHEP format (binary, machine-independent).

eio-hepmc Support for the HepMC format (C++).

eio-lcio Support for the LCIO format (C++).

17.1 Generic Event Handling

We introduce events first in form of an abstract type, together with some utilities. Abstract events can be used by other modules, in particular event I/O, without introducing an explicit dependency on the event implementation.

<event_base.f90>≡
<File header>

```
module event_base

    use kinds
    <Use strings>
    use string_utils, only: lower_case
    use diagnostics
    use model_data
    use particles

    <Standard module head>

    <Event base: public>

    <Event base: parameters>

    <Event base: types>

    <Event base: interfaces>

    contains

    <Event base: procedures>

end module event_base
```

17.1.1 generic event type

<Event base: public>≡
public :: generic_event_t

<Event base: types>≡
type, abstract :: generic_event_t
private
logical :: particle_set_is_valid = .false.
type(particle_set_t), pointer :: particle_set => null ()
logical :: sqme_ref_known = .false.
real(default) :: sqme_ref = 0
logical :: sqme_prc_known = .false.
real(default) :: sqme_prc = 0
logical :: weight_ref_known = .false.
real(default) :: weight_ref = 0

```

    logical :: weight_prc_known = .false.
    real(default) :: weight_prc = 0
    logical :: excess_prc_known = .false.
    real(default) :: excess_prc = 0
    integer :: n_alt = 0
    logical :: sqme_alt_known = .false.
    real(default), dimension(:), allocatable :: sqme_alt
    logical :: weight_alt_known = .false.
    real(default), dimension(:), allocatable :: weight_alt
contains
  <Event base: generic event: TBP>
end type generic_event_t

```

17.1.2 Initialization

This determines the number of alternate weights and sqme values.

```

<Event base: generic event: TBP>≡
  procedure :: base_init => generic_event_init

<Event base: procedures>≡
  subroutine generic_event_init (event, n_alt)
    class(generic_event_t), intent(out) :: event
    integer, intent(in) :: n_alt
    event%n_alt = n_alt
    allocate (event%sqme_alt (n_alt))
    allocate (event%weight_alt (n_alt))
  end subroutine generic_event_init

```

17.1.3 Access particle set

The particle set is the core of the event. We allow access to it via a pointer, and we maintain the information whether the particle set is valid, i.e., has been filled with meaningful data.

```

<Event base: generic event: TBP>+≡
  procedure :: has_valid_particle_set => generic_event_has_valid_particle_set
  procedure :: accept_particle_set => generic_event_accept_particle_set
  procedure :: discard_particle_set => generic_event_discard_particle_set

<Event base: procedures>+≡
  function generic_event_has_valid_particle_set (event) result (flag)
    class(generic_event_t), intent(in) :: event
    logical :: flag
    flag = event%particle_set_is_valid
  end function generic_event_has_valid_particle_set

  subroutine generic_event_accept_particle_set (event)
    class(generic_event_t), intent(inout) :: event
    event%particle_set_is_valid = .true.
  end subroutine generic_event_accept_particle_set

  subroutine generic_event_discard_particle_set (event)

```

```

class(generic_event_t), intent(inout) :: event
event%particle_set_is_valid = .false.
end subroutine generic_event_discard_particle_set

```

These procedures deal with the particle set directly. Return the pointer:

```

(Event base: generic event: TBP)+≡
  procedure :: get_particle_set_ptr => generic_event_get_particle_set_ptr

(Event base: procedures)+≡
  function generic_event_get_particle_set_ptr (event) result (ptr)
    class(generic_event_t), intent(in) :: event
    type(particle_set_t), pointer :: ptr
    ptr => event%particle_set
  end function generic_event_get_particle_set_ptr

```

Let it point to some existing particle set:

```

(Event base: generic event: TBP)+≡
  procedure :: link_particle_set => generic_event_link_particle_set

(Event base: procedures)+≡
  subroutine generic_event_link_particle_set (event, particle_set)
    class(generic_event_t), intent(inout) :: event
    type(particle_set_t), intent(in), target :: particle_set
    event%particle_set => particle_set
    call event%accept_particle_set ()
  end subroutine generic_event_link_particle_set

```

17.1.4 Access sqme and weight

There are several incarnations: the current value, a reference value, alternate values.

```

(Event base: generic event: TBP)+≡
  procedure :: sqme_prc_is_known => generic_event_sqme_prc_is_known
  procedure :: sqme_ref_is_known => generic_event_sqme_ref_is_known
  procedure :: sqme_alt_is_known => generic_event_sqme_alt_is_known
  procedure :: weight_prc_is_known => generic_event_weight_prc_is_known
  procedure :: weight_ref_is_known => generic_event_weight_ref_is_known
  procedure :: weight_alt_is_known => generic_event_weight_alt_is_known
  procedure :: excess_prc_is_known => generic_event_excess_prc_is_known

(Event base: procedures)+≡
  function generic_event_sqme_prc_is_known (event) result (flag)
    class(generic_event_t), intent(in) :: event
    logical :: flag
    flag = event%sqme_prc_known
  end function generic_event_sqme_prc_is_known

  function generic_event_sqme_ref_is_known (event) result (flag)
    class(generic_event_t), intent(in) :: event
    logical :: flag
    flag = event%sqme_ref_known
  end function generic_event_sqme_ref_is_known

```

```

function generic_event_sqme_alt_is_known (event) result (flag)
  class(generic_event_t), intent(in) :: event
  logical :: flag
  flag = event%sqme_alt_known
end function generic_event_sqme_alt_is_known

function generic_event_weight_prc_is_known (event) result (flag)
  class(generic_event_t), intent(in) :: event
  logical :: flag
  flag = event%weight_prc_known
end function generic_event_weight_prc_is_known

function generic_event_weight_ref_is_known (event) result (flag)
  class(generic_event_t), intent(in) :: event
  logical :: flag
  flag = event%weight_ref_known
end function generic_event_weight_ref_is_known

function generic_event_weight_alt_is_known (event) result (flag)
  class(generic_event_t), intent(in) :: event
  logical :: flag
  flag = event%weight_alt_known
end function generic_event_weight_alt_is_known

function generic_event_excess_prc_is_known (event) result (flag)
  class(generic_event_t), intent(in) :: event
  logical :: flag
  flag = event%excess_prc_known
end function generic_event_excess_prc_is_known

```

(Event base: generic event: TBP)+≡
 procedure :: get_n_alt => generic_event_get_n_alt

(Event base: procedures)+≡
 function generic_event_get_n_alt (event) result (n)
 class(generic_event_t), intent(in) :: event
 integer :: n
 n = event%n_alt
end function generic_event_get_n_alt

(Event base: generic event: TBP)+≡
 procedure :: get_sqme_prc => generic_event_get_sqme_prc
 procedure :: get_sqme_ref => generic_event_get_sqme_ref
 generic :: get_sqme_alt => &
 generic_event_get_sqme_alt_0, generic_event_get_sqme_alt_1
 procedure :: generic_event_get_sqme_alt_0
 procedure :: generic_event_get_sqme_alt_1
 procedure :: get_weight_prc => generic_event_get_weight_prc
 procedure :: get_weight_ref => generic_event_get_weight_ref
 generic :: get_weight_alt => &
 generic_event_get_weight_alt_0, generic_event_get_weight_alt_1
 procedure :: generic_event_get_weight_alt_0

```

procedure :: generic_event_get_weight_alt_1
procedure :: get_excess_prc => generic_event_get_excess_prc

(Event base: procedures)+≡

function generic_event_get_sqme_prc (event) result (sqme)
  class(generic_event_t), intent(in) :: event
  real(default) :: sqme
  if (event%sqme_prc_known) then
    sqme = event%sqme_prc
  else
    sqme = 0
  end if
end function generic_event_get_sqme_prc

function generic_event_get_sqme_ref (event) result (sqme)
  class(generic_event_t), intent(in) :: event
  real(default) :: sqme
  if (event%sqme_ref_known) then
    sqme = event%sqme_ref
  else
    sqme = 0
  end if
end function generic_event_get_sqme_ref

function generic_event_get_sqme_alt_0 (event, i) result (sqme)
  class(generic_event_t), intent(in) :: event
  integer, intent(in) :: i
  real(default) :: sqme
  if (event%sqme_alt_known) then
    sqme = event%sqme_alt(i)
  else
    sqme = 0
  end if
end function generic_event_get_sqme_alt_0

function generic_event_get_sqme_alt_1 (event) result (sqme)
  class(generic_event_t), intent(in) :: event
  real(default), dimension(event%n_alt) :: sqme
  sqme = event%sqme_alt
end function generic_event_get_sqme_alt_1

function generic_event_get_weight_prc (event) result (weight)
  class(generic_event_t), intent(in) :: event
  real(default) :: weight
  if (event%weight_prc_known) then
    weight = event%weight_prc
  else
    weight = 0
  end if
end function generic_event_get_weight_prc

function generic_event_get_weight_ref (event) result (weight)
  class(generic_event_t), intent(in) :: event
  real(default) :: weight
  if (event%weight_ref_known) then

```



```

        weight = event%weight_ref
    else
        weight = 0
    end if
end function generic_event_get_weight_ref

function generic_event_get_weight_alt_0 (event, i) result (weight)
    class(generic_event_t), intent(in) :: event
    integer, intent(in) :: i
    real(default) :: weight
    if (event%weight_alt_known) then
        weight = event%weight_alt(i)
    else
        weight = 0
    end if
end function generic_event_get_weight_alt_0

function generic_event_get_weight_alt_1 (event) result (weight)
    class(generic_event_t), intent(in) :: event
    real(default), dimension(event%n_alt) :: weight
    weight = event%weight_alt
end function generic_event_get_weight_alt_1

function generic_event_get_excess_prc (event) result (excess)
    class(generic_event_t), intent(in) :: event
    real(default) :: excess
    if (event%excess_prc_known) then
        excess = event%excess_prc
    else
        excess = 0
    end if
end function generic_event_get_excess_prc

```

(Event base: generic event: TBP)+≡

```

procedure :: set_sqme_prc => generic_event_set_sqme_prc
procedure :: set_sqme_ref => generic_event_set_sqme_ref
procedure :: set_sqme_alt => generic_event_set_sqme_alt
procedure :: set_weight_prc => generic_event_set_weight_prc
procedure :: set_weight_ref => generic_event_set_weight_ref
procedure :: set_weight_alt => generic_event_set_weight_alt
procedure :: set_excess_prc => generic_event_set_excess_prc

```

(Event base: procedures)+≡

```

subroutine generic_event_set_sqme_prc (event, sqme)
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: sqme
    event%sqme_prc = sqme
    event%sqme_prc_known = .true.
end subroutine generic_event_set_sqme_prc

subroutine generic_event_set_sqme_ref (event, sqme)
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: sqme
    event%sqme_ref = sqme

```

```

    event%sqme_ref_known = .true.
end subroutine generic_event_set_sqme_ref

subroutine generic_event_set_sqme_alt (event, sqme)
    class(generic_event_t), intent(inout) :: event
    real(default), dimension(:), intent(in) :: sqme
    event%sqme_alt = sqme
    event%sqme_alt_known = .true.
end subroutine generic_event_set_sqme_alt

subroutine generic_event_set_weight_prc (event, weight)
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: weight
    event%weight_prc = weight
    event%weight_prc_known = .true.
end subroutine generic_event_set_weight_prc

subroutine generic_event_set_weight_ref (event, weight)
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: weight
    event%weight_ref = weight
    event%weight_ref_known = .true.
end subroutine generic_event_set_weight_ref

subroutine generic_event_set_weight_alt (event, weight)
    class(generic_event_t), intent(inout) :: event
    real(default), dimension(:), intent(in) :: weight
    event%weight_alt = weight
    event%weight_alt_known = .true.
end subroutine generic_event_set_weight_alt

subroutine generic_event_set_excess_prc (event, excess)
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: excess
    event%excess_prc = excess
    event%excess_prc_known = .true.
end subroutine generic_event_set_excess_prc

```

Set the appropriate entry directly.

(Event base: generic event: TBP)+≡

```

    procedure :: set => generic_event_set

```

(Event base: procedures)+≡

```

    subroutine generic_event_set (event, &
        weight_ref, weight_prc, weight_alt, &
        excess_prc, &
        sqme_ref, sqme_prc, sqme_alt)
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in), optional :: weight_ref, weight_prc
    real(default), intent(in), optional :: sqme_ref, sqme_prc
    real(default), dimension(:), intent(in), optional :: sqme_alt, weight_alt
    real(default), intent(in), optional :: excess_prc
    if (present (sqme_prc)) then
        call event%set_sqme_prc (sqme_prc)
    end if

```

```

end if
if (present (sqme_ref)) then
  call event%set_sqme_ref (sqme_ref)
end if
if (present (sqme_alt)) then
  call event%set_sqme_alt (sqme_alt)
end if
if (present (weight_prc)) then
  call event%set_weight_prc (weight_prc)
end if
if (present (weight_ref)) then
  call event%set_weight_ref (weight_ref)
end if
if (present (weight_alt)) then
  call event%set_weight_alt (weight_alt)
end if
if (present (excess_prc)) then
  call event%set_excess_prc (excess_prc)
end if
end subroutine generic_event_set

```

17.1.5 Pure Virtual Methods

These procedures can only be implemented in the concrete implementation.

Output (verbose, depending on parameters).

(Event base: generic event: TBP)+≡
 procedure (generic_event_write), deferred :: write

(Event base: interfaces)≡
 abstract interface
 subroutine generic_event_write (object, unit, &
 show_process, show_transforms, &
 show_decay, verbose, testflag)
 import
 class(generic_event_t), intent(in) :: object
 integer, intent(in), optional :: unit
 logical, intent(in), optional :: show_process
 logical, intent(in), optional :: show_transforms
 logical, intent(in), optional :: show_decay
 logical, intent(in), optional :: verbose
 logical, intent(in), optional :: testflag
 end subroutine generic_event_write
end interface

Generate an event, based on a selector index `i_mci`, and optionally on an extra set of random numbers `r`. For the main bunch of random numbers that the generator needs, the event object should contain its own generator.

(Event base: generic event: TBP)+≡
 procedure (generic_event_generate), deferred :: generate

(Event base: interfaces)+≡
 abstract interface

```

subroutine generic_event_generate (event, i_mci, r)
  import
  class(generic_event_t), intent(inout) :: event
  integer, intent(in) :: i_mci
  real(default), dimension(:), intent(in), optional :: r
end subroutine generic_event_generate
end interface

```

Alternative : inject a particle set that is supposed to represent the hard process.
How this determines the event, is dependent on the event structure, therefore
this is a deferred method.

⟨Event base: generic event: TBP⟩+≡

```

  procedure (generic_event_set_hard_particle_set), deferred :: &
    set_hard_particle_set

```

⟨Event base: interfaces⟩+≡

```

  abstract interface
    subroutine generic_event_set_hard_particle_set (event, particle_set)
      import
      class(generic_event_t), intent(inout) :: event
      type(particle_set_t), intent(in) :: particle_set
    end subroutine generic_event_set_hard_particle_set
  end interface

```

Evaluate any expressions associated with the event. No argument needed.

⟨Event base: generic event: TBP⟩+≡

```

  procedure (generic_event_handler), deferred :: evaluate_expressions

```

⟨Event base: interfaces⟩+≡

```

  abstract interface
    subroutine generic_event_handler (event)
      import
      class(generic_event_t), intent(inout) :: event
    end subroutine generic_event_handler
  end interface

```

Select internal parameters

⟨Event base: generic event: TBP⟩+≡

```

  procedure (generic_event_select), deferred :: select

```

⟨Event base: interfaces⟩+≡

```

  abstract interface
    subroutine generic_event_select (event, i_mci, i_term, channel)
      import
      class(generic_event_t), intent(inout) :: event
      integer, intent(in) :: i_mci, i_term, channel
    end subroutine generic_event_select
  end interface

```

Return a pointer to the model for the currently active process.

⟨Event base: generic event: TBP⟩+≡

```

  procedure (generic_event_get_model_ptr), deferred :: get_model_ptr

```

```

(Event base: interfaces)+≡
abstract interface
  function generic_event_get_model_ptr (event) result (model)
    import
    class(generic_event_t), intent(in) :: event
    class(model_data_t), pointer :: model
  end function generic_event_get_model_ptr
end interface

```

Return data used by external event formats.

```

(Event base: generic event: TBP)+≡
  procedure (generic_event_get_index), deferred :: get_index
  procedure (generic_event_get_fac_scale), deferred :: get_fac_scale
  procedure (generic_event_get_alpha_s), deferred :: get_alpha_s

```

```

(Event base: interfaces)+≡
abstract interface
  function generic_event_get_index (event) result (index)
    import
    class(generic_event_t), intent(in) :: event
    integer :: index
  end function generic_event_get_index
end interface

abstract interface
  function generic_event_get_fac_scale (event) result (fac_scale)
    import
    class(generic_event_t), intent(in) :: event
    real(default) :: fac_scale
  end function generic_event_get_fac_scale
end interface

abstract interface
  function generic_event_get_alpha_s (event) result (alpha_s)
    import
    class(generic_event_t), intent(in) :: event
    real(default) :: alpha_s
  end function generic_event_get_alpha_s
end interface

```

Set data used by external event formats.

```

(Event base: generic event: TBP)+≡
  procedure (generic_event_set_alpha_qcd_forced), deferred :: &
    set_alpha_qcd_forced
  procedure (generic_event_set_scale_forced), deferred :: &
    set_scale_forced

(Event base: interfaces)+≡
abstract interface
  subroutine generic_event_set_alpha_qcd_forced (event, alpha_qcd)
    import
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: alpha_qcd
  end subroutine generic_event_set_alpha_qcd_forced

```

```

end interface

abstract interface
  subroutine generic_event_set_scale_forced (event, scale)
    import
    class(generic_event_t), intent(inout) :: event
    real(default), intent(in) :: scale
  end subroutine generic_event_set_scale_forced
end interface

```

17.1.6 Utilities

Applying this, current event contents are marked as incomplete but are not deleted. In particular, the initialization is kept.

```

<Event base: generic event: TBP>+≡
  procedure :: reset => generic_event_reset
  procedure :: base_reset => generic_event_reset

```

```

<Event base: procedures>+≡
  subroutine generic_event_reset (event)
    class(generic_event_t), intent(inout) :: event
    call event%discard_particle_set ()
    event%sqme_ref_known = .false.
    event%sqme_prc_known = .false.
    event%sqme_alt_known = .false.
    event%weight_ref_known = .false.
    event%weight_prc_known = .false.
    event%weight_alt_known = .false.
    event%excess_prc_known = .false.
  end subroutine generic_event_reset

```

Pacify particle set.

```

<Event base: generic event: TBP>+≡
  procedure :: pacify_particle_set => generic_event_pacify_particle_set

<Event base: procedures>+≡
  subroutine generic_event_pacify_particle_set (event)
    class(generic_event_t), intent(inout) :: event
    if (event%has_valid_particle_set ()) call pacify (event%particle_set)
  end subroutine generic_event_pacify_particle_set

```

17.1.7 Event normalization

The parameters for event normalization. For unweighted events, `NORM_UNIT` is intended as default, while for weighted events, it is `NORM_SIGMA`.

Note: the unit test for this is in `eio_data_2` below.

```

<Event base: parameters>≡
  integer, parameter, public :: NORM_UNDEFINED = 0
  integer, parameter, public :: NORM_UNIT = 1
  integer, parameter, public :: NORM_N_EVT = 2

```

```

integer, parameter, public :: NORM_SIGMA = 3
integer, parameter, public :: NORM_S_N = 4

```

These functions translate between the user representation and the internal one.

(Event base: public)+≡

```

public :: event_normalization_mode
public :: event_normalization_string

```

(Event base: procedures)+≡

```

function event_normalization_mode (string, unweighted) result (mode)
  integer :: mode
  type(string_t), intent(in) :: string
  logical, intent(in) :: unweighted
  select case (lower_case (char (string)))
  case ("auto")
    if (unweighted) then
      mode = NORM_UNIT
    else
      mode = NORM_SIGMA
    end if
  case ("1")
    mode = NORM_UNIT
  case ("1/n")
    mode = NORM_N_EVT
  case ("sigma")
    mode = NORM_SIGMA
  case ("sigma/n")
    mode = NORM_S_N
  case default
    call msg_fatal ("Event normalization: unknown value '" &
      // char (string) // "'")
  end select
end function event_normalization_mode

function event_normalization_string (norm_mode) result (string)
  integer, intent(in) :: norm_mode
  type(string_t) :: string
  select case (norm_mode)
  case (NORM_UNDEFINED); string = "[undefined]"
  case (NORM_UNIT);      string = "'1'"
  case (NORM_N_EVT);     string = "'1/n'"
  case (NORM_SIGMA);     string = "'sigma'"
  case (NORM_S_N);       string = "'sigma/n'"
  case default;          string = "???"
  end select
end function event_normalization_string

```

We place this here as a generic helper, so we can update event weights whenever we need, not just in connection with an event sample data object.

(Event base: public)+≡

```

public :: event_normalization_update

```

(Event base: procedures)+≡

```

subroutine event_normalization_update (weight, sigma, n, mode_new, mode_old)

```

```

real(default), intent(inout) :: weight
real(default), intent(in) :: sigma
integer, intent(in) :: n
integer, intent(in) :: mode_new, mode_old
if (mode_new /= mode_old) then
  if (sigma > 0 .and. n > 0) then
    weight = weight / factor (mode_old) * factor (mode_new)
  else
    call msg_fatal ("Event normalization update: null sample")
  end if
end if
contains
function factor (mode)
  real(default) :: factor
  integer, intent(in) :: mode
  select case (mode)
  case (NORM_UNIT);   factor = 1._default
  case (NORM_N_EVT);  factor = 1._default / n
  case (NORM_SIGMA);  factor = sigma
  case (NORM_S_N);    factor = sigma / n
  case default
    call msg_fatal ("Event normalization update: undefined mode")
  end select
end function factor
end subroutine event_normalization_update

```

17.2 Event Sample Data

We define a simple and transparent container for (meta)data that are associated with an event sample.

```

⟨eio_data.f90⟩≡
  ⟨File header⟩

  module eio_data

    use kinds
    use io_units
    ⟨Use strings⟩
    use unit_tests
    use diagnostics

    use event_base

    ⟨Standard module head⟩

    ⟨EIO data: public⟩

    ⟨EIO data: types⟩

  contains

```


<EIO data: procedures>

<EIO data: tests>

end module eio_data

17.2.1 Event Sample Data

These are data that apply to an event sample as a whole. They are given in an easily portable form (no fancy structure) and are used for initializing event formats.

There are two MD5 sums here. `md5sum_proc` depends only on the definition of the contributing processes. A sample with matching checksum can be rescanned with modified model parameters, beam structure etc, to recalculate observables. `md5sum_config` includes all relevant data. Rescanning a sample with matching checksum will produce identical observables. (A third checksum might be added which depends on the event sample itself. This is not needed, so far.)

If alternate weights are part of the event sample (`n_alt` nonzero), there is a configuration MD5 sum for each of them.

<EIO data: public>≡

public :: event_sample_data_t

<EIO data: types>≡

```
type :: event_sample_data_t
  character(32) :: md5sum_prc = ""
  character(32) :: md5sum_cfg = ""
  logical :: unweighted = .true.
  logical :: negative_weights = .false.
  integer :: norm_mode = NORM_UNDEFINED
  integer :: n_beam = 0
  integer, dimension(2) :: pdg_beam = 0
  real(default), dimension(2) :: energy_beam = 0
  integer :: n_proc = 0
  integer :: n_evt = 0
  integer :: split_n_evt = 0
  integer :: split_n_kbytes = 0
  integer :: split_index = 0
  real(default) :: total_cross_section = 0
  integer, dimension(:), allocatable :: proc_num_id
  integer :: n_alt = 0
  character(32), dimension(:), allocatable :: md5sum_alt
  real(default), dimension(:), allocatable :: cross_section
  real(default), dimension(:), allocatable :: error
contains
  <EIO data: event sample data: TBP>
end type event_sample_data_t
```

Initialize: allocate for the number of processes

<EIO data: event sample data: TBP>≡

procedure :: init => event_sample_data_init

```

<EIO data: procedures>≡
subroutine event_sample_data_init (data, n_proc, n_alt)
  class(event_sample_data_t), intent(out) :: data
  integer, intent(in) :: n_proc
  integer, intent(in), optional :: n_alt
  data%n_proc = n_proc
  allocate (data%proc_num_id (n_proc), source = 0)
  allocate (data%cross_section (n_proc), source = 0._default)
  allocate (data%error (n_proc), source = 0._default)
  if (present (n_alt)) then
    data%n_alt = n_alt
    allocate (data%md5sum_alt (n_alt))
    data%md5sum_alt = ""
  end if
end subroutine event_sample_data_init

```

Output.

```

<EIO data: event sample data: TBP>+≡
  procedure :: write => event_sample_data_write

<EIO data: procedures>+≡
subroutine event_sample_data_write (data, unit)
  class(event_sample_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  integer :: u, i
  u = given_output_unit (unit)
  write (u, "(1x,A)") "Event sample properties:"
  write (u, "(3x,A,A,A)") "MD5 sum (proc) = ", data%md5sum_prc, ""
  write (u, "(3x,A,A,A)") "MD5 sum (config) = ", data%md5sum_cfg, ""
  write (u, "(3x,A,L1)") "unweighted = ", data%unweighted
  write (u, "(3x,A,L1)") "negative weights = ", data%negative_weights
  write (u, "(3x,A,A)") "normalization = ", &
    char (event_normalization_string (data%norm_mode))
  write (u, "(3x,A,I0)") "number of beams = ", data%n_beam
  write (u, "(5x,A,2(1x,I19))") "PDG = ", &
    data%pdg_beam(:data%n_beam)
  write (u, "(5x,A,2(1x,ES19.12))") "Energy = ", &
    data%energy_beam(:data%n_beam)
  if (data%n_evt > 0) then
    write (u, "(3x,A,I0)") "number of events = ", data%n_evt
  end if
  if (data%total_cross_section /= 0) then
    write (u, "(3x,A,ES19.12)") "total cross sec. = ", &
      data%total_cross_section
  end if
  write (u, "(3x,A,I0)") "num of processes = ", data%n_proc
  do i = 1, data%n_proc
    write (u, "(3x,A,I0)") "Process #", data%proc_num_id (i)
    select case (data%n_beam)
    case (1)
      write (u, "(5x,A,ES19.12)") "Width = ", data%cross_section(i)
    case (2)
      write (u, "(5x,A,ES19.12)") "CSec = ", data%cross_section(i)
    end select
  end do
end subroutine event_sample_data_write

```

```

        write (u, "(5x,A,ES19.12)") "Error = ", data%error(i)
    end do
    if (data%n_alt > 0) then
        write (u, "(3x,A,I0)") "num of alt wgt  = ", data%n_alt
        do i = 1, data%n_alt
            write (u, "(5x,A,A,A,1x,I0)") "MD5 sum (cfg) = ', &
                data%md5sum_alt(i), "'", i
        end do
    end if
end subroutine event_sample_data_write

```

17.2.2 Unit tests

```

<EIO data: public>+≡
    public :: eio_data_test

<EIO data: tests>≡
    subroutine eio_data_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <EIO data: execute tests>
end subroutine eio_data_test

```

Event Sample Data

Print the contents of a sample data block.

```

<EIO data: execute tests>≡
    call test (eio_data_1, "eio_data_1", &
        "event sample data", &
        u, results)

<EIO data: tests>+≡
    subroutine eio_data_1 (u)
        integer, intent(in) :: u
        type(event_sample_data_t) :: data

        write (u, "(A)")  "* Test output: eio_data_1"
        write (u, "(A)")  "* Purpose: display event sample data"
        write (u, "(A)")

        write (u, "(A)")  "* Decay process, one component"
        write (u, "(A)")

        call data%init (1, 1)
        data%n_beam = 1
        data%pdg_beam(1) = 25
        data%energy_beam(1) = 125

        data%norm_mode = NORM_UNIT

        data%proc_num_id = [42]
        data%cross_section = [1.23e-4_default]
    end subroutine eio_data_1

```

[illegible]

Check the functions for translating modes and updating weights.

```

s = "auto"
unweighted = .true.
write (u, "(1x,A,1x,L1,1x,A)") char (s), unweighted, &
char (event_normalization_string &
(event_normalization_mode (s, unweighted)))
s = "AUTO"
unweighted = .false.
write (u, "(1x,A,1x,L1,1x,A)") char (s), unweighted, &
char (event_normalization_string &
(event_normalization_mode (s, unweighted)))

unweighted = .true.

s = "1"
write (u, "(2(1x,A))") char (s), char (event_normalization_string &
(event_normalization_mode (s, unweighted)))
s = "1/n"
write (u, "(2(1x,A))") char (s), char (event_normalization_string &
(event_normalization_mode (s, unweighted)))
s = "Sigma"
write (u, "(2(1x,A))") char (s), char (event_normalization_string &
(event_normalization_mode (s, unweighted)))
s = "sigma/N"
write (u, "(2(1x,A))") char (s), char (event_normalization_string &
(event_normalization_mode (s, unweighted)))

write (u, "(A)")
write (u, "(A)")  "* Normalization update"
write (u, "(A)")

sigma = 5
n = 2

w0 = 1

w = w0
call event_normalization_update (w, sigma, n, NORM_UNIT, NORM_UNIT)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_N_EVT, NORM_UNIT)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_SIGMA, NORM_UNIT)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_S_N, NORM_UNIT)
write (u, "(2(F6.3))") w0, w

write (u, *)

w0 = 0.5

w = w0
call event_normalization_update (w, sigma, n, NORM_UNIT, NORM_N_EVT)

```

```

write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_N_EVT, NORM_N_EVT)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_SIGMA, NORM_N_EVT)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_S_N, NORM_N_EVT)
write (u, "(2(F6.3))") w0, w

write (u, *)

w0 = 5.0

w = w0
call event_normalization_update (w, sigma, n, NORM_UNIT, NORM_SIGMA)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_N_EVT, NORM_SIGMA)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_SIGMA, NORM_SIGMA)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_S_N, NORM_SIGMA)
write (u, "(2(F6.3))") w0, w

write (u, *)

w0 = 2.5

w = w0
call event_normalization_update (w, sigma, n, NORM_UNIT, NORM_S_N)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_N_EVT, NORM_S_N)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_SIGMA, NORM_S_N)
write (u, "(2(F6.3))") w0, w
w = w0
call event_normalization_update (w, sigma, n, NORM_S_N, NORM_S_N)
write (u, "(2(F6.3))") w0, w

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_data_2"

end subroutine eio_data_2

```

17.3 Abstract I/O Handler

This module defines an abstract object for event I/O and the associated methods.

There are `output` and `input` methods which write or read a single event from/to the I/O stream, respectively. The I/O stream itself may be a file, a common block, or an externally linked structure, depending on the concrete implementation.

A `write` method prints the current content of the implementation-dependent event record in human-readable form.

The `init_in/init_out` and `final` prepare and finalize the I/O stream, respectively. There is also a `switch_inout` method which turns an input stream into an output stream where events can be appended.

Optionally, output files can be split in chunks of well-defined size. The `split_out` method takes care of this.

```
<eio_base.f90>≡  
  <File header>  
  
  module eio_base  
  
    use kinds  
    use io_units  
    <Use strings>  
    use unit_tests  
    use diagnostics  
    use lorentz  
    use model_data  
    use particles  
    use event_base  
    use eio_data  
  
    <Standard module head>  
  
    <EIO base: public>  
  
    <EIO base: types>  
  
    <EIO base: interfaces>  
  
    <EIO base: test types>  
  
    contains  
  
    <EIO base: procedures>  
  
    <EIO base: tests>  
  
  end module eio_base
```

17.3.1 Type

We can assume that most implementations will need the file extension as a fixed string and, if they support file splitting, the current file index.

The fallback model is useful for implementations that are able to read unknown files which may contain hadrons etc., not in the current hard-interaction model.

```
<EIO base: public>≡
    public :: eio_t

<EIO base: types>≡
    type, abstract :: eio_t
        type(string_t) :: sample
        type(string_t) :: extension
        type(string_t) :: filename
        logical :: has_file = .false.
        logical :: split = .false.
        integer :: split_n_evt = 0
        integer :: split_n_kbytes = 0
        integer :: split_index = 0
        integer :: split_count = 0
        class(model_data_t), pointer :: fallback_model => null ()
    contains
        <EIO base: eio: TBP>
    end type eio_t
```

Write to screen. If possible, this should display the contents of the current event, i.e., the last one that was written or read.

```
<EIO base: eio: TBP>≡
    procedure (eio_write), deferred :: write

<EIO base: interfaces>≡
    abstract interface
        subroutine eio_write (object, unit)
            import
            class(eio_t), intent(in) :: object
            integer, intent(in), optional :: unit
        end subroutine eio_write
    end interface
```

Finalize. This should write/read footer data and close input/output channels.

```
<EIO base: eio: TBP>+≡
    procedure (eio_final), deferred :: final

<EIO base: interfaces>+≡
    abstract interface
        subroutine eio_final (object)
            import
            class(eio_t), intent(inout) :: object
        end subroutine eio_final
    end interface
```


Determine splitting parameters from the event sample data.

```

(EIO base: eio: TBP)+≡
  procedure :: set_splitting => eio_set_splitting

(EIO base: procedures)≡
  subroutine eio_set_splitting (eio, data)
    class(eio_t), intent(inout) :: eio
    type(event_sample_data_t), intent(in) :: data
    eio%split = data%split_n_evt > 0 .or. data%split_n_kbytes > 0
    if (eio%split) then
      eio%split_n_evt = data%split_n_evt
      eio%split_n_kbytes = data%split_n_kbytes
      eio%split_index = data%split_index
      eio%split_count = 0
    end if
  end subroutine eio_set_splitting

```

Update the byte count and check if it has increased. We use integer division to determine the number of `n_kbytes` blocks that are in the event file.

```

(EIO base: eio: TBP)+≡
  procedure :: update_split_count => eio_update_split_count

(EIO base: procedures)+≡
  subroutine eio_update_split_count (eio, increased)
    class(eio_t), intent(inout) :: eio
    logical, intent(out) :: increased
    integer :: split_count_old
    if (eio%split_n_kbytes > 0) then
      split_count_old = eio%split_count
      eio%split_count = eio%file_size_kbytes () / eio%split_n_kbytes
      increased = eio%split_count > split_count_old
    end if
  end subroutine eio_update_split_count

```

Generate a filename, taking a possible split index into account.

```

(EIO base: eio: TBP)+≡
  procedure :: set_filename => eio_set_filename

(EIO base: procedures)+≡
  subroutine eio_set_filename (eio)
    class(eio_t), intent(inout) :: eio
    character(32) :: buffer
    if (eio%split) then
      write (buffer, "(I0, '.')" ) eio%split_index
      eio%filename = eio%sample // "." // trim (buffer) // eio%extension
      eio%has_file = .true.
    else
      eio%filename = eio%sample // "." // eio%extension
      eio%has_file = .true.
    end if
  end subroutine eio_set_filename

```

Set the fallback model.

```

(EIO base: eio: TBP)+≡
  procedure :: set_fallback_model => eio_set_fallback_model
(EIO base: procedures)+≡
  subroutine eio_set_fallback_model (eio, model)
    class(eio_t), intent(inout) :: eio
    class(model_data_t), intent(in), target :: model
    eio%fallback_model => model
  end subroutine eio_set_fallback_model

```

Initialize for output. We provide process names. This should open an event file if appropriate and write header data. Some methods may require event sample data.

```

(EIO base: eio: TBP)+≡
  procedure (eio_init_out), deferred :: init_out
(EIO base: interfaces)+≡
  abstract interface
    subroutine eio_init_out (eio, sample, data, success, extension)
      import
      class(eio_t), intent(inout) :: eio
      type(string_t), intent(in) :: sample
      type(event_sample_data_t), intent(in), optional :: data
      logical, intent(out), optional :: success
      type(string_t), intent(in), optional :: extension
    end subroutine eio_init_out
  end interface

```

Initialize for input. We provide process names. This should open an event file if appropriate and read header data. The md5sum can be used to check the integrity of the configuration, it provides a checksum to compare with. In case the extension has changed the extension is also given as an argument.

The `data` argument is `intent(inout)`: we may read part of it and keep other parts and/or check them against the data in the file.

```

(EIO base: eio: TBP)+≡
  procedure (eio_init_in), deferred :: init_in
(EIO base: interfaces)+≡
  abstract interface
    subroutine eio_init_in (eio, sample, data, success, extension)
      import
      class(eio_t), intent(inout) :: eio
      type(string_t), intent(in) :: sample
      type(event_sample_data_t), intent(inout), optional :: data
      logical, intent(out), optional :: success
      type(string_t), intent(in), optional :: extension
    end subroutine eio_init_in
  end interface

```

Re-initialize for output. This should change the status of any event file from input to output and position it for appending new events.

```

(EIO base: eio: TBP)+≡
  procedure (eio_switch_inout), deferred :: switch_inout

```

```

<EIO base: interfaces>+≡
  abstract interface
    subroutine eio_switch_inout (eio, success)
      import
      class(eio_t), intent(inout) :: eio
      logical, intent(out), optional :: success
    end subroutine eio_switch_inout
  end interface

```

This is similar: split the output, i.e., close the current file and open a new one. The default implementation does nothing. For the feature to work, an implementation must override this.

```

<EIO base: eio: TBP>+≡
  procedure :: split_out => eio_split_out

<EIO base: procedures>+≡
  subroutine eio_split_out (eio)
    class(eio_t), intent(inout) :: eio
  end subroutine eio_split_out

```

Determine the file size in kilobytes. More exactly, determine the size in units of 1024 storage units, as returned by the INQUIRE statement.

The implementation returns zero if there is no file. The `has_file` flag is set by the `set_filename` method, so we can be confident that the `inquire` call is meaningful. If this algorithm doesn't apply for a particular format, we still can override the procedure.

```

<EIO base: eio: TBP>+≡
  procedure :: file_size_kbytes => eio_file_size_kbytes

<EIO base: procedures>+≡
  function eio_file_size_kbytes (eio) result (kbytes)
    class(eio_t), intent(in) :: eio
    integer :: kbytes
    integer(i64) :: bytes
    if (eio%has_file) then
      inquire (file = char (eio%filename), size = bytes)
      if (bytes > 0) then
        kbytes = bytes / 1024
      else
        kbytes = 0
      end if
    else
      kbytes = 0
    end if
  end function eio_file_size_kbytes

```

Output an event. All data can be taken from the `event` record. The index `i_prc` identifies the process among the processes that are contained in the current sample. The `reading` flag, if present, indicates that the event was read from file, not generated.

The `passed` flag tells us that this event has passed the selection criteria. Depending on the event format, we may choose to skip events that have not

passed.

```
<EIO base: eio: TBP>+≡
  procedure (eio_output), deferred :: output
<EIO base: interfaces>+≡
  abstract interface
    subroutine eio_output (eio, event, i_prc, reading, passed, pacify)
      import
      class(eio_t), intent(inout) :: eio
      class(generic_event_t), intent(in), target :: event
      integer, intent(in) :: i_prc
      logical, intent(in), optional :: reading, passed, pacify
    end subroutine eio_output
  end interface
```

Input an event. This should fill all event data that cannot be inferred from the associated process.

The input is broken down into two parts. First we read the `i_prc` index. So we know which process to expect in the subsequent event. If we have reached end of file, we also will know. Then, we read the event itself.

The parameter `iostat` is supposed to be set as the Fortran standard requires, negative for EOF and positive for error.

```
<EIO base: eio: TBP>+≡
  procedure (eio_input_i_prc), deferred :: input_i_prc
  procedure (eio_input_event), deferred :: input_event
<EIO base: interfaces>+≡
  abstract interface
    subroutine eio_input_i_prc (eio, i_prc, iostat)
      import
      class(eio_t), intent(inout) :: eio
      integer, intent(out) :: i_prc
      integer, intent(out) :: iostat
    end subroutine eio_input_i_prc
  end interface

  abstract interface
    subroutine eio_input_event (eio, event, iostat)
      import
      class(eio_t), intent(inout) :: eio
      class(generic_event_t), intent(inout), target :: event
      integer, intent(out) :: iostat
    end subroutine eio_input_event
  end interface
```

17.3.2 Unit tests

```
<EIO base: public>+≡
  public :: eio_base_test
```

```

<EIO base: tests>≡
  subroutine eio_base_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <EIO base: execute tests>
  end subroutine eio_base_test

```

The caller has to provide procedures that prepare and cleanup the test environment. They depend on modules that are not available here.

```

<EIO base: interfaces>+≡
  abstract interface
    subroutine eio_prepare_event (event, unweighted, n_alt)
      import
      class(generic_event_t), intent(inout), pointer :: event
      logical, intent(in), optional :: unweighted
      integer, intent(in), optional :: n_alt
    end subroutine eio_prepare_event
  end interface

  abstract interface
    subroutine eio_cleanup_event (event)
      import
      class(generic_event_t), intent(inout), pointer :: event
    end subroutine eio_cleanup_event
  end interface

```

We store pointers to the test-environment handlers as module variables. This allows us to call them from the test routines themselves, which don't allow for extra arguments.

```

<EIO base: public>+≡
  public :: eio_prepare_test, eio_cleanup_test

<EIO base: test types>≡
  procedure(eio_prepare_event), pointer :: eio_prepare_test => null ()
  procedure(eio_cleanup_event), pointer :: eio_cleanup_test => null ()

```

Similarly, for the fallback (hadron) model that some eio tests require:

```

<EIO base: interfaces>+≡
  abstract interface
    subroutine eio_prepare_model (model)
      import
      class(model_data_t), intent(inout), pointer :: model
    end subroutine eio_prepare_model
  end interface

  abstract interface
    subroutine eio_cleanup_model (model)
      import
      class(model_data_t), intent(inout), pointer :: model
    end subroutine eio_cleanup_model
  end interface

```

```

<EIO base: public>+≡
    public :: eio_prepare_fallback_model, eio_cleanup_fallback_model

<EIO base: test types>+≡
    procedure(eio_prepare_model), pointer :: eio_prepare_fallback_model => null ()
    procedure(eio_cleanup_model), pointer :: eio_cleanup_fallback_model => null ()

```

Test type for event I/O

The contents simulate the contents of an external file. We have the `sample` string as the file name and the array of momenta `event_p` as the list of events. The second index is the event index. The `event_i` component is the pointer to the current event, `event_n` is the total number of stored events.

```

<EIO base: test types>+≡
    type, extends (eio_t) :: eio_test_t
        integer :: event_n = 0
        integer :: event_i = 0
        integer :: i_prc = 0
        type(vector4_t), dimension(:,,:), allocatable :: event_p
    contains
        <EIO base: eio test: TBP>
    end type eio_test_t

```

Write to screen. Pretend that this is an actual event format.

```

<EIO base: eio test: TBP>≡
    procedure :: write => eio_test_write

<EIO base: procedures>+≡
    subroutine eio_test_write (object, unit)
        class(eio_test_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Test event stream"
        if (object%event_i /= 0) then
            write (u, "(1x,A,I0,A)") "Event #", object%event_i, ":"
            do i = 1, size (object%event_p, 1)
                call vector4_write (object%event_p(i, object%event_i), u)
            end do
        end if
    end subroutine eio_test_write

```

Finalizer. For the test case, we just reset the event count, but keep the stored “events”. For the real implementations, the events would be stored on an external medium, so we would delete the object contents.

```

<EIO base: eio test: TBP>+≡
    procedure :: final => eio_test_final

<EIO base: procedures>+≡
    subroutine eio_test_final (object)
        class(eio_test_t), intent(inout) :: object
        object%event_i = 0
    end subroutine eio_test_final

```

```
end subroutine eio_test_final
```

Initialization: We store the process IDs and the energy from the beam-data object. We also allocate the momenta (i.e., the simulated event record) for a fixed maximum size of 10 events, 2 momenta each. There is only a single process.

```
<EIO base: eio test: TBP>+≡
  procedure :: init_out => eio_test_init_out

<EIO base: procedures>+≡
  subroutine eio_test_init_out (eio, sample, data, success, extension)
    class(eio_test_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(event_sample_data_t), intent(in), optional :: data
    logical, intent(out), optional :: success
    type(string_t), intent(in), optional :: extension
    eio%sample = sample
    eio%event_n = 0
    eio%event_i = 0
    allocate (eio%event_p (2, 10))
    if (present (success)) success = .true.
  end subroutine eio_test_init_out
```

Initialization for input. Nothing to do for the test type.

```
<EIO base: eio test: TBP>+≡
  procedure :: init_in => eio_test_init_in

<EIO base: procedures>+≡
  subroutine eio_test_init_in (eio, sample, data, success, extension)
    class(eio_test_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(event_sample_data_t), intent(inout), optional :: data
    logical, intent(out), optional :: success
    type(string_t), intent(in), optional :: extension
    if (present (success)) success = .true.
  end subroutine eio_test_init_in
```

Switch from output to input. Again, nothing to do for the test type.

```
<EIO base: eio test: TBP>+≡
  procedure :: switch_inout => eio_test_switch_inout

<EIO base: procedures>+≡
  subroutine eio_test_switch_inout (eio, success)
    class(eio_test_t), intent(inout) :: eio
    logical, intent(out), optional :: success
    if (present (success)) success = .true.
  end subroutine eio_test_switch_inout
```

Output. Increment the event counter and store the momenta of the current event.

```
<EIO base: eio test: TBP>+≡
  procedure :: output => eio_test_output
```

```

(EIO base: procedures)+≡
subroutine eio_test_output (eio, event, i_prc, reading, passed, pacify)
  class(eio_test_t), intent(inout) :: eio
  class(generic_event_t), intent(in), target :: event
  logical, intent(in), optional :: reading, passed, pacify
  integer, intent(in) :: i_prc
  type(particle_set_t), pointer :: pset
  type(particle_t) :: prt
  eio%event_n = eio%event_n + 1
  eio%event_i = eio%event_n
  eio%i_prc = i_prc
  pset => event%get_particle_set_ptr ()
  prt = pset%get_particle (3)
  eio%event_p(1, eio%event_i) = prt%get_momentum ()
  prt = pset%get_particle (4)
  eio%event_p(2, eio%event_i) = prt%get_momentum ()
end subroutine eio_test_output

```

Input. Increment the event counter and retrieve the momenta of the current event. For the test case, we do not actually modify the current event.

```

(EIO base: eio test: TBP)+≡
  procedure :: input_i_prc => eio_test_input_i_prc
  procedure :: input_event => eio_test_input_event

(EIO base: procedures)+≡
subroutine eio_test_input_i_prc (eio, i_prc, iostat)
  class(eio_test_t), intent(inout) :: eio
  integer, intent(out) :: i_prc
  integer, intent(out) :: iostat
  i_prc = eio%i_prc
  iostat = 0
end subroutine eio_test_input_i_prc

subroutine eio_test_input_event (eio, event, iostat)
  class(eio_test_t), intent(inout) :: eio
  class(generic_event_t), intent(inout), target :: event
  integer, intent(out) :: iostat
  eio%event_i = eio%event_i + 1
  iostat = 0
end subroutine eio_test_input_event

```

Test I/O methods

```

(EIO base: execute tests)≡
  call test (eio_base_1, "eio_base_1", &
    "read and write event contents", &
    u, results)

(EIO base: tests)+≡
subroutine eio_base_1 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  class(eio_t), allocatable :: eio

```



```

integer :: i_prc, iostat
type(string_t) :: sample

write (u, "(A)")  "* Test output: eio_base_1"
write (u, "(A)")  "* Purpose: generate and read/write an event"
write (u, "(A)")

write (u, "(A)")  "* Initialize test process"

call eio%prepare_test (event, unweighted = .false.)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_test1"

allocate (eio_test_t :: eio)

call eio%init_out (sample)
call event%generate (1, [0._default, 0._default])
call eio%output (event, 42)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* Re-read the event"
write (u, "(A)")

call eio%init_in (sample)
call eio%input_i_prc (i_prc, iostat)
call eio%input_event (event, iostat)
call eio%write (u)
write (u, "(A)")
write (u, "(1x,A,I0)")  "i = ", i_prc

write (u, "(A)")
write (u, "(A)")  "* Generate and append another event"
write (u, "(A)")

call eio%switch_inout ()
call event%generate (1, [0._default, 0._default])
call eio%output (event, 5)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* Re-read both events"
write (u, "(A)")

call eio%init_in (sample)
call eio%input_i_prc (i_prc, iostat)
call eio%input_event (event, iostat)
call eio%input_i_prc (i_prc, iostat)

```

```

call eio%input_event (event, iostat)
call eio%write (u)
write (u, "(A)")
write (u, "(1x,A,I0)") "i = ", i_prc

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()
deallocate (eio)

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_base_1"

end subroutine eio_base_1

```

17.4 Event Generation Checkpoints

This is an output-only format. Its only use is to write screen messages every n events, to inform the user about progress.

```

<eio_checkpoints.f90>≡
  <File header>

  module eio_checkpoints

    use kinds
    use io_units
    <Use strings>
    use unit_tests
    use diagnostics

    use cputime
    use model_data
    use event_base
    use eio_data
    use eio_base

    <Standard module head>

    <EIO checkpoints: public>

    <EIO checkpoints: parameters>

    <EIO checkpoints: types>

    contains

    <EIO checkpoints: procedures>

```

```
⟨EIO checkpoints: tests⟩
```

```
end module eio_checkpoints
```

17.4.1 Type

```
⟨EIO checkpoints: public⟩≡
```

```
public :: eio_checkpoints_t
```

```
⟨EIO checkpoints: types⟩≡
```

```
type, extends (eio_t) :: eio_checkpoints_t
```

```
logical :: active = .false.
```

```
logical :: running = .false.
```

```
integer :: val = 0
```

```
integer :: n_events = 0
```

```
integer :: n_read = 0
```

```
integer :: i_evt = 0
```

```
logical :: blank = .false.
```

```
type(timer_t) :: timer
```

```
contains
```

```
⟨EIO checkpoints: eio checkpoints: TBP⟩
```

```
end type eio_checkpoints_t
```

17.4.2 Specific Methods

Set parameters that are specifically used with LHEF.

```
⟨EIO checkpoints: eio checkpoints: TBP⟩≡
```

```
procedure :: set_parameters => eio_checkpoints_set_parameters
```

```
⟨EIO checkpoints: procedures⟩≡
```

```
subroutine eio_checkpoints_set_parameters (eio, checkpoint, blank)
```

```
class(eio_checkpoints_t), intent(inout) :: eio
```

```
integer, intent(in) :: checkpoint
```

```
logical, intent(in), optional :: blank
```

```
eio%val = checkpoint
```

```
if (present (blank)) eio%blank = blank
```

```
end subroutine eio_checkpoints_set_parameters
```

17.4.3 Common Methods

Output. This is not the actual event format, but a readable account of the current status.

```
⟨EIO checkpoints: eio checkpoints: TBP⟩+≡
```

```
procedure :: write => eio_checkpoints_write
```

```
⟨EIO checkpoints: procedures⟩+≡
```

```
subroutine eio_checkpoints_write (object, unit)
```

```
class(eio_checkpoints_t), intent(in) :: object
```

```
integer, intent(in), optional :: unit
```

```
integer :: u
```

```
u = given_output_unit (unit)
```

```
if (object%active) then
```

```

        write (u, "(1x,A)") "Event-sample checkpoints: active"
        write (u, "(3x,A,I0)") "interval = ", object%val
        write (u, "(3x,A,I0)") "n_events = ", object%n_events
        write (u, "(3x,A,I0)") "n_read = ", object%n_read
        write (u, "(3x,A,I0)") "n_current = ", object%i_evt
        write (u, "(3x,A,L1)") "blanking = ", object%blank
        call object%timer%write (u)
    else
        write (u, "(1x,A)") "Event-sample checkpoints: off"
    end if
end subroutine eio_checkpoints_write

```

Finalizer: trivial.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: final => eio_checkpoints_final

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_final (object)
        class(eio_checkpoints_t), intent(inout) :: object
        object%active = .false.
    end subroutine eio_checkpoints_final

```

Activate checkpointing for event generation or writing.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: init_out => eio_checkpoints_init_out

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_init_out (eio, sample, data, success, extension)
        class(eio_checkpoints_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(in), optional :: data
        logical, intent(out), optional :: success
        if (present (data)) then
            if (eio%val > 0) then
                eio%active = .true.
                eio%i_evt = 0
                eio%n_read = 0
                eio%n_events = data%n_evt
            end if
        end if
        if (present (success)) success = .true.
    end subroutine eio_checkpoints_init_out

```

No checkpointing for event reading.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: init_in => eio_checkpoints_init_in

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_init_in (eio, sample, data, success, extension)
        class(eio_checkpoints_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(inout), optional :: data

```

```

    logical, intent(out), optional :: success
    call msg_bug ("Event checkpoints: event input not supported")
    if (present (success)) success = .false.
end subroutine eio_checkpoints_init_in

```

Switch from input to output: also not supported.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: switch_inout => eio_checkpoints_switch_inout

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_switch_inout (eio, success)
        class(eio_checkpoints_t), intent(inout) :: eio
        logical, intent(out), optional :: success
        call msg_bug ("Event checkpoints: in-out switch not supported")
        if (present (success)) success = .false.
    end subroutine eio_checkpoints_switch_inout

```

Checkpoints: display progress for the current event, if applicable.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: output => eio_checkpoints_output

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_output (eio, event, i_prc, reading, passed, pacify)
        class(eio_checkpoints_t), intent(inout) :: eio
        class(generic_event_t), intent(in), target :: event
        integer, intent(in) :: i_prc
        logical, intent(in), optional :: reading, passed, pacify
        logical :: rd
        rd = .false.; if (present (reading)) rd = reading
        if (eio%active) then
            if (.not. eio%running) call eio%startup ()
            if (eio%running) then
                eio%i_evt = eio%i_evt + 1
                if (rd) then
                    eio%n_read = eio%n_read + 1
                else if (mod (eio%i_evt, eio%val) == 0) then
                    call eio%message (eio%blank)
                end if
                if (eio%i_evt == eio%n_events) call eio%shutdown ()
            end if
        end if
    end subroutine eio_checkpoints_output

```

When the first event is called, we have to initialize the screen output.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: startup => eio_checkpoints_startup

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_startup (eio)
        class(eio_checkpoints_t), intent(inout) :: eio
        if (eio%active .and. eio%i_evt < eio%n_events) then
            call msg_message ("")
            call msg_message (checkpoint_bar)
            call msg_message (checkpoint_head)
        end if
    end subroutine eio_checkpoints_startup

```

```

        call msg_message (checkpoint_bar)
        write (msg_buffer, checkpoint_fmt) 0., 0, eio%n_events - eio%i_evt, "???"
        call msg_message ()
        eio%running = .true.
        call eio%timer%start ()
    end if
end subroutine eio_checkpoints_startup

```

This message is printed at every checkpoint.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: message => eio_checkpoints_message

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_message (eio, testflag)
        class(eio_checkpoints_t), intent(inout) :: eio
        logical, intent(in), optional :: testflag
        real :: t
        type(time_t) :: time_remaining
        type(string_t) :: time_string
        call eio%timer%stop ()
        t = eio%timer
        call eio%timer%restart ()
        time_remaining = &
            nint (t / (eio%i_evt - eio%n_read) * (eio%n_events - eio%i_evt))
        time_string = time_remaining%to_string_ms (blank = testflag)
        write (msg_buffer, checkpoint_fmt) &
            100 * (eio%i_evt - eio%n_read) / real (eio%n_events - eio%n_read), &
            eio%i_evt - eio%n_read, &
            eio%n_events - eio%i_evt, &
            char (time_string)
        call msg_message ()
    end subroutine eio_checkpoints_message

```

When the last event is called, wrap up.

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: shutdown => eio_checkpoints_shutdown

<EIO checkpoints: procedures>+≡
    subroutine eio_checkpoints_shutdown (eio)
        class(eio_checkpoints_t), intent(inout) :: eio
        if (mod (eio%i_evt, eio%val) /= 0) then
            write (msg_buffer, checkpoint_fmt) &
                100., eio%i_evt - eio%n_read, 0, "0m:00s"
            call msg_message ()
        end if
        call msg_message (checkpoint_bar)
        call msg_message ("")
        eio%running = .false.
    end subroutine eio_checkpoints_shutdown

```

```

<EIO checkpoints: eio checkpoints: TBP>+≡
    procedure :: input_i_prc => eio_checkpoints_input_i_prc
    procedure :: input_event => eio_checkpoints_input_event

```

```

<EIO checkpoints: procedures>+≡
subroutine eio_checkpoints_input_i_prc (eio, i_prc, iostat)
  class(eio_checkpoints_t), intent(inout) :: eio
  integer, intent(out) :: i_prc
  integer, intent(out) :: iostat
  call msg_bug ("Event checkpoints: event input not supported")
  i_prc = 0
  iostat = 1
end subroutine eio_checkpoints_input_i_prc

subroutine eio_checkpoints_input_event (eio, event, iostat)
  class(eio_checkpoints_t), intent(inout) :: eio
  class(generic_event_t), intent(inout), target :: event
  integer, intent(out) :: iostat
  call msg_bug ("Event checkpoints: event input not supported")
  iostat = 1
end subroutine eio_checkpoints_input_event

```

17.4.4 Message header

```

<EIO checkpoints: parameters>≡
character(*), parameter :: &
  checkpoint_head = "| % complete | events generated | events remaining &
  &| time remaining"
character(*), parameter :: &
  checkpoint_bar = "|=====&
  &=====|"
character(*), parameter :: &
  checkpoint_fmt = "(' ',F5.1,T16,I9,T35,I9,T58,A)"

```

17.4.5 Unit tests

```

<EIO checkpoints: public>+≡
public :: eio_checkpoints_test

<EIO checkpoints: tests>≡
subroutine eio_checkpoints_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
  <EIO checkpoints: execute tests>
end subroutine eio_checkpoints_test

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO checkpoints: execute tests>≡
call test (eio_checkpoints_1, "eio_checkpoints_1", &
  "read and write event contents", &
  u, results)

```

```

(EIO checkpoints: tests) +=
subroutine eio_checkpoints_1 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  class(eio_t), allocatable :: eio
  type(event_sample_data_t) :: data
  type(string_t) :: sample
  integer :: i, n_events

  write (u, "(A)")  "* Test output: eio_checkpoints_1"
  write (u, "(A)")  "* Purpose: generate a number of events &
    &with screen output"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize test process"

  call eio_prepare_test (event)

  write (u, "(A)")
  write (u, "(A)")  "* Generate events"
  write (u, "(A)")

  sample = "eio_checkpoints_1"

  allocate (eio_checkpoints_t :: eio)

  n_events = 10
  call data%init (1, 0)
  data%n_evt = n_events

  select type (eio)
  type is (eio_checkpoints_t)
    call eio%set_parameters (checkpoint = 4)
  end select

  call eio%init_out (sample, data)

  do i = 1, n_events
    call event%generate (1, [0._default, 0._default])
    call eio%output (event, i_prc = 0)
  end do

  write (u, "(A)")  "* Checkpointing status"
  write (u, "(A)")

  call eio%write (u)
  call eio%final ()

  write (u, "(A)")
  write (u, "(A)")  "* Cleanup"

  call eio_cleanup_test (event)

  write (u, "(A)")

```



```

write (u, "(A)")  "*" Test output end: eio_checkpoints_1"

end subroutine eio_checkpoints_1

```

17.5 Event Weight Output

This is an output-only format. For each event, we print the indices that identify process, process part (MCI group), and term. As numerical information we print the squared matrix element (trace) and the event weight.

```

(eio_weights.f90)≡
  <File header>

  module eio_weights

    use kinds
    use io_units
    <Use strings>
    use unit_tests
    use diagnostics

    use lorentz
    use model_data
    use particles
    use event_base
    use eio_data
    use eio_base

    <Standard module head>

    <EIO weights: public>

    <EIO weights: types>

    contains

    <EIO weights: procedures>

    <EIO weights: tests>

  end module eio_weights

```

17.5.1 Type

```

<EIO weights: public>≡
  public :: eio_weights_t

<EIO weights: types>≡
  type, extends (eio_t) :: eio_weights_t
    logical :: writing = .false.
    integer :: unit = 0
    logical :: pacify = .false.

```

```

contains
  <EIO weights: eio weights: TBP>
end type eio_weights_t

```

17.5.2 Specific Methods

Set pacify flags.

```

<EIO weights: eio weights: TBP>≡
  procedure :: set_parameters => eio_weights_set_parameters

<EIO weights: procedures>≡
  subroutine eio_weights_set_parameters (eio, pacify)
    class(eio_weights_t), intent(inout) :: eio
    logical, intent(in), optional :: pacify
    if (present (pacify)) eio%pacify = pacify
    eio%extension = "weights.dat"
  end subroutine eio_weights_set_parameters

```

17.5.3 Common Methods

Output. This is not the actual event format, but a readable account of the current object status.

```

<EIO weights: eio weights: TBP>+≡
  procedure :: write => eio_weights_write

<EIO weights: procedures>+≡
  subroutine eio_weights_write (object, unit)
    class(eio_weights_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Weight stream:"
    if (object%writing) then
      write (u, "(3x,A,A)") "Writing to file   = ", char (object%filename)
      write (u, "(3x,A,L1)") "Reduced I/O prec. = ", object%pacify
    else
      write (u, "(3x,A)") "[closed]"
    end if
  end subroutine eio_weights_write

```

Finalizer: close any open file.

```

<EIO weights: eio weights: TBP>+≡
  procedure :: final => eio_weights_final

<EIO weights: procedures>+≡
  subroutine eio_weights_final (object)
    class(eio_weights_t), intent(inout) :: object
    if (object%writing) then
      write (msg_buffer, "(A,A,A)") "Events: closing weight stream file '", &
        char (object%filename), "'"
      call msg_message ()
    end if
  end subroutine eio_weights_final

```

```

        close (object%unit)
        object%writing = .false.
    end if
end subroutine eio_weights_final

```

Initialize event writing.

```

(EIO weights: eio weights: TBP)+≡
    procedure :: init_out => eio_weights_init_out

(EIO weights: procedures)+≡
    subroutine eio_weights_init_out (eio, sample, data, success, extension)
        class(eio_weights_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(in), optional :: data
        logical, intent(out), optional :: success
        if (present(extension)) then
            eio%extension = extension
        else
            eio%extension = "weights.dat"
        end if
        eio%filename = sample // "." // eio%extension
        eio%unit = free_unit ()
        write (msg_buffer, "(A,A,A)") "Events: writing to weight stream file '", &
            char (eio%filename), "'"
        call msg_message ()
        eio%writing = .true.
        open (eio%unit, file = char (eio%filename), &
            action = "write", status = "replace")
        if (present (success)) success = .true.
    end subroutine eio_weights_init_out

```

Initialize event reading.

```

(EIO weights: eio weights: TBP)+≡
    procedure :: init_in => eio_weights_init_in

(EIO weights: procedures)+≡
    subroutine eio_weights_init_in (eio, sample, data, success, extension)
        class(eio_weights_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(inout), optional :: data
        logical, intent(out), optional :: success
        call msg_bug ("Weight stream: event input not supported")
        if (present (success)) success = .false.
    end subroutine eio_weights_init_in

```

Switch from input to output: reopen the file for reading.

```

(EIO weights: eio weights: TBP)+≡
    procedure :: switch_inout => eio_weights_switch_inout

(EIO weights: procedures)+≡
    subroutine eio_weights_switch_inout (eio, success)
        class(eio_weights_t), intent(inout) :: eio

```

```

logical, intent(out), optional :: success
call msg_bug ("Weight stream: in-out switch not supported")
if (present (success)) success = .false.
end subroutine eio_weights_switch_inout

```

Output an event. Write first the event indices, then weight and two values of the squared matrix element: `sqme_ref` is the value stored in the event record, and `sqme_prc` is the one stored in the process instance. (They can differ: when recalculating, the former is read from file and the latter is the result of the new calculation.)

For the alternative entries, the `sqme` value is always obtained by a new calculation, and thus qualifies as `sqme_prc`.

```

(EIO weights: eio weights: TBP)+≡
  procedure :: output => eio_weights_output

(EIO weights: procedures)+≡
  subroutine eio_weights_output (eio, event, i_prc, reading, passed, pacify)
    class(eio_weights_t), intent(inout) :: eio
    class(generic_event_t), intent(in), target :: event
    integer, intent(in) :: i_prc
    logical, intent(in), optional :: reading, passed, pacify
    integer :: n_alt, i
    real(default) :: weight, sqme_ref, sqme_prc
    if (eio%writing) then
      weight = event%get_weight_prc ()
      sqme_ref = event%get_sqme_ref ()
      sqme_prc = event%get_sqme_prc ()
      n_alt = event%get_n_alt ()
1    format (I0,3(1x,ES17.10),3(1x,I0))
2    format (I0,3(1x,ES15.8),3(1x,I0))
      if (eio%pacify) then
        write (eio%unit, 2) 0, weight, sqme_prc, sqme_ref, &
          i_prc
      else
        write (eio%unit, 1) 0, weight, sqme_prc, sqme_ref, &
          i_prc
      end if
      do i = 1, n_alt
        weight = event%get_weight_alt(i)
        sqme_prc = event%get_sqme_alt(i)
        if (eio%pacify) then
          write (eio%unit, 2) i, weight, sqme_prc
        else
          write (eio%unit, 1) i, weight, sqme_prc
        end if
      end do
    else
      call eio%write ()
      call msg_fatal ("Weight stream file is not open for writing")
    end if
  end subroutine eio_weights_output

```

Input an event.

```

<EIO weights: eio weights: TBP>+≡
  procedure :: input_i_prc => eio_weights_input_i_prc
  procedure :: input_event => eio_weights_input_event

<EIO weights: procedures>+≡
  subroutine eio_weights_input_i_prc (eio, i_prc, iostat)
    class(eio_weights_t), intent(inout) :: eio
    integer, intent(out) :: i_prc
    integer, intent(out) :: iostat
    call msg_bug ("Weight stream: event input not supported")
    i_prc = 0
    iostat = 1
  end subroutine eio_weights_input_i_prc

  subroutine eio_weights_input_event (eio, event, iostat)
    class(eio_weights_t), intent(inout) :: eio
    class(generic_event_t), intent(inout), target :: event
    integer, intent(out) :: iostat
    call msg_bug ("Weight stream: event input not supported")
    iostat = 1
  end subroutine eio_weights_input_event

```

17.5.4 Unit tests

```

<EIO weights: public>+≡
  public :: eio_weights_test

<EIO weights: tests>≡
  subroutine eio_weights_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <EIO weights: execute tests>
  end subroutine eio_weights_test

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO weights: execute tests>≡
  call test (eio_weights_1, "eio_weights_1", &
    "read and write event contents", &
    u, results)

<EIO weights: tests>+≡
  subroutine eio_weights_1 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file
    character(80) :: buffer

    write (u, "(A)")  "*" Test output: eio_weights_1"
    write (u, "(A)")  "*"  Purpose: generate an event and write weight to file"

```

```

write (u, "(A)")

write (u, "(A)")  "* Initialize test process"

call eio_prepare_test (event, unweighted = .false.)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_weights_1"

allocate (eio_weights_t :: eio)

call eio%init_out (sample)
call event%generate (1, [0._default, 0._default])

call eio%output (event, i_prc = 42)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents: &
    &(weight, sqme(evt), sqme(prc), i_prc, i_mci, i_term)"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = "eio_weights_1.weights.dat", &
    action = "read", status = "old")
read (u_file, "(A)") buffer
write (u, "(A)") trim (buffer)
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_weights_1"
end subroutine eio_weights_1

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO weights: execute tests>+≡
    call test (eio_weights_2, "eio_weights_2", &
        "multiple weights", &
        u, results)

<EIO weights: tests>+≡
    subroutine eio_weights_2 (u)
        integer, intent(in) :: u

```

```

class(generic_event_t), pointer :: event
class(eio_t), allocatable :: eio
type(string_t) :: sample
integer :: u_file, i
character(80) :: buffer

write (u, "(A)")  "* Test output: eio_weights_2"
write (u, "(A)")  "* Purpose: generate an event and write weight to file"
write (u, "(A)")

write (u, "(A)")  "* Initialize test process"

call eio_prepare_test (event, unweighted = .false., n_alt = 2)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_weights_2"

allocate (eio_weights_t :: eio)

call eio%init_out (sample)
select type (eio)
type is (eio_weights_t)
    call eio%set_parameters (pacify = .true.)
end select
call event%generate (1, [0._default, 0._default])
call event%set (sqme_alt = [2._default, 3._default])
call event%set (weight_alt = &
    [2 * event%get_weight_prc (), 3 * event%get_weight_prc ()])

call eio%output (event, i_prc = 42)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents: &
    &(weight, sqme(evt), sqme(prc), i_prc, i_mci, i_term)"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = "eio_weights_2.weights.dat", &
    action = "read", status = "old")
do i = 1, 3
    read (u_file, "(A)") buffer
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

```

```

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: eio_weights_2"

    end subroutine eio_weights_2

```

17.6 ASCII File Formats

Here, we implement several ASCII file formats. It is possible to switch between them using flags.

$\langle \text{eio_ascii.f90} \rangle \equiv$
 $\langle \text{File header} \rangle$

```

module eio_ascii

    use kinds
    use io_units
 $\langle \text{Use strings} \rangle$ 
    use unit_tests
    use diagnostics

    use lorentz
    use model_data
    use particles
    use event_base
    use hep_common
    use hep_events
    use eio_data
    use eio_base

 $\langle \text{Standard module head} \rangle$ 

 $\langle \text{EIO ascii: public} \rangle$ 

 $\langle \text{EIO ascii: types} \rangle$ 

contains

 $\langle \text{EIO ascii: procedures} \rangle$ 

 $\langle \text{EIO ascii: tests} \rangle$ 

end module eio_ascii

```

17.6.1 Type

$\langle \text{EIO ascii: public} \rangle \equiv$
 public :: eio_ascii_t
 $\langle \text{EIO ascii: types} \rangle \equiv$
 type, abstract, extends (eio_t) :: eio_ascii_t
 logical :: writing = .false.


```

integer :: unit = 0
logical :: keep_beams = .false.
logical :: keep_remnants = .true.
contains
  <EIO ascii: eio_ascii: TBP>
end type eio_ascii_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_ascii_t
<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_ascii_t
end type eio_ascii_ascii_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_athena_t
<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_athena_t
end type eio_ascii_athena_t

```

The debug format has a few options that can be controlled by Sindarin variables.

```

<EIO ascii: public>+≡
  public :: eio_ascii_debug_t
<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_debug_t
    logical :: show_process = .true.
    logical :: show_transforms = .true.
    logical :: show_decay = .true.
    logical :: verbose = .true.
end type eio_ascii_debug_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_hepevt_t
<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_hepevt_t
end type eio_ascii_hepevt_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_hepevt_verb_t
<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_hepevt_verb_t
end type eio_ascii_hepevt_verb_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_lha_t
<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_lha_t
end type eio_ascii_lha_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_lha_verb_t

<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_lha_verb_t
  end type eio_ascii_lha_verb_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_long_t

<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_long_t
  end type eio_ascii_long_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_mokka_t

<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_mokka_t
  end type eio_ascii_mokka_t

```

```

<EIO ascii: public>+≡
  public :: eio_ascii_short_t

<EIO ascii: types>+≡
  type, extends (eio_ascii_t) :: eio_ascii_short_t
  end type eio_ascii_short_t

```

17.6.2 Specific Methods

Set parameters that are specifically used with ASCII file formats. In particular, this is the file extension.

```

<EIO ascii: eio ascii: TBP>≡
  procedure :: set_parameters => eio_ascii_set_parameters

<EIO ascii: procedures>≡
  subroutine eio_ascii_set_parameters (eio, &
    keep_beams, keep_remnants, extension, &
    show_process, show_transforms, show_decay, verbose)
    class(eio_ascii_t), intent(inout) :: eio
    logical, intent(in), optional :: keep_beams
    logical, intent(in), optional :: keep_remnants
    type(string_t), intent(in), optional :: extension
    logical, intent(in), optional :: show_process, show_transforms, show_decay
    logical, intent(in), optional :: verbose
    if (present (keep_beams)) eio%keep_beams = keep_beams
    if (present (keep_remnants)) eio%keep_remnants = keep_remnants
    if (present (extension)) then
      eio%extension = extension
    else
      select type (eio)
      type is (eio_ascii_ascii_t)
        eio%extension = "evt"

```

```

type is (eio_ascii_athena_t)
  eio%extension = "athena.evt"
type is (eio_ascii_debug_t)
  eio%extension = "debug"
type is (eio_ascii_hepevt_t)
  eio%extension = "hepevt"
type is (eio_ascii_hepevt_verb_t)
  eio%extension = "hepevt.verb"
type is (eio_ascii_lha_t)
  eio%extension = "lha"
type is (eio_ascii_lha_verb_t)
  eio%extension = "lha.verb"
type is (eio_ascii_long_t)
  eio%extension = "long.evt"
type is (eio_ascii_mokka_t)
  eio%extension = "mokka.evt"
type is (eio_ascii_short_t)
  eio%extension = "short.evt"
end select
end if
select type (eio)
type is (eio_ascii_debug_t)
  if (present (show_process)) eio%show_process = show_process
  if (present (show_transforms)) eio%show_transforms = show_transforms
  if (present (show_decay)) eio%show_decay = show_decay
  if (present (verbose)) eio%verbose = verbose
end select
end subroutine eio_ascii_set_parameters

```

17.6.3 Common Methods

Output. This is not the actual event format, but a readable account of the current object status.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: write => eio_ascii_write

<EIO ascii: procedures>+≡
  subroutine eio_ascii_write (object, unit)
    class(eio_ascii_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    select type (object)
    type is (eio_ascii_ascii_t)
      write (u, "(1x,A)") "ASCII event stream (default format):"
    type is (eio_ascii_athena_t)
      write (u, "(1x,A)") "ASCII event stream (ATHENA format):"
    type is (eio_ascii_debug_t)
      write (u, "(1x,A)") "ASCII event stream (Debugging format):"
    type is (eio_ascii_hepevt_t)
      write (u, "(1x,A)") "ASCII event stream (HEPEVT format):"
    type is (eio_ascii_hepevt_verb_t)
      write (u, "(1x,A)") "ASCII event stream (verbose HEPEVT format):"

```

```

type is (eio_ascii_lha_t)
  write (u, "(1x,A)") "ASCII event stream (LHA format):"
type is (eio_ascii_lha_verb_t)
  write (u, "(1x,A)") "ASCII event stream (verbose LHA format):"
type is (eio_ascii_long_t)
  write (u, "(1x,A)") "ASCII event stream (long format):"
type is (eio_ascii_mokka_t)
  write (u, "(1x,A)") "ASCII event stream (MOKKA format):"
type is (eio_ascii_short_t)
  write (u, "(1x,A)") "ASCII event stream (short format):"
end select
if (object%writing) then
  write (u, "(3x,A,A)") "Writing to file   = ", char (object%filename)
else
  write (u, "(3x,A)") "[closed]"
end if
write (u, "(3x,A,L1)") "Keep beams      = ", object%keep_beams
write (u, "(3x,A,L1)") "Keep remnants   = ", object%keep_remnants
select type (object)
type is (eio_ascii_debug_t)
  write (u, "(3x,A,L1)") "Show process     = ", object%show_process
  write (u, "(3x,A,L1)") "Show transforms  = ", object%show_transforms
  write (u, "(3x,A,L1)") "Show decay tree  = ", object%show_decay
  write (u, "(3x,A,L1)") "Verbose output   = ", object%verbose
end select
end subroutine eio_ascii_write

```

Finalizer: close any open file.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: final => eio_ascii_final

<EIO ascii: procedures>+≡
  subroutine eio_ascii_final (object)
    class(eio_ascii_t), intent(inout) :: object
    if (object%writing) then
      write (msg_buffer, "(A,A,A)") "Events: closing ASCII file '", &
        char (object%filename), "'"
      call msg_message ()
      close (object%unit)
      object%writing = .false.
    end if
  end subroutine eio_ascii_final

```

Initialize event writing.

Check weight normalization. This applies to all ASCII-type files that use the HEPUP common block. We can't allow normalization conventions that are not covered by the HEPUP definition.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: init_out => eio_ascii_init_out

<EIO ascii: procedures>+≡
  subroutine eio_ascii_init_out (eio, sample, data, success, extension)
    class(eio_ascii_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample

```

```

type(string_t), intent(in), optional :: extension
type(event_sample_data_t), intent(in), optional :: data
logical, intent(out), optional :: success
integer :: i
if (.not. present (data)) &
    call msg_bug ("ASCII initialization: missing data")
if (data%n_beam /= 2) &
    call msg_fatal ("ASCII: defined for scattering processes only")
eio%sample = sample
call eio%check_normalization (data)
call eio%set_splitting (data)
call eio%set_filename ()
eio%unit = free_unit ()
write (msg_buffer, "(A,A,A)") "Events: writing to ASCII file '", &
    char (eio%filename), "'"
call msg_message ()
eio%writing = .true.
open (eio%unit, file = char (eio%filename), &
    action = "write", status = "replace")
select type (eio)
type is (eio_ascii_lha_t)
    call heprup_init &
        (data%pdg_beam, &
        data%energy_beam, &
        n_processes = data%n_proc, &
        unweighted = data%unweighted, &
        negative_weights = data%negative_weights)
    do i = 1, data%n_proc
        call heprup_set_process_parameters (i = i, &
            process_id = data%proc_num_id(i), &
            cross_section = data%cross_section(i), &
            error = data%error(i))
    end do
    call heprup_write_ascii (eio%unit)
type is (eio_ascii_lha_verb_t)
    call heprup_init &
        (data%pdg_beam, &
        data%energy_beam, &
        n_processes = data%n_proc, &
        unweighted = data%unweighted, &
        negative_weights = data%negative_weights)
    do i = 1, data%n_proc
        call heprup_set_process_parameters (i = i, &
            process_id = data%proc_num_id(i), &
            cross_section = data%cross_section(i), &
            error = data%error(i))
    end do
    call heprup_write_verbose (eio%unit)
end select
if (present (success)) success = .true.
end subroutine eio_ascii_init_out

```

Some event properties do not go well with some output formats. In particular, many formats require unweighted events.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: check_normalization => eio_ascii_check_normalization

<EIO ascii: procedures>+≡
  subroutine eio_ascii_check_normalization (eio, data)
    class(eio_ascii_t), intent(in) :: eio
    type(event_sample_data_t), intent(in) :: data
    if (data%unweighted) then
    else
      select type (eio)
      type is (eio_ascii_athena_t); call msg_fatal &
        ("Event output (Athena format): events must be unweighted.")
      type is (eio_ascii_hepevt_t); call msg_fatal &
        ("Event output (HEPEVT format): events must be unweighted.")
      type is (eio_ascii_hepevt_verb_t); call msg_fatal &
        ("Event output (HEPEVT format): events must be unweighted.")
      end select
      select case (data%norm_mode)
      case (NORM_SIGMA)
      case default
        select type (eio)
        type is (eio_ascii_lha_t)
          call msg_fatal &
            ("Event output (LHA): normalization for weighted events &
              &must be 'sigma'")
        type is (eio_ascii_lha_verb_t)
          call msg_fatal &
            ("Event output (LHA): normalization for weighted events &
              &must be 'sigma'")
        end select
      end select
    end if
  end subroutine eio_ascii_check_normalization

```

Initialize event reading.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: init_in => eio_ascii_init_in

<EIO ascii: procedures>+≡
  subroutine eio_ascii_init_in (eio, sample, data, success, extension)
    class(eio_ascii_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(string_t), intent(in), optional :: extension
    type(event_sample_data_t), intent(inout), optional :: data
    logical, intent(out), optional :: success
    call msg_bug ("ASCII: event input not supported")
    if (present (success)) success = .false.
  end subroutine eio_ascii_init_in

```

Switch from input to output: reopen the file for reading.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: switch_inout => eio_ascii_switch_inout

```

```

<EIO ascii: procedures>+≡
subroutine eio_ascii_switch_inout (eio, success)
  class(eio_ascii_t), intent(inout) :: eio
  logical, intent(out), optional :: success
  call msg_bug ("ASCII: in-out switch not supported")
  if (present (success)) success = .false.
end subroutine eio_ascii_switch_inout

```

Split event file: increment the counter, close the current file, open a new one. If the file needs a header, repeat it for the new file. (We assume that the common block contents are still intact.)

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: split_out => eio_ascii_split_out
<EIO ascii: procedures>+≡
subroutine eio_ascii_split_out (eio)
  class(eio_ascii_t), intent(inout) :: eio
  if (eio%split) then
    eio%split_index = eio%split_index + 1
    call eio%set_filename ()
    write (msg_buffer, "(A,A,A)") "Events: writing to ASCII file '", &
      char (eio%filename), "'"
    call msg_message ()
    close (eio%unit)
    open (eio%unit, file = char (eio%filename), &
      action = "write", status = "replace")
    select type (eio)
    type is (eio_ascii_lha_t)
      call heprup_write_ascii (eio%unit)
    type is (eio_ascii_lha_verb_t)
      call heprup_write_verbose (eio%unit)
    end select
  end if
end subroutine eio_ascii_split_out

```

Output an event. Write first the event indices, then weight and squared matrix element, then the particle set.

```

<EIO ascii: eio ascii: TBP>+≡
  procedure :: output => eio_ascii_output
<EIO ascii: procedures>+≡
subroutine eio_ascii_output (eio, event, i_prc, reading, passed, pacify)
  class(eio_ascii_t), intent(inout) :: eio
  class(generic_event_t), intent(in), target :: event
  integer, intent(in) :: i_prc
  logical, intent(in), optional :: reading, passed, pacify
  if (present (passed)) then
    if (.not. passed) return
  end if
  if (eio%writing) then
    select type (eio)
    type is (eio_ascii_lha_t)
      call hepeup_from_event (event, &
        process_index = i_prc, &

```

```

        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepeup_write_lha (eio%unit)
type is (eio_ascii_lha_verb_t)
    call hepeup_from_event (event, &
        process_index = i_prc, &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepeup_write_verbose (eio%unit)
type is (eio_ascii_ascii_t)
    call event%write (eio%unit, &
        show_process = .false., &
        show_transforms = .false., &
        show_decay = .false., &
        verbose = .false., testflag = pacify)
type is (eio_ascii_athena_t)
    call hepevt_from_event (event, &
        i_evt = event%get_index (), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepevt_write_athena (eio%unit)
type is (eio_ascii_debug_t)
    call event%write (eio%unit, &
        show_process = eio%show_process, &
        show_transforms = eio%show_transforms, &
        show_decay = eio%show_decay, &
        verbose = eio%verbose, &
        testflag = pacify)
type is (eio_ascii_hepevt_t)
    call hepevt_from_event (event, &
        i_evt = event%get_index (), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepevt_write_hepevt (eio%unit)
type is (eio_ascii_hepevt_verb_t)
    call hepevt_from_event (event, &
        i_evt = event%get_index (), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepevt_write_verbose (eio%unit)
type is (eio_ascii_long_t)
    call hepevt_from_event (event, &
        i_evt = event%get_index (), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepevt_write_ascii (eio%unit, .true.)
type is (eio_ascii_mokka_t)
    call hepevt_from_event (event, &
        i_evt = event%get_index (), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepevt_write_mokka (eio%unit)
type is (eio_ascii_short_t)
    call hepevt_from_event (event, &

```



```

        i_evt = event%get_index (), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
    call hepevt_write_ascii (eio%unit, .false.)
end select
else
    call eio%write ()
    call msg_fatal ("ASCII file is not open for writing")
end if
end subroutine eio_ascii_output

```

Input an event.

```

<EIO ascii: eio ascii: TBP>+≡
    procedure :: input_i_prc => eio_ascii_input_i_prc
    procedure :: input_event => eio_ascii_input_event

<EIO ascii: procedures>+≡
    subroutine eio_ascii_input_i_prc (eio, i_prc, iostat)
        class(eio_ascii_t), intent(inout) :: eio
        integer, intent(out) :: i_prc
        integer, intent(out) :: iostat
        call msg_bug ("ASCII: event input not supported")
        i_prc = 0
        iostat = 1
    end subroutine eio_ascii_input_i_prc

    subroutine eio_ascii_input_event (eio, event, iostat)
        class(eio_ascii_t), intent(inout) :: eio
        class(generic_event_t), intent(inout), target :: event
        integer, intent(out) :: iostat
        call msg_bug ("ASCII: event input not supported")
        iostat = 1
    end subroutine eio_ascii_input_event

```

17.6.4 Unit tests

```

<EIO ascii: public>+≡
    public :: eio_ascii_test

<EIO ascii: tests>≡
    subroutine eio_ascii_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <EIO ascii: execute tests>
    end subroutine eio_ascii_test

```

Test I/O methods

We test the implementation of all I/O methods, method `ascii`:

```

<EIO ascii: execute tests>≡
    call test (eio_ascii_1, "eio_ascii_1", &

```

```

        "read and write event contents, format [ascii]", &
        u, results)
<EIO ascii: tests>+≡
subroutine eio_ascii_1 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: eio_ascii_1"
    write (u, "(A)")  "*   Purpose: generate an event in ASCII ascii format"
    write (u, "(A)")  "*           and write weight to file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

    call eio_prepare_test (event, unweighted = .false.)

    call data%init (1)
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")
    write (u, "(A)")  "* Generate and write an event"
    write (u, "(A)")

    sample = "eio_ascii_1"

    allocate (eio_ascii_ascii_t :: eio)

    select type (eio)
    class is (eio_ascii_t); call eio%set_parameters ()
    end select
    call eio%init_out (sample, data)
    call event%generate (1, [0._default, 0._default])
    call event%evaluate_expressions ()

    call eio%output (event, i_prc = 1)
    call eio%write (u)
    call eio%final ()

    write (u, "(A)")
    write (u, "(A)")  "* File contents:"
    write (u, "(A)")

```

```

u_file = free_unit ()
open (u_file, file = char (sample // ".evt"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_ascii_t :: eio)

select type (eio)
type is (eio_ascii_ascii_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_1"

end subroutine eio_ascii_1

```

We test the implementation of all I/O methods, method `athena`:

```

<EIO ascii: execute tests>+≡
  call test (eio_ascii_2, "eio_ascii_2", &
    "read and write event contents, format [athena]", &
    u, results)

<EIO ascii: tests>+≡
  subroutine eio_ascii_2 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: eio_ascii_2"
    write (u, "(A)")  "*   Purpose: generate an event in ASCII athena format"
    write (u, "(A)")  "*           and write weight to file"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize test process"

call eio_prepare_test (event, unweighted = .false.)

call data%init (1)
data%n_evt = 1
data%n_beam = 2
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_ascii_2"

allocate (eio_ascii_athena_t :: eio)

select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char(sample // ".athena.evt"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)

```

```

allocate (eio_ascii_athena_t :: eio)

select type (eio)
type is (eio_ascii_athena_t)
    call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_2"

end subroutine eio_ascii_2

```

We test the implementation of all I/O methods, method `debug`:

```

<EIO ascii: execute tests>+≡
    call test (eio_ascii_3, "eio_ascii_3", &
        "read and write event contents, format [debug]", &
        u, results)

<EIO ascii: tests>+≡
subroutine eio_ascii_3 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: eio_ascii_3"
    write (u, "(A)")  "*   Purpose: generate an event in ASCII debug format"
    write (u, "(A)")  "*           and write weight to file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

    call eio_prepare_test (event, unweighted = .false.)

    call data%init (1)
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")

```

```

write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_ascii_3"

allocate (eio_ascii_debug_t :: eio)

select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".debug"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_debug_t :: eio)

select type (eio)
type is (eio_ascii_debug_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_3"

```

```
end subroutine eio_ascii_3
```

We test the implementation of all I/O methods, method `hepevt`:

```
<EIO ascii: execute tests>+≡
  call test (eio_ascii_4, "eio_ascii_4", &
    "read and write event contents, format [hepevt]", &
    u, results)

<EIO ascii: tests>+≡
  subroutine eio_ascii_4 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: eio_ascii_4"
    write (u, "(A)")  "* Purpose: generate an event in ASCII hepevt format"
    write (u, "(A)")  "* and write weight to file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

    call eio_prepare_test (event, unweighted = .false.)

    call data%init (1)
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")
    write (u, "(A)")  "* Generate and write an event"
    write (u, "(A)")

    sample = "eio_ascii_4"

    allocate (eio_ascii_hepevt_t :: eio)

    select type (eio)
    class is (eio_ascii_t); call eio%set_parameters ()
    end select
    call eio%init_out (sample, data)
    call event%generate (1, [0._default, 0._default])
    call event%evaluate_expressions ()

    call eio%output (event, i_prc = 1)
    call eio%write (u)
```

```

call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".hepevt"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat)  buffer
  if (buffer(1:21) == " <generator_version>")  buffer = "[...]"
  if (iostat /= 0)  exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_hepevt_t :: eio)

select type (eio)
type is (eio_ascii_hepevt_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_4"

end subroutine eio_ascii_4

```

We test the implementation of all I/O methods, method `lha` (old LHA):

```

<EIO ascii: execute tests>+≡
  call test (eio_ascii_5, "eio_ascii_5", &
    "read and write event contents, format [lha]", &
    u, results)

<EIO ascii: tests>+≡
subroutine eio_ascii_5 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat

```



```

character(80) :: buffer

write (u, "(A)")  "* Test output: eio_ascii_5"
write (u, "(A)")  "*   Purpose: generate an event in ASCII LHA format"
write (u, "(A)")  "*           and write weight to file"
write (u, "(A)")

write (u, "(A)")  "* Initialize test process"

call eio_prepare_test (event, unweighted = .false.)

call data%init (1)
data%n_evt = 1
data%n_beam = 2
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_ascii_5"

allocate (eio_ascii_lha_t :: eio)

select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".lha"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

```

```

write (u, "(A)")
write (u, "(A)")  "** Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_lha_t :: eio)

select type (eio)
type is (eio_ascii_lha_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "** Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "** Test output end: eio_ascii_5"

end subroutine eio_ascii_5

```

We test the implementation of all I/O methods, method long:

```

<EIO ascii: execute tests>+≡
  call test (eio_ascii_6, "eio_ascii_6", &
    "read and write event contents, format [long]", &
    u, results)

<EIO ascii: tests>+≡
subroutine eio_ascii_6 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat
  character(80) :: buffer

  write (u, "(A)")  "** Test output: eio_ascii_6"
  write (u, "(A)")  "** Purpose: generate an event in ASCII long format"
  write (u, "(A)")  "** and write weight to file"
  write (u, "(A)")

  write (u, "(A)")  "** Initialize test process"

  call eio_prepare_test (event, unweighted = .false.)

  call data%init (1)
  data%n_evt = 1
  data%n_beam = 2
  data%pdg_beam = 25
  data%energy_beam = 500

```

```

data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_ascii_6"

allocate (eio_ascii_long_t :: eio)

select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".long.evt"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_long_t :: eio)

select type (eio)
type is (eio_ascii_long_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```

```

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_6"

end subroutine eio_ascii_6

```

We test the implementation of all I/O methods, method mokka:

```

<EIO ascii: execute tests>+≡
call test (eio_ascii_7, "eio_ascii_7", &
  "read and write event contents, format [mokka]", &
  u, results)

<EIO ascii: tests>+≡
subroutine eio_ascii_7 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat
  character(80) :: buffer

  write (u, "(A)")  "* Test output: eio_ascii_7"
  write (u, "(A)")  "* Purpose: generate an event in ASCII mokka format"
  write (u, "(A)")  "* and write weight to file"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize test process"

  call eio_prepare_test (event, unweighted = .false.)

  call data%init (1)
  data%n_evt = 1
  data%n_beam = 2
  data%pdg_beam = 25
  data%energy_beam = 500
  data%proc_num_id = [42]
  data%cross_section(1) = 100
  data%error(1) = 1
  data%total_cross_section = sum (data%cross_section)

  write (u, "(A)")
  write (u, "(A)")  "* Generate and write an event"
  write (u, "(A)")

  sample = "eio_ascii_7"

  allocate (eio_ascii_mokka_t :: eio)

  select type (eio)
  class is (eio_ascii_t); call eio%set_parameters ()

```

```

end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".mokka.evt"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat)  buffer
  if (buffer(1:21) == " <generator_version>")  buffer = "[...]"
  if (iostat /= 0)  exit
  write (u, "(A)")  trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_mokka_t :: eio)

select type (eio)
type is (eio_ascii_mokka_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_7"

end subroutine eio_ascii_7

```

We test the implementation of all I/O methods, method **short**:

```

<EIO ascii: execute tests>+≡
  call test (eio_ascii_8, "eio_ascii_8", &
    "read and write event contents, format [short]", &
    u, results)
<EIO ascii: tests>+≡

```

```

subroutine eio_ascii_8 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat
  character(80) :: buffer

  write (u, "(A)")  "* Test output: eio_ascii_8"
  write (u, "(A)")  "*   Purpose: generate an event in ASCII short format"
  write (u, "(A)")  "*           and write weight to file"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize test process"

  call eio_prepare_test (event, unweighted = .false.)

  call data%init (1)
  data%n_evt = 1
  data%n_beam = 2
  data%pdg_beam = 25
  data%energy_beam = 500
  data%proc_num_id = [42]
  data%cross_section(1) = 100
  data%error(1) = 1
  data%total_cross_section = sum (data%cross_section)

  write (u, "(A)")
  write (u, "(A)")  "* Generate and write an event"
  write (u, "(A)")

  sample = "eio_ascii_8"

  allocate (eio_ascii_short_t :: eio)

  select type (eio)
  class is (eio_ascii_t); call eio%set_parameters ()
  end select
  call eio%init_out (sample, data)
  call event%generate (1, [0._default, 0._default])
  call event%evaluate_expressions ()

  call eio%output (event, i_prc = 1)
  call eio%write (u)
  call eio%final ()

  write (u, "(A)")
  write (u, "(A)")  "* File contents:"
  write (u, "(A)")

  u_file = free_unit ()
  open (u_file, file = char (sample // ".short.evt"), &
       action = "read", status = "old")

```

```

do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_short_t :: eio)

select type (eio)
type is (eio_ascii_short_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_8"

end subroutine eio_ascii_8

```

We test the implementation of all I/O methods, method `lha` (old LHA) in verbose version:

```

<EIO ascii: execute tests>+≡
  call test (eio_ascii_9, "eio_ascii_9", &
    "read and write event contents, format [lha_verb]", &
    u, results)

<EIO ascii: tests>+≡
  subroutine eio_ascii_9 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: eio_ascii_9"
    write (u, "(A)")  "*   Purpose: generate an event in ASCII LHA verbose format"
    write (u, "(A)")  "*           and write weight to file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

```

```

call eio_prepare_test (event, unweighted = .false.)

call data%init (1)
data%n_evt = 1
data%n_beam = 2
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_ascii_9"

allocate (eio_ascii_lha_verb_t :: eio)

select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".lha.verb"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_lha_verb_t :: eio)

```



```

select type (eio)
type is (eio_ascii_lha_verb_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_9"

end subroutine eio_ascii_9

```

We test the implementation of all I/O methods, method `hepevt_verb`:

(EIO ascii: execute tests)+≡

```

call test (eio_ascii_10, "eio_ascii_10", &
  "read and write event contents, format [hepevt_verb]", &
  u, results)

```

(EIO ascii: tests)+≡

```

subroutine eio_ascii_10 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat
  character(80) :: buffer

  write (u, "(A)")  "* Test output: eio_ascii_10"
  write (u, "(A)")  "*   Purpose: generate an event in ASCII hepevt verbose format"
  write (u, "(A)")  "*           and write weight to file"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize test process"

  call eio_prepare_test (event, unweighted = .false.)

  call data%init (1)
  data%n_evt = 1
  data%n_beam = 2
  data%pdg_beam = 25
  data%energy_beam = 500
  data%proc_num_id = [42]
  data%cross_section(1) = 100
  data%error(1) = 1
  data%total_cross_section = sum (data%cross_section)

  write (u, "(A)")
  write (u, "(A)")  "* Generate and write an event"
  write (u, "(A)")

```

```

sample = "eio_ascii_10"

allocate (eio_ascii_hepevt_verb_t :: eio)

select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".hepevt.verb"), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_ascii_hepevt_verb_t :: eio)

select type (eio)
type is (eio_ascii_hepevt_verb_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_ascii_10"

end subroutine eio_ascii_10

```

17.7 HEP Common Blocks

Long ago, to transfer data between programs one had to set up a common block and link both programs as libraries to the main executable. The HEP community standardizes several of those common blocks.

The modern way of data exchange uses data files with standard formats. However, the LHEF standard data format derives from a common block (actually, two).

WHIZARD used to support those common blocks, and LHEF was implemented via writing/reading blocks. We still keep this convention, but intend to eliminate common blocks (or any other static storage) from the workflow in the future. This will gain flexibility towards concurrent running of program images.

We encapsulate everything here in a module. The module holds the variables which are part of the common block. To access the common block variables, we just have to `use` this module. (They are nevertheless in the common block, since external software may access it in this way.)

Note: This code is taken essentially unchanged from WHIZARD 2.1 and does not (yet) provide unit tests.

```
(hep_common.f90)≡
  <File header>

  module hep_common

    use kinds
    use io_units
  <Use strings>
    use diagnostics
    use physics_defs, only: HADRON_REMNANT
    use physics_defs, only: HADRON_REMNANT_SINGLET
    use physics_defs, only: HADRON_REMNANT_TRIPLET
    use physics_defs, only: HADRON_REMNANT_OCTET
    use xml
    use lorentz
    use flavors
    use colors
    use polarizations
    use model_data
    use particles
    use subevents
    use unit_tests, only: nearly_equal

  <Standard module head>

  <HEP common: public>

  <HEP common: interfaces>

  <HEP common: parameters>

  <HEP common: variables>

  <HEP common: common blocks>
```

```
contains

<HEP common: procedures>

end module hep_common
```

17.7.1 Event characteristics

The maximal number of particles in an event record.

```
<HEP common: parameters>≡
    integer, parameter, public :: MAXNUP = 500
```

The number of particles in this event.

```
<HEP common: variables>≡
    integer, public :: NUP
```

The process ID for this event.

```
<HEP common: variables>+≡
    integer, public :: IDPRUP
```

The weight of this event (± 1 for unweighted events).

```
<HEP common: variables>+≡
    double precision, public :: XWGTUP
```

The factorization scale that is used for PDF calculation (-1 if undefined).

```
<HEP common: variables>+≡
    double precision, public :: SCALUP
```

The QED and QCD couplings α used for this event (-1 if undefined).

```
<HEP common: variables>+≡
    double precision, public :: AQEDUP
    double precision, public :: AQCDUP
```

17.7.2 Particle characteristics

The PDG code:

```
<HEP common: variables>+≡
    integer, dimension(MAXNUP) :: IDUP
```

The status code. Incoming: -1 , outgoing: $+1$. Intermediate t-channel propagator: -2 (currently not used by WHIZARD). Intermediate resonance whose mass should be preserved: 2 . Intermediate resonance for documentation: 3 (currently not used). Beam particles: -9 .

```
<HEP common: variables>+≡
    integer, dimension(MAXNUP), public :: ISTUP
```

Index of first and last mother.

```
<HEP common: variables>+≡
    integer, dimension(2,MAXNUP), public :: MOTHUP
```

Color line index of the color and anticolor entry for the particle. The standard recommends using large numbers; we start from $MAXNUP+1$.

```
<HEP common: variables>+≡
    integer, dimension(2,MAXNUP), public :: ICOLUP
```

Momentum, energy, and invariant mass: (p_x, p_y, p_z, E, M) . For space-like particles, M is the negative square root of the absolute value of the invariant mass.

$\langle \text{HEP common: variables} \rangle + \equiv$
`double precision, dimension(5,MAXNUP), public :: PUP`

Invariant lifetime (distance) from production to decay in mm.

$\langle \text{HEP common: variables} \rangle + \equiv$
`double precision, dimension(MAXNUP), public :: VTIMUP`

Cosine of the angle between the spin-vector and a particle and the 3-momentum of its mother, given in the lab frame. If undefined/unpolarized: 9.

$\langle \text{HEP common: variables} \rangle + \equiv$
`double precision, dimension(MAXNUP), public :: SPINUP`

17.7.3 The HEPRUP common block

This common block is filled once per run.

Run characteristics

The maximal number of different processes.

$\langle \text{HEP common: parameters} \rangle + \equiv$
`integer, parameter, public :: MAXPUP = 100`

The beam PDG codes.

$\langle \text{HEP common: variables} \rangle + \equiv$
`integer, dimension(2), public :: IDBMUP`

The beam energies in GeV.

$\langle \text{HEP common: variables} \rangle + \equiv$
`double precision, dimension(2), public :: EBMUP`

The PDF group and set for the two beams. (Undefined: use -1 ; LHAPDF: use group = 0).

$\langle \text{HEP common: variables} \rangle + \equiv$
`integer, dimension(2), public :: PDFGUP`
`integer, dimension(2), public :: PDFSUP`

The (re)weighting model. 1: events are weighted, the shower generator (SHG) selects processes according to the maximum weight (in pb) and unweights events. 2: events are weighted, the SHG selects processes according to their cross section (in pb) and unweights events. 3: events are unweighted and simply run through the SHG. 4: events are weighted, and the SHG keeps the weight. Negative numbers: negative weights are allowed (and are reweighted to ± 1 by the SHG, if allowed).

WHIZARD only supports modes 3 and 4, as the SHG is not given control over process selection. This is consistent with writing events to file, for offline showering.

$\langle \text{HEP common: variables} \rangle + \equiv$
`integer, public :: IDWTUP`

The number of different processes.

$\langle \text{HEP common: variables} \rangle + \equiv$
`integer, public :: NPRUP`

Process characteristics

Cross section and error in pb. (Cross section is needed only for IDWTUP = 2, so here both values are given for informational purposes only.)

```
<HEP common: variables>+≡  
    double precision, dimension(MAXPUP), public :: XSECUP  
    double precision, dimension(MAXPUP), public :: XERRUP
```

Maximum weight, i.e., the maximum value that XWGTUP can take. Also unused for the supported weighting models. It is ± 1 for unweighted events.

```
<HEP common: variables>+≡  
    double precision, dimension(MAXPUP), public :: XMAXUP
```

Internal ID of the selected process, matches IDPRUP below.

```
<HEP common: variables>+≡  
    integer, dimension(MAXPUP), public :: LPRUP
```

The common block

```
<HEP common: common blocks>≡  
    common /HEPRUP/ &  
        IDBMUP, EBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP, &  
        XSECUP, XERRUP, XMAXUP, LPRUP  
    save /HEPRUP/
```

Fill the run characteristics of the common block. The initialization sets the beam properties, number of processes, and weighting model.

```
<HEP common: public>≡  
    public :: heprup_init  
  
<HEP common: procedures>≡  
    subroutine heprup_init &  
        (beam_pdg, beam_energy, n_processes, unweighted, negative_weights)  
        integer, dimension(2), intent(in) :: beam_pdg  
        real(default), dimension(2), intent(in) :: beam_energy  
        integer, intent(in) :: n_processes  
        logical, intent(in) :: unweighted  
        logical, intent(in) :: negative_weights  
        IDBMUP = beam_pdg  
        EBMUP = beam_energy  
        PDFGUP = -1  
        PDFSUP = -1  
        if (unweighted) then  
            IDWTUP = 3  
        else  
            IDWTUP = 4  
        end if  
        if (negative_weights) IDWTUP = - IDWTUP  
        NPRUP = n_processes  
    end subroutine heprup_init
```

The HEPUP (event) common block is needed for the interface to the shower. Filling of it is triggered by some output file formats. If these are not present, the common block is filled with some dummy information. Be generous with the number of processes in HEPUP so that PYTHIA only rarely needs to be reinitialized in case events with higher process ids are generated.

```

<HEP common: public>+≡
    public :: assure_heprup

<HEP common: procedures>+≡
    subroutine assure_heprup (pset)
        type(particle_set_t), intent(in) :: pset
        integer :: i, num_id
        integer, parameter :: min_processes = 10
        num_id = 1
        if (LPRUP (num_id) /= 0) return
        call heprup_init ( &
            [pset%prt(1)%get_pdg (), pset%prt(2)%get_pdg ()] , &
            [pset%prt(1)%p%p(0), pset%prt(2)%p%p(0)], &
            num_id, .false., .false.)
        do i = 1, (num_id / min_processes + 1) * min_processes
            call heprup_set_process_parameters (i = i, process_id = &
                i, cross_section = 1._default, error = 1._default)
        end do
    end subroutine assure_heprup

```

Read in the LHE file opened in unit u and add the final particles to the `particle_set`, the outgoing particles of the existing `particle_set` are compared to the particles that are read in. When they are equal in flavor and momenta, they are erased and their mother-daughter relations are transferred to the existing particles.

```

<HEP common: public>+≡
    public :: combine_lhef_with_particle_set

<HEP common: procedures>+≡
    subroutine combine_lhef_with_particle_set &
        (particle_set, u, model_in, model_hadrons)
        type(particle_set_t), intent(inout) :: particle_set
        integer, intent(in) :: u
        class(model_data_t), intent(in), target :: model_in
        class(model_data_t), intent(in), target :: model_hadrons
        type(flavor_t) :: flv
        type(color_t) :: col
        class(model_data_t), pointer :: model
        type(particle_t), dimension(:), allocatable :: prt_tmp, prt
        integer :: i, j
        type(vector4_t) :: mom, d_mom
        integer, PARAMETER :: MAXLEN=200
        character(len=maxlen) :: string
        integer :: ibeg, n_tot, n_entries
        integer, dimension(:), allocatable :: relations, mothers, tbd
        INTEGER :: NUP, IDPRUP, IDUP, ISTUP
        real(kind=double) :: XWGTUP, SCALUP, AQEDUP, AQCDUP, VTIMUP, SPINUP
        integer :: MOTHUP(1:2), ICOLUP(1:2)
        real(kind=double) :: PUP(1:5)

```

```

real(kind=default) :: pup_dum(1:5)
character(len=5) :: buffer
character(len=6) :: strfmt
logical :: not_found
logical :: debug_lhef = .false.
STRFMT='(A000)'
WRITE (STRFMT(3:5),'(I3)') MAXLEN

if (debug_lhef) call particle_set%write ()

rewind (u)

do
  read (u,*, END=501, ERR=502) STRING
  IBEG = 0
  do
    if (signal_is_pending ()) return
    IBEG = IBEG + 1
    ! Allow indentation.
    IF (STRING (IBEG:IBEG) .EQ. ' ' .and. IBEG < MAXLEN-6) cycle
    exit
  end do
  IF (string(IBEG:IBEG+6) /= '<event>' .and. &
    string(IBEG:IBEG+6) /= '<event ') cycle
  exit
end do
!!! Read first line of event info -> number of entries
read (u, *, END=503, ERR=504) NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
n_tot = particle_set%get_n_tot ()
allocate (prt_tmp (1:n_tot+NUP))
allocate (relations (1:NUP), mothers (1:NUP), tbd(1:NUP))
do i = 1, n_tot
  if (signal_is_pending ()) return
  prt_tmp (i) = particle_set%get_particle (i)
end do
!!! transfer particles from lhef to particle_set
!!!...Read NUP subsequent lines with information on each particle.
n_entries = 1
mothers = 0
relations = 0
PARTICLE_LOOP: do I = 1, NUP
  read (u,*, END=200, ERR=505) IDUP, ISTUP, MOTHUP(1), MOTHUP(2), &
    ICOLUP(1), ICOLUP(2), (PUP (J),J=1,5), VTIMUP, SPINUP
  if (model_in%test_field (IDUP)) then
    model => model_in
  else if (model_hadrons%test_field (IDUP)) then
    model => model_hadrons
  else
    write (buffer, "(I5)") IDUP
    call msg_error ("Parton " // buffer // &
      " found neither in given model file nor in SM_hadrons")
    return
  end if
  if (debug_lhef) then

```



```

        print *, "IDUP, ISTUP, MOTHUP, PUP = ", IDUP, ISTUP, MOTHUP(1), &
            MOTHUP(2), PUP
    end if
    call flv%init (IDUP, model)
    if (IABS(IDUP) == 2212 .or. IABS(IDUP) == 2112) then
        ! PYTHIA sometimes sets color indices for protons and neutrons (?)
        ICOLUP (1) = 0
        ICOLUP (2) = 0
    end if
    call col%init_col_acl (ICOLUP (1), ICOLUP (2))
    !!! Settings for unpolarized particles
    ! particle_set%prt (oldsize+i)%hel = ??
    ! particle_set%prt (oldsize+i)%pol = ??
    if (MOTHUP(1) /= 0) then
        mothers(i) = MOTHUP(1)
    end if
    pup_dum = PUP
    if (pup_dum(4) < 1E-10_default) cycle
    mom = vector4_moving (pup_dum (4), &
        vector3_moving ([pup_dum (1), pup_dum (2), pup_dum (3)]))
    not_found = .true.
    SCAN_PARTICLES: do j = 1, n_tot
        d_mom = prt_tmp(j)%get_momentum ()
        if (all (nearly_equal &
            (mom%p, d_mom%p, abs_smallness = 1.E-4_default)) .and. &
            (prt_tmp(j)%get_pdg () == IDUP)) then
            if (.not. prt_tmp(j)%get_status () == PRT_BEAM .or. &
                .not. prt_tmp(j)%get_status () == PRT_BEAM_REMNANT) &
                relations(i) = j
            not_found = .false.
        end if
    end do SCAN_PARTICLES
    if (not_found) then
        if (debug_lhef) &
            print *, "Not found: adding particle"
        call prt_tmp(n_tot+n_entries)%set_flavor (flv)
        call prt_tmp(n_tot+n_entries)%set_color (col)
        call prt_tmp(n_tot+n_entries)%set_momentum (mom)
        if (MOTHUP(1) /= 0) then
            if (relations(MOTHUP(1)) /= 0) then
                call prt_tmp(n_tot+n_entries)%set_parents &
                    ([relations(MOTHUP(1))])
                call prt_tmp(relations(MOTHUP(1)))%add_child (n_tot+n_entries)
                if (prt_tmp(relations(MOTHUP(1)))%get_status () &
                    == PRT_OUTGOING) &
                    call prt_tmp(relations(MOTHUP(1)))%reset_status &
                        (PRT_VIRTUAL)
            end if
        end if
        call prt_tmp(n_tot+n_entries)%set_status (PRT_OUTGOING)
        if (debug_lhef) call prt_tmp(n_tot+n_entries)%write ()
        n_entries = n_entries + 1
    end if
end do PARTICLE_LOOP

```

```

do i = 1, n_tot
  if (prt_tmp(i)%get_status () == PRT_OUTGOING .and. &
    prt_tmp(i)%get_n_children () /= 0) then
    call prt_tmp(i)%reset_status (PRT_VIRTUAL)
  end if
end do

allocate (prt (1:n_tot+n_entries-1))
prt = prt_tmp (1:n_tot+n_entries-1)
! transfer to particle_set
call particle_set%replace (prt)
deallocate (prt, prt_tmp)

if (debug_lhef) then
  call particle_set%write ()
  print *, "combine_lhef_with_particle_set"
  ! stop
end if

200 continue
return

501 write(*,*) "READING LHEF failed 501"
return
502 write(*,*) "READING LHEF failed 502"
return
503 write(*,*) "READING LHEF failed 503"
return
504 write(*,*) "READING LHEF failed 504"
return
505 write(*,*) "READING LHEF failed 505"
return
end subroutine combine_lhef_with_particle_set

```

<HEP common: public>+≡

public :: w2p_write_lhef_event

<HEP common: procedures>+≡

```

subroutine w2p_write_lhef_event (unit)
  integer, intent(in) :: unit
  type(xml_tag_t), allocatable :: tag_lhef, tag_head, tag_init, &
    tag_event, tag_gen_n, tag_gen_v
  allocate (tag_lhef, tag_head, tag_init, tag_event, &
    tag_gen_n, tag_gen_v)
  call tag_lhef%init (var_str ("LesHouchesEvents"), &
    [xml_attribute (var_str ("version"), var_str ("1.0"))], .true.)
  call tag_head%init (var_str ("header"), .true.)
  call tag_init%init (var_str ("init"), .true.)
  call tag_event%init (var_str ("event"), .true.)
  call tag_gen_n%init (var_str ("generator_name"), .true.)
  call tag_gen_v%init (var_str ("generator_version"), .true.)
  call tag_lhef%write (unit); write (unit, *)
  call tag_head%write (unit); write (unit, *)
  write (unit, "(2x)", advance = "no")

```

```

call tag_gen_n%write (var_str ("WHIZARD"), unit)
write (unit, *)
write (unit, "(2x)", advance = "no")
call tag_gen_v%write (var_str ("Version"), unit)
write (unit, *)
call tag_head%close (unit); write (unit, *)
call tag_init%write (unit); write (unit, *)
call heprup_write_lhef (unit)
call tag_init%close (unit); write (unit, *)
call tag_event%write (unit); write (unit, *)
call hepeup_write_lhef (unit)
call tag_event%close (unit); write (unit, *)
call tag_lhef%close (unit); write (unit, *)
deallocate (tag_lhef, tag_head, tag_init, tag_event, &
            tag_gen_n, tag_gen_v)
end subroutine w2p_write_lhef_event

```

Extract parameters from the common block. We leave it to the caller to specify which parameters it actually needs.

PDFGUP and PDFSUP are not extracted. IDWTUP=1,2 are not supported by WHIZARD, but correspond to weighted events.

```

<HEP common: public>+≡
public :: heprup_get_run_parameters

<HEP common: procedures>+≡
subroutine heprup_get_run_parameters &
    (beam_pdg, beam_energy, n_processes, unweighted, negative_weights)
integer, dimension(2), intent(out), optional :: beam_pdg
real(default), dimension(2), intent(out), optional :: beam_energy
integer, intent(out), optional :: n_processes
logical, intent(out), optional :: unweighted
logical, intent(out), optional :: negative_weights
if (present (beam_pdg)) beam_pdg = IDBMUP
if (present (beam_energy)) beam_energy = EBMUP
if (present (n_processes)) n_processes = NPRUP
if (present (unweighted)) then
    select case (abs (IDWTUP))
    case (3)
        unweighted = .true.
    case (4)
        unweighted = .false.
    case (1,2) !!! not supported by WHIZARD
        unweighted = .false.
    case default
        call msg_fatal ("HEPRUP: unsupported IDWTUP value")
    end select
end if
if (present (negative_weights)) then
    negative_weights = IDWTUP < 0
end if
end subroutine heprup_get_run_parameters

```

Specify PDF set info. Since we support only LHAPDF, the group entry is zero.

```

<HEP common: public>+≡
  public :: heprup_set_lhapdf_id

<HEP common: procedures>+≡
  subroutine heprup_set_lhapdf_id (i_beam, pdf_id)
    integer, intent(in) :: i_beam, pdf_id
    PDFGUP(i_beam) = 0
    PDFSUP(i_beam) = pdf_id
  end subroutine heprup_set_lhapdf_id

```

Fill the characteristics for a particular process. Only the process ID is mandatory. Note that WHIZARD computes cross sections in fb, so we have to rescale to pb. The maximum weight is meaningless for unweighted events.

```

<HEP common: public>+≡
  public :: heprup_set_process_parameters

<HEP common: procedures>+≡
  subroutine heprup_set_process_parameters &
    (i, process_id, cross_section, error, max_weight)
    integer, intent(in) :: i, process_id
    real(default), intent(in), optional :: cross_section, error, max_weight
    real(default), parameter :: pb_per_fb = 1.e-3_default
    LPRUP(i) = process_id
    if (present (cross_section)) then
      XSECUP(i) = cross_section * pb_per_fb
    else
      XSECUP(i) = 0
    end if
    if (present (error)) then
      XERRUP(i) = error * pb_per_fb
    else
      XERRUP(i) = 0
    end if
    select case (IDWTUP)
    case (3); XMAXUP(i) = 1
    case (4)
      if (present (max_weight)) then
        XMAXUP(i) = max_weight * pb_per_fb
      else
        XMAXUP(i) = 0
      end if
    end select
  end subroutine heprup_set_process_parameters

```

Extract the process parameters, as far as needed.

```

<HEP common: public>+≡
  public :: heprup_get_process_parameters

<HEP common: procedures>+≡
  subroutine heprup_get_process_parameters &
    (i, process_id, cross_section, error, max_weight)
    integer, intent(in) :: i
    integer, intent(out), optional :: process_id
    real(default), intent(out), optional :: cross_section, error, max_weight

```

```

real(default), parameter :: pb_per_fb = 1.e-3_default
if (present (process_id)) process_id = LPRUP(i)
if (present (cross_section)) then
    cross_section = XSECUP(i) / pb_per_fb
end if
if (present (error)) then
    error = XERRUP(i) / pb_per_fb
end if
if (present (max_weight)) then
    select case (IDWTUP)
    case (3)
        max_weight = 1
    case (4)
        max_weight = XMAXUP(i) / pb_per_fb
    case (1,2)    !!! not supported by WHIZARD
        max_weight = 0
    case default
        call msg_fatal ("HEPRUP: unsupported IDWTUP value")
    end select
end if
end subroutine heprup_get_process_parameters

```

17.7.4 Run parameter output (verbose)

This is a verbose output of the HEPRUP block.

```

<HEP common: public>+=
    public :: heprup_write_verbose

<HEP common: procedures>+=
    subroutine heprup_write_verbose (unit)
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(A)") "HEPRUP Common Block"
        write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "IDBMUP", IDBMUP, &
            "PDG code of beams"
        write (u, "(3x,A6,' = ',G12.5,1x,G12.5,8x,A)") "EBMUP ", EBMUP, &
            "Energy of beams in GeV"
        write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "PDFGUP", PDFGUP, &
            "PDF author group [-1 = undefined]"
        write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "PDFSUP", PDFSUP, &
            "PDF set ID [-1 = undefined]"
        write (u, "(3x,A6,' = ',I9,3x,1x,9x,3x,8x,A)") "IDWTUP", IDWTUP, &
            "LHA code for event weight mode"
        write (u, "(3x,A6,' = ',I9,3x,1x,9x,3x,8x,A)") "NPRUP ", NPRUP, &
            "Number of user subprocesses"
        do i = 1, NPRUP
            write (u, "(1x,A,I0)") "Subprocess #", i
            write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "XSECUP", XSECUP(i), &
                "Cross section in pb"
            write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "XERRUP", XERRUP(i), &
                "Cross section error in pb"
            write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "XMAXUP", XMAXUP(i), &

```

```

        "Maximum event weight (cf. IDWTUP)"
        write (u, "(3x,A6,' = ',I9,3x,1x,12x,8x,A)" "LPRUP ", LPRUP(i), &
        "Subprocess ID"
    end do
end subroutine heprup_write_verbose

```

17.7.5 Run parameter output (other formats)

This routine writes the initialization block according to the LHEF standard. It uses the current contents of the HEPRUP block.

```

<HEP common: public>+≡
    public :: heprup_write_lhef

<HEP common: procedures>+≡
    subroutine heprup_write_lhef (unit)
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(2(1x,I0),2(1x,ES17.10),6(1x,I0))" &
            IDBMUP, EBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP
        do i = 1, NPRUP
            write (u, "(3(1x,ES17.10),1x,I0)" &
                XSECUP(i), XERRUP(i), XMAXUP(i), LPRUP(i)
        end do
    end subroutine heprup_write_lhef

```

This routine is a complete dummy at the moment. It uses the current contents of the HEPRUP block. At the end, it should depend on certain input flags for the different ASCII event formats.

```

<HEP common: public>+≡
    public :: heprup_write_ascii

<HEP common: procedures>+≡
    subroutine heprup_write_ascii (unit)
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(2(1x,I0),2(1x,ES17.10),6(1x,I0))" &
            IDBMUP, EBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP
        do i = 1, NPRUP
            write (u, "(3(1x,ES17.10),1x,I0)" &
                XSECUP(i), XERRUP(i), XMAXUP(i), LPRUP(i)
        end do
    end subroutine heprup_write_ascii

```

Run parameter input (LHEF)

In a LHEF file, the parameters are written in correct order on separate lines, but we should not count on the precise format. List-directed input should just work.

```

<HEP common: public>+≡

```

```

public :: heprup_read_lhef
<HEP common: procedures>+≡
subroutine heprup_read_lhef (u)
  integer, intent(in) :: u
  integer :: i
  read (u, *) &
    IDBMUP, EBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP
  do i = 1, NPRUP
    read (u, *) &
      XSECUP(i), XERRUP(i), XMAXUP(i), LPRUP(i)
  end do
end subroutine heprup_read_lhef

```

17.7.6 The HEPEUP common block

```

<HEP common: common blocks>+≡
common /HEPEUP/ &
  NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP, &
  IDUP, ISTUP, MOTHUP, ICOLUP, PUP, VTIMUP, SPINUP
save /HEPEUP/

```

Initialization

Fill the event characteristics of the common block. The initialization sets only the number of particles and initializes the rest with default values. The other routine sets the optional parameters.

```

<HEP common: public>+≡
public :: hepeup_init
public :: hepeup_set_event_parameters

<HEP common: procedures>+≡
subroutine hepeup_init (n_tot)
  integer, intent(in) :: n_tot
  NUP = n_tot
  IDPRUP = 0
  XWGTUP = 1
  SCALUP = -1
  AQEDUP = -1
  AQCDUP = -1
end subroutine hepeup_init

subroutine hepeup_set_event_parameters &
  (proc_id, weight, scale, alpha_qed, alpha_qcd)
  integer, intent(in), optional :: proc_id
  real(default), intent(in), optional :: weight, scale, alpha_qed, alpha_qcd
  if (present (proc_id)) IDPRUP = proc_id
  if (present (weight)) XWGTUP = weight
  if (present (scale)) SCALUP = scale
  if (present (alpha_qed)) AQEDUP = alpha_qed
  if (present (alpha_qcd)) AQCDUP = alpha_qcd
end subroutine hepeup_set_event_parameters

```

Extract event information. The caller determines the parameters.

```

<HEP common: public>+≡
    public :: hepeup_get_event_parameters

<HEP common: procedures>+≡
    subroutine hepeup_get_event_parameters &
        (proc_id, weight, scale, alpha_qed, alpha_qcd)
        integer, intent(out), optional :: proc_id
        real(default), intent(out), optional :: weight, scale, alpha_qed, alpha_qcd
        if (present (proc_id)) proc_id = IDPRUP
        if (present (weight)) weight = XWGTUP
        if (present (scale)) scale = SCALUP
        if (present (alpha_qed)) alpha_qed = AQEDUP
        if (present (alpha_qcd)) alpha_qcd = AQCDUP
    end subroutine hepeup_get_event_parameters

```

Particle data

Below we need the particle status codes which are actually defined in the `subevents` module.

Set the entry for a specific particle. All parameters are set with the exception of lifetime and spin, where default values are stored.

```

<HEP common: public>+≡
    public :: hepeup_set_particle

<HEP common: procedures>+≡
    subroutine hepeup_set_particle (i, pdg, status, parent, col, p, m2)
        integer, intent(in) :: i
        integer, intent(in) :: pdg, status
        integer, dimension(:), intent(in) :: parent
        type(vector4_t), intent(in) :: p
        integer, dimension(2), intent(in) :: col
        real(default), intent(in) :: m2
        if (i > MAXNUP) then
            call msg_error (arr=[ &
                var_str ("Too many particles in HEPEUP common block. " // &
                    "If this happened "), &
                var_str ("during event output, your events will be " // &
                    "invalid; please consider "), &
                var_str ("switching to a modern event format like HEPMC. " // &
                    "If you are not "), &
                var_str ("using an old, HEPEUP based format and " // &
                    "nevertheless get this error,"), &
                var_str ("please notify the WHIZARD developers,") ])
            return
        end if
        IDUP(i) = pdg
        select case (status)
        case (PRT_BEAM);          ISTUP(i) = -9
        case (PRT_INCOMING);      ISTUP(i) = -1
        case (PRT_BEAM_REMNANT);  ISTUP(i) = 3
        case (PRT_OUTGOING);      ISTUP(i) = 1

```



```

      case (PRT_RESONANT);      ISTUP(i) = 2
      case (PRT_VIRTUAL);      ISTUP(i) = 3
      case default;            ISTUP(i) = 0
    end select
    select case (size (parent))
    case (0);      MOTHUP(:,i) = 0
    case (1);      MOTHUP(1,i) = parent(1); MOTHUP(2,i) = 0
    case default;  MOTHUP(:,i) = [ parent(1), parent(size (parent)) ]
    end select
    if (col(1) > 0) then
      ICOLUP(1,i) = 500 + col(1)
    else
      ICOLUP(1,i) = 0
    end if
    if (col(2) > 0) then
      ICOLUP(2,i) = 500 + col(2)
    else
      ICOLUP(2,i) = 0
    end if
    PUP(1:3,i) = vector3_get_components (space_part (p))
    PUP(4,i) = energy (p)
    PUP(5,i) = sign (sqrt (abs (m2)), m2)
    VTIMUP(i) = 0
    SPINUP(i) = 9
  end subroutine hepeup_set_particle

```

Set the lifetime, actually $c\tau$ measured in mm, where τ is the invariant lifetime.

```

<HEP common: public>+=
  public :: hepeup_set_particle_lifetime

<HEP common: procedures>+=
  subroutine hepeup_set_particle_lifetime (i, lifetime)
    integer, intent(in) :: i
    real(default), intent(in) :: lifetime
    VTIMUP(i) = lifetime
  end subroutine hepeup_set_particle_lifetime

```

Set the particle spin entry. We need the cosine of the angle of the spin axis with respect to the three-momentum of the parent particle.

If the particle has a full polarization density matrix given, we need the particle momentum and polarization as well as the mother-particle momentum. The polarization is transformed into a spin vector (which is sensible only for spin-1/2 or massless particles), which then is transformed into the lab frame (by a rotation of the 3-axis to the particle momentum axis). Finally, we compute the scalar product of this vector with the mother-particle three-momentum.

This puts severe restrictions on the applicability of this definition, and Lorentz invariance is lost. Unfortunately, the Les Houches Accord requires this computation.

```

<HEP common: public>+=
  public :: hepeup_set_particle_spin

<HEP common: interfaces>=
  interface hepeup_set_particle_spin

```

```

        module procedure hepeup_set_particle_spin_pol
    end interface

    <HEP common: procedures>+≡
    subroutine hepeup_set_particle_spin_pol (i, p, pol, p_mother)
        integer, intent(in) :: i
        type(vector4_t), intent(in) :: p
        type(polarization_t), intent(in) :: pol
        type(vector4_t), intent(in) :: p_mother
        type(vector3_t) :: s3, p3
        type(vector4_t) :: s4
        s3 = vector3_moving (polarization_get_axis (pol))
        p3 = space_part (p)
        s4 = rotation_to_2nd (3, p3) * vector4_moving (0._default, s3)
        SPINUP(i) = enclosed_angle_ct (s4, p_mother)
    end subroutine hepeup_set_particle_spin_pol

```

Extract particle data. The caller decides which ones to retrieve.

Status codes: beam remnants share the status code with virtual particles. However, for the purpose of WHIZARD we should identify them. We use the PDG code for this.

```

    <HEP common: public>+≡
    public :: hepeup_get_particle

    <HEP common: procedures>+≡
    subroutine hepeup_get_particle (i, pdg, status, parent, col, p, m2)
        integer, intent(in) :: i
        integer, intent(out), optional :: pdg, status
        integer, dimension(:), intent(out), optional :: parent
        type(vector4_t), intent(out), optional :: p
        integer, dimension(2), intent(out), optional :: col
        real(default), dimension(5,MAXNUP) :: pup_def
        real(default), intent(out), optional :: m2
        if (present (pdg)) pdg = IDUP(i)
        if (present (status)) then
            select case (ISTUP(i))
            case (-9); status = PRT_BEAM
            case (-1); status = PRT_INCOMING
            case (1); status = PRT_OUTGOING
            case (2); status = PRT_RESONANT
            case (3);
                select case (abs (IDUP(i)))
                case (HADRON_REMNANT, HADRON_REMNANT_SINGLET, &
                     HADRON_REMNANT_TRIPLET, HADRON_REMNANT_OCTET)
                    status = PRT_BEAM_REMNANT
                case default
                    status = PRT_VIRTUAL
                end select
            case default
                status = PRT_UNDEFINED
            end select
        end if
        if (present (parent)) then
            select case (size (parent))

```

```

      case (0)
      case (1);    parent(1) = MOTHUP(1,i)
      case (2);    parent = MOTHUP(:,i)
      end select
    end if
    if (present (col)) then
      col = ICOLUP(:,i)
    end if
    if (present (p)) then
      pup_def = PUP
      p = vector4_moving (pup_def(4,i), vector3_moving (pup_def(1:3,i)))
    end if
    if (present (m2)) then
      m2 = sign (PUP(5,i) ** 2, PUP(5,i))
    end if
  end subroutine hepeup_get_particle

```

17.7.7 The HEPEVT common block

For the LEP Monte Carlos, a standard common block has been proposed in AKV89. We strongly recommend its use. (The description is an abbreviated transcription of AKV89, Vol. 3, pp. 327-330).

NMXHEP is the maximum number of entries:

```

<HEP common: variables>+≡
  integer, parameter :: NMXHEP = 4000

```

NEVHEP is normally the event number, but may take special values as follows:

0 the program does not keep track of event numbers. -1 a special initialization record. -2 a special final record.

```

<HEP common: variables>+≡
  integer :: NEVHEP

```

NHEP holds the number of entries for this event.

```

<HEP common: variables>+≡
  integer :: NHEP

```

The entry ISTHEP(N) gives the status code for the Nth entry, with the following semantics: 0 a null entry. 1 an existing entry, which has not decayed or fragmented. 2 a decayed or fragmented entry, which is retained for event history information. 3 documentation line. 4- 10 reserved for future standards. 11-200 at the disposal of each model builder. 201- at the disposal of users.

```

<HEP common: variables>+≡
  integer, dimension(NMXHEP) :: ISTHEP

```

The Particle Data Group has proposed standard particle codes, which are to be stored in IDHEP(N).

```

<HEP common: variables>+≡
  integer, dimension(NMXHEP) :: IDHEP

```

JMOHEP(1,N) points to the mother of the Nth entry, if any. It is set to zero for initial entries. JMOHEP(2,N) points to the second mother, if any.

```
<HEP common: variables>+≡
integer, dimension(2, NMXHEP) :: JMOHEP
```

JDAHEP(1,N) and JDAHEP(2,N) point to the first and last daughter of the Nth entry, if any. These are zero for entries which have not yet decayed. The other daughters are stored in between these two.

```
<HEP common: variables>+≡
integer, dimension(2, NMXHEP) :: JDAHEP
```

In PHEP we store the momentum of the particle, more specifically this means that PHEP(1,N), PHEP(2,N), and PHEP(3,N) contain the momentum in the x , y , and z direction (as defined by the machine people), measured in GeV/c. PHEP(4,N) contains the energy in GeV and PHEP(5,N) the mass in GeV/ c^2 . The latter may be negative for spacelike partons.

```
<HEP common: variables>+≡
double precision, dimension(5, NMXHEP) :: PHEP
```

Finally VHEP is the place to store the position of the production vertex. VHEP(1,N), VHEP(2,N), and VHEP(3,N) contain the x , y , and z coordinate (as defined by the machine people), measured in mm. VHEP(4,N) contains the production time in mm/c.

```
<HEP common: variables>+≡
double precision, dimension(4, NMXHEP) :: VHEP
```

As an amendment to the proposed standard common block HEPEVT, we also have a polarisation common block HEPSPN, as described in AKV89. SHEP(1,N), SHEP(2,N), and SHEP(3,N) give the x , y , and z component of the spinvector s of a fermion in the fermions restframe.

Furthermore, we add the polarization of the corresponding outgoing particles:

```
<HEP common: variables>+≡
integer, dimension(NMXHEP) :: hepevt_pol
```

By convention, SHEP(4,N) is always 1. All this is taken from StdHep 4.06 manual and written using Fortran90 conventions.

```
<HEP common: common blocks>+≡
common /HEPEVT/ &
NEVHEP, NHEP, ISTHEP, IDHEP, &
JMOHEP, JDAHEP, PHEP, VHEP
save /HEPEVT/
```

Here we store HEPEVT parameters of the WHIZARD 1 realization which are not part of the HEPEVT common block.

```
<HEP common: variables>+≡
integer :: hepevt_n_out, hepevt_n_remnants
```

```

<HEP common: variables>+≡
  double precision :: hepevt_weight, hepevt_function_value
  double precision :: hepevt_function_ratio

```

Filling HEPEVT: If the event count is not provided, set NEVHEP to zero. If the event count is -1 or -2, the record corresponds to initialization and finalization, and the event is irrelevant.

Note that the event count may be larger than 2^{31} (2 GEvents). In that case, cut off the upper bits since NEVHEP is probably limited to default integer.

```

<HEP common: public>+≡
  public :: hepevt_init
  public :: hepevt_set_event_parameters

<HEP common: procedures>+≡
  subroutine hepevt_init (n_tot, n_out)
    integer, intent(in) :: n_tot, n_out
    NHEP                = n_tot
    NEVHEP              = 0
    hepevt_n_out        = n_out
    hepevt_n_remnants = 0
    hepevt_weight       = 1
    hepevt_function_value = 0
    hepevt_function_ratio = 1
  end subroutine hepevt_init

  subroutine hepevt_set_event_parameters &
    (weight, function_value, function_ratio, i_evt)
    integer, intent(in), optional :: i_evt
    real(default), intent(in), optional :: weight, function_value, &
      function_ratio
    if (present (i_evt)) NEVHEP = i_evt
    if (present (weight)) hepevt_weight = weight
    if (present (function_value)) hepevt_function_value = &
      function_value
    if (present (function_ratio)) hepevt_function_ratio = &
      function_ratio
  end subroutine hepevt_set_event_parameters

```

Set the entry for a specific particle. All parameters are set with the exception of lifetime and spin, where default values are stored.

```

<HEP common: public>+≡
  public :: hepevt_set_particle

<HEP common: procedures>+≡
  subroutine hepevt_set_particle &
    (i, pdg, status, parent, child, p, m2, hel, vtx)
    integer, intent(in) :: i
    integer, intent(in) :: pdg, status
    integer, dimension(:), intent(in) :: parent
    integer, dimension(:), intent(in) :: child
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: m2
    integer, intent(in) :: hel

```

```

type(vector4_t), intent(in) :: vtx
IDHEP(i) = pdg
select case (status)
  case (PRT_BEAM);      ISTHEP(i) = 2
  case (PRT_INCOMING);  ISTHEP(i) = 2
  case (PRT_OUTGOING);  ISTHEP(i) = 1
  case (PRT_VIRTUAL);   ISTHEP(i) = 2
  case (PRT_RESONANT);  ISTHEP(i) = 2
  case default;         ISTHEP(i) = 0
end select
select case (size (parent))
case (0);      JMOHEP(:,i) = 0
case (1);      JMOHEP(1,i) = parent(1); JMOHEP(2,i) = 0
case default;  JMOHEP(:,i) = [ parent(1), parent(size (parent)) ]
end select
select case (size (child))
case (0);      JDAHEP(:,i) = 0
case (1);      JDAHEP(:,i) = child(1)
case default;  JDAHEP(:,i) = [ child(1), child(size (child)) ]
end select
PHEP(1:3,i) = vector3_get_components (space_part (p))
PHEP(4,i) = energy (p)
PHEP(5,i) = sign (sqrt (abs (m2)), m2)
VHEP(1:3,i) = vtx%p(1:3)
VHEP(4,i) = vtx%p(0)
hepevt_pol(i) = hel
end subroutine hepevt_set_particle

```

17.7.8 Event output

This is a verbose output of the HEPEVT block.

```

<HEP common: public>+≡
  public :: hepevt_write_verbose

<HEP common: procedures>+≡
  subroutine hepevt_write_verbose (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A)") "HEPEVT Common Block"
    write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "NEVHEP", NEVHEP, &
      "Event number"
    write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "NHEP ", NHEP, &
      "Number of particles in event"
    do i = 1, NHEP
      write (u, "(1x,A,I0)") "Particle #", i
      write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)", advance="no") &
        "ISTHEP", ISTHEP(i), "Status code: "
      select case (ISTHEP(i))
        case ( 0); write (u, "(A)") "null entry"
        case ( 1); write (u, "(A)") "outgoing"
        case ( 2); write (u, "(A)") "decayed"
        case ( 3); write (u, "(A)") "documentation"
      end select
    end do
  end subroutine

```

```

case (4:10); write (u, "(A)") "[unspecified]"
case (11:200); write (u, "(A)") "[model-specific]"
case (201:); write (u, "(A)") "[user-defined]"
case default; write (u, "(A)") "[undefined]"
end select
write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "IDHEP ", IDHEP(i), &
"PDG code of particle"
write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "JMOHEP", JMOHEP(:,i), &
"Index of first/second mother"
write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "JDAHEP", JDAHEP(:,i), &
"Index of first/last daughter"
write (u, "(3x,A6,' = ',ES12.5,1x,ES12.5,8x,A)") "PHEP12", &
PHEP(1:2,i), "Transversal momentum (x/y) in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "PHEP3 ", PHEP(3,i), &
"Longitudinal momentum (z) in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "PHEP4 ", PHEP(4,i), &
"Energy in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "PHEP5 ", PHEP(5,i), &
"Invariant mass in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,ES12.5,8x,A)") "VHEP12", VHEP(1:2,i), &
"Transversal displacement (xy) in mm"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "VHEP3 ", VHEP(3,i), &
"Longitudinal displacement (z) in mm"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)") "VHEP4 ", VHEP(4,i), &
"Production time in mm"
end do
end subroutine hepevt_write_verbose

```

This is a verbose output of the HEPEUP block.

(HEP common: public)+≡

```
public :: hepeup_write_verbose
```

(HEP common: procedures)+≡

```

subroutine hepeup_write_verbose (unit)
integer, intent(in), optional :: unit
integer :: u, i
u = given_output_unit (unit); if (u < 0) return
write (u, "(A)") "HEPEUP Common Block"
write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "NUP ", NUP, &
"Number of particles in event"
write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "IDPRUP", IDPRUP, &
"Subprocess ID"
write (u, "(3x,A6,' = ',ES12.5,1x,20x,A)") "XWGTUP", XWGTUP, &
"Event weight"
write (u, "(3x,A6,' = ',ES12.5,1x,20x,A)") "SCALUP", SCALUP, &
"Event energy scale in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,20x,A)") "AQEDUP", AQEDUP, &
"QED coupling [-1 = undefined]"
write (u, "(3x,A6,' = ',ES12.5,1x,20x,A)") "AQCDUP", AQCDUP, &
"QCD coupling [-1 = undefined]"
do i = 1, NUP
write (u, "(1x,A,I0)") "Particle #", i
write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "IDUP ", IDUP(i), &
"PDG code of particle"

```

```

write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)", advance="no") &
  "ISTUP ", ISTUP(i), "Status code: "
select case (ISTUP(i))
case (-1); write (u, "(A)" "incoming"
case ( 1); write (u, "(A)" "outgoing"
case (-2); write (u, "(A)" "spacelike"
case ( 2); write (u, "(A)" "resonance"
case ( 3); write (u, "(A)" "resonance (doc)"
case (-9); write (u, "(A)" "beam"
case default; write (u, "(A)" "[undefined]"
end select
write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)" "MOTHUP", MOTHUP(:,i), &
  "Index of first/last mother"
write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)" "ICOLUP", ICOLUP(:,i), &
  "Color/anticolor flow index"
write (u, "(3x,A6,' = ',ES12.5,1x,ES12.5,8x,A)" "PUP1/2", PUP(1:2,i), &
  "Transversal momentum (x/y) in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)" "PUP3 ", PUP(3,i), &
  "Longitudinal momentum (z) in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)" "PUP4 ", PUP(4,i), &
  "Energy in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)" "PUP5 ", PUP(5,i), &
  "Invariant mass in GeV"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)" "VTIMUP", VTIMUP(i), &
  "Invariant lifetime in mm"
write (u, "(3x,A6,' = ',ES12.5,1x,12x,8x,A)" "SPINUP", SPINUP(i), &
  "cos(spin angle) [9 = undefined]"
end do
end subroutine hepeup_write_verbose

```

17.7.9 Event output in various formats

This routine writes event output according to the LHEF standard. It uses the current contents of the HEPEUP block.

```

<HEP common: public>+≡
  public :: hepeup_write_lhef
  public :: hepeup_write_lha

<HEP common: procedures>+≡
  subroutine hepeup_write_lhef (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(2(1x,I0),4(1x,ES17.10))") &
      NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
    do i = 1, NUP
      write (u, "(6(1x,I0),7(1x,ES17.10))") &
        IDUP(i), ISTUP(i), MOTHUP(:,i), ICOLUP(:,i), &
          PUP(:,i), VTIMUP(i), SPINUP(i)
    end do
  end subroutine hepeup_write_lhef

  subroutine hepeup_write_lha (unit)

```



```

integer, intent(in), optional :: unit
integer :: u, i
integer, dimension(MAXNUP) :: spin_up
spin_up = SPINUP
u = given_output_unit (unit); if (u < 0) return
write (u, "(2(1x,I5),1x,ES17.10,3(1x,ES13.6))") &
    NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
write (u, "(500(1x,I5))") IDUP(:NUP)
write (u, "(500(1x,I5))") MOTHUP(1,:NUP)
write (u, "(500(1x,I5))") MOTHUP(2,:NUP)
write (u, "(500(1x,I5))") ICOLUP(1,:NUP)
write (u, "(500(1x,I5))") ICOLUP(2,:NUP)
write (u, "(500(1x,I5))") ISTUP(:NUP)
write (u, "(500(1x,I5))") spin_up(:NUP)
do i = 1, NUP
    write (u, "(1x,I5,4(1x,ES17.10))") i, PUP([ 4,1,2,3 ], i)
end do

end subroutine hepeup_write_lha

```

This routine writes event output according to the HEPEVT standard. It uses the current contents of the HEPEVT block and some additional parameters according to the standard in WHIZARD 1. For the long ASCII format, the value of the sample function (i.e. the product of squared matrix element, structure functions and phase space factor is printed out). The option of reweighting matrix elements with respect to some reference cross section is not implemented in WHIZARD 2 for this event format, therefore the second entry in the long ASCII format (the function ratio) is always one. The ATHENA format is an implementation of the HEPEVT format that is readable by the ATLAS ATHENA software framework. It is very similar to the WHIZARD 1 HEPEVT format, except that it contains an event counter, a particle counter inside the event, and has the HEPEVT ISTHEP status before the PDG code. The MOKKA format is a special ASCII format that contains the information to be parsed to the MOKKA LC fast simulation software.

```

<HEP common: public>+≡
public :: hepevt_write_hepevt
public :: hepevt_write_ascii
public :: hepevt_write_athena
public :: hepevt_write_mokka

<HEP common: procedures>+≡
subroutine hepevt_write_hepevt (unit)
integer, intent(in), optional :: unit
integer :: u, i
u = given_output_unit (unit); if (u < 0) return
write (u, "(3(1x,I0),(1x,ES17.10))") &
    NHEP, hepevt_n_out, hepevt_n_remnants, hepevt_weight
do i = 1, NHEP
    write (u, "(7(1x,I0))") &
        ISTHEP(i), IDHEP(i), JMOHEP(:,i), JDAHEP(:,i), hepevt_pol(i)
    write (u, "(5(1x,ES17.10))") PHEP(:,i)
    write (u, "(5(1x,ES17.10))") VHEP(:,i), 0.d0
end do

```

```

end subroutine hepevt_write_hepevt

subroutine hepevt_write_ascii (unit, long)
  integer, intent(in), optional :: unit
  logical, intent(in) :: long
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(3(1x,I0),(1x,ES17.10))") &
    NHEP, hepevt_n_out, hepevt_n_remnants, hepevt_weight
  do i = 1, NHEP
    if (ISTHEP(i) /= 1) cycle
    write (u, "(2(1x,I0))") IDHEP(i), hepevt_pol(i)
    write (u, "(5(1x,ES17.10))") PHEP(:,i)
  end do
  if (long) then
    write (u, "(2(1x,ES17.10))") &
      hepevt_function_value, hepevt_function_ratio
  end if
end subroutine hepevt_write_ascii

subroutine hepevt_write_athena (unit, i_evt)
  integer, intent(in), optional :: unit, i_evt
  integer :: u, i, num_event
  num_event = 0
  if (present (i_evt)) num_event = i_evt
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(2(1x,I0))") num_event, NHEP
  do i = 1, NHEP
    write (u, "(7(1x,I0))") &
      i, ISTHEP(i), IDHEP(i), JMOHEP(:,i), JDAHEP(:,i)
    write (u, "(5(1x,ES17.10))") PHEP(:,i)
    write (u, "(5(1x,ES17.10))") VHEP(1:4,i)
  end do
end subroutine hepevt_write_athena

subroutine hepevt_write_mokka (unit)
  integer, intent(in), optional :: unit
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  write (u, "(3(1x,I0),(1x,ES17.10))") &
    NHEP, hepevt_n_out, hepevt_n_remnants, hepevt_weight
  do i = 1, NHEP
    write (u, "(4(1x,I0),4(1x,ES17.10))") &
      ISTHEP(i), IDHEP(i), JDAHEP(1,i), JDAHEP(2,i), &
      PHEP(1:3,i), PHEP(5,i)
  end do
end subroutine hepevt_write_mokka

```

17.7.10 Event input in various formats

This routine writes event output according to the LHEF standard. It uses the current contents of the HEPEUP block.

```

<HEP common: public>+≡
  public :: hepeup_read_lhef
<HEP common: procedures>+≡
  subroutine hepeup_read_lhef (u)
    integer, intent(in) :: u
    integer :: i
    read (u, *) &
      NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
    do i = 1, NUP
      read (u, *) &
        IDUP(i), ISTUP(i), MOTHUP(:,i), ICOLUP(:,i), &
          PUP(:,i), VTIMUP(i), SPINUP(i)
    end do
  end subroutine hepeup_read_lhef

```

17.7.11 Data Transfer: particle sets

The WHIZARD format for handling particle data in events is `particle_set_t`. We have to interface this to the common blocks.

We first create a new particle set that contains only the particles that are supported by the LHEF format. These are: beam, incoming, resonant, outgoing. We drop particles with unknown, virtual or beam-remnant status.

From this set we fill the common block. Event information such as process ID and weight is not transferred here; this has to be done by the caller. The spin information is set only if the particle has a unique mother, and if its polarization is fully defined.

```

<HEP common: public>+≡
  public :: hepeup_from_particle_set
<HEP common: procedures>+≡
  subroutine hepeup_from_particle_set (pset_in, keep_beams, keep_remnants)
    type(particle_set_t), intent(in) :: pset_in
    type(particle_set_t), target :: pset
    logical, intent(in), optional :: keep_beams
    logical, intent(in), optional :: keep_remnants
    integer :: i, n_parents, status, n_tot
    integer, dimension(1) :: i_mother
    logical :: activate_remnants
    activate_remnants = .true.
    if (present(keep_remnants)) activate_remnants = keep_remnants
    call pset_in%apply_keep_beams (pset, keep_beams = keep_beams)
    n_tot = pset%get_n_tot ()
    call hepeup_init (n_tot)
    do i = 1, n_tot
      associate (prt => pset%prt(i))
        status = prt%get_status ()
        if (activate_remnants &
          .and. status == PRT_BEAM_REMNANT &
          .and. prt%get_n_children () == 0) &
          status = PRT_OUTGOING
        call hepeup_set_particle (i, &
          prt%get_pdg (), &

```

```

        status, &
        prt%get_parents (), &
        prt%get_color (), &
        prt%get_momentum (), &
        prt%get_p2 ()
    n_parents = prt%get_n_parents ()
    if (n_parents == 1) then
        i_mother = prt%get_parents ()
        select case (prt%get_polarization_status ())
        case (PRT_GENERIC_POLARIZATION)
            call hepeup_set_particle_spin (i, &
                prt%get_momentum (), &
                prt%get_polarization (), &
                pset%prt(i_mother(1))%get_momentum ())
        end select
    end if
end associate
end do
end subroutine hepeup_from_particle_set

```

Input. The particle set should be allocated properly, but we replace the particle contents.

If there are no beam particles in the event, we try to reconstruct beam particles and beam remnants. We assume for simplicity that the beam particles, if any, are the first two particles. If they are absent, the first two particles should be the incoming partons.

(HEP common: public)+≡

```
public :: hepeup_to_particle_set
```

(HEP common: procedures)+≡

```

subroutine hepeup_to_particle_set &
    (particle_set, recover_beams, model, alt_model)
    type(particle_set_t), intent(inout), target :: particle_set
    logical, intent(in), optional :: recover_beams
    class(model_data_t), intent(in), target :: model, alt_model
    type(particle_t), dimension(:), allocatable :: prt
    integer, dimension(2) :: parent
    integer, dimension(:), allocatable :: child
    integer :: i, j, k, pdg, status
    type(flavor_t) :: flv
    type(color_t) :: col
    integer, dimension(2) :: c
    type(vector4_t) :: p
    real(default) :: p2
    logical :: reconstruct
    integer :: off
    if (present (recover_beams)) then
        reconstruct = recover_beams .and. .not. all (ISTUP(1:2) == PRT_BEAM)
    else
        reconstruct = .false.
    end if
    if (reconstruct) then
        off = 4
    else

```

```

        off = 0
    end if
    allocate (prt (NUP + off), child (NUP + off))
    do i = 1, NUP
        k = i + off
        call hepeup_get_particle (i, pdg, status, col = c, p = p, m2 = p2)
        call flv%init (pdg, model, alt_model)
        call prt(k)%set_flavor (flv)
        call prt(k)%reset_status (status)
        call col%init (c)
        call prt(k)%set_color (col)
        call prt(k)%set_momentum (p, p2)
        where (MOTHUP(:,i) /= 0)
            parent = MOTHUP(:,i) + off
        elsewhere
            parent = 0
        end where
        call prt(k)%set_parents (parent)
        child = [(j, j = 1 + off, NUP + off)]
        where (MOTHUP(1,:NUP) /= i .and. MOTHUP(2,:NUP) /= i) child = 0
        call prt(k)%set_children (child)
    end do
    if (reconstruct) then
        do k = 1, 2
            call prt(k)%reset_status (PRT_BEAM)
            call prt(k)%set_children ([k+2,k+4])
        end do
        do k = 3, 4
            call prt(k)%reset_status (PRT_BEAM_REMNANT)
            call prt(k)%set_parents ([k-2])
        end do
        do k = 5, 6
            call prt(k)%set_parents ([k-4])
        end do
    end if
    call particle_set%replace (prt)
end subroutine hepeup_to_particle_set

```

The HEPEVT common block is quite similar, but does contain less information, e.g. no color flows (it was LEP time). The spin information is set only if the particle has a unique mother, and if its polarization is fully defined.

```

<HEP common: public>+≡
    public :: hepevt_from_particle_set

<HEP common: procedures>+≡
    subroutine hepevt_from_particle_set &
        (particle_set, keep_beams, keep_remnants)
        type(particle_set_t), intent(in) :: particle_set
        type(particle_set_t), target :: pset_hepevt
        logical, intent(in), optional :: keep_beams
        logical, intent(in), optional :: keep_remnants
        integer :: i, status, n_tot
        logical :: activate_remnants
        activate_remnants = .true.
    end subroutine

```

```

if (present (keep_remnants)) activate_remnants = keep_remnants
call particle_set%to_hepevt_form (pset_hepevt, keep_beams)
n_tot = pset_hepevt%get_n_tot ()
call hepevt_init (n_tot, pset_hepevt%get_n_out ())
do i = 1, n_tot
  associate (prt => pset_hepevt%prt(i))
    status = prt%get_status ()
    if (activate_remnants &
      .and. status == PRT_BEAM_REMNANT &
      .and. prt%get_n_children () == 0) &
      status = PRT_OUTGOING
    call hepevt_set_particle (i, &
      prt%get_pdg (), status, &
      prt%get_parents (), &
      prt%get_children (), &
      prt%get_momentum (), &
      prt%get_p2 (), &
      prt%get_helicity (), &
      prt%get_vertex ())
  end associate
end do
call pset_hepevt%final ()
end subroutine hepevt_from_particle_set

```

17.8 HepMC events

This section provides the interface to the HepMC C++ library for handling Monte-Carlo events.

Each C++ class of HepMC that we use is mirrored by a Fortran type, which contains as its only component the C pointer to the C++ object.

Each C++ method of HepMC that we use has a C wrapper function. This function takes a pointer to the host object as its first argument. Further arguments are either C pointers, or in the case of simple types (integer, real), interoperable C/Fortran objects.

The C wrapper functions have explicit interfaces in the Fortran module. They are called by Fortran wrapper procedures. These are treated as methods of the corresponding Fortran type.

(hepmc_interface.f90)≡
⟨File header⟩

```

module hepmc_interface

  use, intrinsic :: iso_c_binding !NODEP!

  ⟨Use kinds⟩
  ⟨Use strings⟩
  use io_units
  use constants
  use lorentz
  use unit_tests
  use model_data

```

```

    use flavors
    use colors
    use helicities
    use quantum_numbers
    use polarizations

    <Standard module head>

    <HepMC interface: public>

    <HepMC interface: types>

    <HepMC interface: interfaces>

contains

    <HepMC interface: procedures>

    <HepMC interface: tests>

end module hepmc_interface

```

17.8.1 Interface check

This function can be called in order to verify that we are using the actual HepMC library, and not the dummy version.

```

<HepMC interface: interfaces>≡
    interface
        logical(c_bool) function hepmc_available () bind(C)
        import
        end function hepmc_available
    end interface

<HepMC interface: public>≡
    public :: hepmc_is_available

<HepMC interface: procedures>≡
    function hepmc_is_available () result (flag)
        logical :: flag
        flag = hepmc_available ()
    end function hepmc_is_available

```

17.8.2 FourVector

The C version of four-vectors is often transferred by value, and the associated procedures are all inlined. The wrapper needs to transfer by reference, so we create FourVector objects on the heap which have to be deleted explicitly. The input is a `vector4_t` or `vector3_t` object from the `lorentz` module.

```

<HepMC interface: public>+≡
    public :: hepmc_four_vector_t

```

```

<HepMC interface: types>≡
  type :: hepmc_four_vector_t
  private
  type(c_ptr) :: obj
  end type hepmc_four_vector_t

```

In the C constructor, the zero-component (fourth argument) is optional; if missing, it is set to zero. The Fortran version has initializer form and takes either a three-vector or a four-vector. A further version extracts the four-vector from a HepMC particle object.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_four_vector_xyz (x, y, z) bind(C)
    import
      real(c_double), value :: x, y, z
    end function new_four_vector_xyz
  end interface
  interface
    type(c_ptr) function new_four_vector_xyzt (x, y, z, t) bind(C)
    import
      real(c_double), value :: x, y, z, t
    end function new_four_vector_xyzt
  end interface

<HepMC interface: public>+≡
  public :: hepmc_four_vector_init

<HepMC interface: interfaces>+≡
  interface hepmc_four_vector_init
    module procedure hepmc_four_vector_init_v4
    module procedure hepmc_four_vector_init_v3
    module procedure hepmc_four_vector_init_hepmc_ptr
  end interface

<HepMC interface: procedures>+≡
  subroutine hepmc_four_vector_init_v4 (pp, p)
    type(hepmc_four_vector_t), intent(out) :: pp
    type(vector4_t), intent(in) :: p
    real(default), dimension(0:3) :: pa
    pa = vector4_get_components (p)
    pp%obj = new_four_vector_xyzt &
      (real (pa(1), c_double), &
       real (pa(2), c_double), &
       real (pa(3), c_double), &
       real (pa(0), c_double))
  end subroutine hepmc_four_vector_init_v4

  subroutine hepmc_four_vector_init_v3 (pp, p)
    type(hepmc_four_vector_t), intent(out) :: pp
    type(vector3_t), intent(in) :: p
    real(default), dimension(3) :: pa
    pa = vector3_get_components (p)
    pp%obj = new_four_vector_xyz &
      (real (pa(1), c_double), &
       real (pa(2), c_double), &

```



```

        real (pa(3), c_double))
end subroutine hepmc_four_vector_init_v3

subroutine hepmc_four_vector_init_hepmc_prt (pp, prt)
    type(hepmc_four_vector_t), intent(out) :: pp
    type(hepmc_particle_t), intent(in) :: prt
    pp%obj = gen_particle_momentum (prt%obj)
end subroutine hepmc_four_vector_init_hepmc_prt

```

Here, the destructor is explicitly needed.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine four_vector_delete (p_obj) bind(C)
            import
            type(c_ptr), value :: p_obj
        end subroutine four_vector_delete
    end interface

<HepMC interface: public>+≡
    public :: hepmc_four_vector_final

<HepMC interface: procedures>+≡
    subroutine hepmc_four_vector_final (p)
        type(hepmc_four_vector_t), intent(inout) :: p
        call four_vector_delete (p%obj)
    end subroutine hepmc_four_vector_final

```

Convert to a Lorentz vector.

```

<HepMC interface: interfaces>+≡
    interface
        function four_vector_px (p_obj) result (px) bind(C)
            import
            real(c_double) :: px
            type(c_ptr), value :: p_obj
        end function four_vector_px
    end interface

    interface
        function four_vector_py (p_obj) result (py) bind(C)
            import
            real(c_double) :: py
            type(c_ptr), value :: p_obj
        end function four_vector_py
    end interface

    interface
        function four_vector_pz (p_obj) result (pz) bind(C)
            import
            real(c_double) :: pz
            type(c_ptr), value :: p_obj
        end function four_vector_pz
    end interface

    interface
        function four_vector_e (p_obj) result (e) bind(C)
            import
            real(c_double) :: e

```

```

        type(c_ptr), value :: p_obj
    end function four_vector_e
end interface
<HepMC interface: public>+≡
    public :: hepmc_four_vector_to_vector4
<HepMC interface: procedures>+≡
    subroutine hepmc_four_vector_to_vector4 (pp, p)
        type(hepmc_four_vector_t), intent(in) :: pp
        type(vector4_t), intent(out) :: p
        real(default) :: E
        real(default), dimension(3) :: p3
        E = four_vector_e (pp%obj)
        p3(1) = four_vector_px (pp%obj)
        p3(2) = four_vector_py (pp%obj)
        p3(3) = four_vector_pz (pp%obj)
        p = vector4_moving (E, vector3_moving (p3))
    end subroutine hepmc_four_vector_to_vector4

```

17.8.3 Polarization

Polarization objects are temporarily used for assigning particle polarization. We add a flag `polarized`. If this is false, the polarization is not set and should not be transferred to `hepmc_particle` objects.

```

<HepMC interface: public>+≡
    public :: hepmc_polarization_t
<HepMC interface: types>+≡
    type :: hepmc_polarization_t
    private
    logical :: polarized = .false.
    type(c_ptr) :: obj
end type hepmc_polarization_t

```

Constructor. The C wrapper takes polar and azimuthal angle as arguments. The Fortran version allows for either a complete polarization density matrix, or for a definite (diagonal) helicity.

HepMC does not allow to specify the degree of polarization, therefore we have to map it to either 0 or 1. We choose 0 for polarization less than 0.5 and 1 for polarization greater than 0.5. Even this simplification works only for spin-1/2 and for massless particles; massive vector bosons cannot be treated this way. In particular, zero helicity is always translated as unpolarized.

For massive vector bosons, we arbitrarily choose the convention that the longitudinal (zero) helicity state is mapped to the theta angle $\pi/2$. This works under the condition that helicity is projected onto one of the basis states.

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function new_polarization (theta, phi) bind(C)
            import
            real(c_double), value :: theta, phi
        end function new_polarization
    end interface

```

```

<HepMC interface: public>+≡
    public :: hepmc_polarization_init

<HepMC interface: interfaces>+≡
    interface hepmc_polarization_init
        module procedure hepmc_polarization_init_pol
        module procedure hepmc_polarization_init_hel
        module procedure hepmc_polarization_init_int
    end interface

<HepMC interface: procedures>+≡
    subroutine hepmc_polarization_init_pol (hpol, pol)
        type(hepmc_polarization_t), intent(out) :: hpol
        type(polarization_t), intent(in) :: pol
        real(default) :: r, theta, phi
        if (polarization_is_polarized (pol)) then
            call polarization_to_angles (pol, r, theta, phi)
            if (r >= 0.5) then
                hpol%polarized = .true.
                hpol%obj = new_polarization &
                    (real (theta, c_double), real (phi, c_double))
            end if
        end if
    end subroutine hepmc_polarization_init_pol

    subroutine hepmc_polarization_init_hel (hpol, hel)
        type(hepmc_polarization_t), intent(out) :: hpol
        type(helicity_t), intent(in) :: hel
        integer, dimension(2) :: h
        if (hel%is_defined ()) then
            h = hel%to_pair ()
            select case (h(1))
            case (1:)
                hpol%polarized = .true.
                hpol%obj = new_polarization (0._c_double, 0._c_double)
            case (-1)
                hpol%polarized = .true.
                hpol%obj = new_polarization (real (pi, c_double), 0._c_double)
            case (0)
                hpol%polarized = .true.
                hpol%obj = new_polarization (real (pi/2, c_double), 0._c_double)
            end select
        end if
    end subroutine hepmc_polarization_init_hel

    subroutine hepmc_polarization_init_int (hpol, hel)
        type(hepmc_polarization_t), intent(out) :: hpol
        integer, intent(in) :: hel
        select case (hel)
        case (1:)
            hpol%polarized = .true.
            hpol%obj = new_polarization (0._c_double, 0._c_double)
        case (-1)
            hpol%polarized = .true.
            hpol%obj = new_polarization (real (pi, c_double), 0._c_double)
        end select
    end subroutine hepmc_polarization_init_int

```

```

    case (0)
        hpol%polarized = .true.
        hpol%obj = new_polarization (real (pi/2, c_double), 0._c_double)
    end select
end subroutine hepmc_polarization_init_int

```

Destructor. The C object is deallocated only if the polarized flag is set.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine polarization_delete (pol_obj) bind(C)
            import
            type(c_ptr), value :: pol_obj
        end subroutine polarization_delete
    end interface
<HepMC interface: public>+≡
    public :: hepmc_polarization_final
<HepMC interface: procedures>+≡
    subroutine hepmc_polarization_final (hpol)
        type(hepmc_polarization_t), intent(inout) :: hpol
        if (hpol%polarized) call polarization_delete (hpol%obj)
    end subroutine hepmc_polarization_final

```

Recover polarization from HepMC polarization object (with the abovementioned deficiencies).

```

<HepMC interface: interfaces>+≡
    interface
        function polarization_theta (pol_obj) result (theta) bind(C)
            import
            real(c_double) :: theta
            type(c_ptr), value :: pol_obj
        end function polarization_theta
    end interface
    interface
        function polarization_phi (pol_obj) result (phi) bind(C)
            import
            real(c_double) :: phi
            type(c_ptr), value :: pol_obj
        end function polarization_phi
    end interface
<HepMC interface: public>+≡
    public :: hepmc_polarization_to_pol
<HepMC interface: procedures>+≡
    subroutine hepmc_polarization_to_pol (hpol, flv, pol)
        type(hepmc_polarization_t), intent(in) :: hpol
        type(flavor_t), intent(in) :: flv
        type(polarization_t), intent(out) :: pol
        real(default) :: theta, phi
        theta = polarization_theta (hpol%obj)
        phi = polarization_phi (hpol%obj)
        call polarization_init_angles (pol, flv, 1._default, theta, phi)
    end subroutine hepmc_polarization_to_pol

```

Recover helicity. Here, ϕ is ignored and only the sign of $\cos \theta$ is relevant, mapped to positive/negative helicity.

```

<HepMC interface: public>+≡
    public :: hepmc_polarization_to_hel

<HepMC interface: procedures>+≡
    subroutine hepmc_polarization_to_hel (hpol, flv, hel)
        type(hepmc_polarization_t), intent(in) :: hpol
        type(flavor_t), intent(in) :: flv
        type(helicity_t), intent(out) :: hel
        real(default) :: theta
        integer :: hmax
        theta = polarization_theta (hpol%obj)
        hmax = flv%get_spin_type () / 2
        call hel%init (sign (hmax, nint (cos (theta))))
    end subroutine hepmc_polarization_to_hel

```

17.8.4 GenParticle

Particle objects have the obvious meaning.

```

<HepMC interface: public>+≡
    public :: hepmc_particle_t

<HepMC interface: types>+≡
    type :: hepmc_particle_t
    private
    type(c_ptr) :: obj
    end type hepmc_particle_t

```

Constructor. The C version takes a FourVector object, which in the Fortran wrapper is created on the fly from a `vector4` Lorentz vector.

No destructor is needed as long as all particles are entered into vertex containers.

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function new_gen_particle (prt_obj, pdg_id, status) bind(C)
            import
            type(c_ptr), value :: prt_obj
            integer(c_int), value :: pdg_id, status
        end function new_gen_particle
    end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_init

<HepMC interface: procedures>+≡
    subroutine hepmc_particle_init (prt, p, pdg, status)
        type(hepmc_particle_t), intent(out) :: prt
        type(vector4_t), intent(in) :: p
        integer, intent(in) :: pdg, status
        type(hepmc_four_vector_t) :: pp
        call hepmc_four_vector_init (pp, p)
        prt%obj = new_gen_particle (pp%obj, int (pdg, c_int), int (status, c_int))
    end subroutine hepmc_particle_init

```

```

    call hepmc_four_vector_final (pp)
end subroutine hepmc_particle_init

```

Set the particle color flow.

(HepMC interface: interfaces)+≡

```

interface
  subroutine gen_particle_set_flow (prt_obj, code_index, code) bind(C)
  import
    type(c_ptr), value :: prt_obj
    integer(c_int), value :: code_index, code
  end subroutine gen_particle_set_flow
end interface

```

Set the particle color. Either from a color_t object or directly from a pair of integers.

(HepMC interface: interfaces)+≡

```

interface hepmc_particle_set_color
  module procedure hepmc_particle_set_color_col
  module procedure hepmc_particle_set_color_int
end interface hepmc_particle_set_color

```

(HepMC interface: public)+≡

```

public :: hepmc_particle_set_color

```

(HepMC interface: procedures)+≡

```

subroutine hepmc_particle_set_color_col (prt, col)
  type(hepmc_particle_t), intent(inout) :: prt
  type(color_t), intent(in) :: col
  integer(c_int) :: c
  c = col%get_col ()
  if (c /= 0) call gen_particle_set_flow (prt%obj, 1_c_int, c)
  c = col%get_acl ()
  if (c /= 0) call gen_particle_set_flow (prt%obj, 2_c_int, c)
end subroutine hepmc_particle_set_color_col

subroutine hepmc_particle_set_color_int (prt, col)
  type(hepmc_particle_t), intent(inout) :: prt
  integer, dimension(2), intent(in) :: col
  integer(c_int) :: c
  c = col(1)
  if (c /= 0) call gen_particle_set_flow (prt%obj, 1_c_int, c)
  c = col(2)
  if (c /= 0) call gen_particle_set_flow (prt%obj, 2_c_int, c)
end subroutine hepmc_particle_set_color_int

```

Set the particle polarization. For the restrictions on particle polarization in HepMC, see above hepmc_polarization_init.

(HepMC interface: interfaces)+≡

```

interface
  subroutine gen_particle_set_polarization (prt_obj, pol_obj) bind(C)
  import
    type(c_ptr), value :: prt_obj, pol_obj
  end subroutine gen_particle_set_polarization
end interface

```

```

<HepMC interface: public>+≡
    public :: hepmc_particle_set_polarization

<HepMC interface: interfaces>+≡
    interface hepmc_particle_set_polarization
        module procedure hepmc_particle_set_polarization_pol
        module procedure hepmc_particle_set_polarization_hel
        module procedure hepmc_particle_set_polarization_int
    end interface

<HepMC interface: procedures>+≡
    subroutine hepmc_particle_set_polarization_pol (prt, pol)
        type(hepmc_particle_t), intent(inout) :: prt
        type(polarization_t), intent(in) :: pol
        type(hepmc_polarization_t) :: hpol
        call hepmc_polarization_init (hpol, pol)
        if (hpol%polarized) call gen_particle_set_polarization (prt%obj, hpol%obj)
        call hepmc_polarization_final (hpol)
    end subroutine hepmc_particle_set_polarization_pol

    subroutine hepmc_particle_set_polarization_hel (prt, hel)
        type(hepmc_particle_t), intent(inout) :: prt
        type(helicity_t), intent(in) :: hel
        type(hepmc_polarization_t) :: hpol
        call hepmc_polarization_init (hpol, hel)
        if (hpol%polarized) call gen_particle_set_polarization (prt%obj, hpol%obj)
        call hepmc_polarization_final (hpol)
    end subroutine hepmc_particle_set_polarization_hel

    subroutine hepmc_particle_set_polarization_int (prt, hel)
        type(hepmc_particle_t), intent(inout) :: prt
        integer, intent(in) :: hel
        type(hepmc_polarization_t) :: hpol
        call hepmc_polarization_init (hpol, hel)
        if (hpol%polarized) call gen_particle_set_polarization (prt%obj, hpol%obj)
        call hepmc_polarization_final (hpol)
    end subroutine hepmc_particle_set_polarization_int

```

Return the HepMC barcode (unique integer ID) of the particle.

```

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_barcode (prt_obj) result (barcode) bind(C)
            import
            integer(c_int) :: barcode
            type(c_ptr), value :: prt_obj
        end function gen_particle_barcode
    end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_barcode

<HepMC interface: procedures>+≡
    function hepmc_particle_get_barcode (prt) result (barcode)
        integer :: barcode
        type(hepmc_particle_t), intent(in) :: prt
        barcode = gen_particle_barcode (prt%obj)
    end function

```

```
end function hepmc_particle_get_barcode
```

Return the four-vector component of the particle object as a `vector4_t` Lorentz vector.

```
<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function gen_particle_momentum (prt_obj) bind(C)
    import
    type(c_ptr), value :: prt_obj
    end function gen_particle_momentum
  end interface

<HepMC interface: public>+≡
  public :: hepmc_particle_get_momentum

<HepMC interface: procedures>+≡
  function hepmc_particle_get_momentum (prt) result (p)
    type(vector4_t) :: p
    type(hepmc_particle_t), intent(in) :: prt
    type(hepmc_four_vector_t) :: pp
    call hepmc_four_vector_init (pp, prt)
    call hepmc_four_vector_to_vector4 (pp, p)
    call hepmc_four_vector_final (pp)
  end function hepmc_particle_get_momentum
```

Return the invariant mass squared of the particle object. HepMC stores the signed invariant mass (no squaring).

```
<HepMC interface: interfaces>+≡
  interface
    function gen_particle_generated_mass (prt_obj) result (mass) bind(C)
    import
    real(c_double) :: mass
    type(c_ptr), value :: prt_obj
    end function gen_particle_generated_mass
  end interface

<HepMC interface: public>+≡
  public :: hepmc_particle_get_mass_squared

<HepMC interface: procedures>+≡
  function hepmc_particle_get_mass_squared (prt) result (m2)
    real(default) :: m2
    type(hepmc_particle_t), intent(in) :: prt
    real(default) :: m
    m = gen_particle_generated_mass (prt%obj)
    m2 = sign (m**2, m)
  end function hepmc_particle_get_mass_squared
```

Return the PDG ID:

```
<HepMC interface: interfaces>+≡
  interface
    function gen_particle_pdg_id (prt_obj) result (pdg_id) bind(C)
    import
    integer(c_int) :: pdg_id
```



```

        type(c_ptr), value :: prt_obj
    end function gen_particle_pdg_id
end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_pdg

<HepMC interface: procedures>+≡
    function hepmc_particle_get_pdg (prt) result (pdg)
        integer :: pdg
        type(hepmc_particle_t), intent(in) :: prt
        pdg = gen_particle_pdg_id (prt%obj)
    end function hepmc_particle_get_pdg

Return the status code:

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_status (prt_obj) result (status) bind(C)
            import
            integer(c_int) :: status
            type(c_ptr), value :: prt_obj
        end function gen_particle_status
    end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_status

<HepMC interface: procedures>+≡
    function hepmc_particle_get_status (prt) result (status)
        integer :: status
        type(hepmc_particle_t), intent(in) :: prt
        status = gen_particle_status (prt%obj)
    end function hepmc_particle_get_status

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_is_beam (prt_obj) result (is_beam) bind(C)
            import
            logical(c_bool) :: is_beam
            type(c_ptr), value :: prt_obj
        end function gen_particle_is_beam
    end interface

Determine whether a particle is a beam particle.

<HepMC interface: public>+≡
    public :: hepmc_particle_is_beam

<HepMC interface: procedures>+≡
    function hepmc_particle_is_beam (prt) result (is_beam)
        logical :: is_beam
        type(hepmc_particle_t), intent(in) :: prt
        is_beam = gen_particle_is_beam (prt%obj)
    end function hepmc_particle_is_beam

```

Return the production/decay vertex (as a pointer, no finalization necessary).

(HepMC interface: interfaces)+≡

```
interface
  type(c_ptr) function gen_particle_production_vertex (prt_obj) bind(C)
  import
  type(c_ptr), value :: prt_obj
  end function gen_particle_production_vertex
end interface
interface
  type(c_ptr) function gen_particle_end_vertex (prt_obj) bind(C)
  import
  type(c_ptr), value :: prt_obj
  end function gen_particle_end_vertex
end interface
```

(HepMC interface: public)+≡

```
public :: hepmc_particle_get_production_vertex
public :: hepmc_particle_get_decay_vertex
```

(HepMC interface: procedures)+≡

```
function hepmc_particle_get_production_vertex (prt) result (v)
  type(hepmc_vertex_t) :: v
  type(hepmc_particle_t), intent(in) :: prt
  v%obj = gen_particle_production_vertex (prt%obj)
end function hepmc_particle_get_production_vertex

function hepmc_particle_get_decay_vertex (prt) result (v)
  type(hepmc_vertex_t) :: v
  type(hepmc_particle_t), intent(in) :: prt
  v%obj = gen_particle_end_vertex (prt%obj)
end function hepmc_particle_get_decay_vertex
```

Return the number of parents/children.

(HepMC interface: public)+≡

```
public :: hepmc_particle_get_n_parents
public :: hepmc_particle_get_n_children
```

(HepMC interface: procedures)+≡

```
function hepmc_particle_get_n_parents (prt) result (n_parents)
  integer :: n_parents
  type(hepmc_particle_t), intent(in) :: prt
  type(hepmc_vertex_t) :: v
  v = hepmc_particle_get_production_vertex (prt)
  if (hepmc_vertex_is_valid (v)) then
    n_parents = hepmc_vertex_get_n_in (v)
  else
    n_parents = 0
  end if
end function hepmc_particle_get_n_parents

function hepmc_particle_get_n_children (prt) result (n_children)
  integer :: n_children
  type(hepmc_particle_t), intent(in) :: prt
  type(hepmc_vertex_t) :: v
  v = hepmc_particle_get_decay_vertex (prt)
```

```

    if (hepmc_vertex_is_valid (v)) then
        n_children = hepmc_vertex_get_n_out (v)
    else
        n_children = 0
    end if
end function hepmc_particle_get_n_children

```

Convenience function: Return the array of parent particles for a given HepMC particle. The contents are HepMC barcodes that still have to be mapped to the particle indices.

```

<HepMC interface: public>+≡
    public :: hepmc_particle_get_parent_barcodes
    public :: hepmc_particle_get_child_barcodes

<HepMC interface: procedures>+≡
    function hepmc_particle_get_parent_barcodes (prt) result (parent_barcode)
        type(hepmc_particle_t), intent(in) :: prt
        integer, dimension(:), allocatable :: parent_barcode
        type(hepmc_vertex_t) :: v
        type(hepmc_vertex_particle_in_iterator_t) :: it
        integer :: i
        v = hepmc_particle_get_production_vertex (prt)
        if (hepmc_vertex_is_valid (v)) then
            allocate (parent_barcode (hepmc_vertex_get_n_in (v)))
            if (size (parent_barcode) /= 0) then
                call hepmc_vertex_particle_in_iterator_init (it, v)
                do i = 1, size (parent_barcode)
                    parent_barcode(i) = hepmc_particle_get_barcode &
                        (hepmc_vertex_particle_in_iterator_get (it))
                    call hepmc_vertex_particle_in_iterator_advance (it)
                end do
                call hepmc_vertex_particle_in_iterator_final (it)
            end if
        else
            allocate (parent_barcode (0))
        end if
    end function hepmc_particle_get_parent_barcodes

    function hepmc_particle_get_child_barcodes (prt) result (child_barcode)
        type(hepmc_particle_t), intent(in) :: prt
        integer, dimension(:), allocatable :: child_barcode
        type(hepmc_vertex_t) :: v
        type(hepmc_vertex_particle_out_iterator_t) :: it
        integer :: i
        v = hepmc_particle_get_decay_vertex (prt)
        if (hepmc_vertex_is_valid (v)) then
            allocate (child_barcode (hepmc_vertex_get_n_out (v)))
            call hepmc_vertex_particle_out_iterator_init (it, v)
            if (size (child_barcode) /= 0) then
                do i = 1, size (child_barcode)
                    child_barcode(i) = hepmc_particle_get_barcode &
                        (hepmc_vertex_particle_out_iterator_get (it))
                    call hepmc_vertex_particle_out_iterator_advance (it)
                end do
            end if
        end if
    end function hepmc_particle_get_child_barcodes

```

```

        call hepmc_vertex_particle_out_iterator_final (it)
    end if
else
    allocate (child_barcode (0))
end if
end function hepmc_particle_get_child_barcodes

```

Return the polarization (assuming that the particle is completely polarized).
 Note that the generated polarization object needs finalization.

```

<HepMC interface: interfaces>+≡
interface
    type(c_ptr) function gen_particle_polarization (prt_obj) bind(C)
    import
        type(c_ptr), value :: prt_obj
    end function gen_particle_polarization
end interface

<HepMC interface: public>+≡
public :: hepmc_particle_get_polarization

<HepMC interface: procedures>+≡
function hepmc_particle_get_polarization (prt) result (pol)
    type(hepmc_polarization_t) :: pol
    type(hepmc_particle_t), intent(in) :: prt
    pol%obj = gen_particle_polarization (prt%obj)
end function hepmc_particle_get_polarization

```

Return the particle color as a two-dimensional array (color, anticolor).

```

<HepMC interface: interfaces>+≡
interface
    function gen_particle_flow (prt_obj, code_index) result (code) bind(C)
    import
        integer(c_int) :: code
    type(c_ptr), value :: prt_obj
        integer(c_int), value :: code_index
    end function gen_particle_flow
end interface

<HepMC interface: public>+≡
public :: hepmc_particle_get_color

<HepMC interface: procedures>+≡
function hepmc_particle_get_color (prt) result (col)
    integer, dimension(2) :: col
    type(hepmc_particle_t), intent(in) :: prt
    col(1) = gen_particle_flow (prt%obj, 1)
    col(2) = - gen_particle_flow (prt%obj, 2)
end function hepmc_particle_get_color

<HepMC interface: interfaces>+≡
interface
    function gen_vertex_pos_x (v_obj) result (x) bind(C)
    import
        type(c_ptr), value :: v_obj

```

```

        real(c_double) :: x
    end function gen_vertex_pos_x
end interface
interface
    function gen_vertex_pos_y (v_obj) result (y) bind(C)
        import
        type(c_ptr), value :: v_obj
        real(c_double) :: y
    end function gen_vertex_pos_y
end interface
interface
    function gen_vertex_pos_z (v_obj) result (z) bind(C)
        import
        type(c_ptr), value :: v_obj
        real(c_double) :: z
    end function gen_vertex_pos_z
end interface
interface
    function gen_vertex_time (v_obj) result (t) bind(C)
        import
        type(c_ptr), value :: v_obj
        real(c_double) :: t
    end function gen_vertex_time
end interface
<HepMC interface: public>+≡
    public :: hepmc_vertex_to_vertex
<HepMC interface: procedures>+≡
    function hepmc_vertex_to_vertex (vtx) result (v)
        type(hepmc_vertex_t), intent(in) :: vtx
        type(vector4_t) :: v
        real(default) :: t, vx, vy, vz
        if (hepmc_vertex_is_valid (vtx)) then
            t = gen_vertex_time (vtx%obj)
            vx = gen_vertex_pos_x (vtx%obj)
            vy = gen_vertex_pos_y (vtx%obj)
            vz = gen_vertex_pos_z (vtx%obj)
            v = vector4_moving (t, &
                vector3_moving ([vx, vy, vz]))
        end if
    end function hepmc_vertex_to_vertex

```

17.8.5 GenVertex

Vertices are made of particles (incoming and outgoing).

```

<HepMC interface: public>+≡
    public :: hepmc_vertex_t
<HepMC interface: types>+≡
    type :: hepmc_vertex_t
    private
        type(c_ptr) :: obj
    end type hepmc_vertex_t

```

Constructor. Two versions, one plain, one with the position in space and time (measured in mm) as argument. The Fortran version has initializer form, and the vertex position is an optional argument.

A destructor is unnecessary as long as all vertices are entered into an event container.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_gen_vertex () bind(C)
    import
    end function new_gen_vertex
  end interface
  interface
    type(c_ptr) function new_gen_vertex_pos (prt_obj) bind(C)
    import
    type(c_ptr), value :: prt_obj
    end function new_gen_vertex_pos
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_init
<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_init (v, x)
    type(hepmc_vertex_t), intent(out) :: v
    type(vector4_t), intent(in), optional :: x
    type(hepmc_four_vector_t) :: pos
    if (present (x)) then
      call hepmc_four_vector_init (pos, x)
      v%obj = new_gen_vertex_pos (pos%obj)
      call hepmc_four_vector_final (pos)
    else
      v%obj = new_gen_vertex ()
    end if
  end subroutine hepmc_vertex_init

```

Return true if the vertex pointer is non-null:

```

<HepMC interface: interfaces>+≡
  interface
    function gen_vertex_is_valid (v_obj) result (flag) bind(C)
    import
    logical(c_bool) :: flag
    type(c_ptr), value :: v_obj
    end function gen_vertex_is_valid
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_is_valid
<HepMC interface: procedures>+≡
  function hepmc_vertex_is_valid (v) result (flag)
    logical :: flag
    type(hepmc_vertex_t), intent(in) :: v
    flag = gen_vertex_is_valid (v%obj)
  end function hepmc_vertex_is_valid

```

Add a particle to a vertex, incoming or outgoing.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_vertex_add_particle_in (v_obj, prt_obj) bind(C)
      import
      type(c_ptr), value :: v_obj, prt_obj
    end subroutine gen_vertex_add_particle_in
  end interface
  interface
    subroutine gen_vertex_add_particle_out (v_obj, prt_obj) bind(C)
      import
      type(c_ptr), value :: v_obj, prt_obj
    end subroutine gen_vertex_add_particle_out
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_add_particle_in
  public :: hepmc_vertex_add_particle_out

<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_add_particle_in (v, prt)
    type(hepmc_vertex_t), intent(inout) :: v
    type(hepmc_particle_t), intent(in) :: prt
    call gen_vertex_add_particle_in (v%obj, prt%obj)
  end subroutine hepmc_vertex_add_particle_in

  subroutine hepmc_vertex_add_particle_out (v, prt)
    type(hepmc_vertex_t), intent(inout) :: v
    type(hepmc_particle_t), intent(in) :: prt
    call gen_vertex_add_particle_out (v%obj, prt%obj)
  end subroutine hepmc_vertex_add_particle_out

```

Return the number of incoming/outgoing particles.

```

<HepMC interface: interfaces>+≡
  interface
    function gen_vertex_particles_in_size (v_obj) result (size) bind(C)
      import
      integer(c_int) :: size
      type(c_ptr), value :: v_obj
    end function gen_vertex_particles_in_size
  end interface
  interface
    function gen_vertex_particles_out_size (v_obj) result (size) bind(C)
      import
      integer(c_int) :: size
      type(c_ptr), value :: v_obj
    end function gen_vertex_particles_out_size
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_get_n_in
  public :: hepmc_vertex_get_n_out

```

```

<HepMC interface: procedures>+≡
  function hepmc_vertex_get_n_in (v) result (n_in)
    integer :: n_in
    type(hepmc_vertex_t), intent(in) :: v
    n_in = gen_vertex_particles_in_size (v%obj)
  end function hepmc_vertex_get_n_in

  function hepmc_vertex_get_n_out (v) result (n_out)
    integer :: n_out
    type(hepmc_vertex_t), intent(in) :: v
    n_out = gen_vertex_particles_out_size (v%obj)
  end function hepmc_vertex_get_n_out

```

17.8.6 Vertex-particle-in iterator

This iterator iterates over all incoming particles in an vertex. We store a pointer to the vertex in addition to the iterator. This allows for simple end checking.

The iterator is actually a constant iterator; it can only read.

```

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_in_iterator_t

<HepMC interface: types>+≡
  type :: hepmc_vertex_particle_in_iterator_t
  private
  type(c_ptr) :: obj
  type(c_ptr) :: v_obj
  end type hepmc_vertex_particle_in_iterator_t

```

Constructor. The iterator is initialized at the first particle in the vertex.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function &
      new_vertex_particles_in_const_iterator (v_obj) bind(C)
    import
    type(c_ptr), value :: v_obj
  end function new_vertex_particles_in_const_iterator
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_in_iterator_init

<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_in_iterator_init (it, v)
    type(hepmc_vertex_particle_in_iterator_t), intent(out) :: it
    type(hepmc_vertex_t), intent(in) :: v
    it%obj = new_vertex_particles_in_const_iterator (v%obj)
    it%v_obj = v%obj
  end subroutine hepmc_vertex_particle_in_iterator_init

```

Destructor. Necessary because the iterator is allocated on the heap.

```

<HepMC interface: interfaces>+≡
  interface

```



```

        subroutine vertex_particles_in_const_iterator_delete (it_obj) bind(C)
            import
            type(c_ptr), value :: it_obj
            end subroutine vertex_particles_in_const_iterator_delete
        end interface
    <HepMC interface: public>+≡
        public :: hepmc_vertex_particle_in_iterator_final
    <HepMC interface: procedures>+≡
        subroutine hepmc_vertex_particle_in_iterator_final (it)
            type(hepmc_vertex_particle_in_iterator_t), intent(inout) :: it
            call vertex_particles_in_const_iterator_delete (it%obj)
        end subroutine hepmc_vertex_particle_in_iterator_final

```

Increment

```

    <HepMC interface: interfaces>+≡
        interface
            subroutine vertex_particles_in_const_iterator_advance (it_obj) bind(C)
                import
                type(c_ptr), value :: it_obj
            end subroutine vertex_particles_in_const_iterator_advance
        end interface
    <HepMC interface: public>+≡
        public :: hepmc_vertex_particle_in_iterator_advance
    <HepMC interface: procedures>+≡
        subroutine hepmc_vertex_particle_in_iterator_advance (it)
            type(hepmc_vertex_particle_in_iterator_t), intent(inout) :: it
            call vertex_particles_in_const_iterator_advance (it%obj)
        end subroutine hepmc_vertex_particle_in_iterator_advance

```

Reset to the beginning

```

    <HepMC interface: interfaces>+≡
        interface
            subroutine vertex_particles_in_const_iterator_reset &
                (it_obj, v_obj) bind(C)
                import
                type(c_ptr), value :: it_obj, v_obj
            end subroutine vertex_particles_in_const_iterator_reset
        end interface
    <HepMC interface: public>+≡
        public :: hepmc_vertex_particle_in_iterator_reset
    <HepMC interface: procedures>+≡
        subroutine hepmc_vertex_particle_in_iterator_reset (it)
            type(hepmc_vertex_particle_in_iterator_t), intent(inout) :: it
            call vertex_particles_in_const_iterator_reset (it%obj, it%v_obj)
        end subroutine hepmc_vertex_particle_in_iterator_reset

```

Test: return true as long as we are not past the end.

```

    <HepMC interface: interfaces>+≡
        interface

```

```

        function vertex_particles_in_const_iterator_is_valid &
            (it_obj, v_obj) result (flag) bind(C)
        import
        logical(c_bool) :: flag
        type(c_ptr), value :: it_obj, v_obj
    end function vertex_particles_in_const_iterator_is_valid
end interface
<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_is_valid
<HepMC interface: procedures>+≡
    function hepmc_vertex_particle_in_iterator_is_valid (it) result (flag)
        logical :: flag
        type(hepmc_vertex_particle_in_iterator_t), intent(in) :: it
        flag = vertex_particles_in_const_iterator_is_valid (it%obj, it%v_obj)
    end function hepmc_vertex_particle_in_iterator_is_valid

```

Return the particle pointed to by the iterator. (The particle object should not be finalized, since it contains merely a pointer to the particle which is owned by the vertex.)

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function &
            vertex_particles_in_const_iterator_get (it_obj) bind(C)
        import
        type(c_ptr), value :: it_obj
    end function vertex_particles_in_const_iterator_get
end interface
<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_get
<HepMC interface: procedures>+≡
    function hepmc_vertex_particle_in_iterator_get (it) result (prt)
        type(hepmc_particle_t) :: prt
        type(hepmc_vertex_particle_in_iterator_t), intent(in) :: it
        prt%obj = vertex_particles_in_const_iterator_get (it%obj)
    end function hepmc_vertex_particle_in_iterator_get

```

17.8.7 Vertex-particle-out iterator

This iterator iterates over all incoming particles in an vertex. We store a pointer to the vertex in addition to the iterator. This allows for simple end checking.

The iterator is actually a constant iterator; it can only read.

```

<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_out_iterator_t
<HepMC interface: types>+≡
    type :: hepmc_vertex_particle_out_iterator_t
    private
    type(c_ptr) :: obj
    type(c_ptr) :: v_obj
end type hepmc_vertex_particle_out_iterator_t

```

Constructor. The iterator is initialized at the first particle in the vertex.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function &
      new_vertex_particles_out_const_iterator (v_obj) bind(C)
    import
      type(c_ptr), value :: v_obj
    end function new_vertex_particles_out_const_iterator
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_init
<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_init (it, v)
    type(hepmc_vertex_particle_out_iterator_t), intent(out) :: it
    type(hepmc_vertex_t), intent(in) :: v
    it%obj = new_vertex_particles_out_const_iterator (v%obj)
    it%v_obj = v%obj
  end subroutine hepmc_vertex_particle_out_iterator_init

```

Destructor. Necessary because the iterator is allocated on the heap.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine vertex_particles_out_const_iterator_delete (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end subroutine vertex_particles_out_const_iterator_delete
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_final
<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_final (it)
    type(hepmc_vertex_particle_out_iterator_t), intent(inout) :: it
    call vertex_particles_out_const_iterator_delete (it%obj)
  end subroutine hepmc_vertex_particle_out_iterator_final

```

Increment

```

<HepMC interface: interfaces>+≡
  interface
    subroutine vertex_particles_out_const_iterator_advance (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end subroutine vertex_particles_out_const_iterator_advance
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_advance
<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_advance (it)
    type(hepmc_vertex_particle_out_iterator_t), intent(inout) :: it
    call vertex_particles_out_const_iterator_advance (it%obj)
  end subroutine hepmc_vertex_particle_out_iterator_advance

```

Reset to the beginning

```

<HepMC interface: interfaces>+≡
  interface
    subroutine vertex_particles_out_const_iterator_reset &
      (it_obj, v_obj) bind(C)
    import
      type(c_ptr), value :: it_obj, v_obj
    end subroutine vertex_particles_out_const_iterator_reset
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_reset

<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_reset (it)
    type(hepmc_vertex_particle_out_iterator_t), intent(inout) :: it
    call vertex_particles_out_const_iterator_reset (it%obj, it%v_obj)
  end subroutine hepmc_vertex_particle_out_iterator_reset

```

Test: return true as long as we are not past the end.

```

<HepMC interface: interfaces>+≡
  interface
    function vertex_particles_out_const_iterator_is_valid &
      (it_obj, v_obj) result (flag) bind(C)
    import
      logical(c_bool) :: flag
      type(c_ptr), value :: it_obj, v_obj
    end function vertex_particles_out_const_iterator_is_valid
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_is_valid

<HepMC interface: procedures>+≡
  function hepmc_vertex_particle_out_iterator_is_valid (it) result (flag)
    logical :: flag
    type(hepmc_vertex_particle_out_iterator_t), intent(in) :: it
    flag = vertex_particles_out_const_iterator_is_valid (it%obj, it%v_obj)
  end function hepmc_vertex_particle_out_iterator_is_valid

```

Return the particle pointed to by the iterator. (The particle object should not be finalized, since it contains merely a pointer to the particle which is owned by the vertex.)

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function &
      vertex_particles_out_const_iterator_get (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end function vertex_particles_out_const_iterator_get
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_get

```

```

<HepMC interface: procedures>+≡
  function hepmc_vertex_particle_out_iterator_get (it) result (prt)
    type(hepmc_particle_t) :: prt
    type(hepmc_vertex_particle_out_iterator_t), intent(in) :: it
    prt%obj = vertex_particles_out_const_iterator_get (it%obj)
  end function hepmc_vertex_particle_out_iterator_get

```

17.8.8 GenEvent

The main object of HepMC is a GenEvent. The object is filled by GenVertex objects, which in turn contain GenParticle objects.

```

<HepMC interface: public>+≡
  public :: hepmc_event_t

<HepMC interface: types>+≡
  type :: hepmc_event_t
  private
  type(c_ptr) :: obj
end type hepmc_event_t

```

Constructor. Arguments are process ID (integer) and event ID (integer).
The Fortran version has initializer form.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_gen_event (proc_id, event_id) bind(C)
      import
      integer(c_int), value :: proc_id, event_id
    end function new_gen_event
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_init

<HepMC interface: procedures>+≡
  subroutine hepmc_event_init (evt, proc_id, event_id)
    type(hepmc_event_t), intent(out) :: evt
    integer, intent(in), optional :: proc_id, event_id
    integer(c_int) :: pid, eid
    pid = 0; if (present (proc_id)) pid = proc_id
    eid = 0; if (present (event_id)) eid = event_id
    evt%obj = new_gen_event (pid, eid)
  end subroutine hepmc_event_init

```

Destructor.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_delete (evt_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
    end subroutine gen_event_delete
  end interface

```

```

<HepMC interface: public>+≡
    public :: hepmc_event_final

<HepMC interface: procedures>+≡
    subroutine hepmc_event_final (evt)
        type(hepmc_event_t), intent(inout) :: evt
        call gen_event_delete (evt%obj)
    end subroutine hepmc_event_final

```

Screen output. Printing to file is possible in principle (using a C++ output channel), by allowing an argument. Printing to an open Fortran unit is obviously not possible.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine gen_event_print (evt_obj) bind(C)
            import
            type(c_ptr), value :: evt_obj
        end subroutine gen_event_print
    end interface

<HepMC interface: public>+≡
    public :: hepmc_event_print

<HepMC interface: procedures>+≡
    subroutine hepmc_event_print (evt)
        type(hepmc_event_t), intent(in) :: evt
        call gen_event_print (evt%obj)
    end subroutine hepmc_event_print

```

Get the event number.

```

<HepMC interface: interfaces>+≡
    interface
        integer(c_int) function gen_event_event_number (evt_obj) bind(C)
            use iso_c_binding !NODEP!
            type(c_ptr), value :: evt_obj
        end function gen_event_event_number
    end interface

<HepMC interface: public>+≡
    public :: hepmc_event_get_event_index

<HepMC interface: procedures>+≡
    function hepmc_event_get_event_index (evt) result (i_proc)
        integer :: i_proc
        type(hepmc_event_t), intent(in) :: evt
        i_proc = gen_event_event_number (evt%obj)
    end function hepmc_event_get_event_index

```

Set the numeric signal process ID

```

<HepMC interface: interfaces>+≡
    interface
        subroutine gen_event_set_signal_process_id (evt_obj, proc_id) bind(C)
            import
            type(c_ptr), value :: evt_obj

```

```

        integer(c_int), value :: proc_id
    end subroutine gen_event_set_signal_process_id
end interface

<HepMC interface: public>+≡
    public :: hepmc_event_set_process_id

<HepMC interface: procedures>+≡
    subroutine hepmc_event_set_process_id (evt, proc)
        type(hepmc_event_t), intent(in) :: evt
        integer, intent(in) :: proc
        integer(c_int) :: i_proc
        i_proc = proc
        call gen_event_set_signal_process_id (evt%obj, i_proc)
    end subroutine hepmc_event_set_process_id

```

Get the numeric signal process ID

```

<HepMC interface: interfaces>+≡
    interface
        integer(c_int) function gen_event_signal_process_id (evt_obj) bind(C)
        import
        type(c_ptr), value :: evt_obj
    end function gen_event_signal_process_id
    end interface

<HepMC interface: public>+≡
    public :: hepmc_event_get_process_id

<HepMC interface: procedures>+≡
    function hepmc_event_get_process_id (evt) result (i_proc)
        integer :: i_proc
        type(hepmc_event_t), intent(in) :: evt
        i_proc = gen_event_signal_process_id (evt%obj)
    end function hepmc_event_get_process_id

```

Set the event energy scale

```

<HepMC interface: interfaces>+≡
    interface
        subroutine gen_event_set_event_scale (evt_obj, scale) bind(C)
        import
        type(c_ptr), value :: evt_obj
        real(c_double), value :: scale
    end subroutine gen_event_set_event_scale
    end interface

<HepMC interface: public>+≡
    public :: hepmc_event_set_scale

<HepMC interface: procedures>+≡
    subroutine hepmc_event_set_scale (evt, scale)
        type(hepmc_event_t), intent(in) :: evt
        real(default), intent(in) :: scale
        real(c_double) :: cscale
        cscale = scale
        call gen_event_set_event_scale (evt%obj, cscale)
    end subroutine hepmc_event_set_scale

```

Get the event energy scale

```
<HepMC interface: interfaces>+≡  
  interface  
    real(c_double) function gen_event_event_scale (evt_obj) bind(C)  
    import  
    type(c_ptr), value :: evt_obj  
    end function gen_event_event_scale  
  end interface  
  
<HepMC interface: public>+≡  
  public :: hepmc_event_get_scale  
  
<HepMC interface: procedures>+≡  
  function hepmc_event_get_scale (evt) result (scale)  
    real(default) :: scale  
    type(hepmc_event_t), intent(in) :: evt  
    scale = gen_event_event_scale (evt%obj)  
  end function hepmc_event_get_scale
```

Set the value of α_{QCD} .

```
<HepMC interface: interfaces>+≡  
  interface  
    subroutine gen_event_set_alpha_qcd (evt_obj, a) bind(C)  
    import  
    type(c_ptr), value :: evt_obj  
    real(c_double), value :: a  
    end subroutine gen_event_set_alpha_qcd  
  end interface  
  
<HepMC interface: public>+≡  
  public :: hepmc_event_set_alpha_qcd  
  
<HepMC interface: procedures>+≡  
  subroutine hepmc_event_set_alpha_qcd (evt, alpha)  
    type(hepmc_event_t), intent(in) :: evt  
    real(default), intent(in) :: alpha  
    real(c_double) :: a  
    a = alpha  
    call gen_event_set_alpha_qcd (evt%obj, a)  
  end subroutine hepmc_event_set_alpha_qcd
```

Get the value of α_{QCD} .

```
<HepMC interface: interfaces>+≡  
  interface  
    real(c_double) function gen_event_alpha_qcd (evt_obj) bind(C)  
    import  
    type(c_ptr), value :: evt_obj  
    end function gen_event_alpha_qcd  
  end interface  
  
<HepMC interface: public>+≡  
  public :: hepmc_event_get_alpha_qcd
```



```

<HepMC interface: procedures>+≡
function hepmc_event_get_alpha_qcd (evt) result (alpha)
  real(default) :: alpha
  type(hepmc_event_t), intent(in) :: evt
  alpha = gen_event_alpha_qcd (evt%obj)
end function hepmc_event_get_alpha_qcd

```

Set the value of α_{QED} .

```

<HepMC interface: interfaces>+≡
interface
  subroutine gen_event_set_alpha_qed (evt_obj, a) bind(C)
    import
    type(c_ptr), value :: evt_obj
    real(c_double), value :: a
  end subroutine gen_event_set_alpha_qed
end interface

```

```

<HepMC interface: public>+≡
public :: hepmc_event_set_alpha_qed

```

```

<HepMC interface: procedures>+≡
subroutine hepmc_event_set_alpha_qed (evt, alpha)
  type(hepmc_event_t), intent(in) :: evt
  real(default), intent(in) :: alpha
  real(c_double) :: a
  a = alpha
  call gen_event_set_alpha_qed (evt%obj, a)
end subroutine hepmc_event_set_alpha_qed

```

Get the value of α_{QED} .

```

<HepMC interface: interfaces>+≡
interface
  real(c_double) function gen_event_alpha_qed (evt_obj) bind(C)
    import
    type(c_ptr), value :: evt_obj
  end function gen_event_alpha_qed
end interface

```

```

<HepMC interface: public>+≡
public :: hepmc_event_get_alpha_qed

```

```

<HepMC interface: procedures>+≡
function hepmc_event_get_alpha_qed (evt) result (alpha)
  real(default) :: alpha
  type(hepmc_event_t), intent(in) :: evt
  alpha = gen_event_alpha_qed (evt%obj)
end function hepmc_event_get_alpha_qed

```

Clear a weight value to the end of the weight container.

```

<HepMC interface: interfaces>+≡
interface
  subroutine gen_event_clear_weights (evt_obj) bind(C)
    use iso_c_binding !NODEP!
    type(c_ptr), value :: evt_obj
  end subroutine gen_event_clear_weights
end interface

```

```

        end subroutine gen_event_clear_weights
    end interface

    <HepMC interface: public>+≡
        public :: hepmc_event_clear_weights

    <HepMC interface: procedures>+≡
        subroutine hepmc_event_clear_weights (evt)
            type(hepmc_event_t), intent(in) :: evt
            call gen_event_clear_weights (evt%obj)
        end subroutine hepmc_event_clear_weights

```

Add a weight value to the end of the weight container.

```

    <HepMC interface: interfaces>+≡
        interface
            subroutine gen_event_add_weight (evt_obj, w) bind(C)
                use iso_c_binding !NODEP!
                type(c_ptr), value :: evt_obj
                real(c_double), value :: w
            end subroutine gen_event_add_weight
        end interface

    <HepMC interface: public>+≡
        public :: hepmc_event_add_weight

    <HepMC interface: procedures>+≡
        subroutine hepmc_event_add_weight (evt, weight)
            type(hepmc_event_t), intent(in) :: evt
            real(default), intent(in) :: weight
            real(c_double) :: w
            w = weight
            call gen_event_add_weight (evt%obj, w)
        end subroutine hepmc_event_add_weight

```

Get the size of the weight container (the number of valid elements).

```

    <HepMC interface: interfaces>+≡
        interface
            integer(c_int) function gen_event_weights_size (evt_obj) bind(C)
                use iso_c_binding !NODEP!
                type(c_ptr), value :: evt_obj
            end function gen_event_weights_size
        end interface

    <HepMC interface: public>+≡
        public :: hepmc_event_get_weights_size

    <HepMC interface: procedures>+≡
        function hepmc_event_get_weights_size (evt) result (n)
            integer :: n
            type(hepmc_event_t), intent(in) :: evt
            n = gen_event_weights_size (evt%obj)
        end function hepmc_event_get_weights_size

```

Get the value of the weight with index i. (Count from 1, while C counts from zero.)

```

<HepMC interface: interfaces>+≡
  interface
    real(c_double) function gen_event_weight (evt_obj, i) bind(C)
      use iso_c_binding !NODEP!
      type(c_ptr), value :: evt_obj
      integer(c_int), value :: i
    end function gen_event_weight
  end interface
<HepMC interface: public>+≡
  public :: hepmc_event_get_weight
<HepMC interface: procedures>+≡
  function hepmc_event_get_weight (evt, index) result (weight)
    real(default) :: weight
    type(hepmc_event_t), intent(in) :: evt
    integer, intent(in) :: index
    integer(c_int) :: i
    i = index - 1
    weight = gen_event_weight (evt%obj, i)
  end function hepmc_event_get_weight

```

Add a vertex to the event container.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_add_vertex (evt_obj, v_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
      type(c_ptr), value :: v_obj
    end subroutine gen_event_add_vertex
  end interface
<HepMC interface: public>+≡
  public :: hepmc_event_add_vertex
<HepMC interface: procedures>+≡
  subroutine hepmc_event_add_vertex (evt, v)
    type(hepmc_event_t), intent(inout) :: evt
    type(hepmc_vertex_t), intent(in) :: v
    call gen_event_add_vertex (evt%obj, v%obj)
  end subroutine hepmc_event_add_vertex

```

Mark a particular vertex as the signal process (hard interaction).

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_set_signal_process_vertex (evt_obj, v_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
      type(c_ptr), value :: v_obj
    end subroutine gen_event_set_signal_process_vertex
  end interface
<HepMC interface: public>+≡
  public :: hepmc_event_set_signal_process_vertex

```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_signal_process_vertex (evt, v)
    type(hepmc_event_t), intent(inout) :: evt
    type(hepmc_vertex_t), intent(in) :: v
    call gen_event_set_signal_process_vertex (evt%obj, v%obj)
  end subroutine hepmc_event_set_signal_process_vertex

```

Return the the signal process (hard interaction).

```

<HepMC interface: interfaces>+≡
  interface
    function gen_event_get_signal_process_vertex (evt_obj) &
      result (v_obj) bind(C)
    import
    type(c_ptr), value :: evt_obj
    type(c_ptr) :: v_obj
  end function gen_event_get_signal_process_vertex
end interface

```

```

<HepMC interface: public>+≡
  public :: hepmc_event_get_signal_process_vertex

```

```

<HepMC interface: procedures>+≡
  function hepmc_event_get_signal_process_vertex (evt) result (v)
    type(hepmc_event_t), intent(in) :: evt
    type(hepmc_vertex_t) :: v
    v%obj = gen_event_get_signal_process_vertex (evt%obj)
  end function hepmc_event_get_signal_process_vertex

```

Set the beam particles explicitly.

```

<HepMC interface: public>+≡
  public :: hepmc_event_set_beam_particles

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_beam_particles (evt, prt1, prt2)
    type(hepmc_event_t), intent(inout) :: evt
    type(hepmc_particle_t), intent(in) :: prt1, prt2
    logical(c_bool) :: flag
    flag = gen_event_set_beam_particles (evt%obj, prt1%obj, prt2%obj)
  end subroutine hepmc_event_set_beam_particles

```

The C function returns a boolean which we do not use.

```

<HepMC interface: interfaces>+≡
  interface
    logical(c_bool) function gen_event_set_beam_particles &
      (evt_obj, prt1_obj, prt2_obj) bind(C)
    import
    type(c_ptr), value :: evt_obj, prt1_obj, prt2_obj
  end function gen_event_set_beam_particles
end interface

```

Set the cross section and error explicitly. Note that HepMC uses pb, while WHIZARD uses fb.

```

<HepMC interface: public>+≡
  public :: hepmc_event_set_cross_section

```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_cross_section (evt, xsec, xsec_err)
    type(hepmc_event_t), intent(inout) :: evt
    real(default), intent(in) :: xsec, xsec_err
    call gen_event_set_cross_section &
      (evt%obj, &
       real (xsec * 1e-3_default, c_double), &
       real (xsec_err * 1e-3_default, c_double))
  end subroutine hepmc_event_set_cross_section

```

The C function returns a boolean which we do not use.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_set_cross_section (evt_obj, xs, xs_err) bind(C)
      import
      type(c_ptr), value :: evt_obj
      real(c_double), value :: xs, xs_err
    end subroutine gen_event_set_cross_section
  end interface

```

17.8.9 Event-particle iterator

This iterator iterates over all particles in an event. We store a pointer to the event in addition to the iterator. This allows for simple end checking.

The iterator is actually a constant iterator; it can only read.

```

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_t

<HepMC interface: types>+≡
  type :: hepmc_event_particle_iterator_t
  private
  type(c_ptr) :: obj
  type(c_ptr) :: evt_obj
  end type hepmc_event_particle_iterator_t

```

Constructor. The iterator is initialized at the first particle in the event.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_event_particle_const_iterator (evt_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
    end function new_event_particle_const_iterator
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_init

<HepMC interface: procedures>+≡
  subroutine hepmc_event_particle_iterator_init (it, evt)
    type(hepmc_event_particle_iterator_t), intent(out) :: it
    type(hepmc_event_t), intent(in) :: evt
    it%obj = new_event_particle_const_iterator (evt%obj)

```

```

        it%evt_obj = evt%obj
    end subroutine hepmc_event_particle_iterator_init

```

Destructor. Necessary because the iterator is allocated on the heap.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine event_particle_const_iterator_delete (it_obj) bind(C)
            import
            type(c_ptr), value :: it_obj
        end subroutine event_particle_const_iterator_delete
    end interface
<HepMC interface: public>+≡
    public :: hepmc_event_particle_iterator_final
<HepMC interface: procedures>+≡
    subroutine hepmc_event_particle_iterator_final (it)
        type(hepmc_event_particle_iterator_t), intent(inout) :: it
        call event_particle_const_iterator_delete (it%obj)
    end subroutine hepmc_event_particle_iterator_final

```

Increment

```

<HepMC interface: interfaces>+≡
    interface
        subroutine event_particle_const_iterator_advance (it_obj) bind(C)
            import
            type(c_ptr), value :: it_obj
        end subroutine event_particle_const_iterator_advance
    end interface
<HepMC interface: public>+≡
    public :: hepmc_event_particle_iterator_advance
<HepMC interface: procedures>+≡
    subroutine hepmc_event_particle_iterator_advance (it)
        type(hepmc_event_particle_iterator_t), intent(inout) :: it
        call event_particle_const_iterator_advance (it%obj)
    end subroutine hepmc_event_particle_iterator_advance

```

Reset to the beginning

```

<HepMC interface: interfaces>+≡
    interface
        subroutine event_particle_const_iterator_reset (it_obj, evt_obj) bind(C)
            import
            type(c_ptr), value :: it_obj, evt_obj
        end subroutine event_particle_const_iterator_reset
    end interface
<HepMC interface: public>+≡
    public :: hepmc_event_particle_iterator_reset
<HepMC interface: procedures>+≡
    subroutine hepmc_event_particle_iterator_reset (it)
        type(hepmc_event_particle_iterator_t), intent(inout) :: it
        call event_particle_const_iterator_reset (it%obj, it%evt_obj)
    end subroutine hepmc_event_particle_iterator_reset

```

Test: return true as long as we are not past the end.

```

<HepMC interface: interfaces>+≡
  interface
    function event_particle_const_iterator_is_valid &
      (it_obj, evt_obj) result (flag) bind(C)
    import
      logical(c_bool) :: flag
      type(c_ptr), value :: it_obj, evt_obj
    end function event_particle_const_iterator_is_valid
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_is_valid

<HepMC interface: procedures>+≡
  function hepmc_event_particle_iterator_is_valid (it) result (flag)
    logical :: flag
    type(hepmc_event_particle_iterator_t), intent(in) :: it
    flag = event_particle_const_iterator_is_valid (it%obj, it%evt_obj)
  end function hepmc_event_particle_iterator_is_valid

```

Return the particle pointed to by the iterator. (The particle object should not be finalized, since it contains merely a pointer to the particle which is owned by the vertex.)

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function event_particle_const_iterator_get (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end function event_particle_const_iterator_get
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_get

<HepMC interface: procedures>+≡
  function hepmc_event_particle_iterator_get (it) result (prt)
    type(hepmc_particle_t) :: prt
    type(hepmc_event_particle_iterator_t), intent(in) :: it
    prt%obj = event_particle_const_iterator_get (it%obj)
  end function hepmc_event_particle_iterator_get

```

17.8.10 I/O streams

There is a specific I/O stream type for handling the output of GenEvent objects (i.e., Monte Carlo event samples) to file. Opening the file is done by the constructor, closing by the destructor.

```

<HepMC interface: public>+≡
  public :: hepmc_iostream_t

<HepMC interface: types>+≡
  type :: hepmc_iostream_t
  private
    type(c_ptr) :: obj

```

```
end type hepmc_iostream_t
```

Constructor for an output stream associated to a file.

```
<HepMC interface: interfaces>+≡
interface
  type(c_ptr) function new_io_gen_event_out (filename) bind(C)
  import
    character(c_char), dimension(*), intent(in) :: filename
  end function new_io_gen_event_out
end interface

<HepMC interface: public>+≡
public :: hepmc_iostream_open_out

<HepMC interface: procedures>+≡
subroutine hepmc_iostream_open_out (iostream, filename)
  type(hepmc_iostream_t), intent(out) :: iostream
  type(string_t), intent(in) :: filename
  iostream%obj = new_io_gen_event_out (char (filename) // c_null_char)
end subroutine hepmc_iostream_open_out
```

Constructor for an input stream associated to a file.

```
<HepMC interface: interfaces>+≡
interface
  type(c_ptr) function new_io_gen_event_in (filename) bind(C)
  import
    character(c_char), dimension(*), intent(in) :: filename
  end function new_io_gen_event_in
end interface

<HepMC interface: public>+≡
public :: hepmc_iostream_open_in

<HepMC interface: procedures>+≡
subroutine hepmc_iostream_open_in (iostream, filename)
  type(hepmc_iostream_t), intent(out) :: iostream
  type(string_t), intent(in) :: filename
  iostream%obj = new_io_gen_event_in (char (filename) // c_null_char)
end subroutine hepmc_iostream_open_in
```

Destructor:

```
<HepMC interface: interfaces>+≡
interface
  subroutine io_gen_event_delete (io_obj) bind(C)
  import
    type(c_ptr), value :: io_obj
  end subroutine io_gen_event_delete
end interface

<HepMC interface: public>+≡
public :: hepmc_iostream_close
```



```

<HepMC interface: procedures>+≡
  subroutine hepmc_iostream_close (iostream)
    type(hepmc_iostream_t), intent(inout) :: iostream
    call io_gen_event_delete (iostream%obj)
  end subroutine hepmc_iostream_close

```

Write a single event to the I/O stream.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine io_gen_event_write_event (io_obj, evt_obj) bind(C)
      import
      type(c_ptr), value :: io_obj, evt_obj
    end subroutine io_gen_event_write_event
  end interface

<HepMC interface: public>+≡
  public :: hepmc_iostream_write_event

<HepMC interface: procedures>+≡
  subroutine hepmc_iostream_write_event (iostream, evt)
    type(hepmc_iostream_t), intent(inout) :: iostream
    type(hepmc_event_t), intent(in) :: evt
    call io_gen_event_write_event (iostream%obj, evt%obj)
  end subroutine hepmc_iostream_write_event

```

Read a single event from the I/O stream. Return true if successful.

```

<HepMC interface: interfaces>+≡
  interface
    logical(c_bool) function io_gen_event_read_event (io_obj, evt_obj) bind(C)
      import
      type(c_ptr), value :: io_obj, evt_obj
    end function io_gen_event_read_event
  end interface

<HepMC interface: public>+≡
  public :: hepmc_iostream_read_event

<HepMC interface: procedures>+≡
  subroutine hepmc_iostream_read_event (iostream, evt, ok)
    type(hepmc_iostream_t), intent(inout) :: iostream
    type(hepmc_event_t), intent(inout) :: evt
    logical, intent(out) :: ok
    ok = io_gen_event_read_event (iostream%obj, evt%obj)
  end subroutine hepmc_iostream_read_event

```

17.8.11 Unit tests

This test example is an abridged version from the build-from-scratch example in the HepMC distribution. We create two vertices for $p \rightarrow q$ PDF splitting, then a vertex for a $qq \rightarrow W^- g$ hard-interaction process, and finally a vertex for $W^- \rightarrow qq$ decay. The setup is for LHC kinematics.

Extending the original example, we set color flow for the incoming quarks and polarization for the outgoing photon. For the latter, we have to define a particle-data object for the photon, so a flavor object can be correctly initialized.

```

<HepMC interface: public>+≡
    public :: hepmc_test

<HepMC interface: procedures>+≡
    subroutine hepmc_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <HepMC interface: execute tests>
    end subroutine hepmc_test

<HepMC interface: execute tests>≡
    call test (hepmc_interface_1, "hepmc_interface_1", &
        "check HepMC interface", &
        u, results)

<HepMC interface: tests>≡
    subroutine hepmc_interface_1 (u)
        use physics_defs, only: VECTOR
        use model_data, only: field_data_t
        integer, intent(in) :: u
        integer :: u_file, iostat
        type(hepmc_event_t) :: evt
        type(hepmc_vertex_t) :: v1, v2, v3, v4
        type(hepmc_particle_t) :: prt1, prt2, prt3, prt4, prt5, prt6, prt7, prt8
        type(hepmc_iostream_t) :: iostream
        type(flavor_t) :: flv
        type(color_t) :: col
        type(polarization_t) :: pol
        type(field_data_t), target :: photon_data
        character(80) :: buffer

        write (u, "(A)")  "* Test output: HepMC interface"
        write (u, "(A)")  "* Purpose: test HepMC interface"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")

        ! Initialize a photon flavor object and some polarization
        call photon_data%init (var_str ("PHOTON"), 22)
        call photon_data%set (spin_type=VECTOR)
        call photon_data%freeze ()
        call flv%init (photon_data)
        call polarization_init_angles &
            (pol, flv, 0.6_default, 1._default, 0.5_default)

        ! Event initialization
        call hepmc_event_init (evt, 20, 1)

        write (u, "(A)")  "* p -> q splitting"
        write (u, "(A)")

```

```

! $p\to q$ splittings
call hepmc_vertex_init (v1)
call hepmc_event_add_vertex (evt, v1)
call hepmc_vertex_init (v2)
call hepmc_event_add_vertex (evt, v2)
call particle_init (prt1, &
    0._default, 0._default, 7000._default, 7000._default, &
    2212, 3)
call hepmc_vertex_add_particle_in (v1, prt1)
call particle_init (prt2, &
    0._default, 0._default, -7000._default, 7000._default, &
    2212, 3)
call hepmc_vertex_add_particle_in (v2, prt2)
call particle_init (prt3, &
    .750_default, -1.569_default, 32.191_default, 32.238_default, &
    1, 3)
call color_init_from_array (col, [501])
call hepmc_particle_set_color (prt3, col)
call hepmc_vertex_add_particle_out (v1, prt3)
call particle_init (prt4, &
    -3.047_default, -19._default, -54.629_default, 57.920_default, &
    -2, 3)
call color_init_from_array (col, [-501])
call hepmc_particle_set_color (prt4, col)
call hepmc_vertex_add_particle_out (v2, prt4)

write (u, "(A)")  "* Hard interaction"
write (u, "(A)")

! Hard interaction
call hepmc_vertex_init (v3)
call hepmc_event_add_vertex (evt, v3)
call hepmc_vertex_add_particle_in (v3, prt3)
call hepmc_vertex_add_particle_in (v3, prt4)
call particle_init (prt6, &
    -3.813_default, 0.113_default, -1.833_default, 4.233_default, &
    22, 1)
call hepmc_particle_set_polarization (prt6, pol)
call hepmc_vertex_add_particle_out (v3, prt6)
call particle_init (prt5, &
    1.517_default, -20.68_default, -20.605_default, 85.925_default, &
    -24, 3)
call hepmc_vertex_add_particle_out (v3, prt5)
call hepmc_event_set_signal_process_vertex (evt, v3)

! $W^-$ decay
call vertex_init_pos (v4, &
    0.12_default, -0.3_default, 0.05_default, 0.004_default)
call hepmc_event_add_vertex (evt, v4)
call hepmc_vertex_add_particle_in (v4, prt5)
call particle_init (prt7, &
    -2.445_default, 28.816_default, 6.082_default, 29.552_default, &
    1, 1)

```

```

call hepmc_vertex_add_particle_out (v4, prt7)
call particle_init (prt8, &
    3.962_default, -49.498_default, -26.687_default, 56.373_default, &
    -2, 1)
call hepmc_vertex_add_particle_out (v4, prt8)

! Event output
call hepmc_event_print (evt)
write (u, "(A)") "Writing to file 'hepmc_test.hepmc'"
write (u, "(A)")

call hepmc_iostream_open_out (iostream, var_str ("hepmc_test.hepmc"))
call hepmc_iostream_write_event (iostream, evt)
call hepmc_iostream_close (iostream)

write (u, "(A)") "Writing completed"

write (u, "(A)")
write (u, "(A)") "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = "hepmc_test.hepmc", &
    action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat) buffer
    if (buffer(1:14) == "HepMC::Version") buffer = "[...]"
    if (iostat /= 0) exit
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)") "* Cleanup"
write (u, "(A)")

! Wrapup
call polarization_final (pol)
call hepmc_event_final (evt)

write (u, "(A)")
write (u, "(A)") "* Test output end: hepmc_interface_1"

contains

subroutine vertex_init_pos (v, x, y, z, t)
    type(hepmc_vertex_t), intent(out) :: v
    real(default), intent(in) :: x, y, z, t
    type(vector4_t) :: xx
    xx = vector4_moving (t, vector3_moving ([x, y, z]))
    call hepmc_vertex_init (v, xx)
end subroutine vertex_init_pos

subroutine particle_init (prt, px, py, pz, E, pdg, status)

```

```

    type(hepmc_particle_t), intent(out) :: prt
    real(default), intent(in) :: px, py, pz, E
    integer, intent(in) :: pdg, status
    type(vector4_t) :: p
    p = vector4_moving (E, vector3_moving ([px, py, pz]))
    call hepmc_particle_init (prt, p, pdg, status)
end subroutine particle_init

end subroutine hepmc_interface_1

```

17.9 LCIO events

This section provides the interface to the LCIO C++ library for handling Monte-Carlo events.

Each C++ class of LCIO that we use is mirrored by a Fortran type, which contains as its only component the C pointer to the C++ object.

Each C++ method of LCIO that we use has a C wrapper function. This function takes a pointer to the host object as its first argument. Further arguments are either C pointers, or in the case of simple types (integer, real), interoperable C/Fortran objects.

The C wrapper functions have explicit interfaces in the Fortran module. They are called by Fortran wrapper procedures. These are treated as methods of the corresponding Fortran type.

`<lcio_interface.f90>`≡
<File header>

```
module lcio_interface
```

```
    use, intrinsic :: iso_c_binding !NODEP!
```

<Use kinds>

<Use strings>

```

    use io_units
    use constants
    use lorentz
    use unit_tests
    use diagnostics
    use model_data
    use flavors
    use colors
    use helicities
    use quantum_numbers
    use polarizations

```

<Standard module head>

<LCIO interface: public>

<LCIO interface: types>

<LCIO interface: interfaces>

```
contains

  <LCIO interface: procedures>

  <LCIO interface: tests>

end module lcio_interface
```

17.9.1 Interface check

This function can be called in order to verify that we are using the actual LCIO library, and not the dummy version.

```
<LCIO interface: interfaces>≡
  interface
    logical(c_bool) function lcio_available () bind(C)
      import
    end function lcio_available
  end interface

<LCIO interface: public>≡
  public :: lcio_is_available

<LCIO interface: procedures>≡
  function lcio_is_available () result (flag)
    logical :: flag
    flag = lcio_available ()
  end function lcio_is_available
```

17.9.2 LCIO Run Header

This is a type for the run header of the LCIO file.

```
<LCIO interface: public>+≡
  public :: lcio_run_header_t

<LCIO interface: types>≡
  type :: lcio_run_header_t
  private
    type(c_ptr) :: obj
  end type lcio_run_header_t
```

The Fortran version has initializer form.

```
<LCIO interface: interfaces>+≡
  interface
    type(c_ptr) function new_lcio_run_header (proc_id) bind(C)
      import
      integer(c_int), value :: proc_id
    end function new_lcio_run_header
  end interface
```

```

<LCIO interface: interfaces>+≡
interface
  subroutine run_header_set_simstring &
    (runhdr_obj, simstring) bind(C)
  import
    type(c_ptr), value :: runhdr_obj
    character(c_char), dimension(*), intent(in) :: simstring
  end subroutine run_header_set_simstring
end interface

<LCIO interface: public>+≡
public :: lcio_run_header_init

<LCIO interface: procedures>+≡
subroutine lcio_run_header_init (runhdr, proc_id, run_id)
  type(lcio_run_header_t), intent(out) :: runhdr
  integer, intent(in), optional :: proc_id, run_id
  integer(c_int) :: pid, rid
  pid = 0; if (present (proc_id)) pid = proc_id
  rid = 0; if (present (run_id)) rid = run_id
  runhdr%obj = new_lcio_run_header (rid)
  call run_header_set_simstring (runhdr%obj, &
    "WHIZARD version:" // "<Version>")
end subroutine lcio_run_header_init

<LCIO interface: interfaces>+≡
interface
  subroutine write_run_header (lcwrt_obj, runhdr_obj) bind(C)
  import
    type(c_ptr), value :: lcwrt_obj
    type(c_ptr), value :: runhdr_obj
  end subroutine write_run_header
end interface

<LCIO interface: public>+≡
public :: lcio_run_header_write

<LCIO interface: procedures>+≡
subroutine lcio_run_header_write (wrt, hdr)
  type(lcio_writer_t), intent(inout) :: wrt
  type(lcio_run_header_t), intent(inout) :: hdr
  call write_run_header (wrt%obj, hdr%obj)
end subroutine lcio_run_header_write

```

17.9.3 LCIO Event and LC Collection

The main object of LCIO is a LCEventImpl. The object is filled by MCParticle objects, which are set as LCCollection.

```

<LCIO interface: public>+≡
public :: lccollection_t

<LCIO interface: types>+≡
type :: lccollection_t
private

```

```

        type(c_ptr) :: obj
    end type lccollection_t

```

Initializer.

```

<LCIO interface: interfaces>+≡
    interface
        type(c_ptr) function new_lccollection () bind(C)
        import
        end function new_lccollection
    end interface

<LCIO interface: public>+≡
    public :: lcio_event_t

<LCIO interface: types>+≡
    type :: lcio_event_t
    private
        type(c_ptr) :: obj
        type(lccollection_t) :: lccoll
    end type lcio_event_t

```

Constructor. Arguments are process ID (integer) and event ID (integer).

The Fortran version has initializer form.

```

<LCIO interface: interfaces>+≡
    interface
        type(c_ptr) function new_lcio_event (proc_id, event_id, run_id) bind(C)
        import
        integer(c_int), value :: proc_id, event_id, run_id
        end function new_lcio_event
    end interface

<LCIO interface: public>+≡
    public :: lcio_event_init

<LCIO interface: procedures>+≡
    subroutine lcio_event_init (evt, proc_id, event_id, run_id)
        type(lcio_event_t), intent(out) :: evt
        integer, intent(in), optional :: proc_id, event_id, run_id
        integer(c_int) :: pid, eid, rid
        pid = 0; if (present (proc_id)) pid = proc_id
        eid = 0; if (present (event_id)) eid = event_id
        rid = 0; if (present (run_id)) rid = run_id
        evt%obj = new_lcio_event (pid, eid, rid)
        evt%lccoll%obj = new_lccollection ()
    end subroutine lcio_event_init

```

Destructor.

```

<LCIO interface: interfaces>+≡
    interface
        subroutine lcio_event_delete (evt_obj) bind(C)
        import
        type(c_ptr), value :: evt_obj
        end subroutine lcio_event_delete
    end interface

```


Show event on screen.

```
<LCIO interface: interfaces>+≡
  interface
    subroutine dump_lcio_event (evt_obj) bind(C)
      import
        type(c_ptr), value :: evt_obj
      end subroutine dump_lcio_event
    end interface
<LCIO interface: public>+≡
  public :: show_lcio_event
<LCIO interface: procedures>+≡
  subroutine show_lcio_event (evt)
    type(lcio_event_t), intent(in) :: evt
    if (c_associated (evt%obj)) then
      call dump_lcio_event (evt%obj)
    else
      call msg_error ("LCIO event is not allocated.")
    end if
  end subroutine show_lcio_event
```

Put a single event to file.

```
<LCIO interface: interfaces>+≡
  interface
    subroutine lcio_event_to_file (evt_obj, filename) bind(C)
      import
        type(c_ptr), value :: evt_obj
        character(c_char), dimension(*), intent(in) :: filename
      end subroutine lcio_event_to_file
    end interface
<LCIO interface: public>+≡
  public :: write_lcio_event
<LCIO interface: procedures>+≡
  subroutine write_lcio_event (evt, filename)
    type(lcio_event_t), intent(in) :: evt
    type(string_t), intent(in) :: filename
    call lcio_event_to_file (evt%obj, char (filename) // c_null_char)
  end subroutine write_lcio_event

  <LCIO interface: public>+≡
    public :: lcio_event_final
  <LCIO interface: procedures>+≡
    subroutine lcio_event_final (evt)
      type(lcio_event_t), intent(inout) :: evt
      call lcio_event_delete (evt%obj)
    end subroutine lcio_event_final
```

```
<LCIO interface: interfaces>+≡
  interface
    subroutine lcio_set_alpha_qcd (evt_obj, alphas) bind(C)
      import
```

```

        type(c_ptr), value :: evt_obj
        real(c_double), value :: alphas
    end subroutine lcio_set_alpha_qcd
end interface
interface
    subroutine lcio_set_scale (evt_obj, scale) bind(C)
        import
        type(c_ptr), value :: evt_obj
        real(c_double), value :: scale
    end subroutine lcio_set_scale
end interface

<LCIO interface: public>+≡
    public :: lcio_event_set_alpha_qcd

<LCIO interface: procedures>+≡
    subroutine lcio_event_set_alpha_qcd (evt, alphas)
        type(lcio_event_t), intent(inout) :: evt
        real(default), intent(in) :: alphas
        call lcio_set_alpha_qcd (evt%obj, real (alphas, c_double))
    end subroutine lcio_event_set_alpha_qcd

<LCIO interface: public>+≡
    public :: lcio_event_set_scale

<LCIO interface: procedures>+≡
    subroutine lcio_event_set_scale (evt, scale)
        type(lcio_event_t), intent(inout) :: evt
        real(default), intent(in) :: scale
        call lcio_set_scale (evt%obj, real (scale, c_double))
    end subroutine lcio_event_set_scale

<LCIO interface: interfaces>+≡
    interface
        subroutine lcio_event_add_collection &
            (evt_obj, lccoll_obj) bind(C)
            import
            type(c_ptr), value :: evt_obj, lccoll_obj
        end subroutine lcio_event_add_collection
    end interface

<LCIO interface: public>+≡
    public :: lcio_event_add_coll

<LCIO interface: procedures>+≡
    subroutine lcio_event_add_coll (evt)
        type(lcio_event_t), intent(inout) :: evt
        call lcio_event_add_collection (evt%obj, &
            evt%lccoll%obj)
    end subroutine lcio_event_add_coll

```

17.9.4 LCIO Particle

Particle objects have the obvious meaning.

```

<LCIO interface: public>+≡

```

```

    public :: lcio_particle_t
<LCIO interface: types>+≡
    type :: lcio_particle_t
        private
        type(c_ptr) :: obj
    end type lcio_particle_t

```

Constructor.

```

<LCIO interface: interfaces>+≡
    interface
        type(c_ptr) function new_lcio_particle &
            (px, py, pz, pdg_id, mass, status) bind(C)
        import
        integer(c_int), value :: pdg_id, status
        real(c_double), value :: px, py, pz, mass
        end function new_lcio_particle
    end interface

<LCIO interface: interfaces>+≡
    interface
        subroutine add_particle_to_collection &
            (prt_obj, lccoll_obj) bind(C)
        import
        type(c_ptr), value :: prt_obj, lccoll_obj
        end subroutine add_particle_to_collection
    end interface

<LCIO interface: public>+≡
    public :: lcio_particle_add_to_evt_coll

<LCIO interface: procedures>+≡
    subroutine lcio_particle_add_to_evt_coll &
        (lprt, evt)
        type(lcio_particle_t), intent(in) :: lprt
        type(lcio_event_t), intent(inout) :: evt
        call add_particle_to_collection (lprt%obj, evt%lccoll%obj)
    end subroutine lcio_particle_add_to_evt_coll

```

```

<LCIO interface: public>+≡
    public :: lcio_particle_init

```

```

<LCIO interface: procedures>+≡
    subroutine lcio_particle_init (prt, p, pdg, status)
        type(lcio_particle_t), intent(out) :: prt
        type(vector4_t), intent(in) :: p
        real(default) :: mass
        real(default) :: px, py, pz
        integer, intent(in) :: pdg, status
        px = vector4_get_component (p, 1)
        py = vector4_get_component (p, 2)
        pz = vector4_get_component (p, 3)
        mass = p**1
        prt%obj = new_lcio_particle (real (px, c_double), real (py, c_double), &
            real (pz, c_double), int (pdg, c_int), &

```

```

        real (mass, c_double), int (status, c_int))
end subroutine lcio_particle_init

```

Set the particle color flow.

<LCIO interface: interfaces>+≡

```

interface
  subroutine lcio_set_color_flow (prt_obj, col1, col2) bind(C)
  import
  type(c_ptr), value :: prt_obj
  integer(c_int), value :: col1, col2
end subroutine lcio_set_color_flow
end interface

```

Set the particle color. Either from a color_t object or directly from a pair of integers.

<LCIO interface: interfaces>+≡

```

interface lcio_particle_set_color
  module procedure lcio_particle_set_color_col
  module procedure lcio_particle_set_color_int
end interface lcio_particle_set_color

```

<LCIO interface: public>+≡

```

public :: lcio_particle_set_color

```

<LCIO interface: procedures>+≡

```

subroutine lcio_particle_set_color_col (prt, col)
  type(lcio_particle_t), intent(inout) :: prt
  type(color_t), intent(in) :: col
  integer(c_int), dimension(2) :: c
  c(1) = col%get_col ()
  c(2) = col%get_acl ()
  if (c(1) /= 0 .or. c(2) /= 0) then
    call lcio_set_color_flow (prt%obj, c(1), c(2))
  end if
end subroutine lcio_particle_set_color_col

```

```

subroutine lcio_particle_set_color_int (prt, col)
  type(lcio_particle_t), intent(inout) :: prt
  integer, dimension(2), intent(in) :: col
  integer(c_int), dimension(2) :: c
  c = col
  if (c(1) /= 0 .or. c(2) /= 0) then
    call lcio_set_color_flow (prt%obj, c(1), c(2))
  end if
end subroutine lcio_particle_set_color_int

```

Return the particle color as a two-dimensional array (color, anticolor).

<LCIO interface: interfaces>+≡

```

interface
  integer(c_int) function lcio_particle_flow (prt_obj, col_index) bind(C)
  use iso_c_binding !NODEP!
  type(c_ptr), value :: prt_obj
  integer(c_int), value :: col_index
end function lcio_particle_flow
end interface

```

```

<LCIO interface: public>+≡
  public :: lcio_particle_get_flow

<LCIO interface: procedures>+≡
  function lcio_particle_get_flow (prt) result (col)
    integer, dimension(2) :: col
    type(lcio_particle_t), intent(in) :: prt
    col(1) = lcio_particle_flow (prt%obj, 0_c_int)
    col(2) = - lcio_particle_flow (prt%obj, 1_c_int)
  end function lcio_particle_get_flow

```

Return the four-momentum of a LCIO particle.

```

<LCIO interface: interfaces>+≡
  interface
    real(c_double) function lcio_three_momentum (prt_obj, p_index) bind(C)
      use iso_c_binding !NODEP!
      type(c_ptr), value :: prt_obj
      integer(c_int), value :: p_index
    end function lcio_three_momentum
  end interface

<LCIO interface: interfaces>+≡
  interface
    real(c_double) function lcio_energy (prt_obj) bind(C)
      import
      type(c_ptr), intent(in), value :: prt_obj
    end function lcio_energy
  end interface

<LCIO interface: public>+≡
  public :: lcio_particle_get_momentum

<LCIO interface: procedures>+≡
  function lcio_particle_get_momentum (prt) result (p)
    type(vector4_t) :: p
    type(lcio_particle_t), intent(in) :: prt
    real(default) :: E, px, py, pz
    E = lcio_energy (prt%obj)
    px = lcio_three_momentum (prt%obj, 0_c_int)
    py = lcio_three_momentum (prt%obj, 1_c_int)
    pz = lcio_three_momentum (prt%obj, 2_c_int)
    p = vector4_moving ( E, vector3_moving ([ px, py, pz ]))
  end function lcio_particle_get_momentum

```

Return the invariant mass squared of the particle object. LCIO stores the signed invariant mass (no squaring).

```

<LCIO interface: interfaces>+≡
  interface
    function lcio_mass (prt_obj) result (mass) bind(C)
      import
      real(c_double) :: mass
      type(c_ptr), value :: prt_obj
    end function lcio_mass
  end interface

```

```

<LCIO interface: public>+≡
    public :: lcio_particle_get_mass_squared

<LCIO interface: procedures>+≡
    function lcio_particle_get_mass_squared (prt) result (m2)
        real(default) :: m2
        type(lcio_particle_t), intent(in) :: prt
        real(default) :: m
        m = lcio_mass (prt%obj)
        m2 = sign (m**2, m)
    end function lcio_particle_get_mass_squared

```

Return vertex and production time of a LCIO particle.

```

<LCIO interface: interfaces>+≡
    interface
        real(c_double) function lcio_vtx_x (prt) bind(C)
            import
            type(c_ptr), value :: prt
        end function lcio_vtx_x
    end interface
    interface
        real(c_double) function lcio_vtx_y (prt) bind(C)
            import
            type(c_ptr), value :: prt
        end function lcio_vtx_y
    end interface
    interface
        real(c_double) function lcio_vtx_z (prt) bind(C)
            import
            type(c_ptr), value :: prt
        end function lcio_vtx_z
    end interface
    interface
        real(c_double) function lcio_prt_time (prt) bind(C)
            import
            type(c_ptr), value :: prt
        end function lcio_prt_time
    end interface

<LCIO interface: public>+≡
    public :: lcio_particle_get_vertex
    public :: lcio_particle_get_time

<LCIO interface: procedures>+≡
    function lcio_particle_get_vertex (prt) result (vtx)
        type(vector3_t) :: vtx
        type(lcio_particle_t), intent(in) :: prt
        real(default) :: vx, vy, vz
        vx = lcio_vtx_x (prt%obj)
        vy = lcio_vtx_y (prt%obj)
        vz = lcio_vtx_z (prt%obj)
        vtx = vector3_moving ([vx, vy, vz])
    end function lcio_particle_get_vertex

    function lcio_particle_get_time (prt) result (time)

```

```

    real(default) :: time
    type(lcio_particle_t), intent(in) :: prt
    time = lcio_prt_time (prt%obj)
end function lcio_particle_get_time

```

17.9.5 Polarization

For polarization there is a three-component float entry foreseen in the LCIO format. Completely generic density matrices can in principle be attached to events as float vectors added to `LCCollection` of the `LCEvent`. This is not yet implemented currently. Here, we restrict ourselves to the same implementation as in HepMC format: we use two entries as the polarization angles, while the first entry gives the degree of polarization (something not specified in the HepMC format). *For massive vector bosons, we arbitrarily choose the convention that the longitudinal (zero) helicity state is mapped to the theta angle $\pi/2$. This works under the condition that helicity is projected onto one of the basis states.*

```

<LCIO interface: interfaces>+≡
interface
    subroutine lcio_particle_set_spin (prt_obj, s1, s2, s3) bind(C)
        import
        type(c_ptr), value :: prt_obj
        real(c_double), value :: s1, s2, s3
    end subroutine lcio_particle_set_spin
end interface

<LCIO interface: public>+≡
public :: lcio_polarization_init

<LCIO interface: interfaces>+≡
interface lcio_polarization_init
    module procedure lcio_polarization_init_pol
    module procedure lcio_polarization_init_hel
    module procedure lcio_polarization_init_int
end interface

<LCIO interface: procedures>+≡
subroutine lcio_polarization_init_pol (prt, pol)
    type(lcio_particle_t), intent(out) :: prt
    type(polarization_t), intent(in) :: pol
    real(default) :: r, theta, phi
    if (polarization_is_polarized (pol)) then
        call polarization_to_angles (pol, r, theta, phi)
        call lcio_particle_set_spin (prt%obj, &
            real(r, c_double), real (theta, c_double), real (phi, c_double))
    end if
end subroutine lcio_polarization_init_pol

subroutine lcio_polarization_init_hel (prt, hel)
    type(lcio_particle_t), intent(out) :: prt
    type(helicity_t), intent(in) :: hel
    integer, dimension(2) :: h
    if (hel%is_defined ()) then
        h = hel%to_pair ()
    end if
end subroutine lcio_polarization_init_hel

```

```

        select case (h(1))
        case (1:)
            call lcio_particle_set_spin (prt%obj, 1._c_double, &
                0._c_double, 0._c_double)
        case (:-1)
            call lcio_particle_set_spin (prt%obj, 1._c_double, &
                real (pi, c_double), 0._c_double)
        case (0)
            call lcio_particle_set_spin (prt%obj, 1._c_double, &
                real (pi/2, c_double), 0._c_double)
        end select
    end if
end subroutine lcio_polarization_init_hel

subroutine lcio_polarization_init_int (prt, hel)
    type(lcio_particle_t), intent(out) :: prt
    integer, intent(in) :: hel
    select case (hel)
    case (1:)
        call lcio_particle_set_spin (prt%obj, 1._c_double, &
            0._c_double, 0._c_double)
    case (:-1)
        call lcio_particle_set_spin (prt%obj, 1._c_double, &
            real (pi, c_double), 0._c_double)
    case (0)
        call lcio_particle_set_spin (prt%obj, 1._c_double, &
            real (pi/2, c_double), 0._c_double)
    end select
end subroutine lcio_polarization_init_int

```

Recover polarization from LCIO particle (with the abovementioned deficiencies).

<LCIO interface: interfaces>+≡

```

interface
    function lcio_polarization_degree (prt_obj) result (degree) bind(C)
        import
        real(c_double) :: degree
        type(c_ptr), value :: prt_obj
    end function lcio_polarization_degree
end interface

interface
    function lcio_polarization_theta (prt_obj) result (theta) bind(C)
        import
        real(c_double) :: theta
        type(c_ptr), value :: prt_obj
    end function lcio_polarization_theta
end interface

interface
    function lcio_polarization_phi (prt_obj) result (phi) bind(C)
        import
        real(c_double) :: phi
        type(c_ptr), value :: prt_obj
    end function lcio_polarization_phi
end interface

```



```

<LCIO interface: public>+≡
    public :: lcio_particle_to_pol

<LCIO interface: procedures>+≡
    subroutine lcio_particle_to_pol (prt, flv, pol)
        type(lcio_particle_t), intent(in) :: prt
        type(flavor_t), intent(in) :: flv
        type(polarization_t), intent(out) :: pol
        real(default) :: degree, theta, phi
        degree = lcio_polarization_degree (prt%obj)
        theta = lcio_polarization_theta (prt%obj)
        phi = lcio_polarization_phi (prt%obj)
        call polarization_init_angles (pol, flv, degree, theta, phi)
    end subroutine lcio_particle_to_pol

```

Recover helicity. Here, ϕ and `degree` is ignored and only the sign of $\cos \theta$ is relevant, mapped to positive/negative helicity.

```

<LCIO interface: public>+≡
    public :: lcio_particle_to_hel

<LCIO interface: procedures>+≡
    subroutine lcio_particle_to_hel (prt, flv, hel)
        type(lcio_particle_t), intent(in) :: prt
        type(flavor_t), intent(in) :: flv
        type(helicity_t), intent(out) :: hel
        real(default) :: theta
        integer :: hmax
        theta = lcio_polarization_theta (prt%obj)
        hmax = flv%get_spin_type () / 2
        call hel%init (sign (hmax, nint (cos (theta))))
    end subroutine lcio_particle_to_hel

```

Set the vertex of a particle.

```

<LCIO interface: interfaces>+≡
    interface
        subroutine lcio_particle_set_vertex (prt_obj, vx, vy, vz) bind(C)
            import
            type(c_ptr), value :: prt_obj
            real(c_double), value :: vx, vy, vz
        end subroutine lcio_particle_set_vertex
    end interface
    interface
        subroutine lcio_particle_set_time (prt_obj, t) bind(C)
            import
            type(c_ptr), value :: prt_obj
            real(c_double), value :: t
        end subroutine lcio_particle_set_time
    end interface

<LCIO interface: public>+≡
    public :: lcio_particle_set_vtx

```

```

<LCIO interface: procedures>+≡
  subroutine lcio_particle_set_vtx (prt, vtx)
    type(lcio_particle_t), intent(inout) :: prt
    type(vector3_t), intent(in) :: vtx
    call lcio_particle_set_vertex (prt%obj, real(vtx%p(1), c_double), &
      real(vtx%p(2), c_double), real(vtx%p(3), c_double))
  end subroutine lcio_particle_set_vtx

<LCIO interface: public>+≡
  public :: lcio_particle_set_t

<LCIO interface: procedures>+≡
  subroutine lcio_particle_set_t (prt, t)
    type(lcio_particle_t), intent(out) :: prt
    real(default), intent(in) :: t
    call lcio_particle_set_time (prt%obj, real(t, c_double))
  end subroutine lcio_particle_set_t

<LCIO interface: interfaces>+≡
  interface
    subroutine lcio_particle_add_parent (prt_obj1, prt_obj2) bind(C)
      import
      type(c_ptr), value :: prt_obj1, prt_obj2
    end subroutine lcio_particle_add_parent
  end interface

<LCIO interface: public>+≡
  public :: lcio_particle_set_parent

<LCIO interface: procedures>+≡
  subroutine lcio_particle_set_parent (daughter, parent)
    type(lcio_particle_t), intent(inout) :: daughter, parent
    call lcio_particle_add_parent (daughter%obj, parent%obj)
  end subroutine lcio_particle_set_parent

<LCIO interface: interfaces>+≡
  interface
    integer(c_int) function lcio_particle_get_generator_status &
      (prt_obj) bind(C)
      import
      type(c_ptr), value :: prt_obj
    end function lcio_particle_get_generator_status
  end interface

<LCIO interface: public>+≡
  public :: lcio_particle_get_status

<LCIO interface: procedures>+≡
  function lcio_particle_get_status (lptr) result (status)
    integer :: status
    type(lcio_particle_t), intent(in) :: lptr
    status = lcio_particle_get_generator_status (lptr%obj)
  end function lcio_particle_get_status

```

Getting the PDG code.

```
<LCIO interface: interfaces>+≡  
  interface  
    integer(c_int) function lcio_particle_get_pdg_code (prt_obj) bind(C)  
    import  
    type(c_ptr), value :: prt_obj  
    end function lcio_particle_get_pdg_code  
  end interface  
  
<LCIO interface: public>+≡  
  public :: lcio_particle_get_pdg  
  
<LCIO interface: procedures>+≡  
  function lcio_particle_get_pdg (lptr) result (pdg)  
    integer :: pdg  
    type(lcio_particle_t), intent(in) :: lptr  
    pdg = lcio_particle_get_pdg_code (lptr%obj)  
  end function lcio_particle_get_pdg
```

Obtaining the number of parents and daughters of an LCIO particle.

```
<LCIO interface: interfaces>+≡  
  interface  
    integer(c_int) function lcio_n_parents (prt_obj) bind(C)  
    import  
    type(c_ptr), value :: prt_obj  
    end function lcio_n_parents  
  end interface  
  
<LCIO interface: interfaces>+≡  
  interface  
    integer(c_int) function lcio_n_daughters (prt_obj) bind(C)  
    import  
    type(c_ptr), value :: prt_obj  
    end function lcio_n_daughters  
  end interface  
  
<LCIO interface: public>+≡  
  public :: lcio_particle_get_n_parents  
  
<LCIO interface: procedures>+≡  
  function lcio_particle_get_n_parents (lptr) result (n_parents)  
    integer :: n_parents  
    type(lcio_particle_t), intent(in) :: lptr  
    n_parents = lcio_n_parents (lptr%obj)  
  end function lcio_particle_get_n_parents  
  
  
<LCIO interface: public>+≡  
  public :: lcio_particle_get_n_children  
  
<LCIO interface: procedures>+≡  
  function lcio_particle_get_n_children (lptr) result (n_children)  
    integer :: n_children  
    type(lcio_particle_t), intent(in) :: lptr  
    n_children = lcio_n_daughters (lptr%obj)  
  end function lcio_particle_get_n_children
```

This provides access from the LCIO event `lcio_event_t` to the array entries of the parent and daughter arrays of the LCIO particles.

<LCIO interface: interfaces>+≡

```
interface
  integer(c_int) function lcio_event_parent_k &
    (evt_obj, num_part, k_parent) bind (C)
  use iso_c_binding !NODEP!
  type(c_ptr), value :: evt_obj
  integer(c_int), value :: num_part, k_parent
end function lcio_event_parent_k
end interface
```

<LCIO interface: interfaces>+≡

```
interface
  integer(c_int) function lcio_event_daughter_k &
    (evt_obj, num_part, k_daughter) bind (C)
  use iso_c_binding !NODEP!
  type(c_ptr), value :: evt_obj
  integer(c_int), value :: num_part, k_daughter
end function lcio_event_daughter_k
end interface
```

<LCIO interface: public>+≡

```
public :: lcio_get_n_parents
```

<LCIO interface: procedures>+≡

```
function lcio_get_n_parents (evt, num_part, k_parent) result (index_parent)
  type(lcio_event_t), intent(in) :: evt
  integer, intent(in) :: num_part, k_parent
  integer :: index_parent
  index_parent = lcio_event_parent_k (evt%obj, int (num_part, c_int), &
    int (k_parent, c_int))
end function lcio_get_n_parents
```

<LCIO interface: public>+≡

```
public :: lcio_get_n_children
```

<LCIO interface: procedures>+≡

```
function lcio_get_n_children (evt, num_part, k_daughter) result (index_daughter)
  type(lcio_event_t), intent(in) :: evt
  integer, intent(in) :: num_part, k_daughter
  integer :: index_daughter
  index_daughter = lcio_event_daughter_k (evt%obj, int (num_part, c_int), &
    int (k_daughter, c_int))
end function lcio_get_n_children
```

17.9.6 LCIO Writer type

There is a specific LCIO Writer type for handling the output of `LCEventImpl` objects (i.e., Monte Carlo event samples) to file. Opening the file is done by the constructor, closing by the destructor.

<LCIO interface: public>+≡

```
public :: lcio_writer_t
```

```

<LCIO interface: types>+≡
  type :: lcio_writer_t
  private
  type(c_ptr) :: obj
end type lcio_writer_t

```

Constructor for an output associated to a file.

```

<LCIO interface: interfaces>+≡
  interface
    type(c_ptr) function open_lcio_writer_new (filename, complevel) bind(C)
    import
    character(c_char), dimension(*), intent(in) :: filename
    integer(c_int), intent(in) :: complevel
  end function open_lcio_writer_new
  end interface

<LCIO interface: public>+≡
  public :: lcio_writer_open_out

<LCIO interface: procedures>+≡
  subroutine lcio_writer_open_out (lcio_writer, filename)
    type(lcio_writer_t), intent(out) :: lcio_writer
    type(string_t), intent(in) :: filename
    lcio_writer%obj = open_lcio_writer_new (char (filename) // &
      c_null_char, 9_c_int)
  end subroutine lcio_writer_open_out

```

Destructor:

```

<LCIO interface: interfaces>+≡
  interface
    subroutine lcio_writer_delete (io_obj) bind(C)
    import
    type(c_ptr), value :: io_obj
  end subroutine lcio_writer_delete
  end interface

<LCIO interface: public>+≡
  public :: lcio_writer_close

<LCIO interface: procedures>+≡
  subroutine lcio_writer_close (lciowriter)
    type(lcio_writer_t), intent(inout) :: lciowriter
    call lcio_writer_delete (lciowriter%obj)
  end subroutine lcio_writer_close

```

Write a single event to the LCIO writer.

```

<LCIO interface: interfaces>+≡
  interface
    subroutine lcio_write_event (io_obj, evt_obj) bind(C)
    import
    type(c_ptr), value :: io_obj, evt_obj
  end subroutine lcio_write_event
  end interface

```

```

<LCIO interface: public>+≡
  public :: lcio_event_write

<LCIO interface: procedures>+≡
  subroutine lcio_event_write (wrt, evt)
    type(lcio_writer_t), intent(inout) :: wrt
    type(lcio_event_t), intent(in) :: evt
    call lcio_write_event (wrt%obj, evt%obj)
  end subroutine lcio_event_write

```

17.9.7 LCIO Reader type

There is a specific LCIO Reader type for handling the input of LCEventImpl objects (i.e., Monte Carlo event samples) from file. Opening the file is done by the constructor, closing by the destructor.

```

<LCIO interface: public>+≡
  public :: lcio_reader_t

<LCIO interface: types>+≡
  type :: lcio_reader_t
  private
  type(c_ptr) :: obj
end type lcio_reader_t

```

Constructor for an output associated to a file.

```

<LCIO interface: interfaces>+≡
  interface
    type(c_ptr) function open_lcio_reader (filename) bind(C)
    import
    character(c_char), dimension(*), intent(in) :: filename
    end function open_lcio_reader
  end interface

<LCIO interface: public>+≡
  public :: lcio_open_file

<LCIO interface: procedures>+≡
  subroutine lcio_open_file (lcio_reader, filename)
    type(lcio_reader_t), intent(out) :: lcio_reader
    type(string_t), intent(in) :: filename
    lcio_reader%obj = open_lcio_reader (char (filename) // c_null_char)
  end subroutine lcio_open_file

```

Destructor:

```

<LCIO interface: interfaces>+≡
  interface
    subroutine lcio_reader_delete (io_obj) bind(C)
    import
    type(c_ptr), value :: io_obj
    end subroutine lcio_reader_delete
  end interface

<LCIO interface: public>+≡
  public :: lcio_reader_close

```

```

<LCIO interface: procedures>+≡
  subroutine lcio_reader_close (lcioreader)
    type(lcio_reader_t), intent(inout) :: lcioreader
    call lcio_reader_delete (lcioreader%obj)
  end subroutine lcio_reader_close

```

Read a single event from the event file. Return true if successful.

```

<LCIO interface: interfaces>+≡
  interface
    type(c_ptr) function read_lcio_event (io_obj) bind(C)
    import
    type(c_ptr), value :: io_obj
  end function read_lcio_event
end interface

```

```

<LCIO interface: public>+≡
  public :: lcio_read_event

```

```

<LCIO interface: procedures>+≡
  subroutine lcio_read_event (lcrdr, evt, ok)
    type(lcio_reader_t), intent(inout) :: lcrdr
    type(lcio_event_t), intent(out) :: evt
    logical, intent(out) :: ok
    evt%obj = read_lcio_event (lcrdr%obj)
    ok = c_associated (evt%obj)
  end subroutine lcio_read_event

```

Extract the process ID. This is stored (at the moment abusively) in the RUN ID as well as in an additional event parameter.

```

<LCIO interface: interfaces>+≡
  interface
    integer(c_int) function lcio_event_signal_process_id (evt_obj) bind(C)
    import
    type(c_ptr), value :: evt_obj
  end function lcio_event_signal_process_id
end interface

```

```

<LCIO interface: public>+≡
  public :: lcio_event_get_process_id

```

```

<LCIO interface: procedures>+≡
  function lcio_event_get_process_id (evt) result (i_proc)
    integer :: i_proc
    type(lcio_event_t), intent(in) :: evt
    i_proc = lcio_event_signal_process_id (evt%obj)
  end function lcio_event_get_process_id

```

Number of particles in an LCIO event.

```

<LCIO interface: interfaces>+≡
  interface
    integer(c_int) function lcio_event_get_n_particles (evt_obj) bind(C)
    import
    type(c_ptr), value :: evt_obj
  end function lcio_event_get_n_particles
end interface

```

```

<LCIO interface:>≡
<LCIO interface: public>+≡
    public :: lcio_event_get_n_tot
<LCIO interface: procedures>+≡
    function lcio_event_get_n_tot (evt) result (n_tot)
        integer :: n_tot
        type(lcio_event_t), intent(in) :: evt
        n_tot = lcio_event_get_n_particles (evt%obj)
    end function lcio_event_get_n_tot

```

Extracting α_s and the scale.

```

<LCIO interface: interfaces>+≡
    interface
        function lcio_event_get_alpha_qcd (evt_obj) result (as) bind(C)
            import
            real(c_double) :: as
            type(c_ptr), value :: evt_obj
        end function lcio_event_get_alpha_qcd
    end interface
    interface
        function lcio_event_get_scale (evt_obj) result (scale) bind(C)
            import
            real(c_double) :: scale
            type(c_ptr), value :: evt_obj
        end function lcio_event_get_scale
    end interface
<LCIO interface: public>+≡
    public :: lcio_event_get_alphas
<LCIO interface: procedures>+≡
    function lcio_event_get_alphas (evt) result (as)
        type(lcio_event_t), intent(in) :: evt
        real(default) :: as
        as = lcio_event_get_alpha_qcd (evt%obj)
    end function lcio_event_get_alphas

```

```

<LCIO interface: public>+≡
    public :: lcio_event_get_scaleval
<LCIO interface: procedures>+≡
    function lcio_event_get_scaleval (evt) result (scale)
        type(lcio_event_t), intent(in) :: evt
        real(default) :: scale
        scale = lcio_event_get_scale (evt%obj)
    end function lcio_event_get_scaleval

```

Extracting particles by index from an LCIO event.

```

<LCIO interface: interfaces>+≡
    interface
        type(c_ptr) function lcio_event_particle_k (evt_obj, k) bind(C)
        import

```



```

        type(c_ptr), value :: evt_obj
        integer(c_int), value :: k
    end function lcio_event_particle_k
end interface

<LCIO interface: public>+=
    public :: lcio_event_get_particle

<LCIO interface: procedures>+=
    function lcio_event_get_particle (evt, n) result (prt)
        type(lcio_event_t), intent(in) :: evt
        integer, intent(in) :: n
        type(lcio_particle_t) :: prt
        prt%obj = lcio_event_particle_k (evt%obj, int (n, c_int))
    end function lcio_event_get_particle

```

17.9.8 Unit tests

This test example is an abridged version from the build-from-scratch example in the HepMC distribution, translated to LCIO. There are three different branchings for $p \rightarrow q$ PDF splitting, then a branching for a $qq \rightarrow W^-g$ hard-interaction process, and finally a branching for $W^- \rightarrow qq$ decay. The setup is for LHC kinematics.

Extending the original example, we set color flow for the incoming quarks and polarization for the outgoing photon. For the latter, we have to define a particle-data object for the photon, so a flavor object can be correctly initialized.

```

<LCIO interface: public>+=
    public :: lcio_test

<LCIO interface: procedures>+=
    subroutine lcio_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <LCIO interface: execute tests>
    end subroutine lcio_test

<LCIO interface: execute tests>=
    call test (lcio_interface_1, "lcio_interface_1", &
        "check LCIO interface", &
        u, results)

<LCIO interface: tests>=
    subroutine lcio_interface_1 (u)
        use physics_defs, only: VECTOR
        use model_data, only: field_data_t
        integer, intent(in) :: u
        integer :: u_file, iostat
        type(lcio_event_t) :: evt
        type(lcio_particle_t) :: prt1, prt2, prt3, prt4, prt5, prt6, prt7, prt8
        type(flavor_t) :: flv
        type(color_t) :: col
        type(polarization_t) :: pol
        type(field_data_t), target :: photon_data
        character(220) :: buffer
    end subroutine lcio_interface_1

```

```

write (u, "(A)")  "* Test output: LCIO interface"
write (u, "(A)")  "* Purpose: test LCIO interface"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

! Initialize a photon flavor object and some polarization
call photon_data%init (var_str ("PHOTON"), 22)
call photon_data%set (spin_type=VECTOR)
call photon_data%freeze ()
call flv%init (photon_data)
call polarization_init_angles &
      (pol, flv, 0.6_default, 1._default, 0.5_default)

! Event initialization
call lcio_event_init (evt, 20, 1, 42)

write (u, "(A)")  "* p -> q splitting"
write (u, "(A)")

! $p\to q$ splittings
call particle_init (prt1, &
      0._default, 0._default, 7000._default, 7000._default, &
      2212, 3)
call particle_init (prt2, &
      0._default, 0._default, -7000._default, 7000._default, &
      2212, 3)
call particle_init (prt3, &
      .750_default, -1.569_default, 32.191_default, 32.238_default, &
      1, 3)
call color_init_from_array (col, [501])
call lcio_particle_set_color (prt3, col)
call lcio_particle_set_parent (prt3, prt1)
call lcio_particle_set_parent (prt3, prt2)
call particle_init (prt4, &
      -3.047_default, -19._default, -54.629_default, 57.920_default, &
      -2, 3)
call color_init_from_array (col, [-501])
call lcio_particle_set_color (prt4, col)
call lcio_particle_set_parent (prt4, prt1)
call lcio_particle_set_parent (prt4, prt2)

write (u, "(A)")  "* Hard interaction"
write (u, "(A)")

! Hard interaction
call particle_init (prt6, &
      -3.813_default, 0.113_default, -1.833_default, 4.233_default, &
      22, 1)
call lcio_polarization_init (prt6, pol)
call particle_init (prt5, &
      1.517_default, -20.68_default, -20.605_default, 85.925_default, &

```

```

-24, 3)
call lcio_particle_set_parent (prt5, prt3)
call lcio_particle_set_parent (prt5, prt4)
call lcio_particle_set_parent (prt6, prt3)
call lcio_particle_set_parent (prt6, prt4)

! $W~-$ decay
call particle_init (prt7, &
-2.445_default, 28.816_default, 6.082_default, 29.552_default, &
1, 1)
call particle_init (prt8, &
3.962_default, -49.498_default, -26.687_default, 56.373_default, &
-2, 1)
call lcio_particle_set_t (prt7, 0.12_default)
call lcio_particle_set_t (prt8, 0.12_default)
call lcio_particle_set_vtx &
(prt7, vector3_moving ([-0.3_default, 0.05_default, 0.004_default]))
call lcio_particle_set_vtx &
(prt8, vector3_moving ([-0.3_default, 0.05_default, 0.004_default]))
call lcio_particle_set_parent (prt7, prt5)
call lcio_particle_set_parent (prt8, prt5)
call lcio_particle_add_to_evt_coll (prt1, evt)
call lcio_particle_add_to_evt_coll (prt2, evt)
call lcio_particle_add_to_evt_coll (prt3, evt)
call lcio_particle_add_to_evt_coll (prt4, evt)
call lcio_particle_add_to_evt_coll (prt5, evt)
call lcio_particle_add_to_evt_coll (prt6, evt)
call lcio_particle_add_to_evt_coll (prt7, evt)
call lcio_particle_add_to_evt_coll (prt8, evt)
call lcio_event_add_coll (evt)

! Event output
write (u, "(A)") "Writing in ASCII form to file 'lcio_test.slcio'"
write (u, "(A)")

call write_lcio_event (evt, var_str ("lcio_test.slcio"))

write (u, "(A)") "Writing completed"

write (u, "(A)")
write (u, "(A)") "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = "lcio_test.slcio", &
action = "read", status = "old")
do
read (u_file, "(A)", iostat = iostat) buffer
if (trim (buffer) == "") cycle
if (buffer(1:12) == " - timestamp") buffer = "[...]"
if (buffer(1:6) == " date:") buffer = "[...]"
if (iostat /= 0) exit
write (u, "(A)") trim (buffer)
end do

```

```

close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"
write (u, "(A)")

! Wrapup
call polarization_final (pol)
call lcio_event_final (evt)

write (u, "(A)")
write (u, "(A)")  "* Test output end: lcio_interface_1"

contains

subroutine particle_init &
    (prt, px, py, pz, E, pdg, status)
    type(lcio_particle_t), intent(out) :: prt
    real(default), intent(in) :: px, py, pz, E
    integer, intent(in) :: pdg, status
    type(vector4_t) :: p
    p = vector4_moving (E, vector3_moving ([px, py, pz]))
    call lcio_particle_init (prt, p, pdg, status)
end subroutine particle_init

end subroutine lcio_interface_1

```

17.10 HEP Common and Events

This is a separate module that manages data exchange between the common blocks and `event_t` objects. We separate this from the previous module in order to avoid a circular module dependency. It also contains the functions necessary for communication between `hepmc_event_t` and `event_t` or `lcio_event_t` and `event_t` as well as `particle_set_t` and `particle_t` objects.

(`hep_events.f90`)≡
⟨File header⟩

```

module hep_events

    use kinds
    use io_units
    ⟨Use strings⟩
    use diagnostics
    use lorentz
    use unit_tests

    use flavors
    use colors
    use helicities
    use quantum_numbers
    use interactions

```

```

use state_matrices
use evaluators
use polarizations
use model_data
use subevents
use particles
use hep_common
use hepmc_interface
use lcio_interface
use event_base

```

⟨Standard module head⟩

⟨HEP events: public⟩

contains

⟨HEP events: procedures⟩

⟨HEP events: tests⟩

end module hep_events

17.10.1 Data Transfer: events

Fill the HEPEUP block, given a WHIZARD event object.

⟨HEP events: public⟩≡

```
public :: hepeup_from_event
```

⟨HEP events: procedures⟩≡

```

subroutine hepeup_from_event &
    (event, keep_beams, keep_remnants, process_index)
    class(generic_event_t), intent(in), target :: event
    logical, intent(in), optional :: keep_beams
    logical, intent(in), optional :: keep_remnants
    integer, intent(in), optional :: process_index
    type(particle_set_t), pointer :: particle_set
    real(default) :: scale, alpha_qcd
    if (event%has_valid_particle_set ()) then
        particle_set => event%get_particle_set_ptr ()
        call hepeup_from_particle_set (particle_set, keep_beams, keep_remnants)
        if (present (process_index)) &
            call hepeup_set_event_parameters (proc_id = process_index)
        scale = event%get_fac_scale ()
        if (scale /= 0) &
            call hepeup_set_event_parameters (scale = scale)
        alpha_qcd = event%get_alpha_s ()
        if (alpha_qcd /= 0) &
            call hepeup_set_event_parameters (alpha_qcd = alpha_qcd)
        if (event%weight_prc_is_known ()) then
            call hepeup_set_event_parameters (weight = event%get_weight_prc ())
        else
            call msg_bug ("HEPEUP: process weight is unknown")
        end if
    end if
end subroutine

```

```

    else
      call msg_bug ("HEPEUP: event incomplete")
    end if
  end subroutine hepeup_from_event

```

Reverse.

Note: The current implementation sets the particle set of the hard process and is therefore not useful if the event on file is dressed. This should be reconsidered.

Note: setting of scale or alpha is not yet supported by the `event_t` object. Ticket #628.

```

<HEP events: public>+≡
  public :: hepeup_to_event

<HEP events: procedures>+≡
  subroutine hepeup_to_event &
    (event, fallback_model, process_index, recover_beams, &
     use_alpha_s, use_scale)
    class(generic_event_t), intent(inout), target :: event
    class(model_data_t), intent(in), target :: fallback_model
    integer, intent(out), optional :: process_index
    logical, intent(in), optional :: recover_beams
    logical, intent(in), optional :: use_alpha_s
    logical, intent(in), optional :: use_scale
    class(model_data_t), pointer :: model
    real(default) :: weight, scale, alpha_qcd
    type(particle_set_t) :: particle_set
    model => event%get_model_ptr ()
    call hepeup_to_particle_set &
      (particle_set, recover_beams, model, fallback_model)
    call event%set_hard_particle_set (particle_set)
    call particle_set%final ()
    if (present (process_index)) then
      call hepeup_get_event_parameters (proc_id = process_index)
    end if
    call hepeup_get_event_parameters (weight = weight, &
      scale = scale, alpha_qcd = alpha_qcd)
    call event%set_weight_ref (weight)
    if (present (use_alpha_s)) then
      if (use_alpha_s.and. alpha_qcd > 0) &
        call event%set_alpha_qcd_forced (alpha_qcd)
    end if
    if (present (use_scale)) then
      if (use_scale .and. scale > 0) &
        call event%set_scale_forced (scale)
    end if
  end subroutine hepeup_to_event

```

Fill the HEPEVT (event) common block:

```

<HEP events: public>+≡
  public :: hepevt_from_event

```

(HEP events: procedures)+≡

```

subroutine hepevt_from_event (event, i_evt, keep_beams, keep_remnants)
  class(generic_event_t), intent(in), target :: event
  integer, intent(in), optional :: i_evt
  logical, intent(in), optional :: keep_beams
  logical, intent(in), optional :: keep_remnants
  type(particle_set_t), pointer :: particle_set
  if (event%has_valid_particle_set ()) then
    particle_set => event%get_particle_set_ptr ()
    call hepevt_from_particle_set (particle_set, keep_beams, keep_remnants)
    if (event%weight_prc_is_known () .and. event%sqme_prc_is_known ()) then
      call hepevt_set_event_parameters ( &
        weight = event%get_weight_prc (), &
        function_value = event%get_sqme_prc ())
    else
      call msg_bug ("HEPEVT: event weight and/or sqme unknown")
    end if
    if (present (i_evt)) &
      call hepevt_set_event_parameters (i_evt = i_evt)
  else
    call msg_bug ("HEPEVT: event incomplete")
  end if
end subroutine hepevt_from_event

```

HepMC format

The master output function fills a HepMC GenEvent object that is already initialized, but has no vertices in it.

We first set up the vertex lists and enter the vertices into the HepMC event. Then, we assign first all incoming particles and then all outgoing particles to their associated vertices. Particles which have neither parent nor children entries (this should not happen) are dropped.

Finally, we insert the beam particles. If there are none, use the incoming particles instead. Transform a particle into a `hepmc_particle` object, including color and polarization. The HepMC status is equivalent to the HEPEVT status, in particular: 0 = null entry, 1 = physical particle, 2 = decayed/fragmented SM hadron, tau or muon, 3 = other unphysical particle entry, 4 = incoming particles, 11 = intermediate resonance such as squarks. The use of 11 for intermediate resonances is as done by HERWIG, see <http://herwig.hepforge.org/trac/wiki/FaQs>.

(HEP events: procedures)+≡

```

subroutine particle_to_hepmc (prt, hprt)
  type(particle_t), intent(in) :: prt
  type(hepmc_particle_t), intent(out) :: hprt
  integer :: hepmc_status
  select case (prt%get_status ())
  case (PRT_UNDEFINED)
    hepmc_status = 0
  case (PRT_OUTGOING)
    hepmc_status = 1
  case (PRT_BEAM)
    hepmc_status = 4

```

```

case (PRT_RESONANT)
  if (abs(prt%get_pdg()) == 13 .or. &
      abs(prt%get_pdg()) == 15) then
    hepmc_status = 2
  else
    hepmc_status = 11
  end if
case default
  hepmc_status = 3
end select
call hepmc_particle_init (hprrt, &
  prt%get_momentum (), prt%get_pdg (), &
  hepmc_status)
call hepmc_particle_set_color (hprrt, prt%get_color ())
select case (prt%get_polarization_status ())
case (PRT_DEFINITE_HELICITY)
  call hepmc_particle_set_polarization (hprrt, &
    prt%get_helicity ())
case (PRT_GENERIC_POLARIZATION)
  call hepmc_particle_set_polarization (hprrt, &
    prt%get_polarization ())
end select
end subroutine particle_to_hepmc

```

(HEP events: public)+≡

```
public :: hepmc_event_from_particle_set
```

(HEP events: procedures)+≡

```

subroutine hepmc_event_from_particle_set (evt, particle_set)
  type(hepmc_event_t), intent(inout) :: evt
  type(particle_set_t), intent(in) :: particle_set
  type(hepmc_vertex_t), dimension(:), allocatable :: v
  type(hepmc_particle_t), dimension(:), allocatable :: hprrt
  type(hepmc_particle_t), dimension(2) :: hbeam
  type(vector4_t), dimension(:), allocatable :: vtx
  logical, dimension(:), allocatable :: is_beam
  integer, dimension(:), allocatable :: v_from, v_to
  integer :: n_vertices, n_tot, i
  n_tot = particle_set%get_n_tot ()
  allocate (v_from (n_tot), v_to (n_tot))
  call particle_set%assign_vertices (v_from, v_to, n_vertices)
  allocate (hprrt (n_tot))
  allocate (vtx (n_vertices))
  vtx = vector4_null
  do i = 1, n_tot
    if (v_to(i) /= 0 .or. v_from(i) /= 0) then
      call particle_to_hepmc (particle_set%prt(i), hprrt(i))
      if (v_to(i) /= 0) then
        vtx(v_to(i)) = particle_set%prt(i)%get_vertex ()
      end if
    end if
  end do
  allocate (v (n_vertices))
  do i = 1, n_vertices

```



```

        call hepmc_vertex_init (v(i), vtx(i))
        call hepmc_event_add_vertex (evt, v(i))
    end do
    allocate (is_beam (n_tot))
    is_beam = particle_set%prt(1:n_tot)%get_status () == PRT_BEAM
    if (.not. any (is_beam)) then
        is_beam = particle_set%prt(1:n_tot)%get_status () == PRT_INCOMING
    end if
    if (count (is_beam) == 2) then
        hbeam = pack (hprt, is_beam)
        call hepmc_event_set_beam_particles (evt, hbeam(1), hbeam(2))
    end if
    do i = 1, n_tot
        if (v_to(i) /= 0) then
            call hepmc_vertex_add_particle_in (v(v_to(i)), hprt(i))
        end if
    end do
    do i = 1, n_tot
        if (v_from(i) /= 0) then
            call hepmc_vertex_add_particle_out (v(v_from(i)), hprt(i))
        end if
    end do
    FIND_SIGNAL_PROCESS: do i = 1, n_tot
        if (particle_set%prt(i)%get_status () == PRT_INCOMING) then
            call hepmc_event_set_signal_process_vertex (evt, v(v_to(i)))
            exit FIND_SIGNAL_PROCESS
        end if
    end do FIND_SIGNAL_PROCESS
end subroutine hepmc_event_from_particle_set

```

Initialize a particle from a HepMC particle object. The model is necessary for making a fully qualified flavor component. We have the additional flag **polarized** which tells whether the polarization information should be interpreted or ignored, and the lookup array of barcodes. Note that the lookup array is searched linearly, a possible bottleneck for large particle arrays. If necessary, the barcode array could be replaced by a hash table.

(HEP events: procedures)+≡

```

subroutine particle_from_hepmc_particle &
    (prt, hprt, model, polarization, barcode)
    type(particle_t), intent(out) :: prt
    type(hepmc_particle_t), intent(in) :: hprt
    type(model_data_t), intent(in), target :: model
    type(hepmc_vertex_t) :: vtx
    integer, intent(in) :: polarization
    integer, dimension(:), intent(in) :: barcode
    type(hepmc_polarization_t) :: hpol
    type(flavor_t) :: flv
    type(color_t) :: col
    type(helicity_t) :: hel
    type(polarization_t) :: pol
    type(vector4_t) :: vertex
    integer :: n_parents, n_children
    integer, dimension(:), allocatable :: &

```

```

        parent_barcode, child_barcode, parent, child
integer :: i
select case (hepmc_particle_get_status (hpvt))
case (1); call prt%set_status (PRT_OUTGOING)
case (2); call prt%set_status (PRT_RESONANT)
case (3); call prt%set_status (PRT_VIRTUAL)
end select
if (hepmc_particle_is_beam (hpvt)) call prt%set_status (PRT_BEAM)
call flv%init (hepmc_particle_get_pdg (hpvt), model)
call col%init (hepmc_particle_get_color (hpvt))
call prt%set_flavor (flv)
call prt%set_color (col)
call prt%set_polarization (polarization)
select case (polarization)
case (PRT_DEFINITE_HELICITY)
    hpol = hepmc_particle_get_polarization (hpvt)
    call hepmc_polarization_to_hel (hpol, prt%get_flv (), hel)
    call prt%set_helicity (hel)
    call hepmc_polarization_final (hpol)
case (PRT_GENERIC_POLARIZATION)
    hpol = hepmc_particle_get_polarization (hpvt)
    call hepmc_polarization_to_pol (hpol, prt%get_flv (), pol)
    call prt%set_pol (pol)
    call hepmc_polarization_final (hpol)
end select
call prt%set_momentum (hepmc_particle_get_momentum (hpvt), &
    hepmc_particle_get_mass_squared (hpvt))
n_parents = hepmc_particle_get_n_parents (hpvt)
n_children = hepmc_particle_get_n_children (hpvt)
allocate (parent_barcode (n_parents), parent (n_parents))
allocate (child_barcode (n_children), child (n_children))
parent_barcode = hepmc_particle_get_parent_barcodes (hpvt)
child_barcode = hepmc_particle_get_child_barcodes (hpvt)
do i = 1, size (barcode)
    where (parent_barcode == barcode(i)) parent = i
    where (child_barcode == barcode(i)) child = i
end do
call prt%set_parents (parent)
call prt%set_children (child)
if (prt%get_status () == PRT_VIRTUAL .and. n_parents == 0) &
    call prt%set_status (PRT_INCOMING)
vtx = hepmc_particle_get_decay_vertex (hpvt)
if (hepmc_vertex_is_valid (vtx)) then
    vertex = hepmc_vertex_to_vertex (vtx)
    if (vertex /= vector4_null) call prt%set_vertex (vertex)
end if
end subroutine particle_from_hepmc_particle

```

If a particle set is initialized from a HepMC event record, we have to specify the treatment of polarization (unpolarized or density matrix) which is common to all particles. Correlated polarization information is not available.

There is some complication in reconstructing incoming particles and beam remnants. First of all, they all will be tagged as virtual. We then define an

incoming particle as

(*HEP events: procedures*) +=

```
subroutine hepmc_event_to_particle_set &
  (particle_set, evt, model, fallback_model, polarization)
  type(particle_set_t), intent(inout), target :: particle_set
  type(hepmc_event_t), intent(in) :: evt
  class(model_data_t), intent(in), target :: model, fallback_model
  integer, intent(in) :: polarization
  type(hepmc_event_particle_iterator_t) :: it
  type(hepmc_vertex_t) :: v
  type(hepmc_vertex_particle_in_iterator_t) :: v_it
  type(hepmc_particle_t) :: prt
  integer, dimension(:), allocatable :: barcode
  integer :: n_tot, i, j, bc
  logical :: has_parents, has_children
  n_tot = 0
  call hepmc_event_particle_iterator_init (it, evt)
  do while (hepmc_event_particle_iterator_is_valid (it))
    n_tot = n_tot + 1
    call hepmc_event_particle_iterator_advance (it)
  end do
  allocate (barcode (n_tot))
  call hepmc_event_particle_iterator_reset (it)
  do i = 1, n_tot
    barcode(i) = hepmc_particle_get_barcode &
      (hepmc_event_particle_iterator_get (it))
    call hepmc_event_particle_iterator_advance (it)
  end do
  allocate (particle_set%prt (n_tot))
  call hepmc_event_particle_iterator_reset (it)
  do i = 1, n_tot
    prt = hepmc_event_particle_iterator_get (it)
    call particle_from_hepmc_particle (particle_set%prt(i), &
      prt, model, polarization, barcode)
    call hepmc_event_particle_iterator_advance (it)
  end do
  call hepmc_event_particle_iterator_final (it)
  v = hepmc_event_get_signal_process_vertex (evt)
  if (hepmc_vertex_is_valid (v)) then
    call hepmc_vertex_particle_in_iterator_init (v_it, v)
    do while (hepmc_vertex_particle_in_iterator_is_valid (v_it))
      prt = hepmc_vertex_particle_in_iterator_get (v_it)
      bc = hepmc_particle_get_barcode &
        (hepmc_vertex_particle_in_iterator_get (v_it))
      do i = 1, size(barcode)
        if (bc == barcode(i)) &
          call particle_set%prt(i)%set_status (PRT_INCOMING)
        end do
      call hepmc_vertex_particle_in_iterator_advance (v_it)
    end do
    call hepmc_vertex_particle_in_iterator_final (v_it)
  end if
  do i = 1, n_tot
    if (particle_set%prt(i)%get_status () == PRT_VIRTUAL &
```

```

        .and. particle_set%prt(i)%get_n_children () == 0) &
        call particle_set%prt(i)%set_status (PRT_OUTGOING)
    end do
    particle_set%n_tot = n_tot
    particle_set%n_beam = &
        count (particle_set%prt%get_status () == PRT_BEAM)
    particle_set%n_in = &
        count (particle_set%prt%get_status () == PRT_INCOMING)
    particle_set%n_out = &
        count (particle_set%prt%get_status () == PRT_OUTGOING)
    particle_set%n_vir = &
        particle_set%n_tot - particle_set%n_in - particle_set%n_out
end subroutine hepmc_event_to_particle_set

```

Fill a WHIZARD event from a HepMC event record. Recall that HepMC events are always unweighted, so the weight is unity.

```

<HEP events: public>+≡
    public :: hepmc_to_event

<HEP events: procedures>+≡
    subroutine hepmc_to_event &
        (event, hepmc_event, fallback_model, process_index, recover_beams, &
         use_alpha_s, use_scale)
        class(generic_event_t), intent(inout), target :: event
        type(hepmc_event_t), intent(inout) :: hepmc_event
        class(model_data_t), intent(in), target :: fallback_model
        integer, intent(out), optional :: process_index
        logical, intent(in), optional :: recover_beams
        logical, intent(in), optional :: use_alpha_s
        logical, intent(in), optional :: use_scale
        class(model_data_t), pointer :: model
        real(default) :: weight, scale, alpha_qcd
        type(particle_set_t) :: particle_set
        model => event%get_model_ptr ()
        call hepmc_event_to_particle_set (particle_set, &
            hepmc_event, model, fallback_model, PRT_DEFINITE_HELICITY)
        call event%set_hard_particle_set (particle_set)
        call particle_set%final ()
        call event%set_weight_ref (1._default)
        alpha_qcd = hepmc_event_get_alpha_qcd (hepmc_event)
        scale = hepmc_event_get_scale (hepmc_event)
        if (present (use_alpha_s)) then
            if (use_alpha_s .and. alpha_qcd > 0) &
                call event%set_alpha_qcd_forced (alpha_qcd)
        end if
        if (present (use_scale)) then
            if (use_scale .and. scale > 0) &
                call event%set_scale_forced (scale)
        end if
    end subroutine hepmc_to_event

```

LCIO event format

The master output function fills a LCIO event object that is already initialized, but has no particles in it.

In contrast to HepMC in LCIO there are no vertices (except for tracker and other detector specifications). So we assign first all incoming particles and then all outgoing particles to LCIO particle types. Particles which have neither parent nor children entries (this should not happen) are dropped. Finally, we insert the beam particles. If there are none, use the incoming particles instead.

Transform a particle into a `lcio_particle` object, including color and polarization. The LCIO status is equivalent to the HepMC status, in particular: 0 = null entry, 1 = physical particle, 2 = decayed/fragmented SM hadron, tau or muon, 3 = other unphysical particle entry, 4 = incoming particles, 11 = intermediate resonance such as squarks. The use of 11 for intermediate resonances is as done by HERWIG, see <http://herwig.hepforge.org/trac/wiki/FaQs>.

A beam-remnant particle (e.g., ISR photon) that has no children is tagged as outgoing, otherwise unphysical.

```
<HEP events: public>+≡
  public :: particle_to_lcio

<HEP events: procedures>+≡
  subroutine particle_to_lcio (prt, lpert)
    type(particle_t), intent(in) :: prt
    type(lcio_particle_t), intent(out) :: lpert
    integer :: lcio_status
    type(vector4_t) :: vtx
    select case (prt%get_status ())
    case (PRT_UNDEFINED)
      lcio_status = 0
    case (PRT_OUTGOING)
      lcio_status = 1
    case (PRT_BEAM_REMNANT)
      if (prt%get_n_children () == 0) then
        lcio_status = 1
      else
        lcio_status = 3
      end if
    case (PRT_BEAM)
      lcio_status = 4
    case (PRT_RESONANT)
      if (abs (prt%get_pdg ()) == 13 .or. &
        abs (prt%get_pdg ()) == 15) then
        lcio_status = 2
      else
        lcio_status = 11
      end if
    case default
      lcio_status = 3
    end select
    call lcio_particle_init (lpert, &
      prt%get_momentum (), &
      prt%get_pdg (), &
      lcio_status)
    call lcio_particle_set_color (lpert, prt%get_color ())
```

```

    vtx = prt%get_vertex ()
    call lcio_particle_set_vtx (lprt, space_part (vtx))
    call lcio_particle_set_t (lprt, vtx%p(0))
    select case (prt%get_polarization_status ())
    case (PRT_DEFINITE_HELICITY)
        call lcio_polarization_init (lprt, prt%get_helicity ())
    case (PRT_GENERIC_POLARIZATION)
        call lcio_polarization_init (lprt, prt%get_polarization ())
    end select
end subroutine particle_to_lcio

```

Initialize a particle from a LCIO particle object. The model is necessary for making a fully qualified flavor component.

(HEP events: public)+≡

```

    public :: particle_from_lcio_particle

```

(HEP events: procedures)+≡

```

subroutine particle_from_lcio_particle &
    (prt, lprt, model, daughters, parents, polarization)
    type(particle_t), intent(out) :: prt
    type(lcio_particle_t), intent(in) :: lprt
    type(model_data_t), intent(in), target :: model
    integer, dimension(:), intent(in) :: daughters, parents
    type(vector3_t) :: vtx3
    type(vector4_t) :: vtx4
    type(flavor_t) :: flv
    type(color_t) :: col
    type(helicity_t) :: hel
    type(polarization_t) :: pol
    integer, intent(in) :: polarization
    integer :: i
    select case (lcio_particle_get_status (lprt))
    case (1); call prt%set_status (PRT_OUTGOING)
    case (2); call prt%set_status (PRT_RESONANT)
    case (3); call prt%set_status (PRT_VIRTUAL)
    end select
    call flv%init (lcio_particle_get_pdg (lprt), model)
    call col%init (lcio_particle_get_flow (lprt))
    if (flv%is_beam_remnant ()) call prt%set_status (PRT_BEAM_REMNANT)
    call prt%set_flavor (flv)
    call prt%set_color (col)
    call prt%set_polarization (polarization)
    select case (polarization)
    case (PRT_DEFINITE_HELICITY)
        call lcio_particle_to_hel (lprt, prt%get_flv (), hel)
        call prt%set_helicity (hel)
    case (PRT_GENERIC_POLARIZATION)
        call lcio_particle_to_pol (lprt, prt%get_flv (), pol)
        call prt%set_pol (pol)
    end select
    call prt%set_momentum (lcio_particle_get_momentum (lprt), &
        lcio_particle_get_mass_squared (lprt))
    call prt%set_parents (parents)
    call prt%set_children (daughters)

```

```

    if (prt%get_status () == PRT_VIRTUAL .and. size(parents) == 0) &
        call prt%set_status (PRT_INCOMING)
    vtx4 = vector4_moving (lcio_particle_get_time (lprt), &
        lcio_particle_get_vertex (lprt))
    if (vtx4 /= vector4_null) call prt%set_vertex (vtx4)
end subroutine particle_from_lcio_particle

```

<HEP events: public>+≡

```

public :: lcio_event_from_particle_set

```

<HEP events: procedures>+≡

```

subroutine lcio_event_from_particle_set (evt, particle_set)
    type(lcio_event_t), intent(inout) :: evt
    type(particle_set_t), intent(in) :: particle_set
    type(lcio_particle_t), dimension(:), allocatable :: lprt
    type(lcio_particle_t), dimension(2) :: lbeam
    integer, dimension(:), allocatable :: parent, child
    logical, dimension(:), allocatable :: is_beam
    integer :: n_tot, i, j, n_parents
    n_tot = particle_set%n_tot
    allocate (lprt (n_tot))
    do i = 1, n_tot
        call particle_to_lcio (particle_set%prt(i), lprt(i))
        n_parents = particle_set%prt(i)%get_n_parents ()
        if (n_parents /= 0) then
            allocate (parent (n_parents))
            parent = particle_set%prt(i)%get_parents ()
            do j = 1, n_parents
                call lcio_particle_set_parent (lprt(i), lprt(parent(j)))
            end do
            deallocate (parent)
        end if
        call lcio_particle_add_to_evt_coll (lprt(i), evt)
    end do
    call lcio_event_add_coll (evt)
end subroutine lcio_event_from_particle_set

```

If a particle set is initialized from a LCIO event record, we have to specify the treatment of polarization (unpolarized or density matrix) which is common to all particles. Correlated polarization information is not available.

<HEP events: public>+≡

```

public :: lcio_event_to_particle_set

```

<HEP events: procedures>+≡

```

subroutine lcio_event_to_particle_set &
    (particle_set, evt, model, fallback_model, polarization)
    type(particle_set_t), intent(inout), target :: particle_set
    type(lcio_event_t), intent(in) :: evt
    class(model_data_t), intent(in), target :: model, fallback_model
    integer, intent(in) :: polarization
    type(lcio_particle_t) :: prt
    integer, dimension(:), allocatable :: parents, daughters
    integer :: n_tot, i, j, n_parents, n_children
    n_tot = lcio_event_get_n_tot (evt)

```

```

allocate (particle_set%prt (n_tot))
do i = 1, n_tot
  prt = lcio_event_get_particle (evt, i-1)
  n_parents = lcio_particle_get_n_parents (prt)
  n_children = lcio_particle_get_n_children (prt)
  allocate (daughters (n_children))
  allocate (parents (n_parents))
  if (n_children > 0) then
    do j = 1, n_children
      daughters(j) = lcio_get_n_children (evt,i,j)
    end do
  end if
  if (n_parents > 0) then
    do j = 1, n_parents
      parents(j) = lcio_get_n_parents (evt,i,j)
    end do
  end if
  call particle_from_lcio_particle (particle_set%prt(i), prt, model, &
    daughters, parents, polarization)
  deallocate (daughters, parents)
end do
do i = 1, n_tot
  if (particle_set%prt(i)%get_status () == PRT_VIRTUAL) then
    CHECK_BEAM: do j = 1, particle_set%prt(i)%get_n_parents ()
      if (particle_set%prt(j)%get_status () == PRT_BEAM) &
        call particle_set%prt(i)%set_status (PRT_INCOMING)
      exit CHECK_BEAM
    end do CHECK_BEAM
  end if
end do
particle_set%n_tot = n_tot
particle_set%n_beam = &
  count (particle_set%prt%get_status () == PRT_BEAM)
particle_set%n_in = &
  count (particle_set%prt%get_status () == PRT_INCOMING)
particle_set%n_out = &
  count (particle_set%prt%get_status () == PRT_OUTGOING)
particle_set%n_vir = &
  particle_set%n_tot - particle_set%n_in - particle_set%n_out
end subroutine lcio_event_to_particle_set

```

(HEP events: public)+≡

```
public :: lcio_to_event
```

(HEP events: procedures)+≡

```

subroutine lcio_to_event &
  (event, lcio_event, fallback_model, process_index, recover_beams, &
    use_alpha_s, use_scale)
class(generic_event_t), intent(inout), target :: event
type(lcio_event_t), intent(inout) :: lcio_event
class(model_data_t), intent(in), target :: fallback_model
integer, intent(out), optional :: process_index
logical, intent(in), optional :: recover_beams
logical, intent(in), optional :: use_alpha_s

```



```

logical, intent(in), optional :: use_scale
class(model_data_t), pointer :: model
real(default) :: weight, scale, alpha_qcd
type(particle_set_t) :: particle_set
model => event%get_model_ptr ()
call lcio_event_to_particle_set (particle_set, &
    lcio_event, model, fallback_model, PRT_DEFINITE_HELICITY)
call event%set_hard_particle_set (particle_set)
call particle_set%final ()
alpha_qcd = lcio_event_get_alphas (lcio_event)
scale = lcio_event_get_scaleval (lcio_event)
if (present (use_alpha_s)) then
    if (use_alpha_s .and. alpha_qcd > 0) &
        call event%set_alpha_qcd_forced (alpha_qcd)
end if
if (present (use_scale)) then
    if (use_scale .and. scale > 0) &
        call event%set_scale_forced (scale)
end if
end subroutine lcio_to_event

```

17.10.2 Unit tests

Set up a chain of production and decay and factorize the result into particles.

The process is $d\bar{d} \rightarrow Z \rightarrow q\bar{q}$.

```

<HEP events: public>+=
    public :: hep_events_test
<HEP events: procedures>+=
    subroutine hep_events_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <HEP events: execute tests>
end subroutine hep_events_test

```

If HepMC is available, check the routines via HepMC.

```

<HEP events: execute tests>=
    if (hepmc_is_available ()) then
        call test (hep_events_1, "hep_events_1", &
            "check HepMC event routines", &
            u, results)
    end if
<HEP events: tests>=
    subroutine hep_events_1 (u)
        use os_interface
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(flavor_t), dimension(3) :: flv
        type(color_t), dimension(3) :: col
        type(helicity_t), dimension(3) :: hel
        type(quantum_numbers_t), dimension(3) :: qn
        type(vector4_t), dimension(3) :: p
    end subroutine hep_events_1

```

```

type(interaction_t), target :: int1, int2
type(quantum_numbers_mask_t) :: qn_mask_conn, qn_rest
type(evaluator_t), target :: eval
type(interaction_t), pointer :: int
type(particle_set_t) :: particle_set1, particle_set2
type(particle_set_t) :: particle_set3, particle_set4
type(subevt_t) :: subevt
logical :: ok
integer :: unit, iostat
type(hepmc_event_t) :: hepmc_event
type(hepmc_iostream_t) :: iostream

write (u, "(A)")  "* Test output: HEP events"
write (u, "(A)")  "* Purpose: test HepMC event routines"
write (u, "(A)")

write (u, "(A)")  "* Reading model file"

call model%init_sm_test ()

write (u, "(A)")
write (u, "(A)")  "* Initializing production process"

call int1%basic_init (2, 0, 1, set_relations=.true.)
call flv%init ([1, -1, 23], model)
call col%init_col_acl ([0, 0, 0], [0, 0, 0])
call hel(3)%init ( 1, 1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0.25_default, 0._default))
call hel(3)%init ( 1,-1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0._default, 0.25_default))
call hel(3)%init (-1, 1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0._default,-0.25_default))
call hel(3)%init (-1,-1)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0.25_default, 0._default))
call hel(3)%init ( 0, 0)
call qn%init (flv, col, hel)
call int1%add_state (qn, value=(0.5_default, 0._default))
call int1%freeze ()
p(1) = vector4_moving (45._default, 45._default, 3)
p(2) = vector4_moving (45._default,-45._default, 3)
p(3) = p(1) + p(2)
call int1%set_momenta (p)

write (u, "(A)")
write (u, "(A)")  "* Setup decay process"

call int2%basic_init (1, 0, 2, set_relations=.true.)
call flv%init ([23, 1, -1], model)
call col%init_col_acl ([0, 501, 0], [0, 0, 501])
call hel%init ([1, 1, 1], [1, 1, 1])

```

```

call qn%init (flv, col, hel)
call int2%add_state (qn, value=(1._default, 0._default))
call hel%init ([1, 1, 1], [-1,-1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0._default, 0.1_default))
call hel%init ([-1,-1,-1], [1, 1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0._default,-0.1_default))
call hel%init ([-1,-1,-1], [-1,-1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(1._default, 0._default))
call hel%init ([0, 1,-1], [0, 1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(4._default, 0._default))
call hel%init ([0,-1, 1], [0, 1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(2._default, 0._default))
call hel%init ([0, 1,-1], [0,-1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(2._default, 0._default))
call hel%init ([0,-1, 1], [0,-1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(4._default, 0._default))
call flv%init ([23, 2, -2], model)
call hel%init ([0, 1,-1], [0, 1,-1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0.5_default, 0._default))
call hel%init ([0,-1, 1], [0,-1, 1])
call qn%init (flv, col, hel)
call int2%add_state (qn, value=(0.5_default, 0._default))
call int2%freeze ()
p(2) = vector4_moving (45._default, 45._default, 2)
p(3) = vector4_moving (45._default,-45._default, 2)
call int2%set_momenta (p)
call int2%set_source_link (1, int1, 3)
call int1%basic_write (u)
call int2%basic_write (u)

write (u, "(A)")
write (u, "(A)")  "* Concatenate production and decay"

call eval%init_product (int1, int2, qn_mask_conn, &
    connections_are_resonant=.true.)
call eval%receive_momenta ()
call eval%evaluate ()
call eval%write (u)

write (u, "(A)")
write (u, "(A)")  "* Factorize as subevent (complete, polarized)"
write (u, "(A)")

int => eval%interaction_t
call particle_set1%init &
    (ok, int, int, FM_FACTOR_HELICITY, &

```

```

        [0.2_default, 0.2_default], .false., .true.)
call particle_set1%write (u)

write (u, "(A)")
write (u, "(A)")  "* Factorize as subevent (in/out only, selected helicity)"
write (u, "(A)")

int => eval%interaction_t
call particle_set2%init &
    (ok, int, int, FM_SELECT_HELICITY, &
    [0.9_default, 0.9_default], .false., .false.)
call particle_set2%write (u)
call particle_set2%final ()

write (u, "(A)")
write (u, "(A)")  "* Factorize as subevent (complete, selected helicity)"
write (u, "(A)")

int => eval%interaction_t
call particle_set2%init &
    (ok, int, int, FM_SELECT_HELICITY, &
    [0.7_default, 0.7_default], .false., .true.)
call particle_set2%write (u)

write (u, "(A)")
write (u, "(A)")  "* Transfer particle_set to HepMC, print, and output to"
write (u, "(A)")  "      hep_events.hepmc.dat"
write (u, "(A)")

call hepmc_event_init (hepmc_event, 11, 127)
call hepmc_event_from_particle_set (hepmc_event, particle_set2)
call hepmc_event_print (hepmc_event)
call hepmc_iostream_open_out &
    (iostream , var_str ("hep_events.hepmc.dat"))
call hepmc_iostream_write_event (iostream, hepmc_event)
call hepmc_iostream_close (iostream)

write (u, "(A)")
write (u, "(A)")  "* Recover from HepMC file"
write (u, "(A)")

call particle_set2%final ()
call hepmc_event_final (hepmc_event)
call hepmc_event_init (hepmc_event)
call hepmc_iostream_open_in &
    (iostream , var_str ("hep_events.hepmc.dat"))
call hepmc_iostream_read_event (iostream, hepmc_event, ok)
call hepmc_iostream_close (iostream)
call hepmc_event_to_particle_set (particle_set2, &
    hepmc_event, model, model, PRT_DEFINITE_HELICITY)
call particle_set2%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```

```

        call particle_set1%final ()
        call particle_set2%final ()
        call eval%final ()
        call int1%final ()
        call int2%final ()
        call hepmc_event_final (hepmc_event)
        call model%final ()

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: particles_2"

    end subroutine hep_events_1

```

17.11 LHEF Input/Output

The LHEF event record is standardized. It is an ASCII format. We try our best at using it for both input and output.

`<eio_lhef.f90>`≡
<File header>

```

module eio_lhef

    use kinds
    use io_units
    <Use strings>
    use string_utils
    use unit_tests
    use diagnostics
    use os_interface

    use xml
    use lorentz
    use model_data
    use particles
    use event_base
    use eio_data
    use eio_base
    use hep_common
    use hep_events

    <Standard module head>

    <EIO LHEF: public>

    <EIO LHEF: types>

    <EIO LHEF: interfaces>

contains

```

<EIO LHEF: procedures>

<EIO LHEF: tests>

end module eio_lhef

17.11.1 Type

With sufficient confidence that it will always be three characters, we can store the version string with a default value.

<EIO LHEF: public>≡

public :: eio_lhef_t

<EIO LHEF: types>≡

```
type, extends (eio_t) :: eio_lhef_t
  logical :: writing = .false.
  logical :: reading = .false.
  integer :: unit = 0
  type(event_sample_data_t) :: data
  type(cstream_t) :: cstream
  character(3) :: version = "1.0"
  logical :: keep_beams = .false.
  logical :: keep_remnants = .true.
  logical :: recover_beams = .true.
  logical :: unweighted = .true.
  logical :: write_sqme_ref = .false.
  logical :: write_sqme_prc = .false.
  logical :: write_sqme_alt = .false.
  logical :: use_alpha_s_from_file = .false.
  logical :: use_scale_from_file = .false.
  integer :: n_alt = 0
  integer, dimension(:), allocatable :: proc_num_id
  integer :: i_weight_sqme = 0
  type(xml_tag_t) :: tag_lhef, tag_head, tag_init, tag_event
  type(xml_tag_t), allocatable :: tag_gen_n, tag_gen_v
  type(xml_tag_t), allocatable :: tag_generator, tag_xsecinfo
  type(xml_tag_t), allocatable :: tag_sqme_ref, tag_sqme_prc
  type(xml_tag_t), dimension(:), allocatable :: tag_sqme_alt, tag_wgts_alt
  type(xml_tag_t), allocatable :: tag_weight, tag_weightinfo, tag_weights
contains
  <EIO LHEF: eio_lhef: TBP>
end type eio_lhef_t
```

17.11.2 Specific Methods

Set parameters that are specifically used with LHEF.

<EIO LHEF: eio_lhef: TBP>≡

procedure :: set_parameters => eio_lhef_set_parameters

<EIO LHEF: procedures>≡

```
subroutine eio_lhef_set_parameters (eio, &
  keep_beams, keep_remnants, recover_beams, &
  use_alpha_s_from_file, use_scale_from_file, &
```

```

        version, extension, write_sqme_ref, write_sqme_prc, write_sqme_alt)
class(eio_lhef_t), intent(inout) :: eio
logical, intent(in), optional :: keep_beams
logical, intent(in), optional :: keep_remnants
logical, intent(in), optional :: recover_beams
logical, intent(in), optional :: use_alpha_s_from_file
logical, intent(in), optional :: use_scale_from_file
character(*), intent(in), optional :: version
type(string_t), intent(in), optional :: extension
logical, intent(in), optional :: write_sqme_ref
logical, intent(in), optional :: write_sqme_prc
logical, intent(in), optional :: write_sqme_alt
if (present (keep_beams)) eio%keep_beams = keep_beams
if (present (keep_remnants)) eio%keep_remnants = keep_remnants
if (present (recover_beams)) eio%recover_beams = recover_beams
if (present (use_alpha_s_from_file)) &
    eio%use_alpha_s_from_file = use_alpha_s_from_file
if (present (use_scale_from_file)) &
    eio%use_scale_from_file = use_scale_from_file
if (present (version)) then
    select case (version)
    case ("1.0", "2.0", "3.0")
        eio%version = version
    case default
        call msg_error ("LHEF version " // version &
            // " is not supported. Inserting 2.0")
        eio%version = "2.0"
    end select
end if
if (present (extension)) then
    eio%extension = extension
else
    eio%extension = "lhe"
end if
if (present (write_sqme_ref)) eio%write_sqme_ref = write_sqme_ref
if (present (write_sqme_prc)) eio%write_sqme_prc = write_sqme_prc
if (present (write_sqme_alt)) eio%write_sqme_alt = write_sqme_alt
end subroutine eio_lhef_set_parameters

```

17.11.3 Common Methods

Output. This is not the actual event format, but a readable account of the current object status.

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: write => eio_lhef_write

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_write (object, unit)
        class(eio_lhef_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit)
        write (u, "(1x,A)") "LHEF event stream:"

```

```

if (object%writing) then
  write (u, "(3x,A,A)") "Writing to file  = ", char (object%filename)
else if (object%reading) then
  write (u, "(3x,A,A)") "Reading from file = ", char (object%filename)
else
  write (u, "(3x,A)") "[closed]"
end if
write (u, "(3x,A,L1)") "Keep beams      = ", object%keep_beams
write (u, "(3x,A,L1)") "Keep remnants  = ", object%keep_remnants
write (u, "(3x,A,L1)") "Recover beams   = ", object%recover_beams
write (u, "(3x,A,L1)") "Alpha_s from file = ", &
  object%use_alpha_s_from_file
write (u, "(3x,A,L1)") "Scale from file  = ", &
  object%use_scale_from_file
write (u, "(3x,A,A)") "Version          = ", object%version
write (u, "(3x,A,A,A)") "File extension   = '", &
  char (object%extension), "'"
if (allocated (object%proc_num_id)) then
  write (u, "(3x,A)") "Numerical process IDs:"
  do i = 1, size (object%proc_num_id)
    write (u, "(5x,I0,': ',I0)") i, object%proc_num_id(i)
  end do
end if
end subroutine eio_lhef_write

```

Finalizer: close any open file.

(EIO LHEF: eio_lhef: TBP)+≡

```
procedure :: final => eio_lhef_final
```

(EIO LHEF: procedures)+≡

```

subroutine eio_lhef_final (object)
  class(eio_lhef_t), intent(inout) :: object
  if (allocated (object%proc_num_id)) deallocate (object%proc_num_id)
  if (object%writing) then
    write (msg_buffer, "(A,A,A)") "Events: closing LHEF file '", &
      char (object%filename), "'"
    call msg_message ()
    call object%write_footer ()
    close (object%unit)
    object%writing = .false.
  else if (object%reading) then
    write (msg_buffer, "(A,A,A)") "Events: closing LHEF file '", &
      char (object%filename), "'"
    call msg_message ()
    call object%cstream%final ()
    close (object%unit)
    object%reading = .false.
  end if
end subroutine eio_lhef_final

```

Common initialization for input and output.

(EIO LHEF: eio_lhef: TBP)+≡

```
procedure :: common_init => eio_lhef_common_init
```


<EIO LHEF: procedures>+≡

```

subroutine eio_lhef_common_init (eio, sample, data, extension)
  class(eio_lhef_t), intent(inout) :: eio
  type(string_t), intent(in) :: sample
  type(string_t), intent(in), optional :: extension
  type(event_sample_data_t), intent(in), optional :: data
  if (.not. present (data)) &
    call msg_bug ("LHEF initialization: missing data")
  eio%data = data
  if (data%n_beam /= 2) &
    call msg_fatal ("LHEF: defined for scattering processes only")
  eio%unweighted = data%unweighted
  if (eio%unweighted) then
    select case (data%norm_mode)
    case (NORM_UNIT)
    case default; call msg_fatal &
      ("LHEF: normalization for unweighted events must be '1'")
    end select
  else
    select case (data%norm_mode)
    case (NORM_SIGMA)
    case default; call msg_fatal &
      ("LHEF: normalization for weighted events must be 'sigma'")
    end select
  end if
  eio%n_alt = data%n_alt
  eio%sample = sample
  if (present (extension)) then
    eio%extension = extension
  end if
  call eio%set_filename ()
  eio%unit = free_unit ()
  call eio%init_tags (data)
  allocate (eio%proc_num_id (data%n_proc), source = data%proc_num_id)
end subroutine eio_lhef_common_init

```

Initialize the tag objects. Some tags depend on the LHEF version. In particular, the tags that in LHEF 2.0 identify individual weights by name in each event block, in LHEF 3.0 are replaced by info tags in the init block and a single `weights` tag in the event block. The name attributes of those tags are specific for WHIZARD.

<EIO LHEF: eio_lhef: TBP>+≡

```

procedure :: init_tags => eio_lhef_init_tags

```

<EIO LHEF: procedures>+≡

```

subroutine eio_lhef_init_tags (eio, data)
  class(eio_lhef_t), intent(inout) :: eio
  type(event_sample_data_t), intent(in) :: data
  real(default), parameter :: pb_per_fb = 1.e-3_default
  integer :: i
  call eio%tag_lhef%init ( &
    var_str ("LesHouchesEvents"), &
    [xml_attribute (var_str ("version"), var_str (eio%version))], &
    .true.)

```

```

call eio%tag_head%init ( &
    var_str ("header"), &
    .true.)
call eio%tag_init%init ( &
    var_str ("init"), &
    .true.)
call eio%tag_event%init (var_str ("event"), &
    .true.)
select case (eio%version)
case ("1.0")
    allocate (eio%tag_gen_n)
    call eio%tag_gen_n%init ( &
        var_str ("generator_name"), &
        .true.)
    allocate (eio%tag_gen_v)
    call eio%tag_gen_v%init ( &
        var_str ("generator_version"), &
        .true.)
end select
select case (eio%version)
case ("2.0", "3.0")
    allocate (eio%tag_generator)
    call eio%tag_generator%init ( &
        var_str ("generator"), &
        [xml_attribute (var_str ("version"), var_str ("<Version>"))], &
        .true.)
    allocate (eio%tag_xsecinfo)
    call eio%tag_xsecinfo%init ( &
        var_str ("xsecinfo"), &
        [xml_attribute (var_str ("neve"), str (data%n_evt)), &
        xml_attribute (var_str ("totxsec"), &
            str (data%total_cross_section * pb_per_fb))])
end select
select case (eio%version)
case ("2.0")
    allocate (eio%tag_weight)
    call eio%tag_weight%init (var_str ("weight"), &
        [xml_attribute (var_str ("name"))])
    if (eio%write_sqme_ref) then
        allocate (eio%tag_sqme_ref)
        call eio%tag_sqme_ref%init (var_str ("weight"), &
            [xml_attribute (var_str ("name"), var_str ("sqme_ref"))], &
            .true.)
    end if
    if (eio%write_sqme_prc) then
        allocate (eio%tag_sqme_prc)
        call eio%tag_sqme_prc%init (var_str ("weight"), &
            [xml_attribute (var_str ("name"), var_str ("sqme_prc"))], &
            .true.)
    end if
    if (eio%n_alt > 0) then
        if (eio%write_sqme_alt) then
            allocate (eio%tag_sqme_alt (1))
            call eio%tag_sqme_alt(1)%init (var_str ("weight"), &

```

```

        [xml_attribute (var_str ("name"), var_str ("sqme_alt"))], &
        .true.)
    end if
    allocate (eio%tag_wgts_alt (1))
    call eio%tag_wgts_alt(1)%init (var_str ("weight"), &
        [xml_attribute (var_str ("name"), var_str ("wgts_alt"))], &
        .true.)
    end if
case ("3.0")
    if (eio%write_sqme_ref) then
        allocate (eio%tag_sqme_ref)
        call eio%tag_sqme_ref%init (var_str ("weightinfo"), &
            [xml_attribute (var_str ("name"), var_str ("sqme_ref"))])
    end if
    if (eio%write_sqme_prc) then
        allocate (eio%tag_sqme_prc)
        call eio%tag_sqme_prc%init (var_str ("weightinfo"), &
            [xml_attribute (var_str ("name"), var_str ("sqme_prc"))])
    end if
    if (eio%n_alt > 0) then
        if (eio%write_sqme_alt) then
            allocate (eio%tag_sqme_alt (eio%n_alt))
            do i = 1, eio%n_alt
                call eio%tag_sqme_alt(i)%init (var_str ("weightinfo"), &
                    [xml_attribute (var_str ("name"), &
                        var_str ("sqme_alt") // str (i))])
            end do
        end if
        allocate (eio%tag_wgts_alt (eio%n_alt))
        do i = 1, eio%n_alt
            call eio%tag_wgts_alt(i)%init (var_str ("weightinfo"), &
                [xml_attribute (var_str ("name"), &
                    var_str ("wgts_alt") // str (i))])
        end do
    end if
    allocate (eio%tag_weightinfo)
    call eio%tag_weightinfo%init (var_str ("weightinfo"), &
        [xml_attribute (var_str ("name"))])
    allocate (eio%tag_weights)
    call eio%tag_weights%init (var_str ("weights"), .true.)
end select
end subroutine eio_lhef_init_tags

```

Initialize event writing.

<EIO LHEF: eio_lhef: TBP>+≡

```

    procedure :: init_out => eio_lhef_init_out

```

<EIO LHEF: procedures>+≡

```

subroutine eio_lhef_init_out (eio, sample, data, success, extension)
    class(eio_lhef_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(string_t), intent(in), optional :: extension
    type(event_sample_data_t), intent(in), optional :: data
    logical, intent(out), optional :: success

```

```

integer :: u, i
call eio%set_splitting (data)
call eio%common_init (sample, data, extension)
write (msg_buffer, "(A,A,A)") "Events: writing to LHEF file '", &
    char (eio%filename), "'"
call msg_message ()
eio%writing = .true.
u = eio%unit
open (u, file = char (eio%filename), &
    action = "write", status = "replace")
call eio%write_header ()
call heprup_init &
    (data%pdg_beam, &
    data%energy_beam, &
    n_processes = data%n_proc, &
    unweighted = data%unweighted, &
    negative_weights = data%negative_weights)
do i = 1, data%n_proc
    call heprup_set_process_parameters (i = i, &
        process_id = data%proc_num_id(i), &
        cross_section = data%cross_section(i), &
        error = data%error(i))
end do
call eio%tag_init%write (u); write (u, *)
call heprup_write_lhef (u)
select case (eio%version)
case ("2.0"); call eio%write_init_20 (data)
case ("3.0"); call eio%write_init_30 (data)
end select
call eio%tag_init%close (u); write (u, *)
if (present (success)) success = .true.
end subroutine eio_lhef_init_out

```

Initialize event reading. First read the LHEF tag and version, then read the header and skip over its contents, then read the init block. (We require the opening and closing tags of the init block to be placed on separate lines without extra stuff.)

For input, we do not (yet?) support split event files.

(EIO LHEF: eio_lhef: TBP)+≡

```

procedure :: init_in => eio_lhef_init_in

```

(EIO LHEF: procedures)+≡

```

subroutine eio_lhef_init_in (eio, sample, data, success, extension)
    class(eio_lhef_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(string_t), intent(in), optional :: extension
    type(event_sample_data_t), intent(inout), optional :: data
    logical, intent(out), optional :: success
    logical :: exist, ok, closing
    type(event_sample_data_t) :: data_file
    type(string_t) :: string
    integer :: u
    eio%split = .false.
    call eio%common_init (sample, data, extension)

```

```

write (msg_buffer, "(A,A,A)") "Events: reading from LHEF file '", &
    char (eio%filename), "'"
call msg_message ()
inquire (file = char (eio%filename), exist = exist)
if (.not. exist) call msg_fatal ("Events: LHEF file not found.")
eio%reading = .true.
u = eio%unit
open (u, file = char (eio%filename), &
    action = "read", status = "old")
call eio%cstream%init (u)
call eio%read_header ()
call eio%tag_init%read (eio%cstream, ok)
if (.not. ok) call err_init
select case (eio%version)
case ("1.0"); call eio%read_init_10 (data_file)
    call eio%tag_init%read_content (eio%cstream, string, closing)
    if (string /= "" .or. .not. closing) call err_init
case ("2.0"); call eio%read_init_20 (data_file)
case ("3.0"); call eio%read_init_30 (data_file)
end select
call eio%merge_data (data, data_file)
if (present (success)) success = .true.

contains

subroutine err_init
    call msg_fatal ("LHEF: syntax error in init tag")
end subroutine err_init

end subroutine eio_lhef_init_in

```

Merge event sample data: we can check the data in the file against our assumptions and set or reset parameters.

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: merge_data => eio_merge_data

<EIO LHEF: procedures>+≡
subroutine eio_merge_data (eio, data, data_file)
    class(eio_lhef_t), intent(inout) :: eio
    type(event_sample_data_t), intent(inout) :: data
    type(event_sample_data_t), intent(in) :: data_file
    real, parameter :: tolerance = 1000 * epsilon (1._default)
    if (data%unweighted .neqv. data_file%unweighted) call err_weights
    if (data%negative_weights .neqv. data_file%negative_weights) &
        call err_weights
    if (data%norm_mode /= data_file%norm_mode) call err_norm
    if (data%n_beam /= data_file%n_beam) call err_beams
    if (any (data%pdg_beam /= data_file%pdg_beam)) call err_beams
    if (any (abs ((data%energy_beam - data_file%energy_beam)) &
        > (data%energy_beam + data_file%energy_beam) * tolerance)) &
        call err_beams
    if (data%n_proc /= data_file%n_proc) call err_proc
    if (any (data%proc_num_id /= data_file%proc_num_id)) call err_proc
    where (data%cross_section == 0)

```

```

        data%cross_section = data_file%cross_section
        data%error = data_file%error
    end where
    data%total_cross_section = sum (data%cross_section)
    if (data_file%n_evt > 0) then
        if (data%n_evt > 0 .and. data_file%n_evt /= data%n_evt) call err_n_evt
        data%n_evt = data_file%n_evt
    end if
contains
    subroutine err_weights
        call msg_fatal ("LHEF: mismatch in event weight properties")
    end subroutine err_weights
    subroutine err_norm
        call msg_fatal ("LHEF: mismatch in event normalization")
    end subroutine err_norm
    subroutine err_beams
        call msg_fatal ("LHEF: mismatch in beam properties")
    end subroutine err_beams
    subroutine err_proc
        call msg_fatal ("LHEF: mismatch in process definitions")
    end subroutine err_proc
    subroutine err_n_evt
        call msg_error ("LHEF: mismatch in specified number of events (ignored)")
    end subroutine err_n_evt
end subroutine eio_merge_data

```

Switch from input to output: reopen the file for reading.

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: switch_inout => eio_lhef_switch_inout

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_switch_inout (eio, success)
        class(eio_lhef_t), intent(inout) :: eio
        logical, intent(out), optional :: success
        call msg_bug ("LHEF: in-out switch not supported")
        if (present (success)) success = .false.
    end subroutine eio_lhef_switch_inout

```

Split event file: increment the counter, close the current file, open a new one. If the file needs a header, repeat it for the new file. (We assume that the common block contents are still intact.)

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: split_out => eio_lhef_split_out

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_split_out (eio)
        class(eio_lhef_t), intent(inout) :: eio
        integer :: u
        if (eio%split) then
            eio%split_index = eio%split_index + 1
            call eio%set_filename ()
            write (msg_buffer, "(A,A,A)") "Events: writing to LHEF file '", &
                char (eio%filename), "'"
            call msg_message ()

```

```

    call eio%write_footer ()
    u = eio%unit
    close (u)
    open (u, file = char (eio%filename), &
         action = "write", status = "replace")
    call eio%write_header ()
    call eio%tag_init%write (u); write (u, *)
    call heprup_write_lhef (u)
    select case (eio%version)
    case ("2.0"); call eio%write_init_20 (eio%data)
    case ("3.0"); call eio%write_init_30 (eio%data)
    end select
    call eio%tag_init%close (u); write (u, *)
end if
end subroutine eio_lhef_split_out

```

Output an event. Write first the event indices, then weight and squared matrix element, then the particle set.

```

<EIO LHEF: eio_lhef: TBP>+≡
  procedure :: output => eio_lhef_output

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_output (eio, event, i_prc, reading, passed, pacify)
    class(eio_lhef_t), intent(inout) :: eio
    class(generic_event_t), intent(in), target :: event
    integer, intent(in) :: i_prc
    logical, intent(in), optional :: reading, passed, pacify
    integer :: u
    u = given_output_unit (eio%unit); if (u < 0) return
    if (present (passed)) then
      if (.not. passed) return
    end if
    if (eio%writing) then
      call hepeup_from_event (event, &
        process_index = eio%proc_num_id (i_prc), &
        keep_beams = eio%keep_beams, &
        keep_remnants = eio%keep_remnants)
      write (u, '(A)') "<event>"
      call hepeup_write_lhef (eio%unit)
      select case (eio%version)
      case ("2.0"); call eio%write_event_20 (event)
      case ("3.0"); call eio%write_event_30 (event)
      end select
      write (u, '(A)') "</event>"
    else
      call eio%write ()
      call msg_fatal ("LHEF file is not open for writing")
    end if
  end subroutine eio_lhef_output

```

Input an event. Upon input of `i_prc`, we can just read in the whole HEPEUP common block. These data are known to come first. The `i_prc` value can be deduced from the IDPRUP value by a table lookup.

Reading the common block bypasses the `cstream` which accesses the input unit. This is consistent with the LHEF specification. After the common-block data have been swallowed, we can resume reading from stream.

We don't catch actual I/O errors. However, we return a negative value in `iostat` if we reached the terminating `</LesHouchesEvents>` tag.

```

<EIO LHEF: eio lhef: TBP>+≡
    procedure :: input_i_prc => eio_lhef_input_i_prc

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_input_i_prc (eio, i_prc, iostat)
        class(eio_lhef_t), intent(inout) :: eio
        integer, intent(out) :: i_prc
        integer, intent(out) :: iostat
        integer :: i, proc_num_id
        type(string_t) :: s
        logical :: ok
        iostat = 0
        call eio%tag_lhef%read_content (eio%cstream, s, ok)
        if (ok) then
            if (s == "") then
                iostat = -1
            else
                call err_close
            end if
            return
        else
            call eio%cstream%revert_record (s)
        end if
        call eio%tag_event%read (eio%cstream, ok)
        if (.not. ok) then
            call err_evt1
            return
        end if
        call hepeup_read_lhef (eio%unit)
        call hepeup_get_event_parameters (proc_id = proc_num_id)
        i_prc = 0
        FIND_I_PRC: do i = 1, size (eio%proc_num_id)
            if (eio%proc_num_id(i) == proc_num_id) then
                i_prc = i
                exit FIND_I_PRC
            end if
        end do FIND_I_PRC
        if (i_prc == 0) call err_index
contains
        subroutine err_close
            call msg_error ("LHEF: reading events: syntax error in closing tag")
            iostat = 1
        end subroutine
        subroutine err_evt1
            call msg_error ("LHEF: reading events: invalid event tag, &
                &aborting read")
            iostat = 2
        end subroutine err_evt1
        subroutine err_index

```



```

        call msg_error ("LHEF: reading events: undefined process ID " &
            // char (str (proc_num_id)) // ", aborting read")
        iostat = 3
    end subroutine err_index
end subroutine eio_lhef_input_i_prc

```

Since we have already read the event information from file, this input routine can transfer the common-block contents to the event record. Also, we read any further information in the event record.

Since LHEF doesn't give this information, we must assume that the MCI group, term, and channel can all be safely set to 1. This works if there is only one MCI group and term. The channel doesn't matter for the matrix element.

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: input_event => eio_lhef_input_event

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_input_event (eio, event, iostat)
        class(eio_lhef_t), intent(inout) :: eio
        class(generic_event_t), intent(inout), target :: event
        integer, intent(out) :: iostat
        type(particle_set_t), pointer :: pset
        type(string_t) :: s
        logical :: closing
        iostat = 0
        call event%reset ()
        call event%select (1, 1, 1)
        call hepeup_to_event (event, eio%fallback_model, &
            recover_beams = eio%recover_beams, &
            use_alpha_s = eio%use_alpha_s_from_file, &
            use_scale = eio%use_scale_from_file)
        select case (eio%version)
        case ("1.0")
            call eio%tag_event%read_content (eio%cstream, s, closing = closing)
            if (s /= "" .or. .not. closing) call err_evt2
        case ("2.0"); call eio%read_event_20 (event)
        case ("3.0"); call eio%read_event_30 (event)
        end select
    contains
        subroutine err_evt2
            call msg_error ("LHEF: reading events: syntax error in event record, &
                &aborting read")
            iostat = 2
        end subroutine err_evt2

end subroutine eio_lhef_input_event

```

17.11.4 Les Houches Event File: header/footer

These two routines write the header and footer for the Les Houches Event File format (LHEF).

The current version writes no information except for the generator name and version (v.1.0 only).

```

(EIO LHEF: eio_lhef: TBP)+≡
  procedure :: write_header => eio_lhef_write_header
  procedure :: write_footer => eio_lhef_write_footer

(EIO LHEF: procedures)+≡
  subroutine eio_lhef_write_header (eio)
    class(eio_lhef_t), intent(in) :: eio
    integer :: u
    u = given_output_unit (eio%unit); if (u < 0) return
    call eio%tag_lhef%write (u); write (u, *)
    call eio%tag_head%write (u); write (u, *)
    select case (eio%version)
    case ("1.0")
      write (u, "(2x)", advance = "no")
      call eio%tag_gen_n%write (var_str ("WHIZARD"), u)
      write (u, *)
      write (u, "(2x)", advance = "no")
      call eio%tag_gen_v%write (var_str ("Version"), u)
      write (u, *)
    end select
    call eio%tag_head%close (u); write (u, *)
  end subroutine eio_lhef_write_header

  subroutine eio_lhef_write_footer (eio)
    class(eio_lhef_t), intent(in) :: eio
    integer :: u
    u = given_output_unit (eio%unit); if (u < 0) return
    call eio%tag_lhef%close (u)
  end subroutine eio_lhef_write_footer

```

Reading the header just means finding the tags and ignoring any contents. When done, we should stand just after the header tag.

```

(EIO LHEF: eio_lhef: TBP)+≡
  procedure :: read_header => eio_lhef_read_header

(EIO LHEF: procedures)+≡
  subroutine eio_lhef_read_header (eio)
    class(eio_lhef_t), intent(inout) :: eio
    logical :: success, closing
    type(string_t) :: content
    call eio%tag_lhef%read (eio%cstream, success)
    if (.not. success .or. .not. eio%tag_lhef%has_content) call err_lhef
    if (eio%tag_lhef%get_attribute (1) /= eio%version) call err_version
    call eio%tag_head%read (eio%cstream, success)
    if (.not. success) call err_header
    if (eio%tag_head%has_content) then
      SKIP_HEADER_CONTENT: do
        call eio%tag_head%read_content (eio%cstream, content, closing)
        if (closing) exit SKIP_HEADER_CONTENT
      end do SKIP_HEADER_CONTENT
    end if
  contains

```

```

subroutine err_lhef
  call msg_fatal ("LHEF: LesHouchesEvents tag absent or corrupted")
end subroutine err_lhef
subroutine err_header
  call msg_fatal ("LHEF: header tag absent or corrupted")
end subroutine err_header
subroutine err_version
  call msg_error ("LHEF: version mismatch: expected " &
    // eio%version // ", found " &
    // char (eio%tag_lhef%get_attribute (1)))
end subroutine err_version
end subroutine eio_lhef_read_header

```

17.11.5 Version-Specific Code: 1.0

In version 1.0, the init tag contains just HEPUP data. While a `cstream` is connected to the input unit, we bypass it temporarily for the purpose of reading the HEPUP contents. This is consistent with the LHEF standard.

This routine does not read the closing tag of the init block.

```

<EIO LHEF: eio_lhef: TBP>+≡
  procedure :: read_init_10 => eio_lhef_read_init_10

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_read_init_10 (eio, data)
    class(eio_lhef_t), intent(in) :: eio
    type(event_sample_data_t), intent(out) :: data
    integer :: n_proc, i
    call heprup_read_lhef (eio%unit)
    call heprup_get_run_parameters (n_processes = n_proc)
    call data%init (n_proc)
    data%n_beam = 2
    call heprup_get_run_parameters ( &
      unweighted = data%unweighted, &
      negative_weights = data%negative_weights, &
      beam_pdg = data%pdg_beam, &
      beam_energy = data%energy_beam)
    if (data%unweighted) then
      data%norm_mode = NORM_UNIT
    else
      data%norm_mode = NORM_SIGMA
    end if
    do i = 1, n_proc
      call heprup_get_process_parameters (i, &
        process_id = data%proc_num_id(i), &
        cross_section = data%cross_section(i), &
        error = data%error(i))
    end do
  end subroutine eio_lhef_read_init_10

```

17.11.6 Version-Specific Code: 2.0

This is the init information for the 2.0 format, after the HEPRUP data. We have the following tags:

- **generator** Generator name and version.
- **xsecinfo** Cross section and weights data. We have the total cross section and number of events (assuming that the event file is intact), but information on minimum and maximum weights is not available before the file is complete. We just write the mandatory tags. (Note that the default values of the other tags describe a uniform unit weight, but we can determine most values only after the sample is complete.)
- **cutsinfo** This optional tag is too specific to represent the possibilities of WHIZARD, so we skip it.
- **procinfo** This optional tag is useful for giving details of NLO calculations. Skipped.
- **mergetype** Optional, also not applicable.

```

<EIO LHEF: eio_lhef: TBP>+≡
  procedure :: write_init_20 => eio_lhef_write_init_20

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_write_init_20 (eio, data)
    class(eio_lhef_t), intent(in) :: eio
    type(event_sample_data_t), intent(in) :: data
    integer :: u
    u = eio%unit
    call eio%tag_generator%write (u)
    write (u, "(A)", advance="no") "WHIZARD"
    call eio%tag_generator%close (u); write (u, *)
    call eio%tag_xsecinfo%write (u); write (u, *)
  end subroutine eio_lhef_write_init_20

```

When reading the init block, we first call the 1.0 routine that fills HEPRUP. Then we consider the possible tags. Only the **generator** and **xsecinfo** tags are of interest. We skip everything else except for the closing tag.

```

<EIO LHEF: eio_lhef: TBP>+≡
  procedure :: read_init_20 => eio_lhef_read_init_20

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_read_init_20 (eio, data)
    class(eio_lhef_t), intent(inout) :: eio
    type(event_sample_data_t), intent(out) :: data
    real(default), parameter :: pb_per_fb = 1.e-3_default
    type(string_t) :: content
    logical :: found, closing
    call eio_lhef_read_init_10 (eio, data)
    SCAN_INIT_TAGS: do
      call eio%tag_generator%read (eio%cstream, found)
      if (found) then
        if (.not. eio%tag_generator%has_content) call err_generator

```

```

        call eio%tag_generator%read_content (eio%cstream, content, closing)
        call msg_message ("LHEF: Event file has been generated by " &
            // char (content) // " " &
            // char (eio%tag_generator%get_attribute (1)))
        cycle SCAN_INIT_TAGS
    end if
    call eio%tag_xsecinfo%read (eio%cstream, found)
    if (found) then
        if (eio%tag_xsecinfo%has_content) call err_xsecinfo
        cycle SCAN_INIT_TAGS
    end if
    call eio%tag_init%read_content (eio%cstream, content, closing)
    if (closing) then
        if (content /= "") call err_init
        exit SCAN_INIT_TAGS
    end if
end do SCAN_INIT_TAGS
data%n_evt = &
    read_ival (eio%tag_xsecinfo%get_attribute (1))
data%total_cross_section = &
    read_rval (eio%tag_xsecinfo%get_attribute (2)) / pb_per_fb
contains
    subroutine err_generator
        call msg_fatal ("LHEF: invalid generator tag")
    end subroutine err_generator
    subroutine err_xsecinfo
        call msg_fatal ("LHEF: invalid xsecinfo tag")
    end subroutine err_xsecinfo
    subroutine err_init
        call msg_fatal ("LHEF: syntax error after init tag")
    end subroutine err_init
end subroutine eio_lhef_read_init_20

```

This is additional event-specific information for the 2.0 format, after the HEP-EUP data. We can specify weights, starting from the master weight and adding alternative weights. The alternative weights are collected in a common tag.

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: write_event_20 => eio_lhef_write_event_20

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_write_event_20 (eio, event)
        class(eio_lhef_t), intent(in) :: eio
        class(generic_event_t), intent(in) :: event
        type(string_t) :: s
        integer :: i, u
        u = eio%unit
        if (eio%write_sqme_ref) then
            s = str (event%get_sqme_ref ())
            call eio%tag_sqme_ref%write (s, u); write (u, *)
        end if
        if (eio%write_sqme_prc) then
            s = str (event%get_sqme_prc ())
            call eio%tag_sqme_prc%write (s, u); write (u, *)
        end if
    end if

```

```

if (eio%n_alt > 0) then
  if (eio%write_sqme_alt) then
    s = str (event%get_sqme_alt(1))
    do i = 2, eio%n_alt
      s = s // " " // str (event%get_sqme_alt(i)); write (u, *)
    end do
    call eio%tag_sqme_alt(1)%write (s, u)
  end if
  s = str (event%get_weight_alt(1))
  do i = 2, eio%n_alt
    s = s // " " // str (event%get_weight_alt(i)); write (u, *)
  end do
  call eio%tag_wgts_alt(1)%write (s, u)
end if
end subroutine eio_lhef_write_event_20

```

Read extra event data. If there is a weight entry labeled `sqme_prc`, we take this as the squared matrix-element value (the new *reference* value `sqme_ref`). Other tags, including tags written by the above writer, are skipped.

```

<EIO LHEF: eio_lhef: TBP>+≡
  procedure :: read_event_20 => eio_lhef_read_event_20

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_read_event_20 (eio, event)
    class(eio_lhef_t), intent(inout) :: eio
    class(generic_event_t), intent(inout) :: event
    type(string_t) :: content
    logical :: found, closing
    SCAN_EVENT_TAGS: do
      call eio%tag_weight%read (eio%cstream, found)
      if (found) then
        if (.not. eio%tag_weight%has_content) call err_weight
        call eio%tag_weight%read_content (eio%cstream, content, closing)
        if (.not. closing) call err_weight
        if (eio%tag_weight%get_attribute (1) == "sqme_prc") then
          call event%set_sqme_ref (read_rval (content))
        end if
        cycle SCAN_EVENT_TAGS
      end if
      call eio%tag_event%read_content (eio%cstream, content, closing)
      if (closing) then
        if (content /= "") call err_event
        exit SCAN_EVENT_TAGS
      end if
    end do SCAN_EVENT_TAGS
  contains
    subroutine err_weight
      call msg_fatal ("LHEF: invalid weight tag in event record")
    end subroutine err_weight
    subroutine err_event
      call msg_fatal ("LHEF: syntax error after event tag")
    end subroutine err_event
  end subroutine eio_lhef_read_event_20

```

17.11.7 Version-Specific Code: 3.0

This is the init information for the 3.0 format, after the HEPRUP data. We have the following tags:

- **generator** Generator name and version.
- **xsecinfo** Cross section and weights data. We have the total cross section and number of events (assuming that the event file is intact), but information on minimum and maximum weights is not available before the file is complete. We just write the mandatory tags. (Note that the default values of the other tags describe a uniform unit weight, but we can determine most values only after the sample is complete.)
- **cutsinfo** This optional tag is too specific to represent the possibilities of WHIZARD, so we skip it.
- **procinfo** This optional tag is useful for giving details of NLO calculations. Skipped.
- **weightinfo** Determine the meaning of optional weights, whose values are given in the event record.

```

<EIO LHEF: eio lhef: TBP>+≡
  procedure :: write_init_30 => eio_lhef_write_init_30

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_write_init_30 (eio, data)
    class(eio_lhef_t), intent(in) :: eio
    type(event_sample_data_t), intent(in) :: data
    real(default), parameter :: pb_per_fb = 1.e-3_default
    integer :: u, i
    u = given_output_unit (eio%unit)
    call eio%tag_generator%write (u)
    write (u, "(A)", advance="no") "WHIZARD"
    call eio%tag_generator%close (u); write (u, *)
    call eio%tag_xsecinfo%write (u); write (u, *)
    if (eio%write_sqme_ref) then
      call eio%tag_sqme_ref%write (u); write (u, *)
    end if
    if (eio%write_sqme_prc) then
      call eio%tag_sqme_prc%write (u); write (u, *)
    end if
    if (eio%write_sqme_alt) then
      do i = 1, eio%n_alt
        call eio%tag_sqme_alt(i)%write (u); write (u, *)
      end do
    end if
    do i = 1, eio%n_alt
      call eio%tag_wgts_alt(i)%write (u); write (u, *)
    end do
  end subroutine eio_lhef_write_init_30

```

When reading the init block, we first call the 1.0 routine that fills HEPRUP. Then we consider the possible tags. Only the **generator** and **xsecinfo** tags are of interest. We skip everything else except for the closing tag.

```

(EIO LHEF: eio_lhef: TBP)+≡
  procedure :: read_init_30 => eio_lhef_read_init_30

(EIO LHEF: procedures)+≡
  subroutine eio_lhef_read_init_30 (eio, data)
    class(eio_lhef_t), intent(inout) :: eio
    type(event_sample_data_t), intent(out) :: data
    real(default), parameter :: pb_per_fb = 1.e-3_default
    type(string_t) :: content
    logical :: found, closing
    integer :: n_weightinfo
    call eio_lhef_read_init_10 (eio, data)
    n_weightinfo = 0
    eio%i_weight_sqme = 0
    SCAN_INIT_TAGS: do
      call eio%tag_generator%read (eio%cstream, found)
      if (found) then
        if (.not. eio%tag_generator%has_content) call err_generator
        call eio%tag_generator%read_content (eio%cstream, content, closing)
        call msg_message ("LHEF: Event file has been generated by " &
          // char (content) // " " &
          // char (eio%tag_generator%get_attribute (1)))
        cycle SCAN_INIT_TAGS
      end if
      call eio%tag_xsecinfo%read (eio%cstream, found)
      if (found) then
        if (eio%tag_xsecinfo%has_content) call err_xsecinfo
        cycle SCAN_INIT_TAGS
      end if
      call eio%tag_weightinfo%read (eio%cstream, found)
      if (found) then
        if (eio%tag_weightinfo%has_content) call err_xsecinfo
        n_weightinfo = n_weightinfo + 1
        if (eio%tag_weightinfo%get_attribute (1) == "sqme_prc") then
          eio%i_weight_sqme = n_weightinfo
        end if
        cycle SCAN_INIT_TAGS
      end if
      call eio%tag_init%read_content (eio%cstream, content, closing)
      if (closing) then
        if (content /= "") call err_init
        exit SCAN_INIT_TAGS
      end if
    end do SCAN_INIT_TAGS
    data%n_evt = &
      read_ival (eio%tag_xsecinfo%get_attribute (1))
    data%total_cross_section = &
      read_rval (eio%tag_xsecinfo%get_attribute (2)) / pb_per_fb
  contains
    subroutine err_generator
      call msg_fatal ("LHEF: invalid generator tag")
    end subroutine
  end subroutine

```



```

end subroutine err_generator
subroutine err_xsecinfo
  call msg_fatal ("LHEF: invalid xsecinfo tag")
end subroutine err_xsecinfo
subroutine err_init
  call msg_fatal ("LHEF: syntax error after init tag")
end subroutine err_init
end subroutine eio_lhef_read_init_30

```

This is additional event-specific information for the 3.0 format, after the HEP-EUP data. We can specify weights, starting from the master weight and adding alternative weights. The weight tags are already allocated, so we just have to transfer the weight values to strings, assemble them and write them to file. All weights are collected in a single tag.

Note: If efficiency turns out to be an issue, we may revert to traditional character buffer writing. However, we need to know the maximum length.

```

<EIO LHEF: eio_lhef: TBP>+≡
  procedure :: write_event_30 => eio_lhef_write_event_30

<EIO LHEF: procedures>+≡
  subroutine eio_lhef_write_event_30 (eio, event)
    class(eio_lhef_t), intent(in) :: eio
    class(generic_event_t), intent(in) :: event
    type(string_t) :: s
    integer :: u, i
    u = eio%unit
    s = ""
    if (eio%write_sqme_ref) then
      s = s // str (event%get_sqme_ref ()) // " "
    end if
    if (eio%write_sqme_prc) then
      s = s // str (event%get_sqme_prc ()) // " "
    end if
    if (eio%n_alt > 0) then
      if (eio%write_sqme_alt) then
        s = s // str (event%get_sqme_alt(1)) // " "
        do i = 2, eio%n_alt
          s = s // str (event%get_sqme_alt(i)) // " "
        end do
      end if
      s = s // str (event%get_weight_alt(1)) // " "
      do i = 2, eio%n_alt
        s = s // str (event%get_weight_alt(i)) // " "
      end do
    end if
    if (len_trim (s) > 0) then
      call eio%tag_weights%write (trim (s), u); write (u, *)
    end if
  end subroutine eio_lhef_write_event_30

```

Read extra event data. If there is a `weights` tag and if there was a `weightinfo` entry labeled `sqme_prc`, we extract the corresponding entry from the weights

string and store this as the event's squared matrix-element value. Other tags, including tags written by the above writer, are skipped.

```

<EIO LHEF: eio_lhef: TBP>+≡
    procedure :: read_event_30 => eio_lhef_read_event_30

<EIO LHEF: procedures>+≡
    subroutine eio_lhef_read_event_30 (eio, event)
        class(eio_lhef_t), intent(inout) :: eio
        class(generic_event_t), intent(inout) :: event
        type(string_t) :: content, string
        logical :: found, closing
        integer :: i
        SCAN_EVENT_TAGS: do
            call eio%tag_weights%read (eio%cstream, found)
            if (found) then
                if (.not. eio%tag_weights%has_content) call err_weights
                call eio%tag_weights%read_content (eio%cstream, content, closing)
                if (.not. closing) call err_weights
                if (eio%i_weight_sqme > 0) then
                    SCAN_WEIGHTS: do i = 1, eio%i_weight_sqme
                        call split (content, string, " ")
                        content = adjustl (content)
                        if (i == eio%i_weight_sqme) then
                            call event%set_sqme_ref (read_rval (string))
                            exit SCAN_WEIGHTS
                        end if
                    end do SCAN_WEIGHTS
                end if
            end if
            cycle SCAN_EVENT_TAGS
        end if
        call eio%tag_event%read_content (eio%cstream, content, closing)
        if (closing) then
            if (content /= "") call err_event
            exit SCAN_EVENT_TAGS
        end if
    end do SCAN_EVENT_TAGS
contains
    subroutine err_weights
        call msg_fatal ("LHEF: invalid weights tag in event record")
    end subroutine err_weights
    subroutine err_event
        call msg_fatal ("LHEF: syntax error after event tag")
    end subroutine err_event
end subroutine eio_lhef_read_event_30

```

17.11.8 Unit tests

```

<EIO LHEF: public>+≡
    public :: eio_lhef_test

<EIO LHEF: tests>≡
    subroutine eio_lhef_test (u, results)
        integer, intent(in) :: u

```

```

        type(test_results_t), intent(inout) :: results
    <EIO LHEF: execute tests>
end subroutine eio_lhef_test

```

Version 1.0 Output

We test the implementation of all I/O methods. We start with output according to version 1.0.

```

<EIO LHEF: execute tests>≡
    call test (eio_lhef_1, "eio_lhef_1", &
        "write version 1.0", &
        u, results)

<EIO LHEF: tests>+≡
    subroutine eio_lhef_1 (u)
        integer, intent(in) :: u
        class(generic_event_t), pointer :: event
        type(event_sample_data_t) :: data
        class(eio_t), allocatable :: eio
        type(string_t) :: sample
        integer :: u_file, iostat
        character(80) :: buffer

        write (u, "(A)")  "* Test output: eio_lhef_1"
        write (u, "(A)")  "* Purpose: generate an event and write weight to file"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize test process"

        call eio_prepare_test (event, unweighted = .false.)

        call data%init (1)
        data%n_evt = 1
        data%n_beam = 2
        data%unweighted = .true.
        data%norm_mode = NORM_UNIT
        data%pdg_beam = 25
        data%energy_beam = 500
        data%proc_num_id = [42]
        data%cross_section(1) = 100
        data%error(1) = 1
        data%total_cross_section = sum (data%cross_section)

        write (u, "(A)")
        write (u, "(A)")  "* Generate and write an event"
        write (u, "(A)")

        sample = "eio_lhef_1"

        allocate (eio_lhef_t :: eio)
        select type (eio)
        type is (eio_lhef_t)
            call eio%set_parameters ()

```

```

end select

call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // "." // eio%extension), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:21) == " <generator_version>") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_lhef_t :: eio)
select type (eio)
type is (eio_lhef_t)
  call eio%set_parameters ()
end select

select type (eio)
type is (eio_lhef_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lhef_1"

end subroutine eio_lhef_1

```

Version 2.0 Output

Version 2.0 has added a lot of options to the LHEF format. We implement some of them.

```
(EIO LHEF: execute tests)+≡
  call test (eio_lhef_2, "eio_lhef_2", &
    "write version 2.0", &
    u, results)

(EIO LHEF: tests)+≡
  subroutine eio_lhef_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: eio_lhef_2"
    write (u, "(A)")  "* Purpose: generate an event and write weight to file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

    call eio_prepare_test (event, unweighted = .false.)

    call data%init (1)
    data%unweighted = .false.
    data%norm_mode = NORM_SIGMA
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")
    write (u, "(A)")  "* Generate and write an event"
    write (u, "(A)")

    sample = "eio_lhef_2"

    allocate (eio_lhef_t :: eio)
    select type (eio)
    type is (eio_lhef_t)
      call eio%set_parameters (version = "2.0", write_sqme_prc = .true.)
    end select

    call eio%init_out (sample, data)
    call event%generate (1, [0._default, 0._default])
```

```

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // "." // eio%extension), &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat) buffer
  if (buffer(1:10) == "<generator") buffer = "[...]"
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lhef_2"

end subroutine eio_lhef_2

```

Version 3.0 Output

Version 3.0 is an update which removes some tags (which we didn't use anyway) and suggests a new treatment of weights.

```

<EIO LHEF: execute tests>+≡
  call test (eio_lhef_3, "eio_lhef_3", &
    "write version 3.0", &
    u, results)

<EIO LHEF: tests>+≡
subroutine eio_lhef_3 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat
  character(80) :: buffer

  write (u, "(A)")  "* Test output: eio_lhef_3"
  write (u, "(A)")  "* Purpose: generate an event and write weight to file"
  write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize test process"

call eio_prepare_test (event, unweighted = .false.)

call data%init (1)
data%unweighted = .false.
data%norm_mode = NORM_SIGMA
data%n_evt = 1
data%n_beam = 2
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_lhef_3"

allocate (eio_lhef_t :: eio)
select type (eio)
type is (eio_lhef_t)
    call eio%set_parameters (version = "3.0", write_sqme_prc = .true.)
end select

call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents:"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".lhe"), &
      action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat) buffer
    if (buffer(1:10) == "<generator") buffer = "[...]"
    if (iostat /= 0) exit
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```

```

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lhef_3"

end subroutine eio_lhef_3

```

Version 1.0 Input

Check input of a version-1.0 conforming LHEF file.

```

<EIO LHEF: execute tests>+≡
  call test (eio_lhef_4, "eio_lhef_4", &
    "read version 1.0", &
    u, results)

<EIO LHEF: tests>+≡
  subroutine eio_lhef_4 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: fallback_model
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat, i_prc

    write (u, "(A)")  "* Test output: eio_lhef_4"
    write (u, "(A)")  "* Purpose: read a LHEF 1.0 file"
    write (u, "(A)")

    write (u, "(A)")  "* Write a LHEF data file"
    write (u, "(A)")

    u_file = free_unit ()
    sample = "eio_lhef_4"
    open (u_file, file = char (sample // ".lhe"), &
      status = "replace", action = "readwrite")

    write (u_file, "(A)")  '<LesHouchesEvents version="1.0">'
    write (u_file, "(A)")  '<header>'
    write (u_file, "(A)")  '  <arbitrary_tag opt="foo">content</arbitrary_tag>'
    write (u_file, "(A)")  '  Text'
    write (u_file, "(A)")  '  <another_tag />'
    write (u_file, "(A)")  '</header>'
    write (u_file, "(A)")  '<init>'
    write (u_file, "(A)")  '  25 25  5.0000000000E+02  5.0000000000E+02 &
      & -1 -1 -1 -1 3 1'
    write (u_file, "(A)")  '  1.0000000000E-01  1.0000000000E-03 &
      & 1.0000000000E+00 42'
    write (u_file, "(A)")  '</init>'
    write (u_file, "(A)")  '<event>'
    write (u_file, "(A)")  '  4 42  3.0574068604E+08  1.0000000000E+03 &
      & -1.0000000000E+00 -1.0000000000E+00'
    write (u_file, "(A)")  '  25 -1 0 0 0 0  0.0000000000E+00  0.0000000000E+00 &

```



```

& 4.8412291828E+02 5.0000000000E+02 1.2500000000E+02 &
& 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") ' 25 -1 0 0 0 0 0.0000000000E+00 0.0000000000E+00 &
&-4.8412291828E+02 5.0000000000E+02 1.2500000000E+02 &
& 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") ' 25 1 1 2 0 0 -1.4960220911E+02 -4.6042825611E+02 &
& 0.0000000000E+00 5.0000000000E+02 1.2500000000E+02 &
& 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") ' 25 1 1 2 0 0 1.4960220911E+02 4.6042825611E+02 &
& 0.0000000000E+00 5.0000000000E+02 1.2500000000E+02 &
& 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") '</event>'
write (u_file, "(A)") '</LesHouchesEvents>'
close (u_file)

```

```

write (u, "(A)") "* Initialize test process"
write (u, "(A)")

```

```

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event, unweighted = .false.)

```

```

allocate (eio_lhef_t :: eio)
select type (eio)
type is (eio_lhef_t)
    call eio%set_parameters (recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

```

```

call data%init (1)
data%n_beam = 2
data%unweighted = .true.
data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)
write (u, *)

```

```

write (u, "(A)") "* Initialize and read header"
write (u, "(A)")

```

```

call eio%init_in (sample, data)
call eio%write (u)

```

```

write (u, *)

```

```

select type (eio)
type is (eio_lhef_t)
    call eio%tag_lhef%write (u); write (u, *)
end select

```

```

write (u, *)
call data%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_lhef_t)
  write (u, "(A,IO,A,IO)") "Found process #", i_prc, &
    " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)

call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,IO)") "iostat = ", iostat

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lhef_4"

end subroutine eio_lhef_4

```

Version 2.0 Input

Check input of a version-2.0 conforming LHEF file.

```

<EIO LHEF: execute tests>+≡
  call test (eio_lhef_5, "eio_lhef_5", &
    "read version 2.0", &
    u, results)

<EIO LHEF: tests>+≡
subroutine eio_lhef_5 (u)
  integer, intent(in) :: u
  class(model_data_t), pointer :: fallback_model
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample

```

```

integer :: u_file, iostat, i_prc

write (u, "(A)")  "* Test output: eio_lhef_5"
write (u, "(A)")  "* Purpose: read a LHEF 2.0 file"
write (u, "(A)")

write (u, "(A)")  "* Write a LHEF data file"
write (u, "(A)")

u_file = free_unit ()
sample = "eio_lhef_5"
open (u_file, file = char (sample // ".lhe"), &
      status = "replace", action = "readwrite")

write (u_file, "(A)")  '<LesHouchesEvents version="2.0">'
write (u_file, "(A)")  '<header>'
write (u_file, "(A)")  '</header>'
write (u_file, "(A)")  '<init>'
write (u_file, "(A)")  ' 25 25  5.0000000000E+02  5.0000000000E+02 &
      &-1 -1 -1 -1 4 1'
write (u_file, "(A)")  '  1.0000000000E-01  1.0000000000E-03 &
      & 0.0000000000E+00 42'
write (u_file, "(A)")  '<generator version="2.2.3">WHIZARD&
      &</generator>'
write (u_file, "(A)")  '<xsecinfo neve="1" totxsec="1.0000000000E-01" />'
write (u_file, "(A)")  '</init>'
write (u_file, "(A)")  '<event>'
write (u_file, "(A)")  ' 4 42  3.0574068604E+08  1.0000000000E+03 &
      &-1.0000000000E+00 -1.0000000000E+00'
write (u_file, "(A)")  ' 25 -1 0 0 0 0  0.0000000000E+00 &
      & 0.0000000000E+00 4.8412291828E+02  5.0000000000E+02 &
      & 1.2500000000E+02  0.0000000000E+00  9.0000000000E+00'
write (u_file, "(A)")  ' 25 -1 0 0 0 0  0.0000000000E+00 &
      & 0.0000000000E+00 -4.8412291828E+02  5.0000000000E+02 &
      & 1.2500000000E+02  0.0000000000E+00  9.0000000000E+00'
write (u_file, "(A)")  ' 25 1 1 2 0 0 -1.4960220911E+02 &
      &-4.6042825611E+02  0.0000000000E+00  5.0000000000E+02 &
      & 1.2500000000E+02  0.0000000000E+00  9.0000000000E+00'
write (u_file, "(A)")  ' 25 1 1 2 0 0  1.4960220911E+02 &
      & 4.6042825611E+02  0.0000000000E+00  5.0000000000E+02 &
      & 1.2500000000E+02  0.0000000000E+00  9.0000000000E+00'
write (u_file, "(A)")  '<weight name="sqme_prc">1.0000000000E+00</weight>'
write (u_file, "(A)")  '</event>'
write (u_file, "(A)")  '</LesHouchesEvents>'
close (u_file)

write (u, "(A)")  "* Initialize test process"
write (u, "(A)")

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event, unweighted = .false.)

allocate (eio_lhef_t :: eio)
select type (eio)

```

```

type is (eio_lhef_t)
    call eio%set_parameters (version = "2.0", recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call data%init (1)
data%unweighted = .false.
data%norm_mode = NORM_SIGMA
data%n_beam = 2
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)
write (u, *)

write (u, "(A)")  "* Initialize and read header"
write (u, "(A)")

call eio%init_in (sample, data)
call eio%write (u)

write (u, *)

select type (eio)
type is (eio_lhef_t)
    call eio%tag_lhef%write (u); write (u, *)
end select

write (u, *)
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_lhef_t)
    write (u, "(A,I0,A,I0)")  "Found process #", i_prc, &
        " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)

call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,I0)")  "iostat = ", iostat

```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lhef_5"

end subroutine eio_lhef_5

```

Version 3.0 Input

Check input of a version-3.0 conforming LHEF file.

```

<EIO LHEF: execute tests>+=
call test (eio_lhef_6, "eio_lhef_6", &
  "read version 3.0", &
  u, results)

<EIO LHEF: tests>+=
subroutine eio_lhef_6 (u)
  integer, intent(in) :: u
  class(model_data_t), pointer :: fallback_model
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat, i_prc

  write (u, "(A)")  "* Test output: eio_lhef_6"
  write (u, "(A)")  "* Purpose: read a LHEF 3.0 file"
  write (u, "(A)")

  write (u, "(A)")  "* Write a LHEF data file"
  write (u, "(A)")

  u_file = free_unit ()
  sample = "eio_lhef_6"
  open (u_file, file = char (sample // ".lhe"), &
    status = "replace", action = "readwrite")

  write (u_file, "(A)")  '<LesHouchesEvents version="3.0">'
  write (u_file, "(A)")  '<header>'
  write (u_file, "(A)")  '</header>'
  write (u_file, "(A)")  '<init>'
  write (u_file, "(A)")  ' 25 25 5.0000000000E+02 5.0000000000E+02 &
    &-1 -1 -1 -1 4 1'
  write (u_file, "(A)")  ' 1.0000000000E-01 1.0000000000E-03 &
    & 0.0000000000E+00 42'
  write (u_file, "(A)")  '<generator version="2.2.3">WHIZARD&
    &</generator>'

```

```

write (u_file, "(A)") '<xsecinfo neve="1" totxsec="1.0000000000E-01" />'
write (u_file, "(A)") '<weightinfo name="sqme_prc" />'
write (u_file, "(A)") '</init>'
write (u_file, "(A)") '<event>'
write (u_file, "(A)") ' 4 42 3.0574068604E+08 1.0000000000E+03 &
&-1.0000000000E+00 -1.0000000000E+00'
write (u_file, "(A)") ' 25 -1 0 0 0 0 0.0000000000E+00 &
& 0.0000000000E+00 4.8412291828E+02 5.0000000000E+02 &
& 1.2500000000E+02 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") ' 25 -1 0 0 0 0 0.0000000000E+00 &
& 0.0000000000E+00 -4.8412291828E+02 5.0000000000E+02 &
& 1.2500000000E+02 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") ' 25 1 1 2 0 0 -1.4960220911E+02 &
&-4.6042825611E+02 0.0000000000E+00 5.0000000000E+02 &
& 1.2500000000E+02 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") ' 25 1 1 2 0 0 1.4960220911E+02 &
& 4.6042825611E+02 0.0000000000E+00 5.0000000000E+02 &
& 1.2500000000E+02 0.0000000000E+00 9.0000000000E+00'
write (u_file, "(A)") '<weights>1.0000000000E+00</weights>'
write (u_file, "(A)") '</event>'
write (u_file, "(A)") '</LesHouchesEvents>'
close (u_file)

write (u, "(A)") "* Initialize test process"
write (u, "(A)")

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event, unweighted = .false.)

allocate (eio_lhef_t :: eio)
select type (eio)
type is (eio_lhef_t)
    call eio%set_parameters (version = "3.0", recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call data%init (1)
data%unweighted = .false.
data%norm_mode = NORM_SIGMA
data%n_beam = 2
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)
write (u, *)

write (u, "(A)") "* Initialize and read header"
write (u, "(A)")

call eio%init_in (sample, data)
call eio%write (u)

write (u, *)

```

```

select type (eio)
type is (eio_lhef_t)
  call eio%tag_lhef%write (u); write (u, *)
end select

write (u, *)
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_lhef_t)
  write (u, "(A,I0,A,I0)")  "Found process #", i_prc, &
    " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)

call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,I0)")  "iostat = ", iostat

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lhef_6"

end subroutine eio_lhef_6

```

17.12 STDHEP File Formats

Here, we implement the two existing STDHEP file formats, one based on the HEPUP/HEPEUP common blocks, the other based on the HEPEVT common block. The second one is actually the standard STDHEP format.

`<eio_stdhep.f90>`≡
<File header>

```

module eio_stdhep

    use kinds
    use io_units
    <Use strings>
    use string_utils
    use unit_tests
    use diagnostics

    use lorentz
    use model_data
    use particles
    use event_base
    use hep_common
    use hep_events
    use xdr_stdhep
    use eio_data
    use eio_base

    <Standard module head>

    <EIO stdhep: public>

    <EIO stdhep: types>

    <EIO stdhep: variables>

    contains

    <EIO stdhep: procedures>

    <EIO stdhep: tests>

end module eio_stdhep

```

17.12.1 Type

```

<EIO stdhep: public>≡
    public :: eio_stdhep_t

<EIO stdhep: types>≡
    type, abstract, extends (eio_t) :: eio_stdhep_t
        logical :: writing = .false.
        logical :: reading = .false.
        integer :: unit = 0
        logical :: keep_beams = .false.
        logical :: keep_remnants = .true.
        logical :: recover_beams = .false.
        logical :: use_alpha_s_from_file = .false.
        logical :: use_scale_from_file = .false.
        integer, dimension(:), allocatable :: proc_num_id
        integer(i64) :: n_events_expected = 0
    contains

```



```

    <EIO stdhep: eio stdhep: TBP>
end type eio_stdhep_t

<EIO stdhep: public>+≡
    public :: eio_stdhep_hepevt_t

<EIO stdhep: types>+≡
    type, extends (eio_stdhep_t) :: eio_stdhep_hepevt_t
end type eio_stdhep_hepevt_t

<EIO stdhep: public>+≡
    public :: eio_stdhep_hepeup_t

<EIO stdhep: types>+≡
    type, extends (eio_stdhep_t) :: eio_stdhep_hepeup_t
end type eio_stdhep_hepeup_t

```

17.12.2 Specific Methods

Set parameters that are specifically used with STDHEP file formats.

```

<EIO stdhep: eio stdhep: TBP>≡
    procedure :: set_parameters => eio_stdhep_set_parameters

<EIO stdhep: procedures>≡
    subroutine eio_stdhep_set_parameters (eio, &
        keep_beams, keep_remnants, recover_beams, use_alpha_s_from_file, &
        use_scale_from_file, extension)
        class(eio_stdhep_t), intent(inout) :: eio
        logical, intent(in), optional :: keep_beams
        logical, intent(in), optional :: keep_remnants
        logical, intent(in), optional :: recover_beams
        logical, intent(in), optional :: use_alpha_s_from_file
        logical, intent(in), optional :: use_scale_from_file
        type(string_t), intent(in), optional :: extension
        if (present (keep_beams)) eio%keep_beams = keep_beams
        if (present (keep_remnants)) eio%keep_remnants = keep_remnants
        if (present (recover_beams)) eio%recover_beams = recover_beams
        if (present (use_alpha_s_from_file)) &
            eio%use_alpha_s_from_file = use_alpha_s_from_file
        if (present (use_scale_from_file)) &
            eio%use_scale_from_file = use_scale_from_file
        if (present (extension)) then
            eio%extension = extension
        else
            select type (eio)
            type is (eio_stdhep_hepevt_t)
                eio%extension = "hep"
            type is (eio_stdhep_hepeup_t)
                eio%extension = "up.hep"
            end select
        end if
    end subroutine eio_stdhep_set_parameters

```

17.12.3 Common Methods

Output. This is not the actual event format, but a readable account of the current object status.

```

(EIO stdhep: eio stdhep: TBP)+≡
  procedure :: write => eio_stdhep_write

(EIO stdhep: procedures)+≡
  subroutine eio_stdhep_write (object, unit)
    class(eio_stdhep_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A)") "STDHEP event stream:"
    if (object%writing) then
      write (u, "(3x,A,A)") "Writing to file   = ", char (object%filename)
    else if (object%reading) then
      write (u, "(3x,A,A)") "Reading from file = ", char (object%filename)
    else
      write (u, "(3x,A)") "[closed]"
    end if
    write (u, "(3x,A,L1)") "Keep beams      = ", object%keep_beams
    write (u, "(3x,A,L1)") "Keep remnants   = ", object%keep_remnants
    write (u, "(3x,A,L1)") "Recover beams    = ", object%recover_beams
    write (u, "(3x,A,L1)") "Alpha_s from file = ", &
      object%use_alpha_s_from_file
    write (u, "(3x,A,L1)") "Scale from file  = ", &
      object%use_scale_from_file
    if (allocated (object%proc_num_id)) then
      write (u, "(3x,A)") "Numerical process IDs:"
      do i = 1, size (object%proc_num_id)
        write (u, "(5x,I0,': ',I0)") i, object%proc_num_id(i)
      end do
    end if
  end subroutine eio_stdhep_write

```

Finalizer: close any open file.

```

(EIO stdhep: eio stdhep: TBP)+≡
  procedure :: final => eio_stdhep_final

(EIO stdhep: procedures)+≡
  subroutine eio_stdhep_final (object)
    class(eio_stdhep_t), intent(inout) :: object
    if (allocated (object%proc_num_id)) deallocate (object%proc_num_id)
    if (object%writing) then
      write (msg_buffer, "(A,A,A)") "Events: closing STDHEP file '", &
        char (object%filename), "'"
      call msg_message ()
      call stdhep_write (200)
      call stdhep_end ()
      object%writing = .false.
    else if (object%reading) then
      write (msg_buffer, "(A,A,A)") "Events: closing STDHEP file '", &
        char (object%filename), "'"
      call msg_message ()
    end if
  end subroutine eio_stdhep_final

```

```

        object%reading = .false.
    end if
end subroutine eio_stdhep_final

```

Common initialization for input and output.

```

<EIO stdhep: eio stdhep: TBP>+≡
    procedure :: common_init => eio_stdhep_common_init

<EIO stdhep: procedures>+≡
    subroutine eio_stdhep_common_init (eio, sample, data, extension)
        class(eio_stdhep_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(in), optional :: data
        if (.not. present (data)) &
            call msg_bug ("STDHEP initialization: missing data")
        if (data%n_beam /= 2) &
            call msg_fatal ("STDHEP: defined for scattering processes only")
        if (present (extension)) then
            eio%extension = extension
        end if
        eio%sample = sample
        call eio%set_filename ()
        eio%unit = free_unit ()
        allocate (eio%proc_num_id (data%n_proc), source = data%proc_num_id)
    end subroutine eio_stdhep_common_init

```

Split event file: increment the counter, close the current file, open a new one. If the file needs a header, repeat it for the new file. (We assume that the common block contents are still intact.)

```

<EIO stdhep: eio stdhep: TBP>+≡
    procedure :: split_out => eio_stdhep_split_out

<EIO stdhep: procedures>+≡
    subroutine eio_stdhep_split_out (eio)
        class(eio_stdhep_t), intent(inout) :: eio
        if (eio%split) then
            eio%split_index = eio%split_index + 1
            call eio%set_filename ()
            write (msg_buffer, "(A,A,A)") "Events: writing to STDHEP file '", &
                char (eio%filename), "'"
            call msg_message ()
            call stdhep_write (200)
            call stdhep_end ()
            select type (eio)
            type is (eio_stdhep_hepeup_t)
                call stdhep_init_out (char (eio%filename), &
                    "WHIZARD <Version>", eio%n_events_expected)
                call stdhep_write (100)
                call stdhep_write (STDHEP_HEPRUP)
            type is (eio_stdhep_hepevt_t)
                call stdhep_init_out (char (eio%filename), &
                    "WHIZARD <Version>", eio%n_events_expected)
                call stdhep_write (100)

```

```

        end select
    end if
end subroutine eio_stdhep_split_out

```

Initialize event writing.

```

<EIO stdhep: eio stdhep: TBP>+≡
    procedure :: init_out => eio_stdhep_init_out
<EIO stdhep: procedures>+≡
    subroutine eio_stdhep_init_out (eio, sample, data, success, extension)
        class(eio_stdhep_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(in), optional :: data
        logical, intent(out), optional :: success
        integer :: i
        if (.not. present (data)) &
            call msg_bug ("STDHEP initialization: missing data")
        call eio%set_splitting (data)
        call eio%common_init (sample, data, extension)
        eio%n_events_expected = data%n_evt
        write (msg_buffer, "(A,A,A)") "Events: writing to STDHEP file '", &
            char (eio%filename), "'"
        call msg_message ()
        eio%writing = .true.
        select type (eio)
        type is (eio_stdhep_hepeup_t)
            call heprup_init &
                (data%pdg_beam, &
                 data%energy_beam, &
                 n_processes = data%n_proc, &
                 unweighted = data%unweighted, &
                 negative_weights = data%negative_weights)
            do i = 1, data%n_proc
                call heprup_set_process_parameters (i = i, &
                    process_id = data%proc_num_id(i), &
                    cross_section = data%cross_section(i), &
                    error = data%error(i))
            end do
            call stdhep_init_out (char (eio%filename), &
                "WHIZARD <Version>", eio%n_events_expected)
            call stdhep_write (100)
            call stdhep_write (STDHEP_HEPRUP)
        type is (eio_stdhep_hepevt_t)
            call stdhep_init_out (char (eio%filename), &
                "WHIZARD <Version>", eio%n_events_expected)
            call stdhep_write (100)
        end select
        if (present (success)) success = .true.
    end subroutine eio_stdhep_init_out

```

Initialize event reading.

```

<EIO stdhep: eio stdhep: TBP>+≡
    procedure :: init_in => eio_stdhep_init_in

```

```

<EIO stdhep: procedures>+≡
subroutine eio_stdhep_init_in (eio, sample, data, success, extension)
  class(eio_stdhep_t), intent(inout) :: eio
  type(string_t), intent(in) :: sample
  type(string_t), intent(in), optional :: extension
  type(event_sample_data_t), intent(inout), optional :: data
  logical, intent(out), optional :: success
  integer :: ilbl, lok
  logical :: exist
  call eio%common_init (sample, data, extension)
  write (msg_buffer, "(A,A,A)") "Events: reading from STDHEP file '", &
    char (eio%filename), "'"
  call msg_message ()
  inquire (file = char (eio%filename), exist = exist)
  if (.not. exist) call msg_fatal ("Events: STDHEP file not found.")
  eio%reading = .true.
  call stdhep_init_in (char (eio%filename), eio%n_events_expected)
  call stdhep_read (ilbl, lok)
  if (lok /= 0) then
    call stdhep_end ()
    write (msg_buffer, "(A)") "Events: STDHEP file appears to" // &
      " be empty."
    call msg_message ()
  end if
  if (ilbl == 100) then
    write (msg_buffer, "(A)") "Events: reading in STDHEP events"
    call msg_message ()
  end if
  if (present (success)) success = .false.
end subroutine eio_stdhep_init_in

```

Switch from input to output: reopen the file for reading.

```

<EIO stdhep: eio stdhep: TBP>+≡
  procedure :: switch_inout => eio_stdhep_switch_inout

<EIO stdhep: procedures>+≡
subroutine eio_stdhep_switch_inout (eio, success)
  class(eio_stdhep_t), intent(inout) :: eio
  logical, intent(out), optional :: success
  call msg_bug ("STDHEP: in-out switch not supported")
  if (present (success)) success = .false.
end subroutine eio_stdhep_switch_inout

```

Output an event. Write first the event indices, then weight and squared matrix element, then the particle set.

```

<EIO stdhep: eio stdhep: TBP>+≡
  procedure :: output => eio_stdhep_output

<EIO stdhep: procedures>+≡
subroutine eio_stdhep_output (eio, event, i_prc, reading, passed, pacify)
  class(eio_stdhep_t), intent(inout) :: eio
  class(generic_event_t), intent(in), target :: event
  integer, intent(in) :: i_prc
  logical, intent(in), optional :: reading, passed, pacify

```

```

if (present (passed)) then
  if (.not. passed) return
end if
if (eio%writing) then
  select type (eio)
  type is (eio_stdhep_hepeup_t)
    call hepeup_from_event (event, &
      process_index = eio%proc_num_id (i_prc), &
      keep_beams = eio%keep_beams, &
      keep_remnants = eio%keep_remnants)
    call stdhep_write (STDHEP_HEPEUP)
  type is (eio_stdhep_hepevt_t)
    call hepevt_from_event (event, &
      i_evt = event%get_index (), &
      keep_beams = eio%keep_beams, &
      keep_remnants = eio%keep_remnants)
    call stdhep_write (STDHEP_HEPEVT)
  end select
else
  call eio%write ()
  call msg_fatal ("STDHEP file is not open for writing")
end if
end subroutine eio_stdhep_output

```

Input an event. We do not allow to read in STDHEP files written via the HEPEVT common block as there is no control on the process ID.

```

<EIO stdhep: eio stdhep: TBP>+≡
  procedure :: input_i_prc => eio_stdhep_input_i_prc
  procedure :: input_event => eio_stdhep_input_event

<EIO stdhep: procedures>+≡
  subroutine eio_stdhep_input_i_prc (eio, i_prc, iostat)
    class(eio_stdhep_t), intent(inout) :: eio
    integer, intent(out) :: i_prc
    integer, intent(out) :: iostat
    integer :: i, ilbl, proc_num_id
    iostat = 0
    select type (eio)
    type is (eio_stdhep_hepevt_t)
      if (size (eio%proc_num_id) > 1) then
        call msg_fatal ("Events: only single processes allowed " // &
          "with the STDHEP HEPEVT format.")
      else
        proc_num_id = eio%proc_num_id (1)
        call stdhep_read (ilbl, lok)
      end if
    type is (eio_stdhep_hepeup_t)
      call stdhep_read (ilbl, lok)
      if (lok /= 0) call msg_error ("Events: STDHEP appears to be " // &
        "empty or corrupted.")
      if (ilbl == 12) then
        call stdhep_read (ilbl, lok)
      end if
      if (ilbl == 11) then

```

```

        proc_num_id = IDPRUP
    end if
end select
FIND_I_PRC: do i = 1, size (eio%proc_num_id)
    if (eio%proc_num_id(i) == proc_num_id) then
        i_prc = i
        exit FIND_I_PRC
    end if
end do FIND_I_PRC
if (i_prc == 0) call err_index
contains
subroutine err_index
    call msg_error ("STDHEP: reading events: undefined process ID " &
        // char (str (proc_num_id)) // ", aborting read")
    iostat = 1
end subroutine err_index
end subroutine eio_stdhep_input_i_prc

subroutine eio_stdhep_input_event (eio, event, iostat)
    class(eio_stdhep_t), intent(inout) :: eio
    class(generic_event_t), intent(inout), target :: event
    integer, intent(out) :: iostat
    call event%reset ()
    call event%select (1, 1, 1)
    call hepeup_to_event (event, eio%fallback_model, &
        recover_beams = eio%recover_beams, &
        use_alpha_s = eio%use_alpha_s_from_file, &
        use_scale = eio%use_scale_from_file)
end subroutine eio_stdhep_input_event

```

STDHEP specific routines.

<EIO stdhep: public>+≡

```

public :: stdhep_init_out
public :: stdhep_init_in
public :: stdhep_write
public :: stdhep_end

```

<EIO stdhep: procedures>+≡

```

subroutine stdhep_init_out (file, title, nevt)
    character(len=*), intent(in) :: file, title
    integer(i64), intent(in) :: nevt
    integer(i32) :: nevt32
    external stdxwinit, stdxwrt
    nevt32 = min (nevt, int (huge (1_i32), i64))
    call stdxwinit (file, title, nevt32, istr, lok)
end subroutine stdhep_init_out

subroutine stdhep_init_in (file, nevt)
    character(len=*), intent(in) :: file
    integer(i64), intent(out) :: nevt
    integer(i32) :: nevt32
    external stdxrinit, stdxrd
    call stdxrinit (file, nevt32, istr, lok)
    if (lok /= 0) call msg_fatal ("STDHEP: error in reading file '" // &

```

```

        file // "'.")
        nevt = int (nevt32, i64)
    end subroutine stdhep_init_in

    subroutine stdhep_write (ilbl)
        integer, intent(in) :: ilbl
        external stdxwrt
        call stdxwrt (ilbl, istr, lok)
    end subroutine stdhep_write

    subroutine stdhep_read (ilbl, lok)
        integer, intent(out) :: ilbl, lok
        external stdxrd
        call stdxrd (ilbl, istr, lok)
        if (lok /= 0) return
    end subroutine stdhep_read

    subroutine stdhep_end
        external stdxend
        call stdxend (istr)
    end subroutine stdhep_end

```

17.12.4 Variables

<EIO stdhep: variables>≡

```

integer, save :: istr, lok
integer, parameter :: &
    STDHEP_HEPEVT = 1, STDHEP_HEPEUP = 11, STDHEP_HEPRUP = 12

```

17.12.5 Unit tests

<EIO stdhep: public>+≡

```

public :: eio_stdhep_test

```

<EIO stdhep: tests>≡

```

subroutine eio_stdhep_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
<EIO stdhep: execute tests>
end subroutine eio_stdhep_test

```

Test I/O methods

We test the implementation of the STDHEP HEPEVT I/O method:

<EIO stdhep: execute tests>≡

```

call test (eio_stdhep_1, "eio_stdhep_1", &
    "read and write event contents, format [stdhep]", &
    u, results)

```



```

<EIO stdhep: tests>+≡
subroutine eio_stdhep_1 (u)
  integer, intent(in) :: u
  class(generic_event_t), pointer :: event
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  type(string_t) :: sample
  integer :: u_file, iostat
  character(215) :: buffer

  write (u, "(A)")  "* Test output: eio_stdhep_1"
  write (u, "(A)")  "* Purpose: generate an event in STDHEP HEPEVT format"
  write (u, "(A)")  "*           and write weight to file"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize test process"

  call eio_prepare_test (event)

  call data%init (1)
  data%n_evt = 1
  data%n_beam = 2
  data%pdg_beam = 25
  data%energy_beam = 500
  data%proc_num_id = [42]
  data%cross_section(1) = 100
  data%error(1) = 1
  data%total_cross_section = sum (data%cross_section)

  write (u, "(A)")
  write (u, "(A)")  "* Generate and write an event"
  write (u, "(A)")

  sample = "eio_stdhep_1"

  allocate (eio_stdhep_hepevt_t :: eio)
  select type (eio)
  type is (eio_stdhep_hepevt_t)
    call eio%set_parameters ()
  end select

  call eio%init_out (sample, data)
  call event%generate (1, [0._default, 0._default])
  call event%evaluate_expressions ()
  call event%pacify_particle_set ()

  call eio%output (event, i_prc = 1)
  call eio%write (u)
  call eio%final ()

  write (u, "(A)")
  write (u, "(A)")  "* Write STDHEP file contents to ASCII file"
  write (u, "(A)")

```

```

call write_stdhep_event &
    (sample // ".hep", var_str ("test_1.hep"), 1)

write (u, "(A)")
write (u, "(A)")  "* Read in ASCII contents of STDHEP file"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = "test_1.hep", &
    action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat)  buffer
    if (iostat /= 0) exit
    if (trim (buffer) == "") cycle
    if (buffer(1:18) == "    total blocks: ") &
        buffer = "    total blocks: [...]"
    if (buffer(1:25) == "    title: WHIZARD") &
        buffer = "    title: WHIZARD [version]"
    if (buffer(1:17) == "    date:") &
        buffer = "    date: [...]"
    if (buffer(1:17) == "    closing date:") &
        buffer = "    closing date: [...]"
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_stdhep_hepevt_t :: eio)

select type (eio)
type is (eio_stdhep_hepevt_t)
    call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_stdhep_1"

end subroutine eio_stdhep_1

```

We test the implementation of the STDHEP HEPEUP I/O method:

(EIO_stdhep: execute tests) +=

```

call test (eio_stdhep_2, "eio_stdhep_2", &
    "read and write event contents, format [stdhep]", &

```

```

        u, results)
<EIO stdhep: tests>+=
subroutine eio_stdhep_2 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(model_data_t), pointer :: fallback_model
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(215) :: buffer

    write (u, "(A)")  "* Test output: eio_stdhep_2"
    write (u, "(A)")  "*   Purpose: generate an event in STDHEP HEPEUP format"
    write (u, "(A)")  "*           and write weight to file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

    call eio_prepare_fallback_model (fallback_model)
    call eio_prepare_test (event, unweighted = .false.)

    call data%init (1)
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")
    write (u, "(A)")  "* Generate and write an event"
    write (u, "(A)")

    sample = "eio_stdhep_2"

    allocate (eio_stdhep_hepeup_t :: eio)
    select type (eio)
    type is (eio_stdhep_hepeup_t)
        call eio%set_parameters ()
    end select
    call eio%set_fallback_model (fallback_model)

    call eio%init_out (sample, data)
    call event%generate (1, [0._default, 0._default])
    call event%evaluate_expressions ()

    call eio%output (event, i_prc = 1)
    call eio%write (u)
    call eio%final ()

    write (u, "(A)")

```

```

write (u, "(A)")  "* Write STDHEP file contents to ASCII file"
write (u, "(A)")

call write_stdhep_event &
      (sample // ".up.hep", var_str ("test_2.hep"), 2)

write (u, "(A)")
write (u, "(A)")  "* Read in ASCII contents of STDHEP file"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = "test_2.hep", &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat)  buffer
  if (iostat /= 0) exit
  if (trim (buffer) == "") cycle
  if (buffer(1:18) == "    total blocks: ") &
    buffer = "    total blocks: [...]"
  if (buffer(1:25) == "          title: WHIZARD") &
    buffer = "          title: WHIZARD [version]"
  if (buffer(1:17) == "          date:") &
    buffer = "          date: [...]"
  if (buffer(1:17) == "    closing date:") &
    buffer = "    closing date: [...]"
  write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_stdhep_hepeup_t :: eio)

select type (eio)
type is (eio_stdhep_hepeup_t)
  call eio%set_parameters (keep_beams = .true.)
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_stdhep_2"

end subroutine eio_stdhep_2

```

Check input from a StdHep file, HEPEVT block.

```

<EIO stdhep: execute tests>+=
  call test (eio_stdhep_3, "eio_stdhep_3", &
    "read StdHep file, HEPEVT block", &
    u, results)

<EIO stdhep: tests>+=
  subroutine eio_stdhep_3 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: fallback_model
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat, i_prc

    write (u, "(A)")  "* Test output: eio_stdhep_3"
    write (u, "(A)")  "* Purpose: read a StdHep file, HEPEVT block"
    write (u, "(A)")

    write (u, "(A)")  "* Write a StdHep data file, HEPEVT block"
    write (u, "(A)")

    call eio_prepare_fallback_model (fallback_model)
    call eio_prepare_test (event)

    call data%init (1)
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")
    write (u, "(A)")  "* Generate and write an event"
    write (u, "(A)")

    sample = "eio_stdhep_3"

    allocate (eio_stdhep_hepevt_t :: eio)
    select type (eio)
    type is (eio_stdhep_hepevt_t)
      call eio%set_parameters ()
    end select
    call eio%set_fallback_model (fallback_model)

    call eio%init_out (sample, data)
    call event%generate (1, [0._default, 0._default])
    call event%evaluate_expressions ()

    call eio%output (event, i_prc = 1)
    call eio%write (u)
    call eio%final ()

```

```

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)
deallocate (eio)

write (u, "(A)")  "* Initialize test process"
write (u, "(A)")

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event, unweighted = .false.)

allocate (eio_stdhep_hepevt_t :: eio)
select type (eio)
type is (eio_stdhep_hepevt_t)
    call eio%set_parameters (recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call data%init (1)
data%n_beam = 2
data%unweighted = .true.
data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)
write (u, *)

write (u, "(A)")  "* Initialize"
write (u, "(A)")

call eio%init_in (sample, data)
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_stdhep_hepevt_t)
    write (u, "(A,I0,A,I0)")  "Found process #", i_prc, &
        " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)

call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

```

```

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,IO)") "iostat = ", iostat

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_stdhep_3"

end subroutine eio_stdhep_3

```

Check input from a StdHep file, HEPEVT block.

```

<EIO stdhep: execute tests>+≡
  call test (eio_stdhep_4, "eio_stdhep_4", &
    "read StdHep file, HEPRUP/HEPEUP block", &
    u, results)
<EIO stdhep: tests>+≡
  subroutine eio_stdhep_4 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: fallback_model
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat, i_prc

    write (u, "(A)")  "* Test output: eio_stdhep_3"
    write (u, "(A)")  "* Purpose: read a StdHep file, HEPRUP/HEPEUP block"
    write (u, "(A)")

    write (u, "(A)")  "* Write a StdHep data file, HEPRUP/HEPEUP block"
    write (u, "(A)")

    call eio_prepare_fallback_model (fallback_model)
    call eio_prepare_test (event)

    call data%init (1)
    data%n_evt = 1
    data%n_beam = 2
    data%pdg_beam = 25
    data%energy_beam = 500
    data%proc_num_id = [42]
    data%cross_section(1) = 100
    data%error(1) = 1
    data%total_cross_section = sum (data%cross_section)

    write (u, "(A)")
    write (u, "(A)")  "* Generate and write an event, HEPEUP/HEPRUP"

```

```

write (u, "(A)")

sample = "eio_stdhep_4"

allocate (eio_stdhep_hepeup_t :: eio)
select type (eio)
type is (eio_stdhep_hepeup_t)
    call eio%set_parameters ()
end select
call eio%set_fallback_model (fallback_model)

call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()
call event%pacify_particle_set ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)
deallocate (eio)

write (u, "(A)")  "* Initialize test process"
write (u, "(A)")

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event, unweighted = .false.)

allocate (eio_stdhep_hepeup_t :: eio)
select type (eio)
type is (eio_stdhep_hepeup_t)
    call eio%set_parameters (recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call data%init (1)
data%n_beam = 2
data%unweighted = .true.
data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)
write (u, *)

write (u, "(A)")  "* Initialize"
write (u, "(A)")

call eio%init_in (sample, data)
call eio%write (u)

write (u, "(A)")

```



```

write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_stdhep_hepeup_t)
  write (u, "(A,I0,A,I0)")  "Found process #", i_prc, &
    " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)

call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,I0)")  "iostat = ", iostat

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_stdhep_4"

end subroutine eio_stdhep_4

```

17.13 HepMC Output

The HepMC event record is standardized. It is an ASCII format. We try our best at using it for both input and output.

$\langle \text{eio_hepmc.f90} \rangle \equiv$
 $\langle \text{File header} \rangle$

```

module eio_hepmc

  use kinds
  use io_units
 $\langle \text{Use strings} \rangle$ 
  use string_utils
  use unit_tests
  use diagnostics
  use os_interface

```

```

    use lorentz
    use model_data
    use particles
    use subevents
    use event_base
    use hep_events
    use eio_data
    use eio_base
    use hepmc_interface

    <Standard module head>

    <EIO HepMC: public>

    <EIO HepMC: types>

    <EIO HepMC: interfaces>

contains

    <EIO HepMC: procedures>

    <EIO HepMC: tests>

end module eio_hepmc

```

17.13.1 Type

A type `hepmc_event` is introduced as container to store HepMC event data, particularly for splitting the reading into read out of the process index and the proper event data.

Note: the `keep_beams` flag is not supported. Beams will always be written.

```

<EIO HepMC: public>≡
    public :: eio_hepmc_t

<EIO HepMC: types>≡
    type, extends (eio_t) :: eio_hepmc_t
        logical :: writing = .false.
        logical :: reading = .false.
        ! logical :: keep_beams = .false.
        logical :: recover_beams = .false.
        logical :: use_alpha_s_from_file = .false.
        logical :: use_scale_from_file = .false.
        type(hepmc_iostream_t) :: iostream
        type(hepmc_event_t) :: hepmc_event
        integer, dimension(:), allocatable :: proc_num_id
    contains
        <EIO HepMC: eio_hepmc: TBP>
    end type eio_hepmc_t

```

17.13.2 Specific Methods

Set parameters that are specifically used with HepMC.

(EIO HepMC: eio hepmc: TBP)≡

```
procedure :: set_parameters => eio_hepmc_set_parameters
```

(EIO HepMC: procedures)≡

```
! subroutine eio_hepmc_set_parameters (eio, keep_beams, recover_beams, extension)
subroutine eio_hepmc_set_parameters &
    (eio, recover_beams, use_alpha_s_from_file, use_scale_from_file, &
    extension)
    class(eio_hepmc_t), intent(inout) :: eio
    logical, intent(in), optional :: recover_beams
    logical, intent(in), optional :: use_alpha_s_from_file
    logical, intent(in), optional :: use_scale_from_file
    type(string_t), intent(in), optional :: extension
    if (present (recover_beams)) eio%recover_beams = recover_beams
    if (present (use_alpha_s_from_file)) &
        eio%use_alpha_s_from_file = use_alpha_s_from_file
    if (present (use_scale_from_file)) &
        eio%use_scale_from_file = use_scale_from_file
    if (present (extension)) then
        eio%extension = extension
    else
        eio%extension = "hepmc"
    end if
end subroutine eio_hepmc_set_parameters
```

17.13.3 Common Methods

Output. This is not the actual event format, but a readable account of the current object status.

(EIO HepMC: eio hepmc: TBP)+≡

```
procedure :: write => eio_hepmc_write
```

(EIO HepMC: procedures)+≡

```
subroutine eio_hepmc_write (object, unit)
    class(eio_hepmc_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A)") "HepMC event stream:"
    if (object%writing) then
        write (u, "(3x,A,A)") "Writing to file   = ", char (object%filename)
    else if (object%reading) then
        write (u, "(3x,A,A)") "Reading from file = ", char (object%filename)
    else
        write (u, "(3x,A)") "[closed]"
    end if
    write (u, "(3x,A,L1)") "Recover beams      = ", object%recover_beams
    write (u, "(3x,A,L1)") "Alpha_s from file = ", &
        object%use_alpha_s_from_file
    write (u, "(3x,A,L1)") "Scale from file   = ", &
```

```

        object%use_scale_from_file
write (u, "(3x,A,A,A)")      "File extension    = '", &
    char (object%extension), "'"
if (allocated (object%proc_num_id)) then
    write (u, "(3x,A)") "Numerical process IDs:"
    do i = 1, size (object%proc_num_id)
        write (u, "(5x,I0,': ',I0)") i, object%proc_num_id(i)
    end do
end if
end subroutine eio_hepmc_write

```

Finalizer: close any open file.

(EIO HepMC: eio hepmc: TBP)+≡

```

    procedure :: final => eio_hepmc_final

```

(EIO HepMC: procedures)+≡

```

subroutine eio_hepmc_final (object)
class(eio_hepmc_t), intent(inout) :: object
if (allocated (object%proc_num_id)) deallocate (object%proc_num_id)
if (object%writing) then
    write (msg_buffer, "(A,A,A)") "Events: closing HepMC file '", &
        char (object%filename), "'"
    call msg_message ()
    call hepmc_iostream_close (object%iostream)
    object%writing = .false.
else if (object%reading) then
    write (msg_buffer, "(A,A,A)") "Events: closing HepMC file '", &
        char (object%filename), "'"
    call msg_message ()
    call hepmc_iostream_close (object%iostream)
    object%reading = .false.
end if
end subroutine eio_hepmc_final

```

Split event file: increment the counter, close the current file, open a new one.
If the file needs a header, repeat it for the new file.

(EIO HepMC: eio hepmc: TBP)+≡

```

    procedure :: split_out => eio_hepmc_split_out

```

(EIO HepMC: procedures)+≡

```

subroutine eio_hepmc_split_out (eio)
class(eio_hepmc_t), intent(inout) :: eio
if (eio%split) then
    eio%split_index = eio%split_index + 1
    call eio%set_filename ()
    write (msg_buffer, "(A,A,A)") "Events: writing to HepMC file '", &
        char (eio%filename), "'"
    call msg_message ()
    call hepmc_iostream_close (eio%iostream)
    call hepmc_iostream_open_out (eio%iostream, eio%filename)
end if
end subroutine eio_hepmc_split_out

```

Common initialization for input and output.

```

(EIO HepMC: eio hepmc: TBP)+≡
  procedure :: common_init => eio_hepmc_common_init

(EIO HepMC: procedures)+≡
  subroutine eio_hepmc_common_init (eio, sample, data, extension)
    class(eio_hepmc_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(string_t), intent(in), optional :: extension
    type(event_sample_data_t), intent(in), optional :: data
    if (.not. present (data)) &
      call msg_bug ("HepMC initialization: missing data")
    if (data%n_beam /= 2) &
      call msg_fatal ("HepMC: defined for scattering processes only")
    if (data%unweighted) then
      select case (data%norm_mode)
        case (NORM_UNIT)
          case default; call msg_fatal &
            ("HepMC: normalization for unweighted events must be '1'")
      end select
    else
      call msg_fatal ("HepMC: events must be unweighted")
    end if
    eio%sample = sample
    if (present (extension)) then
      eio%extension = extension
    end if
    call eio%set_filename ()
    allocate (eio%proc_num_id (data%n_proc), source = data%proc_num_id)
  end subroutine eio_hepmc_common_init

```

Initialize event writing.

```

(EIO HepMC: eio hepmc: TBP)+≡
  procedure :: init_out => eio_hepmc_init_out

(EIO HepMC: procedures)+≡
  subroutine eio_hepmc_init_out (eio, sample, data, success, extension)
    class(eio_hepmc_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(string_t), intent(in), optional :: extension
    type(event_sample_data_t), intent(in), optional :: data
    logical, intent(out), optional :: success
    call eio%set_splitting (data)
    call eio%common_init (sample, data, extension)
    write (msg_buffer, "(A,A,A)") "Events: writing to HepMC file '", &
      char (eio%filename), "'"
    call msg_message ()
    eio%writing = .true.
    call hepmc_iostream_open_out (eio%iostream, eio%filename)
    if (present (success)) success = .true.
  end subroutine eio_hepmc_init_out

```

Initialize event reading. For input, we do not (yet) support split event files.

```

(EIO HepMC: eio hepmc: TBP)+≡

```

```

    procedure :: init_in => eio_hepmc_init_in
<EIO HepMC: procedures>+≡
    subroutine eio_hepmc_init_in (eio, sample, data, success, extension)
        class(eio_hepmc_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(inout), optional :: data
        logical, intent(out), optional :: success
        logical :: exist
        eio%split = .false.
        call eio%common_init (sample, data, extension)
        write (msg_buffer, "(A,A,A)") "Events: reading from HepMC file '", &
            char (eio%filename), "'"
        call msg_message ()
        inquire (file = char (eio%filename), exist = exist)
        if (.not. exist) call msg_fatal ("Events: HepMC file not found.")
        eio%reading = .true.
        call hepmc_iostream_open_in (eio%iostream, eio%filename)
        if (present (success)) success = .true.
    end subroutine eio_hepmc_init_in

```

Switch from input to output: reopen the file for reading.

```

<EIO HepMC: eio hepmc: TBP>+≡
    procedure :: switch_inout => eio_hepmc_switch_inout
<EIO HepMC: procedures>+≡
    subroutine eio_hepmc_switch_inout (eio, success)
        class(eio_hepmc_t), intent(inout) :: eio
        logical, intent(out), optional :: success
        call msg_bug ("HepMC: in-out switch not supported")
        if (present (success)) success = .false.
    end subroutine eio_hepmc_switch_inout

```

Output an event to the allocated HepMC output stream.

```

<EIO HepMC: eio hepmc: TBP>+≡
    procedure :: output => eio_hepmc_output
<EIO HepMC: procedures>+≡
    subroutine eio_hepmc_output (eio, event, i_prc, reading, passed, pacify)
        class(eio_hepmc_t), intent(inout) :: eio
        class(generic_event_t), intent(in), target :: event
        integer, intent(in) :: i_prc
        logical, intent(in), optional :: reading, passed, pacify
        type(particle_set_t), pointer :: pset_ptr
        if (present (passed)) then
            if (.not. passed) return
        end if
        if (eio%writing) then
            pset_ptr => event%get_particle_set_ptr ()
            call hepmc_event_init (eio%hepmc_event, &
                proc_id = eio%proc_num_id (i_prc), &
                event_id = event%get_index ())
            call hepmc_event_from_particle_set (eio%hepmc_event, pset_ptr)

```

```

        call hepmc_event_set_scale (eio%hepmc_event, event%get_fac_scale ())
        call hepmc_event_set_alpha_qcd (eio%hepmc_event, event%get_alpha_s ())
        call hepmc_iostream_write_event (eio%iostream, eio%hepmc_event)
        call hepmc_event_final (eio%hepmc_event)
    else
        call eio%write ()
        call msg_fatal ("HepMC file is not open for writing")
    end if
end subroutine eio_hepmc_output

```

Input an event.

(EIO HepMC: eio hepmc: TBP)+≡

```

    procedure :: input_i_prc => eio_hepmc_input_i_prc
    procedure :: input_event => eio_hepmc_input_event

```

(EIO HepMC: procedures)+≡

```

subroutine eio_hepmc_input_i_prc (eio, i_prc, iostat)
    class(eio_hepmc_t), intent(inout) :: eio
    integer, intent(out) :: i_prc
    integer, intent(out) :: iostat
    logical :: ok
    integer :: i, proc_num_id
    iostat = 0
    call hepmc_event_init (eio%hepmc_event)
    call hepmc_iostream_read_event (eio%iostream, eio%hepmc_event, ok)
    proc_num_id = hepmc_event_get_process_id (eio%hepmc_event)
    if (.not. ok) then
        iostat = -1
        return
    end if
    i_prc = 0
    FIND_I_PRC: do i = 1, size (eio%proc_num_id)
        if (eio%proc_num_id(i) == proc_num_id) then
            i_prc = i
            exit FIND_I_PRC
        end if
    end do FIND_I_PRC
    if (i_prc == 0) call err_index
contains
    subroutine err_index
        call msg_error ("HepMC: reading events: undefined process ID " &
            // char (str (proc_num_id)) // ", aborting read")
        iostat = 1
    end subroutine err_index
end subroutine eio_hepmc_input_i_prc

subroutine eio_hepmc_input_event (eio, event, iostat)
    class(eio_hepmc_t), intent(inout) :: eio
    class(generic_event_t), intent(inout), target :: event
    integer, intent(out) :: iostat
    type(particle_set_t), pointer :: pset
    logical :: ok
    iostat = 0
    call event%reset ()

```

```

call event%select (1, 1, 1)
call hepmc_to_event (event, eio%hepmc_event, eio%fallback_model, &
    recover_beams = eio%recover_beams, &
    use_alpha_s = eio%use_alpha_s_from_file, &
    use_scale = eio%use_scale_from_file)
call hepmc_event_final (eio%hepmc_event)
end subroutine eio_hepmc_input_event

```

17.13.4 Unit tests

```

<EIO HepMC: public>+≡
public :: eio_hepmc_test

<EIO HepMC: tests>≡
subroutine eio_hepmc_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
<EIO HepMC: execute tests>
end subroutine eio_hepmc_test

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO HepMC: execute tests>≡
call test (eio_hepmc_1, "eio_hepmc_1", &
    "write event contents", &
    u, results)

<EIO HepMC: tests>+≡
subroutine eio_hepmc_1 (u)
    integer, intent(in) :: u
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat
    character(116) :: buffer

    write (u, "(A)")  "* Test output: eio_hepmc_1"
    write (u, "(A)")  "* Purpose: write a HepMC file"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize test process"

    call eio_prepare_test (event, unweighted=.false.)

    call data%init (1)
    data%n_beam = 2
    data%unweighted = .true.
    data%norm_mode = NORM_UNIT
    data%pdg_beam = 25
    data%energy_beam = 500

```



```

data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_hepmc_1"

allocate (eio_hepmc_t :: eio)
select type (eio)
type is (eio_hepmc_t)
    call eio%set_parameters ()
end select

call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* File contents (blanking out last two digits):"
write (u, "(A)")

u_file = free_unit ()
open (u_file, file = char (sample // ".hepmc"), &
      action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat)  buffer
    if (iostat /= 0) exit
    if (trim (buffer) == "") cycle
    if (buffer(1:14) == "HepMC::Version") cycle
    if (buffer(1:10) == "P 10001 25") &
        call buffer_blanker (buffer, 32, 55, 78)
    if (buffer(1:10) == "P 10002 25") &
        call buffer_blanker (buffer, 33, 56, 79)
    if (buffer(1:10) == "P 10003 25") &
        call buffer_blanker (buffer, 29, 53, 78, 101)
    if (buffer(1:10) == "P 10004 25") &
        call buffer_blanker (buffer, 28, 51, 76, 99)
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_hepmc_t :: eio)

```

```

select type (eio)
type is (eio_hepmc_t)
    call eio%set_parameters ()
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio_cleanup_test (event)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_hepmc_1"

contains

subroutine buffer_blanker (buf, pos1, pos2, pos3, pos4)
    character(len=*), intent(inout) :: buf
    integer, intent(in) :: pos1, pos2, pos3
    integer, intent(in), optional :: pos4
    type(string_t) :: line
    line = var_str (trim (buf))
    line = replace (line, pos1, "XX")
    line = replace (line, pos2, "XX")
    line = replace (line, pos3, "XX")
    if (present (pos4)) then
        line = replace (line, pos4, "XX")
    end if
    line = replace (line, "4999999999999", "5000000000000")
    buf = char (line)
end subroutine buffer_blanker

end subroutine eio_hepmc_1

```

Test also the reading of HepMC events.

```

<EIO HepMC: execute tests>+≡
    call test (eio_hepmc_2, "eio_hepmc_2", &
        "read event contents", &
        u, results)

<EIO HepMC: tests>+≡
subroutine eio_hepmc_2 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: fallback_model
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat, i_prc

    write (u, "(A)")  "* Test output: eio_hepmc_2"
    write (u, "(A)")  "* Purpose: read a HepMC event"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Write a HepMC data file"
write (u, "(A)")

u_file = free_unit ()
sample = "eio_hepmc_2"
open (u_file, file = char (sample // ".hepmc"), &
      status = "replace", action = "readwrite")

write (u_file, "(A)")  "HepMC::Version 2.06.09"
write (u_file, "(A)")  "HepMC::IO_GenEvent-START_EVENT_LISTING"
write (u_file, "(A)")  "E 0 -1 -1.0000000000000000e+00 &
&-1.0000000000000000e+00 &
&-1.0000000000000000e+00 42 0 1 10001 10002 0 0"
write (u_file, "(A)")  "U GEV MM"
write (u_file, "(A)")  "V -1 0 0 0 0 0 2 2 0"
write (u_file, "(A)")  "P 10001 25 0 0 4.8412291827592713e+02 &
&5.0000000000000000e+02 &
&1.2499999999999999e+02 3 0 0 -1 0"
write (u_file, "(A)")  "P 10002 25 0 0 -4.8412291827592713e+02 &
&5.0000000000000000e+02 &
&1.2499999999999999e+02 3 0 0 -1 0"
write (u_file, "(A)")  "P 10003 25 -1.4960220911365536e+02 &
&-4.6042825611414656e+02 &
&0 5.0000000000000000e+02 1.2500000000000000e+02 1 0 0 0 0"
write (u_file, "(A)")  "P 10004 25 1.4960220911365536e+02 &
&4.6042825611414656e+02 &
&0 5.0000000000000000e+02 1.2500000000000000e+02 1 0 0 0 0"
write (u_file, "(A)")  "HepMC::IO_GenEvent-END_EVENT_LISTING"
close (u_file)

write (u, "(A)")  "* Initialize test process"
write (u, "(A)")

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event, unweighted=.false.)

allocate (eio_hepmc_t :: eio)
select type (eio)
type is (eio_hepmc_t)
    call eio%set_parameters (recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call data%init (1)
data%n_beam = 2
data%unweighted = .true.
data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)

write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize"
write (u, "(A)")

call eio%init_in (sample, data)
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_hepmc_t)
  write (u, "(A,I0,A,I0)")  "Found process #", i_prc, &
    " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)

call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,I0)")  "iostat = ", iostat

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_hepmc_2"

end subroutine eio_hepmc_2

```

17.14 LCIO Output

The LCIO event record is standardized for the use with Linear e^+e^- colliders. It is a binary event format. We try our best at using it for both input and output.

```

<eio_lcio.f90>≡
  <File header>

```

```

module eio_lcio

```

```

    use kinds
    use io_units
    <Use strings>
    use string_utils
    use unit_tests
    use diagnostics
    use os_interface
    use lorentz
    use model_data
    use particles
    use subevents
    use event_base
    use hep_events
    use eio_data
    use eio_base
    use lcio_interface

    <Standard module head>

    <EIO LCIO: public>

    <EIO LCIO: types>

    <EIO LCIO: interfaces>

    contains

    <EIO LCIO: procedures>

    <EIO LCIO: tests>

    end module eio_lcio

```

17.14.1 Type

A type `lcio_event` is introduced as container to store LCIO event data, particularly for splitting the reading into read out of the process index and the proper event data.

Note: the `keep_beams` flag is not supported.

<EIO LCIO: public>≡

```
public :: eio_lcio_t
```

<EIO LCIO: types>≡

```

type, extends (eio_t) :: eio_lcio_t
  logical :: writing = .false.
  logical :: reading = .false.
  logical :: recover_beams = .false.
  logical :: use_alpha_s_from_file = .false.
  logical :: use_scale_from_file = .false.
  type(lcio_writer_t) :: lcio_writer
  type(lcio_reader_t) :: lcio_reader
  type(lcio_run_header_t) :: lcio_run_hdr
  type(lcio_event_t) :: lcio_event

```

```

integer, dimension(:), allocatable :: proc_num_id
contains
  <EIO LCIO: eio lcio: TBP>
end type eio_lcio_t

```

17.14.2 Specific Methods

Set parameters that are specifically used with LCIO.

```

<EIO LCIO: eio lcio: TBP>≡
  procedure :: set_parameters => eio_lcio_set_parameters

<EIO LCIO: procedures>≡
  subroutine eio_lcio_set_parameters &
    (eio, recover_beams, use_alpha_s_from_file, use_scale_from_file, &
     extension)
    class(eio_lcio_t), intent(inout) :: eio
    logical, intent(in), optional :: recover_beams
    logical, intent(in), optional :: use_alpha_s_from_file
    logical, intent(in), optional :: use_scale_from_file
    type(string_t), intent(in), optional :: extension
    if (present (recover_beams)) eio%recover_beams = recover_beams
    if (present (use_alpha_s_from_file)) &
      eio%use_alpha_s_from_file = use_alpha_s_from_file
    if (present (use_scale_from_file)) &
      eio%use_scale_from_file = use_scale_from_file
    if (present (extension)) then
      eio%extension = extension
    else
      eio%extension = "slcio"
    end if
  end subroutine eio_lcio_set_parameters

```

17.14.3 Common Methods

Output. This is not the actual event format, but a readable account of the current object status.

```

<EIO LCIO: eio lcio: TBP>+≡
  procedure :: write => eio_lcio_write

<EIO LCIO: procedures>+≡
  subroutine eio_lcio_write (object, unit)
    class(eio_lcio_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A)") "LCIO event stream:"
    if (object%writing) then
      write (u, "(3x,A,A)") "Writing to file  = ", char (object%filename)
    else if (object%reading) then
      write (u, "(3x,A,A)") "Reading from file = ", char (object%filename)
    else

```

```

        write (u, "(3x,A)" "[closed]"
    end if
    write (u, "(3x,A,L1)" "Recover beams      = ", object%recover_beams
    write (u, "(3x,A,L1)" "Alpha_s from file = ", &
        object%use_alpha_s_from_file
    write (u, "(3x,A,L1)" "Scale from file   = ", &
        object%use_scale_from_file
    write (u, "(3x,A,A,A)" "File extension   = '", &
        char (object%extension), "'")
    if (allocated (object%proc_num_id)) then
        write (u, "(3x,A)" "Numerical process IDs:"
        do i = 1, size (object%proc_num_id)
            write (u, "(5x,I0,': ',I0)" i, object%proc_num_id(i)
        end do
    end if
end subroutine eio_lcio_write

```

Finalizer: close any open file.

```

<EIO LCIO: eio lcio: TBP>+≡
    procedure :: final => eio_lcio_final

<EIO LCIO: procedures>+≡
    subroutine eio_lcio_final (object)
        class(eio_lcio_t), intent(inout) :: object
        if (allocated (object%proc_num_id)) deallocate (object%proc_num_id)
        if (object%writing) then
            write (msg_buffer, "(A,A,A)" "Events: closing LCIO file '", &
                char (object%filename), "'")
            call msg_message ()
            call lcio_writer_close (object%lcio_writer)
            object%writing = .false.
        else if (object%reading) then
            write (msg_buffer, "(A,A,A)" "Events: closing LCIO file '", &
                char (object%filename), "'")
            call msg_message ()
            call lcio_reader_close (object%lcio_reader)
            object%reading = .false.
        end if
    end subroutine eio_lcio_final

```

Split event file: increment the counter, close the current file, open a new one.

If the file needs a header, repeat it for the new file.

```

<EIO LCIO: eio lcio: TBP>+≡
    procedure :: split_out => eio_lcio_split_out

<EIO LCIO: procedures>+≡
    subroutine eio_lcio_split_out (eio)
        class(eio_lcio_t), intent(inout) :: eio
        if (eio%split) then
            eio%split_index = eio%split_index + 1
            call eio%set_filename ()
            write (msg_buffer, "(A,A,A)" "Events: writing to LCIO file '", &
                char (eio%filename), "'")
            call msg_message ()

```

```

        call lcio_writer_close (eio%lcio_writer)
        call lcio_writer_open_out (eio%lcio_writer, eio%filename)
    end if
end subroutine eio_lcio_split_out

```

Common initialization for input and output.

```

<EIO LCIO: eio lcio: TBP>+≡
    procedure :: common_init => eio_lcio_common_init

<EIO LCIO: procedures>+≡
    subroutine eio_lcio_common_init (eio, sample, data, extension)
        class(eio_lcio_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(in), optional :: data
        if (.not. present (data)) &
            call msg_bug ("LCIO initialization: missing data")
        if (data%n_beam /= 2) &
            call msg_fatal ("LCIO: defined for scattering processes only")
        if (data%unweighted) then
            select case (data%norm_mode)
            case (NORM_UNIT)
            case default; call msg_fatal &
                ("LCIO: normalization for unweighted events must be '1'")
            end select
        else
            call msg_fatal ("LCIO: events must be unweighted")
        end if
        eio%sample = sample
        if (present (extension)) then
            eio%extension = extension
        end if
        call eio%set_filename ()
        allocate (eio%proc_num_id (data%n_proc), source = data%proc_num_id)
    end subroutine eio_lcio_common_init

```

Initialize event writing.

```

<EIO LCIO: eio lcio: TBP>+≡
    procedure :: init_out => eio_lcio_init_out

<EIO LCIO: procedures>+≡
    subroutine eio_lcio_init_out (eio, sample, data, success, extension)
        class(eio_lcio_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(in), optional :: data
        logical, intent(out), optional :: success
        call eio%set_splitting (data)
        call eio%common_init (sample, data, extension)
        write (msg_buffer, "(A,A,A)" "Events: writing to LCIO file '", &
            char (eio%filename), "'")
        call msg_message ()
        eio%writing = .true.
        call lcio_writer_open_out (eio%lcio_writer, eio%filename)
    end subroutine eio_lcio_init_out

```



```

        call lcio_run_header_init (eio%lcio_run_hdr)
        call lcio_run_header_write (eio%lcio_writer, eio%lcio_run_hdr)
        if (present (success)) success = .true.
    end subroutine eio_lcio_init_out

```

Initialize event reading. For input, we do not (yet) support split event files.

(EIO LCIO: eio lcio: TBP)+≡

```

    procedure :: init_in => eio_lcio_init_in

```

(EIO LCIO: procedures)+≡

```

    subroutine eio_lcio_init_in (eio, sample, data, success, extension)
        class(eio_lcio_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(string_t), intent(in), optional :: extension
        type(event_sample_data_t), intent(inout), optional :: data
        logical, intent(out), optional :: success
        logical :: exist
        eio%split = .false.
        call eio%common_init (sample, data, extension)
        write (msg_buffer, "(A,A,A)") "Events: reading from LCIO file '", &
            char (eio%filename), "'"
        call msg_message ()
        inquire (file = char (eio%filename), exist = exist)
        if (.not. exist) call msg_fatal ("Events: LCIO file not found.")
        eio%reading = .true.
        call lcio_open_file (eio%lcio_reader, eio%filename)
        if (present (success)) success = .true.
    end subroutine eio_lcio_init_in

```

Switch from input to output: reopen the file for reading.

(EIO LCIO: eio lcio: TBP)+≡

```

    procedure :: switch_inout => eio_lcio_switch_inout

```

(EIO LCIO: procedures)+≡

```

    subroutine eio_lcio_switch_inout (eio, success)
        class(eio_lcio_t), intent(inout) :: eio
        logical, intent(out), optional :: success
        call msg_bug ("LCIO: in-out switch not supported")
        if (present (success)) success = .false.
    end subroutine eio_lcio_switch_inout

```

Output an event to the allocated LCIO writer.

(EIO LCIO: eio lcio: TBP)+≡

```

    procedure :: output => eio_lcio_output

```

(EIO LCIO: procedures)+≡

```

    subroutine eio_lcio_output (eio, event, i_prc, reading, passed, pacify)
        class(eio_lcio_t), intent(inout) :: eio
        class(generic_event_t), intent(in), target :: event
        integer, intent(in) :: i_prc
        logical, intent(in), optional :: reading, passed, pacify
        type(particle_set_t), pointer :: pset_ptr
        if (present (passed)) then
            if (.not. passed) return

```

```

end if
if (eio%writing) then
  pset_ptr => event%get_particle_set_ptr ()
  call lcio_event_init (eio%lcio_event, &
    proc_id = eio%proc_num_id (i_prc), &
    event_id = event%get_index ())
  call lcio_event_from_particle_set (eio%lcio_event, pset_ptr)
  call lcio_event_set_scale (eio%lcio_event, event%get_fac_scale ())
  call lcio_event_set_alpha_qcd (eio%lcio_event, event%get_alpha_s ())
  call lcio_event_write (eio%lcio_writer, eio%lcio_event)
  call lcio_event_final (eio%lcio_event)
else
  call eio%write ()
  call msg_fatal ("LCIO file is not open for writing")
end if
end subroutine eio_lcio_output

```

Input an event.

(EIO LCIO: eio lcio: TBP)+≡

```

procedure :: input_i_prc => eio_lcio_input_i_prc
procedure :: input_event => eio_lcio_input_event

```

(EIO LCIO: procedures)+≡

```

subroutine eio_lcio_input_i_prc (eio, i_prc, iostat)
  class(eio_lcio_t), intent(inout) :: eio
  integer, intent(out) :: i_prc
  integer, intent(out) :: iostat
  logical :: ok
  integer :: i, proc_num_id
  iostat = 0
  call lcio_read_event (eio%lcio_reader, eio%lcio_event, ok)
  if (.not. ok) then
    iostat = -1
    return
  end if
  proc_num_id = lcio_event_get_process_id (eio%lcio_event)
  i_prc = 0
  FIND_I_PRC: do i = 1, size (eio%proc_num_id)
    if (eio%proc_num_id(i) == proc_num_id) then
      i_prc = i
      exit FIND_I_PRC
    end if
  end do FIND_I_PRC
  if (i_prc == 0) call err_index
contains
  subroutine err_index
    call msg_error ("LCIO: reading events: undefined process ID " &
      // char (str (proc_num_id)) // ", aborting read")
    iostat = 1
  end subroutine err_index
end subroutine eio_lcio_input_i_prc

subroutine eio_lcio_input_event (eio, event, iostat)
  class(eio_lcio_t), intent(inout) :: eio

```

```

class(generic_event_t), intent(inout), target :: event
integer, intent(out) :: iostat
type(particle_set_t), pointer :: pset
logical :: ok
iostat = 0
call event%reset ()
call event%select (1, 1, 1)
call lcio_to_event (event, eio%lcio_event, eio%fallback_model, &
    recover_beams = eio%recover_beams, &
    use_alpha_s = eio%use_alpha_s_from_file, &
    use_scale = eio%use_scale_from_file)
call lcio_event_final (eio%lcio_event)
end subroutine eio_lcio_input_event

```

17.14.4 Unit tests

```

<EIO LCIO: public>+≡
    public :: eio_lcio_test

<EIO LCIO: tests>≡
    subroutine eio_lcio_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <EIO LCIO: execute tests>
    end subroutine eio_lcio_test

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO LCIO: execute tests>≡
    call test (eio_lcio_1, "eio_lcio_1", &
        "write event contents", &
        u, results)

<EIO LCIO: tests>+≡
    subroutine eio_lcio_1 (u)
        integer, intent(in) :: u
        class(generic_event_t), pointer :: event
        type(event_sample_data_t) :: data
        class(eio_t), allocatable :: eio
        type(particle_set_t), pointer :: pset_ptr
        type(string_t) :: sample
        integer :: u_file, iostat
        character(215) :: buffer

        write (u, "(A)")  "* Test output: eio_lcio_1"
        write (u, "(A)")  "* Purpose: write a LCIO file"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize test process"

        call eio_prepare_test (event)

```

```

call data%init (1)
data%n_beam = 2
data%unweighted = .true.
data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_lcio_1"

allocate (eio_lcio_t :: eio)
select type (eio)
type is (eio_lcio_t)
    call eio%set_parameters ()
end select

call eio%init_out (sample, data)

call event%generate (1, [0._default, 0._default])
call event%pacify_particle_set ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()

write (u, "(A)")
write (u, "(A)")  "* Reset data"
write (u, "(A)")

deallocate (eio)
allocate (eio_lcio_t :: eio)

select type (eio)
type is (eio_lcio_t)
    call eio%set_parameters ()
end select
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write LCIO file contents to ASCII file"
write (u, "(A)")

select type (eio)
type is (eio_lcio_t)
    call lcio_event_init (eio%lcio_event, &
        proc_id = 42, &

```

```

        event_id = event%get_index ()
        pset_ptr => event%get_particle_set_ptr ()
        call lcio_event_from_particle_set &
            (eio%lcio_event, pset_ptr)
        call write_lcio_event (eio%lcio_event, var_str ("test_file.slcio"))
        call lcio_event_final (eio%lcio_event)
    end select

    write (u, "(A)")
    write (u, "(A)")  "* Read in ASCII contents of LCIO file"
    write (u, "(A)")

    u_file = free_unit ()
    open (u_file, file = "test_file.slcio", &
        action = "read", status = "old")
    do
        read (u_file, "(A)", iostat = iostat)  buffer
        if (iostat /= 0) exit
        if (trim (buffer) == "") cycle
        if (buffer(1:12) == " - timestamp") cycle
        if (buffer(1:6) == " date:") cycle
        write (u, "(A)") trim (buffer)
    end do
    close (u_file)

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

    call eio_cleanup_test (event)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: eio_lcio_1"

end subroutine eio_lcio_1

```

Test also the reading of LCIO events.

```

<EIO LCIO: execute tests>+≡
    call test (eio_lcio_2, "eio_lcio_2", &
        "read event contents", &
        u, results)

<EIO LCIO: tests>+≡
subroutine eio_lcio_2 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: fallback_model
    class(generic_event_t), pointer :: event
    type(event_sample_data_t) :: data
    class(eio_t), allocatable :: eio
    type(string_t) :: sample
    integer :: u_file, iostat, i_prc

    write (u, "(A)")  "* Test output: eio_lcio_2"
    write (u, "(A)")  "* Purpose: read a LCIO event"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize test process"

call eio_prepare_fallback_model (fallback_model)
call eio_prepare_test (event)

call data%init (1)
data%n_beam = 2
data%unweighted = .true.
data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
data%cross_section(1) = 100
data%error(1) = 1
data%total_cross_section = sum (data%cross_section)

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_lcio_2"

allocate (eio_lcio_t :: eio)
select type (eio)
type is (eio_lcio_t)
    call eio%set_parameters (recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()
call event%pacify_particle_set ()

call eio%output (event, i_prc = 1)
call eio%write (u)
call eio%final ()
deallocate (eio)

write (u, "(A)")
write (u, "(A)")  "* Initialize"
write (u, "(A)")

allocate (eio_lcio_t :: eio)
select type (eio)
type is (eio_lcio_t)
    call eio%set_parameters (recover_beams = .false.)
end select
call eio%set_fallback_model (fallback_model)

call data%init (1)
data%n_beam = 2
data%unweighted = .true.

```

```

data%norm_mode = NORM_UNIT
data%pdg_beam = 25
data%energy_beam = 500
data%proc_num_id = [42]
call data%write (u)
write (u, *)

write (u, "(A)")  "* Initialize"
write (u, "(A)")

call eio%init_in (sample, data)
call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read event"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)

select type (eio)
type is (eio_lcio_t)
    write (u, "(A,I0,A,I0)")  "Found process #", i_prc, &
        " with ID = ", eio%proc_num_id(i_prc)
end select

call eio%input_event (event, iostat)
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Read closing"
write (u, "(A)")

call eio%input_i_prc (i_prc, iostat)
write (u, "(A,I0)")  "iostat = ", iostat

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()

call eio_cleanup_test (event)
call eio_cleanup_fallback_model (fallback_model)

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_lcio_2"

end subroutine eio_lcio_2

```

Chapter 18

Phase Space

The abstract representation of a type that parameterizes phase space, with methods for construction and evaluation.

phs_base Abstract phase-space representation.

A simple implementation:

phs_single Parameterize the phase space of a single particle, i.e., the solid angle. This is useful only for very restricted problems, but it avoids the complexity of a generic approach in those trivial cases.

The standard implementation is called *wood* phase space. It consists of several auxiliary modules and the actual implementation module.

mappings Generate invariant masses and decay angles from given random numbers (or the inverse operation). Each mapping pertains to a particular node in a phase-space tree. Different mappings account for uniform distributions, resonances, zero-mass behavior, and so on.

phs_trees Phase space parameterizations for scattering processes are defined recursively as if there was an initial particle decaying. This module sets up a representation in terms of abstract trees, where each node gets a unique binary number. Each tree is stored as an array of branches, where integers indicate the connections. This emulates pointers in a transparent way. Real pointers would also be possible, but seem to be less efficient for this particular case.

phs_forests The type defined by this module collects the decay trees corresponding to a given process and the applicable mappings. To set this up, a file is read which is either written by the user or by the **cascades** module functions. The module also contains the routines that evaluate phase space, i.e., generate momenta from random numbers and back.

cascades This module is a pseudo Feynman diagram generator with the particular purpose of finding the phase space parameterizations best suited for a given process. It uses a model file to set up the possible vertices, generates all possible diagrams, identifies resonances and singularities, and simplifies the list by merging equivalent diagrams and dropping irrelevant

ones. This process can be controlled at several points by user-defined parameters. Note that it depends on the particular values of particle masses, so it cannot be done before reading the input file.

phs_wood Make the functionality available in form of an implementation of the abstract phase-space type.

18.1 Abstract phase-space module

In this module we define an abstract base type (and a trivial test implementation) for multi-channel phase-space parameterizations.

```
<phs_base.f90>≡  
<File header>  
  
module phs_base  
  
  <Use kinds>  
  <Use strings>  
  use io_units  
  use constants, only: TWOPI, TWOPI4  
  use format_defs, only: FMT_19  
  use unit_tests  
  use diagnostics  
  use md5  
  use physics_defs  
  use lorentz  
  use model_data  
  use flavors  
  use sf_mappings  
  use sf_base  
  use process_constants  
  
  <Standard module head>  
  
  <PHS base: public>  
  
  <PHS base: types>  
  
  <PHS base: interfaces>  
  
  <PHS base: test types>  
  
  contains  
  
  <PHS base: procedures>  
  
  <PHS base: tests>  
  
end module phs_base
```

18.1.1 Phase-space channels

The kinematics configuration may generate multiple parameterizations of phase space. Some of those have specific properties, such as a resonance in the s channel.

Channel properties

This is the abstract type for the channel properties. We need them as a data transfer container, so everything is public and transparent.

```

<PHS base: public>≡
    public :: channel_prop_t

<PHS base: types>≡
    type, abstract :: channel_prop_t
    contains
        procedure (channel_prop_to_string), deferred :: to_string
        generic :: operator (==) => is_equal
        procedure (channel_eq), deferred :: is_equal
    end type channel_prop_t

<PHS base: interfaces>≡
    abstract interface
        function channel_prop_to_string (object) result (string)
            import
            class(channel_prop_t), intent(in) :: object
            type(string_t) :: string
        end function channel_prop_to_string
    end interface

<PHS base: interfaces>+≡
    abstract interface
        function channel_eq (prop1, prop2) result (flag)
            import
            class(channel_prop_t), intent(in) :: prop1, prop2
            logical :: flag
        end function channel_eq
    end interface

```

Here is a resonance as a channel property. Mass and width are stored here in physical units.

```

<PHS base: public>+≡
    public :: resonance_t

<PHS base: types>+≡
    type, extends (channel_prop_t) :: resonance_t
        real(default) :: mass = 0
        real(default) :: width = 0
    contains
        procedure :: to_string => resonance_to_string
        procedure :: is_equal => resonance_is_equal
    end type resonance_t

```

Print mass and width.

```

<PHS base: procedures>≡
    function resonance_to_string (object) result (string)
        class(resonance_t), intent(in) :: object
        type(string_t) :: string
        character(32) :: buffer
        string = "resonant: m ="
        write (buffer, "(" // FMT_19 // ")") object%mass
        string = string // trim (buffer) // " GeV, w ="
        write (buffer, "(" // FMT_19 // ")") object%width
    end function resonance_to_string

```

```

    string = string // trim (buffer) // " GeV"
end function resonance_to_string

```

Equality.

```

(PHS base: procedures)+≡
function resonance_is_equal (prop1, prop2) result (flag)
  class(resonance_t), intent(in) :: prop1
  class(channel_prop_t), intent(in) :: prop2
  logical :: flag
  select type (prop2)
  type is (resonance_t)
    flag = prop1%mass == prop2%mass .and. prop1%width == prop2%width
  class default
    flag = .false.
  end select
end function resonance_is_equal

```

This is the limiting case of a resonance, namely an on-shell particle. We just store the mass in physical units.

```

(PHS base: public)+≡
  public :: on_shell_t

(PHS base: types)+≡
  type, extends (channel_prop_t) :: on_shell_t
    real(default) :: mass = 0
  contains
    procedure :: to_string => on_shell_to_string
    procedure :: is_equal => on_shell_is_equal
  end type on_shell_t

```

Print mass and width.

```

(PHS base: procedures)+≡
function on_shell_to_string (object) result (string)
  class(on_shell_t), intent(in) :: object
  type(string_t) :: string
  character(32) :: buffer
  string = "on shell: m ="
  write (buffer, "(" // FMT_19 // ")") object%mass
  string = string // trim (buffer) // " GeV"
end function on_shell_to_string

```

Equality.

```

(PHS base: procedures)+≡
function on_shell_is_equal (prop1, prop2) result (flag)
  class(on_shell_t), intent(in) :: prop1
  class(channel_prop_t), intent(in) :: prop2
  logical :: flag
  select type (prop2)
  type is (on_shell_t)
    flag = prop1%mass == prop2%mass
  class default
    flag = .false.
  end select
end function on_shell_is_equal

```

```

        end select
    end function on_shell_is_equal

```

Channel equivalences

This type describes an equivalence. The current channel is equivalent to channel `c`. The equivalence involves a permutation `perm` of integration dimensions and, within each integration dimension, a mapping `mode`.

```

<PHS base: types>+≡
    type :: phs_equivalence_t
        integer :: c = 0
        integer, dimension(:), allocatable :: perm
        integer, dimension(:), allocatable :: mode
    contains
        <PHS base: phs equivalence: TBP>
    end type phs_equivalence_t

```

The mapping modes are

```

<PHS base: types>+≡
    integer, parameter, public :: &
        EQ_IDENTITY = 0, EQ_INVERT = 1, EQ_SYMMETRIC = 2, EQ_INVARIANT = 3

```

In particular, if a channel is equivalent to itself in the `EQ_SYMMETRIC` mode, the integrand can be assumed to be symmetric w.r.t. a reflection $x \rightarrow 1 - x$ of the corresponding integration variable.

These are the associated tags, for output:

```

<PHS base: types>+≡
    character, dimension(0:3), parameter :: TAG = ["+", "-", ":", "x"]

```

Write an equivalence.

```

<PHS base: phs equivalence: TBP>≡
    procedure :: write => phs_equivalence_write

<PHS base: procedures>+≡
    subroutine phs_equivalence_write (object, unit)
        class(phs_equivalence_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, j
        u = given_output_unit (unit)
        write (u, "(5x,'=',1x,I0,1x)", advance = "no") object%c
        if (allocated (object%perm)) then
            write (u, "(A)", advance = "no") "("
            do j = 1, size (object%perm)
                if (j > 1) write (u, "(1x)", advance = "no")
                write (u, "(I0,A1)", advance = "no") &
                    object%perm(j), TAG(object%mode(j))
            end do
            write (u, "(A)") ")"
        else
            write (u, "(A)")
        end if
    end subroutine

```

```
end subroutine phs_equivalence_write
```

Initialize an equivalence. This allocates the `perm` and `mode` arrays with equal size.

```
<PHS base: phs equivalence: TBP>+≡
  procedure :: init => phs_equivalence_init
<PHS base: procedures>+≡
  subroutine phs_equivalence_init (eq, n_dim)
    class(phs_equivalence_t), intent(out) :: eq
    integer, intent(in) :: n_dim
    allocate (eq%perm (n_dim), source = 0)
    allocate (eq%mode (n_dim), source = EQ_IDENTITY)
  end subroutine phs_equivalence_init
```

Channel objects

The channel entry holds (optionally) specific properties.

`sf_channel` is the structure-function channel that corresponds to this phase-space channel. The structure-function channel may be set up with a specific mapping that depends on the phase-space channel properties. (The default setting is to leave the properties empty.)

```
<PHS base: public>+≡
  public :: phs_channel_t
<PHS base: types>+≡
  type :: phs_channel_t
    class(channel_prop_t), allocatable :: prop
    integer :: sf_channel = 1
    type(phs_equivalence_t), dimension(:), allocatable :: eq
  contains
    <PHS base: phs channel: TBP>
  end type phs_channel_t
```

Output.

```
<PHS base: phs channel: TBP>≡
  procedure :: write => phs_channel_write
<PHS base: procedures>+≡
  subroutine phs_channel_write (object, unit)
    class(phs_channel_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, j
    u = given_output_unit (unit)
    write (u, "(1x,I0)", advance="no") object%sf_channel
    if (allocated (object%prop)) then
      write (u, "(1x,A)") char (object%prop%to_string ())
    else
      write (u, *)
    end if
    if (allocated (object%eq)) then
      do j = 1, size (object%eq)
```

```

        call object%eq(j)%write (u)
    end do
end if
end subroutine phs_channel_write

```

Identify the channel with an s-channel resonance.

```

<PHS base: phs channel: TBP>+≡
    procedure :: set_resonant => channel_set_resonant

<PHS base: procedures>+≡
    subroutine channel_set_resonant (channel, mass, width)
        class(phs_channel_t), intent(inout) :: channel
        real(default), intent(in) :: mass, width
        allocate (resonance_t :: channel%prop)
        select type (prop => channel%prop)
            type is (resonance_t)
                prop%mass = mass
                prop%width = width
            end select
    end subroutine channel_set_resonant

```

Identify the channel with an on-shell particle.

```

<PHS base: phs channel: TBP>+≡
    procedure :: set_on_shell => channel_set_on_shell

<PHS base: procedures>+≡
    subroutine channel_set_on_shell (channel, mass)
        class(phs_channel_t), intent(inout) :: channel
        real(default), intent(in) :: mass
        allocate (on_shell_t :: channel%prop)
        select type (prop => channel%prop)
            type is (on_shell_t)
                prop%mass = mass
            end select
    end subroutine channel_set_on_shell

```

18.1.2 Property collection

We can set up a list of all distinct channel properties for a given set of channels.

```

<PHS base: public>+≡
    public :: phs_channel_collection_t

<PHS base: types>+≡
    type :: prop_entry_t
        integer :: i = 0
        class(channel_prop_t), allocatable :: prop
        type(prop_entry_t), pointer :: next => null ()
    end type prop_entry_t

    type :: phs_channel_collection_t
        integer :: n = 0
        type(prop_entry_t), pointer :: first => null ()

```

```

contains
  <PHS base: phs channel collection: TBP>≡
end type phs_channel_collection_t

```

Finalizer for the list.

```

<PHS base: phs channel collection: TBP>≡
  procedure :: final => phs_channel_collection_final

<PHS base: procedures>+≡
  subroutine phs_channel_collection_final (object)
    class(phs_channel_collection_t), intent(inout) :: object
    type(prop_entry_t), pointer :: entry
    do while (associated (object%first))
      entry => object%first
      object%first => entry%next
      deallocate (entry)
    end do
  end subroutine phs_channel_collection_final

```

Output.

Note: eliminating the `string` auxiliary triggers an ICE in gfortran 4.7.2.

```

<PHS base: phs channel collection: TBP>+≡
  procedure :: write => phs_channel_collection_write

<PHS base: procedures>+≡
  subroutine phs_channel_collection_write (object, unit)
    class(phs_channel_collection_t), intent(in) :: object
    integer, intent(in), optional :: unit
    type(prop_entry_t), pointer :: entry
    type(string_t) :: string
    integer :: u
    u = given_output_unit (unit)
    entry => object%first
    do while (associated (entry))
      if (allocated (entry%prop)) then
        string = entry%prop%to_string ()
        write (u, "(1x,I0,1x,A)" entry%i, char (string))
      else
        write (u, "(1x,I0)" entry%i
      end if
      entry => entry%next
    end do
  end subroutine phs_channel_collection_write

```

Push a new property to the stack if it is not yet included. Simultaneously, set the `sf_channel` entry in the phase-space channel object to the index of the matching entry, or the new entry if there was no match.

```

<PHS base: phs channel collection: TBP>+≡
  procedure :: push => phs_channel_collection_push

<PHS base: procedures>+≡
  subroutine phs_channel_collection_push (coll, channel)
    class(phs_channel_collection_t), intent(inout) :: coll

```



```

type(phs_channel_t), intent(inout) :: channel
type(prop_entry_t), pointer :: entry, new
if (associated (coll%first)) then
    entry => coll%first
do
    if (allocated (entry%prop)) then
        if (allocated (channel%prop)) then
            if (entry%prop == channel%prop) then
                channel%sf_channel = entry%i
                return
            end if
        end if
    else if (.not. allocated (channel%prop)) then
        channel%sf_channel = entry%i
        return
    end if
    if (associated (entry%next)) then
        entry => entry%next
    else
        exit
    end if
end do
allocate (new)
entry%next => new
else
    allocate (new)
    coll%first => new
end if
coll%n = coll%n + 1
new%i = coll%n
channel%sf_channel = new%i
if (allocated (channel%prop)) then
    allocate (new%prop, source = channel%prop)
end if
end subroutine phs_channel_collection_push

```

Return the number of collected distinct channels.

```

(PHS base: phs channel collection: TBP)+≡
    procedure :: get_n => phs_channel_collection_get_n

(PHS base: procedures)+≡
    function phs_channel_collection_get_n (coll) result (n)
        class(phs_channel_collection_t), intent(in) :: coll
        integer :: n
        n = coll%n
    end function phs_channel_collection_get_n

```

Return a specific channel (property object).

```

(PHS base: phs channel collection: TBP)+≡
    procedure :: get_entry => phs_channel_collection_get_entry

(PHS base: procedures)+≡
    subroutine phs_channel_collection_get_entry (coll, i, prop)
        class(phs_channel_collection_t), intent(in) :: coll

```

```

integer, intent(in) :: i
class(channel_prop_t), intent(out), allocatable :: prop
type(prop_entry_t), pointer :: entry
integer :: k
if (i > 0 .and. i <= coll%n) then
  entry => coll%first
  do k = 2, i
    entry => entry%next
  end do
  if (allocated (entry%prop)) then
    if (allocated (prop)) deallocate (prop)
    allocate (prop, source = entry%prop)
  end if
else
  call msg_bug ("PHS channel collection: get entry: illegal index")
end if
end subroutine phs_channel_collection_get_entry

```

18.1.3 Kinematics configuration

Here, we store the universal information that is specifically relevant for phase-space generation. It is a subset of the process data, supplemented by basic information on phase-space parameterization channels.

A concrete implementation will contain more data, that describe the phase space in detail.

MD5 sums: the phase space setup depends on the process, it depends on the model parameters (the masses, that is), and on the configuration parameters. (It doesn't depend on the QCD setup.)

```

<PHS base: public>+≡
  public :: phs_config_t

<PHS base: types>+≡
  type, abstract :: phs_config_t
    ! private
    type(string_t) :: id
    integer :: n_in = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    integer :: n_state = 0
    integer :: n_par = 0
    integer :: n_channel = 0
    real(default) :: sqrts = 0
    logical :: sqrts_fixed = .true.
    logical :: cm_frame = .true.
    logical :: azimuthal_dependence = .false.
    integer, dimension(:), allocatable :: dim_flat
    logical :: provides_equivalences = .false.
    logical :: provides_chains = .false.
    logical :: vis_channels = .false.
    integer, dimension(:), allocatable :: chain
    class(model_data_t), pointer :: model => null ()
    type(flavor_t), dimension(:,:), allocatable :: flv

```

```

type(phs_channel_t), dimension(:), allocatable :: channel
character(32) :: md5sum_process = ""
character(32) :: md5sum_model_par = ""
character(32) :: md5sum_phs_config = ""
integer :: nlo_type
contains
  <PHS base: phs config: TBP>
end type phs_config_t

```

Finalizer, deferred.

```

<PHS base: phs config: TBP>≡
  procedure (phs_config_final), deferred :: final
<PHS base: interfaces>+≡
  abstract interface
    subroutine phs_config_final (object)
      import
      class(phs_config_t), intent(inout) :: object
    end subroutine phs_config_final
  end interface

```

Output. We provide an implementation for the output of the base-type contents and an interface for the actual write method.

```

<PHS base: phs config: TBP>+≡
  procedure (phs_config_write), deferred :: write
  procedure :: base_write => phs_config_write
<PHS base: procedures>+≡
  subroutine phs_config_write (object, unit)
    class(phs_config_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i, j
    integer :: n_tot_flv
    n_tot_flv = object%n_tot
    u = given_output_unit (unit)
    write (u, "(3x,A,A,A)") "ID          = '", char (object%id), "'"
    write (u, "(3x,A,I0)") "n_in       = ", object%n_in
    write (u, "(3x,A,I0)") "n_out      = ", object%n_out
    write (u, "(3x,A,I0)") "n_tot      = ", object%n_tot
    write (u, "(3x,A,I0)") "n_state    = ", object%n_state
    write (u, "(3x,A,I0)") "n_par      = ", object%n_par
    write (u, "(3x,A,I0)") "n_channel  = ", object%n_channel
    write (u, "(3x,A," // FMT_19 // ")") "sqrts      = ", object%sqrts
    write (u, "(3x,A,L1)") "s_fixed    = ", object%sqrts_fixed
    write (u, "(3x,A,L1)") "cm_frame   = ", object%cm_frame
    write (u, "(3x,A,L1)") "azim.dep.  = ", object%azimuthal_dependence
    if (allocated (object%dim_flat)) then
      write (u, "(3x,A,I0)") "flat dim. = ", object%dim_flat
    end if
    write (u, "(1x,A)") "Flavor combinations:"
    do i = 1, object%n_state
      write (u, "(3x,I0,':')", advance="no") i
      !
      do j = 1, object%n_tot
        do j = 1, n_tot_flv

```

```

        write (u, "(1x,A)", advance="no") char (object%flv(j,i)%get_name ())
    end do
    write (u, *)
end do
if (allocated (object%channel)) then
    write (u, "(1x,A)") "Phase-space / structure-function channels:"
    do i = 1, object%n_channel
        write (u, "(3x,I0,':')", advance="no") i
        call object%channel(i)%write (u)
    end do
end if
if (object%md5sum_process /= "") then
    write (u, "(3x,A,A,A)") "MD5 sum (process)      = '", &
        object%md5sum_process, "'"
end if
if (object%md5sum_model_par /= "") then
    write (u, "(3x,A,A,A)") "MD5 sum (model par)   = '", &
        object%md5sum_model_par, "'"
end if
if (object%md5sum_phs_config /= "") then
    write (u, "(3x,A,A,A)") "MD5 sum (phs config) = '", &
        object%md5sum_phs_config, "'"
end if
end subroutine phs_config_write

```

Similarly, a basic initializer and an interface. The model pointer is taken as an argument; we may verify that this has the expected model name.

The intent is *inout*. We want to be able to set parameters in advance.

(PHS base: phs config: TBP)+≡

```
procedure :: init => phs_config_init
```

(PHS base: procedures)+≡

```

subroutine phs_config_init (phs_config, data, model)
    class(phs_config_t), intent(inout) :: phs_config
    type(process_constants_t), intent(in) :: data
    class(model_data_t), intent(in), target :: model
    integer :: i, j
    phs_config%id = data%id
    phs_config%n_in = data%n_in
    phs_config%n_out = data%n_out
    phs_config%n_tot = data%n_in + data%n_out
    phs_config%n_state = data%n_flv
    if (data%model_name == model%get_name ()) then
        phs_config%model => model
    else
        call msg_bug ("phs_config_init: model name mismatch")
    end if
    allocate (phs_config%flv (phs_config%n_tot, phs_config%n_state))
    do i = 1, phs_config%n_state
        do j = 1, phs_config%n_tot
            call phs_config%flv(j,i)%init (data%flv_state(j,i), &
                phs_config%model)
        end do
    end do
end do

```

```

    phs_config%md5sum_process = data%md5sum
end subroutine phs_config_init

```

This procedure should complete the phase-space configuration. We need the `sqrts` value as overall scale, which is known only after the beams have been defined. The procedure should determine the number of channels, their properties (if any), and allocate and fill the `channel` array accordingly.

```

<PHS base: phs config: TBP>+≡
    procedure (phs_config_configure), deferred :: configure

<PHS base: interfaces>+≡
    abstract interface
        subroutine phs_config_configure (phs_config, sqrts, &
            sqrts_fixed, cm_frame, azimuthal_dependence, rebuild, ignore_mismatch, &
            nlo_type)
            import
            class(phs_config_t), intent(inout) :: phs_config
            real(default), intent(in) :: sqrts
            logical, intent(in), optional :: sqrts_fixed
            logical, intent(in), optional :: cm_frame
            logical, intent(in), optional :: azimuthal_dependence
            logical, intent(in), optional :: rebuild
            logical, intent(in), optional :: ignore_mismatch
            integer, intent(inout), optional :: nlo_type
        end subroutine phs_config_configure
    end interface

```

Manually assign structure-function channel indices to the phase-space channel objects. (Used by a test routine.)

```

<PHS base: phs config: TBP>+≡
    procedure :: set_sf_channel => phs_config_set_sf_channel

<PHS base: procedures>+≡
    subroutine phs_config_set_sf_channel (phs_config, sf_channel)
        class(phs_config_t), intent(inout) :: phs_config
        integer, dimension(:), intent(in) :: sf_channel
        phs_config%channel%sf_channel = sf_channel
    end subroutine phs_config_set_sf_channel

```

Collect new channels not yet in the collection from this phase-space configuration object. At the same time, assign structure-function channels.

```

<PHS base: phs config: TBP>+≡
    procedure :: collect_channels => phs_config_collect_channels

<PHS base: procedures>+≡
    subroutine phs_config_collect_channels (phs_config, coll)
        class(phs_config_t), intent(inout) :: phs_config
        type(phs_channel_collection_t), intent(inout) :: coll
        integer :: c
        do c = 1, phs_config%n_channel
            call coll%push (phs_config%channel(c))
        end do
    end subroutine phs_config_collect_channels

```

Compute the MD5 sum. We abuse the `write` method. In type implementations, `write` should only display information that is relevant for the MD5 sum. The data include the process MD5 sum which is taken from the process constants, and the MD5 sum of the model parameters. This may change, so it is computed here.

```

<PHS base: phs config: TBP>+≡
  procedure :: compute_md5sum => phs_config_compute_md5sum

<PHS base: procedures>+≡
  subroutine phs_config_compute_md5sum (phs_config)
    class(phs_config_t), intent(inout) :: phs_config
    integer :: u
    phs_config%md5sum_model_par = phs_config%model%get_parameters_md5sum ()
    phs_config%md5sum_phs_config = ""
    u = free_unit ()
    open (u, status = "scratch", action = "readwrite")
    call phs_config%write (u)
    rewind (u)
    phs_config%md5sum_phs_config = md5sum (u)
    close (u)
  end subroutine phs_config_compute_md5sum

```

Print an informative message after phase-space configuration.

```

<PHS base: phs config: TBP>+≡
  procedure (phs_startup_message), deferred :: startup_message
  procedure :: base_startup_message => phs_startup_message

<PHS base: procedures>+≡
  subroutine phs_startup_message (phs_config, unit)
    class(phs_config_t), intent(in) :: phs_config
    integer, intent(in), optional :: unit
    write (msg_buffer, "(A,3(1x,I0,1x,A))") &
      "Phase space:", &
      phs_config%n_channel, "channels,", &
      phs_config%n_par, "dimensions"
    call msg_message (unit = unit)
  end subroutine phs_startup_message

```

This procedure should be implemented such that the phase-space configuration object allocates a phase-space instance of matching type.

```

<PHS base: phs config: TBP>+≡
  procedure (phs_config_allocate_instance), nopass, deferred :: &
    allocate_instance

<PHS base: interfaces>+≡
  abstract interface
    subroutine phs_config_allocate_instance (phs)
      import
      class(phs_t), intent(inout), pointer :: phs
    end subroutine phs_config_allocate_instance
  end interface

```

18.1.4 Extract data

Return the number of MC input parameters.

```
<PHS base: phs config: TBP>+≡
  procedure :: get_n_par => phs_config_get_n_par

<PHS base: procedures>+≡
  function phs_config_get_n_par (phs_config) result (n)
    class(phs_config_t), intent(in) :: phs_config
    integer :: n
    n = phs_config%n_par
  end function phs_config_get_n_par
```

Return dimensions (parameter indices) for which the phase-space dimension is flat, so integration and event generation can be simplified.

```
<PHS base: phs config: TBP>+≡
  procedure :: get_flat_dimensions => phs_config_get_flat_dimensions

<PHS base: procedures>+≡
  function phs_config_get_flat_dimensions (phs_config) result (dim_flat)
    class(phs_config_t), intent(in) :: phs_config
    integer, dimension(:), allocatable :: dim_flat
    if (allocated (phs_config%dim_flat)) then
      allocate (dim_flat (size (phs_config%dim_flat)))
      dim_flat = phs_config%dim_flat
    else
      allocate (dim_flat (0))
    end if
  end function phs_config_get_flat_dimensions
```

Return the number of phase-space channels.

```
<PHS base: phs config: TBP>+≡
  procedure :: get_n_channel => phs_config_get_n_channel

<PHS base: procedures>+≡
  function phs_config_get_n_channel (phs_config) result (n)
    class(phs_config_t), intent(in) :: phs_config
    integer :: n
    n = phs_config%n_channel
  end function phs_config_get_n_channel
```

Return the structure-function channel that corresponds to the phase-space channel c. If the channel array is not allocated (which happens if there is no structure function), return zero.

```
<PHS base: phs config: TBP>+≡
  procedure :: get_sf_channel => phs_config_get_sf_channel

<PHS base: procedures>+≡
  function phs_config_get_sf_channel (phs_config, c) result (c_sf)
    class(phs_config_t), intent(in) :: phs_config
    integer, intent(in) :: c
    integer :: c_sf
    if (allocated (phs_config%channel)) then
      c_sf = phs_config%channel(c)%sf_channel
    end if
  end function phs_config_get_sf_channel
```

```

    else
        c_sf = 0
    end if
end function phs_config_get_sf_channel

```

Return the mass(es) of the incoming particle(s). We take the first flavor combination in the array, assuming that masses must be degenerate among flavors.

```

<PHS base: phs config: TBP>+≡
    procedure :: get_masses_in => phs_config_get_masses_in

<PHS base: procedures>+≡
    subroutine phs_config_get_masses_in (phs_config, m)
        class(phs_config_t), intent(in) :: phs_config
        real(default), dimension(:), intent(out) :: m
        integer :: i
        do i = 1, phs_config%n_in
            m(i) = phs_config%flv(i,1)%get_mass ()
        end do
    end subroutine phs_config_get_masses_in

```

Return the MD5 sum of the configuration.

```

<PHS base: phs config: TBP>+≡
    procedure :: get_md5sum => phs_config_get_md5sum

<PHS base: procedures>+≡
    function phs_config_get_md5sum (phs_config) result (md5sum)
        class(phs_config_t), intent(in) :: phs_config
        character(32) :: md5sum
        md5sum = phs_config%md5sum_phs_config
    end function phs_config_get_md5sum

```

18.1.5 Phase-space point instance

The `phs_t` object holds the workspace for phase-space generation. In the base object, we have the MC input parameters `r` and the Jacobian factor `f`, for each channel, and the incoming and outgoing momenta.

Note: The `active_channel` array is not used yet, all elements are initialized with `.true..` It should be touched by the integrator if it decides to drop irrelevant channels.

```

<PHS base: public>+≡
    public :: phs_t

<PHS base: types>+≡
    type, abstract :: phs_t
        class(phs_config_t), pointer :: config => null ()
        logical :: r_defined = .false.
        integer :: selected_channel = 0
        logical, dimension(:), allocatable :: active_channel
        real(default), dimension(:,:), allocatable :: r
        real(default), dimension(:), allocatable :: f
        real(default), dimension(:), allocatable :: m_in
        real(default), dimension(:), allocatable :: m_out

```



```

    real(default) :: flux = 0
    real(default) :: volume = 0
    type(lorentz_transformation_t) :: lt_cm_to_lab
    logical :: p_defined = .false.
    real(default) :: sqrts_hat = 0
    type(vector4_t), dimension(:), allocatable :: p
    logical :: q_defined = .false.
    type(vector4_t), dimension(:), allocatable :: q
contains
  <PHS base: phs: TBP>
end type phs_t

```

Output. Since phase space may get complicated, we include a `verbose` option for the abstract `write` procedure.

```

<PHS base: phs: TBP>≡
  procedure (phs_write), deferred :: write
<PHS base: interfaces>+≡
  abstract interface
    subroutine phs_write (object, unit, verbose)
      import
      class(phs_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: verbose
    end subroutine phs_write
  end interface

```

This procedure can be called to print the contents of the base type.

```

<PHS base: phs: TBP>+≡
  procedure :: base_write => phs_base_write
<PHS base: procedures>+≡
  subroutine phs_base_write (object, unit)
    class(phs_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, c, i
    u = given_output_unit (unit)
    write (u, "(1x,A)", advance="no") "Partonic phase space: parameters"
    if (object%r_defined) then
      write (u, *)
    else
      write (u, "(1x,A)") "[undefined]"
    end if
    write (u, "(3x,A,999(1x," // FMT_19 // "))") "m_in   =", object%m_in
    write (u, "(3x,A,999(1x," // FMT_19 // "))") "m_out   =", object%m_out
    write (u, "(3x,A," // FMT_19 // ")") "Flux    =", object%flux
    write (u, "(3x,A," // FMT_19 // ")") "Volume  =", object%volume
    if (allocated (object%f)) then
      do c = 1, size (object%f, 2)
        write (u, "(1x,A,IO,A)", advance="no") "Channel #", c, ":"
        if (c == object%selected_channel) then
          write (u, "(1x,A)") "[selected]"
        else
          write (u, *)
        end if
      end do
    end if
  end subroutine phs_base_write

```

```

        end if
        write (u, "(3x,A)", advance="no") "r ="
        do i = 1, size (object%r, 1)
            write (u, "(1x,F9.7)", advance="no") object%r(i,c)
        end do
        write (u, *)
        write (u, "(3x,A,1x,ES13.7)") "f =", object%f(c)
    end do
end if
write (u, "(1x,A)") "Partonic phase space: momenta"
if (object%p_defined) then
    write (u, "(3x,A," // FMT_19 // ")") "sqrts = ", object%sqrts_hat
end if
write (u, "(1x,A)", advance="no") "Incoming:"
if (object%p_defined) then
    write (u, *)
else
    write (u, "(1x,A)") "[undefined]"
end if
if (allocated (object%p)) then
    do i = 1, size (object%p)
        call vector4_write (object%p(i), u)
    end do
end if
write (u, "(1x,A)", advance="no") "Outgoing:"
if (object%q_defined) then
    write (u, *)
else
    write (u, "(1x,A)") "[undefined]"
end if
if (allocated (object%q)) then
    do i = 1, size (object%q)
        call vector4_write (object%q(i), u)
    end do
end if
if (object%p_defined .and. .not. object%config%cm_frame) then
    write (u, "(1x,A)") "Transformation c.m -> lab frame"
    call lorentz_transformation_write (object%lt_cm_to_lab, u)
end if
end subroutine phs_base_write

```

Finalizer. The base type does not need it, but extensions may.

```

<PHS base: phs: TBP>+≡
    procedure (phs_final), deferred :: final

<PHS base: interfaces>+≡
    abstract interface
        subroutine phs_final (object)
            import
            class(phs_t), intent(inout) :: object
        end subroutine phs_final
    end interface

```

Initializer. Everything should be contained in the `process_data` configuration object, so we can require a universal interface.

```

<PHS base: phs: TBP>+≡
  procedure (phs_init), deferred :: init

<PHS base: interfaces>+≡
  abstract interface
    subroutine phs_init (phs, phs_config)
      import
      class(phs_t), intent(out) :: phs
      class(phs_config_t), intent(in), target :: phs_config
    end subroutine phs_init
  end interface

```

The base version will just allocate the arrays. It should be called at the beginning of the implementation of `phs_init`.

```

<PHS base: phs: TBP>+≡
  procedure :: base_init => phs_base_init

<PHS base: procedures>+≡
  subroutine phs_base_init (phs, phs_config)
    class(phs_t), intent(out) :: phs
    class(phs_config_t), intent(in), target :: phs_config
    real(default), dimension(phs_config%n_in) :: m_in
    real(default), dimension(phs_config%n_out) :: m_out
    phs%config => phs_config
    allocate (phs%active_channel (phs%config%n_channel))
    phs%active_channel = .true.
    allocate (phs%r (phs%config%n_par, phs%config%n_channel)); phs%r = 0
    allocate (phs%f (phs%config%n_channel)); phs%f = 0
    allocate (phs%p (phs%config%n_in))
    !!! !!! !!! Workaround for gfortran 5.0 ICE
    m_in = phs_config%flv(:phs_config%n_in, 1)%get_mass ()
    m_out = phs_config%flv(phs_config%n_in+1:, 1)%get_mass ()
    allocate (phs%m_in (phs%config%n_in), source = m_in)
    !!! allocate (phs%m_in (phs%config%n_in), &
    !!!           source = phs_config%flv(:phs_config%n_in, 1)%get_mass ())
    allocate (phs%q (phs%config%n_out))
    allocate (phs%m_out (phs%config%n_out), source = m_out)
    !!! allocate (phs%m_out (phs%config%n_out), &
    !!!           source = phs_config%flv(phs_config%n_in+1:, 1)%get_mass ())
    call phs%compute_flux ()
  end subroutine phs_base_init

```

Manually select a channel.

```

<PHS base: phs: TBP>+≡
  procedure :: select_channel => phs_base_select_channel

<PHS base: procedures>+≡
  subroutine phs_base_select_channel (phs, channel)
    class(phs_t), intent(inout) :: phs
    integer, intent(in), optional :: channel
    if (present (channel)) then
      phs%selected_channel = channel
    end if
  end subroutine phs_base_select_channel

```

```

else
  phs%selected_channel = 0
end if
end subroutine phs_base_select_channel

```

Set incoming momenta. Assume that array shapes match. If requested, compute the Lorentz transformation from the c.m. to the lab frame and apply that transformation to the incoming momenta.

In the c.m. frame, the sum of three-momenta is zero. In a scattering process, the z axis is the direction of the first beam, the second beam is along the negative z axis. The transformation from the c.m. to the lab frame is a rotation from the z axis to the boost axis followed by a boost, such that the c.m. momenta are transformed into the lab-frame momenta. In a decay process, we just boost along the flight direction, without rotation.

```

(PHS base: phs: TBP)+≡
  procedure :: set_incoming_momenta => phs_set_incoming_momenta
(PHS base: procedures)+≡
  subroutine phs_set_incoming_momenta (phs, p)
    class(phs_t), intent(inout) :: phs
    type(vector4_t), dimension(:), intent(in) :: p
    type(vector4_t) :: p0, p1
    type(lorentz_transformation_t) :: lt0
    phs%p = p
    if (phs%config%cm_frame) then
      phs%sqrts_hat = phs%config%sqrts
      phs%p = p
    else
      p0 = sum (p)
      if (phs%config%sqrts_fixed) then
        phs%sqrts_hat = phs%config%sqrts
      else
        phs%sqrts_hat = p0 ** 1
      end if
      lt0 = boost (p0, phs%sqrts_hat)
      select case (phs%config%n_in)
      case (1)
        phs%lt_cm_to_lab = lt0
      case (2)
        p1 = inverse(lt0) * p(1)
        phs%lt_cm_to_lab = lt0 * rotation_to_2nd (3, space_part (p1))
      end select
      phs%p = inverse (phs%lt_cm_to_lab) * p
    end if
    phs%p_defined = .true.
  end subroutine phs_set_incoming_momenta

```

Set outgoing momenta. Assume that array shapes match. The incoming momenta must be known, so can apply the Lorentz transformation from c.m. to lab (inverse) to the momenta.

```

(PHS base: phs: TBP)+≡
  procedure :: set_outgoing_momenta => phs_set_outgoing_momenta

```

```

(PHS base: procedures)+≡
subroutine phs_set_outgoing_momenta (phs, q)
  class(phs_t), intent(inout) :: phs
  type(vector4_t), dimension(:), intent(in) :: q
  if (phs%p_defined) then
    if (phs%config%cm_frame) then
      phs%q = q
    else
      phs%q = inverse (phs%lt_cm_to_lab) * q
    end if
    phs%q_defined = .true.
  end if
end subroutine phs_set_outgoing_momenta

```

Return outgoing momenta. Apply the c.m. to lab transformation if necessary.

```

(PHS base: phs: TBP)+≡
  procedure :: get_outgoing_momenta => phs_get_outgoing_momenta
(PHS base: procedures)+≡
subroutine phs_get_outgoing_momenta (phs, q)
  class(phs_t), intent(in) :: phs
  type(vector4_t), dimension(:), intent(out) :: q
  if (phs%p_defined .and. phs%q_defined) then
    if (phs%config%cm_frame) then
      q = phs%q
    else
      q = phs%lt_cm_to_lab * phs%q
    end if
  else
    q = vector4_null
  end if
end subroutine phs_get_outgoing_momenta

```

Return the input parameter array for a channel.

```

(PHS base: phs: TBP)+≡
  procedure :: get_mcpair => phs_get_mcpair
(PHS base: procedures)+≡
subroutine phs_get_mcpair (phs, c, r)
  class(phs_t), intent(in) :: phs
  integer, intent(in) :: c
  real(default), dimension(:), intent(out) :: r
  if (phs%r_defined) then
    r = phs%r(:,c)
  else
    r = 0
  end if
end subroutine phs_get_mcpair

```

Return the Jacobian factor for a channel.

```

(PHS base: phs: TBP)+≡
  procedure :: get_f => phs_get_f

```

```

(PHS base: procedures)+≡
function phs_get_f (phs, c) result (f)
  class(phs_t), intent(in) :: phs
  integer, intent(in) :: c
  real(default) :: f
  if (phs%r_defined) then
    f = phs%f(c)
  else
    f = 0
  end if
end function phs_get_f

```

Return the overall factor, which is the product of the flux factor for the incoming partons and the phase-space volume for the outgoing partons.

```

(PHS base: phs: TBP)+≡
procedure :: get_overall_factor => phs_get_overall_factor

(PHS base: procedures)+≡
function phs_get_overall_factor (phs) result (f)
  class(phs_t), intent(in) :: phs
  real(default) :: f
  f = phs%flux * phs%volume
end function phs_get_overall_factor

```

Compute flux factor. We do this during initialization (when the incoming momenta \mathbf{p} are undefined), unless `sqrts` is variable. We do this again once for each phase-space point, but then we skip the calculation if `sqrts` is fixed.

There are three different flux factors.

1. For a decaying massive particle, the factor is

$$f = (2\pi)^4/(2M) \quad (18.1)$$

2. For a $2 \rightarrow n$ scattering process with $n > 1$, the factor is

$$f = (2\pi)^4/(2\sqrt{\lambda}) \quad (18.2)$$

where for massless incoming particles, $\sqrt{\lambda} = s$.

3. For a $2 \rightarrow 1$ on-shell production process, the factor includes an extra $1/(2\pi)^3$ factor and a $1/m^2$ factor from the phase-space delta function $\delta(x_1x_2 - m^2/s)$, which originate from the one-particle phase space that we integrate out.

$$f = 2\pi/(2sm^2) \quad (18.3)$$

The delta function is handled by the structure-function parameterization.

```

(PHS base: phs: TBP)+≡
procedure :: compute_flux => phs_compute_flux

```

```

<PHS base: procedures>+≡
subroutine phs_compute_flux (phs)
  class(phs_t), intent(inout) :: phs
  real(default) :: s_hat, lda
  select case (phs%config%n_in)
  case (1)
    if (.not. phs%p_defined) then
      phs%flux = twopi4 / (2 * phs%m_in(1))
    end if
  case (2)
    if (phs%p_defined) then
      if (phs%config%sqrts_fixed) then
        return
      else
        s_hat = sum (phs%p) ** 2
      end if
    else
      if (phs%config%sqrts_fixed) then
        s_hat = phs%config%sqrts ** 2
      else
        return
      end if
    end if
  select case (phs%config%n_out)
  case (2:)
    lda = lambda (s_hat, phs%m_in(1) ** 2, phs%m_in(2) ** 2)
    if (lda > 0) then
      phs%flux = conv * twopi4 / (2 * sqrt (lda))
    else
      phs%flux = 0
    end if
  case (1)
    phs%flux = conv * twopi &
      / (2 * phs%config%sqrts ** 2 * phs%m_out(1) ** 2)
  case default
    phs%flux = 0
  end select
end select
end subroutine phs_compute_flux

```

Evaluate the phase-space point for a particular channel and compute momenta, Jacobian, and phase-space volume. This is, of course, deferred to the implementation.

```

<PHS base: phs: TBP>+≡
  procedure (phs_evaluate_selected_channel), deferred :: &
    evaluate_selected_channel

<PHS base: interfaces>+≡
abstract interface
  subroutine phs_evaluate_selected_channel (phs, c_in, r_in)
    import
    class(phs_t), intent(inout) :: phs
    integer, intent(in) :: c_in
    real(default), dimension(:), intent(in) :: r_in
  end subroutine
end interface

```

```

        end subroutine phs_evaluate_selected_channel
    end interface

```

Compute the inverse mappings to completely fill the **r** and **f** arrays, for the non-selected channels.

```

<PHS base: phs: TBP>+≡
    procedure (phs_evaluate_other_channels), deferred :: &
        evaluate_other_channels

<PHS base: interfaces>+≡
    abstract interface
        subroutine phs_evaluate_other_channels (phs, c_in)
            import
            class(phs_t), intent(inout) :: phs
            integer, intent(in) :: c_in
        end subroutine phs_evaluate_other_channels
    end interface

```

Inverse evaluation. If all momenta are known, we compute the inverse mappings to fill the **r** and **f** arrays.

```

<PHS base: phs: TBP>+≡
    procedure (phs_inverse), deferred :: inverse

<PHS base: interfaces>+≡
    abstract interface
        subroutine phs_inverse (phs)
            import
            class(phs_t), intent(inout) :: phs
        end subroutine phs_inverse
    end interface

```

18.1.6 Auxiliary stuff

The **pacify** subroutine, which is provided by the Lorentz module, has the purpose of setting numbers to zero which are (by comparing with a **tolerance** parameter) considered equivalent with zero. This is useful for numerical checks.

```

<PHS base: public>+≡
    public :: pacify

<PHS base: interfaces>+≡
    interface pacify
        module procedure pacify_phs
    end interface pacify

<PHS base: procedures>+≡
    subroutine pacify_phs (phs)
        class(phs_t), intent(inout) :: phs
        if (phs%p_defined) then
            call pacify (phs%p, 30 * epsilon (1._default) * phs%config%sqrts)
            call pacify (phs%lt_cm_to_lab, 30 * epsilon (1._default))
        end if
        if (phs%q_defined) then

```



```

        call pacify (phs%q, 30 * epsilon (1._default) * phs%config%sqrts)
    end if
end subroutine pacify_phs

```

18.1.7 Unit tests

```

<PHS base: public>+≡
    public :: phs_base_test
<PHS base: tests>≡
    subroutine phs_base_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <PHS base: execute tests>
    end subroutine phs_base_test

```

Test process data

We provide a procedure that initializes a test case for the process constants. This set of process data contains just the minimal contents that we need for the phase space. The rest is left uninitialized.

```

<PHS base: public>+≡
    public :: init_test_process_data
<PHS base: tests>+≡
    subroutine init_test_process_data (id, data)
        type(process_constants_t), intent(out) :: data
        type(string_t), intent(in), optional :: id
        if (present (id)) then
            data%id = id
        else
            data%id = "testproc"
        end if
        data%model_name = "Test"
        data%n_in = 2
        data%n_out = 2
        data%n_flv = 1
        allocate (data%flv_state (data%n_in + data%n_out, data%n_flv))
        data%flv_state = 25
    end subroutine init_test_process_data

```

This is the variant for a decay process.

```

<PHS base: public>+≡
    public :: init_test_decay_data
<PHS base: tests>+≡
    subroutine init_test_decay_data (id, data)
        type(process_constants_t), intent(out) :: data
        type(string_t), intent(in), optional :: id
        if (present (id)) then
            data%id = id
        else

```

```

        data%id = "testproc"
    end if
    data%model_name = "Test"
    data%n_in = 1
    data%n_out = 2
    data%n_flv = 1
    allocate (data%flv_state (data%n_in + data%n_out, data%n_flv))
    data%flv_state(:,1) = [25, 6, -6]
end subroutine init_test_decay_data

```

Test kinematics configuration

This is a trivial implementation of the `phs_config_t` configuration object.

```

<PHS base: public>+≡
    public :: phs_test_config_t

<PHS base: test types>≡
    type, extends (phs_config_t) :: phs_test_config_t
        logical :: create_equivalences = .false.
    contains
        procedure :: final => phs_test_config_final
        procedure :: write => phs_test_config_write
        procedure :: configure => phs_test_config_configure
        procedure :: startup_message => phs_test_config_startup_message
        procedure, nopass :: allocate_instance => phs_test_config_allocate_instance
    end type phs_test_config_t

```

The finalizer is empty.

```

<PHS base: tests>+≡
    subroutine phs_test_config_final (object)
        class(phs_test_config_t), intent(inout) :: object
    end subroutine phs_test_config_final

```

The `cm_frame` parameter is not tested here; we defer this to the `phs_single` implementation.

```

<PHS base: tests>+≡
    subroutine phs_test_config_write (object, unit)
        class(phs_test_config_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Partonic phase-space configuration:"
        call object%base_write (unit)
    end subroutine phs_test_config_write

    subroutine phs_test_config_configure (phs_config, sqrts, &
        sqrts_fixed, cm_frame, azimuthal_dependence, rebuild, ignore_mismatch, &
        nlo_type)
        class(phs_test_config_t), intent(inout) :: phs_config
        real(default), intent(in) :: sqrts
        logical, intent(in), optional :: sqrts_fixed
        logical, intent(in), optional :: cm_frame

```

```

logical, intent(in), optional :: azimuthal_dependence
logical, intent(in), optional :: rebuild
logical, intent(in), optional :: ignore_mismatch
integer, intent(inout), optional :: nlo_type
phs_config%n_channel = 2
phs_config%n_par = 2
phs_config%sqrts = sqrts
if (.not. present (nlo_type)) &
    phs_config%nlo_type = BORN
if (present (sqrts_fixed)) then
    phs_config%sqrts_fixed = sqrts_fixed
end if
if (present (cm_frame)) then
    phs_config%cm_frame = cm_frame
end if
if (present (azimuthal_dependence)) then
    phs_config%azimuthal_dependence = azimuthal_dependence
end if
if (allocated (phs_config%channel)) deallocate (phs_config%channel)
allocate (phs_config%channel (phs_config%n_channel))
if (phs_config%create_equivalences) then
    call setup_test_equivalences (phs_config)
    call setup_test_channel_props (phs_config)
end if
call phs_config%compute_md5sum ()
end subroutine phs_test_config_configure

```

If requested, we make up an arbitrary set of equivalences.

```

<PHS base: tests>+≡
subroutine setup_test_equivalences (phs_config)
class(phs_test_config_t), intent(inout) :: phs_config
integer :: i
associate (channel => phs_config%channel(1))
    allocate (channel%eq (2))
    do i = 1, size (channel%eq)
        call channel%eq(i)%init (phs_config%n_par)
    end do
    associate (eq => channel%eq(1))
        eq%c = 1; eq%perm = [1, 2]; eq%mode = [EQ_IDENTITY, EQ_SYMMETRIC]
    end associate
    associate (eq => channel%eq(2))
        eq%c = 2; eq%perm = [2, 1]; eq%mode = [EQ_INVARIANT, EQ_IDENTITY]
    end associate
end associate
end subroutine setup_test_equivalences

```

Ditto, for channel properties.

```

<PHS base: tests>+≡
subroutine setup_test_channel_props (phs_config)
class(phs_test_config_t), intent(inout) :: phs_config
associate (channel => phs_config%channel(2))
    call channel%set_resonant (140._default, 3.1415_default)
end associate

```

```
end subroutine setup_test_channel_props
```

Startup message

```
<PHS base: tests>+≡
  subroutine phs_test_config_startup_message (phs_config, unit)
    class(phs_test_config_t), intent(in) :: phs_config
    integer, intent(in), optional :: unit
    call phs_config%base_startup_message (unit)
    write (msg_buffer, "(A)") "Phase space: Test"
    call msg_message (unit = unit)
  end subroutine phs_test_config_startup_message
```

The instance type that matches `phs_test_config_t` is `phs_test_t`.

```
<PHS base: tests>+≡
  subroutine phs_test_config_allocate_instance (phs)
    class(phs_t), intent(inout), pointer :: phs
    allocate (phs_test_t :: phs)
  end subroutine phs_test_config_allocate_instance
```

Test kinematics implementation

This implementation of kinematics generates a simple two-particle configuration from the incoming momenta. The incoming momenta must be in the c.m. system, all masses equal.

There are two channels: one generates $\cos \theta$ and ϕ uniformly, in the other channel we map the r_1 parameter which belongs to $\cos \theta$.

We should store the mass parameter that we need.

```
<PHS base: public>+≡
  public :: phs_test_t

<PHS base: test types>+≡
  type, extends (phs_t) :: phs_test_t
    real(default) :: m = 0
    real(default), dimension(:), allocatable :: x
  contains
    <PHS base: phs test: TBP>
  end type phs_test_t
```

Output. The specific data are displayed only if `verbose` is set.

```
<PHS base: phs test: TBP>≡
  procedure :: write => phs_test_write

<PHS base: tests>+≡
  subroutine phs_test_write (object, unit, verbose)
    class(phs_test_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u
    logical :: verb
    u = given_output_unit (unit)
    verb = .false.; if (present (verbose)) verb = verbose
```

```

    if (verb) then
      write (u, "(1x,A)") "Partonic phase space: data"
      write (u, "(3x,A," // FMT_19 // ")") "m = ", object%m
    end if
    call object%base_write (u)
  end subroutine phs_test_write

```

The finalizer is empty.

```

<PHS base: phs test: TBP>+≡
  procedure :: final => phs_test_final

<PHS base: tests>+≡
  subroutine phs_test_final (object)
    class(phs_test_t), intent(inout) :: object
  end subroutine phs_test_final

```

Initialization: set the mass value.

```

<PHS base: phs test: TBP>+≡
  procedure :: init => phs_test_init

<PHS base: tests>+≡
  subroutine phs_test_init (phs, phs_config)
    class(phs_test_t), intent(out) :: phs
    class(phs_config_t), intent(in), target :: phs_config
    call phs%base_init (phs_config)
    phs%m = phs%config%flv(1,1)%get_mass ()
    allocate (phs%x (phs_config%n_par), source = 0._default)
  end subroutine phs_test_init

```

Evaluation. In channel 1, we uniformly generate $\cos\theta$ and ϕ , with Jacobian normalized to one. In channel 2, we prepend a mapping $r_1 \rightarrow r_1^{(1/3)}$ with Jacobian $f = 3r_1^2$.

The component x is allocated in the first subroutine, used and deallocated in the second one.

```

<PHS base: phs test: TBP>+≡
  procedure :: evaluate_selected_channel => phs_test_evaluate_selected_channel
  procedure :: evaluate_other_channels => phs_test_evaluate_other_channels

<PHS base: tests>+≡
  subroutine phs_test_evaluate_selected_channel (phs, c_in, r_in)
    class(phs_test_t), intent(inout) :: phs
    integer, intent(in) :: c_in
    real(default), intent(in), dimension(:) :: r_in
    if (phs%p_defined) then
      call phs%select_channel (c_in)
      phs%r(:,c_in) = r_in
      select case (c_in)
        case (1)
          phs%x = r_in
        case (2)
          phs%x(1) = r_in(1) ** (1 / 3._default)
          phs%x(2) = r_in(2)
      end select
    end if
  end subroutine phs_test_evaluate_selected_channel

```

```

        call compute_kinematics_solid_angle (phs%p, phs%q, phs%x)
        phs%volume = 1
        phs%q_defined = .true.
    end if
end subroutine phs_test_evaluate_selected_channel

subroutine phs_test_evaluate_other_channels (phs, c_in)
    class(phs_test_t), intent(inout) :: phs
    integer, intent(in) :: c_in
    integer :: c, n_channel
    if (phs%p_defined) then
        n_channel = phs%config%n_channel
        do c = 1, n_channel
            if (c /= c_in) then
                call inverse_kinematics_solid_angle (phs%p, phs%q, phs%x)
                select case (c)
                case (1)
                    phs%r(:,c) = phs%x
                case (2)
                    phs%r(1,c) = phs%x(1) ** 3
                    phs%r(2,c) = phs%x(2)
                end select
            end if
        end do
        phs%f(1) = 1
        if (phs%r(1,2) /= 0) then
            phs%f(2) = 1 / (3 * phs%r(1,2) ** (2/3._default))
        else
            phs%f(2) = 0
        end if
        phs%r_defined = .true.
    end if
end subroutine phs_test_evaluate_other_channels

```

Inverse evaluation.

(PHS base: phs test: TBP)+≡

```
procedure :: inverse => phs_test_inverse
```

(PHS base: tests)+≡

```

subroutine phs_test_inverse (phs)
    class(phs_test_t), intent(inout) :: phs
    integer :: c, n_channel
    real(default), dimension(:), allocatable :: x
    if (phs%p_defined .and. phs%q_defined) then
        call phs%select_channel ()
        n_channel = phs%config%n_channel
        allocate (x (phs%config%n_par))
        do c = 1, n_channel
            call inverse_kinematics_solid_angle (phs%p, phs%q, x)
            select case (c)
            case (1)
                phs%r(:,c) = x
            case (2)
                phs%r(1,c) = x(1) ** 3
            end select
        end do
    end if
end subroutine phs_test_inverse

```

```

        phs%r(2,c) = x(2)
    end select
end do
phs%f(1) = 1
if (phs%r(1,2) /= 0) then
    phs%f(2) = 1 / (3 * phs%r(1,2) ** (2/3._default))
else
    phs%f(2) = 0
end if
phs%volume = 1
phs%r_defined = .true.
end if
end subroutine phs_test_inverse

```

Uniform angular distribution

These procedures implement the uniform angular distribution, generated from two parameters x_1 and x_2 :

$$\cos \theta = 1 - 2x_1, \quad \phi = 2\pi x_2 \quad (18.4)$$

We generate a rotation (Lorentz transformation) which rotates the positive z axis into this point on the unit sphere. This rotation is applied to the \mathbf{p} momenta, which are assumed to be back-to-back, on-shell, and with the correct mass.

We do not compute a Jacobian (constant). The uniform distribution is assumed to be normalized.

```

<PHS base: public>+≡
    public :: compute_kinematics_solid_angle

<PHS base: tests>+≡
    subroutine compute_kinematics_solid_angle (p, q, x)
        type(vector4_t), dimension(2), intent(in) :: p
        type(vector4_t), dimension(2), intent(out) :: q
        real(default), dimension(2), intent(in) :: x
        real(default) :: ct, st, phi
        type(lorentz_transformation_t) :: rot
        integer :: i
        ct = 1 - 2*x(1)
        st = sqrt (1 - ct**2)
        phi = twopi * x(2)
        rot = rotation (phi, 3) * rotation (ct, st, 2)
        do i = 1, 2
            q(i) = rot * p(i)
        end do
    end subroutine compute_kinematics_solid_angle

```

This is the inverse transformation. We assume that the outgoing momenta are rotated versions of the incoming momenta, back-to-back. Thus, we determine the angles from $q(1)$ alone. \mathbf{p} is unused.

```

<PHS base: public>+≡
    public :: inverse_kinematics_solid_angle

```

```

<PHS base: tests>+≡
  subroutine inverse_kinematics_solid_angle (p, q, x)
    type(vector4_t), dimension(:), intent(in) :: p
    type(vector4_t), dimension(2), intent(in) :: q
    real(default), dimension(2), intent(out) :: x
    real(default) :: ct, phi
    ct = polar_angle_ct (q(1))
    phi = azimuthal_angle (q(1))
    x(1) = (1 - ct) / 2
    x(2) = phi / twopi
  end subroutine inverse_kinematics_solid_angle

```

Phase-space configuration data

Construct and display a test phase-space configuration object.

```

<PHS base: execute tests>≡
  call test (phs_base_1, "phs_base_1", &
    "phase-space configuration", &
    u, results)

<PHS base: tests>+≡
  subroutine phs_base_1 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    class(phs_config_t), allocatable :: phs_data

    write (u, "(A)")  "* Test output: phs_base_1"
    write (u, "(A)")  "*   Purpose: initialize and display &
      &test phase-space configuration data"
    write (u, "(A)")

    call model%init_test ()

    write (u, "(A)")  "* Initialize a process and a matching &
      &phase-space configuration"
    write (u, "(A)")

    call init_test_process_data (var_str ("phs_base_1"), process_data)

    allocate (phs_test_config_t :: phs_data)
    call phs_data%init (process_data, model)

    call phs_data%write (u)

    call phs_data%final ()
    call model%final ()

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: phs_base_1"

  end subroutine phs_base_1

```


Phase space evaluation

Compute kinematics for given parameters, also invert the calculation.

```
(PHS base: execute tests)+≡
  call test (phs_base_2, "phs_base_2", &
    "phase-space evaluation", &
    u, results)

(PHS base: tests)+≡
  subroutine phs_base_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(process_constants_t) :: process_data
    real(default) :: sqrts, E
    class(phs_config_t), allocatable, target :: phs_data
    class(phs_t), pointer :: phs => null ()
    type(vector4_t), dimension(2) :: p, q

    write (u, "(A)")  "* Test output: phs_base_2"
    write (u, "(A)")  "* Purpose: test simple two-channel phase space"
    write (u, "(A)")

    call model%init_test ()
    call flv%init (25, model)

    write (u, "(A)")  "* Initialize a process and a matching &
      &phase-space configuration"
    write (u, "(A)")

    call init_test_process_data (var_str ("phs_base_2"), process_data)

    allocate (phs_test_config_t :: phs_data)
    call phs_data%init (process_data, model)

    sqrts = 1000._default
    call phs_data%configure (sqrts)

    call phs_data%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize the phase-space instance"
    write (u, "(A)")

    call phs_data%allocate_instance (phs)
    select type (phs)
    type is (phs_test_t)
      call phs%init (phs_data)
    end select

    call phs%write (u, verbose=.true.)

    write (u, "(A)")
    write (u, "(A)")  "* Set incoming momenta"
    write (u, "(A)")
```

```

E = sqrts / 2
p(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
p(2) = vector4_moving (E,-sqrt (E**2 - flv%get_mass ()**2), 3)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute phase-space point in channel 1 &
    &for x = 0.5, 0.125"
write (u, "(A)")

call phs%evaluate_selected_channel (1, [0.5_default, 0.125_default])
call phs%evaluate_other_channels (1)
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute phase-space point in channel 2 &
    &for x = 0.125, 0.125"
write (u, "(A)")

call phs%evaluate_selected_channel (2, [0.125_default, 0.125_default])
call phs%evaluate_other_channels (2)
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"
write (u, "(A)")

call phs%get_outgoing_momenta (q)
deallocate (phs)
call phs_data%allocate_instance (phs)
call phs%init (phs_data)

sqrts = 1000._default
select type (phs_data)
type is (phs_test_config_t)
    call phs_data%configure (sqrts)
end select

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%set_outgoing_momenta (q)

call phs%inverse ()
call phs%write (u)

call phs%final ()
deallocate (phs)

call phs_data%final ()
call model%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_base_2"

end subroutine phs_base_2

```

Phase-space equivalences

Construct a test phase-space configuration which contains channel equivalences.

```

<PHS base: execute tests>+≡
  call test (phs_base_3, "phs_base_3", &
    "channel equivalences", &
    u, results)

<PHS base: tests>+≡
  subroutine phs_base_3 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    class(phs_config_t), allocatable :: phs_data

    write (u, "(A)")  "* Test output: phs_base_3"
    write (u, "(A)")  "* Purpose: construct phase-space configuration data &
      &with equivalences"
    write (u, "(A)")

    call model%init_test ()

    write (u, "(A)")  "* Initialize a process and a matching &
      &phase-space configuration"
    write (u, "(A)")

    call init_test_process_data (var_str ("phs_base_3"), process_data)

    allocate (phs_test_config_t :: phs_data)
    call phs_data%init (process_data, model)
    select type (phs_data)
    type is (phs_test_config_t)
      phs_data%create_equivalences = .true.
    end select

    call phs_data%configure (1000._default)
    call phs_data%write (u)

    call phs_data%final ()
    call model%final ()

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: phs_base_3"

  end subroutine phs_base_3

```

MD5 sum checks

Construct a test phase-space configuration, compute and compare MD5 sums.

```
(PHS base: execute tests)+≡
  call test (phs_base_4, "phs_base_4", &
    "MD5 sum", &
    u, results)

(PHS base: tests)+≡
  subroutine phs_base_4 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    class(phs_config_t), allocatable :: phs_data

    write (u, "(A)")  "* Test output: phs_base_4"
    write (u, "(A)")  "* Purpose: compute and compare MD5 sums"
    write (u, "(A)")

    call model%init_test ()

    write (u, "(A)")  "* Model parameters"
    write (u, "(A)")

    call model%write (unit = u, &
      show_parameters = .true., &
      show_particles = .false., show_vertices = .false.)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize a process and a matching &
      &phase-space configuration"
    write (u, "(A)")

    call init_test_process_data (var_str ("phs_base_4"), process_data)
    process_data%md5sum = "test_process_data_m6sum_12345678"

    allocate (phs_test_config_t :: phs_data)
    call phs_data%init (process_data, model)

    call phs_data%compute_md5sum ()
    call phs_data%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Modify model parameter"
    write (u, "(A)")

    call model%set_par (var_str ("ms"), 100._default)
    call model%write (show_parameters = .true., &
      show_particles = .false., show_vertices = .false.)

    write (u, "(A)")
    write (u, "(A)")  "* PHS configuration"
    write (u, "(A)")

    call phs_data%compute_md5sum ()
```

```

call phs_data%write (u)

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_base_4"

end subroutine phs_base_4

```

Phase-space channel collection

Set up an array of various phase-space channels and collect them in a list.

```

<PHS base: execute tests>+≡
call test (phs_base_5, "phs_base_5", &
  "channel collection", &
  u, results)

<PHS base: tests>+≡
subroutine phs_base_5 (u)
  integer, intent(in) :: u
  type(phs_channel_t), dimension(:), allocatable :: channel
  type(phs_channel_collection_t) :: coll
  integer :: i, n

  write (u, "(A)")  "* Test output: phs_base_5"
  write (u, "(A)")  "* Purpose: collect channel properties"
  write (u, "(A)")

  write (u, "(A)")  "* Set up an array of channels"
  write (u, "(A)")

  n = 6

  allocate (channel (n))
  call channel(2)%set_resonant (75._default, 3._default)
  call channel(4)%set_resonant (130._default, 1._default)
  call channel(5)%set_resonant (75._default, 3._default)
  call channel(6)%set_on_shell (33._default)

  do i = 1, n
    write (u, "(1x,I0)", advance="no") i
    call channel(i)%write (u)
  end do

  write (u, "(A)")
  write (u, "(A)")  "* Collect distinct properties"
  write (u, "(A)")

  do i = 1, n
    call coll%push (channel(i))
  end do

```

```

write (u, "(1x,A,I0)")  "n = ", coll%get_n ()
write (u, "(A)")

call coll%write (u)

write (u, "(A)")
write (u, "(A)")  "* Channel array with collection index assigned"
write (u, "(A)")

do i = 1, n
    write (u, "(1x,I0)", advance="no")  i
    call channel(i)%write (u)
end do

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call coll%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_base_5"

end subroutine phs_base_5

```

18.2 Single-particle phase space

This module implements the phase space for a single particle, i.e., the solid angle, in a straightforward parameterization with a single channel. The phase-space implementation may be used either for $1 \rightarrow 2$ decays or for $2 \rightarrow 2$ scattering processes, so the number of incoming particles is the only free parameter in the configuration. In the latter case, we should restrict its use to non-resonant s-channel processes, because there is no mapping of the scattering angle.

(We might extend this later to account for generic $2 \rightarrow 2$ situations, e.g., account for a Coulomb singularity or detect an s-channel resonance structure that requires matching structure-function mappings.)

This is derived from the `phs_test` implementation in the `phs_base` module above, even more simplified, but intended for actual use.

```
(phs_single.f90)≡  
  <File header>  
  
  module phs_single  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use constants  
    use unit_tests  
    use diagnostics  
    use os_interface  
    use lorentz  
    use physics_defs  
    use model_data  
    use flavors  
    use process_constants  
    use sf_mappings  
    use sf_base  
    use phs_base  
  
    <Standard module head>  
  
    <PHS single: public>  
  
    <PHS single: types>  
  
    contains  
  
    <PHS single: procedures>  
  
    <PHS single: tests>  
  
  end module phs_single
```

18.2.1 Configuration

```
<PHS single: public>≡  
  public :: phs_single_config_t
```

```

<PHS single: types>≡
  type, extends (phs_config_t) :: phs_single_config_t
  contains
    <PHS single: phs single config: TBP>
  end type phs_single_config_t

```

The finalizer is empty.

```

<PHS single: phs single config: TBP>≡
  procedure :: final => phs_single_config_final

<PHS single: procedures>≡
  subroutine phs_single_config_final (object)
    class(phs_single_config_t), intent(inout) :: object
  end subroutine phs_single_config_final

```

Output.

```

<PHS single: phs single config: TBP>+≡
  procedure :: write => phs_single_config_write

<PHS single: procedures>+≡
  subroutine phs_single_config_write (object, unit)
    class(phs_single_config_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Partonic phase-space configuration (single-particle):"
    call object%base_write (unit)
  end subroutine phs_single_config_write

```

Configuration: there is only one channel and two parameters. The second parameter is the azimuthal angle, which may be a flat dimension.

```

<PHS single: phs single config: TBP>+≡
  procedure :: configure => phs_single_config_configure

<PHS single: procedures>+≡
  subroutine phs_single_config_configure (phs_config, sqrts, &
    sqrts_fixed, cm_frame, azimuthal_dependence, rebuild, ignore_mismatch, &
    nlo_type)
    class(phs_single_config_t), intent(inout) :: phs_config
    real(default), intent(in) :: sqrts
    logical, intent(in), optional :: sqrts_fixed
    logical, intent(in), optional :: cm_frame
    logical, intent(in), optional :: azimuthal_dependence
    logical, intent(in), optional :: rebuild
    logical, intent(in), optional :: ignore_mismatch
    integer, intent(inout), optional :: nlo_type
    if (.not. present (nlo_type)) &
      phs_config%nlo_type = BORN
    if (phs_config%n_out == 2) then
      phs_config%n_channel = 1
      phs_config%n_par = 2
      phs_config%sqrts = sqrts
      if (present (sqrts_fixed)) phs_config%sqrts_fixed = sqrts_fixed
    end if
  end subroutine phs_single_config_configure

```



```

    if (present (cm_frame)) phs_config%cm_frame = cm_frame
    if (present (azimuthal_dependence)) then
        phs_config%azimuthal_dependence = azimuthal_dependence
        if (.not. azimuthal_dependence) then
            allocate (phs_config%dim_flat (1))
            phs_config%dim_flat(1) = 2
        end if
    end if
    if (allocated (phs_config%channel)) deallocate (phs_config%channel)
    allocate (phs_config%channel (1))
    call phs_config%compute_md5sum ()
else
    call msg_fatal ("Single-particle phase space requires n_out = 2")
end if
end subroutine phs_single_config_configure

```

Startup message, after configuration is complete.

```

<PHS single: phs single config: TBP>+≡
    procedure :: startup_message => phs_single_config_startup_message
<PHS single: procedures>+≡
    subroutine phs_single_config_startup_message (phs_config, unit)
        class(phs_single_config_t), intent(in) :: phs_config
        integer, intent(in), optional :: unit
        call phs_config%base_startup_message (unit)
        write (msg_buffer, "(A,2(1x,I0,1x,A))") &
            "Phase space: single-particle"
        call msg_message (unit = unit)
    end subroutine phs_single_config_startup_message

```

Allocate an instance: the actual phase-space object.

```

<PHS single: phs single config: TBP>+≡
    procedure, nopass :: allocate_instance => phs_single_config_allocate_instance
<PHS single: procedures>+≡
    subroutine phs_single_config_allocate_instance (phs)
        class(phs_t), intent(inout), pointer :: phs
        allocate (phs_single_t :: phs)
    end subroutine phs_single_config_allocate_instance

```

18.2.2 Kinematics implementation

We generate $\cos\theta$ and ϕ uniformly, covering the solid angle.

Note: The incoming momenta must be in the c.m. system.

```

<PHS single: public>+≡
    public :: phs_single_t
<PHS single: types>+≡
    type, extends (phs_t) :: phs_single_t
        contains
        <PHS single: phs single: TBP>
    end type phs_single_t

```

Output. The `verbose` setting is irrelevant, we just display the contents of the base object.

```

<PHS single: phs single: TBP>≡
  procedure :: write => phs_single_write

<PHS single: procedures>+≡
  subroutine phs_single_write (object, unit, verbose)
    class(phs_single_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u
    u = given_output_unit (unit)
    call object%base_write (u)
  end subroutine phs_single_write

```

The finalizer is empty.

```

<PHS single: phs single: TBP>+≡
  procedure :: final => phs_single_final

<PHS single: procedures>+≡
  subroutine phs_single_final (object)
    class(phs_single_t), intent(inout) :: object
  end subroutine phs_single_final

```

Initialization. We allocate arrays (`base_init`) and adjust the phase-space volume. The massless two-particle phase space volume is

$$\Phi_2 = \frac{1}{4(2\pi)^5} = 2.55294034614 \times 10^{-5} \quad (18.5)$$

For a decay with nonvanishing masses (m_3, m_4), there is a correction factor

$$\Phi_2(m)/\Phi_2(0) = \frac{1}{\hat{s}} \lambda^{1/2}(\hat{s}, m_3^2, m_4^2). \quad (18.6)$$

For a scattering process with nonvanishing masses, the correction factor is

$$\Phi_2(m)/\Phi_2(0) = \frac{1}{\hat{s}^2} \lambda^{1/2}(\hat{s}, m_1^2, m_2^2) \lambda^{1/2}(\hat{s}, m_3^2, m_4^2). \quad (18.7)$$

If the energy is fixed, this is constant. Otherwise, we have to account for varying \hat{s} .

```

<PHS single: phs single: TBP>+≡
  procedure :: init => phs_single_init

<PHS single: procedures>+≡
  subroutine phs_single_init (phs, phs_config)
    class(phs_single_t), intent(out) :: phs
    class(phs_config_t), intent(in), target :: phs_config
    call phs%base_init (phs_config)
    phs%volume = 1 / (4 * twopi5)
    call phs%compute_factor ()
  end subroutine phs_single_init

```

Compute the correction factor for nonzero masses. We do this during initialization (when the incoming momenta \mathbf{p} are undefined), unless `sqrts` is variable. We do this again once for each phase-space point, but then we skip the calculation if `sqrts` is fixed.

```

<PHS single: phs single: TBP>+≡
  procedure :: compute_factor => phs_single_compute_factor

<PHS single: procedures>+≡
  subroutine phs_single_compute_factor (phs)
    class(phs_single_t), intent(inout) :: phs
    real(default) :: s_hat
    select case (phs%config%n_in)
    case (1)
      if (.not. phs%p_defined) then
        if (sum (phs%m_out) < phs%m_in(1)) then
          s_hat = phs%m_in(1) ** 2
          phs%f(1) = 1 / s_hat &
            * sqrt (lambda (s_hat, phs%m_out(1)**2, phs%m_out(2)**2))
        else
          print *, "m_in = ", phs%m_in
          print *, "m_out = ", phs%m_out
          call msg_fatal ("Decay is kinematically forbidden")
        end if
      end if
    case (2)
      if (phs%config%sqrts_fixed) then
        if (phs%p_defined) return
        s_hat = phs%config%sqrts ** 2
      else
        if (.not. phs%p_defined) return
        s_hat = sum (phs%p) ** 2
      end if
      if (sum (phs%m_in)**2 < s_hat .and. sum (phs%m_out)**2 < s_hat) then
        phs%f(1) = 1 / s_hat * &
          ( lambda (s_hat, phs%m_in (1)**2, phs%m_in (2)**2) &
            * lambda (s_hat, phs%m_out(1)**2, phs%m_out(2)**2) ) &
          ** 0.25_default
      else
        phs%f(1) = 0
      end if
    end select
  end subroutine phs_single_compute_factor

```

Evaluation. We uniformly generate $\cos\theta$ and ϕ , with Jacobian normalized to one.

There is only a single channel, so the second subroutine does nothing.

Note: the current implementation works for elastic scattering only.

```

<PHS single: phs single: TBP>+≡
  procedure :: evaluate_selected_channel => phs_single_evaluate_selected_channel
  procedure :: evaluate_other_channels => phs_single_evaluate_other_channels

<PHS single: procedures>+≡
  subroutine phs_single_evaluate_selected_channel (phs, c_in, r_in)
    class(phs_single_t), intent(inout) :: phs

```

```

integer, intent(in) :: c_in
real(default), intent(in), dimension(:) :: r_in
!!! Catching a gfortran bogus warning
type(vector4_t), dimension(2) :: p_dum
if (phs%p_defined) then
  call phs%select_channel (c_in)
  phs%r(:,c_in) = r_in
  select case (phs%config%n_in)
  case (2)
    if (all (phs%m_in == phs%m_out)) then
      call compute_kinematics_solid_angle (phs%p, phs%q, r_in)
    else
      call msg_bug ("PHS single: inelastic scattering not implemented")
    end if
  case (1)
    !!! Catching a gfortran bogus warning
    !!! call compute_kinematics_solid_angle (phs%decay_p (), phs%q, x)
    p_dum = phs%decay_p ()
    call compute_kinematics_solid_angle (p_dum, phs%q, r_in)
  end select
  call phs%compute_factor ()
  phs%q_defined = .true.
  phs%r_defined = .true.
end if
end subroutine phs_single_evaluate_selected_channel

subroutine phs_single_evaluate_other_channels (phs, c_in)
  class(phs_single_t), intent(inout) :: phs
  integer, intent(in) :: c_in
end subroutine phs_single_evaluate_other_channels

```

Auxiliary: split a decaying particle at rest into the decay products, aligned along the z axis.

```

<PHS single: phs single: TBP>+≡
  procedure :: decay_p => phs_single_decay_p

<PHS single: procedures>+≡
  function phs_single_decay_p (phs) result (p)
    class(phs_single_t), intent(in) :: phs
    type(vector4_t), dimension(2) :: p
    real(default) :: k
    real(default), dimension(2) :: E
    k = sqrt (lambda (phs%m_in(1) ** 2, phs%m_out(1) ** 2, phs%m_out(2) ** 2)) &
      / (2 * phs%m_in(1))
    E = sqrt (phs%m_out ** 2 + k ** 2)
    p(1) = vector4_moving (E(1), k, 3)
    p(2) = vector4_moving (E(2), -k, 3)
  end function phs_single_decay_p

```

Inverse evaluation.

```

<PHS single: phs single: TBP>+≡
  procedure :: inverse => phs_single_inverse

```

```

<PHS single: procedures>+≡
  subroutine phs_single_inverse (phs)
    class(phs_single_t), intent(inout) :: phs
    real(default), dimension(:), allocatable :: x
    if (phs%p_defined .and. phs%q_defined) then
      call phs%select_channel ()
      allocate (x (phs%config%n_par))
      call inverse_kinematics_solid_angle (phs%p, phs%q, x)
      phs%r(:,1) = x
      call phs%compute_factor ()
      phs%r_defined = .true.
    end if
  end subroutine phs_single_inverse

```

18.2.3 Unit tests

```

<PHS single: public>+≡
  public :: phs_single_test

<PHS single: tests>≡
  subroutine phs_single_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <PHS single: execute tests>
  end subroutine phs_single_test

```

Phase-space configuration data

Construct and display a test phase-space configuration object. Also check the azimuthal_dependence flag.

```

<PHS single: execute tests>≡
  call test (phs_single_1, "phs_single_1", &
    "phase-space configuration", &
    u, results)

<PHS single: tests>+≡
  subroutine phs_single_1 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    class(phs_config_t), allocatable :: phs_data
    real(default) :: sqrts

    write (u, "(A)")  "* Test output: phs_single_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &phase-space configuration data"
    write (u, "(A)")

    call model%init_test ()

    write (u, "(A)")  "* Initialize a process and a matching &
      &phase-space configuration"

```

```

write (u, "(A)")

call init_test_process_data (var_str ("phs_single_1"), process_data)

allocate (phs_single_config_t :: phs_data)
call phs_data%init (process_data, model)

sqrts = 1000._default
call phs_data%configure (sqrts, azimuthal_dependence=.false.)

call phs_data%write (u)

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "** Test output end: phs_single_1"

end subroutine phs_single_1

```

Phase space evaluation

Compute kinematics for given parameters, also invert the calculation.

(PHS single: execute tests) +=

```

call test (phs_single_2, "phs_single_2", &
  "phase-space evaluation", &
  u, results)

```

(PHS single: tests) +=

```

subroutine phs_single_2 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(flavor_t) :: flv
  type(process_constants_t) :: process_data
  real(default) :: sqrts, E
  class(phs_config_t), allocatable, target :: phs_data
  class(phs_t), pointer :: phs => null ()
  type(vector4_t), dimension(2) :: p, q

  write (u, "(A)")  "** Test output: phs_single_2"
  write (u, "(A)")  "** Purpose: test simple two-channel phase space"
  write (u, "(A)")

  call model%init_test ()
  call flv%init (25, model)

  write (u, "(A)")  "** Initialize a process and a matching &
    &phase-space configuration"
  write (u, "(A)")

  call init_test_process_data (var_str ("phs_single_2"), process_data)

  allocate (phs_single_config_t :: phs_data)

```

```

call phs_data%init (process_data, model)

sqrts = 1000._default
call phs_data%configure (sqrts)

call phs_data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize the phase-space instance"
write (u, "(A)")

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs%write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Set incoming momenta"
write (u, "(A)")

E = sqrts / 2
p(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
p(2) = vector4_moving (E,-sqrt (E**2 - flv%get_mass ()**2), 3)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute phase-space point &
    &for x = 0.5, 0.125"
write (u, "(A)")

call phs%evaluate_selected_channel (1, [0.5_default, 0.125_default])
call phs%evaluate_other_channels (1)
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"
write (u, "(A)")

call phs%get_outgoing_momenta (q)
deallocate (phs)
call phs_data%allocate_instance (phs)
call phs%init (phs_data)

sqrts = 1000._default
call phs_data%configure (sqrts)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%set_outgoing_momenta (q)

call phs%inverse ()

```

```

call phs%write (u)

call phs%final ()
deallocate (phs)

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_single_2"

end subroutine phs_single_2

```

Phase space for non-c.m. system

Compute kinematics for given parameters, also invert the calculation. Since this will involve cancellations, we call `pacify` to eliminate numerical noise.

```

<PHS single: execute tests>+≡
call test (phs_single_3, "phs_single_3", &
    "phase-space evaluation in lab frame", &
    u, results)

<PHS single: tests>+≡
subroutine phs_single_3 (u)
integer, intent(in) :: u
type(model_data_t), target :: model
type(flavor_t) :: flv
type(process_constants_t) :: process_data
real(default) :: sqrts, E
class(phs_config_t), allocatable, target :: phs_data
class(phs_t), pointer :: phs => null ()
type(vector4_t), dimension(2) :: p, q
type(lorentz_transformation_t) :: lt

write (u, "(A)")  "* Test output: phs_single_3"
write (u, "(A)")  "* Purpose: test simple two-channel phase space"
write (u, "(A)")  "*           without c.m. kinematics assumption"
write (u, "(A)")

call model%init_test ()
call flv%init (25, model)

write (u, "(A)")  "* Initialize a process and a matching &
    &phase-space configuration"
write (u, "(A)")

call init_test_process_data (var_str ("phs_single_3"), process_data)

allocate (phs_single_config_t :: phs_data)
call phs_data%init (process_data, model)

sqrts = 1000._default
call phs_data%configure (sqrts, cm_frame=.false., sqrts_fixed=.false.)

```



```

call phs_data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize the phase-space instance"
write (u, "(A)")

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs%write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Set incoming momenta in lab system"
write (u, "(A)")

lt = boost (0.1_default, 1) * boost (0.3_default, 3)

E = sqrts / 2
p(1) = lt * vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
p(2) = lt * vector4_moving (E, -sqrt (E**2 - flv%get_mass ()**2), 3)

call vector4_write (p(1), u)
call vector4_write (p(2), u)

write (u, "(A)")
write (u, "(A)")  "* Compute phase-space point &
      &for x = 0.5, 0.125"
write (u, "(A)")

call phs%set_incoming_momenta (p)
call phs%compute_flux ()

call phs%evaluate_selected_channel (1, [0.5_default, 0.125_default])
call phs%evaluate_other_channels (1)
call pacify (phs)
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Extract outgoing momenta in lab system"
write (u, "(A)")

call phs%get_outgoing_momenta (q)
call vector4_write (q(1), u)
call vector4_write (q(2), u)

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"
write (u, "(A)")

deallocate (phs)
call phs_data%allocate_instance (phs)
call phs%init (phs_data)

```

```

sqrts = 1000._default
call phs_data%configure (sqrts)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%set_outgoing_momenta (q)

call phs%inverse ()
call pacify (phs)
call phs%write (u)

call phs%final ()
deallocate (phs)

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_single_3"

end subroutine phs_single_3

```

Decay Phase space evaluation

Compute kinematics for given parameters, also invert the calculation. This time, implement a decay process.

```

<PHS single: execute tests>+≡
  call test (phs_single_4, "phs_single_4", &
    "decay phase-space evaluation", &
    u, results)

<PHS single: tests>+≡
  subroutine phs_single_4 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(process_constants_t) :: process_data
    class(phs_config_t), allocatable, target :: phs_data
    class(phs_t), pointer :: phs => null ()
    type(vector4_t), dimension(1) :: p
    type(vector4_t), dimension(2) :: q

    write (u, "(A)")  "* Test output: phs_single_4"
    write (u, "(A)")  "* Purpose: test simple two-channel phase space"
    write (u, "(A)")

    call model%init_test ()

    call model%set_par (var_str ("ff"), 0.4_default)
    call model%set_par (var_str ("mf"), &
      model%get_real (var_str ("ff")) * model%get_real (var_str ("ms")))
    call flv%init (25, model)

```

```

write (u, "(A)")  "* Initialize a decay and a matching &
&phase-space configuration"
write (u, "(A)")

call init_test_decay_data (var_str ("phs_single_4"), process_data)

allocate (phs_single_config_t :: phs_data)
call phs_data%init (process_data, model)

call phs_data%configure (flv%get_mass ())

call phs_data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize the phase-space instance"
write (u, "(A)")

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs%write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Set incoming momenta"
write (u, "(A)")

p(1) = vector4_at_rest (flv%get_mass ())

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute phase-space point &
&for x = 0.5, 0.125"
write (u, "(A)")

call phs%evaluate_selected_channel (1, [0.5_default, 0.125_default])
call phs%evaluate_other_channels (1)
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"
write (u, "(A)")

call phs%get_outgoing_momenta (q)
deallocate (phs)
call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs_data%configure (flv%get_mass ())

call phs%set_incoming_momenta (p)
call phs%compute_flux ()

```

```

call phs%set_outgoing_momenta (q)

call phs%inverse ()
call phs%write (u)

call phs%final ()
deallocate (phs)

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_single_4"

end subroutine phs_single_4

```

18.3 Mappings

Mappings are objects that encode the transformation of the interval $(0,1)$ to a physical variable m^2 or $\cos\theta$ (and back), as it is used in the phase space parameterization. The mapping objects contain fixed parameters, the associated methods implement the mapping and inverse mapping operations, including the computation of the Jacobian (phase space factor).

```
<mappings.f90>≡  
  <File header>  
  
  module mappings  
  
    <Use kinds>  
    use kinds, only: TC  
    <Use strings>  
    use io_units  
    use constants, only: pi  
    use format_defs, only: FMT_19  
    use diagnostics  
    use md5  
    use model_data  
    use flavors  
  
    <Standard module head>  
  
    <Mappings: public>  
  
    <Mappings: parameters>  
  
    <Mappings: types>  
  
    <Mappings: interfaces>  
  
    contains  
  
    <Mappings: procedures>  
  
  end module mappings
```

18.3.1 Default parameters

This type holds the default parameters, needed for setting the scale in cases where no mass parameter is available. The contents are public.

```
<Mappings: public>≡  
  public :: mapping_defaults_t  
  
<Mappings: types>≡  
  type :: mapping_defaults_t  
    real(default) :: energy_scale = 10  
    real(default) :: invariant_mass_scale = 10  
    real(default) :: momentum_transfer_scale = 10  
    logical :: step_mapping = .true.  
    logical :: step_mapping_exp = .true.
```

```

        logical :: enable_s_mapping = .false.
contains
    <Mappings: mapping defaults: TBP>
end type mapping_defaults_t

```

Output.

```

<Mappings: mapping defaults: TBP>≡
    procedure :: write => mapping_defaults_write

<Mappings: procedures>≡
    subroutine mapping_defaults_write (object, unit)
        class(mapping_defaults_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A," // FMT_19 // ")") "energy scale = ", &
            object%energy_scale
        write (u, "(3x,A," // FMT_19 // ")") "mass scale = ", &
            object%invariant_mass_scale
        write (u, "(3x,A," // FMT_19 // ")") "q scale = ", &
            object%momentum_transfer_scale
        write (u, "(3x,A,L1)") "step mapping = ", &
            object%step_mapping
        write (u, "(3x,A,L1)") "step exp. mode = ", &
            object%step_mapping_exp
        write (u, "(3x,A,L1)") "allow s mapping = ", &
            object%enable_s_mapping
    end subroutine mapping_defaults_write

<Mappings: public>+≡
    public :: mapping_defaults_md5sum

<Mappings: procedures>+≡
    function mapping_defaults_md5sum (mapping_defaults) result (md5sum_map)
        character(32) :: md5sum_map
        type(mapping_defaults_t), intent(in) :: mapping_defaults
        integer :: u
        u = free_unit ()
        open (u, status = "scratch")
        write (u, *) mapping_defaults%energy_scale
        write (u, *) mapping_defaults%invariant_mass_scale
        write (u, *) mapping_defaults%momentum_transfer_scale
        write (u, *) mapping_defaults%step_mapping
        write (u, *) mapping_defaults%step_mapping_exp
        write (u, *) mapping_defaults%enable_s_mapping
        rewind (u)
        md5sum_map = md5sum (u)
        close (u)
    end function mapping_defaults_md5sum

```

18.3.2 The Mapping type

Each mapping has a type (e.g., s-channel, infrared), a binary code (redundant, but useful for debugging), and a reference particle. The flavor code of this particle is stored for bookkeeping reasons, what matters are the mass and width of this particle. Furthermore, depending on the type, various mapping parameters can be set and used.

The parameters **a1** to **a3** (for m^2 mappings) and **b1** to **b3** (for $\cos \theta$ mappings) are values that are stored once to speed up the calculation, if **variable_limits** is false. The exact meaning of these parameters depends on the mapping type. The limits are fixed if there is a fixed c.m. energy.

```

<Mappings: public>+≡
    public :: mapping_t

<Mappings: types>+≡
    type :: mapping_t
    private
        integer :: type = NO_MAPPING
        integer(TC) :: bincode
        type(flavor_t) :: flv
        real(default) :: mass = 0
        real(default) :: width = 0
        logical :: a_unknown = .true.
        real(default) :: a1 = 0
        real(default) :: a2 = 0
        real(default) :: a3 = 0
        logical :: b_unknown = .true.
        real(default) :: b1 = 0
        real(default) :: b2 = 0
        real(default) :: b3 = 0
        logical :: variable_limits = .true.
    end type mapping_t

```

The valid mapping types. The extra type STEP_MAPPING is used only internally.

```

<Mappings: parameters>≡
    <Mapping modes>

```

18.3.3 Screen output

Do not write empty mappings.

```

<Mappings: public>+≡
    public :: mapping_write

<Mappings: procedures>+≡
    subroutine mapping_write (map, unit, verbose)
        type(mapping_t), intent(in) :: map
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        integer :: u
        character(len=9) :: str
        u = given_output_unit (unit); if (u < 0) return
        select case(map%type)
        case(S_CHANNEL); str = "s_channel"

```

```

case(COLLINEAR); str = "collinear"
case(INFRARED); str = "infrared "
case(RADIATION); str = "radiation"
case(T_CHANNEL); str = "t_channel"
case(U_CHANNEL); str = "u_channel"
case(STEP_MAPPING_E); str = "step_exp"
case(STEP_MAPPING_H); str = "step_hyp"
case(ON_SHELL); str = "on_shell"
case default; str = "??????"
end select
if (map%type /= NO_MAPPING) then
  write (u, '(1x,A,I4,A)') &
    "Branch #", map%bincode, ": " // &
    "Mapping (" // str // ") for particle " // &
    "' ' // char (map%flv%get_name ()) // ' '"
  if (present (verbose)) then
    if (verbose) then
      select case (map%type)
      case (S_CHANNEL, RADIATION, STEP_MAPPING_E, STEP_MAPPING_H)
        write (u, "(1x,A,3(" // FMT_19 // "))" ) &
          " m/w = ", map%mass, map%width
      case default
        write (u, "(1x,A,3(" // FMT_19 // "))" ) &
          " m = ", map%mass
      end select
      select case (map%type)
      case (S_CHANNEL, T_CHANNEL, U_CHANNEL, &
        STEP_MAPPING_E, STEP_MAPPING_H, &
        COLLINEAR, INFRARED, RADIATION)
        write (u, "(1x,A,3(" // FMT_19 // "))" ) &
          " a1/2/3 = ", map%a1, map%a2, map%a3
      end select
      select case (map%type)
      case (T_CHANNEL, U_CHANNEL, COLLINEAR)
        write (u, "(1x,A,3(" // FMT_19 // "))" ) &
          " b1/2/3 = ", map%b1, map%b2, map%b3
      end select
    end if
  end if
end if
end subroutine mapping_write

```

18.3.4 Define a mapping

The initialization routine sets the mapping type and the particle (binary code and flavor code) for which the mapping applies (e.g., a Z resonance in branch #3). We only need the absolute value of the flavor code.

(Mappings: public)+≡

public :: mapping_init

(Mappings: procedures)+≡

```

subroutine mapping_init (mapping, bincode, type, f, model)
  type(mapping_t), intent(inout) :: mapping

```



```

integer(TC), intent(in) :: bincode
type(string_t), intent(in) :: type
integer, intent(in), optional :: f
class(model_data_t), intent(in), optional, target :: model
mapping%bincode = bincode
select case (char (type))
case ("s_channel"); mapping%type = S_CHANNEL
case ("collinear"); mapping%type = COLLINEAR
case ("infrared"); mapping%type = INFRARED
case ("radiation"); mapping%type = RADIATION
case ("t_channel"); mapping%type = T_CHANNEL
case ("u_channel"); mapping%type = U_CHANNEL
case ("step_exp"); mapping%type = STEP_MAPPING_E
case ("step_hyp"); mapping%type = STEP_MAPPING_H
case ("on_shell"); mapping%type = ON_SHELL
case default
    call msg_bug ("Mappings: encountered undefined mapping key '" &
        // char (type) // "'")
end select
if (present (f) .and. present (model)) &
    call mapping%flv%init (abs (f), model)
end subroutine mapping_init

```

This sets the actual mass and width, using a parameter set. Since the auxiliary parameters will only be determined when the mapping is first called, they are marked as unknown.

```

<Mappings: public>+≡
    public :: mapping_set_parameters

<Mappings: procedures>+≡
    subroutine mapping_set_parameters (map, mapping_defaults, variable_limits)
        type(mapping_t), intent(inout) :: map
        type(mapping_defaults_t), intent(in) :: mapping_defaults
        logical, intent(in) :: variable_limits
        if (map%type /= NO_MAPPING) then
            map%mass = map%flv%get_mass ()
            map%width = map%flv%get_width ()
            map%variable_limits = variable_limits
            map%a_unknown = .true.
            map%b_unknown = .true.
            select case (map%type)
            case (S_CHANNEL)
                if (map%mass <= 0) then
                    call mapping_write (map)
                    call msg_fatal &
                        & (" S-channel resonance must have positive mass")
                else if (map%width <= 0) then
                    call mapping_write (map)
                    call msg_fatal &
                        & (" S-channel resonance must have positive width")
                end if
            case (RADIATION)
                map%width = max (map%width, mapping_defaults%energy_scale)
            case (INFRARED, COLLINEAR)

```

```

        map%mass = max (map%mass, mapping_defaults%invariant_mass_scale)
    case (T_CHANNEL, U_CHANNEL)
        map%mass = max (map%mass, mapping_defaults%momentum_transfer_scale)
    end select
end if
end subroutine mapping_set_parameters

```

For a step mapping the mass and width are set directly, instead of being determined from the flavor parameter (which is meaningless here). They correspond to the effective upper bound of phase space due to a resonance, as opposed to the absolute upper bound.

```

<Mappings: public>+≡
    public :: mapping_set_step_mapping_parameters

<Mappings: procedures>+≡
    subroutine mapping_set_step_mapping_parameters (map, &
        mass, width, variable_limits)
        type(mapping_t), intent(inout) :: map
        real(default), intent(in) :: mass, width
        logical, intent(in) :: variable_limits
        select case (map%type)
        case (STEP_MAPPING_E, STEP_MAPPING_H)
            map%variable_limits = variable_limits
            map%a_unknown = .true.
            map%b_unknown = .true.
            map%mass = mass
            map%width = width
        end select
    end subroutine mapping_set_step_mapping_parameters

```

18.3.5 Retrieve contents

Return true if there is any / an s-channel mapping.

```

<Mappings: public>+≡
    public :: mapping_is_set
    public :: mapping_is_s_channel
    public :: mapping_is_on_shell

<Mappings: procedures>+≡
    function mapping_is_set (mapping) result (flag)
        logical :: flag
        type(mapping_t), intent(in) :: mapping
        flag = mapping%type /= NO_MAPPING
    end function mapping_is_set

    function mapping_is_s_channel (mapping) result (flag)
        logical :: flag
        type(mapping_t), intent(in) :: mapping
        flag = mapping%type == S_CHANNEL
    end function mapping_is_s_channel

    function mapping_is_on_shell (mapping) result (flag)

```

```

    logical :: flag
    type(mapping_t), intent(in) :: mapping
    flag = mapping%type == ON_SHELL
end function mapping_is_on_shell

```

Return stored mass and width, respectively.

```

<Mappings: public>+≡
    public :: mapping_get_mass
    public :: mapping_get_width

<Mappings: procedures>+≡
    function mapping_get_mass (mapping) result (mass)
        real(default) :: mass
        type(mapping_t), intent(in) :: mapping
        mass = mapping%mass
    end function mapping_get_mass

    function mapping_get_width (mapping) result (width)
        real(default) :: width
        type(mapping_t), intent(in) :: mapping
        width = mapping%width
    end function mapping_get_width

```

18.3.6 Compare mappings

Equality for single mappings and arrays

```

<Mappings: public>+≡
    public :: operator(==)

<Mappings: interfaces>≡
    interface operator(==)
        module procedure mapping_equal
    end interface

<Mappings: procedures>+≡
    function mapping_equal (m1, m2) result (equal)
        type(mapping_t), intent(in) :: m1, m2
        logical :: equal
        if (m1%type == m2%type) then
            select case (m1%type)
            case (NO_MAPPING)
                equal = .true.
            case (S_CHANNEL, RADIATION, STEP_MAPPING_E, STEP_MAPPING_H)
                equal = (m1%mass == m2%mass) .and. (m1%width == m2%width)
            case default
                equal = (m1%mass == m2%mass)
            end select
        else
            equal = .false.
        end if
    end function mapping_equal

```

18.3.7 Mappings of the invariant mass

Inserting an x value between 0 and 1, we want to compute the corresponding invariant mass $m^2(x)$ and the jacobian, aka phase space factor $f(x)$. We also need the reverse operation.

In general, the phase space factor f is defined by

$$\frac{1}{s} \int_{m_{\min}^2}^{m_{\max}^2} dm^2 g(m^2) = \int_0^1 dx \frac{1}{s} \frac{dm^2}{dx} g(m^2(x)) = \int_0^1 dx f(x) g(x), \quad (18.8)$$

where thus

$$f(x) = \frac{1}{s} \frac{dm^2}{dx}. \quad (18.9)$$

With this mapping, a function of the form

$$g(m^2) = c \frac{dx(m^2)}{dm^2} \quad (18.10)$$

is mapped to a constant:

$$\frac{1}{s} \int_{m_{\min}^2}^{m_{\max}^2} dm^2 g(m^2) = \int_0^1 dx f(x) g(m^2(x)) = \int_0^1 dx \frac{c}{s}. \quad (18.11)$$

Here is the mapping routine. Input are the available energy squared s , the limits for m^2 , and the x value. Output are the m^2 value and the phase space factor f .

```

<Mappings: public>+≡
  public :: mapping_compute_msq_from_x

<Mappings: procedures>+≡
  subroutine mapping_compute_msq_from_x (map, s, msq_min, msq_max, msq, f, x)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: s, msq_min, msq_max
    real(default), intent(out) :: msq, f
    real(default), intent(in) :: x
    real(default) :: z, msq0, msq1, tmp
    integer :: type
    type = map%type
    if (s == 0) &
      call msg_fatal (" Applying msq mapping for zero energy")
    <Modify mapping type if necessary>
    select case(type)
    case (NO_MAPPING)
      <Constants for trivial msq mapping>
      <Apply trivial msq mapping>
    case (S_CHANNEL)
      <Constants for s-channel resonance mapping>
      <Apply s-channel resonance mapping>
    case (COLLINEAR, INFRARED, RADIATION)
      <Constants for s-channel pole mapping>
      <Apply s-channel pole mapping>
    case (T_CHANNEL, U_CHANNEL)
      <Constants for t-channel pole mapping>
      <Apply t-channel pole mapping>
  end subroutine

```

```

case (STEP_MAPPING_E)
  <Constants for exponential step mapping>
  <Apply exponential step mapping>
case (STEP_MAPPING_H)
  <Constants for hyperbolic step mapping>
  <Apply hyperbolic step mapping>
case default
  call msg_fatal ( " Attempt to apply undefined msq mapping")
end select
end subroutine mapping_compute_msq_from_x

```

The inverse mapping

<Mappings: public>+≡

```

public :: mapping_compute_x_from_msq

```

<Mappings: procedures>+≡

```

subroutine mapping_compute_x_from_msq (map, s, msq_min, msq_max, msq, f, x)
  type(mapping_t), intent(inout) :: map
  real(default), intent(in) :: s, msq_min, msq_max
  real(default), intent(in) :: msq
  real(default), intent(out) :: f, x
  real(default) :: msq0, msq1, tmp, z
  integer :: type
  type = map%type
  if (s == 0) &
    call msg_fatal (" Applying inverse msq mapping for zero energy")
  <Modify mapping type if necessary>
  select case (type)
  case (NO_MAPPING)
    <Constants for trivial msq mapping>
    <Apply inverse trivial msq mapping>
  case (S_CHANNEL)
    <Constants for s-channel resonance mapping>
    <Apply inverse s-channel resonance mapping>
  case (COLLINEAR, INFRARED, RADIATION)
    <Constants for s-channel pole mapping>
    <Apply inverse s-channel pole mapping>
  case (T_CHANNEL, U_CHANNEL)
    <Constants for t-channel pole mapping>
    <Apply inverse t-channel pole mapping>
  case (STEP_MAPPING_E)
    <Constants for exponential step mapping>
    <Apply inverse exponential step mapping>
  case (STEP_MAPPING_H)
    <Constants for hyperbolic step mapping>
    <Apply inverse hyperbolic step mapping>
  case default
    call msg_fatal ( " Attempt to apply undefined msq mapping")
  end select
end subroutine mapping_compute_x_from_msq

```

Trivial mapping

We simply map the boundaries of the interval (m_{\min}, m_{\max}) to $(0, 1)$:

$$m^2 = (1 - x)m_{\min}^2 + xm_{\max}^2; \quad (18.12)$$

the inverse is

$$x = \frac{m^2 - m_{\min}^2}{m_{\max}^2 - m_{\min}^2}. \quad (18.13)$$

Hence

$$f(x) = \frac{m_{\max}^2 - m_{\min}^2}{s}, \quad (18.14)$$

and we have, as required,

$$f(x) \frac{dx}{dm^2} = \frac{1}{s}. \quad (18.15)$$

We store the constant parameters the first time the mapping is called – or, if limits vary, recompute them each time.

```

⟨Constants for trivial msq mapping⟩≡
  if (map%variable_limits .or. map%a_unknown) then
    map%a1 = 0
    map%a2 = msq_max - msq_min
    map%a3 = map%a2 / s
    map%a_unknown = .false.
  end if

⟨Apply trivial msq mapping⟩≡
  msq = (1-x) * msq_min + x * msq_max
  f = map%a3

⟨Apply inverse trivial msq mapping⟩≡
  if (map%a2 /= 0) then
    x = (msq - msq_min) / map%a2
  else
    x = 0
  end if
  f = map%a3

```

Resonance or step mapping does not make much sense if the resonance mass is outside the kinematical bounds. If this is the case, revert to `NO_MAPPING`. This is possible even if the kinematical bounds vary from event to event.

```

⟨Modify mapping type if necessary⟩≡
  select case (type)
  case (S_CHANNEL, STEP_MAPPING_E, STEP_MAPPING_H)
    msq0 = map%mass**2
    if (msq0 < msq_min .or. msq0 > msq_max) type = NO_MAPPING
  end select

```

Breit-Wigner mapping

A Breit-Wigner resonance with mass M and width Γ is flattened by the following mapping:

This mapping does not make much sense if the resonance mass is too low. If this is the case, revert to `NO_MAPPING`. There is a tricky point with this if the

mass is too high: `msq_max` is not a constant if structure functions are around. However, switching the type depending on the overall energy does not change the integral, it is just another branching point.

$$m^2 = M(M + t\Gamma), \quad (18.16)$$

where

$$t = \tan \left[(1-x) \arctan \frac{m_{\min}^2 - M^2}{M\Gamma} + x \arctan \frac{m_{\max}^2 - M^2}{M\Gamma} \right]. \quad (18.17)$$

The inverse:

$$x = \frac{\arctan \frac{m^2 - M^2}{M\Gamma} - \arctan \frac{m_{\min}^2 - M^2}{M\Gamma}}{\arctan \frac{m_{\max}^2 - M^2}{M\Gamma} - \arctan \frac{m_{\min}^2 - M^2}{M\Gamma}} \quad (18.18)$$

The phase-space factor of this transformation is

$$f(x) = \frac{M\Gamma}{s} \left(\arctan \frac{m_{\max}^2 - M^2}{M\Gamma} - \arctan \frac{m_{\min}^2 - M^2}{M\Gamma} \right) (1 + t^2). \quad (18.19)$$

This maps any function proportional to

$$g(m^2) = \frac{M\Gamma}{(m^2 - M^2)^2 + M^2\Gamma^2} \quad (18.20)$$

to a constant times $1/s$.

```

⟨Constants for s-channel resonance mapping⟩≡
  if (map%variable_limits .or. map%a_unknown) then
    msq0 = map%mass ** 2
    map%a1 = atan ((msq_min - msq0) / (map%mass * map%width))
    map%a2 = atan ((msq_max - msq0) / (map%mass * map%width))
    map%a3 = (map%a2 - map%a1) * (map%mass * map%width) / s
    map%a_unknown = .false.
  end if

⟨Apply s-channel resonance mapping⟩≡
  z = (1-x) * map%a1 + x * map%a2
  if (-pi/2 < z .and. z < pi/2) then
    tmp = tan (z)
    msq = map%mass * (map%mass + map%width * tmp)
    f = map%a3 * (1 + tmp**2)
  else
    msq = 0
    f = 0
  end if

⟨Apply inverse s-channel resonance mapping⟩≡
  tmp = (msq - msq0) / (map%mass * map%width)
  x = (atan (tmp) - map%a1) / (map%a2 - map%a1)
  f = map%a3 * (1 + tmp**2)

```

Mapping for massless splittings

This mapping accounts for approximately scale-invariant behavior where $\ln M^2$ is evenly distributed.

$$m^2 = m_{\min}^2 + M^2 (\exp(xL) - 1) \quad (18.21)$$

where

$$L = \ln \left(\frac{m_{\max}^2 - m_{\min}^2}{M^2} + 1 \right). \quad (18.22)$$

The inverse:

$$x = \frac{1}{L} \ln \left(\frac{m^2 - m_{\min}^2}{M^2} + 1 \right) \quad (18.23)$$

The constant M is a characteristic scale. Above this scale ($m^2 - m_{\min}^2 \gg M^2$), this mapping behaves like $x \propto \ln m^2$, while below the scale it reverts to a linear mapping.

The phase-space factor is

$$f(x) = \frac{M^2}{s} \exp(xL) L. \quad (18.24)$$

A function proportional to

$$g(m^2) = \frac{1}{(m^2 - m_{\min}^2) + M^2} \quad (18.25)$$

is mapped to a constant, i.e., a simple pole near m_{\min} with a regulator mass M .

This type of mapping is useful for massless collinear and infrared singularities, where the scale is stored as the mass parameter. In the radiation case (IR radiation off massive particle), the heavy particle width is the characteristic scale.

```

⟨Constants for s-channel pole mapping⟩≡
    if (map%variable_limits .or. map%a_unknown) then
        if (type == RADIATION) then
            msq0 = map%width**2
        else
            msq0 = map%mass**2
        end if
        map%a1 = msq0
        map%a2 = log ((msq_max - msq_min) / msq0 + 1)
        map%a3 = map%a2 / s
        map%a_unknown = .false.
    end if

⟨Apply s-channel pole mapping⟩≡
    msq1 = map%a1 * exp (x * map%a2)
    msq = msq1 - map%a1 + msq_min
    f = map%a3 * msq1

⟨Apply inverse s-channel pole mapping⟩≡
    msq1 = msq - msq_min + map%a1
    x = log (msq1 / map%a1) / map%a2
    f = map%a3 * msq1

```


Mapping for t-channel poles

This is also approximately scale-invariant, and we use the same type of mapping as before. However, we map $1/x$ singularities at both ends of the interval; again, the mapping becomes linear when the distance is less than M^2 :

$$m^2 = \begin{cases} m_{\min}^2 + M^2 (\exp(xL) - 1) & \text{for } 0 < x < \frac{1}{2} \\ m_{\max}^2 - M^2 (\exp((1-x)L) - 1) & \text{for } \frac{1}{2} \leq x < 1 \end{cases} \quad (18.26)$$

where

$$L = 2 \ln \left(\frac{m_{\max}^2 - m_{\min}^2}{2M^2} + 1 \right). \quad (18.27)$$

The inverse:

$$x = \begin{cases} \frac{1}{L} \ln \left(\frac{m^2 - m_{\min}^2}{M^2} + 1 \right) & \text{for } m^2 < (m_{\max}^2 - m_{\min}^2)/2 \\ 1 - \frac{1}{L} \ln \left(\frac{m_{\max}^2 - m^2}{M^2} + 1 \right) & \text{for } m^2 \geq (m_{\max}^2 - m_{\min}^2)/2 \end{cases} \quad (18.28)$$

The phase-space factor is

$$f(x) = \begin{cases} \frac{M^2}{s} \exp(xL) L. & \text{for } 0 < x < \frac{1}{2} \\ \frac{M^2}{s} \exp((1-x)L) L. & \text{for } \frac{1}{2} \leq x < 1 \end{cases} \quad (18.29)$$

A (continuous) function proportional to

$$g(m^2) = \begin{cases} 1/(m^2 - m_{\min}^2) + M^2 & \text{for } m^2 < (m_{\max}^2 - m_{\min}^2)/2 \\ 1/((m_{\max}^2 - m^2) + M^2) & \text{for } m^2 \geq (m_{\max}^2 - m_{\min}^2)/2 \end{cases} \quad (18.30)$$

is mapped to a constant by this mapping, i.e., poles near both ends of the interval.

```

⟨Constants for t-channel pole mapping⟩≡
  if (map%variable_limits .or. map%a_unknown) then
    msq0 = map%mass**2
    map%a1 = msq0
    map%a2 = 2 * log ((msq_max - msq_min)/(2*msq0) + 1)
    map%a3 = map%a2 / s
    map%a_unknown = .false.
  end if

⟨Apply t-channel pole mapping⟩≡
  if (x < .5_default) then
    msq1 = map%a1 * exp (x * map%a2)
    msq = msq1 - map%a1 + msq_min
  else
    msq1 = map%a1 * exp ((1-x) * map%a2)
    msq = -(msq1 - map%a1) + msq_max
  end if
  f = map%a3 * msq1

⟨Apply inverse t-channel pole mapping⟩≡
  if (msq < (msq_max + msq_min)/2) then
    msq1 = msq - msq_min + map%a1
    x = log (msq1/map%a1) / map%a2

```

```

else
  msq1 = msq_max - msq + map%a1
  x = 1 - log (msq1/map%a1) / map%a2
end if
f = map%a3 * msq1

```

18.3.8 Step mapping

Step mapping is useful when the allowed range for a squared-mass variable is large, but only a fraction at the lower end is populated because the particle in question is an (off-shell) decay product of a narrow resonance. I.e., if the resonance was forced to be on-shell, the upper end of the range would be the resonance mass, minus the effective (real or resonance) mass of the particle(s) in the sibling branch of the decay.

The edge of this phase space section has a width which is determined by the width of the parent, plus the width of the sibling branch. (The widths might be added in quadrature, but this precision is probably not important.)

Fermi function

A possible mapping is derived from the Fermi function which has precisely this behavior. The Fermi function is given by

$$f(x) = \frac{1}{1 + \exp \frac{x-\mu}{\gamma}} \quad (18.31)$$

where x is taken as the invariant mass squared, μ is the invariant mass squared of the edge, and γ is the effective width which is given by the widths of the parent and the sibling branch. (Widths might be added in quadrature, but we do not require this level of precision.)

$$x = \frac{m^2 - m_{\min}^2}{\Delta m^2} \quad (18.32)$$

$$\mu = \frac{m_{\max, \text{eff}}^2 - m_{\min}^2}{\Delta m^2} \quad (18.33)$$

$$\gamma = \frac{2m_{\max, \text{eff}}\Gamma}{\Delta m^2} \quad (18.34)$$

with

$$\Delta m^2 = m_{\max}^2 - m_{\min}^2 \quad (18.35)$$

m^2 is thus given by

$$m^2(x) = xm_{\max}^2 + (1-x)m_{\min}^2 \quad (18.36)$$

For the mapping, we compute the integral $g(x)$ of the Fermi function, normalized such that $g(0) = 0$ and $g(1) = 1$. We introduce the abbreviations

$$\alpha = 1 - \gamma \ln \frac{1 + \beta e^{1/\gamma}}{1 + \beta} \quad (18.37)$$

$$\beta = e^{-\mu/\gamma} \quad (18.38)$$

and obtain

$$g(x) = \frac{1}{\alpha} \left(x - \gamma \ln \frac{1 + \beta e^{x/\gamma}}{1 + \beta} \right) \quad (18.39)$$

The actual mapping is the inverse function $h(y) = g^{-1}(y)$,

$$h(y) = -\gamma \ln \left(e^{-\alpha y/\gamma} (1 + \beta) - \beta \right) \quad (18.40)$$

The Jacobian is

$$\frac{dh}{dy} = \alpha \left(1 - e^{\alpha y/\gamma} \frac{\beta}{1 + \beta} \right)^{-1} \quad (18.41)$$

which is equal to $1/(dg/dx)$, namely

$$\frac{dg}{dx} = \frac{1}{\alpha} \frac{1}{1 + \beta e^{x/\gamma}} \quad (18.42)$$

The final result is

$$\int_{m_{\min}^2}^{m_{\max}^2} dm^2 F(m^2) = \Delta m^2 \int_0^1 dx F(m^2(x)) \quad (18.43)$$

$$= \Delta m^2 \int_0^1 dy F(m^2(h(y))) \frac{dh}{dy} \quad (18.44)$$

Here is the implementation. We fill `a1`, `a2`, `a3` with α, β, γ , respectively.

```

<Constants for exponential step mapping>≡
  if (map%variable_limits .or. map%a_unknown) then
    map%a3 = max (2 * map%mass * map%width / (msq_max - msq_min), 0.01_default)
    map%a2 = exp (- (map%mass**2 - msq_min) / (msq_max - msq_min) &
                  / map%a3)
    map%a1 = 1 - map%a3 * log ((1 + map%a2 * exp (1 / map%a3)) / (1 + map%a2))
  end if

<Apply exponential step mapping>≡
  tmp = exp (- x * map%a1 / map%a3) * (1 + map%a2)
  z = - map%a3 * log (tmp - map%a2)
  msq = z * msq_max + (1 - z) * msq_min
  f = map%a1 / (1 - map%a2 / tmp) * (msq_max - msq_min) / s

<Apply inverse exponential step mapping>≡
  z = (msq - msq_min) / (msq_max - msq_min)
  tmp = 1 + map%a2 * exp (z / map%a3)
  x = (z - map%a3 * log (tmp / (1 + map%a2))) &
      / map%a1
  f = map%a1 * tmp * (msq_max - msq_min) / s

```

Hyperbolic mapping

The Fermi function has the drawback that it decreases exponentially. It might be preferable to take a function with a power-law decrease, such that the high-mass region is not completely depopulated.

Here, we start with the actual mapping which we take as

$$h(y) = \frac{b}{a - y} - \frac{b}{a} + \mu y \quad (18.45)$$

with the abbreviation

$$a = \frac{1}{2} \left(1 + \sqrt{1 + \frac{4b}{1-\mu}} \right) \quad (18.46)$$

This is a hyperbola in the xy plane. The derivative is

$$\frac{dh}{dy} = \frac{b}{(a-y)^2} + \mu \quad (18.47)$$

The constants correspond to

$$\mu = \frac{m_{\max, \text{eff}}^2 - m_{\min}^2}{\Delta m^2} \quad (18.48)$$

$$b = \frac{1}{\mu} \left(\frac{2m_{\max, \text{eff}} \Gamma}{\Delta m^2} \right)^2 \quad (18.49)$$

The inverse function is the solution of a quadratic equation,

$$g(x) = \frac{1}{2} \left[\left(a + \frac{x}{\mu} + \frac{b}{a\mu} \right) - \sqrt{\left(a - \frac{x}{\mu} \right)^2 + 2 \frac{b}{a\mu} \left(a + \frac{x}{\mu} \right) + \left(\frac{b}{a\mu} \right)^2} \right] \quad (18.50)$$

The constants $a_{1,2,3}$ are identified with a, b, μ .

```

<Constants for hyperbolic step mapping>≡
  if (map%variable_limits .or. map%a_unknown) then
    map%a3 = (map%mass**2 - msq_min) / (msq_max - msq_min)
    map%a2 = max ((2 * map%mass * map%width / (msq_max - msq_min))**2 &
                  / map%a3, 1e-6_default)
    map%a1 = (1 + sqrt (1 + 4 * map%a2 / (1 - map%a3))) / 2
  end if

<Apply hyperbolic step mapping>≡
  z = map%a2 / (map%a1 - x) - map%a2 / map%a1 + map%a3 * x
  msq = z * msq_max + (1 - z) * msq_min
  f = (map%a2 / (map%a1 - x)**2 + map%a3) * (msq_max - msq_min) / s

<Apply inverse hyperbolic step mapping>≡
  z = (msq - msq_min) / (msq_max - msq_min)
  tmp = map%a2 / (map%a1 * map%a3)
  x = ((map%a1 + z / map%a3 + tmp) &
        - sqrt ((map%a1 - z / map%a3)**2 + 2 * tmp * (map%a1 + z / map%a3) &
                + tmp**2)) / 2
  f = (map%a2 / (map%a1 - x)**2 + map%a3) * (msq_max - msq_min) / s

```

18.3.9 Mappings of the polar angle

The other type of singularity, a simple pole just outside the integration region, can occur in the integration over $\cos \theta$. This applies to exchange of massless (or light) particles.

Double poles (Coulomb scattering) are also possible, but only in certain cases. These are also handled by the single-pole mapping.

The mapping is analogous to the previous m^2 pole mapping, but with a different normalization and notation of variables:

$$\frac{1}{2} \int_{-1}^1 d \cos \theta g(\theta) = \int_0^1 dx \frac{d \cos \theta}{dx} g(\theta(x)) = \int_0^1 dx f(x) g(x), \quad (18.51)$$

where thus

$$f(x) = \frac{1}{2} \frac{d \cos \theta}{dx}. \quad (18.52)$$

With this mapping, a function of the form

$$g(\theta) = c \frac{dx(\cos \theta)}{d \cos \theta} \quad (18.53)$$

is mapped to a constant:

$$\int_{-1}^1 d \cos \theta g(\theta) = \int_0^1 dx f(x) g(\theta(x)) = \int_0^1 dx c. \quad (18.54)$$

```

<Mappings: public>+≡
  public :: mapping_compute_ct_from_x

<Mappings: procedures>+≡
  subroutine mapping_compute_ct_from_x (map, s, ct, st, f, x)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: s
    real(default), intent(out) :: ct, st, f
    real(default), intent(in) :: x
    real(default) :: tmp, ct1
    select case (map%type)
    case (NO_MAPPING, S_CHANNEL, INFRARED, RADIATION, &
          STEP_MAPPING_E, STEP_MAPPING_H)
      <Apply trivial ct mapping>
    case (T_CHANNEL, U_CHANNEL, COLLINEAR)
      <Constants for ct pole mapping>
      <Apply ct pole mapping>
    case default
      call msg_fatal (" Attempt to apply undefined ct mapping")
    end select
  end subroutine mapping_compute_ct_from_x

<Mappings: public>+≡
  public :: mapping_compute_x_from_ct

<Mappings: procedures>+≡
  subroutine mapping_compute_x_from_ct (map, s, ct, f, x)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: s
    real(default), intent(in) :: ct
    real(default), intent(out) :: f, x
    real(default) :: ct1
    select case (map%type)
    case (NO_MAPPING, S_CHANNEL, INFRARED, RADIATION, &
          STEP_MAPPING_E, STEP_MAPPING_H)
      <Apply inverse trivial ct mapping>

```

```

case (T_CHANNEL, U_CHANNEL, COLLINEAR)
  <Constants for ct pole mapping>
  <Apply inverse ct pole mapping>
case default
  call msg_fatal (" Attempt to apply undefined inverse ct mapping")
end select
end subroutine mapping_compute_x_from_ct

```

Trivial mapping

This is just the mapping of the interval $(-1, 1)$ to $(0, 1)$:

$$\cos \theta = -1 + 2x \quad (18.55)$$

and

$$f(x) = 1 \quad (18.56)$$

with the inverse

$$x = \frac{1 + \cos \theta}{2} \quad (18.57)$$

```

<Apply trivial ct mapping>≡
  tmp = 2 * (1-x)
  ct = 1 - tmp
  st = sqrt (tmp * (2-tmp))
  f = 1
<Apply inverse trivial ct mapping>≡
  x = (ct + 1) / 2
  f = 1

```

Pole mapping

As above for m^2 , we simultaneously map poles at both ends of the $\cos \theta$ interval. The formulae are completely analogous:

$$\cos \theta = \begin{cases} \frac{M^2}{s} [\exp(xL) - 1] - 1 & \text{for } x < \frac{1}{2} \\ -\frac{M^2}{s} [\exp((1-x)L) - 1] + 1 & \text{for } x \geq \frac{1}{2} \end{cases} \quad (18.58)$$

where

$$L = 2 \ln \frac{M^2 + s}{M^2}. \quad (18.59)$$

Inverse:

$$x = \begin{cases} \frac{1}{2L} \ln \frac{1 + \cos \theta + M^2/s}{M^2/s} & \text{for } \cos \theta < 0 \\ 1 - \frac{1}{2L} \ln \frac{1 - \cos \theta + M^2/s}{M^2/s} & \text{for } \cos \theta \geq 0 \end{cases} \quad (18.60)$$

The phase-space factor:

$$f(x) = \begin{cases} \frac{M^2}{s} \exp(xL) L & \text{for } x < \frac{1}{2} \\ \frac{M^2}{s} \exp((1-x)L) L & \text{for } x \geq \frac{1}{2} \end{cases} \quad (18.61)$$

```

<Constants for ct pole mapping>≡
  if (map%variable_limits .or. map%b_unknown) then

```

```

        map%b1 = map%mass**2 / s
        map%b2 = log ((map%b1 + 1) / map%b1)
        map%b3 = 0
        map%b_unknown = .false.
    end if

    <Apply ct pole mapping>≡
    if (x < .5_default) then
        ct1 = map%b1 * exp (2 * x * map%b2)
        ct = ct1 - map%b1 - 1
    else
        ct1 = map%b1 * exp (2 * (1-x) * map%b2)
        ct = -(ct1 - map%b1) + 1
    end if
    if (ct >= -1 .and. ct <= 1) then
        st = sqrt (1 - ct**2)
        f = ct1 * map%b2
    else
        ct = 1;  st = 0;  f = 0
    end if

    <Apply inverse ct pole mapping>≡
    if (ct < 0) then
        ct1 = ct + map%b1 + 1
        x = log (ct1 / map%b1) / (2 * map%b2)
    else
        ct1 = -ct + map%b1 + 1
        x = 1 - log (ct1 / map%b1) / (2 * map%b2)
    end if
    f = ct1 * map%b2

```

18.4 Phase-space trees

The phase space evaluation is organized in terms of trees, where each branch corresponds to three integrations: m^2 , $\cos\theta$, and ϕ . The complete tree thus makes up a specific parameterization of the multidimensional phase-space integral. For the multi-channel integration, the phase-space tree is a single channel.

The trees imply mappings of formal Feynman tree graphs into arrays of integer numbers: Each branch, corresponding to a particular line in the graph, is assigned an integer code c (with kind value $\text{TC} = \text{tree code}$).

In this integer, each bit determines whether a particular external momentum flows through the line. The external branches therefore have codes 1, 2, 4, 8, ... An internal branch has those bits ORed corresponding to the momenta flowing through it. For example, a branch with momentum $p_1 + p_4$ has code $2^0 + 2^3 = 1 + 8 = 9$.

There is a two-fold ambiguity: Momentum conservation implies that the branch with code

$$c_0 = \sum_{i=1}^{n(\text{ext})} 2^{i-1} \quad (18.62)$$

i.e. the branch with momentum $p_1 + p_2 + \dots p_n$ has momentum zero, which is equivalent to tree code 0 by definition. Correspondingly,

$$c \quad \text{and} \quad c_0 - c = c \text{ XOR } c_0 \quad (18.63)$$

are equivalent. E.g., if there are five externals with codes $c = 1, 2, 4, 8, 16$, then $c = 9$ and $\bar{c} = 31 - 9 = 22$ are equivalent.

This ambiguity may be used to assign a direction to the line: If all momenta are understood as outgoing, $c = 9$ in the example above means $p_1 + p_4$, but $c = 22$ means $p_2 + p_3 + p_5 = -(p_1 + p_4)$.

Here we make use of the ambiguity in a slightly different way. First, the initial particles are singled out as those externals with the highest bits, the IN-bits. (Here: 8 and 16 for a $2 \rightarrow 3$ scattering process, 16 only for a $1 \rightarrow 4$ decay.) Then we invert those codes where all IN-bits are set. For a decay process this maps each tree of an equivalence class onto a unique representative (that one with the smallest integer codes). For a scattering process we proceed further:

The ambiguity remains in all branches where only one IN-bit is set, including the initial particles. If there are only externals with this property, we have an s -channel graph which we leave as it is. In all other cases, an internal with only one IN-bit is a t -channel line, which for phase space integration should be associated with one of the initial momenta as a reference axis. We take that one whose bit is set in the current tree code. (E.g., for branch $c = 9$ we use the initial particle $c = 8$ as reference axis, whereas for the same branch we would take $c = 16$ if it had been assigned $\bar{c} = 31 - 9 = 22$ as tree code.) Thus, different ways of coding the same t -channel graph imply different phase space parameterizations.

s -channel graphs have a unique parameterization. The same sets of parameterizations are used for t -channel graphs, except for the reference frames of their angular parts. We map each t -channel graph onto an s -channel graph as follows:

Working in ascending order, for each t -channel line (whose code has exactly one IN-bit set) the attached initial line is flipped upstream, while the outgoing

line is flipped downstream. (This works only if t -channel graphs are always parameterized beginning at their outer vertices, which we require as a restriction.) After all possible flips have been applied, we have an s -channel graph. We only have to remember the initial particle a vertex was originally attached to.

```

<phs_trees.f90>≡
  <File header>

  module phs_trees

    <Use kinds>
      use kinds, only: TC
    <Use strings>
      use io_units
      use constants, only: twopi, twopi2, twopi5
      use format_defs, only: FMT_19
      use diagnostics
      use lorentz
      use permutations, only: permutation_t, permutation_size
      use permutations, only: permutation_init, permutation_find
      use permutations, only: tc_decay_level, tc_permute
      use model_data
      use flavors
      use mappings

    <Standard module head>

    <PHS trees: public>

    <PHS trees: types>

    contains

    <PHS trees: procedures>

  end module phs_trees

```

18.4.1 Particles

We define a particle type which contains only four-momentum and invariant mass squared, and a flag that tells whether the momentum is filled or not.

```

<PHS trees: public>≡
  public :: phs_prt_t
<PHS trees: types>≡
  type :: phs_prt_t
    private
    logical :: defined = .false.
    type(vector4_t) :: p
    real(default) :: p2
  end type phs_prt_t

```

Set contents:

```

<PHS trees: public>+≡

```

```

public :: phs_prt_set_defined
public :: phs_prt_set_undefined
public :: phs_prt_set_momentum
public :: phs_prt_set_msq

<PHS trees: procedures>≡
elemental subroutine phs_prt_set_defined (prt)
  type(phs_prt_t), intent(inout) :: prt
  prt%defined = .true.
end subroutine phs_prt_set_defined

elemental subroutine phs_prt_set_undefined (prt)
  type(phs_prt_t), intent(inout) :: prt
  prt%defined = .false.
end subroutine phs_prt_set_undefined

elemental subroutine phs_prt_set_momentum (prt, p)
  type(phs_prt_t), intent(inout) :: prt
  type(vector4_t), intent(in) :: p
  prt%p = p
end subroutine phs_prt_set_momentum

elemental subroutine phs_prt_set_msq (prt, p2)
  type(phs_prt_t), intent(inout) :: prt
  real(default), intent(in) :: p2
  prt%p2 = p2
end subroutine phs_prt_set_msq

```

Access methods:

```

<PHS trees: public>+≡
public :: phs_prt_is_defined
public :: phs_prt_get_momentum
public :: phs_prt_get_msq

<PHS trees: procedures>+≡
elemental function phs_prt_is_defined (prt) result (defined)
  logical :: defined
  type(phs_prt_t), intent(in) :: prt
  defined = prt%defined
end function phs_prt_is_defined

elemental function phs_prt_get_momentum (prt) result (p)
  type(vector4_t) :: p
  type(phs_prt_t), intent(in) :: prt
  p = prt%p
end function phs_prt_get_momentum

elemental function phs_prt_get_msq (prt) result (p2)
  real(default) :: p2
  type(phs_prt_t), intent(in) :: prt
  p2 = prt%p2
end function phs_prt_get_msq

```

Addition of momenta (invariant mass square is computed).

```

<PHS trees: public>+≡
    public :: phs_prt_combine

<PHS trees: procedures>+≡
    elemental subroutine phs_prt_combine (prt, prt1, prt2)
        type(phs_prt_t), intent(inout) :: prt
        type(phs_prt_t), intent(in) :: prt1, prt2
        prt%defined = .true.
        prt%p = prt1%p + prt2%p
        prt%p2 = prt%p ** 2
        call phs_prt_check (prt)
    end subroutine phs_prt_combine

```

Output

```

<PHS trees: public>+≡
    public :: phs_prt_write

<PHS trees: procedures>+≡
    subroutine phs_prt_write (prt, unit)
        type(phs_prt_t), intent(in) :: prt
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        if (prt%defined) then
            call vector4_write (prt%p, u)
            write (u, "(1x,A,1x," // FMT_19 // ")") "T = ", prt%p2
        else
            write (u, "(3x,A)") "[undefined]"
        end if
    end subroutine phs_prt_write

<PHS trees: public>+≡
    public :: phs_prt_check

<PHS trees: procedures>+≡
    elemental subroutine phs_prt_check (prt)
        type(phs_prt_t), intent(inout) :: prt
        real(default), parameter :: eps = 1E-9
        if (prt%p2 < 0._default) then
            prt%p2 = 0._default
        end if
    end subroutine phs_prt_check

```

18.4.2 The phase-space tree type

Definition

In the concrete implementation, each branch c may have two *daughters* c_1 and c_2 such that $c_1 + c_2 = c$, a *sibling* c_s and a *mother* c_m such that $c + c_s = c_m$, and a *friend* which is kept during flips, such that it can indicate a fixed reference frame. Absent entries are set $c = 0$.

First, declare the branch type. There is some need to have this public. Give initializations for all components, so no `init` routine is necessary. The branch has some information about the associated coordinates and about connections.

```

(PHS trees: types)+≡
  type :: phs_branch_t
    private
      logical :: set = .false.
      logical :: inverted_decay = .false.
      logical :: inverted_axis = .false.
      integer(TC) :: mother = 0
      integer(TC) :: sibling = 0
      integer(TC) :: friend = 0
      integer(TC) :: origin = 0
      integer(TC), dimension(2) :: daughter = 0
      integer :: firstborn = 0
      logical :: has_children = .false.
      logical :: has_friend = .false.
      logical :: is_real = .false.
    end type phs_branch_t

```

The tree type: No initialization, this is done by `phs_tree_init`. In addition to the branch array which

The branches are collected in an array which holds all possible branches, of which only a few are set. After flips have been applied, the branch $c_M = \sum_{i=1}^{n(\text{fin})} 2^{i-1}$ must be there, indicating the mother of all decay products. In addition, we should check for consistency at the beginning.

`n_branches` is the number of those actually set. `n externals` defines the number of significant bit, and `mask` is a code where all bits are set. Analogous: `n_in` and `mask_in` for the incoming particles.

The mapping array contains the mappings associated to the branches (corresponding indices). The array `mass_sum` contains the sum of the real masses of the external final-state particles associated to the branch. During phase-space evaluation, this determines the boundaries.

```

(PHS trees: public)+≡
  public :: phs_tree_t

(PHS trees: types)+≡
  type :: phs_tree_t
    private
      integer :: n_branches, n externals, n_in, n_msq, n_angles
      integer(TC) :: n_branches_tot, n_branches_out
      integer(TC) :: mask, mask_in, mask_out
      type(phs_branch_t), dimension(:), allocatable :: branch
      type(mapping_t), dimension(:), allocatable :: mapping
      real(default), dimension(:), allocatable :: mass_sum
      real(default), dimension(:), allocatable :: effective_mass
      real(default), dimension(:), allocatable :: effective_width
      logical :: real_phsp = .false.
      integer(TC) :: emitter = 0
      integer, dimension(:), allocatable :: momentum_link
    contains
      (PHS trees: phs tree: TBP)

```

```
end type phs_tree_t
```

The maximum number of external particles that can be represented is related to the bit size of the integer that stores binary codes. With the default integer of 32 bit on common machines, this is more than enough space. If TC is actually the default integer kind, there is no need to keep it separate, but doing so marks this as a special type of integer. So, just state that the maximum number is 32:

```
<Limits: public parameters>≡
integer, parameter, public :: MAX_EXTERNAL = 32
```

Constructor and destructor

Allocate memory for a phase-space tree with given number of externals and incoming. The number of allocated branches can easily become large, but appears manageable for realistic cases, e.g., for `n_in=2` and `n_out=8` we get $2^{10} - 1 = 1023$.

```
<PHS trees: public>+≡
public :: phs_tree_init
public :: phs_tree_final
```

Here we set the masks for incoming and for all externals.

```
<PHS trees: procedures>+≡
elemental subroutine phs_tree_init (tree, n_in, n_out, n_masses, n_angles)
type(phs_tree_t), intent(inout) :: tree
integer, intent(in) :: n_in, n_out, n_masses, n_angles
integer(TC) :: i
tree%n_externals = n_in + n_out
tree%n_branches_tot = 2**(n_in+n_out) - 1
tree%n_branches_out = 2**n_out - 1
tree%mask = 0
do i = 0, n_in + n_out - 1
tree%mask = ibset (tree%mask, i)
end do
tree%n_in = n_in
tree%mask_in = 0
do i = n_out, n_in + n_out - 1
tree%mask_in = ibset (tree%mask_in, i)
end do
tree%mask_out = ieor (tree%mask, tree%mask_in)
tree%n_msq = n_masses
tree%n_angles = n_angles
allocate (tree%branch (tree%n_branches_tot))
tree%n_branches = 0
allocate (tree%mapping (tree%n_branches_out))
allocate (tree%mass_sum (tree%n_branches_out))
allocate (tree%effective_mass (tree%n_branches_out))
allocate (tree%effective_width (tree%n_branches_out))
end subroutine phs_tree_init

elemental subroutine phs_tree_final (tree)
type(phs_tree_t), intent(inout) :: tree
deallocate (tree%branch)
deallocate (tree%mapping)
```

```

deallocate (tree%mass_sum)
deallocate (tree%effective_mass)
deallocate (tree%effective_width)
end subroutine phs_tree_final

```

Screen output

Write only the branches that are set:

<PHS trees: public>+≡

```
public :: phs_tree_write
```

<PHS trees: procedures>+≡

```

subroutine phs_tree_write (tree, unit)
  type(phs_tree_t), intent(in) :: tree
  integer, intent(in), optional :: unit
  integer :: u
  integer(TC) :: k
  u = given_output_unit (unit); if (u < 0) return
  write (u, '(3X,A,1x,I0,5X,A,I3)') &
    'External:', tree%n_externals, 'Mask:', tree%mask
  write (u, '(3X,A,1x,I0,5X,A,I3)') &
    'Incoming:', tree%n_in, 'Mask:', tree%mask_in
  write (u, '(3X,A,1x,I0,5X,A,I3)') &
    'Branches:', tree%n_branches
  do k = size (tree%branch), 1, -1
    if (tree%branch(k)%set) &
      call phs_branch_write (tree%branch(k), unit=unit, kval=k)
  end do
  do k = 1, size (tree%mapping)
    call mapping_write (tree%mapping (k), unit, verbose=.true.)
  end do
  write (u, "(3x,A)") "Arrays: mass_sum, effective_mass, effective_width"
  do k = 1, size (tree%mass_sum)
    if (tree%branch(k)%set) then
      write (u, "(5x,I0,3(2x," // FMT_19 // ")") k, tree%mass_sum(k), &
        tree%effective_mass(k), tree%effective_width(k)
    end if
  end do
end subroutine phs_tree_write

subroutine phs_branch_write (b, unit, kval)
  type(phs_branch_t), intent(in) :: b
  integer, intent(in), optional :: unit
  integer(TC), intent(in), optional :: kval
  integer :: u
  integer(TC) :: k
  character(len=6) :: tmp
  character(len=1) :: firstborn(2), sign_decay, sign_axis
  integer :: i
  u = given_output_unit (unit); if (u < 0) return
  k = 0; if (present (kval)) k = kval
  if (b%origin /= 0) then
    write(tmp, '(A,I4,A)') '(', b%origin, ')'

```

```

else
    tmp = ' '
end if
do i=1, 2
    if (b%firstborn == i) then
        firstborn(i) = "*"
    else
        firstborn(i) = " "
    end if
end do
if (b%inverted_decay) then
    sign_decay = "-"
else
    sign_decay = "+"
end if
if (b%inverted_axis) then
    sign_axis = "-"
else
    sign_axis = "+"
end if
if (b%has_children) then
    if (b%has_friend) then
        write(u, '(4X,A1,I0,3x,A,1X,A,I0,A1,1x,I0,A1,1X,A1,1X,A,1x,I0)') &
            & ' ', k, tmp, &
            & 'Daughters: ', &
            & b%daughter(1), firstborn(1), &
            & b%daughter(2), firstborn(2), sign_decay, &
            & 'Friend: ', b%friend
    else
        write(u, '(4X,A1,I0,3x,A,1X,A,I0,A1,1x,I0,A1,1X,A1,1X,A)') &
            & ' ', k, tmp, &
            & 'Daughters: ', &
            & b%daughter(1), firstborn(1), &
            & b%daughter(2), firstborn(2), sign_decay, &
            & '(axis '//sign_axis//')'
    end if
else
    write(u, '(5X,I0)') k
end if
end subroutine phs_branch_write

```

18.4.3 PHS tree setup

Transformation into an array of branch codes and back

Assume that the tree/array has been created before with the appropriate length and is empty.

```

<PHS trees: public>+≡
    public :: phs_tree_from_array

<PHS trees: procedures>+≡
    subroutine phs_tree_from_array (tree, a)
        type(phs_tree_t), intent(inout) :: tree

```

```

integer(TC), dimension(:), intent(in) :: a
integer :: i
integer(TC) :: k
<Set branches from array a>
<Set external branches if necessary>
<Check number of branches>
<Determine the connections>
contains
<Subroutine: set relatives>
end subroutine phs_tree_from_array

```

First, set all branches specified by the user. If all IN-bits are set, we invert the branch code.

```

<Set branches from array a>≡
do i=1, size(a)
  k = a(i)
  if (iand(k, tree%mask_in) == tree%mask_in) k = ieor(tree%mask, k)
  tree%branch(k)%set = .true.
  tree%n_branches = tree%n_branches+1
end do

```

The external branches are understood, so set them now if not yet done. In all cases ensure that the representative with one bit set is used, except for decays where the in-particle is represented by all OUT-bits set instead.

```

<Set external branches if necessary>≡
do i=0, tree%n externals-1
  k = ibset(0,i)
  if (iand(k, tree%mask_in) == tree%mask_in) k = ieor(tree%mask, k)
  if (tree%branch(ieor(tree%mask, k))%set) then
    tree%branch(ieor(tree%mask, k))%set = .false.
    tree%branch(k)%set = .true.
  else if (.not.tree%branch(k)%set) then
    tree%branch(k)%set = .true.
    tree%n_branches = tree%n_branches+1
  end if
end do

```

Now the number of branches set can be checked. Here we assume that the tree is binary. For three externals there are three branches in total, and for each additional external branch we get another internal one.

```

<Check number of branches>≡
if (tree%n_branches /= tree%n externals*2-3) then
  call phs_tree_write (tree)
  call msg_bug &
    & (" Wrong number of branches set in phase space tree")
end if

```

For all branches that are set, except for the externals, we try to find the daughter branches:

```

<Determine the connections>≡
do k=1, size (tree%branch)
  if (tree%branch(k)%set .and. tc_decay_level (k) /= 1) then
    call branch_set_relatives(k)
  end if
end do

```


To this end, we scan all codes less than the current code, whether we can find two branches which are set and which together give the current code. After that, the tree may still not be connected, but at least we know if a branch does not have daughters: This indicates some inconsistency.

The algorithm ensures that, at this stage, the first daughter has a smaller code value than the second one.

```

(Subroutine: set relatives)≡
subroutine branch_set_relatives (k)
  integer(TC), intent(in) :: k
  integer(TC) :: m,n
  do m=1, k-1
    if(iand(k,m)==m) then
      n = ieor(k,m)
      if ( tree%branch(m)%set .and. tree%branch(n)%set ) then
        tree%branch(k)%daughter(1) = m; tree%branch(k)%daughter(2) = n
        tree%branch(m)%mother      = k; tree%branch(n)%mother      = k
        tree%branch(m)%sibling      = n; tree%branch(n)%sibling      = m
        tree%branch(k)%has_children = .true.
        return
      end if
    end if
  end do
  call phs_tree_write (tree)
  call msg_bug &
    & (" Missing daughter branch(es) in phase space tree")
end subroutine branch_set_relatives

```

The inverse: this is trivial, fortunately.

Flip t -channel into s -channel

Flipping the tree is done upwards, beginning from the decay products. First we select a t -channel branch k : one which is set, which does have an IN-bit, and which is not an external particle.

Next, we determine the adjacent in-particle (called the 'friend' f here, since it will provide the reference axis for the angular integration). In addition, we look for the 'mother' and 'sibling' of this particle. If the latter field is empty, we select the (unique) other out-particle which has no mother, calling the internal subroutine `find_orphan`.

The flip is done as follows: We assume that the first daughter d is an s -channel line, which is true if the daughters are sorted. This will stay the first daughter. The second one is a t -channel line; it is exchanged with the 'sibling' s . The new line which replaces the branch k is just the sum of s and d . In addition, we have to rearrange the relatives of s and d , as well of f .

Finally, we flip 'sibling' and 'friend' and set the new s -channel branch n which replaces the t -channel branch k . After this is complete, we are ready to execute another flip.

[Although the friend is not needed for the final flip, since it would be an initial particle anyway, we need to know whether we have t - or u -channel.]

```

(PHS trees: public)+≡
public :: phs_tree_flip_t_to_s_channel

```

(PHS trees: procedures)+≡

```

subroutine phs_tree_flip_t_to_s_channel (tree)
  type(phs_tree_t), intent(inout) :: tree
  integer(TC) :: k, f, m, n, d, s
  if (tree%n_in == 2) then
    FLIP: do k=3, tree%mask-1
      if (.not. tree%branch(k)%set) cycle FLIP
      f = iand(k,tree%mask_in)
      if (f==0 .or. f==k) cycle FLIP
      m = tree%branch(k)%mother
      s = tree%branch(k)%sibling
      if (s==0) call find_orphan(s)
      d = tree%branch(k)%daughter(1)
      n = ior(d,s)
      tree%branch(k)%set = .false.
      tree%branch(n)%set = .true.
      tree%branch(n)%origin = k
      tree%branch(n)%daughter(1) = d; tree%branch(d)%mother = n
      tree%branch(n)%daughter(2) = s; tree%branch(s)%mother = n
      tree%branch(n)%has_children = .true.
      tree%branch(d)%sibling = s; tree%branch(s)%sibling = d
      tree%branch(n)%sibling = f; tree%branch(f)%sibling = n
      tree%branch(n)%mother = m
      tree%branch(f)%mother = m
      if (m/=0) then
        tree%branch(m)%daughter(1) = n
        tree%branch(m)%daughter(2) = f
      end if
      tree%branch(n)%friend = f
      tree%branch(n)%has_friend = .true.
      tree%branch(n)%firstborn = 2
    end do FLIP
  end if
contains
  subroutine find_orphan(s)
    integer(TC) :: s
    do s=1, tree%mask_out
      if (tree%branch(s)%set .and. tree%branch(s)%mother==0) return
    end do
    call phs_tree_write (tree)
    call msg_bug (" Can't flip phase space tree to channel")
  end subroutine find_orphan
end subroutine phs_tree_flip_t_to_s_channel

```

After the tree has been flipped, one may need to determine what has become of a particular *t*-channel branch. This function gives the bincode of the flipped tree. If the original bincode does not contain IN-bits, we leave it as it is.

(PHS trees: procedures)+≡

```

function tc_flipped (tree, kt) result (ks)
  type(phs_tree_t), intent(in) :: tree
  integer(TC), intent(in) :: kt
  integer(TC) :: ks
  if (iand (kt, tree%mask_in) == 0) then

```

```

        ks = kt
    else
        ks = tree%branch(iand (kt, tree%mask_out))%mother
    end if
end function tc_flipped

```

Scan a tree and make sure that the first daughter has always a smaller code than the second one. Furthermore, delete any **friend** entry in the root branch – this branching has the incoming particle direction as axis anyway. Keep track of reordering by updating **inverted_axis**, **inverted_decay** and **firstborn**.

```

<PHS trees: public>+≡
    public :: phs_tree_canonicalize

<PHS trees: procedures>+≡
    subroutine phs_tree_canonicalize (tree)
        type(phs_tree_t), intent(inout) :: tree
        integer :: n_out
        integer(TC) :: k_out
        call branch_canonicalize (tree%branch(tree%mask_out))
        n_out = tree%n_externals - tree%n_in
        k_out = tree%mask_out
        if (tree%branch(k_out)%has_friend &
            & .and. tree%branch(k_out)%friend == ibset (0, n_out)) then
            tree%branch(k_out)%inverted_axis = .not.tree%branch(k_out)%inverted_axis
        end if
        tree%branch(k_out)%has_friend = .false.
        tree%branch(k_out)%friend = 0
contains
        recursive subroutine branch_canonicalize (b)
            type(phs_branch_t), intent(inout) :: b
            integer(TC) :: d1, d2
            if (b%has_children) then
                d1 = b%daughter(1)
                d2 = b%daughter(2)
                if (d1 > d2) then
                    b%daughter(1) = d2
                    b%daughter(2) = d1
                    b%inverted_decay = .not.b%inverted_decay
                    if (b%firstborn /= 0) b%firstborn = 3 - b%firstborn
                end if
                call branch_canonicalize (tree%branch(b%daughter(1)))
                call branch_canonicalize (tree%branch(b%daughter(2)))
            end if
        end subroutine branch_canonicalize
    end subroutine phs_tree_canonicalize

```

Mappings

Initialize a mapping for the current tree. This is done while reading from file, so the mapping parameters are read, but applied to the flipped tree. Thus, the size of the array of mappings is given by the number of outgoing particles only.

```

<PHS trees: public>+≡

```

```

    public :: phs_tree_init_mapping
<PHS trees: procedures>+≡
    subroutine phs_tree_init_mapping (tree, k, type, pdg, model)
        type(phs_tree_t), intent(inout) :: tree
        integer(TC), intent(in) :: k
        type(string_t), intent(in) :: type
        integer, intent(in) :: pdg
        class(model_data_t), intent(in), target :: model
        integer(TC) :: kk
        kk = tc_flipped (tree, k)
        call mapping_init (tree%mapping(kk), kk, type, pdg, model)
    end subroutine phs_tree_init_mapping

```

Set the physical parameters for the mapping, using a specific parameter set. Also set the mass sum array.

```

<PHS trees: public>+≡
    public :: phs_tree_set_mapping_parameters
<PHS trees: procedures>+≡
    subroutine phs_tree_set_mapping_parameters &
        (tree, mapping_defaults, variable_limits)
        type(phs_tree_t), intent(inout) :: tree
        type(mapping_defaults_t), intent(in) :: mapping_defaults
        logical, intent(in) :: variable_limits
        integer(TC) :: k
        do k = 1, tree%n_branches_out
            call mapping_set_parameters &
                (tree%mapping(k), mapping_defaults, variable_limits)
        end do
    end subroutine phs_tree_set_mapping_parameters

```

Return the mapping for the sum of all outgoing particles. This should either be no mapping or a global s-channel mapping.

```

<PHS trees: public>+≡
    public :: phs_tree_assign_s_mapping
<PHS trees: procedures>+≡
    subroutine phs_tree_assign_s_mapping (tree, mapping)
        type(phs_tree_t), intent(in) :: tree
        type(mapping_t), intent(out) :: mapping
        mapping = tree%mapping(tree%mask_out)
    end subroutine phs_tree_assign_s_mapping

```

Kinematics

Fill the mass sum array, starting from the external particles and working down to the tree root. For each bincode k we scan the bits in k ; if only one is set, we take the physical mass of the corresponding external particle; if more then one is set, we sum up the two masses (which we know have already been set).

```

<PHS trees: public>+≡
    public :: phs_tree_set_mass_sum

```

```

<PHS trees: procedures>+≡
subroutine phs_tree_set_mass_sum (tree, flv)
  type(phs_tree_t), intent(inout) :: tree
  type(flavor_t), dimension(:), intent(in) :: flv
  integer(TC) :: k
  integer :: i
  tree%mass_sum = 0
  do k = 1, tree%n_branches_out
    do i = 0, size (flv) - 1
      if (btest(k,i)) then
        if (ibclr(k,i) == 0) then
          tree%mass_sum(k) = flv(i+1)%get_mass ()
        else
          tree%mass_sum(k) = &
            tree%mass_sum(ibclr(k,i)) + tree%mass_sum(ibset(0,i))
        end if
      end if
    end do
  end do
end subroutine phs_tree_set_mass_sum

```

Set the effective masses and widths. For each non-resonant branch in a tree, the effective mass is equal to the sum of the effective masses of the children (and analogous for the width). External particles have their real mass and width zero. For resonant branches, we insert mass and width from the corresponding mapping.

This routine has `phs_tree_set_mass_sum` and `phs_tree_set_mapping_parameters` as prerequisites.

```

<PHS trees: public>+≡
public :: phs_tree_set_effective_masses

<PHS trees: procedures>+≡
subroutine phs_tree_set_effective_masses (tree)
  type(phs_tree_t), intent(inout) :: tree
  tree%effective_mass = 0
  tree%effective_width = 0
  call set_masses_x (tree%mask_out)
contains
recursive subroutine set_masses_x (k)
  integer(TC), intent(in) :: k
  integer(TC) :: k1, k2
  if (tree%branch(k)%has_children) then
    k1 = tree%branch(k)%daughter(1)
    k2 = tree%branch(k)%daughter(2)
    call set_masses_x (k1)
    call set_masses_x (k2)
    if (mapping_is_s_channel (tree%mapping(k))) then
      tree%effective_mass(k) = mapping_get_mass (tree%mapping(k))
      tree%effective_width(k) = mapping_get_width (tree%mapping(k))
    else
      tree%effective_mass(k) = &
        tree%effective_mass(k1) + tree%effective_mass(k2)
    end if
  end if
end subroutine set_masses_x

```

```

        tree%effective_width(k) = &
            tree%effective_width(k1) + tree%effective_width(k2)
    end if
else
    tree%effective_mass(k) = tree%mass_sum(k)
end if
end subroutine set_masses_x
end subroutine phs_tree_set_effective_masses

```

Define step mappings, recursively, for the decay products of all intermediate resonances. Step mappings account for the fact that a branch may originate from a resonance, which almost replaces the upper limit on the possible invariant mass. The step mapping implements a smooth cutoff that interpolates between the resonance and the real kinematic limit. The mapping width determines the sharpness of the cutoff.

Step mappings are inserted only for branches that are not mapped otherwise.

At each branch, we record the mass that is effectively available for phase space, by taking the previous limit and subtracting the effective mass of the sibling branch. Widths are added, not subtracted.

If we encounter a resonance decay, we discard the previous limit and replace it by the mass and width of the resonance, also subtracting the sibling branch.

Initially, the limit is zero, so it becomes negative at any branch. Only if there is a resonance, the limit becomes positive. Whenever the limit is positive, and the current branch decays, we activate a step mapping for the current branch.

As a result, step mappings are implemented for all internal lines that originate from an intermediate resonance decay.

The flag `variable_limits` applies to the ultimate limit from the available energy, not to the intermediate resonances whose masses are always fixed.

This routine requires `phs_tree_set_effective_masses`

(PHS trees: public)+≡

```
public :: phs_tree_set_step_mappings
```

(PHS trees: procedures)+≡

```

subroutine phs_tree_set_step_mappings (tree, exp_type, variable_limits)
    type(phs_tree_t), intent(inout) :: tree
    logical, intent(in) :: exp_type
    logical, intent(in) :: variable_limits
    type(string_t) :: map_str
    integer(TC) :: k
    if (exp_type) then
        map_str = "step_exp"
    else
        map_str = "step_hyp"
    end if
    k = tree%mask_out
    call set_step_mappings_x (k, 0._default, 0._default)
contains
    recursive subroutine set_step_mappings_x (k, m_limit, w_limit)
        integer(TC), intent(in) :: k
        real(default), intent(in) :: m_limit, w_limit
        integer(TC), dimension(2) :: kk
        real(default), dimension(2) :: m, w

```

```

if (tree%branch(k)%has_children) then
  if (m_limit > 0) then
    if (.not. mapping_is_set (tree%mapping(k))) then
      call mapping_init (tree%mapping(k), k, map_str)
      call mapping_set_step_mapping_parameters (tree%mapping(k), &
        m_limit, w_limit, &
        variable_limits)
    end if
  end if
  kk = tree%branch(k)%daughter
  m = tree%effective_mass(kk)
  w = tree%effective_width(kk)
  if (mapping_is_s_channel (tree%mapping(k))) then
    call set_step_mappings_x (kk(1), &
      mapping_get_mass (tree%mapping(k)) - m(2), &
      mapping_get_width (tree%mapping(k)) + w(2))
    call set_step_mappings_x (kk(2), &
      mapping_get_mass (tree%mapping(k)) - m(1), &
      mapping_get_width (tree%mapping(k)) + w(1))
  else if (m_limit > 0) then
    call set_step_mappings_x (kk(1), &
      m_limit - m(2), &
      w_limit + w(2))
    call set_step_mappings_x (kk(2), &
      m_limit - m(1), &
      w_limit + w(1))
  else
    call set_step_mappings_x (kk(1), &
      - m(2), &
      + w(2))
    call set_step_mappings_x (kk(2), &
      - m(1), &
      + w(1))
  end if
end if
end subroutine set_step_mappings_x
end subroutine phs_tree_set_step_mappings

```

Structural comparison

This function allows to check whether one tree is the permutation of another one. The permutation is applied to the second tree in the argument list. We do not make up a temporary permuted tree, but compare the two trees directly. The branches are scanned recursively, where for each daughter we check the friend and the mapping as well. Once a discrepancy is found, the recursion is exited immediately.

(PHS trees: public)+≡

```
public :: phs_tree_equivalent
```

(PHS trees: procedures)+≡

```
function phs_tree_equivalent (t1, t2, perm) result (is_equal)
  type(phs_tree_t), intent(in) :: t1, t2
  type(permutation_t), intent(in) :: perm

```

```

logical :: equal, is_equal
integer(TC) :: k1, k2, mask_in
k1 = t1%mask_out
k2 = t2%mask_out
mask_in = t1%mask_in
equal = .true.
call check (t1%branch(k1), t2%branch(k2), k1, k2)
is_equal = equal
contains
recursive subroutine check (b1, b2, k1, k2)
  type(phs_branch_t), intent(in) :: b1, b2
  integer(TC), intent(in) :: k1, k2
  integer(TC), dimension(2) :: d1, d2, pd2
  integer :: i
  if (.not.b1%has_friend .and. .not.b2%has_friend) then
    equal = .true.
  else if (b1%has_friend .and. b2%has_friend) then
    equal = (b1%friend == tc_permute (b2%friend, perm, mask_in))
  end if
  if (equal) then
    if (b1%has_children .and. b2%has_children) then
      d1 = b1%daughter
      d2 = b2%daughter
      do i=1, 2
        pd2(i) = tc_permute (d2(i), perm, mask_in)
      end do
      if (d1(1)==pd2(1) .and. d1(2)==pd2(2)) then
        equal = (b1%firstborn == b2%firstborn)
        if (equal) call check &
          & (t1%branch(d1(1)), t2%branch(d2(1)), d1(1), d2(1))
        if (equal) call check &
          & (t1%branch(d1(2)), t2%branch(d2(2)), d1(2), d2(2))
      else if (d1(1)==pd2(2) .and. d1(2)==pd2(1)) then
        equal = ( (b1%firstborn == 0 .and. b2%firstborn == 0) &
          & .or. (b1%firstborn == 3 - b2%firstborn) )
        if (equal) call check &
          & (t1%branch(d1(1)), t2%branch(d2(2)), d1(1), d2(2))
        if (equal) call check &
          & (t1%branch(d1(2)), t2%branch(d2(1)), d1(2), d2(1))
      else
        equal = .false.
      end if
    end if
  end if
  if (equal) then
    equal = (t1%mapping(k1) == t2%mapping(k2))
  end if
end subroutine check
end function phs_tree_equivalent

```

Scan two decay trees and determine the correspondence of mass variables, i.e., the permutation that transfers the ordered list of mass variables belonging to the second tree into the first one. Mass variables are assigned beginning from

branches and ending at the root.

<PHS trees: public>+≡

```
public :: phs_tree_find_msq_permutation
```

<PHS trees: procedures>+≡

```
subroutine phs_tree_find_msq_permutation (tree1, tree2, perm2, msq_perm)
  type(phs_tree_t), intent(in) :: tree1, tree2
  type(permutation_t), intent(in) :: perm2
  type(permutation_t), intent(out) :: msq_perm
  type(permutation_t) :: perm1
  integer(TC) :: mask_in, root
  integer(TC), dimension(:), allocatable :: index1, index2
  integer :: i
  allocate (index1 (tree1%n_msq), index2 (tree2%n_msq))
  call permutation_init (perm1, permutation_size (perm2))
  mask_in = tree1%mask_in
  root = tree1%mask_out
  i = 0
  call tree_scan (tree1, root, perm1, index1)
  i = 0
  call tree_scan (tree2, root, perm2, index2)
  call permutation_find (msq_perm, index1, index2)
contains
  recursive subroutine tree_scan (tree, k, perm, index)
    type(phs_tree_t), intent(in) :: tree
    integer(TC), intent(in) :: k
    type(permutation_t), intent(in) :: perm
    integer, dimension(:), intent(inout) :: index
    if (tree%branch(k)%has_children) then
      call tree_scan (tree, tree%branch(k)%daughter(1), perm, index)
      call tree_scan (tree, tree%branch(k)%daughter(2), perm, index)
      i = i + 1
      if (i <= size (index)) index(i) = tc_permute (k, perm, mask_in)
    end if
  end subroutine tree_scan
end subroutine phs_tree_find_msq_permutation
```

<PHS trees: public>+≡

```
public :: phs_tree_find_angle_permutation
```

<PHS trees: procedures>+≡

```
subroutine phs_tree_find_angle_permutation &
  (tree1, tree2, perm2, angle_perm, sig2)
  type(phs_tree_t), intent(in) :: tree1, tree2
  type(permutation_t), intent(in) :: perm2
  type(permutation_t), intent(out) :: angle_perm
  logical, dimension(:), allocatable, intent(out) :: sig2
  type(permutation_t) :: perm1
  integer(TC) :: mask_in, root
  integer(TC), dimension(:), allocatable :: index1, index2
  logical, dimension(:), allocatable :: sig1
  integer :: i
  allocate (index1 (tree1%n_angles), index2 (tree2%n_angles))
  allocate (sig1 (tree1%n_angles), sig2 (tree2%n_angles))
  call permutation_init (perm1, permutation_size (perm2))
```

```

mask_in = tree1%mask_in
root = tree1%mask_out
i = 0
call tree_scan (tree1, root, perm1, index1, sig1)
i = 0
call tree_scan (tree2, root, perm2, index2, sig2)
call permutation_find (angle_perm, index1, index2)
contains
recursive subroutine tree_scan (tree, k, perm, index, sig)
  type(phs_tree_t), intent(in) :: tree
  integer(TC), intent(in) :: k
  type(permutation_t), intent(in) :: perm
  integer, dimension(:), intent(inout) :: index
  logical, dimension(:), intent(inout) :: sig
  integer(TC) :: k1, k2, kp
  logical :: s
  if (tree%branch(k)%has_children) then
    k1 = tree%branch(k)%daughter(1)
    k2 = tree%branch(k)%daughter(2)
    s = (tc_permute(k1, perm, mask_in) < tc_permute(k2, perm, mask_in))
    kp = tc_permute (k, perm, mask_in)
    i = i + 1
    index(i) = kp
    sig(i) = s
    i = i + 1
    index(i) = - kp
    sig(i) = s
    call tree_scan (tree, k1, perm, index, sig)
    call tree_scan (tree, k2, perm, index, sig)
  end if
end subroutine tree_scan
end subroutine phs_tree_find_angle_permutation

```

18.4.4 Phase-space evaluation

Phase-space volume

We compute the phase-space volume recursively, following the same path as for computing other kinematical variables. However, the volume depends just on $\sqrt{\hat{s}}$, not on the momentum configuration.

Note: counting branches, we may replace this by a simple formula.

```

<PHS trees: public>+≡
  public :: phs_tree_compute_volume

<PHS trees: procedures>+≡
  subroutine phs_tree_compute_volume (tree, sqrts, volume)
    type(phs_tree_t), intent(in) :: tree
    real(default), intent(in) :: sqrts
    real(default), intent(out) :: volume
    integer(TC) :: k
    k = tree%mask_out
    if (tree%branch(k)%has_children) then
      call compute_volume_x (tree%branch(k), k, volume, .true.)
    end if
  end subroutine

```

```

else
    volume = 1
end if
contains
recursive subroutine compute_volume_x (b, k, volume, initial)
    type(phs_branch_t), intent(in) :: b
    integer(TC), intent(in) :: k
    real(default), intent(out) :: volume
    logical, intent(in) :: initial
    integer(TC) :: k1, k2
    real(default) :: v1, v2
    k1 = b%daughter(1); k2 = b%daughter(2)
    if (tree%branch(k1)%has_children) then
        call compute_volume_x (tree%branch(k1), k1, v1, .false.)
    else
        v1 = 1
    end if
    if (tree%branch(k2)%has_children) then
        call compute_volume_x (tree%branch(k2), k2, v2, .false.)
    else
        v2 = 1
    end if
    if (initial) then
        volume = v1 * v2 / (4 * twopi5)
    else
        volume = v1 * v2 * sqrts**2 / (4 * twopi2)
    end if
end subroutine compute_volume_x
end subroutine phs_tree_compute_volume

```

Determine momenta

This is done in two steps: First the masses are determined. This step may fail, in which case `ok` is set to false. If successful, we generate angles and the actual momenta. The array `decay_p` serves for transferring the individual three-momenta of the daughter particles in their mother rest frame from the mass generation to the momentum generation step.

(PHS trees: public)+≡

```
public :: phs_tree_compute_momenta_from_x
```

(PHS trees: procedures)+≡

```

subroutine phs_tree_compute_momenta_from_x &
    (tree, prt, factor, volume, sqrts, x, ok)
    type(phs_tree_t), intent(inout) :: tree
    type(phs_prt_t), dimension(:), intent(inout) :: prt
    real(default), intent(out) :: factor, volume
    real(default), intent(in) :: sqrts
    real(default), dimension(:), intent(in) :: x
    logical, intent(out) :: ok
    real(default), dimension(tree%mask_out) :: decay_p
    integer :: n1, n2
    integer :: n_out
    if (tree%real_phsp) then

```

```

      n_out = tree%n_externals - tree%n_in - 1
      n1 = max (n_out-2, 0)
      n2 = n1 + max (2*n_out, 0)
    else
      n1 = tree%n_msq
      n2 = n1 + tree%n_angles
    end if
    call phs_tree_set_msq &
      (tree, prt, factor, volume, decay_p, sqrts, x(1:n1), ok)
    if (ok) call phs_tree_set_angles &
      (tree, prt, factor, decay_p, sqrts, x(n1+1:n2))
  end subroutine phs_tree_compute_momenta_from_x

```

Mass generation is done recursively. The `ok` flag causes the filled tree to be discarded if set to `.false.` This happens if a three-momentum turns out to be imaginary, indicating impossible kinematics. The index `ix` tells us how far we have used up the input array `x`.

(PHS trees: procedures)+≡

```

subroutine phs_tree_set_msq &
  (tree, prt, factor, volume, decay_p, sqrts, x, ok)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(inout) :: prt
  real(default), intent(out) :: factor, volume
  real(default), dimension(:), intent(out) :: decay_p
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(in) :: x
  logical, intent(out) :: ok
  integer :: ix
  integer(TC) :: k
  real(default) :: m_tot
  ok = .true.
  ix = 1
  k = tree%mask_out
  m_tot = tree%mass_sum(k)
  decay_p(k) = 0.
  if (m_tot < sqrts .or. k == 1) then
    if (tree%branch(k)%has_children) then
      call set_msq_x (tree%branch(k), k, factor, volume, .true.)
    else
      factor = 1
      volume = 1
    end if
  else
    ok = .false.
  end if
contains
recursive subroutine set_msq_x (b, k, factor, volume, initial)
  type(phs_branch_t), intent(in) :: b
  integer(TC), intent(in) :: k
  real(default), intent(out) :: factor, volume
  logical, intent(in) :: initial
  real(default) :: msq, m, m_min, m_max, m1, m2, msq1, msq2, lda, rlda
  integer(TC) :: k1, k2

```

```

real(default) :: f1, f2, v1, v2
k1 = b%daughter(1); k2 = b%daughter(2)
if (tree%branch(k1)%has_children) then
    call set_msq_x (tree%branch(k1), k1, f1, v1, .false.)
    if (.not.ok) return
else
    f1 = 1; v1 = 1
end if
if (tree%branch(k2)%has_children) then
    call set_msq_x (tree%branch(k2), k2, f2, v2, .false.)
    if (.not.ok) return
else
    f2 = 1; v2 = 1
end if
m_min = tree%mass_sum(k)
if (initial) then
    msq = sqrts**2
    m = sqrts
    m_max = sqrts
    factor = f1 * f2
    volume = v1 * v2 / (4 * twopi5)
else
    m_max = sqrts - m_tot + m_min
    call mapping_compute_msq_from_x &
        (tree%mapping(k), sqrts**2, m_min**2, m_max**2, msq, factor, &
        x(ix)); ix = ix + 1
    if (msq >= 0) then
        m = sqrt (msq)
        factor = f1 * f2 * factor
        volume = v1 * v2 * sqrts**2 / (4 * twopi2)
        call phs_prt_set_msq (prt(k), msq)
        call phs_prt_set_defined (prt(k))
    else
        ok = .false.
    end if
end if
if (ok) then
    msq1 = phs_prt_get_msq (prt(k1)); m1 = sqrt (msq1)
    msq2 = phs_prt_get_msq (prt(k2)); m2 = sqrt (msq2)
    lda = lambda (msq, msq1, msq2)
    if (lda > 0 .and. m > m1 + m2 .and. m <= m_max) then
        rlda = sqrt (lda)
        decay_p(k1) = rlda / (2*m)
        decay_p(k2) = - decay_p(k1)
        factor = rlda / msq * factor
    else
        ok = .false.
    end if
end if
end subroutine set_msq_x

end subroutine phs_tree_set_msq

```

The heart of phase space generation: Now we have the invariant masses, let

us generate angles. At each branch, we take a Lorentz transformation and augment it by a boost to the current particle rest frame, and by rotations ϕ and θ around the z and y axis, respectively. This transformation is passed down to the daughter particles, if present.

(PHS trees: procedures)+≡

```

subroutine phs_tree_set_angles (tree, prt, factor, decay_p, sqrts, x)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(inout) :: prt
  real(default), intent(inout) :: factor
  real(default), dimension(:), intent(in) :: decay_p
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(in) :: x
  integer :: ix
  integer(TC) :: k
  ix = 1
  k = tree%mask_out
  call set_angles_x (tree%branch(k), k)
contains
  recursive subroutine set_angles_x (b, k, L0)
    type(phs_branch_t), intent(in) :: b
    integer(TC), intent(in) :: k
    type(lorentz_transformation_t), intent(in), optional :: L0
    real(default) :: m, msq, ct, st, phi, f, E, p, bg
    type(lorentz_transformation_t) :: L, LL
    integer(TC) :: k1, k2
    type(vector3_t) :: axis
    p = decay_p(k)
    msq = phs_prt_get_msq (prt(k)); m = sqrt (msq)
    E = sqrt (msq + p**2)
    if (present (L0)) then
      call phs_prt_set_momentum (prt(k), L0 * vector4_moving (E,p,3))
    else
      call phs_prt_set_momentum (prt(k), vector4_moving (E,p,3))
    end if
    call phs_prt_set_defined (prt(k))
    if (b%has_children) then
      k1 = b%daughter(1)
      k2 = b%daughter(2)
      if (m > 0) then
        bg = p / m
      else
        bg = 0
      end if
      phi = x(ix) * twopi; ix = ix + 1
      call mapping_compute_ct_from_x &
        (tree%mapping(k), sqrts**2, ct, st, f, x(ix)); ix = ix + 1
      factor = factor * f
      if (.not. b%has_friend) then
        L = LT_compose_r2_r3_b3 (ct, st, cos(phi), sin(phi), bg)
        !!! The function above is equivalent to:
        ! L = boost (bg,3) * rotation (phi,3) * rotation (ct,st,2)
      else
        LL = boost (-bg,3); if (present (L0)) LL = LL * inverse(L0)
        axis = space_part ( &

```

```

        LL * phs_prt_get_momentum (prt(tree%branch(k)%friend)) )
    L = boost(bg,3) * rotation_to_2nd (vector3_canonical(3), axis) &
        * LT_compose_r2_r3_b3 (ct, st, cos(phi), sin(phi), 0._default)
    end if
    if (present (L0)) L = L0 * L
    call set_angles_x (tree%branch(k1), k1, L)
    call set_angles_x (tree%branch(k2), k2, L)
    end if
end subroutine set_angles_x

end subroutine phs_tree_set_angles

```

Recover random numbers

For the other channels we want to compute the random numbers that would have generated the momenta that we already know.

```

<PHS trees: public>+≡
    public :: phs_tree_compute_x_from_momenta

<PHS trees: procedures>+≡
    subroutine phs_tree_compute_x_from_momenta (tree, prt, factor, sqrts, x)
        type(phs_tree_t), intent(inout) :: tree
        type(phs_prt_t), dimension(:), intent(in) :: prt
        real(default), intent(out) :: factor
        real(default), intent(in) :: sqrts
        real(default), dimension(:), intent(inout) :: x
        real(default), dimension(tree%mask_out) :: decay_p
        integer :: n1, n2
        n1 = tree%n_msq
        n2 = n1 + tree%n_angles
        call phs_tree_get_msq &
            (tree, prt, factor, decay_p, sqrts, x(1:n1))
        call phs_tree_get_angles &
            (tree, prt, factor, decay_p, sqrts, x(n1+1:n2))
    end subroutine phs_tree_compute_x_from_momenta

```

The inverse operation follows exactly the same steps. The tree is `inout` because it contains mappings whose parameters can be reset when the mapping is applied.

```

<PHS trees: procedures>+≡
    subroutine phs_tree_get_msq (tree, prt, factor, decay_p, sqrts, x)
        type(phs_tree_t), intent(inout) :: tree
        type(phs_prt_t), dimension(:), intent(in) :: prt
        real(default), intent(out) :: factor
        real(default), dimension(:), intent(out) :: decay_p
        real(default), intent(in) :: sqrts
        real(default), dimension(:), intent(inout) :: x
        integer :: ix
        integer(TC) :: k
        real(default) :: m_tot
        ix = 1
        k = tree%mask_out

```

```

m_tot = tree%mass_sum(k)
decay_p(k) = 0.
if (tree%branch(k)%has_children) then
    call get_msq_x (tree%branch(k), k, factor, .true.)
else
    factor = 1
end if
contains
recursive subroutine get_msq_x (b, k, factor, initial)
    type(phas_branch_t), intent(in) :: b
    integer(TC), intent(in) :: k
    real(default), intent(out) :: factor
    logical, intent(in) :: initial
    real(default) :: msq, m, m_min, m_max, msq1, msq2, lda, rlda
    integer(TC) :: k1, k2
    real(default) :: f1, f2
    k1 = b%daughter(1); k2 = b%daughter(2)
    if (tree%branch(k1)%has_children) then
        call get_msq_x (tree%branch(k1), k1, f1, .false.)
    else
        f1 = 1
    end if
    if (tree%branch(k2)%has_children) then
        call get_msq_x (tree%branch(k2), k2, f2, .false.)
    else
        f2 = 1
    end if
    m_min = tree%mass_sum(k)
    m_max = sqrts - m_tot + m_min
    msq = phs_prt_get_msq (prt(k)); m = sqrt (msq)
    if (initial) then
        factor = f1 * f2
    else
        call mapping_compute_x_from_msq &
            (tree%mapping(k), sqrts**2, m_min**2, m_max**2, msq, factor, &
                x(ix)); ix = ix + 1
        factor = f1 * f2 * factor
    end if
    msq1 = phs_prt_get_msq (prt(k1))
    msq2 = phs_prt_get_msq (prt(k2))
    lda = lambda (msq, msq1, msq2)
    if (lda > 0) then
        rlda = sqrt (lda)
        decay_p(k1) = rlda / (2 * m)
        decay_p(k2) = - decay_p(k1)
        factor = rlda / msq * factor
    else
        decay_p(k1) = 0
        decay_p(k2) = 0
        factor = 0
    end if
end subroutine get_msq_x

end subroutine phs_tree_get_msq

```


This subroutine is the most time-critical part of the whole program. Therefore, we do not exactly parallel the angle generation routine above but make sure that things get evaluated only if they are really needed, at the expense of readability. Particularly important is to have as few multiplications of Lorentz transformations as possible.

(*PHS trees: procedures*) \equiv

```

subroutine phs_tree_get_angles (tree, prt, factor, decay_p, sqrts, x)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(in) :: prt
  real(default), intent(inout) :: factor
  real(default), dimension(:), intent(in) :: decay_p
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(out) :: x
  integer :: ix
  integer(TC) :: k
  ix = 1
  k = tree%mask_out
  if (tree%branch(k)%has_children) then
    call get_angles_x (tree%branch(k), k)
  end if
contains
recursive subroutine get_angles_x (b, k, ct0, st0, phi0, L0)
  type(phs_branch_t), intent(in) :: b
  integer(TC), intent(in) :: k
  real(default), intent(in), optional :: ct0, st0, phi0
  type(lorentz_transformation_t), intent(in), optional :: L0
  real(default) :: cp0, sp0, m, msq, ct, st, phi, bg, f
  type(lorentz_transformation_t) :: L, LL
  type(vector4_t) :: p1, pf
  type(vector3_t) :: n, axis
  integer(TC) :: k1, k2, kf
  logical :: has_friend, need_L
  k1 = b%daughter(1)
  k2 = b%daughter(2)
  kf = b%friend
  has_friend = b%has_friend
  if (present(L0)) then
    p1 = L0 * phs_prt_get_momentum (prt(k1))
    if (has_friend) pf = L0 * phs_prt_get_momentum (prt(kf))
  else
    p1 = phs_prt_get_momentum (prt(k1))
    if (has_friend) pf = phs_prt_get_momentum (prt(kf))
  end if
  if (present(phi0)) then
    cp0 = cos (phi0)
    sp0 = sin (phi0)
  end if
  msq = phs_prt_get_msq (prt(k)); m = sqrt (msq)
  if (m > 0) then
    bg = decay_p(k) / m
  else
    bg = 0

```

```

end if
if (has_friend) then
  if (present (phi0)) then
    axis = axis_from_p_r3_r2_b3 (pf, cp0, -sp0, ct0, -st0, -bg)
    LL = rotation_to_2nd (axis, vector3_canonical (3)) &
      * LT_compose_r3_r2_b3 (cp0, -sp0, ct0, -st0, -bg)
  else
    axis = axis_from_p_b3 (pf, -bg)
    LL = rotation_to_2nd (axis, vector3_canonical(3))
    if (bg /= 0) LL = LL * boost(-bg, 3)
  end if
  n = space_part (LL * p1)
else if (present (phi0)) then
  n = axis_from_p_r3_r2_b3 (p1, cp0, -sp0, ct0, -st0, -bg)
else
  n = axis_from_p_b3 (p1, -bg)
end if
phi = azimuthal_angle (n)
x(ix) = phi / twopi; ix = ix + 1
ct = polar_angle_ct (n)
st = sqrt (1 - ct**2)
call mapping_compute_x_from_ct (tree%mapping(k), sqrts**2, ct, f, &
  x(ix)); ix = ix + 1
factor = factor * f
if (tree%branch(k1)%has_children .or. tree%branch(k2)%has_children) then
  need_L = .true.
  if (has_friend) then
    if (present (L0)) then
      L = LL * L0
    else
      L = LL
    end if
  else if (present (L0)) then
    L = LT_compose_r3_r2_b3 (cp0, -sp0, ct0, -st0, -bg) * L0
  else if (present (phi0)) then
    L = LT_compose_r3_r2_b3 (cp0, -sp0, ct0, -st0, -bg)
  else if (bg /= 0) then
    L = boost(-bg, 3)
  else
    need_L = .false.
  end if
  if (need_L) then
    if (tree%branch(k1)%has_children) &
      call get_angles_x (tree%branch(k1), k1, ct, st, phi, L)
    if (tree%branch(k2)%has_children) &
      call get_angles_x (tree%branch(k2), k2, ct, st, phi, L)
  else
    if (tree%branch(k1)%has_children) &
      call get_angles_x (tree%branch(k1), k1, ct, st, phi)
    if (tree%branch(k2)%has_children) &
      call get_angles_x (tree%branch(k2), k2, ct, st, phi)
  end if
end if
end subroutine get_angles_x

```

```
end subroutine phs_tree_get_angles
```

Auxiliary stuff

This calculates all momenta that are not yet known by summing up daughter particle momenta. The external particles must be known. Only composite particles not yet known are calculated.

```

<PHS trees: public>+≡
  public :: phs_tree_combine_particles

<PHS trees: procedures>+≡
  subroutine phs_tree_combine_particles (tree, prt)
    type(phs_tree_t), intent(in) :: tree
    type(phs_prt_t), dimension(:), intent(inout) :: prt
    call combine_particles_x (tree%mask_out)
  contains
    recursive subroutine combine_particles_x (k)
      integer(TC), intent(in) :: k
      integer :: k1, k2
      if (tree%branch(k)%has_children) then
        k1 = tree%branch(k)%daughter(1); k2 = tree%branch(k)%daughter(2)
        call combine_particles_x (k1)
        call combine_particles_x (k2)
        if (.not. prt(k)%defined) then
          call phs_prt_combine (prt(k), prt(k1), prt(k2))
        end if
      end if
    end subroutine combine_particles_x
  end subroutine phs_tree_combine_particles

```

The previous routine is to be evaluated at runtime. Instead of scanning trees, we can as well set up a multiplication table. This is generated here. Note that the table is `intent(out)`.

```

<PHS trees: public>+≡
  public :: phs_tree_setup_prt_combinations

<PHS trees: procedures>+≡
  subroutine phs_tree_setup_prt_combinations (tree, comb)
    type(phs_tree_t), intent(in) :: tree
    integer, dimension(:,:), intent(out) :: comb
    comb = 0
    call setup_prt_combinations_x (tree%mask_out)
  contains
    recursive subroutine setup_prt_combinations_x (k)
      integer(TC), intent(in) :: k
      integer, dimension(2) :: kk
      if (tree%branch(k)%has_children) then
        kk = tree%branch(k)%daughter
        call setup_prt_combinations_x (kk(1))
        call setup_prt_combinations_x (kk(2))
        comb(:,k) = kk
      end if
    end subroutine setup_prt_combinations_x

```

```

end subroutine phs_tree_setup_prt_combinations

<PHS trees: public>+≡
  public :: phs_tree_reshuffle_mappings

<PHS trees: procedures>+≡
  subroutine phs_tree_reshuffle_mappings (tree)
    type(phs_tree_t), intent(inout) :: tree
    integer(TC) :: k0, k_old, k_new, k2
    integer :: i
    type(mapping_t) :: mapping_tmp
    real(default) :: mass_tmp
    do i = 1, size (tree%momentum_link)
      if (i /= tree%momentum_link(i)) then
        k_old = 2**(i-tree%n_in-1)
        k_new = 2**(tree%momentum_link(i)-tree%n_in-1)
        k0 = tree%branch(k_old)%mother
        k2 = k_new + tree%branch(k_old)%sibling
        mapping_tmp = tree%mapping(k0)
        mass_tmp = tree%mass_sum(k0)
        tree%mapping(k0) = tree%mapping(k2)
        tree%mapping(k2) = mapping_tmp
        tree%mass_sum(k0) = tree%mass_sum(k2)
        tree%mass_sum(k2) = mass_tmp
      end if
    end do
  end subroutine phs_tree_reshuffle_mappings

<PHS trees: public>+≡
  public :: phs_tree_set_momentum_links

<PHS trees: procedures>+≡
  subroutine phs_tree_set_momentum_links (tree, list)
    type(phs_tree_t), intent(inout) :: tree
    integer, dimension(:), allocatable :: list
    tree%momentum_link = list
  end subroutine phs_tree_set_momentum_links

```

18.5 The phase-space forest

Simply stated, a phase-space forest is a collection of phase-space trees. More precisely, a `phs_forest` object contains all parameterizations of phase space that `WHIZARD` will use for a single hard process, prepared in the form of `phs_tree` objects. This is suitable for evaluation by the `VAMP` integration package: each parameterization (tree) is a valid channel in the multi-channel adaptive integration, and each variable in a tree corresponds to an integration dimension, defined by an appropriate mapping of the $(0, 1)$ interval to the allowed range of the integration variable.

The trees are grouped in groves. The trees (integration channels) within a grove share a common weight, assuming that they are related by some approximate symmetry.

Trees/channels that are related by an exact symmetry are connected by an array of equivalences; each equivalence object holds the data that relate one channel to another.

The phase-space setup, i.e., the detailed structure of trees and forest, are read from a file. Therefore, this module also contains the syntax definition and the parser needed for interpreting this file.

```
(phs_forests.f90)≡  
  <File header>  
  
  module phs_forests  
  
    <Use kinds>  
    use kinds, only: TC  
    <Use strings>  
    use io_units  
    use format_defs, only: FMT_12, FMT_19  
    use diagnostics  
    use lorentz  
    use unit_tests  
    use permutations  
    use ifiles  
    use syntax_rules  
    use lexers  
    use parser  
    use model_data  
    use model_data  
    use flavors  
    use interactions  
  
    use phs_base  
    use mappings  
    use phs_trees  
  
    <Standard module head>  
  
    <PHS forests: public>  
  
    <PHS forests: types>
```

<PHS forests: interfaces>

<PHS forests: variables>

contains

<PHS forests: procedures>

<PHS forests: tests>

end module phs_forests

18.5.1 Phase-space setup parameters

This transparent container holds the parameters that the algorithm needs for phase-space setup, with reasonable defaults.

The threshold mass (for considering a particle as effectively massless) is specified separately for s- and t-channel. The default is to treat W and Z bosons as massive in the s-channel, but as massless in the t-channel. The b -quark is treated always massless, the t -quark always massive.

<PHS forests: public>≡

public :: phs_parameters_t

<PHS forests: types>≡

type :: phs_parameters_t

real(default) :: sqrts = 0

real(default) :: m_threshold_s = 50._default

real(default) :: m_threshold_t = 100._default

integer :: off_shell = 1

integer :: t_channel = 2

logical :: keep_nonresonant = .true.

end type phs_parameters_t

Write phase-space parameters to file.

<PHS forests: public>+≡

public :: phs_parameters_write

<PHS forests: procedures>≡

subroutine phs_parameters_write (phs_par, unit)

type(phs_parameters_t), intent(in) :: phs_par

integer, intent(in), optional :: unit

integer :: u

u = given_output_unit (unit)

write (u, "(3x,A," // FMT_19 // ")") "sqrts = ", phs_par%sqrts

write (u, "(3x,A," // FMT_19 // ")") "m_threshold_s = ", phs_par%m_threshold_s

write (u, "(3x,A," // FMT_19 // ")") "m_threshold_t = ", phs_par%m_threshold_t

write (u, "(3x,A,I0)") "off_shell = ", phs_par%off_shell

write (u, "(3x,A,I0)") "t_channel = ", phs_par%t_channel

write (u, "(3x,A,L1)") "keep_nonresonant = ", phs_par%keep_nonresonant

end subroutine phs_parameters_write

Read phase-space parameters from file.

```
(PHS forests: public)+≡
  public :: phs_parameters_read

(PHS forests: procedures)+≡
  subroutine phs_parameters_read (phs_par, unit)
    type(phs_parameters_t), intent(out) :: phs_par
    integer, intent(in) :: unit
    character(20) :: dummy
    character :: equals
    read (unit, *) dummy, equals, phs_par%sqrts
    read (unit, *) dummy, equals, phs_par%m_threshold_s
    read (unit, *) dummy, equals, phs_par%m_threshold_t
    read (unit, *) dummy, equals, phs_par%off_shell
    read (unit, *) dummy, equals, phs_par%t_channel
    read (unit, *) dummy, equals, phs_par%keep_nonresonant
  end subroutine phs_parameters_read
```

Comparison.

```
(PHS forests: interfaces)≡
  interface operator(==)
    module procedure phs_parameters_eq
  end interface
  interface operator(/=)
    module procedure phs_parameters_ne
  end interface

(PHS forests: procedures)+≡
  function phs_parameters_eq (phs_par1, phs_par2) result (equal)
    logical :: equal
    type(phs_parameters_t), intent(in) :: phs_par1, phs_par2
    equal = phs_par1%sqrts == phs_par2%sqrts &
      .and. phs_par1%m_threshold_s == phs_par2%m_threshold_s &
      .and. phs_par1%m_threshold_t == phs_par2%m_threshold_t &
      .and. phs_par1%off_shell == phs_par2%off_shell &
      .and. phs_par1%t_channel == phs_par2%t_channel &
      .and.(phs_par1%keep_nonresonant .eqv. phs_par2%keep_nonresonant)
  end function phs_parameters_eq

  function phs_parameters_ne (phs_par1, phs_par2) result (ne)
    logical :: ne
    type(phs_parameters_t), intent(in) :: phs_par1, phs_par2
    ne = phs_par1%sqrts /= phs_par2%sqrts &
      .or. phs_par1%m_threshold_s /= phs_par2%m_threshold_s &
      .or. phs_par1%m_threshold_t /= phs_par2%m_threshold_t &
      .or. phs_par1%off_shell /= phs_par2%off_shell &
      .or. phs_par1%t_channel /= phs_par2%t_channel &
      .or.(phs_par1%keep_nonresonant .neqv. phs_par2%keep_nonresonant)
  end function phs_parameters_ne
```

18.5.2 Equivalences

This type holds information about equivalences between phase-space trees. We make a linked list, where each node contains the two trees which are equivalent and the corresponding permutation of external particles. Two more arrays are to be filled: The permutation of mass variables and the permutation of angular variables, where the signature indicates a necessary exchange of daughter branches.

```
(PHS forests: types)+≡
  type :: equivalence_t
  private
  integer :: left, right
  type(permutation_t) :: perm
  type(permutation_t) :: msq_perm, angle_perm
  logical, dimension(:), allocatable :: angle_sig
  type(equivalence_t), pointer :: next => null ()
end type equivalence_t
```

```
(PHS forests: types)+≡
  type :: equivalence_list_t
  private
  integer :: length = 0
  type(equivalence_t), pointer :: first => null ()
  type(equivalence_t), pointer :: last => null ()
end type equivalence_list_t
```

Append an equivalence to the list

```
(PHS forests: procedures)+≡
  subroutine equivalence_list_add (eql, left, right, perm)
  type(equivalence_list_t), intent(inout) :: eql
  integer, intent(in) :: left, right
  type(permutation_t), intent(in) :: perm
  type(equivalence_t), pointer :: eq
  allocate (eq)
  eq%left = left
  eq%right = right
  eq%perm = perm
  if (associated (eql%last)) then
    eql%last%next => eq
  else
    eql%first => eq
  end if
  eql%last => eq
  eql%length = eql%length + 1
end subroutine equivalence_list_add
```

Delete the list contents. Has to be pure because it is called from an elemental subroutine.

```
(PHS forests: procedures)+≡
  pure subroutine equivalence_list_final (eql)
  type(equivalence_list_t), intent(inout) :: eql
  type(equivalence_t), pointer :: eq
```



```

do while (associated (eql%first))
  eq => eql%first
  eql%first => eql%first%next
  deallocate (eq)
end do
eql%last => null ()
eql%length = 0
end subroutine equivalence_list_final

```

Make a deep copy of the equivalence list. This allows for deep copies of groves and forests.

```

(PHS forests: interfaces)+≡
interface assignment(=)
  module procedure equivalence_list_assign
end interface

(PHS forests: procedures)+≡
subroutine equivalence_list_assign (eql_out, eql_in)
  type(equivalence_list_t), intent(out) :: eql_out
  type(equivalence_list_t), intent(in) :: eql_in
  type(equivalence_t), pointer :: eq, eq_copy
  eq => eql_in%first
  do while (associated (eq))
    allocate (eq_copy)
    eq_copy = eq
    eq_copy%next => null ()
    if (associated (eql_out%first)) then
      eql_out%last%next => eq_copy
    else
      eql_out%first => eq_copy
    end if
    eql_out%last => eq_copy
    eq => eq%next
  end do
end subroutine equivalence_list_assign

```

The number of list entries

```

(PHS forests: procedures)+≡
elemental function equivalence_list_length (eql) result (length)
  integer :: length
  type(equivalence_list_t), intent(in) :: eql
  length = eql%length
end function equivalence_list_length

```

Recursively write the equivalences list

```

(PHS forests: procedures)+≡
subroutine equivalence_list_write (eql, unit)
  type(equivalence_list_t), intent(in) :: eql
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  if (associated (eql%first)) then

```

```

        call equivalence_write_rec (eq1%first, u)
    else
        write (u, *) " [empty]"
    end if
contains
recursive subroutine equivalence_write_rec (eq, u)
    type(equivalence_t), intent(in) :: eq
    integer, intent(in) :: u
    integer :: i
    write (u, "(3x,A,1x,I0,1x,I0,2x,A)", advance="no") &
        "Equivalence:", eq%left, eq%right, "Final state permutation:"
    call permutation_write (eq%perm, u)
    write (u, "(1x,12x,1x,A,1x)", advance="no") &
        "      msq permutation:  "
    call permutation_write (eq%msq_perm, u)
    write (u, "(1x,12x,1x,A,1x)", advance="no") &
        "      angle permutation:"
    call permutation_write (eq%angle_perm, u)
    write (u, "(1x,12x,1x,26x)", advance="no")
    do i = 1, size (eq%angle_sig)
        if (eq%angle_sig(i)) then
            write (u, "(1x,A)", advance="no") "+"
        else
            write (u, "(1x,A)", advance="no") "-"
        end if
    end do
    write (u, *)
    if (associated (eq%next)) call equivalence_write_rec (eq%next, u)
end subroutine equivalence_write_rec
end subroutine equivalence_list_write

```

18.5.3 Groves

A grove is a group of trees (phase-space channels) that share a common weight in the integration. Within a grove, channels can be declared equivalent, so they also share their integration grids (up to symmetries). The grove contains a list of equivalences. The `tree_count_offset` is the total number of trees of the preceding groves; when the trees are counted per forest (integration channels), the offset has to be added to all tree indices.

```

<PHS forests: types>+≡
    type :: phs_grove_t
    private
    integer :: tree_count_offset
    type(phs_tree_t), dimension(:), allocatable :: tree
    type(equivalence_list_t) :: equivalence_list
end type phs_grove_t

```

Call `phs_tree_init` which is also elemental:

```

<PHS forests: procedures>+≡
    elemental subroutine phs_grove_init &
        (grove, n_trees, n_in, n_out, n_masses, n_angles)

```

```

    type(phs_grove_t), intent(inout) :: grove
    integer, intent(in) :: n_trees, n_in, n_out, n_masses, n_angles
    grove%tree_count_offset = 0
    allocate (grove%tree (n_trees))
    call phs_tree_init (grove%tree, n_in, n_out, n_masses, n_angles)
end subroutine phs_grove_init

```

The trees do not have pointer components, thus no call to `phs_tree_final`:

```

<PHS forests: procedures>+≡
    elemental subroutine phs_grove_final (grove)
        type(phs_grove_t), intent(inout) :: grove
        deallocate (grove%tree)
        call equivalence_list_final (grove%equivalence_list)
    end subroutine phs_grove_final

```

Deep copy.

```

<PHS forests: interfaces>+≡
    interface assignment(=)
        module procedure phs_grove_assign0
        module procedure phs_grove_assign1
    end interface

<PHS forests: procedures>+≡
    subroutine phs_grove_assign0 (grove_out, grove_in)
        type(phs_grove_t), intent(out) :: grove_out
        type(phs_grove_t), intent(in) :: grove_in
        grove_out%tree_count_offset = grove_in%tree_count_offset
        if (allocated (grove_in%tree)) then
            allocate (grove_out%tree (size (grove_in%tree)))
            grove_out%tree = grove_in%tree
        end if
        grove_out%equivalence_list = grove_in%equivalence_list
    end subroutine phs_grove_assign0

    subroutine phs_grove_assign1 (grove_out, grove_in)
        type(phs_grove_t), dimension(:), intent(out) :: grove_out
        type(phs_grove_t), dimension(:), intent(in) :: grove_in
        integer :: i
        do i = 1, size (grove_in)
            call phs_grove_assign0 (grove_out(i), grove_in(i))
        end do
    end subroutine phs_grove_assign1

```

Get the global (s-channel) mappings. Implemented as a subroutine which returns an array (slice).

```

<PHS forests: procedures>+≡
    subroutine phs_grove_assign_s_mappings (grove, mapping)
        type(phs_grove_t), intent(in) :: grove
        type(mapping_t), dimension(:), intent(out) :: mapping
        integer :: i
        if (size (mapping) == size (grove%tree)) then
            do i = 1, size (mapping)

```

```

        call phs_tree_assign_s_mapping (grove%tree(i), mapping(i))
    end do
else
    call msg_bug ("phs_grove_assign_s_mappings: array size mismatch")
end if
end subroutine phs_grove_assign_s_mappings

```

18.5.4 The forest type

This is a collection of trees and associated particles. In a given tree, each branch code corresponds to a particle in the `prt` array. Furthermore, we have an array of mass sums which is independent of the decay tree and of the particular event. The mappings directly correspond to the decay trees, and the decay groves collect the trees in classes. The permutation list consists of all permutations of outgoing particles that map the decay forest onto itself.

The particle codes `flv` (one for each external particle) are needed for determining masses and such. The trees and associated information are collected in the `grove` array, together with a lookup table that associates tree indices to groves. Finally, the `prt` array serves as workspace for phase-space evaluation.

The `prt_combination` is a list of index pairs, namely the particle momenta pairs that need to be combined in order to provide all momentum combinations that the phase-space trees need to know.

```

(PHS forests: public)+≡
    public :: phs_forest_t

(PHS forests: types)+≡
    type :: phs_forest_t
    private
        integer :: n_in, n_out, n_tot
        integer :: n_masses, n_angles, n_dimensions
        integer :: n_trees, n_equivalences
        type(flavor_t), dimension(:), allocatable :: flv
        type(phs_grove_t), dimension(:), allocatable :: grove
        integer, dimension(:), allocatable :: grove_lookup
        type(phs_prt_t), dimension(:), allocatable :: prt_in
        type(phs_prt_t), dimension(:), allocatable :: prt_out
        type(phs_prt_t), dimension(:), allocatable :: prt
        integer(TC), dimension(:,:), allocatable :: prt_combination
        type(mapping_t), dimension(:), allocatable :: s_mapping
    contains
        (PHS forests: phs_forest: TBP)
    end type phs_forest_t

```

The initialization merely allocates memory. We have to know how many trees there are in each grove, so we can initialize everything. The number of groves is the size of the `n_tree` array.

In the `grove_lookup` table we store the grove index that belongs to each absolute tree index. The difference between the absolute index and the relative (to the grove) index is stored, for each grove, as `tree_count_offset`.

The particle array is allocated according to the total number of branches each tree has, but not filled.

```

(PHS forests: public)+≡
    public :: phs_forest_init

(PHS forests: procedures)+≡
    subroutine phs_forest_init (forest, n_tree, n_in, n_out)
        type(phs_forest_t), intent(inout) :: forest
        integer, dimension(:), intent(in) :: n_tree
        integer, intent(in) :: n_in, n_out
        integer :: g, count, k_root
        forest%n_in = n_in
        forest%n_out = n_out
        forest%n_tot = n_in + n_out
        forest%n_masses = max (n_out - 2, 0)
        forest%n_angles = max (2*n_out - 2, 0)
        forest%n_dimensions = forest%n_masses + forest%n_angles
        forest%n_trees = sum (n_tree)
        forest%n_equivalences = 0
        allocate (forest%grove (size (n_tree)))
        call phs_grove_init &
            (forest%grove, n_tree, n_in, n_out, forest%n_masses, &
             forest%n_angles)
        allocate (forest%grove_lookup (forest%n_trees))
        count = 0
        do g = 1, size (forest%grove)
            forest%grove(g)%tree_count_offset = count
            forest%grove_lookup (count+1:count+n_tree(g)) = g
            count = count + n_tree(g)
        end do
        allocate (forest%pvt_in (n_in))
        allocate (forest%pvt_out (forest%n_out))
        k_root = 2**forest%n_tot - 1
        allocate (forest%pvt (k_root))
        allocate (forest%pvt_combination (2, k_root))
        allocate (forest%s_mapping (forest%n_trees))
    end subroutine phs_forest_init

```

Assign the global (s-channel) mappings.

```

(PHS forests: public)+≡
    public :: phs_forest_set_s_mappings

(PHS forests: procedures)+≡
    subroutine phs_forest_set_s_mappings (forest)
        type(phs_forest_t), intent(inout) :: forest
        integer :: g, i0, i1, n
        do g = 1, size (forest%grove)
            call phs_forest_get_grove_bounds (forest, g, i0, i1, n)
            call phs_grove_assign_s_mappings &
                (forest%grove(g), forest%s_mapping(i0:i1))
        end do
    end subroutine phs_forest_set_s_mappings

```

The grove finalizer is called because it contains the equivalence list:

```

<PHS forests: public>+≡
    public :: phs_forest_final

<PHS forests: procedures>+≡
    subroutine phs_forest_final (forest)
        type(phs_forest_t), intent(inout) :: forest
        if (allocated (forest%grove)) then
            call phs_grove_final (forest%grove)
            deallocate (forest%grove)
        end if
        if (allocated (forest%grove_lookup)) deallocate (forest%grove_lookup)
        if (allocated (forest%prt)) deallocate (forest%prt)
        if (allocated (forest%s_mapping)) deallocate (forest%s_mapping)
    end subroutine phs_forest_final

```

18.5.5 Screen output

Write the particles that are non-null, then the trees which point to them:

```

<PHS forests: public>+≡
    public :: phs_forest_write

<PHS forests: phs forest: TBP>≡
    procedure :: write => phs_forest_write

<PHS forests: procedures>+≡
    subroutine phs_forest_write (forest, unit)
        class(phs_forest_t), intent(in) :: forest
        integer, intent(in), optional :: unit
        integer :: u
        integer :: i, g, k
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,A)") "Phase space forest:"
        write (u, "(3x,A,I0)") "n_in = ", forest%n_in
        write (u, "(3x,A,I0)") "n_out = ", forest%n_out
        write (u, "(3x,A,I0)") "n_tot = ", forest%n_tot
        write (u, "(3x,A,I0)") "n_masses = ", forest%n_masses
        write (u, "(3x,A,I0)") "n_angles = ", forest%n_angles
        write (u, "(3x,A,I0)") "n_dim = ", forest%n_dimensions
        write (u, "(3x,A,I0)") "n_trees = ", forest%n_trees
        write (u, "(3x,A,I0)") "n_equiv = ", forest%n_equivalences
        write (u, "(3x,A)", advance="no") "flavors ="
        if (allocated (forest%flv)) then
            do i = 1, size (forest%flv)
                write (u, "(1x,I0)", advance="no") forest%flv(i)%get_pdg ()
            end do
            write (u, "(A)")
        else
            write (u, "(1x,A)") "[empty]"
        end if
        write (u, "(1x,A)") "Particle combinations:"
        if (allocated (forest%prt_combination)) then
            do k = 1, size (forest%prt_combination, 2)
                if (forest%prt_combination(1, k) /= 0) then

```

```

        write (u, "(3x,I0,1x,'<=',1x,I0,1x,'+',1x,I0)") &
            k, forest%prt_combination(:,k)
    end if
end do
else
    write (u, "(3x,A)") " [empty]"
end if
write (u, "(1x,A)") "Groves and trees:"
if (allocated (forest%grove)) then
    do g = 1, size (forest%grove)
        write (u, "(3x,A,1x,I0)") "Grove      ", g
        call phs_grove_write (forest%grove(g), unit)
    end do
else
    write (u, "(3x,A)") " [empty]"
end if
write (u, "(1x,A,I0)") "Total number of equivalences: ", &
    forest%n_equivalences
write (u, "(A)")
write (u, "(1x,A)") "Global s-channel mappings:"
if (allocated (forest%s_mapping)) then
    do i = 1, size (forest%s_mapping)
        associate (mapping => forest%s_mapping(i))
            if (mapping_is_s_channel (mapping) &
                .or. mapping_is_on_shell (mapping)) then
                write (u, "(1x,I0,':',1x)", advance="no") i
                call mapping_write (forest%s_mapping(i), unit)
            end if
        end associate
    end do
else
    write (u, "(3x,A)") " [empty]"
end if
write (u, "(A)")
write (u, "(1x,A)") "Incoming particles:"
if (allocated (forest%prt_in)) then
    if (any (phs_prt_is_defined (forest%prt_in))) then
        do i = 1, size (forest%prt_in)
            if (phs_prt_is_defined (forest%prt_in(i))) then
                write (u, "(1x,A,1x,I0)") "Particle", i
                call phs_prt_write (forest%prt_in(i), u)
            end if
        end do
    else
        write (u, "(3x,A)") "[all undefined]"
    end if
else
    write (u, "(3x,A)") " [empty]"
end if
write (u, "(A)")
write (u, "(1x,A)") "Outgoing particles:"
if (allocated (forest%prt_out)) then
    if (any (phs_prt_is_defined (forest%prt_out))) then
        do i = 1, size (forest%prt_out)

```

```

        if (phs_prt_is_defined (forest%prt_out(i))) then
            write (u, "(1x,A,1x,I0)" "Particle", i
                call phs_prt_write (forest%prt_out(i), u)
            end if
        end do
    else
        write (u, "(3x,A)" "[all undefined]"
    end if
else
    write (u, "(1x,A)" " [empty]"
end if
write (u, "(A)")
write (u, "(1x,A)" "Tree particles:"
if (allocated (forest%prt)) then
    if (any (phs_prt_is_defined (forest%prt))) then
        do i = 1, size (forest%prt)
            if (phs_prt_is_defined (forest%prt(i))) then
                write (u, "(1x,A,1x,I0)" "Particle", i
                call phs_prt_write (forest%prt(i), u)
            end if
        end do
    else
        write (u, "(3x,A)" "[all undefined]"
    end if
else
    write (u, "(3x,A)" " [empty]"
end if
end subroutine phs_forest_write

subroutine phs_grove_write (grove, unit)
    type(phs_grove_t), intent(in) :: grove
    integer, intent(in), optional :: unit
    integer :: u
    integer :: t
    u = given_output_unit (unit); if (u < 0) return
    do t = 1, size (grove%tree)
        write (u, "(3x,A,I0)" "Tree      ", t
        call phs_tree_write (grove%tree(t), unit)
    end do
    write (u, "(1x,A)" "Equivalence list:"
    call equivalence_list_write (grove%equivalence_list, unit)
end subroutine phs_grove_write

```

Deep copy.

```

<PHS forests: public>+≡
    public :: assignment(=)

<PHS forests: interfaces>+≡
    interface assignment(=)
        module procedure phs_forest_assign
    end interface

<PHS forests: procedures>+≡
    subroutine phs_forest_assign (forest_out, forest_in)

```



```

type(phs_forest_t), intent(out) :: forest_out
type(phs_forest_t), intent(in) :: forest_in
forest_out%n_in = forest_in%n_in
forest_out%n_out = forest_in%n_out
forest_out%n_tot = forest_in%n_tot
forest_out%n_masses = forest_in%n_masses
forest_out%n_angles = forest_in%n_angles
forest_out%n_dimensions = forest_in%n_dimensions
forest_out%n_trees = forest_in%n_trees
forest_out%n_equivalences = forest_in%n_equivalences
if (allocated (forest_in%flv)) then
    allocate (forest_out%flv (size (forest_in%flv)))
    forest_out%flv = forest_in%flv
end if
if (allocated (forest_in%grove)) then
    allocate (forest_out%grove (size (forest_in%grove)))
    forest_out%grove = forest_in%grove
end if
if (allocated (forest_in%grove_lookup)) then
    allocate (forest_out%grove_lookup (size (forest_in%grove_lookup)))
    forest_out%grove_lookup = forest_in%grove_lookup
end if
if (allocated (forest_in%prt_in)) then
    allocate (forest_out%prt_in (size (forest_in%prt_in)))
    forest_out%prt_in = forest_in%prt_in
end if
if (allocated (forest_in%prt_out)) then
    allocate (forest_out%prt_out (size (forest_in%prt_out)))
    forest_out%prt_out = forest_in%prt_out
end if
if (allocated (forest_in%prt)) then
    allocate (forest_out%prt (size (forest_in%prt)))
    forest_out%prt = forest_in%prt
end if
if (allocated (forest_in%s_mapping)) then
    allocate (forest_out%s_mapping (size (forest_in%s_mapping)))
    forest_out%s_mapping = forest_in%s_mapping
end if
if (allocated (forest_in%prt_combination)) then
    allocate (forest_out%prt_combination &
              (2, size (forest_in%prt_combination, 2)))
    forest_out%prt_combination = forest_in%prt_combination
end if
end subroutine phs_forest_assign

```

18.5.6 Accessing contents

Get the number of integration parameters

(PHS forests: public)+≡

```
public :: phs_forest_get_n_parameters
```

(PHS forests: procedures)+≡

```
function phs_forest_get_n_parameters (forest) result (n)
```

```

integer :: n
type(phs_forest_t), intent(in) :: forest
n = forest%n_dimensions
end function phs_forest_get_n_parameters

```

Get the number of integration channels

```

<PHS forests: public>+≡
public :: phs_forest_get_n_channels

<PHS forests: procedures>+≡
function phs_forest_get_n_channels (forest) result (n)
integer :: n
type(phs_forest_t), intent(in) :: forest
n = forest%n_trees
end function phs_forest_get_n_channels

```

Get the number of groves

```

<PHS forests: public>+≡
public :: phs_forest_get_n_groves

<PHS forests: procedures>+≡
function phs_forest_get_n_groves (forest) result (n)
integer :: n
type(phs_forest_t), intent(in) :: forest
n = size (forest%grove)
end function phs_forest_get_n_groves

```

Get the index bounds for a specific grove.

```

<PHS forests: public>+≡
public :: phs_forest_get_grove_bounds

<PHS forests: procedures>+≡
subroutine phs_forest_get_grove_bounds (forest, g, i0, i1, n)
type(phs_forest_t), intent(in) :: forest
integer, intent(in) :: g
integer, intent(out) :: i0, i1, n
n = size (forest%grove(g)%tree)
i0 = forest%grove(g)%tree_count_offset + 1
i1 = forest%grove(g)%tree_count_offset + n
end subroutine phs_forest_get_grove_bounds

```

Get the number of equivalences

```

<PHS forests: public>+≡
public :: phs_forest_get_n_equivalences

<PHS forests: procedures>+≡
function phs_forest_get_n_equivalences (forest) result (n)
integer :: n
type(phs_forest_t), intent(in) :: forest
n = forest%n_equivalences
end function phs_forest_get_n_equivalences

```

Return true if a particular channel has a global (s-channel) mapping; also return the resonance mass and width for this mapping.

```

(PHS forests: public)+≡
  public :: phs_forest_get_s_mapping
  public :: phs_forest_get_on_shell

(PHS forests: procedures)+≡
  subroutine phs_forest_get_s_mapping (forest, channel, flag, mass, width)
    type(phs_forest_t), intent(in) :: forest
    integer, intent(in) :: channel
    logical, intent(out) :: flag
    real(default), intent(out) :: mass, width
    flag = mapping_is_s_channel (forest%s_mapping(channel))
    if (flag) then
      mass = mapping_get_mass (forest%s_mapping(channel))
      width = mapping_get_width (forest%s_mapping(channel))
    else
      mass = 0
      width = 0
    end if
  end subroutine phs_forest_get_s_mapping

  subroutine phs_forest_get_on_shell (forest, channel, flag, mass)
    type(phs_forest_t), intent(in) :: forest
    integer, intent(in) :: channel
    logical, intent(out) :: flag
    real(default), intent(out) :: mass
    flag = mapping_is_on_shell (forest%s_mapping(channel))
    if (flag) then
      mass = mapping_get_mass (forest%s_mapping(channel))
    else
      mass = 0
    end if
  end subroutine phs_forest_get_on_shell

```

18.5.7 Read the phase space setup from file

The phase space setup is stored in a file. The file may be generated by the `cascades` module below, or by other means. This file has to be read and parsed to create the PHS forest as the internal phase-space representation.

Create lexer and syntax:

```

(PHS forests: procedures)+≡
  subroutine define_phs_forest_syntax (ifile)
    type(ifile_t) :: ifile
    call ifile_append (ifile, "SEQ phase_space_list = process_phase_space*")
    call ifile_append (ifile, "SEQ process_phase_space = " &
      // "process_def process_header phase_space")
    call ifile_append (ifile, "SEQ process_def = process_process_list")
    call ifile_append (ifile, "KEY process")
    call ifile_append (ifile, "LIS process_list = process_tag*")
    call ifile_append (ifile, "IDE process_tag")
    call ifile_append (ifile, "SEQ process_header = " &

```

```

// "md5sum_process = md5sum " &
// "md5sum_model_par = md5sum " &
// "md5sum_phs_config = md5sum " &
// "sqrts = real " &
// "m_threshold_s = real " &
// "m_threshold_t = real " &
// "off_shell = integer " &
// "t_channel = integer " &
// "keep_nonresonant = logical")
call ifile_append (ifile, "KEY '='")
call ifile_append (ifile, "KEY md5sum_process")
call ifile_append (ifile, "KEY md5sum_model_par")
call ifile_append (ifile, "KEY md5sum_phs_config")
call ifile_append (ifile, "KEY sqrts")
call ifile_append (ifile, "KEY m_threshold_s")
call ifile_append (ifile, "KEY m_threshold_t")
call ifile_append (ifile, "KEY off_shell")
call ifile_append (ifile, "KEY t_channel")
call ifile_append (ifile, "KEY keep_nonresonant")
call ifile_append (ifile, "QUO md5sum = '""' ... '""'")
call ifile_append (ifile, "REA real")
call ifile_append (ifile, "INT integer")
call ifile_append (ifile, "IDE logical")
call ifile_append (ifile, "SEQ phase_space = grove_def+")
call ifile_append (ifile, "SEQ grove_def = grove tree_def+")
call ifile_append (ifile, "KEY grove")
call ifile_append (ifile, "SEQ tree_def = tree bincodes mapping*")
call ifile_append (ifile, "KEY tree")
call ifile_append (ifile, "SEQ bincodes = bincodes*")
call ifile_append (ifile, "INT bincodes")
call ifile_append (ifile, "SEQ mapping = map bincodes channel pdg")
call ifile_append (ifile, "KEY map")
call ifile_append (ifile, "ALT channel = &
    &s_channel | t_channel | u_channel | &
    &collinear | infrared | radiation | on_shell")
call ifile_append (ifile, "KEY s_channel")
! call ifile_append (ifile, "KEY t_channel")    !!! Key already exists
call ifile_append (ifile, "KEY u_channel")
call ifile_append (ifile, "KEY collinear")
call ifile_append (ifile, "KEY infrared")
call ifile_append (ifile, "KEY radiation")
call ifile_append (ifile, "KEY on_shell")
call ifile_append (ifile, "INT pdg")
end subroutine define_phs_forest_syntax

```

The model-file syntax and lexer are fixed, therefore stored as module variables:

```

<PHS forests: variables>≡
    type(syntax_t), target, save :: syntax_phs_forest

<PHS forests: public>+≡
    public :: syntax_phs_forest_init

<PHS forests: procedures>+≡
    subroutine syntax_phs_forest_init ()

```

```

type(ifile_t) :: ifile
call define_phs_forest_syntax (ifile)
call syntax_init (syntax_phs_forest, ifile)
call ifile_final (ifile)
end subroutine syntax_phs_forest_init

```

```

<PHS forests: procedures>+≡
subroutine lexer_init_phs_forest (lexer)
  type(lexer_t), intent(out) :: lexer
  call lexer_init (lexer, &
    comment_chars = "#!", &
    quote_chars = '"', &
    quote_match = '"', &
    single_chars = "'", &
    special_class = ["="] , &
    keyword_list = syntax_get_keyword_list_ptr (syntax_phs_forest))
end subroutine lexer_init_phs_forest

```

```

<PHS forests: public>+≡
public :: syntax_phs_forest_final

```

```

<PHS forests: procedures>+≡
subroutine syntax_phs_forest_final ()
  call syntax_final (syntax_phs_forest)
end subroutine syntax_phs_forest_final

```

```

<PHS forests: public>+≡
public :: syntax_phs_forest_write

```

```

<PHS forests: procedures>+≡
subroutine syntax_phs_forest_write (unit)
  integer, intent(in), optional :: unit
  call syntax_write (syntax_phs_forest, unit)
end subroutine syntax_phs_forest_write

```

The concrete parser and interpreter. Generate an input stream for the external `unit`, read the parse tree (with given `syntax` and `lexer`) from this stream, and transfer the contents of the parse tree to the PHS forest.

We look for the matching `process` tag, count groves and trees for initializing the forest, and fill the trees.

If the optional parameters are set, compare the parameters stored in the file to those. Set `match` true if everything agrees.

```

<PHS forests: public>+≡
public :: phs_forest_read

```

```

<PHS forests: interfaces>+≡
interface phs_forest_read
  module procedure phs_forest_read_file
  module procedure phs_forest_read_unit
  module procedure phs_forest_read_parse_tree
end interface

```

(PHS forests: procedures)+≡

```

subroutine phs_forest_read_file &
  (forest, filename, process_id, n_in, n_out, model, found, &
   md5sum_process, md5sum_model_par, &
   md5sum_phs_config, phs_par, match)
  type(phs_forest_t), intent(out) :: forest
  type(string_t), intent(in) :: filename
  type(string_t), intent(in) :: process_id
  integer, intent(in) :: n_in, n_out
  class(model_data_t), intent(in), target :: model
  logical, intent(out) :: found
  character(32), intent(in), optional :: &
    md5sum_process, md5sum_model_par, md5sum_phs_config
  type(phs_parameters_t), intent(in), optional :: phs_par
  logical, intent(out), optional :: match
  type(parse_tree_t), target :: parse_tree
  type(stream_t), target :: stream
  type(lexer_t) :: lexer
  call lexer_init_phs_forest (lexer)
  call stream_init (stream, char (filename))
  call lexer_assign_stream (lexer, stream)
  call parse_tree_init (parse_tree, syntax_phs_forest, lexer)
  call phs_forest_read (forest, parse_tree, &
    process_id, n_in, n_out, model, found, &
    md5sum_process, md5sum_model_par, md5sum_phs_config, phs_par, match)
  call stream_final (stream)
  call lexer_final (lexer)
  call parse_tree_final (parse_tree)
end subroutine phs_forest_read_file

```

```

subroutine phs_forest_read_unit &
  (forest, unit, process_id, n_in, n_out, model, found, &
   md5sum_process, md5sum_model_par, md5sum_phs_config, &
   phs_par, match)
  type(phs_forest_t), intent(out) :: forest
  integer, intent(in) :: unit
  type(string_t), intent(in) :: process_id
  integer, intent(in) :: n_in, n_out
  class(model_data_t), intent(in), target :: model
  logical, intent(out) :: found
  character(32), intent(in), optional :: &
    md5sum_process, md5sum_model_par, md5sum_phs_config
  type(phs_parameters_t), intent(in), optional :: phs_par
  logical, intent(out), optional :: match
  type(parse_tree_t), target :: parse_tree
  type(stream_t), target :: stream
  type(lexer_t) :: lexer
  call lexer_init_phs_forest (lexer)
  call stream_init (stream, unit)
  call lexer_assign_stream (lexer, stream)
  call parse_tree_init (parse_tree, syntax_phs_forest, lexer)
  call phs_forest_read (forest, parse_tree, &
    process_id, n_in, n_out, model, found, &
    md5sum_process, md5sum_model_par, md5sum_phs_config, &

```

```

        phs_par, match)
    call stream_final (stream)
    call lexer_final (lexer)
    call parse_tree_final (parse_tree)
end subroutine phs_forest_read_unit

subroutine phs_forest_read_parse_tree &
    (forest, parse_tree, process_id, n_in, n_out, model, found, &
     md5sum_process, md5sum_model_par, md5sum_phs_config, &
     phs_par, match)
    type(phs_forest_t), intent(out) :: forest
    type(parse_tree_t), intent(in), target :: parse_tree
    type(string_t), intent(in) :: process_id
    integer, intent(in) :: n_in, n_out
    class(model_data_t), intent(in), target :: model
    logical, intent(out) :: found
    character(32), intent(in), optional :: &
        md5sum_process, md5sum_model_par, md5sum_phs_config
    type(phs_parameters_t), intent(in), optional :: phs_par
    logical, intent(out), optional :: match
    type(parse_node_t), pointer :: node_header, node_phs, node_grove
    integer :: n_grove, g
    integer, dimension(:), allocatable :: n_tree
    integer :: t
    node_header => parse_tree_get_process_ptr (parse_tree, process_id)
    found = associated (node_header); if (.not. found) return
    if (present (match)) then
        call phs_forest_check_input (node_header, &
            md5sum_process, md5sum_model_par, md5sum_phs_config, phs_par, match)
        if (.not. match) return
    end if
    node_phs => parse_node_get_next_ptr (node_header)
    n_grove = parse_node_get_n_sub (node_phs)
    allocate (n_tree (n_grove))
    do g = 1, n_grove
        node_grove => parse_node_get_sub_ptr (node_phs, g)
        n_tree(g) = parse_node_get_n_sub (node_grove) - 1
    end do
    call phs_forest_init (forest, n_tree, n_in, n_out)
    do g = 1, n_grove
        node_grove => parse_node_get_sub_ptr (node_phs, g)
        do t = 1, n_tree(g)
            call phs_tree_set (forest%grove(g)%tree(t), &
                parse_node_get_sub_ptr (node_grove, t+1), model)
        end do
    end do
end subroutine phs_forest_read_parse_tree

```

Check the input for consistency. If any MD5 sum or phase-space parameter disagrees, the phase-space file cannot be used. The MD5 sum checks are skipped if the stored MD5 sum is empty.

(PHS forests: procedures)+≡

```

subroutine phs_forest_check_input (pn_header, &

```

```

md5sum_process, md5sum_model_par, md5sum_phs_config, phs_par, match)
type(parse_node_t), intent(in), target :: pn_header
character(32), intent(in) :: &
    md5sum_process, md5sum_model_par, md5sum_phs_config
type(phs_parameters_t), intent(in), optional :: phs_par
logical, intent(out) :: match
type(parse_node_t), pointer :: pn_md5sum, pn_rval, pn_ival, pn_lval
character(32) :: md5sum
type(phs_parameters_t) :: phs_par_old
character(1) :: lstr
pn_md5sum => parse_node_get_sub_ptr (pn_header, 3)
md5sum = parse_node_get_string (pn_md5sum)
if (md5sum /= "" .and. md5sum /= md5sum_process) then
    call msg_message ("Phase space: discarding old configuration &
        &(process changed)")
    match = .false.; return
end if
pn_md5sum => parse_node_get_next_ptr (pn_md5sum, 3)
md5sum = parse_node_get_string (pn_md5sum)
if (md5sum /= "" .and. md5sum /= md5sum_model_par) then
    call msg_message ("Phase space: discarding old configuration &
        &(model parameters changed)")
    match = .false.; return
end if
pn_md5sum => parse_node_get_next_ptr (pn_md5sum, 3)
md5sum = parse_node_get_string (pn_md5sum)
if (md5sum /= "" .and. md5sum /= md5sum_phs_config) then
    call msg_message ("Phase space: discarding old configuration &
        &(configuration parameters changed)")
    match = .false.; return
end if
if (present (phs_par)) then
    pn_rval => parse_node_get_next_ptr (pn_md5sum, 3)
    phs_par_old%sqrts = parse_node_get_real (pn_rval)
    pn_rval => parse_node_get_next_ptr (pn_rval, 3)
    phs_par_old%m_threshold_s = parse_node_get_real (pn_rval)
    pn_rval => parse_node_get_next_ptr (pn_rval, 3)
    phs_par_old%m_threshold_t = parse_node_get_real (pn_rval)
    pn_ival => parse_node_get_next_ptr (pn_rval, 3)
    phs_par_old%off_shell = parse_node_get_integer (pn_ival)
    pn_ival => parse_node_get_next_ptr (pn_ival, 3)
    phs_par_old%t_channel = parse_node_get_integer (pn_ival)
    pn_lval => parse_node_get_next_ptr (pn_ival, 3)
    lstr = parse_node_get_string (pn_lval)
    read (lstr, "(L1)") phs_par_old%keep_nonresonant
    if (phs_par_old /= phs_par) then
        call msg_message &
            ("Phase space: discarding old configuration &
                &(configuration parameters changed)")
        match = .false.; return
    end if
end if
match = .true.
end subroutine phs_forest_check_input

```


Initialize a specific tree in the forest, using the contents of the 'tree' node. First, count the bincodes, allocate an array and read them in, and make the tree. Each *t*-channel tree is flipped to *s*-channel. Then, find mappings and initialize them.

(*PHS forests: procedures*) +=

```

subroutine phs_tree_set (tree, node, model)
  type(phs_tree_t), intent(inout) :: tree
  type(parse_node_t), intent(in), target :: node
  class(model_data_t), intent(in), target :: model
  type(parse_node_t), pointer :: node_bincodes, node_mapping
  integer :: n_bincodes, offset
  integer(TC), dimension(:), allocatable :: bincodes
  integer :: b, n_mappings, m
  integer(TC) :: k
  type(string_t) :: type
  integer :: pdg
  node_bincodes => parse_node_get_sub_ptr (node, 2)
  if (associated (node_bincodes)) then
    select case (char (parse_node_get_rule_key (node_bincodes)))
      case ("bincodes")
        n_bincodes = parse_node_get_n_sub (node_bincodes)
        offset = 2
      case default
        n_bincodes = 0
        offset = 1
    end select
  else
    n_bincodes = 0
    offset = 2
  end if
  allocate (bincodes (n_bincodes))
  do b = 1, n_bincodes
    bincodes(b) = parse_node_get_integer &
      (parse_node_get_sub_ptr (node_bincodes, b))
  end do
  call phs_tree_from_array (tree, bincodes)
  call phs_tree_flip_t_to_s_channel (tree)
  call phs_tree_canonicalize (tree)
  n_mappings = parse_node_get_n_sub (node) - offset
  do m = 1, n_mappings
    node_mapping => parse_node_get_sub_ptr (node, m + offset)
    k = parse_node_get_integer &
      (parse_node_get_sub_ptr (node_mapping, 2))
    type = parse_node_get_key &
      (parse_node_get_sub_ptr (node_mapping, 3))
    pdg = parse_node_get_integer &
      (parse_node_get_sub_ptr (node_mapping, 4))
    call phs_tree_init_mapping (tree, k, type, pdg, model)
  end do
end subroutine phs_tree_set

```

18.5.8 Preparation

The trees that we read from file do not carry flavor information. This is set separately:

The flavor list must be unique for a unique set of masses; if a given particle can have different flavor, the mass must be degenerate, so we can choose one of the possible flavor combinations.

```
(PHS forests: public)+≡
  public :: phs_forest_set_flavors

(PHS forests: procedures)+≡
  subroutine phs_forest_set_flavors (forest, flv, reshuffle, flv_extra)
    type(phs_forest_t), intent(inout) :: forest
    type(flavor_t), dimension(:), intent(in) :: flv
    integer, intent(in), dimension(:), allocatable, optional :: reshuffle
    type(flavor_t), intent(in), optional :: flv_extra
    integer :: i, n_flv0
    if (present (reshuffle) .and. present (flv_extra)) then
      n_flv0 = size (flv)
      do i = 1, n_flv0
        if (reshuffle(i) <= n_flv0) then
          forest%flv(i) = flv (reshuffle(i))
        else
          forest%flv(i) = flv_extra
        end if
      end do
    else
      allocate (forest%flv (size (flv)))
      forest%flv = flv
    end if
  end subroutine phs_forest_set_flavors

(PHS forests: public)+≡
  public :: phs_forest_set_momentum_links

(PHS forests: procedures)+≡
  subroutine phs_forest_set_momentum_links (forest, list)
    type(phs_forest_t), intent(inout) :: forest
    integer, intent(in), dimension(:), allocatable :: list
    integer :: g, t
    do g = 1, size (forest%grove)
      do t = 1, size (forest%grove(g)%tree)
        associate (tree => forest%grove(g)%tree(t))
          call phs_tree_set_momentum_links (tree, list)
        end associate
      end do
    end do
  end subroutine phs_forest_set_momentum_links
```

Once the parameter set is fixed, the masses and the widths of the particles are known and the `mass_sum` arrays as well as the mapping parameters can be computed. Note that order is important: we first compute the mass sums, then the ordinary mappings. The resonances obtained here determine the effective

masses, which in turn are used to implement step mappings for resonance decay products that are not mapped otherwise.

```

(PHS forests: public)+≡
  public :: phs_forest_set_parameters

(PHS forests: procedures)+≡
  subroutine phs_forest_set_parameters &
    (forest, mapping_defaults, variable_limits)
    type(phs_forest_t), intent(inout) :: forest
    type(mapping_defaults_t), intent(in) :: mapping_defaults
    logical, intent(in) :: variable_limits
    integer :: g, t
    do g = 1, size (forest%grove)
      do t = 1, size (forest%grove(g)%tree)
        call phs_tree_set_mass_sum &
          (forest%grove(g)%tree(t), forest%flv(forest%n_in+1:))
        call phs_tree_set_mapping_parameters (forest%grove(g)%tree(t), &
          mapping_defaults, variable_limits)
        call phs_tree_set_effective_masses (forest%grove(g)%tree(t))
        if (mapping_defaults%step_mapping) then
          call phs_tree_set_step_mappings (forest%grove(g)%tree(t), &
            mapping_defaults%step_mapping_exp, variable_limits)
        end if
      end do
    end do
  end subroutine phs_forest_set_parameters

```

Generate the particle combination table. Scan all trees and merge their individual combination tables. At the end, valid entries are non-zero, and they indicate the indices of a pair of particles to be combined to a new particle. If a particle is accessible by more than one tree (this is usual), only keep the first possibility.

```

(PHS forests: public)+≡
  public :: phs_forest_setup_prt_combinations

(PHS forests: procedures)+≡
  subroutine phs_forest_setup_prt_combinations (forest)
    type(phs_forest_t), intent(inout) :: forest
    integer :: g, t
    integer, dimension(:,:), allocatable :: tree_prt_combination
    forest%prt_combination = 0
    allocate (tree_prt_combination (2, size (forest%prt_combination, 2)))
    do g = 1, size (forest%grove)
      do t = 1, size (forest%grove(g)%tree)
        call phs_tree_setup_prt_combinations &
          (forest%grove(g)%tree(t), tree_prt_combination)
        where (tree_prt_combination /= 0 .and. forest%prt_combination == 0)
          forest%prt_combination = tree_prt_combination
        end where
      end do
    end do
  end subroutine phs_forest_setup_prt_combinations

```

18.5.9 Accessing the particle arrays

Set the incoming particles from the contents of an interaction.

```

(PHS forests: public)+≡
    public :: phs_forest_set_prt_in

(PHS forests: interfaces)+≡
    interface phs_forest_set_prt_in
        module procedure phs_forest_set_prt_in_int, phs_forest_set_prt_in_mom
    end interface phs_forest_set_prt_in

(PHS forests: procedures)+≡
    subroutine phs_forest_set_prt_in_int (forest, int, lt_cm_to_lab)
        type(phs_forest_t), intent(inout) :: forest
        type(interaction_t), intent(in) :: int
        type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
        if (present (lt_cm_to_lab)) then
            call phs_prt_set_momentum (forest%prt_in, &
                inverse (lt_cm_to_lab) * &
                int%get_momenta (outgoing=.false.))
        else
            call phs_prt_set_momentum (forest%prt_in, &
                int%get_momenta (outgoing=.false.))
        end if
        associate (m_in => forest%flv(:forest%n_in)%get_mass ())
            call phs_prt_set_msq (forest%prt_in, m_in ** 2)
        end associate
        call phs_prt_set_defined (forest%prt_in)
    end subroutine phs_forest_set_prt_in_int

    subroutine phs_forest_set_prt_in_mom (forest, mom, lt_cm_to_lab)
        type(phs_forest_t), intent(inout) :: forest
        type(vector4_t), dimension(size (forest%prt_in)), intent(in) :: mom
        type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
        if (present (lt_cm_to_lab)) then
            call phs_prt_set_momentum (forest%prt_in, &
                inverse (lt_cm_to_lab) * mom)
        else
            call phs_prt_set_momentum (forest%prt_in, mom)
        end if
        associate (m_in => forest%flv(:forest%n_in)%get_mass ())
            call phs_prt_set_msq (forest%prt_in, m_in ** 2)
        end associate
        call phs_prt_set_defined (forest%prt_in)
    end subroutine phs_forest_set_prt_in_mom

```

Set the outgoing particles from the contents of an interaction.

```

(PHS forests: public)+≡
    public :: phs_forest_set_prt_out

(PHS forests: interfaces)+≡
    interface phs_forest_set_prt_out
        module procedure phs_forest_set_prt_out_int, phs_forest_set_prt_out_mom
    end interface phs_forest_set_prt_out

```

(PHS forests: procedures)+≡

```

subroutine phs_forest_set_prt_out_int (forest, int, lt_cm_to_lab)
  type(phs_forest_t), intent(inout) :: forest
  type(interaction_t), intent(in) :: int
  type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
  if (present (lt_cm_to_lab)) then
    call phs_prt_set_momentum (forest%prt_out, &
      inverse (lt_cm_to_lab) * &
      int%get_momenta (outgoing=.true.))
  else
    call phs_prt_set_momentum (forest%prt_out, &
      int%get_momenta (outgoing=.true.))
  end if
  associate (m_out => forest%flv(forest%n_in+1:)%get_mass ())
    call phs_prt_set_msq (forest%prt_out, m_out ** 2)
  end associate
  call phs_prt_set_defined (forest%prt_out)
end subroutine phs_forest_set_prt_out_int

subroutine phs_forest_set_prt_out_mom (forest, mom, lt_cm_to_lab)
  type(phs_forest_t), intent(inout) :: forest
  type(vector4_t), dimension(size (forest%prt_out)), intent(in) :: mom
  type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
  if (present (lt_cm_to_lab)) then
    call phs_prt_set_momentum (forest%prt_out, &
      inverse (lt_cm_to_lab) * mom)
  else
    call phs_prt_set_momentum (forest%prt_out, mom)
  end if
  associate (m_out => forest%flv(forest%n_in+1:)%get_mass ())
    call phs_prt_set_msq (forest%prt_out, m_out ** 2)
  end associate
  call phs_prt_set_defined (forest%prt_out)
end subroutine phs_forest_set_prt_out_mom

```

Combine particles as described by the particle combination table. Particle momentum sums will be calculated only if the resulting particle is contained in at least one of the trees in the current forest. The others are kept undefined.

(PHS forests: public)+≡

```

public :: phs_forest_combine_particles

```

(PHS forests: procedures)+≡

```

subroutine phs_forest_combine_particles (forest)
  type(phs_forest_t), intent(inout) :: forest
  integer :: k
  integer, dimension(2) :: kk
  do k = 1, size (forest%prt_combination, 2)
    kk = forest%prt_combination(:,k)
    if (kk(1) /= 0) then
      call phs_prt_combine (forest%prt(k), &
        forest%prt(kk(1)), forest%prt(kk(2)))
    end if
  end do
end subroutine phs_forest_combine_particles

```

Extract the outgoing particles and insert into an interaction.

```

(PHS forests: public)+≡
  public :: phs_forest_get_prt_out

(PHS forests: procedures)+≡
  subroutine phs_forest_get_prt_out (forest, int, lt_cm_to_lab)
    type(phs_forest_t), intent(in) :: forest
    type(interaction_t), intent(inout) :: int
    type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
    if (present (lt_cm_to_lab)) then
      call int%set_momenta (lt_cm_to_lab * &
        phs_prt_get_momentum (forest%prt_out), outgoing=.true.)
    else
      call int%set_momenta (phs_prt_get_momentum (forest%prt_out), &
        outgoing=.true.)
    end if
  end subroutine phs_forest_get_prt_out

```

Extract the outgoing particle momenta

```

(PHS forests: public)+≡
  public :: phs_forest_get_momenta_out

(PHS forests: procedures)+≡
  function phs_forest_get_momenta_out (forest, lt_cm_to_lab) result (p)
    type(phs_forest_t), intent(in) :: forest
    type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
    type(vector4_t), dimension(size (forest%prt_out)) :: p
    p = phs_prt_get_momentum (forest%prt_out)
    if (present (lt_cm_to_lab)) p = p * lt_cm_to_lab
  end function phs_forest_get_momenta_out

```

18.5.10 Find equivalences among phase-space trees

Scan phase space for equivalences. We generate the complete set of unique permutations for the given list of outgoing particles, and use this for scanning equivalences within each grove. We scan all pairs of trees, using all permutations. This implies that trivial equivalences are included, and equivalences between different trees are recorded twice. This is intentional.

```

(PHS forests: procedures)+≡
  subroutine phs_grove_set_equivalences (grove, perm_array)
    type(phs_grove_t), intent(inout) :: grove
    type(permutation_t), dimension(:), intent(in) :: perm_array
    type(equivalence_t), pointer :: eq
    integer :: t1, t2, i
    do t1 = 1, size (grove%tree)
      do t2 = 1, size (grove%tree)
        SCAN_PERM: do i = 1, size (perm_array)
          if (phs_tree_equivalent &
            (grove%tree(t1), grove%tree(t2), perm_array(i))) then
            call equivalence_list_add &

```

```

        (grove%equivalence_list, t1, t2, perm_array(i))
    eq => grove%equivalence_list%last
    call phs_tree_find_msq_permutation &
        (grove%tree(t1), grove%tree(t2), eq%perm, &
         eq%msq_perm)
    call phs_tree_find_angle_permutation &
        (grove%tree(t1), grove%tree(t2), eq%perm, &
         eq%angle_perm, eq%angle_sig)
    end if
end do SCAN_PERM
end do
end do
end subroutine phs_grove_set_equivalences

```

```

<PHS forests: public>+≡
    public :: phs_forest_set_equivalences

<PHS forests: procedures>+≡
    subroutine phs_forest_set_equivalences (forest)
        type(phs_forest_t), intent(inout) :: forest
        type(permutation_t), dimension(:), allocatable :: perm_array
        integer :: i
        call permutation_array_make &
            (perm_array, forest%flv(forest%n_in+1:)%get_pdg ())
        do i = 1, size (forest%grove)
            call phs_grove_set_equivalences (forest%grove(i), perm_array)
        end do
        forest%n_equivalences = sum (forest%grove%equivalence_list%length)
    end subroutine phs_forest_set_equivalences

```

18.5.11 Interface for channel equivalences

Here, we store the equivalence list in the appropriate containers that the `phs_base` module provides. There is one separate list for each channel.

```

<PHS forests: public>+≡
    public :: phs_forest_get_equivalences

<PHS forests: procedures>+≡
    subroutine phs_forest_get_equivalences (forest, channel, azimuthal_dependence)
        type(phs_forest_t), intent(in) :: forest
        type(phs_channel_t), dimension(:), intent(out) :: channel
        logical, intent(in) :: azimuthal_dependence
        integer :: n_masses, n_angles
        integer :: mode_azimuthal_angle
        integer, dimension(:), allocatable :: n_eq
        type(equivalence_t), pointer :: eq
        integer, dimension(:), allocatable :: perm, mode
        integer :: g, c, j, left, right
        n_masses = forest%n_masses
        n_angles = forest%n_angles
        allocate (n_eq (forest%n_trees), source = 0)
        allocate (perm (forest%n_dimensions))
        allocate (mode (forest%n_dimensions), source = EQ_IDENTITY)
    end subroutine phs_forest_get_equivalences

```

```

do g = 1, size (forest%grove)
  eq => forest%grove(g)%equivalence_list%first
  do while (associated (eq))
    left = eq%left + forest%grove(g)%tree_count_offset
    n_eq(left) = n_eq(left) + 1
    eq => eq%next
  end do
end do
do c = 1, size (channel)
  allocate (channel(c)%eq (n_eq(c)))
  do j = 1, n_eq(c)
    call channel(c)%eq(j)%init (forest%n_dimensions)
  end do
end do
n_eq = 0
if (azimuthal_dependence) then
  mode_azimuthal_angle = EQ_IDENTITY
else
  mode_azimuthal_angle = EQ_INVARIANT
end if
do g = 1, size (forest%grove)
  eq => forest%grove(g)%equivalence_list%first
  do while (associated (eq))
    left = eq%left + forest%grove(g)%tree_count_offset
    right = eq%right + forest%grove(g)%tree_count_offset
    do j = 1, n_masses
      perm(j) = permute (j, eq%msq_perm)
      mode(j) = EQ_IDENTITY
    end do
    do j = 1, n_angles
      perm(n_masses+j) = n_masses + permute (j, eq%angle_perm)
      if (j == 1) then
        mode(n_masses+j) = mode_azimuthal_angle      ! first az. angle
      else if (mod(j,2) == 1) then
        mode(n_masses+j) = EQ_SYMMETRIC              ! other az. angles
      else if (eq%angle_sig(j)) then
        mode(n_masses+j) = EQ_IDENTITY                ! polar angle +
      else
        mode(n_masses+j) = EQ_INVERT                  ! polar angle -
      end if
    end do
    n_eq(left) = n_eq(left) + 1
    associate (eq_cur => channel(left)%eq(n_eq(left)))
    eq_cur%c = right
    eq_cur%perm = perm
    eq_cur%mode = mode
  end associate
  eq => eq%next
end do
end do
end subroutine phs_forest_get_equivalences

```


18.5.12 Phase-space evaluation

Given one row of the **x** parameter array and the corresponding channel index, compute first all relevant momenta and then recover the remainder of the **x** array, the Jacobians **phs_factor**, and the phase-space **volume**.

The output argument **ok** indicates whether this was successful.

(PHS forests: public)+≡

public :: phs_forest_evaluate_selected_channel

(PHS forests: procedures)+≡

```
subroutine phs_forest_evaluate_selected_channel &
    (forest, channel, active, sqrts, x, phs_factor, volume, ok)
    type(phs_forest_t), intent(inout) :: forest
    integer, intent(in) :: channel
    logical, dimension(:), intent(in) :: active
    real(default), intent(in) :: sqrts
    real(default), dimension(:,:), intent(inout) :: x
    real(default), dimension(:), intent(out) :: phs_factor
    real(default), intent(out) :: volume
    logical, intent(out) :: ok
    integer :: g, t
    integer(TC) :: k, k_root, k_in

    g = forest%grove_lookup (channel)
    t = channel - forest%grove(g)%tree_count_offset
    call phs_prt_set_undefined (forest%prt)
    call phs_prt_set_undefined (forest%prt_out)
    k_in = forest%n_tot

    do k = 1, forest%n_in
        forest%prt(ibset(0,k_in-k)) = forest%prt_in(k)
    end do

    do k = 1, forest%n_out
        call phs_prt_set_msq (forest%prt(ibset(0,k-1)), &
            forest%flv(forest%n_in+k)%get_mass () ** 2)
    end do

    k_root = 2**forest%n_out - 1
    select case (forest%n_in)
    case (1)
        forest%prt(k_root) = forest%prt_in(1)
    case (2)
        call phs_prt_combine &
            (forest%prt(k_root), forest%prt_in(1), forest%prt_in(2))
    end select
    call phs_tree_compute_momenta_from_x (forest%grove(g)%tree(t), &
        forest%prt, phs_factor(channel), volume, sqrts, x(:,channel), ok)
    if (ok) then
        do k = 1, forest%n_out
            forest%prt_out(k) = forest%prt(ibset(0,k-1))
        end do
    end if
end subroutine phs_forest_evaluate_selected_channel
```

The remainder: recover x values for all channels except for the current channel.

NOTE: OpenMP not used for the first loop. `combine_particles` is not a channel-local operation.

```

(PHS forests: public)+≡
    public :: phs_forest_evaluate_other_channels

(PHS forests: procedures)+≡
    subroutine phs_forest_evaluate_other_channels &
        (forest, channel, active, sqrts, x, phs_factor, combine)
        type(phs_forest_t), intent(inout) :: forest
        integer, intent(in) :: channel
        logical, dimension(:), intent(in) :: active
        real(default), intent(in) :: sqrts
        real(default), dimension(:,:), intent(inout) :: x
        real(default), dimension(:), intent(inout) :: phs_factor
        logical, intent(in) :: combine
        integer :: g, t, ch, n_channel

        g = forest%grove_lookup (channel)
        t = channel - forest%grove(g)%tree_count_offset

        n_channel = forest%n_trees
        if (combine) then
            do ch = 1, n_channel
                if (ch == channel) cycle
                if (active(ch)) then
                    g = forest%grove_lookup(ch)
                    t = ch - forest%grove(g)%tree_count_offset
                    call phs_tree_combine_particles &
                        (forest%grove(g)%tree(t), forest%prt)
                end if
            end do
        end if

        !OMP PARALLEL PRIVATE (g,t,ch) SHARED(active,forest,sqrts,x,channel)
        !OMP DO SCHEDULE(STATIC)
        do ch = 1, n_channel
            if (ch == channel) cycle
            if (active(ch)) then
                g = forest%grove_lookup(ch)
                t = ch - forest%grove(g)%tree_count_offset
                call phs_tree_compute_x_from_momenta &
                    (forest%grove(g)%tree(t), &
                     forest%prt, phs_factor(ch), sqrts, x(:,ch))
            end if
        end do
        !OMP END DO
        !OMP END PARALLEL

    end subroutine phs_forest_evaluate_other_channels

```

The complement: recover one row of the x array and the associated Jacobian

entry, corresponding to `channel`, from incoming and outgoing momenta. Also compute the phase-space volume.

```

<PHS forests: public>+≡
    public :: phs_forest_recover_channel

<PHS forests: procedures>+≡
    subroutine phs_forest_recover_channel &
        (forest, channel, sqrts, x, phs_factor, volume)
        type(phs_forest_t), intent(inout) :: forest
        integer, intent(in) :: channel
        real(default), intent(in) :: sqrts
        real(default), dimension(:,:), intent(inout) :: x
        real(default), dimension(:), intent(inout) :: phs_factor
        real(default), intent(out) :: volume
        integer :: g, t
        integer(TC) :: k, k_in
        g = forest%grove_lookup (channel)
        t = channel - forest%grove(g)%tree_count_offset
        call phs_prt_set_undefined (forest%prt)
        k_in = forest%n_tot
        forall (k = 1:forest%n_in)
            forest%prt(ibset(0,k_in-k)) = forest%prt_in(k)
        end forall
        forall (k = 1:forest%n_out)
            forest%prt(ibset(0,k-1)) = forest%prt_out(k)
        end forall
        call phs_forest_combine_particles (forest)
        call phs_tree_compute_volume &
            (forest%grove(g)%tree(t), sqrts, volume)
        call phs_tree_compute_x_from_momenta &
            (forest%grove(g)%tree(t), &
            forest%prt, phs_factor(channel), sqrts, x(:,channel))
    end subroutine phs_forest_recover_channel

```

18.5.13 Unit tests

Write a possible phase-space file for a $2 \rightarrow 3$ process and make the corresponding forest, print the forest. Choose some in-particle momenta and a random-number array and evaluate out-particles and phase-space factors.

```

<PHS forests: public>+≡
    public :: phs_forest_test

<PHS forests: procedures>+≡
    subroutine phs_forest_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <PHS forests: execute tests>
    end subroutine phs_forest_test

<PHS forests: execute tests>≡
    call test (phs_forest_1, "phs_forest_1", &
        "check phs forest setup", &
        u, results)

```

<PHS forests: tests>≡

```

subroutine phs_forest_1 (u)
  use os_interface
  integer, intent(in) :: u
  type(phs_forest_t) :: forest
  type(phs_channel_t), dimension(:), allocatable :: channel
  type(model_data_t), target :: model
  type(string_t) :: process_id
  type(flavor_t), dimension(5) :: flv
  type(string_t) :: filename
  type(interaction_t) :: int
  integer, parameter :: unit_fix = 20
  type(mapping_defaults_t) :: mapping_defaults
  logical :: found_process, ok
  integer :: n_channel, ch, i
  logical, dimension(4) :: active = .true.
  real(default) :: sqrts = 1000
  real(default), dimension(5,4) :: x
  real(default), dimension(4) :: factor
  real(default) :: volume

  write (u, "(A)")  "* Test output: PHS forest"
  write (u, "(A)")  "* Purpose: test PHS forest routines"
  write (u, "(A)")

  write (u, "(A)")  "* Reading model file"

  call model%init_sm_test ()

  write (u, "(A)")
  write (u, "(A)")  "* Create phase-space file 'phs_forest_test.phs'"
  write (u, "(A)")

  call flv%init ([11, -11, 11, -11, 22], model)
  open (file="phs_forest_test.phs", unit=unit_fix, action="write")
  write (unit_fix, *) "process foo"
  write (unit_fix, *) 'md5sum_process      = "6ABA33BC2927925D0F073B1C1170780A"'
  write (unit_fix, *) 'md5sum_model_par   = "1A0B151EE6E2DEB92D880320355A3EAB"'
  write (unit_fix, *) 'md5sum_phs_config = "B6A8877058809A8BDD54753CDAB83ACE"'
  write (unit_fix, *) "sqrts              = 100.00000000000000"
  write (unit_fix, *) "m_threshold_s    = 50.00000000000000"
  write (unit_fix, *) "m_threshold_t    = 100.00000000000000"
  write (unit_fix, *) "off_shell       = 2"
  write (unit_fix, *) "t_channel       = 6"
  write (unit_fix, *) "keep_nonresonant = F"
  write (unit_fix, *) ""
  write (unit_fix, *) "  grove"
  write (unit_fix, *) "    tree 3 7"
  write (unit_fix, *) "      map 3 s_channel 23"
  write (unit_fix, *) "    tree 5 7"
  write (unit_fix, *) "    tree 6 7"
  write (unit_fix, *) "  grove"
  write (unit_fix, *) "    tree 9 11"
  write (unit_fix, *) "      map 9 t_channel 22"

```

```

close (unit_fix)

write (u, "(A)")
write (u, "(A)")  "* Read phase-space file 'phs_forest_test.phs'"

call syntax_phs_forest_init ()
process_id = "foo"
filename = "phs_forest_test.phs"
call phs_forest_read &
    (forest, filename, process_id, 2, 3, model, found_process)

write (u, "(A)")
write (u, "(A)")  "* Set parameters, flavors, equiv, momenta"
write (u, "(A)")

call phs_forest_set_flavors (forest, flv)
call phs_forest_set_parameters (forest, mapping_defaults, .false.)
call phs_forest_setup_prt_combinations (forest)
call phs_forest_set_equivalences (forest)
call int%basic_init (2, 0, 3)
call int%set_momentum &
    (vector4_moving (500._default, 500._default, 3), 1)
call int%set_momentum &
    (vector4_moving (500._default, -500._default, 3), 2)
call phs_forest_set_prt_in (forest, int)
n_channel = 2
x = 0
x(:,n_channel) = [0.3, 0.4, 0.1, 0.9, 0.6]
write (u, "(A)")  "   Input values:"
write (u, "(3x,5(1x," // FMT_12 // "))")  x(:,n_channel)

write (u, "(A)")
write (u, "(A)")  "* Evaluating phase space"

call phs_forest_evaluate_selected_channel (forest, &
    n_channel, active, sqrts, x, factor, volume, ok)
call phs_forest_evaluate_other_channels (forest, &
    n_channel, active, sqrts, x, factor, combine=.true.)
call phs_forest_get_prt_out (forest, int)
write (u, "(A)")  "   Output values:"
do ch = 1, 4
    write (u, "(3x,5(1x," // FMT_12 // "))")  x(:,ch)
end do
call int%basic_write (u)
write (u, "(A)")  "   Factors:"
write (u, "(3x,5(1x," // FMT_12 // "))")  factor
write (u, "(A)")  "   Volume:"
write (u, "(3x,5(1x," // FMT_12 // "))")  volume
call phs_forest_write (forest, u)

write (u, "(A)")
write (u, "(A)")  "* Compute equivalences"

n_channel = 4

```

```

allocate (channel (n_channel))
call phs_forest_get_equivalences (forest, &
    channel, .true.)
do i = 1, n_channel
    write (u, "(ix,i0,':')", advance = "no") ch
    call channel(i)%write (u)
end do

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call model%final ()
call phs_forest_final (forest)
call syntax_phs_forest_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_forest_1"

end subroutine phs_forest_1

```

18.6 Finding phase space parameterizations

If the phase space configuration is not found in the appropriate file, we should generate one.

The idea is to construct all Feynman diagrams subject to certain constraints which eliminate everything that is probably irrelevant for the integration. These Feynman diagrams (cascades) are grouped in groves by finding equivalence classes related by symmetry and ordered with respect to their importance (resonances). Finally, the result (or part of it) is written to file and used for the integration.

This module may eventually disappear and be replaced by CAML code. In particular, we need here a set of Feynman rules (vertices with particle codes, but not the factors). Thus, the module works for the Standard Model only.

Note that this module is stand-alone, it communicates to the main program only via the generated ASCII phase-space configuration file.

```

<cascades.f90>≡
<File header>

```

```

module cascades

```

```

<Use kinds>

```

```

    use kinds, only: TC, i8, i32

```

```

<Use strings>

```

```

    use io_units

```

```

    use format_defs, only: FMT_12, FMT_19

```

```

    use unit_tests

```

```

    use diagnostics

```

```

    use hashes

```

```

    use sorting

```

```

    use physics_defs, only: SCALAR, SPINOR, VECTOR, VECTORSPINOR, TENSOR

```

```

    use physics_defs, only: UNDEFINED
    use model_data
    use flavors
    use phs_forests

    <Standard module head>

    <Cascades: public>

    <Cascades: parameters>

    <Cascades: types>

    <Cascades: interfaces>

    contains

    <Cascades: procedures>

    <Cascades: tests>

    end module cascades

```

18.6.1 The mapping modes

The valid mapping modes, to be used below. We will make use of the convention that mappings of internal particles have a positive value. Only for positive values, the flavor code is propagated when combining cascades.

```

<Mapping modes>≡
    integer, parameter :: &
        & EXTERNAL_PRT = -1, &
        & NO_MAPPING = 0, S_CHANNEL = 1, T_CHANNEL = 2, U_CHANNEL = 3, &
        & RADIATION = 4, COLLINEAR = 5, INFRARED = 6, &
        & STEP_MAPPING_E = 11, STEP_MAPPING_H = 12, &
        & ON_SHELL = 99

    <Cascades: parameters>≡
    <Mapping modes>

```

18.6.2 The cascade type

A cascade is essentially the same as a decay tree (both definitions may be merged in a later version). It contains a linked tree of nodes, each of which representing an internal particle. In contrast to decay trees, each node has a definite particle code. These nodes need not be modified, therefore we can use pointers and do not have to copy them. Thus, physically each cascades has only a single node, the mother particle. However, to be able to compare trees quickly, we store in addition an array of binary codes which is always sorted in ascending order. This is accompanied by a corresponding list of particle codes. The index is the location of the corresponding cascade in the cascade set, this may be used to access the daughters directly.

The real mass is the particle mass belonging to the particle code. The minimal mass is the sum of the real masses of all its daughters; this is the kinematical cutoff. The effective mass may be zero if the particle mass is below a certain threshold; it may be the real mass if the particle is resonant; or it may be some other value.

The logical `t_channel` is set if this a t -channel line, while `initial` is true only for an initial particle. Note that both initial particles are also `t_channel` by definition, and that they are distinguished by the direction of the tree: One of them decays and is the root of the tree, while the other one is one of the leaves.

The cascade is a list of nodes (particles) which are linked via the `daughter` entries. The node is the mother particle of the decay cascade. Much of the information in the nodes is repeated in arrays, to be accessible more easily. The arrays will be kept sorted by binary codes.

The counter `n_off_shell` is increased for each internal line that is neither resonant nor log-enhanced. It is set to zero if the current line is resonant, since this implies on-shell particle production and subsequent decay.

The counter `n_t_channel` is non-negative once an initial particle is included in the tree: then, it counts the number of t -channel lines.

The `multiplicity` is the number of branchings to follow until all daughters are on-shell. A resonant or non-decaying particle has multiplicity one. Merging nodes, the multiplicities add unless the mother is a resonance. An initial or final node has multiplicity zero.

The arrays correspond to the subnode tree `tree` of the current cascade. PDG codes are stored only for those positions which are resonant, with the exception of the last entry, i.e., the current node. Other positions, in particular external legs, are assigned undefined PDG code.

A cascade is uniquely identified by its tree, the tree of PDG codes, and the tree of mappings. The tree of resonances is kept only to mask the PDG tree as described above.

$\langle \text{Cascades: types} \rangle \equiv$

```

type :: cascade_t
  private
  ! counters
  integer :: index = 0
  integer :: grove = 0
  ! status
  logical :: active = .false.
  logical :: complete = .false.
  logical :: incoming = .false.
  ! this node
  integer(TC) :: bincode = 0
  type(flavor_t) :: flv
  integer :: pdg = UNDEFINED
  logical :: is_vector = .false.
  real(default) :: m_min = 0
  real(default) :: m_rea = 0
  real(default) :: m_eff = 0
  integer :: mapping = NO_MAPPING
  logical :: on_shell = .false.
  logical :: resonant = .false.

```



```

logical :: log_enhanced = .false.
logical :: t_channel = .false.
! global tree properties
integer :: multiplicity = 0
integer :: internal = 0
integer :: n_off_shell = 0
integer :: n_resonances = 0
integer :: n_log_enhanced = 0
integer :: n_t_channel = 0
integer :: res_hash = 0
! the sub-node tree
integer :: depth = 0
integer(TC), dimension(:), allocatable :: tree
integer, dimension(:), allocatable :: tree_pdg
integer, dimension(:), allocatable :: tree_mapping
logical, dimension(:), allocatable :: tree_resonant
! branch connections
logical :: has_children = .false.
type(cascade_t), pointer :: daughter1 => null ()
type(cascade_t), pointer :: daughter2 => null ()
type(cascade_t), pointer :: mother => null ()
! next in list
type(cascade_t), pointer :: next => null ()
end type cascade_t

```

<Cascades: procedures>≡

```

subroutine cascade_init (cascade, depth)
  type(cascade_t), intent(out) :: cascade
  integer, intent(in) :: depth
  integer, save :: index = 0
  index = cascade_index ()
  cascade%index = index
  cascade%depth = depth
  cascade%active = .true.
  allocate (cascade%tree (depth))
  allocate (cascade%tree_pdg (depth))
  allocate (cascade%tree_mapping (depth))
  allocate (cascade%tree_resonant (depth))
end subroutine cascade_init

```

Keep and increment a global index

<Cascades: procedures>+≡

```

function cascade_index (seed) result (index)
  integer :: index
  integer, intent(in), optional :: seed
  integer, save :: i = 0
  if (present (seed)) i = seed
  i = i + 1
  index = i
end function cascade_index

```

We need three versions of writing cascades. This goes to the phase-space file:

<Cascades: procedures>+≡

```

subroutine cascade_write_file_format (cascade, model, unit)
  type(cascade_t), intent(in) :: cascade
  class(model_data_t), intent(in), target :: model
  integer, intent(in), optional :: unit
  type(flavor_t) :: flv
  integer :: u, i
1  format(3x,A,1x,40(1x,I4))
2  format(3x,A,1x,I3,1x,A,1x,I7,1x,'!',1x,A)
  u = given_output_unit (unit); if (u < 0) return
  call write_reduced (cascade%tree, u)
  write (u, "(A)")
  do i = 1, cascade%depth
    call flv%init (cascade%tree_pdg(i), model)
    select case (cascade%tree_mapping(i))
    case (NO_MAPPING, EXTERNAL_PRT)
    case (S_CHANNEL)
      write(u,2) 'map', &
        cascade%tree(i), 's_channel', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case (T_CHANNEL)
      write(u,2) 'map', &
        cascade%tree(i), 't_channel', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case (U_CHANNEL)
      write(u,2) 'map', &
        cascade%tree(i), 'u_channel', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case (RADIATION)
      write(u,2) 'map', &
        cascade%tree(i), 'radiation', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case (COLLINEAR)
      write(u,2) 'map', &
        cascade%tree(i), 'collinear', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case (INFRARED)
      write(u,2) 'map', &
        cascade%tree(i), 'infrared ', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case (ON_SHELL)
      write(u,2) 'map', &
        cascade%tree(i), 'on_shell ', abs (cascade%tree_pdg(i)), &
        char (flv%get_name ())
    case default
      call msg_bug (" Impossible mapping mode encountered")
    end select
  end do
contains
  subroutine write_reduced (array, unit)
    integer(TC), dimension(:), intent(in) :: array
    integer, intent(in) :: unit
    integer :: i
    write (u, "(3x,A,1x)", advance="no") "tree"
    do i = 1, size (array)

```

```

        if (decay_level (array(i)) > 1) then
            write (u, "(1x,I0)", advance="no") array(i)
        end if
    end do
end subroutine write_reduced

elemental function decay_level (k) result (l)
    integer(TC), intent(in) :: k
    integer :: l
    integer :: i
    l = 0
    do i = 0, bit_size(k) - 1
        if (btest(k,i)) l = l + 1
    end do
end function decay_level
subroutine start_comment (u)
    integer, intent(in) :: u
    write(u, '(1x,A)', advance='no') '!'
end subroutine start_comment
end subroutine cascade_write_file_format

```

This creates metapost source for graphical display:

(Cascades: procedures)+≡

```

subroutine cascade_write_graph_format (cascade, count, unit)
    type(cascade_t), intent(in) :: cascade
    integer, intent(in) :: count
    integer, intent(in), optional :: unit
    integer :: u
    integer(TC) :: mask
    type(string_t) :: left_str, right_str
    u = given_output_unit (unit); if (u < 0) return
    mask = 2**((cascade%depth+3)/2) - 1
    left_str = ""
    right_str = ""
    write (u, '(A)') "\begin{minipage}{105pt}"
    write (u, '(A)') "\vspace{30pt}"
    write (u, '(A)') "\begin{center}"
    write (u, '(A)') "\begin{fmfgraph*}(55,55)"
    call graph_write (cascade, mask)
    write (u, '(A)') "\fmfleft{" // char (extract (left_str, 2)) // "}"
    write (u, '(A)') "\fmfright{" // char (extract (right_str, 2)) // "}"
    write (u, '(A)') "\end{fmfgraph*}\\"
    write (u, '(A,I5,A)') "\fbox{$", count, "$}"
    write (u, '(A)') "\end{center}"
    write (u, '(A)') "\end{minipage}"
    write (u, '(A)') "%"
contains
    recursive subroutine graph_write (cascade, mask, reverse)
        type(cascade_t), intent(in) :: cascade
        integer(TC), intent(in) :: mask
        logical, intent(in), optional :: reverse
        type(flavor_t) :: anti
        logical :: rev
        rev = .false.; if (present(reverse)) rev = reverse

```

```

if (cascade%has_children) then
  if (.not.rev) then
    call vertex_write (cascade, cascade%daughter1, mask)
    call vertex_write (cascade, cascade%daughter2, mask)
  else
    call vertex_write (cascade, cascade%daughter2, mask, .true.)
    call vertex_write (cascade, cascade%daughter1, mask, .true.)
  end if
  if (cascade%complete) then
    call vertex_write (cascade, cascade%mother, mask, .true.)
    write (u, '(A,I0,A)') "\fmfv{d.shape=square}{v0}"
  end if
else
  if (cascade%incoming) then
    anti = cascade%flv%anti ()
    call external_write (cascade%bincode, anti%get_tex_name (), &
      left_str)
  else
    call external_write (cascade%bincode, cascade%flv%get_tex_name (), &
      right_str)
  end if
end if
end subroutine graph_write
recursive subroutine vertex_write (cascade, daughter, mask, reverse)
  type(cascade_t), intent(in) :: cascade, daughter
  integer(TC), intent(in) :: mask
  logical, intent(in), optional :: reverse
  integer :: bincode
  if (cascade%complete) then
    bincode = 0
  else
    bincode = cascade%bincode
  end if
  call graph_write (daughter, mask, reverse)
  if (daughter%has_children) then
    call line_write (bincode, daughter%bincode, daughter%flv, &
      mapping=daughter%mapping)
  else
    call line_write (bincode, daughter%bincode, daughter%flv)
  end if
end subroutine vertex_write
subroutine line_write (i1, i2, flv, mapping)
  integer(TC), intent(in) :: i1, i2
  type(flavor_t), intent(in) :: flv
  integer, intent(in), optional :: mapping
  integer :: k1, k2
  type(string_t) :: prt_type
  select case (flv%get_spin_type ())
  case (SCALAR);      prt_type = "plain"
  case (SPINOR);      prt_type = "fermion"
  case (VECTOR);      prt_type = "boson"
  case (VECTORSPINOR); prt_type = "fermion"
  case (TENSOR);      prt_type = "dbl_wiggly"
  case default;       prt_type = "dashes"

```

```

end select
if (flv%is_antiparticle ()) then
    k1 = i2; k2 = i1
else
    k1 = i1; k2 = i2
end if
if (present (mapping)) then
    select case (mapping)
    case (S_CHANNEL)
        write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
            & ",f=blue,lab=\sm\blue$" // &
            & char (flv%get_tex_name ()) // "$}" // &
            & "{v", k1, ",v", k2, "}"
    case (T_CHANNEL, U_CHANNEL)
        write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
            & ",f=cyan,lab=\sm\cyan$" // &
            & char (flv%get_tex_name ()) // "$}" // &
            & "{v", k1, ",v", k2, "}"
    case (RADIATION)
        write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
            & ",f=green,lab=\sm\green$" // &
            & char (flv%get_tex_name ()) // "$}" // &
            & "{v", k1, ",v", k2, "}"
    case (COLLINEAR)
        write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
            & ",f=magenta,lab=\sm\magenta$" // &
            & char (flv%get_tex_name ()) // "$}" // &
            & "{v", k1, ",v", k2, "}"
    case (INFRARED)
        write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
            & ",f=red,lab=\sm\red$" // &
            & char (flv%get_tex_name ()) // "$}" // &
            & "{v", k1, ",v", k2, "}"
    case default
        write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
            & ",f=black}" // &
            & "{v", k1, ",v", k2, "}"
    end select
else
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
        & "}" // &
        & "{v", k1, ",v", k2, "}"
end if
end subroutine line_write
subroutine external_write (bincode, name, ext_str)
    integer(TC), intent(in) :: bincode
    type(string_t), intent(in) :: name
    type(string_t), intent(inout) :: ext_str
    character(len=20) :: str
    write (str, '(A2,I0)') ",v", bincode
    ext_str = ext_str // trim (str)
    write (u, '(A,I0,A,I0,A)') "\fmflabel{\sm$" &
        // char (name) &
        // "\,(" , bincode, ")" &

```

```

        // "${v", bincode, "}"
    end subroutine external_write
end subroutine cascade_write_graph_format

```

This is for screen/debugging output:

(*Cascades: procedures*)+=

```

subroutine cascade_write (cascade, unit)
    type(cascade_t), intent(in) :: cascade
    integer, intent(in), optional :: unit
    integer :: u
    character(9) :: depth
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A,(1x,I7))") 'Cascade #', cascade%index
    write (u, "(A,(1x,I7))") ' Grove:      #', cascade%grove
    write (u, "(A,3(1x,L1))") ' act/cmp/inc: ', &
        cascade%active, cascade%complete, cascade%incoming
    write (u, "(A,I0)") ' Brcode:      ', cascade%bincode
    write (u, "(A)", advance="no") ' Flavor:      '
    call cascade%flv%write (unit)
    write (u, "(A,I9)") ' Active flavor:', cascade%pdg
    write (u, "(A,L1)") ' Is vector:    ', cascade%is_vector
    write (u, "(A,3(1x," // FMT_19 // ")") ' Mass (m/r/e): ', &
        cascade%m_min, cascade%m_rea, cascade%m_eff
    write (u, "(A,I1)") ' Mapping:      ', cascade%mapping
    write (u, "(A,3(1x,L1))") ' res/log/tch: ', &
        cascade%resonant, cascade%log_enhanced, cascade%t_channel
    write (u, "(A,(1x,I7))") ' Multiplicity: ', cascade%multiplicity
    write (u, "(A,2(1x,I7))") ' n intern/off: ', &
        cascade%internal, cascade%n_off_shell
    write (u, "(A,3(1x,I7))") ' n res/log/tch:', &
        cascade%n_resonances, cascade%n_log_enhanced, cascade%n_t_channel
    write (u, "(A,I7)") ' Depth:      ', cascade%depth
    write (depth, "(I7)") cascade%depth
    write (u, "(A," // depth // "(1x,I7))") &
        ' Tree:      ', cascade%tree
    write (u, "(A," // depth // "(1x,I7))") &
        ' Tree(PDG):  ', cascade%tree_pdg
    write (u, "(A," // depth // "(1x,I7))") &
        ' Tree(mapping):', cascade%tree_mapping
    write (u, "(A," // depth // "(1x,L1))") &
        ' Tree(res):   ', cascade%tree_resonant
    if (cascade%has_children) then
        write (u, "(A,I7,1x,I7)") ' Daughter1/2: ', &
            cascade%daughter1%index, cascade%daughter2%index
    end if
    if (associated (cascade%mother)) then
        write (u, "(A,I7)") ' Mother:      ', cascade%mother%index
    end if
end subroutine cascade_write

```

18.6.3 Creating new cascades

This initializes a single-particle cascade (external, final state). The PDG entry in the tree is set undefined because the cascade is not resonant. However, the flavor entry is set, so the cascade flavor is identified nevertheless.

```
(Cascades: procedures)+≡  
  subroutine cascade_init_outgoing (cascade, flv, pos, m_thr)  
    type(cascade_t), intent(out) :: cascade  
    type(flavor_t), intent(in) :: flv  
    integer, intent(in) :: pos  
    real(default), intent(in) :: m_thr  
    call cascade_init (cascade, 1)  
    cascade%bincode = ibset (0_TC, pos-1)  
    cascade%flv = flv  
    cascade%pdg = abs (cascade%flv%get_pdg ())  
    cascade%is_vector = flv%get_spin_type () == VECTOR  
    cascade%m_min = flv%get_mass ()  
    cascade%m_rea = cascade%m_min  
    if (cascade%m_rea >= m_thr) then  
      cascade%m_eff = cascade%m_rea  
    end if  
    cascade%on_shell = .true.  
    cascade%multiplicity = 1  
    cascade%tree(1) = cascade%bincode  
    cascade%tree_pdg(1) = cascade%pdg  
    cascade%tree_mapping(1) = EXTERNAL_PRT  
    cascade%tree_resonant(1) = .false.  
  end subroutine cascade_init_outgoing
```

The same for an incoming line:

```
(Cascades: procedures)+≡  
  subroutine cascade_init_incoming (cascade, flv, pos, m_thr)  
    type(cascade_t), intent(out) :: cascade  
    type(flavor_t), intent(in) :: flv  
    integer, intent(in) :: pos  
    real(default), intent(in) :: m_thr  
    call cascade_init (cascade, 1)  
    cascade%incoming = .true.  
    cascade%bincode = ibset (0_TC, pos-1)  
    cascade%flv = flv%anti ()  
    cascade%pdg = abs (flv%get_pdg ())  
    cascade%is_vector = flv%get_spin_type () == VECTOR  
    cascade%m_min = flv%get_mass ()  
    cascade%m_rea = cascade%m_min  
    if (cascade%m_rea >= m_thr) then  
      cascade%m_eff = cascade%m_rea  
    end if  
    cascade%on_shell = .true.  
    cascade%n_t_channel = 0  
    cascade%n_off_shell = 0  
    cascade%tree(1) = cascade%bincode  
    cascade%tree_pdg(1) = cascade%pdg  
    cascade%tree_mapping(1) = EXTERNAL_PRT
```

```

        cascade%tree_resonant(1) = .false.
    end subroutine cascade_init_incoming

```

18.6.4 Tools

This function returns true if the two cascades share no common external particle. This is a requirement for joining them.

```

<Cascades: interfaces>≡
    interface operator(.disjunct.)
        module procedure cascade_disjunct
    end interface

<Cascades: procedures>+=
    function cascade_disjunct (cascade1, cascade2) result (flag)
        logical :: flag
        type(cascade_t), intent(in) :: cascade1, cascade2
        flag = iand (cascade1%bincode, cascade2%bincode) == 0
    end function cascade_disjunct

```

Compute a hash code for the resonance pattern of a cascade. We count the number of times each particle appears as a resonance.

We pack the PDG codes of the resonances in two arrays (s-channel and t-channel), sort them both, concatenate the results, transfer to i8 integers, and compute the hash code from this byte stream.

```

<Cascades: procedures>+=
    subroutine cascade_assign_resonance_hash (cascade)
        type(cascade_t), intent(inout) :: cascade
        integer(i8), dimension(1) :: mold
        cascade%res_hash = hash (transfer &
            (concat (sort (pack (cascade%tree_pdg, &
                cascade%tree_resonant))), &
                sort (pack (cascade%tree_pdg, &
                    cascade%tree_mapping == T_CHANNEL .or. &
                    cascade%tree_mapping == U_CHANNEL))), &
            mold))
    end subroutine cascade_assign_resonance_hash

```

18.6.5 Hash entries for cascades

We will set up a hash array which contains keys of and pointers to cascades. We hold a list of cascade (pointers) within each bucket. This is not for collision resolution, but for keeping similar, but unequal cascades together.

```

<Cascades: types>+=
    type :: cascade_p
        type(cascade_t), pointer :: cascade => null ()
        type(cascade_p), pointer :: next => null ()
    end type cascade_p

```


Here is the bucket or hash entry type:

```
(Cascades: types)+≡
type :: hash_entry_t
integer(i32) :: hashval = 0
integer(i8), dimension(:), allocatable :: key
type(cascade_p), pointer :: first => null ()
type(cascade_p), pointer :: last => null ()
end type hash_entry_t
```

Finalize: just deallocate the list; the contents are just pointers.

```
(Cascades: procedures)+≡
subroutine hash_entry_final (hash_entry)
type(hash_entry_t), intent(inout) :: hash_entry
type(cascade_p), pointer :: current
do while (associated (hash_entry%first))
current => hash_entry%first
hash_entry%first => current%next
deallocate (current)
end do
end subroutine hash_entry_final
```

Output: concise format for debugging, just list cascade indices.

```
(Cascades: procedures)+≡
subroutine hash_entry_write (hash_entry, unit)
type(hash_entry_t), intent(in) :: hash_entry
integer, intent(in), optional :: unit
type(cascade_p), pointer :: current
integer :: u, i
u = given_output_unit (unit); if (u < 0) return
write (u, "(1x,A)", advance="no") "Entry:"
do i = 1, size (hash_entry%key)
write (u, "(1x,I0)", advance="no") hash_entry%key(i)
end do
write (u, "(1x,A)", advance="no") "->"
current => hash_entry%first
do while (associated (current))
write (u, "(1x,I7)", advance="no") current%cascade%index
current => current%next
end do
write (u, *)
end subroutine hash_entry_write
```

This function adds a cascade pointer to the bucket. If ok is present, check first if it is already there and return failure if yes. If cascade_ptr is also present, set it to the current cascade if successful. If not, set it to the cascade that is already there.

```
(Cascades: procedures)+≡
subroutine hash_entry_add_cascade_ptr (hash_entry, cascade, ok, cascade_ptr)
type(hash_entry_t), intent(inout) :: hash_entry
type(cascade_t), intent(in), target :: cascade
logical, intent(out), optional :: ok
type(cascade_t), optional, pointer :: cascade_ptr
```

```

type(cascade_p), pointer :: current
if (present (ok)) then
  call hash_entry_check_cascade (hash_entry, cascade, ok, cascade_ptr)
  if (.not. ok) return
end if
allocate (current)
current%cascade => cascade
if (associated (hash_entry%last)) then
  hash_entry%last%next => current
else
  hash_entry%first => current
end if
hash_entry%last => current
end subroutine hash_entry_add_cascade_ptr

```

This function checks whether a cascade is already in the bucket. For incomplete cascades, we look for an exact match. It should suffice to verify the tree, the PDG codes, and the mapping modes. This is the information that is written to the phase space file.

For complete cascades, we ignore the PDG code at positions with mappings infrared, collinear, or t/u-channel. Thus a cascade which is distinguished only by PDG code at such places, is flagged existent. If the convention is followed that light particles come before heavier ones (in the model definition), this ensures that the lightest particle is kept in the appropriate place, corresponding to the strongest peak.

For external cascades (incoming/outgoing) we take the PDG code into account even though it is zeroed in the PDG-code tree.

(Cascades: procedures)+≡

```

subroutine hash_entry_check_cascade (hash_entry, cascade, ok, cascade_ptr)
type(hash_entry_t), intent(in), target :: hash_entry
type(cascade_t), intent(in), target :: cascade
logical, intent(out) :: ok
type(cascade_t), optional, pointer :: cascade_ptr
type(cascade_p), pointer :: current
integer, dimension(:), allocatable :: tree_pdg
ok = .true.
allocate (tree_pdg (size (cascade%tree_pdg)))
if (cascade%complete) then
  where (cascade%tree_mapping == INFRARED .or. &
        cascade%tree_mapping == COLLINEAR .or. &
        cascade%tree_mapping == T_CHANNEL .or. &
        cascade%tree_mapping == U_CHANNEL)
    tree_pdg = 0
  elsewhere
    tree_pdg = cascade%tree_pdg
  end where
else
  tree_pdg = cascade%tree_pdg
end if
current => hash_entry%first
do while (associated (current))
  if (current%cascade%depth == cascade%depth) then
    if (all (current%cascade%tree == cascade%tree)) then

```

```

        if (all (current%cascade%tree_mapping == cascade%tree_mapping)) &
            then
                if (all (current%cascade%tree_pdg .match. tree_pdg)) then
                    if (present (cascade_ptr)) cascade_ptr => current%cascade
                    ok = .false.; return
                end if
            end if
        end if
    end if
    current => current%next
end do
if (present (cascade_ptr)) cascade_ptr => cascade
end subroutine hash_entry_check_cascade

```

For PDG codes, we specify that the undefined code matches any code. This is already defined for flavor objects, but here we need it for the codes themselves.

```

<Cascades: interfaces>+≡
    interface operator(.match.)
        module procedure pdg_match
    end interface

<Cascades: procedures>+≡
    elemental function pdg_match (pdg1, pdg2) result (flag)
        logical :: flag
        integer(TC), intent(in) :: pdg1, pdg2
        select case (pdg1)
        case (0)
            flag = .true.
        case default
            select case (pdg2)
            case (0)
                flag = .true.
            case default
                flag = pdg1 == pdg2
            end select
        end select
    end function pdg_match

```

18.6.6 The cascade set

The cascade set will later be transformed into the decay forest. It is set up as a linked list. In addition to the usual **first** and **last** pointers, there is a **first_t** pointer which points to the first t-channel cascade (after all s-channel cascades), and a **first_k** pointer which points to the first final cascade (with a keystone).

As an auxiliary device, the object contains a hash array with associated parameters where an additional pointer is stored for each cascade. The keys are made from the relevant cascade data. This hash is used for fast detection (and thus avoidance) of double entries in the cascade list.

```

<Cascades: public>≡
    public :: cascade_set_t

```

```

<Cascades: types>+≡
type :: cascade_set_t
private
class(model_data_t), pointer :: model
integer :: n_in, n_out, n_tot
type(flavor_t), dimension(:,:), allocatable :: flv
integer :: depth_out, depth_tot
real(default) :: sqrts = 0
real(default) :: m_threshold_s = 0
real(default) :: m_threshold_t = 0
integer :: off_shell = 0
integer :: t_channel = 0
logical :: keep_nonresonant
integer :: n_groves = 0
! The cascade list
type(cascade_t), pointer :: first => null ()
type(cascade_t), pointer :: last => null ()
type(cascade_t), pointer :: first_t => null ()
type(cascade_t), pointer :: first_k => null ()
! The hashtable
integer :: n_entries = 0
real :: fill_ratio = 0
integer :: n_entries_max = 0
integer(i32) :: mask = 0
logical :: fatal_beam_decay = .true.
type(hash_entry_t), dimension(:), allocatable :: entry
end type cascade_set_t

```

Return true if there are cascades which are active and complete, so the phase space file would be nonempty.

```

<Cascades: public>+≡
public :: cascade_set_is_valid

<Cascades: procedures>+≡
function cascade_set_is_valid (cascade_set) result (flag)
logical :: flag
type(cascade_set_t), intent(in) :: cascade_set
type(cascade_t), pointer :: cascade
flag = .false.
cascade => cascade_set%first_k
do while (associated (cascade))
    if (cascade%active .and. cascade%complete) then
        flag = .true.
        return
    end if
    cascade => cascade%next
end do
end function cascade_set_is_valid

```

The initializer sets up the hash table with some initial size guessed by looking at the number of external particles. We choose 256 for 3 external particles and a factor of 4 for each additional particle, limited at $2^{30}=1\text{G}$.

Note: the explicit initialization loop might be avoided (ELEMENTAL), but a bug in nagfor 5.3.2 prevents this.

```

<Cascades: parameters>+≡
    real, parameter, public :: CASCADE_SET_FILL_RATIO = 0.1

<Cascades: procedures>+≡
    subroutine cascade_set_init (cascade_set, model, n_in, n_out, phs_par, &
        fatal_beam_decay, flv)
        type(cascade_set_t), intent(out) :: cascade_set
        class(model_data_t), intent(in), target :: model
        integer, intent(in) :: n_in, n_out
        type(phs_parameters_t), intent(in) :: phs_par
        logical, intent(in) :: fatal_beam_decay
        type(flavor_t), dimension(:,,:), intent(in), optional :: flv
        integer :: size_guess
        integer :: i, j
        cascade_set%model => model
        cascade_set%n_in = n_in
        cascade_set%n_out = n_out
        cascade_set%n_tot = n_in + n_out
        if (present (flv)) then
            allocate (cascade_set%flv (size (flv, 1), size (flv, 2)))
            do i = 1, size (flv, 2)
                do j = 1, size (flv, 1)
                    call cascade_set%flv(j,i)%init (flv(j,i)%get_pdg (), model)
                end do
            end do
        end if
        select case (n_in)
        case (1); cascade_set%depth_out = 2 * n_out - 3
        case (2); cascade_set%depth_out = 2 * n_out - 1
        end select
        cascade_set%depth_tot = 2 * cascade_set%n_tot - 3
        cascade_set%sqrts = phs_par%sqrts
        cascade_set%m_threshold_s = phs_par%m_threshold_s
        cascade_set%m_threshold_t = phs_par%m_threshold_t
        cascade_set%off_shell = phs_par%off_shell
        cascade_set%t_channel = phs_par%t_channel
        cascade_set%keep_nonresonant = phs_par%keep_nonresonant
        cascade_set%fill_ratio = CASCADE_SET_FILL_RATIO
        size_guess = ishft (256, min (2 * (cascade_set%n_tot - 3), 22))
        cascade_set%n_entries_max = size_guess * cascade_set%fill_ratio
        cascade_set%mask = size_guess - 1
        allocate (cascade_set%entry (0:cascade_set%mask))
        cascade_set%fatal_beam_decay = fatal_beam_decay
    end subroutine cascade_set_init

```

The finalizer has to delete both the hash and the list.

```

<Cascades: public>+≡
    public :: cascade_set_final

<Cascades: procedures>+≡
    subroutine cascade_set_final (cascade_set)
        type(cascade_set_t), intent(inout), target :: cascade_set

```

```

type(cascade_t), pointer :: current
integer :: i
if (allocated (cascade_set%entry)) then
    do i = 0, cascade_set%mask
        call hash_entry_final (cascade_set%entry(i))
    end do
    deallocate (cascade_set%entry)
end if
do while (associated (cascade_set%first))
    current => cascade_set%first
    cascade_set%first => cascade_set%first%next
    deallocate (current)
end do
end subroutine cascade_set_final

```

Write the process in ASCII format, in columns that are headed by the corresponding bincode.

```

<Cascades: public>+=
    public :: cascade_set_write_process_bincode_format

<Cascades: procedures>+=
    subroutine cascade_set_write_process_bincode_format (cascade_set, unit)
        type(cascade_set_t), intent(in), target :: cascade_set
        integer, intent(in), optional :: unit
        integer, dimension(:), allocatable :: bincode, field_width
        integer :: n_in, n_out, n_tot, n_flv
        integer :: u, f, i, bc
        character(20) :: str
        type(string_t) :: fmt_head
        type(string_t), dimension(:), allocatable :: fmt_proc
        u = given_output_unit (unit); if (u < 0) return
        if (.not. allocated (cascade_set%flv)) return
        write (u, "('!',1x,A)") "List of subprocesses with particle bincodes:"
        n_in = cascade_set%n_in
        n_out = cascade_set%n_out
        n_tot = cascade_set%n_tot
        n_flv = size (cascade_set%flv, 2)
        allocate (bincode (n_tot), field_width (n_tot), fmt_proc (n_tot))
        bc = 1
        do i = 1, n_out
            bincode(n_in + i) = bc
            bc = 2 * bc
        end do
        do i = n_in, 1, -1
            bincode(i) = bc
            bc = 2 * bc
        end do
        do i = 1, n_tot
            write (str, "(I0)") bincode(i)
            field_width(i) = len_trim (str)
            do f = 1, n_flv
                field_width(i) = max (field_width(i), &
                    len (cascade_set%flv(i,f)%get_name ()))
            end do

```

```

end do
fmt_head = "('!''"
do i = 1, n_tot
    fmt_head = fmt_head // ",1x,"
    fmt_proc(i) = "(1x,"
    write (str, "(I0)") field_width(i)
    fmt_head = fmt_head // "I" // trim(str)
    fmt_proc(i) = fmt_proc(i) // "A" // trim(str)
    if (i == n_in) then
        fmt_head = fmt_head // ",1x,' '"
    end if
end do
fmt_proc = fmt_proc // ")"
fmt_head = fmt_head // ")"
write (u, char (fmt_head)) bincode
do f = 1, n_flv
    write (u, "('!''", advance="no")
    do i = 1, n_tot
        write (u, char (fmt_proc(i)), advance="no") &
            char (cascade_set%flv(i,f)%get_name ())
        if (i == n_in) write (u, "(1x,'=>')", advance="no")
    end do
    write (u, *)
end do
write (u, char (fmt_head)) bincode
end subroutine cascade_set_write_process_bincode_format

```

Write the process as a L^AT_EX expression.

$\langle \text{Cascades: procedures} \rangle + \equiv$

```

subroutine cascade_set_write_process_tex_format (cascade_set, unit)
    type(cascade_set_t), intent(in), target :: cascade_set
    integer, intent(in), optional :: unit
    integer :: u, f, i
    u = given_output_unit (unit); if (u < 0) return
    if (.not. allocated (cascade_set%flv)) return
    write (u, "(A)") "\begin{align*}"
    do f = 1, size (cascade_set%flv, 2)
        do i = 1, cascade_set%n_in
            if (i > 1) write (u, "(A)", advance="no") "\quad "
            write (u, "(A)", advance="no") &
                char (cascade_set%flv(i,f)%get_tex_name ())
        end do
        write (u, "(A)", advance="no") "\quad &\to\quad "
        do i = cascade_set%n_in + 1, cascade_set%n_tot
            if (i > cascade_set%n_in + 1) write (u, "(A)", advance="no") "\quad "
            write (u, "(A)", advance="no") &
                char (cascade_set%flv(i,f)%get_tex_name ())
        end do
        if (f < size (cascade_set%flv, 2)) then
            write (u, "(A)") "\\ "
        else
            write (u, "(A)") ""
        end if
    end do
end subroutine

```

```

end do
write (u, "(A)") "\end{align*}"
end subroutine cascade_set_write_process_tex_format

```

Three output routines: phase-space file, graph source code, and screen output.

This version generates the phase space file. It deals only with complete cascades.

```

<Cascades: public>+=
public :: cascade_set_write_file_format

<Cascades: procedures>+=
subroutine cascade_set_write_file_format (cascade_set, unit)
type(cascade_set_t), intent(in), target :: cascade_set
integer, intent(in), optional :: unit
type(cascade_t), pointer :: cascade
integer :: u, grove, count
logical :: first_in_grove
u = given_output_unit (unit); if (u < 0) return
count = 0
do grove = 1, cascade_set%n_groves
first_in_grove = .true.
cascade => cascade_set%first_k
do while (associated (cascade))
if (cascade%active .and. cascade%complete) then
if (cascade%grove == grove) then
if (first_in_grove) then
first_in_grove = .false.
write (u, *)
write (u, "(1x,'!',1x,A,1x,I0,A)", advance='no') &
'Multiplicity =', cascade%multiplicity, ","
select case (cascade%n_resonances)
case (0)
write (u, '(1x,A)', advance='no') 'no resonances, '
case (1)
write (u, '(1x,A)', advance='no') '1 resonance, '
case default
write (u, '(1x,I0,1x,A)', advance='no') &
cascade%n_resonances, 'resonances, '
end select
write (u, '(1x,I0,1x,A)', advance='no') &
cascade%n_log_enhanced, 'logs, '
write (u, '(1x,I0,1x,A)', advance='no') &
cascade%n_off_shell, 'off-shell, '
select case (cascade%n_t_channel)
case (0); write (u, '(1x,A)') 's-channel graph'
case (1); write (u, '(1x,A)') '1 t-channel line'
case default
write(u,'(1x,I0,1x,A)') &
cascade%n_t_channel, 't-channel lines'
end select
write (u, '(1x,A,I0)') 'grove #', grove
end if
count = count + 1
write (u, "(1x,'!',1x,A,I0)") "Channel #", count

```



```

        call cascade_write_file_format (cascade, cascade_set%model, u)
    end if
end if
cascade => cascade%next
end do
end do
end subroutine cascade_set_write_file_format

```

This is the graph output format, the driver-file

```

<Cascades: public>+=
    public :: cascade_set_write_graph_format

<Cascades: procedures>+=
    subroutine cascade_set_write_graph_format &
        (cascade_set, filename, process_id, unit)
        type(cascade_set_t), intent(in), target :: cascade_set
        type(string_t), intent(in) :: filename, process_id
        integer, intent(in), optional :: unit
        type(cascade_t), pointer :: cascade
        integer :: u, grove, count, pgcount
        logical :: first_in_grove
        u = given_output_unit (unit); if (u < 0) return
        write (u, '(A)') "\documentclass[10pt]{article}"
        write (u, '(A)') "\usepackage{amsmath}"
        write (u, '(A)') "\usepackage{feynmp}"
        write (u, '(A)') "\usepackage{url}"
        write (u, '(A)') "\usepackage{color}"
        write (u, *)
        write (u, '(A)') "\textwidth 18.5cm"
        write (u, '(A)') "\evensidemargin -1.5cm"
        write (u, '(A)') "\oddsidemargin -1.5cm"
        write (u, *)
        write (u, '(A)') "\newcommand{\blue}{\color{blue}}"
        write (u, '(A)') "\newcommand{\green}{\color{green}}"
        write (u, '(A)') "\newcommand{\red}{\color{red}}"
        write (u, '(A)') "\newcommand{\magenta}{\color{magenta}}"
        write (u, '(A)') "\newcommand{\cyan}{\color{cyan}}"
        write (u, '(A)') "\newcommand{\sm}{\footnotesize}"
        write (u, '(A)') "\setlength{\parindent}{0pt}"
        write (u, '(A)') "\setlength{\parsep}{20pt}"
        write (u, *)
        write (u, '(A)') "\begin{document}"
        write (u, '(A)') "\begin{fmffile}{ // char (filename) // }"
        write (u, '(A)') "\fmfcmd{color magenta; magenta = red + blue;}"
        write (u, '(A)') "\fmfcmd{color cyan; cyan = green + blue;}"
        write (u, '(A)') "\begin{fmfshrink}{0.5}"
        write (u, '(A)') "\begin{flushleft}"
        write (u, *)
        write (u, '(A)') "\noindent" // &
            & "\textbf{\large\texttt{WHIZARD} phase space channels}" // &
            & "\hfill\today"
        write (u, *)
        write (u, '(A)') "\vspace{10pt}"
        write (u, '(A)') "\noindent" // &

```

```

& "\textbf{Process:} \url{" // char (process_id) // "}"
call cascade_set_write_process_tex_format (cascade_set, u)
write (u, *)
write (u, '(A)') "\noindent" // &
& "\textbf{Note:} These are pseudo Feynman graphs that "
write (u, '(A)') "visualize phase-space parameterizations " // &
& "(‘integration channels’). "
write (u, '(A)') "They do \emph{not} indicate Feynman graphs used for the " // &
& "matrix element."
write (u, *)
write (u, '(A)') "\textbf{Color code:} " // &
& "{\blue resonance,} " // &
& "{\cyan t-channel,} " // &
& "{\green radiation,} "
write (u, '(A)') "{\red infrared,} " // &
& "{\magenta collinear,} " // &
& "external/off-shell"
write (u, *)
write (u, '(A)') "\noindent" // &
& "\textbf{Black square:} Keystone, indicates ordering of " // &
& "phase space parameters."
write (u, *)
write (u, '(A)') "\vspace{-20pt}"
count = 0
pgcount = 0
do grove = 1, cascade_set%n_groves
  first_in_grove = .true.
  cascade => cascade_set%first
  do while (associated (cascade))
    if (cascade%active .and. cascade%complete) then
      if (cascade%grove == grove) then
        if (first_in_grove) then
          first_in_grove = .false.
          write (u, *)
          write (u, '(A)') "\vspace{20pt}"
          write (u, '(A)') "\begin{tabular}{l}"
          write (u, '(A,I5,A)') &
            & "\fbox{\bf Grove \boldmath$, grove, "$} \\\[10pt]"
          write (u, '(A,I1,A)') "Multiplicity: ", &
            cascade%multiplicity, "\\"
          write (u, '(A,I1,A)') "Resonances: ", &
            cascade%n_resonances, "\\"
          write (u, '(A,I1,A)') "Log-enhanced: ", &
            cascade%n_log_enhanced, "\\"
          write (u, '(A,I1,A)') "Off-shell: ", &
            cascade%n_off_shell, "\\"
          write (u, '(A,I1,A)') "t-channel: ", &
            cascade%n_t_channel, ""
          write (u, '(A)') "\end{tabular}"
        end if
        count = count + 1
        call cascade_write_graph_format (cascade, count, unit)
        if (pgcount >= 250) then
          write (u, '(A)') "\clearpage"

```

```

        pgcount = 0
    end if
end if
end if
    cascade => cascade%next
end do
end do
write (u, '(A)') "\end{flushleft}"
write (u, '(A)') "\end{fmfshrink}"
write (u, '(A)') "\end{fmffile}"
write (u, '(A)') "\end{document}"
end subroutine cascade_set_write_graph_format

```

This is for screen output and debugging:

```

<Cascades: public>+=
    public :: cascade_set_write

<Cascades: procedures>+=
    subroutine cascade_set_write (cascade_set, unit, active_only, complete_only)
        type(cascade_set_t), intent(in), target :: cascade_set
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: active_only, complete_only
        logical :: active, complete
        type(cascade_t), pointer :: cascade
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        active = .true.; if (present (active_only)) active = active_only
        complete = .false.; if (present (complete_only)) complete = complete_only
        write (u, "(A)") "Cascade set:"
        write (u, "(3x,A)", advance="no") "Model:"
        if (associated (cascade_set%model)) then
            write (u, "(1x,A)") char (cascade_set%model%get_name ())
        else
            write (u, "(1x,A)") "[none]"
        end if
        write (u, "(3x,A)", advance="no") "n_in/out/tot ="
        write (u, "(3(1x,I7))" &
            cascade_set%n_in, cascade_set%n_out, cascade_set%n_tot
        write (u, "(3x,A)", advance="no") "depth_out/tot ="
        write (u, "(2(1x,I7))" cascade_set%depth_out, cascade_set%depth_tot
        write (u, "(3x,A)", advance="no") "mass thr(s/t) ="
        write (u, "(2(1x," // FMT_19 // "))" &
            cascade_set%m_threshold_s, cascade_set%m_threshold_t
        write (u, "(3x,A)", advance="no") "off shell ="
        write (u, "(1x,I7)" cascade_set%off_shell
        write (u, "(3x,A)", advance="no") "keep_nonreson ="
        write (u, "(1x,L1)" cascade_set%keep_nonresonant
        write (u, "(3x,A)", advance="no") "n_groves ="
        write (u, "(1x,I7)" cascade_set%n_groves
        write (u, "(A)")
        write (u, "(A)") "Cascade list:"
        if (associated (cascade_set%first)) then
            cascade => cascade_set%first
            do while (associated (cascade))

```

```

        if (active .and. .not. cascade%active) cycle
        if (complete .and. .not. cascade%complete) cycle
        call cascade_write (cascade, unit)
        cascade => cascade%next
    end do
else
    write (u, "(A)") "[empty]"
end if
write (u, "(A)") "Hash array"
write (u, "(3x,A)", advance="no") "n_entries      ="
write (u, "(1x,I7)") cascade_set%n_entries
write (u, "(3x,A)", advance="no") "fill_ratio    ="
write (u, "(1x," // FMT_12 // ")") cascade_set%fill_ratio
write (u, "(3x,A)", advance="no") "n_entries_max ="
write (u, "(1x,I7)") cascade_set%n_entries_max
write (u, "(3x,A)", advance="no") "mask          ="
write (u, "(1x,I0)") cascade_set%mask
do i = 0, ubound (cascade_set%entry, 1)
    if (associated (cascade_set%entry(i)%key)) then
        write (u, "(1x,I7)") i
        call hash_entry_write (cascade_set%entry(i), u)
    end if
end do
end subroutine cascade_set_write

```

18.6.7 Adding cascades

Add a deep copy of a cascade to the set. The copy has all content of the original, but the pointers are nullified. We do not care whether insertion was successful or not. The pointer argument, if present, is assigned to the input cascade, or to the hash entry if it is already present.

The procedure is recursive: any daughter or mother entries are also deep-copied and added to the cascade set before the current copy is added.

(Cascades: procedures)+≡

```

recursive subroutine cascade_set_add_copy &
    (cascade_set, cascade_in, cascade_ptr)
type(cascade_set_t), intent(inout), target :: cascade_set
type(cascade_t), intent(in) :: cascade_in
type(cascade_t), optional, pointer :: cascade_ptr
type(cascade_t), pointer :: cascade
logical :: ok
allocate (cascade)
cascade = cascade_in
if (associated (cascade_in%daughter1)) call cascade_set_add_copy &
    (cascade_set, cascade_in%daughter1, cascade%daughter1)
if (associated (cascade_in%daughter2)) call cascade_set_add_copy &
    (cascade_set, cascade_in%daughter2, cascade%daughter2)
if (associated (cascade_in%mother)) call cascade_set_add_copy &
    (cascade_set, cascade_in%mother, cascade%mother)
cascade%next => null ()
call cascade_set_add (cascade_set, cascade, ok, cascade_ptr)
if (.not. ok) deallocate (cascade)

```

```
end subroutine cascade_set_add_copy
```

Add a cascade to the set. This does not deep-copy. We first try to insert it in the hash array. If successful, add it to the list. Failure indicates that it is already present, and we drop it.

The hash key is built solely from the tree array, so neither particle codes nor resonances count, just topology.

Technically, hash and list receive only pointers, so the cascade can be considered as being in either of both. We treat it as part of the list.

(Cascades: procedures)+≡

```
subroutine cascade_set_add (cascade_set, cascade, ok, cascade_ptr)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), intent(in), target :: cascade
  logical, intent(out) :: ok
  type(cascade_t), optional, pointer :: cascade_ptr
  integer(i8), dimension(1) :: mold
  call cascade_set_hash_insert &
    (cascade_set, transfer (cascade%tree, mold), cascade, ok, cascade_ptr)
  if (ok) call cascade_set_list_add (cascade_set, cascade)
end subroutine cascade_set_add
```

Add a new cascade to the list:

(Cascades: procedures)+≡

```
subroutine cascade_set_list_add (cascade_set, cascade)
  type(cascade_set_t), intent(inout) :: cascade_set
  type(cascade_t), intent(in), target :: cascade
  if (associated (cascade_set%last)) then
    cascade_set%last%next => cascade
  else
    cascade_set%first => cascade
  end if
  cascade_set%last => cascade
end subroutine cascade_set_list_add
```

Add a cascade entry to the hash array:

(Cascades: procedures)+≡

```
subroutine cascade_set_hash_insert &
  (cascade_set, key, cascade, ok, cascade_ptr)
  type(cascade_set_t), intent(inout), target :: cascade_set
  integer(i8), dimension(:), intent(in) :: key
  type(cascade_t), intent(in), target :: cascade
  logical, intent(out) :: ok
  type(cascade_t), optional, pointer :: cascade_ptr
  integer(i32) :: h
  if (cascade_set%n_entries >= cascade_set%n_entries_max) &
    call cascade_set_hash_expand (cascade_set)
  h = hash (key)
  call cascade_set_hash_insert_rec &
    (cascade_set, h, h, key, cascade, ok, cascade_ptr)
end subroutine cascade_set_hash_insert
```

Double the hashtable size when necessary:

```

(Cascades: procedures)+=
  subroutine cascade_set_hash_expand (cascade_set)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(hash_entry_t), dimension(:), allocatable, target :: table_tmp
    type(cascade_p), pointer :: current
    integer :: i, s
    allocate (table_tmp (0:cascade_set%mask))
    table_tmp = cascade_set%entry
    deallocate (cascade_set%entry)
    s = 2 * size (table_tmp)
    cascade_set%n_entries = 0
    cascade_set%n_entries_max = s * cascade_set%fill_ratio
    cascade_set%mask = s - 1
    allocate (cascade_set%entry (0:cascade_set%mask))
    do i = 0, ubound (table_tmp, 1)
      current => table_tmp(i)%first
      do while (associated (current))
        call cascade_set_hash_insert_rec &
          (cascade_set, table_tmp(i)%hashval, table_tmp(i)%hashval, &
            table_tmp(i)%key, current%cascade)
        current => current%next
      end do
    end do
  end subroutine cascade_set_hash_expand

```

Insert the cascade at the bucket determined by the hash value. If the bucket is filled, check first for a collision (unequal keys). In that case, choose the following bucket and repeat. Otherwise, add the cascade to the bucket.

If the bucket is empty, record the hash value, allocate and store the key, and then add the cascade to the bucket.

If ok is present, before insertion we check whether the cascade is already stored, and return failure if yes.

```

(Cascades: procedures)+=
  recursive subroutine cascade_set_hash_insert_rec &
    (cascade_set, h, hashval, key, cascade, ok, cascade_ptr)
    type(cascade_set_t), intent(inout) :: cascade_set
    integer(i32), intent(in) :: h, hashval
    integer(i8), dimension(:), intent(in) :: key
    type(cascade_t), intent(in), target :: cascade
    logical, intent(out), optional :: ok
    type(cascade_t), optional, pointer :: cascade_ptr
    integer(i32) :: i
    i = iand (h, cascade_set%mask)
    if (allocated (cascade_set%entry(i)%key)) then
      if (size (cascade_set%entry(i)%key) /= size (key)) then
        call cascade_set_hash_insert_rec &
          (cascade_set, h + 1, hashval, key, cascade, ok, cascade_ptr)
      else if (any (cascade_set%entry(i)%key /= key)) then
        call cascade_set_hash_insert_rec &
          (cascade_set, h + 1, hashval, key, cascade, ok, cascade_ptr)
      else
        call hash_entry_add_cascade_ptr &

```

```

        (cascade_set%entry(i), cascade, ok, cascade_ptr)
    end if
else
    cascade_set%entry(i)%hashval = hashval
    allocate (cascade_set%entry(i)%key (size (key)))
    cascade_set%entry(i)%key = key
    call hash_entry_add_cascade_ptr &
        (cascade_set%entry(i), cascade, ok, cascade_ptr)
    cascade_set%n_entries = cascade_set%n_entries + 1
end if
end subroutine cascade_set_hash_insert_rec

```

18.6.8 External particles

We want to initialize the cascade set with the outgoing particles. In case of multiple processes, initial cascades are prepared for all of them. The hash array check ensures that no particle appears more than once at the same place.

```

<Cascades: interfaces>+≡
interface cascade_set_add_outgoing
    module procedure cascade_set_add_outgoing1
    module procedure cascade_set_add_outgoing2
end interface

<Cascades: procedures>+≡
subroutine cascade_set_add_outgoing2 (cascade_set, flv)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(flavor_t), dimension(:,:), intent(in) :: flv
    integer :: pos, prc, n_out, n_prc
    type(cascade_t), pointer :: cascade
    logical :: ok
    n_out = size (flv, dim=1)
    n_prc = size (flv, dim=2)
    do prc = 1, n_prc
        do pos = 1, n_out
            allocate (cascade)
            call cascade_init_outgoing &
                (cascade, flv(pos,prc), pos, cascade_set%m_threshold_s)
            call cascade_set_add (cascade_set, cascade, ok)
            if (.not. ok) then
                deallocate (cascade)
            end if
        end do
    end do
end subroutine cascade_set_add_outgoing2

subroutine cascade_set_add_outgoing1 (cascade_set, flv)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(flavor_t), dimension(:), intent(in) :: flv
    integer :: pos, n_out
    type(cascade_t), pointer :: cascade
    logical :: ok
    n_out = size (flv, dim=1)

```

```

do pos = 1, n_out
  allocate (cascade)
  call cascade_init_outgoing &
    (cascade, flv(pos), pos, cascade_set%m_threshold_s)
  call cascade_set_add (cascade_set, cascade, ok)
  if (.not. ok) then
    deallocate (cascade)
  end if
end do
end subroutine cascade_set_add_outgoing1

```

The incoming particles are added one at a time. Nevertheless, we may have several processes which are looped over. At the first opportunity, we set the pointer `first_t` in the cascade set which should point to the first t-channel cascade.

Return the indices of the first and last cascade generated.

<Cascades: interfaces>+≡

```

interface cascade_set_add_incoming
  module procedure cascade_set_add_incoming0
  module procedure cascade_set_add_incoming1
end interface

```

<Cascades: procedures>+≡

```

subroutine cascade_set_add_incoming1 (cascade_set, n1, n2, pos, flv)
  type(cascade_set_t), intent(inout), target :: cascade_set
  integer, intent(out) :: n1, n2
  integer, intent(in) :: pos
  type(flavor_t), dimension(:), intent(in) :: flv
  integer :: prc, n_prc
  type(cascade_t), pointer :: cascade
  logical :: ok
  n1 = 0
  n2 = 0
  n_prc = size (flv)
  do prc = 1, n_prc
    allocate (cascade)
    call cascade_init_incoming &
      (cascade, flv(prc), pos, cascade_set%m_threshold_t)
    call cascade_set_add (cascade_set, cascade, ok)
    if (ok) then
      if (n1 == 0) n1 = cascade%index
      n2 = cascade%index
      if (.not. associated (cascade_set%first_t)) then
        cascade_set%first_t => cascade
      end if
    else
      deallocate (cascade)
    end if
  end do
end subroutine cascade_set_add_incoming1

subroutine cascade_set_add_incoming0 (cascade_set, n1, n2, pos, flv)
  type(cascade_set_t), intent(inout), target :: cascade_set

```



```

integer, intent(out) :: n1, n2
integer, intent(in) :: pos
type(flavor_t), intent(in) :: flv
type(cascade_t), pointer :: cascade
logical :: ok
n1 = 0
n2 = 0
allocate (cascade)
call cascade_init_incoming &
    (cascade, flv, pos, cascade_set%m_threshold_t)
call cascade_set_add (cascade_set, cascade, ok)
if (ok) then
    if (n1 == 0) n1 = cascade%index
    n2 = cascade%index
    if (.not. associated (cascade_set%first_t)) then
        cascade_set%first_t => cascade
    end if
else
    deallocate (cascade)
end if
end subroutine cascade_set_add_incoming0

```

18.6.9 Cascade combination I: flavor assignment

We have two disjunct cascades, now use the vertex table to determine the possible flavors of the combination cascade. For each possibility, try to generate a new cascade. The total cascade depth has to be one less than the limit, because this is reached by setting the keystone.

(Cascades: procedures) +=

```

subroutine cascade_match_pair (cascade_set, cascade1, cascade2, s_channel)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    logical, intent(in) :: s_channel
    integer, dimension(:), allocatable :: pdg3
    integer :: i, depth_max
    type(flavor_t) :: flv
    if (s_channel) then
        depth_max = cascade_set%depth_out
    else
        depth_max = cascade_set%depth_tot
    end if
    if (cascade1%depth + cascade2%depth < depth_max) then
        call cascade_set%model%match_vertex ( &
            cascade1%flv%get_pdg (), &
            cascade2%flv%get_pdg (), &
            pdg3)
        do i = 1, size (pdg3)
            call flv%init (pdg3(i), cascade_set%model)
            if (s_channel) then
                call cascade_combine_s (cascade_set, cascade1, cascade2, flv)
            else
                call cascade_combine_t (cascade_set, cascade1, cascade2, flv)
            end if
        end do
    end if
end subroutine cascade_match_pair

```

```

        end if
    end do
    deallocate (pdg3)
end if
end subroutine cascade_match_pair

```

The triplet version takes a third cascade, and we check whether this triplet has a matching vertex in the database. If yes, we make a keystone cascade.

```

(Cascades: procedures)+≡
subroutine cascade_match_triplet &
    (cascade_set, cascade1, cascade2, cascade3, s_channel)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2, cascade3
    logical, intent(in) :: s_channel
    integer :: depth_max
    depth_max = cascade_set%depth_tot
    if (cascade1%depth + cascade2%depth + cascade3%depth == depth_max) then
        if (cascade_set%model%check_vertex ( &
            cascade1%flv%get_pdg (), &
            cascade2%flv%get_pdg (), &
            cascade3%flv%get_pdg ())) then
            call cascade_combine_keystone &
                (cascade_set, cascade1, cascade2, cascade3, s_channel)
        end if
    end if
end subroutine cascade_match_triplet

```

18.6.10 Cascade combination II: kinematics setup and check

Having three matching flavors, we start constructing the combination cascade. We look at the mass hierarchies and determine whether the cascade is to be kept. In passing we set mapping modes, resonance properties and such.

If successful, the cascade is finalized. For a resonant cascade, we prepare in addition a copy without the resonance.

```

(Cascades: procedures)+≡
subroutine cascade_combine_s (cascade_set, cascade1, cascade2, flv)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    type(flavor_t), intent(in) :: flv
    type(cascade_t), pointer :: cascade3, cascade4
    logical :: keep
    keep = .false.
    allocate (cascade3)
    call cascade_init (cascade3, cascade1%depth + cascade2%depth + 1)
    cascade3%bincode = ior (cascade1%bincode, cascade2%bincode)
    cascade3%flv = flv%anti ()
    cascade3%pdg = abs (cascade3%flv%get_pdg ())
    cascade3%is_vector = flv%get_spin_type () == VECTOR
    cascade3%m_min = cascade1%m_min + cascade2%m_min
    cascade3%m_rea = flv%get_mass ()
    if (cascade3%m_rea > cascade_set%m_threshold_s) then

```

```

        cascade3%m_eff = cascade3%m_rea
    end if
    ! Potentially resonant cases [sqrt(s) = m_rea for on-shell decay]
    if (cascade3%m_rea > cascade3%m_min &
        .and. cascade3%m_rea <= cascade_set%sqrts) then
        if (flv%get_width() /= 0) then
            if (cascade1%on_shell .or. cascade2%on_shell) then
                keep = .true.
                cascade3%mapping = S_CHANNEL
                cascade3%resonant = .true.
            end if
        else
            call warn_decay (flv)
        end if
    ! Collinear and IR singular cases
    else if (cascade3%m_rea < cascade_set%sqrts) then
        ! Massless splitting
        if (cascade1%m_eff == 0 .and. cascade2%m_eff == 0 &
            .and. cascade3%depth <= 3) then
            keep = .true.
            cascade3%log_enhanced = .true.
            if (cascade3%is_vector) then
                if (cascade1%is_vector .and. cascade2%is_vector) then
                    cascade3%mapping = COLLINEAR ! three-vector-vertex
                else
                    cascade3%mapping = INFRARED ! vector splitting into matter
                end if
            else
                if (cascade1%is_vector .or. cascade2%is_vector) then
                    cascade3%mapping = COLLINEAR ! vector radiation off matter
                else
                    cascade3%mapping = INFRARED ! scalar radiation/splitting
                end if
            end if
        ! IR radiation off massive particle
        else if (cascade3%m_eff > 0 .and. cascade1%m_eff > 0 &
            .and. cascade2%m_eff == 0 &
            .and. (cascade1%on_shell .or. cascade1%mapping == RADIATION) &
            .and. abs (cascade3%m_eff - cascade1%m_eff) &
                < cascade_set%m_threshold_s) &
            then
                keep = .true.
                cascade3%log_enhanced = .true.
                cascade3%mapping = RADIATION
        else if (cascade3%m_eff > 0 .and. cascade2%m_eff > 0 &
            .and. cascade1%m_eff == 0 &
            .and. (cascade2%on_shell .or. cascade2%mapping == RADIATION) &
            .and. abs (cascade3%m_eff - cascade2%m_eff) &
                < cascade_set%m_threshold_s) &
            then
                keep = .true.
                cascade3%log_enhanced = .true.
                cascade3%mapping = RADIATION
        end if
    end if

```

```

end if
! Non-singular cases, including failed resonances
if (.not. keep) then
  ! Two on-shell particles from a virtual mother
  if (cascade1%on_shell .or. cascade2%on_shell) then
    keep = .true.
    cascade3%m_eff = max (cascade3%m_min, &
                          cascade1%m_eff + cascade2%m_eff)
    if (cascade3%m_eff < cascade_set%m_threshold_s) then
      cascade3%m_eff = 0
    end if
  end if
end if
! Complete and register the cascade (two in case of resonance)
if (keep) then
  cascade3%on_shell = cascade3%resonant .or. cascade3%log_enhanced
  if (cascade3%resonant) then
    cascade3%pdg = abs (cascade3%flv%get_pdg ())
    if (cascade_set%keep_nonresonant) then
      allocate (cascade4)
      cascade4 = cascade3
      cascade4%index = cascade_index ()
      cascade4%pdg = UNDEFINED
      cascade4%mapping = NO_MAPPING
      cascade4%resonant = .false.
      cascade4%on_shell = .false.
    end if
    cascade3%m_min = cascade3%m_rea
    call cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
    if (cascade_set%keep_nonresonant) then
      call cascade_fusion (cascade_set, cascade1, cascade2, cascade4)
    end if
  else
    call cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
  end if
else
  deallocate (cascade3)
end if
contains
subroutine warn_decay (flv)
  type(flavor_t), intent(in) :: flv
  integer :: i
  integer, dimension(MAX_WARN_RESONANCE), save :: warned_code = 0
  LOOP_WARNED: do i = 1, MAX_WARN_RESONANCE
    if (warned_code(i) == 0) then
      warned_code(i) = flv%get_pdg ()
      write (msg_buffer, "(A)") &
        & " Intermediate decay of zero-width particle " &
        & // char (flv%get_name ()) &
        & // " may be possible."
      call msg_warning
      exit LOOP_WARNED
    else if (warned_code(i) == flv%get_pdg ()) then
      exit LOOP_WARNED
    end if
  end do
end subroutine warn_decay

```

```

        end if
    end do LOOP_WARNED
end subroutine warn_decay
end subroutine cascade_combine_s

```

(Cascades: parameters)+≡

```
integer, parameter, public :: MAX_WARN_RESONANCE = 50
```

This is the t-channel version. `cascade1` is t-channel and contains the seed, `cascade2` is s-channel. We check for kinematically allowed beam decay (which is a fatal error), or massless splitting / soft radiation. The cascade is kept in all remaining cases and submitted for registration.

(Cascades: procedures)+≡

```

subroutine cascade_combine_t (cascade_set, cascade1, cascade2, flv)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    type(flavor_t), intent(in) :: flv
    type(cascade_t), pointer :: cascade3
    allocate (cascade3)
    call cascade_init (cascade3, cascade1%depth + cascade2%depth + 1)
    cascade3%bincode = ior (cascade1%bincode, cascade2%bincode)
    cascade3%flv = flv%anti ()
    cascade3%pdg = abs (cascade3%flv%get_pdg ())
    cascade3%is_vector = flv%get_spin_type () == VECTOR
    if (cascade1%incoming) then
        cascade3%m_min = cascade2%m_min
    else
        cascade3%m_min = cascade1%m_min + cascade2%m_min
    end if
    cascade3%m_rea = flv%get_mass ()
    if (cascade3%m_rea > cascade_set%m_threshold_t) then
        cascade3%m_eff = max (cascade3%m_rea, cascade2%m_eff)
    else if (cascade2%m_eff > cascade_set%m_threshold_t) then
        cascade3%m_eff = cascade2%m_eff
    else
        cascade3%m_eff = 0
    end if
    ! Allowed decay of beam particle
    if (cascade1%incoming &
        .and. cascade1%m_rea > cascade2%m_rea + cascade3%m_rea) then
        call beam_decay (cascade_set%fatal_beam_decay)
    ! Massless splitting
    else if (cascade1%m_eff == 0 &
        .and. cascade2%m_eff < cascade_set%m_threshold_t &
        .and. cascade3%m_eff == 0) then
        cascade3%mapping = U_CHANNEL
        cascade3%log_enhanced = .true.
    ! IR radiation off massive particle
    else if (cascade1%m_eff /= 0 .and. cascade2%m_eff == 0 &
        .and. cascade3%m_eff /= 0 &
        .and. (cascade1%on_shell .or. cascade1%mapping == RADIATION) &
        .and. abs (cascade1%m_eff - cascade3%m_eff) &
            < cascade_set%m_threshold_t) &
        then

```

```

        cascade3%pdg = abs (flv%get_pdg ())
        cascade3%log_enhanced = .true.
        cascade3%mapping = RADIATION
    end if
    cascade3%t_channel = .true.
    call cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
contains
    subroutine beam_decay (fatal_beam_decay)
        logical, intent(in) :: fatal_beam_decay
        write (msg_buffer, "(1x,A,1x,'->',1x,A,1x,A)") &
            char (cascade1%flv%get_name ()), &
            char (cascade3%flv%get_name ()), &
            char (cascade2%flv%get_name ())
        call msg_message
        write (msg_buffer, "(1x,'mass(',A,') =' ,1x,E17.10)") &
            char (cascade1%flv%get_name ()), cascade1%m_rea
        call msg_message
        write (msg_buffer, "(1x,'mass(',A,') =' ,1x,E17.10)") &
            char (cascade3%flv%get_name ()), cascade3%m_rea
        call msg_message
        write (msg_buffer, "(1x,'mass(',A,') =' ,1x,E17.10)") &
            char (cascade2%flv%get_name ()), cascade2%m_rea
        call msg_message
        if (fatal_beam_decay) then
            call msg_fatal (" Phase space: Initial beam particle can decay")
        else
            call msg_warning (" Phase space: Initial beam particle can decay")
        end if
    end subroutine beam_decay
end subroutine cascade_combine_t

```

Here we complete a decay cascade. The third input is the single-particle cascade for the initial particle. There is no resonance or mapping assignment. The only condition for keeping the cascade is the mass sum of the final state, which must be less than the available energy.

Two modifications are necessary for scattering cascades: a pure s-channel diagram (cascade1 is the incoming particle) do not have a logarithmic mapping at top-level. And in a t-channel diagram, the last line exchanged is mapped t-channel, not u-channel. Finally, we can encounter the case of a $2 \rightarrow 1$ process, where cascade1 is incoming, and cascade2 is the outgoing particle. In all three cases we register a new cascade with the modified mapping.

(*Cascades: procedures*) $\vdash\equiv$

```

subroutine cascade_combine_keystone &
    (cascade_set, cascade1, cascade2, cascade3, s_channel)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2, cascade3
    logical, intent(in) :: s_channel
    type(cascade_t), pointer :: cascade4, cascade0
    logical :: keep, ok
    keep = .false.
    allocate (cascade4)
    call cascade_init &
        (cascade4, cascade1%depth + cascade2%depth + cascade3%depth)

```

```

cascade4%complete = .true.
if (s_channel) then
    cascade4%bincode = ior (cascade1%bincode, cascade2%bincode)
else
    cascade4%bincode = cascade3%bincode
end if
cascade4%flv = cascade3%flv
cascade4%pdg = cascade3%pdg
cascade4%mapping = EXTERNAL_PRT
cascade4%is_vector = cascade3%is_vector
cascade4%m_min = cascade1%m_min + cascade2%m_min
cascade4%m_rea = cascade3%m_rea
cascade4%m_eff = cascade3%m_rea
if (cascade4%m_min < cascade_set%sqrts) then
    keep = .true.
end if
if (keep) then
    if (cascade1%incoming .and. cascade2%log_enhanced) then
        allocate (cascade0)
        cascade0 = cascade2
        cascade0%next => null ()
        cascade0%index = cascade_index ()
        cascade0%mapping = NO_MAPPING
        cascade0%log_enhanced = .false.
        cascade0%n_log_enhanced = cascade0%n_log_enhanced - 1
        cascade0%tree_mapping(cascade0%depth) = NO_MAPPING
        call cascade_keystone &
            (cascade_set, cascade1, cascade0, cascade3, cascade4, ok)
        if (ok) then
            call cascade_set_add (cascade_set, cascade0, ok)
        else
            deallocate (cascade0)
        end if
    else if (cascade1%t_channel .and. cascade1%mapping == U_CHANNEL) then
        allocate (cascade0)
        cascade0 = cascade1
        cascade0%next => null ()
        cascade0%index = cascade_index ()
        cascade0%mapping = T_CHANNEL
        cascade0%tree_mapping(cascade0%depth) = T_CHANNEL
        call cascade_keystone &
            (cascade_set, cascade0, cascade2, cascade3, cascade4, ok)
        if (ok) then
            call cascade_set_add (cascade_set, cascade0, ok)
        else
            deallocate (cascade0)
        end if
    else if (cascade1%incoming .and. cascade2%depth == 1) then
        allocate (cascade0)
        cascade0 = cascade2
        cascade0%next => null ()
        cascade0%index = cascade_index ()
        cascade0%mapping = ON_SHELL
        cascade0%tree_mapping(cascade0%depth) = ON_SHELL
    end if
end if

```

```

        call cascade_keystone &
            (cascade_set, cascade1, cascade0, cascade3, cascade4, ok)
    if (ok) then
        call cascade_set_add (cascade_set, cascade0, ok)
    else
        deallocate (cascade0)
    end if
else
    call cascade_keystone &
        (cascade_set, cascade1, cascade2, cascade3, cascade4, ok)
end if
else
    deallocate (cascade4)
end if
end subroutine cascade_combine_keystone

```

18.6.11 Cascade combination III: node connections and tree fusion

Here we assign global tree properties. If the allowed number of off-shell lines is exceeded, discard the new cascade. Otherwise, assign the trees, sort them, and assign connections. Finally, append the cascade to the list. This may fail (because in the hash array there is already an equivalent cascade). On failure, discard the cascade.

```

(Cascades: procedures) +=
subroutine cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    type(cascade_t), pointer :: cascade3
    integer :: i1, i2, i3, i4
    logical :: ok
    cascade3%internal = (cascade3%depth - 3) / 2
    if (cascade3%resonant) then
        cascade3%multiplicity = 1
        cascade3%n_resonances = &
            cascade1%n_resonances + cascade2%n_resonances + 1
    else
        cascade3%multiplicity = cascade1%multiplicity + cascade2%multiplicity
        cascade3%n_resonances = cascade1%n_resonances + cascade2%n_resonances
    end if
    if (cascade3%log_enhanced) then
        cascade3%n_log_enhanced = &
            cascade1%n_log_enhanced + cascade2%n_log_enhanced + 1
    else
        cascade3%n_log_enhanced = &
            cascade1%n_log_enhanced + cascade2%n_log_enhanced
    end if
    if (cascade3%resonant) then
        cascade3%n_off_shell = 0
    else if (cascade3%log_enhanced) then
        cascade3%n_off_shell = cascade1%n_off_shell + cascade2%n_off_shell
    else

```



```

        cascade3%n_off_shell = cascade1%n_off_shell + cascade2%n_off_shell + 1
    end if
    if (cascade3%t_channel) then
        cascade3%n_t_channel = cascade1%n_t_channel + 1
    end if
    if (cascade3%n_off_shell > cascade_set%off_shell) then
        deallocate (cascade3)
    else if (cascade3%n_t_channel > cascade_set%t_channel) then
        deallocate (cascade3)
    else
        i1 = cascade1%depth
        i2 = i1 + 1
        i3 = i1 + cascade2%depth
        i4 = cascade3%depth
        cascade3%tree(:i1) = cascade1%tree
        where (cascade1%tree_mapping > NO_MAPPING)
            cascade3%tree_pdg(:i1) = cascade1%tree_pdg
        elsewhere
            cascade3%tree_pdg(:i1) = UNDEFINED
        end where
        cascade3%tree_mapping(:i1) = cascade1%tree_mapping
        cascade3%tree_resonant(:i1) = cascade1%tree_resonant
        cascade3%tree(i2:i3) = cascade2%tree
        where (cascade2%tree_mapping > NO_MAPPING)
            cascade3%tree_pdg(i2:i3) = cascade2%tree_pdg
        elsewhere
            cascade3%tree_pdg(i2:i3) = UNDEFINED
        end where
        cascade3%tree_mapping(i2:i3) = cascade2%tree_mapping
        cascade3%tree_resonant(i2:i3) = cascade2%tree_resonant
        cascade3%tree(i4) = cascade3%bincode
        cascade3%tree_pdg(i4) = cascade3%pdg
        cascade3%tree_mapping(i4) = cascade3%mapping
        cascade3%tree_resonant(i4) = cascade3%resonant
        call tree_sort (cascade3%tree, &
            cascade3%tree_pdg, cascade3%tree_mapping, cascade3%tree_resonant)
        cascade3%has_children = .true.
        cascade3%daughter1 => cascade1
        cascade3%daughter2 => cascade2
        call cascade_set_add (cascade_set, cascade3, ok)
        if (.not. ok) deallocate (cascade3)
    end if
end subroutine cascade_fusion

```

Here we combine a cascade pair with an incoming particle, i.e., we set a keystone. Otherwise, this is similar. On the first opportunity, we set the **first_k** pointer in the cascade set.

(Cascades: procedures) +=

```

subroutine cascade_keystone &
    (cascade_set, cascade1, cascade2, cascade3, cascade4, ok)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2, cascade3
    type(cascade_t), pointer :: cascade4

```

```

logical, intent(out) :: ok
integer :: i1, i2, i3, i4
cascade4%internal = (cascade4%depth - 3) / 2
cascade4%multiplicity = cascade1%multiplicity + cascade2%multiplicity
cascade4%n_resonances = cascade1%n_resonances + cascade2%n_resonances
cascade4%n_off_shell = cascade1%n_off_shell + cascade2%n_off_shell
cascade4%n_log_enhanced = &
    cascade1%n_log_enhanced + cascade2%n_log_enhanced
cascade4%n_t_channel = cascade1%n_t_channel + cascade2%n_t_channel
if (cascade4%n_off_shell > cascade_set%off_shell) then
    deallocate (cascade4)
    ok = .false.
else if (cascade4%n_t_channel > cascade_set%t_channel) then
    deallocate (cascade4)
    ok = .false.
else
    i1 = cascade1%depth
    i2 = i1 + 1
    i3 = i1 + cascade2%depth
    i4 = cascade4%depth
    cascade4%tree(:i1) = cascade1%tree
    where (cascade1%tree_mapping > NO_MAPPING)
        cascade4%tree_pdg(:i1) = cascade1%tree_pdg
    elsewhere
        cascade4%tree_pdg(:i1) = UNDEFINED
    end where
    cascade4%tree_mapping(:i1) = cascade1%tree_mapping
    cascade4%tree_resonant(:i1) = cascade1%tree_resonant
    cascade4%tree(i2:i3) = cascade2%tree
    where (cascade2%tree_mapping > NO_MAPPING)
        cascade4%tree_pdg(i2:i3) = cascade2%tree_pdg
    elsewhere
        cascade4%tree_pdg(i2:i3) = UNDEFINED
    end where
    cascade4%tree_mapping(i2:i3) = cascade2%tree_mapping
    cascade4%tree_resonant(i2:i3) = cascade2%tree_resonant
    cascade4%tree(i4) = cascade4%bincode
    cascade4%tree_pdg(i4) = UNDEFINED
    cascade4%tree_mapping(i4) = cascade4%mapping
    cascade4%tree_resonant(i4) = .false.
    call tree_sort (cascade4%tree, &
        cascade4%tree_pdg, cascade4%tree_mapping, cascade4%tree_resonant)
    cascade4%has_children = .true.
    cascade4%daughter1 => cascade1
    cascade4%daughter2 => cascade2
    cascade4%mother => cascade3
    call cascade_set_add (cascade_set, cascade4, ok)
    if (ok) then
        if (.not. associated (cascade_set%first_k)) then
            cascade_set%first_k => cascade4
        end if
    else
        deallocate (cascade4)
    end if
end if

```

```

    end if
end subroutine cascade_keystone

```

Sort a tree (array of binary codes) and particle code array simultaneously, by ascending binary codes. A convenient method is to use the `maxloc` function iteratively, to find and remove the largest entry in the tree array one by one.

```

<Cascades: procedures>+≡
subroutine tree_sort (tree, pdg, mapping, resonant)
  integer(TC), dimension(:), intent(inout) :: tree
  integer, dimension(:), intent(inout) :: pdg, mapping
  logical, dimension(:), intent(inout) :: resonant
  integer(TC), dimension(size(tree)) :: tree_tmp
  integer, dimension(size(pdg)) :: pdg_tmp, mapping_tmp
  logical, dimension(size(resonant)) :: resonant_tmp
  integer, dimension(1) :: pos
  integer :: i
  tree_tmp = tree
  pdg_tmp = pdg
  mapping_tmp = mapping
  resonant_tmp = resonant
  do i = size(tree), 1, -1
    pos = maxloc (tree_tmp)
    tree(i) = tree_tmp (pos(1))
    pdg(i) = pdg_tmp (pos(1))
    mapping(i) = mapping_tmp (pos(1))
    resonant(i) = resonant_tmp (pos(1))
    tree_tmp(pos(1)) = 0
  end do
end subroutine tree_sort

```

18.6.12 Cascade set generation

These procedures loop over cascades and build up the cascade set. After each iteration of the innermost loop, we set a breakpoint.

s-channel: We use a nested scan to combine all cascades with all other cascades.

```

<Cascades: procedures>+≡
subroutine cascade_set_generate_s (cascade_set)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), pointer :: cascade1, cascade2
  cascade1 => cascade_set%first
  LOOP1: do while (associated (cascade1))
    cascade2 => cascade_set%first
    LOOP2: do while (associated (cascade2))
      if (cascade2%index >= cascade1%index) exit LOOP2
      if (cascade1 .disjunct. cascade2) then
        call cascade_match_pair (cascade_set, cascade1, cascade2, .true.)
      end if
      call terminate_now_if_signal ()
      cascade2 => cascade2%next
    end do LOOP2
  end do LOOP1

```

```

        cascade1 => cascade1%next
    end do LOOP1
end subroutine cascade_set_generate_s

```

The t-channel cascades are directed and have a seed (one of the incoming particles) and a target (the other one). We loop over all possible seeds and targets. Inside this, we loop over all t-channel cascades (*cascade1*) and s-channel cascades (*cascade2*) and try to combine them.

```

(Cascades: procedures)+≡
subroutine cascade_set_generate_t (cascade_set, pos_seed, pos_target)
    type(cascade_set_t), intent(inout), target :: cascade_set
    integer, intent(in) :: pos_seed, pos_target
    type(cascade_t), pointer :: cascade_seed, cascade_target
    type(cascade_t), pointer :: cascade1, cascade2
    integer(TC) :: bc_seed, bc_target
    bc_seed = ibset (0_TC, pos_seed-1)
    bc_target = ibset (0_TC, pos_target-1)
    cascade_seed => cascade_set%first_t
    LOOP_SEED: do while (associated (cascade_seed))
        if (cascade_seed%bincode == bc_seed) then
            cascade_target => cascade_set%first_t
            LOOP_TARGET: do while (associated (cascade_target))
                if (cascade_target%bincode == bc_target) then
                    cascade1 => cascade_set%first_t
                    LOOP_T: do while (associated (cascade1))
                        if ((cascade1 .disjunct. cascade_target) &
                            .and. .not. (cascade1 .disjunct. cascade_seed)) then
                            cascade2 => cascade_set%first
                            LOOP_S: do while (associated (cascade2))
                                if ((cascade2 .disjunct. cascade_target) &
                                    .and. (cascade2 .disjunct. cascade1)) then
                                    call cascade_match_pair &
                                        (cascade_set, cascade1, cascade2, .false.)
                                end if
                                call terminate_now_if_signal ()
                                cascade2 => cascade2%next
                            end do LOOP_S
                        end if
                        call terminate_now_if_signal ()
                        cascade1 => cascade1%next
                    end do LOOP_T
                end if
                call terminate_now_if_signal ()
                cascade_target => cascade_target%next
            end do LOOP_TARGET
        end if
        cascade_seed => cascade_seed%next
    end do LOOP_SEED
end subroutine cascade_set_generate_t

```

This part completes the phase space for decay processes. It is similar to s-channel cascade generation, but combines two cascade with the particular cas-

cade of the incoming particle. This particular cascade is expected to be pointed at by `first_t`.

(Cascades: procedures) +=

```

subroutine cascade_set_generate_decay (cascade_set)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), pointer :: cascade1, cascade2
  type(cascade_t), pointer :: cascade_in
  cascade_in => cascade_set%first_t
  cascade1 => cascade_set%first
  do while (associated (cascade1))
    if (cascade1 .disjunct. cascade_in) then
      cascade2 => cascade1%next
      do while (associated (cascade2))
        if ((cascade2 .disjunct. cascade1) &
            .and. (cascade2 .disjunct. cascade_in)) then
          call cascade_match_triplet (cascade_set, &
                                     cascade1, cascade2, cascade_in, .true.)
        end if
        call terminate_now_if_signal ()
        cascade2 => cascade2%next
      end do
    end if
    call terminate_now_if_signal ()
    cascade1 => cascade1%next
  end do
end subroutine cascade_set_generate_decay

```

This part completes the phase space for scattering processes. We combine a t-channel cascade (containing the seed) with a s-channel cascade and the target.

(Cascades: procedures) +=

```

subroutine cascade_set_generate_scattering &
  (cascade_set, ns1, ns2, nt1, nt2, pos_seed, pos_target)
  type(cascade_set_t), intent(inout), target :: cascade_set
  integer, intent(in) :: pos_seed, pos_target
  integer, intent(in) :: ns1, ns2, nt1, nt2
  type(cascade_t), pointer :: cascade_seed, cascade_target
  type(cascade_t), pointer :: cascade1, cascade2
  integer(TC) :: bc_seed, bc_target
  bc_seed = ibset (0_TC, pos_seed-1)
  bc_target = ibset (0_TC, pos_target-1)
  cascade_seed => cascade_set%first_t
  LOOP_SEED: do while (associated (cascade_seed))
    if (cascade_seed%index < ns1) then
      cascade_seed => cascade_seed%next
      cycle LOOP_SEED
    else if (cascade_seed%index > ns2) then
      exit LOOP_SEED
    else if (cascade_seed%bincode == bc_seed) then
      cascade_target => cascade_set%first_t
      LOOP_TARGET: do while (associated (cascade_target))
        if (cascade_target%index < nt1) then
          cascade_target => cascade_target%next
          cycle LOOP_TARGET
        end if
      end do
    end if
  end do

```

```

else if (cascade_target%index > nt2) then
  exit LOOP_TARGET
else if (cascade_target%bincode == bc_target) then
  cascade1 => cascade_set%first_t
  LOOP_T: do while (associated (cascade1))
    if ((cascade1 .disjunct. cascade_target) &
        .and. .not. (cascade1 .disjunct. cascade_seed)) then
      cascade2 => cascade_set%first
      LOOP_S: do while (associated (cascade2))
        if ((cascade2 .disjunct. cascade_target) &
            .and. (cascade2 .disjunct. cascade1)) then
          call cascade_match_triplet (cascade_set, &
                                     cascade1, cascade2, cascade_target, .false.)
        end if
        call terminate_now_if_signal ()
        cascade2 => cascade2%next
      end do LOOP_S
    end if
    call terminate_now_if_signal ()
    cascade1 => cascade1%next
  end do LOOP_T
end if
call terminate_now_if_signal ()
cascade_target => cascade_target%next
end do LOOP_TARGET
end if
call terminate_now_if_signal ()
cascade_seed => cascade_seed%next
end do LOOP_SEED
end subroutine cascade_set_generate_scattering

```

18.6.13 Groves

Before assigning groves, assign hashcodes to the resonance patterns, so they can easily be compared.

(Cascades: procedures) +=

```

subroutine cascade_set_assign_resonance_hash (cascade_set)
  type(cascade_set_t), intent(inout) :: cascade_set
  type(cascade_t), pointer :: cascade
  cascade => cascade_set%first_k
  do while (associated (cascade))
    call cascade_assign_resonance_hash (cascade)
    cascade => cascade%next
  end do
end subroutine cascade_set_assign_resonance_hash

```

After all cascades are recorded, we group the complete cascades in groves. A grove consists of cascades with identical multiplicity, number of resonances, log-enhanced, t-channel lines, and resonance flavors.

(Cascades: procedures) +=

```

subroutine cascade_set_assign_groves (cascade_set)
  type(cascade_set_t), intent(inout), target :: cascade_set

```

```

type(cascade_t), pointer :: cascade1, cascade2
integer :: multiplicity
integer :: n_resonances, n_log_enhanced, n_t_channel, n_off_shell
integer :: res_hash
integer :: grove
grove = 0
cascade1 => cascade_set%first_k
do while (associated (cascade1))
  if (cascade1%active .and. cascade1%complete &
      .and. cascade1%grove == 0) then
    grove = grove + 1
    cascade1%grove = grove
    multiplicity = cascade1%multiplicity
    n_resonances = cascade1%n_resonances
    n_log_enhanced = cascade1%n_log_enhanced
    n_off_shell = cascade1%n_off_shell
    n_t_channel = cascade1%n_t_channel
    res_hash = cascade1%res_hash
    cascade2 => cascade1%next
    do while (associated (cascade2))
      if (cascade2%grove == 0) then
        if (cascade2%multiplicity == multiplicity &
            .and. cascade2%n_resonances == n_resonances &
            .and. cascade2%n_log_enhanced == n_log_enhanced &
            .and. cascade2%n_off_shell == n_off_shell &
            .and. cascade2%n_t_channel == n_t_channel &
            .and. cascade2%res_hash == res_hash) then
          cascade2%grove = grove
        end if
      end if
      call terminate_now_if_signal ()
      cascade2 => cascade2%next
    end do
  end if
  call terminate_now_if_signal ()
  cascade1 => cascade1%next
end do
cascade_set%n_groves = grove
end subroutine cascade_set_assign_groves

```

18.6.14 Generate the phase space file

Generate a complete phase space configuration.

For each flavor assignment: First, all s-channel graphs that can be built up from the outgoing particles. Then we distinguish (1) decay, where we complete the s-channel graphs by connecting to the input line, and (2) scattering, where we now generate t-channel graphs by introducing an incoming particle, and complete this by connecting to the other incoming particle.

After all cascade sets have been generated, merge them into a common set. This eliminates redundancies between flavor assignments.

```

(Cascades: public) +=
public :: cascade_set_generate

```

<Cascades: procedures>+≡

```

subroutine cascade_set_generate &
    (cascade_set, model, n_in, n_out, flv, phs_par, fatal_beam_decay)
    type(cascade_set_t), intent(out) :: cascade_set
    class(model_data_t), intent(in), target :: model
    integer, intent(in) :: n_in, n_out
    type(flavor_t), dimension(:,:), intent(in) :: flv
    type(phs_parameters_t), intent(in) :: phs_par
    logical, intent(in) :: fatal_beam_decay
    type(cascade_set_t), dimension(:), allocatable :: cset
    type(cascade_t), pointer :: cascade
    integer :: i
    if (phase_space_vanishes (phs_par%sqrts, n_in, flv)) return
    call cascade_set_init (cascade_set, model, n_in, n_out, phs_par, &
        fatal_beam_decay, flv)
    allocate (cset (size (flv, 2)))
    do i = 1, size (cset)
        call cascade_set_generate_single (cset(i), &
            model, n_in, n_out, flv(:,i), phs_par, fatal_beam_decay)
        cascade => cset(i)%first_k
        do while (associated (cascade))
            if (cascade%active .and. cascade%complete) then
                call cascade_set_add_copy (cascade_set, cascade)
            end if
            cascade => cascade%next
        end do
        call cascade_set_final (cset(i))
    end do
    cascade_set%first_k => cascade_set%first
    call cascade_set_assign_resonance_hash (cascade_set)
    call cascade_set_assign_groves (cascade_set)
end subroutine cascade_set_generate

```

This generates phase space for a single channel, without assigning groves.

<Cascades: procedures>+≡

```

subroutine cascade_set_generate_single (cascade_set, &
    model, n_in, n_out, flv, phs_par, fatal_beam_decay)
    type(cascade_set_t), intent(out) :: cascade_set
    class(model_data_t), intent(in), target :: model
    integer, intent(in) :: n_in, n_out
    type(flavor_t), dimension(:), intent(in) :: flv
    type(phs_parameters_t), intent(in) :: phs_par
    logical, intent(in) :: fatal_beam_decay
    integer :: n11, n12, n21, n22
    call cascade_set_init (cascade_set, model, n_in, n_out, phs_par, &
        fatal_beam_decay)
    call cascade_set_add_outgoing (cascade_set, flv(n_in+1:))
    call cascade_set_generate_s (cascade_set)
    select case (n_in)
    case(1)
        call cascade_set_add_incoming &
            (cascade_set, n11, n12, n_out + 1, flv(1))
        call cascade_set_generate_decay (cascade_set)
    end select
end subroutine cascade_set_generate_single

```



```

case(2)
  call cascade_set_add_incoming &
    (cascade_set, n11, n12, n_out + 1, flv(2))
  call cascade_set_add_incoming &
    (cascade_set, n21, n22, n_out + 2, flv(1))
  call cascade_set_generate_t (cascade_set, n_out + 1, n_out + 2)
  call cascade_set_generate_t (cascade_set, n_out + 2, n_out + 1)
  call cascade_set_generate_scattering &
    (cascade_set, n11, n12, n21, n22, n_out + 1, n_out + 2)
  call cascade_set_generate_scattering &
    (cascade_set, n21, n22, n11, n12, n_out + 2, n_out + 1)
end select
end subroutine cascade_set_generate_single

```

Sanity check: Before anything else is done, check if there could possibly be any phase space.

```

<Cascades: procedures>+≡
function phase_space_vanishes (sqrts, n_in, flv) result (flag)
  logical :: flag
  real(default), intent(in) :: sqrts
  integer, intent(in) :: n_in
  type(flavor_t), dimension(:,:), intent(in) :: flv
  real(default), dimension(:,:), allocatable :: mass
  real(default), dimension(:), allocatable :: mass_in, mass_out
  integer :: n_prt, n_flv
  flag = .false.
  if (sqrts <= 0) then
    call msg_error ("Phase space vanishes (sqrts must be positive)")
    flag = .true.; return
  end if
  n_prt = size (flv, 1)
  n_flv = size (flv, 2)
  allocate (mass (n_prt, n_flv), mass_in (n_flv), mass_out (n_flv))
  mass = flv%get_mass ()
  mass_in = sum (mass(:,n_in,:), 1)
  mass_out = sum (mass(n_in+1:,:), 1)
  if (any (mass_in > sqrts)) then
    call msg_error ("Mass sum of incoming particles " &
      // "is more than available energy")
    flag = .true.; return
  end if
  if (any (mass_out > sqrts)) then
    call msg_error ("Mass sum of outgoing particles " &
      // "is more than available energy")
    flag = .true.; return
  end if
end function phase_space_vanishes

```

18.6.15 Unit tests

```

<Cascades: public>+≡
public :: cascade_test

```

```

<Cascades: procedures>+=
  subroutine cascade_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Cascades: execute tests>
  end subroutine cascade_test

```

Checking the basic setup up of the phase space cascade parameterizations.

```

<Cascades: execute tests>=
  call test (cascade_1, "cascade_1", &
    "check cascade setup", &
    u, results)

<Cascades: tests>=
  subroutine cascade_1 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t), dimension(5,2) :: flv
    type(cascade_set_t) :: cascade_set
    type(phs_parameters_t) :: phs_par

    write (u, "(A)")  "* Test output: Cascades"
    write (u, "(A)")  "* Purpose: test cascade phase space functions"
    write (u, "(A)")

    write (u, "(A)")  "* Initializing"
    write (u, "(A)")

    call model%init_sm_test ()

    call flv(1,1)%init ( 2, model)
    call flv(2,1)%init (-2, model)
    call flv(3,1)%init ( 1, model)
    call flv(4,1)%init (-1, model)
    call flv(5,1)%init (21, model)
    call flv(1,2)%init ( 2, model)
    call flv(2,2)%init (-2, model)
    call flv(3,2)%init ( 2, model)
    call flv(4,2)%init (-2, model)
    call flv(5,2)%init (21, model)
    phs_par%sqrts = 1000._default
    phs_par%off_shell = 2

    write (u, "(A)")
    write (u, "(A)")  "* Generating the cascades"
    write (u, "(A)")

    call cascade_set_generate (cascade_set, model, 2, 3, flv, phs_par,.true.)
    call cascade_set_write (cascade_set, u)
    call cascade_set_write_file_format (cascade_set, u)

    write (u, "(A)")  "* Cleanup"
    write (u, "(A)")

```

```

call cascade_set_final (cascade_set)
call model%final ()

write (u, *)
write (u, "(A)")  "** Test output end: cascade_1"

end subroutine cascade_1

```

18.7 WOOD phase space

This is the module that interfaces the `phs_forests` phase-space treatment and the `cascades` module for generating phase-space channels. As an extension of the `phs_base` abstract type, the phase-space configuration and instance implement the standard API.

(Currently, this is the only generic phase-space implementation of WHIZARD. For trivial two-particle phase space, there is `phs_wood` as an alternative.)

```

⟨phs_wood.f90⟩≡
  ⟨File header⟩

  module phs_wood

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use io_units
    use constants
    use unit_tests
    use diagnostics
    use os_interface
    use md5
    use physics_defs
    use lorentz
    use model_data
    use flavors
    use process_constants
    use sf_mappings
    use sf_base
    use phs_base
    use mappings
    use phs_forests
    use cascades

    ⟨Standard module head⟩

    ⟨PHS wood: public⟩

    ⟨PHS wood: types⟩

    contains

    ⟨PHS wood: procedures⟩

```

```
⟨PHS wood: tests⟩
```

```
end module phs_wood
```

18.7.1 Configuration

```
⟨PHS wood: public⟩≡
```

```
public :: phs_wood_config_t
```

```
⟨PHS wood: types⟩≡
```

```
type, extends (phs_config_t) :: phs_wood_config_t
character(32) :: md5sum_forest = ""
integer :: io_unit = 0
logical :: io_unit_keep_open = .false.
logical :: use_equivalences = .false.
logical :: fatal_beam_decay = .true.
type(mapping_defaults_t) :: mapping_defaults
type(phs_parameters_t) :: par
type(string_t) :: run_id
type(cascade_set_t), allocatable :: cascade_set
type(phs_forest_t) :: forest
type(os_data_t) :: os_data
logical :: extended_phs = .false.
contains
⟨PHS wood: phs wood config: TBP⟩
end type phs_wood_config_t
```

Finalizer. We should delete the cascade set and the forest subobject.

Also close the I/O unit, just in case. (We assume that `io_unit` is not standard input/output.)

```
⟨PHS wood: phs wood config: TBP⟩≡
```

```
procedure :: final => phs_wood_config_final
```

```
⟨PHS wood: procedures⟩≡
```

```
subroutine phs_wood_config_final (object)
class(phs_wood_config_t), intent(inout) :: object
logical :: opened
if (object%io_unit /= 0) then
inquire (unit = object%io_unit, opened = opened)
if (opened) close (object%io_unit)
end if
call object%clear_phase_space ()
call phs_forest_final (object%forest)
end subroutine phs_wood_config_final
```

```
⟨PHS wood: phs wood config: TBP⟩+≡
```

```
procedure :: increase_n_par => phs_wood_config_increase_n_par
```

```
⟨PHS wood: procedures⟩+≡
```

```
subroutine phs_wood_config_increase_n_par (phs_config)
class(phs_wood_config_t), intent(inout) :: phs_config
phs_config%n_par = phs_config%n_par + 3
end subroutine phs_wood_config_increase_n_par
```

```

(PHS wood: phs wood config: TBP)+≡
  procedure :: set_extended_phs => phs_wood_config_set_extended_phs

(PHS wood: procedures)+≡
  subroutine phs_wood_config_set_extended_phs (phs_config)
    class(phs_wood_config_t), intent(inout) :: phs_config
    phs_config%extended_phs = .true.
  end subroutine phs_wood_config_set_extended_phs

```

Output. The contents of the PHS forest are not printed explicitly.

```

(PHS wood: phs wood config: TBP)+≡
  procedure :: write => phs_wood_config_write

(PHS wood: procedures)+≡
  subroutine phs_wood_config_write (object, unit)
    class(phs_wood_config_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") &
      "Partonic phase-space configuration (phase-space forest):"
    call object%base_write (unit)
    write (u, "(1x,A)") "Phase-space configuration parameters:"
    call phs_parameters_write (object%par, u)
    call object%mapping_defaults%write (u)
    write (u, "(3x,A,A,A)") "Run ID: '", char (object%run_id), "'"
  end subroutine phs_wood_config_write

```

Print the PHS forest contents.

```

(PHS wood: phs wood config: TBP)+≡
  procedure :: write_forest => phs_wood_config_write_forest

(PHS wood: procedures)+≡
  subroutine phs_wood_config_write_forest (object, unit)
    class(phs_wood_config_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    call phs_forest_write (object%forest, u)
  end subroutine phs_wood_config_write_forest

```

Set the phase-space parameters that the configuration generator requests.

```

(PHS wood: phs wood config: TBP)+≡
  procedure :: set_parameters => phs_wood_config_set_parameters

(PHS wood: procedures)+≡
  subroutine phs_wood_config_set_parameters (phs_config, par)
    class(phs_wood_config_t), intent(inout) :: phs_config
    type(phs_parameters_t), intent(in) :: par
    phs_config%par = par
  end subroutine phs_wood_config_set_parameters

```

Enable the generation of channel equivalences (when calling `configure`).

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: enable_equivalences => phs_wood_config_enable_equivalences

<PHS wood: procedures>+≡
  subroutine phs_wood_config_enable_equivalences (phs_config)
    class(phs_wood_config_t), intent(inout) :: phs_config
    phs_config%use_equivalences = .true.
  end subroutine phs_wood_config_enable_equivalences

```

Set the phase-space mapping parameters that the configuration generator requests.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: set_mapping_defaults => phs_wood_config_set_mapping_defaults

<PHS wood: procedures>+≡
  subroutine phs_wood_config_set_mapping_defaults (phs_config, mapping_defaults)
    class(phs_wood_config_t), intent(inout) :: phs_config
    type(mapping_defaults_t), intent(in) :: mapping_defaults
    phs_config%mapping_defaults = mapping_defaults
  end subroutine phs_wood_config_set_mapping_defaults

```

Define the input stream for the phase-space file as an open logical unit. The unit must be connected.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: set_input => phs_wood_config_set_input

<PHS wood: procedures>+≡
  subroutine phs_wood_config_set_input (phs_config, unit)
    class(phs_wood_config_t), intent(inout) :: phs_config
    integer, intent(in) :: unit
    phs_config%io_unit = unit
    rewind (unit)
  end subroutine phs_wood_config_set_input

```

18.7.2 Phase-space generation

This subroutine generates a phase space configuration using the `cascades` module. Note that this may take time, and the `cascade_set` subobject may consume a large amount of memory.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: generate_phase_space => phs_wood_config_generate_phase_space

<PHS wood: procedures>+≡
  subroutine phs_wood_config_generate_phase_space (phs_config)
    class(phs_wood_config_t), intent(inout) :: phs_config
    integer :: off_shell, extra_off_shell
    call msg_message ("Phase space: generating configuration ...")
    off_shell = phs_config%par%off_shell
    allocate (phs_config%cascade_set)
    do extra_off_shell = 0, max (phs_config%n_tot - 3, 0)
      phs_config%par%off_shell = off_shell + extra_off_shell
    end do
  end subroutine phs_wood_config_generate_phase_space

```

```

call cascade_set_generate (phs_config%cascade_set, &
    phs_config%model, phs_config%n_in, phs_config%n_out, &
    phs_config%flv, &
    phs_config%par, phs_config%fatal_beam_decay)
if (cascade_set_is_valid (phs_config%cascade_set)) then
    exit
else
    call msg_message ("Phase space: ... failed. &
        &Increasing phs_off_shell ...")
end if
end do
if (cascade_set_is_valid (phs_config%cascade_set)) then
    call msg_message ("Phase space: ... success.")
else
    call msg_fatal ("Phase-space: generation failed")
end if
end subroutine phs_wood_config_generate_phase_space

```

Using the generated phase-space configuration, write an appropriate phase-space file to the stored (or explicitly specified) I/O unit.

(PHS wood: phs wood config: TBP)+≡

```

procedure :: write_phase_space => phs_wood_config_write_phase_space

```

(PHS wood: procedures)+≡

```

subroutine phs_wood_config_write_phase_space (phs_config, &
    filename_vis, unit)
class(phs_wood_config_t), intent(in) :: phs_config
integer, intent(in), optional :: unit
type(string_t), intent(in), optional :: filename_vis
type(string_t) :: setenv_tex, setenv_mp, pipe, pipe_dvi
integer :: u, unit_tex, unit_dev, status
if (allocated (phs_config%cascade_set)) then
    if (present (unit)) then
        u = unit
    else
        u = phs_config%io_unit
    end if
    write (u, "(1x,A,A)") "process ", char (phs_config%id)
    write (u, "(A)")
    call cascade_set_write_process_bincode_format (phs_config%cascade_set, u)
    write (u, "(A)")
    write (u, "(3x,A,A,A32,A)") "md5sum_process    = ", &
        '""', phs_config%md5sum_process, '""'
    write (u, "(3x,A,A,A32,A)") "md5sum_model_par  = ", &
        '""', phs_config%md5sum_model_par, '""'
    write (u, "(3x,A,A,A32,A)") "md5sum_phs_config = ", &
        '""', phs_config%md5sum_phs_config, '""'
    call phs_parameters_write (phs_config%par, u)
    call cascade_set_write_file_format (phs_config%cascade_set, u)
    if (phs_config%vis_channels) then
        unit_tex = free_unit ()
        open (unit=unit_tex, file=char(filename_vis // ".tex"), &
            action="write", status="replace")
        call cascade_set_write_graph_format (phs_config%cascade_set, &

```

```

        filename_vis // "-graphs", phs_config%id, unit_tex)
close (unit_tex)
call msg_message ("Phase space: visualizing channels in file " &
// char(trim(filename_vis)) // "...")
if (phs_config%os_data%event_analysis_ps) then
BLOCK: do
    unit_dev = free_unit ()
    open (file = "/dev/null", unit = unit_dev, &
        action = "write", iostat = status)
    if (status /= 0) then
        pipe = ""
        pipe_dvi = ""
    else
        pipe = " > /dev/null"
        pipe_dvi = " 2>/dev/null 1>/dev/null"
    end if
    close (unit_dev)
    if (phs_config%os_data%whizard_texpath /= "") then
        setenv_tex = "TEXINPUTS=" // &
            phs_config%os_data%whizard_texpath // " :$TEXINPUTS "
        setenv_mp = "MPINPUTS=" // &
            phs_config%os_data%whizard_texpath // " :$MPINPUTS "
    else
        setenv_tex = ""
        setenv_mp = ""
    end if
    call os_system_call (setenv_tex // &
        phs_config%os_data%latex // " " // &
        filename_vis // ".tex " // pipe, status)
    if (status /= 0) exit BLOCK
    if (phs_config%os_data%mpost /= "") then
        call os_system_call (setenv_mp // &
            phs_config%os_data%mpost // " " // &
            filename_vis // "-graphs.mp" // pipe, status)
    else
        call msg_fatal ("Could not use MetaPOST.")
    end if
    if (status /= 0) exit BLOCK
    call os_system_call (setenv_tex // &
        phs_config%os_data%latex // " " // &
        filename_vis // ".tex" // pipe, status)
    if (status /= 0) exit BLOCK
    call os_system_call &
        (phs_config%os_data%dvips // " -o " // filename_vis &
        // ".ps " // filename_vis // ".dvi" // pipe_dvi, status)
    if (status /= 0) exit BLOCK
    if (phs_config%os_data%event_analysis_pdf) then
        call os_system_call (phs_config%os_data%ps2pdf // " " // &
            filename_vis // ".ps", status)
        if (status /= 0) exit BLOCK
    end if
    exit BLOCK
end do BLOCK
if (status /= 0) then

```



```

        call msg_error ("Unable to compile analysis output file")
    end if
end if
end if
else
    call msg_fatal ("Phase-space configuration: &
        &no phase space object generated")
end if
end subroutine phs_wood_config_write_phase_space

```

Clear the phase-space configuration. This is useful since the object may become *really* large.

```

<PHS wood: phs wood config: TBP>+≡
    procedure :: clear_phase_space => phs_wood_config_clear_phase_space

<PHS wood: procedures>+≡
    subroutine phs_wood_config_clear_phase_space (phs_config)
        class(phs_wood_config_t), intent(inout) :: phs_config
        if (allocated (phs_config%cascade_set)) then
            call cascade_set_final (phs_config%cascade_set)
            deallocate (phs_config%cascade_set)
        end if
    end subroutine phs_wood_config_clear_phase_space

```

18.7.3 Phase-space configuration

We read the phase-space configuration from the stored I/O unit. If this is not set, we assume that we have to generate a phase space configuration. When done, we open a scratch file and write the configuration.

If `rebuild` is set, we should trash any existing phase space file and build a new one. Otherwise, we try to use an old one, which we check for existence and integrity. If `ignore_mismatch` is set, we reuse an existing file even if it does not match the current setup.

```

<PHS wood: phs wood config: TBP>+≡
    procedure :: configure => phs_wood_config_configure

<PHS wood: procedures>+≡
    subroutine phs_wood_config_configure (phs_config, sqrts, &
        sqrts_fixed, cm_frame, azimuthal_dependence, rebuild, ignore_mismatch, &
        nlo_type)
        class(phs_wood_config_t), intent(inout) :: phs_config
        real(default), intent(in) :: sqrts
        logical, intent(in), optional :: sqrts_fixed
        logical, intent(in), optional :: cm_frame
        logical, intent(in), optional :: azimuthal_dependence
        logical, intent(in), optional :: rebuild
        logical, intent(in), optional :: ignore_mismatch
        integer, intent(inout), optional :: nlo_type
        type(string_t) :: filename, filename_vis
        logical :: variable_limits
        logical :: ok, exist, found, check, match, rebuild_phs
        integer :: g, c0, c1, n
    end subroutine phs_wood_config_configure

```

```

if (present (nlo_type)) then
  phs_config%nlo_type = nlo_type
else
  phs_config%nlo_type = BORN
end if
phs_config%sqrts = sqrts
phs_config%par%sqrts = sqrts
if (present (sqrts_fixed)) &
  phs_config%sqrts_fixed = sqrts_fixed
if (present (cm_frame)) &
  phs_config%cm_frame = cm_frame
if (present (azimuthal_dependence)) &
  phs_config%azimuthal_dependence = azimuthal_dependence
if (present (rebuild)) then
  rebuild_phs = rebuild
else
  rebuild_phs = .true.
end if
if (present (ignore_mismatch)) then
  check = .not. ignore_mismatch
  if (ignore_mismatch) &
    call msg_warning ("Reading phs file: MD5 sum check disabled")
else
  check = .true.
end if
phs_config%md5sum_forest = ""
call phs_config%compute_md5sum ()
if (phs_config%io_unit == 0) then
  if (phs_config%run_id /= "") then
    filename = phs_config%id // "." // phs_config%run_id // ".phs"
    filename_vis = phs_config%id // "." // phs_config%run_id // "_phs"
  else
    filename = phs_config%id // ".phs"
    filename_vis = phs_config%id // "_phs"
  end if
  if (.not. rebuild_phs) then
    if (check) then
      call phs_config%read_phs_file (exist, found, match)
      rebuild_phs = .not. (exist .and. found .and. match)
    else
      call phs_config%read_phs_file (exist, found)
      rebuild_phs = .not. (exist .and. found)
    end if
  end if
  if (rebuild_phs) then
    call phs_config%generate_phase_space ()
    phs_config%io_unit = free_unit ()
    if (phs_config%id /= "") then
      call msg_message ("Phase space: writing configuration file '" &
        // char (filename) // "'")
      open (phs_config%io_unit, file = char (filename), &
        status = "replace", action = "readwrite")
    else
      open (phs_config%io_unit, status = "scratch", action = "readwrite")
    end if
  end if
end if

```

```

        end if
        call phs_config%write_phase_space (filename_vis)
        rewind (phs_config%io_unit)
    else
        call msg_message ("Phase space: keeping configuration file '" &
            // char (filename) // "'")
    end if
end if
if (phs_config%io_unit == 0) then
    ok = .true.
else
    call phs_forest_read (phs_config%forest, phs_config%io_unit, &
        phs_config%id, phs_config%n_in, phs_config%n_out, &
        phs_config%model, ok)
    if (.not. phs_config%io_unit_keep_open) then
        close (phs_config%io_unit)
        phs_config%io_unit = 0
    end if
end if
if (ok) then
    call phs_forest_set_flavors (phs_config%forest, phs_config%flv(:,1))
    variable_limits = .not. phs_config%cm_frame
    call phs_forest_set_parameters &
        (phs_config%forest, phs_config%mapping_defaults, variable_limits)
    call phs_forest_setup_prt_combinations (phs_config%forest)
    phs_config%n_channel = phs_forest_get_n_channels (phs_config%forest)
    phs_config%n_par = phs_forest_get_n_parameters (phs_config%forest)
    allocate (phs_config%channel (phs_config%n_channel))
    if (phs_config%use_equivalences) then
        call phs_forest_set_equivalences (phs_config%forest)
        call phs_forest_get_equivalences (phs_config%forest, &
            phs_config%channel, phs_config%azimuthal_dependence)
        phs_config%provides_equivalences = .true.
    end if
    call phs_forest_set_s_mappings (phs_config%forest)
    call phs_config%record_on_shell ()
    if (phs_config%mapping_defaults%enable_s_mapping) then
        call phs_config%record_s_mappings ()
    end if
    allocate (phs_config%chain (phs_config%n_channel), source = 0)
    do g = 1, phs_forest_get_n_groves (phs_config%forest)
        call phs_forest_get_grove_bounds (phs_config%forest, g, c0, c1, n)
        phs_config%chain (c0:c1) = g
    end do
    phs_config%provides_chains = .true.
    call phs_config%compute_md5sum_forest ()
else
    write (msg_buffer, "(A,A,A)") &
        "Phase space: process '", &
        char (phs_config%id), "' not found in configuration file"
    call msg_fatal ()
end if
end subroutine phs_wood_config_configure

```

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: set_extra_parameters => phs_wood_config_set_extra_parameters

<PHS wood: procedures>+≡
  subroutine phs_wood_config_set_extra_parameters (config)
    class(phs_wood_config_t), intent(inout) :: config
    config%n_par = config%n_par + 3
  end subroutine phs_wood_config_set_extra_parameters

<PHS wood: phs wood config: TBP>+≡
  procedure :: reshuffle_flavors => phs_wood_config_reshuffle_flavors

<PHS wood: procedures>+≡
  subroutine phs_wood_config_reshuffle_flavors (phs_config, reshuffle, flv_extra)
    class(phs_wood_config_t), intent(inout) :: phs_config
    integer, intent(in), dimension(:), allocatable :: reshuffle
    type(flavor_t), intent(in) :: flv_extra
    call phs_forest_set_flavors (phs_config%forest, phs_config%flv(:,1), reshuffle, flv_extra)
  end subroutine phs_wood_config_reshuffle_flavors

<PHS wood: phs wood config: TBP>+≡
  procedure :: set_momentum_links => phs_wood_config_set_momentum_links

<PHS wood: procedures>+≡
  subroutine phs_wood_config_set_momentum_links (phs_config, reshuffle)
    class(phs_wood_config_t), intent(inout) :: phs_config
    integer, intent(in), dimension(:), allocatable :: reshuffle
    call phs_forest_set_momentum_links (phs_config%forest, reshuffle)
  end subroutine phs_wood_config_set_momentum_links

```

Identify resonances which are marked by s-channel mappings for the whole phase space and report them to the channel array.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: record_s_mappings => phs_wood_config_record_s_mappings

<PHS wood: procedures>+≡
  subroutine phs_wood_config_record_s_mappings (phs_config)
    class(phs_wood_config_t), intent(inout) :: phs_config
    logical :: flag
    real(default) :: mass, width
    integer :: c
    do c = 1, phs_config%n_channel
      call phs_forest_get_s_mapping (phs_config%forest, c, flag, mass, width)
      if (flag) then
        if (mass == 0) then
          call msg_fatal ("Phase space: s-channel resonance " &
            // " has zero mass")
        end if
        if (width == 0) then
          call msg_fatal ("Phase space: s-channel resonance " &
            // " has zero width")
        end if
        call phs_config%channel(c)%set_resonant (mass, width)
      end if
    end do
  end subroutine

```

```

end do
end subroutine phs_wood_config_record_s_mappings

```

Identify on-shell mappings for the whole phase space and report them to the channel array.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: record_on_shell => phs_wood_config_record_on_shell

<PHS wood: procedures>+≡
  subroutine phs_wood_config_record_on_shell (phs_config)
    class(phs_wood_config_t), intent(inout) :: phs_config
    logical :: flag
    real(default) :: mass
    integer :: c
    do c = 1, phs_config%n_channel
      call phs_forest_get_on_shell (phs_config%forest, c, flag, mass)
      if (flag) then
        call phs_config%channel(c)%set_on_shell (mass)
      end if
    end do
  end subroutine phs_wood_config_record_on_shell

```

The MD5 sum of the forest is computed in addition to the MD5 sum of the configuration. The reason is that the forest may depend on a user-provided external file. On the other hand, this MD5 sum encodes all information that is relevant for further processing. Therefore, the `get_md5sum` method returns this result, once it is available.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: compute_md5sum_forest => phs_wood_config_compute_md5sum_forest

<PHS wood: procedures>+≡
  subroutine phs_wood_config_compute_md5sum_forest (phs_config)
    class(phs_wood_config_t), intent(inout) :: phs_config
    integer :: u
    u = free_unit ()
    open (u, status = "scratch", action = "readwrite")
    call phs_config%write_forest (u)
    rewind (u)
    phs_config%md5sum_forest = md5sum (u)
    close (u)
  end subroutine phs_wood_config_compute_md5sum_forest

```

Return the most relevant MD5 sum. This overrides the method of the base type.

```

<PHS wood: phs wood config: TBP>+≡
  procedure :: get_md5sum => phs_wood_config_get_md5sum

<PHS wood: procedures>+≡
  function phs_wood_config_get_md5sum (phs_config) result (md5sum)
    class(phs_wood_config_t), intent(in) :: phs_config
    character(32) :: md5sum
    if (phs_config%md5sum_forest /= "") then
      md5sum = phs_config%md5sum_forest
    end if
  end function

```

```

else
    md5sum = phs_config%md5sum_phs_config
end if
end function phs_wood_config_get_md5sum

```

Check whether a phase-space configuration for the current process exists. We look for the phase-space file that should correspond to the current process. If we find it, we check the MD5 sums stored in the file against the MD5 sums in the current configuration (if required).

If successful, read the PHS file.

```

(PHS wood: phs wood config: TBP)+≡
    procedure :: read_phs_file => phs_wood_read_phs_file

(PHS wood: procedures)+≡
    subroutine phs_wood_read_phs_file (phs_config, exist, found, match)
        class(phs_wood_config_t), intent(inout) :: phs_config
        logical, intent(out) :: exist
        logical, intent(out) :: found
        logical, intent(out), optional :: match
        type(string_t) :: filename
        integer :: u
        filename = phs_config%id // ".phs"
        inquire (file = char (filename), exist = exist)
        if (exist) then
            u = free_unit ()
            open (u, file = char (filename), action = "read", status = "old")
            call phs_forest_read (phs_config%forest, u, &
                phs_config%id, phs_config%n_in, phs_config%n_out, &
                phs_config%model, found, &
                phs_config%md5sum_process, &
                phs_config%md5sum_model_par, &
                phs_config%md5sum_phs_config, &
                match = match)
            close (u)
        else
            found = .false.
            if (present (match)) match = .false.
        end if
    end subroutine phs_wood_read_phs_file

```

Startup message, after configuration is complete.

```

(PHS wood: phs wood config: TBP)+≡
    procedure :: startup_message => phs_wood_config_startup_message

(PHS wood: procedures)+≡
    subroutine phs_wood_config_startup_message (phs_config, unit)
        class(phs_wood_config_t), intent(in) :: phs_config
        integer, intent(in), optional :: unit
        integer :: n_groves, n_eq
        n_groves = phs_forest_get_n_groves (phs_config%forest)
        n_eq = phs_forest_get_n_equivalences (phs_config%forest)
        call phs_config%base_startup_message (unit)
        if (phs_config%n_channel == 1) then

```

```

        write (msg_buffer, "(A,2(IO,A))" ) &
            "Phase space: found ", phs_config%n_channel, &
            " channel, collected in ", n_groves, &
            " grove."
    else if (n_groves == 1) then
        write (msg_buffer, "(A,2(IO,A))" ) &
            "Phase space: found ", phs_config%n_channel, &
            " channels, collected in ", n_groves, &
            " grove."
    else
        write (msg_buffer, "(A,2(IO,A))" ) &
            "Phase space: found ", phs_config%n_channel, &
            " channels, collected in ", &
            phs_forest_get_n_groves (phs_config%forest), &
            " groves."
    end if
    call msg_message (unit = unit)
    if (phs_config%use_equivalences) then
        if (n_eq == 1) then
            write (msg_buffer, "(A,IO,A)" ) &
                "Phase space: Using ", n_eq, &
                " equivalence between channels."
        else
            write (msg_buffer, "(A,IO,A)" ) &
                "Phase space: Using ", n_eq, &
                " equivalences between channels."
        end if
    else
        write (msg_buffer, "(A)" ) &
            "Phase space: no equivalences between channels used."
    end if
    call msg_message (unit = unit)
    write (msg_buffer, "(A,2(1x,IO,1x,A))" ) &
        "Phase space: wood"
    call msg_message (unit = unit)
end subroutine phs_wood_config_startup_message

```

Allocate an instance: the actual phase-space object.

```

<PHS wood: phs wood config: TBP>+≡
    procedure, nopass :: allocate_instance => phs_wood_config_allocate_instance

<PHS wood: procedures>+≡
    subroutine phs_wood_config_allocate_instance (phs)
        class(phs_t), intent(inout), pointer :: phs
        allocate (phs_wood_t :: phs)
    end subroutine phs_wood_config_allocate_instance

```

18.7.4 Kinematics implementation

We generate $\cos\theta$ and ϕ uniformly, covering the solid angle.

```

<PHS wood: public>+≡
    public :: phs_wood_t

```

```

<PHS wood: types>+≡
  type, extends (phs_t) :: phs_wood_t
    real(default) :: sqrts = 0
    type(phs_forest_t) :: forest
    real(default), dimension(3) :: r_real
    integer :: n_r_born = 0
  contains
    <PHS wood: phs wood: TBP>
  end type phs_wood_t

```

Output. The `verbose` setting is irrelevant, we just display the contents of the base object.

```

<PHS wood: phs wood: TBP>≡
  procedure :: write => phs_wood_write

<PHS wood: procedures>+≡
  subroutine phs_wood_write (object, unit, verbose)
    class(phs_wood_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u
    u = given_output_unit (unit)
    call object%base_write (u)
  end subroutine phs_wood_write

```

Write the forest separately.

```

<PHS wood: phs wood: TBP>+≡
  procedure :: write_forest => phs_wood_write_forest

<PHS wood: procedures>+≡
  subroutine phs_wood_write_forest (object, unit)
    class(phs_wood_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    call phs_forest_write (object%forest, u)
  end subroutine phs_wood_write_forest

```

Finalizer.

```

<PHS wood: phs wood: TBP>+≡
  procedure :: final => phs_wood_final

<PHS wood: procedures>+≡
  subroutine phs_wood_final (object)
    class(phs_wood_t), intent(inout) :: object
    call phs_forest_final (object%forest)
  end subroutine phs_wood_final

```

Initialization. We allocate arrays (`base_init`) and adjust the phase-space volume. The two-particle phase space volume is

$$\Phi_2 = \frac{1}{4(2\pi)^5} = 2.55294034614 \times 10^{-5} \quad (18.64)$$

independent of the particle masses.

```

(PHS wood: phs wood: TBP)+≡
  procedure :: init => phs_wood_init

(PHS wood: procedures)+≡
  subroutine phs_wood_init (phs, phs_config)
    class(phs_wood_t), intent(out) :: phs
    class(phs_config_t), intent(in), target :: phs_config
    call phs%base_init (phs_config)
    select type (phs_config)
      type is (phs_wood_config_t)
        phs%forest = phs_config%forest
        if (phs_config%extended_phs) &
          phs%n_r_born = phs_config%n_par - 3
    end select
  end subroutine phs_wood_init

```

18.7.5 Evaluation

We compute the outgoing momenta from the incoming momenta and the input parameter set `r_in` in channel `r_in`. We also compute the `r` parameters and Jacobians `f` for all other channels.

We do *not* need to apply a transformation from/to the c.m. frame, because in `phs_base` the momenta are already boosted to the c.m. frame before assigning them in the `phs` object, and inversely boosted when extracting them.

```

(PHS wood: phs wood: TBP)+≡
  procedure :: evaluate_selected_channel => phs_wood_evaluate_selected_channel
  procedure :: evaluate_other_channels => phs_wood_evaluate_other_channels

(PHS wood: procedures)+≡
  subroutine phs_wood_evaluate_selected_channel (phs, c_in, r_in)
    class(phs_wood_t), intent(inout) :: phs
    integer, intent(in) :: c_in
    real(default), intent(in), dimension(:) :: r_in
    logical :: ok
    phs%q_defined = .false.
    if (phs%p_defined) then
      call phs_forest_set_prt_in (phs%forest, phs%p)
      phs%r(:,c_in) = r_in
      call phs_forest_evaluate_selected_channel (phs%forest, &
        c_in, phs%active_channel, &
        phs%sqrts_hat, phs%r, phs%f, phs%volume, ok)
      select type (config => phs%config)
        type is (phs_wood_config_t)
          if (config%extended_phs) then
            if (phs%n_r_born > 0) then
              phs%r_real = r_in (phs%n_r_born+1:phs%n_r_born+3)
            else
              call msg_fatal ("n_r_born should be larger than 0!")
            end if
          end if
        end select
      if (ok) then

```

```

        phs%q = phs_forest_get_momenta_out (phs%forest)
        phs%q_defined = .true.
    end if
end if
end subroutine phs_wood_evaluate_selected_channel

subroutine phs_wood_evaluate_other_channels (phs, c_in)
    class(phs_wood_t), intent(inout) :: phs
    integer, intent(in) :: c_in
    integer :: c
    if (phs%q_defined) then
        call phs_forest_evaluate_other_channels (phs%forest, &
            c_in, phs%active_channel, &
            phs%sqrts_hat, phs%r, phs%f, combine=.true.)
        select type (config => phs%config)
        type is (phs_wood_config_t)
            if (config%extended_phs) then
                if (phs%n_r_born > 0) then
                    do c = 1, size (phs%r, 2)
                        phs%r(phs%n_r_born+1:phs%n_r_born+3,c) = phs%r_real
                    end do
                else
                    phs%r_defined = .false.
                end if
            end if
        end select
        phs%r_defined = .true.
    end if
end subroutine phs_wood_evaluate_other_channels

```

Inverse evaluation.

```

<PHS wood: phs wood: TBP>+≡
    procedure :: inverse => phs_wood_inverse

<PHS wood: procedures>+≡
    subroutine phs_wood_inverse (phs)
        class(phs_wood_t), intent(inout) :: phs
        if (phs%p_defined .and. phs%q_defined) then
            call phs_forest_set_prt_in (phs%forest, phs%p)
            call phs_forest_set_prt_out (phs%forest, phs%q)
            call phs_forest_recover_channel (phs%forest, &
                1, &
                phs%sqrts_hat, phs%r, phs%f, phs%volume)
            call phs_forest_evaluate_other_channels (phs%forest, &
                1, phs%active_channel, &
                phs%sqrts_hat, phs%r, phs%f, combine=.false.)
            phs%r_defined = .true.
        end if
    end subroutine phs_wood_inverse

```

18.7.6 Unit tests

```

<PHS wood: public>+≡

```

```

        public :: phs_wood_test
<PHS wood: tests>≡
    subroutine phs_wood_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <PHS wood: execute tests>
    end subroutine phs_wood_test

<PHS wood: public>+≡
    public :: phs_wood_vis_test

<PHS wood: tests>+≡
    subroutine phs_wood_vis_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <PHS wood: execute vis tests>
    end subroutine phs_wood_vis_test

```

Phase-space configuration data

Construct and display a test phase-space configuration object. Also check the `azimuthal_dependence` flag.

This auxiliary routine writes a phase-space configuration file to unit `u_phs`.

```

<PHS wood: public>+≡
    public :: write_test_phs_file

<PHS wood: tests>+≡
    subroutine write_test_phs_file (u_phs, procname)
        integer, intent(in) :: u_phs
        type(string_t), intent(in), optional :: procname
        if (present (procname)) then
            write (u_phs, "(A,A)") "process ", char (procname)
        else
            write (u_phs, "(A)") "process testproc"
        end if
        write (u_phs, "(A,A)") "  md5sum_process   = ", ''''
        write (u_phs, "(A,A)") "  md5sum_model_par = ", ''''
        write (u_phs, "(A,A)") "  md5sum_phs_config = ", ''''
        write (u_phs, "(A)") "  sqrts           = 1000"
        write (u_phs, "(A)") "  m_threshold_s   = 50"
        write (u_phs, "(A)") "  m_threshold_t   = 100"
        write (u_phs, "(A)") "  off_shell = 2"
        write (u_phs, "(A)") "  t_channel = 6"
        write (u_phs, "(A)") "  keep_nonresonant = T"
        write (u_phs, "(A)") "  grove #1"
        write (u_phs, "(A)") "  tree 3"
    end subroutine write_test_phs_file

<PHS wood: execute tests>≡
    call test (phs_wood_1, "phs_wood_1", &
        "phase-space configuration", &
        u, results)

```

(PHS wood: tests)+≡

```

subroutine phs_wood_1 (u)
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(process_constants_t) :: process_data
  class(phs_config_t), allocatable :: phs_data
  type(mapping_defaults_t) :: mapping_defaults
  real(default) :: sqrts
  integer :: u_phs, iostat
  character(32) :: buffer

  write (u, "(A)")  "* Test output: phs_wood_1"
  write (u, "(A)")  "* Purpose: initialize and display &
    &phase-space configuration data"
  write (u, "(A)")

  call model%init_test ()

  call syntax_phs_forest_init ()

  write (u, "(A)")  "* Initialize a process"
  write (u, "(A)")

  call init_test_process_data (var_str ("phs_wood_1"), process_data)

  write (u, "(A)")  "* Create a scratch phase-space file"
  write (u, "(A)")

  u_phs = free_unit ()
  open (u_phs, status = "scratch", action = "readwrite")
  call write_test_phs_file (u_phs, var_str ("phs_wood_1"))
  rewind (u_phs)
  do
    read (u_phs, "(A)", iostat = iostat)  buffer
    if (iostat /= 0) exit
    write (u, "(A)") trim (buffer)
  end do

  write (u, "(A)")
  write (u, "(A)")  "* Setup phase-space configuration object"
  write (u, "(A)")

  mapping_defaults%step_mapping = .false.

  allocate (phs_wood_config_t :: phs_data)
  call phs_data%init (process_data, model)
  select type (phs_data)
  type is (phs_wood_config_t)
    call phs_data%set_input (u_phs)
    call phs_data%set_mapping_defaults (mapping_defaults)
  end select

  sqrts = 1000._default
  call phs_data%configure (sqrts)

```

```

call phs_data%write (u)
write (u, "(A)")

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%write_forest (u)
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

close (u_phs)
call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_1"

end subroutine phs_wood_1

```

Phase space evaluation

Compute kinematics for given parameters, also invert the calculation.

```

<PHS wood: execute tests>+≡
    call test (phs_wood_2, "phs_wood_2", &
        "phase-space evaluation", &
        u, results)

<PHS wood: tests>+≡
subroutine phs_wood_2 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(flavor_t) :: flv
    type(process_constants_t) :: process_data
    real(default) :: sqrts, E
    class(phs_config_t), allocatable, target :: phs_data
    class(phs_t), pointer :: phs => null ()
    type(vector4_t), dimension(2) :: p, q
    integer :: u_phs

    write (u, "(A)")  "* Test output: phs_wood_2"
    write (u, "(A)")  "* Purpose: test simple single-channel phase space"
    write (u, "(A)")

    call model%init_test ()
    call flv%init (25, model)

    write (u, "(A)")  "* Initialize a process and a matching &
        &phase-space configuration"
    write (u, "(A)")

    call init_test_process_data (var_str ("phs_wood_2"), process_data)

```

```

u_phs = free_unit ()
open (u_phs, status = "scratch", action = "readwrite")
call write_test_phs_file (u_phs, var_str ("phs_wood_2"))
rewind (u_phs)

allocate (phs_wood_config_t :: phs_data)
call phs_data%init (process_data, model)
select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%set_input (u_phs)
end select

sqrt_s = 1000._default
call phs_data%configure (sqrt_s)

call phs_data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize the phase-space instance"
write (u, "(A)")

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs%write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Set incoming momenta"
write (u, "(A)")

E = sqrt_s / 2
p(1) = vector4_moving (E, sqrt (E**2 - flv%get_mass ()**2), 3)
p(2) = vector4_moving (E,-sqrt (E**2 - flv%get_mass ()**2), 3)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute phase-space point &
    &for x = 0.125, 0.5"
write (u, "(A)")

call phs%evaluate_selected_channel (1, [0.125_default, 0.5_default])
call phs%evaluate_other_channels (1)
call phs%write (u)
write (u, "(A)")
select type (phs)
type is (phs_wood_t)
    call phs%write_forest (u)
end select

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"

```

```

write (u, "(A)")

call phs%get_outgoing_momenta (q)
call phs%final ()
deallocate (phs)

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%set_outgoing_momenta (q)

call phs%inverse ()
call phs%write (u)
write (u, "(A)")
select type (phs)
type is (phs_wood_t)
    call phs%write_forest (u)
end select

call phs%final ()
deallocate (phs)

close (u_phs)
call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_2"

end subroutine phs_wood_2

```

Phase-space generation

Generate phase space for a simple process.

(PHS wood: execute tests)+≡

```

call test (phs_wood_3, "phs_wood_3", &
    "phase-space generation", &
    u, results)

```

(PHS wood: tests)+≡

```

subroutine phs_wood_3 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    type(phs_parameters_t) :: phs_par
    class(phs_config_t), allocatable :: phs_data
    integer :: iostat
    character(80) :: buffer

    write (u, "(A)")  "* Test output: phs_wood_3"
    write (u, "(A)")  "* Purpose: generate a phase-space configuration"

```

```

write (u, "(A)")

call model%init_test ()

call syntax_phs_forest_init ()

write (u, "(A)")  "* Initialize a process and phase-space parameters"
write (u, "(A)")

call init_test_process_data (var_str ("phs_wood_3"), process_data)
allocate (phs_wood_config_t :: phs_data)
call phs_data%init (process_data, model)

phs_par%sqrts = 1000
select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%set_parameters (phs_par)
    phs_data%io_unit_keep_open = .true.
end select

write (u, "(A)")
write (u, "(A)")  "* Generate a scratch phase-space file"
write (u, "(A)")

call phs_data%configure (phs_par%sqrts)

select type (phs_data)
type is (phs_wood_config_t)
    rewind (phs_data%io_unit)
    do
        read (phs_data%io_unit, "(A)", iostat = iostat)  buffer
        if (iostat /= 0) exit
        write (u, "(A)") trim (buffer)
    end do
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_3"

end subroutine phs_wood_3

```

Nontrivial process

Generate phase space for a $2 \rightarrow 3$ process.

```

<PHS wood: execute tests>+=
call test (phs_wood_4, "phs_wood_4", &

```



```

        "nontrivial process", &
        u, results)
(PHS wood: tests)+≡
subroutine phs_wood_4 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    type(phs_parameters_t) :: phs_par
    class(phs_config_t), allocatable, target :: phs_data
    integer :: iostat
    character(80) :: buffer
    class(phs_t), pointer :: phs => null ()
    real(default) :: E, pL
    type(vector4_t), dimension(2) :: p
    type(vector4_t), dimension(3) :: q

    write (u, "(A)")  "* Test output: phs_wood_4"
    write (u, "(A)")  "* Purpose: generate a phase-space configuration"
    write (u, "(A)")

    call model%init_test ()

    call syntax_phs_forest_init ()

    write (u, "(A)")  "* Initialize a process and phase-space parameters"
    write (u, "(A)")

    process_data%id = "phs_wood_4"
    process_data%model_name = "Test"
    process_data%n_in = 2
    process_data%n_out = 3
    process_data%n_flv = 1
    allocate (process_data%flv_state (process_data%n_in + process_data%n_out, &
        process_data%n_flv))
    process_data%flv_state(:,1) = [25, 25, 25, 6, -6]

    allocate (phs_wood_config_t :: phs_data)
    call phs_data%init (process_data, model)

    phs_par%sqrts = 1000
    select type (phs_data)
    type is (phs_wood_config_t)
        call phs_data%set_parameters (phs_par)
        phs_data%io_unit_keep_open = .true.
    end select

    write (u, "(A)")
    write (u, "(A)")  "* Generate a scratch phase-space file"
    write (u, "(A)")

    call phs_data%configure (phs_par%sqrts)

    select type (phs_data)
    type is (phs_wood_config_t)

```

```

rewind (phs_data%io_unit)
do
  read (phs_data%io_unit, "(A)", iostat = iostat)  buffer
  if (iostat /= 0) exit
  write (u, "(A)") trim (buffer)
end do
end select

write (u, "(A)")
write (u, "(A)")  "* Initialize the phase-space instance"
write (u, "(A)")

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

write (u, "(A)")  "* Set incoming momenta"
write (u, "(A)")

select type (phs_data)
type is (phs_wood_config_t)
  E = phs_data%sqrts / 2
  pL = sqrt (E**2 - phs_data%flv(1,1)%get_mass ()**2)
end select
p(1) = vector4_moving (E, pL, 3)
p(2) = vector4_moving (E, -pL, 3)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()

write (u, "(A)")  "* Compute phase-space point &
  &for x = 0.1, 0.2, 0.3, 0.4, 0.5"
write (u, "(A)")

call phs%evaluate_selected_channel (1, &
  [0.1_default, 0.2_default, 0.3_default, 0.4_default, 0.5_default])
call phs%evaluate_other_channels (1)
call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Inverse kinematics"
write (u, "(A)")

call phs%get_outgoing_momenta (q)
call phs%final ()
deallocate (phs)

call phs_data%allocate_instance (phs)
call phs%init (phs_data)

call phs%set_incoming_momenta (p)
call phs%compute_flux ()
call phs%set_outgoing_momenta (q)

call phs%inverse ()

```

```

call phs%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call phs%final ()
deallocate (phs)

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_4"

end subroutine phs_wood_4

```

Equivalences

Generate phase space for a simple process, including channel equivalences.

```

<PHS wood: execute tests>+≡
  call test (phs_wood_5, "phs_wood_5", &
    "equivalences", &
    u, results)

<PHS wood: tests>+≡
  subroutine phs_wood_5 (u)
    integer, intent(in) :: u
    type(model_data_t), target :: model
    type(process_constants_t) :: process_data
    type(phs_parameters_t) :: phs_par
    class(phs_config_t), allocatable :: phs_data

    write (u, "(A)")  "* Test output: phs_wood_5"
    write (u, "(A)")  "* Purpose: generate a phase-space configuration"
    write (u, "(A)")

    call model%init_test ()

    call syntax_phs_forest_init ()

    write (u, "(A)")  "* Initialize a process and phase-space parameters"
    write (u, "(A)")

    call init_test_process_data (var_str ("phs_wood_5"), process_data)
    allocate (phs_wood_config_t :: phs_data)
    call phs_data%init (process_data, model)

    phs_par%sqrts = 1000
    select type (phs_data)
    type is (phs_wood_config_t)
      call phs_data%set_parameters (phs_par)
      call phs_data%enable_equivalences ()
    end select

```

```

write (u, "(A)")
write (u, "(A)")  "* Generate a scratch phase-space file"
write (u, "(A)")

call phs_data%configure (phs_par%sqrts)
call phs_data%write (u)
write (u, "(A)")

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%write_forest (u)
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_5"

end subroutine phs_wood_5

```

MD5 sum checks

Generate phase space for a simple process. Repeat this with and without parameter change.

```

<PHS wood: execute tests>+≡
call test (phs_wood_6, "phs_wood_6", &
    "phase-space generation", &
    u, results)

<PHS wood: tests>+≡
subroutine phs_wood_6 (u)
integer, intent(in) :: u
type(model_data_t), target :: model
type(process_constants_t) :: process_data
type(phs_parameters_t) :: phs_par
class(phs_config_t), allocatable :: phs_data
logical :: exist, found, match
integer :: u_phs
character(*), parameter :: filename = "phs_wood_6.p.phs"

write (u, "(A)")  "* Test output: phs_wood_6"
write (u, "(A)")  "* Purpose: generate and check phase-space file"
write (u, "(A)")

call model%init_test ()

call syntax_phs_forest_init ()

```

```

write (u, "(A)")  "* Initialize a process and phase-space parameters"
write (u, "(A)")

call init_test_process_data (var_str ("phs_wood_6"), process_data)
process_data%id = "phs_wood_6_p"
process_data%md5sum = "1234567890abcdef1234567890abcdef"
allocate (phs_wood_config_t :: phs_data)
call phs_data%init (process_data, model)

phs_par%sqrts = 1000
select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%set_parameters (phs_par)
end select

write (u, "(A)")  "* Remove previous phs file, if any"
write (u, "(A)")

inquire (file = filename, exist = exist)
if (exist) then
    u_phs = free_unit ()
    open (u_phs, file = filename, action = "write")
    close (u_phs, status = "delete")
end if

write (u, "(A)")  "* Check phase-space file (should fail)"
write (u, "(A)")

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%read_phs_file (exist, found, match)
    write (u, "(1x,A,L1)")  "exist = ", exist
    write (u, "(1x,A,L1)")  "found = ", found
    write (u, "(1x,A,L1)")  "match = ", match
end select

write (u, "(A)")
write (u, "(A)")  "* Generate a phase-space file"
write (u, "(A)")

call phs_data%configure (phs_par%sqrts)

write (u, "(1x,A,A,A)")  "MD5 sum (process)    = '", &
    phs_data%md5sum_process, "'"
write (u, "(1x,A,A,A)")  "MD5 sum (model par) = '", &
    phs_data%md5sum_model_par, "'"
write (u, "(1x,A,A,A)")  "MD5 sum (phs config) = '", &
    phs_data%md5sum_phs_config, "'"

write (u, "(A)")
write (u, "(A)")  "* Check MD5 sum"
write (u, "(A)")

call phs_data%final ()

```

```

deallocate (phs_data)
allocate (phs_wood_config_t :: phs_data)
call phs_data%init (process_data, model)
phs_par%sqrts = 1000
select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%set_parameters (phs_par)
    phs_data%sqrts = phs_par%sqrts
    phs_data%par%sqrts = phs_par%sqrts
end select
call phs_data%compute_md5sum ()

write (u, "(1x,A,A,A)") "MD5 sum (process)      = '", &
    phs_data%md5sum_process, "'"
write (u, "(1x,A,A,A)") "MD5 sum (model par)   = '", &
    phs_data%md5sum_model_par, "'"
write (u, "(1x,A,A,A)") "MD5 sum (phs config) = '", &
    phs_data%md5sum_phs_config, "'"

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%read_phs_file (exist, found, match)
    write (u, "(1x,A,L1)") "exist = ", exist
    write (u, "(1x,A,L1)") "found = ", found
    write (u, "(1x,A,L1)") "match = ", match
end select

write (u, "(A)")
write (u, "(A)")  "* Modify sqrts and check MD5 sum"
write (u, "(A)")

call phs_data%final ()
deallocate (phs_data)
allocate (phs_wood_config_t :: phs_data)
call phs_data%init (process_data, model)
phs_par%sqrts = 500
select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%set_parameters (phs_par)
    phs_data%sqrts = phs_par%sqrts
    phs_data%par%sqrts = phs_par%sqrts
end select
call phs_data%compute_md5sum ()

write (u, "(1x,A,A,A)") "MD5 sum (process)      = '", &
    phs_data%md5sum_process, "'"
write (u, "(1x,A,A,A)") "MD5 sum (model par)   = '", &
    phs_data%md5sum_model_par, "'"
write (u, "(1x,A,A,A)") "MD5 sum (phs config) = '", &
    phs_data%md5sum_phs_config, "'"

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%read_phs_file (exist, found, match)

```



```

end select
call phs_data%compute_md5sum ()

write (u, "(1x,A,A,A)") "MD5 sum (process)    = '", &
    phs_data%md5sum_process, "'"
write (u, "(1x,A,A,A)") "MD5 sum (model par)  = '", &
    phs_data%md5sum_model_par, "'"
write (u, "(1x,A,A,A)") "MD5 sum (phs config) = '", &
    phs_data%md5sum_phs_config, "'"

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%read_phs_file (exist, found, match)
    write (u, "(1x,A,L1)") "exist = ", exist
    write (u, "(1x,A,L1)") "found = ", found
    write (u, "(1x,A,L1)") "match = ", match
end select

write (u, "(A)")
write (u, "(A)")  "* Modify model parameter and check MD5 sum"
write (u, "(A)")

call phs_data%final ()
deallocate (phs_data)
allocate (phs_wood_config_t :: phs_data)
call model%set_par (var_str ("ms"), 100._default)
call phs_data%init (process_data, model)
phs_par%sqrts = 1000
phs_par%off_shell = 1
select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%set_parameters (phs_par)
    phs_data%sqrts = phs_par%sqrts
    phs_data%par%sqrts = phs_par%sqrts
end select
call phs_data%compute_md5sum ()

write (u, "(1x,A,A,A)") "MD5 sum (process)    = '", &
    phs_data%md5sum_process, "'"
write (u, "(1x,A,A,A)") "MD5 sum (model par)  = '", &
    phs_data%md5sum_model_par, "'"
write (u, "(1x,A,A,A)") "MD5 sum (phs config) = '", &
    phs_data%md5sum_phs_config, "'"

select type (phs_data)
type is (phs_wood_config_t)
    call phs_data%read_phs_file (exist, found, match)
    write (u, "(1x,A,L1)") "exist = ", exist
    write (u, "(1x,A,L1)") "found = ", found
    write (u, "(1x,A,L1)") "match = ", match
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```



```

call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_6"

end subroutine phs_wood_6

```

(PHS wood: execute vis tests)≡

```

call test (phs_wood_vis_1, "phs_wood_vis_1", &
  "visualizing phase space channels", &
  u, results)

```

(PHS wood: tests)+≡

```

subroutine phs_wood_vis_1 (u)
  integer, intent(in) :: u
  type(os_data_t) :: os_data
  type(model_data_t), target :: model
  type(process_constants_t) :: process_data
  class(phs_config_t), allocatable :: phs_data
  type(mapping_defaults_t) :: mapping_defaults
  type(string_t) :: vis_file, pdf_file, ps_file
  real(default) :: sqrts
  logical :: exist, exist_pdf, exist_ps
  integer :: u_phs, iostat, u_vis
  character(95) :: buffer

  write (u, "(A)")  "* Test output: phs_wood_vis_1"
  write (u, "(A)")  "* Purpose: visualizing the &
    &phase-space configuration"
  write (u, "(A)")

  call os_data_init (os_data)
  call model%init_test ()

  call syntax_phs_forest_init ()

  write (u, "(A)")  "* Initialize a process"
  write (u, "(A)")

  call init_test_process_data (var_str ("phs_wood_vis_1"), process_data)

  write (u, "(A)")  "* Create a scratch phase-space file"
  write (u, "(A)")

  u_phs = free_unit ()
  open (u_phs, status = "scratch", action = "readwrite")
  call write_test_phs_file (u_phs, var_str ("phs_wood_vis_1"))
  rewind (u_phs)
  do
    read (u_phs, "(A)", iostat = iostat)  buffer
    if (iostat /= 0) exit
    write (u, "(A)") trim (buffer)
  end do

```

```

end do

write (u, "(A)")
write (u, "(A)")  "* Setup phase-space configuration object"
write (u, "(A)")

mapping_defaults%step_mapping = .false.

allocate (phs_wood_config_t :: phs_data)
call phs_data%init (process_data, model)
select type (phs_data)
type is (phs_wood_config_t)
  call phs_data%set_input (u_phs)
  call phs_data%set_mapping_defaults (mapping_defaults)
  phs_data%os_data = os_data
  phs_data%io_unit = 0
  phs_data%io_unit_keep_open = .true.
  phs_data%vis_channels = .true.
end select

sqrts = 1000._default
call phs_data%configure (sqrts)

call phs_data%write (u)
write (u, "(A)")

select type (phs_data)
type is (phs_wood_config_t)
  call phs_data%write_forest (u)
end select

vis_file = "phs_wood_vis_1_phs.tex"
ps_file  = "phs_wood_vis_1_phs.ps"
pdf_file = "phs_wood_vis_1_phs.pdf"
inquire (file = char (vis_file), exist = exist)
if (exist) then
  u_vis = free_unit ()
  open (u_vis, file = char (vis_file), action = "read", status = "old")
  iostat = 0
  do while (iostat == 0)
    read (u_vis, "(A)", iostat = iostat)  buffer
    if (iostat == 0) write (u, "(A)")  trim (buffer)
  end do
  close (u_vis)
else
  write (u, "(A)")  "[Visualize LaTeX file is missing]"
end if
inquire (file = char (ps_file), exist = exist_ps)
if (exist_ps) then
  write (u, "(A)")  "[Visualize Postscript file exists and is nonempty]"
else
  write (u, "(A)")  "[Visualize Postscript file is missing/non-regular]"
end if
inquire (file = char (pdf_file), exist = exist_pdf)

```

```

if (exist_pdf) then
    write (u, "(A)") "[Visualize PDF file exists and is nonempty]"
else
    write (u, "(A)") "[Visualize PDF file is missing/non-regular]"
end if

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

close (u_phs)
call phs_data%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: phs_wood_vis_1"

end subroutine phs_wood_vis_1

```

Chapter 19

Multi-Channel Integration

The abstract representation of multi-channel Monte Carlo algorithms for integration and event generation.

Module `mci_base`: The abstract types and their methods. It provides a test integrator that is referenced in later unit tests.

`iterations` Container for defining integration call and pass settings.

`integration_results` This module handles results from integrating processes. It records passes and iterations, calculates statistical averages, and provides the user output of integration results.

These are the implementations:

Module `mci_midpoint`: A simple integrator that uses the midpoint rule to sample the integrand uniformly over the unit hypercube. There is only one integration channel, so this can be matched only to single-channel phase space.

Module `mci_vamp`: Interface for the VAMP package.

19.1 Generic Integrator

This module provides a multi-channel integrator (MCI) base type, a corresponding configuration type, and methods for integration and event generation.

```
<mci_base.f90>≡  
<File header>  
  
module mci_base  
  
    use kinds  
<Use strings>  
    use io_units  
    use format_utils, only: pac_fmt  
    use format_defs, only: FMT_14, FMT_17  
    use unit_tests  
    use diagnostics  
    use cputime  
    use phs_base  
    use rng_base  
  
<Standard module head>  
  
<MCI base: public>  
  
<MCI base: types>  
  
<MCI base: interfaces>  
  
<MCI base: test types>  
  
contains  
  
<MCI base: procedures>  
  
<MCI base: tests>  
  
end module mci_base
```

19.1.1 MCI: integrator

The MCI object contains the methods for integration and event generation. For the actual work and data storage, it spawns an MCI instance object.

The base object contains the number of integration dimensions and the number of channels as configuration data. Further configuration data are stored in the concrete extensions.

The MCI sum contains all relevant information about the integrand. It can be used for comparing the current configuration against a previous one. If they match, we can skip an actual integration. (Implemented only for the VAMP version.)

There is a random-number generator (its state with associated methods) available as **rng**. It may or may not be used for integration. It will be used for

event generation.

```

<MCI base: public>≡
    public :: mci_t

<MCI base: types>≡
    type, abstract :: mci_t
        integer :: n_dim = 0
        integer :: n_channel = 0
        integer :: n_chain = 0
        integer, dimension(:), allocatable :: chain
        real(default), dimension(:), allocatable :: chain_weights
        character(32) :: md5sum = ""
        logical :: integral_known = .false.
        logical :: error_known = .false.
        logical :: efficiency_known = .false.
        real(default) :: integral = 0
        real(default) :: error = 0
        real(default) :: efficiency = 0
        logical :: use_timer = .false.
        type(timer_t) :: timer
        class(rng_t), allocatable :: rng
    contains
        <MCI base: mci: TBP>
    end type mci_t

```

Finalizer: the random-number generator may need one.

```

<MCI base: mci: TBP>≡
    procedure :: base_final => mci_final
    procedure (mci_final), deferred :: final

<MCI base: procedures>≡
    subroutine mci_final (object)
        class(mci_t), intent(inout) :: object
        if (allocated (object%rng)) call object%rng%final ()
    end subroutine mci_final

```

Output: basic and extended output.

```

<MCI base: mci: TBP>+≡
    procedure :: base_write => mci_write
    procedure (mci_write), deferred :: write

<MCI base: procedures>+≡
    subroutine mci_write (object, unit, pacify, md5sum_version)
        class(mci_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: pacify
        logical, intent(in), optional :: md5sum_version
        logical :: md5sum_ver
        integer :: u, i, j
        character(len=7) :: fmt
        call pac_fmt (fmt, FMT_17, FMT_14, pacify)
        u = given_output_unit (unit)
        md5sum_ver = .false.
        if (present (md5sum_version)) md5sum_ver = md5sum_version

```

```

if (object%use_timer .and. .not. md5sum_ver) then
  write (u, "(2x)", advance="no")
  call object%timer%write (u)
end if
if (object%integral_known) then
  write (u, "(3x,A," // fmt // ")") &
    "Integral          = ", object%integral
end if
if (object%error_known) then
  write (u, "(3x,A," // fmt // ")") &
    "Error            = ", object%error
end if
if (object%efficiency_known) then
  write (u, "(3x,A," // fmt // ")") &
    "Efficiency       = ", object%efficiency
end if
write (u, "(3x,A,I0)") "Number of channels = ", object%n_channel
write (u, "(3x,A,I0)") "Number of dimensions = ", object%n_dim
if (object%n_chain > 0) then
  write (u, "(3x,A,I0)") "Number of chains = ", object%n_chain
  write (u, "(3x,A)") "Chains:"
  do i = 1, object%n_chain
    write (u, "(5x,I0,':')", advance = "no") i
    do j = 1, object%n_channel
      if (object%chain(j) == i) &
        write (u, "(1x,I0)", advance = "no") j
    end do
    write (u, "(A)")
  end do
end if
end subroutine mci_write

```

Print an informative message when starting integration.

<MCI base: mci: TBP>+≡

```

procedure (mci_startup_message), deferred :: startup_message
procedure :: base_startup_message => mci_startup_message

```

<MCI base: procedures>+≡

```

subroutine mci_startup_message (mci, unit, n_calls)
  class(mci_t), intent(in) :: mci
  integer, intent(in), optional :: unit, n_calls
  if (mci%n_chain > 0) then
    write (msg_buffer, "(A,3(1x,I0,1x,A))") &
      "Integrator:", mci%n_chain, "chains,", &
      mci%n_channel, "channels,", &
      mci%n_dim, "dimensions"
  else
    write (msg_buffer, "(A,3(1x,I0,1x,A))") &
      "Integrator:", &
      mci%n_channel, "channels,", &
      mci%n_dim, "dimensions"
  end if
  call msg_message (unit = unit)
end subroutine mci_startup_message

```

Record the index of the MCI object within a process. For multi-component processes with more than one integrator, the integrator should know about its own index, so file names can be unique, etc. The default implementation does nothing, however.

```

<MCI base: mci: TBP>+≡
  procedure :: record_index => mci_record_index
<MCI base: procedures>+≡
  subroutine mci_record_index (mci, i_mci)
    class(mci_t), intent(inout) :: mci
    integer, intent(in) :: i_mci
  end subroutine mci_record_index

```

There is no Initializer for the abstract type, but a generic setter for the number of channels and dimensions. We make two aliases available, to be able to override it.

```

<MCI base: mci: TBP>+≡
  procedure :: set_dimensions => mci_set_dimensions
  procedure :: base_set_dimensions => mci_set_dimensions
<MCI base: procedures>+≡
  subroutine mci_set_dimensions (mci, n_dim, n_channel)
    class(mci_t), intent(inout) :: mci
    integer, intent(in) :: n_dim
    integer, intent(in) :: n_channel
    mci%n_dim = n_dim
    mci%n_channel = n_channel
  end subroutine mci_set_dimensions

```

Declare particular dimensions as flat. This information can be used to simplify integration. When generating events, the flat dimensions should be sampled with uniform and uncorrelated distribution. It depends on the integrator what to do with that information.

```

<MCI base: mci: TBP>+≡
  procedure (mci_declare_flat_dimensions), deferred :: declare_flat_dimensions
<MCI base: interfaces>≡
  abstract interface
    subroutine mci_declare_flat_dimensions (mci, dim_flat)
      import
      class(mci_t), intent(inout) :: mci
      integer, dimension(:), intent(in) :: dim_flat
    end subroutine mci_declare_flat_dimensions
  end interface

```

Declare particular channels as equivalent, possibly allowing for permutations or reflections of dimensions. We use the information stored in the `phs_channel_t` object array that the phase-space module provides.

(We do not test this here, deferring the unit test to the `mci_vamp` implementation where we actually use this feature.)

```

<MCI base: mci: TBP>+≡
  procedure (mci_declare_equivalences), deferred :: declare_equivalences

```



```

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_declare_equivalences (mci, channel, dim_offset)
      import
      class(mci_t), intent(inout) :: mci
      type(phas_channel_t), dimension(:), intent(in) :: channel
      integer, intent(in) :: dim_offset
    end subroutine mci_declare_equivalences
  end interface

```

Declare particular channels as chained together. The implementation may use this array for keeping their weights equal to each other, etc.

The chain array is an array sized by the number of channels. For each channel, there is an integer entry that indicates the corresponding chains. The total number of chains is the maximum value of this entry.

```

<MCI base: mci: TBP>+≡
  procedure :: declare_chains => mci_declare_chains

<MCI base: procedures>+≡
  subroutine mci_declare_chains (mci, chain)
    class(mci_t), intent(inout) :: mci
    integer, dimension(:), intent(in) :: chain
    allocate (mci%chain (size (chain)))
    mci%n_chain = maxval (chain)
    allocate (mci%chain_weights (mci%n_chain), source = 0._default)
    mci%chain = chain
  end subroutine mci_declare_chains

```

Collect channel weights according to chains and store them in the `chain_weights` for output. We sum up the weights for all channels that share the same `chain` index and store the results in the `chain_weights` array.

```

<MCI base: mci: TBP>+≡
  procedure :: collect_chain_weights => mci_collect_chain_weights

<MCI base: procedures>+≡
  subroutine mci_collect_chain_weights (mci, weight)
    class(mci_t), intent(inout) :: mci
    real(default), dimension(:), intent(in) :: weight
    integer :: i, c
    if (allocated (mci%chain)) then
      mci%chain_weights = 0
      do i = 1, size (mci%chain)
        c = mci%chain(i)
        mci%chain_weights(c) = mci%chain_weights(c) + weight(i)
      end do
    end if
  end subroutine mci_collect_chain_weights

```

Check if there are chains.

```

<MCI base: mci: TBP>+≡
  procedure :: has_chains => mci_has_chains

```

```

<MCI base: procedures>+≡
function mci_has_chains (mci) result (flag)
  class(mci_t), intent(in) :: mci
  logical :: flag
  flag = allocated (mci%chain)
end function mci_has_chains

```

Output of the chain weights, kept separate from the main `write` method.
 [The formatting will work as long as the number of chains is less than 10^{10} ...]

```

<MCI base: mci: TBP>+≡
  procedure :: write_chain_weights => mci_write_chain_weights

<MCI base: procedures>+≡
  subroutine mci_write_chain_weights (mci, unit)
    class(mci_t), intent(in) :: mci
    integer, intent(in), optional :: unit
    integer :: u, i, n, n_digits
    character(4) :: ifmt
    u = given_output_unit (unit)
    if (allocated (mci%chain_weights)) then
      write (u, "(1x,A)") "Weights of channel chains (groves):"
      n_digits = 0
      n = size (mci%chain_weights)
      do while (n > 0)
        n = n / 10
        n_digits = n_digits + 1
      end do
      write (ifmt, "(A1,I1)") "I", n_digits
      do i = 1, size (mci%chain_weights)
        write (u, "(3x," // ifmt // ",F13.10)") i, mci%chain_weights(i)
      end do
    end if
  end subroutine mci_write_chain_weights

```

Set the MD5 sum, independent of initialization.

```

<MCI base: mci: TBP>+≡
  procedure :: set_md5sum => mci_set_md5sum

<MCI base: procedures>+≡
  subroutine mci_set_md5sum (mci, md5sum)
    class(mci_t), intent(inout) :: mci
    character(32), intent(in) :: md5sum
    mci%md5sum = md5sum
  end subroutine mci_set_md5sum

```

Initialize a new integration pass. This is not necessarily meaningful, so we provide an empty base method. The `mci_vamp` implementation overrides this.

```

<MCI base: mci: TBP>+≡
  procedure :: add_pass => mci_add_pass

<MCI base: procedures>+≡
  subroutine mci_add_pass (mci, adapt_grids, adapt_weights, final)
    class(mci_t), intent(inout) :: mci

```

```

    logical, intent(in), optional :: adapt_grids
    logical, intent(in), optional :: adapt_weights
    logical, intent(in), optional :: final
end subroutine mci_add_pass

```

Allocate an instance with matching type. This must be deferred.

```

<MCI base: mci: TBP>+≡
    procedure (mci_allocate_instance), deferred :: allocate_instance

<MCI base: interfaces>+≡
    abstract interface
        subroutine mci_allocate_instance (mci, mci_instance)
            import
            class(mci_t), intent(in) :: mci
            class(mci_instance_t), intent(out), pointer :: mci_instance
        end subroutine mci_allocate_instance
    end interface

```

Import a random-number generator. We transfer the allocation of an existing generator state into the object. The generator state may already be initialized, or we can reset it by its `init` method.

```

<MCI base: mci: TBP>+≡
    procedure :: import_rng => mci_import_rng

<MCI base: procedures>+≡
    subroutine mci_import_rng (mci, rng)
        class(mci_t), intent(inout) :: mci
        class(rng_t), intent(inout), allocatable :: rng
        call move_alloc (rng, mci%rng)
    end subroutine mci_import_rng

```

Activate or deactivate the timer.

```

<MCI base: mci: TBP>+≡
    procedure :: set_timer => mci_set_timer

<MCI base: procedures>+≡
    subroutine mci_set_timer (mci, active)
        class(mci_t), intent(inout) :: mci
        logical, intent(in) :: active
        mci%use_timer = active
    end subroutine mci_set_timer

```

Start and stop signal for the timer, if active. The elapsed time can then be retrieved from the MCI record.

```

<MCI base: mci: TBP>+≡
    procedure :: start_timer => mci_start_timer
    procedure :: stop_timer => mci_stop_timer

<MCI base: procedures>+≡
    subroutine mci_start_timer (mci)
        class(mci_t), intent(inout) :: mci
        if (mci%use_timer) call mci%timer%start ()
    end subroutine mci_start_timer

```

```

subroutine mci_stop_timer (mci)
  class(mci_t), intent(inout) :: mci
  if (mci%use_timer) call mci%timer%stop ()
end subroutine mci_stop_timer

```

Sampler test. Evaluate the sampler a given number of times. Results are discarded, so we don't need the MCI instance which would record them.

The evaluation channel is iterated, and the x parameters are randomly chosen.

```

<MCI base: mci: TBP>+≡
  procedure :: sampler_test => mci_sampler_test

<MCI base: procedures>+≡
  subroutine mci_sampler_test (mci, sampler, n_calls)
    class(mci_t), intent(inout) :: mci
    class(mci_sampler_t), intent(inout), target :: sampler
    integer, intent(in) :: n_calls
    real(default), dimension(:), allocatable :: x_in, f
    real(default), dimension(:,:), allocatable :: x_out
    real(default) :: val
    integer :: i, c
    allocate (x_in (mci%n_dim))
    allocate (f (mci%n_channel))
    allocate (x_out (mci%n_dim, mci%n_channel))
    do i = 1, n_calls
      c = mod (i, mci%n_channel) + 1
      call mci%rng%generate_array (x_in)
      call sampler%evaluate (c, x_in, val, x_out, f)
    end do
  end subroutine mci_sampler_test

```

Integrate: this depends on the implementation. We foresee a pacify flag to take care of small numerical noise on different platforms.

```

<MCI base: mci: TBP>+≡
  procedure (mci_integrate), deferred :: integrate

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_integrate (mci, instance, sampler, &
      n_it, n_calls, results, pacify)
      import
      class(mci_t), intent(inout) :: mci
      class(mci_instance_t), intent(inout) :: instance
      class(mci_sampler_t), intent(inout) :: sampler
      integer, intent(in) :: n_it
      integer, intent(in) :: n_calls
      logical, intent(in), optional :: pacify
      class(mci_results_t), intent(inout), optional :: results
    end subroutine mci_integrate
  end interface

```

Event generation. Depending on the implementation, event generation may or may not require a previous integration pass.

Instead of a black-box **simulate** method, we require an initializer, a finalizer, and procedures for generating a single event. This allows us to interface simulation event by event from the outside, and it facilitates the further processing of an event after successful generation. For integration, this is not necessary.

The initializer has **intent(inout)** for the **mci** passed object. The reason is that the initializer can read integration results and grids from file, where the results can modify the **mci** record.

```

<MCI base: mci: TBP>+≡
  procedure (mci_prepare_simulation), deferred :: prepare_simulation
<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_prepare_simulation (mci)
      import
      class(mci_t), intent(inout) :: mci
    end subroutine mci_prepare_simulation
  end interface

```

The generated event will reside in in the **instance** object (overall results and weight) and in the **sampler** object (detailed data). In the real application, we can subsequently call methods of the **sampler** in order to further process the generated event.

The **target** attributes are required by the VAMP implementation, which uses pointers to refer to the instance and sampler objects from within the integration function.

```

<MCI base: mci: TBP>+≡
  procedure (mci_generate), deferred :: generate_weighted_event
  procedure (mci_generate), deferred :: generate_unweighted_event
<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_generate (mci, instance, sampler)
      import
      class(mci_t), intent(inout) :: mci
      class(mci_instance_t), intent(inout), target :: instance
      class(mci_sampler_t), intent(inout), target :: sampler
    end subroutine mci_generate
  end interface

```

This is analogous, but we rebuild the event from the information stored in **state** instead of generating it.

Note: currently unused outside of tests, might be deleted later.

```

<MCI base: mci: TBP>+≡
  procedure (mci_rebuild), deferred :: rebuild_event
<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_rebuild (mci, instance, sampler, state)
      import
      class(mci_t), intent(inout) :: mci
      class(mci_instance_t), intent(inout) :: instance

```

```

        class(mci_sampler_t), intent(inout) :: sampler
        class(mci_state_t), intent(in) :: state
    end subroutine mci_rebuild
end interface

```

Return the value of the integral, error, efficiency, and time per call.

(MCI base: mci: TBP)+≡

```

    procedure :: get_integral => mci_get_integral
    procedure :: get_error => mci_get_error
    procedure :: get_efficiency => mci_get_efficiency
    procedure :: get_time => mci_get_time

```

(MCI base: procedures)+≡

```

function mci_get_integral (mci) result (integral)
    class(mci_t), intent(in) :: mci
    real(default) :: integral
    if (mci%integral_known) then
        integral = mci%integral
    else
        call msg_bug ("The integral is unknown. This is presumably a" // &
            "WHIZARD bug.")
    end if
end function mci_get_integral

function mci_get_error (mci) result (error)
    class(mci_t), intent(in) :: mci
    real(default) :: error
    if (mci%error_known) then
        error = mci%error
    else
        error = 0
    end if
end function mci_get_error

function mci_get_efficiency (mci) result (efficiency)
    class(mci_t), intent(in) :: mci
    real(default) :: efficiency
    if (mci%efficiency_known) then
        efficiency = mci%efficiency
    else
        efficiency = 0
    end if
end function mci_get_efficiency

function mci_get_time (mci) result (time)
    class(mci_t), intent(in) :: mci
    real(default) :: time
    if (mci%use_timer) then
        time = mci%timer
    else
        time = 0
    end if
end function mci_get_time

```

Return the MD5 sum of the configuration. This may be overridden in an extension, to return a different MD5 sum.

```

<MCI base: mci: TBP>+≡
  procedure :: get_md5sum => mci_get_md5sum

<MCI base: procedures>+≡
  function mci_get_md5sum (mci) result (md5sum)
    class(mci_t), intent(in) :: mci
    character(32) :: md5sum
    md5sum = mci%md5sum
  end function mci_get_md5sum

```

19.1.2 MCI instance

The base type contains an array of channel weights. The value `mci_weight` is the combined MCI weight that corresponds to a particular sampling point.

For convenience, we also store the `x` and Jacobian values for this sampling point.

```

<MCI base: public>+≡
  public :: mci_instance_t

<MCI base: types>+≡
  type, abstract :: mci_instance_t
    logical :: valid = .false.
    real(default), dimension(:), allocatable :: w
    real(default), dimension(:), allocatable :: f
    real(default), dimension(:,:), allocatable :: x
    integer :: selected_channel = 0
    real(default) :: mci_weight = 0
    real(default) :: integrand = 0
  contains
    <MCI base: mci instance: TBP>
  end type mci_instance_t

```

Output: deferred

```

<MCI base: mci instance: TBP>≡
  procedure (mci_instance_write), deferred :: write

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_instance_write (object, unit, pacify)
      import
      class(mci_instance_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: pacify
    end subroutine mci_instance_write
  end interface

```

A finalizer, just in case.

```

<MCI base: mci instance: TBP>+≡
  procedure (mci_instance_final), deferred :: final

```

```

<MCI base: interfaces>+=
  abstract interface
    subroutine mci_instance_final (object)
      import
      class(mci_instance_t), intent(inout) :: object
    end subroutine mci_instance_final
  end interface

```

Init: basic initializer for the arrays, otherwise deferred. Assigning the `mci` object is also deferred, because it depends on the concrete type.

The weights are initialized with an uniform normalized value.

```

<MCI base: mci instance: TBP>+=
  procedure (mci_instance_base_init), deferred :: init
  procedure :: base_init => mci_instance_base_init

<MCI base: procedures>+=
  subroutine mci_instance_base_init (mci_instance, mci)
    class(mci_instance_t), intent(out) :: mci_instance
    class(mci_t), intent(in), target :: mci
    allocate (mci_instance%w (mci%n_channel))
    allocate (mci_instance%f (mci%n_channel))
    allocate (mci_instance%x (mci%n_dim, mci%n_channel))
    if (size (mci_instance%w) /= 0) then
      mci_instance%w = 1._default / size (mci_instance%w)
    end if
    mci_instance%f = 0
    mci_instance%x = 0
  end subroutine mci_instance_base_init

```

Compute the overall weight factor for a configuration of x values and Jacobians f . The x values come in `n_channel` rows with `n_dim` entries each. The f factors constitute an array with `n_channel` entries.

We assume that the x and f arrays are already stored inside the MC instance. The result is also stored there.

```

<MCI base: mci instance: TBP>+=
  procedure (mci_instance_compute_weight), deferred :: compute_weight

<MCI base: interfaces>+=
  abstract interface
    subroutine mci_instance_compute_weight (mci, c)
      import
      class(mci_instance_t), intent(inout) :: mci
      integer, intent(in) :: c
    end subroutine mci_instance_compute_weight
  end interface

```

Record the integrand as returned by the sampler. Depending on the implementation, this may merely copy the value, or do more complicated things.

We may need the MCI weight for the actual computations, so this should be called after the previous routine.

```

<MCI base: mci instance: TBP>+=
  procedure (mci_instance_record_integrand), deferred :: record_integrand

```



```

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_instance_record_integrand (mci, integrand)
      import
      class(mci_instance_t), intent(inout) :: mci
      real(default), intent(in) :: integrand
    end subroutine mci_instance_record_integrand
  end interface

```

Sample a point directly: evaluate the sampler, then compute the weight and the weighted integrand. Finally, record the integrand within the MCI instance.

If a signal (interrupt) was raised recently, we abort the calculation before entering the sampler. Thus, a previous calculation will have completed and any data are already recorded, but any new point can be discarded. If the `abort` flag is present, we may delay the interrupt, so we can do some cleanup.

```

<MCI base: mci instance: TBP>+≡
  procedure :: evaluate => mci_instance_evaluate

<MCI base: procedures>+≡
  subroutine mci_instance_evaluate (mci, sampler, c, x)
    class(mci_instance_t), intent(inout) :: mci
    class(mci_sampler_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x
    real(default) :: val
    call sampler%evaluate (c, x, val, mci%x, mci%f)
    mci%valid = sampler%is_valid ()
    if (mci%valid) then
      call mci%compute_weight (c)
      call mci%record_integrand (val)
    end if
  end subroutine mci_instance_evaluate

```

Initiate and terminate simulation. In contrast to integration, we implement these as methods of the process instance, since the `mci` configuration object is unchanged.

The safety factor reduces the acceptance probability for unweighted events. The implementation of this feature depends on the concrete type.

```

<MCI base: mci instance: TBP>+≡
  procedure (mci_instance_init_simulation), deferred :: init_simulation
  procedure (mci_instance_final_simulation), deferred :: final_simulation

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_instance_init_simulation (instance, safety_factor)
      import
      class(mci_instance_t), intent(inout) :: instance
      real(default), intent(in), optional :: safety_factor
    end subroutine mci_instance_init_simulation
  end interface

  abstract interface
    subroutine mci_instance_final_simulation (instance)

```

```

import
class(mci_instance_t), intent(inout) :: instance
end subroutine mci_instance_final_simulation
end interface

```

Assuming that the sampler is in a completely defined state, just extract the data that `evaluate` would compute. Also record the integrand.

```

⟨MCI base: mci instance: TBP⟩+≡
  procedure :: fetch => mci_instance_fetch
⟨MCI base: procedures⟩+≡
  subroutine mci_instance_fetch (mci, sampler, c)
    class(mci_instance_t), intent(inout) :: mci
    class(mci_sampler_t), intent(in) :: sampler
    integer, intent(in) :: c
    real(default) :: val
    mci%valid = sampler%is_valid ()
    if (mci%valid) then
      call sampler%fetch (val, mci%x, mci%f)
      call mci%compute_weight (c)
      call mci%record_integrand (val)
    end if
  end subroutine mci_instance_fetch

```

The value, i.e., the weighted integrand, is the integrand (which should be taken as-is from the sampler) multiplied by the MCI weight.

```

⟨MCI base: mci instance: TBP⟩+≡
  procedure :: get_value => mci_instance_get_value
⟨MCI base: procedures⟩+≡
  function mci_instance_get_value (mci) result (value)
    class(mci_instance_t), intent(in) :: mci
    real(default) :: value
    if (mci%valid) then
      value = mci%integrand * mci%mci_weight
    else
      value = 0
    end if
  end function mci_instance_get_value

```

This is an extra routine. By default, the event weight is equal to the value returned by the previous routine. However, if we select a channel for event generation not just based on the channel weights, the event weight has to account for this bias, so the event weight that applies to event generation is different. In that case, we should override the default routine.

```

⟨MCI base: mci instance: TBP⟩+≡
  procedure :: get_event_weight => mci_instance_get_value

```

Excess weight can occur during unweighted event generation, if the assumed maximum value of the integrand is too small. This excess should be normalized in the same way as the event weight above (which for unweighted events becomes unity).

```

⟨MCI base: mci instance: TBP⟩+≡
  procedure (mci_instance_get_event_excess), deferred :: get_event_excess

```

```

<MCI base: interfaces>+≡
  abstract interface
    function mci_instance_get_event_excess (mci) result (excess)
      import
        class(mci_instance_t), intent(in) :: mci
        real(default) :: excess
    end function mci_instance_get_event_excess
  end interface

```

19.1.3 MCI state

This object can hold the relevant information that allows us to reconstruct the MCI instance without re-evaluating the sampler completely.

We store the `x_in` MC input parameter set, which coincides with the section of the complete `x` array that belongs to a particular channel. We also store the MC function value. When we want to reconstruct the state, we can use the input array to recover the complete `x` and `f` arrays (i.e., the kinematics), but do not need to recompute the MC function value (the dynamics).

The `mci_state_t` may be extended, to allow storing/recalling more information. In that case, we would override the type-bound procedures. However, the base type is also a concrete type and self-contained.

```

<MCI base: public>+≡
  public :: mci_state_t

<MCI base: types>+≡
  type :: mci_state_t
    integer :: selected_channel = 0
    real(default), dimension(:), allocatable :: x_in
    real(default) :: val
  contains
    <MCI base: mci state: TBP>
  end type mci_state_t

```

Output:

```

<MCI base: mci state: TBP>≡
  procedure :: write => mci_state_write

<MCI base: procedures>+≡
  subroutine mci_state_write (object, unit)
    class(mci_state_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "MCI state:"
    write (u, "(3x,A,I0)") "Channel   = ", object%selected_channel
    write (u, "(3x,A,999(1x,F12.10))") "x (in)     =", object%x_in
    write (u, "(3x,A,ES19.12)") "Integrand = ", object%val
  end subroutine mci_state_write

```

To store the object, we take the relevant section of the `x` array. The channel used for storing data is taken from the `instance` object, but it could be arbitrary in principle.

```

(MCI base: mci instance: TBP)+≡
  procedure :: store => mci_instance_store

(MCI base: procedures)+≡
  subroutine mci_instance_store (mci, state)
    class(mci_instance_t), intent(in) :: mci
    class(mci_state_t), intent(out) :: state
    state%selected_channel = mci%selected_channel
    allocate (state%x_in (size (mci%x, 1)))
    state%x_in = mci%x(:,mci%selected_channel)
    state%val = mci%integrand
  end subroutine mci_instance_store

```

Recalling the state, we must consult the sampler in order to fully reconstruct the `x` and `f` arrays. The integrand value is known, and we also give it to the sampler, bypassing evaluation.

The final steps are equivalent to the `evaluate` method above.

```

(MCI base: mci instance: TBP)+≡
  procedure :: recall => mci_instance_recall

(MCI base: procedures)+≡
  subroutine mci_instance_recall (mci, sampler, state)
    class(mci_instance_t), intent(inout) :: mci
    class(mci_sampler_t), intent(inout) :: sampler
    class(mci_state_t), intent(in) :: state
    if (size (state%x_in) == size (mci%x, 1) &
        .and. state%selected_channel <= size (mci%x, 2)) then
      call sampler%rebuild (state%selected_channel, &
        state%x_in, state%val, mci%x, mci%f)
      call mci%compute_weight (state%selected_channel)
      call mci%record_integrand (state%val)
    else
      call msg_fatal ("Recalling event: mismatch in channel or dimension")
    end if
  end subroutine mci_instance_recall

```

19.1.4 MCI sampler

A sampler is an object that implements a multi-channel parameterization of the unit hypercube. Specifically, it is able to compute, given a channel and a set of x MC parameter values, a the complete set of x values and associated Jacobian factors f for all channels.

Furthermore, the sampler should return a single real value, the integrand, for the given point in the hypercube.

It must implement a method `evaluate` for performing the above computations.

```

(MCI base: public)+≡
  public :: mci_sampler_t

```

```

<MCI base: types>+≡
  type, abstract :: mci_sampler_t
  contains
    <MCI base: mci_sampler: TBP>
  end type mci_sampler_t

```

Output, deferred to the implementation.

```

<MCI base: mci_sampler: TBP>≡
  procedure (mci_sampler_write), deferred :: write

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_sampler_write (object, unit, testflag)
      import
      class(mci_sampler_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: testflag
    end subroutine mci_sampler_write
  end interface

```

The evaluation routine. Input is the channel index *c* and the one-dimensional parameter array *x_in*. Output are the integrand value *val*, the two-dimensional parameter array *x* and the Jacobian array *f*.

```

<MCI base: mci_sampler: TBP>+≡
  procedure (mci_sampler_evaluate), deferred :: evaluate

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_sampler_evaluate (sampler, c, x_in, val, x, f)
      import
      class(mci_sampler_t), intent(inout) :: sampler
      integer, intent(in) :: c
      real(default), dimension(:), intent(in) :: x_in
      real(default), intent(out) :: val
      real(default), dimension(:, :), intent(out) :: x
      real(default), dimension(:), intent(out) :: f
    end subroutine mci_sampler_evaluate
  end interface

```

Query the validity of the sampling point. Can be called after *evaluate*.

```

<MCI base: mci_sampler: TBP>+≡
  procedure (mci_sampler_is_valid), deferred :: is_valid

<MCI base: interfaces>+≡
  abstract interface
    function mci_sampler_is_valid (sampler) result (valid)
      import
      class(mci_sampler_t), intent(in) :: sampler
      logical :: valid
    end function mci_sampler_is_valid
  end interface

```

The shortcut. Again, the channel index `c` and the parameter array `x_in` are input. However, we also provide the integrand value `val`, and we just require that the complete parameter array `x` and Jacobian array `f` are recovered.

```

<MCI base: mci_sampler: TBP>+≡
  procedure (mci_sampler_rebuild), deferred :: rebuild

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_sampler_rebuild (sampler, c, x_in, val, x, f)
      import
      class(mci_sampler_t), intent(inout) :: sampler
      integer, intent(in) :: c
      real(default), dimension(:), intent(in) :: x_in
      real(default), intent(in) :: val
      real(default), dimension(:, :), intent(out) :: x
      real(default), dimension(:), intent(out) :: f
    end subroutine mci_sampler_rebuild
  end interface

```

This routine should extract the important data from a sampler that has been filled by other means. We fetch the integrand value `val`, the two-dimensional parameter array `x` and the Jacobian array `f`.

```

<MCI base: mci_sampler: TBP>+≡
  procedure (mci_sampler_fetch), deferred :: fetch

<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_sampler_fetch (sampler, val, x, f)
      import
      class(mci_sampler_t), intent(in) :: sampler
      real(default), intent(out) :: val
      real(default), dimension(:, :), intent(out) :: x
      real(default), dimension(:), intent(out) :: f
    end subroutine mci_sampler_fetch
  end interface

```

19.1.5 Results record

This is an abstract type which allows us to implement callback: each integration results can optionally be recorded to an instance of this object. The actual object may store a new result, average results, etc. It may also display a result on-line or otherwise, whenever the `record` method is called.

```

<MCI base: public>+≡
  public :: mci_results_t

<MCI base: types>+≡
  type, abstract :: mci_results_t
    contains
    <MCI base: mci_results: TBP>
  end type mci_results_t

```

The output routine is deferred. We provide an extra `verbose` flag, which could serve any purpose.

```

<MCI base: mci_results: TBP>≡
  procedure (mci_results_write), deferred :: write
<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_results_write (object, unit, verbose, suppress)
      import
      class(mci_results_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: verbose, suppress
    end subroutine mci_results_write
  end interface

```

This is the `record` method, which can be called directly from the integrator.

```

<MCI base: mci_results: TBP>+≡
  procedure (mci_results_record), deferred :: record
<MCI base: interfaces>+≡
  abstract interface
    subroutine mci_results_record (object, n_it, &
      n_calls, integral, error, efficiency, chain_weights, suppress)
      import
      class(mci_results_t), intent(inout) :: object
      integer, intent(in) :: n_it
      integer, intent(in) :: n_calls
      real(default), intent(in) :: integral
      real(default), intent(in) :: error
      real(default), intent(in) :: efficiency
      real(default), dimension(:), intent(in), optional :: chain_weights
      logical, intent(in), optional :: suppress
    end subroutine mci_results_record
  end interface

```

19.1.6 Unit tests

```

<MCI base: public>+≡
  public :: mci_base_test
<MCI base: tests>≡
  subroutine mci_base_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <MCI base: execute tests>
  end subroutine mci_base_test

```

Test implementation of the configuration type

The concrete type contains the number of requested calls and the integral result, to be determined.

The `max_factor` entry is set for the actual test integration, where the integrand is not unity but some other constant value. This value should be set here, such that the actual maximum of the integrand is known when vetoing unweighted events.

```

<MCI base: public>+≡
    public :: mci_test_t

<MCI base: test types>≡
    type, extends (mci_t) :: mci_test_t
        integer :: divisions = 0
        integer :: tries = 0
        real(default) :: max_factor = 1
    contains
        procedure :: final => mci_test_final
        procedure :: write => mci_test_write
        procedure :: startup_message => mci_test_startup_message
        procedure :: declare_flat_dimensions => mci_test_ignore_flat_dimensions
        procedure :: declare_equivalences => mci_test_ignore_equivalences
        procedure :: set_divisions => mci_test_set_divisions
        procedure :: set_max_factor => mci_test_set_max_factor
        procedure :: allocate_instance => mci_test_allocate_instance
        procedure :: integrate => mci_test_integrate
        procedure :: prepare_simulation => mci_test_ignore_prepare_simulation
        procedure :: generate_weighted_event => mci_test_generate_weighted_event
        procedure :: generate_unweighted_event => &
            mci_test_generate_unweighted_event
        procedure :: rebuild_event => mci_test_rebuild_event
    end type mci_test_t

```

Finalizer: base version is sufficient

```

<MCI base: tests>+≡
    subroutine mci_test_final (object)
        class(mci_test_t), intent(inout) :: object
        call object%base_final ()
    end subroutine mci_test_final

```

Output: trivial

```

<MCI base: tests>+≡
    subroutine mci_test_write (object, unit, pacify, md5sum_version)
        class(mci_test_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: pacify
        logical, intent(in), optional :: md5sum_version
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Test integrator:"
        call object%base_write (u, pacify, md5sum_version)
        if (object%divisions /= 0) then
            write (u, "(3x,A,I0)") "Number of divisions = ", object%divisions
        end if
        if (allocated (object%rng)) call object%rng%write (u)
    end subroutine mci_test_write

```


Short version.

```
<MCI base: tests>+≡
subroutine mci_test_startup_message (mci, unit, n_calls)
  class(mci_test_t), intent(in) :: mci
  integer, intent(in), optional :: unit, n_calls
  call mci%base_startup_message (unit = unit, n_calls = n_calls)
  write (msg_buffer, "(A,1x,I0,1x,A)") &
    "Integrator: Test:", mci%divisions, "divisions"
  call msg_message (unit = unit)
end subroutine mci_test_startup_message
```

This is a no-op for the test integrator.

```
<MCI base: tests>+≡
subroutine mci_test_ignore_flat_dimensions (mci, dim_flat)
  class(mci_test_t), intent(inout) :: mci
  integer, dimension(:), intent(in) :: dim_flat
end subroutine mci_test_ignore_flat_dimensions
```

Ditto.

```
<MCI base: tests>+≡
subroutine mci_test_ignore_equivalences (mci, channel, dim_offset)
  class(mci_test_t), intent(inout) :: mci
  type(phs_channel_t), dimension(:), intent(in) :: channel
  integer, intent(in) :: dim_offset
end subroutine mci_test_ignore_equivalences
```

Set the number of divisions to a nonzero value.

```
<MCI base: tests>+≡
subroutine mci_test_set_divisions (object, divisions)
  class(mci_test_t), intent(inout) :: object
  integer, intent(in) :: divisions
  object%divisions = divisions
end subroutine mci_test_set_divisions
```

Set the maximum factor (default is 1).

```
<MCI base: tests>+≡
subroutine mci_test_set_max_factor (object, max_factor)
  class(mci_test_t), intent(inout) :: object
  real(default), intent(in) :: max_factor
  object%max_factor = max_factor
end subroutine mci_test_set_max_factor
```

Allocate instance with matching type.

```
<MCI base: tests>+≡
subroutine mci_test_allocate_instance (mci, mci_instance)
  class(mci_test_t), intent(in) :: mci
  class(mci_instance_t), intent(out), pointer :: mci_instance
  allocate (mci_test_instance_t :: mci_instance)
end subroutine mci_test_allocate_instance
```

Integrate: sample at the midpoints of uniform bits and add the results. We implement this for one and for two dimensions. In the latter case, we scan over two channels and multiply with the channel weights.

The arguments `n_it` and `n_calls` are ignored in this implementations.

The test integrator does not set error or efficiency, so those will remain undefined.

```

(MCI base: tests)+≡
subroutine mci_test_integrate (mci, instance, sampler, &
    n_it, n_calls, results, pacify)
    class(mci_test_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout) :: instance
    class(mci_sampler_t), intent(inout) :: sampler
    integer, intent(in) :: n_it
    integer, intent(in) :: n_calls
    logical, intent(in), optional :: pacify
    class(mci_results_t), intent(inout), optional :: results
    real(default), dimension(:), allocatable :: integral
    real(default), dimension(:), allocatable :: x
    integer :: i, j, c
    select type (instance)
    type is (mci_test_instance_t)
        allocate (integral (mci%n_channel))
        integral = 0
        allocate (x (mci%n_dim))
        select case (mci%n_dim)
        case (1)
            do c = 1, mci%n_channel
                do i = 1, mci%divisions
                    x(1) = (i - 0.5_default) / mci%divisions
                    call instance%evaluate (sampler, c, x)
                    integral(c) = integral(c) + instance%get_value ()
                end do
            end do
            mci%integral = dot_product (instance%w, integral) &
                / mci%divisions
            mci%integral_known = .true.
        case (2)
            do c = 1, mci%n_channel
                do i = 1, mci%divisions
                    x(1) = (i - 0.5_default) / mci%divisions
                    do j = 1, mci%divisions
                        x(2) = (j - 0.5_default) / mci%divisions
                        call instance%evaluate (sampler, c, x)
                        integral(c) = integral(c) + instance%get_value ()
                    end do
                end do
            end do
            mci%integral = dot_product (instance%w, integral) &
                / mci%divisions / mci%divisions
            mci%integral_known = .true.
        end select
    if (present (results)) then
        call results%record (n_it, n_calls, &

```

```

        mci%integral, mci%error, &
        efficiency = 0._default)
    end if
end select
end subroutine mci_test_integrate

```

Simulation initializer and finalizer: nothing to do here.

```

<MCI base: tests>+≡
  subroutine mci_test_ignore_prepare_simulation (mci)
    class(mci_test_t), intent(inout) :: mci
  end subroutine mci_test_ignore_prepare_simulation

```

Event generator. We use mock random numbers for first selecting the channel and then setting the x values. The results reside in the state of `instance` and `sampler`.

```

<MCI base: tests>+≡
  subroutine mci_test_generate_weighted_event (mci, instance, sampler)
    class(mci_test_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout), target :: instance
    class(mci_sampler_t), intent(inout), target :: sampler
    real(default) :: r
    real(default), dimension(:), allocatable :: x
    integer :: c
    select type (instance)
    type is (mci_test_instance_t)
      allocate (x (mci%n_dim))
      select case (mci%n_channel)
      case (1)
        c = 1
        call mci%rng%generate (x(1))
      case (2)
        call mci%rng%generate (r)
        if (r < instance%w(1)) then
          c = 1
        else
          c = 2
        end if
        call mci%rng%generate (x)
      end select
      call instance%evaluate (sampler, c, x)
    end select
  end subroutine mci_test_generate_weighted_event

```

For unweighted events, we generate weighted events and apply a simple rejection step to the relative event weight, until an event passes.

(This might result in an endless loop if we happen to be in sync with the mock random generator cycle. Therefore, limit the number of tries.)

```

<MCI base: tests>+≡
  subroutine mci_test_generate_unweighted_event (mci, instance, sampler)
    class(mci_test_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout), target :: instance
    class(mci_sampler_t), intent(inout), target :: sampler

```

```

real(default) :: r
integer :: i
select type (instance)
type is (mci_test_instance_t)
  mci%tries = 0
  do i = 1, 10
    call mci%generate_weighted_event (instance, sampler)
    mci%tries = mci%tries + 1
    call mci%rng%generate (r)
    if (r < instance%rel_value) exit
  end do
end select
end subroutine mci_test_generate_unweighted_event

```

Here, we rebuild the event from the state without consulting the rng.

```

<MCI base: tests>+≡
subroutine mci_test_rebuild_event (mci, instance, sampler, state)
  class(mci_test_t), intent(inout) :: mci
  class(mci_instance_t), intent(inout) :: instance
  class(mci_sampler_t), intent(inout) :: sampler
  class(mci_state_t), intent(in) :: state
  select type (instance)
  type is (mci_test_instance_t)
    call instance%recall (sampler, state)
  end select
end subroutine mci_test_rebuild_event

```

Instance of the test MCI type

This instance type simulates the VAMP approach. We implement the VAMP multi-channel formula, but keep the channel-specific probability functions g_i smooth and fixed. We also keep the weights fixed.

The setup is as follows: we have n mappings of the unit hypercube

$$x = x(x^{(k)}) \quad \text{where } x = (x_1, \dots). \quad (19.1)$$

The Jacobian factors are the determinants

$$f^{(k)}(x^{(k)}) = \left| \frac{\partial x}{\partial x^{(k)}} \right| \quad (19.2)$$

We introduce arbitrary probability functions

$$g^{(k)}(x^{(k)}) \quad \text{with} \quad \int dx^{(k)} g^{(k)}(x^{(k)}) = 1 \quad (19.3)$$

and weights

$$w_k \quad \text{with} \quad \sum_k w_k = 1 \quad (19.4)$$

and construct the joint probability function

$$g(x) = \sum_k w_k \frac{g^{(k)}(x^{(k)}(x))}{f^{(k)}(x^{(k)}(x))} \quad (19.5)$$

which also satisfies

$$\int g(x) dx = 1. \quad (19.6)$$

The algorithm implements a resolution of unity as follows

$$\begin{aligned} 1 &= \int dx = \int \frac{g(x)}{g(x)} dx \\ &= \sum w_k \int \frac{g^{(k)}(x^{(k)}(x))}{f^{(k)}(x^{(k)}(x))} \frac{dx}{g(x)} \\ &= \sum w_k \int g^{(k)}(x^{(k)}) \frac{dx^{(k)}}{g(x(x^{(k)}))} \end{aligned} \quad (19.7)$$

where each of the integrals in the sum is evaluated using the channel-specific variables $x^{(k)}$.

We provide two examples: (1) trivial with one channel, one dimension, and all functions unity and (2) two channels and two dimensions with

$$\begin{aligned} x(x^{(1)}) &= (x_1^{(1)}, x_2^{(1)}) \\ x(x^{(2)}) &= (x_1^{(2)2}, x_2^{(2)}) \end{aligned} \quad (19.8)$$

hence

$$f^{(1)} \equiv 1, \quad f^{(2)}(x^{(2)}) = 2x_1^{(2)} \quad (19.9)$$

The probability functions are

$$g^{(1)} \equiv 1, \quad g^{(2)}(x^{(2)}) = 2x_2^{(2)} \quad (19.10)$$

In the concrete implementation of the integrator instance we store values for the channel probabilities g_i and the accumulated probability g .

We also store the result (product of integrand and MCI weight), the expected maximum for the result in each channel.

```

<MCI base: public>+≡
  public :: mci_test_instance_t

<MCI base: test types>+≡
  type, extends (mci_instance_t) :: mci_test_instance_t
    type(mci_test_t), pointer :: mci => null ()
    real(default) :: g = 0
    real(default), dimension(:), allocatable :: gi
    real(default) :: value = 0
    real(default) :: rel_value = 0
    real(default), dimension(:), allocatable :: max
  contains
    procedure :: write => mci_test_instance_write
    procedure :: final => mci_test_instance_final
    procedure :: init => mci_test_instance_init
    procedure :: compute_weight => mci_test_instance_compute_weight
    procedure :: record_integrand => mci_test_instance_record_integrand
    procedure :: init_simulation => mci_test_instance_init_simulation
    procedure :: final_simulation => mci_test_instance_final_simulation
    procedure :: get_event_excess => mci_test_instance_get_event_excess
  end type mci_test_instance_t

```

Output: trivial

<MCI base: tests>+≡

```

subroutine mci_test_instance_write (object, unit, pacify)
  class(mci_test_instance_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: pacify
  integer :: u, c
  u = given_output_unit (unit)
  write (u, "(1x,A,ES13.7)") "Result value = ", object%value
  write (u, "(1x,A,ES13.7)") "Rel. weight = ", object%rel_value
  write (u, "(1x,A,ES13.7)") "Integrand = ", object%integrand
  write (u, "(1x,A,ES13.7)") "MCI weight = ", object%mci_weight
  write (u, "(3x,A,I0)") "c = ", object%selected_channel
  write (u, "(3x,A,ES13.7)") "g = ", object%g
  write (u, "(1x,A)") "Channel parameters:"
  do c = 1, object%mci%n_channel
    write (u, "(1x,I0,A,4(1x,ES13.7))") c, ": w/f/g/m =", &
      object%w(c), object%f(c), object%gi(c), object%max(c)
    write (u, "(4x,A,9(1x,F9.7))") "x =", object%x(:,c)
  end do
end subroutine mci_test_instance_write

```

The finalizer is empty.

<MCI base: tests>+≡

```

subroutine mci_test_instance_final (object)
  class(mci_test_instance_t), intent(inout) :: object
end subroutine mci_test_instance_final

```

Initializer. We make use of the analytical result that the maximum of the weighted integrand, in each channel, is equal to 1 (one-dimensional case) and 2 (two-dimensional case), respectively.

<MCI base: tests>+≡

```

subroutine mci_test_instance_init (mci_instance, mci)
  class(mci_test_instance_t), intent(out) :: mci_instance
  class(mci_t), intent(in), target :: mci
  call mci_instance%base_init (mci)
  select type (mci)
  type is (mci_test_t)
    mci_instance%mci => mci
  end select
  allocate (mci_instance%gi (mci%n_channel))
  mci_instance%gi = 0
  allocate (mci_instance%max (mci%n_channel))
  select case (mci%n_channel)
  case (1)
    mci_instance%max = 1._default
  case (2)
    mci_instance%max = 2._default
  end select
end subroutine mci_test_instance_init

```

Compute weight: we implement the VAMP multi-channel formula. The channel probabilities `gi` are predefined functions.

```

(MCI base: tests)+≡
subroutine mci_test_instance_compute_weight (mci, c)
  class(mci_test_instance_t), intent(inout) :: mci
  integer, intent(in) :: c
  integer :: i
  mci%selected_channel = c
  select case (mci%mci%n_dim)
  case (1)
    mci%gi(1) = 1
  case (2)
    mci%gi(1) = 1
    mci%gi(2) = 2 * mci%x(2,2)
  end select
  mci%g = 0
  do i = 1, mci%mci%n_channel
    mci%g = mci%g + mci%w(i) * mci%gi(i) / mci%f(i)
  end do
  mci%mci_weight = mci%gi(c) / mci%g
end subroutine mci_test_instance_compute_weight

```

Record the integrand. Apply the Jacobian weight to get the absolute value. Divide by the channel maximum and by any overall factor to get the value relative to the maximum.

```

(MCI base: tests)+≡
subroutine mci_test_instance_record_integrand (mci, integrand)
  class(mci_test_instance_t), intent(inout) :: mci
  real(default), intent(in) :: integrand
  mci%integrand = integrand
  mci%value = mci%integrand * mci%mci_weight
  mci%rel_value = mci%value / mci%max(mci%selected_channel) &
    / mci%mci%max_factor
end subroutine mci_test_instance_record_integrand

```

Nothing to do here.

```

(MCI base: tests)+≡
subroutine mci_test_instance_init_simulation (instance, safety_factor)
  class(mci_test_instance_t), intent(inout) :: instance
  real(default), intent(in), optional :: safety_factor
end subroutine mci_test_instance_init_simulation

subroutine mci_test_instance_final_simulation (instance)
  class(mci_test_instance_t), intent(inout) :: instance
end subroutine mci_test_instance_final_simulation

```

Return always zero.

```

(MCI base: tests)+≡
function mci_test_instance_get_event_excess (mci) result (excess)
  class(mci_test_instance_t), intent(in) :: mci
  real(default) :: excess
  excess = 0
end function

```

```
end function mci_test_instance_get_event_excess
```

Test sampler

The test sampler implements a fixed configuration, either trivial (one-channel, one-dimension), or slightly nontrivial (two-channel, two-dimension). In the second channel, the first parameter is mapped according to $x_1 = x_1^{(2)2}$, so we have $f^{(2)}(x^{(2)}) = 2x_1^{(2)}$.

For display purposes, we store the return values inside the object. This is not strictly necessary.

```
<MCI base: test types>+≡
type, extends (mci_sampler_t) :: test_sampler_t
  real(default) :: integrand = 0
  integer :: selected_channel = 0
  real(default), dimension(:,:), allocatable :: x
  real(default), dimension(:), allocatable :: f
contains
  procedure :: init => test_sampler_init
  procedure :: write => test_sampler_write
  procedure :: compute => test_sampler_compute
  procedure :: is_valid => test_sampler_is_valid
  procedure :: evaluate => test_sampler_evaluate
  procedure :: rebuild => test_sampler_rebuild
  procedure :: fetch => test_sampler_fetch
end type test_sampler_t
```

```
<MCI base: tests>+≡
subroutine test_sampler_init (sampler, n)
  class(test_sampler_t), intent(out) :: sampler
  integer, intent(in) :: n
  allocate (sampler%x (n, n))
  allocate (sampler%f (n))
end subroutine test_sampler_init
```

Output

```
<MCI base: tests>+≡
subroutine test_sampler_write (object, unit, testflag)
  class(test_sampler_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag
  integer :: u, c
  u = given_output_unit (unit)
  write (u, "(1x,A)") "Test sampler:"
  write (u, "(3x,A,ES13.7)") "Integrand = ", object%integrand
  write (u, "(3x,A,I0)") "Channel = ", object%selected_channel
  do c = 1, size (object%f)
    write (u, "(1x,I0,' ',1x,A,ES13.7)") c, "f = ", object%f(c)
    write (u, "(4x,A,9(1x,F9.7))") "x =", object%x(:,c)
  end do
end subroutine test_sampler_write
```


Compute x and Jacobians, given the input parameter array. This is called both by `evaluate` and `rebuild`.

```

(MCI base: tests)+≡
subroutine test_sampler_compute (sampler, c, x_in)
  class(test_sampler_t), intent(inout) :: sampler
  integer, intent(in) :: c
  real(default), dimension(:), intent(in) :: x_in
  sampler%selected_channel = c
  select case (size (sampler%f))
  case (1)
    sampler%x(:,1) = x_in
    sampler%f = 1
  case (2)
    select case (c)
    case (1)
      sampler%x(:,1) = x_in
      sampler%x(1,2) = sqrt (x_in(1))
      sampler%x(2,2) = x_in(2)
    case (2)
      sampler%x(1,1) = x_in(1) ** 2
      sampler%x(2,1) = x_in(2)
      sampler%x(:,2) = x_in
    end select
    sampler%f(1) = 1
    sampler%f(2) = 2 * sampler%x(1,2)
  end select
end subroutine test_sampler_compute

```

The point is always valid.

```

(MCI base: tests)+≡
function test_sampler_is_valid (sampler) result (valid)
  class(test_sampler_t), intent(in) :: sampler
  logical :: valid
  valid = .true.
end function test_sampler_is_valid

```

The integrand is always equal to 1.

```

(MCI base: tests)+≡
subroutine test_sampler_evaluate (sampler, c, x_in, val, x, f)
  class(test_sampler_t), intent(inout) :: sampler
  integer, intent(in) :: c
  real(default), dimension(:), intent(in) :: x_in
  real(default), intent(out) :: val
  real(default), dimension(:,:), intent(out) :: x
  real(default), dimension(:), intent(out) :: f
  call sampler%compute (c, x_in)
  sampler%integrand = 1
  val = sampler%integrand
  x = sampler%x
  f = sampler%f
end subroutine test_sampler_evaluate

```

Construct kinematics from the input x array. Set the integrand instead of evaluating it.

```

<MCI base: tests>+≡
subroutine test_sampler_rebuild (sampler, c, x_in, val, x, f)
  class(test_sampler_t), intent(inout) :: sampler
  integer, intent(in) :: c
  real(default), dimension(:), intent(in) :: x_in
  real(default), intent(in) :: val
  real(default), dimension(:,:), intent(out) :: x
  real(default), dimension(:), intent(out) :: f
  call sampler%compute (c, x_in)
  sampler%integrand = val
  x = sampler%x
  f = sampler%f
end subroutine test_sampler_rebuild

```

Recall contents.

```

<MCI base: tests>+≡
subroutine test_sampler_fetch (sampler, val, x, f)
  class(test_sampler_t), intent(in) :: sampler
  real(default), intent(out) :: val
  real(default), dimension(:,:), intent(out) :: x
  real(default), dimension(:), intent(out) :: f
  val = sampler%integrand
  x = sampler%x
  f = sampler%f
end subroutine test_sampler_fetch

```

Test results object

This mock object just stores and displays the current result.

```

<MCI base: test types>+≡
type, extends (mci_results_t) :: mci_test_results_t
  integer :: n_it = 0
  integer :: n_calls = 0
  real(default) :: integral = 0
  real(default) :: error = 0
  real(default) :: efficiency = 0
contains
  <MCI base: mci test results: TBP>
end type mci_test_results_t

```

Output.

```

<MCI base: mci test results: TBP>≡
  procedure :: write => mci_test_results_write

<MCI base: tests>+≡
subroutine mci_test_results_write (object, unit, verbose, suppress)
  class(mci_test_results_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose, suppress
  integer :: u

```

```

u = given_output_unit (unit)
write (u, "(3x,A,1x,I0)") "Iterations = ", object%n_it
write (u, "(3x,A,1x,I0)") "Calls      = ", object%n_calls
write (u, "(3x,A,1x,F12.10)") "Integral  = ", object%integral
write (u, "(3x,A,1x,F12.10)") "Error     = ", object%error
write (u, "(3x,A,1x,F12.10)") "Efficiency = ", object%efficiency
end subroutine mci_test_results_write

```

Record result.

```

<MCI base: mci test results: TBP>+≡
  procedure :: record => mci_test_results_record

<MCI base: tests>+≡
  subroutine mci_test_results_record (object, n_it, n_calls, &
    integral, error, efficiency, chain_weights, suppress)
    class(mci_test_results_t), intent(inout) :: object
    integer, intent(in) :: n_it
    integer, intent(in) :: n_calls
    real(default), intent(in) :: integral
    real(default), intent(in) :: error
    real(default), intent(in) :: efficiency
    real(default), dimension(:), intent(in), optional :: chain_weights
    logical, intent(in), optional :: suppress
    object%n_it = n_it
    object%n_calls = n_calls
    object%integral = integral
    object%error = error
    object%efficiency = efficiency
  end subroutine mci_test_results_record

```

Integrator configuration data

Construct and display a test integrator configuration object.

```

<MCI base: execute tests>≡
  call test (mci_base_1, "mci_base_1", &
    "integrator configuration", &
    u, results)

<MCI base: tests>+≡
  subroutine mci_base_1 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler

    real(default) :: integrand

    write (u, "(A)")  "* Test output: mci_base_1"
    write (u, "(A)")  "* Purpose: initialize and display &
      &test integrator"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize integrator"

```

```

write (u, "(A)")

allocate (mci_test_t :: mci)
call mci%set_dimensions (2, 2)

call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize instance"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_t :: sampler)
select type (sampler)
type is (test_sampler_t)
    call sampler%init (2)
end select

write (u, "(A)")  "* Evaluate sampler for given point and channel"
write (u, "(A)")

call sampler%evaluate (1, [0.25_default, 0.8_default], &
    integrand, mci_instance%x, mci_instance%f)

call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Compute MCI weight"
write (u, "(A)")

call mci_instance%compute_weight (1)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Get integrand and compute weight for another point"
write (u, "(A)")

call mci_instance%evaluate (sampler, 2, [0.5_default, 0.6_default])
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recall results, again"
write (u, "(A)")

call mci_instance%final ()
deallocate (mci_instance)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

```

```

call mci_instance%fetch (sampler, 2)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Retrieve value"
write (u, "(A)")

write (u, "(1x,A,ES13.7)") "Weighted integrand = ", &
    mci_instance%get_value ()

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_base_1"

end subroutine mci_base_1

```

Trivial integral

Use the MCI approach to compute a trivial one-dimensional integral.

```

<MCI base: execute tests>+≡
call test (mci_base_2, "mci_base_2", &
    "integration", &
    u, results)

<MCI base: tests>+≡
subroutine mci_base_2 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler

    write (u, "(A)")  "* Test output: mci_base_2"
    write (u, "(A)")  "* Purpose: perform a test integral"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize integrator"
    write (u, "(A)")

    allocate (mci_test_t :: mci)
    call mci%set_dimensions (1, 1)
    select type (mci)
    type is (mci_test_t)
        call mci%set_divisions (10)
    end select

    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize instance"
    write (u, "(A)")

```

```

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_t :: sampler)
select type (sampler)
type is (test_sampler_t)
    call sampler%init (1)
end select

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call mci%integrate (mci_instance, sampler, 0, 0)

call mci%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_base_2"

end subroutine mci_base_2

```

Nontrivial integral

Use the MCI approach to compute a simple two-dimensional integral with two channels.

```

<MCI base: execute tests>+≡
    call test (mci_base_3, "mci_base_3", &
        "integration (two channels)", &
        u, results)

<MCI base: tests>+≡
subroutine mci_base_3 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler

    write (u, "(A)")  "* Test output: mci_base_3"
    write (u, "(A)")  "* Purpose: perform a nontrivial test integral"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize integrator"
    write (u, "(A)")

    allocate (mci_test_t :: mci)
    call mci%set_dimensions (2, 2)

```

```

select type (mci)
type is (mci_test_t)
    call mci%set_divisions (10)
end select

write (u, "(A)")  "* Initialize instance"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_t :: sampler)
select type (sampler)
type is (test_sampler_t)
    call sampler%init (2)
end select

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call mci%integrate (mci_instance, sampler, 0, 0)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with higher resolution"
write (u, "(A)")

select type (mci)
type is (mci_test_t)
    call mci%set_divisions (100)
end select

call mci%integrate (mci_instance, sampler, 0, 0)
call mci%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_base_3"

end subroutine mci_base_3

```

Event generation

We generate “random” events, one weighted and one unweighted. The test implementation does not require an integration pass, we can generate events immediately.

(MCI base: execute tests)+≡

```

call test (mci_base_4, "mci_base_4", &
    "event generation (two channels)", &
    u, results)
<MCI base: tests>+≡
subroutine mci_base_4 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(rng_t), allocatable :: rng

    write (u, "(A)")  "* Test output: mci_base_4"
    write (u, "(A)")  "* Purpose: generate events"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize integrator, instance, sampler"
    write (u, "(A)")

    allocate (mci_test_t :: mci)
    call mci%set_dimensions (2, 2)
    select type (mci)
    type is (mci_test_t)
        call mci%set_divisions (10)
    end select

    call mci%allocate_instance (mci_instance)
    call mci_instance%init (mci)

    allocate (test_sampler_t :: sampler)
    select type (sampler)
    type is (test_sampler_t)
        call sampler%init (2)
    end select

    allocate (rng_test_t :: rng)
    call mci%import_rng (rng)

    write (u, "(A)")  "* Generate weighted event"
    write (u, "(A)")

    call mci%generate_weighted_event (mci_instance, sampler)

    call sampler%write (u)
    write (u, *)
    call mci_instance%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Generate unweighted event"
    write (u, "(A)")

    call mci%generate_unweighted_event (mci_instance, sampler)

    select type (mci)
    type is (mci_test_t)

```



```

        write (u, "(A,I0)") " Success in try ", mci%tries
        write (u, "(A)")
    end select

    call sampler%write (u)
    write (u, *)
    call mci_instance%write (u)

    call mci_instance%final ()
    call mci%final ()

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: mci_base_4"

end subroutine mci_base_4

```

Store and recall data

We generate an event and store the relevant data, i.e., the input parameters and the result value for a particular channel. Then we use those data to recover the event, as far as the MCI record is concerned.

```

<MCI base: execute tests>+≡
    call test (mci_base_5, "mci_base_5", &
        "store and recall", &
        u, results)

<MCI base: tests>+≡
    subroutine mci_base_5 (u)
        integer, intent(in) :: u
        class(mci_t), allocatable, target :: mci
        class(mci_instance_t), pointer :: mci_instance => null ()
        class(mci_sampler_t), allocatable :: sampler
        class(rng_t), allocatable :: rng
        class(mci_state_t), allocatable :: state

        write (u, "(A)")  "* Test output: mci_base_5"
        write (u, "(A)")  "* Purpose: store and recall an event"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize integrator, instance, sampler"
        write (u, "(A)")

        allocate (mci_test_t :: mci)
        call mci%set_dimensions (2, 2)
        select type (mci)
        type is (mci_test_t)
            call mci%set_divisions (10)
        end select

        call mci%allocate_instance (mci_instance)
        call mci_instance%init (mci)

        allocate (test_sampler_t :: sampler)

```

```

select type (sampler)
type is (test_sampler_t)
    call sampler%init (2)
end select

allocate (rng_test_t :: rng)
call mci%import_rng (rng)

write (u, "(A)")  "* Generate weighted event"
write (u, "(A)")

call mci%generate_weighted_event (mci_instance, sampler)

call sampler%write (u)
write (u, *)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Store data"
write (u, "(A)")

allocate (state)
call mci_instance%store (state)
call mci_instance%final ()
deallocate (mci_instance)

call state%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recall data and rebuild event"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)
call mci%rebuild_event (mci_instance, sampler, state)

call sampler%write (u)
write (u, *)
call mci_instance%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_base_5"

end subroutine mci_base_5

```

Chained channels

Chain channels together. In the base configuration, this just fills entries in an extra array (each channel may belong to a chain). In type implementations, this

will be used for grouping equivalent channels by keeping their weights equal.

```

(MCI base: execute tests)+≡
  call test (mci_base_6, "mci_base_6", &
    "chained channels", &
    u, results)

(MCI base: tests)+≡
  subroutine mci_base_6 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci

    write (u, "(A)")  "* Test output: mci_base_6"
    write (u, "(A)")  "* Purpose: initialize and display &
      &test integrator with chains"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize integrator"
    write (u, "(A)")

    allocate (mci_test_t :: mci)
    call mci%set_dimensions (1, 5)

    write (u, "(A)")  "* Introduce chains"
    write (u, "(A)")

    call mci%declare_chains ([1, 2, 2, 1, 2])

    call mci%write (u)

    call mci%final ()

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: mci_base_6"

  end subroutine mci_base_6

```

Recording results

Compute a simple two-dimensional integral and record the result.

```

(MCI base: execute tests)+≡
  call test (mci_base_7, "mci_base_7", &
    "recording results", &
    u, results)

(MCI base: tests)+≡
  subroutine mci_base_7 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(mci_results_t), allocatable :: results

    write (u, "(A)")  "* Test output: mci_base_7"

```

```

write (u, "(A)")  "* Purpose: perform a nontrivial test integral &
&and record results"
write (u, "(A)")

write (u, "(A)")  "* Initialize integrator"
write (u, "(A)")

allocate (mci_test_t :: mci)
call mci%set_dimensions (2, 2)
select type (mci)
type is (mci_test_t)
    call mci%set_divisions (10)
end select

write (u, "(A)")  "* Initialize instance"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_t :: sampler)
select type (sampler)
type is (test_sampler_t)
    call sampler%init (2)
end select

allocate (mci_test_results_t :: results)

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call mci%integrate (mci_instance, sampler, 1, 1000, results)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Display results"
write (u, "(A)")

call results%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_base_7"

end subroutine mci_base_7

```

Timer

Simple checks for the embedded timer.

```
(MCI base: execute tests)+≡
    call test (mci_base_8, "mci_base_8", &
        "timer", &
        u, results)

(MCI base: tests)+≡
    subroutine mci_base_8 (u)
        integer, intent(in) :: u
        class(mci_t), allocatable, target :: mci

        write (u, "(A)")  "* Test output: mci_base_8"
        write (u, "(A)")  "* Purpose: check timer availability"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize integrator with timer"
        write (u, "(A)")

        allocate (mci_test_t :: mci)
        call mci%set_dimensions (2, 2)
        select type (mci)
        type is (mci_test_t)
            call mci%set_divisions (10)
        end select

        call mci%set_timer (active = .true.)
        call mci%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Start timer"
        write (u, "(A)")

        call mci%start_timer ()
        call mci%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Stop timer"
        write (u, "(A)")

        call mci%stop_timer ()
        call mci%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Readout"
        write (u, "(A)")

        write (u, "(1x,A,F6.3)")  "Time = ", mci%get_time ()

        write (u, "(A)")
        write (u, "(A)")  "* Deactivate timer"
        write (u, "(A)")

        call mci%set_timer (active = .false.)
```

```

call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_base_8"

end subroutine mci_base_8

```

19.2 Iterations

This module defines a container for the list of iterations and calls, to be submitted to integration.

```

<iterations.f90>≡
  <File header>

  module iterations

    <Use strings>
    use io_units
    use unit_tests
    use diagnostics

    <Standard module head>

    <Iterations: public>

    <Iterations: types>

    contains

    <Iterations: procedures>

    <Iterations: tests>

  end module iterations

```

19.2.1 The iterations list

Each integration pass has a number of iterations and a number of calls per iteration. The last pass produces the end result; the previous passes are used for adaptation.

The flags `adapt_grid` and `adapt_weight` are used only if `custom_adaptation` is set. Otherwise, default settings are used that depend on the integration pass.

```

<Iterations: types>≡
  type :: iterations_spec_t
    private

```

```

integer :: n_it = 0
integer :: n_calls = 0
logical :: custom_adaptation = .false.
logical :: adapt_grids = .false.
logical :: adapt_weights = .false.
end type iterations_spec_t

```

We build up a list of iterations.

```

<Iterations: public>≡
public :: iterations_list_t

<Iterations: types>+≡
type :: iterations_list_t
private
integer :: n_pass = 0
type(iterations_spec_t), dimension(:), allocatable :: pass
contains
<Iterations: iterations list: TBP>
end type iterations_list_t

```

Initialize an iterations list. For each pass, we have to specify the number of iterations and calls. We may provide the adaption conventions explicitly, either as character codes or as logicals.

For passes where the adaptation conventions are not specified, we use the following default setting: adapt weights and grids for all passes except the last one.

```

<Iterations: iterations list: TBP>≡
procedure :: init => iterations_list_init

<Iterations: procedures>≡
subroutine iterations_list_init &
    (it_list, n_it, n_calls, adapt, adapt_code, adapt_grids, adapt_weights)
class(iterations_list_t), intent(inout) :: it_list
integer, dimension(:), intent(in) :: n_it, n_calls
logical, dimension(:), intent(in), optional :: adapt
type(string_t), dimension(:), intent(in), optional :: adapt_code
logical, dimension(:), intent(in), optional :: adapt_grids, adapt_weights
integer :: i
it_list%n_pass = size (n_it)
if (allocated (it_list%pass)) deallocate (it_list%pass)
allocate (it_list%pass (it_list%n_pass))
it_list%pass%n_it = n_it
it_list%pass%n_calls = n_calls
if (present (adapt)) then
    it_list%pass%custom_adaptation = adapt
do i = 1, it_list%n_pass
    if (adapt(i)) then
        if (verify (adapt_code(i), "wg") /= 0) then
            call msg_error ("iteration specification: " &
                // "adaptation code letters must be 'w' or 'g'")
        end if
        it_list%pass(i)%adapt_grids = scan (adapt_code(i), "g") /= 0
        it_list%pass(i)%adapt_weights = scan (adapt_code(i), "w") /= 0
    end if
end do
end subroutine

```

```

        end if
    end do
    else if (present (adapt_grids) .and. present (adapt_weights)) then
        it_list%pass%custom_adaptation = .true.
        it_list%pass%adapt_grids = adapt_grids
        it_list%pass%adapt_weights = adapt_weights
    end if
    do i = 1, it_list%n_pass - 1
        if (.not. it_list%pass(i)%custom_adaptation) then
            it_list%pass(i)%adapt_grids = .true.
            it_list%pass(i)%adapt_weights = .true.
        end if
    end do
end subroutine iterations_list_init

```

<Iterations: iterations list: TBP>+≡

```

    procedure :: clear => iterations_list_clear

```

<Iterations: procedures>+≡

```

    subroutine iterations_list_clear (it_list)
        class(iterations_list_t), intent(inout) :: it_list
        it_list%n_pass = 0
        deallocate (it_list%pass)
    end subroutine iterations_list_clear

```

Write the list of iterations.

<Iterations: iterations list: TBP>+≡

```

    procedure :: write => iterations_list_write

```

<Iterations: procedures>+≡

```

    subroutine iterations_list_write (it_list, unit)
        class(iterations_list_t), intent(in) :: it_list
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(A)") char (it_list%to_string ())
    end subroutine iterations_list_write

```

The output as a single-line string.

<Iterations: iterations list: TBP>+≡

```

    procedure :: to_string => iterations_list_to_string

```

<Iterations: procedures>+≡

```

    function iterations_list_to_string (it_list) result (buffer)
        class(iterations_list_t), intent(in) :: it_list
        type(string_t) :: buffer
        character(30) :: ibuf
        integer :: i
        buffer = "iterations = "
        if (it_list%n_pass > 0) then
            do i = 1, it_list%n_pass
                if (i > 1) buffer = buffer // ", "
                write (ibuf, "(I0,':',I0)") &
                    it_list%pass(i)%n_it, it_list%pass(i)%n_calls
            end do
        end if
    end function iterations_list_to_string

```



```

        buffer = buffer // trim (ibuf)
        if (it_list%pass(i)%custom_adaptation &
            .or. it_list%pass(i)%adapt_grids &
            .or. it_list%pass(i)%adapt_weights) then
            buffer = buffer // ':'
            if (it_list%pass(i)%adapt_grids) buffer = buffer // "g"
            if (it_list%pass(i)%adapt_weights) buffer = buffer // "w"
            buffer = buffer // ','
        end if
    end do
else
    buffer = buffer // "[undefined]"
end if
end function iterations_list_to_string

```

19.2.2 Tools

Return the total number of passes.

```

<Iterations: iterations list: TBP>+≡
    procedure :: get_n_pass => iterations_list_get_n_pass

<Iterations: procedures>+≡
    function iterations_list_get_n_pass (it_list) result (n_pass)
        class(iterations_list_t), intent(in) :: it_list
        integer :: n_pass
        n_pass = it_list%n_pass
    end function iterations_list_get_n_pass

```

Return the number of calls for a specific pass.

```

<Iterations: iterations list: TBP>+≡
    procedure :: get_n_calls => iterations_list_get_n_calls

<Iterations: procedures>+≡
    function iterations_list_get_n_calls (it_list, pass) result (n_calls)
        class(iterations_list_t), intent(in) :: it_list
        integer :: n_calls
        integer, intent(in) :: pass
        if (pass <= it_list%n_pass) then
            n_calls = it_list%pass(pass)%n_calls
        else
            n_calls = 0
        end if
    end function iterations_list_get_n_calls

```

Get the adaptation mode (automatic/custom) and, for custom adaptation, the flags for a specific pass.

```

<Iterations: iterations list: TBP>+≡
    procedure :: adapt_grids => iterations_list_adapt_grids
    procedure :: adapt_weights => iterations_list_adapt_weights

```

```

<Iterations: procedures>+≡
function iterations_list_adapt_grids (it_list, pass) result (flag)
    logical :: flag
    class(iterations_list_t), intent(in) :: it_list
    integer, intent(in) :: pass
    if (pass <= it_list%n_pass) then
        flag = it_list%pass(pass)%adapt_grids
    else
        flag = .false.
    end if
end function iterations_list_adapt_grids

function iterations_list_adapt_weights (it_list, pass) result (flag)
    logical :: flag
    class(iterations_list_t), intent(in) :: it_list
    integer, intent(in) :: pass
    if (pass <= it_list%n_pass) then
        flag = it_list%pass(pass)%adapt_weights
    else
        flag = .false.
    end if
end function iterations_list_adapt_weights

```

Return the total number of iterations / the iterations for a specific pass.

```

<Iterations: iterations list: TBP>+≡
procedure :: get_n_it => iterations_list_get_n_it

<Iterations: procedures>+≡
function iterations_list_get_n_it (it_list, pass) result (n_it)
    class(iterations_list_t), intent(in) :: it_list
    integer :: n_it
    integer, intent(in) :: pass
    if (pass <= it_list%n_pass) then
        n_it = it_list%pass(pass)%n_it
    else
        n_it = 0
    end if
end function iterations_list_get_n_it

```

19.2.3 Test

This is the master for calling self-test procedures.

```

<Iterations: public>+≡
public :: iterations_test

<Iterations: tests>≡
subroutine iterations_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    <Iterations: execute tests>
end subroutine iterations_test

```

Empty list

```
<Iterations: execute tests>≡
  call test (iterations_1, "iterations_1", &
    "empty iterations list", &
    u, results)

<Iterations: tests>+≡
  subroutine iterations_1 (u)
    integer, intent(in) :: u
    type(iterations_list_t) :: it_list

    write (u, "(A)")  "* Test output: iterations_1"
    write (u, "(A)")  "* Purpose: display empty iterations list"
    write (u, "(A)")

    call it_list%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: iterations_1"

  end subroutine iterations_1
```

Fill list

```
<Iterations: execute tests>+≡
  call test (iterations_2, "iterations_2", &
    "create iterations list", &
    u, results)

<Iterations: tests>+≡
  subroutine iterations_2 (u)
    integer, intent(in) :: u
    type(iterations_list_t) :: it_list

    write (u, "(A)")  "* Test output: iterations_2"
    write (u, "(A)")  "* Purpose: fill and display iterations list"
    write (u, "(A)")

    write (u, "(A)")  "* Minimal setup (2 passes)"
    write (u, "(A)")

    call it_list%init ([2, 4], [5000, 20000])

    call it_list%write (u)
    call it_list%clear ()

    write (u, "(A)")
    write (u, "(A)")  "* Setup with flags (3 passes)"
    write (u, "(A)")

    call it_list%init ([2, 4, 5], [5000, 20000, 400], &
      [.false., .true., .true.], &
      [var_str (""), var_str ("g"), var_str ("wg")])
```

```

call it_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Extract data"
write (u, "(A)")

write (u, "(A,I0)")  "n_pass = ", it_list%get_n_pass ()
write (u, "(A)")
write (u, "(A,I0)")  "n_calls(2) = ", it_list%get_n_calls (2)
write (u, "(A)")
write (u, "(A,I0)")  "n_it(3) = ", it_list%get_n_it (3)

write (u, "(A)")
write (u, "(A)")  "* Test output end: iterations_2"

end subroutine iterations_2

```

19.3 Integration results

We record integration results and errors in a dedicated type. This allows us to do further statistics such as weighted average, chi-squared, grouping by integration passes, etc.

Note WHIZARD 2.2.0: This code is taken from the previous `processes` module essentially unchanged and converted into a separate module. It lacks an overhaul and, in particular, self-tests.

```

<integration_results.f90>≡
module integration_results

  <Use kinds>
  <Use strings>
  use io_units
  use format_utils, only: mp_format, pac_fmt
  use format_defs, only: FMT_10, FMT_14
  use diagnostics
  use md5
  use os_interface
  use mci_base

  <Standard module head>

  <Integration results: public>

  <Integration results: parameters>

  <Integration results: types>

contains

  <Integration results: procedures>

```

```
end module integration_results
```

19.3.1 Integration results entry

This object collects the results of an integration pass and makes them available to the outside.

The results object has to distinguish the process type:

We store the process type, the index of the integration pass and the absolute iteration index, the number of iterations contained in this result (for averages), and the integral (cross section or partial width), error estimate, efficiency.

For intermediate results, we set a flag if this result is an improvement w.r.t. previous ones.

The process type indicates decay or scattering. Dummy entries (skipped iterations) have a process type of PRC_UNKNOWN.

<Integration results: types>≡

```
type :: integration_entry_t
private
integer :: process_type = PRC_UNKNOWN
integer :: pass = 0
integer :: it = 0
integer :: n_it = 0
integer :: n_calls = 0
logical :: improved = .false.
real(default) :: integral = 0
real(default) :: error = 0
real(default) :: efficiency = 0
real(default) :: chi2 = 0
real(default), dimension(:), allocatable :: chain_weights
end type integration_entry_t
```

The possible values of the type indicator:

<Integration results: parameters>≡

```
integer, parameter, public :: PRC_UNKNOWN = 0
integer, parameter, public :: PRC_DECAY = 1
integer, parameter, public :: PRC_SCATTERING = 2
```

Initialize with all relevant data

<Integration results: procedures>≡

```
subroutine integration_entry_init (entry, &
    process_type, pass, it, n_it, n_calls, improved, &
    integral, error, efficiency, chi2, chain_weights)
type(integration_entry_t), intent(out) :: entry
integer, intent(in) :: process_type, pass, it, n_it, n_calls
logical, intent(in) :: improved
real(default), intent(in) :: integral, error, efficiency
real(default), intent(in), optional :: chi2
real(default), dimension(:), intent(in), optional :: chain_weights
entry%process_type = process_type
entry%pass = pass
entry%it = it
entry%n_it = n_it
```

```

entry%n_calls = n_calls
entry%improved = improved
entry%integral = integral
entry%error = error
entry%efficiency = efficiency
if (present (chi2)) &
    entry%chi2 = chi2
if (present (chain_weights)) then
    allocate (entry%chain_weights (size (chain_weights)))
    entry%chain_weights = chain_weights
end if
end subroutine integration_entry_init

```

Access values, some of them computed on demand:

(Integration results: procedures)+≡

```

elemental function integration_entry_get_pass (entry) result (n)
    integer :: n
    type(integration_entry_t), intent(in) :: entry
    n = entry%pass
end function integration_entry_get_pass

elemental function integration_entry_get_n_calls (entry) result (n)
    integer :: n
    type(integration_entry_t), intent(in) :: entry
    n = entry%n_calls
end function integration_entry_get_n_calls

elemental function integration_entry_get_integral (entry) result (int)
    real(default) :: int
    type(integration_entry_t), intent(in) :: entry
    int = entry%integral
end function integration_entry_get_integral

elemental function integration_entry_get_error (entry) result (err)
    real(default) :: err
    type(integration_entry_t), intent(in) :: entry
    err = entry%error
end function integration_entry_get_error

elemental function integration_entry_get_relative_error (entry) result (err)
    real(default) :: err
    type(integration_entry_t), intent(in) :: entry
    if (entry%integral /= 0) then
        err = entry%error / entry%integral
    else
        err = 0
    end if
end function integration_entry_get_relative_error

elemental function integration_entry_get_accuracy (entry) result (acc)
    real(default) :: acc
    type(integration_entry_t), intent(in) :: entry
    acc = accuracy (entry%integral, entry%error, entry%n_calls)
end function integration_entry_get_accuracy

```

```

elemental function accuracy (integral, error, n_calls) result (acc)
  real(default) :: acc
  real(default), intent(in) :: integral, error
  integer, intent(in) :: n_calls
  if (integral /= 0) then
    acc = error / integral * sqrt (real (n_calls, default))
  else
    acc = 0
  end if
end function accuracy

elemental function integration_entry_get_efficiency (entry) result (eff)
  real(default) :: eff
  type(integration_entry_t), intent(in) :: entry
  eff = entry%efficiency
end function integration_entry_get_efficiency

elemental function integration_entry_get_chi2 (entry) result (chi2)
  real(default) :: chi2
  type(integration_entry_t), intent(in) :: entry
  chi2 = entry%chi2
end function integration_entry_get_chi2

elemental function integration_entry_has_improved (entry) result (flag)
  logical :: flag
  type(integration_entry_t), intent(in) :: entry
  flag = entry%improved
end function integration_entry_has_improved

elemental function integration_entry_get_n_groves (entry) result (n_groves)
  integer :: n_groves
  type(integration_entry_t), intent(in) :: entry
  if (allocated (entry%chain_weights)) then
    n_groves = size (entry%chain_weights, 1)
  else
    n_groves = 0
  end if
end function integration_entry_get_n_groves

```

Output. This writes the header line for the result account below:

```

<Integration results: procedures>+≡
  subroutine write_header (process_type, unit, logfile)
    integer, intent(in) :: process_type
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: logfile
    character(5) :: phys_unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    select case (process_type)
    case (PRC_DECAY);      phys_unit = "[GeV]"
    case (PRC_SCATTERING); phys_unit = "[fb] "
    case default
      phys_unit = ""
    end select
  end subroutine

```

```

end select
write (msg_buffer, "(A)") &
    "It      Calls  Integral" // phys_unit // &
    " Error" // phys_unit // &
    " Err[%]   Acc  Eff[%]   Chi2 N[It] |"
call msg_message (unit=u, logfile=logfile)
end subroutine write_header

```

This writes a separator for result display:

```

<Integration results: procedures>+≡
subroutine write_hline (unit)
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A)")  "|" // (repeat("-", 77)) // "|"
    flush (u)
end subroutine write_hline

subroutine write_dline (unit)
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A)")  "|" // (repeat("=", 77)) // "|"
    flush (u)
end subroutine write_dline

```

This writes the standard result account into one screen line. The verbose version uses multiple lines and prints the unabridged values. Dummy entries are not written.

```

<Integration results: procedures>+≡
subroutine integration_entry_write (entry, unit, verbose, suppress)
    type(integration_entry_t), intent(in) :: entry
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    logical, intent(in), optional :: suppress
    integer :: u
    character(1) :: star
    character(12) :: fmt
    character(7) :: fmt2
    logical :: verb, supp
    u = given_output_unit (unit); if (u < 0) return
    verb = .false.; if (present (verbose)) verb = verbose
    supp = .false.; if (present (suppress)) supp = suppress
    if (verb) then
        write (u, *) "process_type = ", entry%process_type
        write (u, *) "      pass = ", entry%pass
        write (u, *) "      it = ", entry%it
        write (u, *) "      n_it = ", entry%n_it
        write (u, *) "      n_calls = ", entry%n_calls
        write (u, *) "      improved = ", entry%improved
        write (u, *) "      integral = ", entry%integral
        write (u, *) "      error = ", entry%error
        write (u, *) "      efficiency = ", entry%efficiency
    end if
end subroutine integration_entry_write

```



```

write (u, *) "          chi2 = ", entry%chi2
if (allocated (entry%chain_weights)) then
  write (u, *) "      n_groves = ", size (entry%chain_weights)
  write (u, *) "chain_weights = ", entry%chain_weights
else
  write (u, *) "      n_groves = 0"
end if
else if (entry%process_type /= PRC_UNKNOWN) then
  if (entry%improved .and. .not. supp) then
    star = "*"
  else
    star = " "
  end if
  call pac_fmt (fmt, FMT_14, "3x," // FMT_10 // ",1x", suppress)
  call pac_fmt (fmt2, "1x,F6.2", "2x,F5.1", suppress)
  if (entry%n_it /= 1) then
    write (u, "(1x,I3,1x,I10,1x," // fmt // ",1x,ES9.2,1x,F7.2," // &
      "1x,F7.2,A1," // fmt2 // ",1x,F7.2,1x,I3)" &
      entry%it, &
      entry%n_calls, &
      entry%integral, &
      abs(entry%error), &
      abs(integration_entry_get_relative_error (entry)) * 100, &
      abs(integration_entry_get_accuracy (entry)), &
      star, &
      entry%efficiency * 100, &
      entry%chi2, &
      entry%n_it
  else
    write (u, "(1x,I3,1x,I10,1x," // fmt // ",1x,ES9.2,1x,F7.2," // &
      "1x,F7.2,A1," // fmt2 // ",1x,F7.2,1x,I3)" &
      entry%it, &
      entry%n_calls, &
      entry%integral, &
      abs(entry%error), &
      abs(integration_entry_get_relative_error (entry)) * 100, &
      abs(integration_entry_get_accuracy (entry)), &
      star, &
      entry%efficiency * 100
  end if
end if
flush (u)
end subroutine integration_entry_write

```

Read the entry, assuming it has been written in verbose format.

(Integration results: procedures)+≡

```

subroutine integration_entry_read (entry, unit)
  type(integration_entry_t), intent(out) :: entry
  integer, intent(in) :: unit
  character(30) :: dummy
  character :: equals
  integer :: n_groves
  read (unit, *) dummy, equals, entry%process_type
  read (unit, *) dummy, equals, entry%pass

```

```

read (unit, *) dummy, equals, entry%it
read (unit, *) dummy, equals, entry%n_it
read (unit, *) dummy, equals, entry%n_calls
read (unit, *) dummy, equals, entry%improved
read (unit, *) dummy, equals, entry%integral
read (unit, *) dummy, equals, entry%error
read (unit, *) dummy, equals, entry%efficiency
read (unit, *) dummy, equals, entry%chi2
read (unit, *) dummy, equals, n_groves
if (n_groves /= 0) then
    allocate (entry%chain_weights (n_groves))
    read (unit, *) dummy, equals, entry%chain_weights
end if
end subroutine integration_entry_read

```

Write an account of the channel weights, accumulated by groves.

```

<Integration results: procedures>+≡
subroutine integration_entry_write_chain_weights (entry, unit)
    type(integration_entry_t), intent(in) :: entry
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    if (allocated (entry%chain_weights)) then
        do i = 1, size (entry%chain_weights)
            write (u, "(1x,I3)", advance="no") nint (entry%chain_weights(i) * 100)
        end do
        write (u, *)
    end if
end subroutine integration_entry_write_chain_weights

```

Compute the average for all entries in the specified integration pass. The integrals are weighted w.r.t. their individual errors.

The quoted error of the result is the expected error, computed from the weighted average of the given individual errors.

This should be compared to the actual distribution of the results, from which we also can compute an error estimate if there is more than one iteration. The ratio of the distribution error and the averaged error, is the χ^2 value.

All error distributions are assumed Gaussian, of course. The χ^2 value is a partial check for this assumption. If it is significantly greater than unity, there is something wrong with the individual errors.

The efficiency returned is the one of the last entry in the integration pass.

If any error vanishes, averaging by this algorithm would fail. In this case, we simply average the entries and use the deviations from this average (if any) to estimate the error.

```

<Integration results: procedures>+≡
function compute_average (entry, pass) result (result)
    type(integration_entry_t) :: result
    type(integration_entry_t), dimension(:), intent(in) :: entry
    integer, intent(in) :: pass
    integer :: i
    logical, dimension(size(entry)) :: mask
    real(default), dimension(size(entry)) :: ivar

```

```

real(default) :: sum_ivar, variance
result%process_type = entry(1)%process_type
result%pass = pass
mask = entry%pass == pass .and. entry%process_type /= PRC_UNKNOWN
result%it = maxval (entry%it, mask)
result%n_it = count (mask)
result%n_calls = sum (entry%n_calls, mask)
if (.not. any (mask .and. entry%error == 0)) then
  where (mask)
    ivar = 1 / entry%error ** 2
  elsewhere
    ivar = 0
  end where
  sum_ivar = sum (ivar, mask)
  if (sum_ivar /= 0) then
    variance = 1 / sum_ivar
  else
    variance = 0
  end if
  result%integral = sum (entry%integral * ivar, mask) * variance
  if (result%n_it > 1) then
    result%chi2 = &
      sum ((entry%integral - result%integral)**2 * ivar, mask) &
      / (result%n_it - 1)
  end if
else if (result%n_it /= 0) then
  result%integral = sum (entry%integral, mask) / result%n_it
  if (result%n_it > 1) then
    variance = &
      sum ((entry%integral - result%integral)**2, mask) &
      / (result%n_it - 1)
    if (result%integral /= 0) then
      if (abs (variance / result%integral) &
        < 100 * epsilon (1._default)) then
        variance = 0
      end if
    end if
    result%chi2 = variance / result%n_it
  else
    variance = 0
  end if
end if
result%error = sqrt (variance)
do i = size (entry), 1, -1
  if (mask(i)) then
    result%efficiency = entry(i)%efficiency
    exit
  end if
end do
end function compute_average

```

19.3.2 Combined integration results

We collect a list of results which grows during the execution of the program. This is implemented as an array which grows if necessary; so we can easily compute averages.

We implement this as an extension of the `mci_results_t` which is defined in `mci_base` as an abstract type. We thus decouple the implementation of the integrator from the implementation of the results display, but nevertheless can record intermediate results during integration. This implies that the present extension implements a `record` method.

```
<Integration results: public>≡
  public :: integration_results_t
<Integration results: types>+≡
  type, extends (mci_results_t) :: integration_results_t
    private
      integer :: process_type = PRC_UNKNOWN
      integer :: current_pass = 0
      integer :: n_pass = 0
      integer :: n_it = 0
      logical :: screen = .false.
      integer :: unit = 0
      real(default) :: error_threshold = 0
      type(integration_entry_t), dimension(:), allocatable :: entry
      type(integration_entry_t), dimension(:), allocatable :: average
    contains
      <Integration results: integration results: TBP>
    end type integration_results_t
```

The array is extended in chunks of 10 entries.

```
<Integration results: parameters>+≡
  integer, parameter :: RESULTS_CHUNK_SIZE = 10
```

The standard does not require to explicitly initialize the integers; however, some gfortran version has a bug here and misses the default initialization in the type definition.

```
<Integration results: integration results: TBP>≡
  procedure :: init => integration_results_init
<Integration results: procedures>+≡
  subroutine integration_results_init (results, process_type)
    class(integration_results_t), intent(out) :: results
    integer, intent(in) :: process_type
    results%process_type = process_type
    results%n_pass = 0
    results%n_it = 0
    allocate (results%entry (RESULTS_CHUNK_SIZE))
    allocate (results%average (RESULTS_CHUNK_SIZE))
  end subroutine integration_results_init
```

Set additional parameters: the `error_threshold` declares that any error value (in absolute numbers) smaller than this is to be considered zero.

```
<Integration results: integration results: TBP>+≡
```

```

    procedure :: set_error_threshold => integration_results_set_error_threshold
  <Integration results: procedures>+≡
    subroutine integration_results_set_error_threshold (results, error_threshold)
      class(integration_results_t), intent(inout) :: results
      real(default), intent(in) :: error_threshold
      results%error_threshold = error_threshold
    end subroutine integration_results_set_error_threshold

```

Output (ASCII format). The verbose format is used for writing the header in grid files.

```

  <Integration results: integration results: TBP>+≡
    procedure :: write => integration_results_write
  <Integration results: procedures>+≡
    subroutine integration_results_write (object, unit, verbose, suppress)
      class(integration_results_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: verbose
      logical, intent(in), optional :: suppress
      logical :: verb
      integer :: u, n
      u = given_output_unit (unit); if (u < 0) return
      verb = .false.; if (present (verbose)) verb = verbose
      if (.not. verb) then
        call write_dline (unit)
        if (object%n_it /= 0) then
          call write_header (object%entry(1)%process_type, unit, &
            logfile=.false.)
          call write_dline (unit)
          do n = 1, object%n_it
            if (n > 1) then
              if (object%entry(n)%pass /= object%entry(n-1)%pass) then
                call write_hline (unit)
                call integration_entry_write &
                  (object%average(object%entry(n-1)%pass), &
                    unit, suppress = suppress)
                call write_hline (unit)
              end if
            end if
            call integration_entry_write (object%entry(n), unit, &
              suppress = suppress)
          end do
          call write_hline(unit)
          call integration_entry_write (object%average(object%n_pass), &
            unit, suppress = suppress)
        else
          call msg_message ("[WHIZARD integration results: empty]", unit)
        end if
        call write_dline (unit)
      else
        write (u, *) "begin(integration_results)"
        write (u, *) "  n_pass = ", object%n_pass
        write (u, *) "  n_it = ", object%n_it
        if (object%n_it > 0) then

```

```

write (u, *) "begin(integration_pass)"
do n = 1, object%n_it
  if (n > 1) then
    if (object%entry(n)%pass /= object%entry(n-1)%pass) then
      write (u, *) "end(integration_pass)"
      write (u, *) "begin(integration_pass)"
    end if
  end if
  write (u, *) "begin(iteration)"
  call integration_entry_write (object%entry(n), unit, &
    verbose = verb, suppress = suppress)
  write (u, *) "end(iteration)"
end do
write (u, *) "end(integration_pass)"
end if
write (u, *) "end(integration_results)"
end if
flush (u)
end subroutine integration_results_write

```

During integration, we do not want to print all results at once, but each intermediate result as soon as we get it. Thus, the previous procedure is chopped in pieces. First piece: store the output unit and a flag whether we want to print to standard output as well. Then write the header if the results are still empty, i.e., before integration has started. The second piece writes a single result to the saved output channels. We call this from the `record` method, which can be called from the integrator directly. The third piece writes the average result, once a pass has been completed. The fourth piece writes a footer (if any), assuming that this is the final result.

(Integration results: integration results: TBP)+≡

```

procedure :: display_init => integration_results_display_init
procedure :: display_current => integration_results_display_current
procedure :: display_pass => integration_results_display_pass
procedure :: display_final => integration_results_display_final

```

(Integration results: procedures)+≡

```

subroutine integration_results_display_init &
  (results, process_type, screen, unit)
  class(integration_results_t), intent(inout) :: results
  integer, intent(in) :: process_type
  logical, intent(in) :: screen
  integer, intent(in), optional :: unit
  integer :: u
  if (present (unit)) results%unit = unit
  u = given_output_unit ()
  results%screen = screen
  if (results%n_it == 0) then
    if (results%screen) then
      call write_dline (u)
      call write_header (process_type, u, &
        logfile=.false.)
      call write_dline (u)
    end if
  end if

```

```

        if (results%unit /= 0) then
            call write_dline (results%unit)
            call write_header (process_type, results%unit, &
                logfile=.false.)
            call write_dline (results%unit)
        end if
    else
        if (results%screen) then
            call write_hline (u)
        end if
        if (results%unit /= 0) then
            call write_hline (results%unit)
        end if
    end if
end subroutine integration_results_display_init

subroutine integration_results_display_current (results, pacify)
    class(integration_results_t), intent(in) :: results
    integer :: u
    logical, intent(in), optional :: pacify
    u = given_output_unit ()
    if (results%screen) then
        call integration_entry_write (results%entry(results%n_it), u, &
            suppress = pacify)
    end if
    if (results%unit /= 0) then
        call integration_entry_write (results%entry(results%n_it), &
            results%unit, suppress = pacify)
    end if
end subroutine integration_results_display_current

subroutine integration_results_display_pass (results, pacify)
    class(integration_results_t), intent(in) :: results
    logical, intent(in), optional :: pacify
    integer :: u
    u = given_output_unit ()
    if (results%screen) then
        call write_hline (u)
        call integration_entry_write &
            (results%average(results%entry(results%n_it)%pass), &
            u, suppress = pacify)
    end if
    if (results%unit /= 0) then
        call write_hline (results%unit)
        call integration_entry_write &
            (results%average(results%entry(results%n_it)%pass), &
            results%unit, suppress = pacify)
    end if
end subroutine integration_results_display_pass

subroutine integration_results_display_final (results)
    class(integration_results_t), intent(inout) :: results
    integer :: u
    u = given_output_unit ()

```

```

    if (results%screen) then
        call write_dline (u)
    end if
    if (results%unit /= 0) then
        call write_dline (results%unit)
    end if
    results%screen = .false.
    results%unit = 0
end subroutine integration_results_display_final

```

Write a concise table of chain weights, i.e., the channel history where channels are collected by chains.

(Integration results: integration results: TBP)+≡

```

    procedure :: write_chain_weights => &
        integration_results_write_chain_weights

```

(Integration results: procedures)+≡

```

    subroutine integration_results_write_chain_weights (results, unit)
    class(integration_results_t), intent(in) :: results
    integer, intent(in), optional :: unit
    integer :: u, i, n
    u = given_output_unit (unit); if (u < 0) return
    if (allocated (results%entry(1)%chain_weights) .and. results%n_it /= 0) then
        call msg_message ("Phase-space chain (grove) weight history: " &
            // "(numbers in %)", unit)
        write (u, "(A9)", advance="no") "| chain |"
        do i = 1, integration_entry_get_n_groves (results%entry(1))
            write (u, "(1x,I3)", advance="no") i
        end do
        write (u, *)
        call write_dline (unit)
        do n = 1, results%n_it
            if (n > 1) then
                if (results%entry(n)%pass /= results%entry(n-1)%pass) then
                    call write_hline (unit)
                end if
            end if
            write (u, "(1x,I6,1x,A1)", advance="no") n, "|"
            call integration_entry_write_chain_weights (results%entry(n), unit)
        end do
        flush (u)
        call write_dline(unit)
    end if
end subroutine integration_results_write_chain_weights

```

Read the list from file. The file must be written using the `verbose` option of the writing routine.

(Integration results: procedures)+≡

```

    subroutine integration_results_read (results, unit)
    type(integration_results_t), intent(out) :: results
    integer, intent(in) :: unit
    character(80) :: buffer
    character :: equals

```



```

integer :: pass, it
read (unit, *) buffer
if (trim (adjustl (buffer)) /= "begin(integration_results)") then
    call read_err (); return
end if
read (unit, *) buffer, equals, results%n_pass
read (unit, *) buffer, equals, results%n_it
allocate (results%entry (results%n_it + RESULTS_CHUNK_SIZE))
allocate (results%average (results%n_it + RESULTS_CHUNK_SIZE))
it = 0
do pass = 1, results%n_pass
    read (unit, *) buffer
    if (trim (adjustl (buffer)) /= "begin(integration_pass)") then
        call read_err (); return
    end if
    READ_ENTRIES: do
        read (unit, *) buffer
        if (trim (adjustl (buffer)) /= "begin(iteration)") then
            exit READ_ENTRIES
        end if
        it = it + 1
        call integration_entry_read (results%entry(it), unit)
        read (unit, *) buffer
        if (trim (adjustl (buffer)) /= "end(iteration)") then
            call read_err (); return
        end if
    end do READ_ENTRIES
    if (trim (adjustl (buffer)) /= "end(integration_pass)") then
        call read_err (); return
    end if
    results%average(pass) = compute_average (results%entry, pass)
end do
read (unit, *) buffer
if (trim (adjustl (buffer)) /= "end(integration_results)") then
    call read_err (); return
end if
contains
subroutine read_err ()
    call msg_fatal ("Reading integration results from file: syntax error")
end subroutine read_err
end subroutine integration_results_read

```

Check integration results for consistency. We compare against an array of pass indices and call numbers. If there is a difference, up to the number of iterations done so far, we return failure. Dummy entries (where `pass = 0`) are ignored.

(Integration results: procedures)+≡

```

function integration_results_iterations_are_consistent &
    (results, pass, n_calls) result (flag)
    logical :: flag
    type(integration_results_t), intent(in) :: results
    integer, dimension(:), intent(in) :: pass, n_calls
    integer :: n_it
    n_it = results%n_it

```

```

flag = size (pass) >= n_it .and. size (n_calls) >= n_it
if (flag) then
    flag = all (results%entry(:n_it)%pass == pass(:n_it) &
               .and. &
               (results%entry(:n_it)%n_calls == n_calls(:n_it) &
               .or. &
               results%entry(:n_it)%process_type == PRC_UNKNOWN))
end if
end function integration_results_iterations_are_consistent

```

Discard all results starting from the specified iteration.

(Integration results: procedures)+≡

```

subroutine integration_results_discard (results, it)
    type(integration_results_t), intent(inout) :: results
    integer, intent(in) :: it
    if (it <= results%n_it) then
        select case (it)
        case (:1)
            results%n_it = 0
            results%n_pass = 0
            results%current_pass = 0
        case default
            results%n_it = it - 1
            results%n_pass = maxval (results%entry(1:results%n_it)%pass)
            results%current_pass = results%n_pass
        end select
    end if
end subroutine integration_results_discard

```

Expand the list of entries if the limit has been reached:

(Integration results: integration results: TBP)+≡

```

procedure :: expand => integration_results_expand

```

(Integration results: procedures)+≡

```

subroutine integration_results_expand (results)
    class(integration_results_t), intent(inout) :: results
    type(integration_entry_t), dimension(:), allocatable :: entry_tmp
    if (results%n_it == size (results%entry)) then
        allocate (entry_tmp (results%n_it))
        entry_tmp = results%entry
        deallocate (results%entry)
        allocate (results%entry (results%n_it + RESULTS_CHUNK_SIZE))
        results%entry(:results%n_it) = entry_tmp
        deallocate (entry_tmp)
    end if
    if (results%n_pass == size (results%average)) then
        allocate (entry_tmp (results%n_pass))
        entry_tmp = results%average
        deallocate (results%average)
        allocate (results%average (results%n_it + RESULTS_CHUNK_SIZE))
        results%average(:results%n_pass) = entry_tmp
        deallocate (entry_tmp)
    end if
end subroutine integration_results_expand

```

Increment the `current_pass` counter. Can be done before integration; after integration, the recording method may use the value of this counter to define the entry.

```

<Integration results: integration results: TBP>+≡
    procedure :: new_pass => integration_results_new_pass

<Integration results: procedures>+≡
    subroutine integration_results_new_pass (results)
        class(integration_results_t), intent(inout) :: results
        results%current_pass = results%current_pass + 1
    end subroutine integration_results_new_pass

```

Append a new entry to the list and, if appropriate, compute the average.

```

<Integration results: integration results: TBP>+≡
    procedure :: append_entry => integration_results_append_entry

<Integration results: procedures>+≡
    subroutine integration_results_append_entry (results, entry)
        class(integration_results_t), intent(inout) :: results
        type(integration_entry_t), intent(in), optional :: entry
        if (results%n_it == 0) then
            results%n_it = 1
            results%n_pass = 1
        else
            call results%expand ()
            if (present (entry)) then
                if (entry%pass /= results%entry(results%n_it)%pass) &
                    results%n_pass = results%n_pass + 1
            end if
            results%n_it = results%n_it + 1
        end if
        if (present (entry)) then
            results%entry(results%n_it) = entry
            results%average(results%n_pass) = &
                compute_average (results%entry, entry%pass)
        end if
    end subroutine integration_results_append_entry

```

Enter results into the results list. For the error value, we may compare them with a given threshold. This guards against numerical noise, if the exact error would be zero.

```

<Integration results: integration results: TBP>+≡
    procedure :: append => integration_results_append

<Integration results: procedures>+≡
    subroutine integration_results_append (results, &
        n_it, n_calls, &
        integral, error, efficiency, &
        chain_weights)
        class(integration_results_t), intent(inout) :: results
        integer, intent(in) :: n_it, n_calls
        real(default), intent(in) :: integral, error, efficiency

```

```

real(default), dimension(:), intent(in), optional :: chain_weights
logical :: improved
type(integration_entry_t) :: entry
real(default) :: err_checked
if (results%n_it /= 0) then
    improved = abs(accuracy (integral, error, n_calls)) &
        < abs(integration_entry_get_accuracy (results%entry(results%n_it)))
else
    improved = .true.
end if
if (abs (error) >= results%error_threshold) then
    err_checked = error
else
    err_checked = 0
end if
call integration_entry_init (entry, &
    results%process_type, results%current_pass, &
    results%n_it+1, n_it, n_calls, improved, &
    integral, err_checked, efficiency, &
    chain_weights=chain_weights)
call results%append_entry (entry)
end subroutine integration_results_append

```

Enter an empty result into the results list.

```

<Integration results: public>+=
    public :: integration_results_append_null

<Integration results: procedures>+=
    subroutine integration_results_append_null (results, pass, n_it)
        type(integration_results_t), intent(inout) :: results
        integer, intent(in) :: pass, n_it
        type(integration_entry_t) :: entry
        call integration_entry_init (entry, &
            PRC_UNKNOWN, results%current_pass, n_it, 1, 0, .false., &
            0._default, 0._default, 0._default)
        call results%append_entry (entry)
    end subroutine integration_results_append_null

```

Record an integration pass executed by an mci integrator object.

There is a tolerance below we treat an error (relative to the integral) as zero.

```

<Integration results: parameters>+=
    real(default), parameter, public :: INTEGRATION_ERROR_TOLERANCE = 1e-10

<Integration results: integration results: TBP>+=
    procedure :: record => integration_results_record

<Integration results: procedures>+=
    subroutine integration_results_record &
        (object, n_it, n_calls, integral, error, efficiency, &
        chain_weights, suppress)
        class(integration_results_t), intent(inout) :: object
        integer, intent(in) :: n_it, n_calls
        real(default), intent(in) :: integral, error, efficiency
        real(default), dimension(:), intent(in), optional :: chain_weights

```

```

real(default) :: err
logical, intent(in), optional :: suppress

if (abs (error) >= abs (integral) * INTEGRATION_ERROR_TOLERANCE) then
    err = error
else
    err = 0
end if
call object%append (n_it, n_calls, integral, err, efficiency, chain_weights)
call object%display_current (suppress)
end subroutine integration_results_record

```

19.3.3 Access results

Return true if the results object has entries.

```

<Integration results: integration results: TBP>+≡
procedure :: exist => integration_results_exist

```

```

<Integration results: procedures>+≡
function integration_results_exist (results) result (flag)
    logical :: flag
    class(integration_results_t), intent(in) :: results
    flag = results%n_pass > 0
end function integration_results_exist

```

Retrieve information from the results record. If **last** is set and true, take the last iteration. If it is set instead, take this iteration. If **pass** is set, take this average. If none is set, take the final average.

If the result would be invalid, the entry is not assigned. Due to default initialization, this returns a null entry.

```

<Integration results: integration results: TBP>+≡
procedure :: get_entry => results_get_entry

```

```

<Integration results: procedures>+≡
function results_get_entry (results, last, it, pass) result (entry)
    class(integration_results_t), intent(in) :: results
    type(integration_entry_t) :: entry
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    if (present (last)) then
        if (allocated (results%entry) .and. results%n_it > 0) then
            entry = results%entry(results%n_it)
        else
            call error ()
        end if
    else if (present (it)) then
        if (allocated (results%entry) .and. it > 0 .and. it <= results%n_it) then
            entry = results%entry(it)
        else
            call error ()
        end if
    else if (present (pass)) then

```

```

        if (allocated (results%average) &
            .and. pass > 0 .and. pass <= results%n_pass) then
            entry = results%average (pass)
        else
            call error ()
        end if
    else
        if (allocated (results%average) .and. results%n_pass > 0) then
            entry = results%average (results%n_pass)
        else
            call error ()
        end if
    end if
contains
    subroutine error ()
        call msg_fatal ("Requested integration result is not available")
    end subroutine error
end function results_get_entry

```

The individual procedures. The `results` record should have the `target` attribute, but only locally within the function.

(Integration results: integration results: TBP)+≡

```

procedure :: get_n_calls => integration_results_get_n_calls
procedure :: get_integral => integration_results_get_integral
procedure :: get_error => integration_results_get_error
procedure :: get_accuracy => integration_results_get_accuracy
procedure :: get_chi2 => integration_results_get_chi2
procedure :: get_efficiency => integration_results_get_efficiency

```

(Integration results: procedures)+≡

```

function integration_results_get_n_calls (results, last, it, pass) &
    result (n_calls)
    class(integration_results_t), intent(in), target :: results
    integer :: n_calls
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    n_calls = integration_entry_get_n_calls &
        (results%get_entry (last, it, pass))
end function integration_results_get_n_calls

function integration_results_get_integral (results, last, it, pass) &
    result (integral)
    class(integration_results_t), intent(in), target :: results
    real(default) :: integral
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    integral = integration_entry_get_integral &
        (results%get_entry (last, it, pass))
end function integration_results_get_integral

function integration_results_get_error (results, last, it, pass) &
    result (error)
    class(integration_results_t), intent(in), target :: results
    real(default) :: error

```

```

    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    error = integration_entry_get_error &
        (results%get_entry (last, it, pass))
end function integration_results_get_error

function integration_results_get_accuracy (results, last, it, pass) &
    result (accuracy)
    class(integration_results_t), intent(in), target :: results
    real(default) :: accuracy
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    accuracy = integration_entry_get_accuracy &
        (results%get_entry (last, it, pass))
end function integration_results_get_accuracy

function integration_results_get_chi2 (results, last, it, pass) &
    result (chi2)
    class(integration_results_t), intent(in), target :: results
    real(default) :: chi2
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    chi2 = integration_entry_get_chi2 &
        (results%get_entry (last, it, pass))
end function integration_results_get_chi2

function integration_results_get_efficiency (results, last, it, pass) &
    result (efficiency)
    class(integration_results_t), intent(in), target :: results
    real(default) :: efficiency
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    efficiency = integration_entry_get_efficiency &
        (results%get_entry (last, it, pass))
end function integration_results_get_efficiency

```

Return the last pass index and the index of the last iteration *within* the last pass. The third routine returns the absolute index of the last iteration.

(Integration results: procedures)+≡

```

function integration_results_get_current_pass (results) result (pass)
    integer :: pass
    type(integration_results_t), intent(in) :: results
    pass = results%n_pass
end function integration_results_get_current_pass

function integration_results_get_current_it (results) result (it)
    integer :: it
    type(integration_results_t), intent(in) :: results
    if (allocated (results%entry)) then
        it = count (results%entry(1:results%n_it)%pass == results%n_pass)
    else
        it = 0
    end if
end function

```

```

end function integration_results_get_current_it

function integration_results_get_last_it (results) result (it)
  integer :: it
  type(integration_results_t), intent(in) :: results
  it = results%n_it
end function integration_results_get_last_it

```

Return the index of the best iteration (lowest accuracy value) within the current pass. If none qualifies, return zero.

(Integration results: procedures)+≡

```

function integration_results_get_best_it (results) result (it)
  integer :: it
  type(integration_results_t), intent(in) :: results
  integer :: i
  real(default) :: acc, acc_best
  acc_best = -1
  it = 0
  do i = 1, results%n_it
    if (results%entry(i)%pass == results%n_pass) then
      acc = integration_entry_get_accuracy (results%entry(i))
      if (acc_best < 0 .or. acc <= acc_best) then
        acc_best = acc
        it = i
      end if
    end if
  end do
end function integration_results_get_best_it

```

Compute the MD5 sum by printing everything and checksumming the resulting file.

(Integration results: procedures)+≡

```

function integration_results_get_md5sum (results) result (md5sum_results)
  character(32) :: md5sum_results
  type(integration_results_t), intent(in) :: results
  integer :: u
  u = free_unit ()
  open (unit = u, status = "scratch", action = "readwrite")
  call integration_results_write (results, u, verbose=.true.)
  rewind (u)
  md5sum_results = md5sum (u)
  close (u)
end function integration_results_get_md5sum

```

This is (ab)used to suppress numerical noise when integrating constant matrix elements.

(Integration results: integration results: TBP)+≡

```

procedure :: pacify => integration_results_pacify

```

(Integration results: procedures)+≡

```

subroutine integration_results_pacify (results, efficiency_reset)
  class(integration_results_t), intent(inout) :: results
  logical, intent(in), optional :: efficiency_reset

```



```

integer :: i
logical :: reset
reset = .false.
if (present (efficiency_reset)) reset = efficiency_reset
if (allocated (results%entry)) then
  do i = 1, size (results%entry)
    call pacify (results%entry(i)%error, &
      results%entry(i)%integral * 1.E-9_default)
    if (reset) results%entry(i)%efficiency = 1
  end do
end if
if (allocated (results%average)) then
  do i = 1, size (results%average)
    call pacify (results%average(i)%error, &
      results%average(i)%integral * 1.E-9_default)
    if (reset) results%average(i)%efficiency = 1
  end do
end if
end subroutine integration_results_pacify

```

```

<Integration results: integration results: TBP>+≡
  procedure :: record_correction => integration_results_record_correction

<Integration results: procedures>+≡
  subroutine integration_results_record_correction (object, corr, err)
    class(integration_results_t), intent(inout) :: object
    real(default), intent(in) :: corr, err
    integer :: u
    u = given_output_unit ()
    if (object%screen) then
      call write_hline (u)
      call msg_message ("NLO Results: 0(alpha_s+1)/0(alpha_s)")
      write(u,'(1X,F6.4,A4,F7.5)') corr, ' +- ', err
    end if
  end subroutine integration_results_record_correction

```

19.3.4 Results display

Write a driver file for history visualization.

The ratio of y range over y value must not become too small, otherwise we run into an arithmetic overflow in GAMELAN. 2% appears to be safe.

```

<Integration results: parameters>+≡
  real, parameter, public :: GML_MIN_RANGE_RATIO = 0.02

<Integration results: public>+≡
  public :: integration_results_write_driver

<Integration results: procedures>+≡
  subroutine integration_results_write_driver (results, filename, eff_reset)
    type(integration_results_t), intent(inout) :: results
    type(string_t), intent(in) :: filename
    logical, intent(in), optional :: eff_reset
    type(string_t) :: file_tex

```

```

integer :: unit
integer :: n, i, n_pass, pass
integer, dimension(:), allocatable :: ipass
real(default) :: ymin, ymax, yavg, ydif, y0, y1
logical :: reset
file_tex = filename // ".tex"
unit = free_unit ()
open (unit=unit, file=char(file_tex), action="write", status="replace")
reset = .false.; if (present (eff_reset)) reset = eff_reset
n = results%n_it
n_pass = results%n_pass
allocate (ipass (results%n_pass))
ipass(1) = 0
pass = 2
do i = 1, n-1
    if (integration_entry_get_pass (results%entry(i)) &
        /= integration_entry_get_pass (results%entry(i+1))) then
        ipass(pass) = i
        pass = pass + 1
    end if
end do
ymin = minval (integration_entry_get_integral (results%entry(:n)) &
    - integration_entry_get_error (results%entry(:n)))
ymax = maxval (integration_entry_get_integral (results%entry(:n)) &
    + integration_entry_get_error (results%entry(:n)))
yavg = (ymax + ymin) / 2
ydif = (ymax - ymin)
if (ydif * 1.5 > GML_MIN_RANGE_RATIO * yavg) then
    y0 = yavg - ydif * 0.75
    y1 = yavg + ydif * 0.75
else
    y0 = yavg * (1 - GML_MIN_RANGE_RATIO / 2)
    y1 = yavg * (1 + GML_MIN_RANGE_RATIO / 2)
end if
write (unit, "(A)") "\documentclass{article}"
write (unit, "(A)") "\usepackage{a4wide}"
write (unit, "(A)") "\usepackage{gamelan}"
write (unit, "(A)") "\usepackage{amsmath}"
write (unit, "(A)") ""
write (unit, "(A)") "\begin{document}"
write (unit, "(A)") "\begin{gmlfile}"
write (unit, "(A)") "\section*{Integration Results Display}"
write (unit, "(A)") ""
write (unit, "(A)") "Process: \verb|" // char (filename) // "|"
write (unit, "(A)") ""
write (unit, "(A)") "\vspace*{2\baselineskip}"
write (unit, "(A)") "\unitlength 1mm"
write (unit, "(A)") "\begin{gmlcode}"
write (unit, "(A)") " picture sym; sym = fshape (circle scaled 1mm());"
write (unit, "(A)") " color col.band; col.band = 0.9white;"
write (unit, "(A)") " color col.eband; col.eband = 0.98white;"
write (unit, "(A)") "\end{gmlcode}"
write (unit, "(A)") "\begin{gmlgraph*}(130,180)[history]"
write (unit, "(A)") " setup (linear, linear);"

```

```

write (unit, "(A,I0,A)") " history.n_pass = ", n_pass, ";";
write (unit, "(A,I0,A)") " history.n_it = ", n, ";";
write (unit, "(A,A,A)") " history.y0 = #""", char (mp_format (y0)), """,";
write (unit, "(A,A,A)") " history.y1 = #""", char (mp_format (y1)), """,";
write (unit, "(A)") &
    " graphrange (#0.5, history.y0), (#(n+0.5), history.y1);";
do pass = 1, n_pass
    write (unit, "(A,I0,A,I0,A)") &
        " history.pass[" , pass, "] = ", ipass(pass), ";";
    write (unit, "(A,I0,A,A,A)") &
        " history.avg[" , pass, "] = #""", &
        char (mp_format &
            (integration_entry_get_integral (results%average(pass))))), &
        """,";
    write (unit, "(A,I0,A,A,A)") &
        " history.err[" , pass, "] = #""", &
        char (mp_format &
            (integration_entry_get_error (results%average(pass))))), &
        """,";
    write (unit, "(A,I0,A,A,A)") &
        " history.chi[" , pass, "] = #""", &
        char (mp_format &
            (integration_entry_get_chi2 (results%average(pass))))), &
        """,";
end do
write (unit, "(A,I0,A,I0,A)") &
    " history.pass[" , n_pass + 1, "] = ", n, ";";
write (unit, "(A)") " for i = 1 upto history.n_pass:"
write (unit, "(A)") " if history.chi[i] greater one:"
write (unit, "(A)") " fill plot ("
write (unit, "(A)") &
    " (#(history.pass[i] +.5), " &
    // "history.avg[i] minus history.err[i] times history.chi[i]),"
write (unit, "(A)") &
    " (#(history.pass[i+1]+.5), " &
    // "history.avg[i] minus history.err[i] times history.chi[i]),"
write (unit, "(A)") &
    " (#(history.pass[i+1]+.5), " &
    // "history.avg[i] plus history.err[i] times history.chi[i]),"
write (unit, "(A)") &
    " (#(history.pass[i] +.5), " &
    // "history.avg[i] plus history.err[i] times history.chi[i])"
write (unit, "(A)") " ) withcolor col.eband fi;"
write (unit, "(A)") " fill plot ("
write (unit, "(A)") &
    " (#(history.pass[i] +.5), history.avg[i] minus history.err[i]),"
write (unit, "(A)") &
    " (#(history.pass[i+1]+.5), history.avg[i] minus history.err[i]),"
write (unit, "(A)") &
    " (#(history.pass[i+1]+.5), history.avg[i] plus history.err[i]),"
write (unit, "(A)") &
    " (#(history.pass[i] +.5), history.avg[i] plus history.err[i])"
write (unit, "(A)") " ) withcolor col.band;"
write (unit, "(A)") " draw plot ("

```

```

write (unit, "(A)") &
"      (#(history.pass[i] +.5), history.avg[i]),"
write (unit, "(A)") &
"      (#(history.pass[i+1]+.5), history.avg[i])"
write (unit, "(A)") "      ) dashed evenly;"
write (unit, "(A)") "    endfor"
write (unit, "(A)") "  for i = 1 upto history.n_pass + 1:"
write (unit, "(A)") "    draw plot ("
write (unit, "(A)") &
"      (#(history.pass[i]+.5), history.y0),"
write (unit, "(A)") &
"      (#(history.pass[i]+.5), history.y1)"
write (unit, "(A)") "      ) dashed withdots;"
write (unit, "(A)") "    endfor"
do i = 1, n
  write (unit, "(A,I0,A,A,A,A,A)") " plot (history) (#", &
    i, ", #""", &
    char (mp_format (integration_entry_get_integral (results%entry(i))),&
    """) vbar #""", &
    char (mp_format (integration_entry_get_error (results%entry(i))), &
    """);"
end do
write (unit, "(A)") " draw piecewise from (history) " &
// "withsymbol sym;"
write (unit, "(A)") " fullgrid.lr (5,20);"
write (unit, "(A)") " standardgrid.bt (n);"
write (unit, "(A)") " begingmleps ""Whizard-Logo.eps"";"
write (unit, "(A)") "   base := (120*unitlength,170*unitlength);"
write (unit, "(A)") "   height := 9.6*unitlength;"
write (unit, "(A)") "   width := 11.2*unitlength;"
write (unit, "(A)") " endgmleps;"
write (unit, "(A)") "\end{gmlgraph*}"
write (unit, "(A)") "\end{gmlfile}"
write (unit, "(A)") "\clearpage"
write (unit, "(A)") "\begin{verbatim}"
if (reset) then
  call results%pacify (reset)
end if
call integration_results_write (results, unit)
write (unit, "(A)") "\end{verbatim}"
write (unit, "(A)") "\end{document}"
close (unit)
end subroutine integration_results_write_driver

```

Call L^AT_EX and Metapost for the history driver file, and convert to PS and PDF.

(Integration results: public)+≡

public :: integration_results_compile_driver

(Integration results: procedures)+≡

```

subroutine integration_results_compile_driver (results, filename, os_data)
  type(integration_results_t), intent(in) :: results
  type(string_t), intent(in) :: filename
  type(os_data_t), intent(in) :: os_data
  integer :: unit_dev, status

```

```

type(string_t) :: file_tex, file_dvi, file_ps, file_pdf, file_mp
type(string_t) :: setenv_tex, setenv_mp, pipe, pipe_dvi
if (.not. os_data%event_analysis) then
    call msg_warning ("Skipping integration history display " &
        // "because latex or mpost is not available")
    return
end if
file_tex = filename // ".tex"
file_dvi = filename // ".dvi"
file_ps = filename // ".ps"
file_pdf = filename // ".pdf"
file_mp = filename // ".mp"
call msg_message ("Creating integration history display "&
    // char (file_ps) // " and " // char (file_pdf))
BLOCK: do
    unit_dev = free_unit ()
    open (file = "/dev/null", unit = unit_dev, &
        action = "write", iostat = status)
    if (status /= 0) then
        pipe = ""
        pipe_dvi = ""
    else
        pipe = " > /dev/null"
        pipe_dvi = " 2>/dev/null 1>/dev/null"
    end if
    close (unit_dev)
    if (os_data%whizard_texpath /= "") then
        setenv_tex = &
            "TEXINPUTS=" // os_data%whizard_texpath // ":$TEXINPUTS "
        setenv_mp = &
            "MPINPUTS=" // os_data%whizard_texpath // ":$MPINPUTS "
    else
        setenv_tex = ""
        setenv_mp = ""
    end if
    call os_system_call (setenv_tex // os_data%latex // " " // &
        file_tex // pipe, status)
    if (status /= 0) exit BLOCK
    if (os_data%gml /= "") then
        call os_system_call (setenv_mp // os_data%gml // " " // &
            file_mp // pipe, status)
    else
        call msg_error ("Could not use GAMELAN/MetaPOST.")
        exit BLOCK
    end if
    if (status /= 0) exit BLOCK
    call os_system_call (setenv_tex // os_data%latex // " " // &
        file_tex // pipe, status)
    if (status /= 0) exit BLOCK
    if (os_data%event_analysis_ps) then
        call os_system_call (os_data%dvips // " " // &
            file_dvi // pipe_dvi, status)
        if (status /= 0) exit BLOCK
    else

```

```

        call msg_warning ("Skipping PostScript generation because dvips " &
            // "is not available")
        exit BLOCK
    end if
    if (os_data%event_analysis_pdf) then
        call os_system_call (os_data%ps2pdf // " " // &
            file_ps, status)
        if (status /= 0) exit BLOCK
    else
        call msg_warning ("Skipping PDF generation because ps2pdf " &
            // "is not available")
        exit BLOCK
    end if
    exit BLOCK
end do BLOCK
if (status /= 0) then
    call msg_error ("Unable to compile integration history display")
end if
end subroutine integration_results_compile_driver

```

19.4 Simple midpoint integration

This is a most simple implementation of an integrator. The algorithm is the straightforward multi-dimensional midpoint rule, i.e., the integration hypercube is binned uniformly, the integrand is evaluated at the midpoints of each bin, and the result is the average. The binning is equivalent for all integration dimensions.

This rule is accurate to the order h^2 , where h is the bin width. Given that $h = N^{-1/d}$, where d is the integration dimension and N is the total number of sampling points, we get a relative error of order $N^{-2/d}$. This is superior to MC integration if $d < 4$, and equivalent if $d = 4$. It is not worse than higher-order formulas (such as Gauss integration) if the integrand is not smooth, e.g., if it contains cuts.

The integrator is specifically single-channel. However, we do not limit the dimension.

```
<mci_midpoint.f90>≡  
  <File header>  
  
  module mci_midpoint  
  
    use kinds  
    <Use strings>  
    use io_units  
    use unit_tests  
    use diagnostics  
  
    use phs_base  
    use rng_base  
    use mci_base  
  
    <Standard module head>  
  
    <MCI midpoint: public>  
  
    <MCI midpoint: types>  
  
    <MCI midpoint: test types>  
  
    contains  
  
    <MCI midpoint: procedures>  
  
    <MCI midpoint: tests>  
  
  end module mci_midpoint
```

19.4.1 Integrator

The object contains the methods for integration and event generation. For the actual work and data storage, it spawns an instance object.

After an integration pass, we update the `max` parameter to indicate the maximum absolute value of the integrand that the integrator encountered. This

is required for event generation.

```

<MCI midpoint: public>≡
    public :: mci_midpoint_t

<MCI midpoint: types>≡
    type, extends (mci_t) :: mci_midpoint_t
        integer :: n_dim_binned = 0
        logical, dimension(:), allocatable :: dim_is_binned
        logical :: calls_known = .false.
        integer :: n_calls = 0
        integer :: n_calls_pos = 0
        integer :: n_calls_nul = 0
        integer :: n_calls_neg = 0
        real(default) :: integral_pos = 0
        real(default) :: integral_neg = 0
        integer, dimension(:), allocatable :: n_bin
        logical :: max_known = .false.
        real(default) :: max = 0
        real(default) :: min = 0
        real(default) :: max_abs = 0
        real(default) :: min_abs = 0
    contains
        <MCI midpoint: mci midpoint: TBP>
    end type mci_midpoint_t

```

Finalizer: base version is sufficient

```

<MCI midpoint: mci midpoint: TBP>≡
    procedure :: final => mci_midpoint_final

<MCI midpoint: procedures>≡
    subroutine mci_midpoint_final (object)
        class(mci_midpoint_t), intent(inout) :: object
        call object%base_final ()
    end subroutine mci_midpoint_final

```

Output.

```

<MCI midpoint: mci midpoint: TBP>+≡
    procedure :: write => mci_midpoint_write

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_write (object, unit, pacify, md5sum_version)
        class(mci_midpoint_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: pacify
        logical, intent(in), optional :: md5sum_version
        integer :: u, i
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Single-channel midpoint rule integrator:"
        call object%base_write (u, pacify, md5sum_version)
        if (object%n_dim_binned < object%n_dim) then
            write (u, "(3x,A,99(1x,I0))") "Flat dimensions      =", &
                pack ([i, i = 1, object%n_dim], mask = .not. object%dim_is_binned)
            write (u, "(3x,A,I0)") "Number of binned dim =", object%n_dim_binned
        end if
    end subroutine mci_midpoint_write

```



```

if (object%calls_known) then
  write (u, "(3x,A,99(1x,I0))") "Number of bins      =", object%n_bin
  write (u, "(3x,A,I0)") "Number of calls      =", object%n_calls
  if (object%n_calls_pos /= object%n_calls) then
    write (u, "(3x,A,I0)") "  positive value    =", object%n_calls_pos
    write (u, "(3x,A,I0)") "  zero value       =", object%n_calls_nul
    write (u, "(3x,A,I0)") "  negative value   =", object%n_calls_neg
    write (u, "(3x,A,ES17.10)") &
      "Integral (pos. part) =", object%integral_pos
    write (u, "(3x,A,ES17.10)") &
      "Integral (neg. part) =", object%integral_neg
  end if
end if
if (object%max_known) then
  write (u, "(3x,A,ES17.10)") "Maximum of integrand =", object%max
  write (u, "(3x,A,ES17.10)") "Minimum of integrand =", object%min
  if (object%min /= object%min_abs) then
    write (u, "(3x,A,ES17.10)") "Maximum (abs. value) =", object%max_abs
    write (u, "(3x,A,ES17.10)") "Minimum (abs. value) =", object%min_abs
  end if
end if
if (allocated (object%rng)) call object%rng%write (u)
end subroutine mci_midpoint_write

```

Startup message: short version.

```

<MCI midpoint: mci midpoint: TBP>+≡
  procedure :: startup_message => mci_midpoint_startup_message

<MCI midpoint: procedures>+≡
  subroutine mci_midpoint_startup_message (mci, unit, n_calls)
    class(mci_midpoint_t), intent(in) :: mci
    integer, intent(in), optional :: unit, n_calls
    call mci%base_startup_message (unit = unit, n_calls = n_calls)
    if (mci%n_dim_binned < mci%n_dim) then
      write (msg_buffer, "(A,2(1x,I0,1x,A))") &
        "Integrator: Midpoint rule:", &
        mci%n_dim_binned, "binned dimensions"
    else
      write (msg_buffer, "(A,2(1x,I0,1x,A))") &
        "Integrator: Midpoint rule"
    end if
    call msg_message (unit = unit)
  end subroutine mci_midpoint_startup_message

```

The number of channels must be one.

```

<MCI midpoint: mci midpoint: TBP>+≡
  procedure :: set_dimensions => mci_midpoint_set_dimensions

<MCI midpoint: procedures>+≡
  subroutine mci_midpoint_set_dimensions (mci, n_dim, n_channel)
    class(mci_midpoint_t), intent(inout) :: mci
    integer, intent(in) :: n_dim
    integer, intent(in) :: n_channel
    if (n_channel == 1) then

```

```

        mci%n_channel = n_channel
        mci%n_dim = n_dim
        allocate (mci%dim_is_binned (mci%n_dim))
        mci%dim_is_binned = .true.
        mci%n_dim_binned = count (mci%dim_is_binned)
        allocate (mci%n_bin (mci%n_dim))
        mci%n_bin = 0
    else
        call msg_fatal ("Attempt to initialize single-channel integrator &
            &for multiple channels")
    end if
end subroutine mci_midpoint_set_dimensions

```

Declare particular dimensions as flat. These dimensions will not be binned.

```

<MCI midpoint: mci midpoint: TBP>+≡
    procedure :: declare_flat_dimensions => mci_midpoint_declare_flat_dimensions

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_declare_flat_dimensions (mci, dim_flat)
        class(mci_midpoint_t), intent(inout) :: mci
        integer, dimension(:), intent(in) :: dim_flat
        integer :: d
        mci%n_dim_binned = mci%n_dim - size (dim_flat)
        do d = 1, size (dim_flat)
            mci%dim_is_binned(dim_flat(d)) = .false.
        end do
        mci%n_dim_binned = count (mci%dim_is_binned)
    end subroutine mci_midpoint_declare_flat_dimensions

```

Declare particular channels as equivalent. This has no effect.

```

<MCI midpoint: mci midpoint: TBP>+≡
    procedure :: declare_equivalences => mci_midpoint_ignore_equivalences

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_ignore_equivalences (mci, channel, dim_offset)
        class(mci_midpoint_t), intent(inout) :: mci
        type(phs_channel_t), dimension(:), intent(in) :: channel
        integer, intent(in) :: dim_offset
    end subroutine mci_midpoint_ignore_equivalences

```

Allocate instance with matching type.

```

<MCI midpoint: mci midpoint: TBP>+≡
    procedure :: allocate_instance => mci_midpoint_allocate_instance

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_allocate_instance (mci, mci_instance)
        class(mci_midpoint_t), intent(in) :: mci
        class(mci_instance_t), intent(out), pointer :: mci_instance
        allocate (mci_midpoint_instance_t :: mci_instance)
    end subroutine mci_midpoint_allocate_instance

```

Integrate. The number of dimensions is arbitrary. We make sure that the number of calls is evenly distributed among the dimensions. The actual number of calls will typically be smaller than the requested number, but never smaller than 1.

The sampling over a variable number of dimensions implies a variable number of nested loops. We implement this by a recursive subroutine, one loop in each recursion level.

The number of iterations `n_it` is ignored. Also, the error is set to zero in the current implementation.

With this integrator, we allow the calculation to abort immediately when forced by a signal. There is no state that we can save, hence we do not catch an interrupt.

```

<MCI midpoint: mci midpoint: TBP>+≡
  procedure :: integrate => mci_midpoint_integrate

<MCI midpoint: procedures>+≡
  subroutine mci_midpoint_integrate (mci, instance, sampler, n_it, n_calls, &
    results, pacify)
    class(mci_midpoint_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout) :: instance
    class(mci_sampler_t), intent(inout) :: sampler
    integer, intent(in) :: n_it
    integer, intent(in) :: n_calls
    logical, intent(in), optional :: pacify
    class(mci_results_t), intent(inout), optional :: results
    real(default), dimension(:), allocatable :: x
    real(default) :: integral, integral_pos, integral_neg
    integer :: n_bin
    select type (instance)
    type is (mci_midpoint_instance_t)
      allocate (x (mci%n_dim))
      integral = 0
      integral_pos = 0
      integral_neg = 0
      select case (mci%n_dim_binned)
      case (1)
        n_bin = n_calls
      case (2:)
        n_bin = max (int (n_calls ** (1. / mci%n_dim_binned)), 1)
      end select
      where (mci%dim_is_binned)
        mci%n_bin = n_bin
      elsewhere
        mci%n_bin = 1
      end where
      mci%n_calls = product (mci%n_bin)
      mci%n_calls_pos = 0
      mci%n_calls_nul = 0
      mci%n_calls_neg = 0
      mci%calls_known = .true.
      call sample_dim (mci%n_dim)
      mci%integral = integral / mci%n_calls
      mci%integral_pos = integral_pos / mci%n_calls

```

```

        mci%integral_neg = integral_neg / mci%n_calls
        mci%integral_known = .true.
        call instance%set_max ()
        if (present (results)) then
            call results%record (1, mci%n_calls, &
                mci%integral, mci%error, mci%efficiency)
        end if
    end select
contains
    recursive subroutine sample_dim (d)
        integer, intent(in) :: d
        integer :: i
        real(default) :: value
        do i = 1, mci%n_bin(d)
            x(d) = (i - 0.5_default) / mci%n_bin(d)
            if (d > 1) then
                call sample_dim (d - 1)
            else
                if (signal_is_pending ()) return
                call instance%evaluate (sampler, 1, x)
                value = instance%get_value ()
                if (value > 0) then
                    mci%n_calls_pos = mci%n_calls_pos + 1
                    integral = integral + value
                    integral_pos = integral_pos + value
                else if (value == 0) then
                    mci%n_calls_nul = mci%n_calls_nul + 1
                else
                    mci%n_calls_neg = mci%n_calls_neg + 1
                    integral = integral + value
                    integral_neg = integral_neg + value
                end if
            end if
        end do
    end subroutine sample_dim
end subroutine mci_midpoint_integrate

```

Simulation initializer and finalizer: nothing to do here.

```

<MCI midpoint: mci midpoint: TBP>+≡
    procedure :: prepare_simulation => mci_midpoint_ignore_prepare_simulation
<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_ignore_prepare_simulation (mci)
        class(mci_midpoint_t), intent(inout) :: mci
    end subroutine mci_midpoint_ignore_prepare_simulation

```

Generate weighted event.

```

<MCI midpoint: mci midpoint: TBP>+≡
    procedure :: generate_weighted_event => mci_midpoint_generate_weighted_event
<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_generate_weighted_event (mci, instance, sampler)
        class(mci_midpoint_t), intent(inout) :: mci
        class(mci_instance_t), intent(inout), target :: instance
    end subroutine mci_midpoint_generate_weighted_event

```

```

class(mci_sampler_t), intent(inout), target :: sampler
real(default), dimension(mci%n_dim) :: x
select type (instance)
type is (mci_midpoint_instance_t)
  call mci%rng%generate (x)
  call instance%evaluate (sampler, 1, x)
  instance%excess_weight = 0
end select
end subroutine mci_midpoint_generate_weighted_event

```

For unweighted events, we generate weighted events and apply a simple rejection step to the relative event weight, until an event passes.

Note that we use the `max_abs` value stored in the configuration record, not the one stored in the instance. The latter may change during event generation. After an event generation pass is over, we may update the value for a subsequent pass.

```

<MCI midpoint: mci midpoint: TBP>+≡
  procedure :: generate_unweighted_event => &
    mci_midpoint_generate_unweighted_event

<MCI midpoint: procedures>+≡
  subroutine mci_midpoint_generate_unweighted_event (mci, instance, sampler)
    class(mci_midpoint_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout), target :: instance
    class(mci_sampler_t), intent(inout), target :: sampler
    real(default) :: x, norm, int
    select type (instance)
    type is (mci_midpoint_instance_t)
      if (mci%max_known .and. mci%max_abs > 0) then
        norm = abs (mci%max_abs * instance%safety_factor)
        REJECTION: do
          call mci%generate_weighted_event (instance, sampler)
          if (sampler%is_valid ()) then
            call mci%rng%generate (x)
            int = abs (instance%integrand)
            if (x * norm <= int) then
              if (norm > 0 .and. norm < int) then
                instance%excess_weight = int / norm - 1
              end if
            end if
            exit REJECTION
          end if
        end do REJECTION
      else
        call msg_fatal ("Unweighted event generation: &
          &maximum of integrand is zero or unknown")
      end if
    end select
  end subroutine mci_midpoint_generate_unweighted_event

```

Rebuild an event, using the state input.

```

<MCI midpoint: mci midpoint: TBP>+≡

```

```

    procedure :: rebuild_event => mci_midpoint_rebuild_event
  <MCI midpoint: procedures>+≡
    subroutine mci_midpoint_rebuild_event (mci, instance, sampler, state)
      class(mci_midpoint_t), intent(inout) :: mci
      class(mci_instance_t), intent(inout) :: instance
      class(mci_sampler_t), intent(inout) :: sampler
      class(mci_state_t), intent(in) :: state
      select type (instance)
        type is (mci_midpoint_instance_t)
          call instance%recall (sampler, state)
        end select
      end subroutine mci_midpoint_rebuild_event

```

19.4.2 Integrator instance

Covering the case of flat dimensions, we store a complete x array. This is filled when generating events.

```

  <MCI midpoint: public>+≡
    public :: mci_midpoint_instance_t

  <MCI midpoint: types>+≡
    type, extends (mci_instance_t) :: mci_midpoint_instance_t
      type(mci_midpoint_t), pointer :: mci => null ()
      logical :: max_known = .false.
      real(default) :: max = 0
      real(default) :: min = 0
      real(default) :: max_abs = 0
      real(default) :: min_abs = 0
      real(default) :: safety_factor = 1
      real(default) :: excess_weight = 0
    contains
      <MCI midpoint: mci midpoint instance: TBP>
    end type mci_midpoint_instance_t

```

Output.

```

  <MCI midpoint: mci midpoint instance: TBP>≡
    procedure :: write => mci_midpoint_instance_write

  <MCI midpoint: procedures>+≡
    subroutine mci_midpoint_instance_write (object, unit, pacify)
      class(mci_midpoint_instance_t), intent(in) :: object
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: pacify
      integer :: u
      u = given_output_unit (unit)
      write (u, "(1x,A,9(1x,F12.10))") "x =", object%x(:,1)
      write (u, "(1x,A,ES19.12)") "Integrand = ", object%integrand
      write (u, "(1x,A,ES19.12)") "Weight      = ", object%mci_weight
      if (object%safety_factor /= 1) then
        write (u, "(1x,A,ES19.12)") "Safety f  = ", object%safety_factor
      end if
      if (object%excess_weight /= 0) then

```

```

        write (u, "(1x,A,ES19.12)") "Excess      = ", object%excess_weight
    end if
    if (object%max_known) then
        write (u, "(1x,A,ES19.12)") "Maximum    = ", object%max
        write (u, "(1x,A,ES19.12)") "Minimum    = ", object%min
        if (object%min /= object%min_abs) then
            write (u, "(1x,A,ES19.12)") "Max.(abs) = ", object%max_abs
            write (u, "(1x,A,ES19.12)") "Min.(abs) = ", object%min_abs
        end if
    end if
end if
end subroutine mci_midpoint_instance_write

```

The finalizer is empty.

```

<MCI midpoint: mci midpoint instance: TBP>+≡
    procedure :: final => mci_midpoint_instance_final

<MCI midpoint: tests>≡
    subroutine mci_midpoint_instance_final (object)
        class(mci_midpoint_instance_t), intent(inout) :: object
    end subroutine mci_midpoint_instance_final

```

Initializer.

```

<MCI midpoint: mci midpoint instance: TBP>+≡
    procedure :: init => mci_midpoint_instance_init

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_instance_init (mci_instance, mci)
        class(mci_midpoint_instance_t), intent(out) :: mci_instance
        class(mci_t), intent(in), target :: mci
        call mci_instance%base_init (mci)
        select type (mci)
        type is (mci_midpoint_t)
            mci_instance%mci => mci
            call mci_instance%get_max ()
            mci_instance%selected_channel = 1
        end select
    end subroutine mci_midpoint_instance_init

```

Copy the stored extrema of the integrand in the instance record.

```

<MCI midpoint: mci midpoint instance: TBP>+≡
    procedure :: get_max => mci_midpoint_instance_get_max

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_instance_get_max (instance)
        class(mci_midpoint_instance_t), intent(inout) :: instance
        associate (mci => instance%mci)
            if (mci%max_known) then
                instance%max_known = .true.
                instance%max = mci%max
                instance%min = mci%min
                instance%max_abs = mci%max_abs
                instance%min_abs = mci%min_abs
            end if
        end associate
    end subroutine

```

```
end subroutine mci_midpoint_instance_get_max
```

Reverse operations: recall the extrema, but only if they are wider than the extrema already stored in the configuration. Also recalculate the efficiency value.

```
<MCI midpoint: mci midpoint instance: TBP>+≡
  procedure :: set_max => mci_midpoint_instance_set_max

<MCI midpoint: procedures>+≡
  subroutine mci_midpoint_instance_set_max (instance)
    class(mci_midpoint_instance_t), intent(inout) :: instance
    associate (mci => instance%mci)
      if (instance%max_known) then
        if (mci%max_known) then
          mci%max = max (mci%max, instance%max)
          mci%min = min (mci%min, instance%min)
          mci%max_abs = max (mci%max_abs, instance%max_abs)
          mci%min_abs = min (mci%min_abs, instance%min_abs)
        else
          mci%max = instance%max
          mci%min = instance%min
          mci%max_abs = instance%max_abs
          mci%min_abs = instance%min_abs
          mci%max_known = .true.
        end if
      if (mci%max_abs /= 0) then
        if (mci%integral == mci%integral_pos) then
          mci%efficiency = mci%integral / mci%max_abs
          mci%efficiency_known = .true.
        else if (mci%n_calls /= 0) then
          mci%efficiency = &
            (mci%n_calls_pos * mci%integral_pos &
              - mci%n_calls_neg * mci%integral_neg) &
            / mci%n_calls / mci%max_abs
          mci%efficiency_known = .true.
        end if
      end if
    end if
  end associate
end subroutine mci_midpoint_instance_set_max
```

The weight is the Jacobian of the mapping for the only channel.

```
<MCI midpoint: mci midpoint instance: TBP>+≡
  procedure :: compute_weight => mci_midpoint_instance_compute_weight

<MCI midpoint: procedures>+≡
  subroutine mci_midpoint_instance_compute_weight (mci, c)
    class(mci_midpoint_instance_t), intent(inout) :: mci
    integer, intent(in) :: c
    select case (c)
    case (1)
      mci%weight = mci%f(1)
    case default
      call msg_fatal ("MCI midpoint integrator: only single channel supported")
    end select
  end subroutine
```



```

        end select
    end subroutine mci_midpoint_instance_compute_weight

```

Record the integrand. Update stored values for maximum and minimum.

```

<MCI midpoint: mci midpoint instance: TBP>+≡
    procedure :: record_integrand => mci_midpoint_instance_record_integrand

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_instance_record_integrand (mci, integrand)
        class(mci_midpoint_instance_t), intent(inout) :: mci
        real(default), intent(in) :: integrand
        mci%integrand = integrand
        if (mci%max_known) then
            mci%max = max (mci%max, integrand)
            mci%min = min (mci%min, integrand)
            mci%max_abs = max (mci%max_abs, abs (integrand))
            mci%min_abs = min (mci%min_abs, abs (integrand))
        else
            mci%max = integrand
            mci%min = integrand
            mci%max_abs = abs (integrand)
            mci%min_abs = abs (integrand)
            mci%max_known = .true.
        end if
    end subroutine mci_midpoint_instance_record_integrand

```

We store the safety factor, otherwise nothing to do here.

```

<MCI midpoint: mci midpoint instance: TBP>+≡
    procedure :: init_simulation => mci_midpoint_instance_init_simulation
    procedure :: final_simulation => mci_midpoint_instance_final_simulation

<MCI midpoint: procedures>+≡
    subroutine mci_midpoint_instance_init_simulation (instance, safety_factor)
        class(mci_midpoint_instance_t), intent(inout) :: instance
        real(default), intent(in), optional :: safety_factor
        if (present (safety_factor)) instance%safety_factor = safety_factor
    end subroutine mci_midpoint_instance_init_simulation

    subroutine mci_midpoint_instance_final_simulation (instance)
        class(mci_midpoint_instance_t), intent(inout) :: instance
    end subroutine mci_midpoint_instance_final_simulation

```

Return excess weight for the current event.

```

<MCI midpoint: mci midpoint instance: TBP>+≡
    procedure :: get_event_excess => mci_midpoint_instance_get_event_excess

<MCI midpoint: procedures>+≡
    function mci_midpoint_instance_get_event_excess (mci) result (excess)
        class(mci_midpoint_instance_t), intent(in) :: mci
        real(default) :: excess
        excess = mci%excess_weight
    end function mci_midpoint_instance_get_event_excess

```

19.4.3 Unit tests

```

<MCI midpoint: public>+≡
  public :: mci_midpoint_test

<MCI midpoint: tests>+≡
  subroutine mci_midpoint_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <MCI midpoint: execute tests>
  end subroutine mci_midpoint_test

```

Test sampler

A test sampler object should implement a function with known integral that we can use to check the integrator.

This is the function $f(x) = 3x^2$ with integral $\int_0^1 f(x) dx = 1$ and maximum $f(1) = 3$. If the integration dimension is greater than one, the function is extended as a constant in the other dimension(s).

Mimicking the behavior of a process object, we store the argument and result inside the sampler, so we can `fetch` results.

```

<MCI midpoint: test types>≡
  type, extends (mci_sampler_t) :: test_sampler_1_t
    real(default), dimension(:), allocatable :: x
    real(default) :: val
  contains
  <MCI midpoint: test sampler 1: TBP>
  end type test_sampler_1_t

```

Output: There is nothing stored inside, so just print an informative line.

```

<MCI midpoint: test sampler 1: TBP>≡
  procedure :: write => test_sampler_1_write

<MCI midpoint: procedures>+≡
  subroutine test_sampler_1_write (object, unit, testflag)
    class(test_sampler_1_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Test sampler: f(x) = 3 x^2"
  end subroutine test_sampler_1_write

```

Evaluation: compute the function value. The output x parameter (only one channel) is identical to the input x , and the Jacobian is 1.

```

<MCI midpoint: test sampler 1: TBP>+≡
  procedure :: evaluate => test_sampler_1_evaluate

<MCI midpoint: procedures>+≡
  subroutine test_sampler_1_evaluate (sampler, c, x_in, val, x, f)
    class(test_sampler_1_t), intent(inout) :: sampler
    integer, intent(in) :: c

```

```

    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    if (allocated (sampler%x)) deallocate (sampler%x)
    allocate (sampler%x (size (x_in)))
    sampler%x = x_in
    sampler%val = 3 * x_in(1) ** 2
    call sampler%fetch (val, x, f)
end subroutine test_sampler_1_evaluate

```

The point is always valid.

```

⟨MCI midpoint: test sampler 1: TBP⟩+≡
    procedure :: is_valid => test_sampler_1_is_valid

⟨MCI midpoint: tests⟩+≡
    function test_sampler_1_is_valid (sampler) result (valid)
        class(test_sampler_1_t), intent(in) :: sampler
        logical :: valid
        valid = .true.
    end function test_sampler_1_is_valid

```

Rebuild: compute all but the function value.

```

⟨MCI midpoint: test sampler 1: TBP⟩+≡
    procedure :: rebuild => test_sampler_1_rebuild

⟨MCI midpoint: procedures⟩+≡
    subroutine test_sampler_1_rebuild (sampler, c, x_in, val, x, f)
        class(test_sampler_1_t), intent(inout) :: sampler
        integer, intent(in) :: c
        real(default), dimension(:), intent(in) :: x_in
        real(default), intent(in) :: val
        real(default), dimension(:,:), intent(out) :: x
        real(default), dimension(:), intent(out) :: f
        if (allocated (sampler%x)) deallocate (sampler%x)
        allocate (sampler%x (size (x_in)))
        sampler%x = x_in
        sampler%val = val
        x(:,1) = sampler%x
        f = 1
    end subroutine test_sampler_1_rebuild

```

Extract the results.

```

⟨MCI midpoint: test sampler 1: TBP⟩+≡
    procedure :: fetch => test_sampler_1_fetch

⟨MCI midpoint: procedures⟩+≡
    subroutine test_sampler_1_fetch (sampler, val, x, f)
        class(test_sampler_1_t), intent(in) :: sampler
        real(default), intent(out) :: val
        real(default), dimension(:,:), intent(out) :: x
        real(default), dimension(:), intent(out) :: f
        val = sampler%val
        x(:,1) = sampler%x

```

```

    f = 1
end subroutine test_sampler_1_fetch

```

This is the function $f(x) = 3x^2 + 2y$ with integral $\int_0^1 f(x,y) dx dy = 2$ and maximum $f(1) = 5$.

```

<MCI midpoint: test types>+≡
type, extends (mci_sampler_t) :: test_sampler_2_t
    real(default) :: val
    real(default), dimension(2) :: x
contains
    <MCI midpoint: test sampler 2: TBP>
end type test_sampler_2_t

```

Output: There is nothing stored inside, so just print an informative line.

```

<MCI midpoint: test sampler 2: TBP>≡
    procedure :: write => test_sampler_2_write

<MCI midpoint: procedures>+≡
    subroutine test_sampler_2_write (object, unit, testflag)
        class(test_sampler_2_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: testflag
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Test sampler: f(x) = 3 x^2 + 2 y"
    end subroutine test_sampler_2_write

```

Evaluate: compute the function value. The output x parameter (only one channel) is identical to the input x , and the Jacobian is 1.

```

<MCI midpoint: test sampler 2: TBP>+≡
    procedure :: evaluate => test_sampler_2_evaluate

<MCI midpoint: procedures>+≡
    subroutine test_sampler_2_evaluate (sampler, c, x_in, val, x, f)
        class(test_sampler_2_t), intent(inout) :: sampler
        integer, intent(in) :: c
        real(default), dimension(:), intent(in) :: x_in
        real(default), intent(out) :: val
        real(default), dimension(:,:), intent(out) :: x
        real(default), dimension(:), intent(out) :: f
        sampler%x = x_in
        sampler%val = 3 * x_in(1) ** 2 + 2 * x_in(2)
        call sampler%fetch (val, x, f)
    end subroutine test_sampler_2_evaluate

```

The point is always valid.

```

<MCI midpoint: test sampler 2: TBP>+≡
    procedure :: is_valid => test_sampler_2_is_valid

<MCI midpoint: tests>+≡
    function test_sampler_2_is_valid (sampler) result (valid)
        class(test_sampler_2_t), intent(in) :: sampler
        logical :: valid

```

```

    valid = .true.
end function test_sampler_2_is_valid

```

Rebuild: compute all but the function value.

```

⟨MCI midpoint: test sampler 2: TBP⟩+≡
  procedure :: rebuild => test_sampler_2_rebuild

⟨MCI midpoint: procedures⟩+≡
  subroutine test_sampler_2_rebuild (sampler, c, x_in, val, x, f)
    class(test_sampler_2_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(in) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    sampler%x = x_in
    sampler%val = val
    x(:,1) = sampler%x
    f = 1
  end subroutine test_sampler_2_rebuild

```

```

⟨MCI midpoint: test sampler 2: TBP⟩+≡
  procedure :: fetch => test_sampler_2_fetch

⟨MCI midpoint: procedures⟩+≡
  subroutine test_sampler_2_fetch (sampler, val, x, f)
    class(test_sampler_2_t), intent(in) :: sampler
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    val = sampler%val
    x(:,1) = sampler%x
    f = 1
  end subroutine test_sampler_2_fetch

```

This is the function $f(x) = (1 - 3x^2)\theta(x - 1/2)$ with integral $\int_0^1 f(x) dx = -3/8$, minimum $f(1) = -2$ and maximum $f(1/2) = 1/4$. If the integration dimension is greater than one, the function is extended as a constant in the other dimension(s).

```

⟨MCI midpoint: test types⟩+≡
  type, extends (mci_sampler_t) :: test_sampler_4_t
    real(default) :: val
    real(default), dimension(:), allocatable :: x
  contains
    ⟨MCI midpoint: test sampler 4: TBP⟩
  end type test_sampler_4_t

```

Output: There is nothing stored inside, so just print an informative line.

```

⟨MCI midpoint: test sampler 4: TBP⟩≡
  procedure :: write => test_sampler_4_write

```

```

<MCI midpoint: procedures>+≡
subroutine test_sampler_4_write (object, unit, testflag)
  class(test_sampler_4_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: testflag
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)") "Test sampler: f(x) = 1 - 3 x^2"
end subroutine test_sampler_4_write

```

Evaluation: compute the function value. The output x parameter (only one channel) is identical to the input x , and the Jacobian is 1.

```

<MCI midpoint: test sampler 4: TBP>+≡
  procedure :: evaluate => test_sampler_4_evaluate

<MCI midpoint: procedures>+≡
subroutine test_sampler_4_evaluate (sampler, c, x_in, val, x, f)
  class(test_sampler_4_t), intent(inout) :: sampler
  integer, intent(in) :: c
  real(default), dimension(:), intent(in) :: x_in
  real(default), intent(out) :: val
  real(default), dimension(:,:), intent(out) :: x
  real(default), dimension(:), intent(out) :: f
  if (x_in(1) >= .5_default) then
    sampler%val = 1 - 3 * x_in(1) ** 2
  else
    sampler%val = 0
  end if
  if (.not. allocated (sampler%x)) allocate (sampler%x (size (x_in)))
  sampler%x = x_in
  call sampler%fetch (val, x, f)
end subroutine test_sampler_4_evaluate

```

The point is always valid.

```

<MCI midpoint: test sampler 4: TBP>+≡
  procedure :: is_valid => test_sampler_4_is_valid

<MCI midpoint: tests>+≡
function test_sampler_4_is_valid (sampler) result (valid)
  class(test_sampler_4_t), intent(in) :: sampler
  logical :: valid
  valid = .true.
end function test_sampler_4_is_valid

```

Rebuild: compute all but the function value.

```

<MCI midpoint: test sampler 4: TBP>+≡
  procedure :: rebuild => test_sampler_4_rebuild

<MCI midpoint: procedures>+≡
subroutine test_sampler_4_rebuild (sampler, c, x_in, val, x, f)
  class(test_sampler_4_t), intent(inout) :: sampler
  integer, intent(in) :: c
  real(default), dimension(:), intent(in) :: x_in

```

```

    real(default), intent(in) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    sampler%x = x_in
    sampler%val = val
    x(:,1) = sampler%x
    f = 1
end subroutine test_sampler_4_rebuild

```

```

⟨MCI midpoint: test sampler 4: TBP⟩+≡
    procedure :: fetch => test_sampler_4_fetch

```

```

⟨MCI midpoint: procedures⟩+≡
    subroutine test_sampler_4_fetch (sampler, val, x, f)
        class(test_sampler_4_t), intent(in) :: sampler
        real(default), intent(out) :: val
        real(default), dimension(:,:), intent(out) :: x
        real(default), dimension(:), intent(out) :: f
        val = sampler%val
        x(:,1) = sampler%x
        f = 1
    end subroutine test_sampler_4_fetch

```

One-dimensional integration

Construct an integrator and use it for a one-dimensional sampler.

```

⟨MCI midpoint: execute tests⟩≡
    call test (mci_midpoint_1, "mci_midpoint_1", &
        "one-dimensional integral", &
        u, results)

⟨MCI midpoint: tests⟩+≡
    subroutine mci_midpoint_1 (u)
        integer, intent(in) :: u
        class(mci_t), allocatable, target :: mci
        class(mci_instance_t), pointer :: mci_instance => null ()
        class(mci_sampler_t), allocatable :: sampler

        write (u, "(A)")  "* Test output: mci_midpoint_1"
        write (u, "(A)")  "* Purpose: integrate function in one dimension"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize integrator"
        write (u, "(A)")

        allocate (mci_midpoint_t :: mci)
        call mci%set_dimensions (1, 1)

        call mci%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Initialize instance"
        write (u, "(A)")

```

```

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_1_t :: sampler)
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Evaluate for x = 0.8"
write (u, "(A)")

call mci_instance%evaluate (sampler, 1, [0.8_default])
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Evaluate for x = 0.7"
write (u, "(A)")

call mci_instance%evaluate (sampler, 1, [0.7_default])
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Evaluate for x = 0.9"
write (u, "(A)")

call mci_instance%evaluate (sampler, 1, [0.9_default])
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_calls = 1000"
write (u, "(A)")

call mci%integrate (mci_instance, sampler, 1, 1000)
call mci%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_midpoint_1"

end subroutine mci_midpoint_1

```

Two-dimensional integration

Construct an integrator and use it for a two-dimensional sampler.

(MCI midpoint: execute tests)+≡

```

call test (mci_midpoint_2, "mci_midpoint_2", &
  "two-dimensional integral", &
  u, results)

```



```

<MCI midpoint: tests>+≡
subroutine mci_midpoint_2 (u)
  integer, intent(in) :: u
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler

  write (u, "(A)")  "* Test output: mci_midpoint_2"
  write (u, "(A)")  "* Purpose: integrate function in two dimensions"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize integrator"
  write (u, "(A)")

  allocate (mci_midpoint_t :: mci)
  call mci%set_dimensions (2, 1)

  call mci%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Initialize instance"
  write (u, "(A)")

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  write (u, "(A)")  "* Initialize test sampler"
  write (u, "(A)")

  allocate (test_sampler_2_t :: sampler)
  call sampler%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Evaluate for x = 0.8, y = 0.2"
  write (u, "(A)")

  call mci_instance%evaluate (sampler, 1, [0.8_default, 0.2_default])
  call mci_instance%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Integrate with n_calls = 1000"
  write (u, "(A)")

  call mci%integrate (mci_instance, sampler, 1, 1000)
  call mci%write (u)

  call mci_instance%final ()
  call mci%final ()

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: mci_midpoint_2"

end subroutine mci_midpoint_2

```

Two-dimensional integration with flat dimension

Construct an integrator and use it for a two-dimensional sampler, where the function is constant in the second dimension.

```
(MCI midpoint: execute tests)+≡
  call test (mci_midpoint_3, "mci_midpoint_3", &
    "two-dimensional integral with flat dimension", &
    u, results)

(MCI midpoint: tests)+≡
  subroutine mci_midpoint_3 (u)
    integer, intent(in) :: u
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler

    write (u, "(A)")  "* Test output: mci_midpoint_3"
    write (u, "(A)")  "* Purpose: integrate function with one flat dimension"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize integrator"
    write (u, "(A)")

    allocate (mci_midpoint_t :: mci)
    select type (mci)
    type is (mci_midpoint_t)
      call mci%set_dimensions (2, 1)
      call mci%declare_flat_dimensions ([2])
    end select

    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Initialize instance"
    write (u, "(A)")

    call mci%allocate_instance (mci_instance)
    call mci_instance%init (mci)

    write (u, "(A)")  "* Initialize test sampler"
    write (u, "(A)")

    allocate (test_sampler_1_t :: sampler)
    call sampler%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Evaluate for x = 0.8, y = 0.2"
    write (u, "(A)")

    call mci_instance%evaluate (sampler, 1, [0.8_default, 0.2_default])
    call mci_instance%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Integrate with n_calls = 1000"
    write (u, "(A)")
```

```

call mci%integrate (mci_instance, sampler, 1, 1000)
call mci%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_midpoint_3"

end subroutine mci_midpoint_3

```

Integrand with sign flip

Construct an integrator and use it for a one-dimensional sampler.

```

<MCI midpoint: execute tests>+≡
call test (mci_midpoint_4, "mci_midpoint_4", &
  "integrand with sign flip", &
  u, results)

<MCI midpoint: tests>+≡
subroutine mci_midpoint_4 (u)
  integer, intent(in) :: u
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler

  write (u, "(A)")  "* Test output: mci_midpoint_4"
  write (u, "(A)")  "* Purpose: integrate function with sign flip &
    &in one dimension"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize integrator"
  write (u, "(A)")

  allocate (mci_midpoint_t :: mci)
  call mci%set_dimensions (1, 1)

  call mci%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Initialize instance"
  write (u, "(A)")

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  write (u, "(A)")  "* Initialize test sampler"
  write (u, "(A)")

  allocate (test_sampler_4_t :: sampler)
  call sampler%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Evaluate for x = 0.8"
write (u, "(A)")

call mci_instance%evaluate (sampler, 1, [0.8_default])
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_calls = 1000"
write (u, "(A)")

call mci%integrate (mci_instance, sampler, 1, 1000)
call mci%write (u)

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_midpoint_4"

end subroutine mci_midpoint_4

```

Weighted events

Generate weighted events. Without rejection, we do not need to know maxima and minima, so we can start generating events immediately. We have two dimensions.

```

<MCI midpoint: execute tests>+≡
  call test (mci_midpoint_5, "mci_midpoint_5", &
    "weighted events", &
    u, results)

<MCI midpoint: tests>+≡
subroutine mci_midpoint_5 (u)
  integer, intent(in) :: u
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng
  class(mci_state_t), allocatable :: state

  write (u, "(A)")  "* Test output: mci_midpoint_5"
  write (u, "(A)")  "* Purpose: generate weighted events"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize integrator"
  write (u, "(A)")

  allocate (mci_midpoint_t :: mci)
  call mci%set_dimensions (2, 1)

  call mci%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Initialize instance"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_2_t :: sampler)

write (u, "(A)")  "* Initialize random-number generator"
write (u, "(A)")

allocate (rng_test_t :: rng)
call rng%init ()
call mci%import_rng (rng)

write (u, "(A)")  "* Generate weighted event"
write (u, "(A)")

call mci%generate_weighted_event (mci_instance, sampler)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate weighted event"
write (u, "(A)")

call mci%generate_weighted_event (mci_instance, sampler)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Store data"
write (u, "(A)")

allocate (state)
call mci_instance%store (state)
call mci_instance%final ()
deallocate (mci_instance)

call state%write (u)

write (u, "(A)")
write (u, "(A)")  "* Recall data and rebuild event"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)
call mci%rebuild_event (mci_instance, sampler, state)

call mci_instance%write (u)

write (u, "(A)")

```

```

write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
deallocate (mci_instance)
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_midpoint_5"

end subroutine mci_midpoint_5

```

Unweighted events

Generate unweighted events. The integrand has a sign flip in it.

```

<MCI midpoint: execute tests>+≡
call test (mci_midpoint_6, "mci_midpoint_6", &
  "unweighted events", &
  u, results)

<MCI midpoint: tests>+≡
subroutine mci_midpoint_6 (u)
  integer, intent(in) :: u
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_midpoint_6"
  write (u, "(A)")  "* Purpose: generate unweighted events"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize integrator"
  write (u, "(A)")

  allocate (mci_midpoint_t :: mci)
  call mci%set_dimensions (1, 1)

  write (u, "(A)")  "* Initialize instance"
  write (u, "(A)")

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  write (u, "(A)")  "* Initialize test sampler"
  write (u, "(A)")

  allocate (test_sampler_4_t :: sampler)

  write (u, "(A)")  "* Initialize random-number generator"
  write (u, "(A)")

  allocate (rng_test_t :: rng)
  call rng%init ()

```

```

call mci%import_rng (rng)

write (u, "(A)")  "* Integrate (determine maximum of integrand"
write (u, "(A)")
call mci%integrate (mci_instance, sampler, 1, 1000)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate unweighted event"
write (u, "(A)")

call mci%generate_unweighted_event (mci_instance, sampler)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
deallocate (mci_instance)
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_midpoint_6"

end subroutine mci_midpoint_6

```

Excess weight

Generate unweighted events. With only 2 points for integration, the maximum of the integrand is too low, and we produce excess weight.

```

<MCI midpoint: execute tests>+≡
call test (mci_midpoint_7, "mci_midpoint_7", &
  "excess weight", &
  u, results)

<MCI midpoint: tests>+≡
subroutine mci_midpoint_7 (u)
  integer, intent(in) :: u
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_midpoint_7"
  write (u, "(A)")  "* Purpose: generate unweighted event &
    &with excess weight"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize integrator"
  write (u, "(A)")

  allocate (mci_midpoint_t :: mci)
  call mci%set_dimensions (1, 1)

```

```

write (u, "(A)")  "* Initialize instance"
write (u, "(A)")

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Initialize test sampler"
write (u, "(A)")

allocate (test_sampler_4_t :: sampler)

write (u, "(A)")  "* Initialize random-number generator"
write (u, "(A)")

allocate (rng_test_t :: rng)
call rng%init ()
call mci%import_rng (rng)

write (u, "(A)")  "* Integrate (determine maximum of integrand"
write (u, "(A)")
call mci%integrate (mci_instance, sampler, 1, 2)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate unweighted event"
write (u, "(A)")

call mci_instance%init_simulation ()
call mci%generate_unweighted_event (mci_instance, sampler)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Use getter methods"
write (u, "(A)")

write (u, "(1x,A,1x,ES19.12)")  "weight =", mci_instance%get_event_weight ()
write (u, "(1x,A,1x,ES19.12)")  "excess =", mci_instance%get_event_excess ()

write (u, "(A)")
write (u, "(A)")  "* Apply safety factor"
write (u, "(A)")

call mci_instance%init_simulation (safety_factor = 2.1_default)

write (u, "(A)")  "* Generate unweighted event"
write (u, "(A)")

call mci%generate_unweighted_event (mci_instance, sampler)
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Use getter methods"
write (u, "(A)")

```



```

write (u, "(1x,A,1x,ES19.12)") "weight =", mci_instance%get_event_weight ()
write (u, "(1x,A,1x,ES19.12)") "excess =", mci_instance%get_event_excess ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
deallocate (mci_instance)
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_midpoint_7"

end subroutine mci_midpoint_7

```

19.5 VAMP interface

The standard method for integration is **VAMP**: the multi-channel version of the VEGAS algorithm. Each parameterization (channel) of the hypercube is binned in each dimension. The binning is equally equidistant, but an iteration of the integration procedure, the binning is updated for each dimension, according to the variance distribution of the integrand, summed over all other dimension. In the next iteration, the binning approximates (hopefully) follows the integrand more closely, and the accuracy of the result is increased. Furthermore, the relative weight of the individual channels is also updated after an iteration.

The bin distribution is denoted as the grid for a channel, which we can write to file and reuse later.

In our implementation we specify the generic **VAMP** algorithm more tightly: the number of bins is equal for all dimensions, the initial weights are all equal. The user controls whether to update bins and/or weights after each iteration. The integration is organized in passes, each one consisting of several iterations with a common number of calls to the integrand. The first passes are intended as warmup, so the results are displayed but otherwise discarded. In the final pass, the integration estimates for the individual iterations are averaged for the final result.

```
<mci_vamp.f90>≡  
  <File header>  
  
  module mci_vamp  
  
    use kinds  
    <Use strings>  
    use io_units  
    use constants  
    use format_utils, only: pac_fmt  
    use format_defs, only: FMT_12, FMT_14, FMT_17, FMT_19  
    use unit_tests  
    use diagnostics  
    use md5  
  
    use phs_base  
    use rng_base  
    use rng_tao  
    use mci_base  
  
    use vamp !NODEP!  
    use exceptions !NODEP!  
  
    <Standard module head>  
  
    <MCI vamp: public>  
  
    <MCI vamp: types>  
  
    <MCI vamp: interfaces>  
  
    <MCI vamp: test types>
```

```
contains

<MCI vamp: procedures>

<MCI vamp: tests>

end module mci_vamp
```

19.5.1 Grid parameters

This is a transparent container. It holds the parameters that are stored in grid files, and are checked when grid files are read.

```
<MCI vamp: public>≡
  public :: grid_parameters_t

<MCI vamp: types>≡
  type :: grid_parameters_t
    integer :: threshold_calls = 0
    integer :: min_calls_per_channel = 10
    integer :: min_calls_per_bin = 10
    integer :: min_bins = 3
    integer :: max_bins = 20
    logical :: stratified = .true.
    logical :: use_vamp_equivalences = .true.
    real(default) :: channel_weights_power = 0.25_default
    real(default) :: accuracy_goal = 0
    real(default) :: error_goal = 0
    real(default) :: rel_error_goal = 0
    contains
    <MCI vamp: grid parameters: TBP>
  end type grid_parameters_t
```

I/O:

```
<MCI vamp: grid parameters: TBP>≡
  procedure :: write => grid_parameters_write

<MCI vamp: procedures>≡
  subroutine grid_parameters_write (object, unit)
    class(grid_parameters_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(3x,A,I0)") "threshold_calls      = ", &
      object%threshold_calls
    write (u, "(3x,A,I0)") "min_calls_per_channel = ", &
      object%min_calls_per_channel
    write (u, "(3x,A,I0)") "min_calls_per_bin   = ", &
      object%min_calls_per_bin
    write (u, "(3x,A,I0)") "min_bins           = ", &
      object%min_bins
    write (u, "(3x,A,I0)") "max_bins           = ", &
      object%max_bins
    write (u, "(3x,A,L1)") "stratified         = ", &
```

```

        object%stratified
write (u, "(3x,A,L1)") "use_vamp_equivalences = ", &
        object%use_vamp_equivalences
write (u, "(3x,A,F10.7)") "channel_weights_power = ", &
        object%channel_weights_power
if (object%accuracy_goal > 0) then
        write (u, "(3x,A,F10.7)") "accuracy_goal          = ", &
        object%accuracy_goal
end if
if (object%error_goal > 0) then
        write (u, "(3x,A,F10.7)") "error_goal          = ", &
        object%error_goal
end if
if (object%rel_error_goal > 0) then
        write (u, "(3x,A,F10.7)") "rel_error_goal        = ", &
        object%rel_error_goal
end if
end subroutine grid_parameters_write

```

19.5.2 History parameters

The history parameters are also stored in a transparent container. This is not a part of the grid definition, and should not be included in the MD5 sum.

```

<MCI vamp: public>+≡
    public :: history_parameters_t

<MCI vamp: types>+≡
    type :: history_parameters_t
        logical :: global = .true.
        logical :: global_verb = .false.
        logical :: channel = .false.
        logical :: channel_verb = .false.
    contains
        <MCI vamp: history parameters: TBP>
    end type history_parameters_t

```

I/O:

```

<MCI vamp: history parameters: TBP>≡
    procedure :: write => history_parameters_write

<MCI vamp: procedures>+≡
    subroutine history_parameters_write (object, unit)
        class(history_parameters_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A,L1)") "history(global)          = ", object%global
        write (u, "(3x,A,L1)") "history(global) verb. = ", object%global_verb
        write (u, "(3x,A,L1)") "history(channels)       = ", object%channel
        write (u, "(3x,A,L1)") "history(chann.) verb. = ", object%channel_verb
    end subroutine history_parameters_write

```

19.5.3 Integration pass

We store the parameters for each integration pass in a linked list.

```

<MCI vamp: types>+≡
  type :: pass_t
    integer :: i_pass = 0
    integer :: i_first_it = 0
    integer :: n_it = 0
    integer :: n_calls = 0
    integer :: n_bins = 0
    logical :: adapt_grids = .false.
    logical :: adapt_weights = .false.
    logical :: is_final_pass = .false.
    logical :: integral_defined = .false.
    integer, dimension(:), allocatable :: calls
    real(default), dimension(:), allocatable :: integral
    real(default), dimension(:), allocatable :: error
    real(default), dimension(:), allocatable :: efficiency
    type(vamp_history), dimension(:), allocatable :: v_history
    type(vamp_history), dimension(:, :), allocatable :: v_histories
    type(pass_t), pointer :: next => null ()
  contains
    <MCI vamp: pass: TBP>
  end type pass_t

```

Finalizer. The VAMP histories contain a pointer array.

```

<MCI vamp: pass: TBP>≡
  procedure :: final => pass_final

<MCI vamp: procedures>+≡
  subroutine pass_final (object)
    class(pass_t), intent(inout) :: object
    if (allocated (object%v_history)) then
      call vamp_delete_history (object%v_history)
    end if
    if (allocated (object%v_histories)) then
      call vamp_delete_history (object%v_histories)
    end if
  end subroutine pass_final

```

Output. Note that the precision of the numerical values should match the precision for comparing output from file with data.

```

<MCI vamp: pass: TBP>+≡
  procedure :: write => pass_write

<MCI vamp: procedures>+≡
  subroutine pass_write (object, unit, pacify)
    class(pass_t), intent(in) :: object
    integer, intent(in) :: unit
    logical, intent(in), optional :: pacify
    integer :: u, i
    character(len=7) :: fmt
    call pac_fmt (fmt, FMT_17, FMT_14, pacify)
    u = given_output_unit (unit)

```

```

write (u, "(3x,A,I0)") "n_it          = ", object%n_it
write (u, "(3x,A,I0)") "n_calls       = ", object%n_calls
write (u, "(3x,A,I0)") "n_bins        = ", object%n_bins
write (u, "(3x,A,L1)") "adapt grids   = ", object%adapt_grids
write (u, "(3x,A,L1)") "adapt weights = ", object%adapt_weights
if (object%integral_defined) then
  write (u, "(3x,A)") "Results: [it, calls, integral, error, efficiency]"
  do i = 1, object%n_it
    write (u, "(5x,I0,1x,I0,3(1x," // fmt // ")") &
      i, object%calls(i), object%integral(i), object%error(i), &
      object%efficiency(i)
  end do
else
  write (u, "(3x,A)") "Results: [undefined]"
end if
end subroutine pass_write

```

Read and reconstruct the pass.

(MCI vamp: pass: TBP)+≡

```

procedure :: read => pass_read

```

(MCI vamp: procedures)+≡

```

subroutine pass_read (object, u, n_pass, n_it)
  class(pass_t), intent(out) :: object
  integer, intent(in) :: u, n_pass, n_it
  integer :: i, j
  character(80) :: buffer
  object%i_pass = n_pass + 1
  object%i_first_it = n_it + 1
  call read_ival (u, object%n_it)
  call read_ival (u, object%n_calls)
  call read_ival (u, object%n_bins)
  call read_lval (u, object%adapt_grids)
  call read_lval (u, object%adapt_weights)
  allocate (object%calls (object%n_it), source = 0)
  allocate (object%integral (object%n_it), source = 0._default)
  allocate (object%error (object%n_it), source = 0._default)
  allocate (object%efficiency (object%n_it), source = 0._default)
  read (u, "(A)") buffer
  select case (trim (adjustl (buffer)))
  case ("Results: [it, calls, integral, error, efficiency]")
    do i = 1, object%n_it
      read (u, *) &
        j, object%calls(i), object%integral(i), object%error(i), &
        object%efficiency(i)
    end do
    object%integral_defined = .true.
  case ("Results: [undefined]")
    object%integral_defined = .false.
  case default
    call msg_fatal ("Reading integration pass: corrupted file")
  end select
end subroutine pass_read

```

Write the VAMP history for this pass. (The subroutine writes the whole array at once.)

```

(MCI vamp: pass: TBP)+≡
    procedure :: write_history => pass_write_history

(MCI vamp: procedures)+≡
    subroutine pass_write_history (pass, unit)
        class(pass_t), intent(in) :: pass
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        if (allocated (pass%v_history)) then
            call vamp_write_history (u, pass%v_history)
        else
            write (u, "(1x,A)") "Global history: [undefined]"
        end if
        if (allocated (pass%v_histories)) then
            write (u, "(1x,A)") "Channel histories:"
            call vamp_write_history (u, pass%v_histories)
        else
            write (u, "(1x,A)") "Channel histories: [undefined]"
        end if
    end subroutine pass_write_history

```

Given a number of calls and iterations, compute remaining data.

```

(MCI vamp: pass: TBP)+≡
    procedure :: configure => pass_configure

(MCI vamp: procedures)+≡
    subroutine pass_configure (pass, n_it, n_calls, min_calls, &
        min_bins, max_bins, min_channel_calls)
        class(pass_t), intent(inout) :: pass
        integer, intent(in) :: n_it, n_calls, min_channel_calls
        integer, intent(in) :: min_calls, min_bins, max_bins
        pass%n_it = n_it
        if (min_calls /= 0) then
            pass%n_bins = max (min_bins, &
                min (n_calls / min_calls, max_bins))
        else
            pass%n_bins = max_bins
        end if
        pass%n_calls = max (n_calls, max (min_calls, min_channel_calls))
        if (pass%n_calls /= n_calls) then
            write (msg_buffer, "(A,I0)") "VAMP: too few calls, resetting " &
                // "n_calls to ", pass%n_calls
            call msg_warning ()
        end if
        allocate (pass%calls (n_it), source = 0)
        allocate (pass%integral (n_it), source = 0._default)
        allocate (pass%error (n_it), source = 0._default)
        allocate (pass%efficiency (n_it), source = 0._default)
    end subroutine pass_configure

```

Allocate the VAMP history and give options. We assume that the `configure` routine above has been executed, so the number of iterations is known.

```

(MCI vamp: pass: TBP)+≡
  procedure :: configure_history => pass_configure_history

(MCI vamp: procedures)+≡
  subroutine pass_configure_history (pass, n_channels, par)
    class(pass_t), intent(inout) :: pass
    integer, intent(in) :: n_channels
    type(history_parameters_t), intent(in) :: par
    if (par%global) then
      allocate (pass%v_history (pass%n_it))
      call vamp_create_history (pass%v_history, &
        verbose = par%global_verbose)
    end if
    if (par%channel) then
      allocate (pass%v_histories (pass%n_it, n_channels))
      call vamp_create_history (pass%v_histories, &
        verbose = par%channel_verbose)
    end if
  end subroutine pass_configure_history

```

Given two pass objects, compare them. All parameters must match. Where integrations are done in both (number of calls nonzero), the results must be equal (up to numerical noise).

The allocated array sizes might be different, but should match up to the common `n_it` value.

```

(MCI vamp: interfaces)≡
  interface operator (.matches.)
    module procedure pass_matches
  end interface operator (.matches.)

(MCI vamp: procedures)+≡
  function pass_matches (pass, ref) result (ok)
    type(pass_t), intent(in) :: pass, ref
    integer :: n
    logical :: ok
    ok = .true.
    if (ok) ok = pass%i_pass == ref%i_pass
    if (ok) ok = pass%i_first_it == ref%i_first_it
    if (ok) ok = pass%n_it == ref%n_it
    if (ok) ok = pass%n_calls == ref%n_calls
    if (ok) ok = pass%n_bins == ref%n_bins
    if (ok) ok = pass%adapt_grids .eqv. ref%adapt_grids
    if (ok) ok = pass%adapt_weights .eqv. ref%adapt_weights
    if (ok) ok = pass%integral_defined .eqv. ref%integral_defined
    if (pass%integral_defined) then
      n = pass%n_it
      if (ok) ok = all (pass%calls(:n) == ref%calls(:n))
      if (ok) ok = all (pass%integral(:n) .matches. ref%integral(:n))
      if (ok) ok = all (pass%error(:n) .matches. ref%error(:n))
      if (ok) ok = all (pass%efficiency(:n) .matches. ref%efficiency(:n))
    end if
  end function pass_matches

```


Update a pass object, given a reference. The parameters must match, except for the `n_it` entry. The number of complete iterations must be less or equal to the reference, and the number of complete iterations in the reference must be no larger than `n_it`. Where results are present in both passes, they must match. Where results are present in the reference only, the pass is updated accordingly.

<MCI vamp: pass: TBP>+≡

```
procedure :: update => pass_update
```

<MCI vamp: procedures>+≡

```
subroutine pass_update (pass, ref, ok)
  class(pass_t), intent(inout) :: pass
  type(pass_t), intent(in) :: ref
  logical, intent(out) :: ok
  integer :: n, n_ref
  ok = .true.
  if (ok) ok = pass%i_pass == ref%i_pass
  if (ok) ok = pass%i_first_it == ref%i_first_it
  if (ok) ok = pass%n_calls == ref%n_calls
  if (ok) ok = pass%n_bins == ref%n_bins
  if (ok) ok = pass%adapt_grids .eqv. ref%adapt_grids
  if (ok) ok = pass%adapt_weights .eqv. ref%adapt_weights
  if (ok) then
    if (ref%integral_defined) then
      if (.not. allocated (pass%calls)) then
        allocate (pass%calls (pass%n_it), source = 0)
        allocate (pass%integral (pass%n_it), source = 0._default)
        allocate (pass%error (pass%n_it), source = 0._default)
        allocate (pass%efficiency (pass%n_it), source = 0._default)
      end if
      n = count (pass%calls /= 0)
      n_ref = count (ref%calls /= 0)
      ok = n <= n_ref .and. n_ref <= pass%n_it
      if (ok) ok = all (pass%calls(:n) == ref%calls(:n))
      if (ok) ok = all (pass%integral(:n) .matches. ref%integral(:n))
      if (ok) ok = all (pass%error(:n) .matches. ref%error(:n))
      if (ok) ok = all (pass%efficiency(:n) .matches. ref%efficiency(:n))
      if (ok) then
        pass%calls(n+1:n_ref) = ref%calls(n+1:n_ref)
        pass%integral(n+1:n_ref) = ref%integral(n+1:n_ref)
        pass%error(n+1:n_ref) = ref%error(n+1:n_ref)
        pass%efficiency(n+1:n_ref) = ref%efficiency(n+1:n_ref)
        pass%integral_defined = any (pass%calls /= 0)
      end if
    end if
  end if
end subroutine pass_update
```

Match two real numbers: they are equal up to a tolerance, which is 10^{-8} , matching the number of digits that are output by `pass_write`. In particular, if one number is exactly zero, the other one must also be zero.

<MCI vamp: interfaces>+≡

```
interface operator (.matches.)
```

```

        module procedure real_matches
    end interface operator (.matches.)

<MCI vamp: procedures>+≡
    elemental function real_matches (x, y) result (ok)
        real(default), intent(in) :: x, y
        logical :: ok
        real(default), parameter :: tolerance = 1.e-8_default
        ok = abs (x - y) <= tolerance * max (abs (x), abs (y))
    end function real_matches

```

Return the index of the most recent complete integration. If there is none, return zero.

```

<MCI vamp: pass: TBP>+≡
    procedure :: get_integration_index => pass_get_integration_index

<MCI vamp: procedures>+≡
    function pass_get_integration_index (pass) result (n)
        class (pass_t), intent(in) :: pass
        integer :: n
        integer :: i
        n = 0
        if (allocated (pass%calls)) then
            do i = 1, pass%n_it
                if (pass%calls(i) == 0) exit
                n = i
            end do
        end if
    end function pass_get_integration_index

```

Return the most recent integral and error, if available.

```

<MCI vamp: pass: TBP>+≡
    procedure :: get_calls => pass_get_calls
    procedure :: get_integral => pass_get_integral
    procedure :: get_error => pass_get_error
    procedure :: get_efficiency => pass_get_efficiency

<MCI vamp: procedures>+≡
    function pass_get_calls (pass) result (calls)
        class(pass_t), intent(in) :: pass
        integer :: calls
        integer :: n
        n = pass%get_integration_index ()
        if (n /= 0) then
            calls = pass%calls(n)
        else
            calls = 0
        end if
    end function pass_get_calls

    function pass_get_integral (pass) result (integral)
        class(pass_t), intent(in) :: pass
        real(default) :: integral
        integer :: n

```

```

n = pass%get_integration_index ()
if (n /= 0) then
    integral = pass%integral(n)
else
    integral = 0
end if
end function pass_get_integral

function pass_get_error (pass) result (error)
    class(pass_t), intent(in) :: pass
    real(default) :: error
    integer :: n
    n = pass%get_integration_index ()
    if (n /= 0) then
        error = pass%error(n)
    else
        error = 0
    end if
end function pass_get_error

function pass_get_efficiency (pass) result (efficiency)
    class(pass_t), intent(in) :: pass
    real(default) :: efficiency
    integer :: n
    n = pass%get_integration_index ()
    if (n /= 0) then
        efficiency = pass%efficiency(n)
    else
        efficiency = 0
    end if
end function pass_get_efficiency

```

19.5.4 Integrator

```

<MCI vamp: public>+≡
    public :: mci_vamp_t

<MCI vamp: types>+≡
    type, extends (mci_t) :: mci_vamp_t
        logical, dimension(:), allocatable :: dim_is_flat
        type(grid_parameters_t) :: grid_par
        type(history_parameters_t) :: history_par
        integer :: min_calls = 0
        type(pass_t), pointer :: first_pass => null ()
        type(pass_t), pointer :: current_pass => null ()
        type(vamp_equivalences_t) :: equivalences
        logical :: rebuild = .true.
        logical :: check_grid_file = .true.
        logical :: grid_filename_set = .false.
        logical :: negative_weights = .false.
        logical :: verbose = .false.
        type(string_t) :: grid_filename
        character(32) :: md5sum_adapted = ""

```

```

contains
  <MCI vamp: mci vamp: TBP>
end type mci_vamp_t

```

Reset: delete integration-pass entries.

```

<MCI vamp: mci vamp: TBP>≡
  procedure :: reset => mci_vamp_reset

<MCI vamp: procedures>+≡
  subroutine mci_vamp_reset (object)
    class(mci_vamp_t), intent(inout) :: object
    type(pass_t), pointer :: current_pass
    do while (associated (object%first_pass))
      current_pass => object%first_pass
      object%first_pass => current_pass%next
      call current_pass%final ()
      deallocate (current_pass)
    end do
    object%current_pass => null ()
  end subroutine mci_vamp_reset

```

Finalizer: reset and finalize the equivalences list.

```

<MCI vamp: mci vamp: TBP>+≡
  procedure :: final => mci_vamp_final

<MCI vamp: procedures>+≡
  subroutine mci_vamp_final (object)
    class(mci_vamp_t), intent(inout) :: object
    call object%reset ()
    call vamp_equivalences_final (object%equivalences)
    call object%base_final ()
  end subroutine mci_vamp_final

```

Output. Do not output the grids themselves, this may result in tons of data.

```

<MCI vamp: mci vamp: TBP>+≡
  procedure :: write => mci_vamp_write

<MCI vamp: procedures>+≡
  subroutine mci_vamp_write (object, unit, pacify, md5sum_version)
    class(mci_vamp_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: pacify
    logical, intent(in), optional :: md5sum_version
    type(pass_t), pointer :: current_pass
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A)") "VAMP integrator:"
    call object%base_write (u, pacify, md5sum_version)
    if (allocated (object%dim_is_flat)) then
      write (u, "(3x,A,999(1x,I0))") "Flat dimensions      =", &
        pack ([(i, i = 1, object%n_dim)], object%dim_is_flat)
    end if
    write (u, "(1x,A)") "Grid parameters:"
    call object%grid_par%write (u)

```

```

write (u, "(3x,A,I0)") "min_calls          = ", object%min_calls
write (u, "(3x,A,L1)") "negative weights    = ", &
    object%negative_weights
write (u, "(3x,A,L1)") "verbose           = ", &
    object%verbose
if (object%grid_par%use_vamp_equivalences) then
    call vamp_equivalences_write (object%equivalences, u)
end if
current_pass => object%first_pass
do while (associated (current_pass))
    write (u, "(1x,A,I0,A)") "Integration pass:"
    call current_pass%write (u, pacify)
    current_pass => current_pass%next
end do
if (object%md5sum_adapted /= "") then
    write (u, "(1x,A,A,A)") "MD5 sum (including results) = '", &
        object%md5sum_adapted, "'"
end if
end subroutine mci_vamp_write

```

Write the history parameters.

```

<MCI vamp: mci vamp: TBP>+≡
    procedure :: write_history_parameters => mci_vamp_write_history_parameters
<MCI vamp: procedures>+≡
    subroutine mci_vamp_write_history_parameters (mci, unit)
        class(mci_vamp_t), intent(in) :: mci
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "VAMP history parameters:"
        call mci%history_par%write (unit)
    end subroutine mci_vamp_write_history_parameters

```

Write the history, iterating over passes. We keep this separate from the generic write routine.

```

<MCI vamp: mci vamp: TBP>+≡
    procedure :: write_history => mci_vamp_write_history
<MCI vamp: procedures>+≡
    subroutine mci_vamp_write_history (mci, unit)
        class(mci_vamp_t), intent(in) :: mci
        integer, intent(in), optional :: unit
        type(pass_t), pointer :: current_pass
        integer :: i_pass
        integer :: u
        u = given_output_unit (unit)
        if (associated (mci%first_pass)) then
            write (u, "(1x,A)") "VAMP history (global):"
            i_pass = 0
            current_pass => mci%first_pass
            do while (associated (current_pass))
                i_pass = i_pass + 1
                write (u, "(1x,A,I0,':')") "Pass #", i_pass
            end do
        end if
    end subroutine mci_vamp_write_history

```

```

        call current_pass%write_history (u)
        current_pass => current_pass%next
    end do
end if
end subroutine mci_vamp_write_history

```

Compute the MD5 sum, including the configuration MD5 sum and the printout, which incorporates the current results.

```

<MCI vamp: mci vamp: TBP>+=
    procedure :: compute_md5sum => mci_vamp_compute_md5sum

<MCI vamp: procedures>+=
    subroutine mci_vamp_compute_md5sum (mci, pacify)
        class(mci_vamp_t), intent(inout) :: mci
        logical, intent(in), optional :: pacify
        integer :: u
        mci%md5sum_adapted = ""
        u = free_unit ()
        open (u, status = "scratch", action = "readwrite")
        write (u, "(A)") mci%md5sum
        call mci%write (u, pacify, md5sum_version = .true.)
        rewind (u)
        mci%md5sum_adapted = md5sum (u)
        close (u)
    end subroutine mci_vamp_compute_md5sum

```

Return the MD5 sum: If available, return the adapted one.

```

<MCI vamp: mci vamp: TBP>+=
    procedure :: get_md5sum => mci_vamp_get_md5sum

<MCI vamp: procedures>+=
    function mci_vamp_get_md5sum (mci) result (md5sum)
        class(mci_vamp_t), intent(in) :: mci
        character(32) :: md5sum
        if (mci%md5sum_adapted /= "") then
            md5sum = mci%md5sum_adapted
        else
            md5sum = mci%md5sum
        end if
    end function mci_vamp_get_md5sum

```

Startup message: short version.

```

<MCI vamp: mci vamp: TBP>+=
    procedure :: startup_message => mci_vamp_startup_message

<MCI vamp: procedures>+=
    subroutine mci_vamp_startup_message (mci, unit, n_calls)
        class(mci_vamp_t), intent(in) :: mci
        integer, intent(in), optional :: unit, n_calls
        integer :: num_calls, n_bins
        if (present (n_calls)) then
            num_calls = n_calls
        else

```

```

        num_calls = 0
    end if
    if (mci%min_calls /= 0) then
        n_bins = max (mci%grid_par%min_bins, &
            min (num_calls / mci%min_calls, &
                mci%grid_par%max_bins))
    else
        n_bins = mci%grid_par%max_bins
    end if
    call mci%base_startup_message (unit = unit, n_calls = n_calls)
    if (mci%grid_par%use_vamp_equivalences) then
        write (msg_buffer, "(A,2(1x,I0,1x,A))" &
            "Integrator: Using VAMP channel equivalences"
            call msg_message (unit = unit)
    end if
    write (msg_buffer, "(A,2(1x,I0,1x,A),L1)" &
        "Integrator:", num_calls, &
        "initial calls,", n_bins, &
        "bins, stratified = ", &
        mci%grid_par%stratified
        call msg_message (unit = unit)
    write (msg_buffer, "(A,2(1x,I0,1x,A))" &
        "Integrator: VAMP"
        call msg_message (unit = unit)
    end subroutine mci_vamp_startup_message

```

Set the MCI index (necessary for processes with multiple components). We append the index to the grid filename, just before the final dotted suffix.

```

<MCI vamp: mci vamp: TBP>+≡
    procedure :: record_index => mci_vamp_record_index

<MCI vamp: procedures>+≡
    subroutine mci_vamp_record_index (mci, i_mci)
        class(mci_vamp_t), intent(inout) :: mci
        integer, intent(in) :: i_mci
        type(string_t) :: basename, suffix
        character(32) :: buffer
        if (mci%grid_filename_set) then
            basename = mci%grid_filename
            call split (basename, suffix, ".", back=.true.)
            write (buffer, "(I0)") i_mci
            if (basename /= "") then
                mci%grid_filename = basename // "_m" // trim (buffer) // "." // suffix
            else
                mci%grid_filename = suffix // "_m" // trim (buffer) // ".vg"
            end if
        end if
    end subroutine mci_vamp_record_index

```

Set the grid parameters.

```

<MCI vamp: mci vamp: TBP>+≡
    procedure :: set_grid_parameters => mci_vamp_set_grid_parameters

```

```

<MCI vamp: procedures>+=
  subroutine mci_vamp_set_grid_parameters (mci, grid_par)
    class(mci_vamp_t), intent(inout) :: mci
    type(grid_parameters_t), intent(in) :: grid_par
    mci%grid_par = grid_par
    mci%min_calls = grid_par%min_calls_per_bin * mci%n_channel
  end subroutine mci_vamp_set_grid_parameters

```

Set the history parameters.

```

<MCI vamp: mci vamp: TBP>+=
  procedure :: set_history_parameters => mci_vamp_set_history_parameters

<MCI vamp: procedures>+=
  subroutine mci_vamp_set_history_parameters (mci, history_par)
    class(mci_vamp_t), intent(inout) :: mci
    type(history_parameters_t), intent(in) :: history_par
    mci%history_par = history_par
  end subroutine mci_vamp_set_history_parameters

```

Set the rebuild flag, also the flag for checking the grid file.

```

<MCI vamp: mci vamp: TBP>+=
  procedure :: set_rebuild_flag => mci_vamp_set_rebuild_flag

<MCI vamp: procedures>+=
  subroutine mci_vamp_set_rebuild_flag (mci, rebuild, check_grid_file)
    class(mci_vamp_t), intent(inout) :: mci
    logical, intent(in) :: rebuild
    logical, intent(in) :: check_grid_file
    mci%rebuild = rebuild
    mci%check_grid_file = check_grid_file
  end subroutine mci_vamp_set_rebuild_flag

```

Set the filename.

```

<MCI vamp: mci vamp: TBP>+=
  procedure :: set_grid_filename => mci_vamp_set_grid_filename

<MCI vamp: procedures>+=
  subroutine mci_vamp_set_grid_filename (mci, name, run_id)
    class(mci_vamp_t), intent(inout) :: mci
    type(string_t), intent(in) :: name
    type(string_t), intent(in), optional :: run_id
    if (present (run_id)) then
      mci%grid_filename = name // "." // run_id // ".vg"
    else
      mci%grid_filename = name // ".vg"
    end if
    mci%grid_filename_set = .true.
  end subroutine mci_vamp_set_grid_filename

```

Declare particular dimensions as flat.

```

<MCI vamp: mci vamp: TBP>+=
  procedure :: declare_flat_dimensions => mci_vamp_declare_flat_dimensions

```



```

(MCI vamp: procedures)+≡
subroutine mci_vamp_declare_flat_dimensions (mci, dim_flat)
  class(mci_vamp_t), intent(inout) :: mci
  integer, dimension(:), intent(in) :: dim_flat
  integer :: d
  allocate (mci%dim_is_flat (mci%n_dim), source = .false.)
  do d = 1, size (dim_flat)
    mci%dim_is_flat(dim_flat(d)) = .true.
  end do
end subroutine mci_vamp_declare_flat_dimensions

```

Declare equivalences. We have an array of channel equivalences, provided by the phase-space module. Here, we translate this into the `vamp_equivalences` array.

```

(MCI vamp: mci vamp: TBP)+≡
  procedure :: declare_equivalences => mci_vamp_declare_equivalences
(MCI vamp: procedures)+≡
subroutine mci_vamp_declare_equivalences (mci, channel, dim_offset)
  class(mci_vamp_t), intent(inout) :: mci
  type(phas_channel_t), dimension(:), intent(in) :: channel
  integer, intent(in) :: dim_offset
  integer, dimension(:), allocatable :: perm, mode
  integer :: n_channels, n_dim, n_equivalences
  integer :: c, i, j, left, right
  n_channels = mci%n_channel
  n_dim = mci%n_dim
  n_equivalences = 0
  do c = 1, n_channels
    n_equivalences = n_equivalences + size (channel(c)%eq)
  end do
  call vamp_equivalences_init (mci%equivalences, &
    n_equivalences, n_channels, n_dim)
  allocate (perm (n_dim))
  allocate (mode (n_dim))
  perm(1:dim_offset) = [(i, i = 1, dim_offset)]
  mode(1:dim_offset) = VEQ_IDENTITY
  c = 1
  j = 0
  do i = 1, n_equivalences
    if (j < size (channel(c)%eq)) then
      j = j + 1
    else
      c = c + 1
      j = 1
    end if
    associate (eq => channel(c)%eq(j))
      left = c
      right = eq%c
      perm(dim_offset+1:) = eq%perm + dim_offset
      mode(dim_offset+1:) = eq%mode
      call vamp_equivalence_set (mci%equivalences, &
        i, left, right, perm, mode)
    end associate
  end do
end subroutine mci_vamp_declare_equivalences

```

```

end do
call vamp_equivalences_complete (mci%equivalences)
end subroutine mci_vamp_declare_equivalences

```

Allocate instance with matching type.

```

⟨MCI vamp: mci vamp: TBP⟩+≡
  procedure :: allocate_instance => mci_vamp_allocate_instance

⟨MCI vamp: procedures⟩+≡
  subroutine mci_vamp_allocate_instance (mci, mci_instance)
    class(mci_vamp_t), intent(in) :: mci
    class(mci_instance_t), intent(out), pointer :: mci_instance
    allocate (mci_vamp_instance_t :: mci_instance)
  end subroutine mci_vamp_allocate_instance

```

Allocate a new integration pass. We can preset everything that does not depend on the number of iterations and calls. This is postponed to the `integrate` method.

In the final pass, we do not check accuracy goal etc., since we can assume that the user wants to perform and average all iterations in this pass.

```

⟨MCI vamp: mci vamp: TBP⟩+≡
  procedure :: add_pass => mci_vamp_add_pass

⟨MCI vamp: procedures⟩+≡
  subroutine mci_vamp_add_pass (mci, adapt_grids, adapt_weights, final)
    class(mci_vamp_t), intent(inout) :: mci
    logical, intent(in), optional :: adapt_grids, adapt_weights, final
    integer :: i_pass, i_it
    type(pass_t), pointer :: new
    allocate (new)
    if (associated (mci%current_pass)) then
      i_pass = mci%current_pass%i_pass + 1
      i_it   = mci%current_pass%i_first_it + mci%current_pass%n_it
      mci%current_pass%next => new
    else
      i_pass = 1
      i_it = 1
      mci%first_pass => new
    end if
    mci%current_pass => new
    new%i_pass = i_pass
    new%i_first_it = i_it
    if (present (adapt_grids)) then
      new%adapt_grids = adapt_grids
    else
      new%adapt_grids = .false.
    end if
    if (present (adapt_weights)) then
      new%adapt_weights = adapt_weights
    else
      new%adapt_weights = .false.
    end if
    if (present (final)) then

```

```

        new%is_final_pass = final
    else
        new%is_final_pass = .false.
    end if
end subroutine mci_vamp_add_pass

```

Update the list of integration passes. All passes except for the last one must match exactly. For the last one, integration results are updated. The reference output may contain extra passes, these are ignored.

```

⟨MCI vamp: mci vamp: TBP⟩+=
    procedure :: update_from_ref => mci_vamp_update_from_ref

⟨MCI vamp: procedures⟩+=
    subroutine mci_vamp_update_from_ref (mci, mci_ref, success)
        class(mci_vamp_t), intent(inout) :: mci
        class(mci_t), intent(in) :: mci_ref
        logical, intent(out) :: success
        type(pass_t), pointer :: current_pass, ref_pass
        select type (mci_ref)
            type is (mci_vamp_t)
                current_pass => mci%first_pass
                ref_pass => mci_ref%first_pass
                success = .true.
                do while (success .and. associated (current_pass))
                    if (associated (ref_pass)) then
                        if (associated (current_pass%next)) then
                            success = current_pass .matches. ref_pass
                        else
                            call current_pass%update (ref_pass, success)
                            if (current_pass%integral_defined) then
                                mci%integral = current_pass%get_integral ()
                                mci%error = current_pass%get_error ()
                                mci%efficiency = current_pass%get_efficiency ()
                                mci%integral_known = .true.
                                mci%error_known = .true.
                                mci%efficiency_known = .true.
                            end if
                        end if
                        current_pass => current_pass%next
                        ref_pass => ref_pass%next
                    else
                        success = .false.
                    end if
                end do
            end select
        end subroutine mci_vamp_update_from_ref

```

Update the MCI record (i.e., the integration passes) by reading from input stream. The stream should contain a `write` output from a previous run. We first check the MD5 sum of the configuration parameters. If that matches, we proceed directly to the stored integration passes. If successful, we may continue to read the file; the position will be after a blank line that must follow the MCI

record.

```
<MCI vamp: mci vamp: TBP>+=  
  procedure :: update => mci_vamp_update  
  
<MCI vamp: procedures>+=  
  subroutine mci_vamp_update (mci, u, success)  
    class(mci_vamp_t), intent(inout) :: mci  
    integer, intent(in) :: u  
    logical, intent(out) :: success  
    character(80) :: buffer  
    character(32) :: md5sum_file  
    type(mci_vamp_t) :: mci_file  
    integer :: n_pass, n_it  
    call read_sval (u, md5sum_file)  
    if (mci%check_grid_file) then  
      success = md5sum_file == mci%md5sum  
    else  
      success = .true.  
    end if  
    if (success) then  
      read (u, *)  
      read (u, "(A)") buffer  
      if (trim (adjustl (buffer)) == "VAMP integrator:") then  
        n_pass = 0  
        n_it = 0  
        do  
          read (u, "(A)") buffer  
          select case (trim (adjustl (buffer)))  
            case ("")  
              exit  
            case ("Integration pass:")  
              call mci_file%add_pass ()  
              call mci_file%current_pass%read (u, n_pass, n_it)  
              n_pass = n_pass + 1  
              n_it = n_it + mci_file%current_pass%n_it  
            end select  
          end do  
          call mci%update_from_ref (mci_file, success)  
          call mci_file%final ()  
        else  
          call msg_fatal ("VAMP: reading grid file: corrupted data")  
        end if  
      end if  
    end subroutine mci_vamp_update
```

Read / write grids from / to file.

```
<MCI vamp: mci vamp: TBP>+=  
  procedure :: write_grids => mci_vamp_write_grids  
  procedure :: read_grids_header => mci_vamp_read_grids_header  
  procedure :: read_grids_data => mci_vamp_read_grids_data  
  procedure :: read_grids => mci_vamp_read_grids  
  
<MCI vamp: procedures>+=  
  subroutine mci_vamp_write_grids (mci, instance)
```

```

class(mci_vamp_t), intent(in) :: mci
class(mci_instance_t), intent(inout) :: instance
integer :: u
select type (instance)
type is (mci_vamp_instance_t)
  if (mci%grid_filename_set) then
    if (instance%grids_defined) then
      u = free_unit ()
      open (u, file = char (mci%grid_filename), &
           action = "write", status = "replace")
      write (u, "(1x,A,A,A)") "MD5sum = '", mci%md5sum, "'"
      write (u, *)
      call mci%write (u)
      write (u, *)
      write (u, "(1x,A)") "VAMP grids:"
      call vamp_write_grids (instance%grids, u, &
                           write_integrals = .true.)
      close (u)
    else
      call msg_bug ("VAMP: write grids: grids undefined")
    end if
  else
    call msg_bug ("VAMP: write grids: filename undefined")
  end if
end select
end subroutine mci_vamp_write_grids

subroutine mci_vamp_read_grids_header (mci, success)
class(mci_vamp_t), intent(inout) :: mci
logical, intent(out) :: success
logical :: exist
integer :: u
success = .false.
if (mci%grid_filename_set) then
  inquire (file = char (mci%grid_filename), exist = exist)
  if (exist) then
    u = free_unit ()
    open (u, file = char (mci%grid_filename), &
         action = "read", status = "old")
    call mci%update (u, success)
    close (u)
    if (.not. success) then
      write (msg_buffer, "(A,A,A)") &
           "VAMP: parameter mismatch, discarding grid file '", &
           char (mci%grid_filename), "'"
      call msg_message ()
    end if
  end if
else
  call msg_bug ("VAMP: read grids: filename undefined")
end if
end subroutine mci_vamp_read_grids_header

subroutine mci_vamp_read_grids_data (mci, instance, read_integrals)

```

```

class(mci_vamp_t), intent(in) :: mci
class(mci_instance_t), intent(inout) :: instance
logical, intent(in), optional :: read_integrals
integer :: u
character(80) :: buffer
select type (instance)
type is (mci_vamp_instance_t)
  if (.not. instance%grids_defined) then
    u = free_unit ()
    open (u, file = char (mci%grid_filename), &
          action = "read", status = "old")
    do
      read (u, "(A)") buffer
      if (trim (adjustl (buffer)) == "VAMP grids:") exit
    end do
    call vamp_read_grids (instance%grids, u, read_integrals)
    close (u)
    instance%grids_defined = .true.
  else
    call msg_bug ("VAMP: read grids: grids already defined")
  end if
end select
end subroutine mci_vamp_read_grids_data

subroutine mci_vamp_read_grids (mci, instance, success)
class(mci_vamp_t), intent(inout) :: mci
class(mci_instance_t), intent(inout) :: instance
logical, intent(out) :: success
logical :: exist
integer :: u
character(80) :: buffer
select type (instance)
type is (mci_vamp_instance_t)
  success = .false.
  if (mci%grid_filename_set) then
    if (.not. instance%grids_defined) then
      inquire (file = char (mci%grid_filename), exist = exist)
      if (exist) then
        u = free_unit ()
        open (u, file = char (mci%grid_filename), &
              action = "read", status = "old")
        call mci%update (u, success)
        if (success) then
          read (u, "(A)") buffer
          if (trim (adjustl (buffer)) == "VAMP grids:") then
            call vamp_read_grids (instance%grids, u)
          else
            call msg_fatal ("VAMP: reading grid file: &
                           &corrupted grid data")
          end if
        else
          write (msg_buffer, "(A,A,A)") &
            "VAMP: parameter mismatch, discarding grid file '", &
            char (mci%grid_filename), "' "
        end if
      else
        write (msg_buffer, "(A,A,A)") &
          "VAMP: parameter mismatch, discarding grid file '", &
          char (mci%grid_filename), "' "
      end if
    end if
  end if
end subroutine mci_vamp_read_grids

```

```

        call msg_message ()
    end if
    close (u)
    instance%grids_defined = success
end if
else
    call msg_bug ("VAMP: read grids: grids already defined")
end if
else
    call msg_bug ("VAMP: read grids: filename undefined")
end if
end select
end subroutine mci_vamp_read_grids

```

Auxiliary: Read real, integer, string value. We search for an equals sign, the value must follow.

(MCI vamp: procedures)+≡

```

subroutine read_rval (u, rval)
    integer, intent(in) :: u
    real(default), intent(out) :: rval
    character(80) :: buffer
    read (u, "(A)") buffer
    buffer = adjustl (buffer(scan (buffer, "=") + 1:))
    read (buffer, *) rval
end subroutine read_rval

subroutine read_ival (u, ival)
    integer, intent(in) :: u
    integer, intent(out) :: ival
    character(80) :: buffer
    read (u, "(A)") buffer
    buffer = adjustl (buffer(scan (buffer, "=") + 1:))
    read (buffer, *) ival
end subroutine read_ival

subroutine read_sval (u, sval)
    integer, intent(in) :: u
    character(*), intent(out) :: sval
    character(80) :: buffer
    read (u, "(A)") buffer
    buffer = adjustl (buffer(scan (buffer, "=") + 1:))
    read (buffer, *) sval
end subroutine read_sval

subroutine read_lval (u, lval)
    integer, intent(in) :: u
    logical, intent(out) :: lval
    character(80) :: buffer
    read (u, "(A)") buffer
    buffer = adjustl (buffer(scan (buffer, "=") + 1:))
    read (buffer, *) lval
end subroutine read_lval

```

Integrate. Perform a new integration pass (possibly reusing previous results), which may consist of several iterations.

Note: we record the integral once per iteration. The integral stored in the `mci` record itself is the last integral of the current iteration, no averaging done. The `results` record may average results.

Note: recording the efficiency is not supported yet.

```

<MCI vamp: mci vamp: TBP>+=
  procedure :: integrate => mci_vamp_integrate

<MCI vamp: procedures>+=
  subroutine mci_vamp_integrate (mci, instance, sampler, &
    n_it, n_calls, results, pacify)
    class(mci_vamp_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout) :: instance
    class(mci_sampler_t), intent(inout) :: sampler
    integer, intent(in) :: n_it
    integer, intent(in) :: n_calls
    class(mci_results_t), intent(inout), optional :: results
    logical, intent(in), optional :: pacify
    integer :: it
    logical :: reshape, from_file, success
    select type (instance)
    type is (mci_vamp_instance_t)
      if (associated (mci%current_pass)) then
        mci%current_pass%integral_defined = .false.
        call mci%current_pass%configure (n_it, n_calls, &
          mci%min_calls, mci%grid_par%min_bins, &
          mci%grid_par%max_bins, &
          mci%grid_par%min_calls_per_channel * mci%n_channel)
        call mci%current_pass%configure_history &
          (mci%n_channel, mci%history_par)
        instance%pass_complete = .false.
        instance%it_complete = .false.
        call instance%new_pass (reshape)
        if (.not. instance%grids_defined .or. instance%grids_from_file) then
          if (mci%grid_filename_set .and. .not. mci%rebuild) then
            call mci%read_grids_header (success)
            from_file = success
            if (.not. instance%grids_defined .and. success) then
              call mci%read_grids_data (instance)
            end if
          else
            from_file = .false.
          end if
        else
          from_file = .false.
        end if
      end if
    type is (mci_instance_t)
      from_file = .false.
    end if
    if (from_file) then
      if (.not. mci%check_grid_file) &
        call msg_warning ("Reading grid file: MD5 sum check disabled")
      call msg_message ("VAMP: " &
        // "using grids and results from file '" &
        // char (mci%grid_filename) // "'")
    else if (.not. instance%grids_defined) then

```



```

        call instance%create_grids ()
    end if
    do it = 1, instance%n_it
        if (signal_is_pending ()) return
        instance%grids_from_file = from_file .and. &
            it <= mci%current_pass%get_integration_index ()
        if (.not. instance%grids_from_file) then
            instance%it_complete = .false.
            call instance%adapt_grids ()
            if (signal_is_pending ()) return
            call instance%adapt_weights ()
            if (signal_is_pending ()) return
            call instance%discard_integrals (reshape)
            if (mci%grid_par%use_vamp_equivalences) then
                call instance%sample_grids (mci%rng, sampler, &
                    mci%equivalences)
            else
                call instance%sample_grids (mci%rng, sampler)
            end if
            if (signal_is_pending ()) return
            instance%it_complete = .true.
            if (instance%integral /= 0) then
                mci%current_pass%calls(it) = instance%calls
                mci%current_pass%integral(it) = instance%integral
                if (abs (instance%error / instance%integral) &
                    > epsilon (1._default)) then
                    mci%current_pass%error(it) = instance%error
                end if
                mci%current_pass%efficiency(it) = instance%efficiency
            end if
            mci%current_pass%integral_defined = .true.
        end if
        if (present (results)) then
            if (mci%has_chains ()) then
                call mci%collect_chain_weights (instance%w)
                call results%record (1, &
                    n_calls      = mci%current_pass%calls(it), &
                    integral     = mci%current_pass%integral(it), &
                    error        = mci%current_pass%error(it), &
                    efficiency   = mci%current_pass%efficiency(it), &
                    chain_weights = mci%chain_weights, &
                    suppress     = pacify)
            else
                call results%record (1, &
                    n_calls      = mci%current_pass%calls(it), &
                    integral     = mci%current_pass%integral(it), &
                    error        = mci%current_pass%error(it), &
                    efficiency   = mci%current_pass%efficiency(it), &
                    suppress     = pacify)
            end if
        end if
    end if
    if (.not. instance%grids_from_file &
        .and. mci%grid_filename_set) then
        call mci%write_grids (instance)
    end if
end if

```

```

        end if
        call instance%allow_adaptation ()
        reshape = .false.
        if (.not. mci%current_pass%is_final_pass) then
            call mci%check_goals (it, success)
            if (success) exit
        end if
    end do
    if (signal_is_pending ()) return
    instance%pass_complete = .true.
    mci%integral = mci%current_pass%get_integral()
    mci%error = mci%current_pass%get_error()
    mci%efficiency = mci%current_pass%get_efficiency()
    mci%integral_known = .true.
    mci%error_known = .true.
    mci%efficiency_known = .true.
    call mci%compute_md5sum (pacify)
else
    call msg_bug ("MCI integrate: current_pass object not allocated")
end if
end select
end subroutine mci_vamp_integrate

```

Check whether we are already finished with this pass.

(MCI vamp: mci vamp: TBP)+≡

```

    procedure :: check_goals => mci_vamp_check_goals

```

(MCI vamp: procedures)+≡

```

subroutine mci_vamp_check_goals (mci, it, success)
    class(mci_vamp_t), intent(inout) :: mci
    integer, intent(in) :: it
    logical, intent(out) :: success
    success = .false.
    if (mci%error_reached (it)) then
        mci%current_pass%n_it = it
        call msg_message ("VAMP: error goal reached; &
            &skipping iterations")
        success = .true.
        return
    end if
    if (mci%rel_error_reached (it)) then
        mci%current_pass%n_it = it
        call msg_message ("VAMP: relative error goal reached; &
            &skipping iterations")
        success = .true.
        return
    end if
    if (mci%accuracy_reached (it)) then
        mci%current_pass%n_it = it
        call msg_message ("VAMP: accuracy goal reached; &
            &skipping iterations")
        success = .true.
        return
    end if
end if

```

```
end subroutine mci_vamp_check_goals
```

Return true if the error, relative error, or accuracy goal has been reached, if any.

```
<MCI vamp: mci vamp: TBP>+≡
```

```
procedure :: error_reached => mci_vamp_error_reached
procedure :: rel_error_reached => mci_vamp_rel_error_reached
procedure :: accuracy_reached => mci_vamp_accuracy_reached
```

```
<MCI vamp: procedures>+≡
```

```
function mci_vamp_error_reached (mci, it) result (flag)
  class(mci_vamp_t), intent(in) :: mci
  integer, intent(in) :: it
  logical :: flag
  real(default) :: error_goal, error
  error_goal = mci%grid_par%error_goal
  if (error_goal > 0) then
    associate (pass => mci%current_pass)
      if (pass%integral_defined) then
        error = abs (pass%error(it))
        flag = error < error_goal
      else
        flag = .false.
      end if
    end associate
  else
    flag = .false.
  end if
end function mci_vamp_error_reached

function mci_vamp_rel_error_reached (mci, it) result (flag)
  class(mci_vamp_t), intent(in) :: mci
  integer, intent(in) :: it
  logical :: flag
  real(default) :: rel_error_goal, rel_error
  rel_error_goal = mci%grid_par%rel_error_goal
  if (rel_error_goal > 0) then
    associate (pass => mci%current_pass)
      if (pass%integral_defined) then
        if (pass%integral(it) /= 0) then
          rel_error = abs (pass%error(it) / pass%integral(it))
          flag = rel_error < rel_error_goal
        else
          flag = .true.
        end if
      else
        flag = .false.
      end if
    end associate
  else
    flag = .false.
  end if
end function mci_vamp_rel_error_reached
```

```

function mci_vamp_accuracy_reached (mci, it) result (flag)
  class(mci_vamp_t), intent(in) :: mci
  integer, intent(in) :: it
  logical :: flag
  real(default) :: accuracy_goal, accuracy
  accuracy_goal = mci%grid_par%accuracy_goal
  if (accuracy_goal > 0) then
    associate (pass => mci%current_pass)
      if (pass%integral_defined) then
        if (pass%integral(it) /= 0) then
          accuracy = abs (pass%error(it) / pass%integral(it)) &
            * sqrt (real (pass%calls(it), default))
          flag = accuracy < accuracy_goal
        else
          flag = .true.
        end if
      else
        flag = .false.
      end if
    end associate
  else
    flag = .false.
  end if
end function mci_vamp_accuracy_reached

```

Prepare an event generation pass. Should be called before a sequence of events is generated, then we should call the corresponding finalizer.

The pass-specific data of the previous integration pass are retained, but we reset the number of iterations and calls to zero. The latter now counts the number of events (calls to the sampling function, actually).

(MCI vamp: mci vamp: TBP)+≡

```

procedure :: prepare_simulation => mci_vamp_prepare_simulation

```

(MCI vamp: procedures)+≡

```

subroutine mci_vamp_prepare_simulation (mci)
  class(mci_vamp_t), intent(inout) :: mci
  logical :: success
  if (mci%grid_filename_set) then
    call mci%read_grids_header (success)
    call mci%compute_md5sum ()
    if (.not. success) then
      call msg_fatal ("Simulate: " &
        // "reading integration grids from file '" &
        // char (mci%grid_filename) // "' failed")
    end if
  else
    call msg_bug ("VAMP: simulation: no grids, no grid filename")
  end if
end subroutine mci_vamp_prepare_simulation

```

Generate weighted event. Note that the event weight (`vamp_weight`) is not just the MCI weight. `vamp_next_event` selects a channel based on the channel weights multiplied by the (previously recorded) maximum integrand value of

the channel. The MCI weight is renormalized accordingly, to cancel this effect on the result.

```

(MCI vamp: mci vamp: TBP)+≡
  procedure :: generate_weighted_event => mci_vamp_generate_weighted_event

(MCI vamp: procedures)+≡
  subroutine mci_vamp_generate_weighted_event (mci, instance, sampler)
    class(mci_vamp_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout), target :: instance
    class(mci_sampler_t), intent(inout), target :: sampler
    class(vamp_data_t), allocatable :: data
    type(exception) :: vamp_exception
    select type (instance)
    type is (mci_vamp_instance_t)
      instance%vamp_weight_set = .false.
      allocate (mci_workspace_t :: data)
      select type (data)
      type is (mci_workspace_t)
        data%sampler => sampler
        data%instance => instance
      end select
      select type (rng => mci%rng)
      type is (rng_tao_t)
        if (instance%grids_defined) then
          call vamp_next_event ( &
            instance%vamp_x, &
            rng%state, &
            instance%grids, &
            vamp_sampling_function, &
            data, &
            phi = phi_trivial, &
            weight = instance%vamp_weight, &
            exc = vamp_exception)
          call handle_vamp_exception (vamp_exception, mci%verbose)
          instance%vamp_excess = 0
          instance%vamp_weight_set = .true.
        else
          call msg_bug ("VAMP: generate event: grids undefined")
        end if
      class default
        call msg_fatal ("VAMP event generation: &
          &random-number generator must be TAO")
      end select
    end select
  end subroutine mci_vamp_generate_weighted_event

```

Generate unweighted event.

```

(MCI vamp: mci vamp: TBP)+≡
  procedure :: generate_unweighted_event => &
    mci_vamp_generate_unweighted_event

(MCI vamp: procedures)+≡
  subroutine mci_vamp_generate_unweighted_event (mci, instance, sampler)
    class(mci_vamp_t), intent(inout) :: mci

```

```

class(mci_instance_t), intent(inout), target :: instance
class(mci_sampler_t), intent(inout), target :: sampler
class(vamp_data_t), allocatable :: data
type(exception) :: vamp_exception
select type (instance)
type is (mci_vamp_instance_t)
  instance%vamp_weight_set = .false.
  allocate (mci_workspace_t :: data)
  select type (data)
  type is (mci_workspace_t)
    data%sampler => sampler
    data%instance => instance
  end select
  select type (rng => mci%rng)
  type is (rng_tao_t)
    if (instance%grids_defined) then
      REJECTION: do
        call vamp_next_event ( &
          instance%vamp_x, &
          rng%state, &
          instance%grids, &
          vamp_sampling_function, &
          data, &
          phi = phi_trivial, &
          excess = instance%vamp_excess, &
          exc = vamp_exception)
        if (signal_is_pending ()) return
        if (sampler%is_valid ()) exit REJECTION
      end do REJECTION
      call handle_vamp_exception (vamp_exception, mci%verbose)
      instance%vamp_weight = 1
      instance%vamp_weight_set = .true.
    else
      call msg_bug ("VAMP: generate event: grids undefined")
    end if
  class default
    call msg_fatal ("VAMP event generation: &
      &random-number generator must be TAO")
  end select
end select
end subroutine mci_vamp_generate_unweighted_event

```

Rebuild an event, using the state input.

Note: This feature is currently unused.

```

⟨MCI vamp: mci vamp: TBP⟩+≡
  procedure :: rebuild_event => mci_vamp_rebuild_event

⟨MCI vamp: procedures⟩+≡
  subroutine mci_vamp_rebuild_event (mci, instance, sampler, state)
    class(mci_vamp_t), intent(inout) :: mci
    class(mci_instance_t), intent(inout) :: instance
    class(mci_sampler_t), intent(inout) :: sampler
    class(mci_state_t), intent(in) :: state
    call msg_bug ("MCI vamp rebuild event not implemented yet")
  end subroutine

```

```

end subroutine mci_vamp_rebuild_event

<MCI vamp: mci vamp: TBP>+=
  procedure :: pacify => mci_vamp_pacify

<MCI vamp: procedures>+=
  subroutine mci_vamp_pacify (object, efficiency_reset, error_reset)
    class(mci_vamp_t), intent(inout) :: object
    logical, intent(in), optional :: efficiency_reset, error_reset
    logical :: err_reset
    type(pass_t), pointer :: current_pass
    err_reset = .false.
    if (present (error_reset)) err_reset = error_reset
    current_pass => object%first_pass
    do while (associated (current_pass))
      if (allocated (current_pass%error) .and. err_reset) then
        current_pass%error = 0
      end if
      if (allocated (current_pass%efficiency) .and. err_reset) then
        current_pass%efficiency = 1
      end if
      current_pass => current_pass%next
    end do
  end subroutine mci_vamp_pacify

```

19.5.5 Sampler as Workspace

In the full setup, the sampling function requires the process instance object as workspace. We implement this by (i) implementing the process instance as a type extension of the abstract `sampler_t` object used by the MCI implementation and (ii) providing such an object as an extra argument to the sampling function that VAMP can call. To minimize cross-package dependencies, we use an abstract type `vamp_workspace` that VAMP declares and extend this by including a pointer to the `sampler` and `instance` objects. In the body of the sampling function, we dereference this pointer and can then work with the contents.

```

<MCI vamp: types>+=
  type, extends (vamp_data_t) :: mci_workspace_t
    class(mci_sampler_t), pointer :: sampler => null ()
    class(mci_vamp_instance_t), pointer :: instance => null ()
  end type mci_workspace_t

```

19.5.6 Integrator instance

The history entries should point to the corresponding history entry in the `pass_t` object. If there is none, we may allocate a local history, which is then just transient.

```

<MCI vamp: public>+=
  public :: mci_vamp_instance_t

```

```

<MCI vamp: types>+≡
type, extends (mci_instance_t) :: mci_vamp_instance_t
  type(mci_vamp_t), pointer :: mci => null ()
  logical :: grids_defined = .false.
  logical :: grids_from_file = .false.
  integer :: n_it = 0
  integer :: it = 0
  logical :: pass_complete = .false.
  integer :: n_calls = 0
  integer :: calls = 0
  logical :: it_complete = .false.
  logical :: enable_adapt_grids = .false.
  logical :: enable_adapt_weights = .false.
  logical :: allow_adapt_grids = .false.
  logical :: allow_adapt_weights = .false.
  logical :: negative_weights = .false.
  integer :: n_adapt_grids = 0
  integer :: n_adapt_weights = 0
  logical :: generating_events = .false.
  real(default) :: safety_factor = 1
  type(vamp_grids) :: grids
  real(default) :: g = 0
  real(default), dimension(:), allocatable :: gi
  real(default) :: integral = 0
  real(default) :: error = 0
  real(default) :: efficiency = 0
  real(default), dimension(:), allocatable :: vamp_x
  logical :: vamp_weight_set = .false.
  real(default) :: vamp_weight = 0
  real(default) :: vamp_excess = 0
  logical :: allocate_global_history = .false.
  type(vamp_history), dimension(:), pointer :: v_history => null ()
  logical :: allocate_channel_history = .false.
  type(vamp_history), dimension(:, :), pointer :: v_histories => null ()
contains
  <MCI vamp: mci vamp instance: TBP>
end type mci_vamp_instance_t

```

Output.

```

<MCI vamp: mci vamp instance: TBP>≡
  procedure :: write => mci_vamp_instance_write

<MCI vamp: procedures>+≡
subroutine mci_vamp_instance_write (object, unit, pacify)
  class(mci_vamp_instance_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: pacify
  integer :: u, i
  character(len=7) :: fmt
  call pac_fmt (fmt, FMT_17, FMT_14, pacify)
  u = given_output_unit (unit)
  write (u, "(3x,A," // FMT_19 // ")") "Integrand = ", object%integrand
  write (u, "(3x,A," // FMT_19 // ")") "Weight      = ", object%vamp_weight
  if (object%vamp_weight_set) then

```



```

write (u, "(3x,A," // FMT_19 // ")") "VAMP wgt = ", object%vamp_weight
if (object%vamp_excess /= 0) then
  write (u, "(3x,A," // FMT_19 // ")") "VAMP exc = ", &
    object%vamp_excess
end if
end if
write (u, "(3x,A,L1)") "adapt grids = ", object%enable_adapt_grids
write (u, "(3x,A,L1)") "adapt weights = ", object%enable_adapt_weights
if (object%grids_defined) then
  if (object%grids_from_file) then
    write (u, "(3x,A)") "VAMP grids: read from file"
  else
    write (u, "(3x,A)") "VAMP grids: defined"
  end if
else
  write (u, "(3x,A)") "VAMP grids: [undefined]"
end if
write (u, "(3x,A,I0)") "n_it = ", object%n_it
write (u, "(3x,A,I0)") "it = ", object%it
write (u, "(3x,A,L1)") "pass complete = ", object%it_complete
write (u, "(3x,A,I0)") "n_calls = ", object%n_calls
write (u, "(3x,A,I0)") "calls = ", object%calls
write (u, "(3x,A,L1)") "it complete = ", object%it_complete
write (u, "(3x,A,I0)") "n adapt.(g) = ", object%n_adapt_grids
write (u, "(3x,A,I0)") "n adapt.(w) = ", object%n_adapt_weights
write (u, "(3x,A,L1)") "gen. events = ", object%generating_events
write (u, "(3x,A,L1)") "neg. weights = ", object%negative_weights
if (object%safety_factor /= 1) write &
  (u, "(3x,A," // fmt // ")") "safety f = ", object%safety_factor
write (u, "(3x,A," // fmt // ")") "integral = ", object%integral
write (u, "(3x,A," // fmt // ")") "error = ", object%error
write (u, "(3x,A," // fmt // ")") "eff. = ", object%efficiency
write (u, "(3x,A)") "weights:"
do i = 1, size(object%w)
  write (u, "(5x,I0,1x," // FMT_12 // ")") i, object%w(i)
end do
end subroutine mci_vamp_instance_write

```

Write the grids to the specified unit.

(MCI vamp: mci vamp instance: TBP)+≡

```

procedure :: write_grids => mci_vamp_instance_write_grids

```

(MCI vamp: procedures)+≡

```

subroutine mci_vamp_instance_write_grids (object, unit)
  class(mci_vamp_instance_t), intent(in) :: object
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  if (object%grids_defined) then
    call vamp_write_grids (object%grids, u, write_integrals = .true.)
  end if
end subroutine mci_vamp_instance_write_grids

```

Finalizer: the history arrays are pointer arrays and need finalization.

```

(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: final => mci_vamp_instance_final

(MCI vamp: tests)≡
  subroutine mci_vamp_instance_final (object)
    class(mci_vamp_instance_t), intent(inout) :: object
    if (object%allocate_global_history) then
      if (associated (object%v_history)) then
        call vamp_delete_history (object%v_history)
        deallocate (object%v_history)
      end if
    end if
    if (object%allocate_channel_history) then
      if (associated (object%v_histories)) then
        call vamp_delete_history (object%v_histories)
        deallocate (object%v_histories)
      end if
    end if
    if (object%grids_defined) then
      call vamp_delete_grids (object%grids)
      object%grids_defined = .false.
    end if
  end subroutine mci_vamp_instance_final

```

Initializer.

```

(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: init => mci_vamp_instance_init

(MCI vamp: procedures)+≡
  subroutine mci_vamp_instance_init (mci_instance, mci)
    class(mci_vamp_instance_t), intent(out) :: mci_instance
    class(mci_t), intent(in), target :: mci
    call mci_instance%base_init (mci)
    select type (mci)
      type is (mci_vamp_t)
        mci_instance%mci => mci
        allocate (mci_instance%gi (mci%n_channel))
        mci_instance%allocate_global_history = .not. mci%history_par%global
        mci_instance%allocate_channel_history = .not. mci%history_par%channel
        mci_instance%negative_weights = mci%negative_weights
      end select
  end subroutine mci_vamp_instance_init

```

Prepare a new integration pass: write the pass-specific settings to the `instance` object. This should be called initially, together with the `create_grids` procedure, and whenever we start a new integration pass.

Set `reshape` if the number of calls is different than previously (unless it was zero, indicating the first pass).

We link VAMP histories to the allocated histories in the current pass object, so the recorded results are persistent. However, if there are no histories present there, we allocate them locally. In that case, the histories will disappear together

with the MCI instance object.

```

(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: new_pass => mci_vamp_instance_new_pass

(MCI vamp: procedures)+≡
  subroutine mci_vamp_instance_new_pass (instance, reshape)
    class(mci_vamp_instance_t), intent(inout) :: instance
    logical, intent(out) :: reshape
    type(pass_t), pointer :: current
    associate (mci => instance%mci)
      current => mci%current_pass
      instance%n_it = current%n_it
      if (instance%n_calls == 0) then
        reshape = .false.
        instance%n_calls = current%n_calls
      else if (instance%n_calls == current%n_calls) then
        reshape = .false.
      else
        reshape = .true.
        instance%n_calls = current%n_calls
      end if
      instance%it = 0
      instance%calls = 0
      instance%enable_adapt_grids = current%adapt_grids
      instance%enable_adapt_weights = current%adapt_weights
      instance%generating_events = .false.
      if (instance%allocate_global_history) then
        if (associated (instance%v_history)) then
          call vamp_delete_history (instance%v_history)
          deallocate (instance%v_history)
        end if
        allocate (instance%v_history (instance%n_it))
        call vamp_create_history (instance%v_history, verbose = .false.)
      else
        instance%v_history => current%v_history
      end if
      if (instance%allocate_channel_history) then
        if (associated (instance%v_histories)) then
          call vamp_delete_history (instance%v_histories)
          deallocate (instance%v_histories)
        end if
        allocate (instance%v_histories (instance%n_it, mci%n_channel))
        call vamp_create_history (instance%v_histories, verbose = .false.)
      else
        instance%v_histories => current%v_histories
      end if
    end associate
  end subroutine mci_vamp_instance_new_pass

```

Create a grid set within the instance object, using the data of the current integration pass. Also reset counters that track this grid set.

```

(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: create_grids => mci_vamp_instance_create_grids

```

```

<MCI vamp: procedures>+=
subroutine mci_vamp_instance_create_grids (instance)
  class(mci_vamp_instance_t), intent(inout) :: instance
  type (pass_t), pointer :: current
  integer, dimension(:), allocatable :: num_div
  real(default), dimension(:,:), allocatable :: region
  associate (mci => instance%mci)
    current => mci%current_pass
    allocate (num_div (mci%n_dim))
    allocate (region (2, mci%n_dim))
    region(1,:) = 0
    region(2,:) = 1
    num_div = current%n_bins
    instance%n_adapt_grids = 0
    instance%n_adapt_weights = 0
    if (.not. instance%grids_defined) then
      call vamp_create_grids (instance%grids, &
        region, &
        current%n_calls, &
        weights = instance%w, &
        num_div = num_div, &
        stratified = mci%grid_par%stratified)
      instance%grids_defined = .true.
    else
      call msg_bug ("VAMP: create grids: grids already defined")
    end if
  end associate
end subroutine mci_vamp_instance_create_grids

```

Reset a grid set, so we can start a fresh integration pass. In effect, we delete results of previous integrations, but keep the grid shapes, weights, and variance arrays, so adaptation is still possible. The grids are prepared for a specific number of calls (per iteration) and sampling mode (stratified/importance).

The `vamp_discard_integrals` implementation will reshape the grids only if the argument `num_calls` is present.

```

<MCI vamp: mci vamp instance: TBP>+=
procedure :: discard_integrals => mci_vamp_instance_discard_integrals

<MCI vamp: procedures>+=
subroutine mci_vamp_instance_discard_integrals (instance, reshape)
  class(mci_vamp_instance_t), intent(inout) :: instance
  logical, intent(in) :: reshape
  instance%calls = 0
  instance%integral = 0
  instance%error = 0
  instance%efficiency = 0
  associate (mci => instance%mci)
    if (instance%grids_defined) then
      if (mci%grid_par%use_vamp_equivalences) then
        if (reshape) then
          call vamp_discard_integrals (instance%grids, &
            num_calls = instance%n_calls, &
            stratified = mci%grid_par%stratified, &
            eq = mci%equivalences)

```

```

        else
            call vamp_discard_integrals (instance%grids, &
                stratified = mci%grid_par%stratified, &
                eq = mci%equivalences)
        end if
    else
        if (reshape) then
            call vamp_discard_integrals (instance%grids, &
                num_calls = instance%n_calls, &
                stratified = mci%grid_par%stratified)
        else
            call vamp_discard_integrals (instance%grids, &
                stratified = mci%grid_par%stratified)
        end if
    end if
else
    call msg_bug ("VAMP: discard integrals: grids undefined")
end if
end associate
end subroutine mci_vamp_instance_discard_integrals

```

After grids are created (with equidistant binning and equal weight), adaptation is redundant. Therefore, we should allow it only after a complete integration step has been performed, calling this.

```

<MCI vamp: mci vamp instance: TBP>+≡
    procedure :: allow_adaptation => mci_vamp_instance_allow_adaptation

<MCI vamp: procedures>+≡
    subroutine mci_vamp_instance_allow_adaptation (instance)
        class(mci_vamp_instance_t), intent(inout) :: instance
        instance%allow_adapt_grids = .true.
        instance%allow_adapt_weights = .true.
    end subroutine mci_vamp_instance_allow_adaptation

```

Adapt grids.

```

<MCI vamp: mci vamp instance: TBP>+≡
    procedure :: adapt_grids => mci_vamp_instance_adapt_grids

<MCI vamp: procedures>+≡
    subroutine mci_vamp_instance_adapt_grids (instance)
        class(mci_vamp_instance_t), intent(inout) :: instance
        if (instance%enable_adapt_grids .and. instance%allow_adapt_grids) then
            if (instance%grids_defined) then
                call vamp_refine_grids (instance%grids)
                instance%n_adapt_grids = instance%n_adapt_grids + 1
            else
                call msg_bug ("VAMP: adapt grids: grids undefined")
            end if
        end if
    end subroutine mci_vamp_instance_adapt_grids

```

Adapt weights. Use the variance array returned by VAMP for recalculating the weight array. The parameter `channel_weights_power` dampens fluctuations.

If the number of calls in a given channel falls below a user-defined threshold, the weight is not lowered further but kept at this threshold. The other channel weights are reduced accordingly.

```

(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: adapt_weights => mci_vamp_instance_adapt_weights

(MCI vamp: procedures)+≡
  subroutine mci_vamp_instance_adapt_weights (instance)
    class(mci_vamp_instance_t), intent(inout) :: instance
    real(default) :: w_sum, w_avg_ch, sum_w_underflow, w_min
    integer :: n_ch, ch, n_underflow
    logical, dimension(:), allocatable :: mask, underflow
    type(exception) :: vamp_exception
    if (instance%enable_adapt_weights .and. instance%allow_adapt_weights) then
      associate (mci => instance%mci)
        if (instance%grids_defined) then
          instance%w = instance%grids%weights &
            * vamp_get_variance (instance%grids%grids) &
            ** mci%grid_par%channel_weights_power
          w_sum = sum (instance%w)
          if (w_sum /= 0) then
            instance%w = instance%w / w_sum
            if (mci%n_chain /= 0) then
              allocate (mask (mci%n_channel))
              do ch = 1, mci%n_chain
                mask = mci%chain == ch
                n_ch = count (mask)
                if (n_ch /= 0) then
                  w_avg_ch = sum (instance%w, mask) / n_ch
                  where (mask) instance%w = w_avg_ch
                end if
              end do
            end if
          end if
          if (mci%grid_par%threshold_calls /= 0) then
            w_min = &
              real (mci%grid_par%threshold_calls, default) &
              / instance%n_calls
            allocate (underflow (mci%n_channel))
            underflow = instance%w /= 0 .and. abs (instance%w) < w_min
            n_underflow = count (underflow)
            sum_w_underflow = sum (instance%w, mask=underflow)
            if (sum_w_underflow /= 1) then
              where (underflow)
                instance%w = w_min
              elsewhere
                instance%w = instance%w &
                  * (1 - n_underflow * w_min) / (1 - sum_w_underflow)
              end where
            end if
          end if
        end if
      end if
      call vamp_update_weights (instance%grids, instance%w, &
        exc = vamp_exception)
      call handle_vamp_exception (vamp_exception, mci%verbose)
    end if
  end subroutine

```

```

        else
            call msg_bug ("VAMP: adapt weights: grids undefined")
        end if
    end associate
    instance%n_adapt_weights = instance%n_adapt_weights + 1
end if
end subroutine mci_vamp_instance_adapt_weights

```

Integration: sample the VAMP grids. The number of calls etc. are already stored inside the grids. We provide the random-number generator, the sampling function, and a link to the workspace object, which happens to contain a pointer to the sampler object. The sampler object thus becomes the workspace of the sampling function.

Note: in the current implementation, the random-number generator must be the TAO generator. This explicit dependence should be removed from the VAMP implementation.

```

<MCI vamp: mci_vamp_instance: TBP>+≡
    procedure :: sample_grids => mci_vamp_instance_sample_grids

<MCI vamp: procedures>+≡
    subroutine mci_vamp_instance_sample_grids (instance, rng, sampler, eq)
        class(mci_vamp_instance_t), intent(inout), target :: instance
        class(rng_t), intent(inout) :: rng
        class(mci_sampler_t), intent(inout), target :: sampler
        type(vamp_equivalences_t), intent(in), optional :: eq
        class(vamp_data_t), allocatable :: data
        type(exception) :: vamp_exception
        allocate (mci_workspace_t :: data)
        select type (data)
            type is (mci_workspace_t)
                data%sampler => sampler
                data%instance => instance
            end select
        select type (rng)
            type is (rng_tao_t)
                instance%it = instance%it + 1
                instance%calls = 0
                if (instance%grids_defined) then
                    call vamp_sample_grids ( &
                        rng%state, &
                        instance%grids, &
                        vamp_sampling_function, &
                        data, &
                        1, &
                        eq = eq, &
                        history = instance%v_history(instance%it:), &
                        histories = instance%v_histories(instance%it:,:), &
                        integral = instance%integral, &
                        std_dev = instance%error, &
                        exc = vamp_exception, &
                        negative_weights = instance%negative_weights)
                    call handle_vamp_exception (vamp_exception, instance%nci%verbose)
                    instance%efficiency = instance%get_efficiency ()
                end if
            end select
        end select
    end subroutine

```

```

        else
            call msg_bug ("VAMP: sample grids: grids undefined")
        end if
    class default
        call msg_fatal ("VAMP integration: random-number generator must be TAO")
    end select
end subroutine mci_vamp_instance_sample_grids

```

Compute the reweighting efficiency for the current grids, suitable averaged over all active channels.

```

<MCI vamp: mci vamp instance: TBP>+≡
    procedure :: get_efficiency_array => mci_vamp_instance_get_efficiency_array
    procedure :: get_efficiency => mci_vamp_instance_get_efficiency

<MCI vamp: procedures>+≡
    function mci_vamp_instance_get_efficiency_array (mci) result (efficiency)
        class(mci_vamp_instance_t), intent(in) :: mci
        real(default), dimension(:), allocatable :: efficiency
        allocate (efficiency (mci%mci%n_channel))
        where (mci%grids%grids%f_max /= 0)
            efficiency = mci%grids%grids%mu(1) / abs (mci%grids%grids%f_max)
        elsewhere
            efficiency = 0
        end where
    end function mci_vamp_instance_get_efficiency_array

    function mci_vamp_instance_get_efficiency (mci) result (efficiency)
        class(mci_vamp_instance_t), intent(in) :: mci
        real(default) :: efficiency
        real(default), dimension(:), allocatable :: weight
        real(default) :: norm
        allocate (weight (mci%mci%n_channel))
        weight = mci%grids%weights * abs (mci%grids%grids%f_max)
        norm = sum (weight)
        if (norm /= 0) then
            efficiency = dot_product (mci%get_efficiency_array (), weight) / norm
        else
            efficiency = 1
        end if
    end function mci_vamp_instance_get_efficiency

```

Prepare an event generation pass. Should be called before a sequence of events is generated, then we should call the corresponding finalizer.

The pass-specific data of the previous integration pass are retained, but we reset the number of iterations and calls to zero. The latter now counts the number of events (calls to the sampling function, actually).

```

<MCI vamp: mci vamp instance: TBP>+≡
    procedure :: init_simulation => mci_vamp_instance_init_simulation

<MCI vamp: procedures>+≡
    subroutine mci_vamp_instance_init_simulation (instance, safety_factor)
        class(mci_vamp_instance_t), intent(inout) :: instance
        real(default), intent(in), optional :: safety_factor

```



```

associate (mci => instance%mci)
  allocate (instance%vamp_x (mci%n_dim))
  instance%it = 0
  instance%calls = 0
  instance%generating_events = .true.
  if (present (safety_factor)) instance%safety_factor = safety_factor
  if (.not. instance%grids_defined) then
    if (mci%grid_filename_set) then
      if (.not. mci%check_grid_file) &
        call msg_warning ("Reading grid file: MD5 sum check disabled")
      call msg_message ("Simulate: " &
        // "using integration grids from file '" &
        // char (mci%grid_filename) // "'")
      call mci%read_grids_data (instance)
      if (instance%safety_factor /= 1) then
        write (msg_buffer, "(A,ES10.3,A)") "Simulate: &
          &applying safety factor", instance%safety_factor, &
            " to event rejection"
        call msg_message ()
        instance%grids%grids%f_max = &
          instance%grids%grids%f_max * instance%safety_factor
      end if
    else
      call msg_bug ("VAMP: simulation: no grids, no grid filename")
    end if
  end if
end associate
end subroutine mci_vamp_instance_init_simulation

```

Finalize an event generation pass. Should be called before a sequence of events is generated, then we should call the corresponding finalizer.

```

<MCI vamp: mci vamp instance: TBP>+≡
  procedure :: final_simulation => mci_vamp_instance_final_simulation
<MCI vamp: procedures>+≡
  subroutine mci_vamp_instance_final_simulation (instance)
    class(mci_vamp_instance_t), intent(inout) :: instance
    if (allocated (instance%vamp_x)) deallocate (instance%vamp_x)
  end subroutine mci_vamp_instance_final_simulation

```

19.5.7 Sampling function

The VAMP sampling function has a well-defined interface which we have to implement. The `data` argument allows us to pass pointers to the `sampler` and `instance` objects, so we can access configuration data and fill point-dependent contents within these objects.

The `weights` and `channel` argument must be present in the call.

Note: we would normally declare the `instance` pointer with the concrete type, or just use the `data` component directly. Unfortunately, gfortran 4.6 forgets the inherited base-type methods in that case.

Note: this is the place where we must look for external signals, i.e., interrupt from the OS. We would like to raise a VAMP exception which is then caught by

vamp_sample_grids as the caller, so it dumps its current state and returns (with the signal still pending). WHIZARD will then terminate gracefully. Of course, VAMP should be able to resume from the dump.

In the current implementation, we handle the exception in place and terminate immediately. The incomplete current integration pass is lost.

```

(MCI vamp: procedures)+≡
function vamp_sampling_function &
  (xi, data, weights, channel, grids) result (f)
  real(default) :: f
  real(default), dimension(:), intent(in) :: xi
  class(vamp_data_t), intent(in) :: data
  real(default), dimension(:), intent(in), optional :: weights
  integer, intent(in), optional :: channel
  type(vamp_grid), dimension(:), intent(in), optional :: grids
  type(exception) :: exc
  class(mci_instance_t), pointer :: instance
  logical :: verbose
  character(*), parameter :: FN = "WHIZARD sampling function"
  select type (data)
  type is (mci_workspace_t)
    instance => data%instance
    select type (instance)
    class is (mci_vamp_instance_t)
      instance%calls = instance%calls + 1
      verbose = instance%mci%verbose
    end select
    call instance%evaluate (data%sampler, channel, xi)
    if (signal_is_pending ()) then
      call raise_exception (exc, EXC_FATAL, FN, "signal received")
      call handle_vamp_exception (exc, verbose)
      call terminate_now_if_signal ()
    end if
    f = instance%get_value ()
  end select
end function vamp_sampling_function

```

This is supposed to be the mapping between integration channels. The VAMP event generating procedures technically require it, but it is meaningless in our setup where all transformations happen inside the sampler object. So, this implementation is trivial:

```

(MCI vamp: procedures)+≡
pure function phi_trivial (xi, channel_dummy) result (x)
  real(default), dimension(:), intent(in) :: xi
  integer, intent(in) :: channel_dummy
  real(default), dimension(size(xi)) :: x
  x = xi
end function phi_trivial

```

19.5.8 Integrator instance: evaluation

Here, we compute the multi-channel reweighting factor for the current channel, that accounts for the Jacobians of the transformations from/to all other channels.

The computation of the VAMP probabilities may consume considerable time, therefore we enable parallel evaluation. (Collecting the contributions to `mci%g` is a reduction, which we should also implement via OpenMP.)

```
(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: compute_weight => mci_vamp_instance_compute_weight

(MCI vamp: procedures)+≡
  subroutine mci_vamp_instance_compute_weight (mci, c)
    class(mci_vamp_instance_t), intent(inout) :: mci
    integer, intent(in) :: c
    integer :: i
    mci%selected_channel = c
    !$OMP PARALLEL PRIVATE(i) SHARED(mci)
    !$OMP DO
    do i = 1, mci%mci%n_channel
      if (mci%w(i) /= 0) then
        mci%gi(i) = vamp_probability (mci%grids%grids(i), mci%x(:,i))
      else
        mci%gi(i) = 0
      end if
    end do
    !$OMP END DO
    !$OMP END PARALLEL
    mci%g = 0
    if (mci%gi(c) /= 0) then
      do i = 1, mci%mci%n_channel
        if (mci%w(i) /= 0 .and. mci%f(i) /= 0) then
          mci%g = mci%g + mci%w(i) * mci%gi(i) / mci%f(i)
        end if
      end do
    end if
    if (mci%g /= 0) then
      mci%mci_weight = mci%gi(c) / mci%g
    else
      mci%mci_weight = 0
    end if
  end subroutine mci_vamp_instance_compute_weight
```

Record the integrand.

```
(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: record_integrand => mci_vamp_instance_record_integrand

(MCI vamp: procedures)+≡
  subroutine mci_vamp_instance_record_integrand (mci, integrand)
    class(mci_vamp_instance_t), intent(inout) :: mci
    real(default), intent(in) :: integrand
    mci%integrand = integrand
  end subroutine mci_vamp_instance_record_integrand
```

Get the event weight. The default routine returns the same value that we would use for integration. This is correct if we select the integration channel according to the channel weight. `vamp_next_event` does differently, so we should rather rely on the weight that VAMP returns. This is the value stored in `vamp_weight`. We override the default TBP accordingly.

```

(MCI vamp: mci vamp instance: TBP)+≡
  procedure :: get_event_weight => mci_vamp_instance_get_event_weight
  procedure :: get_event_excess => mci_vamp_instance_get_event_excess

(MCI vamp: procedures)+≡
  function mci_vamp_instance_get_event_weight (mci) result (value)
    class(mci_vamp_instance_t), intent(in) :: mci
    real(default) :: value
    if (mci%vamp_weight_set) then
      value = mci%vamp_weight
    else
      call msg_bug ("VAMP: attempt to read undefined event weight")
    end if
  end function mci_vamp_instance_get_event_weight

  function mci_vamp_instance_get_event_excess (mci) result (value)
    class(mci_vamp_instance_t), intent(in) :: mci
    real(default) :: value
    if (mci%vamp_weight_set) then
      value = mci%vamp_excess
    else
      call msg_bug ("VAMP: attempt to read undefined event excess weight")
    end if
  end function mci_vamp_instance_get_event_excess

```

19.5.9 VAMP exceptions

A VAMP routine may have raised an exception. Turn this into a WHIZARD error message.

An external signal could raise a fatal exception, but this should be delayed and handled by the correct termination routine.

```

(MCI vamp: procedures)+≡
  subroutine handle_vamp_exception (exc, verbose)
    type(exception), intent(in) :: exc
    logical, intent(in) :: verbose
    integer :: exc_level
    if (verbose) then
      exc_level = EXC_INFO
    else
      exc_level = EXC_ERROR
    end if
    if (exc%level >= exc_level) then
      write (msg_buffer, "(A,':',1x,A)") trim (exc%origin), trim (exc%message)
      select case (exc%level)
        case (EXC_INFO); call msg_message ()
        case (EXC_WARN); call msg_warning ()
        case (EXC_ERROR); call msg_error ()
      end select
    end if
  end subroutine handle_vamp_exception

```

```

        case (EXC_FATAL)
            if (signal_is_pending ()) then
                call msg_message ()
            else
                call msg_fatal ()
            end if
        end select
    end if
end subroutine handle_vamp_exception

```

19.5.10 Unit tests

```

<MCI vamp: public>+≡
    public :: mci_vamp_test

<MCI vamp: tests>+≡
    subroutine mci_vamp_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <MCI vamp: execute tests>
    end subroutine mci_vamp_test

```

Test sampler

A test sampler object should implement a function with known integral that we can use to check the integrator.

In mode 1, the function is $f(x) = 3x^2$ with integral $\int_0^1 f(x) dx = 1$ and maximum $f(1) = 3$. If the integration dimension is greater than one, the function is extended as a constant in the other dimension(s).

In mode 2, the function is $11x^{10}$, also with integral 1.

```

<MCI vamp: test types>≡
    type, extends (mci_sampler_t) :: test_sampler_1_t
        real(default), dimension(:), allocatable :: x
        real(default) :: val
        integer :: mode = 1
    contains
        <MCI vamp: test sampler 1: TBP>
    end type test_sampler_1_t

```

Output: There is nothing stored inside, so just print an informative line.

```

<MCI vamp: test sampler 1: TBP>≡
    procedure :: write => test_sampler_1_write

<MCI vamp: tests>+≡
    subroutine test_sampler_1_write (object, unit, testflag)
        class(test_sampler_1_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: testflag
        integer :: u
        u = given_output_unit (unit)
        select case (object%mode)

```

```

case (1)
  write (u, "(1x,A)") "Test sampler: f(x) = 3 x^2"
case (2)
  write (u, "(1x,A)") "Test sampler: f(x) = 11 x^10"
case (3)
  write (u, "(1x,A)") "Test sampler: f(x) = 11 x^10 * 2 * cos^2 (2 pi y)"
end select
end subroutine test_sampler_1_write

```

Evaluation: compute the function value. The output x parameter (only one channel) is identical to the input x , and the Jacobian is 1.

```

<MCI vamp: test_sampler_1: TBP>+≡
  procedure :: evaluate => test_sampler_1_evaluate

<MCI vamp: tests>+≡
  subroutine test_sampler_1_evaluate (sampler, c, x_in, val, x, f)
    class(test_sampler_1_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    if (allocated (sampler%x)) deallocate (sampler%x)
    allocate (sampler%x (size (x_in)))
    sampler%x = x_in
    select case (sampler%mode)
    case (1)
      sampler%val = 3 * x_in(1) ** 2
    case (2)
      sampler%val = 11 * x_in(1) ** 10
    case (3)
      sampler%val = 11 * x_in(1) ** 10 * 2 * cos (twopi * x_in(2)) ** 2
    end select
    call sampler%fetch (val, x, f)
  end subroutine test_sampler_1_evaluate

```

The point is always valid.

```

<MCI vamp: test_sampler_1: TBP>+≡
  procedure :: is_valid => test_sampler_1_is_valid

<MCI vamp: tests>+≡
  function test_sampler_1_is_valid (sampler) result (valid)
    class(test_sampler_1_t), intent(in) :: sampler
    logical :: valid
    valid = .true.
  end function test_sampler_1_is_valid

```

Rebuild: compute all but the function value.

```

<MCI vamp: test_sampler_1: TBP>+≡
  procedure :: rebuild => test_sampler_1_rebuild

<MCI vamp: tests>+≡
  subroutine test_sampler_1_rebuild (sampler, c, x_in, val, x, f)

```

```

class(test_sampler_1_t), intent(inout) :: sampler
integer, intent(in) :: c
real(default), dimension(:), intent(in) :: x_in
real(default), intent(in) :: val
real(default), dimension(:,:), intent(out) :: x
real(default), dimension(:), intent(out) :: f
if (allocated (sampler%x)) deallocate (sampler%x)
allocate (sampler%x (size (x_in)))
sampler%x = x_in
sampler%val = val
x(:,1) = sampler%x
f = 1
end subroutine test_sampler_1_rebuild

```

Extract the results.

```

⟨MCI vamp: test sampler 1: TBP⟩+≡
  procedure :: fetch => test_sampler_1_fetch
⟨MCI vamp: tests⟩+≡
  subroutine test_sampler_1_fetch (sampler, val, x, f)
    class(test_sampler_1_t), intent(in) :: sampler
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    val = sampler%val
    x(:,1) = sampler%x
    f = 1
  end subroutine test_sampler_1_fetch

```

Two-channel, two dimension test sampler

This sampler implements the function

$$f(x, y) = 4 \sin^2(\pi x) \sin^2(\pi y) + 2 \sin^2(\pi v) \quad (19.11)$$

where

$$x = u^v \quad u = xy \quad (19.12)$$

$$y = u^{(1-v)} \quad v = \frac{1}{2} \left(1 + \frac{\log(x/y)}{\log xy} \right) \quad (19.13)$$

Each term contributes 1 to the integral. The first term in the function is peaked along a cross aligned to the coordinates x and y , while the second term is peaked along the diagonal $x = y$.

The Jacobian is

$$\frac{\partial(x, y)}{\partial(u, v)} = |\log u| \quad (19.14)$$

```

⟨MCI vamp: test types⟩+≡
  type, extends (mci_sampler_t) :: test_sampler_2_t
    real(default), dimension(:,:), allocatable :: x
    real(default), dimension(:), allocatable :: f

```

```

    real(default) :: val
contains
  <MCI vamp: test sampler 2: TBP>
end type test_sampler_2_t

```

Output: There is nothing stored inside, so just print an informative line.

```

<MCI vamp: test sampler 2: TBP>≡
  procedure :: write => test_sampler_2_write

<MCI vamp: tests>+≡
  subroutine test_sampler_2_write (object, unit, testflag)
    class(test_sampler_2_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Two-channel test sampler 2"
  end subroutine test_sampler_2_write

```

Kinematics: compute x and Jacobians, given the input parameter array.

```

<MCI vamp: test sampler 2: TBP>+≡
  procedure :: compute => test_sampler_2_compute

<MCI vamp: tests>+≡
  subroutine test_sampler_2_compute (sampler, c, x_in)
    class(test_sampler_2_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default) :: xx, yy, uu, vv
    if (.not. allocated (sampler%x)) &
      allocate (sampler%x (size (x_in), 2))
    if (.not. allocated (sampler%f)) &
      allocate (sampler%f (2))
    select case (c)
    case (1)
      xx = x_in(1)
      yy = x_in(2)
      uu = xx * yy
      vv = (1 + log (xx/yy) / log (xx*yy)) / 2
    case (2)
      uu = x_in(1)
      vv = x_in(2)
      xx = uu ** vv
      yy = uu ** (1 - vv)
    end select
    sampler%val = (2 * sin (pi * xx) * sin (pi * yy)) ** 2 &
      + 2 * sin (pi * vv) ** 2
    sampler%f(1) = 1
    sampler%f(2) = abs (log (uu))
    sampler%x(:,1) = [xx, yy]
    sampler%x(:,2) = [uu, vv]
  end subroutine test_sampler_2_compute

```


Evaluation: compute the function value. The output x parameter (only one channel) is identical to the input x , and the Jacobian is 1.

```

(MCI vamp: test_sampler_2: TBP)+≡
  procedure :: evaluate => test_sampler_2_evaluate

(MCI vamp: tests)+≡
  subroutine test_sampler_2_evaluate (sampler, c, x_in, val, x, f)
    class(test_sampler_2_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    call sampler%compute (c, x_in)
    call sampler%fetch (val, x, f)
  end subroutine test_sampler_2_evaluate

```

The point is always valid.

```

(MCI vamp: test_sampler_2: TBP)+≡
  procedure :: is_valid => test_sampler_2_is_valid

(MCI vamp: tests)+≡
  function test_sampler_2_is_valid (sampler) result (valid)
    class(test_sampler_2_t), intent(in) :: sampler
    logical :: valid
    valid = .true.
  end function test_sampler_2_is_valid

```

Rebuild: compute all but the function value.

```

(MCI vamp: test_sampler_2: TBP)+≡
  procedure :: rebuild => test_sampler_2_rebuild

(MCI vamp: tests)+≡
  subroutine test_sampler_2_rebuild (sampler, c, x_in, val, x, f)
    class(test_sampler_2_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(in) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    call sampler%compute (c, x_in)
    x = sampler%x
    f = sampler%f
  end subroutine test_sampler_2_rebuild

```

Extract the results.

```

(MCI vamp: test_sampler_2: TBP)+≡
  procedure :: fetch => test_sampler_2_fetch

(MCI vamp: tests)+≡
  subroutine test_sampler_2_fetch (sampler, val, x, f)
    class(test_sampler_2_t), intent(in) :: sampler
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x

```

```

    real(default), dimension(:), intent(out) :: f
    val = sampler%val
    x = sampler%x
    f = sampler%f
end subroutine test_sampler_2_fetch

```

Two-channel, one dimension test sampler

This sampler implements the function

$$f(x, y) = a * 5x^4 + b * 5(1 - x)^4 \quad (19.15)$$

Each term contributes 1 to the integral, multiplied by a or b , respectively. The first term is peaked at $x = 1$, the second one at $x = 0$.

We implement the two mappings

$$x = u^{1/5} \quad \text{and} \quad x = 1 - v^{1/5}, \quad (19.16)$$

with Jacobians

$$\frac{\partial(x)}{\partial(u)} = u^{-4/5}/5 \quad \text{and} \quad v^{-4/5}/5, \quad (19.17)$$

respectively. The first mapping concentrates points near $x = 1$, the second one near $x = 0$.

```

<MCI vamp: test types>+≡
type, extends (mci_sampler_t) :: test_sampler_3_t
    real(default), dimension(:, :), allocatable :: x
    real(default), dimension(:), allocatable :: f
    real(default) :: val
    real(default) :: a = 1
    real(default) :: b = 1
contains
    <MCI vamp: test sampler 3: TBP>
end type test_sampler_3_t

```

Output: display a and b

```

<MCI vamp: test sampler 3: TBP>≡
    procedure :: write => test_sampler_3_write
<MCI vamp: tests>+≡
    subroutine test_sampler_3_write (object, unit, testflag)
        class(test_sampler_3_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: testflag
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Two-channel test sampler 3"
        write (u, "(3x,A,F5.2)") "a = ", object%a
        write (u, "(3x,A,F5.2)") "b = ", object%b
    end subroutine test_sampler_3_write

```

Kinematics: compute x and Jacobians, given the input parameter array.

```

(MCI vamp: test sampler 3: TBP)+≡
  procedure :: compute => test_sampler_3_compute

(MCI vamp: tests)+≡
  subroutine test_sampler_3_compute (sampler, c, x_in)
    class(test_sampler_3_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default) :: u, v, xx
    if (.not. allocated (sampler%x)) &
      allocate (sampler%x (size (x_in), 2))
    if (.not. allocated (sampler%f)) &
      allocate (sampler%f (2))
    select case (c)
    case (1)
      u = x_in(1)
      xx = u ** 0.2_default
      v = (1 - xx) ** 5._default
    case (2)
      v = x_in(1)
      xx = 1 - v ** 0.2_default
      u = xx ** 5._default
    end select
    sampler%val = sampler%a * 5 * xx ** 4 + sampler%b * 5 * (1 - xx) ** 4
    sampler%f(1) = 0.2_default * u ** (-0.8_default)
    sampler%f(2) = 0.2_default * v ** (-0.8_default)
    sampler%x(:,1) = [u]
    sampler%x(:,2) = [v]
  end subroutine test_sampler_3_compute

```

Evaluation: compute the function value. The output x parameter (only one channel) is identical to the input x , and the Jacobian is 1.

```

(MCI vamp: test sampler 3: TBP)+≡
  procedure :: evaluate => test_sampler_3_evaluate

(MCI vamp: tests)+≡
  subroutine test_sampler_3_evaluate (sampler, c, x_in, val, x, f)
    class(test_sampler_3_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    call sampler%compute (c, x_in)
    call sampler%fetch (val, x, f)
  end subroutine test_sampler_3_evaluate

```

The point is always valid.

```

(MCI vamp: test sampler 3: TBP)+≡
  procedure :: is_valid => test_sampler_3_is_valid

```

```

<MCI vamp: tests>+=
  function test_sampler_3_is_valid (sampler) result (valid)
    class(test_sampler_3_t), intent(in) :: sampler
    logical :: valid
    valid = .true.
  end function test_sampler_3_is_valid

```

Rebuild: compute all but the function value.

```

<MCI vamp: test sampler 3: TBP>+=
  procedure :: rebuild => test_sampler_3_rebuild

<MCI vamp: tests>+=
  subroutine test_sampler_3_rebuild (sampler, c, x_in, val, x, f)
    class(test_sampler_3_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(in) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    call sampler%compute (c, x_in)
    x = sampler%x
    f = sampler%f
  end subroutine test_sampler_3_rebuild

```

Extract the results.

```

<MCI vamp: test sampler 3: TBP>+=
  procedure :: fetch => test_sampler_3_fetch

<MCI vamp: tests>+=
  subroutine test_sampler_3_fetch (sampler, val, x, f)
    class(test_sampler_3_t), intent(in) :: sampler
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    val = sampler%val
    x = sampler%x
    f = sampler%f
  end subroutine test_sampler_3_fetch

```

One-dimensional integration

Construct an integrator and use it for a one-dimensional sampler.

Note: We would like to check the precise contents of the grid allocated during integration, but the output format for reals is very long (for good reasons), so the last digits in the grid content display are numerical noise. So, we just check the integration results.

```

<MCI vamp: execute tests>=
  call test (mci_vamp_1, "mci_vamp_1", &
    "one-dimensional integral", &
    u, results)

```

```

<MCI vamp: tests>+≡
subroutine mci_vamp_1 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_vamp_1"
  write (u, "(A)")  "* Purpose: integrate function in one dimension &
    &(single channel)"

  write (u, "(A)")
  write (u, "(A)")  "* Initialize integrator"
  write (u, "(A)")

  allocate (mci_vamp_t :: mci)
  call mci%set_dimensions (1, 1)
  select type (mci)
  type is (mci_vamp_t)
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
  end select

  allocate (rng_tao_t :: rng)
  call rng%init ()
  call mci%import_rng (rng)

  call mci%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Initialize instance"
  write (u, "(A)")

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  write (u, "(A)")  "* Initialize test sampler"
  write (u, "(A)")

  allocate (test_sampler_1_t :: sampler)
  call sampler%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Integrate with n_calls = 1000"
  write (u, "(A)")  " (lower precision to avoid"
  write (u, "(A)")  " numerical noise)"
  write (u, "(A)")

  select type (mci)
  type is (mci_vamp_t)
    call mci%add_pass ()
  end select

```

```

call mci%integrate (mci_instance, sampler, 1, 1000, pacify = .true.)
call mci%write (u, .true.)

write (u, "(A)")
write (u, "(A)")  "* Contents of mci_instance:"
write (u, "(A)")

call mci_instance%write (u, .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_1"

end subroutine mci_vamp_1

```

Multiple iterations

Construct an integrator and use it for a one-dimensional sampler. Integrate with five iterations without grid adaptation.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_2, "mci_vamp_2", &
    "multiple iterations", &
    u, results)

<MCI vamp: tests>+≡
subroutine mci_vamp_2 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_vamp_2"
  write (u, "(A)")  "* Purpose: integrate function in one dimension &
    &(single channel)"

  write (u, "(A)")
  write (u, "(A)")  "* Initialize integrator, sampler, instance"
  write (u, "(A)")

  allocate (mci_vamp_t :: mci)
  call mci%set_dimensions (1, 1)
  select type (mci)
  type is (mci_vamp_t)
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
  end select

```

```

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_1_t :: sampler)
select type (sampler)
type is (test_sampler_1_t)
    sampler%mode = 2
end select
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 100"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .false.)
end select
call mci%integrate (mci_instance, sampler, 3, 100)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Contents of mci_instance:"
write (u, "(A)")

call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_2"

end subroutine mci_vamp_2

```

Grid adaptation

Construct an integrator and use it for a one-dimensional sampler. Integrate with three iterations and in-between grid adaptations.

```

<MCI vamp: execute tests>+≡
call test (mci_vamp_3, "mci_vamp_3", &
    "grid adaptation", &
    u, results)

```

```

<MCI vamp: tests>+≡
subroutine mci_vamp_3 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_vamp_3"
  write (u, "(A)")  "* Purpose: integrate function in one dimension &
    &(single channel)"
  write (u, "(A)")  "*           and adapt grid"

  write (u, "(A)")
  write (u, "(A)")  "* Initialize integrator, sampler, instance"
  write (u, "(A)")

  allocate (mci_vamp_t :: mci)
  call mci%set_dimensions (1, 1)
  select type (mci)
  type is (mci_vamp_t)
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
  end select

  allocate (rng_tao_t :: rng)
  call rng%init ()
  call mci%import_rng (rng)

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  allocate (test_sampler_1_t :: sampler)
  select type (sampler)
  type is (test_sampler_1_t)
    sampler%mode = 2
  end select
  call sampler%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 100"
  write (u, "(A)")

  select type (mci)
  type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
  end select
  call mci%integrate (mci_instance, sampler, 3, 100)
  call mci%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Contents of mci_instance:"
  write (u, "(A)")

```



```

call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_3"

end subroutine mci_vamp_3

```

Two-dimensional integral

Construct an integrator and use it for a two-dimensional sampler. Integrate with three iterations and in-between grid adaptations.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_4, "mci_vamp_4", &
    "two-dimensional integration", &
    u, results)
<MCI vamp: tests>+≡
  subroutine mci_vamp_4 (u)
    integer, intent(in) :: u
    type(grid_parameters_t) :: grid_par
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(rng_t), allocatable :: rng

    write (u, "(A)")  "* Test output: mci_vamp_4"
    write (u, "(A)")  "* Purpose: integrate function in two dimensions &
      &(single channel)"
    write (u, "(A)")  "*           and adapt grid"

    write (u, "(A)")
    write (u, "(A)")  "* Initialize integrator, sampler, instance"
    write (u, "(A)")

    allocate (mci_vamp_t :: mci)
    call mci%set_dimensions (2, 1)
    select type (mci)
    type is (mci_vamp_t)
      grid_par%use_vamp_equivalences = .false.
      call mci%set_grid_parameters (grid_par)
    end select

    allocate (rng_tao_t :: rng)
    call rng%init ()
    call mci%import_rng (rng)

```

```

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_1_t :: sampler)
select type (sampler)
type is (test_sampler_1_t)
    sampler%mode = 3
end select
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
end select
call mci%integrate (mci_instance, sampler, 3, 1000)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Contents of mci_instance:"
write (u, "(A)")

call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_4"

end subroutine mci_vamp_4

```

Two-channel integral

Construct an integrator and use it for a two-dimensional sampler with two channels.

Integrate with three iterations and in-between grid adaptations.

```

<MCI vamp: execute tests>+≡
    call test (mci_vamp_5, "mci_vamp_5", &
        "two-dimensional integration", &
        u, results)

<MCI vamp: tests>+≡
    subroutine mci_vamp_5 (u)
        integer, intent(in) :: u
        type(grid_parameters_t) :: grid_par
        class(mci_t), allocatable, target :: mci

```

```

class(mci_instance_t), pointer :: mci_instance => null ()
class(mci_sampler_t), allocatable :: sampler
class(rng_t), allocatable :: rng

write (u, "(A)")  "* Test output: mci_vamp_5"
write (u, "(A)")  "* Purpose: integrate function in two dimensions &
                    &(two channels)"
write (u, "(A)")  "*           and adapt grid"

write (u, "(A)")
write (u, "(A)")  "* Initialize integrator, sampler, instance"
write (u, "(A)")

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (2, 2)
select type (mci)
type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_2_t :: sampler)
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
end select
call mci%integrate(mci_instance, sampler, 3, 1000)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Contents of mci_instance:"
write (u, "(A)")

call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_5"

end subroutine mci_vamp_5

```

Weight adaptation

Construct an integrator and use it for a one-dimensional sampler with two channels.

Integrate with three iterations and in-between weight adaptations.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_6, "mci_vamp_6", &
    "weight adaptation", &
    u, results)

<MCI vamp: tests>+≡
  subroutine mci_vamp_6 (u)
    integer, intent(in) :: u
    type(grid_parameters_t) :: grid_par
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(rng_t), allocatable :: rng

    write (u, "(A)")  "* Test output: mci_vamp_6"
    write (u, "(A)")  "* Purpose: integrate function in one dimension &
      &(two channels)"
    write (u, "(A)")  "*           and adapt weights"

    write (u, "(A)")
    write (u, "(A)")  "* Initialize integrator, sampler, instance"
    write (u, "(A)")

    allocate (mci_vamp_t :: mci)
    call mci%set_dimensions (1, 2)
    select type (mci)
    type is (mci_vamp_t)
      grid_par%stratified = .false.
      grid_par%use_vamp_equivalences = .false.
      call mci%set_grid_parameters (grid_par)
    end select

    allocate (rng_tao_t :: rng)
    call rng%init ()
    call mci%import_rng (rng)

    call mci%allocate_instance (mci_instance)
    call mci_instance%init (mci)

    allocate (test_sampler_3_t :: sampler)
    select type (sampler)
    type is (test_sampler_3_t)

```

```

        sampler%a = 0.9_default
        sampler%b = 0.1_default
    end select
    call sampler%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%add_pass (adapt_weights = .true.)
    end select
    call mci%integrate (mci_instance, sampler, 3, 1000)
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Contents of mci_instance:"
    write (u, "(A)")

    call mci_instance%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

    call mci_instance%final ()
    call mci%final ()
    deallocate (mci_instance)
    deallocate (mci)

    write (u, "(A)")
    write (u, "(A)")  "* Re-initialize with chained channels"
    write (u, "(A)")

    allocate (mci_vamp_t :: mci)
    call mci%set_dimensions (1, 2)
    call mci%declare_chains ([1,1])
    select type (mci)
    type is (mci_vamp_t)
        grid_par%stratified = .false.
        grid_par%use_vamp_equivalences = .false.
        call mci%set_grid_parameters (grid_par)
    end select

    allocate (rng_tao_t :: rng)
    call rng%init ()
    call mci%import_rng (rng)

    call mci%allocate_instance (mci_instance)
    call mci_instance%init (mci)

    write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
    write (u, "(A)")

```

```

select type (mci)
type is (mci_vamp_t)
  call mci%add_pass (adapt_weights = .true.)
end select
call mci%integrate (mci_instance, sampler, 3, 1000)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Contents of mci_instance:"
write (u, "(A)")

call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_6"

end subroutine mci_vamp_6

```

Equivalences

Construct an integrator and use it for a one-dimensional sampler with two channels.

Integrate with three iterations and in-between grid adaptations. Apply an equivalence between the two channels, so the binning of the two channels is forced to coincide. Compare this with the behavior without equivalences.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_7, "mci_vamp_7", &
    "use channel equivalences", &
    u, results)

<MCI vamp: tests>+≡
subroutine mci_vamp_7 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  type(phs_channel_t), dimension(:), allocatable :: channel
  class(rng_t), allocatable :: rng
  real(default), dimension(:,:), allocatable :: x
  integer :: u_grid, iostat, i, div, ch
  character(16) :: buffer

  write (u, "(A)")  "* Test output: mci_vamp_7"
  write (u, "(A)")  "* Purpose: check effect of channel equivalences"

  write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize integrator, sampler, instance"
write (u, "(A)")

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (1, 2)
select type (mci)
type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_3_t :: sampler)
select type (sampler)
type is (test_sampler_3_t)
    sampler%a = 0.7_default
    sampler%b = 0.3_default
end select
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 2 and n_calls = 1000, &
    &adapt grids"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
end select
call mci%integrate (mci_instance, sampler, 2, 1000)

call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write grids and extract binning"
write (u, "(A)")

u_grid = free_unit ()
open (u_grid, status = "scratch", action = "readwrite")
select type (mci_instance)
type is (mci_vamp_instance_t)
    call vamp_write_grids (mci_instance%grids, u_grid)
end select
rewind (u_grid)
allocate (x (0:20, 2))
do div = 1, 2
    FIND_BINS1: do

```

```

        read (u_grid, "(A)") buffer
        if (trim (adjustl (buffer)) == "begin d%x") then
            do
                read (u_grid, *, iostat = iostat) i, x(i,div)
                if (iostat /= 0) exit FIND_BINS1
            end do
        end if
    end do FIND_BINS1
end do
close (u_grid)

write (u, "(1x,A,L1)") "Equal binning in both channels = ", &
    all (x(:,1) == x(:,2))
deallocate (x)

write (u, "(A)")
write (u, "(A)") "* Cleanup"

call mci_instance%final ()
call mci%final ()
deallocate (mci_instance)
deallocate (mci)

write (u, "(A)")
write (u, "(A)") "* Re-initialize integrator, instance"
write (u, "(A)")

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (1, 2)
select type (mci)
type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .true.
    call mci%set_grid_parameters (grid_par)
end select

write (u, "(A)") "* Define equivalences"
write (u, "(A)")

allocate (channel (2))
do ch = 1, 2
    allocate (channel(ch)%eq (2))
    do i = 1, 2
        associate (eq => channel(ch)%eq(i))
            call eq%init (1)
            eq%c = i
            eq%perm = [1]
            eq%mode = [0]
        end associate
    end do
    write (u, "(1x,I0,':')", advance = "no") ch
    call channel(ch)%write (u)
end do
call mci%declare_equivalences (channel, dim_offset = 0)

```



```

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 2 and n_calls = 1000, &
    &adapt grids"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
end select
call mci%integrate (mci_instance, sampler, 2, 1000)

call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write grids and extract binning"
write (u, "(A)")

u_grid = free_unit ()
open (u_grid, status = "scratch", action = "readwrite")
select type (mci_instance)
type is (mci_vamp_instance_t)
    call vamp_write_grids (mci_instance%grids, u_grid)
end select
rewind (u_grid)
allocate (x (0:20, 2))
do div = 1, 2
    FIND_BINS2: do
        read (u_grid, "(A)") buffer
        if (trim (adjustl (buffer)) == "begin d%x") then
            do
                read (u_grid, *, iostat = iostat) i, x(i,div)
                if (iostat /= 0) exit FIND_BINS2
            end do
        end if
    end do FIND_BINS2
end do
close (u_grid)

write (u, "(1x,A,L1)") "Equal binning in both channels = ", &
    all (x(:,1) == x(:,2))
deallocate (x)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

```

```

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_7"

end subroutine mci_vamp_7

```

Multiple passes

Integrate with three passes and different settings for weight and grid adaptation.

```

<MCI vamp: execute tests>+≡
call test (mci_vamp_8, "mci_vamp_8", &
  "integration passes", &
  u, results)

<MCI vamp: tests>+≡
subroutine mci_vamp_8 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_vamp_8"
  write (u, "(A)")  "* Purpose: integrate function in one dimension &
    &(two channels)"
  write (u, "(A)")  "*           in three passes"

  write (u, "(A)")
  write (u, "(A)")  "* Initialize integrator, sampler, instance"
  write (u, "(A)")

  allocate (mci_vamp_t :: mci)
  call mci%set_dimensions (1, 2)
  select type (mci)
  type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
  end select

  allocate (rng_tao_t :: rng)
  call rng%init ()
  call mci%import_rng (rng)

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  allocate (test_sampler_3_t :: sampler)
  select type (sampler)
  type is (test_sampler_3_t)

```

```

        sampler%a = 0.9_default
        sampler%b = 0.1_default
    end select
    call sampler%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Integrate with grid and weight adaptation"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%add_pass (adapt_grids = .true., adapt_weights = .true.)
    end select
    call mci%integrate (mci_instance, sampler, 3, 1000)
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Contents of mci_instance:"
    write (u, "(A)")

    call mci_instance%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Integrate with grid adaptation"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%add_pass (adapt_grids = .true.)
    end select
    call mci%integrate (mci_instance, sampler, 3, 1000)
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Contents of mci_instance:"
    write (u, "(A)")

    call mci_instance%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Integrate without adaptation"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%add_pass ()
    end select
    call mci%integrate (mci_instance, sampler, 3, 1000)
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Contents of mci_instance:"
    write (u, "(A)")

```

```

call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_8"

end subroutine mci_vamp_8

```

Weighted events

Construct an integrator and use it for a two-dimensional sampler with two channels. Integrate and generate a weighted event.

```

<MCI vamp: execute tests>+≡
call test (mci_vamp_9, "mci_vamp_9", &
  "weighted event", &
  u, results)

<MCI vamp: tests>+≡
subroutine mci_vamp_9 (u)
integer, intent(in) :: u
type(grid_parameters_t) :: grid_par
class(mci_t), allocatable, target :: mci
class(mci_instance_t), pointer :: mci_instance => null ()
class(mci_sampler_t), allocatable :: sampler
class(rng_t), allocatable :: rng

write (u, "(A)")  "* Test output: mci_vamp_9"
write (u, "(A)")  "* Purpose: integrate function in two dimensions &
  &(two channels)"
write (u, "(A)")  "*           and generate a weighted event"

write (u, "(A)")
write (u, "(A)")  "* Initialize integrator, sampler, instance"
write (u, "(A)")

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (2, 2)
select type (mci)
type is (mci_vamp_t)
  grid_par%stratified = .false.
  grid_par%use_vamp_equivalences = .false.
  call mci%set_grid_parameters (grid_par)
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

```

```

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_2_t :: sampler)
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
write (u, "(A)")

call mci%add_pass ()
call mci%integrate (mci_instance, sampler, 1, 1000)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate a weighted event"
write (u, "(A)")

call mci_instance%init_simulation ()
call mci%generate_weighted_event (mci_instance, sampler)

write (u, "(1x,A)")  "MCI instance:"
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final_simulation ()
call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_9"

end subroutine mci_vamp_9

```

Grids I/O

Construct an integrator and allocate grids. Write grids to file, read them in again and compare.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_10, "mci_vamp_10", &
    "grids I/O", &
    u, results)

<MCI vamp: tests>+≡
  subroutine mci_vamp_10 (u)
    integer, intent(in) :: u
    type(grid_parameters_t) :: grid_par
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(rng_t), allocatable :: rng

```

```

type(string_t) :: file1, file2
character(80) :: buffer1, buffer2
integer :: u1, u2, iostat1, iostat2
logical :: equal, success

write (u, "(A)")  "* Test output: mci_vamp_10"
write (u, "(A)")  "* Purpose: write and read VAMP grids"

write (u, "(A)")
write (u, "(A)")  "* Initialize integrator, sampler, instance"
write (u, "(A)")

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (2, 2)
select type (mci)
type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

mci%md5sum = "1234567890abcdef1234567890abcdef"

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_2_t :: sampler)
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
write (u, "(A)")

call mci%add_pass ()
call mci%integrate (mci_instance, sampler, 1, 1000)

write (u, "(A)")  "* Write grids to file"
write (u, "(A)")

file1 = "mci_vamp_10.1"
select type (mci)
type is (mci_vamp_t)
    call mci%set_grid_filename (file1)
    call mci%write_grids (mci_instance)
end select

call mci_instance%final ()
call mci%final ()
deallocate (mci)

```

```

write (u, "(A)")  "* Read grids from file"
write (u, "(A)")

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (2, 2)
select type (mci)
type is (mci_vamp_t)
    call mci%set_grid_parameters (grid_par)
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

mci%md5sum = "1234567890abcdef1234567890abcdef"

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

select type (mci)
type is (mci_vamp_t)
    call mci%set_grid_filename (file1)
    call mci%add_pass ()
    call mci%current_pass%configure (1, 1000, &
        mci%min_calls, &
        mci%grid_par%min_bins, mci%grid_par%max_bins, &
        mci%grid_par%min_calls_per_channel * mci%n_channel)
    call mci%read_grids_header (success)
    call mci%compute_md5sum ()
    call mci%read_grids_data (mci_instance, read_integrals = .true.)
end select
write (u, "(1x,A,L1)")  "success = ", success

write (u, "(A)")
write (u, "(A)")  "* Write grids again"
write (u, "(A)")

file2 = "mci_vamp_10.2"
select type (mci)
type is (mci_vamp_t)
    call mci%set_grid_filename (file2)
    call mci%write_grids (mci_instance)
end select

u1 = free_unit ()
open (u1, file = char (file1) // ".vg", action = "read", status = "old")
u2 = free_unit ()
open (u2, file = char (file2) // ".vg", action = "read", status = "old")

equal = .true.
iostat1 = 0
iostat2 = 0
do while (equal .and. iostat1 == 0 .and. iostat2 == 0)
    read (u1, "(A)", iostat = iostat1)  buffer1

```

```

        read (u2, "(A)", iostat = iostat2) buffer2
        equal = buffer1 == buffer2 .and. iostat1 == iostat2
    end do
    close (u1)
    close (u2)

    if (equal) then
        write (u, "(1x,A)") "Success: grid files are identical"
    else
        write (u, "(1x,A)") "Failure: grid files differ"
    end if

    write (u, "(A)")
    write (u, "(A)") "* Cleanup"

    call mci_instance%final ()
    call mci%final ()

    write (u, "(A)")
    write (u, "(A)") "* Test output end: mci_vamp_10"

end subroutine mci_vamp_10

```

Weighted events

Construct an integrator and use it for a two-dimensional sampler with two channels. Integrate, write grids, and generate a weighted event using the grids from file.

```

<MCI vamp: execute tests>+≡
    call test (mci_vamp_11, "mci_vamp_11", &
        "weighted events with grid I/O", &
        u, results)

<MCI vamp: tests>+≡
    subroutine mci_vamp_11 (u)
        integer, intent(in) :: u
        type(grid_parameters_t) :: grid_par
        class(mci_t), allocatable, target :: mci
        class(mci_instance_t), pointer :: mci_instance => null ()
        class(mci_sampler_t), allocatable :: sampler
        class(rng_t), allocatable :: rng

        write (u, "(A)") "* Test output: mci_vamp_11"
        write (u, "(A)") "* Purpose: integrate function in two dimensions &
            &(two channels)"
        write (u, "(A)") "* and generate a weighted event"

        write (u, "(A)")
        write (u, "(A)") "* Initialize integrator, sampler, instance"
        write (u, "(A)")

        allocate (mci_vamp_t :: mci)
        call mci%set_dimensions (2, 2)

```



```

select type (mci)
type is (mci_vamp_t)
  grid_par%stratified = .false.
  grid_par%use_vamp_equivalences = .false.
  call mci%set_grid_parameters (grid_par)
  call mci%set_grid_filename (var_str ("mci_vamp_11"))
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_2_t :: sampler)

write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
write (u, "(A)")

call mci%add_pass ()
call mci%integrate (mci_instance, sampler, 1, 1000)

write (u, "(A)")  "* Reset instance"
write (u, "(A)")

call mci_instance%final ()
call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

write (u, "(A)")  "* Generate a weighted event"
write (u, "(A)")

call mci_instance%init_simulation ()
call mci%generate_weighted_event (mci_instance, sampler)

write (u, "(A)")  "* Cleanup"

call mci_instance%final_simulation ()
call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_11"

end subroutine mci_vamp_11

```

Weighted events

Construct an integrator and use it for a two-dimensional sampler with two channels. Integrate, write grids, and generate a weighted event using the grids from file.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_12, "mci_vamp_12", &
    "unweighted events with grid I/O", &
    u, results)

<MCI vamp: tests>+≡
  subroutine mci_vamp_12 (u)
    integer, intent(in) :: u
    type(grid_parameters_t) :: grid_par
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(rng_t), allocatable :: rng

    write (u, "(A)")  "* Test output: mci_vamp_12"
    write (u, "(A)")  "* Purpose: integrate function in two dimensions &
      &(two channels)"
    write (u, "(A)")  "* and generate an unweighted event"

    write (u, "(A)")
    write (u, "(A)")  "* Initialize integrator, sampler, instance"
    write (u, "(A)")

    allocate (mci_vamp_t :: mci)
    call mci%set_dimensions (2, 2)
    select type (mci)
    type is (mci_vamp_t)
      grid_par%stratified = .false.
      grid_par%use_vamp_equivalences = .false.
      call mci%set_grid_parameters (grid_par)
      call mci%set_grid_filename (var_str ("mci_vamp_12"))
    end select

    allocate (rng_tao_t :: rng)
    call rng%init ()
    call mci%import_rng (rng)

    call mci%allocate_instance (mci_instance)
    call mci_instance%init (mci)

    allocate (test_sampler_2_t :: sampler)

    write (u, "(A)")  "* Integrate with n_it = 3 and n_calls = 1000"
    write (u, "(A)")

    call mci%add_pass ()
    call mci%integrate (mci_instance, sampler, 1, 1000)

    write (u, "(A)")  "* Reset instance"
    write (u, "(A)")

    call mci_instance%final ()
    call mci%allocate_instance (mci_instance)
    call mci_instance%init (mci)

```

```

write (u, "(A)")  "* Generate an unweighted event"
write (u, "(A)")

call mci_instance%init_simulation ()
call mci%generate_unweighted_event (mci_instance, sampler)

write (u, "(1x,A)")  "MCI instance:"
call mci_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final_simulation ()
call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_12"

end subroutine mci_vamp_12

```

Update integration results

Compare two mci objects; match the two and update the first if successful.

```

<MCI vamp: execute tests>+≡
call test (mci_vamp_13, "mci_vamp_13", &
  "updating integration results", &
  u, results)

<MCI vamp: tests>+≡
subroutine mci_vamp_13 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci, mci_ref
  logical :: success

  write (u, "(A)")  "* Test output: mci_vamp_13"
  write (u, "(A)")  "* Purpose: match and update integrators"

  write (u, "(A)")
  write (u, "(A)")  "* Initialize integrator with no passes"
  write (u, "(A)")

  allocate (mci_vamp_t :: mci)
  call mci%set_dimensions (2, 2)
  select type (mci)
  type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
  end select
  call mci%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Initialize reference"
write (u, "(A)")

allocate (mci_vamp_t :: mci_ref)
call mci_ref%set_dimensions (2, 2)
select type (mci_ref)
type is (mci_vamp_t)
    call mci_ref%set_grid_parameters (grid_par)
end select

select type (mci_ref)
type is (mci_vamp_t)
    call mci_ref%add_pass (adapt_grids = .true.)
    call mci_ref%current_pass%configure (2, 1000, 0, 1, 5, 0)
    mci_ref%current_pass%calls = [77, 77]
    mci_ref%current_pass%integral = [1.23_default, 3.45_default]
    mci_ref%current_pass%error = [0.23_default, 0.45_default]
    mci_ref%current_pass%efficiency = [0.1_default, 0.6_default]
    mci_ref%current_pass%integral_defined = .true.

    call mci_ref%add_pass ()
    call mci_ref%current_pass%configure (2, 2000, 0, 1, 7, 0)
    mci_ref%current_pass%calls = [99, 0]
    mci_ref%current_pass%integral = [7.89_default, 0._default]
    mci_ref%current_pass%error = [0.89_default, 0._default]
    mci_ref%current_pass%efficiency = [0.86_default, 0._default]
    mci_ref%current_pass%integral_defined = .true.
end select

call mci_ref%write (u)

write (u, "(A)")
write (u, "(A)")  "* Update integrator (no-op, should succeed)"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%update_from_ref (mci_ref, success)
end select

write (u, "(1x,A,L1)")  "success = ", success
write (u, "(A)")
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Add pass to integrator"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
    call mci%current_pass%configure (2, 1000, 0, 1, 5, 0)
    mci%current_pass%calls = [77, 77]

```

```

        mci%current_pass%integral = [1.23_default, 3.45_default]
        mci%current_pass%error = [0.23_default, 0.45_default]
        mci%current_pass%efficiency = [0.1_default, 0.6_default]
        mci%current_pass%integral_defined = .true.
    end select

    write (u, "(A)")  "* Update integrator (no-op, should succeed)"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%update_from_ref (mci_ref, success)
    end select

    write (u, "(1x,A,L1)")  "success = ", success
    write (u, "(A)")
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Add pass to integrator, wrong parameters"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%add_pass ()
        call mci%current_pass%configure (2, 1000, 0, 1, 7, 0)
    end select

    write (u, "(A)")  "* Update integrator (should fail)"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%update_from_ref (mci_ref, success)
    end select

    write (u, "(1x,A,L1)")  "success = ", success
    write (u, "(A)")
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Reset and add passes to integrator"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%reset ()
        call mci%add_pass (adapt_grids = .true.)
        call mci%current_pass%configure (2, 1000, 0, 1, 5, 0)
        mci%current_pass%calls = [77, 77]
        mci%current_pass%integral = [1.23_default, 3.45_default]
        mci%current_pass%error = [0.23_default, 0.45_default]
        mci%current_pass%efficiency = [0.1_default, 0.6_default]
        mci%current_pass%integral_defined = .true.
    end select

```

```

        call mci%add_pass ()
        call mci%current_pass%configure (2, 2000, 0, 1, 7, 0)
    end select

    write (u, "(A)")  "* Update integrator (should succeed)"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%update_from_ref (mci_ref, success)
    end select

    write (u, "(1x,A,L1)")  "success = ", success
    write (u, "(A)")
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Update again (no-op, should succeed)"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%update_from_ref (mci_ref, success)
    end select

    write (u, "(1x,A,L1)")  "success = ", success
    write (u, "(A)")
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Add extra result to integrator"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        mci%current_pass%calls(2) = 1234
    end select

    write (u, "(A)")  "* Update integrator (should fail)"
    write (u, "(A)")

    select type (mci)
    type is (mci_vamp_t)
        call mci%update_from_ref (mci_ref, success)
    end select

    write (u, "(1x,A,L1)")  "success = ", success
    write (u, "(A)")
    call mci%write (u)

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

```

```

call mci%final ()
call mci_ref%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_13"

end subroutine mci_vamp_13

```

Accuracy Goal

Integrate with multiple iterations. Skip iterations once an accuracy goal has been reached.

```

<MCI vamp: execute tests>+≡
call test (mci_vamp_14, "mci_vamp_14", &
  "accuracy goal", &
  u, results)

<MCI vamp: tests>+≡
subroutine mci_vamp_14 (u)
  integer, intent(in) :: u
  type(grid_parameters_t) :: grid_par
  class(mci_t), allocatable, target :: mci
  class(mci_instance_t), pointer :: mci_instance => null ()
  class(mci_sampler_t), allocatable :: sampler
  class(rng_t), allocatable :: rng

  write (u, "(A)")  "* Test output: mci_vamp_14"
  write (u, "(A)")  "* Purpose: integrate function in one dimension &
    &(single channel)"
  write (u, "(A)")  "*           and check accuracy goal"

  write (u, "(A)")
  write (u, "(A)")  "* Initialize integrator, sampler, instance"
  write (u, "(A)")

  allocate (mci_vamp_t :: mci)
  call mci%set_dimensions (1, 1)
  select type (mci)
  type is (mci_vamp_t)
    grid_par%use_vamp_equivalences = .false.
    grid_par%accuracy_goal = 5E-2_default
    call mci%set_grid_parameters (grid_par)
  end select

  allocate (rng_tao_t :: rng)
  call rng%init ()
  call mci%import_rng (rng)

  call mci%allocate_instance (mci_instance)
  call mci_instance%init (mci)

  allocate (test_sampler_1_t :: sampler)
  select type (sampler)

```

```

type is (test_sampler_1_t)
  sampler%mode = 2
end select
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Integrate with n_it = 5 and n_calls = 100"
write (u, "(A)")

select type (mci)
type is (mci_vamp_t)
  call mci%add_pass (adapt_grids = .true.)
end select
call mci%integrate (mci_instance, sampler, 5, 100)
call mci%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_14"

end subroutine mci_vamp_14

```

VAMP history

Integrate with three passes and different settings for weight and grid adaptation.
Then show the VAMP history.

```

<MCI vamp: execute tests>+≡
  call test (mci_vamp_15, "mci_vamp_15", &
    "VAMP history", &
    u, results)

<MCI vamp: tests>+≡
  subroutine mci_vamp_15 (u)
    integer, intent(in) :: u
    type(grid_parameters_t) :: grid_par
    type(history_parameters_t) :: history_par
    class(mci_t), allocatable, target :: mci
    class(mci_instance_t), pointer :: mci_instance => null ()
    class(mci_sampler_t), allocatable :: sampler
    class(rng_t), allocatable :: rng

    write (u, "(A)")  "* Test output: mci_vamp_15"
    write (u, "(A)")  "* Purpose: integrate function in one dimension &
      &(two channels)"
    write (u, "(A)")  "*           in three passes, show history"

    write (u, "(A)")
    write (u, "(A)")  "* Initialize integrator, sampler, instance"

```



```

write (u, "(A)")

history_par%channel = .true.

allocate (mci_vamp_t :: mci)
call mci%set_dimensions (1, 2)
select type (mci)
type is (mci_vamp_t)
    grid_par%stratified = .false.
    grid_par%use_vamp_equivalences = .false.
    call mci%set_grid_parameters (grid_par)
    call mci%set_history_parameters (history_par)
end select

allocate (rng_tao_t :: rng)
call rng%init ()
call mci%import_rng (rng)

call mci%allocate_instance (mci_instance)
call mci_instance%init (mci)

allocate (test_sampler_3_t :: sampler)
select type (sampler)
type is (test_sampler_3_t)
    sampler%a = 0.9_default
    sampler%b = 0.1_default
end select
call sampler%write (u)

write (u, "(A)")
write (u, "(A)")  "* Pass 1: grid and weight adaptation"

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true., adapt_weights = .true.)
end select
call mci%integrate (mci_instance, sampler, 3, 1000)

write (u, "(A)")
write (u, "(A)")  "* Pass 2: grid adaptation"

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass (adapt_grids = .true.)
end select
call mci%integrate (mci_instance, sampler, 3, 1000)

write (u, "(A)")
write (u, "(A)")  "* Pass 3: without adaptation"

select type (mci)
type is (mci_vamp_t)
    call mci%add_pass ()
end select

```

```

call mci%integrate (mci_instance, sampler, 3, 1000)

write (u, "(A)")
write (u, "(A)")  "* Contents of MCI record, with history"
write (u, "(A)")

call mci%write (u)
select type (mci)
type is (mci_vamp_t)
    call mci%write_history (u)
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call mci_instance%final ()
call mci%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: mci_vamp_15"

end subroutine mci_vamp_15

```

Chapter 20

Parton shower and interface to PYTHIA6

This is the code for the WHIZARD QCD parton shower for final state radiation (FSR) and initial state radiation (ISR) as well as the interface to the PYTHIA module for showering and hadronization.

20.1 Basics of the shower

```
<shower_base.f90>≡  
  <File header>  
  
  module shower_base  
  
    <Use kinds with double>  
    <Use strings>  
    use io_units  
    use constants  
    use diagnostics  
    use format_utils, only: write_separator  
    use os_interface  
    use rng_base  
    use physics_defs  
    use lhpdf !NODEP!  
    use pdf_builtin !NODEP!  
    use sm_physics, only: running_as_lam  
    use particles  
    use variables  
    use model_data  
  
    <Standard module head>  
  
    <Shower base: parameters>  
  
    <Shower base: public>  
  
    <Shower base: types>
```

⟨Shower base: interfaces⟩

contains

⟨Shower base: procedures⟩

end module shower_base

20.1.1 Shower implementations

⟨Shower base: public⟩≡

public :: PS_WHIZARD, PS_PYTHIA6, PS_PYTHIA8, PS_UNDEFINED

⟨Shower base: parameters⟩≡

integer, parameter :: PS_WHIZARD = 1
integer, parameter :: PS_PYTHIA6 = 2
integer, parameter :: PS_PYTHIA8 = 3
integer, parameter :: PS_UNDEFINED = 17

A dictionary

⟨Shower base: public⟩+≡

public :: shower_method_of_string

⟨Shower base: procedures⟩≡

elemental function shower_method_of_string (string) result (i)
integer :: i
type(string_t), intent(in) :: string
select case (char(string))
case ("WHIZARD")
i = PS_WHIZARD
case ("PYTHIA6")
i = PS_PYTHIA6
case ("PYTHIA8")
i = PS_PYTHIA8
case default
i = PS_UNDEFINED
end select
end function shower_method_of_string

⟨Shower base: public⟩+≡

public :: shower_method_to_string

⟨Shower base: procedures⟩+≡

elemental function shower_method_to_string (i) result (string)
type(string_t) :: string
integer, intent(in) :: i
select case (i)
case (PS_WHIZARD)
string = "WHIZARD"
case (PS_PYTHIA6)
string = "PYTHIA6"
case (PS_PYTHIA8)
string = "PYTHIA8"
case default

```

        string = "UNDEFINED"
    end select
end function shower_method_to_string

```

20.1.2 PDF Parameters

The shower has to know about the PDF set used for the parent process, if any. We support the following:

```

⟨Shower base: parameters⟩+≡
    integer, parameter, public :: STRF_NONE = 0
    integer, parameter, public :: STRF_LHAPDF6 = 1
    integer, parameter, public :: STRF_LHAPDF5 = 2
    integer, parameter, public :: STRF_PDF_BUILTIN = 3

```

A container to bundle all necessary PDF data. Could be moved to a more central location.

```

⟨Shower base: public⟩+≡
    public :: pdf_data_t

⟨Shower base: types⟩≡
    type :: pdf_data_t
        type(lhapdf_pdf_t) :: pdf
        real(default) :: xmin, xmax, qmin, qmax
        integer :: type = STRF_NONE
        integer :: set = 0
    contains
        ⟨Shower base: pdf data: TBP⟩
    end type pdf_data_t

```

```

⟨Shower base: pdf data: TBP⟩≡
    procedure :: init => pdf_data_init

```

```

⟨Shower base: procedures⟩+≡
    subroutine pdf_data_init (pdf_data, pdf_data_in)
        class(pdf_data_t), intent(out) :: pdf_data
        type(pdf_data_t), target, intent(in) :: pdf_data_in
        pdf_data%xmin = pdf_data_in%xmin
        pdf_data%xmax = pdf_data_in%xmax
        pdf_data%qmin = pdf_data_in%qmin
        pdf_data%qmax = pdf_data_in%qmax
        pdf_data%set = pdf_data_in%set
        pdf_data%type = pdf_data_in%type
        if (pdf_data%type == STRF_LHAPDF6) then
            if (pdf_data_in%pdf%is_associated ()) then
                call lhpdf_copy_pointer (pdf_data_in%pdf, pdf_data%pdf)
            else
                call msg_bug ('pdf_data_init: pdf_data%pdf was not associated!')
            end if
        end if
    end subroutine pdf_data_init

```

```

<Shower base: pdf data: TBP>+=
  procedure :: write => pdf_data_write

<Shower base: procedures>+=
  subroutine pdf_data_write (pdf_data, unit)
    class(pdf_data_t), intent(in) :: pdf_data
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(3x,A,I0)") "PDF set = ", pdf_data%set
    write (u, "(3x,A,I0)") "PDF type = ", pdf_data%type
  end subroutine pdf_data_write

```

This could be overloaded with a version that only asks for a specific flavor as it is supported by LHAPDF6.

```

<Shower base: pdf data: TBP>+=
  procedure :: evolve => pdf_data_evolve

<Shower base: procedures>+=
  subroutine pdf_data_evolve (pdf_data, x, q_in, f)
    class(pdf_data_t), intent(inout) :: pdf_data
    real(double), intent(in) :: x, q_in
    real(double), dimension(-6:6), intent(out) :: f
    real(double) :: q
    select case (pdf_data%type)
    case (STRF_PDF_BUILTIN)
      call pdf_evolve_LHAPDF (pdf_data%set, x, q_in, f)
    case (STRF_LHAPDF6)
      q = min (pdf_data%qmax, q_in)
      q = max (pdf_data%qmin, q)
      call pdf_data%pdf%evolve_pdfm (x, q, f)
    case (STRF_LHAPDF5)
      q = min (pdf_data%qmax, q_in)
      q = max (pdf_data%qmin, q)
      call evolvePDFM (pdf_data%set, x, q, f)
    case default
      call msg_fatal ("PDF function: unknown PDF method.")
    end select
  end subroutine pdf_data_evolve

```

20.1.3 Shower settings

These the general shower settings, the settings and parameters for the matching are defined in the corresponding matching modules. The width and the cutoff of the Gaussian primordial k_t distribution, PARP(91) and PARP(93), in GeV, are called `isr_primordial_kt_width` and `isr_primordial_kt_cutoff` in WHIZARD. The parameter MSTJ(45) gives the maximum number of flavors in gluon decay to quarks, and is here called `max_n_flavors`.

The two parameters `isr_alpha_s_running` and `[[fsr_alpha_s_running` decide whether to use constant or running α_s in the form of the function $D_{\alpha_s}(t)$ for the FSR and ISR (MSTJ(44), MSTP(64)), respectively. The next

parameter, `fixed_alpha_s` is the parameter `PARU(111)`, which sets the value for constant α_s , and the flag whether to use P_t -ordered ISR is `isr_pt_ordered`.

```

(Shower base: public)+≡
    public :: shower_settings_t

(Shower base: types)+≡
    type :: shower_settings_t
        logical :: active = .false.
        logical :: isr_active = .false.
        logical :: fsr_active = .false.
        logical :: multi_active = .false.
        logical :: verbose = .false.
        integer :: method = PS_UNDEFINED
        logical :: hadronization_active = .false.
        logical :: mlm_matching = .false.
        logical :: ckkw_matching = .false.
        logical :: powheg_matching = .false.
        type(string_t) :: pythia6_pygive
        !!! values present in PYTHIA and WHIZARDS PS,
        !!! comments denote corresponding PYTHIA values
        real(default) :: d_min_t = 1._default          ! PARJ(82)^2
        real(default) :: fsr_lambda = 0.29_default     ! PARP(72)
        real(default) :: isr_lambda = 0.29_default     ! PARP(61)
        integer :: max_n_flavors = 5                  ! MSTJ(45)
        logical :: isr_alpha_s_running = .true.        ! MSTP(64)
        logical :: fsr_alpha_s_running = .true.        ! MSTJ(44)
        real(default) :: fixed_alpha_s = 0.2_default  ! PARU(111)
        logical :: alpha_s_fudged = .true.
        logical :: isr_pt_ordered = .false.
        logical :: isr_angular_ordered = .true.        ! MSTP(62)
        real(default) :: isr_primordial_kt_width = 1.5_default ! PARP(91)
        real(default) :: isr_primordial_kt_cutoff = 5._default ! PARP(93)
        real(default) :: isr_z_cutoff = 0.999_default ! 1-PARP(66)
        real(default) :: isr_minenergy = 2._default   ! PARP(65)
        real(default) :: isr_tscalefactor = 1._default
        logical :: isr_only_onshell_emitted_partons = .true. ! MSTP(63)
contains
    (Shower base: shower settings: TBP)
end type shower_settings_t

```

Read in the shower settings (and flags whether matching and hadronization are switched on).

```

(Shower base: shower settings: TBP)≡
    procedure :: init => shower_settings_init

(Shower base: procedures)+≡
    subroutine shower_settings_init (shower_settings, var_list)
        class(shower_settings_t), intent(out) :: shower_settings
        type(var_list_t), intent(in) :: var_list

        shower_settings%fsr_active = &
            var_list%get_lval (var_str ("?ps_fsr_active"))
        shower_settings%isr_active = &
            var_list%get_lval (var_str ("?ps_isr_active"))
    end subroutine shower_settings_init

```

```

shower_settings%multi_active = &
    var_list%get_lval (var_str ("?multi_active"))
shower_settings%hadronization_active = &
    var_list%get_lval (var_str ("?hadronization_active"))
shower_settings%mlm_matching = &
    var_list%get_lval (var_str ("?mlm_matching"))
shower_settings%ckkw_matching = &
    var_list%get_lval (var_str ("?ckkw_matching"))
shower_settings%powheg_matching = &
    var_list%get_lval (var_str ("?powheg_matching"))

shower_settings%method = shower_method_of_string ( &
    var_list%get_sval (var_str ("$shower_method")))

!!! We have to split off hadronization settings at some point.

shower_settings%active = shower_settings%isr_active .or. &
    shower_settings%fsr_active .or. &
    shower_settings%powheg_matching .or. &
    shower_settings%multi_active .or. &
    shower_settings%hadronization_active
if (.not. shower_settings%active) return
shower_settings%verbose = &
    var_list%get_lval (var_str ("?shower_verbose"))
shower_settings%pythia6_pygive = &
    var_list%get_sval (var_str ("ps_PYTHIA_PYGIVE"))
shower_settings%d_min_t = &
    (var_list%get_rval (var_str ("ps_mass_cutoff"))**2)
shower_settings%fsr_lambda = &
    var_list%get_rval (var_str ("ps_fsr_lambda"))
shower_settings%isr_lambda = &
    var_list%get_rval (var_str ("ps_isr_lambda"))
shower_settings%max_n_flavors = &
    var_list%get_ival (var_str ("ps_max_n_flavors"))
shower_settings%isr_alpha_s_running = &
    var_list%get_lval (var_str ("?ps_isr_alpha_s_running"))
shower_settings%fsr_alpha_s_running = &
    var_list%get_lval (var_str ("?ps_fsr_alpha_s_running"))
shower_settings%fixed_alpha_s = &
    var_list%get_rval (var_str ("ps_fixed_alpha_s"))
shower_settings%isr_pt_ordered = &
    var_list%get_lval (var_str ("?ps_isr_pt_ordered"))
shower_settings%isr_angular_ordered = &
    var_list%get_lval (var_str ("?ps_isr_angular_ordered"))
shower_settings%isr_primordial_kt_width = &
    var_list%get_rval (var_str ("ps_isr_primordial_kt_width"))
shower_settings%isr_primordial_kt_cutoff = &
    var_list%get_rval (var_str ("ps_isr_primordial_kt_cutoff"))
shower_settings%isr_z_cutoff = &
    var_list%get_rval (var_str ("ps_isr_z_cutoff"))
shower_settings%isr_minenergy = &
    var_list%get_rval (var_str ("ps_isr_minenergy"))
shower_settings%isr_tscalefactor = &
    var_list%get_rval (var_str ("ps_isr_tscalefactor"))

```



```

shower_settings%isr_only_onshell_emitted_partons = &
    var_list%get_lval (&
        var_str ("?ps_isr_only_onshell_emitted_partons"))
end subroutine shower_settings_init

```

<Shower base: shower settings: TBP>+≡

```

procedure :: write => shower_settings_write

```

<Shower base: procedures>+≡

```

subroutine shower_settings_write (settings, unit)
    class(shower_settings_t), intent(in) :: settings
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(1x,A)") "Shower settings:"
    call write_separator (u)
    write (u, "(1x,A)") "Master switches:"
    write (u, "(3x,A,1x,L1)") &
        "ps_isr_active                = ", settings%isr_active
    write (u, "(3x,A,1x,L1)") &
        "ps_fsr_active                = ", settings%fsr_active
    write (u, "(1x,A)") "General settings:"
    if (settings%isr_active .or. settings%fsr_active) then
        write (u, "(3x,A)") &
            "shower_method                = " // &
            char (shower_method_to_string (settings%method))
        write (u, "(3x,A,1x,L1)") &
            "shower_verbose                = ", settings%verbose
        write (u, "(3x,A,ES19.12)") &
            "ps_mass_cutoff                = ", sqrt (abs (settings%d_min_t))
        write (u, "(3x,A,1x,I1)") &
            "ps_max_n_flavors                = ", settings%max_n_flavors
    else
        write (u, "(3x,A)") " [ISR and FSR off]"
    end if
    if (settings%isr_active) then
        write (u, "(1x,A)") "ISR settings:"
        write (u, "(3x,A,1x,L1)") &
            "ps_isr_pt_ordered                = ", settings%isr_pt_ordered
        write (u, "(3x,A,ES19.12)") &
            "ps_isr_lambda                = ", settings%isr_lambda
        write (u, "(3x,A,1x,L1)") &
            "ps_isr_alpha_s_running            = ", settings%isr_alpha_s_running
        write (u, "(3x,A,ES19.12)") &
            "ps_isr_primordial_kt_width        = ", settings%isr_primordial_kt_width
        write (u, "(3x,A,ES19.12)") &
            "ps_isr_primordial_kt_cutoff        = ", &
            settings%isr_primordial_kt_cutoff
        write (u, "(3x,A,ES19.12)") &
            "ps_isr_z_cutoff                = ", settings%isr_z_cutoff
        write (u, "(3x,A,ES19.12)") &
            "ps_isr_minenergy                = ", settings%isr_minenergy
        write (u, "(3x,A,ES19.12)") &
            "ps_isr_tscalefactor                = ", settings%isr_tscalefactor
    end if
end subroutine shower_settings_write

```

```

else if (settings%fsr_active) then
  write (u, "(3x,A)" " [ISR off]"
end if
if (settings%fsr_active) then
  write (u, "(1x,A)" "FSR settings:"
  write (u, "(3x,A,ES19.12)" &
    "ps_fsr_lambda           = ", settings%fsr_lambda
  write (u, "(3x,A,1x,L1)" &
    "ps_fsr_alpha_s_running  = ", settings%fsr_alpha_s_running
else if (settings%isr_active) then
  write (u, "(3x,A)" " [FSR off]"
end if
write (u, "(1x,A)" "Hadronization settings:"
write (u, "(3x,A,1x,L1)" &
  "hadronization_active      = ", settings%hadronization_active
write (u, "(1x,A)" "Matching Settings:"
write (u, "(3x,A,1x,L1)" &
  "mlm_matching              = ", settings%mlm_matching
write (u, "(3x,A,1x,L1)" &
  "ckkw_matching             = ", settings%ckkw_matching
write (u, "(1x,A)" "PYTHIA6 specific settings:"
write (u, "(3x,A,A,A)" &
  "ps_PYTHIA_PYGIVE          = '", &
  char(settings%pythia6_pygive), "'"
end subroutine shower_settings_write

```

20.1.4 Abstract matching settings and data types

```

<Shower base: public>+≡
  public :: matching_settings_t

<Shower base: types>+≡
  type, abstract :: matching_settings_t
  contains
  <Shower base: matching settings: TBP>
  end type matching_settings_t

<Shower base: matching settings: TBP>≡
  procedure (matching_settings_init), deferred :: init

<Shower base: interfaces>≡
  abstract interface
    subroutine matching_settings_init (settings, var_list)
      import
      class(matching_settings_t), intent(out) :: settings
      type(var_list_t), intent(in) :: var_list
    end subroutine matching_settings_init
  end interface

<Shower base: matching settings: TBP>+≡
  procedure (matching_settings_write), deferred :: write

```

```

<Shower base: interfaces>+≡
  abstract interface
    subroutine matching_settings_write (settings, unit)
      import
        class(matching_settings_t), intent(in) :: settings
        integer, intent(in), optional :: unit
    end subroutine matching_settings_write
  end interface

```

```

<Shower base: public>+≡
  public :: matching_data_t

```

```

<Shower base: types>+≡
  type, abstract :: matching_data_t
    logical :: is_hadron_collision = .false.
  end type matching_data_t

```

20.1.5 Abstract Shower Type

Any parton shower implementation will use random numbers to generate emissions.

```

<Shower base: public>+≡
  public :: shower_base_t

```

```

<Shower base: types>+≡
  type, abstract :: shower_base_t
    class(rng_t), allocatable :: rng
    type(string_t) :: name
    type(pdf_data_t) :: pdf_data
    type(shower_settings_t) :: settings
  contains
    <Shower base: shower base: TBP>
  end type shower_base_t

```

```

<Shower base: shower base: TBP>≡
  procedure :: write_msg => shower_base_write_msg

```

```

<Shower base: procedures>+≡
  subroutine shower_base_write_msg (shower)
    class(shower_base_t), intent(inout) :: shower
    call msg_message ("Shower: Using " // char(shower%name) // " shower")
  end subroutine shower_base_write_msg

```

```

<Shower base: shower base: TBP>+≡
  procedure :: import_rng => shower_base_import_rng

```

```

<Shower base: procedures>+≡
  pure subroutine shower_base_import_rng (shower, rng)
    class(shower_base_t), intent(inout) :: shower
    class(rng_t), intent(inout), allocatable :: rng
    call move_alloc (from = rng, to = shower%rng)
  end subroutine shower_base_import_rng

```

Shower implementations need to know the overall settings as well as `pdf_data_t` if ISR needs to be simulated.

```

<Shower base: shower base: TBP>+≡
    procedure (shower_base_init), deferred :: init

<Shower base: interfaces>+≡
    abstract interface
        subroutine shower_base_init (shower, settings, pdf_data)
            import
            class(shower_base_t), intent(out) :: shower
            type(shower_settings_t), intent(in) :: settings
            type(pdf_data_t), intent(in) :: pdf_data
        end subroutine shower_base_init
    end interface

<Shower base: shower base: TBP>+≡
    procedure (shower_base_generate_emissions), deferred :: generate_emissions

<Shower base: interfaces>+≡
    abstract interface
        subroutine shower_base_generate_emissions (shower, particle_set, &
            model, model_hadrons, os_data, matching_settings, data, &
            valid, vetoed, number_of_emissions)
            import
            class(shower_base_t), intent(inout), target :: shower
            type(particle_set_t), intent(inout) :: particle_set
            class(model_data_t), intent(in), target :: model
            class(model_data_t), intent(in), target :: model_hadrons
            class(matching_settings_t), intent(in), allocatable :: matching_settings
            class(matching_data_t), intent(inout), allocatable :: data
            type(os_data_t), intent(in) :: os_data
            logical, intent(inout) :: valid
            logical, intent(inout) :: vetoed
            integer, optional, intent(in) :: number_of_emissions
        end subroutine shower_base_generate_emissions
    end interface

```

20.1.6 Additional parameters

`DEBUG_WHIZ_SHOWER` decides whether to print out additional information while `ENSURE` does additional sanity checks that should be disabled for production.

```

<Shower base: parameters>+≡
    logical, parameter, public :: DEBUG_WHIZ_SHOWER = .true.
    logical, parameter, public :: ENSURE = .true.
    logical, parameter, public :: DEBUG_SHOWER = .true.

```

These parameters are the cut-off scale t_{cut} , given in GeV^2 (`PARJ(82)`), the cut-off scale for the P_t^2 -ordered shower in GeV^2 , and the two shower parameters `PARP(72)` and `PARP(61)`, respectively.

```

<Shower base: parameters>+≡
    real(default), public :: D_min_scale = 0.5_default

```

Treating either u and d , or all quarks except t as massless:

```
<Shower base: parameters>+≡
    logical, public :: treat_light_quarks_massless = .true.
    logical, public :: treat_duscb_quarks_massless = .false.
```

Temporary parameters for the P_t -ordered shower:

```
<Shower base: parameters>+≡
    real(default), public :: scalefactor1 = 0.02_default
    real(default), public :: scalefactor2 = 0.02_default

<Shower base: public>+≡
    public :: D_alpha_s_isr
    public :: D_alpha_s_fsr

<Shower base: procedures>+≡
    function D_alpha_s_isr (tin, settings) result (alpha_s)
        real(default), intent(in) :: tin
        type(shower_settings_t), intent(in) :: settings
        real(default) :: d_min_t, d_constalpha_s, d_lambda_isr
        integer :: d_nf
        real(default) :: t
        real(default) :: alpha_s
        d_min_t = settings%d_min_t
        d_lambda_isr = settings%isr_lambda
        d_constalpha_s = settings%fixed_alpha_s
        d_nf = settings%max_n_flavors
        if (settings%alpha_s_fudged) then
            t = max (max (0.1_default * d_min_t, &
                          1.1_default * d_lambda_isr**2), abs(tin))
        else
            t = abs(tin)
        end if
        if (settings%isr_alpha_s_running) then
            alpha_s = running_as_lam (number_of_flavors(t, d_nf, d_min_t), &
                                      sqrt(t), d_lambda_isr, 0)
        else
            alpha_s = d_constalpha_s
        end if
    end function D_alpha_s_isr

    function D_alpha_s_fsr (tin, settings) result (alpha_s)
        real(default), intent(in) :: tin
        type(shower_settings_t), intent(in) :: settings
        real(default) :: d_min_t, d_lambda_fsr, d_constalpha_s
        integer :: d_nf
        real(default) :: t
        real(default) :: alpha_s
        d_min_t = settings%d_min_t
        d_lambda_fsr = settings%fsr_lambda
        d_constalpha_s = settings%fixed_alpha_s
        d_nf = settings%max_n_flavors
        if (settings%alpha_s_fudged) then
            t = max (max (0.1_default * d_min_t, &
                          1.1_default * d_lambda_fsr**2), abs(tin))
        else
```

```

        t = abs(tin)
    end if
    if (settings%fsr_alpha_s_running) then
        alpha_s = running_as_lam (number_of_flavors (t, d_nf, d_min_t), &
            sqrt(t), d_lambda_fsr, 0)
    else
        alpha_s = d_constalpha_s
    end if
end function D_alpha_s_fsr

```

Mass and mass squared selection functions. All masses are in GeV. Light quarks are assumed to be ordered, $m_1 < m_2 < m_3 \dots$, and they get current masses, not elementary ones. Mesons and baryons other than proton and neutron are needed as beam-remnants. Particles with PDG number zero are taken massless, as well as proper beam remnants and any other particles.

```

(Shower base: public)+≡
    public :: mass_type
    public :: mass_squared_type

(Shower base: procedures)+≡
    elemental function mass_type (type) result (mass)
        integer, intent(in) :: type
        real(default) :: mass
        mass = sqrt (mass_squared_type (type))
    end function mass_type

    elemental function mass_squared_type (type) result (mass2)
        integer, intent(in) :: type
        real(default) :: mass2

        select case (abs (type))
        case (1,2)
            if (treat_light_quarks_massless .or. &
                treat_duscb_quarks_massless) then
                mass2 = zero
            else
                mass2 = 0.330_default**2
            end if
        case (3)
            if (treat_duscb_quarks_massless) then
                mass2 = zero
            else
                mass2 = 0.500_default**2
            end if
        case (4)
            if (treat_duscb_quarks_massless) then
                mass2 = zero
            else
                mass2 = 1.500_default**2
            end if
        case (5)
            if (treat_duscb_quarks_massless) then
                mass2 = zero
            else

```

```

        mass2 = 4.800_default**2
    end if
case (6)
    mass2 = 175.00_default**2
case (GLUON)
    mass2 = zero
case (NEUTRON)
    mass2 = 0.939565_default**2
case (PROTON)
    mass2 = 0.93827_default**2
case (DPLUS)
    mass2 = 1.86960_default**2
case (D0)
    mass2 = 1.86483_default**2
case (B0)
    mass2 = 5.27950_default**2
case (BPLUS)
    mass2 = 5.27917_default**2
case (DELTAPLUSPLUS)
    mass2 = 1.232_default**2
case (SIGMA0)
    mass2 = 1.192642_default**2
case (SIGMAPLUS)
    mass2 = 1.18937_default**2
case (SIGMACPLUS)
    mass2 = 2.4529_default**2
case (SIGMACPLUSPLUS)
    mass2 = 2.45402_default**2
case (SIGMAB0)
    mass2 = 5.8152_default**2
case (SIGMABPLUS)
    mass2 = 5.8078_default**2
case (UNDEFINED)
    mass2 = zero
case (BEAM_REMNANT)
    mass2 = zero !!! don't know how to handle the beamremnant
case default
    mass2 = zero
end select
end function mass_squared_type

```

The number of flavors active at a certain scale (virtuality) t .

```

<Shower base: public>+≡
    public :: number_of_flavors

<Shower base: procedures>+≡
    elemental function number_of_flavors (t, d_nf, d_min_t) result (nr)
        real(default), intent(in) :: t, d_min_t
        integer, intent(in) :: d_nf
        real(default) :: nr
        integer :: i
        nr = 0
        if (t < d_min_t) return    ! arbitrary cut off
        ! TODO: do i = 1, min (max (3, d_nf), 6)

```

```

do i = 1, min (3, d_nf)
!!! to do: take heavier quarks(-> cuts on allowed costheta in g->qq)
!!!      into account
      if ((four * mass_squared_type (i) + d_min_t) < t ) then
        nr = i
      else
        exit
      end if
    end do
end function number_of_flavors

```

20.2 Parton module for the shower

```

<shower_partons.f90>≡
  <File header>

  module shower_partons

    <Use kinds>
    use io_units
    use constants
    use system_defs, only: TAB
    use diagnostics
    use physics_defs
    use lorentz
    use sm_physics
    use particles
    use flavors
    use colors
    use subevents
    use model_data
    use shower_base
    use rng_base

    <Standard module head>

    <Shower partons: public>

    <Shower partons: types>

    contains

    <Shower partons: procedures>

  end module shower_partons

```

20.2.1 The basic type defintions

The type `parton_t` defines a parton for the shower. The `x` value of the parton is only needed for spacelike showers. The pointer `initial` is only needed for partons in initial showers, it points to the hadron the parton is coming from.

An auxiliary value for the P_t -ordered ISR is `aux_pt`. Then, there are two auxiliary entries for the clustering of CKKW pseudo weights and CKKW matching, `ckkwlabel` and `ckkwscale`. In order to make shower settings available to all operations on the shower partons, we endow the `parton_t` type with a pointer to `shower_settings_t`.

```

<Shower partons: public>≡
    public :: parton_t

<Shower partons: types>≡
    type :: parton_t
        integer :: nr = 0
        integer :: type = 0
        type(shower_settings_t), pointer :: settings => null()
        type(vector4_t) :: momentum = vector4_null
        real(default) :: t = zero
        real(default) :: scale = zero
        real(default) :: z = zero
        real(default) :: costheta = zero
        real(default) :: x = zero
        logical :: simulated = .false.
        logical :: belongstoFSR = .true.
        logical :: belongstointeraction = .false.
        type(parton_t), pointer :: parent => null ()
        type(parton_t), pointer :: child1 => null ()
        type(parton_t), pointer :: child2 => null ()
        type(parton_t), pointer :: initial => null ()
        integer :: c1 = 0, c2 = 0
        integer :: aux_pt = 0
        integer :: ckkwlabel = 0
        real(default) :: ckkwscale = zero
        integer :: ckkwtype = -1
        integer :: interactionnr = 0
    contains
        <Shower partons: parton: TBP>
    end type parton_t

```

```

<Shower partons: public>+≡
    public :: parton_pointer_t

<Shower partons: types>+≡
    type :: parton_pointer_t
        type(parton_t), pointer :: p => null ()
    end type parton_pointer_t

```

20.2.2 Routines

```

<Shower partons: parton: TBP>≡
    procedure :: to_particle => parton_to_particle

<Shower partons: procedures>≡
    function parton_to_particle (parton, model, from_hard_int) result (particle)
        type(particle_t) :: particle
        class(parton_t), intent(in) :: parton

```

```

class(model_data_t), pointer, intent(in) :: model
logical, intent(in), optional :: from_hard_int
integer :: col, anti_col
call parton%to_color (col, anti_col, from_hard_int)
call particle%init (parton%to_status (from_hard_int), parton%type, &
    model, col, anti_col, parton%momentum)
end function parton_to_particle

```

<Shower partons: parton: TBP>+≡

```

procedure :: to_status => parton_to_status

```

<Shower partons: procedures>+≡

```

pure function parton_to_status (parton, from_hard_int) result (status)
integer :: status
class(parton_t), intent(in) :: parton
logical, intent(in), optional :: from_hard_int
logical :: fhi
fhi = .false.; if (present (from_hard_int)) fhi = from_hard_int
if (fhi .or. parton%is_colored ()) then
    if (associated (parton%initial) .and. .not. parton%belongstoFSR) then
        status = PRT_INCOMING
    else
        status = PRT_OUTGOING
    end if
else
    status = PRT_BEAM_REMNANT
end if
end function parton_to_status

```

<Shower partons: parton: TBP>+≡

```

procedure :: to_color => parton_to_color

```

<Shower partons: procedures>+≡

```

pure subroutine parton_to_color (parton, c1, c2, from_hard_int)
class(parton_t), intent(in) :: parton
integer, intent(out) :: c1, c2
logical, intent(in), optional :: from_hard_int
logical :: fhi
fhi = .false.; if (present (from_hard_int)) fhi = from_hard_int
c1 = 0
c2 = 0
if (parton%is_colored ()) then
    if (fhi) then
        if (parton%c1 /= 0) c1 = parton%c1
        if (parton%c2 /= 0) c2 = parton%c2
    else
        if (parton%c1 /= 0) c1 = 500 + parton%c1
        if (parton%c2 /= 0) c2 = 500 + parton%c2
    end if
end if
end subroutine parton_to_color

```

<Shower partons: public>+≡

```

public :: parton_copy

```

```

(Shower partons: procedures)+≡
subroutine parton_copy (prt1, prt2)
  type(parton_t), intent(in) :: prt1
  type(parton_t), intent(out) :: prt2
  if (associated (prt1%settings)) prt2%settings => prt1%settings
  prt2%nr = prt1%nr
  prt2%type = prt1%type
  prt2%momentum = prt1%momentum
  prt2%t = prt1%t
  prt2%scale = prt1%scale
  prt2%z = prt1%z
  prt2%costheta = prt1%costheta
  prt2%x = prt1%x
  prt2%simulated = prt1%simulated
  prt2%belongstoFSR = prt1%belongstoFSR
  prt2%belongstointeraction = prt1%belongstointeraction
  prt2%interactionnr = prt1%interactionnr
  if (associated (prt1%parent)) prt2%parent => prt1%parent
  if (associated (prt1%child1)) prt2%child1 => prt1%child1
  if (associated (prt1%child2)) prt2%child2 => prt1%child2
  if (associated (prt1%initial)) prt2%initial => prt1%initial
  prt2%c1 = prt1%c1
  prt2%c2 = prt1%c2
  prt2%aux_pt = prt1%aux_pt
end subroutine parton_copy

```

This returns the angle between the daughters assuming them to be massless.

```

(Shower partons: parton: TBP)+≡
  procedure :: get_costheta => parton_get_costheta

(Shower partons: procedures)+≡
elemental function parton_get_costheta (prt) result (costheta)
  class(parton_t), intent(in) :: prt
  real(default) :: costheta
  real(default) :: denom
  denom = two * prt%z * (one - prt%z) * prt%momentum%p(0)**2
  if (denom > eps0) then
    costheta = one - prt%t / denom
  else
    costheta = - one
  end if
end function parton_get_costheta

```

The same for massive daughters.

```

(Shower partons: parton: TBP)+≡
  procedure :: get_costheta_mass => parton_get_costheta_mass

(Shower partons: procedures)+≡
elemental function parton_get_costheta_mass (prt) result (costheta)
  class(parton_t), intent(in) :: prt
  real(default) :: costheta, sqrt12
  if (prt%is_branched ()) then
    if (prt%child1%simulated .and. &
        prt%child2%simulated) then

```

```

      sqrt12 = sqrt (max (zero, (prt%z)**2 * prt%momentum%p(0)**2 &
                          - prt%child1%t)) * &
                sqrt (max (zero, (one - prt%z)**2 * prt%momentum%p(0)**2 &
                          - prt%child2%t))
      if (sqrt12 > eps0) then
        costheta = (prt%t - prt%child1%t - prt%child2%t - &
                    two * prt%z * (one - prt%z) * prt%momentum%p(0)**2) / &
                    (- two * sqrt12)
        return
      end if
    end if
  end if
  costheta = prt%get_costheta ()
end function parton_get_costheta_mass

```

This function returns the angle between the momentum vectors of the parton and first daughter. This is only used for debugging.

```

<Shower partons: parton: TBP>+=
  procedure :: get_costheta_motherfirst => parton_get_costheta_motherfirst

<Shower partons: procedures>+=
  elemental function parton_get_costheta_motherfirst (prt) result (costheta)
    class(parton_t), intent(in) :: prt
    real(default) :: costheta
    if (prt%is_branched ()) then
      if ((prt%child1%simulated .or. &
          prt%child1%is_final () .or. &
          prt%child1%is_branched ()) .and. &
          (prt%child2%simulated .or. &
          prt%child2%is_final () .or. &
          prt%child2%is_branched ())) then
        costheta = enclosed_angle_ct (prt%momentum, prt%child1%momentum)
        return
      end if
    end if
    costheta = - two
  end function parton_get_costheta_motherfirst

```

Get the parton velocities.

```

<Shower partons: parton: TBP>+=
  procedure :: get_beta => parton_get_beta

<Shower partons: procedures>+=
  pure function get_beta (t,E) result (beta)
    real(default), intent(in) :: t,E
    real(default) :: beta
    beta = sqrt (max (tiny_07, one - t / (E**2)))
  end function get_beta

  elemental function parton_get_beta (prt) result (beta)
    class(parton_t), intent(in) :: prt
    real(default) :: beta
    beta = sqrt (max (tiny_07, one - prt%t / prt%momentum%p(0)**2))
  end function parton_get_beta

```

Write routine.

```

(Shower partons: parton: TBP)+≡
  procedure :: write => parton_write

(Shower partons: procedures)+≡
  subroutine parton_write (prt, unit)
    class(parton_t), intent(in) :: prt
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return

    write (u, "(1x,7A)") "Shower parton <nr>", TAB, "<type>", TAB // TAB, &
      "<parent>", TAB, "<mom(0:3)>"
    write (u, "(2x,I5,3A)", advance = "no") prt%nr, TAB, TAB, TAB
    if (prt%is_final ()) then
      write (u, "(1x,I5,1x,A)", advance = "no") prt%type, TAB // TAB
    else
      write (u, "(' ',I5,' ',A)", advance = "no") prt%type, TAB // TAB
    end if
    if (associated (prt%parent)) then
      write (u, "(I5,A)", advance = "no") prt%parent%nr, TAB // TAB
    else
      write (u, "(5x,2A)", advance = "no") TAB, TAB
    end if
    write (u, "(4(ES12.5,A))") prt%momentum%p(0), TAB, &
      prt%momentum%p(1), TAB, &
      prt%momentum%p(2), TAB, &
      prt%momentum%p(3)
    write (u, "(1x,9A)") "<p4square>", TAB // TAB, "<t>", TAB // TAB, &
      "<scale>", TAB // TAB, "<c1>", TAB, "<c2>"
    write (u, "(1x,3(ES12.5,A))", advance = "no") &
      prt%momentum ** 2, TAB // TAB, prt%t, TAB, prt%scale, TAB
    write (u, "(2(I4,A))") prt%c1, TAB, prt%c2, TAB
    if (prt%is_branched ()) then
      if (prt%belongstoFSR) then
        write (u, "(1x,9A)") "costheta(prt)", TAB, &
          "costheta_correct(prt)", TAB, &
          "prt%costheta", TAB, "prt%z", TAB, &
          "costheta_motherfirst(prt)"
        write (u, "(1X,5(ES12.5,A))") &
          prt%get_costheta (), TAB, &
          prt%get_costheta_mass (), TAB // TAB, &
          prt%costheta, TAB, prt%z, TAB, &
          prt%get_costheta_motherfirst (), TAB
      else
        write (u, "(1x,9A)") "prt%z", TAB, "prt%x", TAB, &
          "costheta_correct(prt)", TAB, &
          "prt%costheta", TAB, &
          "costheta_motherfirst(prt)"
        write (u, "(1X,5(ES12.5,A))") &
          prt%z, TAB, prt%x, TAB, &
          prt%get_costheta_mass (), TAB, &
          prt%costheta, TAB, &

```

```

        prt%get_costheta_motherfirst (), TAB
    end if
else
    if (prt%belongstoFSR) then
        write (u, "(1X,A)") "not branched."
    else
        write (u, "(1X,A,ES12.5)") "not branched. x = ", prt%x
    end if
end if
write (u, "(A)", advance = "no") " Parton"
if (prt%belongstoFSR) then
    write (u, "(A)", advance = "no") " is FSR,"
else
    if (associated (prt%initial)) then
        write (u, "(A,I1)", advance = "no") " from hadron,", prt%initial%nr
    else
        write (u, "(A)", advance = "no") ""
    end if
end if
if (prt%is_final ()) then
    write (u, "(A)", advance = "no") " is final,"
else
    write (u, "(A)", advance = "no") ""
end if
if (prt%simulated) then
    write (u, "(A)", advance = "no") " is simulated,"
else
    write (u, "(A)", advance = "no") ""
end if
if (associated (prt%child1) .and. associated (prt%child2)) then
    write (u, "(A,2(I5),A)", advance = "no") &
        " has children: ", prt%child1%nr, prt%child2%nr, ","
else if (associated (prt%child1)) then
    write (u, "(A,1(I5),A)", advance = "no") &
        " has one child: ", prt%child1%nr, ", "
end if
if (prt%belongstointeraction) then
    write (u, "(A,I2)") " belongs to interaction ", &
        prt%interactionnr
else
    write (u, "(A,I2)") " does not belong to interaction ", &
        prt%interactionnr
end if
write (u, "(A)") TAB
end subroutine parton_write

```

<Shower partons: parton: TBP>+≡

```

    procedure :: is_final => parton_is_final

```

<Shower partons: procedures>+≡

```

    elemental function parton_is_final (prt) result (is_final)
        class(parton_t), intent(in) :: prt
        logical :: is_final
        is_final = .false.

```

```

        if (prt%belongstoFSR) then
            is_final = .not. associated (prt%child1) .and. &
                (.not. prt%belongstointeraction .or. &
                    (prt%belongstointeraction .and. prt%simulated))
        end if
    end function parton_is_final

<Shower partons: parton: TBP>+≡
    procedure :: is_branched => parton_is_branched

<Shower partons: procedures>+≡
    elemental function parton_is_branched (prt) result (is_branched)
        class(parton_t), intent(in) :: prt
        logical :: is_branched
        is_branched = associated (prt%child1) .and. associated (prt%child2)
    end function parton_is_branched

<Shower partons: parton: TBP>+≡
    procedure :: set_simulated => parton_set_simulated

<Shower partons: procedures>+≡
    pure subroutine parton_set_simulated (prt, sim)
        class(parton_t), intent(inout) :: prt
        logical, intent(in), optional :: sim
        if (present (sim)) then
            prt%simulated = sim
        else
            prt%simulated = .true.
        end if
    end subroutine parton_set_simulated

<Shower partons: public>+≡
    public :: parton_set_parent

<Shower partons: procedures>+≡
    subroutine parton_set_parent (prt, parent)
        type(parton_t), intent(inout) :: prt
        type(parton_t), intent(in) , target :: parent
        prt%parent => parent
    end subroutine parton_set_parent

<Shower partons: public>+≡
    public :: parton_get_parent

<Shower partons: procedures>+≡
    function parton_get_parent (prt) result (parent)
        type(parton_t), intent(in) :: prt
        type(parton_t), pointer :: parent
        parent => prt%parent
    end function parton_get_parent

<Shower partons: public>+≡
    public :: parton_set_initial

```

```

<Shower partons: procedures>+≡
  subroutine parton_set_initial (prt, initial)
    type(parton_t), intent(inout) :: prt
    type(parton_t), intent(in) , target :: initial
    prt%initial => initial
  end subroutine parton_set_initial

<Shower partons: public>+≡
  public :: parton_get_initial

<Shower partons: procedures>+≡
  function parton_get_initial (prt) result (initial)
    type(parton_t), intent(in) :: prt
    type(parton_t), pointer :: initial
    initial => prt%initial
  end function parton_get_initial

<Shower partons: public>+≡
  public :: parton_set_child

<Shower partons: procedures>+≡
  subroutine parton_set_child (prt, child, i)
    type(parton_t), intent(inout) :: prt
    type(parton_t), intent(in), target :: child
    integer, intent(in) :: i
    if (i == 1) then
      prt%child1 => child
    else
      prt%child2 => child
    end if
  end subroutine parton_set_child

<Shower partons: public>+≡
  public :: parton_get_child

<Shower partons: procedures>+≡
  function parton_get_child (prt, i) result (child)
    type(parton_t), pointer :: child
    type(parton_t), intent(in) :: prt
    integer, intent(in) :: i
    child => null ()
    if (i == 1) then
      child => prt%child1
    else
      child => prt%child2
    end if
  end function parton_get_child

<Shower partons: parton: TBP>+≡
  procedure :: is_quark => parton_is_quark

```



```

<Shower partons: procedures>+=
  elemental function parton_is_quark (prt) result (is_quark)
    class(parton_t), intent(in) :: prt
    logical :: is_quark
    is_quark = abs (prt%type) <= 6 .and. prt%type /= 0
  end function parton_is_quark

<Shower partons: parton: TBP>+=
  procedure :: is_squark => parton_is_squark

<Shower partons: procedures>+=
  elemental function parton_is_squark (prt) result (is_squark)
    class(parton_t), intent(in) :: prt
    logical :: is_squark
    is_squark = ((abs(prt%type) >= 1000001) .and. (abs(prt%type) <= 1000006)) &
      .or. ((abs(prt%type) >= 2000001) .and. (abs(prt%type) <= 2000006))
  end function parton_is_squark

9 can be used for gluons in codes for glueballs

<Shower partons: parton: TBP>+=
  procedure :: is_gluon => parton_is_gluon

<Shower partons: procedures>+=
  elemental function parton_is_gluon (prt) result (is_gluon)
    class(parton_t), intent(in) :: prt
    logical :: is_gluon
    is_gluon = prt%type == GLUON .or. prt%type == 9
  end function parton_is_gluon

<Shower partons: parton: TBP>+=
  procedure :: is_gluino => parton_is_gluino

<Shower partons: procedures>+=
  elemental function parton_is_gluino (prt) result (is_gluino)
    class(parton_t), intent(in) :: prt
    logical :: is_gluino
    is_gluino = prt%type == 1000021
  end function parton_is_gluino

<Shower partons: parton: TBP>+=
  procedure :: is_proton => parton_is_proton

<Shower partons: procedures>+=
  elemental function parton_is_proton (prt) result (is_hadron)
    class(parton_t), intent(in) :: prt
    logical :: is_hadron
    is_hadron = abs (prt%type) == PROTON
  end function parton_is_proton

```

TODO: SUSY partons.

```

<Shower partons: parton: TBP>+=
  procedure :: is_colored => parton_is_colored

```

```

<Shower partons: procedures>+≡
  pure function parton_is_colored (parton) result (is_colored)
    logical :: is_colored
    class(parton_t), intent(in) :: parton
    is_colored = parton_is_quark (parton) .or. parton_is_gluon (parton)
  end function parton_is_colored

```

```

<Shower partons: public>+≡
  public :: parton_mass

```

```

<Shower partons: procedures>+≡
  function parton_mass (prt) result (mass)
    type(parton_t), intent(in) :: prt
    real(default) :: mass
    mass = mass_type (prt%type)
  end function parton_mass

```

```

<Shower partons: parton: TBP>+≡
  procedure :: mass_squared => parton_mass_squared

```

```

<Shower partons: procedures>+≡
  function parton_mass_squared (prt) result (mass_squared)
    class(parton_t), intent(in) :: prt
    real(default) :: mass_squared
    mass_squared = mass_squared_type (prt%type)
  end function parton_mass_squared

```

```

<Shower partons: public>+≡
  public :: P_prt_to_child1

```

```

<Shower partons: procedures>+≡
  function P_prt_to_child1 (prt) result (retvalue)
    type(parton_t), intent(in) :: prt
    real(default) :: retvalue
    retvalue = zero
    if (prt%is_gluon ()) then
      if (prt%child1%is_quark ()) then
        retvalue = P_gqq (prt%z)
      else if (prt%child1%is_gluon ()) then
        retvalue = P_ggg (prt%z) + P_ggg (one - prt%z)
      end if
    else if (prt%is_quark ()) then
      if (prt%child1%is_quark ()) then
        retvalue = P_qqg (prt%z)
      else if (prt%child1%is_gluon ()) then
        retvalue = P_qqg (one - prt%z)
      end if
    end if
  end function P_prt_to_child1

```

This function returns whether the kinematics of the branching of parton prt into its daughters are allowed or not.

```

<Shower partons: public>+≡
  public :: thetabar

```

<Shower partons: procedures>+≡

```

function thetabar (prt, recoiler, isr_ang, E3out) result (retvalue)
  type(parton_t), intent(inout) :: prt
  type(parton_t), intent(in) :: recoiler
  real(default), intent(out), optional :: E3out
  logical, intent(in) :: isr_ang
  logical :: retvalue
  real(default) :: ctheta, cthetachild1
  real(default) p1, p4, p3, E3, shat

  shat = (prt%child1%momentum + recoiler%momentum)**2
  E3 = 0.5_default * (shat / prt%z - recoiler%t + prt%child1%t - &
    prt%child2%mass_squared ()) / sqrt(shat)
  if (present (E3out)) then
    E3out = E3
  end if
  !!! absolute values of momenta in a 3 -> 1 + 4 branching
  p3 = sqrt (E3**2 - prt%t)
  p1 = sqrt (prt%child1%momentum%p(0)**2 - prt%child1%t)
  p4 = sqrt (max (zero, (E3 - prt%child1%momentum%p(0))**2 &
    - prt%child2%t))
  if (p3 > zero) then
    retvalue = ((p1 + p4 >= p3) .and. (p3 >= abs(p1 - p4)) )
    if (retvalue .and. isr_ang) then
      !!! check angular ordering
      if (associated (prt%child1)) then
        if (associated (prt%child1%child2)) then
          ctheta = (E3**2 - p1**2 - p4**2 + prt%t) / (two * p1 * p4)
          cthetachild1 = (prt%child1%momentum%p(0)**2 - &
            space_part (prt%child1%child1%momentum)**2 &
            - space_part (prt%child1%child2%momentum)**2 + prt%child1%t) &
            / (two * space_part (prt%child1%child1%momentum)**1 * &
            space_part (prt%child1%child2%momentum)**1)
          retvalue = (ctheta > cthetachild1)
        end if
      end if
    end if
  else
    retvalue = .false.
  end if
end function thetabar

```

<Shower partons: public>+≡

public :: parton_apply_z

<Shower partons: procedures>+≡

```

recursive subroutine parton_apply_z(prt, newz)
  type(parton_t), intent(inout) :: prt
  real(default), intent(in) :: newz
  if (DEBUG_WHIZ_SHOWER) print *, "D: old z = ", prt%z , " new z = ", newz
  prt%z = newz
  if (associated (prt%child1) .and. associated (prt%child2)) then
    prt%child1%momentum%p(0) = newz * prt%momentum%p(0)
    call parton_apply_z (prt%child1, prt%child1%z)
  end if
end subroutine parton_apply_z

```

```

        prt%child2%momentum%p(0) = (one - newz) * prt%momentum%p(0)
        call parton_apply_z (prt%child2, prt%child2%z)
    end if
end subroutine parton_apply_z

```

<Shower partons: public>+≡

```

    public :: parton_apply_cstheta

```

<Shower partons: procedures>+≡

```

recursive subroutine parton_apply_cstheta (prt, rng)
    type(parton_t), intent(inout) :: prt
    class(rng_t), intent(inout), allocatable :: rng
    if (DEBUG_WHIZ_SHOWER) print *, "D: parton_apply_cstheta for parton " , prt%nr
    prt%z = 0.5_default * (one + prt%get_beta () * prt%costheta)
    if (associated (prt%child1) .and. associated (prt%child2) ) then
        if (prt%child1%simulated .and. &
            prt%child2%simulated) then
            prt%z = 0.5_default * (one + (prt%child1%t - prt%child2%t) / &
                prt%t + prt%get_beta () * prt%costheta * &
                sqrt((prt%t - prt%child1%t - prt%child2%t)**2 - &
                    4 * prt%child1%t * prt%child2%t) / prt%t)
            if (prt%type /= INTERNAL) then
                prt%child1%momentum%p(0) = prt%z * prt%momentum%p(0)
                prt%child2%momentum%p(0) = (one - prt%z) * prt%momentum%p(0)
            end if
            call prt%generate_ps (rng)
            call parton_apply_cstheta (prt%child1, rng)
            call parton_apply_cstheta (prt%child2, rng)
        end if
    end if
end subroutine parton_apply_cstheta

```

<Shower partons: public>+≡

```

    public :: parton_apply_lorentztrafo

```

<Shower partons: procedures>+≡

```

subroutine parton_apply_lorentztrafo (prt, L)
    type(parton_t), intent(inout) :: prt
    type(lorentz_transformation_t), intent(in) :: L
    prt%momentum = L * prt%momentum
end subroutine parton_apply_lorentztrafo

```

<Shower partons: public>+≡

```

    public :: parton_apply_lorentztrafo_recursive

```

<Shower partons: procedures>+≡

```

recursive subroutine parton_apply_lorentztrafo_recursive (prt, L)
    type(parton_t), intent(inout) :: prt
    type(lorentz_transformation_t) ,intent(in) :: L
    if (prt%type /= PROTON .and. prt%type /= BEAM_REMNANT) then
        !!! don't boost hadrons and beam-remnants
        call parton_apply_lorentztrafo (prt, L)
    end if
    if (associated (prt%child1) .and. associated (prt%child2)) then

```

```

    if ((space_part_norm (prt%child1%momentum) < eps0) .and. &
        (space_part_norm (prt%child2%momentum) < eps0) .and. &
        (.not. prt%child1%belongstointeraction) .and. &
        (.not. prt%child2%belongstointeraction)) then
        !!! don't boost unevolved timelike partons
    else
        call parton_apply_lorentztrafo_recursive (prt%child1, L)
        call parton_apply_lorentztrafo_recursive (prt%child2, L)
    end if
else
    if (associated (prt%child1)) then
        call parton_apply_lorentztrafo_recursive (prt%child1, L)
    end if
    if (associated (prt%child2)) then
        call parton_apply_lorentztrafo_recursive (prt%child2, L)
    end if
end if
end subroutine parton_apply_lorentztrafo_recursive

```

This takes the three-momentum of a parton and generates three-momenta of its children given their energy and virtuality

(Shower partons: parton: TBP)+=

```

    procedure :: generate_ps => parton_generate_ps

```

(Shower partons: procedures)+=

```

subroutine parton_generate_ps (prt, rng)
    class(parton_t), intent(inout) :: prt
    class(rng_t), intent(inout), allocatable :: rng
    real(default), dimension(1:3, 1:3) :: directions
    integer i,j
    real(default) :: scproduct, pabs, plabs, p2abs, x, ptabs, phi
    real(default), dimension(1:3) :: momentum
    type(vector3_t) :: pchild1_direction
    type(lorentz_transformation_t) :: L, rotation
    if (DEBUG_WHIZ_SHOWER) print *, "D: parton_generate_ps for parton " , prt%nr
    if (ENSURE) then
        if (.not. (associated (prt%child1) .and. associated (prt%child2))) then
            print *, "no children for generate_ps"
            stop 1
        end if
    end if
    !!! test if parton is a virtual parton from the imagined parton shower history
    if (prt%type == INTERNAL) then
        L = inverse (boost (prt%momentum, sqrt(prt%t)))
        !!! boost to restframe of mother
        call parton_apply_lorentztrafo (prt, L)
        call parton_apply_lorentztrafo (prt%child1, L)
        call parton_apply_lorentztrafo (prt%child2, L)
        !!! Store child1's momenta
        pchild1_direction = direction (space_part (prt%child1%momentum))
        !!! Redistribute energy
        prt%child1%momentum%p(0) = (prt%momentum%p(0)**2 - &
            prt%child2%t + prt%child1%t) / (two * prt%momentum%p(0))
        prt%child2%momentum%p(0) = prt%momentum%p(0) - &

```

```

prt%child1%momentum%p(0)

! rescale momenta and set momenta to be along z-axis
prt%child1%momentum = vector4_moving (prt%child1%momentum%p(0), &
    vector3_canonical(3) * &
    sqrt(prt%child1%momentum%p(0)**2 - prt%child1%t))
prt%child2%momentum = vector4_moving (prt%child2%momentum%p(0), &
    - vector3_canonical(3) * &
    sqrt(prt%child2%momentum%p(0)**2 - prt%child2%t))

!!! rotate so that total momentum is along former total momentum
rotation = rotation_to_2nd (space_part (prt%child1%momentum), &
    pchild1_direction)
call parton_apply_lorentztrafo (prt%child1, rotation)
call parton_apply_lorentztrafo (prt%child2, rotation)

L = inverse (L)          !!! inverse of the boost to restframe of mother
call parton_apply_lorentztrafo (prt, L)
call parton_apply_lorentztrafo (prt%child1, L)
call parton_apply_lorentztrafo (prt%child2, L)
else
    !!! directions(1,:) -> direction of the parent parton
    if (space_part_norm (prt%momentum) < eps0) return
    directions(1,1:3) = prt%momentum%p(1:3) / space_part_norm (prt%momentum)
    !!! directions(2,:) and directions(3,:) -> two random directions
    !!! perpendicular to the direction of the parent parton
    do j = 2, 3
        call rng%generate (directions(j,:))
    end do
    do i = 2, 3
        scproduct = zero
        do j = 1, i - 1
            scproduct = directions(i,1) * directions(j,1) + &
                directions(i,2) * directions(j,2) + &
                directions(i,3) * directions(j,3)
            directions(i,1) = directions(i,1) - directions(j,1) * scproduct
            directions(i,2) = directions(i,2) - directions(j,2) * scproduct
            directions(i,3) = directions(i,3) - directions(j,3) * scproduct
        end do
        scproduct = directions(i,1)**2 + directions(i,2)**2 + &
            directions(i,3)**2
        do j = 1, 3
            directions(i,j) = directions(i,j) / sqrt(scproduct)
        end do
    end do
    <Enforce right-handed system for directions>

    pabs = space_part_norm (prt%momentum)
    if ((prt%child1%momentum%p(0)**2 - prt%child1%t < 0) .or. &
        (prt%child2%momentum%p(0)**2 - prt%child2%t < 0)) then
        if (DEBUG_WHIZ_SHOWER) print *, "D: generate_ps error at E^2 < t"
        return
    end if
    plabs = sqrt (prt%child1%momentum%p(0)**2 - prt%child1%t)

```

```

p2abs = sqrt (prt%child2%momentum%p(0)**2 - prt%child2%t)
x = (pabs**2 + p1abs**2 - p2abs**2) / (two * pabs)
if (pabs > p1abs + p2abs .or. &
    pabs < abs(p1abs - p2abs)) then
  if (DEBUG_WHIZ_SHOWER) then
    print *, "D: parton_generate_ps Dreiecksungleichung error &
      &for parton ", prt%nr, " ", &
      space_part_norm (prt%momentum), " ", p1abs, " ", p2abs
    call prt%write ()
    call prt%child1%write ()
    call prt%child2%write ()
  end if
  return
end if
!!! Due to numerical problems transverse momentum could be imaginary ->
!!!      set transverse momentum to zero
ptabs = sqrt (max (p1abs * p1abs - x * x, zero))
call rng%generate (phi)
phi = twopi * phi
do i = 1, 3
  momentum(i) = x * directions(1,i) + ptabs * &
    (cos(phi) * directions(2,i) + sin(phi) * directions(3,i))
end do
prt%child1%momentum%p(1:3) = momentum(1:3)
do i = 1, 3
  momentum(i) = (space_part_norm (prt%momentum) - x) * directions(1,i) - &
    ptabs * (cos(phi) * directions(2,i) + sin(phi) * directions(3,i))
end do
prt%child2%momentum%p(1:3) = momentum(1:3)
end if
end subroutine parton_generate_ps

```

(Enforce right-handed system for directions)≡

```

  if ((directions(1,1) * (directions(2,2) * directions(3,3) - &
    directions(2,3) * directions(3,2)) + &
    directions(1,2) * (directions(2,3) * directions(3,1) - &
    directions(2,1) * directions(3,3)) + &
    directions(1,3) * (directions(2,1) * directions(3,2) - &
    directions(2,2) * directions(3,1))) < 0) then
    directions(3,:) = - directions(3,:)
  end if

```

This routine is similar to `parton_generate_ps`, but now for the ISR. It takes the three-momentum of a parton's first child as fixed and generates the two remaining three-momenta.

(Shower partons: parton: TBP)+≡

```

  procedure :: generate_ps_ini => parton_generate_ps_ini

```

(Shower partons: procedures)+≡

```

  subroutine parton_generate_ps_ini (prt, rng)
    class(parton_t), intent(inout) :: prt
    class(rng_t), intent(inout), allocatable :: rng
    real(default), dimension(1:3, 1:3) :: directions
    integer :: i,j

```

```

real(default) :: scproduct, pabs, plabs, p2abs, x, ptabs, phi
real(default), dimension(1:3) :: momentum
if (DEBUG_WHIZ_SHOWER) print *, "D: parton_generate_ps_ini: for parton " , prt%nr
if (ENSURE) then
    if (.not. (associated (prt%child1) .and. associated (prt%child2))) then
        print *, "no children for generate_ps"
        stop 1
    end if
end if

if (.not. prt%is_proton()) then
    !!! generate ps for normal partons
    do i = 1, 3
        directions(1,i) = prt%child1%momentum%p(i) / &
            space_part_norm(prt%child1%momentum)
    end do
    do j = 2, 3
        call rng%generate (directions(j,:))
    end do
    do i = 2, 3
        scproduct = zero
        do j = 1, i - 1
            scproduct = directions(i,1) * directions(j,1) + &
                directions(i,2) * directions(j,2) + &
                directions(i,3) * directions(j,3)
            directions(i,1) = directions(i,1) - directions(j,1) * scproduct
            directions(i,2) = directions(i,2) - directions(j,2) * scproduct
            directions(i,3) = directions(i,3) - directions(j,3) * scproduct
        end do
        scproduct = directions(i,1)**2 + directions(i,2)**2 + &
            directions(i,3)**2
        do j = 1, 3
            directions(i,j) = directions(i,j) / sqrt(scproduct)
        end do
    end do
    Enforce right-handed system for directions

    pabs = space_part_norm (prt%child1%momentum)
    plabs = sqrt (prt%momentum%p(0)**2 - prt%t)
    p2abs = sqrt (max(zero, prt%child2%momentum%p(0)**2 - &
        prt%child2%t))

    x = (pabs**2 + plabs**2 - p2abs**2) / (two * pabs)
    if (ENSURE) then
        if (pabs > plabs + p2abs .or. pabs < abs(plabs - p2abs)) then
            print *, "error at generate_ps, Dreiecksungleichung for parton ", &
                prt%nr, " ", pabs," ",plabs," ",p2abs
            call prt%write ()
            call prt%child1%write ()
            call prt%child2%write ()
            stop 1
        end if
    end if
    if (DEBUG_WHIZ_SHOWER) print *, "D: parton_generate_ps_ini: x = ", x

```



```

ptabs = sqrt (plabs * plabs - x**2)
call rng%generate (phi)
phi = twopi * phi
do i = 1,3
    momentum(i) = x * directions(1,i) + ptabs * (cos(phi) * &
        directions(2,i) + sin(phi) * directions(3,i))
end do
prt%momentum%p(1:3) = momentum
do i = 1, 3
    momentum(i) = (x - pabs) * directions(1,i) + ptabs * (cos(phi) * &
        directions(2,i) + sin(phi) * directions(3,i))
end do
prt%child2%momentum%p(1:3) = momentum(1:3)
else
    !!! for first partons just set beam remnants momentum
    prt%child2%momentum = prt%momentum - prt%child1%momentum
end if
end subroutine parton_generate_ps_ini

```

20.2.3 The analytic FSR

```

<Shower partons: parton: TBP>+≡
    procedure :: next_t_ana => parton_next_t_ana

<Shower partons: procedures>+≡
    subroutine parton_next_t_ana (prt, rng)
        class(parton_t), intent(inout) :: prt
        class(rng_t), intent(inout), allocatable :: rng
        integer :: gtoqq
        real(default) :: integral, random

        if (signal_is_pending ()) return
        if (DEBUG_WHIZ_SHOWER) then
            print *, "D: parton_next_t_ana: for parton " , prt%nr
        end if

        ! check if branchings are possible at all
        if (min (prt%t, prt%momentum%p(0)**2) < &
            prt%mass_squared () + prt%settings%d_min_t) then
            prt%t = prt%mass_squared ()
            call prt%set_simulated ()
            return
        end if

        integral = zero
        call rng%generate (random)
        do
            if (signal_is_pending ()) return
            call parton_simulate_stept (prt, rng, integral, random, gtoqq, .false.)
            if (prt%simulated) then
                if (prt%is_gluon ()) then
                    !!! Abusing the x-variable to store the information to which
                    !!! quark flavor the gluon branches (if any)

```

```

        prt%x = one * gtoqq + 0.1_default
        !!! x = gtoqq + 0.1 -> int(x) will be the quark flavor or
        !!! zero for g -> gg
    end if
    exit
end if
end do
end subroutine parton_next_t_ana

```

The shower is actually sensitive to how close we go to the one here.

(Shower partons: procedures)+≡

```

pure function cmax (prt, tt) result (cma)
  type(parton_t), intent(in) :: prt
  real(default), intent(in), optional :: tt
  real(default) :: cma
  real(default) :: t, cost

  if (present(tt)) then
    t = tt
  else
    t = prt%t
  end if

  if (associated (prt%parent)) then
    cost = prt%parent%get_costheta ()
    cma = min (0.99999_default, sqrt( max(zero, one - t/ &
      (prt%get_beta () * prt%momentum%p(0))*2 * &
      (one + cost) / (one - cost))))
  else
    cma = 0.99999_default
  end if
end function cmax

```

Simulation routine. The variable `lookatsister` takes constraints from the sister parton into account, if not given it is assumed `.true.`. `a` and `x` are three-dimensional arrays for values used for the integration.

(Shower partons: public)+≡

```

public :: parton_simulate_stept

```

(Shower partons: procedures)+≡

```

subroutine parton_simulate_stept &
  (prt, rng, integral, random, gtoqq, lookatsister)
  type(parton_t), intent(inout) :: prt
  class(rng_t), intent(inout), allocatable :: rng
  real(default), intent(inout) :: integral
  real(default), intent(inout) :: random
  integer, intent(out) :: gtoqq
  logical, intent(in), optional :: lookatsister

  type(parton_t), pointer :: sister
  real(default) :: tstep, tmin, oldt
  real(default) :: c, cstep
  real(default), dimension(3) :: z, P

```

```

real(default) :: to_integral
real(default) :: a11,a12,a13,a21,a22,a23
real(default) :: cmax_t
real(default) :: temprand
real(default), dimension(3) :: a, x

! higher values -> faster but coarser
real(default), parameter :: tstepfactor = 0.02_default
real(default), parameter :: tstepmin = 0.5_default
real(default), parameter :: cstepfactor = 0.8_default
real(default), parameter :: cstepmin = 0.03_default

if (signal_is_pending ()) return
gtoqq = 111 ! illegal value
call prt%set_simulated (.false.)

<Set sister if lookatsister is true or not given>

tmin = prt%settings%d_min_t + prt%mass_squared ()
if (prt%is_quark ()) then
  to_integral = three * pi * log(one / random)
else if (prt%is_gluon ()) then
  to_integral = four * pi * log(one / random)
else
  prt%t = prt%mass_squared ()
  call prt%set_simulated ()
  return
end if

if (associated (sister)) then
  if (sqrt(prt%t) > sqrt(prt%parent%t) - &
      sqrt(sister%mass_squared ())) then
    prt%t = (sqrt (prt%parent%t) - sqrt (sister%mass_squared ()))**2
  end if
end if
if (prt%t > prt%momentum%p(0)**2) then
  prt%t = prt%momentum%p(0)**2
end if

if (prt%t <= tmin) then
  prt%t = prt%mass_squared ()
  call prt%set_simulated ()
  return
end if

! simulate the branchings between prt%t and prt%t - tstep
tstep = max(tstepfactor * (prt%t - 0.9_default * tmin), tstepmin)
cmax_t = cmax(prt)
c = - cmax_t ! take highest t -> minimal constraint
cstep = max(cstepfactor * (one - abs(c)), cstepmin)
! get values at border of "previous" bin -> to be used in first bin
z(3) = 0.5_default + 0.5_default * get_beta (prt%t - &
  0.5_default * tstep, prt%momentum%p(0)) * c
if (prt%is_gluon ()) then

```

```

P(3) = P_ggg (z(3)) + P_gqq (z(3)) * number_of_flavors &
      (prt%t, prt%settings%max_n_flavors, prt%settings%d_min_t)
else
  P(3) = P_qqg (z(3))
end if
a(3) = D_alpha_s_fsr (z(3) * (one - z(3)) * prt%t, &
      prt%settings) * P(3) / (prt%t - 0.5_default * tstep)

do while (c < cmax_t .and. (integral < to_integral))
  if (signal_is_pending ()) return
  cmax_t = cmax (prt)
  cstep = max (cstepfactor * (one - abs(c)**2), cstepmin)
  if (c + cstep > cmax_t) then
    cstep = cmax_t - c
  end if
  if (cstep < 1E-9_default) then
    !!! reject too small bins
    exit
  end if
  z(1) = z(3)
  z(2) = 0.5_default + 0.5_default * get_beta &
        (prt%t - 0.5_default * tstep, prt%momentum%p(0)) * &
        (c + 0.5_default * cstep)
  z(3) = 0.5_default + 0.5_default * get_beta &
        (prt%t - 0.5_default * tstep, prt%momentum%p(0)) * (c + cstep)
  P(1) = P(3)
  if (prt%is_gluon ()) then
    P(2) = P_ggg(z(2)) + P_gqq(z(2)) * number_of_flavors &
          (prt%t, prt%settings%max_n_flavors, prt%settings%d_min_t)
    P(3) = P_ggg(z(3)) + P_gqq(z(3)) * number_of_flavors &
          (prt%t, prt%settings%max_n_flavors, prt%settings%d_min_t)
  else
    P(2) = P_qqg(z(2))
    P(3) = P_qqg(z(3))
  end if
  ! get values at borders of the integral and in the middle
  a(1) = a(3)
  a(2) = D_alpha_s_fsr (z(2) * (one - z(2)) * prt%t, &
        prt%settings) * P(2) / &
        (prt%t - 0.5_default * tstep)
  a(3) = D_alpha_s_fsr (z(3) * (one - z(3)) * prt%t, &
        prt%settings) * P(3) / &
        (prt%t - 0.5_default * tstep)

  !!! a little tricky:
  !!! fit  $x(1) + x(2)/(1 + c) + x(3)/(1 - c)$  to these values
  a11 = (one+c+0.5_default*cstep) * (one-c-0.5_default*cstep) - &
        (one-c) * (one+c+0.5_default*cstep)
  a12 = (one-c-0.5_default*cstep) - (one+c+0.5_default*cstep) * &
        (one-c) / (one+c)
  a13 = a(2) * (one+c+0.5_default*cstep) * (one-c-0.5_default*cstep) - &
        a(1) * (one-c) * (one+c+0.5_default*cstep)
  a21 = (one+c+cstep) * (one-c-cstep) - (one+c+cstep) * (one-c)
  a22 = (one-c-cstep) - (one+c+cstep) * (one-c) / (one+c)

```

```

a23 = a(3) * (one+c+cstep) * (one-c-cstep) - &
      a(1) * (one-c) * (one+c+cstep)

x(2) = (a23 - a21 * a13 / a11) / (a22 - a12 * a21 / a11)
x(1) = (a13 - a12 * x(2)) / a11
x(3) = a(1) * (one - c) - x(1) * (one - c) - x(2) * (one - c) / (one + c)

integral = integral + tstep * (x(1) * cstep + x(2) * &
      log((one + c + cstep) / (one + c)) - x(3) * &
      log((one - c - cstep) / (one - c)))

if (integral > to_integral) then
  oldt = prt%t
  call rng%generate (temprand)
  prt%t = prt%t - temprand * tstep
  call rng%generate (temprand)
  prt%costheta = c + (0.5_default - temprand) * cstep
  call prt%set_simulated ()

  if (prt%t < prt%settings%d_min_t + prt%mass_squared ()) then
    prt%t = prt%mass_squared ()
  end if
  if (abs(prt%costheta) > cmax_t) then
    ! reject branching due to violation of costheta-limits
    call rng%generate (random)
    if (prt%is_quark ()) then
      to_integral = three * pi * log(one / random)
    else if (prt%is_gluon ()) then
      to_integral = four * pi * log(one / random)
    end if
    integral = zero
    prt%t = oldt
    call prt%set_simulated (.false.)
  end if
  if (prt%is_gluon ()) then
    ! decide between g->gg and g->qqbar splitting
    z(1) = 0.5_default + 0.5_default * prt%costheta
    call rng%generate (temprand)
    if (P_ggg(z(1)) > temprand * (P_ggg (z(1)) + P_gqq (z(1)) * &
      number_of_flavors(prt%t, prt%settings%max_n_flavors, &
      prt%settings%d_min_t))) then
      gtoqq = 0
    else
      call rng%generate (temprand)
      gtoqq = 1 + int (temprand * number_of_flavors &
        (prt%t, prt%settings%max_n_flavors, prt%settings%d_min_t))
    end if
  end if
else
  c = c + cstep
end if
cmax_t = cmax (prt)
end do
if (integral <= to_integral) then

```

```

    prt%t = prt%t - tstep
    if (prt%t < prt%settings%d_min_t + prt%mass_squared ()) then
        prt%t = prt%mass_squared ()
        call prt%set_simulated ()
    end if
end if
end if
end subroutine parton_simulate_step

```

⟨Set sister if lookatsister is true or not given⟩≡

```

sister => null()
SET_SISTER: do
    if (present (lookatsister)) then
        if (.not. lookatsister) then
            exit SET_SISTER
        end if
    end if
    if (prt%nr == prt%parent%child1%nr) then
        sister => prt%parent%child2
    else
        sister => prt%parent%child1
    end if
    exit SET_SISTER
end do SET_SISTER

```

From the whole ISR algorithm all functionality has been moved to `shower_core.f90`. Only `maxzz` remains here, because more than one module needs to access it.

⟨Shower partons: public⟩+≡

```
public :: maxzz
```

⟨Shower partons: procedures⟩+≡

```

function maxzz (shat, s, maxz_isr, minenergy_timelike) result (maxz)
    real(default), intent(in) :: shat, s, minenergy_timelike, maxz_isr
    real(default) :: maxz
    maxz = min (maxz_isr, one - (two * minenergy_timelike * sqrt(shat)) / s)
end function maxzz

```

20.3 Main shower module

⟨shower_core.f90⟩≡

⟨File header⟩

```
module shower_core
```

⟨Use kinds with double⟩

⟨Use strings⟩

```

    use io_units
    use constants
    use format_utils, only: write_separator
    use unit_tests, only: vanishes, nearly_equal
    use system_defs, only: TAB
    use diagnostics
    use physics_defs

```

```

    use os_interface
    use lorentz
    use sm_physics
    use particles
    use model_data
    use flavors
    use colors
    use subevents
    use pdf_builtin !NODEP!
    use lhpdf !NODEP!
    use rng_base
    use shower_base
    use shower_partons
    use mlm_matching
    use ckkw_base
    use ckkw_matching
    use muli, only: muli_t
    use hep_common

    <Standard module head>

    <Shower core: public>

    <Shower core: parameters>

    <Shower core: types>

    <Shower core: interfaces>

contains

    <Shower core: procedures>

end module shower_core

<Shower core: interfaces>≡
    interface
        subroutine evolvePDFM (set, x, q, ff)
            integer, intent(in) :: set
            double precision, intent(in) :: x, q
            double precision, dimension(-6:6), intent(out) :: ff
        end subroutine evolvePDFM
    end interface

    <Shower core: public>≡
        public :: shower_interaction_t

    <Shower core: types>≡
        type :: shower_interaction_t
            type(parton_pointer_t), dimension(:), allocatable :: partons
        end type shower_interaction_t

        type :: shower_interaction_pointer_t
            type(shower_interaction_t), pointer :: i => null ()
        end type shower_interaction_pointer_t

```

The WHIZARD internal shower. Flags distinguish between analytic and k_T -ordered showers. The main type of `shower_core`: It contains many parameter of the shower, namely `maxz_isr` (PARP(66)), the minimal energy of the emitted timelike parton in the ISR `minenergy_timelike` (PARP(65)), the factor for the first scale, as well as the factor by which the integral in the Sudakov factor is suppressed for the respective first scale in ISR. Higher values here correspond to higher starting scales. Also, there is a flag whether ISR is angular ordered (MSTP(62)). The flag corresponding to MSTP(63) sets emitted timelike partons in the spacelike shower on shell.

```

<Shower core: public>+=
  public :: shower_t

<Shower core: types>+=
  type, extends (shower_base_t) :: shower_t
    type(shower_interaction_pointer_t), dimension(:), allocatable :: &
      interactions
    type(parton_pointer_t), dimension(:), allocatable :: partons
    integer :: next_free_nr
    integer :: next_color_nr
    logical :: valid
    logical :: isr_angular_ordered = .true.
    real(default) :: maxz_isr = 0.999_default
    real(default) :: minenergy_timelike = one
    real(default) :: tscalefactor_isr = one
    real(default) :: first_integral_suppression_factor = one
    logical :: isr_only_onshell_emitted_partons = .true.
  contains
    <Shower core: shower: TBP>
  end type shower_t

```

Transfer the generic shower settings to the analytic shower by calling the public `set` functions and setting up the `shower` object.

```

<Shower core: shower: TBP>=
  procedure :: init => shower_init

<Shower core: procedures>=
  subroutine shower_init (shower, settings, pdf_data)
    class(shower_t), intent(out) :: shower
    type(shower_settings_t), intent(in) :: settings
    type(pdf_data_t), intent(in) :: pdf_data
    if (DEBUG_SHOWER) &
      print *, "Transfer settings from shower_settings to shower"
    shower%settings = settings
    shower%isr_angular_ordered = settings%isr_angular_ordered
    shower%maxz_isr = settings%isr_z_cutoff
    shower%minenergy_timelike = settings%isr_minenergy
    shower%tscalefactor_isr = settings%isr_tscalefactor
    call shower%pdf_data%init (pdf_data)
    shower%name = "WHIZARD internal"
    call shower%write_msg ()
  end subroutine shower_init

```



```

<Shower core: shower: TBP>+=
  procedure :: generate_emissions => shower_generate_emissions

<Shower core: procedures>+=
  subroutine shower_generate_emissions ( &
    shower, particle_set, model, model_hadrons, &
    os_data, matching_settings, data, valid, vetoed, number_of_emissions)
    class(shower_t), intent(inout), target :: shower
    type(particle_set_t), intent(inout) :: particle_set
    class(model_data_t), intent(in), target :: model
    class(model_data_t), intent(in), target :: model_hadrons
    class(matching_settings_t), intent(in), allocatable :: matching_settings
    class(matching_data_t), intent(inout), allocatable :: data
    type(os_data_t), intent(in) :: os_data
    logical, intent(inout) :: valid
    logical, intent(inout) :: vetoed
    integer, optional, intent(in) :: number_of_emissions

    type(multi_t), save :: mi
    type(parton_t), dimension(:), allocatable, target :: partons, hadrons
    type(particle_t) :: particle
    type(parton_pointer_t), dimension(:), allocatable :: &
      parton_pointers, final_ME_partons
    real(default) :: mi_scale, ps_scale, shat, phi
    type(parton_pointer_t) :: temppp
    integer, dimension(:), allocatable :: connections
    integer :: n_loop, i, j, k
    integer :: n_beam, n_in, n_out, n_tot
    integer :: n_int, max_color_nr
    integer, dimension(2) :: col_array
    integer, dimension(1) :: parent
    integer, dimension(2,4) :: color_corr

    if (signal_is_pending ()) return

    call shower%create ()
    max_color_nr = 0

    n_beam = particle_set%get_n_beam ()
    n_in = particle_set%get_n_in ()
    n_out = particle_set%get_n_out ()
    n_tot = particle_set%get_n_tot ()

    n_loop = 0
    TRY_SHOWER: do !!! Just a loop to be able to discard events
      n_loop = n_loop + 1
      if (n_loop > 1000) call msg_fatal &
        ("Shower: too many loops (try_shower)")
      if (signal_is_pending ()) return

      allocate (connections (1:n_tot))
      connections = 0
      allocate (partons (1:n_in+n_out))
      allocate (parton_pointers (1:n_in+n_out))
      <Copy hadrons from particle_set to hadrons>

```

```

    <Copy incoming partons from particle_set to partons>
    <Copy outgoing partons from particle_set to partons>
    deallocate (connections)
    if (signal_is_pending ()) return

    if (DEBUG_SHOWER) print *, "Insert partons in shower"
    call shower%set_next_color_nr (1 + max_color_nr)
    if (allocated (data)) then
        select type (data)
            type is (ckkw_matching_data_t)
                call shower%add_interaction_2ton_CKKW (parton_pointers, &
                    data%ckkw_weights)
            class default
                call shower%add_interaction_2ton (parton_pointers)
        end select
    else
        call shower%add_interaction_2ton (parton_pointers)
    end if
    if (signal_is_pending ()) return

    <Activate multiple interactions>
    if (signal_is_pending ()) return

    if (shower%settings%ckkw_matching .and. allocated (matching_settings) &
        .and. allocated (data)) then
        if (DEBUG_SHOWER) print *, "Apply CKKW matching"
        select type (matching_settings)
            type is (ckkw_matching_settings_t)
                select type (data)
                    type is (ckkw_matching_data_t)
                        call ckkw_matching_apply (shower%partons, &
                            matching_settings, &
                            data%ckkw_weights, shower%rng, vetoed)
                        if (vetoed) then
                            return
                        end if
                    class default
                        call msg_fatal ("CKKW matching called with wrong data.")
                end select
            class default
                call msg_fatal ("CKKW matching called with wrong data.")
        end select
    end if

    if (shower%settings%isr_active) then
        if (DEBUG_SHOWER) print *, "Generate ISR with FSR"
        i = 0
        BRANCHINGS: do
            i = i+1
            if (signal_is_pending ()) return
            if (shower%settings%multi_active) then
                call mi%generate_gev2_pt2 &
                    (shower%get_ISR_scale (), mi_scale)
            else

```

```

        mi_scale = 0.0
    end if

    !!! Shower: debugging
    !!! shower%generate_next_isr_branching returns a pointer to
    !!! the parton with the next ISR-branching, this parton's
    !!! scale is the scale of the next branching
    ! temppp=shower%generate_next_isr_branching_veto ()
    temppp = shower%generate_next_isr_branching ()

    if (.not. associated (temppp%p) .and. &
        mi_scale < shower%settings%d_min_t) then
        exit BRANCHINGS
    end if
    !!! check if branching or interaction occurs next
    if (associated (temppp%p)) then
        ps_scale = abs(temppp%p/t)
    else
        ps_scale = 0._default
    end if
    if (mi_scale > ps_scale) then
        !!! discard branching evolution lower than mi_scale
        call shower%set_max_ISR_scale (mi_scale)
        if (associated (temppp%p)) &
            call temppp%p%set_simulated (.false.)

        !!! execute new interaction
        deallocate (partons)
        deallocate (parton_pointers)
        allocate (partons(1:4))
        allocate (parton_pointers(1:4))
        do j = 1, 4
            partons(j)%nr = shower%get_next_free_nr ()
            partons(j)%belongstointeraction = .true.
            parton_pointers(j)%p => partons(j)
        end do
        call mi%generate_partons (partons(1)%nr, partons(2)%nr, &
            partons(1)%x, partons(2)%x, &
            partons(1)%type, partons(2)%type, &
            partons(3)%type, partons(4)%type)
        !!! calculate momenta
        shat = partons(1)%x * partons(2)%x * &
            shower_interaction_get_s (shower%interactions(1)%i)
        partons(1)%momentum = [0.5_default * sqrt(shat), &
            zero, zero, 0.5_default*sqrt(shat)]
        partons(2)%momentum = [0.5_default * sqrt(shat), &
            zero, zero, -0.5_default*sqrt(shat)]
        call parton_set_initial (partons(1), &
            shower%interactions(1)%i%partons(1)%p%initial)
        call parton_set_initial (partons(2), &
            shower%interactions(1)%i%partons(2)%p%initial)
        partons(1)%belongstoFSR = .false.
        partons(2)%belongstoFSR = .false.
        !!! calculate color connection

```

```

call mi%get_color_correlations &
    (shower%get_next_color_nr (), &
    max_color_nr,color_corr)
call shower%set_next_color_nr (max_color_nr)

partons(1)%c1 = color_corr(1,1)
partons(1)%c2 = color_corr(2,1)
partons(2)%c1 = color_corr(1,2)
partons(2)%c2 = color_corr(2,2)
partons(3)%c1 = color_corr(1,3)
partons(3)%c2 = color_corr(2,3)
partons(4)%c1 = color_corr(1,4)
partons(4)%c2 = color_corr(2,4)

call shower%rng%generate (phi)
phi = 2 * pi * phi
partons(3)%momentum = [0.5_default*sqrt(shat), &
    sqrt(mi_scale)*cos(phi), &
    sqrt(mi_scale)*sin(phi), &
    sqrt(0.25_default*shat - mi_scale)]
partons(4)%momentum = [ 0.5_default*sqrt(shat), &
    -sqrt(mi_scale)*cos(phi), &
    -sqrt(mi_scale)*sin(phi), &
    -sqrt(0.25_default*shat - mi_scale)]
partons(3)%belongstoFSR = .true.
partons(4)%belongstoFSR = .true.

call shower%add_interaction_2ton (parton_pointers)
n_int = size (shower%interactions)
do k = 1, 2
    call mi%replace_parton &
        (shower%interactions(n_int)%i%partons(k)%p%initial%nr, &
        shower%interactions(n_int)%i%partons(k)%p%nr, &
        shower%interactions(n_int)%i%partons(k)%p%parent%nr, &
        shower%interactions(n_int)%i%partons(k)%p%type, &
        shower%interactions(n_int)%i%partons(k)%p%x, &
        mi_scale)
end do
else
!!! execute the next branching 'found' in the previous step
call shower%execute_next_isr_branching (temppp)
if (shower%settings%multi_active) then
    call mi%replace_parton (temppp%p%initial%nr, &
        temppp%p%child1%nr, temppp%p%nr, &
        temppp%p%type, temppp%p%x, ps_scale)
end if

end if
end do BRANCHINGS

call shower%generate_fsr_for_isr_partons ()
else
if (signal_is_pending ()) return
if (DEBUG_SHOWER) print *, 'Generate FSR without ISR'

```

```

        call shower%simulate_no_isr_shower ()
    end if

    !!! some bookkeeping, needed after the shower is done
    call shower%boost_to_labframe ()
    call shower%generate_primordial_kt ()
    call shower%update_beamremnants ()

    if (shower%settings%fsr_active) then
        do i = 1, size (shower%interactions)
            if (signal_is_pending ()) return
            call shower%interaction_generate_fsr_2ton &
                (shower%interactions(i)%i)
        end do
    else
        call shower%simulate_no_fsr_shower ()
    end if

    if (DEBUG_SHOWER) then
        write (*, "(A)") "SHOWER FINISHED: "
        call shower%write ()
    end if

    if (shower%settings%mlm_matching .and. allocated (data)) then
        !!! transfer momenta of the partons in the final state of
        !!! the hard interaction
        if (signal_is_pending ()) return
        select type (data)
        type is (mlm_matching_data_t)
            if (allocated (data%P_ME)) deallocate (data%P_ME)
            call shower%get_final_colored_ME_partons (final_ME_partons)
            if (allocated (final_ME_partons)) then
                allocate (data%P_ME(1:size (final_ME_partons)))
                do i = 1, size (final_ME_partons)
                    !!! transfer
                    data%P_ME(i) = final_ME_partons(i)%p%momentum
                end do
                deallocate (final_ME_partons)
            end if
        class default
            call msg_fatal ("MLM matching called with wrong data.")
        end select
    end if

    call shower%combine_with_particle_set (particle_set, model, &
        model_hadrons)

    !!! move the particle data to the PYTHIA COMMON BLOCKS in case
    !!! hadronization is active
    if (shower%settings%hadronization_active) then
        if (signal_is_pending ()) return
        call shower_converttopythia (shower)
    end if
    deallocate (partons)
    deallocate (parton_pointers)

```

```

        exit TRY_SHOWER
    end do TRY_SHOWER

    call shower%final ()
    !!! clean-up muli: we should finalize the muli pdf sets
    !!!      when _all_ runs are done. Not after every event if possible
    ! call mi%finalize()
    return
end subroutine shower_generate_emissions

<Copy hadrons from particle_set to hadrons>≡
j = 0
if (n_beam > 0 .and. all (particle_set%prt(1:2)%flv%get_pdg_abs () > TAU)) then
    allocate (hadrons (1:2))
    if (DEBUG_SHOWER) print *, "Copy hadrons from particle_set to hadrons"
    do i = 1, n_tot
        particle = particle_set%get_particle (i)
        if (particle%get_status () == PRT_BEAM) then
            j = j + 1
            hadrons(j)%nr = shower%get_next_free_nr ()
            hadrons(j)%momentum = particle%get_momentum ()
            hadrons(j)%t = hadrons(j)%momentum**2
            hadrons(j)%type = particle_set%prt(i)%get_pdg ()
            col_array = particle%get_color ()
            hadrons(j)%c1 = col_array(1)
            hadrons(j)%c2 = col_array(2)
            max_color_nr = max (max_color_nr, abs(hadrons(j)%c1), &
                                abs(hadrons(j)%c2))
            hadrons(j)%interactionnr = 1
            connections(i) = j
        end if
    end do
end if

<Copy incoming partons from particle_set to partons>≡
j = 0
if (DEBUG_SHOWER) print *, "Copy incoming partons from particle_set to partons"
do i = 1, n_tot
    particle = particle_set%get_particle (i)
    if (particle%get_status () == PRT_INCOMING) then
        j = j+1
        partons(j)%settings => shower%settings
        partons(j)%nr = shower%get_next_free_nr ()
        partons(j)%momentum = particle%get_momentum ()
        partons(j)%t = partons(j)%momentum**2
        partons(j)%type = particle%get_pdg ()
        col_array = particle%get_color ()
        partons(j)%c1 = col_array (1)
        partons(j)%c2 = col_array (2)
        parton_pointers(j)%p => partons(j)
        max_color_nr = max (max_color_nr, abs (partons(j)%c1), &
                            abs (partons(j)%c2))
        connections(i) = j
        !!! insert dependencies on hadrons
    end if
end do

```

```

        if (particle%get_n_parents () == 1 .and. allocated (hadrons)) then
            parent = particle%get_parents ()
            partons(j)%initial => hadrons (connections (parent(1)))
            partons(j)%x = space_part_norm (partons(j)%momentum) / &
                space_part_norm (partons(j)%initial%momentum)
        end if
    end if
end do

<Copy outgoing partons from particle_set to partons>≡
if (DEBUG_SHOWER) print *, "Copy outgoing partons from particle_set to partons"
do i = 1, n_tot
    particle = particle_set%get_particle (i)
    if (particle%get_status () == PRT_OUTGOING) then
        j = j + 1
        partons(j)%settings => shower%settings
        partons(j)%nr = shower%get_next_free_nr ()
        partons(j)%momentum = particle%get_momentum ()
        partons(j)%t = partons(j)%momentum**2
        partons(j)%type = particle%get_pdg ()
        col_array = particle%get_color ()
        partons(j)%c1 = col_array(1)
        partons(j)%c2 = col_array(2)
        parton_pointers(j)%p => partons(j)
        max_color_nr = max (max_color_nr, abs &
            (partons(j)%c1), abs (partons(j)%c2))
        connections(i) = j
    end if
end do

<Activate multiple interactions>≡
if (shower%settings%multi_active) then
    !!! Initialize multi pdf sets, unless initialized
    if (mi%is_initialized ()) then
        call mi%restart ()
    else
        call mi%initialize (&
            GeV2_scale_cutoff=shower%settings%d_min_t, &
            GeV2_s=shower_interaction_get_s &
            (shower%interactions(1)%i), &
            multi_dir=char(os_data%whizard_mulipath))
    end if

    !!! initial interaction
    call mi%apply_initial_interaction ( &
        GeV2_s=shower_interaction_get_s(shower%interactions(1)%i), &
        x1=shower%interactions(1)%i%partons(1)%p%parent%x, &
        x2=shower%interactions(1)%i%partons(2)%p%parent%x, &
        pdg_f1=shower%interactions(1)%i%partons(1)%p%parent%type, &
        pdg_f2=shower%interactions(1)%i%partons(2)%p%parent%type, &
        n1=shower%interactions(1)%i%partons(1)%p%parent%nr, &
        n2=shower%interactions(1)%i%partons(2)%p%parent%nr)
end if

<Shower core: public>+≡
public :: matching_transfer_PS

```

(Shower core: procedures) +=

```

subroutine matching_transfer_PS &
  (data, particle_set, settings)
  !!! transfer partons after parton shower to data%P_PS
  type(mlm_matching_data_t), intent(inout) :: data
  type(particle_set_t), intent(in) :: particle_set
  type(mlm_matching_settings_t), intent(in) :: settings
  integer :: i, j, n_jets_PS
  integer, dimension(2) :: col
  type(particle_t) :: tempprt
  real(double) :: eta
  type(vector4_t) :: p_tmp

  !!! loop over particles and extract final colored ones with eta<etamax
  n_jets_PS = 0
  do i = 1, particle_set%get_n_tot ()
    if (signal_is_pending ()) return
    tempprt = particle_set%get_particle (i)
    if (tempprt%get_status () /= PRT_OUTGOING) cycle
    col = tempprt%get_color ()
    if (all (col == 0)) cycle
    if (data%is_hadron_collision) then
      p_tmp = tempprt%get_momentum ()
      if (energy (p_tmp) - longitudinal_part (p_tmp) < 1.E-10_default .or. &
          energy (p_tmp) + longitudinal_part (p_tmp) < 1.E-10_default) then
        eta = pseudorapidity (p_tmp)
      else
        eta = rapidity (p_tmp)
      end if
      if (eta > settings%mlm_etaClusfactor * &
          settings%mlm_etamax) then
        if (DEBUG_SHOWER) then
          print *, "REJECTING"
          call tempprt%write ()
        end if
        cycle
      end if
      n_jets_PS = n_jets_PS + 1
    end do

    allocate (data%P_PS(1:n_jets_PS))
    if (DEBUG_SHOWER) write (*, "(A,1x,I0)" "n_jets_ps =", n_jets_ps

    j = 1
    do i = 1, particle_set%get_n_tot ()
      tempprt = particle_set%get_particle (i)
      if (tempprt%get_status () /= PRT_OUTGOING) cycle
      col = tempprt%get_color ()
      if (all(col == 0)) cycle
      if (data%is_hadron_collision) then
        p_tmp = tempprt%get_momentum ()
        if (energy (p_tmp) - longitudinal_part (p_tmp) < 1.E-10_default .or. &
            energy (p_tmp) + longitudinal_part (p_tmp) < 1.E-10_default) then

```



```

        eta = pseudorapidity (p_tmp)
    else
        eta = rapidity (p_tmp)
    end if
    if (eta > settings%mlm_etaClusfactor * &
        settings%mlm_etamax) cycle
    end if
    data%P_PS(j) = tempprt%get_momentum ()
    j = j + 1
end do
end subroutine matching_transfer_PS

```

The parameters of the shower module:

```

(Shower core: parameters)+≡
    real(default), save :: alphasxpdfmax = 12._default

```

```

(Shower core: shower: TBP)+≡
    procedure :: add_interaction_2ton => shower_add_interaction_2ton

```

```

(Shower core: procedures)+≡
    subroutine shower_add_interaction_2ton (shower, partons)
        class(shower_t), intent(inout) :: shower
        type(parton_pointer_t), intent(in), dimension(:), allocatable :: partons
        type(ckkw_pseudo_shower_weights_t) :: ckkw_pseudo_weights
        call shower%add_interaction_2ton_CKKW (partons, ckkw_pseudo_weights)
    end subroutine shower_add_interaction_2ton

```

In this routine, y and y_{\min} are the jet measures, w and w_{\max} are weights, s is the kinematic energy squared of the interaction. The flag `isr_is_possible_and_allowed` checks whether the initial parton is set, lepton-hadron collisions are not implemented (yet). As a workaround: as WHIZARD can treat partons as massless, there might be partons with $E < m$: if such a parton is found, quarks will be treated massless.

```

(Shower core: shower: TBP)+≡
    procedure :: add_interaction_2ton_CKKW => shower_add_interaction_2ton_CKKW

```

```

(Shower core: procedures)+≡
    subroutine shower_add_interaction_2ton_CKKW &
        (shower, partons, ckkw_pseudo_weights)
        class(shower_t), intent(inout) :: shower
        type(parton_pointer_t), intent(in), dimension(:), allocatable :: partons
        type(ckkw_pseudo_shower_weights_t), intent(in) :: ckkw_pseudo_weights

        integer :: n_partons, n_out
        integer :: i, j, imin, jmin
        real(default) :: y, ymin
        real(default) :: w, wmax
        real(default) :: random, sum
        type(parton_pointer_t), dimension(:), allocatable :: new_partons
        type(parton_t), pointer :: prt
        integer :: n_int
        type(shower_interaction_pointer_t), dimension(:), allocatable :: temp
        type(vector4_t) :: prtmomentum, childmomentum

```

```

logical :: isr_is_possible_and_allowed
type(lorentz_transformation_t) :: L

if (signal_is_pending ()) return
if (DEBUG_SHOWER) print *, "Add interaction2toN"
n_partons = size (partons)
n_out = n_partons - 2
if (n_out < 2) then
  call msg_bug &
    ("Shower core: trying to add a 2-> (something<2) interaction")
end if

isr_is_possible_and_allowed = (associated (partons(1)%p%initial) .and. &
  associated (partons(2)%p%initial)) .and. &
  shower%settings%isr_active
if (DEBUG_SHOWER) print *, 'isr_is_possible_and_allowed = ', &
  isr_is_possible_and_allowed

if (associated (partons(1)%p%initial) .and. &
  partons(1)%p%is_quark ()) then
  if (partons(1)%p%momentum%p(0) < &
    two * parton_mass (partons(1)%p)) then
    if (abs(partons(1)%p%type) < 2) then
      treat_light_quarks_massless = .true.
    else
      treat_duscb_quarks_massless = .true.
    end if
  end if
end if
if (associated (partons(2)%p%initial) .and. &
  partons(2)%p%is_quark ()) then
  if (partons(2)%p%momentum%p(0) < &
    two * parton_mass (partons(2)%p)) then
    if (abs(partons(2)%p%type) < 2) then
      treat_light_quarks_massless = .true.
    else
      treat_duscb_quarks_massless = .true.
    end if
  end if
end if

<Add a new interaction to shower%interactions>

if (associated (shower%interactions(n_int)%i%partons(1)%p%initial)) &
  call shower%interactions(n_int)%i%partons(1)%p%initial%set_simulated ()
if (associated (shower%interactions(n_int)%i%partons(2)%p%initial)) &
  call shower%interactions(n_int)%i%partons(2)%p%initial%set_simulated ()
if (isr_is_possible_and_allowed) then
  !!! boost to the CMFrame of the incoming partons
  L = boost (-(shower%interactions(n_int)%i%partons(1)%p%momentum + &
    shower%interactions(n_int)%i%partons(2)%p%momentum), &
    (shower%interactions(n_int)%i%partons(1)%p%momentum + &
    shower%interactions(n_int)%i%partons(2)%p%momentum)**1 )
  do i = 1, n_partons

```

```

        call parton_apply_lorentztrafo &
            (shower%interactions(n_int)%i%partons(i)%p, L)
    end do
end if
do i = 1, size (partons)
    if (signal_is_pending ()) return
    !!! partons are marked as belonging to the hard interaction
    shower%interactions(n_int)%i%partons(i)%p%belongstointeraction &
        = .true.
    shower%interactions(n_int)%i%partons(i)%p%belongstoFSR = i > 2

    shower%interactions(n_int)%i%partons(i)%p%interactionnr &
        = n_int
    !!! include a 2^(i - 1) number as a label for the ckkw clustering
    shower%interactions(n_int)%i%partons(i)%p%ckkwlabel = 2**(i - 1)
end do

<Add partons from shower%interactions to shower%partons>

if (isr_is_possible_and_allowed) then
    if (shower%settings%isr_pt_ordered) then
        call shower_prepare_for_simulate_isr_pt &
            (shower, shower%interactions(size (shower%interactions))%i)
    else
        call shower_prepare_for_simulate_isr_ana_test &
            (shower, shower%interactions(n_int)%i%partons(1)%p, &
            shower%interactions(n_int)%i%partons(2)%p)
    end if
end if

!!! generate pseudo parton shower history and add all partons to
!!! shower%partons-array
!!! TODO initial -> initial + final branchings ??
allocate (new_partons(1:(n_partons - 2)))
do i = 1, size (new_partons)
    nullify (new_partons(i)%p)
end do
do i = 1, size (new_partons)
    new_partons(i)%p => shower%interactions(n_int)%i%partons(i + 2)%p
end do
imin = 0
jmin = 0

if (allocated (ckkw_pseudo_weights%weights)) then
    <Perform clustering using the CKKW weights>
else
    <Perform clustering in the usual way>
end if

!!! set the FSR starting scale for all partons
do i = 1, size (new_partons)
    !!! the imaginary mother is the only parton remaining in new_partons
    if (.not. associated (new_partons(i)%p)) cycle

```

```

        call set_starting_scale (new_partons(i)%p, &
            get_starting_scale (new_partons(i)%p))
        exit
    end do

    deallocate (new_partons)

contains

    <Procedures of shower_add_interaction_2ton_CKKW>
end subroutine shower_add_interaction_2ton_CKKW

<Add a new interaction to shower%interactions>≡
if (allocated (shower%interactions)) then
    n_int = size (shower%interactions) + 1
else
    n_int = 1
end if
allocate (temp (1:n_int))
do i = 1, n_int - 1
    allocate (temp(i)%i)
    temp(i)%i = shower%interactions(i)%i
end do
allocate (temp(n_int)%i)
allocate (temp(n_int)%i%partons(1:n_partons))
do i = 1, n_partons
    allocate (temp(n_int)%i%partons(i)%p)
    call parton_copy (partons(i)%p, temp(n_int)%i%partons(i)%p)
end do
if (allocated (shower%interactions)) deallocate(shower%interactions)
allocate (shower%interactions(1:n_int))
do i = 1, n_int
    shower%interactions(i)%i => temp(i)%i
end do
deallocate (temp)

<Add partons from shower%interactions to shower%partons>≡
if (allocated (shower%partons)) then
    allocate (new_partons(1:size(shower%partons) + &
        size(shower%interactions(n_int)%i%partons)))
    do i = 1, size (shower%partons)
        new_partons(i)%p => shower%partons(i)%p
    end do
    do i = 1, size (shower%interactions(n_int)%i%partons)
        new_partons(size(shower%partons) + i)%p => &
            shower%interactions(n_int)%i%partons(i)%p
    end do
    deallocate (shower%partons)
else
    allocate (new_partons(1:size(shower%interactions(n_int)%i%partons)))
    do i = 1, size (partons)
        new_partons(i)%p => shower%interactions(n_int)%i%partons(i)%p
    end do
end if

```

```

allocate (shower%partons(1:size (new_partons)))
do i = 1, size (new_partons)
  shower%partons(i)%p => new_partons(i)%p
end do
deallocate (new_partons)

<Perform clustering using the CKKW weights>≡
CKKW_CLUSTERING: do
  !!! search for the combination with the highest weight
  wmax = zero
  CKKW_OUTER: do i = 1, size (new_partons)
    CKKW_INNER: do j = i + 1, size (new_partons)
      if (.not. associated (new_partons(i)%p)) cycle
      if (.not. associated (new_partons(j)%p)) cycle
      w = ckkw_pseudo_weights%weights(new_partons(i)%p%ckkwlabel + &
        new_partons(j)%p%ckkwlabel)
      if (w > wmax .or. vanishes(wmax)) then
        wmax = w
        imin = i
        jmin = j
      end if
    end do CKKW_INNER
  end do CKKW_OUTER
  if (wmax > zero) then
    call shower%add_parent (new_partons(imin)%p)
    call parton_set_child (new_partons(imin)%p%parent, &
      new_partons(jmin)%p, 2)
    call parton_set_parent (new_partons(jmin)%p, &
      new_partons(imin)%p%parent)
    prt => new_partons(imin)%p%parent
    prt%nr = shower_get_next_free_nr (shower)
    prt%type = INTERNAL

    prt%momentum = new_partons(imin)%p%momentum + &
      new_partons(jmin)%p%momentum
    prt%t = prt%momentum**2

    !!! auxilliary values for the ckkw matching
    !!! for now, randomly choose the type of the intermediate
    prt%ckkwlabel = new_partons(imin)%p%ckkwlabel + &
      new_partons(jmin)%p%ckkwlabel
    sum = zero
    call shower%rng%generate (random)
    CKKW_TYPE: do i = 0, 4
      if (sum + &
        ckkw_pseudo_weights%weights_by_type(prt%ckkwlabel, i) > &
        random * ckkw_pseudo_weights%weights(prt%ckkwlabel) ) then
        prt%ckkwtype = i
        exit ckkw_type
      end if
      sum = sum + &
        ckkw_pseudo_weights%weights_by_type(prt%ckkwlabel, i)
    end do CKKW_TYPE

    !!! TODO -> calculate costheta and store it for

```

```

!!!          later use in generate_ps

if (space_part_norm(prt%momentum) > tiny_10) then
  prtmomentum = prt%momentum
  childmomentum = prt%child1%momentum
  prtmomentum = boost (- prt%get_beta() / &
    sqrt (one - &
      (prt%get_beta ())*2), space_part (prt%momentum) / &
      space_part_norm(prt%momentum)) * prtmomentum
  childmomentum = boost (- prt%get_beta () / &
    sqrt(one - &
      (prt%get_beta ())*2), space_part (prt%momentum) / &
      space_part_norm(prt%momentum)) * childmomentum
  prt%costheta = enclosed_angle_ct(prtmomentum, childmomentum)
else
  prt%costheta = - one
end if

prt%belongstointeraction = .true.
prt%belongstoFSR = &
  new_partons(imin)%p%belongstoFSR .and. &
  new_partons(jmin)%p%belongstoFSR

nullify (new_partons(imin)%p)
nullify (new_partons(jmin)%p)
new_partons(imin)%p => prt
else
  exit CKKW_CLUSTERING
end if
end do CKKW_CLUSTERING

(Perform clustering in the usual way)≡
CLUSTERING: do
  !!! search for the partons to be clustered together
  ymin = zero
  OUTER: do i = 1, size (new_partons)
    INNER: do j = i + 1, size (new_partons)
      !!! calculate the jet measure
      if (.not.associated (new_partons(i)%p)) cycle INNER
      if (.not.associated (new_partons(j)%p)) cycle INNER
      !if (.not. shower_clustering_allowed &
        !(shower, new_partons, i,j)) &
        !cycle inner
      !!! Durham jet-measure ! don't care about constants
      y = min (new_partons(i)%p%momentum%p(0), &
        new_partons(j)%p%momentum%p(0)) * &
        (one - enclosed_angle_ct &
          (new_partons(i)%p%momentum, &
            new_partons(j)%p%momentum))
      if (y < ymin .or. vanishes(ymin)) then
        ymin = y
        imin = i
        jmin = j
      end if
    end do INNER
  end do OUTER

```

```

end do OUTER
if (ymin > zero) then
  call shower%add_parent (new_partons(imin)%p)
  call parton_set_child &
    (new_partons(imin)%p%parent, new_partons(jmin)%p, 2)
  call parton_set_parent &
    (new_partons(jmin)%p, new_partons(imin)%p%parent)
  prt => new_partons(imin)%p%parent
  prt%nr = shower_get_next_free_nr (shower)
  prt%type = INTERNAL

  prt%momentum = new_partons(imin)%p%momentum + &
    new_partons(jmin)%p%momentum
  prt%t = prt%momentum**2
  !!! TODO -> calculate costheta and store it for
  !!!      later use in generate_ps

  if (space_part_norm(prt%momentum) > tiny_10) then
    prtmomentum = prt%momentum
    childmomentum = prt%child1%momentum
    prtmomentum = boost (- prt%get_beta () / sqrt(one - &
      (prt%get_beta ())**2), space_part(prt%momentum) / &
      space_part_norm(prt%momentum)) * prtmomentum
    childmomentum = boost (- prt%get_beta() / &
      sqrt(one - &
      (prt%get_beta ())**2), space_part(prt%momentum) / &
      space_part_norm(prt%momentum)) * childmomentum
    prt%costheta = enclosed_angle_ct (prtmomentum, childmomentum)
  else
    prt%costheta = - one
  end if

  prt%belongstointeraction = .true.
  nullify (new_partons(imin)%p)
  nullify (new_partons(jmin)%p)
  new_partons(imin)%p => prt
else
  exit CLUSTERING
end if
end do CLUSTERING

(Procedures of shower_add_interaction_2ton_CKKW)≡
recursive subroutine transfer_pointers (destiny, start, prt)
  type(parton_pointer_t), dimension(:), allocatable :: destiny
  integer, intent(inout) :: start
  type(parton_t), pointer :: prt
  destiny(start)%p => prt
  start = start + 1
  if (associated (prt%child1)) then
    call transfer_pointers (destiny, start, prt%child1)
  end if
  if (associated (prt%child2)) then
    call transfer_pointers (destiny, start, prt%child2)
  end if
end subroutine transfer_pointers

```

```

<Procedures of shower_add_interaction_2ton_CKKW>+≡
recursive function get_starting_scale (prt) result (scale)
  type(parton_t), pointer :: prt
  real(default) :: scale
  scale = huge (scale)
  if (associated (prt%child1) .and. associated (prt%child2)) then
    scale = min(scale, prt%t)
  end if
  if (associated (prt%child1)) then
    scale = min (scale, get_starting_scale (prt%child1))
  end if
  if (associated (prt%child2)) then
    scale = min (scale, get_starting_scale (prt%child2))
  end if
end function get_starting_scale

```

```

<Procedures of shower_add_interaction_2ton_CKKW>+≡
recursive subroutine set_starting_scale (prt, scale)
  type(parton_t), pointer :: prt
  real(default) :: scale
  if (prt%type /= INTERNAL) then
    if (scale > prt%settings%d_min_t + prt%mass_squared ()) then
      prt%t = scale
    else
      prt%t = prt%mass_squared ()
      call prt%set_simulated ()
    end if
  end if
  if (associated (prt%child1)) then
    call set_starting_scale (prt%child1, scale)
  end if
  if (associated (prt%child2)) then
    call set_starting_scale (prt%child2, scale)
  end if
end subroutine set_starting_scale

```

```

<Shower core: shower: TBP>+≡
procedure :: simulate_no_isr_shower => shower_simulate_no_isr_shower

```

```

<Shower core: procedures>+≡
subroutine shower_simulate_no_isr_shower (shower)
  class(shower_t), intent(inout) :: shower
  integer :: i, j
  type(parton_t), pointer :: prt
  do i = 1, size (shower%interactions)
    do j = 1, 2
      prt => shower%interactions(i)%i%partons(j)%p
      if (associated (prt%initial)) then
        !!! for virtuality ordered: remove unneeded partons
        if (associated (prt%parent)) then
          if (.not. prt%parent%is_proton ()) then
            if (associated (prt%parent%parent)) then

```



```

        if (.not. prt%parent%is_proton ()) then
            call shower_remove_parton_from_partons &
                (shower, prt%parent%parent)
        end if
    end if
    call shower_remove_parton_from_partons &
        (shower, prt%parent)
    end if
end if
call parton_set_parent (prt, prt%initial)
call parton_set_child (prt%initial, prt, 1)
if (associated (prt%initial%child2)) then
    call shower_remove_parton_from_partons &
        (shower, prt%initial%child2)
    deallocate (prt%initial%child2)
end if
call shower%add_child (prt%initial, 2)
end if
end do
end do
end subroutine shower_simulate_no_isr_shower

```

(Shower core: shower: TBP)+≡
 procedure :: simulate_no_fsr_shower => shower_simulate_no_fsr_shower

(Shower core: procedures)+≡
 subroutine shower_simulate_no_fsr_shower (shower)
 class(shower_t), intent(inout) :: shower
 integer :: i, j
 type(parton_t), pointer :: prt
 do i = 1, size (shower%interactions)
 do j = 3, size (shower%interactions(i)%i%partons)
 prt => shower%interactions(i)%i%partons(j)%p
 call prt%set_simulated ()
 prt%scale = zero
 prt%t = prt%mass_squared ()
 end do
 end do
 end subroutine shower_simulate_no_fsr_shower

(Shower core: procedures)+≡
 subroutine swap_pointers (prtp1, prtp2)
 type(parton_pointer_t), intent(inout) :: prtp1, prtp2
 type(parton_pointer_t) :: prtptemp
 prtptemp%p => prtp1%p
 prtp1%p => prtp2%p
 prtp2%p => prtptemp%p
 end subroutine swap_pointers

This removes emitted timelike partons.

(Shower core: procedures)+≡
 recursive subroutine shower_remove_parton_from_partons (shower, prt)
 type(shower_t), intent(inout) :: shower

```

type(parton_t), pointer :: prt
integer :: i
if (.not. prt%belongstoFSR .and. associated (prt%child2)) then
    call shower_remove_parton_from_partons_recursive (shower, prt%child2)
end if
do i = 1, size (shower%partons)
    if (associated (shower%partons(i)%p, prt)) then
        shower%partons(i)%p => null()
        exit
    end if
    if (ENSURE) then
        if (i == size (shower%partons)) then
            call msg_error ("shower_remove_parton_from_partons: parton&
                &to be removed not found")
            stop 1
        end if
    end if
end do
end subroutine shower_remove_parton_from_partons

```

This removes the parton `prt` and all its children.

(Shower core: procedures)+≡

```

recursive subroutine shower_remove_parton_from_partons_recursive (shower, prt)
type(shower_t), intent(inout) :: shower
type(parton_t), pointer :: prt
if (associated (prt%child1)) then
    call shower_remove_parton_from_partons_recursive (shower, prt%child1)
    deallocate (prt%child1)
end if
if (associated (prt%child2)) then
    call shower_remove_parton_from_partons_recursive (shower, prt%child2)
    deallocate (prt%child2)
end if
call shower_remove_parton_from_partons (shower, prt)
end subroutine shower_remove_parton_from_partons_recursive

```

(Shower core: shower: TBP)+≡

```

procedure :: sort_partons => shower_sort_partons

```

(Shower core: procedures)+≡

```

subroutine shower_sort_partons (shower)
class(shower_t), intent(inout) :: shower
integer :: i, j, maxsort, size_partons
logical :: changed
if (DEBUG_WHIZ_SHOWER) print *, "D: shower_sort_partons"
if (.not. allocated (shower%partons)) return
size_partons = size (shower%partons)
maxsort = 0
do i = 1, size_partons
    if (associated (shower%partons(i)%p)) maxsort = i
end do
if (signal_is_pending ()) return
size_partons = size (shower%partons)
if (size_partons <= 1) return

```

```

do i = 1, maxsort
  if (.not. associated (shower%partons(i)%p)) cycle
  if (.not. shower%settings%isr_pt_ordered) then
    !!! set unsimulated ISR partons to be "typeless" to prevent
    !!! influences from "wrong" masses
    if (.not. shower%partons(i)%p%belongstoFSR .and. &
        .not. shower%partons(i)%p%simulated .and. &
        .not. shower%partons(i)%p%belongstointeraction) then
      shower%partons(i)%p%type = 0
    end if
  end if
end do
if (signal_is_pending ()) return
!!! Just a Bubblesort
!!! Different algorithms needed for t-ordered and pt^2-ordered shower
!!! Pt-ordered:
if (shower%settings%isr_pt_ordered) then
  OUTERDO_PT: do i = 1, maxsort - 1
    changed = .false.
    INNERDO_PT: do j = 1, maxsort - i
      if (.not. associated (shower%partons(j + 1)%p)) cycle
      if (.not. associated (shower%partons(j)%p)) then
        !!! change if j + 1 is associated and j is not
        call swap_pointers (shower%partons(j), shower%partons(j + 1))
        changed = .true.
      else if (shower%partons(j)%p%scale < &
        shower%partons(j + 1)%p%scale) then
        call swap_pointers (shower%partons(j), shower%partons(j + 1))
        changed = .true.
      else if (nearly_equal(shower%partons(j)%p%scale, &
        shower%partons(j + 1)%p%scale)) then
        if (shower%partons(j)%p%nr > shower%partons(j + 1)%p%nr) then
          call swap_pointers (shower%partons(j), shower%partons(j + 1))
          changed = .true.
        end if
      end if
    end do INNERDO_PT
    if (.not. changed) exit OUTERDO_PT
  end do outerdo_pt
!!! |t|-ordered
else
  OUTERDO_T: do i = 1, maxsort - 1
    changed = .false.
    INNERDO_T: do j = 1, maxsort - i
      if (.not. associated (shower%partons(j + 1)%p)) cycle
      if (.not. associated (shower%partons(j)%p)) then
        !!! change if j+1 is associated and j isn't
        call swap_pointers (shower%partons(j), shower%partons(j + 1))
        changed = .true.
      else if (.not. shower%partons(j)%p%belongstointeraction .and. &
        shower%partons(j + 1)%p%belongstointeraction) then
        !!! move partons belonging to the interaction to the front
        call swap_pointers (shower%partons(j), shower%partons(j + 1))
        changed = .true.
      end if
    end do INNERDO_T
  end do OUTERDO_T
end if

```

```

else if (.not. shower%partons(j)%p%belongstointeraction .and. &
.not. shower%partons(j + 1)%p%belongstointeraction ) then
if (abs (shower%partons(j)%p%t) - &
shower%partons(j)%p%mass_squared () < &
abs(shower%partons(j + 1)%p%t) - &
shower%partons(j + 1)%p%mass_squared ()) then
call swap_pointers (shower%partons(j), shower%partons(j + 1))
changed = .true.
else
if (nearly_equal(abs (shower%partons(j)%p%t) - &
shower%partons(j)%p%mass_squared (), &
abs(shower%partons(j + 1)%p%t) - &
shower%partons(j + 1)%p%mass_squared ())) then
if (shower%partons(j)%p%nr > &
shower%partons(j + 1)%p%nr) then
call swap_pointers (shower%partons(j), &
shower%partons(j + 1))
changed = .true.
end if
end if
end if
end if
end do INNERDO_T
if (.not. changed) exit OUTERDO_T
end do OUTERDO_T
end if
if (signal_is_pending ()) return
if (DEBUG_WHIZ_SHOWER) print *, "D: shower_sort_partons: finished"
end subroutine shower_sort_partons

```

Creation and finalization. Note that we do not overwrite PDF data.

```

<Shower core: shower: TBP>+≡
  procedure :: create => shower_create

<Shower core: procedures>+≡
  subroutine shower_create (shower)
    class(shower_t), intent(inout), target :: shower
    shower%next_free_nr = 1
    shower%next_color_nr = 1
    if (ENSURE) then
      if (allocated (shower%interactions)) then
        call msg_bug ("Shower: creating new shower while old one " // &
          "is still associated (interactions)")
      end if
      if (allocated (shower%partons)) then
        call msg_bug ("Shower: creating new shower while old one " // &
          "is still associated (partons)")
      end if
    end if
    treat_light_quarks_massless = .true.
    treat_duscb_quarks_massless = .false.
    shower%valid = .true.
  end subroutine shower_create

```

Deallocate the interaction pointers.

```

<Shower core: shower: TBP>+=
  procedure :: final => shower_final

<Shower core: procedures>+=
  subroutine shower_final (shower)
    class(shower_t), intent(inout) :: shower
    integer :: i
    if (.not. allocated (shower%interactions)) return
    do i = 1, size (shower%interactions)
      if (allocated (shower%interactions(i)%i%partons)) &
        deallocate (shower%interactions(i)%i%partons)
      deallocate (shower%interactions(i)%i)
    end do
    deallocate (shower%interactions)
    deallocate (shower%partons)
  end subroutine shower_final

```

Bookkeeping functions.

```

<Shower core: shower: TBP>+=
  procedure :: get_next_free_nr => shower_get_next_free_nr

<Shower core: procedures>+=
  function shower_get_next_free_nr (shower) result (next_number)
    class(shower_t), intent(inout) :: shower
    integer :: next_number
    next_number = shower%next_free_nr
    shower%next_free_nr = shower%next_free_nr + 1
  end function shower_get_next_free_nr

```

```

<Shower core: shower: TBP>+=
  procedure :: set_next_color_nr => shower_set_next_color_nr

<Shower core: procedures>+=
  subroutine shower_set_next_color_nr (shower, index)
    class(shower_t), intent(inout) :: shower
    integer, intent(in) :: index
    if (index < shower%next_color_nr) then
      call msg_error ("in shower_set_next_color_nr")
    else
      shower%next_color_nr = index
    end if
  end subroutine shower_set_next_color_nr

```

```

<Shower core: shower: TBP>+=
  procedure :: get_next_color_nr => shower_get_next_color_nr

<Shower core: procedures>+=
  function shower_get_next_color_nr (shower) result (next_color)
    class(shower_t), intent(inout) :: shower
    integer :: next_color
    next_color = shower%next_color_nr
    shower%next_color_nr = shower%next_color_nr + 1
  end function shower_get_next_color_nr

```

```

(Shower core: procedures)+≡
subroutine shower_enlarge_partons_array (shower, custom_length)
  type(shower_t), intent(inout) :: shower
  integer, intent(in), optional :: custom_length
  integer :: i, length, oldlength
  type(parton_pointer_t), dimension(:), allocatable :: tmp_partons
  if (DEBUG_WHIZ_SHOWER) print *, "D: shower_enlarge_partons_array"
  if (present(custom_length)) then
    length = custom_length
  else
    length = 10
  end if
  if (ENSURE) then
    if (length < 1) then
      call msg_bug ("Shower: no parton_pointers added in shower%partons")
    end if
  end if
  if (allocated (shower%partons)) then
    oldlength = size (shower%partons)
    allocate (tmp_partons(1:oldlength))
    do i = 1, oldlength
      tmp_partons(i)%p => shower%partons(i)%p
    end do
    deallocate (shower%partons)
  else
    oldlength = 0
  end if
  allocate (shower%partons(1:oldlength + length))
  do i = 1, oldlength
    shower%partons(i)%p => tmp_partons(i)%p
  end do
  do i = oldlength + 1, oldlength + length
    shower%partons(i)%p => null()
  end do
end subroutine shower_enlarge_partons_array

```

```

(Shower core: shower: TBP)+≡
procedure :: add_child => shower_add_child

```

```

(Shower core: procedures)+≡
subroutine shower_add_child (shower, prt, child)
  class(shower_t), intent(inout) :: shower
  type(parton_t), pointer :: prt
  integer, intent(in) :: child
  integer :: i, lastfree
  type(parton_pointer_t) :: newprt
  if (child /= 1 .and. child /= 2) then
    call msg_bug ("Shower: Adding child in nonexisting place")
  end if
  allocate (newprt%p)
  newprt%p%nr = shower%get_next_free_nr ()
  !!! add new parton as child
  if (child == 1) then
    prt%child1 => newprt%p
  end if
end subroutine shower_add_child

```

```

else
    prt%child2 => newprt%p
end if
newprt%p%parent => prt
newprt%p%interactionnr = prt%interactionnr
!!! add new parton to shower%partons list
if (associated (shower%partons (size(shower%partons))%p)) then
    call shower_enlarge_partons_array (shower)
end if
!!! find last free pointer and let it point to the new parton
lastfree = 0
do i = size (shower%partons), 1, -1
    if (.not. associated (shower%partons(i)%p)) then
        lastfree = i
    end if
end do
if (lastfree == 0) then
    call msg_bug ("Shower: no free pointers found")
end if
shower%partons(lastfree)%p => newprt%p
end subroutine shower_add_child

```

<Shower core: shower: TBP>+≡

```

procedure :: add_parent => shower_add_parent

```

<Shower core: procedures>+≡

```

subroutine shower_add_parent (shower, prt)
class(shower_t), intent(inout) :: shower
type(parton_t), intent(inout), target :: prt
integer :: i, lastfree
type(parton_pointer_t) :: newprt
if (DEBUG_WHIZ_SHOWER) print *, "D: shower_add_parent: for parton ", prt%nr
allocate (newprt%p)
newprt%p%nr = shower%get_next_free_nr ()
!!! add new parton as parent
newprt%p%child1 => prt
prt%parent => newprt%p
newprt%p%interactionnr = prt%interactionnr
!!! add new parton to shower%partons list
if (.not. allocated (shower%partons) .or. &
    associated (shower%partons(size(shower%partons))%p)) then
    call shower_enlarge_partons_array (shower)
end if
!!! find last free pointer and let it point to the new parton
lastfree = 0
do i = size(shower%partons), 1, -1
    if (.not. associated (shower%partons(i)%p)) then
        lastfree = i
    end if
end do
if (ENSURE) then
    if (lastfree == 0) then
        call msg_bug ("Shower: no free pointers found")
    end if

```

```

end if
shower%partons(lastfree)%p => newprt%p
end subroutine shower_add_parent

```

For debugging:

```

(Shower core: procedures)+≡
pure function shower_get_total_momentum (shower) result (mom)
  type(shower_t), intent(in) :: shower
  type(vector4_t) :: mom
  integer :: i
  if (.not. allocated (shower%partons)) return
  mom = vector4_null
  do i = 1, size (shower%partons)
    if (.not. associated (shower%partons(i)%p)) cycle
    if (shower%partons(i)%p%is_final ()) then
      mom = mom + shower%partons(i)%p%momentum
    end if
  end do
end function shower_get_total_momentum

```

Count the number of partons by going through `shower%partons` whereby you can require a minimum energy `mine` and specify whether to `include_remnants`, which is done if not given.

```

(Shower core: shower: TBP)+≡
procedure :: get_nr_of_partons => shower_get_nr_of_partons

(Shower core: procedures)+≡
function shower_get_nr_of_partons (shower, mine, &
  include_remnants, no_hard_prts, only_colored) result (nr)
  class(shower_t), intent(in) :: shower
  real(default), intent(in), optional :: mine
  logical, intent(in), optional :: include_remnants, no_hard_prts, &
    only_colored
  logical :: no_hard, only_col, include_rem
  integer :: nr, i
  nr = 0
  no_hard = .false.; if (present (no_hard_prts)) &
    no_hard = no_hard_prts
  only_col = .false.; if (present (only_colored)) &
    only_col = only_colored
  include_rem = .true.; if (present (include_remnants)) &
    include_rem = include_remnants
  do i = 1, size (shower%partons)
    if (.not. associated (shower%partons(i)%p)) cycle
    associate (prt => shower%partons(i)%p)
      if (.not. prt%is_final ()) cycle
      if (present (only_colored)) then
        if (only_col) then
          if (.not. prt%is_colored ()) cycle
        else
          if (prt%is_colored ()) cycle
        end if
      end if
    end if
  end do
end function

```



```

        if (no_hard) then
            if (shower%partons(i)%p%belongstointeraction) cycle
        end if
        if (.not. include_rem) then
            if (prt%type == BEAM_REMNANT) cycle
        end if
        if (present(mine)) then
            if (prt%momentum%p(0) < mine) cycle
        end if
        nr = nr + 1
    end associate
end do
end function shower_get_nr_of_partons

```

(Shower core: procedures)+≡

```

function shower_get_nr_of_final_colored_ME_partons (shower) result (nr)
    type(shower_t), intent(in) :: shower
    integer :: nr
    integer :: i, j
    type(parton_t), pointer :: prt
    nr = 0
    do i = 1, size (shower%interactions)
        do j = 1, size (shower%interactions(i)%i%partons)
            prt => shower%interactions(i)%i%partons(j)%p
            if (.not. associated (prt)) cycle
            if (.not. prt%is_colored ()) cycle
            if (prt%belongstointeraction .and. prt%belongstoFSR .and. &
                (prt%type /= INTERNAL)) then
                nr = nr + 1
            end if
        end do
    end do
end function shower_get_nr_of_final_colored_ME_partons

```

(Shower core: shower: TBP)+≡

```

procedure :: get_final_colored_ME_partons => &
    shower_get_final_colored_ME_partons

```

(Shower core: procedures)+≡

```

subroutine shower_get_final_colored_ME_partons (shower, partons)
    class(shower_t), intent(in) :: shower
    type(parton_pointer_t), dimension(:), allocatable, intent(inout) :: partons
    integer :: i, j, index, s
    type(parton_t), pointer :: prt
    if (allocated(partons)) deallocate(partons)
    s = shower_get_nr_of_final_colored_ME_partons (shower)
    if (s == 0) return
    allocate (partons(1:s))
    index = 0
    do i = 1, size (shower%interactions)
        do j = 1, size (shower%interactions(i)%i%partons)
            prt => shower%interactions(i)%i%partons(j)%p
            if (.not. associated (prt)) cycle
            if (.not. prt%is_colored ()) cycle

```

```

        if (prt%belongstointeraction .and. prt%belongstoFSR .and. &
            (prt%type /= INTERNAL)) then
            index = index + 1
            partons(index)%p => prt
        end if
    end do
end do
end subroutine shower_get_final_colored_ME_partons

```

(Shower core: procedures)+≡

```

recursive function interaction_fsr_is_finished_for_parton &
    (prt) result (finished)
    type(parton_t), intent(in) :: prt
    logical :: finished
    if (prt%belongstoFSR) then
        !!! FSR partons
        if (associated (prt%child1)) then
            finished = interaction_fsr_is_finished_for_parton (prt%child1) &
                .and. interaction_fsr_is_finished_for_parton (prt%child2)
        else
            finished = prt%t <= prt%mass_squared ()
        end if
    else
        !!! search for emitted timelike partons in ISR shower
        if (.not. associated (prt%initial)) then
            !!! no initial -> no ISR
            finished = .true.
        else if (.not. associated (prt%parent)) then
            finished = .false.
        else
            if (.not. prt%parent%is_proton ()) then
                if (associated (prt%child2)) then
                    finished = interaction_fsr_is_finished_for_parton (prt%parent) .and. &
                        interaction_fsr_is_finished_for_parton (prt%child2)
                else
                    finished = interaction_fsr_is_finished_for_parton (prt%parent)
                end if
            else
                if (associated (prt%child2)) then
                    finished = interaction_fsr_is_finished_for_parton (prt%child2)
                else
                    !!! only second partons can come here -> if that happens FSR
                    !!! evolution is not existing
                    finished = .true.
                end if
            end if
        end if
    end if
end function interaction_fsr_is_finished_for_parton

```

(Shower core: procedures)+≡

```

function interaction_fsr_is_finished (interaction) result (finished)
    type(shower_interaction_t), intent(in) :: interaction

```

```

logical :: finished
integer :: i
finished = .true.
if (.not. allocated (interaction%partons)) return
do i = 1, size (interaction%partons)
  if (.not. interaction_fsr_is_finished_for_parton &
      (interaction%partons(i)%p)) then
    finished = .false.
    exit
  end if
end do
end function interaction_fsr_is_finished

```

(Shower core: public)+≡

```

public :: shower_interaction_get_s

```

(Shower core: procedures)+≡

```

function shower_interaction_get_s (interaction) result (s)
  type(shower_interaction_t), intent(in) :: interaction
  real(default) :: s
  s = (interaction%partons(1)%p%initial%momentum + &
      interaction%partons(2)%p%initial%momentum)**2
end function shower_interaction_get_s

```

(Shower core: procedures)+≡

```

function shower_fsr_is_finished (shower) result (finished)
  type(shower_t), intent(in) :: shower
  logical :: finished
  integer :: i
  finished = .true.
  if (.not. allocated (shower%interactions)) return
  do i = 1, size(shower%interactions)
    if (.not. interaction_fsr_is_finished (shower%interactions(i)%i)) then
      finished = .false.
      exit
    end if
  end do
end function shower_fsr_is_finished

```

(Shower core: procedures)+≡

```

function shower_isr_is_finished (shower) result (finished)
  type(shower_t), intent(in) :: shower
  logical :: finished
  integer :: i
  type(parton_t), pointer :: prt
  finished = .true.
  if (.not.allocated (shower%partons)) return
  do i = 1, size (shower%partons)
    if (.not. associated (shower%partons(i)%p)) cycle
    prt => shower%partons(i)%p
    if (shower%settings%isr_pt_ordered) then
      if (.not. prt%belongstoFSR .and. .not. prt%simulated &
          .and. prt%scale > zero) then

```

```

        finished = .false.
        exit
    end if
else
    if (.not. prt%belongstoFSR .and. .not. prt%simulated &
        .and. prt%t < zero) then
        finished = .false.
        exit
    end if
end if
end do
end function shower_isr_is_finished

```

(Shower core: procedures) +=

```

subroutine interaction_find_partons_nearest_to_hadron &
    (interaction, prt1, prt2, isr_pt_ordered)
type(shower_interaction_t), intent(in) :: interaction
type(parton_t), pointer :: prt1, prt2
logical, intent(in) :: isr_pt_ordered
prt1 => null ()
prt2 => null ()
prt1 => interaction%partons(1)%p
do
    if (associated (prt1%parent)) then
        if (prt1%parent%is_proton ()) then
            exit
        else if ((.not. isr_pt_ordered .and. .not. prt1%parent%simulated) &
            .or. (isr_pt_ordered .and. .not. prt1%simulated)) then
            exit
        else
            prt1 => prt1%parent
        end if
    else
        exit
    end if
end do
prt2 => interaction%partons(2)%p
do
    if (associated (prt2%parent)) then
        if (prt2%parent%is_proton ()) then
            exit
        else if ((.not. isr_pt_ordered .and. .not. prt2%parent%simulated) &
            .or. (isr_pt_ordered .and. .not. prt2%simulated)) then
            exit
        else
            prt2 => prt2%parent
        end if
    else
        exit
    end if
end do
end subroutine interaction_find_partons_nearest_to_hadron

```

```

(Shower core: shower: TBP)+≡
  procedure :: update_beamremnants => shower_update_beamremnants

(Shower core: procedures)+≡
  subroutine shower_update_beamremnants (shower)
    class(shower_t), intent(inout) :: shower
    type(parton_t), pointer :: hadron, remnant
    integer :: i
    real(default) :: random
    !!! only proton in first interaction !!!
    !!! currently only first beam-remnant will be updated
    do i = 1,2
      if (associated (shower%interactions(1)%i%partons(i)%p%initial)) then
        hadron => shower%interactions(1)%i%partons(i)%p%initial
      else
        cycle
      end if
      remnant => hadron%child2
      if (associated (remnant)) then
        remnant%momentum = hadron%momentum - hadron%child1%momentum
      end if
      !!! generate flavor of the beam-remnant if beam was proton
      if (abs (hadron%type) == PROTON .and. associated (hadron%child1)) then
        if (hadron%child1%is_quark ()) then
          !!! decide if valence (u,d) or sea quark (s,c,b)
          if ((abs (hadron%child1%type) <= 2) .and. &
              (hadron%type * hadron%child1%type > zero)) then
            !!! valence quark
            if (abs (hadron%child1%type) == 1) then
              !!! if d then remaining diquark is uu_1
              remnant%type = sign (UU1, hadron%type)
            else
              call shower%rng%generate (random)
              !!! if u then remaining diquark is ud_0 or ud_1
              if (random < 0.75_default) then
                remnant%type = sign (UD0, hadron%type)
              else
                remnant%type = sign (UD1, hadron%type)
              end if
            end if
          end if
          remnant%c1 = hadron%child1%c2
          remnant%c2 = hadron%child1%c1
        else if ((hadron%type * hadron%child1%type) < zero) then
          !!! antiquark
          if (.not. associated (remnant%child1)) then
            call shower%add_child (remnant, 1)
          end if
          if (.not. associated (remnant%child2)) then
            call shower%add_child (remnant, 2)
          end if
          call shower%rng%generate (random)
          if (random < 0.6666_default) then
            !!! 2/3 into udq + u
            if (abs (hadron%child1%type) == 1) then
              remnant%child1%type = sign (NEUTRON, hadron%type)
            end if
          end if
        end if
      end if
    end do
  end subroutine

```

```

else if (abs (hadron%child1%type) == 2) then
    remnant%child1%type = sign (PROTON, hadron%type)
else if (abs (hadron%child1%type) == 3) then
    remnant%child1%type = sign (SIGMA0, hadron%type)
else if (abs (hadron%child1%type) == 4) then
    remnant%child1%type = sign (SIGMACPLUS, hadron%type)
else if (abs (hadron%child1%type) == 5) then
    remnant%child1%type = sign (SIGMAB0, hadron%type)
end if
remnant%child2%type = sign (2, hadron%type)
else
    !!! 1/3 into uuq + d
    if (abs (hadron%child1%type) == 1) then
        remnant%child1%type = sign (PROTON, hadron%type)
    else if (abs (hadron%child1%type) == 2) then
        remnant%child1%type = sign (DELTAPLUSPLUS, hadron%type)
    else if (abs (hadron%child1%type) == 3) then
        remnant%child1%type = sign (SIGMAPLUS, hadron%type)
    else if (abs (hadron%child1%type) == 4) then
        remnant%child1%type = sign (SIGMACPLUSPLUS, hadron%type)
    else if (abs (hadron%child1%type) == 5) then
        remnant%child1%type = sign (SIGMABPLUS, hadron%type)
    end if
    remnant%child2%type = sign (1, hadron%type)
end if
remnant%c1 = hadron%child1%c2
remnant%c2 = hadron%child1%c1
remnant%child1%c1 = 0
remnant%child1%c2 = 0
remnant%child2%c1 = remnant%c1
remnant%child2%c2 = remnant%c2
else
    !!! sea quark
    if (.not. associated (remnant%child1)) then
        call shower%add_child (remnant, 1)
    end if
    if (.not. associated (remnant%child2)) then
        call shower%add_child (remnant, 2)
    end if
    call shower%rng%generate (random)
    if (random < 0.5_default) then
        !!! 1/2 into usbar + ud_0
        if (abs (hadron%child1%type) == 3) then
            remnant%child1%type = sign (KPLUS, hadron%type)
        else if (abs (hadron%child1%type) == 4) then
            remnant%child1%type = sign (D0, hadron%type)
        else if (abs (hadron%child1%type) == 5) then
            remnant%child1%type = sign (BPLUS, hadron%type)
        end if
        remnant%child2%type = sign (UD0, hadron%type)
    else if (random < 0.6666_default) then
        !!! 1/6 into usbar + ud_1
        if (abs (hadron%child1%type) == 3) then
            remnant%child1%type = sign (KPLUS, hadron%type)

```

```

        else if (abs (hadron%child1%type) == 4) then
            remnant%child1%type = sign (D0, hadron%type)
        else if (abs (hadron%child1%type) == 5) then
            remnant%child1%type = sign (BPLUS, hadron%type)
        end if
        remnant%child2%type = sign (UD1, hadron%type)
    else
        !!! 1/3 into dsbar + uu_1
        if (abs (hadron%child1%type) == 3) then
            remnant%child1%type = sign (K0, hadron%type)
        else if (abs (hadron%child1%type) == 4) then
            remnant%child1%type = sign (DPLUS, hadron%type)
        else if (abs (hadron%child1%type) == 5) then
            remnant%child1%type = sign (B0, hadron%type)
        end if
        remnant%child2%type = sign (UU1, hadron%type)
    end if
    remnant%c1 = hadron%child1%c2
    remnant%c2 = hadron%child1%c1
    remnant%child1%c1 = 0
    remnant%child1%c2 = 0
    remnant%child2%c1 = remnant%c1
    remnant%child2%c2 = remnant%c2
end if
else if (hadron%child1%is_gluon ()) then
    if (.not.associated (remnant%child1)) then
        call shower%add_child (remnant, 1)
    end if
    if (.not.associated (remnant%child2)) then
        call shower%add_child (remnant, 2)
    end if
    call shower%rng%generate (random)
    if (random < 0.5_default) then
        !!! 1/2 into u + ud_0
        remnant%child1%type = sign (2, hadron%type)
        remnant%child2%type = sign (UD0, hadron%type)
    else if (random < 0.6666_default) then
        !!! 1/6 into u + ud_1
        remnant%child1%type = sign (2, hadron%type)
        remnant%child2%type = sign (UD1, hadron%type)
    else
        !!! 1/3 into d + uu_1
        remnant%child1%type = sign (1, hadron%type)
        remnant%child2%type = sign (UU1, hadron%type)
    end if
    remnant%c1 = hadron%child1%c2
    remnant%c2 = hadron%child1%c1
    if (hadron%type > 0) then
        remnant%child1%c1 = remnant%c1
        remnant%child2%c2 = remnant%c2
    else
        remnant%child1%c2 = remnant%c2
        remnant%child2%c1 = remnant%c1
    end if
end if

```

```

end if
remnant%initial => hadron
if (associated (remnant%child1)) then
  remnant%child1%initial => hadron
  remnant%child2%initial => hadron
  !!! don't care about on-shellness for now
  remnant%child1%momentum = 0.5_default * remnant%momentum
  remnant%child2%momentum = 0.5_default * remnant%momentum
  !!! but care about on-shellness for baryons
  if (mod (remnant%child1%type, 100) >= 10) then
    !!! check if the third quark is set -> meson or baryon
    remnant%child1%t = remnant%child1%mass_squared ()
    remnant%child1%momentum = [remnant%child1%momentum%p(0), &
      (remnant%child1%momentum%p(1:3) / &
        remnant%child1%momentum%p(1:3)**1) * &
      sqrt (remnant%child1%momentum%p(0)**2 - remnant%child1%t)]
    remnant%child2%momentum = remnant%momentum &
      - remnant%child1%momentum
  end if
end if
end if
end do
end subroutine shower_update_beamremnants

```

(Shower core: procedures)+≡

```

subroutine interaction_apply_lorentztrafo (interaction, L)
  type(shower_interaction_t), intent(inout) :: interaction
  type(lorentz_transformation_t), intent(in) :: L
  type(parton_t), pointer :: prt
  integer :: i
  !!! ISR part
  do i = 1,2
    prt => interaction%partons(i)%p
    !!! loop over ancestors
    MOTHERS: do
      !!! boost parton
      call parton_apply_lorentztrafo (prt, L)
      if (associated (prt%child2)) then
        !!! boost emitted timelike parton (and daughters)
        call parton_apply_lorentztrafo_recursive (prt%child2, L)
      end if
      if (associated (prt%parent)) then
        if (.not. prt%parent%is_proton ()) then
          prt => prt%parent
        else
          exit
        end if
      else
        exit
      end if
    end do MOTHERS
  end do
  !!! FSR part
  if (associated (interaction%partons(3)%p%parent)) then

```



```

      !!! pseudo Parton-Shower histora has been generated -> find
      !!! mother and go on from there recursively
      prt => interaction%partons(3)%p
      do while (associated (prt%parent))
        prt => prt%parent
      end do
      call parton_apply_lorentztrafo_recursive (prt, L)
    else
      do i = 3, size (interaction%partons)
        call parton_apply_lorentztrafo (interaction%partons(i)%p, L)
      end do
    end if
  end subroutine interaction_apply_lorentztrafo

```

(Shower core: procedures) +=

```

subroutine shower_apply_lorentztrafo (shower, L)
  type(shower_t), intent(inout) :: shower
  type(lorentz_transformation_t), intent(in) :: L
  integer :: i
  do i = 1, size (shower%interactions)
    call interaction_apply_lorentztrafo (shower%interactions(i)%i, L)
  end do
end subroutine shower_apply_lorentztrafo

```

This boosts partons belonging to the interaction to the center-of-mass frame of its partons nearest to the hadron.

(Shower core: procedures) +=

```

subroutine interaction_boost_to_CMframe (interaction, isr_pt_ordered)
  type(shower_interaction_t), intent(inout) :: interaction
  logical, intent(in) :: isr_pt_ordered
  type(vector4_t) :: beta
  type(parton_t), pointer :: prt1, prt2
  call interaction_find_partons_nearest_to_hadron &
    (interaction, prt1, prt2, isr_pt_ordered)
  beta = prt1%momentum + prt2%momentum
  beta = beta / beta%p(0)
  if (ENSURE) then
    if (beta**2 > one) then
      call msg_error ("Shower: boost to CM frame: beta > 1")
      return
    end if
  end if
  if (space_part(beta)**2 > tiny_13) then
    call interaction_apply_lorentztrafo (interaction, &
      boost(space_part(beta)**1 / &
        sqrt (one - space_part(beta)**2), -direction(beta)))
  end if
end subroutine interaction_boost_to_CMframe

```

This boosts every interaction to the center-of-mass-frame of its partons nearest to the hadron.

(Shower core: shower: TBP) +=

```

procedure :: boost_to_CMframe => shower_boost_to_CMframe

```

```

(Shower core: procedures)+≡
subroutine shower_boost_to_CMframe (shower)
  class(shower_t), intent(inout) :: shower
  integer :: i
  do i = 1, size (shower%interactions)
    call interaction_boost_to_CMframe &
      (shower%interactions(i)%i, shower%settings%isr_pt_ordered)
  end do
  ! TODO: (bcn 2015-03-23) this shouldnt be here !
  call shower%update_beamremnants ()
end subroutine shower_boost_to_CMframe

```

This boost all partons so that initial partons have their assigned x -value.

```

(Shower core: shower: TBP)+≡
  procedure :: boost_to_labframe => shower_boost_to_labframe

(Shower core: procedures)+≡
subroutine shower_boost_to_labframe (shower)
  class(shower_t), intent(inout) :: shower
  integer :: i
  do i = 1, size (shower%interactions)
    call interaction_boost_to_labframe &
      (shower%interactions(i)%i, shower%settings%isr_pt_ordered)
  end do
end subroutine shower_boost_to_labframe

```

This boosts all partons so that initial partons have their assigned x -value.

```

(Shower core: procedures)+≡
subroutine interaction_boost_to_labframe (interaction, isr_pt_ordered)
  type(shower_interaction_t), intent(inout) :: interaction
  logical, intent(in) :: isr_pt_ordered
  type(parton_t), pointer :: prt1, prt2
  type(vector3_t) :: beta
  call interaction_find_partons_nearest_to_hadron &
    (interaction, prt1, prt2, isr_pt_ordered)
  if (.not. associated (prt1%initial) .or. .not. &
    associated (prt2%initial)) then
    return
  end if
  !!! transform partons to overall labframe.
  beta = vector3_canonical(3) * &
    ((prt1%x * prt2%momentum%p(0) - &
      prt2%x * prt1%momentum%p(0)) / &
    (prt1%x * prt2%momentum%p(3) - &
      prt2%x * prt1%momentum%p(3)))
  if (beta**1 > tiny_10) &
    call interaction_apply_lorentztrafo (interaction, &
      boost (beta**1 / sqrt(one - beta**2), -direction(beta)))
end subroutine interaction_boost_to_labframe

```

Only rotate to z if initial hadrons are given (and they are assumed to be aligned along the z -axis).

```

(Shower core: procedures)+≡

```

```

subroutine interaction_rotate_to_z (interaction, isr_pt_ordered)
  type(shower_interaction_t), intent(inout) :: interaction
  logical, intent(in) :: isr_pt_ordered
  type(parton_t), pointer :: prt1, prt2
  call interaction_find_partons_nearest_to_hadron &
    (interaction, prt1, prt2, isr_pt_ordered)
  if (associated (prt1%initial)) then
    call interaction_apply_lorentztrafo (interaction, &
      rotation_to_2nd (space_part (prt1%momentum), &
        vector3_canonical(3) * sign (one, &
          prt1%initial%momentum%p(3))))
  end if
end subroutine interaction_rotate_to_z

```

Rotate initial partons to lie along $\pm z$ axis.

```

<Shower core: shower: TBP>+=
  procedure :: rotate_to_z => shower_rotate_to_z

<Shower core: procedures>+=
  subroutine shower_rotate_to_z (shower)
    class(shower_t), intent(inout) :: shower
    integer :: i
    do i = 1, size (shower%interactions)
      call interaction_rotate_to_z &
        (shower%interactions(i)%i, shower%settings%isr_pt_ordered)
    end do
    ! TODO: (bcn 2015-03-23) this shouldnt be here !
    call shower%update_beamremnants ()
  end subroutine shower_rotate_to_z

```

Return if there are no initials, electron-hadron collision not implemented.

```

<Shower core: procedures>+=
  subroutine interaction_generate_primordial_kt &
    (interaction, primordial_kt_width, primordial_kt_cutoff, rng)
    type(shower_interaction_t), intent(inout) :: interaction
    real(default), intent(in) :: primordial_kt_width, primordial_kt_cutoff
    class(rng_t), intent(inout), allocatable :: rng
    type(parton_t), pointer :: had1, had2
    type(vector4_t) :: momenta(2)
    type(vector3_t) :: beta
    real(default) :: pt (2), phi(2)
    real(default) :: shat
    real(default) :: btheta, bphi
    integer :: i
    if (vanishes (primordial_kt_width)) return
    if (.not. associated (interaction%partons(1)%p%initial) .or. &
      .not. associated (interaction%partons(2)%p%initial)) then
      return
    end if
    had1 => interaction%partons(1)%p%initial
    had2 => interaction%partons(2)%p%initial
    !!! copy momenta and energy
    momenta(1) = had1%child1%momentum

```

```

momenta(2) = had2%child1%momentum
GENERATE_PT_PHI: do i = 1, 2
  !!! generate transverse momentum and phi
  GENERATE_PT: do
    call rng%generate (pt (i))
    pt(i) = primordial_kt_width * sqrt(-log(pt(i)))
    if (pt(i) < primordial_kt_cutoff) exit
  end do GENERATE_PT
  call rng%generate (phi (i))
  phi(i) = twopi * phi(i)
end do GENERATE_PT_PHI
!!! adjust momenta
shat = (momenta(1) + momenta(2))*2
momenta(1) = [momenta(1)%p(0), &
  pt(1) * cos(phi(1)), &
  pt(1) * sin(phi(1)), &
  momenta(1)%p(3)]
momenta(2) = [momenta(2)%p(0), &
  pt(2) * cos(phi(2)), &
  pt(2) * sin(phi(2)), &
  momenta(2)%p(3)]
beta = [momenta(1)%p(1) + momenta(2)%p(1), &
  momenta(1)%p(2) + momenta(2)%p(2), zero] / sqrt(shat)
momenta(1) = boost (beta**1 / sqrt(one - beta**2), -direction(beta)) &
  * momenta(1)
bphi = azimuthal_angle (momenta(1))
btheta = polar_angle (momenta(1))
call interaction_apply_lorentztrafo (interaction, &
  rotation (cos(bphi), sin(bphi), 3) * rotation(cos(btheta), &
  sin(btheta), 2) * rotation(cos(-bphi), sin(-bphi), 3))
call interaction_apply_lorentztrafo (interaction, &
  boost (beta**1 / sqrt(one - beta**2), -direction(beta)))
end subroutine interaction_generate_primordial_kt

```

<Shower core: shower: TBP>+≡

```

procedure :: generate_primordial_kt => shower_generate_primordial_kt

```

<Shower core: procedures>+≡

```

subroutine shower_generate_primordial_kt (shower)
  class(shower_t), intent(inout) :: shower
  integer :: i
  do i = 1, size (shower%interactions)
    call interaction_generate_primordial_kt (shower%interactions(i)%i, &
      shower%settings%isr_primordial_kt_width, &
      shower%settings%isr_primordial_kt_cutoff, shower%rng)
  end do
  ! TODO: (bcn 2015-03-23) this shouldnt be here !
  call shower%update_beamremnants ()
end subroutine shower_generate_primordial_kt

```

Output.

<Shower core: procedures>+≡

```

subroutine interaction_write (interaction, unit)

```

```

type(shower_interaction_t), intent(in) :: interaction
integer, intent(in), optional :: unit
integer :: i, u
u = given_output_unit (unit); if (u < 0) return
if (associated (interaction%partons(1)%p)) then
    if (associated (interaction%partons(1)%p%initial)) &
        call interaction%partons(1)%p%initial%write (u)
    end if
if (associated (interaction%partons(2)%p)) then
    if (associated (interaction%partons(2)%p%initial)) &
        call interaction%partons(2)%p%initial%write (u)
    end if
if (allocated (interaction%partons)) then
    do i = 1, size (interaction%partons)
        call interaction%partons(i)%p%write (u)
    end do
end if
write (u, "(A)")
end subroutine interaction_write

```

<Shower core: shower: TBP>+≡

```

procedure :: write => shower_write

```

<Shower core: procedures>+≡

```

subroutine shower_write (shower, unit)
class(shower_t), intent(in) :: shower
integer, intent(in), optional :: unit
integer :: i, u
u = given_output_unit (unit); if (u < 0) return
write (u, "(1x,A)") "-----"
write (u, "(1x,A)") "WHIZARD internal parton shower"
write (u, "(1x,A)") "-----"
call shower%pdf_data%write (u)
write (u, "(3x,A,L1)") "ISR: angular ordered = ", &
    shower%isr_angular_ordered
write (u, "(3x,A,ES19.12)") "ISR: maxz_isr = ", shower%maxz_isr
write (u, "(3x,A,ES19.12)") "ISR: min. energy/timelike emission = ", &
    shower%minenergy_timelike
write (u, "(3x,A,ES19.12)") "ISR: first scale = ", shower%tscalefactor_isr
write (u, "(3x,A,ES19.12)") "ISR: 1st integral suppression factor = ", &
    shower%first_integral_suppression_factor
write (u, "(3x,A,L1)") "ISR: partons only onshell = ", &
    shower%isr_only_onshell_emitted_partons
if (size (shower%interactions) > 0) then
    write (u, "(3x,A)") "Interactions: "
    do i = 1, size (shower%interactions)
        write (u, "(4x,A,I0)") "Interaction number ", i
        if (.not. associated (shower%interactions(i)%i)) then
            call msg_fatal ("Shower: missing interaction in shower")
        end if
        call interaction_write (shower%interactions(i)%i, u)
    end do
else
    write (u, "(3x,A)") "[no interactions in shower]"

```

```

end if
write (u, "(A)")
if (allocated (shower%partons)) then
  write (u, "(5x,A)") "Partons:"
  do i = 1, size (shower%partons)
    if (associated (shower%partons(i)%p)) then
      call shower%partons(i)%p%write (u)
      if (i < size (shower%partons)) then
        if (associated (shower%partons(i + 1)%p)) then
          if (shower%partons(i)%p%belongstointeraction .and. &
              .not. shower%partons(i + 1)%p%belongstointeraction) then
            call write_separator (u)
          end if
        end if
      end if
    end if
  end do
else
  write (u, "(5x,A)") "[no partons in shower]"
end if
write (u, "(4x,A)") "Total Momentum: "
call vector4_write (shower_get_total_momentum (shower))
write (u, "(1x,A,L1)") "ISR finished: ", shower_isr_is_finished (shower)
write (u, "(1x,A,L1)") "FSR finished: ", shower_fsr_is_finished (shower)
end subroutine shower_write

```

We combine the `particle_set` from the hard interaction with the partons of the shower. For simplicity, we do not maintain the mother-daughter-relations of the shower. Hadronic beam_remnants of the old `particle_set` are removed as they are provided, including proper flavor information, by the ISR shower. We assume that beam remnants come after initials such that we don't have to update the MDRs of the hard final state.

```

(Shower core: shower: TBP)+≡
  procedure :: combine_with_particle_set => shower_combine_with_particle_set

(Shower core: procedures)+≡
  subroutine shower_combine_with_particle_set (shower, particle_set, &
      model_in, model_hadrons)
    class(shower_t), intent(in) :: shower
    type(particle_set_t), intent(inout) :: particle_set
    type(particle_t), dimension(:), allocatable :: particles
    integer, dimension(:), allocatable :: hard_colored_ids, &
        shower_partons_ids, incoming_ids, outgoing_ids
    class(model_data_t), intent(in), target :: model_in
    class(model_data_t), intent(in), target :: model_hadrons
    class(model_data_t), pointer :: model
    logical, dimension(:), allocatable :: hard_colored_mask
    integer :: n_shower_partons, n_remnants, i, j
    integer :: n_in, n_out, n_beam, n_tot_old
    if (signal_is_pending ()) return

    if (DEBUG_SHOWER) then
      print *, 'Particle set before replacing'
      call particle_set%write (summary=.true., compressed=.true.)
    end if
  end subroutine shower_combine_with_particle_set

```

```

end if
n_shower_partons = shower%get_nr_of_partons (only_colored = &
                                           .true., no_hard_prts = .true.)
n_remnants = shower%get_nr_of_partons (only_colored = .false., &
                                       no_hard_prts = .true.)
call particle_set%without_hadronic_remnants &
    (particles, n_tot_old, n_shower_partons + n_remnants)
if (DEBUG_SHOWER) then
    print *, 'Particle set without hadronic remnants'
    call particle_set%replace (particles)
    call particle_set%write (summary=.true., compressed=.true.)
end if
call count_and_allocate ()
if (shower%settings%isr_active) then
    call replace_incoming_and_outgoings ()
end if
call set_hard_colored_as_resonant_parents_for_shower ()
call add_to_pset (n_tot_old, .true.)
call add_to_pset (n_tot_old + n_remnants, .false.)
call particle_set%replace (particles)
if (DEBUG_SHOWER) then
    print *, 'Particle set after replacing'
    call particle_set%write (summary=.true., compressed=.true.)
end if

```

contains

<Shower core: shower combine with particle set: procedures>

end subroutine shower_combine_with_particle_set

<Shower core: shower combine with particle set: procedures>≡

```

subroutine count_and_allocate ()
    n_beam = particle_set%get_n_beam ()
    n_in = particle_set%get_n_in ()
    n_out = particle_set%get_n_out ()
    allocate (hard_colored_mask (n_tot_old))
    hard_colored_mask = (particles%get_status () == PRT_INCOMING .or. &
                        particles%get_status () == PRT_OUTGOING) .and. &
                        particles%is_colored ()
    hard_colored_ids = pack ([i, i=1, size (particles)], hard_colored_mask)
    shower_partons_ids = [(n_tot_old + n_remnants + i, i=1, n_shower_partons)]
    incoming_ids = [(n_beam + i, i=1, n_in)]
    outgoing_ids = [(n_tot_old - n_out + i, i=1, n_out)]
    if (DEBUG_SHOWER) then
        print *, 'n_remnants = ', n_remnants
        print *, 'n_tot_old = ', n_tot_old
        print *, 'n_beam = ', n_beam
        print *, 'n_in, n_out = ', n_in, n_out
    end if
end subroutine count_and_allocate

```

<Shower core: shower combine with particle set: procedures>+≡

```

subroutine replace_incoming_and_outgoings ()
  do i = 1, size (shower%interactions)
    if (i > 1) then
      call msg_bug ('shower_combine_with_particle_set assumes 1 interaction')
    end if
    associate (interaction => shower%interactions(i)%i)
      do j = 1, size (interaction%partons)
        if (associated (interaction%partons(j)%p)) then
          call replace_parton_in_particles (j, interaction%partons(j)%p)
        end if
      end do
    end associate
  end do
end subroutine replace_incoming_and_outgoings

```

(Shower core: shower combine with particle set: procedures)+≡

```

subroutine replace_parton_in_particles (j, prt)
  integer, intent(in) :: j
  type(parton_t), intent(in) :: prt
  integer :: idx
  call find_model (model, prt%type, model_in, model_hadrons)
  if (associated (prt%initial)) then
    idx = n_beam + j
    particles(idx) = prt%to_particle (model, from_hard_int=.true.)
    call particles(idx)%set_parents ([prt%initial%nr])
    call particles(idx)%set_children (outgoing_ids)
  else
    idx = n_tot_old - n_out - n_in + j
    particles(idx) = prt%to_particle (model, from_hard_int=.true.)
    call particles(idx)%set_parents (incoming_ids)
  end if
  if (DEBUG_SHOWER) then
    print *, 'idx = ', idx
    call particles(idx)%write()
  end if
end subroutine replace_parton_in_particles

```

(Shower core: shower combine with particle set: procedures)+≡

```

subroutine set_hard_colored_as_resonant_parents_for_shower ()
  do i = 1, n_tot_old
    if (hard_colored_mask (i)) then
      call particles(i)%add_children (shower_partons_ids)
      if (particles(i)%get_status () == PRT_OUTGOING) then
        call particles(i)%set_status (PRT_RESONANT)
      end if
    end if
  end do
end subroutine set_hard_colored_as_resonant_parents_for_shower

```

(Shower core: shower combine with particle set: procedures)+≡

```

subroutine add_to_pset (offset, remnants)
  integer, intent(in) :: offset
  logical, intent(in) :: remnants

```



```

integer :: i, j
j = offset
do i = 1, size (shower%partons)
  if (.not. associated (shower%partons(i)%p)) cycle
  associate (prt => shower%partons(i)%p)
    if (.not. prt%is_final () .or. &
        prt%belongstointeraction) cycle
    if (remnants) then
      if (prt%is_colored ()) cycle
    else
      if (.not. (prt%is_colored ())) cycle
    end if
    j = j + 1
    call find_model (model, prt%type, model_in, model_hadrons)
    particles (j) = prt%to_particle (model)
    if (remnants) then
      call particles(j)%set_parents ([prt%initial%nr])
      call particles(prt%initial%nr)%add_child (j)
    else
      call particles(j)%set_parents (hard_colored_ids)
    end if
  end associate
end do
end subroutine add_to_pset

```

(Shower core: shower: TBP)+=

```

procedure :: write_lhef => shower_write_lhef

```

(Shower core: procedures)+=

```

subroutine shower_write_lhef (shower, unit)
  class(shower_t), intent(in) :: shower
  integer, intent(in), optional :: unit
  integer :: u
  integer :: i
  integer :: c1, c2
  u = given_output_unit (unit); if (u < 0) return
  write(u,'(A)') '<LesHouchesEvents version="1.0">'
  write(u,'(A)') '<-- not a complete lhe file - just one event -->'
  write(u,'(A)') '<event>'
  write(u, *) 2 + shower%get_nr_of_partons (), 1, 1.0, 1.0, 1.0, 1.0
  !!! write incoming partons
  do i = 1, 2
    if (abs (shower%partons(i)%p%type) < 1000) then
      c1 = 0
      c2 = 0
      if (shower%partons(i)%p%is_colored ()) then
        if (shower%partons(i)%p%c1 /= 0) c1 = 500 + shower%partons(i)%p%c1
        if (shower%partons(i)%p%c2 /= 0) c2 = 500 + shower%partons(i)%p%c2
      end if
      write (u,*) shower%partons(i)%p%type, -1, 0, 0, c1, c2, &
        shower%partons(i)%p%momentum%p(1), &
        shower%partons(i)%p%momentum%p(2), &
        shower%partons(i)%p%momentum%p(3), &
        shower%partons(i)%p%momentum%p(0), &

```

```

        shower%partons(i)%p%momentum**2, zero, 9.0
    else
        write (u,*) shower%partons(i)%p%type, -9, 0, 0, 0, 0, &
            shower%partons(i)%p%momentum%p(1), &
            shower%partons(i)%p%momentum%p(2), &
            shower%partons(i)%p%momentum%p(3), &
            shower%partons(i)%p%momentum%p(0), &
            shower%partons(i)%p%momentum**2, zero, 9.0
    end if
end do
!!! write outgoing partons
do i = 3, size (shower%partons)
    if (.not. associated (shower%partons(i)%p)) cycle
    if (.not. shower%partons(i)%p%is_final ()) cycle
    c1 = 0
    c2 = 0
    if (shower%partons(i)%p%is_colored ()) then
        if (shower%partons(i)%p%c1 /= 0) c1 = 500 + shower%partons(i)%p%c1
        if (shower%partons(i)%p%c2 /= 0) c2 = 500 + shower%partons(i)%p%c2
    end if
    write (u,*) shower%partons(i)%p%type, 1, 1, 2, c1, c2, &
        shower%partons(i)%p%momentum%p(1), &
        shower%partons(i)%p%momentum%p(2), &
        shower%partons(i)%p%momentum%p(3), &
        shower%partons(i)%p%momentum%p(0), &
        shower%partons(i)%p%momentum**2, zero, 9.0
end do
write(u,'(A)') '</event>'
write(u,'(A)') '</LesHouchesEvents>'
end subroutine shower_write_lhef

```

(Shower core: procedures)+≡

```

subroutine shower_replace_parent_by_hadron (shower, prt)
    type(shower_t), intent(inout) :: shower
    type(parton_t), intent(inout), target :: prt
    type(parton_t), pointer :: remnant => null()
    if (associated (prt%parent)) then
        call shower_remove_parton_from_partons (shower, prt%parent)
        deallocate (prt%parent)
    end if
    if (.not. associated (prt%initial%child2)) then
        call shower%add_child (prt%initial, 2)
    end if
    prt%parent => prt%initial
    prt%parent%child1 => prt
    ! make other child to be a beam-remnant
    remnant => prt%initial%child2
    remnant%type = BEAM_REMNANT
    remnant%momentum = prt%parent%momentum - prt%momentum
    remnant%x = one - prt%x
    remnant%parent => prt%initial
    remnant%t = zero
end subroutine shower_replace_parent_by_hadron

```

```

(Shower core: procedures)+≡
subroutine shower_get_first_ISR_scale_for_parton (shower, prt, tmax)
  type(shower_t), intent(inout), target :: shower
  type(parton_t), intent(inout), target :: prt
  real(default), intent(in), optional :: tmax
  real(default) :: t, tstep, random, integral, temp1
  real(default) :: temprand
  if (present(tmax)) then
    t = max (max (-shower%tscalefactor_isr * prt%momentum%p(0)**2, &
      -abs(tmax)), prt%t)
  else
    t = max (-shower%tscalefactor_isr * prt%momentum%p(0)**2, prt%t)
  end if
  call shower%rng%generate (random)
  random = -twopi * log(random)
  !!! compare Integral and log(random) instead of random and exp(-Integral)
  random = random / shower%first_integral_suppression_factor
  integral = zero
  call prt%set_simulated (.false.)
  do
    call shower%rng%generate (temprand)
    tstep = max (abs (0.01_default * t) * temprand, 0.1_default * &
      shower%settings%d_min_t)
    if (t + 0.5_default * tstep > - shower%settings%d_min_t) then
      prt%t = prt%mass_squared ()
      call prt%set_simulated ()
      exit
    end if
    prt%t = t + 0.5_default * tstep
    temp1 = integral_over_z_simple (prt, (random - integral) / tstep)
    integral = integral + tstep * temp1
    if (integral > random) then
      prt%t = t + 0.5_default * tstep
      exit
    end if
    t = t + tstep
  end do
  if (prt%t > - shower%settings%d_min_t) then
    call shower_replace_parent_by_hadron (shower, prt)
  end if
contains
function integral_over_z_simple (prt, final) result (integral)
  type(parton_t), intent(inout) :: prt
  real(default), intent(in) :: final
  real(default) :: integral

  real(default), parameter :: zstepfactor = one
  real(default), parameter :: zstepmin = 0.0001_default
  real(default) :: z, zstep, minz, maxz
  real(default) :: pdfsum
  integer :: quark, d_nf

```

```

integral = zero
if (DEBUG_WHIZ_SHOWER) then
  print *, "D: integral_over_z_simple: t = ", prt%t
end if
minz = prt%x
! maxz = maxzz(shat, s, shower%maxz_isr, shower%minenergy_timelike)
maxz = shower%maxz_isr
z = minz
d_nf = shower%settings%max_n_flavors
!!! TODO -> Adapt zstep to structure of divergencies
if (prt%child1%is_gluon ()) then
  !!! gluon coming from g->gg
  do
    call shower%rng%generate (temprand)
    zstep = max(zstepmin, temprand * zstepfactor * z * (one - z))
    zstep = min(zstep, maxz - z)
    integral = integral + zstep * (D_alpha_s_isr ((one - &
      (z + 0.5_default * zstep)) * abs(prt%t), &
      shower%settings) / (abs(prt%t))) * &
      P_ggg (z + 0.5_default * zstep) * &
      shower%get_pdf (prt%initial%type, &
        prt%x / (z + 0.5_default * zstep), abs(prt%t), GLUON)
    if (integral > final) then
      exit
    end if
    z = z + zstep
    if (z >= maxz) then
      exit
    end if
  end do
  !!! gluon coming from q->qg ! correctly implemented yet?
  if (integral < final) then
    z = minz
    do
      call shower%rng%generate (temprand)
      zstep = max(zstepmin, temprand * zstepfactor * z * (one - z))
      zstep = min(zstep, maxz - z)
      pdfsum = zero
      do quark = -d_nf, d_nf
        if (quark == 0) cycle
        pdfsum = pdfsum + shower%get_pdf (prt%initial%type, &
          prt%x / (z + 0.5_default * zstep), abs(prt%t), quark)
      end do
      integral = integral + zstep * (D_alpha_s_isr &
        ((z + 0.5_default * zstep) * abs(prt%t), &
        shower%settings) / (abs(prt%t))) * &
        P_qgg (one - (z + 0.5_default * zstep)) * pdfsum
      if (integral > final) then
        exit
      end if
      z = z + zstep
      if (z >= maxz) then
        exit
      end if
    end do
  end if
end if

```

```

        end do
    end if
else if (prt%child1%is_quark ()) then
    !!! quark coming from q->qg
    do
        call shower%rng%generate(temprand)
        zstep = max(zstepmin, temprand * zstepfactor * z * (one - z))
        zstep = min(zstep, maxz - z)
        integral = integral + zstep * (D_alpha_s_isr ((one - &
            (z + 0.5_default * zstep)) * abs(prt%t), &
            shower%settings) / (abs(prt%t))) * &
            P_qqg (z + 0.5_default * zstep) * &
            shower%get_pdf (prt%initial%type, &
                prt%x / (z + 0.5_default * zstep), abs(prt%t), prt%type)
        if (integral > final) then
            exit
        end if
        z = z + zstep
        if (z >= maxz) then
            exit
        end if
    end do
    !!! quark coming from g->qqbar
    if (integral < final) then
        z = minz
        do
            call shower%rng%generate (temprand)
            zstep = max(zstepmin, temprand * zstepfactor * z*(one - z))
            zstep = min(zstep, maxz - z)
            integral = integral + zstep * (D_alpha_s_isr &
                ((one - (z + 0.5_default * zstep)) * abs(prt%t), &
                shower%settings) / (abs(prt%t))) * &
                P_gqq (z + 0.5_default * zstep) * &
                shower%get_pdf (prt%initial%type, &
                    prt%x / (z + 0.5_default * zstep), abs(prt%t), GLUON)
            if (integral > final) then
                exit
            end if
            z = z + zstep
            if (z >= maxz) then
                exit
            end if
        end do
    end if

    end if
    integral = integral / shower%get_pdf (prt%initial%type, prt%x, &
        abs(prt%t), prt%type)
end function integral_over_z_simple

end subroutine shower_get_first_ISR_scale_for_parton

```

(Shower core: procedures)+≡

```

subroutine shower_prepare_for_simulate_isr_pt (shower, interaction)

```

```

type(shower_t), intent(inout) :: shower
type(shower_interaction_t), intent(inout) :: interaction
real(default) :: s
s = (interaction%partons(1)%p%momentum + &
      interaction%partons(2)%p%momentum)**2
interaction%partons(1)%p%scale = shower%tscalefactor_isr * 0.25_default * s
interaction%partons(2)%p%scale = shower%tscalefactor_isr * 0.25_default * s
end subroutine shower_prepare_for_simulate_isr_pt

```

(Shower core: procedures) +=

```

subroutine shower_prepare_for_simulate_isr_ana_test (shower, prt1, prt2)
  type(shower_t), intent(inout) :: shower
  type(parton_t), intent(inout), target :: prt1, prt2
  type(parton_t), pointer :: prt, prta, prtb
  real(default) :: scale, factor, E
  integer :: i
  if (.not. associated (prt1%initial) .or. .not. associated (prt2%initial)) then
    return
  end if
  scale = - (prt1%momentum + prt2%momentum) ** 2
  call prt1%set_simulated ()
  call prt2%set_simulated ()
  call shower%add_parent (prt1)
  call shower%add_parent (prt2)
  factor = sqrt (energy (prt1%momentum)**2 - scale) / &
    space_part_norm(prt1%momentum)
  prt1%parent%type = prt1%type
  prt1%parent%z = one
  prt1%parent%momentum = prt1%momentum
  prt1%parent%t = scale
  prt1%parent%x = prt1%x
  prt1%parent%initial => prt1%initial
  prt1%parent%belongstoFSR = .false.
  prt1%parent%c1 = prt1%c1
  prt1%parent%c2 = prt1%c2

  prt2%parent%type= prt2%type
  prt2%parent%z = one
  prt2%parent%momentum = prt2%momentum
  prt2%parent%t = scale
  prt2%parent%x = prt2%x
  prt2%parent%initial => prt2%initial
  prt2%parent%belongstoFSR = .false.
  prt2%parent%c1 = prt2%c1
  prt2%parent%c2 = prt2%c2

  do
    call shower_get_first_ISR_scale_for_parton (shower, prt1%parent)
    call shower_get_first_ISR_scale_for_parton (shower, prt2%parent)

    !!! redistribute energy among first partons
    prta => prt1%parent
    prtb => prt2%parent
  end do

```

```

      E = energy (prt1%momentum + prt2%momentum)
      prta%momentum%p(0) = (E**2 - prtb%t + prta%t) / (two * E)
      prtb%momentum%p(0) = E - prta%momentum%p(0)

      exit
    end do

    call prt1%parent%set_simulated ()
    call prt2%parent%set_simulated ()
    !!! rescale momenta
    do i = 1, 2
      if (i == 1) then
        prt => prt1%parent
      else
        prt => prt2%parent
      end if
      factor = sqrt (energy (prt%momentum)**2 - prt%t) &
        / space_part_norm (prt%momentum)
      prt%momentum = vector4_moving (energy (prt%momentum), &
        factor * space_part (prt%momentum))
    end do

    if (prt1%parent%t < zero) then
      call shower%add_parent (prt1%parent)
      prt1%parent%parent%momentum = prt1%parent%momentum
      prt1%parent%parent%t = prt1%parent%t
      prt1%parent%parent%x = prt1%parent%x
      prt1%parent%parent%initial => prt1%parent%initial
      prt1%parent%parent%belongstoFSR = .false.
      call shower%add_child (prt1%parent%parent, 2)
    end if

    if (prt2%parent%t < zero) then
      call shower%add_parent (prt2%parent)
      prt2%parent%parent%momentum = prt2%parent%momentum
      prt2%parent%parent%t = prt2%parent%t
      prt2%parent%parent%x = prt2%parent%x
      prt2%parent%parent%initial => prt2%parent%initial
      prt2%parent%parent%belongstoFSR = .false.
      call shower%add_child (prt2%parent%parent, 2)
    end if

    end subroutine shower_prepare_for_simulate_isr_ana_test

```

(Shower core: procedures) +≡

```

subroutine shower_add_children_of_emitted_timelike_parton (shower, prt)
  type(shower_t), intent(inout) :: shower
  type(parton_t), pointer :: prt

  if (prt%t > prt%mass_squared () + shower%settings%d_min_t) then
    if (prt%is_quark ()) then
      !!! q -> qg
      call shower%add_child (prt, 1)
      prt%child1%type = prt%type
    end if
  end if

```

```

prt%child1%momentum%p(0) = prt%z * prt%momentum%p(0)
prt%child1%t = prt%t
call shower%add_child (prt, 2)
prt%child2%type = GLUON
prt%child2%momentum%p(0) = (one - prt%z) * prt%momentum%p(0)
prt%child2%t = prt%t
else
  if (int (prt%x) > 0) then
    call shower%add_child (prt, 1)
    prt%child1%type = int (prt%x)
    prt%child1%momentum%p(0) = prt%z * prt%momentum%p(0)
    prt%child1%t = prt%t
    call shower%add_child (prt, 2)
    prt%child2%type = -int (prt%x)
    prt%child2%momentum%p(0) = (one - prt%z) * prt%momentum%p(0)
    prt%child2%t = prt%t
  else
    call shower%add_child (prt, 1)
    prt%child1%type = GLUON
    prt%child1%momentum%p(0) = prt%z * prt%momentum%p(0)
    prt%child1%t = prt%t
    call shower%add_child (prt, 2)
    prt%child2%type = GLUON
    prt%child2%momentum%p(0) = (one - prt%z) * prt%momentum%p(0)
    prt%child2%t = prt%t
  end if
end if
end if
end subroutine shower_add_children_of_emitted_timelike_parton

```

(Shower core: procedures)+≡

```

subroutine shower_simulate_children_ana (shower,prt)
  type(shower_t), intent(inout), target :: shower
  type(parton_t), intent(inout) :: prt
  real(default), dimension(1:2) :: t, random, integral
  integer, dimension(1:2) :: gtoqq
  integer :: daughter
  type(parton_t), pointer :: daughterprt
  integer :: n_loop

  if (signal_is_pending ()) return
  gtoqq = 0

  if (DEBUG_WHIZ_SHOWER) print *, "D: shower_simulate_children_ana: for parton " , prt%nr

  if (.not. associated (prt%child1) .or. .not. associated (prt%child2)) then
    call msg_error ("Shower: error in simulate_children_ana: no children.")
    return
  end if

```

(Set beam-remnants and internal partons as simulated)

```

integral = zero

```



```

!!! impose constraints by angular ordering -> cf. (26) of Gaining analytic control
!!! check if no branchings are possible
if (.not. prt%child1%simulated) then
  prt%child1%t = min (prt%child1%t, &
    0.5_default * prt%child1%momentum%p(0)**2 * (one - &
    prt%get_cstheta ()))
  if (.not. associated (prt%child1%settings)) &
    prt%child1%settings => shower%settings
  if (min (prt%child1%t, prt%child1%momentum%p(0)**2) < &
    prt%child1%mass_squared () + &
    prt%child1%settings%d_min_t) then
    prt%child1%t = prt%child1%mass_squared ()
    call prt%child1%set_simulated ()
  end if
end if
if (.not. prt%child2%simulated) then
  prt%child2%t = min (prt%child2%t, &
    0.5_default * prt%child2%momentum%p(0)**2 * (one - &
    prt%get_cstheta ()))
  if (.not. associated (prt%child2%settings)) &
    prt%child2%settings => shower%settings
  if (min (prt%child2%t, prt%child2%momentum%p(0)**2) < &
    prt%child2%mass_squared () + &
    prt%child2%settings%d_min_t) then
    prt%child2%t = prt%child2%mass_squared ()
    call prt%child2%set_simulated ()
  end if
end if

call shower%rng%generate (random)

n_loop = 0
do
  if (signal_is_pending ()) return
  n_loop = n_loop + 1
  if (n_loop > 900) then
    !!! try with massless quarks
    treat_duscb_quarks_massless = .true.
  end if
  if (n_loop > 1000) then
    call shower%write ()
    call msg_message (" simulate_children_ana failed for parton ", prt%nr)
    call msg_error ("BUG: too many loops in simulate_children_ana (?)")
    shower%valid = .false.
    return
  end if

  t(1) = prt%child1%t
  t(2) = prt%child2%t

  !!! check if a branching in the range t(i) to t(i) - tstep(i) occurs

  !!! check for child1
  if (.not. prt%child1%simulated) then

```

```

        call parton_simulate_stept &
            (prt%child1, shower%rng, integral(1), random(1), gtoqq(1))
    end if
    !!! check for child2
    if (.not. prt%child2%simulated) then
        call parton_simulate_stept &
            (prt%child2, shower%rng, integral(2), random(2), gtoqq(2))
    end if

    if (prt%child1%simulated .and. &
        prt%child2%simulated) then
        if (sqrt (prt%t) <= sqrt (prt%child1%t) + sqrt (prt%child2%t)) then
            <Repeat the simulation for the parton with the lower virtuality>
        else
            exit
        end if
    end if
end do

call parton_apply_costheta (prt, shower%rng)

<Add children>
call shower_parton_update_color_connections (shower, prt)
end subroutine shower_simulate_children_ana

<Set beam-remnants and internal partons as simulated>≡
if (HADRON_REMNANT <= abs (prt%type) .and. abs (prt%type) <= HADRON_REMNANT_OCTET) then
    !!! prt is beam-remnant
    call prt%set_simulated ()
    return
end if

!!! check if partons are "internal" -> fixed scale
if (prt%child1%type == INTERNAL) then
    call prt%child1%set_simulated ()
end if
if (prt%child2%type == INTERNAL) then
    call prt%child2%set_simulated ()
end if

<Repeat the simulation for the parton with the lower virtuality>≡
!!! virtuality : t - m**2 (assuming it's not fixed)
if (prt%child1%type == INTERNAL .and. prt%child2%type == INTERNAL) then
    call msg_fatal &
        ("Shower: both partons fixed, but momentum not conserved")
else if (prt%child1%type == INTERNAL) then
    !!! reset child2
    call prt%child2%set_simulated (.false.)
    prt%child2%t = min (prt%child1%t, (sqrt (prt%t) - &
        sqrt (prt%child1%t))**2)
    integral(2) = zero
    call shower%rng%generate (random(2))
else if (prt%child2%type == INTERNAL) then
    ! reset child1

```

```

    call prt%child1%set_simulated (.false.)
    prt%child1%t = min (prt%child2%t, (sqrt (prt%t) - &
        sqrt (prt%child2%t))*2)
    integral(1) = zero
    call shower%rng%generate (random(1))
else if (prt%child1%t - prt%child1%mass_squared () > &
    prt%child2%t - prt%child2%mass_squared ()) then
    !!! reset child2
    call prt%child2%set_simulated (.false.)
    prt%child2%t = min (prt%child1%t, (sqrt (prt%t) - &
        sqrt (prt%child1%t))*2)
    integral(2) = zero
    call shower%rng%generate (random(2))
else
    !!! reset child1 ! TODO choose child according to their t
    call prt%child1%set_simulated (.false.)
    prt%child1%t = min (prt%child2%t, (sqrt (prt%t) - &
        sqrt (prt%child2%t))*2)
    integral(1) = zero
    call shower%rng%generate (random(1))
end if
(Add children)≡
if (.not. associated (prt%child1%settings)) &
    prt%child1%settings => shower%settings
if (.not. associated (prt%child2%settings)) &
    prt%child2%settings => shower%settings
do daughter = 1, 2
    if (signal_is_pending ()) return
    if (daughter == 1) then
        daughterprt => prt%child1
    else
        daughterprt => prt%child2
    end if
    if (daughterprt%t < daughterprt%mass_squared () + &
        daughterprt%settings%d_min_t) then
        cycle
    end if
    if (.not. (daughterprt%is_quark () .or. daughterprt%is_gluon ())) then
        cycle
    end if
    if (daughterprt%is_quark ()) then
        !!! q -> qg
        call shower%add_child (daughterprt, 1)
        daughterprt%child1%type = daughterprt%type
        daughterprt%child1%momentum%p(0) = daughterprt%z * &
            daughterprt%momentum%p(0)
        daughterprt%child1%t = daughterprt%t
        call shower%add_child (daughterprt, 2)
        daughterprt%child2%type = GLUON
        daughterprt%child2%momentum%p(0) = (one - daughterprt%z) * &
            daughterprt%momentum%p(0)
        daughterprt%child2%t = daughterprt%t
    else if (daughterprt%is_gluon ()) then
        if (gtoqq(daughter) > 0) then

```

```

        call shower%add_child (daughterprt, 1)
        daughterprt%child1%type = gtoqq (daughter)
        daughterprt%child1%momentum%p(0) = &
            daughterprt%z * daughterprt%momentum%p(0)
        daughterprt%child1%t = daughterprt%t
        call shower%add_child (daughterprt, 2)
        daughterprt%child2%type = - gtoqq (daughter)
        daughterprt%child2%momentum%p(0) = (one - &
            daughterprt%z) * daughterprt%momentum%p(0)
        daughterprt%child2%t = daughterprt%t
    else
        call shower%add_child (daughterprt, 1)
        daughterprt%child1%type = GLUON
        daughterprt%child1%momentum%p(0) = &
            daughterprt%z * daughterprt%momentum%p(0)
        daughterprt%child1%t = daughterprt%t
        call shower%add_child (daughterprt, 2)
        daughterprt%child2%type = GLUON
        daughterprt%child2%momentum%p(0) = (one - &
            daughterprt%z) * daughterprt%momentum%p(0)
        daughterprt%child2%t = daughterprt%t
    end if
end if
end do

```

The recoiler is `otherprt`. Instead of the random number and the exponential of the integral, we compare the logarithm of the random number and the integral.

(*Shower core: procedures*) +=

```

subroutine shower_isr_step_pt (shower, prt)
    type(shower_t), intent(inout) :: shower
    type(parton_t), target, intent(inout) :: prt
    type(parton_t), pointer :: otherprt

    real(default) :: scale, scalestep
    real(default) :: integral, random, factor
    real(default) :: temprand1, temprand2

    otherprt => shower%find_recoiler (prt)

    scale = prt%scale
    call shower%rng%generate (temprand1)
    call shower%rng%generate (temprand2)
    scalestep = max (abs (scalefactor1 * scale) * temprand1, &
        scalefactor2 * temprand2 * D_Min_scale)
    call shower%rng%generate (random)
    random = - twopi * log(random)
    integral = zero

    if (scale - 0.5_default * scalestep < D_Min_scale) then
        !!! close enough to cut-off scale -> ignore
        prt%scale = zero
        prt%t = prt%mass_squared ()
        call prt%set_simulated ()
    else

```

```

    prt%scale = scale - 0.5_default * scalestep
    factor = scalestep * (D_alpha_s_isr (prt%scale, &
        shower%settings) / (prt%scale * &
        shower%get_pdf (prt%initial%type, prt%x, prt%scale, prt%type)))
    integral = integral + factor * integral_over_z_isr_pt &
        (prt, otherprt, (random - integral) / factor)
    if (integral > random) then
        !!! prt%scale set above and prt%z set in integral_over_z_isr_pt
        call prt%set_simulated ()
        prt%t = - prt%scale / (one - prt%z)
    else
        prt%scale = scale - scalestep
    end if
end if

contains

function integral_over_z_isr_pt (prt, otherprt, final) &
    result (integral)
    type(parton_t), intent(inout) :: prt, otherprt
    real(default), intent(in) :: final
    real(default) :: integral
    real(default) :: mbr, r
    real(default) :: zmin, zmax, z, zstep
    integer :: n_bin
    integer, parameter :: n_total_bins = 100
    real(default) :: quarkpdfsum
    real(default) :: temprand
    integer :: quark, d_nf

    quarkpdfsum = zero
    d_nf = shower%settings%max_n_flavors
    if (DEBUG_WHIZ_SHOWER) then
        print *, "D: integral_over_z_isr_pt: for scale = ", prt%scale
    end if

    integral = zero
    mbr = (prt%momentum + otherprt%momentum)**1
    zmin = prt%x
    zmax = min (one - (sqrt (prt%scale) / mbr) * &
        (sqrt(one + 0.25_default * prt%scale / mbr**2) - &
        0.25_default * sqrt(prt%scale) / mbr), shower%maxz_isr)
    zstep = (zmax - zmin) / n_total_bins

    if (ENSURE) then
        if (zmin > zmax) then
            call msg_bug(" error in integral_over_z_isr_pt: zmin > zmax ")
            integral = zero
        end if
    end if

    !!! divide the range [zmin:zmax] in n_total_bins
    BINS: do n_bin = 1, n_total_bins
        z = zmin + zstep * (n_bin - 0.5_default)

```

```

!!! z-value in the middle of the bin

if (prt%is_gluon ()) then
  QUARKS: do quark = -d_nf, d_nf
    if (quark == 0) cycle quarks
    quarkpdfsum = quarkpdfsum + shower%get_pdf &
      (prt%initial%type, prt%x / z, prt%scale, quark)
  end do QUARKS
  !!! g -> gg or q -> gq
  integral = integral + (zstep / z) * ((P_ggg (z) + &
    P_ggg (one - z)) * shower%get_pdf (prt%initial%type, &
    prt%x / z, prt%scale, GLUON) + P_qqg (one - z) * quarkpdfsum)
else if (prt%is_quark ()) then
  !!! q -> qg or g -> qq
  integral = integral + (zstep / z) * ( P_qqg (z) * &
    shower%get_pdf (prt%initial%type, prt%x / z, prt%scale, &
    prt%type) + &
    P_gqq(z) * shower%get_pdf (prt%initial%type, prt%x / z, &
    prt%scale, GLUON))
else
  ! call msg_fatal ("Bug neither quark nor gluon in" &
  ! // " integral_over_z_isr_pt")
end if
if (integral > final) then
  prt%z = z
  call shower%rng%generate (temprand)
  !!! decide type of father partons
  if (prt%is_gluon ()) then
    if (temprand > (P_qqg (one - z) * quarkpdfsum) / &
      ((P_ggg (z) + P_ggg (one - z)) * shower%get_pdf &
      (prt%initial%type, prt%x / z, prt%scale, GLUON) &
      + P_qqg (one - z) * quarkpdfsum)) then
      !!! gluon => gluon + gluon
      prt%aux_pt = GLUON
    else
      !!! quark => quark + gluon
      !!! decide which quark flavor the parent is
      r = temprand * quarkpdfsum
      WHICH_QUARK: do quark = -d_nf, d_nf
        if (quark == 0) cycle WHICH_QUARK
        if (r > quarkpdfsum - shower%get_pdf (prt%initial%type, &
          prt%x / z, prt%scale, quark)) then
          prt%aux_pt = quark
          exit WHICH_QUARK
        else
          quarkpdfsum = quarkpdfsum - shower%get_pdf &
            (prt%initial%type, prt%x / z, prt%scale, quark)
        end if
      end do WHICH_QUARK
    end if
  end if
else if (prt%is_quark ()) then
  if (temprand > (P_qqg (z) * shower%get_pdf (prt%initial%type, &
    prt%x / z, prt%scale, prt%type)) / &

```

```

        (P_qqg (z) * shower%get_pdf (prt%initial%type, prt%x / z, &
        prt%scale, prt%type) + &
        P_gqq (z) * shower%get_pdf (prt%initial%type, prt%x / z, &
        prt%scale, GLUON))) then
        !!! gluon => quark + antiquark
        prt%aux_pt = GLUON
    else
        !!! quark => quark + gluon
        prt%aux_pt = prt%type
    end if
end if
exit BINS
end if
end do BINS
end function integral_over_z_isr_pt
end subroutine shower_isr_step_pt

```

This function returns a pointer to the parton with the next ISR branching, while FSR branchings are ignored.

```

<Shower core: shower: TBP>+≡
    procedure :: generate_next_isr_branching_veto => &
        shower_generate_next_isr_branching_veto

<Shower core: procedures>+≡
    function shower_generate_next_isr_branching_veto &
        (shower) result (next_brancher)
    class(shower_t), intent(inout) :: shower
    type(parton_pointer_t) :: next_brancher
    integer :: i
    type(parton_t), pointer :: prt
    real(default) :: random
    !!! pointers to branchable partons
    type(parton_pointer_t), dimension(:), allocatable :: partons
    integer :: n_partons
    real(default) :: weight
    real(default) :: temp1, temp2, temp3, E3

    if (signal_is_pending ()) return

    if (shower%settings%isr_pt_ordered) then
        next_brancher = shower%generate_next_isr_branching ()
        return
    end if
    next_brancher%p => null()
    !!! branchable partons
    n_partons = 0
    do i = 1, size (shower%partons)
        prt => shower%partons(i)%p
        if (signal_is_pending ()) return
        if (.not. associated (prt)) cycle
        if (prt%belongstoFSR) cycle
        if (prt%is_final ()) cycle
        if (.not. prt%belongstoFSR .and. prt%simulated) cycle
        n_partons = n_partons + 1
    end do
    next_brancher = partons(n_partons)
end function shower_generate_next_isr_branching_veto

```

```

end do
if (n_partons == 0) then
    return
end if
allocate (partons(1:n_partons))
n_partons = 1
do i = 1, size (shower%partons)
    prt => shower%partons(i)%p
    if (.not. associated (prt)) cycle
    if (prt%belongstoFSR) cycle
    if (prt%is_final ()) cycle
    if (.not. prt%belongstoFSR .and. prt%simulated) cycle
    if (signal_is_pending ()) return
    partons(n_partons)%p => shower%partons(i)%p
    n_partons = n_partons + 1
end do
!!! generate initial trial scales
do i = 1, size (partons)
    if (signal_is_pending ()) return
    call generate_next_trial_scale (partons(i)%p)
end do

do
    !!! search for parton with the highest trial scale
    prt => partons(1)%p
    do i = 1, size (partons)
        if (prt%t >= zero) cycle
        if (abs (partons(i)%p%t) > abs (prt%t)) then
            prt => partons(i)%p
        end if
    end do

    if (prt%t >= zero) then
        next_brancher%p => null()
        exit
    end if
    !!! generate trial z and type of mother prt
    call generate_trial_z_and_typ (prt)

    !!! weight with pdf and alpha_s
    temp1 = (D_alpha_s_isr ((one - prt%z) * abs(prt%t), &
        shower%settings) / sqrt (alphasxpdfmax))
    temp2 = shower%get_xpdf (prt%initial%type, prt%x, prt%t, &
        prt%type) / sqrt (alphasxpdfmax)
    temp3 = shower%get_xpdf (prt%initial%type, prt%child1%x, prt%child1%t, &
        prt%child1%type) / &
        shower%get_xpdf (prt%initial%type, prt%child1%x, prt%t, &
        prt%child1%type)
    ! TODO: (bcn 2015-02-19) ???
    if (temp1 * temp2 * temp3 > one) then
        print *, "weights:", temp1, temp2, temp3
    end if
    weight = (D_alpha_s_isr ((one - prt%z) * abs(prt%t), &
        shower%settings)) * &

```



```

        shower%get_xpdf (prt%initial%type, prt%x, prt%t, prt%type) * &
        shower%get_xpdf (prt%initial%type, prt%child1%x, prt%child1%t, &
        prt%child1%type) / &
        shower%get_xpdf &
        (prt%initial%type, prt%child1%x, prt%t, prt%child1%type)
    if (weight > alphasxpdfmax) then
        print *, "Setting alphasxpdfmax from ", alphasxpdfmax, " to ", weight
        alphasxpdfmax = weight
    end if
    weight = weight / alphasxpdfmax
    call shower%rng%generate (random)
    if (weight < random) then
        !!! discard branching
        call generate_next_trial_scale (prt)
        cycle
    end if
    !!! branching accepted so far
    !!! generate emitted parton
    prt%child2%t = abs(prt%t)
    prt%child2%momentum%p(0) = sqrt (abs(prt%t))
    if (shower%isr_only_onshell_emitted_partons) then
        prt%child2%t = prt%child2%mass_squared ()
    else
        call prt%child2%next_t_ana (shower%rng)
    end if

    if (thetabar (prt, shower%find_recoiler (prt), &
        shower%isr_angular_ordered, E3)) then
        prt%momentum%p(0) = E3
        prt%child2%momentum%p(0) = E3 - prt%child1%momentum%p(0)

        !!! found branching
        call prt%generate_ps_ini (shower%rng)
        next_brancher%p => prt
        call prt%set_simulated ()
        exit
    else
        call generate_next_trial_scale (prt)
        cycle
    end if
end do
if (.not. associated (next_brancher%p)) then
    !!! no further branching found -> all partons emitted by hadron
    print *, "--all partons emitted by hadrons---"
    do i = 1, size(partons)
        call shower_replace_parent_by_hadron (shower, partons(i)%p%child1)
    end do
end if
!!! some bookkeeping
call shower%sort_partons ()
! call shower%boost_to_CMframe ()      ! really necessary?
! call shower%rotate_to_z ()          ! really necessary?
contains

```

```

subroutine generate_next_trial_scale (prt)
  type(parton_t), pointer, intent(inout) :: prt
  real(default) :: random, F
  real(default) :: zmax = 0.99_default !! ??
  call shower%rng%generate (random)
  F = one    !!! TODO
  F = alphaspdfmax / (two * pi)
  if (prt%child1%is_quark ()) then
    F = F * (integral_over_P_gqq (prt%child1%x, zmax) + &
             integral_over_P_qqg (prt%child1%x, zmax))
  else if (prt%child1%is_gluon ()) then
    F = F * (integral_over_P_ggg (prt%child1%x, zmax) + &
             two * shower%settings%max_n_flavors * &
             integral_over_P_qqg (one - zmax, one - prt%child1%x))
  else
    call msg_bug("neither quark nor gluon in generate_next_trial_scale")
  end if
  F = F / shower%get_xpdf (prt%child1%initial%type, prt%child1%x, &
                          prt%child1%t, prt%child1%type)
  prt%t = prt%t * random**(one / F)
  if (abs (prt%t) - prt%mass_squared () < &
      prt%settings%d_min_t) then
    prt%t = prt%mass_squared ()
  end if
end subroutine generate_next_trial_scale

subroutine generate_trial_z_and_typ (prt)
  type(parton_t), pointer, intent(inout) :: prt
  real(default) :: random
  real(default) :: z, zstep, zmin, integral
  real(default) :: zmax = 0.99_default !! ??
  if (DEBUG_WHIZ_SHOWER) print *, "D: generate generate_trial_z_and_typ"
  call shower%rng%generate (random)
  integral = zero
  !!! decide which branching a->bc occurs
  if (prt%child1%is_quark ()) then
    if (random < integral_over_P_qqg (prt%child1%x, zmax) / &
        (integral_over_P_qqg (prt%child1%x, zmax) + &
         integral_over_P_gqq (prt%child1%x, zmax))) then
      prt%type = prt%child1%type
      prt%child2%type = GLUON
      integral = integral_over_P_qqg (prt%child1%x, zmax)
    else
      prt%type = GLUON
      prt%child2%type = - prt%child1%type
      integral = integral_over_P_gqq (prt%child1%x, zmax)
    end if
  else if (prt%child1%is_gluon ()) then
    if (random < integral_over_P_ggg (prt%child1%x, zmax) / &
        (integral_over_P_ggg (prt%child1%x, zmax) + two * &
         shower%settings%max_n_flavors * &
         integral_over_P_qqg (one - zmax, &
                              one - prt%child1%x))) then
      prt%type = GLUON
    end if
  end if
end subroutine generate_trial_z_and_typ

```

```

    prt%child2%type = GLUON
    integral = integral_over_P_ggg (prt%child1%x, zmax)
else
    call shower%rng%generate (random)
    prt%type = 1 + floor(random * shower%settings%max_n_flavors)
    call shower%rng%generate (random)
    if (random > 0.5_default) prt%type = - prt%type
    prt%child2%type = prt%type
    integral = integral_over_P_qqg (one - zmax, &
        one - prt%child1%x)
end if
else
    call msg_bug("neither quark nor gluon in generate_next_trial_scale")
end if
!!! generate the z-value
!!! z between prt%child1%x and zmax
! prt%z = one - random * (one - prt%child1%x)      ! TODO

call shower%rng%generate (random)
zmin = prt%child1%x
zstep = max(0.1_default, 0.5_default * (zmax - zmin))
z = zmin
if (zmin > zmax) then
    print *, " zmin = ", zmin, " zmax = ", zmax
    call msg_fatal ("Shower: zmin greater than zmax")
end if
!!! procedure pointers would be helpful here
if (prt%is_quark () .and. prt%child1%is_quark ()) then
    do
        zstep = min(zstep, 0.5_default * (zmax - z))
        if (abs(zstep) < 0.00001) exit
        if (integral_over_P_qqg (zmin, z) < random * integral) then
            if (integral_over_P_qqg (zmin, min(z + zstep, zmax)) &
                < random * integral) then
                z = min (z + zstep, zmax)
                cycle
            else
                zstep = zstep * 0.5_default
                cycle
            end if
        end if
    end do
else if (prt%is_quark () .and. prt%child1%is_gluon ()) then
    do
        zstep = min(zstep, 0.5_default * (zmax - z))
        if (abs(zstep) < 0.00001) exit
        if (integral_over_P_qqg (zmin, z) < random * integral) then
            if (integral_over_P_qqg (zmin, min(z + zstep, zmax)) &
                < random * integral) then
                z = min(z + zstep, zmax)
                cycle
            else
                zstep = zstep * 0.5_default
                cycle
            end if
        end if
    end do

```

```

        end if
    end if
end do
else if (prt%is_gluon () .and. prt%child1%is_quark ()) then
do
    zstep = min(zstep, 0.5_default * (zmax - z))
    if (abs (zstep) < 0.00001) exit
    if (integral_over_P_gqq (zmin, z) < random * integral) then
        if (integral_over_P_gqq (zmin, min(z + zstep, zmax)) &
            < random * integral) then
            z = min (z + zstep, zmax)
            cycle
        else
            zstep = zstep * 0.5_default
            cycle
        end if
    end if
end do
else if (prt%is_gluon () .and. prt%child1%is_gluon ()) then
do
    zstep = min(zstep, 0.5_default * (zmax - z))
    if (abs (zstep) < 0.00001) exit
    if (integral_over_P_ggg (zmin, z) < random * integral) then
        if (integral_over_P_ggg (zmin, min(z + zstep, zmax)) &
            < random * integral) then
            z = min(z + zstep, zmax)
            cycle
        else
            zstep = zstep * 0.5_default
            cycle
        end if
    end if
end do
else
end if
prt%z = z
prt%x = prt%child1%x / prt%z
end subroutine generate_trial_z_and_typ
end function shower_generate_next_isr_branching_veto

```

(Shower core: shower: TBP)+≡

```
procedure :: find_recoiler => shower_find_recoiler
```

(Shower core: procedures)+≡

```

function shower_find_recoiler (shower, prt) result(recoiler)
    class(shower_t), intent(inout) :: shower
    type(parton_t), intent(inout), target :: prt
    type(parton_t), pointer :: recoiler
    type(parton_t), pointer :: otherprt1, otherprt2
    integer :: n_int
    otherprt1 => null()
    otherprt2 => null()
    DO_INTERACTIONS: do n_int = 1, size(shower%interactions)
        otherprt1 => shower%interactions(n_int)%i%partons(1)%p
    end do
end function shower_find_recoiler

```

```

otherprt2 => shower%interactions(n_int)%i%partons(2)%p
PARTON1: do
  if (associated (otherprt1%parent)) then
    if (.not. otherprt1%parent%is_proton () .and. &
        otherprt1%parent%simulated) then
      otherprt1 => otherprt1%parent
      if (associated (otherprt1, prt)) then
        exit PARTON1
      end if
    else
      exit PARTON1
    end if
  else
    exit PARTON1
  end if
end do PARTON1
PARTON2: do
  if (associated (otherprt2%parent)) then
    if (.not. otherprt2%parent%is_proton () .and. &
        otherprt2%parent%simulated) then
      otherprt2 => otherprt2%parent
      if (associated (otherprt2, prt)) then
        exit PARTON2
      end if
    else
      exit PARTON2
    end if
  else
    exit PARTON2
  end if
end do PARTON2

if (associated (otherprt1, prt) .or. associated (otherprt2, prt)) then
  exit DO_INTERACTIONS
end if
if (associated (otherprt1%parent, prt) .or. &
    associated (otherprt2%parent, prt)) then
  exit DO_INTERACTIONS
end if
end do DO_INTERACTIONS

recoiler => null()
if (associated (otherprt1%parent, prt)) then
  recoiler => otherprt2
else if (associated (otherprt2%parent, prt)) then
  recoiler => otherprt1
else if (associated (otherprt1, prt)) then
  recoiler => otherprt2
else if (associated (otherprt2, prt)) then
  recoiler => otherprt1
else
  call shower%write ()
  call prt%write ()
  call msg_error ("Shower: no otherparton found")

```

```

end if
end function shower_find_recoiler

```

(Shower core: procedures)+≡

```

subroutine shower_isr_step (shower, prt)
  type(shower_t), intent(inout) :: shower
  type(parton_t), target, intent(inout) :: prt
  type(parton_t), pointer :: otherprt => null()
  real(default) :: t, tstep
  real(default) :: integral, random
  real(default) :: temprand1, temprand2
  integer :: d_nf
  otherprt => shower%find_recoiler (prt)
  ! if (.not. otherprt%child1%belongstointeraction) then
  !   otherprt => otherprt%child1
  ! end if

  if (signal_is_pending ()) return
  t = max(prt%t, prt%child1%t)
  call shower%rng%generate (random)
  d_nf = shower%settings%max_n_flavors
  ! compare Integral and log(random) instead of random and exp(-Integral)
  random = - twopi * log(random)
  integral = zero
  call shower%rng%generate (temprand1)
  call shower%rng%generate (temprand2)
  tstep = max (abs (0.02_default * t) * temprand1, &
    0.02_default * temprand2 * shower%settings%d_min_t)
  if (t + 0.5_default * tstep > - shower%settings%d_min_t) then
    prt%t = prt%mass_squared ()
    call prt%set_simulated ()
  else
    prt%t = t + 0.5_default * tstep
    integral = integral + tstep * &
      integral_over_z_isr (prt, otherprt, (random - integral) / tstep)
    if (integral > random) then
      prt%t = t + 0.5_default * tstep
      prt%x = prt%child1%x / prt%z
      call prt%set_simulated ()
    else
      prt%t = t + tstep
    end if
  end if
end if

```

contains

```

function integral_over_z_isr (prt, otherprt, final) result (integral)
  type(parton_t), intent(inout) :: prt, otherprt
  real(default), intent(in) :: final
  real(default) integral
  real(default) :: minz, maxz, z, shat,s
  integer :: quark

  !!! calculate shat -> s of parton-parton system

```

```

shat= (otherprt%momentum + prt%child1%momentum)**2
!!! calculate s -> s of hadron-hadron system
s= (otherprt%initial%momentum + prt%initial%momentum)**2
integral = zero
minz = prt%child1%x
maxz = maxx (shat, s, shower%maxz_isr, shower%minenergy_timelike)

!!! for gluon
if (prt%child1%is_gluon ()) then
  !!! 1: g->gg
  prt%type = GLUON
  prt%child2%type = GLUON
  z = minz
  prt%child2%t = abs(prt%t)
  call integral_over_z_part_isr &
    (prt, otherprt, shat, minz, maxz, integral, final)
  if (integral > final) then
    return
  end if
  !!! 2: q->qq
  do quark = -d_nf, d_nf
    if (quark == 0) cycle
    prt%type = quark
    prt%child2%type = quark
    z = minz
    prt%child2%t = abs(prt%t)
    call integral_over_z_part_isr &
      (prt, otherprt, shat, minz, maxz, integral, final)
    if (integral > final) then
      return
    end if
  end do
else if (prt%child1%is_quark ()) then
  !!! 1: q->qg
  prt%type = prt%child1%type
  prt%child2%type = GLUON
  z = minz
  prt%child2%t = abs(prt%t)
  call integral_over_z_part_isr &
    (prt, otherprt, shat, minz, maxz, integral, final)
  if (integral > final) then
    return
  end if
  !!! 2: g->qqbar
  prt%type = GLUON
  prt%child2%type = -prt%child1%type
  z = minz
  prt%child2%t = abs(prt%t)
  call integral_over_z_part_isr &
    (prt, otherprt, shat, minz, maxz, integral, final)
  if (integral > final) then
    return
  end if
end if

```

```

end function integral_over_z_isr

subroutine integral_over_z_part_isr &
  (prt, otherprt, shat ,minz, maxz, retvalue, final)
  type(parton_t), intent(inout) :: prt, otherprt
  real(default), intent(in) :: shat, minz, maxz, final
  real(default), intent(inout) :: retvalue
  real(default) :: z, zstep
  real(default) :: r1,r3,s1,s3
  real(default) :: pdf_divisor
  real(default) :: temprand
  real(default), parameter :: zstepfactor = 0.1_default
  real(default), parameter :: zstepmin = 0.0001_default
  if (DEBUG_WHIZ_SHOWER) print *, "D: integral_over_z_part_isr"
  pdf_divisor = shower%get_pdf &
    (prt%initial%type, prt%child1%x, prt%t, prt%child1%type)
  z = minz
  s1 = shat + abs(otherprt%t) + abs(prt%child1%t)
  r1 = sqrt (s1**2 - four * abs(otherprt%t * prt%child1%t))
  ZLOOP: do
    if (signal_is_pending ()) return
    if (z >= maxz) then
      exit
    end if
    call shower%rng%generate (temprand)
    if (prt%child1%is_gluon ()) then
      if (prt%is_gluon ()) then
        !!! g-> gg -> divergencies at z->0 and z->1
        zstep = max(zstepmin, temprand * zstepfactor * z * (one - z))
      else
        !!! q-> qq -> divergencies at z->0
        zstep = max(zstepmin, temprand * zstepfactor * (one - z))
      end if
    else
      if (prt%is_gluon ()) then
        !!! g-> qqbar -> no divergencies
        zstep = max(zstepmin, temprand * zstepfactor)
      else
        !!! q-> qg -> divergencies at z->1
        zstep = max(zstepmin, temprand * zstepfactor * (one - z))
      end if
    end if
    zstep = min(zstep, maxz - z)
    prt%z = z + 0.5_default * zstep
    s3 = shat / prt%z + abs(otherprt%t) + abs(prt%t)
    r3 = sqrt (s3**2 - four * abs(otherprt%t * prt%t))
    !!! TODO: WHY is this if needed?
    if (abs(otherprt%t) > eps0) then
      prt%child2%t = min ((s1 * s3 - r1 * r3) / &
        (two * abs(otherprt%t)) - abs(prt%child1%t) - &
        abs(prt%t), abs(prt%child1%t))
    else
      prt%child2%t = abs(prt%child1%t)
    end if
  end if

```



```

do
  prt%child2%momentum%p(0) = sqrt (abs(prt%child2%t))
  if (shower%isr_only_onshell_emitted_partons) then
    prt%child2%t = prt%child2%mass_squared ()
  else
    call prt%child2%next_t_ana (shower%rng)
  end if
  !!! take limits by recoiler into account
  prt%momentum%p(0) = (shat / prt%z + &
    abs(otherprt%t) - abs(prt%child1%t) - &
    prt%child2%t) / (two * sqrt(shat))
  prt%child2%momentum%p(0) = &
    prt%momentum%p(0) - prt%child1%momentum%p(0)
  !!! check if E and t of prt%child2 are consistent
  if (prt%child2%momentum%p(0)**2 < prt%child2%t &
    .and. prt%child2%t > prt%child2%mass_squared ()) then
    !!! E is too small to have  $p_T^2 = E^2 - t > 0$ 
    !!!      -> cycle to find another solution
    cycle
  else
    !!! E is big enough -> exit
    exit
  end if
end do
if (thetabar (prt, otherprt, shower%isr_angular_ordered) &
  .and. pdf_divisor > zero &
  .and. prt%child2%momentum%p(0) > zero) then
  retvalue = retvalue + (zstep / prt%z) * &
    (D_alpha_s_isr ((one - prt%z) * prt%t, &
      shower%settings) * &
    P_prt_to_child1 (prt) * &
    shower%get_pdf (prt%initial%type, prt%child1%x / prt%z, &
      prt%t, prt%type)) / (abs(prt%t) * pdf_divisor)
end if
if (retvalue > final) then
  exit
else
  z = z + zstep
end if
end do ZLOOP
end subroutine integral_over_z_part_isr
end subroutine shower_isr_step

```

This returns a pointer to the parton with the next ISR branching, again FSR branchings are ignored.

(Shower core: shower: TBP)+≡

```

procedure :: generate_next_isr_branching => &
  shower_generate_next_isr_branching

```

(Shower core: procedures)+≡

```

function shower_generate_next_isr_branching &
  (shower) result (next_brancher)
  class(shower_t), intent(inout) :: shower
  type(parton_pointer_t) :: next_brancher

```

```

integer i, index
type(parton_t), pointer :: prt
real(default) :: maxscale
next_brancher%p => null()
do
  if (signal_is_pending ()) return
  if (shower_isr_is_finished (shower)) exit
  !!! find mother with highest |t| or pt to be simulated
  index = 0
  maxscale = zero
  call shower%sort_partons ()
  do i = 1,size (shower%partons)
    prt => shower%partons(i)%p
    if (.not. associated (prt)) cycle
    if (.not. shower%settings%isr_pt_ordered) then
      if (prt%belongstointeraction) cycle
    end if
    if (prt%belongstoFSR) cycle
    if (prt%is_final ()) cycle
    if (.not. prt%belongstoFSR .and. prt%simulated) cycle
    index = i
    exit
  end do
  if (ENSURE) then
    if (index == 0) then
      call msg_fatal(" no branchable partons found")
      return
    end if
  end if

  prt => shower%partons(index)%p

  !!! ISR simulation
  if (shower%settings%isr_pt_ordered) then
    call shower_isr_step_pt (shower, prt)
  else
    call shower_isr_step (shower, prt)
  end if
  if (prt%simulated) then
    if (prt%t < zero) then
      next_brancher%p => prt
      if (.not. shower%settings%isr_pt_ordered) &
        call prt%generate_ps_ini (shower%rng)
      exit
    else
      if (.not. shower%settings%isr_pt_ordered) then
        call shower_replace_parent_by_hadron (shower, prt%child1)
      else
        call shower_replace_parent_by_hadron (shower, prt)
      end if
    end if
  end if
end if
end do

```

```

!!! some bookkeeping
call shower%sort_partons ()
call shower%boost_to_CMframe ()          !!! really necessary?
call shower%rotate_to_z ()              !!! really necessary?
end function shower_generate_next_isr_branching

```

This is a loop which searches for all emitted and branched partons.

```

(Shower core: shower: TBP)+≡
  procedure :: generate_fsr_for_isr_partons => &
    shower_generate_fsr_for_partons_emitted_in_ISR
(Shower core: procedures)+≡
  subroutine shower_generate_fsr_for_partons_emitted_in_ISR (shower)
    class(shower_t), intent(inout) :: shower
    integer :: n_int, i
    type(parton_t), pointer :: prt
    if (shower%isr_only_onshell_emitted_partons) return
    if (DEBUG_WHIZ_SHOWER) print *, "D: shower_generate_fsr_for_partons_emitted_in_ISR"
    INTERACTIONS_LOOP: do n_int = 1, size (shower%interactions)
      INCOMING_PARTONS_LOOP: do i = 1, 2
        if (signal_is_pending ()) return
        prt => shower%interactions(n_int)%i%partons(i)%p
        PARENT_PARTONS_LOOP: do
          if (associated (prt%parent)) then
            if (.not. prt%parent%is_proton ()) then
              prt => prt%parent
            else
              exit
            end if
          else
            exit
          end if
          if (associated (prt%child2)) then
            if (prt%child2%is_branched ()) then
              call shower_parton_generate_fsr (shower, prt%child2)
            end if
          else
            ! call msg_fatal ("Shower: no child2 associated?")
          end if
        end do PARENT_PARTONS_LOOP
      end do INCOMING_PARTONS_LOOP
    end do INTERACTIONS_LOOP
  end subroutine shower_generate_fsr_for_partons_emitted_in_ISR

```

This executes the branching generated by `shower_generate_next_isr_branching`, that means it generates the flavors, momenta, etc.

```

(Shower core: shower: TBP)+≡
  procedure :: execute_next_isr_branching => shower_execute_next_isr_branching
(Shower core: procedures)+≡
  subroutine shower_execute_next_isr_branching (shower, prtp)
    class(shower_t), intent(inout) :: shower
    type(parton_pointer_t), intent(inout) :: prtp
    type(parton_t), pointer :: prt, otherprt

```

```

type(parton_t), pointer :: prta, prtb, prtc, prtr
real(default) :: mar, mbr
real(default) :: phirand
if (DEBUG_WHIZ_SHOWER) print *, "D: shower_execute_next_isr_branching"
if (.not. associated (prtp%p)) then
    call msg_fatal ("Shower: prtp not associated")
end if

prt => prtp%p

if ((.not. shower%settings%isr_pt_ordered .and. &
    prt%t > - shower%settings%d_min_t) .or. &
    (shower%settings%isr_pt_ordered .and. prt%scale < D_Min_scale)) then
    call msg_error ("Shower: no branching to be executed.")
end if

otherprt => shower%find_recoiler (prt)
if (shower%settings%isr_pt_ordered) then
    !!! get the recoiler
    otherprt => shower%find_recoiler (prt)
    if (associated (otherprt%parent)) then
        !!! Why only for pt ordered
        if (.not. otherprt%parent%is_proton () .and. &
            shower%settings%isr_pt_ordered) otherprt => otherprt%parent
    end if
    if (.not. associated (prt%parent)) then
        call shower%add_parent (prt)
    end if
    prt%parent%belongstoFSR = .false.
    if (.not. associated (prt%parent%child2)) then
        call shower%add_child (prt%parent, 2)
    end if

    prta => prt%parent          !!! new parton a with branching a->bc
    prtb => prt                 !!! former parton
    prtc => prt%parent%child2    !!! emitted parton
    prtr => otherprt            !!! recoiler

    mbr = (prtb%momentum + prtr%momentum)**1
    mar = mbr / sqrt(prt%z)

    !!! 1. assume you are in the restframe
    !!! 2. rotate by random phi
    call shower%rng%generate (phirand)
    phirand = twopi * phirand
    call shower_apply_lorentztrafo (shower, &
        rotation(cos(phirand), sin(phirand), vector3_canonical(3)))
    !!! 3. Put the b off-shell
    !!! and
    !!! 4. construct the massless a
    !!! and the parton (eventually emitted by a)

    !!! generate the flavor of the parent (prta)
    if (prtb%aux_pt /= 0) prta%type = prtb%aux_pt

```

```

if (prtb%is_quark ()) then
  if (prta%type == prtb%type) then
    !!! (anti)-quark -> (anti-)quark + gluon
    prta%type = prtb%type    ! quarks have same flavor
    prtc%type = GLUON        ! emitted gluon
  else
    !!! gluon -> quark + antiquark
    prta%type = GLUON
    prtc%type = - prtb%type
  end if
else if (prtb%is_gluon ()) then
  prta%type = GLUON
  prtc%type = GLUON
else
  ! STOP "Bug in shower_execute_next_branching: neither quark nor gluon"
end if

prta%initial => prtb%initial
prta%belongstoFSR = .false.
prta%scale = prtb%scale
prta%x = prtb%x / prtb%z

prtb%momentum = vector4_moving ((mbr**2 + prtb%t) / (two * mbr), &
  vector3_canonical(3) * &
  sign ((mbr**2 - prtb%t) / (two * mbr), &
  prtb%momentum%p(3)))
prtr%momentum = vector4_moving ((mbr**2 - prtb%t) / (two * mbr), &
  vector3_canonical(3) * &
  sign( (mbr**2 - prtb%t) / (two * mbr), &
  prtr%momentum%p(3)))

prta%momentum = vector4_moving ((0.5_default / mbr) * &
  ((mbr**2 / prtb%z) + prtb%t - prtc%mass_squared ()), &
  vector3_null)
prta%momentum = vector4_moving (prta%momentum%p(0), &
  vector3_canonical(3) * &
  (0.5_default / prtb%momentum%p(3)) * &
  ((mbr**2 / prtb%z) - two &
  * prtr%momentum%p(0) * prta%momentum%p(0) ) )
if (prta%momentum%p(0)**2 - prta%momentum%p(3)**2 - &
  prtc%mass_squared () > zero) then
  !!! This SHOULD be always fulfilled???
  prta%momentum = vector4_moving (prta%momentum%p(0), &
    vector3_moving(sqrt (prta%momentum%p(0)**2 - &
    prta%momentum%p(3)**2 - &
    prtc%mass_squared ()), zero, &
    prta%momentum%p(3]))
end if
prtc%momentum = prta%momentum - prtb%momentum

!!! 5. rotate to have a along z-axis
call shower%boost_to_CMframe ()
call shower%rotate_to_z ()
!!! 6. rotate back in phi

```

```

        call shower_apply_lorentztrafo (shower, rotation &
            (cos(-phirand), sin(-phirand), vector3_canonical(3)))
    else
        if (prt%child2%t > prt%child2%mass_squared ()) then
            call shower_add_children_of_emitted_timelike_parton &
                (shower, prt%child2)
            call prt%child2%set_simulated ()
        end if

        call shower%add_parent (prt)
        call shower%add_child (prt%parent, 2)

        prt%parent%momentum = prt%momentum
        prt%parent%t = prt%t
        prt%parent%x = prt%x
        prt%parent%initial => prt%initial
        prt%parent%belongstoFSR = .false.

        prta => prt
        prtb => prt%child1
        prtc => prt%child2
    end if
    if (signal_is_pending ()) return
    if (shower%settings%isr_pt_ordered) then
        call prt%parent%generate_ps_ini (shower%rng)
    else
        call prt%generate_ps_ini (shower%rng)
    end if

    !!! add color connections
    if (prtb%is_quark ()) then

        if (prta%type == prtb%type) then
            if (prtb%type > 0) then
                !!! quark -> quark + gluon
                prtc%c2 = prtb%c1
                prtc%c1 = shower%get_next_color_nr ()
                prta%c1 = prtc%c1
            else
                !!! antiquark -> antiquark + gluon
                prtc%c1 = prtb%c2
                prtc%c2 = shower%get_next_color_nr ()
                prta%c2 = prtc%c2
            end if
        else
            !!! gluon -> quark + antiquark
            if (prtb%type > 0) then
                !!! gluon -> quark + antiquark
                prta%c1 = prtb%c1
                prtc%c1 = 0
                prtc%c2 = shower%get_next_color_nr ()
                prta%c2 = prtc%c2
            else
                !!! gluon -> antiquark + quark

```

```

        prta%c2 = prtb%c2
        prtc%c1 = shower%get_next_color_nr ()
        prtc%c2 = 0
        prta%c1 = prtc%c1
    end if
end if
else if (prtb%is_gluon ()) then
    if (prta%is_gluon ()) then
        !!! g -> gg
        prtc%c2 = prtb%c1
        prtc%c1 = shower%get_next_color_nr ()
        prta%c1 = prtc%c1
        prta%c2 = prtb%c2
    else if (prta%is_quark ()) then
        if (prta%type > 0) then
            prta%c1 = prtb%c1
            prta%c2 = 0
            prtc%c1 = prtb%c2
            prtc%c2 = 0
        else
            prta%c1 = 0
            prta%c2 = prtb%c2
            prtc%c1 = 0
            prtc%c2 = prtb%c1
        end if
    end if
end if

call shower%sort_partons ()
call shower%boost_to_CMframe ()
call shower%rotate_to_z ()

end subroutine shower_execute_next_isr_branching

```

(Shower core: procedures)+≡

```

subroutine shower_remove_parents_and_stuff (shower, prt)
    type(shower_t), intent(inout) :: shower
    type(parton_t), intent(inout), target :: prt
    type(parton_t), pointer :: actprt, nextprt
    nextprt => prt%parent
    actprt => null()
    !!! remove children of emitted timelike parton
    if (associated (prt%child2)) then
        if (associated (prt%child2%child1)) then
            call shower_remove_parton_from_partons_recursive &
                (shower, prt%child2%child1)
        end if
        prt%child2%child1 => null()
        if (associated (prt%child2%child2)) then
            call shower_remove_parton_from_partons_recursive &
                (shower, prt%child2%child2)
        end if
        prt%child2%child2 => null()
    end if
end if

```

```

do
  actprt => nextprt
  if (.not. associated (actprt)) then
    exit
  else if (actprt%is_proton ()) then
    !!! remove beam-remnant
    call shower_remove_parton_from_partons (shower, actprt%child2)
    exit
  end if
  if (associated (actprt%parent)) then
    nextprt => actprt%parent
  else
    nextprt => null()
  end if
  call shower_remove_parton_from_partons_recursive &
    (shower, actprt%child2)
  call shower_remove_parton_from_partons (shower, actprt)

end do
prt%parent=>null()

end subroutine shower_remove_parents_and_stuff

<Shower core: shower: TBP>+≡
  procedure :: get_ISR_scale => shower_get_ISR_scale

<Shower core: procedures>+≡
  function shower_get_ISR_scale (shower) result (scale)
    class(shower_t), intent(in) :: shower
    real(default) :: scale
    type(parton_t), pointer :: prt1, prt2
    integer :: i
    scale = zero
    do i = 1, size (shower%interactions)
      call interaction_find_partons_nearest_to_hadron &
        (shower%interactions(i)%i, prt1, prt2, &
        shower%settings%isr_pt_ordered)
      if (.not. prt1%simulated .and. abs(prt1%scale) > scale) &
        scale = abs(prt1%scale)
      if (.not. prt1%simulated .and. abs(prt2%scale) > scale) &
        scale = abs(prt2%scale)
    end do
  end function shower_get_ISR_scale

<Shower core: shower: TBP>+≡
  procedure :: set_max_isr_scale => shower_set_max_isr_scale

<Shower core: procedures>+≡
  subroutine shower_set_max_isr_scale (shower, newscale)
    class(shower_t), intent(inout) :: shower
    real(default), intent(in) :: newscale
    real(default) :: scale
    type(parton_t), pointer :: prt
    integer :: i,j

```



```

print *, "shower_set_max_isr_scale", newscale
call shower%write ()

if (shower%settings%isr_pt_ordered) then
    scale = newscale
else
    scale = -abs(newscale)
end if

INTERACTIONS: do i = 1, size (shower%interactions)
    PARTONS: do j = 1, 2
        prt => shower%interactions(i)%i%partons(j)%p
        do
            if (.not. shower%settings%isr_pt_ordered) then
                if (prt%belongstointeraction) prt => prt%parent
            end if
            if (prt%t < scale) then
                if (associated (prt%parent)) then
                    prt => prt%parent
                else
                    exit    !!! unresolved prt found
                end if
            else
                exit    !!! prt with scale above newscale found
            end if
        end do
        if (.not. shower%settings%isr_pt_ordered) then
            if (prt%child1%belongstointeraction .or. &
                prt%is_proton ()) then
                !!! don't reset scales of "first" spacelike partons
                !!!    in virtuality ordered shower or hadrons
                cycle
            end if
        else
            if (prt%is_proton ()) then
                !!! don't reset scales of hadrons
                cycle
            end if
        end if
        if (shower%settings%isr_pt_ordered) then
            prt%scale = scale
        else
            prt%t = scale
        end if
        call prt%set_simulated (.false.)
        call shower_remove_parents_and_stuff (shower, prt)
    end do PARTONS
end do INTERACTIONS

call shower%write ()
print *, "shower_set_max_isr_scale finished"
end subroutine shower_set_max_isr_scale

```

(Shower core: shower: TBP)+≡

```

procedure :: interaction_generate_fsr_2ton => &
    shower_interaction_generate_fsr_2ton

<Shower core: procedures>+=
subroutine shower_interaction_generate_fsr_2ton (shower, interaction)
    class(shower_t), intent(inout) :: shower
    type(shower_interaction_t), intent(inout) :: interaction
    type(parton_t), pointer :: prt
    prt => interaction%partons(3)%p
    do
        if (.not. associated (prt%parent)) exit
        prt => prt%parent
    end do
    call shower_parton_generate_fsr (shower, prt)
    call shower_parton_update_color_connections (shower, prt)
end subroutine shower_interaction_generate_fsr_2ton

```

Perform the FSR for one parton, it is assumed, that the parton already branched. Hence, its children are to be simulated. This procedure is intended for branched FSR-partons emitted in the ISR.

```

<Shower core: procedures>+=
subroutine shower_parton_generate_fsr (shower, prt)
    type(shower_t), intent(inout) :: shower
    type(parton_t), intent(inout), target :: prt
    type(parton_pointer_t), dimension(:), allocatable :: partons
    logical :: single_emission = .false.
    if (DEBUG_WHIZ_SHOWER) print *, 'D: shower_parton_generate_fsr'
    if (signal_is_pending ()) return
    if (ENSURE) then
        if (.not. prt%is_branched ()) then
            call msg_error ("shower_parton_generate_fsr: parton not branched")
            return
        end if
        if (prt%child1%simulated .or. &
            prt%child2%simulated) then
            print *, " error in shower_parton_generate_fsr:", &
                "children already simulated for parton ", prt%nr
            call shower%write ()
            return
        end if
    end if

    allocate (partons(1))
    partons(1)%p => prt
    if (single_emission) then
        call shower%parton_pointer_array_generate_fsr (partons, partons)
    else
        call shower%parton_pointer_array_generate_fsr_recursive (partons)
    end if

end subroutine shower_parton_generate_fsr

```

```

<Shower core: shower: TBP>+=

```

```

procedure :: parton_pointer_array_generate_fsr_recursive => &
    shower_parton_pointer_array_generate_fsr_recursive

<Shower core: procedures>+≡
    recursive subroutine shower_parton_pointer_array_generate_fsr_recursive &
        (shower, partons)
        class(shower_t), intent(inout) :: shower
        type(parton_pointer_t), dimension(:), allocatable, intent(inout) :: &
            partons
        type(parton_pointer_t), dimension(:), allocatable :: partons_new
        if (DEBUG_WHIZ_SHOWER) print *, 'D: shower_parton_pointer_array_generate_fsr_recursive'
        if (signal_is_pending ()) return
        if (size (partons) == 0) return
        call shower%parton_pointer_array_generate_fsr (partons, partons_new)
        call shower%parton_pointer_array_generate_fsr_recursive (partons_new)
    end subroutine shower_parton_pointer_array_generate_fsr_recursive

<Shower core: shower: TBP>+≡
    procedure :: parton_pointer_array_generate_fsr => &
        shower_parton_pointer_array_generate_fsr

<Shower core: procedures>+≡
    subroutine shower_parton_pointer_array_generate_fsr &
        (shower, partons, partons_new)
        class(shower_t), intent(inout) :: shower
        type(parton_pointer_t), dimension(:), allocatable, intent(inout) :: &
            partons
        type(parton_pointer_t), dimension(:), allocatable, intent(out) :: &
            partons_new
        integer :: i, size_partons, size_partons_new
        if (DEBUG_WHIZ_SHOWER) print *, 'D: shower_parton_pointer_array_generate_fsr'
        !!! Simulate highest/first parton
        call shower_simulate_children_ana (shower, partons(1)%p)
        !!! check for new daughters to be included in new_partons
        size_partons = size (partons)
        size_partons_new = size_partons - 1  !!! partons(1) not needed anymore
        if (partons(1)%p%child1%is_branched ()) &
            size_partons_new = size_partons_new + 1
        if (partons(1)%p%child2%is_branched ()) &
            size_partons_new = size_partons_new + 1

        allocate (partons_new (1:size_partons_new))

        if (size_partons > 1) then
            do i = 2, size_partons
                partons_new (i - 1)%p => partons(i)%p
            end do
        end if
        if (partons(1)%p%child1%is_branched ()) &
            partons_new (size_partons)%p => partons(1)%p%child1
        if (partons(1)%p%child2%is_branched ()) then
            !!! check if child1 is already included
            if (size_partons_new == size_partons) then
                partons_new (size_partons)%p => partons(1)%p%child2
            else if (size_partons_new == size_partons + 1) then
                partons_new (size_partons + 1)%p => partons(1)%p%child2
            end if
        end if
    end subroutine

```

```

        else
            call msg_fatal ("Shower: wrong sizes in" &
                // "shower_parton_pointer_array_generate_fsr")
        end if
    end if
end if
deallocate (partons)

end subroutine shower_parton_pointer_array_generate_fsr

(Shower core: procedures)+≡
recursive subroutine shower_parton_update_color_connections &
    (shower, prt)
    type(shower_t), intent(inout) :: shower
    type(parton_t), intent(inout) :: prt
    real(default) :: temprand
    if (.not. associated (prt%child1) .or. &
        .not. associated (prt%child2)) return

    if (signal_is_pending ()) return
    if (prt%is_gluon ()) then
        if (prt%child1%is_quark ()) then
            !!! give the quark the colorpartner and the antiquark
            !!! the anticolorpartner
            if (prt%child1%type > 0) then
                !!! child1 is quark, child2 is antiquark
                prt%child1%c1 = prt%c1
                prt%child2%c2 = prt%c2
            else
                !!! child1 is antiquark, child2 is quark
                prt%child1%c2 = prt%c2
                prt%child2%c1 = prt%c1
            end if
        else
            !!! g -> gg splitting -> random choosing of partners
            call shower%rng%generate (temprand)
            if (temprand > 0.5_default) then
                prt%child1%c1 = prt%c1
                prt%child1%c2 = shower%get_next_color_nr ()
                prt%child2%c1 = prt%child1%c2
                prt%child2%c2 = prt%c2
            else
                prt%child1%c2 = prt%c2
                prt%child2%c1 = prt%c1
                prt%child2%c2 = shower%get_next_color_nr ()
                prt%child1%c1 = prt%child2%c2
            end if
        end if
    else if (prt%is_quark ()) then
        if (prt%child1%is_quark ()) then
            if (prt%child1%type > 0) then
                !!! q -> q + g
                prt%child2%c1 = prt%c1
                prt%child2%c2 = shower%get_next_color_nr ()
                prt%child1%c1 = prt%child2%c2
            end if
        end if
    end if
end subroutine

```

```

        else
            !!! qbar -> qbar + g
            prt%child2%c2 = prt%c2
            prt%child2%c1 = shower%get_next_color_nr ()
            prt%child1%c2 = prt%child2%c1
        end if
    else
        if (prt%child2%type > 0) then
            !!! q -> g + q
            prt%child1%c1 = prt%c1
            prt%child1%c2 = shower%get_next_color_nr ()
            prt%child2%c1 = prt%child1%c2
        else
            !!! qbar -> g + qbar
            prt%child1%c2 = prt%c2
            prt%child1%c1 = shower%get_next_color_nr ()
            prt%child2%c2 = prt%child1%c1
        end if
    end if
end if

call shower_parton_update_color_connections (shower, prt%child1)
call shower_parton_update_color_connections (shower, prt%child2)
end subroutine shower_parton_update_color_connections

```

The next two routines are for PDFs. Wrapper function to return parton densities.

```

<Shower core: shower: TBP>+≡
    procedure :: get_pdf => shower_get_pdf

<Shower core: procedures>+≡
    function shower_get_pdf (shower, mother, x, Q2, daughter) result (pdf)
        <get pdf>
        if (x > eps0) then
            pdf = pdf / x
        end if
    end function shower_get_pdf

<Shower core: shower: TBP>+≡
    procedure :: get_xpdf => shower_get_xpdf

<Shower core: procedures>+≡
    function shower_get_xpdf (shower, mother, x, Q2, daughter) result (pdf)
        <get pdf>
    end function shower_get_xpdf

<get pdf>≡
    class(shower_t), intent(inout), target :: shower
    integer, intent(in) :: mother, daughter
    real(default), intent(in) :: x, Q2
    real(default) :: pdf
    real(double), save :: f(-6:6) = 0._double
    real(double), save :: lastx, lastQ2 = 0._double
    if (ENSURE) then

```

```

if (abs (mother) /= PROTON) then
  pdf = zero
  print *, "mother = ", mother
  call msg_fatal ("Shower: pdf only implemented for (anti-)proton")
end if
if (.not. (abs (daughter) >= 1 .and. abs (daughter) <= 6 .or. &
  daughter == GLUON)) then
  pdf = zero
  print *, "daughter = ", daughter
  call msg_fatal ("Shower: error in pdf, unknown daughter")
end if
end if
if (x > zero .and. x < one) then
  if ((dble(Q2) - lastQ2) > eps0 .or. (dble(x) - lastx) > eps0) then
    call shower%pdf_data%evolve &
      (dble(x), sqrt (abs (dble(Q2))), f)
  end if
  if (abs (daughter) >= 1 .and. abs (daughter) <= 6) then
    pdf = max (f(daughter * sign (1,mother)), tiny_10)
  else
    pdf = max (f(0), tiny_10)
  end if
else
  pdf = zero
end if
lastQ2 = dble(Q2)
lastx = dble(x)

```

Convert Whizard shower to Pythia6. Currently only works for one interaction

(Shower core: public)+≡

public :: shower_converttopythia

(Shower core: procedures)+≡

```

subroutine shower_converttopythia (shower)
  IMPLICIT DOUBLE PRECISION(A-H, O-Z)
  IMPLICIT INTEGER(I-N)
  COMMON/PYJETS/N,NPAD,K(4000,5),P(4000,5),V(4000,5)
  COMMON/PYDAT1/MSTU(200),PARU(200),MSTJ(200),PARJ(200)
  COMMON/PYDAT2/KCHG(500,4),PMAS(500,4),PARF(2000),VCKM(4,4)
  COMMON/PYDAT3/MDCY(500,3),MDME(8000,2),BRAT(8000),KFDP(8000,5)
  COMMON/PYSUBS/MSEL,MSELPD,MSUB(500),KFIN(2,-40:40),CKIN(200)
  COMMON/PYPARS/MSTP(200),PARP(200),MSTI(200),PARI(200)
  SAVE /PYJETS/,/PYDAT1/,/PYDAT2/,/PYDAT3/,/PYSUBS/,/PYPARS/

  type(shower_t), intent(in) :: shower
  type(parton_t), pointer :: pp, ppparent
  integer :: i, j, nz

  do i = 1, 2
    !!! get history of the event
    pp => shower%interactions(1)%i%partons(i)%p
    !!! add these partons to the event record
    if (associated (pp%initial)) then
      !!! add hadrons
      K(i,1) = 21
    end if
  end do

```

```

K(i,2) = pp%initial%type
K(i,3) = 0
P(i,1:5) = pp%initial%momentum%to_pythia6 ()
!!! add partons emitted by the hadron
ppparent => pp
do while (associated (ppparent%parent))
  if (ppparent%parent%is_proton ()) then
    exit
  else
    ppparent => ppparent%parent
  end if
end do
K(i+2,1) = 21
K(i+2,2) = ppparent%type
K(i+2,3) = i
P(i+2,1:5) = ppparent%momentum%to_pythia6 ()
!!! add partons in the initial state of the ME
K(i+4,1) = 21
K(i+4,2) = pp%type
K(i+4,3) = i
P(i+4,1:5) = pp%momentum%to_pythia6 ()
else
  !!! for e+e- without ISR all entries are the same
  K(i,1) = 21
  K(i,2) = pp%type
  K(i,3) = 0
  P(i,1:5) = pp%momentum%to_pythia6 ()
  P(i+2,:) = P(1,:)
  K(i+2,:) = K(1,:)
  K(i+2,3) = i
  P(i+4,:) = P(1,:)
  K(i+4,:) = K(1,:)
  K(i+4,3) = i
  P(i+4,5) = 0.
end if
end do
N = 6
!!! create intermediate (fake) Z-Boson
!K(7,1) = 21
!K(7,2) = 23
!K(7,3) = 0
!P(7,1:4) = P(5,1:4) + P(6,1:4)
!P(7,5) = P(7,4)**2 - P(7,3)**2 - P(7,2)**2 - P(7,1)**2
!N = 7
!!! include partons in the final state of the hard matrix element
do i = 1, size (shower%interactions(1)%i%partons) - 2
  !!! get partons that are in the final state of the hard matrix element
  pp => shower%interactions(1)%i%partons(2+i)%p
  !!! add these partons to the event record
  K(7+I,1) = 21
  K(7+I,2) = pp%type
  K(7+I,3) = 7
  P(7+I,1:5) = pp%momentum%to_pythia6 ()
  !N = 7 + I

```

```

      N = 6 + I
end do
!!! include "Z" (again)
!N = N + 1
!K(N,1) = 11
!K(N,2) = 23
!K(N,3) = 7
!P(N,1:5) = P(7,1:5)
!nz = N
!!! include partons from the final state of the parton shower
call shower_transfer_final_partons_to_pythia (shower, 8)
!!! set "children" of "Z"
!K(nz,4) = 11
!K(nz,5) = N

!!! be sure to remove the next partons (=first obsolete partons)
!!! otherwise they might be interpreted as thrust information
K(N+1:N+3,1:3) = 0
end subroutine shower_converttopythia

```

(Shower core: procedures)+≡

```

subroutine shower_transfer_final_partons_to_pythia (shower, first)
  IMPLICIT DOUBLE PRECISION(A-H, O-Z)
  IMPLICIT INTEGER(I-N)
  ! C... Commonblocks.
  COMMON/PYJETS/N,NPAD,K(4000,5),P(4000,5),V(4000,5)
  COMMON/PYDAT1/MSTU(200),PARU(200),MSTJ(200),PARJ(200)
  COMMON/PYDAT2/KCHG(500,4),PMAS(500,4),PARF(2000),VCKM(4,4)
  COMMON/PYDAT3/MDCY(500,3),MDME(8000,2),BRAT(8000),KFDP(8000,5)
  COMMON/PYSUBS/MSEL,MSELPD,MSUB(500),KFIN(2,-40:40),CKIN(200)
  COMMON/PYPARS/MSTP(200),PARP(200),MSTI(200),PARI(200)
  SAVE /PYJETS/,/PYDAT1/,/PYDAT2/,/PYDAT3/,/PYSUBS/,/PYPARS/

  type(shower_t), intent(in) :: shower
  integer, intent(in) :: first
  type(parton_t), pointer :: prt
  integer :: i, j, n_finals
  type(parton_t), dimension(:), allocatable :: final_partons
  type(parton_t) :: temp_parton
  integer :: minindex, maxindex

  prt => null()

  !!! get total number of final partons
  n_finals = 0
  do i = 1, size (shower%partons)
    if (.not. associated (shower%partons(i)%p)) cycle
    prt => shower%partons(i)%p
    if (.not. prt%belongstoFSR) cycle
    if (associated (prt%child1)) cycle
    n_finals = n_finals + 1
  end do

  allocate (final_partons(1:n_finals))

```



```

j = 1
do i = 1, size (shower%partons)
  if (.not. associated (shower%partons(i)%p)) cycle
  prt => shower%partons(i)%p
  if (.not. prt%belongstoFSR) cycle
  if (associated (prt%child1)) cycle
  final_partons(j) = shower%partons(i)%p
  j = j + 1
end do

!!! move quark to front as beginning of color string
minindex = 1
maxindex = size (final_partons)
FIND_Q: do i = minindex, maxindex
  if (final_partons(i)%type >= 1 .and. final_partons(i)%type <= 6) then
    temp_parton = final_partons(minindex)
    final_partons(minindex) = final_partons(i)
    final_partons(i) = temp_parton
    exit FIND_Q
  end if
end do FIND_Q

!!! sort so that connected partons are next to each other, don't care about zeros
do i = 1, size (final_partons)
  !!! ensure that final_partons begins with a color (not an anticolor)
  if (final_partons(i)%c1 > 0 .and. final_partons(i)%c2 == 0) then
    if (i == 1) then
      exit
    else
      temp_parton = final_partons(1)
      final_partons(1) = final_partons(i)
      final_partons(i) = temp_parton
      exit
    end if
  end if
end do

do i = 1, size (final_partons) - 1
  !!! search for color partner and move it to i + 1
  PARTNERS: do j = i + 1, size (final_partons)
    if (final_partons(j)%c2 == final_partons(i)%c1) exit PARTNERS
  end do PARTNERS
  if (j > size (final_partons)) then
    print *, "no color connected parton found" !WRONG???
    print *, "particle: ", final_partons(i)%nr, " index: ", &
      final_partons(i)%c1
    exit
  end if
  temp_parton = final_partons(i + 1)
  final_partons(i + 1) = final_partons(j)
  final_partons(j) = temp_parton
end do

!!! transferring partons

```

```

do i = 1, size (final_partons)
  prt = final_partons(i)
  N = N + 1
  K(N,1) = 2
  if (prt%c1 == 0) K(N,1) = 1      !!! end of color string
  K(N,2) = prt%type
  !K(N,3) = first
  K(N,3) = 0
  K(N,4) = 0
  K(N,5) = 0
  P(N,1:5) = prt%momentum%to_pythia6()
end do
deallocate (final_partons)
end subroutine shower_transfer_final_partons_to_pythia

```

20.4 Interface to PYTHIA

```

<shower_pythia6.f90>≡
  <File header>

  module shower_pythia6

    <Use kinds with double>
    <Use strings>
    use unit_tests, only: vanishes, nearly_equal
    use constants
    use io_units
    use physics_defs
    use diagnostics
    use system_defs, only: LF
    use os_interface
    use lorentz
    use subevents
    use mlm_matching
    use shower_base
    use particles
    use model_data
    use hep_common

    <Standard module head>

    <Shower PYTHIA6: public>

    <Shower PYTHIA6: types>

    contains

    <Shower PYTHIA6: procedures>

    end module shower_pythia6

```

The PYTHIA6 shower type.

```

<Shower PYTHIA6: public>≡
    public :: shower_pythia6_t

<Shower PYTHIA6: types>≡
    type, extends (shower_base_t) :: shower_pythia6_t
        integer :: initialized_for_NPRUP = 0
        logical :: warning_given = .false.
    contains
        <Shower PYTHIA6: shower PYTHIA6: TBP>
    end type shower_pythia6_t

```

Initialize the PYTHIA6 shower.

```

<Shower PYTHIA6: shower PYTHIA6: TBP>≡
    procedure :: init => shower_pythia6_init

<Shower PYTHIA6: procedures>≡
    subroutine shower_pythia6_init (shower, settings, pdf_data)
        class(shower_pythia6_t), intent(out) :: shower
        type(shower_settings_t), intent(in) :: settings
        type(pdf_data_t), intent(in) :: pdf_data
        if (DEBUG_SHOWER) print *, &
            "Transfer settings from shower_settings to shower"
        shower%settings = settings
        call pythia6_set_verbose (settings%verbose)
        call shower%pdf_data%init (pdf_data)
        shower%name = "PYTHIA6"
        call shower%write_msg ()
    end subroutine shower_pythia6_init

<Shower PYTHIA6: shower PYTHIA6: TBP>+≡
    procedure :: generate_emissions => shower_pythia6_generate_emissions

<Shower PYTHIA6: procedures>+≡
    subroutine shower_pythia6_generate_emissions ( &
        shower, particle_set, model, model_hadrons, &
        os_data, matching_settings, data, valid, vetoed, number_of_emissions)
        integer :: N, NPAD, K
        real(double) :: P, V
        common /PYJETS/ N, NPAD, K(4000,5), P(4000,5), V(4000,5)
        save /PYJETS/
        class(shower_pythia6_t), intent(inout), target :: shower
        type(particle_set_t), intent(inout) :: particle_set
        class(model_data_t), intent(in), target :: model
        class(model_data_t), intent(in), target :: model_hadrons
        class(matching_settings_t), intent(in), allocatable :: matching_settings
        class(matching_data_t), intent(inout), allocatable :: data
        type(os_data_t), intent(in) :: os_data
        logical, intent(inout) :: valid
        logical, intent(inout) :: vetoed
        integer, optional, intent(in) :: number_of_emissions
        type(particle_set_t) :: pset_reduced
        integer :: u_W2P
        logical :: varying_energy = .true.

```

```

if (signal_is_pending ()) return
if (DEBUG_SHOWER) then
  print *, "pythia6_generate_emissions"
  print *, 'IDBMUP(1:2) = ', IDBMUP(1:2)
  print *, 'EBMUP, PDFGUP, PDFSUP, IDWTUP = ', &
    EBMUP, PDFGUP, PDFSUP, IDWTUP
  print *, "NPRUP = ", NPRUP
end if
if (any (abs(IDBMUP) <= 8)) then
  if (.not. shower%warning_given) then
    call msg_error ("PYTHIA doesn't support quarks as beam particles," &
      // LF // " neglecting ISR, FSR and hadronization")
    shower%warning_given = .true.
  end if
  return
end if
call particle_set%reduce (pset_reduced)
call hepeup_from_particle_set (pset_reduced)
call hepeup_set_event_parameters (proc_id=1)
call pythia6_setup_lhe_io_units (u_W2P)
call w2p_write_lhef_event (u_W2P)
rewind (u_W2P)
call shower%transfer_settings ()

if (DEBUG_SHOWER) write (*, "(A)") "calling pyevnt"
if (varying_energy) then
  P(1,1:5) = pset_reduced%prt(1)%p%to_pythia6 ()
  P(2,1:5) = pset_reduced%prt(2)%p%to_pythia6 ()
end if
call pyevnt ()

call shower%combine_with_particle_set (particle_set, model, model_hadrons)

!!! Transfer momenta of the partons in the final state of
!!! the hard interaction
if (shower%settings%mlm_matching .and. allocated (data)) then
  select type (data)
  type is (mlm_matching_data_t)
    call get_ME_momenta_from_PYTHIA (data%P_ME)
  class default
    call msg_fatal ("MLM matching called with wrong data.")
  end select
end if

valid = pythia6_handle_errors ()
close (u_W2P)

end subroutine shower_pythia6_generate_emissions

```

<Shower PYTHIA6: shower PYTHIA6: TBP>+≡
 procedure :: transfer_settings => shower_pythia6_transfer_settings
<Shower PYTHIA6: procedures>+≡

```

subroutine shower_pythia6_transfer_settings (shower)
  class(shower_pythia6_t), intent(inout) :: shower
  character(len=10) :: buffer
  real(default) :: rand
  if (shower%settings%isr_active) then
    call pygive ("MSTP(61)=1")
  else
    call pygive ("MSTP(61)=0")  !!! switch off ISR
  end if
  if (shower%settings%fsr_active) then
    call pygive ("MSTP(71)=1")
  else
    call pygive ("MSTP(71)=0")  !!! switch off FSR
  end if
  call pygive ("MSTP(111)=1")    !!! Allow hadronization and decays
  call pygive ("MSTJ(1)=0")      !!! No jet fragmentation
  call pygive ("MSTJ(21)=1")     !!! Allow decays but no jet fragmentation
  call pygive ("MSTP(11)=0")     !!! Disable Pythias QED-ISR per default
  call pygive ("MSTP(171)=1")    !!! Allow variable energies

  if (shower%initialized_for_NPRUP >= NPRUP) then
    if (DEBUG_SHOWER) print *, "calling upinit"
    call upinit
  else
    write (buffer, "(F10.5)") sqrt (abs (shower%settings%d_min_t))
    call pygive ("PARJ(82)=" // buffer)
    write (buffer, "(F10.5)") shower%settings%isr_tscaletfactor
    call pygive ("PARP(71)=" // buffer)
    write (buffer, "(F10.5)") shower%settings%fsr_lambda
    call pygive ("PARP(72)=" // buffer)
    write (buffer, "(F10.5)") shower%settings%isr_lambda
    call pygive ("PARP(61)=" // buffer)
    write (buffer, "(I10)") shower%settings%max_n_flavors
    call pygive ("MSTJ(45)=" // buffer)
    if (shower%settings%isr_alpha_s_running) then
      call pygive ("MSTP(64)=2")
    else
      call pygive ("MSTP(64)=0")
    end if
    if (shower%settings%fsr_alpha_s_running) then
      call pygive ("MSTJ(44)=2")
    else
      call pygive ("MSTJ(44)=0")
    end if
    write (buffer, "(F10.5)") shower%settings%fixed_alpha_s
    call pygive ("PARU(111)=" // buffer)
    write (buffer, "(F10.5)") shower%settings%isr_primordial_kt_width
    call pygive ("PARP(91)=" // buffer)
    write (buffer, "(F10.5)") shower%settings%isr_primordial_kt_cutoff
    call pygive ("PARP(93)=" // buffer)
    write (buffer, "(F10.5)") 1._double - shower%settings%isr_z_cutoff
    call pygive ("PARP(66)=" // buffer)
    write (buffer, "(F10.5)") shower%settings%isr_minenergy
    call pygive ("PARP(65)=" // buffer)
  end if
end subroutine

```

```

if (shower%settings%isr_only_onshell_emitted_partons) then
  call pygive ("MSTP(63)=0")
else
  call pygive ("MSTP(63)=2")
end if
if (shower%settings%mlm_matching) then
  call pygive ("MSTP(62)=2")
  call pygive ("MSTP(67)=0")
end if
if (DEBUG_SHOWER) print *, "calling pyinit"
call PYINIT ("USER", "", "", 0D0)
call shower%rng%generate (rand)
write (buffer, "(I10)") floor (rand*900000000)
call pygive ("MRPY(1)=" // buffer)
call pygive ("MRPY(2)=0")
call pythia6_set_config (shower%settings%pythia6_pygive)
shower%initialized_for_NPRUP = NPRUP
end if
end subroutine shower_pythia6_transfer_settings

```

<Shower PYTHIA6: shower PYTHIA6: TBP>+≡

```

  procedure :: combine_with_particle_set => &
    shower_pythia6_combine_with_particle_set

```

<Shower PYTHIA6: procedures>+≡

```

  subroutine shower_pythia6_combine_with_particle_set &
    (shower, particle_set, model_in, model_hadrons)
    class(shower_pythia6_t), intent(inout) :: shower
    type(particle_set_t), intent(inout) :: particle_set
    class(model_data_t), intent(in), target :: model_in
    class(model_data_t), intent(in), target :: model_hadrons
    call pythia6_combine_with_particle_set &
      (particle_set, model_in, model_hadrons)
  end subroutine shower_pythia6_combine_with_particle_set

```

K(I,1) pythia status code

- 1 = undecayed particle or unfragmented parton
(single or last of parton system)
- 2 = unfragmented parton
(followed by more partons in the same color singlet)
- 3 = unfragmented parton (color info in K(I,4), K(I,5))
- 11 = decayed particle or fragmented parton
- 12 = fragmented parton
- 13 = fragmented parton that has been removed
- 14 = branched parton with color info like 3
- 21 = documentation lines

The first two

K(I,2) PDG code

K(I,3) Parent where known else 0. Unphysical to assign
particles partons as parents

K(I,4) Normally first daughter

K(I,5) Normally last daughter

particles are always the beams, in Pythia and Whizard. We remove all beam remnants (including the ISR photons) since those are added back in by Pythia.

```

<Shower PYTHIA6: public>+≡
    public :: pythia6_combine_with_particle_set

<Shower PYTHIA6: procedures>+≡
    subroutine pythia6_combine_with_particle_set (particle_set, model_in, model_hadrons)
        type(particle_set_t), intent(inout) :: particle_set
        class(model_data_t), intent(in), target :: model_in
        class(model_data_t), intent(in), target :: model_hadrons
        class(model_data_t), pointer :: model
        type(vector4_t) :: momentum
        type(particle_t), dimension(:), allocatable :: particles
        integer :: dangling_col, dangling_anti_col, color, anti_color
        integer :: i, j, py_entries, next_color, n_tot_old, parent, real_parent
        integer :: pdg, status, child, hadro_start
        integer, allocatable, dimension(:) :: old_index, new_index, backup_parents
        logical, allocatable, dimension(:) :: pythia_particle, valid
        type(lorentz_transformation_t) :: L
        logical :: boost_required
        integer :: N, NPAD, K
        real(double) :: P, V
        common /PYJETS/ N, NPAD, K(4000,5), P(4000,5), V(4000,5)
        save /PYJETS/
        integer, parameter :: KSUSY1 = 1000000, KSUSY2 = 2000000

        if (signal_is_pending ()) return
        if (DEBUG_SHOWER) then
            print *, 'Combine PYTHIA6 with particle set'
            print *, 'Particle set before replacing'
            call particle_set%write (summary=.true., compressed=.true.)
            call pylist (2)
        end if
        call determine_boost ()
        call count_valid_entries_in_pythia_record ()
        call particle_set%without_hadronic_remnants &
            (particles, n_tot_old, py_entries)
        if (DEBUG_SHOWER) then
            print *, 'n_tot_old = ', n_tot_old
            print *, 'py_entries = ', py_entries
        end if
        call prepare_temporary_objects_and_particles ()
        call add_particles_of_pythia ()
        if (boost_required) then
            where (pythia_particle) particles%p = L * particles%p
        end if
        call particle_set%replace (particles)
        call set_parent_child_relations_of_known_pythia_parents ()
        call set_parent_child_relations_of_color_strings_to_hadrons ()
        call give_orphans_backup_parents ()
        where ((particle_set%prt%status == PRT_OUTGOING .or. &
            particle_set%prt%status == PRT_VIRTUAL .or. &
            particle_set%prt%status == PRT_BEAM_REMNANT) .and. &
            particle_set%prt%has_children ()) &
            particle_set%prt%status = PRT_RESONANT
        if (DEBUG_SHOWER) then
            print *, 'Particle set after replacing'

```

```

        call particle_set%write (summary=.true., compressed=.true.)
    end if

contains

    <Shower PYTHIA6: combine with particle set: procedures>

    end subroutine pythia6_combine_with_particle_set

    <Shower PYTHIA6: combine with particle set: procedures>≡
    subroutine count_valid_entries_in_pythia_record ()
        integer :: pset_idx
        hadro_start = 0
        allocate (valid(N))
        valid = .false.
        FIND: do i = 5, N
            if (K(i,2) >= 91 .and. K(i,2) <= 94) then
                hadro_start = i
                exit FIND
            end if
        end do FIND
        do i = 5, N
            status = K(i,1)
            if (any (P(i,1:4) > eps0) .and. (status >= 1 .and. status <= 21)) then
                pset_idx = find_pythia_particle (i)
                if (pset_idx == 0) then
                    valid (i) = .true.
                end if
            end if
        end do
        py_entries = count (valid)
        allocate (old_index (py_entries))
        allocate (new_index (N))
    end subroutine count_valid_entries_in_pythia_record

    <Shower PYTHIA6: combine with particle set: procedures>+≡
    subroutine prepare_temporary_objects_and_particles ()
        allocate (pythia_particle (n_tot_old + py_entries))
        pythia_particle = .false.
        backup_parents = pack ([i, i=1, size (particles)], &
            (particles%get_status () == PRT_INCOMING .or. &
            particles%get_status () == PRT_OUTGOING))
    end subroutine prepare_temporary_objects_and_particles

    <Shower PYTHIA6: combine with particle set: procedures>+≡
    subroutine add_particles_of_pythia ()
        integer :: whizard_status
        dangling_col = 0
        dangling_anti_col = 0
        next_color = 500
        j = 1
        do i = 5, N
            status = K(i,1)
            if (valid(i)) then

```



```

      call assign_colors (color, anti_color)
      momentum = real ([P(i,4), P(i,1:3)], kind=default)
      pdg = K(i,2)
      parent = K(i,3)
      call find_model (model, pdg, model_in, model_hadrons)
      if (status <= 10) then
        whizard_status = PRT_OUTGOING
      else
        whizard_status = PRT_VIRTUAL
      end if
      call particles(n_tot_old + j)%init &
        (whizard_status, pdg, model, color, anti_color, momentum)
      old_index(j) = i
      new_index(i) = n_tot_old + j
      pythia_particle(n_tot_old + j) = .true.
      j = j + 1
    end if
  end do
end subroutine add_particles_of_pythia

```

(Shower PYTHIA6: combine with particle set: procedures)+≡

```

subroutine determine_boost ()
  type(vector4_t) :: sum_vec_in, sum_vec_out
  boost_required = .false.
  if (all (particle_set%prt(1:2)%flv%get_pdg_abs () >= ELECTRON .and. &
    particle_set%prt(1:2)%flv%get_pdg_abs () <= TAU)) then
    sum_vec_in = sum (particle_set%prt%p, &
      mask=particle_set%prt%get_status () == PRT_INCOMING)
    sum_vec_out = [zero, zero, zero, zero]
    do i = 1, N
      if (K(i,1) <= 10) then
        momentum = real ([P(i,4), P(i,1:3)], kind=default)
        sum_vec_out = sum_vec_out + momentum
      end if
    end do
    !sum_vec_out = sum (particles%p, &
      !mask=particles%get_status () == PRT_OUTGOING)
    if (DEBUG_SHOWER) then
      print *, 'sum_vec_in%p = ', sum_vec_in%p
      print *, 'sum_vec_out%p = ', sum_vec_out%p
    end if
    if (.not. nearly_equal (sum_vec_in%p(3), sum_vec_out%p(3), &
      abs_smallness = 1E-9_default, &
      rel_smallness = 1E-6_default)) then
      boost_required = .true.
      L = boost (sum_vec_in, sum_vec_out%p(0))
    end if
  end if
  if (DEBUG_SHOWER) then
    print *, 'boost_required = ', boost_required
  end if
end subroutine determine_boost

```

(Shower PYTHIA6: combine with particle set: procedures) +=

```

subroutine assign_colors (color, anti_color)
  integer, intent(out) :: color, anti_color
  if ((K(I,2) == 21) .or. (abs (K(I,2)) <= 8) .or. &
      (abs (K(I,2)) >= KSUSY1+1 .and. abs (K(I,2)) <= KSUSY1+8) .or. &
      (abs (K(I,2)) >= KSUSY2+1 .and. abs (K(I,2)) <= KSUSY2+8) .or. &
      (abs (K(I,2)) >= 1000 .and. abs (K(I,2)) <= 9999) .and. &
      hadro_start == 0) then
    if (dangling_col == 0 .and. dangling_anti_col == 0) then
      ! new color string
      ! Gluon and gluino only color octets implemented so far
      if (K(I,2) == 21 .or. K(I,2) == 1000021) then
        color = next_color
        dangling_col = color
        next_color = next_color + 1
        anti_color = next_color
        dangling_anti_col = anti_color
        next_color = next_color + 1
      else if (K(I,2) > 0) then ! particles have color
        color = next_color
        dangling_col = color
        anti_color = 0
        next_color = next_color + 1
      else if (K(I,2) < 0) then ! antiparticles have anticolor
        anti_color = next_color
        dangling_anti_col = anti_color
        color = 0
        next_color = next_color + 1
      end if
    else if(status == 1) then
      ! end of string
      color = dangling_anti_col
      anti_color = dangling_col
      dangling_col = 0
      dangling_anti_col = 0
    else
      ! inside the string
      if(dangling_col /= 0) then
        anti_color = dangling_col
        color = next_color
        dangling_col = next_color
        next_color = next_color +1
      else if(dangling_anti_col /= 0) then
        color = dangling_anti_col
        anti_color = next_color
        dangling_anti_col = next_color
        next_color = next_color +1
      else
        call msg_bug ("Couldn't assign colors")
      end if
    end if
  else
    color = 0
    anti_color = 0
  end if
end if

```

```

end if
end subroutine assign_colors

```

(Shower PYTHIA6: combine with particle set: procedures)+≡

```

subroutine set_parent_child_relations_of_known_pythia_parents ()
do j = 1, py_entries
parent = K(old_index(j),3)
child = n_tot_old + j
if (parent > 0) then
if (parent >= 1 .and. parent <= 2) then
call particle_set%parent_add_child (parent, child)
else
real_parent = find_pythia_particle (parent)
if (real_parent > 0 .and. real_parent /= child) then
call particle_set%parent_add_child (real_parent, child)
end if
end if
end if
end do
end subroutine set_parent_child_relations_of_known_pythia_parents

```

(Shower PYTHIA6: combine with particle set: procedures)+≡

```

subroutine set_parent_child_relations_of_color_strings_to_hadrons ()
integer :: begin_string, end_string, old_start, next_start, real_child
integer, allocatable, dimension(:) :: parents
if (hadro_start > 0) then
old_start = hadro_start
do
next_start = 0
FIND: do i = old_start + 1, N
if (K(i,2) >= 91 .and. K(i,2) <= 94) then
next_start = i
exit FIND
end if
end do FIND
begin_string = K(old_start,3)
do i = begin_string, N
if (K(i,1) == 11) then
end_string = i
exit
end if
end do
allocate (parents (end_string - begin_string + 1))
parents = 0
real_child = find_pythia_particle (old_start)
do i = begin_string, end_string
real_parent = find_pythia_particle (i)
if (real_parent > 0) then
call particle_set%prt(real_parent)%add_child (real_child)
parents (i - begin_string + 1) = real_parent
end if
end do
call particle_set%prt(real_child)%set_parents (parents)

```

```

        deallocate (parents)
        if (next_start == 0) exit
        old_start = next_start
    end do
end if
end subroutine set_parent_child_relations_of_color_strings_to_hadrons

```

(Shower PYTHIA6: combine with particle set: procedures)+≡

```

function find_pythia_particle (i) result (j)
    integer :: j
    integer, intent(in) :: i
    logical :: nb
    pdg = K(i,2)
    momentum = real([P(i,4), P(i,1:3)], kind=default)
    if (boost_required) then
        momentum = L * momentum
    end if
    j = particle_set%find_particle (pdg, momentum, &
        abs_smallness = 1E-9_default, &
        rel_smallness = 1E-6_default)
end function find_pythia_particle

```

(Shower PYTHIA6: combine with particle set: procedures)+≡

```

subroutine give_orphans_backup_parents ()
    do i = 1, size (particle_set%prt)
        if ((particle_set%prt(i)%status == PRT_OUTGOING .or. &
            particle_set%prt(i)%status == PRT_VIRTUAL .or. &
            particle_set%prt(i)%status == PRT_RESONANT) .and. .not. &
            particle_set%prt(i)%has_parents ()) then
            call particle_set%prt(i)%set_parents (backup_parents)
            do j = 1, size(backup_parents)
                call particle_set%prt(backup_parents(j))%add_child (i)
            end do
        end if
    end do
end subroutine give_orphans_backup_parents

```

(Shower PYTHIA6: procedures)+≡

```

subroutine get_ME_momenta_from_PYTHIA (jets_me)
    IMPLICIT DOUBLE PRECISION(A-H, O-Z)
    IMPLICIT INTEGER(I-N)
    COMMON/PYJETS/N,NPAD,K(4000,5),P(4000,5),V(4000,5)
    SAVE /PYJETS/

    type(vector4_t), dimension(:), allocatable :: jets_me
    integer :: i, j, n_jets

    if (allocated (jets_me)) deallocate (jets_me)

    if (signal_is_pending ()) return
    !!! final ME partons start in 7th row of event record
    i = 7
    !!! find number of jets

```

```

n_jets = 0
do
  if (K(I,1) /= 21) exit
  if ((K(I,2) == 21) .or. (abs(K(I,2)) <= 6)) then
    n_jets = n_jets + 1
  end if
  i = i + 1
end do

if (n_jets == 0) return
allocate (jets_me(1:n_jets))

!!! transfer jets
i = 7
j = 1
do
  if (K(I,1) /= 21) exit
  if ((K(I,2) == 21) .or. (abs(K(I,2)) <= 6)) then
    jets_me(j) = real ([P(i,4), P(i,1:3)], kind=default)
    j = j + 1
  end if
  i = i + 1
end do
end subroutine get_ME_momenta_from_PYTHIA

```

<Shower PYTHIA6: public>+≡
 public :: pylheo

<Shower PYTHIA6: procedures>+≡
 !!!!!!!!!!!PYTHIA STYLE!!!!!!!!!!!!!!
 !!! originally PYLHEF subroutine from PYTHIA 6.4.22

!C...Write out the showered event to a Les Houches Event File.

subroutine pylheo (u_P2W)

!C...Double precision and integer declarations.

IMPLICIT DOUBLE PRECISION(A-H, O-Z)

IMPLICIT INTEGER(I-N)

integer, intent(in) :: u_P2W

!C...PYTHIA commonblock: only used to provide read/write units and version.

common /PYPARS/ MSTP(200), PARP(200), MSTI(200), PARI(200)

common /PYJETS/ N, NPAD, K(4000,5), P(4000,5), V(4000,5)

save /PYPARS/

save /PYJETS/

!C...User process initialization commonblock.

!C...User process event common block.

integer, parameter :: MAXPUP = 100, MAXNUP = 500

integer :: IDBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP, LPRUP

integer :: NUP, IDPRUP, IDUP, ISTUP, MOTHUP, ICOLUP

real(double) :: EBMUP, XSECUP, XERRUP, XMAXUP

real(double) :: XWGTUP, SCALUP, AQEDUP, AQCDUP, PUP, VTIMUP, SPINUP

```

integer, parameter :: KSUSY1 = 1000000, KSUSY2 = 2000000
common /HEPRUP/ &
    IDBMUP(2), EBMUP(2), PDFGUP(2), PDFSUP(2), IDWTUP, NPRUP, &
    XSECUP(MAXPUP), XERRUP(MAXPUP), XMAXUP(MAXPUP), LPRUP(MAXPUP)
save /HEPRUP/
common /HEPEUP/ &
    NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP, IDUP(MAXNUP), &
    ISTUP(MAXNUP), MOTHUP(2,MAXNUP), ICOLUP(2,MAXNUP), &
    PUP(5,MAXNUP), VTIMUP(MAXNUP), SPINUP(MAXNUP)
save /HEPEUP/

!C...Lines to read in assumed never longer than 200 characters.
PARAMETER (MAXLEN=200)
character(len=maxlen) :: string

integer :: LEN, ndangling_color, ndangling_antic, ncolor

!C...Format for reading lines.
character(len=6) :: strfmt
STRFMT='(A000)'
write (STRFMT(3:5),'(I3)') MAXLEN

!C...Rewind initialization and event files.
rewind MSTP(161)
rewind MSTP(162)

!C...Write header info.
write (u_P2W, "(A)")  '<LesHouchesEvents version="1.0">'
write (u_P2W, "(A)")  "<!--"
write (u_P2W, "(A,I1,A1,I3)")  "File generated with PYTHIA ", &
    MSTP(181), ".", MSTP(182)
write (u_P2W, "(A)")  " and the WHIZARD2 interface"
write (u_P2W, "(A)")  "-->"

!C...Loop until finds line beginning with "<init>" or "<init ".
100 READ(MSTP(161),STRFMT,END=400,ERR=400) STRING
    IBEG=0
110 IBEG=IBEG+1
!C...Allow indentation.
IF (STRING(IBEG:IBEG).EQ.' '.AND.IBEG.LT.MAXLEN-5) GOTO 110
IF (STRING(IBEG:IBEG+5).NE.'<init>'.AND.STRING(IBEG:IBEG+5).NE.'<init ') GOTO 100

!C...Read first line of initialization info and get number of processes.
READ(MSTP(161),'(A)',END=400,ERR=400) STRING
READ(STRING,*,ERR=400) IDBMUP(1),IDBMUP(2),EBMUP(1),EBMUP(2),PDFGUP(1),PDFGUP(2),PDFSUP(1),PDF
!C...Copy initialization lines, omitting trailing blanks.
!C...Embed in <init> ... </init> block.
WRITE(u_P2W,'(A)') '<init>'
do IPR = 0, NPRUP
    IF(IPR.GT.0) READ(MSTP(161),'(A)',END=400,ERR=400) STRING
    LEN=MAXLEN+1
120    LEN=LEN-1
    IF (LEN.GT.1.AND.STRING(LEN:LEN).EQ.' ') GOTO 120

```

```

        WRITE(u_P2W,'(A)',ERR=400) STRING(1:LEN)
    end DO
    write (u_P2W, "(A)") "</init>"

    !!! Find the numbers of entries of the <event block>
    NENTRIES = 0
    do I = 1, N
        if (K(I,1) == 1 .or. K(I,1) == 2 .or. K(I,1) == 21) then
            NENTRIES = NENTRIES + 1
        end if
    end do

    !C...Begin an <event> block. Copy event lines, omitting trailing blanks.
    write (u_P2W, "(A)") "<event>"
    write (u_P2W, *) NENTRIES, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP

    ndangling_color = 0
    ncolor = 0
    ndangling_antic = 0
    NANTIC = 0
    NNEXTC = 1 ! TODO find next free color number ??
    do I = 1, N
        if (signal_is_pending ()) return
        if ((K(I,1) >= 1 .and. K(I,1) <= 15) .or. (K(I,1) == 21)) then
            if ((K(I,2).eq.21) .or. (IABS(K(I,2)) <= 8) .or. &
                (IABS(K(I,2)) >= KSUSY1+1 .and. IABS(K(I,2)) <= KSUSY1+8) &
                .or. &
                (IABS(K(I,2)) >= KSUSY2+1 .and. IABS(K(I,2)) <= KSUSY2+8) .or. &
                (IABS(K(I,2)) >= 1000 .and. IABS(K(I,2)) <= 9999) ) then
                if (ndangling_color.eq.0 .and. ndangling_antic.eq.0) then
                    ! new color string
                    ! Gluon and gluino only color octets implemented so far
                    if (K(I,2).eq.21 .or. K(I,2).eq.1000021) then
                        ncolor = NNEXTC
                        ndangling_color = ncolor
                        NNEXTC = NNEXTC + 1
                        NANTIC = NNEXTC
                        ndangling_antic = NANTIC
                        NNEXTC = NNEXTC + 1
                    else if (K(I,2) .gt. 0) then ! particles to have color
                        ncolor = NNEXTC
                        ndangling_color = ncolor
                        NANTIC = 0
                        NNEXTC = NNEXTC + 1
                    else if (K(I,2) .lt. 0) then ! antiparticles to have anticolor
                        NANTIC = NNEXTC
                        ndangling_antic = NANTIC
                        ncolor = 0
                        NNEXTC = NNEXTC + 1
                    end if
                else if(K(I,1).eq.1) then
                    ! end of string
                    ncolor = ndangling_antic
                    NANTIC = ndangling_color
                end if
            end if
        end if
    end do

```

```

        ndangling_color = 0
        ndangling_antic = 0
    else
        ! inside the string
        if(ndangling_color .ne. 0) then
            NANTIC = ndangling_color
            ncolor = NNEXTC
            ndangling_color = NNEXTC
            NNEXTC = NNEXTC +1
        else if(ndangling_antic .ne. 0) then
            ncolor = ndangling_antic
            NANTIC = NNEXTC
            ndangling_antic = NNEXTC
            NNEXTC = NNEXTC +1
        else
            print *, "ERROR IN PYLHEO"
        end if
    end if
else
    ncolor = 0
    NANTIC = 0
end if
!!! As no intermediate are given out here, assume the
!!! incoming partons to be the mothers
write (u_P2W,*) K(I,2), K(I,1), K(I,3), K(I,3), &
    ncolor, NANTIC, (P(I,J),J=1,5), 0, -9
end if
end do

!C..End the <event> block. Loop back to look for next event.
write (MSTP(163), "(A)") "</event>"

!C...Successfully reached end of event loop: write closing tag
!C...and remove temporary intermediate files (unless asked not to).
write (MSTP(163), "(A)") "</LesHouchesEvents>"
return

!!C...Error exit.
400 write(*,*) ' PYLHEO file joining failed!'

return
end subroutine pylheo

```

```

<Shower PYTHIA6: public>+≡
    public :: pythia6_setup_lhe_io_units
<Shower PYTHIA6: procedures>+≡
    subroutine pythia6_setup_lhe_io_units (u_W2P, u_P2W)
        integer, intent(out) :: u_W2P
        integer, intent(out), optional :: u_P2W
        character(len=10) :: buffer
        u_W2P = free_unit ()
        if (DEBUG_SHOWER) then
            open (unit=u_W2P, status="replace", file="whizardout.lhe", &

```



```

        action="readwrite")
    else
        open (unit=u_W2P, status="scratch", action="readwrite")
    end if
    write (buffer, "(I10)" u_W2P
    call pygive ("MSTP(161)=" // buffer) !!! Unit for PYUPIN (LHA)
    call pygive ("MSTP(162)=" // buffer) !!! Unit for PYUPEV (LHA)
    if (present (u_P2W)) then
        u_P2W = free_unit ()
        write (buffer, "(I10)" u_P2W
        call pygive ("MSTP(163)=" // buffer)
        if (DEBUG_SHOWER) then
            open (unit=u_P2W, file="pythiaout2.lhe", status="replace", &
                action="readwrite")
        else
            open (unit=u_P2W, status="scratch", action="readwrite")
        end if
    end if
end if
end subroutine pythia6_setup_lhe_io_units

```

<Shower PYTHIA6: public>+≡

```
public :: pythia6_set_config
```

<Shower PYTHIA6: procedures>+≡

```

subroutine pythia6_set_config (pygive_all)
    type(string_t), intent(in) :: pygive_all
    type(string_t) :: pygive_remaining, pygive_partial
    if (len (pygive_all) > 0) then
        pygive_remaining = pygive_all
        do while (len (pygive_remaining) > 0)
            call split (pygive_remaining, pygive_partial, ";")
            call pygive (char (pygive_partial))
        end do
        if (pythia6_get_error() /= 0) then
            call msg_fatal &
                (" PYTHIA6 did not recognize ps_PYTHIA_PYGIVE setting.")
        end if
    end if
end subroutine pythia6_set_config

```

Exchanging error messages with PYTHIA6.

<Shower PYTHIA6: public>+≡

```
public :: pythia6_set_error
```

<Shower PYTHIA6: procedures>+≡

```

subroutine pythia6_set_error (mstu23)
    IMPLICIT DOUBLE PRECISION(A-H, O-Z)
    IMPLICIT INTEGER(I-N)
    COMMON/PYDAT1/MSTU(200),PARU(200),MSTJ(200),PARJ(200)
    SAVE/PYDAT1/
    integer, intent(in) :: mstu23
    MSTU(23) = mstu23
end subroutine pythia6_set_error

```



```

C*
C*          SUSY and Technicolor parts by
C*          Stephen Mrenna
C*          Computing Division
C*          Generators and Detector Simulation Group
C*          Fermi National Accelerator Laboratory
C*          MS 234, Batavia, IL 60510, USA
C*          phone + 1 - 630 - 840 - 2556
C*          E-mail mrenna@fnal.gov
C*
C*
C*          New multiple interactions and more SUSY parts by
C*          Peter Skands
C*          CERN/PH, CH-1211 Geneva, Switzerland
C*          phone +41 - 22 - 767 2447
C*          E-mail peter.skands@cern.ch
C*
C*
C*          Several parts are written by Hans-Uno Bengtsson
C*          PYSHOW is written together with Mats Bengtsson
C*          PYMAEL is written by Emanuel Norrbin
C*          advanced popcorn baryon production written by Patrik Eden
C*          code for virtual photons mainly written by Christer Friberg
C*          code for low-mass strings mainly written by Emanuel Norrbin
C*          Bose-Einstein code mainly written by Leif Lonnblad
C*          CTEQ parton distributions are by the CTEQ collaboration
C*          GRV 94 parton distributions are by Glueck, Reya and Vogt
C*          SaS photon parton distributions together with Gerhard Schuler
C*          g + g and q + qbar -> t + tbar + H code by Zoltan Kunszt
C*          MSSM Higgs mass calculation code by M. Carena,
C*          J.R. Espinosa, M. Quiros and C.E.M. Wagner
C*          UED implementation by M. Elkacimi, D. Goujdami, H. Przysiezniak
C*          PYGAUS adapted from CERN library (K.S. Kolbig)
C*          NRQCD/colour octet production of onium by S. Wolf
C*
C*
C*          The latest program version and documentation is found on WWW
C*          http://www.thep.lu.se/~torbjorn/Pythia.html
C*
C*
C*          Copyright Torbjorn Sjostrand, Lund 2010
C*
C*****
C*****

```

(pythia6_up.f)+≡

```

C...UPINIT
C...Is supposed to fill the HEPRUP commonblock with info
C...on incoming beams and allowed processes.

```

SUBROUTINE UPINIT

```

C...Double precision and integer declarations.
      IMPLICIT DOUBLE PRECISION(A-H, O-Z)
      IMPLICIT INTEGER(I-N)

```

```

C...PYTHIA commonblock: only used to provide read unit MSTP(161).
      COMMON/PYPARS/MSTP(200),PARP(200),MSTI(200),PARI(200)

```

```

        SAVE /PYPARS/

C...User process initialization commonblock.
        INTEGER MAXPUP
        PARAMETER (MAXPUP=100)
        INTEGER IDBMUP,PDFGUP,PDFSUP,IDWTUP,NPRUP,LPRUP
        DOUBLE PRECISION EBMUP,XSECUP,XERRUP,XMAXUP
        COMMON/HEPRUP/IDBMUP(2),EBMUP(2),PDFGUP(2),PDFSUP(2),
        &IDWTUP,NPRUP,XSECUP(MAXPUP),XERRUP(MAXPUP),XMAXUP(MAXPUP),
        &LPRUP(MAXPUP)
        SAVE /HEPRUP/

C...Lines to read in assumed never longer than 200 characters.
        PARAMETER (MAXLEN=200)
        CHARACTER*(MAXLEN) STRING

C...Format for reading lines.
        CHARACTER(len=6) STRFMT
        STRFMT='(A000)'
        WRITE(STRFMT(3:5),'(I3)') MAXLEN

C...Loop until finds line beginning with "<init>" or "<init ".
        100 READ(MSTP(161),STRFMT,END=130,ERR=130) STRING
        IBEG=0
        110 IBEG=IBEG+1
C...Allow indentation.
        IF(STRING(IBEG:IBEG).EQ.' '.AND.IBEG.LT.MAXLEN-5) GOTO 110
        IF(STRING(IBEG:IBEG+5).NE.'<init>'.AND.
        &STRING(IBEG:IBEG+5).NE.'<init ') GOTO 100

C...Read first line of initialization info.
        READ(MSTP(161),*,END=130,ERR=130) IDBMUP(1),IDBMUP(2),EBMUP(1),
        &EBMUP(2),PDFGUP(1),PDFGUP(2),PDFSUP(1),PDFSUP(2),IDWTUP,NPRUP

C...Read NPRUP subsequent lines with information on each process.
        DO 120 IPR=1,NPRUP
            READ(MSTP(161),*,END=130,ERR=130) XSECUP(IPR),XERRUP(IPR),
            & XMAXUP(IPR),LPRUP(IPR)
        120 CONTINUE
        RETURN

C...Error exit: give up if initialization does not work.
        130 WRITE(*,*) ' Failed to read LHEF initialization information.'
        WRITE(*,*) ' Event generation will be stopped.'
        CALL PYSTOP(12)

        RETURN
        END

<pythia6_up.f>+≡
C...UPEVNT
C...Dummy routine, to be replaced by a user implementing external
C...processes. Depending on cross section model chosen, it either has
C...to generate a process of the type IDPRUP requested, or pick a type

```

C...itself and generate this event. The event is to be stored in the C...HEPEUP commonblock, including (often) an event weight.

C...New example: handles a standard Les Houches Events File.

```
SUBROUTINE UPEVNT
```

C...Double precision and integer declarations.

```
IMPLICIT DOUBLE PRECISION(A-H, O-Z)
IMPLICIT INTEGER(I-N)
```

C...PYTHIA commonblock: only used to provide read unit MSTP(162).

```
COMMON/PYPARS/MSTP(200),PARP(200),MSTI(200),PARI(200)
SAVE /PYPARS/
```

C...Added by WHIZARD

```
COMMON/PYDAT1/MSTU(200),PARU(200),MSTJ(200),PARJ(200)
SAVE/PYDAT1/
```

C...User process event common block.

```
INTEGER MAXNUP
PARAMETER (MAXNUP=500)
INTEGER NUP,IDPRUP,IDUP,ISTUP,MOTHUP,ICOLUP
DOUBLE PRECISION XWGTUP,SCALUP,AQEDUP,AQCDUP,PUP,VTIMUP,SPINUP
COMMON/HEPEUP/NUP,IDPRUP,XWGTUP,SCALUP,AQEDUP,AQCDUP,IDUP(MAXNUP),
&ISTUP(MAXNUP),MOTHUP(2,MAXNUP),ICOLUP(2,MAXNUP),PUP(5,MAXNUP),
&VTIMUP(MAXNUP),SPINUP(MAXNUP)
SAVE /HEPEUP/
```

C...Lines to read in assumed never longer than 200 characters.

```
PARAMETER (MAXLEN=200)
CHARACTER*(MAXLEN) STRING
```

C...Format for reading lines.

```
CHARACTER(len=6) STRFMT
STRFMT='(A000)'
WRITE(STRFMT(3:5),'(I3)') MAXLEN
```

C...Loop until finds line beginning with "<event>" or "<event ".

```
100 READ(MSTP(162),STRFMT,END=130,ERR=130) STRING
IBEG=0
110 IBEG=IBEG+1
```

C...Allow indentation.

```
IF(STRING(IBEG:IBEG).EQ.' ' .AND. IBEG.LT.MAXLEN-6) GOTO 110
IF(STRING(IBEG:IBEG+6).NE.'<event>' .AND.
&STRING(IBEG:IBEG+6).NE.'<event ') GOTO 100
```

C...Read first line of event info.

```
READ(MSTP(162),*,END=130,ERR=130) NUP,IDPRUP,XWGTUP,SCALUP,
&AQEDUP,AQCDUP
```

C...Read NUP subsequent lines with information on each particle.

```
DO 120 I=1,NUP
READ(MSTP(162),*,END=130,ERR=130) IDUP(I),ISTUP(I),
```

```

      & MOTHUP(1,I),MOTHUP(2,I),ICOLUP(1,I),ICOLUP(2,I),
      & (PUP(J,I),J=1,5),VTIMUP(I),SPINUP(I)
120 CONTINUE
      RETURN

C...Error exit, typically when no more events.
130 CONTINUE
C      WRITE(*,*) ' Failed to read LHEF event information.'
C      WRITE(*,*) ' Will assume end of file has been reached.'
      NUP=0
      MSTI(51)=1
C...Added by WHIZARD, mark these failed events
      MSTU(23)=1

      RETURN
      END

(pythia6_up.f)+≡
C...UPVETO
C...Dummy routine, to be replaced by user, to veto event generation
C...on the parton level, after parton showers but before multiple
C...interactions, beam remnants and hadronization is added.
C...If resonances like W, Z, top, Higgs and SUSY particles are handed
C...undecayed from UPEVNT, or are generated by PYTHIA, they will also
C...be undecayed at this stage; if decayed their decay products will
C...have been allowed to shower.

C...All partons at the end of the shower phase are stored in the
C...HEPEVT commonblock. The interesting information is
C...NHEP = the number of such partons, in entries 1 <= i <= NHEP,
C...IDHEP(I) = the particle ID code according to PDG conventions,
C...PHEP(J,I) = the (p_x, p_y, p_z, E, m) of the particle.
C...All ISTHEP entries are 1, while the rest is zeroed.

C...The user decision is to be conveyed by the IVETO value.
C...IVETO = 0 : retain current event and generate in full;
C...      = 1 : abort generation of current event and move to next.

      SUBROUTINE UPVETO(IVETO)

C...HEPEVT commonblock.
      PARAMETER (NMXHEP=4000)
      COMMON/HEPEVT/NEVHEP,NHEP,ISTHEP(NMXHEP),IDHEP(NMXHEP),
      &JMOHEP(2,NMXHEP),JDAHEP(2,NMXHEP),PHEP(5,NMXHEP),VHEP(4,NMXHEP)
      DOUBLE PRECISION PHEP,VHEP
      SAVE /HEPEVT/

C...Next few lines allow you to see what info PYVETO extracted from
C...the full event record for the first two events.
C...Delete if you don't want it.
      DATA NLIST/0/
      SAVE NLIST
      IF(NLIST.LE.2) THEN
        WRITE(*,*) ' Full event record at time of UPVETO call:'

```

```

        CALL PYLIST(1)
        WRITE(*,*) ' Part of event record made available to UPVETO:'
        CALL PYLIST(5)
        NLIST=NLIST+1
    ENDIF

C...Make decision here.
    IVETO = 0

    RETURN
END

```

20.5 Matching

20.5.1 MLM matching

```

<mlm_matching.f90>≡
<File header>

module mlm_matching

<Use kinds with double>
<Use strings>
    use io_units
    use constants
    use format_utils, only: write_separator
    use diagnostics
    use file_utils
    use lorentz
    use shower_base
    use variables

<Standard module head>

<MLM matching: public>

<MLM matching: types>

contains

<MLM matching: procedures>

end module mlm_matching
<MLM matching: public>≡
    public :: mlm_matching_settings_t
<MLM matching: types>≡
    type, extends (matching_settings_t) :: mlm_matching_settings_t
        real(default) :: mlm_Qcut_ME = one
        real(default) :: mlm_Qcut_PS = one
        real(default) :: mlm_ptmin, mlm_etamax, mlm_Rmin, mlm_Emin
        real(default) :: mlm_ETclusfactor = 0.2_default

```

```

    real(default) :: mlm_ETclusminE = five
    real(default) :: mlm_etaclusfactor = one
    real(default) :: mlm_Rclusfactor = one
    real(default) :: mlm_Eclusfactor = one
    integer :: kt_imode_hadronic = 4313
    integer :: kt_imode_leptonic = 1111
    integer :: mlm_nmaxMEjets = 0
contains
  <MLM matching: MLM matching: TBP>
end type mlm_matching_settings_t

```

```

<MLM matching: MLM matching: TBP>≡
  procedure :: init => mlm_matching_settings_init

```

```

<MLM matching: procedures>≡
  subroutine mlm_matching_settings_init (settings, var_list)
    class(mlm_matching_settings_t), intent(out) :: settings
    type(var_list_t), intent(in) :: var_list
    settings%mlm_Qcut_ME = &
      var_list%get_rval (var_str ("mlm_Qcut_ME"))
    settings%mlm_Qcut_PS = &
      var_list%get_rval (var_str ("mlm_Qcut_PS"))
    settings%mlm_ptmin = &
      var_list%get_rval (var_str ("mlm_ptmin"))
    settings%mlm_etamax = &
      var_list%get_rval (var_str ("mlm_etamax"))
    settings%mlm_Rmin = &
      var_list%get_rval (var_str ("mlm_Rmin"))
    settings%mlm_Emin = &
      var_list%get_rval (var_str ("mlm_Emin"))
    settings%mlm_nmaxMEjets = &
      var_list%get_ival (var_str ("mlm_nmaxMEjets"))

    settings%mlm_ETclusfactor = &
      var_list%get_rval (var_str ("mlm_ETclusfactor"))
    settings%mlm_ETclusminE = &
      var_list%get_rval (var_str ("mlm_ETclusminE"))
    settings%mlm_etaclusfactor = &
      var_list%get_rval (var_str ("mlm_etaclusfactor"))
    settings%mlm_Rclusfactor = &
      var_list%get_rval (var_str ("mlm_Rclusfactor"))
    settings%mlm_Eclusfactor = &
      var_list%get_rval (var_str ("mlm_Eclusfactor"))
  end subroutine mlm_matching_settings_init

```

```

<MLM matching: MLM matching: TBP>+≡
  procedure :: write => mlm_matching_settings_write

```

```

<MLM matching: procedures>+≡
  subroutine mlm_matching_settings_write (settings, unit)
    class(mlm_matching_settings_t), intent(in) :: settings
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return

```



```

write (u, "(3x,A,ES19.12)") &
  "mlm_Qcut_ME" = ", settings%mlm_Qcut_ME
write (u, "(3x,A,ES19.12)") &
  "mlm_Qcut_PS" = ", settings%mlm_Qcut_PS
write (u, "(3x,A,ES19.12)") &
  "mlm_ptmin" = ", settings%mlm_ptmin
write (u, "(3x,A,ES19.12)") &
  "mlm_etamax" = ", settings%mlm_etamax
write (u, "(3x,A,ES19.12)") &
  "mlm_Rmin" = ", settings%mlm_Rmin
write (u, "(3x,A,ES19.12)") &
  "mlm_Emin" = ", settings%mlm_Emin
write (u, "(3x,A,1x,I0)") &
  "mlm_nmaxMEjets" = ", settings%mlm_nmaxMEjets
write (u, "(3x,A,ES19.12)") &
  "mlm_ETclusfactor (D=0.2)" = ", settings%mlm_ETclusfactor
write (u, "(3x,A,ES19.12)") &
  "mlm_ETclusminE (D=5.0)" = ", settings%mlm_ETclusminE
write (u, "(3x,A,ES19.12)") &
  "mlm_etaclusfactor (D=1.0)" = ", settings%mlm_etaClusfactor
write (u, "(3x,A,ES19.12)") &
  "mlm_Rclusfactor (D=1.0)" = ", settings%mlm_RClusfactor
write (u, "(3x,A,ES19.12)") &
  "mlm_Eclusfactor (D=1.0)" = ", settings%mlm_EClusfactor
end subroutine mlm_matching_settings_write

```

This is a container for the (colored) parton momenta as well as the jet momenta.

```

<MLM matching: public>+≡
  public :: mlm_matching_data_t

<MLM matching: types>+≡
  type, extends (matching_data_t) :: mlm_matching_data_t
    type(vector4_t), dimension(:), allocatable, public :: P_ME
    type(vector4_t), dimension(:), allocatable, public :: P_PS
    type(vector4_t), dimension(:), allocatable, private :: JETS_ME
    type(vector4_t), dimension(:), allocatable, private :: JETS_PS
  end type mlm_matching_data_t

<MLM matching: public>+≡
  public :: mlm_matching_data_write

<MLM matching: procedures>+≡
  subroutine mlm_matching_data_write (data, unit)
    type(mlm_matching_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    integer :: i
    integer :: u
    u = given_output_unit (unit); if (u < 0) return

    write (u, "(1x,A)") "MLM matching data:"
    write (u, "(3x,A)") "Momenta of ME partons:"
    if (allocated (data%P_ME)) then
      do i = 1, size (data%P_ME)
        write (u, "(4x)", advance = "no")

```

```

        call vector4_write (data%P_ME(i), unit = u)
    end do
else
    write (u, "(5x,A)") "[empty]"
end if
call write_separator (u)
write (u, "(3x,A)") "Momenta of ME jets:"
if (allocated (data%JETS_ME)) then
    do i = 1, size (data%JETS_ME)
        write (u, "(4x)", advance = "no")
        call vector4_write (data%JETS_ME(i), unit = u)
    end do
else
    write (u, "(5x,A)") "[empty]"
end if
call write_separator (u)
write(u, "(3x,A)") "Momenta of shower partons:"
if (allocated (data%P_PS)) then
    do i = 1, size (data%P_PS)
        write (u, "(4x)", advance = "no")
        call vector4_write (data%P_PS(i), unit = u)
    end do
else
    write (u, "(5x,A)") "[empty]"
end if
call write_separator (u)
write (u, "(3x,A)") "Momenta of shower jets:"
if (allocated (data%JETS_PS)) then
    do i = 1, size (data%JETS_PS)
        write (u, "(4x)", advance = "no")
        call vector4_write (data%JETS_PS(i), unit = u)
    end do
else
    write (u, "(5x,A)") "[empty]"
end if
call write_separator (u)
end subroutine mlm_matching_data_write

```

<MLM matching: public>+≡

```
public :: mlm_matching_data_final
```

<MLM matching: procedures>+≡

```

subroutine mlm_matching_data_final (data)
    type(mlm_matching_data_t), intent(inout) :: data
    ! if (allocated (data%P_ME)) deallocate(data%P_ME)
    if (allocated (data%P_PS)) deallocate (data%P_PS)
    if (allocated (data%JETS_ME)) deallocate(data%JETS_ME)
    if (allocated (data%JETS_PS)) deallocate(data%JETS_PS)
end subroutine mlm_matching_data_final

```

<MLM matching: public>+≡

```
public :: mlm_matching_apply
```

```

<MLM matching: procedures>+≡
  subroutine mlm_matching_apply (data, settings, vetoed)
    type(mlm_matching_data_t), intent(inout) :: data
    type(mlm_matching_settings_t), intent(in) :: settings
    logical, intent(out) :: vetoed

    integer :: i, j
    integer :: n_jets_ME, n_jets_PS, n_jets_PS_atycut
    real(double) :: ycut
    real(double), dimension(:, :), allocatable :: PP
    real(double), dimension(:), allocatable :: Y
    real(double), dimension(:, :), allocatable :: P_JETS
    real(double), dimension(:, :), allocatable :: P_ME
    integer, dimension(:), allocatable :: JET
    integer :: NJET, NSUB
    integer :: imode
    !!! TODO: (bcn 2014-03-26) Why is ECUT hard coded to 1?
    !!! It is the denominator of the KT measure. Candidate for removal
    real(double) :: ECUT = 1._double
    integer :: ip1, ip2

    ! KTCLUS COMMON BLOCK
    INTEGER NMAX, NUM, HIST
    PARAMETER (NMAX=512)
    DOUBLE PRECISION P, KT, KTP, KTS, ETOT, RSQ, KTLAST
    COMMON /KTCOMM/ETOT, RSQ, P(9, NMAX), KTP(NMAX, NMAX), KTS(NMAX), &
      KT(NMAX), KTLAST(NMAX), HIST(NMAX), NUM

    vetoed = .true.
    if (signal_is_pending ()) return

    <Set n_jets_ME/PS from data (or equal zero)>

    <Jet clustering for partons after matrix element>

    <Jet clustering for partons after shower>

    <Veto: too many or not enough jets after PS>

    <Cluster ME jets with PS jets one at a time>

    vetoed = .false.
999 continue
  end subroutine mlm_matching_apply

<Set n_jets_ME/PS from data (or equal zero)>≡
  if (allocated (data%P_ME)) then
    ! print *, "number of partons after ME: ", size(data%P_ME)
    n_jets_ME = size (data%P_ME)
  else
    n_jets_ME = 0
  end if
  if (allocated (data%p_PS)) then
    ! print *, "number of partons after PS: ", size(data%p_PS)

```

```

        n_jets_PS = size (data%p_PS)
    else
        n_jets_PS = 0
    end if

    <Jet clustering for partons after matrix element>≡
    if (n_jets_ME > 0) then
        ycut = (settings%mlm_ptmin)**2
        allocate (PP(1:4, 1:N_jets_ME))
        do i = 1, n_jets_ME
            PP(1:3,i) = data%p_ME(i)%p(1:3)
            PP(4,i) = data%p_ME(i)%p(0)
        end do

        <Set imode for lepton or hadron collisions>

        allocate (P_ME(1:4,1:n_jets_ME))
        allocate (JET(1:n_jets_ME))
        allocate (Y(1:n_jets_ME))

        if (signal_is_pending ()) return
        call KTCLUR (imode, PP, n_jets_ME, &
            dble (settings%mlm_Rclusfactor * settings%mlm_Rmin), ECUT, y, *999)
        call KTRECO (1, PP, n_jets_ME, ECUT, ycut, ycut, P_ME, JET, &
            NJET, NSUB, *999)

        n_jets_ME = NJET
        if (NJET > 0) then
            allocate (data%JETS_ME (1:NJET))
            do i = 1, NJET
                data%JETS_ME(i) = vector4_moving (REAL(P_ME(4,i), default), &
                    vector3_moving([REAL(P_ME(1,i), default), &
                        REAL(P_ME(2,i), default), REAL(P_ME(3,i), default)]))
            end do
        end if
        deallocate (P_ME)
        deallocate (JET)
        deallocate (Y)
        deallocate (PP)
    end if

    <Jet clustering for partons after shower>≡
    if (n_jets_PS > 0) then
        ycut = (settings%mlm_ptmin + max (settings%mlm_ETclusminE, &
            settings%mlm_ETclusfactor * settings%mlm_ptmin))**2
        allocate (PP(1:4, 1:n_jets_PS))
        do i = 1, n_jets_PS
            PP(1:3,i) = data%p_PS(i)%p(1:3)
            PP(4,i) = data%p_PS(i)%p(0)
        end do

        <Set imode for lepton or hadron collisions>

        allocate (P_JETS(1:4,1:n_jets_PS))
        allocate (JET(1:n_jets_PS))

```

```

allocate (Y(1:n_jets_PS))

if (signal_is_pending ()) return
call KTCLUR (imode, PP, n_jets_PS, &
             dble (settings%mlm_Rclusfactor * settings%mlm_Rmin), &
             ECUT, y, *999)
call KTRECO (1, PP, n_jets_PS, ECUT, ycut, ycut, P_JETS, JET, &
             NJET, NSUB, *999)
n_jets_PS_atycut = NJET
if (n_jets_ME == settings%mlm_nmaxMEjets .and. NJET > 0) then
    ! print *, " resetting ycut to ", Y(settings%mlm_nmaxMEjets)
    ycut = y(settings%mlm_nmaxMEjets)
    call KTRECO (1, PP, n_jets_PS, ECUT, ycut, ycut, P_JETS, JET, &
                 NJET, NSUB, *999)
end if

! !Sample of code for a FastJet interface
! palg = 1d0          ! 1.0d0 = kt, 0.0d0 = Cam/Aachen, -1.0d0 = anti-kt
! R = 0.7_double      ! radius parameter
! f = 0.75_double     ! overlap threshold
! !call fastjetppgenkt(PP,n,R,palg,P_JETS,NJET) ! KT-Algorithm
! !call fastjetsiscone(PP,n,R,f,P_JETS,NJET)   ! SiSCone-Algorithm

if (NJET > 0) then
    allocate (data%JETS_PS(1:NJET))
    do i = 1, NJET
        data%JETS_PS(i) = vector4_moving (REAL(P_JETS(4,i), default), &
                                           vector3_moving([REAL(P_JETS(1,i), default), &
                                                             REAL(P_JETS(2,i), default), REAL(P_JETS(3,i), default)]))
    end do
end if

deallocate (P_JETS)
deallocate (JET)
deallocate (Y)
else
    n_jets_PS_atycut = 0
end if

<Set imode for lepton or hadron collisions>≡
if (data%is_hadron_collision) then
    imode = settings%kt_imode_hadronic
else
    imode = settings%kt_imode_leptonic
end if

<Veto: too many or not enough jets after PS>≡
if (n_jets_PS_atycut < n_jets_ME) then
    ! print *, "DISCARDING: Not enough PS jets: ", n_jets_PS_atycut
    return
end if
if (n_jets_PS_atycut > n_jets_ME .and. n_jets_ME /= settings%mlm_nmaxMEjets) then
    ! print *, "DISCARDING: Too many PS jets: ", n_jets_PS_atycut
    return
end if

```

```

<Cluster ME jets with PS jets one at a time>≡
  if (allocated(data%JETS_PS)) then
    ! print *, "number of jets after PS: ", size(data%JETS_PS)
    n_jets_PS = size (data%JETS_PS)
  else
    n_jets_PS = 0
  end if
  if (n_jets_ME > 0 .and. n_jets_PS > 0) then
    n_jets_PS = size (data%JETS_PS)
    if (allocated (PP)) deallocate(PP)
    allocate (PP(1:4, 1:n_jets_PS + 1))
    do i = 1, n_jets_PS
      if (signal_is_pending ()) return
      PP(1:3,i) = data%JETS_PS(i)%p(1:3)
      PP(4,i) = data%JETS_PS(i)%p(0)
    end do
    if (allocated (Y)) deallocate(Y)
    allocate (Y(1:n_jets_PS + 1))
    y = zero
    do i = 1, n_jets_ME
      PP(1:3,n_jets_PS + 2 - i) = data%JETS_ME(i)%p(1:3)
      PP(4,n_jets_PS + 2 - i) = data%JETS_ME(i)%p(0)
      !!! This makes more sense than hardcoding
      ! call KTCLUS (4313, PP, (n_jets_PS + 2 - i), 1.0_double, Y, *999)
      call KTCLUR (imode, PP, (n_jets_PS + 2 - i), &
        dble (settings%mlm_Rclusfactor * settings%mlm_Rmin), &
        ECUT, y, *999)
      if (0.99 * y(n_jets_PS + 1 - (i - 1)).gt.ycut) then
        ! print *, "DISCARDING: Jet ", i, " not clustered"
        return
      end if
      !!! search for and remove PS jet clustered with ME Jet
      ip1 = HIST(n_jets_PS + 2 - i) / NMAX
      ip2 = mod(hist(n_jets_PS + 2 - i), NMAX)
      if ((ip2 /= n_jets_PS + 2 - i) .or. (ip1 <= 0)) then
        ! print *, "DISCARDING: Jet ", i, " not clustered ", ip1, ip2, &
        !      hist(n_jets_PS + 2 - i)
        return
      else
        ! print *, "PARTON clustered", ip1, ip2, hist(n_jets_PS + 2 - i)
        PP(:,IP1) = zero
        do j = IP1, n_jets_PS - i
          PP(:, j) = PP(:,j + 1)
        end do
      end if
    end do
  end if
end if

<MLM matching: procedures>+≡
!C-----
!C-----
!C-----
!C      KTCLUS: written by Mike Seymour, July 1992.
!C      Last modified November 2000.
!C      Please send comments or suggestions to Mike.Seymour@rl.ac.uk

```

```

!C
!C This is a general-purpose kt clustering package.
!C It can handle ee, ep and pp collisions.
!C It is loosely based on the program of Siggi Bethke.
!C
!C The time taken (on a 10MIP machine) is (0.2microsec)*N**3
!C where N is the number of particles.
!C Over 90 percent of this time is used in subroutine KTPMIN, which
!C simply finds the minimum member of a one-dimensional array.
!C It is well worth thinking about optimization: on the SPARCstation
!C a factor of two increase was obtained simply by increasing the
!C optimization level from its default value.
!C
!C The approach is to separate the different stages of analysis.
!C KTCLUS does all the clustering and records a merging history.
!C It returns a simple list of the y values at which each merging
!C occurred. Then the following routines can be called to give extra
!C information on the most recently analysed event.
!C KTCLUR is identical but includes an R parameter, see below.
!C KTYCUT gives the number of jets at each given YCUT value.
!C KTYSUB gives the number of sub-jets at each given YCUT value.
!C KTBEAM gives same info as KTCLUS but only for merges with the beam
!C KTJOIN gives same info as KTCLUS but for merges of sub-jets.
!C KTRECO reconstructs the jet momenta at a given value of YCUT.
!C It also gives information on which jets at scale YCUT belong to
!C which macro-jets at scale YMAC, for studying sub-jet properties.
!C K TINCL reconstructs the jet momenta according to the inclusive jet
!C definition of Ellis and Soper.
!C KTISUB, KTIJOI and KTIREC are like KTYSUB, KTJOIN and KTRECO,
!C except that they only apply to one inclusive jet at a time,
!C with the pt of that jet automatically used for ECUT.
!C KTWICH gives a list of which particles ended up in which jets.
!C KTWCHS gives the same thing, but only for subjets.
!C Note that the numbering of jets used by these two routines is
!C guaranteed to be the same as that used by KTRECO.
!C
!C The collision type and analysis type are indicated by the first
!C argument of KTCLUS. IMODE=<TYPE><ANGLE><MONO><RECOM> where
!C TYPE: 1=>ee, 2=>ep with p in -z direction, 3=>pe, 4=>pp
!C ANGLE: 1=>angular kt def., 2=>DeltaR, 3=>f(DeltaEta,DeltaPhi)
!C where f()=2(cosh(eta)-cos(phi)) is the QCD emission metric
!C MONO: 1=>derive relative pseudoparticle angles from jets
!C 2=>monotonic definitions of relative angles
!C RECOM: 1=>E recombination scheme, 2=>pt scheme, 3=>pt**2 scheme
!C
!C There are also abbreviated forms for the most common combinations:
!C IMODE=1 => E scheme in e+e- (1111)
!C 2 => E scheme in ep (2111)
!C 3 => E scheme in pe (3111)
!C 4 => E scheme in pp (4111)
!C 5 => covariant E scheme in pp (4211)
!C 6 => covariant pt-scheme in pp (4212)
!C 7 => covariant monotonic pt**2-scheme in pp (4223)
!C

```

!C KTRECO no longer needs to reconstruct the momenta according to the
 !C same recombination scheme in which they were clustered. Its first
 !C argument gives the scheme, taking the same values as RECOM above.
 !C
 !C Note that unlike previous versions, all variables which hold y
 !C values have been named in a consistent way:
 !C Y() is the output scale at which jets were merged,
 !C YCUT is the input scale at which jets should be counted, and
 !C jet-momenta reconstructed etc,
 !C YMAC is the input macro-jet scale, used in determining whether
 !C or not each jet is a sub-jet.
 !C The original scheme defined in our papers is equivalent to always
 !C setting YMAC=1.
 !C Whenever a YCUT or YMAC variable is used, it is rounded down
 !C infinitesimally, so that for example, setting YCUT=Y(2) refers
 !C to the scale where the event is 2-jet, even if rounding errors
 !C have shifted its value slightly.
 !C
 !C An R parameter can be used in hadron-hadron collisions by
 !C calling KTCLUR instead of KTCLUS. This is as suggested by
 !C Ellis and Soper, but implemented slightly differently,
 !C as in M.H. Seymour, LU TP 94/2 (submitted to Nucl. Phys. B.).
 !C R**2 multiplies the single Kt everywhere it is used.
 !C Calling KTCLUR with R=1 is identical to calling KTCLUS.
 !C R plays a similar role to the jet radius in a cone-type algorithm,
 !C but is scaled up by about 40% (ie R=0.7 in a cone algorithm is
 !C similar to this algorithm with R=1).
 !C Note that R.EQ.1 must be used for the e+e- and ep versions,
 !C and is strongly recommended for the hadron-hadron version.
 !C However, R values smaller than 1 have been found to be useful for
 !C certain applications, particularly the mass reconstruction of
 !C highly-boosted colour-singlets such as high-pt hadronic Ws,
 !C as in M.H. Seymour, LU TP 93/8 (to appear in Z. Phys. C.).
 !C Situations in which R<1 is useful are likely to also be those in
 !C which the inclusive reconstruction method is more useful.
 !C
 !C Also included is a set of routines for doing Lorentz boosts:
 !C KTLBST finds the boost matrix to/from the cm frame of a 4-vector
 !C KTRROT finds the rotation matrix from one vector to another
 !C KTMUL multiplies together two matrices
 !C KTMUL multiplies a vector by a matrix
 !C KTINVT inverts a transformation matrix (nb NOT a general 4 by 4)
 !C KTFRAM boosts a list of vectors between two arbitrary frames
 !C KTBREI boosts a list of vectors between the lab and Breit frames
 !C KTHADR boosts a list of vectors between the lab and hadronic cmf
 !C The last two need the momenta in the +z direction of the lepton
 !C and hadron beams, and the 4-momentum of the outgoing lepton.
 !C
 !C The main reference is:
 !C S. Catani, Yu.L. Dokshitzer, M.H. Seymour and B.R. Webber,
 !C Nucl.Phys.B406(1993)187.
 !C The ep version was proposed in:
 !C S. Catani, Yu.L. Dokshitzer and B.R. Webber,
 !C Phys.Lett.285B(1992)291.


```

!C      The inclusive reconstruction method was proposed in:
!C      S.D. Ellis and D.E. Soper,
!C      Phys.Rev.D48(1993)3160.
!C
!C-----
!C-----
!C-----

<MLM matching: procedures>+≡
      SUBROUTINE KTCLUR(IMODE,PP,NN,R,ECUT,Y,*)
      IMPLICIT NONE
!C---DO CLUSTER ANALYSIS OF PARTICLES IN PP
!C
!C  IMODE   = INPUT   : DESCRIBED ABOVE
!C  PP(I,J) = INPUT   : 4-MOMENTUM OF Jth PARTICLE: I=1,4 => PX,PY,PZ,E
!C  NN      = INPUT   : NUMBER OF PARTICLES
!C  R       = INPUT   : ELLIS AND SOPER'S R PARAMETER, SEE ABOVE.
!C  ECUT    = INPUT   : DENOMINATOR OF KT MEASURE. IF ZERO, ETOT IS USED
!C  Y(J)    = OUTPUT  : VALUE OF Y FOR WHICH EVENT CHANGES FROM BEING
!C                      J JET TO J-1 JET
!C  LAST ARGUMENT IS LABEL TO JUMP TO IF FOR ANY REASON THE EVENT
!C  COULD NOT BE PROCESSED (MOST LIKELY DUE TO TOO MANY PARTICLES)
!C
!C  NOTE THAT THE MOMENTA ARE DECLARED DOUBLE PRECISION,
!C  AND ALL OTHER FLOATING POINT VARIABLES ARE DECLARED DOUBLE PRECISION
!C
      INTEGER NMAX,IM,IMODE,TYPE,ANGL,MONO,RECO,N,I,J,NN, &
      IMIN,JMIN,KMIN,NUM,HIST,INJET,IABBR,NABBR
      PARAMETER (NMAX=512,NABBR=7)
      DOUBLE PRECISION PP(4,*)
      integer :: u
!C  CHANGE   DOUBLE PRECISION R,ECUT,Y(*),P,KT,ETOT,RSQ,KTP,KTS,KTPAIR,KTSING, &
      DOUBLE PRECISION R,ECUT,Y(*),P,KT,ETOT,RSQ,KTP,KTS, &
      KTMIN,ETSQ,KTLAST,KTMAX,KTTMP
      LOGICAL FIRST
      CHARACTER TITLE(4,4)*10
!C---KT RECORDS THE KT**2 OF EACH MERGING.
!C---KTLAST RECORDS FOR EACH MERGING, THE HIGHEST ECUT**2 FOR WHICH THE
!C  RESULT IS NOT MERGED WITH THE BEAM (COULD BE LARGER THAN THE
!C  KT**2 AT WHICH IT WAS MERGED IF THE KT VALUES ARE NOT MONOTONIC).
!C  THIS MAY SOUND POINTLESS, BUT ITS USEFUL FOR DETERMINING WHETHER
!C  SUB-JETS SURVIVED TO SCALE Y=YMAC OR NOT.
!C---HIST RECORDS MERGING HISTORY:
!C  N=>DELETED TRACK N, M*NMAX+N=>MERGED TRACKS M AND N (M<N).
      COMMON /KTCOMM/ETOT,RSQ,P(9,NMAX),KTP(NMAX,NMAX),KTS(NMAX), &
      KT(NMAX),KTLAST(NMAX),HIST(NMAX),NUM
      DIMENSION INJET(NMAX),IABBR(NABBR)
      DATA FIRST,TITLE,IABBR/.TRUE., &
      'e+e-      ','ep      ','pe      ','pp      ', &
      'angle      ','DeltaR    ','f(DeltaR) ','*****', &
      'no         ','yes      ','*****', '*****', &
      'E          ','Pt      ','Pt**2    ','*****', &
      1111,2111,3111,4111,4211,4212,4223/
!C---CHECK INPUT
      IM=IMODE

```

```

IF (IM.GE.1.AND.IM.LE.NABBR) IM=IABBR(IM)
TYPE=MOD(IM/1000,10)
ANGL=MOD(IM/100,10)
MONO=MOD(IM/10,10)
RECO=MOD(IM,10)
IF (NN.GT.NMAX) CALL KTWARN('KT-MAX',100,*999)
IF (NN.LT.1) CALL KTWARN('KT-LT1',100,*999)
IF (NN.LT.2.AND.TYPE.EQ.1) CALL KTWARN('KT-LT2',100,*999)
IF (TYPE.LT.1.OR.TYPE.GT.4.OR.ANGL.LT.1.OR.ANGL.GT.4.OR. &
    MONO.LT.1.OR.MONO.GT.2.OR.RECO.LT.1.OR.RECO.GT.3) CALL KTWARN('KTCLUS',101,*999)
u = given_output_unit ()
IF (FIRST) THEN
    WRITE (u,'(/,1X,54(''*''))/A)') &
        ' KTCLUS: written by Mike Seymour, July 1992.'
    WRITE (u,'(A)') &
        ' Last modified November 2000.'
    WRITE (u,'(A)') &
        ' Please send comments or suggestions to Mike.Seymour@rl.ac.uk'
    WRITE (u,'(/A,I2,2A)') &
        ' Collision type =',TYPE,' = ',TITLE(TYPE,1)
    WRITE (u,'(A,I2,2A)') &
        ' Angular variable =',ANGL,' = ',TITLE(ANGL,2)
    WRITE (u,'(A,I2,2A)') &
        ' Monotonic definition =',MONO,' = ',TITLE(MONO,3)
    WRITE (u,'(A,I2,2A)') &
        ' Recombination scheme =',RECO,' = ',TITLE(RECO,4)
    IF (R.NE.1) THEN
        WRITE (u,'(A,F5.2)') &
            ' Radius parameter =',R
        IF (TYPE.NE.4) WRITE (u,'(A)') &
            ' R.NE.1 is strongly discouraged for this collision type!'
    ENDIF
    WRITE (u,'(1X,54(''*''))/)')
    FIRST=.FALSE.
ENDIF
!C---COPY PP TO P
N=NN
NUM=NN
CALL KTCOPY(PP,N,P,(RECO.NE.1))
ETOT=0
DO I=1,N
    ETOT=ETOT+P(4,I)
END DO
IF (ETOT.EQ.0) CALL KTWARN('KTCLUS',102,*999)
IF (ECUT.EQ.0) THEN
    ETSQ=1/ETOT**2
ELSE
    ETSQ=1/ECUT**2
ENDIF
RSQ=R**2
!C---CALCULATE ALL PAIR KT's
DO I=1,N-1
    DO J=I+1,N
        KTP(J,I)=-1

```

```

        KTP(I,J)=KTPAIR(ANGL,P(1,I),P(1,J),KTP(J,I))
    END DO
END DO
!C---CALCULATE ALL SINGLE KT's
DO I=1,N
    KTS(I)=KTSING(ANGL,TYPE,P(1,I))
END DO
KTMX=0
!C---MAIN LOOP
300 CONTINUE
!C---FIND MINIMUM MEMBER OF KTP
CALL KTPMIN(KTP,NMAX,N,IMIN,JMIN)
!C---FIND MINIMUM MEMBER OF KTS
CALL KTSMIN(KTS,NMAX,N,KMIN)
!C---STORE Y VALUE OF TRANSITION FROM N TO N-1 JETS
KTMIN=KTP(IMIN,JMIN)
KTTMP=RSQ*KTS(KMIN)
IF ((TYPE.GE.2.AND.TYPE.LE.4).AND. &
    (KTTMP.LE.KTMIN.OR.N.EQ.1)) &
    KTMIN=KTTMP
KT(N)=KTMIN
Y(N)=KT(N)*ETSQ
!C---IF MONO.GT.1, SEQUENCE IS SUPPOSED TO BE MONOTONIC, IF NOT, WARN
IF (KTMIN.LT.KTMX.AND.MONO.GT.1) CALL KTWARN('KTCLUS',1,*999)
IF (KTMIN.GE.KTMX) KTMX=KTMIN
!C---IF LOWEST KT IS TO A BEAM, THROW IT AWAY AND MOVE LAST ENTRY UP
IF (KTMIN.EQ.KTTMP) THEN
    CALL KTMOVE(P,KTP,KTS,NMAX,N,KMIN,1)
!C---UPDATE HISTORY AND CROSS-REFERENCES
    HIST(N)=KMIN
    INJET(N)=KMIN
    DO I=N,NN
        IF (INJET(I).EQ.KMIN) THEN
            KTLAST(I)=KTMX
            INJET(I)=0
        ELSEIF (INJET(I).EQ.N) THEN
            INJET(I)=KMIN
        ENDIF
    END DO
!C---OTHERWISE MERGE JETS IMIN AND JMIN AND MOVE LAST ENTRY UP
    ELSE
        CALL KTMERG(P,KTP,KTS,NMAX,IMIN,JMIN,N,TYPE,ANGL,MONO,RECO)
        CALL KTMOVE(P,KTP,KTS,NMAX,N,JMIN,1)
!C---UPDATE HISTORY AND CROSS-REFERENCES
        HIST(N)=IMIN*NMAX+JMIN
        INJET(N)=IMIN
        DO I=N,NN
            IF (INJET(I).EQ.JMIN) THEN
                INJET(I)=IMIN
            ELSEIF (INJET(I).EQ.N) THEN
                INJET(I)=JMIN
            ENDIF
        END DO
    ENDIF
ENDIF

```

```

!C---THATS ALL THERE IS TO IT
      N=N-1
      IF (N.GT.1 .OR. N.GT.0.AND.(TYPE.GE.2.AND.TYPE.LE.4)) GOTO 300
      IF (N.EQ.1) THEN
        KT(N)=1D20
        Y(N)=KT(N)*ETSQ
      ENDIF
      RETURN
999 RETURN 1
      END SUBROUTINE KTCLUR
!C-----
<MLM matching: procedures>+≡
!C-----
      SUBROUTINE KTRECO(RECO,PP,NN,ECUT,YCUT,YMAC,PJET,JET,NJET,NSUB,*)
      IMPLICIT NONE
!C---RECONSTRUCT KINEMATICS OF JET SYSTEM, WHICH HAS ALREADY BEEN
!C ANALYSED BY KTCLUS. NOTE THAT NO CONSISTENCY CHECK IS MADE: USER
!C IS TRUSTED TO USE THE SAME PP VALUES AS FOR KTCLUS
!C
!C RECO      = INPUT : RECOMBINATION SCHEME (NEED NOT BE SAME AS KTCLUS)
!C PP(I,J)   = INPUT : 4-MOMENTUM OF Jth PARTICLE: I=1,4 => PX,PY,PZ,E
!C NN        = INPUT : NUMBER OF PARTICLES
!C ECUT      = INPUT : DENOMINATOR OF KT MEASURE. IF ZERO, ETOT IS USED
!C YCUT      = INPUT : Y VALUE AT WHICH TO RECONSTRUCT JET MOMENTA
!C YMAC      = INPUT : Y VALUE USED TO DEFINE MACRO-JETS, TO DETERMINE
!C              WHICH JETS ARE SUB-JETS
!C PJET(I,J)=OUTPUT : 4-MOMENTUM OF Jth JET AT SCALE YCUT
!C JET(J)    =OUTPUT : THE MACRO-JET WHICH CONTAINS THE Jth JET,
!C              SET TO ZERO IF JET IS NOT A SUB-JET
!C NJET      =OUTPUT : THE NUMBER OF JETS
!C NSUB      =OUTPUT : THE NUMBER OF SUB-JETS (EQUAL TO THE NUMBER OF
!C              NON-ZERO ENTRIES IN JET())
!C LAST ARGUMENT IS LABEL TO JUMP TO IF FOR ANY REASON THE EVENT
!C COULD NOT BE PROCESSED
!C
!C NOTE THAT THE MOMENTA ARE DECLARED DOUBLE PRECISION,
!C AND ALL OTHER FLOATING POINT VARIABLES ARE DECLARED DOUBLE PRECISION
!C
      INTEGER NMAX,RECO,NUM,N,NN,NJET,NSUB,JET(*),HIST,IMIN,JMIN,I,J
      PARAMETER (NMAX=512)
      DOUBLE PRECISION PP(4,*),PJET(4,*)
      DOUBLE PRECISION ECUT,P,KT,KTP,KTS,ETOT,RSQ,ETSQ,YCUT,YMAC,KTLAST, &
      ROUND
      PARAMETER (ROUND=0.99999D0)
      COMMON /KTCOMM/ETOT,RSQ,P(9,NMAX),KTP(NMAX,NMAX),KTS(NMAX), &
      KT(NMAX),KTLAST(NMAX),HIST(NMAX),NUM
!C---CHECK INPUT
      if (signal_is_pending ()) return
      IF (RECO.LT.1.OR.RECO.GT.3) THEN
        PRINT *, 'RECO=',RECO
        CALL KTWARN('KTRECO',100,*999)
      ENDIF
!C---COPY PP TO P
      N=NN

```

```

      IF (NUM.NE.NN) CALL KTWARN('KTRECO',101,*999)
      CALL KTCOPY(PP,N,P,(RECO.NE.1))
      IF (ECUT.EQ.0) THEN
        ETSQ=1/ETOT**2
      ELSE
        ETSQ=1/ECUT**2
      ENDIF
!C---KEEP MERGING UNTIL YCUT
100  IF (ETSQ*KT(N).LT.ROUND*YCUT) THEN
      IF (HIST(N).LE.NMAX) THEN
        CALL KTMOVE(P,KTP,KTS,NMAX,N,HIST(N),0)
      ELSE
        IMIN=HIST(N)/NMAX
        JMIN=HIST(N)-IMIN*NMAX
        CALL KTMERG(P,KTP,KTS,NMAX,IMIN,JMIN,N,0,0,0,RECO)
        CALL KTMOVE(P,KTP,KTS,NMAX,N,JMIN,0)
      ENDIF
      N=N-1
      IF (N.GT.0) GOTO 100
    ENDIF
!C---IF YCUT IS TOO LARGE THERE ARE NO JETS
    NJET=N
    NSUB=N
    IF (N.EQ.0) RETURN
!C---SET UP OUTPUT MOMENTA
    DO I=1,NJET
      IF (RECO.EQ.1) THEN
        DO J=1,4
          PJET(J,I)=P(J,I)
        END DO
      ELSE
        PJET(1,I)=P(6,I)*COS(P(8,I))
        PJET(2,I)=P(6,I)*SIN(P(8,I))
        PJET(3,I)=P(6,I)*SINH(P(7,I))
        PJET(4,I)=P(6,I)*COSH(P(7,I))
      ENDIF
      JET(I)=I
    END DO
!C---KEEP MERGING UNTIL YMAC TO FIND THE FATE OF EACH JET
300  IF (ETSQ*KT(N).LT.ROUND*YMAC) THEN
      IF (HIST(N).LE.NMAX) THEN
        IMIN=0
        JMIN=HIST(N)
        NSUB=NSUB-1
      ELSE
        IMIN=HIST(N)/NMAX
        JMIN=HIST(N)-IMIN*NMAX
        IF (ETSQ*KTLAST(N).LT.ROUND*YMAC) NSUB=NSUB-1
      ENDIF
      DO I=1,NJET
        IF (JET(I).EQ.JMIN) JET(I)=IMIN
        IF (JET(I).EQ.N) JET(I)=JMIN
      END DO
      N=N-1

```

```

        IF (N.GT.0) GOTO 300
    ENDIF
    RETURN
999    RETURN 1
    END SUBROUTINE KTRECO
!C-----
<MLM matching: procedures>+≡
!C-----
    FUNCTION KTPAIR(ANGL,P,Q,ANGLE)
        IMPLICIT NONE
!C---CALCULATE LOCAL KT OF PAIR, USING ANGULAR SCHEME:
!C    1=>ANGULAR, 2=>DeltaR, 3=>f(DeltaEta,DeltaPhi)
!C    WHERE f(eta,phi)=2(COSH(eta)-COS(phi)) IS THE QCD EMISSION METRIC
!C---IF ANGLE<0, IT IS SET TO THE ANGULAR PART OF THE LOCAL KT ON RETURN
!C    IF ANGLE>0, IT IS USED INSTEAD OF THE ANGULAR PART OF THE LOCAL KT
        INTEGER ANGL
!    CHANGE        DOUBLE PRECISION P(9),Q(9),KTPAIR,R,KTMDPI,ANGLE,ETA,PHI,ESQ
        DOUBLE PRECISION P(9),Q(9),KTPAIR,R,ANGLE,ETA,PHI,ESQ
!C---COMPONENTS OF MOMENTA ARE PX,PY,PZ,E,1/P,PT,ETA,PHI,PT**2
        R=ANGLE
        IF (ANGL.EQ.1) THEN
            IF (R.LE.0) R=2*(1-(P(1)*Q(1)+P(2)*Q(2)+P(3)*Q(3))*(P(5)*Q(5)))
            ESQ=MIN(P(4),Q(4))**2
        ELSEIF (ANGL.EQ.2.OR.ANGL.EQ.3) THEN
            IF (R.LE.0) THEN
                ETA=P(7)-Q(7)
                PHI=KTMDPI(P(8)-Q(8))
                IF (ANGL.EQ.2) THEN
                    R=ETA**2+PHI**2
                ELSE
                    R=2*(COSH(ETA)-COS(PHI))
                ENDIF
            ENDIF
            ESQ=MIN(P(9),Q(9))
        ELSEIF (ANGL.EQ.4) THEN
            ESQ=(1d0/(P(5)*Q(5))-P(1)*Q(1)-P(2)*Q(2)- &
                P(3)*Q(3))*2d0/(P(5)*Q(5))/(0.0001d0+1d0/P(5)+1d0/Q(5))**2
            R=1d0
        ELSE
            CALL KTWARN('KTPAIR',200,*999)
            STOP
        ENDIF
        KTPAIR=ESQ*R
        IF (ANGLE.LT.0) ANGLE=R
999    END FUNCTION KTPAIR
!C-----
    FUNCTION KTSING(ANGL,TYPE,P)
        IMPLICIT NONE
!C---CALCULATE KT OF PARTICLE, USING ANGULAR SCHEME:
!C    1=>ANGULAR, 2=>DeltaR, 3=>f(DeltaEta,DeltaPhi)
!C---TYPE=1 FOR E+E-, 2 FOR EP, 3 FOR PE, 4 FOR PP
!C    FOR EP, PROTON DIRECTION IS DEFINED AS -Z
!C    FOR PE, PROTON DIRECTION IS DEFINED AS +Z
        INTEGER ANGL,TYPE

```

```

      DOUBLE PRECISION P(9),KTSING,COSTH,R,SMALL
      DATA SMALL/1D-4/
      IF (ANGL.EQ.1.OR.ANGL.EQ.4) THEN
        COSTH=P(3)*P(5)
        IF (TYPE.EQ.2) THEN
          COSTH=-COSTH
        ELSEIF (TYPE.EQ.4) THEN
          COSTH=ABS(COSTH)
        ELSEIF (TYPE.NE.1.AND.TYPE.NE.3) THEN
          CALL KTWARN('KTSING',200,*999)
          STOP
        ENDIF
        R=2*(1-COSTH)
!C---IF CLOSE TO BEAM, USE APPROX 2*(1-COS(THETA))=SIN**2(THETA)
        IF (R.LT.SMALL) R=(P(1)**2+P(2)**2)*P(5)**2
        KTSING=P(4)**2*R
        ELSEIF (ANGL.EQ.2.OR.ANGL.EQ.3) THEN
          KTSING=P(9)
        ELSE
          CALL KTWARN('KTSING',201,*999)
          STOP
        ENDIF
999 END FUNCTION KTSING
!C-----
      SUBROUTINE KTPMIN(A,NMAX,N,IMIN,JMIN)
      IMPLICIT NONE
!C---FIND THE MINIMUM MEMBER OF A(NMAX,NMAX) WITH IMIN < JMIN <= N
      INTEGER NMAX,N,IMIN,JMIN,KMIN,I,J,K
!C---REMEMBER THAT A(X+(Y-1)*NMAX)=A(X,Y)
!C   THESE LOOPING VARIABLES ARE J=Y-2, I=X+(Y-1)*NMAX
      DOUBLE PRECISION A(*),AMIN
      K=1+NMAX
      KMIN=K
      AMIN=A(KMIN)
      DO J=0,N-2
        DO I=K,K+J
          IF (A(I).LT.AMIN) THEN
            KMIN=I
            AMIN=A(KMIN)
          ENDIF
        END DO
        K=K+NMAX
      END DO
      JMIN=KMIN/NMAX+1
      IMIN=KMIN-(JMIN-1)*NMAX
      END SUBROUTINE KTPMIN
!C-----
      SUBROUTINE KTSMIN(A,NMAX,N,IMIN)
      IMPLICIT NONE
!C---FIND THE MINIMUM MEMBER OF A
      INTEGER N,NMAX,IMIN,I
      DOUBLE PRECISION A(NMAX)
      IMIN=1
      DO I=1,N

```

```

        IF (A(I).LT.A(IMIN)) IMIN=I
    END DO
END SUBROUTINE KTSMIN
!C-----
SUBROUTINE KTCOPY(A,N,B,ONSHLL)
    IMPLICIT NONE
!C---COPY FROM A TO B. 5TH=1/(3-MTM), 6TH=PT, 7TH=ETA, 8TH=PHI, 9TH=PT**2
!C IF ONSHLL IS .TRUE. PARTICLE ENTRIES ARE PUT ON-SHELL BY SETTING E=P
    INTEGER I,N
    DOUBLE PRECISION A(4,N)
    LOGICAL ONSHLL
    DOUBLE PRECISION B(9,N),ETAMAX,SINMIN,EPS
    DATA ETAMAX,SINMIN,EPS/10,0,1D-6/
!C---SINMIN GETS CALCULATED ON FIRST CALL
    IF (SINMIN.EQ.0) SINMIN=1/COSH(ETAMAX)
    DO I=1,N
        B(1,I)=A(1,I)
        B(2,I)=A(2,I)
        B(3,I)=A(3,I)
        B(4,I)=A(4,I)
        B(5,I)=SQRT(A(1,I)**2+A(2,I)**2+A(3,I)**2)
        IF (ONSHLL) B(4,I)=B(5,I)
        IF (B(5,I).EQ.0) B(5,I)=1D-10
        B(5,I)=1/B(5,I)
        B(9,I)=A(1,I)**2+A(2,I)**2
        B(6,I)=SQRT(B(9,I))
        B(7,I)=B(6,I)*B(5,I)
        IF (B(7,I).GT.SINMIN) THEN
            B(7,I)=A(4,I)**2-A(3,I)**2
            IF (B(7,I).LE.EPS*B(4,I)**2.OR. ONSHLL) B(7,I)=B(9,I)
            B(7,I)=LOG((B(4,I)+ABS(B(3,I)))**2/B(7,I))/2
        ELSE
            B(7,I)=ETAMAX+2
        ENDIF
        B(7,I)=SIGN(B(7,I),B(3,I))
        IF (A(1,I).EQ.0 .AND. A(2,I).EQ.0) THEN
            B(8,I)=0
        ELSE
            B(8,I)=ATAN2(A(2,I),A(1,I))
        ENDIF
    END DO
END SUBROUTINE KTCOPY
!C-----
SUBROUTINE KTMERG(P,KTP,KTS,NMAX,I,J,N,TYPE,ANGL,MONO,RECO)
    IMPLICIT NONE
!C---MERGE THE Jth PARTICLE IN P INTO THE Ith PARTICLE
!C J IS ASSUMED GREATER THAN I. P CONTAINS N PARTICLES BEFORE MERGING.
!C---ALSO RECALCULATING THE CORRESPONDING KTP AND KTS VALUES IF MONO.GT.0
!C FROM THE RECOMBINED ANGULAR MEASURES IF MONO.GT.1
!C---NOTE THAT IF MONO.LE.0, TYPE AND ANGL ARE NOT USED
    INTEGER ANGL,RECO,TYPE,I,J,K,N,NMAX,MONO
    DOUBLE PRECISION P(9,NMAX),KTP(NMAX,NMAX),KTS(NMAX),PT,PTT, &
! CHANGE      KTMDPI,KTUP,PI,PJ,ANG,KTPAIR,KTSING,ETAMAX,EPS
      KTUP,PI,PJ,ANG,ETAMAX,EPS

```



```

      KTUP(I,J)=KTP(MAX(I,J),MIN(I,J))
      DATA ETAMAX,EPS/10,1D-6/
      IF (J.LE.I) CALL KTWARN('KTMERG',200,*999)
!C---COMBINE ANGULAR MEASURES IF NECESSARY
      IF (MONO.GT.1) THEN
        DO K=1,N
          IF (K.NE.I.AND.K.NE.J) THEN
            IF (RECO.EQ.1) THEN
              PI=P(4,I)
              PJ=P(4,J)
            ELSEIF (RECO.EQ.2) THEN
              PI=P(6,I)
              PJ=P(6,J)
            ELSEIF (RECO.EQ.3) THEN
              PI=P(9,I)
              PJ=P(9,J)
            ELSE
              CALL KTWARN('KTMERG',201,*999)
              STOP
            ENDIF
            IF (PI.EQ.0.AND.PJ.EQ.0) THEN
              PI=1
              PJ=1
            ENDIF
            KTP(MAX(I,K),MIN(I,K))= &
              (PI*KTUP(I,K)+PJ*KTUP(J,K))/(PI+PJ)
          ENDIF
        END DO
      ENDIF
      IF (RECO.EQ.1) THEN
!C---VECTOR ADDITION
        P(1,I)=P(1,I)+P(1,J)
        P(2,I)=P(2,I)+P(2,J)
        P(3,I)=P(3,I)+P(3,J)
!c      P(4,I)=P(4,I)+P(4,J) ! JA
        P(5,I)=SQRT(P(1,I)**2+P(2,I)**2+P(3,I)**2)
        P(4,I)=P(5,I) ! JA (Massless scheme)
        IF (P(5,I).EQ.0) THEN
          P(5,I)=1
        ELSE
          P(5,I)=1/P(5,I)
        ENDIF
      ELSEIF (RECO.EQ.2) THEN
!C---PT WEIGHTED ETA-PHI ADDITION
        PT=P(6,I)+P(6,J)
        IF (PT.EQ.0) THEN
          PTT=1
        ELSE
          PTT=1/PT
        ENDIF
        P(7,I)=(P(6,I)*P(7,I)+P(6,J)*P(7,J))*PTT
        P(8,I)=KTMDPI(P(8,I)+P(6,J)*PTT*KTMDPI(P(8,J)-P(8,I)))
        P(6,I)=PT
        P(9,I)=PT**2

```

```

ELSEIF (RECO.EQ.3) THEN
!C---PT**2 WEIGHTED ETA-PHI ADDITION
PT=P(9,I)+P(9,J)
IF (PT.EQ.0) THEN
PTT=1
ELSE
PTT=1/PT
ENDIF
P(7,I)=(P(9,I)*P(7,I)+P(9,J)*P(7,J))*PTT
P(8,I)=KTMDPI(P(8,I)+P(9,J)*PTT*KTMDPI(P(8,J)-P(8,I)))
P(6,I)=P(6,I)+P(6,J)
P(9,I)=P(6,I)**2
ELSE
CALL KTWARN('KTMERG',202,*999)
STOP
ENDIF
!C---IF MONO.GT.0 CALCULATE NEW KT MEASURES. IF MONO.GT.1 USE ANGULAR ONES.
IF (MONO.LE.0) RETURN
!C---CONVERTING BETWEEN 4-MTM AND PT,ETA,PHI IF NECESSARY
IF (ANGL.NE.1.AND.RECO.EQ.1) THEN
P(9,I)=P(1,I)**2+P(2,I)**2
P(7,I)=P(4,I)**2-P(3,I)**2
IF (P(7,I).LE.EPS*P(4,I)**2) P(7,I)=P(9,I)
IF (P(7,I).GT.0) THEN
P(7,I)=LOG((P(4,I)+ABS(P(3,I)))*2/P(7,I))/2
IF (P(7,I).GT.ETAMAX) P(7,I)=ETAMAX+2
ELSE
P(7,I)=ETAMAX+2
ENDIF
P(7,I)=SIGN(P(7,I),P(3,I))
IF (P(1,I).NE.0.AND.P(2,I).NE.0) THEN
P(8,I)=ATAN2(P(2,I),P(1,I))
ELSE
P(8,I)=0
ENDIF
ELSEIF (ANGL.EQ.1.AND.RECO.NE.1) THEN
P(1,I)=P(6,I)*COS(P(8,I))
P(2,I)=P(6,I)*SIN(P(8,I))
P(3,I)=P(6,I)*SINH(P(7,I))
P(4,I)=P(6,I)*COSH(P(7,I))
IF (P(4,I).NE.0) THEN
P(5,I)=1/P(4,I)
ELSE
P(5,I)=1
ENDIF
ENDIF
ANG=0
DO K=1,N
IF (K.NE.I.AND.K.NE.J) THEN
IF (MONO.GT.1) ANG=KTUP(I,K)
KTP(MIN(I,K),MAX(I,K))= &
KTPAIR(ANGL,P(1,I),P(1,K),ANG)
ENDIF
END DO

```

```

      KTS(I)=KTSING(ANGL,TYPE,P(1,I))
999 END SUBROUTINE KTMERG
!C-----
      SUBROUTINE KTMOVE(P,KTP,KTS,NMAX,N,J,IOPT)
      IMPLICIT NONE
!C---MOVE THE Nth PARTICLE IN P TO THE Jth POSITION
!C---ALSO MOVING KTP AND KTS IF IOPT.GT.0
      INTEGER I,J,N,NMAX,IOPT
      DOUBLE PRECISION P(9,NMAX),KTP(NMAX,NMAX),KTS(NMAX)
      DO I=1,9
        P(I,J)=P(I,N)
      END DO
      IF (IOPT.LE.0) RETURN
      DO I=1,J-1
        KTP(I,J)=KTP(I,N)
        KTP(J,I)=KTP(N,I)
      END DO
      DO I=J+1,N-1
        KTP(J,I)=KTP(I,N)
        KTP(I,J)=KTP(N,I)
      END DO
      KTS(J)=KTS(N)
      END SUBROUTINE KTMOVE
!C-----
(MLM matching: procedures)+≡
      FUNCTION KTMDPI(PHI)
      IMPLICIT NONE
!C---RETURNS PHI, MOVED ONTO THE RANGE [-PI,PI)
      DOUBLE PRECISION KTMDPI,PHI,PI,TWOPI,THRPI,EPS
      PARAMETER (PI=3.14159265358979324D0,TWOPI=6.28318530717958648D0, &
        THRPI=9.42477796076937972D0)
      PARAMETER (EPS=1D-15)
      KTMDPI=PHI
      IF (KTMDPI.LE.PI) THEN
        IF (KTMDPI.GT.-PI) THEN
          GOTO 100
        ELSEIF (KTMDPI.GT.-THRPI) THEN
          KTMDPI=KTMDPI+TWOPI
        ELSE
          KTMDPI=-MOD(PI-KTMDPI,TWOPI)+PI
        ENDIF
      ELSEIF (KTMDPI.LE.THRPI) THEN
        KTMDPI=KTMDPI-TWOPI
      ELSE
        KTMDPI=MOD(PI+KTMDPI,TWOPI)-PI
      ENDIF
100 IF (ABS(KTMDPI).LT.EPS) KTMDPI=0
      END FUNCTION KTMDPI
!C-----
      SUBROUTINE KTWARN(SUBRTN,ICODE,*)
!C      DEALS WITH ERRORS DURING EXECUTION
!C      SUBRTN = NAME OF CALLING SUBROUTINE
!C      ICODE = ERROR CODE:      - 99 PRINT WARNING & CONTINUE
!C                                100-199 PRINT WARNING & JUMP

```

```

!C                                     200-   PRINT WARNING & STOP DEAD
!C-----
      INTEGER ICODE
      CHARACTER(len=6) SUBRTN
      WRITE (6,10) SUBRTN,ICODE
10   FORMAT(/' KTWARN CALLED FROM SUBPROGRAM ',A6,' : CODE =',I4/)
      IF (ICODE.LT.100) RETURN
      IF (ICODE.LT.200) RETURN 1
      STOP
      END SUBROUTINE KTWARN
!C-----
!C-----
!C-----

```

CKKW settings, data and (pseudo) weights

This module contains the definitions for the basic settings for CKKW matching.

The type `ckkw_pseudo_shower_weights_t` gives the (relative) weights for different clusterings of the final particles, as given in Eq. (2.7) of hep-ph/0503281v1. Each particle has a binary labelling (power of 2) (first particle = 1, second particle = 2, third particle = 4, ...). Each recombination therefore corresponds to an integer, that is not a power of 2. For multiple subsequent recombinations, no different weights for different sequences of clustering are stored. It is assumed that the weight of a multiply recombined state is a combination of the states with one fewer recombination and that these states' contributions are proportional to their weights. For a $2-n$ event, the weights array thus has the size $2^{(2+n)-1}$. The `weights_by_type` array gives the weights depending on the type of the particle, the first index is the same as for weights, the second index gives the type of the new mother particle:

- 0: uncolored (γ , Z , W , Higgs)
- 1: colored (quark)
- 2: gluon
- 3: squark
- 4: gluino

`alphaS` gives the value for α_s used in the generation of the matrix element. This is needed for the reweighting using the values for a running α_s at the scales of the clusterings.

```

<ckkw_base.f90>≡
  <File header>

  module ckkw_base

    <Use kinds>
    use io_units
    use constants
    use format_utils, only: write_separator

```

```

    use shower_base
    use variables

```

<Standard module head>

<CKKW base: public>

<CKKW base: types>

```
contains
```

<CKKW base: procedures>

```
end module ckkw_base
```

The fundamental CKKW matching parameter are defined here:

<CKKW base: public>≡

```
    public :: ckkw_matching_settings_t
```

<CKKW base: types>≡

```

    type, extends (matching_settings_t) :: ckkw_matching_settings_t
        real(default) :: alphaS = 0.118_default
        real(default) :: Qmin = one
        integer :: n_max_jets = 0
    contains
        <CKKW base: CKKW matching: TBP>
    end type ckkw_matching_settings_t

```

This is empty for the moment.

<CKKW base: CKKW matching: TBP>≡

```
    procedure :: init => ckkw_matching_settings_init
```

<CKKW base: procedures>≡

```

    subroutine ckkw_matching_settings_init (settings, var_list)
        class(ckkw_matching_settings_t), intent(out) :: settings
        type(var_list_t), intent(in) :: var_list
    end subroutine ckkw_matching_settings_init

```

<CKKW base: CKKW matching: TBP>+≡

```
    procedure :: write => ckkw_matching_settings_write
```

<CKKW base: procedures>+≡

```

    subroutine ckkw_matching_settings_write (settings, unit)
        class(ckkw_matching_settings_t), intent(in) :: settings
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,A)") "CKKW matching settings:"
        call write_separator (u)
        write (u, "(3x,A,1x,ES19.12)") &
            "alphaS      = ", settings%alphaS
        write (u, "(3x,A,1x,ES19.12)") &
            "Qmin        = ", settings%Qmin
        write (u, "(3x,A,1x,I0)") &
            "n_max_jets   = ", settings%n_max_jets
    end subroutine ckkw_matching_settings_write

```

```

end subroutine ckkw_matching_settings_write

<CKKW base: public>+≡
public :: ckkw_pseudo_shower_weights_t

<CKKW base: types>+≡
type :: ckkw_pseudo_shower_weights_t
  real(default) :: alphaS
  real(default), dimension(:), allocatable :: weights
  real(default), dimension(:,:), allocatable :: weights_by_type
end type ckkw_pseudo_shower_weights_t

<CKKW base: public>+≡
public :: ckkw_pseudo_shower_weights_init

<CKKW base: procedures>+≡
subroutine ckkw_pseudo_shower_weights_init (weights)
  type(ckkw_pseudo_shower_weights_t), intent(out) :: weights
  weights%alphaS = zero
  if (allocated (weights%weights)) deallocate(weights%weights)
  if (allocated (weights%weights_by_type)) &
    deallocate(weights%weights_by_type)
end subroutine ckkw_pseudo_shower_weights_init

<CKKW base: public>+≡
public :: ckkw_pseudo_shower_weights_write

<CKKW base: procedures>+≡
subroutine ckkw_pseudo_shower_weights_write (weights, unit)
  type(ckkw_pseudo_shower_weights_t), intent(in) :: weights
  integer, intent(in), optional :: unit
  integer :: s, i, u
  u = given_output_unit (unit); if (u < 0) return
  s = size (weights%weights)
  write (u, "(1x,A)") "CKKW (pseudo) shower weights: "
  do i = 1, s
    write (u, "(3x,I0,2(ES19.12))") i, weights%weights(i), &
      weights%weights_by_type(i,:)
  end do
  write (u, "(3x,A,1x,I0)") "alphaS =", weights%alphaS
end subroutine ckkw_pseudo_shower_weights_write

<CKKW base: public>+≡
public :: ckkw_matching_data_t

<CKKW base: types>+≡
type, extends (matching_data_t) :: ckkw_matching_data_t
  type(ckkw_pseudo_shower_weights_t) :: ckkw_weights
end type ckkw_matching_data_t

```

20.5.2 CKKW matching

```
<ckkw_matching.f90>≡  
<File header>  
  
module ckkw_matching  
  
  <Use kinds with double>  
    use io_units  
    use constants  
    use format_utils, only: write_separator  
    use diagnostics  
    use physics_defs  
    use lorentz  
    use rng_base  
    use shower_base  
    use shower_partons  
    use ckkw_base  
    use variables  
  
  <Standard module head>  
  
  <CKKW matching: public>  
  
  contains  
  
  <CKKW matching: procedures>  
  
end module ckkw_matching  
<CKKW matching: public>≡  
  public :: ckkw_matching_apply  
<CKKW matching: procedures>≡  
  subroutine ckkw_matching_apply (partons, settings, weights, rng, veto)  
    type(parton_pointer_t), dimension(:), intent(inout), allocatable :: &  
      partons  
    type(ckkw_matching_settings_t), intent(in) :: settings  
    type(ckkw_pseudo_shower_weights_t), intent(in) :: weights  
    class(rng_t), intent(inout), allocatable :: rng  
    logical, intent(out) :: veto  
  
    real(default), dimension(:), allocatable :: scales  
    real(double) :: weight, sf  
    real(default) :: rand  
    integer :: i, n_partons  
  
    if (signal_is_pending ()) return  
    weight = one  
  
    n_partons = size (partons)  
  
    do i = 1, n_partons  
      call partons(i)%p%write ()  
    end do
```

```

!!! the pseudo parton shower is already simulated by shower_add_interaction
!!! get the respective clustering scales
allocate (scales (1:n_partons))
do i = 1, n_partons
  if (.not. associated (partons(i)%p)) cycle
  if (partons(i)%p%type == INTERNAL) then
    scales(i) = two * min (partons(i)%p%child1%momentum%p(0), &
                          partons(i)%p%child2%momentum%p(0))*2 * &
      (1.0 - (space_part (partons(i)%p%child1%momentum) * &
        space_part (partons(i)%p%child2%momentum)) / &
      (space_part (partons(i)%p%child1%momentum)**1 * &
        space_part (partons(i)%p%child2%momentum)**1))
    scales(i) = sqrt (scales(i))
    partons(i)%p%ckkwscale = scales(i)
    print *, scales(i)
  end if
end do

print *, " scales finished"
!!! if (highest multiplicity) -> reweight with PDF(mu_F) / PDF(mu_cut)
do i = 1, n_partons
  call partons(i)%p%write ()
end do

!!! Reweight and possibly veto the whole event

!!! calculate the relative alpha_S weight

!! calculate the Sudakov weights for internal lines
!! calculate the Sudakov weights for external lines
do i = 1, n_partons
  if (signal_is_pending ()) return
  if (.not. associated (partons(i)%p)) cycle
  if (partons(i)%p%type == INTERNAL) then
    !!! get type
    !!! check that all particles involved are colored
    if ((partons(i)%p%is_colored () .or. &
      partons(i)%p%ckkwtype > 0) .and. &
      (partons(i)%p%child1%is_colored () .or. &
      partons(i)%p%child1%ckkwtype > 0) .and. &
      (partons(i)%p%child1%is_colored () .or. &
      partons(i)%p%child1%ckkwtype > 0)) then
      print *, "reweight with alphaS(" , partons(i)%p%ckkwscale, &
        ") for particle ", partons(i)%p%nr
      if (partons(i)%p%belongstoFSR) then
        print *, "FSR"
        weight = weight * D_alpha_s_fsr (partons(i)%p%ckkwscale**2, &
          partons(i)%p%settings) / settings%alphas
      else
        print *, "ISR"
        weight = weight * &
          D_alpha_s_isr (partons(i)%p%ckkwscale**2, &
          partons(i)%p%settings) / settings%alphas
      end if
    end if
  end if
end do

```



```

else
  print *, "no reweight with alphaS for ", partons(i)%p%nr
end if
if (partons(i)%p%child1%type == INTERNAL) then
  print *, "internal line from ", &
    partons(i)%p%child1%ckkwscale, &
    " to ", partons(i)%p%ckkwscale, &
    " for type ", partons(i)%p%child1%ckkwtype
  if (partons(i)%p%child1%ckkwtype == 0) then
    sf = 1.0
  else if (partons(i)%p%child1%ckkwtype == 1) then
    sf = SudakovQ (partons(i)%p%child1%ckkwscale, &
      partons(i)%p%ckkwscale, &
      partons(i)%p%settings, .true., rng)
    print *, "SFQ = ", sf
  else if (partons(i)%p%child1%ckkwtype == 2) then
    sf = SudakovG (partons(i)%p%child1%ckkwscale, &
      partons(i)%p%ckkwscale, &
      partons(i)%p%settings, .true., rng)
    print *, "SFG = ", sf
  else
    print *, "SUSY not yet implemented"
  end if
  weight = weight * min (one, sf)
else
  print *, "external line from ", settings%Qmin, &
    partons(i)%p%ckkwscale
  if (partons(i)%p%child1%is_quark ()) then
    sf = SudakovQ (settings%Qmin, &
      partons(i)%p%ckkwscale, &
      partons(i)%p%settings, .true., rng)
    print *, "SFQ = ", sf
  else if (partons(i)%p%child1%is_gluon ()) then
    sf = SudakovG (settings%Qmin, &
      partons(i)%p%ckkwscale, &
      partons(i)%p%settings, .true., rng)
    print *, "SFG = ", sf
  else
    print *, "not yet implemented (", &
      partons(i)%p%child2%type, ")"
    sf = one
  end if
  weight = weight * min (one, sf)
end if
if (partons(i)%p%child2%type == INTERNAL) then
  print *, "internal line from ", partons(i)%p%child2%ckkwscale, &
    " to ", partons(i)%p%ckkwscale, &
    " for type ", partons(i)%p%child2%ckkwtype
  if (partons(i)%p%child2%ckkwtype == 0) then
    sf = 1.0
  else if (partons(i)%p%child2%ckkwtype == 1) then
    sf = SudakovQ (partons(i)%p%child2%ckkwscale, &
      partons(i)%p%ckkwscale, &
      partons(i)%p%settings, .true., rng)

```

```

        print *, "SFQ = ", sf
    else if (partons(i)%p%child2%ckkwtype == 2) then
        sf = SudakovG (partons(i)%p%child2%ckkwscale, &
            partons(i)%p%ckkwscale, &
            partons(i)%p%settings, .true., rng)
        print *, "SFG = ", sf
    else
        print *, "SUSY not yet implemented"
    end if
    weight = weight * min (one, sf)
else
    print *, "external line from ", settings%Qmin, &
        partons(i)%p%ckkwscale
    if (partons(i)%p%child2%is_quark ()) then
        sf = SudakovQ (settings%Qmin, &
            partons(i)%p%ckkwscale, &
            partons(i)%p%settings, .true., rng)
        print *, "SFQ = ", sf
    else if (partons(i)%p%child2%is_gluon ()) then
        sf = SudakovG (settings%Qmin, &
            partons(i)%p%ckkwscale, &
            partons(i)%p%settings, .true., rng)
        print *, "SFG = ", sf
    else
        print *, "not yet implemented (", &
            partons(i)%p%child2%type, ")"
        sf = one
    end if
    weight = weight * min (one, sf)
end if
end do

call rng%generate (rand)

print *, "final weight: ", weight

!!!!!!! WRONG
veto = .false.
veto = (rand > weight)
if (veto) then
    return
end if

!!! finally perform the parton shower
!!! veto emissions that are too hard

deallocate (scales)
end subroutine ckkw_matching_apply

```

(CKKW matching: procedures)+≡

```

function GammaQ (smallq, largeq, settings, fsr) result (gamma)
    real(default), intent(in) :: smallq, largeq
    type(shower_settings_t), intent(in) :: settings

```

```

logical, intent(in) :: fsr
real(default) :: gamma
gamma = (8._default / three) / (pi * smallq)
gamma = gamma * (log(largeq / smallq) - 0.75)
if (fsr) then
    gamma = gamma * D_alpha_s_fsr (smallq**2, settings)
else
    gamma = gamma * D_alpha_s_isr (smallq**2, settings)
end if
end function GammaQ

```

<CKKW matching: procedures>+≡

```

function GammaG (smallq, largeq, settings, fsr) result (gamma)
    real(default), intent(in) :: smallq, largeq
    type(shower_settings_t), intent(in) :: settings
    logical, intent(in) :: fsr
    real(default) :: gamma
    gamma = 6._default / (pi * smallq)
    gamma = gamma * ( log(largeq / smallq) - 11.0 / 12.0)
    if (fsr) then
        gamma = gamma * D_alpha_s_fsr (smallq**2, settings)
    else
        gamma = gamma * D_alpha_s_isr (smallq**2, settings)
    end if
end function GammaG

```

<CKKW matching: procedures>+≡

```

function GammaF (smallq, settings, fsr) result (gamma)
    real(default), intent(in) :: smallq
    type(shower_settings_t), intent(in) :: settings
    logical, intent(in) :: fsr
    real(default) :: gamma
    gamma = number_of_flavors (smallq, settings%max_n_flavors, &
        settings%d_min_t) / (three * pi * smallq)
    if (fsr) then
        gamma = gamma * D_alpha_s_fsr (smallq**2, settings)
    else
        gamma = gamma * D_alpha_s_isr (smallq**2, settings)
    end if
end function GammaF

```

<CKKW matching: procedures>+≡

```

function SudakovQ (Q1, Q, settings, fsr, rng) result (sf)
    real(default), intent(in) :: Q1, Q
    type(shower_settings_t), intent(in) :: settings
    class(rng_t), intent(inout), allocatable :: rng
    logical, intent(in) :: fsr
    real(default) :: sf
    real(default) :: integral
    integer, parameter :: NTRIES = 100
    integer :: i
    real(default) :: rand
    integral = zero

```

```

do i = 1, NTRIES
  call rng%generate (rand)
  integral = integral + GammaQ (Q1 + rand * (Q - Q1), Q, settings, fsr)
end do
integral = integral / NTRIES
sf = exp (-integral)
end function SudakovQ

```

(CKKW matching: procedures)+≡

```

function SudakovG (Q1, Q, settings, fsr, rng) result (sf)
  real(default), intent(in) :: Q1, Q
  type(shower_settings_t), intent(in) :: settings
  logical, intent(in) :: fsr
  real(default) :: sf
  real(default) :: integral
  class(rng_t), intent(inout), allocatable :: rng
  integer, parameter :: NTRIES = 100
  integer :: i
  real(default) :: rand
  integral = zero
  do i = 1, NTRIES
    call rng%generate (rand)
    integral = integral + &
      GammaG (Q1 + rand * (Q - Q1), Q, settings, fsr) + &
      GammaF (Q1 + rand * (Q - Q1), settings, fsr)
  end do
  integral = integral / NTRIES
  sf = exp (-integral)
end function SudakovG

```

Chapter 21

Multiple Interactions (MPI) Code

This is the code for the `WHIZARD` module for multiple interactions (MPI) in hadron collisions. It also provides the interleaved shower with together with the shower module.

21.1 Basic types

This file contains the module `multi_basic` which is included by all other modules of the MPI code. It's main purpose is serialization and deserialization, but it also contains some bitmodel parameters and some minor definitions common to all modules and types.

Serialization is implemented in three layers:

1. **I/O layer:** streamfile access and exact, retrievable and compiler independent representation of all intrinsic types
2. **Marking layer:** storing/restoring pointer association and better human readability
3. **Derived type layer:** abstract type as parent for all serializable derived types

The I/O Layer The I/O layer is implemented by `page_ring_t` and its type bound procedures. We chose not to use the standard formatted sequential I/O for several reasons:

- Sequential I/O is line orientated, but serialization is not.
- Formatted I/O of floating point numbers is inexact. There were problems in reading numbers like `1+epsilon(1)` or `huge(1)` including arithmetic exceptions and wrong results.
- Formatted reading is slow. This does matter, when you read files of $\mathcal{O}(100)$ MB.

`page_ring_t` is a ring buffer of default kind characters holding a region of the addressed file. All read and write procedures use the ring buffer, not the file. `page_ring` automatically reads more characters from the file when needed and writes and discards parts of the ring buffer when not any longer needed.

Marking layer Marking is done by `marking_t` and its type bound procedures. Files written by `marking_t` are regular XML files, so you can use your favorite XML editor to examine or edit serialized contents. The main purpose of this layer is to recover the type of polymorphic entities and to restore association of pointers, but it also assigns names to all contents, so it is much easier to read generated files.

Type recovery is done by a reference list. You must push a representative object to this reference list for each type that might get resolved before starting deserialization. `marker_t` will care for comparing these representatives to the contents of the files.

Association restoration is done by a heap list. It is technically equal to the reference list, but holds all targets that have been processed so far. Generation of this list is handled by `marking_t`, so you don't have to care for this aspect at all. Up to the present it is not possible to restore association, when a non-pointer target is serialized after its associated pointer is serialized. There is no trivial solution and this case does not appear here, so we will not take care of this.

Derived type layer Each instance that shall become serialized must extend `ser_class_t`. Essential for type recovery is the virtual type bound procedure `get_type`. Each non-virtual type shall override `get_type` and return the actual name of its type in lower-case letters. Each type which adds new, non-redundant components shall override `write_to_marker` and `read_from_marker`. These type-bound procedures define, what contents get serialized. While the marker cares about tagging the type and association of the instance, every instance still has to define what to serialize. The rule is to mark the begin of its contents, then its parents procedure, then mark all non-redundant components, then mark the end of its contents. Finally, each serializable type shall override `print_to_unit`. This procedure is called for an arbitrary human-readable output. It is quite similar to `write_to_ring`, but without strict format and ignoring machine-readability.

`ser_class_t` has strictly speaking two layers. `write_to_marker` and `read_from_marker` are only for internal usage. Serialization and deserialization are triggered by the TBPs `serialize` and `deserialize`. These procedures take care of initialization and finalization of the marker. A serializable type should override these procedures to push a representative of itself and any other references to the reference list of its marker before (de)serialization and to pop them from the list afterwards.

```
<multi_base.f90>≡
  <File header>
```

```
module multi_base
  use, intrinsic :: iso_fortran_env
  <Use kinds with double>
  use kinds, only: i64
  <Use strings>
```

```

    use constants
    use io_units
    use diagnostics

    <Standard module head>

    <Muli base: variables>

    <Muli base: public>

    <Muli base: types>

    <Muli base: interfaces>

contains

    <Muli base: procedures>

end module muli_base

```

These are the bitmodel parameters.

```

<Muli base: variables>≡
    integer, public, parameter :: dik = i64
    integer(dik), public, parameter :: i_one = int(1, kind=dik)
    integer(dik), public, parameter :: i_zero = int(0, kind=dik)

```

These are the serialization parameters.

```

<Muli base: variables>+≡
    integer(dik), public, parameter :: serialize_page_size = 1024
    integer(dik), public, parameter :: serialize_ok = 0000
    integer(dik), public, parameter :: serialize_syntax_error = 1001
    integer(dik), public, parameter :: serialize_wrong_tag = 1002
    integer(dik), public, parameter :: serialize_wrong_id = 1003
    integer(dik), public, parameter :: serialize_wrong_type = 1004
    integer(dik), public, parameter :: serialize_wrong_name = 1005
    integer(dik), public, parameter :: serialize_no_target = 1006
    integer(dik), public, parameter :: serialize_no_pointer = 1007
    integer(dik), public, parameter :: serialize_wrong_action = 1008
    integer(dik), public, parameter :: serialize_unexpected_content = 1009
    integer(dik), public, parameter :: serialize_null = 1010
    integer(dik), public, parameter :: serialize_nothing = 1011
    logical, public, parameter :: serialize_default_indent = .true.
    logical, public, parameter :: serialize_default_line_break = .true.
    logical, public, parameter :: serialize_default_asynchronous = .false.

```

And some private variables:

```

<Muli base: variables>+≡
    integer(dik) :: last_id = 0
    character(len=*) , parameter :: serialize_integer_characters = &
        "-0123456789"

<Muli base: interfaces>≡
    abstract interface
        subroutine ser_write_if (this, marker, status)

```

```

import ser_class_t
import marker_t
import dik
class(ser_class_t), intent(in) :: this
class(marker_t), intent(inout) :: marker
integer(dik), intent(out) :: status
end subroutine ser_write_if
end interface

abstract interface
  subroutine ser_read_if (this, marker, status)
    import ser_class_t
    import marker_t
    import dik
    class(ser_class_t), intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
  end subroutine ser_read_if
end interface

abstract interface
  subroutine ser_unit (this, unit, parents, components, peers)
    import ser_class_t
    import dik
    class(ser_class_t), intent(in) :: this
    integer,intent(in) :: unit
    integer(dik), intent(in) :: parents,components,peers
  end subroutine ser_unit
end interface

abstract interface
  pure subroutine ser_type (type)
    character(:), allocatable, intent(out) :: type
  end subroutine ser_type
end interface

```

$\langle \text{Muli base: interfaces} \rangle + \equiv$

```

abstract interface
  elemental function measure_int (this)
    import
    class(measure_class_t), intent(in) :: this
    real(default) :: measure_int
  end function measure_int
end interface

```

$\langle \text{Muli base: public} \rangle \equiv$

```

public :: operator(<)

```

$\langle \text{Muli base: interfaces} \rangle + \equiv$

```

interface operator(<)
  module procedure measurable_less_measurable
  module procedure measurable_less_default
end interface operator(<)

```



```

<Muli base: public>+≡
    public :: operator(<=)

<Muli base: interfaces>+≡
    interface operator(<=)
        module procedure measurable_less_or_equal_measurable
        module procedure measurable_less_or_equal_default
    end interface operator(<=)

<Muli base: public>+≡
    public :: operator(==)

<Muli base: interfaces>+≡
    interface operator(==)
        module procedure measurable_equal_measurable
        module procedure measurable_equal_default
    end interface operator(==)

<Muli base: public>+≡
    public :: operator(>=)

<Muli base: interfaces>+≡
    interface operator(>=)
        module procedure measurable_equal_or_greater_measurable
        module procedure measurable_equal_or_greater_default
    end interface operator(>=)

<Muli base: public>+≡
    public :: operator(>)

<Muli base: interfaces>+≡
    interface operator(>)
        module procedure measurable_greater_measurable
        module procedure measurable_greater_default
    end interface operator(>)

<Muli base: interfaces>+≡
    interface page_ring_position_is_before
        module procedure page_ring_position_is_before_int_pos
        module procedure page_ring_position_is_before_pos_pos
        module procedure page_ring_position_is_before_pos_int
    end interface

<Muli base: public>+≡
    public :: ser_class_t

<Muli base: types>≡
    type, abstract :: ser_class_t
    contains
    <Muli base: serial class: TBP>
    end type ser_class_t

<Muli base: serial class: TBP>≡
    procedure(ser_write_if), deferred :: write_to_marker

```

This is a dummy procedure. Usually, you do not need to deserialize targets, so by implementing this dummy we don't force all descendants to override this procedure. Then again this is the only way to read targets from markers.

<Muli base: serial class: TBP>+≡

```
procedure(ser_read_if), deferred :: read_from_marker
```

<Muli base: procedures>≡

```
subroutine serializable_read_target_from_marker (this, marker, status)
  class(ser_class_t), target, intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  write (output_unit, "(A)") "serializable_read_target_from_marker:"
  write (output_unit, "(A)") "This is a dummy procedure. Usually, this " &
    // "message indicates a missing overridden " &
    // "read_target_from_marker TPB for "
  call this%write_type (output_unit)
  write (output_unit, "(A)") ""
  call this%read_from_marker (marker, status)
end subroutine serializable_read_target_from_marker
```

<Muli base: serial class: TBP>+≡

```
procedure(ser_unit), deferred :: print_to_unit
```

<Muli base: procedures>+≡

```
subroutine serializable_serialize_to_unit (this, unit, name)
  class(ser_class_t), intent(in) :: this
  integer, intent(in) :: unit
  character (len=*), intent(in) :: name
  logical :: opened
  character(32) :: file
  !!!   gfortran bug
  !!!   character::stream
  character::write
  type(marker_t)::marker
  !   inquire(unit=unit,opened=opened,stream=stream,write=write)
  inquire (unit=unit,opened=opened,write=write)
  if (opened) then
    !!! if(stream=="Y")then
    if(write=="Y")then
      print *, "dummy: serializable_serialize_to_unit"
      stop
    else
      print *, "serializable_serialize_to_unit: cannot write to read-only unit."
    end if
    !!!   else
    !!!   print *, "serializable_serialize_to_unit: access kind of unit is not 'stream'"
    !!!   end if
  else
    call msg_error ("serializable_serialize_to_unit: file is not opened.")
  end if
end subroutine serializable_serialize_to_unit
```

<Muli base: serial class: TBP>+≡

```
procedure(ser_type), nopass, deferred :: get_type
```

```

<Muli base: serial class: TBP>+=
  procedure, nopass :: verify_type => serializable_verify_type

<Muli base: procedures>+=
  elemental function serializable_verify_type (type) result (match)
    character(*), intent(in) :: type
    logical :: match
    match = type == "ser_class_t"
  end function serializable_verify_type

<Muli base: serial class: TBP>+=
  procedure :: read_target_from_marker => &
    serializable_read_target_from_marker

<Muli base: serial class: TBP>+=
  procedure :: write_type => serializable_write_type

<Muli base: procedures>+=
  subroutine serializable_write_type (this, unit)
    class(ser_class_t), intent(in) :: this
    integer, intent(in) :: unit
    character(:), allocatable :: this_type
    call this%get_type (this_type)
    write (unit, "(A)", advance="no") this_type
  end subroutine serializable_write_type

<Muli base: serial class: TBP>+=
  procedure :: print => serializable_print

<Muli base: procedures>+=
  recursive subroutine serializable_print &
    (this, parents, components, peers, unit)
    class(ser_class_t), intent(in) :: this
    integer(dik), intent(in) :: parents, components, peers
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(A)")
    write (u, "(A)", advance="no") "Instance of type: "
    call this%write_type (u)
    write (u, "(A)")
    call this%print_to_unit (u, parents, components, peers)
  end subroutine serializable_print

<Muli base: serial class: TBP>+=
  procedure :: print_error => serializable_print_error

<Muli base: procedures>+=
  recursive subroutine serializable_print_error (this)
    class(ser_class_t), intent(in) :: this
    call this%print_to_unit (error_unit, i_zero, i_zero, i_zero)
  end subroutine serializable_print_error

<Muli base: serial class: TBP>+=
  procedure :: print_all => serializable_print_all

```

```

<Muli base: procedures>+≡
recursive subroutine serializable_print_all (this, unit)
  class(ser_class_t), intent(in) :: this
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, "(A)")
  write (u, "(A)", advance="no") "Instance of type: "
  call this%write_type (u)
  write (u, "(A)")
  call this%print_to_unit (u, huge(i_one), huge(i_one), huge(i_one))
end subroutine serializable_print_all

<Muli base: serial class: TBP>+≡
procedure :: print_little => serializable_print_little

<Muli base: procedures>+≡
recursive subroutine serializable_print_little (this, unit)
  class(ser_class_t), intent(in) :: this
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (u)
  write(u, "(A)")
  write(u, "(A)", advance="no") "Instance of type: "
  call this%write_type (u)
  write(u, "(A)")
  call this%print_to_unit (u, i_zero, i_zero, i_zero)
end subroutine serializable_print_little

<Muli base: serial class: TBP>+≡
procedure :: print_parents => serializable_print_parents

<Muli base: procedures>+≡
recursive subroutine serializable_print_parents (this)
  class(ser_class_t), intent(in) :: this
  write(output_unit, "(A)")
  write(output_unit, "(A)", advance="no") "Instance of type: "
  call this%write_type (output_unit)
  write (output_unit, "(A)")
  call this%print_to_unit (output_unit, huge(i_one), i_zero, i_zero)
end subroutine serializable_print_parents

<Muli base: serial class: TBP>+≡
procedure :: print_components => serializable_print_components

<Muli base: procedures>+≡
recursive subroutine serializable_print_components(this)
  class(ser_class_t), intent(in) :: this
  write (output_unit, "(A)")
  write (output_unit, "(A)", advance="no") "Instance of type: "
  call this%write_type (output_unit)
  write(output_unit, "(A)")
  call this%print_to_unit (output_unit, i_zero, huge(i_one), i_zero)
end subroutine serializable_print_components

```

```

<Muli base: serial class: TBP>+=
    procedure :: print_peers => serializable_print_peers

<Muli base: procedures>+=
    recursive subroutine serializable_print_peers (this)
        class(ser_class_t), intent(in) :: this
        write (output_unit, "(A)")
        write (output_unit, "(A)", advance="no") "Instance of type: "
        call this%write_type (output_unit)
        write (output_unit, "(A)")
        call this%print_to_unit (output_unit, i_zero, i_zero, huge(i_one))
    end subroutine serializable_print_peers

<Muli base: serial class: TBP>+=
    procedure :: serialize_to_file => serializable_serialize_to_file

<Muli base: procedures>+=
    subroutine serializable_serialize_to_file (this, name, file)
        class(ser_class_t), intent(in) :: this
        character(len=*), intent(in) :: file, name
        type(marker_t) :: marker
        call marker%open_for_write_access (file)
        write (output_unit, "(A,A)" &
            "Serializable_serialize_to_file: writing xml preamble to ", file)
        call marker%activate_next_page ()
        call marker%push ('<?xml version="1.0"?>')
        call marker%mark_begin (tag="file", name = file)
        flush(marker%unit)
        call this%serialize_to_marker (marker, name)
        call marker%mark_end ("file")
        call marker%close ()
        call marker%finalize ()
    end subroutine serializable_serialize_to_file

<Muli base: serial class: TBP>+=
    procedure :: serialize_to_unit => serializable_serialize_to_unit

<Muli base: serial class: TBP>+=
    procedure :: serialize_to_marker => serializable_serialize_to_marker

<Muli base: procedures>+=
    recursive subroutine serializable_serialize_to_marker (this, marker, name)
        class(ser_class_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        character(len=*), intent(in) :: name
        if (marker%action == 1) then
            call marker%mark_instance (this, name)
        else
            call msg_error ("serializable_serialize_to_marker: Marker is " &
                // "not ready for write access.")
        end if
    end subroutine serializable_serialize_to_marker

<Muli base: serial class: TBP>+=
    procedure :: deserialize_from_file => serializable_deserialize_from_file

```

<Muli base: procedures>+≡

```

subroutine serializable_deserialize_from_file (this, name, file)
  class(ser_class_t), intent(out) :: this
  character(*), intent(in) :: name, file
  type(marker_t) :: marker
  integer(dik), dimension(2) :: p1, p2
  call marker%open_for_read_access (file, "</file>")
  marker%eof_int = huge(i_one)
  marker%eof_pos = page_ring_position (marker%eof_int)
  call marker%read_page ()
  call marker%find ('<?', skip=2, proceed=.true., pos=p1)
  call marker%find ('?>', skip=3, proceed=.false., pos=p2)
  if ((p1(2) <= 0) .or. (p2(2) <= 0)) then
    call msg_error ("serializable_deserialize_from_file: no " &
      // "version substring found.")
  end if
  call marker%set_position (p2)
  call marker%find ('<file ', skip=4, proceed=.true., pos=p1)
  call marker%find ('>', skip=1, proceed=.false., pos=p2)
  if((p1(2)>0) .and. (p2(2)>0))then
    call marker%push_position (p2)
    call marker%find ('name="', skip=4, proceed=.true., pos=p1)
    call marker%find ('"', skip=1, proceed=.false., pos=p2)
    call marker%pop_position ()
  else
    call msg_error ("serializable_deserialize_from_file: no file " &
      // "header found.")
  end if
  call this%deserialize_from_marker (name, marker)
  call marker%close ()
  call marker%finalize ()
end subroutine serializable_deserialize_from_file

```

<Muli base: serial class: TBP>+≡

```

procedure :: deserialize_from_unit => &
  serializable_deserialize_from_unit

```

<Muli base: procedures>+≡

```

subroutine serializable_deserialize_from_unit (this, unit, name)
  class(ser_class_t), intent(inout) :: this
  integer, intent(in) :: unit
  character(len=*), intent(in) :: name
  logical::opened
  !!!   gfortran bug
  !!!   character::stream
  character::read
  type(marker_t)::marker
  !!!   inquire(unit=unit,opened=opened,stream=stream,read=read)
  inquire(unit=unit,opened=opened,read=read)
  if(opened)then
    !!!       if(stream=="Y")then
    if(read=="Y")then
      print *, "dummy: serializable_serialize_from_unit"
      stop
    end if
  end if

```

```

        else
            print *,"serializable_serialize_from_unit: cannot write from read-only unit."
        end if
    !!!        else
    !!!            print *,"serializable_serialize_from_unit: access kind of unit is not 'stre
    !!!        end if
else
    print *,"serializable_serialize_from_unit: file is not opened."
end if
end subroutine serializable_deserialize_from_unit

```

This needs to be made public, and not only be present as a TBP.

```

<Muli base: public>+≡
    public :: serializable_deserialize_from_marker

<Muli base: serial class: TBP>+≡
    procedure :: deserialize_from_marker => &
        serializable_deserialize_from_marker

<Muli base: procedures>+≡
    subroutine serializable_deserialize_from_marker (this, name, marker)
        class(ser_class_t), intent(out) :: this
        character(*), intent(in) :: name
        class(marker_t), intent(inout) :: marker
        integer(dik) :: status
        if (marker%action == 2) then
            call marker%pick_instance (name, this, status)
        else
            call msg_error ("serializable_deserialize_from_marker: Marker is " &
                // "not ready for read access.")
        end if
    end subroutine serializable_deserialize_from_marker

<Muli base: serial class: TBP>+≡
    generic :: serialize => serialize_to_file, serialize_to_unit, &
        serialize_to_marker

<Muli base: serial class: TBP>+≡
    generic :: deserialize => deserialize_from_file, &
        deserialize_from_unit, deserialize_from_marker

<Muli base: public>+≡
    public :: serialize_print_peer_pointer

<Muli base: procedures>+≡
    recursive subroutine serialize_print_peer_pointer &
        (ser, unit, parents, components, peers, name)
        class(ser_class_t), pointer, intent(in) :: ser
        integer, intent(in) :: unit
        integer(dik) :: parents, components, peers
        character(len=*), intent(in) :: name
        if (associated (ser)) then
            write (unit,*) name, " is associated."
            if (peers>0) then
                write (unit,*) "Printing components of ", name
            end if
        end if
    end subroutine serialize_print_peer_pointer

```

```

        call ser%print_to_unit (unit, parents, components, peers - i_one)
    else
        write (unit,*) "Skipping components of ", name
    end if
else
    write (unit,*) name, " is not associated."
end if
end subroutine serialize_print_peer_pointer

```

<Muli base: public>+≡

```
public :: serialize_print_comp_pointer
```

<Muli base: procedures>+≡

```

recursive subroutine serialize_print_comp_pointer &
    (ser, unit, parents, components, peers, name)
class(ser_class_t), pointer, intent(in) :: ser
integer, intent(in) :: unit
integer(dik), intent(in) :: parents, components, peers
character(len=*), intent(in) :: name
if (associated (ser)) then
    write (unit,*) name," is associated."
    if (components > 0) then
        write (unit,*) "Printing components of ", name
        call ser%print_to_unit (unit, parents, components - i_one, peers)
    else
        write (unit,*) "Skipping components of ", name
    end if
else
    write (unit,*) name," is not associated."
end if
end subroutine serialize_print_comp_pointer

```

<Muli base: public>+≡

```
public :: serialize_print_allocatable
```

<Muli base: procedures>+≡

```

subroutine serialize_print_allocatable &
    (ser, unit, parents, components, peers, name)
class(ser_class_t), allocatable, intent(in) :: ser
integer, intent(in) :: unit
integer(dik), intent(in) :: parents, components, peers
character(len=*), intent(in) :: name
if (allocated (ser)) then
    write (unit,*) name, " is allocated."
    if (components > 0) then
        write (unit,*) "Printing components of ",name
        call ser%print_to_unit (unit, parents, components-1, peers)
    else
        write (unit,*) "Skipping components of ",name
    end if
else
    write (unit,*) name," is not allocated."
end if
end subroutine serialize_print_allocatable

```



```

<Muli base: public>+≡
    public :: measure_class_t

<Muli base: types>+≡
    type, abstract, extends (ser_class_t) :: measure_class_t
    contains
        procedure(measure_int), public, deferred :: measure
    end type measure_class_t

<Muli base: public>+≡
    public :: identified_t

<Muli base: types>+≡
    type, extends (ser_class_t) :: identified_t
    private
        integer(dik) :: id
        type(string_t) :: name
    contains
        <Muli base: identified type: TBP>
    end type identified_t

<Muli base: identified type: TBP>≡
    procedure :: base_write_to_marker => identified_write_to_marker
    procedure :: write_to_marker => identified_write_to_marker

<Muli base: procedures>+≡
    subroutine identified_write_to_marker (this, marker, status)
        class(identified_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        integer(dik) :: id
        id = this%get_id ()
        call marker%mark_begin ("identified_t")
        call marker%mark ("name", this%get_name ())
        call marker%mark ("id", id)
        call marker%mark_end ("identified_t")
    end subroutine identified_write_to_marker

<Muli base: identified type: TBP>+≡
    procedure :: base_read_from_marker => identified_read_from_marker
    procedure :: read_from_marker => identified_read_from_marker

<Muli base: procedures>+≡
    subroutine identified_read_from_marker (this, marker, status)
        class(identified_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        character(:), allocatable :: name
        call marker%pick_begin ("identified_t", status=status)
        call marker%pick ("name", name, status)
        call marker%pick ("id", this%id, status)
        call marker%pick_end ("identified_t", status=status)
        this%name = name
    end subroutine identified_read_from_marker

```

```

<Muli base: identified type: TBP>+≡
    procedure :: base_print_to_unit => identified_print_to_unit
    procedure :: print_to_unit => identified_print_to_unit

<Muli base: procedures>+≡
    subroutine identified_print_to_unit (this, unit, parents, components, peers)
        class(identified_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        write (unit, "(A)")          "Components of identified_t:"
        write (unit, "(A,A)")        "Name:           ", this%get_name ()
        write (unit, "(A,I10)")      "ID:             ", this%get_id ()
    end subroutine identified_print_to_unit

<Muli base: identified type: TBP>+≡
    procedure, nopass :: get_type => identified_get_type

<Muli base: procedures>+≡
    pure subroutine identified_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="identified_t")
    end subroutine identified_get_type

<Muli base: identified type: TBP>+≡
    procedure, nopass :: verify_type => identified_verify_type

<Muli base: procedures>+≡
    elemental logical function identified_verify_type (type)
        character(len=*), intent(in) :: type
        identified_verify_type = (type == "identified_t")
    end function identified_verify_type

<Muli base: identified type: TBP>+≡
    generic :: initialize => identified_initialize
    procedure, private :: identified_initialize

<Muli base: procedures>+≡
    subroutine identified_initialize (this, id, name)
        class(identified_t), intent(out) :: this
        integer(dik), intent(in) :: id
        character(len=*), intent(in) :: name
        this%name = name
        this%id = id
    end subroutine identified_initialize

<Muli base: identified type: TBP>+≡
    procedure :: get_id => identified_get_id

<Muli base: procedures>+≡
    elemental function identified_get_id (this) result(id)
        class(identified_t), intent(in) :: this
        integer(dik) :: id
        id = this%id
    end function identified_get_id

```

```

<Muli base: identified type: TBP>+≡
    procedure :: get_name => identified_get_name

<Muli base: procedures>+≡
    pure function identified_get_name (this)
        class(identified_t), intent(in) :: this
        character(len (this%name)) :: identified_get_name
        identified_get_name = char (this%name)
    end function identified_get_name

<Muli base: public>+≡
    public :: unique_t

<Muli base: types>+≡
    type, extends (identified_t) :: unique_t
        private
            integer(dik) :: unique_id
        contains
            <Muli base: unique type: TBP>
        end type unique_t

<Muli base: unique type: TBP>≡
    procedure, nopass :: get_type => unique_get_type

<Muli base: procedures>+≡
    pure subroutine unique_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="unique_t")
    end subroutine unique_get_type

<Muli base: unique type: TBP>+≡
    procedure, nopass :: verify_type => unique_verify_type

<Muli base: procedures>+≡
    elemental logical function unique_verify_type (type)
        character(len=*), intent(in) :: type
        unique_verify_type = (type == "unique_t")
    end function unique_verify_type

<Muli base: unique type: TBP>+≡
    procedure :: write_to_marker => unique_write_to_marker

<Muli base: procedures>+≡
    subroutine unique_write_to_marker (this, marker, status)
        class(unique_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%mark_begin ("unique_t")
        call identified_write_to_marker (this, marker, status)
        call marker%mark ("unique_id", this%get_unique_id ())
        call marker%mark_end ("unique_t")
    end subroutine unique_write_to_marker

```

```

<Muli base: unique marker: TBP>≡
    procedure :: read_from_marker => unique_read_from_marker

<Muli base: procedures>+≡
    subroutine unique_read_from_marker (this, marker, status)
        class(unique_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%pick_begin ("unique_t", status=status)
        call identified_read_from_marker (this, marker, status)
        call marker%pick ("unique_id", this%unique_id, status)
        call marker%pick_end ("unique_t", status)
    end subroutine unique_read_from_marker

<Muli base: unique type: TBP>+≡
    procedure :: print_to_unit => unique_print_to_unit

<Muli base: procedures>+≡
    subroutine unique_print_to_unit (this, unit, parents, components, peers)
        class(unique_t), intent(in) :: this
        integer,intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        if (parents > 0) call identified_print_to_unit &
            (this, unit, parents-1, components, peers)
        write (unit, "(A,I10)") "Unique ID:      ", this%get_unique_id ()
    end subroutine unique_print_to_unit

<Muli base: unique type: TBP>+≡
    procedure :: identified_initialize => unique_initialize

<Muli base: procedures>+≡
    subroutine unique_initialize(this,id,name)
        class(unique_t), intent(out) :: this
        integer(dik), intent(in) :: id
        character(len=*), intent(in) :: name
        call identified_initialize (this, id, name)
        last_id = last_id + 1
        this%unique_id = last_id
    end subroutine unique_initialize

<Muli base: unique type: TBP>+≡
    procedure :: get_unique_id => unique_get_unique_id

<Muli base: procedures>+≡
    pure function unique_get_unique_id (this)
        class(unique_t), intent(in) :: this
        integer(dik) :: unique_get_unique_id
        unique_get_unique_id = this%unique_id
    end function unique_get_unique_id

<Muli base: types>+≡
    type :: serializable_ref_type
        private
        integer(dik) :: id

```

```

        class(ser_class_t), pointer :: ref => null()
        class(serializable_ref_type), pointer :: next => null()
contains
    <Muli base: serial ref: TBP>
end type serializable_ref_type

<Muli base: serial ref: TBP>≡
    procedure :: finalize => serializable_ref_finalize

<Muli base: procedures>+≡
    subroutine serializable_ref_finalize (this)
        class(serializable_ref_type), intent(inout) :: this
        class(serializable_ref_type), pointer :: next
        do while (associated (this%next))
            next => this%next
            this%next => next%next
            nullify (next%ref)
            deallocate (next)
        end do
        if (associated (this%ref)) nullify (this%ref)
    end subroutine serializable_ref_finalize

<Muli base: types>+≡
    type :: position_stack_t
        private
        integer(dik), dimension(2) :: position
        class(position_stack_t), pointer :: next => null()
contains
    <Muli base: position stack: TBP>
end type position_stack_t

<Muli base: position stack: TBP>≡
    generic :: push => push_head, push_given
    procedure :: push_head => position_stack_push_head
    procedure :: push_given => position_stack_push_given

<Muli base: procedures>+≡
    subroutine position_stack_push_head (this)
        class(position_stack_t) :: this
        class(position_stack_t), pointer :: new
        allocate (new)
        new%next => this%next
        new%position = this%position
        this%next => new
    end subroutine position_stack_push_head

<Muli base: procedures>+≡
    subroutine position_stack_push_given (this, position)
        class(position_stack_t) :: this
        integer(dik), dimension(2), intent(in) :: position
        class(position_stack_t), pointer :: new
        allocate (new)
        new%next => this%next

```

```

        new%position = position
        this%next => new
    end subroutine position_stack_push_given

<Muli base: position stack: TBP>+≡
    generic :: pop => position_stack_pop, position_stack_drop
    procedure :: position_stack_pop
    procedure :: position_stack_drop

<Muli base: procedures>+≡
    subroutine position_stack_pop (this)
        class(position_stack_t) :: this
        class(position_stack_t), pointer :: old
        if (associated (this%next)) then
            old => this%next
            this%next => old%next
            this%position = old%position
            deallocate (old)
        end if
    end subroutine position_stack_pop

<Muli base: procedures>+≡
    subroutine position_stack_drop (this, position)
        class(position_stack_t) :: this
        integer(dik), dimension(2), intent(out) :: position
        class(position_stack_t), pointer :: old
        if (associated (this%next)) then
            old => this%next
            this%next => old%next
            position = old%position
            deallocate (old)
        else
            position= [0,0]
        end if
    end subroutine position_stack_drop

<Muli base: position stack: TBP>+≡
    procedure :: nth_position => position_stack_nth_position

<Muli base: procedures>+≡
    function position_stack_nth_position (this, n) result (position)
        class(position_stack_t), intent(in) :: this
        integer(dik), intent(in) :: n
        integer(dik), dimension(2) :: position
        class(position_stack_t), pointer :: tmp
        integer(dik) :: pos
        tmp => this%next
        pos = n
        do while (associated (tmp) .and. pos>0)
            tmp => tmp%next
            pos = pos - 1
        end do
        if (associated(tmp)) then
            position = tmp%position
        end if
    end function position_stack_nth_position

```

```

        else
            position = [0,0]
        end if
    end function position_stack_nth_position

<Muli base: position stack: TBP>+=
    procedure :: first => position_stack_first

<Muli base: procedures>+=
    function position_stack_first(this) result(position)
        class(position_stack_t), intent(in) :: this
        integer(kind=dik), dimension(2) :: position, tmp_position
        class(position_stack_t), pointer :: tmp_stack
        tmp_position = this%position
        tmp_stack => this%next
        do while (associated (tmp_stack))
            if (page_ring_position_is_before (tmp_stack%position, tmp_position)) then
                tmp_position = tmp_stack%position
            end if
            tmp_stack => tmp_stack%next
        end do
    end function position_stack_first

<Muli base: position stack: TBP>+=
    procedure :: last => position_stack_last

<Muli base: procedures>+=
    function position_stack_last (this) result (position)
        class(position_stack_t), intent(in) :: this
        integer(dik), dimension(2) :: position, tmp_position
        class(position_stack_t), pointer :: tmp_stack
        tmp_position = this%position
        tmp_stack => this%next
        do while (associated (tmp_stack))
            if (page_ring_position_is_before (tmp_position, tmp_stack%position)) then
                tmp_position = tmp_stack%position
            end if
            tmp_stack => tmp_stack%next
        end do
    end function position_stack_last

<Muli base: position stack: TBP>+=
    procedure :: range => position_stack_range

<Muli base: procedures>+=
    pure function position_stack_range (this) result (position)
        class(position_stack_t), intent(in) :: this
        integer(dik), dimension(2) :: position
        class(position_stack_t), pointer :: tmp
    end function position_stack_range

<Muli base: public>+=
    public :: page_ring_t

```

```

<Muli base: types>+≡
type :: page_ring_t
private
logical :: asynchronous = serialize_default_asynchronous
logical :: eof_reached = .false.
integer :: unit = -1
integer(dik) :: ring_size = 2
integer(dik) :: action = 0
integer(dik) :: eof_int = -1
integer(dik) :: out_unit = output_unit
integer(dik) :: err_unit = error_unit
integer(dik), dimension(2) :: active_pages = [0,-1]
integer(dik), dimension(2) :: eof_pos = [-1,-1]
type(string_t) :: eof_string
type(position_stack_t) :: position_stack
character(serialize_page_size), dimension(:), allocatable::ring
contains
<Muli base: page ring: TBP>
end type page_ring_t

```

These are the `page_ring_t` procedures, here for read access only:

```

<Muli base: page ring: TBP>≡
procedure :: open_for_read_access => page_ring_open_for_read_access

<Muli base: procedures>+≡
subroutine page_ring_open_for_read_access &
    (this, file, eof_string, asynchronous)
class(page_ring_t), intent(inout) :: this
character(*), intent(in) :: file, eof_string
logical, intent(in), optional :: asynchronous
logical :: exist
this%eof_string = eof_string
inquire (file=file, exist=exist)
if (exist) then
    this%action = 2
else
    call msg_error ("page_ring_open: File " // file // " is opened " &
        // "for read access but does not exist.")
end if
if (present (asynchronous)) this%asynchronous = asynchronous
if (this%unit < 0) call generate_unit (this%unit, 100, 1000)
if (this%unit < 0) then
    call msg_error ("page_ring_open: No free unit found.")
end if
this%ring_size = 2
call this%set_position ([i_zero,i_one])
this%active_pages = [i_zero,-i_one]
if (allocated (this%ring)) deallocate (this%ring)
allocate (this%ring (i_zero:this%ring_size - i_one))
if (this%asynchronous) then
    open (this%unit, file=file, access="stream", &
        action="read", asynchronous="yes", status="old")
else
    open (this%unit, file=file, access="stream", action="read", &

```



```

        asynchronous="no", status="old")
    end if
    call this%read_page ()
end subroutine page_ring_open_for_read_access

```

<Muli base: page ring: TBP>+≡

```

    procedure :: read_page => page_ring_read_page

```

<Muli base: procedures>+≡

```

subroutine page_ring_read_page (this)
    class(page_ring_t), intent(inout) :: this
    integer(dik) :: iostat
    character(8) :: iomsg
    if (.not. this%eof_reached) then
        call this%activate_next_page ()
        read (this%unit, iostat=iostat) this%ring (this%last_index ())
        if (iostat == iostat_end) then
            this%eof_reached = .true.
            this%eof_pos(1) = this%last_page ()
            this%eof_pos(2) = index(this%ring(this%last_index()), &
                char(this%eof_string))
            this%eof_pos(2) = this%eof_pos(2) + len(this%eof_string) - 1
            this%eof_int = page_ring_ordinal(this%eof_pos)
        end if
    end if
end subroutine page_ring_read_page

```

Those are the write access only type-bound procedures of `page_ring_t`:

<Muli base: page ring: TBP>+≡

```

    procedure :: open_for_write_access => page_ring_open_for_write_access

```

<Muli base: procedures>+≡

```

subroutine page_ring_open_for_write_access (this, file, asynchronous)
    class(page_ring_t), intent(inout) :: this
    character(*), intent(in) :: file
    logical, intent(in), optional :: asynchronous
    this%action = 1
    if (present (asynchronous)) this%asynchronous = asynchronous
    if (this%unit < 0) call generate_unit (this%unit, 100, 1000)
    if (this%unit < 0) then
        call msg_error ("page_ring_open: No free unit found.")
    end if
    this%ring_size = 2
    call this%set_position ([i_zero,i_one])
    this%active_pages = [i_zero,-i_one]
    if (allocated (this%ring)) deallocate (this%ring)
    allocate (this%ring (i_zero:this%ring_size-i_one))
    if (this%asynchronous) then
        open (this%unit, file=file, access="stream", action="write", &
            asynchronous="yes", status="replace")
    else
        open (this%unit, file=file, access="stream", action="write", &
            asynchronous="no", status="replace")
    end if
end subroutine

```

```

end subroutine page_ring_open_for_write_access

<Muli base: page ring: TBP>+≡
  procedure :: flush => page_ring_flush

<Muli base: procedures>+≡
  subroutine page_ring_flush (this)
    class(page_ring_t), intent(inout) :: this
    integer(dik) :: page
    do while (this%active_pages(1) < this%actual_page ())
      if (this%asynchronous) then
        write (this%unit, asynchronous="yes") &
          this%ring(mod(this%active_pages(1), this%ring_size))
      else
        write (this%unit, asynchronous="no") &
          this%ring(mod(this%active_pages(1), this%ring_size))
      end if
      this%active_pages(1) = this%active_pages(1) + 1
    end do
  end subroutine page_ring_flush

<Muli base: page ring: TBP>+≡
  procedure :: break => page_ring_break

<Muli base: procedures>+≡
  subroutine page_ring_break(this)
    class(page_ring_t), intent(inout) :: this
    if (this%actual_page () >= this%active_pages(2)) &
      call this%activate_next_page ()
    call this%turn_page ()
  end subroutine page_ring_break

```

For comparisons:

```

<Muli base: page ring: TBP>+≡
  procedure :: str_equal => page_ring_str_equal

<Muli base: procedures>+≡
  pure logical function page_ring_str_equal (this, string, pos)
    class(page_ring_t), intent(in) :: this
    character(*), intent(in) :: string
    integer(dik), dimension(2,2), intent(in) :: pos
    page_ring_str_equal = string == this%substring (pos)
  end function page_ring_str_equal

```

Routines for searching:

```

<Muli base: page ring: TBP>+≡
  generic :: find => page_ring_find, page_ring_find_default
  procedure, private :: page_ring_find
  procedure, private :: page_ring_find_default

```

```

<Multi base: procedures>+≡
recursive subroutine page_ring_find &
    (this, exp, start, limit, skip, proceed, pos)
    class(page_ring_t), intent(inout) :: this
    integer(dik), dimension(2), intent(in) :: start
    integer(dik), dimension(2), intent(in) :: limit
    character(*), intent(in) :: exp
    integer, intent(in) :: skip
    logical, intent(in) :: proceed
    integer(dik), dimension(2), intent(out) :: pos
    integer(dik) :: page, page2, ind
    page = this%ring_index (start(1))
    if (limit(1) == start(1)) then
        ind = index(this%ring(page) (start(2):limit(2)), exp)
        if (ind > 0) then
            select case (skip)
            case (1)
                pos = [start(1), start(2)+ind-2]
                if (pos(2) == 0) then
                    pos(1) = pos(1) - 1
                    pos(2) = serialize_page_size
                end if
            case (2)
                pos = [start(1), start(2)+ind-1]
            case (3)
                pos = [start(1), start(2)+ind+len(exp)-2]
            case (4)
                pos = [start(1), start(2)+ind+len(exp)-1]
                if (pos(1) == this%last_page()) call this%read_page ()
                if (pos(2) > serialize_page_size) then
                    pos(1) = pos(1) + 1
                    pos(2) = pos(2) - serialize_page_size
                end if
            end select
            if (proceed) call this%set_position (pos)
        else
            Call msg_warning ("page_ring_find: limit reached.")
            pos = [-1, -1]
        end if
    else
        ind = index (this%ring(page) (start(2):), exp)
        if (ind > 0) then
            select case (skip)
            case (1)
                pos = [start(1), start(2)+ind-2]
                if (pos(2) == 0) then
                    pos(1) = pos(1) - 1
                    pos(2) = serialize_page_size
                end if
            case (2)
                pos = [start(1), start(2)+ind-1]
            case (3)
                pos = [start(1), start(2)+ind+len(exp)-2]
            case (4)

```

```

        pos = [start(1), start(2)+ind+len(exp)-1]
        if (pos(1) == this%last_page ()) call this%read_page ()
        if (pos(2) > serialize_page_size) then
            pos(1) = pos(1) + 1
            pos(2) = i_one
        end if
    end select
    if(proceed)call this%set_position(pos)
else
    if (start(1) + 1 > this%active_pages (2)) then
        call this%read_page ()
        page = this%ring_index(start(1))
    end if
    page2 = this%ring_index(start(1)+1)
    ind = index(this%ring(page) (serialize_page_size - &
        len(exp)+1:)//this%ring(page2)(:len(exp)),exp)
    if (ind > 0) then
        select case (skip)
        case (1)
            pos = [start(1), serialize_page_size-len(exp)+ind-1]
        case (2)
            pos = [start(1), serialize_page_size-len(exp)+ind]
        case (3)
            pos = [start(1)+1, ind-1]
        case (4)
            pos = [start(1)+1, ind]
        end select
        if (pos(2) > serialize_page_size) then
            pos(1) = pos(1) + 1
            pos(2) = pos(2) - serialize_page_size
        else
            if (pos(2) < 0) then
                pos(1) = pos(1) - 1
                pos(2) = pos(2) + serialize_page_size
            end if
        end if
        if (proceed) call this%set_position (pos)
    else
        if (proceed) this%active_pages(1) = this%active_pages(2)
        call this%find (exp, [start(1) + i_one, i_one], &
            limit, skip, proceed, pos)
    end if
end if
end if
end subroutine page_ring_find

```

(Multi base: procedures)+≡

```

subroutine page_ring_find_default (this, exp, skip, proceed, pos)
    class(page_ring_t), intent(inout) :: this
    character(*), intent(in), optional :: exp
    integer, intent(in) :: skip
    logical, intent(in) :: proceed
    integer(dik), dimension(2), intent(out) :: pos
    call this%find (exp, this%position_stack%position, this%eof_pos, &

```

```

        skip, proceed, pos)
end subroutine page_ring_find_default

```

<Multi base: page ring: TBP>+≡

```

    procedure :: find_pure => page_ring_find_pure

```

<Multi base: procedures>+≡

```

pure recursive function page_ring_find_pure &
    (this, exp, start, limit, skip) result (pos)
class(page_ring_t),intent(in) :: this
integer(dik), dimension(2), intent(in) :: start
integer(dik), dimension(2), intent(in) :: limit
character(*),intent(in) :: exp
integer,optional,intent(in) :: skip
integer(dik), dimension(2) :: pos
integer(dik) :: page, page2, ind, actual_skip
!!! Is the starting point before limit?
if (start(1) <= limit(1)) then
    !!! Default skip is what you expect from the build-in index function
    if (present(skip)) then
        actual_skip = skip
    else
        actual_skip = 2
    end if
    page = mod(start(1), this%ring_size)
    !!! Does the scanning region end on the page?
    if (start(1) == limit(1)) then
        ind = index (this%ring (page) (start(2):limit(2)),exp)
    else
        ind = index (this%ring (page) (start(2):),exp)
    end if
    if (ind > 0) then
        !!! substring found on first page
        select case (actual_skip)
        case (1)
            pos = [start(1), start(2)+ind-2]
            if (pos(2) == 0) then
                pos(1) = pos(1) - 1
                pos(2) = serialize_page_size
            end if
        case (2)
            pos= [start(1), start(2)+ind-1]
        case (3)
            pos= [start(1), start(2)+ind+len(exp)-2]
        case (4)
            pos= [start(1), start(2)+ind+len(exp)-1]
            if (pos(2) > serialize_page_size) then
                pos(1) = pos(1) + 1
                pos(2) = pos(2) - serialize_page_size
            end if
        end select
    else
        !!! Substring not found on first page. Is the next page already read?
        if ((start(1) >= limit(1)) .or. &

```

```

        (start(1)+1 > this%active_pages(2))) then
        !!! Either the limit is reached or the next page is not ready.
        pos = [0, 0]
    else
        !!! The next page is available.
        page2 = mod(start(1)+1, this%ring_size)
        !!! We concatenate the edges. When l is the length of exp,
        !!! then we want to concatenate the l-1 last characters of
        !!! page one and the first l characters of page two.
        ! print *, "overlap: |", this%ring(page) &
        !       (serialize_page_size-len(exp)+2)//this%ring(page2) &
        !       (:len(exp)), "|"
        ind = index (this%ring(page) (serialize_page_size - &
            len(exp)+2)//this%ring(page2) (:len(exp)), exp)
        if (ind > 0) then
            select case (actual_skip)
            case (1)
                pos = [start(1), serialize_page_size-len(exp)+ind]
            case (2)
                pos = [start(1), serialize_page_size-len(exp)+ind+1]
            case (3)
                pos = [start(1)+1, ind]
            case (4)
                pos = [start(1)+1, ind+1]
            end select
        else
            !!! EXP is not found in the overlap region.
            !!! We recursively search the next pages.
            pos = this%find_pure (exp, [start(i_one) + i_one, i_one], &
                limit, skip)
        end if
    end if
end if
else
    !!! Limit is before start
    pos = [0, 0]
end if
end function page_ring_find_pure

```

page_ring_t routines for positioning:

```

<Multi base: page ring: TBP>+≡
    generic :: get_position => page_ring_get_position1, page_ring_get_position2
    procedure, private :: page_ring_get_position1
    procedure, private :: page_ring_get_position2

<Multi base: procedures>+≡
    pure subroutine page_ring_get_position1 (this, pos)
        class(page_ring_t), intent(in) :: this
        integer(dik), intent(out) :: pos
        pos = page_ring_ordinal (this%position_stack%position)
    end subroutine page_ring_get_position1

```

<Multi base: procedures>+≡

```

pure subroutine page_ring_get_position2 (this, pos)
  class(page_ring_t), intent(in) :: this
  integer(dik), dimension(2), intent(out) :: pos
  pos = this%position_stack%position
end subroutine page_ring_get_position2

<Muli base: page ring: TBP>+≡
generic :: pop_position => pop_actual_position, pop_given_position
procedure, private :: pop_actual_position => &
  page_ring_ring_pop_actual_position
procedure, private :: pop_given_position => &
  page_ring_ring_pop_given_position

<Muli base: procedures>+≡
subroutine page_ring_ring_pop_actual_position (this)
  class(page_ring_t), intent(inout) :: this
  call this%position_stack%pop ()
end subroutine page_ring_ring_pop_actual_position

<Muli base: procedures>+≡
subroutine page_ring_ring_pop_given_position (this, pos)
  class(page_ring_t), intent(inout) :: this
  integer(dik), dimension(2), intent(out) :: pos
  call this%position_stack%pop (pos)
end subroutine page_ring_ring_pop_given_position

<Muli base: page ring: TBP>+≡
generic :: push_position => push_actual_position, push_given_position
procedure, private :: push_actual_position => &
  page_ring_ring_push_actual_position
procedure, private :: push_given_position => &
  page_ring_ring_push_given_position

<Muli base: procedures>+≡
subroutine page_ring_ring_push_actual_position (this)
  class(page_ring_t), intent(inout) :: this
  call this%position_stack%push ()
end subroutine page_ring_ring_push_actual_position

<Muli base: procedures>+≡
subroutine page_ring_ring_push_given_position (this, pos)
  class(page_ring_t), intent(inout) :: this
  integer(dik), dimension(2), intent(in) :: pos
  call this%position_stack%push (pos)
end subroutine page_ring_ring_push_given_position

<Muli base: page ring: TBP>+≡
procedure :: set_position => page_ring_set_position

<Muli base: procedures>+≡
subroutine page_ring_set_position (this, pos)
  class(page_ring_t), intent(inout) :: this
  integer(dik), dimension(2), intent(in) :: pos

```

```

        this%position_stack%position = pos
    end subroutine page_ring_set_position

```

<Muli base: page ring: TBP>+≡

```

    procedure :: turn_page => page_ring_turn_page

```

<Muli base: procedures>+≡

```

    subroutine page_ring_turn_page (this)
        class(page_ring_t), intent(inout) :: this
        this%position_stack%position(1) = this%position_stack%position(1) + 1
        this%position_stack%position(2) = 1
    end subroutine page_ring_turn_page

```

<Muli base: page ring: TBP>+≡

```

    procedure :: proceed => page_ring_proceed

```

<Muli base: procedures>+≡

```

    subroutine page_ring_proceed (this, n, deactivate)
        class(page_ring_t), intent(inout) :: this
        integer(dik), intent(in) :: n
        logical, intent(in), optional :: deactivate
        integer(dik) :: offset
        offset = this%position_stack%position(2) + n
        do while (offset > serialize_page_size)
            if (this%position_stack%position(1) >= this%active_pages(2)) &
                call this%activate_next_page ()
            this%position_stack%position(1) = this%position_stack%position(1) + 1
            offset = offset - serialize_page_size
        end do
        this%position_stack%position(2) = offset
        if (present (deactivate)) then
            if (deactivate)this%active_pages(1) = this%actual_page ()
        end if
    end subroutine page_ring_proceed

```

These are the `page_ring_t` routines for printing:

<Muli base: page ring: TBP>+≡

```

    procedure :: print_to_unit => page_ring_print_to_unit

```

<Muli base: procedures>+≡

```

    subroutine page_ring_print_to_unit (this, unit, parents, components, peers)
        class(page_ring_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        write (unit, "(1x,A)") "Components of page_ring_t: "
        write (unit, "(3x,A,A)") "asynchronous: ", this%asynchronous
        write (unit, "(3x,A,L1)") "eof reached: ", this%eof_reached
        write (unit, "(3x,A,I0)") "ring_size: ", this%ring_size
        write (unit, "(3x,A,I0)") "unit: ", this%unit
        write (unit, "(3x,A,I0)") "action: ", this%action
        write (unit, "(3x,A,I0,I0)") &
            "position: ", this%position_stack%position
        write (unit, "(3x,A,I0)") "active_pages: ", this%active_pages
        write (unit, "(3x,A,I0)") "file size: ", this%eof_int
    end subroutine page_ring_print_to_unit

```



```

write (unit, "(3x,A,I0,I0)") "eof position: ", this%eof_pos
write (unit, "(3x,A,A)") "eof string:  ", char(this%eof_string)
if (allocated (this%ring)) then
    write (unit, "(3x,A)") "Ring is allocated."
    if (components > 0) call this%print_ring (unit)
else
    write (unit, "(3x,A)") "Ring is not allocated."
end if
end subroutine page_ring_print_to_unit

```

```

<Muli base: page ring: TBP>+≡
procedure :: print_ring => page_ring_print_ring

```

```

<Muli base: procedures>+≡
subroutine page_ring_print_ring (this, unit)
    class(page_ring_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik) :: n
    write (unit, "(1x,A)") "Begin of page ring"
    do n = this%active_pages(1), this%active_pages(2)
        write (unit, "(3x,A,I0,A,A)") &
            "(", n, ")", this%ring (mod(n, this%ring_size))
    end do
    write (unit, "(1x,A)") "End of page ring"
end subroutine page_ring_print_ring

```

```

<Muli base: page ring: TBP>+≡
procedure :: print_position => page_ring_print_position

```

```

<Muli base: procedures>+≡
subroutine page_ring_print_position(this)
    class(page_ring_t), intent(inout) :: this
    print *, this%actual_position(), &
        this%ring(this%actual_index()) (:this%actual_offset() - 1), "|", &
        this%ring(this%actual_index()) (this%actual_offset():)
end subroutine page_ring_print_position

```

Here are the `page_ring_t` routines for writing:

```

<Muli base: page ring: TBP>+≡
procedure :: put => page_ring_put

```

```

<Muli base: procedures>+≡
subroutine page_ring_put (this)
    class(page_ring_t), intent(inout) :: this
end subroutine page_ring_put

```

```

<Muli base: page ring: TBP>+≡
generic :: push => push_string, push_integer, push_integer_dik, &
    push_real, push_integer_array, push_integer_array_dik, &
    push_real_array

```

```

<Muli base: page ring: TBP>+≡
procedure, private :: push_string => page_ring_push_string

```

```

<Muli base: procedures>+≡
recursive subroutine page_ring_push_string (this, string)
  class(page_ring_t), intent(inout) :: this
  character(*), intent(in) :: string
  integer(dik) :: cut, l
  l = len(string)
  if (l <= serialize_page_size-this%actual_offset()+1) then
    this%ring(this%actual_index()) &
      (this%actual_offset():this%actual_offset()+l-1)=string
    if (l == serialize_page_size-this%actual_offset()+1) then
      call this%break()
      call this%flush()
    else
      call this%proceed(l)
    end if
  else
    cut = serialize_page_size-this%actual_offset() + 1
    call this%push_string(string(:cut))
    call this%push_string(string(cut+1:))
  end if
end subroutine page_ring_push_string

```

```

<Muli base: page ring: TBP>+≡
procedure, private :: push_integer => page_ring_push_integer

```

```

<Muli base: procedures>+≡
subroutine page_ring_push_integer (this, in)
  class(page_ring_t), intent(inout) :: this
  integer, intent(in) :: in
  call this%push_integer_dik (int(in,kind=dik))
end subroutine page_ring_push_integer

```

```

<Muli base: page ring: TBP>+≡
procedure, private :: push_integer_dik => page_ring_push_integer_dik

```

```

<Muli base: procedures>+≡
recursive subroutine page_ring_push_integer_dik (this, int)
  class(page_ring_t), intent(inout) :: this
  integer(dik), intent(in) :: int
  integer(dik) :: int1
  if (int < 0) then
    call this%push ("-")
    call this%push_integer_dik (-int)
  else
    if (int > 9) call this%push (int/10)
    int1 = mod(int, 10*i_one)
    select case (int1)
    case (0)
      call this%push ("0")
    case (1)
      call this%push ("1")
    case (2)
      call this%push ("2")
    case (3)

```

```

        call this%push ("3")
    case (4)
        call this%push ("4")
    case (5)
        call this%push ("5")
    case (6)
        call this%push ("6")
    case (7)
        call this%push ("7")
    case (8)
        call this%push ("8")
    case (9)
        call this%push ("9")
    end select
end if
end subroutine page_ring_push_integer_dik

```

<Muli base: page ring: TBP>+≡
 procedure, private :: push_integer_array => page_ring_push_integer_array

<Muli base: procedures>+≡
 subroutine page_ring_push_integer_array(this,int)
 class(page_ring_t), intent(inout) :: this
 integer, dimension(:), intent(in) :: int
 integer :: n
 do n = 1, size(int)
 call this%push (int(n))
 call this%push (" ")
 end do
end subroutine page_ring_push_integer_array

<Muli base: page ring: TBP>+≡
 procedure, private :: push_integer_array_dik => &
 page_ring_push_integer_array_dik

<Muli base: procedures>+≡
 subroutine page_ring_push_integer_array_dik(this,int)
 class(page_ring_t), intent(inout) :: this
 integer(dik), dimension(:), intent(in) :: int
 integer(dik) :: n
 do n = 1, size(int)
 call this%push (int(n))
 call this%push (" ")
 end do
end subroutine page_ring_push_integer_array_dik

<Muli base: page ring: TBP>+≡
 procedure, private :: push_real => page_ring_push_real

<Muli base: procedures>+≡
 subroutine page_ring_push_real (this, dou)
 class(page_ring_t), intent(inout) :: this
 real(default), intent(in) :: dou
 integer(dik) :: f

```

! print *, "page_ring_push_real: ", dou
if (dou == 0D0) then
  call this%push ("0")
else
  f = int (scale (fraction(dou), digits(dou)), kind=dik)
  call this%push (digits(dou))
  call this%push (":")
  call this%push (f)
  call this%push (":")
  call this%push (exponent(dou))
end if
call this%push (" ")
end subroutine page_ring_push_real

```

<Muli base: page ring: TBP>+≡
 procedure, private :: push_real_array => page_ring_push_real_array

<Muli base: procedures>+≡
 subroutine page_ring_push_real_array (this, dou)
 class(page_ring_t), intent(inout) :: this
 real(default), dimension(:), intent(in) :: dou
 integer(dik) :: n
 do n=1, size(dou)
 call this%push (dou(n))
 end do
end subroutine page_ring_push_real_array

<Muli base: page ring: TBP>+≡
 procedure :: get_character => page_ring_get_character

<Muli base: procedures>+≡
 elemental function page_ring_get_character (this)
 class(page_ring_t), intent(in) :: this
 character :: page_ring_get_character
 page_ring_get_character = this%ring (this%actual_index()) &
 (this%actual_offset():this%actual_offset())
end function page_ring_get_character

<Muli base: page ring: TBP>+≡
 procedure :: allocate_substring => page_ring_allocate_substring

<Muli base: procedures>+≡
 subroutine page_ring_allocate_substring (this, p1, p2, string)
 class(page_ring_t), intent(in) :: this
 integer(dik), dimension(2), intent(in) :: p1, p2
 character(:), allocatable, intent(out) :: string
 string = this%substring (p1, p2)
end subroutine page_ring_allocate_substring

<Muli base: page ring: TBP>+≡
 procedure :: pop_character => page_ring_pop_character

```

<Muli base: procedures>+≡
subroutine page_ring_pop_character (this, c)
  class(page_ring_t), intent(inout) :: this
  character, intent(out) :: c
  c = this%ring (this%actual_index()) &
    (this%actual_offset():this%actual_offset())
  if (this%actual_offset () == serialize_page_size) call this%read_page
  call this%proceed (i_one)
end subroutine page_ring_pop_character

```

```

<Muli base: page ring: TBP>+≡
procedure :: pop_by_keys => page_ring_pop_by_keys

```

```

<Muli base: procedures>+≡
subroutine page_ring_pop_by_keys (this, start, stop, inclusive, res)
  class(page_ring_t), intent(inout) :: this
  character(*), intent(in), optional :: start
  character(*), intent(in) :: stop
  logical, optional, intent(in) :: inclusive
  character(len=*), intent(out) :: res
  integer(dik), dimension(2) :: i1, i2
  if (inclusive) then
    call this%find (start, 2, .true., i1)
    call this%find (stop, 3, .false., i2)
  else
    call this%find (start, 4, .true., i1)
    call this%find (stop, 1, .false., i2)
  end if
  res = this%substring (i1, i2)
  call this%set_position (i2)
end subroutine page_ring_pop_by_keys

```

```

<Muli base: page ring: TBP>+≡
generic :: substring => page_ring_substring1, page_ring_substring2
procedure, private :: page_ring_substring1
procedure, private :: page_ring_substring2

```

```

<Muli base: procedures>+≡
pure function page_ring_substring1 (this, i) result (res)
  class(page_ring_t), intent(in) :: this
  integer(dik), dimension(2,2), intent(in) :: i
  character(ring_position_metric1(i)) :: res
  integer(dik) :: page, pos
  if (i(1,1) == i(1,2)) then
    res = this%ring (mod(i(1,1), this%ring_size)) (i(2,1):i(2,2))
  else
    pos = serialize_page_size - i(2,1)
    res(1:pos+1) = this%ring (mod(i(1,1),this%ring_size)) (i(2,1):)
    do page = i(1,1) + 1, i(1,1) - 1
      res (pos+2:pos+2+serialize_page_size) = &
        this%ring (mod(page,this%ring_size))
      pos = pos + serialize_page_size
    end do
    res(pos+2:pos+1+i(2,2)) = &

```

```

        this%ring (mod(page,this%ring_size)) (1:i(2,2))
    end if
end function page_ring_substring1

```

<Muli base: procedures>+≡

```

pure function page_ring_substring2 (this, i1, i2) result (res)
    class(page_ring_t), intent(in) :: this
    integer(dik), dimension(2), intent(in) :: i1,i2
    character(ring_position_metric2(i1,i2)) :: res
    integer(dik) :: page, pos
    if (i1(1) == i2(1)) then
        res = this%ring(mod(i1(1),this%ring_size)) (i1(2):i2(2))
    else
        pos = serialize_page_size - i1(2)
        res(1:pos+1) = this%ring(mod(i1(1),this%ring_size)) (i1(2):)
        do page = i1(1)+1, i2(1)-1
            res(pos+2:pos+2+serialize_page_size) = &
                this%ring(mod(page, this%ring_size))
            pos = pos + serialize_page_size
        end do
        res(pos+2:pos+1+i2(2)) = this%ring(mod(page, this%ring_size)) (1:i2(2))
    end if
end function page_ring_substring2

```

<Muli base: page ring: TBP>+≡

```

generic :: substring_by_keys => page_ring_character_by_keys, &
    page_ring_positions_by_keys
procedure, private :: page_ring_character_by_keys
procedure, private :: page_ring_positions_by_keys

```

<Muli base: procedures>+≡

```

pure recursive subroutine page_ring_character_by_keys (this, exp1, &
    exp2, start, limit, inclusive, length, string)
    class(page_ring_t), intent(in) :: this
    character(*), intent(in) :: exp1, exp2
    integer(dik), dimension(2), intent(in) :: start, limit
    logical, optional, intent(in) :: inclusive
    integer(dik), intent(out), optional :: length
    character(:), allocatable, intent(out) :: string
    integer(dik), dimension(2,2) :: pos
    call this%substring_by_keys (exp1, exp2, start, limit, &
        inclusive, length, pos)
    string = this%substring (pos(:,1),pos(:,2))
end subroutine page_ring_character_by_keys

```

<Muli base: procedures>+≡

```

pure recursive subroutine page_ring_positions_by_keys (this, exp1, &
    exp2, start, limit, inclusive, length, pos)
    class(page_ring_t), intent(in) :: this
    character(*), intent(in) :: exp1, exp2
    integer(dik), dimension(2), intent(in) :: start, limit
    logical, optional, intent(in) :: inclusive
    integer(dik), intent(out), optional :: length

```

```

integer(dik), dimension(2,2), intent(out) :: pos
if (inclusive) then
    pos(1:2,1) = this%find_pure (exp1, start, limit, 2)
else
    pos(1:2,1) = this%find_pure (exp1,start, limit, 4)
end if
! print *,pos1
if (present(length)) then
    length = 0
end if
if (pos(2,1) > 0) then
    if (inclusive) then
        pos(1:2,2) = this%find_pure (exp2, pos(1:2,1), limit, 3)
    else
        pos(1:2,2) = this%find_pure (exp2, pos(1:2,1), limit, 1)
    end if
    ! print *,pos2
    if (pos(2,2) > 0) then
        if (present (length)) then
            length = ring_position_metric1 (pos)
        end if
    end if
end if
end subroutine page_ring_positions_by_keys

```

<Muli base: page ring: TBP>+≡

```

generic :: pop => pop_string, pop_integer, pop_integer_dik, &
    pop_real, pop_logical, pop_integer_array, &
    pop_integer_array_dik, pop_real_array

```

<Muli base: page ring: TBP>+≡

```

procedure, private :: pop_string => page_ring_pop_string

```

<Muli base: procedures>+≡

```

recursive subroutine page_ring_pop_string (this, res)
    class(page_ring_t), intent(inout) :: this
    character(len=*), intent(out) :: res
    integer(dik) :: n, cut
    n = len(res)
    cut = serialize_page_size-this%actual_offset() + 1
    if (n <= cut) then
        res = this%ring (this%actual_index()) &
            (this%actual_offset():this%actual_offset()+n)
        if (n == cut) then
            call this%read_page
        end if
        call this%proceed (n)
    else
        call this%pop (res(:cut))
        call this%pop (res(cut+1:))
    end if
end subroutine page_ring_pop_string

```

<Muli base: page ring: TBP>+≡

```

procedure, private :: pop_integer => page_ring_pop_integer

```

```

<Muli base: procedures>+≡
  subroutine page_ring_pop_integer (this,in)
    class(page_ring_t), intent(inout) :: this
    integer, intent(out) :: in
    integer(dik) :: in_dik
    call this%pop (in_dik)
    in = int(in_dik)
  end subroutine page_ring_pop_integer

<Muli base: page ring: TBP>+≡
  procedure, private :: pop_integer_dik => page_ring_pop_integer_dik

<Muli base: procedures>+≡
  subroutine page_ring_pop_integer_dik (this, int)
    class(page_ring_t), intent(inout) :: this
    integer(dik), intent(out) :: int
    integer(dik) :: int1
    integer(dik) :: sign
    character :: c
    int = 0
    sign = 1
    c = " "
    do while (scan (c, serialize_integer_characters) == 0)
      call this%pop_character (c)
    end do
    if (c == "-") then
      sign = -1
      call this%pop_character (c)
    end if
    do while (scan (c, serialize_integer_characters) > 0)
      int = int * 10
      select case (c)
        case ("1")
          int = int + 1
        case ("2")
          int = int + 2
        case ("3")
          int = int + 3
        case ("4")
          int = int + 4
        case ("5")
          int = int + 5
        case ("6")
          int = int + 6
        case ("7")
          int = int + 7
        case ("8")
          int = int + 8
        case ("9")
          int = int + 9
      end select
      call this%pop_character (c)
    end do
    int = int * sign

```



```

        if (c == "<") call this%proceed (-i_one)
    end subroutine page_ring_pop_integer_dik

<Muli base: page ring: TBP>+≡
    procedure, private :: pop_integer_array => page_ring_pop_integer_array

<Muli base: procedures>+≡
    subroutine page_ring_pop_integer_array (this, int)
        class(page_ring_t), intent(inout) :: this
        integer, dimension(:), intent(out) :: int
        integer :: n
        do n = 1, size(int)
            call this%pop (int(n))
        end do
    end subroutine page_ring_pop_integer_array

<Muli base: page ring: TBP>+≡
    procedure, private :: pop_integer_array_dik => &
        page_ring_pop_integer_array_dik

<Muli base: procedures>+≡
    subroutine page_ring_pop_integer_array_dik (this, int)
        class(page_ring_t), intent(inout) :: this
        integer(dik), dimension(:), intent(out) :: int
        integer(dik) :: n
        do n = 1, size(int)
            call this%pop (int(n))
        end do
    end subroutine page_ring_pop_integer_array_dik

<Muli base: page ring: TBP>+≡
    procedure, private :: pop_logical => page_ring_pop_logical

<Muli base: procedures>+≡
    subroutine page_ring_pop_logical (this, l)
        class(page_ring_t), intent(inout) :: this
        logical, intent(out) :: l
        character(1) :: lc
        call this%pop (lc)
        do while (scan (lc,"tTfF") == 0)
            call this%pop (lc)
        end do
        read (lc, "(L1)") l
    end subroutine page_ring_pop_logical

<Muli base: page ring: TBP>+≡
    procedure, private :: pop_real => page_ring_pop_real

<Muli base: procedures>+≡
    subroutine page_ring_pop_real (this, def, skip)
        class(page_ring_t), intent(inout) :: this
        real(default), intent(out) :: def
        logical, optional, intent(in) :: skip
        integer(dik) :: d, f, e

```

```

call this%pop (d)
if (d == i_zero) then
    def = zero
else
    call this%pop (f)
    call this%pop (e)
    def = set_exponent (scale (real(f, kind=default), -d), e)
end if
if (present (skip)) then
    if (.not. skip) call this%proceed (-i_one)
end if
end subroutine page_ring_pop_real

```

<Muli base: page ring: TBP>+≡
 procedure, private :: pop_real_array => page_ring_pop_real_array

<Muli base: procedures>+≡
 subroutine page_ring_pop_real_array (this, def, skip)
 class(page_ring_t), intent(inout) :: this
 real(default), dimension(:), intent(out) :: def
 logical, optional, intent(in) :: skip
 integer(dik) :: n
 call this%pop_real (def(1))
 do n = 2, size(def)
 call this%pop_real (def(n))
 end do
 if (present(skip)) then
 if (.not. skip) call this%proceed (-i_one)
 end if
end subroutine page_ring_pop_real_array

<Muli base: page ring: TBP>+≡
 procedure :: close => page_ring_close

<Muli base: procedures>+≡
 subroutine page_ring_close (this)
 class(page_ring_t), intent(inout) :: this
 if (this%action == 1) then
 call this%flush ()
 ! call this%print_position()
 if (this%asynchronous) then
 write (this%unit, asynchronous="yes") &
 this%ring (this%actual_index()) (:this%actual_offset() - 1)
 else
 write (this%unit, asynchronous="no") &
 this%ring (this%actual_index()) (:this%actual_offset() - 1)
 end if
 end if
 close (this%unit)
end subroutine page_ring_close

<Muli base: page ring: TBP>+≡
 procedure :: ring_index => page_ring_ring_index

```

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_ring_index (this, n)
        class(page_ring_t), intent(in) :: this
        integer(dik), intent(in) :: n
        page_ring_ring_index = mod(n, this%ring_size)
    end function page_ring_ring_index

<Muli base: page ring: TBP>+≡
    procedure, private :: activate_next_page => page_ring_activate_next_page

<Muli base: procedures>+≡
    subroutine page_ring_activate_next_page (this)
        class(page_ring_t), intent(inout) :: this
        if (this%active_pages(2) - this%active_pages(1) + 1 >= &
            this%ring_size) call this%enlarge
        this%active_pages(2) = this%active_pages(2) + 1
    end subroutine page_ring_activate_next_page

<Muli base: page ring: TBP>+≡
    procedure, private :: enlarge => page_ring_enlarge

<Muli base: procedures>+≡
    subroutine page_ring_enlarge (this)
        class(page_ring_t), intent(inout) :: this
        character(serialize_page_size), dimension(:), allocatable :: tmp_ring
        integer(dik) :: n
        call move_alloc (this%ring, tmp_ring)
        allocate (this%ring(0:this%ring_size*2-1))
        do n = this%active_pages(1), this%active_pages(2)
            this%ring (mod(n,this%ring_size*2)) = tmp_ring (mod(n,this%ring_size))
        end do
        this%ring_size = this%ring_size * 2
    end subroutine page_ring_enlarge

```

These are specific implementations of generic procedures:

```

<Muli base: page ring: TBP>+≡
    procedure, private :: actual_index => page_ring_actual_index

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_actual_index (this)
        class(page_ring_t), intent(in) :: this
        page_ring_actual_index = &
            mod (this%position_stack%position(1), this%ring_size)
    end function page_ring_actual_index

<Muli base: page ring: TBP>+≡
    procedure, private :: actual_page => page_ring_actual_page

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_actual_page (this)
        class(page_ring_t), intent(in) :: this
        page_ring_actual_page = this%position_stack%position(1)
    end function page_ring_actual_page

```

```

<Muli base: page ring: TBP>+≡
    procedure, private :: actual_offset => page_ring_actual_offset

<Muli base: procedures>+≡
    elemental integer(kind=dik) function page_ring_actual_offset(this)
        class(page_ring_t), intent(in) :: this
        page_ring_actual_offset=this%position_stack%position(2)
    end function page_ring_actual_offset

<Muli base: page ring: TBP>+≡
    procedure, private :: actual_position => page_ring_actual_position

<Muli base: procedures>+≡
    pure function page_ring_actual_position(this)
        class(page_ring_t), intent(in) :: this
        integer(dik), dimension(2) :: page_ring_actual_position
        page_ring_actual_position = this%position_stack%position
    end function page_ring_actual_position

<Muli base: page ring: TBP>+≡
    procedure, private :: first_index => page_ring_first_index

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_first_index (this)
        class(page_ring_t), intent(in) :: this
        page_ring_first_index = mod(this%active_pages(1), this%ring_size)
    end function page_ring_first_index

<Muli base: page ring: TBP>+≡
    procedure, private :: first_page => page_ring_first_page

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_first_page (this)
        class(page_ring_t), intent(in) :: this
        page_ring_first_page = this%active_pages(1)
    end function page_ring_first_page

<Muli base: page ring: TBP>+≡
    procedure, private :: last_index => page_ring_last_index

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_last_index (this)
        class(page_ring_t), intent(in) :: this
        page_ring_last_index = mod(this%active_pages(2), this%ring_size)
    end function page_ring_last_index

<Muli base: page ring: TBP>+≡
    procedure, private :: last_page => page_ring_last_page

<Muli base: procedures>+≡
    elemental integer(dik) function page_ring_last_page (this)
        class(page_ring_t), intent(in) :: this
        page_ring_last_page = this%active_pages(2)
    end function page_ring_last_page

```

```

<Muli base: public>+≡
    public :: marker_t

<Muli base: types>+≡
    type, extends (page_ring_t) :: marker_t
        private
            integer(dik) :: indentation=0
            integer(dik) :: n_instances=0
            logical :: do_break=.true.
            logical :: do_indent=.false.
            class(serializable_ref_type),pointer :: heap=>null()
            class(serializable_ref_type),pointer :: references=>null()
        contains
            <Muli base: marker: TBP>
        end type marker_t

<Muli base: marker: TBP>≡
    procedure :: mark_begin => marker_mark_begin

<Muli base: procedures>+≡
    subroutine marker_mark_begin (this, tag, type, name, target, pointer, shape)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: tag
        character(*), intent(in), optional :: type, name
        integer(kind=dik), intent(in), optional :: target, pointer
        integer,intent(in), dimension(:), optional :: shape
        call this%indent ()
        call this%push ("<")
        call this%push (tag)
        if (present (type)) call this%push (' type="//type//"')
        if (present (name)) call this%push (' name="//name//"')
        if (present (target)) then
            call this%push (' target="')
            call this%push (target)
            call this%push ('"')
        end if
        if (present (pointer))then
            call this%push (' pointer="')
            call this%push (pointer)
            call this%push ('"')
        end if
        if (present (shape))then
            call this%push (' shape="')
            call this%push (shape)
            call this%push ('"')
        end if
        call this%push (">")
        this%indentation = this%indentation + 1
    end subroutine marker_mark_begin

<Muli base: marker: TBP>+≡
    procedure :: mark_instance_begin => marker_mark_instance_begin

```

```

<Muli base: procedures>+≡
  subroutine marker_mark_instance_begin &
    (this, ser, name, target, pointer, shape)
    class(marker_t), intent(inout) :: this
    class(ser_class_t), intent(in) :: ser
    character(*), intent(in) :: name
    integer(dik), intent(in), optional :: target, pointer
    integer, dimension(:), intent(in), optional :: shape
    character(:), allocatable :: this_type
    call ser%get_type (this_type)
    call this%mark_begin ("ser", this_type, name, target, pointer, shape)
  end subroutine marker_mark_instance_begin

<Muli base: marker: TBP>+≡
  procedure :: mark_end => marker_mark_end

<Muli base: procedures>+≡
  subroutine marker_mark_end (this, tag)
    class(marker_t), intent(inout) :: this
    character(*), intent(in), optional :: tag
    this%indentation = this%indentation - 1
    call this%indent ()
    if (present (tag)) then
      call this%push ("</"//tag//">")
    else
      call this%push ("</ser>")
    end if
  end subroutine marker_mark_end

<Muli base: marker: TBP>+≡
  procedure :: mark_instance_end => marker_mark_instance_end

<Muli base: procedures>+≡
  subroutine marker_mark_instance_end (this)
    class(marker_t), intent(inout) :: this
    call this%mark_end ("ser")
  end subroutine marker_mark_instance_end

<Muli base: marker: TBP>+≡
  generic :: mark => mark_logical, &
    mark_integer, mark_integer_array, mark_integer_matrix, &
    mark_integer_dik, mark_integer_array_dik, mark_integer_matrix_dik, &
    mark_default, mark_default_array, mark_default_matrix, mark_string
  procedure, private :: mark_logical => marker_mark_logical

<Muli base: procedures>+≡
  subroutine marker_mark_logical (this, name, content)
    class(marker_t), intent(inout) :: this
    character(*), intent(in) :: name
    logical, intent(in) :: content
    call this%indent ()
    call this%push ("</"//name//">")
    if (content) then
      call this%push ("T")
    end if
  end subroutine marker_mark_logical

```

```

        else
            call this%push ("F")
        end if
        call this%push ("< //"//name//">")
    end subroutine marker_mark_logical

    <Muli base: marker: TBP>+≡
        procedure :: mark_integer => marker_mark_integer

    <Muli base: procedures>+≡
        subroutine marker_mark_integer (this, name, content)
            class(marker_t), intent(inout) :: this
            character(*), intent(in) :: name
            integer, intent(in) :: content
            call this%indent ()
            call this%push ("< //"//name//">")
            call this%push (content)
            call this%push ("< //"//name//">")
        end subroutine marker_mark_integer

    <Muli base: marker: TBP>+≡
        procedure :: mark_integer_array => marker_mark_integer_array

    <Muli base: procedures>+≡
        subroutine marker_mark_integer_array (this, name, content)
            class(marker_t), intent(inout) :: this
            character(*), intent(in) :: name
            integer, dimension(:), intent(in) :: content
            call this%indent ()
            call this%push ("< //"//name//">")
            call this%push (content)
            call this%push ("< //"//name//">")
        end subroutine marker_mark_integer_array

    <Muli base: marker: TBP>+≡
        procedure :: mark_integer_matrix => marker_mark_integer_matrix

    <Muli base: procedures>+≡
        subroutine marker_mark_integer_matrix (this, name, content)
            class(marker_t), intent(inout) :: this
            character(*), intent(in) :: name
            integer, dimension(:,:), intent(in) :: content
            integer :: n
            integer, dimension(2) :: s
            s= shape(content)
            call this%indent ()
            call this%push ("< //"//name//">")
            do n = 1, s(2)
                call this%push (content(:,n))
                call this%push (" ")
            end do
            call this%push ("< //"//name//">")
        end subroutine marker_mark_integer_matrix

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_integer_dik => marker_mark_integer_dik

<Muli base: procedures>+≡
    subroutine marker_mark_integer_dik (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), intent(in) :: content
        call this%indent ()
        call this%push ("<"//name//">")
        call this%push (content)
        call this%push ("</"//name//">")
    end subroutine marker_mark_integer_dik

<Muli base: marker: TBP>+≡
    procedure :: mark_integer_array_dik => marker_mark_integer_array_dik

<Muli base: procedures>+≡
    subroutine marker_mark_integer_array_dik (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), dimension(:), intent(in) :: content
        call this%indent ()
        call this%push ("<"//name//">")
        call this%push (content)
        call this%push ("</"//name//">")
    end subroutine marker_mark_integer_array_dik

<Muli base: marker: TBP>+≡
    procedure :: mark_integer_matrix_dik => marker_mark_integer_matrix_dik

<Muli base: procedures>+≡
    subroutine marker_mark_integer_matrix_dik (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), dimension(:, :), intent(in) :: content
        integer :: n
        integer, dimension(2) :: s
        call this%indent ()
        call this%push ("<"//name//">")
        do n = 1, s(2)
            call this%push (content(:,n))
            call this%push (" ")
        end do
        call this%push ("</"//name//">")
    end subroutine marker_mark_integer_matrix_dik

<Muli base: marker: TBP>+≡
    procedure :: mark_default => marker_mark_default

<Muli base: procedures>+≡
    subroutine marker_mark_default (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name

```



```

    real(default), intent(in) :: content
    call this%indent ()
    call this%push ("<("//name//">")
    call this%push (content)
    call this%push ("<("//name//">")
end subroutine marker_mark_default

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_default_array => marker_mark_default_array

```

```

<Muli base: procedures>+≡
    subroutine marker_mark_default_array (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        real(default), dimension(:), intent(in) :: content
        call this%indent ()
        call this%push ("<("//name//">")
        call this%push (content)
        call this%push ("<("//name//">")
    end subroutine marker_mark_default_array

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_default_matrix => marker_mark_default_matrix

```

```

<Muli base: procedures>+≡
    subroutine marker_mark_default_matrix (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        real(default), dimension(:,:), intent(in) :: content
        integer :: n
        integer, dimension(2) :: s
        s = shape(content)
        call this%indent ()
        call this%push ("<("//name//">")
        do n = 1, s(2)
            call this%push (content(:,n))
            call this%push (" ")
        end do
        call this%push ("<("//name//">")
    end subroutine marker_mark_default_matrix

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_string => marker_mark_string

```

```

<Muli base: procedures>+≡
    subroutine marker_mark_string (this, name, content)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name, content
        call this%indent ()
        call this%push ("<("//name//">")
        call this%push (content)
        call this%push ("<("//name//">")
    end subroutine marker_mark_string

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_instance => marker_mark_instance

<Muli base: procedures>+≡
    recursive subroutine marker_mark_instance (this, ser, name, target, pointer)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), intent(in) :: ser
        character(len=*), intent(in) :: name
        integer(dik), intent(in), optional :: target, pointer
        integer(dik) :: status
        call this%mark_instance_begin (ser, name, target, pointer)
        call ser%write_to_marker (this, status)
        call this%mark_end ("ser")
    end subroutine marker_mark_instance

<Muli base: marker: TBP>+≡
    procedure :: mark_target => marker_mark_target

<Muli base: procedures>+≡
    recursive subroutine marker_mark_target (this, name, ser)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), target, intent(in) :: ser
        character(len=*), intent(in) :: name
        this%n_instances = this%n_instances + 1
        call this%push_heap (ser, this%n_instances)
        call this%mark_instance (ser, name, target = this%n_instances)
    end subroutine marker_mark_target

<Muli base: marker: TBP>+≡
    procedure :: mark_allocatable => marker_mark_allocatable

<Muli base: procedures>+≡
    subroutine marker_mark_allocatable (this, name, ser)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), allocatable, intent(in) :: ser
        character(len=*), intent(in) :: name
        if (allocated (ser)) then
            call this%mark_instance (ser, name)
        else
            call this%mark_null (name)
        end if
    end subroutine marker_mark_allocatable

<Muli base: marker: TBP>+≡
    procedure :: mark_pointer => marker_mark_pointer

<Muli base: procedures>+≡
    recursive subroutine marker_mark_pointer (this, name, ser)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), pointer, intent(in) :: ser
        character(len=*), intent(in) :: name
        character(:), allocatable :: type
        integer(dik) :: p
        if (associated (ser)) then

```

```

    call this%search_heap (ser, p)
    if (p > 0) then
        call ser%get_type (type)
        call this%push ('<ser type="')
        call this%push (type)
        call this%push ('" name="')
        call this%push (name)
        call this%push ('" pointer="')
        call this%push (p)
        call this%push ('"/>')
    else
        call this%mark_target (name, ser)
    end if
else
    call this%mark_null (name)
end if
end subroutine marker_mark_pointer

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_null => marker_mark_null

```

```

<Muli base: procedures>+≡
    subroutine marker_mark_null (this, name)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        call this%indent ()
        call this%push ('<ser type="null" name="')
        call this%push (name)
        call this%push ('"/>')
    end subroutine marker_mark_null

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_nothing => marker_mark_nothing

```

```

<Muli base: procedures>+≡
    subroutine marker_mark_nothing (this, name)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        call this%indent ()
        call this%push ('<')
        call this%push (name)
        call this%push ('/>')
    end subroutine marker_mark_nothing

```

```

<Muli base: marker: TBP>+≡
    procedure :: mark_empty => marker_mark_empty

```

```

<Muli base: procedures>+≡
    subroutine marker_mark_empty (this, tag, type, name, target, pointer, shape)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: tag
        character(*), intent(in), optional :: type, name
        integer(dik), intent(in), optional :: target, pointer
        integer, dimension(:), intent(in), optional :: shape
    end subroutine marker_mark_empty

```

```

call this%push("<")
call this%push(tag)
if (present (type)) call this%push (' type="//type//"')
if (present (name)) call this%push (' name="//name//"')
if (present (target)) then
    call this%push (' target="')
    call this%push (target)
    call this%push ('"')
end if
if (present (pointer)) then
    call this%push (' pointer="')
    call this%push (pointer)
    call this%push ('"')
end if
if (present (shape)) then
    call this%push (' shape="')
    call this%push (shape)
    call this%push ('"')
end if
call this%push(">")
end subroutine marker_mark_empty

```

(Multi base: marker: TBP)+≡

```

procedure :: pick_begin => marker_pick_begin

```

(Multi base: procedures)+≡

```

subroutine marker_pick_begin (this, tag, type, name, target, &
    pointer, shape, status)
    class(marker_t), intent(inout) :: this
    character(*), intent(in) :: tag
    integer(dik), dimension(2,2), intent(out), optional :: type, name
    integer(dik), intent(out), optional :: target, pointer
    integer, dimension(:), allocatable, optional, intent(out) :: shape
    integer(dik), intent(out) :: status
    integer(dik), dimension(2) :: p1, p2, p3
    integer(dik) :: l
    call this%find("<", skip=4, proceed=.true., pos=p1)
    call this%find(">", skip=1, proceed=.false., pos=p2)
    p3 = this%find_pure (" ", p1, p2, skip=1)
    if (p3(2) > 0) then
        if (this%substring(p1, p3) == tag) then
            status = serialize_ok
            if (present (type)) then
                call this%substring_by_keys &
                    ('type="','"', p3, p2, .false., 1, type)
                if (l <= 0) then
                    call msg_error ("marker_pick_begin: No type found")
                    status = serialize_wrong_type
                end if
            end if
            if (present (name)) then
                call this%substring_by_keys &
                    ('name="','"', p3, p2, .false., 1, name)
                if (l <= 0) then

```

```

        call msg_error ("marker_pick_begin: No name found")
        status = serialize_wrong_name
        call this%print_position ()
        stop
    end if
end if
if (present (target)) then
    p1 = this%find_pure ('target=', p3, p2, 4)
    if (p1(2) > 0) then
        call this%set_position (p1)
        call this%pop (target)
    else
        target = -1
        status = serialize_ok
    end if
end if
if (present (pointer)) then
    p1=this%find_pure ('pointer=', p3, p2, 4)
    if (p1(2) > 0)then
        call this%set_position (p1)
        call this%pop (pointer)
    else
        pointer = -1
        status = serialize_ok
    end if
end if
if (present (shape)) then
    p1 = this%find_pure ('shape=', p3, p2, 4)
    if (p1(2) > 0) then
        call this%set_position (p1)
        call this%pop (shape)
    else
        status = serialize_ok
    end if
end if
else
    call msg_error ("marker_pick_begin: Wrong tag. Expected: " // &
        tag // " Found: " // this%substring(p1, p3))
    status = serialize_wrong_tag
    call this%print_position ()
end if
else
    if (this%substring(p1, p2) == tag) then
        status = serialize_ok
    else
        call msg_error ("marker_pick_begin: Wrong tag. Expected: " // &
            tag // " Found: " // this%substring(p1, p2))
        status = serialize_wrong_tag
    end if
end if
call this%set_position (p2)
call this%proceed (i_one*2, .true.)
end subroutine marker_pick_begin

```

```

<Muli base: marker: TBP>+≡
    procedure :: query_instance_begin => marker_query_instance_begin

<Muli base: procedures>+≡
    subroutine marker_query_instance_begin &
        (this, type, name, target, pointer, shape, status)
        class(marker_t), intent(inout) :: this
        integer(dik), dimension(2,2), intent(out), optional :: type, name
        integer(dik), intent(out), optional :: target, pointer
        integer, dimension(:), allocatable, intent(out), optional :: shape
        integer(dik), intent(out) :: status
        call this%pick_begin ("ser", type, name, target, pointer, shape, status)
    end subroutine marker_query_instance_begin

<Muli base: marker: TBP>+≡
    procedure :: pick_instance_begin => marker_pick_instance_begin

<Muli base: procedures>+≡
    subroutine marker_pick_instance_begin &
        (this, name, type, target, pointer, shape, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), dimension(2,2), intent(out), optional :: type
        integer(dik), intent(out), optional :: target, pointer
        integer, dimension(:), allocatable, intent(out), optional :: shape
        integer(dik), intent(out) :: status
        integer(dik), dimension(2,2) :: read_name
        call this%query_instance_begin &
            (type, read_name, target, pointer, shape, status)
        if (status == serialize_ok) then
            if (.not. this%str_equal (name, read_name)) &
                status = serialize_wrong_name
        end if
    end subroutine marker_pick_instance_begin

<Muli base: marker: TBP>+≡
    procedure :: pick_end => marker_pick_end

<Muli base: procedures>+≡
    subroutine marker_pick_end (this, tag, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: tag
        integer(dik), intent(out) :: status
        integer(dik), dimension(2) :: p1, p2
        call this%find ("

```

```

        call this%proceed (i_one*2, .true.)
    end subroutine marker_pick_end

```

```

<Muli base: marker: TBP>+≡
    procedure :: pick_instance_end => marker_pick_instance_end

```

```

<Muli base: procedures>+≡
    subroutine marker_pick_instance_end (this, status)
        class(marker_t), intent(inout) :: this
        integer(dik), intent(out) :: status
        call this%pick_end ("ser", status)
    end subroutine marker_pick_instance_end

```

```

<Muli base: marker: TBP>+≡
    procedure :: pick_instance => marker_pick_instance

```

```

<Muli base: procedures>+≡
    subroutine marker_pick_instance (this, name, ser, status)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), intent(out) :: ser
        character(*), intent(in) :: name
        integer(dik), intent(out) :: status
        integer(dik), dimension(2,2) :: type, r_name
        call this%pick_begin ("ser", type, r_name, status=status)
        if (status == serialize_ok) then
            if (ser%verify_type (this%substring(type))) then
                if (this%str_equal (name, r_name)) then
                    call ser%read_from_marker (this, status)
                    call this%pick_end ("ser", status)
                else
                    call msg_error ("marker_pick_instance: Name mismatch")
                    write (*,*) "Expected: ", name, " Found: ", r_name
                    status = serialize_wrong_name
                    call this%print_position
                end if
            else
                call msg_error ("marker_pick_instance: Type mismatch: ")
                write (*,*) type
                call ser%write_type (output_unit)
                write (*,*)
                status = serialize_wrong_type
                call this%print_position
            end if
        end if
    end subroutine marker_pick_instance

```

```

<Muli base: marker: TBP>+≡
    procedure :: pick_target => marker_pick_target

```

```

<Muli base: procedures>+≡
    subroutine marker_pick_target (this, name, ser, status)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), target, intent(out) :: ser
        character(*), intent(in) :: name

```

```

integer(dik), intent(out) :: status
integer(dik), dimension(2,2) :: type, r_name
integer(dik) :: target
call this%pick_begin ("ser", type, r_name, target, status=status)
if (status == serialize_ok) then
  if (ser%verify_type (this%substring(type))) then
    if (this%str_equal (name, r_name)) then
      call ser%read_target_from_marker (this, status)
      if (target > 0) call this%push_heap (ser, target)
    else
      call msg_error ("marker_pick_instance: Name mismatch: ")
      write (*,*) "Expected: ", name, " Found: ", r_name
      status = serialize_wrong_name
    end if
  else
    call msg_error ("marker_pick_instance: Type mismatch: ")
    write (*,*) type
    status = serialize_wrong_type
  end if
end if
call this%pick_end ("ser", status)
end subroutine marker_pick_target

```

<Muli base: marker: TBP>+≡

```

procedure :: pick_allocatable => marker_pick_allocatable

```

<Muli base: procedures>+≡

```

subroutine marker_pick_allocatable (this, name, ser)
  class(marker_t), intent(inout) :: this
  character(*), intent(in) :: name
  class(ser_class_t), allocatable, intent(out) :: ser
  class(ser_class_t), pointer :: ref
  integer(dik), dimension(2,2) :: type, r_name
  integer(dik) :: status
  call this%pick_begin ("ser", type, r_name, status=status)
  if (status == serialize_ok) then
    if (ser%verify_type (this%substring(type))) then
      if (this%str_equal (name, r_name)) then
        call this%search_reference (type, ref)
        if (associated (ref)) then
          allocate (ser, source=ref)
          call ser%read_from_marker (this, status)
        else
          call msg_error ("marker_pick_allocatable:")
          write (*,*) "Type ", type, " not found on reference stack."
        end if
      else
        call msg_error ("marker_pick_instance: Name mismatch: ")
        write (*,*) "Expected: ", name, " Found: ", r_name
        status = serialize_wrong_name
      end if
    else
      call msg_error ("marker_pick_instance: Type mismatch: ")
      write (*,*) type
    end if
  end if
end subroutine marker_pick_allocatable

```



```

        status = serialize_wrong_type
    end if
end if
call this%pick_end ("ser", status)
end subroutine marker_pick_allocatable

```

<Muli base: marker: TBP>+≡

```

procedure :: pick_pointer => marker_pick_pointer

```

<Muli base: procedures>+≡

```

recursive subroutine marker_pick_pointer (this, name, ser)
    class(marker_t), intent(inout) :: this
    character(*), intent(in) :: name
    class(ser_class_t), pointer, intent(out) :: ser
    class(ser_class_t), pointer :: ref
    integer(dik), dimension(2,2) :: type, r_name
    integer(dik) :: status, t, p
    nullify (ser)
    call this%pick_begin &
        ("ser", type, r_name, target=t, pointer=p, status=status)
    if (status == serialize_ok) then
        if (.not. this%str_equal ("null",type)) then
            if (p > 0) then
                call this%search_heap (p, ser)
            else
                call this%search_reference (type, ref)
                if (associated (ref))then
                    allocate (ser, source=ref)
                    call ser%read_target_from_marker (this, status)
                    call this%pick_end ("ser", status)
                    if (t > 0) call this%push_heap (ser, t)
                else
                    write (*,*) "marker_pick_pointer:&
                        & Type ",type," not found on reference stack."
                end if
            end if
        end if
    end if
end if
end subroutine marker_pick_pointer

```

<Muli base: marker: TBP>+≡

```

generic :: pick => pick_logical, &
    pick_integer, pick_integer_array, pick_integer_matrix, &
    pick_integer_dik, pick_integer_array_dik, pick_integer_matrix_dik, &
    pick_default, pick_default_array, pick_default_matrix, pick_string
procedure :: pick_logical => marker_pick_logical

```

<Muli base: procedures>+≡

```

subroutine marker_pick_logical (this, name, content, status)
    class(marker_t), intent(inout) :: this
    character(*), intent(in) :: name
    logical, intent(out) :: content
    integer(dik), intent(out) :: status
    call this%pick_begin (name, status=status)

```

```

        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name, status)
        end if
    end subroutine marker_pick_logical

<Muli base: marker: TBP>+≡
    procedure :: pick_integer => marker_pick_integer

<Muli base: procedures>+≡
    subroutine marker_pick_integer (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer, intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name, status)
        end if
    end subroutine marker_pick_integer

<Muli base: marker: TBP>+≡
    procedure :: pick_integer_array => marker_pick_integer_array

<Muli base: procedures>+≡
    subroutine marker_pick_integer_array (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer, dimension(:), intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name, status)
        end if
    end subroutine marker_pick_integer_array

<Muli base: marker: TBP>+≡
    procedure :: pick_integer_matrix => marker_pick_integer_matrix

<Muli base: procedures>+≡
    subroutine marker_pick_integer_matrix (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer, dimension(:,:), intent(out) :: content
        integer(dik), intent(out) :: status
        integer :: n
        integer, dimension(2) :: s
        s = shape(content)
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            do n = 1, s(2)
                call this%pop (content(:,n))
            end do
        end if
    end subroutine marker_pick_integer_matrix

```

```

        end do
        call this%pick_end (name, status)
    end if
end subroutine marker_pick_integer_matrix

<Muli base: marker: TBP>+≡
    procedure :: pick_integer_dik => marker_pick_integer_dik

<Muli base: procedures>+≡
    subroutine marker_pick_integer_dik (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name,status)
        end if
    end subroutine marker_pick_integer_dik

<Muli base: marker: TBP>+≡
    procedure :: pick_integer_array_dik => marker_pick_integer_array_dik

<Muli base: procedures>+≡
    subroutine marker_pick_integer_array_dik (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), dimension(:), intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name, status)
        end if
    end subroutine marker_pick_integer_array_dik

<Muli base: marker: TBP>+≡
    procedure :: pick_integer_matrix_dik => marker_pick_integer_matrix_dik

<Muli base: procedures>+≡
    subroutine marker_pick_integer_matrix_dik (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), dimension(:,:), intent(out) :: content
        integer(dik), intent(out) :: status
        integer :: n
        integer, dimension(2) :: s
        s = shape(content)
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            do n = 1, s(2)
                call this%pop (content(:,n))
            end do
        end if
    end subroutine marker_pick_integer_matrix_dik

```

```

        call this%pick_end (name,status)
    end if
end subroutine marker_pick_integer_matrix_dik

<Muli base: marker: TBP>+≡
    procedure :: pick_default => marker_pick_default

<Muli base: procedures>+≡
    subroutine marker_pick_default (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        real(default), intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name,status)
        end if
    end subroutine marker_pick_default

<Muli base: marker: TBP>+≡
    procedure :: pick_default_array => marker_pick_default_array

<Muli base: procedures>+≡
    subroutine marker_pick_default_array (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        real(default), dimension(:), intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name, status)
        end if
    end subroutine marker_pick_default_array

<Muli base: marker: TBP>+≡
    procedure :: pick_default_matrix => marker_pick_default_matrix

<Muli base: procedures>+≡
    subroutine marker_pick_default_matrix (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        real(default), dimension(:,:), intent(out) :: content
        integer(dik), intent(out) :: status
        integer :: n
        integer, dimension(2) :: s
        s = shape(content)
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            do n = 1, s(2)
                call this%pop (content(:,n))
            end do
            call this%pick_end (name,status)
        end if
    end subroutine marker_pick_default_matrix

```

```

        end if
    end subroutine marker_pick_default_matrix

    <Muli base: marker: TBP>+≡
    procedure :: pick_string => marker_pick_string

    <Muli base: procedures>+≡
    subroutine marker_pick_string (this, name, content, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        character(:), allocatable, intent(out) :: content
        integer(dik), intent(out) :: status
        call this%pick_begin (name, status=status)
        if (status == serialize_ok) then
            call this%pop (content)
            call this%pick_end (name, status)
        end if
    end subroutine marker_pick_string

    <Muli base: marker: TBP>+≡
    procedure :: verify_nothing => marker_verify_nothing

    <Muli base: procedures>+≡
    subroutine marker_verify_nothing (this, name, status)
        class(marker_t), intent(inout) :: this
        character(*), intent(in) :: name
        integer(dik), intent(out) :: status
        integer(dik), dimension(2) :: p1, p2
        call this%find ("<", skip=4, proceed=.false., pos=p1)
        call this%find (">", 1, .false., p2)
        if (name//"/" == this%substring(p1, p2)) then
            status = serialize_nothing
            call this%set_position (p2)
            call this%proceed (i_one*3, .true.)
        else
            if (name == this%substring(p1, p2)) then
                status = serialize_ok
            else
                status = serialize_wrong_tag
            end if
        end if
    end subroutine marker_verify_nothing

    <Muli base: marker: TBP>+≡
    procedure :: indent => marker_indent

    <Muli base: procedures>+≡
    subroutine marker_indent (this, step)
        class(marker_t), intent(inout) :: this
        integer(dik), optional :: step
        if (this%do_break) call this%push (new_line(" "))
        if (this%do_indent) then
            if (present(step)) this%indentation = this%indentation + step
            call this%push (repeat(" ", this%indentation))
        end if
    end subroutine marker_indent

```

```

        end if
        this%active_pages(1) = this%actual_page()
    end subroutine marker_indent

    <Muli base: marker: TBP>+≡
    procedure :: push_heap => marker_push_heap

    <Muli base: procedures>+≡
    subroutine marker_push_heap (this, ser, id)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), target, intent(in) :: ser
        integer(dik), intent(in) :: id
        class(serializable_ref_type), pointer :: new_ref
        allocate (new_ref)
        new_ref%next => this%heap
        new_ref%ref => ser
        new_ref%id = id
        this%heap => new_ref
    end subroutine marker_push_heap

    <Muli base: marker: TBP>+≡
    procedure :: pop_heap => marker_pop_heap

    <Muli base: procedures>+≡
    subroutine marker_pop_heap (this, ser)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), pointer, intent(out) :: ser
        class(serializable_ref_type), pointer :: old_ref
        if (associated (this%heap)) then
            old_ref => this%heap
            ser => old_ref%ref
            this%heap => this%heap%next
            deallocate (old_ref)
        else
            call msg_error ("marker_pop_heap: heap_stack is not associated.")
        end if
    end subroutine marker_pop_heap

    <Muli base: marker: TBP>+≡
    procedure :: push_reference => marker_push_reference

    <Muli base: procedures>+≡
    subroutine marker_push_reference (this, ser, id)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), target, intent(in) :: ser
        integer(kind=dik), intent(in), optional :: id
        class(serializable_ref_type), pointer :: new_ref
        allocate (new_ref)
        new_ref%next => this%references
        new_ref%ref => ser
        if (present(id)) then
            new_ref%id = id
        else
            new_ref%id = -1
        end if
    end subroutine marker_push_reference

```

```

        end if
        this%references => new_ref
    end subroutine marker_push_reference

<Muli base: marker: TBP>+≡
    procedure :: pop_reference => marker_pop_reference

<Muli base: procedures>+≡
    subroutine marker_pop_reference (this, ser)
        class(marker_t), intent(inout) :: this
        class(ser_class_t), pointer, intent(out) :: ser
        class(serializable_ref_type), pointer :: old_ref
        if (associated (this%references)) then
            old_ref => this%references
            ser => old_ref%ref
            this%references => this%references%next
            deallocate (old_ref)
        else
            call msg_error &
                ("marker_pop_reference: reference_stack is not associated.")
        end if
    end subroutine marker_pop_reference

<Muli base: marker: TBP>+≡
    procedure :: reset_references => marker_reset_references

<Muli base: procedures>+≡
    subroutine marker_reset_references (this)
        class(marker_t), intent(inout) :: this
        if (associated (this%references)) then
            call this%references%finalize ()
            deallocate (this%references)
        end if
    end subroutine marker_reset_references

<Muli base: marker: TBP>+≡
    procedure :: search_reference => marker_search_reference

<Muli base: procedures>+≡
    subroutine marker_search_reference (this, type, ser)
        class(marker_t), intent(in) :: this
        integer(dik), dimension(2,2), intent(in) :: type
        class(ser_class_t), pointer, intent(out) :: ser
        !!! !!! !!! NAG bug workaround
        class(ser_class_t), pointer :: tmp_ser
        class(serializable_ref_type), pointer :: ref
        ref => this%references
        nullify (ser)
        do while (associated (ref))
            tmp_ser => ref%ref
            if (tmp_ser%verify_type (this%substring(type))) then
                ser => tmp_ser
                exit
            end if
        end while
    end subroutine marker_search_reference

```

```

        ref => ref%next
    end do
end subroutine marker_search_reference

<Muli base: marker: TBP>+≡
    procedure :: reset_heap => marker_reset_heap

<Muli base: procedures>+≡
    subroutine marker_reset_heap (this)
        class(marker_t), intent(inout) :: this
        if (associated (this%heap)) then
            call this%heap%finalize ()
            deallocate (this%heap)
        end if
    end subroutine marker_reset_heap

<Muli base: marker: TBP>+≡
    procedure :: finalize => marker_finalize

<Muli base: procedures>+≡
    subroutine marker_finalize (this)
        class(marker_t), intent(inout) :: this
        call this%reset_heap ()
        call this%reset_references ()
    end subroutine marker_finalize

<Muli base: marker: TBP>+≡
    generic :: search_heap => search_heap_by_id, search_heap_by_ref
    procedure :: search_heap_by_id => marker_search_heap_by_id
    procedure :: search_heap_by_ref => marker_search_heap_by_ref

<Muli base: procedures>+≡
    subroutine marker_search_heap_by_ref (this, ref, id)
        class(marker_t), intent(in) :: this
        class(ser_class_t), pointer, intent(in) :: ref
        integer(dik), intent(out) :: id
        class(serializable_ref_type), pointer :: ref_p
        ref_p => this%heap
        id = 0
        do while (associated (ref_p))
            if (associated (ref, ref_p%ref)) then
                id = ref_p%id
                exit
            end if
            ref_p => ref_p%next
        end do
    end subroutine marker_search_heap_by_ref

<Muli base: procedures>+≡
    subroutine marker_search_heap_by_id (this, id, ser)
        class(marker_t), intent(in) :: this
        integer(dik), intent(in) :: id
        class(ser_class_t), pointer, intent(out) :: ser

```



```

class(serializable_ref_type), pointer :: ref
ref => this%heap
do while (associated (ref))
  if (id == ref%id) then
    ser => ref%ref
    exit
  end if
  ref => ref%next
end do
end subroutine marker_search_heap_by_id

```

<Muli base: procedures>+≡

```

elemental function measurable_less_measurable (mea1, mea2)
  class(measure_class_t), intent(in) :: mea1, mea2
  logical :: measurable_less_measurable
  measurable_less_measurable = mea1%measure() < mea2%measure()
end function measurable_less_measurable

```

<Muli base: procedures>+≡

```

elemental function measurable_less_default (mea1, def)
  class(measure_class_t), intent(in) :: mea1
  real(default), intent(in) :: def
  logical :: measurable_less_default
  measurable_less_default = mea1%measure() < def
end function measurable_less_default

```

<Muli base: procedures>+≡

```

elemental function measurable_less_or_equal_measurable (mea1, mea2)
  class(measure_class_t), intent(in) :: mea1, mea2
  logical :: measurable_less_or_equal_measurable
  measurable_less_or_equal_measurable = mea1%measure() <= mea2%measure()
end function measurable_less_or_equal_measurable

```

<Muli base: procedures>+≡

```

elemental function measurable_less_or_equal_default (mea1, def)
  class(measure_class_t), intent(in) :: mea1
  real(default), intent(in) :: def
  logical :: measurable_less_or_equal_default
  measurable_less_or_equal_default = mea1%measure() <= def
end function measurable_less_or_equal_default

```

<Muli base: procedures>+≡

```

elemental function measurable_equal_measurable (mea1, mea2)
  class(measure_class_t), intent(in) :: mea1, mea2
  logical :: measurable_equal_measurable
  measurable_equal_measurable = mea1%measure() == mea2%measure()
end function measurable_equal_measurable

```

<Muli base: procedures>+≡

```

elemental function measurable_equal_default (mea1, def)
  class(measure_class_t), intent(in) :: mea1

```

```

    real(default), intent(in) :: def
    logical :: measurable_equal_default
    measurable_equal_default = mea1%measure() == def
end function measurable_equal_default

```

```

<Muli base: procedures>+≡
elemental function measurable_equal_or_greater_measurable (mea1, mea2)
    class(measure_class_t), intent(in) :: mea1, mea2
    logical :: measurable_equal_or_greater_measurable
    measurable_equal_or_greater_measurable = mea1%measure() >= mea2%measure()
end function measurable_equal_or_greater_measurable

```

```

<Muli base: procedures>+≡
elemental function measurable_equal_or_greater_default (mea1, def)
    class(measure_class_t), intent(in) :: mea1
    real(default), intent(in) :: def
    logical :: measurable_equal_or_greater_default
    measurable_equal_or_greater_default = mea1%measure() >= def
end function measurable_equal_or_greater_default

```

```

<Muli base: procedures>+≡
elemental function measurable_greater_measurable (mea1, mea2)
    class(measure_class_t), intent(in) :: mea1, mea2
    logical :: measurable_greater_measurable
    measurable_greater_measurable = mea1%measure() > mea2%measure()
end function measurable_greater_measurable

```

```

<Muli base: procedures>+≡
elemental function measurable_greater_default (mea1, def)
    class(measure_class_t), intent(in) :: mea1
    real(default), intent(in) :: def
    logical :: measurable_greater_default
    measurable_greater_default = mea1%measure() > def
end function measurable_greater_default

```

```

<Muli base: procedures>+≡
pure function page_ring_position (n)
    integer(dik), intent(in) :: n
    integer(dik), dimension(2) :: page_ring_position
    page_ring_position(2) = mod(n, serialize_page_size)
    page_ring_position(1) = (n-page_ring_position(2)) / serialize_page_size
end function page_ring_position

```

```

<Muli base: procedures>+≡
pure integer(dik) function page_ring_ordinal (pos)
    integer(dik), dimension(2), intent(in) :: pos
    page_ring_ordinal = pos(1) * serialize_page_size + pos(2)
end function page_ring_ordinal

```

<Muli base: procedures>+≡

```

pure logical function page_ring_position_is_before_int_pos (m, n)
  integer(dik), intent(in) :: m
  integer(dik), dimension(2), intent(in) :: n
  if (m < page_ring_ordinal(n)) then
    page_ring_position_is_before_int_pos = .true.
  else
    page_ring_position_is_before_int_pos = .false.
  end if
end function page_ring_position_is_before_int_pos

```

<Muli base: procedures>+≡

```

pure logical function page_ring_position_is_before_pos_int (m, n)
  integer(dik), dimension(2), intent(in) :: m
  integer(dik), intent(in) :: n
  if (page_ring_ordinal(m) < n) then
    page_ring_position_is_before_pos_int = .true.
  else
    page_ring_position_is_before_pos_int = .false.
  end if
end function page_ring_position_is_before_pos_int

```

<Muli base: procedures>+≡

```

pure logical function page_ring_position_is_before_pos_pos (m, n)
  integer(dik), dimension(2), intent(in) :: m,n
  if (m(1) < n(1)) then
    page_ring_position_is_before_pos_pos = .true.
  else
    if (m(1) > n(1)) then
      page_ring_position_is_before_pos_pos = .false.
    else
      if (m(2) < n(2)) then
        page_ring_position_is_before_pos_pos = .true.
      else
        page_ring_position_is_before_pos_pos = .false.
      end if
    end if
  end if
end function page_ring_position_is_before_pos_pos

```

<Muli base: procedures>+≡

```

subroutine ring_position_increase (pos, n)
  integer(dik), dimension(2), intent(inout) :: pos
  integer(dik), intent(in) :: n
  pos = page_ring_position (page_ring_ordinal(pos) + n)
end subroutine ring_position_increase

```

<Muli base: procedures>+≡

```

pure integer(dik) function ring_position_metric1 (p)
  integer(dik), dimension(2,2), intent(in) :: p
  ring_position_metric1 = (p(1,2) - p(1,1)) * serialize_page_size + &
    p(2,2) - p(2,1) + 1

```

```

end function ring_position_metric1

pure integer(dik) function ring_position_metric2 (p1, p2)
    integer(dik), dimension(2), intent(in) :: p1, p2
    ring_position_metric2 = (p2(1) - p1(1)) * &
        serialize_page_size + p2(2) - p1(2) + 1
end function ring_position_metric2

<Muli base: public>+≡
    public :: generate_unit

<Muli base: procedures>+≡
    subroutine generate_unit (unit, min, max)
        integer, intent(out) :: unit
        integer, intent(in), optional :: min,max
        integer :: min_u, max_u
        logical :: is_open
        ! print *, "generate_unit"
        unit = -1
        if (present (min)) then
            min_u = min
        else
            min_u = 10
        end if
        if (present (max)) then
            max_u = max
        else
            max_u = huge (max_u)
        end if
        do unit = min_u, max_u
            !print *, "testing ", unit
            inquire (unit, opened = is_open)
            if (.not. is_open) then
                exit
            end if
        end do
    end subroutine generate_unit

<Muli base: public>+≡
    public :: ilog2

<Muli base: procedures>+≡
    subroutine ilog2 (int, exp, rem)
        integer, intent(in) :: int
        integer, intent(out) :: exp, rem
        integer :: count
        count = 2
        exp = 1
        do while (count < int)
            exp = exp + 1
            count = ishft(count, 1)
        end do
        if (count > int) then
            rem = (int - ishft(count, -1))

```

```

    else
        rem = 0
    end if
end subroutine ilog2

```

<Muli base: public>+≡

```

public :: integer_with_leading_zeros

```

<Muli base: procedures>+≡

```

subroutine integer_with_leading_zeros (number, length, string)
    integer, intent(in) :: number, length
    character(len=*), intent(out) :: string
    integer :: zeros
    character::sign
    if (number == 0) then
        string = repeat("0", length)
    else
        if (number > 0) then
            zeros = length - floor(log10 (real(number))) - 1
            if (zeros < 0) then
                string = repeat(" ", length)
            else
                write (string, fmt="(A,I0)") repeat("0", zeros), number
            end if
        else
            zeros = length - floor (log10 (real (-number))) - 2
            if (zeros < 0) then
                string = repeat(" ", length)
            else
                write (string, fmt="(A,A,I0)") "-", repeat("0", zeros), &
                    abs(number)
            end if
        end if
    end if
end subroutine integer_with_leading_zeros

```

<Muli base: procedures>+≡

```

pure logical function character_is_in (c, array)
    character, intent(in) :: c
    character, dimension(:), intent(in) :: array
    integer(dik) :: n
    character_is_in = .false.
    do n=1,size(array)
        if (c == array(n)) then
            character_is_in = .true.
            exit
        end if
    end do
end function character_is_in

```

21.2 Transverse momenta

This file contains the module `muli_momentum`. Its purpose is to store the actual value of the evolution parameter p_t^2 in a convenient way. We use the normalized value $p_t^2/p_{t,\max}^2$ for generating the next value of the scale, also need the square root of both p_t^2 and $p_t^2/p_{t,\max}^2$ for other purposes. That's why I store all four combinations together with $p_{t,\max}$ in an array.

```

<muli_momentum.f90>≡
  <File header>

  module muli_momentum

    <Use kinds>
      use constants
      use muli_base

    <Standard module head>

    <Muli mom: public>

    <Muli mom: types>

    <Muli mom: interfaces>

    contains

    <Muli mom: procedures>

  end module muli_momentum

<Muli mom: public>≡
  public :: transverse_mom_t

<Muli mom: types>≡
  type, extends (ser_class_t) :: transverse_mom_t
    private
      real(default), dimension(0:4) :: momentum = [0, 0, 0, 0, 0]
    contains
      <Muli mom: trans mom: TBP>
    end type transverse_mom_t

<Muli mom: trans mom: TBP>≡
  procedure :: mom_write_to_marker => transverse_mom_write_to_marker
  procedure :: write_to_marker => transverse_mom_write_to_marker

<Muli mom: procedures>≡
  subroutine transverse_mom_write_to_marker (this, marker, status)
    class(transverse_mom_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    call marker%mark_begin ("transverse_mom_t")
    call marker%mark ("gev_momenta", this%momentum(0:1))
    call marker%mark_end ("transverse_mom_t")
  end subroutine

```

```

end subroutine transverse_mom_write_to_marker

<Muli mom: trans mom: TBP>+≡
  procedure :: mom_read_from_marker => transverse_mom_read_from_marker
  procedure :: read_from_marker => transverse_mom_read_from_marker

<Muli mom: procedures>+≡
  subroutine transverse_mom_read_from_marker (this, marker, status)
    class(transverse_mom_t), intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    call marker%pick_begin ("transverse_mom_t", status=status)
    call marker%pick ("gev_momenta", this%momentum(0:1), status)
    this%momentum(2:4) = [ this%momentum(1)**2, &
                          this%momentum(1) / this%momentum(0), &
                          (this%momentum(1)/this%momentum(0))**2 ]
    call marker%pick_end ("transverse_mom_t", status=status)
  end subroutine transverse_mom_read_from_marker

<Muli mom: trans mom: TBP>+≡
  procedure :: mom_print_to_unit => transverse_mom_print_to_unit
  procedure :: print_to_unit => transverse_mom_print_to_unit

<Muli mom: procedures>+≡
  subroutine transverse_mom_print_to_unit &
    (this, unit, parents, components, peers)
    class(transverse_mom_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    write (unit, "(1x,A)") "Components of transverse_mom_t:"
    write (unit, "(3x,A)") "Actual energy scale:"
    write (unit, "(A,E20.10)") "Max scale (MeV)      :", this%momentum(0)
    write (unit, "(A,E20.10)") "Scale (MeV)       :", this%momentum(1)
    write (unit, "(A,E20.10)") "Scale^2 (MeV^2)    :", this%momentum(2)
    write (unit, "(A,E20.10)") "Scale normalized  :", this%momentum(3)
    write (unit, "(A,E20.10)") "Scale^2 normalized:", this%momentum(4)
  end subroutine transverse_mom_print_to_unit

<Muli mom: trans mom: TBP>+≡
  procedure, nopass :: get_type => transverse_mom_get_type

<Muli mom: procedures>+≡
  pure subroutine transverse_mom_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="transverse_mom_t")
  end subroutine transverse_mom_get_type

<Muli mom: trans mom: TBP>+≡
  procedure :: get_gev_initial_cme => transverse_mom_get_gev_initial_cme

<Muli mom: procedures>+≡
  elemental function transverse_mom_get_gev_initial_cme (this) result(scale)
    class(transverse_mom_t), intent(in) :: this
    real(default) :: scale

```

```

        scale = this%momentum(0) * 2D0
    end function transverse_mom_get_gev_initial_cme

<Muli mom: trans mom: TBP>+≡
    procedure :: get_gev_max_scale => transverse_mom_get_gev_max_scale

<Muli mom: procedures>+≡
    elemental function transverse_mom_get_gev_max_scale (this) result (scale)
        class(transverse_mom_t), intent(in) :: this
        real(default) :: scale
        scale = this%momentum(0)
    end function transverse_mom_get_gev_max_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: get_gev2_max_scale => transverse_mom_get_gev2_max_scale

<Muli mom: procedures>+≡
    elemental function transverse_mom_get_gev2_max_scale (this) result (scale)
        class(transverse_mom_t), intent(in) :: this
        real(default) :: scale
        scale = this%momentum(0)**2
    end function transverse_mom_get_gev2_max_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: get_gev_scale => transverse_mom_get_gev_scale

<Muli mom: procedures>+≡
    elemental function transverse_mom_get_gev_scale(this) result(scale)
        class(transverse_mom_t), intent(in) :: this
        real(default) :: scale
        scale = this%momentum(1)
    end function transverse_mom_get_gev_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: get_gev2_scale => transverse_mom_get_gev2_scale

<Muli mom: procedures>+≡
    elemental function transverse_mom_get_gev2_scale (this) result (scale)
        class(transverse_mom_t), intent(in) :: this
        real(default) :: scale
        scale = this%momentum(2)
    end function transverse_mom_get_gev2_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: get_unit_scale => transverse_mom_get_unit_scale

<Muli mom: procedures>+≡
    pure function transverse_mom_get_unit_scale (this) result (scale)
        class(transverse_mom_t), intent(in) :: this
        real(default) :: scale
        scale = this%momentum(3)
    end function transverse_mom_get_unit_scale

```



```

<Muli mom: trans mom: TBP>+≡
  procedure :: get_unit2_scale => transverse_mom_get_unit2_scale

<Muli mom: procedures>+≡
  pure function transverse_mom_get_unit2_scale (this) result (scale)
    class(transverse_mom_t), intent(in) :: this
    real(default) :: scale
    scale = this%momentum(4)
  end function transverse_mom_get_unit2_scale

<Muli mom: trans mom: TBP>+≡
  procedure :: set_gev_initial_cme => transverse_mom_set_gev_initial_cme

<Muli mom: procedures>+≡
  subroutine transverse_mom_set_gev_initial_cme (this, new_gev_initial_cme)
    class(transverse_mom_t), intent(inout) :: this
    real(default), intent(in) :: new_gev_initial_cme
    this%momentum(0) = new_gev_initial_cme / 2D0
    this%momentum(3) = this%momentum(1) / this%momentum(0)
    this%momentum(4) = this%momentum(3)**2
  end subroutine transverse_mom_set_gev_initial_cme

<Muli mom: trans mom: TBP>+≡
  procedure :: set_gev_max_scale => transverse_mom_set_gev_max_scale

<Muli mom: procedures>+≡
  subroutine transverse_mom_set_gev_max_scale (this, new_gev_max_scale)
    class(transverse_mom_t), intent(inout) :: this
    real(default), intent(in) :: new_gev_max_scale
    this%momentum(0) = new_gev_max_scale
    this%momentum(3) = this%momentum(1) / this%momentum(0)
    this%momentum(4) = this%momentum(3)**2
  end subroutine transverse_mom_set_gev_max_scale

<Muli mom: trans mom: TBP>+≡
  procedure :: set_gev2_max_scale => transverse_mom_set_gev2_max_scale

<Muli mom: procedures>+≡
  subroutine transverse_mom_set_gev2_max_scale (this, new_gev2_max_scale)
    class(transverse_mom_t), intent(inout) :: this
    real(default), intent(in) :: new_gev2_max_scale
    this%momentum(0) = sqrt (new_gev2_max_scale)
    this%momentum(3) = this%momentum(1) / this%momentum(0)
    this%momentum(4) = this%momentum(3)**2
  end subroutine transverse_mom_set_gev2_max_scale

<Muli mom: trans mom: TBP>+≡
  procedure :: set_gev_scale => transverse_mom_set_gev_scale

<Muli mom: procedures>+≡
  subroutine transverse_mom_set_gev_scale (this, new_gev_scale)
    class(transverse_mom_t), intent(inout) :: this
    real(default), intent(in) :: new_gev_scale
    this%momentum(1) = new_gev_scale

```

```

    this%momentum(2) = new_gev_scale**2
    this%momentum(3) = new_gev_scale / this%momentum(0)
    this%momentum(4) = this%momentum(3)**2
end subroutine transverse_mom_set_gev_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: set_gev2_scale => transverse_mom_set_gev2_scale

<Muli mom: procedures>+≡
    subroutine transverse_mom_set_gev2_scale (this, new_gev2_scale)
        class(transverse_mom_t), intent(inout) :: this
        real(default), intent(in) :: new_gev2_scale
        this%momentum(1) = sqrt (new_gev2_scale)
        this%momentum(2) = new_gev2_scale
        this%momentum(3) = this%momentum(1) / this%momentum(0)
        this%momentum(4) = this%momentum(3)**2
    end subroutine transverse_mom_set_gev2_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: set_unit_scale => transverse_mom_set_unit_scale

<Muli mom: procedures>+≡
    subroutine transverse_mom_set_unit_scale (this, new_unit_scale)
        class(transverse_mom_t), intent(inout)::this
        real(default), intent(in) :: new_unit_scale
        this%momentum(1) = new_unit_scale * this%momentum(0)
        this%momentum(2) = this%momentum(1)**2
        this%momentum(3) = new_unit_scale
        this%momentum(4) = this%momentum(3)**2
    end subroutine transverse_mom_set_unit_scale

<Muli mom: trans mom: TBP>+≡
    procedure :: set_unit2_scale => transverse_mom_set_unit2_scale

<Muli mom: procedures>+≡
    subroutine transverse_mom_set_unit2_scale (this, new_unit2_scale)
        class(transverse_mom_t), intent(inout)::this
        real(default), intent(in) :: new_unit2_scale
        this%momentum(3) = sqrt (new_unit2_scale)
        this%momentum(4) = new_unit2_scale
        this%momentum(1) = this%momentum(3) * this%momentum(0)
        this%momentum(2) = this%momentum(1)**2
    end subroutine transverse_mom_set_unit2_scale

<Muli mom: trans mom: TBP>+≡
    generic :: initialize => transverse_mom_initialize
    procedure :: transverse_mom_initialize

<Muli mom: procedures>+≡
    subroutine transverse_mom_initialize (this, gev2_s)
        class(transverse_mom_t), intent(out) :: this
        real(default), intent(in) :: gev2_s
        real(default) :: gev_s
        gev_s = sqrt (gev2_s)

```

```

        this%momentum = [gev_s/2, gev_s/2, gev2_s/4, one, one]
    end subroutine transverse_mom_initialize

<Muli mom: public>+≡
    public :: qcd_2_2_class

<Muli mom: types>+≡
    type, extends (transverse_mom_t), abstract :: qcd_2_2_class
    contains
        <Muli mom: QCD22: TBP>
    end type qcd_2_2_class

<Muli mom: QCD22: TBP>≡
    procedure(qcd_get_int), deferred :: get_process_id

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int), deferred :: get_integrand_id

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int), deferred :: get_diagram_kind

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int_4), deferred :: get_lha_flavors

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int_4), deferred :: get_pdg_flavors

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int_by_int), deferred :: get_parton_id

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int_2), deferred :: get_parton_kinds

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_int_2), deferred :: get_pdf_int_kinds

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_real), deferred :: get_momentum_boost

<Muli mom: QCD22: TBP>+≡
    ! procedure(qcd_get_real_3),deferred :: get_parton_in_momenta

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_real_2), deferred :: get_remnant_momentum_fractions

<Muli mom: QCD22: TBP>+≡
    procedure(qcd_get_real_2), deferred :: get_total_momentum_fractions

<Muli mom: interfaces>≡
    abstract interface
        subroutine qcd_none (this)
            import qcd_2_2_class
            class(qcd_2_2_class), target, intent(in) :: this
        end subroutine qcd_none
    end interface

```

```

<Muli mom: interfaces>+≡
! abstract interface
!   subroutine qcd_get_beam (this, beam)
!     import qcd_2_2_class
!     import pp_remnant_class
!     class(qcd_2_2_class),target, intent(in) :: this
!     class(pp_remnant_class),pointer, intent(out) :: beam
!   end subroutine qcd_get_beam
! end interface

<Muli mom: interfaces>+≡
abstract interface
  elemental function qcd_get_real (this)
    import
    class(qcd_2_2_class), intent(in) :: this
    real(default) :: qcd_get_real
  end function qcd_get_real
end interface

<Muli mom: interfaces>+≡
abstract interface
  pure function qcd_get_real_2 (this)
    import
    class(qcd_2_2_class), intent(in) :: this
    real(default), dimension(2) :: qcd_get_real_2
  end function qcd_get_real_2
end interface

<Muli mom: interfaces>+≡
abstract interface
  pure function qcd_get_real_3 (this)
    import
    class(qcd_2_2_class), intent(in) :: this
    real(default), dimension(3) :: qcd_get_real_3
  end function qcd_get_real_3
end interface

<Muli mom: interfaces>+≡
abstract interface
  elemental function qcd_get_int (this)
    import
    class(qcd_2_2_class), intent(in) :: this
    integer :: qcd_get_int
  end function qcd_get_int
end interface

<Muli mom: interfaces>+≡
abstract interface
  pure function qcd_get_int_by_int (this, n)
    import
    class(qcd_2_2_class), intent(in) :: this
    integer, intent(in) :: n
    integer :: qcd_get_int_by_int
  end function qcd_get_int_by_int
end interface

```

```

<Muli mom: interfaces>+≡
  abstract interface
    pure function qcd_get_int_2 (this)
      import
        class(qcd_2_2_class), intent(in) :: this
        integer, dimension(2) :: qcd_get_int_2
    end function qcd_get_int_2
  end interface

<Muli mom: interfaces>+≡
  abstract interface
    pure function qcd_get_int_4 (this)
      import
        class(qcd_2_2_class), intent(in) :: this
        integer, dimension(4) :: qcd_get_int_4
    end function qcd_get_int_4
  end interface

```

21.3 Multi parton interactions

This file contains the module `muli_interactions`. The allowed interactions and their cross sections are defined here. Additionally, some coordinate transformations which annihilate divergencies of the cross sections are defined. Since the phase space border is hyperbolic, this transformations are also hyperbolic. That's why all interactions are named `x_cart` for cartesian or `x_hyp` for hyperbolic to avoid confusion.

```

<muli_interactions.f90>≡
  <File header>

  module muli_interactions

    <Use kinds with double>
    use constants
    use muli_momentum

    <Standard module head>

    <Muli interactions: public>

    <Muli interactions: variables>

    <Muli interactions: interfaces>

    contains

    <Muli interactions: procedures>

  end module muli_interactions

<Muli interactions: variables>≡
  character(len=2), dimension(-6:6), parameter :: integer_parton_names = &

```

```

        ["-6", "-5", "-4", "-3", "-2", "-1", "00", &
         "+1", "+2", "+3", "+4", "+5", "+6" ]
character, dimension(-6:6), parameter :: traditional_parton_names = &
        ["T", "B", "C", "S", "U", "D", "g", "d", "u", "s", "c", "b", "t"]

```

These are the phase space coefficients of the polynomial mappings, the evolution variable is $pt2s/(x1*x2)$.

```

<Muli interactions: variables>+≡
real(default), dimension(1:4,1:5), parameter :: &
    phase_space_coefficients_in = reshape (source = &
        [ 6144, -4608, +384, 0, &
          6144, -5120, +384, 0, &
          6144, -2048, +128, -576, &
          13824, -9600, +1056, 0, &
          31104, -19872, +2160, +486 ], shape=[4,5])

<Muli interactions: variables>+≡
integer, parameter :: hadron_A_kind = 2212
integer, parameter :: hadron_B_kind = -2212
integer, dimension(4), parameter, public :: &
    parton_kind_of_int_kind = [1, 1, 2, 2]
real(default), parameter :: b_sigma_tot_all = 100 !mb PDG
real(default), parameter :: &
    b_sigma_tot_nd = 0.5*b_sigma_tot_all !!! PRD 49 n5 1994
real(default), parameter, public :: &
    gev_cme_tot = 14000 ! total center of mass energie
real(default), parameter :: gev2_cme_tot = gev_cme_tot**2 !!! s
real(default), parameter :: gev_pt_max = gev_cme_tot/2D0
real(default), parameter :: gev2_pt_max = gev2_cme_tot/4D0
!model parameters
real(default), parameter :: gev_pt_min = 8E-1_default
real(default), parameter :: gev2_pt_min = gev_pt_min**2
real(default), parameter :: pts_min = gev_pt_min / gev_pt_max
real(default), parameter :: pts2_min = gev2_pt_min / gev2_pt_max
real(default), parameter :: gev_p_t_0 = 2.0
real(default), parameter :: gev2_p_t_0 = gev_p_t_0**2
real(default), parameter :: norm_p_t_0 = gev_p_t_0 / gev_pt_max
real(default), parameter :: norm2_p_t_0 = gev2_p_t_0 / gev2_pt_max
!mathematical constants
real(default), parameter, public :: euler = exp(one)
!physical constants
real(default), parameter :: gev2_mbarn = 0.389379304_default
real(default), parameter :: const_pref = pi * gev2_mbarn / &
    (gev2_cme_tot * b_sigma_tot_nd)

```

```

<Muli interactions: variables>+≡
integer, parameter, public :: LHA_FLAVOR_AT = -6
integer, parameter, public :: LHA_FLAVOR_AB = -5
integer, parameter, public :: LHA_FLAVOR_AC = -4
integer, parameter, public :: LHA_FLAVOR_AS = -3
integer, parameter, public :: LHA_FLAVOR_AU = -2
integer, parameter, public :: LHA_FLAVOR_AD = -1
integer, parameter, public :: LHA_FLAVOR_G = 0
integer, parameter, public :: LHA_FLAVOR_D = 1

```

```

integer, parameter, public :: LHA_FLAVOR_U = 2
integer, parameter, public :: LHA_FLAVOR_S = 3
integer, parameter, public :: LHA_FLAVOR_C = 4
integer, parameter, public :: LHA_FLAVOR_B = 5
integer, parameter, public :: LHA_FLAVOR_T = 6

```

(Muli interactions: variables)+≡

```

integer, parameter, public :: PDG_FLAVOR_AT = -6
integer, parameter, public :: PDG_FLAVOR_AB = -5
integer, parameter, public :: PDG_FLAVOR_AC = -4
integer, parameter, public :: PDG_FLAVOR_AS = -3
integer, parameter, public :: PDG_FLAVOR_AU = -2
integer, parameter, public :: PDG_FLAVOR_AD = -1
integer, parameter, public :: PDG_FLAVOR_G = 21
integer, parameter, public :: PDG_FLAVOR_D = 1
integer, parameter, public :: PDG_FLAVOR_U = 2
integer, parameter, public :: PDG_FLAVOR_S = 3
integer, parameter, public :: PDG_FLAVOR_C = 4
integer, parameter, public :: PDG_FLAVOR_B = 5
integer, parameter, public :: PDG_FLAVOR_T = 6

```

(Muli interactions: variables)+≡

```

integer, parameter, public :: PARTON_SEA = 1
integer, parameter, public :: PARTON_VALENCE = 2
integer, parameter, public :: PARTON_SEA_AND_VALENCE = 3
integer, parameter, public :: PARTON_TWIN = 4
integer, parameter, public :: PARTON_SEA_AND_TWIN = 5
integer, parameter, public :: PARTON_VALENCE_AND_TWIN = 6
integer, parameter, public :: PARTON_ALL = 7

```

(Muli interactions: variables)+≡

```

integer, parameter, public :: PDF_UNDEFINED = 0
integer, parameter, public :: PDF_GLUON = 1
integer, parameter, public :: PDF_SEA = 2
integer, parameter, public :: PDF_VALENCE_DOWN = 3
integer, parameter, public :: PDF_VALENCE_UP = 4
integer, parameter, public :: PDF_TWIN = 5

```

Evolution variable is $pt2s/(x1*x2)$.

(Muli interactions: variables)+≡

```

real(default), dimension(1:4,1:8),parameter :: &
  phase_space_coefficients_inout = reshape(source=[ &
    3072, -2304, +192, 0, &
    6144, -5120, +384, 0, &
    0, 0, 192, -96, &
    3072, -2048, +192, -96, &
    0, 2048, -2176, +576, &
    0, 288, -306, +81, &
    6912, -4800, +528, 0, &
    31104, -23328, +5832, -486], &
    shape=[4,8])

```

```

(Multi interactions: variables)+≡
integer, dimension(1:4,0:8), parameter :: inout_signatures = &
  reshape (source = [ &
    1, 1, 1, 1, & !1a
    -1, 1,-1, 1, & !1b
    1, 1, 1, 1, & !2
    1,-1, 1,-1, & !3
    1,-1, 1,-1, & !4
    1,-1, 0, 0, & !5
    0, 0, 1,-1, & !6
    1, 0, 1, 0, & !7
    0, 0, 0, 0 ], &
    shape = [4,9])

```

```

(Multi interactions: variables)+≡
integer, dimension(6,-234:234), save, public :: valid_processes
data valid_processes (:,-234) / -6, -6, -6, -6, 2, 2 /
data valid_processes (:,-233) / -6, -5, -6, -5, 1, 1 /
data valid_processes (:,-232) / -6, -5, -5, -6, 1, 1 /
data valid_processes (:,-231) / -6, -4, -6, -4, 1, 1 /
data valid_processes (:,-230) / -6, -4, -4, -6, 1, 1 /
data valid_processes (:,-229) / -6, -3, -6, -3, 1, 1 /
data valid_processes (:,-228) / -6, -3, -3, -6, 1, 1 /
data valid_processes (:,-227) / -6, -2, -6, -2, 1, 1 /
data valid_processes (:,-226) / -6, -2, -2, -6, 1, 1 /
data valid_processes (:,-225) / -6, -1, -6, -1, 1, 1 /
data valid_processes (:,-224) / -6, -1, -1, -6, 1, 1 /
data valid_processes (:,-223) / -6, 0, -6, 0, 4, 7 /
data valid_processes (:,-222) / -6, 0, 0, -6, 4, 7 /
data valid_processes (:,-221) / -6, 1, -6, 1, 1, 1 /
data valid_processes (:,-220) / -6, 1, 1, -6, 1, 1 /
data valid_processes (:,-219) / -6, 2, -6, 2, 1, 1 /
data valid_processes (:,-218) / -6, 2, 2, -6, 1, 1 /
data valid_processes (:,-217) / -6, 3, -6, 3, 1, 1 /
data valid_processes (:,-216) / -6, 3, 3, -6, 1, 1 /
data valid_processes (:,-215) / -6, 4, -6, 4, 1, 1 /
data valid_processes (:,-214) / -6, 4, 4, -6, 1, 1 /
data valid_processes (:,-213) / -6, 5, -6, 5, 1, 1 /
data valid_processes (:,-212) / -6, 5, 5, -6, 1, 1 /
data valid_processes (:,-211) / -6, 6, -6, 6, 3, 4 /
data valid_processes (:,-210) / -6, 6, -5, 5, 3, 3 /
data valid_processes (:,-209) / -6, 6, -4, 4, 3, 3 /
data valid_processes (:,-208) / -6, 6, -3, 3, 3, 3 /
data valid_processes (:,-207) / -6, 6, -2, 2, 3, 3 /
data valid_processes (:,-206) / -6, 6, -1, 1, 3, 3 /
data valid_processes (:,-205) / -6, 6, 0, 0, 3, 5 /
data valid_processes (:,-204) / -6, 6, 1, -1, 3, 3 /
data valid_processes (:,-203) / -6, 6, 2, -2, 3, 3 /
data valid_processes (:,-202) / -6, 6, 3, -3, 3, 3 /
data valid_processes (:,-201) / -6, 6, 4, -4, 3, 3 /
data valid_processes (:,-200) / -6, 6, 5, -5, 3, 3 /
data valid_processes (:,-199) / -6, 6, 6, -6, 3, 4 /
data valid_processes (:,-198) / -5, -6, -6, -5, 1, 1 /
data valid_processes (:,-197) / -5, -6, -5, -6, 1, 1 /

```



```

data valid_processes (:,-196) / -5, -5, -5, -5, 2, 2 /
data valid_processes (:,-195) / -5, -4, -5, -4, 1, 1 /
data valid_processes (:,-194) / -5, -4, -4, -5, 1, 1 /
data valid_processes (:,-193) / -5, -3, -5, -3, 1, 1 /
data valid_processes (:,-192) / -5, -3, -3, -5, 1, 1 /
data valid_processes (:,-191) / -5, -2, -5, -2, 1, 1 /
data valid_processes (:,-190) / -5, -2, -2, -5, 1, 1 /
data valid_processes (:,-189) / -5, -1, -5, -1, 1, 1 /
data valid_processes (:,-188) / -5, -1, -1, -5, 1, 1 /
data valid_processes (:,-187) / -5, 0, -5, 0, 4, 7 /
data valid_processes (:,-186) / -5, 0, 0, -5, 4, 7 /
data valid_processes (:,-185) / -5, 1, -5, 1, 1, 1 /
data valid_processes (:,-184) / -5, 1, 1, -5, 1, 1 /
data valid_processes (:,-183) / -5, 2, -5, 2, 1, 1 /
data valid_processes (:,-182) / -5, 2, 2, -5, 1, 1 /
data valid_processes (:,-181) / -5, 3, -5, 3, 1, 1 /
data valid_processes (:,-180) / -5, 3, 3, -5, 1, 1 /
data valid_processes (:,-179) / -5, 4, -5, 4, 1, 1 /
data valid_processes (:,-178) / -5, 4, 4, -5, 1, 1 /
data valid_processes (:,-177) / -5, 5, -6, 6, 3, 3 /
data valid_processes (:,-176) / -5, 5, -5, 5, 3, 4 /
data valid_processes (:,-175) / -5, 5, -4, 4, 3, 3 /
data valid_processes (:,-174) / -5, 5, -3, 3, 3, 3 /
data valid_processes (:,-173) / -5, 5, -2, 2, 3, 3 /
data valid_processes (:,-172) / -5, 5, -1, 1, 3, 3 /
data valid_processes (:,-171) / -5, 5, 0, 0, 3, 5 /
data valid_processes (:,-170) / -5, 5, 1, -1, 3, 3 /
data valid_processes (:,-169) / -5, 5, 2, -2, 3, 3 /
data valid_processes (:,-168) / -5, 5, 3, -3, 3, 3 /
data valid_processes (:,-167) / -5, 5, 4, -4, 3, 3 /
data valid_processes (:,-166) / -5, 5, 5, -5, 3, 4 /
data valid_processes (:,-165) / -5, 5, 6, -6, 3, 3 /
data valid_processes (:,-164) / -5, 6, -5, 6, 1, 1 /
data valid_processes (:,-163) / -5, 6, 6, -5, 1, 1 /
data valid_processes (:,-162) / -4, -6, -6, -4, 1, 1 /
data valid_processes (:,-161) / -4, -6, -4, -6, 1, 1 /
data valid_processes (:,-160) / -4, -5, -5, -4, 1, 1 /
data valid_processes (:,-159) / -4, -5, -4, -5, 1, 1 /
data valid_processes (:,-158) / -4, -4, -4, -4, 2, 2 /
data valid_processes (:,-157) / -4, -3, -4, -3, 1, 1 /
data valid_processes (:,-156) / -4, -3, -3, -4, 1, 1 /
data valid_processes (:,-155) / -4, -2, -4, -2, 1, 1 /
data valid_processes (:,-154) / -4, -2, -2, -4, 1, 1 /
data valid_processes (:,-153) / -4, -1, -4, -1, 1, 1 /
data valid_processes (:,-152) / -4, -1, -1, -4, 1, 1 /
data valid_processes (:,-151) / -4, 0, -4, 0, 4, 7 /
data valid_processes (:,-150) / -4, 0, 0, -4, 4, 7 /
data valid_processes (:,-149) / -4, 1, -4, 1, 1, 1 /
data valid_processes (:,-148) / -4, 1, 1, -4, 1, 1 /
data valid_processes (:,-147) / -4, 2, -4, 2, 1, 1 /
data valid_processes (:,-146) / -4, 2, 2, -4, 1, 1 /
data valid_processes (:,-145) / -4, 3, -4, 3, 1, 1 /
data valid_processes (:,-144) / -4, 3, 3, -4, 1, 1 /
data valid_processes (:,-143) / -4, 4, -6, 6, 3, 3 /

```

```

data valid_processes (:,-142) / -4, 4, -5, 5, 3, 3 /
data valid_processes (:,-141) / -4, 4, -4, 4, 3, 4 /
data valid_processes (:,-140) / -4, 4, -3, 3, 3, 3 /
data valid_processes (:,-139) / -4, 4, -2, 2, 3, 3 /
data valid_processes (:,-138) / -4, 4, -1, 1, 3, 3 /
data valid_processes (:,-137) / -4, 4, 0, 0, 3, 5 /
data valid_processes (:,-136) / -4, 4, 1, -1, 3, 3 /
data valid_processes (:,-135) / -4, 4, 2, -2, 3, 3 /
data valid_processes (:,-134) / -4, 4, 3, -3, 3, 3 /
data valid_processes (:,-133) / -4, 4, 4, -4, 3, 4 /
data valid_processes (:,-132) / -4, 4, 5, -5, 3, 3 /
data valid_processes (:,-131) / -4, 4, 6, -6, 3, 3 /
data valid_processes (:,-130) / -4, 5, -4, 5, 1, 1 /
data valid_processes (:,-129) / -4, 5, 5, -4, 1, 1 /
data valid_processes (:,-128) / -4, 6, -4, 6, 1, 1 /
data valid_processes (:,-127) / -4, 6, 6, -4, 1, 1 /
data valid_processes (:,-126) / -3, -6, -6, -3, 1, 1 /
data valid_processes (:,-125) / -3, -6, -3, -6, 1, 1 /
data valid_processes (:,-124) / -3, -5, -5, -3, 1, 1 /
data valid_processes (:,-123) / -3, -5, -3, -5, 1, 1 /
data valid_processes (:,-122) / -3, -4, -4, -3, 1, 1 /
data valid_processes (:,-121) / -3, -4, -3, -4, 1, 1 /
data valid_processes (:,-120) / -3, -3, -3, -3, 2, 2 /
data valid_processes (:,-119) / -3, -2, -3, -2, 1, 1 /
data valid_processes (:,-118) / -3, -2, -2, -3, 1, 1 /
data valid_processes (:,-117) / -3, -1, -3, -1, 1, 1 /
data valid_processes (:,-116) / -3, -1, -1, -3, 1, 1 /
data valid_processes (:,-115) / -3, 0, -3, 0, 4, 7 /
data valid_processes (:,-114) / -3, 0, 0, -3, 4, 7 /
data valid_processes (:,-113) / -3, 1, -3, 1, 1, 1 /
data valid_processes (:,-112) / -3, 1, 1, -3, 1, 1 /
data valid_processes (:,-111) / -3, 2, -3, 2, 1, 1 /
data valid_processes (:,-110) / -3, 2, 2, -3, 1, 1 /
data valid_processes (:,-109) / -3, 3, -6, 6, 3, 3 /
data valid_processes (:,-108) / -3, 3, -5, 5, 3, 3 /
data valid_processes (:,-107) / -3, 3, -4, 4, 3, 3 /
data valid_processes (:,-106) / -3, 3, -3, 3, 3, 4 /
data valid_processes (:,-105) / -3, 3, -2, 2, 3, 3 /
data valid_processes (:,-104) / -3, 3, -1, 1, 3, 3 /
data valid_processes (:,-103) / -3, 3, 0, 0, 3, 5 /
data valid_processes (:,-102) / -3, 3, 1, -1, 3, 3 /
data valid_processes (:,-101) / -3, 3, 2, -2, 3, 3 /
data valid_processes (:,-100) / -3, 3, 3, -3, 3, 4 /
data valid_processes (:, -99) / -3, 3, 4, -4, 3, 3 /
data valid_processes (:, -98) / -3, 3, 5, -5, 3, 3 /
data valid_processes (:, -97) / -3, 3, 6, -6, 3, 3 /
data valid_processes (:, -96) / -3, 4, -3, 4, 1, 1 /
data valid_processes (:, -95) / -3, 4, 4, -3, 1, 1 /
data valid_processes (:, -94) / -3, 5, -3, 5, 1, 1 /
data valid_processes (:, -93) / -3, 5, 5, -3, 1, 1 /
data valid_processes (:, -92) / -3, 6, -3, 6, 1, 1 /
data valid_processes (:, -91) / -3, 6, 6, -3, 1, 1 /
data valid_processes (:, -90) / -2, -6, -6, -2, 1, 1 /
data valid_processes (:, -89) / -2, -6, -2, -6, 1, 1 /

```

```

data valid_processes (:, -88) / -2, -5, -5, -2, 1, 1 /
data valid_processes (:, -87) / -2, -5, -2, -5, 1, 1 /
data valid_processes (:, -86) / -2, -4, -4, -2, 1, 1 /
data valid_processes (:, -85) / -2, -4, -2, -4, 1, 1 /
data valid_processes (:, -84) / -2, -3, -3, -2, 1, 1 /
data valid_processes (:, -83) / -2, -3, -2, -3, 1, 1 /
data valid_processes (:, -82) / -2, -2, -2, -2, 2, 2 /
data valid_processes (:, -81) / -2, -1, -2, -1, 1, 1 /
data valid_processes (:, -80) / -2, -1, -1, -2, 1, 1 /
data valid_processes (:, -79) / -2, 0, -2, 0, 4, 7 /
data valid_processes (:, -78) / -2, 0, 0, -2, 4, 7 /
data valid_processes (:, -77) / -2, 1, -2, 1, 1, 1 /
data valid_processes (:, -76) / -2, 1, 1, -2, 1, 1 /
data valid_processes (:, -75) / -2, 2, -6, 6, 3, 3 /
data valid_processes (:, -74) / -2, 2, -5, 5, 3, 3 /
data valid_processes (:, -73) / -2, 2, -4, 4, 3, 3 /
data valid_processes (:, -72) / -2, 2, -3, 3, 3, 3 /
data valid_processes (:, -71) / -2, 2, -2, 2, 3, 4 /
data valid_processes (:, -70) / -2, 2, -1, 1, 3, 3 /
data valid_processes (:, -69) / -2, 2, 0, 0, 3, 5 /
data valid_processes (:, -68) / -2, 2, 1, -1, 3, 3 /
data valid_processes (:, -67) / -2, 2, 2, -2, 3, 4 /
data valid_processes (:, -66) / -2, 2, 3, -3, 3, 3 /
data valid_processes (:, -65) / -2, 2, 4, -4, 3, 3 /
data valid_processes (:, -64) / -2, 2, 5, -5, 3, 3 /
data valid_processes (:, -63) / -2, 2, 6, -6, 3, 3 /
data valid_processes (:, -62) / -2, 3, -2, 3, 1, 1 /
data valid_processes (:, -61) / -2, 3, 3, -2, 1, 1 /
data valid_processes (:, -60) / -2, 4, -2, 4, 1, 1 /
data valid_processes (:, -59) / -2, 4, 4, -2, 1, 1 /
data valid_processes (:, -58) / -2, 5, -2, 5, 1, 1 /
data valid_processes (:, -57) / -2, 5, 5, -2, 1, 1 /
data valid_processes (:, -56) / -2, 6, -2, 6, 1, 1 /
data valid_processes (:, -55) / -2, 6, 6, -2, 1, 1 /
data valid_processes (:, -54) / -1, -6, -6, -1, 1, 1 /
data valid_processes (:, -53) / -1, -6, -1, -6, 1, 1 /
data valid_processes (:, -52) / -1, -5, -5, -1, 1, 1 /
data valid_processes (:, -51) / -1, -5, -1, -5, 1, 1 /
data valid_processes (:, -50) / -1, -4, -4, -1, 1, 1 /
data valid_processes (:, -49) / -1, -4, -1, -4, 1, 1 /
data valid_processes (:, -48) / -1, -3, -3, -1, 1, 1 /
data valid_processes (:, -47) / -1, -3, -1, -3, 1, 1 /
data valid_processes (:, -46) / -1, -2, -2, -1, 1, 1 /
data valid_processes (:, -45) / -1, -2, -1, -2, 1, 1 /
data valid_processes (:, -44) / -1, -1, -1, -1, 2, 2 /
data valid_processes (:, -43) / -1, 0, -1, 0, 4, 7 /
data valid_processes (:, -42) / -1, 0, 0, -1, 4, 7 /
data valid_processes (:, -41) / -1, 1, -6, 6, 3, 3 /
data valid_processes (:, -40) / -1, 1, -5, 5, 3, 3 /
data valid_processes (:, -39) / -1, 1, -4, 4, 3, 3 /
data valid_processes (:, -38) / -1, 1, -3, 3, 3, 3 /
data valid_processes (:, -37) / -1, 1, -2, 2, 3, 3 /
data valid_processes (:, -36) / -1, 1, -1, 1, 3, 4 /
data valid_processes (:, -35) / -1, 1, 0, 0, 3, 5 /

```

```

data valid_processes (:, -34) / -1, 1, 1, -1, 3, 4 /
data valid_processes (:, -33) / -1, 1, 2, -2, 3, 3 /
data valid_processes (:, -32) / -1, 1, 3, -3, 3, 3 /
data valid_processes (:, -31) / -1, 1, 4, -4, 3, 3 /
data valid_processes (:, -30) / -1, 1, 5, -5, 3, 3 /
data valid_processes (:, -29) / -1, 1, 6, -6, 3, 3 /
data valid_processes (:, -28) / -1, 2, -1, 2, 1, 1 /
data valid_processes (:, -27) / -1, 2, 2, -1, 1, 1 /
data valid_processes (:, -26) / -1, 3, -1, 3, 1, 1 /
data valid_processes (:, -25) / -1, 3, 3, -1, 1, 1 /
data valid_processes (:, -24) / -1, 4, -1, 4, 1, 1 /
data valid_processes (:, -23) / -1, 4, 4, -1, 1, 1 /
data valid_processes (:, -22) / -1, 5, -1, 5, 1, 1 /
data valid_processes (:, -21) / -1, 5, 5, -1, 1, 1 /
data valid_processes (:, -20) / -1, 6, -1, 6, 1, 1 /
data valid_processes (:, -19) / -1, 6, 6, -1, 1, 1 /
data valid_processes (:, -18) / 0, -6, -6, 0, 4, 7 /
data valid_processes (:, -17) / 0, -6, 0, -6, 4, 7 /
data valid_processes (:, -16) / 0, -5, -5, 0, 4, 7 /
data valid_processes (:, -15) / 0, -5, 0, -5, 4, 7 /
data valid_processes (:, -14) / 0, -4, -4, 0, 4, 7 /
data valid_processes (:, -13) / 0, -4, 0, -4, 4, 7 /
data valid_processes (:, -12) / 0, -3, -3, 0, 4, 7 /
data valid_processes (:, -11) / 0, -3, 0, -3, 4, 7 /
data valid_processes (:, -10) / 0, -2, -2, 0, 4, 7 /
data valid_processes (:, -9) / 0, -2, 0, -2, 4, 7 /
data valid_processes (:, -8) / 0, -1, -1, 0, 4, 7 /
data valid_processes (:, -7) / 0, -1, 0, -1, 4, 7 /
data valid_processes (:, -6) / 0, 0, -6, 6, 5, 6 /
data valid_processes (:, -5) / 0, 0, -5, 5, 5, 6 /
data valid_processes (:, -4) / 0, 0, -4, 4, 5, 6 /
data valid_processes (:, -3) / 0, 0, -3, 3, 5, 6 /
data valid_processes (:, -2) / 0, 0, -2, 2, 5, 6 /
data valid_processes (:, -1) / 0, 0, -1, 1, 5, 6 /
data valid_processes (:, 0) / 0, 0, 0, 0, 5, 8 /
data valid_processes (:, 1) / 0, 0, 1, -1, 5, 6 /
data valid_processes (:, 2) / 0, 0, 2, -2, 5, 6 /
data valid_processes (:, 3) / 0, 0, 3, -3, 5, 6 /
data valid_processes (:, 4) / 0, 0, 4, -4, 5, 6 /
data valid_processes (:, 5) / 0, 0, 5, -5, 5, 6 /
data valid_processes (:, 6) / 0, 0, 6, -6, 5, 6 /
data valid_processes (:, 7) / 0, 1, 0, 1, 4, 7 /
data valid_processes (:, 8) / 0, 1, 1, 0, 4, 7 /
data valid_processes (:, 9) / 0, 2, 0, 2, 4, 7 /
data valid_processes (:, 10) / 0, 2, 2, 0, 4, 7 /
data valid_processes (:, 11) / 0, 3, 0, 3, 4, 7 /
data valid_processes (:, 12) / 0, 3, 3, 0, 4, 7 /
data valid_processes (:, 13) / 0, 4, 0, 4, 4, 7 /
data valid_processes (:, 14) / 0, 4, 4, 0, 4, 7 /
data valid_processes (:, 15) / 0, 5, 0, 5, 4, 7 /
data valid_processes (:, 16) / 0, 5, 5, 0, 4, 7 /
data valid_processes (:, 17) / 0, 6, 0, 6, 4, 7 /
data valid_processes (:, 18) / 0, 6, 6, 0, 4, 7 /
data valid_processes (:, 19) / 1, -6, -6, 1, 1, 1 /

```

```

data valid_processes (:, 20) / 1, -6, 1, -6, 1, 1 /
data valid_processes (:, 21) / 1, -5, -5, 1, 1, 1 /
data valid_processes (:, 22) / 1, -5, 1, -5, 1, 1 /
data valid_processes (:, 23) / 1, -4, -4, 1, 1, 1 /
data valid_processes (:, 24) / 1, -4, 1, -4, 1, 1 /
data valid_processes (:, 25) / 1, -3, -3, 1, 1, 1 /
data valid_processes (:, 26) / 1, -3, 1, -3, 1, 1 /
data valid_processes (:, 27) / 1, -2, -2, 1, 1, 1 /
data valid_processes (:, 28) / 1, -2, 1, -2, 1, 1 /
data valid_processes (:, 29) / 1, -1, -6, 6, 3, 3 /
data valid_processes (:, 30) / 1, -1, -5, 5, 3, 3 /
data valid_processes (:, 31) / 1, -1, -4, 4, 3, 3 /
data valid_processes (:, 32) / 1, -1, -3, 3, 3, 3 /
data valid_processes (:, 33) / 1, -1, -2, 2, 3, 3 /
data valid_processes (:, 34) / 1, -1, -1, 1, 3, 4 /
data valid_processes (:, 35) / 1, -1, 0, 0, 3, 5 /
data valid_processes (:, 36) / 1, -1, 1, -1, 3, 4 /
data valid_processes (:, 37) / 1, -1, 2, -2, 3, 3 /
data valid_processes (:, 38) / 1, -1, 3, -3, 3, 3 /
data valid_processes (:, 39) / 1, -1, 4, -4, 3, 3 /
data valid_processes (:, 40) / 1, -1, 5, -5, 3, 3 /
data valid_processes (:, 41) / 1, -1, 6, -6, 3, 3 /
data valid_processes (:, 42) / 1, 0, 0, 1, 4, 7 /
data valid_processes (:, 43) / 1, 0, 1, 0, 4, 7 /
data valid_processes (:, 44) / 1, 1, 1, 1, 2, 2 /
data valid_processes (:, 45) / 1, 2, 1, 2, 1, 1 /
data valid_processes (:, 46) / 1, 2, 2, 1, 1, 1 /
data valid_processes (:, 47) / 1, 3, 1, 3, 1, 1 /
data valid_processes (:, 48) / 1, 3, 3, 1, 1, 1 /
data valid_processes (:, 49) / 1, 4, 1, 4, 1, 1 /
data valid_processes (:, 50) / 1, 4, 4, 1, 1, 1 /
data valid_processes (:, 51) / 1, 5, 1, 5, 1, 1 /
data valid_processes (:, 52) / 1, 5, 5, 1, 1, 1 /
data valid_processes (:, 53) / 1, 6, 1, 6, 1, 1 /
data valid_processes (:, 54) / 1, 6, 6, 1, 1, 1 /
data valid_processes (:, 55) / 2, -6, -6, 2, 1, 1 /
data valid_processes (:, 56) / 2, -6, 2, -6, 1, 1 /
data valid_processes (:, 57) / 2, -5, -5, 2, 1, 1 /
data valid_processes (:, 58) / 2, -5, 2, -5, 1, 1 /
data valid_processes (:, 59) / 2, -4, -4, 2, 1, 1 /
data valid_processes (:, 60) / 2, -4, 2, -4, 1, 1 /
data valid_processes (:, 61) / 2, -3, -3, 2, 1, 1 /
data valid_processes (:, 62) / 2, -3, 2, -3, 1, 1 /
data valid_processes (:, 63) / 2, -2, -6, 6, 3, 3 /
data valid_processes (:, 64) / 2, -2, -5, 5, 3, 3 /
data valid_processes (:, 65) / 2, -2, -4, 4, 3, 3 /
data valid_processes (:, 66) / 2, -2, -3, 3, 3, 3 /
data valid_processes (:, 67) / 2, -2, -2, 2, 3, 4 /
data valid_processes (:, 68) / 2, -2, -1, 1, 3, 3 /
data valid_processes (:, 69) / 2, -2, 0, 0, 3, 5 /
data valid_processes (:, 70) / 2, -2, 1, -1, 3, 3 /
data valid_processes (:, 71) / 2, -2, 2, -2, 3, 4 /
data valid_processes (:, 72) / 2, -2, 3, -3, 3, 3 /
data valid_processes (:, 73) / 2, -2, 4, -4, 3, 3 /

```

```

data valid_processes (:, 74) / 2, -2, 5, -5, 3, 3 /
data valid_processes (:, 75) / 2, -2, 6, -6, 3, 3 /
data valid_processes (:, 76) / 2, -1, -1, 2, 1, 1 /
data valid_processes (:, 77) / 2, -1, 2, -1, 1, 1 /
data valid_processes (:, 78) / 2, 0, 0, 2, 4, 7 /
data valid_processes (:, 79) / 2, 0, 2, 0, 4, 7 /
data valid_processes (:, 80) / 2, 1, 1, 2, 1, 1 /
data valid_processes (:, 81) / 2, 1, 2, 1, 1, 1 /
data valid_processes (:, 82) / 2, 2, 2, 2, 2, 2 /
data valid_processes (:, 83) / 2, 3, 2, 3, 1, 1 /
data valid_processes (:, 84) / 2, 3, 3, 2, 1, 1 /
data valid_processes (:, 85) / 2, 4, 2, 4, 1, 1 /
data valid_processes (:, 86) / 2, 4, 4, 2, 1, 1 /
data valid_processes (:, 87) / 2, 5, 2, 5, 1, 1 /
data valid_processes (:, 88) / 2, 5, 5, 2, 1, 1 /
data valid_processes (:, 89) / 2, 6, 2, 6, 1, 1 /
data valid_processes (:, 90) / 2, 6, 6, 2, 1, 1 /
data valid_processes (:, 91) / 3, -6, -6, 3, 1, 1 /
data valid_processes (:, 92) / 3, -6, 3, -6, 1, 1 /
data valid_processes (:, 93) / 3, -5, -5, 3, 1, 1 /
data valid_processes (:, 94) / 3, -5, 3, -5, 1, 1 /
data valid_processes (:, 95) / 3, -4, -4, 3, 1, 1 /
data valid_processes (:, 96) / 3, -4, 3, -4, 1, 1 /
data valid_processes (:, 97) / 3, -3, -6, 6, 3, 3 /
data valid_processes (:, 98) / 3, -3, -5, 5, 3, 3 /
data valid_processes (:, 99) / 3, -3, -4, 4, 3, 3 /
data valid_processes (:, 100) / 3, -3, -3, 3, 3, 4 /
data valid_processes (:, 101) / 3, -3, -2, 2, 3, 3 /
data valid_processes (:, 102) / 3, -3, -1, 1, 3, 3 /
data valid_processes (:, 103) / 3, -3, 0, 0, 3, 5 /
data valid_processes (:, 104) / 3, -3, 1, -1, 3, 3 /
data valid_processes (:, 105) / 3, -3, 2, -2, 3, 3 /
data valid_processes (:, 106) / 3, -3, 3, -3, 3, 4 /
data valid_processes (:, 107) / 3, -3, 4, -4, 3, 3 /
data valid_processes (:, 108) / 3, -3, 5, -5, 3, 3 /
data valid_processes (:, 109) / 3, -3, 6, -6, 3, 3 /
data valid_processes (:, 110) / 3, -2, -2, 3, 1, 1 /
data valid_processes (:, 111) / 3, -2, 3, -2, 1, 1 /
data valid_processes (:, 112) / 3, -1, -1, 3, 1, 1 /
data valid_processes (:, 113) / 3, -1, 3, -1, 1, 1 /
data valid_processes (:, 114) / 3, 0, 0, 3, 4, 7 /
data valid_processes (:, 115) / 3, 0, 3, 0, 4, 7 /
data valid_processes (:, 116) / 3, 1, 1, 3, 1, 1 /
data valid_processes (:, 117) / 3, 1, 3, 1, 1, 1 /
data valid_processes (:, 118) / 3, 2, 2, 3, 1, 1 /
data valid_processes (:, 119) / 3, 2, 3, 2, 1, 1 /
data valid_processes (:, 120) / 3, 3, 3, 3, 2, 2 /
data valid_processes (:, 121) / 3, 4, 3, 4, 1, 1 /
data valid_processes (:, 122) / 3, 4, 4, 3, 1, 1 /
data valid_processes (:, 123) / 3, 5, 3, 5, 1, 1 /
data valid_processes (:, 124) / 3, 5, 5, 3, 1, 1 /
data valid_processes (:, 125) / 3, 6, 3, 6, 1, 1 /
data valid_processes (:, 126) / 3, 6, 6, 3, 1, 1 /
data valid_processes (:, 127) / 4, -6, -6, 4, 1, 1 /

```

```

data valid_processes (:, 128) / 4, -6, 4, -6, 1, 1 /
data valid_processes (:, 129) / 4, -5, -5, 4, 1, 1 /
data valid_processes (:, 130) / 4, -5, 4, -5, 1, 1 /
data valid_processes (:, 131) / 4, -4, -6, 6, 3, 3 /
data valid_processes (:, 132) / 4, -4, -5, 5, 3, 3 /
data valid_processes (:, 133) / 4, -4, -4, 4, 3, 4 /
data valid_processes (:, 134) / 4, -4, -3, 3, 3, 3 /
data valid_processes (:, 135) / 4, -4, -2, 2, 3, 3 /
data valid_processes (:, 136) / 4, -4, -1, 1, 3, 3 /
data valid_processes (:, 137) / 4, -4, 0, 0, 3, 5 /
data valid_processes (:, 138) / 4, -4, 1, -1, 3, 3 /
data valid_processes (:, 139) / 4, -4, 2, -2, 3, 3 /
data valid_processes (:, 140) / 4, -4, 3, -3, 3, 3 /
data valid_processes (:, 141) / 4, -4, 4, -4, 3, 4 /
data valid_processes (:, 142) / 4, -4, 5, -5, 3, 3 /
data valid_processes (:, 143) / 4, -4, 6, -6, 3, 3 /
data valid_processes (:, 144) / 4, -3, -3, 4, 1, 1 /
data valid_processes (:, 145) / 4, -3, 4, -3, 1, 1 /
data valid_processes (:, 146) / 4, -2, -2, 4, 1, 1 /
data valid_processes (:, 147) / 4, -2, 4, -2, 1, 1 /
data valid_processes (:, 148) / 4, -1, -1, 4, 1, 1 /
data valid_processes (:, 149) / 4, -1, 4, -1, 1, 1 /
data valid_processes (:, 150) / 4, 0, 0, 4, 4, 7 /
data valid_processes (:, 151) / 4, 0, 4, 0, 4, 7 /
data valid_processes (:, 152) / 4, 1, 1, 4, 1, 1 /
data valid_processes (:, 153) / 4, 1, 4, 1, 1, 1 /
data valid_processes (:, 154) / 4, 2, 2, 4, 1, 1 /
data valid_processes (:, 155) / 4, 2, 4, 2, 1, 1 /
data valid_processes (:, 156) / 4, 3, 3, 4, 1, 1 /
data valid_processes (:, 157) / 4, 3, 4, 3, 1, 1 /
data valid_processes (:, 158) / 4, 4, 4, 4, 2, 2 /
data valid_processes (:, 159) / 4, 5, 4, 5, 1, 1 /
data valid_processes (:, 160) / 4, 5, 5, 4, 1, 1 /
data valid_processes (:, 161) / 4, 6, 4, 6, 1, 1 /
data valid_processes (:, 162) / 4, 6, 6, 4, 1, 1 /
data valid_processes (:, 163) / 5, -6, -6, 5, 1, 1 /
data valid_processes (:, 164) / 5, -6, 5, -6, 1, 1 /
data valid_processes (:, 165) / 5, -5, -6, 6, 3, 3 /
data valid_processes (:, 166) / 5, -5, -5, 5, 3, 4 /
data valid_processes (:, 167) / 5, -5, -4, 4, 3, 3 /
data valid_processes (:, 168) / 5, -5, -3, 3, 3, 3 /
data valid_processes (:, 169) / 5, -5, -2, 2, 3, 3 /
data valid_processes (:, 170) / 5, -5, -1, 1, 3, 3 /
data valid_processes (:, 171) / 5, -5, 0, 0, 3, 5 /
data valid_processes (:, 172) / 5, -5, 1, -1, 3, 3 /
data valid_processes (:, 173) / 5, -5, 2, -2, 3, 3 /
data valid_processes (:, 174) / 5, -5, 3, -3, 3, 3 /
data valid_processes (:, 175) / 5, -5, 4, -4, 3, 3 /
data valid_processes (:, 176) / 5, -5, 5, -5, 3, 4 /
data valid_processes (:, 177) / 5, -5, 6, -6, 3, 3 /
data valid_processes (:, 178) / 5, -4, -4, 5, 1, 1 /
data valid_processes (:, 179) / 5, -4, 5, -4, 1, 1 /
data valid_processes (:, 180) / 5, -3, -3, 5, 1, 1 /
data valid_processes (:, 181) / 5, -3, 5, -3, 1, 1 /

```

```

data valid_processes (:, 182) / 5, -2, -2, 5, 1, 1 /
data valid_processes (:, 183) / 5, -2, 5, -2, 1, 1 /
data valid_processes (:, 184) / 5, -1, -1, 5, 1, 1 /
data valid_processes (:, 185) / 5, -1, 5, -1, 1, 1 /
data valid_processes (:, 186) / 5, 0, 0, 5, 4, 7 /
data valid_processes (:, 187) / 5, 0, 5, 0, 4, 7 /
data valid_processes (:, 188) / 5, 1, 1, 5, 1, 1 /
data valid_processes (:, 189) / 5, 1, 5, 1, 1, 1 /
data valid_processes (:, 190) / 5, 2, 2, 5, 1, 1 /
data valid_processes (:, 191) / 5, 2, 5, 2, 1, 1 /
data valid_processes (:, 192) / 5, 3, 3, 5, 1, 1 /
data valid_processes (:, 193) / 5, 3, 5, 3, 1, 1 /
data valid_processes (:, 194) / 5, 4, 4, 5, 1, 1 /
data valid_processes (:, 195) / 5, 4, 5, 4, 1, 1 /
data valid_processes (:, 196) / 5, 5, 5, 5, 2, 2 /
data valid_processes (:, 197) / 5, 6, 5, 6, 1, 1 /
data valid_processes (:, 198) / 5, 6, 6, 5, 1, 1 /
data valid_processes (:, 199) / 6, -6, -6, 6, 3, 4 /
data valid_processes (:, 200) / 6, -6, -5, 5, 3, 3 /
data valid_processes (:, 201) / 6, -6, -4, 4, 3, 3 /
data valid_processes (:, 202) / 6, -6, -3, 3, 3, 3 /
data valid_processes (:, 203) / 6, -6, -2, 2, 3, 3 /
data valid_processes (:, 204) / 6, -6, -1, 1, 3, 3 /
data valid_processes (:, 205) / 6, -6, 0, 0, 3, 5 /
data valid_processes (:, 206) / 6, -6, 1, -1, 3, 3 /
data valid_processes (:, 207) / 6, -6, 2, -2, 3, 3 /
data valid_processes (:, 208) / 6, -6, 3, -3, 3, 3 /
data valid_processes (:, 209) / 6, -6, 4, -4, 3, 3 /
data valid_processes (:, 210) / 6, -6, 5, -5, 3, 3 /
data valid_processes (:, 211) / 6, -6, 6, -6, 3, 4 /
data valid_processes (:, 212) / 6, -5, -5, 6, 1, 1 /
data valid_processes (:, 213) / 6, -5, 6, -5, 1, 1 /
data valid_processes (:, 214) / 6, -4, -4, 6, 1, 1 /
data valid_processes (:, 215) / 6, -4, 6, -4, 1, 1 /
data valid_processes (:, 216) / 6, -3, -3, 6, 1, 1 /
data valid_processes (:, 217) / 6, -3, 6, -3, 1, 1 /
data valid_processes (:, 218) / 6, -2, -2, 6, 1, 1 /
data valid_processes (:, 219) / 6, -2, 6, -2, 1, 1 /
data valid_processes (:, 220) / 6, -1, -1, 6, 1, 1 /
data valid_processes (:, 221) / 6, -1, 6, -1, 1, 1 /
data valid_processes (:, 222) / 6, 0, 0, 6, 4, 7 /
data valid_processes (:, 223) / 6, 0, 6, 0, 4, 7 /
data valid_processes (:, 224) / 6, 1, 1, 6, 1, 1 /
data valid_processes (:, 225) / 6, 1, 6, 1, 1, 1 /
data valid_processes (:, 226) / 6, 2, 2, 6, 1, 1 /
data valid_processes (:, 227) / 6, 2, 6, 2, 1, 1 /
data valid_processes (:, 228) / 6, 3, 3, 6, 1, 1 /
data valid_processes (:, 229) / 6, 3, 6, 3, 1, 1 /
data valid_processes (:, 230) / 6, 4, 4, 6, 1, 1 /
data valid_processes (:, 231) / 6, 4, 6, 4, 1, 1 /
data valid_processes (:, 232) / 6, 5, 5, 6, 1, 1 /
data valid_processes (:, 233) / 6, 5, 6, 5, 1, 1 /
data valid_processes (:, 234) / 6, 6, 6, 6, 2, 2 /

```



```

<Multi interactions: variables>+≡
integer, dimension(2,0:16), parameter, public :: &
double_pdf_kinds = reshape ( [ &
0, 0, &
1, 1, &
1, 2, &
1, 3, &
1, 4, &
2, 1, &
2, 2, &
2, 3, &
2, 4, &
3, 1, &
3, 2, &
3, 3, &
3, 4, &
4, 1, &
4, 2, &
4, 3, &
4, 4], [2, 17])

```

```

<Multi interactions: variables>+≡
integer, parameter, dimension(371), public :: int_all = [ &
-6, -5, -4, -3, -2, -1, 0, 1, 2, &
3, 4, 5, 6, -14, -13, -12, -11, -10, &
9, -8, -7, 7, 8, 9, 10, 11, 12, &
13, 14, 7, 8, 9, 10, -151, -150, -115, &
-114, -79, -78, -43, -42, 42, 43, 78, 79, &
114, 115, 150, 151, -158, -157, -156, -155, -154, &
-153, -152, -149, -148, -147, -146, -145, -144, -143, &
-142, -141, -140, -139, -138, -137, -136, -135, -134, &
-133, -132, -131, -122, -121, -120, -119, -118, -117, &
-116, -113, -112, -111, -110, -109, -108, -107, -106, &
-105, -104, -103, -102, -101, -100, -99, -98, -97, &
-96, -95, -86, -85, -84, -83, -82, -81, -80, &
-77, -76, -75, -74, -73, -72, -71, -70, -69, &
-68, -67, -66, -65, -64, -63, -62, -61, -60, &
-59, -50, -49, -48, -47, -46, -45, -44, -41, &
-40, -39, -38, -37, -36, -35, -34, -33, -32, &
-31, -30, -29, -28, -27, -26, -25, -24, -23, &
23, 24, 25, 26, 27, 28, 29, 30, 31, &
32, 33, 34, 35, 36, 37, 38, 39, 40, &
41, 44, 45, 46, 47, 48, 49, 50, 59, &
60, 61, 62, 63, 64, 65, 66, 67, 68, &
69, 70, 71, 72, 73, 74, 75, 76, 77, &
80, 81, 82, 83, 84, 85, 86, 95, 96, &
97, 98, 99, 100, 101, 102, 103, 104, 105, &
106, 107, 108, 109, 110, 111, 112, 113, 116, &
117, 118, 119, 120, 121, 122, 131, 132, 133, &
134, 135, 136, 137, 138, 139, 140, 141, 142, &
143, 144, 145, 146, 147, 148, 149, 152, 153, &
154, 155, 156, 157, 158, -149, -148, -113, -112, &
-77, -76, -41, -40, -39, -38, -37, -36, -35, &
-34, -33, -32, -31, -30, -29, 44, 80, 81, &

```

```

116, 117, 152, 153, -147, -146, -111, -110, -75, &
-74, -73, -72, -71, -70, -69, -68, -67, -66, &
-65, -64, -63, -28, -27, 45, 46, 82, 118, &
119, 154, 155, 42, 43, 23, 24, 25, 26, &
27, 28, 29, 30, 31, 32, 33, 34, 35, &
36, 37, 38, 39, 40, 41, 44, 45, 46, &
47, 48, 49, 50, 44, 45, 46, 78, 79, &
59, 60, 61, 62, 63, 64, 65, 66, 67, &
68, 69, 70, 71, 72, 73, 74, 75, 76, &
77, 80, 81, 82, 83, 84, 85, 86, 80, &
81, 82 ]

```

(Multi interactions: variables)+≡

```

integer, parameter, dimension(16), public :: int_sizes_all = &
[13, 16, 2, 2, 16, 208, 26, 26, 2, 26, 1, 2, 2, 26, 2, 1]

```

(Multi interactions: variables)+≡

```

integer, parameter, dimension(3,0:8), public :: multi_flow_stats = &
reshape( [ &
1, 2, 4, &
3, 4, 4, &
5, 6, 8, &
7, 8, 4, &
9, 10, 8, &
11, 16, 16, &
17, 22, 16, &
23, 28, 16, &
29, 52, 96 ], &
[3,9])

```

(Multi interactions: variables)+≡

```

integer, parameter, dimension(0:4,52), public :: multi_flows = &
reshape( [ &
3, 0, 0, 1, 2, & !1a
1, 0, 0, 2, 1, &
1, 2, 0, 0, 3, & !1b
3, 3, 0, 0, 2, &
4, 0, 0, 1, 2, & !2
4, 0, 0, 2, 1, &
3, 2, 0, 0, 3, & !3
1, 3, 0, 0, 2, &
4, 2, 0, 0, 3, & !4
4, 3, 0, 0, 2, &
4, 0, 1, 3, 4, & !5
4, 0, 1, 4, 3, &
2, 0, 3, 1, 4, &
2, 0, 4, 1, 3, &
2, 0, 3, 4, 1, &
2, 0, 4, 3, 1, &
4, 1, 2, 4, 0, & !6
2, 1, 4, 2, 0, &
4, 2, 1, 4, 0, &
2, 4, 1, 2, 0, &

```

```

2, 2, 4, 1, 0, &
2, 4, 2, 1, 0, &
2, 0, 1, 2, 4, &      !7
2, 0, 1, 4, 2, &
4, 0, 2, 1, 4, &
4, 0, 4, 1, 2, &
2, 0, 2, 4, 1, &
2, 0, 4, 2, 1, &
9, 1, 2, 3, 4, &      !8
5, 1, 2, 4, 3, &
5, 1, 3, 2, 4, &
3, 1, 4, 2, 3, &
3, 1, 3, 4, 2, &
5, 1, 4, 3, 2, &
5, 2, 1, 3, 4, &
5, 2, 1, 4, 3, &
3, 3, 1, 2, 4, &
3, 4, 1, 2, 3, &
3, 3, 1, 4, 2, &
3, 4, 1, 3, 2, &
3, 2, 3, 1, 4, &
3, 2, 4, 1, 3, &
5, 3, 2, 1, 4, &
3, 4, 2, 1, 3, &
5, 3, 4, 1, 2, &
3, 4, 3, 1, 2, &
3, 2, 3, 4, 1, &
3, 2, 4, 3, 1, &
3, 3, 2, 4, 1, &
5, 4, 2, 3, 1, &
3, 3, 4, 2, 1, &
5, 4, 3, 2, 1], [5, 52])

```

This value, `pts2_scale`, seems to be nowhere set in the code.

```

<Muli interactions: variables>+≡
  real(default) :: pts2_scale

<Muli interactions: interfaces>≡
  abstract interface
    function trafo_in (in)
      use kinds !NODEP!
      real(default), dimension(3) :: trafo_in
      real(default), dimension(3), intent(in) :: in
    end function trafo_in
  end interface

<Muli interactions: interfaces>+≡
  abstract interface
    pure function coord_scalar_in (hyp)
      use kinds !NODEP!
      real(default) :: coord_scalar_in
      real(double), dimension(3), intent(in) :: hyp
    end function coord_scalar_in
  end interface

```

<Muli interactions: interfaces>+≡

```
abstract interface
  subroutine coord_hcd_in (hyp, cart, denom)
    use kinds !NODEP!
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out) :: denom
  end subroutine coord_hcd_in
end interface
```

This is the interface to the routines `alphasPDF` and `evolvePDF` from LHAPDF or internal PDFs which therefore need to be explicitly in double precision.

<Muli interactions: interfaces>+≡

```
interface
  pure function alphaspdf (Q)
    use kinds !NODEP!
    real(double) :: alphaspdf
    real(double), intent(in) :: Q
  end function alphaspdf
end interface
```

<Muli interactions: interfaces>+≡

```
interface
  pure subroutine evolvepdf (x, q, f)
    use kinds !NODEP!
    real(double), intent(in) :: x, q
    real(double), intent(out), dimension(-6:6) :: f
  end subroutine evolvepdf
end interface
```

<Muli interactions: public>≡

```
public :: muli_get_state_transformations
```

<Muli interactions: procedures>≡

```
pure function muli_get_state_transformations &
  (inout_kind, lha_flavors) result (transformations)
  integer, intent(in) :: inout_kind
  integer, dimension(4), intent(in) :: lha_flavors
  integer, dimension(4) :: signature
  logical, dimension(3) :: transformations
  where (lha_flavors > 0)
    signature = 1
  elsewhere (lha_flavors < 0)
    signature = -1
  elsewhere
    signature = 0
  end where
  ! print *, "inout_kind=", inout_kind
  ! print *, "lha_flavors=", lha_flavors
  ! print *, "signature", signature
  if ((sum(inout_signatures(1:2, inout_kind)) == sum(signature(1:2))) .and. &
    (sum(inout_signatures(3:4, inout_kind)) == sum(signature(3:4)))) then
    transformations(1) = .false.
  else
    transformations(1) = .true.
```

```

        signature = -signature
    end if
    if (all (inout_signatures(1:2,inout_kind) == signature(1:2))) then
        transformations(2) = .false.
    else
        transformations(2) = .true.
    end if
    if (all(inout_signatures(3:4,inout_kind) == signature(3:4))) then
        transformations(3) = .false.
    else
        transformations(3) = .true.
    end if
    ! print *, "signature", signature
    ! print *, "transformations=", transformations
end function multi_get_state_transformations

```

<Multi interactions: public>+≡
 public :: h_to_c_param

<Multi interactions: procedures>+≡
 pure function h_to_c_param (hyp)
 real(default), dimension(3) :: h_to_c_param
 real(default), dimension(3), intent(in) :: hyp
 h_to_c_param = [sqrt (sqrt (((hyp(1)**4) * (one-hyp(3))) + &
 hyp(3))**2 + (((hyp(2)-(5E-1_default))**3)*4)**2) - &
 ((hyp(2)-(5E-1_default))**3)*4), &
 sqrt (sqrt (((hyp(1)**4)*(one-hyp(3))) + hyp(3))**2 + &
 (((hyp(2)-(5E-1_default))**3)*4)**2) + &
 ((hyp(2)-(5E-1_default))**3)*4), hyp(3)]
 end function h_to_c_param

<Multi interactions: public>+≡
 public :: c_to_h_param

<Multi interactions: procedures>+≡
 pure function c_to_h_param (cart)
 real(default), dimension(3) :: c_to_h_param
 real(default), dimension(3), intent(in)::cart
 c_to_h_param= [(((cart(1)*cart(2)) - cart(3)) / &
 (one - cart(3)))**2*(1/four), (one + sign(abs((cart(2)**2) - &
 (cart(1)**2))**2*(1/three), cart(2) - cart(1))) / two, cart(3)]
 end function c_to_h_param

<Multi interactions: public>+≡
 public :: h_to_c_param_def

<Multi interactions: procedures>+≡
 pure function h_to_c_param_def (hyp)
 real(default), dimension(3) :: h_to_c_param_def
 real(default), dimension(3), intent(in) :: hyp
 h_to_c_param_def = h_to_c_param ([hyp(1), hyp(2), pts2_scale])
 end function h_to_c_param_def

```

<Muli interactions: public>+≡
  public :: h_to_c_ort

<Muli interactions: procedures>+≡
  pure function h_to_c_ort (hyp)
    real(default), dimension(3) :: h_to_c_ort
    real(default), dimension(3), intent(in) :: hyp
    h_to_c_ort = [sqrt (sqrt (((hyp(1) * (one - hyp(3))) + hyp(3))**2 + &
      (hyp(2) - (5E-1_default))**2) - (hyp(2) - (5E-1_default))), &
      sqrt (sqrt (((hyp(1) * (one - hyp(3))) + hyp(3))**2 + &
      (hyp(2) - (5E-1_default))**2) + (hyp(2) - (5E-1_default))), hyp(3)]
  end function h_to_c_ort

<Muli interactions: public>+≡
  public :: c_to_h_ort

<Muli interactions: procedures>+≡
  pure function c_to_h_ort (cart)
    real(default), dimension(3) :: c_to_h_ort
    real(default), dimension(3), intent(in) :: cart
    c_to_h_ort = [ (cart(3) - (cart(1)*cart(2))) / (cart(3) - one), &
      (one - cart(1)**2 + cart(2)**2) / two, cart(3)]
  end function c_to_h_ort

<Muli interactions: public>+≡
  public :: h_to_c_ort_def

<Muli interactions: procedures>+≡
  pure function h_to_c_ort_def (hyp)
    real(default), dimension(3) :: h_to_c_ort_def
    real(default), dimension(3), intent(in) :: hyp
    h_to_c_ort_def = h_to_c_ort ([hyp(1), hyp(2), pts2_scale])
  end function h_to_c_ort_def

<Muli interactions: public>+≡
  public :: c_to_h_ort_def

<Muli interactions: procedures>+≡
  pure function c_to_h_ort_def (cart)
    real(default), dimension(3) :: c_to_h_ort_def
    real(default), dimension(3), intent(in) :: cart
    c_to_h_ort_def = c_to_h_ort ([ cart(1), cart(2), pts2_scale])
  end function c_to_h_ort_def

<Muli interactions: public>+≡
  public :: h_to_c_noparam

<Muli interactions: procedures>+≡
  pure function h_to_c_noparam (hyp)
    real(default), dimension(2) :: h_to_c_noparam
    real(default), dimension(2), intent(in) :: hyp
    h_to_c_noparam = [sqrt (sqrt (hyp(1)**8 + (((hyp(2) - &
      (5E-1_default))**3)*4)**2) - ((hyp(2)-(5E-1_default))**3)*4), &
      sqrt (sqrt (hyp(1)**8 + (((hyp(2)-(5E-1_default))**3)*4)**2) + &

```

```

        ((hyp(2)-(5E-1_default))**3)*4)]
end function h_to_c_noparam

<Muli interactions: public>+≡
public :: c_to_h_noparam

<Muli interactions: procedures>+≡
pure function c_to_h_noparam (cart)
  real(default), dimension(2) :: c_to_h_noparam
  real(default), dimension(2), intent(in) :: cart
  c_to_h_noparam = [sqrt (sqrt (cart(1)*cart(2))), &
    (one + sign(abs((cart(2)**2) - (cart(1)**2))**(one/three), &
    cart(2)-cart(1)))/two]
end function c_to_h_noparam

<Muli interactions: public>+≡
public :: c_to_h_param_def

<Muli interactions: procedures>+≡
pure function c_to_h_param_def (cart)
  real(default), dimension(3) :: c_to_h_param_def
  real(default), dimension(3), intent(in) :: cart
  if (product (cart(1:2)) >= pts2_scale) then
    c_to_h_param_def = c_to_h_param ([cart(1), cart(2), pts2_scale])
  else
    c_to_h_param_def = [-one, -one, -one]
  end if
end function c_to_h_param_def

<Muli interactions: public>+≡
public :: h_to_c_smooth

<Muli interactions: procedures>+≡
pure function h_to_c_smooth (hyp)
  real(default), dimension(3) :: h_to_c_smooth
  real(default), dimension(3), intent(in) :: hyp
  real(default) :: h2
  h2 = (((hyp(2) - 5E-1_default)**3) * 4._default + hyp(2)-5E-1_default) &
    / two
  h_to_c_smooth = &
    [sqrt (sqrt (((hyp(1)**4)*(one-hyp(3)))+hyp(3)**2+h2**2) - h2), &
    sqrt (sqrt (((hyp(1)**4)*(one-hyp(3)))+hyp(3)**2+h2**2) + h2), &
    hyp(3)]
end function h_to_c_smooth

<Muli interactions: public>+≡
public :: c_to_h_smooth

<Muli interactions: procedures>+≡
pure function c_to_h_smooth (cart)
  real(default), dimension(3) :: c_to_h_smooth
  real(default), dimension(3), intent(in) :: cart
  c_to_h_smooth = &
    [((product (cart(1:2)) - cart(3)) / (one - cart(3)))*(1/four), &

```

```

        (three-three**(two/3) / (-9._default * cart(1)**2 + &
        9._default * cart(2)**2 + sqrt (three + 81._default * &
        (cart(1)**2 - cart(2)**2)**2)**(one/three)&
        + 3**(one/3)*(-9._default * cart(1)**2 + 9._default*cart(2)**2 &
        + sqrt(three + 81._default*(cart(1)**2&
        - cart(2)**2)**2)**(one/3))/6._default, cart(3)]
end function c_to_h_smooth

<Muli interactions: public>+≡
    public :: h_to_c_smooth_def

<Muli interactions: procedures>+≡
    pure function h_to_c_smooth_def (hyp)
        real(default), dimension(3) :: h_to_c_smooth_def
        real(default), dimension(3), intent(in) :: hyp
        h_to_c_smooth_def = h_to_c_smooth ([hyp(1), hyp(2), pts2_scale])
    end function h_to_c_smooth_def

<Muli interactions: public>+≡

<Muli interactions: procedures>+≡
    pure function c_to_h_smooth_def (cart)
        real(default), dimension(3)::c_to_h_smooth_def
        real(default), dimension(3), intent(in) :: cart
        if (product (cart(1:2)) >= pts2_scale) then
            c_to_h_smooth_def = c_to_h_smooth ([cart(1), cart(2), pts2_scale])
        else
            c_to_h_smooth_def = [-one, -one, -one]
        end if
    end function c_to_h_smooth_def

<Muli interactions: public>+≡
    public :: voxel_h_to_c_ort

<Muli interactions: procedures>+≡
    pure function voxel_h_to_c_ort (hyp)
        real(default) :: voxel_h_to_c_ort
        real(default), dimension(3), intent(in) :: hyp
        real(default) :: T, TH1
        T = one - hyp(3)
        TH1 = T * (one - hyp(1))
        voxel_h_to_c_ort = sqrt (T**2 / (five - four*(one-hyp(2))*hyp(2) - &
            four*(two-TH1)*TH1))
    end function voxel_h_to_c_ort

<Muli interactions: public>+≡
    public :: voxel_c_to_h_ort

<Muli interactions: procedures>+≡
    pure function voxel_c_to_h_ort(cart)
        real(default) :: voxel_c_to_h_ort
        real(default), dimension(3), intent(in) :: cart
        real(default) :: P
        P = product (cart(1:2))

```



```

        if (P > cart(3)) then
            voxel_c_to_h_ort = (cart(1)**2 + cart(2)**2) / (one - cart(3))
        else
            voxel_c_to_h_ort = zero
        end if
    end function voxel_c_to_h_ort

<Muli interactions: public>+≡
    public :: voxel_h_to_c_noparam

<Muli interactions: procedures>+≡
    pure function voxel_h_to_c_noparam (hyp)
        real(default) :: voxel_h_to_c_noparam
        real(default), dimension(3), intent(in) :: hyp
        voxel_h_to_c_noparam = 12._default * sqrt ((hyp(1)**6 * &
            (one - two*hyp(2))**4) / (4*hyp(1)**8 + (one - two*hyp(2))**6))
    end function voxel_h_to_c_noparam

<Muli interactions: public>+≡
    public :: voxel_c_to_h_noparam

<Muli interactions: procedures>+≡
    pure function voxel_c_to_h_noparam (cart)
        real(default) :: voxel_c_to_h_noparam
        real(default), dimension(3), intent(in) :: cart
        real(default) :: P
        voxel_c_to_h_noparam = (cart(1)**2 + cart(2)**2) / (12._default * &
            (cart(1)*cart(2))**(three/four) * &
            (cart(2)**2 + cart(1)**2)**(two/three))
    end function voxel_c_to_h_noparam

<Muli interactions: public>+≡
    public :: voxel_h_to_c_param

<Muli interactions: procedures>+≡
    pure function voxel_h_to_c_param (hyp)
        real(default) :: voxel_h_to_c_param
        real(default), dimension(3), intent(in) :: hyp
        voxel_h_to_c_param = 12*Sqrt((hyp(1)**6 * &
            (one - 2._default*hyp(2))**4 * (hyp(3) - one)**2) / &
            ((one - two * hyp(2))**6 + four * &
            (hyp(3)-(hyp(1)**4*(hyp(3)-one))**2))
    end function voxel_h_to_c_param

<Muli interactions: public>+≡
    public :: voxel_c_to_h_param

<Muli interactions: procedures>+≡
    pure function voxel_c_to_h_param (cart)
        real(default)::voxel_c_to_h_param
        real(default), dimension(3), intent(in) :: cart
        real(default) :: P, T, CP, CM
        P = product (cart(1:2))
        if (P > cart(3)) then

```

```

    P = P - cart(3)
    CP = cart(1)**2 + cart(2)**2
    CM = abs(cart(2)**2 - cart(1)**2)
    T = 1 - cart(3)
    voxel_c_to_h_param = (Cp*sqrt(sqrt(P/T))) / (12*CM**(two/three)*P)
else
    voxel_c_to_h_param = zero
end if
end function voxel_c_to_h_param

```

<Muli interactions: public>+≡

```
public :: voxel_h_to_c_smooth
```

<Muli interactions: procedures>+≡

```

pure function voxel_h_to_c_smooth (hyp)
  real(default) :: voxel_h_to_c_smooth
  real(default), dimension(3), intent(in) :: hyp
  real(default) :: T
  T = one - hyp(3)
  voxel_h_to_c_smooth = 8._default * (hyp(1)**3 * (one + three * &
    (hyp(2) - one)*hyp(2))*T) / sqrt ((one - two*hyp(2) * (two + &
    hyp(2)*(two*hyp(2)-three))**2 + &
    four * (one + (hyp(1)**4 - one)*T)**2)
end function voxel_h_to_c_smooth

```

<Muli interactions: public>+≡

```
public :: voxel_c_to_h_smooth
```

<Muli interactions: procedures>+≡

```

pure function voxel_c_to_h_smooth (cart)
  real(default) :: voxel_c_to_h_smooth
  real(default), dimension(3), intent(in) :: cart
  real(default) :: P, S, T, CM, CP
  P = product (cart(1:2))
  if (P > cart(3)) then
    P = P - cart(3)
    CP = cart(1)**2 + cart(2)**2
    CM = cart(2)**2 - cart(1)**2
    T = 1 - cart(3)
    S = sqrt(three + 81._default*cm**2)
    voxel_c_to_h_smooth = (three**(one/three) * Cp*(three**(one/three) + &
      (9._default*CM + S)**(two/three)) * sqrt (sqrt (P/T))) / &
      (four * P * S * (9._default * CM + S)**(one/three))
  else
    voxel_c_to_h_smooth = zero
  end if
end function voxel_c_to_h_smooth

```

<Muli interactions: public>+≡

```
public :: voxel_h_to_c_ort_def
```

<Muli interactions: procedures>+≡

```

pure function voxel_h_to_c_ort_def (hyp)
  real(default) :: voxel_h_to_c_ort_def

```

```

        real(default), dimension(3), intent(in) :: hyp
        voxel_h_to_c_ort_def = voxel_h_to_c_ort (hyp)
    end function voxel_h_to_c_ort_def

<Muli interactions: public>+≡
    public :: voxel_c_to_h_ort_def

<Muli interactions: procedures>+≡
    pure function voxel_c_to_h_ort_def (cart)
        real(default) :: voxel_c_to_h_ort_def
        real(default), dimension(3), intent(in) :: cart
        voxel_c_to_h_ort_def = voxel_c_to_h_ort (cart)
    end function voxel_c_to_h_ort_def

<Muli interactions: public>+≡
    public :: voxel_h_to_c_param_def

<Muli interactions: procedures>+≡
    pure function voxel_h_to_c_param_def (hyp)
        real(default) :: voxel_h_to_c_param_def
        real(default), dimension(3), intent(in) :: hyp
        voxel_h_to_c_param_def = voxel_h_to_c_param (hyp)
    end function voxel_h_to_c_param_def

<Muli interactions: public>+≡
    public :: voxel_c_to_h_param_def

<Muli interactions: procedures>+≡
    pure function voxel_c_to_h_param_def (cart)
        real(default) :: voxel_c_to_h_param_def
        real(default), dimension(3), intent(in) :: cart
        voxel_c_to_h_param_def = voxel_c_to_h_param (cart)
    end function voxel_c_to_h_param_def

<Muli interactions: public>+≡
    public :: voxel_h_to_c_smooth_def

<Muli interactions: procedures>+≡
    pure function voxel_h_to_c_smooth_def (hyp)
        real(default) :: voxel_h_to_c_smooth_def
        real(default), dimension(3), intent(in) :: hyp
        voxel_h_to_c_smooth_def = voxel_h_to_c_smooth (hyp)
    end function voxel_h_to_c_smooth_def

<Muli interactions: public>+≡
    public :: voxel_c_to_h_smooth_def

<Muli interactions: procedures>+≡
    pure function voxel_c_to_h_smooth_def (cart)
        real(default) :: voxel_c_to_h_smooth_def
        real(default), dimension(3), intent(in) :: cart
        voxel_c_to_h_smooth_def = voxel_c_to_h_smooth (cart)
    end function voxel_c_to_h_smooth_def

```

```

<Muli interactions: public>+≡
  public :: denom_cart

<Muli interactions: procedures>+≡
  pure function denom_cart (cart)
    real(default) :: denom_cart
    real(default), dimension(3), intent(in) :: cart
    denom_cart = 1._default / (864._default * sqrt (cart(3)**3 * &
      (1._default - cart(3) / product(cart(1:2)))))
  end function denom_cart

<Muli interactions: public>+≡
  public :: denom_ort

<Muli interactions: procedures>+≡
  pure function denom_ort (hyp)
    real(default) :: denom_ort
    real(default), dimension(3), intent(in) :: hyp
    real(default) :: Y, P
    Y = (one - two * hyp(2))**2
    P = one - hyp(3)
    if (hyp(1) > zero .and. hyp(3) > zero) then
      denom_ort = sqrt ((P + (-1 + Hyp(1))*P**2) / &
        (746496*hyp(1)*hyp(3)**3 * (4*(1 + (-1 + hyp(1))*P)**2 + Y)))
    else
      denom_ort = zero
    end if
  end function denom_ort

<Muli interactions: public>+≡
  public :: denom_param

<Muli interactions: procedures>+≡
  pure function denom_param (hyp)
    real(default) :: denom_param
    real(default), dimension(3), intent(in) :: hyp
    real(default) :: X, Y, P
    X = hyp(1)**4
    Y = 1._default - 2._default * hyp(2)
    P = 1._default - hyp(3)
    if (hyp(3) > 0._default) then
      denom_param = sqrt ((P * (1+P*(X-1)) * Sqrt(X)*Y**4) / &
        (5184*(4*(1+P*(X-1))**2+Y**6)*hyp(3)**3))
    else
      denom_param = zero
    end if
  end function denom_param

<Muli interactions: public>+≡
  public :: denom_param_reg

<Muli interactions: procedures>+≡
  pure function denom_param_reg (hyp)
    real(default) :: denom_param_reg

```

```

real(default), dimension(3), intent(in) :: hyp
real(default) :: X, Y, P
X = hyp(1)**4
Y = one - two * hyp(2)
P = one - hyp(3)
if (hyp(3) > zero) then
    denom_param_reg = sqrt ((P*(1+P*(X-1)) * Sqrt(X)*Y**4) / &
        (5184*(4*(1+P*(X-1))**2+Y**6) * (hyp(3) + norm2_p_t_0)**3))
else
    denom_param_reg = zero
end if
end function denom_param_reg

```

<Multi interactions: public>+≡
public :: denom_smooth

<Multi interactions: procedures>+≡
pure function denom_smooth (hyp)
real(default) :: denom_smooth
real(default), dimension(3), intent(in) :: hyp
real(default) :: X, Y, P
X = hyp(1)**2
Y = (one - two * hyp(2))**2
P = one - hyp(3)
if (hyp(3) > zero) then
 denom_smooth = sqrt ((P * X * (one + P*(-one + X**2)) * &
 (1 + three*Y)**2)/(46656*hyp(3)**3 &
 (16(1 + P*(-1 + X**2))**2 + Y + 2*Y**2 + Y**3)))
else
 denom_smooth = zero
end if
end function denom_smooth

<Multi interactions: public>+≡
public :: denom_smooth_reg

<Multi interactions: procedures>+≡
pure function denom_smooth_reg (hyp)
real(default) :: denom_smooth_reg
real(default), dimension(3), intent(in) :: hyp
real(default) :: X, Y, P
X = hyp(1)**2
Y = (one - two * hyp(2))**2
P = one - hyp(3)
if (hyp(3) > zero) then
 denom_smooth_reg = sqrt ((P * X * (1 + P*(-1 + X**2)) * &
 (1 + 3*Y)**2)/(46656*(hyp(3) + norm2_p_t_0)**3 * &
 (16 * (1 + P*(-1 + X**2))**2 + Y + 2*Y**2 + Y**3)))
else
 denom_smooth_reg = zero
end if
end function denom_smooth_reg

```

<Muli interactions: public>+≡
  public :: denom_cart_save

<Muli interactions: procedures>+≡
  pure function denom_cart_save (cart)
    real(default) :: denom_cart_save
    real(default), dimension(3), intent(in) :: cart
    if (product(cart(1:2)) > cart(3)) then
      denom_cart_save = denom_cart (cart)
    else
      denom_cart_save = zero
    end if
  end function denom_cart_save

```

```

<Muli interactions: public>+≡
  public :: denom_ort_save

<Muli interactions: procedures>+≡
  pure function denom_ort_save (hyp)
    real(default) :: denom_ort_save
    real(default), dimension(3), intent(in) :: hyp
    real(default) :: Y, Z, W
    real(default), dimension(3) :: cart
    cart = h_to_c_ort (hyp)
    if (cart(1) > one .or. cart(2) > one) then
      denom_ort_save = zero
    else
      denom_ort_save = denom_ort (hyp)
    end if
  end function denom_ort_save

```

```

<Muli interactions: public>+≡
  public :: denom_param_save

<Muli interactions: procedures>+≡
  pure function denom_param_save (hyp)
    real(default) :: denom_param_save
    real(default), dimension(3), intent(in) :: hyp
    real(default) :: Y, Z, W
    real(default), dimension(3) :: cart
    cart=h_to_c_param (hyp)
    if (cart(1) > one .or. cart(2) > one) then
      denom_param_save = zero
    else
      denom_param_save = denom_param (hyp)
    end if
  end function denom_param_save

```

```

<Muli interactions: public>+≡
  public :: denom_smooth_save

<Muli interactions: procedures>+≡
  pure function denom_smooth_save (hyp)
    real(default) :: denom_smooth_save

```

```

real(default), dimension(3), intent(in) :: hyp
real(default) :: Y, Z, W
real(default), dimension(3) :: cart
cart = h_to_c_smooth (hyp)
if (cart(1) > one .or. cart(2) > one) then
    denom_smooth_save = zero
else
    denom_smooth_save = denom_smooth (hyp)
end if
end function denom_smooth_save

```

<Muli interactions: public>+≡

```
public :: denom_cart_cuba_int
```

<Muli interactions: procedures>+≡

```

subroutine denom_cart_cuba_int (d_cart, cart, d_denom, denom, pt2s)
    real(default), dimension(3), intent(in) :: cart
    real(default), dimension(1), intent(out) :: denom
    real(default), intent(in) :: pt2s
    integer, intent(in) :: d_cart, d_denom
    denom(1) = denom_cart_save ([cart(1), cart(2), pt2s])
end subroutine denom_cart_cuba_int

```

<Muli interactions: public>+≡

```
public :: denom_ort_cuba_int
```

<Muli interactions: procedures>+≡

```

subroutine denom_ort_cuba_int (d_hyp, hyp, d_denom, denom, pt2s)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(1), intent(out) :: denom
    real(default), intent(in) :: pt2s
    integer, intent(in) :: d_hyp, d_denom
    denom(1) = denom_ort_save ([hyp(1), hyp(2), pt2s])
end subroutine denom_ort_cuba_int

```

<Muli interactions: public>+≡

```
public :: denom_param_cuba_int
```

<Muli interactions: procedures>+≡

```

subroutine denom_param_cuba_int (d_hyp, hyp, d_denom, denom, pt2s)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(1), intent(out) :: denom
    real(default), intent(in) :: pt2s
    integer, intent(in) :: d_hyp, d_denom
    denom(1) = denom_param_save ([hyp(1), hyp(2), pt2s])
end subroutine denom_param_cuba_int

```

<Muli interactions: public>+≡

```
public :: denom_smooth_cuba_int
```

<Muli interactions: procedures>+≡

```

subroutine denom_smooth_cuba_int (d_hyp, hyp, d_denom, denom, pt2s)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(1), intent(out) :: denom

```

```

    real(default), intent(in) :: pt2s
    integer, intent(in) :: d_hyp, d_denom
    denom(1) = denom_smooth_save ([hyp(1), hyp(2), pt2s])
end subroutine denom_smooth_cuba_int

```

<Muli interactions: public>+≡

```

public :: coordinates_hcd_cart

```

<Muli interactions: procedures>+≡

```

subroutine coordinates_hcd_cart (hyp, cart, denom)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out) :: denom
    cart = hyp
    denom = denom_cart_save (cart)
end subroutine coordinates_hcd_cart

```

<Muli interactions: public>+≡

```

public :: coordinates_hcd_ort

```

<Muli interactions: procedures>+≡

```

subroutine coordinates_hcd_ort (hyp, cart, denom)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out)::denom
    cart = h_to_c_ort (hyp)
    denom = denom_ort (hyp)
end subroutine coordinates_hcd_ort

```

<Muli interactions: public>+≡

```

public :: coordinates_hcd_param

```

<Muli interactions: procedures>+≡

```

subroutine coordinates_hcd_param (hyp, cart, denom)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out) :: denom
    cart = h_to_c_param (hyp)
    denom = denom_param (hyp)
end subroutine coordinates_hcd_param

```

<Muli interactions: public>+≡

```

public :: coordinates_hcd_param_reg

```

<Muli interactions: procedures>+≡

```

subroutine coordinates_hcd_param_reg (hyp, cart, denom)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out) :: denom
    cart = h_to_c_param (hyp)
    denom = denom_param_reg (hyp)
end subroutine coordinates_hcd_param_reg

```



```

<Muli interactions: public>+≡
  public :: coordinates_hcd_smooth

<Muli interactions: procedures>+≡
  subroutine coordinates_hcd_smooth (hyp, cart, denom)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out) :: denom
    cart = h_to_c_smooth (hyp)
    denom = denom_smooth (hyp)
  end subroutine coordinates_hcd_smooth

<Muli interactions: public>+≡
  public :: coordinates_hcd_smooth_reg

<Muli interactions: procedures>+≡
  subroutine coordinates_hcd_smooth_reg (hyp, cart, denom)
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default), intent(out) :: denom
    cart = h_to_c_smooth (hyp)
    denom = denom_smooth_reg (hyp)
  end subroutine coordinates_hcd_smooth_reg

<Muli interactions: public>+≡
  public :: interactions_dddsigma_reg

<Muli interactions: procedures>+≡
  pure subroutine interactions_dddsigma_reg &
    (process_id, double_pdf_id, hyp, cart, dddsigma)
    real(default), intent(out) :: dddsigma
    integer, intent(in) :: process_id, double_pdf_id
    real(default), dimension(3), intent(in) :: hyp
    real(default), dimension(3), intent(out) :: cart
    real(default) :: a, pt2shat, gev_pt, gev2_pt
    cart = h_to_c_param (hyp)
    a = product (cart(1:2))
    if (cart(1) <= 1D0 .and. cart(2) <= 1D0) then
      pt2shat = hyp(3) / a
      gev_pt = sqrt(hyp(3)) * gev_pt_max
      gev2_pt = hyp(3) * gev2_pt_max
      ! print *,process_id,pt2shat
      dddsigma = &
        const_pref &
        * alphasPDF (dble (sqrt (gev2_pt+gev2_p_t_0)))*2 &
        * ps_io_pol (process_id, pt2shat) &
        * pdf_in_in_kind &
        (process_id, double_pdf_id, cart(1), cart(2), gev_pt) &
        * denom_param_reg (hyp) / a
    else
      dddsigma = zero
    end if
  end subroutine interactions_dddsigma_reg

```

```

<Muli interactions: public>+≡
  public :: pdf_in_in_kind

<Muli interactions: procedures>+≡
  pure function pdf_in_in_kind (process_id, double_pdf_id, c1, c2, gev_pt)
    real(default) :: pdf_in_in_kind
    real(default), intent(in) :: c1, c2, gev_pt
    integer, intent(in) :: process_id, double_pdf_id
    real(default) :: pdf1, pdf2
    call single_pdf (valid_processes(1, process_id), &
      double_pdf_kinds(1, double_pdf_id), c1, gev_pt, pdf1)
    call single_pdf (valid_processes(2, process_id), &
      double_pdf_kinds(2, double_pdf_id), c2, gev_pt, pdf2)
    pdf_in_in_kind = pdf1 * pdf2
  contains
    pure subroutine single_pdf (flavor, pdf_kind, c, gev_pt, pdf)
      integer, intent(in) :: flavor, pdf_kind
      real(default), intent(in) :: c, gev_pt
      real(default), intent(out) :: pdf
      real(double), dimension(-6:6) :: lha_pdf
      call evolvePDF (dble (c), dble (gev_pt), lha_pdf)
      select case (pdf_kind)
      case (1)
        pdf = lha_pdf (0)
      case (2)
        if (flavor==1 .or. flavor==2) then
          pdf = lha_pdf (-flavor)
        else
          pdf = lha_pdf (flavor)
        end if
      case (3)
        pdf = lha_pdf(1) - lha_pdf(-1)
      case (4)
        pdf = lha_pdf(2) - lha_pdf(-2)
      end select
    end subroutine single_pdf
  end function pdf_in_in_kind

<Muli interactions: public>+≡
  public :: ps_io_pol

<Muli interactions: procedures>+≡
  elemental function ps_io_pol (process_io_id, pt2shat)
    real(default) :: ps_io_pol
    integer, intent(in) :: process_io_id
    real(default), intent(in) :: pt2shat
    ps_io_pol = dot_product([1._default, pt2shat, pt2shat**2, pt2shat**3], &
      phase_space_coefficients_inout (1:4, &
        valid_processes (6, process_io_id)))
  end function ps_io_pol

<Muli interactions: public>+≡
  public :: interactions_dddsigma

```

<Muli interactions: procedures>+≡

```

pure subroutine interactions_dddsigma &
  (process_id, double_pdf_id, hyp, cart, dddsigma)
  real(default), intent(out) :: dddsigma
  integer, intent(in) :: process_id, double_pdf_id
  real(default), dimension(3), intent(in) :: hyp
  real(default), dimension(3), intent(out) :: cart
  real(default) :: a, pt2shat, gev_pt
  cart = h_to_c_param (hyp)
  a = product (cart(1:2))
  if (cart(1) <= 1._default .and. cart(2) <= 1._default) then
    pt2shat = hyp(3) / a
    gev_pt = sqrt(hyp(3)) * gev_pt_max
    ! print *,process_id,pt2shat
    dddsigma = const_pref * &
      alphasPDF (dble (gev_pt))**2 * &
      ps_io_pol (process_id, pt2shat) * &
      pdf_in_in_kind &
      (process_id, double_pdf_id, cart(1), cart(2), gev_pt) * &
      denom_param(hyp) / a
  else
    dddsigma = zero
  end if
end subroutine interactions_dddsigma

```

<Muli interactions: public>+≡

```

public :: interactions_dddsigma_print

```

<Muli interactions: procedures>+≡

```

subroutine interactions_dddsigma_print &
  (process_id, double_pdf_id, hyp, cart, dddsigma)
  real(default), intent(out) :: dddsigma
  integer, intent(in) :: process_id, double_pdf_id
  real(default), dimension(3), intent(in) :: hyp
  real(default), dimension(3), intent(out) :: cart
  real(default) :: a, pt2shat, gev_pt
  cart = h_to_c_param (hyp)
  a = product (cart(1:2))
  if (cart(1) <= 1._default .and. cart(2) <= 1._default) then
    pt2shat = hyp(3) / a
    gev_pt=sqrt(hyp(3))*gev_pt_max
    ! print *,process_id,pt2shat
    dddsigma = const_pref * &
      ! alphasPDF(dble (gev_pt))**2 * &
      ps_io_pol (process_id, pt2shat) * &
      pdf_in_in_kind &
      (process_id, double_pdf_id, cart(1), cart(2), gev_pt) * &
      denom_param (hyp) / a
  else
    dddsigma = zero
  end if
  write(11, *) dddsigma, pt2shat, &
    pdf_in_in_kind (process_id, double_pdf_id, cart(1), cart(2), &
      gev_pt), ps_io_pol (process_id, pt2shat), const_pref, &

```

```

        denom_param(hyp), a
    flush(11)
end subroutine interactions_dddsigma_print

```

<Muli interactions: public>+≡

```

    public :: interactions_dddsigma_cart

```

<Muli interactions: procedures>+≡

```

    pure subroutine interactions_dddsigma_cart &
        (process_id, double_pdf_id, cart, dddsigma)
        real(default), intent(out) :: dddsigma
        integer, intent(in) :: process_id, double_pdf_id
        real(default), dimension(3), intent(in) :: cart
        real(default) :: a, pt2shat, gev_pt
        a = product (cart(1:2))
        if (cart(1) <= one .and. cart(2) <= one) then
            pt2shat = cart(3) / a
            gev_pt = sqrt(cart(3)) * gev_pt_max
            ! print *,process_id,pt2shat
            dddsigma = const_pref * &
                alphasPDF (dble (gev_pt))*2 * &
                ps_io_pol (process_id, pt2shat) * &
                pdf_in_in_kind &
                (process_id, double_pdf_id, cart(1), cart(2), gev_pt) * &
                denom_cart (cart) / a
        else
            dddsigma = zero
        end if
    end subroutine interactions_dddsigma_cart

```

<Muli interactions: public>+≡

```

    public :: cuba_gg_me_smooth

```

<Muli interactions: procedures>+≡

```

    subroutine cuba_gg_me_smooth (d_hyp, hyp, d_me, me, pt2s)
        integer, intent(in) :: d_hyp, d_me
        real(default), dimension(d_hyp), intent(in) :: hyp
        real(default), dimension(1), intent(out) :: me
        real(default), dimension(3) :: cart
        real(default), intent(in) :: pt2s
        real(default) :: p, p2
        if (d_hyp == 3) then
            p = hyp(3)
            p2 = hyp(3)**2
        else
            if (d_hyp == 2) then
                p = sqrt (pt2s)
                p2 = pt2s
            end if
        end if
        cart = h_to_c_smooth ([hyp(1), hyp(2), p2])
        if (p > pts_min .and. product (cart(1:2)) > p2) then
            me(1) = const_pref * &
                alphasPDF (dble (p*gev_pt_max))*2 * &

```

```

        ps_io_pol (109, p2) * &
        pdf_in_in_kind (109, 11, cart(1), cart(2), p2) * &
        denom_smooth ([hyp(1), hyp(2), p2]) / product (cart(1:2))
    else
        me(1) = zero
    end if
end subroutine cuba_gg_me_smooth

```

<Multi interactions: public>+≡

```
public :: cuba_gg_me_param
```

<Multi interactions: procedures>+≡

```

subroutine cuba_gg_me_param (d_hyp, hyp, d_me, me, pt2s)
    integer, intent(in)::d_hyp,d_me
    real(default), dimension(d_hyp), intent(in) :: hyp
    real(default), dimension(1), intent(out) :: me
    real(default), dimension(3) :: cart
    real(default), intent(in) :: pt2s
    real(default) :: p, p2
    if (d_hyp == 3) then
        p = hyp(3)
        p2 = hyp(3)**2
    else
        if (d_hyp == 2) then
            p = sqrt (pt2s)
            p2 = pt2s
        end if
    end if
    cart = h_to_c_param ([hyp(1), hyp(2), p2])
    if (p>pts_min .and. product (cart(1:2))>p2) then
        me(1) = const_pref * &
            alphasPDF(dble (p*gev_pt_max))**2 * &
            ps_io_pol (109, p2) * &
            pdf_in_in_kind (109, 11, cart(1), cart(2), p2) * &
            denom_param ([hyp(1), hyp(2), p2]) / product(cart(1:2))
    else
        me(1) = zero
    end if
end subroutine cuba_gg_me_param

```

<Multi interactions: public>+≡

```
public :: cuba_gg_me_ort
```

<Multi interactions: procedures>+≡

```

subroutine cuba_gg_me_ort (d_hyp, hyp, d_me, me, pt2s)
    integer, intent(in) :: d_hyp, d_me
    real(default), dimension(d_hyp), intent(in) :: hyp
    real(default), dimension(1), intent(out) :: me
    real(default), dimension(3) :: cart
    real(default), intent(in) :: pt2s
    real(default) :: p, p2
    if (d_hyp == 3) then
        p = hyp(3)
        p2 = hyp(3)**2
    end if

```

```

else
  if (d_hyp == 2) then
    p = sqrt(pt2s)
    p2 = pt2s
  end if
end if
cart = h_to_c_ort ([hyp(1), cart(2), p2])
if (p > pts_min .and. product (cart(1:2)) > p2) then
  me(1) = const_pref * &
    alphasPDF(dble (p*gev_pt_max))**2 * &
    ps_io_pol (109, p2) * &
    pdf_in_in_kind (109, 11, cart(1), cart(2), p2) * &
    denom_ort ([hyp(1), hyp(2), p2]) / product (cart(1:2))
else
  me(1) = zero
end if
end subroutine cuba_gg_me_ort

```

<Multi interactions: public>+≡

```
public :: cuba_gg_me_cart
```

<Multi interactions: procedures>+≡

```

subroutine cuba_gg_me_cart (d_cart, cart, d_me, me, pt2s)
  integer, intent(in) :: d_cart, d_me
  real(default), dimension(d_cart), intent(in) :: cart
  real(default), dimension(1), intent(out) :: me
  real(default), intent(in) :: pt2s
  real(default) :: a, p, p2
  if (d_cart == 3) then
    p = cart(3)
    p2 = cart(3)**2
  else
    if (d_cart == 2) then
      p = sqrt (pt2s)
      p2 = pt2s
    end if
  end if
  a = product (cart(1:2))
  if (p > pts_min .and. a > p2) then
    me(1) = const_pref * &
      alphasPDF (dble (p*gev_pt_max))**2 * &
      ps_io_pol (109, p2) * &
      pdf_in_in_kind (109, 11, cart(1), cart(2), p2) * &
      denom_cart ([cart(1), cart(2), p2]) / a
  else
    me(1) = zero
  end if
end subroutine cuba_gg_me_cart

```

<Multi interactions: public>+≡

```
public :: interactions_proton_proton_integrand_generic_17_reg
```

<Multi interactions: procedures>+≡

```
subroutine interactions_proton_proton_integrand_generic_17_reg &
```

```

(hyp_2, trafo, f, pt)
real(default), dimension(2), intent(in) :: hyp_2
procedure(coord_hcd_in) :: trafo
real(default), dimension(17), intent(out) :: f
class(transverse_mom_t), intent(in) :: pt
real(default), dimension(3) :: cart, hyp_3
real(default), dimension(5) :: psin
real(double), dimension(-6:6) :: c_dble, d_dble
real(default), dimension(-6:6) :: c, d
real(default) :: gev_pt, gev2_pt, pts, pt2s, pt2shat, a, &
    pdf_seaquark_seaquark, pdf_seaquark_gluon, pdf_gluon_gluon, &
    pdf_up_seaquark, pdf_up_gluon, pdf_down_seaquark, pdf_down_gluon, &
    v1u, v1d, v2u, v2d, denom

pts = pt%get_unit_scale()
pt2s = pt%get_unit2_scale()
gev_pt = pt%get_gev_scale()
gev2_pt = pt%get_gev2_scale()

hyp_3(1:2) = hyp_2
hyp_3(3) = pt2s
call trafo (hyp_3, cart, denom)
a = product (cart(1:2))
if (cart(1) <= one .and. cart(2) <= one .and. a > pt2s) then
    pt2shat = pt2s / a
    ! phase space polynom
    psin = matmul ([one, pt2shat, pt2shat**2, pt2shat**3], &
        phase_space_coefficients_in)
    ! pdf
    call evolvepdf (dble (cart(1)), dble (gev_pt), c_dble)
    call evolvepdf (dble (cart(2)), dble (gev_pt), d_dble)
    c = c_dble
    d = d_dble
    ! c = [1,1,1,1,1,1,1,1,1,1,1,1,1,1,1]*1D0
    ! d = c
    v1d = c(1) - c(-1)
    v1u = c(2) - c(-2)
    v2d = d(1) - d(-1)
    v2u = d(2) - d(-2)
    c(1) = c(-1)
    c(2) = c(-2)
    d(1) = d(-1)
    d(2) = d(-2)
    f(1) = zero
    !!! gluon_gluon
    f( 2) = (c(0)*d(0)) * psin(5)
    !!! type5
    !!! gluon_seaquark
    f( 3) = (c(0)*d(-4) + c(0)*d(-3) + c(0)*d(-2) + c(0)*d(-1) + &
        c(0)*d(1) + c(0)*d(2) + c(0)*d(3) + c(0)*d(4)) * psin(4)
    !!! type4
    !!! gluon_down
    f( 4) = (c(0)*v2d) * psin(4)
    !!! type4

```

```

!!! gluon_up
f( 5) = (c(0)*v2u) * psin(4)
      !!! type4
!!! seaquark_gluon
f( 6) = (c(-4)*d(0) + c(-3)*d(0) + c(-2)*d(0) + c(-1)*d(0) + &
        c(1)*d(0) + c(2)*d(0) + c(3)*d(0) + c(4)*d(0)) * psin(4)
      !!! type4
!!! seaquark_seaquark
f( 7) = &
      !!! type1
        (c(-4)*d(-3) + c(-4)*d(-2) + c(-4)*d(-1) + c(-4)*d( 1) + &
        c(-4)*d( 2) + c(-4)*d( 3) + c(-3)*d(-4) + c(-3)*d(-2) + &
        c(-3)*d(-1) + c(-3)*d( 1) + c(-3)*d( 2) + c(-3)*d( 4) + &
        c(-2)*d(-4) + c(-2)*d(-3) + c(-2)*d(-1) + c(-2)*d( 1) + &
        c(-2)*d( 3) + c(-2)*d( 4) + c(-1)*d(-4) + c(-1)*d(-3) + &
        c(-1)*d(-2) + c(-1)*d( 2) + c(-1)*d( 3) + c(-1)*d( 4) + &
        c( 1)*d(-4) + c( 1)*d(-3) + c( 1)*d(-2) + c( 1)*d( 2) + &
        c( 1)*d( 3) + c( 1)*d( 4) + c( 2)*d(-4) + c( 2)*d(-3) + &
        c( 2)*d(-1) + c( 2)*d( 1) + c( 2)*d( 3) + c( 2)*d( 4) + &
        c( 3)*d(-4) + c( 3)*d(-2) + c( 3)*d(-1) + c( 3)*d( 1) + &
        c( 3)*d( 2) + c( 3)*d( 4) + c( 4)*d(-3) + c( 4)*d(-2) + &
        c( 4)*d(-1) + c( 4)*d( 1) + c( 4)*d( 2) + c( 4)*d( 3)) * &
        psin(1) + &
      !!! type2
        (c(-4)*d(-4) + c(-3)*d(-3) + c(-2)*d(-2) + c(-1)*d(-1) + &
        c( 4)*d( 4) + c( 3)*d( 3) + c(2)*d( 2) + c(1)*d( 1)) * &
        psin(2) + &
      !!! type3
        (c(-4)*d( 4) + c(-3)*d( 3) + c(-2)*d( 2) + c(-1)*d( 1) + &
        c( 4)*d(-4) + c( 3)*d(-3) + c(2)*d(-2) + c(1)*d(-1)) * &
        psin(3)
!!! seaquark_down
f( 8) = &
      !!! type1
        (c(-4)*v2d + c(-3)*v2d + c(-2)*v2d + c( 2)*v2d + &
        c( 3)*v2d + c( 4)*v2d) * psin(1) + &
      !!! type2
        c( 1)*v2d * psin(2) + &
      !!! type3
        c(-1)*v2d * psin(3)
!!! seaquark_up
f( 9) = &
      !!! type1
        (c(-4)*v2u + c(-3)*v2u + c(-1)*v2u + c( 1)*v2u + &
        c( 3)*v2u + c( 4)*v2u) * psin(1) + &
      !!! type2
        c(2)*v2u * psin(2) + &
      !!! type3
        c(-2)*v2u * psin(3)
!!! down_gluon
f(10) = (v1d*d( 0)) * psin(4)
      !!! type4
!!! down_seaquark
f(11) = &

```



```

      !!! type1
      (v1d*d(-4) + v1d*d(-3) + v1d*d(-2) + v1d*d( 2) + &
      v1d*d( 3) + v1d*d( 4)) * psin(1) + &
      !!! type2
      v1d*d( 1) * psin(2) + &
      !!! type3
      v1d*d(-1) * psin(3)
      !!! down_down
      f(12) = v1d*v2d * psin(2)
      !!! down_up
      f(13) = v1d*v2u * psin(1)
      !!! up_gluon
      f(14) = (v1u*d(0)) * psin(4)
      !!! type4
      !!! up_seaquark
      f(15) = &
      !!! type1
      (v1u*d(-4) + v1u*d(-3) + v1u*d(-1) + v1u*d( 1) + &
      v1u*d( 3) + v1u*d( 4)) * psin(1) + &
      !!! type2
      v1u*d(2) * psin(2) + &
      !!! type3
      v1u*d(-2) * psin(3)
      !!! up_down
      f(16) = v1u * v2d * psin(1)
      !!! up_up
      f(17) = v1u * v2u * psin(2)
      f=f * const_pref &
      * alphasPDF (dble (sqrt(gev2_pt+gev2_p_t_0)))*2 &
      * denom / a
      ! print *, const_pref, alphasPDF(gev_pt)**2, denom_smooth (hyp), a
    else
      f = [zero, zero, zero, zero, zero, zero, zero, zero, zero, &
      zero, zero, zero, zero, zero, zero, zero, zero, zero]
    end if
    ! print *, pt2shat, c(0)*d(0), psin(5), const_pref, &
    ! alphasPDF(gev_pt)**2, denom, a
  end subroutine interactions_proton_proton_integrand_generic_17_reg

```

(Multi interactions: procedures)+≡

```

! subroutine coordinates_proton_proton_integrand_cart_11 &
!   (d_hyp, hyp_2, d_f, f)
!   integer, intent(in) :: d_hyp, d_f
!   real(default), dimension(2), intent(in) :: hyp_2
!   real(default), dimension(11), intent(out) :: f
!   call coordinates_proton_proton_integrand_generic_11 &
!     (hyp_2, coordinates_hcd_cart, f)
!   ! write (51,*) hyp_2, momentum_get_pts_scale(), f
! end subroutine coordinates_proton_proton_integrand_cart_11

```

(Multi interactions: procedures)+≡

```

! subroutine coordinates_proton_proton_integrand_ort_11 &
!   (d_hyp, hyp_2, d_f, f)

```

```

!   integer, intent(in) :: d_hyp, d_f
!   real(default), dimension(2), intent(in) :: hyp_2
!   real(default), dimension(11), intent(out) :: f
!   call coordinates_proton_proton_integrand_generic_11 &
!     (hyp_2, coordinates_hcd_ort, f)
!   ! write (52,*) hyp_2, momentum_get_pts_scale(), f
! end subroutine coordinates_proton_proton_integrand_ort_11

```

<Multi interactions: procedures>+≡

```

!   subroutine coordinates_proton_proton_integrand_param_11 &
!     (d_hyp, hyp_2, d_f, f)
!   integer, intent(in) :: d_hyp, d_f
!   real(default), dimension(2), intent(in) :: hyp_2
!   real(default), dimension(11), intent(out) :: f
!   call coordinates_proton_proton_integrand_generic_11 &
!     (hyp_2, coordinates_hcd_param, f)
!   ! write(53,*) hyp_2, momentum_get_pts_scale(), f
! end subroutine coordinates_proton_proton_integrand_param_11

```

<Multi interactions: procedures>+≡

```

!   subroutine coordinates_proton_proton_integrand_smooth_11 &
!     (d_hyp, hyp_2, d_f, f)
!   integer, intent(in)::d_hyp,d_f
!   real(default), dimension(2), intent(in) :: hyp_2
!   real(default), dimension(11), intent(out) :: f
!   call coordinates_proton_proton_integrand_generic_11 (hyp_2, &
!     coordinates_hcd_smooth, f)
!   ! write (54,*) hyp_2, momentum_get_pts_scale(), f
! end subroutine coordinates_proton_proton_integrand_smooth_11

```

<Multi interactions: public>+≡

```

public :: interactions_proton_proton_integrand_param_17_reg

```

<Multi interactions: procedures>+≡

```

subroutine interactions_proton_proton_integrand_param_17_reg &
  (d_hyp, hyp_2, d_f, f, pt)
  integer, intent(in) :: d_hyp, d_f
  real(default), dimension(2), intent(in) :: hyp_2
  real(default), dimension(17), intent(out) :: f
  class(transverse_mom_t), intent(in) :: pt
  call interactions_proton_proton_integrand_generic_17_reg &
    (hyp_2, coordinates_hcd_param_reg, f, pt)
  ! write (53,*) hyp_2,momentum_get_pts_scale(),f
end subroutine interactions_proton_proton_integrand_param_17_reg

```

<Multi interactions: public>+≡

```

public :: interactions_proton_proton_integrand_smooth_17_reg

```

<Multi interactions: procedures>+≡

```

subroutine interactions_proton_proton_integrand_smooth_17_reg &
  (d_hyp, hyp_2, d_f, f, pt)
  integer, intent(in) :: d_hyp, d_f
  real(default), dimension(2), intent(in) :: hyp_2

```

```

real(default), dimension(17), intent(out) :: f
class(transverse_mom_t), intent(in) :: pt
call interactions_proton_proton_integrand_generic_17_reg &
    (hyp_2, coordinates_hcd_smooth_reg, f, pt)
! write (53,*)hyp_2,momentum_get_pts_scale(), f
end subroutine interactions_proton_proton_integrand_smooth_17_reg

```

21.4 VEGAS and CUBA integration routines

This file contains the module `muli_cuba`, a wrapper for the CUBA integration library. Different algorithms and settings have been tried out for the integration, including VEGAS, and this wrapper has been mainly written for that purpose.

```

<muli_cuba.f90>≡
  <File header>

  module muli_cuba

    <Use kinds>
    use constants
    use diagnostics
    use muli_base
    use muli_momentum

    <Standard module head>

    <Muli CUBA: public>

    <Muli CUBA: variables>

    <Muli CUBA: types>

    <Muli CUBA: interfaces>

    contains

    <Muli CUBA: procedures>

  end module muli_cuba

<Muli CUBA: variables>≡
  integer, parameter :: max_maxeval = huge(1)

<Muli CUBA: public>≡
  public :: cuba_class

<Muli CUBA: types>≡
  type, extends (ser_class_t), abstract :: cuba_class
    real(default) :: start_time = zero
    real(default) :: stop_time = zero
    real(default) :: run_time = zero
    integer :: dim_x = 2

```

```

integer :: dim_f = 1
type(transverse_mom_t) :: userdata
real(default) :: eps_rel = 1.E-3_default
real(default) :: eps_abs = 0._default
integer :: flags = 0
integer :: seed = 1
integer :: min_eval = 0
integer :: max_eval = max_maxeval
integer :: neval = 0
integer, public :: fail = -1
integer :: nregions = 0
real(default), dimension(:), allocatable :: integral
real(default), dimension(:), allocatable :: error
real(default), dimension(:), allocatable :: prob
procedure(integrand_interface), nopass, pointer :: integrand
contains
  <Muli CUBA: cuba class: TBP>
end type cuba_class

<Muli CUBA: types>+≡
type, extends (cuba_class) :: cuba_cuhre_t
private
  integer :: key = 13
contains
  <Muli CUBA: cuba_cuhre: TBP>
end type cuba_cuhre_t

<Muli CUBA: types>+≡
type, extends (cuba_class) :: cuba_suave_t
private
  integer :: nnew = 10000      !1000
  integer :: flatness = 5     !50
contains
  <Muli CUBA: cuba suave: TBP>
end type cuba_suave_t

<Muli CUBA: public>+≡
public :: cuba_divonne_t

<Muli CUBA: types>+≡
type, extends (cuba_class) :: cuba_divonne_t
private
  integer :: key1 = 13
  integer :: key2 = 13
  integer :: key3 = 13
  integer :: maxpass = 2
  real(default) :: border = zero
  real(default) :: maxchisq = 10._default
  real(default) :: mindeviation = .25_default
  integer :: ngiven = 0
  integer :: ldxgiven = 0
  ! real(default), dimension(ldxgiven,ngiven) :: &
  !   xgiven = reshape( source = [ 0.0,0.0 ], shape = [2,1])

```

```

        real(default), dimension(:,:), allocatable :: xgiven
        ! real(default), dimension(2) :: xgiven = [1E-1_default, 5E-1_default]
        integer :: nextra = 0
    contains
        <Muli CUBA: cuba divonne: TBP>
    end type cuba_divonne_t

<Muli CUBA: types>+≡
type, extends (cuba_class) :: cuba_vegas_t
private
    integer :: nstart = 500
    integer :: nincrease = 1000
    integer :: nbatch = 1000
    integer :: gridno = 0
    character(len=8), pointer :: statefile => null()
contains
    <Muli CUBA: cuba vegas: TBP>
end type cuba_vegas_t

<Muli CUBA: cuba class: TBP>≡
procedure :: write_to_marker => cuba_write_to_marker

<Muli CUBA: procedures>≡
subroutine cuba_write_to_marker (this, marker, status)
    class(cuba_class), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    call marker%mark_begin ("cuba_class")
    call marker%mark ("dim_x", this%dim_x)
    call marker%mark ("dim_f", this%dim_f)
    call marker%mark ("eps_rel", this%eps_rel)
    call marker%mark ("eps_abs", this%eps_abs)
    call marker%mark ("flags", this%flags)
    call marker%mark ("min_eval", this%min_eval)
    call marker%mark ("max_eval", this%max_eval)
    call marker%mark ("neval", this%neval)
    call marker%mark ("fail", this%fail)
    call marker%mark ("nregions", this%nregions)
    if (allocated (this%integral)) then
        call marker%mark ("integral", this%integral)
    else
        call marker%mark_null ("integral")
    end if
    if (allocated(this%error)) then
        call marker%mark ("error", this%error)
    else
        call marker%mark_null ("error")
    end if
    if (allocated (this%prob)) then
        call marker%mark ("prob", this%prob)
    else
        call marker%mark_null ("prob")
    end if
end if

```

```

    call marker%mark_null ("cuba_class")
end subroutine cuba_write_to_marker

```

(Multi CUBA: cuba class: TBP)+≡

```

    procedure :: read_from_marker => cuba_read_from_marker

```

(Multi CUBA: procedures)+≡

```

subroutine cuba_read_from_marker (this, marker, status)
    class(cuba_class), intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out)::status
    call marker%pick_begin ("CUBA_CLASS", status=status)
    call marker%pick ("dim_x", this%dim_x,status)
    call marker%pick ("dim_f", this%dim_f,status)
    call marker%pick ("eps_rel", this%eps_rel,status)
    call marker%pick ("eps_abs", this%eps_abs,status)
    call marker%pick ("flags", this%flags,status)
    call marker%pick ("min_eval", this%min_eval,status)
    call marker%pick ("max_eval", this%max_eval,status)
    call marker%pick ("neval", this%neval,status)
    call marker%pick ("fail", this%fail,status)
    call marker%pick ("nregions", this%nregions,status)
    call marker%verify_nothing("integral",status)
    if (allocated (this%integral)) deallocate (this%integral)
    if (status == serialize_ok) then
        allocate (this%integral (this%dim_f))
        call marker%pick ("integral", this%integral, status)
    end if
    call marker%verify_nothing ("error", status)
    if (allocated (this%error)) deallocate (this%error)
    if (status == serialize_ok) then
        allocate (this%error (this%dim_f))
        call marker%pick ("error", this%error, status)
    end if
    call marker%verify_nothing ("prob", status)
    if (allocated (this%prob)) deallocate (this%prob)
    if (status == serialize_ok) then
        allocate (this%prob (this%dim_f))
        call marker%pick ("prob", this%prob, status)
    end if
    call marker%pick_end ("cuba_class", status)
end subroutine cuba_read_from_marker

```

(Multi CUBA: cuba class: TBP)+≡

```

    procedure :: print_to_unit => cuba_print_to_unit

```

(Multi CUBA: procedures)+≡

```

subroutine cuba_print_to_unit (this, unit, parents, components, peers)
    class(cuba_class), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    character(11) :: n
    write (n, '(("I2,"(E12.4))")') this%dim_f
    write (unit, "(1x,A)" "Components of cuba_class:"

```

```

write (unit, "(3x,A)" "Parameters:")
write (unit, "(3x,A,I10)" "dim_f: ", this%dim_f
write (unit, "(3x,A,I10)" "dim_x: ", this%dim_x
call this%userdata%print_to_unit (unit, parents, components-1, peers)
write (unit, "(3x,A,E10.4)" "eps_rel: ", this%eps_rel
write (unit, "(3x,A,E10.4)" "eps_abs: ", this%eps_abs
write (unit, "(3x,A,I10)" "flags: ", this%flags
write (unit, "(3x,A,I10)" "seed: ", this%seed
write (unit, "(3x,A,I10)" "min_eval: ", this%min_eval
write (unit, "(3x,A,I10)" "max_eval: ", this%max_eval
write (unit, "(3x,A)" "Results:")
write (unit, "(3x,A,I10)" "neval: ", this%neval
write (unit, "(3x,A,I10)" "fail: ", this%fail
write (unit, "(3x,A)", advance="no") "integral: "
write (unit, fmt=n) this%integral
write (unit, "(3x,A)", advance="no") "error: "
write (unit, fmt=n) this%error
write (unit, "(3x,A)", advance="no") "prob: "
write (unit, fmt=n) this%prob
write (unit, "(3x,A,E10.4)" "time: ", &
      this%stop_time - this%start_time
! write(unit,'("time: ",E10.4)') this%run_time
end subroutine cuba_print_to_unit

```

<Muli CUBA: cuba class: TBP>+≡

```

generic :: get_integral => get_integral_array, get_integral_1
procedure :: get_integral_array => cuba_get_integral_array
procedure :: get_integral_1 => cuba_get_integral_1

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_get_integral_array (this, integral)
class(cuba_class) :: this
real(default), intent(out), dimension(:) :: integral
integral = this%integral
end subroutine cuba_get_integral_array

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_get_integral_1 (this, integral)
class(cuba_class) :: this
real(default), intent(out) :: integral
integral = this%integral(1)
end subroutine cuba_get_integral_1

```

<Muli CUBA: cuba class: TBP>+≡

```

procedure :: copy_common => cuba_copy_common

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_copy_common (this, source)
class(cuba_class), intent(out) :: this
class(cuba_class), intent(in) :: source
this%dim_x = source%dim_x
this%dim_f = source%dim_f
this%eps_rel = source%eps_rel

```

```

    this%eps_abs = source%eps_abs
    this%flags = source%flags
    this%min_eval = source%min_eval
    this%max_eval = source%max_eval
    call this%alloc()
end subroutine cuba_copy_common

```

```

<Muli CUBA: cuba class: TBP>+≡
    procedure :: set_common => cuba_set_common

```

```

<Muli CUBA: procedures>+≡
    subroutine cuba_set_common (this, dim_x, dim_f, eps_rel, eps_abs, &
        flags, seed, min_eval, max_eval, integrand, userdata)
        class(cuba_class), intent(inout) :: this
        integer, intent(in), optional :: dim_x, dim_f, flags, min_eval, &
            max_eval, seed
        real(default), intent(in), optional :: eps_rel, eps_abs
        type(transverse_mom_t), intent(in), optional :: userdata
        procedure(integrand_interface), optional :: integrand
        if (present (dim_x)) then
            call this%set_dim_x (dim_x)
        end if
        if (present (dim_f)) then
            call this%set_dim_f (dim_f)
        end if
        if (present (flags)) then
            this%flags = flags
        end if
        if (present (seed)) then
            this%seed = seed
        end if
        if (present (min_eval)) then
            this%min_eval = min_eval
        end if
        if (present (max_eval)) then
            if (max_eval < max_maxeval) then
                this%max_eval = max_eval
            else
                call msg_warning &
                    ("cuba_set_common: Value of max_eval is too large.")
                this%max_eval = max_maxeval
            end if
        end if
        if (present (eps_rel)) then
            this%eps_rel = eps_rel
        end if
        if (present (eps_abs)) then
            this%eps_abs = eps_abs
        end if
        if (present (integrand)) this%integrand=>integrand
        if (present (userdata)) this%userdata=userdata
    end subroutine cuba_set_common

```



```

<Muli CUBA: cuba class: TBP>+=
  procedure :: set_dim_f => cuba_set_dim_f

<Muli CUBA: procedures>+=
  subroutine cuba_set_dim_f (this, new_dim_f)
    class(cuba_class) :: this
    integer, intent(in) :: new_dim_f
    if (new_dim_f > 0) then
      this%dim_f = new_dim_f
      call this%alloc_dim_f
    else
      call msg_error ("cuba_set_dim_f: New value for dim_f is " &
        // "negative. dim_f is not set.")
    end if
  end subroutine cuba_set_dim_f

<Muli CUBA: cuba class: TBP>+=
  procedure :: set_dim_x => cuba_set_dim_x

<Muli CUBA: procedures>+=
  subroutine cuba_set_dim_x (this, new_dim_x)
    class(cuba_class) :: this
    integer, intent(in) :: new_dim_x
    if (new_dim_x > 0) then
      this%dim_x = new_dim_x
    else
      call msg_error ("cuba_set_dim_x: New value for dim_x is " &
        // "negative. dim_x is not set.")
    end if
  end subroutine cuba_set_dim_x

<Muli CUBA: cuba class: TBP>+=
  procedure :: reset_timer => cuba_reset_timer

<Muli CUBA: procedures>+=
  subroutine cuba_reset_timer (this)
    class(cuba_class), intent(inout) :: this
    this%start_time = zero
    this%stop_time = zero
    this%run_time = zero
  end subroutine cuba_reset_timer

<Muli CUBA: cuba class: TBP>+=
  procedure :: integrate_with_timer => cuba_integrate_with_timer

<Muli CUBA: procedures>+=
  subroutine cuba_integrate_with_timer (this, integrand)
    class(cuba_class), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    call cpu_time (this%start_time)
    call this%integrate (integrand)
    call cpu_time (this%stop_time)
    this%run_time = this%run_time + this%stop_time - this%start_time
  end subroutine cuba_integrate_with_timer

```

```

<Muli CUBA: cuba class: TBP>+=
  procedure :: integrate_associated => cuba_integrate_associated

<Muli CUBA: procedures>+=
  subroutine cuba_integrate_associated (this)
    class(cuba_class), intent(inout) :: this
    call this%integrate_with_timer (this%integrand)
  end subroutine cuba_integrate_associated

<Muli CUBA: cuba class: TBP>+=
  generic :: integrate => integrate_nd, integrate_userdata
  procedure(integrate_interface), deferred :: integrate_nd
  procedure(integrate_userdata_interface), deferred :: integrate_userdata
  procedure(cuba_copy_interface), deferred :: copy

<Muli CUBA: cuba class: TBP>+=
  procedure :: dealloc_dim_f => cuba_dealloc_dim_f

<Muli CUBA: procedures>+=
  subroutine cuba_dealloc_dim_f(this)
    class(cuba_class) :: this
    ! print '("cuba_dealloc_dim_f...")'
    if (allocated (this%integral)) then
      deallocate (this%integral)
    end if
    if (allocated (this%error)) then
      deallocate (this%error)
    end if
    if (allocated (this%prob)) then
      deallocate (this%prob)
    end if
    ! print '("done")'
  end subroutine cuba_dealloc_dim_f

<Muli CUBA: cuba class: TBP>+=
  procedure :: alloc_dim_f => cuba_alloc_dim_f

<Muli CUBA: procedures>+=
  subroutine cuba_alloc_dim_f (this)
    class(cuba_class) :: this
    call this%dealloc_dim_f ()
    allocate (this%integral (this%dim_f))
    allocate (this%error (this%dim_f))
    allocate (this%prob (this%dim_f))
  end subroutine cuba_alloc_dim_f

<Muli CUBA: cuba class: TBP>+=
  procedure :: dealloc => cuba_dealloc

<Muli CUBA: procedures>+=
  subroutine cuba_dealloc (this)
    class(cuba_class) :: this
    call this%dealloc_dim_f
  end subroutine cuba_dealloc

```

```

<Muli CUBA: cuba class: TBP>+≡
    procedure :: alloc => cuba_alloc

<Muli CUBA: procedures>+≡
    subroutine cuba_alloc (this)
        class(cuba_class) :: this
        call this%alloc_dim_f
    end subroutine cuba_alloc

<Muli CUBA: cuba vegas: TBP>≡
    procedure :: write_to_marker => cuba_vegas_write_to_marker

<Muli CUBA: procedures>+≡
    subroutine cuba_vegas_write_to_marker (this, marker, status)
        class(cuba_vegas_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%mark_begin ("cuba_vegas_t")
        call cuba_write_to_marker (this, marker, status)
        call marker%mark("nstart", this%nstart)
        call marker%mark("nincrease", this%nincrease)
        call marker%mark_null ("cuba_vegas_t")
    end subroutine cuba_vegas_write_to_marker

<Muli CUBA: cuba vegas: TBP>+≡
    procedure :: read_from_marker => cuba_vegas_read_from_marker

<Muli CUBA: procedures>+≡
    subroutine cuba_vegas_read_from_marker (this, marker, status)
        class(cuba_vegas_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%pick_begin ("cuba_vegas_t", status=status)
        call cuba_read_from_marker (this, marker, status)
        call marker%pick ("nstart", this%nstart, status)
        call marker%pick ("nincrease", this%nincrease, status)
        call marker%pick_end ("cuba_vegas_t", status)
    end subroutine cuba_vegas_read_from_marker

<Muli CUBA: cuba vegas: TBP>+≡
    procedure :: print_to_unit => cuba_vegas_print_to_unit

<Muli CUBA: procedures>+≡
    subroutine cuba_vegas_print_to_unit(this,unit,parents,components,peers)
        class(cuba_vegas_t), intent(in) :: this
        INTEGER, INTENT(IN) :: unit
        integer(dik), intent(in)::parents,components,peers
        if (parents>0)call cuba_print_to_unit(this,unit,parents-1,components,peers)
        write (unit, "(1x,A)")          "Components of cuba_vegas_t:"
        write (unit, "(3x,A,I10)")      "nstart:      ", this%nstart
        write (unit, "(3x,A,I10)")      "nincrease:  ", this%nincrease
        write (unit, "(3x,A,I10)")      "nbatch:    ", this%nbatch
        write (unit, "(3x,A,I10)")      "gridno:    ", this%gridno
        if (associated (this%statefile)) then

```

```

        write (unit, "(3x,A,A)") "statefile: ", this%statefile
    else
        write (unit, "(3x,A)") "statefile: not associated"
    end if
end subroutine cuba_vegas_print_to_unit

<Muli CUBA: cuba vegas: TBP>+≡
    procedure, nopass :: get_type => cuba_vegas_get_type

<Muli CUBA: procedures>+≡
    pure subroutine cuba_vegas_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="cuba_vegas_t")
    end subroutine cuba_vegas_get_type

<Muli CUBA: cuba vegas: TBP>+≡
    procedure :: integrate_nd => integrate_vegas

<Muli CUBA: procedures>+≡
    subroutine integrate_vegas (this, integrand)
        class(cuba_vegas_t), intent(inout) :: this
        procedure(integrand_interface) :: integrand
        ! print '("vegas")'
        ! call vegas (this%dim_x, this%dim_f, integrand, this%userdata, &
        !             this%eps_rel, this%eps_abs, this%flags, this%seed, &
        !             this%min_eval, this%max_eval, this%nstart, this%nincrease, &
        !             this%nbatch, this%gridno, this%statefile, this%neval, &
        !             this%fail, this%integral, this%error, this%prob)
    end subroutine integrate_vegas

<Muli CUBA: cuba vegas: TBP>+≡
    procedure :: integrate_userdata => integrate_vegas_userdata

<Muli CUBA: procedures>+≡
    subroutine integrate_vegas_userdata (this, integrand, userdata)
        class(cuba_vegas_t), intent(inout) :: this
        procedure(integrand_interface) :: integrand
        class(transverse_mom_t), intent(in) :: userdata
        ! print '("vegas")'
        ! call vegas(this%dim_x, this%dim_f, integrand, userdata, this%eps_rel, &
        !             this%eps_abs, this%flags, this%seed, this%min_eval, this%max_eval, &
        !             this%nstart, this%nincrease, this%nbatch, this%gridno, &
        !             this%statefile, this%neval, this%fail, this%integral, &
        !             this%error, this%prob)
    end subroutine integrate_vegas_userdata

<Muli CUBA: cuba vegas: TBP>+≡
    procedure :: copy => cuba_vegas_copy

<Muli CUBA: procedures>+≡
    subroutine cuba_vegas_copy (this, source)
        class(cuba_vegas_t), intent(out) :: this
        class(cuba_class), intent(in) :: source
        select type (source)

```

```

class is (cuba_vegas_t)
  call this%copy_common (source)
  this%nstart = source%nstart
  this%nincrease = source%nincrease
class default
  call msg_error ("cuba_vegas_copy: type of source is not type " &
    // "compatible with cuba_vegas_t.")
end select
end subroutine cuba_vegas_copy

```

<Muli CUBA: cuba vegas: TBP>+≡

```

procedure :: set_deferred => cuba_vegas_set_deferred

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_vegas_set_deferred &
  (this, n_start, n_increase, nbatch, gridno, statefile)
  class(cuba_vegas_t), intent(inout) :: this
  integer, intent(in), optional :: n_start, n_increase, nbatch, gridno
  character(len=*), intent(in), target, optional :: statefile
  if (present (n_start)) this%nstart = n_start
  if (present (n_increase)) this%nincrease = n_increase
  if (present (nbatch)) this%nbatch = nbatch
  if (present (gridno)) this%gridno = gridno
  if (present (statefile)) this%statefile => statefile
end subroutine cuba_vegas_set_deferred

```

<Muli CUBA: cuba divonne: TBP>≡

```

procedure :: write_to_marker => cuba_divonne_write_to_marker

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_divonne_write_to_marker (this, marker, status)
  class(cuba_divonne_t), intent(in) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  call marker%mark_begin ("cuba_divonne_t")
  call cuba_write_to_marker (this, marker, status)
  call marker%mark ("key1", this%key1)
  call marker%mark ("key2", this%key2)
  call marker%mark ("key3", this%key3)
  call marker%mark ("maxpass", this%maxpass)
  call marker%mark ("border", this%border)
  call marker%mark ("maxchisq", this%maxchisq)
  call marker%mark ("mindeviation", this%mindeviation)
  call marker%mark ("ngiven", this%ngiven)
  call marker%mark ("ldxgiven", this%ldxgiven)
  call marker%mark ("nextra", this%nextra)
  call marker%mark ("xgiven", this%xgiven)
  call marker%mark_null ("cuba_divonne_t")
end subroutine cuba_divonne_write_to_marker

```

<Muli CUBA: cuba divonne: TBP>+≡

```

procedure :: read_from_marker => cuba_divonne_read_from_marker

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_divonne_read_from_marker (this, marker, status)
  class(cuba_divonne_t), intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  call marker%pick_begin ("cuba_divonne_t", status=status)
  call cuba_read_from_marker (this, marker, status)
  call marker%pick ("key1", this%key1, status)
  call marker%pick ("key2", this%key2, status)
  call marker%pick ("key3", this%key3, status)
  call marker%pick ("maxpass", this%maxpass, status)
  call marker%pick ("border", this%border, status)
  call marker%pick ("maxchisq", this%maxchisq, status)
  call marker%pick ("mindeviation", this%mindeviation, status)
  call marker%pick ("ngiven", this%ngiven, status)
  call marker%pick ("ldxgiven", this%ldxgiven, status)
  call marker%pick ("nextra", this%nextra, status)
  if (allocated (this%xgiven)) deallocate (this%xgiven)
  allocate (this%xgiven (this%ldxgiven, this%ngiven))
  call marker%pick ("xgiven", this%xgiven, status)
  call marker%pick_end ("cuba_divonne_t", status)
end subroutine cuba_divonne_read_from_marker

```

<Muli CUBA: cuba divonne: TBP>+≡

```

procedure :: print_to_unit => cuba_divonne_print_to_unit

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_divonne_print_to_unit (this, unit, parents, components, peers)
  class(cuba_divonne_t), intent(in) :: this
  INTEGER, INTENT(IN) :: unit
  integer(dik), intent(in) :: parents, components, peers
  if (parents > 0) &
    call cuba_print_to_unit (this, unit, parents-1, components, peers)
  write (unit, "(1x,A)") "Components of cuba_divonne_t:"
  write (unit, "(3x,A,I10)") "key1: ", this%key1
  write (unit, "(3x,A,I10)") "key2: ", this%key2
  write (unit, "(3x,A,I10)") "key3: ", this%key3
  write (unit, "(3x,A,I10)") "maxpass: ", this%maxpass
  write (unit, "(3x,A,I10)") "ngiven: ", this%ngiven
  write (unit, "(3x,A,I10)") "ldxgiven: ", this%ldxgiven
  write (unit, "(3x,A,I10)") "nextra: ", this%nextra
  write (unit, "(3x,A,E10.4)") "border: ", this%border
  write (unit, "(3x,A,E10.4)") "maxchisq: ", this%maxchisq
  write (unit, "(3x,A,E10.4)") "mindeviation:", this%mindeviation
  write (unit, "(3x,A,2(E10.4))") "xgiven: ", this%xgiven
end subroutine cuba_divonne_print_to_unit

```

<Muli CUBA: cuba divonne: TBP>+≡

```

procedure, nopass :: get_type => cuba_divonne_get_type

```

<Muli CUBA: procedures>+≡

```

pure subroutine cuba_divonne_get_type (type)
  character(:), allocatable, intent(out) :: type
  allocate(type, source="cuba_divonne_t")

```

```

end subroutine cuba_divonne_get_type

<Muli CUBA: cuba divonne: TBP>+≡
  procedure :: integrate_nd => integrate_divonne
<Muli CUBA: procedures>+≡
  subroutine integrate_divonne (this, integrand)
    class(cuba_divonne_t), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    ! call this%reset_output()
    ! print '("divonne")'
    ! call divonne(this%dim_x, this%dim_f, integrand, this%userdata, &
    !   this%eps_rel, this%eps_abs, this%flags, this%seed, this%min_eval, &
    !   this%max_eval, this%key1, this%key2, this%key3, this%maxpass, &
    !   this%border, this%maxchisq, this%mindeviation, this%ngiven, &
    !   this%ldxgiven, this%xgiven, this%nexttra, &
    !   ! this%peakfinder, &
    !   0, this%nregions, this%neval, this%fail, this%integral, &
    !   this%error, this%prob)
  end subroutine integrate_divonne

<Muli CUBA: cuba divonne: TBP>+≡
  procedure :: integrate_userdata => integrate_divonne_userdata
<Muli CUBA: procedures>+≡
  subroutine integrate_divonne_userdata (this, integrand, userdata)
    class(cuba_divonne_t), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    class(transverse_mom_t), intent(in) :: userdata
    ! call this%reset_output()
    ! print '("divonne")'
    ! call divonne (this%dim_x, this%dim_f, integrand, userdata, &
    !   this%eps_rel, this%eps_abs, this%flags, this%seed, this%min_eval, &
    !   this%max_eval, this%key1, this%key2, this%key3, this%maxpass, &
    !   this%border, this%maxchisq, this%mindeviation, this%ngiven, &
    !   this%ldxgiven, this%xgiven, this%nexttra, &
    !   ! this%peakfinder, &
    !   0, this%nregions, this%neval, this%fail, this%integral, &
    !   this%error, this%prob)
  end subroutine integrate_divonne_userdata

<Muli CUBA: cuba divonne: TBP>+≡
  procedure :: copy => cuba_divonne_copy
<Muli CUBA: procedures>+≡
  subroutine cuba_divonne_copy (this, source)
    class(cuba_divonne_t), intent(out) :: this
    class(cuba_class), intent(in) :: source
    select type (source)
    class is (cuba_divonne_t)
      call this%copy_common(source)
      call this%set_deferred (source%key1, source%key2, source%key3, &
        source%maxpass, source%border, source%maxchisq, &
        source%mindeviation, source%xgiven)

```

```

class default
  call msg_error ("cuba_divonne_copy: type of source is not " &
    // "type compatible with cuba_divonne_t.")
end select
end subroutine cuba_divonne_copy

```

<Muli CUBA: cuba divonne: TBP>+≡

```

procedure :: set_deferred => cuba_divonne_set_deferred

```

<Muli CUBA: procedures>+≡

```

subroutine cuba_divonne_set_deferred (this, key1, key2, key3, maxpass, &
  border, maxchisq, mindeviation, xgiven, xgiven_flat)
  class(cuba_divonne_t) :: this
  integer, optional, intent(in) :: key1, key2, key3, maxpass
  real(default), optional, intent(in) :: border, maxchisq, mindeviation
  real(default), dimension(:,:), optional, intent(in) :: xgiven
  real(default), dimension(:), optional, intent(in) :: xgiven_flat
  integer, dimension(2) :: s
  if (present (key1)) this%key1 = key1
  if (present (key2)) this%key2 = key2
  if (present (key3)) this%key3 = key3
  if (present (maxpass)) this%maxpass = maxpass
  if (present (border)) this%border = border
  if (present (maxchisq)) this%maxchisq = maxchisq
  if (present (mindeviation)) this%mindeviation = mindeviation
  if (present (xgiven)) then
    if (allocated (this%xgiven)) deallocate (this%xgiven)
    s = shape(xgiven)
    if (s(1) == this%dim_x) then
      allocate (this%xgiven (s(1), s(2)), source=xgiven)
      this%ldxgiven = s(1)
      this%ngiven = s(2)
    else
      call msg_error ("cuba_divonne_set_deferred: shape of xgiven " &
        // "is not [dim_x,:].")
      this%ngiven = 0
    end if
  end if
  if (present (xgiven_flat)) then
    if (allocated (this%xgiven)) deallocate (this%xgiven)
    if (mod(size(xgiven_flat), this%dim_x) == 0) then
      this%ngiven = size(xgiven_flat) / this%dim_x
      this%ldxgiven = this%dim_x
      allocate (this%xgiven (this%ldxgiven, this%ngiven))
      this%xgiven = reshape(xgiven_flat, [this%ldxgiven, this%ngiven])
    else
      call msg_error ("cuba_divonne_set_deferred: size of xgiven_flat " &
        // "is no multiple of dim_x.")
      this%ngiven = 0
    end if
  end if
end subroutine cuba_divonne_set_deferred

```

<Muli CUBA: cuba cuhre: TBP>≡


```

    procedure :: write_to_marker => cuba_cuhre_write_to_marker

<Muli CUBA: procedures>+≡
    subroutine cuba_cuhre_write_to_marker (this, marker, status)
        class(cuba_cuhre_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%mark_begin ("cuba_cuhre_t")
        call cuba_write_to_marker (this, marker, status)
        call marker%mark ("key", this%key)
        call marker%pick_end ("cuba_cuhre_t", status)
    end subroutine cuba_cuhre_write_to_marker

<Muli CUBA: cuba_cuhre: TBP>+≡
    procedure :: read_from_marker => cuba_cuhre_read_from_marker

<Muli CUBA: procedures>+≡
    subroutine cuba_cuhre_read_from_marker (this, marker, status)
        class(cuba_cuhre_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%pick_begin ("cuba_cuhre_t", status=status)
        call cuba_read_from_marker (this, marker, status)
        call marker%pick ("key", this%key, status)
        call marker%pick_end ("cuba_cuhre_t", status)
    end subroutine cuba_cuhre_read_from_marker

<Muli CUBA: cuba_cuhre: TBP>+≡
    procedure :: print_to_unit => cuba_cuhre_print_to_unit

<Muli CUBA: procedures>+≡
    subroutine cuba_cuhre_print_to_unit (this, unit, parents, components, peers)
        class(cuba_cuhre_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        if (parents > 0) &
            call cuba_print_to_unit (this, unit, parents-1, components, peers)
        write (unit, "(1x,A)")      "Components of cuba_cuhre_t:"
        write (unit, "(3x,A,I10)") "key:      ", this%key
    end subroutine cuba_cuhre_print_to_unit

<Muli CUBA: cuba_cuhre: TBP>+≡
    procedure, nopass :: get_type => cuba_cuhre_get_type

<Muli CUBA: procedures>+≡
    pure subroutine cuba_cuhre_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="cuba_cuhre_t")
    end subroutine cuba_cuhre_get_type

<Muli CUBA: cuba_cuhre: TBP>+≡
    procedure :: integrate_nd => integrate_cuhre

```

```

<Muli CUBA: procedures>+≡
  subroutine integrate_cuhre (this, integrand)
    class(cuba_cuhre_t), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    ! print '("cuhre")'
    ! call cuhre(this%dim_x, this%dim_f, integrand, this%userdata, &
    !           this%eps_rel, this%eps_abs, this%flags, &
    !           ! this%seed, &
    !           this%min_eval, this%max_eval, this%key, this%nregions, &
    !           this%neval, this%fail, this%integral, this%error, this%prob)
  end subroutine integrate_cuhre

<Muli CUBA: cuba_cuhre: TBP>+≡
  procedure :: integrate_userdata => integrate_cuhre_userdata

<Muli CUBA: procedures>+≡
  subroutine integrate_cuhre_userdata (this, integrand, userdata)
    class(cuba_cuhre_t), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    class(transverse_mom_t), intent(in) :: userdata
    ! print '("cuhre")'
    ! call cuhre(this%dim_x, this%dim_f, integrand, userdata, this%eps_rel, &
    !           this%eps_abs, this%flags, &
    !           ! this%seed, &
    !           this%min_eval, this%max_eval, this%key, this%nregions, &
    !           this%neval, this%fail, this%integral, this%error, this%prob)
  end subroutine integrate_cuhre_userdata

<Muli CUBA: cuba_cuhre: TBP>+≡
  procedure :: copy => cuba_cuhre_copy

<Muli CUBA: procedures>+≡
  subroutine cuba_cuhre_copy (this, source)
    class(cuba_cuhre_t), intent(out) :: this
    class(cuba_class), intent(in) :: source
    select type (source)
    class is (cuba_cuhre_t)
      call this%copy_common (source)
      this%key = source%key
    class default
      call msg_error ("cuba_cuhre_copy: type of source is not type " &
        // "compatible with cuba_cuhre_t.")
    end select
  end subroutine cuba_cuhre_copy

<Muli CUBA: cuba_cuhre: TBP>+≡
  procedure :: set_deferred => cuba_cuhre_set_deferred

<Muli CUBA: procedures>+≡
  subroutine cuba_cuhre_set_deferred (this, key)
    class(cuba_cuhre_t), intent(inout) :: this
    integer, intent(in) :: key
    this%key = key
  end subroutine cuba_cuhre_set_deferred

```

```

<Muli CUBA: cuba suave: TBP>≡
    procedure :: write_to_marker => cuba_suave_write_to_marker

<Muli CUBA: procedures>+≡
    subroutine cuba_suave_write_to_marker (this, marker, status)
        class(cuba_suave_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%mark_begin ("cuba_suave_t")
        call cuba_write_to_marker (this, marker, status)
        call marker%mark ("nnew", this%nnew)
        call marker%mark ("flatness", this%flatness)
        call marker%mark_null ("cuba_suave_t")
    end subroutine cuba_suave_write_to_marker

<Muli CUBA: cuba suave: TBP>+≡
    procedure :: read_from_marker => cuba_suave_read_from_marker

<Muli CUBA: procedures>+≡
    subroutine cuba_suave_read_from_marker (this, marker, status)
        class(cuba_suave_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%pick_begin ("cuba_suave_t", status=status)
        call cuba_read_from_marker (this, marker, status)
        call marker%pick ("nnew", this%nnew, status)
        call marker%pick ("flatnes", this%flatness, status)
        call marker%pick_end ("cuba_suave_t", status)
    end subroutine cuba_suave_read_from_marker

<Muli CUBA: cuba suave: TBP>+≡
    procedure :: print_to_unit => cuba_suave_print_to_unit

<Muli CUBA: procedures>+≡
    subroutine cuba_suave_print_to_unit (this, unit, parents, components, peers)
        class(cuba_suave_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        if (parents > 0) &
            call cuba_print_to_unit (this, unit, parents-1, components, peers)
        write (unit, "(1x,A)")      "Components of cuba_suave_t:"
        write (unit, "(3x,A,I10)") "nnew:      ", this%nnew
        write (unit, "(3x,A,I10)") "flatness: ", this%flatness
    end subroutine cuba_suave_print_to_unit

<Muli CUBA: cuba suave: TBP>+≡
    procedure, nopass :: get_type => cuba_suave_get_type

<Muli CUBA: procedures>+≡
    pure subroutine cuba_suave_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="cuba_suave_t")
    end subroutine cuba_suave_get_type

```

```

<Muli CUBA: cuba suave: TBP>+≡
  procedure :: integrate_nd => integrate_suave

<Muli CUBA: procedures>+≡
  subroutine integrate_suave (this, integrand)
    class(cuba_suave_t), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    ! print '("suave")'
    ! call suave(this%dim_x, this%dim_f, integrand, this%userdata, &
    !           this%eps_rel, this%eps_abs, this%flags, this%seed, &
    !           this%min_eval, this%max_eval, this%nnew, this%flatness, &
    !           this%nregions, this%neval, this%fail, this%integral, &
    !           this%error, this%prob)
  end subroutine integrate_suave

<Muli CUBA: cuba suave: TBP>+≡
  procedure :: integrate_userdata => integrate_suave_userdata

<Muli CUBA: procedures>+≡
  subroutine integrate_suave_userdata (this, integrand, userdata)
    class(cuba_suave_t), intent(inout) :: this
    procedure(integrand_interface) :: integrand
    class(transverse_mom_t), intent(in) :: userdata
    ! print '("suave")'
    ! call suave (this%dim_x, this%dim_f, integrand, userdata, &
    !             this%eps_rel, this%eps_abs, this%flags, this%seed, &
    !             this%min_eval, this%max_eval, this%nnew, this%flatness, &
    !             this%nregions, this%neval, this%fail, this%integral, &
    !             this%error, this%prob)
  end subroutine integrate_suave_userdata

<Muli CUBA: cuba suave: TBP>+≡
  procedure :: copy => cuba_suave_copy

<Muli CUBA: procedures>+≡
  subroutine cuba_suave_copy (this, source)
    class(cuba_suave_t), intent(out) :: this
    class(cuba_class), intent(in) :: source
    select type (source)
    class is (cuba_suave_t)
      call this%copy_common (source)
      this%nnew = source%nnew
      this%flatness = source%flatness
    class default
      call msg_error ("cuba_suave_copy: type of source is not type " &
        // "compatible with cuba_suave_t.")
    end select
  end subroutine cuba_suave_copy

<Muli CUBA: interfaces>≡
  interface
    subroutine integrand_interface (dim_x, x, dim_f, f, userdata)
      <Use kinds>
      use multi_momentum

```

```

        integer, intent(in) :: dim_x, dim_f
        real(default), dimension(dim_x), intent(in) :: x
        real(default), dimension(dim_f), intent(out) :: f
        class(transverse_mom_t), intent(in) :: userdata
    end subroutine integrand_interface
end interface

<Muli CUBA: interfaces>+≡
interface
    subroutine cuba_copy_interface (this, source)
        import :: cuba_class
        class(cuba_class), intent(out) :: this
        class(cuba_class), intent(in) :: source
    end subroutine cuba_copy_interface
end interface

<Muli CUBA: interfaces>+≡
interface
    subroutine ca_plain (this)
        import :: cuba_class
        class(cuba_class) :: this
    end subroutine ca_plain
end interface

<Muli CUBA: interfaces>+≡
interface
    subroutine integrate_interface (this, integrand)
        import :: cuba_class
        class(cuba_class), intent(inout) :: this
        interface
            subroutine integrand (dim_x, x, dim_f, f,userdata)
                <Use kinds>
                use multi_momentum
                integer, intent(in) :: dim_x, dim_f
                real(default), dimension(dim_x), intent(in) :: x
                real(default), dimension(dim_f), intent(out) :: f
                class(transverse_mom_t), intent(in) :: userdata
            end subroutine integrand
        end interface
    end subroutine integrate_interface
end interface

<Muli CUBA: interfaces>+≡
interface
    subroutine integrate_userdata_interface (this, integrand,userdata)
        use multi_momentum
        import :: cuba_class
        class(cuba_class), intent(inout) :: this
        interface
            subroutine integrand (dim_x, x, dim_f, f,userdata)
                <Use kinds>
                use multi_momentum
                integer, intent(in) :: dim_x, dim_f
                real(default), dimension(dim_x), intent(in) :: x
                real(default), dimension(dim_f), intent(out) :: f
                class(transverse_mom_t), intent(in) :: userdata
            end subroutine integrand
        end interface
    end subroutine integrate_userdata_interface
end interface

```

```

        end subroutine integrand
    end interface
    class(transverse_mom_t), intent(in) :: userdata
    end subroutine integrate_userdata_interface
end interface

```

21.5 Trapezoidal integration routines

This file contains the module "muli_trapezium". The name is derived from the trapezoidal integration rule. The purpose of this module is to define a binary tree `muli_trapezium_tree_t` which holds a probability function in terms of trapezoidal segments. Its leaves of type `muli_trapezium_list_t` are connected to form a list, so you can either walk the root function back and forth or pick a certain segment in logarithmic time by walking down the tree. All nodes extend `muli_trapezium_t` which holds the actual values. Those are the values of the density function, the integral from this segment to the end of the integration area and a probability function calculated from these values. All values are taken at the upper "right" bound of the segment. Additionally the differences of these values to the values of the left neighbor is stored.

```

<muli_trapezium.f90>≡
  <File header>

  module muli_trapezium
    use, intrinsic :: iso_fortran_env, only: output_unit
  <Use kinds>
    use constants
    use diagnostics
    use muli_base

  <Standard module head>

  <Muli trapezium: variables>

  <Muli trapezium: public>

  <Muli trapezium: types>

  <Muli trapezium: interfaces>

  contains

  <Muli trapezium: procedures>

  end module muli_trapezium

<Muli trapezium: variables>≡
  integer, private, parameter :: value_dimension = 7
  integer, private, parameter :: r_value_index = 1
  integer, private, parameter :: d_value_index = 2
  integer, private, parameter :: r_integral_index = 3

```

```

integer, private, parameter :: d_integral_index = 4
integer, private, parameter :: r_probability_index = 5
integer, private, parameter :: d_probability_index = 6
integer, private, parameter :: error_index = 7

```

```

<Muli trapezium: interfaces>≡
  abstract interface
    subroutine muli_trapezium_append_interface (this, right)
      import muli_trapezium_node_class_t
      class(muli_trapezium_node_class_t), intent(inout), target :: this, right
    end subroutine muli_trapezium_append_interface
  end interface

```

```

<Muli trapezium: interfaces>+≡
  abstract interface
    subroutine muli_trapezium_final_interface (this)
      import muli_trapezium_node_class_t
      class(muli_trapezium_node_class_t), intent(inout) :: this
    end subroutine muli_trapezium_final_interface
  end interface

```

This is the base type `muli_trapezium_t`. Its component values has a first index is in $\{0, \dots, \text{dim} - 1\}$, while the second index distinguishes between `r_value`, `d_value`, `r_integral`, `d_integral`, `r_probability`, `d_probability`.

```

<Muli trapezium: public>≡
  public :: muli_trapezium_t

<Muli trapezium: types>≡
  type, extends (measure_class_t) :: muli_trapezium_t
    private
      integer :: dim = 0
      real(default) :: r_position = 0
      real(default) :: d_position = 0
      real(default) :: measure_comp = 0
      real(default), dimension(:,:), allocatable :: values
    contains
      <Muli trapezium: trapezium: TBP>
  end type muli_trapezium_t

```

```

<Muli trapezium: public>+≡
  public :: muli_trapezium_node_class_t

```

```

<Muli trapezium: types>+≡
  type, extends (muli_trapezium_t), abstract :: muli_trapezium_node_class_t
    private
      class(muli_trapezium_node_class_t), pointer :: left => null()
      class(muli_trapezium_node_class_t), pointer :: right => null()
      ! real(default) :: criterion
    contains
      <Muli trapezium: node: TBP>
  end type muli_trapezium_node_class_t

```

```

<Muli trapezium: public>+≡
  public :: muli_trapezium_tree_t

```

```

<Muli trapezium: types>+≡
  type, extends(muli_trapezium_node_class_t) :: muli_trapezium_tree_t
    class(muli_trapezium_node_class_t), pointer :: down => null()
    contains
      <Muli trapezium: tree: TBP>
    end type muli_trapezium_tree_t

<Muli trapezium: public>+≡
  public :: muli_trapezium_list_t

<Muli trapezium: types>+≡
  type, extends (muli_trapezium_node_class_t) :: muli_trapezium_list_t
    contains
      <Muli trapezium: list: TBP>
    end type muli_trapezium_list_t

<Muli trapezium: trapezium: TBP>≡
  procedure :: write_to_marker => muli_trapezium_write_to_marker

<Muli trapezium: procedures>≡
  subroutine muli_trapezium_write_to_marker (this,marker,status)
    class(muli_trapezium_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    integer::dim
    call marker%mark_begin ("muli_trapezium_t")
    call marker%mark ("dim", this%dim)
    call marker%mark ("r_position", this%r_position)
    call marker%mark ("d_position", this%d_position)
    if (allocated(this%values)) then
      call marker%mark ("values", this%values)
    else
      call marker%mark_null ("values")
    end if
    call marker%mark_end ("muli_trapezium_t")
  end subroutine muli_trapezium_write_to_marker

<Muli trapezium: trapezium: TBP>+≡
  procedure :: read_from_marker => muli_trapezium_read_from_marker

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_read_from_marker (this,marker,status)
    class(muli_trapezium_t), intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    integer :: dim
    call marker%pick_begin ("muli_trapezium_t", status=status)
    call marker%pick ("dim", this%dim,status)
    call marker%pick ("r_position", this%r_position, status)
    call marker%pick ("d_position", this%d_position, status)
    if (allocated (this%values)) deallocate (this%values)
    call marker%verify_nothing ("values", status)
    if (status == serialize_ok) then
      allocate(this%values(0:this%dim-1,7))
    end if
  end subroutine muli_trapezium_read_from_marker

```



```

        call marker%pick ("values",this%values, status)
    end if
    call marker%pick_end("multi_trapezium_t",status)
end subroutine multi_trapezium_read_from_marker

<Multi trapezium: trapezium: TBP>+=
    procedure :: print_to_unit => multi_trapezium_print_to_unit

<Multi trapezium: procedures>+=
    subroutine multi_trapezium_print_to_unit (this, unit, parents, components, peers)
        class(multi_trapezium_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        write (unit, "(1x,A)") "Components of multi_trapezium_t:"
        write (unit, fmt=*)"Dimension:          ",this%dim
        write (unit,fmt=*)"Right position:      ",this%r_position
        write (unit,fmt=*)"Position step:      ",this%d_position
        if (allocated(this%values)) then
            if (components>0) then
                write (unit,fmt=*)"Right values:          ",multi_trapezium_get_r_value_array(this)
                write (unit,fmt=*)"Value step:          ", this%get_d_value()
                write (unit,fmt=*)"Right integrals:      ",this%get_r_integral()
                write (unit,fmt=*)"Integral step:      ",this%get_d_integral()
                write (unit,fmt=*)"Right propabilities:",this%get_r_probability()
                write (unit,fmt=*)"Probability step:  ",this%get_d_probability()
                write (unit,fmt=*)"Errors:              ",this%get_error()
            else
                write (unit, "(3x,A)") "Values are allocated."
            end if
        else
            write (unit, "(3x,A)") "Values are not allocated."
        end if
    end subroutine multi_trapezium_print_to_unit

<Multi trapezium: trapezium: TBP>+=
    procedure, nopass :: get_type => multi_trapezium_get_type

<Multi trapezium: procedures>+=
    pure subroutine multi_trapezium_get_type (type)
        character(:),allocatable, intent(out) :: type
        allocate (type, source="multi_trapezium_t")
    end subroutine multi_trapezium_get_type

<Multi trapezium: trapezium: TBP>+=
    procedure, nopass :: verify_type => multi_trapezium_verify_type

<Multi trapezium: procedures>+=
    elemental logical function multi_trapezium_verify_type (type) result (match)
        character(*), intent(in) :: type
        match = type == "multi_trapezium_t"
    end function multi_trapezium_verify_type

<Multi trapezium: trapezium: TBP>+=
    procedure :: measure => multi_trapezium_measure

```

```

<Muli trapezium: procedures>+≡
    elemental function muli_trapezium_measure (this)
        class(muli_trapezium_t), intent(in) :: this
        real(default) :: muli_trapezium_measure
        muli_trapezium_measure = this%measure_comp
    end function muli_trapezium_measure

<Muli trapezium: trapezium: TBP>+≡
    procedure :: initialize => muli_trapezium_initialize

<Muli trapezium: procedures>+≡
    subroutine muli_trapezium_initialize (this, dim, r_position, d_position)
        class(muli_trapezium_t), intent(inout) :: this
        integer, intent(in) :: dim
        real(default), intent(in) :: r_position, d_position
        integer :: dim1, dim2
        this%dim = dim
        this%r_position = r_position
        this%d_position = d_position
        if (allocated (this%values)) deallocate (this%values)
        allocate (this%values(0:dim-1,value_dimension))
        do dim2 = 1, value_dimension-1
            do dim1 = 0, dim-1
                this%values(dim1,dim2) = zero
            end do
        end do
        do dim1 = 0, dim-1
            this%values(dim1, value_dimension) = huge(one)
        end do
        this%measure_comp = huge(one)
    end subroutine muli_trapezium_initialize

<Muli trapezium: trapezium: TBP>+≡
    procedure :: get_dimension => muli_trapezium_get_dimension

<Muli trapezium: procedures>+≡
    elemental function muli_trapezium_get_dimension (this) result (dim)
        class(muli_trapezium_t), intent(in) :: this
        integer :: dim
        dim = this%dim
    end function muli_trapezium_get_dimension

<Muli trapezium: trapezium: TBP>+≡
    procedure :: get_l_position => muli_trapezium_get_l_position

<Muli trapezium: procedures>+≡
    pure function muli_trapezium_get_l_position (this) result (pos)
        class(muli_trapezium_t), intent(in) :: this
        real(default) :: pos
        pos = this%r_position - this%d_position
    end function muli_trapezium_get_l_position

<Muli trapezium: trapezium: TBP>+≡
    procedure :: get_r_position => muli_trapezium_get_r_position

```

```

<Muli trapezium: procedures>+≡
  pure function muli_trapezium_get_r_position (this) result (pos)
    class(muli_trapezium_t), intent(in) :: this
    real(default) :: pos
    pos = this%r_position
  end function muli_trapezium_get_r_position

<Muli trapezium: trapezium: TBP>+≡
  procedure :: get_d_position => muli_trapezium_get_d_position

<Muli trapezium: procedures>+≡
  pure function muli_trapezium_get_d_position (this) result (pos)
    class(muli_trapezium_t), intent(in) :: this
    real(default) :: pos
    pos = this%d_position
  end function muli_trapezium_get_d_position

<Muli trapezium: trapezium: TBP>+≡
  generic :: get_l_value => get_l_value_array, get_l_value_element
  procedure :: get_l_value_array => muli_trapezium_get_l_value_array
  procedure :: get_l_value_element => muli_trapezium_get_l_value_element

<Muli trapezium: procedures>+≡
  pure function muli_trapezium_get_l_value_array (this) result (subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: subarray
    subarray = this%values(0:this%dim-1, r_value_index) - &
      this%values(0:this%dim-1, d_value_index)
  end function muli_trapezium_get_l_value_array

<Muli trapezium: procedures>+≡
  pure function muli_trapezium_get_l_value_element (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element = this%values(set, r_value_index) - this%values(set, d_value_index)
  end function muli_trapezium_get_l_value_element

<Muli trapezium: trapezium: TBP>+≡
  generic :: get_r_value => get_r_value_array, get_r_value_element
  procedure :: get_r_value_array => muli_trapezium_get_r_value_array
  procedure :: get_r_value_element => muli_trapezium_get_r_value_element

<Muli trapezium: procedures>+≡
  pure function muli_trapezium_get_r_value_element (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element = this%values (set, r_value_index)
  end function muli_trapezium_get_r_value_element

```

```

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_r_value_array (this) result (subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: subarray
    subarray = this%values(0:this%dim-1, r_value_index)
  end function muli_trapezium_get_r_value_array

<Muli trapezium: trapezium: TBP>+=
  generic :: get_d_value => get_d_value_array, get_d_value_element
  procedure :: get_d_value_array => muli_trapezium_get_d_value_array
  procedure :: get_d_value_element => muli_trapezium_get_d_value_element

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_d_value_element (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element=this%values (set, d_value_index)
  end function muli_trapezium_get_d_value_element

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_d_value_array (this) result (subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: subarray
    subarray = this%values(0:this%dim-1, d_value_index)
  end function muli_trapezium_get_d_value_array

<Muli trapezium: trapezium: TBP>+=
  generic :: get_l_integral => get_l_integral_array, get_l_integral_element
  procedure :: get_l_integral_array => muli_trapezium_get_l_integral_array
  procedure :: get_l_integral_element => muli_trapezium_get_l_integral_element

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_l_integral_element &
    (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element = this%values (set, r_integral_index) - &
      this%values (set, d_integral_index)
  end function muli_trapezium_get_l_integral_element

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_l_integral_array (this) result (subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: subarray
    subarray = this%values (0:this%dim-1, r_integral_index) - &
      this%values (0:this%dim-1, d_integral_index)
  end function muli_trapezium_get_l_integral_array

```

```

<Muli trapezium: trapezium: TBP>+=
generic :: get_r_integral => get_r_integral_array, get_r_integral_element
procedure :: get_r_integral_array => muli_trapezium_get_r_integral_array
procedure :: get_r_integral_element => muli_trapezium_get_r_integral_element

<Muli trapezium: procedures>+=
pure function muli_trapezium_get_r_integral_element (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element = this%values (set, r_integral_index)
end function muli_trapezium_get_r_integral_element

<Muli trapezium: procedures>+=
pure function muli_trapezium_get_r_integral_array (this) result (subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: subarray
    subarray = this%values (0:this%dim-1, r_integral_index)
end function muli_trapezium_get_r_integral_array

<Muli trapezium: trapezium: TBP>+=
generic :: get_d_integral => get_d_integral_array, get_d_integral_element
procedure :: get_d_integral_array => muli_trapezium_get_d_integral_array
procedure :: get_d_integral_element => muli_trapezium_get_d_integral_element

<Muli trapezium: procedures>+=
pure function muli_trapezium_get_d_integral_element &
    (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element = this%values (set, d_integral_index)
end function muli_trapezium_get_d_integral_element

<Muli trapezium: procedures>+=
pure function muli_trapezium_get_d_integral_array (this) result (subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: subarray
    subarray = this%values (0:this%dim-1, d_integral_index)
end function muli_trapezium_get_d_integral_array

<Muli trapezium: trapezium: TBP>+=
generic :: get_l_probability => &
    get_l_probability_array, get_l_probability_element
procedure :: get_l_probability_element => &
    muli_trapezium_get_l_probability_element
procedure :: get_l_probability_array => &
    muli_trapezium_get_l_probability_array

<Muli trapezium: procedures>+=
pure function muli_trapezium_get_l_probability_element &
    (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this

```

```

integer, intent(in) :: set
real(default) :: element
element = this%values (set, r_probability_index) - &
    this%values (set, d_probability_index)
end function multi_trapezium_get_l_probability_element

<Muli trapezium: procedures>+=
pure function multi_trapezium_get_l_probability_array (this) result (subarray)
class(muli_trapezium_t), intent(in) :: this
real(default), dimension(this%dim) :: subarray
subarray = this%values (0:this%dim-1, r_probability_index) - &
    this%values (0:this%dim-1, d_probability_index)
end function multi_trapezium_get_l_probability_array

<Muli trapezium: trapezium: TBP>+=
generic :: get_r_probability => &
    get_r_probability_array, get_r_probability_element
procedure :: get_r_probability_element => &
    multi_trapezium_get_r_probability_element
procedure :: get_r_probability_array => &
    multi_trapezium_get_r_probability_array

<Muli trapezium: procedures>+=
pure function multi_trapezium_get_r_probability_element &
    (this, set) result (element)
class(muli_trapezium_t), intent(in) :: this
integer, intent(in) :: set
real(default) :: element
element = this%values (set, r_probability_index)
end function multi_trapezium_get_r_probability_element

<Muli trapezium: procedures>+=
pure function multi_trapezium_get_r_probability_array (this) result (subarray)
class(muli_trapezium_t), intent(in) :: this
real(default), dimension(this%dim) :: subarray
subarray = this%values (0:this%dim-1, r_probability_index)
end function multi_trapezium_get_r_probability_array

<Muli trapezium: trapezium: TBP>+=
generic :: get_d_probability => &
    get_d_probability_array, get_d_probability_element
procedure :: get_d_probability_element => &
    multi_trapezium_get_d_probability_element
procedure :: get_d_probability_array => &
    multi_trapezium_get_d_probability_array

<Muli trapezium: procedures>+=
pure function multi_trapezium_get_d_probability_array (this) result (subarray)
class(muli_trapezium_t), intent(in) :: this
real(default), dimension(this%dim) :: subarray
subarray = this%values (0:this%dim-1, d_probability_index)
end function multi_trapezium_get_d_probability_array

```

```

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_d_probability_element &
    (this, set) result (element)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: set
    real(default) :: element
    element = this%values (set, d_probability_index)
  end function muli_trapezium_get_d_probability_element

<Muli trapezium: trapezium: TBP>+=
  procedure :: get_error => muli_trapezium_get_error

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_error_sum (this) result (error)
    class(muli_trapezium_t), intent(in) :: this
    real(default) :: error
    error = sum (this%values (0:this%dim-1, error_index))
  end function muli_trapezium_get_error_sum

<Muli trapezium: trapezium: TBP>+=
  procedure :: get_error_sum => muli_trapezium_get_error_sum

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_error (this) result (error)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: error
    error = this%values (0:this%dim-1, error_index)
  end function muli_trapezium_get_error

<Muli trapezium: trapezium: TBP>+=
  procedure :: get_integral_sum => muli_trapezium_get_integral_sum

<Muli trapezium: procedures>+=
  pure function muli_trapezium_get_integral_sum (this) result (error)
    class(muli_trapezium_t), intent(in) :: this
    real(default) :: error
    error = sum (this%values (0:this%dim-1, d_integral_index))
  end function muli_trapezium_get_integral_sum

<Muli trapezium: trapezium: TBP>+=
  procedure :: get_value_at_position => muli_trapezium_get_value_at_position

<Muli trapezium: procedures>+=
  subroutine muli_trapezium_get_value_at_position (this, pos, subarray)
    class(muli_trapezium_t), intent(in) :: this
    real(default), intent(in) :: pos
    real(default), dimension(this%dim), intent(out) :: subarray
    subarray = this%get_r_value_array() - this%get_d_value() * &
      this%d_position / (this%r_position-pos)
  end subroutine muli_trapezium_get_value_at_position

<Muli trapezium: trapezium: TBP>+=
  procedure :: set_r_value => muli_trapezium_set_r_value

```

```

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_set_r_value (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values(0:this%dim-1, r_value_index) = subarray
  end subroutine muli_trapezium_set_r_value

<Muli trapezium: trapezium: TBP>+≡
  procedure :: set_d_value => muli_trapezium_set_d_value

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_set_d_value (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values(0:this%dim-1, d_value_index) = subarray
  end subroutine muli_trapezium_set_d_value

<Muli trapezium: trapezium: TBP>+≡
  procedure :: set_r_integral => muli_trapezium_set_r_integral

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_set_r_integral (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values(0:this%dim-1, r_integral_index) = subarray
  end subroutine muli_trapezium_set_r_integral

<Muli trapezium: trapezium: TBP>+≡
  procedure :: set_d_integral => muli_trapezium_set_d_integral

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_set_d_integral (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values (0:this%dim-1, d_integral_index) = subarray
  end subroutine muli_trapezium_set_d_integral

<Muli trapezium: trapezium: TBP>+≡
  procedure :: set_r_probability => muli_trapezium_set_r_probability

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_set_r_probability (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values (0:this%dim-1, r_probability_index) = subarray
  end subroutine muli_trapezium_set_r_probability

<Muli trapezium: trapezium: TBP>+≡
  procedure :: set_d_probability => muli_trapezium_set_d_probability

```



```

<Muli trapezium: procedures>+=
  subroutine muli_trapezium_set_d_probability (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values (0:this%dim-1,d_probability_index) = subarray
  end subroutine muli_trapezium_set_d_probability

<Muli trapezium: trapezium: TBP>+=
  procedure :: set_error => muli_trapezium_set_error

<Muli trapezium: procedures>+=
  subroutine muli_trapezium_set_error (this, subarray)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in), dimension(0:this%dim-1) :: subarray
    this%values (0:this%dim-1, error_index) = subarray
    this%measure_comp = sum (subarray)
  end subroutine muli_trapezium_set_error

<Muli trapezium: trapezium: TBP>+=
  procedure :: is_left_of => muli_trapezium_is_left_of

<Muli trapezium: procedures>+=
  pure function muli_trapezium_is_left_of (this, that) result (is_left)
    logical :: is_left
    class(muli_trapezium_t), intent(in) :: this, that
    is_left = this%r_position <= that%r_position !-that%d_position
    ! if (is_left.and.that%r_position < this%r_position) then
    !   print *,!"
    !   STOP
    ! end if
  end function muli_trapezium_is_left_of

<Muli trapezium: trapezium: TBP>+=
  procedure :: includes => muli_trapezium_includes

<Muli trapezium: procedures>+=
  elemental logical function muli_trapezium_includes &
    (this, dim, position, value, integral, probability) result (includes)
    class(muli_trapezium_t), intent(in) :: this
    integer, intent(in) :: dim
    real(default), intent(in), optional :: position, value, integral, probability
    includes = .true.
    if (present (position)) then
      if (this%get_l_position() > position .or. &
        position >= this%get_r_position()) includes = .false.
    end if
    if (present (value)) then
      if (this%get_l_value(dim) > value .or. value >= &
        this%get_r_value(dim)) includes = .false.
    end if
    if (present (integral)) then
      if (this%get_l_integral(dim) > integral .or. integral >= &
        this%get_r_integral(dim)) includes = .false.
    end if
  end function

```

```

    if (present (probability)) then
        if (this%get_l_probability(dim) > probability .or. &
            probability >= this%get_r_probability(dim)) includes = .false.
    end if
end function multi_trapezium_includes

```

<Muli trapezium: trapezium: TBP>+≡

```

    procedure :: to_node => multi_trapezium_to_node

```

<Muli trapezium: procedures>+≡

```

    subroutine multi_trapezium_to_node (this, value, list, tree)
        class(muli_trapezium_t), intent(in) :: this
        real(default), intent(in) :: value
        ! class(muli_trapezium_node_class_t), optional, pointer, intent(out) :: node
        class(muli_trapezium_list_t), optional, pointer, intent(out) :: list
        class(muli_trapezium_tree_t), optional, pointer, intent(out) :: tree
        ! if (present (node)) then
        !     allocate (node)
        !     node%dim = this%dim
        !     node%r_position = this%r_position
        !     node%d_position = this%d_position
        !     allocate (node%values (this%dim, value_dimension), source=this%values)
        ! end if
        if (present (list)) then
            allocate (list)
            list%dim = this%dim
            list%r_position = this%r_position
            list%d_position = this%d_position
            allocate (list%values (0:this%dim-1, value_dimension), source=this%values)
        end if
        if (present (tree)) then
            allocate (tree)
            tree%dim = this%dim
            tree%r_position = this%r_position
            tree%d_position = this%d_position
            allocate (tree%values (0:this%dim-1, value_dimension), source=this%values)
        end if
    end subroutine multi_trapezium_to_node

```

<Muli trapezium: trapezium: TBP>+≡

```

    procedure :: sum_up => multi_trapezium_sum_up

```

<Muli trapezium: procedures>+≡

```

    subroutine multi_trapezium_sum_up (this)
        class(muli_trapezium_t), intent(inout) :: this
        integer :: i
        if (allocated (this%values)) then
            do i = 1, 7
                this%values (0,i) = sum (this%values (1:this%dim-1,i))
            end do
        end if
    end subroutine multi_trapezium_sum_up

```

```

<Muli trapezium: trapezium: TBP>+=
  procedure :: approx_value => muli_trapezium_approx_value

<Muli trapezium: procedures>+=
  pure function muli_trapezium_approx_value (this, x) result (val)
    ! returns the values at x
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: val
    real(default), intent(in) :: x
    val = this%get_r_value_array() + (x - this%r_position) * &
      this%get_d_value() / this%d_position
  end function muli_trapezium_approx_value

```

This function returns the value at x.

```

<Muli trapezium: trapezium: TBP>+=
  procedure :: approx_value_n => muli_trapezium_approx_value_n

<Muli trapezium: procedures>+=
  elemental function muli_trapezium_approx_value_n (this, x, n) result (val)
    class(muli_trapezium_t), intent(in) :: this
    real(default) :: val
    real(default), intent(in) :: x
    integer, intent(in) :: n
    val = this%get_r_value_element(n) + (x - this%r_position) * &
      this%get_d_value_element(n) / this%d_position
  end function muli_trapezium_approx_value_n

```

This function returns the integral from x to r_position.

```

<Muli trapezium: trapezium: TBP>+=
  procedure :: approx_integral => muli_trapezium_approx_integral

<Muli trapezium: procedures>+=
  pure function muli_trapezium_approx_integral (this, x)
    class(muli_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: muli_trapezium_approx_integral
    real(default), intent(in) :: x
    muli_trapezium_approx_integral = &
      ! this%get_r_integral()+&
      ! (this%r_position-x)*this%get_r_value()+&
      ! (x**2-this%r_position**2)*this%get_d_integral()/(this%d_position*2D0)
      this%get_r_integral() + &
      ((this%r_position - x) * &
        (-this%get_d_value() * (this%r_position - x) + 2 * &
          this%d_position*this%get_r_value_array())) / &
      (2 * this%d_position)
  end function muli_trapezium_approx_integral

```

This function returns the integral from x to r_position.

```

<Muli trapezium: trapezium: TBP>+=
  procedure :: approx_integral_n => muli_trapezium_approx_integral_n

<Muli trapezium: procedures>+=
  elemental function muli_trapezium_approx_integral_n (this, x, n) result (val)
    class(muli_trapezium_t), intent(in) :: this

```

```

real(default) :: val
real(default), intent(in) :: x
integer, intent(in) :: n
val = this%get_r_integral_element (n) + ((this%r_position - x) * &
      (-this%get_d_value_element (n) * (this%r_position - x) + 2 * &
      this%d_position * this%get_r_value_element (n))) / &
      (2 * this%d_position)
end function multi_trapezium_approx_integral_n

```

This function returns the values at x.

```

<Multi trapezium: trapezium: TBP>+=
  procedure :: approx_probability => multi_trapezium_approx_probability

<Multi trapezium: procedures>+=
  pure function multi_trapezium_approx_probability (this, x) result (prop)
    class(multi_trapezium_t), intent(in) :: this
    real(default), dimension(this%dim) :: prop
    real(default), intent(in) :: x
    prop = exp (- this%approx_integral (x))
  end function multi_trapezium_approx_probability

```

This function returns the integral from x to r_position.

```

<Multi trapezium: trapezium: TBP>+=
  procedure :: approx_probability_n => multi_trapezium_approx_probability_n

<Multi trapezium: procedures>+=
  elemental function multi_trapezium_approx_probability_n (this, x, n) result (val)
    class(multi_trapezium_t), intent(in) :: this
    real(default) :: val
    real(default), intent(in) :: x
    integer, intent(in) :: n
    val = exp (- this%approx_integral_n (x, n))
  end function multi_trapezium_approx_probability_n

```

```

<Multi trapezium: trapezium: TBP>+=
  procedure :: approx_position_by_integral => &
    multi_trapezium_approx_position_by_integral

<Multi trapezium: procedures>+=
  elemental function multi_trapezium_approx_position_by_integral &
    (this, dim, int) result (val)
    class(multi_trapezium_t), intent(in) :: this
    real(default) :: val
    integer, intent(in) :: dim
    real(default), intent(in) :: int
    real(default) :: dpdv
    dpdv = (this%d_position / this%values (dim,d_value_index))
    val = this%r_position - dpdv * (this%values (dim, r_value_index) - &
      sqrt (((this%values (dim, r_integral_index) - int) * two / dpdv) + &
      this%values (dim, r_value_index)**2))
  end function multi_trapezium_approx_position_by_integral

```

```

<Multi trapezium: trapezium: TBP>+=
  ! procedure :: choose_partons => multi_trapezium_choose_partons

```

```

(Muli trapezium: trapezium: TBP)+≡
  procedure :: split => multi_trapezium_split

(Muli trapezium: procedures)+≡
  subroutine multi_trapezium_split (this, c_value, c_position, new_node)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), intent(in) :: c_position
    real(default), intent(in), dimension(this%dim) :: c_value
    class(muli_trapezium_t), intent(out), pointer :: new_node
    real(default) :: ndpr, ndpl
    real(default), dimension(:), allocatable :: ov, edv
    ndpr = this%r_position - c_position
    ndpl = this%d_position - ndpr
    allocate (ov (0:this%dim-1), source=this%get_r_value_array() - ndpr * &
      this%get_d_value() / this%d_position)
    allocate (edv (0:this%dim-1), source=c_value-ov)
    allocate (new_node)
    call new_node%initialize (dim=this%dim, r_position=c_position, &
      d_position=ndpl)
    call new_node%set_r_value (c_value)
    call new_node%set_d_value (this%get_d_value() + &
      c_value-this%get_r_value_array())
    call new_node%set_d_integral (ndpl*(this%get_d_value() - &
      this%get_r_value_array() - c_value) / two)
    call new_node%set_error (abs((edv*ndpl) / two))
    ! new_node%measure_comp = sum (abs((edv*ndpl) / two))
    this%d_position = ndpr
    call this%set_d_value (this%get_r_value_array() - c_value)
    call this%set_d_integral (- (ndpr*(this%get_r_value_array() + c_value) / two))
    call this%set_error (abs(edv*ndpr / two))
    ! this%measure_comp = sum (abs(edv*ndpr / two))
    ! write (*, "(1x,A)") "multi_trapezium_split: new errors:"
    ! write (*, "(3x,ES14.7)") this%get_error()
    ! write (*, "(3x,ES14.7)") new_node%get_error()
    ! write (*, "(3x,11(ES20.10)") new_node%get_d_integral()
    ! write (*, "(3x,11(ES20.10)") this%get_d_integral()
  end subroutine multi_trapezium_split

(Muli trapezium: trapezium: TBP)+≡
  procedure :: update => multi_trapezium_update

(Muli trapezium: procedures)+≡
  subroutine multi_trapezium_update (this)
    class(muli_trapezium_t), intent(inout) :: this
    real(default), dimension(:), allocatable :: integral
    real(default), dimension(0:this%dim-1) :: d_int
    !!! !!! !!! Workaround for gfortran 5.0 ICE
    d_int = this%get_d_integral ()
    allocate (integral (0:this%dim-1), source=d_int)
    call this%set_d_integral (-this%d_position * (this%get_r_value_array() &
      - this%get_d_value() / 2))
    call this%set_error (abs (this%get_d_integral() - integral))
    ! write (*, "(3x,11(ES20.10)") this%get_d_integral()
  end subroutine multi_trapezium_update

```

```

<Muli trapezium: node: TBP>≡
    procedure :: deserialize_from_marker => &
        muli_trapezium_node_deserialize_from_marker

<Muli trapezium: procedures>+≡
    subroutine muli_trapezium_node_deserialize_from_marker (this, name, marker)
        class(muli_trapezium_node_class_t), intent(out) :: this
        character(*), intent(in) :: name
        class(marker_t), intent(inout) :: marker
        integer(dik) :: status
        class(ser_class_t), pointer :: ser
        allocate (muli_trapezium_tree_t :: ser)
        call marker%push_reference (ser)
        allocate (muli_trapezium_list_t::ser)
        call marker%push_reference (ser)
        call serializable_deserialize_from_marker (this, name, marker)
        call marker%pop_reference (ser)
        deallocate (ser)
        call marker%pop_reference (ser)
        deallocate (ser)
    end subroutine muli_trapezium_node_deserialize_from_marker

<Muli trapezium: node: TBP>+≡
    procedure(muli_trapezium_append_interface), deferred :: append

<Muli trapezium: node: TBP>+≡
    procedure(muli_trapezium_final_interface), deferred :: finalize

<Muli trapezium: list: TBP>≡
    procedure :: append => muli_trapezium_list_append

<Muli trapezium: procedures>+≡
    subroutine muli_trapezium_list_append (this, right)
        class(muli_trapezium_list_t), intent(inout), target :: this
        class(muli_trapezium_node_class_t), intent(inout), target :: right
        this%right => right
        right%left => this
    end subroutine muli_trapezium_list_append

<Muli trapezium: node: TBP>+≡
    procedure :: nullify => muli_trapezium_node_nullify

<Muli trapezium: procedures>+≡
    subroutine muli_trapezium_node_nullify (this)
        class(muli_trapezium_node_class_t), intent(out) :: this
        nullify (this%left)
        nullify (this%right)
    end subroutine muli_trapezium_node_nullify

<Muli trapezium: node: TBP>+≡
    procedure :: get_left => muli_trapezium_node_get_left

```

```

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_node_get_left (this, left)
    class(muli_trapezium_node_class_t), intent(in) :: this
    class(muli_trapezium_node_class_t), pointer, intent(out) :: left
    left => this%left
  end subroutine muli_trapezium_node_get_left

<Muli trapezium: node: TBP>+≡
  procedure :: get_right => muli_trapezium_node_get_right

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_node_get_right (this, right)
    class(muli_trapezium_node_class_t), intent(in) :: this
    class(muli_trapezium_node_class_t), pointer, intent(out) :: right
    right => this%right
  end subroutine muli_trapezium_node_get_right

<Muli trapezium: node: TBP>+≡
  procedure :: get_leftmost => muli_trapezium_node_get_leftmost

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_node_get_leftmost (this, node)
    class(muli_trapezium_node_class_t), intent(in) :: this
    class(muli_trapezium_node_class_t), pointer, intent(out) :: node
    if (associated (this%left)) then
      node => this%left
      do while (associated (node%left))
        node => node%left
      end do
    else
      nullify (node)
    end if
  end subroutine muli_trapezium_node_get_leftmost

<Muli trapezium: node: TBP>+≡
  procedure :: get_rightmost => muli_trapezium_node_get_rightmost

<Muli trapezium: procedures>+≡
  subroutine muli_trapezium_node_get_rightmost (this, right)
    class(muli_trapezium_node_class_t), intent(in) :: this
    class(muli_trapezium_node_class_t), pointer, intent(out) :: right
    if (associated (this%right)) then
      right => this%right
      do while (associated (right%right))
        right => right%right
      end do
    else
      nullify (right)
    end if
  end subroutine muli_trapezium_node_get_rightmost

```

```

<Muli trapezium: node: TBP>+≡
generic :: decide => decide_by_value, decide_by_position
procedure :: decide_by_value => muli_trapezium_node_decide_by_value
procedure :: decide_by_position => muli_trapezium_node_decide_by_position

<Muli trapezium: procedures>+≡
subroutine muli_trapezium_node_decide_by_value (this, value, dim, record, node)
  class(muli_trapezium_node_class_t), intent(in) :: this
  real(default), intent(in) :: value
  integer, intent(in) :: record, dim
  class(muli_trapezium_node_class_t), pointer, intent(out) :: node
  if (this%values (dim, record) > value) then
    node => this%left
  else
    node => this%right
  end if
end subroutine muli_trapezium_node_decide_by_value

<Muli trapezium: procedures>+≡
subroutine muli_trapezium_node_decide_by_position (this, position, node)
  class(muli_trapezium_node_class_t), intent(in) :: this
  real(default), intent(in) :: position
  class(muli_trapezium_node_class_t), pointer, intent(out) :: node
  if (this%r_position > position) then
    node => this%left
  else
    node => this%right
  end if
end subroutine muli_trapezium_node_decide_by_position

<Muli trapezium: node: TBP>+≡
procedure :: decide_decreasing => muli_trapezium_node_decide_decreasing

<Muli trapezium: procedures>+≡
subroutine muli_trapezium_node_decide_decreasing &
  (this, value, dim, record, node)
  class(muli_trapezium_node_class_t), intent(in) :: this
  real(default), intent(in) :: value
  integer, intent(in) :: record, dim
  class(muli_trapezium_node_class_t), pointer, intent(out) :: node
  if (this%values (dim, record) <= value) then
    node => this%left
  else
    node => this%right
  end if
end subroutine muli_trapezium_node_decide_decreasing

<Muli trapezium: node: TBP>+≡
procedure :: to_tree => muli_trapezium_node_to_tree

<Muli trapezium: procedures>+≡
subroutine muli_trapezium_node_to_tree (this, out_tree)
  class(muli_trapezium_node_class_t), target, intent(in) :: this
  class(muli_trapezium_tree_t), intent(out) :: out_tree

```



```

        out_tree%left => this%left
        out_tree%right => this%right
    end subroutine muli_trapezium_node_to_tree

<Muli trapezium: node: TBP>+≡
    procedure :: untangle => muli_trapezium_node_untangle

<Muli trapezium: procedures>+≡
    subroutine muli_trapezium_node_untangle(this)
        class(muli_trapezium_node_class_t), intent(inout), target :: this
        if (associated (this%left)) then
            if (associated (this%left%right, this)) then
                nullify (this%left%right)
                nullify (this%left)
            end if
        end if
    end subroutine muli_trapezium_node_untangle

<Muli trapezium: node: TBP>+≡
    procedure :: apply => muli_trapezium_node_apply

<Muli trapezium: procedures>+≡
    recursive subroutine muli_trapezium_node_apply(this,proc)
        class(muli_trapezium_node_class_t), intent(inout) :: this
        interface
            subroutine proc(this)
                import muli_trapezium_node_class_t
                class(muli_trapezium_node_class_t), intent(inout) :: this
            end subroutine proc
        end interface
        if (associated(this%right))call proc(this%right)
        if (associated(this%left))call proc(this%left)
        call proc(this)
    end subroutine muli_trapezium_node_apply

<Muli trapezium: node: TBP>+≡
    ! procedure :: copy => muli_trapezium_node_copy
    ! generic :: assignment(=) => copy
    ! procedure, deferred :: approx => muli_trapezium_node_approx

<Muli trapezium: tree: TBP>≡
    procedure :: write_to_marker => muli_trapezium_tree_write_to_marker

<Muli trapezium: procedures>+≡
    subroutine muli_trapezium_tree_write_to_marker (this, marker, status)
        class(muli_trapezium_tree_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        class(muli_trapezium_list_t), pointer :: list
        class(ser_class_t), pointer :: ser
        call marker%mark_begin ("muli_trapezium_tree_t")
        call this%get_left_list (list)
        ser => list
        call marker%mark_pointer ("list", ser)
    end subroutine

```

```

        call marker%mark_end ("multi_trapezium_tree_t")
    end subroutine multi_trapezium_tree_write_to_marker

```

<Multi trapezium: tree: TBP>+≡

```

    procedure :: read_from_marker => multi_trapezium_tree_read_from_marker

```

<Multi trapezium: procedures>+≡

```

    subroutine multi_trapezium_tree_read_from_marker (this, marker, status)
        class(multi_trapezium_tree_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        class(ser_class_t), pointer :: ser
        call marker%pick_begin ("multi_trapezium_tree_t", status=status)
        call marker%pick_pointer ("list", ser)
        if (associated (ser)) then
            select type (ser)
            class is (multi_trapezium_list_t)
                call ser%to_tree (this)
            class default
                nullify (this%left)
                nullify (this%right)
                nullify (this%down)
            end select
        else
            nullify (this%left)
            nullify (this%right)
            nullify (this%down)
        end if
        call marker%pick_end ("multi_trapezium_tree_t", status)
    end subroutine multi_trapezium_tree_read_from_marker

```

<Multi trapezium: tree: TBP>+≡

```

    procedure :: print_to_unit => multi_trapezium_tree_print_to_unit

```

<Multi trapezium: procedures>+≡

```

    recursive subroutine multi_trapezium_tree_print_to_unit &
        (this, unit, parents, components, peers)
        class(multi_trapezium_tree_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        class(ser_class_t), pointer :: ser
        if (parents > 0) call multi_trapezium_print_to_unit &
            (this, unit, parents-1, components, peers)
        ser => this%down
        call serialize_print_peer_pointer (ser, unit, i_one, i_zero, i_one, "DOWN")
        if (associated (this%left)) then
            select type (sertmp => this%left)
            class is (multi_trapezium_list_t)
                ser => sertmp
                call serialize_print_peer_pointer &
                    (ser, unit, parents, components, i_zero, "LEFT")
            class default
                call serialize_print_peer_pointer &
                    (ser, unit, parents, components, peers, "LEFT")
        end if
    end subroutine

```

```

        end select
    else
        write (unit, "(1x,A)") "Left is not associated."
    end if
    if (associated (this%right)) then
        select type (sertmp => this%right)
        class is (multi_trapezium_list_t)
            ser => sertmp
            call serialize_print_peer_pointer &
                (ser, unit, parents, components, i_zero, "RIGHT")
        class default
            call serialize_print_peer_pointer &
                (ser, unit, parents, components, peers, "RIGHT")
        end select
    else
        write (unit, "(1x,A)") "Right is not associated."
    end if
end subroutine multi_trapezium_tree_print_to_unit

<Multi trapezium: tree: TBP>+≡
    procedure, nopass :: get_type => multi_trapezium_tree_get_type

<Multi trapezium: procedures>+≡
    pure subroutine multi_trapezium_tree_get_type (type)
        character(:),allocatable, intent(out) :: type
        allocate (type, source="multi_trapezium_tree_t")
    end subroutine multi_trapezium_tree_get_type

<Multi trapezium: tree: TBP>+≡
    procedure, nopass :: verify_type => multi_trapezium_tree_verify_type

<Multi trapezium: procedures>+≡
    elemental logical function multi_trapezium_tree_verify_type (type) result (match)
        character(*), intent(in) :: type
        match = type == "multi_trapezium_tree_t"
    end function multi_trapezium_tree_verify_type

<Multi trapezium: tree: TBP>+≡
    procedure :: nullify => multi_trapezium_tree_nullify

<Multi trapezium: procedures>+≡
    subroutine multi_trapezium_tree_nullify (this)
        class(multi_trapezium_tree_t), intent(out) :: this
        call multi_trapezium_node_nullify (this)
        nullify (this%down)
    end subroutine multi_trapezium_tree_nullify

<Multi trapezium: tree: TBP>+≡
    procedure :: finalize => multi_trapezium_tree_finalize

<Multi trapezium: procedures>+≡
    recursive subroutine multi_trapezium_tree_finalize (this)
        class(multi_trapezium_tree_t), intent(inout) :: this
        if (associated (this%right)) then

```

```

        call this%right%untangle ()
        call this%right%finalize ()
        deallocate (this%right)
    end if
    if (associated (this%left)) then
        call this%left%untangle ()
        call this%left%finalize ()
        deallocate (this%left)
    end if
    this%dim = 0
end subroutine multi_trapezium_tree_finalize

```

<Muli trapezium: tree: TBP>+≡

```

    procedure :: decide_by_value => multi_trapezium_tree_decide_by_value

```

<Muli trapezium: procedures>+≡

```

    subroutine multi_trapezium_tree_decide_by_value (this, value, dim, record, node)
        class(multi_trapezium_tree_t), intent(in) :: this
        real(default), intent(in) :: value
        integer, intent(in) :: record, dim
        class(multi_trapezium_node_class_t), pointer, intent(out) :: node
        if (this%down%values (dim, record) > value) then
            node => this%left
        else
            node => this%right
        end if
    end subroutine multi_trapezium_tree_decide_by_value

```

<Muli trapezium: tree: TBP>+≡

```

    procedure :: decide_by_position => multi_trapezium_tree_decide_by_position

```

<Muli trapezium: procedures>+≡

```

    subroutine multi_trapezium_tree_decide_by_position (this, position, node)
        class(multi_trapezium_tree_t), intent(in) :: this
        real(default), intent(in) :: position
        class(multi_trapezium_node_class_t), pointer, intent(out) :: node
        if (this%down%r_position > position) then
            node => this%left
        else
            node => this%right
        end if
    end subroutine multi_trapezium_tree_decide_by_position

```

<Muli trapezium: tree: TBP>+≡

```

    procedure :: decide_decreasing => multi_trapezium_tree_decide_decreasing

```

<Muli trapezium: procedures>+≡

```

    subroutine multi_trapezium_tree_decide_decreasing &
        (this, value, dim, record, node)
        class(multi_trapezium_tree_t), intent(in) :: this
        real(default), intent(in) :: value
        integer, intent(in) :: record, dim
        ! integer, save :: count=0
        class(multi_trapezium_node_class_t), pointer, intent(out) :: node

```

```

! count = count + 1
if (this%down%values (dim, record) <= value) then
! print ('("Decide: value(",I2,"","I1,")=",E20.7," > ",E20.7, &
!      ": go left.")'), dim, record, this%down%values(dim, record), value
node => this%left
else
! print ('("Decide: value(",I2,"","I1,")=",E20.7," <= ", &
!      E20.7,"": go right.")'), &
!      dim, record, this%down%values(dim, record), value
node => this%right
end if
end subroutine multi_trapezium_tree_decide_decreasing

```

(Multi trapezium: tree: TBP)+≡

```

procedure :: get_left_list => multi_trapezium_tree_get_left_list

```

(Multi trapezium: procedures)+≡

```

subroutine multi_trapezium_tree_get_left_list (this, list)
class(multi_trapezium_tree_t), intent(in) :: this
class(multi_trapezium_list_t), pointer, intent(out) :: list
class(multi_trapezium_node_class_t), pointer::node
call this%get_leftmost (node)
if (associated (node)) then
select type (node)
class is (multi_trapezium_list_t)
list => node
class default
nullify (list)
end select
else
nullify (list)
end if
end subroutine multi_trapezium_tree_get_left_list

```

(Multi trapezium: tree: TBP)+≡

```

procedure :: get_right_list => multi_trapezium_tree_get_right_list

```

(Multi trapezium: procedures)+≡

```

subroutine multi_trapezium_tree_get_right_list (this, list)
class(multi_trapezium_tree_t), intent(in) :: this
class(multi_trapezium_list_t), pointer, intent(out) :: list
class(multi_trapezium_node_class_t), pointer::node
call this%get_rightmost (node)
if (associated (node)) then
select type (node)
class is (multi_trapezium_list_t)
list => node
class default
nullify (list)
end select
else
nullify (list)
end if
end subroutine multi_trapezium_tree_get_right_list

```

```

<Muli trapezium: tree: TBP>+≡
generic :: find => find_by_value, find_by_position
procedure :: find_by_value => multi_trapezium_tree_find_by_value
procedure :: find_by_position => multi_trapezium_tree_find_by_position

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_tree_find_by_value (this, value, dim, record, node)
  class(muli_trapezium_tree_t), intent(in), target :: this
  real(default), intent(in) :: value
  integer, intent(in) :: record, dim
  class(muli_trapezium_node_class_t), pointer, intent(out) :: node
  node => this
  do while (.not. allocated (node%values))
    call node%decide (value, dim, record, node)
  end do
end subroutine multi_trapezium_tree_find_by_value

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_tree_find_by_position (this, position, node)
  class(muli_trapezium_tree_t), intent(in), target :: this
  real(default), intent(in) :: position
  class(muli_trapezium_node_class_t), pointer, intent(out) :: node
  node => this
  do while (.not. allocated (node%values))
    call node%decide (position, node)
  end do
end subroutine multi_trapezium_tree_find_by_position

<Muli trapezium: tree: TBP>+≡
procedure :: find_decreasing => multi_trapezium_tree_find_decreasing

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_tree_find_decreasing (this, value, dim, node)
  class(muli_trapezium_tree_t), intent(in), target :: this
  real(default), intent(in) :: value
  integer, intent(in) :: dim
  class(muli_trapezium_node_class_t), pointer, intent(out) :: node
  node => this
  do while (.not. allocated (node%values))
    call node%decide_decreasing (value, dim, r_integral_index, node)
  end do
end subroutine multi_trapezium_tree_find_decreasing

<Muli trapezium: tree: TBP>+≡
procedure :: approx_by_integral => multi_trapezium_tree_approx_by_integral

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_tree_approx_by_integral &
  (this, int, dim, in_range, position, value, integral, content)
  class(muli_trapezium_tree_t), intent(in), target :: this
  real(default), intent(in) :: int
  integer, intent(in) :: dim
  logical, intent(out) :: in_range
  class(muli_trapezium_node_class_t), pointer, intent(out), optional :: content

```

```

real(default), intent(out), optional :: position, value, integral
integer :: i
real(default) :: DINT      !,l_prop,r_prop,d_prop
real(default) :: RP, DP, RV, DV, RI      !FC = gfortran
class(muli_trapezium_node_class_t), pointer :: node
node => this
do while (.not. allocated (node%values))
    call node%decide_decreasing(INT, dim, r_integral_index, node)
end do
if (    int<=node%values(dim,r_integral_index)-node%values(dim,d_integral_index)&
    &.and.&
    &int>=node%values(dim,r_integral_index)) then
    in_range=.true.
    !      associate(&!FC = nagfor
    !          &RP=>node%r_position,&!FC = nagfor
    !          &DP=>node%d_position,&!FC = nagfor
    !          &RV=>node%values(dim,r_value_index),&!FC = nagfor
    !          &DV=>node%values(dim,d_value_index),&!FC = nagfor
    !          &RI=>node%values(dim,r_integral_index))!FC = nagfor
    RP=node%r_position!FC = gfortran
    DP=node%d_position!FC = gfortran
    RV=node%values(dim,r_value_index)!FC = gfortran
    DV=node%values(dim,d_value_index)!FC = gfortran
    RI=node%values(dim,r_integral_index)!FC = gfortran
    if (present(position)) then
        DINT=(ri-int)*2D0*dv/dp
        position=rp-(dp/dv)*(rv-sqrt(dint+rv**2))
    end if
    if (present(value)) then
        value=Sqrt(dp*(-2*dv*int + 2*dv*ri + dp*rv**2))/dp
    end if
    if (present(integral)) then
        integral=int
    end if
    if (present(content)) then
        content=>node
    end if
    !      end associate!FC = nagfor
else
    in_range=.false.
end if
end subroutine muli_trapezium_tree_approx_by_integral

```

<Muli trapezium: tree: TBP>+≡

```
procedure :: approx_by_probability => muli_trapezium_tree_approx_by_probability
```

<Muli trapezium: procedures>+≡

```

subroutine muli_trapezium_tree_approx_by_probability &
    (this, prop, dim, in_range, position, value, integral, content)
class(muli_trapezium_tree_t), intent(in), target :: this
real(default), intent(in) :: prop
integer, intent(in) :: dim
logical, intent(out) :: in_range
class(muli_trapezium_node_class_t), pointer, intent(out), optional :: content

```

```

real(default), intent(out), optional :: position, value, integral
integer :: i
real(default) :: int
class(muli_trapezium_node_class_t), pointer :: node
if (zero < prop .and. prop < one) then
    node => this
    int = -log (prop)
    call muli_trapezium_tree_approx_by_integral &
        (this, int, dim, in_range, position, value, integral, content)
else
    in_range = .false.
end if
end subroutine muli_trapezium_tree_approx_by_probability

```

<Muli trapezium: tree: TBP>+≡

```

procedure :: to_tree => muli_trapezium_tree_to_tree

```

<Muli trapezium: procedures>+≡

```

subroutine muli_trapezium_tree_to_tree (this, out_tree)
    class(muli_trapezium_tree_t), target, intent(in) :: this
    class(muli_trapezium_tree_t), intent(out) :: out_tree
    out_tree%left => this%left
    out_tree%right => this%right
    out_tree%down => this%down
end subroutine muli_trapezium_tree_to_tree

```

<Muli trapezium: tree: TBP>+≡

```

procedure :: append => muli_trapezium_tree_append

```

<Muli trapezium: procedures>+≡

```

subroutine muli_trapezium_tree_append(this,right)
    class(muli_trapezium_tree_t), intent(inout), target :: this
    class(muli_trapezium_node_class_t), intent(inout), target :: right
    call msg_error ("muli_trapezium_tree_append: Not yet implemented.")
end subroutine muli_trapezium_tree_append

```

<Muli trapezium: tree: TBP>+≡

```

procedure :: gnuplot => muli_trapezium_tree_gnuplot

```

<Muli trapezium: procedures>+≡

```

subroutine muli_trapezium_tree_gnuplot (this, dir)
    class(muli_trapezium_tree_t), intent(in) :: this
    character(len=*), intent(in) :: dir
    class(muli_trapezium_list_t), pointer :: list
    call this%get_left_list (list)
    call list%gnuplot (dir)
end subroutine muli_trapezium_tree_gnuplot

```

<Muli trapezium: list: TBP>+≡

```

procedure :: write_to_marker => muli_trapezium_list_write_to_marker

```



```

<Muli trapezium: procedures>+=
recursive subroutine muli_trapezium_list_write_to_marker (this, marker, status)
  class(muli_trapezium_list_t), intent(in) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  class(ser_class_t), pointer :: ser
  call marker%mark_begin ("muli_trapezium_list_t")
  call muli_trapezium_write_to_marker (this, marker, status)
  ser => this%right
  call marker%mark_pointer ("right", ser)
  call marker%mark_end ("muli_trapezium_list_t")
end subroutine muli_trapezium_list_write_to_marker

```

```

<Muli trapezium: list: TBP>+=
procedure :: read_from_marker => muli_trapezium_list_read_from_marker

```

```

<Muli trapezium: procedures>+=
recursive subroutine muli_trapezium_list_read_from_marker (this, marker, status)
  class(muli_trapezium_list_t), intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  call msg_warning ("muli_trapezium_list_read_from_marker: " // &
    "You cannot deserialize a list with this subroutine.")
  call msg_error ("Use muli_trapezium_list_read_target_from_marker instead.")
end subroutine muli_trapezium_list_read_from_marker

```

```

<Muli trapezium: list: TBP>+=
procedure :: read_target_from_marker => &
  muli_trapezium_list_read_target_from_marker

```

```

<Muli trapezium: procedures>+=
recursive subroutine muli_trapezium_list_read_target_from_marker &
  (this, marker, status)
  class(muli_trapezium_list_t), target, intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  class(ser_class_t), pointer :: ser
  call marker%pick_begin ("muli_trapezium_list_t", status=status)
  call muli_trapezium_read_from_marker (this, marker, status)
  call marker%pick_pointer ("right", ser)
  if (associated (ser)) then
    select type (ser)
      class is (muli_trapezium_list_t)
        this%right => ser
        ser%left => this
      class default
        nullify (this%right)
        call msg_error ("muli_trapezium_list_read_target_from_marker: " &
          // "Unexpected type for right component.")
    end select
  else
    nullify (this%right)
  end if
  call marker%pick_end ("muli_trapezium_list_t", status)

```

```

end subroutine multi_trapezium_list_read_target_from_marker

<Multi trapezium: list: TBP>+≡
  procedure :: print_to_unit => multi_trapezium_list_print_to_unit

<Multi trapezium: procedures>+≡
  recursive subroutine multi_trapezium_list_print_to_unit &
    (this, unit, parents, components, peers)
    class(multi_trapezium_list_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    class(ser_class_t), pointer :: ser
    if (parents > 0) call multi_trapezium_print_to_unit &
      (this, unit, parents-1, components, peers)
    ser => this%left
    call serialize_print_peer_pointer &
      (ser, unit, -i_one, -i_one, -i_one, "LEFT")
    ser => this%right
    call serialize_print_peer_pointer &
      (ser, unit, parents, components, peers, "RIGHT")
  end subroutine multi_trapezium_list_print_to_unit

<Multi trapezium: list: TBP>+≡
  procedure, nopass :: get_type => multi_trapezium_list_get_type

<Multi trapezium: procedures>+≡
  pure subroutine multi_trapezium_list_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="multi_trapezium_list_t")
  end subroutine multi_trapezium_list_get_type

<Multi trapezium: list: TBP>+≡
  procedure, nopass :: verify_type => multi_trapezium_list_verify_type

<Multi trapezium: procedures>+≡
  elemental logical function multi_trapezium_list_verify_type (type) result (match)
    character(*), intent(in) :: type
    match = type == "multi_trapezium_list_t"
  end function multi_trapezium_list_verify_type

<Multi trapezium: list: TBP>+≡
  procedure :: finalize => multi_trapezium_list_finalize

<Multi trapezium: procedures>+≡
  recursive subroutine multi_trapezium_list_finalize(this)
    class(multi_trapezium_list_t), intent(inout)::this
    if (associated(this%right)) then
      call this%right%finalize()
      deallocate(this%right)
    end if
    this%dim=0
  end subroutine multi_trapezium_list_finalize

```

```

<Muli trapezium: list: TBP>+≡
generic :: insert_right => insert_right_a  !, insert_right_b
procedure :: insert_right_a => multi_trapezium_list_insert_right_a
! procedure :: insert_right_b => multi_trapezium_list_insert_right_b

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_list_insert_right_a (this, value, content, new_node)
  class(muli_trapezium_list_t), intent(inout), target :: this
  real(default), intent(in) :: value
  class(muli_trapezium_t), intent(in) :: content
  class(muli_trapezium_list_t), pointer, intent(out) :: new_node
  class(muli_trapezium_list_t), pointer :: tmp_list
  call content%to_node (value, list=tmp_list)
  if (associated (this%right)) then
    this%right%left => tmp_list
    tmp_list%right => this%right
  else
    nullify (tmp_list%right)
  end if
  this%right => tmp_list
  tmp_list%left => this
  new_node => tmp_list
end subroutine multi_trapezium_list_insert_right_a

<Muli trapezium: list: TBP>+≡
generic :: insert_left => insert_left_a  !, insert_left_b
procedure :: insert_left_a => multi_trapezium_list_insert_left_a
! procedure :: insert_left_b => multi_trapezium_list_insert_left_b

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_list_insert_left_a (this, value, content, new_node)
  class(muli_trapezium_list_t), intent(inout), target :: this
  real(default), intent(in) :: value
  class(muli_trapezium_t), intent(in) :: content
  class(muli_trapezium_list_t), pointer, intent(out) :: new_node
  call content%to_node (value, list=new_node)
  new_node%right => this
  if (associated (this%left)) then
    new_node%left => this%left
    this%left%right => new_node
  else
    nullify (new_node%left)
  end if
  this%left => new_node
end subroutine multi_trapezium_list_insert_left_a

<Muli trapezium: list: TBP>+≡
procedure :: to_tree => multi_trapezium_list_to_tree

<Muli trapezium: procedures>+≡
subroutine multi_trapezium_list_to_tree (this, out_tree)
  class(muli_trapezium_list_t), target, intent(in) :: this
  class(muli_trapezium_tree_t), intent(out) :: out_tree
  type(muli_trapezium_tree_t), target :: do_list
  class(muli_trapezium_node_class_t), pointer :: this_entry, do_list_entry, node

```

```

class(multi_trapezium_tree_t),pointer :: tree1,tree2
integer :: ite,log,n_deep,n_leaves
n_leaves=0
this_entry => this
count: do while(associated(this_entry))
    n_leaves=n_leaves+1
    this_entry=>this_entry%right
end do count
call ilog2(n_leaves,log,n_deep)
this_entry => this
do_list_entry => do_list
deep: do ite=0,n_deep-1
    allocate(tree1)
    tree1%down=>this_entry%right
    allocate(tree2)
    tree2%down=>this_entry
    tree2%left=>this_entry
    tree2%right=>this_entry%right
    tree1%left=>tree2
    this_entry => this_entry%right%right
    do_list_entry%right=>tree1
    do_list_entry=>tree1
end do deep
rest: do while(associated(this_entry))
    allocate(tree1)
    tree1%down=>this_entry
    tree1%left=>this_entry
    do_list_entry%right => tree1
    do_list_entry => tree1
    this_entry => this_entry%right
    ite=ite+1
end do rest
tree: do while(ite>2)
    do_list_entry => do_list%right
    node=>do_list
    level: do while(associated(do_list_entry))
        node%right=>do_list_entry%right
        node=>do_list_entry%right
        do_list_entry%right=>node%left
        node%left=>do_list_entry
        do_list_entry=>node%right
        ite=ite-1
    end do level
end do tree
node=>do_list%right
select type(node)
type is (multi_trapezium_tree_t)
    call node%to_tree(out_tree)
class default
    print *,"multi_trapezium_list_to_tree"
    print *,"unexpeted type for do_list%right"
end select
out_tree%right=>out_tree%right%left
if (allocated(out_tree%values)) then

```

```

        deallocate(out_tree%values)
    end if
    deallocate(do_list%right%right)
    deallocate(do_list%right)
end subroutine multi_trapezium_list_to_tree

```

<Multi trapezium: list: TBP>+≡

```

    procedure :: gnuplot => multi_trapezium_list_gnuplot

```

<Multi trapezium: procedures>+≡

```

subroutine multi_trapezium_list_gnuplot (this, dir)
    class(multi_trapezium_list_t), intent(in), target :: this
    character(len=*), intent(in) :: dir
    character(len=*), parameter :: val_file = "/value.plot"
    character(len=*), parameter :: int_file = "/integral.plot"
    character(len=*), parameter :: err_file = "/integral_error.plot"
    character(len=*), parameter :: pro_file = "/probability.plot"
    character(len=*), parameter :: den_file = "/density.plot"
    character(len=*), parameter :: fmt = "(ES20.10)"
    class(multi_trapezium_node_class_t), pointer :: list
    integer :: val_unit, err_unit, int_unit, pro_unit, den_unit
    list => this
    call generate_unit (val_unit, 100, 1000)
    open (val_unit, file = dir // val_file)
    call generate_unit (int_unit, 100, 1000)
    open (int_unit, file = dir // int_file)
    call generate_unit (err_unit, 100, 1000)
    open (err_unit, file = dir // err_file)
    call generate_unit (pro_unit, 100, 1000)
    open (pro_unit, file = dir // pro_file)
    call generate_unit (den_unit, 100, 1000)
    open (den_unit, file = dir // den_file)
    do while (associated (list))
        ! print *,list%r_position,list%get_r_value()
        !!! !!! !!! gfortran 5.0.0 ICE
        ! write (val_unit, fmt, advance="no") list%r_position
        ! call write_array (val_unit, list%get_r_value_array(), fmt)
        ! write (int_unit,fmt,advance="no") list%r_position
        ! call write_array (int_unit, list%get_r_integral(), fmt)
        ! write (err_unit, fmt, advance="no") list%r_position
        ! call write_array (err_unit, list%get_error(), fmt)
        ! write (pro_unit, fmt, advance="no") list%r_position
        ! call write_array (pro_unit, list%get_r_probability(), fmt)
        ! write (den_unit, fmt, advance="no") list%r_position
        ! call write_array (den_unit, list%get_r_probability() * &
        !     list%get_r_value_array(), fmt)
        list => list%right
    end do
    close (val_unit)
    close (int_unit)
    close (err_unit)
    close (pro_unit)
    close (den_unit)
contains

```

```

subroutine write_array (unit, array, form)
  integer, intent(in) :: unit
  real(default), dimension(:), intent(in) :: array
  character(len=*), intent(in) :: form
  integer :: n
  do n = 1, size(array)
    write (unit, form, advance="no") array(n)
    flush (unit)
  end do
  write (unit, *)
end subroutine write_array
end subroutine multi_trapezium_list_gnuplot

```

(Multi trapezium: list: TBP)+≡

```

procedure :: integrate => multi_trapezium_list_integrate

```

(Multi trapezium: procedures)+≡

```

subroutine multi_trapezium_list_integrate (this, integral_sum, error_sum)
  class(multi_trapezium_list_t), intent(in), target :: this
  real(default), intent(out) :: error_sum, integral_sum
  real(default), dimension(:), allocatable :: integral
  class(multi_trapezium_node_class_t), pointer :: node
  allocate (integral (0:this%dim-1))
  call this%get_rightmost (node)
  integral = 0._default
  integral_sum = 0._default
  error_sum = 0._default
  integrate: do while (associated (node))
    node%values(1,r_value_index) = sum(node%values(1:this%dim-1,r_value_index))
    node%values(1,d_value_index) = sum(node%values(1:this%dim-1,d_value_index))
    ! node%values (1, r_integral_index) = &
    !   sum (node%values (1:this%dim-1, r_integral_index))
    ! node%values (1, d_integral_index) = &
    !   sum (node%values (1:this%dim-1, d_integral_index))
    node%values(1, error_index) = sum (node%values(1:this%dim-1, error_index))
    error_sum = error_sum + node%values (1, error_index)
    !!! !!! !!! gfortran 5.0.0 ICE
    ! call node%set_d_integral (node%get_d_position() * &
    !   (node%get_d_value() / 2 - node%get_r_value_array ()))
    call node%set_r_probability (exp (-integral))
    call node%set_r_integral (integral)
    !!! !!! !!! gfortran 5.0.0 ICE
    ! integral = integral - node%get_d_integral()
    ! call node%set_d_probability (node%get_r_probability() - exp(-integral))
    ! call multi_trapezium_write (node, output_unit)
    call node%get_left (node)
  end do integrate
  integral_sum = integral (1)
end subroutine multi_trapezium_list_integrate

```

(Multi trapezium: list: TBP)+≡

```

procedure :: check => multi_trapezium_list_check

```

(Multi trapezium: procedures)+≡

```

recursive subroutine multi_trapezium_list_check (this)
  class(multi_trapezium_list_t), intent(in), target :: this
  class(multi_trapezium_node_class_t), pointer :: tn, next
  real(default), parameter :: eps = 1E-10_default
  logical::test
  if (associated(this%right)) then
    next=>this%right
    test=(this%r_position.le.this%right%get_l_position()+eps)
    print *, "position check: ", test
    if (.not.test) then
      call this%print_parents()
      call next%print_parents()
    end if
    select type (next)
    class is (multi_trapezium_list_t)
      tn=>this
      print *, "structure check: ", associated(tn,next%left)
      print *, "class check:      T"
      call next%check()
    class default
      print *, "class check:      F"
    end select
  else
    print *, "end of list at ", this%r_position
  end if
end subroutine multi_trapezium_list_check

```

(Multi trapezium: list: TBP)+≡

```

procedure :: apply => multi_trapezium_list_apply

```

(Multi trapezium: procedures)+≡

```

recursive subroutine multi_trapezium_list_apply (this, proc)
  class(multi_trapezium_list_t), intent(inout) :: this
  interface
    subroutine proc (this)
      import multi_trapezium_node_class_t
      class(multi_trapezium_node_class_t), intent(inout) :: this
    end subroutine proc
  end interface
  if (associated (this%right)) call this%right%apply (proc)
  call proc (this)
end subroutine multi_trapezium_list_apply

```

(Multi trapezium: procedures)+≡

```

!  subroutine multi_trapezium_list_insert_right_old &
!    (this, value, content, new_node)
!    class(multi_trapezium_list_t), intent(inout), target :: this
!    real(default), intent(in) :: value
!    class(multi_trapezium_t), intent(in) :: content
!    class(multi_trapezium_list_t), pointer, intent(out) :: new_node
!    call content%to_node (value, list=new_node)
!    new_node%left => this
!    if (associated (this%right)) then

```

```

!      new_node%right => this%right
!      this%right%left => new_node
!      else
!          nullify (new_node%right)
!      end if
!      this%right => new_node
!  end subroutine multi_trapezium_list_insert_right_old

```

```

<Multi trapezium: procedures>+≡
!  subroutine multi_trapezium_node_error_no_content (this)
!      class(multi_trapezium_node_class_t), intent(in) :: this
!!      print ("multi_trapezium_node: Trying to access unallocated content.")
!!      call this%print()
!  end subroutine multi_trapezium_node_error_no_content

```

21.6 Fibonacci trees

This file contains the module `multi_fibonacci_tree`. A fibonacci tree is a self-balancing binary tree. "Balanced" means that the depth of the left successor may differ from the depth of the right successor in any node by maximally one. The maximally unbalanced tree is maximally unbalanced in every node. So the number of leaves of a maximally unbalanced fibonacci tree of depth n is precisely the n th fibonacci number.

We use this tree for the adaptive quadrature. In every iteration of the algorithm, we have to pick the segment with largest integration error, cut it into pieces and calculate the new integration error for the pieces. A binary tree is obviously a good choice for sorting these segments. The problem is, that we always pick leaves from the same side of the tree. So the tree must decline at one side and grow at the other side. Sorting gets less efficient and finally most of the overall CPU time gets wasted for sorting. This tree outperforms a naive binary tree significantly in this particular job.

```

<File header>+≡
<multi_fibonacci_tree.f90>≡

module multi_fibonacci_tree

  <Use kinds>
    use diagnostics
    use multi_base

  <Standard module head>

  <Multi fibonacci: public>

  <Multi fibonacci: variables>

  <Multi fibonacci: types>

contains

```



```

    <Muli fibonacci: procedures>

end module muli_fibonacci_tree

<Muli fibonacci: variables>≡
    character(*), parameter :: no_par = "edge=\noparent"
    character(*), parameter :: no_ret = "edge=\noreturn"
    character(*), parameter :: no_kid = "edge=\nochild"
    character(*), parameter :: le_kid = "edge=\childofleave"

<Muli fibonacci: public>≡
    public :: fibonacci_node_t

<Muli fibonacci: types>≡
    type, extends (measure_class_t) :: fibonacci_node_t
        ! private
        class(fibonacci_node_t), pointer :: up => null()
        class(measure_class_t), pointer :: down => null()
        class(fibonacci_node_t), pointer :: left => null()
        class(fibonacci_node_t), pointer :: right => null()
        integer :: depth = 0
        ! real(default) :: value
    contains
        <Muli fibonacci: fibonacci node: TBP>
    end type fibonacci_node_t

<Muli fibonacci: fibonacci node: TBP>≡
    procedure :: write_to_marker => fibonacci_node_write_to_marker

<Muli fibonacci: procedures>≡
    recursive subroutine fibonacci_node_write_to_marker (this, marker, status)
        class(fibonacci_node_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        class(ser_class_t), pointer :: ser
        call marker%mark_begin ("fibonacci_node_t")
        ser => this%left
        call marker%mark_pointer ("left", ser)
        ser => this%right
        call marker%mark_pointer ("right", ser)
        ser => this%down
        call marker%mark_pointer ("down", ser)
        call marker%mark_end ("fibonacci_node_t")
    end subroutine fibonacci_node_write_to_marker

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: read_from_marker => fibonacci_node_read_from_marker

<Muli fibonacci: procedures>+≡
    recursive subroutine fibonacci_node_read_from_marker (this, marker, status)
        class(fibonacci_node_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker

```

```

integer(dik), intent(out) :: status
call msg_warning ("fibonacci_node_read_from_marker: You cannot " // &
  "deserialize a list with this subroutine.")
call msg_error ("Use fibonacci_node_read_target_from_marker instead.")
end subroutine fibonacci_node_read_from_marker

```

```

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: read_target_from_marker => fibonacci_node_read_target_from_marker

```

```

<Muli fibonacci: procedures>+≡
  recursive subroutine fibonacci_node_read_target_from_marker &
    (this, marker, status)
    class(fibonacci_node_t), target, intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    class(ser_class_t), pointer :: ser
    call marker%pick_begin ("fibonacci_node_t", status=status)
    call marker%pick_pointer ("left", ser)
    if (status == 0) then
      select type (ser)
        class is (fibonacci_node_t)
          this%left => ser
          this%left%up => this
        end select
      end if
    call marker%pick_pointer ("right", ser)
    if (status == 0) then
      select type (ser)
        class is (fibonacci_node_t)
          this%right => ser
          this%right%up => this
        end select
      end if
    call marker%pick_pointer ("down", ser)
    if (status == 0) then
      select type (ser)
        class is (measure_class_t)
          this%down => ser
        end select
      end if
    call marker%pick_end ("fibonacci_node_t", status)
  end subroutine fibonacci_node_read_target_from_marker

```

```

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: print_to_unit => fibonacci_node_print_to_unit

```

```

<Muli fibonacci: procedures>+≡
  recursive subroutine fibonacci_node_print_to_unit &
    (this, unit, parents, components, peers)
    class(fibonacci_node_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    class(ser_class_t), pointer :: ser
    write (unit, "(1x,A)")      "Components of fibonacci_node_t:"

```

```

write (unit, "(3x,A,I22)") "Depth: ", this%depth
write (unit, "(3x,A,E23.16)") "Value: ", this%measure ()
ser => this%up
call serialize_print_comp_pointer &
    (ser, unit, parents, -i_one, -i_one, "Up: ")
ser => this%left
call serialize_print_peer_pointer &
    (ser, unit, parents, components, peers, "Left: ")
ser => this%right
call serialize_print_peer_pointer &
    (ser, unit, parents, components, peers, "Right: ")
end subroutine fibonacci_node_print_to_unit

```

```

<Muli fibonacci: fibonacci node: TBP>+≡
procedure, nopass :: get_type => fibonacci_node_get_type

```

```

<Muli fibonacci: procedures>+≡
pure subroutine fibonacci_node_get_type (type)
character(:), allocatable, intent(out) :: type
allocate (type, source="fibonacci_node_t")
end subroutine fibonacci_node_get_type

```

```

<Muli fibonacci: fibonacci node: TBP>+≡
procedure :: deserialize_from_marker => fibonacci_node_deserialize_from_marker

```

```

<Muli fibonacci: procedures>+≡
subroutine fibonacci_node_deserialize_from_marker (this, name, marker)
class(fibonacci_node_t), intent(out) :: this
character(*), intent(in) :: name
class(marker_t), intent(inout) :: marker
class(ser_class_t), pointer :: ser
allocate (fibonacci_leave_t :: ser)
call marker%push_reference (ser)
allocate (fibonacci_node_t :: ser)
call marker%push_reference (ser)
call serializable_deserialize_from_marker (this, name, marker)
call marker%pop_reference (ser)
deallocate (ser)
call marker%pop_reference (ser)
deallocate (ser)
end subroutine fibonacci_node_deserialize_from_marker

```

```

<Muli fibonacci: fibonacci node: TBP>+≡
procedure :: measure => fibonacci_node_measure

```

```

<Muli fibonacci: procedures>+≡
elemental function fibonacci_node_measure (this)
class(fibonacci_node_t), intent(in) :: this
real(default) :: fibonacci_node_measure
fibonacci_node_measure = this%down%measure ()
end function fibonacci_node_measure

```

```

<Muli fibonacci: fibonacci node: TBP>+≡
procedure :: deallocate_tree => fibonacci_node_deallocate_tree

```

```

<Muli fibonacci: procedures>+≡
recursive subroutine fibonacci_node_deallocate_tree (this)
  class(fibonacci_node_t), intent(inout) :: this
  if (associated (this%left)) then
    call this%left%deallocate_tree ()
    deallocate (this%left)
  end if
  if (associated (this%right)) then
    call this%right%deallocate_tree ()
    deallocate (this%right)
  end if
  call this%set_depth (0)
end subroutine fibonacci_node_deallocate_tree

<Muli fibonacci: fibonacci node: TBP>+≡
procedure :: deallocate_all => fibonacci_node_deallocate_all

<Muli fibonacci: procedures>+≡
recursive subroutine fibonacci_node_deallocate_all (this)
  class(fibonacci_node_t), intent(inout) :: this
  if (associated (this%left)) then
    call this%left%deallocate_all ()
    deallocate (this%left)
  end if
  if (associated (this%right)) then
    call this%right%deallocate_all ()
    deallocate (this%right)
  end if
  call this%set_depth (0)
end subroutine fibonacci_node_deallocate_all

<Muli fibonacci: fibonacci node: TBP>+≡
procedure :: get_depth => fibonacci_node_get_depth

<Muli fibonacci: procedures>+≡
elemental function fibonacci_node_get_depth (this)
  class(fibonacci_node_t), intent(in) :: this
  integer :: fibonacci_node_get_depth
  fibonacci_node_get_depth = this%depth
end function fibonacci_node_get_depth

<Muli fibonacci: fibonacci node: TBP>+≡
procedure :: count_leaves => fibonacci_node_count_leaves

<Muli fibonacci: procedures>+≡
recursive subroutine fibonacci_node_count_leaves (this, n)
  class(fibonacci_node_t), intent(in) :: this
  integer, intent(out) :: n
  integer :: n1, n2
  if (associated (this%left) .and. associated (this%right)) then
    call fibonacci_node_count_leaves (this%left, n1)
    call fibonacci_node_count_leaves (this%right, n2)
    n = n1 + n2
  else

```

```

        n = 1
    end if
end subroutine fibonacci_node_count_leaves

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure,public,nopass :: is_leave => fibonacci_node_is_leave

<Muli fibonacci: procedures>+≡
    elemental function fibonacci_node_is_leave ()
        logical :: fibonacci_node_is_leave
        fibonacci_node_is_leave = .false.
    end function fibonacci_node_is_leave

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure,public,nopass :: is_root => fibonacci_node_is_root

<Muli fibonacci: procedures>+≡
    elemental function fibonacci_node_is_root ()
        logical :: fibonacci_node_is_root
        fibonacci_node_is_root = .false.
    end function fibonacci_node_is_root

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure,public,nopass :: is_inner => fibonacci_node_is_inner

<Muli fibonacci: procedures>+≡
    elemental function fibonacci_node_is_inner ()
        logical :: fibonacci_node_is_inner
        fibonacci_node_is_inner = .true.
    end function fibonacci_node_is_inner

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: write_association => fibonacci_node_write_association

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_write_association (this, that)
        class(fibonacci_node_t), intent(in), target :: this
        class(fibonacci_node_t), intent(in), target :: that
        if (associated (that%left, this)) then
            write(*, "(A)") "This is left child of that"
        end if
        if (associated (that%right, this)) then
            write(*, "(A)") "This is right child of that"
        end if
        if (associated (that%up, this)) then
            write(*, "(A)") "This is parent of that"
        end if
        if (associated (this%left, that)) then
            write(*, "(A)") "That is left child of this"
        end if
        if (associated (this%right, that)) then
            write(*, "(A)") "That is right child of this"
        end if
        if (associated (this%up, that)) then

```

```

        write(*, "(A)") "That is parent of this"
    end if
end subroutine fibonacci_node_write_association

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: write_contents => fibonacci_node_write_contents

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_write_contents (this, unit)
        class(fibonacci_node_t), intent(in), target :: this
        integer, intent(in), optional :: unit
        call this%apply_to_leaves (fibonacci_leave_write_content, unit)
    end subroutine fibonacci_node_write_contents

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: write_values => fibonacci_node_write_values

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_write_values (this, unit)
        class(fibonacci_node_t), intent(in), target :: this
        integer, intent(in), optional :: unit
        call this%apply_to_leaves (fibonacci_leave_write_value, unit)
    end subroutine fibonacci_node_write_values

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: write_leaves => fibonacci_node_write_leaves

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_write_leaves (this, unit)
        class(fibonacci_node_t), intent(in), target :: this
        integer, intent(in), optional :: unit
        call this%apply_to_leaves (fibonacci_leave_write, unit)
    end subroutine fibonacci_node_write_leaves

<Muli fibonacci: fibonacci node: TBP>+≡
    ! procedure :: write => fibonacci_node_write_contents

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: write_pstricks => fibonacci_node_write_pstricks

<Muli fibonacci: procedures>+≡
    recursive subroutine fibonacci_node_write_pstricks (this, unitnr)
        class(fibonacci_node_t), intent(in), target :: this
        integer, intent(in) :: unitnr
        if (associated (this%up)) then
            if (associated (this%up%left, this) .neqv. &
                (associated (this%up%right, this))) then
                ! write (unitnr, '("\begin{psTree}{\Toval{$",i3,$$}")') int(this%depth)
                write (unitnr, &
                    '("\begin{psTree}{\Toval{\node{" ,i3,"}{ ,f9.3,}}}")') &
                    int(this%depth), this%measure()
            else
                write (unitnr, &
                    '("\begin{psTree}{\Toval[" ,a,"]{\node{" ,i3,"}{ ,f9.3,}}}")') &

```

```

        no_ret, int(this%depth), this%measure()
    end if
else
    write (unitnr, &
        '("\begin{psTree}{\Toval["a,"]{\node{"i3,"}{f9.3,"}}}') &
        no_par, int(this%depth), this%measure()
    end if
    if (associated (this%left)) then
        call this%left%write_pstricks (unitnr)
    else
        write (unitnr, '("\Tr[edge=brokenline]{}')')
    end if
    if (associated (this%right)) then
        call this%right%write_pstricks (unitnr)
    else
        write (unitnr, '("\Tr[edge=brokenline]{}')')
    end if
    write (unitnr, '("\end{psTree}"))')
end subroutine fibonacci_node_write_pstricks

```

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: copy_node => fibonacci_node_copy_node

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_copy_node (this, primitive)
 class(fibonacci_node_t), intent(out) :: this
 class(fibonacci_node_t), intent(in) :: primitive
 this%up => primitive%up
 this%left => primitive%left
 this%right => primitive%right
 this%depth = primitive%depth
 this%down => primitive%down
 end subroutine fibonacci_node_copy_node

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: find_root => fibonacci_node_find_root

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_find_root (this, root)
 class(fibonacci_node_t), intent(in), target :: this
 class(fibonacci_root_t), pointer, intent(out) :: root
 class(fibonacci_node_t), pointer :: node
 node => this
 do while (associated (node%up))
 node => node%up
 end do
 select type (node)
 class is (fibonacci_root_t)
 root => node
 class default
 nullify (root)
 call msg_error ("fibonacci_node_find_root: root is not type " // &
 "compatible to fibonacci_root_t. Returned NULL().")
 end select

```

end subroutine fibonacci_node_find_root

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: find_leftmost => fibonacci_node_find_leftmost
<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_find_leftmost (this, leave)
    class(fibonacci_node_t), intent(in), target :: this
    class(fibonacci_leave_t), pointer, intent(out) :: leave
    class(fibonacci_node_t), pointer :: node
    node => this
    do while (associated (node%left))
      node => node%left
    end do
    select type (node)
    class is (fibonacci_leave_t)
      leave => node
    class default
      leave => null()
    end select
  end subroutine fibonacci_node_find_leftmost

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: find_rightmost => fibonacci_node_find_rightmost
<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_find_rightmost (this, leave)
    class(fibonacci_node_t), intent(in), target :: this
    class(fibonacci_leave_t), pointer, intent(out) :: leave
    class(fibonacci_node_t), pointer :: node
    node => this
    do while (associated (node%right))
      node => node%right
    end do
    select type (node)
    class is (fibonacci_leave_t)
      leave => node
    class default
      leave => null()
    end select
  end subroutine fibonacci_node_find_rightmost

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: find => fibonacci_node_find
<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_find (this, value, leave)
    class(fibonacci_node_t), intent(in), target :: this
    real(default), intent(in) :: value
    class(fibonacci_leave_t), pointer, intent(out) :: leave
    class(fibonacci_node_t), pointer :: node
    node => this
    do
      if (node >= value) then

```



```

        if (associated (node%left)) then
            node => node%left
        else
            call msg_warning ("fibonacci_node_find: broken tree!")
            leave => null()
            return
        end if
    else
        if (associated (node%right)) then
            node => node%right
        else
            call msg_warning ("fibonacci_node_find: broken tree!")
            leave => null()
            return
        end if
    end if
    select type (node)
    class is (fibonacci_leave_t)
        leave => node
    exit
    end select
end do
end subroutine fibonacci_node_find

```

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: find_left_leave => fibonacci_node_find_left_leave

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_find_left_leave (this, leave)
 class(fibonacci_node_t), intent(in), target :: this
 class(fibonacci_node_t), pointer :: node
 class(fibonacci_leave_t), pointer, intent(out) :: leave
 nullify(leave)
 node => this
 do while (associated (node%up))
 if (associated (node%up%right, node)) then
 node => node%up%left
 do while (associated (node%right))
 node => node%right
 end do
 select type (node)
 class is (fibonacci_leave_t)
 leave => node
 end select
 exit
 end if
 node => node%up
 end do
end subroutine fibonacci_node_find_left_leave

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: find_right_leave => fibonacci_node_find_right_leave

```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_find_right_leave (this, leave)
    class(fibonacci_node_t), intent(in), target :: this
    class(fibonacci_node_t), pointer :: node
    class(fibonacci_leave_t), pointer, intent(out) :: leave
    nullify (leave)
    node => this
    do while (associated (node%up))
      if (associated (node%up%left, node)) then
        node => node%up%right
        do while (associated (node%left))
          node => node%left
        end do
        select type (node)
        class is (fibonacci_leave_t)
          leave => node
        end select
        exit
      end if
      node => node%up
    end do
  end subroutine fibonacci_node_find_right_leave

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: apply_to_leaves => fibonacci_node_apply_to_leaves

<Muli fibonacci: procedures>+≡
  recursive subroutine fibonacci_node_apply_to_leaves (node, func, unit)
    class(fibonacci_node_t), intent(in), target :: node
    interface
      subroutine func (this, unit)
        import fibonacci_leave_t
        class(fibonacci_leave_t), intent(in), target :: this
        integer, intent(in), optional :: unit
      end subroutine func
    end interface
    integer, intent(in), optional :: unit
    select type (node)
    class is (fibonacci_leave_t)
      call func (node, unit)
    class default
      call node%left%apply_to_leaves (func, unit)
      call node%right%apply_to_leaves (func, unit)
    end select
  end subroutine fibonacci_node_apply_to_leaves

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: apply_to_leaves_rl => fibonacci_node_apply_to_leaves_rl

<Muli fibonacci: procedures>+≡
  recursive subroutine fibonacci_node_apply_to_leaves_rl (node, func, unit)
    class(fibonacci_node_t), intent(in), target :: node
    interface
      subroutine func (this, unit)

```

```

import fibonacci_leave_t
class(fibonacci_leave_t), intent(in), target :: this
integer, intent(in), optional :: unit
end subroutine func
end interface
integer, intent(in), optional :: unit
select type (node)
class is (fibonacci_leave_t)
call func (node, unit)
class default
call node%right%apply_to_leaves_rl (func, unit)
call node%left%apply_to_leaves_rl (func, unit)
end select
end subroutine fibonacci_node_apply_to_leaves_rl

```

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: set_depth => fibonacci_node_set_depth

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_set_depth (this, depth)
 class(fibonacci_node_t), intent(inout) :: this
 integer, intent(in) :: depth
 this%depth = depth
end subroutine fibonacci_node_set_depth

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: append_left => fibonacci_node_append_left

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_append_left(this,new_branch)
 class(fibonacci_node_t),target :: this
 class(fibonacci_node_t),target :: new_branch
 this%left => new_branch
 new_branch%up => this
end subroutine fibonacci_node_append_left

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: append_right => fibonacci_node_append_right

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_append_right (this, new_branch)
 class(fibonacci_node_t), intent(inout), target :: this
 class(fibonacci_node_t), target :: new_branch
 this%right => new_branch
 new_branch%up => this
end subroutine fibonacci_node_append_right

<Muli fibonacci: fibonacci node: TBP>+≡
 procedure :: replace => fibonacci_node_replace

<Muli fibonacci: procedures>+≡
 subroutine fibonacci_node_replace (this, old_node)
 class(fibonacci_node_t), intent(inout), target :: this
 class(fibonacci_node_t), target :: old_node

```

if (associated (old_node%up)) then
  if (old_node%is_left_child ()) then
    old_node%up%left => this
  else
    if (old_node%is_right_child ()) then
      old_node%up%right => this
    end if
  end if
  this%up => old_node%up
else
  nullify (this%up)
end if
end subroutine fibonacci_node_replace

```

<Multi fibonacci: fibonacci node: TBP>+≡
 procedure :: swap => fibonacci_node_swap_nodes

<Multi fibonacci: procedures>+≡
 subroutine fibonacci_node_swap_nodes (left, right)
 class(fibonacci_node_t), target, intent(inout) :: left, right
 class(fibonacci_node_t), pointer :: left_left, right_right
 class(measure_class_t), pointer::down
 ! swap branches
 left_left => left%left
 right_right => right%right
 left%left => right%right
 right%right => left_left
 ! repair up components
 right_right%up => left
 left_left%up => right
 ! repair down components
 down => left%down
 left%down => right%down
 right%down => down
 end subroutine fibonacci_node_swap_nodes

```

! subroutine fibonacci_node_swap_nodes (this, that)
!   class(fibonacci_node_t),target :: this
!   class(fibonacci_node_t), pointer, intent(in) :: that
!   class(fibonacci_node_t), pointer :: par_i, par_a
!   par_i => this%up
!   par_a => that%up
!   if (associated (par_i%left, this)) then
!     par_i%left => that
!   else
!     par_i%right => that
!   end if
!   if (associated (par_a%left, that)) then
!     par_a%left => this
!   else
!     par_a%right => this
!   end if
!   this%up => par_a
!   that%up => par_i

```

```

! end subroutine fibonacci_node_swap_nodes

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: flip => fibonacci_node_flip_children
<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_flip_children (this)
    class(fibonacci_node_t), intent(inout) :: this
    class(fibonacci_node_t), pointer :: child
    child => this%left
    this%left => this%right
    this%right => child
  end subroutine fibonacci_node_flip_children

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: rip => fibonacci_node_rip
<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_rip (this)
    class(fibonacci_node_t), intent(inout), target :: this
    if (this%is_left_child ()) then
      nullify (this%up%left)
    end if
    if (this%is_right_child ()) then
      nullify (this%up%right)
    end if
    nullify (this%up)
  end subroutine fibonacci_node_rip

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: remove_and_keep_parent => fibonacci_node_remove_and_keep_parent
<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_remove_and_keep_parent (this, pa)
    class(fibonacci_node_t), intent(inout), target :: this
    class(fibonacci_node_t), intent(out), pointer :: pa
    class(fibonacci_node_t), pointer :: twin
    if (.not. (this%is_root ())) then
      pa => this%up
      if (this%is_left_child ()) then
        twin => pa%right
      else
        twin => pa%left
      end if
      twin%up => pa%up
      if (associated (twin%left)) then
        twin%left%up => pa
      end if
      if (associated (twin%right)) then
        twin%right%up => pa
      end if
      call pa%copy_node (twin)
      select type (pa)
        class is (fibonacci_root_t)

```

```

        call pa%set_leftmost ()
        call pa%set_rightmost ()
    end select
    if (associated (this%right)) then
        this%right%left => this%left
    end if
    if (associated (this%left)) then
        this%left%right => this%right
    end if
    nullify (this%left)
    nullify (this%right)
    nullify (this%up)
    deallocate (twin)
else
    pa => this
end if
end subroutine fibonacci_node_remove_and_keep_parent

```

(Multi fibonacci: fibonacci node: TBP)+≡
 procedure :: remove_and_keep_twin => fibonacci_node_remove_and_keep_twin

(Multi fibonacci: procedures)+≡
 subroutine fibonacci_node_remove_and_keep_twin (this, twin)
 class(fibonacci_node_t), intent(inout), target :: this
 class(fibonacci_node_t), intent(out), pointer :: twin
 class(fibonacci_node_t), pointer :: pa
 if (.not. (this%is_root ())) then
 pa => this%up
 if (.not. pa%is_root ()) then
 if (this%is_left_child ()) then
 twin => pa%right
 else
 twin => pa%left
 end if
 if (pa%is_left_child ()) then
 pa%up%left => twin
 else
 pa%up%right => twin
 end if
 end if
 twin%up => pa%up
 if (associated (this%right)) then
 this%right%left => this%left
 end if
 if (associated (this%left)) then
 this%left%right => this%right
 end if
 nullify (this%left)
 nullify (this%right)
 nullify (this%up)
 deallocate (pa)
 end if
end subroutine fibonacci_node_remove_and_keep_twin

```

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: rotate_left => fibonacci_node_rotate_left

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_rotate_left (this)
        class(fibonacci_node_t), intent(inout), target :: this
        call this%swap (this%right)
        call this%right%flip ()
        call this%right%update_depth_unsave ()
        call this%flip ()
        ! value = this%value
        ! this%value = this%left%value
        ! this%left%value = value
    end subroutine fibonacci_node_rotate_left

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: rotate_right => fibonacci_node_rotate_right

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_rotate_right (this)
        class(fibonacci_node_t), intent(inout), target :: this
        call this%left%swap (this)
        call this%left%flip ()
        call this%left%update_depth_unsave ()
        call this%flip ()
        ! value = this%value
        ! this%value = this%right%value
        ! this%right%value = value
    end subroutine fibonacci_node_rotate_right

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: rotate => fibonacci_node_rotate

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_rotate (this)
        class(fibonacci_node_t), intent(inout), target :: this
        if (this%is_left_short ()) then
            call this%rotate_left ()
        else
            if (this%is_right_short ()) then
                call this%rotate_right ()
            end if
        end if
    end subroutine fibonacci_node_rotate

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: balance_node => fibonacci_node_balance_node

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_node_balance_node (this, changed)
        class(fibonacci_node_t), intent(inout), target :: this
        logical, intent(out) :: changed
        changed = .false.
        if (this%is_left_too_short ()) then

```

```

        if (this%right%is_right_short ()) then
            call this%right%rotate_right
        end if
        call this%rotate_left ()
        changed = .true.
    else
        if (this%is_right_too_short ()) then
            if (this%left%is_left_short ()) then
                call this%left%rotate_left
            end if
            call this%rotate_right ()
            changed = .true.
        end if
    end if
end subroutine fibonacci_node_balance_node

```

(Muli fibonacci: fibonacci node: TBP)+≡
 procedure :: update_depth_save => fibonacci_node_update_depth_save

(Muli fibonacci: procedures)+≡
 subroutine fibonacci_node_update_depth_save (this, updated)
 class(fibonacci_node_t), intent(inout) :: this
 logical, intent(out) :: updated
 integer :: left, right, new_depth
 if (associated (this%left)) then
 left = this%left%depth + 1
 else
 left = -1
 end if
 if (associated (this%right)) then
 right = this%right%depth + 1
 else
 right = -1
 end if
 new_depth = max(left, right)
 if (this%depth == new_depth) then
 updated = .false.
 else
 this%depth = new_depth
 updated = .true.
 end if
end subroutine fibonacci_node_update_depth_save

(Muli fibonacci: fibonacci node: TBP)+≡
 procedure :: update_depth_unsave => fibonacci_node_update_depth_unsave

(Muli fibonacci: procedures)+≡
 subroutine fibonacci_node_update_depth_unsave (this)
 class(fibonacci_node_t), intent(inout) :: this
 this%depth = max (this%left%depth+1, this%right%depth+1)
end subroutine fibonacci_node_update_depth_unsave

(Muli fibonacci: fibonacci node: TBP)+≡
 procedure :: repair => fibonacci_node_repair


```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_node_repair (this)
    class(fibonacci_node_t), intent(inout), target :: this
    class(fibonacci_node_t), pointer :: node
    logical :: new_depth, new_balance
    new_depth = .true.
    node => this
    do while ((new_depth .or. new_balance) .and. (associated (node)))
      call node%balance_node (new_balance)
      call node%update_depth_save (new_depth)
      node => node%up
    end do
  end subroutine fibonacci_node_repair

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: is_left_short => fibonacci_node_is_left_short

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_node_is_left_short(this)
    class(fibonacci_node_t), intent(in) :: this
    fibonacci_node_is_left_short = (this%left%depth < this%right%depth)
  end function fibonacci_node_is_left_short

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: is_right_short => fibonacci_node_is_right_short

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_node_is_right_short (this)
    class(fibonacci_node_t), intent(in) :: this
    fibonacci_node_is_right_short = (this%right%depth < this%left%depth)
  end function fibonacci_node_is_right_short

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: is_unbalanced => fibonacci_node_is_unbalanced

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_node_is_unbalanced (this)
    class(fibonacci_node_t), intent(in) :: this
    fibonacci_node_is_unbalanced = &
      (this%is_left_short () .or. this%is_right_short ())
  end function fibonacci_node_is_unbalanced

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: is_left_too_short => fibonacci_node_is_left_too_short

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_node_is_left_too_short (this)
    class(fibonacci_node_t), intent(in) :: this
    fibonacci_node_is_left_too_short = (this%left%depth+1 < this%right%depth)
  end function fibonacci_node_is_left_too_short

<Muli fibonacci: fibonacci node: TBP>+≡
  procedure :: is_right_too_short => fibonacci_node_is_right_too_short

```

```

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_node_is_right_too_short (this)
        class(fibonacci_node_t), intent(in) :: this
        fibonacci_node_is_right_too_short = (this%right%depth+1 < this%left%depth)
    end function fibonacci_node_is_right_too_short

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: is_too_unbalanced => fibonacci_node_is_too_unbalanced

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_node_is_too_unbalanced (this)
        class(fibonacci_node_t), intent(in) :: this
        fibonacci_node_is_too_unbalanced = &
            (this%is_left_too_short() .or. this%is_right_too_short())
    end function fibonacci_node_is_too_unbalanced

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: is_left_child => fibonacci_node_is_left_child

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_node_is_left_child (this)
        class(fibonacci_node_t), intent(in), target :: this
        fibonacci_node_is_left_child = associated (this%up%left, this)
    end function fibonacci_node_is_left_child

<Muli fibonacci: fibonacci node: TBP>+≡
    procedure :: is_right_child => fibonacci_node_is_right_child

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_node_is_right_child (this)
        class(fibonacci_node_t), intent(in), target :: this
        fibonacci_node_is_right_child = associated (this%up%right, this)
    end function fibonacci_node_is_right_child

<Muli fibonacci: fibonacci node: TBP>+≡
    ! user
    ! node
    ! tree
    ! procedure :: balance
    ! procedure :: sort
    ! procedure :: merge
    ! procedure :: split

<Muli fibonacci: public>+≡
    public :: fibonacci_leave_t

<Muli fibonacci: types>+≡
    type, extends (fibonacci_node_t) :: fibonacci_leave_t
        ! class(measure_class_t), pointer :: content
    contains
    <Muli fibonacci: fibonacci leave: TBP>
    end type fibonacci_leave_t

```

```

<Muli fibonacci: fibonacci leave: TBP>≡
! procedure :: write_to_marker => fibonacci_leave_write_to_marker
! procedure :: read_from_marker => fibonacci_leave_read_from_marker
procedure :: print_to_unit => fibonacci_leave_print_to_unit

<Muli fibonacci: procedures>+≡
subroutine fibonacci_leave_print_to_unit &
    (this, unit, parents, components, peers)
    class(fibonacci_leave_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    class(ser_class_t), pointer :: ser
    if (parents > 0) call fibonacci_node_print_to_unit &
        (this, unit, parents-i_one, components, -i_one)
    write(unit, "(A)") "Components of fibonacci_leave_t:"
    ser => this%down
    call serialize_print_comp_pointer &
        (ser, unit, parents, components, peers, "Content:")
end subroutine fibonacci_leave_print_to_unit

<Muli fibonacci: fibonacci leave: TBP>+≡
procedure, nopass :: get_type => fibonacci_leave_get_type

<Muli fibonacci: procedures>+≡
pure subroutine fibonacci_leave_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="fibonacci_leave_t")
end subroutine fibonacci_leave_get_type

<Muli fibonacci: fibonacci leave: TBP>+≡
procedure :: deallocate_all => fibonacci_leave_deallocate_all

<Muli fibonacci: procedures>+≡
subroutine fibonacci_leave_deallocate_all (this)
    class(fibonacci_leave_t), intent(inout) :: this
    if (associated (this%down)) then
        deallocate (this%down)
    end if
end subroutine fibonacci_leave_deallocate_all

<Muli fibonacci: fibonacci leave: TBP>+≡
procedure :: pick => fibonacci_leave_pick

<Muli fibonacci: procedures>+≡
subroutine fibonacci_leave_pick (this)
    class(fibonacci_leave_t), target, intent(inout) :: this
    class(fibonacci_node_t), pointer :: other
    class(fibonacci_root_t), pointer :: root
    ! call this%up%print_parents()
    call this%find_root (root)
    if (associated (this%up, root)) then
        if (this%up%depth < 2) then
            call msg_error ("fibonacci_leave_pick: Cannot pick leave. " // &
                "Tree must have at least three leaves.")
        end if
    end if
end subroutine fibonacci_leave_pick

```

```

        else
            call this%remove_and_keep_parent (other)
            call other%repair ()
        end if
    else
        call this%remove_and_keep_twin (other)
        call other%up%repair ()
    end if
    if (associated (root%leftmost, this)) call root%set_leftmost ()
    if (associated (root%rightmost, this)) call root%set_rightmost ()
end subroutine fibonacci_leave_pick

```

<Muli fibonacci: fibonacci leave: TBP>+≡

```

procedure :: get_left => fibonacci_leave_get_left

```

<Muli fibonacci: procedures>+≡

```

subroutine fibonacci_leave_get_left (this, leave)
    class(fibonacci_leave_t), intent(in) :: this
    class(fibonacci_leave_t), intent(out), pointer :: leave
    class(fibonacci_node_t), pointer :: node
    node => this%left
    select type (node)
    class is (fibonacci_leave_t)
        leave => node
    end select
end subroutine fibonacci_leave_get_left

```

<Muli fibonacci: fibonacci leave: TBP>+≡

```

procedure :: get_right => fibonacci_leave_get_right

```

<Muli fibonacci: procedures>+≡

```

subroutine fibonacci_leave_get_right (this, leave)
    class(fibonacci_leave_t), intent(in) :: this
    class(fibonacci_leave_t), intent(out), pointer :: leave
    class(fibonacci_node_t), pointer :: node
    ! print *, "fibonacci_leave_get_right"
    ! call this%down%print_little
    if (associated (this%right)) then
        node => this%right
        ! call node%down%print_little
        select type (node)
        class is (fibonacci_leave_t)
            leave => node
        end select
    else
        ! print *, "no right leave"
        nullify (leave)
    end if
end subroutine fibonacci_leave_get_right

```

<Muli fibonacci: fibonacci leave: TBP>+≡

```

procedure :: write_pstricks => fibonacci_leave_write_pstricks

```

```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_leave_write_pstricks (this, unitnr)
    class(fibonacci_leave_t), intent(in), target :: this
    integer, intent(in) :: unitnr
    write (unitnr, "(A,I3,A,F9.3,A)") &
      "\begin{psTree}{\Toval[linecolor=green]{\node{" , this%depth, "}{", &
      this%measure(), "}}}"
    if (associated (this%left)) then
      write (unitnr, "(A,A,A)") "\Tr[" , le_kid, "]{}"
    end if
    if (associated (this%right)) then
      write (unitnr, "(A,A,A)") "\Tr[" , le_kid, "]{}"
    end if
    write (unitnr, "(A)") "\end{psTree}"
  end subroutine fibonacci_leave_write_pstricks

```

```

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure :: copy_content => fibonacci_leave_copy_content

```

```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_leave_copy_content (this, content)
    class(fibonacci_leave_t) :: this
    class(measure_class_t), intent(in) :: content
    allocate (this%down, source=content)
  end subroutine fibonacci_leave_copy_content

```

```

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure :: set_content => fibonacci_leave_set_content

```

```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_leave_set_content (this, content)
    class(fibonacci_leave_t) :: this
    class(measure_class_t), target, intent(in) :: content
    this%down => content
  end subroutine fibonacci_leave_set_content

```

```

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure :: get_content => fibonacci_leave_get_content

```

```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_leave_get_content (this, content)
    class(fibonacci_leave_t), intent(in) :: this
    class(measure_class_t), pointer :: content
    content => this%down
  end subroutine fibonacci_leave_get_content

```

```

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure, nopass :: is_inner => fibonacci_leave_is_inner

```

```

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_leave_is_inner ()
    fibonacci_leave_is_inner = .false.
  end function fibonacci_leave_is_inner

```

```

<Muli fibonacci: fibonacci leave: TBP>+≡
    procedure, nopass :: is_leave => fibonacci_leave_is_leave

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_leave_is_leave ()
        fibonacci_leave_is_leave = .true.
    end function fibonacci_leave_is_leave

<Muli fibonacci: fibonacci leave: TBP>+≡
    procedure :: insert_leave_by_node => fibonacci_leave_insert_leave_by_node

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_leave_insert_leave_by_node (this, new_leave)
        class(fibonacci_leave_t), target, intent(inout) :: this, new_leave
        class(fibonacci_node_t), pointer :: parent, new_node
        parent => this%up
        !print *, associated (this%left), associated (this%right)
        if (this < new_leave) then
            call fibonacci_node_spawn (new_node, this, new_leave, this%left, this%right)
            ! print *, "Repair! ", this%measure(), new_leave%measure()
        else
            call fibonacci_node_spawn (new_node, new_leave, this, this%left, this%right)
        end if
        if (associated (parent%left, this)) then
            call parent%append_left (new_node)
        else
            call parent%append_right (new_node)
        end if
        call parent%repair ()
    end subroutine fibonacci_leave_insert_leave_by_node

<Muli fibonacci: fibonacci leave: TBP>+≡
    procedure :: is_left_short => fibonacci_leave_is_left_short

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_leave_is_left_short (this)
        class(fibonacci_leave_t), intent(in) :: this
        fibonacci_leave_is_left_short = .false.
    end function fibonacci_leave_is_left_short

<Muli fibonacci: fibonacci leave: TBP>+≡
    procedure :: is_right_short => fibonacci_leave_is_right_short

<Muli fibonacci: procedures>+≡
    elemental logical function fibonacci_leave_is_right_short (this)
        class(fibonacci_leave_t), intent(in) :: this
        fibonacci_leave_is_right_short = .false.
    end function fibonacci_leave_is_right_short

<Muli fibonacci: fibonacci leave: TBP>+≡
    procedure :: is_unbalanced => fibonacci_leave_is_unbalanced

```

```

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_leave_is_unbalanced (this)
    class(fibonacci_leave_t), intent(in) :: this
    fibonacci_leave_is_unbalanced = .false.
  end function fibonacci_leave_is_unbalanced

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure :: is_left_too_short => fibonacci_leave_is_left_too_short

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_leave_is_left_too_short (this)
    class(fibonacci_leave_t), intent(in) :: this
    fibonacci_leave_is_left_too_short = .false.
  end function fibonacci_leave_is_left_too_short

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure :: is_right_too_short => fibonacci_leave_is_right_too_short

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_leave_is_right_too_short (this)
    class(fibonacci_leave_t), intent(in) :: this
    fibonacci_leave_is_right_too_short = .false.
  end function fibonacci_leave_is_right_too_short

<Muli fibonacci: fibonacci leave: TBP>+≡
  procedure :: is_too_unbalanced => fibonacci_leave_is_too_unbalanced

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_leave_is_too_unbalanced (this)
    class(fibonacci_leave_t), intent(in) :: this
    fibonacci_leave_is_too_unbalanced = .false.
  end function fibonacci_leave_is_too_unbalanced

<Muli fibonacci: public>+≡
  public :: fibonacci_root_t

<Muli fibonacci: types>+≡
  type, extends (fibonacci_node_t) :: fibonacci_root_t
    logical::is_valid_c=.false.
    class(fibonacci_leave_t),pointer :: leftmost => null()
    class(fibonacci_leave_t),pointer :: rightmost => null()
  contains
    <Muli fibonacci: fibonacci root: TBP>
      procedure :: is_left_child => fibonacci_root_is_left_child
      procedure :: is_right_child => fibonacci_root_is_right_child
    end type fibonacci_root_t

<Muli fibonacci: fibonacci root: TBP>≡
  procedure :: write_to_marker => fibonacci_root_write_to_marker

```

```

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_root_write_to_marker (this, marker, status)
    class(fibonacci_root_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    ! call marker%mark_begin ("fibonacci_root_t")
    call fibonacci_node_write_to_marker (this, marker, status)
    ! marker%mark_end ("fibonacci_root_t")
  end subroutine fibonacci_root_write_to_marker

<Muli fibonacci: fibonacci root: TBP>+≡
  procedure :: read_target_from_marker => fibonacci_root_read_target_from_marker

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_root_read_target_from_marker (this, marker, status)
    class(fibonacci_root_t), target, intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    ! call marker%pick_begin ("fibonacci_root_t", status)
    call fibonacci_node_read_from_marker (this, marker, status)
    call this%find_leftmost (this%leftmost)
    call this%find_rightmost (this%rightmost)
    ! call marker%pick_end ("fibonacci_root_t", status)
  end subroutine fibonacci_root_read_target_from_marker

<Muli fibonacci: fibonacci root: TBP>+≡
  procedure :: print_to_unit => fibonacci_root_print_to_unit

<Muli fibonacci: procedures>+≡
  subroutine fibonacci_root_print_to_unit (this, unit, parents, components, peers)
    class(fibonacci_root_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    class(ser_class_t), pointer :: ser
    if (parents > 0) call fibonacci_node_print_to_unit &
      (this, unit, parents-1, components, peers)
    write (unit, "(A)") "Components of fibonacci_root_t:"
    ser => this%leftmost
    call serialize_print_peer_pointer &
      (ser, unit, parents, components, min(peers, i_one), "Leftmost: ")
    ser => this%rightmost
    call serialize_print_peer_pointer &
      (ser, unit, parents, components, min(peers, i_one), "Rightmost:")
  end subroutine fibonacci_root_print_to_unit

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_root_is_left_child (this)
    class(fibonacci_root_t), target, intent(in) :: this
    fibonacci_root_is_left_child = .false.
  end function fibonacci_root_is_left_child

<Muli fibonacci: procedures>+≡
  elemental logical function fibonacci_root_is_right_child (this)

```



```

        class(fibonacci_root_t),target, intent(in) :: this
        fibonacci_root_is_right_child = .false.
    end function fibonacci_root_is_right_child

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure, nopass :: get_type => fibonacci_root_get_type

<Muli fibonacci: procedures>+≡
    pure subroutine fibonacci_root_get_type (type)
        character(:),allocatable, intent(out) :: type
        allocate (type, source="fibonacci_root_t")
    end subroutine fibonacci_root_get_type

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: get_leftmost=>fibonacci_root_get_leftmost

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_get_leftmost (this, leftmost)
        class(fibonacci_root_t), intent(in) :: this
        class(fibonacci_leave_t), pointer :: leftmost
        leftmost => this%leftmost
    end subroutine fibonacci_root_get_leftmost

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: get_rightmost=>fibonacci_root_get_rightmost

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_get_rightmost (this, rightmost)
        class(fibonacci_root_t), intent(in) :: this
        class(fibonacci_leave_t),pointer :: rightmost
        rightmost => this%rightmost
    end subroutine fibonacci_root_get_rightmost

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure, nopass :: is_root => fibonacci_root_is_root

<Muli fibonacci: procedures>+≡
    elemental function fibonacci_root_is_root ()
        logical::fibonacci_root_is_root
        fibonacci_root_is_root = .true.
    end function fibonacci_root_is_root

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure, nopass :: is_inner => fibonacci_root_is_inner

<Muli fibonacci: procedures>+≡
    elemental function fibonacci_root_is_inner ()
        logical::fibonacci_root_is_inner
        fibonacci_root_is_inner = .false.
    end function fibonacci_root_is_inner

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: is_valid => fibonacci_root_is_valid

```

```

<Muli fibonacci: procedures>+≡
    elemental function fibonacci_root_is_valid (this)
        class(fibonacci_root_t), intent(in) :: this
        logical :: fibonacci_root_is_valid
        fibonacci_root_is_valid = this%is_valid_c
    end function fibonacci_root_is_valid

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: count_leaves => fibonacci_root_count_leaves

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_count_leaves (this, n)
        class(fibonacci_root_t), intent(in) :: this
        integer, intent(out) :: n
        n = 0
        call fibonacci_node_count_leaves (this, n)
    end subroutine fibonacci_root_count_leaves

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: write_pstricks => fibonacci_root_write_pstricks

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_write_pstricks (this, unitnr)
        class(fibonacci_root_t), intent(in), target :: this
        integer, intent(in) :: unitnr
        logical :: is_opened
        character :: is_sequential, is_formatted, is_writeable
        print *, "pstricks"
        inquire (unitnr, opened=is_opened, sequential=is_sequential, &
            formatted=is_formatted, write=is_writeable)
        if (is_opened) then
            if (is_sequential == "Y" .and. is_formatted == "Y" &
                .and. is_writeable == "Y") then
                ! write (unitnr, "(A,I3,A)") &
                !     "\begin{psTree}{\Toval[linecolor=blue]{$", int(this%depth), "$}"
                write (unitnr, "(A,I3,A,F9.3,A)") &
                !     "\begin{psTree}{\Toval[linecolor=blue]{\node{" , this%depth, &
                !     "}{", this%measure(), "}}}"
                if (associated (this%leftmost)) then
                    call this%leftmost%write_pstricks (unitnr)
                else
                    write (unitnr, "(A,A,A)") "\Tr[" , no_kid, "]"
                end if
                if (associated (this%left)) then
                    call this%left%write_pstricks (unitnr)
                else
                    write (unitnr, "(A,A,A)") "\Tr[" , no_kid, "]"
                end if
                if (associated (this%right)) then
                    call this%right%write_pstricks (unitnr)
                else
                    write (unitnr, "(A,A,A)") "\Tr[" , no_kid, "]"
                end if
                if (associated (this%rightmost)) then

```

```

        call this%rightmost%write_pstricks (unitnr)
    else
        write(unitnr,'("\Tr["a,"]{}")') no_kid
    end if
    write (unitnr, "(A)"  "\end{psTree}")
    write (unitnr, "(A)"  "\\")
else
    write (*, "(A,I2,A)" &
        "fibonacci_node_write_pstricks: Unit ", unitnr, &
        " is not opened properly.")
    write (*, "(A)"  "No output is written to unit.")
end if
else
    write (*, "(A,I2,A)" &
        "fibonacci_node_write_pstricks: Unit ", unitnr, &
        " is not opened.")
    write (*, "(A)"  "No output is written to unit.")
end if
end subroutine fibonacci_root_write_pstricks

```

<Muli fibonacci: fibonacci root: TBP>+≡

```

    procedure :: copy_root => fibonacci_root_copy_root

```

<Muli fibonacci: procedures>+≡

```

    subroutine fibonacci_root_copy_root (this, primitive)
        class(fibonacci_root_t), intent(out) :: this
        class(fibonacci_root_t), intent(in)  :: primitive
        call fibonacci_node_copy_node (this, primitive)
        this%leftmost => primitive%leftmost
        this%rightmost => primitive%rightmost
    end subroutine fibonacci_root_copy_root

```

<Muli fibonacci: fibonacci root: TBP>+≡

```

    procedure :: push_by_content => fibonacci_root_push_by_content

```

<Muli fibonacci: procedures>+≡

```

    subroutine fibonacci_root_push_by_content (this, content)
        class(fibonacci_root_t), target, intent(inout) :: this
        class(measure_class_t), target, intent(in)  :: content
        class(fibonacci_leave_t), pointer :: node
        ! print *, "fibonacci_root_push_by_content: ", content%measure()
        allocate (node)
        node%down => content
        call this%push_by_leave (node)
    end subroutine fibonacci_root_push_by_content

```

This is a workaround for gfortran bug 44696. This subroutine is a merge of `fibonacci_tree_push_by_node`, `fibonacci_node_find`, and `fibonacci_leave_insert_leave_by_node`.

<Muli fibonacci: fibonacci root: TBP>+≡

```

    procedure :: push_by_leave => fibonacci_root_push_by_leave

```

<Muli fibonacci: procedures>+≡

```

    subroutine fibonacci_root_push_by_leave (this, new_leave)
        class(fibonacci_root_t), target, intent(inout) :: this

```

```

class(fibonacci_leave_t), pointer, intent(inout) :: new_leave
class(fibonacci_leave_t), pointer :: old_leave
class(fibonacci_node_t), pointer :: node, new_node, leave_c
! write (11, fmt=*) "push by leave(", new_leave%measure(), ")\\" !PSTRICKS
! flush(11) !PSTRICKS
if (new_leave <= this%leftmost) then
    old_leave => this%leftmost
    this%leftmost => new_leave
    node => old_leave%up
    call fibonacci_node_spawn &
        (new_node, new_leave, old_leave, old_leave%left, old_leave%right)
    call node%append_left (new_node)
else
    if (new_leave > this%rightmost) then
        old_leave => this%rightmost
        this%rightmost => new_leave
        node => old_leave%up
        call fibonacci_node_spawn &
            (new_node, old_leave, new_leave, old_leave%left, old_leave%right)
        call node%append_right (new_node)
    else
        node => this
        do
            if (new_leave <= node) then
                leave_c => node%left
                select type (leave_c)
                class is (fibonacci_leave_t)
                    if (new_leave <= leave_c) then
                        ! print *, "left left"
                        call fibonacci_node_spawn (new_node, new_leave, &
                            leave_c, leave_c%left, leave_c%right)
                    else
                        ! print *, "left right"
                        call fibonacci_node_spawn (new_node, leave_c, &
                            new_leave, leave_c%left, leave_c%right)
                    end if
                call node%append_left (new_node)
                exit
            class default
                ! print *, "left"
                node => node%left
            end select
        else
            leave_c => node%right
            select type (leave_c)
            class is (fibonacci_leave_t)
                if (new_leave <= leave_c) then
                    ! print *, "right left"
                    call fibonacci_node_spawn (new_node, new_leave, &
                        leave_c, leave_c%left, leave_c%right)
                else
                    ! print *, "right right"
                    call fibonacci_node_spawn (new_node, leave_c, &
                        new_leave, leave_c%left, leave_c%right)
                end if
            end select
        end do
    end if
end if

```

```

        end if
        call node%append_right (new_node)
        exit
    class default
        ! print *, "right"
        node => node%right
    end select
end if
end do
end if
end if
! call this%write_pstricks(11) ! PSTRICKS
! flush(11) ! PSTRICKS
! write(11,fmt=*)"repair\\" ! PSTRICKS
call node%repair ()
! call this%write_pstricks (11) !PSTRICKS
! flush(11) !PSTRICKS
! call node%update_value (right_value)
! call this%write_pstricks (11)
! print *, new_node%value, new_node%left%value, new_node%right%value
end subroutine fibonacci_root_push_by_leave

```

<Muli fibonacci: fibonacci root: TBP>+≡

```

    procedure :: pop_left => fibonacci_root_pop_left

```

<Muli fibonacci: procedures>+≡

```

subroutine fibonacci_root_pop_left (this, leave)
    class(fibonacci_root_t), intent(inout), target :: this
    class(fibonacci_leave_t), pointer, intent(out) :: leave
    class(fibonacci_node_t), pointer :: parent, grand
    ! write (11,fmt=*) "fibonacci root pop left\\" ! PSTRICKS
    ! flush (11) ! PSTRICKS
    leave => this%leftmost
    if (this%left%depth >= 1) then
        parent => leave%up
        grand => parent%up
        grand%left => parent%right
        parent%right%up => grand
        deallocate (parent)
        parent => grand%left
        if (.not. parent%is_leave ()) then
            parent => parent%left
        end if
        select type (parent)
        class is (fibonacci_leave_t)
            this%leftmost => parent
        class default
            call parent%print_all()
            call msg_fatal ("fibonacci_root_pop_left: ERROR: leftmost is no leave.")
        end select
    ! call this%write_pstricks (11) ! PSTRICKS
    ! flush (11) ! PSTRICKS
    ! write (11,fmt=*) "fibonacci node repair\\" ! PSTRICKS
    ! flush (11) ! PSTRICKS

```

```

        call grand%repair ()
    else
        if (this%left%depth == 0 .and. this%right%depth == 1) then
            parent => this%right
            parent%right%up => this
            parent%left%up => this
            this%left => parent%left
            this%right => parent%right
            this%depth = 1
            deallocate (parent)
            parent => this%left
            select type (parent)
            class is (fibonacci_leave_t)
            this%leftmost => parent
            end select
            this%down => this%leftmost%down
        end if
    end if
    nullify (leave%right%left)
    nullify (leave%up)
    nullify (leave%right)
    nullify (this%leftmost%left)
    ! call this%write_pstricks (11)    ! PSTricks
    ! flush (11)    ! PSTricks
end subroutine fibonacci_root_pop_left

```

<Muli fibonacci: fibonacci root: TBP>+≡

```

    procedure :: pop_right => fibonacci_root_pop_right

```

<Muli fibonacci: procedures>+≡

```

subroutine fibonacci_root_pop_right (this, leave)
    class(fibonacci_root_t), intent(inout), target :: this
    class(fibonacci_leave_t), pointer, intent(out) :: leave
    class(fibonacci_node_t), pointer :: parent, grand
    leave => this%rightmost
    if (this%right%depth >= 1) then
        parent => leave%up
        grand => parent%up
        grand%right => parent%left
        parent%left%up => grand
        deallocate (parent)
        parent => grand%right
        if (.not. parent%is_leave ()) then
            parent => parent%right
        end if
        select type (parent)
        class is (fibonacci_leave_t)
            this%rightmost => parent
        class default
            call parent%print_all()
            call msg_fatal ("fibonacci_root_pop_left: ERROR: leftmost is no leave.")
        end select
        call grand%repair ()
    else

```

```

    if (this%right%depth == 0 .and. this%left%depth == 1) then
      parent => this%left
      parent%left%up => this
      parent%right%up => this
      this%right => parent%right
      this%left => parent%left
      this%depth = 1
      deallocate (parent)
      parent => this%right
      select type (parent)
      class is (fibonacci_leave_t)
      this%rightmost => parent
      end select
      this%down => this%rightmost%down
    end if
  end if
end subroutine fibonacci_root_pop_right

```

<Muli fibonacci: fibonacci root: TBP>+≡

```

  procedure :: list_to_tree => fibonacci_root_list_to_tree

```

<Muli fibonacci: procedures>+≡

```

  subroutine fibonacci_root_list_to_tree (this, n_leaves, leave_list_target)
    class(fibonacci_root_t), target, intent(inout) :: this
    integer, intent(in) :: n_leaves
    type(fibonacci_leave_list_t), target, intent(in) :: leave_list_target
    ! class(fibonacci_root_t), pointer, intent(out) :: tree
    integer :: depth, n_deep, n_merge
    class(fibonacci_node_t), pointer :: node
    class(fibonacci_leave_list_t), pointer :: leave_list
    class(fibonacci_leave_t), pointer :: content
    real(default) :: up_value
    leave_list => leave_list_target
    call ilog2 (n_leaves, depth, n_deep)
    n_deep = n_deep * 2
    n_merge = 0
    this%depth = depth
    node => this
    OUTER: do
      do while (depth > 1)
        depth = depth - 1
        allocate (node%left)
        node%left%up => node
        node => node%left
        node%depth = depth
      end do
      node%left => leave_list%leave
      node%down => leave_list%leave%down
      leave_list => leave_list%next
      node%right => leave_list%leave
      content => leave_list%leave
      leave_list => leave_list%next
      n_merge = n_merge + 2
    INNER: do

```

```

        if (associated (node%up)) then
            if (node%is_left_child ()) then
                if (n_merge == n_deep .and. depth == 1) then
                    node => node%up
                    node%right => leave_list%leave
                    node%right%up => node
                    node%down => content%down
                    content => leave_list%leave
                    leave_list => leave_list%next
                    n_merge = n_merge + 1
                    cycle
                end if
                exit INNER
            else
                node => node%up
                depth = depth + 1
            end if
        else
            exit OUTER
        end if
    end do INNER
    node => node%up
    node%down => content%down
    allocate (node%right)
    node%right%up => node
    node => node%right
    if (n_deep == n_merge) then
        depth = depth - 1
    end if
    node%depth = depth
end do OUTER
call this%set_leftmost
call this%set_rightmost
end subroutine fibonacci_root_list_to_tree

```

This subroutine has neither been used nor revised for a long time, so it might be broken.

(Multi fibonacci: fibonacci root: TBP)+≡

```

    procedure :: merge => fibonacci_root_merge

```

(Multi fibonacci: procedures)+≡

```

    subroutine fibonacci_root_merge(this_tree,that_tree,merge_tree)
        class(fibonacci_root_t), intent(in) :: this_tree
        class(fibonacci_root_t), intent(in) :: that_tree
        class(fibonacci_root_t), pointer, intent(out) :: merge_tree
        class(fibonacci_leave_t), pointer :: this_leave, that_leave, old_leave
        type(fibonacci_leave_list_t), target :: leave_list
        class(fibonacci_leave_list_t), pointer :: last_leave
        integer :: n_leaves
        if (associated (this_tree%leftmost) .and. associated (that_tree%leftmost)) then
            n_leaves = 1
            this_leave => this_tree%leftmost
            that_leave => that_tree%leftmost
            if (this_leave < that_leave) then

```



```

        allocate (leave_list%leave, source=this_leave)
        call this_leave%find_right_leave (this_leave)
    else
        allocate (leave_list%leave, source=that_leave)
        call that_leave%find_right_leave (that_leave)
    end if
    last_leave => leave_list
    do while (associated (this_leave) .and. associated (that_leave))
        if (this_leave < that_leave) then
            old_leave => this_leave
            call this_leave%find_right_leave (this_leave)
        else
            old_leave=>that_leave
            call that_leave%find_right_leave (that_leave)
        end if
        allocate (last_leave%next)
        last_leave => last_leave%next
        allocate (last_leave%leave, source=old_leave)
        n_leaves = n_leaves + 1
    end do
    if (associated (this_leave)) then
        old_leave => this_leave
    else
        old_leave => that_leave
    end if
    do while (associated (old_leave))
        allocate (last_leave%next)
        last_leave => last_leave%next
        allocate (last_leave%leave, source=old_leave)
        n_leaves = n_leaves + 1
        call old_leave%find_right_leave (old_leave)
    end do
    allocate (merge_tree)
    call merge_tree%list_to_tree (n_leaves, leave_list)
else
    n_leaves = 0
end if
if (associated (leave_list%next)) then
    last_leave => leave_list%next
    do while (associated (last_leave%next))
        leave_list%next => last_leave%next
        deallocate (last_leave)
        last_leave => leave_list%next
    end do
    deallocate (last_leave)
end if
end subroutine fibonacci_root_merge

```

```

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: set_leftmost => fibonacci_root_set_leftmost

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_set_leftmost (this)
        class(fibonacci_root_t) :: this
    end subroutine

```

```

        call this%find_leftmost (this%leftmost)
    end subroutine fibonacci_root_set_leftmost

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: set_rightmost => fibonacci_root_set_rightmost

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_set_rightmost (this)
        class(fibonacci_root_t) :: this
        call this%find_rightmost (this%rightmost)
    end subroutine fibonacci_root_set_rightmost

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: init_by_leave => fibonacci_root_init_by_leave

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_init_by_leave (this, left_leave, right_leave)
        class(fibonacci_root_t), target, intent(out) :: this
        class(fibonacci_leave_t), target, intent(in) :: left_leave, right_leave
        if (left_leave <= right_leave) then
            this%left => left_leave
            this%right => right_leave
            this%leftmost => left_leave
            this%rightmost => right_leave
        else
            this%left => right_leave
            this%right => left_leave
            this%leftmost => right_leave
            this%rightmost => left_leave
        end if
        this%left%up => this
        this%right%up => this
        this%down => this%leftmost%down
        this%depth = 1
        this%leftmost%right => this%rightmost
        this%rightmost%left => this%leftmost
        this%is_valid_c = .true.
    end subroutine fibonacci_root_init_by_leave

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: init_by_content => fibonacci_root_init_by_content

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_init_by_content (this, left_content, right_content)
        class(fibonacci_root_t), target, intent(out) :: this
        class(measure_class_t), intent(in), target :: left_content, right_content
        call this%reset ()
        print *, "fibonacci_root_init_by_content: ", left_content%measure (), &
            right_content%measure ()
        if (left_content < right_content) then
            call this%leftmost%set_content (left_content)
            call this%rightmost%set_content (right_content)
        else
            call this%leftmost%set_content (right_content)

```

```

        call this%rightmost%set_content (left_content)
    end if
    this%down => this%leftmost%down
    this%is_valid_c = .true.
end subroutine fibonacci_root_init_by_content

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: reset => fibonacci_root_reset

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_root_reset (this)
        class(fibonacci_root_t), target, intent(inout) :: this
        call this%deallocate_tree ()
        allocate (this%leftmost)
        allocate (this%rightmost)
        this%depth = 1
        this%leftmost%depth = 0
        this%rightmost%depth = 0
        this%left => this%leftmost
        this%right => this%rightmost
        this%left%up => this
        this%right%up => this
        this%leftmost%right => this%rightmost
        this%rightmost%left => this%leftmost
    end subroutine fibonacci_root_reset

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: deallocate_tree => fibonacci_root_deallocate_tree

<Muli fibonacci: procedures>+≡
    recursive subroutine fibonacci_root_deallocate_tree (this)
        class(fibonacci_root_t), intent(inout) :: this
        call this%deallocate_tree ()
        nullify (this%leftmost)
        nullify (this%rightmost)
    end subroutine fibonacci_root_deallocate_tree

<Muli fibonacci: fibonacci root: TBP>+≡
    procedure :: deallocate_all => fibonacci_root_deallocate_all

<Muli fibonacci: procedures>+≡
    recursive subroutine fibonacci_root_deallocate_all (this)
        class(fibonacci_root_t), intent(inout) :: this
        call this%deallocate_all ()
        nullify (this%leftmost)
        nullify (this%rightmost)
    end subroutine fibonacci_root_deallocate_all

<Muli fibonacci: types>+≡
    ! class(serializable_ref_type), pointer :: ref_list

```

```

<Muli fibonacci: types>+≡
    type, extends (fibonacci_root_t) :: fibonacci_stub_t
    contains
        <Muli fibonacci: fibonacci_stub: TBP>
    end type fibonacci_stub_t

<Muli fibonacci: fibonacci_stub: TBP>≡
    procedure :: write_to_marker => fibonacci_stub_write_to_marker

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_stub_write_to_marker (this, marker, status)
        class(fibonacci_stub_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
    end subroutine fibonacci_stub_write_to_marker

<Muli fibonacci: fibonacci_stub: TBP>+≡
    procedure :: read_target_from_marker => fibonacci_stub_read_target_from_marker

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_stub_read_target_from_marker (this, marker, status)
        class(fibonacci_stub_t), target, intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
    end subroutine fibonacci_stub_read_target_from_marker

<Muli fibonacci: fibonacci_stub: TBP>+≡
    ! procedure :: print_to_unit => fibonacci_stub_print_to_unit

<Muli fibonacci: fibonacci_stub: TBP>+≡
    procedure, nopass :: get_type => fibonacci_stub_get_type

<Muli fibonacci: procedures>+≡
    pure subroutine fibonacci_stub_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="fibonacci_stub_t")
    end subroutine fibonacci_stub_get_type

<Muli fibonacci: fibonacci_stub: TBP>+≡
    procedure :: push_by_content => fibonacci_stub_push_by_content

<Muli fibonacci: procedures>+≡
    subroutine fibonacci_stub_push_by_content (this, content)
        class(fibonacci_stub_t), target, intent(inout) :: this
        class(measure_class_t), target, intent(in) :: content
        class(fibonacci_leave_t), pointer :: leave
        allocate (leave)
        call leave%set_content (content)
        call this%push_by_leave (leave)
    end subroutine fibonacci_stub_push_by_content

<Muli fibonacci: fibonacci_stub: TBP>+≡
    procedure :: push_by_leave => fibonacci_stub_push_by_leave

```

```

<Muli fibonacci: procedures>+≡
subroutine fibonacci_stub_push_by_leave (this, new_leave)
  class(fibonacci_stub_t), target, intent(inout) :: this
  class(fibonacci_leave_t), pointer, intent(inout) :: new_leave
  class(fibonacci_leave_t), pointer :: old_leave
  if (this%depth < 1) then
    if (associated (this%leftmost)) then
      old_leave => this%leftmost
      call this%init_by_leave (old_leave, new_leave)
    else
      this%leftmost => new_leave
    end if
  else
    call fibonacci_root_push_by_leave (this, new_leave)
  end if
end subroutine fibonacci_stub_push_by_leave

```

```

<Muli fibonacci: fibonacci stub: TBP>+≡
procedure :: pop_left => fibonacci_stub_pop_left

```

```

<Muli fibonacci: procedures>+≡
subroutine fibonacci_stub_pop_left (this, leave)
  class(fibonacci_stub_t), intent(inout), target :: this
  class(fibonacci_leave_t), pointer, intent(out) :: leave
  if (this%depth < 2) then
    if (this%depth == 1) then
      leave => this%leftmost
      this%leftmost => this%rightmost
      nullify (this%rightmost)
      nullify (this%right)
      nullify (this%left)
      this%depth = 0
      this%is_valid_c = .false.
    else
      if (associated (this%leftmost)) then
        leave => this%leftmost
        nullify (this%leftmost)
      end if
    end if
  else
    call fibonacci_root_pop_left (this, leave)
  end if
end subroutine fibonacci_stub_pop_left

```

```

<Muli fibonacci: fibonacci stub: TBP>+≡
procedure :: pop_right => fibonacci_stub_pop_right

```

```

<Muli fibonacci: procedures>+≡
subroutine fibonacci_stub_pop_right (this, leave)
  class(fibonacci_stub_t), intent(inout), target :: this
  class(fibonacci_leave_t), pointer, intent(out) :: leave
  if (this%depth < 2) then
    if (this%depth == 1) then
      this%is_valid_c = .false.
    end if
  end if
end subroutine fibonacci_stub_pop_right

```

```

        if (associated (this%rightmost)) then
            leave => this%rightmost
            nullify (this%rightmost)
            nullify (this%right)
        else
            if (associated (this%leftmost)) then
                leave => this%leftmost
                nullify (this%leftmost)
                nullify (this%left)
            else
                nullify (leave)
            end if
        end if
    end if
else
    call fibonacci_root_pop_right (this, leave)
end if
end subroutine fibonacci_stub_pop_right

```

```

<Muli fibonacci: public>+≡
    public :: fibonacci_leave_list_t

```

```

<Muli fibonacci: types>+≡
    type fibonacci_leave_list_t
        class(fibonacci_leave_t), pointer :: leave => null()
        class(fibonacci_leave_list_t), pointer :: next => null()
    end type fibonacci_leave_list_t

```

```

<Muli fibonacci: procedures>+≡
    ! subroutine fibonacci_node_update_value (this, right_value)
    !     class(fibonacci_node_t), target :: this
    !     class(fibonacci_node_t), pointer :: node
    !     real(default), intent(in) :: right_value
    !     if (associated (this%left) .and. associated (this%right)) then
    !         node => this
    !         ! node%value = node%left%value
    !         ! right_value = node%right%value
    !         INNER: do while (associated (node%up))
    !             if (node%is_right_child ()) then
    !                 node => node%up
    !             else
    !                 node%up%value = right_value
    !                 exit
    !             end if
    !         end do INNER
    !     end if
    ! end subroutine fibonacci_node_update_value

```

```

<Muli fibonacci: procedures>+≡
    ! subroutine fibonacci_root_copy_node (this, primitive)
    !     class(fibonacci_root_t), intent(out) :: this
    !     type(fibonacci_node_t), intent(in) :: primitive
    !     call fibonacci_node_copy_node (this, primitive)

```

```

!   call primitive%find_leftmost (this%leftmost)
!   call primitive%find_rightmost (this%rightmost)
! end subroutine fibonacci_root_copy_node

```

<Multi fibonacci: procedures>+≡

```

! subroutine fibonacci_root_push_by_node (this, new_leave)
!   class(fibonacci_root_t), target, intent(inout) :: this
!   class(fibonacci_leave_t), pointer, intent(inout) :: new_leave
!   class(fibonacci_leave_t), pointer :: old_leave
!   if (new_leave <= this%leftmost) then
!     old_leave => this%leftmost
!     this%leftmost => new_leave
!   else
!     if (new_leave > this%rightmost) then
!       old_leave => this%rightmost
!       this%rightmost => new_leave
!     else
!       call this%find (new_leave%measure(), old_leave)
!     end if
!   end if
!   ! call old_leave%insert_leave_by_node (new_leave)
!   call fibonacci_leave_insert_leave_by_node (old_leave, new_leave)
!   call new_leave%up%repair ()
!   ! call new_leave%up%update_value ()
! end subroutine fibonacci_root_push_by_node

```

<Multi fibonacci: procedures>+≡

```

subroutine fibonacci_leave_write_content (this, unit)
  class(fibonacci_leave_t), intent(in), target :: this
  integer, optional, intent(in) :: unit
  call this%down%print_all (unit)
end subroutine fibonacci_leave_write_content

```

<Multi fibonacci: procedures>+≡

```

subroutine fibonacci_leave_write (this, unit)
  class(fibonacci_leave_t), intent(in), target :: this
  integer, optional, intent(in) :: unit
  call this%print_all (unit)
end subroutine fibonacci_leave_write

```

<Multi fibonacci: procedures>+≡

```

subroutine fibonacci_leave_write_value (this, unit)
  class(fibonacci_leave_t), intent(in), target :: this
  integer, intent(in), optional :: unit
  if (present (unit)) then
    write(unit, fmt=*) this%measure ()
  else
    print *, this%measure ()
  end if
  ! call this%print_little (unit)
end subroutine fibonacci_leave_write_value

```

```

<Multi fibonacci: procedures>+=
  subroutine fibonacci_node_spawn (new_node, left_leave, right_leave, &
    left_left_leave, right_right_leave)
    class(fibonacci_node_t), pointer, intent(out) :: new_node
    class(fibonacci_leave_t), target, intent(inout) :: left_leave, right_leave
    class(fibonacci_node_t), pointer, intent(inout) :: left_left_leave, &
      right_right_leave
    allocate (new_node)
    new_node%depth = 1
    if (associated (left_left_leave)) then
      left_left_leave%right => left_leave
      left_leave%left => left_left_leave
    else
      nullify (left_leave%left)
    end if
    if (associated (right_right_leave)) then
      right_right_leave%left => right_leave
      right_leave%right => right_right_leave
    else
      nullify (right_leave%right)
    end if
    new_node%left => left_leave
    new_node%right => right_leave
    new_node%down => left_leave%down
    new_node%depth = 1
    left_leave%up => new_node
    right_leave%up => new_node
    left_leave%right => right_leave
    right_leave%left => left_leave
  end subroutine fibonacci_node_spawn

```

21.7 Adaptive Quadrature

This file contains the module `muli_aq` which is an acronym for adaptive quadrature. The abstract type `aq_class` is extended and the deferred procedure `evaluate` is defined. `muli_aq` calls `evaluate` to evaluate the integrand at any point in the given range. We have tried to use a procedure pointer instead of the deferred type-bound procedure, but no compiler was able to handle procedure pointers plus `cuba` was not able to handle parameters, to wit dimensions of the integrand that should not get integrated. So we switched to this odd way of using inheritance. Meanwhile these problems got solved and we could go for a more straightforward solution, but it works fine as it is.

`aq_class` uses `muli_trapezium` to approximate the integral. It still has to do the subdivision of segments and has to check whether the precision goal is reached.

Finally, the result is written to disc using the serialization framework defined in `muli_base`. Since QCD is not expected to change frequently, the only reason to regenerate this function is a change of the used PDF set. Then you can read the integral from disc each time you run a simulation with the same PDF set.

```

<muli_aq.f90>=

```


⟨File header⟩

```
module multi_aq
```

⟨Use kinds⟩

```
  use constants
  use diagnostics
  use multi_base
  use multi_cuba
  use multi_trapezium
  use multi_fibonacci_tree
```

⟨Standard module head⟩

⟨Multi aq: public⟩

⟨Multi aq: types⟩

⟨Multi aq: interfaces⟩

```
contains
```

⟨Multi aq: procedures⟩

```
end module multi_aq
```

The variables `error_goal`, `err_tree` and `int_list` must be initialised before the main loop can be called. Additionally, the nodes and segments should be preprocessed by `first_run` before the main loop is called.

⟨Multi aq: public⟩≡

```
  public :: aq_class
```

⟨Multi aq: types⟩≡

```
  type, extends (identified_t), abstract :: aq_class
    logical :: is_deferred_initialised = .false.
    logical :: is_error_tree_initialised = .false.
    logical :: is_goal_set = .false.
    logical :: is_initialised = .false.
    logical :: is_run = .false.
    logical :: is_goal_reached = .false.
    logical :: is_integrated = .false.
    integer(dik) :: n_nodes = 0
    integer(dik) :: max_nodes = 10000
    integer :: dim_integral = 1
    real(default) :: abs_error_goal = 0._default
    real(default) :: rel_error_goal = 0.1_default
    real(default) :: scaled_error_goal = 0._default
    real(default) :: integral = 1._default
    real(default) :: integral_error = 0._default
    real(default), dimension(2) :: region = [0._default, 1._default]
    real(default), dimension(:, :), allocatable :: convergence
    real(default) :: total_time = 0
    real(default) :: loop_time = 0
    real(default) :: int_time = 0
```

```

    real(default) :: cuba_time = 0
    real(default) :: init_time = 0
    real(default) :: cpu_time = 0
    real(default) :: error_goal = 0._default
    class(fibonacci_root_t), pointer :: err_tree => null()
    class(muli_trapezium_list_t), pointer :: int_list => null()
contains
  <Muli aq: aq class: TBP>
end type aq_class

```

<Muli aq: aq class: TBP>≡

```

  procedure :: basic_write_to_marker => aq_write_to_marker
  procedure :: write_to_marker => aq_write_to_marker

```

<Muli aq: procedures>≡

```

  subroutine aq_write_to_marker (this, marker, status)
    class(aq_class), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    class(ser_class_t), pointer :: ser
    call marker%mark_begin ("aq_class")
    call this%base_write_to_marker (marker, status)
    call marker%mark ("is_deferred_initialised", &
      this%is_deferred_initialised)
    call marker%mark ("is_error_tree_initialised", &
      this%is_error_tree_initialised)
    call marker%mark ("is_goal_set", this%is_goal_set)
    call marker%mark ("is_initialised", this%is_initialised)
    call marker%mark ("is_run", this%is_run)
    call marker%mark ("is_goal_reached", this%is_goal_reached)
    call marker%mark ("is_integrated", this%is_integrated)
    call marker%mark ("n_nodes", this%n_nodes)
    call marker%mark ("max_nodes", this%max_nodes)
    call marker%mark ("dim_integral", this%dim_integral)
    call marker%mark ("abs_error_goal", this%abs_error_goal)
    call marker%mark ("rel_error_goal", this%rel_error_goal)
    call marker%mark ("scaled_error_goal", this%scaled_error_goal)
    call marker%mark ("error_goal", this%error_goal)
    call marker%mark ("integral", this%integral)
    call marker%mark ("integral_error", this%integral_error)
    call marker%mark ("region", this%region(1:2))
    ser => this%err_tree
    call marker%mark_pointer ("err_tree", ser)
    ser => this%int_list
    call marker%mark_pointer ("int_list", ser)
    call marker%mark_end ("aq_class")
  end subroutine aq_write_to_marker

```

<Muli aq: aq class: TBP>+≡

```

  procedure :: basic_read_from_marker => aq_read_from_marker
  procedure :: read_from_marker => aq_read_from_marker

```

<Muli aq: procedures>+≡

```

  subroutine aq_read_from_marker (this, marker, status)

```

```

class(aq_class), intent(out) :: this
class(marker_t), intent(inout) :: marker
integer(dik), intent(out) :: status
class(ser_class_t), pointer :: ser
call marker%pick_begin ("aq_class", status=status)
call this%base_read_from_marker (marker, status)
call marker%pick ("is_deferred_initialised", &
    this%is_deferred_initialised, status)
call marker%pick ("is_error_tree_initialised", &
    this%is_error_tree_initialised, status)
call marker%pick ("is_goal_set", this%is_goal_set, status)
call marker%pick ("is_initialised", this%is_initialised, status)
call marker%pick ("is_run", this%is_run, status)
call marker%pick ("is_goal_reached", this%is_goal_reached, status)
call marker%pick ("is_integrated", this%is_integrated, status)
call marker%pick ("n_nodes", this%n_nodes, status)
call marker%pick ("max_nodes", this%max_nodes, status)
call marker%pick ("dim_integral", this%dim_integral, status)
call marker%pick ("abs_error_goal", this%abs_error_goal, status)
call marker%pick ("rel_error_goal", this%rel_error_goal, status)
call marker%pick ("scaled_error_goal", this%scaled_error_goal, status)
call marker%pick ("error_goal", this%error_goal, status)
call marker%pick ("integral", this%integral, status)
call marker%pick ("integral_error", this%integral_error, status)
call marker%pick ("region", this%region(1:2), status)
call marker%pick_pointer ("err_tree", ser)
if (associated (ser)) then
    select type (ser)
    class is (fibonacci_root_t)
        this%err_tree => ser
    class default
        nullify (this%err_tree)
    end select
end if
call marker%pick_pointer ("int_list", ser)
if (associated (ser)) then
    select type (ser)
    class is (mulitrapezium_list_t)
        this%int_list => ser
    class default
        nullify (this%int_list)
    end select
end if
call marker%pick_end ("aq_class", status)
end subroutine aq_read_from_marker

```

(Mulitrapezium aq class: TBP) +=

```

procedure :: basic_print_to_unit => aq_print_to_unit
procedure :: print_to_unit => aq_print_to_unit

```

(Mulitrapezium aq procedures) +=

```

subroutine aq_print_to_unit (this, unit, parents, components, peers)
    class(aq_class), intent(in) :: this
    integer, intent(in) :: unit

```

```

integer(dik), intent(in) :: parents, components, peers
integer :: ite
class(ser_class_t), pointer :: ser
if (parents > 0) call this%base_print_to_unit &
    (unit, parents-1, components, peers)
write (unit, "(A)") "Components of aq_class"
write (unit, "(A,L1)") "Deferred class initialised: ", &
    this%is_deferred_initialised
write (unit, "(A,L1)") "Error tree initialised: ", &
    this%is_error_tree_initialised
write (unit, "(A,L1)") "Accuracy goal set: ", this%is_goal_set
write (unit, "(A,L1)") "Ready for run: ", this%is_initialised
write (unit, "(A,L1)") "Is run: ", this%is_run
write (unit, "(A,L1)") "Accuracy goal reached: ", this%is_goal_reached
write (unit, "(A,L1)") "Integral calculated: ", this%is_integrated
write (unit, "(A,I10)") "Number of nodes: ", this%n_nodes
write (unit, "(A,I10)") "Maximal number of nodes: ", this%max_nodes
write (unit, "(A,I10)") "Dimension of integral: ", this%dim_integral
write (unit, "(A,E20.10)") "Given abs. error goal: ", this%abs_error_goal
write (unit, "(A,E20.10)") "Given rel. error goal: ", this%rel_error_goal
write (unit, "(A,E20.10)") "Guessed abs error goal: ", this%scaled_error_goal
write (unit, "(A,E20.10)") "Actual abs error goal: ", this%error_goal
write (unit, "(A,E20.10)") "Integral ", this%integral
write (unit, "(A,E20.10)") "Estimated abs. error: ", this%integral_error
! if (this%integral == 0) then
!   write (unit, "(A,E20.10)") "Estimated rel. error: ", &
!       this%integral_error / this%integral
! else
!   write (unit, "(A,E20.10)") "Estimated rel. error: INF"
! end if
write (unit, "(A,E10.5,A,E10.5,A)") "Integration region = (", &
    this%region(1), " : ", this%region(2), ")"
ser => this%err_tree
call serialize_print_comp_pointer &
    (ser, unit, parents, components, peers, "error tree")
ser => this%int_list
call serialize_print_comp_pointer &
    (ser, unit, parents, components, peers, "integral list")
end subroutine aq_print_to_unit

```

<Muli aq: aq class: TBP>+≡
 procedure, nopass :: get_type => aq_get_type

<Muli aq: procedures>+≡
 pure subroutine aq_get_type (type)
 character(:), allocatable, intent(out) :: type
 allocate (type, source="aq_type")
 end subroutine aq_get_type

<Muli aq: aq class: TBP>+≡
 procedure :: deserialize_from_marker => aq_deserialize_from_marker

<Muli aq: procedures>+≡
 subroutine aq_deserialize_from_marker (this, name, marker)

```

class(aq_class), intent(out) :: this
character(*), intent(in) :: name
class(marker_t), intent(inout) :: marker
class(ser_class_t), pointer :: ser
allocate (mulitrapezium_t :: ser)
call marker%push_reference (ser)
allocate (fibonacci_root_t :: ser)
call marker%push_reference (ser)
allocate (fibonacci_leave_t :: ser)
call marker%push_reference (ser)
allocate (fibonacci_node_t :: ser)
call marker%push_reference (ser)
call serializable_deserialize_from_marker (this, name, marker)
call marker%pop_reference (ser)
deallocate (ser)
call marker%pop_reference (ser)
deallocate (ser)
call marker%pop_reference (ser)
deallocate (ser)
call marker%pop_reference (ser)
deallocate (ser)
end subroutine aq_deserialize_from_marker

```

The relative error goal is supposed to be 10^{-4} .

(Multi aq: aq class: TBP)+≡

```

generic :: initialize => aq_initialize
procedure :: aq_initialize

```

(Multi aq: procedures)+≡

```

subroutine aq_initialize (this, id, name, goal, max_nodes, dim, init)
class(aq_class), intent(out) :: this
integer(dik), intent(in) :: id, max_nodes
integer, intent(in) :: dim
character, intent(in) :: name
real(default) :: goal
real(default), dimension(:), intent(in) :: init
call this%initialize (id, name)
this%rel_error_goal = goal
this%max_nodes = max_nodes
call this%init_error_tree (dim, init)
end subroutine aq_initialize

```

(Multi aq: aq class: TBP)+≡

```

procedure :: print_times => aq_print_times

```

(Multi aq: procedures)+≡

```

subroutine aq_print_times (this)
class(aq_class), intent(in) :: this
write (*, "(A,E20.10)") "Initialization time: ", this%init_time
write (*, "(A,E20.10)") "Main loop time:      ", this%loop_time
write (*, "(A,E20.10)") "Integration time:   ", this%int_time
write (*, "(A,E20.10)") "Overall run time:    ", this%total_time
write (*, "(A,E20.10)") "Cuba integration time:", this%cuba_time
end subroutine aq_print_times

```

```

<Multi aq: aq class: TBP>+≡
    procedure :: write_convergence => aq_write_convergence

<Multi aq: procedures>+≡
    subroutine aq_write_convergence (this, unit)
        class(aq_class), intent(in) :: this
        integer, intent(in) :: unit
        integer, dimension(2) :: s
        integer :: node
        if (allocated (this%convergence)) then
            s = shape (this%convergence)
            do node = 1, s(2)
                write (unit, *) node, this%convergence (1:2, node)
            end do
        end if
    end subroutine aq_write_convergence

<Multi aq: aq class: TBP>+≡
    procedure :: reset => aq_reset

<Multi aq: procedures>+≡
    subroutine aq_reset (this)
        class(aq_class) :: this
        this%is_deferred_initialised = .false.
        this%is_error_tree_initialised = .false.
        this%is_goal_set = .false.
        this%is_initialised = .false.
        this%is_run = .false.
        this%is_goal_reached = .false.
        this%is_integrated = .false.
        this%n_nodes = 0
        this%max_nodes = 10000
        this%dim_integral = 1
        this%abs_error_goal = 1._default
        this%rel_error_goal = 0.1_default
        this%scaled_error_goal = 0.0_default
        this%error_goal = 0.0_default
        this%integral = 0.0_default
        this%integral_error = 0.0_default
        this%region = [ 0.0_default, 1._default ]
        this%total_time = 0
        this%loop_time = 0
        this%int_time = 0
        this%init_time = 0
        call this%dealloc_trees ()
    end subroutine aq_reset

<Multi aq: aq class: TBP>+≡
    procedure :: dealloc_trees => aq_dealloc_trees
    procedure :: finalize => aq_dealloc_trees

```

```

<Muli aq: procedures>+=
  subroutine aq_dealloc_trees (this)
    class(aq_class) :: this
    if (associated (this%err_tree)) then
      call this%err_tree%deallocate_all ()
      deallocate (this%err_tree)
    end if
    if (associated (this%int_list)) then
      call this%int_list%finalize ()
      deallocate (this%int_list)
    end if
  end subroutine aq_dealloc_trees

<Muli aq: aq class: TBP>+=
  procedure :: init_error_tree => aq_init_error_tree

<Muli aq: procedures>+=
  subroutine aq_init_error_tree (this, dim_integral, x_array)
    class(aq_class) :: this
    integer, intent(in) :: dim_integral
    real(default), dimension(:), intent(in) :: x_array
    real(default) :: center
    real(default), dimension(:), allocatable :: l_val, c_val, r_val
    class(muli_trapezium_t), pointer :: left_node => null()
    class(muli_trapezium_t), pointer :: right_node => null()
    integer :: x_size, pos
    ! print '("Entermarker aq_init_error_tree...")'
    call cpu_time (this%init_time)
    this%is_initialised = .false.
    this%integral = 0._default
    this%dim_integral = dim_integral
    x_size = size(x_array)
    if (x_size < 2) then
      call msg_error ("aq_init_error_tree: I need at least two real values")
    else
      allocate (l_val (0:dim_integral-1))
      allocate (c_val (0:dim_integral-1))
      allocate (r_val (0:dim_integral-1))
      this%region = [x_array(1), x_array(x_size)]
      if (x_size < 3) then
        center = (x_array(2) - x_array(1)) / 2._default
        call this%evaluate (x_array(1), l_val)
        call this%evaluate (center, c_val)
        call this%evaluate (x_array(2), r_val)
        allocate (left_node)
        call left_node%initialize (dim=dim_integral, &
          r_position=center, d_position=center-x_array(1))
        call left_node%set_r_value (c_val)
        call left_node%set_d_value (c_val - l_val)
        allocate (right_node)
        call right_node%initialize (dim=dim_integral, &
          r_position=x_array(2), d_position=x_array(2)-center)
        call right_node%set_r_value (r_val)
        call right_node%set_d_value (r_val - c_val)
      end if
    end if
  end subroutine aq_init_error_tree

```

```

else
  call this%evaluate (x_array(1), l_val)
  call this%evaluate (x_array(2), c_val)
  call this%evaluate (x_array(3), r_val)
  allocate (left_node)
  call left_node%initialize (dim=dim_integral, &
    r_position=x_array(2), d_position=x_array(2)-x_array(1))
  call left_node%set_r_value (c_val)
  call left_node%set_d_value (c_val - l_val)
  allocate (right_node)
  call right_node%initialize (dim=dim_integral, &
    r_position=x_array(3), d_position=x_array(3)-x_array(2))
  call right_node%set_r_value (r_val)
  call right_node%set_d_value (r_val - c_val)
end if
call left_node%update ()
call right_node%update ()
this%integral = sum (left_node%get_d_integral () + &
  right_node%get_d_integral ())
if (.not. associated (this%err_tree)) then
  allocate(this%err_tree)
end if
print *, left_node%measure ()
print *, right_node%measure ()
call this%err_tree%init_by_content (left_node, right_node)
! call this%err_tree%write_pstricks (11)
if (x_size > 3) then
  do pos = 4, x_size
    print *, "aq_init_error_tree", pos, "/", x_size
    l_val = right_node%get_r_value_array ()
    call this%evaluate (x_array(pos), r_val)
    c_val = r_val - l_val
    allocate (right_node)
    call right_node%initialize (dim=dim_integral, &
      r_position=x_array(pos), &
      d_position=x_array(pos)-x_array(pos-1))
    call right_node%set_r_value (r_val)
    call right_node%set_d_value (c_val)
    call right_node%update ()
    call this%err_tree%push_by_content (right_node)
    ! call this%err_tree%write_pstricks (11)
    this%integral = this%integral + sum (right_node%get_d_integral())
  end do
  this%n_nodes = x_size
end if
this%is_error_tree_initialised = .true.
end if
call this%set_goal ()
this%is_initialised = .true.
call cpu_time (this%cpu_time)
this%init_time = this%cpu_time - this%init_time
this%cuba_time = this%init_time
allocate (this%convergence (2, this%n_nodes:this%max_nodes))
end subroutine aq_init_error_tree

```



```

<Muli aq: aq class: TBP>+≡
    procedure :: set_rel_goal => aq_set_rel_goal

<Muli aq: procedures>+≡
    subroutine aq_set_rel_goal (this, goal)
        class(aq_class) :: this
        real(default) :: goal
        this%rel_error_goal = goal
        call this%set_goal
    end subroutine aq_set_rel_goal

<Muli aq: aq class: TBP>+≡
    procedure :: set_abs_goal => aq_set_abs_goal

<Muli aq: procedures>+≡
    subroutine aq_set_abs_goal (this, goal)
        class(aq_class) :: this
        real(default) :: goal
        this%abs_error_goal = goal
        call this%set_goal
    end subroutine aq_set_abs_goal

<Muli aq: aq class: TBP>+≡
    procedure :: set_goal => aq_set_goal

<Muli aq: procedures>+≡
    subroutine aq_set_goal (this)
        class(aq_class) :: this
        this%scaled_error_goal = this%rel_error_goal * abs(this%integral)
        if ((this%scaled_error_goal == zero) .and. &
            (this%abs_error_goal == zero)) then
            this%is_goal_set = .false.
            this%error_goal = zero
        else
            if (this%scaled_error_goal == zero) then
                this%error_goal = this%abs_error_goal
            else
                if (this%abs_error_goal == zero) then
                    this%error_goal = this%scaled_error_goal
                else
                    this%error_goal = max(this%scaled_error_goal, &
                        this%abs_error_goal)
                end if
            end if
        end if
        if (this%error_goal > zero) then
            this%is_goal_set = .true.
        else
            this%is_goal_set = .false.
        end if
    end if
end subroutine aq_set_goal

```

```

<Muli aq: aq class: TBP>+≡
  procedure :: check_init => aq_check_init

<Muli aq: procedures>+≡
  subroutine aq_check_init (this)
    class(aq_class) :: this
    this%is_initialised = this%is_error_tree_initialised .and. &
      this%is_deferred_initialised
  end subroutine aq_check_init

```

This routine is unsafe, when `n_nodes < 4`.

```

<Muli aq: aq class: TBP>+≡
  procedure :: main_loop => aq_main_loop

<Muli aq: procedures>+≡
  subroutine aq_main_loop (this)
    class(aq_class) :: this
    class(fibonacci_leave_t), pointer :: rightmost
    class(measure_class_t), pointer :: content
    class(muli_trapezium_t), pointer :: new_node !,debug
    logical :: limit = .false.
    real(default) :: center
    real(default), dimension(:), allocatable :: c_val
    allocate (c_val (0:this%dim_integral-1))
    LOOP: do
      call this%err_tree%pop_right (rightmost)
      if (rightmost < this%error_goal / this%n_nodes) then
        this%is_goal_reached = .true.
        exit LOOP
      else
        call rightmost%get_content (content)
        select type (content)
          class is (mulitrapezium_t)
            write (*, "(A,I5,A,E14.7,A,E14.7,A,E14.7,A,E14.7)") &
              "nodes: ", this%n_nodes, " error: ", &
              rightmost%measure() * this%n_nodes, &
              " goal: ", this%error_goal, " node at: ", &
              content%get_l_position(), "-", content%get_r_position()
            this%convergence (1, this%n_nodes) = this%error_goal / this%n_nodes
            this%convergence (2, this%n_nodes) = rightmost%measure ()
            center = content%get_r_position () - &
              content%get_d_position () / two
            call cpu_time (this%cpu_time)
            this%cuba_time = this%cuba_time - this%cpu_time
            call this%evaluate (center, c_val)
            call cpu_time (this%cpu_time)
            this%cuba_time = this%cuba_time + this%cpu_time
            call content%split (c_val, center, new_node)
            call this%err_tree%push_by_leave (rightmost)
            call this%err_tree%push_by_content (new_node)
          end select
          this%n_nodes = this%n_nodes + 1
          if (this%n_nodes > this%max_nodes) then
            limit = .true.
            exit LOOP
          end if
        end if
      end if
    end do
  end subroutine aq_main_loop

```

```

        end if
    end if
end do LOOP
    call this%err_tree%push_by_leave (rightmost)
end subroutine aq_main_loop

<Muli aq: aq class: TBP>+≡
    procedure :: run => aq_run

<Muli aq: procedures>+≡
    subroutine aq_run (this)
        class(aq_class) :: this
        call cpu_time (this%total_time)
        if (.not. this%is_error_tree_initialised) then
            call this%init_error_tree (this%dim_integral, this%region)
        end if
        this%is_run = .false.
        this%is_goal_reached = .false.
        call this%main_loop ()
        this%is_run = .true.
        call cpu_time (this%cpu_time)
        this%total_time = this%cpu_time - this%total_time
    end subroutine aq_run

<Muli aq: aq class: TBP>+≡
    procedure :: integrate => aq_integrate

<Muli aq: procedures>+≡
    subroutine aq_integrate (this, int_tree)
        class(aq_class) :: this
        class(muli_trapezium_node_class_t), pointer :: node
        type(muli_trapezium_tree_t), intent(out) :: int_tree
        real(default) :: sum
        this%is_integrated = .false.
        this%integral_error = zero
        if (this%is_run) then
            call cpu_time (this%int_time)
            call fibonacci_tree_resort_and_convert_to_trapezium_list &
                (this%err_tree, this%int_list)
            ! call this%int_list%print_all ()
            call this%int_list%integrate (this%integral, this%integral_error)
            call this%int_list%to_tree (int_tree)
            this%is_integrated = .true.
            call cpu_time (this%cpu_time)
            this%int_time = this%cpu_time - this%int_time
        end if
    end subroutine aq_integrate

<Muli aq: aq class: TBP>+≡
    procedure(evaluate_if), deferred :: evaluate
    ! procedure(evaluate_ratios_if), deferred :: evaluate_ratios

<Muli aq: procedures>+≡

```

Usually, the tree is sorted by the sum of errors. Now it shall be sorted by the right position. When at least one branch of the tree is itself a tree, i.e. each branch has got at least two leaves, then process each branch and merge the results. Now we got two sorted lists. Which one's leftmost node has got the lowest value of `r_position`? That one shall be the beginning of the merged list `lin_list`. Everything is prepared for the algorithm: `lin_list` is the beginning of the sorted list, `last_node` is its end. `left_node` and `right_node` are the leftmost nodes of the remainders of `left_list` and `right_list`. The latter will get stripped from left to right, until one of them ends. Then, either `left_list` or `right_list` is completely merged into `lin_list`. The other one gets appended to `lin_list`. In the second part of the big if clause, the tree has got two leaves at most. Is it more than one? There, `fib_tree` is a single leave with an allocated "content" component of type `muli_trapezium_t`. If "content" is not type-compatible with `muli_trapezium_t`, then this whole conversion cannot succeed. We allocate a new node of type `muli_trapezium_list_t`. This list does not contain the content of `fib_tree`, it *is* a copy of the content, for `muli_trapezium_list_t` is an extension of `muli_trapezium_t`. In the next step, each branch of `fib_tree` is a single leave. We could call this subroutine for each branch, but we do copy and paste for each branch instead. Finally we append one list to the other, the lowest value of `r_position` comes first.

(Muli aq: procedures)+≡

```
recursive subroutine fibonacci_tree_resort_and_convert_to_trapezium_list &
(fib_tree, lin_list)
class(fibonacci_node_t), intent(in) :: fib_tree
class(fibonacci_node_t), pointer :: leave
class(muli_trapezium_list_t), pointer, intent(out) :: lin_list
class(muli_trapezium_list_t), pointer :: left_list, right_list
class(muli_trapezium_node_class_t), pointer :: &
    left_node, right_node, last_node
class(measure_class_t), pointer :: content
if (fib_tree%depth > 1) then
    ! print *, "3A"
    call fibonacci_tree_resort_and_convert_to_trapezium_list &
        (fib_tree%left, left_list)
    call fibonacci_tree_resort_and_convert_to_trapezium_list &
        (fib_tree%right, right_list)
    if (left_list%is_left_of (right_list)) then
        lin_list => left_list
        call left_list%get_right (left_node)
        right_node => right_list
    else
        lin_list => right_list
        left_node => left_list
        call right_list%get_right (right_node)
    end if
    last_node => lin_list
    do while (associated (left_node) .and. associated (right_node))
        if (left_node%is_left_of (right_node)) then
            call last_node%append (left_node)
            call last_node%get_right (last_node)
            call left_node%get_right (left_node)
        else
```

```

        call last_node%append (right_node)
        call last_node%get_right (last_node)
        call right_node%get_right (right_node)
    end if
end do
if (associated (left_node)) then
    call last_node%append (left_node)
else
    call last_node%append (right_node)
end if
!!! It's done.
! print *, "3E"
else
if (fib_tree%depth == 0) then
! print *, "1A"
select type (fib_tree)
class is (fibonacci_leave_t)
    call fib_tree%get_content (content)
    select type (content)
    class is (multi_trapezium_t)
        call content%to_node (content%get_r_position(), list=lin_list)
    class default
        call msg_fatal &
            ("fibonacci_tree_resort_and_convert_to_trapezium_list: " // &
            "Content of fibonacci_tree is not type compatible " // &
            "to multi_trapezium_t")
    end select
end select
! print *, "1E"
else
! print *, "2A"
leave => fib_tree%left
select type (leave)
class is (fibonacci_leave_t)
    call leave%get_content (content)
    select type (content)
    class is (multi_trapezium_t)
        call content%to_node (content%get_r_position(), list=left_list)
    class default
        call msg_fatal &
            ("fibonacci_tree_resort_and_convert_to_trapezium_list: " // &
            "Content of fibonacci_tree is not type compatible " // &
            "to multi_trapezium_t")
    end select
end select
leave => fib_tree%right
select type (leave)
class is (fibonacci_leave_t)
    call leave%get_content (content)
    select type (content)
    class is (multi_trapezium_t)
        call content%to_node (content%get_r_position(), list=right_list)
    class default
        call msg_fatal &

```

```

        ("fibonacci_tree_resort_and_convert_to_trapezium_list: " // &
        "Content of fibonacci_tree is not type compatible " // &
        "to multi_trapezium_t")
    end select
end select
if (left_list%is_left_of (right_list)) then
    call left_list%append (right_list)
    lin_list => left_list
else
    call right_list%append (left_list)
    lin_list => right_list
end if
! print *, "2E"
end if
end if
! call lin_list%print_all ()
! call lin_list%check ()
end subroutine fibonacci_tree_resort_and_convert_to_trapezium_list

<Multi aq: interfaces>≡
interface
    subroutine evaluate_if (this, x, y)
        use kinds !NODEP!
        import aq_class
        class(aq_class), intent(inout) :: this
        real(default), intent(in) :: x
        real(default), intent(out) , dimension(:) :: y
    end subroutine evaluate_if

    ! subroutine evaluate_ratios_if (this, cont)
    !   use kinds
    !   use lin_approx_tree_module, only: multi_trapezium_t
    !   import aq_class
    !   class(aq_class) :: this
    !   class(multi_trapezium_t), intent(inout), pointer :: cont
    ! end subroutine evaluate_ratios_if
end interface

<multi_parameters.f90>≡
! This is a dummy for multi_parameters_module
module multi_parameters_module
end module multi_parameters_module

```

21.8 Integrands for Multiple Interactions

This file contains the module `multi_dsigma`. Its only type `multi_dsigma_t` provides an integrand to `aq_class`. The actual integrand is the normalized differential cross section of a QCD $2 \rightarrow 2$ process $1/\sigma_0 \times d^3\sigma/(dp_T^2 dx_1 dx_2)$. We need a root function of this integrand in terms of p_T , so we have to integrate out x_1 and x_2 and have to approximate the root function of the leftover variable p_T .

Integration of x_1 and x_2 is done by CUBA, the root function is approximated by `muli_aq`.

```

<muli_dsigma.f90>≡
  <File header>

  module muli_dsigma
    <Use kinds>
    use constants
    use muli_momentum
    use muli_interactions
    use muli_base
    use muli_cuba
    use muli_trapezium
    use muli_aq

    <Standard module head>

    <Muli dsigma: variables>

    <Muli dsigma: public>

    <Muli dsigma: types>

    contains

    <Muli dsigma: procedures>

  end module muli_dsigma

  <Muli dsigma: variables>≡
    integer, parameter :: dim_f = 17

  <Muli dsigma: public>≡
    public :: muli_dsigma_t

  <Muli dsigma: types>≡
    type, extends (aq_class) :: muli_dsigma_t
    private
    type(transverse_mom_t) :: pt
    type(cuba_divonne_t) :: cuba_int
    contains
    <Muli dsigma: dsigma: TBP>
  end type muli_dsigma_t

  <Muli dsigma: dsigma: TBP>≡
    procedure :: write_to_marker => muli_dsigma_write_to_marker

  <Muli dsigma: procedures>≡
    subroutine muli_dsigma_write_to_marker (this, marker, status)
      class(muli_dsigma_t), intent(in) :: this
      class(marker_t), intent(inout) :: marker
      integer(dik), intent(out) :: status
      class(ser_class_t), pointer :: ser

```

```

        call marker%mark_begin ("multi_dsigma_t")
        call this%basic_write_to_marker (marker, status)
        call this%cuba_int%serialize (marker, "cuba_int")
        call marker%mark_end ("multi_dsigma_t")
    end subroutine multi_dsigma_write_to_marker

<Muli dsigma: dsigma: TBP>+≡
    procedure :: read_from_marker => multi_dsigma_read_from_marker

<Muli dsigma: procedures>+≡
    subroutine multi_dsigma_read_from_marker (this, marker, status)
        class(multi_dsigma_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%pick_begin ("multi_dsigma_t", status=status)
        call this%basic_read_from_marker (marker, status)
        call this%cuba_int%deserialize ("cuba_int", marker)
        call marker%pick_end ("multi_dsigma_t", status)
    end subroutine multi_dsigma_read_from_marker

<Muli dsigma: dsigma: TBP>+≡
    procedure :: print_to_unit => multi_dsigma_print_to_unit

<Muli dsigma: procedures>+≡
    subroutine multi_dsigma_print_to_unit &
        (this, unit, parents, components, peers)
        class(multi_dsigma_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        integer :: ite
        if (parents > 0) call this%basic_print_to_unit &
            (unit, parents-1, components, peers)
        write (unit, "(A)") "Components of multi_dsigma_t"
        if (components > 0) then
            write (unit, "(A)") "Printing components of cuba_int:"
            call this%cuba_int%print_to_unit (unit, parents, components-1, peers)
        else
            write (unit, "(A)") "Skipping components of cuba_int:"
        end if
    end subroutine multi_dsigma_print_to_unit

<Muli dsigma: dsigma: TBP>+≡
    procedure, nopass :: get_type => multi_dsigma_get_type

<Muli dsigma: procedures>+≡
    pure subroutine multi_dsigma_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="multi_dsigma_t")
    end subroutine multi_dsigma_get_type

<Muli dsigma: dsigma: TBP>+≡
    procedure :: generate => multi_dsigma_generate

```


<Muli dsigma: procedures>+≡

```

subroutine multi_dsigma_generate (this, gev2_scale_cutoff, gev2_s, int_tree)
  class(muli_dsigma_t), intent(inout) :: this
  real(default), intent(in) :: gev2_scale_cutoff, gev2_s
  type(muli_trapezium_tree_t), intent(out) :: int_tree
  real(default), dimension(ceiling (log (gev2_s/gev2_scale_cutoff)/two)) :: &
    initial_values
  integer :: n
  print *, gev2_s/gev2_scale_cutoff, &
    ceiling (log (gev2_s/gev2_scale_cutoff)/two)
  ! allocate (initial_values (ceiling (-log (gev2_scale_cutoff))/2))
  ! allocate (real(default), &
  !   dimension (ceiling (log(gev2_scale_cutoff))/2) :: initial_values)
  initial_values(1) = sqrt(gev2_scale_cutoff/gev2_s) * two
  do n = 2, size(initial_values) - 1
    initial_values(n) = initial_values(n-1) * euler
  end do
  initial_values(n) = one
  print *, initial_values
  ! stop
  call this%initialize (i_one, "dsigma")
  call this%pt%initialize (gev2_s)
  this%abs_error_goal = zero
  this%rel_error_goal = scale(one, -12) !-12
  this%max_nodes = 1000
  call this%cuba_int%set_common (dim_f=dim_f, dim_x=2, &
    eps_rel=scale(this%rel_error_goal,-8), flags = 0)
  call this%cuba_int%set_deferred (xgiven_flat = [1.E-2_default, &
    5.E-1_default + epsilon(1._default), 1.E-2_default, &
    5.E-1_default - epsilon(1._default)])
  print *, "multi_dsigma_generate:"
  ! print *, "Cuba Error Goal:   ", this%cuba_int%eps_rel
  print *, "Overall Error Goal: ", this%rel_error_goal
  call this%init_error_tree (dim_f, initial_values)
  call this%run ()
  call this%integrate (int_tree)
  call this%err_tree%deallocate_all ()
  deallocate (this%err_tree)
  nullify (this%int_list)
end subroutine multi_dsigma_generate

```

<Muli dsigma: dsigma: TBP>+≡

```

procedure :: evaluate => multi_dsigma_evaluate

```

<Muli dsigma: procedures>+≡

```

subroutine multi_dsigma_evaluate (this, x, y)
  class(muli_dsigma_t), intent(inout) :: this
  real(default), intent(in) :: x
  real(default), intent(out), dimension(:):: y
  call this%pt%set_unit_scale (x)
  ! print *, "multi_dsigma_evaluate x=", x
  ! call this%cuba_int%integrate_userdata &
  !   (interactions_proton_proton_integrand_param_17_reg, this%pt)
  ! if (this%cuba_int%fail == 0) then

```

```

! call this%cuba_int%print_all ()
call this%cuba_int%get_integral_array (y)
! else
!   print *, "multi_dsigma_evaluate: failed."
!   stop
! end if
end subroutine multi_dsigma_evaluate

```

<Muli dsigma: dsigma: TBP>+≡

```

generic :: initialize => multi_dsigma_initialize
procedure :: multi_dsigma_initialize

```

<Muli dsigma: procedures>+≡

```

subroutine multi_dsigma_initialize &
  (this, id, name, goal, max_nodes, dim, cuba_goal)
  class(muli_dsigma_t), intent(inout) :: this
  integer(dik), intent(in) :: id, max_nodes
  integer, intent(in) :: dim
  character(*), intent(in) :: name
  real(default), intent(in) :: goal, cuba_goal
  call this%initialize (id,name)
  ! 1E-4
  this%rel_error_goal = goal
  this%max_nodes = max_nodes
  call this%cuba_int%set_common (dim_f=dim, dim_x=2, &
    ! 1E-6
    eps_rel=cuba_goal, flags = 0)
  call this%cuba_int%set_deferred (xgiven_flat = [1.E-2_default, &
    5.E-1_default + epsilon(1._default), &
    1.E-2_default, 5.E-1_default - epsilon(1._default)])
  ! call aq_initialize (this, id, name, d_goal, max_nodes, dim_f, &
  !   [8E-1_default/7E3_default, 2E-3_default, 1E-2_default, &
  !   1E-1_default, one])
  call this%init_error_tree (dim, [8.E-1_default/7.E3_default, &
    2.E-3_default, 1.E-2_default, 1.E-1_default, &
    1._default])
  this%is_deferred_initialised = .true.
end subroutine multi_dsigma_initialize

```

<Muli dsigma: dsigma: TBP>+≡

```

! procedure :: reset => multi_dsigma_reset

```

<Muli dsigma: procedures>+≡

```

! subroutine multi_dsigma_reset (this)
!   class(muli_dsigma_t), intent(inout) :: this
!   call aq_reset (this)
!   call this%initialize &
!     (id, name, d_goal, max_nodes, dim_f, init, cuba_goal)
! end subroutine multi_dsigma_reset

```

21.9 MC Integrations for QCD $2 \rightarrow 2$ processes

This file contains the module `muli_mcint` which is the Monte Carlo generator for QCD $2 \rightarrow 2$ interactions at given evolution parameter and given stratus. While `muli_t` takes care of generating the evolution parameter and the stratus, this module is about bookkeeping the strati and implementing a downstream importance sampling. The evolution parameter is a measure of transferred momentum and a “stratus” is a PDF category or, to be more precise, is whether the incoming partons are gluons or sea quarks or valence quarks.

The importance sampling then subdivides the phase space of variables $\{x_1, x_2, p_T\}$ into n^3 regions such that each region holds approximately n interactions. Thus, we can generate a phase space point very quickly just by randomly picking a region, randomly picking a point within this region and comparing its exact cross section with the mean cross section for this actual evolution parameter and the actual stratus times the area of the picked phase space region.

The mean values must be generated in the module `muli_dsigma` before and are given to the procedure `sample_inclusive_generate_hit`. Finally the generated subregions should be written to a file via `write_to_marker` and then reused for each later WHIZARD run.

The type `sample_inclusive_t` holds the 16 strati, while the type `sample_int_kind_t` represents a single stratus, `sample_3d_t` is the whole $\{x_1, x_2, p_T\}$ phase space for each stratus, `sample_2d_t` is the $\{x_1, x_2\}$ plane with a slice of p_T and `sample_region_t` finally is a phase space region.

```

<muli_mcint.f90>≡
  <File header>

  module muli_mcint
    <Use kinds>
    use constants
    use muli_base
    use tao_random_numbers !NODEP!
    use muli_interactions

    <Standard module head>

    <Muli MC int: variables>

    <Muli MC int: public>

    <Muli MC int: types>

    contains

    <Muli MC int: procedures>

  end module muli_mcint

<Muli MC int: variables>≡
  integer, parameter :: max_n = 2**30
<Muli MC int: variables>+≡
  real(default), parameter :: max_d = one * max_n

```

```

<Muli MC int: variables>+≡
    real(default), parameter, dimension(2,2) :: &
        unit_square = reshape([zero,zero,one,one], [2,2])

<Muli MC int: public>≡
    public :: sample_region_t

<Muli MC int: types>≡
    type, extends (ser_class_t) :: sample_region_t
        integer :: n_hits = 0
        integer :: n_alloc = 0
        real(default), dimension(2,2) :: corners = unit_square
        real(default), dimension(:,:), allocatable :: hyp_hits
    contains
        <Muli MC int: sample region: TBP>
    end type sample_region_t

<Muli MC int: sample region: TBP>≡
    procedure :: write_to_marker => sample_region_write_to_marker

<Muli MC int: procedures>≡
    subroutine sample_region_write_to_marker (this, marker, status)
        class(sample_region_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        integer :: n
        call marker%mark_begin ("sample_region_t")
        call marker%mark ("n_hits", this%n_hits)
        call marker%mark ("n_alloc", this%n_alloc)
        call marker%mark ("lower_corner", this%corners(1:2,1))
        call marker%mark ("upper_corner", this%corners(1:2,2))
        if (allocated (this%hyp_hits)) then
            call marker%mark ("hyp_hits", this%hyp_hits (1:3,:this%n_hits))
        else
            call marker%mark_nothing ("hyp_hits")
        end if
        call marker%mark_end ("sample_region_t")
    end subroutine sample_region_write_to_marker

<Muli MC int: sample region: TBP>+≡
    procedure :: read_from_marker => sample_region_read_from_marker

<Muli MC int: procedures>+≡
    subroutine sample_region_read_from_marker (this, marker, status)
        class(sample_region_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        integer :: n
        call marker%pick_begin ("sample_region_t", status=status)
        call marker%pick ("n_hits", this%n_hits, status)
        call marker%pick ("n_alloc", this%n_alloc, status)
        call marker%pick ("lower_corner", this%corners(1:2,1), status)
        call marker%pick ("upper_corner", this%corners(1:2,2), status)
        if (allocated (this%hyp_hits)) deallocate (this%hyp_hits)

```

```

    call marker%verify_nothing ("hyp_hits", status)
    if (.not. status == serialize_nothing) then
        allocate (this%hyp_hits (3,this%n_alloc))
        call marker%pick ("hyp_hits", this%hyp_hits (1:3,:this%n_hits), status)
    end if
    call marker%pick_end ("sample_region_t", status)
end subroutine sample_region_read_from_marker

```

<Muli MC int: sample region: TBP>+≡

```

    procedure :: print_to_unit => sample_region_print_to_unit

```

<Muli MC int: procedures>+≡

```

subroutine sample_region_print_to_unit &
    (this, unit, parents, components, peers)
class(sample_region_t), intent(in) :: this
integer, intent(in) :: unit
integer(dik), intent(in) :: parents, components, peers
write (unit, "(1x,A)")      "components of sample_region_t"
write (unit, "(3x,A,I10)")  "n_hits:           ", this%n_hits
write (unit, "(3x,A,I10)")  "n_alloc:          ", this%n_alloc
write (unit, "(3x,4(E20.10))") "corners:         ", this%corners
if (allocated (this%hyp_hits) .and. this%n_hits > 0) then
    if (components > 0) then
        write (unit,"(3x,A)") "hits:"
        print *, shape (this%hyp_hits)
        write (unit, "(3(e20.10))") this%hyp_hits (1:3, this%n_hits)
    else
        write (unit, "(3x,A)") "skipping hits."
    end if
else
    write (unit, "(3x,A)") "hits are not allocated."
end if
end subroutine sample_region_print_to_unit

```

<Muli MC int: sample region: TBP>+≡

```

    procedure, nopass :: get_type => sample_region_get_type

```

<Muli MC int: procedures>+≡

```

pure subroutine sample_region_get_type (type)
character(:), allocatable, intent(out) :: type
allocate (type, source="sample_region_t")
end subroutine sample_region_get_type

```

<Muli MC int: sample region: TBP>+≡

```

    procedure :: initialize => sample_region_initialize

```

<Muli MC int: procedures>+≡

```

subroutine sample_region_initialize (this, n_alloc)
class(sample_region_t), intent(out) :: this
integer, intent(in) :: n_alloc
if (allocated (this%hyp_hits)) deallocate (this%hyp_hits)
allocate (this%hyp_hits (3,n_alloc))
this%n_alloc = n_alloc
end subroutine sample_region_initialize

```

```

<Muli MC int: sample region: TBP>+=
  procedure :: generate_hit => sample_region_generate_hit

<Muli MC int: procedures>+=
  pure subroutine sample_region_generate_hit (this, rnd, area, hit)
    class(sample_region_t), intent(in) :: this
    integer, intent(in), dimension(2) :: rnd
    real(default), dimension(2), intent(out) :: hit
    real(default), intent(out) :: area
    call muli_mcint_generate_hit (rnd, this%corners, hit)
    area = this%area ()
  end subroutine sample_region_generate_hit

<Muli MC int: sample region: TBP>+=
  procedure :: confirm_hit => sample_region_confirm_hit

<Muli MC int: procedures>+=
  subroutine sample_region_confirm_hit (this, hit)
    class(sample_region_t), intent(inout) :: this
    real(default), dimension(3), intent(in) :: hit
    ! print *, "sample_region_confirm_hit: ", this%n_hits, this%n_alloc, hit
    this%n_hits = this%n_hits + 1
    if (this%n_hits <= this%n_alloc) then
      this%hyp_hits (1:3, this%n_hits) = hit
    else
      print *, "sample_region_confirm_hit: Region is already full."
    end if
  end subroutine sample_region_confirm_hit

<Muli MC int: sample region: TBP>+=
  procedure :: split => sample_region_split

<Muli MC int: procedures>+=
  subroutine sample_region_split (this, pos, dimX, n_alloc, lower, upper)
    class(sample_region_t), intent(in) :: this
    type(sample_region_t), intent(out) :: lower, upper
    real(default), dimension(3) :: hit
    real(default), intent(in) :: pos
    integer, intent(in) :: dimX, n_alloc
    integer :: n_hit
    call lower%initialize (n_alloc)
    call upper%initialize (n_alloc)
    do n_hit = 1, this%n_hits
      hit = this%hyp_hits (1:3, n_hit)
      if (hit(dimX) < pos) then
        call lower%confirm_hit (hit)
      else
        call upper%confirm_hit (hit)
      end if
    end do
    lower%corners = this%corners
    upper%corners = this%corners
    if (dimX < 3) then
      lower%corners(dimX,2) = pos
      upper%corners(dimX,1) = pos
    end if
  end subroutine sample_region_split

```

```

        end if
    end subroutine sample_region_split

<Muli MC int: sample region: TBP>+≡
    procedure :: write_hits => sample_region_write_hits

<Muli MC int: procedures>+≡
    subroutine sample_region_write_hits (this, unit)
        class(sample_region_t), intent(in) :: this
        integer, intent(in) :: unit
        integer :: n
        do n = 1, this%n_hits
            write (unit, *) this%hyp_hits (1:3,n)
        end do
    end subroutine sample_region_write_hits

<Muli MC int: sample region: TBP>+≡
    procedure :: is_full => sample_region_is_full

<Muli MC int: procedures>+≡
    elemental logical function sample_region_is_full (this)
        class(sample_region_t), intent(in) :: this
        sample_region_is_full = this%n_alloc == this%n_hits
    end function sample_region_is_full

<Muli MC int: sample region: TBP>+≡
    procedure :: move_components => sample_region_move_components

<Muli MC int: procedures>+≡
    subroutine sample_region_move_components (this, that)
        class(sample_region_t), intent(inout) :: this
        class(sample_region_t), intent(out) :: that
        that%n_alloc = this%n_alloc
        that%n_hits = this%n_hits
        that%corners = this%corners
        call move_alloc (this%hyp_hits, that%hyp_hits)
        this%n_alloc = 0
        this%n_hits = 0
    end subroutine sample_region_move_components

<Muli MC int: sample region: TBP>+≡
    procedure :: mean => sample_region_mean

<Muli MC int: procedures>+≡
    elemental function sample_region_mean (this, dim)
        real(default) :: sample_region_mean
        class(sample_region_t), intent(in) :: this
        integer, intent(in) :: dim
        sample_region_mean = sum (this%hyp_hits (dim,1:this%n_hits)) / this%n_hits
    end function sample_region_mean

<Muli MC int: sample region: TBP>+≡
    procedure :: area => sample_region_area

```

```

<Muli MC int: procedures>+≡
    elemental function sample_region_area (this)
        real(default) :: sample_region_area
        class(sample_region_t), intent(in) :: this
        sample_region_area = product (this%corners(1:2,2) - this%corners(1:2,1))
    end function sample_region_area

<Muli MC int: sample region: TBP>+≡
    procedure :: density => sample_region_density

<Muli MC int: procedures>+≡
    elemental function sample_region_density (this)
        real(default) :: sample_region_density
        class(sample_region_t), intent(in) :: this
        sample_region_density = this%n_hits / this%area ()
    end function sample_region_density

<Muli MC int: sample region: TBP>+≡
    procedure :: contains => sample_region_contains

<Muli MC int: procedures>+≡
    pure logical function sample_region_contains (this, hit)
        class(sample_region_t), intent(in) :: this
        real(default), intent(in), dimension(3) :: hit
        sample_region_contains = (this%corners(1,1) <= hit(1) .and. &
            hit(1) <= this%corners(1,2) .and. &
            this%corners(2,1) <= hit(2) .and. &
            hit(2) <= this%corners(2,2))
    end function sample_region_contains

<Muli MC int: sample region: TBP>+≡
    procedure :: to_generator => sample_region_to_generator

<Muli MC int: procedures>+≡
    subroutine sample_region_to_generator (this)
        class(sample_region_t), intent(inout) :: this
        if (allocated (this%hyp_hits)) deallocate (this%hyp_hits)
        this%n_alloc = 0
    end subroutine sample_region_to_generator

<Muli MC int: public>+≡
    public :: sample_2d_t

<Muli MC int: types>+≡
    type, extends (ser_class_t) :: sample_2d_t
        integer :: n_regions = 0
        integer :: n_alloc = 0
        integer :: n_hits = 0
        real(default), dimension(2) :: range = [0,1]
        type(sample_region_t), dimension(:), allocatable :: regions
    contains
        <Muli MC int: sample 2D: TBP>
    end type sample_2d_t

```



```

<Muli MC int: sample 2D: TBP>≡
  procedure :: write_to_marker => sample_2d_write_to_marker

<Muli MC int: procedures>+≡
  subroutine sample_2d_write_to_marker (this, marker, status)
    class(sample_2d_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    integer :: n
    call marker%mark_begin ("sample_2d_t")
    call marker%mark ("n_regions", this%n_regions)
    call marker%mark ("n_alloc", this%n_alloc)
    call marker%mark ("n_hits", this%n_hits)
    call marker%mark ("range", this%range)
    if (this%n_regions > 0) then
      call marker%mark_instance_begin &
        (this%regions(1), name="sample_2d_t", shape=shape (this%regions))
      do n = 1, this%n_regions
        call sample_region_write_to_marker (this%regions(n), marker, status)
      end do
      call marker%mark_instance_end ()
    end if
    call marker%mark_end ("sample_2d_t")
  end subroutine sample_2d_write_to_marker

<Muli MC int: sample 2D: TBP>+≡
  procedure :: read_from_marker => sample_2d_read_from_marker

<Muli MC int: procedures>+≡
  subroutine sample_2d_read_from_marker (this, marker, status)
    class(sample_2d_t), intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    integer :: n
    call marker%pick_begin ("sample_2d_t", status=status)
    call marker%pick ("n_regions", this%n_regions, status)
    call marker%pick ("n_alloc", this%n_alloc, status)
    call marker%pick ("n_hits", this%n_hits, status)
    call marker%pick ("range", this%range, status)
    if (this%n_regions > 0) then
      call marker%pick_begin ("regions", status=status)
      allocate (this%regions (this%n_regions))
      do n = 1, this%n_regions
        call sample_region_read_from_marker (this%regions(n), marker, status)
      end do
      call marker%pick_end ("regions", status)
    end if
    call marker%pick_end ("sample_2d_t", status)
  end subroutine sample_2d_read_from_marker

<Muli MC int: sample 2D: TBP>+≡
  procedure :: print_to_unit => sample_2d_print_to_unit

```

```

<Muli MC int: procedures>+≡
subroutine sample_2d_print_to_unit (this, unit, parents, components, peers)
  class(sample_2d_t), intent(in) :: this
  integer, intent(in) :: unit
  integer(dik), intent(in) :: parents, components, peers
  integer :: n
  write (unit, "(1x,A)") "components of sample_2d_t"
  write (unit, "(3x,A,I10)") "n_regions: ", this%n_regions
  write (unit, "(3x,A,I10)") "n_alloc: ", this%n_alloc
  write (unit, "(3x,A,2(E20.10))") "range: ", this%range
  if (allocated (this%regions)) then
    if (components > 0) then
      write (unit, "(3x,A)") "regions:"
      do n = 1, this%n_regions
        call this%regions(n)%print_to_unit &
          (unit, parents, components-1, peers)
      end do
    else
      write (unit, "(3x,A)") "skipping regions."
    end if
  else
    write (unit, "(3x,A)") "regions are not allocated."
  end if
end subroutine sample_2d_print_to_unit

```

```

<Muli MC int: sample 2D: TBP>+≡
procedure, nopass :: get_type => sample_2d_get_type

```

```

<Muli MC int: procedures>+≡
pure subroutine sample_2d_get_type (type)
  character(:), allocatable, intent(out) :: type
  allocate (type, source="sample_2d_t")
end subroutine sample_2d_get_type

```

```

<Muli MC int: sample 2D: TBP>+≡
procedure :: initialize => sample_2d_initialize

```

```

<Muli MC int: procedures>+≡
subroutine sample_2d_initialize (this, n_alloc)
  class(sample_2d_t), intent(out) :: this
  integer, intent(in) :: n_alloc
  integer :: n
  if (allocated (this%regions)) deallocate (this%regions)
  allocate (this%regions (n_alloc))
  this%n_alloc = n_alloc
  this%n_regions = 1
  call this%regions(1)%initialize (n_alloc)
  ! do n = 1, n_alloc
  !   call this%regions(n)%initialize (n_alloc)
  ! end do
end subroutine sample_2d_initialize

```

```

<Muli MC int: sample 2D: TBP>+≡
procedure :: contains => sample_2d_contains

```

```

<Muli MC int: procedures>+≡
  pure logical function sample_2d_contains (this, pts2)
    class(sample_2d_t), intent(in) :: this
    real(default), intent(in) :: pts2
    sample_2d_contains = this%range(1) <= pts2 .and. pts2 <= this%range(2)
  end function sample_2d_contains

<Muli MC int: sample 2D: TBP>+≡
  procedure :: generate_hit => sample_2d_generate_hit

<Muli MC int: procedures>+≡
  pure subroutine sample_2d_generate_hit (this, rnd, boost, hit, region)
    class(sample_2d_t), intent(in) :: this
    integer, dimension(3), intent(in) :: rnd
    integer, intent(out) :: region
    integer :: n, sum
    real(default), dimension(2), intent(out) :: hit
    real(default), intent(out) :: boost
    if (0 < this%n_hits .and. this%n_hits < 10) then
      !!! this should be improved
      sum = modulo(rnd(1), this%n_hits) + 1
      region = 0
      do while (sum > 0)
        region = region + 1
        sum = sum - this%regions(region)%n_hits
      end do
      call this%regions(region)%generate_hit (rnd(2:3), boost, hit)
      boost = boost * this%n_hits / this%regions(region)%n_hits
    else
      if (this%n_regions > 1) then
        !!! this should be improved
        region = modulo(rnd(1), this%n_regions) + 1
        call this%regions(region)%generate_hit (rnd(2:3), boost, hit)
        boost = boost * this%n_regions
      else
        region = 1
        call this%regions(1)%generate_hit (rnd(2:3), boost, hit)
      end if
    end if
  end subroutine sample_2d_generate_hit

! pure subroutine sample_2d_generate_hit (this, rnd, boost, hit, region)
!   class(sample_2d_t), intent(in) :: this
!   integer, dimension(3), intent(in) :: rnd
!   integer, intent(out) :: region
!   real(double), dimension(2), intent(out) :: hit
!   real(double), intent(out) :: boost
!   region = modulo(rnd(1), this%n_regions) + 1   !!! this should be improved
!   call this%regions(region)%generate_hit (rnd(2:3), boost, hit)
!   boost = boost * this%n_regions
! end subroutine sample_2d_generate_hit

<Muli MC int: sample 2D: TBP>+≡
  procedure :: confirm_hit => sample_2d_confirm_hit

```

<Muli MC int: procedures>+≡

```

subroutine sample_2d_confirm_hit (this, hit, region, full)
  class(sample_2d_t), intent(inout) :: this
  integer, intent(in) :: region
  real(default), dimension(3), intent(in) :: hit
  type(sample_region_t), allocatable :: old_region
  real(default), dimension(2) :: mean, var, diff, cm, cv, c
  integer :: n, n_alloc, dim
  logical, intent(out) :: full
  this%n_hits = this%n_hits + 1
  if (region <= this%n_alloc) then
    full = .false.
    call this%regions(region)%confirm_hit (hit)
    n_alloc = this%regions(region)%n_alloc
    if (this%regions(region)%is_full()) then
      if (this%is_full()) then
        full = .true.
      else
        this%n_regions = this%n_regions + 1
        allocate (old_region)
        call this%regions(region)%move_components (old_region)
        mean = sum (old_region%hyp_hits(1:2,:), dim=2) / n_alloc
        var = 0
        do n = 1, n_alloc
          var = var + abs(mean-old_region%hyp_hits(1:2,n))
        end do
        var = var / n_alloc
        diff = old_region%corners(1:2,2) - old_region%corners(1:2,1)
        cm = abs ([0.5_default,0.5_default] - &
          (old_region%corners(1:2,2) - mean) / diff)
        cv = abs(2*([0.25_default,0.25_default] - var / diff))
        c = max(cm,cv)
        if (c(1) < c(2)) then
          dim = 2
        else
          dim = 1
        end if
        call old_region%split (mean(dim), dim, this%n_alloc, &
          this%regions(region), this%regions(this%n_regions))
      end if
    end if
  else
    write (*,*) "sample_2d_confirm_hit: Region ", region, &
      " not allocated."
  end if
end subroutine sample_2d_confirm_hit

```

<Muli MC int: sample 2D: TBP>+≡

```

procedure :: split => sample_2d_split

```

<Muli MC int: procedures>+≡

```

recursive subroutine sample_2d_split (this, n_alloc, pos, lower, upper)
  class(sample_2d_t), intent(in) :: this
  integer, intent(in) :: n_alloc

```

```

real(default), intent(in) :: pos
type(sample_2d_t), intent(out) :: lower, upper
integer :: n_r, n_h
real(default), dimension(3) :: hit
! print *, "sample_2d_split: ", pos, this%range
call lower%initialize (4*n_alloc)
call upper%initialize (4*n_alloc)
do n_r = this%n_regions, 1, -1
  do n_h = 1, this%regions(n_r)%n_hits
    hit = this%regions(n_r)%hyp_hits (1:3,n_h)
    if (hit(3) > pos) then
      call upper%push (hit)
    else
      call lower%push (hit)
    end if
  end do
end do
lower%range = [this%range(1), pos]
upper%range = [pos, this%range(2)]
end subroutine sample_2d_split

! subroutine sample_2d_split (this, n_alloc, pos, lower, upper)
!   class(sample_2d_t), intent(in) :: this
!   integer, intent(in) :: n_alloc
!   real(default), intent(in) :: pos
!   type(sample_2d_t), intent(out) :: lower, upper
!   integer :: n, n_hit
!   real(default), dimension(3) :: hit
!   allocate (lower%regions (n_alloc))
!   allocate (upper%regions (n_alloc))
!   !$OMP PARALLEL DO FIRSTPRIVATE (this, pos, n_alloc) SHARED (lower, upper)
!   do n = 1, this%n_regions
!     call sample_region_split (this%regions(n), pos, 3, n_alloc, &
!       lower%regions(n), upper%regions(n))
!   end do
!   !$OMP END PARALLEL DO
!   lower%n_regions = this%n_regions
!   upper%n_regions = this%n_regions
!   lower%n_alloc = n_alloc
!   upper%n_alloc = n_alloc
!   lower%range = [this%range(1), pos]
!   upper%range = [pos, this%range(2)]
! end subroutine sample_2d_split

```

<Multi MC int: sample 2D: TBP>+≡

```

  procedure :: push => sample_2d_push

```

<Multi MC int: procedures>+≡

```

subroutine sample_2d_push (this, hit)
  class(sample_2d_t), intent(inout) :: this
  real(default), dimension(3), intent(in) :: hit
  integer :: region
  logical :: full
  do region = 1, this%n_regions

```

```

        if (this%regions(region)%contains (hit)) then
            call this%confirm_hit (hit, region, full)
            ! call this%regions(region)%confirm_hit (hit)
            if (full) print *, "sample_2d_push: region is full now"
            exit
        end if
    end do
    if (region > this%n_regions) &
        print *, "sample_2d_push: no region contains ", hit
end subroutine sample_2d_push

```

<Muli MC int: sample 2D: TBP>+≡

```

    procedure :: write_hits => sample_2d_write_hits

```

<Muli MC int: procedures>+≡

```

    subroutine sample_2d_write_hits (this, unit)
        class(sample_2d_t), intent(in) :: this
        integer, intent(in) :: unit
        integer :: n
        do n = 1, this%n_regions
            call this%regions(n)%write_hits (unit)
        end do
    end subroutine sample_2d_write_hits

```

<Muli MC int: sample 2D: TBP>+≡

```

    procedure :: is_full => sample_2d_is_full

```

<Muli MC int: procedures>+≡

```

    elemental logical function sample_2d_is_full (this)
        class(sample_2d_t), intent(in) :: this
        sample_2d_is_full = this%n_alloc == this%n_regions
    end function sample_2d_is_full

```

<Muli MC int: sample 2D: TBP>+≡

```

    procedure :: move_components => sample_2d_move_components

```

<Muli MC int: procedures>+≡

```

    subroutine sample_2d_move_components (this, that)
        class(sample_2d_t), intent(inout) :: this
        class(sample_2d_t), intent(out) :: that
        that%n_alloc = this%n_alloc
        that%n_regions = this%n_regions
        that%n_hits = this%n_hits
        that%range = this%range
        call move_alloc (this%regions, that%regions)
        this%n_alloc = 0
        this%n_regions = 0
        this%n_hits = 0
        this%range = [zero,zero]
    end subroutine sample_2d_move_components

```

<Muli MC int: sample 2D: TBP>+≡

```

    procedure :: thickness => sample_2d_thickness

```

```

<Multi MC int: procedures>+≡
  elemental function sample_2d_thickness (this)
    class(sample_2d_t), intent(in) :: this
    real(default) :: sample_2d_thickness
    sample_2d_thickness = this%range(2) - this%range(1)
  end function sample_2d_thickness

```

```

<Multi MC int: sample 2D: TBP>+≡
  procedure :: analyse => sample_2d_analyse

```

```

<Multi MC int: procedures>+≡
  subroutine sample_2d_analyse (this, dir, file)
    class(sample_2d_t), intent(in) :: this
    character(*), intent(in) :: dir, file
    integer :: u
    real(default), dimension(1:2,0:100,0:100) :: grid
    integer, dimension(0:100,0:100) :: i_grid
    integer :: r, x, y
    integer, dimension(2,2) :: i
    call generate_unit (u)
    print *, "sample_2d_analyse: ", dir // "/" // file
    open (u, file=dir//"/"//file)
    do x = 0, 100
      do y = 0, 100
        grid(1:2,x,y) = [-one,-one]
      end do
    end do
    do r = 1, this%n_regions
      i = int(this%regions(r)%corners*1E2_default)
      do x = i(1,1), i(1,2)
        do y = i(2,1), i(2,2)
          i_grid(x,y) = this%regions(r)%n_hits
          grid(1,x,y) = one / this%regions(r)%area ()
          grid(2,x,y) = this%regions(r)%density ()
        end do
      end do
    end do
    do x = 0, 100
      do y = 0, 100
        write (u, *) x, y, i_grid(x,y), grid(1:2,x,y)
      end do
      write (u, *)
    end do
    close (u)
  end subroutine sample_2d_analyse

```

```

<Multi MC int: sample 2D: TBP>+≡
  procedure :: to_generator => sample_2d_to_generator

```

```

<Multi MC int: procedures>+≡
  subroutine sample_2d_to_generator (this)
    class(sample_2d_t), intent(inout) :: this
    integer :: region
    do region = 1, this%n_regions

```

```

        call this%regions(region)%to_generator ()
    end do
end subroutine sample_2d_to_generator

<Muli MC int: sample 2D: TBP>+≡
    procedure :: mean => sample_2d_mean

<Muli MC int: procedures>+≡
    elemental function sample_2d_mean (this, dim) result (mean)
        class(sample_2d_t), intent(in) :: this
        integer, intent(in) :: dim
        real(default) :: mean
        integer :: region, hit
        mean = zero
        do region = 1, this%n_regions
            do hit = 1, this%regions(region)%n_hits
                mean = mean + this%regions(region)%hyp_hits (dim, hit)
            end do
        end do
        mean = mean / this%n_hits
    end function sample_2d_mean

<Muli MC int: public>+≡
    public :: sample_3d_t

<Muli MC int: types>+≡
    type, extends (ser_class_t) :: sample_3d_t
        integer::n_slices=0
        integer::n_alloc=0
        type(sample_2d_t), dimension(:),allocatable::slices
    contains
        <Muli MC int: sample 3D: TBP>
    end type sample_3d_t

<Muli MC int: sample 3D: TBP>≡
    procedure :: write_to_marker => sample_3d_write_to_marker

<Muli MC int: procedures>+≡
    subroutine sample_3d_write_to_marker (this, marker, status)
        class(sample_3d_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        integer :: n
        call marker%mark_begin ("sample_3d_t")
        call marker%mark ("n_slices", this%n_slices)
        call marker%mark ("n_alloc", this%n_alloc)
        if (this%n_slices > 0) then
            call marker%mark_instance_begin &
                (this%slices(1), "slices", shape=shape(this%slices))
            do n = 1, this%n_slices
                call sample_2d_write_to_marker (this%slices(n), marker, status)
            end do
            call marker%mark_instance_end ()
        end if
    end subroutine

```



```

        call marker%mark_end ("sample_3d_t")
    end subroutine sample_3d_write_to_marker

<Muli MC int: sample 3D: TBP>+≡
    procedure :: read_from_marker => sample_3d_read_from_marker

<Muli MC int: procedures>+≡
    subroutine sample_3d_read_from_marker (this, marker, status)
        class(sample_3d_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        integer :: n
        call marker%pick_begin ("sample_3d_t", status=status)
        call marker%pick ("n_slices", this%n_slices, status)
        call marker%pick ("n_alloc", this%n_alloc, status)
        if (this%n_slices > 0) then
            call marker%pick_instance_begin ("slices", status=status)
            allocate(this%slices (this%n_slices))
            do n = 1, this%n_slices
                call sample_2d_read_from_marker (this%slices(n), marker, status)
            end do
            call marker%pick_instance_end (status)
        end if
        call marker%pick_end ("sample_3d_t", status)
    end subroutine sample_3d_read_from_marker

<Muli MC int: sample 3D: TBP>+≡
    procedure :: print_to_unit => sample_3d_print_to_unit

<Muli MC int: procedures>+≡
    subroutine sample_3d_print_to_unit (this, unit, parents, components, peers)
        class(sample_3d_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        integer :: n
        write (unit, "(1x,A)") "components of sample_3d_t"
        write (unit, "(3x,A,I10)") "n_slices: ", this%n_slices
        write (unit, "(3x,A,I10)") "n_alloc: ", this%n_alloc
        if (allocated (this%slices)) then
            if (components > 0) then
                do n = 1, this%n_slices
                    call this%slices(n)%print_to_unit (unit, parents, components-1, peers)
                end do
            else
                write (unit, "(3x,A)") "skipping slices."
            end if
        else
            write (unit, "(3x,A)") "slices are not allocated."
        end if
    end subroutine sample_3d_print_to_unit

<Muli MC int: sample 3D: TBP>+≡
    procedure, nopass :: get_type => sample_3d_get_type

```

```

<Muli MC int: procedures>+≡
  pure subroutine sample_3d_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="sample_3d_t")
  end subroutine sample_3d_get_type

<Muli MC int: sample 3D: TBP>+≡
  procedure :: measure => sample_3d_measure

<Muli MC int: procedures>+≡
  elemental function sample_3d_measure (this)
    real(default) :: sample_3d_measure
    class(sample_3d_t), intent(in) :: this
    sample_3d_measure = one
  end function sample_3d_measure

<Muli MC int: sample 3D: TBP>+≡
  procedure :: to_generator => sample_3d_to_generator

<Muli MC int: procedures>+≡
  subroutine sample_3d_to_generator(this)
    class(sample_3d_t), intent(inout)::this
    integer::slice
    do slice=1,this%n_slices
      call this%slices(slice)%to_generator()
    end do
  end subroutine sample_3d_to_generator

<Muli MC int: sample 3D: TBP>+≡
  generic :: initialize => sample_3d_initialize
  procedure :: sample_3d_initialize

<Muli MC int: procedures>+≡
  subroutine sample_3d_initialize (this, n_alloc)
    class(sample_3d_t), intent(out) :: this
    integer, intent(in) :: n_alloc
    if (allocated (this%slices)) deallocate (this%slices)
    if (n_alloc > 0) then
      allocate (this%slices (n_alloc))
      this%n_alloc = n_alloc
      this%n_slices = 1
      call this%slices(1)%initialize (n_alloc)
    else
      this%n_alloc = 0
    end if
  end subroutine sample_3d_initialize

<Muli MC int: sample 3D: TBP>+≡
  procedure :: sample_3d_generate_hit
  generic :: generate_hit => sample_3d_generate_hit

```

<Muli MC int: procedures>+≡

```

pure subroutine sample_3d_generate_hit &
  (this, rnd, pts2, boost, hit, region, slice)
  class(sample_3d_t), intent(in) :: this
  integer, intent(in), dimension(3) :: rnd
  real(default), intent(in) :: pts2
  integer, intent(out) :: slice, region
  real(default), dimension(3), intent(out) :: hit
  real(default), intent(out) :: boost
  if (this%n_slices == 0) then
    call muli_mcint_generate_hit (rnd, unit_square, hit(1:2))
    boost = 1._default
    slice = 1
    region = 1
  else
    do slice = 1, this%n_slices
      if (this%slices(slice)%contains (pts2)) exit
    end do
    call this%slices(slice)%generate_hit (rnd, boost, hit(1:2), region)
  end if
  hit(3) = pts2
end subroutine sample_3d_generate_hit

```

<Muli MC int: sample 3D: TBP>+≡

```

procedure :: sample_3d_confirm_hit
generic :: confirm_hit => sample_3d_confirm_hit

```

<Muli MC int: procedures>+≡

```

subroutine sample_3d_confirm_hit (this, hit, region, slice)
  class(sample_3d_t), intent(inout) :: this
  integer, intent(in) :: slice, region
  real(default), intent(in), dimension(3) :: hit
  type(sample_2d_t), allocatable :: old_slice
  integer :: n
  logical :: full
  if (this%n_alloc < slice) then
    print *, "sample_3d_confirm_hit: Slice ", slice, " not allocated."
  else
    ! if (.not. allocated (this%slices)) call this%initialize (2)
    call this%slices(slice)%confirm_hit (hit, region, full)
    if (full) then
      if (this%n_alloc == this%n_slices) call this%enlarge ()
      this%n_slices = this%n_slices + 1
      allocate (old_slice)
      call this%slices(slice)%move_components (old_slice)
      call sample_2d_split (old_slice, this%n_alloc, &
        old_slice%mean(3), this%slices(slice), &
        this%slices(this%n_slices))
    end if
  end if
end subroutine sample_3d_confirm_hit

```

<Muli MC int: sample 3D: TBP>+≡

```

procedure :: enlarge => sample_3d_enlarge

```

```

<Muli MC int: procedures>+≡
  subroutine sample_3d_enlarge (this)
    class(sample_3d_t), intent(inout) :: this
    type(sample_2d_t), allocatable, dimension(:) :: old_slices
    integer :: n
    print *, "sample_3d_enlarge"
    call move_alloc (this%slices, old_slices)
    this%n_alloc = this%n_alloc * 2
    allocate (this%slices (this%n_alloc))
    do n = 1, size(old_slices)
      call old_slices(n)%move_components(this%slices(n))
    end do
  end subroutine sample_3d_enlarge

<Muli MC int: public>+≡
  public :: sample_int_kind_t

<Muli MC int: types>+≡
  type, extends (sample_3d_t) :: sample_int_kind_t
    integer :: n_proc = 0
    integer(kind=i64) :: n_tries = 0
    integer :: n_hits = 0
    integer :: n_over = 0
    integer, dimension(:), allocatable :: hits, weights, processes
    real(default) :: overall_boost = 1E-1_default
  contains
    <Muli MC int: sample int: TBP>
  end type sample_int_kind_t

<Muli MC int: sample int: TBP>≡
  procedure :: write_to_marker => sample_int_kind_write_to_marker

<Muli MC int: procedures>+≡
  subroutine sample_int_kind_write_to_marker (this, marker, status)
    class(sample_int_kind_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    call marker%mark_begin ("sample_int_kind_t")
    call sample_3d_write_to_marker (this, marker, status)
    call marker%mark ("n_hits", this%n_hits)
    call marker%mark ("n_proc", this%n_proc)
    call marker%mark ("boost", this%overall_boost)
    if (this%n_hits > 0) then
      call marker%mark ("hits", this%hits)
    end if
    if (this%n_proc > 0) then
      call marker%mark ("processes", this%processes)
      call marker%mark ("weights", this%weights)
    end if
    call marker%mark_end ("sample_int_kind_t")
  end subroutine sample_int_kind_write_to_marker

<Muli MC int: sample int: TBP>+≡
  procedure :: read_from_marker => sample_int_kind_read_from_marker

```

<Muli MC int: procedures>+≡

```

subroutine sample_int_kind_read_from_marker (this, marker, status)
  class(sample_int_kind_t), intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  call marker%pick_begin ("sample_int_kind_t", status=status)
  call sample_3d_read_from_marker (this, marker, status)
  call marker%pick ("n_hits", this%n_hits, status)
  call marker%pick ("n_proc", this%n_proc, status)
  call marker%pick ("boost", this%overall_boost, status)
  if (this%n_hits > 0) then
    allocate (this%hits (this%n_hits))
    call marker%pick ("hits", this%hits, status)
  end if
  if (this%n_proc > 0) then
    allocate (this%processes (this%n_proc))
    call marker%pick ("processes", this%processes, status)
    allocate (this%weights (this%n_proc))
    call marker%pick ("weights", this%weights, status)
  end if
  call marker%pick_end ("sample_int_kind_t", status)
end subroutine sample_int_kind_read_from_marker

```

<Muli MC int: sample int: TBP>+≡

```

procedure :: print_to_unit => sample_int_kind_print_to_unit

```

<Muli MC int: procedures>+≡

```

subroutine sample_int_kind_print_to_unit (this, unit, parents, components, peers)
  class(sample_int_kind_t), intent(in) :: this
  integer, intent(in) :: unit
  integer(dik), intent(in) :: parents, components, peers
  integer :: n
  if (parents > 0) call sample_3d_print_to_unit &
    (this, unit, parents, components, peers)
  write (unit, "(1x,A)") "components of sample_int_kind_t"
  write (unit, "(3x,A,I10)") "n_hits: ", this%n_hits
  write (unit, "(3x,A,I10)") "n_proc: ", this%n_proc
  write (unit, "(3x,A,E14.7)") "overall_boost: ", this%overall_boost
  write (unit, "(3x,A)") "hits:"
  write (unit, "(3x,10(I0,1x))") this%hits(1:this%n_hits)
  write (unit, "(3x,A)") "weights:"
  write (unit, "(3x,10(I0,1x))") this%weights
  write (unit, "(3x,A)") "processes:"
  write (unit, "(3x,2(I0,1x))") this%processes
end subroutine sample_int_kind_print_to_unit

```

<Muli MC int: sample int: TBP>+≡

```

procedure, nopass :: get_type => sample_int_kind_get_type

```

<Muli MC int: procedures>+≡

```

pure subroutine sample_int_kind_get_type (type)
  character(:),allocatable, intent(out) :: type
  allocate (type, source="sample_int_kind_t")

```

```

end subroutine sample_int_kind_get_type

<Muli MC int: sample int: TBP>+≡
  procedure :: to_generator => sample_int_kind_to_generator

<Muli MC int: procedures>+≡
  subroutine sample_int_kind_to_generator(this)
    class(sample_int_kind_t), intent(inout)::this
    integer::int_kind
    if (allocated(this%hits))deallocate(this%hits)
    call sample_3d_to_generator(this)
  end subroutine sample_int_kind_to_generator

<Muli MC int: sample int: TBP>+≡
  procedure :: process_id => sample_int_kind_process_id

<Muli MC int: procedures>+≡
  elemental integer function sample_int_kind_process_id (this, subprocess)
    class(sample_int_kind_t), intent(in) :: this
    integer, intent(in) :: subprocess
    sample_int_kind_process_id = this%processes(subprocess)
  end function sample_int_kind_process_id

<Muli MC int: sample int: TBP>+≡
  procedure :: sample_int_kind_initialize
  generic :: initialize => sample_int_kind_initialize

<Muli MC int: procedures>+≡
  subroutine sample_int_kind_initialize (this, n_alloc, processes, overall_boost)
    class(sample_int_kind_t), intent(out) :: this
    integer, intent(in) :: n_alloc
    integer, intent(in), dimension(:) :: processes
    real(default), optional, intent(in) :: overall_boost
    integer :: s, n
    s = size(processes)
    call sample_3d_initialize (this, n_alloc)
    if (allocated (this%hits)) deallocate (this%hits)
    allocate (this%hits (n_alloc))
    if (allocated (this%weights)) deallocate (this%weights)
    allocate (this%weights(s))
    if (allocated (this%processes)) deallocate (this%processes)
    allocate (this%processes(s), source=processes)
    do n = 1, s
      this%weights(n) = 0
    end do
    this%n_alloc = n_alloc
    this%n_hits = 0
    this%n_proc = s
    if (present (overall_boost)) this%overall_boost = overall_boost
    this%overall_boost = this%overall_boost * this%n_proc
    ! print *, this%weights
  end subroutine sample_int_kind_initialize

```

<Muli MC int: sample int: TBP>+≡

```
procedure :: sample_int_kind_generate_hit
```

<Muli MC int: procedures>+≡

```
pure subroutine sample_int_kind_generate_hit &
  (this, rnd, pts2, boost, hit, region, slice, subprocess)
  class(sample_int_kind_t), intent(in) :: this
  integer, dimension(4), intent(in) :: rnd
  real(default), intent(in) :: pts2
  real(default), dimension(3), intent(out) :: hit
  integer, intent(out) :: region, slice, subprocess
  real(default), intent(out) :: boost
  integer :: n_n
  ! print *, rnd, pts2, boost, hit, region, slice, subprocess
  call sample_3d_generate_hit &
    (this, rnd(2:4), pts2, boost, hit, region, slice)
  n_n = modulo(rnd(1), this%n_hits + size(this%weights)) + 1
  if (n_n > this%n_hits) then
    subprocess = n_n - this%n_hits
  else
    subprocess = this%hits(n_n)
  end if
  boost = boost * this%overall_boost * (this%n_proc + this%n_hits) / &
    (this%n_proc * (this%weights(subprocess) + 1))
end subroutine sample_int_kind_generate_hit
```

<Muli MC int: sample int: TBP>+≡

```
procedure :: mcgenerate_hit => sample_int_kind_mcgenerate_hit
generic :: generate_hit => sample_int_kind_generate_hit
```

<Muli MC int: procedures>+≡

```
subroutine sample_int_kind_mcgenerate_hit (this, pts2, mean, &
  integrand_kind, tao_rnd, process_id, cart_hit)
  class(sample_int_kind_t), intent(inout) :: this
  integer, intent(in) :: integrand_kind
  real(default), intent(in) :: pts2, mean
  type(tao_random_state), intent(inout) :: tao_rnd
  real(default), dimension(3), intent(out) :: cart_hit
  integer, intent(out) :: process_id
  real(default) :: boost
  integer :: region, slice, subprocess
  integer, dimension(4) :: i_rnd
  real(default) :: dddsigma, d_rnd
  real(default), dimension(3) :: hyp_hit
  MC: do
    this%n_tries = this%n_tries + 1
    call tao_random_number (tao_rnd, i_rnd)
    call tao_random_number (tao_rnd, d_rnd)
    ! print *, pts2, mean, integrand_kind, process_id, cart_hit
    call this%generate_hit (i_rnd, pts2, boost, hyp_hit, region, &
      slice, subprocess)
    process_id = this%process_id(subprocess)
    call interactions_dddsigma_reg (process_id, integrand_kind, &
      hyp_hit, cart_hit, dddsigma)
    dddsigma = dddsigma * boost
  end do
```

```

        if (d_rnd*mean < dddsigma) then
            exit MC
        end if
    end do MC
    if (mean < dddsigma) then
        call this%confirm_hit (hyp_hit, region, slice, subprocess, .true.)
    else
        call this%confirm_hit (hyp_hit, region, slice, subprocess, .false.)
    end if
end subroutine sample_int_kind_mcgenerate_hit

```

(Multi MC int: sample int: TBP)+≡

```

procedure :: sample_int_kind_confirm_hit
generic :: confirm_hit => sample_int_kind_confirm_hit

```

(Multi MC int: procedures)+≡

```

subroutine sample_int_kind_confirm_hit &
    (this, hit, region, slice, subprocess, over)
class(sample_int_kind_t), intent(inout) :: this
real(default), dimension(3), intent(in) :: hit
integer, intent(in) :: region, slice, subprocess
integer, dimension(:), allocatable :: tmp_hits
logical, optional, intent(in) :: over
this%n_hits = this%n_hits + 1
if (present(over)) then
    if (over) then
        this%n_over = this%n_over + 1
        this%overall_boost = this%overall_boost / 1.1_default
    else
        this%overall_boost = this%overall_boost * 1.0001_default
    end if
end if
if (0 < size(this%hits)) then
    if (this%n_hits > size(this%hits)) then
        call move_alloc (this%hits, tmp_hits)
        allocate (this%hits (2*size(tmp_hits)))
        this%hits (1:size(tmp_hits)) = tmp_hits
    end if
    this%hits(this%n_hits) = subprocess
end if
this%weights(subprocess) = this%weights(subprocess) + 1
call sample_3d_confirm_hit (this, hit, region, slice)
end subroutine sample_int_kind_confirm_hit

```

(Multi MC int: sample int: TBP)+≡

```

procedure :: analyse => sample_int_kind_analyse

```

(Multi MC int: procedures)+≡

```

subroutine sample_int_kind_analyse (this, dir, prefix)
class(sample_int_kind_t), intent(in) :: this
character(*), intent(in) :: dir, prefix
integer :: slices_unit, subprocs_unit
integer :: n, slice
character(3) :: slice_name

```



```

integer, dimension(:), allocatable :: int_a
real(default), dimension(:), allocatable :: real_a
call generate_unit (slices_unit)
print *, "sample_int_kind_analyse: ", dir // "/" // prefix // &
      "slice_distribution.plot"
open (slices_unit, file=dir // "/" // prefix // "slice_distribution.plot")
call generate_unit (subprocs_unit)
print *, "sample_int_kind_analyse: ", dir // "/" // prefix // &
      "subproc_distribution.plot"
open (subprocs_unit, file=dir // "/" // prefix // &
      "subproc_distribution.plot")
allocate (real_a (this%n_slices))
allocate (int_a (this%n_slices))
do n = 1, this%n_slices
  real_a(n) = this%slices(n)%range(1)
end do
call misc_sort (real_a, int_a)
do n = 1, size (this%weights)
  if (this%n_hits > 0) then
    write (subprocs_unit, fmt=*) real(this%weights(n)), &
      real(this%weights(n)+1) / this%n_hits
  else
    write (subprocs_unit, fmt=*) 0, 0
  end if
end do
do n = 1, this%n_slices
  slice = int_a (n)
  call integer_with_leading_zeros (n, 3, slice_name)
  call sample_2d_analyse (this%slices(slice), dir, prefix // &
    slice_name // ".plot")
  print *, this%n_hits, this%slices(slice)%range(2) - &
    this%slices(slice)%range(1)
  if (this%n_hits > 0) then
    write (slices_unit, *) this%slices(slice)%range(1), &
      this%slices(slice)%range(2), this%slices(slice)%n_hits, &
      real (this%slices(slice)%n_hits) / (this%n_hits * &
        (this%slices(slice)%range(2) - this%slices(slice)%range(1)))
  else
    write (slices_unit, *) this%slices(slice)%range(1), &
      this%slices(slice)%range(2), this%slices(slice)%n_hits, zero
  end if
end do
write (slices_unit, *) one, zero, zero, zero
close (slices_unit)
close (subprocs_unit)
end subroutine sample_int_kind_analyse

```

<Multi MC int: public>+≡
 public :: sample_inclusive_t

<Multi MC int: types>+≡
 type, extends (ser_class_t) :: sample_inclusive_t
 integer :: n_alloc = 0
 integer(kind=i64) :: n_tries_sum = i_zero

```

        integer(kind=i64) :: n_over_sum = i_zero
        integer(kind=i64) :: n_hits_sum = i_zero
        type(sample_int_kind_t), dimension(:), allocatable :: int_kinds
contains
    <Muli MC int: sample inclusive: TBP>
end type sample_inclusive_t

<Muli MC int: sample inclusive: TBP>≡
    procedure :: write_to_marker => sample_inclusive_write_to_marker
<Muli MC int: procedures>+≡
    subroutine sample_inclusive_write_to_marker (this, marker, status)
        class(sample_inclusive_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        integer :: n
        call marker%mark_begin ("sample_inclusive_t")
        call marker%mark ("n_alloc", this%n_alloc)
        if (allocated (this%int_kinds)) then
            call marker%mark_begin (tag="int_kinds", shape=shape(this%int_kinds))
            do n = 1, size(this%int_kinds)
                call this%int_kinds(n)%write_to_marker (marker, status)
            end do
            call marker%mark_instance_end ()
        else
            call marker%mark_empty (tag="int_kinds", shape=[0])
        end if
        call marker%mark_end ("sample_inclusive_t")
    end subroutine sample_inclusive_write_to_marker

    <Muli MC int: sample inclusive: TBP>+≡
        procedure :: read_from_marker => sample_inclusive_read_from_marker
    <Muli MC int: procedures>+≡
        subroutine sample_inclusive_read_from_marker (this, marker, status)
            class(sample_inclusive_t), intent(out) :: this
            class(marker_t), intent(inout) :: marker
            integer(dik), intent(out) :: status
            integer :: n
            integer, dimension(:), allocatable :: s
            call marker%pick_begin ("sample_inclusive_t", status=status)
            call marker%pick ("n_alloc", this%n_alloc, status)
            call marker%pick_begin ("int_kinds", shape=s, status=status)
            if (s(1) > 0) then
                do n = 1, size(this%int_kinds)
                    call this%int_kinds(n)%read_from_marker (marker, status)
                end do
                call marker%pick_end ("int_kinds",status)
            end if
            call marker%pick_end ("sample_inclusive_t", status)
        end subroutine sample_inclusive_read_from_marker

    <Muli MC int: sample inclusive: TBP>+≡
        procedure :: print_to_unit => sample_inclusive_print_to_unit

```

<Muli MC int: procedures>+≡

```

subroutine sample_inclusive_print_to_unit (this, unit, parents, components, peers)
  class(sample_inclusive_t), intent(in) :: this
  integer, intent(in) :: unit
  integer(dik), intent(in) :: parents, components, peers
  integer :: n
  write (unit, "(1x,A)") "components of sample_inclusive_t"
  write (unit, "(3x,A,I10)") "n_alloc:          ", this%n_alloc
  if (allocated (this%int_kinds)) then
    if (components > 0) then
      write (unit, "(3x,A)") "int_kinds:"
      do n = 1, this%n_alloc
        call this%int_kinds(n)%print_to_unit &
          (unit, parents, components-1, peers)
      end do
    else
      write (unit, "(3x,A)") "skipping int_kinds."
    end if
  else
    write (unit, "(3x,A)") "int_kinds are not allocated."
  end if
end subroutine sample_inclusive_print_to_unit

```

<Muli MC int: sample inclusive: TBP>+≡

```

procedure, nopass :: get_type => sample_inclusive_get_type

```

<Muli MC int: procedures>+≡

```

pure subroutine sample_inclusive_get_type (type)
  character(:), allocatable, intent(out) :: type
  allocate (type, source = "sample_inclusive_t")
end subroutine sample_inclusive_get_type

```

<Muli MC int: sample inclusive: TBP>+≡

```

procedure :: process_id => sample_inclusive_process_id

```

<Muli MC int: procedures>+≡

```

elemental integer function sample_inclusive_process_id &
  (this, subprocess, int_kind)
  class(sample_inclusive_t), intent(in) :: this
  integer, intent(in) :: subprocess, int_kind
  sample_inclusive_process_id = &
    this%int_kinds(int_kind)%processes (subprocess)
end function sample_inclusive_process_id

```

<Muli MC int: sample inclusive: TBP>+≡

```

procedure :: initialize => sample_inclusive_initialize

```

<Muli MC int: procedures>+≡

```

subroutine sample_inclusive_initialize &
  (this, n_alloc, sizes, processes, overall_boost)
  class(sample_inclusive_t), intent(out) :: this
  integer, intent(in) :: n_alloc
  integer, dimension(:), intent(in) :: sizes, processes
  real(default), optional, intent(in) :: overall_boost

```

```

integer :: n, sum
this%n_tries_sum = i_zero
this%n_over_sum = 0
this%n_alloc = size(sizes)
if (allocated(this%int_kinds)) deallocate (this%int_kinds)
allocate (this%int_kinds (this%n_alloc))
sum = 0
do n = 1, this%n_alloc
    call this%int_kinds(n)%initialize (n_alloc, &
        processes(sum+1:sum+sizes(n)), overall_boost)
    sum = sum + sizes(n)
end do
end subroutine sample_inclusive_initialize

```

<Multi MC int: sample inclusive: TBP>+≡
 procedure :: finalize => sample_inclusive_finalize

<Multi MC int: procedures>+≡
 subroutine sample_inclusive_finalize (this)
 class(sample_inclusive_t), intent(inout) :: this
 deallocate (this%int_kinds)
 this%n_alloc = 0
 end subroutine sample_inclusive_finalize

<Multi MC int: sample inclusive: TBP>+≡
 procedure :: generate_hit => sample_inclusive_generate_hit

<Multi MC int: procedures>+≡
 pure subroutine sample_inclusive_generate_hit &
 (this, rnd, pts2, int_kind, hit, region, boost, slice, process)
 class(sample_inclusive_t), intent(in) :: this
 integer, dimension(4), intent(in) :: rnd
 real(default), intent(in) :: pts2
 integer, intent(in) :: int_kind
 real(default), dimension(3), intent(out) :: hit
 integer, intent(out) :: region, slice, process
 real(default), intent(out) :: boost
 call this%int_kinds(int_kind)%generate_hit &
 (rnd, pts2, boost, hit, region, slice, process)
 end subroutine sample_inclusive_generate_hit

<Multi MC int: sample inclusive: TBP>+≡
 procedure :: mcgenerate_hit => sample_inclusive_mcgenerate_hit

<Multi MC int: procedures>+≡
 subroutine sample_inclusive_mcgenerate_hit &
 (this, pts2, mean, integrand_kind, tao_rnd, process_id, cart_hit)
 class(sample_inclusive_t), intent(inout) :: this
 real(default), intent(in) :: pts2, mean
 integer, intent(in) :: integrand_kind
 type(tao_random_state), intent(inout) :: tao_rnd
 real(default), dimension(3), intent(out) :: cart_hit
 integer, intent(out) :: process_id
 ! print *, "sample_inclusive_mcgenerate_hit &

```

! (this,"pts2,mean,integrand_kind,process_id,cart_hit,")"
! print *, allocated (this%int_kinds)
call sample_int_kind_mcgenerate_hit (this%int_kinds(integrand_kind), &
    pts2, mean, integrand_kind, tao_rnd, process_id, cart_hit)
end subroutine sample_inclusive_mcgenerate_hit

<Muli MC int: sample inclusive: TBP>+≡
procedure :: confirm_hit => sample_inclusive_confirm_hit

<Muli MC int: procedures>+≡
subroutine sample_inclusive_confirm_hit &
    (this, hit, int_kind, region, slice, process, over)
class(sample_inclusive_t), intent(inout) :: this
real(default), dimension(3), intent(in) :: hit
integer, intent(in) :: int_kind, region, slice, process
logical, optional, intent(in) :: over
call this%int_kinds(int_kind)%confirm_hit &
    (hit, region, slice, process, over)
end subroutine sample_inclusive_confirm_hit

<Muli MC int: sample inclusive: TBP>+≡
procedure :: sum_up => sample_inclusive_sum_up

<Muli MC int: procedures>+≡
subroutine sample_inclusive_sum_up (this)
class(sample_inclusive_t), intent(inout) :: this
integer :: n
this%n_tries_sum = i_zero
this%n_hits_sum = i_zero
this%n_over_sum = i_zero
do n = 1, this%n_alloc
    this%n_tries_sum = this%n_tries_sum+this%int_kinds(n)%n_tries
    this%n_hits_sum = this%n_hits_sum+this%int_kinds(n)%n_hits
    this%n_over_sum = this%n_over_sum+this%int_kinds(n)%n_over
end do
end subroutine sample_inclusive_sum_up

<Muli MC int: sample inclusive: TBP>+≡
procedure :: analyse => sample_inclusive_analyse

<Muli MC int: procedures>+≡
subroutine sample_inclusive_analyse (this, dir, subdirs)
class(sample_inclusive_t), intent(in) :: this
character(*), intent(in) :: dir
logical, intent(in) :: subdirs
integer :: inclusive_unit
integer :: n, n_hits
character(2) :: sample_name
call generate_unit (inclusive_unit)
open (inclusive_unit, file = dir // "/int_kinds.plot")
n_hits = 0
do n = 1, size(this%int_kinds)
    n_hits = n_hits + this%int_kinds(n)%n_hits
end do

```

```

do n = 1, size(this%int_kinds)
  write (inclusive_unit, *) n, real(this%int_kinds(n)%n_hits) / n_hits
  call integer_with_leading_zeros (n, 2, sample_name)
  if (subdirs) then
    call sample_int_kind_analyse (this%int_kinds(n), &
      dir // "/" // sample_name, "")
  else
    call sample_int_kind_analyse (this%int_kinds(n), &
      dir, sample_name // "-")
  end if
end do
close (inclusive_unit)
end subroutine sample_inclusive_analyse

```

<Muli MC int: sample inclusive: TBP>+≡
 procedure :: to_generator => sample_inclusive_to_generator

<Muli MC int: procedures>+≡
 subroutine sample_inclusive_to_generator (this)
 class(sample_inclusive_t), intent(inout) :: this
 integer :: int_kind
 do int_kind = 1, size(this%int_kinds)
 call this%int_kinds(int_kind)%to_generator ()
 end do
end subroutine sample_inclusive_to_generator

<Muli MC int: sample inclusive: TBP>+≡
 procedure :: allocate => sample_inclusive_allocate

<Muli MC int: procedures>+≡
 subroutine sample_inclusive_allocate (this, n_alloc)
 class(sample_inclusive_t), intent(out) :: this
 integer, intent(in) :: n_alloc
 allocate (this%int_kinds (n_alloc))
 this%n_alloc = n_alloc
end subroutine sample_inclusive_allocate

<Muli MC int: procedures>+≡
 pure subroutine multi_mcint_generate_hit (rnd, corners, hit)
 real(default), dimension(2), intent(out) :: hit
 integer, intent(in), dimension(2) :: rnd
 real(default), dimension(2,2), intent(in) :: corners
 ! print *, hit
 ! print *, corners
 ! print *, (corners(1:2,2) - corners(1:2,1))
 hit = (rnd / max_d) * (corners(1:2,2) - corners(1:2,1)) + corners(1:2,1)
end subroutine multi_mcint_generate_hit

<Muli MC int: procedures>+≡
 subroutine plot_pstvue3d (unit, corners, density)
 integer, intent(in) :: unit
 real(default), dimension(2,2), intent(in) :: corners
 real(default), intent(in) :: density


```

<Multi MC int: procedures>+≡
recursive subroutine misc_sort (in, out)
  real(default), dimension(:), intent(in) :: in
  integer, dimension(:), intent(out) :: out
  integer, dimension(:), allocatable :: tmp
  integer :: n, k, l, cut
  if (size(in) == 1) then
    out = [1]
  else
    if (size(in) == 2) then
      if (in(1) <= in(2)) then
        out = [1,2]
      else
        out = [2,1]
      end if
    else
      cut = size(in) / 2
      k = 1
      l = cut + 1
      allocate (tmp (size(in)))
      call misc_sort (in(1:cut), tmp(1:cut))
      call misc_sort (in(cut+1:), tmp(cut+1:))
      do n = cut + 1, size(in)
        tmp(n) = tmp(n) + cut
      end do
      do n = 1, size(in)
        if (k > cut) then
          out(n) = tmp(l)
          l = l + 1
        else
          if (l > size(tmp)) then
            out(n) = tmp(k)
            k = k + 1
          else
            if (in(tmp(k)) < in(tmp(l))) then
              out(n) = tmp(k)
              k = k + 1
            else
              out(n) = tmp(l)
              l = l + 1
            end if
          end if
        end if
      end do
    end if
  end if
end subroutine misc_sort

```

21.10 Proton remnants

This file contains the module `muli_remnant`. All bookkeeping of the proton remnants and twin quarks is done here. Furthermore, reweighting of the PDFs

to derive remnant PDFs is done here.

```

<multi_remnant.f90>≡
  <File header>

  module multi_remnant
    use, intrinsic :: iso_fortran_env
    <Use kinds with double>
    <Use strings>
    use string_utils
    use constants
    use diagnostics
    use pdf_builtin !NODEP!
    use tao_random_numbers !NODEP!
    use multi_base
    use multi_interactions
    use multi_momentum
    ! use sf_lhapdf !NODEP!

    <Standard module head>

    <Multi remnant: variables>

    <Multi remnant: public>

    <Multi remnant: types>

    <Multi remnant: interfaces>

    contains

    <Multi remnant: procedures>

  end module multi_remnant

  <Multi remnant: public>≡
    public :: pdfnorm_t

  <Multi remnant: types>≡
    type, extends (ser_class_t) :: pdfnorm_t
      real(default) :: qmin, qmax, dq
      real(default), dimension(-6:6, 0:nq) :: pdf_int
      real(default), dimension(0:4, 0:nq) :: pdf_norm
    contains
      <Multi remnant: pdfnorm: TBP>
    end type pdfnorm_t

  <Multi remnant: pdfnorm: TBP>≡
    procedure :: write_to_marker => pdfnorm_write_to_marker

  <Multi remnant: procedures>≡
    subroutine pdfnorm_write_to_marker (this, marker, status)
      class(pdfnorm_t), intent(in) :: this
      class(marker_t), intent(inout) :: marker
      integer(dik), intent(out) :: status

```

```

    call marker%mark_begin ("pdfnorm_t")
    call marker%mark ("qmin", this%qmin)
    call marker%mark ("qmax", this%qmax)
    call marker%mark ("dq", this%dq)
    call marker%mark ("pdf_int", this%pdf_int)
    call marker%mark ("pdf_norm", this%pdf_norm)
    call marker%mark_end ("pdfnorm_t")
end subroutine pdfnorm_write_to_marker

```

(Muli remnant: pdfnorm: TBP)+≡

```

procedure :: read_from_marker => pdfnorm_read_from_marker

```

(Muli remnant: procedures)+≡

```

subroutine pdfnorm_read_from_marker (this, marker, status)
  class(pdfnorm_t), intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  character(:), allocatable :: name
  call marker%pick_begin ("pdfnorm_t", status=status)
  call marker%pick ("qmin", this%qmin, status)
  call marker%pick ("qmax", this%qmax, status)
  call marker%pick ("dq", this%dq, status)
  call marker%pick ("pdf_int", this%pdf_int, status)
  call marker%pick ("pdf_norm", this%pdf_norm, status)
  call marker%pick_end ("pdfnorm_t", status=status)
end subroutine pdfnorm_read_from_marker

```

(Muli remnant: pdfnorm: TBP)+≡

```

procedure :: print_to_unit => pdfnorm_print_to_unit

```

(Muli remnant: procedures)+≡

```

recursive subroutine pdfnorm_print_to_unit &
  (this, unit, parents, components, peers)
  class(pdfnorm_t), intent(in) :: this
  integer, intent(in) :: unit
  integer(dik), intent(in) :: parents, components, peers
  write (unit, "(1x,A)") "Components of pdfnorm_t:"
  write (unit, "(3x,A,F7.6)") "qmin: ", this%qmin
  write (unit, "(3x,A,F7.6)") "qmax: ", this%qmax
  write (unit, "(3x,A,F7.6)") "dq: ", this%dq
  if (components > 0) then
    write(unit, "(3x,A,13(F8.6,1x))") "pdf_int: ", this%pdf_int
    write(unit, "(3x,A,5(F8.6,1x))") "pdf_norm: ", this%pdf_norm
  else
    write(unit, "(3x,A)") "Skipping pdf_int"
    write(unit, "(3x,A)") "Skipping pdf_norm"
  end if
end subroutine pdfnorm_print_to_unit

```

(Muli remnant: procedures)+≡

(Muli remnant: pdfnorm: TBP)+≡

```

procedure, nopass :: get_type => pdfnorm_get_type

```

```

<Muli remnant: procedures>+≡
  pure subroutine pdfnorm_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="pdfnorm_t")
  end subroutine pdfnorm_get_type

<Muli remnant: pdfnorm: TBP>+≡
  procedure, nopass :: verify_type => pdfnorm_verify_type

<Muli remnant: procedures>+≡
  elemental logical function pdfnorm_verify_type (type) result (match)
    character(*), intent(in) :: type
    match = type == "pdfnorm_t"
  end function pdfnorm_verify_type

<Muli remnant: pdfnorm: TBP>+≡
  procedure :: scan => pdfnorm_scan

<Muli remnant: procedures>+≡
  subroutine pdfnorm_scan (this)
    class(pdfnorm_t), intent(out) :: this
    integer :: ix, iq
    real(double) :: xmin, xmax, dx
    real(double) :: q, q2min, q2max
    real(double), dimension(-6:6) :: f
    real(double), dimension(0:2) :: x
    call getxmin (0, xmin)
    call getxmax (0, xmax)
    call getq2min (0, q2min)
    call getq2max (0, q2max)
    this%qmin = sqrt(sqrt(q2min))
    this%qmax = sqrt(sqrt(q2max))
    this%dq = (this%qmax - this%qmin) / nq
    xmin = sqrt(xmin)
    xmax = sqrt(xmax)
    dx = (xmax - xmin) / nx
    do iq = 0, nq
      print *, "iq=", iq, "/", nq
      q = (this%qmin + iq * this%dq)**2
      x(0) = xmin**2
      x(1) = (xmin+dx)**2
      call evolvePDF (x(0), q, f)
      f(1) = f(1) - f(-1)
      f(2) = f(2) - f(-2)
      this%pdf_int(:,iq) = (x(1) - x(0)) * f
      do ix = 2, nx
        x(2) = (xmin + ix*dx)**2
        call evolvePDF (x(1), q, f)
        f(1) = f(1) - f(-1)
        f(2) = f(2) - f(-2)
        this%pdf_int(:,iq) = this%pdf_int(:,iq) + f*(x(2) - x(0))
        x(0) = x(1)
        x(1) = x(2)
      end do
    end do
  end subroutine pdfnorm_scan

```

```

call evolvePDF (x(1), q, f)
f(1) = f(1) - f(-1)
f(2) = f(2) - f(-2)
this%pdf_int(:,iq) = (this%pdf_int(:,iq) + f*(x(1)-x(0))) / two
this%pdf_norm(4,iq) = this%pdf_int(2,iq)
this%pdf_norm(3,iq) = this%pdf_int(1,iq)
this%pdf_int(2,iq) = this%pdf_int(2,iq) + this%pdf_int(-2,iq)
this%pdf_int(1,iq) = this%pdf_int(1,iq) + this%pdf_int(-1,iq)
this%pdf_norm(1,iq) = this%pdf_int(0,iq)
this%pdf_norm(2,iq) = sum (this%pdf_int(-6:-1,iq)) + &
    sum(this%pdf_int(-2:-1,iq)) + sum(this%pdf_int(3:6,iq))
this%pdf_norm(0,iq) = sum(this%pdf_int(:,iq))
this%pdf_norm(1,iq) = this%pdf_norm(1,iq) / this%pdf_norm(0,iq)
this%pdf_norm(2,iq) = this%pdf_norm(2,iq) / this%pdf_norm(0,iq)
this%pdf_norm(3,iq) = this%pdf_norm(3,iq) / this%pdf_norm(0,iq)
this%pdf_norm(4,iq) = this%pdf_norm(4,iq) / this%pdf_norm(0,iq)
! print *, this%pdf_norm(0,iq) - one
end do
end subroutine pdfnorm_scan

```

(Multi remnant: pdfnorm: TBP)+≡

```
procedure :: get_norm => pdfnorm_get_norm
```

(Multi remnant: procedures)+≡

```

subroutine pdfnorm_get_norm (this, gev_q, dim, kind, norm)
class(pdfnorm_t), intent(in) :: this
real(default), intent(in) :: gev_q
integer, intent(in) :: dim, kind
real(default), intent(out)::norm
integer :: iq
real(default) :: x,q , z0, z1, z2, z3, z4
norm = -one
q = sqrt(gev_q) - this%qmin
iq = floor(q / this%dq)
x = q / this%dq - iq
if (iq < 0) then
    print *, "pdfnorm_getnorm: q < q_min ", gev_q, this%qmin**2
    norm = this%pdf_norm (kind, 0)
else
    if (iq >= nq) then
        print *, "pdfnorm_getnorm: q >= q_max ", gev_q, this%qmax**2
        norm = this%pdf_norm (kind, nq)
    else
        select case (dim)
        case (0)
            norm = this%pdf_norm (kind, iq)
        case (1)
            norm = this%pdf_norm(kind,iq) * (one - x) + &
                this%pdf_norm(kind,iq+1) * x
        case (2)
            x = x + mod(iq,2)
            iq = iq - mod(iq,2)
            z0 = this%pdf_norm(kind, iq)
            z1 = this%pdf_norm(kind, iq+1)

```

```

        z2 = this%pdf_norm(kind, iq+2)
        norm = ((z0 - 2D0*z1 + z2) * x - (three*z0 - four*z1 + z2)) * &
            x / two + z0
    case (3)
        x = x + mod(iq,3)
        iq = iq - mod(iq,3)
        z0 = this%pdf_norm(kind, iq)
        z1 = this%pdf_norm(kind, iq+1)
        z2 = this%pdf_norm(kind, iq+2)
        z3 = this%pdf_norm(kind, iq+3)
        norm = (((- (z0 - 3*z1 + 3*z2 - z3) * x + 3 * (2*z0 - &
            5*z1 + 4*z2 - z3))*x - (11*z0 - 18*z1 + 9*z2 - 2*z3)) * &
            x / 6._default + z0
    case (4)
        x = x + mod(iq,4)
        iq = iq - mod(iq,4)
        z0 = this%pdf_norm(kind, iq)
        z1 = this%pdf_norm(kind, iq+1)
        z2 = this%pdf_norm(kind, iq+2)
        z3 = this%pdf_norm(kind, iq+3)
        z4 = this%pdf_norm(kind, iq+4)
        norm = (((((z0 - 4*z1 + 6*z2 - 4*z3 + z4) * x &
            -2 * (5*z0 - 18*z1 + 24*z2 - 14*z3 + 3*z4)) * x &
            + (35*z0 - 104*z1 + 114*z2 - 56*z3 + 11*z4)) * x &
            -2 * (25*z0 - 48*z1 + 36*z2 - 16*z3 + 3*z4)) * x) / &
            24._default + z0
    case default
        norm = this%pdf_norm(kind, iq) * (one - x) + &
            this%pdf_norm(kind, iq+1) * x
    end select
    ! print *, iq, x, norm
end if
end if
end subroutine pdfnorm_get_norm

```

```

<Muli remnant: variables>≡
    integer, parameter :: nx = 10000000
<Muli remnant: variables>+≡
    integer, parameter :: nq = 60
<Muli remnant: public>+≡
    public :: remnant_weight_model
<Muli remnant: variables>+≡
    integer :: remnant_weight_model = 2
<Muli remnant: variables>+≡
    integer :: gluon_exp = 4

<Muli remnant: public>+≡
    public :: muli_parton_t
<Muli remnant: types>+≡
    type, extends (ser_class_t) :: muli_parton_t
    private

```

```

integer :: id = -1
integer :: lha_flavor
real(default) :: momentum = -1
class(muli_parton_t), pointer :: twin => null()
class(muli_parton_t), pointer :: next => null()
contains
  <Muli remnant: muli parton: TBP>
end type muli_parton_t

<Muli remnant: muli parton: TBP>≡
  procedure :: write_to_marker => parton_write_to_marker

<Muli remnant: procedures>+≡
  subroutine parton_write_to_marker (this, marker, status)
    class(muli_parton_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    call marker%mark_begin ("muli_parton_t")
    call marker%mark ("id", this%id)
    call marker%mark ("lha", this%lha_flavor)
    call marker%mark ("momentum", this%momentum)
    call marker%mark_end ("muli_parton_t")
  end subroutine parton_write_to_marker

  <Muli remnant: muli parton: TBP>+≡
    procedure :: read_from_marker => parton_read_from_marker

  <Muli remnant: procedures>+≡
    subroutine parton_read_from_marker (this, marker, status)
      class(muli_parton_t), intent(out) :: this
      class(marker_t), intent(inout) :: marker
      integer(dik), intent(out) :: status
      character(:), allocatable :: name
      call marker%pick_begin ("muli_parton_t", status=status)
      call marker%pick ("id", this%id, status)
      call marker%pick ("lha", this%lha_flavor, status)
      call marker%pick ("momentum", this%momentum, status)
      call marker%pick_end ("muli_parton_t", status=status)
    end subroutine parton_read_from_marker

    <Muli remnant: muli parton: TBP>+≡
      procedure :: print_to_unit => parton_print_to_unit

    <Muli remnant: procedures>+≡
      recursive subroutine parton_print_to_unit &
        (this, unit, parents, components, peers)
        class(muli_parton_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        class(ser_class_t), pointer :: ser
        write (unit, "(1x,A)") "Components of muli_parton_t:"
        write (unit, "(3x,A,I7)") "id: ", this%id
        write (unit, "(3x,A,I7)") "lha flavor: ", this%lha_flavor
        write (unit, "(3x,A,F7.6)") "momentum: ", this%momentum

```

```

ser => this%next
call serialize_print_peer_pointer &
    (ser, unit, parents, components, peers-i_one, "next")
ser => this%twin
call serialize_print_comp_pointer &
    (ser, unit, parents, components, peers-i_one, "twin")
end subroutine parton_print_to_unit

```

```

<Muli remnant: muli parton: TBP>+≡
  procedure, nopass :: get_type => parton_get_type

```

```

<Muli remnant: procedures>+≡
  pure subroutine parton_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="muli_parton_t")
  end subroutine parton_get_type

```

```

<Muli remnant: muli parton: TBP>+≡
  procedure :: unweighted_pdf => twin_unweighted_pdf

```

```

<Muli remnant: procedures>+≡
  pure function twin_unweighted_pdf (this, momentum_fraction) result (pdf)
    !parton pdf
    class(muli_parton_t), intent(in) :: this
    real(default), intent(in) :: momentum_fraction
    real(default) :: pdf
    if (momentum_fraction + this%twin%momentum < one) then
      pdf = remnant_twin_pdf_p (momentum_fraction, &
        this%twin%momentum, gluon_exp)
    else
      pdf = zero
    end if
  end function twin_unweighted_pdf

```

```

<Muli remnant: muli parton: TBP>+≡
  procedure :: deallocate => twin_deallocate

```

```

<Muli remnant: procedures>+≡
  recursive subroutine twin_deallocate (this)
    class(muli_parton_t) :: this
    if (associated (this%next)) then
      call this%next%deallocate
      deallocate (this%next)
    end if
  end subroutine twin_deallocate

```

```

<Muli remnant: muli parton: TBP>+≡
  procedure :: push => parton_push

```

```

<Muli remnant: procedures>+≡
  subroutine parton_push (this, parton)
    class(muli_parton_t), intent(inout) :: this
    class(muli_parton_t), intent(inout), pointer :: parton
    ! print *, "parton_push ", parton%id

```

```

parton%next => this%next
this%next => parton
end subroutine parton_push

```

(Muli remnant: muli parton: TBP)+≡

```

generic :: pop => pop_by_id, pop_by_association
procedure :: pop_by_id => parton_pop_by_id
procedure :: pop_by_association => parton_pop_by_association

```

(Muli remnant: procedures)+≡

```

subroutine parton_pop_by_id (this, id, parton)
  class(muli_parton_t), target, intent(inout) :: this
  integer, intent(in) :: id
  class(muli_parton_t), intent(out), pointer :: parton
  class(muli_parton_t), pointer :: tmp_parton
  tmp_parton => this
  do while (associated (tmp_parton%next))
    if (tmp_parton%next%id == id) exit
    tmp_parton => tmp_parton%next
  end do
  if (associated (tmp_parton%next)) then
    parton => tmp_parton%next
    tmp_parton%next => parton%next
    nullify (parton%next)
    ! print *, "parton_pop ", id, parton%id
  else
    nullify (parton)
    print *, "parton_pop ", id, "NULL"
  end if
end subroutine parton_pop_by_id

```

(Muli remnant: procedures)+≡

```

subroutine parton_pop_by_association (this, parton)
  class(muli_parton_t), target, intent(inout) :: this
  class(muli_parton_t), intent(inout), target :: parton
  class(muli_parton_t), pointer :: tmp_parton
  tmp_parton => this
  do while (associated (tmp_parton%next))
    if (associated (tmp_parton%next, parton)) exit
    tmp_parton=>tmp_parton%next
  end do
  if (associated(tmp_parton%next)) then
    tmp_parton%next => parton%next
    nullify (parton%next)
    ! print *, "parton_pop ", parton%id
  else
    print *, "parton_pop NULL"
  end if
end subroutine parton_pop_by_association

```

(Muli remnant: public)+≡

```

public :: proton_remnant_t

```



```

<Muli remnant: types>+≡
  type, extends (ser_class_t) :: proton_remnant_t
    private
      integer, dimension(2) :: valence_content = [1,2]
      integer :: n_twins = 0
      !!! [gluon, sea quark, valence down, valence up, twin]
      real(default), dimension(5) :: pdf_int_weight = [one, one, one, one, one]
      real(default) :: momentum_fraction = one
      real(default) :: twin_norm = one
      type(muli_parton_t) :: twin_partons
      type(muli_parton_t) :: is_partons
      type(muli_parton_t) :: fs_partons
      !!! These pointers shall not be allocated, deallocated,
      !!! serialized or deserialized explicitly.
      class(pdfnorm_t), pointer :: pdf_norm => null()
    contains
      <Muli remnant: proton remnant: TBP>
    end type proton_remnant_t

<Muli remnant: proton remnant: TBP>≡
  procedure :: remove_valence_quark => proton_remnant_remove_valence_quark

<Muli remnant: procedures>+≡
  subroutine proton_remnant_remove_valence_quark &
    (this, id, GeV_scale, momentum_fraction, lha_flavor)
    class(proton_remnant_t), intent(inout) :: this
    integer, intent(in) :: id
    real(default), intent(in) :: GeV_scale, momentum_fraction
    integer, intent(in) :: lha_flavor !!! d=1, u=2
    if (lha_flavor == 1 .or. lha_flavor == 2) then
      associate (q => this%valence_content (lha_flavor))
        if (q > 0) then
          q = q - 1
          call this%push_is_parton (id, lha_flavor, momentum_fraction)
          this%momentum_fraction = this%momentum_fraction * (one - momentum_fraction)
          call this%calculate_weight (GeV_scale)
        else
          write (*, "(1x,A,I2,A)") "proton_remnant_remove_valence_quark: " // &
            "Cannot remove parton ", lha_flavor, ": There are no such " // &
            "partons left."
          call this%print_all ()
        end if
      end associate
    else
      write (*, "(1x,A,I2,A)") "proton_remnant_remove_valence_quark: Cannot " // &
        "remove parton ", lha_flavor, ": There are no such valence partons."
    end if
  end subroutine proton_remnant_remove_valence_quark

<Muli remnant: proton remnant: TBP>+≡
  procedure :: remove_sea_quark => proton_remnant_remove_sea_quark

<Muli remnant: procedures>+≡
  subroutine proton_remnant_remove_sea_quark &

```

```

        (this, id, GeV_scale, momentum_fraction, lha_flavor)
class(proton_remnant_t), intent(inout) :: this
integer, intent(in) :: id
real(default), intent(in) :: GeV_scale, momentum_fraction
integer, intent(in) :: lha_flavor
! print *, "proton_remnant_remove_sea_quark", momentum_fraction
if (lha_flavor > -6 .and. lha_flavor < 6 .and. lha_flavor .ne. 0) then
    this%momentum_fraction = this%momentum_fraction * &
        (one - momentum_fraction)
    call this%push_twin (id, lha_flavor, momentum_fraction, GeV_scale)
end if
end subroutine proton_remnant_remove_sea_quark

<Muli remnant: proton remnant: TBP>+=
procedure :: remove_gluon => proton_remnant_remove_gluon

<Muli remnant: procedures>+=
subroutine proton_remnant_remove_gluon &
    (this, id, GeV_scale, momentum_fraction)
class(proton_remnant_t), intent(inout) :: this
integer, intent(in) :: id
real(default), intent(in) :: GeV_scale, momentum_fraction
this%momentum_fraction = this%momentum_fraction * (one - momentum_fraction)
call this%push_is_parton (id, LHA_FLAVOR_g, momentum_fraction)
end subroutine proton_remnant_remove_gluon

<Muli remnant: proton remnant: TBP>+=
procedure :: remove_valence_up_quark => proton_remnant_remove_valence_up_quark

<Muli remnant: procedures>+=
subroutine proton_remnant_remove_valence_up_quark &
    (this, id, GeV_scale, momentum_fraction)
class(proton_remnant_t), intent(inout) :: this
integer, intent(in) :: id
real(default), intent(in) :: GeV_scale, momentum_fraction
associate (q => this%valence_content (LHA_FLAVOR_u))
    if (q > 0) then
        q = q - 1
        call this%push_is_parton (id, LHA_FLAVOR_u, momentum_fraction)
        this%momentum_fraction = this%momentum_fraction * (one - momentum_fraction)
        call this%calculate_weight (GeV_scale)
    else
        write (*, "(1x,A,I2,A)") "proton_remnant_remove_valence_up_quark: " // &
            "Cannot remove parton ", LHA_FLAVOR_u, ": There are no such " // &
            "partons left."
        call this%print_all
    end if
end associate
end subroutine proton_remnant_remove_valence_up_quark

<Muli remnant: proton remnant: TBP>+=
procedure :: remove_valence_down_quark => &
    proton_remnant_remove_valence_down_quark

```

<Muli remnant: procedures>+≡

```

subroutine proton_remnant_remove_valence_down_quark &
  (this, id, GeV_scale, momentum_fraction)
  class(proton_remnant_t), intent(inout) :: this
  integer, intent(in) :: id
  real(default), intent(in) :: GeV_scale, momentum_fraction
  associate (q => this%valence_content(LHA_FLAVOR_d))
    if (q > 0) then
      q = q - 1
      call this%push_is_parton (id, LHA_FLAVOR_d, momentum_fraction)
      this%momentum_fraction = this%momentum_fraction * &
        (one - momentum_fraction)
      call this%calculate_weight (GeV_scale)
    else
      write (*, "(1x,A,I2,A)") "proton_remnant_remove_valence_down_quark:" // &
        "Cannot remove parton ", LHA_FLAVOR_d, ": There are no " // &
        "such partons left."
      call this%print_all
    end if
  end associate
end subroutine proton_remnant_remove_valence_down_quark

```

<Muli remnant: proton remnant: TBP>+≡

```

procedure :: remove_twin => proton_remnant_remove_twin

```

<Muli remnant: procedures>+≡

```

subroutine proton_remnant_remove_twin (this, id, GeV_scale)
  class(proton_remnant_t), intent(inout) :: this
  integer, intent(in) :: id
  real(default), intent(in) :: GeV_scale
  class(muli_parton_t), pointer :: twin
  call this%twin_partons%pop (id, twin)
  call this%fs_partons%push (twin)
  this%twin_norm = this%twin_norm - twin%momentum
  this%n_twins = this%n_twins - 1
  call this%calculate_weight (GeV_scale)
end subroutine proton_remnant_remove_twin

```

<Muli remnant: proton remnant: TBP>+≡

```

procedure :: momentum_twin_pdf => proton_remnant_momentum_twin_pdf

```

<Muli remnant: procedures>+≡

```

subroutine proton_remnant_momentum_twin_pdf &
  (this, lha_flavor, momentum_fraction, pdf)
  class(proton_remnant_t), intent(in) :: this
  integer, intent(in) :: lha_flavor
  real(default), intent(in) :: momentum_fraction
  real(default), intent(out) :: pdf
  call this%parton_twin_pdf (lha_flavor, momentum_fraction, pdf)
  pdf = pdf * momentum_fraction
end subroutine proton_remnant_momentum_twin_pdf

```

<Muli remnant: proton remnant: TBP>+≡

```

procedure :: momentum_twin_pdf_array => proton_remnant_momentum_twin_pdf_array

```

(Muli remnant: procedures)+≡

```
subroutine proton_remnant_momentum_twin_pdf_array &
  (this, momentum_fraction, pdf)
  class(proton_remnant_t), intent(in) :: this
  real(default), intent(in) :: momentum_fraction
  real(default), dimension(this%n_twins), intent(out) :: pdf
  call this%parton_twin_pdf_array (momentum_fraction, pdf)
  pdf = pdf * momentum_fraction
end subroutine proton_remnant_momentum_twin_pdf_array
```

(Muli remnant: proton remnant: TBP)+≡

```
procedure :: momentum_kind_pdf => proton_remnant_momentum_kind_pdf
```

(Muli remnant: procedures)+≡

```
subroutine proton_remnant_momentum_kind_pdf (this, GeV_scale, &
  momentum_fraction, lha_flavor, valence_pdf, sea_pdf, twin_pdf)
  class(proton_remnant_t), intent(in) :: this
  real(default), intent(in) :: GeV_scale, momentum_fraction
  integer, intent(in) :: lha_flavor      !!! g, u, d, etc.
  real(default), intent(out) :: valence_pdf, sea_pdf, twin_pdf
  real(double), dimension(-6:6) :: pdf_array
  call evolvePDF (momentum_fraction, GeV_scale, pdf_array)
  select case (lha_flavor)
  case (0) !!! gluon
    valence_pdf = zero
    sea_pdf=pdf_array(0)
  case (1) !!! down
    valence_pdf = this%get_valence_down_weight() * (pdf_array(1) - pdf_array(-1))
    sea_pdf = pdf_array(-1)
  case (2) !!! up
    valence_pdf = this%get_valence_up_weight() * (pdf_array(2) - pdf_array(-2))
    sea_pdf = pdf_array(-2)
  case default
    valence_pdf = zero
    sea_pdf = pdf_array (lha_flavor)
  end select
  sea_pdf = sea_pdf * this%get_sea_weight()
  call this%momentum_twin_pdf (lha_flavor, momentum_fraction, twin_pdf)
end subroutine proton_remnant_momentum_kind_pdf
```

(Muli remnant: proton remnant: TBP)+≡

```
procedure :: momentum_flavor_pdf => proton_remnant_momentum_flavor_pdf
```

(Muli remnant: procedures)+≡

```
subroutine proton_remnant_momentum_flavor_pdf (this, GeV_scale, &
  momentum_fraction, lha_flavor, pdf)
  class(proton_remnant_t), intent(in) :: this
  real(default), intent(in) :: GeV_scale, momentum_fraction
  integer, intent(in) :: lha_flavor      !!! g, u, d, etc.
  real(default), intent(out) :: pdf
  real(default) :: valence_pdf, sea_pdf, twin_pdf
  call this%momentum_kind_pdf (GeV_scale, momentum_fraction, &
    lha_flavor, valence_pdf, sea_pdf, twin_pdf)
```

```

    pdf = valence_pdf + sea_pdf + twin_pdf
end subroutine proton_remnant_momentum_flavor_pdf

<Muli remnant: proton remnant: TBP>+≡
    procedure :: momentum_kind_pdf_array => &
        proton_remnant_momentum_kind_pdf_array

<Muli remnant: procedures>+≡
    subroutine proton_remnant_momentum_kind_pdf_array (this, GeV_scale, &
        momentum_fraction, valence_pdf, sea_pdf)
        class(proton_remnant_t), intent(in) :: this
        real(default), intent(in) :: GeV_scale, momentum_fraction
        real(default), dimension(2), intent(out) :: valence_pdf
        real(double), dimension(-6:6), intent(out) :: sea_pdf
        call evolvePDF (momentum_fraction, GeV_scale, sea_pdf)
        valence_pdf(1) = (sea_pdf(1) - sea_pdf(-1)) * &
            this%pdf_int_weight (PDF_VALENCE_DOWN)
        valence_pdf(2) = (sea_pdf(2) - sea_pdf(-2)) * &
            this%pdf_int_weight (PDF_VALENCE_UP)
        sea_pdf(1) = sea_pdf(-1)
        sea_pdf(2) = sea_pdf(-2)
        sea_pdf = sea_pdf * this%get_sea_weight()
        !!! no twin yet
    end subroutine proton_remnant_momentum_kind_pdf_array

<Muli remnant: proton remnant: TBP>+≡
    procedure :: momentum_flavor_pdf_array => proton_remnant_momentum_flavor_pdf_array

<Muli remnant: procedures>+≡
    subroutine proton_remnant_momentum_flavor_pdf_array &
        (this, GeV_scale, momentum_fraction, pdf)
        class(proton_remnant_t), intent(in) :: this
        real(default), intent(in) :: GeV_scale, momentum_fraction
        real(double), dimension(-6:6), intent(out) :: pdf
        real(default), dimension(2) :: valence_pdf
        call this%momentum_kind_pdf_array &
            (GeV_scale, momentum_fraction, valence_pdf, pdf)
        pdf(1:2) = pdf(1:2) + valence_pdf
        !!! no twin yet
    end subroutine proton_remnant_momentum_flavor_pdf_array

<Muli remnant: proton remnant: TBP>+≡
    procedure :: parton_twin_pdf => proton_remnant_parton_twin_pdf

<Muli remnant: procedures>+≡
    subroutine proton_remnant_parton_twin_pdf &
        (this, lha_flavor, momentum_fraction, pdf)
        class(proton_remnant_t), intent(in) :: this
        integer, intent(in) :: lha_flavor
        real(default), intent(in) :: momentum_fraction
        real(default) :: pdf
        class(multi_parton_t), pointer :: tmp_twin
        pdf = 0D0
        tmp_twin => this%twin_partons%next

```

```

do while (associated (tmp_twin))
  if (tmp_twin%lha_flavor == lha_flavor) pdf = pdf &
    + tmp_twin%unweighted_pdf (momentum_fraction)
  tmp_twin => tmp_twin%next
end do
pdf = pdf * this%get_twin_weight ()
end subroutine proton_remnant_parton_twin_pdf

```

(Muli remnant: proton remnant: TBP)+≡
 procedure :: parton_twin_pdf_array => proton_remnant_parton_twin_pdf_array

(Muli remnant: procedures)+≡
 subroutine proton_remnant_parton_twin_pdf_array &
 (this, momentum_fraction, pdf)
 class(proton_remnant_t), intent(in) :: this
 real(default), intent(in) :: momentum_fraction
 real(default), dimension(this%n_twins), intent(out) :: pdf
 class(muli_parton_t), pointer :: tmp_twin
 integer :: l
 tmp_twin => this%twin_partons%next
 l = 0
 do while (associated (tmp_twin))
 l = l + 1
 pdf(l) = tmp_twin%unweighted_pdf (momentum_fraction) * this%twin_norm
 tmp_twin => tmp_twin%next
 end do
 end subroutine proton_remnant_parton_twin_pdf_array

(Muli remnant: proton remnant: TBP)+≡
 procedure :: parton_kind_pdf => proton_remnant_parton_kind_pdf

(Muli remnant: procedures)+≡
 subroutine proton_remnant_parton_kind_pdf (this, GeV_scale, momentum_fraction, &
 lha_flavor, valence_pdf, sea_pdf, twin_pdf)
 class(proton_remnant_t), intent(in) :: this
 real(default), intent(in) :: GeV_scale, momentum_fraction
 integer, intent(in) :: lha_flavor !!! g, u, d, etc.
 real(default), intent(out) :: valence_pdf, sea_pdf, twin_pdf
 call this%momentum_kind_pdf (GeV_scale, momentum_fraction, &
 lha_flavor, valence_pdf, sea_pdf, twin_pdf)
 valence_pdf = valence_pdf / momentum_fraction
 sea_pdf = sea_pdf / momentum_fraction
 twin_pdf = twin_pdf / momentum_fraction
 end subroutine proton_remnant_parton_kind_pdf

(Muli remnant: proton remnant: TBP)+≡
 procedure :: parton_flavor_pdf => proton_remnant_parton_flavor_pdf

(Muli remnant: procedures)+≡
 subroutine proton_remnant_parton_flavor_pdf (this, GeV_scale, &
 momentum_fraction, lha_flavor, pdf)
 class(proton_remnant_t), intent(in) :: this
 real(default), intent(in) :: GeV_scale, momentum_fraction
 integer, intent(in) :: lha_flavor !g,u,d,etc.

```

    real(default), intent(out) :: pdf
    call this%momentum_flavor_pdf (GeV_scale, momentum_fraction, &
        lha_flavor, pdf)
    pdf = pdf / momentum_fraction
end subroutine proton_remnant_parton_flavor_pdf

<Muli remnant: proton remnant: TBP>+=
    procedure :: parton_kind_pdf_array => proton_remnant_parton_kind_pdf_array

<Muli remnant: procedures>+=
    subroutine proton_remnant_parton_kind_pdf_array &
        (this, GeV_scale, momentum_fraction, valence_pdf, sea_pdf)
    class(proton_remnant_t), intent(in) :: this
    real(default), intent(in) :: GeV_scale, momentum_fraction
    real(default), dimension(2), intent(out) :: valence_pdf
    real(double), dimension(-6:6), intent(out) :: sea_pdf
    call evolvePDF (momentum_fraction, GeV_scale, sea_pdf)
    sea_pdf = sea_pdf / momentum_fraction
    valence_pdf(1) = (sea_pdf(1) - sea_pdf(-1)) * this%valence_content(1)
    valence_pdf(2) = (sea_pdf(2) - sea_pdf(-2)) * (this%valence_content(2) / two)
    sea_pdf(1) = sea_pdf(-1)
    sea_pdf(2) = sea_pdf(-2)
    valence_pdf = valence_pdf * this%get_valence_weight()
    sea_pdf = sea_pdf * this%get_sea_weight()
    !!! no twin yet
end subroutine proton_remnant_parton_kind_pdf_array

<Muli remnant: proton remnant: TBP>+=
    procedure :: parton_flavor_pdf_array => proton_remnant_parton_flavor_pdf_array

<Muli remnant: procedures>+=
    subroutine proton_remnant_parton_flavor_pdf_array &
        (this, GeV_scale, momentum_fraction, pdf)
    class(proton_remnant_t), intent(in) :: this
    real(default), intent(in) :: GeV_scale, momentum_fraction
    real(double), dimension(-6:6), intent(out) :: pdf
    real(double), dimension(2) :: valence_pdf
    real(double), dimension(-6:6) :: twin_pdf
    call msg_error ("proton_remnant_flavor_pdf_array: Not yet implemented.")
end subroutine proton_remnant_parton_flavor_pdf_array

<Muli remnant: proton remnant: TBP>+=
    procedure :: get_pdf_int_weight => proton_remnant_get_pdf_int_weight

<Muli remnant: procedures>+=
    pure function proton_remnant_get_pdf_int_weight (this) result(weight)
    class(proton_remnant_t), intent(in) :: this
    real(default), dimension(5) :: weight
    weight = this%pdf_int_weight
end function proton_remnant_get_pdf_int_weight

<Muli remnant: proton remnant: TBP>+=
    procedure :: get_valence_down_weight => proton_remnant_get_valence_down_weight

```

```

<Muli remnant: procedures>+≡
  elemental function proton_remnant_get_valence_down_weight (this) result (weight)
    class(proton_remnant_t), intent(in) :: this
    real(default) :: weight
    weight = this%pdf_int_weight (PDF_VALENCE_DOWN)
  end function proton_remnant_get_valence_down_weight

<Muli remnant: proton remnant: TBP>+≡
  procedure :: get_valence_up_weight => proton_remnant_get_valence_up_weight

<Muli remnant: procedures>+≡
  elemental function proton_remnant_get_valence_up_weight (this) result (weight)
    class(proton_remnant_t), intent(in) :: this
    real(default) :: weight
    weight = this%pdf_int_weight (PDF_VALENCE_UP)
  end function proton_remnant_get_valence_up_weight

<Muli remnant: proton remnant: TBP>+≡
  procedure :: get_valence_weight => proton_remnant_get_valence_weight

<Muli remnant: procedures>+≡
  pure function proton_remnant_get_valence_weight (this) result (weight)
    class(proton_remnant_t), intent(in) :: this
    real(default), dimension(2) :: weight
    weight = this%pdf_int_weight(3:4)
  end function proton_remnant_get_valence_weight

<Muli remnant: proton remnant: TBP>+≡
  procedure :: get_gluon_weight => proton_remnant_get_gluon_weight

<Muli remnant: procedures>+≡
  elemental function proton_remnant_get_gluon_weight (this) result (weight)
    class(proton_remnant_t), intent(in) :: this
    real(default) :: weight
    weight = this%pdf_int_weight (PDF_GLUON)
  end function proton_remnant_get_gluon_weight

<Muli remnant: proton remnant: TBP>+≡
  procedure :: get_sea_weight => proton_remnant_get_sea_weight

<Muli remnant: procedures>+≡
  elemental function proton_remnant_get_sea_weight (this) result (weight)
    class(proton_remnant_t), intent(in) :: this
    real(default) :: weight
    weight = this%pdf_int_weight (PDF_SEA)
  end function proton_remnant_get_sea_weight

<Muli remnant: proton remnant: TBP>+≡
  procedure :: get_twin_weight => proton_remnant_get_twin_weight

```



```

<Muli remnant: procedures>+≡
    elemental function proton_remnant_get_twin_weight (this) result (weight)
        class(proton_remnant_t), intent(in) :: this
        real(default) :: weight
        weight = this%pdf_int_weight (PDF_TWIN)
    end function proton_remnant_get_twin_weight

<Muli remnant: proton remnant: TBP>+≡
    procedure :: get_valence_content => proton_remnant_get_valence_content

<Muli remnant: procedures>+≡
    pure function proton_remnant_get_valence_content (this) result (valence)
        class(proton_remnant_t), intent(in) :: this
        integer, dimension(2) :: valence
        valence = this%valence_content
    end function proton_remnant_get_valence_content

<Muli remnant: proton remnant: TBP>+≡
    procedure :: get_momentum_fraction => proton_remnant_get_momentum_fraction

<Muli remnant: procedures>+≡
    elemental function proton_remnant_get_momentum_fraction (this) result (momentum)
        class(proton_remnant_t), intent(in) :: this
        real(default) :: momentum
        momentum = this%momentum_fraction
    end function proton_remnant_get_momentum_fraction

<Muli remnant: proton remnant: TBP>+≡
    procedure :: deallocate => proton_remnant_deallocate

<Muli remnant: procedures>+≡
    subroutine proton_remnant_deallocate (this)
        class(proton_remnant_t), intent(inout) :: this
        call this%is_partons%deallocate
        call this%fs_partons%deallocate
        call this%twin_partons%deallocate
        this%twin_norm = zero
        this%n_twins = 0
    end subroutine proton_remnant_deallocate

<Muli remnant: proton remnant: TBP>+≡
    procedure :: initialize => proton_remnant_initialize

<Muli remnant: procedures>+≡
    subroutine proton_remnant_initialize (this, pdf_norm)
        class(proton_remnant_t), intent(out) :: this
        class(pdfnorm_t), target, intent(in) :: pdf_norm
        this%pdf_norm => pdf_norm
    end subroutine proton_remnant_initialize

<Muli remnant: proton remnant: TBP>+≡
    procedure :: finalize => proton_remnant_finalize

```

```

<Muli remnant: procedures>+≡
  subroutine proton_remnant_finalize (this)
    class(proton_remnant_t), intent(inout) :: this
    call this%deallocate ()
    nullify (this%pdf_norm)
  end subroutine proton_remnant_finalize

<Muli remnant: proton remnant: TBP>+≡
  procedure :: apply_initial_splitting => proton_remnant_apply_initial_splitting

<Muli remnant: procedures>+≡
  subroutine proton_remnant_apply_initial_splitting &
    (this, id, pdg_flavor, x, gev_scale, rnd)
    class(proton_remnant_t), intent(inout) :: this
    integer, intent(in) :: id, pdg_flavor
    real(default), intent(in) :: x, gev_scale, rnd
    real(default) :: valence_pdf, sea_pdf, twin_pdf
    select case (pdg_flavor)
    case (PDG_FLAVOR_g)
      call this%remove_gluon (id, gev_scale, x)
    case (PDG_FLAVOR_u)
      call this%parton_kind_pdf (gev_scale, x, pdg_flavor, &
        valence_pdf, sea_pdf, twin_pdf)
      if (valence_pdf / (valence_pdf + sea_pdf) < rnd) then
        call this%remove_sea_quark (id, gev_scale, x, pdg_flavor)
      else
        call this%remove_valence_up_quark (id, gev_scale, x)
      end if
    case (PDG_FLAVOR_d)
      call this%parton_kind_pdf (gev_scale, x, &
        pdg_flavor, valence_pdf, sea_pdf, twin_pdf)
      if (valence_pdf / (valence_pdf + sea_pdf) < rnd) then
        call this%remove_sea_quark (id, gev_scale, x, pdg_flavor)
      else
        call this%remove_valence_down_quark (id, gev_scale, x)
      end if
    case default
      call this%remove_sea_quark (id, gev_scale, x, pdg_flavor)
    end select
    this%momentum_fraction = (one - x)
  end subroutine proton_remnant_apply_initial_splitting

<Muli remnant: proton remnant: TBP>+≡
  procedure :: reset => proton_remnant_reset

<Muli remnant: procedures>+≡
  subroutine proton_remnant_reset (this)
    class(proton_remnant_t), intent(inout) :: this
    call this%deallocate ()
    this%valence_content = [1, 2]
    this%pdf_int_weight = [one, one, one, one, one]
    this%momentum_fraction = one
  end subroutine proton_remnant_reset

```

```

<Muli remnant: proton remnant: TBP>+=
  procedure :: calculate_weight => proton_remnant_calculate_weight

<Muli remnant: procedures>+=
  subroutine proton_remnant_calculate_weight (this, GeV_scale)
    class(proton_remnant_t), intent(inout) :: this
    real(default), intent(in) :: GeV_scale
    real(default) :: all, gluon, sea, vu, vd, valence, twin, weight
    call this%pdf_norm%get_norm (GeV_scale, 1, 0, all)
    call this%pdf_norm%get_norm (GeV_scale, 1, PDF_GLUON, gluon)
    call this%pdf_norm%get_norm (GeV_scale, 1, PDF_SEA, sea)
    call this%pdf_norm%get_norm (GeV_scale, 1, PDF_VALENCE_DOWN, vd)
    call this%pdf_norm%get_norm (GeV_scale, 1, PDF_VALENCE_UP, vu)
    valence = vd * this%valence_content (LHA_FLAVOR_d) + &
              vu * this%valence_content (LHA_FLAVOR_u) / two
    twin = this%twin_norm / all
    ! print *, all, gluon + sea + valence + twin, gluon, sea, valence, twin
    ! pdf_rescale = (one - n_d_valence * mean_d1 - n_u_valence * mean_u2) / &
    ! (1.E-1_default * mean_d1 - two * mean_u2) !!! pythia
    select case (remnant_weight_model)
    case (0) !!! no reweighting
      this%pdf_int_weight = [one, one, one, one, one]
    case (2) !!! pythia-like, only sea
      weight = (one - valence - twin) / (sea + gluon)
      this%pdf_int_weight = [weight, weight, one, one, one]
    case (3) !!! only valence and twin
      weight = (one - sea - gluon) / (valence + twin)
      this%pdf_int_weight = [one, one, weight, weight, weight]
    case (4) !!! only sea and twin
      weight = (one - valence) / (sea + gluon + twin)
      this%pdf_int_weight = [one, weight, one, one, weight]
    case default !!! equal weight
      weight = one / (valence + sea + gluon + twin)
      this%pdf_int_weight = [weight, weight, weight, weight, weight]
    end select
    this%pdf_int_weight(PDF_VALENCE_DOWN) = &
      this%pdf_int_weight(PDF_VALENCE_DOWN) * this%valence_content(1)
    this%pdf_int_weight(PDF_VALENCE_UP) = &
      this%pdf_int_weight(PDF_VALENCE_UP) * this%valence_content(2) * &
      5.E-1_default
    ! print('("New rescale factors are: ",2(I10),7(E14.7))'),&
    !   this%valence_content,&
    !   this%pdf_int_weight,&
    !   sea_norm,&
    !   valence_norm,&
    !   this%twin_norm
  end subroutine proton_remnant_calculate_weight

<Muli remnant: proton remnant: TBP>+=
  procedure :: push_is_parton => proton_remnant_push_is_parton

<Muli remnant: procedures>+=
  subroutine proton_remnant_push_is_parton &
    (this, id, lha_flavor, momentum_fraction)
    class(proton_remnant_t), intent(inout) :: this

```

```

integer, intent(in) :: id, lha_flavor
real(default), intent(in) :: momentum_fraction
class(multi_parton_t), pointer :: tmp_parton
allocate (tmp_parton)
tmp_parton%id = id
tmp_parton%lha_flavor = lha_flavor
tmp_parton%momentum = momentum_fraction
call this%is_partons%push (tmp_parton)
end subroutine proton_remnant_push_is_parton

```

(Muli remnant: proton remnant: TBP)+≡
 procedure :: push_twin => proton_remnant_push_twin

(Muli remnant: procedures)+≡
 subroutine proton_remnant_push_twin &
 (this, id, lha_flavor, momentum_fraction, gev_scale)
 class(proton_remnant_t), intent(inout) :: this
 integer, intent(in) :: id, lha_flavor !!! of IS parton
 real(default), intent(in) :: momentum_fraction !!! of IS parton
 real(default), intent(in) :: GeV_scale
 class(multi_parton_t), pointer :: new_is, new_twin
 real(default) :: norm
 ! print *, "proton_remnant_push_twin", momentum_fraction
 allocate (new_is)
 allocate (new_twin)
 !!! IS initialization
 new_is%id = id
 new_is%lha_flavor = lha_flavor
 new_is%momentum = momentum_fraction
 new_is%twin => new_twin
 !!! twin initialization
 new_twin%id = -id
 new_twin%lha_flavor = -lha_flavor
 new_twin%momentum = remnant_twin_momentum_4 (momentum_fraction)
 new_twin%twin => new_is
 !!! remnant update
 this%n_twins = this%n_twins + 1
 this%twin_norm = this%twin_norm + new_twin%momentum
 call this%is_partons%push (new_is)
 call this%twin_partons%push (new_twin)
 call this%calculate_weight (GeV_scale)
end subroutine proton_remnant_push_twin

(Muli remnant: proton remnant: TBP)+≡
 procedure :: calculate_twin_norm => proton_remnant_calculate_twin_norm

(Muli remnant: procedures)+≡
 subroutine proton_remnant_calculate_twin_norm (this)
 class(proton_remnant_t), intent(inout) :: this
 class(multi_parton_t), pointer :: twin
 integer :: n
 if (associated (this%twin_partons%next)) then
 this%twin_norm = zero
 twin => this%twin_partons%next

```

do while (associated (twin))
  this%twin_norm = this%twin_norm + twin%momentum
  twin => twin%next
end do
else
  this%twin_norm = zero
end if
end subroutine proton_remnant_calculate_twin_norm

```

(Multi remnant: proton remnant: TBP)+≡

```

procedure :: replace_is_parton => proton_remnant_replace_is_parton

```

(Multi remnant: procedures)+≡

```

subroutine proton_remnant_replace_is_parton &
  (this, old_id, new_id, pdg_f, x_proton, gev_scale)
  class(proton_remnant_t), intent(inout) :: this
  integer, intent(in) :: old_id, new_id, pdg_f
  real(default), intent(in) :: x_proton, gev_scale
  class(multi_parton_t), pointer :: old_is_parton
  integer :: lha_flavor
  real(default) :: momentum_fraction
  momentum_fraction = x_proton / this%momentum_fraction
  !!! convert PDG flavor numbers to LHA flavor numbers
  if (pdg_f == PDG_FLAVOR_g) then
    lha_flavor = LHA_FLAVOR_g
  else
    lha_flavor = pdg_f
  end if
  !!! we remove the old initial state parton from initial state stack.
  call this%is_partons%pop (old_id, old_is_parton)
  !!! this check has no physical meaning, it's just a check for consistency.
  if (associated (old_is_parton)) then
    !!! do we emit a gluon?
    if (lha_flavor == old_is_parton%lha_flavor) then
      !!! has the old initial state parton been a sea quark?
      if (associated (old_is_parton%twin)) then
        !!! the connection of the old IS parton with its twin was
        !!! provisional. We remove it now
        call this%twin_partons%pop (old_is_parton%twin)
        call this%fs_partons%push (old_is_parton%twin)
        this%n_twins = this%n_twins - 1
        !!! and generate a new initial state parton - twin pair.
        call this%push_twin &
          (new_id, lha_flavor, momentum_fraction, gev_scale)
      else
        !!! there is no twin, so we just insert the new initial state parton.
        call this%push_is_parton (new_id, lha_flavor, momentum_fraction)
      end if
    else
      ! we emit a quark. is this a g->qqbar splitting?
      if (lha_flavor==LHA_FLAVOR_g) then
        !!! we insert the new initial state gloun.
        call this%push_is_parton (new_id, lha_flavor, momentum_fraction)
        !!! has the old initial state quark got a twin?

```

```

    if (associated (old_is_parton%twin)) then
        !!! we assume that this twin is the second splitting particle.
        !!! so the twin becomes a final state particle now and
        !!! must be removed from the is stack.
        call this%remove_twin (-old_id, GeV_scale)
    else
        !!! the old initial state quark has been a valence quark.
        !!! what should we do now? is this splitting sensible at all?
        !!! we don't know but allow these splittings. The most trivial
        !!! treatment is to restore the former valence quark.
        this%valence_content (old_is_parton%lha_flavor) = &
            this%valence_content (old_is_parton%lha_flavor) + 1
    end if
else
    !!! this is a q->qg splitting. the new initial state quark emits
    !!! the preceding initial state gluon. yeah, backward evolution is
    !!! confusing! the new initial state quark is not part of the
    !!! proton remnant any longer. how do we remove a quark from
    !!! the remnant? we add a conjugated twin parton and assume,
    !!! that this twin is created in a not yet resolved g->qqbar splitting.
    call this%push_twin (new_id, lha_flavor, momentum_fraction, gev_scale)
end if
end if
!!! everything is done. what shall we do with the old initial state
!!! parton? we don't need it any more but we store it anyway.
call this%fs_partons%push (old_is_parton)
!!! the new initial state parton has taken away momentum, so we update
!!! the remnant momentum fraction.
this%momentum_fraction = this%momentum_fraction * (1 - &
    momentum_fraction) / (1 - old_is_parton%momentum)
else
    !!! this is a bug.
    print *, "proton_remnant_replace_is_parton: parton #", old_id, &
        " not found on ISR stack."
    if (associated (this%is_partons%next)) then
        print *, "actual content of isr stack:"
        call this%is_partons%next%print_peers ()
    else
        print *, "ISR stack is not associated."
    end if
    stop
end if
end if
end subroutine proton_remnant_replace_is_parton

```

<Multi remnant: proton remnant: TBP>+≡

```

    procedure :: write_to_marker => proton_remnant_write_to_marker

```

<Multi remnant: procedures>+≡

```

    subroutine proton_remnant_write_to_marker (this, marker, status)
        class(proton_remnant_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%mark_begin ("proton_remnant_t")
        call marker%mark ("valence_content", this%valence_content)
    end subroutine

```

```

        call marker%mark ("momentum_fraction", this%momentum_fraction)
        call marker%mark ("pdf_int_weight", this%pdf_int_weight)
        call marker%mark_end ("proton_remnant_t")
    end subroutine proton_remnant_write_to_marker

<Muli remnant: proton remnant: TBP>+≡
    procedure :: read_from_marker => proton_remnant_read_from_marker

<Muli remnant: procedures>+≡

    subroutine proton_remnant_read_from_marker (this, marker, status)
        class(proton_remnant_t), intent(out) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        character(:), allocatable :: name
        call marker%pick_begin ("proton_remnant_t", status=status)
        call marker%pick ("valence_content", this%valence_content, status)
        call marker%pick ("momentum_fraction", this%momentum_fraction, status)
        call marker%pick ("pdf_int_weight", this%pdf_int_weight, status)
        call marker%pick_end ("proton_remnant_t", status=status)
    end subroutine proton_remnant_read_from_marker

<Muli remnant: proton remnant: TBP>+≡
    procedure :: print_to_unit => proton_remnant_print_to_unit

<Muli remnant: procedures>+≡
    subroutine proton_remnant_print_to_unit (this, unit, parents, components, peers)
        class(proton_remnant_t), intent(in) :: this
        integer, intent(in) :: unit
        integer(dik), intent(in) :: parents, components, peers
        write (unit, '("Components of proton_remnant_t:")')
        write (unit, '("Valence Content:           ",I1,":",I1)')this%
            &%valence_content
        write (unit, "(1x,A,I1)") "N Twins:           ", this%n_twins
        write (unit, "(1x,A,5(F7.3))") "INT weights [g,s,d,u,t]    ", &
            this%pdf_int_weight
        write (unit, "(1x,A,F7.3)") "Total Momentum Fraction:  ", &
            this%momentum_fraction
        write (unit, "(1x,A,F7.3)") "Twin Norm:           ", this%twin_norm
    end subroutine proton_remnant_print_to_unit

<Muli remnant: proton remnant: TBP>+≡
    procedure, nopass :: get_type => proton_remnant_get_type

<Muli remnant: procedures>+≡
    pure subroutine proton_remnant_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="proton_remnant_t")
    end subroutine proton_remnant_get_type

<Muli remnant: proton remnant: TBP>+≡
    procedure :: gnuplot_momentum_kind_pdf_array => &
        proton_remnant_gnuplot_momentum_kind_pdf_array

```

```

<Muli remnant: procedures>+=
subroutine proton_remnant_gnuplot_momentum_kind_pdf_array &
  (this, momentum_unit, parton_unit, GeV_scale)
  class(proton_remnant_t), intent(in) :: this
  integer, intent(in) :: momentum_unit, parton_unit
  real(default), intent(in) :: GeV_scale
  real(default), dimension(2) :: valence_pdf
  real(double), dimension(-6:6) :: sea_pdf
  real(default), dimension(this%n_twins) :: twin_pdf
  integer :: x
  real(default) :: momentum_fraction
  do x = 1, 100
    momentum_fraction = x * 1E-2_default
    call this%momentum_kind_pdf_array (GeV_scale, momentum_fraction, &
      valence_pdf, sea_pdf)
    call this%momentum_twin_pdf_array (momentum_fraction, twin_pdf)
    write (momentum_unit, fmt=*) momentum_fraction, &
      sum(valence_pdf) + sum(sea_pdf) + sum(twin_pdf), &
      valence_pdf, sea_pdf, twin_pdf
    call this%parton_kind_pdf_array (GeV_scale, momentum_fraction, &
      valence_pdf, sea_pdf)
    call this%parton_twin_pdf_array (momentum_fraction, twin_pdf)
    write(parton_unit,fmt=*) momentum_fraction, &
      sum(valence_pdf) + sum(sea_pdf) + sum(twin_pdf), &
      valence_pdf, sea_pdf, twin_pdf
  end do
end subroutine proton_remnant_gnuplot_momentum_kind_pdf_array

<Muli remnant: public>+=
public :: pp_remnant_t

<Muli remnant: types>+=
type, extends (ser_class_t) :: pp_remnant_t
  logical :: initialized = .false.
  real(default), private :: gev_initial_cme = gev_cme_tot
  real(default), private :: X = one
  type(proton_remnant_t), dimension(2) :: proton
  class(pdfnorm_t), pointer :: pdf_norm
contains
  <Muli remnant: PP remnant: TBP>
end type pp_remnant_t

<Muli remnant: PP remnant: TBP>=
procedure :: write_to_marker => pp_remnant_write_to_marker

<Muli remnant: procedures>+=
subroutine pp_remnant_write_to_marker (this, marker, status)
  class(pp_remnant_t), intent(in) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  call marker%mark_begin ("pp_remnant_t")
  call marker%mark ("gev_initial_cme", this%gev_initial_cme)
  call marker%mark ("X", this%X)
  call this%proton(1)%write_to_marker (marker, status)

```



```

    call this%proton(2)%write_to_marker (marker, status)
    call marker%mark_end ("pp_remnant_t")
end subroutine pp_remnant_write_to_marker

```

<Muli remnant: PP remnant: TBP>+≡

```

    procedure :: read_from_marker => pp_remnant_read_from_marker

```

<Muli remnant: procedures>+≡

```

subroutine pp_remnant_read_from_marker (this, marker, status)
    class(pp_remnant_t), intent(out) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    character(:), allocatable :: name
    call marker%pick_begin ("pp_remnant_t", status=status)
    call marker%pick ("gev_initial_cme", this%gev_initial_cme, status)
    call marker%pick ("X", this%X, status)
    call this%proton(1)%read_from_marker (marker, status)
    call this%proton(2)%read_from_marker (marker, status)
    call marker%pick_end ("pp_remnant_t", status=status)
end subroutine pp_remnant_read_from_marker

```

<Muli remnant: PP remnant: TBP>+≡

```

    procedure :: print_to_unit => pp_remnant_print_to_unit

```

<Muli remnant: procedures>+≡

```

subroutine pp_remnant_print_to_unit (this, unit, parents, components, peers)
    class(pp_remnant_t), intent(in) :: this
    integer, intent(in) :: unit
    integer(dik), intent(in) :: parents, components, peers
    write (unit, "(1x,A)") "Components of pp_remnant_t:"
    write (unit, "(1x,A,F10.3)") "Initial center of mass energy: ", &
        this%gev_initial_cme
    write (unit, "(1x,A,F10.3)") "Actual center of mass energy: ", &
        this%get_gev_actual_cme ()
    write (unit, "(1x,A,F10.3)") "Total Momentum Fraction is: ", this%X
    if (components>0) then
        write (unit, "(3x,A)") "Proton 1:"
        call this%proton(1)%print_to_unit (unit, parents, components-1, peers)
        write (unit, "(3x,A)") "Proton 2:"
        call this%proton(2)%print_to_unit (unit, parents, components-1, peers)
    end if
    ! write (unit, "(1x,A,F7.2)") "Total Momentum Fraction: ", &
    !     this%momentum_fraction
end subroutine pp_remnant_print_to_unit

```

<Muli remnant: PP remnant: TBP>+≡

```

    procedure, nopass :: get_type => pp_remnant_get_type

```

<Muli remnant: procedures>+≡

```

pure subroutine pp_remnant_get_type (type)
    character(:), allocatable, intent(out) :: type
    allocate (type, source="pp_remnant_t")
end subroutine pp_remnant_get_type

```

```

<Muli remnant: PP remnant: TBP>+≡
  procedure :: initialize => pp_remnant_initialize

<Muli remnant: procedures>+≡
  subroutine pp_remnant_initialize (this, muli_dir, &
    lhpdf_dir, lhpdf_file, lhpdf_member)
    class(pp_remnant_t), intent(out) :: this
    character(*), intent(in) :: muli_dir, lhpdf_dir, lhpdf_file
    integer, intent(in) :: lhpdf_member
    logical :: exist
    allocate (this%pdf_norm)
    ! call InitPDFset (lhpdf_dir // lhpdf_file)
    ! call InitPDF (lhpdf_member)
    print *, "looking for previously generated pdf integrals..."
    inquire (file=muli_dir // "/pdf_norm_" // lhpdf_file // &
      ".xml", exist=exist)
    if (exist) then
      print *, "found. Starting deserialization..."
      call this%pdf_norm%deserialize (name="pdf_norm_" // lhpdf_file, &
        file=muli_dir // "/pdf_norm_" // lhpdf_file // ".xml")
      print *, "done."
    else
      print *, "No integrals found. Starting generation..."
      call this%pdf_norm%scan ()
      print *, "done."
      call this%pdf_norm%serialize (name="pdf_norm_" // lhpdf_file, &
        file=muli_dir // "/pdf_norm_" // lhpdf_file // ".xml")
    end if
    call this%proton(1)%initialize (this%pdf_norm)
    call this%proton(2)%initialize (this%pdf_norm)
    this%initialized = .true.
    ! call this%print_all ()
  end subroutine pp_remnant_initialize

<Muli remnant: PP remnant: TBP>+≡
  procedure :: finalize => pp_remnant_finalize

<Muli remnant: procedures>+≡
  subroutine pp_remnant_finalize (this)
    class(pp_remnant_t), intent(inout) :: this
    call this%proton(1)%finalize ()
    call this%proton(2)%finalize ()
    deallocate (this%pdf_norm)
  end subroutine pp_remnant_finalize

<Muli remnant: PP remnant: TBP>+≡
  procedure :: apply_initial_interaction => &
    pp_remnant_apply_initial_interaction

<Muli remnant: procedures>+≡
  subroutine pp_remnant_apply_initial_interaction (this, gev_cme, x1, &
    x2, pdg_f1, pdg_f2, n1, n2, gev_scale, rnd1, rnd2)
    class(pp_remnant_t), intent(inout) :: this
    real(default), intent(in)::gev_cme,x1,x2,gev_scale,rnd1,rnd2
    integer, intent(in) :: pdg_f1, pdg_f2, n1, n2

```

```

if (this%initialized) then
  call this%proton(1)%apply_initial_splitting &
    (n1, pdg_f1, x1, gev_scale, rnd1)
  call this%proton(2)%apply_initial_splitting &
    (n2, pdg_f2, x2, gev_scale, rnd2)
  this%X = (one - x1) * (one - x2)
  this%gev_initial_cme = gev_cme
  ! call this%print_all ()
else
  call msg_error ("pp_remnant_apply_initial_interaction: Not yet " // &
    "initialized, call pp_remnant_initialize first!")
end if
end subroutine pp_remnant_apply_initial_interaction

```

<Muli remnant: PP remnant: TBP>+≡
 procedure :: reset => pp_remnant_reset

<Muli remnant: procedures>+≡
 subroutine pp_remnant_reset (this)
 class(pp_remnant_t), intent(inout) :: this
 call this%proton(1)%reset ()
 call this%proton(2)%reset ()
 this%X = one
end subroutine pp_remnant_reset

<Muli remnant: PP remnant: TBP>+≡
 procedure :: replace_parton => pp_remnant_replace_parton

<Muli remnant: procedures>+≡
 subroutine pp_remnant_replace_parton (this, proton_id, old_id, &
 new_id, pdg_f, x_proton, gev_scale)
 class(pp_remnant_t), intent(inout) :: this
 integer, intent(in) :: proton_id, old_id, new_id, pdg_f
 real(default), intent(in) :: x_proton, gev_scale
 call this%proton(proton_id)%replace_is_parton &
 (old_id, new_id, pdg_f, x_proton, gev_scale)
end subroutine pp_remnant_replace_parton

<Muli remnant: PP remnant: TBP>+≡
 procedure :: momentum_pdf => pp_remnant_momentum_pdf

<Muli remnant: procedures>+≡
 subroutine pp_remnant_momentum_pdf &
 (this, x_proton, gev2_scale, n, pdg_f, pdf)
 class(pp_remnant_t), intent(in) :: this
 real(default), intent(in) :: x_proton, gev2_scale
 integer, intent(in) :: n, pdg_f
 real(default), intent(out) :: pdf
 if (n==1 .or. n==2) then
 if (x_proton <= this%proton(n)%momentum_fraction) then
 if (pdg_f == PDG_FLAVOR_g) then
 call this%proton(n)%momentum_flavor_pdf (sqrt(Gev2_scale), &
 x_proton / this%proton(n)%momentum_fraction, &
 LHA_FLAVOR_g, pdf)

```

        else
            call this%proton(n)%momentum_flavor_pdf (sqrt(GeV2_scale), &
                x_proton / this%proton(n)%momentum_fraction, &
                pdg_f, pdf)
        end if
        pdf = pdf * this%proton(n)%momentum_fraction
    else
        pdf = zero
    end if
else
    call msg_error ("pp_remnant_momentum_pdf: n must be either 1 or 2, " &
        // "but it is " // char (str (n)) // ".")
    stop
end if
end subroutine pp_remnant_momentum_pdf

```

<Multi remnant: PP remnant: TBP>+≡

```

    procedure :: parton_pdf => pp_remnant_parton_pdf

```

<Multi remnant: procedures>+≡

```

subroutine pp_remnant_parton_pdf (this, x_proton, gev2_scale, n, pdg_f, pdf)
    class(pp_remnant_t), intent(in) :: this
    real(default), intent(in) :: x_proton, gev2_scale
    integer, intent(in) :: n, pdg_f
    real(default), intent(out) :: pdf
    if (n==1 .or. n==2) then
        if (x_proton <= this%proton(n)%momentum_fraction) then
            if (pdg_f == PDG_FLAVOR_g) then
                call this%proton(n)%parton_flavor_pdf (sqrt(GeV2_scale), &
                    x_proton/this%proton(n)%momentum_fraction, LHA_FLAVOR_g, &
                    pdf)
            else
                call this%proton(n)%parton_flavor_pdf (sqrt(GeV2_scale), &
                    x_proton/this%proton(n)%momentum_fraction, pdg_f, pdf)
            end if
            pdf = pdf * this%proton(n)%momentum_fraction
        else
            pdf = zero
        end if
    else
        call msg_error ("pp_remnant_parton_pdf: n must be either 1 or 2, " &
            // "but it is " // char (str (n)) // ".")
        stop
    end if
end subroutine pp_remnant_parton_pdf

```

<Multi remnant: PP remnant: TBP>+≡

```

    procedure :: apply_interaction => pp_remnant_apply_interaction

```

<Multi remnant: procedures>+≡

```

subroutine pp_remnant_apply_interaction (this, qcd_2_2)
    class(pp_remnant_t), intent(inout) :: this
    class(qcd_2_2_class), intent(in) :: qcd_2_2
    integer, dimension(4) :: lha_f

```

```

integer, dimension(2) :: int_k
real(default) :: gev_pt
real(default), dimension(2) :: mom_f
integer :: n
mom_f = qcd_2_2%get_remnant_momentum_fractions ()
lha_f = qcd_2_2%get_lha_flavors ()
int_k = qcd_2_2%get_pdf_int_kinds ()
gev_pt = qcd_2_2%get_gev_scale ()
! print *, "pp_remnant_apply_interaction", mom_f, &
!   qcd_2_2%get_parton_id(1), qcd_2_2%get_parton_id(2), lha_f
do n = 1, 2
  select case (int_k(n))
  case (PDF_VALENCE_DOWN)
    call this%proton(n)%remove_valence_down_quark &
      (qcd_2_2%get_parton_id(n), gev_pt, mom_f(n))
  case (PDF_VALENCE_UP)
    call this%proton(n)%remove_valence_up_quark &
      (qcd_2_2%get_parton_id(n), gev_pt, mom_f(n))
  case (PDF_SEA)
    call this%proton(n)%remove_sea_quark &
      (qcd_2_2%get_parton_id(n), gev_pt, mom_f(n), lha_f(n))
  case (PDF_GLUON)
    call this%proton(n)%remove_gluon &
      (qcd_2_2%get_parton_id(n), gev_pt, mom_f(n))
  end select
end do
this%X = this%proton(1)%momentum_fraction * &
  this%proton(2)%momentum_fraction
end subroutine pp_remnant_apply_interaction

```

<Muli remnant: PP remnant: TBP>+≡
 procedure :: get_pdf_int_weights => pp_remnant_get_pdf_int_weights

<Muli remnant: procedures>+≡
 pure function pp_remnant_get_pdf_int_weights &
 (this, pdf_int_kinds) result (weight)
 class(pp_remnant_t), intent(in) :: this
 real(default) :: weight
 integer, dimension(2), intent(in) :: pdf_int_kinds ! pdf_int_kind
 weight = this%proton(1)%pdf_int_weight (pdf_int_kinds(1)) * &
 this%proton(2)%pdf_int_weight (pdf_int_kinds(2)) !*((this%x)**2)
 end function pp_remnant_get_pdf_int_weights

<Muli remnant: PP remnant: TBP>+≡
 procedure :: get_pdf_int_weight => pp_remnant_get_pdf_int_weight

<Muli remnant: procedures>+≡
 elemental function pp_remnant_get_pdf_int_weight &
 (this, kind1, kind2) result (weight)
 class(pp_remnant_t), intent(in) :: this
 real(double) :: weight
 integer, intent(in) :: kind1, kind2 ! pdf_int_kind
 weight = this%proton(1)%pdf_int_weight(kind1) * &
 this%proton(2)%pdf_int_weight(kind2) !*((this%x)**2)

```

end function pp_remnant_get_pdf_int_weight

<Muli remnant: PP remnant: TBP>+≡
  procedure :: set_pdf_weight => pp_remnant_set_pdf_weight

<Muli remnant: procedures>+≡
  subroutine pp_remnant_set_pdf_weight (this, weights)
    class(pp_remnant_t), intent(inout) :: this
    real(default), dimension(10), intent(in) :: weights
    this%proton(1)%pdf_int_weight = weights(1:5)
    this%proton(2)%pdf_int_weight = weights(6:10)
  end subroutine pp_remnant_set_pdf_weight

<Muli remnant: PP remnant: TBP>+≡
  procedure :: get_gev_initial_cme => pp_remnant_get_gev_initial_cme

<Muli remnant: procedures>+≡
  elemental function pp_remnant_get_gev_initial_cme (this) result (cme)
    class(pp_remnant_t), intent(in) :: this
    real(double) :: cme
    cme = this%gev_initial_cme
  end function pp_remnant_get_gev_initial_cme

<Muli remnant: PP remnant: TBP>+≡
  procedure :: get_gev_actual_cme => pp_remnant_get_gev_actual_cme

<Muli remnant: procedures>+≡
  elemental function pp_remnant_get_gev_actual_cme (this) result (cme)
    class(pp_remnant_t), intent(in) :: this
    real(double) :: cme
    cme = this%gev_initial_cme * this%X
  end function pp_remnant_get_gev_actual_cme

<Muli remnant: PP remnant: TBP>+≡
  procedure :: get_cme_fraction => pp_remnant_get_cme_fraction

<Muli remnant: procedures>+≡
  elemental function pp_remnant_get_cme_fraction (this) result (cme)
    class(pp_remnant_t), intent(in) :: this
    real(double) :: cme
    cme = this%X
  end function pp_remnant_get_cme_fraction

<Muli remnant: PP remnant: TBP>+≡
  procedure :: get_proton_remnant_momentum_fractions => &
    pp_remnant_get_proton_remnant_momentum_fractions

<Muli remnant: procedures>+≡
  pure function pp_remnant_get_proton_remnant_momentum_fractions &
    (this) result (fractions)
    class(pp_remnant_t), intent(in) :: this
    real(double), dimension(2) :: fractions
    fractions = [this%proton(1)%get_momentum_fraction(), &

```

```

        this%proton(2)%get_momentum_fraction()]
end function pp_remnant_get_proton_remnant_momentum_fractions

<Muli remnant: PP remnant: TBP>+≡
    procedure :: get_proton_remnants => pp_remnant_get_proton_remnants

<Muli remnant: procedures>+≡
    subroutine pp_remnant_get_proton_remnants (this, proton1, proton2)
        class(pp_remnant_t), target, intent(in) :: this
        class(proton_remnant_t), intent(out), pointer :: proton1, proton2
        proton1 => this%proton(1)
        proton2 => this%proton(2)
    end subroutine pp_remnant_get_proton_remnants

<Muli remnant: PP remnant: TBP>+≡
    procedure :: get_remnant_parton_flavor_pdf_arrays => &
        pp_remnant_get_remnant_parton_flavor_pdf_arrays

<Muli remnant: procedures>+≡
    subroutine pp_remnant_get_remnant_parton_flavor_pdf_arrays &
        (this, GeV_scale, momentum1, momentum2, pdf1, pdf2)
        class(pp_remnant_t), intent(in) :: this
        real(default), intent(in) :: GeV_scale, momentum1, momentum2
        real(double), dimension(-6:6), intent(out) :: pdf1, pdf2
        call this%proton(1)%parton_flavor_pdf_array (GeV_scale, momentum1, pdf1)
        call this%proton(2)%parton_flavor_pdf_array (GeV_scale, momentum2, pdf2)
    end subroutine pp_remnant_get_remnant_parton_flavor_pdf_arrays

<Muli remnant: interfaces>≡
    interface
        subroutine getxmin (mem, xmin)
            integer, intent(in) :: mem
            double precision, intent(out) :: xmin
        end subroutine getxmin
    end interface

<Muli remnant: interfaces>+≡
    interface
        subroutine getxmax (mem, xmax)
            integer, intent(in) :: mem
            double precision, intent(out) :: xmax
        end subroutine getxmax
    end interface

<Muli remnant: interfaces>+≡
    interface
        subroutine getq2min (mem, q2min)
            integer, intent(in) :: mem
            double precision, intent(out) :: q2min
        end subroutine getq2min
    end interface

```

<Muli remnant: interfaces>+≡

```
interface
  subroutine getq2max (mem, q2max)
    integer, intent(in) :: mem
    double precision, intent(out) :: q2max
  end subroutine getq2max
end interface
```

<Muli remnant: procedures>+≡

```
pure function remnant_dglap_splitting_gqq (z) result(p)
  real(default) :: p
  real(default), intent(in) :: z
  p = (z**2 + (1-z)**2) / two
end function remnant_dglap_splitting_gqq
```

<Muli remnant: procedures>+≡

```
pure function remnant_gluon_pdf_approx (x, p) result (g)
  real(default) :: g
  integer, intent(in) :: p
  real(default), intent(in) :: x
  g = ((1-x)**p) / x
end function remnant_gluon_pdf_approx
```

<Muli remnant: procedures>+≡

```
pure function remnant_norm_0 (xs) result (c0)
  real(default) :: c0
  real(default), intent(in) :: xs
  c0 = 6*xs / (2 - xs * (3 - 3*xs + 2*xs**2))
end function remnant_norm_0
```

<Muli remnant: procedures>+≡

```
pure function remnant_norm_1 (xs) result (c1)
  real(default) :: c1
  real(default), intent(in)::xs
  c1 = 3*xs / (2 - xs**2 * (3-xs) + 3*xs*log(xs))
end function remnant_norm_1
```

<Muli remnant: procedures>+≡

```
pure function remnant_norm_4 (xs) result (c4)
  real(default) :: c4
  real(default), intent(in) :: xs
  real(default) :: y
  if ((one-xs) > 1E-3_default) then
    c4 = 3*xs / (1 + 11*xs + 6*xs*log(xs) + 12*xs**3*log(xs) + &
      18*xs**2*log(xs) + 9*xs**2 - 19*xs**3 - 2*xs**4)
  else
    y=one / (one-xs)
    c4= 1130._default / 11907._default &
      - 10._default * y**5 &
      - 40._default * y**4 / three &
      -160._default * y**3 / 63._default &
      + 50._default * y**2 / 189._default &
```



```

-565._default * y / 3969._default &
-186170._default * (one-xs) / 2750517._default
end if
end function remnant_norm_4

```

(Multi remnant: procedures)+≡

```

pure function remnant_norm (xs, p) result (c)
  real(default) :: c
  real(default), intent(in) :: xs
  integer, intent(in) :: p
  select case (p)
  case (0)
    c = remnant_norm_0 (xs)
  case (1)
    c = remnant_norm_1 (xs)
  case default
    c = remnant_norm_4 (xs)
  end select
end function remnant_norm

```

(Multi remnant: procedures)+≡

```

pure function remnant_twin_pdf_p (x, xs, p) result (qc)
  real(default) :: qc
  real(default), intent(in) :: x, xs
  integer, intent(in) :: p
  qc = remnant_norm (xs, p) * remnant_gluon_pdf_approx (xs + x, p) &
    * remnant_dglap_splitting_gqq (xs / (xs+x)) / (xs+x)
end function remnant_twin_pdf_p

```

(Multi remnant: procedures)+≡

```

elemental function remnant_twin_momentum_4 (xs) result (p)
  real(default) :: p
  real(default), intent(in) :: xs
  if (xs < 0.99_default) then
    p = (-9 * (-1+xs) * xs * (1+xs) * (5+xs*(24+xs)) + &
      12*xs*(1+2*xs)*(1+2*xs*(5+2*xs))*Log(xs))/&
      (8*(1+2*xs)*((-1+xs)*(1+xs*(10+xs))-6*xs*(1+xs)*Log(xs)))
  else
    p = (1-xs) / 6 - (5*(-1+xs)**2) / 63 + (5*(-1+xs)**3) / 216
  end if
end function remnant_twin_momentum_4

```

(Multi remnant: procedures)+≡

```

subroutine gnuplot_integrated_pdf (this, momentum_unit, parton_unit)
  class(proton_remnant_t), intent(in) :: this
  integer, intent(in) :: momentum_unit, parton_unit
  ! real(double), intent(in) :: gev_scale
  integer, parameter :: x_grid = 1000000
  integer, parameter :: q_grid = 100
  integer :: n, m, mem
  real(default) :: x, q, dx, dq, overall_sum, xmin, xmax, &
    q2min, q2max, qmin, qmax

```

```

real(double) :: q2min_dbl, q2max_dbl, xmin_dbl, xmax_dbl
real(double), dimension(-6:6) :: sea_pdf, sea_momentum_pdf_sum, &
    sea_parton_pdf_sum
real(default), dimension(2) :: valence_pdf, valence_momentum_pdf_sum, &
    valence_parton_pdf_sum
real(default), allocatable, dimension(:) :: twin_momentum_pdf_sum
class(multi_parton_t), pointer :: tmp_twin
mem = 1
call GetXmin (mem, xmin_dbl)
call GetXmax (mem, xmax_dbl)
call GetQ2max (mem, q2max_dbl)
call GetQ2min (mem, q2min_dbl)
xmin = xmin_dbl
xmax = xmax_dbl
q2min = q2min_dbl
q2max = q2max_dbl
qmin = sqrt(q2min)
qmax = sqrt(q2max)
print *, "qmin=", qmin, "GeV"
print *, "qmax=", qmax, "GeV"
dx = (xmax-xmin) / x_grid
dq = (qmax-qmin) / q_grid
q = qmin + dq / 2D0
tmp_twin => this%twin_partons%next
n = 0
if (this%n_twins > 0) then
    allocate (twin_momentum_pdf_sum (this%n_twins))
    do while (associated (tmp_twin))
        n = n + 1
        twin_momentum_pdf_sum(n) = tmp_twin%momentum
        tmp_twin => tmp_twin%next
    end do
end if
do m = 1, q_grid
    valence_momentum_pdf_sum = [0D0,0D0]
    valence_parton_pdf_sum = [0D0,0D0]
    sea_momentum_pdf_sum = &
        [0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0]
    sea_parton_pdf_sum = &
        [0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0]
    x = xmin + dx / 2D0
    do n = 1, x_grid
        call this%parton_kind_pdf_array (Q, x, valence_pdf, sea_pdf)
        valence_parton_pdf_sum = valence_parton_pdf_sum + valence_pdf
        sea_parton_pdf_sum = sea_parton_pdf_sum + sea_pdf
        call this%momentum_kind_pdf_array (Q, x, valence_pdf, sea_pdf)
        valence_momentum_pdf_sum = valence_momentum_pdf_sum + valence_pdf
        sea_momentum_pdf_sum = sea_momentum_pdf_sum + sea_pdf
        x = x + dx
    end do
    valence_parton_pdf_sum = valence_parton_pdf_sum * dx
    sea_parton_pdf_sum = sea_parton_pdf_sum * dx
    valence_momentum_pdf_sum = valence_momentum_pdf_sum * dx
    sea_momentum_pdf_sum = sea_momentum_pdf_sum * dx
end do

```

```

    if (this%n_twins > 0) then
      write (momentum_unit, fmt=*) q, &
        sum(valence_momentum_pdf_sum) + &
        sum(sea_momentum_pdf_sum) + sum(twin_momentum_pdf_sum), &
        valence_momentum_pdf_sum, &
        sea_momentum_pdf_sum, &
        twin_momentum_pdf_sum
    else
      write (momentum_unit, fmt=*) q, &
        sum(valence_momentum_pdf_sum) + sum(sea_momentum_pdf_sum), &
        valence_momentum_pdf_sum, &
        sea_momentum_pdf_sum
    end if
    write (parton_unit, fmt=*) q, &
      sum(valence_parton_pdf_sum) + sum(sea_parton_pdf_sum), &
      valence_parton_pdf_sum, &
      sea_parton_pdf_sum
    q = q + dq
  end do
end subroutine gnuplot_integrated_pdf

```

21.11 The Multiple Interactions main module

This file contains the module `muli` which is the multiple parton interactions interface module to `WHIZARD`. `muli` is supposed to run together with initial state radiation. Both share a momentum evolution variable and compete for beam momentum, so the generation of this scale variable must be fully transparent to `WHIZARD`. That is why the corresponding procedures are here, while all other work like phase space integration, flavor generation and treatment of the beam remnant is put into `muli_dsigma`, `muli_mcint` and `muli_remnant`, respectively.

`qcd_2_2_t` is a container class for properties of QCD $2 \rightarrow 2$ interactions. It holds a very condensed internal representation and offers a convenient set of TBP to query all aspects without the burden of the generator internals.

`muli_t` then is an extension of `qcd_2_2_t` that adds generator internals like random number generator, integrated cross-sections, the actual Monte Carlo generator for flavor generation and beam remnants in `tao_rnd`, `dsigma`, `samples` and `beam`, respectively.

```

<muli.f90>≡
  <File header>

  module muli
    use, intrinsic :: iso_fortran_env
  <Use kinds>
    use constants
    use tao_random_numbers !NODEP!
    use muli_base
    use muli_momentum
    use muli_trapezium
    use muli_interactions
    use muli_dsigma

```

```

    use muli_mcint
    use muli_remnant

    <Standard module head>

    <Muli: variables>

    <Muli: public>

    <Muli: types>

contains

    <Muli: procedures>

end module muli

<Muli: variables>≡
    logical, parameter :: muli_default_modify_pdfs = .true.
    integer, parameter :: muli_default_lhapdf_member = 0
    character(*), parameter :: muli_default_lhapdf_file = "cteq6ll.LHpdf"

<Muli: types>≡
    type, extends(qcd_2_2_class) :: qcd_2_2_t
        private
        integer :: process_id = -1
        integer :: integrand_id = -1
        integer, dimension(2) :: parton_ids = [0,0]
        integer, dimension(4) :: flow = [0,0,0,0]
        real(default), dimension(3) :: momentum_fractions = [-one, -one, -one]
        real(default), dimension(3) :: hyperbolic_fractions = [-one, -one, -one]
        contains
        <Muli: QCD22: TBP>
    end type qcd_2_2_t

<Muli: QCD22: TBP>≡
    procedure :: write_to_marker => qcd_2_2_write_to_marker

<Muli: procedures>≡
    subroutine qcd_2_2_write_to_marker (this, marker, status)
        class(qcd_2_2_t), intent(in) :: this
        class(marker_t), intent(inout) :: marker
        integer(dik), intent(out) :: status
        call marker%mark_begin ("qcd_2_2_t")
        call this%mom_write_to_marker (marker, status)
        call marker%mark ("process_id", this%process_id)
        call marker%mark ("integrand_id", this%integrand_id)
        call marker%mark ("momentum_fractions", this%momentum_fractions)
        call marker%mark ("hyperbolic_fractions", this%hyperbolic_fractions)
        call marker%mark_end ("qcd_2_2_t")
    end subroutine qcd_2_2_write_to_marker

<Muli: QCD22: TBP>+≡
    procedure :: read_from_marker => qcd_2_2_read_from_marker

```

<Muli: procedures>+≡

```

subroutine qcd_2_2_read_from_marker (this, marker, status)
  class(qcd_2_2_t), intent(out) :: this
  class(marker_t), intent(inout) :: marker
  integer(dik), intent(out) :: status
  call marker%pick_begin ("qcd_2_2_t", status=status)
  call this%mom_read_from_marker (marker, status)
  call marker%pick ("process_id", this%process_id, status)
  call marker%pick ("integrand_id", this%integrand_id, status)
  call marker%pick ("momentum_fractions", this%momentum_fractions, status)
  call marker%pick &
    ("hyperbolic_fractions", this%hyperbolic_fractions, status)
  call marker%pick_end ("qcd_2_2_t", status=status)
end subroutine qcd_2_2_read_from_marker

```

<Muli: QCD22: TBP>+≡

```

procedure :: print_to_unit => qcd_2_2_print_to_unit

```

<Muli: procedures>+≡

```

subroutine qcd_2_2_print_to_unit (this, unit, parents, components, peers)
  class(qcd_2_2_t), intent(in) :: this
  integer, intent(in) :: unit
  integer(dik), intent(in) :: parents, components, peers
  integer, dimension(2,4) :: flow
  integer :: index
  if (parents > i_zero) &
    call this%mom_print_to_unit (unit, parents-1, components, peers)
  write (unit, "(1x,A)") "Components of qcd_2_2_t:"
  write (unit, "(3x,A,I3)") "Process id is:      ", this%get_process_id ()
  write (unit, "(3x,A,I3)") "Integrand id is:    ", this%get_integrand_id ()
  if (this%get_integrand_id () > 0) then
    write (unit, "(3x,A,4(I3))") "LHA Flavors are:    ", &
      this%get_lha_flavors ()
    write (unit, "(3x,A,4(I3))") "PDG Flavors are:    ", &
      this%get_pdg_flavors ()
    write (unit, "(3x,A,2(I3))") "Parton kinds are:   ", &
      this%get_parton_kinds ()
    write (unit, "(3x,A,2(I3))") "PDF int kinds are:  ", &
      this%get_pdf_int_kinds ()
    write (unit, "(3x,A,2(I3))") "Diagram kind is:    ", &
      this%get_diagram_kind ()
  end if
  call this%get_color_correlations (1, index, flow)
  write (unit, "(3x,A,4(I0))") "Color Permutations: ", this%flow
  write (unit, "(3x,A)") "Color Connections:"
  write (unit, &
    '("  (" ,I0," ,",I0," )+(" ,I0," ,",I0," )->(" ,I0," ,",I0,&
    &")+(" ,I0," ,",I0," )")') flow
  write (unit, "(3x,A,E14.7)") "Evolution scale is: ", &
    this%get_unit2_scale ()
  write (unit, "(3x,A,E14.7)") "Momentum boost is:  ", &
    this%get_momentum_boost ()
  write (unit, "(3x,A,2(E14.7))") "Remnant momentum fractions are: ", &
    this%get_remnant_momentum_fractions ()

```

```

        write (unit, "(3x,A,2(E14.7))") "Total momentum fractions are: ", &
            this%get_total_momentum_fractions ()
    end subroutine qcd_2_2_print_to_unit

<Muli: QCD22: TBP>+≡
    procedure, nopass :: get_type => qcd_2_2_get_type

<Muli: procedures>+≡
    pure subroutine qcd_2_2_get_type (type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="qcd_2_2_t")
    end subroutine qcd_2_2_get_type

<Muli: QCD22: TBP>+≡
    procedure :: get_process_id => qcd_2_2_get_process_id

<Muli: procedures>+≡
    elemental function qcd_2_2_get_process_id (this) result (id)
        class(qcd_2_2_t), intent(in) :: this
        integer :: id
        id = this%process_id
    end function qcd_2_2_get_process_id

<Muli: QCD22: TBP>+≡
    procedure :: get_integrand_id => qcd_2_2_get_integrand_id

<Muli: procedures>+≡
    elemental function qcd_2_2_get_integrand_id (this) result (id)
        class(qcd_2_2_t), intent(in) :: this
        integer :: id
        id = this%integrand_id
    end function qcd_2_2_get_integrand_id

<Muli: QCD22: TBP>+≡
    procedure :: get_diagram_kind => qcd_2_2_get_diagram_kind

<Muli: procedures>+≡
    elemental function qcd_2_2_get_diagram_kind (this) result (kind)
        class(qcd_2_2_t), intent(in) :: this
        integer :: kind
        kind = valid_processes (6, this%process_id)
    end function qcd_2_2_get_diagram_kind

```

This is one more hack. Before merging into the interleaved algorithm, muli has only cared for summed cross sections, but not in specific color flows. So two different diagrams with equal cross sections were summed up to diagram kind 1. Now muli also generates color flows, so we must divide diagram kind 1 into diagram color kind 0 and diagram color kind 1.

```

<Muli: QCD22: TBP>+≡
    procedure :: get_diagram_color_kind => qcd_2_2_get_diagram_color_kind

```

```

<Muli: procedures>+=
  pure function qcd_2_2_get_diagram_color_kind (this) result (kind)
    class(qcd_2_2_t), intent(in) :: this
    integer :: kind
    kind = valid_processes (6, this%process_id)
    if (kind == 1) then
      if (product (valid_processes (1:2, this%process_id)) > 0) then
        kind = 0
      end if
    end if
  end function qcd_2_2_get_diagram_color_kind

<Muli: QCD22: TBP>+=
  procedure :: get_io_kind => qcd_2_2_get_io_kind

<Muli: procedures>+=
  elemental function qcd_2_2_get_io_kind (this) result (kind)
    class(qcd_2_2_t), intent(in) :: this
    integer :: kind
    kind = valid_processes (5, this%process_id)
  end function qcd_2_2_get_io_kind

<Muli: QCD22: TBP>+=
  procedure :: get_lha_flavors => qcd_2_2_get_lha_flavors

<Muli: procedures>+=
  pure function qcd_2_2_get_lha_flavors (this) result (lha)
    class(qcd_2_2_t), intent(in) :: this
    integer, dimension(4) :: lha
    lha = valid_processes (1:4, this%process_id)
  end function qcd_2_2_get_lha_flavors

<Muli: QCD22: TBP>+=
  procedure :: get_pdg_flavors => qcd_2_2_get_pdg_flavors

<Muli: procedures>+=
  pure function qcd_2_2_get_pdg_flavors (this) result (pdg)
    class(qcd_2_2_t), intent(in) :: this
    integer, dimension(4) :: pdg
    pdg = this%get_lha_flavors ()
    where (pdg == 0) pdg = 21
  end function qcd_2_2_get_pdg_flavors

<Muli: QCD22: TBP>+=
  procedure :: get_parton_id => qcd_2_2_get_parton_id

<Muli: procedures>+=
  pure function qcd_2_2_get_parton_id (this, n) result (id)
    class(qcd_2_2_t), intent(in) :: this
    integer, intent(in) :: n
    integer :: id
    id = this%parton_ids (n)
  end function qcd_2_2_get_parton_id

```

```

<Muli: QCD22: TBP>+=
  procedure :: get_parton_kinds => qcd_2_2_get_parton_kinds
<Muli: procedures>+=
  pure function qcd_2_2_get_parton_kinds (this) result (kinds)
    class(qcd_2_2_t), intent(in) :: this
    integer, dimension(2) :: kinds
    kinds = this%get_pdf_int_kinds ()
    kinds(1) = parton_kind_of_int_kind (kinds(1))
    kinds(2) = parton_kind_of_int_kind (kinds(2))
  end function qcd_2_2_get_parton_kinds

<Muli: QCD22: TBP>+=
  procedure :: get_pdf_int_kinds => qcd_2_2_get_pdf_int_kinds
<Muli: procedures>+=
  pure function qcd_2_2_get_pdf_int_kinds (this) result (kinds)
    class(qcd_2_2_t), intent(in) :: this
    integer, dimension(2) :: kinds
    kinds = double_pdf_kinds (1:2, this%integrand_id)
  end function qcd_2_2_get_pdf_int_kinds

<Muli: QCD22: TBP>+=
  procedure :: get_momentum_boost => qcd_2_2_get_momentum_boost
<Muli: procedures>+=
  elemental function qcd_2_2_get_momentum_boost (this) result (boost)
    class(qcd_2_2_t), intent(in) :: this
    real(default) :: boost
    boost = - one
    ! print('("qcd_2_2_get_momentum_boost: not yet implemented.")')
    ! boost = this%momentum_boost
  end function qcd_2_2_get_momentum_boost

<Muli: QCD22: TBP>+=
  procedure :: get_hyperbolic_fractions => qcd_2_2_get_hyperbolic_fractions
<Muli: procedures>+=
  pure function qcd_2_2_get_hyperbolic_fractions (this) result (fractions)
    class(qcd_2_2_t), intent(in) :: this
    real(double), dimension(3) :: fractions
    fractions = this%hyperbolic_fractions
  end function qcd_2_2_get_hyperbolic_fractions

<Muli: QCD22: TBP>+=
  procedure :: get_remnant_momentum_fractions => &
    qcd_2_2_get_remnant_momentum_fractions
<Muli: procedures>+=
  pure function qcd_2_2_get_remnant_momentum_fractions &
    (this) result (fractions)
    class(qcd_2_2_t), intent(in) :: this
    real(default), dimension(2) :: fractions
    fractions = this%momentum_fractions(1:2)
  end function qcd_2_2_get_remnant_momentum_fractions

```



```

<Muli: QCD22: TBP>+=
  procedure :: get_total_momentum_fractions => &
    qcd_2_2_get_total_momentum_fractions

<Muli: procedures>+=
  pure function qcd_2_2_get_total_momentum_fractions &
    (this) result (fractions)
    class(qcd_2_2_t), intent(in) :: this
    real(default), dimension(2) :: fractions
    fractions = [-one, -one]
    ! fractions = this%hyperbolic_fractions(1:2) * &
    !   this%beam%get_proton_remnant_momentum_fractions()
  end function qcd_2_2_get_total_momentum_fractions

<Muli: QCD22: TBP>+=
  procedure :: get_color_flow => qcd_2_2_get_color_flow

<Muli: procedures>+=
  pure function qcd_2_2_get_color_flow (this) result (flow)
    class(qcd_2_2_t), intent(in) :: this
    integer, dimension(4) :: flow
    flow = this%flow
  end function qcd_2_2_get_color_flow

<Muli: QCD22: TBP>+=
  procedure :: get_color_correlations => qcd_2_2_get_color_correlations

<Muli: procedures>+=
  subroutine qcd_2_2_get_color_correlations &
    (this, start_index, final_index, flow)
    class(qcd_2_2_t), intent(in) :: this
    integer, intent(in) :: start_index
    integer, intent(out) :: final_index
    integer, dimension(2,4), intent(out) :: flow
    integer :: pos, f_end, f_beginning
    final_index = start_index
    !!! We set all flows to i_zero. i_zero means no connection.
    flow = reshape([0,0,0,0,0,0,0,0],[2,4])
    !!! look at all four possible ends of color lines
    do f_end = 1, 4
      !!! The beginning of of this potential line is stored in flow.
      !!! i_zero means no line.
      f_beginning = this%flow(f_end)
      !!! Is there a line beginning at f_beginning and ending at f_end?
      if (f_beginning > 0) then
        !!! yes it is. we get a new number for this new line
        final_index = final_index + 1
        !!! Is this line beginning in the initial state?
        if (f_beginning < 3) then
          !!! Yes it is. lets connect the color entry of f_begin.
          flow(1,f_beginning) = final_index
        else
          !!! No, it's the final state.
          !!! lets connect the anticolor entry of f_begin.
          flow(2,f_beginning) = final_index
        end if
      end if
    end do
  end subroutine

```

```

        end if
        !!! Is this line ending in the final state?
        if (f_end > 2) then
            !!! Yes it is. lets connect the color entry of f_end.
            flow(1,f_end) = final_index
        else
            !!! No, it's the initial state.
            !!! Lets connect the anticolor entry of f_end.
            flow(2,f_end) = final_index
        end if
    end if
end do
end subroutine qcd_2_2_get_color_correlations

```

<Muli: QCD22: TBP>+≡

```

generic :: initialize => qcd_2_2_initialize
procedure :: qcd_2_2_initialize

```

<Muli: procedures>+≡

```

subroutine qcd_2_2_initialize (this, gev2_s, process_id, &
    integrand_id, parton_ids, flow, hyp, cart)
    class(qcd_2_2_t), intent(out) :: this
    real(default), intent(in) :: gev2_s
    integer, intent(in) :: process_id, integrand_id
    integer, dimension(2), intent(in) :: parton_ids
    integer, dimension(4), intent(in) :: flow
    real(default), dimension(3), intent(in)::hyp
    real(default), dimension(3), intent(in), optional :: cart
    call this%initialize (gev2_s)
    this%process_id = process_id
    this%integrand_id = integrand_id
    this%parton_ids = parton_ids
    this%flow = flow
    this%hyperbolic_fractions = hyp
    if (present (cart)) then
        this%momentum_fractions = cart
    else
        this%momentum_fractions = h_to_c_param (hyp)
    end if
end subroutine qcd_2_2_initialize

```

21.11.1 The main Multiple Interactions type

<Muli: public>≡

```

public :: muli_t

```

<Muli: types>+≡

```

type, extends(qcd_2_2_t) :: muli_t
    real(default) :: GeV2_scale_cutoff
    logical :: modify_pdfs = muli_default_modify_pdfs
    !!! Pt chain status
    logical :: finished = .false.
    logical :: exceeded = .false.

```

```

    !!! Timers
    real(default) :: init_time = zero
    real(default) :: pt_time = zero
    real(default) :: partons_time = zero
    real(default) :: confirm_time = zero
    !!! Generator internals
    logical :: initialized = .false.
    logical :: initial_interaction_given = .false.
    real(default) :: mean = one
    real(default), dimension(0:16) :: start_integrals = &
        [0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0]
    type(tao_random_state) :: tao_rnd
    type(multi_trapezium_tree_t) :: dsigma
    type(sample_inclusive_t) :: samples
    type(pp_remnant_t) :: beam
    !!! These pointers shall not be allocated, deallocated,
    !!! serialized or deserialized explicitly.
    class(multi_trapezium_node_class_t), pointer :: node => null()
contains
    <Muli: muli: TBP>
end type multi_t

```

<Muli: muli: TBP>≡

```

    procedure :: write_to_marker => muli_write_to_marker

```

<Muli: procedures>+≡

```

subroutine muli_write_to_marker (this, marker, status)
    class(multi_t), intent(in) :: this
    class(marker_t), intent(inout) :: marker
    integer(dik), intent(out) :: status
    call marker%mark_begin ("muli_t")
    call qcd_2_2_write_to_marker (this, marker, status)
    call marker%mark ("modify_pdfs", this%modify_pdfs)
    call marker%mark ("initialized", this%initialized)
    call marker%mark &
        ("initial_interaction_given", this%initial_interaction_given)
    call marker%mark ("finished", this%finished)
    call marker%mark ("init_time", this%init_time)
    call marker%mark ("pt_time", this%pt_time)
    call marker%mark ("partons_time", this%partons_time)
    call marker%mark ("confirm_time", this%confirm_time)
    ! call marker%mark_instance (this%start_values, "start_values")
    call marker%mark_instance (this%dsigma, "dsigma")
    call marker%mark_instance (this%samples, "samples")
    call marker%mark_instance (this%beam, "beam")
    call marker%mark_end ("muli_t")
end subroutine muli_write_to_marker

```

<Muli: muli: TBP>+≡

```

    procedure :: read_from_marker => muli_read_from_marker

```

<Muli: procedures>+≡

```

subroutine muli_read_from_marker (this, marker, status)
    class(multi_t), intent(out) :: this

```

```

class(marker_t), intent(inout) :: marker
integer(dik), intent(out) :: status
call marker%pick_begin ("multi_t", status=status)
call qcd_2_2_read_from_marker (this, marker, status)
call marker%pick ("modify_pdfs", this%modify_pdfs, status)
call marker%pick ("initialized", this%initialized, status)
call marker%pick &
    ("initial_interaction_given", this%initial_interaction_given, status)
call marker%pick ("finished", this%finished, status)
call marker%pick ("init_time", this%init_time, status)
call marker%pick ("pt_time", this%pt_time, status)
call marker%pick ("partons_time", this%partons_time, status)
call marker%pick ("confirm_time", this%confirm_time, status)
! call marker%pick_instance &
!     ("start_values", this%start_values, status=status)
call marker%pick_instance ("dsigma", this%dsigma, status=status)
call marker%pick_instance ("samples", this%samples, status=status)
call marker%pick_instance ("beam", this%beam, status=status)
call marker%pick_end ("multi_t", status)
end subroutine multi_read_from_marker

```

(Muli: muli: TBP)+≡

```

procedure :: print_to_unit => multi_print_to_unit

```

(Muli: procedures)+≡

```

subroutine multi_print_to_unit (this, unit, parents, components, peers)
class(multi_t), intent(in) :: this
integer, intent(in) :: unit
integer(dik), intent(in) :: parents, components, peers
if (parents>0) &
    call qcd_2_2_print_to_unit (this, unit, parents-1, components, peers)
write (unit, "(1x,A)") "Components of multi_t :"
write (unit, "(3x,A)") "Model Parameters:"
write (unit, "(3x,A,E20.10)") "GeV2_scale_cutoff : ", &
    this%GeV2_scale_cutoff
write (unit, "(3x,A,L1)") "Modify PDF          : ", this%modify_pdfs
write (unit, "(3x,A)") "PT Chain Status:"
write (unit, "(3x,A,L1)") "Initialized          : ", this%initialized
write (unit, "(3x,A,L1)") "initial_interaction_given: ", &
    this%initial_interaction_given
write (unit, "(3x,A,L1)") "Finished            : ", this%finished
write (unit, "(3x,A,L1)") "Exceeded            : ", this%exceeded
write (unit, "(3x,A)") "Generator Internals:"
write (unit, "(3x,A,E20.10)") "Mean Value          : ", this%mean
if (components > i_zero) then
    write (unit, "(3x,A,16(E20.10))") "Start Integrals    : ", &
        this%start_integrals(1:16)
    ! write (unit, "(3x,A)") "start_values Component:"
    ! call this%start_values%print_to_unit &
    !     (unit, parents, components-1, peers)
    write (unit, "(3x,A)") "dsigma Component:"
    call this%dsigma%print_to_unit (unit, parents, components-1, peers)
    write (unit, "(3x,A)") "samples Component:"
    call this%samples%print_to_unit (unit, parents, components-1, peers)

```

```

        write (unit, "(3x,A)") "beam Component:"
        call this%beam%print_to_unit (unit, parents, components-1, peers)
    else
        write (unit, "(3x,A)") "Skipping Derived-Type Components."
    end if
    ! call print_comp_pointer (this%start_node, unit, i_zero, &
    !     min(components-1,i_one), i_zero, "start_node")
    ! call serialize_print_comp_pointer (this%node, unit, i_zero, &
    !     min(components-1,i_one), i_zero, "node")
end subroutine multi_print_to_unit

```

<Multi: multi: TBP>+≡

```

    procedure, nopass :: get_type => multi_get_type

```

<Multi: procedures>+≡

```

    pure subroutine multi_get_type(type)
        character(:), allocatable, intent(out) :: type
        allocate (type, source="multi_t")
    end subroutine multi_get_type

```

<Multi: multi: TBP>+≡

```

    generic :: initialize => multi_initialize
    procedure :: multi_initialize

```

<Multi: procedures>+≡

```

    subroutine multi_initialize (this, GeV2_scale_cutoff, gev2_s, &
        multi_dir, random_seed)
        class(multi_t), intent(out) :: this
        real(kind=default), intent(in) :: gev2_s, GeV2_scale_cutoff
        character(*), intent(in) :: multi_dir
        integer, intent(in), optional :: random_seed
        real(double) :: time
        logical :: exist
        type(multi_dsigma_t) :: dsigma_aq
        character(3) :: lhpdf_member_c
        call cpu_time(time)
        this%init_time = this%init_time-time
        print *, "multi_initialize: The MULI modules are still not fully " &
            // "populated, so MULI might generate some dummy values instead " &
            // "of real Monte Carlo generated interactions."
        print *, "Given Parameters:"
        print *, "GeV2_scale_cutoff=", GeV2_scale_cutoff
        print *, "multi_dir=", multi_dir
        print *, "lhpdf_dir=", ""
        print *, "lhpdf_file=", multi_default_lhpdf_file
        print *, "lhpdf_member=", multi_default_lhpdf_member
        print *, ""
        call this%transverse_mom_t%initialize (gev2_s)
        call this%beam%initialize (multi_dir, lhpdf_dir="", &
            lhpdf_file=multi_default_lhpdf_file, &
            lhpdf_member=multi_default_lhpdf_member)
        this%GeV2_scale_cutoff = GeV2_scale_cutoff
        if (present(random_seed)) then
            call tao_random_create (this%tao_rnd, random_seed)

```

```

else
    call tao_random_create (this%tao_rnd, 1)
end if
print *, "looking for previously generated root function..."
call integer_with_leading_zeros (multi_default_lhapdf_member, 3, &
    lhpdf_member_c)
inquire (file=multi_dir//"/dsigma_"//multi_default_lhapdf_file//".xml", &
    exist=exist)
if (exist) then
    print *, "found. Starting deserialization..."
    call this%dsigma%deserialize &
        (name="dsigma_"//multi_default_lhapdf_file//"/_"//lhpdf_member_c, &
        file=multi_dir//"/dsigma_"//multi_default_lhapdf_file//".xml")
    ! call this%dsigma%print_all ()
    print *, "done. Starting generation of plots..."
    call this%dsigma%gnuplot (multi_dir)
    print *, "done."
else
    print *, &
        "No root function found. Starting generation of root function..."
    call dsigma_aq%generate (GeV2_scale_cutoff, gev2_s, this%dsigma)
    print *, "done. Starting serialization of root function..."
    call this%dsigma%serialize &
        (name="dsigma_"//multi_default_lhapdf_file//"/_"//lhpdf_member_c, &
        file=multi_dir//"/dsigma_"//multi_default_lhapdf_file//".xml")
    print *, "done. Starting serialization of generator..."
    call dsigma_aq%serialize &
        (name="dsigma_aq_"//multi_default_lhapdf_file//"/_" // &
        lhpdf_member_c, file=multi_dir//"/dsigma_aq_" // &
        multi_default_lhapdf_file//".xml")
    print *, "done. Starting generation of plots..."
    call this%dsigma%gnuplot (multi_dir)
    print *, "done."
end if
print *, ""
print *, "looking for previously generated samples..."
inquire (file=multi_dir//"/samples.xml", exist=exist)
if (exist) then
    print *, "found. Starting deserialization..."
    call this%samples%deserialize ("samples",multi_dir//"/samples.xml")
else
    print *, "No samples found. Starting with default initialization."
    call this%samples%initialize (4, int_sizes_all, int_all, 1E-2_default)
end if
call this%restart ()
this%initialized = .true.
call cpu_time (time)
this%init_time = this%init_time + time
end subroutine multi_initialize

```

$\langle \text{Muli: muli: TBP} \rangle + \equiv$

procedure :: apply_initial_interaction => multi_apply_initial_interaction

$\langle \text{Muli: procedures} \rangle + \equiv$

```

subroutine muli_apply_initial_interaction (this, GeV2_s, &
    x1, x2, pdg_f1, pdg_f2, n1, n2)
    class(muli_t), intent(inout) :: this
    real(default), intent(in) :: GeV2_s, x1, x2
    integer, intent(in):: pdg_f1, pdg_f2, n1, n2
    real(default) :: rnd1, rnd2, time
    if (this%initialized) then
        call cpu_time (time)
        this%init_time = this%init_time - time
        print *, "muli_apply_initial_interaction:"
        print *, "gev2_s=", gev2_s
        print *, "x1=", x1
        print *, "x2=", x2
        print *, "pdg_f1=", pdg_f1
        print *, "pdg_f2=", pdg_f2
        print *, "n1=", n1
        print *, "n2=", n2
        call tao_random_number (this%tao_rnd, rnd1)
        call tao_random_number (this%tao_rnd, rnd2)
        call cpu_time (time)
        this%init_time = this%init_time + time
        call this%beam%apply_initial_interaction &
            (sqrt (gev2_s), x1, x2, pdg_f1, pdg_f2, n1, n2,&
            !!! This is a hack: We should give the pt scale of the initial
            !!! interaction. Unfortunately, we only know the invariant
            !!! mass shat. shat/2 is the upper bound of pt, so we
            !!! use it for now.
            sqrt(gev2_s) * x1 *x2 / 2D0, &
            rnd1, rnd2)
        this%initial_interaction_given = .true.
    else
        print *, &
            "muli_apply_initial_interaction: call muli_initialize first. STOP"
        stop
    end if
end subroutine muli_apply_initial_interaction

```

<Muli: muli: TBP>+≡
 procedure :: finalize => muli_finalize

<Muli: procedures>+≡
 subroutine muli_finalize (this)
 class(muli_t), intent(inout) :: this
 print *, "muli_finalize"
 nullify (this%node)
 call this%dsigma%finalize ()
 call this%samples%finalize ()
 call this%beam%finalize ()
 end subroutine muli_finalize

<Muli: muli: TBP>+≡
 procedure :: stop_trainer => muli_stop_trainer

```

<Muli: procedures>+≡
  subroutine muli_stop_trainer (this)
    class(muli_t), intent(inout) :: this
    print *, "muli_stop_trainer: DUMMY!"
  end subroutine muli_stop_trainer

<Muli: muli: TBP>+≡
  procedure :: reset_timer => muli_reset_timer

<Muli: procedures>+≡
  subroutine muli_reset_timer (this)
    class(muli_t), intent(inout) :: this
    this%init_time = 0D0
    this%pt_time = 0D0
    this%partons_time = 0D0
    this%confirm_time = 0D0
  end subroutine muli_reset_timer

<Muli: muli: TBP>+≡
  procedure :: restart => muli_restart

<Muli: procedures>+≡
  subroutine muli_restart (this)
    class(muli_t), intent(inout) :: this
    call this%dsigma%get_rightmost (this%node)
    call this%beam%reset ()
    ! print *, associated(this%node)
    ! nullify (this%node)
    this%finished = .false.
    this%process_id = -1
    this%integrand_id = -1
    this%momentum_fractions = [-1D0,-1D0,1D0]
    this%hyperbolic_fractions = [-1D0,-1D0,1D0]
    ! this%start_values%process_id = -1
    ! this%start_values%integrand_id = -1
    ! this%start_values%momentum_fractions = [-1D0,-1D0,1D0]
    ! this%start_values%hyperbolic_fractions = [-1D0,-1D0,1D0]
    this%start_integrals = &
      [0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0,0D0]
  end subroutine muli_restart

<Muli: muli: TBP>+≡
  procedure :: is_initialized => muli_is_initialized

<Muli: procedures>+≡
  elemental function muli_is_initialized (this) result (res)
    logical :: res
    class(muli_t), intent(in) :: this
    res = this%initialized
  end function muli_is_initialized

<Muli: muli: TBP>+≡
  procedure :: is_initial_interaction_given => &
    muli_is_initial_interaction_given

```



```

<Muli: procedures>+≡
    elemental function muli_is_initial_interaction_given (this) result (res)
        logical :: res
        class(muli_t), intent(in) :: this
        res = this%initial_interaction_given
    end function muli_is_initial_interaction_given

<Muli: muli: TBP>+≡
    procedure :: is_finished => muli_is_finished

<Muli: procedures>+≡
    elemental function muli_is_finished (this) result (res)
        logical :: res
        class(muli_t), intent(in) :: this
        res = this%finished
    end function muli_is_finished

<Muli: muli: TBP>+≡
    procedure :: enable_remnant_pdf => muli_enable_remnant_pdf

<Muli: procedures>+≡
    subroutine muli_enable_remnant_pdf (this)
        class(muli_t), intent(inout) :: this
        this%modify_pdfs = .true.
    end subroutine muli_enable_remnant_pdf

<Muli: muli: TBP>+≡
    procedure :: disable_remnant_pdf => muli_disable_remnant_pdf

<Muli: procedures>+≡
    subroutine muli_disable_remnant_pdf (this)
        class(muli_t), intent(inout) :: this
        this%modify_pdfs = .false.
    end subroutine muli_disable_remnant_pdf

<Muli: muli: TBP>+≡
    procedure :: generate_gev2_pt2 => muli_generate_gev2_pt2

<Muli: procedures>+≡
    subroutine muli_generate_gev2_pt2 (this, gev2_start_scale, gev2_new_scale)
        class(muli_t), intent(inout) :: this
        real(kind=default), intent(in) :: gev2_start_scale
        real(kind=default), intent(out) :: gev2_new_scale
        real(double) :: time
        call cpu_time (time)
        this%pt_time = this%pt_time - time
        call this%set_gev2_scale (gev2_start_scale)
        this%start_integrals = this%node%approx_integral (this%get_unit_scale ())
        call this%generate_next_scale ()
        gev2_new_scale = this%get_gev2_scale ()
        call cpu_time (time)
        this%pt_time = this%pt_time + time
    end subroutine muli_generate_gev2_pt2

```

```

<Muli: muli: TBP>+≡
  procedure :: generate_partons => multi_generate_partons

<Muli: procedures>+≡
  subroutine multi_generate_partons (this, n1, n2, x_proton_1, x_proton_2, &
    pdg_f1, pdg_f2, pdg_f3, pdg_f4)
    class(muli_t), intent(inout) :: this
    integer, intent(in) :: n1, n2
    real(kind=default), intent(out) :: x_proton_1, x_proton_2
    integer, intent(out) :: pdg_f1, pdg_f2, pdg_f3, pdg_f4
    integer, dimension(4) :: pdg_f
    real(double) :: time
    ! print *, "multi_generate_partons: n1=", n1, " n2=", n2
    this%parton_ids(1) = n1
    this%parton_ids(2) = n2
    call cpu_time (time)
    this%partons_time = this%partons_time - time
    this%mean = this%node%approx_value_n (this%get_unit_scale(), &
      this%integrand_id)
    call this%samples%mcgenerate_hit (this%get_unit2_scale(), &
      this%mean, this%integrand_id, this%tao_rnd, this%process_id, &
      this%momentum_fractions)
    ! print *, "multi_generate_partons", this%momentum_fractions
    call this%generate_flow ()
    if (this%modify_pdfs) then
      call cpu_time (time)
      this%partons_time = this%partons_time + time
      this%confirm_time = this%confirm_time - time
      call this%beam%apply_interaction (this)
      call cpu_time (time)
      this%confirm_time = this%confirm_time + time
      this%partons_time = this%partons_time - time
    end if
    x_proton_1 = this%momentum_fractions(1)
    x_proton_2 = this%momentum_fractions(2)
    pdg_f = this%get_pdg_flavors ()
    pdg_f1 = pdg_f(1)
    pdg_f2 = pdg_f(2)
    pdg_f3 = pdg_f(3)
    pdg_f4 = pdg_f(4)
    call cpu_time (time)
    this%partons_time = this%partons_time - time
    call qcd_2_2_print_to_unit (this, output_unit, 100_dik, 100_dik, 100_dik)
  end subroutine multi_generate_partons

```

```

<Muli: muli: TBP>+≡
  procedure :: generate_flow => multi_generate_flow

<Muli: procedures>+≡
  subroutine multi_generate_flow(this)
    class(muli_t), intent(inout)::this
    integer::rnd
    integer::m,n
    logical, dimension(3)::t
    integer, dimension(4)::tmp_flow, tmp_array

```

```

! we initialize with zeros. a i_zero means no line ends here.
this%flow=[0,0,0,0]
! we randomly pick a color flow
call tao_random_number(this%tao_rnd,rnd)
! the third position of multi_flow_stats is the sum of all flow wheights of stratum diagram_kin
! so we generate a random number 0 <= m < sum(weights)
m=modulo(rnd,multi_flow_stats(3,this%get_diagram_color_kind()))
! lets visit all color flows of stratum diagram_kind. the first and second position of multi_fl
! tells us the index of the first and the last valid color flow.
do n=multi_flow_stats(1,this%get_diagram_color_kind()),multi_flow_stats(2,this%get_diagram_color
! now we remove the weight of flow n from our random number.
m=m-multi_flows(0,n)
! this is how we pick a flow.
if (m<0) then
! the actual flow
this%flow=multi_flows(1:4,n)
exit
end if
end do
! the diagram kind contains a primitive diagram and all diagramms which can be derived by
! (1) global charge conjugation
! (2) permutation of the initial state particles
! (3) permutation of the final state particles
! lets see, what transformations we have got in our actual interaction.
tmp_array = this%get_lha_flavors ()
t = multi_get_state_transformations (this%get_diagram_color_kind (), &
tmp_array)
! this%get_lha_flavors ()
! now we have to apply these transformations to our flow.
! (1) means: swap beginning and end of a line. flow is a permutation that maps
! ends to their beginnings, so we apply flow to itself:
!!$ print *, "(0)", this%flow
if (t(1)) then
tmp_flow=this%flow
this%flow=[0,0,0,0]
do n=1,4
if (tmp_flow(n)>0)this%flow(tmp_flow(n))=n
end do
!!$ print *, "(1)", this%flow
end if
if (t(2)) then
! we swap the particles 1 and 2
tmp_flow(1)=this%flow(2)
tmp_flow(2)=this%flow(1)
tmp_flow(3:4)=this%flow(3:4)
!!$ print *, "(2)", tmp_flow
! we swap the beginnings assigned to particle 1 and 2
where(tmp_flow==1)
this%flow=2
elsewhere(tmp_flow==2)
this%flow=1
elsewhere
this%flow=tmp_flow
end where

```

```

!!$      print *, "(2)", this%flow
end if
if (t(3)) then
    ! we swap the particles 3 and 4
    tmp_flow(1:2)=this%flow(1:2)
    tmp_flow(3)=this%flow(4)
    tmp_flow(4)=this%flow(3)
!!$      print *, "(3)", tmp_flow
    ! we swap the beginnings assigned to particle 3 and 4
    where(tmp_flow==3)
        this%flow=4
    elsewhere(tmp_flow==4)
        this%flow=3
    elsewhere
        this%flow=tmp_flow
    end where
!!$      print *, "(3)", this%flow
end if
end subroutine multi_generate_flow

```

<Multi: multi: TBP>+≡

```

procedure :: replace_parton => multi_replace_parton

```

<Multi: procedures>+≡

```

subroutine multi_replace_parton &
    (this, proton_id, old_id, new_id, pdg_f, x_proton, gev_scale)
class(multi_t), intent(inout) :: this
integer, intent(in) :: proton_id, old_id, new_id, pdg_f
real(kind=default), intent(in) :: x_proton, gev_scale
! print *, "multi_replace_parton(", proton_id, old_id, new_id, &
!   pdg_f, x_proton, gev_scale, ")"
if (proton_id==1 .or. proton_id==2) then
    call this%beam%replace_parton &
        (proton_id, old_id, new_id, pdg_f, x_proton, gev_scale)
else
    print *, "multi_replace_parton: proton_id must be 1 or 2, but ", &
        proton_id, " was given."
    stop
end if
end subroutine multi_replace_parton

```

<Multi: multi: TBP>+≡

```

procedure :: get_parton_pdf => multi_get_parton_pdf

```

<Multi: procedures>+≡

```

function multi_get_parton_pdf &
    (this, x_proton, gev2_scale, n, pdg_f) result (pdf)
real(default) :: pdf
class(multi_t), intent(in) :: this
real(default), intent(in) :: x_proton, gev2_scale
integer, intent(in) :: n, pdg_f
call this%beam%parton_pdf (x_proton, gev2_scale, n, pdg_f, pdf)
end function multi_get_parton_pdf

```

```

<Muli: muli: TBP>+≡
  procedure :: get_momentum_pdf => muli_get_momentum_pdf

<Muli: procedures>+≡
  function muli_get_momentum_pdf &
    (this, x_proton, gev2_scale, n, pdg_f) result (pdf)
    real(default) :: pdf
    class(muli_t), intent(in) :: this
    real(default), intent(in) :: x_proton, gev2_scale
    integer, intent(in) :: n, pdg_f
    call this%beam%momentum_pdf (x_proton, gev2_scale, n, pdg_f, pdf)
  end function muli_get_momentum_pdf

<Muli: muli: TBP>+≡
  procedure :: print_timer => muli_print_timer

<Muli: procedures>+≡
  subroutine muli_print_timer(this)
    class(muli_t), intent(in) :: this
    print ("(1x,A,E20.10)", "Init time: ", this%init_time)
    print ("(1x,A,E20.10)", "PT gen time: ", this%pt_time)
    print ("(1x,A,E20.10)", "Partons time: ", this%partons_time)
    print ("(1x,A,E20.10)", "Confirm time: ", this%confirm_time)
    print ("(1x,A,E20.10)", "Overall time: ", &
      this%init_time + this%pt_time + this%partons_time + this%confirm_time)
  end subroutine muli_print_timer

<Muli: muli: TBP>+≡
  procedure :: generate_samples => muli_generate_samples

<Muli: procedures>+≡
  subroutine muli_generate_samples &
    (this, n_total, n_print, integrand_kind, muli_dir, analyse)
    class(muli_t), intent(inout) :: this
    integer(dik), intent(in) :: n_total, n_print
    integer, intent(in) :: integrand_kind
    character(*), intent(in) :: muli_dir
    logical, intent(in) :: analyse
    integer(dik) :: n_inner

    class(muli_trapezium_node_class_t), pointer :: start_node => null()
    class(muli_trapezium_node_class_t), pointer, save :: s_node => null()
    class(muli_trapezium_node_class_t), pointer, save :: node => null()

    character(2) :: prefix
    integer, save :: t_slice, t_region, t_proc, t_subproc, t_max_n = 0
    integer(dik) :: n_t, n_p, n_m
    integer :: n, m, u, unit = 0
    integer(dik) :: n_tries = 0
    integer(dik) :: n_hits = 0
    integer(dik) :: n_over = 0
    integer(dik) :: n_miss = 0
    real(default), save, dimension(3) :: cart_hit
    integer, save, dimension(4) :: t_i_rnd
    ! integer, save, dimension(5) :: r_n_proc

```

```

real(default), dimension(16) :: d_rnd
real(default), save :: t_area, t_dddsigma, t_rnd, t_weight, t_arg
real(default) :: mean = 0D0
real(default) :: time = 0D0
real(default) :: timepa = 0D0
real(default) :: timept = 0D0
real(default) :: timet = 0D0
real(default) :: pts, s_pts = 1D0
real(default) :: pts2 = 1D0
real(default) :: rnd
logical :: running
character(3) :: num
integer :: success = -1
integer :: chain_length = 0
integer :: int_kind
integer :: process_id
real(double), dimension(0:16) :: integral
call this%print_parents ()
n_tries = one
n_inner = n_total / n_print
n_t = i_zero
PRINT: do while (n_t < n_total)
    call cpu_time (time)
    timet = - time
    n_p = i_zero
    INNER: do while (n_p < n_print)
        chain_length = 0
        ! print *, "new chain"
        call this%restart ()
        this%integrand_id = integrand_kind
        call cpu_time (time)
        timept = timept - time
        call this%generate_next_scale (integrand_kind)
        call cpu_time (time)
        timept = timept + time
        CHAIN: do while (.not. this%is_finished ())
            chain_length = chain_length + 1
            n_p = n_p + 1
            call this%confirm ()
            call cpu_time (time)
            timepa = timepa - time
            ! print *, this%get_unit2_scale ()
            call this%samples%mcgenerate_hit (this%get_unit2_scale(), &
                this%mean, this%integrand_id, this%tao_rnd, this%process_id, &
                this%momentum_fractions)
            call cpu_time (time)
            timepa = timepa + time
            timept = timept - time
            call this%generate_next_scale (integrand_kind)
            call cpu_time (time)
            timept = timept + time
        end do CHAIN
        ! print *, "chain length = ", chain_length
    end do INNER
end do PRINT

```

```

n_t = n_t + n_p
call this%samples%sum_up ()
call cpu_time (time)
timet = timet + time
print *, n_t, "/", n_total
print *, "time: ", timet
print *, "pt time: ", timept
print *, "pa time: ", timepa
print *, this%samples%n_tries_sum, this%samples%n_hits_sum, &
      this%samples%n_over_sum
if (this%samples%n_hits_sum > 0) then
  print *, (this%samples%n_hits_sum * 10000) / &
        this%samples%n_tries_sum, (this%samples%n_over_sum * 10000) / &
        this%samples%n_hits_sum
else
  print *, "no hits"
end if
! print ('(7(I11," "),5(E14.7," "))'), n_p, n_print, n_tries, &
!   n_hits,n_over, int((n_hits*1D3)/n_tries), &
!   int((n_over*1D6)/n_tries), n_hits/real(n_over), time1, time2, &
!   time3, this%samples%int_kinds(integrand_kind)%overall_boost
end do print
call integer_with_leading_zeros (integrand_kind, 2, prefix)
if (analyse) then
  call this%samples%int_kinds(integrand_kind)%analyse &
        (multi_dir, prefix//"-")
  call this%samples%int_kinds(integrand_kind)%serialize &
        ("sample_int_kind_"//prefix, &
        multi_dir//"/sample_int_kind_"//prefix//".xml")
end if
call this%samples%int_kinds(integrand_kind)%serialize &
        ("sample_int_kind_"//prefix, &
        multi_dir//"/sample_int_kind_"//prefix//".xml")
end subroutine multi_generate_samples

```

<Muli: muli: TBP>+≡

```

procedure :: fake_interaction => multi_fake_interaction

```

<Muli: procedures>+≡

```

subroutine multi_fake_interaction (this, GeV2_scale, x1, x2, &
      process_id, integrand_id, n1, n2, flow)
  class(multi_t), intent(inout) :: this
  real(default), intent(in) :: GeV2_scale, x1, x2
  integer, intent(in) :: process_id, integrand_id, n1, n2
  integer, dimension(4), intent(in), optional :: flow
  call this%set_gev2_scale (GeV2_scale)
  this%process_id = process_id
  this%integrand_id = integrand_id
  this%parton_ids = [n1, n2]
  if (present (flow)) then
    this%flow = flow
  else
    this%flow = [0,0,0,0]
  end if

```

```

    this%momentum_fractions = [x1, x2, this%get_unit2_scale()]
    call this%beam%apply_interaction (this)
    call this%beam%print_all ()
end subroutine multi_fake_interaction

```

(Multi: multi: TBP)+≡

```

    procedure :: generate_next_scale => multi_generate_next_scale

```

(Multi: procedures)+≡

```

subroutine multi_generate_next_scale (this, integrand_kind)
    class(multi_t), intent(inout) :: this
    integer, intent(in), optional :: integrand_kind
    real(default) :: pts, tmp_pts, rnd
    integer :: tmp_int_kind
    class(multi_trapezium_node_class_t), pointer :: tmp_node
    pts = - one
    if (present (integrand_kind)) then
        call tao_random_number (this%tao_rnd, rnd)
        call generate_single_pts (integrand_kind, &
            this%start_integrals(integrand_kind), &
            this%beam%get_pdf_int_weights &
            (double_pdf_kinds (1:2,integrand_kind)), rnd, this%dsigma, &
            pts, this%node)
    else
        do tmp_int_kind = 1, 16
            call tao_random_number (this%tao_rnd, rnd)
            call generate_single_pts (tmp_int_kind, &
                this%start_integrals(tmp_int_kind), &
                this%beam%get_pdf_int_weights &
                (double_pdf_kinds(1:2,tmp_int_kind)), rnd, &
                this%dsigma, tmp_pts, tmp_node)
            if (tmp_pts > pts) then
                pts = tmp_pts
                this%integrand_id = tmp_int_kind
                this%node => tmp_node
            end if
        end do
    end if
    if (pts > 0) then
        call this%set_unit_scale (pts)
    else
        this%finished = .true.
    end if
    ! print *, this%finished, this%integrand_id
contains
    subroutine generate_single_pts &
        (int_kind, start_int, weight, rnd, int_tree, pts, node)
        integer, intent(in) :: int_kind
        real(default), intent(in) :: start_int, weight, rnd
        type(multi_trapezium_tree_t), intent(in) :: int_tree
        real(default), intent(out) :: pts
        class(multi_trapezium_node_class_t), pointer, intent(out) :: node
        real(default) :: arg
        ! print *, int_kind, start_int, weight, rnd

```



```

    if (weight > 0D0) then
        arg = start_int - log(rnd) / weight
        call int_tree%find_decreasing (arg, int_kind, node)
        if (node%get_l_integral(int_kind) > arg) then
            pts = node%approx_position_by_integral (int_kind, arg)
        else
            pts = -1D0
        end if
    else
        pts = -1D0
    end if
end subroutine generate_single_pts
end subroutine multi_generate_next_scale

```

<Multi: multi: TBP>+≡

```

    procedure :: confirm => multi_confirm

```

<Multi: procedures>+≡

```

    subroutine multi_confirm (this)
        class(multi_t), intent(inout) :: this
        this%mean = this%node%approx_value_n(this%get_unit_scale (), &
            this%integrand_id)
        this%start_integrals = this%node%approx_integral (this%get_unit_scale ())
    end subroutine multi_confirm

```

<multi_cross_sections.f90>≡

```

    ! This is a dummy for multi_cross_sections_module
    module multi_cross_sections_module
    end module multi_cross_sections_module

```

<multi_sampling.f90>≡

```

    ! This is a dummy for multi_sampling_module
    module multi_sampling_module
    end module multi_sampling_module

```

Chapter 22

User Plugin Support

Here we collect interface code that enables the user to inject his own code into the WHIZARD workflow. The code uses data types defined elsewhere, and is referenced in the `eval_trees` module.

These are the modules:

user_code_interface Generic support and specific additions.

sf_user Handle user-defined structure functions.

22.1 User Code Interface

```
(user_code_interface.f90)≡  
  <File header>  
  
  module user_code_interface  
  
    use iso_c_binding !NODEP!  
    <Use kinds>  
    <Use strings>  
    use diagnostics  
    use c_particles  
    use os_interface  
  
    <Standard module head>  
  
    <User Code: public>  
  
    <User Code: variables>  
  
    <User Code: interfaces>  
  
    contains  
  
    <User Code: procedures>  
  
  end module user_code_interface
```

22.1.1 User Code Management

This data structure globally holds the filehandle of the user-code library:

```
<User Code: public>≡  
  public :: has_user_lib  
  
<User Code: variables>≡  
  type(dlaccess_t), save :: user_lib_handle  
  logical, save :: has_user_lib = .false.  
  type(string_t), save :: user
```

Compile, link and load user code files. Dlopen all user-provided libraries, included the one just compiled (if any).

By default, we are looking for a library `user.so/dylib`. If this is not present, try `user.f90` and compile it. This can be overridden.

In detail: First, compile all sources explicitly specified on the command line. Then collect all libraries specified on the command line, including `user.so` if it was generated. If there is still no code, check for an existing `user.f90` and compile this. Link everything into a `user.la` libtool library. When done, dlopen all libraries that we have so far.

```
<User Code: public>+≡  
  public :: user_code_init
```

{User Code: procedures}≡

```

subroutine user_code_init (user_src, user_lib, user_target, rebuild, os_data)
  type(string_t), dimension(:), intent(in) :: user_src, user_lib
  type(string_t), intent(in) :: user_target
  logical, intent(in) :: rebuild
  type(os_data_t), intent(in) :: os_data
  type(string_t) :: user_src_file, user_obj_files, user_lib_file
  logical :: exist
  type(c_funptr) :: fptr
  integer :: i
  call msg_message ("Initializing user code")
  user = user_target; if (user == "") user = "user"
  user_obj_files = ""
  inquire (file = char (user) // ".la", exist = exist)
  if (rebuild .or. .not. exist) then
    do i = 1, size (user_src)
      user_src_file = user_src(i) // os_data%fc_src_ext
      inquire (file = char (user_src_file), exist = exist)
      if (exist) then
        call msg_message ("Found user-code source '" &
          // char (user_src_file) // "'.")
        call compile_user_src (user_src_file, user_obj_files)
      else
        call msg_fatal ("User-code source '" // char (user_src_file) &
          // "' not found")
      end if
    end do
    do i = 1, size (user_lib)
      user_lib_file = user_lib(i) // ".la"
      inquire (file = char (user_lib_file), exist = exist)
      if (exist) then
        call msg_message ("Found user-code library '" &
          // char (user_lib_file) // "'.")
      else
        user_lib_file = user_lib(i) // os_data%fc_shrlib_ext
        inquire (file = char (user_lib_file), exist = exist)
        if (exist) then
          call msg_message ("Found user-code library '" &
            // char (user_lib_file) // "'.")
        else
          call msg_fatal ("User-code library '" // char (user_lib(i)) &
            // "' not found")
        end if
      end if
    end do
    user_obj_files = user_obj_files // " " // user_lib_file
  end do
  if (user_obj_files == "") then
    user_src_file = user // os_data%fc_src_ext
    inquire (file = char (user_src_file), exist = exist)
    if (exist) then
      call msg_message ("Found user-code source '" &
        // char (user_src_file) // "'.")
      call compile_user_src (user_src_file, user_obj_files)
    else

```

```

        call msg_fatal ("User-code source '" // char (user_src_file) &
            // "' not found")
    end if
end if
if (user_obj_files /= "") then
    call link_user (char (user), user_obj_files)
end if
end if
call dlaccess_init &
    (user_lib_handle, var_str ("."), &
    user // os_data%fc_shrplib_ext, os_data)
if (dlaccess_has_error (user_lib_handle)) then
    call msg_error (char (dlaccess_get_error (user_lib_handle)))
    call msg_fatal ("Loading user code library '" // char (user) &
        // ".la' failed")
else
    call msg_message ("User code library '" // char (user) &
        // ".la' successfully loaded")
    has_user_lib = .true.
end if
contains
subroutine compile_user_src (user_src_file, user_obj_files)
    type(string_t), intent(in) :: user_src_file
    type(string_t), intent(inout) :: user_obj_files
    type(string_t) :: basename, ext
    logical :: exist
    basename = user_src_file
    call split (basename, ext, ".", back=.true.)
    if ( "." // ext == os_data%fc_src_ext) then
        inquire (file = char (user_src_file), exist = exist)
        if (exist) then
            call msg_message ("Compiling user code file '" &
                // char (user_src_file) // "'")
            call os_compile_shared (basename, os_data)
            user_obj_files = user_obj_files // " " // basename // ".lo"
        else
            call msg_error ("User code file '" // char (user_src_file) &
                // "' not found.")
        end if
    else
        call msg_error ("User code file '" // char (user_src_file) &
            // "' should have file extension '" &
            // char (os_data%fc_src_ext) // "'")
    end if
end subroutine compile_user_src
subroutine link_user (user_lib, user_obj_files)
    character(*), intent(in) :: user_lib
    type(string_t), intent(in) :: user_obj_files
    call msg_message ("Linking user code library '" &
        // user_lib // char (os_data%fc_shrplib_ext) // "'")
    call os_link_shared (user_obj_files, var_str (user_lib), os_data)
end subroutine link_user
end subroutine user_code_init

```

Unload all user-code libraries.

```

<User Code: public>+≡
    public :: user_code_final

<User Code: procedures>+≡
    subroutine user_code_final ()
        if (has_user_lib) then
            call dlaccess_final (user_lib_handle)
            has_user_lib = .false.
        end if
    end subroutine user_code_final

```

Try to load the possible user-defined procedures from the dlopened libraries. If a procedure is not found, do nothing.

```

<User Code: public>+≡
    public :: user_code_find_proc

<User Code: procedures>+≡
    function user_code_find_proc (name) result (fptr)
        type(string_t), intent(in) :: name
        type(c_funptr) :: fptr
        integer :: i
        fptr = c_null_funptr
        !!! Ticket #529
        ! fptr = libmanager_get_c_funptr (char (user), char (name))
        if (.not. c_associated (fptr)) then
            if (has_user_lib) then
                fptr = dlaccess_get_c_funptr (user_lib_handle, name)
                if (.not. c_associated (fptr)) then
                    call msg_fatal ("User procedure '" // char (name) // "' not found")
                end if
            else
                call msg_fatal ("User procedure '" // char (name) &
                    // "' called without user library (missing -u flag?)")
            end if
        end if
    end function user_code_find_proc

```

22.1.2 Interfaces for user-defined functions

The following functions represent user-defined real observables. There may be one or two particles as argument, the result is a real value.

```

<User Code: public>+≡
    public :: user_obs_int_unary
    public :: user_obs_int_binary
    public :: user_obs_real_unary
    public :: user_obs_real_binary

<User Code: interfaces>≡
    abstract interface
        function user_obs_int_unary (prt1) result (ival) bind(C)
            use iso_c_binding !NODEP!

```

```

        use c_particles !NODEP!
        type(c_prt_t), intent(in) :: prt1
        integer(c_int) :: ival
    end function user_obs_int_unary
end interface

abstract interface
    function user_obs_int_binary (prt1, prt2) result (ival) bind(C)
        use iso_c_binding !NODEP!
        use c_particles !NODEP!
        type(c_prt_t), intent(in) :: prt1, prt2
        integer(c_int) :: ival
    end function user_obs_int_binary
end interface

abstract interface
    function user_obs_real_unary (prt1) result (rval) bind(C)
        use iso_c_binding !NODEP!
        use c_particles !NODEP!
        type(c_prt_t), intent(in) :: prt1
        real(c_double) :: rval
    end function user_obs_real_unary
end interface

abstract interface
    function user_obs_real_binary (prt1, prt2) result (rval) bind(C)
        use iso_c_binding !NODEP!
        use c_particles !NODEP!
        type(c_prt_t), intent(in) :: prt1, prt2
        real(c_double) :: rval
    end function user_obs_real_binary
end interface

```

The following function takes an array of C-compatible particles and return a single value. The particle array represents a subevent. For C interoperability, we have to use an assumed-size array, hence the array size has to be transferred explicitly.

The cut function returns an `int`, which we should interpret as a logical value (nonzero=true).

```

<User Code: public>+≡
    public :: user_cut_fun

<User Code: interfaces>+≡
    abstract interface
        function user_cut_fun (prt, n_prt) result (iflag) bind(C)
            use iso_c_binding !NODEP!
            use c_particles !NODEP!
            type(c_prt_t), dimension(*), intent(in) :: prt
            integer(c_int), intent(in) :: n_prt
            integer(c_int) :: iflag
        end function user_cut_fun
    end interface

```

The event-shape function returns a real value.

```

<User Code: public>+≡
    public :: user_event_shape_fun

<User Code: interfaces>+≡
    abstract interface
        function user_event_shape_fun (prt, n_prt) result (rval) bind(C)
            use iso_c_binding !NODEP!
            use c_particles !NODEP!
            type(c_prt_t), dimension(*), intent(in) :: prt
            integer(c_int), intent(in) :: n_prt
            real(c_double) :: rval
        end function user_event_shape_fun
    end interface

```

22.1.3 Interfaces for user-defined interactions

The following procedure interfaces pertain to user-defined interactions, e.g., spectra or structure functions.

This subroutine retrieves the basic information for setting up the interaction and event generation. All parameters are `intent(inout)`, so we can provide default values. `n_in` and `n_out` are the number of incoming and outgoing particles, respectively. `n_states` is the total number of distinct states that should be generated (counting all states of the incoming particles). `n_col` is the maximal number of color entries a particle can have. `n_dim` is the number of input parameters, i.e., integration dimensions, that the structure function call requires for computing kinematics and matrix elements. `n_var` is the number of variables (e.g., momentum fractions) that the structure function call has to transfer from the kinematics to the dynamics evaluation.

```

<User Code: public>+≡
    public :: user_int_info

<User Code: interfaces>+≡
    abstract interface
        subroutine user_int_info (n_in, n_out, n_states, n_col, n_dim, n_var) &
            bind(C)
            use iso_c_binding !NODEP!
            integer(c_int), intent(inout) :: n_in, n_out, n_states, n_col
            integer(c_int), intent(inout) :: n_dim, n_var
        end subroutine user_int_info
    end interface

```

This subroutine retrieves the settings for the quantum number mask of a given particle index in the interaction. A nonzero value indicates that the corresponding quantum number is to be ignored. The lock index is the index of a particle that the current particle is related to. The relation applies if quantum numbers of one of the locked particles are summed over. (This is intended for helicity.)

```

<User Code: public>+≡
    public :: user_int_mask

```



```

<User Code: interfaces>+≡
  abstract interface
    subroutine user_int_mask (i_prt, m_flv, m_hel, m_col, i_lock) bind(C)
      use iso_c_binding !NODEP!
      integer(c_int), intent(in) :: i_prt
      integer(c_int), intent(inout) :: m_flv, m_hel, m_col, i_lock
    end subroutine user_int_mask
  end interface

```

This subroutine retrieves the quantum numbers for the particle index `i_prt` in state `i_state`. The `flv` value is a PDG code. The `hel` value is an integer helicity (twice the helicity for fermions). The `col` array is an array which has at most `n_col` entries (see above). All parameters are `intent(inout)` since default values exist. In particular, if a mask entry is set by the previous procedure, the corresponding quantum number is ignored anyway.

```

<User Code: public>+≡
  public :: user_int_state

<User Code: interfaces>+≡
  abstract interface
    subroutine user_int_state (i_state, i_prt, flv, hel, col) bind(C)
      use iso_c_binding !NODEP!
      integer(c_int), intent(in) :: i_state, i_prt
      integer(c_int), intent(inout) :: flv, hel
      integer(c_int), dimension(*), intent(inout) :: col
    end subroutine user_int_state
  end interface

```

This subroutine takes an array of particle objects with array length `n_in` and an array of input parameters between 0 and 1 with array length `n_dim`. It returns an array of particle objects with array length `n_out`. In addition, it returns an array of internal variables (e.g., momentum fractions, Jacobian) with array length `n_var` that is used by the following subroutine for evaluating the dynamics, i.e., the matrix elements.

```

<User Code: public>+≡
  public :: user_int_kinematics

<User Code: interfaces>+≡
  abstract interface
    subroutine user_int_kinematics (prt_in, rval, prt_out, xval) bind(C)
      use iso_c_binding !NODEP!
      use c_particles !NODEP!
      type(c_prt_t), dimension(*), intent(in) :: prt_in
      real(c_double), dimension(*), intent(in) :: rval
      type(c_prt_t), dimension(*), intent(inout) :: prt_out
      real(c_double), dimension(*), intent(out) :: xval
    end subroutine user_int_kinematics
  end interface

```

This subroutine takes the array of variables (e.g., momentum fractions) with length `n_var` which has been generated by the previous subroutine and a real variable, the energy scale of the event. It returns an array of matrix-element

values, one entry for each quantum state `n_states`. The ordering of matrix elements must correspond to the ordering of states.

```

<User Code: public>+≡
    public :: user_int_evaluate

<User Code: interfaces>+≡
    abstract interface
        subroutine user_int_evaluate (xval, scale, fval) bind(C)
            use iso_c_binding !NODEP!
            real(c_double), dimension(*), intent(in) :: xval
            real(c_double), intent(in) :: scale
            real(c_double), dimension(*), intent(out) :: fval
        end subroutine user_int_evaluate
    end interface

```

22.2 User Plugin for Structure Functions

This variant gives access to user-defined structure functions or spectra.

22.2.1 The module

```

<sf_user.f90>≡
    <File header>

    module sf_user

        use, intrinsic :: iso_c_binding !NODEP!
        <Use kinds>
        <Use strings>
        use io_units
        use format_defs, only: FMT_17
        use diagnostics
        use c_particles
        use lorentz
        use subevents
        use user_code_interface
        use pdg_arrays
        use model_data
        use flavors
        use helicities
        use colors
        use quantum_numbers
        use state_matrices
        use polarizations
        use interactions
        use sf_aux
        use sf_base

        <Standard module head>

        <SF user: public>

```

```

<SF user: types>

contains

<SF user: procedures>

end module sf_user

```

22.2.2 The user structure function data block

The data block holds the procedure pointers that are used for retrieving static information, as well as the actual evaluation.

```

<SF user: public>≡
    public :: user_data_t

<SF user: types>≡
    type, extends(sf_data_t) :: user_data_t
        private
            type(string_t) :: name
            integer :: n_in
            integer :: n_out
            integer :: n_tot
            integer :: n_states
            integer :: n_col
            integer :: n_dim
            integer :: n_var
            integer, dimension(2) :: pdg_in
            class(model_data_t), pointer :: model => null ()
            procedure(user_int_info), nopass, pointer :: info => null ()
            procedure(user_int_mask), nopass, pointer :: mask => null ()
            procedure(user_int_state), nopass, pointer :: state => null ()
            procedure(user_int_kinematics), nopass, pointer :: kinematics => null ()
            procedure(user_int_evaluate), nopass, pointer :: evaluate => null ()
        contains
            <SF user: user data: TBP>
        end type user_data_t

```

Assign procedure pointers from a dynamically loaded library, given the specified name.

We have to distinguish three cases: (1) Both beams are affected, and the user spectrum implements both beams. There is a single data object. (2) Both beams are affected, and the user spectrum applies to single beams. Fill two different objects. (3) A single beam is affected.

```

<SF User: public>≡
    public :: sf_user_data_init

<SF User: procedures>≡
    subroutine sf_user_data_init (data, name, flv, model)
        type(sf_user_data_t), intent(out) :: data
        type(string_t), intent(in) :: name
        type(flavor_t), dimension(2), intent(in) :: flv
        class(model_data_t), intent(in), target :: model

```

```

integer(c_int) :: n_in
integer(c_int) :: n_out
integer(c_int) :: n_states
integer(c_int) :: n_col
integer(c_int) :: n_dim
integer(c_int) :: n_var
data%name = name
data%pdg_in = flavor_get_pdg (flv)
data%model => model
call c_f_procpointer (user_code_find_proc (name // "_info"), data%info)
call c_f_procpointer (user_code_find_proc (name // "_mask"), data%mask)
call c_f_procpointer (user_code_find_proc (name // "_state"), data%state)
call c_f_procpointer &
    (user_code_find_proc (name // "_kinematics"), data%kinematics)
call c_f_procpointer &
    (user_code_find_proc (name // "_evaluate"), data%evaluate)
n_in = 1
n_out = 2
n_states = 1
n_col = 2
n_dim = 1
n_var = 1
call data%info (n_in, n_out, n_states, n_col, n_dim, n_var)
data%n_in = n_in
data%n_out = n_out
data%n_tot = n_in + n_out
data%n_states = n_states
data%n_col = n_col
data%n_dim = n_dim
data%n_var = n_var
end subroutine sf_user_data_init

```

Output

```

<SF user: user data: TBP>≡
    procedure :: write => user_data_write

<SF user: procedures>≡
    subroutine user_data_write (data, unit, verbose)
        class(user_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        write (u, "(1x,A,A)") "User structure function: ", char (data%name)
    end subroutine user_data_write

```

Retrieving contents

```

<SF User: public>+≡
    public :: sf_user_data_get_name

<SF User: procedures>+≡
    function sf_user_data_get_name (data) result (name)
        type(string_t) :: name
        type(sf_user_data_t), intent(in) :: data
    end function sf_user_data_get_name

```

```

        name = data%/name
    end function sf_user_data_get_name

<SF User: public>+≡
    public :: sf_user_data_get_n_in
    public :: sf_user_data_get_n_out
    public :: sf_user_data_get_n_tot
    public :: sf_user_data_get_n_dim
    public :: sf_user_data_get_n_var

<SF User: procedures>+≡
    function sf_user_data_get_n_in (data) result (n_in)
        integer :: n_in
        type(sf_user_data_t), intent(in) :: data
        n_in = data%/n_in
    end function sf_user_data_get_n_in

    function sf_user_data_get_n_out (data) result (n_out)
        integer :: n_out
        type(sf_user_data_t), intent(in) :: data
        n_out = data%/n_out
    end function sf_user_data_get_n_out

    function sf_user_data_get_n_tot (data) result (n_tot)
        integer :: n_tot
        type(sf_user_data_t), intent(in) :: data
        n_tot = data%/n_tot
    end function sf_user_data_get_n_tot

    function sf_user_data_get_n_dim (data) result (n_dim)
        integer :: n_dim
        type(sf_user_data_t), intent(in) :: data
        n_dim = data%/n_dim
    end function sf_user_data_get_n_dim

    function sf_user_data_get_n_var (data) result (n_var)
        integer :: n_var
        type(sf_user_data_t), intent(in) :: data
        n_var = data%/n_var
    end function sf_user_data_get_n_var

```

22.2.3 The interaction

We fill the interaction by looking up the table of states using the interface functions.

For particles which have a known flavor (as indicated by the mask), we compute the mass squared, so we can use it for the invariant mass of the particle objects.

```

<SF user: user: TBP>≡
    procedure :: init => user_init

```

<SF user: procedures>+≡

```

subroutine user_init (sf_int, data)
  !!! JRR: WK please check (#529)
  class(user_t), intent(out) :: sf_int
  class(sf_data_t), intent(in), target :: data
  type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
  integer, dimension(:), allocatable :: hel_lock
  integer(c_int) :: m_flv, m_hel, m_col, i_lock
  type(quantum_numbers_t), dimension(:), allocatable :: qn
  integer(c_int) :: f, h
  integer(c_int), dimension(:), allocatable :: c
  type(flavor_t) :: flv
  type(helicity_t) :: hel
  type(color_t) :: col
  integer :: i, s
  integer(c_int) :: i_prt, i_state
  select type (data)
  type is (user_data_t)
    allocate (mask (data%n_tot))
    allocate (hel_lock (data%n_tot))
    allocate (qn (data%n_tot))
    allocate (c (data%n_col))
    do i = 1, size (mask)
      i_prt = i
      m_flv = 0; m_col = 0; m_hel = 0; i_lock = 0
      call data%mask (i_prt, m_flv, m_col, m_hel, i_lock)
      mask(i) = &
        quantum_numbers_mask (m_flv /= 0, m_col /= 0, m_hel /= 0)
      hel_lock(i) = i_lock
    end do
    !!! JRR: WK please check (#529)
    !!! Will have to be filled in later.
    ! call sf_int%base_init (mask, &
    !   hel_lock = hel_lock)
    call sf_int%basic_init &
      (data%n_in, 0, data%n_out, mask=mask, &
      hel_lock=hel_lock, set_relations=.true.)
    do s = 1, data%n_states
      i_state = s
      do i = 1, data%n_tot
        i_prt = i
        f = 0; h = 0; c = 0
        call data%state (i_state, i_prt, f, h, c)
        if (m_flv == 0) then
          call flv%init (int (f), data%model)
        else
          call flv%init ()
        end if
        if (m_hel == 0) then
          call hel%init (int (h))
        else
          call hel%init ()
        end if
        if (m_col == 0) then

```

```

        call color_init_from_array (col, int (c))
    else
        call col%init ()
    end if
    call qn(i)%init (flv, col, hel)
end do
call sf_int%add_state (qn)
end do
call sf_int%freeze ()
!!! JRR: WK please check (#529)
!!! What has to be inserted here?
! call sf_int%set_incoming (??)
! call sf_int%set_radiated (??)
! call sf_int%set_outgoing (??)
sf_int%status = SF_INITIAL
end select
end subroutine user_init

```

Allocate the interaction record.

```

<SF user: user data: TBP>+≡
    procedure :: allocate_sf_int => user_data_allocate_sf_int

<SF user: procedures>+≡
    subroutine user_data_allocate_sf_int (data, sf_int)
        class(user_data_t), intent(in) :: data
        class(sf_int_t), intent(inout), allocatable :: sf_int
        allocate (user_t :: sf_int)
    end subroutine user_data_allocate_sf_int

```

The number of parameters is one. We do not generate transverse momentum.

```

<SF user: user data: TBP>+≡
    procedure :: get_n_par => user_data_get_n_par

<SF user: procedures>+≡
    function user_data_get_n_par (data) result (n)
        class(user_data_t), intent(in) :: data
        integer :: n
        n = data%n_var
    end function user_data_get_n_par

```

Return the outgoing particle PDG codes. This has to be inferred from the states (right?). JRR: WK please check.

```

<SF user: user data: TBP>+≡
    procedure :: get_pdg_out => user_data_get_pdg_out

<SF user: procedures>+≡
    subroutine user_data_get_pdg_out (data, pdg_out)
        class(user_data_t), intent(in) :: data
        type(pdg_array_t), dimension(:), intent(inout) :: pdg_out
        !!! JRR: WK please check (#529)
        !!! integer :: n, np, i
        !!! n = count (data%mask)
        !!! np = 0; if (data%has_photon .and. data%mask_photon) np = 1

```

```

    !!! allocate (pdg_out (n + np))
    !!! pdg_out(1:n) = pack ([i, i = -6, 6]), data%mask)
    !!! if (np == 1) pdg_out(n+np) = PHOTON
end subroutine user_data_get_pdg_out

```

22.2.4 The user structure function

For maximal flexibility, user structure functions separate kinematics from dynamics just as the PDF interface does. (JRR: Ok, I guess this now done for all structure functions, right?) We create `c_prt_t` particle objects from the incoming momenta (all other quantum numbers are irrelevant) and call the user-supplied kinematics function to compute the outgoing momenta, along with other variables that will be needed for matrix element evaluation. If known, we use the mass squared computed above. !!! JRR: WK please check (#529) I don't know actually whether this really fits into the setup done by WK.

```

<SF user: types>+≡
    !!! JRR: WK please check (#529)
    type, extends (sf_int_t) :: user_t
        type(user_data_t), pointer :: data => null ()
        real(default) :: x = 0
        real(default) :: q = 0
    contains
        <SF user: user: TBP>
    end type user_t

```

Type string: display the name of the user structure function.

```

<SF user: user: TBP>+≡
    procedure :: type_string => user_type_string

<SF user: procedures>+≡
    function user_type_string (object) result (string)
        class(user_t), intent(in) :: object
        type(string_t) :: string
        if (associated (object%data)) then
            string = "User structure function: " // object%data%name
        else
            string = "User structure function: [undefined]"
        end if
    end function user_type_string

```

Output. Call the interaction routine after displaying the configuration.

```

<SF user: user: TBP>+≡
    procedure :: write => user_write

<SF user: procedures>+≡
    subroutine user_write (object, unit, testflag)
        !!! JRR: WK please check (#529)
        !!! Guess these variables do not exist for user strfun (?)
        class(user_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: testflag

```



```

integer :: u
u = given_output_unit (unit)
if (associated (object%data)) then
  call object%data%write (u)
  if (object%status >= SF_DONE_KINEMATICS) then
    write (u, "(1x,A)") "SF parameters:"
    write (u, "(3x,A," // FMT_17 // ")") "x =", object%x
    if (object%status >= SF_FAILED_EVALUATION) then
      write (u, "(3x,A," // FMT_17 // ")") "Q =", object%q
    end if
  end if
  call object%base_write (u, testflag)
else
  write (u, "(1x,A)") "User structure function data: [undefined]"
end if
end subroutine user_write

```

22.2.5 Kinematics

Set kinematics. If `map` is unset, the r and x values coincide, and the Jacobian $f(r)$ is trivial.

If `map` is set, we are asked to provide an efficient mapping. For the test case, we set $x = r^2$ and consequently $f(r) = 2r$.

```

<SF user: user: TBP>+≡
  procedure :: complete_kinematics => user_complete_kinematics
<SF user: procedures>+≡
  subroutine user_complete_kinematics (sf_int, x, f, r, rb, map)
    !!! JRR: WK please check (#529)
    !!! This cannot be correct, as the CIRCE1 structure function has
    !!! twice the variables (2->4 instead of 1->2 splitting)
    class(user_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(out) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(in) :: r
    real(default), dimension(:), intent(in) :: rb
    logical, intent(in) :: map
    real(default) :: xb1
    if (map) then
      call msg_fatal ("User structure function: map flag not supported")
    else
      x(1) = r(1)
      f = 1
    end if
    xb1 = 1 - x(1)
    call sf_int%split_momentum (x, xb1)
    select case (sf_int%status)
    case (SF_DONE_KINEMATICS)
      sf_int%x = x(1)
    case (SF_FAILED_KINEMATICS)
      sf_int%x = 0
      f = 0
    end select
  end subroutine

```

```
end subroutine user_complete_kinematics
```

Compute inverse kinematics. Here, we start with the x array and compute the “input” r values and the Jacobian f . After this, we can set momenta by the same formula as for normal kinematics.

```
<SF user: user: TBP>+≡
  procedure :: inverse_kinematics => user_inverse_kinematics

<SF user: procedures>+≡
  subroutine user_inverse_kinematics (sf_int, x, f, r, rb, map, set_momenta)
    !!! JRR: WK please check (#529)
    !!! This cannot be correct, as the CIRCE1 structure function has
    !!! twice the variables (2->4 instead of 1->2 splitting)
    class(user_t), intent(inout) :: sf_int
    real(default), dimension(:), intent(in) :: x
    real(default), intent(out) :: f
    real(default), dimension(:), intent(out) :: r
    real(default), dimension(:), intent(out) :: rb
    logical, intent(in) :: map
    logical, intent(in), optional :: set_momenta
    real(default) :: xb1
    logical :: set_mom
    set_mom = .false.; if (present (set_momenta)) set_mom = set_momenta
    if (map) then
      call msg_fatal ("User structure function: map flag not supported")
    else
      r(1) = x(1)
      f = 1
    end if
    xb1 = 1 - x(1)
    rb = 1 - r
    if (set_mom) then
      call sf_int%split_momentum (x, xb1)
      select case (sf_int%status)
        case (SF_DONE_KINEMATICS)
          sf_int%x = x(1)
        case (SF_FAILED_KINEMATICS)
          sf_int%x = 0
          f = 0
        end select
    end if
  end subroutine user_inverse_kinematics
```

```
<SF User: public>+≡
  public :: interaction_set_kinematics_sf_user

<SF User: procedures>+≡
  subroutine interaction_set_kinematics_sf_user (int, x, r, data)
    type(interaction_t), intent(inout) :: int
    real(default), dimension(:), intent(out) :: x
    real(default), dimension(:), intent(in) :: r
    type(sf_user_data_t), intent(in) :: data
    type(vector4_t), dimension(data%n_in) :: p_in
    type(vector4_t), dimension(data%n_out) :: p_out
```

```

type(c_prt_t), dimension(data%n_in) :: prt_in
type(c_prt_t), dimension(data%n_out) :: prt_out
real(c_double), dimension(data%n_var) :: xval
call int%get_momenta_sub (p_in, outgoing=.false.)
prt_in = vector4_to_c_prt (p_in)
prt_in%type = PRT_INCOMING
call data%kinematics (prt_in, real (r, c_double), prt_out, xval)
x = xval
p_out = vector4_from_c_prt (prt_out)
call int%set_momenta (p_out, outgoing=.true.)
end subroutine interaction_set_kinematics_sf_user

```

The matrix-element evaluation may require a scale parameter, therefore this routine is separate. We take the variables computed above together with the event energy scale and call the user function that computes the matrix elements.

```

<SF user: user: TBP>+≡
  procedure :: apply => user_apply

<SF user: procedures>+≡
  subroutine user_apply (sf_int, scale) !, x, data)
    !!! JRR: WK please check (#529)
    class(user_t), intent(inout) :: sf_int
    real(default), intent(in) :: scale
    real(default), dimension(:), allocatable :: x
    real(c_double), dimension(sf_int%data%n_states) :: fval
    complex(default), dimension(sf_int%data%n_states) :: fc
    associate (data => sf_int%data)
      !!! This is wrong, has to be replaced
      ! allocate (x, size (sf_int%x))
      x = sf_int%x
      call data%evaluate (real (x, c_double), real (scale, c_double), fval)
      fc = fval
      call sf_int%set_matrix_element (fc)
    end associate
    sf_int%status = SF_EVALUATED
  end subroutine user_apply

```

Chapter 23

BLHA Interface

The code in this chapter implements support for the BLHA record that communicates data for NLO processes.

These are the modules:

blha_config

blha_interface

blha_driver

23.1 Module definition

These modules implement the communication with one loop matrix element providers according to the Binoth LesHouches Accord Interface. The actual matrix element(s) are loaded as a dynamic library.

This module defines the common OLP-interfaces defined through the Binoth Les-Houches accord.

```
<blha_olp_interfaces.f90>≡  
  <File header>  
  
  module blha_olp_interfaces  
  
    use, intrinsic :: iso_c_binding !NODEP!  
    use, intrinsic :: iso_fortran_env  
  
    use kinds  
    <Use strings>  
    use system_defs, only: TAB  
    use io_units  
    use string_utils  
    use physics_defs  
    use diagnostics  
    use os_interface  
    use lorentz  
    use sm_qcd  
    use interactions
```

```

use flavors
use model_data

use prclib_interfaces
use process_libraries
use prc_core_def
use prc_core

use blha_config

<Standard module head>

<BLHA OLP interfaces: public>

<BLHA OLP interfaces: public parameters>

<BLHA OLP interfaces: types>

<BLHA OLP interfaces: interfaces>

contains

<BLHA OLP interfaces: procedures>

end module blha_olp_interfaces

<BLHA OLP interfaces: public>≡
  public :: blha_template_t
<BLHA OLP interfaces: types>≡
  type :: blha_template_t
    integer :: I_REAL = 1
    integer :: I_LOOP = 2
    integer :: I_SUB = 3
    logical, dimension(3) :: compute_component
  contains
    <BLHA OLP interfaces: blha template: TBP>
  end type blha_template_t

<BLHA OLP interfaces: public>+≡
  public :: prc_blha_t
<BLHA OLP interfaces: types>+≡
  type, abstract, extends (prc_core_t) :: prc_blha_t
    type(qcd_t) :: qcd
    integer :: n_flv
    integer :: n_particles
    real(default) :: maximum_accuracy = 10000.0
    integer, dimension(:), allocatable :: i_born, i_sc, i_cc
    integer, dimension(:), allocatable :: i_real
    integer, dimension(:), allocatable :: i_virt
  contains
    <BLHA OLP interfaces: prc blha: TBP>
  end type prc_blha_t

```

```

<BLHA OLP interfaces: public>+≡
  public :: blha_driver_t

<BLHA OLP interfaces: types>+≡
  type, abstract, extends (prc_core_driver_t) :: blha_driver_t
    type(string_t) :: contract_file
    procedure(olp_start), nopass, pointer :: &
      blha_olp_start => null ()
    procedure(olp_eval), nopass, pointer :: &
      blha_olp_eval => null ()
    procedure(olp_info), nopass, pointer :: &
      blha_olp_info => null ()
    procedure(olp_set_parameter), nopass, pointer :: &
      blha_olp_set_parameter => null ()
    procedure(olp_eval2), nopass, pointer :: &
      blha_olp_eval2 => null ()
    procedure(olp_option), nopass, pointer :: &
      blha_olp_option => null ()
    procedure(olp_polvec), nopass, pointer :: &
      blha_olp_polvec => null ()
    procedure(olp_finalize), nopass, pointer :: &
      blha_olp_finalize => null ()
    procedure(olp_print_parameter), nopass, pointer :: &
      blha_olp_print_parameter => null ()

```

We have to add two O'Mega-routines to the GoSam driver to ensure proper process setup.

```

<BLHA OLP interfaces: types>+≡
  procedure(omega_update_alpha_s), nopass, pointer :: &
    update_alpha_s => null ()
  procedure(omega_is_allowed), nopass, pointer :: &
    is_allowed => null ()
  contains
  <BLHA OLP interfaces: blha driver: TBP>
  end type blha_driver_t

```

```

<BLHA OLP interfaces: public>+≡
  public :: prc_blha_writer_t

<BLHA OLP interfaces: types>+≡
  type, abstract, extends (prc_writer_f_module_t) :: prc_blha_writer_t
    type(blha_configuration_t) :: blha_cfg
    type(string_t) :: model_name
    type(string_t) :: process_mode
    type(string_t) :: process_string
  contains
  <BLHA OLP interfaces: blha writer: TBP>
  end type prc_blha_writer_t

```

```

<BLHA OLP interfaces: public>+≡
  public :: blha_def_t

<BLHA OLP interfaces: types>+≡
  type, abstract, extends (prc_core_def_t) :: blha_def_t
    type(string_t) :: basename

```

```

        type(string_t) :: suffix
contains
<BLHA OLP interfaces: blha def: TBP>
end type blha_def_t

<BLHA OLP interfaces: public>+≡
    public :: blha_state_t

<BLHA OLP interfaces: types>+≡
    type, abstract, extends (prc_core_state_t) :: blha_state_t
        logical :: new_kinematics = .true.
        real(default) :: alpha_qcd = -1
contains
<BLHA OLP interfaces: blha state: TBP>
end type blha_state_t

<BLHA OLP interfaces: blha state: TBP>≡
    procedure :: reset_new_kinematics => blha_state_reset_new_kinematics

<BLHA OLP interfaces: procedures>≡
    subroutine blha_state_reset_new_kinematics (object)
        class(blha_state_t), intent(inout) :: object
        object%new_kinematics = .true.
    end subroutine blha_state_reset_new_kinematics

<BLHA OLP interfaces: blha def: TBP>≡
    procedure, nopass :: needs_code => blha_def_needs_code

<BLHA OLP interfaces: procedures>+≡
    function blha_def_needs_code () result (flag)
        logical :: flag
        flag = .true.
    end function blha_def_needs_code

<BLHA OLP interfaces: blha def: TBP>+≡
    procedure, nopass :: get_features => blha_def_get_features

<BLHA OLP interfaces: procedures>+≡
    subroutine blha_def_get_features (features)
        type(string_t), dimension(:), allocatable, intent(out) :: features
        allocate (features (6))
        features = [ &
            var_str ("init"), &
            var_str ("update_alpha_s"), &
            var_str ("reset_helicity_selection"), &
            var_str ("is_allowed"), &
            var_str ("new_event"), &
            var_str ("get_amplitude")]
    end subroutine blha_def_get_features

<BLHA OLP interfaces: blha def: TBP>+≡
    procedure :: connect => blha_def_connect

```

<BLHA OLP interfaces: procedures>+≡

```

subroutine blha_def_connect (def, lib_driver, i, proc_driver)
  class(blha_def_t), intent(in) :: def
  class(prclib_driver_t), intent(in) :: lib_driver
  integer, intent(in) :: i
  integer :: pid, fid
  class(prc_core_driver_t), intent(inout) :: proc_driver
  type(c_funptr) :: fptr
  select type (proc_driver)
  class is (blha_driver_t)
    pid = i
    fid = 2
    call lib_driver%get_fptr (pid, fid, fptr)
    call c_f_procpointer (fptr, proc_driver%update_alpha_s)
    fid = 4
    call lib_driver%get_fptr (pid, fid, fptr)
    call c_f_procpointer (fptr, proc_driver%is_allowed)
  end select
end subroutine blha_def_connect

```

<BLHA OLP interfaces: public parameters>≡

```

integer, parameter, public :: OLP_PARAMETER_LIMIT = 10
integer, parameter, public :: OLP_MOMENTUM_LIMIT = 50
integer, parameter, public :: OLP_RESULTS_LIMIT = 60

```

<BLHA OLP interfaces: public>+≡

```

public :: olp_start

```

<BLHA OLP interfaces: interfaces>≡

```

interface
  subroutine olp_start (contract_file_name, ierr) bind (C,name="OLP_Start")
    import
    character(kind=c_char, len=1), intent(in) :: contract_file_name
    integer(kind=c_int), intent(out) :: ierr
  end subroutine olp_start
end interface

```

<BLHA OLP interfaces: public>+≡

```

public :: olp_eval

```

<BLHA OLP interfaces: interfaces>+≡

```

interface
  subroutine olp_eval (label, momenta, mu, parameters, res) &
    bind (C,name="OLP_EvalSubProcess")
    import
    integer(kind=c_int), value, intent(in) :: label
    real(kind=c_double), value, intent(in) :: mu
    real(kind=c_double), dimension(OLP_MOMENTUM_LIMIT), intent(in) :: &
      momenta
    real(kind=c_double), dimension(OLP_PARAMETER_LIMIT), intent(in) :: &
      parameters
    real(kind=c_double), dimension(OLP_RESULTS_LIMIT), intent(out) :: res
  end subroutine olp_eval
end interface

```


<BLHA OLP interfaces: public>+≡

public :: olp_info

<BLHA OLP interfaces: interfaces>+≡

interface

subroutine olp_info (olp_file, olp_version, message) bind(C)

import

character(kind=c_char), intent(inout), dimension(15) :: olp_file

character(kind=c_char), intent(inout), dimension(15) :: olp_version

character(kind=c_char), intent(inout), dimension(255) :: message

end subroutine olp_info

end interface

<BLHA OLP interfaces: public>+≡

public :: olp_set_parameter

<BLHA OLP interfaces: interfaces>+≡

interface

subroutine olp_set_parameter &

(variable_name, real_part, complex_part, success) bind(C)

import

character(kind=c_char,len=1), intent(in) :: variable_name

real(kind=c_double), intent(in) :: real_part, complex_part

integer(kind=c_int), intent(out) :: success

end subroutine olp_set_parameter

end interface

<BLHA OLP interfaces: public>+≡

public :: olp_eval2

<BLHA OLP interfaces: interfaces>+≡

interface

subroutine olp_eval2 (label, momenta, mu, res, acc) bind(C)

import

integer(kind=c_int), intent(in) :: label

real(kind=c_double), intent(in) :: mu

real(kind=c_double), dimension(OLP_MOMENTUM_LIMIT), intent(in) :: momenta

real(kind=c_double), dimension(OLP_RESULTS_LIMIT), intent(out) :: res

real(kind=c_double), intent(out) :: acc

end subroutine olp_eval2

end interface

<BLHA OLP interfaces: public>+≡

public :: olp_option

<BLHA OLP interfaces: interfaces>+≡

interface

subroutine olp_option (line, stat) bind(C)

import

character(kind=c_char, len=1), intent(in) :: line

integer(kind=c_int), intent(out) :: stat

end subroutine

end interface

```

<BLHA OLP interfaces: public>+≡
    public :: olp_polvec

<BLHA OLP interfaces: interfaces>+≡
    interface
        subroutine olp_polvec (p, q, eps) bind(C)
            import
            real(kind=c_double), dimension(0:3), intent(in) :: p, q
            real(kind=c_double), dimension(0:7), intent(out) :: eps
        end subroutine
    end interface

<BLHA OLP interfaces: public>+≡
    public :: olp_finalize

<BLHA OLP interfaces: interfaces>+≡
    interface
        subroutine olp_finalize () bind(C)
            import
        end subroutine olp_finalize
    end interface

<BLHA OLP interfaces: public>+≡
    public :: olp_print_parameter

<BLHA OLP interfaces: interfaces>+≡
    interface
        subroutine olp_print_parameter (filename) bind(C)
            import
            character(kind=c_char, len=1), intent(in) :: filename
        end subroutine olp_print_parameter
    end interface

<BLHA OLP interfaces: interfaces>+≡
    abstract interface
        subroutine omega_update_alpha_s (alpha_s) bind(C)
            import
            real(c_default_float), intent(in) :: alpha_s
        end subroutine omega_update_alpha_s
    end interface

    abstract interface
        subroutine omega_is_allowed (flv, hel, col, flag) bind(C)
            import
            integer(c_int), intent(in) :: flv, hel, col
            logical(c_bool), intent(out) :: flag
        end subroutine omega_is_allowed
    end interface

<BLHA OLP interfaces: public>+≡
    public :: blha_result_array_size

```

```

<BLHA OLP interfaces: procedures>+=
  pure function blha_result_array_size (n_part, amp_type) result (rsize)
    integer, intent(in) :: n_part, amp_type
    integer :: rsize
    select case (amp_type)
      case (BLHA_AMP_TREE)
        rsize = 1
      case (BLHA_AMP_LOOP)
        rsize = 4
      case (BLHA_AMP_CC)
        rsize = n_part*(n_part-1)/2
      case (BLHA_AMP_SC)
        rsize = 2*n_part**2
    end select
  end function blha_result_array_size

<BLHA OLP interfaces: public>+=
  ! public :: create_blha_momentum_array

<BLHA OLP interfaces: prc blha: TBP>=
  procedure :: create_momentum_array => prc_blha_create_momentum_array

<BLHA OLP interfaces: procedures>+=
  function prc_blha_create_momentum_array (object, p) result (mom)
    class(prc_blha_t), intent(in) :: object
    type(vector4_t), intent(in), dimension(:) :: p
    real(double), dimension(5*object%n_particles) :: mom
    integer :: n, i, k

    n = size (p)
    if (n > 10) call msg_fatal ("Number of external particles exceeds" &
                               // "size of GoSam-internal momentum array")

    k = 1
    do i = 1, n
      mom(k:k+3) = vector4_get_components (p(i))
      mom(k+4) = invariant_mass (p(i))
      k = k+5
    end do
    ! mom (k:50) = 0.0
  end function prc_blha_create_momentum_array

<BLHA OLP interfaces: blha template: TBP>=
  procedure :: init => blha_template_init

<BLHA OLP interfaces: procedures>+=
  subroutine blha_template_init (template)
    class(blha_template_t), intent(inout) :: template
    template%compute_component = .false.
  end subroutine blha_template_init

<BLHA OLP interfaces: blha template: TBP>+=
  procedure :: set_loop => blha_template_set_loop
  procedure :: set_subtraction => blha_template_set_subtraction
  procedure :: set_real_trees => blha_template_set_real_trees

```

```

<BLHA OLP interfaces: procedures>+≡
  subroutine blha_template_set_loop (template)
    class(blha_template_t), intent(inout) :: template
    template%compute_component(template%I_LOOP) = .true.
  end subroutine blha_template_set_loop

  subroutine blha_template_set_subtraction (template)
    class(blha_template_t), intent(inout) :: template
    template%compute_component (template%I_SUB) = .true.
  end subroutine blha_template_set_subtraction

  subroutine blha_template_set_real_trees (template)
    class(blha_template_t), intent(inout) :: template
    template%compute_component (template%I_REAL) = .true.
  end subroutine blha_template_set_real_trees

<BLHA OLP interfaces: blha template: TBP>+≡
  procedure :: compute_loop => blha_template_compute_loop
  procedure :: compute_subtraction => blha_template_compute_subtraction
  procedure :: compute_real_trees => blha_template_compute_real_trees

<BLHA OLP interfaces: procedures>+≡
  function blha_template_compute_loop (template) result (val)
    class(blha_template_t), intent(in) :: template
    logical :: val
    val = template%compute_component (template%I_LOOP)
  end function blha_template_compute_loop

  function blha_template_compute_subtraction (template) result (val)
    class(blha_template_t), intent(in) :: template
    logical :: val
    val = template%compute_component (template%I_SUB)
  end function blha_template_compute_subtraction

  function blha_template_compute_real_trees (template) result (val)
    class(blha_template_t), intent(in) :: template
    logical :: val
    val = template%compute_component (template%I_REAL)
  end function blha_template_compute_real_trees

<BLHA OLP interfaces: blha template: TBP>+≡
  procedure :: check => blha_template_check

<BLHA OLP interfaces: procedures>+≡
  function blha_template_check (template) result (val)
    class(blha_template_t), intent(in) :: template
    logical :: val
    val = count (template%compute_component) == 1
  end function blha_template_check

<BLHA OLP interfaces: blha template: TBP>+≡
  procedure :: reset => blha_template_reset

```

```

<BLHA OLP interfaces: procedures>+=
  subroutine blha_template_reset (template)
    class(blha_template_t), intent(inout) :: template
    template%compute_component = .false.
  end subroutine blha_template_reset

<BLHA OLP interfaces: blha writer: TBP>=
  procedure :: write_wrapper => prc_blha_writer_write_wrapper

<BLHA OLP interfaces: procedures>+=
  subroutine prc_blha_writer_write_wrapper (writer, unit, id, feature)
    class(prc_blha_writer_t), intent(in) :: writer
    integer, intent(in) :: unit
    type(string_t), intent(in) :: id, feature
    type(string_t) :: name
    name = writer%get_c_procname (id, feature)
    write (unit, *)
    select case (char (feature))
    case ("init")
      write (unit, "(9A)") "subroutine ", char (name), " (par) bind(C)"
      write (unit, "(2x,9A)") "use iso_c_binding"
      write (unit, "(2x,9A)") "use kinds"
      write (unit, "(2x,9A)") "use opr_", char (id)
      write (unit, "(2x,9A)") "real(c_default_float), dimension(*), &
        &intent(in) :: par"
      if (c_default_float == default) then
        write (unit, "(2x,9A)") "call ", char (feature), " (par)"
      end if
      write (unit, "(9A)") "end subroutine ", char (name)
    case ("update_alpha_s")
      write (unit, "(9A)") "subroutine ", char (name), " (alpha_s) bind(C)"
      write (unit, "(2x,9A)") "use iso_c_binding"
      write (unit, "(2x,9A)") "use kinds"
      write (unit, "(2x,9A)") "use opr_", char (id)
      if (c_default_float == default) then
        write (unit, "(2x,9A)") "real(c_default_float), intent(in) &
          &:: alpha_s"
        write (unit, "(2x,9A)") "call ", char (feature), " (alpha_s)"
      end if
      write (unit, "(9A)") "end subroutine ", char (name)
    case ("reset_helicity_selection")
      write (unit, "(9A)") "subroutine ", char (name), &
        " (threshold, cutoff) bind(C)"
      write (unit, "(2x,9A)") "use iso_c_binding"
      write (unit, "(2x,9A)") "use kinds"
      write (unit, "(2x,9A)") "use opr_", char (id)
      if (c_default_float == default) then
        write (unit, "(2x,9A)") "real(c_default_float), intent(in) &
          &:: threshold"
        write (unit, "(2x,9A)") "integer(c_int), intent(in) :: cutoff"
        write (unit, "(2x,9A)") "call ", char (feature), &
          " (threshold, int (cutoff))"
      end if
      write (unit, "(9A)") "end subroutine ", char (name)
  end subroutine prc_blha_writer_write_wrapper

```

```

case ("is_allowed")
  write (unit, "(9A)") "subroutine ", char (name), &
    " (flv, hel, col, flag) bind(C)"
  write (unit, "(2x,9A)") "use iso_c_binding"
  write (unit, "(2x,9A)") "use kinds"
  write (unit, "(2x,9A)") "use opr_", char (id)
  write (unit, "(2x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
  write (unit, "(2x,9A)") "logical(c_bool), intent(out) :: flag"
  write (unit, "(2x,9A)") "flag = ", char (feature), &
    " (int (flv), int (hel), int (col))"
  write (unit, "(9A)") "end subroutine ", char (name)
case ("new_event")
  write (unit, "(9A)") "subroutine ", char (name), " (p) bind(C)"
  write (unit, "(2x,9A)") "use iso_c_binding"
  write (unit, "(2x,9A)") "use kinds"
  write (unit, "(2x,9A)") "use opr_", char (id)
  if (c_default_float == default) then
    write (unit, "(2x,9A)") "real(c_default_float), dimension(0:3,*), &
      &intent(in) :: p"
    write (unit, "(2x,9A)") "call ", char (feature), " (p)"
  end if
  write (unit, "(9A)") "end subroutine ", char (name)
case ("get_amplitude")
  write (unit, "(9A)") "subroutine ", char (name), &
    " (flv, hel, col, amp) bind(C)"
  write (unit, "(2x,9A)") "use iso_c_binding"
  write (unit, "(2x,9A)") "use kinds"
  write (unit, "(2x,9A)") "use opr_", char (id)
  write (unit, "(2x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
  write (unit, "(2x,9A)") "complex(c_default_complex), intent(out) &
    &:: amp"
  write (unit, "(2x,9A)") "amp = ", char (feature), &
    " (int (flv), int (hel), int (col))"
  write (unit, "(9A)") "end subroutine ", char (name)
end select

end subroutine prc_blha_writer_write_wrapper

```

<BLHA OLP interfaces: blha writer: TBP>+≡

```
procedure :: write_interface => prc_blha_writer_write_interface
```

<BLHA OLP interfaces: procedures>+≡

```

subroutine prc_blha_writer_write_interface (writer, unit, id, feature)
  class(prc_blha_writer_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id
  type(string_t), intent(in) :: feature
  type(string_t) :: name
  name = writer%get_c_procname (id, feature)
  write (unit, "(2x,9A)") "interface"
  select case (char (feature))
  case ("init")
    write (unit, "(5x,9A)") "subroutine ", char (name), " (par) bind(C)"
    write (unit, "(7x,9A)") "import"

```

```

        write (unit, "(7x,9A)") "real(c_default_float), dimension(*), &
            &intent(in) :: par"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("update_alpha_s")
        write (unit, "(5x,9A)") "subroutine ", char (name), " (alpha_s) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "real(c_default_float), intent(in) :: alpha_s"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("reset_helicity_selection")
        write (unit, "(5x,9A)") "subroutine ", char (name), " &
            &(threshold, cutoff) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "real(c_default_float), intent(in) :: threshold"
        write (unit, "(7x,9A)") "integer(c_int), intent(in) :: cutoff"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("is_allowed")
        write (unit, "(5x,9A)") "subroutine ", char (name), " &
            &(flv, hel, col, flag) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
        write (unit, "(7x,9A)") "logical(c_bool), intent(out) :: flag"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("new_event")
        write (unit, "(5x,9A)") "subroutine ", char (name), " (p) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "real(c_default_float), dimension(0:3,*), &
            &intent(in) :: p"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
    case ("get_amplitude")
        write (unit, "(5x,9A)") "subroutine ", char (name), " &
            &(flv, hel, col, amp) bind(C)"
        write (unit, "(7x,9A)") "import"
        write (unit, "(7x,9A)") "integer(c_int), intent(in) :: flv, hel, col"
        write (unit, "(7x,9A)") "complex(c_default_complex), intent(out) &
            &:: amp"
        write (unit, "(5x,9A)") "end subroutine ", char (name)
end select
write (unit, "(2x,9A)") "end interface"
end subroutine prc_blha_writer_write_interface

```

$\langle BLHA \ OLP \ interfaces: \ blha \ writer: \ TBP \rangle + \equiv$

```
procedure :: write_source_code => prc_blha_writer_write_source_code
```

$\langle BLHA \ OLP \ interfaces: \ procedures \rangle + \equiv$

```

subroutine prc_blha_writer_write_source_code (writer, id)
    class(prc_blha_writer_t), intent(in) :: writer
    type(string_t), intent(in) :: id
    !!! This is a dummy
end subroutine prc_blha_writer_write_source_code

```

$\langle BLHA \ OLP \ interfaces: \ blha \ writer: \ TBP \rangle + \equiv$

```
procedure :: write_makefile_code => prc_blha_writer_write_makefile_code
```

(BLHA OLP interfaces: procedures)+≡

```

subroutine prc_blha_writer_write_makefile_code (writer, unit, id, os_data, testflag)
  class(prc_blha_writer_t), intent(in) :: writer
  integer, intent(in) :: unit
  type(string_t), intent(in) :: id
  type(os_data_t), intent(in) :: os_data
  logical, intent(in), optional :: testflag
  type(string_t) :: omega_binary, omega_path
  omega_binary = "omega_" // writer%model_name // ".opt"
  omega_path = os_data%whizard_omega_binpath // "/" // omega_binary
  write (unit, "(5A)") "OBJECTS += ", char (id), ".lo"
  write (unit, "(5A)") char (id), ".f90:"
  write (unit, "(99A)") TAB, char (omega_path), &
    " -o ", char (id), ".f90", &
    " -target:whizard", &
    " -target:parameter_module parameters-", char (writer%model_name), &
    " -target:module opr-", char (id), &
    " -target:md5sum '", writer%md5sum, "'", &
    char (writer%process_mode), char (writer%process_string)
  write (unit, "(5A)") "clean-", char (id), ":"
  write (unit, "(5A)") TAB, "rm -f ", char (id), ".f90"
  write (unit, "(5A)") TAB, "rm -f opr-", char (id), ".mod"
  write (unit, "(5A)") TAB, "rm -f ", char (id), ".lo"
  write (unit, "(5A)") "CLEAN_SOURCES += ", char (id), ".f90"
  write (unit, "(5A)") "CLEAN_OBJECTS += opr-", char (id), ".mod"
  write (unit, "(5A)") "CLEAN_OBJECTS += ", char (id), ".lo"
  write (unit, "(5A)") char (id), ".lo: ", char (id), ".f90"
  write (unit, "(5A)") TAB, "$(LTF_COMPILE) $<"

end subroutine prc_blha_writer_write_makefile_code

```

(BLHA OLP interfaces: blha writer: TBP)+≡

procedure, nopass:: get_procname => prc_blha_writer_writer_get_procname

(BLHA OLP interfaces: procedures)+≡

```

function prc_blha_writer_writer_get_procname (feature) result (name)
  type(string_t) :: name
  type(string_t), intent(in) :: feature
  select case (char (feature))
    case ("n_in"); name = "number_particles_in"
    case ("n_out"); name = "number_particles_out"
    case ("n_flv"); name = "number_flavor_states"
    case ("n_hel"); name = "number_spin_states"
    case ("n_col"); name = "number_color_flows"
    case ("n_cin"); name = "number_color_indices"
    case ("n_cf"); name = "number_color_factors"
    case ("flv_state"); name = "flavor_states"
    case ("hel_state"); name = "spin_states"
    case ("col_state"); name = "color_flows"
    case default
      name = feature
  end select
end function prc_blha_writer_writer_get_procname

```



```

<BLHA OLP interfaces: blha writer: TBP>+≡
    procedure, nopass :: get_module_name => prc_blha_writer_get_module_name

<BLHA OLP interfaces: procedures>+≡
    function prc_blha_writer_get_module_name (id) result (name)
        type(string_t) :: name
        type(string_t), intent(in) :: id
        name = "opr_" // id
    end function prc_blha_writer_get_module_name

<BLHA OLP interfaces: blha writer: TBP>+≡
    procedure :: write => prc_blha_writer_write

<BLHA OLP interfaces: procedures>+≡
    subroutine prc_blha_writer_write (writer, unit)
        class(prc_blha_writer_t), intent(in) :: writer
        integer, intent(in) :: unit
        write (unit, "(1x,A)") char (writer%get_process_string ())
    end subroutine prc_blha_writer_write

<BLHA OLP interfaces: blha writer: TBP>+≡
    procedure :: get_process_string => prc_blha_writer_get_process_string

<BLHA OLP interfaces: procedures>+≡
    function prc_blha_writer_get_process_string (writer) result (s_proc)
        class(prc_blha_writer_t), intent(in) :: writer
        type(string_t) :: s_proc
        !!! This is a dummy
    end function prc_blha_writer_get_process_string

<BLHA OLP interfaces: blha writer: TBP>+≡
    procedure :: get_n_proc => prc_blha_writer_get_n_proc

<BLHA OLP interfaces: procedures>+≡
    function prc_blha_writer_get_n_proc (writer) result (n_proc)
        class(prc_blha_writer_t), intent(in) :: writer
        integer :: n_proc
        n_proc = blha_configuration_get_n_proc (writer%blha_cfg)
    end function prc_blha_writer_get_n_proc

<BLHA OLP interfaces: blha driver: TBP>≡
    procedure :: set_alpha_qed => blha_driver_set_alpha_qed

<BLHA OLP interfaces: procedures>+≡
    subroutine blha_driver_set_alpha_qed (driver, alpha)
        class(blha_driver_t), intent(inout) :: driver
        real(default), intent(in) :: alpha
        integer :: ierr
        call driver%blha_olp_set_parameter &
            (c_char_'alpha_qed'//c_null_char, &
             dble (alpha), 0._double, ierr)
    end subroutine blha_driver_set_alpha_qed

```

```

<BLHA OLP interfaces: blha driver: TBP>+≡
  procedure(blha_driver_set_alpha_s), deferred :: &
    set_alpha_s

<BLHA OLP interfaces: interfaces>+≡
  abstract interface
    subroutine blha_driver_set_alpha_s (driver, alpha_s)
      import
      class(blha_driver_t), intent(inout) :: driver
      real(default), intent(in) :: alpha_s
    end subroutine blha_driver_set_alpha_s
  end interface

<BLHA OLP interfaces: blha driver: TBP>+≡
  procedure(blha_driver_print_alpha_s), deferred :: &
    print_alpha_s

<BLHA OLP interfaces: interfaces>+≡
  abstract interface
    subroutine blha_driver_print_alpha_s (object)
      import
      class(blha_driver_t), intent(in) :: object
    end subroutine blha_driver_print_alpha_s
  end interface

<BLHA OLP interfaces: blha driver: TBP>+≡
  procedure :: set_mass_and_width => blha_driver_set_mass_and_width

<BLHA OLP interfaces: procedures>+≡
  subroutine blha_driver_set_mass_and_width (driver, &
                                             i_pdg, mass, width)

    class(blha_driver_t), intent(inout) :: driver
    integer, intent(in) :: i_pdg
    real(default), intent(in), optional :: mass
    real(default), intent(in), optional :: width
    type(string_t) :: buf
    character(kind=c_char,len=20) :: c_string
    integer :: ierr
    if (present (mass)) then
      buf = 'mass(' // str (abs(i_pdg)) // ')'
      c_string = char(buf)//c_null_char
      call driver%blha_olp_set_parameter &
        (c_string, dble(mass), 0._double, ierr)
      if (ierr == 0) then
        buf = "BLHA driver: Attempt to set mass of particle " // &
          str (abs(i_pdg)) // "failed"
        call msg_fatal (char(buf))
      end if
    end if
    if (present (width)) then
      buf = 'width(' // str (abs(i_pdg)) // ')'
      c_string = char(buf)//c_null_char
      call driver%blha_olp_set_parameter &
        (c_string, dble(width), 0._double, ierr)
      if (ierr == 0) then

```

```

        buf = "BLHA driver: Attempt to set width of particle " // &
              str (abs(i_pdg)) // "failed"
        call msg_fatal (char(buf))
    end if
end if
end subroutine blha_driver_set_mass_and_width

<BLHA OLP interfaces: blha driver: TBP>+≡
    procedure(blha_driver_init_dlaccess_to_library), deferred :: &
        init_dlaccess_to_library

<BLHA OLP interfaces: interfaces>+≡
    abstract interface
        subroutine blha_driver_init_dlaccess_to_library &
            (object, os_data, dlaccess, success)
        import
        class(blha_driver_t), intent(in) :: object
        type(os_data_t), intent(in) :: os_data
        type(dlaccess_t), intent(out) :: dlaccess
        logical, intent(out) :: success
    end subroutine blha_driver_init_dlaccess_to_library
    end interface

<BLHA OLP interfaces: blha driver: TBP>+≡
    procedure :: load => blha_driver_load

<BLHA OLP interfaces: procedures>+≡
    subroutine blha_driver_load (object, os_data, success)
        class(blha_driver_t), intent(inout) :: object
        type(os_data_t), intent(in) :: os_data
        logical, intent(out) :: success
        type(dlaccess_t) :: dlaccess
        type(c_funptr) :: c_funptr
        logical :: init_success

        call object%init_dlaccess_to_library (os_data, dlaccess, init_success)

        c_funptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_Start"))
        call c_f_procpointer (c_funptr, object%blha_olp_start)
        call check_for_error (var_str ("OLP_Start"))

        c_funptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_EvalSubProcess"))
        call c_f_procpointer (c_funptr, object%blha_olp_eval)
        call check_for_error (var_str ("OLP_EvalSubProcess"))

        c_funptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_Info"))
        call c_f_procpointer (c_funptr, object%blha_olp_info)
        call check_for_error (var_str ("OLP_Info"))

        c_funptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_SetParameter"))
        call c_f_procpointer (c_funptr, object%blha_olp_set_parameter)
        call check_for_error (var_str ("OLP_SetParameter"))

        c_funptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_EvalSubProcess2"))

```

```

call c_f_procpointer (c_fptr, object%blha_olp_eval2)
call check_for_error (var_str ("OLP_EvalSubProcess2"))

!!! Is OLP_Option really not implemented in OpenLoops?
!!! c_fptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_Option"))
!!! call c_f_procpointer (c_fptr, object%blha_olp_option)
!!! call check_for_error (var_str ("OLP_Option"))

!!! Is OLP_Polvec really not implemented in OpenLoops?
!!! c_fptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_Polvec"))
!!! call c_f_procpointer (c_fptr, object%blha_olp_polvec)
!!! call check_for_error (var_str ("OLP_Polvec"))

!!! Is OLP_Polvec really not implemented in OpenLoops?
!!! c_fptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_Finalize"))
!!! call c_f_procpointer (c_fptr, object%blha_olp_finalize)
!!! call check_for_error (var_str ("OLP_Finalize"))

c_fptr = dlaccess_get_c_funptr (dlaccess, var_str ("OLP_PrintParameter"))
call c_f_procpointer (c_fptr, object%blha_olp_print_parameter)
call check_for_error (var_str ("OLP_PrintParameter"))

success = .true.
contains
  subroutine check_for_error (function_name)
    type(string_t), intent(in) :: function_name
    if (dlaccess_has_error (dlaccess)) &
      call msg_fatal (char ("Loading of " // function_name // " failed!"))
  end subroutine check_for_error
end subroutine blha_driver_load

```

(BLHA OLP interfaces: blha driver: TBP)+≡

```

procedure :: read_contract_file => blha_driver_read_contract_file

```

(BLHA OLP interfaces: procedures)+≡

```

subroutine blha_driver_read_contract_file (driver, flavors, amp_type, flv_index, label)
  class(blha_driver_t), intent(inout) :: driver
  integer, intent(in), dimension(:,:) :: flavors
  integer, intent(out), dimension(20) :: amp_type, flv_index, label
  integer :: unit, filestat
  character(len=100) :: rd_line
  logical :: read_flavor, born_found
  integer :: k, i_flv, i_part
  integer :: i_next, n_entries
  integer, dimension(size(flavors, 1) + 2) :: i_array
  integer, parameter :: NO_NUMBER = -1000

  amp_type = -1; flv_index = -1; label = -1
  n_entries = size(flavors, 1) + 2
  unit = free_unit ()
  open (unit, file=char(driver%contract_file), status="old")
  read_flavor=.false.
  k = 1
  do

```

```

read (unit, '(A)', iostat = filestat) rd_line
if (filestat == iostat_end) then
  exit
else
  if (rd_line(1:13) == 'AmplitudeType') then
    i_next = find_next_word_index (rd_line, 13)
    if (rd_line(i_next:i_next+4) == 'Loop') then
      amp_type(k) = BLHA_AMP_LOOP
    else if (rd_line(i_next:i_next+4) == 'Tree') then
      amp_type(k) = BLHA_AMP_TREE
    else if (rd_line(i_next:i_next+6) == 'ccTree') then
      amp_type(k) = BLHA_AMP_CC
    else if (rd_line(i_next:i_next+6) == 'scTree') then
      amp_type(k) = BLHA_AMP_SC
    else
      call msg_fatal ("AmplitudeType present but &
                     &AmpType not known!")
    end if
    read_flavor = .true.
  else if (read_flavor) then
    born_found = .false.
    i_array = create_flavor_string (rd_line, n_entries)
    do i_flg = 1, size (flavors, 2)
      if (all (i_array (1:n_entries-2) == flavors (:,i_flg))) then
        label(k) = i_array (n_entries)
        flv_index (k) = i_flg
        born_found = .true.
        k = k+1
        read_flavor = .false.
        exit
      end if
    end do
    if (.not. born_found) call msg_fatal &
      ("No underlying Born found")
  end if
end if
end do
close(unit)
contains
function create_flavor_string (s, n_entries) result (i_array)
  character(len=100), intent(in) :: s
  integer, intent(in) :: n_entries
  integer, dimension(n_entries) :: i_array
  character(len=10) :: buf
  integer :: k, current_position
  logical :: valid_buffer
  integer :: i_entry
  k = 1; current_position = 1
  do
    if (current_position > 100) &
      call msg_fatal ("Read OLC File: Current position exceeds maximum value")
    if (s(current_position:current_position) /= " ") then
      call create_integer (s, i_entry, current_position)
      if (i_entry /= NO_NUMBER) then

```

```

        i_array(k) = i_entry
        k = k+1
        if (k > n_entries) then
            return
        else
            current_position = find_next_word_index (s, current_position)
        end if
    else
        current_position = find_next_word_index (s, current_position)
    end if
else
    current_position = find_next_word_index (s, current_position)
end if
end do
end function create_flavor_string

subroutine create_integer (s, i_particle, current_position)
    character(len=100), intent(in) :: s
    integer, intent(out) :: i_particle
    integer, intent(inout) :: current_position
    character(len=10) :: buf
    integer :: i
    logical :: valid
    i = 1
    do
        if (s(current_position:current_position) /= " ") then
            buf(i:i) = s(current_position:current_position)
            i = i+1; current_position = current_position+1
        else
            exit
        end if
    end do
    valid = (buf(1:i-1) /= "->" .and. buf(1:i-1) /= "|")
    if (valid) then
        i_particle = read_ival (var_str (buf(1:i-1)))
    else
        i_particle = NO_NUMBER
    end if
end subroutine create_integer

function find_next_word_index (blub, i_start) result (i_next)
    character(len=100), intent(in) :: blub
    integer, intent(in) :: i_start
    integer :: i_next
    i_next = i_start + 1
    do
        if (blub(i_next:i_next) /= " ") then
            exit
        else
            i_next = i_next + 1
        end if
        if (i_next > 100) call msg_fatal ("Find next word: line limit exceeded")
    end do
end function find_next_word_index

```

```

end subroutine blha_driver_read_contract_file

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: needs_mcset => prc_blha_needs_mcset

<BLHA OLP interfaces: procedures>+≡
  function prc_blha_needs_mcset (object) result (flag)
    class(prc_blha_t), intent(in) :: object
    logical :: flag
    flag = .true.
  end function prc_blha_needs_mcset

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: get_n_terms => prc_blha_get_n_terms

<BLHA OLP interfaces: procedures>+≡
  function prc_blha_get_n_terms (object) result (n)
    class(prc_blha_t), intent(in) :: object
    integer :: n
    n = 1
  end function prc_blha_get_n_terms

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: is_allowed => prc_blha_is_allowed

<BLHA OLP interfaces: procedures>+≡
  function prc_blha_is_allowed (object, i_term, f, h, c) result (flag)
    class(prc_blha_t), intent(in) :: object
    integer, intent(in) :: i_term, f, h, c
    logical :: flag
    logical(c_bool) :: cflag
    select type (driver => object%driver)
    class is (blha_driver_t)
    !      call driver%is_allowed (f, h, c, cflag)
    !      flag = cflag
    !      flag = .true.
    class default
    !      call msg_fatal &
    !        ("BLHA instance created, but driver is not a BLHA driver!")
    end select
  end function prc_blha_is_allowed

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: update_alpha_s => prc_blha_update_alpha_s

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_update_alpha_s (object, core_state, fac_scale)
    class(prc_blha_t), intent(in) :: object
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    real(default), intent(in) :: fac_scale
    real(default) :: alpha_qcd
    if (allocated (object%qcd%alpha)) then
      alpha_qcd = object%qcd%alpha%get (fac_scale)
    end if
  end subroutine prc_blha_update_alpha_s

```

```

        select type (driver => object%driver)
        class is (blha_driver_t)
            call driver%update_alpha_s (alpha_qcd)
        end select
    end if
end subroutine prc_blha_update_alpha_s

```

<BLHA OLP interfaces: prc blha: TBP>+≡

```

    procedure :: get_alpha_s => prc_blha_get_alpha_s

```

<BLHA OLP interfaces: procedures>+≡

```

    function prc_blha_get_alpha_s (object, core_state) result (alpha)
        class(prc_blha_t), intent(in) :: object
        class(prc_core_state_t), intent(in), allocatable :: core_state
        real(default) :: alpha
        if (allocated (core_state)) then
            select type (core_state)
            class is (blha_state_t)
                alpha = core_state%alpha_qcd
            end select
        else
            alpha = 0._default
        end if
    end function prc_blha_get_alpha_s

```

<BLHA OLP interfaces: prc blha: TBP>+≡

```

    procedure :: set_alpha_qcd => prc_blha_set_alpha_qcd

```

<BLHA OLP interfaces: procedures>+≡

```

    subroutine prc_blha_set_alpha_qcd (object, alpha)
        class(prc_blha_t), intent(inout) :: object
        real(default), intent(in) :: alpha
        select type (driver => object%driver)
        class is (blha_driver_t)
            call driver%set_alpha_qcd (alpha)
        end select
    end subroutine prc_blha_set_alpha_qcd

```

<BLHA OLP interfaces: prc blha: TBP>+≡

```

    procedure :: read_contract_file => prc_blha_read_contract_file

```

<BLHA OLP interfaces: procedures>+≡

```

    subroutine prc_blha_read_contract_file (object, flavors)
        class(prc_blha_t), intent(inout) :: object
        integer, intent(in), dimension(:,:) :: flavors
        integer, dimension(20) :: amp_type, flv_index, label
        integer :: i_proc
        select type (driver => object%driver)
        class is (blha_driver_t)
            call driver%read_contract_file (flavors, amp_type, flv_index, label)
        end select
        do i_proc = 1, size (amp_type)
            if (amp_type (i_proc) < 0) exit
            select case (amp_type (i_proc))

```



```

case (BLHA_AMP_TREE)
  if (allocated (object%i_born)) then
    object%i_born(flv_index(i_proc)) = label(i_proc)

  else if (allocated (object%i_real)) then
    object%i_real(flv_index(i_proc)) = label(i_proc)
  else
    call msg_fatal ("Tree matrix element present, &
                    &but neither Born nor real indices are allocated!")
  end if
case (BLHA_AMP_CC)
  if (allocated (object%i_cc)) then
    object%i_cc(flv_index(i_proc)) = label(i_proc)
  else
    call msg_fatal ("Color-correlated matrix element present, &
                    &but cc-indices are not allocated!")
  end if
case (BLHA_AMP_SC)
  if (allocated (object%i_sc)) then
    object%i_sc(flv_index(i_proc)) = label(i_proc)
  else
    call msg_fatal ("Spin-correlated matrix element present, &
                    &but sc-indices are not allocated!")
  end if
case (BLHA_AMP_LOOP)
  if (allocated (object%i_virt)) then
    object%i_virt(flv_index(i_proc)) = label(i_proc)
  else
    call msg_fatal ("Loop matrix element present, &
                    &but virt-indices are not allocated!")
  end if
case default
  call msg_fatal ("Undefined amplitude type")
end select
end do
end subroutine prc_blha_read_contract_file

```

(BLHA OLP interfaces: prc blha: TBP)+≡

```

procedure :: print_parameter_file => prc_blha_print_parameter_file

```

(BLHA OLP interfaces: procedures)+≡

```

subroutine prc_blha_print_parameter_file (object)
  class(prc_blha_t), intent(in) :: object
  type(string_t) :: filename

  select type (def => object%def)
  class is (blha_def_t)
    filename = def%basename // '.olp.parameters'
  end select
  select type (driver => object%driver)
  class is (blha_driver_t)
    call driver%blha_olp_print_parameter (char(filename)//c_null_char)
  end select
end subroutine prc_blha_print_parameter_file

```

```

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: compute_hard_kinematics => prc_blha_compute_hard_kinematics
<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_compute_hard_kinematics &
    (object, p_seed, i_term, int_hard, core_state)
    class(prc_blha_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(in) :: p_seed
    integer, intent(in) :: i_term
    type(interaction_t), intent(inout) :: int_hard
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    call int_hard%set_momenta (p_seed)
    if (allocated (core_state)) then
      select type (core_state)
        class is (blha_state_t); core_state%new_kinematics = .true.
      end select
    end if
  end subroutine prc_blha_compute_hard_kinematics

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: compute_eff_kinematics => prc_blha_compute_eff_kinematics
<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_compute_eff_kinematics &
    (object, i_term, int_hard, int_eff, core_state)
    class(prc_blha_t), intent(in) :: object
    integer, intent(in) :: i_term
    type(interaction_t), intent(in) :: int_hard
    type(interaction_t), intent(inout) :: int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
  end subroutine prc_blha_compute_eff_kinematics

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: compute_amplitude => prc_blha_compute_amplitude
<BLHA OLP interfaces: procedures>+≡
  function prc_blha_compute_amplitude &
    (object, j, p, f, h, c, fac_scale, ren_scale, alpha_qcd_forced, &
     core_state) result (amp)
    class(prc_blha_t), intent(in) :: object
    integer, intent(in) :: j
    type(vector4_t), dimension(:), intent(in) :: p
    integer, intent(in) :: f, h, c
    real(default), intent(in) :: fac_scale, ren_scale
    real(default), intent(in), allocatable :: alpha_qcd_forced
    class(prc_core_state_t), intent(inout), allocatable, optional :: core_state
    complex(default) :: amp
    select type (core_state)
      class is (blha_state_t)
        core_state%alpha_qcd = object%qcd%alpha%get (fac_scale)
      end select
    amp = 0.0
  end function prc_blha_compute_amplitude

```

```

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: recover_kinematics => prc_blha_recover_kinematics

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_recover_kinematics &
    (object, p_seed, int_hard, int_eff, core_state)
    class(prc_blha_t), intent(in) :: object
    type(vector4_t), dimension(:), intent(inout) :: p_seed
    type(interaction_t), intent(inout) :: int_hard, int_eff
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    integer :: n_in
    n_in = int_eff%get_n_in ()
    call int_eff%set_momenta (p_seed(1:n_in), outgoing = .false.)
    p_seed(n_in+1:) = int_eff%get_momenta (outgoing = .true.)
  end subroutine prc_blha_recover_kinematics

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: init_blha => prc_blha_init_blha

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_init_blha (object, blha_template)
    class(prc_blha_t), intent(inout) :: object
    type(blha_template_t), intent(inout) :: blha_template
    integer :: i_flv

    object%n_particles = size (object%data%flv_state, 1)
    object%n_flv = size (object%data%flv_state, 2)

    if (blha_template%compute_loop ()) then
      allocate (object%i_virt (object%n_flv), &
        object%i_cc (object%n_flv))
    else if (blha_template%compute_subtraction ()) then
      allocate (object%i_born (object%n_flv), &
        object%i_cc (object%n_flv) , &
        object%i_sc (object%n_flv))
    else if (blha_template%compute_real_trees ()) then
      allocate (object%i_real (object%n_flv))
    end if
  end subroutine prc_blha_init_blha

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: get_nflv => prc_blha_get_nflv

<BLHA OLP interfaces: procedures>+≡
  function prc_blha_get_nflv (object) result (n_flv)
    class(prc_blha_t), intent(in) :: object
    integer :: n_flv
    n_flv = object%n_flv
  end function prc_blha_get_nflv

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: set_parameters => prc_blha_set_parameters

```

```

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_set_parameters (object, qcd, use_color_factors)
    class(prc_blha_t), intent(inout) :: object
    type(qcd_t), intent(in) :: qcd
    logical, intent(in) :: use_color_factors
    object%qcd = qcd
    object%use_color_factors = use_color_factors

  end subroutine prc_blha_set_parameters

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: set_particle_properties => prc_blha_set_particle_properties

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_set_particle_properties (object, model)
    class(prc_blha_t), intent(inout) :: object
    class(model_data_t), intent(in), target :: model
    integer :: i, i_pdg
    type(flavor_t) :: flv
    real(default) :: mass, width
    do i = 1, OLP_N_MASSIVE_PARTICLES
      i_pdg = OLP_MASSIVE_PARTICLES(i)
      call flv%init (i_pdg, model)
      mass = flv%get_mass (); width = flv%get_width ()
      select type (driver => object%driver)
        class is (blha_driver_t)
          call driver%set_mass_and_width (i_pdg, mass=mass, width=width)
        end select
      end do
    end subroutine prc_blha_set_particle_properties

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: set_bquark_mass => prc_blha_set_bquark_mass

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_set_bquark_mass (object, model)
    class(prc_blha_t), intent(inout) :: object
    class(model_data_t), intent(in), target :: model
    type(flavor_t) :: flv
    real(default) :: mass, width
    integer :: ierr
    call flv%init (5, model)
    mass = flv%get_mass (); width = flv%get_width ()
    select type (driver => object%driver)
      class is (blha_driver_t)
        call driver%set_mass_and_width (5, mass=mass, width=width)
        call driver%blha_olp_set_parameter ('yuk(5)'/c_null_char, &
          dble(mass), 0._double, ierr)
      end select
    end subroutine prc_blha_set_bquark_mass

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: compute_sqme_virt => prc_blha_compute_sqme_virt

```

```

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_compute_sqme_virt (object, &
    i_flv, p, ren_scale, sqme, bad_point)
    class(prc_blha_t), intent(inout) :: object
    integer, intent(in) :: i_flv
    type(vector4_t), dimension(:), intent(in) :: p
    real(default), intent(in) :: ren_scale
    logical, intent(out) :: bad_point
    real(default), dimension(4), intent(out) :: sqme
    real(double), dimension(5*object%n_particles) :: mom
    real(double), dimension(blha_result_array_size (object%n_particles, &
      BLHA_AMP_LOOP)) :: r

    real(double) :: mu_dble
    real(default) :: mu
    real(double) :: acc_dble
    real(default) :: acc
    real(default) :: alpha_s

    mom = object%create_momentum_array (p)
    if (ren_scale == 0.0) then
      mu = sqrt (2* (p(1)*p(2)))
    else
      mu = ren_scale
    end if
    mu_dble = dble(mu)
    alpha_s = object%qcd%alpha%get (mu)
    select type (driver => object%driver)
    class is (blha_driver_t)
      call driver%set_alpha_s (alpha_s)
      call driver%blha_olp_eval2 (object%i_virt(i_flv), &
        mom, mu_dble, r, acc_dble)
    end select
    acc = acc_dble
    sqme = r(1:4)
    if (acc > object%maximum_accuracy) then
      bad_point = .true.
    else
      bad_point = .false.
    end if
  end subroutine prc_blha_compute_sqme_virt

```

```

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure(prc_blha_compute_sqme_real), deferred :: &
    compute_sqme_real

```

```

<BLHA OLP interfaces: interfaces>+≡
  abstract interface
    subroutine prc_blha_compute_sqme_real (object, i_flv, &
      p, ren_scale, sqme, bad_point)
    import
    class(prc_blha_t), intent(inout) :: object
    integer, intent(in) :: i_flv
    type(vector4_t), intent(in), dimension(:) :: p
    real(default), intent(in) :: ren_scale
  end interface

```

```

    real(default), intent(out) :: sqme
    logical, intent(out) :: bad_point
end subroutine prc_blha_compute_sqme_real
end interface

```

Compute the Born matrix element. This will always occur in connection to a subtraction term, so scales and couplings have already been set, and the momenta are in the BLHA format. Hence, the interface is simpler than in the other routines.

```

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure(prc_blha_compute_sqme_born), deferred :: &
    compute_sqme_born

<BLHA OLP interfaces: interfaces>+≡
  abstract interface
    subroutine prc_blha_compute_sqme_born (object, i_born, &
      mom, mu, sqme, acc_born)
    import
    class(prc_blha_t), intent(inout) :: object
    integer, intent(in) :: i_born
    real(double), intent(in), dimension(5*object%n_particles) :: mom
    real(double), intent(in) :: mu
    real(default), intent(out) :: sqme
    real(default), intent(out) :: acc_born
  end subroutine prc_blha_compute_sqme_born
end interface

<BLHA OLP interfaces: prc blha: TBP>+≡
  procedure :: compute_sqme_cc => prc_blha_compute_sqme_cc

<BLHA OLP interfaces: procedures>+≡
  subroutine prc_blha_compute_sqme_cc &
    (object, i_flv, p, ren_scale, &
      born_out, born_cc, bad_point)
    class(prc_blha_t), intent(inout) :: object
    integer, intent(in) :: i_flv
    type(vector4_t), intent(in), dimension(:) :: p
    real(default), intent(in) :: ren_scale
    real(default), intent(out), optional :: born_out
    real(default), intent(inout), dimension(:,:) :: born_cc
    logical, intent(out) :: bad_point
    real(double), dimension(5*object%n_particles) :: mom
    real(double), dimension(blha_result_array_size (object%n_particles, &
      BLHA_AMP_CC)) :: r

    real(default) :: mu
    real(double) :: mu_dble
    real(default) :: alpha_s
    integer :: i, j, pos
    integer :: im1, jm1
    real(double) :: acc_dble
    real(default) :: acc1, acc2
    real(default) :: born

    mom = object%create_momentum_array (p)

```

```

if (ren_scale == 0.0) then
  mu = sqrt (2*p(1)*p(2))
else
  mu = ren_scale
end if
mu_dble = dble(mu)
alpha_s = object%qcd%alpha%get (mu)
select type (driver => object%driver)
class is (blha_driver_t)
  call driver%set_alpha_s (alpha_s)
  if (allocated (object%i_born)) then
    call object%compute_sqme_born (object%i_born(i_flg), &
                                  mom, mu_dble, born, acc1)
  else
    born = 0._default
    acc1 = 0._default
  end if
  if (present (born_out)) born_out = born
  call driver%blha_olp_eval2 (object%i_cc(i_flg), &
                              mom, mu_dble, r, acc_dble)
end select
do j = 1, size (p)
  do i = 1, j
    if (i <= 2 .or. j <= 2) then
      born_cc (i,j) = 0._default
    else if (i == j) then
      born_cc (i,j) = -cf*born
    else
      im1 = i-1; jm1 = j-1
      pos = im1 + jm1*(jm1-1)/2 + 1
      born_cc (i,j) = -r(pos)
    end if
    born_cc (j,i) = born_cc (i,j)
  end do
end do
acc2 = acc_dble
if (acc1 > object%maximum_accuracy .or. &
    acc2 > object%maximum_accuracy) then
  bad_point = .true.
end if
end subroutine prc_blha_compute_sqme_cc

```

(BLHA OLP interfaces: prc blha: TBP)+≡
 procedure(prc_blha_compute_sqme_sc), deferred :: &
 compute_sqme_sc

(BLHA OLP interfaces: interfaces)+≡
 abstract interface
 subroutine prc_blha_compute_sqme_sc (object, &
 i_flg, em, p, ren_scale_in, me_sc, bad_point)
 import
 class(prc_blha_t), intent(inout) :: object
 integer, intent(in) :: i_flg, em
 type(vector4_t), intent(in), dimension(:) :: p

```

        real(default), intent(in) :: ren_scale_in
        complex(default), intent(out) :: me_sc
        logical, intent(out) :: bad_point
    end subroutine prc_blha_compute_sqme_sc
end interface

```

```

<BLHA OLP interfaces: prc blha: TBP>+≡
    procedure(prc_blha_init_driver), deferred :: &
        init_driver

```

```

<BLHA OLP interfaces: interfaces>+≡
    abstract interface
        subroutine prc_blha_init_driver (object, os_data)
            import
            class(prc_blha_t), intent(inout) :: object
            type(os_data_t), intent(in) :: os_data
        end subroutine prc_blha_init_driver
    end interface

```

The module is split into a configuration interface which manages configuration and handles the request and contract files, a module which interfaces the OLP matrix elements and a driver.

```

<blha_config.f90>≡
    <File header>

```

```

module blha_config

    use kinds
    <Use strings>
    use io_units
    use constants
    use string_utils
    use system_defs, only: EOF
    use diagnostics
    use md5
    use model_data
    use flavors
    use quantum_numbers
    use pdg_arrays
    use sorting
    use lexers
    use parser
    use syntax_rules
    use ifiles

    use fks_regions, only: flv_structure_t

```

```

    <Standard module head>

```

```

    <BLHA config: public>

```

```

    <BLHA config: parameters>

```

```

    <BLHA config: types>

```



```

    <BLHA config: variables>

    <BLHA config: interfaces>

contains

    <BLHA config: procedures>

end module blha_config

<blha_interface.f90>≡
    <File header>

    module blha_interface

    <Use strings>
        use io_units
        use string_utils
        use constants
        use diagnostics
        use sm_physics
        use md5
        use lorentz
        use model_data
        use flavors
        use quantum_numbers
        use interactions
        use evaluators
        use particles
        use quantum_numbers
        use blha_config
        use, intrinsic :: iso_c_binding !NODEP!
        use os_interface

    <Standard module head>

    <BLHA interface: public>

    <BLHA interface: types>

    <BLHA interface: interfaces>

contains

    <BLHA interface: procedures>

end module blha_interface

<blha_driver.f90>≡
    <File header>

    module blha_driver

```

```

<Use strings>
  use io_units
  use constants
  use diagnostics
  use sm_physics
  use md5
  use lorentz
  use model_data
  use flavors
  use quantum_numbers
  use interactions
  use evaluators
  use particles
  use quantum_numbers
  use blha_config
  use blha_interface

<Standard module head>

<BLHA driver: public>

contains

<BLHA driver: procedures>

end module blha_driver

```

23.2 Configuration

Parameters to enumerate the different options in the order.

```

<BLHA config: parameters>≡
  integer, public, parameter :: &
    BLHA_MEST_SUM=1, BLHA_MEST_AVG=2, BLHA_MEST_OTHER=3
  integer, public, parameter :: &
    BLHA_CT_QCD=1, BLHA_CT_EW=2, BLHA_CT_QED=3, BLHA_CT_OTHER=4
  integer, public, parameter :: &
    BLHA_IRREG_CDR=1, BLHA_IRREG_DRED=2, BLHA_IRREG_THV=3, &
    BLHA_IRREG_MREG=4, BLHA_IRREG_OTHER=5
  integer, public, parameter :: &
    BLHA_SUBMODE_NONE = 1, BLHA_SUBMODE_OTHER = 2
  integer, public, parameter :: &
    BLHA_MPS_ONSHELL=1, BLHA_MPS_OTHER=2
  integer, public, parameter :: &
    BLHA_MODE_GOSAM=1, BLHA_MODE_FEYNARTS = 2, BLHA_MODE_GENERIC=3, &
    BLHA_MODE_OPENLOOPS=4
  integer, public, parameter :: &
    BLHA_OM_NONE=1, BLHA_OM_NOCPL=2, BLHA_OM_OTHER=3
  integer, public, parameter :: &
    BLHA_VERSION_1 = 1, BLHA_VERSION_2 = 2
  integer, public, parameter :: &
    BLHA_AMP_LOOP = 1, BLHA_AMP_CC = 2, BLHA_AMP_SC = 3, &
    BLHA_AMP_TREE = 4, BLHA_AMP_LOOPINDUCED = 5
  integer, public, parameter :: &

```

```

        BLHA_EW_GF = 1, BLHA_EW_MZ = 2, BLHA_EW_MSBAR = 3, &
        BLHA_EW_0 = 4, BLHA_EW_RUN = 5, BLHA_EW_DEFAULT = 6
integer, public, parameter :: &
    BLHA_WIDTH_COMPLEX = 1, BLHA_WIDTH_FIXED = 2, &
    BLHA_WIDTH_RUNNING = 3, BLHA_WIDTH_POLE = 4, &
    BLHA_WIDTH_DEFAULT = 5

```

Those are the default pdg codes for massive particles in BLHA programs

```

<BLHA config: parameters>+=
integer, parameter, public :: OLP_N_MASSIVE_PARTICLES = 10
integer, dimension(OLP_N_MASSIVE_PARTICLES), public :: &
    OLP_MASSIVE_PARTICLES = [5,-5,6,-6,15,-15,23,24,-24,25]

```

This type encapsulates a BLHA request.

```

<BLHA config: public>=
public :: blha_configuration_t
public :: blha_cfg_process_node_t

<BLHA config: types>=
type :: blha_cfg_process_node_t
    integer, dimension(:), allocatable :: pdg_in, pdg_out
    integer, dimension(:), allocatable :: fingerprint
    integer :: nsub
    integer, dimension(:), allocatable :: ids
    integer :: amplitude_type
    type(blha_cfg_process_node_t), pointer :: next => null ()
end type blha_cfg_process_node_t

type :: blha_configuration_t
    type(string_t) :: name
    class(model_data_t), pointer :: model => null ()
    type(string_t) :: md5
    integer :: version = 2
    logical :: dirty = .false.
    integer :: n_proc = 0
    real(default) :: accuracy_target
    logical :: debug_unstable
    integer :: mode = BLHA_MODE_GENERIC
    type(blha_cfg_process_node_t), pointer :: processes => null ()
    integer, dimension(2) :: matrix_element_square_type = BLHA_MEST_SUM
    integer :: correction_type = BLHA_CT_QCD
    type(string_t) :: correction_type_other
    integer :: irreg = BLHA_IRREG_THV
    type(string_t) :: irreg_other
    integer :: massive_particle_scheme = BLHA_MPS_ONSHELL
    type(string_t) :: massive_particle_scheme_other
    integer :: subtraction_mode = BLHA_SUBMODE_NONE
    type(string_t) :: subtraction_mode_other
    type(string_t) :: model_file
    logical :: subdivide_subprocesses = .false.
    integer :: alphas_power = -1, alpha_power = -1
    integer :: ew_scheme = BLHA_EW_DEFAULT
    integer :: width_scheme = BLHA_WIDTH_DEFAULT
    integer :: operation_mode = BLHA_OM_NONE

```

```

        type(string_t) :: operation_mode_other
    end type blha_configuration_t

```

This types control the creation of BLHA-interface files

```

<BLHA config: public>+≡
    public :: blha_flv_state_t
    public :: blha_master_t

<BLHA config: types>+≡
    type :: blha_flv_state_t
        integer, dimension(:), allocatable :: flavors
        integer :: flv_mult
        logical :: flv_real = .false.
    end type blha_flv_state_t

    type :: blha_master_t
        integer, dimension(3) :: blha_mode
        ! integer, dimension(:, :), allocatable :: flv_born, flv_real
        integer :: n_in, n_out
        logical :: compute_loops = .true.
        logical :: compute_correlations = .false.
        logical :: compute_real_trees = .false.
        integer :: alpha_power, alphas_power
        type(string_t) :: basename
        type(string_t), dimension(:), allocatable :: suffix
        type(blha_configuration_t), dimension(:), allocatable :: blha_cfg
        integer :: n_files = 0
    contains
        <BLHA config: blha master: TBP>
    end type blha_master_t

```

Master-Routines

```

<BLHA config: blha master: TBP>≡
    procedure :: init => blha_master_init

<BLHA config: procedures>≡
    subroutine blha_master_init (master, basename, model, &
                                n_in, n_out, &
                                cmp_loops, cmp_corr, cmp_real, &
                                alpha_power, alphas_power, &
                                flv_born, flv_real)

        class(blha_master_t), intent(inout) :: master
        type(string_t), intent(in) :: basename
        class(model_data_t), intent(in), target :: model
        integer, intent(in) :: n_in, n_out
        logical, intent(in) :: cmp_loops, cmp_corr, cmp_real
        integer, intent(in) :: alpha_power, alphas_power
        integer, dimension(:, :), allocatable, intent(in) :: &
            flv_born, flv_real

        integer :: n_proc, n_proc_real, n_flv
        type(blha_flv_state_t), dimension(:), allocatable :: blha_flavor
        integer :: i, i_flv
        integer :: i_file
        integer, dimension(:), allocatable :: amp_type
    end subroutine blha_master_init

```

```

n_proc = 0; n_flv = 1; n_proc_real = 0
master%compute_real_trees = cmp_real
if (cmp_loops) master%n_files = master%n_files+1
if (cmp_corr) master%n_files = master%n_files+1
if (cmp_real) then
  if (allocated (flv_real)) then
    master%n_files = master%n_files+1
    n_proc_real = size (flv_real, 2)
    n_flv = n_flv + n_proc_real
  end if
end if
allocate (master%blha_cfg (master%n_files))
allocate (master%suffix (master%n_files))
i_file = 1
if (cmp_loops) then
  if (allocated (flv_born)) then
    allocate (blha_flavor (size (flv_born, 2)))
    do i_flv = 1, size (flv_born, 2)
      blha_flavor(i_flv)%flavors = flv_born(:,i_flv)
      blha_flavor(i_flv)%flv_mult = 2
    end do
    master%suffix(i_file) = "_LOOP"
    call blha_init_virtual (master%blha_cfg(i_file), blha_flavor, &
      alpha_power, alphas_power, &
      basename, model, master%blha_mode(1))

    i_file = i_file+1
  else
    call msg_fatal ("GoSam Loops requested but " &
      // "Born flavor not existing")
  end if
end if
if (allocated (blha_flavor)) deallocate (blha_flavor)
if (cmp_corr) then
  if (allocated (flv_born)) then
    allocate (blha_flavor (size (flv_born, 2)))
    do i_flv = 1, size (flv_born, 2)
      blha_flavor(i_flv)%flavors = flv_born(:,i_flv)
      blha_flavor(i_flv)%flv_mult = 3
    end do
    master%suffix(i_file) = "_SUB"
    call blha_init_subtraction (master%blha_cfg(i_file), blha_flavor, &
      alpha_power, alphas_power, &
      basename, model, master%blha_mode(2))

    i_file = i_file+1
  else
    call msg_fatal ("GoSam Correlations requested but "&
      // "Born flavor not existing")
  end if
end if
if (allocated (blha_flavor)) deallocate (blha_flavor)
if (cmp_real) then
  if (allocated (flv_real)) then
    allocate (blha_flavor (size (flv_real, 2)))

```

```

do i_flg = 1, size (flv_real, 2)
  blha_flavor(i_flg)%flavors = flv_real(:,i_flg)
  blha_flavor(i_flg)%flv_mult = 1
end do
master%suffix(i_file) = "_REAL"
call blha_init_real (master%blha_cfg(i_file), blha_flavor, &
                    alpha_power, alphas_power, &
                    basename, model, master%blha_mode(3))
else
  call msg_fatal ("GoSam Trees requested but "&
                 // "Real flavor not existing")
end if
end if
end subroutine blha_master_init

```

<BLHA config: blha master: TBP>+≡

```

procedure :: set_gosam => blha_master_set_gosam

```

<BLHA config: procedures>+≡

```

subroutine blha_master_set_gosam (master, i)
  class(blha_master_t), intent(inout) :: master
  integer, intent(in) :: i
  master%blha_mode(i) = BLHA_MODE_GOSAM
end subroutine blha_master_set_gosam

```

<BLHA config: blha master: TBP>+≡

```

procedure :: set_openloops => blha_master_set_openloops

```

<BLHA config: procedures>+≡

```

subroutine blha_master_set_openloops (master, i)
  class(blha_master_t), intent(inout) :: master
  integer, intent(in) :: i
  master%blha_mode(i) = BLHA_MODE_OPENLOOPS
end subroutine blha_master_set_openloops

```

<BLHA config: procedures>+≡

```

subroutine blha_init_virtual (blha_cfg, blha_flavor, ap, asp, basename, model, blha_mode)
  type(blha_configuration_t), intent(inout) :: blha_cfg
  type(blha_flg_state_t), intent(in), dimension(:) :: blha_flavor
  integer, intent(in) :: ap, asp
  type(string_t), intent(in) :: basename
  type(model_data_t), intent(in), target :: model
  integer, intent(in) :: blha_mode
  integer, dimension(:), allocatable :: amp_type
  integer :: i, ew_scheme

  allocate (amp_type (size (blha_flavor)*2))
  do i = 1, size (blha_flavor)
    amp_type(2*i-1) = BLHA_AMP_LOOP
    amp_type(2*i) = BLHA_AMP_CC
  end do
  call blha_configuration_init (blha_cfg, basename // "_LOOP" , &
                              model, blha_mode)

```

```

call blha_configuration_append_processes (blha_cfg, &
                                         blha_flavor, amp_type)

select case (blha_cfg%mode)
case (BLHA_MODE_GOSAM)
    ew_scheme = BLHA_EW_GF
case (BLHA_MODE_OPENLOOPS)
    ew_scheme = BLHA_EW_0
end select
call blha_configuration_set (blha_cfg, 2, &
                             correction_type = BLHA_CT_QCD, &
                             irreg = BLHA_IRREG_CDR, &
                             alphas_power = asp, &
                             alpha_power = ap, &
                             ew_scheme = ew_scheme, &
                             debug = blha_mode == BLHA_MODE_GOSAM)
end subroutine blha_init_virtual

subroutine blha_init_subtraction (blha_cfg, blha_flavor, ap, asp, basename, model, blha_mode)
    type(blha_configuration_t), intent(inout) :: blha_cfg
    type(blha_flv_state_t), intent(in), dimension(:) :: blha_flavor
    integer, intent(in) :: ap, asp
    type(string_t), intent(in) :: basename
    type(model_data_t), intent(in), target :: model
    integer, intent(in) :: blha_mode
    integer, dimension(:), allocatable :: amp_type
    integer :: i, ew_scheme

    allocate (amp_type (size (blha_flavor)*3))
    do i = 1, size (blha_flavor)
        amp_type(3*i-2) = BLHA_AMP_TREE
        amp_type(3*i-1) = BLHA_AMP_CC
        amp_type(3*i) = BLHA_AMP_SC
    end do
    call blha_configuration_init (blha_cfg, basename // "_SUB" , &
                                 model, blha_mode)
    call blha_configuration_append_processes (blha_cfg, &
                                              blha_flavor, amp_type)

    select case (blha_cfg%mode)
    case (BLHA_MODE_GOSAM)
        ew_scheme = BLHA_EW_GF
    case (BLHA_MODE_OPENLOOPS)
        ew_scheme = BLHA_EW_0
    end select
    call blha_configuration_set (blha_cfg, 2, &
                                correction_type = BLHA_CT_QCD, &
                                irreg = BLHA_IRREG_CDR, &
                                alphas_power = asp, &
                                alpha_power = ap, &
                                ew_scheme = ew_scheme, &
                                debug = .true.)
!
                                debug = blha_mode == BLHA_MODE_GOSAM)
end subroutine blha_init_subtraction

subroutine blha_init_real (blha_cfg, blha_flavor, ap, asp, basename, model, blha_mode)

```

```

type(blha_configuration_t), intent(inout) :: blha_cfg
type(blha_flv_state_t), intent(in), dimension(:) :: blha_flavor
integer, intent(in) :: ap, asp
type(string_t), intent(in) :: basename
type(model_data_t), intent(in), target :: model
integer, intent(in) :: blha_mode
integer, dimension(:), allocatable :: amp_type
integer :: i, ew_scheme

allocate (amp_type (size (blha_flavor)))
do i = 1, size (blha_flavor)
    amp_type(i) = BLHA_AMP_TREE
end do
call blha_configuration_init (blha_cfg, basename // "_REAL" , &
                             model, blha_mode)
call blha_configuration_append_processes (blha_cfg, &
                                         blha_flavor, amp_type)

select case (blha_cfg%mode)
case (BLHA_MODE_GOSAM)
    ew_scheme = BLHA_EW_GF
case (BLHA_MODE_OPENLOOPS)
    ew_scheme = BLHA_EW_0
end select
call blha_configuration_set (blha_cfg, 2, &
                             correction_type = BLHA_CT_QCD, &
                             irreg = BLHA_IRREG_CDR, &
                             alphas_power = asp+1, &
                             alpha_power = ap, &
                             ew_scheme = ew_scheme, &
                             debug = .true.)
!
debug = blha_mode == BLHA_MODE_GOSAM)

end subroutine blha_init_real

```

<BLHA config: blha master: TBP>+≡

```
procedure :: generate => blha_master_generate
```

<BLHA config: procedures>+≡

```

subroutine blha_master_generate (master, basename)
class(blha_master_t), intent(in) :: master
type(string_t), intent(in) :: basename
integer :: unit
type(string_t) :: filename
integer :: i_file
do i_file = 1, master%n_files
    filename = basename // master%suffix(i_file) // ".olp"
    unit = free_unit ()
    open (unit, file = char (filename), status = 'replace', action = 'write')
    call blha_configuration_write (master%blha_cfg(i_file), unit)
    close (unit)
end do
end subroutine blha_master_generate

```

Initializer.

<BLHA config: public>+≡


```

public :: blha_configuration_init
<BLHA config: procedures>+≡
subroutine blha_configuration_init (cfg, name, model, mode)
  type(blha_configuration_t), intent(inout) :: cfg
  type(string_t), intent(in) :: name
  class(model_data_t), target, intent(in) :: model
  integer, intent(in), optional :: mode
  if (.not. associated (cfg%model)) then
    cfg%name = name
    cfg%model => model
  end if
  if (present (mode)) cfg%mode = mode
end subroutine blha_configuration_init

```

Finalizer.

```

<BLHA config: public>+≡
public :: blha_configuration_final
<BLHA config: procedures>+≡
subroutine blha_configuration_final (cfg)
  type(blha_configuration_t), intent(inout) :: cfg
  type(blha_cfg_process_node_t), pointer :: cur, next
  cur => cfg%processes
  do while (associated (cur))
    next => cur%next
    deallocate (cur)
    nullify (cur)
    cur => next
  end do
end subroutine blha_configuration_final

```

Merge sort a process list w.r.t. to the process fingerprints. This is necessary for canonicalizing the process list prior to calculating the MD5 sum.

```

<BLHA config: procedures>+≡
subroutine sort_processes (list, n)
  type(blha_cfg_process_node_t), pointer :: list
  integer, intent(in), optional :: n
  type :: pnode
  type(blha_cfg_process_node_t), pointer :: p
end type pnode
type(pnode), dimension(:), allocatable :: array
integer :: count, i, s, i1, i2, i3
type(blha_cfg_process_node_t), pointer :: node
if (present (n)) then
  count = n
else
  node => list
  count = 0
  do while (associated (node))
    node => node%next
    count = count + 1
  end do
end if
end if

```

```

! Store list nodes into an array
if (count == 0) return
allocate (array(count))
i = 1
node => list
do i = 1, count
    array(i)%p => node
    node => node%next
end do
s = 1
! Merge sort the array
do while (s < count)
    i = 0
    i1 = 1
    i2 = s
    do while (i2 < count)
        i3 = min (s*(i+2), count)
        array(i1:i3) = merge (array(i1:i2), array(i2+1:i3))
        i = i + 2
        i1 = s*i+1
        i2 = s*(i+1)
    end do
    s = s * 2
end do
! Relink according to their new order
list => array(1)%p
nullify (array(count)%p%next)
node => list
do i = 2, count
    node%next => array(i)%p
    node => node%next
end do

contains

! .le. comparision
function lt (n1, n2) result (predicate)
    type(blha_cfg_process_node_t), intent(in) :: n1, n2
    logical :: predicate
    integer :: i
    predicate = .true.
    do i = 1, size (n1%fingerprint)
        if (n1%fingerprint(i) < n2%fingerprint(i)) return
        if (n1%fingerprint(i) > n2%fingerprint(i)) then
            predicate = .false.
            return
        end if
    end do
end function lt

! Sorting core --- merge two sorted chunks
function merge (l1, l2) result (lo)
    type(pnode), dimension(:), intent(in) :: l1, l2
    type(pnode), dimension(size (l1) + size (l2)) :: lo

```

```

integer :: i, i1, i2
i1 = 1
i2 = 1
do i = 1, size (lo)
  if (i1 > size (l1)) then
    lo(i)%p => l2(i2)%p
    i2 = i2 + 1
  elseif (i2 > size (l2)) then
    lo(i)%p => l1(i1)%p
    i1 = i1 + 1
  elseif (lt (l1(i1)%p, l2(i2)%p)) then
    lo(i)%p => l1(i1)%p
    i1 = i1 + 1
  else
    lo(i)%p => l2(i2)%p
    i2 = i2 + 1
  end if
end do
end function merge

end subroutine sort_processes

```

Create an array of massive particle indices, to be used by the "MassiveParticle"-statement of the order file.

(BLHA config: procedures)+≡

```

subroutine blha_configuration_get_massive_particles &
  (cfg, massive, i_massive)
  type(blha_configuration_t), intent(in) :: cfg
  logical, intent(out) :: massive
  integer, intent(out), dimension(:), allocatable :: i_massive
  integer, parameter :: max_particles = 10
  integer, dimension(max_particles) :: i_massive_tmp
  integer, dimension(max_particles) :: checked
  type(blha_cfg_process_node_t), pointer :: current_process
  integer :: k
  integer :: n_massive
  n_massive = 0; k = 1
  checked = 0
  if (associated (cfg%processes)) then
    current_process => cfg%processes
  else
    call msg_fatal ("BLHA, massive particles: " // &
      "No processes allocated!")
  end if
  do
    call check_pdg_list (current_process%pdg_in)
    call check_pdg_list (current_process%pdg_out)
    if (k > max_particles) &
      call msg_fatal ("BLHA, massive particles: " // &
        "Max. number of particles exceeded!")
    if (associated (current_process%next)) then
      current_process => current_process%next
    else

```

```

        exit
    end if
end do
if (n_massive > 0) then
    allocate (i_massive (n_massive))
    i_massive = i_massive_tmp (1:n_massive)
    massive = .true.
else
    massive = .false.
end if
contains
subroutine check_pdg_list (pdg_list)
    integer, dimension(:), intent(in) :: pdg_list
    integer :: i, i_pdg
    type(flavor_t) :: flv
    do i = 1, size (pdg_list)
        i_pdg = abs (pdg_list(i))
        call flv%init (i_pdg, cfg%model)
        if (flv%get_mass () > 0._default) then
            !!! Avoid duplicates in output
            if (.not. any (checked == i_pdg)) then
                i_massive_tmp(k) = i_pdg
                checked(k) = i_pdg
                k=k+1
                n_massive=n_massive+1
            end if
        end if
    end do
end subroutine check_pdg_list
end subroutine blha_configuration_get_massive_particles

```

Append a process. This expands the flavor sum, sorts it and then eliminates any duplicates.

<BLHA config: public>+≡

```
public :: blha_configuration_append_process
```

<BLHA config: procedures>+≡

```

subroutine blha_configuration_append_process (cfg, pdg_in, pdg_out, nsub, ids)
    type(blha_configuration_t), intent(inout) :: cfg
    type(pdg_array_t), dimension(:), intent(in) :: pdg_in, pdg_out
    integer, optional, intent(in) :: nsub
    integer, optional, dimension(:), intent(in) :: ids
    type(blha_cfg_process_node_t), pointer :: root, node, tmp
    ! Multiindex for counting through the PDG numbers
    integer, dimension(size (pdg_in)) :: i_in
    integer, dimension(size (pdg_out)) :: i_out
    ! Handle the list of lists
    type :: ilist
        integer, dimension(:), allocatable :: i
    end type ilist
    type(ilist), dimension(size (pdg_in)) :: ilist_i
    type(ilist), dimension(size (pdg_out)) :: ilist_o
    integer :: i, j, nproc
    logical :: inc

```

```

! Extract PDGs into integer lists
do i = 1, size (pdg_in)
    ilist_i(i)%i = pdg_in(i)
end do
do i = 1, size (pdg_out)
    ilist_o(i)%i = pdg_out(i)
end do
i_in = 1
i_out = 1
allocate (root)
node => root
! Perform the expansion
nproc = 0
EXPAND: do
    ! Transfer the PDG selection...
    allocate (node%pdg_in(size (pdg_in)))
    allocate (node%pdg_out(size (pdg_out)))
    allocate (node%fingerprint (size (pdg_in) + size (pdg_out)))
    if (present (nsub)) node%nsub = nsub
    if (present (ids)) then
        allocate (node%ids(size (ids)))
        node%ids = ids
    end if
    forall (j=1:size(ilist_i)) &
        node%pdg_in(j) = ilist_i(j)%i(i_in(j))
    forall (j=1:size(ilist_o)) &
        node%pdg_out(j) = ilist_o(j)%i(i_out(j))
    node%fingerprint = [ node%pdg_in, sort (node%pdg_out) ]
    nproc = nproc + 1
    inc = .false.
    ! ... and increment the multiindex
    do j = 1, size (i_out)
        if (i_out(j) < size (ilist_o(j)%i)) then
            i_out(j) = i_out(j) + 1
            inc = .true.
            exit
        else
            i_out(j) = 1
        end if
    end do
    if (.not. inc) then
        do j = 1, size (i_in)
            if (i_in(j) < size (ilist_i(j)%i)) then
                i_in(j) = i_in(j) + 1
                inc = .true.
                exit
            else
                i_in(j) = 1
            end if
        end do
    end if
    if (.not. inc) exit EXPAND
    allocate (node%next)
    node => node%next
end do

```

```

end do EXPAND
! Do the sorting
call sort_processes (root, nproc)
! Kill duplicates
node => root
do while (associated (node))
  if (.not. associated (node%next)) exit
  if (all (node%fingerprint == node%next%fingerprint)) then
    tmp => node%next%next
    deallocate (node%next)
    node%next => tmp
    nproc = nproc - 1
  else
    node => node%next
  end if
end do
! Append the remaining list
if (associated (cfg%processes)) then
  node => cfg%processes
  do while (associated (node%next))
    node => node%next
  end do
  node%next => root
else
  cfg%processes => root
end if
cfg%n_proc = cfg%n_proc + nproc
cfg%dirty = .true.

end subroutine blha_configuration_append_process

```

(BLHA config: public)+≡

public :: blha_configuration_append_processes

(BLHA config: procedures)+≡

```

subroutine blha_configuration_append_processes (cfg, flavor, amp_type)
  type(blha_configuration_t), intent(inout) :: cfg
  type(blha_flv_state_t), dimension(:), intent(in) :: flavor
  integer, dimension(:), intent(in), optional :: amp_type
  integer :: n_tot
  type(blha_cfg_process_node_t), pointer :: current_node
  integer :: i_process, i_flv
  integer, dimension(:), allocatable :: pdg_in, pdg_out
  integer, dimension(:), allocatable :: flavor_state
  integer :: proc_offset, n_proc_tot
  proc_offset = 0; n_proc_tot = 0
  do i_flv = 1, size (flavor)
    n_proc_tot = n_proc_tot + flavor(i_flv)%flv_mult
  end do
  if (.not. associated (cfg%processes)) &
    allocate (cfg%processes)
  current_node => cfg%processes
  do i_flv = 1, size (flavor)
    n_tot = size (flavor(i_flv)%flavors)

```

```

allocate (pdg_in (2), pdg_out (n_tot - 2))
allocate (flavor_state (n_tot))
flavor_state = flavor(i_flg)%flavors
do i_process = 1, flavor(i_flg)%flv_mult
  pdg_in = flavor_state (1:2)
  pdg_out = flavor_state (3:)
  current_node%pdg_in = pdg_in
  current_node%pdg_out = pdg_out
  current_node%amplitude_type = amp_type (proc_offset+i_process)
  if (proc_offset+i_process /= n_proc_tot) then
    allocate (current_node%next)
    current_node => current_node%next
  end if
  if (i_process == flavor(i_flg)%flv_mult) &
    proc_offset = proc_offset + flavor(i_flg)%flv_mult
end do
deallocate (pdg_in, pdg_out)
deallocate (flavor_state)
end do
end subroutine blha_configuration_append_processes

```

Change parameter(s).

(BLHA config: public)+≡

public :: blha_configuration_set

(BLHA config: procedures)+≡

```

! subroutine blha_configuration_set ( cfg, &
!   matrix_element_square_type_hel, matrix_element_square_type_hel_other, &
!   matrix_element_square_type_col, matrix_element_square_type_col_other, &
!   correction_type, correction_type_other, &
!   irreg, irreg_other, &
!   massive_particle_scheme, massive_particle_scheme_other, &
!   subtraction_mode, subtraction_mode_other, &
!   model_file, subdivide_subprocesses, alphas_power, alpha_power, &
!   operation_mode, operation_mode_other)
subroutine blha_configuration_set (cfg, &
!   version, amplitude_type, correction_type, irreg, massive_particle_scheme, &
!   version, correction_type, irreg, massive_particle_scheme, &
!   model_file, alphas_power, alpha_power, ew_scheme, width_scheme, &
!   accuracy, debug)
type(blha_configuration_t), intent(inout) :: cfg
integer, optional, intent(in) :: version
! integer, optional, intent(in) :: amplitude_type
! integer, optional, intent(in) :: matrix_element_square_type_hel
! type(string_t), optional, intent(in) :: matrix_element_square_type_hel_other
! integer, optional, intent(in) :: matrix_element_square_type_col
! type(string_t), optional, intent(in) :: matrix_element_square_type_col_other
integer, optional, intent(in) :: correction_type
! type(string_t), optional, intent(in) :: correction_type_other
integer, optional, intent(in) :: irreg
! type(string_t), optional, intent(in) :: irreg_other
integer, optional, intent(in) :: massive_particle_scheme
! type(string_t), optional, intent(in) :: massive_particle_scheme_other
! integer, optional, intent(in) :: subtraction_mode

```

```

!   type(string_t), optional, intent(in) :: subtraction_mode_other
type(string_t), optional, intent(in) :: model_file
!   logical, optional, intent(in) :: subdivide_subprocesses
integer, optional, intent(in) :: alphas_power, alpha_power
integer, optional, intent(in) :: ew_scheme
integer, optional, intent(in) :: width_scheme
real(default), optional, intent(in) :: accuracy
logical, optional, intent(in) :: debug
!   integer, intent(in), optional :: operation_mode
!   type(string_t), intent(in), optional :: operation_mode_other
!   if (present (matrix_element_square_type_hel)) &
!       cfg%matrix_element_square_type(1) = matrix_element_square_type_hel
!   if (present (matrix_element_square_type_hel_other)) &
!       cfg%matrix_element_square_type_other(1) = matrix_element_square_type_hel_other
!   if (present (matrix_element_square_type_col)) &
!       cfg%matrix_element_square_type(2) = matrix_element_square_type_col
!   if (present (matrix_element_square_type_col_other)) &
!       cfg%matrix_element_square_type_other(2) = matrix_element_square_type_col_other
if (present (version)) &
    cfg%version = version
!   if (present (amplitude_type)) &
!       cfg%amplitude_type = amplitude_type
if (present (correction_type)) &
    cfg%correction_type = correction_type
!   if (present (correction_type_other)) &
!       cfg%correction_type_other = correction_type_other
if (present (irreg)) &
    cfg%irreg = irreg
!   if (present (irreg_other)) &
!       cfg%irreg_other = irreg_other
if (present (massive_particle_scheme)) &
    cfg%massive_particle_scheme = massive_particle_scheme
!   if (present (massive_particle_scheme_other)) &
!       cfg%massive_particle_scheme_other = massive_particle_scheme_other
!   if (present (subtraction_mode)) &
!       cfg%subtraction_mode = subtraction_mode
!   if (present (subtraction_mode_other)) &
!       cfg%subtraction_mode_other = subtraction_mode_other
if (present (model_file)) &
    cfg%model_file = model_file
!   if (present (subdivide_subprocesses)) &
!       cfg%subdivide_subprocesses = subdivide_subprocesses
if (present (alphas_power)) &
    cfg%alphas_power = alphas_power
if (present (alpha_power)) &
    cfg%alpha_power = alpha_power
!   if (present (operation_mode)) &
!       cfg%operation_mode = operation_mode
!   if (present (operation_mode_other)) &
!       cfg%operation_mode_other = operation_mode_other
if (present (ew_scheme)) &
    cfg%ew_scheme = ew_scheme
if (present (width_scheme)) &
    cfg%width_scheme = width_scheme

```



```

    if (present (accuracy)) &
        cfg%accuracy_target = accuracy
    if (present (debug)) &
        cfg%debug_unstable = debug
    cfg%dirty = .false.
end subroutine blha_configuration_set

```

```

<BLHA config: public>+≡
    public :: blha_configuration_get_n_proc

<BLHA config: procedures>+≡
    function blha_configuration_get_n_proc (cfg) result (n_proc)
        type(blha_configuration_t), intent(in) :: cfg
        integer :: n_proc
        n_proc = cfg%n_proc
    end function blha_configuration_get_n_proc

```

Write the BLHA file. Internal mode is intended for md5summing only.

```

<BLHA config: public>+≡
    public :: blha_configuration_write

<BLHA config: procedures>+≡
    subroutine blha_configuration_write (cfg, unit, internal)
        type(blha_configuration_t), intent(in) :: cfg
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: internal
        integer :: u
        logical :: full
        type(string_t) :: buf
        type(blha_cfg_process_node_t), pointer :: node
        integer :: i
        character(3) :: pdg_char
        character(6) :: accuracy
        character(len=25), parameter :: pad = ""
        integer, dimension(:), allocatable :: i_massive
        logical :: massive_particles
        u = given_output_unit (unit)
        full = .true.; if (present (internal)) full = .not. internal
        if (full .and. cfg%dirty) call msg_bug ( &
            "BUG: attempted to write out a dirty BLHA configuration")
        if (full) then
            write (u,'(A)') "# BLHA order written by WHIZARD <Version>"
            write (u,'(A)')
        end if
        select case (cfg%mode)
            case (BLHA_MODE_GOSAM); buf = "GoSam"
            case (BLHA_MODE_OPENLOOPS); buf = "OpenLoops"
            case default; buf = "vanilla"
        end select
        write (u,'(A)') "# BLHA interface mode: " // char (buf)
        write (u,'(A)') "# process: " // char (cfg%name)
        write (u,'(A)') "# model: " // char (cfg%model%get_name ())
        ! if (full) then
        !     write (u,'(A)')
    end subroutine

```

```

!       write (u,'(A)') '#@WO MD5 "' // char (cfg%md5) // '"'
!       write (u,'(A)')
!
!     end if
!     if (all (cfg%matrix_element_square_type == BLHA_MEST_SUM)) then
!       buf = "CHsummed"
!     elseif (all (cfg%matrix_element_square_type == BLHA_MEST_AVG)) then
!       buf = "CHaveraged"
!     else
!       buf = (render_mest ("H", cfg%matrix_element_square_type(1), &
!         cfg%matrix_element_square_type_other(1)) // " ") // &
!         render_mest ("C", cfg%matrix_element_square_type(2), &
!           cfg%matrix_element_square_type_other(2))
!     end if
!     write (u,'(A25,A)') "MatrixElementSquareType" // pad, char (buf)
!   select case (cfg%version)
!     case (1); buf = "BLHA1"
!     case (2); buf = "BLHA2"
!   end select
!   write (u, '(A25,A)') "InterfaceVersion " // pad, char (buf)
!   select case (cfg%correction_type)
!     case (BLHA_CT_QCD); buf = "QCD"
!     case (BLHA_CT_EW); buf = "EW"
!     case (BLHA_CT_QED); buf = "QED"
!     case default; buf = cfg%correction_type_other
!   end select
!   write (u,'(A25,A)') "CorrectionType" // pad, char (buf)
!
!   select case (cfg%mode)
!     case (BLHA_MODE_OPENLOOPS)
!       buf = cfg%name // '.olc'
!       write (u, '(A25,A)') "Extra AnswerFile" // pad, char (buf)
!     end select
!
!   select case (cfg%irreg)
!     case (BLHA_IRREG_CDR); buf = "CDR"
!     case (BLHA_IRREG_DRED); buf = "DRED"
!     case (BLHA_IRREG_THV); buf = "tHV"
!     case (BLHA_IRREG_MREG); buf = "MassReg"
!     case default; buf = cfg%irreg_other
!   end select
!   write (u,'(A25,A)') "IRregularisation" // pad, char (buf)
!   select case (cfg%massive_particle_scheme)
!     case (BLHA_MPS_ONSHELL); buf = "OnShell"
!     case default; buf = cfg%massive_particle_scheme_other
!   end select
!   if (cfg%mode == BLHA_MODE_GOSAM) &
!     write (u,'(A25,A)') "MassiveParticleScheme" // pad, char (buf)
!   select case (cfg%subtraction_mode)
!     case (BLHA_SUBMODE_NONE); buf = "None"
!     case default; buf = cfg%subtraction_mode_other
!   end select
!   write (u,'(A25,A)') "IRsubtractionMethod" // pad, char (buf)
!   write (u,'(A25,A)') "ModelFile" // pad, char (cfg%model_file)
!   if (cfg%subdivide_subprocesses) then

```

```

!       write (u,'(A25,A)') "SubdivideSubprocesses" // pad, "yes"
!     else
!       write (u,'(A25,A)') "SubdivideSubprocess" // pad, "no"
!     end if
select case (cfg%version)
case (1)
  if (cfg%alphas_power >= 0) write (u,'(A25,A)') &
    "AlphasPower" // pad, int2char (cfg%alphas_power)
  if (cfg%alpha_power >= 0) write (u,'(A25,A)') &
    "AlphaPower " // pad, int2char (cfg%alpha_power)
case (2)
  if (cfg%alphas_power >= 0) write (u,'(A25,A)') &
    "CouplingPower QCD " // pad, int2char (cfg%alphas_power)
  if (cfg%alpha_power >= 0) write (u,'(A25,A)') &
    "CouplingPower QED " // pad, int2char (cfg%alpha_power)
end select
select case (cfg%ew_scheme)
  case (BLHA_EW_GF); buf = "alphaGF"
  case (BLHA_EW_MZ); buf = "alphaMZ"
  case (BLHA_EW_MSBAR); buf = "alphaMSbar"
  case (BLHA_EW_0); buf = "alpha0"
  case (BLHA_EW_RUN); buf = "alphaRUN"
  case (BLHA_EW_DEFAULT); buf = "OLPDefined"
end select
select case (cfg%mode)
case (BLHA_MODE_GOSAM)
  write (u, '(A25, A)') "EWScheme " // pad, char (buf)
case (BLHA_MODE_OPENLOOPS)
!   write (u, '(A25, A)') "ewscheme " // pad, char (buf)
endselect
select case (cfg%mode)
case (BLHA_MODE_GOSAM)
  call blha_configuration_get_massive_particles &
    (cfg, massive_particles, i_massive)
  if (massive_particles) then
    write (u, '(A25)', advance='no') "MassiveParticles " // pad
    do i = 1, size (OLP_MASSIVE_PARTICLES)
      if (OLP_MASSIVE_PARTICLES(i) > 0) &
        write (u, '(I2,I1)', advance='no') OLP_MASSIVE_PARTICLES(i)
    end do
    write (u,*)
  end if
case (BLHA_MODE_OPENLOOPS)
  write (u, '(A25,I1)') "extra use_cms " // pad, 0
end select
if (full) then
  write (u,'(A)')
  write (u,'(A)') "# Process definitions"
  write (u,'(A)')
end if
!   if (cfg%accuracy_target /= 0) then
!     write (accuracy, '(f6.5)') cfg%accuracy_target
!     write (u, '(A25,A)') "AccuracyTarget " // pad, accuracy
!   end if

```

```

!   if (cfg%debug_unstable) then
!       buf = "True"
!   else
!       buf = "False"
!   end if
!   write (u, '(A25,A)') "DebugUnstable " // pad, char (buf)
if (cfg%debug_unstable) &
    write (u, '(A25,A)') "DebugUnstable " // pad, "True"
write (u, *)
node => cfg%processes
do while (associated (node))
    select case (node%amplitude_type)
        case (BLHA_AMP_LOOP); buf = "Loop"
        case (BLHA_AMP_CC); buf = "ccTree"
        case (BLHA_AMP_SC); buf = "scTree"
        case (BLHA_AMP_TREE); buf = "Tree"
        case (BLHA_AMP_LOOPINDUCED); buf = "LoopInduced"
    end select
    write (u, '(A25, A)') "AmplitudeType " // pad, char (buf)

    buf = ""
    do i = 1, size (node%pdg_in)
        write (pdg_char, '(I3)') node%pdg_in(i)
        buf = (buf // pdg_char) // " "
    end do
    buf = buf // "-> "
    do i = 1, size (node%pdg_out)
        write (pdg_char, '(I3)') node%pdg_out(i)
        buf = (buf // pdg_char) // " "
    end do
    write (u, '(A)') char (trim (buf))
    write (u, *)
    node => node%next
end do

contains

function render_mest (prefix, mest, other) result (tag)
    character, intent(in) :: prefix
    integer, intent(in) :: mest
    type(string_t), intent(in) :: other
    type(string_t) :: tag
    select case (mest)
        case (BLHA_MEST_AVG); tag = prefix // "averaged"
        case (BLHA_MEST_SUM); tag = prefix // "summed"
        case default; tag = other
    end select
end function render_mest

end subroutine blha_configuration_write

```

“Freeze” the configuration by calculating the MD5 sum.

$\langle BLHA \text{ config: public} \rangle + \equiv$

```

    public :: blha_configuration_freeze
<BLHA config: procedures>+≡
    subroutine blha_configuration_freeze (cfg)
        type(blha_configuration_t), intent(inout) :: cfg
        integer :: u
        if (.not. cfg%dirty) return
        call sort_processes (cfg%processes)
        u = free_unit ()
        open (unit=u, status="scratch", action="readwrite")
        call blha_configuration_write (cfg, u, internal=.true.)
        rewind (u)
        cfg%md5 = md5sum (u)
        cfg%dirty = .false.
        close (u)
    end subroutine blha_configuration_freeze

```

Read a contract file, again creating a blha_configuration_t object.

```

<BLHA config: public>+≡
    public :: blha_read_contract

<BLHA config: interfaces>≡
    interface blha_read_contract
        module procedure blha_read_contract_unit, &
            blha_read_contract_file
    end interface blha_read_contract

<BLHA config: procedures>+≡
    subroutine blha_read_contract_file (cfg, ok, fname, success)
        type(blha_configuration_t), intent(inout) :: cfg
        logical, intent(out) :: ok
        type(string_t), intent(in) :: fname
        logical, intent(out), optional :: success
        integer :: u, stat
        u = free_unit ()
        open (u, file=char (fname), status="old", action="read", iostat=stat)
        if (stat /= 0) then
            if (present (success)) then
                success = .false.
                return
            else
                call msg_bug ('Unable to open contract file "' // char (fname) // '"')
            end if
        end if
        call blha_read_contract_unit (cfg, ok, u, success)
        close (u)
    end subroutine blha_read_contract_file

    subroutine blha_read_contract_unit (cfg, ok, u, success)
        type(blha_configuration_t), intent(inout) :: cfg
        logical, intent(out) :: ok
        integer, intent(in) :: u
        logical, intent(out), optional :: success
        type(stream_t) :: stream

```

```

type(ifile_t) :: preprocessed
type(lexer_t) :: lexer
type(parse_tree_t) :: parse_tree
type(string_t) :: md5
call stream_init (stream, u)
call contract_preprocess (stream, preprocessed)
call stream_final (stream)
call stream_init (stream, preprocessed)
call blha_init_lexer (lexer)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_blha_contract, lexer)
call blha_transfer_contract (cfg, ok, parse_tree, success)
call blha_configuration_write (cfg, internal=.true.)
call lexer_final (lexer)
call stream_final (stream)
call ifile_final (preprocessed)
if (ok) then
  md5 = cfg%md5
  call blha_configuration_freeze (cfg)
  if (char (trim (md5 )) /= "") then
    if (md5 /= cfg%md5) then
      call msg_warning ("BLHA contract does not match the recorded " &
        // "checksum --- this counts as an error!")
      ok = .false.
    end if
  else
    call msg_warning ("It seems the OLP scrubbed our checksum, unable " &
      // "to check contract consistency.")
  end if
end if
end subroutine blha_read_contract_unit

```

Walk the parse tree and transfer the results to the `blha_configuration` object. The `goto` is a poor man's replacement for exceptions which would be an appropriate error handling mechanism here.

(BLHA config: procedures)+≡

```

subroutine blha_transfer_contract (cfg, ok, parse_tree, success)
  type(blha_configuration_t), intent(inout) :: cfg
  logical, intent(out) :: ok
  type(parse_tree_t), intent(in), target :: parse_tree
  logical, intent(out), optional :: success
  type(parse_node_t), pointer :: pn_root, pn_line, pn_request, &
    pn_result, pn_key, pn_opt, pn_state_in, pn_state_out, pn_pdg
  type(string_t) :: emsg
  integer :: nopt, i, nsub
  integer, dimension(:), allocatable :: ids
  logical, dimension(2) :: flags
  type(pdg_array_t), dimension(:), allocatable :: pdg_in, pdg_out
  ok = .true.
  pn_root => parse_tree_get_root_ptr (parse_tree)
  pn_line => parse_node_get_sub_ptr (pn_root)
  do while (associated (pn_line))
    pn_request => parse_node_get_sub_ptr (pn_line)

```

```

if (.not. associated (pn_request)) cycle
if (char (parse_node_get_rule_key (pn_request)) == "process") then
  pn_result => parse_node_get_sub_ptr (pn_line, 2)
  pn_state_in => parse_node_get_sub_ptr (pn_request, 1)
  pn_state_out => parse_node_get_sub_ptr (pn_request, 3)
  allocate (pdg_in (parse_node_get_n_sub (pn_state_in)))
  allocate (pdg_out (parse_node_get_n_sub (pn_state_out)))
  i = 1
  pn_pdg => parse_node_get_sub_ptr (pn_state_in)
  do while (associated (pn_pdg))
    pdg_in(i) = [get_int (pn_pdg)]
    pn_pdg => parse_node_get_next_ptr (pn_pdg)
    i = i + 1
  end do
  i = 1
  pn_pdg => parse_node_get_sub_ptr (pn_state_out)
  do while (associated (pn_pdg))
    pdg_out(i) = [get_int (pn_pdg)]
    pn_pdg => parse_node_get_next_ptr (pn_pdg)
    i = i + 1
  end do
  i = parse_node_get_n_sub (pn_result)
  emsg = "broken process line"
  if (i < 2) goto 10
  pn_opt => parse_node_get_sub_ptr (pn_result, 2)
  do while (associated (pn_opt))
    if (char (parse_node_get_rule_key (pn_opt)) == "string") then
      call msg_warning ("While reading the BLHA contract: " // &
        'the OLP returned an error for a process: "' // &
        char (parse_node_get_string (pn_opt)) // "'")
      ok = .false.
      return
    end if
    pn_opt => parse_node_get_next_ptr (pn_opt)
  end do
  pn_opt => parse_node_get_sub_ptr (pn_result, 2)
  nsub = get_int (pn_opt)
  if (nsub /= i - 2) goto 10
  allocate (ids(nsub))
  i = 1
  pn_opt => parse_node_get_next_ptr (pn_opt)
  do while (associated (pn_opt))
    ids(i) = get_int (pn_opt)
    pn_opt => parse_node_get_next_ptr (pn_opt)
  end do
  call blha_configuration_append_process (cfg, pdg_in, pdg_out, &
    nsub=nsub, ids=ids)
  deallocate (pdg_in, pdg_out, ids)
else
  pn_result => parse_node_get_sub_ptr (parse_node_get_next_ptr (pn_request), 2)
  pn_key => parse_node_get_sub_ptr (pn_request)
  pn_opt => parse_node_get_next_ptr (pn_key)
  nopt = parse_node_get_n_sub (pn_request) - 1
  select case (char (parse_node_get_rule_key (pn_key)))

```

```

case ("md5")
    cfg%md5 = parse_node_get_string (pn_opt)
case ("modelfile")
    cfg%model_file = get_fname (pn_opt)
    call check_result (pn_result, "ModelFile")
case ("irregularisation")
    select case (lower_case (char (parse_node_get_string (pn_opt))))
        case ("cdr"); cfg%irreg = BLHA_IRREG_CDR
        case ("dred"); cfg%irreg = BLHA_IRREG_DRED
        case ("thv"); cfg%irreg = BLHA_IRREG_THV
        case ("mreg"); cfg%irreg = BLHA_IRREG_MREG
        case default
            cfg%irreg = BLHA_IRREG_OTHER
            cfg%irreg_other = parse_node_get_string (pn_opt)
    end select
    call check_result (pn_result, "IRRegularisation")
case ("irsubtractionmethod")
    select case (lower_case (char (parse_node_get_string (pn_opt))))
        case ("none"); cfg%subtraction_mode = BLHA_SUBMODE_NONE
        case default
            cfg%subtraction_mode = BLHA_SUBMODE_OTHER
            cfg%subtraction_mode_other = parse_node_get_string(pn_opt)
    end select
    call check_result (pn_result, "IRSubtractionMethod")
case ("massiveparticlescheme")
    select case (lower_case (char (parse_node_get_string (pn_opt))))
        case ("onshell")
            cfg%massive_particle_scheme = BLHA_MPS_ONSHELL
        case default
            cfg%massive_particle_scheme = BLHA_MPS_OTHER
            cfg%massive_particle_scheme_other = &
                parse_node_get_string (pn_opt)
    end select
    call check_result (pn_result, "MassiveParticleScheme")
case ("matricelementsquaretype")
    select case (nopt)
        case (1)
            select case (lower_case (char (parse_node_get_string (pn_opt))))
                case ("chsummed")
                    cfg%matrix_element_square_type = BLHA_MEST_SUM
                case ("chaveraged")
                    cfg%matrix_element_square_type = BLHA_MEST_AVG
                case default
                    emsg = "invalid MatrixElementSquareType: " // &
                        parse_node_get_string (pn_opt)
                    goto 10
            end select
        case (2)
            do i = 1, 2
                pn_opt => parse_node_get_next_ptr (pn_key, i)
                select case (lower_case (char (parse_node_get_string ( &
                    pn_opt))))
                    case ("csummed")
                        cfg%matrix_element_square_type(2) = BLHA_MEST_SUM

```



```

        flags(2) = .true.
    case ("caveraged")
        cfg%matrix_element_square_type(2) = BLHA_MEST_AVG
        flags(2) = .true.
    case ("hsummed")
        cfg%matrix_element_square_type(1) = BLHA_MEST_SUM
        flags(1) = .true.
    case ("haveraged")
        cfg%matrix_element_square_type(1) = BLHA_MEST_AVG
        flags(1) = .true.
    case default
        emsg = "invalid MatrixElementSquareType: " // &
            parse_node_get_string (pn_opt)
        goto 10
    end select
end do
if (.not. all (flags)) then
    emsg = "MatrixElementSquareType: setup not exhaustive"
    goto 10
end if
case default
    emsg = "MatrixElementSquareType: too many options"
    goto 10
end select
call check_result (pn_result, "MatrixElementSquareType")
case ("correctiontype")
    select case (lower_case (char (parse_node_get_string (pn_opt))))
        case ("qcd"); cfg%correction_type = BLHA_CT_QCD
        case ("qed"); cfg%correction_type = BLHA_CT_QED
        case ("ew"); cfg%correction_type = BLHA_CT_EW
        case default
            cfg%correction_type = BLHA_CT_OTHER
            cfg%correction_type_other = parse_node_get_string (pn_opt)
        end select
    call check_result (pn_result, "CorrectionType")
case ("alphaspower")
    cfg%alpha_power = get_int (pn_opt)
    call check_result (pn_result, "AlphasPower")
case ("alphapower")
    cfg%alpha_power = get_int (pn_opt)
    call check_result (pn_result, "AlphaPower")
case ("subdividesubprocess")
    select case (lower_case (char (parse_node_get_string (pn_opt))))
        case ("yes"); cfg%subdivide_subprocesses = .true.
        case ("no"); cfg%subdivide_subprocesses = .false.
        case default
            emsg = 'SubdivideSubprocess: invalid argument "' // &
                parse_node_get_string (pn_opt) // '"'
            goto 10
        end select
    call check_result (pn_result, "SubdivideSubprocess")
case default
    emsg = "unknown statement: " // parse_node_get_rule_key (pn_key)
    goto 10

```

```

        end select
    end if
    pn_line => parse_node_get_next_ptr (pn_line)
end do
if (present (success)) success = .true.
return
10 continue
if (present (success)) then
    call msg_error ("Error reading BLHA contract: " // char (emsg))
    success = .false.
    return
else
    call msg_fatal ("Error reading BLHA contract: " // char (emsg))
end if

contains

function get_int (pn) result (i)
    type(parse_node_t), pointer :: pn
    integer :: i
    if (char (parse_node_get_rule_key (pn)) == "integer") then
        i = parse_node_get_integer (pn)
    else
        i = parse_node_get_integer (parse_node_get_sub_ptr (pn, 2))
        if (char (parse_node_get_rule_key (parse_node_get_sub_ptr (pn))) &
            == "-") i = -i
    end if
end function get_int

subroutine check_result (pn, step)
    type(parse_node_t), pointer :: pn
    character(*), intent(in) :: step
    type(string_t) :: res
    res = parse_node_get_string (pn)
    if (char (trim (res)) == "") then
        call msg_warning ("BLHA contract file: " // step // &
            ": OLP didn't return a status --- assuming an error")
        ok = .false.
    elseif (char (upper_case (res)) /= "OK") then
        call msg_warning ("BLHA contract file: " // step // &
            ': OLP error ' // char (res) // ' "')
        ok = .false.
    end if
end subroutine check_result

function get_fname (pn) result (fname)
    type(parse_node_t), pointer :: pn
    type(string_t) :: fname
    type(parse_node_t), pointer :: pn_component
    if (char (parse_node_get_rule_key (pn)) == "string") then
        fname = parse_node_get_string (pn)
    else
        fname = ""
        pn_component => parse_node_get_sub_ptr (pn)
    end if
end function get_fname

```

```

do while (associated (pn_component))
  if (char (parse_node_get_rule_key (pn_component)) == "id") then
    fname = fname // parse_node_get_string (pn_component)
  else
    fname = fname // parse_node_get_key (pn_component)
  end if
  pn_component => parse_node_get_next_ptr (pn_component)
end do
end if
end function get_fname

end subroutine blha_transfer_contract

```

Initialize the lexer.

```

<BLHA config: procedures>+≡
subroutine blha_init_lexer (lexer)
  type(lexer_t), intent(inout) :: lexer
  call lexer_init (lexer, &
    comment_chars = "#", &
    quote_chars = "'", &
    quote_match = "'", &
    single_chars = '{}|./\:', &
    special_class = ["->"], &
    keyword_list = syntax_get_keyword_list_ptr (syntax_blha_contract), &
    upper_case_keywords = .false. &
  )
end subroutine blha_init_lexer

```

Define the parser syntax table.

```

<BLHA config: variables>≡
  type(syntax_t), target, save :: syntax_blha_contract

<BLHA config: public>+≡
  public :: syntax_blha_contract_init

<BLHA config: procedures>+≡
subroutine syntax_blha_contract_init ()
  type(ifile_t) :: ifile
  call ifile_append (ifile, "SEQ contract = line*")
  call ifile_append (ifile, "KEY '->'")
  call ifile_append (ifile, "KEY '.'"")
  call ifile_append (ifile, "KEY '/'")
  call ifile_append (ifile, "KEY '\\")
  call ifile_append (ifile, "KEY '+'")
  call ifile_append (ifile, "KEY '-'")
  call ifile_append (ifile, "KEY '|')")
  call ifile_append (ifile, "KEY ':'")
  call ifile_append (ifile, "IDE id")
  call ifile_append (ifile, "INT integer")
  call ifile_append (ifile, "ALT sign = '+' | '-'")
  call ifile_append (ifile, "SEQ signed_integer = sign integer")
  call ifile_append (ifile, "QUO string = '...'")
  call ifile_append (ifile, "GRO line = '{' line_contents '}'")
  call ifile_append (ifile, "SEQ line_contents = request result?")

```

```

call ifile_append (ifile, "ALT request = definition | process")
call ifile_append (ifile, "ALT definition = option_unary | option_nary | " &
    // "option_path | option_numeric")
call ifile_append (ifile, "KEY matrixelementsquaretype")
call ifile_append (ifile, "KEY irregularisation")
call ifile_append (ifile, "KEY massiveparticlescheme")
call ifile_append (ifile, "KEY irsubtractionmethod")
call ifile_append (ifile, "KEY modelfile")
call ifile_append (ifile, "KEY operationmode")
call ifile_append (ifile, "KEY subdividesubprocess")
call ifile_append (ifile, "KEY alphaspower")
call ifile_append (ifile, "KEY alphapower")
call ifile_append (ifile, "KEY correctiontype")
call ifile_append (ifile, "KEY md5")
call ifile_append (ifile, "SEQ option_unary = key_unary arg")
call ifile_append (ifile, "SEQ option_nary = key_nary arg+")
call ifile_append (ifile, "SEQ option_path = key_path arg_path")
call ifile_append (ifile, "SEQ option_numeric = key_numeric arg_numeric")
call ifile_append (ifile, "ALT key_unary = irregularisation | " &
    // "massiveparticlescheme | irsubtractionmethod | subdividesubprocess | " &
    // "correctiontype | md5")
call ifile_append (ifile, "ALT key_nary = matrixelementsquaretype | " &
    // "operationmode")
call ifile_append (ifile, "ALT key_numeric = alphaspower | alphapower")
call ifile_append (ifile, "ALT key_path = modelfile")
call ifile_append (ifile, "ALT arg = id | string")
call ifile_append (ifile, "ALT arg_numeric = integer | signed_integer")
call ifile_append (ifile, "ALT arg_path = filename | string")
call ifile_append (ifile, "SEQ filename = filename_atom+")
call ifile_append (ifile, "ALT filename_atom = id | '.' | '/' | '\' | ':'")
call ifile_append (ifile, "SEQ process = state '->' state")
call ifile_append (ifile, "SEQ state = pdg+")
call ifile_append (ifile, "ALT pdg = integer | signed_integer")
call ifile_append (ifile, "SEQ result = '|' result_atom+")
call ifile_append (ifile, "ALT result_atom = integer | string")
call syntax_init (syntax_blha_contract, ifile)
call ifile_final (ifile)
end subroutine syntax_blha_contract_init

```

```

<BLHA config: public>+≡
    public :: syntax_blha_contract_final

<BLHA config: procedures>+≡
    subroutine syntax_blha_contract_final
        call syntax_final (syntax_blha_contract)
    end subroutine syntax_blha_contract_final

```

As the contract file is line-oriented, we apply a preprocessing step which reformats the file in a way suitable for our free-form parser.

```

<BLHA config: procedures>+≡
    subroutine contract_preprocess (stream, ifile)
        type(stream_t), intent(inout) :: stream
        type(ifile_t), intent(out) :: ifile
    end subroutine contract_preprocess

```

```

type(string_t) :: buf, reg, transformed
integer :: stat, n
buf = ""
LINES: do
    call stream_get_record (stream, reg, stat)
    select case (stat)
        case (0)
        case (EOF); exit LINES
        case default
            call msg_bug ("I/O error while reading BLHA contract file")
    end select
    buf = buf // trim (reg)
    ! Take care of continuation lines
    if (char (extract (buf, len (buf), len(buf))) == '&') then
        buf = extract (buf, 1, len (buf) - 1) // " "
        cycle LINES
    end if
    buf = adjustl (buf)
    ! Transform #@WO comments into ordinary statements
    if (char (extract (buf, 1, 4)) == "#@WO") &
        buf = extract (buf, 5)
    ! Kill comments and blank lines
    if ((char (trim (buf)) == "") .or. &
        (char (extract (buf, 1, 1)) == "#")) then
        buf = ""
        cycle LINES
    end if
    ! Chop off any end-of-line comments
    call split (buf, reg, "#")
    ! Split line into order and result
    call split (reg, buf, "|")
    reg = trim (adjustl (reg))
    buf = trim (adjustl (buf))
    ! Check whether the order is a process definition
    n = scan (buf, ">")
    if (n == 0) then
        ! No -> quote result
        reg = (''' // reg) // ''''
    else
        ! Yes -> leave any numbers as they are, quote any leftovers
        n = scan (reg, "0123456789", back=.true.)
        if (n < len (reg)) &
            reg = char (extract (reg, 1, n)) // ' ' // &
                char (trim (adjustl (extract (reg, n+1)))) // ''''
    end if
    ! Enclose the line into curly brackets
    transformed = "{" // char (buf) // " | " // char (reg) // "}"
    call ifile_append (ifile, transformed)
    buf = ""
end do LINES
end subroutine contract_preprocess

```

Test.

<BLHA config: public>+≡

```

public :: blha_config_test
<BLHA config: procedures>+=
subroutine blha_config_test (model, cfg, ok)
  type(pdg_array_t), dimension(2) :: pdg_in
  type(pdg_array_t), dimension(4) :: pdg_out
  class(model_data_t), pointer :: model
  type(blha_configuration_t), intent(out) :: cfg
  logical, intent(out) :: ok
  integer :: u
  logical :: flag
  ok = .false.
  pdg_in(1) = [1, 2, -1, -2]
  pdg_in(2) = pdg_in(1)
  pdg_out(1) = pdg_in(1)
  pdg_out(2) = [11]
  pdg_out(3) = [-11]
  pdg_out(4) = pdg_out(1)
  call blha_configuration_init (cfg, var_str ("test"), model)
  call blha_configuration_set (cfg, alphas_power = 2, alpha_power = 3)
  call blha_configuration_append_process (cfg, pdg_in, pdg_out)
  call blha_configuration_freeze (cfg)
  print *
  call blha_configuration_write (cfg)
  print *
  call blha_configuration_final (cfg)
  call blha_configuration_init (cfg, var_str ("test"), model, &
    mode=BLHA_MODE_GOSAM)
  call blha_configuration_set (cfg, alphas_power = 0, &
    model_file = var_str ("test.slha"))
  pdg_in(1) = [1]
  pdg_in(2) = [-1]
  pdg_out(1) = [22]
  pdg_out(2) = [22]
  call blha_configuration_append_process (cfg, pdg_in, pdg_out(1:2))
  call blha_configuration_freeze (cfg)
  u = free_unit ()
  open (u, file="test.blha.order", action="write", status="replace")
  call blha_configuration_write (cfg, u)
  call blha_configuration_final (cfg)
  inquire (file="test.blha.contract", exist=flag)
  if (.not. flag) return
  call blha_configuration_init (cfg, var_str ("test"), model, mode=BLHA_MODE_GOSAM)
  call blha_read_contract (cfg, ok, var_str ("test.blha.contract"), success=flag)
  print *, "Reading back processed configuration: success? ", ok
end subroutine blha_config_test

```

23.3 OLP matrix element interface

The prototypes of the OLP functions.

```

<BLHA interface: interfaces>=
abstract interface

```

```

subroutine ext_olp_start (file, status) bind(c)
  import
  character(c_char), dimension(*), intent(in) :: file
  integer(c_int), intent(out) :: status
end subroutine ext_olp_start

subroutine ext_olp_evalsubprocess &
  (label, momenta, scale, parameters, amp) bind(c)
  import
  integer(c_int), intent(in), value :: label
  real(c_double), dimension(*), intent(in) :: momenta
  real(c_double), intent(in), value :: scale
  real(c_double), dimension(*), intent(in) :: parameters
  real(c_double), dimension(*), intent(out) :: amp
end subroutine ext_olp_evalsubprocess

subroutine ext_olp_finalize () bind(c)
end subroutine ext_olp_finalize

subroutine ext_olp_option (assignment, status) bind(c)
  import
  character(c_char), dimension(*), intent(in) :: assignment
  integer(c_int), intent(out) :: status
end subroutine ext_olp_option
end interface

```

The OLP library is encapsulated together with the configuration in derived type:

```

<BLHA interface: public>≡
  public :: blha_olp_t

<BLHA interface: types>≡
  type :: blha_olp_t
  private
  type(blha_configuration_t) :: cfg
  type(string_t) :: library
  integer :: n_in, n_out, n_flv, n_hel, n_col
  integer, dimension(:,:), allocatable :: flv_state
  logical :: color_summed = .true., flavor_summed = .true.
  logical :: loaded = .false.
  type(dlaccess_t) :: lib_handle
  procedure(ext_olp_start), pointer, nopass :: olp_start => null ()
  procedure(ext_olp_evalsubprocess), pointer, nopass :: &
    olp_evalsubprocess => null ()
  procedure(ext_olp_finalize), pointer, nopass :: olp_finalize => null ()
  procedure(ext_olp_option), pointer, nopass :: olp_option => null ()
end type blha_olp_t

```

Init the `blha_olp_t` object and try to dlopen the library.

```

<BLHA interface: public>+≡
  public :: blha_olp_init

<BLHA interface: procedures>≡
  subroutine blha_olp_init (olp, cfg, library, success)
    type(blha_olp_t), intent(out) :: olp

```

```

type(string_t), intent(in), optional :: library
type(blha_configuration_t), intent(in) :: cfg
logical, intent(out), optional :: success
type(blha_cfg_process_node_t), pointer :: node
type(string_t) :: prefix, libname
type(c_funptr) :: fptr
integer :: olp_status
success = .true.
node => cfg%processes
if (.not. associated (node)) then
    call error ("blha_interface_init: empty process list")
    return
end if
olp%n_in = size (node%pdg_in)
olp%n_out = size (node%pdg_out)
do while (associated (node))
    if ((olp%n_in /= size (node%pdg_in)) .or. &
        (olp%n_out /= size (node%pdg_out))) then
        call error ("blha_interface_init: inconsistent process list")
        return
    end if
    node => node%next
end do
if (present (library)) then
    olp%library = library
else
    olp%library = cfg%name // ".so"
end if
if (char (extract (olp%library, 1, 1)) == "/") then
    prefix = ""
    libname = extract (olp%library, 2)
else
    prefix = "."
    libname = olp%library
end if
call dlaccess_init (olp%lib_handle, prefix, libname)
if (dlaccess_has_error (olp%lib_handle)) then
    call error ("blha_interface_init: error opening library: " // &
        char (dlaccess_get_error (olp%lib_handle)))
    call dlaccess_final (olp%lib_handle)
    return
end if
fptr = dlaccess_get_c_funptr (olp%lib_handle, var_str ("OLP_Start"))
if (.not. check_dlstate ()) return
call c_f_procpointer (fptr, olp%olp_start)
fptr = dlaccess_get_c_funptr (olp%lib_handle, var_str ("OLP_EvalSubProcess"))
if (.not. check_dlstate ()) return
call c_f_procpointer (fptr, olp%olp_evalsubprocess)
if (olp%cfg%mode == BLHA_MODE_GOSAM) then
    fptr = dlaccess_get_c_funptr (olp%lib_handle, var_str ("OLP_Finalize"))
    if (.not. check_dlstate ()) return
    call c_f_procpointer (fptr, olp%olp_finalize)
    fptr = dlaccess_get_c_funptr (olp%lib_handle, var_str ("OLP_Option"))
    if (.not. check_dlstate ()) return

```



```

        call c_f_procpointer (fptr, olp%olp_option)
    end if
    call olp%olp_start (string_f2c (cfg%model_file), olp_status)
    if (olp_status /= 1) then
        call error ("blha_interface_init: OLP initialization failed")
        call dlaccess_final (olp%lib_handle)
    end if
    success = .true.
    olp%loaded = .true.

contains

function check_dlstate () result (ok)
    logical :: ok
    ok = .not. dlaccess_has_error (olp%lib_handle)
    if (.not. ok) then
        call error ("blha_interface_init: error loading library: " // &
            char (dlaccess_get_error (olp%lib_handle)))
        call dlaccess_final (olp%lib_handle)
    end if
end function check_dlstate

subroutine error (msg)
    character(*), intent(in) :: msg
    if (present (success)) then
        call msg_error (msg)
        success = .false.
    else
        call msg_fatal (msg)
    end if
end subroutine error

end subroutine blha_olp_init

```

Finalizer.

```

<BLHA interface: public>+≡
    public :: blha_olp_final

<BLHA interface: procedures>+≡
    subroutine blha_olp_final (olp)
        type(blha_olp_t), intent(inout) :: olp
        if (.not. olp%loaded) return
        if (associated (olp%olp_finalize)) call olp%olp_finalize
        call dlaccess_final (olp%lib_handle)
        olp%loaded = .false.
    end subroutine blha_olp_final

```

Test.

```

<BLHA interface: public>+≡
    public :: blha_interface_test

<BLHA interface: procedures>+≡
    subroutine blha_interface_test (cfg, ok)
        type(blha_configuration_t), intent(inout) :: cfg

```

```

type(blha_olp_t) :: olp
logical, intent(out) :: ok
call blha_olp_init (olp, cfg, library=var_str ("blha_test.so"), success=ok)
print *, "loading OLP library: success?", ok
call blha_olp_final (olp)
end subroutine blha_interface_test

```

23.4 OLP driver

```

<BLHA driver: public>≡
  public :: blha_test

<BLHA driver: procedures>≡
  subroutine blha_test (model)
    class(model_data_t), pointer :: model
    type (blha_configuration_t) :: cfg
    logical :: ok
    call blha_config_test (model, cfg, ok)
    if (ok) call blha_interface_test (cfg, ok)
  end subroutine blha_test

```

Chapter 24

GoSam Interface

The code in this chapter makes amplitudes accessible to **WHIZARD** that are generated and computed by the GoSam package.

These are the modules:

loop_archive Provide some useful extra functionality.

prc_gosam The actual interface, following the **WHIZARD** conventions for matrix-element generator methods.

24.1 Save previously generated loop libraries

```
<loop_archive.f90>≡
  <File header>

  module loop_archive

    use io_units
    <Use strings>
    use diagnostics
    use os_interface

    <Standard module head>

    <Loop archive: public>

    <Loop archive: types>

    contains

    <Loop archive: procedures>

  end module loop_archive

<Loop archive: public>≡
  public :: loop_archive_t

<Loop archive: types>≡
  type :: loop_archive_t
    logical :: active = .false.
    type(string_t) :: name
    type(string_t) :: current_prefix
    type(os_data_t) :: os_data
  contains
    <Loop archive: loop archive: TBP>
  end type loop_archive_t

<Loop archive: loop archive: TBP>≡
  procedure :: activate => loop_archive_activate

<Loop archive: procedures>≡
  subroutine loop_archive_activate (archive, name, os_data)
    class(loop_archive_t), intent(inout) :: archive
    type(string_t), intent(in) :: name
    type(os_data_t), intent(in) :: os_data
    integer :: status, success
    type(string_t) :: prefix
    archive%name = name
    archive%os_data = os_data
    call os_system_call ('test -d "' // name // &
                        '", status = status, verbose = .true.)
  if (status /= 0) then
    call os_system_call ('mkdir ' // name, &
                        status = success, verbose = .true.)
    if (success /= 0) call msg_fatal ("Creation of loop archive failed!")
```

```

end if
archive%active = .true.
end subroutine loop_archive_activate

```

<Loop archive: loop archive: TBP>+≡

```

procedure :: record => loop_archive_record

```

<Loop archive: procedures>+≡

```

subroutine loop_archive_record (archive, olp_file, olc_file, config_file, lib)
  class(loop_archive_t), intent(inout) :: archive
  type(string_t), intent(in) :: olp_file, olc_file, config_file, lib
  type(string_t) :: current_prefix
  type(string_t) :: filename

  ! Copy, rename and move olp-file and olc-file
  filename = archive%current_prefix // '.olp'
  call os_system_call ('cp ' // olp_file // ' ' // &
    filename)
  call os_system_call ('mv ' // filename // ' ' // &
    archive%name)
  filename = archive%current_prefix // '.olc'
  call os_system_call ('cp ' // olc_file // ' ' // &
    filename)
  call os_system_call ('mv ' // filename // ' ' // &
    archive%name)
  ! Do the same with the loop-library and the config file
  filename = archive%current_prefix // '_libgolem_olp.' // &
    archive%os_data%shrlib_ext
  call os_system_call ('cp ' // lib // ' ' // filename)
  call os_system_call ('mv ' // filename // ' ' // &
    archive%name)
  filename = archive%current_prefix // '_golem.in'
  call os_system_call ('cp ' // config_file // ' ' // &
    filename)
  call os_system_call ('mv ' // filename // ' ' // &
    archive%name)
end subroutine loop_archive_record

```

<Loop archive: loop archive: TBP>+≡

```

procedure :: search => loop_archive_search

```

<Loop archive: procedures>+≡

```

subroutine loop_archive_search (archive, files, found)
  class(loop_archive_t), intent(inout) :: archive
  type(string_t), dimension(3), intent(in) :: files
  logical, intent(out) :: found
  type(string_t) :: current_olp, current_config, current_lib
  character(len=3) :: prefix
  integer :: counter
  logical, dimension(2) :: exist
  integer, dimension(2) :: identical
  integer :: i

  counter = 1

```

```

do
  write(prefix,"(A,I2.2)") 'V', counter
  current_olp = archive%name // '/' // var_str (prefix) // '.olp'
  current_config = archive%name // '/' // var_str (prefix) // '_golem.in'
  current_lib = archive%name // '/' // var_str (prefix) // &
    '_libgolem_olp.' // archive%os_data%shrlib_ext
  inquire (file = char (current_olp), exist = exist(1))
  inquire (file = char (current_config), exist = exist(2))
  if (all (exist)) then
    call os_system_call ('diff ' // current_olp // ' ' // files(1) // &
      ' > /dev/null', status=identical(1))
    call os_system_call ('diff ' // current_config // ' ' // files(2) // &
      ' > /dev/null', status=identical(2))
    if (all (identical == 0)) then
      found = .true.
      exit
    else
      counter = counter+1
    end if
  else
    found = .false.
    exit
  end if
  if (counter >= 100) call msg_fatal ("Maximum number of loop-libraries exceeded!")
end do
write(prefix,"(A,I2.2)") 'V', counter
archive%current_prefix = var_str (prefix)
end subroutine loop_archive_search

```

<Loop archive: loop archive: TBP>+≡

```
procedure :: restore => loop_archive_restore
```

<Loop archive: procedures>+≡

```

subroutine loop_archive_restore (archive, olp_orig, olc_orig, path)
  class(loop_archive_t), intent(inout) :: archive
  type(string_t), intent(in) :: olp_orig, olc_orig, path
  type(string_t) :: olp_file, olc_file, config_file, lib

  olp_file = archive%current_prefix // '.olp'
  olc_file = archive%current_prefix // '.olc'
  config_file = archive%current_prefix // '_golem.in'
  lib = archive%current_prefix // '_libgolem_olp.' // &
    archive%os_data%shrlib_ext

  call os_system_call ('cp ' // archive%name // '/' // olp_file // ' .')
  call os_system_call ('mv ' // olp_file // ' ' // olp_orig)

  call os_system_call ('cp ' // archive%name // '/' // olc_file // ' .')
  call os_system_call ('mv ' // olc_file // ' ' // olc_orig)

  call os_system_call ('cp ' // archive%name // '/' // config_file // ' .')
  call os_system_call ('mv ' // config_file // ' golem.in')

  call os_system_call ('cp ' // archive%name // '/' // lib // ' .')

```

```
call os_system_call ('mv ' // lib // ' libgolem_olp.' // &
archive%os_data%shrlib_ext)
call os_system_call ('mv libgolem_olp.' // archive%os_data%shrlib_ext &
// ' ' // path // '/.libs')

end subroutine loop_archive_restore
```

24.2 Gosam Interface

```
<prc_gosam.f90>≡  
  <File header>  
  
  module prc_gosam  
  
    use, intrinsic :: iso_c_binding !NODEP!  
    use, intrinsic :: iso_fortran_env  
  
    use kinds  
    <Use strings>  
    use io_units  
    use constants  
    use system_defs, only: TAB  
    use system_dependencies  
    use file_utils  
    use string_utils  
    use physics_defs  
    use diagnostics  
    use os_interface  
    use lorentz  
    use interactions  
    use pdg_arrays  
    use sm_qcd  
    use flavors  
    use model_data  
  
    use process_constants  
    use prclib_interfaces  
    use process_libraries  
    use prc_core_def  
    use prc_core  
  
    use blha_config  
    use blha_olp_interfaces  
    use loop_archive  
  
    <Standard module head>  
  
    <prc gosam: constants>  
  
    <prc gosam: public>  
  
    <prc gosam: types>  
  
    <prc gosam: interfaces>  
  
    contains  
  
    <prc gosam: procedures>  
  
  end module prc_gosam
```



```

<prc gosam: constants>≡
  character(10), dimension(5), parameter :: &
    lib_suffix = [character(10) :: &
      '.a', '.la', '.so', '.so.0', '.so.0.0.0']

```

Different types of QCD splittings: 1 - $q \rightarrow qg$, 2 - $g \rightarrow gg$, 3 - $g \rightarrow qq$.

```

<prc gosam: constants>+≡
  integer, parameter :: Q_TO_QG = 1
  integer, parameter :: G_TO_GG = 2
  integer, parameter :: G_TO_QQ = 3

```

```

<prc gosam: types>≡
  type, extends (prc_blha_writer_t) :: gosam_writer_t
    type(string_t) :: gosam_dir
    type(string_t) :: golem_dir
    type(string_t) :: samurai_dir
    type(string_t) :: ninja_dir
    type(string_t) :: form_dir
    type(string_t) :: qgraf_dir
  contains
    <prc gosam: gosam writer: TBP>
  end type gosam_writer_t

```

```

<prc gosam: public>≡
  public :: gosam_def_t

```

```

<prc gosam: types>+≡
  type, extends (blha_def_t) :: gosam_def_t
    logical :: execute_olp = .true.
  contains
    <prc gosam: gosam def: TBP>
  end type gosam_def_t

```

```

<prc gosam: types>+≡
  type, extends (blha_driver_t) :: gosam_driver_t
    type(string_t) :: gosam_dir
    type(string_t) :: olp_file
    type(string_t) :: olc_file
    type(string_t) :: olp_dir
    type(string_t) :: olp_lib
    type(loop_archive_t) :: loop_archive
  contains
    <prc gosam: gosam driver: TBP>
  end type gosam_driver_t

```

```

<prc gosam: public>+≡
  public :: prc_gosam_t

```

```

<prc gosam: types>+≡
  type, extends (prc_blha_t) :: prc_gosam_t
    logical :: initialized = .false.
  contains

```

```

    <prc gosam: prc gosam: TBP>
    end type prc_gosam_t

<prc gosam: types>+≡
    type, extends (blha_state_t) :: gosam_state_t
    contains
    <prc gosam: gosam state: TBP>
    end type gosam_state_t

<prc gosam: gosam def: TBP>≡
    procedure :: init => gosam_def_init

<prc gosam: procedures>≡
    subroutine gosam_def_init (object, basename, model_name, &
                               prt_in, prt_out, nlo_type)
        class(gosam_def_t), intent(inout) :: object
        type(string_t), intent(in) :: model_name
        type(string_t), intent(in) :: basename
        type(string_t), dimension(:), intent(in) :: prt_in, prt_out
        integer, intent(in) :: nlo_type
        object%basename = basename
        allocate (gosam_writer_t :: object%writer)
        select case (nlo_type)
            case (NLO_REAL)
                object%suffix = '_REAL'
            case (NLO_VIRTUAL)
                object%suffix = '_LOOP'
            case (NLO_SUBTRACTION)
                object%suffix = '_SUB'
        end select
        select type (writer => object%writer)
            type is (gosam_writer_t)
                call writer%init (model_name, prt_in, prt_out)
        end select
    end subroutine gosam_def_init

<prc gosam: gosam def: TBP>+≡
    procedure, nopass :: type_string => gosam_def_type_string

<prc gosam: procedures>+≡
    function gosam_def_type_string () result (string)
        type(string_t) :: string
        string = "gosam"
    end function gosam_def_type_string

<prc gosam: gosam def: TBP>+≡
    procedure :: write => gosam_def_write

<prc gosam: procedures>+≡
    subroutine gosam_def_write (object, unit)
        class(gosam_def_t), intent(in) :: object
        integer, intent(in) :: unit
        select type (writer => object%writer)

```

```

        type is (gosam_writer_t)
        call writer%write (unit)
    end select
end subroutine gosam_def_write

<prc gosam: gosam def: TBP>+≡
    procedure :: read => gosam_def_read

<prc gosam: procedures>+≡
    subroutine gosam_def_read (object, unit)
        class(gosam_def_t), intent(out) :: object
        integer, intent(in) :: unit
        call msg_bug ("GoSam process definition: input not supported yet")
    end subroutine gosam_def_read

<prc gosam: gosam def: TBP>+≡
    procedure :: allocate_driver => gosam_def_allocate_driver

<prc gosam: procedures>+≡
    subroutine gosam_def_allocate_driver (object, driver, basename)
        class(gosam_def_t), intent(in) :: object
        class(prc_core_driver_t), intent(out), allocatable :: driver
        type(string_t), intent(in) :: basename
        if (.not. allocated (driver)) allocate (gosam_driver_t :: driver)
    end subroutine gosam_def_allocate_driver

<prc gosam: gosam writer: TBP>≡
    procedure, nopass :: type_name => gosam_writer_type_name

<prc gosam: procedures>+≡
    function gosam_writer_type_name () result (string)
        type(string_t) :: string
        string = "gosam"
    end function gosam_writer_type_name

<prc gosam: gosam writer: TBP>+≡
    procedure :: init => gosam_writer_init

<prc gosam: procedures>+≡
    subroutine gosam_writer_init (writer,model_name, prt_in, prt_out)
        class(gosam_writer_t), intent(inout) :: writer
        type(string_t), intent(in) :: model_name
        type(string_t), dimension(:), intent(in) :: prt_in, prt_out
        integer :: i, unit

        writer%gosam_dir = GOSAM_DIR
        writer%golem_dir = GOLEM_DIR
        writer%samurai_dir = SAMURAI_DIR
        writer%ninja_dir = NINJA_DIR
        writer%form_dir = FORM_DIR
        writer%qgraf_dir = QGRAF_DIR

        writer%model_name = model_name

```

```

select case (size (prt_in))
  case (1); writer%process_mode = " -decay"
  case (2); writer%process_mode = " -scatter"
end select
associate (s => writer%process_string)
  s = " '"
  do i = 1, size (prt_in)
    if (i > 1) s = s // " "
    s = s // prt_in(i)
  end do
  s = s // " ->"
  do i = 1, size (prt_out)
    s = s // " " // prt_out(i)
  end do
  s = s // "'"
end associate

unit = free_unit ()
open (unit, file = "golem.in", status = "replace", action = "write")
call writer%generate_configuration_file (unit)
close(unit)
end subroutine gosam_writer_init

```

```

<prc gosam: gosam driver: TBP>≡
  procedure, nopass :: type_name => gosam_driver_type_name

```

```

<prc gosam: procedures>+≡
  function gosam_driver_type_name () result (string)
    type(string_t) :: string
    string = "gosam"
  end function gosam_driver_type_name

```

```

<prc gosam: gosam driver: TBP>+≡
  procedure :: init_gosam => gosam_driver_init_gosam

```

```

<prc gosam: procedures>+≡
  subroutine gosam_driver_init_gosam (object, os_data, olp_file, &
                                     olc_file, olp_dir, olp_lib)
    class(gosam_driver_t), intent(inout) :: object
    type(os_data_t), intent(in) :: os_data
    type(string_t), intent(in) :: olp_file, olc_file, olp_dir, olp_lib
    object%gosam_dir = GOSAM_DIR
    object%olp_file = olp_file
    object%contract_file = olc_file
    object%olp_dir = olp_dir
    object%olp_lib = olp_lib
    call object%loop_archive%activate (var_str ('Generated_Loops'), os_data)
  end subroutine gosam_driver_init_gosam

```

```

<prc gosam: gosam driver: TBP>+≡
  procedure :: init_dlaccess_to_library => gosam_driver_init_dlaccess_to_library

```

```

<prc gosam: procedures>+≡
  subroutine gosam_driver_init_dlaccess_to_library &
    (object, os_data, dlaccess, success)
    class(gosam_driver_t), intent(in) :: object
    type(os_data_t), intent(in) :: os_data
    type(dlaccess_t), intent(out) :: dlaccess
    logical, intent(out) :: success
    type(string_t) :: libname, msg_buffer
    libname = object%olp_dir // '/.libs/libgolem_olp.' // &
      os_data%shrlib_ext
    msg_buffer = "USING GOSAM"
    call msg_message (char(msg_buffer))
    msg_buffer = "Loading library: " // libname
    call msg_message (char(msg_buffer))
    call dlaccess_init (dlaccess, var_str (.), libname, os_data)
    success = .not. dlaccess_has_error (dlaccess)
  end subroutine gosam_driver_init_dlaccess_to_library

<prc gosam: gosam writer: TBP>+≡
  procedure :: generate_configuration_file => &
    gosam_writer_generate_configuration_file

<prc gosam: procedures>+≡
  subroutine gosam_writer_generate_configuration_file &
    (object, unit)
    class(gosam_writer_t), intent(in) :: object
    integer, intent(in) :: unit
    type(string_t) :: fc_bin
    type(string_t) :: form_bin, qgraf_bin, haggies_bin
    type(string_t) :: fcflags_golem, ldflags_golem
    type(string_t) :: fcflags_samurai, ldflags_samurai
    type(string_t) :: fcflags_ninja, ldflags_ninja
    type(string_t) :: ldflags_avh_olo, ldflags_qcdloop
    fc_bin = DEFAULT_FC
    form_bin = object%form_dir // '/bin/tform'
    qgraf_bin = object%qgraf_dir // '/bin/qgraf'
    if (object%gosam_dir /= "") then
      haggies_bin = '/usr/bin/java -jar ' // object%gosam_dir // &
        '/share/golem/haggies/haggies.jar'
    else
      call msg_fatal("generate_configuration_file: At least " // &
        "the GoSam Directory has to be specified!")
    end if
    if (object%golem_dir /= "") then
      fcflags_golem = "-I" // object%golem_dir // "/include/golem95"
      ldflags_golem = "-L" // object%golem_dir // "/lib -lgolem"
    end if
    if (object%samurai_dir /= "") then
      fcflags_samurai = "-I" // object%samurai_dir // "/include/samurai"
      ldflags_samurai = "-L" // object%samurai_dir // "/lib -lsamurai"
      ldflags_avh_olo = "-L" // object%samurai_dir // "/lib -lavh_olo"
      ldflags_qcdloop = "-L" // object%samurai_dir // "/lib -lqcdloop"
    end if
    if (object%ninja_dir /= "") then

```

```

fcflags_ninja = "-I" // object%ninja_dir // "/include/ninja " &
// "-I" // object%ninja_dir // "/include"
ldflags_ninja = "-L" // object%ninja_dir // "/lib -lninja"
end if
write (unit, "(A)") "+avh_olo.ldflags=" &
// char (ldflags_avh_olo)
write (unit, "(A)") "reduction_programs=golem95, samurai, ninja"
write (unit, "(A)") "extensions=autotools"
write (unit, "(A)") "+qcdloop.ldflags=" &
// char (ldflags_qcdloop)
write (unit, "(A)") "+zzz.extensions=qcdloop, avh_olo"
write (unit, "(A)") "fc.bin=" // char (fc_bin)
write (unit, "(A)") "form.bin=" // char (form_bin)
write (unit, "(A)") "qgraf.bin=" // char (qgraf_bin)
write (unit, "(A)") "golem95.fcflags=" // char (fcflags_golem)
write (unit, "(A)") "golem95.ldflags=" // char (ldflags_golem)
write (unit, "(A)") "haggies.bin=" // char (haggies_bin)
write (unit, "(A)") "samurai.fcflags=" // char (fcflags_samurai)
write (unit, "(A)") "samurai.ldflags=" // char (ldflags_samurai)
write (unit, "(A)") "ninja.fcflags=" // char (fcflags_ninja)
write (unit, "(A)") "ninja.ldflags=" // char (ldflags_ninja)
!!! This might collide with the mass-setup in the order-file
!!! write (unit, "(A)") "zero=mU,mD,mC,mS,mB"
write (unit, "(A)") "PSP_check=False"
write (unit, "(A)") "filter.lo=lambda d: d.iprop(H) == 0 and d.iprop(chi) == 0"
write (unit, "(A)") "filter.nlo=lambda d: d.iprop(H) == 0 and d.iprop(chi) == 0"
end subroutine gosam_writer_generate_configuration_file

```

We have to assure that all files necessary for the configure process in the GoSam code are ready. This is done with a stamp mechanism.

```

<prc gosam: gosam_driver: TBP>+≡
  procedure :: write_makefile => gosam_driver_write_makefile

<prc gosam: procedures>+≡
  subroutine gosam_driver_write_makefile (object, unit, libname)
    class(gosam_driver_t), intent(in) :: object
    integer, intent(in) :: unit
    type(string_t), intent(in) :: libname
    write (unit, "(2A)") "OLP_FILE = ", char (object%olp_file)
    write (unit, "(2A)") "OLP_DIR = ", char (object%olp_dir)
    write (unit, "(A)")
    write (unit, "(A)") "all: autogen"
    write (unit, "(4A)") TAB, "make ", &
      char (object%loop_archive%os_data%makeflags), &
      " -C $(OLP_DIR) install"
    write (unit, "(A)")
    write (unit, "(3A)") "autogen: ", char (libname)
    write (unit, "(3A)") TAB, "cd $(OLP_DIR); ./autogen.sh --prefix=", &
      "$(dir $(abspath $(lastword $(MAKEFILE_LIST))))"
    write (unit, "(A)")
    write (unit, "(2A)") char (libname), ":"
    write (unit, "(4A)") TAB, char (object%gosam_dir // "/bin/gosam.py "), &
      "--olp $(OLP_FILE) --destination=$(OLP_DIR)", &
      " -f -z"
  end subroutine

```

```

        end subroutine gosam_driver_write_makefile

<prc gosam: gosam driver: TBP>+≡
    procedure :: set_alpha_s => gosam_driver_set_alpha_s

<prc gosam: procedures>+≡
    subroutine gosam_driver_set_alpha_s (driver, alpha_s)
        class(gosam_driver_t), intent(inout) :: driver
        real(default), intent(in) :: alpha_s
        integer :: ierr
        call driver%blha_olp_set_parameter &
            (c_char_'alphaS'//c_null_char, &
             dble (alpha_s), 0._double, ierr)
    end subroutine gosam_driver_set_alpha_s

<prc gosam: gosam driver: TBP>+≡
    procedure :: print_alpha_s => gosam_driver_print_alpha_s

<prc gosam: procedures>+≡
    subroutine gosam_driver_print_alpha_s (object)
        class(gosam_driver_t), intent(in) :: object
        call object%blha_olp_print_parameter (c_char_'alphaS'//c_null_char)
    end subroutine gosam_driver_print_alpha_s

<prc gosam: prc gosam: TBP>≡
    procedure :: search_for_existing_library => &
        prc_gosam_search_for_existing_library

<prc gosam: procedures>+≡
    subroutine prc_gosam_search_for_existing_library (object, os_data, found)
        class(prc_gosam_t), intent(inout) :: object
        type(os_data_t), intent(in) :: os_data
        logical, intent(out) :: found
        select type (driver => object%driver)
            type is (gosam_driver_t)
                call driver%loop_archive%search ([driver%olp_file, &
                    var_str ('golem.in'), driver%olp_dir // &
                    '/.libs/libgolem_olp.' // os_data%shrlib_ext], found)
            end select
    end subroutine prc_gosam_search_for_existing_library

<prc gosam: prc gosam: TBP>+≡
    procedure :: write_makefile => prc_gosam_write_makefile

<prc gosam: procedures>+≡
    subroutine prc_gosam_write_makefile (object, unit, libname)
        class(prc_gosam_t), intent(in) :: object
        integer, intent(in) :: unit
        type(string_t), intent(in) :: libname
        select type (driver => object%driver)
            type is (gosam_driver_t)
                call driver%write_makefile (unit, libname)
            end select
    end subroutine prc_gosam_write_makefile

```

```

<prc gosam: prc gosam: TBP>+=
    procedure :: execute_makefile => prc_gosam_execute_makefile

<prc gosam: procedures>+=
    subroutine prc_gosam_execute_makefile (object, libname)
        class(prc_gosam_t), intent(in) :: object
        type(string_t), intent(in) :: libname
        select type (driver => object%driver)
            type is (gosam_driver_t)
                call os_system_call ("make " // &
                    driver%loop_archive%os_data%makeflags // " -f " // &
                    char (libname // "_gosam.makefile"))
            end select
        end subroutine prc_gosam_execute_makefile

<prc gosam: prc gosam: TBP>+=
    procedure :: create_olp_library => prc_gosam_create_olp_library

<prc gosam: procedures>+=
    subroutine prc_gosam_create_olp_library (object, libname, lib_exists)
        class(prc_gosam_t), intent(inout) :: object
        type(string_t), intent(in) :: libname
        logical, intent(in) :: lib_exists
        integer :: unit
        select type (driver => object%driver)
            type is (gosam_driver_t)
                if (lib_exists) then
                    call driver%loop_archive%restore (driver%olp_file, driver%contract_file, &
                        driver%olp_dir)
                else
                    unit = free_unit ()
                    open (unit, file = char (libname // "_gosam.makefile"), &
                        status = "replace", action= "write")
                    call object%write_makefile (unit, libname)
                    close (unit)
                    call object%execute_makefile (libname)
                end if
            end select
        end subroutine prc_gosam_create_olp_library

<prc gosam: prc gosam: TBP>+=
    procedure :: load_driver => prc_gosam_load_driver

<prc gosam: procedures>+=
    subroutine prc_gosam_load_driver (object, os_data, store)
        class(prc_gosam_t), intent(inout) :: object
        type(os_data_t), intent(in) :: os_data
        logical, intent(in) :: store
        logical :: dl_success
        type(string_t) :: libname

        select type (driver => object%driver)
            type is (gosam_driver_t)
                call driver%load (os_data, dl_success)
                if (.not. dl_success) &

```



```

        call msg_fatal ("Error: GoSam Libraries could not be loaded")
    if (store .and. dl_success) then
        libname = driver%olp_dir // './.libs/libgolem_olp.' // &
            os_data%shrlib_ext
        call driver%loop_archive%record (driver%olp_file, driver%contract_file, &
            var_str ('golem.in'), libname)
    end if
end select
end subroutine prc_gosam_load_driver

<prc gosam: prc gosam: TBP>+≡
    procedure :: start => prc_gosam_start

<prc gosam: procedures>+≡
    subroutine prc_gosam_start (object)
        class(prc_gosam_t), intent(inout) :: object
        integer :: ierr
        select type (driver => object%driver)
        type is (gosam_driver_t)
            call driver%blha_olp_start (char (driver%contract_file), ierr)
        end select
    end subroutine prc_gosam_start

<prc gosam: prc gosam: TBP>+≡
    procedure :: write => prc_gosam_write

<prc gosam: procedures>+≡
    subroutine prc_gosam_write (object, unit)
        class(prc_gosam_t), intent(in) :: object
        integer, intent(in), optional :: unit
        call msg_message ("GOSAM")
    end subroutine prc_gosam_write

<prc gosam: prc gosam: TBP>+≡
    procedure :: init_driver => prc_gosam_init_driver

<prc gosam: procedures>+≡
    subroutine prc_gosam_init_driver (object, os_data)
        class(prc_gosam_t), intent(inout) :: object
        type(os_data_t), intent(in) :: os_data
        logical :: dl_success
        type(string_t) :: olp_file, olc_file, olp_dir
        integer(c_int) :: success
        logical :: found = .false.

        select type (def => object%def)
        type is (gosam_def_t)
            olp_file = def%basename // def%suffix // '.olp'
            olc_file = def%basename // def%suffix // '.olc'
            olp_dir = def%basename // def%suffix // '_olp_modules'
        class default
            call msg_bug ("prc_gosam_init_driver: core_def should be of gosam-type")
        end select
    end subroutine prc_gosam_init_driver

```

```

        select type(driver => object%driver)
        type is (gosam_driver_t)
            call driver%init_gosam (os_data, olp_file, olc_file, olp_dir, &
                var_str ("libgolem_olp"))
        end select
    end subroutine prc_gosam_init_driver

<prc gosam: prc gosam: TBP>+≡
    procedure :: set_initialized => prc_gosam_set_initialized

<prc gosam: procedures>+≡
    subroutine prc_gosam_set_initialized (prc_gosam)
        class(prc_gosam_t), intent(inout) :: prc_gosam
        prc_gosam%initialized = .true.
    end subroutine prc_gosam_set_initialized

<prc gosam: prc gosam: TBP>+≡
    procedure :: compute_sqme_born => prc_gosam_compute_sqme_born

<prc gosam: procedures>+≡
    subroutine prc_gosam_compute_sqme_born &
        (object, i_born, mom, mu, sqme, acc_born)
        class(prc_gosam_t), intent(inout) :: object
        integer, intent(in) :: i_born
        real(double), intent(in), dimension(5*object%n_particles) :: mom
        real(double), intent(in) :: mu
        real(default), intent(out) :: sqme
        real(default), intent(out) :: acc_born

        real(double), dimension(OLP_RESULTS_LIMIT) :: r
        real(double) :: acc_dble

        select type (driver => object%driver)
        type is (gosam_driver_t)
            call driver%blha_olp_eval2 (i_born, mom, mu, r, acc_dble)
            sqme = r(4)
        end select
        acc_born = acc_dble
    end subroutine prc_gosam_compute_sqme_born

<prc gosam: prc gosam: TBP>+≡
    procedure :: compute_sqme_real => prc_gosam_compute_sqme_real

<prc gosam: procedures>+≡
    subroutine prc_gosam_compute_sqme_real &
        (object, i_flv, p, ren_scale, sqme, bad_point)
        class(prc_gosam_t), intent(inout) :: object
        integer, intent(in) :: i_flv
        type(vector4_t), intent(in), dimension(:) :: p
        real(default), intent(in) :: ren_scale
        real(default), intent(out) :: sqme
        logical, intent(out) :: bad_point
        real(double), dimension(5*object%n_particles) :: mom
        real(double), dimension(OLP_RESULTS_LIMIT) :: r

```

```

real(double) :: mu_dble
real(default) :: mu
real(double) :: acc_dble
real(default) :: acc
real(default) :: alpha_s

mom = object%create_momentum_array (p)
if (ren_scale == 0.0) then
    mu = sqrt (2*p(1)*p(2))
else
    mu = ren_scale
end if
mu_dble = dble(mu)
alpha_s = object%qcd%alpha%get (mu)
select type (driver => object%driver)
type is (gosam_driver_t)
    call driver%set_alpha_s (alpha_s)
    call driver%blha_olp_eval2 (object%i_real(i_flg), mom, &
                                mu_dble, r, acc_dble)

    sqme = r(4)
end select
acc = acc_dble
if (acc > object%maximum_accuracy) bad_point = .true.
end subroutine prc_gosam_compute_sqme_real

```

(prc gosam: prc gosam: TBP)+≡

```

procedure :: compute_sqme_sc => prc_gosam_compute_sqme_sc

```

(prc gosam: procedures)+≡

```

subroutine prc_gosam_compute_sqme_sc (object, &
    i_flg, em, p, ren_scale_in, &
    me_sc, bad_point)
class(prc_gosam_t), intent(inout) :: object
integer, intent(in) :: i_flg
integer, intent(in) :: em
type(vector4_t), intent(in), dimension(:) :: p
real(default), intent(in) :: ren_scale_in
complex(default), intent(out) :: me_sc
logical, intent(out) :: bad_point
real(double), dimension(OLP_MOMENTUM_LIMIT) :: mom
real(double), dimension(OLP_RESULTS_LIMIT) :: r
real(double) :: ren_scale_dble
integer :: i, igm1, n
integer :: pos_real, pos_imag
real(double) :: acc_dble
real(default) :: acc, ren_scale
real(default) :: alpha_s

me_sc = cmplx(0,0,default)
mom = object%create_momentum_array (p)
if (ren_scale_in == 0.0) then
    ren_scale = sqrt (2*p(1)*p(2))
else
    ren_scale = ren_scale_in

```

```

end if
alpha_s = object%qcd%alpha%get (ren_scale)
ren_scale_dble = dble (ren_scale)
select type (driver => object%driver)
type is (gosam_driver_t)
  call driver%set_alpha_s (alpha_s)
  call driver%blha_olp_eval2 (object%i_sc(i_flg), &
    mom, ren_scale_dble, r, acc_dble)
end select

```

The BLHA-interface conventions require the quantity $S_{ij} = \langle M_{i,+} | T_i T_j | M_{i,-} \rangle$ to be produced, where i is the position of the splitting gluon. However, $\tilde{M} = \langle M_{i,-} | M_{i,+} \rangle$ is needed. This can be obtained using color conservation, $\sum_j T_j |M\rangle = 0$, so that

$$\sum_{j \neq i} S_{ij} = -\langle M_{i,+} | T_i^2 | M_{i,-} \rangle = -C_A \langle M_{i,+} | M_{i,-} \rangle = -C_A \tilde{M}^*$$

According to BLHA conventions, the real part of S_{ij} is located at positions $2i + 2nj$ in the output array, where n denotes the number of external particles and the enumeration of particles starts at zero. The subsequent position, i.e. $2i + 2nj + 1$ is designated to the imaginary part of S_{ij} . Note that, since the first array position is 1, the implemented position association deviates from the above one in the addition of 1.

```

<prc gosam: procedures> +=
  igm1 = em-1
  n = size(p)
  do i = 0, n-1
    pos_real = 2*igm1 + 2*n*i + 1
    pos_imag = pos_real + 1
    me_sc = me_sc + cmplx (r(pos_real), r(pos_imag), default)
  end do

  me_sc = -conjg(me_sc)/CA

  acc = acc_dble
  if (acc > object%maximum_accuracy) bad_point = .true.
end subroutine prc_gosam_compute_sqme_sc

<prc gosam: prc gosam: TBP> +=
  procedure :: allocate_workspace => prc_gosam_allocate_workspace

<prc gosam: procedures> +=
  subroutine prc_gosam_allocate_workspace (object, core_state)
    class(prc_gosam_t), intent(in) :: object
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    allocate (gosam_state_t :: core_state)
  end subroutine prc_gosam_allocate_workspace

<prc gosam: gosam state: TBP> =
  procedure :: write => gosam_state_write

```

```

<prc gosam: procedures>+≡
  subroutine gosam_state_write (object, unit)
    class(gosam_state_t), intent(in) :: object
    integer, intent(in), optional :: unit
    call msg_warning ("gosam_state_write: What to write?")
  end subroutine gosam_state_write

```

Chapter 25

FKS Subtraction Scheme

The code in this chapter implements the FKS subtraction scheme for use with WHIZARD.

These are the modules:

fks_regions Given a process definition, identify singular regions in the associated phase space.

virtual Handle the virtual correction matrix element.

real_subtraction Handle the real-subtraction matrix element.

nlo_data Manage the subtraction objects.

phs_fks Phase-space parameterization with modifications for the FKS scheme.

This chapter deals with next-to-leading order contributions to cross sections. Basically, there are three major issues to be addressed: The creation of the $N+1$ -particle flavor structure, the construction of the $N+1$ -particle phase space and the actual calculation of the real- and virtual-subtracted matrix elements. The first is dealt with using the **auto_components** class, and it will be shown that the second and third issue are connected in FKS subtraction.

25.1 Brief outline of FKS subtraction

In the current state, this discussion is only concerned with lepton collisions. For hadron collisions, renormalization of parton distributions has to be taken into account. Further, for QCD corrections, initial-state radiation is necessarily present. However, most quantities have so far been only constructed for final-state emissions

The aim is to calculate the next-to-leading order cross section according to

$$d\sigma_{\text{NLO}} = \mathcal{B} + \mathcal{V} + \mathcal{R}d\Phi_{\text{rad}}.$$

Analytically, the divergences, in terms of poles in the complex quantity $\varepsilon = 2 - d/2$, cancel. However, this is in general only valid in an arbitrary, complex number of dimensions. This is, roughly, the content of the KLN-theorem. WHIZARD, as any other numerical program, is confined to four dimensions. We will assume

that the KLN-theorem is valid and that there exist subtraction terms \mathcal{C} such that

$$d\sigma_{\text{NLO}} = \mathcal{B} + \underbrace{\mathcal{V} + \mathcal{C}}_{\text{finite}} + \underbrace{\mathcal{R} - \mathcal{C}}_{\text{finite}},$$

i.e. the subtraction terms correspond to the divergent limits of the real and virtual matrix element.

Because \mathcal{C} subtracts the divergences of \mathcal{R} as well as those of \mathcal{V} , it suffices to consider one of them, so we focus on \mathcal{R} . For this purpose, \mathcal{R} is rewritten,

$$\mathcal{R} = \frac{1}{\xi^2} \frac{1}{1-y} (\xi^2(1-y)\mathcal{R}) = \frac{1}{\xi^2} \frac{1}{1-y} \tilde{\mathcal{R}},$$

with $\xi = (2k_{\text{rad}}^0)/\sqrt{s}$ and $y = \cos\theta$, where k_{rad}^0 denotes the energy of the radiated parton and θ is the angle between emitter and radiated parton. $\tilde{\mathcal{R}}$ is finite, therefore the whole singularity structure is contained in the prefactor $\xi^{-2}(1-y)^{-1}$. Combined with the d-dimensional phase space element,

$$\frac{d^{d-1}k}{2k^0(2\pi)^{d-1}} = \frac{s^{1-\varepsilon}}{(4\pi)^{d-1}} \xi^{1-2\varepsilon} (1-y)^{-\varepsilon} d\xi dy d\Omega^{d-2},$$

this yields

$$d\Phi_{\text{rad}}\mathcal{R} = dy(1-y)^{-1-\varepsilon} d\xi \xi^{-1-2\varepsilon} \tilde{R}.$$

This can further be rewritten in terms of plus-distributions,

$$\begin{aligned} \xi^{-1-2\varepsilon} &= -\frac{1}{2\varepsilon} \delta(\xi) + \left(\frac{1}{\xi}\right)_+ - 2\varepsilon \left(\frac{\log \xi}{\xi}\right)_+ + \mathcal{O}(\varepsilon^2), \\ (1-y)^{-1-\varepsilon} &= -\frac{2^{-\varepsilon}}{\varepsilon} \delta(1-y) + \left(\frac{1}{1-y}\right)_+ - \varepsilon \left(\frac{1}{1-y}\right)_+ \log(1-y) + \mathcal{O}(\varepsilon^2), \end{aligned}$$

(imagine that all this is written inside of integrals, which are spared for ease of notation) such that

$$\begin{aligned} d\Phi_{\text{rad}}\mathcal{R} &= -\frac{1}{2\varepsilon} dy(1-y)^{-1-\varepsilon} \tilde{R}(0, y) - d\xi \left[\frac{2^{-\varepsilon}}{\varepsilon} \left(\frac{1}{\xi}\right)_+ - 2 \left(\frac{\log \xi}{\xi}\right)_+ \right] \tilde{R}(\xi, 1) \\ &\quad + dy d\xi \left(\frac{1}{\xi}\right)_+ \left(\frac{1}{1-y}\right)_+ \tilde{R}(\xi, y) + \mathcal{O}(\varepsilon). \end{aligned}$$

The summand in the second line is of order $\mathcal{O}(1)$ and is the only one to reproduce $\mathcal{R}\xi, y$. It thus constitutes the sum of the real matrix element and the corresponding counterterms. The first summand consequently consists of the subtraction terms to the virtual matrix elements. Above formula thus allows to calculate all quantities to render the matrix elements finite.

alr	flst_alr	emi	ftuple_list
1	[-11,11,2,-2,21,21]	3	(3,5), (3,6), (4,5), (4,6), (5,6)
2	[-11,11,2,-2,21,21]	4	(3,5), (3,6), (4,5), (4,6), (5,6)
3	[-11,11,2,-2,21,21]	5	(3,5), (3,6), (4,5), (4,6), (5,6)
4	[-11,11,2,-2,2,-2]	5	(5,6)

Table 25.1: List of singular regions. The particles are represented by their PDG codes. The third column contains the emitter for the specific singular region. For the process involving an additional gluon, the gluon can either be emitted from one of the quarks or from the first gluon. Each emitter yields the same list of fundamental tuples, five in total. The last singular region corresponds to the process where the gluon splits up into two quarks. Here, there is only one fundamental tuple, corresponding to a singular configuration of the momenta of the additional quarks.

25.2 Identifying singular regions

In the FKS subtraction scheme, the phase space is decomposed into disjoint singular regions, such that

$$\sum_i \mathcal{S}_i + \sum_{ij} \mathcal{S}_{ij} = 1. \quad (25.1)$$

The quantities \mathcal{S}_i and \mathcal{S}_{ij} are functions of phase space corresponding to a pair of particles indices which can make up a divergent phase space region. We call such an index pair a fundamental tuple. For example, the process $e^+ e^- \rightarrow u \bar{u} g$ has two singular regions, (3, 5) and (4, 5), indicating that the gluon can be soft or collinear with respect to either the quark or the anti-quark. Therefore, the functions \mathcal{S}_{ij} have to be chosen in such a way that their contribution makes up most of (25.1) in phase-space configurations where (final-state) particle j is collinear to particle i or/and particle j is soft. The functions \mathcal{S}_i is the corresponding quantity for initial-state divergences.

As a singular region we understand the collection of real flavor structures associated with an emitter and a list of all possible fundamental tuples. As an example, consider the process $e^+ e^- \rightarrow u \bar{u} g$. At next-to-leading order, processes with an additionally radiated particle have to be considered. In this case, these are $e^+ e^- \rightarrow u \bar{u}, g g$, and $e^+ e^- \rightarrow u \bar{u} u \bar{u}$ (or the same process with any other quark). Table 25.2 sums up all possible singular regions for this problem.

Thus, during the preparation of a NLO-calculation, the possible singular regions have to be identified. `fk_regions.f90` deals with this issue.

alr	ftuple	emitter	flst_alr
1	(3, 5)	5	[-11,11,-2,21,2,21]
2	(4, 5)	5	[-11,11,2,21,-2,21]
3	(3, 6)	5	[-11,11,-2,21,2,21]
4	(4, 6)	5	[-11,11,2,21,-2,21]
5	(5, 6)	5	[-11,11,2,-2,21,21]
6	(5, 6)	5	[-11,11,2,-2,2,-2]

Table 25.2: Initial list of singular regions

25.3 FKS Regions

`<fks_regions.f90>`≡
<File header>

```

module fks_regions

    use kinds
    use io_units
    <Use strings>
    use constants
    use diagnostics
    use flavors
    use process_constants
    use lorentz
    use pdg_arrays
    use model_data
    use physics_defs

    <Standard module head>

    <fks regions: public>

    <fks regions: parameters>

    <fks regions: types>

    <fks regions: interfaces>

    contains

    <fks regions: procedures>

end module fks_regions

```

There are three fundamental splitting types: $q \rightarrow qg$, $g \rightarrow gg$ and $g \rightarrow qq$.

`<fks regions: parameters>`≡

```

integer, parameter :: UNDEFINED_SPLITTING = 0
integer, parameter :: Q_TO_QG = 1
integer, parameter :: G_TO_GG = 2
integer, parameter :: G_TO_QQ = 3

```

We group the indices of the emitting and the radiated particle in the `ftuple`-object.

`<fks regions: public>`≡

```

public :: ftuple_t

```

`<fks regions: types>`≡

```

type :: ftuple_t
    integer, dimension(2) :: ireg
    integer :: splitting_type
contains
    <fks regions: ftuple: TBP>
end type ftuple_t

```

```

<fks regions: ftuple: TBP>≡
  procedure :: write => ftuple_write

<fks regions: procedures>≡
  subroutine ftuple_write (ftuple, unit)
    class(ftuple_t), intent(in) :: ftuple
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u, "(A1,I1,A1,I1,A1)") &
      '(', ftuple%ireg(1), ', ', ftuple%ireg(2), ') '
  end subroutine ftuple_write

<fks regions: ftuple: TBP>+≡
  procedure :: get => ftuple_get

<fks regions: procedures>+≡
  subroutine ftuple_get (ftuple, pos1, pos2)
    class(ftuple_t), intent(in) :: ftuple
    integer, intent(out) :: pos1, pos2
    pos1 = ftuple%ireg(1)
    pos2 = ftuple%ireg(2)
  end subroutine ftuple_get

<fks regions: ftuple: TBP>+≡
  procedure :: set => ftuple_set

<fks regions: procedures>+≡
  subroutine ftuple_set (ftuple, pos1, pos2)
    class(ftuple_t), intent(inout) :: ftuple
    integer, intent(in) :: pos1, pos2
    ftuple%ireg(1) = pos1
    ftuple%ireg(2) = pos2
  end subroutine ftuple_set

<fks regions: ftuple: TBP>+≡
  procedure :: determine_splitting_type => ftuple_determine_splitting_type

<fks regions: procedures>+≡
  subroutine ftuple_determine_splitting_type (ftuple, flv, i, j)
    class(ftuple_t), intent(inout) :: ftuple
    type(flv_structure_t), intent(in) :: flv
    integer, intent(in) :: i, j
    associate (flst => flv%flst)
      if (flst(i) == GLUON .and. flst(j) == GLUON) then
        ftuple%splitting_type = G_TO_GG
      else if (flst(i)+flst(j) == 0 &
        .and. is_quark (abs(flst(i)))) then
        ftuple%splitting_type = G_TO_QQ
      else if (is_quark(abs(flst(i))) .and. flst(j) == GLUON &
        .or. is_quark(abs(flst(j))) .and. flst(i) == GLUON) then
        ftuple%splitting_type = Q_TO_QG
      else
        ftuple%splitting_type = UNDEFINED_SPLITTING
      end if
    end associate
  end subroutine ftuple_determine_splitting_type

```

```

        end if
    end associate
end subroutine ftuple_determine_splitting_type

```

Each singular region can have a different number of emitter-radiation pairs. This is coped with using the linked list `ftuple_list`.

```

<fks regions: types>+≡
type :: ftuple_list_t
    integer :: index
    type(ftuple_t) :: ftuple
    type(ftuple_list_t), pointer :: next
    type(ftuple_list_t), pointer :: prev
    type(ftuple_list_t), pointer :: equiv
contains
    <fks regions: ftuple list: TBP>
end type ftuple_list_t

<fks regions: ftuple list: TBP>≡
procedure :: init => ftuple_list_init

<fks regions: procedures>+≡
subroutine ftuple_list_init (list)
    class(ftuple_list_t), intent(inout) :: list
    list%index = 0
    nullify (list%next)
    nullify (list%prev)
    nullify (list%equiv)
end subroutine ftuple_list_init

<fks regions: ftuple list: TBP>+≡
procedure :: write => ftuple_list_write

<fks regions: procedures>+≡
subroutine ftuple_list_write (list)
    class(ftuple_list_t), intent(in), target :: list
    type(ftuple_list_t), pointer :: current
    select type (list)
    type is (ftuple_list_t)
        current => list
    do
        call current%ftuple%write
        if (associated (current%next)) then
            current => current%next
        else
            exit
        end if
    end do
end select
end subroutine ftuple_list_write

<fks regions: ftuple list: TBP>+≡
procedure :: append => ftuple_list_append

```

```

(fks regions: procedures) +=
subroutine ftuple_list_append (list, ftuple)
class(ftuple_list_t), intent(inout), target :: list
type(ftuple_t), intent(in) :: ftuple
type(ftuple_list_t), pointer :: current

select type (list)
type is (ftuple_list_t)
if (list%index == 0) then
    nullify(list%next)
    list%index = 1
    list%ftuple = ftuple
else
    current => list
    do
        if (associated (current%next)) then
            current => current%next
        else
            allocate (current%next)
            nullify (current%next%next)
            nullify (current%next%equiv)
            current%next%prev => current
            current%next%index = current%index + 1
            current%next%ftuple = ftuple
            exit
        end if
    end do
end if
end select
end subroutine ftuple_list_append

(fks regions: ftuple list: TBP) +=
procedure :: get_n_tuples => ftuple_list_get_n_tuples

(fks regions: procedures) +=
function ftuple_list_get_n_tuples (list) result(n_tuples)
class(ftuple_list_t), intent(inout), target :: list
integer :: n_tuples
type(ftuple_list_t), pointer :: current
select type (list)
type is (ftuple_list_t)
    current => list
    n_tuples = 1
    do
        if (associated (current%next)) then
            current => current%next
            n_tuples = n_tuples + 1
        else
            exit
        end if
    end do
end select
end function ftuple_list_get_n_tuples

```

```

(fks regions: ftuple list: TBP)+≡
  procedure :: get_entry => ftuple_list_get_entry

(fks regions: procedures)+≡
  function ftuple_list_get_entry(list, index) result(entry)
    class(ftuple_list_t), intent(inout), target :: list
    integer, intent(in) :: index
    type(ftuple_list_t), pointer :: entry
    type(ftuple_list_t), pointer :: current
    integer :: i
    select type (list)
    type is (ftuple_list_t)
      current => list
      if (index <= list%get_n_tuples ()) then
        if (index == 1) then
          entry => current
        else
          do i=1,index-1
            current => current%next
          end do
          entry => current
        end if
      else
        call msg_fatal &
          ("Index must be smaller or equal than the total number of regions!")
      end if
    end select
  end function ftuple_list_get_entry

(fks regions: ftuple list: TBP)+≡
  procedure :: get_ftuple => ftuple_list_get_ftuple

(fks regions: procedures)+≡
  function ftuple_list_get_ftuple (list, index) result (ftuple)
    class(ftuple_list_t), intent(inout) :: list
    integer, intent(in) :: index
    type(ftuple_t) :: ftuple
    type(ftuple_list_t) :: entry
    entry = list%get_entry (index)
    ftuple = entry%ftuple
  end function ftuple_list_get_ftuple

(fks regions: ftuple list: TBP)+≡
  procedure :: set_equiv => ftuple_list_set_equiv

(fks regions: procedures)+≡
  subroutine ftuple_list_set_equiv (list, i1, i2)
    class(ftuple_list_t), intent(inout) :: list
    integer, intent(in) :: i1, i2
    type(ftuple_list_t), pointer :: list1, list2
    select type (list)
    type is (ftuple_list_t)
      list1 => list%get_entry (i1)
      list2 => list%get_entry (i2)
    do

```

```

        if (associated (list1%equiv)) then
            list1 => list1%equiv
        else
            exit
        end if
    end do
    list1%equiv => list2
end select
end subroutine ftuple_list_set_equiv

```

```

<fks regions: ftuple list: TBP>+≡
    procedure :: check_equiv => ftuple_list_check_equiv

<fks regions: procedures>+≡
    function ftuple_list_check_equiv(list, i1, i2) result(eq)
        class(ftuple_list_t), intent(inout) :: list
        integer, intent(in) :: i1, i2
        logical :: eq
        type(ftuple_list_t), pointer :: current
        select type (list)
        type is (ftuple_list_t)
            current => list%get_entry (i1)
        do
            if (associated (current%equiv)) then
                current => current%equiv
                if (current%index == i2) then
                    eq = .true.
                    exit
                end if
            else
                eq = .false.
                exit
            end if
        end do
    end select
end function ftuple_list_check_equiv

```

Class for working with the flavor specification arrays.

```

<fks regions: public>+≡
    public :: flv_structure_t

<fks regions: types>+≡
    type :: flv_structure_t
        integer, dimension(:), allocatable :: flst
        integer :: nlegs
        logical, dimension(:), allocatable :: massive
        logical, dimension(:), allocatable :: colored
    contains
    <fks regions: flv structure: TBP>
    end type flv_structure_t

```

Returns `true` if the two particles at position `i` and `j` in the flavor array can originate from the same splitting. For this purpose, the function first checks

whether the splitting is allowed at all. If this is the case, the emitter is removed from the flavor array. If the resulting array is equivalent to the Born flavor structure `flv_born`, the pair is accepted as a valid splitting.

```

(fks regions: flv structure: TBP)≡
  procedure :: valid_pair => flv_structure_valid_pair

(fks regions: procedures)+≡
  function flv_structure_valid_pair &
    (flv_real,i,j, flv_born, model) result (valid)
    class(flv_structure_t), intent(in) :: flv_real
    integer, intent(in) :: i,j
    type(flv_structure_t), intent(in) :: flv_born
    type(model_data_t), intent(in) :: model
    logical :: valid
    integer :: k, n_orig
    type(flv_structure_t) :: flv_test
    integer, dimension(:), allocatable :: flv_orig, flv_orig2
    valid = .false.

```

First check whether the splitting is possible. The array `flv_orig` contains all particles which share a vertex with the particles at position `i` and `j`. If its size is equal to zero, no splitting is possible and the subroutine is exited.

```

(fks regions: procedures)+≡
  call model%match_vertex &
    (flv_real%flst(i), flv_real%flst(j), flv_orig)
  n_orig = size (flv_orig)
  if (n_orig == 0) then
    return
  else

```

For a quark emitting a gluon, `flv_orig` contains the PDG code of the anti-quark. To be on the safe side, a second array is created, which contains both the positively and negatively signed PDG codes. Then, the original tuple (i, j) is removed from the real flavor structure and the particles in `flv_orig2` are inserted. If the resulting Born configuration is equal to the underlying Born configuration, up to a permutation of final-state particles, the tuple (i, j) is accepted as valid.

```

(fks regions: procedures)+≡
  allocate (flv_orig2 (2*n_orig))
  flv_orig2 (1:n_orig) = flv_orig
  flv_orig2 (n_orig+1:2*n_orig) = -flv_orig
  do k = 1, 2*n_orig
    flv_test = flv_real%insert_particle (i,j,flv_orig2(k))
    valid = flv_born == flv_test
    if (valid) return
  end do
end if
end function flv_structure_valid_pair

```

This function checks whether two flavor arrays are the same up to a permutation of the final-state particles

```

(fks regions: procedures)+≡
  function flv_structure_equivalent (flv1, flv2) result(equiv)

```



```

type(flv_structure_t), intent(in) :: flv1, flv2
logical :: equiv
integer :: i, j, n
logical, dimension(:), allocatable :: present, checked
n = size (flv1%flst)
equiv = .true.
if (n /= size (flv2%flst)) then
    call msg_fatal &
        ('flv_structure_equivalent: flavor arrays do not have equal lengths')
else
    allocate (present(n))
    allocate (checked(n))
    do i=1,n
        present(i) = .false.
        checked(i) = .false.
    end do
    do i=1,n
        do j=1,n
            if (flv1%flst(i) == flv2%flst(j) .and. .not. checked(j)) then
                present(i) = .true.
                checked(j) = .true.
                exit
            end if
        end do
    end do
    do i=1,n
        if(.not.present(i)) equiv = .false.
    end do
end if
end function flv_structure_equivalent

```

Returns a new flavor array with the particle at position `index` removed.

(fks regions: flv structure: TBP)+≡

```

procedure :: remove_particle => flv_structure_remove_particle

```

(fks regions: procedures)+≡

```

function flv_structure_remove_particle (flv1, index) result(flv2)
    class(flv_structure_t), intent(in) :: flv1
    integer, intent(in) :: index
    type(flv_structure_t) :: flv2
    integer :: n1, n2
    n1 = size (flv1%flst)
    n2 = n1-1
    if (allocated (flv2%flst)) then
        deallocate (flv2%flst)
    end if
    allocate (flv2%flst (n2))
    if (index == 1) then
        flv2%flst(1:n2) = flv1%flst(2:n1)
    else if (index == n1) then
        flv2%flst(1:n2) = flv1%flst(1:n2)
    else
        flv2%flst(1:index-1) = flv1%flst(1:index-1)
        flv2%flst(index:n2) = flv1%flst(index+1:n1)
    end if
end function

```

```

        end if
    end function flv_structure_remove_particle

```

Removes the particles at position i1 and i2 and inserts a new particle at position i1.

```

⟨fks regions: flv structure: TBP⟩+≡
    procedure :: insert_particle => flv_structure_insert_particle

⟨fks regions: procedures⟩+≡
    function flv_structure_insert_particle (flv1, i1, i2, particle) result (flv2)
        class(flv_structure_t), intent(in) :: flv1
        integer, intent(in) :: i1, i2, particle
        type(flv_structure_t) :: flv2
        type(flv_structure_t) :: flv_tmp
        integer :: n1, n2
        n1 = size (flv1%flst)
        n2 = n1-1
        allocate (flv2%flst(n2))
        if (i1 < i2) then
            flv_tmp = flv1%remove_particle (i1)
            flv_tmp = flv_tmp%remove_particle (i2-1)
        else if (i2 < i1) then
            flv_tmp = flv1%remove_particle(i2)
            flv_tmp = flv_tmp%remove_particle(i1-1)
        else
            call msg_fatal ("Trying to set ftuple with i1 = i2!")
        end if
        if (i1 == 1) then
            flv2%flst(1) = particle
            flv2%flst(2:n2) = flv_tmp%flst(1:n2-1)
        else if (i1 == n1 .or. i1 == n2) then
            flv2%flst(1:n2-1) = flv_tmp%flst(1:n2-1)
            flv2%flst(n2) = particle
        else
            flv2%flst(1:i1-1) = flv_tmp%flst(1:i1-1)
            flv2%flst(i1) = particle
            flv2%flst(i1+1:n2) = flv_tmp%flst(i1:n2-1)
        end if
    end function flv_structure_insert_particle

```

Returns the number of particles in a flavor array

```

⟨fks regions: flv structure: TBP⟩+≡
    procedure :: get_nlegs => flv_structure_get_nlegs

⟨fks regions: procedures⟩+≡
    function flv_structure_get_nlegs (flv) result(n)
        class(flv_structure_t), intent(in) :: flv
        integer :: n
        n = size (flv%flst)
    end function flv_structure_get_nlegs

```

Counts the number of occurrences of a particle in a flavor array

```

⟨fks regions: flv structure: TBP⟩+≡
    procedure :: count_particle => flv_structure_count_particle

```

```

<fks regions: procedures>+≡
function flv_structure_count_particle (flv, part) result (n)
  class(flv_structure_t), intent(in) :: flv
  integer, intent(in) :: part
  integer :: n
  n = count (flv%flst == part)
end function flv_structure_count_particle

```

Initializer for flavor structures

```

<fks regions: flv structure: TBP>+≡
procedure :: init => flv_structure_init

<fks regions: procedures>+≡
subroutine flv_structure_init (flv, aval)
  class(flv_structure_t), intent(inout) :: flv
  integer, intent(in), dimension(:) :: aval
  integer :: n
  n = size (aval)
  allocate (flv%flst (n))
  flv%flst(1:n) = aval(1:n)
  flv%nlegs = n
end subroutine flv_structure_init

```

```

<fks regions: flv structure: TBP>+≡
procedure :: write => flv_structure_write

<fks regions: procedures>+≡
subroutine flv_structure_write (flv, unit)
  class(flv_structure_t), intent(in) :: flv
  integer, intent(in), optional :: unit
  integer :: i, u
  u = given_output_unit (unit); if (u < 0) return
  write (u, '(A1)', advance = 'no') '['
  do i = 1, size(flv%flst)-1
    write (u, '(I3,A1)', advance = 'no') flv%flst(i), ','
  end do
  write (u, '(I3,A1)') flv%flst(i), ']'
end subroutine flv_structure_write

```

Creates the underlying Born flavor structure for a given real flavor structure if the particle at position `emitter` is removed

```

<fks regions: flv structure: TBP>+≡
procedure :: create_uborn => flv_structure_create_uborn

<fks regions: procedures>+≡
function flv_structure_create_uborn (flst_alr, emitter) result(flst_uborn)
  class(flv_structure_t), intent(in) :: flst_alr
  integer, intent(in) :: emitter
  type(flv_structure_t) :: flst_uborn
  integer n_alr, n_uborn
  n_alr = size(flst_alr%flst)
  n_uborn = n_alr-1
  allocate (flst_uborn%flst (n_uborn))
  if (emitter > 2) then

```

```

    if (flst_alr%flst(n_alr) == 21) then
        !!! Emitted particle is a gluon => just remove it
        flst_uborn = flst_alr%remove_particle(n_alr)
        !!! Emission type is a gluon splitting into two quars
    else if (is_quark (abs(flst_alr%flst(n_alr))) .and. &
             is_quark (abs(flst_alr%flst(n_alr-1))) .and. &
             flst_alr%flst(n_alr) + flst_alr%flst(n_alr-1) == 0) then
        flst_uborn = flst_alr%insert_particle(n_alr-1,n_alr,21)
    end if
else
    if (flst_alr%flst(n_alr) == 21) then
        flst_uborn = flst_alr%remove_particle(n_alr)
    else if (is_quark (abs(flst_alr%flst(n_alr))) .and. &
             is_gluon (abs(flst_alr%flst(emitter)))) then
        flst_uborn = &
            flst_alr%insert_particle (emitter,n_alr,-flst_alr%flst(n_alr))
    else if (is_quark (abs(flst_alr%flst(n_alr))) .and. &
             is_quark (abs(flst_alr%flst(emitter))) .and. &
             flst_alr%flst(n_alr) == flst_alr%flst(emitter)) then
        flst_uborn = flst_alr%insert_particle(emitter,n_alr,21)
    end if
end if
end function flv_structure_create_uborn

```

<fks regions: flv structure: TBP>+≡
 procedure :: evaluate => flv_structure_evaluate

<fks regions: procedures>+≡
 subroutine flv_structure_evaluate (flv, n, model)
 class(flv_structure_t), intent(inout) :: flv
 integer, intent(in) :: n
 type(model_data_t), intent(in) :: model
 integer :: i
 type(flavor_t) :: flavor
 allocate (flv%massive (n), flv%colored(n))
 do i = 1, n
 call flavor%init (flv%flst(i), model)
 flv%massive(i) = flavor%get_mass () > 0
 flv%colored(i) = is_quark (abs(flv%flst(i))) .or. &
 is_gluon (flv%flst(i))
 end do
end subroutine flv_structure_evaluate

<fks regions: public>+≡
 public :: singular_region_t

<fks regions: types>+≡
 type :: singular_region_t
 integer :: alr
 type(flv_structure_t) :: flst_real
 type(flv_structure_t) :: flst_uborn
 integer :: mult
 integer :: emitter
 integer :: nregions

```

integer :: real_index
type(ftuple_t), dimension(:), allocatable :: flst_allreg
integer :: uborn_index
logical :: double_fsr
logical :: soft_divergence
logical :: coll_divergence
contains
<fks regions: singular region: TBP>
end type singular_region_t

```

In case of a $g \rightarrow gg$ or $g \rightarrow qq$ splitting, the factor

$$\frac{2E_{\text{em}}}{E_{\text{em}} + E_{\text{rad}}}$$

is multiplied to the real matrix element. This way, the symmetry of the splitting is used and only one singular region has to be taken into account. However, the factor ensures that there is only a soft singularity if the radiated parton becomes soft.

```

<fks regions: singular region: TBP>≡
  procedure :: set_splitting_info => singular_region_set_splitting_info

<fks regions: procedures>+≡
  subroutine singular_region_set_splitting_info (region)
    class(singular_region_t), intent(inout) :: region
    integer :: i1, i2
    integer :: reg
    region%double_fsr = .false.
    associate (ftuple => region%flst_allreg)
      do reg = 1, region%nregions
        call ftuple(reg)%get (i1, i2)
        if (i1 /= region%emitter) then
          cycle
        else
          region%soft_divergence = &
            ftuple(reg)%splitting_type /= G_TO_QQ

          if (i1 == 0) then
            !!! IS-splitting always has a collinear divergence (because massless)
            region%coll_divergence = .true.
          else
            region%coll_divergence = &
              .not. region%flst_real%massive(i1)
          end if

          if (ftuple(reg)%splitting_type > 1) then
            region%double_fsr = .true.
            exit
          else if (ftuple(reg)%splitting_type == UNDEFINED_SPLITTING) then
            call msg_fatal ("All splittings should be defined!")
          end if
        end if
      end do
    end associate
  end subroutine

```

```

end subroutine singular_region_set_splitting_info

<fks regions: singular region: TBP>+≡
  procedure :: double_fsr_factor => singular_region_double_fsr_factor

<fks regions: procedures>+≡
  function singular_region_double_fsr_factor (region, p) result (val)
    class(singular_region_t), intent(in) :: region
    type(vector4_t), intent(in), dimension(:) :: p
    real(default) :: val
    real(default) :: E_rad, E_em
    if (region%double_fsr) then
      E_em = energy (p(region%emitter))
      E_rad = energy (p(region%flst_real%get_nlegs()))
      val = 2*E_em/(E_em + E_rad)
    else
      val = 1._default
    end if
  end function singular_region_double_fsr_factor

<fks regions: singular region: TBP>+≡
  procedure :: has_soft_divergence => singular_region_has_soft_divergence

<fks regions: procedures>+≡
  function singular_region_has_soft_divergence (region) result (div)
    class(singular_region_t), intent(in) :: region
    logical :: div
    div = region%soft_divergence
  end function singular_region_has_soft_divergence

<fks regions: singular region: TBP>+≡
  procedure :: has_collinear_divergence => &
    singular_region_has_collinear_divergence

<fks regions: procedures>+≡
  function singular_region_has_collinear_divergence (region) result (div)
    class(singular_region_t), intent(in) :: region
    logical :: div
    div = region%coll_divergence
  end function singular_region_has_collinear_divergence

<fks regions: types>+≡
  type, abstract :: fks_mapping_t
    real(default) :: sumdi_j
    real(default) :: sumdi_j_soft
  contains
    <fks regions: fks mapping: TBP>
  end type fks_mapping_t

<fks regions: public>+≡
  public :: fks_mapping_default_t

```

```

<fks regions: types>+≡
  type, extends (fks_mapping_t) :: fks_mapping_default_t
    real(default) :: exp_1, exp_2
  contains
  <fks regions: fks mapping 1: TBP>
end type fks_mapping_default_t

<fks regions: interfaces>≡
  interface operator(==)
    module procedure flv_structure_equivalent
  end interface

<fks regions: public>+≡
  public :: region_data_t

<fks regions: types>+≡
  type :: region_data_t
    type(singular_region_t), dimension(:), allocatable :: regions
    type(flv_structure_t), dimension(:), allocatable :: flv_born
    type(flv_structure_t), dimension(:), allocatable :: flv_real
    integer, dimension(:), allocatable :: emitters
    integer :: n_regions
    integer :: n_emitters
    integer :: n_flv_born
    integer :: n_flv_real
    integer :: nlegs_born
    integer :: nlegs_real
    type(flavor_t) :: flv_extra
    class(fks_mapping_t), allocatable :: fks_mapping
  contains
  <fks regions: reg data: TBP>
end type region_data_t

<fks regions: reg data: TBP>≡
  procedure :: init => region_data_init

<fks regions: procedures>+≡
  subroutine region_data_init (reg_data, model, flavor_born, &
                               flavor_real, mapping_type)
    class(region_data_t), intent(inout) :: reg_data
    type(model_data_t), intent(in) :: model
    integer, intent(inout), dimension(:,:), allocatable :: &
      flavor_born, flavor_real
    integer, intent(in) :: mapping_type
    integer, dimension(:), allocatable :: current_flavor
    type(ftuple_list_t), dimension(:), allocatable :: ftuples
    integer, dimension(:), allocatable :: emitter
    type(flv_structure_t), dimension(:), allocatable :: flst_alr
    integer :: i
    reg_data%n_flv_born = size(flavor_born(1,:))
    reg_data%n_flv_real = size(flavor_real(1,:))
    reg_data%nlegs_born = size(flavor_born(:,1))
    reg_data%nlegs_real = reg_data%nlegs_born + 1
  end subroutine

```

```

allocate (reg_data%flv_born (reg_data%n_flv_born))
allocate (reg_data%flv_real (reg_data%n_flv_real))
allocate (current_flavor (reg_data%n_flv_born))
do i = 1, reg_data%n_flv_born
    current_flavor = flavor_born(:,i)
    call reg_data%flv_born(i)%init (current_flavor)
end do
deallocate (current_flavor)
allocate (current_flavor (reg_data%n_flv_real))
do i = 1, reg_data%n_flv_real
    current_flavor = flavor_real(:,i)
    call reg_data%flv_real(i)%init (current_flavor)
end do

select case (mapping_type)
case (1)
    allocate (fks_mapping_default_t :: reg_data%fks_mapping)
case default
    call msg_fatal ("Init region_data: FKS mapping not implemented!")
end select

call reg_data%flv_extra%init &
    (reg_data%flv_real(1)%flst(reg_data%nlegs_real), &
    model)
call reg_data%find_regions (model, ftuples, emitter, flst_alr)
call reg_data%init_regions (ftuples, emitter, flst_alr)
call reg_data%evaluate_flavors (model)
call reg_data%set_splitting_info ()
call reg_data%find_emitters ()
end subroutine region_data_init

```

(fks regions: reg data: TBP)+≡

```

procedure :: evaluate_flavors => region_data_evaluate_flavors

```

(fks regions: procedures)+≡

```

subroutine region_data_evaluate_flavors (reg_data, model)
class(region_data_t), intent(inout) :: reg_data
type(model_data_t), intent(in) :: model
integer :: i
do i = 1, reg_data%n_regions
    associate (region => reg_data%regions(i))
        call region%flst_uborn%evaluate (reg_data%nlegs_born, model)
        call region%flst_real%evaluate (reg_data%nlegs_real, model)
    end associate
end do
do i = 1, reg_data%n_flv_born
    call reg_data%flv_born(i)%evaluate (reg_data%nlegs_born, model)
end do
do i = 1, reg_data%n_flv_real
    call reg_data%flv_real(i)%evaluate (reg_data%nlegs_real, model)
end do
end subroutine region_data_evaluate_flavors

```


Creates a list containing the emitter of each singular region.

```

<fks regions: reg data: TBP>+≡
  procedure :: get_emitter_list => region_data_get_emitter_list

<fks regions: procedures>+≡
  pure function region_data_get_emitter_list (reg_data) result(emitters)
    class(region_data_t), intent(in) :: reg_data
    integer, dimension(:), allocatable :: emitters
    integer :: i
    allocate (emitters (reg_data%n_regions))
    do i = 1, reg_data%n_regions
      emitters(i) = reg_data%regions(i)%emitter
    end do
  end function region_data_get_emitter_list

```

```

<fks regions: reg data: TBP>+≡
  procedure :: get_emitter => region_data_get_emitter

<fks regions: procedures>+≡
  pure function region_data_get_emitter (reg_data, alr) result (emitter)
    class(region_data_t), intent(in) :: reg_data
    integer, intent(in) :: alr
    integer :: emitter
    emitter = reg_data%regions(alr)%emitter
  end function region_data_get_emitter

```

Returns $S_i = \frac{1}{\mathcal{D}d_i}$ or $S_{ij} = \frac{1}{\mathcal{D}d_{ij}}$ for one particular singular region. At this point, the flavor array should be rearranged in such a way that the emitted particle is at the last position of the flavor structure list.

```

<fks regions: reg data: TBP>+≡
  procedure :: get_svalue => region_data_get_svalue

<fks regions: procedures>+≡
  function region_data_get_svalue (reg_data, p, alr, emitter) result (sval)
    class(region_data_t), intent(inout) :: reg_data
    type(vector4_t), intent(in), dimension(:) :: p
    integer, intent(in) :: alr, emitter
    real(default) :: sval
    associate (map => reg_data%fks_mapping)
      map%sumdij = map%compute_sumdij (reg_data%regions(alr), p)
      sval = map%svalue (p, emitter, reg_data%nlegs_real)
    end associate
  end function region_data_get_svalue

```

The same as above, but for the soft limit.

```

<fks regions: reg data: TBP>+≡
  procedure :: get_svalue_soft => region_data_get_svalue_soft

<fks regions: procedures>+≡
  function region_data_get_svalue_soft &
    (reg_data, p, p_soft, alr, emitter) result (sval)
    class(region_data_t), intent(inout) :: reg_data
    type(vector4_t), intent(in), dimension(:) :: p
    type(vector4_t), intent(in) :: p_soft

```

```

integer, intent(in) :: alr, emitter
real(default) :: sval
associate (map => reg_data%fks_mapping)
  map%sumdij_soft = &
  map%compute_sumdij_soft (reg_data%regions(alr), p, p_soft)
  sval = map%value_soft (p, p_soft, emitter)
end associate
end function region_data_get_svalue_soft

```

This subroutine starts with a specification of N - and $N + 1$ -particle configurations, `flst_born` and `flst_real`, saved in `reg_data`. From these, it creates a list of fundamental tuples, a list of emitters and a list containing the $N + 1$ -particle configuration, rearranged in such a way that the emitter-radiation pair is last (`flst_alr`). For the $e^+ e^- \rightarrow u \bar{u} g$ - example, the generated objects are shown in table 25.2. Note that at this point, `flst_alr` is arranged in such a way that the emitter can only be equal to $n_{legs} - 1$ for final-state radiation or 0, 1, or 2 for initial-state radiation. Further, it occurs that regions can be equivalent. For example in table 25.2 the regions corresponding to `alr = 1` and `alr = 3` as well as `alr = 2` and `alr = 4` describe the same physics and are therefore equivalent.

```

⟨fks regions: reg data: TBP⟩+=
  procedure :: find_regions => region_data_find_regions

⟨fks regions: procedures⟩+=
  subroutine region_data_find_regions &
    (reg_data, model, ftuples, emitter, flst_alr)
    class(region_data_t), intent(in) :: reg_data
    type(model_data_t), intent(in) :: model
    type(ftuple_list_t), intent(out), dimension(:), allocatable :: ftuples
    integer, intent(out), dimension(:), allocatable :: emitter
    type(flv_structure_t), intent(out), dimension(:), allocatable :: flst_alr
    type(ftuple_t) :: current_ftuple
    integer, dimension(:), allocatable :: emitter_tmp
    type(flv_structure_t), dimension(:), allocatable :: flst_alr_tmp
    integer :: nreg, nborn, nreal
    integer :: nlegreal
    integer :: n_gluon_real, n_gluon_born
    integer, parameter :: maxnregions = 100
    integer :: i, j, k, l, n

    associate (flv_born => reg_data%flv_born)
      associate (flv_real => reg_data%flv_real)
        nborn = size (flv_born)
        nreal = size (flv_real)
        nlegreal = size (flv_real(1)%flst)
        allocate (ftuples (nreal))
        allocate (emitter_tmp (maxnregions))
        allocate (flst_alr_tmp (maxnregions))
        n = 0

        ITERATE_REAL_FLAVOR: do l = 1, nreal
          call ftuples(l)%init
        end do
      end associate
    end associate
  end subroutine

⟨fks: check final state emissions⟩

```

```

<fks: check initial state emissions>
  end do ITERATE_REAL_FLAVOR

```

```

    nreg = n

    end associate
  end associate

  allocate (flst_alr (nreg))
  allocate (emitter (nreg))
  flst_alr(1:nreg) = flst_alr_tmp(1:nreg)
  emitter(1:nreg) = emitter_tmp(1:nreg)
end subroutine region_data_find_regions

```

First check final state emissions

```

<fks: check final state emissions>≡
  do i = 3, nlegreal
    do j = i+1, nlegreal
      do k = 1, nborn
        if (flv_real(1)%valid_pair(i,j, flv_born(k), model) &
          .or. flv_real(1)%valid_pair(j,i,flv_born(k), model)) then
          n = n+1
          n_gluon_real = flv_real(1)%count_particle (GLUON)
          n_gluon_born = flv_born(k)%count_particle (GLUON)
          if (n_gluon_born - n_gluon_real < 0) then
            if(flv_real(1)%valid_pair(i,j, flv_born(k), model)) then
              flst_alr_tmp(n) = create_alr (flv_real(1),i,j)
            else
              flst_alr_tmp(n) = create_alr (flv_real(1),j,i)
            end if
          else
            flst_alr_tmp(n) = flv_real(1)
          end if
          call current_ftuple%set (i,j)
          call current_ftuple%determine_splitting_type (flv_real(1), i, j)
          call ftuples(1)%append (current_ftuple)
          emitter_tmp(n) = nlegreal - 1
          exit
        end if
      end do
    end do
  end do
end do

```

Check initial-state emissions. It suffices to just check the final-state of the first and the initial-state of the second array.

```

<fks: check initial state emissions>≡
  do k = 1, nborn
    if (flv_real(1)%valid_pair(1,i, flv_born(k), model) &
      .and. flv_real(1)%valid_pair(2,i, flv_born(k), model)) then
      n = n + 1
      call current_ftuple%set (0,i)
      call ftuples(1)%append (current_ftuple)
      emitter_tmp(n) = 0
      flst_alr_tmp(n) = create_alr (flv_real(1),0,i)
      exit
    end if
  end do
end do

```

```

else if (flv_real(1)%valid_pair(1,i, flv_born(k), model) &
.and. .not. flv_real(1)%valid_pair(2,i, flv_born(k), model)) then
n = n+1
call current_ftuple%set (1,i)
call ftuples(1)%append (current_ftuple)
emitter_tmp(n) = 1
flst_alr_tmp(n) = create_alr (flv_real(1),1,i)
exit
else if (flv_real(1)%valid_pair(2,i, flv_born(k), model) &
.and. .not. flv_real(1)%valid_pair(1,i, flv_born(k), model)) then
n = n+1
call current_ftuple%set(2,i)
call ftuples(1)%append (current_ftuple)
emitter_tmp(n) = 2
flst_alr_tmp(n) = create_alr (flv_real(1),2,i)
exit
end if
end do
end do

```

Creates singular regions according to table 25.2. It scans all regions in table 25.2 and records the real flavor structures. If they are equivalent, the flavor structure is not recorded, but the multiplicity of the present one is increased.

(fks regions: reg data: TBP)+≡

```

procedure :: init_regions => region_data_init_singular_regions

```

(fks regions: procedures)+≡

```

subroutine region_data_init_singular_regions &
(reg_data, ftuples, emitter, flst_alr)
class(region_data_t), intent(inout) :: reg_data
type(ftuple_list_t), intent(inout), dimension(:), allocatable :: ftuples
type(ftuple_list_t) :: current_region
integer, intent(in), dimension(:), allocatable :: emitter
type(flv_structure_t), intent(in), dimension(:), allocatable :: flst_alr
type(flv_structure_t), dimension(:), allocatable :: flst_uborn, flst_alr2
integer, dimension(:), allocatable :: mult
integer, dimension(:), allocatable :: flst_emitter
integer :: nregions, maxregions
integer, dimension(:,:), allocatable :: perm_list
integer, dimension(:), allocatable :: index
integer :: i, j, k, l
integer :: nlegs
logical :: equiv
integer :: nreg, i1, i2
integer :: i_first, j_first
integer, dimension(:), allocatable :: &
region_to_ftuple, ftuple_limits, k_index
type(flv_structure_t) :: flst_save

maxregions = size (emitter)
nlegs = size(flst_alr(1)%flst)

allocate (flst_uborn (maxregions))
allocate (flst_alr2 (maxregions))
allocate (mult (maxregions))

```

```

allocate (flst_emitter (maxregions))
allocate (index (maxregions))
allocate (region_to_ftuple (maxregions))
allocate (ftuple_limits (size (ftuples)))
allocate (k_index (maxregions))

mult = 0

do i = 1, size(ftuples)
    ftuple_limits(i) = ftuples(i)%get_n_tuples ()
end do
if (.not. (sum (ftuple_limits) == maxregions)) &
    call msg_fatal ("Too many regions!")
k = 1
do j =1, size(ftuples)
    do i = 1, ftuple_limits(j)
        region_to_ftuple(k) = i
        k = k + 1
    end do
end do
i_first = 1
j_first = 1
j = 1
SCAN_REGIONS: do l = 1, size(ftuples)
    SCAN_FTUPLES: do i = i_first, i_first + ftuple_limits (l) -1
        equiv = .false.
        if (i==i_first) then
            flst_alr2(j)%flst = flst_alr(i)%flst
            mult(j) = mult(j) + 1
            flst_uborn(j) = flst_alr(i)%create_uborn (emitter(i))
            flst_emitter(j) = emitter(i)
            index (j) = region_to_index(ftuples, i)
            k_index (j) = region_to_ftuple(i)
            j = j+1
        else
            !!! Check for equivalent flavor structures
            do k =j_first ,j-1
                if (emitter(i) == emitter(k) .and. emitter(i) > 2) then
                    if (flst_alr(i) == flst_alr2(k) .and. &
                        flst_alr(i)%flst(nlegs-1) == flst_alr2(k)%flst(nlegs-1) &
                        .and. flst_alr(i)%flst(nlegs) == flst_alr2(k)%flst(nlegs)) then
                        mult(k) = mult(k) + 1
                        equiv = .true.
                        call ftuples (region_to_index(ftuples, i))%set_equiv &
                            (k_index(k), region_to_ftuple(i))
                        exit
                    end if
                else if (emitter(i) == emitter(k) .and. emitter(i) <= 2) then
                    if (flst_alr(i) == flst_alr2(k)) then
                        mult(k) = mult(k) + 1
                        equiv = .true.
                        call ftuples (region_to_index(ftuples,i))%set_equiv &
                            (k_index(k), region_to_ftuple(i))
                        exit
                    end if
                end if
            end do
        end if
    end do
end do

```

```

        end if
    end if
end do
if (.not.equiv) then
    flst_alr2(j)%flst = flst_alr(i)%flst
    mult(j) = mult(j) + 1
    flst_uborn(j) = flst_alr(i)%create_uborn (emitter(i))
    flst_emitter(j) = emitter(i)
    index (j) = region_to_index (ftuples, i)
    k_index (j) = region_to_ftuple(i)
    j = j+1
end if
end if
end do SCAN_FTUPLES
i_first = i_first + ftuple_limits(1)
j_first = j_first + j - 1
end do SCAN_REGIONS
nregions = j-1
allocate (reg_data%regions (nregions))
do j = 1, nregions
    do i = 1, reg_data%n_flv_born
        if (reg_data%flv_born (i) == flst_uborn (j)) then
            if (allocated (perm_list)) deallocate (perm_list)
            call fks_permute_born &
                (reg_data%flv_born (i), flst_uborn (j), perm_list)
            call fks_apply_perm (flst_alr2(j), flst_emitter(j), perm_list)
        end if
    end do
end do
end do
!!! Check if new emitters require a rearrangement of ftuples
do i = 1, nregions
    reg_data%regions(i)%alr = i
    reg_data%regions(i)%flst_real = flst_alr2(i)
    reg_data%regions(i)%mult = mult(i)
    reg_data%regions(i)%flst_uborn = flst_uborn(i)
    reg_data%regions(i)%emitter = flst_emitter(i)
    nreg = ftuples (index(i))%get_n_tuples ()
    reg_data%regions(i)%nregions = nreg
    allocate (reg_data%regions(i)%flst_allreg (nreg))
    do j = 1, nreg
        current_region = ftuples (index(i))%get_entry (j)
        if (.not. associated (current_region%equiv)) then
            call current_region%ftuple%get (i1, i2)
            if (i2 /= nlegs) &
                call current_region%ftuple%set (i1, nlegs)
            end if
            reg_data%regions(i)%flst_allreg (j) = current_region%ftuple
        end do
    end do
end do
end do
!!! Find underlying Born index
do j = 1, nregions
    do i = 1, reg_data%n_flv_born
        if (reg_data%flv_born (i) == reg_data%regions(j)%flst_uborn) then
            reg_data%regions(j)%uborn_index = i
        end if
    end do
end do

```

```

        exit
    end if
end do

k = 1
associate (regions => reg_data%regions)
do i = 1, nregions
    if (i==1) then
        regions(i)%real_index = 1
        flst_save = flst_alr2(1)
        cycle
    end if
    if (flst_alr2(i) == flst_save) then
        regions(i)%real_index = k
    else
        k = k+1
        regions(i)%real_index = k
        flst_save = flst_alr2(i)
    end if
end do
end associate
reg_data%n_regions = size (reg_data%regions)

end subroutine region_data_init_singular_regions

```

Create an array containing all emitters of a singular region.

```

<fks regions: reg data: TBP>+≡
    procedure :: find_emitters => region_data_find_emitters

<fks regions: procedures>+≡
    subroutine region_data_find_emitters (reg_data)
        class(region_data_t), intent(inout) :: reg_data
        integer :: i, j, n
        integer :: em
        integer, dimension(10) :: em_count
        em_count = 0
        n = 0

        !!! Count the number of different emitters
        do i = 1, reg_data%n_regions
            em = reg_data%regions(i)%emitter
            if (.not. any (em_count == em)) then
                n = n+1
                em_count(i) = em
            end if
        end do

        if (n < 1) call msg_fatal ("region_data_find_emitters: No emitters found")
        reg_data%n_emitters = n
        allocate (reg_data%emitters (reg_data%n_emitters))
        reg_data%emitters = 0

        j = 1
    end subroutine

```

```

do i = 1, size(reg_data%regions)
  em = reg_data%regions(i)%emitter
  if (.not. any (reg_data%emitters == em)) then
    reg_data%emitters(j) = em
    j = j+1
  end if
end do
end subroutine region_data_find_emitters

```

```

<fks regions: reg data: TBP>+≡
  procedure :: set_splitting_info => region_data_set_splitting_info
<fks regions: procedures>+≡
  subroutine region_data_set_splitting_info (reg_data)
    class(region_data_t), intent(inout) :: reg_data
    integer :: reg
    do reg = 1, reg_data%n_regions
      call reg_data%regions(reg)%set_splitting_info ()
    end do
  end subroutine region_data_set_splitting_info

```

```

<fks regions: reg data: TBP>+≡
  procedure :: write_to_file => region_data_write_to_file
<fks regions: procedures>+≡
  subroutine region_data_write_to_file (reg_data, proc_id)
    class(region_data_t), intent(inout) :: reg_data
    type(string_t), intent(in) :: proc_id
    type(string_t) :: filename
    integer :: u

    filename = proc_id // "_fks_regions.log"
    u = free_unit ()
    open (u, file=char(filename), action = "write", status="replace")
    call reg_data%write (u)
    close (u)
  end subroutine region_data_write_to_file

```

Creates a table with information about all singular regions and writes it to a file. Returns the index of the real flavor structure an ftuple belongs to.

```

<fks regions: reg data: TBP>+≡
  procedure :: write => region_data_write
<fks regions: procedures>+≡
  subroutine region_data_write (reg_data, u)
    class(region_data_t), intent(inout) :: reg_data
    integer, intent(in) :: u
    integer :: i, j
    integer :: nreal, nborn
    integer :: i1, i2, nreg
    integer :: maxnregions, nreg_diff
    integer :: nleft, nright
    type(singular_region_t) :: region
    type(string_t) :: flst_title, ftuple_title

```



```

character(len=7) :: flst_format = "(I3,A1)"
character(len=16) :: ireg_format = "(A1,I3,A1,I3,A2)"
character(len=7) :: ireg_space_format = "(7X,A1)"

maxnregions = 1
do j = 1, reg_data%n_regions
    if (size (reg_data%regions(j)%flst_allreg) > maxnregions) &
        maxnregions = reg_data%regions(j)%nregions
end do
flst_title = '(A' // flst_title_format(reg_data%nlegs_real) // ')'
ftuple_title = '(A' // ftuple_title_format() // ')'
write (u,*) 'Total number of regions: ', size(reg_data%regions)
write (u, '(A3)', advance = 'no') 'alr'
call write_separator ()
write (u, char (flst_title), advance = 'no') 'flst_real'
call write_separator ()
write (u, '(A3)', advance = 'no') 'em'
call write_separator ()
write (u, '(A3)', advance = 'no') 'mult'
call write_separator ()
write (u, '(A4)', advance = 'no') 'nreg'
call write_separator ()
write (u, char (ftuple_title), advance = 'no') 'ftuples'
call write_separator ()
flst_title = '(A' // flst_title_format(reg_data%nlegs_born) // ')'
write (u, char (flst_title), advance = 'no') 'flst_born'
call write_separator ()
write (u, '(A7)') 'i_uborn'
do j = 1, reg_data%n_regions
    region = reg_data%regions(j)
    nreal = size (region%flst_real%flst)
    nborn = size (region%flst_uborn%flst)
    write (u, '(I3)', advance = 'no') j
    call write_separator ()
    write (u, '(A1)', advance = 'no') '['
    do i = 1, nreal-1
        write (u, flst_format, advance = 'no') region%flst_real%flst(i), ', '
    end do
    write (u, flst_format, advance = 'no') region%flst_real%flst(nreal), ']'
    call write_separator ()
    write (u, '(I3)', advance = 'no') region%emitter
    call write_separator ()
    write (u, '(I3)', advance = 'no') region%mult
    call write_separator ()
    write (u, '(I4)', advance = 'no') region%nregions
    call write_separator ()
    !!! write ftuples
    nreg = region%nregions
    if (nreg == maxnregions) then
        nleft = 0
        nright = 0
    else
        nreg_diff = maxnregions - nreg
        nleft = nreg_diff/2

```

```

        if (mod(nreg_diff,2) == 0) then
            nright = nleft
        else
            nright = nleft + 1
        end if
    end if
    if (nleft > 0) then
        do i=1,nleft
            write(u,ireg_space_format, advance='no') ' '
        end do
    end if
    write (u,'(A1)', advance = 'no') '{'
    if (nreg > 1) then
        do i=1,nreg-1
            call region%flst_allreg(i)%get (i1, i2)
            write(u,ireg_format,advance = 'no') '(', i1, ',', i2, '), '
        end do
    end if
    call region%flst_allreg(nreg)%get (i1, i2)
    write (u,ireg_format,advance = 'no') '(', i1, ',', i2, ')}'
    if (nright > 0) then
        do i=1,nright
            write(u,ireg_space_format, advance='no') ' '
        end do
    end if
    call write_separator ()
    write (u,'(A1)',advance = 'no') '['
    do i=1,nborn-1
        write(u,flst_format,advance = 'no') region%flst_uborn%flst(i), ', '
    end do
    write (u,flst_format, advance = 'no') region%flst_uborn%flst(nborn), ']'
    call write_separator ()
    write (u, '(I7)', advance = 'no') region%uborn_index
    write(u,*) ''
end do
contains
function flst_title_format (n) result (frmt)
    integer, intent(in) :: n
    type(string_t) :: frmt
    character(len=2) :: frmt_char
    write (frmt_char, '(I2)') 4*n+1
    frmt = var_str (frmt_char)
end function flst_title_format

function ftuple_title_format () result (frmt)
    type(string_t) :: frmt
    character(len=2) :: frmt_char
    write (frmt_char, '(I2)') 10*maxnregions+1
    frmt = var_str (frmt_char)
end function ftuple_title_format

subroutine write_separator ()
    character(len=10) :: sep_format = "(1X,A2,1X)"
    write (u, sep_format, advance = 'no') '||'
end subroutine

```

```

end subroutine write_separator

end subroutine region_data_write

```

Returns the index of the real flavor structure an ftuple belongs to.

```

<fks regions: procedures>+≡
function region_to_index (list, i) result(index)
  type(ftuple_list_t), intent(inout), dimension(:), allocatable :: list
  integer, intent(in) :: i
  integer :: index
  integer :: nlist
  integer :: j
  integer, dimension(:), allocatable :: nreg
  nlist = size(list)
  allocate (nreg (nlist))
  do j = 1, nlist
    if (j == 1) then
      nreg(j) = list(j)%get_n_tuples ()
    else
      nreg(j) = nreg(j-1) + list(j)%get_n_tuples ()
    end if
  end do
  do j = 1, nlist
    if (j == 1) then
      if (i <= nreg(j)) then
        index = j
        exit
      end if
    else
      if (i > nreg(j-1) .and. i <= nreg(j)) then
        index = j
        exit
      end if
    end if
  end do
end function region_to_index

```

Final state emission: Rearrange the flavor array in such a way that the emitted particle is last and the emitter is second last. *i1* is the index of the emitter, *i2* is the index of the emitted particle. Initial state emission: Just put the emitted particle to the last position.

```

<fks regions: procedures>+≡
function create_alr (flv1,i_em,i_rad) result(flv2)
  type(flv_structure_t), intent(in) :: flv1
  integer, intent(in) :: i_em, i_rad
  type(flv_structure_t) :: flv2
  integer :: n
  n = size (flv1%flst)
  allocate (flv2%flst (n))
  if (i_em > 2) then
    flv2%flst(1:2) = flv1%flst(1:2)
    flv2%flst(n-1) = flv1%flst(i_em)
    flv2%flst(n) = flv1%flst(i_rad)
  end if
end function create_alr

```

```

        call fill_remaining_flavors (.true.)
    else
        flv2%flst(1:2) = flv1%flst(1:2)
        flv2%flst(n) = flv1%flst(i_rad)
        call fill_remaining_flavors (.false.)
    end if
contains

```

Order remaining particles according to their original position

```

(fks regions: procedures)+≡
    subroutine fill_remaining_flavors (final_final)
        logical, intent(in) :: final_final
        integer :: i, j
        logical :: check
        j = 3
        do i = 3, n
            if (final_final) then
                check = (i /= i_em .and. i /= i_rad)
            else
                check = (i /= i_rad)
            end if
            if (check) then
                flv2%flst(j) = flv1%flst(i)
                j = j+1
            end if
        end do
    end subroutine fill_remaining_flavors
end function create_alr

```

Explain

```

(fks regions: procedures)+≡
    subroutine fks_permute_born (flv_in, flv_out, perm_list)
        type(flv_structure_t), intent(in) :: flv_in
        type(flv_structure_t), intent(inout) :: flv_out
        integer, intent(out), dimension(:, :), allocatable :: perm_list
        integer, dimension(:, :), allocatable :: perm_list_tmp
        integer :: n_perms, n_perms_max
        integer :: nlegs
        integer :: flv1, flv2, tmp
        integer :: i, j, j_min
        n_perms_max = 100
        !!! actually (n-1)!, but there seems to be no intrinsic function
        !!! of this type in fortran
        if (allocated (perm_list_tmp)) deallocate (perm_list_tmp)
        allocate (perm_list_tmp (n_perms_max, 2))
        n_perms = 0
        j_min = 3
        nlegs = size (flv_in%flst)
        do i = 3, nlegs
            flv1 = flv_in%flst(i)
            do j = j_min, nlegs
                flv2 = flv_out%flst(j)
                if (flv1 == flv2 .and. i /= j) then
                    n_perms = n_perms + 1

```

```

        tmp = flv_out%flst(i)
        flv_out%flst(i) = flv2
        flv_out%flst(j) = tmp
        perm_list_tmp (n_perms, 1) = j
        perm_list_tmp (n_perms, 2) = i
        j_min = j_min + 1
        exit
    end if
end do
end do
allocate (perm_list (n_perms, 2))
perm_list (1:n_perms, :) = perm_list_tmp (1:n_perms, :)
end subroutine fks_permute_born

```

Explain

```

<fks regions: procedures>+=
subroutine fks_apply_perm (flv, emitter, perm_list)
    type(flv_structure_t), intent(inout) :: flv
    integer, intent(inout) :: emitter
    integer, intent(in), dimension(:, :), allocatable :: perm_list
    integer :: i
    integer :: i1, i2
    integer :: tmp
    do i = 1, size (perm_list (:,1))
        i1 = perm_list (i,1)
        i2 = perm_list (i,2)
        tmp = flv%flst (i1)
        flv%flst (i1) = flv%flst (i2)
        flv%flst (i2) = tmp
        if (i1 == emitter) emitter = i2
    end do
end subroutine fks_apply_perm

```

Translates the tree code of the emitter branch into the position of the emitter in the flavor structure array.

```

<fks regions: public>+=
public :: fks_tree_to_position

<fks regions: procedures>+=
function fks_tree_to_position (k, n_tot) result(pos)
    integer, intent(in) :: k, n_tot
    integer :: pos
    integer :: k_tot
    k_tot = 2**(n_tot - 1)
    !!! Initial-state particles
    if (k == k_tot) then
        pos = 1
    else if (k == k_tot/2) then
        pos = 2
        !!! Final-state particles
    else
        ! pos = 3 + nint(log(k)/log(2))
        pos = 3 + dual_log (k)
    end if
end function fks_tree_to_position

```

```

        end if
contains
    recursive function dual_log (x) result (ld)
        integer, intent(in) :: x
        integer :: ld
        if (x == 1) then
            ld = 0
        else
            ld = 1 + dual_log (x/2)
        end if
    end function dual_log
end function fks_tree_to_position

⟨fks regions: fks mapping: TBP⟩≡
    procedure (fks_mapping_dij), deferred :: dij

⟨fks regions: interfaces⟩+≡
    abstract interface
        function fks_mapping_dij (map, p, i, j) result (d)
            import
            class(fks_mapping_t), intent(in) :: map
            type(vector4_t), intent(in), dimension(:) :: p
            integer, intent(in) :: i, j
            real(default) :: d
        end function fks_mapping_dij
    end interface

⟨fks regions: fks mapping: TBP⟩+≡
    procedure (fks_mapping_compute_sumdij), deferred :: compute_sumdij

⟨fks regions: interfaces⟩+≡
    abstract interface
        function fks_mapping_compute_sumdij (map, sregion, p) result (d)
            import
            class(fks_mapping_t), intent(in) :: map
            type(singular_region_t), intent(inout) :: sregion
            type(vector4_t), intent(in), dimension(:) :: p
            real(default) :: d
        end function fks_mapping_compute_sumdij
    end interface

⟨fks regions: fks mapping: TBP⟩+≡
    procedure (fks_mapping_svalue), deferred :: svalue

⟨fks regions: interfaces⟩+≡
    abstract interface
        function fks_mapping_svalue (map, p, i, j) result (value)
            import
            class(fks_mapping_t), intent(in) :: map
            type(vector4_t), intent(in), dimension(:) :: p
            integer, intent(in) :: i, j
            real(default) :: value
        end function fks_mapping_svalue
    end interface

```

```

<fks regions: fks mapping: TBP>+≡
  procedure (fks_mapping_dij_soft), deferred :: dij_soft

<fks regions: interfaces>+≡
  abstract interface
    function fks_mapping_dij_soft (map, p_born, p_soft, em) result (d)
      import
      class(fks_mapping_t), intent(in) :: map
      type(vector4_t), intent(in), dimension(:) :: p_born
      type(vector4_t), intent(in) :: p_soft
      integer, intent(in) :: em
      real(default) :: d
    end function fks_mapping_dij_soft
  end interface

<fks regions: fks mapping: TBP>+≡
  procedure (fks_mapping_compute_sumdij_soft), deferred :: compute_sumdij_soft

<fks regions: interfaces>+≡
  abstract interface
    function fks_mapping_compute_sumdij_soft (map, sregion, p_born, p_soft) result (d)
      import
      class(fks_mapping_t), intent(in) :: map
      type(singular_region_t), intent(inout) :: sregion
      type(vector4_t), intent(in), dimension(:) :: p_born
      type(vector4_t), intent(in) :: p_soft
      real(default) :: d
    end function
  end interface

<fks regions: fks mapping: TBP>+≡
  procedure (fks_mapping_svalue_soft), deferred :: svalue_soft

<fks regions: interfaces>+≡
  abstract interface
    function fks_mapping_svalue_soft (map, p_born, p_soft, em) result (value)
      import
      class(fks_mapping_t), intent(in) :: map
      type(vector4_t), intent(in), dimension(:) :: p_born
      type(vector4_t), intent(in) :: p_soft
      integer, intent(in) :: em
      real(default) :: value
    end function fks_mapping_svalue_soft
  end interface

<fks regions: fks mapping 1: TBP>≡
  procedure :: set_parameter => fks_mapping_default_set_parameter

<fks regions: procedures>+≡
  subroutine fks_mapping_default_set_parameter (map, dij_exp1, dij_exp2)
    class(fks_mapping_default_t), intent(inout) :: map
    real(default), intent(in) :: dij_exp1, dij_exp2
    map%exp_1 = dij_exp1
    map%exp_2 = dij_exp2
  end subroutine fks_mapping_default_set_parameter

```

```

<fks regions: fks mapping 1: TBP>+=
  procedure :: dij => fks_mapping_default_dij

<fks regions: procedures>+=
  function fks_mapping_default_dij (map, p, i, j) result (d)
    class(fks_mapping_default_t), intent(in) :: map
    type(vector4_t), intent(in), dimension(:) :: p
    integer, intent(in) :: i, j
    real(default) :: d
    real(default) :: sqrts
    real :: y
    real :: E1, E2

    if (i /= j .and. (i > 2 .or. j > 2)) then
      if (i == 0 .or. j == 0) then
        if (j == 0) then
          E1 = energy (p(i))
          y = polar_angle_ct (p(i))
        else
          E1 = energy (p(j))
          y = polar_angle_ct(p(j))
        end if
        d = (E1**2 * (1-y**2))**map%exp_2
      else
        E1 = energy(p(i))
        E2 = energy(p(j))
        y = enclosed_angle_ct (p(i), p(j))
        sqrts = (p(1)+p(2))**1
        d = (2*p(i)*p(j) * E1*E2 / (E1 + E2)**2)**map%exp_1
      end if
    else if (i == j) then
      call msg_fatal ("Invalid FKS region: Emitter equals FKS parton!")
    else
      !!! case i,j <= 2 not yet implemented
      d = 0
    end if
  end function fks_mapping_default_dij

<fks regions: fks mapping 1: TBP>+=
  procedure :: compute_sumdij => fks_mapping_default_compute_sumdij

<fks regions: procedures>+=
  function fks_mapping_default_compute_sumdij (map, sregion, p) result (d)
    class(fks_mapping_default_t), intent(in) :: map
    type(singular_region_t), intent(inout) :: sregion
    type(vector4_t), intent(in), dimension(:) :: p
    real(default) :: d
    integer :: i, k, l

    associate (ftuples => sregion%flst_allreg)
      d = 0
      do i = 1, sregion%nregions
        call ftuples(i)%get (k, l)
        d = d + 1.0/map%dij (p, k, l)
      end do
    end associate
  end function

```



```

end associate

end function fks_mapping_default_compute_sumdij

<fks regions: fks mapping 1: TBP>+≡
procedure :: svalue => fks_mapping_default_svalue

<fks regions: procedures>+≡
function fks_mapping_default_svalue (map, p, i, j) result (value)
  class(fks_mapping_default_t), intent(in) :: map
  type(vector4_t), intent(in), dimension(:) :: p
  integer, intent(in) :: i, j
  real(default) :: value
  value = 1._default / (map%dij (p, i, j) * map%sumdij)
end function fks_mapping_default_svalue

<fks regions: fks mapping 1: TBP>+≡
procedure :: dij_soft => fks_mapping_default_dij_soft

<fks regions: procedures>+≡
function fks_mapping_default_dij_soft (map, p_born, p_soft, em) result (d)
  class(fks_mapping_default_t), intent(in) :: map
  type(vector4_t), intent(in), dimension(:) :: p_born
  type(vector4_t), intent(in) :: p_soft
  integer, intent(in) :: em
  real(default) :: d
  d = (2*p_born(em)*p_soft / energy(p_born(em)))*map%exp_1
end function fks_mapping_default_dij_soft

<fks regions: fks mapping 1: TBP>+≡
procedure :: compute_sumdij_soft => fks_mapping_default_compute_sumdij_soft

<fks regions: procedures>+≡
function fks_mapping_default_compute_sumdij_soft (map, sregion, p_born, p_soft) result (d)
  class(fks_mapping_default_t), intent(in) :: map
  type(singular_region_t), intent(inout) :: sregion
  type(vector4_t), intent(in), dimension(:) :: p_born
  type(vector4_t), intent(in) :: p_soft
  real(default) :: d
  integer :: i, k, l
  integer :: nlegs
  d = 0
  nlegs = size (sregion%flst_real%flst)
  associate (ftuples => sregion%flst_allreg)
    do i = 1, sregion%nregions
      call ftuples(i)%get (k,l)
      if (l == nlegs) then
        d = d + 1._default/map%dij_soft (p_born, p_soft, k)
      end if
    end do
  end associate
end function fks_mapping_default_compute_sumdij_soft

```

```

⟨fks regions: fks mapping 1: TBP⟩+≡
  procedure :: svalue_soft => fks_mapping_default_svalue_soft

⟨fks regions: procedures⟩+≡
  function fks_mapping_default_svalue_soft (map, p_born, p_soft, em) result (value)
    class(fks_mapping_default_t), intent(in) :: map
    type(vector4_t), intent(in), dimension(:) :: p_born
    type(vector4_t), intent(in) :: p_soft
    integer, intent(in) :: em
    real(default) :: value
    value = 1._default/(map%sumdij_soft*map%dij_soft (p_born, p_soft, em))
  end function fks_mapping_default_svalue_soft

```

25.4 Virtual contribution to the cross section

```

<virtual.f90>≡
  <File header>

  module virtual

    <Use kinds>
    <Use strings>
    use constants, only: pi, twopi
    use diagnostics
    use pdg_arrays
    use model_data
    use physics_defs
    use sm_physics
    use lorentz
    use flavors
    use fks_regions

    <Standard module head>

    <virtual: public>

    <virtual: types>

    contains

    <virtual: procedures>

  end module virtual

<virtual: public>≡
  public :: virtual_t

<virtual: types>≡
  type :: virtual_t
    real(default) :: Q
    real(default), dimension(:,:), allocatable :: I
    real(default) :: vfin
    real(default) :: sqme_cc
    real(default) :: sqme_virt
    real(default), dimension(:,:), allocatable :: gamma_0, gamma_p, c_flv
    real(default) :: ren_scale2, fac_scale
    integer, dimension(:), allocatable :: n_is_neutrinos
    integer :: nlegs, nflv
    logical :: bad_point
    logical :: use_internal_color_correlations
  contains
    <virtual: virtual: TBP>
  end type virtual_t

<virtual: virtual: TBP>≡
  procedure :: init => virtual_init

<virtual: procedures>≡
  subroutine virtual_init (object, flv_born)

```

```

class(virtual_t), intent(inout) :: object
integer, intent(in), dimension(:, :) :: flv_born
integer :: i_flv
object%nlegs = size (flv_born, 1); object%nflv = size (flv_born, 2)
allocate (object%I (object%nlegs, object%nlegs))
allocate (object%gamma_0 (object%nlegs, object%nflv), &
          object%gamma_p (object%nlegs, object%nflv), &
          object%c_flv (object%nlegs, object%nflv))
call object%init_constants (flv_born)
allocate (object%n_is_neutrinos (object%nflv))
object%n_is_neutrinos = 0
do i_flv = 1, object%nflv
  if (is_neutrino (flv_born(1, i_flv))) &
    object%n_is_neutrinos(i_flv) = object%n_is_neutrinos(i_flv) + 1
  if (is_neutrino (flv_born(2, i_flv))) &
    object%n_is_neutrinos(i_flv) = object%n_is_neutrinos(i_flv) + 1
end do
contains
function is_neutrino (flv) result (neutrino)
  integer, intent(in) :: flv
  logical :: neutrino
  neutrino = (abs(flv)==12 .or. abs(flv)==14 .or. abs(flv)==16)
end function is_neutrino
end subroutine virtual_init

```

Write down constant definition somewhere

<virtual: virtual: TBP>+≡

```

procedure :: init_constants => virtual_init_constants

```

<virtual: procedures>+≡

```

subroutine virtual_init_constants (object, flv_born)
  class(virtual_t), intent(inout) :: object
  integer, intent(in), dimension(:, :) :: flv_born
  integer :: i_part, i_flv
  integer, parameter :: nf = 1
  do i_flv = 1, size (flv_born, 2)
    do i_part = 1, size (flv_born, 1)
      if (is_gluon (flv_born(i_part, i_flv))) then
        object%gamma_0(i_part, i_flv) = (11*ca - 2*nf)/6
        object%gamma_p(i_part, i_flv) = (67.0/9 - 2*pi**2/3)*ca - 23.0/18*nf
        object%c_flv(i_part, i_flv) = ca
      else if (is_quark (abs(flv_born(i_part, i_flv)))) then
        object%gamma_0(i_part, i_flv) = 1.5*cf
        object%gamma_p(i_part, i_flv) = (6.5 - 2*pi**2/3)*cf
        object%c_flv(i_part, i_flv) = cf
      else
        object%gamma_0(i_part, i_flv) = 0
        object%gamma_p(i_part, i_flv) = 0
        object%c_flv(i_part, i_flv) = 0
      end if
    end do
  end do
end subroutine virtual_init_constants

```

Set the renormalization scale. If the input is zero, use the center-of-mass energy.

```

<virtual: virtual: TBP>+=
  procedure :: set_ren_scale => virtual_set_ren_scale

<virtual: procedures>+=
  subroutine virtual_set_ren_scale (object, p, ren_scale)
    class(virtual_t), intent(inout) :: object
    type(vector4_t), dimension(:), intent(in) :: p
    real(default), intent(in) :: ren_scale
    if (ren_scale > 0) then
      object%ren_scale2 = ren_scale**2
    else
      object%ren_scale2 = (p(1)+p(2))**2
    end if
  end subroutine virtual_set_ren_scale

```

```

<virtual: virtual: TBP>+=
  procedure :: set_fac_scale => virtual_set_fac_scale

<virtual: procedures>+=
  subroutine virtual_set_fac_scale (object, p, fac_scale)
    class(virtual_t), intent(inout) :: object
    type(vector4_t), dimension(:), intent(in) :: p
    real(default), optional :: fac_scale
    if (present (fac_scale)) then
      object%fac_scale = fac_scale
    else
      object%fac_scale = (p(1)+p(2))**1
    end if
  end subroutine virtual_set_fac_scale

```

The virtual-subtracted matrix element is given by the equation

$$\mathcal{V} = \frac{\alpha_s}{2\pi} \left(\mathcal{Q}\mathcal{B} + \sum \mathcal{I}_{ij} \mathcal{B}_{ij} + \mathcal{V}_{fin} \right), \quad (25.2)$$

where the quantity \mathcal{Q} is given by

$$\begin{aligned} \mathcal{Q} = \sum_{i=3}^n & \left[\gamma'_{fi} - \log \frac{s}{Q^2} \left(\gamma_{fi} - 2C_{fi} \log \frac{2E_i}{\sqrt{s}} \right) \right. \\ & \left. + 2C_{fi} \log^2 \frac{2E_i}{\sqrt{s}} - 2\gamma_{fi} \frac{2E_i}{\sqrt{s}} \right] \\ & - \log \frac{\mu_F^2}{Q^2} (\gamma_{f+} + \gamma_{f-}). \end{aligned} \quad (25.3)$$

Note that the summation only runs over final-state particles. The expressions for \mathcal{I}_{ij} can be found in equations (25.4), (25.5), (25.6), depending on whether the particles involved in the radiation process are massive or massless.

```

<virtual: virtual: TBP>+=
  procedure :: evaluate => virtual_evaluate

```

```

<virtual: procedures>+=
  subroutine virtual_evaluate &
    (object, reg_data, i_flv, alpha_s, p_born, born, b_ij)
    class(virtual_t), intent(inout) :: object
    type(region_data_t), intent(in) :: reg_data
    integer, intent(in) :: i_flv
    real(default), intent(in) :: alpha_s
    type(vector4_t), intent(inout), dimension(:), allocatable :: p_born
    real(default), intent(in) :: born
    real(default), intent(in), dimension(:,:,:), allocatable :: b_ij
    integer :: i, j, alr
    real(default) :: BI
    if (object%bad_point) then
      object%sqme_virt = 0
    else
      BI = 0
      alr = find_first_matching_uborn (reg_data, i_flv)
      associate (flst_born => reg_data%regions(alr)%flst_uborn)
        call object%compute_Q (p_born, i_flv, flst_born%massive)
        do i = 1, object%nlegs
          do j = 1, object%nlegs
            if (i /= j) then
              if (flst_born%colored(i) .and. flst_born%colored(j)) then
                call object%compute_I (p_born, flst_born%massive, i, j)
                BI = BI + b_ij (i,j,reg_data%regions(alr)%uborn_index) * &
                  object%I(i,j)
              end if
            end if
          end do
        end do
      end associate
      if (object%use_internal_color_correlations) BI = BI*born
      !!! A factor of alpha_s/twopi is assumed to be included in vfin
      object%sqme_virt = alpha_s/twopi * (object%Q*born + BI) + object%vfin
      if (object%n_is_neutrinos(i_flv) > 0) &
        object%sqme_virt = object%sqme_virt * object%n_is_neutrinos(i_flv)*2
    end if
  contains
    function find_first_matching_uborn (reg_data, i_proc) result (alr_out)
      type(region_data_t), intent(in) :: reg_data
      integer, intent(in) :: i_proc
      integer :: alr_out
      integer :: k
      alr_out = 0
      do k = 1, reg_data%n_regions
        alr_out = alr_out+1
        if (reg_data%regions(k)%uborn_index == i_proc) exit
      end do
    end function find_first_matching_uborn
  end subroutine virtual_evaluate

<virtual: virtual: TBP>+=
  procedure :: compute_vfin_test => virtual_compute_vfin_test

```

```

<virtual: procedures>+=
  subroutine virtual_compute_vfin_test (object, p_born, sqme_born)
    class(virtual_t), intent(inout) :: object
    type(vector4_t), intent(in), dimension(:) :: p_born
    real(default), intent(in) :: sqme_born
    real(default) :: s
    s = (p_born(1)+p_born(2))**2
    !!! ----NOTE: Test implementation for e+ e- -> u ubar
    object%vfin = sqme_born * cf * &
      (pi**2 - 8 + 3*log(s/object%ren_scale2) - log(s/object%ren_scale2)**2)
    object%bad_point = .false.
  end subroutine virtual_compute_vfin_test

```

```

<virtual: virtual: TBP>+=
  procedure :: set_vfin => virtual_set_vfin

```

```

<virtual: procedures>+=
  subroutine virtual_set_vfin (object, vfin)
    class(virtual_t), intent(inout) :: object
    real(default) :: vfin
    object%vfin = vfin
  end subroutine virtual_set_vfin

```

```

<virtual: virtual: TBP>+=
  procedure :: set_bad_point => virtual_set_bad_point

```

```

<virtual: procedures>+=
  subroutine virtual_set_bad_point (object, value)
    class(virtual_t), intent(inout) :: object
    logical, intent(in) :: value
    object%bad_point = value
  end subroutine virtual_set_bad_point

```

Note that this implementation only works for lepton collisions. This implies that both the summand containing $\log(s/q^2)$ and the γ -factors vanish.

```

<virtual: virtual: TBP>+=
  procedure :: compute_Q => virtual_compute_Q

<virtual: procedures>+=
  subroutine virtual_compute_Q (object, p_born, i_flv, massive)
    class(virtual_t), intent(inout) :: object
    type(vector4_t), intent(in), dimension(:), allocatable :: p_born
    integer, intent(in) :: i_flv
    logical, dimension(:), intent(in) :: massive
    real(default) :: sqrts, E
    real(default) :: s1, s2, s3, s4
    integer :: i
    sqrts = sqrt ((p_born(1)+p_born(2))**2)
    object%Q = 0
    do i = 1, 2
      object%Q = object%Q - object%gamma_0(i, i_flv) * 2*log(object%fac_scale/sqrts)
    end do
    do i = 3, object%nlegs
      if (.not. massive (i)) then

```

```

s1 = object%gamma_p(i, i_flg)
E = vector4_get_component (p_born(i), 0)
s2 = log(sqrts**2/object%ren_scale2)* &
      (object%gamma_0(i, i_flg) - 2*object%c_flg(i, i_flg)*log(2*E/sqrts))
s3 = 2*log(2*E/sqrts)**2*object%c_flg(i, i_flg)
s4 = 2*log(2*E/sqrts)*object%gamma_0(i, i_flg)
object%Q = object%Q + s1 - s2 + s3 - s4
else
s1 = log(sqrts**2/object%ren_scale2)
s2 = 0.5*I_m_eps (p_born(i))
object%Q = object%Q - object%c_flg(i, i_flg) * (s1-s2)
end if
end do
end subroutine virtual_compute_Q

```

The following code implements the \mathcal{I}_{ij} -function appearing in eq. blub. They are defined as follows:

Massless-Massless Case

$$\begin{aligned}
\mathcal{I}_{ij} = & \frac{1}{2} \log^2 \frac{s}{Q^2} + \log \frac{s}{Q^2} \log \frac{k_i k_j}{2E_i E_j} - \text{Li}_2 \left(\frac{k_i k_j}{2E_i E_j} \right) \\
& + \frac{1}{2} \log^2 \frac{k_i k_j}{2E_i E_j} - \log \left(1 - \frac{k_i k_j}{2E_i E_j} \right) \log \frac{k_i k_j}{2E_i E_j}.
\end{aligned} \tag{25.4}$$

Massive-Massive Case

$$\mathcal{I}_{ij} = -\frac{1}{2} I_0(k_i, k_j) \log \frac{Q^2}{s} - \frac{1}{2} I_\epsilon(k_i, k_j) \tag{25.5}$$

with

$$I_0(k_i, k_j) = \frac{1}{\beta} \log \frac{1 + \beta}{1 - \beta}, \quad \beta = \sqrt{1 - \frac{k_i^2 k_j^2}{(k_i \cdot k_j)^2}}$$

and a rather involved expression for I_ϵ :

$$\begin{aligned}
I_\epsilon(k_i, k_j) &= (K(z_j) - K(z_i)) \frac{1 - \vec{\beta}_i \cdot \vec{\beta}_j}{\sqrt{a(1-b)}}, \\
\vec{\beta}_i &= \frac{\vec{k}_i}{k_i^0}, \\
a &= \beta_i^2 + \beta_j^2 - 2\vec{\beta}_i \cdot \vec{\beta}_j, \\
x_i &= \frac{\beta_i^2 - \vec{\beta}_i \cdot \vec{\beta}_j}{a}, \\
x_j &= \frac{\beta_j^2 - \vec{\beta}_i \cdot \vec{\beta}_j}{a} = 1 - x_i, \\
b &= \frac{\beta_i^2 \beta_j^2 - (\vec{\beta}_i \cdot \vec{\beta}_j)^2}{a}, \\
c &= \sqrt{\frac{b}{4a}}, \\
z_+ &= \frac{1 + \sqrt{1-b}}{\sqrt{b}}, \\
z_- &= \frac{1 - \sqrt{1-b}}{\sqrt{b}}, \\
z_i &= \frac{\sqrt{x_i^2 + 4c^2} - x_i}{2c}, \\
z_j &= \frac{\sqrt{x_j^2 + 4c^2} + x_j}{2c}, \\
K(z) &= -\frac{1}{2} \log^2 \frac{(z - z_-)(z_+ - z)}{(z_+ + z)(z_- + z)} - 2Li_2 \left(\frac{2z_-(z_+ - z)}{(z_+ - z_-)(z_- + z)} \right) \\
&\quad - 2Li_2 \left(-\frac{2z_+(z_- + z)}{(z_+ - z_-)(z_+ - z)} \right)
\end{aligned}$$

Massive-Massless Case

$$\mathcal{I}_{ij} = \frac{1}{2} \left[\log^2 \frac{Q}{s} - \frac{\pi^2}{6} \right] - \frac{1}{2} I_0(k_i, k_j) \log \frac{Q^2}{s} - \frac{1}{2} I_\epsilon(k_i, k_j) \quad (25.6)$$

with

$$\begin{aligned}
I_0(p, k) &= \log \frac{(\hat{p} \cdot \hat{k})^2}{\hat{k}^2}, \\
I_\epsilon(p, k) &= -2 \left[\frac{1}{4} \log^2 \frac{1-\beta}{1+\beta} + \log \frac{\hat{p} \cdot \hat{k}}{1+\beta} \log \frac{\hat{p} \cdot \hat{k}}{1-\beta} + Li_2 \left(1 - \frac{\hat{p} \cdot \hat{k}}{1+\beta} \right) + Li_2 \left(1 - \frac{\hat{p} \cdot \hat{k}}{1-\beta} \right) \right]
\end{aligned}$$

using

$$\hat{p} = \frac{p}{p^0}, \quad \hat{k} = \frac{k}{k^0}, \quad \beta = \frac{|\vec{k}|}{k_0}.$$

(virtual: virtual: TBP)+=

```
procedure :: compute_I => virtual_compute_I
```

```

<virtual: procedures>+≡
subroutine virtual_compute_I (object, p_born, massive, i, j)
  class(virtual_t), intent(inout) :: object
  type(vector4_t), intent(in), dimension(:) :: p_born
  logical, dimension(:), intent(in) :: massive
  integer, intent(in) :: i, j
  real(default) :: somu2
  somu2 = (p_born(1)+p_born(2))*2/object%ren_scale2
  if (massive(i) .and. massive(j)) then
    object%I(i,j) = compute_Imm (p_born(i), p_born(j), somu2)
  else if (.not.massive(i) .and. massive(j)) then
    object%I(i,j) = compute_I0m (p_born(i), p_born(j), somu2)
  else if (massive(i) .and. .not.massive(j)) then
    object%I(i,j) = compute_I0m (p_born(j), p_born(i), somu2)
  else
    object%I(i,j) = compute_I00 (p_born(i), p_born(j), somu2)
  end if
end subroutine virtual_compute_I

function compute_I00 (pi, pj, somu2) result (I)
  type(vector4_t), intent(in) :: pi, pj
  real(default), intent(in) :: somu2
  real(default) :: I
  real(default) :: Ei, Ej
  real(default) :: pij, Eij
  real(default) :: s1, s2, s3, s4, s5
  real(default) :: arglog
  real(default), parameter :: tiny_value = epsilon(1.0)
  !!! ----NOTE: As above, only lepton collisions. Therefore, the
  !!!           first and second summand are not taken into account.

  s1 = 0; s2 = 0; s3 = 0; s4 = 0; s5 = 0
  Ei = vector4_get_component (pi, 0)
  Ej = vector4_get_component (pj, 0)
  pij = pi*pj; Eij = Ei*Ej
  s1 = 0.5*log(somu2)**2
  s2 = log(somu2)*log(pij/(2*Eij))
  s3 = Li2 (pij / (2*Eij))
  s4 = 0.5*log (pij / (2*Eij))**2
  arglog = 1._default - pij/(2*Eij)
  if (arglog > tiny_value) then
    s5 = log(arglog) * log(pij / (2*Eij))
  else
    s5 = 0
  end if
  I = s1 + s2 - s3 + s4 - s5
end function compute_I00

function compute_I0m (ki, kj, somu2) result (I)
  type(vector4_t), intent(in) :: ki, kj
  real(default), intent(in) :: somu2
  real(default) :: I
  real(default) :: logsomu
  real(default) :: s1, s2, s3

```

```

s1 = 0; s2 = 0; s3 = 0
logsomu = log(somu2)
s1 = 0.5*(0.5*logsomu - pi**2/6)
s2 = 0.5*I_0m_0 (ki, kj)*logsomu
s3 = 0.5*I_0m_eps (ki, kj)
I = s1 + s2 - s3
end function compute_I0m

function compute_Imm (pi, pj, somu2) result (I)
  type(vector4_t), intent(in) :: pi, pj
  real(default), intent(in) :: somu2
  real(default) :: I
  real(default) :: s1, s2
  s1 = 0.5*log(somu2)*I_mm_0(pi, pj)
  s2 = 0.5*I_mm_eps(pi, pj)
  I = s1 - s2
end function compute_Imm

```

```

<virtual: procedures>+=
function I_m_eps (p) result (I)
  type(vector4_t), intent(in) :: p
  real(default) :: I
  real(default) :: beta
  beta = space_part_norm (p)/p%p(0)
  I = 2*log((1+beta)/(1-beta))/beta
end function I_m_eps

```

@For $p^2 = 0$ and $k^2 \neq 0$, this computes the expression

$$I_\epsilon(p, k) = -2 \left[\frac{1}{4} \log^2 \frac{1-\beta}{1+\beta} + \log \frac{\hat{p} \cdot k}{1+\beta} \log \hat{p} \cdot k - \beta + Li_2 \left(1 - \frac{\hat{p} \cdot k}{1+\beta} \right) + Li_2 \left(1 - \frac{\hat{p} \cdot k}{1-\beta} \right) \right],$$

with $\hat{p} = \frac{p}{p^0}$ and $\beta = \frac{|\vec{k}|}{k^0}$.

```

<virtual: procedures>+=
function I_0m_eps (p, k) result (I)
  type(vector4_t), intent(in) :: p, k
  real(default) :: I
  type(vector4_t) :: pp, kp
  real(default) :: beta

  pp = p/energy(p); kp = k/energy(k)

  beta = sqrt (1-kp*kp)
  I = -2*(log((1-beta)/(1+beta))**2/4 + log((pp*kp)/(1+beta))*log((pp*kp)/(1-beta)) &
    + Li2(1-(pp*kp)/(1+beta)) + Li2(1-(pp*kp)/(1-beta)))
end function I_0m_eps

```

@For $p^2 = 0$ and $k^2 \neq 0$, computes the expression

$$I_0(p, k) = \log \frac{(\hat{p} \cdot \hat{k})^2}{\hat{k}^2}$$

```

<virtual: procedures>+=

```

```

function I_0m_0 (p, k) result (I)
  type(vector4_t), intent(in) :: p, k
  real(default) :: I
  type(vector4_t) :: pp, kp

  pp = p/energy(p); kp = k/energy(k)
  I = log((pp*kp)**2/kp**2)
end function I_0m_0

```

For $k_1^2 \neq 0$ and $k_2^2 \neq 0$, computes the expression

$$I_\epsilon(k_1, k_2) = [K(z_2) - K(z_1)] \frac{1 - \vec{\beta}_1 \cdot \vec{\beta}_2}{\sqrt{a(1-b)}},$$

where $\vec{\beta}_i = \frac{\vec{k}_i}{k_i^0}$. Further

$$\begin{aligned}
a &= \beta_1^2 + \beta_2^2 - 2\vec{\beta}_1 \cdot \vec{\beta}_2, \\
b &= \frac{\beta_1^2 \beta_2^2 - (\vec{\beta}_1 \cdot \vec{\beta}_2)^2}{a}, \\
c &= \sqrt{\frac{b}{4a}}, \\
K(z) &= -\frac{1}{2} \log^2 \frac{(z - z_-)(z_+ - z)}{(z_+ + z)(z_- + z)} - 2Li_2 \left(\frac{2z_-(z_+ - z)}{(z_+ - z_-)(z_- + z)} \right) \\
&\quad - 2Li_2 \left(-\frac{2z_+(z_- + z)}{(z_+ - z_-)(z_+ - z)} \right), \\
z_+ &= \frac{1 + \sqrt{1-b}}{\sqrt{b}}, \\
z_- &= \frac{1 - \sqrt{1-b}}{\sqrt{b}}, \\
x_1 &= \frac{\beta_1^2 - \vec{\beta}_1 \cdot \vec{\beta}_2}{a}, \\
x_2 &= 1 - x_1 z_1 \\
z_2 &= \frac{\sqrt{x_2^2 + 4c^2} + x_2}{2c}.
\end{aligned}$$

$$= \frac{\sqrt{x_1^2 + 4c^2} - x_1}{2c},$$

(virtual: procedures) +=

```

function I_mm_eps (p1, p2) result (I)
  type(vector4_t), intent(in) :: p1, p2
  real(default) :: I
  type(vector3_t) :: beta1, beta2
  real(default) :: a, b
  real(default) :: zp, zm, z1, z2, x1, x2
  real(default) :: zmb, z1b
  real(default) :: K1, K2

  beta1 = space_part (p1)/energy(p1)
  beta2 = space_part (p2)/energy(p2)

```

```

a = beta1**2 + beta2**2 - 2*beta1*beta2
b = beta1**2*beta2**2 - (beta1*beta2)**2
x1 = beta1**2 - beta1*beta2
x2 = beta2**2 - beta1*beta2
zp = sqrt(a) + sqrt(a-b)
zm = sqrt(a) - sqrt(a-b)
zmb = 1/zp
z1 = sqrt(x1**2+b) - x1
z2 = sqrt(x2**2+b) + x2
z1b = 1/(sqrt(x1**2+b)+x1)
K1 = -0.5*log(((z1b-zmb)*(zp-z1))/((zp+z1)*(z1b+zmb))))**2 &
      -2*Li2((2*zmb*(zp-z1))/((zp-zm)*(zmb+z1b)))) &
      -2*Li2((-2*zp*(zm+z1))/((zp-zm)*(zp-z1)))
K2 = -0.5*log(((z2-zm)*(zp-z2))/((zp+z2)*(z2+zm))))**2 &
      -2*Li2((2*zmb*(zp-z2))/((zp-zm)*(zm+z2)))) &
      -2*Li2((-2*zp*(zm+z2))/((zp-zm)*(zp-z2)))
I = (K2 - K1) * (1-beta1*beta2)/sqrt(a-b)
end function I_mm_eps

```

@For $k_1^2 \neq 0$ and $k_2^2 \neq 0$,computes the expression

$$I_0(k_1, k_2) = \frac{1}{\beta} \log \frac{1+\beta}{1-\beta}, \quad \beta = \sqrt{1 - \frac{k_1^2 k_2^2}{(k_1 \cdot k_2)^2}}$$

(virtual: procedures)+≡

```

function I_mm_0 (k1, k2) result (I)
  type(vector4_t), intent(in) :: k1, k2
  real(default) :: I
  real(default) :: beta
  beta = sqrt (1-k1**2*k2**2/(k1*k2)**2)
  I = log((1+beta)/(1-beta))/beta
end function I_mm_0

```

25.5 Real Subtraction

```

⟨real_subtraction.f90⟩≡
  ⟨File header⟩

  module real_subtraction

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use io_units, only: given_output_unit
    use constants
    use unit_tests
    use diagnostics
    use pdg_arrays
    use model_data
    use physics_defs
    use sm_physics
    use lorentz
    use flavors
    use fks_regions
    use nlo_data

    ⟨Standard module head⟩

    ⟨real subtraction: public⟩

    ⟨real subtraction: types⟩

    contains

    ⟨real subtraction: procedures⟩

  end module real_subtraction

```

Soft subtraction terms

In the soft limit, the real matrix element behaves as

$$\mathcal{R}_{\text{soft}} = 4\pi\alpha_s \left[\sum_{i \neq j} \mathcal{B}_{ij} \frac{k_i \cdot k_j}{(k_i \cdot k)(k_j \cdot k)} - \mathcal{B} \sum_i \frac{k_i^2}{(k_i \cdot k)^2} C_i \right],$$

where k denotes the momentum of the emitted parton. The quantity \mathcal{B}_{ij} is called the color-correlated Born matrix element defined as

$$\mathcal{B}_{ij} = \frac{1}{2s} \sum_{\substack{\text{colors} \\ \text{spins}}} \mathcal{M}_{\{c_k\}} \left(\mathcal{M}_{\{c_k\}}^\dagger \right)_{\substack{c_i \rightarrow c'_i \\ c_j \rightarrow c'_j}} T_{c_i, c'_i}^a T_{c_j, c'_j}^a.$$

```

⟨real subtraction: types⟩≡
  type :: soft_subtraction_t
    real(default), dimension(:), allocatable :: value
    type(region_data_t) :: reg_data
    integer :: nlegs_born, nlegs_real

```

```

    real(default), dimension(:,:), allocatable :: momentum_matrix
    logical :: use_internal_color_correlations = .true.
    logical :: use_internal_spin_correlations = .false.
contains
<real subtraction: soft sub: TBP>
end type soft_subtraction_t

<real subtraction: soft sub: TBP>≡
    procedure :: init => soft_subtraction_init

<real subtraction: procedures>≡
    subroutine soft_subtraction_init (sub_soft, reg_data, nlegs_born, &
                                     nlegs_real)
        class(soft_subtraction_t), intent(inout) :: sub_soft
        type(region_data_t), intent(in) :: reg_data
        integer, intent(in) :: nlegs_born, nlegs_real
        sub_soft%reg_data = reg_data
        sub_soft%nlegs_born = nlegs_born
        sub_soft%nlegs_real = nlegs_real
        allocate (sub_soft%value (reg_data%n_regions))
        allocate (sub_soft%momentum_matrix &
                 (nlegs_born, nlegs_born))
    end subroutine soft_subtraction_init

```

The treatment of the momentum k follows the discussion about the soft limit of the partition functions (ref????). The parton momentum is pulled out, $k = E\hat{k}$. In fact, we will substitute \hat{k} for k throughout the code, because the energy will factor out of the equation when the soft \mathcal{S} -function is multiplied. The soft momentum is a unit vector, because $k^2 = (k^0)^2 - (\hat{k})^2 = 0$.

```

<real subtraction: procedures>+≡
    function create_softvec_fsr (p_born, y, phi, emitter) result (p_soft)
        type(vector4_t), intent(in), dimension(:) :: p_born
        real(default), intent(in) :: y, phi
        integer, intent(in) :: emitter
        type(vector4_t) :: p_soft
        type(vector3_t) :: dir
        type(lorentz_transformation_t) :: rot

```

The soft momentum is constructed by first creating a unit vector parallel to the emitter's Born momentum. This unit vector is then rotated about the corresponding angles y and ϕ .

```

<real subtraction: procedures>+≡
    p_soft%p(0) = 1._default
    p_soft%p(1:3) = p_born(emitter)%p(1:3) / space_part_norm (p_born(emitter))
    dir = create_orthogonal (space_part (p_born(emitter)))
    rot = rotation (y, sqrt(1-y**2), dir)
    p_soft = rot*p_soft
    if (.not. vanishes (phi)) then
        dir = space_part (p_born(emitter)) / &
              space_part_norm (p_born(emitter))
        rot = rotation (cos(phi), sin(phi), dir)
        p_soft = rot*p_soft
    end if

```

```
end function create_softvec_fsr
```

For initial-state emissions, the soft vector is just a unit vector with the same direction as the radiated particle.

```
(real subtraction: procedures)+≡
function create_softvec_isr (y, phi) result (p_soft)
  real(default), intent(in) :: y, phi
  type(vector4_t) :: p_soft
  real(default) :: sin_theta
  sin_theta = sqrt(1-y**2)
  p_soft%p(0) = 1._default
  p_soft%p(1) = sin_theta * sin(phi)
  p_soft%p(2) = sin_theta * cos(phi)
  p_soft%p(3) = y
end function create_softvec_isr
```

Computation of $\mathcal{R}_{\text{soft}}$:

```
(real subtraction: soft sub: TBP)+≡
procedure :: compute => soft_subtraction_compute

(real subtraction: procedures)+≡
subroutine soft_subtraction_compute (sub_soft, p_born, &
  born_ij, y, y_soft, phi, alpha_s_born, alr, emitter)
  class(soft_subtraction_t), intent(inout) :: sub_soft
  type(vector4_t), intent(in), dimension(:) :: p_born
  real(default), intent(in), dimension(:, :) :: born_ij
  real(default), intent(in) :: y, y_soft, phi
  real(default), intent(in) :: alpha_s_born
  integer, intent(in) :: alr, emitter
  type(vector4_t) :: p_soft
  real(default) :: s_alpha_soft
  real(default) :: q02
  real(default) :: kb
  integer :: i, j

  if (emitter > 2) then
    p_soft = create_softvec_fsr (p_born, y_soft, phi, emitter)
  else
    p_soft = create_softvec_isr (y_soft, phi)
  end if
  s_alpha_soft = sub_soft%reg_data%get_svalue_soft &
    (p_born, p_soft, alr, emitter)
  call sub_soft%compute_momentum_matrix (p_born, p_soft)
  sub_soft%value(alr) = 4*pi*alpha_s_born * s_alpha_soft
  kb = 0._default
  do i = 1, size (p_born)
    do j = 1, size (p_born)
      kb = kb + sub_soft%momentum_matrix (i,j) * &
        born_ij (i,j)
    end do
  end do
  sub_soft%value(alr) = sub_soft%value(alr)*kb
  q02 = 4* vector4_get_component (p_born(1), 0) * &
```



```

        vector4_get_component (p_born(2), 0)
        sub_soft%value(alr) = 4/q02 * (1-y) * sub_soft%value(alr)
    end subroutine soft_subtraction_compute

```

We have to multiply this with $\xi^2(1-y)$. Further, when applying the soft \mathcal{S} -function, the energy of the radiated particle is factored out. Thus we have $\xi^2/E_{em}^2(1-y) = 4/q_0^2(1-y)$.

(nlo controller: soft subtraction computation)≡

Computes the quantity $\mathcal{K}_{ij} = \frac{k_i \cdot k_j}{(k_i \cdot k)(k_j \cdot k)}$.

(real subtraction: soft sub: TBP)+≡

```

    procedure :: compute_momentum_matrix => &
        soft_subtraction_compute_momentum_matrix

```

(real subtraction: procedures)+≡

```

    subroutine soft_subtraction_compute_momentum_matrix &
        (sub_soft, p_born, p_soft)
    class(soft_subtraction_t), intent(inout) :: sub_soft
    type(vector4_t), intent(in), dimension(:) :: p_born
    type(vector4_t), intent(in) :: p_soft
    real(default) :: num, deno1, deno2
    integer :: i, j
    do i = 1, sub_soft%nlegs_born
        do j = 1, sub_soft%nlegs_born
            if (i <= j) then
                num = p_born(i) * p_born(j)
                deno1 = p_born(i)*p_soft
                deno2 = p_born(j)*p_soft
                sub_soft%momentum_matrix(i,j) = num/(deno1*deno2)
            else
                !!! momentum matrix is symmetric.
                sub_soft%momentum_matrix(i,j) = sub_soft%momentum_matrix(j,i)
            end if
        end do
    end do
end subroutine soft_subtraction_compute_momentum_matrix

```

25.5.1 Collinear and soft-collinear subtraction terms

This data type deals with the calculation of the collinear and soft-collinear contribution to the cross section.

(real subtraction: types)+≡

```

    type :: coll_subtraction_t
        real(default), dimension(:), allocatable :: value
        real(default), dimension(:), allocatable :: value_soft
        integer :: n_alr
        real(default), dimension(0:3,0:3) :: b_munu
        real(default), dimension(0:3,0:3) :: k_perp_matrix
    contains
        (real subtraction: coll sub: TBP)
    end type coll_subtraction_t

```

```

⟨real subtraction: coll sub: TBP⟩≡
  procedure :: init => coll_subtraction_init

⟨real subtraction: procedures⟩+≡
  subroutine coll_subtraction_init (coll_sub, n_alr)
    class(coll_subtraction_t), intent(inout) :: coll_sub
    integer, intent(in) :: n_alr
    coll_sub%n_alr = n_alr
    allocate (coll_sub%value (n_alr))
    allocate (coll_sub%value_soft (n_alr))
  end subroutine coll_subtraction_init

```

To compute the collinear limit of \mathcal{R} , we follow the original FKS-paper. Here, the real amplitude is supposed to factorize in the collinear limit. considering a splitting $g \rightarrow g(i)g(j)$,

$$\mathcal{A}^{(n)}(h_i, h_j, \{h_l\}) \xrightarrow{i||j} g_s \sum_{d_e} \sum_{h_e} C(d_e, b, c) S_{gg}^{h_e h_i h_j}(z) \mathcal{A}_{d_e}^{(n-1)}(h_e, \{h_l\})$$

Explain quantities. Evaluating this expression leads to

$$|\mathcal{A}^{(n)}(h_i, h_j, \{h_l\})|^2 \xrightarrow{i||j} |\mathcal{N}^{(n)}(h_i, h_j, \{h_l\})|^2 + \mathcal{R}(h_i, h_j, \{h_l\})^2,$$

where \mathcal{R} contains all contributions with spin-correlated amplitudes, i.e. terms like $\mathcal{A}_{d_e}^{(n-1)}(+, \{h_l\}) \left(\mathcal{A}_{d_e}^{(n-1)}(-, \{h_l\}) \right)^*$. Explicitly,

$$\sum_{h_i, h_j, \{h_l\}} \sum_{\{d_l\}} |\mathcal{N}^{(n)}(h_i, h_j, \{h_l\})|^2 = \frac{4\pi\alpha_s}{k_i \cdot k_j} P_{gg}(z) |\mathcal{A}^{(n-1)}|^2,$$

and

$$\begin{aligned} \sum_{h_i, h_j, \{h_l\}} \sum_{\{d_l\}} \mathcal{R}(h_i, h_j, \{h_l\}) &= 32\pi\alpha_s C_A z(1-z) \\ &\times \underbrace{Re \left\{ \frac{\langle ij \rangle}{[ij]} \sum_{\{h_l\}} \sum_{d_e, \{d_l\}} \mathcal{A}_{d_e}^{(n-1)}(+, \{h_l\}) \left(\mathcal{A}_{d_e}^{(n-1)}(-, \{h_l\}) \right)^* \right\}}_{-\tilde{\mathcal{M}}^{(n-1)}/(2k_i \cdot k_j)}. \end{aligned}$$

This yields

$$\mathcal{M}^{(n)} \xrightarrow{i||j} \frac{4\pi\alpha_s}{k_i \cdot k_j} P_{gg}(z) \mathcal{M}^{(n-1)} - \frac{16\pi\alpha_s}{k_i \cdot k_j} C_A z(1-z) \tilde{\mathcal{M}}^{(n-1)}. \quad (25.7)$$

The equivalent expression for a $g \rightarrow qq$ -splitting is given by

$$\mathcal{M}^{(n)} \xrightarrow{i||j} \frac{4\pi\alpha_s}{k_i \cdot k_j} P_{qg}(z) \mathcal{M}^{(n-1)} + \frac{16\pi\alpha_s}{k_i \cdot k_j} T_F z(1-z) \tilde{\mathcal{M}}^{(n-1)}. \quad (25.8)$$

```

⟨real subtraction: coll sub: TBP⟩+≡
  procedure :: compute => coll_subtraction_compute

```

```

<real subtraction: procedures>+≡
subroutine coll_subtraction_compute &
  (coll_sub, sregion, p_born, sqme_born, sqme_born_sc, &
   xi, alpha_s, alr, soft_in)
class(coll_subtraction_t), intent(inout) :: coll_sub
type(singular_region_t), intent(in) :: sregion
type(vector4_t), intent(in), dimension(:) :: p_born
real(default), intent(in) :: sqme_born
real(default), intent(in) :: sqme_born_sc
real(default), intent(in) :: xi, alpha_s
integer, intent(in) :: alr

```

The function obtains a flag to indicate whether the limit to be computed is also soft. Moreover, this consideration explains the structure of the code. In the soft limit, we find $z \rightarrow 0$ as well as $\xi \rightarrow 0$. However, the quantity z/ξ is finite, because

$$\frac{z}{\xi} = \frac{p_{rad}^0}{\bar{p}_{em}^0} \frac{q^0}{2p_{em}^0} = \frac{q^0}{2\bar{p}_{em}^0}.$$

Thus, all expressions are written in terms of this well-behaved quantity. Recalling that there is a prefactor of $(\xi^2 z)^{-1}$, it is necessary to expand with z once.

```

<real subtraction: procedures>+≡
  logical, intent(in), optional :: soft_in
  real(default) :: res
  real(default) :: q0, z, p0
  real(default) :: zoxi, onemz
  real(default) :: pggz, pqgz
  integer :: nlegs, emitter
  integer :: flv_em, flv_rad
  logical :: soft
  if (present (soft_in)) then
    soft = soft_in
  else
    soft = .false.
  end if
  nlegs = size (sregion%flst_real%flst)
  emitter = sregion%emitter
  flv_rad = sregion%flst_real%flst(nlegs)
  flv_em = sregion%flst_real%flst(emitter)
  p0 = vector4_get_component (p_born(emitter),0)
  q0 = vector4_get_component (p_born(1), 0) + &
    vector4_get_component (p_born(2), 0)
  !!! Here, z corresponds to 1-z in the formulas of arXiv:1002.2581;
  !!! the integrand is symmetric under this variable change
  zoxi = q0/(2*p0)
  z = xi*zoxi; onemz = 1-z

  if (sregion%emitter <= 2) then
    !!! Initial-state: No spin-correlations up to now
    if (is_quark(abs (flv_em)) .and. is_gluon(flz_rad)) then
      res = sqme_born*CF*(z+z**3)/onemz/zoxi
    else if (is_gluon(flz_em) .and. is_quark(abs (flz_rad))) then
      res = sqme_born*TR*(z**2+(1-z)**2)*z/zoxi
    end if
  end if

```

```

        end if
    else
        if (is_gluon(flv_em) .and. is_gluon(flv_rad)) then

```

Implementation of equation (25.7). Note that an additional factor z , so that in the last step, the whole expression is divided by z/ξ .

```

<real subtraction: procedures>+=
    pggz = 2*CA*(z**2*onemz + z**2/onemz + onemz)
    res = pggz*sqme_born - 4*CA*z**2*onemz*sqme_born_sc
    res = res/zoxi
    else if (is_quark(abs(flv_em)) .and. is_quark (abs(flv_rad))) then

```

Equation 25.8

```

<real subtraction: procedures>+=
    pqgz = TR*z*(1-2*z*onemz)
    res = pqgz*sqme_born + 4*TR*z**2*onemz*sqme_born_sc
    res = res/zoxi
    else if (is_quark (abs(flv_em)) .and. is_gluon (flv_rad)) then
        res = sqme_born*CF*(1+onemz**2)/zoxi
    else
        call msg_fatal ('Impossible flavor structure in collinear counterterm!')
    end if
end if
res = res /(p0**2*onemz*zoxi)
res = res * 4*pi*alpha_s

if (soft) then
    coll_sub%value_soft (alr) = res
else
    coll_sub%value (alr) = res
end if
end subroutine coll_subtraction_compute

```

Here, $\xi = 0$ is already required.

```

<real subtraction: coll sub: TBP>+=
    procedure :: compute_soft_limit => coll_subtraction_compute_soft_limit

<real subtraction: procedures>+=
    subroutine coll_subtraction_compute_soft_limit &
        (coll_sub, sregion, p_born, sqme_born, &
         sqme_born_sc, xi, alpha_s, alr)
        class(coll_subtraction_t), intent(inout) :: coll_sub
        type(singular_region_t), intent(in) :: sregion
        type(vector4_t), intent(in), dimension(:) :: p_born
        real(default), intent(in) :: sqme_born
        real(default), intent(in) :: sqme_born_sc
        real(default) :: xi, alpha_s
        integer, intent(in) :: alr
        call coll_sub%compute (sregion, p_born, sqme_born, &
                             sqme_born_sc, xi, alpha_s, alr, .true.)
    end subroutine coll_subtraction_compute_soft_limit

```

25.5.2 Real Subtraction

```

<real subtraction: public>≡
  public :: real_subtraction_t

<real subtraction: types>+≡
  type :: real_subtraction_t
    type(region_data_t) :: reg_data
    type(vector4_t), dimension(:), allocatable :: p_born, p_real
    type(real_kinematics_t), pointer :: real_kinematics => null()
    type(isr_kinematics_t), pointer :: isr_kinematics => null()
    integer :: current_alr = 0
    real(default), dimension(:), pointer :: sqme_real_non_sub => null ()
    real(default), dimension(:), pointer :: sqme_born => null ()
    real(default), dimension(:,:,:), pointer :: sqme_born_cc => null ()
    complex(default), dimension(:), pointer :: sqme_born_sc => null()
    type(soft_subtraction_t) :: sub_soft
    type(coll_subtraction_t) :: sub_coll
    logical, dimension(:), allocatable :: sc_required
    logical :: sqme_np1_active = .true.
    logical :: subtraction_active = .true.
  contains
    <real subtraction: real subtraction: TBP>
  end type real_subtraction_t

```

Initializer

```

<real subtraction: real subtraction: TBP>≡
  procedure :: init => real_subtraction_init

<real subtraction: procedures>+≡
  subroutine real_subtraction_init (rsub, reg_data, nlegs_born, &
                                   nlegs_real, sqme_collector)
    class(real_subtraction_t), intent(inout) :: rsub
    type(region_data_t), intent(in) :: reg_data
    integer, intent(in) :: nlegs_born, nlegs_real
    type(sqme_collector_t), intent(in), target :: sqme_collector
    integer :: alr, i_uborn
    rsub%reg_data = reg_data
    allocate (rsub%p_born (nlegs_born), rsub%p_real (nlegs_real))
    rsub%sqme_real_non_sub => sqme_collector%sqme_real_non_sub
    rsub%sqme_born => sqme_collector%sqme_born_list
    rsub%sqme_born_cc => sqme_collector%sqme_born_cc
    rsub%sqme_born_sc => sqme_collector%sqme_born_sc
    allocate (rsub%sc_required (reg_data%n_regions))
    do alr = 1, reg_data%n_regions
      i_uborn = reg_data%regions(alr)%uborn_index
      rsub%sc_required(alr) = &
        reg_data%flv_born(i_uborn)%count_particle (GLUON) > 0
    end do

    call rsub%sub_soft%init (reg_data, nlegs_born, nlegs_real)
    call rsub%sub_coll%init (reg_data%n_regions)
  end subroutine real_subtraction_init

```

```

<real subtraction: real subtraction: TBP>+≡
  procedure :: set_momenta => real_subtraction_set_momenta

<real subtraction: procedures>+≡
  subroutine real_subtraction_set_momenta (rsub, p_born, p_real)
    class(real_subtraction_t), intent(inout) :: rsub
    type(vector4_t), intent(in), dimension(:) :: p_born, p_real
    rsub%p_born = p_born; rsub%p_real = p_real
  end subroutine real_subtraction_set_momenta

<real subtraction: real subtraction: TBP>+≡
  procedure :: set_real_kinematics => real_subtraction_set_real_kinematics

<real subtraction: procedures>+≡
  subroutine real_subtraction_set_real_kinematics (rsub, real_kinematics)
    class(real_subtraction_t), intent(inout) :: rsub
    type(real_kinematics_t), intent(in), target :: real_kinematics
    rsub%real_kinematics => real_kinematics
  end subroutine real_subtraction_set_real_kinematics

<real subtraction: real subtraction: TBP>+≡
  procedure :: set_isr_kinematics => real_subtraction_set_isr_kinematics

<real subtraction: procedures>+≡
  subroutine real_subtraction_set_isr_kinematics (rsub, fractions)
    class(real_subtraction_t), intent(inout) :: rsub
    type(isr_kinematics_t), intent(in), target :: fractions
    rsub%isr_kinematics => fractions
  end subroutine real_subtraction_set_isr_kinematics

<real subtraction: real subtraction: TBP>+≡
  procedure :: set_alr => real_subtraction_set_alr

<real subtraction: procedures>+≡
  subroutine real_subtraction_set_alr (rsub, alr)
    class(real_subtraction_t), intent(inout) :: rsub
    integer, intent(in) :: alr
    rsub%current_alr = alr
  end subroutine real_subtraction_set_alr

```

@

25.5.3 The real contribution to the cross section

In each singular region α , the real contribution to σ is given by the second summand of eqn. ??,

$$\sigma_{\text{real}}^{\alpha} = \int d\Phi_n \int_0^{2\pi} d\phi \int_{-1}^1 dy \int_0^{\xi_{\max}} d\xi \left(\frac{1}{\xi} \right)_+ \left(\frac{1}{1-y} \right)_+ \underbrace{\frac{J(\Phi_n, \xi, y, \phi)}{\xi} [(1-y)\xi^2 \mathcal{R}^{\alpha}(\Phi_{n+1})]}_{g^{\alpha}(\xi, y)} \quad (25.9)$$

Writing out the plus-distribution and introducing $\tilde{\xi} = \xi/\xi_{\max}$ to set the upper integration limit to 1, this turns out to be equal to

$$\sigma_{\text{real}}^{\alpha} = \int d\Phi_n \int_0^{2/\pi} d\phi \int_{-1}^1 \frac{dy}{1-y} \left\{ \int_0^1 d\tilde{\xi} \left[\frac{g^{\alpha}(\tilde{\xi}\xi_{\max}, y)}{\tilde{\xi}} - \underbrace{\frac{g^{\alpha}(0, y)}{\tilde{\xi}}}_{\text{soft}} - \underbrace{\frac{g^{\alpha}(\tilde{\xi}\xi_{\max}, 1)}{\tilde{\xi}}}_{\text{coll.}} + \underbrace{\frac{g^{\alpha}(0, 1)}{\tilde{\xi}}}_{\text{coll.+soft}} \right] \right. \\ \left. + [\log \xi_{\max}(y)g^{\alpha}(0, y) - \log \xi_{\max}(1)g^{\alpha}(0, 1)] \right\}. \quad (25.10)$$

This formula is implemented in `compute_sqme_real_fin`

```
<real subtraction: real subtraction: TBP>+≡
  procedure :: compute => real_subtraction_compute

<real subtraction: procedures>+≡
  function real_subtraction_compute (rsub, emitter, alpha_s) result (sqme)
    class(real_subtraction_t), intent(inout) :: rsub
    integer, intent(in) :: emitter
    real(default) :: alpha_s
    real(default) :: sqme
    integer :: alr

    sqme = 0._default
    !!! Loop over all singular regions
    do alr = 1, size (rsub%reg_data%regions)
      if (emitter == rsub%reg_data%regions(alr)%emitter) then
        call rsub%set_alr (alr)
        sqme = sqme + rsub%evaluate_region (emitter, alpha_s)
      end if
    end do
    if (rsub%subtraction_active) sqme = sqme*rsub%get_phs_factor ()
  end function real_subtraction_compute
```

This subroutine computes the finite part of the real matrix element in an individual singular region. First, the radiation variables are fetched and \mathcal{R} is multiplied by the appropriate S_{α} -factors, region multiplicities and double-FSR factors. Then, it computes the soft, collinear, soft-collinear and remnant matrix elements and supplies the corresponding factor $1/\xi/(1-y)$ as well as the corresponding jacobians.

```
<real subtraction: real subtraction: TBP>+≡
  procedure :: evaluate_region => real_subtraction_evaluate_region

<real subtraction: procedures>+≡
  function real_subtraction_evaluate_region (rsub, emitter, &
                                            alpha_s) result (sqme)

    class(real_subtraction_t), intent(inout) :: rsub
    integer, intent(in) :: emitter
    real(default), intent(in) :: alpha_s
    real(default) :: sqme
    integer :: i_real
    real(default) :: sqme0, sqme_soft, sqme_coll, sqme_cs, sqme_remn
    real(default) :: s_alpha
```

```

real(default) :: xi, xi_max, xi_tilde, y, phi
real(default) :: s
xi_tilde = rsub%real_kinematics%xi_tilde
xi_max = rsub%real_kinematics%xi_max(emitter)
xi = xi_tilde * xi_max
y = rsub%real_kinematics%y(emitter)
phi = rsub%real_kinematics%phi
associate (region => rsub%reg_data%regions(rsub%current_alr))
  i_real = region%real_index
  sqme0 = rsub%sqme_real_non_sub (i_real)
  s_alpha = rsub%reg_data%get_svalue (rsub%p_real, rsub%current_alr, emitter)
  sqme0 = sqme0 * s_alpha
  sqme0 = sqme0 * region%mult
  sqme0 = sqme0 * region%double_fsr_factor (rsub%p_real)
  if (rsub%subtraction_active) then
    sqme0 = sqme0 * xi**2/xi_tilde * rsub%real_kinematics%jac(emitter)%jac(1)
  else
    s = rsub%real_kinematics%cms_energy2
    sqme0 = sqme0*rsub%real_kinematics%jac(emitter)%jac(1)*s/(8*twopi3)*xi
  end if
  if (rsub%subtraction_active) then
    call rsub%evaluate_subtraction_terms (emitter, alpha_s, &
      sqme_soft, sqme_coll, sqme_cs)
    associate (jac => rsub%real_kinematics%jac)
      sqme_soft = sqme_soft/(1-y)/xi_tilde * jac(emitter)%jac(2)
      sqme_coll = sqme_coll/(1-y)/xi_tilde * jac(emitter)%jac(3)
      sqme_cs = sqme_cs/(1-y)/xi_tilde * jac(emitter)%jac(2)
    end associate
    sqme_remn = (sqme_soft - sqme_cs)*log(xi_max)*xi_tilde
    sqme = sqme0 - sqme_soft - sqme_coll + sqme_cs + sqme_remn
    sqme = sqme * rsub%real_kinematics%jac_rand (emitter)
  else
    sqme = sqme0
  end if
end associate
!!! This occurs if the result is NaN.
if (sqme /= sqme) &
  call write_computation_status ()
contains
subroutine write_computation_status (unit)
  integer, intent(in), optional :: unit
  integer :: i_uborn
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  i_uborn = rsub%reg_data%regions(rsub%current_alr)%uborn_index
  write (u,'(A,I2)') 'alr: ', rsub%current_alr
  write (u,'(A,I2)') 'emitter: ', emitter
  write (u,'(A,F4.2)') 'xi_max: ', xi_max
  write (u,'(A,F4.2,A,F4.2)') 'xi: ', xi, 'y: ', y
  print *, 'sqme_born: ', rsub%sqme_born(i_uborn)
  print *, 'sqme_real: ', sqme0
  print *, 'sqme_soft: ', sqme_soft
  print *, 'sqme_coll: ', sqme_coll
  print *, 'sqme_coll-soft: ', sqme_cs

```



```

        print *, 'sqme_remn: ', sqme_remn
    end subroutine write_computation_status

end function real_subtraction_evaluate_region

<real subtraction: real subtraction: TBP>+≡
    procedure :: evaluate_subtraction_terms => &
        real_subtraction_evaluate_subtraction_terms

<real subtraction: procedures>+≡
    subroutine real_subtraction_evaluate_subtraction_terms (rsub, &
        emitter, alpha_s, &
        sqme_soft, sqme_coll, sqme_cs)
        class(real_subtraction_t), intent(inout) :: rsub
        integer, intent(in) :: emitter
        real(default), intent(in) :: alpha_s
        real(default), intent(out) :: sqme_soft, sqme_coll, sqme_cs
        integer :: alr
        real(default) :: xi
        alr = rsub%current_alr
        call rsub%compute_sub_soft (emitter, alpha_s)
        call rsub%compute_sub_coll (emitter, alpha_s)
        call rsub%compute_sub_coll_soft (emitter, alpha_s)
        sqme_soft = rsub%sub_soft%value(alr)
        sqme_coll = rsub%sub_coll%value(alr)
        sqme_cs = rsub%sub_coll%value_soft(alr)
    end subroutine real_subtraction_evaluate_subtraction_terms

<real subtraction: real subtraction: TBP>+≡
    procedure :: get_phs_factor => real_subtraction_get_phs_factor

<real subtraction: procedures>+≡
    function real_subtraction_get_phs_factor (rsub) result (factor)
        class(real_subtraction_t), intent(in) :: rsub
        real(default) :: factor
        real(default) :: s
        s = (rsub%p_born(1)+rsub%p_born(2))*2
        factor = s / (8*twopi3)
    end function real_subtraction_get_phs_factor

```

25.5.4 xxx

```

<real subtraction: real subtraction: TBP>+≡
    procedure :: compute_sub_soft => real_subtraction_compute_sub_soft

<real subtraction: procedures>+≡
    subroutine real_subtraction_compute_sub_soft &
        (rsub, emitter, alpha_s)
        class(real_subtraction_t), intent(inout) :: rsub
        integer, intent(in) :: emitter
        real(default), intent(in) :: alpha_s
        integer :: alr
        alr = rsub%current_alr

```

```

associate (sregion => rsub%reg_data%regions(alr))
  if (sregion%has_soft_divergence ()) then
    call rsub%sub_soft%compute (rsub%p_born, &
                                rsub%sqme_born_cc(:, :, sregion%uborn_index), &
                                rsub%real_kinematics%y(emitter), &
                                rsub%real_kinematics%y_soft(emitter), &
                                rsub%real_kinematics%phi, &
                                alpha_s, alr, emitter)
  else
    rsub%sub_soft%value(alr) = 0._default
  end if
end if
end associate
end subroutine real_subtraction_compute_sub_soft

```

(real subtraction: real subtraction: TBP)+≡

```

procedure :: compute_sub_coll => real_subtraction_compute_sub_coll

```

(real subtraction: procedures)+≡

```

subroutine real_subtraction_compute_sub_coll (rsub, em, alpha_s)
  class(real_subtraction_t), intent(inout) :: rsub
  integer, intent(in) :: em
  real(default), intent(in) :: alpha_s
  real(default) :: xi
  real(default) :: sqme_sc
  complex(default) :: prod1, prod2
  integer :: alr
  alr = rsub%current_alr
  xi = rsub%real_kinematics%xi_tilde * rsub%real_kinematics%xi_max (em)
  associate (sregion => rsub%reg_data%regions(alr))
    if (sregion%has_collinear_divergence ()) then
      if (rsub%sc_required(alr)) then
        call spinor_product (rsub%p_real(em), rsub%p_real(rsub%reg_data%nlegs_real), &
                             prod1, prod2)
        sqme_sc = real (prod1/prod2*rsub%sqme_born_sc(sregion%uborn_index))
      else
        sqme_sc = 0._default
      end if
      call rsub%sub_coll%compute (sregion, rsub%p_born, &
                                  rsub%sqme_born(sregion%uborn_index), &
                                  sqme_sc, xi, alpha_s, alr)
    else
      rsub%sub_coll%value(alr) = 0._default
    end if
  end if
end associate
end subroutine real_subtraction_compute_sub_coll

```

(real subtraction: real subtraction: TBP)+≡

```

procedure :: compute_sub_coll_soft => real_subtraction_compute_sub_coll_soft

```

(real subtraction: procedures)+≡

```

subroutine real_subtraction_compute_sub_coll_soft (rsub, em, alpha_s)
  class(real_subtraction_t), intent(inout) :: rsub
  integer, intent(in) :: em
  real(default), intent(in) :: alpha_s

```

```

complex(default) :: prod1, prod2
real(default) :: sqme_sc
real(default), parameter :: xi = 0
integer :: alr
alr = rsub%current_alr
associate (sregion => rsub%reg_data%regions(alr))
  if (sregion%has_collinear_divergence ()) then
    if (rsub%sc_required(alr)) then
      call spinor_product (rsub%p_real(em), rsub%p_real(rsub%reg_data%nlegs_real), &
                           prod1, prod2)
      sqme_sc = real (prod1/prod2*rsub%sqme_born_sc(sregion%uborn_index))
    else
      sqme_sc = 0._default
    end if
    call rsub%sub_coll%compute_soft_limit (sregion, rsub%p_born, &
                                           rsub%sqme_born(sregion%uborn_index), &
                                           sqme_sc, xi, alpha_s, alr)
  else
    rsub%sub_coll%value_soft(alr) = 0._default
  end if
end associate
end subroutine real_subtraction_compute_sub_coll_soft

```

25.6 Combining the FKS Pieces

```

<nlo_data.f90>≡
  <File header>

  module nlo_data

    <Use kinds>
    <Use strings>
    use io_units
    use lorentz

    <Standard module head>

    <nlo data: public>

    <nlo data: types>

    contains

    <nlo data: procedures>

  end module nlo_data

<nlo data: public>≡
  public :: fks_template_t

<nlo data: types>≡
  type :: fks_template_t
    type(string_t) :: id
    integer :: mapping_type
    logical :: count_kinematics = .false.
    real(default) :: fks_dij_exp1
    real(default) :: fks_dij_exp2
  contains
    <nlo data: fks template: TBP>
  end type fks_template_t

<nlo data: fks template: TBP>≡
  procedure :: write => fks_template_write

<nlo data: procedures>≡
  subroutine fks_template_write (object, unit)
    class(fks_template_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u,'(1x,A)') 'FKS Template: '
    write (u,'(1x,A,I0)') 'Mapping Type: ', object%mapping_type
    write (u,'(1x,A,ES4.3,ES4.3)') 'd_ij exponentials: ', object%fks_dij_exp1, object%fks_dij_exp2
  end subroutine fks_template_write

<nlo data: fks template: TBP>+≡
  procedure :: set_dij_exp => fks_template_set_dij_exp

```

```

<nlo data: procedures>+≡
  subroutine fks_template_set_dij_exp (object, exp1, exp2)
    class(fks_template_t), intent(inout) :: object
    real(default), intent(in) :: exp1, exp2
    object%fks_dij_exp1 = exp1
    object%fks_dij_exp2 = exp2
  end subroutine fks_template_set_dij_exp

<nlo data: fks template: TBP>+≡
  procedure :: set_mapping_type => fks_template_set_mapping_type

<nlo data: procedures>+≡
  subroutine fks_template_set_mapping_type (object, val)
    class(fks_template_t), intent(inout) :: object
    integer, intent(in) :: val
    object%mapping_type = val
  end subroutine fks_template_set_mapping_type

<nlo data: fks template: TBP>+≡
  procedure :: set_counter => fks_template_set_counter

<nlo data: procedures>+≡
  subroutine fks_template_set_counter (object)
    class(fks_template_t), intent(inout) :: object
    object%count_kinematics = .true.
  end subroutine fks_template_set_counter

<nlo data: types>+≡
  type :: real_jacobian_t
    real(default), dimension(3) :: jac = 1._default
  contains
    <nlo data: real jacobian: TBP>
  end type real_jacobian_t

```

Just a container for the real kinematics variables.

```

<nlo data: public>+≡
  public :: real_kinematics_t

<nlo data: types>+≡
  type :: real_kinematics_t
    logical :: supply_xi_max = .true.
    real(default) :: xi_tilde
    real(default) :: phi
    real(default), dimension(:), allocatable :: xi_max, y
    type(real_jacobian_t), dimension(:), allocatable :: jac
    type(vector4_t), dimension(:), allocatable :: p_born
    type(vector4_t), dimension(:), allocatable :: p_real
    real(default), dimension(:), allocatable :: jac_rand
    real(default), dimension(:), allocatable :: y_soft
    real(default) :: cms_energy2
  contains
    <nlo data: real kinematics: TBP>
  end type real_kinematics_t

```

```

<nlo data: real kinematics: TBP>≡
  procedure :: write => real_kinematics_write

<nlo data: procedures>+≡
  subroutine real_kinematics_write (r, unit)
    class(real_kinematics_t), intent(in) :: r
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    write (u,"(A)") "Real kinematics: "
    write (u,"(A,F5.3)") "xi_tilde: ", r%xi_tilde
    write (u,"(A,F5.3)") "phi: ", r%phi
    write (u,"(A,100F5.3,1X)") "xi_max: ", r%xi_max
    write (u,"(A,100F5.3,1X)") "y: ", r%y
    write (u,"(A,100F5.3,1X)") "jac_rand: ", r%jac_rand
    write (u,"(A,100F5.3,1X)") "y_soft: ", r%y_soft
  end subroutine real_kinematics_write

```

Another container for the x_{\oplus} - and x_{\ominus} -values for initial-state phase spaces.

```

<nlo data: public>+≡
  public :: isr_kinematics_t

<nlo data: types>+≡
  type :: isr_kinematics_t
    real(default), dimension(2) :: x = 1._default
    real(default), dimension(2) :: z
    real(default) :: sqrts_born
    real(default) :: beam_energy
    real(default) :: fac_scale
    real(default), dimension(2) :: jacobian = 1._default
  end type isr_kinematics_t

```

```

<nlo_controller.f90>≡
  <File header>

  module nlo_controller

    <Use kinds>
    <Use strings>
    use io_units
    use constants, only: zero, pi, twopi
    use unit_tests
    use diagnostics
    use physics_defs
    use process_constants !NODEP!
    use sm_physics
    use os_interface
    use model_data
    use parser
    use pdg_arrays
    use particle_specifiers
    use phs_single
    use state_matrices
    use interactions

```

```

use lorentz
use prc_core
use pdg_arrays
use sf_base
use colors
use flavors
use fks_regions
use nlo_data
use phs_fks
use virtual
use real_subtraction
use pdf_subtraction

```

<Standard module head>

<nlo controller: public>

<nlo controller: types>

contains

<nlo controller: procedures>

end module nlo_controller

We need to associate singular regions with compatible color flows.

<nlo controller: types>≡

```

type :: ftuple_color_map_t
  integer :: index
  integer :: color_index
  type(ftuple_color_map_t), pointer :: next
  type(ftuple_color_map_t), pointer :: prev
contains
<nlo controller: color map: TBP>
end type ftuple_color_map_t

```

<nlo controller: color map: TBP>≡

```

procedure :: init => ftuple_color_map_init

```

<nlo controller: procedures>≡

```

subroutine ftuple_color_map_init (icm)
  class(ftuple_color_map_t), intent(inout), target :: icm
  icm%index = 0
  icm%color_index = 0
  nullify (icm%next)
  nullify (icm%prev)
end subroutine ftuple_color_map_init

```

Explain

<nlo controller: color map: TBP>+≡

```

procedure :: present => ftuple_color_map_present

```

<nlo controller: procedures>+≡

```

function ftuple_color_map_present (icm, color_index) result(pres)

```

```

class(ftuple_color_map_t), intent(in), target :: icm
integer, intent(in) :: color_index
logical :: pres
type(ftuple_color_map_t), pointer :: current
select type (icm)
type is (ftuple_color_map_t)
current => icm
pres = .false.
do
  if (current%color_index == color_index) then
    pres = .true.
    exit
  else
    if (associated (current%next)) then
      current => current%next
    else
      exit
    end if
  end if
end do
end select
end function ftuple_color_map_present

```

Appends a color flow to the list

<nlo controller: color map: TBP>+≡

```

procedure :: append => ftuple_color_map_append

```

<nlo controller: procedures>+≡

```

subroutine ftuple_color_map_append (icm, val)
class(ftuple_color_map_t), intent(inout), target :: icm
integer, intent(in) :: val
type(ftuple_color_map_t), pointer :: current
select type (icm)
type is (ftuple_color_map_t)
if (.not. icm%present (val)) then
  if (icm%index == 0) then
    nullify(icm%next)
    icm%index = 1
    icm%color_index = val
  else
    current => icm
    do
      if (associated (current%next)) then
        current => current%next
      else
        allocate (current%next)
        nullify (current%next%next)
        current%next%prev => current
        current%next%index = current%index + 1
        current%next%color_index = val
        exit
      end if
    end do
  end if
end select
end if
end subroutine

```



```

        end if
    end select
end subroutine ftuple_color_map_append

```

```

<nlo controller: color map: TBP>+≡
    procedure :: get_n_entries => ftuple_color_map_get_n_entries

<nlo controller: procedures>+≡
    function ftuple_color_map_get_n_entries (icm) result(n_entries)
        class(ftuple_color_map_t), intent(in), target :: icm
        integer :: n_entries
        type(ftuple_color_map_t), pointer :: current
        select type (icm)
        type is (ftuple_color_map_t)
            current => icm
            n_entries = 0
        do
            if (associated (current%next)) then
                current => current%next
            else
                n_entries = current%index
                exit
            end if
        end do
        end select
    end function ftuple_color_map_get_n_entries

```

Explain

```

<nlo controller: color map: TBP>+≡
    procedure :: get_index_array => ftuple_color_map_get_index_array

<nlo controller: procedures>+≡
    function ftuple_color_map_get_index_array (icm) result(iarr)
        class(ftuple_color_map_t), intent(in), target :: icm
        integer, dimension(:), allocatable :: iarr
        type(ftuple_color_map_t), pointer :: current
        integer :: n_entries
        integer :: i
        select type (icm)
        type is (ftuple_color_map_t)
            n_entries = icm%get_n_entries ()
            allocate (iarr(n_entries))
        do i = 1, n_entries
            if (i == 1) then
                current => icm
            else
                current => current%next
            end if
            iarr(i) = current%color_index
        end do
        end select
    end function ftuple_color_map_get_index_array

```

```

<nlo controller: color map: TBP>+=
  procedure :: get_entry => ftuple_color_map_get_entry

<nlo controller: procedures>+=
  function ftuple_color_map_get_entry (icm, index) result(entry)
    class(ftuple_color_map_t), intent(in), target :: icm
    integer, intent(in) :: index
    integer :: entry
    type(ftuple_color_map_t), pointer :: current
    integer :: i
    select type (icm)
    type is (ftuple_color_map_t)
    if (index <= icm%get_n_entries ()) then
      do i = 1, icm%get_n_entries ()
        if (i == 1) then
          current => icm
        else
          current => current%next
        end if
        if (i == index) entry = current%color_index
      end do
    else
      entry = 0
    end if
  end select
end function ftuple_color_map_get_entry

```

Explain

```

<nlo controller: color map: TBP>+=
  procedure :: create_map => ftuple_color_map_create_map

<nlo controller: procedures>+=
  recursive subroutine ftuple_color_map_create_map (icm, flst, &
    emitter, allreg, color_states_born, color_states_real, p_rad_in)
    class(ftuple_color_map_t), intent(inout) :: icm
    type(flv_structure_t), intent(in) :: flst
    integer, intent(in) :: emitter
    type(ftuple_t), intent(in), dimension(:) :: allreg
    integer, intent(in), dimension(:, :, :) :: color_states_born
    integer, intent(in), dimension(:, :, :) :: color_states_real
    integer, intent(in), optional :: p_rad_in
    integer :: nreg, region
    integer :: p1, p2, p_rad
    integer :: flv_em, flv_rad
    integer :: n_col_real, n_col_born
    integer, dimension(2) :: col_em, col_rad
    integer :: i
    !!! splitting type: 1 - q -> qg
    !!!                 2 - g -> qq
    !!!                 3 - g -> gg
    integer :: splitting_type_flv, splitting_type_col
    nreg = size (allreg)
    n_col_real = size (color_states_real (1,1,:))
    n_col_born = size (color_states_born (1,1,:))
    do region = 1, nreg

```

```

call allreg(region)%get (p1, p2)
if (p1 == emitter .or. p2 == emitter .or. present (p_rad_in)) then
  if (.not. present (p_rad_in)) then
    if (p1 == emitter) then
      p_rad = p2
    else
      p_rad = p1
    end if
  else
    p_rad = p_rad_in
  end if
  if (emitter /= 0) then
    flv_em = flst%flst (emitter)
  else
    call icm%create_map &
      (flst, 1, allreg, color_states_born, color_states_real, p_rad)
    call icm%create_map &
      (flst, 2, allreg, color_states_born, color_states_real, p_rad)
    return
  end if
  flv_rad = flst%flst (p_rad)
  if (is_quark (abs(flv_em)) .and. is_gluon (flv_rad)) then
    splitting_type_flv = 1
  else if (is_quark (abs(flv_em)) .and. flv_em + flv_rad == 0) then
    splitting_type_flv = 2
  else if (is_gluon (flv_em) .and. is_gluon (flv_rad)) then
    splitting_type_flv = 3
  else
    splitting_type_flv = 0
  end if
  do i = 1, n_col_real
    col_em = color_states_real(:,emitter,i)
    col_rad = color_states_real(:,p_rad,i)
    if (is_color_singlet (col_em(1), col_em(2)) &
      .and. (is_color_doublet (col_rad(1), col_rad(2)) &
      .or. is_color_ghost (col_rad(1), col_rad(2)))) then
      splitting_type_col = 1
    else if (is_color_singlet (col_em(1), col_em(2)) .and. &
      is_color_singlet (col_rad(1), col_rad(2))) then
      splitting_type_col = 2
    else if (is_color_doublet (col_em(1), col_em(2)) .and. &
      is_color_doublet (col_rad(1), col_rad(2))) then
      splitting_type_col = 3
    else
      splitting_type_col = 0
    end if
    if (splitting_type_flv == splitting_type_col .and. &
      splitting_type_flv /= 0) then
      call icm%append (i)
    end if
  end do
end if
end do
contains

```

```

function is_color_singlet (c1, c2) result (singlet)
  integer, intent(in) :: c1, c2
  logical :: singlet
  singlet = (c1 == 0 .and. c2 /= 0) .or. (c1 /= 0 .and. c2 == 0)
end function is_color_singlet
function is_color_doublet (c1, c2) result (doublet)
  integer, intent(in) :: c1, c2
  logical :: doublet
  doublet = c1 /= 0 .and. c2 /= 0
end function is_color_doublet
function is_color_ghost (c1, c2) result (ghost)
  integer, intent(in) :: c1, c2
  logical :: ghost
  ghost = c1 == 0 .and. c2 == 0
end function is_color_ghost
end subroutine ftuple_color_map_create_map

```

This data type contains color information, necessary for both soft and virtual counterterms.

```

<nlo controller: types>+≡
type color_data_t
  type(ftuple_color_map_t), dimension(:), allocatable :: icm
  integer, dimension(:,:,:), allocatable :: col_state_born, col_state_real
  logical, dimension(:,:), allocatable :: ghost_flag_born, ghost_flag_real
  integer :: n_col_born, n_col_real
  type(color_t), dimension(:,:), allocatable :: color_real, color_born
  integer, dimension(:), allocatable :: col_born
  complex(default), dimension(:), allocatable :: color_factors_born
  integer, dimension(:,:), allocatable :: cf_index_real
  real(default), dimension(:,:,:), allocatable :: beta_ij
  logical :: color_is_conserved
contains
  <nlo controller: color data: TBP>
end type color_data_t

```

```

<nlo controller: color data: TBP>≡
procedure :: init => color_data_init

```

```

<nlo controller: procedures>+≡
subroutine color_data_init (color_data, reg_data, prc_constants)
  class(color_data_t), intent(inout) :: color_data
  type(region_data_t), intent(inout) :: reg_data
  type(process_constants_t), intent(in), dimension(2) :: prc_constants
  integer :: nlegs_born, nlegs_real
  integer :: i, n_in
  nlegs_born = reg_data%nlegs_born
  nlegs_real = reg_data%nlegs_real
  call prc_constants(1)%get_col_state (color_data%col_state_born)
  call prc_constants(2)%get_col_state (color_data%col_state_real)
  call prc_constants(2)%get_cf_index (color_data%cf_index_real)
  call prc_constants(1)%get_color_factors (color_data%color_factors_born)
  color_data%n_col_born = size (color_data%col_state_born(1,1,:))
  color_data%n_col_real = size (color_data%col_state_real(1,1,:))

```

```

color_data%ghost_flag_born = prc_constants(1)%get_ghost_flag ()
color_data%ghost_flag_real = prc_constants(2)%get_ghost_flag ()
allocate (color_data%color_real (nlegs_real, color_data%n_col_real))
allocate (color_data%icm (reg_data%n_regions))
do i = 1, color_data%n_col_real
    call color_init_from_array (color_data%color_real (:,i), &
        color_data%col_state_real (:,:,i), &
        color_data%ghost_flag_real (:,i))
    n_in = prc_constants(1)%n_in
    call color_data%color_real (1:n_in,i)%invert ()
end do
do i = 1, size(reg_data%regions)
    call color_data%icm(i)%init
    associate (region => reg_data%regions(i))
        call color_data%icm(i)%create_map (region%flst_real, region%emitter, &
            region%flst_allreg, color_data%col_state_born, &
            color_data%col_state_real)
    end associate
end do
call color_data%init_betaij (reg_data)
end subroutine color_data_init

```

Allocate and compute β_{ij} :

```

<nlo controller: color data: TBP>+≡
    procedure :: init_betaij => color_data_init_betaij

<nlo controller: procedures>+≡
    subroutine color_data_init_betaij (color_data, reg_data)
        class(color_data_t), intent(inout) :: color_data
        type(region_data_t), intent(inout) :: reg_data
        integer :: i
        allocate (color_data%beta_ij (reg_data%nlegs_born, &
            reg_data%nlegs_born, reg_data%n_flv_born))
        do i = 1, reg_data%n_flv_born
            call color_data%fill_betaij_matrix (reg_data%nlegs_born, i, &
                reg_data%regions(1)%flst_real, reg_data)
        end do
    end subroutine color_data_init_betaij

```

Actual computation of β_{ij} .

```

<nlo controller: color data: TBP>+≡
    procedure :: fill_betaij_matrix => color_data_fill_betaij_matrix

<nlo controller: procedures>+≡
    subroutine color_data_fill_betaij_matrix &
        (color_data, n_legs, uborn_index, flst_real, reg_data)
        class(color_data_t), intent(inout) :: color_data
        integer, intent(in) :: n_legs, uborn_index
        type(flv_structure_t), intent(in) :: flst_real
        type(region_data_t), intent(inout) :: reg_data
        integer :: em1, em2
        associate (flv_born => reg_data%flv_born (uborn_index))
            do em1 = 1, n_legs
                do em2 = 1, n_legs

```

```

if (flv_born%colored(em1) .and. flv_born%colored(em2)) then
  if (em1 < em2) then
    color_data%beta_ij (em1, em2, uborn_index) &
      = color_data%compute_bij &
        (reg_data, uborn_index, flst_real, em1, em2)
  else if (em1 > em2) then
    !!! B_ij is symmetric
    color_data%beta_ij (em1, em2, uborn_index) = &
      color_data%beta_ij (em2, em1, uborn_index)
  else
    if (is_quark (abs (flv_born%flst (em1)))) then
      color_data%beta_ij (em1, em2, uborn_index) = -cf
    else
      color_data%beta_ij (em1, em2, uborn_index) = -ca
    end if
  end if
end if
else
  color_data%beta_ij (em1, em2, uborn_index) = 0.0
end if
end do
end do
end associate
call check_color_conservation (color_data%beta_ij (:,:,uborn_index), &
  n_legs, color_data%color_is_conserved)
contains
subroutine check_color_conservation (bij_matrix, n_legs, success)
  real(default), intent(in), dimension(:,:) :: bij_matrix
  integer, intent(in) :: n_legs
  logical, intent(out) :: success
  logical, dimension(:), allocatable :: check
  integer :: i, j
  real(default) :: bcheck
  real(default), parameter :: tol = 0.0001_default
  allocate (check (n_legs))
  do i = 1, n_legs
    bcheck = 0.0
    do j = 1, n_legs
      if (i /= j) bcheck = bcheck + bij_matrix (i, j)
    end do
    if (is_quark (abs(flst_real%flst (i))) .or. &
      is_gluon (flst_real%flst (i))) then
      if (is_quark (abs(flst_real%flst (i))) .and. &
        (bcheck - cf) < tol) then
        check (i) = .true.
      else if (is_gluon (flst_real%flst (i)) .and. &
        (bcheck - ca) < tol) then
        check (i) = .true.
      else
        check (i) = .false.
      end if
    else
      if (bcheck < tol) then
        check (i) = .true.
      else

```

```

        check (i) = .false.
    end if
end if
end do
if (.not. all (check)) then
    success = .false.
else
    success = .true.
end if
end subroutine check_color_conservation
end subroutine color_data_fill_betaij_matrix

```

Explain

```

<nlo controller: color data: TBP>+≡
    procedure :: compute_bij => color_data_compute_bij

<nlo controller: procedures>+≡
    function color_data_compute_bij &
        (color_data, reg_data, uborn_index, flst_real, em1, em2) result (bij)
        class(color_data_t), intent(inout) :: color_data
        type(region_data_t), intent(inout) :: reg_data
        integer, intent(in) :: uborn_index
        type(flv_structure_t), intent(in) :: flst_real
        integer, intent(in) :: em1, em2
        real(default) :: bij
        logical, dimension(:,:), allocatable :: cf_present
        type(singular_region_t), dimension(2,100) :: reg
        integer :: i, j, k, l
        type(ftuple_color_map_t) :: icm1, icm2
        integer :: i1, i2
        real(default) :: color_factor, color_factor_born
        integer, dimension(2) :: i_reg
        logical , dimension(2) :: found
        integer, dimension(2,100) :: map_em_col_tmp
        integer, dimension(:), allocatable :: map_em_col1, map_em_col2
        integer, dimension(2) :: col1, col2
        integer, dimension(:), allocatable :: iarray1, iarray2
        integer, dimension(:), allocatable :: iisec1, iisec2
        integer :: sign
        color_factor = zero; color_factor_born = zero
        found = .false.
        !!! Include distinction between Born flavors
        do i = 1, size (color_data%color_factors_born)
            color_factor_born = color_factor_born + &
                real (color_data%color_factors_born (i))
        end do
        i1 = 1
        i2 = 1
        !!! Catch case em = 0
        if (em1 == 0 .or. em2 == 0) then
            !!! What to do?
            bij = zero
        else
            do i = 1, color_data%n_col_real

```

```

col1 = color_data%col_state_real (:, em1, i)
col2 = color_data%col_state_real (:, reg_data%nlegs_real, i)
if (share_line (col1, col2)) then
    map_em_col_tmp(1,i1) = i
    i1 = i1+1
end if
col1 = color_data%col_state_real (:, em2, i)
if (share_line (col1, col2)) then
    map_em_col_tmp(2,i2) = i
    i2 = i2 + 1
end if
end do
allocate (map_em_col1 (i1), map_em_col2 (i2))
map_em_col1 = map_em_col_tmp (1,1:i1-1)
map_em_col2 = map_em_col_tmp (2,1:i2-1)

i_reg = 1

do i = 1, reg_data%n_regions
    if (uborn_index == reg_data%regions(i)%uborn_index) then
        if (em1 == reg_data%regions(i)%emitter .or. &
            (em1 <= 2 .and. reg_data%regions(i)%emitter == 0)) then
            reg(1,i_reg(1)) = reg_data%regions(i)
            i_reg(1) = i_reg(1)+1
            found(1) = .true.
        end if
        if (em2 == reg_data%regions(i)%emitter .or. &
            (em2 <= 2 .and. reg_data%regions(i)%emitter == 0)) then
            reg(2,i_reg(2)) = reg_data%regions(i)
            i_reg(2) = i_reg(2)+1
            found(2) = .true.
        end if
    end if
end do
if (.not. (found(1).and.found(2))) then
    bij = 0
    return
end if

do i = 1, i_reg(1)-1
    do j = 1, i_reg(2)-1
        icm1 = color_data%icm (reg(1,i)%alr)
        icm2 = color_data%icm (reg(2,j)%alr)

        iarray1 = icm1%get_index_array ()
        iarray2 = icm2%get_index_array ()

        iisec1 = pack (iarray1, [ (any(iarray1(i) == map_em_col1), &
            i = 1, size(iarray1)) ])
        iisec2 = pack (iarray2, [ (any(iarray2(i) == map_em_col2), &
            i = 1, size(iarray2)) ])

        cf_present = color_index_present (color_data%cf_index_real)

```



```

do k = 1, size (iisec1)
  do l = 1, size (iisec2)
    i1 = iisec1(k)
    i2 = iisec2(l)
    if (cf_present (i1, i2)) then
      if (is_gluon (flst_real%flst (em1)) .or. &
         is_gluon (flst_real%flst (em2))) then
        sign = get_sign (color_data%col_state_real (:,i1)) * &
              get_sign (color_data%col_state_real (:,i2))
      else
        sign = 1
      end if
      color_factor = color_factor + sign*compute_color_factor &
        (color_data%color_real(:,i1), &
         color_data%color_real(:,i2))
    end if
  end do
end do
end do
end do
!!! The real color factor always differs from the Born one
!!! by one vertex factor. Thus, apply the factor 1/2
bij = color_factor / (2 * color_factor_born)
end if

contains

function share_line (col1, col2) result (share)
  integer, intent(in), dimension(2) :: col1, col2
  logical :: share
  logical :: id1, id2, id3
  id1 = (abs(col1(1)) == abs(col2(1)) .and. col1(1) /= 0) .or. &
        (abs(col1(2)) == abs(col2(2)) .and. col1(2) /= 0)
  id2 = (abs(col1(1)) == abs(col2(2)) .and. col1(1) /= 0) .or. &
        (abs(col1(2)) == abs(col2(1)) .and. col1(2) /= 0)
  id3 = col2(1) == 0 .and. col2(2) == 0
  if (id1 .or. id2 .or. id3) then
    share = .true.
  else
    share = .false.
  end if
end function share_line

function get_sign (col) result (sign)
  integer, intent(in), dimension(:, :) :: col
  integer :: sign
  integer, dimension(:), allocatable :: iref, iperm
  integer :: iref1, iperm1
  integer :: n, i, i_first, j
  integer :: i1, i2
  integer :: p1, p2
  p1 = 2; p2 = 2
  iref1 = 0; iperm1 = 0; i_first = 0
  do i = 1, size(col(1,:))
    if (.not. all (col(:,i) == 0)) then

```

```

        if (col(1,i) == 0) then
            i1 = col(2,i)
            iref1 = i; iperm1 = i
            i_first = i
        else
            i1 = col(1,i)
            iref1 = i; iperm1 = i
            i_first = i
        end if
        exit
    end if
end do
if (iref1 == 0 .or. iperm1 == 0 .or. i_first == 0) &
    call msg_fatal ("Invalid color structure")
n = size(col(1,:)) - i_first + 1
allocate (iref(n), iperm(n))
iref(1) = iref1; iperm(1) = iperm1
do i = i_first+1, size(col(1,:))
    if (all (col(:,i) == 0)) cycle
    if (i == size(col(1,:))) then
        iref(p1) = i_first + 1
    else
        iref(p1) = i + 1
        p1 = p1 + 1
    end if
    do j = i_first+1, size(col(1,:))
        if (col(1,j) == -i1) then
            i1 = col(2,j)
            iperm(p2) = j
            p2 = p2 + 1
            exit
        else if (col(2,j) == -i1) then
            i1 = col(1,j)
            iperm(p2) = j
            p2 = p2 + 1
            exit
        end if
    end do
end do
sign = 1
do i = 1, n
    if (iperm(i) == iref(i)) then
        cycle
    else
        do j = i+1, n
            if (iperm(j) == iref(i)) then
                i1 = j
                exit
            end if
        end do
        i2 = iperm(i)
        iperm(i) = iperm(i1)
        iperm(i1) = i2
        sign = -sign
    end if
end do

```

```

        end if
    end do
end function get_sign

function color_index_present (cf_index) result (cf_present)
    integer, intent(in), dimension(:,:), allocatable :: cf_index
    logical, dimension(:,:), allocatable :: cf_present
    integer :: n_col
    integer :: c, i1, i2
    n_col = size (cf_index(1,:))
    allocate (cf_present (n_col, n_col))
    cf_present = .false.
    do c = 1, n_col
        i1 = cf_index (1, c)
        i2 = cf_index (2, c)
        cf_present (i1, i2) = .true.
        if (i1 /= i2) cf_present(i2, i1) = .true.
    end do
end function color_index_present
end function color_data_compute_bij

```

<nlo controller: color data: TBP>+≡

```

    procedure :: write => color_data_write

```

<nlo controller: procedures>+≡

```

subroutine color_data_write (color_data, unit)
    class(color_data_t), intent(in) :: color_data
    integer, intent(in), optional :: unit
    integer :: u, i, i1, i2
    integer :: n_legs
    u = given_output_unit (unit); if (u < 0) return
    n_legs = size (color_data%beta_ij, dim=2)
    write (u, "(1x,A)") "Color information: "
    write (u, "(1x,A,1x,I1)") "Number of Born color states: ", &
        color_data%n_col_born
    write (u, "(1x,A,1x,I1)") "Number of real color states: ", &
        color_data%n_col_real
    write (u, "(1x,A)") "Color correlation: "
    do i = 1, size (color_data%beta_ij, dim=3)
        write (u, "(1x,A,1x,I1)") "State nr. ", i
        write (u, "(1x,A)") "-----"
        write (u, "(1x,A,1x,A,1x,A)") "i1", "i2", "color factor"
        do i1 = 1, n_legs
            do i2 = 1, i1
                write (u, "(1x,I1,1x,I1,1x,F5.2)") &
                    i1, i2, color_data%beta_ij (i1,i2,i)
            end do
        end do
        write (u, "(1x,A)") "===== "
    end do
    if (color_data%color_is_conserved) then
        write (u, "(1x,A)") "Color is conserved."
    else
        write (u, "(1x,A)") "Fatal error: Color conversation is violated."
    end if
end subroutine color_data_write

```

```

end if
end subroutine color_data_write

```

```

<nlo controller: nlo controller: TBP>≡
  procedure :: compute_sqme_real_fin => nlo_controller_compute_sqme_real_fin

<nlo controller: procedures>+≡
  function nlo_controller_compute_sqme_real_fin &
    (nlo_controller, weight, p_real) result (sqme_fin)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    real(default), intent(in) :: weight
    type(vector4_t), intent(inout), dimension(:), allocatable :: p_real
    type(vector4_t), dimension(:), allocatable :: p_born
    real(default) :: sqme_fin
    integer :: emitter
    if (.not. nlo_controller%alpha_s_born_set) &
      call msg_fatal ("Strong coupling not set for real calculation")
    emitter = nlo_controller%get_active_emitter ()
    p_born = nlo_controller%int_born%get_momenta ()
    call nlo_controller%real_terms%set_momenta (p_born, p_real)
    call nlo_controller%real_terms%set_real_kinematics &
      (nlo_controller%real_kinematics)
    call nlo_controller%real_terms%set_isr_kinematics &
      (nlo_controller%isr_kinematics)
    sqme_fin = nlo_controller%real_terms%compute &
      (emitter, nlo_controller%alpha_s_born)
    sqme_fin = sqme_fin * weight
  end function nlo_controller_compute_sqme_real_fin

```

Check if there are massive emitters. Since the mass-structure of all underlying Born configurations have to be the same, we just use the first one to determine this.

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: has_massive_emitter => nlo_controller_has_massive_emitter

<nlo controller: procedures>+≡
  function nlo_controller_has_massive_emitter (nlo_controller) result (val)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    logical :: val
    integer :: n_tot, i
    val = .false.
    associate (particle_data => nlo_controller%particle_data)
      n_tot = particle_data%n_in + particle_data%n_out_born
      do i = particle_data%n_in+1, n_tot
        if (any (i == nlo_controller%reg_data%emitters)) &
          val = val .or. nlo_controller%reg_data%flv_born(1)%massive(i)
      end do
    end associate
  end function nlo_controller_has_massive_emitter

```

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_mass_info => nlo_controller_get_mass_info

```

```

<nlo controller: procedures>+≡
function nlo_controller_get_mass_info (nlo_controller, i_flv) result (massive)
  class(nlo_controller_t), intent(in) :: nlo_controller
  integer, intent(in) :: i_flv
  logical, dimension(:), allocatable :: massive
  massive = nlo_controller%reg_data%flv_born(i_flv)%massive
end function nlo_controller_get_mass_info

```

25.6.1 Putting it together

```

<nlo data: public>+≡
public :: nlo_particle_data_t

<nlo data: types>+≡
type :: nlo_particle_data_t
  integer :: n_in
  integer :: n_out_born, n_out_real
  integer :: n_flv_born, n_flv_real
end type nlo_particle_data_t

<nlo data: public>+≡
public :: nlo_states_t

<nlo data: types>+≡
type :: nlo_states_t
  integer, dimension(:,:), allocatable :: flv_state_born
  integer, dimension(:,:), allocatable :: flv_state_real
  integer, dimension(:), allocatable :: flv_born
  integer, dimension(:), allocatable :: hel_born
  integer, dimension(:), allocatable :: col_born
end type nlo_states_t

<nlo data: public>+≡
public :: sqme_collector_t

<nlo data: types>+≡
type :: sqme_collector_t
  real(default) :: current_sqme_born
  real(default) :: current_sqme_real
  real(default), dimension(:), allocatable :: sqme_real_per_emitter
  real(default), dimension(:), allocatable :: sqme_real_non_sub
  real(default), dimension(:,:), allocatable :: sqme_born_cc
  complex(default), dimension(:), allocatable :: sqme_born_sc
  real(default) :: sqme_real_sum
  real(default) :: current_sqme_virt
  real(default), dimension(:), allocatable :: sqme_born_list
contains
  <nlo data: sqme collector: TBP>
end type sqme_collector_t

<nlo data: sqme collector: TBP>≡
procedure :: get_sqme_sum => sqme_collector_get_sqme_sum

```

```

<nlo data: procedures>+≡
function sqme_collector_get_sqme_sum (collector) result (sqme)
  class(sqme_collector_t), intent(in) :: collector
  real(default) :: sqme
  sqme = collector%current_sqme_born + &
        collector%sqme_real_sum + &
        collector%current_sqme_virt
end function sqme_collector_get_sqme_sum

<nlo data: sqme collector: TBP>+≡
procedure :: get_sqme_born => sqme_collector_get_sqme_born

<nlo data: procedures>+≡
function sqme_collector_get_sqme_born (collector, i_flv) result (sqme)
  class(sqme_collector_t), intent(in) :: collector
  integer, intent(in), optional :: i_flv
  real(default) :: sqme
  if (present (i_flv)) then
    sqme = collector%sqme_born_list (i_flv)
  else
    sqme = collector%current_sqme_born
  end if
end function sqme_collector_get_sqme_born

<nlo data: sqme collector: TBP>+≡
procedure :: setup_sqme_real => sqme_collector_setup_sqme_real

<nlo data: procedures>+≡
subroutine sqme_collector_setup_sqme_real (collector, n_particles)
  class(sqme_collector_t), intent(inout) :: collector
  integer, intent(in) :: n_particles
  if (.not. allocated (collector%sqme_real_per_emitter)) &
    allocate (collector%sqme_real_per_emitter (n_particles))
  collector%sqme_real_per_emitter = 0._default
end subroutine sqme_collector_setup_sqme_real

```

This data type governs the whole calculation. It contains information about color, spin and flavor as well as the information about the Born process.

```

<nlo controller: public>≡
public :: nlo_controller_t

<nlo controller: types>+≡
type :: nlo_controller_t
  type(region_data_t) :: reg_data
  type(nlo_particle_data_t) :: particle_data
  type(nlo_states_t) :: particle_states
  type(sqme_collector_t) :: sqme_collector
  integer :: n_allowed_born
  integer :: active_emitter
  complex(default), dimension(:), allocatable :: amp_born
  type(color_data_t) :: color_data
  type(real_kinematics_t), pointer :: real_kinematics => null()
  type(isr_kinematics_t), pointer :: isr_kinematics => null()
  type(virtual_t) :: virtual_terms

```

```

type(real_subtraction_t) :: real_terms
type(pdf_subtraction_t) :: pdf_terms
real(default) :: alpha_s_born
logical :: alpha_s_born_set
complex(default) :: me_sc
type(interaction_t), public :: int_born
type(kinematics_counter_t), public :: counter
logical, public :: counter_exists = .false.
logical :: use_internal_color_correlations = .true.
logical :: use_internal_spin_correlations = .false.
logical :: combined_nlo_integration = .false.
contains
<nlo controller: nlo controller: TBP>
end type nlo_controller_t

```

<nlo controller: nlo controller: TBP>+≡

```

procedure :: init => nlo_controller_init

```

<nlo controller: procedures>+≡

```

subroutine nlo_controller_init (nlo_controller, prc_constants, template, model)
  class(nlo_controller_t), intent(inout) :: nlo_controller
  type(process_constants_t), intent(in), dimension(2) :: prc_constants
  type(fks_template_t), intent(in) :: template
  type(model_data_t), intent(in) :: model
  call nlo_controller%set_flv_states (prc_constants)
  call nlo_controller%init_region_data (template, model)
  call nlo_controller%set_particle_data (prc_constants)
  call nlo_controller%setup_matrix_elements ()
  if (nlo_controller%use_internal_color_correlations) &
    call nlo_controller%color_data%init (nlo_controller%reg_data, prc_constants)
  nlo_controller%alpha_s_born_set = .false.
  call nlo_controller%init_real_kinematics ()
  associate (particle_data => nlo_controller%particle_data)
    call nlo_controller%real_terms%init (nlo_controller%reg_data, &
                                          particle_data%n_in + particle_data%n_out_born, &
                                          particle_data%n_in + particle_data%n_out_real, &
                                          nlo_controller%sqme_collector)
  end associate
  nlo_controller%counter_exists = template%count_kinematics
  if (nlo_controller%counter_exists) call nlo_controller%counter%init(20)
end subroutine nlo_controller_init

```

<nlo controller: nlo controller: TBP>+≡

```

procedure :: set_flv_states => nlo_controller_set_flv_states

```

<nlo controller: procedures>+≡

```

subroutine nlo_controller_set_flv_states (nlo_controller, prc_constants)
  class(nlo_controller_t), intent(inout) :: nlo_controller
  type(process_constants_t), intent(in), dimension(2) :: prc_constants
  associate (states => nlo_controller%particle_states)
    states%flv_state_born = prc_constants(1)%get_flv_state ()
    states%flv_state_real = prc_constants(2)%get_flv_state ()
  end associate
end subroutine nlo_controller_set_flv_states

```

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_flv_state_real => nlo_controller_get_flv_state_real

<nlo controller: procedures>+≡
  function nlo_controller_get_flv_state_real (nlo_controller, i_uborn) result (flv_state)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer, intent(in) :: i_uborn
    integer, dimension(:), allocatable :: flv_state
    flv_state = nlo_controller%particle_states%flv_state_real (:,i_uborn)
  end function nlo_controller_get_flv_state_real

<nlo controller: nlo controller: TBP>+≡
  procedure :: set_particle_data => nlo_controller_set_particle_data

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_particle_data (nlo_controller, prc_constants)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    type(process_constants_t), intent(in), dimension(2) :: prc_constants
    associate (particle_data => nlo_controller%particle_data)
      particle_data%n_flv_born = nlo_controller%reg_data%n_flv_born
      particle_data%n_flv_real = nlo_controller%reg_data%n_flv_real
      particle_data%n_in = prc_constants(2)%n_in
      particle_data%n_out_born = prc_constants(1)%n_out
      particle_data%n_out_real = prc_constants(2)%n_out
    end associate
  end subroutine nlo_controller_set_particle_data

<nlo controller: nlo controller: TBP>+≡
  procedure :: setup_matrix_elements => nlo_controller_setup_matrix_elements

<nlo controller: procedures>+≡
  subroutine nlo_controller_setup_matrix_elements (nlo_controller)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    integer :: n_tot_born
    associate (collector => nlo_controller%sqme_collector, &
      particle_data => nlo_controller%particle_data)
      allocate (collector%sqme_born_list (particle_data%n_flv_born))
      allocate (collector%sqme_real_non_sub (particle_data%n_flv_real))
      allocate (collector%sqme_real_per_emitter (particle_data%n_in + particle_data%n_out_born))
      n_tot_born = particle_data%n_in + particle_data%n_out_born
      allocate (collector%sqme_born_cc (n_tot_born, n_tot_born, particle_data%n_flv_born))
      allocate (collector%sqme_born_sc (particle_data%n_flv_born))
      collector%sqme_born_list = 0._default
      collector%sqme_real_non_sub = 0._default
      collector%sqme_real_per_emitter = 0._default
      collector%sqme_born_cc = 0._default
      collector%sqme_born_sc = cmplx (0._default, 0._default, kind=default)
    end associate
  end subroutine nlo_controller_setup_matrix_elements

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_n_particles_real => nlo_controller_get_n_particles_real

```



```

<nlo controller: procedures>+≡
  pure function nlo_controller_get_n_particles_real (nlo_controller) result (n_particles)
    integer :: n_particles
    class(nlo_controller_t), intent(in) :: nlo_controller
    n_particles = nlo_controller%particle_data%n_in + nlo_controller%particle_data%n_out_real
  end function nlo_controller_get_n_particles_real

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_n_flv_born => nlo_controller_get_n_flv_born

<nlo controller: procedures>+≡
  elemental function nlo_controller_get_n_flv_born (nlo_controller) result (n_flv)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer :: n_flv
    n_flv = nlo_controller%particle_data%n_flv_born
  end function nlo_controller_get_n_flv_born

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_n_flv_real => nlo_controller_get_n_flv_real

<nlo controller: procedures>+≡
  elemental function nlo_controller_get_n_flv_real (nlo_controller) result (n_flv)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer :: n_flv
    n_flv = nlo_controller%particle_data%n_flv_real
  end function nlo_controller_get_n_flv_real

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_n_alr => nlo_controller_get_n_alr

<nlo controller: procedures>+≡
  elemental function nlo_controller_get_n_alr (nlo_controller) result (n_alr)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer :: n_alr
    n_alr = nlo_controller%reg_data%n_regions
  end function nlo_controller_get_n_alr

<nlo controller: nlo controller: TBP>+≡
  procedure :: init_region_data => nlo_controller_init_region_data

<nlo controller: procedures>+≡
  subroutine nlo_controller_init_region_data (nlo_controller, template, model)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    type(fks_template_t), intent(in) :: template
    type(model_data_t), intent(in) :: model
    associate (states => nlo_controller%particle_states)
      call nlo_controller%reg_data%init (model, &
        states%flv_state_born, states%flv_state_real, &
        template%mapping_type)
      call nlo_controller%reg_data%write_to_file (template%id)
    end associate
    select type (mapping => nlo_controller%reg_data%fks_mapping)
    type is (fks_mapping_default_t)
      call mapping%set_parameter (template%fks_dij_exp1, template%fks_dij_exp2)

```

```

        end select
    end subroutine nlo_controller_init_region_data

<nlo controller: nlo controller: TBP>+≡
    procedure :: get_xi_max => nlo_controller_get_xi_max

<nlo controller: procedures>+≡
    function nlo_controller_get_xi_max (nlo_controller, alr) result (xi_max)
        class(nlo_controller_t), intent(in) :: nlo_controller
        integer, intent(in) :: alr
        real(default) :: xi_max
        integer :: emitter
        emitter = nlo_controller%get_emitter (alr)
        xi_max = nlo_controller%real_kinematics%xi_max (emitter)
    end function nlo_controller_get_xi_max

<nlo controller: nlo controller: TBP>+≡
    procedure :: init_born_amps => nlo_controller_init_born_amps

<nlo controller: procedures>+≡
    subroutine nlo_controller_init_born_amps (nlo_controller, n)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        integer, intent(in) :: n
        nlo_controller%n_allowed_born = n
        if (.not. allocated (nlo_controller%amp_born)) &
            allocate (nlo_controller%amp_born (n))
    end subroutine nlo_controller_init_born_amps

<nlo controller: nlo controller: TBP>+≡
    procedure :: set_internal_procedures => nlo_controller_set_internal_procedures

<nlo controller: procedures>+≡
    subroutine nlo_controller_set_internal_procedures (nlo_controller, flag_color, flag_spin)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        logical, intent(in) :: flag_color, flag_spin
        nlo_controller%use_internal_color_correlations = flag_color
        nlo_controller%real_terms%sub_soft%use_internal_color_correlations = flag_color
        nlo_controller%virtual_terms%use_internal_color_correlations = flag_color
        nlo_controller%use_internal_spin_correlations = flag_spin
    end subroutine nlo_controller_set_internal_procedures

<nlo controller: nlo controller: TBP>+≡
    procedure :: init_virtual => nlo_controller_init_virtual

<nlo controller: procedures>+≡
    subroutine nlo_controller_init_virtual (nlo_controller)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        call nlo_controller%virtual_terms%init (nlo_controller%particle_states%flv_state_born)
    end subroutine nlo_controller_init_virtual

<nlo controller: nlo controller: TBP>+≡
    procedure :: init_pdf_subtraction => nlo_controller_init_pdf_subtraction

```

```

<nlo controller: procedures>+≡
  subroutine nlo_controller_init_pdf_subtraction (nlo_controller)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    call nlo_controller%pdf_terms%init (nlo_controller%isr_kinematics, &
                                         nlo_controller%particle_states%flv_state_born, &
                                         nlo_controller%reg_data%n_regions, &
                                         nlo_controller%sqme_collector)
  end subroutine nlo_controller_init_pdf_subtraction

<nlo controller: nlo controller: TBP>+≡
  procedure :: pdf_subtraction_is_required => nlo_controller_pdf_subtraction_is_required

<nlo controller: procedures>+≡
  function nlo_controller_pdf_subtraction_is_required (nlo_controller) result (required)
    class(nlo_controller_t), intent(in) :: nlo_controller
    logical :: required
    required = nlo_controller%pdf_terms%required
  end function nlo_controller_pdf_subtraction_is_required

<nlo controller: nlo controller: TBP>+≡
  procedure :: evaluate_pdf_subtraction => nlo_controller_evaluate_pdf_subtraction

<nlo controller: procedures>+≡
  function nlo_controller_evaluate_pdf_subtraction (nlo_controller, weight, sqme_born) result (sqme)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    real(default), intent(in) :: weight, sqme_born
    real(default) :: sqme
    integer :: alr

    sqme = 0._default
    if (.not. nlo_controller%alpha_s_born_set) &
      call msg_fatal ("Strong coupling not set for pdf subtraction")
    !   call nlo_controller%pdf_terms%set_isr_kinematics (nlo_controller%isr_kinematics)
    call nlo_controller%pdf_terms%evaluate (nlo_controller%alpha_s_born, sqme_born, 1)
    sqme = nlo_controller%pdf_terms%value(1) * weight
  end function nlo_controller_evaluate_pdf_subtraction

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_emitter_list => nlo_controller_get_emitter_list

<nlo controller: procedures>+≡
  pure function nlo_controller_get_emitter_list (nlo_controller) result(emitters)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer, dimension(:), allocatable :: emitters
    emitters = nlo_controller%reg_data%get_emitter_list ()
  end function nlo_controller_get_emitter_list

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_emitter => nlo_controller_get_emitter

<nlo controller: procedures>+≡
  pure function nlo_controller_get_emitter (nlo_controller, alr) result (emitter)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer, intent(in) :: alr

```

```

        integer :: emitter
        emitter = nlo_controller%reg_data%get_emitter (alr)
    end function nlo_controller_get_emitter

<nlo controller: nlo controller: TBP>+≡
    procedure :: set_active_emitter => nlo_controller_set_active_emitter

<nlo controller: procedures>+≡
    subroutine nlo_controller_set_active_emitter (nlo_controller, emitter)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        integer, intent(in) :: emitter
        nlo_controller%active_emitter = emitter
    end subroutine nlo_controller_set_active_emitter

<nlo controller: nlo controller: TBP>+≡
    procedure :: get_active_emitter => nlo_controller_get_active_emitter

<nlo controller: procedures>+≡
    function nlo_controller_get_active_emitter (nlo_controller) result(emitter)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        integer :: emitter
        emitter = nlo_controller%active_emitter
    end function nlo_controller_get_active_emitter

<nlo controller: nlo controller: TBP>+≡
    procedure :: disable_subtraction => nlo_controller_disable_subtraction
    procedure :: is_subtraction_active => nlo_controller_is_subtraction_active

<nlo controller: procedures>+≡
    subroutine nlo_controller_disable_subtraction (nlo_controller)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        nlo_controller%real_terms%sqme_np1_active = .true.
        nlo_controller%real_terms%subtraction_active = .false.
    end subroutine nlo_controller_disable_subtraction

    function nlo_controller_is_subtraction_active (nlo_controller) result (active)
        class(nlo_controller_t), intent(in) :: nlo_controller
        logical :: active
        active = nlo_controller%real_terms%subtraction_active
    end function nlo_controller_is_subtraction_active

<nlo controller: nlo controller: TBP>+≡
    procedure :: disable_sqme_np1 => nlo_controller_disable_sqme_np1

<nlo controller: procedures>+≡
    subroutine nlo_controller_disable_sqme_np1 (nlo_controller)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        nlo_controller%real_terms%sqme_np1_active = .false.
        nlo_controller%real_terms%subtraction_active = .false.
    end subroutine nlo_controller_disable_sqme_np1

<nlo controller: nlo controller: TBP>+≡
    procedure :: set_alr => nlo_controller_set_alr

```

```

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_alr (nlo_controller, alr)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    integer, intent(in) :: alr
    call nlo_controller%real_terms%set_alr (alr)
  end subroutine nlo_controller_set_alr

<nlo controller: nlo controller: TBP>+≡
  procedure :: set_flv_born => nlo_controller_set_flv_born

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_flv_born (nlo_controller, flv_in)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    integer, intent(in), dimension(:), allocatable :: flv_in
    associate (states => nlo_controller%particle_states)
      allocate (states%flv_born (size (flv_in)))
      states%flv_born = flv_in
    end associate
  end subroutine nlo_controller_set_flv_born

<nlo controller: nlo controller: TBP>+≡
  procedure :: set_hel_born => nlo_controller_set_hel_born

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_hel_born (nlo_controller, hel_in)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    integer, intent(in), dimension(:), allocatable :: hel_in
    associate (states => nlo_controller%particle_states)
      allocate (states%hel_born (size (hel_in)))
      states%hel_born = hel_in
    end associate
  end subroutine nlo_controller_set_hel_born

<nlo controller: nlo controller: TBP>+≡
  procedure :: set_col_born => nlo_controller_set_col_born

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_col_born (nlo_controller, col_in)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    integer, intent(in), dimension(:), allocatable :: col_in
    associate (states => nlo_controller%particle_states)
      allocate (states%col_born (size (col_in)))
      states%col_born = col_in
    end associate
  end subroutine nlo_controller_set_col_born

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_flv_born => nlo_controller_get_flv_born

<nlo controller: procedures>+≡
  elemental function nlo_controller_get_flv_born (nlo_controller, i) result (flv)
    class(nlo_controller_t), intent(in) :: nlo_controller
    integer, intent(in) :: i
    integer :: flv

```

```

        flv = nlo_controller%particle_states%flv_born(i)
    end function nlo_controller_get_flv_born

<nlo controller: nlo controller: TBP>+≡
    procedure :: get_hel_born => nlo_controller_get_hel_born

<nlo controller: procedures>+≡
    elemental function nlo_controller_get_hel_born (nlo_controller, i) result (hel)
        class(nlo_controller_t), intent(in) :: nlo_controller
        integer, intent(in) :: i
        integer :: hel
        hel = nlo_controller%particle_states%hel_born (i)
    end function nlo_controller_get_hel_born

<nlo controller: nlo controller: TBP>+≡
    procedure :: get_col_born => nlo_controller_get_col_born

<nlo controller: procedures>+≡
    elemental function nlo_controller_get_col_born (nlo_controller, i) result (col)
        class(nlo_controller_t), intent(in) :: nlo_controller
        integer, intent(in) :: i
        integer :: col
        col = nlo_controller%particle_states%col_born (i)
    end function nlo_controller_get_col_born

<nlo controller: nlo controller: TBP>+≡
    procedure :: set_alpha_s_born => nlo_controller_set_alpha_s_born

<nlo controller: procedures>+≡
    subroutine nlo_controller_set_alpha_s_born (nlo_controller, as_born)
        class (nlo_controller_t), intent(inout) :: nlo_controller
        real(default), intent(in) :: as_born
        nlo_controller%alpha_s_born = as_born
        nlo_controller%alpha_s_born_set = .true.
    end subroutine nlo_controller_set_alpha_s_born

<nlo controller: nlo controller: TBP>+≡
    procedure :: init_real_kinematics => nlo_controller_init_real_kinematics

<nlo controller: procedures>+≡
    subroutine nlo_controller_init_real_kinematics (nlo_controller)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        integer :: n_tot
        n_tot = nlo_controller%particle_data%n_in + &
            nlo_controller%particle_data%n_out_born
        allocate (nlo_controller%real_kinematics)
        allocate (nlo_controller%isr_kinematics)
        associate (real_kinematics => nlo_controller%real_kinematics)
            allocate (real_kinematics%xi_max (n_tot))
            allocate (real_kinematics%y (n_tot))
            allocate (real_kinematics%y_soft (n_tot))
            allocate (real_kinematics%jac_rand (n_tot))
            allocate (real_kinematics%p_real (n_tot+1))
            allocate (real_kinematics%jac (n_tot))
        end associate
    end subroutine nlo_controller_init_real_kinematics

```

```

        real_kinematics%xi_tilde = 0
        real_kinematics%y = 0
        real_kinematics%xi_max = 0
        real_kinematics%phi = 0
        real_kinematics%cms_energy2 = 0
    end associate
end subroutine nlo_controller_init_real_kinematics

<nlo_controller: nlo_controller: TBP>+≡
    procedure :: init_isr_kinematics => nlo_controller_init_isr_kinematics

<nlo_controller: procedures>+≡
    subroutine nlo_controller_init_isr_kinematics (nlo_controller)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        if (.not. associated (nlo_controller%isr_kinematics)) &
            allocate (nlo_controller%isr_kinematics)
    end subroutine nlo_controller_init_isr_kinematics

<nlo_controller: nlo_controller: TBP>+≡
    procedure :: set_real_kinematics => nlo_controller_set_real_kinematics

<nlo_controller: procedures>+≡
    subroutine nlo_controller_set_real_kinematics (nlo_controller, xi_tilde, y, phi, xi_max, &
                                                jac, jac_rand)
        class(nlo_controller_t), intent(inout) :: nlo_controller
        real(default), dimension(:), allocatable :: xi_max, y
        real(default), intent(in) :: xi_tilde
        real(default), intent(in) :: phi
        real(default), intent(in), dimension(3) :: jac
        real(default), intent(in), dimension(:), allocatable :: jac_rand
        nlo_controller%real_kinematics%xi_tilde = xi_tilde
        nlo_controller%real_kinematics%y = y
        nlo_controller%real_kinematics%phi = phi
        nlo_controller%real_kinematics%xi_max = xi_max
        nlo_controller%real_kinematics%jac(1)%jac = jac
        nlo_controller%real_kinematics%jac_rand = jac_rand
    end subroutine nlo_controller_set_real_kinematics

<nlo_controller: nlo_controller: TBP>+≡
    procedure :: get_real_kinematics => nlo_controller_get_real_kinematics

<nlo_controller: procedures>+≡
    subroutine nlo_controller_get_real_kinematics &
        (nlo_controller, em, xi_tilde, y, xi_max, jac, phi, jac_rand)
        class(nlo_controller_t), intent(in) :: nlo_controller
        integer, intent(in) :: em
        real(default), intent(out) :: xi_tilde, y, xi_max
        real(default), intent(out), dimension(3), optional :: jac
        !!! For most applications, phi is not relevant. Thus, it is not
        !!! always transferred as a dummy-variable
        real(default), intent(out), optional :: phi
        real(default), intent(out), dimension(:), optional :: jac_rand
        xi_tilde = nlo_controller%real_kinematics%xi_tilde
        y = nlo_controller%real_kinematics%y(em)

```

```

xi_max = nlo_controller%real_kinematics%xi_max (em)
if (present (jac)) jac = nlo_controller%real_kinematics%jac(1)%jac
if (present (phi)) phi = nlo_controller%real_kinematics%phi
if (present (jac_rand)) jac_rand = nlo_controller%real_kinematics%jac_rand
end subroutine nlo_controller_get_real_kinematics

```

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: set_real_momenta => nlo_controller_set_real_momenta

```

```

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_real_momenta (nlo_controller, p)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    type(vector4_t), intent(in), dimension(:) :: p
    nlo_controller%real_kinematics%p_real = p
  end subroutine nlo_controller_set_real_momenta

```

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: get_real_momenta => nlo_controller_get_real_momenta

```

```

<nlo controller: procedures>+≡
  function nlo_controller_get_real_momenta (nlo_controller) result (p)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    type(vector4_t), dimension(:), allocatable :: p
    p = nlo_controller%real_kinematics%p_real
  end function nlo_controller_get_real_momenta

```

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: set_fac_scale => nlo_controller_set_fac_scale

```

```

<nlo controller: procedures>+≡
  subroutine nlo_controller_set_fac_scale (nlo_controller, fac_scale)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    real(default), intent(in) :: fac_scale
    if (associated (nlo_controller%isr_kinematics)) &
      nlo_controller%isr_kinematics%fac_scale = fac_scale
  end subroutine nlo_controller_set_fac_scale

```

25.6.2 xxx

```

<nlo controller: nlo controller: TBP>+≡
  procedure :: compute_virt => nlo_controller_compute_virt

```

```

<nlo controller: procedures>+≡
  function nlo_controller_compute_virt &
    (nlo_controller, i_flv, int_born) result(sqme_virt)
    class(nlo_controller_t), intent(inout) :: nlo_controller
    integer, intent(in) :: i_flv
    type(interaction_t), intent(in) :: int_born
    real(default) :: sqme_virt
    type(vector4_t), dimension(:), allocatable :: p_born
    p_born = int_born%get_momenta ()
    associate (collector => nlo_controller%sqme_collector)
      if (nlo_controller%use_internal_color_correlations) then

```



```

        call nlo_controller%virtual_terms%evaluate &
            (nlo_controller%reg_data, &
             i_flv, nlo_controller%alpha_s_born, &
             p_born, collector%current_sqme_born, &
             nlo_controller%color_data%beta_ij)
    else
        call nlo_controller%virtual_terms%evaluate &
            (nlo_controller%reg_data, &
             i_flv, nlo_controller%alpha_s_born, &
             p_born, collector%current_sqme_born, &
             collector%sqme_born_cc)
    end if
end associate
sqme_virt = nlo_controller%virtual_terms%sqme_virt
end function nlo_controller_compute_virt

```

```

<nlo controller: nlo controller: TBP>+≡
    procedure :: requires_spin_correlation => &
        nlo_controller_requires_spin_correlation

<nlo controller: procedures>+≡
    function nlo_controller_requires_spin_correlation &
        (nlo_controller, i_flv) result (val)
        class(nlo_controller_t), intent(in) :: nlo_controller
        integer, intent(in) :: i_flv
        logical :: val
        val = nlo_controller%real_terms%sc_required (i_flv)
    end function nlo_controller_requires_spin_correlation

```

25.7 The FKS phase space

To handle the FKS phase space and adapt it to multi-channel integration, some extensions have to be made for pre-existing types. The `phs_tree`-type has an attribute containing the tree-code of the emitting branch.

```
<PHS trees: phs tree: TBP>≡
  procedure :: get_emitter => phs_tree_get_emitter

<PHS trees: procedures>+≡
  function phs_tree_get_emitter (tree) result (emitter)
    class(phs_tree_t), intent(in) :: tree
    integer :: emitter
    emitter = tree%emitter
  end function phs_tree_get_emitter

<phs_fks.f90>≡
<File header>

  module phs_fks

    <Use kinds>
    <Use strings>
    use constants
    use diagnostics
    use io_units, only: given_output_unit
    use format_utils, only: write_separator
    use lorentz
    use physics_defs
    use flavors
    use sf_mappings
    use sf_base
    use phs_base
    use phs_wood
    use process_constants
    use process_libraries
    use unit_tests
    use nlo_data

    <Standard module head>

    <phs fks: public>

    <phs fks: parameters>

    <phs fks: types>

    <phs fks: interfaces>

    contains

    <phs fks: procedures>

  end module phs_fks
```

```

<phs fks: parameters>≡
  integer, parameter, public :: I_XI = 1
  integer, parameter, public :: I_Y = 2
  integer, parameter, public :: I_PHI = 3

  integer, parameter, public :: PHS_MODE_UNDEFINED = 0
  integer, parameter, public :: PHS_MODE_ADDITIONAL_PARTICLE = 1
  integer, parameter, public :: PHS_MODE_COLLINEAR_REMNANT = 2

<phs fks: public>≡
  public :: phs_fks_config_t

<phs fks: types>≡
  type, extends (phs_wood_config_t) :: phs_fks_config_t
    integer :: mode = PHS_MODE_UNDEFINED
  contains
    <phs fks: fks config: TBP>
  end type phs_fks_config_t

<phs fks: fks config: TBP>≡
  procedure :: final => phs_fks_config_final

<phs fks: procedures>≡
  subroutine phs_fks_config_final (object)
    class(phs_fks_config_t), intent(inout) :: object
    !   call object%phs_wood_config_t%final ()
  end subroutine phs_fks_config_final

<phs fks: fks config: TBP>+≡
  procedure :: write => phs_fks_config_write

<phs fks: procedures>+≡
  subroutine phs_fks_config_write (object, unit)
    class(phs_fks_config_t), intent(in) :: object
    integer, intent(in), optional :: unit
    call object%phs_wood_config_t%write
  end subroutine phs_fks_config_write

<phs fks: fks config: TBP>+≡
  procedure :: set_mode => phs_fks_config_set_mode

<phs fks: procedures>+≡
  subroutine phs_fks_config_set_mode (phs_config, mode)
    class(phs_fks_config_t), intent(inout) :: phs_config
    integer, intent(in) :: mode
    select case (mode)
    case (NLO_REAL)
      phs_config%mode = PHS_MODE_ADDITIONAL_PARTICLE
    case (NLO_PDF)
      phs_config%mode = PHS_MODE_COLLINEAR_REMNANT
    end select
  end subroutine phs_fks_config_set_mode

```

```

<phs fks: fks config: TBP>+≡
  procedure :: configure => phs_fks_config_configure

<phs fks: procedures>+≡
  subroutine phs_fks_config_configure (phs_config, sqrts, &
    sqrts_fixed, cm_frame, azimuthal_dependence, rebuild, &
    ignore_mismatch, nlo_type)
    class(phs_fks_config_t), intent(inout) :: phs_config
    real(default), intent(in) :: sqrts
    logical, intent(in), optional :: sqrts_fixed
    logical, intent(in), optional :: cm_frame
    logical, intent(in), optional :: azimuthal_dependence
    logical, intent(in), optional :: rebuild
    logical, intent(in), optional :: ignore_mismatch
    integer, intent(inout), optional :: nlo_type
    if (present (nlo_type)) then
      if (.not. (nlo_type == NLO_REAL .or. nlo_type == NLO_PDF)) &
        call msg_fatal ("FKS config has to be called with nlo_type = 'Real' or nlo_type = 'Pdf'")
      end if
    if (.not. phs_config%extended_phs) then
      select case (phs_config%mode)
        case (PHS_MODE_ADDITIONAL_PARTICLE)
          phs_config%n_par = phs_config%n_par + 3
        case (PHS_MODE_COLLINEAR_REMNANT)
          phs_config%n_par = phs_config%n_par + 1
        end select
      end if
    !!! Channel equivalences not accessible yet
    phs_config%provides_equivalences = .false.
  end subroutine phs_fks_config_configure

<phs fks: fks config: TBP>+≡
  procedure :: startup_message => phs_fks_config_startup_message

<phs fks: procedures>+≡
  subroutine phs_fks_config_startup_message (phs_config, unit)
    class(phs_fks_config_t), intent(in) :: phs_config
    integer, intent(in), optional :: unit
    call phs_config%phs_wood_config_t%startup_message
  end subroutine phs_fks_config_startup_message

<phs fks: fks config: TBP>+≡
  procedure, nopass :: allocate_instance => phs_fks_config_allocate_instance

<phs fks: procedures>+≡
  subroutine phs_fks_config_allocate_instance (phs)
    class(phs_t), intent(inout), pointer :: phs
    allocate (phs_fks_t :: phs)
  end subroutine phs_fks_config_allocate_instance

<phs fks: fks config: TBP>+≡
  procedure :: set_born_config => phs_fks_config_set_born_config

```

```

<phs fks: procedures>+≡
subroutine phs_fks_config_set_born_config (phs_config, phs_cfg_born)
  class(phs_fks_config_t), intent(inout) :: phs_config
  type(phs_wood_config_t), intent(in), target :: phs_cfg_born
  phs_config%forest = phs_cfg_born%forest
  phs_config%n_channel = phs_cfg_born%n_channel
  allocate (phs_config%channel (phs_config%n_channel))
  phs_config%n_par = phs_cfg_born%n_par
  phs_config%sqrts = phs_cfg_born%sqrts
  phs_config%par = phs_cfg_born%par
  phs_config%sqrts_fixed = phs_cfg_born%sqrts_fixed
  phs_config%azimuthal_dependence = phs_cfg_born%azimuthal_dependence
  phs_config%provides_chains = phs_cfg_born%provides_chains
  phs_config%chain = phs_cfg_born%chain
end subroutine phs_fks_config_set_born_config

```

Keep score about the real kinematics.

```

<phs fks: public>+≡
  public :: kinematics_counter_t

<phs fks: types>+≡
  type :: kinematics_counter_t
    integer :: n_bins = 0
    integer, dimension(:), allocatable :: histo_xi
    integer, dimension(:), allocatable :: histo_xi_tilde
    integer, dimension(:), allocatable :: histo_xi_max
    integer, dimension(:), allocatable :: histo_y
    integer, dimension(:), allocatable :: histo_phi
  contains
    <phs fks: kinematics counter: TBP>
  end type kinematics_counter_t

```

```

<phs fks: kinematics counter: TBP>≡
  procedure :: init => kinematics_counter_init

<phs fks: procedures>+≡
subroutine kinematics_counter_init (counter, n_bins)
  class(kinematics_counter_t), intent(inout) :: counter
  integer, intent(in) :: n_bins
  counter%n_bins = n_bins
  allocate (counter%histo_xi (n_bins), counter%histo_xi_tilde (n_bins))
  allocate (counter%histo_y (n_bins), counter%histo_phi (n_bins))
  allocate (counter%histo_xi_max (n_bins))
  counter%histo_xi = 0
  counter%histo_xi_tilde = 0
  counter%histo_xi_max = 0
  counter%histo_y = 0
  counter%histo_phi = 0
end subroutine kinematics_counter_init

```

```

<phs fks: kinematics counter: TBP>+≡
  procedure :: record => kinematics_counter_record

```

<phs fks: procedures>+≡

```

subroutine kinematics_counter_record (counter, xi, xi_tilde, &
                                     xi_max, y, phi)
  class(kinematics_counter_t), intent(inout) :: counter
  real(default), intent(in), optional :: xi, xi_tilde, xi_max
  real(default), intent(in), optional :: y, phi

  if (counter%n_bins > 0) then
    if (present (xi)) then
      call fill_histogram (counter%histo_xi, xi, &
                          0.0_default, 1.0_default)
    end if
    if (present (xi_tilde)) then
      call fill_histogram (counter%histo_xi_tilde, xi_tilde, &
                          0.0_default, 1.0_default)
    end if
    if (present (xi_max)) then
      call fill_histogram (counter%histo_xi_max, xi_max, &
                          0.0_default, 1.0_default)
    end if
    if (present (y)) then
      call fill_histogram (counter%histo_y, y, -1.0_default, 1.0_default)
    end if
    if (present (phi)) then
      call fill_histogram (counter%histo_phi, phi, 0.0_default, twopi)
    end if
  end if
contains
  subroutine fill_histogram (histo, value, val_min, val_max)
    integer, dimension(:), allocatable :: histo
    real(default), intent(in) :: value, val_min, val_max
    real(default) :: step, lo, hi
    integer :: bin
    step = (val_max-val_min) / counter%n_bins
    do bin = 1, counter%n_bins
      lo = (bin-1) * step
      hi = bin * step
      if (value >= lo .and. value < hi) then
        histo (bin) = histo (bin) + 1
      end if
    end do
  end subroutine fill_histogram
end subroutine kinematics_counter_record

```

<phs fks: kinematics counter: TBP>+≡

```

procedure :: display => kinematics_counter_display

```

<phs fks: procedures>+≡

```

subroutine kinematics_counter_display (counter)
  class(kinematics_counter_t), intent(in) :: counter
  print *, 'xi: ', counter%histo_xi
  print *, 'xi_tilde: ', counter%histo_xi_tilde
  print *, 'xi_max: ', counter%histo_xi_max

```

```

    print *, 'y: ', counter%histo_y
    print *, 'phi: ', counter%histo_phi
end subroutine kinematics_counter_display

```

```

<phs fks: public>+≡
    public :: phs_fks_generator_t

<phs fks: types>+≡
    type :: phs_fks_generator_t
        integer, dimension(:), allocatable :: emitters
        type(real_kinematics_t), pointer :: real_kinematics => null()
    !   real(default), dimension(2) :: is_momentum_fractions = 1._default
        type(isr_kinematics_t), pointer :: isr_kinematics => null()
        !!! xi_min should be set to a non-zero value in order to avoid
        !!! phase-space points with p_real(emitter) = 0
        real(default) :: xi_min = tiny_07
        real(default) :: y_max = 1._default
        real(default) :: E_beam_tot
        real(default) :: E_gluon
        real(default) :: mrec2
        real(default), dimension(:), allocatable :: m2
        logical :: massive_phsp = .false.
        logical, dimension(:), allocatable :: is_massive
        logical :: singular_jacobian = .false.
    contains
    <phs fks: phs fks generator: TBP>
end type phs_fks_generator_t

```

The fks phase space type contains the wood phase space and separately the in- and outgoing momenta for the real process and the corresponding Born momenta. Additionally, there are the variables ξ, ξ_{max}, y and ϕ which are used to create the real phase space, as well as the jacobian and its corresponding soft and collinear limit. Lastly, the array `ch_to_em` connects each channel with an emitter.

```

<phs fks: public>+≡
    public :: phs_fks_t

<phs fks: types>+≡
    type, extends (phs_wood_t) :: phs_fks_t
        integer :: mode = PHS_MODE_UNDEFINED
        type(vector4_t), dimension(:), allocatable :: p_born
        type(vector4_t), dimension(:), allocatable :: q_born
        type(vector4_t), dimension(:), allocatable :: p_real
        type(vector4_t), dimension(:), allocatable :: q_real
        type(vector4_t), dimension(:), allocatable :: p_born_tot
        type(real_kinematics_t), pointer :: real_kinematics => null()
        type(isr_kinematics_t), pointer :: isr_kinematics => null()
        type(phs_fks_generator_t) :: generator
        type(kinematics_counter_t) :: counter
        logical :: massive_phsp = .false.
        logical :: perform_generation = .true.
        !!! Not entirely suited for combined integration
        !!! TODO: Modify global r_real-array

```

```

        real(default) :: r_isr

contains
  <phs fks: phs fks: TBP>
  end type phs_fks_t

  <phs fks: interfaces>≡

  interface compute_beta
    module procedure compute_beta_massless
    module procedure compute_beta_massive
  end interface

  interface get_xi_max_fsr
    module procedure get_xi_max_fsr_massless
    module procedure get_xi_max_fsr_massive
  end interface

```

Initializer for the phase space. Calls the initialization of the corresponding Born phase space, sets up the channel-emitter-association and allocates space for the momenta.

```

  <phs fks: phs fks: TBP>≡
  procedure :: init => phs_fks_init

  <phs fks: procedures>+≡
  subroutine phs_fks_init (phs, phs_config)
    class(phs_fks_t), intent(out) :: phs
    class(phs_config_t), intent(in), target :: phs_config

    call phs%base_init (phs_config)
    select type (phs_config)
    type is (phs_fks_config_t)
      phs%config => phs_config
      phs%forest = phs_config%forest
    end select

    select type(phs)
    type is (phs_fks_t)
      select type (phs_config)
      type is (phs_fks_config_t)
        phs%mode = phs_config%mode
      end select

      select case (phs%mode)
      case (PHS_MODE_ADDITIONAL_PARTICLE)
        phs%n_r_born = phs%config%n_par - 3
      case (PHS_MODE_COLLINEAR_REMNANT)
        phs%n_r_born = phs%config%n_par - 1
      end select
      call phs%init_momenta (phs_config)
    end select
  end subroutine phs_fks_init

```



```

<phs fks: phs fks: TBP>+≡
  procedure :: setup_real_kinematics => phs_fks_setup_real_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_setup_real_kinematics (phs, real_kinematics)
    class(phs_fks_t), intent(inout) :: phs
    type(real_kinematics_t), intent(in), target :: real_kinematics
    phs%real_kinematics => real_kinematics
  end subroutine phs_fks_setup_real_kinematics

<phs fks: phs fks: TBP>+≡
  procedure :: setup_isr_kinematics => phs_fks_setup_isr_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_setup_isr_kinematics (phs, fractions)
    class(phs_fks_t), intent(inout) :: phs
    type(isr_kinematics_t), intent(in), target :: fractions
    phs%isr_kinematics => fractions
  end subroutine phs_fks_setup_isr_kinematics

<phs fks: phs fks: TBP>+≡
  procedure :: final => phs_fks_final

<phs fks: procedures>+≡
  subroutine phs_fks_final (object)
    class(phs_fks_t), intent(inout) :: object
  end subroutine phs_fks_final

<phs fks: phs fks: TBP>+≡
  procedure :: init_momenta => phs_fks_init_momenta

<phs fks: procedures>+≡
  subroutine phs_fks_init_momenta (phs, phs_config)
    class(phs_fks_t), intent(inout) :: phs
    class(phs_config_t), intent(in) :: phs_config
    allocate (phs%p_born (phs_config%n_in))
    allocate (phs%p_real (phs_config%n_in))
    select case (phs%mode)
    case (PHS_MODE_ADDITIONAL_PARTICLE)
      allocate (phs%q_born (phs_config%n_out-1))
      allocate (phs%q_real (phs_config%n_out-1))
      allocate (phs%p_born_tot (phs%config%n_in + phs%config%n_out-1))
    end select
  end subroutine phs_fks_init_momenta

```

Evaluate selected channel. First, the subroutine calls the evaluation procedure of the underlying Born phase space, using $n_r - 3$ random numbers. Then, the remaining three random numbers are used to create ξ , y and ϕ , from which the real momenta are calculated from the Born momenta.

```

<phs fks: phs fks: TBP>+≡
  procedure :: evaluate_selected_channel => phs_fks_evaluate_selected_channel

```

```

<phs fks: procedures>+≡
subroutine phs_fks_evaluate_selected_channel (phs, c_in, r_in)
  class(phs_fks_t), intent(inout) :: phs
  integer, intent(in) :: c_in
  real(default), intent(in), dimension(:) :: r_in
  integer :: n_in

  call phs%phs_wood_t%evaluate_selected_channel (c_in, r_in)
  phs%r(:,c_in) = r_in

  if (phs%perform_generation) then
    select case (phs%mode)
    case (PHS_MODE_ADDITIONAL_PARTICLE)
      n_in = phs%config%n_in
      phs%p_born = phs%phs_wood_t%p
      phs%q_born = phs%phs_wood_t%q
      phs%p_born_tot (1:n_in) = phs%p_born
      phs%p_born_tot (n_in+1:) = phs%q_born
      call phs%generate_radiation_variables (r_in(phs%n_r_born+1:phs%n_r_born+3))
    case (PHS_MODE_COLLINEAR_REMNANT)
      call phs%compute_isr_kinematics (r_in(phs%n_r_born+1))
      phs%r_isr = r_in(phs%n_r_born+1)
    end select
  end if
end subroutine phs_fks_evaluate_selected_channel

<phs fks: phs fks: TBP>+≡
procedure :: evaluate_other_channels => phs_fks_evaluate_other_channels

<phs fks: procedures>+≡
subroutine phs_fks_evaluate_other_channels (phs, c_in)
  class(phs_fks_t), intent(inout) :: phs
  integer, intent(in) :: c_in
  call phs%phs_wood_t%evaluate_other_channels (c_in)
  phs%r_defined = .true.
end subroutine phs_fks_evaluate_other_channels

<phs fks: phs fks: TBP>+≡
procedure :: get_mcpair => phs_fks_get_mcpair

<phs fks: procedures>+≡
subroutine phs_fks_get_mcpair (phs, c, r)
  class(phs_fks_t), intent(in) :: phs
  integer, intent(in) :: c
  real(default), dimension(:), intent(out) :: r
  r(1:phs%n_r_born) = phs%r(1:phs%n_r_born,c)
  select case (phs%mode)
  case (PHS_MODE_ADDITIONAL_PARTICLE)
    r(phs%n_r_born+1:) = phs%r_real
  case (PHS_MODE_COLLINEAR_REMNANT)
    r(phs%n_r_born+1:) = phs%r_isr
  end select
end subroutine phs_fks_get_mcpair

```

```

<phs fks: phs fks: TBP>+≡
  procedure :: get_real_kinematics => phs_fks_get_real_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_get_real_kinematics (phs, xit, y, phi, xi_max, jac, jac_rand)
    class(phs_fks_t), intent(inout) :: phs
    real(default), intent(out), dimension(:), allocatable :: xi_max
    real(default), intent(out) :: xit
    real(default), intent(out), dimension(:), allocatable :: y
    real(default), intent(out) :: phi
    real(default), intent(out), dimension(3) :: jac
    real(default), intent(out), dimension(:), allocatable :: jac_rand
    associate (real_kinematics => phs%real_kinematics)
      xit = real_kinematics%xi_tilde
      y = real_kinematics%y
      phi = real_kinematics%phi
      xi_max = real_kinematics%xi_max
      jac = real_kinematics%jac(1)%jac
      jac_rand = real_kinematics%jac_rand
    end associate
  end subroutine phs_fks_get_real_kinematics

<phs fks: phs fks: TBP>+≡
  procedure :: set_beam_energy => phs_fks_set_beam_energy

<phs fks: procedures>+≡
  subroutine phs_fks_set_beam_energy (phs)
    class(phs_fks_t), intent(inout) :: phs
    call phs%generator%set_beam_energy (phs%config%sqrts)
    phs%isr_kinematics%beam_energy = phs%config%sqrts/2
  end subroutine phs_fks_set_beam_energy

<phs fks: phs fks: TBP>+≡
  procedure :: set_emitters => phs_fks_set_emitters

<phs fks: procedures>+≡
  subroutine phs_fks_set_emitters (phs, emitters)
    class(phs_fks_t), intent(inout) :: phs
    integer, intent(in), dimension(:), allocatable :: emitters
    call phs%generator%set_emitters (emitters)
  end subroutine phs_fks_set_emitters

<phs fks: phs fks: TBP>+≡
  procedure :: setup_masses => phs_fks_setup_masses

<phs fks: procedures>+≡
  subroutine phs_fks_setup_masses (phs, n_tot)
    class(phs_fks_t), intent(inout) :: phs
    integer, intent(in) :: n_tot
    call phs%generator%setup_masses (n_tot)
  end subroutine phs_fks_setup_masses

<phs fks: phs fks: TBP>+≡
  procedure :: set_mass_info => phs_fks_set_mass_info

```

```

<phs fks: procedures>+≡
  subroutine phs_fks_set_mass_info (phs, massive)
    class(phs_fks_t), intent(inout) :: phs
    logical, dimension(:), allocatable :: massive
    phs%generator%is_massive = massive
  end subroutine phs_fks_set_mass_info

<phs fks: phs fks: TBP>+≡
  procedure :: set_singular_jacobian => phs_fks_set_singular_jacobian

<phs fks: procedures>+≡
  subroutine phs_fks_set_singular_jacobian (phs, value)
    class(phs_fks_t), intent(inout) :: phs
    logical, intent(in) :: value
    phs%generator%singular_jacobian = value
  end subroutine phs_fks_set_singular_jacobian

<phs fks: phs fks: TBP>+≡
  procedure :: get_born_momenta => phs_fks_get_born_momenta

<phs fks: procedures>+≡
  subroutine phs_fks_get_born_momenta (phs, p)
    class(phs_fks_t), intent(inout) :: phs
    type(vector4_t), intent(out), dimension(:) :: p
    select case (phs%mode)
    case (PHS_MODE_ADDITIONAL_PARTICLE)
      p(1:phs%config%n_in) = phs%p_born
      p(phs%config%n_in+1:) = phs%q_born
    case (PHS_MODE_COLLINEAR_REMNANT)
      p(1:phs%config%n_in) = phs%phs_wood_t%p
      p(phs%config%n_in+1:) = phs%phs_wood_t%q
    end select
  end subroutine phs_fks_get_born_momenta

<phs fks: phs fks: TBP>+≡
  procedure :: get_outgoing_momenta => phs_fks_get_outgoing_momenta

<phs fks: procedures>+≡
  subroutine phs_fks_get_outgoing_momenta (phs, q)
    class(phs_fks_t), intent(in) :: phs
    type(vector4_t), intent(out), dimension(:) :: q
    select case (phs%mode)
    case (PHS_MODE_ADDITIONAL_PARTICLE)
      q = phs%q_real
    case (PHS_MODE_COLLINEAR_REMNANT)
      q = phs%phs_wood_t%q
    end select
  end subroutine phs_fks_get_outgoing_momenta

<phs fks: phs fks: TBP>+≡
  procedure :: get_incoming_momenta => phs_fks_get_incoming_momenta

```

```

<phs fks: procedures>+≡
  subroutine phs_fks_get_incoming_momenta (phs, p)
    class(phs_fks_t), intent(in) :: phs
    type(vector4_t), intent(inout), dimension(:), allocatable :: p
    p = phs%p_real
  end subroutine phs_fks_get_incoming_momenta

<phs fks: phs fks: TBP>+≡
  procedure :: display_kinematics => phs_fks_display_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_display_kinematics (phs)
    class(phs_fks_t), intent(in) :: phs
    !    call phs%counter%display ()
  end subroutine phs_fks_display_kinematics

<phs fks: phs fks: TBP>+≡
  procedure :: setup_generator_kinematics => phs_fks_setup_generator_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_setup_generator_kinematics (phs)
    class(phs_fks_t), intent(inout), target :: phs
    phs%generator%real_kinematics => phs%real_kinematics
    phs%generator%isr_kinematics => phs%isr_kinematics
    phs%generator%massive_phsp = phs%massive_phsp
  end subroutine phs_fks_setup_generator_kinematics

<phs fks: phs fks: TBP>+≡
  procedure :: generate_radiation_variables => &
    phs_fks_generate_radiation_variables

<phs fks: procedures>+≡
  subroutine phs_fks_generate_radiation_variables (phs, r_in)
    class(phs_fks_t), intent(inout) :: phs
    real(default), intent(in), dimension(:) :: r_in
    if (size (r_in) /= 3) call msg_fatal &
      ("Real kinematics need to be generated using three random numbers!")
    call phs%generator%generate_radiation_variables (r_in, phs%p_born_tot)
    phs%r_real = r_in
  end subroutine phs_fks_generate_radiation_variables

```

25.7.1 Creation of the real phase space - FSR

At this point, the Born phase space has been generated, as well as the three random variables ξ , y and ϕ . The question is how the real phase space is generated for a final-state emission configuration. We work with two different sets of momenta, the Born configuration $\{\bar{k}_\oplus, \bar{k}_\ominus, \bar{k}_1, \dots, \bar{k}_n\}$ and the real configuration $\{k_\oplus, k_\ominus, k_1, \dots, k_n, k_{n+1}\}$. We define the momentum of the emitter to be on the n -th position and the momentum of the radiated particle to be at position $n+1$. The magnitude of the spatial component of \mathbf{k} is denoted by \underline{k} .

For final-state emissions, it is $\bar{k}_\oplus = k_\oplus$ and $\bar{k}_\ominus = k_\ominus$. Thus, the center-of-mass systems coincide and it is

$$q = \sum_{i=1}^n \bar{k}_i = \sum_{i=1}^{n+1} k_i, \quad (25.11)$$

with $\vec{q} = 0$ and $q^2 = (q^0)^2$.

We want to construct the real phase space from the Born phase space using three random numbers. They are defined as follows:

- $\xi = \frac{2k_{n+1}^0}{\sqrt{s}} \in [0, \xi_{max}]$, where k_{n+1} denotes the four-momentum of the radiated particle.
- $y = \cos \theta = \frac{\vec{k}_n \cdot \vec{k}_{n+1}}{k_n k_{n+1}}$ is the splitting angle.
- The angle between the two splitting particles in the transversal plane, $\phi \in [0, 2\pi]$.

Further, $k_{rec} = \sum_{i=1}^{n-1} k_i$ denotes the sum of all recoiling momenta.

$\langle phs\ fks: phs\ fks\ generator: TBP \rangle \equiv$

procedure :: generate_fsr => phs_fks_generator_generate_fsr

$\langle phs\ fks: procedures \rangle + \equiv$

```
subroutine phs_fks_generator_generate_fsr (generator, emitter, p_born, p_real)
  !!! Important: Momenta must be input in the center-of-mass frame
  class(phs_fks_generator_t), intent(inout) :: generator
  integer, intent(in) :: emitter
  type(vector4_t), intent(in), dimension(:) :: p_born
  type(vector4_t), intent(out), dimension(:), allocatable :: p_real
  integer :: nlegborn, nlegreal
  type(vector4_t) :: q
  real(default) :: q0, q2, uk_np1, uk_n
  real(default) :: uk_rec, k_rec0
  type(vector3_t) :: k_n_born, k
  real(default) :: uk_n_born
  real(default) :: uk, k2, k0_n
  real(default) :: cpsi, beta
  type(vector3_t) :: vec, vec_orth
  type(lorentz_transformation_t) :: rot, lambda
  integer :: i
  real(default) :: xi, y, phi

  associate (rad_var => generator%real_kinematics)
    xi = rad_var%xi_tilde
    if (rad_var%supply_xi_max) xi = xi*rad_var%xi_max(emitter)
    y = rad_var%y(emitter)
    phi = rad_var%phi
  end associate
  nlegborn = size (p_born)
  nlegreal = nlegborn+1
  if (emitter <= 2 .or. emitter > nlegborn) then
    call msg_fatal ("Generate FSR phase space: Invalid emitter!")
  end if
```

```

allocate (p_real (nlegreal))

p_real(1) = p_born(1)
p_real(2) = p_born(2)
q = p_born(1) + p_born(2)
q0 = q%p(0)
q2 = q**2
generator%real_kinematics%cms_energy2 = q2

generator%E_gluon = q0*xi/2
uk_np1 = generator%E_gluon
k_n_born = p_born(emitter)%p(1:3)
uk_n_born = k_n_born**1

generator%mrec2 = (q-p_born(emitter))**2
if (generator%is_massive(emitter)) then
    call generator%compute_emitter_kinematics (emitter, k0_n, uk_n, uk)
else
    call generator%compute_emitter_kinematics (emitter, uk_n, uk)
    generator%real_kinematics%y_soft = y
    k0_n = uk_n
end if

vec = uk_n / uk_n_born * k_n_born
vec_orth = create_orthogonal (vec)
p_real(emitter)%p(0) = k0_n
p_real(emitter)%p(1:3) = vec%p(1:3)
cpsi = (uk_n**2 + uk**2 - uk_np1**2) / (2*(uk_n * uk))
!!! This is to catch the case where cpsi = 1, but numerically
!!! turns out to be slightly larger than 1.
call check_cpsi_bound (cpsi)
rot = rotation (cpsi, -sqrt (1._default-cpsi**2), vec_orth)
p_real(emitter) = rot*p_real(emitter)
vec = uk_np1 / uk_n_born * k_n_born
vec_orth = create_orthogonal (vec)
p_real(nlegreal)%p(0) = uk_np1
p_real(nlegreal)%p(1:3) = vec%p(1:3)
cpsi = (uk_np1**2 + uk**2 - uk_n**2) / (2*(uk_np1 * uk))
call check_cpsi_bound (cpsi)
rot = rotation (cpsi, sqrt (1._default-cpsi**2), vec_orth)
p_real(nlegreal) = rot*p_real(nlegreal)

```

Construction of the recoiling momenta. The reshuffling of momenta must not change the invariant mass of the recoiling system, which means $k_{\text{rec}}^2 = k_{\text{rec}}^{-2}$. Therefore, the momenta are related by a boost, $\bar{k}_i = \Lambda k_i$. The boost parameter is

$$\beta = \frac{q^2 - (k_{\text{rec}}^0 + \underline{k}_{\text{rec}})^2}{q^2 + (k_{\text{rec}}^0 + \underline{k}_{\text{rec}})^2}$$

```

<phs fks: procedures>+≡
    k_rec0 = q0 - p_real(emitter)%p(0) - p_real(nlegreal)%p(0)
    uk_rec = sqrt (k_rec0**2 - generator%mrec2)
    if (generator%is_massive(emitter)) then
        beta = compute_beta (q2, k_rec0, uk_rec, &
            p_born(emitter)%p(0), uk_n_born)
    end if

```

```

else
  beta = compute_beta (q2, k_rec0, uk_rec)
end if
k = p_real(emitter)%p(1:3) + p_real(nlegreal)%p(1:3)
vec%p(1:3) = 1/uk*k%p(1:3)
lambda = boost (beta/sqrt(1-beta**2), vec)
do i = 3, nlegborn
  if (i /= emitter) then
    p_real(i) = lambda * p_born(i)
  end if
end do
vec%p(1:3) = p_born(emitter)%p(1:3)/uk_n_born
rot = rotation (cos(phi), sin(phi), vec)
p_real(nlegreal) = rot * p_real(nlegreal)
p_real(emitter) = rot * p_real(emitter)

```

The factor $\frac{q^2}{(4\pi)^3}$ is not included here since it is supplied during phase space generation. Also, we already divide by ξ .

```

<phs fks: procedures>+≡
  associate (jac => generator%real_kinematics%jac(emitter))
    if (generator%is_massive(emitter)) then
      jac%jac(1) = jac%jac(1)*4/q0/uk_n_born/xi
    else
      k2 = 2*uk_n*uk_np1*(1-y)
      jac%jac(1) = uk_n**2/uk_n_born / (uk_n - k2/(2*q0))
    end if
    !!! Soft jacobian
    jac%jac(2) = 1._default
    !!! Collinear jacobian
    jac%jac(3) = 1-xi/2*q0/uk_n_born
  end associate
contains
  subroutine check_cpsi_bound (cpsi)
    real(default), intent(inout) :: cpsi
    if (cpsi > 1._default) cpsi = 1._default
  end subroutine check_cpsi_bound
end subroutine phs_fks_generator_generate_fsr

<phs fks: phs fks: TBP>+≡
  procedure :: generate_fsr => phs_fks_generate_fsr

<phs fks: procedures>+≡
  subroutine phs_fks_generate_fsr (phs, emitter, p_born, p_real)
    class(phs_fks_t), intent(inout) :: phs
    integer, intent(in) :: emitter
    type(vector4_t), intent(in), dimension(:) :: p_born
    type(vector4_t), intent(out), dimension(:), allocatable :: p_real
    call phs%generator%generate_fsr (emitter, p_born, p_real)
  end subroutine phs_fks_generate_fsr

<phs fks: phs fks generator: TBP>+≡
  generic :: compute_emitter_kinematics => &
    compute_emitter_kinematics_massless, &
    compute_emitter_kinematics_massive

```



```

procedure :: compute_emitter_kinematics_massless => &
    phs_fks_generator_compute_emitter_kinematics_massless
procedure :: compute_emitter_kinematics_massive => &
    phs_fks_generator_compute_emitter_kinematics_massive
<phs fks: procedures>+≡
subroutine phs_fks_generator_compute_emitter_kinematics_massless &
    (generator, em, uk_em, uk)
    class(phs_fks_generator_t), intent(inout) :: generator
    integer, intent(in) :: em
    real(default), intent(out) :: uk_em, uk
    real(default) :: y, k0_np1, q0, q2

    y = generator%real_kinematics%y(em)
    k0_np1 = generator%E_gluon
    q0 = generator%E_beam_tot; q2 = q0**2

    uk_em = (q2 - generator%mrec2 - 2*q0*k0_np1) / (2*(q0 - k0_np1*(1-y)))
    uk = sqrt(uk_em**2 + k0_np1**2 + 2*uk_em*k0_np1*y)
end subroutine phs_fks_generator_compute_emitter_kinematics_massless

subroutine phs_fks_generator_compute_emitter_kinematics_massive &
    (generator, em, k0_em, uk_em, uk)
    class(phs_fks_generator_t), intent(inout) :: generator
    integer, intent(in) :: em
    real(default), intent(inout) :: k0_em, uk_em, uk
    real(default) :: y, k0_np1, q0, q2, mrec2, m2
    real(default) :: k0_rec_max, k0_em_max, k0_rec, uk_rec
    real(default) :: z, z1, z2

    y = generator%real_kinematics%y(em)
    k0_np1 = generator%E_gluon
    q0 = generator%E_beam_tot; q2 = q0**2
    mrec2 = generator%mrec2
    m2 = generator%m2(em)

    k0_rec_max = (q2-m2+mrec2)/(2*q0)
    k0_em_max = (q2+m2-mrec2)/(2*q0)
    z1 = (k0_rec_max+sqrt(k0_rec_max**2-mrec2))/q0
    z2 = (k0_rec_max-sqrt(k0_rec_max**2-mrec2))/q0
    z = z2 - (z2-z1)*(1+y)/2
    k0_em = k0_em_max - k0_np1*z
    k0_rec = q0 - k0_np1 - k0_em
    uk_em = sqrt(k0_em**2-m2)
    uk_rec = sqrt(k0_rec**2 - mrec2)
    uk = uk_rec
    generator%real_kinematics%cms_energy2 = q2
    generator%real_kinematics%jac(em)%jac = q0*(z1-z2)/4*k0_np1
    generator%real_kinematics%y_soft = &
        (2*q2*z-q2-mrec2+m2)/(sqrt(k0_em_max**2-m2)*q0)/2
end subroutine phs_fks_generator_compute_emitter_kinematics_massive

<phs fks: procedures>+≡
function compute_beta_massless (q2, k0_rec, uk_rec) result (beta)

```

```

real(default), intent(in) :: q2, k0_rec, uk_rec
real(default) :: beta
beta = (q2 - (k0_rec + uk_rec)**2) / (q2 + (k0_rec + uk_rec)**2)
end function compute_beta_massless

function compute_beta_massive (q2, k0_rec, uk_rec, &
                               k0_em_born, uk_em_born) result (beta)
real(default), intent(in) :: q2, k0_rec, uk_rec
real(default), intent(in) :: k0_em_born, uk_em_born
real(default) :: beta
real(default) :: k0_rec_born, uk_rec_born, alpha
k0_rec_born = sqrt(q2) - k0_em_born
uk_rec_born = uk_em_born
alpha = (k0_rec+uk_rec)/(k0_rec_born+uk_rec_born)
beta = (1-alpha**2)/(1+alpha**2)
end function compute_beta_massive

```

The momentum of the radiated particle is computed according to

$$\underline{k}_n = \frac{q^2 - M_{\text{rec}}^2 - 2q^0 \underline{k}_{n+1}}{2(q^0 - \underline{k}_{n+1}(1 - y))}, \quad (25.12)$$

with $k = k_n + k_{n+1}$ and $M_{\text{rec}}^2 = k_{\text{rec}}^2 = (q - k)^2$. Because of $\bar{\mathbf{k}}_n \parallel \mathbf{k}_n + \mathbf{k}_{n+1}$ we find $M_{\text{rec}}^2 = (q - \bar{k}_n)^2$. Equation ?? follows from the fact that $(\mathbf{k} - \mathbf{k}_n)^2 = \mathbf{k}_{n+1}^2$, which is equivalent to $\mathbf{k}_n \cdot \mathbf{k} = \frac{1}{2}(\underline{k}_n^2 + \underline{k}^2 - \underline{k}_{n+1}^2)$. \mathbf{k}_n and \mathbf{k}_{n+1} are obtained by first setting up vectors parallel to $\bar{\mathbf{k}}_n$,

$$\mathbf{k}'_n = \underline{k}_n \frac{\bar{\mathbf{k}}_n}{\underline{k}_n}, \quad \mathbf{k}'_{n+1} = \underline{k}_{n+1} \frac{\bar{\mathbf{k}}_n}{\underline{k}_n},$$

and then rotating these vectors by an amount of $\cos \psi_n = \frac{\mathbf{k}_n \cdot \mathbf{k}}{\underline{k}_n \underline{k}}$. The emitted particle cannot have more momentum than the emitter has in the Born phase space. Thus, there is an upper bound for ξ , determined by the condition $k_{n+1}^0 = \underline{k}_n$, which is equal to

$$\xi_{\text{max}} = \frac{2}{\underline{k}_n} q^0.$$

(phs fks: procedures)+≡

```

pure function get_xi_max_fsr_massless (p_born, emitter) result (xi_max)
type(vector4_t), intent(in), dimension(:) :: p_born
integer, intent(in) :: emitter
real(default) :: xi_max
real(default) :: uk_n_born, q0
q0 = vector4_get_component (p_born(1) + p_born(2), 0)
uk_n_born = space_part_norm (p_born(emitter))
xi_max = 2*uk_n_born / q0
end function get_xi_max_fsr_massless

```

(phs fks: procedures)+≡

```

pure function get_xi_max_fsr_massive (p_born, emitter, m2, y) result (xi_max)
type(vector4_t), intent(in), dimension(:) :: p_born
integer, intent(in) :: emitter

```

```

real(default), intent(in) :: m2, y
real(default) :: xi_max
real(default) :: q0, mrec2, k0_rec_max
real(default) :: z, z1, z2
real(default) :: k_np1_max
q0 = 2*p_born(1)%p(0)
associate (p => p_born(emitter)%p)
  mrec2 = (q0-p(0))**2 - p(1)**2 - p(2)**2 - p(3)**2
end associate
k0_rec_max = (q0**2-m2+mrec2)/(2*q0)
z1 = (k0_rec_max+sqrt(k0_rec_max**2-mrec2))/q0
z2 = (k0_rec_max-sqrt(k0_rec_max**2-mrec2))/q0
z = z2 - (z2-z1)*(1+y)/2
k_np1_max = -(q0**2*z**2 - 2*q0*k0_rec_max*z + mrec2)/(2*q0*z*(1-z))
xi_max = 2*k_np1_max/q0
end function get_xi_max_fsr_massive

```

<phs fks: procedures>+≡

```

function get_xi_max_isr (xb, y) result (xi_max)
  real(default), dimension(2), intent(in) :: xb
  real(default), intent(in) :: y
  real(default) :: xb_plus, xb_minus
  real(default) :: xi_max
  real(default) :: plus_val, minus_val

  xb_plus = xb(1); xb_minus = xb(2)

  plus_val = 2*(1+y)*xb_plus**2 / &
    (sqrt ((1+xb_plus**2)**2*(1-y)**2 + 16*y*xb_plus**2) &
    + (1-y)*(1-xb_plus**2))
  minus_val = 2*(1-y)*xb_minus**2 / &
    (sqrt ((1+xb_minus**2)**2*(1+y)**2 - 16*y*xb_minus**2) &
    + (1-y)*(1-xb_minus**2))
  xi_max = one - max (plus_val, minus_val)
end function get_xi_max_isr

```

25.7.2 Creation of the real phase space - ISR

<phs fks: phs fks: TBP>+≡

```

procedure :: generate_isr => phs_fks_generate_isr

```

<phs fks: procedures>+≡

```

subroutine phs_fks_generate_isr &
  (phs, emitter, p_born, p_real)
  class(phs_fks_t), intent(inout) :: phs
  integer, intent(in) :: emitter
  type(vector4_t), intent(in), dimension(:) :: p_born
  type(vector4_t), intent(out), dimension(:), allocatable :: p_real
  call phs%generator%generate_isr (p_born, p_real)
end subroutine phs_fks_generate_isr

```

<phs fks: phs fks generator: TBP>+≡

```

procedure :: generate_isr => phs_fks_generator_generate_isr

```

(phs fks: procedures)+≡

```

subroutine phs_fks_generator_generate_isr &
  (generator, p_born, p_real)
  !!! Important: Import momenta in the lab frame
  class(phs_fks_generator_t), intent(inout) :: generator
  type(vector4_t), intent(in) , dimension(:) :: p_born
  type(vector4_t), intent(out), dimension(:), allocatable :: p_real
  real(default) :: xi_max, xi, y, phi
  integer :: nlegborn, nlegreal
  real(default) :: sqrts_real
  real(default) :: k0_np1
  type(lorentz_transformation_t) :: lambda_transv, lambda_longit, lambda_longit_inv
  real(default) :: x_plus, x_minus, xb_plus, xb_minus
  integer :: i

  associate (rad_var => generator%real_kinematics)
    xi_max = rad_var%xi_max(1)
    xi = rad_var%xi_tilde * xi_max
    y = rad_var%y(1)
    phi = rad_var%phi
    rad_var%y_soft = y
  end associate
  nlegborn = size (p_born)
  nlegreal = nlegborn+1
  generator%isr_kinematics%sqrts_born = sqrt ((p_born(1) + p_born(2))**2)
  allocate (p_real (nlegreal))

  !!! Initial state real momenta
  xb_plus = generator%isr_kinematics%x(1)
  xb_minus = generator%isr_kinematics%x(2)
  x_plus = xb_plus/sqrt(1-xi) * sqrt ((2-xi*(1-y)) / (2-xi*(1+y)))
  x_minus = xb_minus/sqrt(1-xi) * sqrt ((2-xi*(1+y)) / (2-xi*(1-y)))
  p_real(1) = x_plus/xb_plus * p_born(1)
  p_real(2) = x_minus/xb_minus * p_born(2)

  !!! Create radiation momentum
  sqrts_real = generator%isr_kinematics%sqrts_born / (1-xi)
  k0_np1 = sqrts_real*xi/2
  p_real(nlegreal)%p(0) = k0_np1
  p_real(nlegreal)%p(1) = k0_np1*sqrt(1-y**2)*sin(phi)
  p_real(nlegreal)%p(2) = k0_np1*sqrt(1-y**2)*cos(phi)
  p_real(nlegreal)%p(3) = k0_np1*y

  lambda_longit = create_longitudinal_boost (p_real, inverse = .false.)
  p_real(nlegreal) = lambda_longit * p_real(nlegreal)

  lambda_longit = create_longitudinal_boost (p_born, inverse = .false.)
  forall (i=3:nlegborn) &
    p_real(i) = lambda_longit * p_born(i)

  lambda_transv = create_transversal_boost (p_real(nlegreal), xi, sqrts_real)
  forall (i=3:nlegborn) &
    p_real(i) = lambda_transv * p_real(i)

```

```

lambda_longit_inv = create_longitudinal_boost (p_real, inverse = .true.)
forall (i=3:nlegborn) &
    p_real(i) = lambda_longit_inv * p_real(i)

contains
function create_longitudinal_boost (p, inverse) result (lambda)
    type(vector4_t), intent(in), dimension(:) :: p
    logical, intent(in) :: inverse
    type(lorentz_transformation_t) :: lambda
    type(vector3_t) :: beta_vec
    real(default) :: beta_gamma
    beta_vec = (p(1)%p(1:3) + p(2)%p(1:3)) / (p(1)%p(0) + p(2)%p(0))
    beta_gamma = beta_vec**1 / sqrt (1-beta_vec**2)
    beta_vec = beta_vec / beta_gamma**1
    if (inverse) beta_gamma = -beta_gamma
    lambda = boost (-beta_gamma, beta_vec)
end function create_longitudinal_boost

function create_transversal_boost (p_rad, xi, sqrts_real) result (lambda)
    type(vector4_t), intent(in) :: p_rad
    real(default), intent(in) :: xi, sqrts_real
    type(lorentz_transformation_t) :: lambda
    type(vector3_t) :: vec_transverse
    real(default) :: pt2, beta, beta_gamma
    pt2 = transverse_part(p_rad)**2
    beta = 1.0 / sqrt (1 + sqrts_real**2 * (1-xi)/pt2)
    beta_gamma = beta / sqrt (1-beta**2)
    vec_transverse%p(1:2) = p_rad%p(1:2)
    vec_transverse%p(3) = 0._default
    call normalize (vec_transverse)
    lambda = boost (-beta_gamma, vec_transverse)
end function create_transversal_boost
end subroutine phs_fks_generator_generate_isr

<phs fks: phs fks generator: TBP>+≡
    procedure :: set_beam_energy => phs_fks_generator_set_beam_energy

<phs fks: procedures>+≡
    pure subroutine phs_fks_generator_set_beam_energy (generator, E_beam)
        class(phs_fks_generator_t), intent(inout) :: generator
        real(default), intent(in) :: E_beam
        generator%E_beam_tot = E_beam
    end subroutine phs_fks_generator_set_beam_energy

<phs fks: phs fks generator: TBP>+≡
    procedure :: set_emitters => phs_fks_generator_set_emitters

<phs fks: procedures>+≡
    subroutine phs_fks_generator_set_emitters (generator, emitters)
        class(phs_fks_generator_t), intent(inout) :: generator
        integer, intent(in), dimension(:), allocatable :: emitters
        generator%emitters = emitters
    end subroutine phs_fks_generator_set_emitters

```

```

<phs fks: phs fks generator: TBP>+≡
  procedure :: setup_masses => phs_fks_generator_setup_masses

<phs fks: procedures>+≡
  subroutine phs_fks_generator_setup_masses (generator, n_tot)
    class (phs_fks_generator_t), intent(inout) :: generator
    integer, intent(in) :: n_tot
    if (.not. allocated (generator%m2)) then
      allocate (generator%is_massive (n_tot))
      allocate (generator%m2 (n_tot))
      generator%is_massive = .false.
      generator%m2 = 0._default
    end if
  end subroutine phs_fks_generator_setup_masses

<phs fks: phs fks generator: TBP>+≡
  procedure :: set_isr_kinematics => phs_fks_generator_set_isr_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_generator_set_isr_kinematics (generator, p_born)
    class(phs_fks_generator_t), intent(inout) :: generator
    type(vector4_t), dimension(:), intent(in) :: p_born
    generator%isr_kinematics%x = space_part_norm (p_born(1:2)) / (generator%E_beam_tot/2)
  end subroutine phs_fks_generator_set_isr_kinematics

<phs fks: phs fks generator: TBP>+≡
  procedure :: setup_real_kinematics => phs_fks_generator_setup_real_kinematics

<phs fks: procedures>+≡
  subroutine phs_fks_generator_setup_real_kinematics (generator, real_kinematics)
    class(phs_fks_generator_t), intent(inout) :: generator
    type(real_kinematics_t), intent(in), pointer :: real_kinematics
    generator%real_kinematics => real_kinematics
  end subroutine phs_fks_generator_setup_real_kinematics

<phs fks: phs fks generator: TBP>+≡
  procedure :: generate_radiation_variables => &
    phs_fks_generator_generate_radiation_variables

<phs fks: procedures>+≡
  subroutine phs_fks_generator_generate_radiation_variables &
    (generator, r_in, p_born)
    class(phs_fks_generator_t), intent(inout) :: generator
    real(default), intent(in), dimension(:) :: r_in
    type(vector4_t), intent(in), dimension(:) :: p_born
    integer :: em

!   call generator%set_beam_energy (p_born(1)%p(0) + p_born(2)%p(0))
  if (any (generator%emitters <= 2)) call generator%set_isr_kinematics (p_born)
  associate (rad_var => generator%real_kinematics)
    rad_var%jac_rand = 1.0
    call generator%compute_xi_tilde (r_in(I_XI))
    rad_var%phi = r_in (I_PHI)*twopi
    rad_var%jac_rand = rad_var%jac_rand*twopi
  end associate

```

```

call generator%compute_y (r_in(I_Y), p_born)
do em = 1, size (p_born)
  if (any (generator%emitters == em)) then
    if (generator%is_massive(em)) then
      if (em <= 2) then
        call msg_fatal ("Massive emitters incompatible with IS phase space")
      else
        rad_var%xi_max (em) = get_xi_max_fsr &
          (p_born, em, generator%m2(em), rad_var%y(em))
      end if
    else
      if (em <= 2) then
        rad_var%xi_max(em) = get_xi_max_isr (generator%isr_kinematics%x, rad_var%y(em))
      else
        rad_var%xi_max(em) = get_xi_max_fsr (p_born, em)
      end if
    end if
  end if
end do
end associate
end subroutine phs_fks_generator_generate_radiation_variables

```

<phs fks: phs fks generator: TBP>+≡

```

  procedure :: compute_y => phs_fks_generator_compute_y

```

<phs fks: procedures>+≡

```

subroutine phs_fks_generator_compute_y (generator, r_y, p)
  class(phs_fks_generator_t), intent(inout) :: generator
  real(default), intent(in) :: r_y
  type(vector4_t), dimension(:) :: p
  integer :: em
  real(default) :: beta
  associate (rad_var => generator%real_kinematics)
    do em = 1, size (p)
      if (any (generator%emitters == em)) then
        if (generator%is_massive (em)) then
          generator%m2(em) = p(em)**2
          beta = beta_emitter (generator%E_beam_tot, p(em))
          rad_var%y(em) = 1.0/beta * (1-(1+beta) * &
            exp(-r_y*log((1+beta)/(1-beta))))
          rad_var%jac_rand(em) = rad_var%jac_rand(em) * &
            (1-beta*rad_var%y(em))*log((1+beta)/(1-beta))/beta
        else
          rad_var%y(em) = (1-2*r_y)*generator%y_max
          rad_var%jac_rand(em) = rad_var%jac_rand(em)*3*(1-rad_var%y(em)**2)
          rad_var%y(em) = 1.5_default*(rad_var%y(em) - rad_var%y(em)**3/3)
        end if
      end if
    end do
  end associate
contains
  pure function beta_emitter (q0, p) result (beta)
    real(default), intent(in) :: q0
    type(vector4_t), intent(in) :: p

```

```

    real(default) :: beta
    real(default) :: m2, mrec2, k0_max
    m2 = p**2
    mrec2 = (q0-p%p(0))**2 - p%p(1)**2 - p%p(2)**2 - p%p(3)**2
    k0_max = (q0**2-mrec2+m2)/(2*q0)
    beta = sqrt(1-m2/k0_max**2)
end function beta_emitter
end subroutine phs_fks_generator_compute_y

```

<phs fks: phs fks generator: TBP>+≡

```

    procedure :: compute_xi_tilde => phs_fks_generator_compute_xi_tilde

```

<phs fks: procedures>+≡

```

    pure subroutine phs_fks_generator_compute_xi_tilde (generator, r)
    class(phs_fks_generator_t), intent(inout) :: generator
    real(default), intent(in) :: r
    associate (rad_var => generator%real_kinematics)
        if (generator%singular_jacobian) then
            rad_var%xi_tilde = (1-generator%xi_min) - (1-r)**2*(1-2*generator%xi_min)
            rad_var%jac_rand = rad_var%jac_rand * 2*(1-r)*(1-2*generator%xi_min)
        else
            rad_var%xi_tilde = generator%xi_min + r*(1-generator%xi_min)
            rad_var%jac_rand = rad_var%jac_rand *(1-generator%xi_min)
        end if
    end associate
end subroutine phs_fks_generator_compute_xi_tilde

```

<phs fks: phs fks generator: TBP>+≡

```

    procedure :: generate_fsr_from_x => phs_fks_generator_generate_fsr_from_x

```

<phs fks: procedures>+≡

```

    function phs_fks_generator_generate_fsr_from_x (generator, &
        r_in, emitter, p_born) result (p_real)
    type(vector4_t), dimension(:), allocatable :: p_real
    class(phs_fks_generator_t), intent(inout) :: generator
    real(default), intent(in), dimension(:) :: r_in
    integer, intent(in) :: emitter
    type(vector4_t), intent(in), dimension(:) :: p_born

    call generator%generate_radiation_variables (r_in, p_born)
    call generator%generate_fsr (emitter, p_born, p_real)
end function phs_fks_generator_generate_fsr_from_x

```

<phs fks: phs fks generator: TBP>+≡

```

    procedure :: generate_fsr_from_xi_and_y => &
        phs_fks_generator_generate_fsr_from_xi_and_y

```

<phs fks: procedures>+≡

```

    function phs_fks_generator_generate_fsr_from_xi_and_y (generator, xi, y, &
        phi, emitter, p_born) result (p_real)
    class(phs_fks_generator_t), intent(inout) :: generator
    real(default), intent(in) :: xi, y, phi
    integer, intent(in) :: emitter
    type(vector4_t), intent(in), dimension(:) :: p_born

```



```

type(vector4_t), dimension(:), allocatable :: p_real
associate (rad_var => generator%real_kinematics)
    rad_var%supply_xi_max = .false.
    rad_var%xi_tilde = xi
    rad_var%y(emitter) = y
    rad_var%phi = phi
end associate
call generator%set_beam_energy (p_born(1)%p(0) + p_born(2)%p(0))
call generator%generate_fsr (emitter, p_born, p_real)
end function phs_fks_generator_generate_fsr_from_xi_and_y

```

<phs fks: phs fks generator: TBP>+≡

```

procedure :: get_radiation_variables => &
    phs_fks_generator_get_radiation_variables

```

<phs fks: procedures>+≡

```

pure subroutine phs_fks_generator_get_radiation_variables (generator, &
    emitter, xi, y, phi)
class(phs_fks_generator_t), intent(in) :: generator
integer, intent(in) :: emitter
real(default), intent(out) :: xi, y
real(default), intent(out), optional :: phi
associate (rad_var => generator%real_kinematics)
    xi = rad_var%xi_max(emitter) * rad_var%xi_tilde
    y = rad_var%y(emitter)
    if (present (phi)) phi = rad_var%phi
end associate
end subroutine phs_fks_generator_get_radiation_variables

```

<phs fks: phs fks generator: TBP>+≡

```

procedure :: get_jacobian => phs_fks_generator_get_jacobian

```

<phs fks: procedures>+≡

```

subroutine phs_fks_generator_get_jacobian (generator, emitter, jac)
class(phs_fks_generator_t), intent(in) :: generator
integer, intent(in) :: emitter
real(default) :: jac
associate (rad_var => generator%real_kinematics)
    jac = rad_var%jac_rand (emitter) * rad_var%jac(emitter)%jac(1)
end associate
end subroutine phs_fks_generator_get_jacobian

```

<phs fks: phs fks generator: TBP>+≡

```

procedure :: write => phs_fks_generator_write

```

<phs fks: procedures>+≡

```

subroutine phs_fks_generator_write (generator, unit)
class(phs_fks_generator_t), intent(in) :: generator
integer, intent(in), optional :: unit
integer :: u
type(string_t) :: massive_phsp
u = given_output_unit (unit); if (u < 0) return
if (generator%massive_phsp) then
    massive_phsp = " massive "

```

```

else
    massive_phsp = " massless "
end if
write (u, "(A)") char ("This is a generator for a" // massive_phsp // "phase space")
if (associated (generator%real_kinematics)) then
    call generator%real_kinematics%write ()
else
    write (u, "(A)") "Warning: There are no real kinematics associated with this generator"
end if
call write_separator (u)
write (u, "(A,F5.3)") "E_beam_tot: ", generator%E_beam_tot
write (u, "(A,F5.3)") "E_gluon: ", generator%E_gluon
write (u, "(A,F5.3)") "mrec2: ", generator%mrec2
end subroutine phs_fks_generator_write

```

<phs fks: phs fks: TBP>+≡

```

procedure :: compute_isr_kinematics => phs_fks_compute_isr_kinematics

```

<phs fks: procedures>+≡

```

subroutine phs_fks_compute_isr_kinematics (phs, r)
    class(phs_fks_t), intent(inout) :: phs
    real(default), intent(in) :: r
    real(default) :: E_beam
    integer :: em
    type(vector4_t), dimension(2) :: p_in
    E_beam = phs%isr_kinematics%beam_energy
    do em = 1, 2
        p_in(em) = phs%phs_wood_t%p(em)
        phs%isr_kinematics%x(em) = p_in(em)%p(0) / E_beam
        phs%isr_kinematics%z(em) = one - (one-phs%isr_kinematics%x(em))*r
        phs%isr_kinematics%jacobian(em) = phs%isr_kinematics%jacobian(em) * (one-phs%isr_kinematics%z(em))
    end do

    phs%isr_kinematics%sqrts_born = (p_in(1) + p_in(2))*1
end subroutine phs_fks_compute_isr_kinematics

```

25.7.3 Unit tests

<phs fks: public>+≡

```

public :: phs_fks_generator_test

```

<phs fks: procedures>+≡

```

subroutine phs_fks_generator_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    call test(phs_fks_generator_1, "phs_fks_generator_1", &
        "Test the generation of FKS phase spaces", u, results)
    call test(phs_fks_generator_2, "phs_fks_generator_2", &
        "Test the generation of an ISR FKS phase space", u, results)
end subroutine phs_fks_generator_test

```

```

<phs fks: procedures>+≡
subroutine phs_fks_generator_1 (u)
  integer, intent(in) :: u
  type(phs_fks_generator_t) :: generator
  type(vector4_t), dimension(:), allocatable :: p_born
  type(vector4_t), dimension(:), allocatable :: p_real
  integer :: emitter
  real(default) :: x1, x2, x3
  real(default), parameter :: sqrts = 250.0_default
  write (u, "(A)") "* Test output: phs_fks_generator_1"
  write (u, "(A)") "* Purpose: Create massless fsr phase space"
  write (u, "(A)")

  allocate (p_born (4))
  p_born(1)%p(0) = 125.0_default
  p_born(1)%p(1:2) = 0.0_default
  p_born(1)%p(3) = 125.0_default
  p_born(2)%p(0) = 125.0_default
  p_born(2)%p(1:2) = 0.0_default
  p_born(2)%p(3) = -125.0_default
  p_born(3)%p(0) = 125.0_default
  p_born(3)%p(1) = -39.5618_default
  p_born(3)%p(2) = -20.0791_default
  p_born(3)%p(3) = -114.6957_default
  p_born(4)%p(0) = 125.0_default
  p_born(4)%p(1:3) = -p_born(3)%p(1:3)

  call generator%set_beam_energy (sqrts)

  write (u, "(A)") "* Use four-particle phase space containing: "
  call vector4_write_set (p_born, u, testflag = .true.)
  write (u, "(A)") "*****"
  write (u, "(A)")

  x1=0.5_default; x2=0.25_default; x3=0.75_default
  write (u, "(A)" ) "* Use random numbers: "
  write (u, "(A,F3.2,A,F3.2,A,F3.2)") "x1: ", x1, "x2: ", x2, "x3: ", x3
  allocate (generator%real_kinematics)
  associate (rad_var => generator%real_kinematics)
    allocate (rad_var%xi_max(4), rad_var%y(4))
    allocate (rad_var%p_born(4), rad_var%p_real(5))
    allocate (rad_var%jac(4))
    allocate (rad_var%jac_rand(4), rad_var%y_soft(4))
  end associate
  allocate (generator%emitters (2))
  generator%emitters(1) = 3; generator%emitters(2) = 4
  allocate (generator%m2 (4))
  generator%m2 = 0._default
  allocate (generator%is_massive (4))
  generator%is_massive(1:2) = .false.
  generator%is_massive(3:4) = .true.
  call generator%generate_radiation_variables ([x1,x2,x3], p_born)
  write (u, "(A)") &

```

```

        "* With these, the following radiation variables have been produced:"
associate (rad_var => generator%real_kinematics)
    write (u, "(A,F3.2)") "xi_tilde: ", rad_var%xi_tilde
    write (u, "(A,F3.2)") "y: " , rad_var%y(3)
    write (u, "(A,F3.2)") "phi: ", rad_var%phi
end associate
call write_separator (u)
write (u, "(A)") "Produce real momenta: "
emitter = 3
write (u, "(A,I1)") "emitter: ", emitter
call generator%generate_fsr (emitter, p_born, p_real)
call vector4_write_set (p_real, u, testflag = .true.)
call write_separator (u)
write (u, "(A)") &
    "Test direct interface via phs_fks_generator_generate_from_x"
p_real = generator%generate_fsr_from_x ([x1,x2,x3], emitter, p_born)
call vector4_write_set (p_real, u, testflag = .true.)
write (u, "(A)")
write (u, "(A)") "* Test output end: phs_fks_generator_1"

end subroutine phs_fks_generator_1

```

(phs fks: procedures)+≡

```

subroutine phs_fks_generator_2 (u)
    integer, intent(in) :: u
    type(phs_fks_generator_t) :: generator
    type(vector4_t), dimension(:), allocatable :: p_born
    type(vector4_t), dimension(:), allocatable :: p_real
    integer :: emitter
    real(default) :: x1, x2, x3
    real(default), parameter :: sqrts_hadronic = 250.0_default
    write (u, "(A)") "* Test output: phs_fks_generator_1"
    write (u, "(A)") "* Purpose: Create massless ISR phase space"
    write (u, "(A)")

    allocate (p_born (4))
    p_born(1)%p(0) = 114.661_default
    p_born(1)%p(1:2) = 0.0_default
    p_born(1)%p(3) = 114.661_default
    p_born(2)%p(0) = 121.784_default
    p_born(2)%p(1:2) = 0.0_default
    p_born(2)%p(3) = -121.784_default
    p_born(3)%p(0) = 115.148_default
    p_born(3)%p(1) = -46.250_default
    p_born(3)%p(2) = -37.711_default
    p_born(3)%p(3) = 98.478_default
    p_born(4)%p(0) = 121.296_default
    p_born(4)%p(1:2) = -p_born(3)%p(1:2)
    p_born(4)%p(3) = -105.601_default

    allocate (generator%emitters (2))
    allocate (generator%isr_kinematics)
    generator%emitters(1) = 1; generator%emitters(2) = 2

```

```

call generator%set_beam_energy (sqrts_hadronic)
call generator%set_isr_kinematics (p_born)

write (u, "(A)") "* Use four-particle phase space containing: "
call vector4_write_set (p_born, u, testflag = .true.)
write (u, "(A)") "*****"
write (u, "(A)")

x1=0.5_default; x2=0.25_default; x3=0.65_default
write (u, "(A)" ) "* Use random numbers: "
write (u, "(A,F3.2,A,F3.2,A,F3.2)") "x1: ", x1, "x2: ", x2, "x3: ", x3
allocate (generator%real_kinematics)
associate (rad_var => generator%real_kinematics)
    allocate (rad_var%xi_max(4), rad_var%y(4))
    allocate (rad_var%p_born(4), rad_var%p_real(5))
    allocate (rad_var%jac(4))
    allocate (rad_var%jac_rand(4), rad_var%y_soft(4))
end associate
allocate (generator%m2 (2))
generator%m2(1) = 0._default; generator%m2(2) = 0._default
allocate (generator%is_massive (4))
generator%is_massive = .false.
call generator%generate_radiation_variables ([x1,x2,x3], p_born)
write (u, "(A)") &
    "* With these, the following radiation variables have been produced:"
associate (rad_var => generator%real_kinematics)
    write (u, "(A,F3.2)") "xi_tilde: ", rad_var%xi_tilde
    write (u, "(A,F3.2)") "y: " , rad_var%y(1)
    write (u, "(A,F3.2)") "phi: ", rad_var%phi
end associate
write (u, "(A)") "Initial-state momentum fractions: "
associate (xb => generator%isr_kinematics%x)
    write (u, "(A,F3.2)") "x_born_plus: ", xb(1)
    write (u, "(A,F3.2)") "x_born_minus: ", xb(2)
end associate
call write_separator (u)
write (u, "(A)") "Produce real momenta: "
emitter = 1
write (u, "(A,I1)") "emitter: ", emitter
call generator%generate_isr (p_born, p_real)
call vector4_write_set (p_real, u, testflag = .true.)
call write_separator (u)
write (u, "(A)")
write (u, "(A)") "* Test output end: phs_fks_generator_2"

end subroutine phs_fks_generator_2

```

25.8 Subtraction of initial-state divergences

We must calculate two terms, G_{\oplus} and G_{\ominus} for each possible initial-state emitter. Following the notation of 0709.2092, this is separated into $G = \tilde{\mathcal{L}}\mathcal{G}$, such that $\tilde{\mathcal{L}}$ contains the PDF-values at the scales, explicitly

$$\tilde{\mathcal{L}} = \begin{cases} \mathcal{L}(\bar{x}_{\oplus}/z, \bar{x}_{\ominus}) & \text{for } \alpha \in \text{ISR}_{\oplus} \\ \mathcal{L}(\bar{x}_{\oplus}, \bar{x}_{\ominus}/z) & \text{for } \alpha \in \text{ISR}_{\ominus} \end{cases}$$

For each flavor combination f_{\oplus} and f_{\ominus} of initial-state particles, the relevant terms are given by

$$\mathcal{G}_{\oplus}^{f_{\oplus}f_{\ominus}}(z) = \frac{\alpha_s}{2\pi} \sum_{f'_{\oplus}} \left\{ (1-z)P^{f_{\oplus}f'_{\oplus}}(z, 0) \left[\left(\frac{1}{1-z} \right)_+ \log \frac{s}{2\mu_F^2} + 2 \left(\frac{\log(1-z)}{1-z} \right)_+ \right] - \left[\frac{\partial P^{f_{\oplus}f'_{\oplus}}(z, \epsilon)}{\partial \epsilon} \right]_{\epsilon=0} - K^{f_{\oplus}f'_{\oplus}} \right\} \mathcal{B}^{f_{\oplus}f_{\ominus}}(z)$$

where $P(z, \epsilon)$ are the Altarelli-Parisi splitting functions

$$\begin{aligned} P_{qq}(z, \epsilon) &= C_F \left[\frac{1+z^2}{1-z} - \epsilon(1-z) \right], \\ P_{qg}(z, \epsilon) &= C_F \left[\frac{1+(1-z)^2}{z} - \epsilon z \right], \\ P_{gq}(z, \epsilon) &= T_F \left[1 - \frac{2z(1-z)}{1-\epsilon} \right], \\ P_{gg}(z, \epsilon) &= 2C_A \left[\frac{z}{1-z} + \frac{1-z}{z} + z(1-z) \right]. \end{aligned}$$

In the code we deal with $\hat{P}^{f_{\oplus}f_{\ominus}}(z) = (1-z)P^{f_{\oplus}f_{\ominus}}(z, 0)$ because this quantity behaves nicely in the limit $z \rightarrow 1$. The factor $K^{f_{\oplus}f_{\ominus}}$ depends on the renormalization scheme and vanishes for \overline{MS} .

The second thing to consider is the fact that the integration over z is carried out over the interval $[\bar{x}_{\oplus}, 1]$ or $[\bar{x}_{\ominus}, 1]$, respectively, but the plus-distribution can only be evaluated over $[0, 1]$. We thus use the identities

$$\begin{aligned} \int_{\bar{x}_{\oplus}}^1 dz \left(\frac{1}{1-z} \right)_+ f(z) &= \log(1-\bar{x}_{\oplus})f(1) + \int_{\bar{x}_{\oplus}}^1 dz \frac{f(z) - f(1)}{1-z}, \\ \int_{\bar{x}_{\oplus}}^1 dz \left(\frac{\log(1-z)}{1-z} \right)_+ f(z) &= \frac{1}{2} \log^2(1-\bar{x}_{\oplus})f(1) + \int_{\bar{x}_{\oplus}}^1 dz \frac{\log(1-z)[f(z) - f(1)]}{1-z}. \end{aligned}$$

`<pdf_subtraction.f90>` \equiv
`<File header>`

`module pdf_subtraction`

`<Use kinds with double>`

`<Use strings>`

`use system_dependencies, only: LHAPDF6_AVAILABLE`

```

    use diagnostics
    use shower_base
    use constants
    use physics_defs
    use pdg_arrays
    use sf_lhapdf
    use nlo_data

    <Standard module head>

    <pdf subtraction: public>

    <pdf subtraction: types>

contains

    <pdf subtraction: procedures>

end module pdf_subtraction

<pdf subtraction: types>≡
    type :: pdf_container_t
        real(default), dimension(-6:6) :: f
    end type pdf_container_t

<pdf subtraction: public>≡
    public :: pdf_subtraction_t

<pdf subtraction: types>+≡
    type :: pdf_subtraction_t
        type(pdf_data_t) :: pdf_data
        logical :: required = .false.
        type(isr_kinematics_t), pointer :: isr_kinematics => null ()
        integer, dimension(:), allocatable :: i_light_quarks
        integer, dimension(2) :: flv_in
        type(pdf_container_t), dimension(2) :: pdf_scaled
        type(pdf_container_t), dimension(2) :: pdf_born
        real(default), dimension(:), pointer :: sqme_born => null ()
        real(default), dimension(:), allocatable :: value
    contains
        <pdf subtraction: pdf subtraction: TBP>
    end type pdf_subtraction_t

<pdf subtraction: pdf subtraction: TBP>≡
    procedure :: init => pdf_subtraction_init

<pdf subtraction: procedures>≡
    subroutine pdf_subtraction_init (pdf_sub, isr_kinematics, flv, n_alr, sqme_collector)
        class(pdf_subtraction_t), intent(inout) :: pdf_sub
        type(isr_kinematics_t), intent(in), target :: isr_kinematics
        integer, dimension(:,:), intent(in) :: flv
        integer, intent(in) :: n_alr
        type(sqme_collector_t), intent(in), target :: sqme_collector

```

```

integer :: i, j, n_quarks
logical, dimension(-6:6) :: quark_checked = .false.
pdf_sub%required = any ([is_quark(flv(1,1)), &
    is_quark(flv(2,1)), is_gluon(flv(1,1)), is_gluon(flv(2,1))])
if (.not. pdf_sub%required) return

pdf_sub%sqme_born => sqme_collector%sqme_born_list
pdf_sub%isr_kinematics => isr_kinematics
allocate (pdf_sub%value (n_alr))
call pdf_sub%set_incoming_flavor (flv(1,1), flv(2,1))
n_quarks = 0
do i = 1, size (flv, dim=1 )
    if (is_quark(flv(i,1))) then
        n_quarks = n_quarks+1
        quark_checked(flv(i,1)) = .true.
    end if
end do
allocate (pdf_sub%i_light_quarks (n_quarks))
j = 1
do i = -6, 6
    if (quark_checked(i)) then
        pdf_sub%i_light_quarks(j) = i
        j = j+1
    end if
end do

call pdf_sub%init_pdfs ()
end subroutine pdf_subtraction_init

```

<pdf subtraction: pdf subtraction: TBP>+≡
 procedure :: set_incoming_flavor => pdf_subtraction_set_incoming_flavor

<pdf subtraction: procedures>+≡
 subroutine pdf_subtraction_set_incoming_flavor (pdf_sub, flv1, flv2)
 class(pdf_subtraction_t), intent(inout) :: pdf_sub
 integer, intent(in) :: flv1, flv2
 pdf_sub%flv_in(1) = flv1; pdf_sub%flv_in(2) = flv2
 end subroutine pdf_subtraction_set_incoming_flavor

<pdf subtraction: pdf subtraction: TBP>+≡
 procedure :: init_pdfs => pdf_subtraction_init_pdfs

<pdf subtraction: procedures>+≡
 subroutine pdf_subtraction_init_pdfs (pdf_sub)
 class(pdf_subtraction_t), intent(inout) :: pdf_sub
 type(string_t) :: lhpdf_dir, lhpdf_file
 integer :: lhpdf_member
 lhpdf_dir = ""
 lhpdf_file = ""
 lhpdf_member = 0
 if (LHAPDF6_AVAILABLE) then
 call lhpdf_initialize &
 (1, lhpdf_dir, lhpdf_file, lhpdf_member, pdf_sub%pdf_data%pdf)
 associate (pdf_data => pdf_sub%pdf_data)


```

        pdf_data%type = STRF_LHAPDF6
        pdf_data%xmin = pdf_data%pdf%getxmin ()
        pdf_data%xmax = pdf_data%pdf%getxmax ()
        pdf_data%qmin = sqrt(pdf_data%pdf%getq2min ())
        pdf_data%qmax = sqrt(pdf_data%pdf%getq2max ())
    end associate
else
    call msg_fatal ("Real subtraction: PDFs could not be initialized")
end if
end subroutine pdf_subtraction_init_pdfs

<pdf subtraction: pdf subtraction: TBP>+≡
    procedure :: compute_pdfs => pdf_subtraction_compute_pdfs

<pdf subtraction: procedures>+≡
    subroutine pdf_subtraction_compute_pdfs (pdf_sub)
        class(pdf_subtraction_t), intent(inout) :: pdf_sub
        integer :: i
        real(default) :: z, x, Q
        real(double), dimension(-6:6) :: f_dble = 0._double
        do i = 1, 2
            x = pdf_sub%isr_kinematics%x(i)
            z = pdf_sub%isr_kinematics%z(i)
            Q = pdf_sub%isr_kinematics%fac_scale
            call pdf_sub%pdf_data%evolve (dble(x), dble(Q), f_dble)
            pdf_sub%pdf_born(i)%f = f_dble
            call pdf_sub%pdf_data%evolve (dble(x/z), dble(Q), f_dble)
            pdf_sub%pdf_scaled(i)%f = f_dble
        end do
    end subroutine pdf_subtraction_compute_pdfs

<pdf subtraction: pdf subtraction: TBP>+≡
    procedure :: get_gluon_pdf => pdf_subtraction_get_gluon_pdf

<pdf subtraction: procedures>+≡
    function pdf_subtraction_get_gluon_pdf (pdf_sub, em, scaled) result (pdf)
        class(pdf_subtraction_t), intent(in) :: pdf_sub
        integer, intent(in) :: em
        logical, intent(in) :: scaled
        real(default) :: pdf
        if (scaled) then
            pdf = pdf_sub%pdf_scaled(em)%f(0)
        else
            pdf = pdf_sub%pdf_born(em)%f(0)
        end if
    end function pdf_subtraction_get_gluon_pdf

<pdf subtraction: pdf subtraction: TBP>+≡
    procedure :: get_quark_pdf => pdf_subtraction_get_quark_pdf

<pdf subtraction: procedures>+≡
    function pdf_subtraction_get_quark_pdf (pdf_sub, em, i, scaled) result (pdf)
        class(pdf_subtraction_t), intent(in) :: pdf_sub
        integer, intent(in) :: em, i

```

```

logical, intent(in) :: scaled
real(default) :: pdf
if (scaled) then
    pdf = pdf_sub%pdf_scaled(em)%f(i)
else
    pdf = pdf_sub%pdf_born(em)%f(i)
end if
end function pdf_subtraction_get_quark_pdf

```

```

(pdf subtraction: pdf subtraction: TBP)+≡
procedure :: get_summed_quark_pdf => pdf_subtraction_get_summed_quark_pdf

```

```

(pdf subtraction: procedures)+≡
function pdf_subtraction_get_summed_quark_pdf (pdf_sub, em) result (pdf)
    class(pdf_subtraction_t), intent(in) :: pdf_sub
    integer, intent(in) :: em
    real(default) :: pdf
    integer :: i_quark
    pdf = 0._default
    do i_quark = -6, 6
        if (any(i_quark == pdf_sub%i_light_quarks)) &
            pdf = pdf + pdf_sub%get_quark_pdf(em, i_quark, scaled = .true.)
    end do
end function pdf_subtraction_get_summed_quark_pdf

```

```

(pdf subtraction: pdf subtraction: TBP)+≡
procedure :: evaluate => pdf_subtraction_evaluate

```

```

(pdf subtraction: procedures)+≡
subroutine pdf_subtraction_evaluate (pdf_sub, alpha_s, sqme_born, alr)
    class(pdf_subtraction_t), intent(inout) :: pdf_sub
    real(default), intent(in) :: alpha_s
    real(default), intent(in) :: sqme_born
    integer, intent(in) :: alr
    real(default) :: factor, factor_soft, remnant
    real(default) :: pdfs, pdfb
    integer :: emitter
    real(default), dimension(2) :: tmp
    real(default) :: sb, xb, onemz
    real(default) :: fac_scale2, jac

    pdf_sub%value = 0._default
    sb = pdf_sub%isr_kinematics%sqrts_born
    tmp = 0._default
    fac_scale2 = pdf_sub%isr_kinematics%fac_scale**2

    call pdf_sub%compute_pdfs ()

    do emitter = 1, 2
        associate (z => pdf_sub%isr_kinematics%z(emitter))
            jac = pdf_sub%isr_kinematics%jacobian(emitter)
            onemz = one - z
            factor = log(sb/z/fac_scale2)/onemz + 2*log(onemz)/onemz
            factor_soft = log(sb/fac_scale2)/onemz + 2*log(onemz)/onemz

```

```

xb = pdf_sub%isr_kinematics%x(emitter)
remnant = log(1-xb)*log(sb/fac_scale2) + log(1-xb)**2

if (is_gluon(pdf_sub%flv_in(1))) then
  pdfs = pdf_sub%get_gluon_pdf (emitter, scaled = .true.)
  pdfb = pdf_sub%get_gluon_pdf (emitter, scaled = .false.)
  tmp(emitter) = p_hat_gg(z) * factor/z * pdfs/pdfb * jac &
    - p_hat_gg(one) * factor_soft * jac &
    + p_hat_gg(one) * remnant
  pdfs = pdf_sub%get_summed_quark_pdf (emitter)
  tmp(emitter) = tmp(emitter) + (p_hat_qg(z)*factor - p_derived_qg(z))/z * pdfs/pdfb * jac
else if (is_quark(abs(pdf_sub%flv_in(emitter)))) then
  pdfs = pdf_sub%get_quark_pdf (emitter, pdf_sub%flv_in(emitter), scaled = .true.)
  pdfb = pdf_sub%get_quark_pdf (emitter, pdf_sub%flv_in(emitter), scaled = .false.)
  if (pdfb == 0._default) then
    pdf_sub%value(alr) = 0._default
    return
  end if
  tmp(emitter) = p_hat_qq(z) * factor/z * pdfs/pdfb * jac &
    - p_derived_qq(z)/z * pdfs/pdfb * jac &
    - p_hat_qq(one) * factor_soft * jac &
    + p_hat_qq(one) * remnant
  pdfs = pdf_sub%get_gluon_pdf (emitter, scaled = .true.)
  tmp(emitter) = tmp(emitter) + (p_hat_gq(z)*factor - p_derived_gq(z))/z * pdfs/pdfb * jac
end if
end associate
end do
pdf_sub%value(alr) = alpha_s/twopi * (tmp(1)+tmp(2)) * sqme_born
end subroutine pdf_subtraction_evaluate

```

```

(pdf subtraction: procedures)+≡
function p_hat_gg (z)
  real(default) :: p_hat_gg
  (p variables)
  p_hat_gg = 2*CA*(z + onemz**2/z + z*onemz**2)
end function p_hat_gg

function p_hat_qg (z)
  real(default) :: p_hat_qg
  (p variables)
  p_hat_qg = CF * onemz/z * (1+onemz**2)
end function p_hat_qg

function p_hat_gq (z)
  real(default) :: p_hat_gq
  (p variables)
  p_hat_gq = TR*(onemz - 2*z*onemz**2)
end function p_hat_gq

function p_hat_qq (z)
  real(default) :: p_hat_qq
  (p variables)
  p_hat_qq = CF*(one+z**2)

```

```

end function p_hat_qq

function p_derived_gg (z)
  real(default) :: p_derived_gg
  <p variables>
  p_derived_gg = 0._default
end function p_derived_gg

function p_derived_qg (z)
  real(default) :: p_derived_qg
  <p variables>
  p_derived_qg = -CF*z
end function p_derived_qg

function p_derived_gq (z)
  real(default) :: p_derived_gq
  <p variables>
  p_derived_gq = -2*TR*z*onemz
end function p_derived_gq

function p_derived_qq (z)
  real(default) :: p_derived_qq
  <p variables>
  p_derived_qq = -CF*onemz
end function p_derived_qq

<p variables>≡
  real(default), intent(in) :: z
  real(default) :: onemz
  onemz = one - z

```

Chapter 26

Model Handling and Features

These modules deal with process definitions and physics models.

These modules use the `model_data` methods to automatically generate process definitions.

auto_components Generic process-definition generator. We can specify a basic process or initial particle(s) and some rules to extend this process, given a model definition with particle names and vertex structures.

radiation_generator Applies the generic generator to the specific problem of generating NLO corrections in a restricted setup.

Model construction:

eval_trees Implementation of the generic `expr_t` type for the concrete evaluation of expressions that access user variables.

This module is actually part of the Sindarin language implementation, and should be moved elsewhere. Currently, the `models` module relies on it.

models Extends the `model_data_t` structure by user-variable objects for easy access, and provides the means to read a model definition from file.

slha_interface Read/write a SUSY model in the standardized SLHA format. The format defines fields and parameters, but no vertices.

26.1 Automatic generation of process components

This module provides the functionality for automatically generating radiation corrections or decays, provided as lists of PDG codes.

```
<auto_components.f90>≡  
  <File header>  
  
  module auto_components  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use unit_tests  
    use diagnostics  
    use model_data  
    use pdg_arrays  
    use model_testbed  
  
    <Standard module head>  
  
    <Auto components: public>  
  
    <Auto components: types>  
  
    <Auto components: interfaces>  
  
    contains  
  
    <Auto components: procedures>  
  
    <Auto components: tests>  
  
  end module auto_components
```

26.1.1 Constraints: Abstract types

An abstract type that denotes a constraint on the automatically generated states. The concrete objects are applied as visitor objects at certain hooks during the splitting algorithm.

```
<Auto components: types>≡  
  type, abstract :: split_constraint_t  
    contains  
    <Auto components: split constraint: TBP>  
  end type split_constraint_t
```

By default, all checks return true.

```
<Auto components: split constraint: TBP>≡  
  procedure :: check_before_split => split_constraint_check_before_split  
  procedure :: check_before_insert => split_constraint_check_before_insert  
  procedure :: check_before_record => split_constraint_check_before_record
```

```

<Auto components: procedures>≡
  subroutine split_constraint_check_before_split (c, table, pl, k, passed)
    class(split_constraint_t), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: k
    logical, intent(out) :: passed
    passed = .true.
  end subroutine split_constraint_check_before_split

  subroutine split_constraint_check_before_insert (c, table, pa, pl, passed)
    class(split_constraint_t), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_array_t), intent(in) :: pa
    type(pdg_list_t), intent(inout) :: pl
    logical, intent(out) :: passed
    passed = .true.
  end subroutine split_constraint_check_before_insert

  subroutine split_constraint_check_before_record (c, table, pl, n_loop, passed)
    class(split_constraint_t), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n_loop
    logical, intent(out) :: passed
    passed = .true.
  end subroutine split_constraint_check_before_record

```

A transparent wrapper, so we can collect constraints of different type.

```

<Auto components: types>+≡
  type :: split_constraint_wrap_t
    class(split_constraint_t), allocatable :: c
  end type split_constraint_wrap_t

```

A collection of constraints.

```

<Auto components: public>≡
  public :: split_constraints_t

<Auto components: types>+≡
  type :: split_constraints_t
    class(split_constraint_wrap_t), dimension(:), allocatable :: cc
    contains
    <Auto components: split constraints: TBP>
  end type split_constraints_t

```

Initialize the constraints set with a specific number of elements.

```

<Auto components: split constraints: TBP>≡
  procedure :: init => split_constraints_init

<Auto components: procedures>+≡
  subroutine split_constraints_init (constraints, n)
    class(split_constraints_t), intent(out) :: constraints
    integer, intent(in) :: n

```

```

        allocate (constraints%cc (n))
    end subroutine split_constraints_init

```

Set a constraint.

```

<Auto components: split constraints: TBP>+≡
    procedure :: set => split_constraints_set

<Auto components: procedures>+≡
    subroutine split_constraints_set (constraints, i, c)
        class(split_constraints_t), intent(inout) :: constraints
        integer, intent(in) :: i
        class(split_constraint_t), intent(in) :: c
        allocate (constraints%cc(i)%c, source = c)
    end subroutine split_constraints_set

```

Apply checks.

`check_before_split` is applied to the particle list that we want to split.
`check_before_insert` is applied to the particle list `pl` that is to replace the particle `pa` that is split. This check may transform the particle list.
`check_before_record` is applied to the complete new particle list that results from splitting before it is recorded.

```

<Auto components: split constraints: TBP>+≡
    procedure :: check_before_split => split_constraints_check_before_split
    procedure :: check_before_insert => split_constraints_check_before_insert
    procedure :: check_before_record => split_constraints_check_before_record

<Auto components: procedures>+≡
    subroutine split_constraints_check_before_split &
        (constraints, table, pl, k, passed)
        class(split_constraints_t), intent(in) :: constraints
        class(ps_table_t), intent(in) :: table
        type(pdg_list_t), intent(in) :: pl
        integer, intent(in) :: k
        logical, intent(out) :: passed
        integer :: i
        passed = .true.
        do i = 1, size (constraints%cc)
            call constraints%cc(i)%c%check_before_split (table, pl, k, passed)
            if (.not. passed) return
        end do
    end subroutine split_constraints_check_before_split

    subroutine split_constraints_check_before_insert &
        (constraints, table, pa, pl, passed)
        class(split_constraints_t), intent(in) :: constraints
        class(ps_table_t), intent(in) :: table
        type(pdg_array_t), intent(in) :: pa
        type(pdg_list_t), intent(inout) :: pl
        logical, intent(out) :: passed
        integer :: i
        passed = .true.
        do i = 1, size (constraints%cc)
            call constraints%cc(i)%c%check_before_insert (table, pa, pl, passed)

```



```

        if (.not. passed) return
    end do
end subroutine split_constraints_check_before_insert

subroutine split_constraints_check_before_record &
    (constraints, table, pl, n_loop, passed)
    class(split_constraints_t), intent(in) :: constraints
    class(ps_table_t), intent(in) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n_loop
    logical, intent(out) :: passed
    integer :: i
    passed = .true.
    do i = 1, size (constraints%cc)
        call constraints%cc(i)%check_before_record (table, pl, n_loop, passed)
        if (.not. passed) return
    end do
end subroutine split_constraints_check_before_record

```

26.1.2 Specific constraints

Number of particles

Specific constraint: The number of particles plus the number of loops, if any, must remain less than the given limit. Note that the number of loops is defined only when we are recording the entry.

```

<Auto components: types>+≡
    type, extends (split_constraint_t) :: constraint_n_tot
    private
    integer :: n_max = 0
    contains
    procedure :: check_before_split => constraint_n_tot_check_before_split
    procedure :: check_before_record => constraint_n_tot_check_before_record
end type constraint_n_tot

<Auto components: public>+≡
    public :: constrain_n_tot

<Auto components: procedures>+≡
    function constrain_n_tot (n_max) result (c)
    integer, intent(in) :: n_max
    type(constraint_n_tot) :: c
    c%n_max = n_max
end function constrain_n_tot

subroutine constraint_n_tot_check_before_split (c, table, pl, k, passed)
    class(constraint_n_tot), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: k
    logical, intent(out) :: passed
    passed = pl%get_size () < c%n_max
end subroutine constraint_n_tot_check_before_split

```

```

subroutine constraint_n_tot_check_before_record (c, table, pl, n_loop, passed)
  class(constraint_n_tot), intent(in) :: c
  class(ps_table_t), intent(in) :: table
  type(pdg_list_t), intent(in) :: pl
  integer, intent(in) :: n_loop
  logical, intent(out) :: passed
  passed = pl%get_size () + n_loop <= c%n_max
end subroutine constraint_n_tot_check_before_record

```

Number of loops

Specific constraint: The number of loops is limited, independent of the total number of particles.

```

<Auto components: types>+≡
  type, extends (split_constraint_t) :: constraint_n_loop
  private
  integer :: n_loop_max = 0
  contains
  procedure :: check_before_record => constraint_n_loop_check_before_record
end type constraint_n_loop

<Auto components: public>+≡
  public :: constrain_n_loop

<Auto components: procedures>+≡
  function constrain_n_loop (n_loop_max) result (c)
    integer, intent(in) :: n_loop_max
    type(constraint_n_loop) :: c
    c%n_loop_max = n_loop_max
  end function constrain_n_loop

  subroutine constraint_n_loop_check_before_record &
    (c, table, pl, n_loop, passed)
    class(constraint_n_loop), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n_loop
    logical, intent(out) :: passed
    passed = n_loop <= c%n_loop_max
  end subroutine constraint_n_loop_check_before_record

```

Particles allowed in splitting

Specific constraint: The entries in the particle list ready for insertion are matched to a given list of particle patterns. If a match occurs, the entry is replaced by the corresponding pattern. If there is no match, the check fails.

```

<Auto components: types>+≡
  type, extends (split_constraint_t) :: constraint_insert
  private
  type(pdg_list_t) :: pl_match

```

```

contains
  procedure :: check_before_insert => constraint_insert_check_before_insert
end type constraint_insert

<Auto components: public>+≡
  public :: constrain_insert

<Auto components: procedures>+≡
  function constrain_insert (pl_match) result (c)
    type(pdg_list_t), intent(in) :: pl_match
    type(constraint_insert) :: c
    c%pl_match = pl_match
  end function constrain_insert

  subroutine constraint_insert_check_before_insert (c, table, pa, pl, passed)
    class(constraint_insert), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_array_t), intent(in) :: pa
    type(pdg_list_t), intent(inout) :: pl
    logical, intent(out) :: passed
    call pl%match_replace (c%pl_match, passed)
  end subroutine constraint_insert_check_before_insert

```

Particles required in final state

Specific constraint: The entries in the recorded state must be a superset of the entries in the given list (for instance, the lowest-order state).

```

<Auto components: types>+≡
  type, extends (split_constraint_t) :: constraint_require
  private
  type(pdg_list_t) :: pl
  contains
  procedure :: check_before_record => constraint_require_check_before_record
end type constraint_require

```

We check the current state by matching all particle entries against the stored particle list, and crossing out the particles in the latter list when a match is found. The constraint passed if all entries have been crossed out.

For an `if_table` in particular, we check the final state only.

```

<Auto components: public>+≡
  public :: constrain_require

<Auto components: procedures>+≡
  function constrain_require (pl) result (c)
    type(pdg_list_t), intent(in) :: pl
    type(constraint_require) :: c
    c%pl = pl
  end function constrain_require

  subroutine constraint_require_check_before_record &
    (c, table, pl, n_loop, passed)
    class(constraint_require), intent(in) :: c

```

```

class(ps_table_t), intent(in) :: table
type(pdg_list_t), intent(in) :: pl
integer, intent(in) :: n_loop
logical, intent(out) :: passed
logical, dimension(:), allocatable :: mask
integer :: i, k, n_in
select type (table)
type is (if_table_t)
    n_in = 2
class default
    n_in = 0
end select
allocate (mask (c%pl%get_size ()), source = .true.)
do i = n_in + 1, pl%get_size ( )
    k = c%pl%find_match (pl%get (i), mask)
    if (k /= 0) mask(k) = .false.
end do
passed = .not. any (mask)
end subroutine constraint_require_check_before_record

```

Radiation

Specific constraint: We have radiation pattern if the original particle matches an entry in the list of particles that should replace it. The constraint prohibits this situation.

```

<Auto components: public>+≡
public :: constrain_radiation

```

```

<Auto components: types>+≡
type, extends (split_constraint_t) :: constraint_radiation
private
contains
    procedure :: check_before_insert => &
        constraint_radiation_check_before_insert
end type constraint_radiation

```

```

<Auto components: procedures>+≡
function constrain_radiation ( ) result (c)
    type(constraint_radiation) :: c
end function constrain_radiation

```

```

subroutine constraint_radiation_check_before_insert (c, table, pa, pl, passed)
    class(constraint_radiation), intent(in) :: c
    class(ps_table_t), intent(in) :: table
    type(pdg_array_t), intent(in) :: pa
    type(pdg_list_t), intent(inout) :: pl
    logical, intent(out) :: passed
    passed = .not. (pl .match. pa)
end subroutine constraint_radiation_check_before_insert

```

Mass sum

Specific constraint: The sum of masses within the particle list must be smaller than a given limit. For in/out state combinations, we check initial and final state separately.

If we specify `margin` in the initialization, the sum must be strictly less than the limit minus the given margin (which may be zero). If not, equality is allowed.

```
(Auto components: public)+≡
    public :: constrain_mass_sum

(Auto components: types)+≡
    type, extends (split_constraint_t) :: constraint_mass_sum
    private
        real(default) :: mass_limit = 0
        logical :: strictly_less = .false.
        real(default) :: margin = 0
    contains
        procedure :: check_before_record => constraint_mass_sum_check_before_record
    end type constraint_mass_sum

(Auto components: procedures)+≡
    function constrain_mass_sum (mass_limit, margin) result (c)
        real(default), intent(in) :: mass_limit
        real(default), intent(in), optional :: margin
        type(constraint_mass_sum) :: c
        c%mass_limit = mass_limit
        if (present (margin)) then
            c%strictly_less = .true.
            c%margin = margin
        end if
    end function constrain_mass_sum

    subroutine constraint_mass_sum_check_before_record &
        (c, table, pl, n_loop, passed)
        class(constraint_mass_sum), intent(in) :: c
        class(ps_table_t), intent(in) :: table
        type(pdg_list_t), intent(in) :: pl
        integer, intent(in) :: n_loop
        logical, intent(out) :: passed
        real(default) :: limit
        if (c%strictly_less) then
            limit = c%mass_limit - c%margin
            select type (table)
            type is (if_table_t)
                passed = mass_sum (pl, 1, 2, table%model) < limit &
                    .and. mass_sum (pl, 3, pl%get_size (), table%model) < limit
            class default
                passed = mass_sum (pl, 1, pl%get_size (), table%model) < limit
            end select
        else
            limit = c%mass_limit
            select type (table)
            type is (if_table_t)
                passed = mass_sum (pl, 1, 2, table%model) <= limit &
```

```

        .and. mass_sum (pl, 3, pl%get_size (), table%model) <= limit
class default
    passed = mass_sum (pl, 1, pl%get_size (), table%model) <= limit
end select
end if
end subroutine constraint_mass_sum_check_before_record

```

Initial state particles

Specific constraint: The two incoming particles must both match the given particle list. This is checked for the generated particle list, just before it is recorded.

```

<Auto components: public>+≡
    public :: constrain_in_state

<Auto components: types>+≡
    type, extends (split_constraint_t) :: constraint_in_state
    private
        type(pdg_list_t) :: pl
    contains
        procedure :: check_before_record => constraint_in_state_check_before_record
    end type constraint_in_state

<Auto components: procedures>+≡
    function constrain_in_state (pl) result (c)
        type(pdg_list_t), intent(in) :: pl
        type(constraint_in_state) :: c
        c%pl = pl
    end function constrain_in_state

    subroutine constraint_in_state_check_before_record &
        (c, table, pl, n_loop, passed)
        class(constraint_in_state), intent(in) :: c
        class(ps_table_t), intent(in) :: table
        type(pdg_list_t), intent(in) :: pl
        integer, intent(in) :: n_loop
        logical, intent(out) :: passed
        integer :: i
        select type (table)
        type is (if_table_t)
            passed = .false.
            do i = 1, 2
                if (.not. (c%pl .match. pl%get (i))) return
            end do
        end select
        passed = .true.
    end subroutine constraint_in_state_check_before_record

```

26.1.3 Tables of states

Automatically generate a list of possible process components for a given initial set (a single massive particle or a preset list of states).

The set of process components are generated by recursive splitting, applying constraints on the fly that control and limit the process. The generated states are accumulated in a table that we can read out after completion.

```

⟨Auto components: types⟩+≡
  type, extends (pdg_list_t) :: ps_entry_t
    integer :: n_loop = 0
    integer :: n_rad = 0
    type(ps_entry_t), pointer :: previous => null ()
    type(ps_entry_t), pointer :: next => null ()
  end type ps_entry_t

```

This is the wrapper type for the decay tree for the list of final states and the final array. First, an abstract base type:

```

⟨Auto components: public⟩+≡
  public :: ps_table_t

⟨Auto components: types⟩+≡
  type, abstract :: ps_table_t
    private
      class(model_data_t), pointer :: model => null ()
      logical :: loops = .false.
      type(ps_entry_t), pointer :: first => null ()
      type(ps_entry_t), pointer :: last => null ()
    contains
      ⟨Auto components: ps table: TBP⟩
  end type ps_table_t

```

The extensions: one for decay, one for generic final states. The decay-state table stores the initial particle. The final-state table is indifferent, and the initial/final state table treats the first two particles in its list as incoming antiparticles.

```

⟨Auto components: public⟩+≡
  public :: ds_table_t
  public :: if_table_t

⟨Auto components: types⟩+≡
  type, extends (ps_table_t) :: ds_table_t
    private
      integer :: pdg_in = 0
    contains
      ⟨Auto components: ds table: TBP⟩
  end type ds_table_t

  type, extends (ps_table_t) :: fs_table_t
    contains
      ⟨Auto components: fs table: TBP⟩
  end type fs_table_t

  type, extends (fs_table_t) :: if_table_t
    contains

```

```

    <Auto components: if table: TBP>
end type if_table_t

```

Finalizer: we must deallocate the embedded list.

```

<Auto components: ps table: TBP>≡
    procedure :: final => ps_table_final

<Auto components: procedures>+≡
    subroutine ps_table_final (object)
        class(ps_table_t), intent(inout) :: object
        type(ps_entry_t), pointer :: current
        do while (associated (object%first))
            current => object%first
            object%first => current%next
            deallocate (current)
        end do
        nullify (object%last)
    end subroutine ps_table_final

```

Write the table. A base writer for the body and specific writers for the headers.

```

<Auto components: ps table: TBP>+≡
    procedure :: base_write => ps_table_base_write
    procedure (ps_table_write), deferred :: write

<Auto components: interfaces>≡
    interface
        subroutine ps_table_write (object, unit)
            import
            class(ps_table_t), intent(in) :: object
            integer, intent(in), optional :: unit
        end subroutine ps_table_write
    end interface

<Auto components: ds table: TBP>≡
    procedure :: write => ds_table_write

<Auto components: fs table: TBP>≡
    procedure :: write => fs_table_write

<Auto components: if table: TBP>≡
    procedure :: write => if_table_write

```

The first `n_in` particles will be replaced by antiparticles in the output, and we write an arrow if `n_in` is present.

```

<Auto components: procedures>+≡
    subroutine ps_table_base_write (object, unit, n_in)
        class(ps_table_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer, intent(in), optional :: n_in
        integer, dimension(:), allocatable :: pdg
        type(ps_entry_t), pointer :: entry
        type(field_data_t), pointer :: prt
        integer :: u, i, j, n0
        u = given_output_unit (unit)
        entry => object%first
        do while (associated (entry))

```



```

write (u, "(2x)", advance = "no")
if (present (n_in)) then
  do i = 1, n_in
    write (u, "(1x)", advance = "no")
    pdg = entry%get (i)
    do j = 1, size (pdg)
      prt => object%model%get_field_ptr (pdg(j))
      if (j > 1) write (u, "(::)", advance = "no")
      write (u, "(A)", advance = "no") &
        char (prt%get_name (pdg(j) >= 0))
    end do
  end do
  write (u, "(1x,A)", advance = "no")  "=>"
  n0 = n_in + 1
else
  n0 = 1
end if
do i = n0, entry%get_size ()
  write (u, "(1x)", advance = "no")
  pdg = entry%get (i)
  do j = 1, size (pdg)
    prt => object%model%get_field_ptr (pdg(j))
    if (j > 1) write (u, "(::)", advance = "no")
    write (u, "(A)", advance = "no") &
      char (prt%get_name (pdg(j) < 0))
  end do
end do
if (object%loops) then
  write (u, "(2x,['I0','I0,','I0,']')")  entry%n_loop, entry%n_rad
else
  write (u, *)
end if
entry => entry%next
end do
end subroutine ps_table_base_write

subroutine ds_table_write (object, unit)
  class(ds_table_t), intent(in) :: object
  integer, intent(in), optional :: unit
  type(field_data_t), pointer :: prt
  integer :: u
  u = given_output_unit (unit)
  prt => object%model%get_field_ptr (object%pdg_in)
  write (u, "(1x,A,1x,A)")  "Decays for particle:", &
    char (prt%get_name (object%pdg_in < 0))
  call object%base_write (u)
end subroutine ds_table_write

subroutine fs_table_write (object, unit)
  class(fs_table_t), intent(in) :: object
  integer, intent(in), optional :: unit
  integer :: u
  u = given_output_unit (unit)
  write (u, "(1x,A)")  "Table of final states:"

```

```

        call object%base_write (u)
    end subroutine fs_table_write

    subroutine if_table_write (object, unit)
        class(if_table_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Table of in/out states:"
        call object%base_write (u, n_in = 2)
    end subroutine if_table_write

```

Obtain a particle string for a given index in the pdg list

(Auto components: ps table: TBP)+≡

```

    procedure :: get_particle_string => ps_table_get_particle_string

```

(Auto components: procedures)+≡

```

    subroutine ps_table_get_particle_string (object, index, n_in, prt_in, prt_out)
        class(ps_table_t), intent(in) :: object
        integer, intent(in) :: index
        integer, intent(in) :: n_in
        type(string_t), intent(out), dimension(:), allocatable :: prt_in, prt_out
        type(string_t) :: prt_tmp
        type(field_data_t), pointer :: prt
        type(ps_entry_t), pointer :: entry
        integer, dimension(:), allocatable :: pdg
        integer :: n0
        integer :: i, j
        entry => object%first
        i = 1
        do while (i < index)
            if (associated (entry%next)) then
                entry => entry%next
                i=i+1
            else
                call msg_fatal ("ps_table: entry with requested index does not exist!")
            end if
        end do
        n0 = n_in + 1
        allocate (prt_in (n_in), prt_out (entry%get_size () - n_in))
        do i = 1, n_in
            prt_in(i) = ""
            pdg = entry%get(i)
            do j = 1, size(pdg)
                prt => object%model%get_field_ptr (pdg(j))
                prt_in(i) = prt_in(i) // prt%get_name (pdg(j) >= 0)
                if (j /= size(pdg)) &
                    prt_in(i) = prt_in(i) // ":"
            end do
        end do
        do i = n0, entry%get_size ()
            prt_out(i-n_in) = ""
            pdg = entry%get(i)
            do j = 1, size(pdg)

```

```

        prt => object%model%get_field_ptr (pdg(j))
        prt_out(i-n_in) = prt_out(i-n_in) // prt%get_name (pdg(j) < 0)
        if (j /= size(pdg)) &
            prt_out(i-n_in) = prt_out(i-n_in) // ":"
        end do
    end do
end subroutine ps_table_get_particle_string

```

Initialize with a predefined set of final states, or in/out state lists.

```

<Auto components: ps table: TBP>+≡
    generic :: init => ps_table_init
    procedure, private :: ps_table_init

<Auto components: if table: TBP>+≡
    generic :: init => if_table_init
    procedure, private :: if_table_init

<Auto components: procedures>+≡
    subroutine ps_table_init (table, model, pl, constraints)
        class(ps_table_t), intent(out) :: table
        class(model_data_t), intent(in), target :: model
        type(pdg_list_t), dimension(:), intent(in) :: pl
        type(split_constraints_t), intent(in) :: constraints
        logical :: passed
        integer :: i
        table%model => model
        do i = 1, size (pl)
            call table%record (pl(i), 0, 0, constraints, passed)
            if (.not. passed) then
                call msg_fatal ("Registering process components: constraint failed")
            end if
        end do
    end subroutine ps_table_init

    subroutine if_table_init (table, model, pl_in, pl_out, constraints)
        class(if_table_t), intent(out) :: table
        class(model_data_t), intent(in), target :: model
        type(pdg_list_t), dimension(:), intent(in) :: pl_in, pl_out
        type(split_constraints_t), intent(in) :: constraints
        integer :: i, j, k, p, n_in, n_out
        type(pdg_array_t), dimension(:), allocatable :: pa_in
        type(pdg_list_t), dimension(:), allocatable :: pl
        allocate (pl (size (pl_in) * size (pl_out)))
        k = 0
        do i = 1, size (pl_in)
            n_in = pl_in(i)%get_size ()
            allocate (pa_in (n_in))
            do p = 1, n_in
                pa_in(p) = pl_in(i)%get (p)
            end do
            do j = 1, size (pl_out)
                n_out = pl_out(j)%get_size ()
                k = k + 1
                call pl(k)%init (n_in + n_out)
                do p = 1, n_in

```

```

        call pl(k)%set (p, invert_pdg_array (pa_in(p), model))
    end do
    do p = 1, n_out
        call pl(k)%set (n_in + p, pl_out(j)%get (p))
    end do
end do
deallocate (pa_in)
end do
call table%init (model, pl, constraints)
end subroutine if_table_init

```

Enable loops for the table. This affects both splitting and output.

```

<Auto components: ps table: TBP>+≡
    procedure :: enable_loops => ps_table_enable_loops

<Auto components: procedures>+≡
    subroutine ps_table_enable_loops (table)
        class(ps_table_t), intent(inout) :: table
        table%loops = .true.
    end subroutine ps_table_enable_loops

```

26.1.4 Top-level methods

Create a table for a single-particle decay. Construct all possible final states from a single particle with PDG code `pdg_in`. The construction is limited by the given `constraints`.

```

<Auto components: ds table: TBP>+≡
    procedure :: make => ds_table_make

<Auto components: procedures>+≡
    subroutine ds_table_make (table, model, pdg_in, constraints)
        class(ds_table_t), intent(out) :: table
        class(model_data_t), intent(in), target :: model
        integer, intent(in) :: pdg_in
        type(split_constraints_t), intent(in) :: constraints
        type(pdg_list_t) :: pl_in
        type(pdg_list_t), dimension(0) :: pl
        logical :: passed
        call table%init (model, pl, constraints)
        table%pdg_in = pdg_in
        call pl_in%init (1)
        call pl_in%set (1, [pdg_in])
        call table%split (pl_in, 0, constraints)
    end subroutine ds_table_make

```

Split all entries in a growing table, starting from a table that may already contain states. Add and record split states on the fly.

```

<Auto components: fs table: TBP>+≡
    procedure :: radiate => fs_table_radiate

```

```

<Auto components: procedures>+≡
subroutine fs_table_radiate (table, constraints)
  class(fs_table_t), intent(inout) :: table
  type(split_constraints_t) :: constraints
  type(ps_entry_t), pointer :: current
  integer :: i, s
  logical :: passed
  current => table%first
  do while (associated (current))
    call table%split (current, 0, constraints, record = .true.)
    current => current%next
  end do
end subroutine fs_table_radiate

```

26.1.5 Splitting algorithm

Recursive splitting. First of all, we record the current `pdg_list` in the table, subject to `constraints`, if requested. We also record copies of the list marked as loop corrections.

When we record a particle list, we sort it first.

If there is room for splitting, We take a PDG array list and the index of an element, and split this element in all possible ways. The split entry is inserted into the list, which we split further.

The recursion terminates whenever the split array would have a length greater than n_{\max} .

```

<Auto components: ps table: TBP>+≡
  procedure :: split => ps_table_split

<Auto components: procedures>+≡
recursive subroutine ps_table_split (table, pl, n_rad, constraints, &
  record)
  class(ps_table_t), intent(inout) :: table
  class(pdg_list_t), intent(in) :: pl
  integer, intent(in) :: n_rad
  type(split_constraints_t), intent(in) :: constraints
  logical, intent(in), optional :: record
  integer :: n_loop, i
  logical :: passed
  type(vertex_iterator_t) :: vit
  integer, dimension(:), allocatable :: pdg1
  integer, dimension(:), allocatable :: pdg2
  if (present (record)) then
    if (record) then
      n_loop = 0
      INCR_LOOPS: do
        call table%record_sorted (pl, n_loop, n_rad, constraints, passed)
        if (.not. passed) exit INCR_LOOPS
        if (.not. table%loops) exit INCR_LOOPS
        n_loop = n_loop + 1
      end do INCR_LOOPS
    end if
  end if
end if

```

```

do i = 1, pl%get_size ()
  call constraints%check_before_split (table, pl, i, passed)
  if (passed) then
    pdg1 = pl%get (i)
    call vit%init (table%model, pdg1)
    SCAN_VERTICES: do
      call vit%get_next_match (pdg2)
      if (allocated (pdg2)) then
        call table%insert (pl, n_rad, i, pdg2, constraints)
      else
        exit SCAN_VERTICES
      end if
    end do SCAN_VERTICES
  end if
end do
end subroutine ps_table_split

```

The worker part: insert the list of particles found by vertex matching in place of entry *i* in the PDG list. Then split/record further.

The *n_in* parameter tells the replacement routine to insert the new particles after entry *n_in*. Otherwise, they follow index *i*.

(Auto components: ps table: TBP)+≡

```

procedure :: insert => ps_table_insert

```

(Auto components: procedures)+≡

```

recursive subroutine ps_table_insert &
  (table, pl, n_rad, i, pdg, constraints, n_in)
  class(ps_table_t), intent(inout) :: table
  class(pdg_list_t), intent(in) :: pl
  integer, intent(in) :: n_rad, i
  integer, dimension(:), intent(in) :: pdg
  type(split_constraints_t), intent(in) :: constraints
  integer, intent(in), optional :: n_in
  type(pdg_list_t) :: pl_insert
  logical :: passed
  integer :: k, s
  s = size (pdg)
  call pl_insert%init (s)
  do k = 1, s
    call pl_insert%set (k, pdg(k))
  end do
  call constraints%check_before_insert (table, pl%get (i), pl_insert, passed)
  if (passed) then
    call table%split (pl%replace (i, pl_insert, n_in), n_rad + s - 1, &
      constraints, record = .true.)
  end if
end subroutine ps_table_insert

```

Special case: If we are splitting an initial particle, there is slightly more to do. We loop over the particles from the vertex match and replace the initial particle by each of them in turn. The remaining particles must be appended after the second initial particle, so they will end up in the out state. This is done by providing the *n_in* argument to the base method as an optional argument.

Note that we must call the base-method procedure explicitly, so the `table` argument keeps its dynamic type as `if_table` inside this procedure.

```

<Auto components: if table: TBP>+≡
  procedure :: insert => if_table_insert

<Auto components: procedures>+≡
  recursive subroutine if_table_insert &
    (table, pl, n_rad, i, pdg, constraints, n_in)
    class(if_table_t), intent(inout) :: table
    class(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n_rad, i
    integer, dimension(:), intent(in) :: pdg
    type(split_constraints_t), intent(in) :: constraints
    integer, intent(in), optional :: n_in
    integer, dimension(:), allocatable :: pdg_work
    integer :: p
    if (i > 2) then
      call ps_table_insert (table, pl, n_rad, i, pdg, constraints)
    else
      allocate (pdg_work (size (pdg)))
      do p = 1, size (pdg)
        pdg_work(1) = pdg(p)
        pdg_work(2:p) = pdg(1:p-1)
        pdg_work(p+1:) = pdg(p+1:)
        call ps_table_insert (table, &
          pl, n_rad, i, pdg_work, constraints, n_in = 2)
      end do
    end if
  end subroutine if_table_insert

```

Sort before recording. In the case of the `if_table`, we do not sort the first `n_in` particle entries. Instead, we check whether they are allowed in the `pl_beam` PDG list, if that is provided.

```

<Auto components: ps table: TBP>+≡
  procedure :: record_sorted => ps_table_record_sorted

<Auto components: if table: TBP>+≡
  procedure :: record_sorted => if_table_record_sorted

<Auto components: procedures>+≡
  subroutine ps_table_record_sorted &
    (table, pl, n_loop, n_rad, constraints, passed)
    class(ps_table_t), intent(inout) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n_loop, n_rad
    type(split_constraints_t), intent(in) :: constraints
    logical, intent(out) :: passed
    call table%record (pl%sort_abs (), n_loop, n_rad, constraints, passed)
  end subroutine ps_table_record_sorted

  subroutine if_table_record_sorted &
    (table, pl, n_loop, n_rad, constraints, passed)
    class(if_table_t), intent(inout) :: table
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n_loop, n_rad

```

```

    type(split_constraints_t), intent(in) :: constraints
    logical, intent(out) :: passed
    integer :: i
    call table%record (pl%sort_abs (2), n_loop, n_rad, constraints, passed)
end subroutine if_table_record_sorted

```

Record an entry: insert into the list. Check the ordering and insert it at the correct place, unless it is already there.

We record an array only if its mass sum is less than the total available energy. This restriction is removed by setting `constrained` to false.

```

<Auto components: ps table: TBP>+≡
    procedure :: record => ps_table_record

<Auto components: procedures>+≡
    subroutine ps_table_record (table, pl, n_loop, n_rad, constraints, passed)
        class(ps_table_t), intent(inout) :: table
        type(pdg_list_t), intent(in) :: pl
        integer, intent(in) :: n_loop, n_rad
        type(split_constraints_t), intent(in) :: constraints
        logical, intent(out) :: passed
        type(ps_entry_t), pointer :: current
        logical :: mass_limit
        if (.not. pl%is_regular ()) return
        call constraints%check_before_record (table, pl, n_loop, passed)
        if (.not. passed) return
        current => table%first
        do while (associated (current))
            if (pl == current) then
                if (n_loop == current%n_loop) return
            else if (pl < current) then
                call insert
                return
            end if
            current => current%next
        end do
        call insert
contains
        subroutine insert ()
            type(ps_entry_t), pointer :: entry
            allocate (entry)
            entry%pdg_list_t = pl
            entry%n_loop = n_loop
            entry%n_rad = n_rad
            if (associated (current)) then
                if (associated (current%previous)) then
                    current%previous%next => entry
                    entry%previous => current%previous
                else
                    table%first => entry
                end if
                entry%next => current
                current%previous => entry
            else
                if (associated (table%last)) then

```



```

        table%last%next => entry
        entry%previous => table%last
    else
        table%first => entry
    end if
    table%last => entry
end if
end subroutine insert
end subroutine ps_table_record

```

26.1.6 Tools

Compute the mass sum for a PDG list object, counting the entries with indices between (including) `n1` and `n2`. Rely on the requirement that if an entry is a PDG array, this array must be degenerate in mass.

(Auto components: procedures)+≡

```

function mass_sum (pl, n1, n2, model) result (m)
    type(pdg_list_t), intent(in) :: pl
    integer, intent(in) :: n1, n2
    class(model_data_t), intent(in), target :: model
    integer, dimension(:), allocatable :: pdg
    real(default) :: m
    type(field_data_t), pointer :: prt
    integer :: i
    m = 0
    do i = n1, n2
        pdg = pl%get (i)
        prt => model%get_field_ptr (pdg(1))
        m = m + prt%get_mass ()
    end do
end function mass_sum

```

Invert a PDG array, replacing particles by antiparticles. This depends on the model.

(Auto components: procedures)+≡

```

function invert_pdg_array (pa, model) result (pa_inv)
    type(pdg_array_t), intent(in) :: pa
    class(model_data_t), intent(in), target :: model
    type(pdg_array_t) :: pa_inv
    type(field_data_t), pointer :: prt
    integer :: i, pdg
    pa_inv = pa
    do i = 1, pa_inv%get_length ()
        pdg = pa_inv%get (i)
        prt => model%get_field_ptr (pdg)
        if (prt%has_antiparticle ()) call pa_inv%set (i, -pdg)
    end do
end function invert_pdg_array

```

26.1.7 Access results

Return the number of generated decays.

```
<Auto components: ps table: TBP>+≡
  procedure :: get_length => ps_table_get_length

<Auto components: procedures>+≡
  function ps_table_get_length (ps_table) result (n)
    class(ps_table_t), intent(in) :: ps_table
    integer :: n
    type(ps_entry_t), pointer :: entry
    n = 0
    entry => ps_table%first
    do while (associated (entry))
      n = n + 1
      entry => entry%next
    end do
  end function ps_table_get_length
```

Return an allocated array of decay products (PDG codes). If requested, return also the loop and radiation order count.

```
<Auto components: ps table: TBP>+≡
  procedure :: get_pdg_out => ps_table_get_pdg_out

<Auto components: procedures>+≡
  subroutine ps_table_get_pdg_out (ps_table, i, pa_out, n_loop, n_rad)
    class(ps_table_t), intent(in) :: ps_table
    integer, intent(in) :: i
    type(pdg_array_t), dimension(:), allocatable, intent(out) :: pa_out
    integer, intent(out), optional :: n_loop, n_rad
    type(ps_entry_t), pointer :: entry
    integer :: n, j
    n = 0
    entry => ps_table%first
    FIND_ENTRY: do while (associated (entry))
      n = n + 1
      if (n == i) then
        allocate (pa_out (entry%get_size ()))
        do j = 1, entry%get_size ()
          pa_out(j) = entry%get (j)
          if (present (n_loop)) n_loop = entry%n_loop
          if (present (n_rad)) n_rad = entry%n_rad
        end do
        exit FIND_ENTRY
      end if
      entry => entry%next
    end do FIND_ENTRY
  end subroutine ps_table_get_pdg_out
```

26.1.8 Unit tests

```
<Auto components: public>+≡
  public :: auto_components_test
```

```

<Auto components: tests>≡
  subroutine auto_components_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Auto components: execute tests>
  end subroutine auto_components_test

```

Generate Decay Table

Determine all kinematically allowed decay channels for a Higgs boson, using default parameter values.

```

<Auto components: execute tests>≡
  call test (auto_components_1, "auto_components_1", &
    "generate decay table", &
    u, results)

<Auto components: tests>+≡
  subroutine auto_components_1 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: model
    type(field_data_t), pointer :: prt
    type(ds_table_t) :: ds_table
    type(split_constraints_t) :: constraints

    write (u, "(A)")  "* Test output: auto_components_1"
    write (u, "(A)")  "* Purpose: determine Higgs decay table"
    write (u, *)

    write (u, "(A)")  "* Read Standard Model"

    call prepare_model (model, var_str ("SM"))

    prt => model%get_field_ptr (25)

    write (u, *)
    write (u, "(A)")  "* Higgs decays n = 2"
    write (u, *)

    call constraints%init (2)
    call constraints%set (1, constrain_n_tot (2))
    call constraints%set (2, constrain_mass_sum (prt%get_mass ()))

    call ds_table%make (model, 25, constraints)
    call ds_table%write (u)
    call ds_table%final ()

    write (u, *)
    write (u, "(A)")  "* Higgs decays n = 3 (w/o radiative)"
    write (u, *)

    call constraints%init (3)
    call constraints%set (1, constrain_n_tot (3))
    call constraints%set (2, constrain_mass_sum (prt%get_mass ()))

```

```

call constraints%set (3, constrain_radiation ())

call ds_table%make (model, 25, constraints)
call ds_table%write (u)
call ds_table%final ()

write (u, *)
write (u, "(A)")  "* Higgs decays n = 3 (w/ radiative)"
write (u, *)

call constraints%init (2)
call constraints%set (1, constrain_n_tot (3))
call constraints%set (2, constrain_mass_sum (prt%get_mass ()))

call ds_table%make (model, 25, constraints)
call ds_table%write (u)
call ds_table%final ()

write (u, *)
write (u, "(A)")  "* Cleanup"

call cleanup_model (model)

write (u, *)
write (u, "(A)")  "* Test output end: auto_components_1"

end subroutine auto_components_1

```

Generate radiation

Given a final state, add radiation (NLO and NNLO). We provide a list of particles that is allowed to occur in the generated final states.

```

<Auto components: execute tests>+≡
  call test (auto_components_2, "auto_components_2", &
    "generate NLO corrections, final state", &
    u, results)

<Auto components: tests>+≡
  subroutine auto_components_2 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: model
    type(pdg_list_t), dimension(:), allocatable :: pl, pl_zzh
    type(pdg_list_t) :: pl_match
    type(fs_table_t) :: fs_table
    type(split_constraints_t) :: constraints
    real(default) :: sqrts
    integer :: i

    write (u, "(A)")  "* Test output: auto_components_2"
    write (u, "(A)")  "* Purpose: generate radiation (NLO)"
    write (u, *)

```

```

write (u, "(A)")  "* Read Standard Model"

call prepare_model (model, var_str ("SM"))

write (u, *)
write (u, "(A)")  "* LO final state"
write (u, *)

allocate (pl (2))
call pl(1)%init (2)
call pl(1)%set (1, 1)
call pl(1)%set (2, -1)
call pl(2)%init (2)
call pl(2)%set (1, 21)
call pl(2)%set (2, 21)
do i = 1, 2
    call pl(i)%write (u); write (u, *)
end do

write (u, *)
write (u, "(A)")  "* Initialize FS table"
write (u, *)

call constraints%init (1)
call constraints%set (1, constrain_n_tot (3))

call fs_table%init (model, pl, constraints)
call fs_table%write (u)

write (u, *)
write (u, "(A)")  "* Generate NLO corrections, unconstrained"
write (u, *)

call fs_table%radiate (constraints)
call fs_table%write (u)
call fs_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NLO corrections, &
    &complete but mass-constrained"
write (u, *)

sqrts = 50

call constraints%init (2)
call constraints%set (1, constrain_n_tot (3))
call constraints%set (2, constrain_mass_sum (sqrts))

call fs_table%init (model, pl, constraints)
call fs_table%radiate (constraints)
call fs_table%write (u)
call fs_table%final ()

write (u, *)

```

```

write (u, "(A)")  "* Generate NLO corrections, restricted"
write (u, *)

call pl_match%init ([1, -1, 21])

call constraints%init (2)
call constraints%set (1, constrain_n_tot (3))
call constraints%set (2, constrain_insert (pl_match))

call fs_table%init (model, pl, constraints)
call fs_table%radiate (constraints)
call fs_table%write (u)
call fs_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NNLO corrections, restricted, with one loop"
write (u, *)

call pl_match%init ([1, -1, 21])

call constraints%init (3)
call constraints%set (1, constrain_n_tot (4))
call constraints%set (2, constrain_n_loop (1))
call constraints%set (3, constrain_insert (pl_match))

call fs_table%init (model, pl, constraints)
call fs_table%enable_loops ()
call fs_table%radiate (constraints)
call fs_table%write (u)
call fs_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NNLO corrections, restricted, with loops"
write (u, *)

call constraints%init (2)
call constraints%set (1, constrain_n_tot (4))
call constraints%set (2, constrain_insert (pl_match))

call fs_table%init (model, pl, constraints)
call fs_table%enable_loops ()
call fs_table%radiate (constraints)
call fs_table%write (u)
call fs_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NNLO corrections, restricted, to Z Z H, &
&no loops"
write (u, *)

allocate (pl_zzh (1))
call pl_zzh(1)%init (3)
call pl_zzh(1)%set (1, 23)
call pl_zzh(1)%set (2, 23)

```

```

call pl_zzh(1)%set (3, 25)

call constraints%init (3)
call constraints%set (1, constrain_n_tot (5))
call constraints%set (2, constrain_mass_sum (500._default))
call constraints%set (3, constrain_require (pl_zzh(1)))

call fs_table%init (model, pl_zzh, constraints)
call fs_table%radiate (constraints)
call fs_table%write (u)
call fs_table%final ()

call cleanup_model (model)

write (u, *)
write (u, "(A)")  "** Test output end: auto_components_2"

end subroutine auto_components_2

```

Generate radiation from initial and final state

Given a process, add radiation (NLO and NNLO). We provide a list of particles that is allowed to occur in the generated final states.

```

<Auto components: execute tests>+≡
  call test (auto_components_3, "auto_components_3", &
    "generate NLO corrections, in and out", &
    u, results)

<Auto components: tests>+≡
  subroutine auto_components_3 (u)
    integer, intent(in) :: u
    class(model_data_t), pointer :: model
    type(pdg_list_t), dimension(:), allocatable :: pl_in, pl_out
    type(pdg_list_t) :: pl_match, pl_beam
    type(if_table_t) :: if_table
    type(split_constraints_t) :: constraints
    real(default) :: sqrts
    integer :: i

    write (u, "(A)")  "** Test output: auto_components_3"
    write (u, "(A)")  "**  Purpose: generate radiation (NLO)"
    write (u, *)

    write (u, "(A)")  "** Read Standard Model"

    call prepare_model (model, var_str ("SM"))

    write (u, *)
    write (u, "(A)")  "** LO initial state"
    write (u, *)

    allocate (pl_in (2))
    call pl_in(1)%init (2)

```

```

call pl_in(1)%set (1, 1)
call pl_in(1)%set (2, -1)
call pl_in(2)%init (2)
call pl_in(2)%set (1, -1)
call pl_in(2)%set (2, 1)
do i = 1, 2
  call pl_in(i)%write (u); write (u, *)
end do

write (u, *)
write (u, "(A)")  "* LO final state"
write (u, *)

allocate (pl_out (1))
call pl_out(1)%init (1)
call pl_out(1)%set (1, 23)
call pl_out(1)%write (u); write (u, *)

write (u, *)
write (u, "(A)")  "* Initialize FS table"
write (u, *)

call constraints%init (1)
call constraints%set (1, constrain_n_tot (4))

call if_table%init (model, pl_in, pl_out, constraints)
call if_table%write (u)

write (u, *)
write (u, "(A)")  "* Generate NLO corrections, unconstrained"
write (u, *)

call if_table%radiate (constraints)
call if_table%write (u)
call if_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NLO corrections, &
                  &complete but mass-constrained"
write (u, *)

sqrts = 100
call constraints%init (2)
call constraints%set (1, constrain_n_tot (4))
call constraints%set (2, constrain_mass_sum (sqrts))

call if_table%init (model, pl_in, pl_out, constraints)
call if_table%radiate (constraints)
call if_table%write (u)
call if_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NLO corrections, &
                  &mass-constrained, restricted beams"

```



```

write (u, *)

call pl_beam%init (3)
call pl_beam%set (1, 1)
call pl_beam%set (2, -1)
call pl_beam%set (3, 21)

call constraints%init (3)
call constraints%set (1, constrain_n_tot (4))
call constraints%set (2, constrain_in_state (pl_beam))
call constraints%set (3, constrain_mass_sum (sqrts))

call if_table%init (model, pl_in, pl_out, constraints)
call if_table%radiate (constraints)
call if_table%write (u)
call if_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NLO corrections, restricted"
write (u, *)

call pl_match%init ([1, -1, 21])

call constraints%init (4)
call constraints%set (1, constrain_n_tot (4))
call constraints%set (2, constrain_in_state (pl_beam))
call constraints%set (3, constrain_mass_sum (sqrts))
call constraints%set (4, constrain_insert (pl_match))

call if_table%init (model, pl_in, pl_out, constraints)
call if_table%radiate (constraints)
call if_table%write (u)
call if_table%final ()

write (u, *)
write (u, "(A)")  "* Generate NNLO corrections, restricted, Z preserved, &
                  &with loops"
write (u, *)

call constraints%init (5)
call constraints%set (1, constrain_n_tot (5))
call constraints%set (2, constrain_in_state (pl_beam))
call constraints%set (3, constrain_mass_sum (sqrts))
call constraints%set (4, constrain_insert (pl_match))
call constraints%set (5, constrain_require (pl_out(1)))

call if_table%init (model, pl_in, pl_out, constraints)
call if_table%enable_loops ()
call if_table%radiate (constraints)
call if_table%write (u)
call if_table%final ()

call cleanup_model (model)

```

```

        write (u, *)
        write (u, "(A)")  "* Test output end: auto_components_3"

    end subroutine auto_components_3

```

26.2 Creating the real flavor structure

```

<radiation_generator.f90>≡
<File header>

module radiation_generator

<Use kinds>
<Use strings>
    use diagnostics
    use format_utils, only: write_separator
    use os_interface
    use models
    use pdg_arrays
    use particle_specifiers
    use model_data
    use auto_components
    use physics_defs
    use unit_tests

    implicit none
    private

<radiation_generator: public>

<radiation_generator: types>

<radiation_generator: interfaces>

contains

<radiation_generator: procedures>

end module radiation_generator

<radiation_generator: types>≡
    type :: pdg_sorter_t
        integer :: pdg
        logical :: checked = .false.
        integer :: associated_born = 0
    end type pdg_sorter_t

<radiation_generator: types>+≡
    type :: pdg_states_t
        type(pdg_array_t), dimension(:), allocatable :: pdg
        type(pdg_states_t), pointer :: next
        integer :: n_particles

```

```

contains
  <radiation generator: pdg states: TBP>
end type pdg_states_t

<radiation generator: types>+≡
type :: reshuffle_list_t
  integer, dimension(:), allocatable :: ii
  type(reshuffle_list_t), pointer :: next => null ()
contains
  <radiation generator: reshuffle list: TBP>
end type reshuffle_list_t

<radiation generator: reshuffle list: TBP>≡
  procedure :: append => reshuffle_list_append

<radiation generator: procedures>≡
  subroutine reshuffle_list_append (rlist, ii)
    class(reshuffle_list_t), intent(inout) :: rlist
    integer, dimension(:), allocatable :: ii
    type(reshuffle_list_t), pointer :: current
    if (associated (rlist%next)) then
      current => rlist%next
    do
      if (associated (current%next)) then
        current => current%next
      else
        allocate (current%next)
        current%next%ii = ii
        exit
      end if
    end do
  else
    allocate (rlist%next)
    rlist%next%ii = ii
  end if
end subroutine reshuffle_list_append

<radiation generator: reshuffle list: TBP>+≡
  procedure :: get => reshuffle_list_get

<radiation generator: procedures>+≡
  function reshuffle_list_get (rlist, index) result (ii)
    class(reshuffle_list_t), intent(inout) :: rlist
    integer, intent(in) :: index
    integer, dimension(:), allocatable :: ii
    type(reshuffle_list_t), pointer :: current
    integer :: i
    if (associated (rlist%next)) then
      current => rlist%next
    else
      call msg_fatal ("Reshuffle list is empty")
    end if
    do i = 1, index-1
      if (associated (current%next)) then

```

```

        current => current%next
    else
        call msg_fatal ("Index exceeds size of reshuffling list")
    end if
end do
ii = current%ii
end function reshuffle_list_get

<radiation generator: public>≡
    public :: radiation_generator_t

<radiation generator: types>+≡
    type :: radiation_generator_t
        logical :: qcd_enabled = .false.
        logical :: qed_enabled = .false.
        logical :: is_gluon = .false.
        logical :: fs_gluon = .false.
        logical :: only_final_state = .true.
        type(pdg_list_t) :: pl_in, pl_out
        type(split_constraints_t) :: constraints
        integer :: n_tot
        integer :: n_in, n_out
        integer :: n_loops
        integer :: n_light_quarks
        real(default) :: mass_sum
        class(model_data_t), pointer :: radiation_model
        type(pdg_states_t) :: pdg_raw
        type(pdg_array_t), dimension(:), allocatable :: pdg_in_born, pdg_out_born
    contains
        <radiation generator: radiation generator: TBP>
    end type radiation_generator_t

<radiation generator: pdg states: TBP>≡
    procedure :: init => pdg_states_init

<radiation generator: procedures>+≡
    subroutine pdg_states_init (states)
        class(pdg_states_t), intent(inout) :: states
        nullify (states%next)
    end subroutine pdg_states_init

<radiation generator: pdg states: TBP>+≡
    procedure :: add => pdg_states_add

<radiation generator: procedures>+≡
    subroutine pdg_states_add (states, pdg)
        class(pdg_states_t), intent(inout), target :: states
        type(pdg_array_t), dimension(:), intent(in) :: pdg
        type(pdg_states_t), pointer :: current_state
        select type (states)
            type is (pdg_states_t)
                current_state => states
            do
                if (associated (current_state%next)) then

```

```

        current_state => current_state%next
    else
        allocate (current_state%next)
        nullify(current_state%next%next)
        current_state%pdg = pdg
        exit
    end if
end do
end select
end subroutine pdg_states_add

```

<radiation generator: pdg states: TBP>+≡
 procedure :: get_n_states => pdg_states_get_n_states

<radiation generator: procedures>+≡
 function pdg_states_get_n_states (states) result (n)
 class(pdg_states_t), intent(in), target :: states
 integer :: n
 type(pdg_states_t), pointer :: current_state
 n = 0
 select type(states)
 type is (pdg_states_t)
 current_state => states
 do
 if (associated (current_state%next)) then
 n = n+1
 current_state => current_state%next
 else
 exit
 end if
 end do
end select
end function pdg_states_get_n_states

<radiation generator: radiation generator: TBP>≡
 generic :: init => init_pdg_list, init_pdg_array
 procedure :: init_pdg_list => radiation_generator_init_pdg_list
 procedure :: init_pdg_array => radiation_generator_init_pdg_array

<radiation generator: procedures>+≡
 subroutine radiation_generator_init_pdg_list &
 (generator, pl_in, pl_out, qcd, qed)
 class(radiation_generator_t), intent(inout) :: generator
 type(pdg_list_t), intent(in) :: pl_in, pl_out
 logical, intent(in), optional :: qcd, qed
 if (present (qcd)) generator%qcd_enabled = qcd
 if (present (qed)) generator%qed_enabled = qed
 generator%pl_in = pl_in
 generator%pl_out = pl_out
 generator%is_gluon = pl_in%search_for_particle (GLUON)
 generator%fs_gluon = pl_out%search_for_particle (GLUON)
 generator%only_final_state = .not. (&
 generator%qcd_enabled .and. pl_in%contains_colored_particles ())
 generator%mass_sum = 0._default

```

        call generator%pdg_raw%init ()
    end subroutine radiation_generator_init_pdg_list

subroutine radiation_generator_init_pdg_array &
    (generator, pdg_in, pdg_out, qcd, qed)
    class(radiation_generator_t), intent(inout) :: generator
    type(pdg_array_t), intent(in), dimension(:) :: pdg_in, pdg_out
    logical, intent(in), optional :: qcd, qed
    type(pdg_list_t) :: pl_in, pl_out
    integer :: i
    call pl_in%init(size (pdg_in))
    call pl_out%init(size (pdg_out))
    do i = 1, size (pdg_in)
        call pl_in%set (i, pdg_in(i))
    end do
    do i = 1, size (pdg_out)
        call pl_out%set (i, pdg_out(i))
    end do
    call generator%init (pl_in, pl_out, qcd, qed)
end subroutine radiation_generator_init_pdg_array

<radiation generator: radiation generator: TBP>+≡
    procedure :: init_radiation_model => &
        radiation_generator_init_radiation_model

<radiation generator: procedures>+≡
    subroutine radiation_generator_init_radiation_model (generator, model)
        class(radiation_generator_t), intent(inout) :: generator
        class(model_data_t), intent(in), target :: model
        generator%radiation_model => model
    end subroutine radiation_generator_init_radiation_model

<radiation generator: radiation generator: TBP>+≡
    procedure :: set_n => radiation_generator_set_n

<radiation generator: procedures>+≡
    subroutine radiation_generator_set_n (generator, n_in, n_out, n_loops)
        class(radiation_generator_t), intent(inout) :: generator
        integer, intent(in) :: n_in, n_out, n_loops
        generator%n_tot = n_in + n_out + 1
        generator%n_in = n_in
        generator%n_out = n_out
        generator%n_loops = n_loops
    end subroutine radiation_generator_set_n

<radiation generator: radiation generator: TBP>+≡
    procedure :: set_constraints => radiation_generator_set_constraints

<radiation generator: procedures>+≡
    subroutine radiation_generator_set_constraints &
        (generator, set_n_loop, set_mass_sum, &
        set_selected_particles, set_required_particles)
        class(radiation_generator_t), intent(inout), target :: generator
        logical, intent(in) :: set_n_loop

```

```

logical, intent(in) :: set_mass_sum
logical, intent(in) :: set_selected_particles
logical, intent(in) :: set_required_particles
integer :: i, j, n, n_constraints
type(pdg_list_t) :: pl_req, pl_insert
type(pdg_list_t) :: pl_antiparticles
type(pdg_array_t) :: pdg_gluon, pdg_photon
type(pdg_array_t) :: pdg_add, pdg_tmp
integer :: i_skip, last_index
integer :: n_new_particles
i_skip = -1

n_constraints = 1 + count([set_n_loop, set_mass_sum, &
    set_selected_particles, set_required_particles])
associate (constraints => generator%constraints)
    n = 1
    call constraints%init (n_constraints)
    call constraints%set (n, constrain_n_tot (generator%n_tot))
    n = n+1
    if (set_n_loop) then
        call constraints%set (n, constrain_n_loop(generator%n_loops))
        n = n+1
    end if
    if (set_mass_sum) then
        call constraints%set (n, constrain_mass_sum(generator%mass_sum))
        n = n+1
    end if
    if (set_required_particles) then
        if (generator%fs_gluon) then
            do i = 1, generator%n_out
                pdg_tmp = generator%pl_out%get(i)
                if (pdg_tmp%search_for_particle (GLUON)) then
                    i_skip = i
                    exit
                end if
            end do
            call pl_req%init (generator%n_out-1)
        else
            call pl_req%init (generator%n_out)
        end if
        do i = 1, generator%n_out
            if (i == i_skip) cycle
            call pl_req%set (i, generator%pl_out%get(i))
        end do
        call constraints%set (n, constrain_require (pl_req))
        n = n+1
    end if
    if (set_selected_particles) then
        if (generator%only_final_state ) then
            call pl_insert%init (generator%n_out+1)
            do i = 1, generator%n_out
                call pl_insert%set(i, generator%pl_out%get(i))
            end do
            last_index = generator%n_out
        end if
    end if
end associate

```

```

else
  call generator%pl_in%create_antiparticles (pl_antiparticles, n_new_particles)
  call pl_insert%init (generator%n_tot+n_new_particles+1)
  do i = 1, generator%n_in
    call pl_insert%set(i, generator%pl_in%get(i))
  end do
  do i = 1, generator%n_out
    j = i + generator%n_in
    call pl_insert%set(j, generator%pl_out%get(i))
  end do
  do i = 1, n_new_particles
    j = i + generator%n_in + generator%n_out
    call pl_insert%set(j, pl_antiparticles%get(i))
  end do
  last_index = generator%n_tot + n_new_particles + 1
end if
pdg_gluon = GLUON; pdg_photon = PHOTON
if (generator%qcd_enabled) pdg_add = pdg_add // pdg_gluon
if (generator%qed_enabled) pdg_add = pdg_add // pdg_photon
call pl_insert%set (last_index, pdg_add)
call constraints%set (n, constrain_insert (pl_insert))
end if
end associate

end subroutine radiation_generator_set_constraints

```

(radiation generator: radiation generator: TBP)+≡

```

procedure :: generate => radiation_generator_generate

```

(radiation generator: procedures)+≡

```

subroutine radiation_generator_generate (generator, prt_tot_in, prt_tot_out)
  type :: prt_array_t
    type(string_t), dimension(:), allocatable :: prt
  end type
  integer, parameter :: n_flv_max = 10
  class(radiation_generator_t), intent(inout) :: generator
  type(string_t), intent(out), dimension(:), allocatable :: prt_tot_in, prt_tot_out
  type(prt_array_t), dimension(n_flv_max) :: prt_in, prt_out
  type(prt_array_t), dimension(n_flv_max) :: prt_out0, prt_in0
  type(pdg_array_t), dimension(:), allocatable :: pdg_tmp, pdg_out, pdg_in
  type(if_table_t) :: if_table
  type(pdg_list_t), dimension(:), allocatable :: pl_in, pl_out
  integer :: i, j
  integer, dimension(:), allocatable :: reshuffle_list_local
  type(reshuffle_list_t) :: reshuffle_list
  logical :: found
  integer :: flv
  integer :: n_out
  type(string_t), dimension(:), allocatable :: buf
  integer :: i_buf

  allocate (pl_in (1), pl_out (1))
  found = .false.
  flv = 0

```



```

pl_in(1) = generator%pl_in
pl_out(1) = generator%pl_out

call pl_in(1)%create_pdg_array (pdg_in)
call pl_out(1)%create_pdg_array (pdg_out)

call if_table%init &
      (generator%radiation_model, pl_in, pl_out, generator%constraints)
call if_table%radiate (generator%constraints)

do i = 1, if_table%get_length ()
  call if_table%get_pdg_out (i, pdg_tmp)
  if (size (pdg_tmp) == generator%n_tot) then
    call if_table%get_particle_string (i, 2, &
      prt_in0(fl_v+1)%prt, prt_out0(fl_v+1)%prt)
    call pdg_reshuffle (pdg_out, pdg_tmp, reshuffle_list_local)
    call reshuffle_list%append (reshuffle_list_local)
    found = .true.
    fl_v = fl_v+1
  end if
end do

if (found) then
  do i = 1, fl_v
    allocate (prt_in(i)%prt (generator%n_in))
    allocate (prt_out(i)%prt (generator%n_tot-generator%n_in))
  end do
  allocate (prt_tot_in (generator%n_in))
  allocate (prt_tot_out (generator%n_tot-generator%n_in))
  allocate (buf (generator%n_tot))
  buf = ""

  do j = 1, fl_v
    do i = 1, generator%n_in
      prt_in(j)%prt(i) = prt_in0(j)%prt(i)
      call fill_buffer (buf(i), prt_in0(j)%prt(i))
    end do
  end do
  prt_tot_in = buf(1:generator%n_in)

  do j = 1, fl_v
    reshuffle_list_local = reshuffle_list%get(j)
    do i = 1, size (reshuffle_list_local)
      prt_out(j)%prt(reshuffle_list_local(i)) = prt_out0(j)%prt(i)
      i_buf = reshuffle_list_local(i) + generator%n_in
      call fill_buffer (buf(i_buf), &
        prt_out(j)%prt(reshuffle_list_local(i)))
    end do
  end do
  prt_tot_out = buf(generator%n_in+1:generator%n_tot)
else
  call msg_fatal ("No NLO QCD corrections for this process!")
end if

```

```

contains
subroutine pdg_reshuffle (pdg_born, pdg_real, list)
  type(pdg_array_t), intent(in), dimension(:) :: pdg_born, pdg_real
  integer, intent(out), dimension(:), allocatable :: list
  type(pdg_sorter_t), dimension(:), allocatable :: sort_born
  type(pdg_sorter_t), dimension(:), allocatable :: sort_real
  integer :: i, i_min
  integer :: n_born, n_real
  integer :: ib, ir
  logical :: check
  integer, parameter :: n_in = 2

  n_born = size (pdg_born); n_real = size (pdg_real)
  allocate (list (n_real-n_in))
  allocate (sort_born (n_born))
  allocate (sort_real (n_real-n_in))

  sort_born%pdg = pdg_born%get ()
  sort_real%pdg = pdg_real(3:n_real)%get ()

  do ib = 1, n_born
    if (any (sort_born(ib)%pdg == sort_real%pdg)) &
      call associate_born_indices (sort_born(ib), sort_real, ib, n_real)
  end do

  i_min = maxval (sort_real%associated_born) + 1

  do ir = 1, n_real-2
    if (sort_real(ir)%associated_born == 0) then
      sort_real(ir)%associated_born = i_min
      i_min = i_min+1
    end if
  end do

  list = sort_real%associated_born

end subroutine pdg_reshuffle

subroutine associate_born_indices (sort_born, sort_real, ib, n_real)
  type(pdg_sorter_t), intent(in) :: sort_born
  type(pdg_sorter_t), intent(inout), dimension(:) :: sort_real
  integer, intent(in) :: ib, n_real
  integer :: ir

  do ir = 1, n_real-2
    if (sort_born%pdg == sort_real(ir)%pdg &
      .and..not. sort_real(ir)%checked) then
      sort_real(ir)%associated_born = ib
      sort_real(ir)%checked = .true.
      exit
    end if
  end do
end subroutine associate_born_indices

```

```

subroutine fill_buffer (buffer, particle)
  type(string_t), intent(inout) :: buffer
  type(string_t), intent(in) :: particle
  logical :: particle_present
  if (len(buffer) > 0) then
    particle_present = check_for_substring (char(buffer), char(particle))
    if (.not. particle_present) buffer = buffer // ":" // particle
  else
    buffer = buffer // particle
  end if
end subroutine fill_buffer

function check_for_substring (buffer, substring) result (exist)
  character(len=*), intent(in) :: buffer
  character(len=*), intent(in) :: substring
  character(len=50) :: buffer_internal
  logical :: exist
  integer :: i_first, i_last
  exist = .false.
  i_first = 1; i_last = 1
  do
    if (buffer(i_last:i_last) == ":") then
      buffer_internal = buffer (i_first:i_last-1)
      if (buffer_internal == substring) then
        exist = .true.
        exit
      end if
      i_first = i_last+1; i_last = i_first+1
      if (i_last > len(buffer)) exit
    else if (i_last == len(buffer)) then
      buffer_internal = buffer (i_first:i_last)
      exist = (buffer_internal == substring)
      exit
    else
      i_last = i_last+1
      if (i_last > len(buffer)) exit
    end if
  end do
end function check_for_substring
end subroutine radiation_generator_generate

```

(radiation generator: radiation generator: TBP)+≡

```

  procedure :: get_raw_states => radiation_generator_get_raw_states

```

(radiation generator: procedures)+≡

```

function radiation_generator_get_raw_states (generator) result (raw_states)
  class(radiation_generator_t), intent(in), target :: generator
  integer, dimension(:,:), allocatable :: raw_states
  type(pdg_states_t), pointer :: state
  integer :: n_states, n_particles
  integer :: i_state
  integer :: j
  state => generator%pdg_raw
  n_states = generator%pdg_raw%get_n_states ()

```

```

n_particles = size (generator%pdg_raw%pdg)
allocate (raw_states (n_particles, n_states))
do i_state = 1, n_states
  do j = 1, n_particles
    raw_states (j, i_state) = state%pdg(j)%get ()
  end do
  state => state%next
end do
end function radiation_generator_get_raw_states

<radiation generator: radiation generator: TBP>+≡
  procedure :: save_born_raw => radiation_generator_save_born_raw

<radiation generator: procedures>+≡
  subroutine radiation_generator_save_born_raw (generator, pdg_in, pdg_out)
    class(radiation_generator_t), intent(inout) :: generator
    type(pdg_array_t), dimension(:), allocatable, intent(in) :: pdg_in, pdg_out
    integer :: i
    !!! !!! !!! Explicit allocation due to gfortran 4.7.4
    allocate (generator%pdg_in_born (size (pdg_in)))
    do i = 1, size (pdg_in)
      generator%pdg_in_born(i) = pdg_in(i)
    end do
    allocate (generator%pdg_out_born (size (pdg_out)))
    do i = 1, size (pdg_out)
      generator%pdg_out_born(i) = pdg_out(i)
    end do
  end subroutine radiation_generator_save_born_raw

<radiation generator: radiation generator: TBP>+≡
  procedure :: get_born_raw => radiation_generator_get_born_raw

<radiation generator: procedures>+≡
  function radiation_generator_get_born_raw (generator) result (flv_born)
    class(radiation_generator_t), intent(in) :: generator
    integer, dimension(:,:), allocatable :: flv_born
    integer :: i_part, n_particles
    n_particles = size (generator%pdg_in_born) + size (generator%pdg_out_born)
    allocate (flv_born (n_particles, 1))
    flv_born(1,1) = generator%pdg_in_born(1)%get ()
    flv_born(2,1) = generator%pdg_in_born(2)%get ()
    do i_part = 3, n_particles
      flv_born(i_part, 1) = generator%pdg_out_born(i_part-2)%get ()
    end do
  end function radiation_generator_get_born_raw

```

26.2.1 Unit tests

```

<radiation generator: public>+≡
  public :: radiation_generator_test

<radiation generator: procedures>+≡
  subroutine radiation_generator_test (u, results)
    integer, intent(in) :: u

```

```

type(test_results_t), intent(inout) :: results
call test(radiation_generator_1, "radiation_generator_1", &
    "Test the generator of N+1-particle flavor structures", &
    u, results)
end subroutine radiation_generator_test

```

(radiation generator: procedures)+≡

```

subroutine radiation_generator_1 (u)
    integer, intent(in) :: u
    type (radiation_generator_t) :: generator
    type(pdg_array_t), dimension(:), allocatable :: pdg_in, pdg_out
    type(string_t), dimension(:), allocatable :: prt_strings_in
    type(string_t), dimension(:), allocatable :: prt_strings_out
    type(os_data_t) :: os_data
    type(model_list_t) :: model_list
    type(model_t), pointer :: radiation_model => null ()
    integer :: i

    write (u, "(A)") "* Test output: radiation_generator_1"
    write (u, "(A)") "* Purpose: Create N+1-particle flavor structures from predefined N-particle"
    write (u, "(A)") "* One additional strong coupling, no additional electroweak coupling"
    write (u, "(A)")
    write (u, "(A)") "* Loading radiation model: SM_rad.mdl"

    call syntax_model_file_init ()
    call os_data_init (os_data)
    call model_list%read_model &
        (var_str ("SM_rad"), var_str ("SM_rad.mdl"), &
        os_data, radiation_model)
    call generator%init_radiation_model (radiation_model)
    write (u, "(A)") "* Success"

    allocate (pdg_in (2))
    pdg_in(1) = 11; pdg_in(2) = -11

    write (u, "(A)") "* Start checking processes"
    call write_separator (u)

    write (u, "(A)") "* Process 1: Quark-antiquark production"
    allocate (pdg_out(2))
    pdg_out(1) = 2; pdg_out(2) = -2
    call test_process (generator, pdg_in, pdg_out, u)
    deallocate (pdg_out)

    write (u, "(A)") "* Process 2: Quark-antiquark production with additional gluon"
    allocate (pdg_out(3))
    pdg_out(1) = 2; pdg_out(2) = -2; pdg_out(3) = 21
    call test_process (generator, pdg_in, pdg_out, u)
    deallocate (pdg_out)

    write (u, "(A)") "* Process 3: Z + jets"
    allocate (pdg_out(3))
    pdg_out(1) = 2; pdg_out(2) = -2; pdg_out(3) = 23
    call test_process (generator, pdg_in, pdg_out, u)

```

```

deallocate (pdg_out)

write (u, "(A)") "* Process 4: Top Decay"
allocate (pdg_out(4))
pdg_out(1) = 24; pdg_out(2) = -24
pdg_out(3) = 5; pdg_out(4) = -5
call test_process (generator, pdg_in, pdg_out, u)
deallocate (pdg_out)

write (u, "(A)") "* Process 5: Production of four quarks"
allocate (pdg_out(4))
pdg_out(1) = 2; pdg_out(2) = -2;
pdg_out(3) = 2; pdg_out(4) = -2
call test_process (generator, pdg_in, pdg_out, u)
deallocate (pdg_out); deallocate (pdg_in)

write (u, "(A)") "* Process 6: Drell-Yan lepto-production"
allocate (pdg_in (2)); allocate (pdg_out (2))
pdg_in(1) = 2; pdg_in(2) = -2
pdg_out(1) = 11; pdg_out(2) = -11
call test_process (generator, pdg_in, pdg_out, u)
deallocate (pdg_out); deallocate (pdg_in)

write (u, "(A)") "* Process 7: WZ production at hadron-colliders"
allocate (pdg_in (2)); allocate (pdg_out (2))
pdg_in(1) = 1; pdg_in(2) = -2
pdg_out(1) = -24; pdg_out(2) = 23
call test_process (generator, pdg_in, pdg_out, u)
deallocate (pdg_out); deallocate (pdg_in)

contains
subroutine test_process (generator, pdg_in, pdg_out, u)
  type(radiation_generator_t), intent(inout) :: generator
  type(pdg_array_t), dimension(:), intent(in) :: pdg_in, pdg_out
  integer, intent(in) :: u
  type(string_t), dimension(:), allocatable :: prt_strings_in
  type(string_t), dimension(:), allocatable :: prt_strings_out
  write (u, "(A)") "* Leading order: "
  write (u, "(A)", advance = 'no') '* Incoming: '
  call write_pdg_array (pdg_in, u)
  write (u, "(A)", advance = 'no') '* Outgoing: '
  call write_pdg_array (pdg_out, u)

  call generator%init (pdg_in, pdg_out, qcd = .true., qed = .false.)
  call generator%set_n (2, size(pdg_out), 0)
  call generator%set_constraints (.false., .false., .true., .true.)
  call generator%generate (prt_strings_in, prt_strings_out)
  write (u, "(A)") "* Additional radiation: "
  write (u, "(A)") "* Incoming: "
  call write_particle_string (prt_strings_in, u)
  write (u, "(A)") "* Outgoing: "
  call write_particle_string (prt_strings_out, u)
  call write_separator(u)
end subroutine test_process

```

```

subroutine write_pdg_array (pdg, u)
  type(pdg_array_t), dimension(:), intent(in) :: pdg
  integer, intent(in) :: u
  integer :: i
  do i = 1, size (pdg)
    call pdg(i)%write (u)
  end do
  write (u, "(A)")
end subroutine write_pdg_array

subroutine write_particle_string (prt, u)
  type(string_t), dimension(:), intent(in) :: prt
  integer, intent(in) :: u
  integer :: i
  do i = 1, size (prt)
    write (u, "(A,1X)", advance = "no") char (prt(i))
  end do
  write (u, "(A)")
end subroutine write_particle_string
end subroutine radiation_generator_1

```

26.3 Sindarin Expression Implementation

This module defines expressions of all kinds, represented in a tree structure, for repeated evaluation. This provides an implementation of the `expr_base` abstract type.

We have two flavors of expressions: one with particles and one without particles. The latter version is used for defining cut/selection criteria and for online analysis.

```
(eval_trees.f90)≡  
  (File header)  
  
  module eval_trees  
  
    use, intrinsic :: iso_c_binding !NODEP!  
    (Use kinds)  
    (Use strings)  
    use io_units  
    use constants  
    use format_defs, only: FMT_19  
    use unit_tests  
    use diagnostics  
    use lorentz  
    use md5  
    use formats  
    use sorting  
    use ifiles  
    use lexers  
    use syntax_rules  
    use parser  
    use analysis  
    use jets  
    use pdg_arrays  
    use subevents  
    use user_code_interface  
    use var_base  
    use expr_base  
    use variables  
    use observables  
  
    (Standard module head)  
  
    (Eval trees: public)  
  
    (Eval trees: types)  
  
    (Eval trees: interfaces)  
  
    (Eval trees: variables)  
  
    contains  
  
    (Eval trees: procedures)
```


<Eval trees: tests>

end module eval_trees

26.3.1 Tree nodes

The evaluation tree consists of branch nodes (unary and binary) and of leaf nodes, originating from a common root. The node object should be polymorphic. For the time being, polymorphism is emulated here. This means that we have to maintain all possibilities that the node may hold, including associated procedures as pointers.

The following parameter values characterize the node. Unary and binary operators have sub-nodes. The other are leaf nodes. Possible leafs are literal constants or named-parameter references.

<Eval trees: types>≡

```
integer, parameter :: EN_UNKNOWN = 0, EN_UNARY = 1, EN_BINARY = 2
integer, parameter :: EN_CONSTANT = 3, EN_VARIABLE = 4
integer, parameter :: EN_CONDITIONAL = 5, EN_BLOCK = 6
integer, parameter :: EN_RECORD_CMD = 7
integer, parameter :: EN_OBS1_INT = 11, EN_OBS2_INT = 12
integer, parameter :: EN_OBS1_REAL = 21, EN_OBS2_REAL = 22
integer, parameter :: EN_UOBS1_INT = 31, EN_UOBS2_INT = 32
integer, parameter :: EN_UOBS1_REAL = 41, EN_UOBS2_REAL = 42
integer, parameter :: EN_PRT_FUN_UNARY = 101, EN_PRT_FUN_BINARY = 102
integer, parameter :: EN_EVAL_FUN_UNARY = 111, EN_EVAL_FUN_BINARY = 112
integer, parameter :: EN_LOG_FUN_UNARY = 121, EN_LOG_FUN_BINARY = 122
integer, parameter :: EN_INT_FUN_UNARY = 131, EN_INT_FUN_BINARY = 132
integer, parameter :: EN_REAL_FUN_UNARY = 141, EN_REAL_FUN_BINARY = 142
integer, parameter :: EN_FORMAT_STR = 161
```

<Eval trees: types>+≡

```
type :: eval_node_t
private
type(string_t) :: tag
integer :: type = EN_UNKNOWN
integer :: result_type = V_NONE
type(var_list_t), pointer :: var_list => null ()
type(string_t) :: var_name
logical, pointer :: value_is_known => null ()
logical,          pointer :: lval => null ()
integer,          pointer :: ival => null ()
real(default),    pointer :: rval => null ()
complex(default), pointer :: cval => null ()
type(subevt_t),   pointer :: pval => null ()
type(pdg_array_t), pointer :: aval => null ()
type(string_t),   pointer :: sval => null ()
type(eval_node_t), pointer :: arg0 => null ()
type(eval_node_t), pointer :: arg1 => null ()
type(eval_node_t), pointer :: arg2 => null ()
type(eval_node_t), pointer :: arg3 => null ()
type(eval_node_t), pointer :: arg4 => null ()
procedure(obs_unary_int), nopass, pointer :: obs1_int => null ()
```

```

procedure(obs_unary_real), nopass, pointer :: obs1_real => null ()
procedure(obs_binary_int), nopass, pointer :: obs2_int => null ()
procedure(obs_binary_real), nopass, pointer :: obs2_real => null ()
integer, pointer :: prt_type => null ()
integer, pointer :: index => null ()
real(default), pointer :: tolerance => null ()
integer, pointer :: jet_algorithm => null ()
real(default), pointer :: jet_r => null ()
type(prt_t), pointer :: prt1 => null ()
type(prt_t), pointer :: prt2 => null ()
procedure(unary_log), nopass, pointer :: op1_log => null ()
procedure(unary_int), nopass, pointer :: op1_int => null ()
procedure(unary_real), nopass, pointer :: op1_real => null ()
procedure(unary_cmplx), nopass, pointer :: op1_cmplx => null ()
procedure(unary_pdg), nopass, pointer :: op1_pdg => null ()
procedure(unary_sev), nopass, pointer :: op1_sev => null ()
procedure(unary_str), nopass, pointer :: op1_str => null ()
procedure(unary_cut), nopass, pointer :: op1_cut => null ()
procedure(unary_evi), nopass, pointer :: op1_evi => null ()
procedure(unary_evr), nopass, pointer :: op1_evr => null ()
procedure(binary_log), nopass, pointer :: op2_log => null ()
procedure(binary_int), nopass, pointer :: op2_int => null ()
procedure(binary_real), nopass, pointer :: op2_real => null ()
procedure(binary_cmplx), nopass, pointer :: op2_cmplx => null ()
procedure(binary_pdg), nopass, pointer :: op2_pdg => null ()
procedure(binary_sev), nopass, pointer :: op2_sev => null ()
procedure(binary_str), nopass, pointer :: op2_str => null ()
procedure(binary_cut), nopass, pointer :: op2_cut => null ()
procedure(binary_evi), nopass, pointer :: op2_evi => null ()
procedure(binary_evr), nopass, pointer :: op2_evr => null ()
end type eval_node_t

```

Finalize a node recursively. Allocated constants are deleted, pointers are ignored.

(Eval trees: procedures)≡

```

recursive subroutine eval_node_final_rec (node)
  type(eval_node_t), intent(inout) :: node
  select case (node%type)
  case (EN_UNARY)
    call eval_node_final_rec (node%arg1)
  case (EN_BINARY)
    call eval_node_final_rec (node%arg1)
    call eval_node_final_rec (node%arg2)
  case (EN_CONDITIONAL)
    call eval_node_final_rec (node%arg0)
    call eval_node_final_rec (node%arg1)
    call eval_node_final_rec (node%arg2)
  case (EN_BLOCK)
    call eval_node_final_rec (node%arg0)
    call eval_node_final_rec (node%arg1)
  case (EN_PRT_FUN_UNARY, EN_EVAL_FUN_UNARY, &
        EN_LOG_FUN_UNARY, EN_INT_FUN_UNARY, EN_REAL_FUN_UNARY)
    if (associated (node%arg0)) call eval_node_final_rec (node%arg0)

```

```

        call eval_node_final_rec (node%arg1)
        deallocate (node%index)
        deallocate (node%prt1)
    case (EN_PRT_FUN_BINARY, EN_EVAL_FUN_BINARY, &
          EN_LOG_FUN_BINARY, EN_INT_FUN_BINARY, EN_REAL_FUN_BINARY)
        if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
        call eval_node_final_rec (node%arg1)
        call eval_node_final_rec (node%arg2)
        deallocate (node%index)
        deallocate (node%prt1)
        deallocate (node%prt2)
    case (EN_FORMAT_STR)
        if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
        if (associated (node%arg1)) call eval_node_final_rec (node%arg1)
        deallocate (node%ival)
    case (EN_RECORD_CMD)
        if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
        if (associated (node%arg1)) call eval_node_final_rec (node%arg1)
        if (associated (node%arg2)) call eval_node_final_rec (node%arg2)
        if (associated (node%arg3)) call eval_node_final_rec (node%arg3)
        if (associated (node%arg4)) call eval_node_final_rec (node%arg4)
    end select
    select case (node%type)
    case (EN_UNARY, EN_BINARY, EN_CONDITIONAL, EN_CONSTANT, EN_BLOCK, &
          EN_PRT_FUN_UNARY, EN_PRT_FUN_BINARY, &
          EN_EVAL_FUN_UNARY, EN_EVAL_FUN_BINARY, &
          EN_LOG_FUN_UNARY, EN_LOG_FUN_BINARY, &
          EN_INT_FUN_UNARY, EN_INT_FUN_BINARY, &
          EN_REAL_FUN_UNARY, EN_REAL_FUN_BINARY, &
          EN_FORMAT_STR, EN_RECORD_CMD)
        select case (node%result_type)
        case (V_LOG); deallocate (node%lval)
        case (V_INT); deallocate (node%ival)
        case (V_REAL); deallocate (node%rval)
        case (V_CMPLX); deallocate (node%cval)
        case (V_SEV); deallocate (node%pval)
        case (V_PDG); deallocate (node%aval)
        case (V_STR); deallocate (node%sval)
        end select
        deallocate (node%value_is_known)
    end select
end subroutine eval_node_final_rec

```

Leaf nodes

Initialize a leaf node with a literal constant.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_log (node, lval)
    type(eval_node_t), intent(out) :: node
    logical, intent(in) :: lval
    node%type = EN_CONSTANT
    node%result_type = V_LOG
    allocate (node%lval, node%value_is_known)

```

```

        node%lval = lval
        node%value_is_known = .true.
    end subroutine eval_node_init_log

subroutine eval_node_init_int (node, ival)
    type(eval_node_t), intent(out) :: node
    integer, intent(in) :: ival
    node%type = EN_CONSTANT
    node%result_type = V_INT
    allocate (node%ival, node%value_is_known)
    node%ival = ival
    node%value_is_known = .true.
end subroutine eval_node_init_int

subroutine eval_node_init_real (node, rval)
    type(eval_node_t), intent(out) :: node
    real(default), intent(in) :: rval
    node%type = EN_CONSTANT
    node%result_type = V_REAL
    allocate (node%rval, node%value_is_known)
    node%rval = rval
    node%value_is_known = .true.
end subroutine eval_node_init_real

subroutine eval_node_init_cmplx (node, cval)
    type(eval_node_t), intent(out) :: node
    complex(default), intent(in) :: cval
    node%type = EN_CONSTANT
    node%result_type = V_CMPLX
    allocate (node%cval, node%value_is_known)
    node%cval = cval
    node%value_is_known = .true.
end subroutine eval_node_init_cmplx

subroutine eval_node_init_subevt (node, pval)
    type(eval_node_t), intent(out) :: node
    type(subevt_t), intent(in) :: pval
    node%type = EN_CONSTANT
    node%result_type = V_SEV
    allocate (node%pval, node%value_is_known)
    node%pval = pval
    node%value_is_known = .true.
end subroutine eval_node_init_subevt

subroutine eval_node_init_pdg_array (node, aval)
    type(eval_node_t), intent(out) :: node
    type(pdg_array_t), intent(in) :: aval
    node%type = EN_CONSTANT
    node%result_type = V_PDG
    allocate (node%aval, node%value_is_known)
    node%aval = aval
    node%value_is_known = .true.
end subroutine eval_node_init_pdg_array

```

```

subroutine eval_node_init_string (node, sval)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: sval
  node%type = EN_CONSTANT
  node%result_type = V_STR
  allocate (node%sval, node%value_is_known)
  node%sval = sval
  node%value_is_known = .true.
end subroutine eval_node_init_string

```

Initialize a leaf node with a pointer to a named parameter

(*Eval trees: procedures*) \equiv

```

subroutine eval_node_init_log_ptr (node, name, lval, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  logical, intent(in), target :: lval
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_LOG
  node%lval => lval
  node%value_is_known => is_known
end subroutine eval_node_init_log_ptr

```

```

subroutine eval_node_init_int_ptr (node, name, ival, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  integer, intent(in), target :: ival
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_INT
  node%ival => ival
  node%value_is_known => is_known
end subroutine eval_node_init_int_ptr

```

```

subroutine eval_node_init_real_ptr (node, name, rval, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  real(default), intent(in), target :: rval
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_REAL
  node%rval => rval
  node%value_is_known => is_known
end subroutine eval_node_init_real_ptr

```

```

subroutine eval_node_init_cmplx_ptr (node, name, cval, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  complex(default), intent(in), target :: cval
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE

```

```

    node%tag = name
    node%result_type = V_CMPLX
    node%cval => cval
    node%value_is_known => is_known
end subroutine eval_node_init_cmplx_ptr

subroutine eval_node_init_subevt_ptr (node, name, pval, is_known)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(subevt_t), intent(in), target :: pval
    logical, intent(in), target :: is_known
    node%type = EN_VARIABLE
    node%tag = name
    node%result_type = V_SEV
    node%pval => pval
    node%value_is_known => is_known
end subroutine eval_node_init_subevt_ptr

subroutine eval_node_init_pdg_array_ptr (node, name, aval, is_known)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in), target :: aval
    logical, intent(in), target :: is_known
    node%type = EN_VARIABLE
    node%tag = name
    node%result_type = V_PDG
    node%aval => aval
    node%value_is_known => is_known
end subroutine eval_node_init_pdg_array_ptr

subroutine eval_node_init_string_ptr (node, name, sval, is_known)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(string_t), intent(in), target :: sval
    logical, intent(in), target :: is_known
    node%type = EN_VARIABLE
    node%tag = name
    node%result_type = V_STR
    node%sval => sval
    node%value_is_known => is_known
end subroutine eval_node_init_string_ptr

```

The procedure-pointer cases:

<Eval trees: procedures>+≡

```

subroutine eval_node_init_obs1_int_ptr (node, name, obs1_iptr, p1)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    procedure(obs_unary_int), intent(in), pointer :: obs1_iptr
    type(prt_t), intent(in), target :: p1
    node%type = EN_OBS1_INT
    node%tag = name
    node%result_type = V_INT
    node%obs1_int => obs1_iptr
    node%prt1 => p1

```

```

        allocate (node%ival, node%value_is_known)
        node%value_is_known = .false.
end subroutine eval_node_init_obs1_int_ptr

subroutine eval_node_init_obs2_int_ptr (node, name, obs2_iptr, p1, p2)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    procedure(obs_binary_int), intent(in), pointer :: obs2_iptr
    type(prt_t), intent(in), target :: p1, p2
    node%type = EN_OBS2_INT
    node%tag = name
    node%result_type = V_INT
    node%obs2_int => obs2_iptr
    node%prt1 => p1
    node%prt2 => p2
    allocate (node%ival, node%value_is_known)
    node%value_is_known = .false.
end subroutine eval_node_init_obs2_int_ptr

subroutine eval_node_init_obs1_real_ptr (node, name, obs1_rptr, p1)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    procedure(obs_unary_real), intent(in), pointer :: obs1_rptr
    type(prt_t), intent(in), target :: p1
    node%type = EN_OBS1_REAL
    node%tag = name
    node%result_type = V_REAL
    node%obs1_real => obs1_rptr
    node%prt1 => p1
    allocate (node%rval, node%value_is_known)
    node%value_is_known = .false.
end subroutine eval_node_init_obs1_real_ptr

subroutine eval_node_init_obs2_real_ptr (node, name, obs2_rptr, p1, p2)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    procedure(obs_binary_real), intent(in), pointer :: obs2_rptr
    type(prt_t), intent(in), target :: p1, p2
    node%type = EN_OBS2_REAL
    node%tag = name
    node%result_type = V_REAL
    node%obs2_real => obs2_rptr
    node%prt1 => p1
    node%prt2 => p2
    allocate (node%rval, node%value_is_known)
    node%value_is_known = .false.
end subroutine eval_node_init_obs2_real_ptr

```

These nodes refer to user-defined procedures.

<Eval trees: procedures>+≡

```

subroutine eval_node_init_uobs1_int (node, name, arg)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(eval_node_t), intent(in), target :: arg

```

```

node%type = EN_UOBS1_INT
node%tag = name
node%result_type = V_INT
allocate (node%ival, node%value_is_known)
node%value_is_known = .false.
node%arg0 => arg
end subroutine eval_node_init_uobs1_int

subroutine eval_node_init_uobs2_int (node, name, arg)
type(eval_node_t), intent(out) :: node
type(string_t), intent(in) :: name
type(eval_node_t), intent(in), target :: arg
node%type = EN_UOBS2_INT
node%tag = name
node%result_type = V_INT
allocate (node%ival, node%value_is_known)
node%value_is_known = .false.
node%arg0 => arg
end subroutine eval_node_init_uobs2_int

subroutine eval_node_init_uobs1_real (node, name, arg)
type(eval_node_t), intent(out) :: node
type(string_t), intent(in) :: name
type(eval_node_t), intent(in), target :: arg
node%type = EN_UOBS1_REAL
node%tag = name
node%result_type = V_REAL
allocate (node%rval, node%value_is_known)
node%value_is_known = .false.
node%arg0 => arg
end subroutine eval_node_init_uobs1_real

subroutine eval_node_init_uobs2_real (node, name, arg)
type(eval_node_t), intent(out) :: node
type(string_t), intent(in) :: name
type(eval_node_t), intent(in), target :: arg
node%type = EN_UOBS2_REAL
node%tag = name
node%result_type = V_REAL
allocate (node%rval, node%value_is_known)
node%value_is_known = .false.
node%arg0 => arg
end subroutine eval_node_init_uobs2_real

```

Branch nodes

Initialize a branch node, sub-nodes are given.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_branch (node, tag, result_type, arg1, arg2)
type(eval_node_t), intent(out) :: node
type(string_t), intent(in) :: tag
integer, intent(in) :: result_type
type(eval_node_t), intent(in), target :: arg1

```



```

type(eval_node_t), intent(in), target, optional :: arg2
if (present (arg2)) then
    node%type = EN_BINARY
else
    node%type = EN_UNARY
end if
node%tag = tag
node%result_type = result_type
call eval_node_allocate_value (node)
node%arg1 => arg1
if (present (arg2)) node%arg2 => arg2
end subroutine eval_node_init_branch

```

Allocate the node value according to the result type.

(Eval trees: procedures)+≡

```

subroutine eval_node_allocate_value (node)
type(eval_node_t), intent(inout) :: node
select case (node%result_type)
case (V_LOG); allocate (node%lval)
case (V_INT); allocate (node%ival)
case (V_REAL); allocate (node%rval)
case (V_CMPLX); allocate (node%cval)
case (V_PDG); allocate (node%aval)
case (V_SEV); allocate (node%pval)
    call subevt_init (node%pval)
case (V_STR); allocate (node%sval)
end select
allocate (node%value_is_known)
node%value_is_known = .false.
end subroutine eval_node_allocate_value

```

Initialize a block node which contains, in addition to the expression to be evaluated, a variable definition. The result type is not yet assigned, because we can compile the enclosed expression only after the var list is set up.

Note that the node always allocates a new variable list and appends it to the current one. Thus, if the variable redefines an existing one, it only shadows it but does not reset it. Any side-effects are therefore absent and need not be undone outside the block.

If the flag `new` is set, a variable is (re)declared. This must not be done for intrinsic variables. Vice versa, if the variable is not existent, the `new` flag is required.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_block (node, name, type, var_def, var_list)
type(eval_node_t), intent(out), target :: node
type(string_t), intent(in) :: name
integer, intent(in) :: type
type(eval_node_t), intent(in), target :: var_def
type(var_list_t), intent(in), target :: var_list
node%type = EN_BLOCK
node%tag = "var_def"
node%var_name = name
node%arg1 => var_def

```

```

allocate (node%var_list)
call node%var_list%link (var_list)
if (var_def%type == EN_CONSTANT) then
  select case (type)
    case (V_LOG)
      call var_list_append_log (node%var_list, name, var_def%lval)
    case (V_INT)
      call var_list_append_int (node%var_list, name, var_def%ival)
    case (V_REAL)
      call var_list_append_real (node%var_list, name, var_def%rval)
    case (V_CMPLX)
      call var_list_append_cmplx (node%var_list, name, var_def%cval)
    case (V_PDG)
      call var_list_append_pdg_array &
        (node%var_list, name, var_def%aval)
    case (V_SEV)
      call var_list_append_subevt &
        (node%var_list, name, var_def%pval)
    case (V_STR)
      call var_list_append_string (node%var_list, name, var_def%sval)
  end select
else
  select case (type)
    case (V_LOG); call var_list_append_log_ptr &
      (node%var_list, name, var_def%lval, var_def%value_is_known)
    case (V_INT); call var_list_append_int_ptr &
      (node%var_list, name, var_def%ival, var_def%value_is_known)
    case (V_REAL); call var_list_append_real_ptr &
      (node%var_list, name, var_def%rval, var_def%value_is_known)
    case (V_CMPLX); call var_list_append_cmplx_ptr &
      (node%var_list, name, var_def%cval, var_def%value_is_known)
    case (V_PDG); call var_list_append_pdg_array_ptr &
      (node%var_list, name, var_def%aval, var_def%value_is_known)
    case (V_SEV); call var_list_append_subevt_ptr &
      (node%var_list, name, var_def%pval, var_def%value_is_known)
    case (V_STR); call var_list_append_string_ptr &
      (node%var_list, name, var_def%sval, var_def%value_is_known)
  end select
end if
end subroutine eval_node_init_block

```

Complete block initialization by assigning the expression to evaluate to `arg0`.

(Eval trees: procedures)+≡

```

subroutine eval_node_set_expr (node, arg, result_type)
  type(eval_node_t), intent(inout) :: node
  type(eval_node_t), intent(in), target :: arg
  integer, intent(in), optional :: result_type
  if (present (result_type)) then
    node%result_type = result_type
  else
    node%result_type = arg%result_type
  end if
  call eval_node_allocate_value (node)
  node%arg0 => arg

```

```
end subroutine eval_node_set_expr
```

Initialize a conditional. There are three branches: the condition (evaluates to logical) and the two alternatives (evaluate both to the same arbitrary type).

(Eval trees: procedures)+≡

```
subroutine eval_node_init_conditional (node, result_type, cond, arg1, arg2)
  type(eval_node_t), intent(out) :: node
  integer, intent(in) :: result_type
  type(eval_node_t), intent(in), target :: cond, arg1, arg2
  node%type = EN_CONDITIONAL
  node%tag = "cond"
  node%result_type = result_type
  call eval_node_allocate_value (node)
  node%arg0 => cond
  node%arg1 => arg1
  node%arg2 => arg2
end subroutine eval_node_init_conditional
```

Initialize a recording command (which evaluates to a logical constant). The first branch is the ID of the analysis object to be filled, the optional branches 1 to 4 are the values to be recorded.

If the event-weight pointer is null, we record values with unit weight. Otherwise, we use the value pointed to as event weight.

There can be up to four arguments which represent x , y , Δy , Δx . Therefore, this is the only node type that may fill four sub-nodes.

(Eval trees: procedures)+≡

```
subroutine eval_node_init_record_cmd &
  (node, event_weight, id, arg1, arg2, arg3, arg4)
  type(eval_node_t), intent(out) :: node
  real(default), pointer :: event_weight
  type(eval_node_t), intent(in), target :: id
  type(eval_node_t), intent(in), optional, target :: arg1, arg2, arg3, arg4
  call eval_node_init_log (node, .true.)
  node%type = EN_RECORD_CMD
  node%rval => event_weight
  node%tag = "record_cmd"
  node%arg0 => id
  if (present (arg1)) then
    node%arg1 => arg1
    if (present (arg2)) then
      node%arg2 => arg2
      if (present (arg3)) then
        node%arg3 => arg3
        if (present (arg4)) then
          node%arg4 => arg4
        end if
      end if
    end if
  end if
end if
end if
end if
end if
end subroutine eval_node_init_record_cmd
```

Initialize a node for operations on subevents. The particle lists (one or two) are inserted as `arg1` and `arg2`. We allocated particle pointers as temporaries for iterating over particle lists. The procedure pointer which holds the function to evaluate for the subevents (e.g., combine, select) is also initialized.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_prt_fun_unary (node, arg1, name, proc)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), intent(in), target :: arg1
  type(string_t), intent(in) :: name
  procedure(unary_sev) :: proc
  node%type = EN_PRT_FUN_UNARY
  node%tag = name
  node%result_type = V_SEV
  call eval_node_allocate_value (node)
  node%arg1 => arg1
  allocate (node%index, source = 0)
  allocate (node%prt1)
  node%op1_sev => proc
end subroutine eval_node_init_prt_fun_unary

subroutine eval_node_init_prt_fun_binary (node, arg1, arg2, name, proc)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), intent(in), target :: arg1, arg2
  type(string_t), intent(in) :: name
  procedure(binary_sev) :: proc
  node%type = EN_PRT_FUN_BINARY
  node%tag = name
  node%result_type = V_SEV
  call eval_node_allocate_value (node)
  node%arg1 => arg1
  node%arg2 => arg2
  allocate (node%index, source = 0)
  allocate (node%prt1)
  allocate (node%prt2)
  node%op2_sev => proc
end subroutine eval_node_init_prt_fun_binary

```

Similar, but for particle-list functions that evaluate to a real value.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_eval_fun_unary (node, arg1, name)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), intent(in), target :: arg1
  type(string_t), intent(in) :: name
  node%type = EN_EVAL_FUN_UNARY
  node%tag = name
  node%result_type = V_REAL
  call eval_node_allocate_value (node)
  node%arg1 => arg1
  allocate (node%index, source = 0)
  allocate (node%prt1)
end subroutine eval_node_init_eval_fun_unary

subroutine eval_node_init_eval_fun_binary (node, arg1, arg2, name)

```

```

type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1, arg2
type(string_t), intent(in) :: name
node%type = EN_EVAL_FUN_BINARY
node%tag = name
node%result_type = V_REAL
call eval_node_allocate_value (node)
node%arg1 => arg1
node%arg2 => arg2
allocate (node%index, source = 0)
allocate (node%prt1)
allocate (node%prt2)
end subroutine eval_node_init_eval_fun_binary

```

These are for particle-list functions that evaluate to a logical value.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_log_fun_unary (node, arg1, name, proc)
type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1
type(string_t), intent(in) :: name
procedure(unary_cut) :: proc
node%type = EN_LOG_FUN_UNARY
node%tag = name
node%result_type = V_LOG
call eval_node_allocate_value (node)
node%arg1 => arg1
allocate (node%index, source = 0)
allocate (node%prt1)
node%op1_cut => proc
end subroutine eval_node_init_log_fun_unary

subroutine eval_node_init_log_fun_binary (node, arg1, arg2, name, proc)
type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1, arg2
type(string_t), intent(in) :: name
procedure(binary_cut) :: proc
node%type = EN_LOG_FUN_BINARY
node%tag = name
node%result_type = V_LOG
call eval_node_allocate_value (node)
node%arg1 => arg1
node%arg2 => arg2
allocate (node%index, source = 0)
allocate (node%prt1)
allocate (node%prt2)
node%op2_cut => proc
end subroutine eval_node_init_log_fun_binary

```

These are for particle-list functions that evaluate to an integer value.

(Eval trees: procedures)+≡

```

subroutine eval_node_init_int_fun_unary (node, arg1, name, proc)
type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1

```

```

    type(string_t), intent(in) :: name
    procedure(unary_evi) :: proc
    node%type = EN_INT_FUN_UNARY
    node%tag = name
    node%result_type = V_INT
    call eval_node_allocate_value (node)
    node%arg1 => arg1
    allocate (node%index, source = 0)
    allocate (node%prt1)
    node%op1_evi => proc
end subroutine eval_node_init_int_fun_unary

subroutine eval_node_init_int_fun_binary (node, arg1, arg2, name, proc)
    type(eval_node_t), intent(out) :: node
    type(eval_node_t), intent(in), target :: arg1, arg2
    type(string_t), intent(in) :: name
    procedure(binary_evi) :: proc
    node%type = EN_INT_FUN_BINARY
    node%tag = name
    node%result_type = V_INT
    call eval_node_allocate_value (node)
    node%arg1 => arg1
    node%arg2 => arg2
    allocate (node%index, source = 0)
    allocate (node%prt1)
    allocate (node%prt2)
    node%op2_evi => proc
end subroutine eval_node_init_int_fun_binary

```

These are for particle-list functions that evaluate to a real value.

(*Eval trees: procedures*) $\vdash\equiv$

```

subroutine eval_node_init_real_fun_unary (node, arg1, name, proc)
    type(eval_node_t), intent(out) :: node
    type(eval_node_t), intent(in), target :: arg1
    type(string_t), intent(in) :: name
    procedure(unary_evr) :: proc
    node%type = EN_REAL_FUN_UNARY
    node%tag = name
    node%result_type = V_INT
    call eval_node_allocate_value (node)
    node%arg1 => arg1
    allocate (node%index, source = 0)
    allocate (node%prt1)
    node%op1_evr => proc
end subroutine eval_node_init_real_fun_unary

subroutine eval_node_init_real_fun_binary (node, arg1, arg2, name, proc)
    type(eval_node_t), intent(out) :: node
    type(eval_node_t), intent(in), target :: arg1, arg2
    type(string_t), intent(in) :: name
    procedure(binary_evr) :: proc
    node%type = EN_REAL_FUN_BINARY
    node%tag = name
    node%result_type = V_INT

```

```

call eval_node_allocate_value (node)
node%arg1 => arg1
node%arg2 => arg2
allocate (node%index, source = 0)
allocate (node%prt1)
allocate (node%prt2)
node%op2_evr => proc
end subroutine eval_node_init_real_fun_binary

```

Initialize a node for a string formatting function (sprintf).

```

<Eval trees: procedures>+≡
subroutine eval_node_init_format_string (node, fmt, arg, name, n_args)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), pointer :: fmt, arg
  type(string_t), intent(in) :: name
  integer, intent(in) :: n_args
  node%type = EN_FORMAT_STR
  node%tag = name
  node%result_type = V_STR
  call eval_node_allocate_value (node)
  node%arg0 => fmt
  node%arg1 => arg
  allocate (node%ival)
  node%ival = n_args
end subroutine eval_node_init_format_string

```

If particle functions depend upon a condition (or an expression is evaluated), the observables that can be evaluated for the given particles have to be thrown on the local variable stack. This is done here. Each observable is initialized with the particle pointers which have been allocated for the node.

The integer variable that is referred to by the `Index` pseudo-observable is always known when it is referred to.

```

<Eval trees: procedures>+≡
subroutine eval_node_set_observables (node, var_list)
  type(eval_node_t), intent(inout) :: node
  type(var_list_t), intent(in), target :: var_list
  logical, save, target :: known = .true.
  allocate (node%var_list)
  call node%var_list%link (var_list)
  allocate (node%index, source = 0)
  call var_list_append_int_ptr &
    (node%var_list, var_str ("Index"), node%index, known, intrinsic=.true.)
  if (.not. associated (node%prt2)) then
    call var_list_set_observables_unary &
      (node%var_list, node%prt1)
  else
    call var_list_set_observables_binary &
      (node%var_list, node%prt1, node%prt2)
  end if
end subroutine eval_node_set_observables

```

Output

<Eval trees: procedures>+≡

```
subroutine eval_node_write (node, unit, indent)
  type(eval_node_t), intent(in) :: node
  integer, intent(in), optional :: unit
  integer, intent(in), optional :: indent
  integer :: u, ind
  u = given_output_unit (unit); if (u < 0) return
  ind = 0; if (present (indent)) ind = indent
  write (u, "(A)", advance="no") repeat ("| ", ind) // "o "
  select case (node%type)
  case (EN_UNARY, EN_BINARY, EN_CONDITIONAL, &
        EN_PRT_FUN_UNARY, EN_PRT_FUN_BINARY, &
        EN_EVAL_FUN_UNARY, EN_EVAL_FUN_BINARY, &
        EN_LOG_FUN_UNARY, EN_LOG_FUN_BINARY, &
        EN_INT_FUN_UNARY, EN_INT_FUN_BINARY, &
        EN_REAL_FUN_UNARY, EN_REAL_FUN_BINARY)
    write (u, "(A)", advance="no") "[" // char (node%tag) // "]" = "
  case (EN_CONSTANT)
    write (u, "(A)", advance="no") "[const] ="
  case (EN_VARIABLE)
    write (u, "(A)", advance="no") char (node%tag) // " =>"
  case (EN_OBS1_INT, EN_OBS2_INT, EN_OBS1_REAL, EN_OBS2_REAL, &
        EN_UOBS1_INT, EN_UOBS2_INT, EN_UOBS1_REAL, EN_UOBS2_REAL)
    write (u, "(A)", advance="no") char (node%tag) // " ="
  case (EN_BLOCK)
    write (u, "(A)", advance="no") "[" // char (node%tag) // "]" // &
      char (node%var_name) // " [expr] = "
  case default
    write (u, "(A)", advance="no") "[???" = "
  end select
  select case (node%result_type)
  case (V_LOG)
    if (node%value_is_known) then
      if (node%lval) then
        write (u, "(1x,A)") "true"
      else
        write (u, "(1x,A)") "false"
      end if
    else
      write (u, "(1x,A)") "[unknown logical]"
    end if
  case (V_INT)
    if (node%value_is_known) then
      write (u, "(1x,I0)") node%ival
    else
      write (u, "(1x,A)") "[unknown integer]"
    end if
  case (V_REAL)
    if (node%value_is_known) then
      write (u, "(1x," // FMT_19 // ")") node%rval
    else
      write (u, "(1x,A)") "[unknown real]"
    end if
  end select
```



```

        end if
    case (V_CMPLX)
        if (node%value_is_known) then
            write (u, "(1x,'('," // FMT_19 // ",',''," // &
                FMT_19 // ",')')") node%cval
        else
            write (u, "(1x,A)") "[unknown complex]"
        end if
    case (V_SEV)
        if (char (node%tag) == "@evt") then
            write (u, "(1x,A)") "[event subevent]"
        else if (node%value_is_known) then
            call subevt_write &
                (node%pval, unit, prefix = repeat ("| ", ind + 1))
        else
            write (u, "(1x,A)") "[unknown subevent]"
        end if
    case (V_PDG)
        write (u, "(1x)", advance="no")
        call pdg_array_write (node%aval, u); write (u, *)
    case (V_STR)
        if (node%value_is_known) then
            write (u, "(A)" // char (node%sval) // '')
        else
            write (u, "(1x,A)") "[unknown string]"
        end if
    case default
        write (u, "(1x,A)") "[empty]"
    end select
select case (node%type)
case (EN_OBS1_INT, EN_OBS1_REAL, EN_UOBS1_INT, EN_UOBS1_REAL)
    write (u, "(A,6x,A)", advance="no") repeat ("| ", ind), "prt1 ="
    call prt_write (node%prt1, unit)
case (EN_OBS2_INT, EN_OBS2_REAL, EN_UOBS2_INT, EN_UOBS2_REAL)
    write (u, "(A,6x,A)", advance="no") repeat ("| ", ind), "prt1 ="
    call prt_write (node%prt1, unit)
    write (u, "(A,6x,A)", advance="no") repeat ("| ", ind), "prt2 ="
    call prt_write (node%prt2, unit)
end select
end subroutine eval_node_write

recursive subroutine eval_node_write_rec (node, unit, indent)
    type(eval_node_t), intent(in) :: node
    integer, intent(in), optional :: unit
    integer, intent(in), optional :: indent
    integer :: u, ind
    u = given_output_unit (unit); if (u < 0) return
    ind = 0; if (present (indent)) ind = indent
    call eval_node_write (node, unit, indent)
    select case (node%type)
    case (EN_UNARY)
        if (associated (node%arg0)) &
            call eval_node_write_rec (node%arg0, unit, ind+1)
        call eval_node_write_rec (node%arg1, unit, ind+1)

```

```

case (EN_BINARY)
  if (associated (node%arg0)) &
    call eval_node_write_rec (node%arg0, unit, ind+1)
    call eval_node_write_rec (node%arg1, unit, ind+1)
    call eval_node_write_rec (node%arg2, unit, ind+1)
case (EN_BLOCK)
  call eval_node_write_rec (node%arg1, unit, ind+1)
  call eval_node_write_rec (node%arg0, unit, ind+1)
case (EN_CONDITIONAL)
  call eval_node_write_rec (node%arg0, unit, ind+1)
  call eval_node_write_rec (node%arg1, unit, ind+1)
  call eval_node_write_rec (node%arg2, unit, ind+1)
case (EN_PRT_FUN_UNARY, EN_EVAL_FUN_UNARY, &
      EN_LOG_FUN_UNARY, EN_INT_FUN_UNARY, EN_REAL_FUN_UNARY)
  if (associated (node%arg0)) &
    call eval_node_write_rec (node%arg0, unit, ind+1)
    call eval_node_write_rec (node%arg1, unit, ind+1)
case (EN_PRT_FUN_BINARY, EN_EVAL_FUN_BINARY, &
      EN_LOG_FUN_BINARY, EN_INT_FUN_BINARY, EN_REAL_FUN_BINARY)
  if (associated (node%arg0)) &
    call eval_node_write_rec (node%arg0, unit, ind+1)
    call eval_node_write_rec (node%arg1, unit, ind+1)
    call eval_node_write_rec (node%arg2, unit, ind+1)
case (EN_RECORD_CMD)
  if (associated (node%arg1)) then
    call eval_node_write_rec (node%arg1, unit, ind+1)
    if (associated (node%arg2)) then
      call eval_node_write_rec (node%arg2, unit, ind+1)
      if (associated (node%arg3)) then
        call eval_node_write_rec (node%arg3, unit, ind+1)
        if (associated (node%arg4)) then
          call eval_node_write_rec (node%arg4, unit, ind+1)
        end if
      end if
    end if
  end if
end if
end select
end subroutine eval_node_write_rec

```

26.3.2 Operation types

For the operations associated to evaluation tree nodes, we define abstract interfaces for all cases.

Particles/subevents are transferred by-reference, to avoid unnecessary copying. Therefore, subroutines instead of functions. (Furthermore, the function version of `unary_prt` triggers an obscure bug in nagfor 5.2(649) [invalid C code].)

(Eval trees: interfaces)≡

```

abstract interface
  logical function unary_log (arg)
    import eval_node_t
    type(eval_node_t), intent(in) :: arg
  end function unary_log

```

```

end interface
abstract interface
    integer function unary_int (arg)
        import eval_node_t
        type(eval_node_t), intent(in) :: arg
    end function unary_int
end interface
abstract interface
    real(default) function unary_real (arg)
        import default
        import eval_node_t
        type(eval_node_t), intent(in) :: arg
    end function unary_real
end interface
abstract interface
    complex(default) function unary_cmplx (arg)
        import default
        import eval_node_t
        type(eval_node_t), intent(in) :: arg
    end function unary_cmplx
end interface
abstract interface
    subroutine unary_pdg (pdg_array, arg)
        import pdg_array_t
        import eval_node_t
        type(pdg_array_t), intent(out) :: pdg_array
        type(eval_node_t), intent(in) :: arg
    end subroutine unary_pdg
end interface
abstract interface
    subroutine unary_sev (subevt, arg, arg0)
        import subevt_t
        import eval_node_t
        type(subevt_t), intent(inout) :: subevt
        type(eval_node_t), intent(in) :: arg
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine unary_sev
end interface
abstract interface
    subroutine unary_str (string, arg)
        import string_t
        import eval_node_t
        type(string_t), intent(out) :: string
        type(eval_node_t), intent(in) :: arg
    end subroutine unary_str
end interface
abstract interface
    logical function unary_cut (arg1, arg0)
        import eval_node_t
        type(eval_node_t), intent(in) :: arg1
        type(eval_node_t), intent(inout) :: arg0
    end function unary_cut
end interface
abstract interface

```

```

subroutine unary_evi (ival, arg1, arg0)
  import eval_node_t
  integer, intent(out) :: ival
  type(eval_node_t), intent(in) :: arg1
  type(eval_node_t), intent(inout), optional :: arg0
end subroutine unary_evi
end interface
abstract interface
  subroutine unary_evr (rval, arg1, arg0)
    import eval_node_t, default
    real(default), intent(out) :: rval
    type(eval_node_t), intent(in) :: arg1
    type(eval_node_t), intent(inout), optional :: arg0
  end subroutine unary_evr
end interface
abstract interface
  logical function binary_log (arg1, arg2)
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_log
end interface
abstract interface
  integer function binary_int (arg1, arg2)
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_int
end interface
abstract interface
  real(default) function binary_real (arg1, arg2)
    import default
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_real
end interface
abstract interface
  complex(default) function binary_cmplx (arg1, arg2)
    import default
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_cmplx
end interface
abstract interface
  subroutine binary_pdg (pdg_array, arg1, arg2)
    import pdg_array_t
    import eval_node_t
    type(pdg_array_t), intent(out) :: pdg_array
    type(eval_node_t), intent(in) :: arg1, arg2
  end subroutine binary_pdg
end interface
abstract interface
  subroutine binary_sev (subevt, arg1, arg2, arg0)
    import subevt_t
    import eval_node_t
    type(subevt_t), intent(inout) :: subevt

```

```

        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine binary_sev
end interface
abstract interface
    subroutine binary_str (string, arg1, arg2)
        import string_t
        import eval_node_t
        type(string_t), intent(out) :: string
        type(eval_node_t), intent(in) :: arg1, arg2
    end subroutine binary_str
end interface
abstract interface
    logical function binary_cut (arg1, arg2, arg0)
        import eval_node_t
        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout) :: arg0
    end function binary_cut
end interface
abstract interface
    subroutine binary_evi (ival, arg1, arg2, arg0)
        import eval_node_t
        integer, intent(out) :: ival
        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine binary_evi
end interface
abstract interface
    subroutine binary_evr (rval, arg1, arg2, arg0)
        import eval_node_t, default
        real(default), intent(out) :: rval
        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine binary_evr
end interface

```

The following subroutines set the procedure pointer:

<Eval trees: procedures>+≡

```

subroutine eval_node_set_op1_log (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_log) :: op
    en%op1_log => op
end subroutine eval_node_set_op1_log

subroutine eval_node_set_op1_int (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_int) :: op
    en%op1_int => op
end subroutine eval_node_set_op1_int

subroutine eval_node_set_op1_real (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_real) :: op
    en%op1_real => op

```

```

end subroutine eval_node_set_op1_real

subroutine eval_node_set_op1_cplx (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(unary_cplx) :: op
  en%op1_cplx => op
end subroutine eval_node_set_op1_cplx

subroutine eval_node_set_op1_pdg (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(unary_pdg) :: op
  en%op1_pdg => op
end subroutine eval_node_set_op1_pdg

subroutine eval_node_set_op1_sev (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(unary_sev) :: op
  en%op1_sev => op
end subroutine eval_node_set_op1_sev

subroutine eval_node_set_op1_str (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(unary_str) :: op
  en%op1_str => op
end subroutine eval_node_set_op1_str

subroutine eval_node_set_op2_log (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_log) :: op
  en%op2_log => op
end subroutine eval_node_set_op2_log

subroutine eval_node_set_op2_int (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_int) :: op
  en%op2_int => op
end subroutine eval_node_set_op2_int

subroutine eval_node_set_op2_real (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_real) :: op
  en%op2_real => op
end subroutine eval_node_set_op2_real

subroutine eval_node_set_op2_cplx (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_cplx) :: op
  en%op2_cplx => op
end subroutine eval_node_set_op2_cplx

subroutine eval_node_set_op2_pdg (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_pdg) :: op
  en%op2_pdg => op

```

```

end subroutine eval_node_set_op2_pdg

subroutine eval_node_set_op2_sev (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_sev) :: op
  en%op2_sev => op
end subroutine eval_node_set_op2_sev

subroutine eval_node_set_op2_str (en, op)
  type(eval_node_t), intent(inout) :: en
  procedure(binary_str) :: op
  en%op2_str => op
end subroutine eval_node_set_op2_str

```

26.3.3 Specific operators

Our expression syntax contains all Fortran functions that make sense. These functions have to be provided in a form that they can be used in procedures pointers, and have the abstract interfaces above. For some intrinsic functions, we could use specific versions provided by Fortran directly. However, this has two drawbacks: (i) We should work with the values instead of the eval-nodes as argument, which complicates the interface; (ii) more importantly, the **default** real type need not be equivalent to double precision. This would, at least, introduce system dependencies. Finally, for operators there are no specific versions.

Therefore, we write wrappers for all possible functions, at the expense of some overhead.

Binary numerical functions

<Eval trees: procedures>+≡

```

integer function add_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival + en2%ival
end function add_ii

real(default) function add_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival + en2%rval
end function add_ir

complex(default) function add_ic (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival + en2%cval
end function add_ic

real(default) function add_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%rval + en2%ival
end function add_ri

complex(default) function add_ci (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%cval + en2%ival
end function add_ci

complex(default) function add_cr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2

```

```

        y = en1%cval + en2%rval
    end function add_cr
    complex(default) function add_rc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval + en2%cval
    end function add_rc
    real(default) function add_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval + en2%rval
    end function add_rr
    complex(default) function add_cc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval + en2%cval
    end function add_cc

    integer function sub_ii (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival - en2%ival
    end function sub_ii
    real(default) function sub_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival - en2%rval
    end function sub_ir
    real(default) function sub_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval - en2%ival
    end function sub_ri
    complex(default) function sub_ic (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival - en2%cval
    end function sub_ic
    complex(default) function sub_ci (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval - en2%ival
    end function sub_ci
    complex(default) function sub_cr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval - en2%rval
    end function sub_cr
    complex(default) function sub_rc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval - en2%cval
    end function sub_rc
    real(default) function sub_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval - en2%rval
    end function sub_rr
    complex(default) function sub_cc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval - en2%cval
    end function sub_cc

    integer function mul_ii (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2

```



```

        y = en1%ival * en2%ival
    end function mul_ii
    real(default) function mul_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival * en2%rval
    end function mul_ir
    real(default) function mul_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval * en2%ival
    end function mul_ri
    complex(default) function mul_ic (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival * en2%cval
    end function mul_ic
    complex(default) function mul_ci (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval * en2%ival
    end function mul_ci
    complex(default) function mul_rc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval * en2%cval
    end function mul_rc
    complex(default) function mul_cr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval * en2%rval
    end function mul_cr
    real(default) function mul_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval * en2%rval
    end function mul_rr
    complex(default) function mul_cc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval * en2%cval
    end function mul_cc

    integer function div_ii (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        if (en2%ival == 0) then
            if (en1%ival >= 0) then
                call msg_warning ("division by zero: " // int2char (en1%ival) // &
                    " / 0 ; result set to 0")
            else
                call msg_warning ("division by zero: (" // int2char (en1%ival) // &
                    ") / 0 ; result set to 0")
            end if
            y = 0
            return
        end if
        y = en1%ival / en2%ival
    end function div_ii
    real(default) function div_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival / en2%rval
    end function div_ir

```

```

real(default) function div_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval / en2%ival
end function div_ri
complex(default) function div_ic (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival / en2%cval
end function div_ic
complex(default) function div_ci (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval / en2%ival
end function div_ci
complex(default) function div_rc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval / en2%cval
end function div_rc
complex(default) function div_cr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval / en2%rval
end function div_cr
real(default) function div_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval / en2%rval
end function div_rr
complex(default) function div_cc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval / en2%cval
end function div_cc

integer function pow_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    integer :: a, b
    real(default) :: rres
    a = en1%ival
    b = en2%ival
    if ((a == 0) .and. (b < 0)) then
        call msg_warning ("division by zero: " // int2char (a) // &
            " ^ (" // int2char (b) // ") ; result set to 0")
        y = 0
        return
    end if
    rres = real(a, default) ** b
    y = rres
    if (real(y, default) /= rres) then
        if (b < 0) then
            call msg_warning ("result of all-integer operation " // &
                int2char (a) // " ^ (" // int2char (b) // &
                ") has been truncated to " // int2char (y), &
                [ var_str ("Chances are that you want to use " // &
                    "reals instead of integers at this point.") ])
        else
            call msg_warning ("integer overflow in " // int2char (a) // &
                " ^ " // int2char (b) // " ; result is " // int2char (y), &
                [ var_str ("Using reals instead of integers might help.") ])
        end if
    end if
end function pow_ii

```

```

        end if
    end if
end function pow_ii
real(default) function pow_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval ** en2%ival
end function pow_ri
complex(default) function pow_ci (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval ** en2%ival
end function pow_ci
real(default) function pow_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival ** en2%rval
end function pow_ir
real(default) function pow_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval ** en2%rval
end function pow_rr
complex(default) function pow_cr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval ** en2%rval
end function pow_cr
complex(default) function pow_ic (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival ** en2%cval
end function pow_ic
complex(default) function pow_rc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval ** en2%cval
end function pow_rc
complex(default) function pow_cc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval ** en2%cval
end function pow_cc

integer function max_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (en1%ival, en2%ival)
end function max_ii
real(default) function max_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (real (en1%ival, default), en2%rval)
end function max_ir
real(default) function max_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (en1%rval, real (en2%ival, default))
end function max_ri
real(default) function max_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (en1%rval, en2%rval)
end function max_rr
integer function min_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2

```

```

    y = min (en1%ival, en2%ival)
end function min_ii
real(default) function min_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (real (en1%ival, default), en2%rval)
end function min_ir
real(default) function min_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (en1%rval, real (en2%ival, default))
end function min_ri
real(default) function min_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (en1%rval, en2%rval)
end function min_rr

integer function mod_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = mod (en1%ival, en2%ival)
end function mod_ii
real(default) function mod_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = mod (real (en1%ival, default), en2%rval)
end function mod_ir
real(default) function mod_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = mod (en1%rval, real (en2%ival, default))
end function mod_ri
real(default) function mod_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = mod (en1%rval, en2%rval)
end function mod_rr
integer function modulo_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = modulo (en1%ival, en2%ival)
end function modulo_ii
real(default) function modulo_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = modulo (real (en1%ival, default), en2%rval)
end function modulo_ir
real(default) function modulo_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = modulo (en1%rval, real (en2%ival, default))
end function modulo_ri
real(default) function modulo_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = modulo (en1%rval, en2%rval)
end function modulo_rr

```

Unary numeric functions

<Eval trees: procedures>+≡

```

real(default) function real_i (en) result (y)
    type(eval_node_t), intent(in) :: en

```

```

        y = en%ival
    end function real_i
    real(default) function real_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%cval
    end function real_c
    integer function int_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%rval
    end function int_r
    complex(default) function cmplx_i (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%ival
    end function cmplx_i
    integer function int_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%cval
    end function int_c
    complex(default) function cmplx_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%rval
    end function cmplx_r
    integer function nint_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = nint (en%rval)
    end function nint_r
    integer function floor_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = floor (en%rval)
    end function floor_r
    integer function ceiling_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = ceiling (en%rval)
    end function ceiling_r

    integer function neg_i (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = - en%ival
    end function neg_i
    real(default) function neg_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = - en%rval
    end function neg_r
    complex(default) function neg_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = - en%cval
    end function neg_c
    integer function abs_i (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = abs (en%ival)
    end function abs_i
    real(default) function abs_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = abs (en%rval)

```

```

end function abs_r
real(default) function abs_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = abs (en%cval)
end function abs_c
integer function sgn_i (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sign (1, en%ival)
end function sgn_i
real(default) function sgn_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sign (1._default, en%rval)
end function sgn_r

real(default) function sqrt_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sqrt (en%rval)
end function sqrt_r
real(default) function exp_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = exp (en%rval)
end function exp_r
real(default) function log_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = log (en%rval)
end function log_r
real(default) function log10_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = log10 (en%rval)
end function log10_r

complex(default) function sqrt_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sqrt (en%cval)
end function sqrt_c
complex(default) function exp_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = exp (en%cval)
end function exp_c
complex(default) function log_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = log (en%cval)
end function log_c

real(default) function sin_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sin (en%rval)
end function sin_r
real(default) function cos_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = cos (en%rval)
end function cos_r
real(default) function tan_r (en) result (y)
    type(eval_node_t), intent(in) :: en

```

```

        y = tan (en%rval)
    end function tan_r
    real(default) function asin_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = asin (en%rval)
    end function asin_r
    real(default) function acos_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = acos (en%rval)
    end function acos_r
    real(default) function atan_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = atan (en%rval)
    end function atan_r

    complex(default) function sin_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = sin (en%cval)
    end function sin_c
    complex(default) function cos_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = cos (en%cval)
    end function cos_c

    real(default) function sinh_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = sinh (en%rval)
    end function sinh_r
    real(default) function cosh_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = cosh (en%rval)
    end function cosh_r
    real(default) function tanh_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = tanh (en%rval)
    end function tanh_r
    !!! These are F2008 additions but accepted by nagfor 5.3 and gfortran 4.6+
    !!! Currently not used.
    !   real(default) function asinh_r (en) result (y)
    !       type(eval_node_t), intent(in) :: en
    !       y = asinh (en%rval)
    !   end function asinh_r
    !   real(default) function acosh_r (en) result (y)
    !       type(eval_node_t), intent(in) :: en
    !       y = acosh (en%rval)
    !   end function acosh_r
    !   real(default) function atanh_r (en) result (y)
    !       type(eval_node_t), intent(in) :: en
    !       y = atanh (en%rval)
    !   end function atanh_r

```

Binary logical functions

Logical expressions:

```
<Eval trees: procedures>+≡
  logical function ignore_first_ll (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en2%lval
  end function ignore_first_ll
  logical function or_ll (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%lval .or. en2%lval
  end function or_ll
  logical function and_ll (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%lval .and. en2%lval
  end function and_ll
```

Comparisons:

```
<Eval trees: procedures>+≡
  logical function comp_lt_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival < en2%ival
  end function comp_lt_ii
  logical function comp_lt_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival < en2%rval
  end function comp_lt_ir
  logical function comp_lt_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval < en2%ival
  end function comp_lt_ri
  logical function comp_lt_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval < en2%rval
  end function comp_lt_rr

  logical function comp_gt_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival > en2%ival
  end function comp_gt_ii
  logical function comp_gt_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival > en2%rval
  end function comp_gt_ir
  logical function comp_gt_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval > en2%ival
  end function comp_gt_ri
  logical function comp_gt_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval > en2%rval
  end function comp_gt_rr

  logical function comp_le_ii (en1, en2) result (y)
```



```

        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival <= en2%ival
    end function comp_le_ii
logical function comp_le_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival <= en2%rval
end function comp_le_ir
logical function comp_le_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval <= en2%ival
end function comp_le_ri
logical function comp_le_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval <= en2%rval
end function comp_le_rr

logical function comp_ge_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival >= en2%ival
end function comp_ge_ii
logical function comp_ge_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival >= en2%rval
end function comp_ge_ir
logical function comp_ge_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval >= en2%ival
end function comp_ge_ri
logical function comp_ge_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval >= en2%rval
end function comp_ge_rr

logical function comp_eq_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival == en2%ival
end function comp_eq_ii
logical function comp_eq_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival == en2%rval
end function comp_eq_ir
logical function comp_eq_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval == en2%ival
end function comp_eq_ri
logical function comp_eq_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval == en2%rval
end function comp_eq_rr
logical function comp_eq_ss (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%sval == en2%sval
end function comp_eq_ss

```

```

logical function comp_ne_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival /= en2%ival
end function comp_ne_ii
logical function comp_ne_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival /= en2%rval
end function comp_ne_ir
logical function comp_ne_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%rval /= en2%ival
end function comp_ne_ri
logical function comp_ne_rr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%rval /= en2%rval
end function comp_ne_rr
logical function comp_ne_ss (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%sval /= en2%sval
end function comp_ne_ss

```

Comparisons with tolerance:

(Eval trees: procedures)+≡

```

logical function comp_se_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%ival - en2%ival) <= en1%tolerance
  else
    y = en1%ival == en2%ival
  end if
end function comp_se_ii
logical function comp_se_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%rval - en2%ival) <= en1%tolerance
  else
    y = en1%rval == en2%ival
  end if
end function comp_se_ri
logical function comp_se_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%ival - en2%rval) <= en1%tolerance
  else
    y = en1%ival == en2%rval
  end if
end function comp_se_ir
logical function comp_se_rr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%rval - en2%rval) <= en1%tolerance
  else
    y = en1%rval == en2%rval
  end if
end function comp_se_rr

```

```

end function comp_se_rr
logical function comp_ns_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%ival - en2%ival) > en1%tolerance
  else
    y = en1%ival /= en2%ival
  end if
end function comp_ns_ii
logical function comp_ns_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%rval - en2%ival) > en1%tolerance
  else
    y = en1%rval /= en2%ival
  end if
end function comp_ns_ri
logical function comp_ns_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%ival - en2%rval) > en1%tolerance
  else
    y = en1%ival /= en2%rval
  end if
end function comp_ns_ir
logical function comp_ns_rr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = abs (en1%rval - en2%rval) > en1%tolerance
  else
    y = en1%rval /= en2%rval
  end if
end function comp_ns_rr

logical function comp_ls_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%ival <= en2%ival + en1%tolerance
  else
    y = en1%ival <= en2%ival
  end if
end function comp_ls_ii
logical function comp_ls_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%rval <= en2%ival + en1%tolerance
  else
    y = en1%rval <= en2%ival
  end if
end function comp_ls_ri
logical function comp_ls_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%ival <= en2%rval + en1%tolerance

```

```

        else
            y = en1%ival <= en2%rval
        end if
    end function comp_ls_ir
logical function comp_ls_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = en1%rval <= en2%rval + en1%tolerance
    else
        y = en1%rval <= en2%rval
    end if
end function comp_ls_rr

logical function comp_ll_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = en1%ival < en2%ival - en1%tolerance
    else
        y = en1%ival < en2%ival
    end if
end function comp_ll_ii
logical function comp_ll_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = en1%rval < en2%ival - en1%tolerance
    else
        y = en1%rval < en2%ival
    end if
end function comp_ll_ri
logical function comp_ll_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = en1%ival < en2%rval - en1%tolerance
    else
        y = en1%ival < en2%rval
    end if
end function comp_ll_ir
logical function comp_ll_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = en1%rval < en2%rval - en1%tolerance
    else
        y = en1%rval < en2%rval
    end if
end function comp_ll_rr

logical function comp_gs_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = en1%ival >= en2%ival - en1%tolerance
    else
        y = en1%ival >= en2%ival
    end if
end function comp_gs_ii

```

```

logical function comp_gs_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%rval >= en2%ival - en1%tolerance
  else
    y = en1%rval >= en2%ival
  end if
end function comp_gs_ri
logical function comp_gs_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%ival >= en2%rval - en1%tolerance
  else
    y = en1%ival >= en2%rval
  end if
end function comp_gs_ir
logical function comp_gs_rr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%rval >= en2%rval - en1%tolerance
  else
    y = en1%rval >= en2%rval
  end if
end function comp_gs_rr

logical function comp_gg_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%ival > en2%ival + en1%tolerance
  else
    y = en1%ival > en2%ival
  end if
end function comp_gg_ii
logical function comp_gg_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%rval > en2%ival + en1%tolerance
  else
    y = en1%rval > en2%ival
  end if
end function comp_gg_ri
logical function comp_gg_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%ival > en2%rval + en1%tolerance
  else
    y = en1%ival > en2%rval
  end if
end function comp_gg_ir
logical function comp_gg_rr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  if (associated (en1%tolerance)) then
    y = en1%rval > en2%rval + en1%tolerance
  else

```

```

        y = en1%rval > en2%rval
    end if
end function comp_gg_rr

```

Unary logical functions

<Eval trees: procedures>+≡

```

logical function not_l (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = .not. en%lval
end function not_l

```

Unary PDG-array functions

Make a PDG-array object from an integer.

<Eval trees: procedures>+≡

```

subroutine pdg_i (pdg_array, en)
    type(pdg_array_t), intent(out) :: pdg_array
    type(eval_node_t), intent(in) :: en
    pdg_array = en%ival
end subroutine pdg_i

```

Binary PDG-array functions

Concatenate two PDG-array objects.

<Eval trees: procedures>+≡

```

subroutine concat_cc (pdg_array, en1, en2)
    type(pdg_array_t), intent(out) :: pdg_array
    type(eval_node_t), intent(in) :: en1, en2
    pdg_array = en1%aval // en2%aval
end subroutine concat_cc

```

Unary particle-list functions

Combine all particles of the first argument. If **en0** is present, create a mask which is true only for those particles that pass the test.

<Eval trees: procedures>+≡

```

subroutine collect_p (subevt, en1, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask1
    integer :: n, i
    n = subevt_get_length (en1%pval)
    allocate (mask1 (n))
    if (present (en0)) then
        do i = 1, n
            en0%index = i

```

```

        en0%prt1 = subevt_get_prt (en1%pval, i)
        call eval_node_evaluate (en0)
        mask1(i) = en0%lval
    end do
else
    mask1 = .true.
end if
call subevt_collect (subevt, en1%pval, mask1)
end subroutine collect_p

```

Cluster the particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test.

(Eval trees: procedures)+≡

```

subroutine cluster_p (subevt, en1, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask1
    integer :: n, i
    ! Should not be hardcoded!
    type(jet_definition_t) :: jet_def
    call jet_def%init (en1%jet_algorithm, en1%jet_r)
    n = subevt_get_length (en1%pval)
    allocate (mask1 (n))
    if (present (en0)) then
        do i = 1, n
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            call eval_node_evaluate (en0)
            mask1(i) = en0%lval
        end do
    else
        mask1 = .true.
    end if
    call subevt_cluster (subevt, en1%pval, mask1, jet_def)
    call jet_def%final ()
end subroutine cluster_p

```

Select all particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test.

(Eval trees: procedures)+≡

```

subroutine select_p (subevt, en1, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask1
    integer :: n, i
    n = subevt_get_length (en1%pval)
    allocate (mask1 (n))
    if (present (en0)) then
        do i = 1, subevt_get_length (en1%pval)
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)

```

```

        call eval_node_evaluate (en0)
        mask1(i) = en0%ival
    end do
else
    mask1 = .true.
end if
call subevt_select (subevt, en1%pval, mask1)
end subroutine select_p

```

Extract the particle with index given by `en0` from the argument list. Negative indices count from the end. If `en0` is absent, extract the first particle. The result is a list with a single entry, or no entries if the original list was empty or if the index is out of range.

This function has no counterpart with two arguments.

<Eval trees: procedures>+≡

```

subroutine extract_p (subevt, en1, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    integer :: index
    if (present (en0)) then
        call eval_node_evaluate (en0)
        select case (en0%result_type)
            case (V_INT); index = en0%ival
            case default
                call eval_node_write (en0)
                call msg_fatal (" Index parameter of 'extract' must be integer.")
        end select
    else
        index = 1
    end if
    call subevt_extract (subevt, en1%pval, index)
end subroutine extract_p

```

Sort the subevent according to the result of evaluating `en0`. If `en0` is absent, sort by default method (PDG code, particles before antiparticles).

<Eval trees: procedures>+≡

```

subroutine sort_p (subevt, en1, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    integer, dimension(:), allocatable :: ival
    real(default), dimension(:), allocatable :: rval
    integer :: i, n
    n = subevt_get_length (en1%pval)
    if (present (en0)) then
        select case (en0%result_type)
            case (V_INT); allocate (ival (n))
            case (V_REAL); allocate (rval (n))
        end select
        do i = 1, n
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)

```



```

        call eval_node_evaluate (en0)
        select case (en0%result_type)
        case (V_INT); ival(i) = en0%ival
        case (V_REAL); rval(i) = en0%rval
        end select
    end do
    select case (en0%result_type)
    case (V_INT); call subevt_sort (subevt, en1%pval, ival)
    case (V_REAL); call subevt_sort (subevt, en1%pval, rval)
    end select
else
    call subevt_sort (subevt, en1%pval)
end if
end subroutine sort_p

```

The following functions return a logical value. `all` evaluates to true if the condition `en0` is true for all elements of the subevent. `any` and `no` are analogous.

(Eval trees: procedures) +≡

```

function all_p (en1, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout) :: en0
    integer :: i, n
    n = subevt_get_length (en1%pval)
    lval = .true.
    do i = 1, n
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        call eval_node_evaluate (en0)
        lval = en0%lval
        if (.not. lval) exit
    end do
end function all_p

function any_p (en1, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout) :: en0
    integer :: i, n
    n = subevt_get_length (en1%pval)
    lval = .false.
    do i = 1, n
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        call eval_node_evaluate (en0)
        lval = en0%lval
        if (lval) exit
    end do
end function any_p

function no_p (en1, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1

```

```

type(eval_node_t), intent(inout) :: en0
integer :: i, n
n = subevt_get_length (en1%pval)
lval = .true.
do i = 1, n
    en0%index = i
    en0%prt1 = subevt_get_prt (en1%pval, i)
    call eval_node_evaluate (en0)
    lval = .not. en0%lval
    if (lval) exit
end do
end function no_p

```

This is the interface to user-supplied observables. The node `en0` evaluates to a string that indicates the procedure name. We search for the procedure in the dynamic library and load it into the procedure pointer which is then called. `en1` is the subevent on which the external code operates. The external function returns a `c_int`, which we translate into a real value.

<Eval trees: procedures>+≡

```

function user_obs_int_p (en0, prt1) result (ival)
    integer :: ival
    type(eval_node_t), intent(inout) :: en0
    type(prt_t), intent(in) :: prt1
    type(string_t) :: name
    procedure(user_obs_int_unary), pointer :: user_obs
    call eval_node_evaluate (en0)
    if (en0%value_is_known) then
        select case (en0%result_type)
            case (V_STR); name = en0%sval
            case default
                call msg_bug ("user_obs: procedure name must be a string")
                name = ""
        end select
        call c_f_procpointer (user_code_find_proc (name), user_obs)
        ival = user_obs (c_prt (prt1))
    else
        call eval_node_write_rec (en0)
        call msg_fatal ("User observable name is undefined")
    end if
end function user_obs_int_p

function user_obs_real_p (en0, prt1) result (rval)
    real(default) :: rval
    type(eval_node_t), intent(inout) :: en0
    type(prt_t), intent(in) :: prt1
    type(string_t) :: name
    procedure(user_obs_real_unary), pointer :: user_obs
    call eval_node_evaluate (en0)
    if (en0%value_is_known) then
        select case (en0%result_type)
            case (V_STR); name = en0%sval
            case default
                call msg_bug ("user_obs: procedure name must be a string")

```

```

        name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_obs)
    rval = user_obs (c_prt (prt1))
else
    call eval_node_write_rec (en0)
    call msg_fatal ("User observable name is undefined")
end if
end function user_obs_real_p

```

This is the interface to user-supplied cut code. The node `en0` evaluates to a string that indicates the procedure name.

(Eval trees: procedures)+≡

```

function user_cut_p (en1, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout) :: en0
    type(string_t) :: name
    procedure(user_cut_fun), pointer :: user_cut
    call eval_node_evaluate (en0)
    select case (en0%result_type)
    case (V_STR); name = en0%sval
    case default
        call msg_bug ("user_cut: procedure name must be a string")
        name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_cut)
    lval = user_cut (c_prt (en1%pval), &
                    int (subevt_get_length (en1%pval), kind=c_int)) &
        /= 0
end function user_cut_p

```

The following function returns an integer value, namely the number of particles for which the condition is true. If there is no condition, it returns simply the length of the subevent.

A function would be more natural. Making it a subroutine avoids another compiler bug (internal error in nagfor 5.2 (649)). (See the interface `unary_evi`.)

(Eval trees: procedures)+≡

```

subroutine count_a (ival, en1, en0)
    integer, intent(out) :: ival
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    integer :: i, n, count
    n = subevt_get_length (en1%pval)
    if (present (en0)) then
        count = 0
        do i = 1, n
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            call eval_node_evaluate (en0)
            if (en0%lval) count = count + 1
        end do
    end if
    ival = count
end subroutine count_a

```

```

else
    ival = n
end if
end subroutine count_a

```

This evaluates a user-defined event-shape observable for the current subevent.

```

<Eval trees: procedures>+≡
subroutine user_event_shape_a (rval, en1, en0)
    real(default), intent(out) :: rval
    type(eval_node_t), intent(in) :: en1
    type(eval_node_t), intent(inout), optional :: en0
    type(string_t) :: name
    procedure(user_event_shape_fun), pointer :: user_event_shape
    if (.not. present (en0)) call msg_bug &
        ("user_event_shape called without procedure name")
    call eval_node_evaluate (en0)
    select case (en0%result_type)
    case (V_STR); name = en0%sval
    case default
        call msg_bug ("user_event_shape: procedure name must be a string")
        name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_event_shape)
    rval = user_event_shape (c_prt (en1%pval), &
        int (subvt_get_length (en1%pval), kind=c_int))
end subroutine user_event_shape_a

```

Binary particle-list functions

This joins two subevents, stored in the evaluation nodes `en1` and `en2`. If `en0` is also present, it amounts to a logical test returning true or false for every pair of particles. A particle of the second list gets a mask entry only if it passes the test for all particles of the first list.

```

<Eval trees: procedures>+≡
subroutine join_pp (subvt, en1, en2, en0)
    type(subvt_t), intent(inout) :: subvt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask2
    integer :: i, j, n1, n2
    n1 = subvt_get_length (en1%pval)
    n2 = subvt_get_length (en2%pval)
    allocate (mask2 (n2))
    mask2 = .true.
    if (present (en0)) then
        do i = 1, n1
            en0%index = i
            en0%prt1 = subvt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subvt_get_prt (en2%pval, j)
                call eval_node_evaluate (en0)
                mask2(j) = mask2(j) .and. en0%lval
            end do
        end do
    end if
end subroutine join_pp

```

```

        end do
    end do
end if
    call subevt_join (subevt, en1%pval, en2%pval, mask2)
end subroutine join_pp

```

Combine two subevents, i.e., make a list of composite particles built from all possible particle pairs from the two lists. If `en0` is present, create a mask which is true only for those pairs that pass the test.

(Eval trees: procedures)+≡

```

subroutine combine_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:,:), allocatable :: mask12
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    if (present (en0)) then
        allocate (mask12 (n1, n2))
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subevt_get_prt (en2%pval, j)
                call eval_node_evaluate (en0)
                mask12(i,j) = en0%lval
            end do
        end do
        call subevt_combine (subevt, en1%pval, en2%pval, mask12)
    else
        call subevt_combine (subevt, en1%pval, en2%pval)
    end if
end subroutine combine_pp

```

Combine all particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test w.r.t. all particles in the second argument. If `en0` is absent, the second argument is ignored.

(Eval trees: procedures)+≡

```

subroutine collect_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask1
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    allocate (mask1 (n1))
    mask1 = .true.
    if (present (en0)) then
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)

```

```

        do j = 1, n2
            en0%prt2 = subevt_get_prt (en2%pval, j)
            call eval_node_evaluate (en0)
            mask1(i) = mask1(i) .and. en0%lval
        end do
    end do
end if
call subevt_collect (subevt, en1%pval, mask1)
end subroutine collect_pp

```

Select all particles of the first argument. If **en0** is present, create a mask which is true only for those particles that pass the test w.r.t. all particles in the second argument. If **en0** is absent, the second argument is ignored, and the first argument is transferred unchanged. (This case is not very useful, of course.)

(Eval trees: procedures)+≡

```

subroutine select_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask1
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    allocate (mask1 (n1))
    mask1 = .true.
    if (present (en0)) then
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subevt_get_prt (en2%pval, j)
                call eval_node_evaluate (en0)
                mask1(i) = mask1(i) .and. en0%lval
            end do
        end do
    end if
    call subevt_select (subevt, en1%pval, mask1)
end subroutine select_pp

```

Sort the first subevent according to the result of evaluating **en0**. From the second subevent, only the first element is taken as reference. If **en0** is absent, we sort by default method (PDG code, particles before antiparticles).

(Eval trees: procedures)+≡

```

subroutine sort_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    integer, dimension(:), allocatable :: ival
    real(default), dimension(:), allocatable :: rval
    integer :: i, n1
    n1 = subevt_get_length (en1%pval)
    if (present (en0)) then
        select case (en0%result_type)

```

```

        case (V_INT); allocate (ival (n1))
        case (V_REAL); allocate (rval (n1))
    end select
    do i = 1, n1
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        en0%prt2 = subevt_get_prt (en2%pval, 1)
        call eval_node_evaluate (en0)
        select case (en0%result_type)
            case (V_INT); ival(i) = en0%ival
            case (V_REAL); rval(i) = en0%rval
        end select
    end do
    select case (en0%result_type)
        case (V_INT); call subevt_sort (subevt, en1%pval, ival)
        case (V_REAL); call subevt_sort (subevt, en1%pval, rval)
    end select
else
    call subevt_sort (subevt, en1%pval)
end if
end subroutine sort_pp

```

The following functions return a logical value. `all` evaluates to true if the condition `en0` is true for all valid element pairs of both subevents. Invalid pairs (with common `src` entry) are ignored.

`any` and `no` are analogous.

(Eval trees: procedures)+≡

```

function all_pp (en1, en2, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout) :: en0
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    lval = .true.
    LOOP1: do i = 1, n1
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        do j = 1, n2
            en0%prt2 = subevt_get_prt (en2%pval, j)
            if (are_disjoint (en0%prt1, en0%prt2)) then
                call eval_node_evaluate (en0)
                lval = en0%lval
                if (.not. lval) exit LOOP1
            end if
        end do
    end do LOOP1
end function all_pp

function any_pp (en1, en2, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout) :: en0

```

```

integer :: i, j, n1, n2
n1 = subevt_get_length (en1%pval)
n2 = subevt_get_length (en2%pval)
lval = .false.
LOOP1: do i = 1, n1
  en0%index = i
  en0%prt1 = subevt_get_prt (en1%pval, i)
  do j = 1, n2
    en0%prt2 = subevt_get_prt (en2%pval, j)
    if (are_disjoint (en0%prt1, en0%prt2)) then
      call eval_node_evaluate (en0)
      lval = en0%lval
      if (lval) exit LOOP1
    end if
  end do
end do LOOP1
end function any_pp

function no_pp (en1, en2, en0) result (lval)
  logical :: lval
  type(eval_node_t), intent(in) :: en1, en2
  type(eval_node_t), intent(inout) :: en0
  integer :: i, j, n1, n2
  n1 = subevt_get_length (en1%pval)
  n2 = subevt_get_length (en2%pval)
  lval = .true.
  LOOP1: do i = 1, n1
    en0%index = i
    en0%prt1 = subevt_get_prt (en1%pval, i)
    do j = 1, n2
      en0%prt2 = subevt_get_prt (en2%pval, j)
      if (are_disjoint (en0%prt1, en0%prt2)) then
        call eval_node_evaluate (en0)
        lval = .not. en0%lval
        if (lval) exit LOOP1
      end if
    end do
  end do LOOP1
end function no_pp

```

This function evaluates an observable for a pair of particles. From the two particle lists, we take the first pair without `src` overlap. If there is no valid pair, we revert the status of the value to unknown.

(Eval trees: procedures)+≡

```

subroutine eval_pp (en1, en2, en0, rval, is_known)
  type(eval_node_t), intent(in) :: en1, en2
  type(eval_node_t), intent(inout) :: en0
  real(default), intent(out) :: rval
  logical, intent(out) :: is_known
  integer :: i, j, n1, n2
  n1 = subevt_get_length (en1%pval)
  n2 = subevt_get_length (en2%pval)
  rval = 0

```



```

is_known = .false.
LOOP1: do i = 1, n1
  en0%index = i
  en0%prt1 = subevt_get_prt (en1%pval, i)
  do j = 1, n2
    en0%prt2 = subevt_get_prt (en2%pval, j)
    if (are_disjoint (en0%prt1, en0%prt2)) then
      call eval_node_evaluate (en0)
      rval = en0%rval
      is_known = .true.
      exit LOOP1
    end if
  end do
end do LOOP1
end subroutine eval_pp

```

This is the interface to user-supplied observables. The node `en0` evaluates to a string that indicates the procedure name. We search for the procedure in the dynamic library and load it into the procedure pointer which is then called. `en1` is the subevent on which the external code operates. The external function returns a `c_int`, which we translate into a real value.

(Eval trees: procedures)+≡

```

function user_obs_int_pp (en0, prt1, prt2) result (ival)
  integer :: ival
  type(eval_node_t), intent(inout) :: en0
  type(prt_t), intent(in) :: prt1, prt2
  type(string_t) :: name
  procedure(user_obs_int_binary), pointer :: user_obs
  call eval_node_evaluate (en0)
  if (en0%value_is_known) then
    select case (en0%result_type)
    case (V_STR); name = en0%sval
    case default
      call msg_bug ("user_obs: procedure name must be a string")
      name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_obs)
    ival = user_obs (c_prt (prt1), c_prt (prt2))
  else
    call eval_node_write_rec (en0)
    call msg_fatal ("User observable name is undefined")
  end if
end function user_obs_int_pp

function user_obs_real_pp (en0, prt1, prt2) result (rval)
  real(default) :: rval
  type(eval_node_t), intent(inout) :: en0
  type(prt_t), intent(in) :: prt1, prt2
  type(string_t) :: name
  procedure(user_obs_real_binary), pointer :: user_obs
  call eval_node_evaluate (en0)
  if (en0%value_is_known) then
    select case (en0%result_type)

```

```

        case (V_STR); name = en0% sval
    case default
        call msg_bug ("user_obs: procedure name must be a string")
        name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_obs)
    rval = user_obs (c_prt (prt1), c_prt (prt2))
else
    call eval_node_write_rec (en0)
    call msg_fatal ("User observable name is undefined")
end if
end function user_obs_real_pp

```

The following function returns an integer value, namely the number of valid particle-pairs from both lists for which the condition is true. Invalid pairs (with common src entry) are ignored. If there is no condition, it returns the number of valid particle pairs.

A function would be more natural. Making it a subroutine avoids another compiler bug (internal error in nagfor 5.2 (649)). (See the interface `binary_num`.)

<Eval trees: procedures>+≡

```

subroutine count_pp (ival, en1, en2, en0)
    integer, intent(out) :: ival
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    integer :: i, j, n1, n2, count
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    if (present (en0)) then
        count = 0
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subevt_get_prt (en2%pval, j)
                if (are_disjoint (en0%prt1, en0%prt2)) then
                    call eval_node_evaluate (en0)
                    if (en0%lval) count = count + 1
                end if
            end do
        end do
    else
        count = 0
        do i = 1, n1
            do j = 1, n2
                if (are_disjoint (subevt_get_prt (en1%pval, i), &
                                     subevt_get_prt (en2%pval, j))) then
                    count = count + 1
                end if
            end do
        end do
    end if
    ival = count

```

```
end subroutine count_pp
```

This function makes up a subevent from the second argument which consists only of particles which match the PDG code array (first argument).

<Eval trees: procedures>+≡

```
subroutine select_pdg_ca (subevt, en1, en2, en0)
  type(subevt_t), intent(inout) :: subevt
  type(eval_node_t), intent(in) :: en1, en2
  type(eval_node_t), intent(inout), optional :: en0
  if (present (en0)) then
    call subevt_select_pdg_code (subevt, en1%aval, en2%pval, en0%ival)
  else
    call subevt_select_pdg_code (subevt, en1%aval, en2%pval)
  end if
end subroutine select_pdg_ca
```

Binary string functions

Currently, the only string operation is concatenation.

<Eval trees: procedures>+≡

```
subroutine concat_ss (string, en1, en2)
  type(string_t), intent(out) :: string
  type(eval_node_t), intent(in) :: en1, en2
  string = en1%sval // en2%sval
end subroutine concat_ss
```

26.3.4 Compiling the parse tree

The evaluation tree is built recursively by following a parse tree. Debug option:

<Eval trees: variables>≡

```
logical, parameter :: debug = .false.
```

Evaluate an expression. The requested type is given as an optional argument; default is numeric (integer or real).

<Eval trees: procedures>+≡

```
recursive subroutine eval_node_compile_genexpr &
  (en, pn, var_list, result_type)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  integer, intent(in), optional :: result_type
  if (debug) then
    print *, "read genexpr"; call parse_node_write (pn)
  end if
  if (present (result_type)) then
    select case (result_type)
    case (V_INT, V_REAL, V_CMPLX)
      call eval_node_compile_expr (en, pn, var_list)
    case (V_LOG)
```

```

        call eval_node_compile_lexpr (en, pn, var_list)
    case (V_SEV)
        call eval_node_compile_pexpr (en, pn, var_list)
    case (V_PDG)
        call eval_node_compile_cexpr (en, pn, var_list)
    case (V_STR)
        call eval_node_compile_sexpr (en, pn, var_list)
    end select
else
    call eval_node_compile_expr (en, pn, var_list)
end if
if (debug) then
    call eval_node_write (en)
    print *, "done genexpr"
end if
end subroutine eval_node_compile_genexpr

```

Numeric expressions

This procedure compiles a numerical expression. This is a single term or a sum or difference of terms. We have to account for all combinations of integer and real arguments. If both are constant, we immediately do the calculation and allocate a constant node.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_expr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_term, pn_addition, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(string_t) :: key
    integer :: t1, t2, t
    if (debug) then
        print *, "read expr"; call parse_node_write (pn)
    end if
    pn_term => parse_node_get_sub_ptr (pn)
    select case (char (parse_node_get_rule_key (pn_term)))
    case ("term")
        call eval_node_compile_term (en, pn_term, var_list)
        pn_addition => parse_node_get_next_ptr (pn_term, tag="addition")
    case ("addition")
        en => null ()
        pn_addition => pn_term
    case default
        call parse_node_mismatch ("term|addition", pn)
    end select
    do while (associated (pn_addition))
        pn_op => parse_node_get_sub_ptr (pn_addition)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="term")
        call eval_node_compile_term (en2, pn_arg, var_list)
        t2 = en2%result_type
        if (associated (en)) then

```

```

en1 => en
t1 = en1%result_type
else
allocate (en1)
select case (t2)
case (V_INT); call eval_node_init_int (en1, 0)
case (V_REAL); call eval_node_init_real (en1, 0._default)
case (V_CMPLX); call eval_node_init_cmplx (en1, cmplx &
(0._default, 0._default, kind=default))
end select
t1 = t2
end if
t = numeric_result_type (t1, t2)
allocate (en)
key = parse_node_get_key (pn_op)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
select case (char (key))
case ("+")
select case (t1)
case (V_INT)
select case (t2)
case (V_INT); call eval_node_init_int (en, add_ii (en1, en2))
case (V_REAL); call eval_node_init_real (en, add_ir (en1, en2))
case (V_CMPLX); call eval_node_init_cmplx (en, add_ic (en1, en2))
end select
case (V_REAL)
select case (t2)
case (V_INT); call eval_node_init_real (en, add_ri (en1, en2))
case (V_REAL); call eval_node_init_real (en, add_rr (en1, en2))
case (V_CMPLX); call eval_node_init_cmplx (en, add_rc (en1, en2))
end select
case (V_CMPLX)
select case (t2)
case (V_INT); call eval_node_init_cmplx (en, add_ci (en1, en2))
case (V_REAL); call eval_node_init_cmplx (en, add_cr (en1, en2))
case (V_CMPLX); call eval_node_init_cmplx (en, add_cc (en1, en2))
end select
end select
case ("-")
select case (t1)
case (V_INT)
select case (t2)
case (V_INT); call eval_node_init_int (en, sub_ii (en1, en2))
case (V_REAL); call eval_node_init_real (en, sub_ir (en1, en2))
case (V_CMPLX); call eval_node_init_cmplx (en, sub_ic (en1, en2))
end select
case (V_REAL)
select case (t2)
case (V_INT); call eval_node_init_real (en, sub_ri (en1, en2))
case (V_REAL); call eval_node_init_real (en, sub_rr (en1, en2))
case (V_CMPLX); call eval_node_init_cmplx (en, sub_rc (en1, en2))
end select
case (V_CMPLX)
select case (t2)

```

```

        case (V_INT); call eval_node_init_cmplx (en, sub_ci (en1, en2))
        case (V_REAL); call eval_node_init_cmplx (en, sub_cr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, sub_cc (en1, en2))
    end select
end select
end select
call eval_node_final_rec (en1)
call eval_node_final_rec (en2)
deallocate (en1, en2)
else
call eval_node_init_branch (en, key, t, en1, en2)
select case (char (key))
case ("+")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, add_ii)
        case (V_REAL); call eval_node_set_op2_real (en, add_ir)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, add_ic)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, add_ri)
        case (V_REAL); call eval_node_set_op2_real (en, add_rr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, add_rc)
        end select
    case (V_CMPLX)
        select case (t2)
        case (V_INT); call eval_node_set_op2_cmplx (en, add_ci)
        case (V_REAL); call eval_node_set_op2_cmplx (en, add_cr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, add_cc)
        end select
    end select
case ("-")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, sub_ii)
        case (V_REAL); call eval_node_set_op2_real (en, sub_ir)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, sub_ic)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, sub_ri)
        case (V_REAL); call eval_node_set_op2_real (en, sub_rr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, sub_rc)
        end select
    case (V_CMPLX)
        select case (t2)
        case (V_INT); call eval_node_set_op2_cmplx (en, sub_ci)
        case (V_REAL); call eval_node_set_op2_cmplx (en, sub_cr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, sub_cc)
        end select
    end select
end select

```

```

        end select
    end if
    pn_addition => parse_node_get_next_ptr (pn_addition)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done expr"
end if
end subroutine eval_node_compile_expr

```

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_term (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_factor, pn_multiplication, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(string_t) :: key
    integer :: t1, t2, t
    if (debug) then
        print *, "read term"; call parse_node_write (pn)
    end if
    pn_factor => parse_node_get_sub_ptr (pn, tag="factor")
    call eval_node_compile_factor (en, pn_factor, var_list)
    pn_multiplication => &
        parse_node_get_next_ptr (pn_factor, tag="multiplication")
    do while (associated (pn_multiplication))
        pn_op => parse_node_get_sub_ptr (pn_multiplication)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="factor")
        en1 => en
        call eval_node_compile_factor (en2, pn_arg, var_list)
        t1 = en1%result_type
        t2 = en2%result_type
        t = numeric_result_type (t1, t2)
        allocate (en)
        key = parse_node_get_key (pn_op)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            select case (char (key))
            case ("*")
                select case (t1)
                case (V_INT)
                    select case (t2)
                    case (V_INT); call eval_node_init_int (en, mul_ii (en1, en2))
                    case (V_REAL); call eval_node_init_real (en, mul_ir (en1, en2))
                    case (V_CMPLX); call eval_node_init_cmplx (en, mul_ic (en1, en2))
                    end select
                case (V_REAL)
                    select case (t2)
                    case (V_INT); call eval_node_init_real (en, mul_ri (en1, en2))
                    case (V_REAL); call eval_node_init_real (en, mul_rr (en1, en2))
                    case (V_CMPLX); call eval_node_init_cmplx (en, mul_rc (en1, en2))
                    end select
                case (V_CMPLX)
                    select case (t2)

```

```

        case (V_INT); call eval_node_init_cmplx (en, mul_ci (en1, en2))
        case (V_REAL); call eval_node_init_cmplx (en, mul_cr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, mul_cc (en1, en2))
    end select
end select
case ("/")
select case (t1)
case (V_INT)
    select case (t2)
    case (V_INT); call eval_node_init_int (en, div_ii (en1, en2))
    case (V_REAL); call eval_node_init_real (en, div_ir (en1, en2))
    case (V_CMPLX); call eval_node_init_real (en, div_ir (en1, en2))
    end select
case (V_REAL)
    select case (t2)
    case (V_INT); call eval_node_init_real (en, div_ri (en1, en2))
    case (V_REAL); call eval_node_init_real (en, div_rr (en1, en2))
    case (V_CMPLX); call eval_node_init_cmplx (en, div_rc (en1, en2))
    end select
case (V_CMPLX)
    select case (t2)
    case (V_INT); call eval_node_init_cmplx (en, div_ci (en1, en2))
    case (V_REAL); call eval_node_init_cmplx (en, div_cr (en1, en2))
    case (V_CMPLX); call eval_node_init_cmplx (en, div_cc (en1, en2))
    end select
end select
end select
call eval_node_final_rec (en1)
call eval_node_final_rec (en2)
deallocate (en1, en2)
else
call eval_node_init_branch (en, key, t, en1, en2)
select case (char (key))
case ("*")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, mul_ii)
        case (V_REAL); call eval_node_set_op2_real (en, mul_ir)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, mul_ic)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, mul_ri)
        case (V_REAL); call eval_node_set_op2_real (en, mul_rr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, mul_rc)
        end select
    case (V_CMPLX)
        select case (t2)
        case (V_INT); call eval_node_set_op2_cmplx (en, mul_ci)
        case (V_REAL); call eval_node_set_op2_cmplx (en, mul_cr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, mul_cc)
        end select
    end select
end select

```



```

case ("/")
  select case (t1)
    case (V_INT)
      select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, div_ii)
        case (V_REAL); call eval_node_set_op2_real (en, div_ir)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, div_ic)
      end select
    case (V_REAL)
      select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, div_ri)
        case (V_REAL); call eval_node_set_op2_real (en, div_rr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, div_rc)
      end select
    case (V_CMPLX)
      select case (t2)
        case (V_INT); call eval_node_set_op2_cmplx (en, div_ci)
        case (V_REAL); call eval_node_set_op2_cmplx (en, div_cr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, div_cc)
      end select
    end select
  end select
end if
pn_multiplication => parse_node_get_next_ptr (pn_multiplication)
end do
if (debug) then
  call eval_node_write (en)
  print *, "done term"
end if
end subroutine eval_node_compile_term

```

(*Eval trees: procedures*) \equiv

```

recursive subroutine eval_node_compile_factor (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_value, pn_exponentiation, pn_op, pn_arg
  type(eval_node_t), pointer :: en1, en2
  type(string_t) :: key
  integer :: t1, t2, t
  if (debug) then
    print *, "read factor"; call parse_node_write (pn)
  end if
  pn_value => parse_node_get_sub_ptr (pn)
  call eval_node_compile_signed_value (en, pn_value, var_list)
  pn_exponentiation => &
    parse_node_get_next_ptr (pn_value, tag="exponentiation")
  if (associated (pn_exponentiation)) then
    pn_op => parse_node_get_sub_ptr (pn_exponentiation)
    pn_arg => parse_node_get_next_ptr (pn_op)
    en1 => en
    call eval_node_compile_signed_value (en2, pn_arg, var_list)
    t1 = en1%result_type
    t2 = en2%result_type
  end if
end subroutine eval_node_compile_factor

```

```

t = numeric_result_type (t1, t2)
allocate (en)
key = parse_node_get_key (pn_op)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
  select case (t1)
    case (V_INT)
      select case (t2)
        case (V_INT); call eval_node_init_int (en, pow_ii (en1, en2))
        case (V_REAL); call eval_node_init_real (en, pow_ir (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, pow_ic (en1, en2))
      end select
    case (V_REAL)
      select case (t2)
        case (V_INT); call eval_node_init_real (en, pow_ri (en1, en2))
        case (V_REAL); call eval_node_init_real (en, pow_rr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, pow_rc (en1, en2))
      end select
    case (V_CMPLX)
      select case (t2)
        case (V_INT); call eval_node_init_cmplx (en, pow_ci (en1, en2))
        case (V_REAL); call eval_node_init_cmplx (en, pow_cr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, pow_cc (en1, en2))
      end select
  end select
  call eval_node_final_rec (en1)
  call eval_node_final_rec (en2)
  deallocate (en1, en2)
else
  call eval_node_init_branch (en, key, t, en1, en2)
  select case (t1)
    case (V_INT)
      select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, pow_ii)
        case (V_REAL,V_CMPLX); call eval_type_error (pn, "exponentiation", t1)
      end select
    case (V_REAL)
      select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, pow_ri)
        case (V_REAL); call eval_node_set_op2_real (en, pow_rr)
        case (V_CMPLX); call eval_type_error (pn, "exponentiation", t1)
      end select
    case (V_CMPLX)
      select case (t2)
        case (V_INT); call eval_node_set_op2_cmplx (en, pow_ci)
        case (V_REAL); call eval_node_set_op2_cmplx (en, pow_cr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, pow_cc)
      end select
  end select
end if
end if
if (debug) then
  call eval_node_write (en)
  print *, "done factor"
end if

```

```
end subroutine eval_node_compile_factor
```

(Eval trees: procedures)+≡

```
recursive subroutine eval_node_compile_signed_value (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_arg
  type(eval_node_t), pointer :: en1
  integer :: t
  if (debug) then
    print *, "read signed value"; call parse_node_write (pn)
  end if
  select case (char (parse_node_get_rule_key (pn)))
  case ("signed_value")
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    call eval_node_compile_value (en1, pn_arg, var_list)
    t = en1%result_type
    allocate (en)
    if (en1%type == EN_CONSTANT) then
      select case (t)
      case (V_INT); call eval_node_init_int (en, neg_i (en1))
      case (V_REAL); call eval_node_init_real (en, neg_r (en1))
      case (V_CMPLX); call eval_node_init_cmplx (en, neg_c (en1))
      end select
      call eval_node_final_rec (en1)
      deallocate (en1)
    else
      call eval_node_init_branch (en, var_str ("-"), t, en1)
      select case (t)
      case (V_INT); call eval_node_set_op1_int (en, neg_i)
      case (V_REAL); call eval_node_set_op1_real (en, neg_r)
      case (V_CMPLX); call eval_node_set_op1_cmplx (en, neg_c)
      end select
    end if
  case default
    call eval_node_compile_value (en, pn, var_list)
  end select
  if (debug) then
    call eval_node_write (en)
    print *, "done signed value"
  end if
end subroutine eval_node_compile_signed_value
```

Integer, real and complex values have an optional unit. The unit is extracted and applied immediately. An integer with unit evaluates to a real constant.

(Eval trees: procedures)+≡

```
recursive subroutine eval_node_compile_value (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  if (debug) then
    print *, "read value"; call parse_node_write (pn)
```

```

end if
select case (char (parse_node_get_rule_key (pn)))
case ("integer_value", "real_value", "complex_value")
    call eval_node_compile_numeric_value (en, pn)
case ("pi")
    call eval_node_compile_constant (en, pn)
case ("I")
    call eval_node_compile_constant (en, pn)
case ("variable")
    call eval_node_compile_variable (en, pn, var_list)
case ("result")
    call eval_node_compile_result (en, pn, var_list)
case ("user_observable")
    call eval_node_compile_user_observable (en, pn, var_list)
case ("expr")
    call eval_node_compile_expr (en, pn, var_list)
case ("block_expr")
    call eval_node_compile_block_expr (en, pn, var_list)
case ("conditional_expr")
    call eval_node_compile_conditional (en, pn, var_list)
case ("unary_function")
    call eval_node_compile_unary_function (en, pn, var_list)
case ("binary_function")
    call eval_node_compile_binary_function (en, pn, var_list)
case ("eval_fun")
    call eval_node_compile_eval_function (en, pn, var_list)
case ("count_fun", "user_event_fun")
    call eval_node_compile_numeric_function (en, pn, var_list)
case default
    call parse_node_mismatch &
        ("integer|real|complex|constant|variable|" // &
         "expr|block_expr|conditional_expr|" // &
         "unary_function|binary_function|numeric_pexpr", pn)
end select
if (debug) then
    call eval_node_write (en)
    print *, "done value"
end if
end subroutine eval_node_compile_value

```

Real, complex and integer values are numeric literals with an optional unit attached. In case of an integer, the unit actually makes it a real value in disguise. The signed version of real values is not possible in generic expressions; it is a special case for numeric constants in model files (see below). We do not introduce signed versions of complex values.

(Eval trees: procedures)+≡

```

subroutine eval_node_compile_numeric_value (en, pn)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(parse_node_t), pointer :: pn_val, pn_unit
    allocate (en)
    pn_val => parse_node_get_sub_ptr (pn)
    pn_unit => parse_node_get_next_ptr (pn_val)

```

```

select case (char (parse_node_get_rule_key (pn)))
case ("integer_value")
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      parse_node_get_integer (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_int (en, parse_node_get_integer (pn_val))
  end if
case ("real_value")
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      parse_node_get_real (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_real (en, parse_node_get_real (pn_val))
  end if
case ("complex_value")
  if (associated (pn_unit)) then
    call eval_node_init_cmplx (en, &
      parse_node_get_cmplx (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_cmplx (en, parse_node_get_cmplx (pn_val))
  end if
case ("neg_real_value")
  pn_val => parse_node_get_sub_ptr (parse_node_get_sub_ptr (pn, 2))
  pn_unit => parse_node_get_next_ptr (pn_val)
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      - parse_node_get_real (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_real (en, - parse_node_get_real (pn_val))
  end if
case ("pos_real_value")
  pn_val => parse_node_get_sub_ptr (parse_node_get_sub_ptr (pn, 2))
  pn_unit => parse_node_get_next_ptr (pn_val)
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      parse_node_get_real (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_real (en, parse_node_get_real (pn_val))
  end if
case default
  call parse_node_mismatch &
    ("integer_value|real_value|complex_value|neg_real_value|pos_real_value", pn)
end select
end subroutine eval_node_compile_numeric_value

```

These are the units, predefined and hardcoded. The default energy unit is GeV, the default angular unit is radians. We include units for observables of dimension energy squared. Luminosities are normalized in inverse femtobarns.

(Eval trees: procedures)+≡

```

function parse_node_get_unit (pn) result (factor)
  real(default) :: factor
  real(default) :: unit

```

```

type(parse_node_t), intent(in) :: pn
type(parse_node_t), pointer :: pn_unit, pn_unit_power
type(parse_node_t), pointer :: pn_frac, pn_num, pn_int, pn_div, pn_den
integer :: num, den
pn_unit => parse_node_get_sub_ptr (pn)
select case (char (parse_node_get_key (pn_unit)))
case ("TeV"); unit = 1.e3_default
case ("GeV"); unit = 1
case ("MeV"); unit = 1.e-3_default
case ("keV"); unit = 1.e-6_default
case ("eV"); unit = 1.e-9_default
case ("meV"); unit = 1.e-12_default
case ("nbarn"); unit = 1.e6_default
case ("pbarn"); unit = 1.e3_default
case ("fbarn"); unit = 1
case ("abarn"); unit = 1.e-3_default
case ("rad"); unit = 1
case ("mrad"); unit = 1.e-3_default
case ("degree"); unit = degree
case ("%"); unit = 1.e-2_default
case default
    call msg_bug (" Unit ' " // &
        char (parse_node_get_key (pn)) // "' is undefined.")
end select
pn_unit_power => parse_node_get_next_ptr (pn_unit)
if (associated (pn_unit_power)) then
    pn_frac => parse_node_get_sub_ptr (pn_unit_power, 2)
    pn_num => parse_node_get_sub_ptr (pn_frac)
    select case (char (parse_node_get_rule_key (pn_num)))
    case ("neg_int")
        pn_int => parse_node_get_sub_ptr (pn_num, 2)
        num = - parse_node_get_integer (pn_int)
    case ("pos_int")
        pn_int => parse_node_get_sub_ptr (pn_num, 2)
        num = parse_node_get_integer (pn_int)
    case ("integer_literal")
        num = parse_node_get_integer (pn_num)
    case default
        call parse_node_mismatch ("neg_int|pos_int|integer_literal", pn_num)
    end select
    pn_div => parse_node_get_next_ptr (pn_num)
    if (associated (pn_div)) then
        pn_den => parse_node_get_sub_ptr (pn_div, 2)
        den = parse_node_get_integer (pn_den)
    else
        den = 1
    end if
else
    num = 1
    den = 1
end if
factor = unit ** (real (num, default) / den)
end function parse_node_get_unit

```

There are only two predefined constants, but more can be added easily.

<Eval trees: procedures>+≡

```

subroutine eval_node_compile_constant (en, pn)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  if (debug) then
    print *, "read constant"; call parse_node_write (pn)
  end if
  allocate (en)
  select case (char (parse_node_get_key (pn)))
    case ("pi");      call eval_node_init_real (en, pi)
    case ("I");       call eval_node_init_cmplx (en, imago)
    case default
      call parse_node_mismatch ("pi or I", pn)
  end select
  if (debug) then
    call eval_node_write (en)
    print *, "done constant"
  end if
end subroutine eval_node_compile_constant

```

Compile a variable, with or without a specified type. Take the list of variables, look for the name and make a node with a pointer to the value. If no type is provided, the variable is numeric, and the stored value determines whether it is real or integer.

We explicitly demand that the variable is defined, so we do not accidentally point to variables that are declared only later in the script but have come into existence in a previous compilation pass.

Variables may actually be anonymous, these are expressions in disguise. In that case, the expression replaces the variable name in the parse tree, and we allocate an ordinary expression node in the eval tree.

Variables of type V_PDG (pdg-code array) are not treated here. They are handled by `eval_node_compile_cvariable`.

<Eval trees: procedures>+≡

```

recursive subroutine eval_node_compile_variable (en, pn, var_list, var_type)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in), target :: pn
  type(var_list_t), intent(in), target :: var_list
  integer, intent(in), optional :: var_type
  type(parse_node_t), pointer :: pn_name
  type(string_t) :: var_name
  logical, target, save :: no_lval
  real(default), target, save :: no_rval
  type(subvt_t), target, save :: no_pval
  type(string_t), target, save :: no_sval
  logical, target, save :: unknown = .false.
  integer :: type
  logical :: defined
  logical, pointer :: known
  logical, pointer :: lptr
  integer, pointer :: iptr
  real(default), pointer :: rptr

```

```

complex(default), pointer :: cptr
type(pdg_array_t), pointer :: aptr
type(subevt_t), pointer :: pptr
type(string_t), pointer :: sptr
procedure(obs_unary_int), pointer :: obs1_iptr
procedure(obs_unary_real), pointer :: obs1_rptr
procedure(obs_binary_int), pointer :: obs2_iptr
procedure(obs_binary_real), pointer :: obs2_rptr
type(prt_t), pointer :: p1, p2
if (debug) then
    print *, "read variable"; call parse_node_write (pn)
end if
if (present (var_type)) then
    select case (var_type)
        case (V_REAL, V_OBS1_REAL, V_OBS2_REAL, V_INT, V_OBS1_INT, &
              V_OBS2_INT, V_CMPLX)
            pn_name => pn
        case default
            pn_name => parse_node_get_sub_ptr (pn, 2)
        end select
    else
        pn_name => pn
    end if
    select case (char (parse_node_get_rule_key (pn_name)))
        case ("expr")
            call eval_node_compile_expr (en, pn_name, var_list)
        case ("lexpr")
            call eval_node_compile_lexpr (en, pn_name, var_list)
        case ("sexpr")
            call eval_node_compile_sexpr (en, pn_name, var_list)
        case ("pexpr")
            call eval_node_compile_pexpr (en, pn_name, var_list)
        case ("variable")
            var_name = parse_node_get_string (pn_name)
            if (present (var_type)) then
                select case (var_type)
                    case (V_LOG); var_name = "?" // var_name
                    case (V_SEV); var_name = "@" // var_name
                    case (V_STR); var_name = "$" // var_name ! $ sign
                end select
            end if
            call var_list%get_var_properties &
                (var_name, req_type=var_type, type=type, is_defined=defined)
            allocate (en)
            if (defined) then
                select case (type)
                    case (V_LOG)
                        call var_list%get_lptr (var_name, lptr, known)
                        call eval_node_init_log_ptr (en, var_name, lptr, known)
                    case (V_INT)
                        call var_list%get_iptr (var_name, iptr, known)
                        call eval_node_init_int_ptr (en, var_name, iptr, known)
                    case (V_REAL)
                        call var_list%get_rptr (var_name, rptr, known)

```



```

        call eval_node_init_real_ptr (en, var_name, rptr, known)
case (V_CMPLX)
    call var_list%get_cptr (var_name, cptr, known)
    call eval_node_init_cmplx_ptr (en, var_name, cptr, known)
case (V_SEV)
    call var_list%get_pptr (var_name, pptr, known)
    call eval_node_init_subevt_ptr (en, var_name, pptr, known)
case (V_STR)
    call var_list%get_sptr (var_name, sptr, known)
    call eval_node_init_string_ptr (en, var_name, sptr, known)
case (V_OBS1_INT)
    call var_list%get_obs1_iptr (var_name, obs1_iptr, p1)
    call eval_node_init_obs1_int_ptr (en, var_name, obs1_iptr, p1)
case (V_OBS2_INT)
    call var_list%get_obs2_iptr (var_name, obs2_iptr, p1, p2)
    call eval_node_init_obs2_int_ptr (en, var_name, obs2_iptr, p1, p2)
case (V_OBS1_REAL)
    call var_list%get_obs1_rptr (var_name, obs1_rptr, p1)
    call eval_node_init_obs1_real_ptr (en, var_name, obs1_rptr, p1)
case (V_OBS2_REAL)
    call var_list%get_obs2_rptr (var_name, obs2_rptr, p1, p2)
    call eval_node_init_obs2_real_ptr (en, var_name, obs2_rptr, p1, p2)
case default
    call parse_node_write (pn)
    call msg_fatal ("Variable of this type " // &
        "is not allowed in the present context")
    if (present (var_type)) then
        select case (var_type)
        case (V_LOG)
            call eval_node_init_log_ptr (en, var_name, no_lval, unknown)
        case (V_SEV)
            call eval_node_init_subevt_ptr &
                (en, var_name, no_pval, unknown)
        case (V_STR)
            call eval_node_init_string_ptr &
                (en, var_name, no_sval, unknown)
        end select
    else
        call eval_node_init_real_ptr (en, var_name, no_rval, unknown)
    end if
end select
else
    call parse_node_write (pn)
    call msg_error ("This variable is undefined at this point")
    if (present (var_type)) then
        select case (var_type)
        case (V_LOG)
            call eval_node_init_log_ptr (en, var_name, no_lval, unknown)
        case (V_SEV)
            call eval_node_init_subevt_ptr &
                (en, var_name, no_pval, unknown)
        case (V_STR)
            call eval_node_init_string_ptr (en, var_name, no_sval, unknown)
        end select
    end if
end select

```

```

        else
            call eval_node_init_real_ptr (en, var_name, no_rval, unknown)
        end if
    end if
end select
if (debug) then
    call eval_node_write (en)
    print *, "done variable"
end if
end subroutine eval_node_compile_variable

```

In a given context, a variable has to have a certain type.

(Eval trees: procedures)+≡

```

subroutine check_var_type (pn, ok, type_actual, type_requested)
    type(parse_node_t), intent(in) :: pn
    logical, intent(out) :: ok
    integer, intent(in) :: type_actual
    integer, intent(in), optional :: type_requested
    if (present (type_requested)) then
        select case (type_requested)
        case (V_LOG)
            select case (type_actual)
            case (V_LOG)
            case default
                call parse_node_write (pn)
                call msg_fatal ("Variable type is invalid (should be logical)")
                ok = .false.
            end select
        case (V_SEV)
            select case (type_actual)
            case (V_SEV)
            case default
                call parse_node_write (pn)
                call msg_fatal &
                    ("Variable type is invalid (should be particle set)")
                ok = .false.
            end select
        case (V_PDG)
            select case (type_actual)
            case (V_PDG)
            case default
                call parse_node_write (pn)
                call msg_fatal &
                    ("Variable type is invalid (should be PDG array)")
                ok = .false.
            end select
        case (V_STR)
            select case (type_actual)
            case (V_STR)
            case default
                call parse_node_write (pn)
                call msg_fatal &
                    ("Variable type is invalid (should be string)")
                ok = .false.
            end select
        end select
    end if
end subroutine check_var_type

```

```

        end select
      case default
        call parse_node_write (pn)
        call msg_bug ("Variable type is unknown")
      end select
    else
      select case (type_actual)
        case (V_REAL, V_OBS1_REAL, V_OBS2_REAL, V_INT, V_OBS1_INT, &
              V_OBS2_INT, V_CMPLX)
        case default
          call parse_node_write (pn)
          call msg_fatal ("Variable type is invalid (should be numeric)")
          ok = .false.
        end select
      end if
      ok = .true.
    end subroutine check_var_type

```

Retrieve the result of an integration. If the requested process has been integrated, the results are available as special variables. (The variables cannot be accessed in the usual way since they contain brackets in their names.)

Since this compilation step may occur before the processes have been loaded, we have to initialize the required variables before they are used.

(Eval trees: procedures)+≡

```

subroutine eval_node_compile_result (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in), target :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_key, pn_prc_id
  type(string_t) :: key, prc_id, var_name
  integer, pointer :: iptr
  real(default), pointer :: rptr
  logical, pointer :: known
  if (debug) then
    print *, "read result"; call parse_node_write (pn)
  end if
  pn_key => parse_node_get_sub_ptr (pn)
  pn_prc_id => parse_node_get_next_ptr (pn_key)
  key = parse_node_get_key (pn_key)
  prc_id = parse_node_get_string (pn_prc_id)
  var_name = key // "(" // prc_id // ")"
  if (var_list%contains (var_name)) then
    allocate (en)
    select case (char(key))
      case ("num_id", "n_calls")
        call var_list%get_iptr (var_name, iptr, known)
        call eval_node_init_int_ptr (en, var_name, iptr, known)
      case ("integral", "error")
        call var_list%get_rptr (var_name, rptr, known)
        call eval_node_init_real_ptr (en, var_name, rptr, known)
    end select
  else
    call msg_fatal ("Result variable '" // char (var_name) &

```

```

        // '' is undefined (call 'integrate' before use)")
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done result"
    end if
end subroutine eval_node_compile_result

```

This user observable behaves like a variable. We link the node to the generic user-observable entry in the variable list. The syntax element has an argument which provides the name of the user variable, this is stored as an eval-node alongside with the variable. When the variable value is used, the user-supplied external function is called and provides the (real) result value.

(*Eval trees: procedures*) +=

```

subroutine eval_node_compile_user_observable (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_arg, pn_obs
    type(eval_node_t), pointer :: en0
    integer :: res_type
    type(string_t) :: var_name
    integer :: type
    logical :: defined
    if (debug) then
        print *, "read user observable"; call parse_node_write (pn)
    end if
    pn_key => parse_node_get_sub_ptr (pn)
    select case (char (parse_node_get_key (pn_key)))
    case ("user_obs")
        res_type = V_REAL
    case default
        call parse_node_write (pn_key)
        call msg_bug ("user_observable: wrong keyword")
    end select
    pn_arg => parse_node_get_next_ptr (pn_key)
    pn_obs => parse_node_get_sub_ptr (pn_arg)
    call eval_node_compile_sexpr (en0, pn_obs, var_list)
    select case (res_type)
    case (V_INT); var_name = "_User_obs_int"
    case (V_REAL); var_name = "_User_obs_real"
    end select
    call var_list%get_var_properties (var_name, type=type, is_defined=defined)
    allocate (en)
    if (defined) then
        select case (type)
        case (V_UOBS1_INT)
            call eval_node_init_uobs1_int (en, var_name, en0)
        case (V_UOBS2_INT)
            call eval_node_init_uobs2_int (en, var_name, en0)
        case (V_UOBS1_REAL)
            call eval_node_init_uobs1_real (en, var_name, en0)
        case (V_UOBS2_REAL)

```

```

        call eval_node_init_uobs2_real (en, var_name, en0)
    end select
else
    call parse_node_write (pn)
    call msg_error ("This variable is undefined at this point")
end if
if (debug) then
    call eval_node_write (en)
    print *, "done user observable"
end if
end subroutine eval_node_compile_user_observable

```

Functions with a single argument. For non-constant arguments, watch for functions which convert their argument to a different type.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_unary_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_fname, pn_arg
    type(eval_node_t), pointer :: en1
    type(string_t) :: key
    integer :: t
    if (debug) then
        print *, "read unary function"; call parse_node_write (pn)
    end if
    pn_fname => parse_node_get_sub_ptr (pn)
    pn_arg => parse_node_get_next_ptr (pn_fname, tag="function_arg1")
    call eval_node_compile_expr &
        (en1, parse_node_get_sub_ptr (pn_arg, tag="expr"), var_list)
    t = en1%result_type
    allocate (en)
    key = parse_node_get_key (pn_fname)
    if (en1%type == EN_CONSTANT) then
        select case (char (key))
        case ("complex")
            select case (t)
            case (V_INT); call eval_node_init_cmplx (en, cmplx_i (en1))
            case (V_REAL); call eval_node_init_cmplx (en, cmplx_r (en1))
            case (V_CMPLX); deallocate (en); en => en1; en1 => null ()
            case default; call eval_type_error (pn, char (key), t)
            end select
        case ("real")
            select case (t)
            case (V_INT); call eval_node_init_real (en, real_i (en1))
            case (V_REAL); deallocate (en); en => en1; en1 => null ()
            case (V_CMPLX); call eval_node_init_real (en, real_c (en1))
            case default; call eval_type_error (pn, char (key), t)
            end select
        case ("int")
            select case (t)
            case (V_INT); deallocate (en); en => en1; en1 => null ()
            case (V_REAL); call eval_node_init_int (en, int_r (en1))

```

```

        case (V_CMPLX); call eval_node_init_int (en, int_c (en1))
    end select
case ("nint")
    select case (t)
        case (V_INT); deallocate (en); en => en1; en1 => null ()
        case (V_REAL); call eval_node_init_int (en, nint_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("floor")
    select case (t)
        case (V_INT); deallocate (en); en => en1; en1 => null ()
        case (V_REAL); call eval_node_init_int (en, floor_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("ceiling")
    select case (t)
        case (V_INT); deallocate (en); en => en1; en1 => null ()
        case (V_REAL); call eval_node_init_int (en, ceiling_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("abs")
    select case (t)
        case (V_INT); call eval_node_init_int (en, abs_i (en1))
        case (V_REAL); call eval_node_init_real (en, abs_r (en1))
        case (V_CMPLX); call eval_node_init_real (en, abs_c (en1))
    end select
case ("sgn")
    select case (t)
        case (V_INT); call eval_node_init_int (en, sgn_i (en1))
        case (V_REAL); call eval_node_init_real (en, sgn_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("sqrt")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, sqrt_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, sqrt_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("exp")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, exp_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, exp_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("log")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, log_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, log_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("log10")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, log10_r (en1))
        case default; call eval_type_error (pn, char (key), t)

```

```

        end select
    case ("sin")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, sin_r (en1))
            case (V_CMPLX); call eval_node_init_cmplx (en, sin_c (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("cos")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, cos_r (en1))
            case (V_CMPLX); call eval_node_init_cmplx (en, cos_c (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("tan")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, tan_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("asin")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, asin_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("acos")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, acos_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("atan")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, atan_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("sinh")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, sinh_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("cosh")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, cosh_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("tanh")
        select case (t)
            case (V_REAL); call eval_node_init_real (en, tanh_r (en1))
            case default; call eval_type_error (pn, char (key), t)
        end select
    case default
        call parse_node_mismatch ("function name", pn_fname)
    end select
if (associated (en1)) then
    call eval_node_final_rec (en1)
    deallocate (en1)

```

```

        end if
else
    select case (char (key))
    case ("complex")
        call eval_node_init_branch (en, key, V_CMPLX, en1)
    case ("real")
        call eval_node_init_branch (en, key, V_REAL, en1)
    case ("int", "nint", "floor", "ceiling")
        call eval_node_init_branch (en, key, V_INT, en1)
    case default
        call eval_node_init_branch (en, key, t, en1)
    end select
    select case (char (key))
    case ("complex")
        select case (t)
        case (V_INT); call eval_node_set_op1_cmplx (en, cmplx_i)
        case (V_REAL); call eval_node_set_op1_cmplx (en, cmplx_r)
        case (V_CMPLX); deallocate (en); en => en1
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("real")
        select case (t)
        case (V_INT); call eval_node_set_op1_real (en, real_i)
        case (V_REAL); deallocate (en); en => en1
        case (V_CMPLX); call eval_node_set_op1_real (en, real_c)
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("int")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_set_op1_int (en, int_r)
        case (V_CMPLX); call eval_node_set_op1_int (en, int_c)
        end select
    case ("nint")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_set_op1_int (en, nint_r)
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("floor")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_set_op1_int (en, floor_r)
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("ceiling")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_set_op1_int (en, ceiling_r)
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("abs")
        select case (t)
        case (V_INT); call eval_node_set_op1_int (en, abs_i)

```



```

        case (V_REAL); call eval_node_set_op1_real (en, abs_r)
        case (V_CMPLX);
            call eval_node_init_branch (en, key, V_REAL, en1)
            call eval_node_set_op1_real (en, abs_c)
        end select
    case ("sgn")
        select case (t)
            case (V_INT); call eval_node_set_op1_int (en, sgn_i)
            case (V_REAL); call eval_node_set_op1_real (en, sgn_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("sqrt")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, sqrt_r)
            case (V_CMPLX); call eval_node_set_op1_cmplx (en, sqrt_c)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("exp")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, exp_r)
            case (V_CMPLX); call eval_node_set_op1_cmplx (en, exp_c)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("log")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, log_r)
            case (V_CMPLX); call eval_node_set_op1_cmplx (en, log_c)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("log10")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, log10_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("sin")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, sin_r)
            case (V_CMPLX); call eval_node_set_op1_cmplx (en, sin_c)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("cos")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, cos_r)
            case (V_CMPLX); call eval_node_set_op1_cmplx (en, cos_c)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("tan")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, tan_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("asin")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, asin_r)

```

```

        case default; call eval_type_error (pn, char (key), t)
    end select
case ("acos")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, acos_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("atan")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, atan_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("sinh")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, sinh_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("cosh")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, cosh_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("tanh")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, tanh_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case default
    call parse_node_mismatch ("function name", pn_fname)
end select
end if
if (debug) then
    call eval_node_write (en)
    print *, "done function"
end if
end subroutine eval_node_compile_unary_function

```

Functions with two arguments.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_binary_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_fname, pn_arg, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en1, en2
    type(string_t) :: key
    integer :: t1, t2
    if (debug) then
        print *, "read binary function"; call parse_node_write (pn)
    end if
    pn_fname => parse_node_get_sub_ptr (pn)
    pn_arg => parse_node_get_next_ptr (pn_fname, tag="function_arg2")
    pn_arg1 => parse_node_get_sub_ptr (pn_arg, tag="expr")
    pn_arg2 => parse_node_get_next_ptr (pn_arg1, tag="expr")

```

```

call eval_node_compile_expr (en1, pn_arg1, var_list)
call eval_node_compile_expr (en2, pn_arg2, var_list)
t1 = en1%result_type
t2 = en2%result_type
allocate (en)
key = parse_node_get_key (pn_fname)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
  select case (char (key))
    case ("max")
      select case (t1)
        case (V_INT)
          select case (t2)
            case (V_INT); call eval_node_init_int  (en, max_ii (en1, en2))
            case (V_REAL); call eval_node_init_real (en, max_ir (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
          end select
        case (V_REAL)
          select case (t2)
            case (V_INT); call eval_node_init_real (en, max_ri (en1, en2))
            case (V_REAL); call eval_node_init_real (en, max_rr (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
          end select
        case default; call eval_type_error (pn, char (key), t1)
      end select
    case ("min")
      select case (t1)
        case (V_INT)
          select case (t2)
            case (V_INT); call eval_node_init_int  (en, min_ii (en1, en2))
            case (V_REAL); call eval_node_init_real (en, min_ir (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
          end select
        case (V_REAL)
          select case (t2)
            case (V_INT); call eval_node_init_real (en, min_ri (en1, en2))
            case (V_REAL); call eval_node_init_real (en, min_rr (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
          end select
        case default; call eval_type_error (pn, char (key), t1)
      end select
    case ("mod")
      select case (t1)
        case (V_INT)
          select case (t2)
            case (V_INT); call eval_node_init_int  (en, mod_ii (en1, en2))
            case (V_REAL); call eval_node_init_real (en, mod_ir (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
          end select
        case (V_REAL)
          select case (t2)
            case (V_INT); call eval_node_init_real (en, mod_ri (en1, en2))
            case (V_REAL); call eval_node_init_real (en, mod_rr (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
          end select
      end select
  end select
end if

```

```

        case default; call eval_type_error (pn, char (key), t1)
    end select
case ("modulo")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_int (en, modulo_ii (en1, en2))
        case (V_REAL); call eval_node_init_real (en, modulo_ir (en1, en2))
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_init_real (en, modulo_ri (en1, en2))
        case (V_REAL); call eval_node_init_real (en, modulo_rr (en1, en2))
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case default; call eval_type_error (pn, char (key), t2)
    end select
case default
    call parse_node_mismatch ("function name", pn_fname)
end select
call eval_node_final_rec (en1)
deallocate (en1)
else
    call eval_node_init_branch (en, key, t1, en1, en2)
    select case (char (key))
    case ("max")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_set_op2_int (en, max_ii)
            case (V_REAL); call eval_node_set_op2_real (en, max_ir)
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_set_op2_real (en, max_ri)
            case (V_REAL); call eval_node_set_op2_real (en, max_rr)
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case ("min")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_set_op2_int (en, min_ii)
            case (V_REAL); call eval_node_set_op2_real (en, min_ir)
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_set_op2_real (en, min_ri)
            case (V_REAL); call eval_node_set_op2_real (en, min_rr)

```

```

        case default; call eval_type_error (pn, char (key), t2)
    end select
    case default; call eval_type_error (pn, char (key), t2)
end select
case ("mod")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, mod_ii)
        case (V_REAL); call eval_node_set_op2_real (en, mod_ir)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, mod_ri)
        case (V_REAL); call eval_node_set_op2_real (en, mod_rr)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case default; call eval_type_error (pn, char (key), t2)
    end select
case ("modulo")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, modulo_ii)
        case (V_REAL); call eval_node_set_op2_real (en, modulo_ir)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, modulo_ri)
        case (V_REAL); call eval_node_set_op2_real (en, modulo_rr)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case default; call eval_type_error (pn, char (key), t2)
    end select
case default
    call parse_node_mismatch ("function name", pn_fname)
end select
end if
if (debug) then
    call eval_node_write (en)
    print *, "done function"
end if
end subroutine eval_node_compile_binary_function

```

Variable definition

A block expression contains a variable definition (first argument) and an expression where the definition can be used (second argument). The `result_type` decides which type of expression is expected for the second argument. For numeric variables, if there is a mismatch between real and integer type, insert an

extra node for type conversion.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_block_expr &
  (en, pn, var_list, result_type)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  integer, intent(in), optional :: result_type
  type(parse_node_t), pointer :: pn_var_spec, pn_var_subspec
  type(parse_node_t), pointer :: pn_var_type, pn_var_name, pn_var_expr
  type(parse_node_t), pointer :: pn_expr
  type(string_t) :: var_name
  type(eval_node_t), pointer :: en1, en2
  integer :: var_type
  logical :: new
  if (debug) then
    print *, "read block expr"; call parse_node_write (pn)
  end if
  new = .false.
  pn_var_spec => parse_node_get_sub_ptr (pn, 2)
  select case (char (parse_node_get_rule_key (pn_var_spec)))
  case ("var_num");      var_type = V_NONE
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec)
  case ("var_int");      var_type = V_INT
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_real");     var_type = V_REAL
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_cmplx");    var_type = V_CMPLX
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_logical_new"); var_type = V_LOG
    new = .true.
    pn_var_subspec => parse_node_get_sub_ptr (pn_var_spec, 2)
    pn_var_name => parse_node_get_sub_ptr (pn_var_subspec, 2)
  case ("var_logical_spec"); var_type = V_LOG
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_plist_new"); var_type = V_SEV
    new = .true.
    pn_var_subspec => parse_node_get_sub_ptr (pn_var_spec, 2)
    pn_var_name => parse_node_get_sub_ptr (pn_var_subspec, 2)
  case ("var_plist_spec"); var_type = V_SEV
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_alias");    var_type = V_PDG
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_string_new"); var_type = V_STR
    new = .true.
    pn_var_subspec => parse_node_get_sub_ptr (pn_var_spec, 2)
    pn_var_name => parse_node_get_sub_ptr (pn_var_subspec, 2)
  case ("var_string_spec"); var_type = V_STR
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)

```

```

case default
    call parse_node_mismatch &
        ("logical|int|real|plist|alias", pn_var_type)
end select
pn_var_expr => parse_node_get_next_ptr (pn_var_name, 2)
pn_expr => parse_node_get_next_ptr (pn_var_spec, 2)
var_name = parse_node_get_string (pn_var_name)
select case (var_type)
case (V_LOG); var_name = "?" // var_name
case (V_SEV); var_name = "@" // var_name
case (V_STR); var_name = "$" // var_name      ! $ sign
end select
call var_list_check_user_var (var_list, var_name, var_type, new)
call eval_node_compile_genexpr (en1, pn_var_expr, var_list, var_type)
call insert_conversion_node (en1, var_type)
allocate (en)
call eval_node_init_block (en, var_name, var_type, en1, var_list)
call eval_node_compile_genexpr (en2, pn_expr, en%var_list, result_type)
call eval_node_set_expr (en, en2)
if (debug) then
    call eval_node_write (en)
    print *, "done block expr"
end if
end subroutine eval_node_compile_block_expr

```

Insert a conversion node for integer/real/complex transformation if necessary.
 What shall we do for the complex to integer/real conversion?

(Eval trees: procedures)+≡

```

subroutine insert_conversion_node (en, result_type)
    type(eval_node_t), pointer :: en
    integer, intent(in) :: result_type
    type(eval_node_t), pointer :: en_conv
    select case (en%result_type)
    case (V_INT)
        select case (result_type)
        case (V_REAL)
            allocate (en_conv)
            call eval_node_init_branch (en_conv, var_str ("real"), V_REAL, en)
            call eval_node_set_op1_real (en_conv, real_i)
            en => en_conv
        case (V_CMPLX)
            allocate (en_conv)
            call eval_node_init_branch (en_conv, var_str ("complex"), V_CMPLX, en)
            call eval_node_set_op1_cmplx (en_conv, cmplx_i)
            en => en_conv
        end select
    case (V_REAL)
        select case (result_type)
        case (V_INT)
            allocate (en_conv)
            call eval_node_init_branch (en_conv, var_str ("int"), V_INT, en)
            call eval_node_set_op1_int (en_conv, int_r)
            en => en_conv

```

```

        case (V_CMPLX)
            allocate (en_conv)
            call eval_node_init_branch (en_conv, var_str ("complex"), V_CMPLX, en)
            call eval_node_set_op1_cmplx (en_conv, cmplx_r)
            en => en_conv
        end select
    case (V_CMPLX)
        select case (result_type)
            case (V_INT)
                allocate (en_conv)
                call eval_node_init_branch (en_conv, var_str ("int"), V_INT, en)
                call eval_node_set_op1_int (en_conv, int_c)
                en => en_conv
            case (V_REAL)
                allocate (en_conv)
                call eval_node_init_branch (en_conv, var_str ("real"), V_REAL, en)
                call eval_node_set_op1_real (en_conv, real_c)
                en => en_conv
            end select
        case default
            end select
    end subroutine insert_conversion_node

```

Conditionals

A conditional has the structure `if lexpr then expr else expr`. So we first evaluate the logical expression, then depending on the result the first or second expression. Note that the second expression is mandatory.

The `result_type`, if present, defines the requested type of the `then` and `else` clauses. Default is numeric (int/real). If there is a mismatch between real and integer result types, insert conversion nodes.

(Eval trees: procedures) +=

```

recursive subroutine eval_node_compile_conditional &
    (en, pn, var_list, result_type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in), optional :: result_type
    type(parse_node_t), pointer :: pn_condition, pn_expr
    type(parse_node_t), pointer :: pn_maybe_elseif, pn_elseif_branch
    type(parse_node_t), pointer :: pn_maybe_else, pn_else_branch, pn_else_expr
    type(eval_node_t), pointer :: en0, en1, en2
    integer :: restype
    if (debug) then
        print *, "read conditional"; call parse_node_write (pn)
    end if
    pn_condition => parse_node_get_sub_ptr (pn, 2, tag="lexpr")
    pn_expr => parse_node_get_next_ptr (pn_condition, 2)
    call eval_node_compile_lexpr (en0, pn_condition, var_list)
    call eval_node_compile_genexpr (en1, pn_expr, var_list, result_type)
    if (present (result_type)) then
        restype = major_result_type (result_type, en1%result_type)
    end if

```



```

else
    restype = en1%result_type
end if
pn_maybe_elseif => parse_node_get_next_ptr (pn_expr)
select case (char (parse_node_get_rule_key (pn_maybe_elseif)))
case ("maybe_elseif_expr", &
      "maybe_elseif_lexpr", &
      "maybe_elseif_pexpr", &
      "maybe_elseif_cexpr", &
      "maybe_elseif_sexpr")
    pn_elseif_branch => parse_node_get_sub_ptr (pn_maybe_elseif)
    pn_maybe_else => parse_node_get_next_ptr (pn_maybe_elseif)
    select case (char (parse_node_get_rule_key (pn_maybe_else)))
    case ("maybe_else_expr", &
          "maybe_else_lexpr", &
          "maybe_else_pexpr", &
          "maybe_else_cexpr", &
          "maybe_else_sexpr")
        pn_else_branch => parse_node_get_sub_ptr (pn_maybe_else)
        pn_else_expr => parse_node_get_sub_ptr (pn_else_branch, 2)
    case default
        pn_else_expr => null ()
    end select
    call eval_node_compile_elseif &
        (en2, pn_elseif_branch, pn_else_expr, var_list, restype)
case ("maybe_else_expr", &
      "maybe_else_lexpr", &
      "maybe_else_pexpr", &
      "maybe_else_cexpr", &
      "maybe_else_sexpr")
    pn_maybe_else => pn_maybe_elseif
    pn_maybe_elseif => null ()
    pn_else_branch => parse_node_get_sub_ptr (pn_maybe_else)
    pn_else_expr => parse_node_get_sub_ptr (pn_else_branch, 2)
    call eval_node_compile_genexpr &
        (en2, pn_else_expr, var_list, restype)
case ("endif")
    call eval_node_compile_default_else (en2, restype)
case default
    call msg_bug ("Broken conditional: unexpected " &
                 // char (parse_node_get_rule_key (pn_maybe_elseif)))
end select
call eval_node_create_conditional (en, en0, en1, en2, restype)
call conditional_insert_conversion_nodes (en, restype)
if (debug) then
    call eval_node_write (en)
    print *, "done conditional"
end if
end subroutine eval_node_compile_conditional

```

This recursively generates 'elseif' conditionals as a chain of sub-nodes of the main conditional.

<Eval trees: procedures>+≡

```

recursive subroutine eval_node_compile_elseif &
    (en, pn, pn_elseif_expr, var_list, result_type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(parse_node_t), pointer :: pn_elseif_expr
    type(var_list_t), intent(in), target :: var_list
    integer, intent(inout) :: result_type
    type(parse_node_t), pointer :: pn_next, pn_condition, pn_expr
    type(eval_node_t), pointer :: en0, en1, en2
    pn_condition => parse_node_get_sub_ptr (pn, 2, tag="lexpr")
    pn_expr => parse_node_get_next_ptr (pn_condition, 2)
    call eval_node_compile_lexpr (en0, pn_condition, var_list)
    call eval_node_compile_genexpr (en1, pn_expr, var_list, result_type)
    result_type = major_result_type (result_type, en1%result_type)
    pn_next => parse_node_get_next_ptr (pn)
    if (associated (pn_next)) then
        call eval_node_compile_elseif &
            (en2, pn_next, pn_elseif_expr, var_list, result_type)
        result_type = major_result_type (result_type, en2%result_type)
    else if (associated (pn_elseif_expr)) then
        call eval_node_compile_genexpr &
            (en2, pn_elseif_expr, var_list, result_type)
        result_type = major_result_type (result_type, en2%result_type)
    else
        call eval_node_compile_default_else (en2, result_type)
    end if
    call eval_node_create_conditional (en, en0, en1, en2, result_type)
end subroutine eval_node_compile_elseif

```

This makes a default 'else' branch in case it was omitted. The default value just depends on the expected type.

(*Eval trees: procedures*)+≡

```

subroutine eval_node_compile_default_else (en, result_type)
    type(eval_node_t), pointer :: en
    integer, intent(in) :: result_type
    type(subvt_t) :: pval_empty
    type(pdg_array_t) :: aval_undefined
    allocate (en)
    select case (result_type)
    case (V_LOG); call eval_node_init_log (en, .false.)
    case (V_INT); call eval_node_init_int (en, 0)
    case (V_REAL); call eval_node_init_real (en, 0._default)
    case (V_CMPLX)
        call eval_node_init_cmplx (en, (0._default, 0._default))
    case (V_SEV)
        call subvt_init (pval_empty)
        call eval_node_init_subvt (en, pval_empty)
    case (V_PDG)
        call eval_node_init_pdg_array (en, aval_undefined)
    case (V_STR)
        call eval_node_init_string (en, var_str (""))
    case default
        call msg_bug ("Undefined type for 'else' branch in conditional")
    end select
end subroutine eval_node_compile_default_else

```

```

end select
end subroutine eval_node_compile_default_else

```

If the logical expression is constant, we can simplify the conditional node by replacing it with the selected branch. Otherwise, we initialize a true branching.

(Eval trees: procedures)+≡

```

subroutine eval_node_create_conditional (en, en0, en1, en2, result_type)
  type(eval_node_t), pointer :: en, en0, en1, en2
  integer, intent(in) :: result_type
  if (en0%type == EN_CONSTANT) then
    if (en0%lval) then
      en => en1
      call eval_node_final_rec (en2)
      deallocate (en2)
    else
      en => en2
      call eval_node_final_rec (en1)
      deallocate (en1)
    end if
  else
    allocate (en)
    call eval_node_init_conditional (en, result_type, en0, en1, en2)
  end if
end subroutine eval_node_create_conditional

```

Return the numerical result type which should be used for the combination of the two result types.

(Eval trees: procedures)+≡

```

function major_result_type (t1, t2) result (t)
  integer :: t
  integer, intent(in) :: t1, t2
  select case (t1)
  case (V_INT)
    select case (t2)
    case (V_INT, V_REAL, V_CMPLX)
      t = t2
    case default
      call type_mismatch ()
    end select
  case (V_REAL)
    select case (t2)
    case (V_INT)
      t = t1
    case (V_REAL, V_CMPLX)
      t = t2
    case default
      call type_mismatch ()
    end select
  case (V_CMPLX)
    select case (t2)
    case (V_INT, V_REAL, V_CMPLX)
      t = t1
    case default

```

```

        call type_mismatch ()
    end select
case default
    if (t1 == t2) then
        t = t1
    else
        call type_mismatch ()
    end if
end select
contains
    subroutine type_mismatch ()
        call msg_bug ("Type mismatch in branches of a conditional expression")
    end subroutine type_mismatch
end function major_result_type

```

Recursively insert conversion nodes where necessary.

```

<Eval trees: procedures>+≡
recursive subroutine conditional_insert_conversion_nodes (en, result_type)
    type(eval_node_t), intent(inout), target :: en
    integer, intent(in) :: result_type
    select case (result_type)
    case (V_INT, V_REAL, V_CMPLX)
        call insert_conversion_node (en%arg1, result_type)
        if (en%arg2%type == EN_CONDITIONAL) then
            call conditional_insert_conversion_nodes (en%arg2, result_type)
        else
            call insert_conversion_node (en%arg2, result_type)
        end if
    end select
end subroutine conditional_insert_conversion_nodes

```

Logical expressions

A logical expression consists of one or more singlet logical expressions concatenated by ;. This is for allowing side-effects, only the last value is used.

```

<Eval trees: procedures>+≡
recursive subroutine eval_node_compile_lexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_term, pn_sequel, pn_arg
    type(eval_node_t), pointer :: en1, en2
    if (debug) then
        print *, "read lexpr"; call parse_node_write (pn)
    end if
    pn_term => parse_node_get_sub_ptr (pn, tag="lsinglet")
    call eval_node_compile_lsinglet (en, pn_term, var_list)
    pn_sequel => parse_node_get_next_ptr (pn_term, tag="lsequel")
    do while (associated (pn_sequel))
        pn_arg => parse_node_get_sub_ptr (pn_sequel, 2, tag="lsinglet")
        en1 => en
        call eval_node_compile_lsinglet (en2, pn_arg, var_list)
    end do
end subroutine eval_node_compile_lexpr

```

```

allocate (en)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
  call eval_node_init_log (en, ignore_first_ll (en1, en2))
  call eval_node_final_rec (en1)
  call eval_node_final_rec (en2)
  deallocate (en1, en2)
else
  call eval_node_init_branch &
    (en, var_str ("lsequel"), V_LOG, en1, en2)
  call eval_node_set_op2_log (en, ignore_first_ll)
end if
pn_sequel => parse_node_get_next_ptr (pn_sequel)
end do
if (debug) then
  call eval_node_write (en)
  print *, "done lexpr"
end if
end subroutine eval_node_compile_lexpr

```

A logical singlet expression consists of one or more logical terms concatenated by or.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_lsinglet (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_term, pn_alternative, pn_arg
  type(eval_node_t), pointer :: en1, en2
  if (debug) then
    print *, "read lsinglet"; call parse_node_write (pn)
  end if
  pn_term => parse_node_get_sub_ptr (pn, tag="lterm")
  call eval_node_compile_lterm (en, pn_term, var_list)
  pn_alternative => parse_node_get_next_ptr (pn_term, tag="alternative")
  do while (associated (pn_alternative))
    pn_arg => parse_node_get_sub_ptr (pn_alternative, 2, tag="lterm")
    en1 => en
    call eval_node_compile_lterm (en2, pn_arg, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
      call eval_node_init_log (en, or_ll (en1, en2))
      call eval_node_final_rec (en1)
      call eval_node_final_rec (en2)
      deallocate (en1, en2)
    else
      call eval_node_init_branch &
        (en, var_str ("alternative"), V_LOG, en1, en2)
      call eval_node_set_op2_log (en, or_ll)
    end if
    pn_alternative => parse_node_get_next_ptr (pn_alternative)
  end do
  if (debug) then
    call eval_node_write (en)
  end if
end subroutine eval_node_compile_lsinglet

```

```

        print *, "done lsinglet"
    end if
end subroutine eval_node_compile_lsinglet

```

A logical term consists of one or more logical values concatenated by **and**.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_lterm (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_term, pn_coincidence, pn_arg
    type(eval_node_t), pointer :: en1, en2
    if (debug) then
        print *, "read lterm"; call parse_node_write (pn)
    end if
    pn_term => parse_node_get_sub_ptr (pn)
    call eval_node_compile_lvalue (en, pn_term, var_list)
    pn_coincidence => parse_node_get_next_ptr (pn_term, tag="coincidence")
    do while (associated (pn_coincidence))
        pn_arg => parse_node_get_sub_ptr (pn_coincidence, 2)
        en1 => en
        call eval_node_compile_lvalue (en2, pn_arg, var_list)
        allocate (en)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            call eval_node_init_log (en, and_ll (en1, en2))
            call eval_node_final_rec (en1)
            call eval_node_final_rec (en2)
            deallocate (en1, en2)
        else
            call eval_node_init_branch &
                (en, var_str ("coincidence"), V_LOG, en1, en2)
            call eval_node_set_op2_log (en, and_ll)
        end if
        pn_coincidence => parse_node_get_next_ptr (pn_coincidence)
    end do
    if (debug) then
        call eval_node_write (en)
        print *, "done lterm"
    end if
end subroutine eval_node_compile_lterm

```

Logical variables are disabled, because they are confused with the l.h.s. of compared expressions.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_lvalue (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    if (debug) then
        print *, "read lvalue"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("true")

```

```

        allocate (en)
        call eval_node_init_log (en, .true.)
case ("false")
    allocate (en)
    call eval_node_init_log (en, .false.)
case ("negation")
    call eval_node_compile_negation (en, pn, var_list)
case ("lvariable")
    call eval_node_compile_variable (en, pn, var_list, V_LOG)
case ("lexpr")
    call eval_node_compile_lexpr (en, pn, var_list)
case ("block_lexpr")
    call eval_node_compile_block_expr (en, pn, var_list, V_LOG)
case ("conditional_lexpr")
    call eval_node_compile_conditional (en, pn, var_list, V_LOG)
case ("compared_expr")
    call eval_node_compile_compared_expr (en, pn, var_list, V_REAL)
case ("compared_sexpr")
    call eval_node_compile_compared_expr (en, pn, var_list, V_STR)
case ("all_fun", "any_fun", "no_fun", "user_cut_fun")
    call eval_node_compile_log_function (en, pn, var_list)
case ("record_cmd")
    call eval_node_compile_record_cmd (en, pn, var_list)
case default
    call parse_node_mismatch &
        ("true|false|negation|lvariable|" // &
        "lexpr|block_lexpr|conditional_lexpr|" // &
        "compared_expr|compared_sexpr|logical_pexpr", pn)
end select
if (debug) then
    call eval_node_write (en)
    print *, "done lvalue"
end if
end subroutine eval_node_compile_lvalue

```

A negation consists of the keyword not and a logical value.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_negation (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_arg
    type(eval_node_t), pointer :: en1
    if (debug) then
        print *, "read negation"; call parse_node_write (pn)
    end if
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    call eval_node_compile_lvalue (en1, pn_arg, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT) then
        call eval_node_init_log (en, not_1 (en1))
        call eval_node_final_rec (en1)
        deallocate (en1)
    else

```

```

        call eval_node_init_branch (en, var_str ("not"), V_LOG, en1)
        call eval_node_set_op1_log (en, not_1)
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done negation"
    end if
end subroutine eval_node_compile_negation

```

Comparisons

Up to the loop, this is easy. There is always at least one comparison. This is evaluated, and the result is the logical node **en**. If it is constant, we keep its second sub-node as **en2**. (Thus, at the very end **en2** has to be deleted if **en** is (still) constant.)

If there is another comparison, we first check if the first comparison was constant. In that case, there are two possibilities: (i) it was true. Then, its right-hand side is compared with the new right-hand side, and the result replaces the previous one which is deleted. (ii) it was false. In this case, the result of the whole comparison is false, and we can exit the loop without evaluating anything else.

Now assume that the first comparison results in a valid branch, its second sub-node kept as **en2**. We first need a copy of this, which becomes the new left-hand side. If **en2** is constant, we make an identical constant node **en1**. Otherwise, we make **en1** an appropriate pointer node. Next, the first branch is saved as **en0** and we evaluate the comparison between **en1** and the a right-hand side. If this turns out to be constant, there are again two possibilities: (i) true, then we revert to the previous result. (ii) false, then the wh

<Eval trees: procedures>+≡

```

recursive subroutine eval_node_compile_compared_expr (en, pn, var_list, type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in) :: type
    type(parse_node_t), pointer :: pn_comparison, pn_expr1
    type(eval_node_t), pointer :: en0, en1, en2
    if (debug) then
        print *, "read comparison"; call parse_node_write (pn)
    end if
    select case (type)
    case (V_INT, V_REAL)
        pn_expr1 => parse_node_get_sub_ptr (pn, tag="expr")
        call eval_node_compile_expr (en1, pn_expr1, var_list)
        pn_comparison => parse_node_get_next_ptr (pn_expr1, tag="comparison")
    case (V_STR)
        pn_expr1 => parse_node_get_sub_ptr (pn, tag="sexpr")
        call eval_node_compile_sexpr (en1, pn_expr1, var_list)
        pn_comparison => parse_node_get_next_ptr (pn_expr1, tag="str_comparison")
    end select
    call eval_node_compile_comparison &
        (en, en1, en2, pn_comparison, var_list, type)

```



```

pn_comparision => parse_node_get_next_ptr (pn_comparision)
SCAN_FURTHER: do while (associated (pn_comparision))
  if (en%type == EN_CONSTANT) then
    if (en%lval) then
      en1 => en2
      call eval_node_final_rec (en); deallocate (en)
      call eval_node_compile_comparision &
        (en, en1, en2, pn_comparision, var_list, type)
    else
      exit SCAN_FURTHER
    end if
  else
    allocate (en1)
    if (en2%type == EN_CONSTANT) then
      select case (en2%result_type)
        case (V_INT); call eval_node_init_int      (en1, en2%ival)
        case (V_REAL); call eval_node_init_real    (en1, en2%rval)
        case (V_STR); call eval_node_init_string   (en1, en2%sval)
      end select
    else
      select case (en2%result_type)
        case (V_INT); call eval_node_init_int_ptr &
          (en1, var_str ("(previous)"), en2%ival, en2%value_is_known)
        case (V_REAL); call eval_node_init_real_ptr &
          (en1, var_str ("(previous)"), en2%rval, en2%value_is_known)
        case (V_STR); call eval_node_init_string_ptr &
          (en1, var_str ("(previous)"), en2%sval, en2%value_is_known)
      end select
    end if
    en0 => en
    call eval_node_compile_comparision &
      (en, en1, en2, pn_comparision, var_list, type)
    if (en%type == EN_CONSTANT) then
      if (en%lval) then
        call eval_node_final_rec (en); deallocate (en)
        en => en0
      else
        call eval_node_final_rec (en0); deallocate (en0)
        exit SCAN_FURTHER
      end if
    else
      en1 => en
      allocate (en)
      call eval_node_init_branch (en, var_str ("and"), V_LOG, en0, en1)
      call eval_node_set_op2_log (en, and_ll)
    end if
  end if
  pn_comparision => parse_node_get_next_ptr (pn_comparision)
end do SCAN_FURTHER
if (en%type == EN_CONSTANT .and. associated (en2)) then
  call eval_node_final_rec (en2); deallocate (en2)
end if
if (debug) then
  call eval_node_write (en)

```

```

        print *, "done compared_expr"
    end if
end subroutine eval_node_compile_compared_expr

```

This takes two extra arguments: **en1**, the left-hand-side of the comparison, is already allocated and evaluated. **en2** (the right-hand side) and **en** (the result) are allocated by the routine. **pn** is the parse node which contains the operator and the right-hand side as subnodes.

If the result of the comparison is constant, **en1** is deleted but **en2** is kept, because it may be used in a subsequent comparison. **en** then becomes a constant. If the result is variable, **en** becomes a branch node which refers to **en1** and **en2**.

(*Eval trees: procedures*)+≡

```

recursive subroutine eval_node_compile_comparison &
    (en, en1, en2, pn, var_list, type)
    type(eval_node_t), pointer :: en, en1, en2
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in) :: type
    type(parse_node_t), pointer :: pn_op, pn_arg
    type(string_t) :: key
    integer :: t1, t2
    real(default), pointer :: tolerance_ptr
    pn_op => parse_node_get_sub_ptr (pn)
    key = parse_node_get_key (pn_op)
    select case (type)
    case (V_INT, V_REAL)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="expr")
        call eval_node_compile_expr (en2, pn_arg, var_list)
    case (V_STR)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="sexpr")
        call eval_node_compile_sexpr (en2, pn_arg, var_list)
    end select
    t1 = en1%result_type
    t2 = en2%result_type
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
        call var_list%get_rptr (var_str ("tolerance"), tolerance_ptr)
        en1%tolerance => tolerance_ptr
        select case (char (key))
        case ("<")
            select case (t1)
            case (V_INT)
                select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_lt_ii (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_ll_ir (en1, en2))
                end select
            case (V_REAL)
                select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_ll_ri (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_ll_rr (en1, en2))
                end select
            end select
        case (">")

```

```

select case (t1)
case (V_INT)
  select case (t2)
    case (V_INT); call eval_node_init_log (en, comp_gt_ii (en1, en2))
    case (V_REAL); call eval_node_init_log (en, comp_gg_ir (en1, en2))
  end select
case (V_REAL)
  select case (t2)
    case (V_INT); call eval_node_init_log (en, comp_gg_ri (en1, en2))
    case (V_REAL); call eval_node_init_log (en, comp_gg_rr (en1, en2))
  end select
end select
case ("<=")
  select case (t1)
  case (V_INT)
    select case (t2)
      case (V_INT); call eval_node_init_log (en, comp_le_ii (en1, en2))
      case (V_REAL); call eval_node_init_log (en, comp_ls_ir (en1, en2))
    end select
  case (V_REAL)
    select case (t2)
      case (V_INT); call eval_node_init_log (en, comp_ls_ri (en1, en2))
      case (V_REAL); call eval_node_init_log (en, comp_ls_rr (en1, en2))
    end select
  end select
case (">=")
  select case (t1)
  case (V_INT)
    select case (t2)
      case (V_INT); call eval_node_init_log (en, comp_ge_ii (en1, en2))
      case (V_REAL); call eval_node_init_log (en, comp_gs_ir (en1, en2))
    end select
  case (V_REAL)
    select case (t2)
      case (V_INT); call eval_node_init_log (en, comp_gs_ri (en1, en2))
      case (V_REAL); call eval_node_init_log (en, comp_gs_rr (en1, en2))
    end select
  end select
case ("==")
  select case (t1)
  case (V_INT)
    select case (t2)
      case (V_INT); call eval_node_init_log (en, comp_eq_ii (en1, en2))
      case (V_REAL); call eval_node_init_log (en, comp_se_ir (en1, en2))
    end select
  case (V_REAL)
    select case (t2)
      case (V_INT); call eval_node_init_log (en, comp_se_ri (en1, en2))
      case (V_REAL); call eval_node_init_log (en, comp_se_rr (en1, en2))
    end select
  case (V_STR)
    select case (t2)
      case (V_STR); call eval_node_init_log (en, comp_eq_ss (en1, en2))
    end select

```

```

        end select
    case ("<>")
        select case (t1)
            case (V_INT)
                select case (t2)
                    case (V_INT); call eval_node_init_log (en, comp_ne_ii (en1, en2))
                    case (V_REAL); call eval_node_init_log (en, comp_ns_ir (en1, en2))
                end select
            case (V_REAL)
                select case (t2)
                    case (V_INT); call eval_node_init_log (en, comp_ns_ri (en1, en2))
                    case (V_REAL); call eval_node_init_log (en, comp_ns_rr (en1, en2))
                end select
            case (V_STR)
                select case (t2)
                    case (V_STR); call eval_node_init_log (en, comp_ne_ss (en1, en2))
                end select
            end select
        end select
        call eval_node_final_rec (en1)
        deallocate (en1)
    else
        call eval_node_init_branch (en, key, V_LOG, en1, en2)
        select case (char (key))
            case ("<")
                select case (t1)
                    case (V_INT)
                        select case (t2)
                            case (V_INT); call eval_node_set_op2_log (en, comp_lt_ii)
                            case (V_REAL); call eval_node_set_op2_log (en, comp_ll_ir)
                        end select
                    case (V_REAL)
                        select case (t2)
                            case (V_INT); call eval_node_set_op2_log (en, comp_ll_ri)
                            case (V_REAL); call eval_node_set_op2_log (en, comp_ll_rr)
                        end select
                    end select
            case (">")
                select case (t1)
                    case (V_INT)
                        select case (t2)
                            case (V_INT); call eval_node_set_op2_log (en, comp_gt_ii)
                            case (V_REAL); call eval_node_set_op2_log (en, comp_gg_ir)
                        end select
                    case (V_REAL)
                        select case (t2)
                            case (V_INT); call eval_node_set_op2_log (en, comp_gg_ri)
                            case (V_REAL); call eval_node_set_op2_log (en, comp_gg_rr)
                        end select
                    end select
            case ("<=")
                select case (t1)
                    case (V_INT)
                        select case (t2)

```

```

        case (V_INT); call eval_node_set_op2_log (en, comp_le_ii)
        case (V_REAL); call eval_node_set_op2_log (en, comp_ls_ir)
    end select
case (V_REAL)
    select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_ls_ri)
        case (V_REAL); call eval_node_set_op2_log (en, comp_ls_rr)
    end select
end select
case (">=")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_set_op2_log (en, comp_ge_ii)
                case (V_REAL); call eval_node_set_op2_log (en, comp_gs_ir)
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_set_op2_log (en, comp_gs_ri)
                case (V_REAL); call eval_node_set_op2_log (en, comp_gs_rr)
            end select
        end select
    case ("==")
        select case (t1)
            case (V_INT)
                select case (t2)
                    case (V_INT); call eval_node_set_op2_log (en, comp_eq_ii)
                    case (V_REAL); call eval_node_set_op2_log (en, comp_se_ir)
                end select
            case (V_REAL)
                select case (t2)
                    case (V_INT); call eval_node_set_op2_log (en, comp_se_ri)
                    case (V_REAL); call eval_node_set_op2_log (en, comp_se_rr)
                end select
            case (V_STR)
                select case (t2)
                    case (V_STR); call eval_node_set_op2_log (en, comp_eq_ss)
                end select
            end select
        case ("<>")
            select case (t1)
                case (V_INT)
                    select case (t2)
                        case (V_INT); call eval_node_set_op2_log (en, comp_ne_ii)
                        case (V_REAL); call eval_node_set_op2_log (en, comp_ns_ir)
                    end select
                case (V_REAL)
                    select case (t2)
                        case (V_INT); call eval_node_set_op2_log (en, comp_ns_ri)
                        case (V_REAL); call eval_node_set_op2_log (en, comp_ns_rr)
                    end select
                case (V_STR)
                    select case (t2)
                        case (V_STR); call eval_node_set_op2_log (en, comp_ne_ss)
                    end select
            end select
        end select
    end select
end select

```

```

        end select
    end select
end select
    call var_list%get_rptr (var_str ("tolerance"), tolerance_ptr)
    en1%tolerance => tolerance_ptr
end if
end subroutine eval_node_compile_comparison

```

Recording analysis data

The `record` command is actually a logical expression which always evaluates true.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_record_cmd (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_tag, pn_arg
    type(parse_node_t), pointer :: pn_arg1, pn_arg2, pn_arg3, pn_arg4
    type(eval_node_t), pointer :: en0, en1, en2, en3, en4
    real(default), pointer :: event_weight
    if (debug) then
        print *, "read record_cmd"; call parse_node_write (pn)
    end if
    pn_key => parse_node_get_sub_ptr (pn)
    pn_tag => parse_node_get_next_ptr (pn_key)
    pn_arg => parse_node_get_next_ptr (pn_tag)
    select case (char (parse_node_get_key (pn_key)))
    case ("record")
        call var_list%get_rptr (var_str ("event_weight"), event_weight)
    case ("record_unweighted")
        event_weight => null ()
    case ("record_excess")
        call var_list%get_rptr (var_str ("event_excess"), event_weight)
    end select
    select case (char (parse_node_get_rule_key (pn_tag)))
    case ("analysis_id")
        allocate (en0)
        call eval_node_init_string (en0, parse_node_get_string (pn_tag))
    case default
        call eval_node_compile_sexpr (en0, pn_tag, var_list)
    end select
    allocate (en)
    if (associated (pn_arg)) then
        pn_arg1 => parse_node_get_sub_ptr (pn_arg)
        call eval_node_compile_expr (en1, pn_arg1, var_list)
        if (en1%result_type == V_INT) &
            call insert_conversion_node (en1, V_REAL)
        pn_arg2 => parse_node_get_next_ptr (pn_arg1)
        if (associated (pn_arg2)) then
            call eval_node_compile_expr (en2, pn_arg2, var_list)
            if (en2%result_type == V_INT) &

```

```

        call insert_conversion_node (en2, V_REAL)
    pn_arg3 => parse_node_get_next_ptr (pn_arg2)
    if (associated (pn_arg3)) then
        call eval_node_compile_expr (en3, pn_arg3, var_list)
        if (en3%result_type == V_INT) &
            call insert_conversion_node (en3, V_REAL)
        pn_arg4 => parse_node_get_next_ptr (pn_arg3)
        if (associated (pn_arg4)) then
            call eval_node_compile_expr (en4, pn_arg4, var_list)
            if (en4%result_type == V_INT) &
                call insert_conversion_node (en4, V_REAL)
            call eval_node_init_record_cmd &
                (en, event_weight, en0, en1, en2, en3, en4)
        else
            call eval_node_init_record_cmd &
                (en, event_weight, en0, en1, en2, en3)
        end if
    else
        call eval_node_init_record_cmd (en, event_weight, en0, en1, en2)
    end if
else
    call eval_node_init_record_cmd (en, event_weight, en0, en1)
end if
else
    call eval_node_init_record_cmd (en, event_weight, en0)
end if
if (debug) then
    call eval_node_write (en)
    print *, "done record_cmd"
end if
end subroutine eval_node_compile_record_cmd

```

Particle-list expressions

A particle expression is a subevent or a concatenation of particle-list terms (using join).

(Eval trees: procedures) +≡

```

recursive subroutine eval_node_compile_pexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_pterm, pn_concatenation, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(subevt_t) :: subevt
    if (debug) then
        print *, "read pexpr"; call parse_node_write (pn)
    end if
    pn_pterm => parse_node_get_sub_ptr (pn)
    call eval_node_compile_pterm (en, pn_pterm, var_list)
    pn_concatenation => &
        parse_node_get_next_ptr (pn_pterm, tag="pconcatenation")
    do while (associated (pn_concatenation))

```

```

pn_op => parse_node_get_sub_ptr (pn_concatenation)
pn_arg => parse_node_get_next_ptr (pn_op)
en1 => en
call eval_node_compile_pterm (en2, pn_arg, var_list)
allocate (en)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
  call subevt_join (subevt, en1%pval, en2%pval)
  call eval_node_init_subevt (en, subevt)
  call eval_node_final_rec (en1)
  call eval_node_final_rec (en2)
  deallocate (en1, en2)
else
  call eval_node_init_branch &
    (en, var_str ("join"), V_SEV, en1, en2)
  call eval_node_set_op2_sev (en, join_pp)
end if
pn_concatenation => parse_node_get_next_ptr (pn_concatenation)
end do
if (debug) then
  call eval_node_write (en)
  print *, "done pexpr"
end if
end subroutine eval_node_compile_pexpr

```

A particle term is a subevent or a combination of particle-list values (using combine).

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_pterm (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_pvalue, pn_combination, pn_op, pn_arg
  type(eval_node_t), pointer :: en1, en2
  type(subevt_t) :: subevt
  if (debug) then
    print *, "read pterm"; call parse_node_write (pn)
  end if
  pn_pvalue => parse_node_get_sub_ptr (pn)
  call eval_node_compile_pvalue (en, pn_pvalue, var_list)
  pn_combination => &
    parse_node_get_next_ptr (pn_pvalue, tag="pcombination")
  do while (associated (pn_combination))
    pn_op => parse_node_get_sub_ptr (pn_combination)
    pn_arg => parse_node_get_next_ptr (pn_op)
    en1 => en
    call eval_node_compile_pvalue (en2, pn_arg, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
      call subevt_combine (subevt, en1%pval, en2%pval)
      call eval_node_init_subevt (en, subevt)
      call eval_node_final_rec (en1)
      call eval_node_final_rec (en2)
      deallocate (en1, en2)
    end if
  end do
end subroutine eval_node_compile_pterm

```



```

else
  call eval_node_init_branch &
    (en, var_str ("combine"), V_SEV, en1, en2)
  call eval_node_set_op2_sev (en, combine_pp)
end if
pn_combination => parse_node_get_next_ptr (pn_combination)
end do
if (debug) then
  call eval_node_write (en)
  print *, "done pterm"
end if
end subroutine eval_node_compile_pterm

```

A particle-list value is a PDG-code array, a particle identifier, a variable, a (grouped) pexpr, a block pexpr, a conditional, or a particle-list function.

The `cexpr` node is responsible for transforming a constant PDG-code array into a subevent. It takes the code array as its first argument, the event subevent as its second argument, and the requested particle type (incoming/outgoing) as its zero-th argument. The result is the list of particles in the event that match the code array.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_pvalue (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_prefix_cexpr
  type(eval_node_t), pointer :: en1, en2, en0
  type(string_t) :: key
  type(subevt_t), pointer :: evt_ptr
  logical, pointer :: known
  if (debug) then
    print *, "read pvalue"; call parse_node_write (pn)
  end if
  select case (char (parse_node_get_rule_key (pn)))
  case ("pexpr_src")
    call eval_node_compile_prefix_cexpr (en1, pn, var_list)
    allocate (en2)
    if (var_list%contains (var_str ("@evt"))) then
      call var_list%get_pptr (var_str ("@evt"), evt_ptr, known)
      call eval_node_init_subevt_ptr (en2, var_str ("@evt"), evt_ptr, known)
      allocate (en)
      call eval_node_init_branch &
        (en, var_str ("prt_selection"), V_SEV, en1, en2)
      call eval_node_set_op2_sev (en, select_pdg_ca)
      allocate (en0)
      pn_prefix_cexpr => parse_node_get_sub_ptr (pn)
      key = parse_node_get_rule_key (pn_prefix_cexpr)
      select case (char (key))
      case ("incoming_prt")
        call eval_node_init_int (en0, PRT_INCOMING)
        en%arg0 => en0
      case ("outgoing_prt")
        call eval_node_init_int (en0, PRT_OUTGOING)

```

```

        en%arg0 => en0
    end select
else
    call parse_node_write (pn)
    call msg_bug (" Missing event data while compiling pvalue")
end if
case ("pvariable")
    call eval_node_compile_variable (en, pn, var_list, V_SEV)
case ("pexpr")
    call eval_node_compile_pexpr (en, pn, var_list)
case ("block_pexpr")
    call eval_node_compile_block_expr (en, pn, var_list, V_SEV)
case ("conditional_pexpr")
    call eval_node_compile_conditional (en, pn, var_list, V_SEV)
case ("join_fun", "combine_fun", "collect_fun", "cluster_fun", &
    "select_fun", "extract_fun", "sort_fun")
    call eval_node_compile_prt_function (en, pn, var_list)
case default
    call parse_node_mismatch &
        ("prefix_cexpr|pvariable|" // &
        "grouped_pexpr|block_pexpr|conditional_pexpr|" // &
        "prt_function", pn)
end select
if (debug) then
    call eval_node_write (en)
    print *, "done pvalue"
end if
end subroutine eval_node_compile_pvalue

```

Particle functions

This combines the treatment of 'join', 'combine', 'collect', 'cluster', 'select', and 'extract' which all have the same syntax. The one or two argument nodes are allocated. If there is a condition, the condition node is also allocated as a logical expression, for which the variable list is augmented by the appropriate (unary/binary) observables.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_prt_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_clause, pn_key, pn_cond, pn_args
    type(parse_node_t), pointer :: pn_arg0, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2
    type(string_t) :: key
    if (debug) then
        print *, "read prt_function"; call parse_node_write (pn)
    end if
    pn_clause => parse_node_get_sub_ptr (pn)
    pn_key => parse_node_get_sub_ptr (pn_clause)
    pn_cond => parse_node_get_next_ptr (pn_key)
    if (associated (pn_cond)) &

```

```

        pn_arg0 => parse_node_get_sub_ptr (pn_cond, 2)
pn_args => parse_node_get_next_ptr (pn_clause)
pn_arg1 => parse_node_get_sub_ptr (pn_args)
pn_arg2 => parse_node_get_next_ptr (pn_arg1)
key = parse_node_get_key (pn_key)
call eval_node_compile_pexpr (en1, pn_arg1, var_list)
allocate (en)
if (.not. associated (pn_arg2)) then
    select case (char (key))
    case ("collect")
        call eval_node_init_prt_fun_unary (en, en1, key, collect_p)
    case ("cluster")
        if (fastjet_available ()) then
            call fastjet_init ()
        else
            call msg_fatal &
                (''cluster' function requires FastJet, which is not enabled')
        end if
        call eval_node_init_prt_fun_unary (en, en1, key, cluster_p)
        call var_list%get_iptr (var_str ("jet_algorithm"), en1%jet_algorithm)
        call var_list%get_rptr (var_str ("jet_r"), en1%jet_r)
    case ("select")
        call eval_node_init_prt_fun_unary (en, en1, key, select_p)
    case ("extract")
        call eval_node_init_prt_fun_unary (en, en1, key, extract_p)
    case ("sort")
        call eval_node_init_prt_fun_unary (en, en1, key, sort_p)
    case default
        call msg_bug (" Unary particle function '" // char (key) // &
            "' undefined")
    end select
else
    call eval_node_compile_pexpr (en2, pn_arg2, var_list)
    select case (char (key))
    case ("join")
        call eval_node_init_prt_fun_binary (en, en1, en2, key, join_pp)
    case ("combine")
        call eval_node_init_prt_fun_binary (en, en1, en2, key, combine_pp)
    case ("collect")
        call eval_node_init_prt_fun_binary (en, en1, en2, key, collect_pp)
    case ("select")
        call eval_node_init_prt_fun_binary (en, en1, en2, key, select_pp)
    case ("sort")
        call eval_node_init_prt_fun_binary (en, en1, en2, key, sort_pp)
    case default
        call msg_bug (" Binary particle function '" // char (key) // &
            "' undefined")
    end select
end if
if (associated (pn_cond)) then
    call eval_node_set_observables (en, var_list)
    select case (char (key))
    case ("extract", "sort")
        call eval_node_compile_expr (en0, pn_arg0, en%var_list)

```

```

        case default
            call eval_node_compile_lexpr (en0, pn_arg0, en%var_list)
        end select
        en%arg0 => en0
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done prt_function"
    end if
end subroutine eval_node_compile_prt_function

```

The `eval` expression is similar, but here the expression `arg0` is mandatory, and the whole thing evaluates to a numeric value.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_eval_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_arg0, pn_args, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2
    type(string_t) :: key
    if (debug) then
        print *, "read eval_function"; call parse_node_write (pn)
    end if
    pn_key => parse_node_get_sub_ptr (pn)
    pn_arg0 => parse_node_get_next_ptr (pn_key)
    pn_args => parse_node_get_next_ptr (pn_arg0)
    pn_arg1 => parse_node_get_sub_ptr (pn_args)
    pn_arg2 => parse_node_get_next_ptr (pn_arg1)
    key = parse_node_get_key (pn_key)
    call eval_node_compile_pexpr (en1, pn_arg1, var_list)
    allocate (en)
    if (.not. associated (pn_arg2)) then
        call eval_node_init_eval_fun_unary (en, en1, key)
    else
        call eval_node_compile_pexpr (en2, pn_arg2, var_list)
        call eval_node_init_eval_fun_binary (en, en1, en2, key)
    end if
    call eval_node_set_observables (en, var_list)
    call eval_node_compile_expr (en0, pn_arg0, en%var_list)
    if (en0%result_type /= V_REAL) &
        call msg_fatal (" 'eval' function does not result in real value")
    call eval_node_set_expr (en, en0)
    if (debug) then
        call eval_node_write (en)
        print *, "done eval_function"
    end if
end subroutine eval_node_compile_eval_function

```

Logical functions of subevents.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_log_function (en, pn, var_list)
    type(eval_node_t), pointer :: en

```

```

type(parse_node_t), intent(in) :: pn
type(var_list_t), intent(in), target :: var_list
type(parse_node_t), pointer :: pn_key, pn_str
type(parse_node_t), pointer :: pn_arg0, pn_args, pn_arg1, pn_arg2
type(eval_node_t), pointer :: en0, en1, en2
type(string_t) :: key
if (debug) then
    print *, "read log_function"; call parse_node_write (pn)
end if
select case (char (parse_node_get_rule_key (pn)))
case ("all_fun", "any_fun", "no_fun")
    pn_key => parse_node_get_sub_ptr (pn)
    pn_arg0 => parse_node_get_next_ptr (pn_key)
    pn_args => parse_node_get_next_ptr (pn_arg0)
case ("user_cut_fun")
    pn_key => parse_node_get_sub_ptr (pn)
    pn_str => parse_node_get_next_ptr (pn_key)
    pn_arg0 => parse_node_get_sub_ptr (pn_str)
    pn_args => parse_node_get_next_ptr (pn_str)
case default
    call parse_node_mismatch &
        ("all_fun|any_fun|no_fun|user_cut_fun", &
        pn)
end select
pn_arg1 => parse_node_get_sub_ptr (pn_args)
pn_arg2 => parse_node_get_next_ptr (pn_arg1)
key = parse_node_get_key (pn_key)
call eval_node_compile_pexpr (en1, pn_arg1, var_list)
allocate (en)
if (.not. associated (pn_arg2)) then
    select case (char (key))
    case ("all")
        call eval_node_init_log_fun_unary (en, en1, key, all_p)
    case ("any")
        call eval_node_init_log_fun_unary (en, en1, key, any_p)
    case ("no")
        call eval_node_init_log_fun_unary (en, en1, key, no_p)
    case ("user_cut")
        call eval_node_init_log_fun_unary (en, en1, key, user_cut_p)
    case default
        call msg_bug ("Unary logical particle function '" // char (key) // &
            "' undefined")
    end select
else
    call eval_node_compile_pexpr (en2, pn_arg2, var_list)
    select case (char (key))
    case ("all")
        call eval_node_init_log_fun_binary (en, en1, en2, key, all_pp)
    case ("any")
        call eval_node_init_log_fun_binary (en, en1, en2, key, any_pp)
    case ("no")
        call eval_node_init_log_fun_binary (en, en1, en2, key, no_pp)
    case default
        call msg_bug ("Binary logical particle function '" // char (key) // &

```

```

        "' undefined")
    end select
end if
if (associated (pn_arg0)) then
    call eval_node_set_observables (en, var_list)
    select case (char (key))
    case ("all", "any", "no")
        call eval_node_compile_lexpr (en0, pn_arg0, en%var_list)
    case ("user_cut")
        call eval_node_compile_sexpr (en0, pn_arg0, en%var_list)
    case default
        call msg_bug ("Compiling logical particle function: missing mode")
    end select
    call eval_node_set_expr (en, en0, V_LOG)
end if
if (debug) then
    call eval_node_write (en)
    print *, "done log_function"
end if
end subroutine eval_node_compile_log_function

```

Numeric functions of subevents.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_numeric_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_clause, pn_key, pn_cond, pn_args
    type(parse_node_t), pointer :: pn_arg0, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2
    type(string_t) :: key
    if (debug) then
        print *, "read numeric_function"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("count_fun")
        pn_clause => parse_node_get_sub_ptr (pn)
        pn_key => parse_node_get_sub_ptr (pn_clause)
        pn_cond => parse_node_get_next_ptr (pn_key)
        if (associated (pn_cond)) then
            pn_arg0 => parse_node_get_sub_ptr (pn_cond, 2)
        else
            pn_arg0 => null ()
        end if
        pn_args => parse_node_get_next_ptr (pn_clause)
    case ("user_event_fun")
        pn_key => parse_node_get_sub_ptr (pn)
        pn_cond => parse_node_get_next_ptr (pn_key)
        pn_arg0 => parse_node_get_sub_ptr (pn_cond)
        pn_args => parse_node_get_next_ptr (pn_cond)
    end select
    pn_arg1 => parse_node_get_sub_ptr (pn_args)
    pn_arg2 => parse_node_get_next_ptr (pn_arg1)
    key = parse_node_get_key (pn_key)

```

```

call eval_node_compile_pexpr (en1, pn_arg1, var_list)
allocate (en)
if (.not. associated (pn_arg2)) then
  select case (char (key))
    case ("count")
      call eval_node_init_int_fun_unary (en, en1, key, count_a)
    case ("user_event_shape")
      call eval_node_init_real_fun_unary (en, en1, key, user_event_shape_a)
    case default
      call msg_bug ("Unary subevent function '" // char (key) // &
        "' undefined")
  end select
else
  call eval_node_compile_pexpr (en2, pn_arg2, var_list)
  select case (char (key))
    case ("count")
      call eval_node_init_int_fun_binary (en, en1, en2, key, count_pp)
    case default
      call msg_bug ("Binary subevent function '" // char (key) // &
        "' undefined")
  end select
end if
if (associated (pn_arg0)) then
  call eval_node_set_observables (en, var_list)
  select case (char (key))
    case ("count")
      call eval_node_compile_lexpr (en0, pn_arg0, en%var_list)
      call eval_node_set_expr (en, en0, V_INT)
    case ("user_event_shape")
      call eval_node_compile_sexpr (en0, pn_arg0, en%var_list)
      call eval_node_set_expr (en, en0, V_REAL)
  end select
end if
if (debug) then
  call eval_node_write (en)
  print *, "done numeric_function"
end if
end subroutine eval_node_compile_numeric_function

```

PDG-code arrays

A PDG-code expression is either prefixed by incoming or outgoing, a block, or a conditional. In any case, it evaluates to a constant.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_prefix_cexpr (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_avalue, pn_prt
  type(string_t) :: key
  if (debug) then
    print *, "read prefix_cexpr"; call parse_node_write (pn)

```

```

end if
pn_avalue => parse_node_get_sub_ptr (pn)
key = parse_node_get_rule_key (pn_avalue)
select case (char (key))
case ("incoming_prt")
    pn_prt => parse_node_get_sub_ptr (pn_avalue, 2)
    call eval_node_compile_cexpr (en, pn_prt, var_list)
case ("outgoing_prt")
    pn_prt => parse_node_get_sub_ptr (pn_avalue, 1)
    call eval_node_compile_cexpr (en, pn_prt, var_list)
case default
    call parse_node_mismatch &
        ("incoming_prt|outgoing_prt", &
        pn_avalue)
end select
if (debug) then
    call eval_node_write (en)
    print *, "done prefix_cexpr"
end if
end subroutine eval_node_compile_prefix_cexpr

```

A PDG array is a string of PDG code definitions (or aliases), concatenated by '.'. The code definitions may be variables which are not defined at compile time, so we have to allocate sub-nodes. This analogous to `eval_node_compile_term`.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_cexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_prt, pn_concatenation
    type(eval_node_t), pointer :: en1, en2
    type(pdg_array_t) :: aval
    if (debug) then
        print *, "read cexpr"; call parse_node_write (pn)
    end if
    pn_prt => parse_node_get_sub_ptr (pn)
    call eval_node_compile_avalue (en, pn_prt, var_list)
    pn_concatenation => parse_node_get_next_ptr (pn_prt)
    do while (associated (pn_concatenation))
        pn_prt => parse_node_get_sub_ptr (pn_concatenation, 2)
        en1 => en
        call eval_node_compile_avalue (en2, pn_prt, var_list)
        allocate (en)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            call concat_cc (aval, en1, en2)
            call eval_node_init_pdg_array (en, aval)
            call eval_node_final_rec (en1)
            call eval_node_final_rec (en2)
            deallocate (en1, en2)
        else
            call eval_node_init_branch (en, var_str (":"), V_PDG, en1, en2)
            call eval_node_set_op2_pdg (en, concat_cc)
        end if
    end if
end if

```



```

        pn_concatenation => parse_node_get_next_ptr (pn_concatenation)
    end do
    if (debug) then
        call eval_node_write (en)
        print *, "done cexpr"
    end if
end subroutine eval_node_compile_cexpr

```

Compile a PDG-code type value. It may be either an integer expression or a variable of type PDG array, optionally quoted.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_avalue (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    if (debug) then
        print *, "read avalue"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("pdg_code")
        call eval_node_compile_pdg_code (en, pn, var_list)
    case ("cvariable", "variable", "prt_name")
        call eval_node_compile_cvariable (en, pn, var_list)
    case ("cexpr")
        call eval_node_compile_cexpr (en, pn, var_list)
    case ("block_cexpr")
        call eval_node_compile_block_expr (en, pn, var_list, V_PDG)
    case ("conditional_cexpr")
        call eval_node_compile_conditional (en, pn, var_list, V_PDG)
    case default
        call parse_node_mismatch &
            ("grouped_cexpr|block_cexpr|conditional_cexpr|" // &
             "pdg_code|cvariable|prt_name", pn)
    end select
    if (debug) then
        call eval_node_write (en)
        print *, "done avalue"
    end if
end subroutine eval_node_compile_avalue

```

Compile a PDG-code expression, which is the key PDG with an integer expression as argument. The procedure is analogous to `eval_node_compile_unary_function`.

(Eval trees: procedures)+≡

```

subroutine eval_node_compile_pdg_code (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_arg
    type(eval_node_t), pointer :: en1
    type(string_t) :: key
    type(pdg_array_t) :: aval
    integer :: t
    if (debug) then

```

```

        print *, "read PDG code"; call parse_node_write (pn)
    end if
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    call eval_node_compile_expr &
        (en1, parse_node_get_sub_ptr (pn_arg, tag="expr"), var_list)
    t = en1%result_type
    allocate (en)
    key = "PDG"
    if (en1%type == EN_CONSTANT) then
        select case (t)
            case (V_INT)
                call pdg_i (aval, en1)
                call eval_node_init_pdg_array (en, aval)
            case default; call eval_type_error (pn, char (key), t)
        end select
        call eval_node_final_rec (en1)
        deallocate (en1)
    else
        select case (t)
            case (V_INT); call eval_node_set_op1_pdg (en, pdg_i)
            case default; call eval_type_error (pn, char (key), t)
        end select
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done function"
    end if
end subroutine eval_node_compile_pdg_code

```

This is entirely analogous to `eval_node_compile_variable`. However, PDG-array variables occur in different contexts.

To avoid name clashes between PDG-array variables and ordinary variables, we prepend a character (*). This is not visible to the user.

(Eval trees: procedures)+≡

```

subroutine eval_node_compile_cvariable (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_name
    type(string_t) :: var_name
    type(pdg_array_t), pointer :: aptr
    type(pdg_array_t), target, save :: no_aval
    logical, pointer :: known
    logical, target, save :: unknown = .false.
    if (debug) then
        print *, "read cvariable"; call parse_node_write (pn)
    end if
    pn_name => pn
    var_name = parse_node_get_string (pn_name)
    allocate (en)
    if (var_list%contains (var_name)) then
        call var_list%get_aptr (var_name, aptr, known)
        call eval_node_init_pdg_array_ptr (en, var_name, aptr, known)
    end if
end subroutine eval_node_compile_cvariable

```

```

else
  call parse_node_write (pn)
  call msg_error ("This PDG-array variable is undefined at this point")
  call eval_node_init_pdg_array_ptr (en, var_name, no_aval, unknown)
end if
if (debug) then
  call eval_node_write (en)
  print *, "done cvariable"
end if
end subroutine eval_node_compile_cvariable

```

String expressions

A string expression is either a string value or a concatenation of string values.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_sexpr (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_svalue, pn_concatenation, pn_op, pn_arg
  type(eval_node_t), pointer :: en1, en2
  type(string_t) :: string
  if (debug) then
    print *, "read sexpr"; call parse_node_write (pn)
  end if
  pn_svalue => parse_node_get_sub_ptr (pn)
  call eval_node_compile_svalue (en, pn_svalue, var_list)
  pn_concatenation => &
    parse_node_get_next_ptr (pn_svalue, tag="str_concatenation")
  do while (associated (pn_concatenation))
    pn_op => parse_node_get_sub_ptr (pn_concatenation)
    pn_arg => parse_node_get_next_ptr (pn_op)
    en1 => en
    call eval_node_compile_svalue (en2, pn_arg, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
      call concat_ss (string, en1, en2)
      call eval_node_init_string (en, string)
      call eval_node_final_rec (en1)
      call eval_node_final_rec (en2)
      deallocate (en1, en2)
    else
      call eval_node_init_branch &
        (en, var_str ("concat"), V_STR, en1, en2)
      call eval_node_set_op2_str (en, concat_ss)
    end if
    pn_concatenation => parse_node_get_next_ptr (pn_concatenation)
  end do
  if (debug) then
    call eval_node_write (en)
    print *, "done sexpr"
  end if
end subroutine eval_node_compile_sexpr

```

A string value is a string literal, a variable, a (grouped) sexpr, a block sexpr, or a conditional.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_svalue (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  if (debug) then
    print *, "read svalue"; call parse_node_write (pn)
  end if
  select case (char (parse_node_get_rule_key (pn)))
  case ("svariable")
    call eval_node_compile_variable (en, pn, var_list, V_STR)
  case ("sexpr")
    call eval_node_compile_sexpr (en, pn, var_list)
  case ("block_sexpr")
    call eval_node_compile_block_expr (en, pn, var_list, V_STR)
  case ("conditional_sexpr")
    call eval_node_compile_conditional (en, pn, var_list, V_STR)
  case ("sprintf_fun")
    call eval_node_compile_sprintf (en, pn, var_list)
  case ("string_literal")
    allocate (en)
    call eval_node_init_string (en, parse_node_get_string (pn))
  case default
    call parse_node_mismatch &
      ("svariable|" // &
       "grouped_sexpr|block_sexpr|conditional_sexpr|" // &
       "string_function|string_literal", pn)
  end select
  if (debug) then
    call eval_node_write (en)
    print *, "done svalue"
  end if
end subroutine eval_node_compile_svalue

```

There is currently one string function, `sprintf`. For `sprintf`, the first argument (no brackets) is the format string, the optional arguments in brackets are the expressions or variables to be formatted.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_compile_sprintf (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_clause, pn_key, pn_args
  type(parse_node_t), pointer :: pn_arg0
  type(eval_node_t), pointer :: en0, en1
  integer :: n_args
  type(string_t) :: key
  if (debug) then
    print *, "read sprintf_fun"; call parse_node_write (pn)
  end if

```

```

pn_clause => parse_node_get_sub_ptr (pn)
pn_key => parse_node_get_sub_ptr (pn_clause)
pn_arg0 => parse_node_get_next_ptr (pn_key)
pn_args => parse_node_get_next_ptr (pn_clause)
call eval_node_compile_sexpr (en0, pn_arg0, var_list)
if (associated (pn_args)) then
    call eval_node_compile_sprintf_args (en1, pn_args, var_list, n_args)
else
    n_args = 0
    en1 => null ()
end if
allocate (en)
key = parse_node_get_key (pn_key)
call eval_node_init_format_string (en, en0, en1, key, n_args)
if (debug) then
    call eval_node_write (en)
    print *, "done sprintf_fun"
end if
end subroutine eval_node_compile_sprintf

```

(Eval trees: procedures)+≡

```

subroutine eval_node_compile_sprintf_args (en, pn, var_list, n_args)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(out) :: n_args
    type(parse_node_t), pointer :: pn_arg
    integer :: i
    type(eval_node_t), pointer :: en1, en2
    n_args = parse_node_get_n_sub (pn)
    en => null ()
    do i = n_args, 1, -1
        pn_arg => parse_node_get_sub_ptr (pn, i)
        select case (char (parse_node_get_rule_key (pn_arg)))
            case ("lvariable")
                call eval_node_compile_variable (en1, pn_arg, var_list, V_LOG)
            case ("svariable")
                call eval_node_compile_variable (en1, pn_arg, var_list, V_STR)
            case ("expr")
                call eval_node_compile_expr (en1, pn_arg, var_list)
            case default
                call parse_node_mismatch ("variable|svariable|lvariable|expr", pn_arg)
        end select
        if (associated (en)) then
            en2 => en
            allocate (en)
            call eval_node_init_branch &
                (en, var_str ("sprintf_arg"), V_NONE, en1, en2)
        else
            allocate (en)
            call eval_node_init_branch &
                (en, var_str ("sprintf_arg"), V_NONE, en1)
        end if
    end do
end do

```

```
end subroutine eval_node_compile_sprintf_args
```

Evaluation. We allocate the argument list and apply the Fortran wrapper for the `sprintf` function.

(Eval trees: procedures)+≡

```
subroutine evaluate_sprintf (string, n_args, en_fmt, en_arg)
  type(string_t), intent(out) :: string
  integer, intent(in) :: n_args
  type(eval_node_t), pointer :: en_fmt
  type(eval_node_t), intent(in), optional, target :: en_arg
  type(eval_node_t), pointer :: en_branch, en_var
  type(sprintf_arg_t), dimension(:), allocatable :: arg
  type(string_t) :: fmt
  logical :: autoformat
  integer :: i, j, sprintf_argc
  autoformat = .not. associated (en_fmt)
  if (autoformat) fmt = ""
  if (present (en_arg)) then
    sprintf_argc = 0
    en_branch => en_arg
    do i = 1, n_args
      select case (en_branch%arg1%result_type)
        case (V_CMPLX); sprintf_argc = sprintf_argc + 2
        case default ; sprintf_argc = sprintf_argc + 1
      end select
      en_branch => en_branch%arg2
    end do
    allocate (arg (sprintf_argc))
    j = 1
    en_branch => en_arg
    do i = 1, n_args
      en_var => en_branch%arg1
      select case (en_var%result_type)
        case (V_LOG)
          call sprintf_arg_init (arg(j), en_var%lval)
          if (autoformat) fmt = fmt // "%s "
        case (V_INT);
          call sprintf_arg_init (arg(j), en_var%ival)
          if (autoformat) fmt = fmt // "%i "
        case (V_REAL);
          call sprintf_arg_init (arg(j), en_var%rval)
          if (autoformat) fmt = fmt // "%g "
        case (V_STR)
          call sprintf_arg_init (arg(j), en_var%sval)
          if (autoformat) fmt = fmt // "%s "
        case (V_CMPLX)
          call sprintf_arg_init (arg(j), real (en_var%cval, default))
          j = j + 1
          call sprintf_arg_init (arg(j), aimag (en_var%cval))
          if (autoformat) fmt = fmt // "(%g + %g * I) "
        case default
          call eval_node_write (en_var)
          call msg_error ("sprintf is implemented " &
```

```

// "for logical, integer, real, and string values only")
end select
j = j + 1
en_branch => en_branch%arg2
end do
else
allocate (arg(0))
end if
if (autoformat) then
string = sprintf (trim (fmt), arg)
else
string = sprintf (en_fmt%sval, arg)
end if
end subroutine evaluate_sprintf

```

26.3.5 Auxiliary functions for the compiler

Issue an error that the current node could not be compiled because of type mismatch:

```

<Eval trees: procedures>+≡
subroutine eval_type_error (pn, string, t)
type(parse_node_t), intent(in) :: pn
character(*), intent(in) :: string
integer, intent(in) :: t
type(string_t) :: type
select case (t)
case (V_NONE); type = "(none)"
case (V_LOG); type = "'logical'"
case (V_INT); type = "'integer'"
case (V_REAL); type = "'real'"
case (V_CMPLX); type = "'complex'"
case default; type = "(unknown)"
end select
call parse_node_write (pn)
call msg_fatal (" The " // string // &
" operation is not defined for the given argument type " // &
char (type))
end subroutine eval_type_error

```

If two numerics are combined, the result is integer if both arguments are integer, if one is integer and the other real or both are real, than its argument is real, otherwise complex.

```

<Eval trees: procedures>+≡
function numeric_result_type (t1, t2) result (t)
integer, intent(in) :: t1, t2
integer :: t
if (t1 == V_INT .and. t2 == V_INT) then
t = V_INT
else if (t1 == V_INT .and. t2 == V_REAL) then
t = V_REAL
else if (t1 == V_REAL .and. t2 == V_INT) then
t = V_REAL

```

```

else if (t1 == V_REAL .and. t2 == V_REAL) then
    t = V_REAL
else
    t = V_CMPLX
end if
end function numeric_result_type

```

26.3.6 Evaluation

Evaluation is done recursively. For leaf nodes nothing is to be done.

Evaluating particle-list functions: First, we evaluate the particle lists. If a condition is present, we assign the particle pointers of the condition node to the allocated particle entries in the parent node, keeping in mind that the observables in the variable stack used for the evaluation of the condition also contain pointers to these entries. Then, the assigned procedure is evaluated, which sets the subevent in the parent node. If required, the procedure evaluates the condition node once for each (pair of) particles to determine the result.

(Eval trees: procedures)+≡

```

recursive subroutine eval_node_evaluate (en)
    type(eval_node_t), intent(inout) :: en
    logical :: exist
    select case (en%type)
    case (EN_UNARY)
        if (associated(en%arg1)) then
            call eval_node_evaluate(en%arg1)
            en%value_is_known = en%arg1%value_is_known
        else
            en%value_is_known = .false.
        end if
        if (en%value_is_known) then
            select case (en%result_type)
            case (V_LOG); en%lval = en% op1_log (en%arg1)
            case (V_INT); en%ival = en% op1_int (en%arg1)
            case (V_REAL); en%rval = en% op1_real (en%arg1)
            case (V_CMPLX); en%cval = en% op1_cmplx (en%arg1)
            case (V_PDG);
                call en% op1_pdg (en%aval, en%arg1)
            case (V_SEV)
                if (associated(en%arg0)) then
                    call en% op1_sev (en%pval, en%arg1, en%arg0)
                else
                    call en% op1_sev (en%pval, en%arg1)
                end if
            case (V_STR)
                call en% op1_str (en%sval, en%arg1)
            end select
        end if
    case (EN_BINARY)
        if (associated(en%arg1) .and. associated(en%arg2)) then
            call eval_node_evaluate(en%arg1)
            call eval_node_evaluate(en%arg2)
            en%value_is_known = &

```



```

        en%arg1%value_is_known .and. en%arg2%value_is_known
    else
        en%value_is_known = .false.
    end if
    if (en%value_is_known) then
        select case (en%result_type)
            case (V_LOG); en%lval = en% op2_log (en%arg1, en%arg2)
            case (V_INT); en%ival = en% op2_int (en%arg1, en%arg2)
            case (V_REAL); en%rval = en% op2_real (en%arg1, en%arg2)
            case (V_CMPLX); en%cval = en% op2_cmplx (en%arg1, en%arg2)
            case (V_PDG)
                call en% op2_pdg (en%aval, en%arg1, en%arg2)
            case (V_SEV)
                if (associated (en%arg0)) then
                    call en% op2_sev (en%pval, en%arg1, en%arg2, en%arg0)
                else
                    call en% op2_sev (en%pval, en%arg1, en%arg2)
                end if
            case (V_STR)
                call en% op2_str (en%sval, en%arg1, en%arg2)
        end select
    end if
case (EN_BLOCK)
    if (associated (en%arg1) .and. associated (en%arg0)) then
        call eval_node_evaluate (en%arg1)
        call eval_node_evaluate (en%arg0)
        en%value_is_known = en%arg0%value_is_known
    else
        en%value_is_known = .false.
    end if
    if (en%value_is_known) then
        select case (en%result_type)
            case (V_LOG); en%lval = en%arg0%lval
            case (V_INT); en%ival = en%arg0%ival
            case (V_REAL); en%rval = en%arg0%rval
            case (V_CMPLX); en%cval = en%arg0%cval
            case (V_PDG); en%aval = en%arg0%aval
            case (V_SEV); en%pval = en%arg0%pval
            case (V_STR); en%sval = en%arg0%sval
        end select
    end if
case (EN_CONDITIONAL)
    if (associated (en%arg0)) then
        call eval_node_evaluate (en%arg0)
        en%value_is_known = en%arg0%value_is_known
    else
        en%value_is_known = .false.
    end if
    if (en%arg0%value_is_known) then
        if (en%arg0%lval) then
            call eval_node_evaluate (en%arg1)
            en%value_is_known = en%arg1%value_is_known
            if (en%value_is_known) then
                select case (en%result_type)

```

```

        case (V_LOG); en%lval = en%arg1%lval
        case (V_INT); en%ival = en%arg1%ival
        case (V_REAL); en%rval = en%arg1%rval
        case (V_CMPLX); en%cval = en%arg1%cval
        case (V_PDG); en%aval = en%arg1%aval
        case (V_SEV); en%pval = en%arg1%pval
        case (V_STR); en%sval = en%arg1%sval
    end select
end if
else
    call eval_node_evaluate (en%arg2)
    en%value_is_known = en%arg2%value_is_known
    if (en%value_is_known) then
        select case (en%result_type)
            case (V_LOG); en%lval = en%arg2%lval
            case (V_INT); en%ival = en%arg2%ival
            case (V_REAL); en%rval = en%arg2%rval
            case (V_CMPLX); en%cval = en%arg2%cval
            case (V_PDG); en%aval = en%arg2%aval
            case (V_SEV); en%pval = en%arg2%pval
            case (V_STR); en%sval = en%arg2%sval
        end select
    end if
end if
end if
case (EN_RECORD_CMD)
    exist = .true.
    en%lval = .false.
    call eval_node_evaluate (en%arg0)
    if (en%arg0%value_is_known) then
        if (associated (en%arg1)) then
            call eval_node_evaluate (en%arg1)
            if (en%arg1%value_is_known) then
                if (associated (en%arg2)) then
                    call eval_node_evaluate (en%arg2)
                    if (en%arg2%value_is_known) then
                        if (associated (en%arg3)) then
                            call eval_node_evaluate (en%arg3)
                            if (en%arg3%value_is_known) then
                                if (associated (en%arg4)) then
                                    call eval_node_evaluate (en%arg4)
                                    if (en%arg4%value_is_known) then
                                        if (associated (en%rval)) then
                                            call analysis_record_data (en%arg0%sval, &
                                                en%arg1%rval, en%arg2%rval, &
                                                en%arg3%rval, en%arg4%rval, &
                                                weight=en%rval, exist=exist, &
                                                success=en%lval)
                                        else
                                            call analysis_record_data (en%arg0%sval, &
                                                en%arg1%rval, en%arg2%rval, &
                                                en%arg3%rval, en%arg4%rval, &
                                                exist=exist, success=en%lval)
                                        end if
                                    end if
                                end if
                            end if
                        end if
                    end if
                end if
            end if
        end if
    end if
end if

```

```

        end if
    else
        if (associated (en%rval)) then
            call analysis_record_data (en%arg0%sval, &
                en%arg1%rval, en%arg2%rval, &
                en%arg3%rval, &
                weight=en%rval, exist=exist, &
                success=en%lval)
        else
            call analysis_record_data (en%arg0%sval, &
                en%arg1%rval, en%arg2%rval, &
                en%arg3%rval, &
                exist=exist, success=en%lval)
        end if
    end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            weight=en%rval, exist=exist, &
            success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            exist=exist, success=en%lval)
    end if
end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, &
            weight=en%rval, exist=exist, success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, &
            exist=exist, success=en%lval)
    end if
end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, 1._default, &
            weight=en%rval, exist=exist, success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, 1._default, &
            exist=exist, success=en%lval)
    end if
end if
if (.not. exist) then
    call msg_error ("Analysis object '" // char (en%arg0%sval) &
        // "' is undefined")
    en%arg0%value_is_known = .false.

```

```

        end if
    end if
case (EN_OBS1_INT)
    en%ival = en% obs1_int (en%prt1)
    en%value_is_known = .true.
case (EN_OBS2_INT)
    en%ival = en% obs2_int (en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_OBS1_REAL)
    en%rval = en% obs1_real (en%prt1)
    en%value_is_known = .true.
case (EN_OBS2_REAL)
    en%rval = en% obs2_real (en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_UOBS1_INT)
    en%ival = user_obs_int_p (en%arg0, en%prt1)
    en%value_is_known = .true.
case (EN_UOBS2_INT)
    en%ival = user_obs_int_pp (en%arg0, en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_UOBS1_REAL)
    en%rval = user_obs_real_p (en%arg0, en%prt1)
    en%value_is_known = .true.
case (EN_UOBS2_REAL)
    en%rval = user_obs_real_pp (en%arg0, en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_PRT_FUN_UNARY)
    call eval_node_evaluate (en%arg1)
    en%value_is_known = en%arg1%value_is_known
    if (en%value_is_known) then
        if (associated (en%arg0)) then
            en%arg0%index => en%index
            en%arg0%prt1 => en%prt1
            call en% op1_sev (en%pval, en%arg1, en%arg0)
        else
            call en% op1_sev (en%pval, en%arg1)
        end if
    end if
case (EN_PRT_FUN_BINARY)
    call eval_node_evaluate (en%arg1)
    call eval_node_evaluate (en%arg2)
    en%value_is_known = &
        en%arg1%value_is_known .and. en%arg2%value_is_known
    if (en%value_is_known) then
        if (associated (en%arg0)) then
            en%arg0%index => en%index
            en%arg0%prt1 => en%prt1
            en%arg0%prt2 => en%prt2
            call en% op2_sev (en%pval, en%arg1, en%arg2, en%arg0)
        else
            call en% op2_sev (en%pval, en%arg1, en%arg2)
        end if
    end if
case (EN_EVAL_FUN_UNARY)

```

```

call eval_node_evaluate (en%arg1)
en%value_is_known = subevt_is_nonempty (en%arg1%pval)
if (en%value_is_known) then
  en%arg0%index => en%index
  en%index = 1
  en%arg0%prt1 => en%prt1
  en%prt1 = subevt_get_prt (en%arg1%pval, 1)
  call eval_node_evaluate (en%arg0)
  en%rval = en%arg0%rval
end if
case (EN_EVAL_FUN_BINARY)
  call eval_node_evaluate (en%arg1)
  call eval_node_evaluate (en%arg2)
  en%value_is_known = &
    subevt_is_nonempty (en%arg1%pval) .and. &
    subevt_is_nonempty (en%arg2%pval)
  if (en%value_is_known) then
    en%arg0%index => en%index
    en%arg0%prt1 => en%prt1
    en%arg0%prt2 => en%prt2
    en%index = 1
    call eval_pp (en%arg1, en%arg2, en%arg0, en%rval, en%value_is_known)
  end if
case (EN_LOG_FUN_UNARY)
  call eval_node_evaluate (en%arg1)
  en%value_is_known = .true.
  if (en%value_is_known) then
    en%arg0%index => en%index
    en%arg0%prt1 => en%prt1
    en%lval = en% op1_cut (en%arg1, en%arg0)
  end if
case (EN_LOG_FUN_BINARY)
  call eval_node_evaluate (en%arg1)
  call eval_node_evaluate (en%arg2)
  en%value_is_known = .true.
  if (en%value_is_known) then
    en%arg0%index => en%index
    en%arg0%prt1 => en%prt1
    en%arg0%prt2 => en%prt2
    en%lval = en% op2_cut (en%arg1, en%arg2, en%arg0)
  end if
case (EN_INT_FUN_UNARY)
  call eval_node_evaluate (en%arg1)
  en%value_is_known = en%arg1%value_is_known
  if (en%value_is_known) then
    if (associated (en%arg0)) then
      en%arg0%index => en%index
      en%arg0%prt1 => en%prt1
      call en% op1_evi (en%ival, en%arg1, en%arg0)
    else
      call en% op1_evi (en%ival, en%arg1)
    end if
  end if
case (EN_INT_FUN_BINARY)

```

```

call eval_node_evaluate (en%arg1)
call eval_node_evaluate (en%arg2)
en%value_is_known = &
    en%arg1%value_is_known .and. &
    en%arg2%value_is_known
if (en%value_is_known) then
    if (associated (en%arg0)) then
        en%arg0%index => en%index
        en%arg0%prt1 => en%prt1
        en%arg0%prt2 => en%prt2
        call en% op2_evi (en%ival, en%arg1, en%arg2, en%arg0)
    else
        call en% op2_evi (en%ival, en%arg1, en%arg2)
    end if
end if
case (EN_REAL_FUN_UNARY)
    call eval_node_evaluate (en%arg1)
    en%value_is_known = en%arg1%value_is_known
    if (en%value_is_known) then
        if (associated (en%arg0)) then
            en%arg0%index => en%index
            en%arg0%prt1 => en%prt1
            call en% op1_evr (en%rval, en%arg1, en%arg0)
        else
            call en% op1_evr (en%rval, en%arg1)
        end if
    end if
case (EN_REAL_FUN_BINARY)
    call eval_node_evaluate (en%arg1)
    call eval_node_evaluate (en%arg2)
    en%value_is_known = &
        en%arg1%value_is_known .and. &
        en%arg2%value_is_known
    if (en%value_is_known) then
        if (associated (en%arg0)) then
            en%arg0%index => en%index
            en%arg0%prt1 => en%prt1
            en%arg0%prt2 => en%prt2
            call en% op2_evr (en%rval, en%arg1, en%arg2, en%arg0)
        else
            call en% op2_evr (en%rval, en%arg1, en%arg2)
        end if
    end if
case (EN_FORMAT_STR)
    if (associated (en%arg0)) then
        call eval_node_evaluate (en%arg0)
        en%value_is_known = en%arg0%value_is_known
    else
        en%value_is_known = .true.
    end if
    if (associated (en%arg1)) then
        call eval_node_evaluate (en%arg1)
        en%value_is_known = &
            en%value_is_known .and. en%arg1%value_is_known

```

```

        if (en%value_is_known) then
            call evaluate_sprintf (en%sval, en%ival, en%arg0, en%arg1)
        end if
    else
        if (en%value_is_known) then
            call evaluate_sprintf (en%sval, en%ival, en%arg0)
        end if
    end if
end select
if (debug) then
    print *, "evaluated"
    call eval_node_write (en)
end if
end subroutine eval_node_evaluate

```

26.3.7 Evaluation syntax

We have two different flavors of the syntax: with and without particles.

```

<Eval trees: variables>+≡
    type(syntax_t), target, save :: syntax_expr
    type(syntax_t), target, save :: syntax_pexpr

```

These are for testing only and may be removed:

```

<Eval trees: public>≡
    public :: syntax_expr_init
    public :: syntax_pexpr_init

<Eval trees: procedures>+≡
    subroutine syntax_expr_init ()
        type(ifile_t) :: ifile
        call define_expr_syntax (ifile, particles=.false., analysis=.false.)
        call syntax_init (syntax_expr, ifile)
        call ifile_final (ifile)
    end subroutine syntax_expr_init

    subroutine syntax_pexpr_init ()
        type(ifile_t) :: ifile
        call define_expr_syntax (ifile, particles=.true., analysis=.false.)
        call syntax_init (syntax_pexpr, ifile)
        call ifile_final (ifile)
    end subroutine syntax_pexpr_init

<Eval trees: public>+≡
    public :: syntax_expr_final
    public :: syntax_pexpr_final

<Eval trees: procedures>+≡
    subroutine syntax_expr_final ()
        call syntax_final (syntax_expr)
    end subroutine syntax_expr_final

    subroutine syntax_pexpr_final ()
        call syntax_final (syntax_pexpr)
    end subroutine syntax_pexpr_final

```

```

end subroutine syntax_pexpr_final

<Eval trees: public>+≡
public :: syntax_pexpr_write

<Eval trees: procedures>+≡
subroutine syntax_pexpr_write (unit)
  integer, intent(in), optional :: unit
  call syntax_write (syntax_pexpr, unit)
end subroutine syntax_pexpr_write

<Eval trees: public>+≡
public :: define_expr_syntax

Numeric expressions.

<Eval trees: procedures>+≡
subroutine define_expr_syntax (ifile, particles, analysis)
  type(ifile_t), intent(inout) :: ifile
  logical, intent(in) :: particles, analysis
  type(string_t) :: numeric_pexpr
  type(string_t) :: var_plist, var_alias
  if (particles) then
    numeric_pexpr = " | numeric_pexpr"
    var_plist = " | var_plist"
    var_alias = " | var_alias"
  else
    numeric_pexpr = ""
    var_plist = ""
    var_alias = ""
  end if
  call ifile_append (ifile, "SEQ expr = subexpr addition*")
  call ifile_append (ifile, "ALT subexpr = addition | term")
  call ifile_append (ifile, "SEQ addition = plus_or_minus term")
  call ifile_append (ifile, "SEQ term = factor multiplication*")
  call ifile_append (ifile, "SEQ multiplication = times_or_over factor")
  call ifile_append (ifile, "SEQ factor = value exponentiation?")
  call ifile_append (ifile, "SEQ exponentiation = to_the value")
  call ifile_append (ifile, "ALT plus_or_minus = '+' | '-'")
  call ifile_append (ifile, "ALT times_or_over = '*' | '/'")
  call ifile_append (ifile, "ALT to_the = '^' | '**")
  call ifile_append (ifile, "KEY '+'")
  call ifile_append (ifile, "KEY '-'")
  call ifile_append (ifile, "KEY '*'")
  call ifile_append (ifile, "KEY '/'")
  call ifile_append (ifile, "KEY '^'")
  call ifile_append (ifile, "KEY '**")
  call ifile_append (ifile, "ALT value = signed_value | unsigned_value")
  call ifile_append (ifile, "SEQ signed_value = '-' unsigned_value")
  call ifile_append (ifile, "ALT unsigned_value = " // &
    "numeric_value | constant | variable | " // &
    "result | user_observable | " // &
    "grouped_expr | block_expr | conditional_expr | " // &
    "unary_function | binary_function" // &
    numeric_pexpr)

```



```

call ifile_append (ifile, "ALT numeric_value = integer_value | " &
// "real_value | complex_value")
call ifile_append (ifile, "SEQ integer_value = integer_literal unit_expr?")
call ifile_append (ifile, "SEQ real_value = real_literal unit_expr?")
call ifile_append (ifile, "SEQ complex_value = complex_literal unit_expr?")
call ifile_append (ifile, "INT integer_literal")
call ifile_append (ifile, "REA real_literal")
call ifile_append (ifile, "COM complex_literal")
call ifile_append (ifile, "SEQ unit_expr = unit unit_power?")
call ifile_append (ifile, "ALT unit = " // &
"TeV | GeV | MeV | keV | eV | meV | " // &
"nbarn | pbarn | fbarn | abarn | " // &
"rad | mrad | degree | '%'"")
call ifile_append (ifile, "KEY TeV")
call ifile_append (ifile, "KEY GeV")
call ifile_append (ifile, "KEY MeV")
call ifile_append (ifile, "KEY keV")
call ifile_append (ifile, "KEY eV")
call ifile_append (ifile, "KEY meV")
call ifile_append (ifile, "KEY nbarn")
call ifile_append (ifile, "KEY pbarn")
call ifile_append (ifile, "KEY fbarn")
call ifile_append (ifile, "KEY abarn")
call ifile_append (ifile, "KEY rad")
call ifile_append (ifile, "KEY mrad")
call ifile_append (ifile, "KEY degree")
call ifile_append (ifile, "KEY '%'"")
call ifile_append (ifile, "SEQ unit_power = '^' frac_expr")
call ifile_append (ifile, "ALT frac_expr = frac | grouped_frac")
call ifile_append (ifile, "GRO grouped_frac = ( frac_expr )")
call ifile_append (ifile, "SEQ frac = signed_int div?")
call ifile_append (ifile, "ALT signed_int = " &
// "neg_int | pos_int | integer_literal")
call ifile_append (ifile, "SEQ neg_int = '-' integer_literal")
call ifile_append (ifile, "SEQ pos_int = '+' integer_literal")
call ifile_append (ifile, "SEQ div = '/' integer_literal")
call ifile_append (ifile, "ALT constant = pi | I")
call ifile_append (ifile, "KEY pi")
call ifile_append (ifile, "KEY I")
call ifile_append (ifile, "IDE variable")
call ifile_append (ifile, "SEQ result = result_key result_arg")
call ifile_append (ifile, "ALT result_key = " // &
"num_id | integral | error")
call ifile_append (ifile, "SEQ user_observable = user_obs user_arg")
call ifile_append (ifile, "KEY user_obs")
call ifile_append (ifile, "ARG user_arg = ( sexpr )")
call ifile_append (ifile, "KEY num_id")
call ifile_append (ifile, "KEY integral")
call ifile_append (ifile, "KEY error")
call ifile_append (ifile, "GRO result_arg = ( process_id )")
call ifile_append (ifile, "IDE process_id")
call ifile_append (ifile, "SEQ unary_function = fun_unary function_arg1")
call ifile_append (ifile, "SEQ binary_function = fun_binary function_arg2")
call ifile_append (ifile, "ALT fun_unary = " // &

```

```

"complex | real | int | nint | floor | ceiling | abs | sgn | " // &
"sqrt | exp | log | log10 | " // &
"sin | cos | tan | asin | acos | atan | " // &
"sinh | cosh | tanh")
call ifile_append (ifile, "KEY complex")
call ifile_append (ifile, "KEY real")
call ifile_append (ifile, "KEY int")
call ifile_append (ifile, "KEY nint")
call ifile_append (ifile, "KEY floor")
call ifile_append (ifile, "KEY ceiling")
call ifile_append (ifile, "KEY abs")
call ifile_append (ifile, "KEY sgn")
call ifile_append (ifile, "KEY sqrt")
call ifile_append (ifile, "KEY exp")
call ifile_append (ifile, "KEY log")
call ifile_append (ifile, "KEY log10")
call ifile_append (ifile, "KEY sin")
call ifile_append (ifile, "KEY cos")
call ifile_append (ifile, "KEY tan")
call ifile_append (ifile, "KEY asin")
call ifile_append (ifile, "KEY acos")
call ifile_append (ifile, "KEY atan")
call ifile_append (ifile, "KEY sinh")
call ifile_append (ifile, "KEY cosh")
call ifile_append (ifile, "KEY tanh")
call ifile_append (ifile, "ALT fun_binary = max | min | mod | modulo")
call ifile_append (ifile, "KEY max")
call ifile_append (ifile, "KEY min")
call ifile_append (ifile, "KEY mod")
call ifile_append (ifile, "KEY modulo")
call ifile_append (ifile, "ARG function_arg1 = ( expr )")
call ifile_append (ifile, "ARG function_arg2 = ( expr, expr )")
call ifile_append (ifile, "GRO grouped_expr = ( expr )")
call ifile_append (ifile, "SEQ block_expr = let var_spec in expr")
call ifile_append (ifile, "KEY let")
call ifile_append (ifile, "ALT var_spec = " // &
"var_num | var_int | var_real | var_complex | " // &
"var_logical" // var_plist // var_alias // " | var_string")
call ifile_append (ifile, "SEQ var_num = var_name '=' expr")
call ifile_append (ifile, "SEQ var_int = int var_name '=' expr")
call ifile_append (ifile, "SEQ var_real = real var_name '=' expr")
call ifile_append (ifile, "SEQ var_complex = complex var_name '=' complex_expr")
call ifile_append (ifile, "ALT complex_expr = " // &
"cexpr_real | cexpr_complex")
call ifile_append (ifile, "ARG cexpr_complex = ( expr, expr )")
call ifile_append (ifile, "SEQ cexpr_real = expr")
call ifile_append (ifile, "IDE var_name")
call ifile_append (ifile, "KEY '='")
call ifile_append (ifile, "KEY in")
call ifile_append (ifile, "SEQ conditional_expr = " // &
"if lexpr then expr maybe_elseif_expr maybe_else_expr endif")
call ifile_append (ifile, "SEQ maybe_elseif_expr = elseif_expr*")
call ifile_append (ifile, "SEQ maybe_else_expr = else_expr?")
call ifile_append (ifile, "SEQ elseif_expr = elseif lexpr then expr")

```

```

call ifile_append (ifile, "SEQ else_expr = else expr")
call ifile_append (ifile, "KEY if")
call ifile_append (ifile, "KEY then")
call ifile_append (ifile, "KEY elsif")
call ifile_append (ifile, "KEY else")
call ifile_append (ifile, "KEY endif")
call define_lexpr_syntax (ifile, particles, analysis)
call define_sexpr_syntax (ifile)
if (particles) then
    call define_pexpr_syntax (ifile)
    call define_cexpr_syntax (ifile)
    call define_var_plist_syntax (ifile)
    call define_var_alias_syntax (ifile)
    call define_numeric_pexpr_syntax (ifile)
    call define_logical_pexpr_syntax (ifile)
end if

end subroutine define_expr_syntax

```

Logical expressions.

(Eval trees: procedures)+≡

```

subroutine define_lexpr_syntax (ifile, particles, analysis)
    type(ifile_t), intent(inout) :: ifile
    logical, intent(in) :: particles, analysis
    type(string_t) :: logical_pexpr, record_cmd
    if (particles) then
        logical_pexpr = " | logical_pexpr"
    else
        logical_pexpr = ""
    end if
    if (analysis) then
        record_cmd = " | record_cmd"
    else
        record_cmd = ""
    end if
    call ifile_append (ifile, "SEQ lexpr = lsinglet lsequel*")
    call ifile_append (ifile, "SEQ lsequel = ';' lsinglet")
    call ifile_append (ifile, "SEQ lsinglet = lterm alternative*")
    call ifile_append (ifile, "SEQ alternative = or lterm")
    call ifile_append (ifile, "SEQ lterm = lvalue coincidence*")
    call ifile_append (ifile, "SEQ coincidence = and lvalue")
    call ifile_append (ifile, "KEY ';'")
    call ifile_append (ifile, "KEY or")
    call ifile_append (ifile, "KEY and")
    call ifile_append (ifile, "ALT lvalue = " // &
        "true | false | lvariable | negation | " // &
        "grouped_lexpr | block_lexpr | conditional_lexpr | " // &
        "compared_expr | compared_sexpr" // &
        logical_pexpr // record_cmd)
    call ifile_append (ifile, "KEY true")
    call ifile_append (ifile, "KEY false")
    call ifile_append (ifile, "SEQ lvariable = '?' alt_lvariable")
    call ifile_append (ifile, "KEY '?'")
    call ifile_append (ifile, "ALT alt_lvariable = variable | grouped_lexpr")

```

```

call ifile_append (ifile, "SEQ negation = not lvalue")
call ifile_append (ifile, "KEY not")
call ifile_append (ifile, "GRO grouped_lexpr = ( lexpr )")
call ifile_append (ifile, "SEQ block_lexpr = let var_spec in lexpr")
call ifile_append (ifile, "ALT var_logical = " // &
    "var_logical_new | var_logical_spec")
call ifile_append (ifile, "SEQ var_logical_new = logical var_logical_spec")
call ifile_append (ifile, "KEY logical")
call ifile_append (ifile, "SEQ var_logical_spec = '?' var_name = lexpr")
call ifile_append (ifile, "SEQ conditional_lexpr = " // &
    "if lexpr then lexpr maybe_elseif_lexpr maybe_else_lexpr endif")
call ifile_append (ifile, "SEQ maybe_elseif_lexpr = elseif_lexpr*")
call ifile_append (ifile, "SEQ maybe_else_lexpr = else_lexpr?")
call ifile_append (ifile, "SEQ elseif_lexpr = elseif lexpr then lexpr")
call ifile_append (ifile, "SEQ else_lexpr = else lexpr")
call ifile_append (ifile, "SEQ compared_expr = expr comparison+")
call ifile_append (ifile, "SEQ comparison = compare expr")
call ifile_append (ifile, "ALT compare = " // &
    "<' | '> | '<=' | '>=' | '==' | '<>'")
call ifile_append (ifile, "KEY '<'")
call ifile_append (ifile, "KEY '>'")
call ifile_append (ifile, "KEY '<='")
call ifile_append (ifile, "KEY '>='")
call ifile_append (ifile, "KEY '=='")
call ifile_append (ifile, "KEY '<>'")
call ifile_append (ifile, "SEQ compared_sexpr = sexpr str_comparison+")
call ifile_append (ifile, "SEQ str_comparison = str_compare sexpr")
call ifile_append (ifile, "ALT str_compare = '==' | '<>'")
if (analysis) then
    call ifile_append (ifile, "SEQ record_cmd = " // &
        "record_key analysis_tag record_arg?")
    call ifile_append (ifile, "ALT record_key = " // &
        "record | record_unweighted | record_excess")
    call ifile_append (ifile, "KEY record")
    call ifile_append (ifile, "KEY record_unweighted")
    call ifile_append (ifile, "KEY record_excess")
    call ifile_append (ifile, "ALT analysis_tag = analysis_id | sexpr")
    call ifile_append (ifile, "IDE analysis_id")
    call ifile_append (ifile, "ARG record_arg = ( expr+ )")
end if
end subroutine define_lexpr_syntax

```

String expressions.

(Eval trees: procedures)+≡

```

subroutine define_sexpr_syntax (ifile)
    type(ifile_t), intent(inout) :: ifile
    call ifile_append (ifile, "SEQ sexpr = svalue str_concatenation*")
    call ifile_append (ifile, "SEQ str_concatenation = '&' svalue")
    call ifile_append (ifile, "KEY '&'")
    call ifile_append (ifile, "ALT svalue = " // &
        "grouped_sexpr | block_sexpr | conditional_sexpr | " // &
        "svariable | string_function | string_literal")
    call ifile_append (ifile, "GRO grouped_sexpr = ( sexpr )")
    call ifile_append (ifile, "SEQ block_sexpr = let var_spec in sexpr")

```

```

call ifile_append (ifile, "SEQ conditional_sexpr = " // &
    "if lexpr then sexpr maybe_elseif_sexpr maybe_else_sexpr endif")
call ifile_append (ifile, "SEQ maybe_elseif_sexpr = elseif_sexpr*")
call ifile_append (ifile, "SEQ maybe_else_sexpr = else_sexpr?")
call ifile_append (ifile, "SEQ elseif_sexpr = elseif lexpr then sexpr")
call ifile_append (ifile, "SEQ else_sexpr = else sexpr")
call ifile_append (ifile, "SEQ svariable = '$' alt_svariable")
call ifile_append (ifile, "KEY '$'")
call ifile_append (ifile, "ALT alt_svariable = variable | grouped_sexpr")
call ifile_append (ifile, "ALT var_string = " // &
    "var_string_new | var_string_spec")
call ifile_append (ifile, "SEQ var_string_new = string var_string_spec")
call ifile_append (ifile, "KEY string")
call ifile_append (ifile, "SEQ var_string_spec = '$' var_name = sexpr") ! $
call ifile_append (ifile, "ALT string_function = sprintf_fun")
call ifile_append (ifile, "SEQ sprintf_fun = sprintf_clause sprintf_args?")
call ifile_append (ifile, "SEQ sprintf_clause = sprintf sexpr")
call ifile_append (ifile, "KEY sprintf")
call ifile_append (ifile, "ARG sprintf_args = ( sprintf_arg* )")
call ifile_append (ifile, "ALT sprintf_arg = " &
    // "lvariable | svariable | expr")
call ifile_append (ifile, "QUO string_literal = '""'...'""'")
end subroutine define_sexpr_syntax

```

Eval trees that evaluate to subevents.

(Eval trees: procedures)+≡

```

subroutine define_pexpr_syntax (ifile)
    type(ifile_t), intent(inout) :: ifile
    call ifile_append (ifile, "SEQ pexpr = pterm pconcatenation*")
    call ifile_append (ifile, "SEQ pconcatenation = '&' pterm")
    ! call ifile_append (ifile, "KEY '&'" ) !!! (Key exists already)
    call ifile_append (ifile, "SEQ pterm = pvalue pcombination*")
    call ifile_append (ifile, "SEQ pcombination = '+' pvalue")
    ! call ifile_append (ifile, "KEY '+'" ) !!! (Key exists already)
    call ifile_append (ifile, "ALT pvalue = " // &
        "pexpr_src | pvariable | " // &
        "grouped_pexpr | block_pexpr | conditional_pexpr | " // &
        "prt_function")
    call ifile_append (ifile, "SEQ pexpr_src = prefix_cexpr")
    call ifile_append (ifile, "ALT prefix_cexpr = " // &
        "incoming_prt | outgoing_prt")
    call ifile_append (ifile, "SEQ incoming_prt = incoming cexpr")
    call ifile_append (ifile, "KEY incoming")
    call ifile_append (ifile, "SEQ outgoing_prt = cexpr")
    call ifile_append (ifile, "SEQ pvariable = '@' alt_pvariable")
    call ifile_append (ifile, "KEY '@'")
    call ifile_append (ifile, "ALT alt_pvariable = variable | grouped_pexpr")
    call ifile_append (ifile, "GRO grouped_pexpr = '[' pexpr ']'" )
    call ifile_append (ifile, "SEQ block_pexpr = let var_spec in pexpr")
    call ifile_append (ifile, "SEQ conditional_pexpr = " // &
        "if lexpr then pexpr maybe_elseif_pexpr maybe_else_pexpr endif")
    call ifile_append (ifile, "SEQ maybe_elseif_pexpr = elseif_pexpr*")
    call ifile_append (ifile, "SEQ maybe_else_pexpr = else_pexpr?")
    call ifile_append (ifile, "SEQ elseif_pexpr = elseif lexpr then pexpr")

```

```

call ifile_append (ifile, "SEQ else_pexpr = else pexpr")
call ifile_append (ifile, "ALT prt_function = " // &
    "join_fun | combine_fun | collect_fun | cluster_fun | " // &
    "select_fun | extract_fun | sort_fun")
call ifile_append (ifile, "SEQ join_fun = join_clause pargs2")
call ifile_append (ifile, "SEQ combine_fun = combine_clause pargs2")
call ifile_append (ifile, "SEQ collect_fun = collect_clause pargs1")
call ifile_append (ifile, "SEQ cluster_fun = cluster_clause pargs1")
call ifile_append (ifile, "SEQ select_fun = select_clause pargs1")
call ifile_append (ifile, "SEQ extract_fun = extract_clause pargs1")
call ifile_append (ifile, "SEQ sort_fun = sort_clause pargs1")
call ifile_append (ifile, "SEQ join_clause = join condition?")
call ifile_append (ifile, "SEQ combine_clause = combine condition?")
call ifile_append (ifile, "SEQ collect_clause = collect condition?")
call ifile_append (ifile, "SEQ cluster_clause = cluster condition?")
call ifile_append (ifile, "SEQ select_clause = select condition?")
call ifile_append (ifile, "SEQ extract_clause = extract position?")
call ifile_append (ifile, "SEQ sort_clause = sort criterion?")
call ifile_append (ifile, "KEY join")
call ifile_append (ifile, "KEY combine")
call ifile_append (ifile, "KEY collect")
call ifile_append (ifile, "KEY cluster")
call ifile_append (ifile, "KEY select")
call ifile_append (ifile, "SEQ condition = if lexpr")
call ifile_append (ifile, "KEY extract")
call ifile_append (ifile, "SEQ position = index expr")
call ifile_append (ifile, "KEY sort")
call ifile_append (ifile, "SEQ criterion = by expr")
call ifile_append (ifile, "KEY index")
call ifile_append (ifile, "KEY by")
call ifile_append (ifile, "ARG pargs2 = '[' pexpr, pexpr ']'")
call ifile_append (ifile, "ARG pargs1 = '[' pexpr, pexpr? ']'")
end subroutine define_pexpr_syntax

```

Eval trees that evaluate to PDG-code arrays.

<Eval trees: procedures>+≡

```

subroutine define_cexpr_syntax (ifile)
    type(ifile_t), intent(inout) :: ifile
    call ifile_append (ifile, "SEQ cexpr = avalue concatenation*")
    call ifile_append (ifile, "SEQ concatenation = ':' avalue")
    call ifile_append (ifile, "KEY ':'")
    call ifile_append (ifile, "ALT avalue = " // &
        "grouped_cexpr | block_cexpr | conditional_cexpr | " // &
        "variable | pdg_code | prt_name")
    call ifile_append (ifile, "GRO grouped_cexpr = ( cexpr )")
    call ifile_append (ifile, "SEQ block_cexpr = let var_spec in cexpr")
    call ifile_append (ifile, "SEQ conditional_cexpr = " // &
        "if lexpr then cexpr maybe_elseif_cexpr maybe_else_cexpr endif")
    call ifile_append (ifile, "SEQ maybe_elseif_cexpr = elseif_cexpr*")
    call ifile_append (ifile, "SEQ maybe_else_cexpr = else_cexpr?")
    call ifile_append (ifile, "SEQ elseif_cexpr = elseif lexpr then cexpr")
    call ifile_append (ifile, "SEQ else_cexpr = else cexpr")
    call ifile_append (ifile, "SEQ pdg_code = pdg pdg_arg")
    call ifile_append (ifile, "KEY pdg")

```

```

    call ifile_append (ifile, "ARG pdg_arg = ( expr )")
    call ifile_append (ifile, "QUO prt_name = '""'...'""'")
end subroutine define_cexpr_syntax

```

Extra variable types.

<Eval trees: procedures>+≡

```

subroutine define_var_plist_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "ALT var_plist = var_plist_new | var_plist_spec")
  call ifile_append (ifile, "SEQ var_plist_new = subevt var_plist_spec")
  call ifile_append (ifile, "KEY subevt")
  call ifile_append (ifile, "SEQ var_plist_spec = '@' var_name '=' pexpr")
end subroutine define_var_plist_syntax

subroutine define_var_alias_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "SEQ var_alias = alias var_name '=' cexpr")
  call ifile_append (ifile, "KEY alias")
end subroutine define_var_alias_syntax

```

Particle-list expressions that evaluate to numeric values

<Eval trees: procedures>+≡

```

subroutine define_numeric_pexpr_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "ALT numeric_pexpr = " &
    // "eval_fun | count_fun | event_shape_fun")
  call ifile_append (ifile, "SEQ eval_fun = eval expr pargs1")
  call ifile_append (ifile, "SEQ count_fun = count_clause pargs1")
  call ifile_append (ifile, "SEQ count_clause = count condition?")
  call ifile_append (ifile, "KEY eval")
  call ifile_append (ifile, "KEY count")
  call ifile_append (ifile, "ALT event_shape_fun = user_event_fun")
  call ifile_append (ifile, "SEQ user_event_fun = " &
    // "user_event_shape user_arg pargs1")
  call ifile_append (ifile, "KEY user_event_shape")
end subroutine define_numeric_pexpr_syntax

```

Particle-list functions that evaluate to logical values.

<Eval trees: procedures>+≡

```

subroutine define_logical_pexpr_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "ALT logical_pexpr = " // &
    "all_fun | any_fun | no_fun | user_cut_fun")
  call ifile_append (ifile, "SEQ all_fun = all lexpr pargs1")
  call ifile_append (ifile, "SEQ any_fun = any lexpr pargs1")
  call ifile_append (ifile, "SEQ no_fun = no lexpr pargs1")
  call ifile_append (ifile, "KEY all")
  call ifile_append (ifile, "KEY any")
  call ifile_append (ifile, "KEY no")
  call ifile_append (ifile, "SEQ user_cut_fun = user_cut user_arg pargs1")
  call ifile_append (ifile, "KEY user_cut")
end subroutine define_logical_pexpr_syntax

```

All characters that can occur in expressions (apart from alphanumeric).

```

<Eval trees: procedures>+≡
subroutine lexer_init_eval_tree (lexer, particles)
  type(lexer_t), intent(out) :: lexer
  logical, intent(in) :: particles
  type(keyword_list_t), pointer :: keyword_list
  if (particles) then
    keyword_list => syntax_get_keyword_list_ptr (syntax_pexpr)
  else
    keyword_list => syntax_get_keyword_list_ptr (syntax_expr)
  end if
  call lexer_init (lexer, &
    comment_chars = "#!", &
    quote_chars = "'", &
    quote_match = '"', &
    single_chars = "()[];:&%?${}@", &
    special_class = [ "+-*/^", "<>=~ " ] , &
    keyword_list = keyword_list)
end subroutine lexer_init_eval_tree

```

26.3.8 Set up appropriate parse trees

Parse an input stream as a specific flavor of expression. The appropriate expression syntax has to be available.

```

<Eval trees: public>+≡
public :: parse_tree_init_expr
public :: parse_tree_init_lexpr
public :: parse_tree_init_pexpr
public :: parse_tree_init_cexpr
public :: parse_tree_init_sexpr

<Eval trees: procedures>+≡
subroutine parse_tree_init_expr (parse_tree, stream, particles)
  type(parse_tree_t), intent(out) :: parse_tree
  type(stream_t), intent(inout), target :: stream
  logical, intent(in) :: particles
  type(lexer_t) :: lexer
  call lexer_init_eval_tree (lexer, particles)
  call lexer_assign_stream (lexer, stream)
  if (particles) then
    call parse_tree_init &
      (parse_tree, syntax_pexpr, lexer, var_str ("expr"))
  else
    call parse_tree_init &
      (parse_tree, syntax_expr, lexer, var_str ("expr"))
  end if
  call lexer_final (lexer)
end subroutine parse_tree_init_expr

subroutine parse_tree_init_lexpr (parse_tree, stream, particles)
  type(parse_tree_t), intent(out) :: parse_tree
  type(stream_t), intent(inout), target :: stream
  logical, intent(in) :: particles

```



```

type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, particles)
call lexer_assign_stream (lexer, stream)
if (particles) then
    call parse_tree_init &
        (parse_tree, syntax_pexpr, lexer, var_str ("lexpr"))
else
    call parse_tree_init &
        (parse_tree, syntax_expr, lexer, var_str ("lexpr"))
end if
call lexer_final (lexer)
end subroutine parse_tree_init_lexpr

subroutine parse_tree_init_pexpr (parse_tree, stream)
type(parse_tree_t), intent(out) :: parse_tree
type(stream_t), intent(inout), target :: stream
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, .true.)
call lexer_assign_stream (lexer, stream)
call parse_tree_init &
    (parse_tree, syntax_pexpr, lexer, var_str ("pexpr"))
call lexer_final (lexer)
end subroutine parse_tree_init_pexpr

subroutine parse_tree_init_cexpr (parse_tree, stream)
type(parse_tree_t), intent(out) :: parse_tree
type(stream_t), intent(inout), target :: stream
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, .true.)
call lexer_assign_stream (lexer, stream)
call parse_tree_init &
    (parse_tree, syntax_pexpr, lexer, var_str ("cexpr"))
call lexer_final (lexer)
end subroutine parse_tree_init_cexpr

subroutine parse_tree_init_sexpr (parse_tree, stream, particles)
type(parse_tree_t), intent(out) :: parse_tree
type(stream_t), intent(inout), target :: stream
logical, intent(in) :: particles
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, particles)
call lexer_assign_stream (lexer, stream)
if (particles) then
    call parse_tree_init &
        (parse_tree, syntax_pexpr, lexer, var_str ("seexpr"))
else
    call parse_tree_init &
        (parse_tree, syntax_expr, lexer, var_str ("seexpr"))
end if
call lexer_final (lexer)
end subroutine parse_tree_init_sexpr

```

26.3.9 The evaluation tree

The evaluation tree contains the initial variable list and the root node.

```

<Eval trees: public>+≡
    public :: eval_tree_t

<Eval trees: types>+≡
    type, extends (expr_t) :: eval_tree_t
    private
        type(parse_node_t), pointer :: pn => null ()
        type(var_list_t) :: var_list
        type(eval_node_t), pointer :: root => null ()
    contains
        <Eval trees: eval tree: TBP>
    end type eval_tree_t

```

Init from stream, using a temporary parse tree.

```

<Eval trees: procedures>+≡
    subroutine eval_tree_init_stream &
        (eval_tree, stream, var_list, subvt, result_type)
        type(eval_tree_t), intent(out), target :: eval_tree
        type(stream_t), intent(inout), target :: stream
        type(var_list_t), intent(in), target :: var_list
        type(subvt_t), intent(in), target, optional :: subvt
        integer, intent(in), optional :: result_type
        type(parse_tree_t) :: parse_tree
        type(parse_node_t), pointer :: nd_root
        integer :: type
        type = V_REAL; if (present (result_type)) type = result_type
        select case (type)
        case (V_INT, V_REAL, V_CMPLX)
            call parse_tree_init_expr (parse_tree, stream, present (subvt))
        case (V_LOG)
            call parse_tree_init_lexpr (parse_tree, stream, present (subvt))
        case (V_SEV)
            call parse_tree_init_pexpr (parse_tree, stream)
        case (V_PDG)
            call parse_tree_init_cexpr (parse_tree, stream)
        case (V_STR)
            call parse_tree_init_sexpr (parse_tree, stream, present (subvt))
        end select
        nd_root => parse_tree_get_root_ptr (parse_tree)
        if (associated (nd_root)) then
            select case (type)
            case (V_INT, V_REAL, V_CMPLX)
                call eval_tree_init_expr (eval_tree, nd_root, var_list, subvt)
            case (V_LOG)
                call eval_tree_init_lexpr (eval_tree, nd_root, var_list, subvt)
            case (V_SEV)
                call eval_tree_init_pexpr (eval_tree, nd_root, var_list, subvt)
            case (V_PDG)
                call eval_tree_init_cexpr (eval_tree, nd_root, var_list, subvt)
            case (V_STR)
                call eval_tree_init_sexpr (eval_tree, nd_root, var_list, subvt)
            end select
        end if
    end subroutine

```

```

        end select
    end if
    call parse_tree_final (parse_tree)
end subroutine eval_tree_init_stream

```

API (to be superseded by the methods below): Init from a given parse-tree node. If we evaluate an expression that contains particle-list references, the original subevent has to be supplied. The initial variable list is optional.

<Eval trees: eval tree: TBP>≡

```

procedure :: init_expr => eval_tree_init_expr
procedure :: init_lexpr => eval_tree_init_lexpr
procedure :: init_pexpr => eval_tree_init_pexpr
procedure :: init_cexpr => eval_tree_init_cexpr
procedure :: init_sexpr => eval_tree_init_sexpr

```

<Eval trees: procedures>+≡

```

subroutine eval_tree_init_expr &
    (expr, parse_node, var_list, subevt)
    class(eval_tree_t), intent(out), target :: expr
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    call eval_tree_link_var_list (expr, var_list)
    if (present (subevt)) call eval_tree_set_subevt (expr, subevt)
    call eval_node_compile_expr &
        (expr%root, parse_node, expr%var_list)
end subroutine eval_tree_init_expr

```

```

subroutine eval_tree_init_lexpr &
    (expr, parse_node, var_list, subevt)
    class(eval_tree_t), intent(out), target :: expr
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    call eval_tree_link_var_list (expr, var_list)
    if (present (subevt)) call eval_tree_set_subevt (expr, subevt)
    call eval_node_compile_lexpr &
        (expr%root, parse_node, expr%var_list)
end subroutine eval_tree_init_lexpr

```

```

subroutine eval_tree_init_pexpr &
    (expr, parse_node, var_list, subevt)
    class(eval_tree_t), intent(out), target :: expr
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    call eval_tree_link_var_list (expr, var_list)
    if (present (subevt)) call eval_tree_set_subevt (expr, subevt)
    call eval_node_compile_pexpr &
        (expr%root, parse_node, expr%var_list)
end subroutine eval_tree_init_pexpr

```

```

subroutine eval_tree_init_cexpr &
    (expr, parse_node, var_list, subevt)

```

```

class(eval_tree_t), intent(out), target :: expr
type(parse_node_t), intent(in), target :: parse_node
type(var_list_t), intent(in), target :: var_list
type(subvt_t), intent(in), optional, target :: subvt
call eval_tree_link_var_list (expr, var_list)
if (present (subvt)) call eval_tree_set_subvt (expr, subvt)
call eval_node_compile_cexpr &
    (expr%root, parse_node, expr%var_list)
end subroutine eval_tree_init_cexpr

subroutine eval_tree_init_sexpr &
    (expr, parse_node, var_list, subvt)
class(eval_tree_t), intent(out), target :: expr
type(parse_node_t), intent(in), target :: parse_node
type(var_list_t), intent(in), target :: var_list
type(subvt_t), intent(in), optional, target :: subvt
call eval_tree_link_var_list (expr, var_list)
if (present (subvt)) call eval_tree_set_subvt (expr, subvt)
call eval_node_compile_sexpr &
    (expr%root, parse_node, expr%var_list)
end subroutine eval_tree_init_sexpr

```

Alternative: set up the expression using the parse node that has already been stored. We assume that the `subvt` or any other variable that may be referred to has already been added to the local variable list.

(Eval trees: eval tree: TBP)+≡

```

procedure :: setup_expr  => eval_tree_setup_expr
procedure :: setup_lexpr => eval_tree_setup_lexpr
procedure :: setup_pexpr => eval_tree_setup_pexpr
procedure :: setup_cexpr => eval_tree_setup_cexpr
procedure :: setup_sexpr => eval_tree_setup_sexpr

```

(Eval trees: procedures)+≡

```

subroutine eval_tree_setup_expr (expr, vars)
class(eval_tree_t), intent(inout), target :: expr
class(vars_t), intent(in), target :: vars
call eval_tree_link_var_list (expr, vars)
call eval_node_compile_expr (expr%root, expr%pn, expr%var_list)
end subroutine eval_tree_setup_expr

subroutine eval_tree_setup_lexpr (expr, vars)
class(eval_tree_t), intent(inout), target :: expr
class(vars_t), intent(in), target :: vars
call eval_tree_link_var_list (expr, vars)
call eval_node_compile_lexpr (expr%root, expr%pn, expr%var_list)
end subroutine eval_tree_setup_lexpr

subroutine eval_tree_setup_pexpr (expr, vars)
class(eval_tree_t), intent(inout), target :: expr
class(vars_t), intent(in), target :: vars
call eval_tree_link_var_list (expr, vars)
call eval_node_compile_pexpr (expr%root, expr%pn, expr%var_list)
end subroutine eval_tree_setup_pexpr

```

```

subroutine eval_tree_setup_cexpr (expr, vars)
  class(eval_tree_t), intent(inout), target :: expr
  class(vars_t), intent(in), target :: vars
  call eval_tree_link_var_list (expr, vars)
  call eval_node_compile_cexpr (expr%root, expr%pn, expr%var_list)
end subroutine eval_tree_setup_cexpr

subroutine eval_tree_setup_sexpr (expr, vars)
  class(eval_tree_t), intent(inout), target :: expr
  class(vars_t), intent(in), target :: vars
  call eval_tree_link_var_list (expr, vars)
  call eval_node_compile_sexpr (expr%root, expr%pn, expr%var_list)
end subroutine eval_tree_setup_sexpr

```

This extra API function handles numerical constant expressions only. The only nontrivial part is the optional unit.

```

<Eval trees: eval tree: TBP>+≡
  procedure :: init_numeric_value => eval_tree_init_numeric_value

<Eval trees: procedures>+≡
  subroutine eval_tree_init_numeric_value (eval_tree, parse_node)
    class(eval_tree_t), intent(out), target :: eval_tree
    type(parse_node_t), intent(in), target :: parse_node
    call eval_node_compile_numeric_value (eval_tree%root, parse_node)
  end subroutine eval_tree_init_numeric_value

```

Initialize the variable list, linking it to a context variable list.

```

<Eval trees: procedures>+≡
  subroutine eval_tree_link_var_list (eval_tree, vars)
    type(eval_tree_t), intent(inout), target :: eval_tree
    class(vars_t), intent(in), target :: vars
    call eval_tree%var_list%link (vars)
  end subroutine eval_tree_link_var_list

```

Include a subevent object in the initialization. We add a pointer to this as variable @evt in the local variable list.

```

<Eval trees: procedures>+≡
  subroutine eval_tree_set_subevt (eval_tree, subevt)
    type(eval_tree_t), intent(inout), target :: eval_tree
    type(subevt_t), intent(in), target :: subevt
    logical, save, target :: known = .true.
    call var_list_append_subevt_ptr &
      (eval_tree%var_list, var_str("@evt"), subevt, known, &
        intrinsic=.true.)
  end subroutine eval_tree_set_subevt

```

Finalizer.

```

<Eval trees: eval tree: TBP>+≡
  procedure :: final => eval_tree_final

```

```

<Eval trees: procedures>+≡
subroutine eval_tree_final (expr)
  class(eval_tree_t), intent(inout) :: expr
  call expr%var_list%final ()
  if (associated (expr%root)) then
    call eval_node_final_rec (expr%root)
    deallocate (expr%root)
  end if
end subroutine eval_tree_final

```

```

<Eval trees: eval tree: TBP>+≡
procedure :: evaluate => eval_tree_evaluate

```

```

<Eval trees: procedures>+≡
subroutine eval_tree_evaluate (expr)
  class(eval_tree_t), intent(inout) :: expr
  if (associated (expr%root)) then
    call eval_node_evaluate (expr%root)
  end if
end subroutine eval_tree_evaluate

```

Check if the eval tree is allocated.

```

<Eval trees: procedures>+≡
function eval_tree_is_defined (eval_tree) result (flag)
  logical :: flag
  type(eval_tree_t), intent(in) :: eval_tree
  flag = associated (eval_tree%root)
end function eval_tree_is_defined

```

Check if the eval tree result is constant.

```

<Eval trees: procedures>+≡
function eval_tree_is_constant (eval_tree) result (flag)
  logical :: flag
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    flag = eval_tree%root%type == EN_CONSTANT
  else
    flag = .false.
  end if
end function eval_tree_is_constant

```

Insert a conversion node at the root, if necessary (only for real/int conversion)

```

<Eval trees: procedures>+≡
subroutine eval_tree_convert_result (eval_tree, result_type)
  type(eval_tree_t), intent(inout) :: eval_tree
  integer, intent(in) :: result_type
  if (associated (eval_tree%root)) then
    call insert_conversion_node (eval_tree%root, result_type)
  end if
end subroutine eval_tree_convert_result

```

Return the value of the top node, after evaluation. If the tree is empty, return the type of V_NONE. When extracting the value, no check for existence is done. For numeric values, the functions are safe against real/integer mismatch.

<Eval trees: eval tree: TBP>+≡

```

procedure :: is_known => eval_tree_result_is_known
procedure :: get_log => eval_tree_get_log
procedure :: get_int => eval_tree_get_int
procedure :: get_real => eval_tree_get_real
procedure :: get_cmplx => eval_tree_get_cmplx
procedure :: get_pdg_array => eval_tree_get_pdg_array
procedure :: get_subevt => eval_tree_get_subevt
procedure :: get_string => eval_tree_get_string

```

<Eval trees: procedures>+≡

```

function eval_tree_get_result_type (expr) result (type)
    integer :: type
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        type = expr%root%result_type
    else
        type = V_NONE
    end if
end function eval_tree_get_result_type

```

```

function eval_tree_result_is_known (expr) result (flag)
    logical :: flag
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        select case (expr%root%result_type)
            case (V_LOG, V_INT, V_REAL)
                flag = expr%root%value_is_known
            case default
                flag = .true.
        end select
    else
        flag = .false.
    end if
end function eval_tree_result_is_known

```

```

function eval_tree_result_is_known_ptr (expr) result (ptr)
    logical, pointer :: ptr
    class(eval_tree_t), intent(in) :: expr
    logical, target, save :: known = .true.
    if (associated (expr%root)) then
        select case (expr%root%result_type)
            case (V_LOG, V_INT, V_REAL)
                ptr => expr%root%value_is_known
            case default
                ptr => known
        end select
    else
        ptr => null ()
    end if
end function eval_tree_result_is_known_ptr

```

```

function eval_tree_get_log (expr) result (lval)
    logical :: lval
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) lval = expr%root%lval
end function eval_tree_get_log

```

```

function eval_tree_get_int (expr) result (ival)
    integer :: ival
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        select case (expr%root%result_type)
            case (V_INT); ival = expr%root%ival
            case (V_REAL); ival = expr%root%rval
            case (V_CMPLX); ival = expr%root%cval
        end select
    end if
end function eval_tree_get_int

```

```

function eval_tree_get_real (expr) result (rval)
    real(default) :: rval
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        select case (expr%root%result_type)
            case (V_REAL); rval = expr%root%rval
            case (V_INT); rval = expr%root%ival
            case (V_CMPLX); rval = expr%root%cval
        end select
    end if
end function eval_tree_get_real

```

```

function eval_tree_get_cmplx (expr) result (cval)
    complex(default) :: cval
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        select case (expr%root%result_type)
            case (V_CMPLX); cval = expr%root%cval
            case (V_REAL); cval = expr%root%rval
            case (V_INT); cval = expr%root%ival
        end select
    end if
end function eval_tree_get_cmplx

```

```

function eval_tree_get_pdg_array (expr) result (aval)
    type(pdg_array_t) :: aval
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        aval = expr%root%aval
    end if
end function eval_tree_get_pdg_array

```

```

function eval_tree_get_subevt (expr) result (pval)
    type(subevt_t) :: pval
    class(eval_tree_t), intent(in) :: expr

```



```

        if (associated (expr%root)) then
            pval = expr%root%pval
        end if
    end function eval_tree_get_subvt

function eval_tree_get_string (expr) result (sval)
    type(string_t) :: sval
    class(eval_tree_t), intent(in) :: expr
    if (associated (expr%root)) then
        sval = expr%root%sval
    end if
end function eval_tree_get_string

```

Return a pointer to the value of the top node.

(Eval trees: procedures)+≡

```

function eval_tree_get_log_ptr (eval_tree) result (lval)
    logical, pointer :: lval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        lval => eval_tree%root%lval
    else
        lval => null ()
    end if
end function eval_tree_get_log_ptr

function eval_tree_get_int_ptr (eval_tree) result (ival)
    integer, pointer :: ival
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        ival => eval_tree%root%ival
    else
        ival => null ()
    end if
end function eval_tree_get_int_ptr

function eval_tree_get_real_ptr (eval_tree) result (rval)
    real(default), pointer :: rval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        rval => eval_tree%root%rval
    else
        rval => null ()
    end if
end function eval_tree_get_real_ptr

function eval_tree_get_cmplx_ptr (eval_tree) result (cval)
    complex(default), pointer :: cval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        cval => eval_tree%root%cval
    else
        cval => null ()
    end if
end function eval_tree_get_cmplx_ptr

```

```

end function eval_tree_get_cmlx_ptr

function eval_tree_get_subevt_ptr (eval_tree) result (pval)
  type(subevt_t), pointer :: pval
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    pval => eval_tree%root%pval
  else
    pval => null ()
  end if
end function eval_tree_get_subevt_ptr

function eval_tree_get_pdg_array_ptr (eval_tree) result (aval)
  type(pdg_array_t), pointer :: aval
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    aval => eval_tree%root%aval
  else
    aval => null ()
  end if
end function eval_tree_get_pdg_array_ptr

function eval_tree_get_string_ptr (eval_tree) result (sval)
  type(string_t), pointer :: sval
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    sval => eval_tree%root%sval
  else
    sval => null ()
  end if
end function eval_tree_get_string_ptr

```

<Eval trees: eval tree: TBP>+≡

```

procedure :: write => eval_tree_write

```

<Eval trees: procedures>+≡

```

subroutine eval_tree_write (expr, unit, write_vars)
  class(eval_tree_t), intent(in) :: expr
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: write_vars
  integer :: u
  logical :: vl
  u = given_output_unit (unit); if (u < 0) return
  vl = .false.; if (present (write_vars)) vl = write_vars
  write (u, "(1x,A)") "Evaluation tree:"
  if (associated (expr%root)) then
    call eval_node_write_rec (expr%root, unit)
  else
    write (u, "(3x,A)") "[empty]"
  end if
  if (vl) call var_list_write (expr%var_list, unit)
end subroutine eval_tree_write

```

Use the written representation for generating an MD5 sum:

```

<Eval trees: procedures>+≡
function eval_tree_get_md5sum (eval_tree) result (md5sum_et)
  character(32) :: md5sum_et
  type(eval_tree_t), intent(in) :: eval_tree
  integer :: u
  u = free_unit ()
  open (unit = u, status = "scratch", action = "readwrite")
  call eval_tree_write (eval_tree, unit=u)
  rewind (u)
  md5sum_et = md5sum (u)
  close (u)
end function eval_tree_get_md5sum

```

26.3.10 Direct evaluation

These procedures create an eval tree and evaluate it on-the-fly, returning only the final value. The evaluation must yield a well-defined value, unless the `is_known` flag is present, which will be set accordingly.

```

<Eval trees: public>+≡
public :: eval_log
public :: eval_int
public :: eval_real
public :: eval_cmplx
public :: eval_subevt
public :: eval_pdg_array
public :: eval_string

<Eval trees: procedures>+≡
function eval_log &
  (parse_node, var_list, subevt, is_known) result (lval)
  logical :: lval
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subevt_t), intent(in), optional, target :: subevt
  logical, intent(out), optional :: is_known
  type(eval_tree_t), target :: eval_tree
  call eval_tree_init_lexpr &
    (eval_tree, parse_node, var_list, subevt)
  call eval_tree_evaluate (eval_tree)
  if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    lval = eval_tree_get_log (eval_tree)
  else if (present (is_known)) then
    is_known = .false.
  else
    call eval_tree_unknown (eval_tree, parse_node)
    lval = .false.
  end if
  call eval_tree_final (eval_tree)
end function eval_log

function eval_int &
  (parse_node, var_list, subevt, is_known) result (ival)

```

```

integer :: ival
type(parse_node_t), intent(in), target :: parse_node
type(var_list_t), intent(in), target :: var_list
type(subvt_t), intent(in), optional, target :: subvt
logical, intent(out), optional :: is_known
type(eval_tree_t), target :: eval_tree
call eval_tree_init_expr &
    (eval_tree, parse_node, var_list, subvt)
call eval_tree_evaluate (eval_tree)
if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    ival = eval_tree_get_int (eval_tree)
else if (present (is_known)) then
    is_known = .false.
else
    call eval_tree_unknown (eval_tree, parse_node)
    ival = 0
end if
call eval_tree_final (eval_tree)
end function eval_int

function eval_real &
    (parse_node, var_list, subvt, is_known) result (rval)
real(default) :: rval
type(parse_node_t), intent(in), target :: parse_node
type(var_list_t), intent(in), target :: var_list
type(subvt_t), intent(in), optional, target :: subvt
logical, intent(out), optional :: is_known
type(eval_tree_t), target :: eval_tree
call eval_tree_init_expr &
    (eval_tree, parse_node, var_list, subvt)
call eval_tree_evaluate (eval_tree)
if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    rval = eval_tree_get_real (eval_tree)
else if (present (is_known)) then
    is_known = .false.
else
    call eval_tree_unknown (eval_tree, parse_node)
    rval = 0
end if
call eval_tree_final (eval_tree)
end function eval_real

function eval_cplx &
    (parse_node, var_list, subvt, is_known) result (cval)
complex(default) :: cval
type(parse_node_t), intent(in), target :: parse_node
type(var_list_t), intent(in), target :: var_list
type(subvt_t), intent(in), optional, target :: subvt
logical, intent(out), optional :: is_known
type(eval_tree_t), target :: eval_tree
call eval_tree_init_expr &
    (eval_tree, parse_node, var_list, subvt)

```

```

call eval_tree_evaluate (eval_tree)
if (eval_tree_result_is_known (eval_tree)) then
  if (present (is_known)) is_known = .true.
  cval = eval_tree_get_cmlx (eval_tree)
else if (present (is_known)) then
  is_known = .false.
else
  call eval_tree_unknown (eval_tree, parse_node)
  cval = 0
end if
call eval_tree_final (eval_tree)
end function eval_cmlx

function eval_subvt &
  (parse_node, var_list, subvt, is_known) result (pval)
  type(subvt_t) :: pval
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subvt_t), intent(in), optional, target :: subvt
  logical, intent(out), optional :: is_known
  type(eval_tree_t), target :: eval_tree
  call eval_tree_init_pexpr &
    (eval_tree, parse_node, var_list, subvt)
  call eval_tree_evaluate (eval_tree)
  if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    pval = eval_tree_get_subvt (eval_tree)
  else if (present (is_known)) then
    is_known = .false.
  else
    call eval_tree_unknown (eval_tree, parse_node)
  end if
  call eval_tree_final (eval_tree)
end function eval_subvt

function eval_pdg_array &
  (parse_node, var_list, subvt, is_known) result (aval)
  type(pdg_array_t) :: aval
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subvt_t), intent(in), optional, target :: subvt
  logical, intent(out), optional :: is_known
  type(eval_tree_t), target :: eval_tree
  call eval_tree_init_cexpr &
    (eval_tree, parse_node, var_list, subvt)
  call eval_tree_evaluate (eval_tree)
  if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    aval = eval_tree_get_pdg_array (eval_tree)
  else if (present (is_known)) then
    is_known = .false.
  else
    call eval_tree_unknown (eval_tree, parse_node)
  end if
end if

```

```

        call eval_tree_final (eval_tree)
    end function eval_pdg_array

function eval_string &
    (parse_node, var_list, subevt, is_known) result (sval)
    type(string_t) :: sval
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    logical, intent(out), optional :: is_known
    type(eval_tree_t), target :: eval_tree
    call eval_tree_init_sexpr &
        (eval_tree, parse_node, var_list, subevt)
    call eval_tree_evaluate (eval_tree)
    if (eval_tree_result_is_known (eval_tree)) then
        if (present (is_known)) is_known = .true.
        sval = eval_tree_get_string (eval_tree)
    else if (present (is_known)) then
        is_known = .false.
    else
        call eval_tree_unknown (eval_tree, parse_node)
        sval = ""
    end if
    call eval_tree_final (eval_tree)
end function eval_string

```

Here is a variant that returns numeric values of all possible kinds, the appropriate kind to be selected later:

```

<Eval trees: public>+≡
    public :: eval_numeric

<Eval trees: procedures>+≡
    subroutine eval_numeric &
        (parse_node, var_list, subevt, ival, rval, cval, &
         is_known, result_type)
        type(parse_node_t), intent(in), target :: parse_node
        type(var_list_t), intent(in), target :: var_list
        type(subevt_t), intent(in), optional, target :: subevt
        integer, intent(out), optional :: ival
        real(default), intent(out), optional :: rval
        complex(default), intent(out), optional :: cval
        logical, intent(out), optional :: is_known
        integer, intent(out), optional :: result_type
        type(eval_tree_t), target :: eval_tree
        call eval_tree_init_expr &
            (eval_tree, parse_node, var_list, subevt)
        call eval_tree_evaluate (eval_tree)
        if (eval_tree_result_is_known (eval_tree)) then
            if (present (ival)) ival = eval_tree_get_int (eval_tree)
            if (present (rval)) rval = eval_tree_get_real (eval_tree)
            if (present (cval)) cval = eval_tree_get_cmplx (eval_tree)
            if (present (is_known)) is_known = .true.
        else
            call eval_tree_unknown (eval_tree, parse_node)
        end if
    end subroutine

```

```

        if (present (ival)) ival = 0
        if (present (rval)) rval = 0
        if (present (cval)) cval = 0
        if (present (is_known)) is_known = .false.
    end if
    if (present (result_type)) &
        result_type = eval_tree_get_result_type (eval_tree)
    call eval_tree_final (eval_tree)
end subroutine eval_numeric

```

Error message with debugging info:

```

<Eval trees: procedures>+≡
subroutine eval_tree_unknown (eval_tree, parse_node)
    type(eval_tree_t), intent(in) :: eval_tree
    type(parse_node_t), intent(in) :: parse_node
    call parse_node_write_rec (parse_node)
    call eval_tree_write (eval_tree)
    call msg_error ("Evaluation yields an undefined result, inserting default")
end subroutine eval_tree_unknown

```

26.3.11 Factory Type

Since `eval_tree_t` is an implementation of `expr_t`, we also need a matching factory type and build method.

```

<Eval trees: public>+≡
    public :: eval_tree_factory_t

<Eval trees: types>+≡
    type, extends (expr_factory_t) :: eval_tree_factory_t
    private
        type(parse_node_t), pointer :: pn => null ()
    contains
        <Eval trees: eval tree factory: TBP>
    end type eval_tree_factory_t

```

Output: delegate to the output of the embedded parse node.

```

<Eval trees: eval tree factory: TBP>≡
    procedure :: write => eval_tree_factory_write

<Eval trees: procedures>+≡
    subroutine eval_tree_factory_write (expr_factory, unit)
        class(eval_tree_factory_t), intent(in) :: expr_factory
        integer, intent(in), optional :: unit
        if (associated (expr_factory%pn)) then
            call parse_node_write_rec (expr_factory%pn, unit)
        end if
    end subroutine eval_tree_factory_write

```

Initializer: take a parse node and hide it thus from the environment.

```

<Eval trees: eval tree factory: TBP>+≡
    procedure :: init => eval_tree_factory_init

```

```

<Eval trees: procedures>+≡
  subroutine eval_tree_factory_init (expr_factory, pn)
    class(eval_tree_factory_t), intent(out) :: expr_factory
    type(parse_node_t), intent(in), pointer :: pn
    expr_factory%pn => pn
  end subroutine eval_tree_factory_init

```

Factory method: allocate expression with correct eval tree type. If the stored parse node is not associate, don't allocate.

```

<Eval trees: eval tree factory: TBP>+≡
  procedure :: build => eval_tree_factory_build

<Eval trees: procedures>+≡
  subroutine eval_tree_factory_build (expr_factory, expr)
    class(eval_tree_factory_t), intent(in) :: expr_factory
    class(expr_t), intent(out), allocatable :: expr
    if (associated (expr_factory%pn)) then
      allocate (eval_tree_t :: expr)
      select type (expr)
        type is (eval_tree_t)
          expr%pn => expr_factory%pn
        end select
      end if
    end subroutine eval_tree_factory_build

```

26.3.12 Unit tests

```

<Eval trees: public>+≡
  public :: expressions_test

<Eval trees: procedures>+≡
  subroutine expressions_test (u, results)
    integer, intent(in) :: u
    type (test_results_t), intent(inout) :: results
  <Eval trees: execute tests>
  end subroutine expressions_test

```

Testing the routines of the expressions module. First a simple unary observable and the node evaluation.

```

<Eval trees: execute tests>≡
  call test (expressions_1, "expressions_1", &
    "check simple observable", &
    u, results)

<Eval trees: tests>≡
  subroutine expressions_1 (u)
    integer, intent(in) :: u
    type(var_list_t), pointer :: var_list => null ()
    type(eval_node_t), pointer :: node => null ()
    type(prt_t), pointer :: prt => null ()
    type(string_t) :: var_name
    procedure(obs_unary_int), pointer :: obs1_iptr
    type(prt_t), pointer :: p1

```



```

write (u, "(A)")  "* Test output: Expressions"
write (u, "(A)")  "* Purpose: test simple observable and node evaluation"
write (u, "(A)")

write (u, "(A)")  "* Setting a unary observable:"
write (u, "(A)")

allocate (var_list)
allocate (prt)
call var_list_set_observables_unary (var_list, prt)
call var_list_write (var_list, u)

write (u, "(A)")  "* Evaluating the observable node:"
write (u, "(A)")

var_name = "PDG"

allocate (node)
call var_list%get_obs1_iptr (var_name, obs1_iptr, p1)
call eval_node_init_obs1_int_ptr (node, var_name, obs1_iptr, p1)
call eval_node_write (node, u)

write (u, "(A)")  "* Cleanup"
write (u, "(A)")

call eval_node_final_rec (node)
deallocate (node)
call var_list%final ()
deallocate (var_list)
deallocate (prt)

write (u, "(A)")
write (u, "(A)")  "* Test output end: expressions_1"

end subroutine expressions_1

```

Parse a complicated expression, transfer it to a parse tree and evaluate.

(Eval trees: execute tests)+≡

```

call test (expressions_2, "expressions_2", &
  "check expression transfer to parse tree", &
  u, results)

```

(Eval trees: tests)+≡

```

subroutine expressions_2 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(stream_t) :: stream
  type(eval_tree_t) :: eval_tree
  type(string_t) :: expr_text
  type(var_list_t), pointer :: var_list => null ()

  write (u, "(A)")  "* Test output: Expressions"
  write (u, "(A)")  "* Purpose: test parse routines"

```

```

write (u, "(A)")

call syntax_expr_init ()
call syntax_write (syntax_expr, u)
allocate (var_list)
call var_list_append_real (var_list, var_str ("tolerance"), 0._default)
call var_list_append_real (var_list, var_str ("x"), -5._default)
call var_list_append_int (var_list, var_str ("foo"), -27)
call var_list_append_real (var_list, var_str ("mb"), 4._default)
expr_text = &
    "let real twopi = 2 * pi in" // &
    "  twopi * sqrt (25.d0 - mb^2)" // &
    "  / (let int mb_or_0 = max (mb, 0) in" // &
    "    1 + (if -1 TeV <= x < mb_or_0 then abs(x) else x endif))"
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call var_list_write (var_list, unit = u)
call eval_tree_init_stream (eval_tree, stream, var_list=var_list)
call eval_tree_evaluate (eval_tree)
call eval_tree_write (eval_tree, u)

write (u, "(A)")  "* Input string:"
write (u, "(A,A)")  "      ", char (expr_text)
write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call stream_final (stream)
call ifile_final (ifile)
call eval_tree_final (eval_tree)
call var_list%final ()
deallocate (var_list)
call syntax_expr_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: expressions_2"

end subroutine expressions_2

```

Test a subevent expression.

(Eval trees: execute tests)+≡

```

call test (expressions_3, "expressions_3", &
    "check subevent expressions", &
    u, results)

```

(Eval trees: tests)+≡

```

subroutine expressions_3 (u)
  integer, intent(in) :: u
  type(subvt_t) :: subvt

  write (u, "(A)")  "* Test output: Expressions"
  write (u, "(A)")  "* Purpose: test subevent expressions"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize subevent:"

```

```

write (u, "(A)")

call subevt_init (subevt)
call subevt_reset (subevt, 1)
call subevt_set_incoming (subevt, 1, &
    22, vector4_moving (1.e3_default, 1.e3_default, 1), &
    0._default, [2])
call subevt_write (subevt, u)
call subevt_reset (subevt, 4)
call subevt_reset (subevt, 3)
call subevt_set_incoming (subevt, 1, &
    21, vector4_moving (1.e3_default, 1.e3_default, 3), &
    0._default, [1])
call subevt_polarize (subevt, 1, -1)
call subevt_set_outgoing (subevt, 2, &
    1, vector4_moving (0._default, 1.e3_default, 3), &
    -1.e6_default, [7])
call subevt_set_composite (subevt, 3, &
    vector4_moving (-1.e3_default, 0._default, 3), &
    [2, 7])
call subevt_write (subevt, u)

write (u, "(A)")
write (u, "(A)")  "* Test output end: expressions_3"

end subroutine expressions_3

```

Test expressions from a PDG array.

(Eval trees: execute tests)+≡

```

call test (expressions_4, "expressions_4", &
    "check pdg array expressions", &
    u, results)

```

(Eval trees: tests)+≡

```

subroutine expressions_4 (u)
    integer, intent(in) :: u
    type(subevt_t), target :: subevt
    type(string_t) :: expr_text
    type(ifile_t) :: ifile
    type(stream_t) :: stream
    type(eval_tree_t) :: eval_tree
    type(var_list_t), pointer :: var_list => null ()
    type(pdg_array_t) :: aval

    write (u, "(A)")  "* Test output: Expressions"
    write (u, "(A)")  "* Purpose: test pdg array expressions"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization:"
    write (u, "(A)")

    call syntax_pexpr_init ()
    call syntax_write (syntax_pexpr, u)
    allocate (var_list)

```

```

call var_list_append_real (var_list, var_str ("tolerance"), 0._default)
aval = 0
call var_list_append_pdg_array (var_list, var_str ("particle"), aval)
aval = [11,-11]
call var_list_append_pdg_array (var_list, var_str ("lepton"), aval)
aval = 22
call var_list_append_pdg_array (var_list, var_str ("photon"), aval)
aval = 1
call var_list_append_pdg_array (var_list, var_str ("u"), aval)
call subevt_init (subevt)
call subevt_reset (subevt, 6)
call subevt_set_incoming (subevt, 1, &
    1, vector4_moving (1._default, 1._default, 1), 0._default)
call subevt_set_incoming (subevt, 2, &
    -1, vector4_moving (2._default, 2._default, 1), 0._default)
call subevt_set_outgoing (subevt, 3, &
    22, vector4_moving (3._default, 3._default, 1), 0._default)
call subevt_set_outgoing (subevt, 4, &
    22, vector4_moving (4._default, 4._default, 1), 0._default)
call subevt_set_outgoing (subevt, 5, &
    11, vector4_moving (5._default, 5._default, 1), 0._default)
call subevt_set_outgoing (subevt, 6, &
    -11, vector4_moving (6._default, 6._default, 1), 0._default)
write (u, "(A)")
write (u, "(A)")  "* Expression:"
expr_text = &
    "let alias quark = pdg(1):pdg(2):pdg(3) in" // &
    "  any E > 3 GeV " // &
    "    [sort by - Pt " // &
    "      [select if Index < 6 " // &
    "        [photon:pdg(-11):pdg(3):quark " // &
    "          & incoming particle]]]" // &
    "  and" // &
    "  eval Theta [extract index -1 [photon]] > 45 degree" // &
    "  and" // &
    "  count [incoming photon] * 3 > 0"
write (u, "(A,A)")  "  ", char (expr_text)
write (u, "(A)")

write (u, "(A)")
write (u, "(A)")  "* Extract the evaluation tree:"
write (u, "(A)")

call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call eval_tree_init_stream (eval_tree, stream, var_list, subevt, V_LOG)
call eval_tree_write (eval_tree, u)
call eval_tree_evaluate (eval_tree)

write (u, "(A)")
write (u, "(A)")  "* Evaluate the tree:"
write (u, "(A)")

call eval_tree_write (eval_tree, u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"
write (u, "(A)")

call stream_final (stream)
call ifile_final (ifile)
call eval_tree_final (eval_tree)
call var_list%final ()
deallocate (var_list)
call syntax_pexpr_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: expressions_4"

end subroutine expressions_4

```

26.4 Physics Models

A model object represents a physics model. It contains a table of particle data, a list of parameters, and a vertex table. The list of parameters is a variable list which includes the real parameters (which are pointers to the particle data table) and PDG array variables for the particles themselves. The vertex list is used for phase-space generation, not for calculating the matrix element.

The actual numeric model data are in the base type `model_data_t`, as part of the `qft` section. We implement the `model_t` as an extension of this, for convenient direct access to the base-type methods via inheritance. (Alternatively, we could delegate these calls explicitly.) The extension contains administrative additions, such as the methods for recalculating derived data and keeping the parameter set consistent. It thus acts as a proxy of the actual model-data object towards the WHIZARD package. There are further proxy objects, such as the `parameter_t` array which provides the interface to the actual numeric parameters.

Model definitions are read from model files. Therefore, this module contains a parser for model files. The parameter definitions (derived parameters) are Sindarin expressions.

The models, as read from file, are stored in a model library which is a simple list of model definitions. For setting up a process object we should make a copy (an instance) of a model, which gets the current parameter values from the global variable list.

26.4.1 Module

`<models.f90>`≡
<File header>

```
module models

    use, intrinsic :: iso_c_binding !NODEP!

    <Use kinds>
    use kinds, only: i8, i32
    use kinds, only: c_default_float
    <Use strings>
    use format_defs, only: FMT_19
    use io_units
    use unit_tests
    use diagnostics
    use md5
    use os_interface
    use physics_defs, only: UNDEFINED, SCALAR, SPINOR
    use model_data

    use ifiles
    use syntax_rules
    use lexers
    use parser
    use pdg_arrays
    use variables
```

```

    use expr_base
    use eval_trees

    <Standard module head>

    <Models: public>

    <Models: parameters>

    <Models: types>

    <Models: interfaces>

    <Models: variables>

contains

    <Models: procedures>

    <Models: tests>

end module models

```

26.4.2 Physics Parameters

A parameter has a name, a value. Derived parameters also have a definition in terms of other parameters, which is stored as an `eval_tree`. External parameters are set by an external program.

This parameter object should be considered as a proxy object. The parameter name and value are stored in a corresponding `modelpar_data_t` object which is located in a `model_data_t` object. The latter is a component of the `model_t` handler. Methods of `parameter_t` can be delegated to the `par_data_t` component.

The `pn` component is a pointer to the parameter definition inside the model parse tree. It allows us to recreate the `eval_tree` when making copies (instances) of the parameter object.

```

<Models: parameters>≡
    integer, parameter :: PAR_NONE = 0
    integer, parameter :: PAR_INDEPENDENT = 1, PAR_DERIVED = 2
    integer, parameter :: PAR_EXTERNAL = 3

<Models: types>≡
    type :: parameter_t
    private
        integer :: type = PAR_NONE
        class(modelpar_data_t), pointer :: data => null ()
        type(parse_node_t), pointer :: pn => null ()
        class(expr_t), allocatable :: expr
    contains
        <Models: parameter: TBP>
    end type parameter_t

```

Initialization depends on parameter type. Independent parameters are initialized by a constant value or a constant numerical expression (which may contain a unit). Derived parameters are initialized by an arbitrary numerical expression, which makes use of the current variable list. The expression is evaluated by the function `parameter_reset`.

This implementation supports only real parameters and real values.

```

<Models: parameter: TBP>≡
  procedure :: init_independent_value => parameter_init_independent_value
  procedure :: init_independent => parameter_init_independent
  procedure :: init_derived => parameter_init_derived
  procedure :: init_external => parameter_init_external

<Models: procedures>≡
  subroutine parameter_init_independent_value (par, par_data, name, value)
    class(parameter_t), intent(out) :: par
    class(modelpar_data_t), intent(in), target :: par_data
    type(string_t), intent(in) :: name
    real(default), intent(in) :: value
    par%type = PAR_INDEPENDENT
    par%data => par_data
    call par%data%init (name, value)
  end subroutine parameter_init_independent_value

  subroutine parameter_init_independent (par, par_data, name, pn)
    class(parameter_t), intent(out) :: par
    class(modelpar_data_t), intent(in), target :: par_data
    type(string_t), intent(in) :: name
    type(parse_node_t), intent(in), target :: pn
    par%type = PAR_INDEPENDENT
    par%pn => pn
    allocate (eval_tree_t :: par%expr)
    select type (expr => par%expr)
    type is (eval_tree_t)
      call expr%init_numeric_value (pn)
    end select
    par%data => par_data
    call par%data%init (name, par%expr%get_real ())
  end subroutine parameter_init_independent

  subroutine parameter_init_derived (par, par_data, name, pn, var_list)
    class(parameter_t), intent(out) :: par
    class(modelpar_data_t), intent(in), target :: par_data
    type(string_t), intent(in) :: name
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    par%type = PAR_DERIVED
    par%pn => pn
    allocate (eval_tree_t :: par%expr)
    select type (expr => par%expr)
    type is (eval_tree_t)
      call expr%init_expr (pn, var_list=var_list)
    end select
    par%data => par_data
    call par%expr%evaluate ()
  end subroutine parameter_init_derived

```



```

    call par%data%init (name, par%expr%get_real ())
end subroutine parameter_init_derived

subroutine parameter_init_external (par, par_data, name)
  class(parameter_t), intent(out) :: par
  class(modelpar_data_t), intent(in), target :: par_data
  type(string_t), intent(in) :: name
  par%type = PAR_EXTERNAL
  par%data => par_data
  call par%data%init (name, 0._default)
end subroutine parameter_init_external

```

The finalizer is needed for the evaluation tree in the definition.

```

<Models: parameter: TBP>+≡
  procedure :: final => parameter_final

<Models: procedures>+≡
  subroutine parameter_final (par)
    class(parameter_t), intent(inout) :: par
    if (allocated (par%expr)) then
      call par%expr%final ()
    end if
  end subroutine parameter_final

```

All derived parameters should be recalculated if some independent parameters have changed:

```

<Models: parameter: TBP>+≡
  procedure :: reset_derived => parameter_reset_derived

<Models: procedures>+≡
  subroutine parameter_reset_derived (par)
    class(parameter_t), intent(inout) :: par
    select case (par%type)
    case (PAR_DERIVED)
      call par%expr%evaluate ()
      par%data = par%expr%get_real ()
    end select
  end subroutine parameter_reset_derived

```

Output. [We should have a formula format for the eval tree, suitable for input and output!]

```

<Models: parameter: TBP>+≡
  procedure :: write => parameter_write

<Models: procedures>+≡
  subroutine parameter_write (par, unit, write_defs)
    class(parameter_t), intent(in) :: par
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: write_defs
    logical :: defs
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    defs = .false.; if (present (write_defs)) defs = write_defs

```

```

select case (par%type)
case (PAR_INDEPENDENT)
    write (u, "(3x,A)", advance="no") "parameter"
case (PAR_DERIVED)
    write (u, "(3x,A)", advance="no") "derived"
case (PAR_EXTERNAL)
    write (u, "(3x,A)", advance="no") "external"
end select
call par%data%write (u)
select case (par%type)
case (PAR_DERIVED)
    if (defs) then
        call par%expr%write (unit)
    else
        write (u, *)
    end if
case default
    write (u, *)
end select
end subroutine parameter_write

```

Screen output variant. Restrict output to the given parameter type.

```

<Models: parameter: TBP>+≡
    procedure :: show => parameter_show

<Models: procedures>+≡
    subroutine parameter_show (par, l, u, partype)
    class(parameter_t), intent(in) :: par
    integer, intent(in) :: l, u
    integer, intent(in) :: partype
    if (par%type == partype) then
        call par%data%show (l, u)
    end if
    end subroutine parameter_show

```

26.4.3 Model Object

A model object holds all information about parameters, particles, and vertices. For models that require an external program for parameter calculation, there is the pointer to a function that does this calculation, given the set of independent and derived parameters.

As explained above, the type inherits from `model_data_t`, which is the actual storage for the model data.

When reading a model, we create a parse tree. Parameter definitions are available via parse nodes. Since we may need those later when making model instances, we keep the whole parse tree in the model definition (but not in the instances).

```

<Models: public>≡
    public :: model_t

```

```

<Models: types>+=
  type, extends (model_data_t) :: model_t
    private
      character(32) :: md5sum = ""
      type(parameter_t), dimension(:), allocatable :: par
      integer :: max_par_name_length = 0
      integer :: max_field_name_length = 0
      type(var_list_t) :: var_list
      type(string_t) :: dlname
      procedure(model_init_external_parameters), nopass, pointer :: &
        init_external_parameters => null ()
      type(dlaccess_t) :: dlaccess
      type(parse_tree_t) :: parse_tree
    contains
      <Models: model: TBP>
    end type model_t

```

This is the interface for a procedure that initializes the calculation of external parameters, given the array of all parameters.

```

<Models: interfaces>=
  abstract interface
    subroutine model_init_external_parameters (par) bind (C)
      import
      real(c_default_float), dimension(*), intent(inout) :: par
    end subroutine model_init_external_parameters
  end interface

```

Initialization: Specify the number of parameters, particles, vertices and allocate memory. If an associated DL library is specified, load this library.

```

<Models: model: TBP>=
  generic :: init => model_init
  procedure, private :: model_init

<Models: procedures>+=
  subroutine model_init &
    (model, name, libname, os_data, n_par, n_prt, n_vtx)
    class(model_t), intent(inout) :: model
    type(string_t), intent(in) :: name, libname
    type(os_data_t), intent(in) :: os_data
    integer, intent(in) :: n_par, n_prt, n_vtx
    type(c_funptr) :: c_funptr
    type(string_t) :: libpath
    call model%basic_init (name, n_par, n_prt, n_vtx)
    if (libname /= "") then
      if (.not. os_data%use_testfiles) then
        libpath = os_data%whizard_models_libpath_local
        model%dlname = os_get_dlname ( &
          libpath // "/" // libname, os_data, ignore=.true.)
      end if
      if (model%dlname == "") then
        libpath = os_data%whizard_models_libpath
        model%dlname = os_get_dlname (libpath // "/" // libname, os_data)
      end if
    end if
  end subroutine model_init

```

```

else
  model%dlname = ""
end if
if (model%dlname /= "") then
  if (.not. dlaccess_is_open (model%dlaccess)) then
    if (logging) &
      call msg_message ("Loading model auxiliary library '" &
        // char (libpath) // "/" // char (model%dlname) // "'")
    call dlaccess_init (model%dlaccess, os_data%whizard_models_libpath, &
      model%dlname, os_data)
    if (dlaccess_has_error (model%dlaccess)) then
      call msg_message (char (dlaccess_get_error (model%dlaccess)))
      call msg_fatal ("Loading model auxiliary library '" &
        // char (model%dlname) // "' failed")
      return
    end if
    c_fptr = dlaccess_get_c_funptr (model%dlaccess, &
      var_str ("init_external_parameters"))
    if (dlaccess_has_error (model%dlaccess)) then
      call msg_message (char (dlaccess_get_error (model%dlaccess)))
      call msg_fatal ("Loading function from auxiliary library '" &
        // char (model%dlname) // "' failed")
      return
    end if
    call c_f_procpointer (c_fptr, model% init_external_parameters)
  end if
end if
end subroutine model_init

```

For a model instance, we do not attempt to load a DL library. This is the core of the full initializer above.

```

<Models: model: TBP>+≡
  procedure, private :: basic_init => model_basic_init

<Models: procedures>+≡
  subroutine model_basic_init (model, name, n_par, n_prt, n_vtx)
    class(model_t), intent(inout) :: model
    type(string_t), intent(in) :: name
    integer, intent(in) :: n_par, n_prt, n_vtx
    allocate (model%par (n_par))
    call model%model_data_t%init (name, n_par, 0, n_prt, n_vtx)
  end subroutine model_basic_init

```

Finalization: The variable list contains allocated pointers, also the parse tree. We also close the DL access object, if any, that enables external parameter calculation.

```

<Models: model: TBP>+≡
  procedure :: final => model_final

<Models: procedures>+≡
  subroutine model_final (model)
    class(model_t), intent(inout) :: model
    integer :: i
    if (allocated (model%par)) then

```

```

        do i = 1, size (model%par)
            call model%par(i)%final ()
        end do
    end if
    call model%var_list%final (follow_link=.false.)
    if (model%dlname /= "") call dlaccess_final (model%dlaccess)
    call parse_tree_final (model%parse_tree)
    call model%model_data_t%final ()
end subroutine model_final

```

Output. By default, the output is in the form of an input file. If `verbose` is true, for each derived parameter the definition (eval tree) is displayed, and the vertex hash table is shown.

(Models: model: TBP)+≡

```

    procedure :: write => model_write

```

(Models: procedures)+≡

```

subroutine model_write (model, unit, verbose, &
    show_md5sum, show_variables, show_parameters, &
    show_particles, show_vertices)
    class(model_t), intent(in) :: model
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    logical, intent(in), optional :: show_md5sum
    logical, intent(in), optional :: show_variables
    logical, intent(in), optional :: show_parameters
    logical, intent(in), optional :: show_particles
    logical, intent(in), optional :: show_vertices
    logical :: verb, show_md5, show_par, show_var
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    verb = .false.; if (present (verbose)) verb = verbose
    show_md5 = .true.; if (present (show_md5sum)) &
        show_md5 = show_md5sum
    show_par = .true.; if (present (show_parameters)) &
        show_par = show_parameters
    show_var = verb; if (present (show_variables)) &
        show_var = show_variables
    write (u, "(A,A,A)" 'model ', char (model%get_name ()), ' ')
    if (show_md5 .and. model%md5sum /= "") &
        write (u, "(1x,A,A,A)" "md5sum = ", model%md5sum, " ")
    if (show_par) then
        write (u, *)
        do i = 1, size (model%par)
            call model%par(i)%write (u, write_defs=verbose)
        end do
    end if
    call model%model_data_t%write (unit, verbose, &
        show_md5sum, show_variables, &
        show_parameters=.false., &
        show_particles=show_particles, &
        show_vertices=show_vertices)
    if (show_var) then
        write (u, *)
    end if
end subroutine model_write

```

```

        call var_list_write (model%var_list, unit, follow_link=.false.)
    end if
end subroutine model_write

```

Screen output, condensed form.

```

<Models: model: TBP>+≡
    procedure :: show => model_show

<Models: procedures>+≡
    subroutine model_show (model, unit)
        class(model_t), intent(in) :: model
        integer, intent(in), optional :: unit
        integer :: i, u, l
        u = given_output_unit (unit)
        write (u, "(A,1x,A)") "Model:", char (model%get_name ())
        l = model%max_field_name_length
        call model%show_fields (l, u)
        l = model%max_par_name_length
        if (any (model%par%type == PAR_INDEPENDENT)) then
            write (u, "(2x,A)") "Independent parameters:"
            do i = 1, size (model%par)
                call model%par(i)%show (l, u, PAR_INDEPENDENT)
            end do
        end if
        if (any (model%par%type == PAR_DERIVED)) then
            write (u, "(2x,A)") "Derived parameters:"
            do i = 1, size (model%par)
                call model%par(i)%show (l, u, PAR_DERIVED)
            end do
        end if
        if (any (model%par%type == PAR_EXTERNAL)) then
            write (u, "(2x,A)") "External parameters:"
            do i = 1, size (model%par)
                call model%par(i)%show (l, u, PAR_EXTERNAL)
            end do
        end if
    end subroutine model_show

```

Show all fields/particles.

```

<Models: model: TBP>+≡
    procedure :: show_fields => model_show_fields

<Models: procedures>+≡
    subroutine model_show_fields (model, l, unit)
        class(model_t), intent(in), target :: model
        integer, intent(in) :: l
        integer, intent(in), optional :: unit
        type(field_data_t), pointer :: field
        integer :: u, i
        u = given_output_unit (unit)
        write (u, "(2x,A)") "Particles:"
        do i = 1, model%get_n_field ()
            field => model%get_field_ptr_by_index (i)
            call field%show (l, u)
        end do
    end subroutine model_show_fields

```

```

end do
end subroutine model_show_fields

```

Show the list of stable, unstable, polarized, or unpolarized particles, respectively.

(Models: model: TBP)+≡

```

procedure :: show_stable => model_show_stable
procedure :: show_unstable => model_show_unstable
procedure :: show_polarized => model_show_polarized
procedure :: show_unpolarized => model_show_unpolarized

```

(Models: procedures)+≡

```

subroutine model_show_stable (model, unit)
  class(model_t), intent(in), target :: model
  integer, intent(in), optional :: unit
  type(field_data_t), pointer :: field
  integer :: u, i
  u = given_output_unit (unit)
  write (u, "(A,1x)", advance="no") "Stable particles:"
  do i = 1, model%get_n_field ()
    field => model%get_field_ptr_by_index (i)
    if (field%is_stable (.false.)) then
      write (u, "(1x,A)", advance="no") char (field%get_name (.false.))
    end if
    if (field%has_antiparticle ()) then
      if (field%is_stable (.true.)) then
        write (u, "(1x,A)", advance="no") char (field%get_name (.true.))
      end if
    end if
  end do
  write (u, *)
end subroutine model_show_stable

subroutine model_show_unstable (model, unit)
  class(model_t), intent(in), target :: model
  integer, intent(in), optional :: unit
  type(field_data_t), pointer :: field
  integer :: u, i
  u = given_output_unit (unit)
  write (u, "(A,1x)", advance="no") "Unstable particles:"
  do i = 1, model%get_n_field ()
    field => model%get_field_ptr_by_index (i)
    if (.not. field%is_stable (.false.)) then
      write (u, "(1x,A)", advance="no") char (field%get_name (.false.))
    end if
    if (field%has_antiparticle ()) then
      if (.not. field%is_stable (.true.)) then
        write (u, "(1x,A)", advance="no") char (field%get_name (.true.))
      end if
    end if
  end do
  write (u, *)
end subroutine model_show_unstable

subroutine model_show_polarized (model, unit)

```

```

class(model_t), intent(in), target :: model
integer, intent(in), optional :: unit
type(field_data_t), pointer :: field
integer :: u, i
u = given_output_unit (unit)
write (u, "(A,1x)", advance="no") "Polarized particles:"
do i = 1, model%get_n_field ()
  field => model%get_field_ptr_by_index (i)
  if (field%is_polarized (.false.)) then
    write (u, "(1x,A)", advance="no") char (field%get_name (.false.))
  end if
  if (field%has_antiparticle ()) then
    if (field%is_polarized (.true.)) then
      write (u, "(1x,A)", advance="no") char (field%get_name (.true.))
    end if
  end if
end do
write (u, *)
end subroutine model_show_polarized

subroutine model_show_unpolarized (model, unit)
class(model_t), intent(in), target :: model
integer, intent(in), optional :: unit
type(field_data_t), pointer :: field
integer :: u, i
u = given_output_unit (unit)
write (u, "(A,1x)", advance="no") "Unpolarized particles:"
do i = 1, model%get_n_field ()
  field => model%get_field_ptr_by_index (i)
  if (.not. field%is_polarized (.false.)) then
    write (u, "(1x,A)", advance="no") &
      char (field%get_name (.false.))
  end if
  if (field%has_antiparticle ()) then
    if (.not. field%is_polarized (.true.)) then
      write (u, "(1x,A)", advance="no") char (field%get_name (.true.))
    end if
  end if
end do
write (u, *)
end subroutine model_show_unpolarized

```

Retrieve the MD5 sum of a model (actually, of the model file).

```

<Models: model: TBP>+≡
  procedure :: get_md5sum => model_get_md5sum

<Models: procedures>+≡
  function model_get_md5sum (model) result (md5sum)
    character(32) :: md5sum
    class(model_t), intent(in) :: model
    md5sum = model%md5sum
  end function model_get_md5sum

```

Parameters are defined by an expression which may be constant or arbitrary.

Note: the auxiliary pointer `value_ptr` is a workaround for a bug in gfortran 4.8.1: the target of the function pointer is lost, if the pointer is provided directly as argument.

```

<Models: model: TBP>+≡
  procedure, private :: &
    set_parameter_constant => model_set_parameter_constant
  procedure, private :: &
    set_parameter_parse_node => model_set_parameter_parse_node
  procedure, private :: &
    set_parameter_external => model_set_parameter_external

<Models: procedures>+≡
  subroutine model_set_parameter_constant (model, i, name, value)
    class(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(string_t), intent(in) :: name
    real(default), intent(in) :: value
    logical, save, target :: known = .true.
    class(modelpar_data_t), pointer :: par_data
    real(default), pointer :: value_ptr
    par_data => model%get_par_real_ptr (i)
    call model%par(i)%init_independent_value (par_data, name, value)
    value_ptr => par_data%get_real_ptr ()
    call var_list_append_real_ptr (model%var_list, &
      name, value_ptr, &
      is_known=known, intrinsic=.true.)
    model%max_par_name_length = max (model%max_par_name_length, len (name))
  end subroutine model_set_parameter_constant

  subroutine model_set_parameter_parse_node (model, i, name, pn, constant)
    class(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(string_t), intent(in) :: name
    type(parse_node_t), intent(in), target :: pn
    logical, intent(in) :: constant
    logical, save, target :: known = .true.
    class(modelpar_data_t), pointer :: par_data
    real(default), pointer :: value_ptr
    par_data => model%get_par_real_ptr (i)
    if (constant) then
      call model%par(i)%init_independent (par_data, name, pn)
    else
      call model%par(i)%init_derived (par_data, name, pn, model%var_list)
    end if
    value_ptr => par_data%get_real_ptr ()
    call var_list_append_real_ptr (model%var_list, &
      name, value_ptr, &
      is_known=known, locked=.not.constant, intrinsic=.true.)
    model%max_par_name_length = max (model%max_par_name_length, len (name))
  end subroutine model_set_parameter_parse_node

  subroutine model_set_parameter_external (model, i, name)
    class(model_t), intent(inout), target :: model
    integer, intent(in) :: i

```

```

type(string_t), intent(in) :: name
logical, save, target :: known = .true.
class(modelpar_data_t), pointer :: par_data
real(default), pointer :: value_ptr
par_data => model%get_par_real_ptr (i)
call model%par(i)%init_external (par_data, name)
value_ptr => par_data%get_real_ptr ()
call var_list_append_real_ptr (model%var_list, &
    name, value_ptr, &
    is_known=known, locked=.true., intrinsic=.true.)
model%max_par_name_length = max (model%max_par_name_length, len (name))
end subroutine model_set_parameter_external

```

Make a copy of a parameter. We assume that the `model_data_t` parameter arrays have already been copied, so names and values are available in the current model, and can be used as targets. The eval tree should not be copied, since it should refer to the new variable list. The safe solution is to make use of the above initializers, which also take care of the building a new variable list.

```

<Models: model: TBP>+≡
    procedure, private :: copy_parameter => model_copy_parameter

<Models: procedures>+≡
    subroutine model_copy_parameter (model, i, par)
        class(model_t), intent(inout), target :: model
        integer, intent(in) :: i
        type(parameter_t), intent(in) :: par
        type(string_t) :: name
        real(default) :: value
        name = par%data%get_name ()
        select case (par%type)
        case (PAR_INDEPENDENT)
            if (associated (par%pn)) then
                call model%set_parameter_parse_node (i, name, par%pn, &
                    constant = .true.)
            else
                value = par%data%get_real ()
                call model%set_parameter_constant (i, name, value)
            end if
        case (PAR_DERIVED)
            call model%set_parameter_parse_node (i, name, par%pn, &
                constant = .false.)
        case (PAR_EXTERNAL)
            call model%set_parameter_external (i, name)
        end select
    end subroutine model_copy_parameter

```

Rcalculate all derived parameters.

```

<Models: model: TBP>+≡
    procedure :: update_parameters => model_parameters_update

<Models: procedures>+≡
    subroutine model_parameters_update (model)
        class(model_t), intent(inout) :: model

```

```

integer :: i
real(default), dimension(:), allocatable :: par
do i = 1, size (model%par)
    call model%par(i)%reset_derived ()
end do
if (associated (model%init_external_parameters)) then
    allocate (par (model%get_n_real ()))
    call model%real_parameters_to_c_array (par)
    call model%init_external_parameters (par)
    call model%real_parameters_from_c_array (par)
end if
end subroutine model_parameters_update

```

Initialize field data with PDG long name and PDG code.

```

<Models: model: TBP>+≡
    procedure, private :: init_field => model_init_field

<Models: procedures>+≡
    subroutine model_init_field (model, i, longname, pdg)
        class(model_t), intent(inout), target :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: longname
        integer, intent(in) :: pdg
        type(field_data_t), pointer :: field
        field => model%get_field_ptr_by_index (i)
        call field%init (longname, pdg)
    end subroutine model_init_field

```

Copy field data for index i from another particle which serves as a template.
The name should be the unique long name.

```

<Models: model: TBP>+≡
    procedure, private :: copy_field => model_copy_field

<Models: procedures>+≡
    subroutine model_copy_field (model, i, name_src)
        class(model_t), intent(inout), target :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: name_src
        type(field_data_t), pointer :: field_src, field
        field_src => model%get_field_ptr (name_src)
        field => model%get_field_ptr_by_index (i)
        call field%copy_from (field_src)
    end subroutine model_copy_field

```

26.4.4 Model Access via Variables

Write the model variable list.

```

<Models: model: TBP>+≡
    procedure :: write_var_list => model_write_var_list

```

```

<Models: procedures>+≡
  subroutine model_write_var_list (model, unit, follow_link)
    class(model_t), intent(in) :: model
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: follow_link
    call var_list_write (model%var_list, unit, follow_link)
  end subroutine model_write_var_list

```

Link a variable list to the model variables.

```

<Models: model: TBP>+≡
  procedure :: link_var_list => model_link_var_list

<Models: procedures>+≡
  subroutine model_link_var_list (model, var_list)
    class(model_t), intent(inout) :: model
    type(var_list_t), intent(in), target :: var_list
    call model%var_list%link (var_list)
  end subroutine model_link_var_list

```

Check if the model contains a named variable.

```

<Models: model: TBP>+≡
  procedure :: var_exists => model_var_exists

<Models: procedures>+≡
  function model_var_exists (model, name) result (flag)
    class(model_t), intent(in) :: model
    type(string_t), intent(in) :: name
    logical :: flag
    flag = model%var_list%contains (name, follow_link=.false.)
  end function model_var_exists

```

Check if the model variable is a derived parameter, i.e., locked.

```

<Models: model: TBP>+≡
  procedure :: var_is_locked => model_var_is_locked

<Models: procedures>+≡
  function model_var_is_locked (model, name) result (flag)
    class(model_t), intent(in) :: model
    type(string_t), intent(in) :: name
    logical :: flag
    flag = model%var_list%is_locked (name, follow_link=.false.)
  end function model_var_is_locked

```

Set a model parameter via the named variable. We assume that the variable exists and is writable, i.e., non-locked. We update the model and variable list, so independent and derived parameters are always synchronized.

```

<Models: model: TBP>+≡
  procedure :: set_real => model_var_set_real

<Models: procedures>+≡
  subroutine model_var_set_real (model, name, rval, verbose, pacified)
    class(model_t), intent(inout) :: model
    type(string_t), intent(in) :: name

```

```

real(default), intent(in) :: rval
logical, intent(in), optional :: verbose, pacified
call var_list_set_real (model%var_list, name, rval, &
    is_known=.true., ignore=.false., &
    verbose=verbose, model_name=model%get_name (), pacified=pacified)
call model%update_parameters ()
end subroutine model_var_set_real

```

Retrieve a model parameter value.

```

<Models: model: TBP>+≡
    procedure :: get_rval => model_var_get_rval

<Models: procedures>+≡
    function model_var_get_rval (model, name) result (rval)
        class(model_t), intent(in) :: model
        type(string_t), intent(in) :: name
        real(default) :: rval
        rval = model%var_list%get_rval (name, follow_link=.false.)
    end function model_var_get_rval

```

[To be deleted] Return a pointer to the variable list.

```

<Models: model: TBP>+≡
    procedure :: get_var_list_ptr => model_get_var_list_ptr

<Models: procedures>+≡
    function model_get_var_list_ptr (model) result (var_list)
        type(var_list_t), pointer :: var_list
        class(model_t), intent(in), target :: model
        var_list => model%var_list
    end function model_get_var_list_ptr

```

26.4.5 Reading models from file

This procedure defines the model-file syntax for the parser, returning an internal file (ifile).

Note that arithmetic operators are defined as keywords in the expression syntax, so we exclude them here.

```

<Models: procedures>+≡
    subroutine define_model_file_syntax (ifile)
        type(ifile_t), intent(inout) :: ifile
        call ifile_append (ifile, "SEQ model_def = model_name_def " // &
            "parameters derived_pars external_pars particles vertices")
        call ifile_append (ifile, "SEQ model_name_def = model model_name")
        call ifile_append (ifile, "KEY model")
        call ifile_append (ifile, "QUO model_name = '...'" // &
            "'")
        call ifile_append (ifile, "SEQ parameters = parameter_def*")
        call ifile_append (ifile, "SEQ parameter_def = parameter par_name " // &
            "'=' any_real_value")
        call ifile_append (ifile, "ALT any_real_value = " &
            "// "neg_real_value | pos_real_value | real_value")
        call ifile_append (ifile, "SEQ neg_real_value = '-' real_value")
        call ifile_append (ifile, "SEQ pos_real_value = '+' real_value")
    end subroutine define_model_file_syntax

```

```

call ifile_append (ifile, "KEY parameter")
call ifile_append (ifile, "IDE par_name")
! call ifile_append (ifile, "KEY '='")          !!! Key already exists
call ifile_append (ifile, "SEQ derived_pars = derived_def*")
call ifile_append (ifile, "SEQ derived_def = derived par_name " // &
"'" '=' expr")
call ifile_append (ifile, "KEY derived")
call ifile_append (ifile, "SEQ external_pars = external_def*")
call ifile_append (ifile, "SEQ external_def = external par_name")
call ifile_append (ifile, "KEY external")
call ifile_append (ifile, "SEQ particles = particle_def*")
call ifile_append (ifile, "SEQ particle_def = particle prt_longname " // &
"prt_pdg prt_details")
call ifile_append (ifile, "KEY particle")
call ifile_append (ifile, "IDE prt_longname")
call ifile_append (ifile, "INT prt_pdg")
call ifile_append (ifile, "ALT prt_details = prt_src | prt_properties")
call ifile_append (ifile, "SEQ prt_src = like prt_longname prt_properties")
call ifile_append (ifile, "KEY like")
call ifile_append (ifile, "SEQ prt_properties = prt_property*")
call ifile_append (ifile, "ALT prt_property = " // &
"parton | invisible | gauge | left | right | " // &
"prt_name | prt_anti | prt_tex_name | prt_tex_anti | " // &
"prt_spin | prt_isospin | prt_charge | " // &
"prt_color | prt_mass | prt_width")
call ifile_append (ifile, "KEY parton")
call ifile_append (ifile, "KEY invisible")
call ifile_append (ifile, "KEY gauge")
call ifile_append (ifile, "KEY left")
call ifile_append (ifile, "KEY right")
call ifile_append (ifile, "SEQ prt_name = name name_def+")
call ifile_append (ifile, "SEQ prt_anti = anti name_def+")
call ifile_append (ifile, "SEQ prt_tex_name = tex_name name_def")
call ifile_append (ifile, "SEQ prt_tex_anti = tex_anti name_def")
call ifile_append (ifile, "KEY name")
call ifile_append (ifile, "KEY anti")
call ifile_append (ifile, "KEY tex_name")
call ifile_append (ifile, "KEY tex_anti")
call ifile_append (ifile, "ALT name_def = name_string | name_id")
call ifile_append (ifile, "QUO name_string = '""'...'""'")
call ifile_append (ifile, "IDE name_id")
call ifile_append (ifile, "SEQ prt_spin = spin frac")
call ifile_append (ifile, "KEY spin")
call ifile_append (ifile, "SEQ prt_isospin = isospin frac")
call ifile_append (ifile, "KEY isospin")
call ifile_append (ifile, "SEQ prt_charge = charge frac")
call ifile_append (ifile, "KEY charge")
call ifile_append (ifile, "SEQ prt_color = color integer_literal")
call ifile_append (ifile, "KEY color")
call ifile_append (ifile, "SEQ prt_mass = mass par_name")
call ifile_append (ifile, "KEY mass")
call ifile_append (ifile, "SEQ prt_width = width par_name")
call ifile_append (ifile, "KEY width")
call ifile_append (ifile, "SEQ vertices = vertex_def*")

```

```

    call ifile_append (ifile, "SEQ vertex_def = vertex name_def+")
    call ifile_append (ifile, "KEY vertex")
    call define_expr_syntax (ifile, particles=.false., analysis=.false.)
end subroutine define_model_file_syntax

```

The model-file syntax and lexer are fixed, therefore stored as module variables:

```

<Models: variables>≡
    type(syntax_t), target, save :: syntax_model_file

<Models: public>+≡
    public :: syntax_model_file_init

<Models: procedures>+≡
    subroutine syntax_model_file_init ()
        type(ifile_t) :: ifile
        call define_model_file_syntax (ifile)
        call syntax_init (syntax_model_file, ifile)
        call ifile_final (ifile)
    end subroutine syntax_model_file_init

<Models: procedures>+≡
    subroutine lexer_init_model_file (lexer)
        type(lexer_t), intent(out) :: lexer
        call lexer_init (lexer, &
            comment_chars = "#!", &
            quote_chars = '"{', &
            quote_match = '"}', &
            single_chars = ":()", &
            special_class = [ "+-*/^", "<>= " ] , &
            keyword_list = syntax_get_keyword_list_ptr (syntax_model_file))
    end subroutine lexer_init_model_file

<Models: public>+≡
    public :: syntax_model_file_final

<Models: procedures>+≡
    subroutine syntax_model_file_final ()
        call syntax_final (syntax_model_file)
    end subroutine syntax_model_file_final

<Models: public>+≡
    public :: syntax_model_file_write

<Models: procedures>+≡
    subroutine syntax_model_file_write (unit)
        integer, intent(in), optional :: unit
        call syntax_write (syntax_model_file, unit)
    end subroutine syntax_model_file_write

<Models: model: TBP>+≡
    procedure :: read => model_read

```

<Models: procedures>+≡

```

subroutine model_read (model, filename, os_data, exist)
  class(model_t), intent(out), target :: model
  type(string_t), intent(in) :: filename
  type(os_data_t), intent(in) :: os_data
  logical, intent(out), optional :: exist
  type(string_t) :: file
  type(stream_t), target :: stream
  type(lexer_t) :: lexer
  integer :: unit
  character(32) :: model_md5sum
  type(parse_node_t), pointer :: nd_model_def, nd_model_name_def
  type(parse_node_t), pointer :: nd_parameters, nd_derived_pars
  type(parse_node_t), pointer :: nd_external_pars
  type(parse_node_t), pointer :: nd_particles, nd_vertices
  type(string_t) :: model_name, lib_name
  integer :: n_par, n_der, n_ext, n_prt, n_vtx
  real(c_default_float), dimension(:), allocatable :: par
  integer :: i
  type(parse_node_t), pointer :: nd_par_def
  type(parse_node_t), pointer :: nd_der_def
  type(parse_node_t), pointer :: nd_ext_def
  type(parse_node_t), pointer :: nd_prt
  type(parse_node_t), pointer :: nd_vtx
  logical :: model_exist
  file = filename
  inquire (file=char(file), exist=model_exist)
  if ((.not. model_exist) .and. (.not. os_data%use_testfiles)) then
    file = os_data%whizard_modelpath_local // "/" // filename
    inquire (file = char (file), exist = model_exist)
  end if
  if (.not. model_exist) then
    file = os_data%whizard_modelpath // "/" // filename
    inquire (file = char (file), exist = model_exist)
  end if
  if (.not. model_exist) then
    call msg_fatal ("Model file '" // char (filename) // "' not found")
    if (present (exist)) exist = .false.
    return
  end if
  if (present (exist)) exist = .true.
  if (logging) call msg_message ("Reading model file '" // char (file) // "'")
  call lexer_init_model_file (lexer)
  unit = free_unit ()
  open (file=char(file), unit=unit, action="read", status="old")
  model_md5sum = md5sum (unit)
  close (unit)
  call stream_init (stream, char (file))
  call lexer_assign_stream (lexer, stream)
  call parse_tree_init (model%parse_tree, syntax_model_file, lexer)
  call stream_final (stream)
  call lexer_final (lexer)
  nd_model_def => parse_tree_get_root_ptr (model%parse_tree)
  nd_model_name_def => parse_node_get_sub_ptr (nd_model_def)

```



```

model_name = parse_node_get_string &
    (parse_node_get_sub_ptr (nd_model_name_def, 2))
nd_parameters => parse_node_get_next_ptr (nd_model_name_def)
if (associated (nd_parameters)) then
    if (parse_node_get_rule_key (nd_parameters) == "parameters") then
        n_par = parse_node_get_n_sub (nd_parameters)
        nd_par_def => parse_node_get_sub_ptr (nd_parameters)
        nd_derived_pars => parse_node_get_next_ptr (nd_parameters)
    else
        n_par = 0
        nd_derived_pars => nd_parameters
        nd_parameters => null ()
    end if
else
    n_par = 0
    nd_derived_pars => null ()
end if
if (associated (nd_derived_pars)) then
    if (parse_node_get_rule_key (nd_derived_pars) == "derived_pars") then
        n_der = parse_node_get_n_sub (nd_derived_pars)
        nd_der_def => parse_node_get_sub_ptr (nd_derived_pars)
        nd_external_pars => parse_node_get_next_ptr (nd_derived_pars)
    else
        n_der = 0
        nd_external_pars => nd_derived_pars
        nd_derived_pars => null ()
    end if
else
    n_der = 0
    nd_external_pars => null ()
end if
if (associated (nd_external_pars)) then
    if (parse_node_get_rule_key (nd_external_pars) == "external_pars") then
        n_ext = parse_node_get_n_sub (nd_external_pars)
        lib_name = "external." // model_name
        nd_ext_def => parse_node_get_sub_ptr (nd_external_pars)
        nd_particles => parse_node_get_next_ptr (nd_external_pars)
    else
        n_ext = 0
        lib_name = ""
        nd_particles => nd_external_pars
        nd_external_pars => null ()
    end if
else
    n_ext = 0
    lib_name = ""
    nd_particles => null ()
end if
if (associated (nd_particles)) then
    if (parse_node_get_rule_key (nd_particles) == "particles") then
        n_prt = parse_node_get_n_sub (nd_particles)
        nd_prt => parse_node_get_sub_ptr (nd_particles)
        nd_vertices => parse_node_get_next_ptr (nd_particles)
    else

```

```

        n_prt = 0
        nd_vertices => nd_particles
        nd_particles => null ()
    end if
else
    n_prt = 0
    nd_vertices => null ()
end if
if (associated (nd_vertices)) then
    n_vtx = parse_node_get_n_sub (nd_vertices)
    nd_vtx => parse_node_get_sub_ptr (nd_vertices)
else
    n_vtx = 0
end if
call model%init (model_name, lib_name, os_data, &
    n_par + n_der + n_ext, n_prt, n_vtx)
model%md5sum = model_md5sum
do i = 1, n_par
    call model%read_parameter (i, nd_par_def)
    nd_par_def => parse_node_get_next_ptr (nd_par_def)
end do
do i = n_par + 1, n_par + n_der
    call model%read_derived (i, nd_der_def)
    nd_der_def => parse_node_get_next_ptr (nd_der_def)
end do
do i = n_par + n_der + 1, n_par + n_der + n_ext
    call model%read_external (i, nd_ext_def)
    nd_ext_def => parse_node_get_next_ptr (nd_ext_def)
end do
if (associated (model% init_external_parameters)) then
    allocate (par (model%get_n_real ()))
    call model%real_parameters_to_c_array (par)
    call model%init_external_parameters (par)
    call model%real_parameters_from_c_array (par)
end if
do i = 1, n_prt
    call model%read_field (i, nd_prt)
    nd_prt => parse_node_get_next_ptr (nd_prt)
end do
do i = 1, n_vtx
    call model%read_vertex (i, nd_vtx)
    nd_vtx => parse_node_get_next_ptr (nd_vtx)
end do
call model%freeze_vertices ()
call model%append_field_vars ()
end subroutine model_read

```

Parameters are real values (literal) with an optional unit.

<Models: model: TBP>+≡

```
procedure, private :: read_parameter => model_read_parameter
```

<Models: procedures>+≡

```
subroutine model_read_parameter (model, i, node)
class(model_t), intent(inout), target :: model

```

```

integer, intent(in) :: i
type(parse_node_t), intent(in), target :: node
type(parse_node_t), pointer :: node_name, node_val
type(string_t) :: name
node_name => parse_node_get_sub_ptr (node, 2)
name = parse_node_get_string (node_name)
node_val => parse_node_get_next_ptr (node_name, 2)
call model%set_parameter_parse_node (i, name, node_val, constant=.true.)
end subroutine model_read_parameter

```

Derived parameters have any numeric expression as their definition.

<Models: model: TBP>+≡

```

procedure, private :: read_derived => model_read_derived

```

<Models: procedures>+≡

```

subroutine model_read_derived (model, i, node)
class(model_t), intent(inout), target :: model
integer, intent(in) :: i
type(parse_node_t), intent(in), target :: node
type(string_t) :: name
type(parse_node_t), pointer :: pn_expr
name = parse_node_get_string (parse_node_get_sub_ptr (node, 2))
pn_expr => parse_node_get_sub_ptr (node, 4)
call model%set_parameter_parse_node (i, name, pn_expr, constant=.false.)
end subroutine model_read_derived

```

External parameters have no definition; they are handled by an external library.

<Models: model: TBP>+≡

```

procedure, private :: read_external => model_read_external

```

<Models: procedures>+≡

```

subroutine model_read_external (model, i, node)
class(model_t), intent(inout), target :: model
integer, intent(in) :: i
type(parse_node_t), intent(in), target :: node
type(string_t) :: name
name = parse_node_get_string (parse_node_get_sub_ptr (node, 2))
call model%set_parameter_external (i, name)
end subroutine model_read_external

```

<Models: model: TBP>+≡

```

procedure, private :: read_field => model_read_field

```

<Models: procedures>+≡

```

subroutine model_read_field (model, i, node)
class(model_t), intent(inout), target :: model
integer, intent(in) :: i
type(parse_node_t), intent(in) :: node
type(parse_node_t), pointer :: nd_src, nd_props, nd_prop
type(string_t) :: longname
integer :: pdg
type(string_t) :: name_src
type(string_t), dimension(:), allocatable :: name
type(field_data_t), pointer :: field, field_src

```

```

longname = parse_node_get_string (parse_node_get_sub_ptr (node, 2))
pdg = parse_node_get_integer (parse_node_get_sub_ptr (node, 3))
field => model%get_field_ptr_by_index (i)
call field%init (longname, pdg)
nd_src => parse_node_get_sub_ptr (node, 4)
if (associated (nd_src)) then
  if (parse_node_get_rule_key (nd_src) == "prt_src") then
    name_src = parse_node_get_string (parse_node_get_sub_ptr (nd_src, 2))
    field_src => model%get_field_ptr (name_src, check=.true.)
    call field%copy_from (field_src)
    nd_props => parse_node_get_sub_ptr (nd_src, 3)
  else
    nd_props => nd_src
  end if
nd_prop => parse_node_get_sub_ptr (nd_props)
do while (associated (nd_prop))
  select case (char (parse_node_get_rule_key (nd_prop)))
  case ("invisible")
    call field%set (is_visible=.false.)
  case ("parton")
    call field%set (is_parton=.true.)
  case ("gauge")
    call field%set (is_gauge=.true.)
  case ("left")
    call field%set (is_left_handed=.true.)
  case ("right")
    call field%set (is_right_handed=.true.)
  case ("prt_name")
    call read_names (nd_prop, name)
    call field%set (name=name)
  case ("prt_anti")
    call read_names (nd_prop, name)
    call field%set (anti=name)
  case ("prt_tex_name")
    call field%set ( &
      tex_name = parse_node_get_string &
      (parse_node_get_sub_ptr (nd_prop, 2)))
  case ("prt_tex_anti")
    call field%set ( &
      tex_anti = parse_node_get_string &
      (parse_node_get_sub_ptr (nd_prop, 2)))
  case ("prt_spin")
    call field%set ( &
      spin_type = read_frac &
      (parse_node_get_sub_ptr (nd_prop, 2), 2))
  case ("prt_isospin")
    call field%set ( &
      isospin_type = read_frac &
      (parse_node_get_sub_ptr (nd_prop, 2), 2))
  case ("prt_charge")
    call field%set ( &
      charge_type = read_frac &
      (parse_node_get_sub_ptr (nd_prop, 2), 3))
  case ("prt_color")

```

```

        call field%set ( &
            color_type = parse_node_get_integer &
            (parse_node_get_sub_ptr (nd_prop, 2)))
    case ("prt_mass")
        call field%set ( &
            mass_data = model%get_par_data_ptr &
            (parse_node_get_string &
            (parse_node_get_sub_ptr (nd_prop, 2))))
    case ("prt_width")
        call field%set ( &
            width_data = model%get_par_data_ptr &
            (parse_node_get_string &
            (parse_node_get_sub_ptr (nd_prop, 2))))
    case default
        call msg_bug (" Unknown particle property '" &
            // char (parse_node_get_rule_key (nd_prop)) // "'")
    end select
    if (allocated (name)) deallocate (name)
    nd_prop => parse_node_get_next_ptr (nd_prop)
end do
end if
call field%freeze ()
end subroutine model_read_field

```

<Models: model: TBP>+≡

```

    procedure, private :: read_vertex => model_read_vertex

```

<Models: procedures>+≡

```

subroutine model_read_vertex (model, i, node)
    class(model_t), intent(inout) :: model
    integer, intent(in) :: i
    type(parse_node_t), intent(in) :: node
    type(string_t), dimension(:), allocatable :: name
    call read_names (node, name)
    call model%set_vertex (i, name)
end subroutine model_read_vertex

```

<Models: procedures>+≡

```

subroutine read_names (node, name)
    type(parse_node_t), intent(in) :: node
    type(string_t), dimension(:), allocatable, intent(inout) :: name
    type(parse_node_t), pointer :: nd_name
    integer :: n_names, i
    n_names = parse_node_get_n_sub (node) - 1
    allocate (name (n_names))
    nd_name => parse_node_get_sub_ptr (node, 2)
    do i = 1, n_names
        name(i) = parse_node_get_string (nd_name)
        nd_name => parse_node_get_next_ptr (nd_name)
    end do
end subroutine read_names

```

<Models: procedures>+≡

```

    function read_frac (nd_frac, base) result (qn_type)

```

```

integer :: qn_type
type(parse_node_t), intent(in) :: nd_frac
integer, intent(in) :: base
type(parse_node_t), pointer :: nd_num, nd_den
integer :: num, den
nd_num => parse_node_get_sub_ptr (nd_frac)
nd_den => parse_node_get_next_ptr (nd_num)
select case (char (parse_node_get_rule_key (nd_num)))
case ("integer_literal")
    num = parse_node_get_integer (nd_num)
case ("neg_int")
    num = - parse_node_get_integer (parse_node_get_sub_ptr (nd_num, 2))
case ("pos_int")
    num = parse_node_get_integer (parse_node_get_sub_ptr (nd_num, 2))
case default
    call parse_tree_bug (nd_num, "int|neg_int|pos_int")
end select
if (associated (nd_den)) then
    den = parse_node_get_integer (parse_node_get_sub_ptr (nd_den, 2))
else
    den = 1
end if
if (den == 1) then
    qn_type = sign (1 + abs (num) * base, num)
else if (den == base) then
    qn_type = sign (abs (num) + 1, num)
else
    call parse_node_write_rec (nd_frac)
    call msg_fatal (" Fractional quantum number: wrong denominator")
end if
end function read_frac

```

Append field (PDG-array) variables to the variable list, based on the field content.

<Models: model: TBP>+≡

```

procedure, private :: append_field_vars => model_append_field_vars

```

<Models: procedures>+≡

```

subroutine model_append_field_vars (model)
class(model_t), intent(inout) :: model
type(pdg_array_t) :: aval
type(field_data_t), dimension(:), pointer :: field_array
type(field_data_t), pointer :: field
type(string_t) :: name
type(string_t), dimension(:), allocatable :: name_array
integer, dimension(:), allocatable :: pdg
logical, dimension(:), allocatable :: mask
integer :: i, j
field_array => model%get_field_array_ptr ()
aval = UNDEFINED
call var_list_append_pdg_array &
    (model%var_list, var_str ("particle"), &
    aval, locked = .true., intrinsic=.true.)
do i = 1, size (field_array)

```

```

    aval = field_array(i)%get_pdg ()
    name = field_array(i)%get_longname ()
    call var_list_append_pdg_array &
      (model%var_list, name, aval, locked=.true., intrinsic=.true.)
    call field_array(i)%get_name_array (.false., name_array)
    do j = 1, size (name_array)
      call var_list_append_pdg_array &
        (model%var_list, name_array(j), &
          aval, locked=.true., intrinsic=.true.)
    end do
    model%max_field_name_length = &
      max (model%max_field_name_length, len (name_array(1)))
    aval = - field_array(i)%get_pdg ()
    call field_array(i)%get_name_array (.true., name_array)
    do j = 1, size (name_array)
      call var_list_append_pdg_array &
        (model%var_list, name_array(j), &
          aval, locked=.true., intrinsic=.true.)
    end do
    if (size (name_array) > 0) then
      model%max_field_name_length = &
        max (model%max_field_name_length, len (name_array(1)))
    end if
  end do
  call model%get_all_pdg (pdg)
  allocate (mask (size (pdg)))
  do i = 1, size (pdg)
    field => model%get_field_ptr (pdg(i))
    mask(i) = field%get_charge_type () /= 1
  end do
  aval = pack (pdg, mask)
  call var_list_append_pdg_array &
    (model%var_list, var_str ("charged"), &
      aval, locked = .true., intrinsic=.true.)
  do i = 1, size (pdg)
    field => model%get_field_ptr (pdg(i))
    mask(i) = field%get_color_type () /= 1
  end do
  aval = pack (pdg, mask)
  call var_list_append_pdg_array &
    (model%var_list, var_str ("colored"), &
      aval, locked = .true., intrinsic=.true.)
end subroutine model_append_field_vars

```

26.4.6 Model list

List of currently active models

(Models: types)+≡

```

type, extends (model_t) :: model_entry_t
  type(model_entry_t), pointer :: next => null ()
end type model_entry_t

```

```

<Models: public>+≡
    public :: model_list_t

<Models: types>+≡
    type :: model_list_t
        type(model_entry_t), pointer :: first => null ()
        type(model_entry_t), pointer :: last => null ()
        type(model_list_t), pointer :: context => null ()
    contains
        <Models: model list: TBP>
    end type model_list_t

```

Write an account of the model list. We write linked lists first, starting from the global context.

```

<Models: model list: TBP>≡
    procedure :: write => model_list_write

<Models: procedures>+≡
    recursive subroutine model_list_write (object, unit, verbose, follow_link)
        class(model_list_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        logical, intent(in), optional :: follow_link
        type(model_entry_t), pointer :: current
        logical :: rec
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        rec = .true.; if (present (follow_link)) rec = follow_link
        if (rec .and. associated (object%context)) then
            call object%context%write (unit, verbose, follow_link)
        end if
        current => object%first
        if (associated (current)) then
            do while (associated (current))
                call current%write (unit, verbose)
                current => current%next
                if (associated (current)) write (u, *)
            end do
        end if
    end subroutine model_list_write

```

Link this list to another one.

```

<Models: model list: TBP>+≡
    procedure :: link => model_list_link

<Models: procedures>+≡
    subroutine model_list_link (model_list, context)
        class(model_list_t), intent(inout) :: model_list
        type(model_list_t), intent(in), target :: context
        model_list%context => context
    end subroutine model_list_link

```


(Private, used below:) Append an existing model, for which we have allocated a pointer entry, to the model list. The original pointer becomes disassociated, and the model should now be considered as part of the list. We assume that this model is not yet part of the list.

If we provide a `model` argument, this returns a pointer to the new entry.

```

<Models: model list: TBP>+≡
  procedure, private :: import => model_list_import

<Models: procedures>+≡
  subroutine model_list_import (model_list, current, model)
    class(model_list_t), intent(inout) :: model_list
    type(model_entry_t), pointer, intent(inout) :: current
    type(model_t), optional, pointer, intent(out) :: model
    if (associated (current)) then
      if (associated (model_list%first)) then
        model_list%last%next => current
      else
        model_list%first => current
      end if
      model_list%last => current
      if (present (model)) model => current%model_t
      current => null ()
    end if
  end subroutine model_list_import

```

(Private, currently test only:) Add a new model with given `name` to the list, if it does not yet exist. If successful, return a pointer to the new model.

```

<Models: model list: TBP>+≡
  procedure, private :: add => model_list_add

<Models: procedures>+≡
  subroutine model_list_add (model_list, &
    name, os_data, n_par, n_prt, n_vtx, model)
    class(model_list_t), intent(inout) :: model_list
    type(string_t), intent(in) :: name
    type(os_data_t), intent(in) :: os_data
    integer, intent(in) :: n_par, n_prt, n_vtx
    type(model_t), pointer :: model
    type(model_entry_t), pointer :: current
    if (model_list%model_exists (name, follow_link=.false.)) then
      model => null ()
    else
      allocate (current)
      call current%init (name, var_str (""), os_data, &
        n_par, n_prt, n_vtx)
      call model_list%import (current, model)
    end if
  end subroutine model_list_add

```

Read a new model from file and add to the list, if it does not yet exist. Finalize the model by allocating the vertex table. Return a pointer to the new model. If unsuccessful, return the original pointer.

The model is always inserted in the last link of a chain of model lists. This way, we avoid loading models twice from different contexts. When a model is modified, we should first allocate a local copy.

```

<Models: model list: TBP>+≡
  procedure :: read_model => model_list_read_model

<Models: procedures>+≡
  subroutine model_list_read_model (model_list, name, filename, os_data, model)
    class(model_list_t), intent(inout), target :: model_list
    type(string_t), intent(in) :: name, filename
    type(os_data_t), intent(in) :: os_data
    type(model_t), pointer, intent(inout) :: model
    class(model_list_t), pointer :: global_model_list
    type(model_entry_t), pointer :: current
    logical :: exist
    if (.not. model_list%model_exists (name, follow_link=.true.)) then
      allocate (current)
      call current%read (filename, os_data, exist)
      if (.not. exist) return
      if (current%get_name () /= name) then
        call msg_fatal ("Model file '" // char (filename) // &
          "' contains model '" // char (current%get_name ()) // &
          "' instead of '" // char (name) // "'")
        call current%final (); deallocate (current)
        return
      end if
      global_model_list => model_list
      do while (associated (global_model_list%context))
        global_model_list => global_model_list%context
      end do
      call global_model_list%import (current, model)
    else
      model => model_list%get_model_ptr (name)
    end if
  end subroutine model_list_read_model

```

Append a copy of an existing model to a model list. Optionally, return pointer to the new entry.

```

<Models: model list: TBP>+≡
  procedure :: append_copy => model_list_append_copy

<Models: procedures>+≡
  subroutine model_list_append_copy (model_list, orig, model)
    class(model_list_t), intent(inout) :: model_list
    type(model_t), intent(in), target :: orig
    type(model_t), intent(out), pointer, optional :: model
    type(model_entry_t), pointer :: copy
    allocate (copy)
    call copy%init_instance (orig)
    call model_list%import (copy, model)
  end subroutine model_list_append_copy

```

Check if a model exists by examining the list. Check recursively unless told otherwise.

```

<Models: model list: TBP>+≡
  procedure :: model_exists => model_list_model_exists

<Models: procedures>+≡
  recursive function model_list_model_exists (model_list, name, follow_link) &
    result (exists)
    class(model_list_t), intent(in) :: model_list
    logical :: exists
    type(string_t), intent(in) :: name
    logical, intent(in), optional :: follow_link
    type(model_entry_t), pointer :: current
    logical :: rec
    rec = .true.; if (present (follow_link)) rec = follow_link
    current => model_list%first
    do while (associated (current))
      if (current%get_name () == name) then
        exists = .true.
        return
      end if
      current => current%next
    end do
    if (rec .and. associated (model_list%context)) then
      exists = model_list%context%model_exists (name, follow_link)
    else
      exists = .false.
    end if
  end function model_list_model_exists

```

Return a pointer to a named model. Search recursively unless told otherwise.

```

<Models: model list: TBP>+≡
  procedure :: get_model_ptr => model_list_get_model_ptr

<Models: procedures>+≡
  recursive function model_list_get_model_ptr (model_list, name, follow_link) &
    result (model)
    class(model_list_t), intent(in) :: model_list
    type(model_t), pointer :: model
    type(string_t), intent(in) :: name
    logical, intent(in), optional :: follow_link
    type(model_entry_t), pointer :: current
    logical :: rec
    rec = .true.; if (present (follow_link)) rec = follow_link
    current => model_list%first
    do while (associated (current))
      if (current%get_name () == name) then
        model => current%model_t
        return
      end if
      current => current%next
    end do
    if (rec .and. associated (model_list%context)) then
      model => model_list%context%get_model_ptr (name, follow_link)
    end if
  end function model_list_get_model_ptr

```

```

else
    model => null ()
end if
end function model_list_get_model_ptr

```

Delete the list of models. No recursion.

```

⟨Models: model list: TBP⟩+≡
    procedure :: final => model_list_final

⟨Models: procedures⟩+≡
    subroutine model_list_final (model_list)
        class(model_list_t), intent(inout) :: model_list
        type(model_entry_t), pointer :: current
        model_list%last => null ()
        do while (associated (model_list%first))
            current => model_list%first
            model_list%first => model_list%first%next
            call current%final ()
            deallocate (current)
        end do
    end subroutine model_list_final

```

26.4.7 Model instances

A model instance is a copy of a model object. The parameters are true copies. The particle data and the variable list pointers should point to the copy, so modifying the parameters has only a local effect. Hence, we build them up explicitly. The vertex array is also rebuilt, it contains particle pointers. Finally, the vertex hash table can be copied directly since it contains no pointers.

The `multiplicity` entry depends on the association of the `mass_data` entry and therefore has to be set at the end.

The instance must carry the `target` attribute.

Parameters: the `copy_parameter` method essentially copies the parameter decorations (parse node, expression etc.). The current parameter values are part of the `model_data_t` base type and are copied afterwards via its `copy_from` method.

```

⟨Models: model: TBP⟩+≡
    procedure :: init_instance => model_copy

⟨Models: procedures⟩+≡
    subroutine model_copy (model, orig)
        class(model_t), intent(out), target :: model
        type(model_t), intent(in) :: orig
        integer :: n_par, n_prt, n_vtx
        integer :: i
        n_par = size (orig%par)
        n_prt = orig%get_n_field ()
        n_vtx = orig%get_n_vtx ()
        call model%basic_init (orig%get_name (), n_par, n_prt, n_vtx)
        model%md5sum = orig%md5sum
        do i = 1, n_par
            call model%copy_parameter (i, orig%par(i))
        end do
    end subroutine model_copy

```

```

end do
model%init_external_parameters => orig%init_external_parameters
call model%copy_from (orig)
model%max_par_name_length = orig%max_par_name_length
call model%append_field_vars ()
end subroutine model_copy

```

(Obsolete:) Turn a pointer to a model into a true copy, i.e., a new instance.
Reset: delete this instance.

```

<Models: public>+≡
!   public :: model_pointer_to_instance
!   public :: model_pointer_delete_instance

<Models: procedures>+≡
!   subroutine model_pointer_to_instance (model)
!       type(model_t), pointer, intent(inout) :: model
!       type(model_t), pointer :: model_tmp
!       model_tmp => model
!       allocate (model)
!       call model%init_instance (model_tmp)
!   end subroutine model_pointer_to_instance

!   subroutine model_pointer_delete_instance (model)
!       type(model_t), pointer, intent(inout) :: model
!       if (associated (model)) then
!           call model%final ()
!           deallocate (model)
!       end if
!   end subroutine model_pointer_delete_instance

```

26.4.8 Unit tests

```

<Models: public>+≡
    public :: models_test

<Models: tests>≡
    subroutine models_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Models: execute tests>
    end subroutine models_test

```

Construct a Model

Here, we construct a toy model explicitly without referring to a file.

```

<Models: execute tests>≡
    call test (models_1, "models_1", &
        "construct model", &
        u, results)

```

$\langle Models: tests \rangle + \equiv$

```

subroutine models_1 (u)
  integer, intent(in) :: u
  type(os_data_t) :: os_data
  type(model_list_t) :: model_list
  type(model_t), pointer :: model
  type(string_t) :: model_name
  type(string_t) :: x_longname
  type(string_t), dimension(2) :: parname
  type(string_t), dimension(2) :: x_name
  type(string_t), dimension(1) :: x_anti
  type(string_t) :: x_tex_name, x_tex_anti
  type(string_t) :: y_longname
  type(string_t), dimension(2) :: y_name
  type(string_t) :: y_tex_name
  type(field_data_t), pointer :: field

  write (u, "(A)")  "* Test output: models_1"
  write (u, "(A)")  "* Purpose: create a model"
  write (u, *)

  model_name = "Test model"
  call model_list%add (model_name, os_data, 2, 2, 3, model)
  parname(1) = "mx"
  parname(2) = "coup"
  call model%set_parameter_constant (1, parname(1), 10._default)
  call model%set_parameter_constant (2, parname(2), 1.3_default)
  x_longname = "X_LEPTON"
  x_name(1) = "X"
  x_name(2) = "x"
  x_anti(1) = "Xbar"
  x_tex_name = "X^+"
  x_tex_anti = "X^-"
  field => model%get_field_ptr_by_index (1)
  call field%init (x_longname, 99)
  call field%set ( &
    .true., .false., .false., .false., .false., &
    name=x_name, anti=x_anti, tex_name=x_tex_name, tex_anti=x_tex_anti, &
    spin_type=SPINOR, isospin_type=-3, charge_type=2, &
    mass_data=model%get_par_data_ptr (parname(1)))
  y_longname = "Y_COLORON"
  y_name(1) = "Y"
  y_name(2) = "yc"
  y_tex_name = "Y^0"
  field => model%get_field_ptr_by_index (2)
  call field%init (y_longname, 97)
  call field%set ( &
    .false., .false., .true., .false., .false., &
    name=y_name, tex_name=y_tex_name, &
    spin_type=SCALAR, isospin_type=2, charge_type=1, color_type=8)
  call model%set_vertex (1, [99, 99, 99])
  call model%set_vertex (2, [99, 99, 99, 99])
  call model%set_vertex (3, [99, 97, 99])
  call model_list%write (u)

```

```

call model_list%final ()

write (u, *)
write (u, "(A)")  "* Test output end: models_1"

end subroutine models_1

```

Read a Model

Read a predefined model from file.

```

<Models: execute tests>+≡
call test (models_2, "models_2", &
  "read model", &
  u, results)

<Models: tests>+≡
subroutine models_2 (u)
  integer, intent(in) :: u
  type(os_data_t) :: os_data
  type(model_list_t) :: model_list
  type(model_t), pointer :: model

  write (u, "(A)")  "* Test output: models_2"
  write (u, "(A)")  "* Purpose: read a model from file"
  write (u, *)

  call syntax_model_file_init ()
  call os_data_init (os_data)

  call model_list%read_model (var_str ("Test"), var_str ("Test.mdl"), &
    os_data, model)
  call model_list%write (u)

  write (u, *)
  write (u, "(A)")  "* Variable list"
  write (u, *)

  call var_list_write (model%var_list, u)

  write (u, *)
  write (u, "(A)")  "* Cleanup"

  call model_list%final ()
  call syntax_model_file_final ()

  write (u, *)
  write (u, "(A)")  "* Test output end: models_2"

end subroutine models_2

```

Model Instance

Read a predefined model from file and create an instance.

```
(Models: execute tests)+≡
    call test (models_3, "models_3", &
               "model instance", &
               u, results)

(Models: tests)+≡
    subroutine models_3 (u)
        integer, intent(in) :: u
        type(os_data_t) :: os_data
        type(model_list_t) :: model_list
        type(model_t), pointer :: model
        type(model_t), pointer :: instance

        write (u, "(A)")  "* Test output: models_3"
        write (u, "(A)")  "* Purpose: create a model instance"
        write (u, *)

        call syntax_model_file_init ()
        call os_data_init (os_data)

        call model_list%read_model (var_str ("Test"), var_str ("Test.mdl"), &
                                     os_data, model)
        allocate (instance)
        call instance%init_instance (model)

        call model%write (u)

        write (u, *)
        write (u, "(A)")  "* Variable list"
        write (u, *)

        call var_list_write (instance%var_list, u)

        write (u, *)
        write (u, "(A)")  "* Cleanup"

        call instance%final ()
        deallocate (instance)

        call model_list%final ()
        call syntax_model_file_final ()

        write (u, *)
        write (u, "(A)")  "* Test output end: models_3"

    end subroutine models_3
```

Unstable and Polarized Particles

Read a predefined model from file and define decays and polarization.


```

<Models: execute tests>+=
    call test (models_4, "models_4", &
        "handle decays and polarization", &
        u, results)

<Models: tests>+=
    subroutine models_4 (u)
        integer, intent(in) :: u
        type(os_data_t) :: os_data
        type(model_list_t) :: model_list
        type(model_t), pointer :: model, model_instance
        character(32) :: md5sum

        write (u, "(A)")  "* Test output: models_4"
        write (u, "(A)")  "* Purpose: set and unset decays and polarization"
        write (u, *)

        call syntax_model_file_init ()
        call os_data_init (os_data)

        write (u, "(A)")  "* Read model from file"

        call model_list%read_model (var_str ("Test"), var_str ("Test.mdl"), &
            os_data, model)

        md5sum = model%get_parameters_md5sum ()
        write (u, *)
        write (u, "(1x,3A)")  "MD5 sum (parameters) = '", md5sum, "'"

        write (u, *)
        write (u, "(A)")  "* Set particle decays and polarization"
        write (u, *)

        call model%set_unstable (25, [var_str ("dec1"), var_str ("dec2")])
        call model%set_polarized (6)
        call model%set_unstable (-6, [var_str ("fdec")])

        call model%write (u)

        md5sum = model%get_parameters_md5sum ()
        write (u, *)
        write (u, "(1x,3A)")  "MD5 sum (parameters) = '", md5sum, "'"

        write (u, *)
        write (u, "(A)")  "* Create a model instance"

        allocate (model_instance)
        call model_instance%init_instance (model)

        write (u, *)
        write (u, "(A)")  "* Revert particle decays and polarization"
        write (u, *)

        call model%set_stable (25)
        call model%set_unpolarized (6)

```

```

call model%set_stable (-6)

call model%write (u)

md5sum = model%get_parameters_md5sum ()
write (u, *)
write (u, "(1x,3A)") "MD5 sum (parameters) = '", md5sum, "'"

write (u, *)
write (u, "(A)")  "* Show the model instance"
write (u, *)

call model_instance%write (u)

md5sum = model_instance%get_parameters_md5sum ()
write (u, *)
write (u, "(1x,3A)") "MD5 sum (parameters) = '", md5sum, "'"

write (u, *)
write (u, "(A)")  "* Cleanup"

call model_instance%final ()
deallocate (model_instance)
call model_list%final ()
call syntax_model_file_final ()

write (u, *)
write (u, "(A)")  "* Test output end: models_4"

end subroutine models_4

```

Model Variables

Read a predefined model from file and modify some parameters.

Note that the MD5 sum is not modified by this.

```

<Models: execute tests>+≡
  call test (models_5, "models_5", &
    "handle parameters", &
    u, results)

<Models: tests>+≡
  subroutine models_5 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(model_list_t) :: model_list
    type(model_t), pointer :: model, model_instance
    character(32) :: md5sum

    write (u, "(A)")  "* Test output: models_5"
    write (u, "(A)")  "* Purpose: access and modify model variables"
    write (u, *)

    call syntax_model_file_init ()

```

```

call os_data_init (os_data)

write (u, "(A)")  "* Read model from file"

call model_list%read_model (var_str ("Test"), var_str ("Test.mdl"), &
    os_data, model)

write (u, *)

call model%write (u, &
    show_md5sum = .true., &
    show_variables = .true., &
    show_parameters = .true., &
    show_particles = .false., &
    show_vertices = .false.)

write (u, *)
write (u, "(A)")  "* Check parameter status"
write (u, *)

write (u, "(1x,A,L1)") "xy exists = ", model%var_exists (var_str ("xx"))
write (u, "(1x,A,L1)") "ff exists = ", model%var_exists (var_str ("ff"))
write (u, "(1x,A,L1)") "mf exists = ", model%var_exists (var_str ("mf"))
write (u, "(1x,A,L1)") "ff locked = ", model%var_is_locked (var_str ("ff"))
write (u, "(1x,A,L1)") "mf locked = ", model%var_is_locked (var_str ("mf"))

write (u, *)
write (u, "(1x,A,F6.2)") "ff = ", model%get_rval (var_str ("ff"))
write (u, "(1x,A,F6.2)") "mf = ", model%get_rval (var_str ("mf"))

write (u, *)
write (u, "(A)")  "* Modify parameter"
write (u, *)

call model%set_real (var_str ("ff"), 1._default)

call model%write (u, &
    show_md5sum = .true., &
    show_variables = .true., &
    show_parameters = .true., &
    show_particles = .false., &
    show_vertices = .false.)

write (u, *)
write (u, "(A)")  "* Cleanup"

call model_list%final ()
call syntax_model_file_final ()

write (u, *)
write (u, "(A)")  "* Test output end: models_5"

end subroutine models_5

```

26.5 The SUSY Les Houches Accord

The SUSY Les Houches Accord defines a standard interfaces for storing the physics data of SUSY models. Here, we provide the means for reading, storing, and writing such data.

```
<slha_interface.f90>≡  
  <File header>  
  
  module slha_interface  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use constants  
    use string_utils, only: upper_case  
    use unit_tests  
    use system_defs, only: VERSION_STRING  
    use system_defs, only: EOF  
    use diagnostics  
    use os_interface  
    use ifiles  
    use lexers  
    use syntax_rules  
    use parser  
    use variables  
    use models  
  
    <Standard module head>  
  
    <SLHA: public>  
  
    <SLHA: parameters>  
  
    <SLHA: variables>  
  
    save  
  
    contains  
  
    <SLHA: procedures>  
  
    <SLHA: tests>  
  
  end module slha_interface
```

26.5.1 Preprocessor

SLHA is a mixed-format standard. It should be read in assuming free format (but line-oriented), but it has some fixed-format elements.

To overcome this difficulty, we implement a preprocessing step which transforms the SLHA into a format that can be swallowed by our generic free-format lexer and parser. Each line with a blank first character is assumed to be a

data line. We prepend a 'DATA' keyword to these lines. Furthermore, to enforce line-orientation, each line is appended a '\$' key which is recognized by the parser. To do this properly, we first remove trailing comments, and skip lines consisting only of comments.

The preprocessor reads from a stream and puts out an `ifile`. Blocks that are not recognized are skipped. For some blocks, data items are quoted, so they can be read as strings if necessary.

<SLHA: parameters>≡

```
integer, parameter :: MODE_SKIP = 0, MODE_DATA = 1, MODE_INFO = 2
```

<SLHA: procedures>≡

```
subroutine slha_preprocess (stream, ifile)
  type(stream_t), intent(inout), target :: stream
  type(ifile_t), intent(out) :: ifile
  type(string_t) :: buffer, line, item
  integer :: iostat
  integer :: mode
  mode = MODE
  SCAN_FILE: do
    call stream_get_record (stream, buffer, iostat)
    select case (iostat)
    case (0)
      call split (buffer, line, "#")
      if (len_trim (line) == 0) cycle SCAN_FILE
      select case (char (extract (line, 1, 1)))
      case ("B", "b")
        mode = check_block_handling (line)
        call ifile_append (ifile, line // "$")
      case ("D", "d")
        mode = MODE_DATA
        call ifile_append (ifile, line // "$")
      case (" ")
        select case (mode)
        case (MODE_DATA)
          call ifile_append (ifile, "DATA" // line // "$")
        case (MODE_INFO)
          line = adjustl (line)
          call split (line, item, " ")
          call ifile_append (ifile, "INFO" // " " // item // " " &
            // ' ' // trim (adjustl (line)) // ' ' '$')
          end select
        case default
          call msg_message (char (line))
          call msg_fatal ("SLHA: Incomprehensible line")
        end select
      case (EOF)
        exit SCAN_FILE
      case default
        call msg_fatal ("SLHA: I/O error occured while reading SLHA input")
      end select
    end do SCAN_FILE
  end subroutine slha_preprocess
```

Return the mode that we should treat this block with. We need to recognize only those blocks that we actually use.

```

<SLHA: procedures>+≡
function check_block_handling (line) result (mode)
  integer :: mode
  type(string_t), intent(in) :: line
  type(string_t) :: buffer, key, block_name
  buffer = trim (line)
  call split (buffer, key, " ")
  buffer = adjustl (buffer)
  call split (buffer, block_name, " ")
  block_name = trim (adjustl (upper_case (block_name)))
  select case (char (block_name))
  case ("MODESEL", "MINPAR", "SMINPUTS")
    mode = MODE_DATA
  case ("MASS")
    mode = MODE_DATA
  case ("NMIX", "UMIX", "VMIX", "STOPMIX", "SBOTMIX", "STAUMIX")
    mode = MODE_DATA
  case ("NMHMIX", "NMAMIX", "NMNMIX", "NMSSMRUN")
    mode = MODE_DATA
  case ("ALPHA", "HMIX")
    mode = MODE_DATA
  case ("AU", "AD", "AE")
    mode = MODE_DATA
  case ("SPINFO", "DCINFO")
    mode = MODE_INFO
  case default
    mode = MODE_SKIP
  end select
end function check_block_handling

```

26.5.2 Lexer and syntax

```

<SLHA: variables>≡
type(syntax_t), target :: syntax_slha

```

```

<SLHA: public>≡
public :: syntax_slha_init

```

```

<SLHA: procedures>+≡
subroutine syntax_slha_init ()
  type(ifile_t) :: ifile
  call define_slha_syntax (ifile)
  call syntax_init (syntax_slha, ifile)
  call ifile_final (ifile)
end subroutine syntax_slha_init

```

```

<SLHA: public>+≡
public :: syntax_slha_final

```

```

<SLHA: procedures>+≡
subroutine syntax_slha_final ()

```

```

        call syntax_final (syntax_slha)
    end subroutine syntax_slha_final

<SLHA: public>+=
    public :: syntax_slha_write

<SLHA: procedures>+=
    subroutine syntax_slha_write (unit)
        integer, intent(in), optional :: unit
        call syntax_write (syntax_slha, unit)
    end subroutine syntax_slha_write

<SLHA: procedures>+=
    subroutine define_slha_syntax (ifile)
        type(ifile_t), intent(inout) :: ifile
        call ifile_append (ifile, "SEQ slha = chunk*")
        call ifile_append (ifile, "ALT chunk = block_def | decay_def")
        call ifile_append (ifile, "SEQ block_def = " &
            // "BLOCK block_spec '$' block_line*")
        call ifile_append (ifile, "KEY BLOCK")
        call ifile_append (ifile, "SEQ block_spec = block_name qvalue?")
        call ifile_append (ifile, "IDE block_name")
        call ifile_append (ifile, "SEQ qvalue = qname '=' real")
        call ifile_append (ifile, "IDE qname")
        call ifile_append (ifile, "KEY '='")
        call ifile_append (ifile, "REA real")
        call ifile_append (ifile, "KEY '$'")
        call ifile_append (ifile, "ALT block_line = block_data | block_info")
        call ifile_append (ifile, "SEQ block_data = DATA data_line '$'")
        call ifile_append (ifile, "KEY DATA")
        call ifile_append (ifile, "SEQ data_line = data_item+")
        call ifile_append (ifile, "ALT data_item = signed_number | number")
        call ifile_append (ifile, "SEQ signed_number = sign number")
        call ifile_append (ifile, "ALT sign = '+' | '-'")
        call ifile_append (ifile, "ALT number = integer | real")
        call ifile_append (ifile, "INT integer")
        call ifile_append (ifile, "KEY '-'")
        call ifile_append (ifile, "KEY '+'")
        call ifile_append (ifile, "SEQ block_info = INFO info_line '$'")
        call ifile_append (ifile, "KEY INFO")
        call ifile_append (ifile, "SEQ info_line = integer string_literal")
        call ifile_append (ifile, "QUO string_literal = '...'"")
        call ifile_append (ifile, "SEQ decay_def = " &
            // "DECAY decay_spec '$' decay_data*")
        call ifile_append (ifile, "KEY DECAY")
        call ifile_append (ifile, "SEQ decay_spec = pdg_code data_item")
        call ifile_append (ifile, "ALT pdg_code = signed_integer | integer")
        call ifile_append (ifile, "SEQ signed_integer = sign integer")
        call ifile_append (ifile, "SEQ decay_data = DATA decay_line '$'")
        call ifile_append (ifile, "SEQ decay_line = data_item integer pdg_code+")
    end subroutine define_slha_syntax

```

The SLHA specification allows for string data items in certain places. Currently, we do not interpret them, but the strings, which are not quoted, must be parsed

somehow. The hack for this problem is to allow essentially all characters as special characters, so the string can be read before it is discarded.

```

<SLHA: public>+=
    public :: lexer_init_slha

<SLHA: procedures>+=
    subroutine lexer_init_slha (lexer)
        type(lexer_t), intent(out) :: lexer
        call lexer_init (lexer, &
            comment_chars = "#", &
            quote_chars = "'", &
            quote_match = "'", &
            single_chars = "+-=$", &
            special_class = [ "" ], &
            keyword_list = syntax_get_keyword_list_ptr (syntax_slha), &
            upper_case_keywords = .true.) ! $
    end subroutine lexer_init_slha

```

26.5.3 Interpreter

Find blocks

From the parse tree, find the node that represents a particular block. If `required` is true, issue an error if not found. Since `block_name` is always invoked with capital letters, we have to capitalize `pn_block_name`.

```

<SLHA: procedures>+=
    function slha_get_block_ptr &
        (parse_tree, block_name, required) result (pn_block)
        type(parse_node_t), pointer :: pn_block
        type(parse_tree_t), intent(in) :: parse_tree
        type(string_t), intent(in) :: block_name
        logical, intent(in) :: required
        type(parse_node_t), pointer :: pn_root, pn_block_spec, pn_block_name
        pn_root => parse_tree_get_root_ptr (parse_tree)
        pn_block => parse_node_get_sub_ptr (pn_root)
        do while (associated (pn_block))
            select case (char (parse_node_get_rule_key (pn_block)))
            case ("block_def")
                pn_block_spec => parse_node_get_sub_ptr (pn_block, 2)
                pn_block_name => parse_node_get_sub_ptr (pn_block_spec)
                if (trim (adjustl (upper_case (parse_node_get_string &
                    (pn_block_name)))) == block_name) then
                    return
                end if
            end select
            pn_block => parse_node_get_next_ptr (pn_block)
        end do
        if (required) then
            call msg_fatal ("SLHA: block '" // char (block_name) // "' not found")
        end if
    end function slha_get_block_ptr

```


Scan the file for the first/next DECAY block.

```

<SLHA: procedures>+≡
function slha_get_first_decay_ptr (parse_tree) result (pn_decay)
  type(parse_node_t), pointer :: pn_decay
  type(parse_tree_t), intent(in) :: parse_tree
  type(parse_node_t), pointer :: pn_root
  pn_root => parse_tree_get_root_ptr (parse_tree)
  pn_decay => parse_node_get_sub_ptr (pn_root)
  do while (associated (pn_decay))
    select case (char (parse_node_get_rule_key (pn_decay)))
      case ("decay_def")
        return
    end select
    pn_decay => parse_node_get_next_ptr (pn_decay)
  end do
end function slha_get_first_decay_ptr

function slha_get_next_decay_ptr (pn_block) result (pn_decay)
  type(parse_node_t), pointer :: pn_decay
  type(parse_node_t), intent(in), target :: pn_block
  pn_decay => parse_node_get_next_ptr (pn_block)
  do while (associated (pn_decay))
    select case (char (parse_node_get_rule_key (pn_decay)))
      case ("decay_def")
        return
    end select
    pn_decay => parse_node_get_next_ptr (pn_decay)
  end do
end function slha_get_next_decay_ptr

```

Extract and transfer data from blocks

Given the parse node of a block, find the parse node of a particular switch or data line. Return this node and the node of the data item following the integer code.

```

<SLHA: procedures>+≡
subroutine slha_find_index_ptr (pn_block, pn_data, pn_item, code)
  type(parse_node_t), intent(in), target :: pn_block
  type(parse_node_t), intent(out), pointer :: pn_data
  type(parse_node_t), intent(out), pointer :: pn_item
  integer, intent(in) :: code
  pn_data => parse_node_get_sub_ptr (pn_block, 4)
  call slha_next_index_ptr (pn_data, pn_item, code)
end subroutine slha_find_index_ptr

subroutine slha_find_index_pair_ptr (pn_block, pn_data, pn_item, code1, code2)
  type(parse_node_t), intent(in), target :: pn_block
  type(parse_node_t), intent(out), pointer :: pn_data
  type(parse_node_t), intent(out), pointer :: pn_item
  integer, intent(in) :: code1, code2
  pn_data => parse_node_get_sub_ptr (pn_block, 4)
  call slha_next_index_pair_ptr (pn_data, pn_item, code1, code2)
end subroutine slha_find_index_pair_ptr

```

```
end subroutine slha_find_index_pair_ptr
```

Starting from the pointer to a data line, find a data line with the given integer code.

(SLHA: procedures)+≡

```
subroutine slha_next_index_ptr (pn_data, pn_item, code)
  type(parse_node_t), intent(inout), pointer :: pn_data
  integer, intent(in) :: code
  type(parse_node_t), intent(out), pointer :: pn_item
  type(parse_node_t), pointer :: pn_line, pn_code
  do while (associated (pn_data))
    pn_line => parse_node_get_sub_ptr (pn_data, 2)
    pn_code => parse_node_get_sub_ptr (pn_line)
    select case (char (parse_node_get_rule_key (pn_code)))
    case ("integer")
      if (parse_node_get_integer (pn_code) == code) then
        pn_item => parse_node_get_next_ptr (pn_code)
        return
      end if
    end select
    pn_data => parse_node_get_next_ptr (pn_data)
  end do
  pn_item => null ()
end subroutine slha_next_index_ptr
```

Starting from the pointer to a data line, find a data line with the given integer code pair.

(SLHA: procedures)+≡

```
subroutine slha_next_index_pair_ptr (pn_data, pn_item, code1, code2)
  type(parse_node_t), intent(inout), pointer :: pn_data
  integer, intent(in) :: code1, code2
  type(parse_node_t), intent(out), pointer :: pn_item
  type(parse_node_t), pointer :: pn_line, pn_code1, pn_code2
  do while (associated (pn_data))
    pn_line => parse_node_get_sub_ptr (pn_data, 2)
    pn_code1 => parse_node_get_sub_ptr (pn_line)
    select case (char (parse_node_get_rule_key (pn_code1)))
    case ("integer")
      if (parse_node_get_integer (pn_code1) == code1) then
        pn_code2 => parse_node_get_next_ptr (pn_code1)
        if (associated (pn_code2)) then
          select case (char (parse_node_get_rule_key (pn_code2)))
          case ("integer")
            if (parse_node_get_integer (pn_code2) == code2) then
              pn_item => parse_node_get_next_ptr (pn_code2)
              return
            end if
          end select
        end if
      end select
    end if
  end do
  pn_data => parse_node_get_next_ptr (pn_data)
end do
```

```

    pn_item => null ()
end subroutine slha_next_index_pair_ptr

```

Handle info data

Return all strings with index *i*. The result is an allocated string array. Since we do not know the number of matching entries in advance, we build an intermediate list which is transferred to the final array and deleted before exiting.

(*SLHA: procedures*) +=

```

subroutine retrieve_strings_in_block (pn_block, code, str_array)
  type(parse_node_t), intent(in), target :: pn_block
  integer, intent(in) :: code
  type(string_t), dimension(:), allocatable, intent(out) :: str_array
  type(parse_node_t), pointer :: pn_data, pn_item
  type :: str_entry_t
    type(string_t) :: str
    type(str_entry_t), pointer :: next => null ()
  end type str_entry_t
  type(str_entry_t), pointer :: first => null ()
  type(str_entry_t), pointer :: current => null ()
  integer :: n
  n = 0
  call slha_find_index_ptr (pn_block, pn_data, pn_item, code)
  if (associated (pn_item)) then
    n = n + 1
    allocate (first)
    first%str = parse_node_get_string (pn_item)
    current => first
    do while (associated (pn_data))
      pn_data => parse_node_get_next_ptr (pn_data)
      call slha_next_index_ptr (pn_data, pn_item, code)
      if (associated (pn_item)) then
        n = n + 1
        allocate (current%next)
        current => current%next
        current%str = parse_node_get_string (pn_item)
      end if
    end do
    allocate (str_array (n))
    n = 0
    do while (associated (first))
      n = n + 1
      current => first
      str_array(n) = current%str
      first => first%next
      deallocate (current)
    end do
  else
    allocate (str_array (0))
  end if
end subroutine retrieve_strings_in_block

```

Transfer data from SLHA to variables

Extract real parameter with index *i*. If it does not exist, retrieve it from the variable list, using the given name.

(SLHA: procedures)+≡

```
function get_parameter_in_block (pn_block, code, name, var_list) result (var)
  real(default) :: var
  type(parse_node_t), intent(in), target :: pn_block
  integer, intent(in) :: code
  type(string_t), intent(in) :: name
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_data, pn_item
  call slha_find_index_ptr (pn_block, pn_data, pn_item, code)
  if (associated (pn_item)) then
    var = get_real_parameter (pn_item)
  else
    var = var_list%get_rval (name)
  end if
end function get_parameter_in_block
```

Extract a real data item with index *i*. If it does exist, set it in the variable list, using the given name. If the variable is not present in the variable list, ignore it.

(SLHA: procedures)+≡

```
subroutine set_data_item (pn_block, code, name, var_list)
  type(parse_node_t), intent(in), target :: pn_block
  integer, intent(in) :: code
  type(string_t), intent(in) :: name
  type(var_list_t), intent(inout), target :: var_list
  type(parse_node_t), pointer :: pn_data, pn_item
  call slha_find_index_ptr (pn_block, pn_data, pn_item, code)
  if (associated (pn_item)) then
    call var_list_set_real &
      (var_list, name, get_real_parameter (pn_item), &
       is_known=.true., ignore=.true.)
  end if
end subroutine set_data_item
```

Extract a real matrix element with index *i, j*. If it does exist, set it in the variable list, using the given name. If the variable is not present in the variable list, ignore it.

(SLHA: procedures)+≡

```
subroutine set_matrix_element (pn_block, code1, code2, name, var_list)
  type(parse_node_t), intent(in), target :: pn_block
  integer, intent(in) :: code1, code2
  type(string_t), intent(in) :: name
  type(var_list_t), intent(inout), target :: var_list
  type(parse_node_t), pointer :: pn_data, pn_item
  call slha_find_index_pair_ptr (pn_block, pn_data, pn_item, code1, code2)
  if (associated (pn_item)) then
    call var_list_set_real &
      (var_list, name, get_real_parameter (pn_item), &
       is_known=.true., ignore=.true.)
  end if
end subroutine set_matrix_element
```

```

        end if
    end subroutine set_matrix_element

```

Transfer data from variables to SLHA

Get a real/integer parameter with index *i* from the variable list and write it to the current output file. In the integer case, we account for the fact that the variable is type real. If it does not exist, do nothing.

(SLHA: procedures)+≡

```

    subroutine write_integer_data_item (u, code, name, var_list, comment)
        integer, intent(in) :: u
        integer, intent(in) :: code
        type(string_t), intent(in) :: name
        type(var_list_t), intent(in) :: var_list
        character(*), intent(in) :: comment
        integer :: item
        if (var_list%contains (name)) then
            item = nint (var_list%get_rval (name))
            call write_integer_parameter (u, code, item, comment)
        end if
    end subroutine write_integer_data_item

    subroutine write_real_data_item (u, code, name, var_list, comment)
        integer, intent(in) :: u
        integer, intent(in) :: code
        type(string_t), intent(in) :: name
        type(var_list_t), intent(in) :: var_list
        character(*), intent(in) :: comment
        real(default) :: item
        if (var_list%contains (name)) then
            item = var_list%get_rval (name)
            call write_real_parameter (u, code, item, comment)
        end if
    end subroutine write_real_data_item

```

Get a real data item with two integer indices from the variable list and write it to the current output file. If it does not exist, do nothing.

(SLHA: procedures)+≡

```

    subroutine write_matrix_element (u, code1, code2, name, var_list, comment)
        integer, intent(in) :: u
        integer, intent(in) :: code1, code2
        type(string_t), intent(in) :: name
        type(var_list_t), intent(in) :: var_list
        character(*), intent(in) :: comment
        real(default) :: item
        if (var_list%contains (name)) then
            item = var_list%get_rval (name)
            call write_real_matrix_element (u, code1, code2, item, comment)
        end if
    end subroutine write_matrix_element

```

26.5.4 Auxiliary function

Write a block header.

```
(SLHA: procedures)+≡
subroutine write_block_header (u, name, comment)
  integer, intent(in) :: u
  character(*), intent(in) :: name, comment
  write (u, "(A,1x,A,3x,'#',1x,A)") "BLOCK", name, comment
end subroutine write_block_header
```

Extract a real parameter that may be defined real or integer, signed or unsigned.

```
(SLHA: procedures)+≡
function get_real_parameter (pn_item) result (var)
  real(default) :: var
  type(parse_node_t), intent(in), target :: pn_item
  type(parse_node_t), pointer :: pn_sign, pn_var
  integer :: sign
  select case (char (parse_node_get_rule_key (pn_item)))
  case ("signed_number")
    pn_sign => parse_node_get_sub_ptr (pn_item)
    pn_var => parse_node_get_next_ptr (pn_sign)
    select case (char (parse_node_get_key (pn_sign)))
    case ("+"); sign = +1
    case ("-"); sign = -1
    end select
  case default
    sign = +1
    pn_var => pn_item
  end select
  select case (char (parse_node_get_rule_key (pn_var)))
  case ("integer"); var = sign * parse_node_get_integer (pn_var)
  case ("real"); var = sign * parse_node_get_real (pn_var)
  end select
end function get_real_parameter
```

Auxiliary: Extract an integer parameter that may be defined signed or unsigned.
A real value is an error.

```
(SLHA: procedures)+≡
function get_integer_parameter (pn_item) result (var)
  integer :: var
  type(parse_node_t), intent(in), target :: pn_item
  type(parse_node_t), pointer :: pn_sign, pn_var
  integer :: sign
  select case (char (parse_node_get_rule_key (pn_item)))
  case ("signed_integer")
    pn_sign => parse_node_get_sub_ptr (pn_item)
    pn_var => parse_node_get_next_ptr (pn_sign)
    select case (char (parse_node_get_key (pn_sign)))
    case ("+"); sign = +1
    case ("-"); sign = -1
    end select
  case ("integer")
    sign = +1
```

```

        pn_var => pn_item
    case default
        call parse_node_write (pn_var)
        call msg_error ("SLHA: Integer parameter expected")
        var = 0
        return
    end select
    var = sign * parse_node_get_integer (pn_var)
end function get_integer_parameter

```

Write an integer parameter with a single index directly to file, using the required output format.

<SLHA: procedures>+≡

```

subroutine write_integer_parameter (u, code, item, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code
    integer, intent(in) :: item
    character(*), intent(in) :: comment
1   format (1x, I9, 3x, 3x, I9, 4x, 3x, '#', 1x, A)
    write (u, 1) code, item, comment
end subroutine write_integer_parameter

```

Write a real parameter with two indices directly to file, using the required output format.

<SLHA: procedures>+≡

```

subroutine write_real_parameter (u, code, item, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code
    real(default), intent(in) :: item
    character(*), intent(in) :: comment
1   format (1x, I9, 3x, 1P, E16.8, 0P, 3x, '#', 1x, A)
    write (u, 1) code, item, comment
end subroutine write_real_parameter

```

Write a real parameter with a single index directly to file, using the required output format.

<SLHA: procedures>+≡

```

subroutine write_real_matrix_element (u, code1, code2, item, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code1, code2
    real(default), intent(in) :: item
    character(*), intent(in) :: comment
1   format (1x, I2, 1x, I2, 3x, 1P, E16.8, 0P, 3x, '#', 1x, A)
    write (u, 1) code1, code2, item, comment
end subroutine write_real_matrix_element

```

The concrete SLHA interpreter

SLHA codes for particular physics models

<SLHA: parameters>+≡

```
integer, parameter :: MDL_MSSM = 0
integer, parameter :: MDL_NMSSM = 1
```

Take the parse tree and extract relevant data. Select the correct model and store all data that is present in the appropriate variable list. Finally, update the variable record.

(SLHA: procedures)+≡

```
subroutine slha_interpret_parse_tree &
  (parse_tree, model, input, spectrum, decays)
  type(parse_tree_t), intent(in) :: parse_tree
  type(model_t), intent(inout), target :: model
  logical, intent(in) :: input, spectrum, decays
  logical :: errors
  integer :: mssm_type
  call slha_handle_MODSEL (parse_tree, model, mssm_type)
  if (input) then
    call slha_handle_SMINPUTS (parse_tree, model)
    call slha_handle_MINPAR (parse_tree, model, mssm_type)
  end if
  if (spectrum) then
    call slha_handle_info_block (parse_tree, "SPINFO", errors)
    if (errors) return
    call slha_handle_MASS (parse_tree, model)
    call slha_handle_matrix_block (parse_tree, "NMIX", "mn_", 4, 4, model)
    call slha_handle_matrix_block (parse_tree, "NMNMIX", "mixn_", 5, 5, model)
    call slha_handle_matrix_block (parse_tree, "UMIX", "mu_", 2, 2, model)
    call slha_handle_matrix_block (parse_tree, "VMIX", "mv_", 2, 2, model)
    call slha_handle_matrix_block (parse_tree, "STOPMIX", "mt_", 2, 2, model)
    call slha_handle_matrix_block (parse_tree, "SBOTMIX", "mb_", 2, 2, model)
    call slha_handle_matrix_block (parse_tree, "STAUMIX", "ml_", 2, 2, model)
    call slha_handle_matrix_block (parse_tree, "NMHMX", "mixh0_", 3, 3, model)
    call slha_handle_matrix_block (parse_tree, "NMAMIX", "mixa0_", 2, 3, model)
    call slha_handle_ALPHA (parse_tree, model)
    call slha_handle_HMIX (parse_tree, model)
    call slha_handle_NMSSMRUN (parse_tree, model)
    call slha_handle_matrix_block (parse_tree, "AU", "Au_", 3, 3, model)
    call slha_handle_matrix_block (parse_tree, "AD", "Ad_", 3, 3, model)
    call slha_handle_matrix_block (parse_tree, "AE", "Ae_", 3, 3, model)
  end if
  if (decays) then
    call slha_handle_info_block (parse_tree, "DCINFO", errors)
    if (errors) return
    call slha_handle_decays (parse_tree, model)
  end if
end subroutine slha_interpret_parse_tree
```

Info blocks

Handle the informational blocks SPINFO and DCINFO. The first two items are program name and version. Items with index 3 are warnings. Items with index 4 are errors. We reproduce these as WHIZARD warnings and errors.

(SLHA: procedures)+≡

```
subroutine slha_handle_info_block (parse_tree, block_name, errors)
```



```

type(parse_tree_t), intent(in) :: parse_tree
character(*), intent(in) :: block_name
logical, intent(out) :: errors
type(parse_node_t), pointer :: pn_block
type(string_t), dimension(:), allocatable :: msg
integer :: i
pn_block => slha_get_block_ptr &
    (parse_tree, var_str (block_name), required=.true.)
if (.not. associated (pn_block)) then
    call msg_error ("SLHA: Missing info block '" &
        // trim (block_name) // "'; ignored.")
    errors = .true.
    return
end if
select case (block_name)
case ("SPINFO")
    call msg_message ("SLHA: SUSY spectrum program info:")
case ("DCINFO")
    call msg_message ("SLHA: SUSY decay program info:")
end select
call retrieve_strings_in_block (pn_block, 1, msg)
do i = 1, size (msg)
    call msg_message ("SLHA: " // char (msg(i)))
end do
call retrieve_strings_in_block (pn_block, 2, msg)
do i = 1, size (msg)
    call msg_message ("SLHA: " // char (msg(i)))
end do
call retrieve_strings_in_block (pn_block, 3, msg)
do i = 1, size (msg)
    call msg_warning ("SLHA: " // char (msg(i)))
end do
call retrieve_strings_in_block (pn_block, 4, msg)
do i = 1, size (msg)
    call msg_error ("SLHA: " // char (msg(i)))
end do
errors = size (msg) > 0
end subroutine slha_handle_info_block

```

MODSEL

Handle the overall model definition. Only certain models are recognized. The soft-breaking model templates that determine the set of input parameters:

<SLHA: parameters>+≡

```

integer, parameter :: MSSM_GENERIC = 0
integer, parameter :: MSSM_SUGRA = 1
integer, parameter :: MSSM_GMSB = 2
integer, parameter :: MSSM_AMSB = 3

```

<SLHA: procedures>+≡

```

subroutine slha_handle_MODSEL (parse_tree, model, mssm_type)
    type(parse_tree_t), intent(in) :: parse_tree

```

```

type(model_t), intent(in), target :: model
integer, intent(out) :: mssm_type
type(parse_node_t), pointer :: pn_block, pn_data, pn_item
type(string_t) :: model_name
pn_block => slha_get_block_ptr &
    (parse_tree, var_str ("MODSEL"), required=.true.)
call slha_find_index_ptr (pn_block, pn_data, pn_item, 1)
if (associated (pn_item)) then
    mssm_type = get_integer_parameter (pn_item)
else
    mssm_type = MSSM_GENERIC
end if
call slha_find_index_ptr (pn_block, pn_data, pn_item, 3)
if (associated (pn_item)) then
    select case (parse_node_get_integer (pn_item))
    case (MDL_MSSM); model_name = "MSSM"
    case (MDL_NMSSM); model_name = "NMSSM"
    case default
        call msg_fatal ("SLHA: unknown model code in MODSEL")
        return
    end select
else
    model_name = "MSSM"
end if
call slha_find_index_ptr (pn_block, pn_data, pn_item, 4)
if (associated (pn_item)) then
    call msg_fatal (" R-parity violation is currently not supported by WHIZARD.")
end if
call slha_find_index_ptr (pn_block, pn_data, pn_item, 5)
if (associated (pn_item)) then
    call msg_fatal (" CP violation is currently not supported by WHIZARD.")
end if
select case (char (model_name))
case ("MSSM")
    select case (char (model%get_name ()))
    case ("MSSM", "MSSM_CKM", "MSSM_Grav", "MSSM_Hgg")
        model_name = model%get_name ()
    case default
        call msg_fatal ("Selected model '" &
            // char (model%get_name ()) // "' does not match model '" &
            // char (model_name) // "' in SLHA input file.")
        return
    end select
case ("NMSSM")
    select case (char (model%get_name ()))
    case ("NMSSM", "NMSSM_CKM", "NMSSM_Hgg")
        model_name = model%get_name ()
    case default
        call msg_fatal ("Selected model '" &
            // char (model%get_name ()) // "' does not match model '" &
            // char (model_name) // "' in SLHA input file.")
        return
    end select
case default

```

```

        call msg_bug ("SLHA model name '" &
                     // char (model_name) // "' not recognized.")
        return
    end select
    call msg_message ("SLHA: Initializing model '" // char (model_name) // "'")
end subroutine slha_handle_MODSEL

```

Write a MODSEL block, based on the contents of the current model.

(SLHA: procedures)+≡

```

subroutine slha_write_MODSEL (u, model, mssm_type)
    integer, intent(in) :: u
    type(model_t), intent(in), target :: model
    integer, intent(out) :: mssm_type
    type(var_list_t), pointer :: var_list
    integer :: model_id
    type(string_t) :: mtype_string
    var_list => model%get_var_list_ptr ()
    if (var_list%contains (var_str ("mtype"))) then
        mssm_type = nint (var_list%get_rval (var_str ("mtype")))
    else
        call msg_error ("SLHA: parameter 'mtype' (SUSY breaking scheme) " &
                       // "is unknown in current model, no SLHA output possible")
        mssm_type = -1
        return
    end if
    call write_block_header (u, "MODSEL", "SUSY model selection")
    select case (mssm_type)
    case (0); mtype_string = "Generic MSSM"
    case (1); mtype_string = "SUGRA"
    case (2); mtype_string = "GMSB"
    case (3); mtype_string = "AMSB"
    case default
        mtype_string = "unknown"
    end select
    call write_integer_parameter (u, 1, mssm_type, &
                                "SUSY-breaking scheme: " // char (mtype_string))
    select case (char (model%get_name ()))
    case ("MSSM"); model_id = MDL_MSSM
    case ("NMSSM"); model_id = MDL_NMSSM
    case default
        model_id = 0
    end select
    call write_integer_parameter (u, 3, model_id, &
                                "SUSY model type: " // char (model%get_name ()))
end subroutine slha_write_MODSEL

```

SMINPUTS

Read SM parameters and update the variable list accordingly. If a parameter is not defined in the block, we use the previous value from the model variable list. For the basic parameters we have to do a small recalculation, since SLHA uses

the G_F - α - m_Z scheme, while WHIZARD derives them from G_F , m_W , and m_Z .

(SLHA: procedures)+≡

```
subroutine slha_handle_SMINPUTS (parse_tree, model)
  type(parse_tree_t), intent(in) :: parse_tree
  type(model_t), intent(inout), target :: model
  type(parse_node_t), pointer :: pn_block
  real(default) :: alpha_em_i, GF, alphas, mZ
  real(default) :: ee, vv, cw_sw, cw2, mW
  real(default) :: mb, mtop, mtau
  type(var_list_t), pointer :: var_list
  var_list => model%get_var_list_ptr ()
  pn_block => slha_get_block_ptr &
    (parse_tree, var_str ("SMINPUTS"), required=.true.)
  if (.not. (associated (pn_block))) return
  alpha_em_i = &
    get_parameter_in_block (pn_block, 1, var_str ("alpha_em_i"), var_list)
  GF = get_parameter_in_block (pn_block, 2, var_str ("GF"), var_list)
  alphas = &
    get_parameter_in_block (pn_block, 3, var_str ("alphas"), var_list)
  mZ = get_parameter_in_block (pn_block, 4, var_str ("mZ"), var_list)
  mb = get_parameter_in_block (pn_block, 5, var_str ("mb"), var_list)
  mtop = get_parameter_in_block (pn_block, 6, var_str ("mtop"), var_list)
  mtau = get_parameter_in_block (pn_block, 7, var_str ("mtau"), var_list)
  ee = sqrt (4 * pi / alpha_em_i)
  vv = 1 / sqrt (sqrt (2._default) * GF)
  cw_sw = ee * vv / (2 * mZ)
  if (2*cw_sw <= 1) then
    cw2 = (1 + sqrt (1 - 4 * cw_sw**2)) / 2
    mW = mZ * sqrt (cw2)
    call var_list_set_real (var_list, var_str ("GF"), GF, .true.)
    call var_list_set_real (var_list, var_str ("mZ"), mZ, .true.)
    call var_list_set_real (var_list, var_str ("mW"), mW, .true.)
    call var_list_set_real (var_list, var_str ("mtau"), mtau, .true.)
    call var_list_set_real (var_list, var_str ("mb"), mb, .true.)
    call var_list_set_real (var_list, var_str ("mtop"), mtop, .true.)
    call var_list_set_real (var_list, var_str ("alphas"), alphas, .true.)
  else
    call msg_fatal ("SLHA: Unphysical SM parameter values")
    return
  end if
end subroutine slha_handle_SMINPUTS
```

Write a SMINPUTS block.

(SLHA: procedures)+≡

```
subroutine slha_write_SMINPUTS (u, model)
  integer, intent(in) :: u
  type(model_t), intent(in), target :: model
  type(var_list_t), pointer :: var_list
  var_list => model%get_var_list_ptr ()
  call write_block_header (u, "SMINPUTS", "SM input parameters")
  call write_real_data_item (u, 1, var_str ("alpha_em_i"), var_list, &
    "Inverse electromagnetic coupling alpha (Z pole)")
  call write_real_data_item (u, 2, var_str ("GF"), var_list, &
```

```

        "Fermi constant")
    call write_real_data_item (u, 3, var_str ("alphas"), var_list, &
        "Strong coupling alpha_s (Z pole)")
    call write_real_data_item (u, 4, var_str ("mZ"), var_list, &
        "Z mass")
    call write_real_data_item (u, 5, var_str ("mb"), var_list, &
        "b running mass (at mb)")
    call write_real_data_item (u, 6, var_str ("mtop"), var_list, &
        "top mass")
    call write_real_data_item (u, 7, var_str ("mtau"), var_list, &
        "tau mass")
end subroutine slha_write_SMINPUTS

```

MINPAR

The block of SUSY input parameters. They are accessible to WHIZARD, but they only get used when an external spectrum generator is invoked. The precise set of parameters depends on the type of SUSY breaking, which by itself is one of the parameters.

(SLHA: procedures) +=

```

subroutine slha_handle_MINPAR (parse_tree, model, mssm_type)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    integer, intent(in) :: mssm_type
    type(var_list_t), pointer :: var_list
    type(parse_node_t), pointer :: pn_block
    var_list => model%get_var_list_ptr ()
    call var_list_set_real (var_list, &
        var_str ("mtype"), real(mssm_type, default), is_known=.true.)
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("MINPAR"), required=.true.)
    select case (mssm_type)
    case (MSSM_SUGRA)
        call set_data_item (pn_block, 1, var_str ("m_zero"), var_list)
        call set_data_item (pn_block, 2, var_str ("m_half"), var_list)
        call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
        call set_data_item (pn_block, 4, var_str ("sgn_mu"), var_list)
        call set_data_item (pn_block, 5, var_str ("A0"), var_list)
    case (MSSM_GMSB)
        call set_data_item (pn_block, 1, var_str ("Lambda"), var_list)
        call set_data_item (pn_block, 2, var_str ("M_mes"), var_list)
        call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
        call set_data_item (pn_block, 4, var_str ("sgn_mu"), var_list)
        call set_data_item (pn_block, 5, var_str ("N_5"), var_list)
        call set_data_item (pn_block, 6, var_str ("c_grav"), var_list)
    case (MSSM_AMSB)
        call set_data_item (pn_block, 1, var_str ("m_zero"), var_list)
        call set_data_item (pn_block, 2, var_str ("m_grav"), var_list)
        call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
        call set_data_item (pn_block, 4, var_str ("sgn_mu"), var_list)
    case default
        call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
    end select
end subroutine

```

```

end select
end subroutine slha_handle_MINPAR

```

Write a MINPAR block as appropriate for the current model type.

(*SLHA: procedures*) +=

```

subroutine slha_write_MINPAR (u, model, mssm_type)
  integer, intent(in) :: u
  type(model_t), intent(in), target :: model
  integer, intent(in) :: mssm_type
  type(var_list_t), pointer :: var_list
  var_list => model%get_var_list_ptr ()
  call write_block_header (u, "MINPAR", "Basic SUSY input parameters")
  select case (mssm_type)
  case (MSSM_SUGRA)
    call write_real_data_item (u, 1, var_str ("m_zero"), var_list, &
      "Common scalar mass")
    call write_real_data_item (u, 2, var_str ("m_half"), var_list, &
      "Common gaugino mass")
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
      "tan(beta)")
    call write_integer_data_item (u, 4, &
      var_str ("sgn_mu"), var_list, &
      "Sign of mu")
    call write_real_data_item (u, 5, var_str ("A0"), var_list, &
      "Common trilinear coupling")
  case (MSSM_GMSB)
    call write_real_data_item (u, 1, var_str ("Lambda"), var_list, &
      "Soft-breaking scale")
    call write_real_data_item (u, 2, var_str ("M_mes"), var_list, &
      "Messenger scale")
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
      "tan(beta)")
    call write_integer_data_item (u, 4, &
      var_str ("sgn_mu"), var_list, &
      "Sign of mu")
    call write_integer_data_item (u, 5, var_str ("N_5"), var_list, &
      "Messenger index")
    call write_real_data_item (u, 6, var_str ("c_grav"), var_list, &
      "Gravitino mass factor")
  case (MSSM_AMSB)
    call write_real_data_item (u, 1, var_str ("m_zero"), var_list, &
      "Common scalar mass")
    call write_real_data_item (u, 2, var_str ("m_grav"), var_list, &
      "Gravitino mass")
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
      "tan(beta)")
    call write_integer_data_item (u, 4, &
      var_str ("sgn_mu"), var_list, &
      "Sign of mu")
  case default
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
      "tan(beta)")
  end select
end subroutine slha_write_MINPAR

```

Mass spectrum

Set masses. Since the particles are identified by PDG code, read the line and try to set the appropriate particle mass in the current model. At the end, update parameters, just in case the W or Z mass was included.

(SLHA: procedures)+≡

```
subroutine slha_handle_MASS (parse_tree, model)
  type(parse_tree_t), intent(in) :: parse_tree
  type(model_t), intent(inout), target :: model
  type(parse_node_t), pointer :: pn_block, pn_data, pn_line, pn_code
  type(parse_node_t), pointer :: pn_mass
  integer :: pdg
  real(default) :: mass
  pn_block => slha_get_block_ptr &
    (parse_tree, var_str ("MASS"), required=.true.)
  if (.not. (associated (pn_block))) return
  pn_data => parse_node_get_sub_ptr (pn_block, 4)
  do while (associated (pn_data))
    pn_line => parse_node_get_sub_ptr (pn_data, 2)
    pn_code => parse_node_get_sub_ptr (pn_line)
    if (associated (pn_code)) then
      pdg = get_integer_parameter (pn_code)
      pn_mass => parse_node_get_next_ptr (pn_code)
      if (associated (pn_mass)) then
        mass = get_real_parameter (pn_mass)
        call model%set_field_mass (pdg, mass)
      else
        call msg_error ("SLHA: Block MASS: Missing mass value")
      end if
    else
      call msg_error ("SLHA: Block MASS: Missing PDG code")
    end if
    pn_data => parse_node_get_next_ptr (pn_data)
  end do
end subroutine slha_handle_MASS
```

Widths

Set widths. For each DECAY block, extract the header, read the PDG code and width, and try to set the appropriate particle width in the current model.

(SLHA: procedures)+≡

```
subroutine slha_handle_decays (parse_tree, model)
  type(parse_tree_t), intent(in) :: parse_tree
  type(model_t), intent(inout), target :: model
  type(parse_node_t), pointer :: pn_decay, pn_decay_spec, pn_code, pn_width
  integer :: pdg
  real(default) :: width
  pn_decay => slha_get_first_decay_ptr (parse_tree)
  do while (associated (pn_decay))
    pn_decay_spec => parse_node_get_sub_ptr (pn_decay, 2)
```

```

        pn_code => parse_node_get_sub_ptr (pn_decay_spec)
        pdg = get_integer_parameter (pn_code)
        pn_width => parse_node_get_next_ptr (pn_code)
        width = get_real_parameter (pn_width)
        call model%set_field_width (pdg, width)
        pn_decay => slha_get_next_decay_ptr (pn_decay)
    end do
end subroutine slha_handle_decays

```

Mixing matrices

Read mixing matrices. We can treat all matrices by a single procedure if we just know the block name, variable prefix, and matrix dimension. The matrix dimension must be less than 10. For the pseudoscalar Higgses in NMSSM-type models we need off-diagonal matrices, so we generalize the definition.

(*SLHA: procedures*) +=

```

subroutine slha_handle_matrix_block &
    (parse_tree, block_name, var_prefix, dim1, dim2, model)
    type(parse_tree_t), intent(in) :: parse_tree
    character(*), intent(in) :: block_name, var_prefix
    integer, intent(in) :: dim1, dim2
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block
    type(var_list_t), pointer :: var_list
    integer :: i, j
    character(len=len(var_prefix)+2) :: var_name
    var_list => model%get_var_list_ptr ()
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str (block_name), required=.false.)
    if (.not. (associated (pn_block))) return
    do i = 1, dim1
        do j = 1, dim2
            write (var_name, "(A,I1,I1)") var_prefix, i, j
            call set_matrix_element (pn_block, i, j, var_str (var_name), var_list)
        end do
    end do
end subroutine slha_handle_matrix_block

```

Higgs data

Read the block ALPHA which holds just the Higgs mixing angle.

(*SLHA: procedures*) +=

```

subroutine slha_handle_ALPHA (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block, pn_line, pn_data, pn_item
    type(var_list_t), pointer :: var_list
    real(default) :: al_h
    var_list => model%get_var_list_ptr ()
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("ALPHA"), required=.false.)

```



```

    if (.not. (associated (pn_block))) return
    pn_data => parse_node_get_sub_ptr (pn_block, 4)
    pn_line => parse_node_get_sub_ptr (pn_data, 2)
    pn_item => parse_node_get_sub_ptr (pn_line)
    if (associated (pn_item)) then
        al_h = get_real_parameter (pn_item)
        call var_list_set_real (var_list, var_str ("al_h"), al_h, &
            is_known=.true., ignore=.true.)
    end if
end subroutine slha_handle_ALPHA

```

Read the block HMX for the Higgs mixing parameters

<SLHA: procedures>+≡

```

subroutine slha_handle_HMX (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block
    type(var_list_t), pointer :: var_list
    var_list => model%get_var_list_ptr ()
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("HMX"), required=.false.)
    if (.not. (associated (pn_block))) return
    call set_data_item (pn_block, 1, var_str ("mu_h"), var_list)
    call set_data_item (pn_block, 2, var_str ("tanb_h"), var_list)
end subroutine slha_handle_HMX

```

Read the block NMSSMRUN for the specific NMSSM parameters

<SLHA: procedures>+≡

```

subroutine slha_handle_NMSSMRUN (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block
    type(var_list_t), pointer :: var_list
    var_list => model%get_var_list_ptr ()
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("NMSSMRUN"), required=.false.)
    if (.not. (associated (pn_block))) return
    call set_data_item (pn_block, 1, var_str ("ls"), var_list)
    call set_data_item (pn_block, 2, var_str ("ks"), var_list)
    call set_data_item (pn_block, 3, var_str ("a_ls"), var_list)
    call set_data_item (pn_block, 4, var_str ("a_ks"), var_list)
    call set_data_item (pn_block, 5, var_str ("nmu"), var_list)
end subroutine slha_handle_NMSSMRUN

```

26.5.5 Parser

Read a SLHA file from stream, including preprocessing, and make up a parse tree.

<SLHA: procedures>+≡

```

subroutine slha_parse_stream (stream, parse_tree)
    type(stream_t), intent(inout), target :: stream

```

```

type(parse_tree_t), intent(out) :: parse_tree
type(ifile_t) :: ifile
type(lexer_t) :: lexer
type(stream_t), target :: stream_tmp
call slha_preprocess (stream, ifile)
call stream_init (stream_tmp, ifile)
call lexer_init_slha (lexer)
call lexer_assign_stream (lexer, stream_tmp)
call parse_tree_init (parse_tree, syntax_slha, lexer)
call lexer_final (lexer)
call stream_final (stream_tmp)
call ifile_final (ifile)
end subroutine slha_parse_stream

```

Read a SLHA file chosen by name. Check first the current directory, then the directory where SUSY input files should be located.

<SLHA: procedures>+≡

```

subroutine slha_parse_file (file, os_data, parse_tree)
type(string_t), intent(in) :: file
type(os_data_t), intent(in) :: os_data
type(parse_tree_t), intent(out) :: parse_tree
logical :: exist
type(string_t) :: filename
type(stream_t), target :: stream
call msg_message ("Reading SLHA input file '" // char (file) // "'")
filename = file
inquire (file=char(filename), exist=exist)
if (.not. exist) then
filename = os_data%whizard_susypath // "/" // file
inquire (file=char(filename), exist=exist)
if (.not. exist) then
call msg_fatal ("SLHA input file '" // char (file) // "' not found")
return
end if
end if
call stream_init (stream, char (filename))
call slha_parse_stream (stream, parse_tree)
call stream_final (stream)
end subroutine slha_parse_file

```

26.5.6 API

Read the SLHA file, parse it, and interpret the parse tree. The model parameters retrieved from the file will be inserted into the appropriate model, which is loaded and modified in the background. The pointer to this model is returned as the last argument.

<SLHA: public>+≡

```

public :: slha_read_file

```

<SLHA: procedures>+≡

```

subroutine slha_read_file &
(file, os_data, model, input, spectrum, decays)

```

```

type(string_t), intent(in) :: file
type(os_data_t), intent(in) :: os_data
type(model_t), intent(inout), target :: model
logical, intent(in) :: input, spectrum, decays
type(parse_tree_t) :: parse_tree
call slha_parse_file (file, os_data, parse_tree)
if (associated (parse_tree_get_root_ptr (parse_tree))) then
    call slha_interpret_parse_tree &
        (parse_tree, model, input, spectrum, decays)
    call parse_tree_final (parse_tree)
    call model%update_parameters ()
end if
end subroutine slha_read_file

```

Write the SLHA contents, as far as possible, to external file.

```

<SLHA: public>+=
public :: slha_write_file

<SLHA: procedures>+=
subroutine slha_write_file (file, model, input, spectrum, decays)
    type(string_t), intent(in) :: file
    type(model_t), target, intent(in) :: model
    logical, intent(in) :: input, spectrum, decays
    integer :: mssm_type
    integer :: u
    u = free_unit ()
    call msg_message ("Writing SLHA output file '" // char (file) // "'")
    open (unit=u, file=char(file), action="write", status="replace")
    write (u, "(A)")  "# SUSY Les Houches Accord"
    write (u, "(A)")  "# Output generated by " // trim (VERSION_STRING)
    call slha_write_MODSEL (u, model, mssm_type)
    if (input) then
        call slha_write_SMINPUTS (u, model)
        call slha_write_MINPAR (u, model, mssm_type)
    end if
    if (spectrum) then
        call msg_bug ("SLHA: spectrum output not supported yet")
    end if
    if (decays) then
        call msg_bug ("SLHA: decays output not supported yet")
    end if
    close (u)
end subroutine slha_write_file

```

26.5.7 Unit tests

```

<SLHA: public>+=
public :: slha_test

<SLHA: procedures>+=
subroutine slha_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results

```

```

    <SLHA: execute tests>
end subroutine slha_test

```

Checking the basics of the SLHA interface.

```

<SLHA: execute tests>≡
    call test (slha_1, "slha_1", &
               "check SLHA interface", &
               u, results)

<SLHA: tests>≡
subroutine slha_1 (u)
    integer, intent(in) :: u
    type(os_data_t), pointer :: os_data => null ()
    type(parse_tree_t), pointer :: parse_tree => null ()
    integer :: u_file, iostat
    character(80) :: buffer
    character(*), parameter :: file_slha = "slha_test.dat"
    type(model_list_t) :: model_list
    type(model_t), pointer :: model => null ()

    write (u, "(A)")  "* Test output: SLHA Interface"
    write (u, "(A)")  "* Purpose: test SLHA file reading and writing"
    write (u, "(A)")

    write (u, "(A)")  "* Initializing"
    write (u, "(A)")

    allocate (os_data)
    allocate (parse_tree)
    call os_data_init (os_data)
    call syntax_model_file_init ()
    call model_list%read_model &
         (var_str("MSSM"), var_str("MSSM.mdl"), os_data, model)
    call syntax_slha_init ()

    write (u, "(A)")  "* Reading SLHA file spslap_decays.slha"
    write (u, "(A)")

    call slha_parse_file (var_str ("spslap_decays.slha"), os_data, parse_tree)

    write (u, "(A)")  "* Writing the parse tree:"
    write (u, "(A)")

    call parse_tree_write (parse_tree, u)

    write (u, "(A)")  "* Interpreting the parse tree"
    write (u, "(A)")

    call slha_interpret_parse_tree (parse_tree, model, &
                                     input=.true., spectrum=.true., decays=.true.)
    call parse_tree_final (parse_tree)

    write (u, "(A)")  "* Writing out the list of variables (reals only):"
    write (u, "(A)")

```

```

call var_list_write (model%get_var_list_ptr (), &
    only_type = V_REAL, unit = u)

write (u, "(A)")
write (u, "(A)")  "* Writing SLHA output to '" // file_slha // "'"
write (u, "(A)")

call slha_write_file (var_str (file_slha), model, input=.true., &
    spectrum=.false., decays=.false.)
u_file = free_unit ()
open (u_file, file = file_slha, action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat)  buffer
    if (buffer(1:37) == "# Output generated by WHIZARD version") then
        buffer = "[...]"
    end if
    if (iostat /= 0) exit
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"
write (u, "(A)")

call parse_tree_final (parse_tree)
deallocate (parse_tree)
deallocate (os_data)

write (u, "(A)")  "* Test output end: slha_1"
write (u, "(A)")

end subroutine slha_1

```

Chapter 27

Integration and Process Objects

This is the central part of the WHIZARD package. It provides the functionality for evaluating structure functions, kinematics and matrix elements, integration and event generation. It combines the various parts that deal with those tasks individually and organizes the data transfer between them.

subvt_expr This enables process observables as (abstract) expressions, to be evaluated for each process call.

parton_states A `parton_state_t` object represents an elementary partonic interaction. There are two versions: one for the isolated elementary process, one for the elementary process convoluted with the structure-function chain. The parton state is an effective state. It needs not coincide with the seed-kinematics state which is used in evaluating phase space.

processes Here, all pieces are combined for the purpose of evaluating the elementary processes. The whole algorithm is coded in terms of abstract data types as defined in the appropriate modules: `prc_core` for matrix-element evaluation, `prc_core_def` for the associated configuration and driver, `sf_base` for beams and structure-functions, `phs_base` for phase space, and `mci_base` for integration and event generation.

process_stacks Process stacks collect process objects.

27.1 Process observables

We define an abstract `subvt_expr_t` object as an extension of the `subvt_t` type. The object contains a local variable list, variable instances (as targets for pointers in the variable list), and evaluation trees. The evaluation trees reference both the variables and the `subvt`.

There are two instances of the abstract type: one for process instances, one for physical events. Both have a common logical expression `selection` which determines whether the object passes user-defined cuts.

The intention is that we fill the `subvt_t` base object and compute the variables once we have evaluated a kinematical phase space point (or a complete

event). We then evaluate the expressions and can use the results in further calculations.

The `process_expr_t` extension contains furthermore scale and weight expressions. The `event_expr_t` extension contains a reweighting-factor expression and a logical expression for event analysis. In practice, we will link the variable list of the `event_obs` object to the variable list of the currently active `process_obs` object, such that the process variables are available to both objects. Event variables are meaningful only for physical events.

Note that there are unit tests, but they are deferred to the `expr_tests` module.

```

<subevt_expr.f90>≡
  <File header>
  module subevt_expr

    <Use kinds>
    <Use strings>
    use io_units
    use format_utils, only: write_separator
    use diagnostics
    use lorentz
    use subevents
    use variables
    use flavors
    use quantum_numbers
    use interactions
    use particles
    use expr_base

    <Standard module head>

    <Subevt expr: public>

    <Subevt expr: types>

    <Subevt expr: interfaces>

    contains

    <Subevt expr: procedures>

  end module subevt_expr

```

27.1.1 Abstract base type

```

<Subevt expr: types>≡
  type, extends (subevt_t), abstract :: subevt_expr_t
    logical :: subevt_filled = .false.
    type(var_list_t) :: var_list
    real(default) :: sqrts_hat = 0
    integer :: n_in = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    logical :: has_selection = .false.

```

```

        class(expr_t), allocatable :: selection
contains
    <Subvt expr: subvt expr: TBP>
end type subvt_expr_t

```

Output: Base and extended version. We already have a `write` routine for the `subvt_t` parent type.

```

<Subvt expr: subvt expr: TBP>≡
    procedure :: base_write => subvt_expr_write

<Subvt expr: procedures>≡
    subroutine subvt_expr_write (object, unit, pacified)
        class(subvt_expr_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: pacified
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Local variables:"
        call write_separator (u)
        call var_list_write (object%var_list, u, follow_link=.false., &
            pacified = pacified)
        call write_separator (u)
        if (object%subvt_filled) then
            call object%subvt_t%write (u, pacified = pacified)
            if (object%has_selection) then
                call write_separator (u)
                write (u, "(1x,A)") "Selection expression:"
                call write_separator (u)
                call object%selection%write (u)
            end if
        else
            write (u, "(1x,A)") "subvt: [undefined]"
        end if
    end subroutine subvt_expr_write

```

Finalizer.

```

<Subvt expr: subvt expr: TBP>+≡
    procedure (subvt_expr_final), deferred :: final
    procedure :: base_final => subvt_expr_final

<Subvt expr: procedures>+≡
    subroutine subvt_expr_final (object)
        class(subvt_expr_t), intent(inout) :: object
        call object%var_list%final ()
        if (object%has_selection) then
            call object%selection%final ()
        end if
    end subroutine subvt_expr_final

```

27.1.2 Initialization

Initialization: define local variables and establish pointers.

The common variables are `sqrts` (the nominal beam energy, fixed), `sqrts_hat` (the actual energy), `n_in`, `n_out`, and `n_tot` for the subevt. With the exception of `sqrts`, all are implemented as pointers to subobjects.

```

<Subevt expr: subevt expr: TBP>+≡
  procedure (subevt_expr_setup_vars), deferred :: setup_vars
  procedure :: base_setup_vars => subevt_expr_setup_vars
<Subevt expr: procedures>+≡
  subroutine subevt_expr_setup_vars (expr, sqrts)
    class(subevt_expr_t), intent(inout), target :: expr
    real(default), intent(in) :: sqrts
    call expr%var_list%final ()
    call var_list_append_real (expr%var_list, &
      var_str ("sqrts"), sqrts, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_real_ptr (expr%var_list, &
      var_str ("sqrts_hat"), expr%sqrts_hat, &
      is_known = expr%subevt_filled, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_int_ptr (expr%var_list, &
      var_str ("n_in"), expr%n_in, &
      is_known = expr%subevt_filled, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_int_ptr (expr%var_list, &
      var_str ("n_out"), expr%n_out, &
      is_known = expr%subevt_filled, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_int_ptr (expr%var_list, &
      var_str ("n_tot"), expr%n_tot, &
      is_known = expr%subevt_filled, &
      locked = .true., verbose = .false., intrinsic = .true.)
  end subroutine subevt_expr_setup_vars

```

Append the subevent expr (its base-type core) itself to the variable list, if it is not yet present.

```

<Subevt expr: subevt expr: TBP>+≡
  procedure :: setup_var_self => subevt_expr_setup_var_self
<Subevt expr: procedures>+≡
  subroutine subevt_expr_setup_var_self (expr)
    class(subevt_expr_t), intent(inout), target :: expr
    if (.not. expr%var_list%contains (var_str ("@evt"))) then
      call var_list_append_subevt_ptr &
        (expr%var_list, &
        var_str ("@evt"), expr%subevt_t, &
        is_known = expr%subevt_filled, &
        locked = .true., verbose = .false., intrinsic=.true.)
    end if
  end subroutine subevt_expr_setup_var_self

```

Link a variable list to the local one. This could be done event by event, but before evaluating expressions.

```

<Subevt expr: subevt expr: TBP>+≡
  procedure :: link_var_list => subevt_expr_link_var_list

```

```

<Subvt expr: procedures>+≡
  subroutine subvt_expr_link_var_list (expr, var_list)
    class(subvt_expr_t), intent(inout) :: expr
    type(var_list_t), intent(in), target :: var_list
    call expr%var_list%link (var_list)
  end subroutine subvt_expr_link_var_list

```

Compile the selection expression. If there is no expression, the build method won't allocate the expression object.

```

<Subvt expr: subvt expr: TBP>+≡
  procedure :: setup_selection => subvt_expr_setup_selection

<Subvt expr: procedures>+≡
  subroutine subvt_expr_setup_selection (expr, ef_cuts)
    class(subvt_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_cuts
    call ef_cuts%build (expr%selection)
    if (allocated (expr%selection)) then
      call expr%setup_var_self ()
      call expr%selection%setup_lexpr (expr%var_list)
      expr%has_selection = .true.
    end if
  end subroutine subvt_expr_setup_selection

```

27.1.3 Evaluation

Reset to initial state, i.e., mark the subvt as invalid.

```

<Subvt expr: subvt expr: TBP>+≡
  procedure :: reset => subvt_expr_reset
  procedure :: base_reset => subvt_expr_reset

<Subvt expr: procedures>+≡
  subroutine subvt_expr_reset (expr)
    class(subvt_expr_t), intent(inout) :: expr
    expr%subvt_filled = .false.
  end subroutine subvt_expr_reset

```

Evaluate the selection expression and return the result. There is also a deferred version: this should evaluate the remaining expressions if the event has passed.

```

<Subvt expr: subvt expr: TBP>+≡
  procedure :: base_evaluate => subvt_expr_evaluate

<Subvt expr: procedures>+≡
  subroutine subvt_expr_evaluate (expr, passed)
    class(subvt_expr_t), intent(inout) :: expr
    logical, intent(out) :: passed
    if (expr%has_selection) then
      call expr%selection%evaluate ()
      if (expr%selection%is_known ()) then
        passed = expr%selection%get_log ()
      else
        call msg_error ("Evaluate selection expression: result undefined")
      end if
    end if
  end subroutine subvt_expr_evaluate

```

```

        passed = .false.
    end if
else
    passed = .true.
end if
end subroutine subevt_expr_evaluate

```

27.1.4 Implementation for partonic events

This implementation contains the expressions that we can evaluate for the partonic process during integration.

```

⟨Subevt expr: public⟩≡
    public :: parton_expr_t

⟨Subevt expr: types⟩+≡
    type, extends (subevt_expr_t) :: parton_expr_t
        integer, dimension(:), allocatable :: i_beam
        integer, dimension(:), allocatable :: i_in
        integer, dimension(:), allocatable :: i_out
        logical :: has_scale = .false.
        logical :: has_fac_scale = .false.
        logical :: has_ren_scale = .false.
        logical :: has_weight = .false.
        class(expr_t), allocatable :: scale
        class(expr_t), allocatable :: fac_scale
        class(expr_t), allocatable :: ren_scale
        class(expr_t), allocatable :: weight
    contains
        ⟨Subevt expr: parton expr: TBP⟩
    end type parton_expr_t

```

Finalizer.

```

⟨Subevt expr: parton expr: TBP⟩≡
    procedure :: final => parton_expr_final

⟨Subevt expr: procedures⟩+≡
    subroutine parton_expr_final (object)
        class(parton_expr_t), intent(inout) :: object
        call object%base_final ()
        if (object%has_scale) then
            call object%scale%final ()
        end if
        if (object%has_fac_scale) then
            call object%fac_scale%final ()
        end if
        if (object%has_ren_scale) then
            call object%ren_scale%final ()
        end if
        if (object%has_weight) then
            call object%weight%final ()
        end if
    end subroutine parton_expr_final

```

Output: continue writing the active expressions, after the common selection expression.

Note: the `prefix` argument is declared in the `write` method of the `subevt_t` base type. Here, it is unused.

```

<Subevt expr: parton expr: TBP>+≡
  procedure :: write => parton_expr_write

<Subevt expr: procedures>+≡
  subroutine parton_expr_write (object, unit, prefix, pacified)
    class(parton_expr_t), intent(in) :: object
    integer, intent(in), optional :: unit
    character(*), intent(in), optional :: prefix
    logical, intent(in), optional :: pacified
    integer :: u
    u = given_output_unit (unit)
    call object%base_write (u, pacified = pacified)
    if (object%subevt_filled) then
      if (object%has_scale) then
        call write_separator (u)
        write (u, "(1x,A)") "Scale expression:"
        call write_separator (u)
        call object%scale%write (u)
      end if
      if (object%has_fac_scale) then
        call write_separator (u)
        write (u, "(1x,A)") "Factorization scale expression:"
        call write_separator (u)
        call object%fac_scale%write (u)
      end if
      if (object%has_ren_scale) then
        call write_separator (u)
        write (u, "(1x,A)") "Renormalization scale expression:"
        call write_separator (u)
        call object%ren_scale%write (u)
      end if
      if (object%has_weight) then
        call write_separator (u)
        write (u, "(1x,A)") "Weight expression:"
        call write_separator (u)
        call object%weight%write (u)
      end if
    end if
  end subroutine parton_expr_write

```

Define variables.

```

<Subevt expr: parton expr: TBP>+≡
  procedure :: setup_vars => parton_expr_setup_vars

<Subevt expr: procedures>+≡
  subroutine parton_expr_setup_vars (expr, sqrts)
    class(parton_expr_t), intent(inout), target :: expr
    real(default), intent(in) :: sqrts
    call expr%base_setup_vars (sqrts)
  end subroutine parton_expr_setup_vars

```

Compile the scale expressions. If a pointer is disassociated, there is no expression.

```

<Subevt expr: parton expr: TBP>+≡
  procedure :: setup_scale => parton_expr_setup_scale
  procedure :: setup_fac_scale => parton_expr_setup_fac_scale
  procedure :: setup_ren_scale => parton_expr_setup_ren_scale

<Subevt expr: procedures>+≡
  subroutine parton_expr_setup_scale (expr, ef_scale)
    class(parton_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_scale
    call ef_scale%build (expr%scale)
    if (allocated (expr%scale)) then
      call expr%setup_var_self ()
      call expr%scale%setup_expr (expr%var_list)
      expr%has_scale = .true.
    end if
  end subroutine parton_expr_setup_scale

  subroutine parton_expr_setup_fac_scale (expr, ef_fac_scale)
    class(parton_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_fac_scale
    call ef_fac_scale%build (expr%fac_scale)
    if (allocated (expr%fac_scale)) then
      call expr%setup_var_self ()
      call expr%fac_scale%setup_expr (expr%var_list)
      expr%has_fac_scale = .true.
    end if
  end subroutine parton_expr_setup_fac_scale

  subroutine parton_expr_setup_ren_scale (expr, ef_ren_scale)
    class(parton_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_ren_scale
    call ef_ren_scale%build (expr%ren_scale)
    if (allocated (expr%ren_scale)) then
      call expr%setup_var_self ()
      call expr%ren_scale%setup_expr (expr%var_list)
      expr%has_ren_scale = .true.
    end if
  end subroutine parton_expr_setup_ren_scale

```

Compile the weight expression.

```

<Subevt expr: parton expr: TBP>+≡
  procedure :: setup_weight => parton_expr_setup_weight

<Subevt expr: procedures>+≡
  subroutine parton_expr_setup_weight (expr, ef_weight)
    class(parton_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_weight
    call ef_weight%build (expr%weight)
    if (allocated (expr%weight)) then
      call expr%setup_var_self ()
      call expr%weight%setup_expr (expr%var_list)
    end if
  end subroutine parton_expr_setup_weight

```

```

        expr%has_weight = .true.
    end if
end subroutine parton_expr_setup_weight

```

Filling the partonic state consists of two parts. The first routine prepares the subevt without assigning momenta. It takes the particles from an `interaction_t`. It needs the indices and flavors for the beam, incoming, and outgoing particles.

We can assume that the particle content of the subevt does not change. Therefore, we set the event variables `n_in`, `n_out`, `n_tot` already in this initialization step.

```

<Subevt expr: parton_expr: TBP>+≡
    procedure :: setup_subevt => parton_expr_setup_subevt

<Subevt expr: procedures>+≡
    subroutine parton_expr_setup_subevt (expr, int, &
        i_beam, i_in, i_out, f_beam, f_in, f_out)
        class(parton_expr_t), intent(inout) :: expr
        type(interaction_t), intent(in), target :: int
        integer, dimension(:), intent(in) :: i_beam, i_in, i_out
        type(flavor_t), dimension(:), intent(in) :: f_beam, f_in, f_out
        allocate (expr%i_beam (size (i_beam)))
        allocate (expr%i_in (size (i_in)))
        allocate (expr%i_out (size (i_out)))
        expr%i_beam = i_beam
        expr%i_in = i_in
        expr%i_out = i_out
        call interaction_to_subevt (int, &
            expr%i_beam, expr%i_in, expr%i_out, expr%subevt_t)
        call subevt_set_pdg_beam      (expr%subevt_t, f_beam%get_pdg ())
        call subevt_set_pdg_incoming (expr%subevt_t, f_in%get_pdg ())
        call subevt_set_pdg_outgoing (expr%subevt_t, f_out%get_pdg ())
        call subevt_set_p2_beam      (expr%subevt_t, f_beam%get_mass () ** 2)
        call subevt_set_p2_incoming (expr%subevt_t, f_in%get_mass () ** 2)
        call subevt_set_p2_outgoing (expr%subevt_t, f_out%get_mass () ** 2)
        expr%n_in = size (i_in)
        expr%n_out = size (i_out)
        expr%n_tot = expr%n_in + expr%n_out
    end subroutine parton_expr_setup_subevt

```

Transfer PDG codes, masses (initialization) and momenta to a predefined subevent. We use the flavor assignment of the first branch in the interaction state matrix. Only incoming and outgoing particles are transferred. Switch momentum sign for incoming particles.

```

<Subevt expr: public>+≡
    ! public :: interaction_to_subevt
    ! public :: interaction_momenta_to_subevt

<Subevt expr: interfaces>≡
    interface interaction_momenta_to_subevt
        module procedure interaction_momenta_to_subevt_id
        module procedure interaction_momenta_to_subevt_tr
    end interface

```

<Subevt expr: procedures>+≡

```

subroutine interaction_to_subevt (int, j_beam, j_in, j_out, subevt)
  type(interaction_t), intent(in), target :: int
  integer, dimension(:), intent(in) :: j_beam, j_in, j_out
  type(subevt_t), intent(out) :: subevt
  type(flavor_t), dimension(:), allocatable :: flv
  integer :: n_beam, n_in, n_out, i, j
  allocate (flv (int%get_n_tot ()))
  flv = quantum_numbers_get_flavor (int%get_quantum_numbers (1))
  n_beam = size (j_beam)
  n_in = size (j_in)
  n_out = size (j_out)
  call subevt_init (subevt, n_beam + n_in + n_out)
  do i = 1, n_beam
    j = j_beam(i)
    call subevt_set_beam (subevt, i, &
      flv(j)%get_pdg (), &
      vector4_null, &
      flv(j)%get_mass () ** 2)
  end do
  do i = 1, n_in
    j = j_in(i)
    call subevt_set_incoming (subevt, n_beam + i, &
      flv(j)%get_pdg (), &
      vector4_null, &
      flv(j)%get_mass () ** 2)
  end do
  do i = 1, n_out
    j = j_out(i)
    call subevt_set_outgoing (subevt, n_beam + n_in + i, &
      flv(j)%get_pdg (), &
      vector4_null, &
      flv(j)%get_mass () ** 2)
  end do
end subroutine interaction_to_subevt

subroutine interaction_momenta_to_subevt_id (int, j_beam, j_in, j_out, subevt)
  type(interaction_t), intent(in) :: int
  integer, dimension(:), intent(in) :: j_beam, j_in, j_out
  type(subevt_t), intent(inout) :: subevt
  call subevt_set_p_beam (subevt, - int%get_momenta (j_beam))
  call subevt_set_p_incoming (subevt, - int%get_momenta (j_in))
  call subevt_set_p_outgoing (subevt, int%get_momenta (j_out))
end subroutine interaction_momenta_to_subevt_id

subroutine interaction_momenta_to_subevt_tr &
  (int, j_beam, j_in, j_out, lt, subevt)
  type(interaction_t), intent(in) :: int
  integer, dimension(:), intent(in) :: j_beam, j_in, j_out
  type(subevt_t), intent(inout) :: subevt
  type(lorentz_transformation_t), intent(in) :: lt
  call subevt_set_p_beam &
    (subevt, - lt * int%get_momenta (j_beam))
  call subevt_set_p_incoming &

```

```

        (subevt, - lt * int%get_momenta (j_in))
    call subevt_set_p_outgoing &
        (subevt, lt * int%get_momenta (j_out))
end subroutine interaction_momenta_to_subevt_tr

```

The second part takes the momenta from the interaction object and thus completes the subevt. The partonic energy can then be computed.

```

⟨Subevt expr: parton expr: TBP⟩+≡
    procedure :: fill_subevt => parton_expr_fill_subevt

⟨Subevt expr: procedures⟩+≡
    subroutine parton_expr_fill_subevt (expr, int)
        class(parton_expr_t), intent(inout) :: expr
        type(interaction_t), intent(in), target :: int
        call interaction_momenta_to_subevt (int, &
            expr%i_beam, expr%i_in, expr%i_out, expr%subevt_t)
        expr%sqrts_hat = subevt_get_sqrts_hat (expr%subevt_t)
        expr%subevt_filled = .true.
    end subroutine parton_expr_fill_subevt

```

Evaluate, if the event passes the selection. For absent expressions we take default values.

```

⟨Subevt expr: parton expr: TBP⟩+≡
    procedure :: evaluate => parton_expr_evaluate

⟨Subevt expr: procedures⟩+≡
    subroutine parton_expr_evaluate &
        (expr, passed, scale, fac_scale, ren_scale, weight, scale_forced)
        class(parton_expr_t), intent(inout) :: expr
        logical, intent(out) :: passed
        real(default), intent(out) :: scale
        real(default), intent(out) :: fac_scale
        real(default), intent(out) :: ren_scale
        real(default), intent(out) :: weight
        real(default), intent(in), allocatable, optional :: scale_forced
        logical :: force_scale
        force_scale = .false.
        if (present (scale_forced)) force_scale = allocated (scale_forced)
        call expr%base_evaluate (passed)
        if (passed) then
            if (force_scale) then
                scale = scale_forced
            else if (expr%has_scale) then
                call expr%scale%evaluate ()
                if (expr%scale%is_known ()) then
                    scale = expr%scale%get_real ()
                else
                    call msg_error ("Evaluate scale expression: result undefined")
                    scale = 0
                end if
            else
                scale = expr%sqrts_hat
            end if
            if (force_scale) then

```



```

        fac_scale = scale_forced
    else if (expr%has_fac_scale) then
        call expr%fac_scale%evaluate ()
        if (expr%fac_scale%is_known ()) then
            fac_scale = expr%fac_scale%get_real ()
        else
            call msg_error ("Evaluate factorization scale expression: &
                &result undefined")
            fac_scale = 0
        end if
    else
        fac_scale = scale
    end if
    if (force_scale) then
        ren_scale = scale_forced
    else if (expr%has_ren_scale) then
        call expr%ren_scale%evaluate ()
        if (expr%ren_scale%is_known ()) then
            ren_scale = expr%ren_scale%get_real ()
        else
            call msg_error ("Evaluate renormalization scale expression: &
                &result undefined")
            ren_scale = 0
        end if
    else
        ren_scale = scale
    end if
    if (expr%has_weight) then
        call expr%weight%evaluate ()
        if (expr%weight%is_known ()) then
            weight = expr%weight%get_real ()
        else
            call msg_error ("Evaluate weight expression: result undefined")
            weight = 0
        end if
    else
        weight = 1
    end if
end if
end subroutine parton_expr_evaluate

```

Return the beam/incoming parton indices.

```

<Subevt expr: parton expr: TBP>+≡
    procedure :: get_beam_index => parton_expr_get_beam_index
    procedure :: get_in_index => parton_expr_get_in_index

<Subevt expr: procedures>+≡
    subroutine parton_expr_get_beam_index (expr, i_beam)
        class(parton_expr_t), intent(in) :: expr
        integer, dimension(:), intent(out) :: i_beam
        i_beam = expr%i_beam
    end subroutine parton_expr_get_beam_index

    subroutine parton_expr_get_in_index (expr, i_in)

```

```

class(parton_expr_t), intent(in) :: expr
integer, dimension(:), intent(out) :: i_in
i_in = expr%i_in
end subroutine parton_expr_get_in_index

```

27.1.5 Implementation for full events

This implementation contains the expressions that we can evaluate for the full event. It also contains data that pertain to the event, suitable for communication with external event formats. These data simultaneously serve as pointer targets for the variable lists hidden in the expressions (eval trees).

Squared matrix element and weight values: when reading events from file, the `ref` value is the number in the file, while the `prc` value is the number that we calculate from the momenta in the file, possibly with different parameters. When generating events the first time, or if we do not recalculate, the numbers should coincide. Furthermore, the array of `alt` values is copied from an array of alternative event records. These values should represent calculated values.

```

⟨Subvt expr: public⟩+≡
    public :: event_expr_t

⟨Subvt expr: types⟩+≡
    type, extends (subvt_expr_t) :: event_expr_t
        logical :: has_reweight = .false.
        logical :: has_analysis = .false.
        class(expr_t), allocatable :: reweight
        class(expr_t), allocatable :: analysis
        logical :: has_id = .false.
        type(string_t) :: id
        logical :: has_num_id = .false.
        integer :: num_id = 0
        logical :: has_index = .false.
        integer :: index = 0
        logical :: has_sqme_ref = .false.
        real(default) :: sqme_ref = 0
        logical :: has_sqme_prc = .false.
        real(default) :: sqme_prc = 0
        logical :: has_weight_ref = .false.
        real(default) :: weight_ref = 0
        logical :: has_weight_prc = .false.
        real(default) :: weight_prc = 0
        logical :: has_excess_prc = .false.
        real(default) :: excess_prc = 0
        integer :: n_alt = 0
        logical :: has_sqme_alt = .false.
        real(default), dimension(:), allocatable :: sqme_alt
        logical :: has_weight_alt = .false.
        real(default), dimension(:), allocatable :: weight_alt
contains
    ⟨Subvt expr: event expr: TBP⟩
end type event_expr_t

```

Finalizer for the expressions.

```

<Subevt expr: event expr: TBP>≡
  procedure :: final => event_expr_final

<Subevt expr: procedures>+≡
  subroutine event_expr_final (object)
    class(event_expr_t), intent(inout) :: object
    call object%base_final ()
    if (object%has_reweight) then
      call object%reweight%final ()
    end if
    if (object%has_analysis) then
      call object%analysis%final ()
    end if
  end subroutine event_expr_final

```

Output: continue writing the active expressions, after the common selection expression.

Note: the `prefix` argument is declared in the `write` method of the `subevt_t` base type. Here, it is unused.

```

<Subevt expr: event expr: TBP>+≡
  procedure :: write => event_expr_write

<Subevt expr: procedures>+≡
  subroutine event_expr_write (object, unit, prefix, pacified)
    class(event_expr_t), intent(in) :: object
    integer, intent(in), optional :: unit
    character(*), intent(in), optional :: prefix
    logical, intent(in), optional :: pacified
    integer :: u
    u = given_output_unit (unit)
    call object%base_write (u, pacified = pacified)
    if (object%subevt_filled) then
      if (object%has_reweight) then
        call write_separator (u)
        write (u, "(1x,A)") "Reweighting expression:"
        call write_separator (u)
        call object%reweight%write (u)
      end if
      if (object%has_analysis) then
        call write_separator (u)
        write (u, "(1x,A)") "Analysis expression:"
        call write_separator (u)
        call object%analysis%write (u)
      end if
    end if
  end subroutine event_expr_write

```

Initializer. This is required only for the `sqme_alt` and `weight_alt` arrays.

```

<Subevt expr: event expr: TBP>+≡
  procedure :: init => event_expr_init

```

```

<Subevt expr: procedures>+≡
  subroutine event_expr_init (expr, n_alt)
    class(event_expr_t), intent(out) :: expr
    integer, intent(in), optional :: n_alt
    if (present (n_alt)) then
      expr%n_alt = n_alt
      allocate (expr%sqme_alt (n_alt), source = 0._default)
      allocate (expr%weight_alt (n_alt), source = 0._default)
    end if
  end subroutine event_expr_init

```

Define variables. We have the variables of the base type plus specific variables for full events. There is the event index.

```

<Subevt expr: event expr: TBP>+≡
  procedure :: setup_vars => event_expr_setup_vars

<Subevt expr: procedures>+≡
  subroutine event_expr_setup_vars (expr, sqrts)
    class(event_expr_t), intent(inout), target :: expr
    real(default), intent(in) :: sqrts
    call expr%base_setup_vars (sqrts)
    call var_list_append_string_ptr (expr%var_list, &
      var_str ("process_id"), expr%id, &
      is_known = expr%has_id, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_int_ptr (expr%var_list, &
      var_str ("process_num_id"), expr%num_id, &
      is_known = expr%has_num_id, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_real_ptr (expr%var_list, &
      var_str ("sqme"), expr%sqme_prc, &
      is_known = expr%has_sqme_prc, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_real_ptr (expr%var_list, &
      var_str ("sqme_ref"), expr%sqme_ref, &
      is_known = expr%has_sqme_ref, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_int_ptr (expr%var_list, &
      var_str ("event_index"), expr%index, &
      is_known = expr%has_index, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_real_ptr (expr%var_list, &
      var_str ("event_weight"), expr%weight_prc, &
      is_known = expr%has_weight_prc, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_real_ptr (expr%var_list, &
      var_str ("event_weight_ref"), expr%weight_ref, &
      is_known = expr%has_weight_ref, &
      locked = .true., verbose = .false., intrinsic = .true.)
    call var_list_append_real_ptr (expr%var_list, &
      var_str ("event_excess"), expr%excess_prc, &
      is_known = expr%has_excess_prc, &
      locked = .true., verbose = .false., intrinsic = .true.)
  end subroutine event_expr_setup_vars

```

Compile the analysis expression. If the pointer is disassociated, there is no expression.

```

<Subevt expr: event expr: TBP>+≡
  procedure :: setup_analysis => event_expr_setup_analysis

<Subevt expr: procedures>+≡
  subroutine event_expr_setup_analysis (expr, ef_analysis)
    class(event_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_analysis
    call ef_analysis%build (expr%analysis)
    if (allocated (expr%analysis)) then
      call expr%setup_var_self ()
      call expr%analysis%setup_lexpr (expr%var_list)
      expr%has_analysis = .true.
    end if
  end subroutine event_expr_setup_analysis

```

Compile the reweight expression.

```

<Subevt expr: event expr: TBP>+≡
  procedure :: setup_reweight => event_expr_setup_reweight

<Subevt expr: procedures>+≡
  subroutine event_expr_setup_reweight (expr, ef_reweight)
    class(event_expr_t), intent(inout), target :: expr
    class(expr_factory_t), intent(in) :: ef_reweight
    call ef_reweight%build (expr%reweight)
    if (allocated (expr%reweight)) then
      call expr%setup_var_self ()
      call expr%reweight%setup_expr (expr%var_list)
      expr%has_reweight = .true.
    end if
  end subroutine event_expr_setup_reweight

```

Store the string or numeric process ID. This should be done during initialization.

```

<Subevt expr: event expr: TBP>+≡
  procedure :: set_process_id => event_expr_set_process_id
  procedure :: set_process_num_id => event_expr_set_process_num_id

<Subevt expr: procedures>+≡
  subroutine event_expr_set_process_id (expr, id)
    class(event_expr_t), intent(inout) :: expr
    type(string_t), intent(in) :: id
    expr%id = id
    expr%has_id = .true.
  end subroutine event_expr_set_process_id

  subroutine event_expr_set_process_num_id (expr, num_id)
    class(event_expr_t), intent(inout) :: expr
    integer, intent(in) :: num_id
    expr%num_id = num_id
    expr%has_num_id = .true.
  end subroutine event_expr_set_process_num_id

```

Reset / set the data that pertain to a particular event.

<Subevt expr: event expr: TBP>+≡

```
procedure :: reset => event_expr_reset
procedure :: set  => event_expr_set
```

<Subevt expr: procedures>+≡

```
subroutine event_expr_reset (expr)
  class(event_expr_t), intent(inout) :: expr
  call expr%base_reset ()
  expr%has_sqme_ref = .false.
  expr%has_sqme_prc = .false.
  expr%has_sqme_alt = .false.
  expr%has_weight_ref = .false.
  expr%has_weight_prc = .false.
  expr%has_weight_alt = .false.
  expr%has_excess_prc = .false.
end subroutine event_expr_reset

subroutine event_expr_set (expr, &
  weight_ref, weight_prc, weight_alt, &
  excess_prc, &
  sqme_ref, sqme_prc, sqme_alt)
  class(event_expr_t), intent(inout) :: expr
  real(default), intent(in), optional :: weight_ref, weight_prc
  real(default), intent(in), optional :: excess_prc
  real(default), intent(in), optional :: sqme_ref, sqme_prc
  real(default), dimension(:), intent(in), optional :: sqme_alt, weight_alt
  if (present (sqme_ref)) then
    expr%has_sqme_ref = .true.
    expr%sqme_ref = sqme_ref
  end if
  if (present (sqme_prc)) then
    expr%has_sqme_prc = .true.
    expr%sqme_prc = sqme_prc
  end if
  if (present (sqme_alt)) then
    expr%has_sqme_alt = .true.
    expr%sqme_alt = sqme_alt
  end if
  if (present (weight_ref)) then
    expr%has_weight_ref = .true.
    expr%weight_ref = weight_ref
  end if
  if (present (weight_prc)) then
    expr%has_weight_prc = .true.
    expr%weight_prc = weight_prc
  end if
  if (present (weight_alt)) then
    expr%has_weight_alt = .true.
    expr%weight_alt = weight_alt
  end if
  if (present (excess_prc)) then
    expr%has_excess_prc = .true.
    expr%excess_prc = excess_prc
  end if
```

```
end subroutine event_expr_set
```

Fill the event expression: take the particle data and kinematics from a `particle_set` object.

We allow the particle content to change for each event. Therefore, we set the event variables each time.

Also increment the event index; initialize it if necessary.

```
<Subevt expr: event expr: TBP>+=
  procedure :: fill_subevt => event_expr_fill_subevt

<Subevt expr: procedures>+=
  subroutine event_expr_fill_subevt (expr, particle_set)
    class(event_expr_t), intent(inout) :: expr
    type(particle_set_t), intent(in) :: particle_set
    call particle_set%to_subevt (expr%subevt_t)
    expr%sqrts_hat = subevt_get_sqrts_hat (expr%subevt_t)
    expr%n_in = subevt_get_n_in (expr%subevt_t)
    expr%n_out = subevt_get_n_out (expr%subevt_t)
    expr%n_tot = expr%n_in + expr%n_out
    expr%subevt_filled = .true.
    if (expr%has_index) then
      expr%index = expr%index + 1
    else
      expr%index = 1
      expr%has_index = .true.
    end if
  end subroutine event_expr_fill_subevt
```

Evaluate, if the event passes the selection. For absent expressions we take default values.

```
<Subevt expr: event expr: TBP>+=
  procedure :: evaluate => event_expr_evaluate

<Subevt expr: procedures>+=
  subroutine event_expr_evaluate (expr, passed, reweight, analysis_flag)
    class(event_expr_t), intent(inout) :: expr
    logical, intent(out) :: passed
    real(default), intent(out) :: reweight
    logical, intent(out) :: analysis_flag
    call expr%base_evaluate (passed)
    if (passed) then
      if (expr%has_reweight) then
        call expr%reweight%evaluate ()
        if (expr%reweight%is_known ()) then
          reweight = expr%reweight%get_real ()
        else
          call msg_error ("Evaluate reweight expression: &
            &result undefined")
          reweight = 0
        end if
      else
        reweight = 1
      end if
    end if
```

```

    if (expr%has_analysis) then
      call expr%analysis%evaluate ()
      if (expr%analysis%is_known ()) then
        analysis_flag = expr%analysis%get_log ()
      else
        call msg_error ("Evaluate analysis expression: &
          &result undefined")
        analysis_flag = .false.
      end if
    else
      analysis_flag = .true.
    end if
  end if
end subroutine event_expr_evaluate

```

27.2 Parton states

A `parton_state_t` object contains the effective kinematics and dynamics of an elementary partonic interaction, with or without the beam/structure function state included. The type is abstract and has two distinct extensions. The `isolated_state_t` extension describes the isolated elementary interaction where the `int_eff` subobject contains the complex transition amplitude, exclusive in all quantum numbers. The particle content and kinematics describe the effective partonic state. The `connected_state_t` extension contains the partonic `subevt` and the expressions for cuts and scales which use it.

In the isolated state, the effective partonic interaction may either be identical to the hard interaction, in which case it is just a pointer to the latter. Or it may involve a rearrangement of partons, in which case we allocate it explicitly and flag this by `int_is_allocated`.

The `trace` evaluator contains the absolute square of the effective transition amplitude matrix, summed over final states. It is also summed over initial states, depending on the the beam setup allows. The result is used for integration.

The `matrix` evaluator is the counterpart of `trace` which is kept exclusive in all observable quantum numbers. The `flows` evaluator is furthermore exclusive in colors, but neglecting all color interference. The `matrix` and `flows` evaluators are filled only for sampling points that become part of physical events.

Note: It would be natural to make the evaluators allocatable. However, this causes memory corruption in gfortran 4.6.3. The extra `has_XXX` flags indicate whether evaluators are active, instead.

This module contains no unit tests. The tests are covered by the `processes` module below.

```

(parton_states.f90)≡
  <File header>
  module parton_states

    <Use kinds>
    <Use strings>
    use io_units
    use format_utils, only: write_separator

```



```

use diagnostics
use lorentz
use subevents
use variables
use expr_base
use model_data
use flavors
use helicities
use colors
use quantum_numbers
use state_matrices
use polarizations
use interactions
use evaluators

use beams
use sf_base
use process_constants
use prc_core
use subevt_expr

⟨Standard module head⟩

⟨Parton states: public⟩

⟨Parton states: types⟩

contains

⟨Parton states: procedures⟩

end module parton_states

```

27.2.1 Abstract base type

The common part are the evaluators, one for the trace (summed over all quantum numbers), one for the transition matrix (summed only over unobservable quantum numbers), and one for the flow distribution (transition matrix without interferences, exclusive in color flow).

```

⟨Parton states: types⟩≡
  type, abstract :: parton_state_t
    logical :: has_trace = .false.
    logical :: has_matrix = .false.
    logical :: has_flows = .false.
    type(evaluator_t) :: trace
    type(evaluator_t) :: matrix
    type(evaluator_t) :: flows
  contains
    ⟨Parton states: parton state: TBP⟩
  end type parton_state_t

```

The `isolated_state_t` extension contains the `sf_chain_eff` object and the (hard) effective interaction `int_eff`, separately, both implemented as a pointer.

The evaluators (trace, matrix, flows) apply to the hard interaction only.

If the effective interaction differs from the hard interaction, the pointer is allocated explicitly. Analogously for `sf_chain_eff`.

```

(Parton states: public)≡
  public :: isolated_state_t

(Parton states: types)+≡
  type, extends (parton_state_t) :: isolated_state_t
    logical :: sf_chain_is_allocated = .false.
    type(sf_chain_instance_t), pointer :: sf_chain_eff => null ()
    logical :: int_is_allocated = .false.
    type(interaction_t), pointer :: int_eff => null ()
  contains
    (Parton states: isolated state: TBP)
  end type isolated_state_t

```

The `connected_state_t` extension contains all data that enable the evaluation of observables for the effective connected state. The evaluators connect the (effective) structure-function chain and hard interaction that were kept separate in the `isolated_state_t`.

The `flows_sf` evaluator is an extended copy of the structure-function

The `expr` subobject consists of the `subevt`, a simple event record, expressions for cuts etc. which refer to this record, and a `var_list` which contains event-specific variables, linked to the process variable list. Variables used within the expressions are looked up in `var_list`.

```

(Parton states: types)+≡
  public :: connected_state_t

(Parton states: types)+≡
  type, extends (parton_state_t) :: connected_state_t
    type(state_flv_content_t) :: state_flv
    logical :: has_flows_sf = .false.
    type(evaluator_t) :: flows_sf
    logical :: has_expr = .false.
    type(parton_expr_t) :: expr
  contains
    (Parton states: connected state: TBP)
  end type connected_state_t

```

Output: each evaluator is written only when it is active. The `sf_chain` is only written if it is explicitly allocated.

```

(Parton states: parton state: TBP)≡
  procedure :: write => parton_state_write

(Parton states: procedures)≡
  subroutine parton_state_write (state, unit, testflag)
    class(parton_state_t), intent(in) :: state
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u
    u = given_output_unit (unit)
    select type (state)
    class is (isolated_state_t)

```

```

    if (state%sf_chain_is_allocated) then
        call write_separator (u)
        call state%sf_chain_eff%write (u)
    end if
    if (state%int_is_allocated) then
        call write_separator (u)
        write (u, "(1x,A)" &
            "Effective interaction:")
        call write_separator (u)
        call state%int_eff%basic_write (u, testflag = testflag)
    end if
class is (connected_state_t)
    if (state%has_flows_sf) then
        call write_separator (u)
        write (u, "(1x,A)" &
            "Evaluator (extension of the beam evaluator &
            &with color contractions):")
        call write_separator (u)
        call state%flows_sf%write (u, testflag = testflag)
    end if
end select
if (state%has_trace) then
    call write_separator (u)
    write (u, "(1x,A)" &
        "Evaluator (trace of the squared transition matrix):")
    call write_separator (u)
    call state%trace%write (u, testflag = testflag)
end if
if (state%has_matrix) then
    call write_separator (u)
    write (u, "(1x,A)" &
        "Evaluator (squared transition matrix):")
    call write_separator (u)
    call state%matrix%write (u, testflag = testflag)
end if
if (state%has_flows) then
    call write_separator (u)
    write (u, "(1x,A)" &
        "Evaluator (squared color-flow matrix):")
    call write_separator (u)
    call state%flows%write (u, testflag = testflag)
end if
select type (state)
class is (connected_state_t)
    if (state%has_expr) then
        call write_separator (u)
        call state%expr%write (u)
    end if
end select
end subroutine parton_state_write

```

Finalize interaction and evaluators, but only if allocated.

$\langle \text{Parton states: parton state: } TBP \rangle + \equiv$

```

    procedure :: final => parton_state_final
  (Parton states: procedures)+≡
    subroutine parton_state_final (state)
      class(parton_state_t), intent(inout) :: state
      if (state%has_flows) then
        call state%flows%final ()
        state%has_flows = .false.
      end if
      if (state%has_matrix) then
        call state%matrix%final ()
        state%has_matrix = .false.
      end if
      if (state%has_trace) then
        call state%trace%final ()
        state%has_trace = .false.
      end if
      select type (state)
      class is (connected_state_t)
        if (state%has_flows_sf) then
          call state%flows_sf%final ()
          state%has_flows_sf = .false.
        end if
        call state%expr%final ()
      class is (isolated_state_t)
        if (state%int_is_allocated) then
          call state%int_eff%final ()
          deallocate (state%int_eff)
          state%int_is_allocated = .false.
        end if
        if (state%sf_chain_is_allocated) then
          call state%sf_chain_eff%final ()
        end if
      end select
    end subroutine parton_state_final

```

27.2.2 Common Initialization

Initialize the isolated parton state. In this version, the effective structure-function chain `sf_chain_eff` and the effective interaction `int_eff` both are trivial pointers to the seed structure-function chain and to the hard interaction, respectively.

```

  (Parton states: isolated state: TBP)≡
    procedure :: init => isolated_state_init_pointers
  (Parton states: procedures)+≡
    subroutine isolated_state_init_pointers (state, sf_chain, int)
      class(isolated_state_t), intent(out) :: state
      type(sf_chain_instance_t), intent(in), target :: sf_chain
      type(interaction_t), intent(in), target :: int
      state%sf_chain_eff => sf_chain
      state%int_eff => int
    end subroutine isolated_state_init_pointers

```

27.2.3 Evaluator initialization: isolated state

Create an evaluator for the trace of the squared transition matrix. The trace goes over all outgoing quantum numbers. Whether we trace over incoming quantum numbers other than color, depends on the given `qn_mask_in`.

There are two options: explicitly computing the color factor table (`use_cf` false; `nc` defined), or taking the color factor table from the hard matrix element data.

```

(Parton states: isolated state: TBP)+≡
  procedure :: setup_square_trace => isolated_state_setup_square_trace

(Parton states: procedures)+≡
  subroutine isolated_state_setup_square_trace (state, core, qn_mask_in, &
    col)
    class(isolated_state_t), intent(inout), target :: state
    class(prc_core_t), intent(in) :: core
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
    integer, dimension(:), intent(in) :: col
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
    associate (data => core%data)
      allocate (qn_mask (data%n_in + data%n_out))
      qn_mask(:data%n_in) = &
        quantum_numbers_mask (.false., .true., .false.) &
        .or. qn_mask_in
      qn_mask(data%n_in+1:) = &
        quantum_numbers_mask (.true., .true., .true.)
    if (core%use_color_factors) then
      call state%trace%init_square (state%int_eff, qn_mask, &
        col_flow_index = data%cf_index, &
        col_factor = data%color_factors, &
        col_index_hi = col, &
        nc = core%nc)
    else
      call state%trace%init_square (state%int_eff, qn_mask, nc = core%nc)
    end if
    end associate
    state%has_trace = .true.
  end subroutine isolated_state_setup_square_trace

```

Setup the evaluator for the transition matrix, exclusive in helicities where this is requested.

For all unstable final-state particles we keep polarization according to the applicable decay options. If the process is a decay itself, this applies also to the initial state.

For all polarized final-state particles, we keep polarization including off-diagonal entries. We drop helicity completely for unpolarized final-state particles.

For the initial state, if the particle has not been handled yet, we apply the provided `qn_mask_in` which communicates the beam properties.

```

(Parton states: isolated state: TBP)+≡
  procedure :: setup_square_matrix => isolated_state_setup_square_matrix

```

```

(Parton states: procedures)+≡
subroutine isolated_state_setup_square_matrix &
  (state, core, model, qn_mask_in, col)
  class(isolated_state_t), intent(inout), target :: state
  class(prc_core_t), intent(in) :: core
  class(model_data_t), intent(in), target :: model
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
  integer, dimension(:), intent(in) :: col
  type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
  type(flavor_t), dimension(:), allocatable :: flv
  integer :: i
  logical :: helmask, helmask_hd
  associate (data => core%data)
    allocate (qn_mask (data%n_in + data%n_out))
    allocate (flv (data%n_flv))
    do i = 1, data%n_in + data%n_out
      call flv%init (data%flv_state(i,:), model)
      if ((data%n_in == 1 .or. i > data%n_in) &
        .and. any (.not. flv%is_stable ())) then
        helmask = all (flv%decays_isotropically ())
        helmask_hd = all (flv%decays_diagonal ())
        qn_mask(i) = quantum_numbers_mask (.false., .true., helmask, &
          mask_hd = helmask_hd)
      else if (i > data%n_in) then
        helmask = all (.not. flv%is_polarized ())
        qn_mask(i) = quantum_numbers_mask (.false., .true., helmask)
      else
        qn_mask(i) = quantum_numbers_mask (.false., .true., .false.) &
          .or. qn_mask_in(i)
      end if
    end do
  end do
  if (core%use_color_factors) then
    call state%matrix%init_square (state%int_eff, qn_mask, &
      col_flow_index = data%cf_index, &
      col_factor = data%color_factors, &
      col_index_hi = col, &
      nc = core%nc)
  else
    call state%matrix%init_square (state%int_eff, &
      qn_mask, &
      nc = core%nc)
  end if
end associate
state%has_matrix = .true.
end subroutine isolated_state_setup_square_matrix

```

This procedure initializes the evaluator that computes the contributions to color flows, neglecting color interference. The incoming-particle mask can be used to sum over incoming flavor.

Helicity handling: see above.

```

(Parton states: isolated state: TBP)+≡
  procedure :: setup_square_flows => isolated_state_setup_square_flows
(Parton states: procedures)+≡

```

```

subroutine isolated_state_setup_square_flows (state, core, model, qn_mask_in)
  class(isolated_state_t), intent(inout), target :: state
  class(prc_core_t), intent(in) :: core
  class(model_data_t), intent(in), target :: model
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
  type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
  type(flavor_t), dimension(:), allocatable :: flv
  integer :: i
  logical :: helmask, helmask_hd
  associate (data => core%data)
    allocate (qn_mask (data%n_in + data%n_out))
    allocate (flv (data%n_flv))
    do i = 1, data%n_in + data%n_out
      call flv%init (data%flv_state(i,:), model)
      if ((data%n_in == 1 .or. i > data%n_in) &
        .and. any (.not. flv%is_stable ())) then
        helmask = all (flv%decays_isotropically ())
        helmask_hd = all (flv%decays_diagonal ())
        qn_mask(i) = quantum_numbers_mask (.false., .false., helmask, &
          mask_hd = helmask_hd)
      else if (i > data%n_in) then
        helmask = all (.not. flv%is_polarized ())
        qn_mask(i) = quantum_numbers_mask (.false., .false., helmask)
      else
        qn_mask(i) = quantum_numbers_mask (.false., .false., .false.) &
          .or. qn_mask_in(i)
      end if
    end do
    call state%flows%init_square (state%int_eff, qn_mask, &
      expand_color_flows = .true.)
  end associate
  state%has_flows = .true.
end subroutine isolated_state_setup_square_flows

```

27.2.4 Evaluator initialization: connected state

Setup a trace evaluator as a product of two evaluators (incoming state, effective interaction). In the result, all quantum numbers are summed over.

If the optional `int` interaction is provided, use this for the first factor in the convolution. Otherwise, use the final interaction of the stored `sf_chain`.

The `resonant` flag applies if we want to construct a decay chain. The resonance property can propagate to the final event output.

(Parton states: connected state: TBP)≡

```

  procedure :: setup_connected_trace => connected_state_setup_connected_trace

```

(Parton states: procedures)+≡

```

  subroutine connected_state_setup_connected_trace &
    (state, isolated, int, resonant)
    class(connected_state_t), intent(inout), target :: state
    type(isolated_state_t), intent(in), target :: isolated
    type(interaction_t), intent(in), optional, target :: int
    logical, intent(in), optional :: resonant

```

```

type(quantum_numbers_mask_t) :: mask
type(interaction_t), pointer :: src_int
mask = quantum_numbers_mask (.true., .true., .true.)
if (present (int)) then
    src_int => int
else
    src_int => isolated%sf_chain_eff%get_out_int_ptr ()
end if
call state%trace%init_product (src_int, isolated%trace, &
    qn_mask_conn = mask, &
    qn_mask_rest = mask, &
    connections_are_resonant = resonant)
state%has_trace = .true.
end subroutine connected_state_setup_connected_trace

```

Setup a matrix evaluator as a product of two evaluators (incoming state, effective interaction). In the intermediate state, color and helicity is summed over. In the final state, we keep the quantum numbers which are present in the original evaluators.

```

(Parton states: connected state: TBP)+≡
    procedure :: setup_connected_matrix => connected_state_setup_connected_matrix
(Parton states: procedures)+≡
    subroutine connected_state_setup_connected_matrix &
        (state, isolated, int, resonant, qn_filter_conn)
    class(connected_state_t), intent(inout), target :: state
    type(isolated_state_t), intent(in), target :: isolated
    type(interaction_t), intent(in), optional, target :: int
    logical, intent(in), optional :: resonant
    type(quantum_numbers_t), intent(in), optional :: qn_filter_conn
    type(quantum_numbers_mask_t) :: mask
    type(interaction_t), pointer :: src_int
    mask = quantum_numbers_mask (.false., .true., .true.)
    if (present (int)) then
        src_int => int
    else
        src_int => isolated%sf_chain_eff%get_out_int_ptr ()
    end if
    call state%matrix%init_product &
        (src_int, isolated%matrix, mask, &
        qn_filter_conn = qn_filter_conn, &
        connections_are_resonant = resonant)
    state%has_matrix = .true.
end subroutine connected_state_setup_connected_matrix

```

Setup a matrix evaluator as a product of two evaluators (incoming state, effective interaction). In the intermediate state, only helicity is summed over. In the final state, we keep the quantum numbers which are present in the original evaluators.

If the optional `int` interaction is provided, use this for the first factor in the convolution. Otherwise, use the final interaction of the stored `sf_chain`, after creating an intermediate interaction that includes a correlated color state. We assume that for a caller-provided `int`, this is not necessary.

```

(Parton states: connected state: TBP)+≡

```



```

    procedure :: setup_connected_flows => connected_state_setup_connected_flows
  (Parton states: procedures)+≡
    subroutine connected_state_setup_connected_flows &
      (state, isolated, int, resonant, qn_filter_conn)
      class(connected_state_t), intent(inout), target :: state
      type(isolated_state_t), intent(in), target :: isolated
      type(interaction_t), intent(in), optional, target :: int
      logical, intent(in), optional :: resonant
      type(quantum_numbers_t), intent(in), optional :: qn_filter_conn
      type(quantum_numbers_mask_t) :: mask
      type(interaction_t), pointer :: src_int
      mask = quantum_numbers_mask (.false., .false., .true.)
      if (present (int)) then
        src_int => int
      else
        src_int => isolated%sf_chain_eff%get_out_int_ptr ()
        call state%flows_sf%init_color_contractions (src_int)
        state%has_flows_sf = .true.
        src_int => state%flows_sf%interaction_t
      end if
      call state%flows%init_product (src_int, isolated%flows, mask, &
        qn_filter_conn = qn_filter_conn, &
        connections_are_resonant = resonant)
      state%has_flows = .true.
    end subroutine connected_state_setup_connected_flows

```

Determine and store the flavor content for the connected state. This queries the matrix evaluator component, which should hold the requested flavor information.

```

  (Parton states: connected state: TBP)+≡
    procedure :: setup_state_flv => connected_state_setup_state_flv
  (Parton states: procedures)+≡
    subroutine connected_state_setup_state_flv (state, n_out_hard)
      class(connected_state_t), intent(inout), target :: state
      integer, intent(in) :: n_out_hard
      call interaction_get_flv_content &
        (state%matrix%interaction_t, state%state_flv, n_out_hard)
    end subroutine connected_state_setup_state_flv

```

Return the current flavor state object.

```

  (Parton states: connected state: TBP)+≡
    procedure :: get_state_flv => connected_state_get_state_flv
  (Parton states: procedures)+≡
    function connected_state_get_state_flv (state) result (state_flv)
      class(connected_state_t), intent(in) :: state
      type(state_flv_content_t) :: state_flv
      state_flv = state%state_flv
    end function connected_state_get_state_flv

```

27.2.5 Cuts and expressions

Set up the `subevt` that corresponds to the connected interaction. The index arrays refer to the interaction.

We assign the particles as follows: the beam particles are the first two (decay process: one) entries in the trace evaluator. The incoming partons are identified by their link to the outgoing partons of the structure-function chain. The outgoing partons are those of the trace evaluator, which include radiated partons during the structure-function chain.

```

(Parton states: connected state: TBP)+≡
  procedure :: setup_subevt => connected_state_setup_subevt

(Parton states: procedures)+≡
  subroutine connected_state_setup_subevt (state, sf_chain, f_beam, f_in, f_out)
    class(connected_state_t), intent(inout), target :: state
    type(sf_chain_instance_t), intent(in), target :: sf_chain
    type(flavor_t), dimension(:), intent(in) :: f_beam, f_in, f_out
    integer :: n_beam, n_in, n_out, n_vir, n_tot, i, j
    integer, dimension(:), allocatable :: i_beam, i_in, i_out
    integer :: sf_out_i
    type(interaction_t), pointer :: sf_int
    sf_int => sf_chain%get_out_int_ptr ()
    n_beam = size (f_beam)
    n_in = size (f_in)
    n_out = size (f_out)
    n_vir = state%trace%get_n_vir ()
    n_tot = state%trace%get_n_tot ()
    allocate (i_beam (n_beam), i_in (n_in), i_out (n_out))
    i_beam = [(i, i = 1, n_beam)]
    do j = 1, n_in
      sf_out_i = sf_chain%get_out_i (j)
      i_in(j) = interaction_find_link &
        (state%trace%interaction_t, sf_int, sf_out_i)
    end do
    i_out = [(i, i = n_vir + 1, n_tot)]
    call state%expr%setup_subevt (state%trace%interaction_t, &
      i_beam, i_in, i_out, f_beam, f_in, f_out)
    state%has_expr = .true.
  end subroutine connected_state_setup_subevt

```

Initialize the variable list specific for this state/term. We insert event variables (`sqrts_hat`) and link the process variable list. The variable list acquires pointers to subobjects of `state`, which must therefore have a `target` attribute.

```

(Parton states: connected state: TBP)+≡
  procedure :: setup_var_list => connected_state_setup_var_list

(Parton states: procedures)+≡
  subroutine connected_state_setup_var_list (state, process_var_list, beam_data)
    class(connected_state_t), intent(inout), target :: state
    type(var_list_t), intent(in), target :: process_var_list
    type(beam_data_t), intent(in) :: beam_data
    call state%expr%setup_vars (beam_data_get_sqrts (beam_data))
    call state%expr%link_var_list (process_var_list)
  end subroutine connected_state_setup_var_list

```

Allocate the cut expression etc.

```

(Parton states: connected state: TBP)+≡
  procedure :: setup_cuts => connected_state_setup_cuts
  procedure :: setup_scale => connected_state_setup_scale
  procedure :: setup_fac_scale => connected_state_setup_fac_scale
  procedure :: setup_ren_scale => connected_state_setup_ren_scale
  procedure :: setup_weight => connected_state_setup_weight

(Parton states: procedures)+≡
  subroutine connected_state_setup_cuts (state, ef_cuts)
    class(connected_state_t), intent(inout), target :: state
    class(expr_factory_t), intent(in) :: ef_cuts
    call state%expr%setup_selection (ef_cuts)
  end subroutine connected_state_setup_cuts

  subroutine connected_state_setup_scale (state, ef_scale)
    class(connected_state_t), intent(inout), target :: state
    class(expr_factory_t), intent(in) :: ef_scale
    call state%expr%setup_scale (ef_scale)
  end subroutine connected_state_setup_scale

  subroutine connected_state_setup_fac_scale (state, ef_fac_scale)
    class(connected_state_t), intent(inout), target :: state
    class(expr_factory_t), intent(in) :: ef_fac_scale
    call state%expr%setup_fac_scale (ef_fac_scale)
  end subroutine connected_state_setup_fac_scale

  subroutine connected_state_setup_ren_scale (state, ef_ren_scale)
    class(connected_state_t), intent(inout), target :: state
    class(expr_factory_t), intent(in) :: ef_ren_scale
    call state%expr%setup_ren_scale (ef_ren_scale)
  end subroutine connected_state_setup_ren_scale

  subroutine connected_state_setup_weight (state, ef_weight)
    class(connected_state_t), intent(inout), target :: state
    class(expr_factory_t), intent(in) :: ef_weight
    call state%expr%setup_weight (ef_weight)
  end subroutine connected_state_setup_weight

```

Reset the expression object: invalidate the subevt.

```

(Parton states: connected state: TBP)+≡
  procedure :: reset_expressions => connected_state_reset_expressions

(Parton states: procedures)+≡
  subroutine connected_state_reset_expressions (state)
    class(connected_state_t), intent(inout) :: state
    if (state%has_expr) call state%expr%reset ()
  end subroutine connected_state_reset_expressions

```

27.2.6 Evaluation

Transfer momenta to the trace evaluator and fill the `subevt` with this effective kinematics, if applicable.

Note: we may want to apply a boost for the `subevt`.

```

(Parton states: parton state: TBP)+≡
  procedure :: receive_kinematics => parton_state_receive_kinematics

(Parton states: procedures)+≡
  subroutine parton_state_receive_kinematics (state)
    class(parton_state_t), intent(inout), target :: state
    if (state%has_trace) then
      call state%trace%receive_momenta ()
      select type (state)
        class is (connected_state_t)
          if (state%has_expr) then
            call state%expr%fill_subevt (state%trace%interaction_t)
          end if
        end select
      end if
    end if
  end subroutine parton_state_receive_kinematics

```

Recover kinematics: We assume that the trace evaluator is filled with momenta. Send those momenta back to the sources, then fill the variables and subevent as above.

The incoming momenta of the connected state are not connected to the isolated state but to the beam interaction. Therefore, the incoming momenta within the isolated state do not become defined, yet. Instead, we reconstruct the beam (and ISR) momentum configuration.

```

(Parton states: parton state: TBP)+≡
  procedure :: send_kinematics => parton_state_send_kinematics

(Parton states: procedures)+≡
  subroutine parton_state_send_kinematics (state)
    class(parton_state_t), intent(inout), target :: state
    if (state%has_trace) then
      call interaction_send_momenta (state%trace%interaction_t)
      select type (state)
        class is (connected_state_t)
          call state%expr%fill_subevt (state%trace%interaction_t)
        end select
      end if
    end if
  end subroutine parton_state_send_kinematics

```

Evaluate the expressions. The routine evaluates first the cut expression. If the event passes, it evaluates the other expressions. Where no expressions are defined, default values are inserted.

```

(Parton states: connected state: TBP)+≡
  procedure :: evaluate_expressions => connected_state_evaluate_expressions

(Parton states: procedures)+≡
  subroutine connected_state_evaluate_expressions (state, passed, &
    scale, fac_scale, ren_scale, weight, scale_forced)

```

```

class(connected_state_t), intent(inout) :: state
logical, intent(out) :: passed
real(default), intent(out) :: scale, fac_scale, ren_scale, weight
real(default), intent(in), allocatable, optional :: scale_forced
if (state%has_expr) then
    call state%expr%evaluate (passed, scale, fac_scale, ren_scale, weight, &
        scale_forced)
end if
end subroutine connected_state_evaluate_expressions

```

Evaluate the structure-function chain, if it is allocated explicitly. The argument is the factorization scale.

If the chain is merely a pointer, the chain should already be evaluated at this point.

```

(Parton states: isolated state: TBP) +=
    procedure :: evaluate_sf_chain => isolated_state_evaluate_sf_chain

(Parton states: procedures) +=
    subroutine isolated_state_evaluate_sf_chain (state, fac_scale)
        class(isolated_state_t), intent(inout) :: state
        real(default), intent(in) :: fac_scale
        if (state%sf_chain_is_allocated) then
            call state%sf_chain_eff%evaluate (fac_scale)
        end if
    end subroutine isolated_state_evaluate_sf_chain

```

Evaluate the trace.

```

(Parton states: parton state: TBP) +=
    procedure :: evaluate_trace => parton_state_evaluate_trace

(Parton states: procedures) +=
    subroutine parton_state_evaluate_trace (state)
        class(parton_state_t), intent(inout) :: state
        if (state%has_trace) then
            call state%trace%evaluate ()
        end if
    end subroutine parton_state_evaluate_trace

```

Evaluate the extra evaluators that we need for physical events.

```

(Parton states: parton state: TBP) +=
    procedure :: evaluate_event_data => parton_state_evaluate_event_data

(Parton states: procedures) +=
    subroutine parton_state_evaluate_event_data (state)
        class(parton_state_t), intent(inout) :: state
        select type (state)
            type is (connected_state_t)
                if (state%has_flows_sf) then
                    call state%flows_sf%receive_momenta ()
                    call state%flows_sf%evaluate ()
                end if
        end select
        if (state%has_matrix) then

```

```

        call state%matrix%receive_momenta ()
        call state%matrix%evaluate ()
    end if
    if (state%has_flows) then
        call state%flows%receive_momenta ()
        call state%flows%evaluate ()
    end if
end subroutine parton_state_evaluate_event_data

```

Normalize the helicity density matrix by its trace, i.e., factor out the trace and put it into an overall normalization factor. The trace and flow evaluators are unchanged.

```

<Parton states: parton state: TBP>+≡
    procedure :: normalize_matrix_by_trace => &
        parton_state_normalize_matrix_by_trace

<Parton states: procedures>+≡
    subroutine parton_state_normalize_matrix_by_trace (state)
        class(parton_state_t), intent(inout) :: state
        if (state%has_matrix) then
            call state%matrix%normalize_by_trace ()
        end if
    end subroutine parton_state_normalize_matrix_by_trace

```

27.2.7 Accessing the state

Three functions return a pointer to the event-relevant interactions.

```

<Parton states: parton state: TBP>+≡
    procedure :: get_trace_int_ptr => parton_state_get_trace_int_ptr
    procedure :: get_matrix_int_ptr => parton_state_get_matrix_int_ptr
    procedure :: get_flows_int_ptr => parton_state_get_flows_int_ptr

<Parton states: procedures>+≡
    function parton_state_get_trace_int_ptr (state) result (ptr)
        class(parton_state_t), intent(in), target :: state
        type(interaction_t), pointer :: ptr
        if (state%has_trace) then
            ptr => state%trace%interaction_t
        else
            ptr => null ()
        end if
    end function parton_state_get_trace_int_ptr

    function parton_state_get_matrix_int_ptr (state) result (ptr)
        class(parton_state_t), intent(in), target :: state
        type(interaction_t), pointer :: ptr
        if (state%has_matrix) then
            ptr => state%matrix%interaction_t
        else
            ptr => null ()
        end if
    end function parton_state_get_matrix_int_ptr

```

```

function parton_state_get_flows_int_ptr (state) result (ptr)
  class(parton_state_t), intent(in), target :: state
  type(interaction_t), pointer :: ptr
  if (state%has_flows) then
    ptr => state%flows%interaction_t
  else
    ptr => null ()
  end if
end function parton_state_get_flows_int_ptr

```

Return the indices of the beam particles and the outgoing particles within the trace (and thus, matrix and flows) evaluator, respectively.

```

(Parton states: connected state: TBP)+≡
  procedure :: get_beam_index => connected_state_get_beam_index
  procedure :: get_in_index => connected_state_get_in_index

(Parton states: procedures)+≡
  subroutine connected_state_get_beam_index (state, i_beam)
    class(connected_state_t), intent(in) :: state
    integer, dimension(:), intent(out) :: i_beam
    call state%expr%get_beam_index (i_beam)
  end subroutine connected_state_get_beam_index

  subroutine connected_state_get_in_index (state, i_in)
    class(connected_state_t), intent(in) :: state
    integer, dimension(:), intent(out) :: i_in
    call state%expr%get_in_index (i_in)
  end subroutine connected_state_get_in_index

```

Return the number of outgoing (hard) particles for the state.

```

(Parton states: parton state: TBP)+≡
  procedure :: get_n_out => parton_state_get_n_out

(Parton states: procedures)+≡
  function parton_state_get_n_out (state) result (n)
    class(parton_state_t), intent(in), target :: state
    integer :: n
    n = state%trace%get_n_out ()
  end function parton_state_get_n_out

```

27.3 Complete Elementary Processes

This module combines hard interactions, phase space, and (for scatterings) structure functions and interfaces them to the integration module.

The process object implements the combination of a fixed beam and structure-function setup with a number of elementary processes. The latter are called process components. The process object represents an entity which is supposedly observable. It should be meaningful to talk about the cross section of a process.

The individual components of a process are, technically, processes themselves, but they may have unphysical cross sections which have to be added for a physical result. Process components may be exclusive tree-level elementary processes, dipole subtraction term, loop corrections, etc.

The beam and structure function setup is common to all process components. Thus, there is only one instance of this part.

The process may be a scattering process or a decay process. In the latter case, there are no structure functions, and the beam setup consists of a single particle. Otherwise, the two classes are treated on the same footing.

Once a sampling point has been chosen, a process determines a set of partons with a correlated density matrix of quantum numbers. In general, each sampling point will generate, for each process component, one or more distinct parton configurations. This is the **computed** state. The computed state is the subject of the multi-channel integration algorithm.

For NLO computations, it is necessary to project the computed states onto another set of parton configurations (e.g., by recombining certain pairs). This is the **observed** state. When computing partonic observables, the information is taken from the observed state.

For the purpose of event generation, we will later select one parton configuration from the observed state and collapse the correlated quantum state. This configuration is then dressed by applying parton shower, decays and hadronization. The decay chain, in particular, combines a scattering process with possible subsequent decay processes on the parton level, which are full-fledged process objects themselves.

```

<processes.f90>≡
  <File header>

  module processes

    <Use kinds>
    <Use strings>
    use io_units
    use constants, only: twopi4
    use format_utils, only: write_separator
    use unit_tests
    use system_dependencies
    use diagnostics
    use md5
    use cputime
    use os_interface
    use physics_defs
    use lorentz
    use sm_qcd
    use pdg_arrays
    use subevents
    use variables
    use expr_base
    use model_data
    use flavors
    use helicities
    use colors
    use quantum_numbers

```



```

use state_matrices
use polarizations
use interactions
use evaluators
use particles
use beam_structures
use beams
use sf_mappings
use sf_base
use process_constants
use phs_base
use phs_single
use rng_base
use mci_base
use mci_midpoint
use mci_vamp

use vamp !NODEP!

use process_constants
use prclib_interfaces
use prc_core_def
use process_libraries
use prc_test

use integration_results
use prc_core
use parton_states

use nlo_data
use nlo_controller
use phs_wood
use phs_fks
use prc_gosam
use prc_openloops
use prc_omega
use blha_config
use blha_olp_interfaces

```

⟨Standard module head⟩

⟨Processes: public⟩

⟨Processes: parameters⟩

⟨Processes: types⟩

⟨Processes: process part types⟩

⟨Processes: process type⟩

⟨Processes: interfaces⟩

⟨Processes: test types⟩

```

contains

  <Processes: procedures>

  <Processes: tests>

end module processes

```

27.3.1 The Process Object

A process object is the workspace for creating process instances for event generation. After initialization, its contents are filled by integration passes which shape the integration grids and compute cross sections. Processes are set up initially from user-level configuration data. After calculating integrals and thus developing integration grid data, the program may use a process object or a copy of it for the purpose of generating events.

The process object consists of several subobjects with their specific purposes. The corresponding types are defined below. (Technically, the subobject type definitions have to come before the process type definition, but with NOWEB magic we reverse this order here.)

The **type** determines whether we are considering a decay or a scattering process.

The **meta** object describes the process and its environment. All contents become fixed when the object is initialized.

The **config** object holds physical and technical configuration data that have been obtained during process initialization, and which are common to all process components.

The individual process components are configured in the **component** objects. These objects contain more configuration parameters and workspace, as needed for the specific process variant.

The **term** objects describe parton configurations which are technically used as phase-space points. Each process component may split into several terms with distinct kinematics and particle content. Furthermore, each term may project on a different physical state, e.g., by particle recombination. The **term** object provides the framework for this projection, for applying cuts, weight, and thus completing the process calculation.

The **beam_config** object describes the incoming particles, either the decay mother or the scattering beams. It also contains the structure-function information.

The **mci_entry** objects configure a MC input parameter set and integrator, each. The number of parameters depends on the process component and on the beam and structure-function setup.

```

<Processes: public>≡
  public :: process_t

<Processes: process type>≡
  type :: process_t
  private
  type(process_metadata_t) :: &
    meta

```

```

type(process_config_data_t) :: &
    config
type(process_counter_t) :: &
    counter
type(process_component_t), dimension(:), allocatable :: &
    component
type(process_term_t), dimension(:), allocatable :: &
    term
type(process_beam_config_t) :: &
    beam_config
type(process_mci_entry_t), dimension(:), allocatable :: &
    mci_entry
logical :: nlo_process
contains
<Processes: process: TBP>
end type process_t

```

This procedure is an important debugging and inspection tool; it is not used during normal operation. The process object is written to a file (identified by unit, which may also be standard output). Optional flags determine whether we show everything or just the interesting parts.

```

<Processes: process: TBP>≡
    procedure :: write => process_write

<Processes: procedures>≡
    subroutine process_write (process, screen, unit, &
        show_all, show_var_list, &
        show_os_data, &
        show_rng_factory, show_model, show_expressions, &
        show_sfchain, &
        show_equivalences, show_history, show_histories, &
        show_forest, show_x, &
        show_subevt, show_evaluators, pacify)
    class(process_t), intent(in) :: process
    logical, intent(in) :: screen
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_all
    logical, intent(in), optional :: show_var_list
    logical, intent(in), optional :: show_os_data
    logical, intent(in), optional :: show_rng_factory
    logical, intent(in), optional :: show_model, show_expressions
    logical, intent(in), optional :: show_sfchain
    logical, intent(in), optional :: show_equivalences
    logical, intent(in), optional :: show_history, show_histories
    logical, intent(in), optional :: show_forest, show_x
    logical, intent(in), optional :: show_subevt, show_evaluators
    logical, intent(in), optional :: pacify
    logical :: all
    logical :: var_list
    logical :: counters
    logical :: os_data
    logical :: rng_factory, model, expressions
    integer :: u, i
    u = given_output_unit (unit)

```

```

if (present (show_all)) then
    all = show_all
else
    all = .false.
end if
var_list = .false.
counters = .true.
os_data = .false.
model = .false.
rng_factory = .true.
expressions = .false.
if (present (show_var_list)) then
    all = .false.; var_list = show_var_list
end if
if (present (show_os_data)) then
    all = .false.; os_data = show_os_data
end if
if (present (show_rng_factory)) then
    all = .false.; rng_factory = show_rng_factory
end if
if (present (show_model)) then
    all = .false.; model = show_model
end if
if (present (show_expressions)) then
    all = .false.; expressions = show_expressions
end if
if (all) then
    var_list = .true.
    rng_factory = .true.
    model = .true.
    expressions = .true.
end if
if (screen) then
    write (msg_buffer, "(A)") repeat ("-", 72)
    call msg_message ()
else
    call write_separator (u, 2)
end if
call process%meta%write (u, var_list, screen)
if (process%meta%type == PRC_UNKNOWN) then
    call write_separator (u, 2)
    return
else
    if (.not. screen) call write_separator (u)
end if
if (screen) return
call process%config%write &
    (u, counters, os_data, rng_factory, model, expressions)
call write_separator (u, 2)
if (allocated (process%component)) then
    write (u, "(1x,A)") "Process component configuration:"
    do i = 1, size (process%component)
        call write_separator (u)
        call process%component(i)%write (u)
    end do
end if

```

```

        end do
    else
        write (u, "(1x,A)") "Process component configuration: [undefined]"
    end if
    call write_separator (u, 2)
    if (allocated (process%term)) then
        write (u, "(1x,A)") "Process term configuration:"
        do i = 1, size (process%term)
            call write_separator (u)
            call process%term(i)%write (u)
        end do
    else
        write (u, "(1x,A)") "Process term configuration: [undefined]"
    end if
    call write_separator (u, 2)
    call process%beam_config%write (u)
    call write_separator (u, 2)
    if (allocated (process%mci_entry)) then
        write (u, "(1x,A)") "Multi-channel integrator configurations:"
        do i = 1, size (process%mci_entry)
            call write_separator (u)
            write (u, "(1x,A,IO,A)") "MCI #", i, ":"
            call process%mci_entry(i)%write (u, pacify)
        end do
    end if
    call write_separator (u, 2)
end subroutine process_write

```

Screen output. Write a short account of the process configuration and the current results. The verbose version lists the components, the short version just the results.

```

<Processes: process: TBP>+≡
    procedure :: show => process_show

<Processes: procedures>+≡
    subroutine process_show (object, unit, verbose)
        class(process_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        integer :: u
        logical :: verb
        u = given_output_unit (unit)
        verb = .true.; if (present (verbose)) verb = verbose
        if (verb) then
            call object%meta%show (u, object%config%model%get_name ())
            select case (object%meta%type)
            case (PRC_DECAY)
                write (u, "(2x,A)", advance="no") "Computed width ="
            case (PRC_SCATTERING)
                write (u, "(2x,A)", advance="no") "Computed cross section ="
            case default; return
            end select
        else
            write (u, "(A)", advance="no") char (object%meta%id)
        end if
    end subroutine process_show

```

```

select case (object%meta%num_id)
case (0)
write (u, "(:)")
case default
write (u, "(1x,'(,IO,')',':')") object%meta%num_id
end select
write (u, "(2x)", advance="no")
end if
write (u, "(ES14.7,1x,'+-',ES9.2)", advance="no") &
object%get_integral_tot (), object%get_error_tot ()
select case (object%meta%type)
case (PRC_DECAY)
write (u, "(1x,A)" "GeV"
case (PRC_SCATTERING)
write (u, "(1x,A)" "fb"
case default
write (u, *)
end select
end subroutine process_show

```

Finalizer. Explicitly iterate over all subobjects that may contain allocated pointers.

```

<Processes: process: TBP>+=
procedure :: final => process_final

<Processes: procedures>+=
subroutine process_final (process)
class(process_t), intent(inout) :: process
integer :: i
call process%meta%final ()
call process%config%final ()
if (allocated (process%component)) then
do i = 1, size (process%component)
call process%component(i)%final ()
end do
end if
if (allocated (process%term)) then
do i = 1, size (process%term)
call process%term(i)%final ()
end do
end if
call process%beam_config%final ()
if (allocated (process%mci_entry)) then
do i = 1, size (process%mci_entry)
call process%mci_entry(i)%final ()
end do
end if
end subroutine process_final

```

Process setup

Initialize a process. We need a process library, the name of the process, and a run ID. The model is imported via its pointer, and the original pointer freed.

```

<Processes: process: TBP>+=
  procedure :: init => process_init

<Processes: procedures>+=
  subroutine process_init &
    (process, proc_id, run_id, lib, os_data, qcd, rng_factory, model)
    class(process_t), intent(out) :: process
    type(string_t), intent(in) :: proc_id
    type(string_t), intent(in) :: run_id
    type(process_library_t), intent(in), target :: lib
    type(os_data_t), intent(in) :: os_data
    type(qcd_t), intent(in) :: qcd
    class(rng_factory_t), intent(inout), allocatable :: rng_factory
    class(model_data_t), intent(inout), pointer :: model
    if (.not. lib%is_active ()) then
      call msg_bug ("Process init: inactive library not handled yet")
    end if
    if (.not. lib%contains (proc_id)) then
      call msg_fatal ("Process library doesn't contain process '" &
        // char (proc_id) // "'")
      return
    end if
    associate (meta => process%meta)
      call meta%init (proc_id, run_id, lib)
      call process%config%init (meta, os_data, qcd, rng_factory, model)
      allocate (process%component (meta%n_components))
    end associate
    process%nlo_process = lib%get_nlo_process (proc_id)
  end subroutine process_init

```

Store a snapshot of the common variable list.

```

<Processes: process: TBP>+=
  procedure :: set_var_list => process_set_var_list

<Processes: procedures>+=
  subroutine process_set_var_list (process, var_list)
    class(process_t), intent(inout) :: process
    type(var_list_t), intent(in) :: var_list
    call var_list_init_snapshot &
      (process%meta%var_list, var_list, follow_link=.true.)
  end subroutine process_set_var_list

```

Initialize the process components, one by one, using a template for the process core object. The template is taken only for allocating the correct type; the contents are set by extracting the process entry from the library.

```

<Processes: process: TBP>+=
  procedure :: init_component => process_init_component

<Processes: procedures>+=
  subroutine process_init_component &
    (process, index, core_template, mci_template, phs_config_template, &
      fks_template, blha_template)
    class(process_t), intent(inout) :: process
    integer, intent(in) :: index

```

```

class(prc_core_t), intent(in), allocatable :: core_template
class(mci_t), intent(in), allocatable :: mci_template
class(phs_config_t), intent(in), allocatable :: phs_config_template
type(fks_template_t), intent(in), optional :: fks_template
type(blha_template_t), intent(inout), optional :: blha_template
call process%component(index)%init (index, &
    process%meta, process%config, &
    core_template, mci_template, phs_config_template, &
    blha_template, fks_template)
if (.not. process%component(index)%active) then
    call process%meta%deactivate_component(index)
end if
end subroutine process_init_component

```

Determine the process terms for each process component.

$\langle Processes: process: TBP \rangle + \equiv$

```

procedure :: setup_terms => process_setup_terms

```

$\langle Processes: procedures \rangle + \equiv$

```

subroutine process_setup_terms (process)
class(process_t), intent(inout) :: process
class(model_data_t), pointer :: model
integer :: i, j, k
integer, dimension(:), allocatable :: n_entry
integer :: n_components, n_tot
model => process%config%model
n_components = process%meta%n_components
allocate (n_entry (n_components), source = 0)
do i = 1, n_components
    associate (component => process%component(i))
        if (component%active) n_entry(i) = component%core%get_n_terms ()
    end associate
end do
n_tot = sum (n_entry)
allocate (process%term (n_tot))
k = 0
do i = 1, n_components
    associate (component => process%component(i))
        if (.not. component%active) cycle
        associate (core => component%core)
            allocate (component%i_term (n_entry(i)))
            do j = 1, n_entry(i)
                component%i_term(j) = k + j
                call process%term(k+j)%init (k+j, i, j, core, model)
            end do
        end associate
    end associate
    k = k + n_entry(i)
end do
process%config%n_terms = n_tot
end subroutine process_setup_terms

```

Initialize the beam setup. This is the trivial version where the incoming state of the matrix element coincides with the initial state of the process. For a

scattering process, we need the c.m. energy, all other variables are set to their default values (no polarization, lab frame and c.m. frame coincide, etc.)

We assume that all components consistently describe a scattering process, i.e., two incoming particles.

Note: The current layout of the `beam_data_t` record requires that the flavor for each beam is unique. For processes with multiple flavors in the initial state, one has to set up beams explicitly. This restriction could be removed by extending the code in the `beams` module.

```

(Processes: process: TBP)+≡
  procedure :: setup_beams_sqrts => process_setup_beams_sqrts

(Processes: procedures)+≡
  subroutine process_setup_beams_sqrts (process, sqrts, beam_structure)
    class(process_t), intent(inout) :: process
    real(default), intent(in) :: sqrts
    type(beam_structure_t), intent(in), optional :: beam_structure
    type(pdg_array_t), dimension(:,,:), allocatable :: pdg_in
    integer, dimension(2) :: pdg_scattering
    type(flavor_t), dimension(2) :: flv_in
    integer :: i, i0
    allocate (pdg_in (2, process%meta%n_components))
    i0 = 0
    do i = 1, process%meta%n_components
      if (process%component(i)%active) then
        pdg_in(:,i) = process%component(i)%get_pdg_in ()
        if (i0 == 0) i0 = i
      end if
    end do
    do i = 1, process%meta%n_components
      if (.not. process%component(i)%active) then
        pdg_in(:,i) = pdg_in(:,i0)
      end if
    end do
    if (all (pdg_array_get_length (pdg_in) == 1) .and. &
        all (pdg_in(1,:) == pdg_in(1,i0)) .and. &
        all (pdg_in(2,:) == pdg_in(2,i0))) then
      pdg_scattering = pdg_array_get (pdg_in(:,i0), 1)
      call flv_in%init (pdg_scattering, process%config%model)
      call process%beam_config%init_scattering (flv_in, sqrts, beam_structure)
    else
      call msg_fatal ("Setting up process '" // char (process%meta%id) // "':", &
        [var_str ("-----"), &
        var_str ("Inconsistent initial state. This happens if either "), &
        var_str ("several processes with non-matching initial states "), &
        var_str ("have been added, or for a single process with an "), &
        var_str ("initial state flavor sum. In that case, please set beams "), &
        var_str ("explicitly [singling out a flavor / structure function.]")])
    end if
  end subroutine process_setup_beams_sqrts

```

This is the version that applies to decay processes. The energy is the particle mass, hence no extra argument.

```

(Processes: process: TBP)+≡

```

```

procedure :: setup_beams_decay => process_setup_beams_decay
<Processes: procedures>+≡
subroutine process_setup_beams_decay (process, rest_frame, beam_structure)
class(process_t), intent(inout) :: process
logical, intent(in), optional :: rest_frame
type(beam_structure_t), intent(in), optional :: beam_structure
type(pdg_array_t), dimension(:, :), allocatable :: pdg_in
integer, dimension(1) :: pdg_decay
type(flavor_t), dimension(1) :: flv_in
integer :: i, i0
allocate (pdg_in (1, process%meta%n_components))
i0 = 0
do i = 1, process%meta%n_components
  if (process%component(i)%active) then
    pdg_in(:, i) = process%component(i)%get_pdg_in ()
    if (i0 == 0) i0 = i
  end if
end do
do i = 1, process%meta%n_components
  if (.not. process%component(i)%active) then
    pdg_in(:, i) = pdg_in(:, i0)
  end if
end do
if (all (pdg_array_get_length (pdg_in) == 1) &
    .and. all (pdg_in(1, :) == pdg_in(1, i0))) then
  pdg_decay = pdg_array_get (pdg_in(:, i0), 1)
  call flv_in%init (pdg_decay, process%config%model)
  call process%beam_config%init_decay (flv_in, rest_frame, beam_structure)
else
  call msg_fatal ("Setting up decay '" &
    // char (process%meta%id) // "' : decaying particle not unique")
end if
end subroutine process_setup_beams_decay

```

We have to make sure that the masses of the various flavors in a given position in the particle string coincide.

```

<Processes: process: TBP>+≡
procedure :: check_masses => process_check_masses
<Processes: procedures>+≡
subroutine process_check_masses (process)
class(process_t), intent(in) :: process
type(flavor_t), dimension(:), allocatable :: flv
real(default), dimension(:), allocatable :: mass
integer :: i, j
do i = 1, process%meta%n_components
  if (.not. process%component(i)%active) cycle
  associate (data => process%component(i)%core%data)
    allocate (flv (data%n_flv), mass (data%n_flv))
    do j = 1, data%n_in + data%n_out
      call flv%init (data%flv_state(j, :), process%config%model)
      mass = flv%get_mass ()
      if (any (.not. nearly_equal(mass, mass(1)))) then
        call msg_fatal ("Process '" // char (process%meta%id) // "' : " &

```

```

// "mass values in flavor combination do not coincide. ")
end if
end do
deallocate (flv, mass)
end associate
end do
end subroutine process_check_masses

```

For some structure functions we need to get the list of initial state flavors. This is a two-dimensional array. The first index is the beam index, the second index is the component index. Each array element is itself a PDG array object, which consists of the list of incoming PDG values for this beam and component.

```

(Processes: process: TBP)+≡
  procedure :: get_pdg_in => process_get_pdg_in

(Processes: procedures)+≡
  subroutine process_get_pdg_in (process, pdg_in)
    class(process_t), intent(in) :: process
    type(pdg_array_t), dimension(:,:), allocatable, intent(out) :: pdg_in
    integer :: i
    allocate (pdg_in (process%config%n_in, process%meta%n_components))
    do i = 1, process%meta%n_components
      if (process%component(i)%active) then
        pdg_in(:,i) = process%component(i)%get_pdg_in ()
      end if
    end do
  end subroutine process_get_pdg_in

```

Initialize from a complete beam setup.

```

(Processes: process: TBP)+≡
  procedure :: setup_beams_beam_structure => process_setup_beams_beam_structure

(Processes: procedures)+≡
  subroutine process_setup_beams_beam_structure &
    (process, beam_structure, sqrts, decay_rest_frame)
    class(process_t), intent(inout) :: process
    type(beam_structure_t), intent(in) :: beam_structure
    real(default), intent(in) :: sqrts
    logical, intent(in), optional :: decay_rest_frame
    if (process%get_n_in () == beam_structure%get_n_beam ()) then
      call process%beam_config%init_beam_structure &
        (beam_structure, sqrts, process%get_model_ptr (), decay_rest_frame)
    else if (beam_structure%get_n_beam () == 0) then
      call msg_fatal ("Asymmetric beams: missing beam particle specification")
    else
      call msg_fatal ("Mismatch of process and beam setup (scattering/decay)")
    end if
  end subroutine process_setup_beams_beam_structure

```

Notify the user about beam setup.

```

(Processes: process: TBP)+≡
  procedure :: beams_startup_message => process_beams_startup_message

```

<Processes: procedures>+≡

```

subroutine process_beams_startup_message (process, unit, beam_structure)
  class(process_t), intent(in) :: process
  integer, intent(in), optional :: unit
  type(beam_structure_t), intent(in), optional :: beam_structure
  call process%beam_config%startup_message (unit, beam_structure)
end subroutine process_beams_startup_message

```

We complete the kinematics configuration after the beam setup, but before we configure the chain of structure functions. The reason is that we need the total energy `sqrts` for the kinematics, but the structure-function setup requires the number of channels, which depends on the kinematics configuration. For instance, the kinematics module may return the need for parameterizing an s-channel resonance.

<Processes: process: TBP>+≡

```

procedure :: configure_phs => process_configure_phs

```

<Processes: procedures>+≡

```

subroutine process_configure_phs (process, rebuild, ignore_mismatch, verbose, &
                                combined_integration)
  class(process_t), intent(inout) :: process
  logical, intent(in), optional :: rebuild
  logical, intent(in), optional :: ignore_mismatch, verbose
  logical, intent(in), optional :: combined_integration
  real(default) :: sqrts
  integer :: i, i_born
  class(phs_config_t), allocatable :: phs_config_born
  sqrts = process%get_sqrts ()
  do i = 1, process%meta%n_components
    associate (component => process%component(i))
      if (component%active) then
        if (process%nlo_process) then
          select case (component%config%get_nlo_type ())
            case (BORN, NLO_VIRTUAL, NLO_SUBTRACTION)
              call component%configure_phs (sqrts, process%beam_config, &
                                             rebuild, ignore_mismatch, verbose=verbose)
              call check_and_extend_phs (component, combined_integration)
            case (NLO_REAL, NLO_PDF)
              i_born = component%config%get_associated_born ()
              call check_and_extend_phs (component, combined_integration)
              call process%component(i_born)%extract_phs_config (phs_config_born)
              select type (phs_config_born)
                type is (phs_wood_config_t)
                  call component%configure_phs (sqrts, &
                                                  process%beam_config, rebuild, ignore_mismatch, &
                                                  phs_config_born, verbose=verbose)
                type is default
                  call component%configure_phs (sqrts, process%beam_config, rebuild, ignore_mismatch, &
                                                  verbose=verbose)
              end select
              call process%component(i_born)%restore_phs_config (phs_config_born)
            end select
          end select
        else
          call component%configure_phs (sqrts, process%beam_config, &
                                         rebuild, ignore_mismatch, verbose=verbose)
        end if
      end if
    end if
  end do
end subroutine process_configure_phs

```

```

        end associate
    end do
contains
    subroutine check_and_extend_phs (component, combined_integration)
        type(process_component_t), intent(inout) :: component
        logical, intent(in), optional :: combined_integration
        if (present (combined_integration)) then
            if (combined_integration) then
                select type (phs_config => component%phs_config)
                type is (phs_wood_config_t)
                    call phs_config%set_extended_phs ()
                    call phs_config%increase_n_par ()
                type is (phs_fks_config_t)
                    call phs_config%set_extended_phs ()
                end select
            end if
        end if
    end subroutine check_and_extend_phs
end subroutine process_configure_phs

```

Insert the structure-function configuration data. First allocate the storage, then insert data one by one. The third procedure declares a mapping (of the MC input parameters) for a specific channel and structure-function combination.

We take the number of channels from the corresponding entry in the `config_data` section.

Otherwise, these are simple wrapper routines. The extra level in the call tree may allow for simple addressing of multiple concurrent beam configurations, not implemented currently.

If we do not want structure functions, we simply do not call those procedures.

(Processes: process: TBP)+≡

```

    procedure :: init_sf_chain => process_init_sf_chain
    generic :: set_sf_channel => set_sf_channel_single
    procedure :: set_sf_channel_single => process_set_sf_channel
    generic :: set_sf_channel => set_sf_channel_array
    procedure :: set_sf_channel_array => process_set_sf_channel_array

```

(Processes: procedures)+≡

```

    subroutine process_init_sf_chain (process, sf_config, sf_trace_file)
        class(process_t), intent(inout) :: process
        type(sf_config_t), dimension(:), intent(in) :: sf_config
        type(string_t), intent(in), optional :: sf_trace_file
        type(string_t) :: file
        if (present (sf_trace_file)) then
            if (sf_trace_file /= "") then
                file = sf_trace_file
            else
                file = process%get_id () // "_sftrace.dat"
            end if
            call process%beam_config%init_sf_chain (sf_config, file)
        else
            call process%beam_config%init_sf_chain (sf_config)
        end if
    end subroutine process_init_sf_chain

```

```

subroutine process_set_sf_channel (process, c, sf_channel)
  class(process_t), intent(inout) :: process
  integer, intent(in) :: c
  type(sf_channel_t), intent(in) :: sf_channel
  call process%beam_config%set_sf_channel (c, sf_channel)
end subroutine process_set_sf_channel

subroutine process_set_sf_channel_array (process, sf_channel)
  class(process_t), intent(inout) :: process
  type(sf_channel_t), dimension(:), intent(in) :: sf_channel
  integer :: c
  call process%beam_config%allocate_sf_channels (size (sf_channel))
  do c = 1, size (sf_channel)
    call process%beam_config%set_sf_channel (c, sf_channel(c))
  end do
end subroutine process_set_sf_channel_array

```

Notify about the structure-function setup.

```

<Processes: process: TBP>+≡
  procedure :: sf_startup_message => process_sf_startup_message

<Processes: procedures>+≡
  subroutine process_sf_startup_message (process, sf_string, unit)
    class(process_t), intent(in) :: process
    type(string_t), intent(in) :: sf_string
    integer, intent(in), optional :: unit
    call process%beam_config%sf_startup_message (sf_string, unit)
  end subroutine process_sf_startup_message

```

As soon as both the kinematics configuration and the structure-function setup are complete, we match parameterizations (channels) for both. The matching entries are (re)set in the component phase-space configuration, while the structure-function configuration is left intact.

```

<Processes: process: TBP>+≡
  procedure :: collect_channels => process_collect_channels

<Processes: procedures>+≡
  subroutine process_collect_channels (process, coll)
    class(process_t), intent(inout) :: process
    type(phs_channel_collection_t), intent(inout) :: coll
    integer :: i
    do i = 1, process%meta%n_components
      associate (component => process%component(i))
        if (component%active) then
          call component%collect_channels (coll)
        end if
      end associate
    end do
  end subroutine process_collect_channels

```

Independently, we should be able to check if any component doesn't contain phase-space parameters. Such a process can only be integrated if there are

structure functions.

```

(Processes: process: TBP)+≡
  procedure :: contains_trivial_component => process_contains_trivial_component

(Processes: procedures)+≡
  function process_contains_trivial_component (process) result (flag)
    class(process_t), intent(in) :: process
    logical :: flag
    integer :: i
    flag = .true.
    do i = 1, process%meta%n_components
      associate (component => process%component(i))
        if (component%active) then
          if (component%get_n_phs_par () == 0) return
        end if
      end associate
    end do
    flag = .false.
  end function process_contains_trivial_component

```

Determine the MC parameter set structure and the MCI configuration for each process component. We need data from the structure-function and phase-space setup, so those should be complete before this is called. We also make a random-number generator instance for each MCI group.

```

(Processes: process: TBP)+≡
  procedure :: setup_mci => process_setup_mci

(Processes: procedures)+≡
  subroutine process_setup_mci (process, combined_integration)
    class(process_t), intent(inout) :: process
    logical, intent(in), optional :: combined_integration
    integer :: n_mci, i_mci
    integer :: i
    n_mci = 0
    do i = 1, process%meta%n_components
      associate (component => process%component(i))
        if (component%needs_mci_entry () .and. &
            component%config%get_nlo_type () /= NLO_SUBTRACTION) then
          n_mci = n_mci + 1
          component%i_mci = n_mci
        end if
      end associate
    end do
    process%config%n_mci = n_mci
    if (.not. allocated (process%config%rng_factory)) &
      call msg_bug ("Process setup: rng factory not allocated")
    allocate (process%mci_entry (n_mci))
    i_mci = 0
    do i = 1, process%meta%n_components
      associate (component => process%component(i))
        if (component%needs_mci_entry () .and. &
            component%config%get_nlo_type () /= NLO_SUBTRACTION) then
          i_mci = i_mci + 1
          associate (mci_entry => process%mci_entry(i_mci))

```

```

        call mci_entry%set_combined_integration (combined_integration)
        call mci_entry%init (process%meta%type, &
            i_mci, i, component, process%beam_config, &
            process%config%rng_factory)
    end associate
end if
end associate
end do
do i_mci = 1, size (process%mci_entry)
    call process%mci_entry(i_mci)%set_parameters (process%meta%var_list)
end do
end subroutine process_setup_mci

```

Set cuts. This is a parse node, namely the right-hand side of the cut assignment. When creating an instance, we compile this into an evaluation tree. The parse node may be null.

```

<Processes: process: TBP>+=
    procedure :: set_cuts => process_set_cuts

<Processes: procedures>+=
    subroutine process_set_cuts (process, ef_cuts)
        class(process_t), intent(inout) :: process
        class(expr_factory_t), intent(in) :: ef_cuts
        allocate (process%config%ef_cuts, source = ef_cuts)
    end subroutine process_set_cuts

```

Analogously for the other expressions.

```

<Processes: process: TBP>+=
    procedure :: set_scale => process_set_scale
    procedure :: set_fac_scale => process_set_fac_scale
    procedure :: set_ren_scale => process_set_ren_scale
    procedure :: set_weight => process_set_weight

<Processes: procedures>+=
    subroutine process_set_scale (process, ef_scale)
        class(process_t), intent(inout) :: process
        class(expr_factory_t), intent(in) :: ef_scale
        allocate (process%config%ef_scale, source = ef_scale)
    end subroutine process_set_scale

    subroutine process_set_fac_scale (process, ef_fac_scale)
        class(process_t), intent(inout) :: process
        class(expr_factory_t), intent(in) :: ef_fac_scale
        allocate (process%config%ef_fac_scale, source = ef_fac_scale)
    end subroutine process_set_fac_scale

    subroutine process_set_ren_scale (process, ef_ren_scale)
        class(process_t), intent(inout) :: process
        class(expr_factory_t), intent(in) :: ef_ren_scale
        allocate (process%config%ef_ren_scale, source = ef_ren_scale)
    end subroutine process_set_ren_scale

    subroutine process_set_weight (process, ef_weight)
        class(process_t), intent(inout) :: process

```



```

class(expr_factory_t), intent(in) :: ef_weight
allocate (process%config%ef_weight, source = ef_weight)
end subroutine process_set_weight

```

MD5 sum

The MD5 sum of the process object should reflect the state completely, including integration results. It is used for checking the integrity of event files. This global checksum includes checksums for the various parts. In particular, the MCI object receives a checksum that includes the configuration of all configuration parts relevant for an individual integration. This checksum is used for checking the integrity of integration grids.

We do not need MD5 sums for the process terms, since these are generated from the component definitions.

```

<Processes: process: TBP>+≡
  procedure :: compute_md5sum => process_compute_md5sum

<Processes: procedures>+≡
  subroutine process_compute_md5sum (process)
    class(process_t), intent(inout) :: process
    integer :: i
    call process%config%compute_md5sum ()
    do i = 1, process%config%n_components
      associate (component => process%component(i))
        if (component%active) then
          call component%compute_md5sum ()
        end if
      end associate
    end do
    call process%beam_config%compute_md5sum ()
    do i = 1, process%config%n_mci
      call process%mci_entry(i)%compute_md5sum &
        (process%config, process%component, process%beam_config)
    end do
  end subroutine process_compute_md5sum

```

Integration and event generation

The sampler test should just evaluate the squared matrix element `n_calls` times, discarding the results, and return. This can be done before integration, e.g., for timing estimates.

```

<Processes: process: TBP>+≡
  procedure :: sampler_test => process_sampler_test

<Processes: procedures>+≡
  subroutine process_sampler_test (process, instance, i_mci, n_calls)
    class(process_t), intent(inout) :: process
    type(process_instance_t), intent(inout), target :: instance
    integer, intent(in) :: i_mci
    integer, intent(in) :: n_calls
    call process%mci_entry(i_mci)%sampler_test (instance, n_calls)
  end subroutine process_sampler_test

```

```
end subroutine process_sampler_test
```

Integrate the process, using a previously initialized process instance. We select one of the available MCI integrators by its index `i_mci` and thus integrate over (structure functions and) phase space for the associated (group of) process component(s).

The finalizer should be called after all integration passes have been completed. It will, for instance, write a summary of the integration results.

`integrate_dummy` does a “dummy” integration in the sense that nothing is done but just empty integration results appended.

```
<Processes: process: TBP>+≡
```

```
procedure :: integrate => process_integrate
procedure :: final_integration => process_final_integration
procedure :: integrate_dummy => process_integrate_dummy
```

```
<Processes: procedures>+≡
```

```
subroutine process_integrate (process, instance, i_mci, n_it, n_calls, &
    adapt_grids, adapt_weights, final, pacify)
class(process_t), intent(inout) :: process
type(process_instance_t), intent(inout) :: instance
integer, intent(in) :: i_mci
integer, intent(in) :: n_it
integer, intent(in) :: n_calls
logical, intent(in), optional :: adapt_grids
logical, intent(in), optional :: adapt_weights
logical, intent(in), optional :: final, pacify
call process%mci_entry(i_mci)%integrate (instance, n_it, n_calls, &
    adapt_grids, adapt_weights, final, pacify, i_mci)
call instance%display_real_kinematics (i_mci)
end subroutine process_integrate
```

```
subroutine process_final_integration (process, i_mci)
class(process_t), intent(inout) :: process
integer, intent(in) :: i_mci
call process%mci_entry(i_mci)%final_integration ()
end subroutine process_final_integration
```

```
subroutine process_integrate_dummy (process)
class(process_t), intent(inout) :: process
type(integration_results_t) :: results
integer :: u_log
u_log = logfile_unit ()
call results%init (process%meta%type)
call results%display_init (process%meta%type, screen = .true., unit = u_log)
call results%new_pass ()
call results%record (1, 0, 0._default, 0._default, 0._default)
call results%display_final ()
end subroutine process_integrate_dummy
```

Display the final results for the sum of all components. (This is useful, obviously, only if there is more than one component.)

```
<Processes: process: TBP>+≡
```

```
procedure :: display_summed_results => process_display_summed_results
```

```

<Processes: procedures>+=
  subroutine process_display_summed_results (process)
    class(process_t), intent(inout) :: process
    type(integration_results_t) :: results
    integer :: u_log
    u_log = logfile_unit ()
    call results%init (process%meta%type)
    call results%display_init (process%meta%type, screen = .true., unit = u_log)
    call results%new_pass ()
    call results%record (1, 0, &
      process%get_integral (), &
      process%get_error (), &
      process%get_efficiency ())
    if (process%nlo_process) &
      call results%record_correction (process%get_correction (), &
        process%get_correction_error ())
    call results%display_final ()
  end subroutine process_display_summed_results

```

Run LaTeX/Metapost to generate a ps/pdf file for the integration history. We (re)write the driver file – just in case it has been missed before – then we compile it.

```

<Processes: process: TBP>+=
  procedure :: display_integration_history => &
    process_display_integration_history

<Processes: procedures>+=
  subroutine process_display_integration_history &
    (process, i_mci, filename, os_data, eff_reset)
    class(process_t), intent(inout) :: process
    integer, intent(in) :: i_mci
    type(string_t), intent(in) :: filename
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: eff_reset
    call integration_results_write_driver &
      (process%mc_entry(i_mci)%results, filename, eff_reset)
    call integration_results_compile_driver &
      (process%mc_entry(i_mci)%results, filename, os_data)
  end subroutine process_display_integration_history

```

Write a complete logfile (with hardcoded name based on the process ID). We do not write internal data.

```

<Processes: process: TBP>+=
  procedure :: write_logfile => process_write_logfile

<Processes: procedures>+=
  subroutine process_write_logfile (process, i_mci, filename)
    class(process_t), intent(inout) :: process
    integer, intent(in) :: i_mci
    type(string_t), intent(in) :: filename
    type(time_t) :: time
    integer :: unit, u
    unit = free_unit ()
    open (unit = unit, file = char (filename), action = "write", &

```

```

        status = "replace")
u = given_output_unit (unit)
write (u, "(A)") repeat ("#", 79)
call process%meta%write (u, .false., .false.)
write (u, "(A)") repeat ("#", 79)
write (u, "(3x,A,ES17.10)") "Integral   = ", &
    process%mc_entry(i_mci)%get_integral ()
write (u, "(3x,A,ES17.10)") "Error      = ", &
    process%mc_entry(i_mci)%get_error ()
write (u, "(3x,A,ES17.10)") "Accuracy   = ", &
    process%mc_entry(i_mci)%get_accuracy ()
write (u, "(3x,A,ES17.10)") "Chi2       = ", &
    process%mc_entry(i_mci)%get_chi2 ()
write (u, "(3x,A,ES17.10)") "Efficiency = ", &
    process%mc_entry(i_mci)%get_efficiency ()
call process%mc_entry(i_mci)%get_time (time, 10000)
if (time%is_known ()) then
    write (u, "(3x,A,1x,A)") "T(10k evt) = ", char (time%to_string_dhms ())
else
    write (u, "(3x,A)") "T(10k evt) = [undefined]"
end if
call process%mc_entry(i_mci)%results%write (u)
write (u, "(A)") repeat ("#", 79)
call process%mc_entry(i_mci)%results%write_chain_weights (u)
write (u, "(A)") repeat ("#", 79)
call process%mc_entry(i_mci)%counter%write (u)
write (u, "(A)") repeat ("#", 79)
select type (mci => process%mc_entry(i_mci)%mci)
type is (mci_midpoint_t)
    write (u, "(1x,A)") "MC Integrator is Midpoint rule"
type is (mci_vamp_t)
    write (u, "(1x,A)") "MC Integrator is VAMP"
    call write_separator (u)
    call mci%write_history (u)
    call write_separator (u)
    if (mci%grid_par%use_vamp_equivalences) then
        call vamp_equivalences_write (mci%equivalences, u)
    else
        write (u, "(3x,A)") "No VAMP equivalences have been used"
    end if
    call write_separator (u)
    call process%mc_entry(i_mci)%write_chain_weights (u)
class default
    write (u, "(1x,A)") "MC Integrator: [unknown]"
end select
write (u, "(A)") repeat ("#", 79)
call process%beam_config%data%write (u)
write (u, "(A)") repeat ("#", 79)
if (allocated (process%config%ef_cuts)) then
    write (u, "(3x,A)") "Cut expression:"
    call process%config%ef_cuts%write (u)
else
    write (u, "(3x,A)") "No cuts used."
end if

```

```

call write_separator (u)
if (allocated (process%config%ef_scale)) then
  write (u, "(3x,A)") "Scale expression:"
  call process%config%ef_scale%write (u)
else
  write (u, "(3x,A)") "No scale expression was given."
end if
call write_separator (u)
if (allocated (process%config%ef_fac_scale)) then
  write (u, "(3x,A)") "Factorization scale expression:"
  call process%config%ef_fac_scale%write (u)
else
  write (u, "(3x,A)") "No factorization scale expression was given."
end if
call write_separator (u)
if (allocated (process%config%ef_ren_scale)) then
  write (u, "(3x,A)") "Renormalization scale expression:"
  call process%config%ef_ren_scale%write (u)
else
  write (u, "(3x,A)") "No renormalization scale expression was given."
end if
call write_separator (u)
if (allocated (process%config%ef_weight)) then
  call write_separator (u)
  write (u, "(3x,A)") "Weight expression:"
  call process%config%ef_weight%write (u)
else
  write (u, "(3x,A)") "No weight expression was given."
end if
write (u, "(A)") repeat ("#", 79)
write (u, "(1x,A)") "Summary of quantum-number states:"
write (u, "(1x,A)") " + sign: allowed and contributing"
write (u, "(1x,A)") " no + : switched off at runtime"
call process%write_state_summary (u)
write (u, "(A)") repeat ("#", 79)
write (u, "(A)") "Variable list:"
call var_list_write (process%meta%var_list, u)
write (u, "(A)") repeat ("#", 79)
close (u)
end subroutine process_write_logfile

```

Display the quantum-number combinations of the process components, and their current status (allowed or switched off).

```

<Processes: process: TBP>+≡
  procedure :: write_state_summary => process_write_state_summary

<Processes: procedures>+≡
  subroutine process_write_state_summary (process, unit)
    class(process_t), intent(in) :: process
    integer, intent(in), optional :: unit
    integer :: i, i_component, u
    u = given_output_unit (unit)
    do i = 1, size (process%term)
      call write_separator (u)

```

```

        i_component = process%term(i)%i_component
        if (i_component /= 0) then
            call process%term(i)%write_state_summary &
                (process%component(i_component)%core, unit)
        end if
    end do
end subroutine process_write_state_summary

```

Prepare event generation for the specified MCI entry. This implies, in particular, checking the phase-space file.

```

<Processes: process: TBP>+≡
    procedure :: prepare_simulation => process_prepare_simulation
<Processes: procedures>+≡
    subroutine process_prepare_simulation (process, i_mci)
        class(process_t), intent(inout) :: process
        integer, intent(in) :: i_mci
        call process%mci_entry(i_mci)%prepare_simulation ()
    end subroutine process_prepare_simulation

```

Generate a weighted event. We select one of the available MCI integrators by its index `i_mci` and thus generate an event for the associated (group of) process component(s). The arguments exactly correspond to the initializer and finalizer above.

The resulting event is stored in the `process_instance` object, which also holds the workspace of the integrator.

Note: The `process` object is declared `intent(inout)` because it contains the random-number state, which changes for each event. Otherwise, all volatile data are inside the `instance` object.

```

<Processes: process: TBP>+≡
    procedure :: generate_weighted_event => process_generate_weighted_event
    procedure :: generate_unweighted_event => process_generate_unweighted_event
<Processes: procedures>+≡
    subroutine process_generate_weighted_event (process, instance, i_mci)
        class(process_t), intent(inout) :: process
        type(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_mci
        call process%mci_entry(i_mci)%generate_weighted_event (instance)
    end subroutine process_generate_weighted_event

    subroutine process_generate_unweighted_event (process, instance, i_mci)
        class(process_t), intent(inout) :: process
        type(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_mci
        call process%mci_entry(i_mci)%generate_unweighted_event (instance)
    end subroutine process_generate_unweighted_event

```

This replaces the event generation methods for the situation that the process instance object has been filled by other means (i.e., reading and/or recalculating its contents). We just have to fill in missing MCI data, especially the event weight.

```

<Processes: process: TBP>+≡

```

```

    procedure :: recover_event => process_recover_event
  <Processes: procedures>+≡
    subroutine process_recover_event (process, instance, i_term)
      class(process_t), intent(inout) :: process
      type(process_instance_t), intent(inout) :: instance
      integer, intent(in) :: i_term
      call process%mci_entry(instance%i_mci)%recover_event (instance, i_term)
    end subroutine process_recover_event

```

Retrieve process data

Tell whether integral (and error) are known.

```

  <Processes: process: TBP>+≡
    generic :: has_integral => has_integral_tot, has_integral_mci
    procedure :: has_integral_tot => process_has_integral_tot
    procedure :: has_integral_mci => process_has_integral_mci

  <Processes: procedures>+≡
    function process_has_integral_mci (process, i_mci) result (flag)
      class(process_t), intent(in) :: process
      integer, intent(in) :: i_mci
      logical :: flag
      flag = process%mci_entry(i_mci)%has_integral ()
    end function process_has_integral_mci

    function process_has_integral_tot (process) result (flag)
      class(process_t), intent(in) :: process
      logical :: flag
      integer :: i
      flag = .true.
      do i = 1, size (process%mci_entry)
        if (process%is_active_nlo_component (i)) &
          flag = flag .and. process%mci_entry(i)%has_integral ()
      end do
    end function process_has_integral_tot

```

Return the current integral and error obtained by the integrator *i_mci*.

```

  <Processes: process: TBP>+≡
    generic :: get_integral => get_integral_tot, get_integral_mci
    generic :: get_error => get_error_tot, get_error_mci
    generic :: get_efficiency => get_efficiency_tot, get_efficiency_mci
    procedure :: get_integral_tot => process_get_integral_tot
    procedure :: get_integral_mci => process_get_integral_mci
    procedure :: get_error_tot => process_get_error_tot
    procedure :: get_error_mci => process_get_error_mci
    procedure :: get_efficiency_tot => process_get_efficiency_tot
    procedure :: get_efficiency_mci => process_get_efficiency_mci

  <Processes: procedures>+≡
    function process_get_integral_mci (process, i_mci) result (integral)
      class(process_t), intent(in) :: process
      integer, intent(in) :: i_mci

```

```

    real(default) :: integral
    integral = process%mci_entry(i_mci)%get_integral ()
end function process_get_integral_mci

function process_get_error_mci (process, i_mci) result (error)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i_mci
    real(default) :: error
    error = process%mci_entry(i_mci)%get_error ()
end function process_get_error_mci

function process_get_efficiency_mci (process, i_mci) result (efficiency)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i_mci
    real(default) :: efficiency
    efficiency = process%mci_entry(i_mci)%get_efficiency ()
end function process_get_efficiency_mci

function process_get_integral_tot (process) result (integral)
    class(process_t), intent(in) :: process
    real(default) :: integral
    integer :: i
    integral = 0
    if (allocated (process%mci_entry)) then
        do i = 1, size (process%mci_entry)
            if (process%is_active_nlo_component(i)) &
                integral = integral + process%mci_entry(i)%get_integral ()
        end do
    end if
end function process_get_integral_tot

function process_get_error_tot (process) result (error)
    class(process_t), intent(in) :: process
    real(default) :: error
    real(default) :: variance
    integer :: i
    variance = 0
    if (allocated (process%mci_entry)) then
        do i = 1, size (process%mci_entry)
            if (process%is_active_nlo_component(i)) &
                variance = variance + process%mci_entry(i)%get_error () ** 2
        end do
    end if
    error = sqrt (variance)
end function process_get_error_tot

function process_get_efficiency_tot (process) result (efficiency)
    class(process_t), intent(in) :: process
    real(default) :: efficiency
    real(default) :: den, eff, int
    integer :: i
    den = 0
    if (allocated (process%mci_entry)) then
        do i = 1, size (process%mci_entry)

```



```

        if (process%is_active_nlo_component(i)) then
            int = process%get_integral (i)
            if (int > 0) then
                eff = process%mci_entry(i)%get_efficiency ()
                if (eff > 0) then
                    den = den + int / eff
                else
                    efficiency = 0
                    return
                end if
            end if
        end if
    end do
    if (den > 0) then
        efficiency = process%get_integral () / den
    else
        efficiency = 0
    end if
end function process_get_efficiency_tot

```

$\langle Processes: process: TBP \rangle + \equiv$

```

procedure :: get_correction => process_get_correction
procedure :: get_correction_error => process_get_correction_error

```

$\langle Processes: procedures \rangle + \equiv$

```

function process_get_correction (process) result (ratio)
    class(process_t), intent(in) :: process
    real(default) :: ratio
    real(default) :: int_real, int_virt, int_born
    int_born = process%mci_entry(1)%get_integral ()
    int_real = process%mci_entry(2)%get_integral ()
    int_virt = process%mci_entry(3)%get_integral ()
    ratio = (int_real + int_virt) / int_born
end function process_get_correction

function process_get_correction_error (process) result (error)
    class(process_t), intent(in) :: process
    real(default) :: error
    real(default) :: int_born, int_real, int_virt
    real(default) :: err_born, err_real, err_virt
    real(default) :: err2
    int_born = process%mci_entry(1)%get_integral ()
    int_real = process%mci_entry(2)%get_integral ()
    int_virt = process%mci_entry(3)%get_integral ()
    err_born = process%mci_entry(1)%get_error ()
    err_real = process%mci_entry(2)%get_error ()
    err_virt = process%mci_entry(3)%get_error ()
    err2 = (int_real + int_virt)**2 / int_born**4 * err_born**2 &
        + (err_real**2 + err_virt**2) / int_born**2
    error = sqrt (err2)
end function process_get_correction_error

```

$\langle Processes: process: TBP \rangle + \equiv$

```

        procedure :: component_reset_helicity => process_component_reset_helicity
    <Processes: procedures>+≡
        subroutine process_component_reset_helicity(proc, i)
            class(process_t), intent(inout) :: proc
            integer, intent(in) :: i
            select type (core => proc%component(i)%core)
                type is (prc_omega_t)
                    call core%reset_helicity_selection ()
            end select
            if (i == 2) then
                select type (core_sub_born => proc%component(i)%core_sub_born)
                    type is (prc_omega_t)
                        call core_sub_born%reset_helicity_selection ()
                end select
            end if
        end subroutine process_component_reset_helicity

```

```

    <Processes: process: TBP>+≡
        procedure :: is_nlo_calculation => process_is_nlo_calculation
    <Processes: procedures>+≡
        function process_is_nlo_calculation (process) result (nlo)
            class(process_t), intent(in) :: process
            logical :: nlo
            nlo = process%nlo_process
        end function process_is_nlo_calculation

```

Return nlo data of a process component

```

    <Processes: process: TBP>+≡
        procedure :: get_component_nlo_type => process_get_component_nlo_type
    <Processes: procedures>+≡
        function process_get_component_nlo_type (process, i_component) &
            result (nlo_type)
            class(process_t), intent(in) :: process
            integer, intent(in) :: i_component
            integer :: nlo_type
            nlo_type = process%component(i_component)%config%get_nlo_type ()
        end function process_get_component_nlo_type

```

```

    <Processes: process: TBP>+≡
        procedure :: get_component_associated_born &
            => process_get_component_associated_born
    <Processes: procedures>+≡
        function process_get_component_associated_born (process, i_component) &
            result (i_born)
            class(process_t), intent(in) :: process
            integer, intent(in) :: i_component
            integer :: i_born
            i_born = process%component(i_component)%config%get_associated_born ()
        end function process_get_component_associated_born

```

```

<Processes: process: TBP>+≡
  procedure :: get_n_allowed_born => process_get_n_allowed_born

<Processes: procedures>+≡
  function process_get_n_allowed_born (process, i_born) result (n_born)
    class(process_t), intent(inout) :: process
    integer, intent(in) :: i_born
    integer :: n_born
    n_born = process%term(i_born)%n_allowed

  end function process_get_n_allowed_born

<Processes: process: TBP>+≡
  procedure :: is_active_nlo_component => process_is_active_nlo_component

<Processes: procedures>+≡
  function process_is_active_nlo_component (process, i_component) &
    result (active)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i_component
    logical :: active
    associate (component => process%component(i_component))
      active = component%config%is_active_nlo_component () &
        .and. component%component_type <= COMP_MASTER
    end associate
  end function process_is_active_nlo_component

```

Return the MD5 sums that summarize the process component definitions. These values should be independent of parameters, beam details, expressions, etc. They can be used for checking the integrity of a process when reusing an old event file.

```

<Processes: process: TBP>+≡
  procedure :: get_md5sum_prc => process_get_md5sum_prc

<Processes: procedures>+≡
  function process_get_md5sum_prc (process, i_component) result (md5sum)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i_component
    character(32) :: md5sum
    if (process%component(i_component)%active) then
      md5sum = process%component(i_component)%config%get_md5sum ()
    else
      md5sum = ""
    end if
  end function process_get_md5sum_prc

```

Return the MD5 sums that summarize the state of the MCI integrators. These values should encode all process data, integration and phase space configuration, etc., and the integration results. They can thus be used for checking the integrity of an event-generation setup when reusing an old event file.

```

<Processes: process: TBP>+≡
  procedure :: get_md5sum_mci => process_get_md5sum_mci

```

```

<Processes: procedures>+=
  function process_get_md5sum_mci (process, i_mci) result (md5sum)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i_mci
    character(32) :: md5sum
    md5sum = process%mci_entry(i_mci)%get_md5sum ()
  end function process_get_md5sum_mci

```

Return the MD5 sum of the process configuration. This should encode the process setup, data, and expressions, but no integration results.

```

<Processes: process: TBP>+=
  procedure :: get_md5sum_cfg => process_get_md5sum_cfg

<Processes: procedures>+=
  function process_get_md5sum_cfg (process) result (md5sum)
    class(process_t), intent(in) :: process
    character(32) :: md5sum
    md5sum = process%config%md5sum
  end function process_get_md5sum_cfg

```

27.3.2 Metadata

This information describes the process and its environment. It is fixed upon initialization.

The `id` string is the name of the process object, as given by the user. The matrix element generator will use this string for naming Fortran procedures and types, so it should qualify as a Fortran name.

The `num_id` is meaningful if nonzero. It is used for communication with external programs or file standards which do not support string IDs.

The `run_id` string distinguishes among several runs for the same process. It identifies process instances with respect to adapted integration grids and similar run-specific data. The run ID is kept when copying processes for creating instances, however, so it does not distinguish event samples.

The `var_list` is a snapshot of the variable list, taken at the point where the process was initialized.

The `lib` pointer accesses the process library where the process definition and the process driver are located.

The `lib_index` is the index of entry in the process library that corresponds to the current process.

The `component_id` array identifies the individual process components.

The `component_description` is an array of human-readable strings that characterize the process components, for instance `a, b => c, d`.

The `active` mask array marks those components which are active. The others are skipped.

```

<Processes: process part types>=
  type :: process_metadata_t
  private
    integer :: type = PRC_UNKNOWN
    type(string_t) :: id
    integer :: num_id = 0

```

```

type(string_t) :: run_id
type(var_list_t) :: var_list
type(process_library_t), pointer :: lib => null ()
integer :: lib_index = 0
integer :: n_components = 0
type(string_t), dimension(:), allocatable :: component_id
type(string_t), dimension(:), allocatable :: component_description
logical, dimension(:), allocatable :: active
contains
  <Processes: process metadata: TBP>
end type process_metadata_t

```

The local var list is a snapshot and needs a finalizer.

```

<Processes: process metadata: TBP>≡
  procedure :: final => process_metadata_final

<Processes: procedures>+≡
  subroutine process_metadata_final (meta)
    class(process_metadata_t), intent(inout) :: meta
    call meta%var_list%final (follow_link=.true.)
  end subroutine process_metadata_final

```

Output: ID and run ID. We write the variable list only upon request.

```

<Processes: process metadata: TBP>+≡
  procedure :: write => process_metadata_write

<Processes: procedures>+≡
  subroutine process_metadata_write (meta, u, var_list, screen)
    class(process_metadata_t), intent(in) :: meta
    integer, intent(in) :: u
    logical, intent(in) :: var_list, screen
    integer :: i
    select case (meta%type)
    case (PRC_UNKNOWN)
      if (screen) then
        write (msg_buffer, "(A)") "Process [undefined]"
      else
        write (u, "(1x,A)") "Process [undefined]"
      end if
      return
    case (PRC_DECAY)
      if (screen) then
        write (msg_buffer, "(A,1x,A,A,A)") "Process [decay]:", &
          "", char (meta%id), ""
      else
        write (u, "(1x,A)", advance="no") "Process [decay]:"
      end if
    case (PRC_SCATTERING)
      if (screen) then
        write (msg_buffer, "(A,1x,A,A,A)") "Process [scattering]:", &
          "", char (meta%id), ""
      else
        write (u, "(1x,A)", advance="no") "Process [scattering]:"
      end if
    end select
  end subroutine process_metadata_write

```

```

case default
    call msg_bug ("process_write: undefined process type")
end select
if (screen) then
    call msg_message ()
else
    write (u, "(1x,A,A,A)") "'", char (meta%id), "'"
end if
if (meta%num_id /= 0) then
    if (screen) then
        write (msg_buffer, "(2x,A,I0)") "ID (num)      = ", meta%num_id
        call msg_message ()
    else
        write (u, "(3x,A,I0)") "ID (num)      = ", meta%num_id
    end if
end if
if (screen) then
    if (meta%run_id /= "") then
        write (msg_buffer, "(2x,A,A,A)") "Run ID      = '", &
            char (meta%run_id), "'"
        call msg_message ()
    end if
else
    write (u, "(3x,A,A,A)") "Run ID      = '", char (meta%run_id), "'"
end if
if (associated (meta%lib)) then
    if (screen) then
        write (msg_buffer, "(2x,A,A,A)") "Library name = '", &
            char (meta%lib%get_name ()), "'"
        call msg_message ()
    else
        write (u, "(3x,A,A,A)") "Library name = '", &
            char (meta%lib%get_name ()), "'"
    end if
else
    if (screen) then
        write (msg_buffer, "(2x,A)") "Library name = [not associated]"
        call msg_message ()
    else
        write (u, "(3x,A)") "Library name = [not associated]"
    end if
end if
if (screen) then
    write (msg_buffer, "(2x,A,I0)") "Process index = ", meta%lib_index
    call msg_message ()
else
    write (u, "(3x,A,I0)") "Process index = ", meta%lib_index
end if
if (allocated (meta%component_id)) then
    if (screen) then
        if (any (meta%active)) then
            write (msg_buffer, "(2x,A)") "Process components:"
        else
            write (msg_buffer, "(2x,A)") "Process components: [none]"
        end if
    end if
end if

```

```

        end if
        call msg_message ()
    else
        write (u, "(3x,A)" "Process components:"
    end if
    do i = 1, size (meta%component_id)
        if (.not. meta%active(i)) cycle
        if (screen) then
            write (msg_buffer, "(4x,I0,9A)" i, ": '", &
                char (meta%component_id (i)), "' : ", &
                char (meta%component_description (i))
            call msg_message ()
        else
            write (u, "(5x,I0,9A)" i, ": '", &
                char (meta%component_id (i)), "' : ", &
                char (meta%component_description (i))
        end if
    end do
end if
if (screen) then
    write (msg_buffer, "(A)" repeat (" ", 72)
    call msg_message ()
else
    call write_separator (u)
end if
if (screen) return
if (var_list) then
    write (u, "(1x,A)" "Variable list:"
    call write_separator (u)
    call var_list_write (meta%var_list, u)
else
    write (u, "(1x,A)" "Variable list: [not shown]"
end if
end subroutine process_metadata_write

```

Short output: list components.

(Processes: process metadata: TBP)+≡

```
procedure :: show => process_metadata_show
```

(Processes: procedures)+≡

```

subroutine process_metadata_show (meta, u, model_name)
    class(process_metadata_t), intent(in) :: meta
    integer, intent(in) :: u
    type(string_t), intent(in) :: model_name
    integer :: i
    select case (meta%type)
    case (PRC_UNKNOWN)
        write (u, "(A)" "Process: [undefined]"
        return
    case default
        write (u, "(A)", advance="no") "Process:"
    end select
    write (u, "(1x,A)", advance="no") char (meta%id)
    select case (meta%num_id)

```

```

case (0)
case default
    write (u, "(1x,'(,I0,')')", advance="no") meta%num_id
end select
select case (char (model_name))
case ("")
case default
    write (u, "(1x,[',A,']')", advance="no") char (model_name)
end select
write (u, *)
if (allocated (meta%component_id)) then
    do i = 1, size (meta%component_id)
        if (meta%active(i)) then
            write (u, "(2x,I0,':',1x,A)") i, &
                char (meta%component_description (i))
        end if
    end do
end if
end subroutine process_metadata_show

```

Initialize.

(Processes: process metadata: TBP)+≡

```

procedure :: init => process_metadata_init

```

(Processes: procedures)+≡

```

subroutine process_metadata_init (meta, id, run_id, lib)
class(process_metadata_t), intent(out) :: meta
type(string_t), intent(in) :: id
type(string_t), intent(in) :: run_id
type(process_library_t), intent(in), target :: lib
select case (lib%get_n_in (id))
case (1); meta%type = PRC_DECAY
case (2); meta%type = PRC_SCATTERING
case default
    call msg_bug ("Process ' ' // char (id) // "': impossible n_in")
end select
meta%id = id
meta%run_id = run_id
meta%lib => lib
meta%lib_index = lib%get_entry_index (id)
meta%num_id = lib%get_num_id (id)
call lib%get_component_list (id, meta%component_id)
meta%n_components = size (meta%component_id)
call lib%get_component_description_list (id, meta%component_description)
allocate (meta%active (meta%n_components), source = .true.)
end subroutine process_metadata_init

```

Mark a component as inactive.

(Processes: process metadata: TBP)+≡

```

procedure :: deactivate_component => process_metadata_deactivate_component

```

(Processes: procedures)+≡

```

subroutine process_metadata_deactivate_component (meta, i)
class(process_metadata_t), intent(inout) :: meta

```



```

integer, intent(in) :: i
call msg_message ("Process component '" &
    // char (meta%component_id(i)) // "': matrix element vanishes")
meta%active(i) = .false.
end subroutine process_metadata_deactivate_component

```

27.3.3 Generic Configuration Data

This information concerns physical and technical properties of the process. It is fixed upon initialization, using data from the process specification and the variable list.

The number **n_in** is the number of incoming beam particles, simultaneously the number of incoming partons, 1 for a decay and 2 for a scattering process. (The number of outgoing partons may depend on the process component.)

The number **n_components** is the number of components that constitute the current process.

The number **n_terms** is the number of distinct contributions to the scattering matrix that constitute the current process. Each component may generate several terms.

The number **n_mci** is the number of independent MC integration configurations that this process uses. Distinct process components that share a MCI configuration may be combined pointwise. (Nevertheless, a given MC variable set may correspond to several “nearby” kinematical configurations.) This is also the number of distinct sampling-function results that this process can generate. Process components that use distinct variable sets are added only once after an integration pass has completed.

The **model** pointer identifies the physics model and its parameters. This is a pointer to an external object.

The **rng_factory** component spawns independent random-number generators for use in integration, event generation, and event postprocessing.

Various **parse_node_t** objects are taken from the SINDARIN input. They encode expressions for evaluating cuts and scales. The workspaces for evaluating those expressions are set up in the **effective_state** subobjects. Note that these are really pointers, so the actual nodes are not stored inside the process object.

The **md5sum** is taken and used to verify the process configuration when re-reading data from file.

(Processes: process part types)+≡

```

type :: process_config_data_t
private
integer :: n_in = 0
integer :: n_components = 0
integer :: n_terms = 0
integer :: n_mci = 0
type(os_data_t) :: os_data
class(rng_factory_t), allocatable :: rng_factory
type(string_t) :: model_name
class(model_data_t), pointer :: model => null ()
type(qcd_t) :: qcd
class(expr_factory_t), allocatable :: ef_cuts

```

```

class(expr_factory_t), allocatable :: ef_scale
class(expr_factory_t), allocatable :: ef_fac_scale
class(expr_factory_t), allocatable :: ef_ren_scale
class(expr_factory_t), allocatable :: ef_weight
character(32) :: md5sum = ""
contains
  <Processes: process config data: TBP>
end type process_config_data_t

```

Here, we may compress the expressions for cuts etc.

```

<Processes: process config data: TBP>≡
  procedure :: write => process_config_data_write

<Processes: procedures>+≡
  subroutine process_config_data_write (config, u, &
    counters, os_data, rng_factory, model, expressions)
    class(process_config_data_t), intent(in) :: config
    integer, intent(in) :: u
    logical, intent(in) :: counters
    logical, intent(in) :: os_data
    logical, intent(in) :: rng_factory
    logical, intent(in) :: model
    logical, intent(in) :: expressions
    write (u, "(1x,A)") "Configuration data:"
    if (counters) then
      write (u, "(3x,A,I0)") "Number of incoming particles = ", &
        config%n_in
      write (u, "(3x,A,I0)") "Number of process components = ", &
        config%n_components
      write (u, "(3x,A,I0)") "Number of process terms = ", &
        config%n_terms
      write (u, "(3x,A,I0)") "Number of MCI configurations = ", &
        config%n_mci
    end if
    if (os_data) then
      call os_data_write (config%os_data, u)
    end if
    if (associated (config%model)) then
      write (u, "(3x,A,A)") "Model = ", char (config%model_name)
      if (model) then
        call write_separator (u)
        call config%model%write (u)
        call write_separator (u)
      end if
    else
      write (u, "(3x,A,A,A)") "Model = ", char (config%model_name), &
        " [not associated]"
    end if
    call config%qcd%write (u, show_md5sum = .false.)
    if (rng_factory) then
      if (allocated (config%rng_factory)) then
        write (u, "(2x)", advance = "no")
        call config%rng_factory%write (u)
      end if
    end if

```

```

end if
call write_separator (u)
if (expressions) then
  if (allocated (config%ef_cuts)) then
    call write_separator (u)
    write (u, "(3x,A)") "Cut expression:"
    call config%ef_cuts%write (u)
  end if
  if (allocated (config%ef_scale)) then
    call write_separator (u)
    write (u, "(3x,A)") "Scale expression:"
    call config%ef_scale%write (u)
  end if
  if (allocated (config%ef_fac_scale)) then
    call write_separator (u)
    write (u, "(3x,A)") "Factorization scale expression:"
    call config%ef_fac_scale%write (u)
  end if
  if (allocated (config%ef_ren_scale)) then
    call write_separator (u)
    write (u, "(3x,A)") "Renormalization scale expression:"
    call config%ef_ren_scale%write (u)
  end if
  if (allocated (config%ef_weight)) then
    call write_separator (u)
    write (u, "(3x,A)") "Weight expression:"
    call config%ef_weight%write (u)
  end if
else
  call write_separator (u)
  write (u, "(3x,A)") "Expressions (cut, scales, weight): [not shown]"
end if
if (config%md5sum /= "") then
  call write_separator (u)
  write (u, "(3x,A,A,A)") "MD5 sum (config) = '", config%md5sum, "'"
end if
end subroutine process_config_data_write

```

Initialize. We use information from the process metadata and from the process library, given the process ID. We also store the currently active OS data set.

The model that we import here should be an instance of the global model. If we create the instance outside, we can make it an extension of the basic `model_data_t`. This will allow us to synchronize the variable list with the model. Using a pointer instead of an allocatable, we can guarantee the `target` attribute.

The RNG factory object is imported by moving the allocation.

```

<Processes: process config data: TBP>+=
  procedure :: init => process_config_data_init

<Processes: procedures>+=
  subroutine process_config_data_init &
    (config, meta, os_data, qcd, rng_factory, model)
    class(process_config_data_t), intent(out) :: config

```

```

type(process_metadata_t), intent(in) :: meta
type(os_data_t), intent(in) :: os_data
type(qcd_t), intent(in) :: qcd
class(rng_factory_t), intent(inout), allocatable :: rng_factory
class(model_data_t), intent(inout), pointer :: model
config%n_in = meta%lib%get_n_in (meta%id)
config%n_components = size (meta%component_id)
config%os_data = os_data
config%qcd = qcd
call move_alloc (from = rng_factory, to = config%rng_factory)
config%model_name = model%get_name ()
config%model => model
model => null ()
end subroutine process_config_data_init

```

Since the captured model is a separate object allocated via a pointer, we need a finalizer.

```

<Processes: process config data: TBP>+=
  procedure :: final => process_config_data_final

<Processes: procedures>+=
  subroutine process_config_data_final (config)
    class(process_config_data_t), intent(inout) :: config
    if (associated (config%model)) then
      call config%model%final ()
      deallocate (config%model)
    end if
  end subroutine process_config_data_final

```

Compute the MD5 sum of the configuration data. This encodes, in particular, the model and the expressions for cut, scales, weight, etc. It should not contain the IDs and number of components, etc., since the MD5 sum should be useful for integrating individual components.

This is done only once. If the MD5 sum is nonempty, the calculation is skipped.

```

<Processes: process config data: TBP>+=
  procedure :: compute_md5sum => process_config_data_compute_md5sum

<Processes: procedures>+=
  subroutine process_config_data_compute_md5sum (config)
    class(process_config_data_t), intent(inout) :: config
    integer :: u
    if (config%md5sum == "") then
      u = free_unit ()
      open (u, status = "scratch", action = "readwrite")
      call config%write (u, counters = .false., os_data = .false., &
        rng_factory = .false., model = .true., expressions = .true.)
      rewind (u)
      config%md5sum = md5sum (u)
      close (u)
    end if
  end subroutine process_config_data_compute_md5sum

```

27.3.4 Beam configuration

The object `data` holds all details about the initial beam configuration. The allocatable array `sf` holds the structure-function configuration blocks. There are `n_strfun` entries in the structure-function chain (not counting the initial beam object). We maintain `n_channel` independent parameterizations of this chain. If this is greater than zero, we need a multi-channel sampling algorithm, where for each point one channel is selected to generate kinematics.

The number of parameters that are required for generating a structure-function chain is `n_sfpar`.

The flag `azimuthal_dependence` tells whether the process setup is symmetric about the beam axis in the c.m. system. This implies that there is no transversal beam polarization. The flag `lab_is_cm_frame` is obvious.

```

<Processes: process part types>+=
  type :: process_beam_config_t
    private
    type(bm_data_t) :: data
    integer :: n_strfun = 0
    integer :: n_channel = 1
    integer :: n_sfpar = 0
    type(sf_config_t), dimension(:), allocatable :: sf
    type(sf_channel_t), dimension(:), allocatable :: sf_channel
    logical :: azimuthal_dependence = .false.
    logical :: lab_is_cm_frame = .true.
    character(32) :: md5sum = ""
    logical :: sf_trace = .false.
    type(string_t) :: sf_trace_file
  contains
    <Processes: process beam config: TBP>
  end type process_beam_config_t

```

Here we write beam data only if they are actually used.

```

<Processes: process beam config: TBP>=
  procedure :: write => process_beam_config_write

<Processes: procedures>+=
  subroutine process_beam_config_write (object, u)
    class(process_beam_config_t), intent(in) :: object
    integer, intent(in) :: u
    integer :: i, c
    call object%data%write (u)
    if (object%data%initialized) then
      write (u, "(3x,A,L1)") "Azimuthal dependence    = ", &
        object%azimuthal_dependence
      write (u, "(3x,A,L1)") "Lab frame is c.m. frame = ", &
        object%lab_is_cm_frame
      if (object%md5sum /= "") then
        write (u, "(3x,A,A,A)") "MD5 sum (beams/strf) = '", &
          object%md5sum, "'"
      end if
      if (allocated (object%sf)) then
        do i = 1, size (object%sf)
          call object%sf(i)%write (u)
        end do
      end if
    end if
  end subroutine process_beam_config_write

```

```

        end do
        if (any_sf_channel_has_mapping (object%sf_channel)) then
            write (u, "(1x,A,L1)") "Structure-function mappings per channel:"
            do c = 1, object%n_channel
                write (u, "(3x,I0,':')", advance="no") c
                call object%sf_channel(c)%write (u)
            end do
        end if
    end if
end if
end subroutine process_beam_config_write

```

The beam data have a finalizer. We assume that there is none for the structure-function data.

```

<Processes: process beam config: TBP>+≡
    procedure :: final => process_beam_config_final

<Processes: procedures>+≡
    subroutine process_beam_config_final (object)
        class(process_beam_config_t), intent(inout) :: object
        call beam_data_final (object%data)
    end subroutine process_beam_config_final

```

Initialize the beam setup with a given beam structure object.

```

<Processes: process beam config: TBP>+≡
    procedure :: init_beam_structure => process_beam_config_init_beam_structure

<Processes: procedures>+≡
    subroutine process_beam_config_init_beam_structure &
        (beam_config, beam_structure, sqrts, model, decay_rest_frame)
        class(process_beam_config_t), intent(out) :: beam_config
        type(beam_structure_t), intent(in) :: beam_structure
        logical, intent(in), optional :: decay_rest_frame
        real(default), intent(in) :: sqrts
        class(model_data_t), intent(in), target :: model
        call beam_data_init_structure (beam_config%data, &
            beam_structure, sqrts, model, decay_rest_frame)
        beam_config%lab_is_cm_frame = beam_data_cm_frame (beam_config%data)
    end subroutine process_beam_config_init_beam_structure

```

Initialize the beam setup for a scattering process with specified flavor combination, other properties taken from the beam structure object (if any).

```

<Processes: process beam config: TBP>+≡
    procedure :: init_scattering => process_beam_config_init_scattering

<Processes: procedures>+≡
    subroutine process_beam_config_init_scattering &
        (beam_config, flv_in, sqrts, beam_structure)
        class(process_beam_config_t), intent(out) :: beam_config
        type(flavor_t), dimension(2), intent(in) :: flv_in
        real(default), intent(in) :: sqrts
        type(beam_structure_t), intent(in), optional :: beam_structure
        if (present (beam_structure)) then

```

```

        if (beam_structure%polarized ()) then
            call beam_data_init_sqrts (beam_config%data, sqrts, flv_in, &
                beam_structure%get_smatrix (), beam_structure%get_pol_f ())
        else
            call beam_data_init_sqrts (beam_config%data, sqrts, flv_in)
        end if
    else
        call beam_data_init_sqrts (beam_config%data, sqrts, flv_in)
    end if
end subroutine process_beam_config_init_scattering

```

Initialize the beam setup for a decay process with specified flavor, other properties taken from the beam structure object (if present).

For a cascade decay, we set `rest_frame` to false, indicating a event-wise varying momentum. The beam data itself are initialized for the particle at rest.

(Processes: process beam config: TBP)+≡

```

    procedure :: init_decay => process_beam_config_init_decay

```

(Processes: procedures)+≡

```

    subroutine process_beam_config_init_decay &
        (beam_config, flv_in, rest_frame, beam_structure)
    class(process_beam_config_t), intent(out) :: beam_config
    type(flavor_t), dimension(1), intent(in) :: flv_in
    logical, intent(in), optional :: rest_frame
    type(beam_structure_t), intent(in), optional :: beam_structure
    if (present (beam_structure)) then
        if (beam_structure%polarized ()) then
            call beam_data_init_decay (beam_config%data, flv_in, &
                beam_structure%get_smatrix (), beam_structure%get_pol_f (), &
                rest_frame = rest_frame)
        else
            call beam_data_init_decay (beam_config%data, flv_in, &
                rest_frame = rest_frame)
        end if
    else
        call beam_data_init_decay (beam_config%data, flv_in, &
            rest_frame = rest_frame)
    end if
    beam_config%lab_is_cm_frame = beam_data_cm_frame (beam_config%data)
end subroutine process_beam_config_init_decay

```

Print an informative message.

(Processes: process beam config: TBP)+≡

```

    procedure :: startup_message => process_beam_config_startup_message

```

(Processes: procedures)+≡

```

    subroutine process_beam_config_startup_message &
        (beam_config, unit, beam_structure)
    class(process_beam_config_t), intent(in) :: beam_config
    integer, intent(in), optional :: unit
    type(beam_structure_t), intent(in), optional :: beam_structure
    integer :: u
    u = free_unit ()
    open (u, status="scratch", action="readwrite")

```

```

        if (present (beam_structure)) then
            call beam_structure%write (u)
        end if
        call beam_data_write (beam_config%data, u)
        rewind (u)
        do
            read (u, "(1x,A)", end=1) msg_buffer
            call msg_message ()
        end do
1    continue
        close (u)
    end subroutine process_beam_config_startup_message

```

Allocate the structure-function array.

```

<Processes: process beam config: TBP>+≡
    procedure :: init_sf_chain => process_beam_config_init_sf_chain

<Processes: procedures>+≡
    subroutine process_beam_config_init_sf_chain &
        (beam_config, sf_config, sf_trace_file)
        class(process_beam_config_t), intent(inout) :: beam_config
        type(sf_config_t), dimension(:), intent(in) :: sf_config
        type(string_t), intent(in), optional :: sf_trace_file
        integer :: i
        beam_config%n_strfun = size (sf_config)
        allocate (beam_config%sf (beam_config%n_strfun))
        do i = 1, beam_config%n_strfun
            associate (sf => sf_config(i))
                call beam_config%sf(i)%init (sf%i, sf%data)
                if (.not. sf%data%is_generator ()) then
                    beam_config%n_sfpar = beam_config%n_sfpar + sf%data%get_n_par ()
                end if
            end associate
        end do
        if (present (sf_trace_file)) then
            beam_config%sf_trace = .true.
            beam_config%sf_trace_file = sf_trace_file
        end if
    end subroutine process_beam_config_init_sf_chain

```

Allocate the structure-function mapping channel array, given the requested number of channels.

```

<Processes: process beam config: TBP>+≡
    procedure :: allocate_sf_channels => process_beam_config_allocate_sf_channels

<Processes: procedures>+≡
    subroutine process_beam_config_allocate_sf_channels (beam_config, n_channel)
        class(process_beam_config_t), intent(inout) :: beam_config
        integer, intent(in) :: n_channel
        beam_config%n_channel = n_channel
        call allocate_sf_channels (beam_config%sf_channel, &
            n_channel = n_channel, &
            n_strfun = beam_config%n_strfun)
    end subroutine process_beam_config_allocate_sf_channels

```


Set a structure-function mapping channel for an array of structure-function entries, for a single channel. (The default is no mapping.)

```

(Processes: process beam config: TBP)+≡
  procedure :: set_sf_channel => process_beam_config_set_sf_channel

(Processes: procedures)+≡
  subroutine process_beam_config_set_sf_channel (beam_config, c, sf_channel)
    class(process_beam_config_t), intent(inout) :: beam_config
    integer, intent(in) :: c
    type(sf_channel_t), intent(in) :: sf_channel
    beam_config%sf_channel(c) = sf_channel
  end subroutine process_beam_config_set_sf_channel

```

Print an informative startup message.

```

(Processes: process beam config: TBP)+≡
  procedure :: sf_startup_message => process_beam_config_sf_startup_message

(Processes: procedures)+≡
  subroutine process_beam_config_sf_startup_message &
    (beam_config, sf_string, unit)
    class(process_beam_config_t), intent(in) :: beam_config
    type(string_t), intent(in) :: sf_string
    integer, intent(in), optional :: unit
    if (beam_config%n_strfun > 0) then
      call msg_message ("Beam structure: " // char (sf_string), unit = unit)
      write (msg_buffer, "(A,3(1x,I0,1x,A))") &
        "Beam structure:", &
        beam_config%n_channel, "channels,", &
        beam_config%n_sfpar, "dimensions"
      call msg_message (unit = unit)
      if (beam_config%sf_trace) then
        call msg_message ("Beam structure: tracing &
          &values in '" // char (beam_config%sf_trace_file) // "'")
      end if
    end if
  end subroutine process_beam_config_sf_startup_message

```

Return the PDF set currently in use, if any. This should be unique, so we scan the structure functions until we get a nonzero number.

(This implies that if the PDF set is not unique (e.g., proton and photon structure used together), this doesn't work correctly.)

```

(Processes: process beam config: TBP)+≡
  procedure :: get_pdf_set => process_beam_config_get_pdf_set

(Processes: procedures)+≡
  function process_beam_config_get_pdf_set (beam_config) result (pdf_set)
    class(process_beam_config_t), intent(in) :: beam_config
    integer :: pdf_set
    integer :: i
    if (allocated (beam_config%sf)) then
      do i = 1, size (beam_config%sf)
        pdf_set = beam_config%sf(i)%get_pdf_set ()
      end do
    end if
  end function process_beam_config_get_pdf_set

```

```

        if (pdf_set /= 0) return
    end do
    else
        pdf_set = 0
    end if
end function process_beam_config_get_pdf_set

```

Compute the MD5 sum for the complete beam setup. We rely on the default output of `write` to contain all relevant data.

This is done only once, when the MD5 sum is still empty.

```

<Processes: process beam config: TBP>+≡
    procedure :: compute_md5sum => process_beam_config_compute_md5sum

<Processes: procedures>+≡
    subroutine process_beam_config_compute_md5sum (beam_config)
        class(process_beam_config_t), intent(inout) :: beam_config
        integer :: u
        if (beam_config%md5sum == "") then
            u = free_unit ()
            open (u, status = "scratch", action = "readwrite")
            call beam_config%write (u)
            rewind (u)
            beam_config%md5sum = md5sum (u)
            close (u)
        end if
    end subroutine process_beam_config_compute_md5sum

```

Process call statistics

This object can record process calls, categorized by evaluation status. It is a part of the `mci_entry` component below.

```

<Processes: types>≡
    type :: process_counter_t
        integer :: total = 0
        integer :: failed_kinematics = 0
        integer :: failed_cuts = 0
        integer :: passed = 0
        integer :: evaluated = 0
        integer :: complete = 0
    contains
        <Processes: process counter: TBP>
    end type process_counter_t

```

Here are the corresponding numeric codes:

```

<Processes: parameters>≡
    integer, parameter :: STAT_UNDEFINED = 0
    integer, parameter :: STAT_INITIAL = 1
    integer, parameter :: STAT_ACTIVATED = 2
    integer, parameter :: STAT_BEAM_MOMENTA = 3
    integer, parameter :: STAT_FAILED_KINEMATICS = 4
    integer, parameter :: STAT_SEED_KINEMATICS = 5

```

```

integer, parameter :: STAT_HARD_KINEMATICS = 6
integer, parameter :: STAT_EFF_KINEMATICS = 7
integer, parameter :: STAT_FAILED_CUTS = 8
integer, parameter :: STAT_PASSED_CUTS = 9
integer, parameter :: STAT_EVALUATED_TRACE = 10
integer, parameter :: STAT_EVENT_COMPLETE = 11

integer, parameter, public :: COMP_DEFAULT = 0
integer, parameter, public :: COMP_MASTER = 1
integer, parameter, public :: COMP_VIRT = 2
integer, parameter, public :: COMP_REAL = 3
integer, parameter, public :: COMP_PDF = 4
integer, parameter, public :: COMP_SUB = 5

```

Output.

```

<Processes: process counter: TBP>≡
  procedure :: write => process_counter_write

<Processes: procedures>+≡
  subroutine process_counter_write (object, unit)
    class(process_counter_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    if (object%total > 0) then
      write (u, "(1x,A)") "Call statistics (current run):"
      write (u, "(3x,A,I0)") "total          = ", object%total
      write (u, "(3x,A,I0)") "failed kin. = ", object%failed_kinematics
      write (u, "(3x,A,I0)") "failed cuts = ", object%failed_cuts
      write (u, "(3x,A,I0)") "passed cuts = ", object%passed
      write (u, "(3x,A,I0)") "evaluated   = ", object%evaluated
    else
      write (u, "(1x,A)") "Call statistics (current run): [no calls]"
    end if
  end subroutine process_counter_write

```

Reset. Just enforce default initialization.

```

<Processes: process counter: TBP>+≡
  procedure :: reset => process_counter_reset

<Processes: procedures>+≡
  subroutine process_counter_reset (counter)
    class(process_counter_t), intent(out) :: counter
  end subroutine process_counter_reset

```

We record an event according to the lowest status code greater or equal to the actual status. This is actually done by the process instance; the process object just copies the instance counter.

```

<Processes: process counter: TBP>+≡
  procedure :: record => process_counter_record

<Processes: procedures>+≡
  subroutine process_counter_record (counter, status)
    class(process_counter_t), intent(inout) :: counter

```

```

integer, intent(in) :: status
if (status <= STAT_FAILED_KINEMATICS) then
  counter%failed_kinematics = counter%failed_kinematics + 1
else if (status <= STAT_FAILED_CUTS) then
  counter%failed_cuts = counter%failed_cuts + 1
else if (status <= STAT_PASSED_CUTS) then
  counter%passed = counter%passed + 1
else
  counter%evaluated = counter%evaluated + 1
end if
counter%total = counter%total + 1
end subroutine process_counter_record

```

27.3.5 Multi-channel integration

The `process_mci_entry_t` block contains, for each process component that is integrated independently, the configuration data for its MC input parameters. Each input parameter set is handled by a `mci_t` integrator.

The MC input parameter set is broken down into the parameters required by the structure-function chain and the parameters required by the phase space of the elementary process.

The MD5 sum collects all information about the associated processes that may affect the integration. It does not contain the MCI object itself or integration results.

MC integration is organized in passes. Each pass may consist of several iterations, and for each iteration there is a number of calls. We store explicitly the values that apply to the current pass. Previous values are archived in the `results` object.

The `counter` receives the counter statistics from the associated process instance, for diagnostics.

The `results` object records results, broken down in passes and iterations.

(Processes: process part types)+≡

```

type :: process_mci_entry_t
  integer :: i_mci = 0
  integer, dimension(:), allocatable :: i_component
  integer :: process_type = PRC_UNKNOWN
  integer :: n_par = 0
  integer :: n_par_sf = 0
  integer :: n_par_phs = 0
  character(32) :: md5sum = ""
  integer :: pass = 0
  integer :: n_it = 0
  integer :: n_calls = 0
  logical :: activate_timer = .false.
  real(default) :: error_threshold = 0
  class(mci_t), allocatable :: mci
  type(process_counter_t) :: counter
  type(integration_results_t) :: results
  logical :: negative_weights
  logical :: combined_integration = .false.
contains

```

```

    <Processes: process mci entry: TBP>
end type process_mci_entry_t

```

Finalizer for the mci component.

```

<Processes: process mci entry: TBP>≡
    procedure :: final => process_mci_entry_final

<Processes: procedures>+≡
    subroutine process_mci_entry_final (object)
        class(process_mci_entry_t), intent(inout) :: object
        if (allocated (object%mci)) call object%mci%final ()
    end subroutine process_mci_entry_final

```

Output. Write pass/iteration information only if set (the pass index is nonzero). Write the MCI block only if it exists (for some self-tests it does not). Write results only if there are any.

```

<Processes: process mci entry: TBP>+≡
    procedure :: write => process_mci_entry_write

<Processes: procedures>+≡
    subroutine process_mci_entry_write (object, unit, pacify)
        class(process_mci_entry_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: pacify
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A,I0)") "Associated components = ", object%i_component
        write (u, "(3x,A,I0)") "MC input parameters = ", object%n_par
        write (u, "(3x,A,I0)") "MC parameters (SF) = ", object%n_par_sf
        write (u, "(3x,A,I0)") "MC parameters (PHS) = ", object%n_par_phs
        if (object%pass > 0) then
            write (u, "(3x,A,I0)") "Current pass = ", object%pass
            write (u, "(3x,A,I0)") "Number of iterations = ", object%n_it
            write (u, "(3x,A,I0)") "Number of calls = ", object%n_calls
        end if
        if (object%md5sum /= "") then
            write (u, "(3x,A,A,A)") "MD5 sum (components) = '", object%md5sum, "'"
        end if
        if (allocated (object%mci)) then
            call object%mci%write (u)
        end if
        call object%counter%write (u)
        if (object%results%exist ()) then
            call object%results%write (u, suppress = pacify)
            call object%results%write_chain_weights (u)
        end if
    end subroutine process_mci_entry_write

```

Write the weights that are assigned to the chains of channels (call groves in the wood phase-space implementation. This depends on the implementation and is delegated to the mci component.

```

<Processes: process mci entry: TBP>+≡
    procedure :: write_chain_weights => process_mci_entry_write_chain_weights

```

```

<Processes: procedures>+≡
  subroutine process_mci_entry_write_chain_weights (mci_entry, unit)
    class(process_mci_entry_t), intent(in) :: mci_entry
    integer, intent(in), optional :: unit
    if (allocated (mci_entry%mci)) then
      call mci_entry%mci%write_chain_weights (unit)
    end if
  end subroutine process_mci_entry_write_chain_weights

```

Initialize. From the existing configuration, we obtain the number of channels and the number of parameters, separately for the structure-function chain and for the associated process component. We assume that the phase-space object has already been configured.

The allocation of the MCI integrator with the appropriate concrete type is the duty of the process core.

We assume that there is only one component associated with a MCI entry. This restriction should be relaxed.

```

<Processes: process mci entry: TBP>+≡
  procedure :: init => process_mci_entry_init

<Processes: procedures>+≡
  subroutine process_mci_entry_init (mci_entry, &
    process_type, i_mci, i_component, component,&
    beam_config, rng_factory)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    integer, intent(in) :: process_type
    integer, intent(in) :: i_mci
    integer, intent(in) :: i_component
    type(process_component_t), intent(in), target :: component
    type(process_beam_config_t), intent(in) :: beam_config
    class(rng_factory_t), intent(inout) :: rng_factory
    class(rng_t), allocatable :: rng
    associate (phs_config => component%phs_config)
      mci_entry%i_mci = i_mci
      call mci_entry%create_component_list (i_component, component)
      mci_entry%n_par_sf = beam_config%n_sfpar
      mci_entry%n_par_phs = phs_config%get_n_par ()
      mci_entry%n_par = mci_entry%n_par_sf + mci_entry%n_par_phs
      mci_entry%process_type = process_type
      if (allocated (component%mci_template)) then
        allocate (mci_entry%mci, source=component%mci_template)
        call mci_entry%mci%record_index (mci_entry%i_mci)
        call mci_entry%mci%set_dimensions &
          (mci_entry%n_par, phs_config%get_n_channel ())
        call mci_entry%mci%declare_flat_dimensions &
          (phs_config%get_flat_dimensions ())
        if (phs_config%provides_equivalences) then
          call mci_entry%mci%declare_equivalences &
            (phs_config%channel, mci_entry%n_par_sf)
        end if
        if (phs_config%provides_chains) then
          call mci_entry%mci%declare_chains (phs_config%chain)
        end if
      end if
    end associate
  end subroutine process_mci_entry_init

```

```

        call rng_factory%make (rng)
        call mci_entry%mci%import_rng (rng)
    end if
end associate
call mci_entry%results%init (process_type)
end subroutine process_mci_entry_init

```

<Processes: process mci entry: TBP>+≡

```

    procedure :: create_component_list => &
        process_mci_entry_create_component_list

```

<Processes: procedures>+≡

```

    subroutine process_mci_entry_create_component_list (mci_entry, &
        i_component, component)
    class (process_mci_entry_t), intent(inout) :: mci_entry
    integer, intent(in) :: i_component
    type(process_component_t), intent(in), target :: component
    integer, dimension(4) :: i_list
    if (mci_entry%combined_integration) then
        allocate (mci_entry%i_component (3))
        i_list = component%config%get_association_list ()
        mci_entry%i_component = i_list(1:3)
    else
        allocate (mci_entry%i_component (1))
        mci_entry%i_component(1) = i_component
    end if
end subroutine process_mci_entry_create_component_list

```

<Processes: process mci entry: TBP>+≡

```

    procedure :: set_combined_integration => &
        process_mci_entry_set_combined_integration

```

<Processes: procedures>+≡

```

    subroutine process_mci_entry_set_combined_integration (mci_entry, value)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    logical, intent(in), optional :: value
    if (present (value)) &
        mci_entry%combined_integration = value
    end subroutine process_mci_entry_set_combined_integration

```

Set some additional parameters.

<Processes: process mci entry: TBP>+≡

```

    procedure :: set_parameters => process_mci_entry_set_parameters

```

<Processes: procedures>+≡

```

    subroutine process_mci_entry_set_parameters (mci_entry, var_list)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(var_list_t), intent(in) :: var_list
    real(default) :: error_threshold
    error_threshold = &
        var_list%get_rval (var_str ("error_threshold"))
    mci_entry%activate_timer = &
        var_list%get_lval (var_str ("?integration_timer"))
    call mci_entry%results%set_error_threshold (error_threshold)

```

```
end subroutine process_mci_entry_set_parameters
```

Compute a MD5 sum that summarizes all information that could influence integration results, for the associated process components. We take the process-configuration MD5 sum which represents parameters, cuts, etc., the MD5 sums for the process component definitions and their phase space objects (which should be configured), and the beam configuration MD5 sum. (The QCD setup is included in the process configuration data MD5 sum.)

Done only once, when the MD5 sum is still empty.

```
(Processes: process mci entry: TBP)+≡
  procedure :: compute_md5sum => process_mci_entry_compute_md5sum
(PProcesses: procedures)+≡
  subroutine process_mci_entry_compute_md5sum (mci_entry, &
    config, component, beam_config)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(process_config_data_t), intent(in) :: config
    type(process_component_t), dimension(:), intent(in) :: component
    type(process_beam_config_t), intent(in) :: beam_config
    type(string_t) :: buffer
    integer :: i
    if (mci_entry%md5sum == "") then
      buffer = config%md5sum // beam_config%md5sum
      do i = 1, size (component)
        if (component(i)%active) then
          buffer = buffer // component(i)%config%get_md5sum () &
            // component(i)%md5sum_phs
        end if
      end do
      mci_entry%md5sum = md5sum (char (buffer))
    end if
    if (allocated (mci_entry%pci)) then
      call mci_entry%pci%set_md5sum (mci_entry%md5sum)
    end if
  end subroutine process_mci_entry_compute_md5sum
```

Test the MCI sampler by calling it a given number of time, discarding the results. The instance should be initialized.

The `mci_entry` is `intent(inout)` because the integrator contains the random-number state.

```
(Processes: process mci entry: TBP)+≡
  procedure :: sampler_test => process_mci_entry_sampler_test
(PProcesses: procedures)+≡
  subroutine process_mci_entry_sampler_test (mci_entry, instance, n_calls)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(process_instance_t), intent(inout), target :: instance
    integer, intent(in) :: n_calls
    call instance%choose_mci (mci_entry%i_mci)
    call instance%reset_counter ()
    call mci_entry%pci%sampler_test (instance, n_calls)
    mci_entry%counter = instance%get_counter ()
  end subroutine process_mci_entry_sampler_test
```


Integrate. The instance should be initialized.

The `integrate` method counts as an integration pass; the pass count is increased by one. We transfer the pass parameters (number of iterations and number of calls) to the actual integration routine.

The `mci_entry` is `intent(inout)` because the integrator contains the random-number state.

Note: The results are written to screen and to logfile. This behavior is hardcoded.

```

(Processes: process mci_entry: TBP)+≡
  procedure :: integrate => process_mci_entry_integrate
  procedure :: final_integration => process_mci_entry_final_integration

(Processes: procedures)+≡
  subroutine process_mci_entry_integrate (mci_entry, instance, n_it, n_calls, &
    adapt_grids, adapt_weights, final, pacify, &
    i_component)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: n_it
    integer, intent(in) :: n_calls
    logical, intent(in), optional :: adapt_grids
    logical, intent(in), optional :: adapt_weights
    logical, intent(in), optional :: final, pacify
    integer, intent(in), optional :: i_component
    integer :: u_log
    integer :: nlo_type
    if (present (i_component)) then
      if (associated (instance%component(i_component)%config)) then
        nlo_type = instance%component(i_component)%config%config%get_nlo_type ()
      end if
    else
      nlo_type = BORN
    end if
    u_log = logfile_unit ()
    call instance%choose_mci (mci_entry%i_mci)
    call instance%reset_counter ()
    mci_entry%pass = mci_entry%pass + 1
    mci_entry%n_it = n_it
    mci_entry%n_calls = n_calls
    if (mci_entry%pass == 1) &
      call mci_entry%mci%startup_message (n_calls = n_calls)
    call mci_entry%mci%set_timer (active = mci_entry%activate_timer)
    call mci_entry%results%display_init &
      (mci_entry%process_type, screen = .true., unit = u_log)
    call mci_entry%results%new_pass ()
    associate (mci_instance => instance%mci_work(mci_entry%i_mci)%mci)
      select case (nlo_type)
        case (NLO_VIRTUAL, NLO_REAL, NLO_PDF)
          select type (mci_instance)
            type is (mci_vamp_instance_t)
              mci_instance%negative_weights = .true.
            end select
          end select
      call mci_entry%mci%add_pass (adapt_grids, adapt_weights, final)
    end associate
  end subroutine

```

```

        call mci_entry%mci%start_timer ()
        call mci_entry%mci%integrate (mci_instance, instance, n_it, &
            n_calls, mci_entry%results, pacify = pacify)
        call mci_entry%mci%stop_timer ()
        if (signal_is_pending ()) return
    end associate
    mci_entry%counter = instance%get_counter ()
    call mci_entry%results%display_pass (pacify)
end subroutine process_mci_entry_integrate

subroutine process_mci_entry_final_integration (mci_entry)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    call mci_entry%results%display_final ()
    call mci_entry%time_message ()
end subroutine process_mci_entry_final_integration

```

If appropriate, issue an informative message about the expected time for an event sample.

```

(Processes: process mci entry: TBP) +=
    procedure :: get_time => process_mci_entry_get_time
    procedure :: time_message => process_mci_entry_time_message

(Processes: procedures) +=
    subroutine process_mci_entry_get_time (mci_entry, time, sample)
        class(process_mci_entry_t), intent(in) :: mci_entry
        type(time_t), intent(out) :: time
        integer, intent(in) :: sample
        real(default) :: time_last_pass, efficiency, calls
        time_last_pass = mci_entry%mci%get_time ()
        calls = mci_entry%results%get_n_calls ()
        efficiency = mci_entry%mci%get_efficiency ()
        if (time_last_pass > 0 .and. calls > 0 .and. efficiency > 0) then
            time = nint (time_last_pass / calls / efficiency * sample)
        end if
    end subroutine process_mci_entry_get_time

    subroutine process_mci_entry_time_message (mci_entry)
        class(process_mci_entry_t), intent(in) :: mci_entry
        type(time_t) :: time
        integer :: sample
        sample = 10000
        call mci_entry%get_time (time, sample)
        if (time%is_known ()) then
            call msg_message ("Time estimate for generating 10000 events: " &
                // char (time%to_string_dhms ()))
        end if
    end subroutine process_mci_entry_time_message

```

Prepare event generation. (For the test integrator, this does nothing. It is relevant for the VAMP integrator.)

```

(Processes: process mci entry: TBP) +=
    procedure :: prepare_simulation => process_mci_entry_prepare_simulation

```

```

<Processes: procedures>+=
  subroutine process_mci_entry_prepare_simulation (mci_entry)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    call mci_entry%mci%prepare_simulation ()
  end subroutine process_mci_entry_prepare_simulation

```

Generate an event. The instance should be initialized, otherwise event generation is directed by the mci integrator subobject. The integrator instance is contained in a mci_work subobject of the process instance, which simultaneously serves as the sampler object. (We avoid the anti-aliasing rules if we assume that the sampling itself does not involve the integrator instance contained in the process instance.)

Regarding weighted events, we only take events which are valid, which means that they have valid kinematics and have passed cuts. Therefore, we have a rejection loop. For unweighted events, the unweighting routine should already take care of this.

```

<Processes: process mci entry: TBP>+=
  procedure :: generate_weighted_event => &
    process_mci_entry_generate_weighted_event
  procedure :: generate_unweighted_event => &
    process_mci_entry_generate_unweighted_event
  procedure :: recover_event => process_mci_entry_recover_event

<Processes: procedures>+=
  subroutine process_mci_entry_generate_weighted_event (mci_entry, instance)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(process_instance_t), intent(inout) :: instance
    call instance%choose_mci (mci_entry%i_mci)
    associate (mci_instance => instance%mci_work(mci_entry%i_mci)%mci)
      REJECTION: do
        call mci_entry%mci%generate_weighted_event (mci_instance, instance)
        if (signal_is_pending ()) return
        if (instance%is_valid ()) exit REJECTION
      end do REJECTION
    end associate
  end subroutine process_mci_entry_generate_weighted_event

  subroutine process_mci_entry_generate_unweighted_event (mci_entry, instance)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(process_instance_t), intent(inout) :: instance
    call instance%choose_mci (mci_entry%i_mci)
    associate (mci_instance => instance%mci_work(mci_entry%i_mci)%mci)
      call mci_entry%mci%generate_unweighted_event (mci_instance, instance)
    end associate
  end subroutine process_mci_entry_generate_unweighted_event

  subroutine process_mci_entry_recover_event (mci_entry, instance, i_term)
    class(process_mci_entry_t), intent(inout) :: mci_entry
    type(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: i_term
    integer :: channel
    mci_entry%i_mci = instance%i_mci
    channel = instance%get_channel ()

```

```

        associate (mci_instance => instance%mci_work(mci_entry%i_mci)%mci)
            call mci_instance%fetch (instance, channel)
        end associate
    end subroutine process_mci_entry_recover_event

```

Extract results.

```

<Processes: process mci entry: TBP>+≡
    procedure :: has_integral => process_mci_entry_has_integral
    procedure :: get_integral => process_mci_entry_get_integral
    procedure :: get_error => process_mci_entry_get_error
    procedure :: get_accuracy => process_mci_entry_get_accuracy
    procedure :: get_chi2 => process_mci_entry_get_chi2
    procedure :: get_efficiency => process_mci_entry_get_efficiency

<Processes: procedures>+≡
    function process_mci_entry_has_integral (mci_entry) result (flag)
        class(process_mci_entry_t), intent(in) :: mci_entry
        logical :: flag
        flag = mci_entry%results%exist ()
    end function process_mci_entry_has_integral

    function process_mci_entry_get_integral (mci_entry) result (integral)
        class(process_mci_entry_t), intent(in) :: mci_entry
        real(default) :: integral
        integral = mci_entry%results%get_integral ()
    end function process_mci_entry_get_integral

    function process_mci_entry_get_error (mci_entry) result (error)
        class(process_mci_entry_t), intent(in) :: mci_entry
        real(default) :: error
        error = mci_entry%results%get_error ()
    end function process_mci_entry_get_error

    function process_mci_entry_get_accuracy (mci_entry) result (accuracy)
        class(process_mci_entry_t), intent(in) :: mci_entry
        real(default) :: accuracy
        accuracy = mci_entry%results%get_accuracy ()
    end function process_mci_entry_get_accuracy

    function process_mci_entry_get_chi2 (mci_entry) result (chi2)
        class(process_mci_entry_t), intent(in) :: mci_entry
        real(default) :: chi2
        chi2 = mci_entry%results%get_chi2 ()
    end function process_mci_entry_get_chi2

    function process_mci_entry_get_efficiency (mci_entry) result (efficiency)
        class(process_mci_entry_t), intent(in) :: mci_entry
        real(default) :: efficiency
        efficiency = mci_entry%results%get_efficiency ()
    end function process_mci_entry_get_efficiency

```

Return the MCI checksum. This may be the one used for configuration, but may also incorporate results, if they change the state of the integrator (adaptation).

```

<Processes: process mci entry: TBP>+≡

```

```

    procedure :: get_md5sum => process_mci_entry_get_md5sum
  (Processes: procedures)+≡
    function process_mci_entry_get_md5sum (entry) result (md5sum)
      class(process_mci_entry_t), intent(in) :: entry
      character(32) :: md5sum
      md5sum = entry%mci%get_md5sum ()
    end function process_mci_entry_get_md5sum

```

27.3.6 Process Components

A process component is an individual contribution to a process (scattering or decay) which needs not be physical. The sum over all components should be physical.

The `index` identifies this component within its parent process.

The actual process component is stored in the `core` subobject. We use a polymorphic subobject instead of an extension of `process_component_t`, because the individual entries in the array of process components can have different types. In short, `process_component_t` is a wrapper for the actual process variants.

If the `active` flag is false, we should skip this component. This happens if the associated process has vanishing matrix element.

The index array `i_term` points to the individual terms generated by this component. The indices refer to the parent process.

The index `i_mci` is the index of the MC integrator and parameter set which are associated to this process component.

```

  (Processes: process part types)+≡
    type :: process_component_t
      private
      type(process_component_def_t), pointer :: config => null ()
      integer :: index = 0
      class(prc_core_t), allocatable :: core
      class(prc_core_t), pointer :: core_sub_born
      logical :: active = .false.
      class(mci_t), allocatable :: mci_template
      integer, dimension(:), allocatable :: i_term
      integer :: i_mci = 0
      class(phs_config_t), allocatable :: phs_config
      character(32) :: md5sum_phs = ""
      type(fks_template_t) :: fks_template
      integer :: component_type = COMP_DEFAULT
    contains
      (Processes: process component: TBP)
    end type process_component_t

```

Finalizer. The MCI template may (potentially) need a finalizer. The process configuration finalizer may include closing an open scratch file.

```

  (Processes: process component: TBP)≡
    procedure :: final => process_component_final

```

```

<Processes: procedures>+=
  subroutine process_component_final (object)
    class(process_component_t), intent(inout) :: object
    if (allocated (object%mci_template)) then
      call object%mci_template%final ()
    end if
    if (allocated (object%phs_config)) then
      call object%phs_config%final ()
    end if
  end subroutine process_component_final

```

The meaning of **verbose** depends on the process variant.

```

<Processes: process component: TBP>+=

```

```

  procedure :: write => process_component_write

```

```

<Processes: procedures>+=

```

```

  subroutine process_component_write (object, unit)
    class(process_component_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    if (allocated (object%core)) then
      write (u, "(1x,A,I0)") "Component #", object%index
      if (associated (object%config)) then
        call object%config%write (u)
        if (object%md5sum_phs /= "") then
          write (u, "(3x,A,A,A)") "MD5 sum (phs)          = ', &
            object%md5sum_phs, "'
        end if
      end if
      write (u, "(1x,A)") "Process core:"
      call object%core%write (u)
    else
      write (u, "(1x,A)") "Process component: [not allocated]"
    end if
    if (.not. object%active) then
      write (u, "(1x,A)") "[Inactive]"
      return
    end if
    write (u, "(1x,A)") "Referenced data:"
    if (allocated (object%i_term)) then
      write (u, "(3x,A,999(1x,I0))") "Terms          =", &
        object%i_term
    else
      write (u, "(3x,A)") "Terms          = [undefined]"
    end if
    if (object%i_mci /= 0) then
      write (u, "(3x,A,I0)") "MC dataset          = ", object%i_mci
    else
      write (u, "(3x,A)") "MC dataset          = [undefined]"
    end if
    if (allocated (object%phs_config)) then
      call object%phs_config%write (u)
    end if

```

end subroutine process_component_write

Initialize the component.

$\langle \text{Processes: process component: TBP} \rangle + \equiv$

procedure :: init => process_component_init

$\langle \text{Processes: procedures} \rangle + \equiv$

```

subroutine process_component_init (component, &
    i_component, meta, config, &
    core_template, mci_template, phs_config_template, &
    blha_template, fks_template)
class(process_component_t), intent(out) :: component
integer, intent(in) :: i_component
type(process_metadata_t), intent(in) :: meta
type(process_config_data_t), intent(in) :: config
class(prc_core_t), intent(in), allocatable :: core_template
class(mci_t), intent(in), allocatable :: mci_template
class(phs_config_t), intent(in), allocatable :: phs_config_template
type(blha_template_t), intent(inout), optional :: blha_template
type(fks_template_t), intent(in), optional :: fks_template

component%index = i_component
component%config => meta%lib%get_component_def_ptr (meta%id, i_component)
allocate (component%core, source=core_template)
call component%core%init (component%config%get_core_def_ptr (), &
    meta%lib, meta%id, i_component)
if (present (fks_template)) then
    component%fks_template = fks_template
end if
select type (core => component%core)
class is (prc_blha_t)
    if (present (blha_template)) then
        call core%init_blha (blha_template)
    else
        call msg_bug ("process_component_init: BLHA core cannot be initialized - &
            & missing template")
    end if
    call core%init_driver (config%os_data)
!    call core%set_initialized ()
end select
component%active = component%core%has_matrix_element ()
if (component%active) then
    if (allocated (mci_template)) &
        allocate (component%mci_template, source=mci_template)
    allocate (component%phs_config, source=phs_config_template)
    call component%phs_config%init (component%core%data, config%model)
end if
end subroutine process_component_init

```

Finalize the phase-space configuration.

$\langle \text{Processes: process component: TBP} \rangle + \equiv$

procedure :: configure_phs => process_component_configure_phs

```

<Processes: procedures>+≡
subroutine process_component_configure_phs &
    (component, sqrts, beam_config, rebuild, &
     ignore_mismatch, phs_config, verbose)
class(process_component_t), intent(inout) :: component
real(default), intent(in) :: sqrts
type(process_beam_config_t), intent(in) :: beam_config
logical, intent(in), optional :: rebuild
logical, intent(in), optional :: ignore_mismatch
type(phs_wood_config_t), intent(in), optional, target :: phs_config
logical, intent(in), optional :: verbose
logical :: no_strfun, verb
integer :: nlo_type
no_strfun = beam_config%n_strfun == 0
verb = .true.; if (present(verbose)) verb = verbose
nlo_type = component%config%get_nlo_type ()
if (present(phs_config)) then
    select type (config => component%phs_config)
    type is (phs_fks_config_t)
        call config%set_born_config (phs_config)
        call config%set_mode (nlo_type)
    end select
end if
call component%phs_config%configure (sqrts, &
    azimuthal_dependence = beam_config%azimuthal_dependence, &
    sqrts_fixed = no_strfun, &
    cm_frame = beam_config%lab_is_cm_frame .and. no_strfun, &
    rebuild = rebuild, ignore_mismatch = ignore_mismatch, &
    nlo_type = nlo_type)
if (verb) call component%phs_config%startup_message ()
end subroutine process_component_configure_phs

```

```

<Processes: process component: TBP>+≡
procedure :: increase_phs_par => process_component_increase_phs_par

<Processes: procedures>+≡
subroutine process_component_increase_phs_par (component)
class(process_component_t), intent(inout) :: component
select type (phs_config => component%phs_config)
type is (phs_wood_config_t)
    call phs_config%increase_n_par ()
end select
end subroutine process_component_increase_phs_par

```

The process component possesses two MD5 sums: the checksum of the component definition, which should be available when the component is initialized, and the phase-space MD5 sum, which is available after configuration.

```

<Processes: process component: TBP>+≡
procedure :: compute_md5sum => process_component_compute_md5sum

<Processes: procedures>+≡
subroutine process_component_compute_md5sum (component)
class(process_component_t), intent(inout) :: component
component%md5sum_phs = component%phs_config%get_md5sum ()

```



```
end subroutine process_component_compute_md5sum
```

Match phase-space channels with structure-function channels, where applicable.
This calls a method of the `phs_config` phase-space implementation.

```
<Processes: process component: TBP>+=
  procedure :: collect_channels => process_component_collect_channels

<Processes: procedures>+=
  subroutine process_component_collect_channels (component, coll)
    class(process_component_t), intent(inout) :: component
    type(phs_channel_collection_t), intent(inout) :: coll
    call component%phs_config%collect_channels (coll)
  end subroutine process_component_collect_channels
```

Return the number of phase-space parameters.

```
<Processes: process component: TBP>+=
  procedure :: get_n_phs_par => process_component_get_n_phs_par

<Processes: procedures>+=
  function process_component_get_n_phs_par (component) result (n_par)
    class(process_component_t), intent(in) :: component
    integer :: n_par
    n_par = component%phs_config%get_n_par ()
  end function process_component_get_n_phs_par
```

Return the incoming flavor combination as an array of PDG arrays, one for a decay or two for a scattering process.

```
<Processes: process component: TBP>+=
  procedure :: get_pdg_in => process_component_get_pdg_in

<Processes: procedures>+=
  function process_component_get_pdg_in (component) result (pdg_in)
    class(process_component_t), intent(in) :: component
    type(pdg_array_t), dimension(:), allocatable :: pdg_in
    type(pdg_array_t) :: pdg_tmp
    integer :: i
    associate (data => component%core%data)
      allocate (pdg_in (data%n_in))
      do i = 1, data%n_in
        pdg_tmp = data%flv_state(i,:)
        pdg_in(i) = sort_abs (pdg_tmp, unique = .true.)
      end do
    end associate
  end function process_component_get_pdg_in
```

```
<Processes: process component: TBP>+=
  procedure :: extract_phs_config => process_component_extract_phs_config
  procedure :: restore_phs_config => process_component_restore_phs_config

<Processes: procedures>+=
  subroutine process_component_extract_phs_config (component, phs_config)
    class(process_component_t), intent(inout) :: component
    class(phs_config_t), intent(inout), allocatable :: phs_config
```

```

    call move_alloc (from = component%phs_config, to = phs_config)
end subroutine process_component_extract_phs_config

subroutine process_component_restore_phs_config (component, phs_config)
    class(process_component_t), intent(inout) :: component
    class(phs_config_t), intent(inout), allocatable :: phs_config
    call move_alloc (from = phs_config, to = component%phs_config)
end subroutine process_component_restore_phs_config

```

27.3.7 Process terms

For straightforward tree-level calculations, each process component corresponds to a unique elementary interaction. However, in the case of NLO calculations with subtraction terms, a process component may split into several separate contributions to the scattering, which are qualified by interactions with distinct kinematics and particle content. We represent their configuration as `process_term_t` objects, the actual instances will be introduced below as `term_instance_t`. In any case, the process term contains an elementary interaction with a definite quantum-number and momentum content.

The index `i_term_global` identifies the term relative to the process.

The index `i_component` identifies the process component which generates this term, relative to the parent process.

The index `i_term` identifies the term relative to the process component (not the process).

The `data` subobject holds all process constants.

The number of allowed flavor/helicity/color combinations is stored as `n_allowed`.

This is the total number of independent entries in the density matrix. For each combination, the index of the flavor, helicity, and color state is stored in the arrays `flv`, `hel`, and `col`, respectively.

The flag `rearrange` is true if we need to rearrange the particles of the hard interaction, to obtain the effective parton state.

The interaction `int` holds the quantum state for the (resolved) hard interaction, the parent-child relations of the particles, and their momenta. The momenta are not filled yet; this is postponed to copies of `int` which go into the process instances.

If recombination is in effect, we should allocate `int_eff` to describe the rearranged partonic state.

(Processes: process part types)+≡

```

type :: process_term_t
    integer :: i_term_global = 0
    integer :: i_component = 0
    integer :: i_term = 0
    integer :: n_allowed = 0
    integer :: n_allowed_sub_born = 0
    type(process_constants_t) :: data
    real(default) :: alpha_s = 0
    integer, dimension(:), allocatable :: flv, hel, col
    logical :: rearrange = .false.
    type(interaction_t) :: int
    type(interaction_t), pointer :: int_eff => null ()

```

```

contains
  <Processes: process term: TBP>
end type process_term_t

```

For the output, we skip the process constants and the tables of allowed quantum numbers. Those can also be read off from the interaction object.

```

<Processes: process term: TBP>≡
  procedure :: write => process_term_write

<Processes: procedures>+≡
  subroutine process_term_write (term, unit)
    class(process_term_t), intent(in) :: term
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A,I0)") "Term #", term%i_term_global
    write (u, "(3x,A,I0)") "Process component index      = ", &
      term%i_component
    write (u, "(3x,A,I0)") "Term index w.r.t. component = ", &
      term%i_term
    write (u, "(3x,A,L1)") "Rearrange partons          = ", &
      term%rearrange
    call write_separator (u)
    write (u, "(1x,A)") "Hard interaction:"
    call write_separator (u)
    call term%int%basic_write (u)
    if (term%rearrange) then
      call write_separator (u)
      write (u, "(1x,A)") "Rearranged hard interaction:"
      call write_separator (u)
      call term%int_eff%basic_write (u)
    end if
  end subroutine process_term_write

```

Write an account of all quantum number states and their current status.

```

<Processes: process term: TBP>+≡
  procedure :: write_state_summary => process_term_write_state_summary

<Processes: procedures>+≡
  subroutine process_term_write_state_summary (term, core, unit)
    class(process_term_t), intent(in) :: term
    class(prc_core_t), intent(in) :: core
    integer, intent(in), optional :: unit
    integer :: u, i, f, h, c
    type(state_iterator_t) :: it
    character :: sgn
    u = given_output_unit (unit)
    write (u, "(1x,A,I0)") "Term #", term%i_term_global
    call it%init (term%int%get_state_matrix_ptr ())
    do while (it%is_valid ())
      i = it%get_me_index ()
      f = term%flv(i)
      h = term%hel(i)
      c = term%col(i)

```

```

        if (core%is_allowed (term%i_term, f, h, c)) then
            sgn = "+"
        else
            sgn = " "
        end if
        write (u, "(1x,A1,1x,I0,2x)", advance="no") sgn, i
        call quantum_numbers_write (it%get_quantum_numbers (), u)
        write (u, *)
        call it%advance ()
    end do
end subroutine process_term_write_state_summary

```

Finalizer: the `int` and potentially `int_eff` components have a finalizer that we must call.

```

<Processes: process term: TBP> +=
    procedure :: final => process_term_final

<Processes: procedures> +=
    subroutine process_term_final (term)
        class(process_term_t), intent(inout) :: term
        call term%int%final ()
        if (term%rearrange) then
            call term%int_eff%final ()
            deallocate (term%int_eff)
        end if
    end subroutine process_term_final

```

Initialize the term. We copy the process constants from the `core` object and set up the `int` hard interaction accordingly.

The `alpha_s` value is useful for writing external event records. This is the constant value which may be overridden by a event-specific running value. If the model does not contain the strong coupling, the value is zero.

The `rearrange` part is commented out; this or something equivalent could become relevant for NLO algorithms.

```

<Processes: process term: TBP> +=
    procedure :: init => process_term_init

<Processes: procedures> +=
    subroutine process_term_init &
        (term, i_term_global, i_component, i_term, core, model)
        class(process_term_t), intent(inout), target :: term
        integer, intent(in) :: i_term_global
        integer, intent(in) :: i_component
        integer, intent(in) :: i_term
        class(prc_core_t), intent(in) :: core
        class(model_data_t), intent(in), target :: model
        class(modelpar_data_t), pointer :: alpha_s_ptr
!     type(var_list_t), pointer :: var_list
        term%i_term_global = i_term_global
        term%i_component = i_component
        term%i_term = i_term
        call core%get_constants (term%data, i_term)
!     var_list => model%get_var_list_ptr ()
    end subroutine process_term_init

```

```

!   if (var_list%contains (var_str ("alphas"))) then
!       term%alpha_s = var_list%get_rval (var_list, var_str ("alphas"))
!   else
!       term%alpha_s = -1
!   end if
alpha_s_ptr => model%get_par_data_ptr (var_str ("alphas"))
if (associated (alpha_s_ptr)) then
    term%alpha_s = alpha_s_ptr%get_real ()
else
    term%alpha_s = -1
end if

    call term%setup_interaction (core, model)
!   if (term%rearrange) then
!       call term%setup_effective_interaction (core, term%int, term%int_eff)
!   end if
end subroutine process_term_init

```

We fetch the process constants which determine the quantum numbers and use those to create the interaction. The interaction contains incoming and outgoing particles, no virtuals. The incoming particles are parents of the outgoing ones.

Keeping previous WHIZARD conventions, we invert the color assignment (but not flavor or helicity) for the incoming particles. When the color-flow square matrix is evaluated, this inversion is done again, so in the color-flow sequence we get the color assignments of the matrix element.

(Processes: process term: TBP)+≡

```

    procedure :: setup_interaction => process_term_setup_interaction

```

(Processes: procedures)+≡

```

subroutine process_term_setup_interaction (term, core, model)
    class(process_term_t), intent(inout) :: term
    class(prc_core_t), intent(in) :: core
    class(model_data_t), intent(in), target :: model
    integer :: n_tot
    type(flavor_t), dimension(:), allocatable :: flv
    type(color_t), dimension(:), allocatable :: col
    type(helicity_t), dimension(:), allocatable :: hel
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    integer :: i, n, f, h, c
    associate (data => term%data)
        n_tot = data%n_in + data%n_out
        n = 0
        do f = 1, data%n_flv
            do h = 1, data%n_hel
                do c = 1, data%n_col
                    if (core%is_allowed (term%i_term, f, h, c)) n = n + 1
                end do
            end do
        end do
        allocate (term%flv (n), term%col (n), term%hel (n))
        term%n_allowed = n
        allocate (flv (n_tot), col (n_tot), hel (n_tot))
        allocate (qn (n_tot))
    end associate
end subroutine

```

```

call term%int%basic_init &
  (data%n_in, 0, data%n_out, set_relations=.true.)
i = 0
do f = 1, data%n_flv
  do h = 1, data%n_hel
    do c = 1, data%n_col
      if (core%is_allowed (term%i_term, f, h, c)) then
        i = i + 1
        term%flv(i) = f
        term%hel(i) = h
        term%col(i) = c
        call flv%init (data%flv_state(:,f), model)
        call color_init_from_array (col, &
          data%col_state(:,c), &
          data%ghost_flag(:,c))
        call col(:,data%n_in)%invert ()
        call hel%init (data%hel_state(:,h))
        call qn%init (flv, col, hel)
        call term%int%add_state (qn)
      end if
    end do
  end do
end do
call term%int%freeze ()
end associate
end subroutine process_term_setup_interaction

```

```

<Processes: process term: TBP>+=
  procedure :: fetch_constants => process_term_fetch_process_constants

<Processes: procedures>+=
  subroutine process_term_fetch_process_constants &
    (term, prc_constants)
    class(process_term_t), intent(inout) :: term
    type(process_constants_t), intent(out) :: prc_constants
    prc_constants = term%data
  end subroutine process_term_fetch_process_constants

```

27.3.8 Default Iterations

If the user does not specify the passes and iterations for integration, we should be able to give reasonable defaults. These depend on the process, therefore we implement the following procedures as methods of the process object. The algorithm is not very sophisticated yet, it may be improved by looking at the process in more detail.

We investigate only the first process component, assuming that it characterizes the complexity of the process reasonable well.

The number of passes is limited to two: one for adaption, one for integration.

```

<Processes: process: TBP>+=
  procedure :: get_n_pass_default => process_get_n_pass_default
  procedure :: adapt_grids_default => process_adapt_grids_default
  procedure :: adapt_weights_default => process_adapt_weights_default

```

(Processes: procedures)+≡

```

function process_get_n_pass_default (process) result (n_pass)
  class(process_t), intent(in) :: process
  integer :: n_pass
  integer :: n_eff
  type(process_component_def_t), pointer :: config
  config => process%component(1)%config
  n_eff = config%get_n_tot () - 2
  select case (n_eff)
  case (1)
    n_pass = 1
  case default
    n_pass = 2
  end select
end function process_get_n_pass_default

function process_adapt_grids_default (process, pass) result (flag)
  class(process_t), intent(in) :: process
  integer, intent(in) :: pass
  logical :: flag
  integer :: n_eff
  type(process_component_def_t), pointer :: config
  config => process%component(1)%config
  n_eff = config%get_n_tot () - 2
  select case (n_eff)
  case (1)
    flag = .false.
  case default
    select case (pass)
    case (1); flag = .true.
    case (2); flag = .false.
    case default
      call msg_bug ("adapt grids default: impossible pass index")
    end select
  end select
end function process_adapt_grids_default

function process_adapt_weights_default (process, pass) result (flag)
  class(process_t), intent(in) :: process
  integer, intent(in) :: pass
  logical :: flag
  integer :: n_eff
  type(process_component_def_t), pointer :: config
  config => process%component(1)%config
  n_eff = config%get_n_tot () - 2
  select case (n_eff)
  case (1)
    flag = .false.
  case default
    select case (pass)
    case (1); flag = .true.
    case (2); flag = .false.
    case default
      call msg_bug ("adapt weights default: impossible pass index")
    end select
  end select
end function process_adapt_weights_default

```

```

        end select
    end select
end function process_adapt_weights_default

```

The number of iterations and calls per iteration depends on the number of outgoing particles.

```

<Processes: process: TBP>+≡
    procedure :: get_n_it_default => process_get_n_it_default
    procedure :: get_n_calls_default => process_get_n_calls_default

<Processes: procedures>+≡
    function process_get_n_it_default (process, pass) result (n_it)
        class(process_t), intent(in) :: process
        integer, intent(in) :: pass
        integer :: n_it
        integer :: n_eff
        type(process_component_def_t), pointer :: config
        config => process%component(1)%config
        n_eff = config%get_n_tot () - 2
        select case (pass)
        case (1)
            select case (n_eff)
            case (1);    n_it = 1
            case (2);    n_it = 3
            case (3);    n_it = 5
            case (4:5);  n_it = 10
            case (6);    n_it = 15
            case (7:);   n_it = 20
            end select
        case (2)
            select case (n_eff)
            case (:3);   n_it = 3
            case (4:);   n_it = 5
            end select
        end select
    end function process_get_n_it_default

    function process_get_n_calls_default (process, pass) result (n_calls)
        class(process_t), intent(in) :: process
        integer, intent(in) :: pass
        integer :: n_calls
        integer :: n_eff
        type(process_component_def_t), pointer :: config
        config => process%component(1)%config
        n_eff = config%get_n_tot () - 2
        select case (pass)
        case (1)
            select case (n_eff)
            case (1);    n_calls = 100
            case (2);    n_calls = 1000
            case (3);    n_calls = 5000
            case (4);    n_calls = 10000
            case (5);    n_calls = 20000
            case (6:);   n_calls = 50000
            end select
        end select
    end function process_get_n_calls_default

```



```

        end select
    case (2)
        select case (n_eff)
            case (:3); n_calls = 10000
            case (4);  n_calls = 20000
            case (5);  n_calls = 50000
            case (6);  n_calls = 100000
            case (7:); n_calls = 200000
        end select
    end select
end function process_get_n_calls_default

```

27.3.9 Constant process data

The following methods return basic process data that stay constant after initialization.

The process and IDs.

```

<Processes: process: TBP>+≡
    procedure :: get_id => process_get_id
    procedure :: get_num_id => process_get_num_id
    procedure :: get_run_id => process_get_run_id
    procedure :: get_library_name => process_get_library_name

<Processes: procedures>+≡
    function process_get_id (process) result (id)
        class(process_t), intent(in) :: process
        type(string_t) :: id
        id = process%meta%id
    end function process_get_id

    function process_get_num_id (process) result (id)
        class(process_t), intent(in) :: process
        integer :: id
        id = process%meta%num_id
    end function process_get_num_id

    function process_get_run_id (process) result (id)
        class(process_t), intent(in) :: process
        type(string_t) :: id
        id = process%meta%run_id
    end function process_get_run_id

    function process_get_library_name (process) result (id)
        class(process_t), intent(in) :: process
        type(string_t) :: id
        id = process%meta%lib%get_name ()
    end function process_get_library_name

```

The number of incoming particles.

```

<Processes: process: TBP>+≡
    procedure :: get_n_in => process_get_n_in

```

```

<Processes: procedures>+≡
function process_get_n_in (process) result (n)
  class(process_t), intent(in) :: process
  integer :: n
  n = process%config%n_in
end function process_get_n_in

```

The number of MCI data sets.

```

<Processes: process: TBP>+≡
  procedure :: get_n_mci => process_get_n_mci
<Processes: procedures>+≡
function process_get_n_mci (process) result (n)
  class(process_t), intent(in) :: process
  integer :: n
  n = process%config%n_mci
end function process_get_n_mci

```

The number of process components, total.

```

<Processes: process: TBP>+≡
  procedure :: get_n_components => process_get_n_components
<Processes: procedures>+≡
function process_get_n_components (process) result (n)
  class(process_t), intent(in) :: process
  integer :: n
  n = process%meta%n_components
end function process_get_n_components

```

The number of process terms, total.

```

<Processes: process: TBP>+≡
  procedure :: get_n_terms => process_get_n_terms
<Processes: procedures>+≡
function process_get_n_terms (process) result (n)
  class(process_t), intent(in) :: process
  integer :: n
  n = process%config%n_terms
end function process_get_n_terms

```

Return the indices of the components that belong to a specific MCI entry.

```

<Processes: process: TBP>+≡
  procedure :: get_i_component => process_get_i_component
<Processes: procedures>+≡
  subroutine process_get_i_component (process, i_mci, i_component)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i_mci
    integer, dimension(:), intent(out), allocatable :: i_component
    associate (mci_entry => process%mci_entry(i_mci))
      allocate (i_component (size (mci_entry%i_component)))
      i_component = mci_entry%i_component
    end associate
  end subroutine process_get_i_component

```

Return the ID of a specific component.

```

<Processes: process: TBP>+≡
    procedure :: get_component_id => process_get_component_id

<Processes: procedures>+≡
    function process_get_component_id (process, i_component) result (id)
        class(process_t), intent(in) :: process
        integer, intent(in) :: i_component
        type(string_t) :: id
        id = process%meta%component_id(i_component)
    end function process_get_component_id

```

Return a pointer to the definition of a specific component.

```

<Processes: process: TBP>+≡
    procedure :: get_component_def_ptr => process_get_component_def_ptr

<Processes: procedures>+≡
    function process_get_component_def_ptr (process, i_component) result (ptr)
        class(process_t), intent(in) :: process
        integer, intent(in) :: i_component
        type(process_component_def_t), pointer :: ptr
        ptr => process%meta%lib%get_component_def_ptr (process%meta%id, i_component)
    end function process_get_component_def_ptr

```

These procedures extract and restore (by transferring the allocation) the process core. This is useful for changing process parameters from outside this module.

```

<Processes: process: TBP>+≡
    procedure :: extract_component_core => process_extract_component_core
    procedure :: restore_component_core => process_restore_component_core

<Processes: procedures>+≡
    subroutine process_extract_component_core (process, i_component, core)
        class(process_t), intent(inout) :: process
        integer, intent(in) :: i_component
        class(prc_core_t), intent(inout), allocatable :: core
        call move_alloc (from = process%component(i_component)%core, to = core)
    end subroutine process_extract_component_core

    subroutine process_restore_component_core (process, i_component, core)
        class(process_t), intent(inout) :: process
        integer, intent(in) :: i_component
        class(prc_core_t), intent(inout), allocatable :: core
        call move_alloc (from = core, to = process%component(i_component)%core)
    end subroutine process_restore_component_core

```

The block of process constants.

```

<Processes: process: TBP>+≡
    procedure :: get_constants => process_get_constants

<Processes: procedures>+≡
    function process_get_constants (process, i) result (data)
        class(process_t), intent(in) :: process
        integer, intent(in) :: i
        type(process_constants_t) :: data

```

```

    data = process%component(i)%core%data
end function process_get_constants

```

Return the set of outgoing flavors that are associated with a particular term. We deduce this from the effective interaction.

```

<Processes: process: TBP>+≡
    procedure :: get_term_flv_out => process_get_term_flv_out

<Processes: procedures>+≡
    subroutine process_get_term_flv_out (process, i_term, flv)
        class(process_t), intent(in), target :: process
        integer, intent(in) :: i_term
        type(flavor_t), dimension(:, :), allocatable, intent(out) :: flv
        type(interaction_t), pointer :: int
        int => process%term(i_term)%int_eff
        if (.not. associated(int)) int => process%term(i_term)%int
        call interaction_get_flv_out (int, flv)
    end subroutine process_get_term_flv_out

```

Return true if there is any unstable particle in any of the process terms. We decide this based on the provided model instance, not the one that is stored in the process object.

```

<Processes: process: TBP>+≡
    procedure :: contains_unstable => process_contains_unstable

<Processes: procedures>+≡
    function process_contains_unstable (process, model) result (flag)
        class(process_t), intent(in) :: process
        class(model_data_t), intent(in), target :: model
        logical :: flag
        integer :: i_term
        type(flavor_t), dimension(:, :), allocatable :: flv
        flag = .false.
        do i_term = 1, process%get_n_terms ()
            call process%get_term_flv_out (i_term, flv)
            call flv%set_model (model)
            flag = .not. all (flv%is_stable ())
            deallocate (flv)
            if (flag) return
        end do
    end function process_contains_unstable

```

The nominal process energy.

```

<Processes: process: TBP>+≡
    procedure :: get_sqrts => process_get_sqrts

<Processes: procedures>+≡
    function process_get_sqrts (process) result (sqrts)
        class(process_t), intent(in) :: process
        real(default) :: sqrts
        sqrts = beam_data_get_sqrts (process%beam_config%data)
    end function process_get_sqrts

```

```

<Processes: process: TBP>+≡
    procedure :: has_matrix_element => process_has_matrix_element

<Processes: procedures>+≡
    function process_has_matrix_element (process, i) result (flag)
        class(process_t), intent(in) :: process
        integer, intent(in), optional :: i
        logical :: flag
        if (present (i)) then
            flag = process%component(i)%active
        else
            flag = any (process%component%active)
        end if
    end function process_has_matrix_element

```

Pointer to the beam data object.

```

<Processes: process: TBP>+≡
    procedure :: get_beam_data_ptr => process_get_beam_data_ptr

<Processes: procedures>+≡
    function process_get_beam_data_ptr (process) result (beam_data)
        class(process_t), intent(in), target :: process
        type(beam_data_t), pointer :: beam_data
        beam_data => process%beam_config%data
    end function process_get_beam_data_ptr

```

Return true if lab and c.m. frame coincide for this process.

```

<Processes: process: TBP>+≡
    procedure :: cm_frame => process_cm_frame

<Processes: procedures>+≡
    function process_cm_frame (process) result (flag)
        class(process_t), intent(in), target :: process
        logical :: flag
        type(beam_data_t), pointer :: beam_data
        beam_data => process%beam_config%data
        flag = beam_data_cm_frame (beam_data)
    end function process_cm_frame

```

Get the PDF set currently in use, if any.

```

<Processes: process: TBP>+≡
    procedure :: get_pdf_set => process_get_pdf_set

<Processes: procedures>+≡
    function process_get_pdf_set (process) result (pdf_set)
        class(process_t), intent(in) :: process
        integer :: pdf_set
        pdf_set = process%beam_config%get_pdf_set ()
    end function process_get_pdf_set

```

Pointer to the process variable list.

```

<Processes: process: TBP>+≡
    procedure :: get_var_list_ptr => process_get_var_list_ptr

```

```

<Processes: procedures>+≡
  function process_get_var_list_ptr (process) result (ptr)
    class(process_t), intent(in), target :: process
    type(var_list_t), pointer :: ptr
    ptr => process%meta%var_list
  end function process_get_var_list_ptr

```

Pointer to the common model.

```

<Processes: process: TBP>+≡
  procedure :: get_model_ptr => process_get_model_ptr

<Processes: procedures>+≡
  function process_get_model_ptr (process) result (ptr)
    class(process_t), intent(in) :: process
    class(model_data_t), pointer :: ptr
    ptr => process%config%model
  end function process_get_model_ptr

```

Use the embedded RNG factory to spawn a new random-number generator instance. (This modifies the state of the factory.)

```

<Processes: process: TBP>+≡
  procedure :: make_rng => process_make_rng

<Processes: procedures>+≡
  subroutine process_make_rng (process, rng)
    class(process_t), intent(inout) :: process
    class(rng_t), intent(out), allocatable :: rng
    if (allocated (process%config%rng_factory)) then
      call process%config%rng_factory%make (rng)
    else
      call msg_bug ("Process: make rng: factory not allocated")
    end if
  end subroutine process_make_rng

```

27.3.10 Compute an amplitude

Each process variant should allow for computing an amplitude value directly, without generating a process instance.

The process component is selected by the index *i*. The term within the process component is selected by *j*. The momentum combination is transferred as the array *p*. The function sets the specific quantum state via the indices of a flavor *f*, helicity *h*, and color *c* combination. Each index refers to the list of flavor, helicity, and color states, respectively, as stored in the process data.

Optionally, we may set factorization and renormalization scale. If unset, the partonic c.m. energy is inserted.

The function checks arguments for validity. For invalid arguments (quantum states), we return zero.

```

<Processes: process: TBP>+≡
  procedure :: compute_amplitude => process_compute_amplitude

```

```

<Processes: procedures>+≡
function process_compute_amplitude &
    (process, i, j, p, f, h, c, fac_scale, ren_scale, alpha_qcd_forced) &
    result (amp)
    class(process_t), intent(in) :: process
    integer, intent(in) :: i, j
    type(vector4_t), dimension(:), intent(in) :: p
    integer, intent(in) :: f, h, c
    real(default), intent(in), optional :: fac_scale, ren_scale
    real(default), intent(in), allocatable, optional :: alpha_qcd_forced
    real(default) :: fscale, rscale
    real(default), allocatable :: aqcd_forced
    complex(default) :: amp
    amp = 0
    if (0 < i .and. i <= process%meta%n_components) then
        if (process%component(i)%active) then
            associate (data => process%component(i)%core%data)
                if (size (p) == data%n_in + data%n_out &
                    .and. 0 < f .and. f <= data%n_flv &
                    .and. 0 < h .and. h <= data%n_hel &
                    .and. 0 < c .and. c <= data%n_col) then
                    if (present (fac_scale)) then
                        fscale = fac_scale
                    else
                        fscale = sum (p(data%n_in+1:)) ** 1
                    end if
                    if (present (ren_scale)) then
                        rscale = ren_scale
                    else
                        rscale = fscale
                    end if
                    if (present (alpha_qcd_forced)) then
                        if (allocated (alpha_qcd_forced)) &
                            allocate (aqcd_forced, source = alpha_qcd_forced)
                        end if
                        amp = process%component(i)%core%compute_amplitude &
                            (j, p, f, h, c, fscale, rscale, aqcd_forced)
                    end if
                end associate
            else
                amp = 0
            end if
        end if
    end function process_compute_amplitude

```

```

<Processes: process: TBP>+≡
procedure :: set_component_type => process_set_component_type

```

```

<Processes: procedures>+≡
subroutine process_set_component_type (process, i_component, i_type)
    class(process_t), intent(inout) :: process
    integer, intent(in) :: i_component, i_type
    process%component(i_component)%component_type = i_type
end subroutine process_set_component_type

```

This is for suppression of numerical noise in the integration results stored in the `process_mci_entry` type. As the error and efficiency enter the MD5 sum, we recompute it.

```

<Processes: process: TBP>+≡
    procedure :: pacify => process_pacify
<Processes: procedures>+≡
    subroutine process_pacify (process, efficiency_reset, error_reset)
        class(process_t), intent(inout) :: process
        logical, intent(in), optional :: efficiency_reset, error_reset
        logical :: eff_reset, err_reset
        integer :: i
        eff_reset = .false.
        err_reset = .false.
        if (present (efficiency_reset)) eff_reset = efficiency_reset
        if (present (error_reset)) err_reset = error_reset
        if (allocated (process%mci_entry)) then
            do i = 1, size (process%mci_entry)
                call process%mci_entry(i)%results%pacify (efficiency_reset)
                if (allocated (process%mci_entry(i)%mci)) then
                    if (process%mci_entry(i)%mci%error_known .and. err_reset) &
                        process%mci_entry(i)%mci%error = 0
                    if (process%mci_entry(i)%mci%efficiency_known .and. &
                        eff_reset) process%mci_entry(i)%mci%efficiency = 1
                    select type (mci => process%mci_entry(i)%mci)
                        type is (mci_vamp_t)
                            call mci%pacify (efficiency_reset, error_reset)
                            call mci%compute_md5sum ()
                        end select
                end if
            end do
        end if
    end subroutine process_pacify

```

27.3.11 Process instances

Kinematics instance

In this data type we combine all objects (instances) necessary for generating (or recovering) a kinematical configuration. The components work together as an implementation of multi-channel phase space.

`sf_chain` is an instance of the structure-function chain. It is used both for generating kinematics and, after the proper scale has been determined, evaluating the structure function entries.

`p_h_s` is an instance of the phase space for the elementary process.

The array `f` contains the products of the Jacobians that originate from parameter mappings in the structure-function chain or in the phase space. We allocate this explicitly if either `sf_chain` or `p_h_s` are explicitly allocated, otherwise we can take over a pointer.

All components are implemented as pointers to (anonymous) targets. For each component, there is a flag that tells whether this component is to be regarded as a proper component ('owned' by the object) or as a pointer.

```

<Processes: types>+≡
  type :: kinematics_t
    integer :: n_in = 0
    integer :: n_channel = 0
    integer :: selected_channel = 0
    type(sf_chain_instance_t), pointer :: sf_chain => null ()
    class(phs_t), pointer :: phs => null ()
    real(default), dimension(:), pointer :: f => null ()
    real(default) :: phs_factor
    logical :: sf_chain_allocated = .false.
    logical :: phs_allocated = .false.
    logical :: f_allocated = .false.
    integer :: nlo_type
    integer :: emitter
  contains
    <Processes: kinematics: TBP>
  end type kinematics_t

```

Output. Show only those components which are marked as owned.

```

<Processes: kinematics: TBP>≡
  procedure :: write => kinematics_write

<Processes: procedures>+≡
  subroutine kinematics_write (object, unit)
    class(kinematics_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, c
    u = given_output_unit (unit)
    if (object%f_allocated) then
      write (u, "(1x,A)") "Flux * PHS volume:"
      write (u, "(2x,ES19.12)") object%phs_factor
      write (u, "(1x,A)") "Jacobian factors per channel:"
      do c = 1, size (object%f)
        write (u, "(3x,I0,':',1x,ES13.7)", advance="no") c, object%f(c)
        if (c == object%selected_channel) then
          write (u, "(1x,A)") "[selected]"
        else
          write (u, *)
        end if
      end do
    end if
    if (object%sf_chain_allocated) then
      call write_separator (u)
      call object%sf_chain%write (u)
    end if
    if (object%phs_allocated) then
      call write_separator (u)
      call object%phs%write (u)
    end if
  end subroutine kinematics_write

```

Finalizer. Delete only those components which are marked as owned.

```

<Processes: kinematics: TBP>+≡
  procedure :: final => kinematics_final

<Processes: procedures>+≡
  subroutine kinematics_final (object)
    class(kinematics_t), intent(inout) :: object
    if (object%sf_chain_allocated) then
      call object%sf_chain%final ()
      deallocate (object%sf_chain)
      object%sf_chain_allocated = .false.
    end if
    if (object%phs_allocated) then
      call object%phs%final ()
      deallocate (object%phs)
      object%phs_allocated = .false.
    end if
    if (object%f_allocated) then
      deallocate (object%f)
      object%f_allocated = .false.
    end if
  end subroutine kinematics_final

```

Set the flags indicating whether the phase space shall be set up for the calculation of the real contribution. For this case, also set the emitter.

```

<Processes: kinematics: TBP>+≡
  procedure :: set_nlo_info => kinematics_set_nlo_info

<Processes: procedures>+≡
  subroutine kinematics_set_nlo_info (k, nlo_type, emitter)
    class(kinematics_t), intent(inout) :: k
    integer, intent(in) :: nlo_type
    integer, intent(in), optional :: emitter
    k%nlo_type = nlo_type
    if (present (emitter)) then
      k%emitter = emitter
    end if
  end subroutine kinematics_set_nlo_info

```

Allocate the structure-function chain instance, initialize it as a copy of the `sf_chain` template, and prepare it for evaluation.

The `sf_chain` remains a target because the (usually constant) beam momenta are taken from there.

```

<Processes: kinematics: TBP>+≡
  procedure :: init_sf_chain => kinematics_init_sf_chain

<Processes: procedures>+≡
  subroutine kinematics_init_sf_chain (k, core, sf_chain, config, core_state)
    class(kinematics_t), intent(inout) :: k
    class(prc_core_t), intent(in) :: core
    type(sf_chain_t), intent(in), target :: sf_chain
    type(process_beam_config_t), intent(in) :: config
    class(prc_core_state_t), intent(inout), allocatable :: core_state
    integer :: n_strfun, n_channel

```

```

integer :: c
k%n_in = beam_data_get_n_in (config%data)
n_strfun = config%n_strfun
n_channel = config%n_channel
allocate (k%sf_chain)
k%sf_chain_allocated = .true.
call core%init_sf_chain (k%sf_chain, sf_chain, n_channel, core_state)
if (n_strfun /= 0) then
  do c = 1, n_channel
    call k%sf_chain%set_channel (c, config%sf_channel(c))
  end do
end if
call k%sf_chain%link_interactions ()
call k%sf_chain%exchange_mask ()
call k%sf_chain%init_evaluators ()
end subroutine kinematics_init_sf_chain

```

Allocate and initialize the phase-space part and the array of Jacobian factors.

```

<Processes: kinematics: TBP>+≡
  procedure :: init_phs => kinematics_init_phs

<Processes: procedures>+≡
  subroutine kinematics_init_phs (k, config)
    class(kinematics_t), intent(inout) :: k
    class(phs_config_t), intent(in), target :: config
    k%n_channel = config%get_n_channel ()
    call config%allocate_instance (k%phs)
    call k%phs%init (config)
    k%phs_allocated = .true.
    allocate (k%f (k%n_channel))
    k%f = 0
    k%f_allocated = .true.
  end subroutine kinematics_init_phs

```

Initialize the kinematics in form of simple pointers. In essence, this is a shallow copy, but we have to set the flags correctly to indicate this fact.

```

<Processes: kinematics: TBP>+≡
  procedure :: init_ptr => kinematics_init_ptr

<Processes: procedures>+≡
  subroutine kinematics_init_ptr (k, k_in)
    class(kinematics_t), intent(out) :: k
    type(kinematics_t), intent(in) :: k_in
    k%n_in = k_in%n_in
    k%n_channel = k_in%n_channel
    k%sf_chain => k_in%sf_chain
    k%phs => k_in%phs
    k%f => k_in%f
  end subroutine kinematics_init_ptr

```

Generate kinematics, given a phase-space channel and a MC parameter set. The main result is the momentum array *p*, but we also fill the momentum entries in

the structure-function chain and the Jacobian-factor array *f*. Regarding phase space, We fill only the parameter arrays for the selected channel.

```

(Processes: kinematics: TBP)+≡
  procedure :: compute_selected_channel => kinematics_compute_selected_channel

(Processes: procedures)+≡
  subroutine kinematics_compute_selected_channel &
    (k, mci_work, phs_channel, p, success, nlo_controller)
    class(kinematics_t), intent(inout) :: k
    type(mci_work_t), intent(in) :: mci_work
    integer, intent(in) :: phs_channel
    type(vector4_t), dimension(:), intent(out) :: p
    logical, intent(out) :: success
    type(nlo_controller_t), intent(inout), optional :: nlo_controller
    integer :: sf_channel
    k%selected_channel = phs_channel
    sf_channel = k%phs%config%get_sf_channel (phs_channel)
    call k%sf_chain%compute_kinematics (sf_channel, mci_work%get_x_strfun ())
    call k%sf_chain%get_out_momenta (p(1:k%n_in))
    call k%phs%set_incoming_momenta (p(1:k%n_in))
    call k%phs%compute_flux ()
    call k%phs%select_channel (phs_channel)
    call k%phs%evaluate_selected_channel &
      (phs_channel, mci_work%get_x_process ())

    select type (phs => k%phs)
    type is (phs_fks_t)
      if (phs%q_defined) then
        call phs%get_born_momenta (p)
        k%phs_factor = phs%get_overall_factor ()
        success = .true.
      else
        k%phs_factor = 0
        success = .false.
      end if
    class default
    !   call phs%evaluate_selected_channel &
    !   (phs_channel, mci_work%get_x_process ())
      if (phs%q_defined) then
        call k%phs%get_outgoing_momenta (p(k%n_in+1:))
        k%phs_factor = k%phs%get_overall_factor ()
        success = .true.
      else
        k%phs_factor = 0
        success = .false.
      end if
    end select
  end subroutine kinematics_compute_selected_channel

```

Complete kinematics by filling the non-selected phase-space parameter arrays.

```

(Processes: kinematics: TBP)+≡
  procedure :: compute_other_channels => kinematics_compute_other_channels

(Processes: procedures)+≡

```

```

subroutine kinematics_compute_other_channels (k, mci_work, phs_channel)
  class(kinematics_t), intent(inout) :: k
  type(mci_work_t), intent(in) :: mci_work
  integer, intent(in) :: phs_channel
  integer :: c, c_sf
  call k%phs%evaluate_other_channels (phs_channel)
  do c = 1, k%n_channel
    c_sf = k%phs%config%get_sf_channel (c)
    k%f(c) = k%sf_chain%get_f (c_sf) * k%phs%get_f (c)
  end do
end subroutine kinematics_compute_other_channels

```

Just fetch the outgoing momenta of the `sf_chain` subobject, which become the incoming (seed) momenta of the hard interaction.

This is a stripped down-version of the above which we use when recovering kinematics. Momenta are known, but no MC parameters yet.

(We do not use the `get_out_momenta` method of the chain, since this relies on the structure-function interactions, which are not necessary filled here. We do rely on the momenta of the last evaluator in the chain, however.)

(Processes: kinematics: TBP)+≡

```

  procedure :: get_incoming_momenta => kinematics_get_incoming_momenta

```

(Processes: procedures)+≡

```

subroutine kinematics_get_incoming_momenta (k, p)
  class(kinematics_t), intent(in) :: k
  type(vector4_t), dimension(:), intent(out) :: p
  type(interaction_t), pointer :: int
  integer :: i
  int => k%sf_chain%get_out_int_ptr ()
  do i = 1, k%n_in
    p(i) = int%get_momentum (k%sf_chain%get_out_i (i))
  end do
end subroutine kinematics_get_incoming_momenta

```

This inverts the remainder of the above `compute` method. We know the momenta and recover the rest, as far as needed. If we select a channel, we can complete the inversion and reconstruct the MC parameter set.

(Processes: kinematics: TBP)+≡

```

  procedure :: recover_mcpair => kinematics_recover_mcpair

```

(Processes: procedures)+≡

```

subroutine kinematics_recover_mcpair (k, mci_work, phs_channel, p)
  class(kinematics_t), intent(inout) :: k
  type(mci_work_t), intent(inout) :: mci_work
  integer, intent(in) :: phs_channel
  type(vector4_t), dimension(:), intent(in) :: p
  integer :: c, c_sf
  real(default), dimension(:), allocatable :: x_sf, x_phs
  c = phs_channel
  c_sf = k%phs%config%get_sf_channel (c)
  k%selected_channel = c
  call k%sf_chain%recover_kinematics (c_sf)
  call k%phs%set_incoming_momenta (p(1:k%n_in))

```

```

call k%phs%compute_flux ()
call k%phs%set_outgoing_momenta (p(k%n_in+1:))
call k%phs%inverse ()
do c = 1, k%n_channel
  c_sf = k%phs%config%get_sf_channel (c)
  k%f(c) = k%sf_chain%get_f (c_sf) * k%phs%get_f (c)
end do
k%phs_factor = k%phs%get_overall_factor ()
c = phs_channel
c_sf = k%phs%config%get_sf_channel (c)
allocate (x_sf (k%sf_chain%config%get_n_bound ()))
allocate (x_phs (k%phs%config%get_n_par ()))
call k%phs%select_channel (c)
call k%sf_chain%get_mcpair (c_sf, x_sf)
call k%phs%get_mcpair (c, x_phs)
call mci_work%set_x_strfun (x_sf)
call mci_work%set_x_process (x_phs)
end subroutine kinematics_recover_mcpair

```

Retrieve the MC input parameter array for a specific channel. We assume that the kinematics is complete, so this is known for all channels.

```

<Processes: kinematics: TBP>+≡
  procedure :: get_mcpair => kinematics_get_mcpair

<Processes: procedures>+≡
  subroutine kinematics_get_mcpair (k, phs_channel, r)
    class(kinematics_t), intent(in) :: k
    integer, intent(in) :: phs_channel
    real(default), dimension(:), intent(out) :: r
    integer :: sf_channel, n_par_sf, n_par_phs
    sf_channel = k%phs%config%get_sf_channel (phs_channel)
    n_par_phs = k%phs%config%get_n_par ()
    n_par_sf = k%sf_chain%config%get_n_bound ()
    if (n_par_sf > 0) then
      call k%sf_chain%get_mcpair (sf_channel, r(1:n_par_sf))
    end if
    if (n_par_phs > 0) then
      call k%phs%get_mcpair (phs_channel, r(n_par_sf+1:))
    end if
  end subroutine kinematics_get_mcpair

```

Evaluate the structure function chain, assuming that kinematics is known.

The status must be precisely SF_DONE_KINEMATICS. We thus avoid evaluating the chain twice via different pointers to the same target.

```

<Processes: kinematics: TBP>+≡
  procedure :: evaluate_sf_chain => kinematics_evaluate_sf_chain

<Processes: procedures>+≡
  subroutine kinematics_evaluate_sf_chain (k, fac_scale)
    class(kinematics_t), intent(inout) :: k
    real(default), intent(in) :: fac_scale
    select case (k%sf_chain%get_status ())
    case (SF_DONE_KINEMATICS)
      call k%sf_chain%evaluate (fac_scale)
    end select
  end subroutine kinematics_evaluate_sf_chain

```

```

    end select
end subroutine kinematics_evaluate_sf_chain

```

Recover beam momenta, i.e., return the beam momenta stored in the current `sf_chain` to their source. This is a side effect.

```

⟨Processes: kinematics: TBP⟩+≡
    procedure :: return_beam_momenta => kinematics_return_beam_momenta

⟨Processes: procedures⟩+≡
    subroutine kinematics_return_beam_momenta (k)
        class(kinematics_t), intent(in) :: k
        call k%sf_chain%return_beam_momenta ()
    end subroutine kinematics_return_beam_momenta

```

Process component instance

The actual calculation of a sampling point is done from here.

The `config` pointer accesses the corresponding configuration in the `process` object.

The `active` flag indicates that we are currently computing this component, together with all other components that share the same MC parameter set. Inactive components are using a different MC parameter set and are not in use for this sampling point.

The `k_seed` subobject contains the kinematics (structure-function chain, phase space, etc.) that implements the ‘seed’ configuration of momenta. This version of the process kinematics is accessed by the MCI setup.

`p_seed` is the array of momenta that we compute from the MC input parameters, via the `k_seed` subobject. Depending on the process variant, these may or may not coincide with the momenta that enter the process terms associated to this component.

The `core_state` object can be used for storing intermediate results. Its precise type and contents depend on the process variant.

```

⟨Processes: types⟩+≡
    type :: component_instance_t
        type(process_component_t), pointer :: config => null ()
        logical :: active = .false.
        type(kinematics_t) :: k_seed
        type(vector4_t), dimension(:), allocatable :: p_seed
        logical :: sqme_known = .false.
        real(default) :: sqme = 0
        class(prc_core_state_t), allocatable :: core_state
        type(nlo_controller_t), pointer :: nlo_controller => null ()
        integer :: nlo_type = BORN
    contains
        ⟨Processes: component instance: TBP⟩
    end type component_instance_t

```

In the header, fetch the component index from the configuration record. `process_component_t` configuration block.

We write the `sf_chain` subobject only upon request, since its instances appear elsewhere.

```

<Processes: component instance: TBP>≡
  procedure :: write => component_instance_write

<Processes: procedures>+≡
  subroutine component_instance_write (object, unit, testflag)
    class(component_instance_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u, i
    u = given_output_unit (unit)
    if (object%active) then
      if (associated (object%config)) then
        write (u, "(1x,A,I0)") "Component #", object%config%index
      else
        write (u, "(1x,A)") "Component [undefined]"
      end if
    else
      write (u, "(1x,A,I0,A)") "Component #", object%config%index, &
        " [inactive]"
    end if
    if (allocated (object%p_seed)) then
      write (u, "(1x,A)") "Seed momenta:"
      do i = 1, size (object%p_seed)
        call vector4_write (object%p_seed(i), u, testflag = testflag)
      end do
    end if
    write (u, "(1x,A)") "Squared matrix element:"
    if (object%sqme_known) then
      write (u, "(2x,ES19.12)") object%sqme
    else
      write (u, "(2x,A)") "[undefined]"
    end if
    call object%k_seed%write (u)
    if (allocated (object%core_state)) then
      call write_separator (u)
      call object%core_state%write (u)
    end if
  end subroutine component_instance_write

```

Finalizer

```

<Processes: component instance: TBP>+≡
  procedure :: final => component_instance_final

<Processes: procedures>+≡
  subroutine component_instance_final (object)
    class(component_instance_t), intent(inout) :: object
    call object%k_seed%final ()
  end subroutine component_instance_final

```

Initialize: associate the configuration pointer. Also initialize the process workspace, if there is anything to do. This initialization is a matter of the process core.

```

<Processes: component instance: TBP>+≡

```



```

    procedure :: init => component_instance_init
  <Processes: procedures>+≡
    subroutine component_instance_init (component, config)
      class(component_instance_t), intent(out) :: component
      type(process_component_t), intent(in), target :: config
      integer :: nlo_type
      integer :: n_in, n_tot
      component%config => config
      nlo_type = component%config%config%get_nlo_type ()
      component%nlo_type = nlo_type
      associate (core => component%config%core)
        n_in = core%data%n_in
        n_tot = n_in + core%data%n_out
        select case (nlo_type)
          case (NLO_REAL)
            allocate (component%p_seed (n_tot -1))
          case (BORN, NLO_VIRTUAL, NLO_PDF)
            allocate (component%p_seed (n_tot))
          end select
        call core%allocate_workspace (component%core_state)
      end associate
    end subroutine component_instance_init

```

Initialize the seed-kinematics configuration. All subobjects are allocated explicitly.

```

  <Processes: component instance: TBP>+≡
    procedure :: setup_kinematics => component_instance_setup_kinematics
  <Processes: procedures>+≡
    subroutine component_instance_setup_kinematics (component, sf_chain, config, &
                                                    combined_integration)
      class(component_instance_t), intent(inout) :: component
      type(sf_chain_t), intent(in), target :: sf_chain
      type(process_beam_config_t), intent(in) :: config
      logical, intent(in), optional :: combined_integration
      integer :: nlo_type
      nlo_type = component%config%config%get_nlo_type ()
      if (present (combined_integration)) then
        if (combined_integration) then
          select type (phs_config => component%config%phs_config)
            type is (phs_wood_config_t)
              call phs_config%set_extended_phs ()
            end select
          end if
        end if
        call component%k_seed%init_sf_chain &
          (component%config%core, sf_chain, config, component%core_state)
        call component%k_seed%init_phs (component%config%phs_config)
      end subroutine component_instance_setup_kinematics
  <Processes: component instance: TBP>+≡
    procedure :: setup_fks_kinematics => component_instance_setup_fks_kinematics

```

```

<Processes: procedures>+≡
subroutine component_instance_setup_fks_kinematics (component, var_list)
  class(component_instance_t), intent(inout), target :: component
  type(var_list_t), intent(in) :: var_list
  logical :: singular_jacobian
  logical, dimension(:), allocatable :: is_massive
  select type (phs => component%k_seed%phs)
  type is (phs_fks_t)
    associate (nlo_controller => component%nlo_controller)
      call phs%setup_isr_kinematics (nlo_controller%isr_kinematics)
      call phs%setup_real_kinematics (nlo_controller%real_kinematics)
      call phs%set_beam_energy ()
      phs%massive_phsp = nlo_controller%has_massive_emitter ()
      call phs%set_emitters (nlo_controller%reg_data%emitters)
      call phs%setup_masses (nlo_controller%particle_data%n_in + &
                           nlo_controller%particle_data%n_out_born)
      is_massive = nlo_controller%get_mass_info(1)
      call phs%set_mass_info (is_massive)
      singular_jacobian = var_list%get_lval (var_str ("?powheg_use_singular_jacobian"))
      call phs%set_singular_jacobian (singular_jacobian)
    end associate
  !   call phs%setup_real_kinematics (component%nlo_controller%real_kinematics)
  !   call phs%set_beam_energy ()
  !   call phs%setup_isr_kinematics (component%nlo_controller%isr_kinematics)
  call phs%setup_generator_kinematics ()
class default
  call msg_fatal ("Phase space should be an FKS phase space!")
end select
end subroutine component_instance_setup_fks_kinematics

```

Setup seed kinematics, starting from the MC parameter set given as argument. As a result, the `k_seed` kinematics object is evaluated (except for the structure-function matrix-element evaluation, which we postpone until we know the factorization scale), and we have a valid `p_seed` momentum array.

```

<Processes: component instance: TBP>+≡
procedure :: compute_seed_kinematics => &
  component_instance_compute_seed_kinematics

<Processes: procedures>+≡
subroutine component_instance_compute_seed_kinematics &
  (component, mci_work, phs_channel, success)
  class(component_instance_t), intent(inout), target :: component
  type(mci_work_t), intent(in) :: mci_work
  integer, intent(in) :: phs_channel
  logical, intent(out) :: success
  select type (phs => component%k_seed%phs)
  type is (phs_fks_t)
    call component%k_seed%compute_selected_channel &
      (mci_work, phs_channel, component%p_seed, success, &
       component%nlo_controller)
    call component%nlo_controller%int_born%set_momenta &
      (component%p_seed)
class default
  call component%k_seed%compute_selected_channel &

```

```

        (mci_work, phs_channel, component%p_seed, success)
    end select
end subroutine component_instance_compute_seed_kinematics

```

Inverse: recover missing parts of the kinematics, given a complete set of seed momenta. Select a channel and reconstruct the MC parameter set.

```

<Processes: component instance: TBP>+≡
    procedure :: recover_mcpair => component_instance_recover_mcpair

<Processes: procedures>+≡
    subroutine component_instance_recover_mcpair (component, mci_work, phs_channel)
        class(component_instance_t), intent(inout), target :: component
        type(mci_work_t), intent(inout) :: mci_work
        integer, intent(in) :: phs_channel
        call component%k_seed%recover_mcpair &
            (mci_work, phs_channel, component%p_seed)
    end subroutine component_instance_recover_mcpair

```

Compute the momenta in the hard interactions, one for each term that constitutes this process component. In simple cases this amounts to just copying momenta. In more advanced cases, we may generate distinct sets of momenta from the seed kinematics.

The interactions in the term instances are accessed individually. We may choose to calculate all terms at once together with the seed kinematics, use `component%core_state` for storage, and just fill the interactions here.

```

<Processes: component instance: TBP>+≡
    procedure :: compute_hard_kinematics => &
        component_instance_compute_hard_kinematics

<Processes: procedures>+≡
    subroutine component_instance_compute_hard_kinematics &
        (component, term, skip_term, real_pbsp)
        class(component_instance_t), intent(inout) :: component
        type(term_instance_t), dimension(:), intent(inout) :: term
        integer, intent(in), optional :: skip_term
        logical, intent(in), optional :: real_pbsp
        integer :: j, i
        associate (core => component%config%core)
            associate (i_term => component%config%i_term)
                if (allocated (component%core_state)) then
                    call component%core_state%reset_new_kinematics ()
                end if
                do j = 1, size (i_term)
                    i = i_term(j)
                    if (present (skip_term)) then
                        if (i == skip_term) cycle
                    end if
                    if (present (real_pbsp)) then
                        if (real_pbsp) then
                            call core%compute_hard_kinematics &
                                (component%p_seed, i, term(i)%nlo_controller%int_born, &
                                    component%core_state)
                        else

```

```

        call core%compute_hard_kinematics &
            (component%p_seed, i, term(i)%int_hard, &
             component%core_state)
    end if
else
    call core%compute_hard_kinematics &
        (component%p_seed, i, term(i)%int_hard, component%core_state)
    end if
end do
end associate
end associate
end subroutine component_instance_compute_hard_kinematics

```

Here, we invert this. We fetch the incoming momenta which reside in the appropriate `sf_chain` object, stored within the `k_seed` subobject. On the other hand, we have the outgoing momenta of the effective interaction. We rely on the process core to compute the remaining seed momenta and to fill the momenta within the hard interaction. (The latter is trivial if hard and effective interaction coincide.)

After this is done, the incoming momenta in the trace evaluator that corresponds to the hard (effective) interaction, are still left undefined. We remedy this by calling `receive_kinematics` once.

```

<Processes: component instance: TBP>+≡
    procedure :: recover_seed_kinematics => &
        component_instance_recover_seed_kinematics

<Processes: procedures>+≡
    subroutine component_instance_recover_seed_kinematics (component, term)
        class(component_instance_t), intent(inout) :: component
        type(term_instance_t), intent(inout) :: term
        integer :: n_in
        n_in = component%k_seed%n_in
        call component%k_seed%get_incoming_momenta (component%p_seed(1:n_in))
        associate (core => component%config%core)
            call core%recover_kinematics &
                (component%p_seed, term%int_hard, term%isolated%int_eff, &
                 component%core_state)
            call term%isolated%receive_kinematics ()
        end associate
    end subroutine component_instance_recover_seed_kinematics

```

Compute the integration parameters for all channels except the selected one.

```

<Processes: component instance: TBP>+≡
    procedure :: compute_other_channels => &
        component_instance_compute_other_channels

<Processes: procedures>+≡
    subroutine component_instance_compute_other_channels &
        (component, mci_work, phs_channel)
        class(component_instance_t), intent(inout), target :: component
        type(mci_work_t), intent(in) :: mci_work
        integer, intent(in) :: phs_channel
        call component%k_seed%compute_other_channels (mci_work, phs_channel)
    end subroutine component_instance_compute_other_channels

```

```
end subroutine component_instance_compute_other_channels
```

Recover beam momenta, i.e., return the beam momenta as currently stored in the kinematics subobject to their source. This is a side effect.

```
<Processes: component instance: TBP>+≡
  procedure :: return_beam_momenta => component_instance_return_beam_momenta

<Processes: procedures>+≡
  subroutine component_instance_return_beam_momenta (component)
    class(component_instance_t), intent(in) :: component
    call component%k_seed%return_beam_momenta ()
  end subroutine component_instance_return_beam_momenta
```

```
<Processes: component instance: TBP>+≡
  procedure :: evaluate_sqme_born => component_instance_evaluate_sqme_born

<Processes: procedures>+≡
  subroutine component_instance_evaluate_sqme_born (component, term)
    class(component_instance_t), intent(inout) :: component
    type(term_instance_t), intent(inout), target :: term
    real(default) :: sqme
    sqme = real (term%connected%trace%get_matrix_element (1))
    component%sqme = sqme * term%weight
  end subroutine component_instance_evaluate_sqme_born
```

Evaluate the trace of the transition matrix, convoluted with the initial state, and summed over all terms. The trace evaluators of the individual terms have only a single matrix element. We implicitly drop the imaginary part of the terms, which should be zero anyway.

```
<Processes: component instance: TBP>+≡
  procedure :: evaluate_sqme => component_instance_evaluate_sqme

<Processes: procedures>+≡
  subroutine component_instance_evaluate_sqme (component, term)
    class(component_instance_t), intent(inout) :: component
    type(term_instance_t), dimension(:), intent(inout), target :: term
    integer :: j, i

    component%sqme = 0
    call reset_nlo_components (component)
    associate (i_term => component%config%i_term)
      do j = 1, size (i_term)
        i = i_term(j)
        if (term(i)%passed) then
          call component%evaluate_sqme_born (term(i))
          call associate_sqme_born (component, component%sqme*term(i)%weight)
          call component%evaluate_sqme_real (term(i))
          call component%evaluate_sqme_virt (term(i))
          call component%evaluate_sqme_pdf (term(i))
        end if
      end do
    end associate
    component%sqme_known = .true.
```

```
end subroutine component_instance_evaluate_sqme
```

(Processes: procedures)+≡

```
subroutine reset_nlo_components (component)
  type(component_instance_t), intent(inout) :: component
  select case (component%config%config%get_nlo_type ())
  case (NLO_REAL, NLO_VIRTUAL, NLO_PDF)
    associate (collector => component%nlo_controller%sqme_collector)
      collector%current_sqme_born = 0
      collector%sqme_real_non_sub = 0
    end associate
  end select
end subroutine reset_nlo_components
```

(Processes: procedures)+≡

```
subroutine associate_sqme_born (component, summand)
  type(component_instance_t), intent(inout) :: component
  real(default), intent(in) :: summand
  select case (component%config%config%get_nlo_type ())
  case (NLO_REAL)
    associate (collector => component%nlo_controller%sqme_collector)
      collector%current_sqme_born = summand
      collector%sqme_born_list(1) = summand
    end associate
  end select
end subroutine associate_sqme_born
```

Perform the matrix-element-evaluation if the component is flagged as virtual

(Processes: component instance: TBP)+≡

```
procedure :: evaluate_sqme_virt => component_instance_evaluate_sqme_virt
```

(Processes: procedures)+≡

```
subroutine component_instance_evaluate_sqme_virt (component, term)
  class(component_instance_t), intent(inout) :: component
  type(term_instance_t), intent(inout) :: term
  real(default), dimension(4) :: sqme_virt
  integer :: i_flg
  logical :: bad_point

  if (term%nlo_type /= NLO_VIRTUAL) return
  associate (nlo_controller => component%nlo_controller)
    call nlo_controller%set_alpha_s_born &
      (component%config%core%get_alpha_s (component%core_state))
    call nlo_controller%virtual_terms%set_ren_scale &
      (term%int_hard%get_momenta (), term%ren_scale)
    call nlo_controller%virtual_terms%set_fac_scale &
      (term%int_hard%get_momenta (), term%fac_scale)
    select type (core => component%config%core)
    class is (prc_blha_t)
      do i_flg = 1, core%get_nflv()
        call core%update_alpha_s (component%core_state, term%fac_scale)
        call core%compute_sqme_virt (i_flg, &
          term%int_hard%get_momenta (), &
```

```

        term%ren_scale, &
        sqme_virt, bad_point)
    if (.not. nlo_controller%use_internal_color_correlations) &
        call core%compute_sqme_cc (i_flv, &
            term%int_hard%get_momenta (), &
            term%ren_scale, &
            born_cc = nlo_controller%sqme_collector%sqme_born_cc (:,:,i_flv), &
            bad_point = bad_point)
    call nlo_controller%virtual_terms%set_vfin (sqme_virt(3))
    call nlo_controller%virtual_terms%set_bad_point (bad_point)
    nlo_controller%sqme_collector%current_sqme_born = sqme_virt (4)
    component%sqme = component%sqme + &
        nlo_controller%compute_virt (i_flv, term%int_hard) * &
        term%weight
end do
call core%print_parameter_file ()
end select

end associate
end subroutine component_instance_evaluate_sqme_virt

```

Perform the matrix-element evaluation if the component is flagged as pdf

```

<Processes: component instance: TBP>+≡
    procedure :: evaluate_sqme_pdf => component_instance_evaluate_sqme_pdf

<Processes: procedures>+≡
    subroutine component_instance_evaluate_sqme_pdf (component, term)
        class(component_instance_t), intent(inout) :: component
        type(term_instance_t), intent(inout) :: term
        real(default) :: sqme_pdf
        if (term%nlo_type /= NLO_PDF) return
        associate (nlo_controller => component%nlo_controller)
            if (.not. nlo_controller%pdf_subtraction_is_required ()) return
            call nlo_controller%set_alpha_s_born &
                (component%config%core%get_alpha_s (component%core_state))
            sqme_pdf = nlo_controller%evaluate_pdf_subtraction (term%weight, component%sqme)
        end associate
    end subroutine component_instance_evaluate_sqme_pdf

```

Perform the matrix-element evaluation if the component is flagged as real

```

<Processes: component instance: TBP>+≡
    procedure :: evaluate_sqme_real => component_instance_evaluate_sqme_real

<Processes: procedures>+≡
    subroutine component_instance_evaluate_sqme_real (component, term)
        class(component_instance_t), intent(inout) :: component
        type(term_instance_t), intent(inout), target :: term
        type(vector4_t), dimension(:), allocatable :: p_real
        integer :: i_flv
        logical :: bad_point

        if (term%nlo_type /= NLO_REAL) return
        p_real = term%nlo_controller%get_real_momenta ()
        select type (core => component%config%core)

```

```

!!! Get the unsubtracted real matrix element,
!!! either from the parton states or from GoSam
type is (prc_omega_t)
    component%nlo_controller%sqme_collector%sqme_real_non_sub = &
        real (term%connected_real%trace%get_matrix_element (1))
class is (prc_blha_t)
    do i_flv = 1, component%nlo_controller%get_n_flv_real ()
        call core%update_alpha_s (component%core_state, term%fac_scale)
        call core%compute_sqme_real (i_flv, p_real, 0._default, &
            component%nlo_controller%sqme_collector%sqme_real_non_sub(i_flv), &
            bad_point)
    end do
end select
!!! Get the necessary subtraction matrix elements.
associate (nlo_controller => component%nlo_controller)
    if (nlo_controller%is_subtraction_active ()) then
        associate (collector => nlo_controller%sqme_collector)
        select type (core_born => component%config%core_sub_born)
        class is (prc_blha_t)
            do i_flv = 1, nlo_controller%get_n_flv_born ()
                if (.not. nlo_controller%use_internal_color_correlations) then
                    call core_born%update_alpha_s (component%core_state, term%fac_scale)
                    call core_born%compute_sqme_cc (i_flv, &
                        nlo_controller%int_born%get_momenta (), &
                        0._default, &
                        collector%sqme_born_list (i_flv), &
                        collector%sqme_born_cc (:,:,i_flv), &
                        bad_point)
                else
                    !!! Implementation for color-correlations using color_data
                end if
                if (.not. nlo_controller%use_internal_spin_correlations &
                    .and. nlo_controller%requires_spin_correlation (i_flv)) then
                    call core_born%update_alpha_s (component%core_state, term%fac_scale)
                    call core_born%compute_sqme_sc (i_flv, 5, &
                        nlo_controller%int_born%get_momenta (), &
                        0._default, collector%sqme_born_sc(i_flv), bad_point)
                end if
            end do
        end do
        type is (prc_omega_t)
            collector%sqme_born_cc (:,:,1) = collector%current_sqme_born * &
                nlo_controller%color_data%beta_ij (:,:,1)
        end select
    end associate
end if
call nlo_controller%set_alpha_s_born &
    (component%config%core%get_alpha_s (component%core_state))
nlo_controller%sqme_collector%current_sqme_real = &
    nlo_controller%compute_sqme_real_fin (term%weight, p_real)
end associate
end subroutine component_instance_evaluate_sqme_real

```

Get nlo-type and emitter of the component.


```

<Processes: component instance: TBP>+≡
    procedure :: get_nlo_type => component_instance_get_nlo_type

<Processes: procedures>+≡
    elemental function component_instance_get_nlo_type (component) &
        result (nlo_type)
        class(component_instance_t), intent(in) :: component
        integer :: nlo_type
        nlo_type = component%nlo_type
    end function component_instance_get_nlo_type

<Processes: component instance: TBP>+≡
    procedure :: get_component_type => &
        component_instance_get_component_type

<Processes: procedures>+≡
    function component_instance_get_component_type (component) result (val)
        class(component_instance_t), intent(in) :: component
        integer :: val
        val = component%config%component_type
    end function component_instance_get_component_type

<Processes: component instance: TBP>+≡
    procedure :: set_component_type => &
        component_instance_set_component_type

<Processes: procedures>+≡
    subroutine component_instance_set_component_type (component, val)
        class(component_instance_t), intent(in) :: component
        integer, intent(in) :: val
        component%config%component_type = val
    end subroutine component_instance_set_component_type

<Processes: process component: TBP>+≡
    procedure :: needs_mci_entry => process_component_needs_mci_entry

<Processes: procedures>+≡
    function process_component_needs_mci_entry (component) result (value)
        class(process_component_t), intent(in) :: component
        logical :: value
        value = component%active .and. component%core%needs_mcset () &
            .and. component%component_type <= COMP_MASTER
    end function process_component_needs_mci_entry

```

Term instance

A `term_instance_t` object contains all data that describe a term. Each process component consists of one or more distinct terms which may differ in kinematics, but whose squared transition matrices have to be added pointwise.

The `active` flag is set when this term is connected to an active process component. Inactive terms are skipped for kinematics and evaluation.

The `k_term` object is the instance of the kinematics setup (structure-function chain, phase space, etc.) that applies specifically to this term. In ordinary cases, it consists of straight pointers to the seed kinematics.

The `amp` array stores the amplitude values when we get them from evaluating the associated matrix-element code.

The `int_hard` interaction describes the elementary hard process. It receives the momenta and the amplitude entries for each sampling point.

The `isolated` object holds the effective parton state for the elementary interaction. The amplitude entries are computed from `int_hard`.

The `connected` evaluator set convolutes this scattering matrix with the beam (and possibly structure-function) density matrix.

The `checked` flag is set once we have applied cuts on this term. The result of this is stored in the `passed` flag. Once the term has passed cuts, we calculate the various scale and weight expressions.

```

(Processes: types)+≡
  type :: term_instance_t
    type(process_term_t), pointer :: config => null ()
    logical :: active = .false.
    type(kinematics_t) :: k_term
    complex(default), dimension(:), allocatable :: amp
    type(interaction_t) :: int_hard
    type(interaction_t) :: int_hard_real
    type(isolated_state_t) :: isolated
    type(connected_state_t) :: connected
    type(isolated_state_t) :: isolated_real
    type(connected_state_t) :: connected_real
    logical :: checked = .false.
    logical :: passed = .false.
    real(default) :: scale = 0
    real(default) :: fac_scale = 0
    real(default) :: ren_scale = 0
    real(default), allocatable :: alpha_qcd_forced
    real(default) :: weight = 1
    type(vector4_t), dimension(:), allocatable :: p_hard
    type(nlo_controller_t), pointer :: nlo_controller => null ()
    integer :: nlo_type = BORN
  contains
    (Processes: term instance: TBP)
  end type term_instance_t

(Processes: term instance: TBP)≡
  procedure :: write => term_instance_write

(Processes: procedures)+≡
  subroutine term_instance_write (term, unit, show_eff_state, testflag)
    class(term_instance_t), intent(in) :: term
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_eff_state
    logical, intent(in), optional :: testflag
    integer :: u
    logical :: state
    u = given_output_unit (unit)
    state = .true.; if (present (show_eff_state)) state = show_eff_state

```

```

if (term%active) then
  if (associated (term%config)) then
    write (u, "(1x,A,IO,A,IO,A)") "Term #", term%config%i_term, &
      " (component #", term%config%i_component, ")"
  else
    write (u, "(1x,A)") "Term [undefined]"
  end if
else
  write (u, "(1x,A,IO,A)") "Term #", term%config%i_term, &
    " [inactive]"
end if
if (term%checked) then
  write (u, "(3x,A,L1)") "passed cuts" = ", term%passed
end if
if (term%passed) then
  write (u, "(3x,A,ES19.12)") "overall scale" = ", term%scale
  write (u, "(3x,A,ES19.12)") "factorization scale" = ", term%fac_scale
  write (u, "(3x,A,ES19.12)") "renormalization scale" = ", term%ren_scale
  if (allocated (term%alpha_qcd_forced)) then
    write (u, "(3x,A,ES19.12)") "alpha(QCD) forced" = ", &
      term%alpha_qcd_forced
  end if
  write (u, "(3x,A,ES19.12)") "reweighting factor" = ", term%weight
end if
call term%k_term%write (u)
call write_separator (u)
write (u, "(1x,A)") "Amplitude (transition matrix of the &
  &hard interaction):"
call write_separator (u)
call term%int_hard%basic_write (u, testflag = testflag)
if (state .and. term%isolated%has_trace) then
  call write_separator (u)
  write (u, "(1x,A)") "Evaluators for the hard interaction:"
  call term%isolated%write (u, testflag = testflag)
end if
if (state .and. term%connected%has_trace) then
  call write_separator (u)
  write (u, "(1x,A)") "Evaluators for the connected process:"
  call term%connected%write (u, testflag = testflag)
end if
end subroutine term_instance_write

```

The interactions and evaluators must be finalized.

```

<Processes: term instance: TBP>+≡
  procedure :: final => term_instance_final

<Processes: procedures>+≡
  subroutine term_instance_final (term)
    class(term_instance_t), intent(inout) :: term
    call term%k_term%final ()
    call term%connected%final ()
    call term%isolated%final ()
    call term%int_hard%final ()
    select case (term%nlo_type)

```

```

case (NLO_REAL)
  call term%connected_real%final ()
  call term%isolated_real%final ()
  call term%int_hard_real%final ()
end select
end subroutine term_instance_final

```

For initialization, we make use of defined assignment for the `interaction_t` type. This creates a deep copy.

The hard interaction (incoming momenta) is linked to the structure function instance. In the isolated state, we either set pointers to both, or we create modified copies (`rearrange`) as effective structure-function chain and interaction, respectively.

Finally, we set up the `subevt` component that will be used for evaluating observables, collecting particles from the trace evaluator in the effective connected state. Their quantum numbers must be determined by following back source links and set explicitly, since they are already eliminated in that trace.

The `rearrange` parts are still commented out; they could become relevant for a NLO algorithm.

```

<Processes: term instance: TBP>+≡
  procedure :: init => term_instance_init

<Processes: procedures>+≡
  subroutine term_instance_init (term, &
    config, k_seed, beam_config, core, process_var_list, nlo_controller)
    class(term_instance_t), intent(inout), target :: term
    type(process_term_t), intent(in), target :: config
    type(kinematics_t), intent(in) :: k_seed
    type(process_beam_config_t), intent(in) :: beam_config
    type(interaction_t), pointer :: sf_chain_int
    type(interaction_t), pointer :: src_int
    class(prc_core_t), intent(in) :: core
    type(var_list_t), intent(in), target :: process_var_list
    type(nlo_controller_t), intent(inout), pointer :: nlo_controller
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask_in
    type(state_matrix_t), pointer :: state_matrix
    type(flavor_t), dimension(:), allocatable :: flv_int, flv_src, f_in, f_out
    type(flavor_t), dimension(:), allocatable :: f_out_real
    integer :: n_in, n_vir, n_out, n_tot
    integer :: i, j
    type(interaction_t), pointer, save :: int_sav
    type(sf_chain_instance_t), pointer, save :: sf_sav
    integer, dimension(:), allocatable, save :: col_sav
    type(prc_omega_t), save :: core_sav

    term%config => config
    term%nlo_controller => nlo_controller
    if (config%rearrange) then
      ! rearrangement of seed to hard kinematics not implemented yet
      ! allocate k_term distinct from k_seed as needed.
    else
      ! here, k_term trivially accesses k_seed via pointers
      call term%k_term%init_ptr (k_seed)
    end if
  end subroutine

```

```

end if
allocate (term%amp (config%n_allowed))
term%int_hard = config%int
allocate (term%p_hard (term%int_hard%get_n_tot ()))
sf_chain_int => term%k_term%sf_chain%get_out_int_ptr ()
n_in = term%int_hard%get_n_in ()
do j = 1, n_in
  i = term%k_term%sf_chain%get_out_i (j)
  call term%int_hard%set_source_link (j, sf_chain_int, i)
end do
if (config%rearrange) then
  ! rearrangement hard to effective kinematics not implemented yet
  ! should use term%config%int_eff as template
  ! allocate distinct sf_chain in term%connected as needed
else
  select type (phs => term%k_term%phs)
    type is (phs_wood_t)
      ! here, int_hard and sf_chain are trivially accessed via pointers
      call term%isolated%init (term%k_term%sf_chain, term%int_hard)
      int_sav => term%int_hard
      sf_sav => term%k_term%sf_chain
    type is (phs_fks_t)
      select case (phs%mode)
        case (PHS_MODE_ADDITIONAL_PARTICLE)
          term%nlo_controller%int_born = int_sav
          call term%isolated%init (sf_sav, term%nlo_controller%int_born)
          call term%setup_real_interaction (term%int_hard)
        case (PHS_MODE_COLLINEAR_REMNANT)
          call term%isolated%init (term%k_term%sf_chain, term%int_hard)
        end select
      class default
        call term%isolated%init (term%k_term%sf_chain, term%int_hard)
      end select
    end if
  allocate (mask_in (n_in))
  mask_in = term%k_term%sf_chain%get_out_mask ()
  select type (phs => term%k_term%phs)
    type is (phs_wood_t)
      call term%isolated%setup_square_trace (core, mask_in, term%config%col)
      if (.not. allocated (col_sav)) then
        allocate (col_sav (size (term%config%col)))
        col_sav = term%config%col
      end if
      select type (core)
        type is (prc_omega_t)
          core_sav = core
        end select
      type is (phs_fks_t)
        select case (phs%mode)
          case (PHS_MODE_ADDITIONAL_PARTICLE)
            mask_in = sf_sav%get_out_mask ()
            call term%isolated%setup_square_trace (core_sav, mask_in, col_sav)
            call term%init_states (core)
          case (PHS_MODE_COLLINEAR_REMNANT)

```

```

        call term%isolated%setup_square_trace (core, mask_in, term%config%col)
    end select
    class default
        call term%isolated%setup_square_trace (core, mask_in, term%config%col)
    end select
    call term%connected%setup_connected_trace (term%isolated)
    associate (int_eff => term%isolated%int_eff)
        state_matrix => int_eff%get_state_matrix_ptr ()
        n_tot = int_eff%get_n_tot ()
        allocate (flv_int (n_tot))
        flv_int = quantum_numbers_get_flavor &
            (state_matrix%get_quantum_numbers (1))
        allocate (f_in (n_in))
        f_in = flv_int(1:n_in)
        deallocate (flv_int)
    end associate
    n_in = term%connected%trace%get_n_in ()
    n_vir = term%connected%trace%get_n_vir ()
    n_out = term%connected%trace%get_n_out ()
    allocate (f_out (n_out))
    do j = 1, n_out
        call term%connected%trace%find_source &
            (n_in + n_vir + j, src_int, i)
        if (associated (src_int)) then
            state_matrix => src_int%get_state_matrix_ptr ()
            allocate (flv_src (src_int%get_n_tot ()))
            flv_src = quantum_numbers_get_flavor &
                (state_matrix%get_quantum_numbers (1))
            f_out(j) = flv_src(i)
            deallocate (flv_src)
        end if
    end do
    call term%connected%setup_subevt (term%isolated%sf_chain_eff, &
        beam_config%data%flv, f_in, f_out)
    call term%connected%setup_var_list (process_var_list, beam_config%data)
    select case (term%nlo_type)
    case (NLO_REAL)
        allocate (f_out_real (n_out+1))
        f_out_real (1:n_out) = f_out
        f_out_real (n_out+1) = term%nlo_controller%reg_data%flv_extra
        call term%connected_real%setup_subevt (term%isolated_real%sf_chain_eff, &
            beam_config%data%flv, f_in, f_out_real)
        call term%connected_real%setup_var_list (process_var_list, beam_config%data)
    end select

end subroutine term_instance_init

```

Set up the state objects.

```

<Processes: term instance: TBP>+≡
    procedure :: init_states => term_instance_init_states

<Processes: procedures>+≡
    subroutine term_instance_init_states (term, core)
        class(term_instance_t), intent(inout), target :: term

```

```

class(prc_core_t), intent(in) :: core
type(quantum_numbers_mask_t), dimension(:), allocatable :: mask_in
integer :: i
mask_in = term%k_term%sf_chain%get_out_mask ()
call term%isolated_real%init (term%k_term%sf_chain, term%int_hard_real)
call term%isolated_real%setup_square_trace (core, mask_in, term%config%col)
call term%connected_real%setup_connected_trace (term%isolated_real)
end subroutine term_instance_init_states

```

For initializing the expressions, we need the local variable list and the parse trees.

(Processes: term instance: TBP)+≡

```

procedure :: setup_expressions => term_instance_setup_expressions

```

(Processes: procedures)+≡

```

subroutine term_instance_setup_expressions (term, meta, config)
class(term_instance_t), intent(inout), target :: term
type(process_metadata_t), intent(in), target :: meta
type(process_config_data_t), intent(in) :: config
if (allocated (config%ef_cuts)) &
    call term%connected%setup_cuts (config%ef_cuts)
if (allocated (config%ef_scale)) &
    call term%connected%setup_scale (config%ef_scale)
if (allocated (config%ef_fac_scale)) &
    call term%connected%setup_fac_scale (config%ef_fac_scale)
if (allocated (config%ef_ren_scale)) &
    call term%connected%setup_ren_scale (config%ef_ren_scale)
if (allocated (config%ef_weight)) &
    call term%connected%setup_weight (config%ef_weight)
end subroutine term_instance_setup_expressions

```

(Processes: term instance: TBP)+≡

```

procedure :: setup_expressions_real => term_instance_setup_expressions_real

```

(Processes: procedures)+≡

```

subroutine term_instance_setup_expressions_real (term, meta, config)
class(term_instance_t), intent(inout), target :: term
type(process_metadata_t), intent(in), target :: meta
type(process_config_data_t), intent(in) :: config
if (allocated (config%ef_cuts)) &
    call term%connected_real%setup_cuts (config%ef_cuts)
if (allocated (config%ef_scale)) &
    call term%connected_real%setup_scale (config%ef_scale)
if (allocated (config%ef_fac_scale)) &
    call term%connected_real%setup_fac_scale (config%ef_fac_scale)
if (allocated (config%ef_ren_scale)) &
    call term%connected_real%setup_ren_scale (config%ef_ren_scale)
if (allocated (config%ef_weight)) &
    call term%connected_real%setup_weight (config%ef_weight)
end subroutine term_instance_setup_expressions_real

```

Prepare the extra evaluators that we need for processing events.

The quantum numbers mask of the incoming particle

```

(Processes: term instance: TBP)+≡
  procedure :: setup_event_data => term_instance_setup_event_data

(Processes: procedures)+≡
  subroutine term_instance_setup_event_data (term, core, model)
    class(term_instance_t), intent(inout), target :: term
    class(prc_core_t), intent(in) :: core
    class(model_data_t), intent(in), target :: model
    integer :: n_in
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask_in
    n_in = term%int_hard%get_n_in ()
    allocate (mask_in (n_in))
    mask_in = term%k_term%sf_chain%get_out_mask ()
    select case (term%nlo_type)
    case (BORN, NLO_VIRTUAL, NLO_PDF)
      call term%isolated%setup_square_matrix (core, model, mask_in, &
        term%config%col)
      call term%isolated%setup_square_flows (core, model, mask_in)
      call term%connected%setup_connected_matrix (term%isolated)
      call term%connected%setup_connected_flows (term%isolated)
      call term%connected%setup_state_flv (term%isolated%get_n_out ())
    case (NLO_REAL)
      call term%isolated_real%setup_square_matrix (core, model, mask_in, &
        term%config%col)
      call term%isolated_real%setup_square_flows (core, model, mask_in)
      call term%connected_real%setup_connected_matrix &
        (term%isolated_real)
      call term%connected_real%setup_connected_flows &
        (term%isolated_real)
      call term%connected_real%setup_state_flv (term%isolated_real%get_n_out ())
    end select
  end subroutine term_instance_setup_event_data

```

Associate the hard real interaction.

```

(Processes: term instance: TBP)+≡
  procedure :: setup_real_interaction => term_instance_setup_real_interaction

(Processes: procedures)+≡
  subroutine term_instance_setup_real_interaction (term, int)
    class(term_instance_t), intent(inout) :: term
    type(interaction_t), intent(in) :: int
    integer :: i
    term%int_hard_real = int
  end subroutine term_instance_setup_real_interaction

```

Reset the term instance: clear the parton-state expressions and deactivate.

```

(Processes: term instance: TBP)+≡
  procedure :: reset => term_instance_reset

(Processes: procedures)+≡
  subroutine term_instance_reset (term)
    class(term_instance_t), intent(inout) :: term
    call term%connected%reset_expressions ()

```



```

        if (allocated (term%alpha_qcd_forced)) deallocate (term%alpha_qcd_forced)
        term%active = .false.
    end subroutine term_instance_reset

```

Force an α_s value that should be used in the matrix-element calculation.

```

<Processes: term instance: TBP>+≡
    procedure :: set_alpha_qcd_forced => term_instance_set_alpha_qcd_forced

<Processes: procedures>+≡
    subroutine term_instance_set_alpha_qcd_forced (term, alpha_qcd)
        class(term_instance_t), intent(inout) :: term
        real(default), intent(in) :: alpha_qcd
        if (allocated (term%alpha_qcd_forced)) then
            term%alpha_qcd_forced = alpha_qcd
        else
            allocate (term%alpha_qcd_forced, source = alpha_qcd)
        end if
    end subroutine term_instance_set_alpha_qcd_forced

```

Complete the kinematics computation for the effective parton states.

We assume that the `compute_hard_kinematics` method of the process component instance has already been called, so the `int_hard` contains the correct hard kinematics. The duty of this procedure is first to compute the effective kinematics and store this in the `int_eff` effective interaction inside the `isolated` parton state. The effective kinematics may differ from the kinematics in the hard interaction. It may involve parton recombination or parton splitting. The `rearrange_partons` method is responsible for this part.

We may also call a method to compute the effective structure-function chain at this point. This is not implemented yet.

In the simple case that no rearrangement is necessary, as indicated by the `rearrange` flag, the effective interaction is a pointer to the hard interaction, and we can skip the rearrangement method. Similarly for the effective structure-function chain. (If we have an algorithm that uses rearrangement, it should evaluate `k_term` explicitly.)

The final step of kinematics setup is to transfer the effective kinematics to the evaluators and to the `subevt`.

```

<Processes: term instance: TBP>+≡
    procedure :: compute_eff_kinematics => &
        term_instance_compute_eff_kinematics

<Processes: procedures>+≡
    subroutine term_instance_compute_eff_kinematics (term, component)
        class(term_instance_t), intent(inout) :: term
        type(component_instance_t), dimension(:), intent(inout) :: component
        integer :: i_component, i_term
        term%checked = .false.
        term%passed = .false.
        if (term%config%rearrange) then
            ! should evaluate k_term first if allocated separately, not impl. yet
            i_component = term%config%i_component
            i_term = term%config%i_term
            associate (core => component(i_component)%config%core)

```

```

select case (term%nlo_type)
case (BORN, NLO_VIRTUAL, NLO_PDF)
  call core%compute_eff_kinematics &
    (i_term, term%int_hard, term%isolated%int_eff, &
     component(i_component)%core_state)
case (NLO_REAL)
  call component(i_component)%config%core_sub_born%compute_eff_kinematics &
    (i_term, term%nlo_controller%int_born, term%isolated%int_eff, &
     component(i_component)%core_state)
end select
select case (term%nlo_type)
case (NLO_REAL)
  call core%compute_eff_kinematics &
    (i_term, term%int_hard_real, term%isolated_real%int_eff, &
     component(i_component)%core_state)
end select
end associate
end if
call term%isolated%receive_kinematics ()
call term%connected%receive_kinematics ()
end subroutine term_instance_compute_eff_kinematics

```

Inverse. Reconstruct the connected state from the momenta in the trace evaluator (which we assume to be set), then reconstruct the isolated state as far as possible. The second part finalizes the momentum configuration, using the incoming seed momenta

```

(Processes: term instance: TBP)+≡
  procedure :: recover_hard_kinematics => &
    term_instance_recover_hard_kinematics

(Processes: procedures)+≡
  subroutine term_instance_recover_hard_kinematics (term, component)
    class(term_instance_t), intent(inout) :: term
    type(component_instance_t), dimension(:), intent(inout) :: component
    term%checked = .false.
    term%passed = .false.
    call term%connected%send_kinematics ()
    call term%isolated%send_kinematics ()
  end subroutine term_instance_recover_hard_kinematics

```

Check the term whether it passes cuts and, if successful, evaluate scales and weights. The factorization scale is also given to the term kinematics, enabling structure-function evaluation.

```

(Processes: term instance: TBP)+≡
  procedure :: evaluate_expressions => &
    term_instance_evaluate_expressions

(Processes: procedures)+≡
  subroutine term_instance_evaluate_expressions (term, scale_forced)
    class(term_instance_t), intent(inout) :: term
    real(default), intent(in), allocatable, optional :: scale_forced
    call term%connected%evaluate_expressions (term%passed, &
      term%scale, term%fac_scale, term%ren_scale, term%weight, &

```

```

        scale_forced)
    term%checked = .true.
end subroutine term_instance_evaluate_expressions

```

Evaluate the trace: first evaluate the hard interaction, then the trace evaluator. We use the `evaluate_interaction` method of the process component which generated this term. The `subevt` and `cut` expressions are not yet filled.

The `component` argument is `intent(inout)` because the `compute_amplitude` method may modify the `core_state` workspace object.

(Processes: term instance: TBP)+≡

```

    procedure :: evaluate_interaction => term_instance_evaluate_interaction

```

(Processes: procedures)+≡

```

subroutine term_instance_evaluate_interaction (term, component)
    class(term_instance_t), intent(inout) :: term
    type(component_instance_t), dimension(:), intent(inout) :: component
    integer :: i_component, i_term, i
    i_component = term%config%i_component
    i_term = term%config%i_term
    term%p_hard = term%int_hard%get_momenta ()
    select case (term%nlo_type)
    case (BORN, NLO_VIRTUAL, NLO_PDF)
        associate (core => component(i_component)%config%core)
            do i = 1, term%config%n_allowed
                term%amp(i) = core%compute_amplitude (i_term, term%p_hard, &
                    term%config%flv(i), term%config%hel(i), term%config%col(i), &
                    term%fac_scale, term%ren_scale, term%alpha_qcd_forced, &
                    component(i_component)%core_state)
            end do
            call term%int_hard%set_matrix_element (term%amp)
            if (associated (term%nlo_controller)) call term%nlo_controller%set_fac_scale (term%fac_s
        end associate
    case (NLO_REAL)
        call term%evaluate_interaction_real (component(i_component), i_term)
    end select
end subroutine term_instance_evaluate_interaction

```

Evaluate the trace. First evaluate the structure-function chain (i.e., the density matrix of the incoming partons). Do this twice, in case the `sf-chain` instances within `k_term` and `isolated` differ. Next, evaluate the hard interaction, then compute the convolution with the initial state.

(Processes: term instance: TBP)+≡

```

    procedure :: evaluate_trace => term_instance_evaluate_trace

```

(Processes: procedures)+≡

```

subroutine term_instance_evaluate_trace (term)
    class(term_instance_t), intent(inout) :: term
    call term%k_term%evaluate_sf_chain (term%fac_scale)
    call term%isolated%evaluate_sf_chain (term%fac_scale)
    call term%isolated%evaluate_trace ()
    call term%connected%evaluate_trace ()
    select case (term%nlo_type)
    case (NLO_REAL)

```

```

        call term%isolated_real%evaluate_trace ()
        call term%connected_real%evaluate_trace ()
    end select
end subroutine term_instance_evaluate_trace

```

Evaluate the extra data that we need for processing the object as a physical event.

```

<Processes: term instance: TBP>+≡
    procedure :: evaluate_event_data => term_instance_evaluate_event_data

<Processes: procedures>+≡
    subroutine term_instance_evaluate_event_data (term)
        class(term_instance_t), intent(inout) :: term
        select case (term%nlo_type)
        case (BORN, NLO_VIRTUAL, NLO_PDF)
            call term%isolated%evaluate_event_data ()
            call term%connected%evaluate_event_data ()
        case (NLO_REAL)
            call term%isolated_real%evaluate_event_data ()
            call term%connected_real%evaluate_event_data ()
        end select
    end subroutine term_instance_evaluate_event_data

```

Evaluate interaction for an $N + 1$ -particle phase space

```

<Processes: term instance: TBP>+≡
    procedure :: evaluate_interaction_real &
        => term_instance_evaluate_interaction_real

<Processes: procedures>+≡
    subroutine term_instance_evaluate_interaction_real (term, component, i_term)
        class(term_instance_t), intent(inout) :: term
        type(component_instance_t), intent(inout) :: component
        integer, intent(in) :: i_term
        integer :: emitter
        type(vector4_t), dimension(:), allocatable :: p_born
        type(vector4_t), dimension(:), allocatable :: p_real
        integer :: i

        emitter = term%nlo_controller%get_active_emitter ()
        p_born = term%nlo_controller%int_born%get_momenta ()
        select type (phs => term%k_term%phs)
        type is (phs_fks_t)
            if (emitter > 2) then
                call phs%generate_fsr (emitter, p_born, p_real)
            else
                call phs%generate_isr (emitter, p_born, p_real)
            end if
        class default
            call msg_fatal ("Evaluate real interaction: Phase space not of FKS-type!")
        end select

        call term%nlo_controller%set_real_momenta (p_real)
        call term%int_hard_real%set_momenta (p_real)
    end subroutine term_instance_evaluate_interaction_real

```

```

call term%isolated_real%receive_kinematics ()
call term%connected_real%receive_kinematics ()

call term%connected_real%evaluate_expressions (term%passed, &
    term%scale, term%fac_scale, term%ren_scale, term%weight)

if (term%passed) then
    call component%core_state%reset_new_kinematics ()
    select type (core => component%config%core)
    type is (prc_omega_t)
        do i = 1, term%config%n_allowed
            term%amp(i) = core%compute_amplitude (i_term, &
                term%int_hard_real%get_momenta (), &
                term%config%flv(i), term%config%hel(i), term%config%col(i), &
                term%fac_scale, term%ren_scale, term%alpha_qcd_forced, &
                component%core_state)
        end do
    class is (prc_blha_t)
        call core%update_alpha_s (component%core_state, term%fac_scale)
        term%amp = 0._default
    end select
    call term%int_hard_real%set_matrix_element (term%amp)
    call component%core_state%reset_new_kinematics ()
    select type (core_sub_born => component%config%core_sub_born)
    type is (prc_omega_t)
        do i = 1, term%nlo_controller%n_allowed_born
            term%nlo_controller%amp_born(i) = &
                core_sub_born%compute_amplitude (i_term, &
                term%nlo_controller%int_born%get_momenta (), &
                term%nlo_controller%get_flv_born(i), &
                term%nlo_controller%get_hel_born(i), &
                term%nlo_controller%get_col_born(i), &
                term%fac_scale, term%ren_scale, &
                term%alpha_qcd_forced, &
                component%core_state)
        end do
    class is (prc_blha_t)
        call core_sub_born%update_alpha_s &
            (component%core_state, term%fac_scale)
        term%nlo_controller%amp_born = 0._default
    end select
    call term%nlo_controller%int_born%set_matrix_element &
        (term%nlo_controller%amp_born)
    end if
end subroutine term_instance_evaluate_interaction_real

<Processes: term instance: TBP>+≡
    procedure :: evaluate_interaction_real_rad => &
        term_instance_evaluate_interaction_real_rad

<Processes: procedures>+≡
    subroutine term_instance_evaluate_interaction_real_rad (term, &
        component, p_born, p_real, alpha_s, i_term)

```

```

class(term_instance_t), intent(inout) :: term
type(component_instance_t), intent(inout) :: component
type(vector4_t), intent(in), dimension(:) :: p_born, p_real
real(default), intent(in) :: alpha_s
integer, intent(in) :: i_term
integer :: i
real(default), allocatable :: alpha_qcd_forced

call term%nlo_controller%int_born%set_momenta (p_born)
call term%int_hard_real%set_momenta (p_real)
call term%nlo_controller%set_real_momenta (p_real)

call term%isolated_real%receive_kinematics ()
call term%connected_real%receive_kinematics ()

call term%connected_real%evaluate_expressions (term%passed, &
      term%scale, term%fac_scale, term%ren_scale, term%weight)

call component%core_state%reset_new_kinematics ()
select type (core => component%config%core)
type is (prc_omega_t)
  if (allocated (alpha_qcd_forced)) then
    alpha_qcd_forced = alpha_s
  else
    allocate (alpha_qcd_forced, source = alpha_s)
  end if
  do i = 1, term%config%n_allowed
    term%amp(i) = core%compute_amplitude (i_term, &
      term%int_hard_real%get_momenta (), &
      term%config%flv(i), term%config%hel(i), term%config%col(i), &
      term%fac_scale, term%ren_scale, alpha_qcd_forced, &
      component%core_state)
  end do
class is (prc_blha_t)
  call core%update_alpha_s (component%core_state, term%fac_scale)
  term%amp = 0._default
end select
call term%int_hard_real%set_matrix_element (term%amp)
call component%core_state%reset_new_kinematics ()
select type (core_sub_born => component%config%core_sub_born)
type is (prc_omega_t)
  do i = 1, term%nlo_controller%n_allowed_born
    term%nlo_controller%amp_born(i) = core_sub_born%compute_amplitude (i_term, &
      term%nlo_controller%int_born%get_momenta (), &
      term%nlo_controller%get_flv_born(i), term%nlo_controller%get_hel_born(i), &
      term%nlo_controller%get_col_born(i), term%fac_scale, term%ren_scale, &
      term%alpha_qcd_forced, component%core_state)
  end do
class is (prc_blha_t)
  term%nlo_controller%amp_born = 0._default
  call core_sub_born%update_alpha_s (component%core_state, term%fac_scale)
end select
call term%nlo_controller%int_born%set_matrix_element &
  (term%nlo_controller%amp_born)

```

```
end subroutine term_instance_evaluate_interaction_real_rad
```

```

(Processes: term instance: TBP)+≡
  procedure :: set_fac_scale => term_instance_set_fac_scale
(Processes: procedures)+≡
  subroutine term_instance_set_fac_scale (term, fac_scale)
    class(term_instance_t), intent(inout) :: term
    real(default), intent(in) :: fac_scale
    term%fac_scale = fac_scale
  end subroutine term_instance_set_fac_scale

```

Return data that might be useful for external processing. The factorization scale:

```

(Processes: term instance: TBP)+≡
  procedure :: get_fac_scale => term_instance_get_fac_scale
(Processes: procedures)+≡
  function term_instance_get_fac_scale (term) result (fac_scale)
    class(term_instance_t), intent(in) :: term
    real(default) :: fac_scale
    fac_scale = term%fac_scale
  end function term_instance_get_fac_scale

```

We take the strong coupling from the process core. The value is calculated when a new event is requested, so we should call it only after the event has been evaluated. If it is not available there (a negative number is returned), we take the value stored in the term configuration, which should be determined by the model. If the model does not provide a value, the result is zero.

```

(Processes: term instance: TBP)+≡
  procedure :: get_alpha_s => term_instance_get_alpha_s
(Processes: procedures)+≡
  function term_instance_get_alpha_s (term, component) result (alpha_s)
    class(term_instance_t), intent(in) :: term
    type(component_instance_t), dimension(:), intent(in) :: component
    real(default) :: alpha_s
    integer :: i_component
    i_component = term%config%i_component
    associate (core => component(i_component)%config%core)
      alpha_s = core%get_alpha_s (component(i_component)%core_state)
    end associate
    if (alpha_s < 0) alpha_s = term%config%alpha_s
  end function term_instance_get_alpha_s

```

MC parameter set and MCI instance

For each process component that is associated with a multi-channel integration (MCI) object, the `mci_work_t` object contains the currently active parameter set. It also holds the implementation of the `mci_instance_t` that the integrator needs for doing its work.

```
(Processes: types)+≡
```

```

type :: mci_work_t
  type(process_mci_entry_t), pointer :: config => null ()
  real(default), dimension(:), allocatable :: x
  class(mci_instance_t), pointer :: mci => null ()
  type(process_counter_t) :: counter
contains
  <Processes: mci work: TBP>
end type mci_work_t

```

First write configuration data, then the current values.

```

<Processes: mci work: TBP>≡
  procedure :: write => mci_work_write
<Processes: procedures>+≡
  subroutine mci_work_write (mci_work, unit, testflag)
    class(mci_work_t), intent(in) :: mci_work
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A,I0,A)") "Active MCI instance #", &
      mci_work%config%i_mci, " ="
    write (u, "(2x)", advance="no")
    do i = 1, mci_work%config%n_par
      write (u, "(1x,F7.5)", advance="no") mci_work%x(i)
      if (i == mci_work%config%n_par_sf) &
        write (u, "(1x,'|')", advance="no")
    end do
    write (u, *)
    if (associated (mci_work%mci)) then
      call mci_work%mci%write (u, pacify = testflag)
      call mci_work%counter%write (u)
    end if
  end subroutine mci_work_write

```

The mci component may require finalization.

```

<Processes: mci work: TBP>+≡
  procedure :: final => mci_work_final
<Processes: procedures>+≡
  subroutine mci_work_final (mci_work)
    class(mci_work_t), intent(inout) :: mci_work
    if (associated (mci_work%mci)) then
      call mci_work%mci%final ()
      deallocate (mci_work%mci)
    end if
  end subroutine mci_work_final

```

Initialize with the maximum length that we will need. Contents are not initialized.

The integrator inside the `mci_entry` object is responsible for allocating and initializing its own instance, which is referred to by a pointer in the `mci_work` object.

```

<Processes: mci work: TBP>+≡

```



```

    procedure :: init => mci_work_init
  <Processes: procedures>+≡
    subroutine mci_work_init (mci_work, mci_entry)
      class(mci_work_t), intent(out) :: mci_work
      type(process_mci_entry_t), intent(in), target :: mci_entry
      mci_work%config => mci_entry
      allocate (mci_work%x (mci_entry%n_par))
      if (allocated (mci_entry%mci)) then
        call mci_entry%mci%allocate_instance (mci_work%mci)
        call mci_work%mci%init (mci_entry%mci)
      end if
    end subroutine mci_work_init

```

Set parameters explicitly, either all at once, or separately for the structure-function and process parts.

```

  <Processes: mci work: TBP>+≡
    procedure :: set => mci_work_set
    procedure :: set_x_strfun => mci_work_set_x_strfun
    procedure :: set_x_process => mci_work_set_x_process

  <Processes: procedures>+≡
    subroutine mci_work_set (mci_work, x)
      class(mci_work_t), intent(inout) :: mci_work
      real(default), dimension(:), intent(in) :: x
      mci_work%x = x
    end subroutine mci_work_set

    subroutine mci_work_set_x_strfun (mci_work, x)
      class(mci_work_t), intent(inout) :: mci_work
      real(default), dimension(:), intent(in) :: x
      mci_work%x(1 : mci_work%config%n_par_sf) = x
    end subroutine mci_work_set_x_strfun

    subroutine mci_work_set_x_process (mci_work, x)
      class(mci_work_t), intent(inout) :: mci_work
      real(default), dimension(:), intent(in) :: x
      mci_work%x(mci_work%config%n_par_sf + 1 : mci_work%config%n_par) = x
    end subroutine mci_work_set_x_process

```

Return the array of active components, i.e., those that correspond to the currently selected MC parameter set.

```

  <Processes: mci work: TBP>+≡
    procedure :: get_active_components => mci_work_get_active_components

  <Processes: procedures>+≡
    function mci_work_get_active_components (mci_work) result (i_component)
      class(mci_work_t), intent(in) :: mci_work
      integer, dimension(:), allocatable :: i_component
      allocate (i_component (size (mci_work%config%i_component)))
      i_component = mci_work%config%i_component
    end function mci_work_get_active_components

```

Return the active parameters as a simple array with correct length. Do this separately for the structure-function parameters and the process parameters.

```

(Processes: mci work: TBP)+≡
  procedure :: get_x_strfun => mci_work_get_x_strfun
  procedure :: get_x_process => mci_work_get_x_process

(Processes: procedures)+≡
  function mci_work_get_x_strfun (mci_work) result (x)
    class(mci_work_t), intent(in) :: mci_work
    real(default), dimension(mci_work%config%n_par_sf) :: x
    x = mci_work%x(1 : mci_work%config%n_par_sf)
  end function mci_work_get_x_strfun

  function mci_work_get_x_process (mci_work) result (x)
    class(mci_work_t), intent(in) :: mci_work
    real(default), dimension(mci_work%config%n_par_phs) :: x
    x = mci_work%x(mci_work%config%n_par_sf + 1 : mci_work%config%n_par)
  end function mci_work_get_x_process

```

Initialize and finalize event generation for the specified MCI entry. This also resets the counter.

```

(Processes: mci work: TBP)+≡
  procedure :: init_simulation => mci_work_init_simulation
  procedure :: final_simulation => mci_work_final_simulation

(Processes: procedures)+≡
  subroutine mci_work_init_simulation (mci_work, safety_factor)
    class(mci_work_t), intent(inout) :: mci_work
    real(default), intent(in), optional :: safety_factor
    call mci_work%mci%init_simulation (safety_factor)
    call mci_work%counter%reset ()
  end subroutine mci_work_init_simulation

  subroutine mci_work_final_simulation (mci_work)
    class(mci_work_t), intent(inout) :: mci_work
    call mci_work%mci%final_simulation ()
  end subroutine mci_work_final_simulation

```

Counter.

```

(Processes: mci work: TBP)+≡
  procedure :: reset_counter => mci_work_reset_counter
  procedure :: record_call => mci_work_record_call
  procedure :: get_counter => mci_work_get_counter

(Processes: procedures)+≡
  subroutine mci_work_reset_counter (mci_work)
    class(mci_work_t), intent(inout) :: mci_work
    call mci_work%counter%reset ()
  end subroutine mci_work_reset_counter

  subroutine mci_work_record_call (mci_work, status)
    class(mci_work_t), intent(inout) :: mci_work
    integer, intent(in) :: status
    call mci_work%counter%record (status)
  end subroutine mci_work_record_call

```

```

end subroutine mci_work_record_call

function mci_work_get_counter (mci_work) result (counter)
  class(mci_work_t), intent(in) :: mci_work
  type(process_counter_t) :: counter
  counter = mci_work%counter
end function mci_work_get_counter

```

The process instance

A process instance contains all process data that depend on the sampling point and thus change often. In essence, it is an event record at the elementary (parton) level. We do not call it such, to avoid confusion with the actual event records. If decays are involved, the latter are compositions of several elementary processes (i.e., their instances).

We implement the process instance as an extension of the `mci_sampler_t` that we need for computing integrals and generate events.

The base type contains: the `integrand`, the `selected_channel`, the two-dimensional array `x` of parameters, and the one-dimensional array `f` of Jacobians. These subobjects are public and used for communicating with the multi-channel integrator.

The `process` pointer accesses the process of which this record is an instance. It is required whenever the calculation needs invariant configuration data, therefore the process should stay in memory for the whole lifetime of its instances.

The `evaluation_status` code is used to check the current status. In particular, failure at various stages is recorded there.

The `count` object records process evaluations, broken down according to status.

The `sqme` value is the single real number that results from evaluating and tracing the kinematics and matrix elements. This is the number that is handed over to an integration routine.

The `weight` value is the event weight. It is defined when an event has been generated from the process instance, either weighted or unweighted. The value is the `sqme` value times Jacobian weights from the integration, or unity, respectively.

The `i_mci` index chooses a subset of components that are associated with a common parameter set and integrator, i.e., that are added coherently.

The `sf_chain` subobject is a realization of the beam and structure-function configuration in the `process` object. It is not used for calculation directly but serves as the template for the sf-chain instances that are contained in the `component` objects.

The `component` subobjects determine the state of each component.

The `term` subobjects are workspace for evaluating kinematics, matrix elements, cuts etc.

The `mci_work` subobject contains the array of real input parameters (random numbers) that generates the kinematical point. It also contains the workspace for the MC integrators. The active entry of the `mci_work` array is selected by the `i_mci` index above.

(Processes: public)+≡

```

public :: process_instance_t
<Processes: types>+≡
type, extends (mci_sampler_t) :: process_instance_t
  type(process_t), pointer :: process => null ()
  integer :: evaluation_status = STAT_UNDEFINED
  real(default) :: sqme = 0
  real(default), dimension(:), allocatable :: sqme_real
  real(default) :: weight = 0
  real(default) :: excess = 0
  integer :: i_mci = 0
  integer :: selected_channel = 0
  type(sf_chain_t) :: sf_chain
  type(component_instance_t), dimension(:), allocatable :: component
  type(term_instance_t), dimension(:), allocatable :: term
  type(mci_work_t), dimension(:), allocatable :: mci_work
  type(sqme_collector_t), pointer :: sqme_collector => null()
  type(nlo_controller_t), pointer :: nlo_controller => null()
contains
  <Processes: process instance: TBP>
end type process_instance_t

```

The output routine contains a header with the most relevant information about the process, copied from `process_metadata_write`. We mark the active components by an asterisk.

The next section is the MC parameter input. The following sections are written only if the evaluation status is beyond setting the parameters, or if the `verbose` option is set.

```

<Processes: process instance: TBP>≡
  procedure :: write_header => process_instance_write_header
  procedure :: write => process_instance_write
<Processes: procedures>+≡
  subroutine process_instance_write_header (object, unit, testflag)
    class(process_instance_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag
    integer :: u, i
    u = given_output_unit (unit)
    call write_separator (u, 2)
    if (associated (object%process)) then
      associate (meta => object%process%meta)
        select case (meta%type)
          case (PRC_UNKNOWN)
            write (u, "(1x,A)") "Process instance [undefined]"
            return
          case (PRC_DECAY)
            write (u, "(1x,A)", advance="no") "Process instance [decay]:"
          case (PRC_SCATTERING)
            write (u, "(1x,A)", advance="no") "Process instance [scattering]:"
          case default
            call msg_bug ("process_instance_write: undefined process type")
        end select
      write (u, "(1x,A,A,A)") "' '", char (meta%id), "' "
    end if
  end subroutine

```

```

write (u, "(3x,A,A,A)") "Run ID = ', char (meta%run_id), "'
if (allocated (meta%component_id)) then
write (u, "(3x,A)") "Process components:"
do i = 1, size (meta%component_id)
if (object%component(i)%active) then
write (u, "(3x,'*')", advance="no")
else
write (u, "(4x)", advance="no")
end if
write (u, "(1x,I0,9A)") i, ": '", &
char (meta%component_id (i)), "' : ", &
char (meta%component_description (i))
end do
end if
end associate
else
write (u, "(1x,A)") "Process instance [undefined process]"
return
end if
write (u, "(3x,A)", advance = "no") "status = "
select case (object%evaluation_status)
case (STAT_INITIAL); write (u, "(A)") "initialized"
case (STAT_ACTIVATED); write (u, "(A)") "activated"
case (STAT_BEAM_MOMENTA); write (u, "(A)") "beam momenta set"
case (STAT_FAILED_KINEMATICS); write (u, "(A)") "failed kinematics"
case (STAT_SEED_KINEMATICS); write (u, "(A)") "seed kinematics"
case (STAT_HARD_KINEMATICS); write (u, "(A)") "hard kinematics"
case (STAT_EFF_KINEMATICS); write (u, "(A)") "effective kinematics"
case (STAT_FAILED_CUTS); write (u, "(A)") "failed cuts"
case (STAT_PASSED_CUTS); write (u, "(A)") "passed cuts"
case (STAT_EVALUATED_TRACE); write (u, "(A)") "evaluated trace"
call write_separator (u)
write (u, "(3x,A,ES19.12)") "sqme = ", object%sqme
case (STAT_EVENT_COMPLETE); write (u, "(A)") "event complete"
call write_separator (u)
write (u, "(3x,A,ES19.12)") "sqme = ", object%sqme
write (u, "(3x,A,ES19.12)") "weight = ", object%weight
if (.not. vanishes (object%excess)) &
write (u, "(3x,A,ES19.12)") "excess = ", object%excess
case default; write (u, "(A)") "undefined"
end select
if (object%i_mci /= 0) then
call write_separator (u)
call object%mc_i_work(object%i_mci)%write (u, testflag)
end if
call write_separator (u, 2)
end subroutine process_instance_write_header

subroutine process_instance_write (object, unit, testflag)
class(process_instance_t), intent(in) :: object
integer, intent(in), optional :: unit
logical, intent(in), optional :: testflag
integer :: u, i
u = given_output_unit (unit)

```

```

call object%write_header (u)
if (object%evaluation_status >= STAT_BEAM_MOMENTA) then
  call object%sf_chain%write (u)
  call write_separator (u, 2)
  if (object%evaluation_status >= STAT_SEED_KINEMATICS) then
    write (u, "(1x,A)") "Active components:"
    do i = 1, size (object%component)
      if (object%component(i)%active) then
        call write_separator (u)
        call object%component(i)%write (u, testflag)
      end if
    end do
  if (object%evaluation_status >= STAT_HARD_KINEMATICS) then
    call write_separator (u, 2)
    write (u, "(1x,A)") "Active terms:"
    if (any (object%term%active)) then
      do i = 1, size (object%term)
        if (object%term(i)%active) then
          call write_separator (u)
          call object%term(i)%write (u, &
            show_eff_state = &
            object%evaluation_status >= STAT_EFF_KINEMATICS, &
            testflag = testflag)
        end if
      end do
    end if
  end if
  call write_separator (u, 2)
end if
end if
end subroutine process_instance_write

```

Finalize all subobjects that may contain allocated pointers.

(Processes: process_instance: TBP)+≡

```

  procedure :: final => process_instance_final

```

(Processes: procedures)+≡

```

  subroutine process_instance_final (instance)
    class(process_instance_t), intent(inout) :: instance
    integer :: i
    if (allocated (instance%mc_i_work)) then
      do i = 1, size (instance%mc_i_work)
        call instance%mc_i_work(i)%final ()
      end do
    end if
    call instance%sf_chain%final ()
    if (allocated (instance%component)) then
      do i = 1, size (instance%component)
        call instance%component(i)%final ()
      end do
    end if
    if (allocated (instance%term)) then
      do i = 1, size (instance%term)
        call instance%term(i)%final ()
      end do
    end if
  end subroutine process_instance_final

```

```

        end do
    end if
    deallocate (instance%nlo_controller)
    instance%evaluation_status = STAT_UNDEFINED
end subroutine process_instance_final

```

Revert the process instance to initial state. We do not deallocate anything, just reset the state index and deactivate all components and terms.

We do not reset the choice of the MCI set `i_mci` unless this is required explicitly.

```

<Processes: process instance: TBP>+≡
    procedure :: reset => process_instance_reset

<Processes: procedures>+≡
    subroutine process_instance_reset (instance, reset_mci)
        class(process_instance_t), intent(inout) :: instance
        logical, intent(in), optional :: reset_mci
        integer :: i
        instance%component%active = .false.
        do i = 1, size (instance%term)
            call instance%term(i)%reset ()
        end do
        instance%term%checked = .false.
        instance%term%passed = .false.
        if (present (reset_mci)) then
            if (reset_mci) instance%i_mci = 0
        end if
        instance%selected_channel = 0
        instance%evaluation_status = STAT_INITIAL
    end subroutine process_instance_reset

```

Activate the components and terms that correspond to a currently selected MCI parameter set.

```

<Processes: process instance: TBP>+≡
    procedure :: activate => process_instance_activate

<Processes: procedures>+≡
    subroutine process_instance_activate (instance)
        class(process_instance_t), intent(inout) :: instance
        integer :: i, j
        associate (mci_work => instance%mci_work(instance%i_mci))
            instance%component(mci_work%get_active_components ())%active &
                = .true.
            do i = 1, size (instance%component)
                associate (component => instance%component(i))
                    if (component%active) then
                        do j = 1, size (component%config%i_term)
                            instance%term(component%config%i_term(j))%active &
                                = .true.
                        end do
                    end if
                end associate
            end do
        end associate
    end subroutine process_instance_activate

```

```

end associate
instance%evaluation_status = STAT_ACTIVATED
end subroutine process_instance_activate

```

(Processes: process instance: TBP)+≡

```

procedure :: disable_virtual_components => &
    process_instance_disable_virtual_components

```

(Processes: procedures)+≡

```

subroutine process_instance_disable_virtual_components (instance)
    class(process_instance_t), intent(inout) :: instance
    integer :: i
    if (.not. associated (instance%sqme_collector)) &
        call msg_fatal ("Sqme collector must be allocated to prepare for&
            &component selection")
    do i = 1, size (instance%component)
        associate (component => instance%component(i))
            if (component%config%component_type == COMP_VIRT) then
                component%active = .false.
                instance%term(component%config%i_term)%active = .false.
            end if
        end associate
    end do
end subroutine process_instance_disable_virtual_components

```

Initialization connects the instance with a process. All initial information is transferred from the process object. The process object contains templates for the interaction subobjects (beam and term), but no evaluators. The initialization routine creates evaluators for the matrix element trace, other evaluators are left untouched.

The **instance** object must have the **target** attribute (also in any caller) since the initialization routine assigns various pointers to subobject of **instance**.

(Processes: process instance: TBP)+≡

```

procedure :: init => process_instance_init

```

(Processes: procedures)+≡

```

subroutine process_instance_init (instance, process, cc_flag, &
    combined_integration)
    class(process_instance_t), intent(out), target :: instance
    type(process_t), intent(inout), target :: process
    logical, intent(in), optional :: cc_flag
    logical, intent(in), optional :: combined_integration
    integer :: i, i_component
    type(process_constants_t), dimension(2), save :: prc_constants
    integer :: nlo_type
    integer :: i_born, i_real
    logical :: use_internal_cc, use_internal_sc

    instance%process => process
    call instance%setup_sf_chain (process%beam_config)
    allocate (instance%mci_work (process%config%n_mci))
    do i = 1, size (instance%mci_work)
        call instance%mci_work(i)%init (process%mci_entry(i))
    end do

```



```

end do
allocate (instance%component (process%config%n_components))
allocate (instance%nlo_controller)
do i_component = 1, size (instance%component)
  if (process%component(i_component)%active) then
    associate (component => instance%component(i_component))
    call component%init (process%component(i_component))
    nlo_type = component%config%config%get_nlo_type ()
    select case (nlo_type)
    case (BORN)
      component%nlo_controller => instance%nlo_controller
      if (associated (instance%sqme_collector)) &
        call component%set_component_type (COMP_MASTER)
    case (NLO_REAL)
      component%nlo_controller => instance%nlo_controller
      i_born = component%config%config%get_associated_born ()
      call process%term(i_born)%fetch_constants (prc_constants(1))
      call process%term(i_component)%fetch_constants(prc_constants(2))
      if (present (cc_flag)) then
        use_internal_cc = cc_flag
        use_internal_sc = .false.
      else
        use_internal_cc = .true.
        use_internal_sc = .false.
      end if
      component%nlo_type = NLO_REAL
      call component%nlo_controller%set_internal_procedures &
        (use_internal_cc, use_internal_sc)
      process%component(i_component)%fks_template%id = &
        prc_constants(1)%id
      call component%nlo_controller%init (prc_constants, &
        process%component(i_component)%fks_template, &
        process%config%model)
      call component%nlo_controller%set_flv_born &
        (process%term(i_born)%flv)
      call component%nlo_controller%set_col_born &
        (process%term(i_born)%col)
      call component%nlo_controller%set_hel_born &
        (process%term(i_born)%hel)
      allocate (instance%sqme_real &
        (size (component%nlo_controller%reg_data%regions)))
      call component%nlo_controller%init_born_amps &
        (process%get_n_allowed_born (i_born))
      if (associated (instance%sqme_collector)) &
        call component%set_component_type (COMP_REAL)
    case (NLO_VIRTUAL)
      i_born = component%config%config%get_associated_born ()
      i_real = i_born + process%config%n_components / 3
      component%nlo_controller => instance%nlo_controller
      component%nlo_type = NLO_VIRTUAL
      call component%nlo_controller%init_virtual ()
      if (associated (instance%sqme_collector)) &
        call component%set_component_type (COMP_VIRT)
    case (NLO_PDF)

```

```

        i_born = component%config%config%get_associated_born ()
        component%nlo_controller => instance%nlo_controller
        component%nlo_type = NLO_PDF
        call component%nlo_controller%init_pdf_subtraction ()
        if (associated (instance%sqme_collector)) &
            call component%set_component_type (COMP_PDF)
        case (NLO_SUBTRACTION)
            component%nlo_controller => instance%nlo_controller
            component%nlo_type = NLO_SUBTRACTION
        end select
        call component%setup_kinematics &
            (instance%sf_chain, process%beam_config, &
             combined_integration)
        if (nlo_type == NLO_REAL .or. nlo_type == NLO_PDF) &
            call component%setup_fks_kinematics (process%meta%var_list)
        end associate
    end if
end do
if (associated (instance%sqme_collector)) then
    call instance%sqme_collector%setup_sqme_real &
        (instance%nlo_controller%particle_data%n_in + &
         instance%nlo_controller%particle_data%n_out_born)
end if
allocate (instance%term (process%config%n_terms))
do i = 1, size (instance%term)
    associate (term => instance%term(i))
        i_component = process%term(i)%i_component
        if (i_component /= 0) then
            associate (component => instance%component(i_component))
                nlo_type = component%config%config%get_nlo_type ()
                term%nlo_type = nlo_type
                call component%k_seed%set_nlo_info (nlo_type)

                call term%init (process%term(i), &
                    component%k_seed, &
                    process%beam_config, &
                    process%component(i_component)%core, &
                    process%meta%var_list, component%nlo_controller)
                call term%setup_expressions (process%meta, process%config)
                select case (nlo_type)
                    case (NLO_REAL)
                        call term%setup_expressions_real (process%meta, process%config)
                    end select
            end associate
        end associate
    end if
end do
if (present (combined_integration)) then
    if (combined_integration) &
        instance%sqme_collector => instance%nlo_controller%sqme_collector
end if
instance%evaluation_status = STAT_INITIAL
end subroutine process_instance_init

```

Subroutine of the initialization above: initialize the beam and structure-function chain template. We establish pointers to the configuration data, so `beam_config` must have a `target` attribute.

The resulting chain is not used directly for calculation. It will acquire instances which are stored in the process-component instance objects.

```

<Processes: process instance: TBP>+≡
  procedure :: setup_sf_chain => process_instance_setup_sf_chain

<Processes: procedures>+≡
  subroutine process_instance_setup_sf_chain (instance, config)
    class(process_instance_t), intent(inout) :: instance
    type(process_beam_config_t), intent(in), target :: config
    integer :: n_strfun
    n_strfun = config%n_strfun
    if (n_strfun /= 0) then
      call instance%sf_chain%init (config%data, config%sf)
    else
      call instance%sf_chain%init (config%data)
    end if
    if (config%sf_trace) then
      call instance%sf_chain%setup_tracing (config%sf_trace_file)
    end if
  end subroutine process_instance_setup_sf_chain

```

This initialization routine should be called only for process instances which we intend as a source for physical events. It initializes the evaluators in the parton states of the terms. They describe the (semi-)exclusive transition matrix and the distribution of color flow for the partonic process, convoluted with the beam and structure-function chain.

If the model is not provided explicitly, we may use the model instance that belongs to the process. However, an explicit model allows us to override particle settings.

```

<Processes: process instance: TBP>+≡
  procedure :: setup_event_data => process_instance_setup_event_data

<Processes: procedures>+≡
  subroutine process_instance_setup_event_data (instance, model)
    class(process_instance_t), intent(inout), target :: instance
    class(model_data_t), intent(in), optional, target :: model
    class(model_data_t), pointer :: current_model
    integer :: i, i_component
    if (present (model)) then
      current_model => model
    else
      current_model => instance%process%config%model
    end if
    do i = 1, size (instance%term)
      associate (term => instance%term(i))
        if (associated (term%config)) then
          i_component = term%config%i_component
          associate (component => instance%process%component(i_component))
            call term%setup_event_data (component%core, current_model)
          end associate
        end associate
      end do
    end subroutine process_instance_setup_event_data

```

```

        end if
    end associate
end do
end subroutine process_instance_setup_event_data

```

Choose a MC parameter set and the corresponding integrator. The choice persists beyond calls of the `reset` method above. This method is automatically called here.

```

<Processes: process instance: TBP>+=
    procedure :: choose_mci => process_instance_choose_mci

<Processes: procedures>+=
    subroutine process_instance_choose_mci (instance, i_mci)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_mci
        instance%i_mci = i_mci
        call instance%reset ()
    end subroutine process_instance_choose_mci

```

Explicitly set a MC parameter set. Works only if we are in initial state. We assume that the length of the parameter set is correct.

After setting the parameters, activate the components and terms that correspond to the chosen MC parameter set.

```

<Processes: process instance: TBP>+=
    procedure :: set_mcpair => process_instance_set_mcpair

<Processes: procedures>+=
    subroutine process_instance_set_mcpair (instance, x)
        class(process_instance_t), intent(inout) :: instance
        real(default), dimension(:), intent(in) :: x
        if (instance%evaluation_status == STAT_INITIAL) then
            associate (mci_work => instance%mci_work(instance%i_mci))
                call mci_work%set (x)
            end associate
            call instance%activate ()
        end if
    end subroutine process_instance_set_mcpair

```

Receive the beam momentum/momenta from a source interaction. This applies to a cascade decay process instance, where the ‘beam’ momentum varies event by event.

The master beam momentum array is contained in the main structure function chain subobject `sf_chain`. The sf-chain instance that reside in the components will take their beam momenta from there.

The procedure transforms the instance status into `STAT_BEAM_MOMENTA`. For process instance with fixed beam, this intermediate status is skipped.

```

<Processes: process instance: TBP>+=
    procedure :: receive_beam_momenta => process_instance_receive_beam_momenta

<Processes: procedures>+=
    subroutine process_instance_receive_beam_momenta (instance)
        class(process_instance_t), intent(inout) :: instance

```

```

        if (instance%evaluation_status >= STAT_INITIAL) then
            call instance%sf_chain%receive_beam_momenta ()
            instance%evaluation_status = STAT_BEAM_MOMENTA
        end if
    end subroutine process_instance_receive_beam_momenta

```

Set the beam momentum/momenta explicitly. Otherwise, analogous to the previous procedure.

```

<Processes: process instance: TBP>+≡
    procedure :: set_beam_momenta => process_instance_set_beam_momenta

<Processes: procedures>+≡
    subroutine process_instance_set_beam_momenta (instance, p)
        class(process_instance_t), intent(inout) :: instance
        type(vector4_t), dimension(:), intent(in) :: p
        if (instance%evaluation_status >= STAT_INITIAL) then
            call instance%sf_chain%set_beam_momenta (p)
            instance%evaluation_status = STAT_BEAM_MOMENTA
        end if
    end subroutine process_instance_set_beam_momenta

```

Recover the initial beam momenta (those in the `sf_chain` component), given a valid (recovered) `sf_chain_instance` in one of the active components. We need to do this only if the lab frame is not the c.m. frame, otherwise those beams would be fixed anyway.

```

<Processes: process instance: TBP>+≡
    procedure :: recover_beam_momenta => process_instance_recover_beam_momenta

<Processes: procedures>+≡
    subroutine process_instance_recover_beam_momenta (instance, i_term)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_term
        integer :: i
        if (.not. instance%process%beam_config%lab_is_cm_frame) then
            if (instance%evaluation_status >= STAT_EFF_KINEMATICS) then
                i = instance%term(i_term)%config%i_component
                call instance%component(i)%return_beam_momenta ()
            end if
        end if
    end subroutine process_instance_recover_beam_momenta

```

Explicitly choose MC integration channel. We assume here that the channel count is identical for all active components.

```

<Processes: process instance: TBP>+≡
    procedure :: select_channel => process_instance_select_channel

<Processes: procedures>+≡
    subroutine process_instance_select_channel (instance, channel)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: channel
        instance%selected_channel = channel
    end subroutine process_instance_select_channel

```

First step of process evaluation: set up seed kinematics. That is, for each active process component, compute a momentum array from the MC input parameters.

If `skip_term` is set, we skip the component that accesses this term. We can assume that the associated data have already been recovered, and we are just computing the rest.

```

(Processes: process instance: TBP)+≡
  procedure :: compute_seed_kinematics => &
    process_instance_compute_seed_kinematics

(Processes: procedures)+≡
  subroutine process_instance_compute_seed_kinematics (instance, skip_term)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in), optional :: skip_term
    integer :: channel, skip_component, i
    logical :: success
    channel = instance%selected_channel
    if (channel == 0) then
      call msg_bug ("Compute seed kinematics: undefined integration channel")
    end if
    if (present (skip_term)) then
      skip_component = instance%term(skip_term)%config%i_component
    else
      skip_component = 0
    end if
    if (instance%evaluation_status >= STAT_ACTIVATED) then
      success = .true.
      do i = 1, size (instance%component)
        if (i == skip_component) cycle
        if (instance%component(i)%active) then
          call instance%component(i)%compute_seed_kinematics &
            (instance%mc_i_work(instance%i_mci), channel, success)
          if (.not. success) exit
        end if
      end do
      if (success) then
        instance%evaluation_status = STAT_SEED_KINEMATICS
      else
        instance%evaluation_status = STAT_FAILED_KINEMATICS
      end if
    end if
  end subroutine process_instance_compute_seed_kinematics

```

Inverse: recover missing parts of the kinematics from the momentum configuration, which we know for a single term and component. Given a channel, reconstruct the MC parameter set.

```

(Processes: process instance: TBP)+≡
  procedure :: recover_mcpair => process_instance_recover_mcpair

(Processes: procedures)+≡
  subroutine process_instance_recover_mcpair (instance, i_term)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: i_term
    integer :: channel
    integer :: i

```

```

if (instance%evaluation_status >= STAT_EFF_KINEMATICS) then
  channel = instance%selected_channel
  if (channel == 0) then
    call msg_bug ("Recover MC parameters: undefined integration channel")
  end if
  i = instance%term(i_term)%config%i_component
  call instance%component(i)%recover_mcpair &
    (instance%mc_work(instance%i_mci), channel)
end if
end subroutine process_instance_recover_mcpair

```

Second step of process evaluation: compute all momenta, for all active components, from the seed kinematics.

```

<Processes: process instance: TBP>+=
  procedure :: compute_hard_kinematics => &
    process_instance_compute_hard_kinematics

<Processes: procedures>+=
  subroutine process_instance_compute_hard_kinematics (instance, skip_term)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in), optional :: skip_term
    integer :: i
    logical :: real_phsp
    if (instance%evaluation_status >= STAT_SEED_KINEMATICS) then
      do i = 1, size (instance%component)
        if (instance%component(i)%active) then
          select case (instance%component(i)%config%config%get_nlo_type())
            case (BORN, NLO_VIRTUAL, NLO_PDF)
              real_phsp = .false.
            case (NLO_REAL)
              real_phsp = .true.
          end select
          call instance%component(i)% &
            compute_hard_kinematics (instance%term, skip_term, real_phsp)
        end if
      end do
      instance%evaluation_status = STAT_HARD_KINEMATICS
    end if
  end subroutine process_instance_compute_hard_kinematics

```

Inverse: recover seed kinematics. We know the beam momentum configuration and the outgoing momenta of the effective interaction, for one specific term.

```

<Processes: process instance: TBP>+=
  procedure :: recover_seed_kinematics => &
    process_instance_recover_seed_kinematics

<Processes: procedures>+=
  subroutine process_instance_recover_seed_kinematics (instance, i_term)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: i_term
    if (instance%evaluation_status >= STAT_EFF_KINEMATICS) then
      associate (i_component => instance%term(i_term)%config%i_component)
        call instance%component(i_component)% &
          recover_seed_kinematics (instance%term(i_term))
      end associate
    end if
  end subroutine process_instance_recover_seed_kinematics

```

```

        end associate
    end if
end subroutine process_instance_recover_seed_kinematics

```

Third step of process evaluation: compute the effective momentum configurations, for all active terms, from the hard kinematics.

```

<Processes: process instance: TBP>+≡
    procedure :: compute_eff_kinematics => &
        process_instance_compute_eff_kinematics

<Processes: procedures>+≡
    subroutine process_instance_compute_eff_kinematics (instance, skip_term)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in), optional :: skip_term
        integer :: i
        if (instance%evaluation_status >= STAT_HARD_KINEMATICS) then
            do i = 1, size (instance%term)
                if (present (skip_term)) then
                    if (i == skip_term) cycle
                end if
                if (instance%term(i)%active) then
                    call instance%term(i)% &
                        compute_eff_kinematics (instance%component)
                end if
            end do
            instance%evaluation_status = STAT_EFF_KINEMATICS
        end if
    end subroutine process_instance_compute_eff_kinematics

```

Inverse: recover the hard kinematics from effective kinematics for one term, then compute effective kinematics for the other terms.

```

<Processes: process instance: TBP>+≡
    procedure :: recover_hard_kinematics => &
        process_instance_recover_hard_kinematics

<Processes: procedures>+≡
    subroutine process_instance_recover_hard_kinematics (instance, i_term)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_term
        integer :: i
        if (instance%evaluation_status >= STAT_EFF_KINEMATICS) then
            call instance%term(i_term)%recover_hard_kinematics (instance%component)
            do i = 1, size (instance%term)
                if (i /= i_term) then
                    if (instance%term(i)%active) then
                        call instance%term(i)% &
                            compute_eff_kinematics (instance%component)
                    end if
                end if
            end do
            instance%evaluation_status = STAT_EFF_KINEMATICS
        end if
    end subroutine process_instance_recover_hard_kinematics

```


Fourth step of process evaluation: check cuts for all terms. Where successful, compute any scales and weights. Otherwise, deactivate the term. If any of the terms has passed, set the state to STAT_PASSED_CUTS.

The argument `scale_forced`, if present, will override the scale calculation in the term expressions.

```

(Processes: process instance: TBP)+≡
  procedure :: evaluate_expressions => &
    process_instance_evaluate_expressions

(Processes: procedures)+≡
  subroutine process_instance_evaluate_expressions (instance, scale_forced)
    class(process_instance_t), intent(inout) :: instance
    real(default), intent(in), allocatable, optional :: scale_forced
    integer :: i
    if (instance%evaluation_status >= STAT_EFF_KINEMATICS) then
      do i = 1, size (instance%term)
        if (instance%term(i)%active) then
          call instance%term(i)%evaluate_expressions (scale_forced)
        end if
      end do
      if (any (instance%term%passed)) then
        instance%evaluation_status = STAT_PASSED_CUTS
      else
        instance%evaluation_status = STAT_FAILED_CUTS
      end if
    end if
  end subroutine process_instance_evaluate_expressions

```

Fifth step of process evaluation: fill the parameters for the non-selected channels, that have not been used for seeding. We should do this after evaluating cuts, since we may save some expensive calculations if the phase space point fails the cuts.

If `skip_term` is set, we skip the component that accesses this term. We can assume that the associated data have already been recovered, and we are just computing the rest.

```

(Processes: process instance: TBP)+≡
  procedure :: compute_other_channels => &
    process_instance_compute_other_channels

(Processes: procedures)+≡
  subroutine process_instance_compute_other_channels (instance, skip_term)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in), optional :: skip_term
    integer :: channel, skip_component, i
    channel = instance%selected_channel
    if (channel == 0) then
      call msg_bug ("Compute other channels: undefined integration channel")
    end if
    if (present (skip_term)) then
      skip_component = instance%term(skip_term)%config%i_component
    else
      skip_component = 0
    end if
  end subroutine process_instance_compute_other_channels

```

```

if (instance%evaluation_status >= STAT_PASSED_CUTS) then
  do i = 1, size (instance%component)
    if (i == skip_component) cycle
    if (instance%component(i)%active) then
      call instance%component(i)%compute_other_channels &
        (instance%nci_work(instance%nci), channel)
    end if
  end do
end if
end subroutine process_instance_compute_other_channels

```

Sixth step of process evaluation: evaluate the matrix elements, and compute the trace (summed over quantum numbers) for all terms. Finally, sum up the terms, iterating over all active process components.

(Processes: process instance: TBP)+≡

```

  procedure :: evaluate_trace => process_instance_evaluate_trace

```

(Processes: procedures)+≡

```

subroutine process_instance_evaluate_trace (instance)
  class(process_instance_t), intent(inout) :: instance
  integer :: i, i_real
  instance%sqme = 0
  i_real = 0
  if (instance%evaluation_status >= STAT_PASSED_CUTS) then
    do i = 1, size (instance%term)
      associate (term => instance%term(i))
        if (term%active .and. term%passed) then
          select case (term%nlo_type)
            case (NLO_REAL)
              if (.not. associated (instance%sqme_collector)) then
                call instance%evaluate_trace_real (term, i)
              else
                i_real = i
              end if
            case (BORN, NLO_VIRTUAL, NLO_PDF)
              call term%evaluate_interaction (instance%component)
              call term%evaluate_trace ()
            end select
          end if
        end associate
      end do
    do i = 1, size (instance%component)
      associate (component => instance%component(i))
        if (component%active) then
          select case (component%config%config%get_nlo_type())
            case (BORN, NLO_VIRTUAL, NLO_PDF)
              call component%evaluate_sqme (instance%term)
              instance%sqme = instance%sqme + component%sqme
              instance%evaluation_status = STAT_EVALUATED_TRACE
              associate (collector => instance%nlo_controller%sqme_collector)
                select case (component%get_component_type())
                  case (COMP_DEFAULT, COMP_MASTER)
                    collector%current_sqme_born = component%sqme
                  case (COMP_VIRT)

```

```

        collector%current_sqme_virt = component%sqme
    end select
end associate
end select
end if
end associate
end do
if (associated (instance%sqme_collector)) &
    call instance%evaluate_trace_real (instance%term(i_real), i_real)
else
    ! failed kinematics, failed cuts: set sqme to zero
    instance%sqme = 0
end if
end subroutine process_instance_evaluate_trace

```

Final step of process evaluation: evaluate the matrix elements, and compute the trace (summed over quantum numbers) for all terms. Finally, sum up the terms, iterating over all active process components.

If `weight` is provided, we already know the kinematical event weight (the MCI weight which depends on the kinematics sampling algorithm, but not on the matrix element), so we do not need to take it from the MCI record.

```

(Processes: process instance: TBP) +=
    procedure :: evaluate_event_data => process_instance_evaluate_event_data

(Processes: procedures) +=
    subroutine process_instance_evaluate_event_data (instance, weight)
        class(process_instance_t), intent(inout) :: instance
        real(default), intent(in), optional :: weight
        integer :: i
        if (instance%evaluation_status >= STAT_EVALUATED_TRACE) then
            do i = 1, size (instance%term)
                associate (term => instance%term(i))
                    if (term%active .and. term%passed) then
                        call term%evaluate_event_data ()
                    end if
                end associate
            end do
            if (present (weight)) then
                instance%weight = weight
            else
                instance%weight = &
                    instance%mci_work(instance%i_mci)%mci%get_event_weight ()
                instance%excess = &
                    instance%mci_work(instance%i_mci)%mci%get_event_excess ()
            end if
            instance%evaluation_status = STAT_EVENT_COMPLETE
        else
            ! failed kinematics etc.: set weight to zero
            instance%weight = 0
        end if
    end subroutine process_instance_evaluate_event_data

```

For the real part of the process evaluation at NLO, trace evaluation is a bit

more intricate because the phase-spaces for different emitters might be treated differently by cuts. A phase-space point is discarded if it fails the cuts for at least one emitter.

```

<Processes: process instance: TBP>+≡
  procedure :: evaluate_trace_real => process_instance_evaluate_trace_real

<Processes: procedures>+≡
  subroutine process_instance_evaluate_trace_real (instance, term, i)
    class(process_instance_t), intent(inout) :: instance
    type(term_instance_t), intent(inout) :: term
    integer, intent(in) :: i
    integer :: j, ireg
    integer :: nlegs
    real(default) :: sqme_born

    nlegs = term%nlo_controller%reg_data%nlegs_real
    ireg = 1
    instance%sqme_real = 0
    do j = 1, nlegs
      if (any (term%nlo_controller%reg_data%emitters == j)) then
        call term%nlo_controller%set_active_emitter (j)
        call term%evaluate_interaction_real (instance%component(i), i)
        if (.not. term%passed) then
          !!! Cuts failed, leave subroutine
          instance%evaluation_status = STAT_FAILED_CUTS
          instance%sqme_real = 0
          return
        end if
        call term%evaluate_trace ()
        if (instance%component(i)%active) then
          associate (component => instance%component(i))
            if (.not. associated (instance%sqme_collector)) then
              call component%evaluate_sqme_born (term)
              sqme_born = component%sqme
            else
              sqme_born = instance%sqme_collector%current_sqme_born
            end if
            call associate_sqme_born (component, sqme_born*term%weight)
            call component%evaluate_sqme_real (term)
            instance%sqme_real(ireg) = &
              component%nlo_controller%sqme_collector%current_sqme_real
            if (associated (instance%sqme_collector)) then
              instance%sqme_collector%sqme_real_per_emitter(j) = &
                instance%sqme_real(ireg)
            end if
          end associate
        end if
        ireg = ireg + 1
      end if
    end do
    instance%sqme = instance%sqme + sum (instance%sqme_real)
    if (associated (instance%sqme_collector)) &
      instance%sqme_collector%sqme_real_sum = sum (instance%sqme_real)
    instance%evaluation_status = STAT_EVALUATED_TRACE
  end subroutine

```

```

end subroutine process_instance_evaluate_trace_real

<Processes: process instance: TBP>+≡
  procedure :: evaluate_trace_real_rad => process_instance_evaluate_trace_real_rad

<Processes: procedures>+≡
  subroutine process_instance_evaluate_trace_real_rad (instance, term, i)
    class(process_instance_t), intent(inout) :: instance
    type(term_instance_t), intent(inout) :: term
    integer, intent(in) :: i
    integer :: emitter

    call term%evaluate_trace ()
    emitter = term%nlo_controller%active_emitter
    associate (component => instance%component(i), &
               collector => instance%sqme_collector)
      call component%evaluate_sqme_real (term)
      collector%sqme_real_per_emitter (emitter) = collector%current_sqme_real
    end associate
  end subroutine process_instance_evaluate_trace_real_rad

<Processes: process instance: TBP>+≡
  procedure :: compute_sqme_real_rad => process_instance_compute_sqme_real_rad

<Processes: procedures>+≡
  subroutine process_instance_compute_sqme_real_rad &
    (instance, emitter, p_born, p_real, alpha_s)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: emitter
    type(vector4_t), intent(in), dimension(:), allocatable :: p_born
    type(vector4_t), intent(in), dimension(:), allocatable :: p_real
    real(default), intent(in) :: alpha_s
    integer :: i_real

    if (.not. associated (instance%sqme_collector)) &
      call msg_fatal ("Compute radiation matrix elements: " // &
                     "Sqme collector must be allocated!")
    call instance%nlo_controller%set_active_emitter (emitter)
    call instance%nlo_controller%disable_subtraction ()
    i_real = instance%component(1)%config%config%get_associated_real ()
    associate (term => instance%term(i_real))
      call term%evaluate_interaction_real_rad (instance%component(i_real), &
        p_born, p_real, alpha_s, i_real)
      call instance%evaluate_trace_real_rad (term, i_real)
    end associate
  end subroutine process_instance_compute_sqme_real_rad

<Processes: process instance: TBP>+≡
  procedure :: get_matrix_elements => process_instance_get_matrix_elements

<Processes: procedures>+≡
  subroutine process_instance_get_matrix_elements &
    (instance, sqme_born, sqme_real)
    class(process_instance_t), intent(inout) :: instance

```

```

    real(default), intent(out) :: sqme_born, sqme_real
    integer :: emitter
    emitter = instance%nlo_controller%active_emitter
    sqme_born = instance%sqme_collector%current_sqme_born
    sqme_real = instance%sqme_collector%sqme_real_per_emitter (emitter)
end subroutine process_instance_get_matrix_elements

```

For unweighted event generation, we should reset the reported event weight to unity (signed) or zero. The latter case is appropriate for an event which failed for whatever reason.

```

<Processes: process instance: TBP>+≡
    procedure :: normalize_weight => process_instance_normalize_weight

<Processes: procedures>+≡
    subroutine process_instance_normalize_weight (instance)
        class(process_instance_t), intent(inout) :: instance
        if (.not. vanishes (instance%weight)) then
            instance%weight = sign (1._default, instance%weight)
        end if
    end subroutine process_instance_normalize_weight

```

This is a convenience routine that performs the computations of the steps 1 to 5 in a single step. The arguments are the input for `set_mcp`. After this, the evaluation status should be either `STAT_FAILED_KINEMATICS`, `STAT_FAILED_CUTS` or `STAT_EVALUATED_TRACE`.

Before calling this, we should call `choose_mci`.

```

<Processes: process instance: TBP>+≡
    procedure :: evaluate_sqme => process_instance_evaluate_sqme

<Processes: procedures>+≡
    subroutine process_instance_evaluate_sqme (instance, channel, x)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: channel
        real(default), dimension(:), intent(in) :: x
        call instance%reset ()
        call instance%set_mcp (x)
        call instance%select_channel (channel)
        call instance%compute_seed_kinematics ()
        call instance%compute_hard_kinematics ()
        call instance%compute_eff_kinematics ()
        call instance%evaluate_expressions ()
        call instance%compute_other_channels ()
        call instance%evaluate_trace ()
        if (associated (instance%sqme_collector)) &
            instance%sqme = instance%sqme_collector%get_sqme_sum ()
    end subroutine process_instance_evaluate_sqme

```

This is the inverse. Assuming that the final trace evaluator contains a valid momentum configuration, recover kinematics and recalculate the matrix elements and their trace.

To be precise, we first recover kinematics for the given term and associated component, then recalculate from that all other terms and active components.

The `channel` is not really required to obtain the matrix element, but it allows us to reconstruct the exact MC parameter set that corresponds to the given phase space point.

Before calling this, we should call `choose_mci`.

```

<Processes: process instance: TBP>+=
  procedure :: recover => process_instance_recover

<Processes: procedures>+=
  subroutine process_instance_recover &
    (instance, channel, i_term, update_sqme, scale_forced)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: channel
    integer, intent(in) :: i_term
    logical, intent(in) :: update_sqme
    real(default), intent(in), allocatable, optional :: scale_forced
    call instance%activate ()
    instance%evaluation_status = STAT_EFF_KINEMATICS
    call instance%recover_hard_kinematics (i_term)
    call instance%recover_seed_kinematics (i_term)
    call instance%select_channel (channel)
    call instance%recover_mcpair (i_term)
    call instance%recover_beam_momenta (i_term)
    call instance%compute_seed_kinematics (i_term)
    call instance%compute_hard_kinematics (i_term)
    call instance%compute_eff_kinematics (i_term)
    call instance%compute_other_channels (i_term)
    call instance%evaluate_expressions (scale_forced)
    if (update_sqme) call instance%evaluate_trace ()
  end subroutine process_instance_recover

```

The `evaluate` method is required by the `sampler_t` base type of which the process instance is an extension.

The requirement is that after the process instance is evaluated, the integrand, the selected channel, the x array, and the f Jacobian array are exposed by the `sampler_t` object.

```

<Processes: process instance: TBP>+=
  procedure :: evaluate => process_instance_evaluate

<Processes: procedures>+=
  subroutine process_instance_evaluate (sampler, c, x_in, val, x, f)
    class(process_instance_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    call sampler%evaluate_sqme (c, x_in)
    if (sampler%is_valid ()) call sampler%fetch (val, x, f)
    call sampler%record_call ()
  end subroutine process_instance_evaluate

```

The phase-space point is valid if the event has valid kinematics and has passed the cuts.

```

<Processes: process instance: TBP>+≡
  procedure :: is_valid => process_instance_is_valid

<Processes: procedures>+≡
  function process_instance_is_valid (sampler) result (valid)
    class(process_instance_t), intent(in) :: sampler
    logical :: valid
    valid = sampler%evaluation_status >= STAT_PASSED_CUTS
  end function process_instance_is_valid

```

The `rebuild` method should rebuild the kinematics section out of the `x_in` parameter set. The integrand value `val` should not be computed, but is provided as input.

```

<Processes: process instance: TBP>+≡
  procedure :: rebuild => process_instance_rebuild

<Processes: procedures>+≡
  subroutine process_instance_rebuild (sampler, c, x_in, val, x, f)
    class(process_instance_t), intent(inout) :: sampler
    integer, intent(in) :: c
    real(default), dimension(:), intent(in) :: x_in
    real(default), intent(in) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    call msg_bug ("process_instance_rebuild not implemented yet")
    x = 0
    f = 0
  end subroutine process_instance_rebuild

```

This is another method required by the `sampler_t` base type: fetch the data that are relevant for the MCI record.

```

<Processes: process instance: TBP>+≡
  procedure :: fetch => process_instance_fetch

<Processes: procedures>+≡
  subroutine process_instance_fetch (sampler, val, x, f)
    class(process_instance_t), intent(in) :: sampler
    real(default), intent(out) :: val
    real(default), dimension(:,:), intent(out) :: x
    real(default), dimension(:), intent(out) :: f
    integer :: i, cc
    integer :: n_channel
    val = 0
    FIND_COMPONENT: do i = 1, size (sampler%component)
      associate (component => sampler%component(i))
        if (component%active) then
          associate (k => component%k_seed)
            n_channel = k%n_channel
            do cc = 1, n_channel
              call k%get_mcpair (cc, x(:,cc))
            end do
            f = k%f
            val = sampler%sqme * k%phs_factor
          end associate
        end if
      end do
    end associate
  end subroutine process_instance_fetch

```



```

        exit FIND_COMPONENT
    end if
end associate
end do FIND_COMPONENT
end subroutine process_instance_fetch

```

Initialize and finalize event generation for the specified MCI entry.

```

<Processes: process instance: TBP>+≡
    procedure :: init_simulation => process_instance_init_simulation
    procedure :: final_simulation => process_instance_final_simulation

<Processes: procedures>+≡
    subroutine process_instance_init_simulation (instance, i_mci, safety_factor)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_mci
        real(default), intent(in), optional :: safety_factor
        call instance%mci_work(i_mci)%init_simulation (safety_factor)
    end subroutine process_instance_init_simulation

    subroutine process_instance_final_simulation (instance, i_mci)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: i_mci
        call instance%mci_work(i_mci)%final_simulation ()
    end subroutine process_instance_final_simulation

```

27.3.12 Accessing the process instance

Once the seed kinematics is complete, we can retrieve the MC input parameters for all channels, not just the seed channel.

Note: We choose the first active component. This makes sense only if the seed kinematics is identical for all active components.

```

<Processes: process instance: TBP>+≡
    procedure :: get_mcpair => process_instance_get_mcpair

<Processes: procedures>+≡
    subroutine process_instance_get_mcpair (instance, channel, x)
        class(process_instance_t), intent(inout) :: instance
        integer, intent(in) :: channel
        real(default), dimension(:), intent(out) :: x
        integer :: i
        if (instance%evaluation_status >= STAT_SEED_KINEMATICS) then
            do i = 1, size (instance%component)
                if (instance%component(i)%active) then
                    call instance%component(i)%k_seed%get_mcpair (channel, x)
                    return
                end if
            end do
            call msg_bug ("Process instance: get_mcpair: no active channels")
        else
            call msg_bug ("Process instance: get_mcpair: no seed kinematics")
        end if
    end subroutine process_instance_get_mcpair

```

Return true if the `sqme` value is known. This also implies that the event is kinematically valid and has passed all cuts.

```

(Processes: process instance: TBP)+≡
  procedure :: has_evaluated_trace => process_instance_has_evaluated_trace

(Processes: procedures)+≡
  function process_instance_has_evaluated_trace (instance) result (flag)
    class(process_instance_t), intent(in) :: instance
    logical :: flag
    flag = instance%evaluation_status >= STAT_EVALUATED_TRACE
  end function process_instance_has_evaluated_trace

```

Return true if the event is complete. In particular, the event must be kinematically valid, passed all cuts, and the event data have been computed.

```

(Processes: process instance: TBP)+≡
  procedure :: is_complete_event => process_instance_is_complete_event

(Processes: procedures)+≡
  function process_instance_is_complete_event (instance) result (flag)
    class(process_instance_t), intent(in) :: instance
    logical :: flag
    flag = instance%evaluation_status >= STAT_EVENT_COMPLETE
  end function process_instance_is_complete_event

```

Select a term for the process instance which is to provide the event record.

Note: this should be done using random numbers and applying probabilities for the various terms and components that belong to the selected MCI group. The current implementation simply selects the first term for the first active component.

```

(Processes: process instance: TBP)+≡
  procedure :: select_i_term => process_instance_select_i_term

(Processes: procedures)+≡
  subroutine process_instance_select_i_term (instance, i_term)
    class(process_instance_t), intent(in) :: instance
    integer, intent(out) :: i_term
    integer :: i_mci, i_component
    i_mci = instance%i_mci
    i_component = instance%process%mci_entry(i_mci)%i_component(1)
    i_term = instance%process%component(i_component)%i_term(1)
  end subroutine process_instance_select_i_term

```

Return pointer to the master beam interaction.

```

(Processes: process instance: TBP)+≡
  procedure :: get_beam_int_ptr => process_instance_get_beam_int_ptr

(Processes: procedures)+≡
  function process_instance_get_beam_int_ptr (instance) result (ptr)
    class(process_instance_t), intent(in), target :: instance
    type(interaction_t), pointer :: ptr
    ptr => instance%sf_chain%get_beam_int_ptr ()
  end function process_instance_get_beam_int_ptr

```

Return pointers to the matrix and flows interactions, given a term index.

```

(Processes: process instance: TBP)+≡
  procedure :: get_trace_int_ptr => process_instance_get_trace_int_ptr
  procedure :: get_matrix_int_ptr => process_instance_get_matrix_int_ptr
  procedure :: get_flows_int_ptr => process_instance_get_flows_int_ptr

(Processes: procedures)+≡
  function process_instance_get_trace_int_ptr (instance, i_term) result (ptr)
    class(process_instance_t), intent(in), target :: instance
    integer, intent(in) :: i_term
    type(interaction_t), pointer :: ptr
    ptr => instance%term(i_term)%connected%get_trace_int_ptr ()
  end function process_instance_get_trace_int_ptr

  function process_instance_get_matrix_int_ptr (instance, i_term) result (ptr)
    class(process_instance_t), intent(in), target :: instance
    integer, intent(in) :: i_term
    type(interaction_t), pointer :: ptr
    select case (instance%term(i_term)%nlo_type)
      case (BORN, NLO_VIRTUAL, NLO_PDF)
        ptr => instance%term(i_term)%connected%get_matrix_int_ptr ()
      case (NLO_REAL)
        ptr => instance%term(i_term)%connected_real%get_matrix_int_ptr ()
    end select
  end function process_instance_get_matrix_int_ptr

  function process_instance_get_flows_int_ptr (instance, i_term) result (ptr)
    class(process_instance_t), intent(in), target :: instance
    integer, intent(in) :: i_term
    type(interaction_t), pointer :: ptr
    select case (instance%term(i_term)%nlo_type)
      case (BORN, NLO_VIRTUAL, NLO_PDF)
        ptr => instance%term(i_term)%connected%get_flows_int_ptr ()
      case (NLO_REAL)
        ptr => instance%term(i_term)%connected_real%get_flows_int_ptr ()
    end select
  end function process_instance_get_flows_int_ptr

```

Return the complete account of flavor combinations in the underlying interaction object, including beams, radiation, and hard interaction.

```

(Processes: process instance: TBP)+≡
  procedure :: get_state_flv => process_instance_get_state_flv

(Processes: procedures)+≡
  function process_instance_get_state_flv (instance, i_term) result (state_flv)
    class(process_instance_t), intent(in) :: instance
    integer, intent(in) :: i_term
    type(state_flv_content_t) :: state_flv
    state_flv = instance%term(i_term)%connected%get_state_flv ()
  end function process_instance_get_state_flv

```

Return pointers to the parton states of a selected term.

```

(Processes: process instance: TBP)+≡

```

```

procedure :: get_isolated_state_ptr => &
    process_instance_get_isolated_state_ptr
procedure :: get_connected_state_ptr => &
    process_instance_get_connected_state_ptr
<Processes: procedures>+=
function process_instance_get_isolated_state_ptr (instance, i_term) &
    result (ptr)
    class(process_instance_t), intent(in), target :: instance
    integer, intent(in) :: i_term
    type(isolated_state_t), pointer :: ptr
    ptr => instance%term(i_term)%isolated
end function process_instance_get_isolated_state_ptr

function process_instance_get_connected_state_ptr (instance, i_term) &
    result (ptr)
    class(process_instance_t), intent(in), target :: instance
    integer, intent(in) :: i_term
    type(connected_state_t), pointer :: ptr
    ptr => instance%term(i_term)%connected
end function process_instance_get_connected_state_ptr

```

Return the indices of the beam particles and incoming partons within the currently active state matrix, respectively.

```

<Processes: process instance: TBP>+=
procedure :: get_beam_index => process_instance_get_beam_index
procedure :: get_in_index => process_instance_get_in_index
<Processes: procedures>+=
subroutine process_instance_get_beam_index (instance, i_term, i_beam)
    class(process_instance_t), intent(in) :: instance
    integer, intent(in) :: i_term
    integer, dimension(:), intent(out) :: i_beam
    call instance%term(i_term)%connected%get_beam_index (i_beam)
end subroutine process_instance_get_beam_index

subroutine process_instance_get_in_index (instance, i_term, i_in)
    class(process_instance_t), intent(in) :: instance
    integer, intent(in) :: i_term
    integer, dimension(:), intent(out) :: i_in
    call instance%term(i_term)%connected%get_in_index (i_in)
end subroutine process_instance_get_in_index

```

Return squared matrix element and event weight, and event weight excess where applicable.

```

<Processes: process instance: TBP>+=
procedure :: get_sqme => process_instance_get_sqme
procedure :: get_weight => process_instance_get_weight
procedure :: get_excess => process_instance_get_excess
<Processes: procedures>+=
function process_instance_get_sqme (instance) result (sqme)
    class(process_instance_t), intent(in) :: instance
    real(default) :: sqme

```

```

    if (instance%evaluation_status >= STAT_EVALUATED_TRACE) then
        sqme = instance%sqme
    else
        sqme = 0
    end if
end function process_instance_get_sqme

function process_instance_get_weight (instance) result (weight)
    class(process_instance_t), intent(in) :: instance
    real(default) :: weight
    if (instance%evaluation_status >= STAT_EVENT_COMPLETE) then
        weight = instance%weight
    else
        weight = 0
    end if
end function process_instance_get_weight

function process_instance_get_excess (instance) result (excess)
    class(process_instance_t), intent(in) :: instance
    real(default) :: excess
    if (instance%evaluation_status >= STAT_EVENT_COMPLETE) then
        excess = instance%excess
    else
        excess = 0
    end if
end function process_instance_get_excess

```

Return the currently selected MCI channel.

```

<Processes: process instance: TBP>+≡
    procedure :: get_channel => process_instance_get_channel

<Processes: procedures>+≡
    function process_instance_get_channel (instance) result (channel)
        class(process_instance_t), intent(in) :: instance
        integer :: channel
        channel = instance%selected_channel
    end function process_instance_get_channel

<Processes: process instance: TBP>+≡
    procedure :: set_fac_scale => process_instance_set_fac_scale

<Processes: procedures>+≡
    subroutine process_instance_set_fac_scale (instance, fac_scale)
        class(process_instance_t), intent(inout) :: instance
        real(default), intent(in) :: fac_scale
        integer :: i_term
        i_term = 1
        call instance%term(i_term)%set_fac_scale (fac_scale)
    end subroutine process_instance_set_fac_scale

```

Return factorization scale and strong coupling. We have to select a term instance.

```

<Processes: process instance: TBP>+≡

```

```

procedure :: get_fac_scale => process_instance_get_fac_scale
procedure :: get_alpha_s => process_instance_get_alpha_s

<Processes: procedures>+≡
function process_instance_get_fac_scale (instance, i_term) result (fac_scale)
  class(process_instance_t), intent(in) :: instance
  integer, intent(in) :: i_term
  real(default) :: fac_scale
  fac_scale = instance%term(i_term)%get_fac_scale ()
end function process_instance_get_fac_scale

function process_instance_get_alpha_s (instance, i_term) result (alpha_s)
  class(process_instance_t), intent(in) :: instance
  integer, intent(in) :: i_term
  real(default) :: alpha_s
  alpha_s = instance%term(i_term)%get_alpha_s (instance%component)
end function process_instance_get_alpha_s

```

Counter.

```

<Processes: process instance: TBP>+≡
procedure :: reset_counter => process_instance_reset_counter
procedure :: record_call => process_instance_record_call
procedure :: get_counter => process_instance_get_counter

<Processes: procedures>+≡
subroutine process_instance_reset_counter (process_instance)
  class(process_instance_t), intent(inout) :: process_instance
  call process_instance%mci_work(process_instance%i_mci)%reset_counter ()
end subroutine process_instance_reset_counter

subroutine process_instance_record_call (process_instance)
  class(process_instance_t), intent(inout) :: process_instance
  call process_instance%mci_work(process_instance%i_mci)%record_call &
    (process_instance%evaluation_status)
end subroutine process_instance_record_call

function process_instance_get_counter (process_instance) result (counter)
  class(process_instance_t), intent(in) :: process_instance
  type(process_counter_t) :: counter
  counter = process_instance%mci_work(process_instance%i_mci)%get_counter ()
end function process_instance_get_counter

```

27.3.13 Particle sets

Here we provide two procedures that convert the process instance from/to a particle set. The conversion applies to the trace evaluator which has no quantum-number information, thus it involves only the momenta and the parent-child relations. We keep virtual particles.

Nevertheless, it is possible to reconstruct the complete structure from a particle set. The reconstruction implies a re-evaluation of the structure function and matrix-element codes.

The `i_term` index is needed for both input and output, to select among different active trace evaluators.

In both cases, the `instance` object must be properly initialized.

NB: The `recover_beams` option should be used only when the particle set originates from an external event file, and the user has asked for it. It should be switched off when reading from raw event file.

```

(Processes: process instance: TBP)+≡
  procedure :: get_trace => process_instance_get_trace
  procedure :: set_trace => process_instance_set_trace

(Processes: procedures)+≡
  subroutine process_instance_get_trace (instance, pset, i_term)
    class(process_instance_t), intent(in), target :: instance
    type(particle_set_t), intent(out) :: pset
    integer, intent(in) :: i_term
    type(interaction_t), pointer :: int
    logical :: ok
    int => instance%get_trace_int_ptr (i_term)
    call pset%init (ok, int, int, FM_IGNORE_HELICITY, &
      [0._default, 0._default], .false., .true.)
  end subroutine process_instance_get_trace

  subroutine process_instance_set_trace &
    (instance, pset, i_term, recover_beams, check_match)
    class(process_instance_t), intent(inout), target :: instance
    type(particle_set_t), intent(in) :: pset
    integer, intent(in) :: i_term
    logical, intent(in), optional :: recover_beams, check_match
    type(interaction_t), pointer :: int
    integer :: n_in
    int => instance%get_trace_int_ptr (i_term)
    n_in = instance%process%get_n_in ()
    call pset%fill_interaction (int, n_in, &
      recover_beams = recover_beams, &
      check_match = check_match, &
      state_flg = instance%get_state_flg (i_term))
  end subroutine process_instance_set_trace

```

This procedure allows us to override any QCD setting of the WHIZARD process and directly set the coupling value that comes together with a particle set.

```

(Processes: process instance: TBP)+≡
  procedure :: set_alpha_qcd_forced => process_instance_set_alpha_qcd_forced

(Processes: procedures)+≡
  subroutine process_instance_set_alpha_qcd_forced (instance, i_term, alpha_qcd)
    class(process_instance_t), intent(inout) :: instance
    integer, intent(in) :: i_term
    real(default), intent(in) :: alpha_qcd
    call instance%term(i_term)%set_alpha_qcd_forced (alpha_qcd)
  end subroutine process_instance_set_alpha_qcd_forced

(Processes: process instance: TBP)+≡
  procedure :: display_real_kinematics => &
    process_instance_display_real_kinematics

```

```

<Processes: procedures>+≡
  subroutine process_instance_display_real_kinematics (instance, i)
    class(process_instance_t), intent(in) :: instance
    integer, intent(in) :: i
    if (associated (instance%term(i)%nlo_controller)) then
      if (instance%term(i)%nlo_controller%counter_exists) &
        call instance%term(i)%nlo_controller%counter%display ()
    end if
  end subroutine process_instance_display_real_kinematics

<Processes: process instance: TBP>+≡
  procedure :: has_nlo_component => process_instance_has_nlo_component

<Processes: procedures>+≡
  function process_instance_has_nlo_component (instance) result (nlo)
    class(process_instance_t), intent(in) :: instance
    logical :: nlo
    nlo = any (instance%component%nlo_type /= BORN)
  end function process_instance_has_nlo_component

<Processes: process instance: TBP>+≡
  procedure :: create_blha_interface => process_instance_create_blha_interface

<Processes: procedures>+≡
  subroutine process_instance_create_blha_interface (instance)
    class(process_instance_t), intent(inout) :: instance
    logical :: use_external_loops
    logical :: use_external_correlations
    logical :: use_external_real_trees
    integer :: alpha_power, alphas_power
    integer, dimension(:, :), allocatable :: flv_born, flv_real
    integer :: i
    type(blha_master_t) :: blha_master
    type(string_t) :: loop_me_method
    type(string_t) :: correlation_me_method
    type(string_t) :: real_tree_me_method

    associate (process => instance%process)
      associate (var_list => process%meta%var_list)
        loop_me_method = var_list%get_sval (var_str ("loop_me_method"))
        correlation_me_method = var_list%get_sval (var_str ("correlation_me_method"))
        real_tree_me_method = var_list%get_sval (var_str ("real_tree_me_method"))
        alpha_power = var_list%get_ival (&
                                          var_str ('alpha_power'))
        alphas_power = var_list%get_ival (&
                                          var_str ('alphas_power'))
      end associate
    end associate

    do i = 1, size (process%term)
      if (instance%component(i)%nlo_type == BORN) then
        flv_born = process%term(i)%data%flv_state
      else if (instance%component(i)%nlo_type == NLO_REAL) then
        flv_real = process%term(i)%data%flv_state
      end if
    end do
  end subroutine process_instance_create_blha_interface

```



```

use_external_loops = loop_me_method /= 'omega'
use_external_correlations = correlation_me_method /= 'omega'
use_external_real_trees = real_tree_me_method /= 'omega'

select case (char (loop_me_method))
case ('gosam')
    call blha_master%set_gosam (1)
case ('openloops')
    call blha_master%set_openloops (1)
end select
select case (char (correlation_me_method))
case ('gosam')
    call blha_master%set_gosam (2)
case ('openloops')
    call blha_master%set_openloops (2)
end select
select case (char (real_tree_me_method))
case ('gosam')
    call blha_master%set_gosam (3)
case ('openloops')
    call blha_master%set_openloops (3)
end select

call blha_master%init (process%meta%id, process%config%model, &
    2, size (flv_born,1)-2, use_external_loops, &
    use_external_correlations, use_external_real_trees, &
    alpha_power, alphas_power, &
    flv_born, flv_real)
call blha_master%generate (process%meta%id)
end associate
end subroutine process_instance_create_blha_interface

```

(Processes: process instance: TBP)+≡

```

procedure :: load_blha_libraries => process_instance_load_blha_libraries

```

(Processes: procedures)+≡

```

subroutine process_instance_load_blha_libraries (instance, os_data)
class(process_instance_t), intent(inout) :: instance
type(os_data_t), intent(in) :: os_data
type(string_t) :: libname
logical :: lib_found
integer :: i
libname = instance%process%get_library_name ()
do i = 1, size (instance%component)
    select type (core => instance%component(i)%config%core)
    type is (prc_gosam_t)
        call core%search_for_existing_library (os_data, lib_found)
        call core%create_olp_library (libname, lib_found)
        call core%load_driver (os_data, .not. lib_found)
        call core%start ()
        call core%read_contract_file (instance%process%term(i)%data%flv_state)
        call core%set_particle_properties (instance%process%config%model)
    type is (prc_openloops_t)
        call core%load_driver (os_data)

```

```

        call core%reset_parameters ()
        call core%set_bquark_mass (instance%process%config%model)
        call core%set_verbosity (3)
        call core%start ()
        call core%read_contract_file (instance%process%term(i)%data%flv_state)
        call core%set_particle_properties (instance%process%config%model)
    end select
end do
end subroutine process_instance_load_blha_libraries

```

<Processes: process instance: TBP>+≡

```

    procedure :: set_blha_constants => process_instance_set_blha_constants

```

<Processes: procedures>+≡

```

subroutine process_instance_set_blha_constants (instance, var_list)
    class(process_instance_t), intent(inout) :: instance
    type(var_list_t), intent(in), pointer :: var_list
    real(default) :: alpha
    integer :: i

    do i = 1, size (instance%component)
        select type (core => instance%component(i)%config%core)
            type is (prc_openloops_t)
                alpha = 1._default / var_list%get_rval (var_str ("alpha_em_i"))
                call core%set_alpha_qed (alpha)
            end select
        end do
    end do
end subroutine process_instance_set_blha_constants

```

The `pacify` subroutine has the purpose of setting numbers to zero which are (by comparing with a `tolerance` parameter) considered equivalent with zero. We do this in some unit tests. Here, we apply this to the phase space subobject of the process instance.

<Processes: public>+≡

```

    public :: pacify

```

<Processes: interfaces>≡

```

    interface pacify
        module procedure pacify_process_instance
    end interface pacify

```

<Processes: procedures>+≡

```

subroutine pacify_process_instance (instance)
    type(process_instance_t), intent(inout) :: instance
    integer :: i
    do i = 1, size (instance%component)
        call pacify (instance%component(i)%k_seed%phs)
    end do
end subroutine pacify_process_instance

```

<Processes: public>+≡

```

    public :: setup_nlo_component_cores

```

```

<Processes: procedures>+≡
  subroutine setup_nlo_component_cores (process)
    type(process_t), intent(inout), target :: process
    integer :: i_born, i_sub
    integer :: n_components, i_component
    integer :: nlo_type
    n_components = process%get_n_components ()
    do i_component = 1, n_components
      nlo_type = process%get_component_nlo_type (i_component)
      i_born = process%get_component_associated_born (i_component)
      i_sub = i_born + 3
      select case (nlo_type)
        case (NLO_REAL, NLO_VIRTUAL)
          associate (component => process%component (i_component))
            component%core_sub_born => process%component(i_sub)%core
          end associate
        end select
      end do
    end subroutine setup_nlo_component_cores

```

27.3.14 Unit tests

```

<Processes: public>+≡
  public :: processes_test

<Processes: tests>≡
  subroutine processes_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Processes: execute tests>
  end subroutine processes_test

```

Test process type

For the following tests, we define a simple implementation of the abstract `prc_core_t`, designed such as to complement the `prc_test_t` process definition type.

Note that it is not given that the actual process is defined as `prc_test_t` type. We enforce this by calling `prc_test_create_library`. The driver component in the process core will then become of type `prc_test_t`.

```

<Processes: public>+≡
  public :: test_t

<Processes: test types>≡
  type, extends (prc_core_t) :: test_t
  contains
    procedure :: write => test_write
    procedure :: needs_mcset => test_needs_mcset
    procedure :: get_n_terms => test_get_n_terms
    procedure :: is_allowed => test_is_allowed
    procedure :: compute_hard_kinematics => test_compute_hard_kinematics
    procedure :: compute_eff_kinematics => test_compute_eff_kinematics

```

```

        procedure :: recover_kinematics => test_recover_kinematics
        procedure :: compute_amplitude => test_compute_amplitude
    end type test_t

```

```

<Processes: tests>+≡
    subroutine test_write (object, unit)
        class(test_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(3x,A)") "test type implementing prc_test"
    end subroutine test_write

```

This process type always needs a MC parameter set and a single term. This only state is always allowed.

```

<Processes: tests>+≡
    function test_needs_mcset (object) result (flag)
        class(test_t), intent(in) :: object
        logical :: flag
        flag = .true.
    end function test_needs_mcset

    function test_get_n_terms (object) result (n)
        class(test_t), intent(in) :: object
        integer :: n
        n = 1
    end function test_get_n_terms

    function test_is_allowed (object, i_term, f, h, c) result (flag)
        class(test_t), intent(in) :: object
        integer, intent(in) :: i_term, f, h, c
        logical :: flag
        flag = .true.
    end function test_is_allowed

```

Transfer the generated momenta directly to the hard interaction in the (only) term. We assume that everything has been set up correctly, so the array fits.

```

<Processes: tests>+≡
    subroutine test_compute_hard_kinematics &
        (object, p_seed, i_term, int_hard, core_state)
        class(test_t), intent(in) :: object
        type(vector4_t), dimension(:), intent(in) :: p_seed
        integer, intent(in) :: i_term
        type(interaction_t), intent(inout) :: int_hard
        class(prc_core_state_t), intent(inout), allocatable :: core_state
        call int_hard%set_momenta (p_seed)
    end subroutine test_compute_hard_kinematics

```

This procedure is not called for test_t, just a placeholder.

```

<Processes: tests>+≡
    subroutine test_compute_eff_kinematics &
        (object, i_term, int_hard, int_eff, core_state)

```

```

class(test_t), intent(in) :: object
integer, intent(in) :: i_term
type(interaction_t), intent(in) :: int_hard
type(interaction_t), intent(inout) :: int_eff
class(prc_core_state_t), intent(inout), allocatable :: core_state
end subroutine test_compute_eff_kinematics

```

Transfer the incoming momenta of `p_seed` directly to the effective interaction, and vice versa for the outgoing momenta.

`int_hard` is left untouched since `int_eff` is an alias (via pointer) to it.

(Processes: tests)+≡

```

subroutine test_recover_kinematics &
  (object, p_seed, int_hard, int_eff, core_state)
class(test_t), intent(in) :: object
type(vector4_t), dimension(:), intent(inout) :: p_seed
type(interaction_t), intent(inout) :: int_hard
type(interaction_t), intent(inout) :: int_eff
class(prc_core_state_t), intent(inout), allocatable :: core_state
integer :: n_in
n_in = int_eff%get_n_in ()
call int_eff%set_momenta (p_seed(1:n_in), outgoing = .false.)
p_seed(n_in+1:) = int_eff%get_momenta (outgoing = .true.)
end subroutine test_recover_kinematics

```

Compute the amplitude. The driver ignores all quantum numbers and, in fact, returns a constant. Nevertheless, we properly transfer the momentum vectors.

(Processes: tests)+≡

```

function test_compute_amplitude &
  (object, j, p, f, h, c, fac_scale, ren_scale, alpha_qcd_forced, core_state) &
  result (amp)
class(test_t), intent(in) :: object
integer, intent(in) :: j
type(vector4_t), dimension(:), intent(in) :: p
integer, intent(in) :: f, h, c
real(default), intent(in) :: fac_scale, ren_scale
real(default), intent(in), allocatable :: alpha_qcd_forced
class(prc_core_state_t), intent(inout), allocatable, optional :: core_state
complex(default) :: amp
real(default), dimension(:,:), allocatable :: parray
integer :: i, n_tot
select type (driver => object%driver)
type is (prc_test_t)
  if (driver%scattering) then
    n_tot = 4
  else
    n_tot = 3
  end if
  allocate (parray (0:3,n_tot))
  forall (i = 1:n_tot) parray(:,i) = vector4_get_components (p(i))
  amp = driver%get_amplitude (parray)
end select
end function test_compute_amplitude

```

Write an empty process object

The most trivial test is to write an uninitialized process object.

```
<Processes: execute tests>≡
    call test (processes_1, "processes_1", &
               "write an empty process object", &
               u, results)

<Processes: tests>+≡
    subroutine processes_1 (u)
        integer, intent(in) :: u
        type(process_t) :: process

        write (u, "(A)")  "* Test output: processes_1"
        write (u, "(A)")  "* Purpose: display an empty process object"
        write (u, "(A)")

        call process%write (.false., u)

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: processes_1"

    end subroutine processes_1
```

Initialize a process object

Initialize a process and display it.

```
<Processes: execute tests>+≡
    call test (processes_2, "processes_2", &
               "initialize a simple process object", &
               u, results)

<Processes: tests>+≡
    subroutine processes_2 (u)
        integer, intent(in) :: u
        type(process_library_t), target :: lib
        type(string_t) :: libname
        type(string_t) :: procname
        type(string_t) :: run_id
        type(os_data_t) :: os_data
        type(qcd_t) :: qcd
        class(rng_factory_t), allocatable :: rng_factory
        class(model_data_t), pointer :: model
        type(process_t), allocatable :: process
        class(prc_core_t), allocatable :: core_template
        class(mci_t), allocatable :: mci_template
        class(phs_config_t), allocatable :: phs_config_template

        write (u, "(A)")  "* Test output: processes_2"
        write (u, "(A)")  "* Purpose: initialize a simple process object"
        write (u, "(A)")

        write (u, "(A)")  "* Build and load a test library with one process"
        write (u, "(A)")
```

```

libname = "processes2"
procname = libname
run_id = "run2"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

write (u, "(A)")  "* Initialize a process object"
write (u, "(A)")

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

call process%setup_mci ()

call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_2"

end subroutine processes_2

```

Compute a trivial matrix element

Initialize a process, retrieve some information and compute a matrix element.

We use the same trivial process as for the previous test. All momentum and state dependence is trivial, so we just test basic functionality.

```

<Processes: execute tests>+≡
  call test (processes_3, "processes_3", &
    "retrieve a trivial matrix element", &
    u, results)

<Processes: tests>+≡
  subroutine processes_3 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname

```

```

type(string_t) :: run_id
type(os_data_t) :: os_data
type(qcd_t) :: qcd
class(rng_factory_t), allocatable :: rng_factory
class(model_data_t), pointer :: model
type(process_t), allocatable :: process
class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
type(process_constants_t) :: data
type(vector4_t), dimension(:), allocatable :: p

write (u, "(A)")  "* Test output: processes_3"
write (u, "(A)")  "* Purpose: create a process &
                  &and compute a matrix element"
write (u, "(A)")

write (u, "(A)")  "* Build and load a test library with one process"
write (u, "(A)")

libname = "processes3"
procname = libname
run_id = "run3"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (mci_test_t :: mci_template)
select type (mci_template)
type is (mci_test_t)
    call mci_template%set_dimensions (2, 2)
    call mci_template%set_divisions (100)
end select
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Return the number of process components"
write (u, "(A)")

write (u, "(A,I0)")  "n_components = ", process%get_n_components ()

write (u, "(A)")
write (u, "(A)")  "* Return the number of flavor states"
write (u, "(A)")

data = process%get_constants (1)

```



```

write (u, "(A,I0)")  "n_flv(1) = ", data%n_flv

write (u, "(A)")
write (u, "(A)")  "* Return the first flavor state"
write (u, "(A)")

write (u, "(A,4(1x,I0))")  "flv_state(1) =", data%flv_state (:,1)

write (u, "(A)")
write (u, "(A)")  "* Set up kinematics &
                  &[arbitrary, the matrix element is constant]"

allocate (p (4))

write (u, "(A)")
write (u, "(A)")  "* Retrieve the matrix element"
write (u, "(A)")

write (u, "(A,F5.3,' + ',F5.3,' I')")  "me (1, p, 1, 1, 1) = ", &
    process%compute_amplitude (1, 1, p, 1, 1, 1)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_3"

end subroutine processes_3

```

Generate a process instance

Initialize a process and process instance, choose a sampling point and fill the process instance.

We use the same trivial process as for the previous test. All momentum and state dependence is trivial, so we just test basic functionality.

```

<Processes: execute tests>+≡
  call test (processes_4, "processes_4", &
    "create and fill a process instance (partonic event)", &
    u, results)

<Processes: tests>+≡
  subroutine processes_4 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data

```

```

type(qcd_t) :: qcd
class(rng_factory_t), allocatable :: rng_factory
class(model_data_t), pointer :: model
type(process_t), allocatable, target :: process
class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
real(default) :: sqrts
type(process_instance_t), allocatable, target :: process_instance
type(particle_set_t) :: pset

write (u, "(A)")  "* Test output: processes_4"
write (u, "(A)")  "*   Purpose: create a process &
                  &and fill a process instance"
write (u, "(A)")

write (u, "(A)")  "* Build and initialize a test process"
write (u, "(A)")

libname = "processes4"
procname = libname
run_id = "run4"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

call reset_interaction_counter ()

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
      (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()
call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_terms ()
call process%write (.false., u)

write (u, "(A)")

```

```

write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Inject a set of random numbers"
write (u, "(A)")

call process_instance%choose_mci (1)
call process_instance%set_mcpars ([0._default, 0._default])
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Set up hard kinematics"
write (u, "(A)")

call process_instance%select_channel (1)
call process_instance%compute_seed_kinematics ()
call process_instance%compute_hard_kinematics ()
call process_instance%compute_eff_kinematics ()
call process_instance%evaluate_expressions ()
call process_instance%compute_other_channels ()

write (u, "(A)")  "* Evaluate matrix element and square"
write (u, "(A)")

call process_instance%evaluate_trace ()
call process_instance%write (u)

call process_instance%get_trace (pset, 1)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)
call process_instance%choose_mci (1)
call process_instance%set_trace (pset, 1, check_match = .false.)

call process_instance%activate ()

```

```

process_instance%evaluation_status = STAT_EFF_KINEMATICS
call process_instance%recover_hard_kinematics (i_term = 1)
call process_instance%recover_seed_kinematics (i_term = 1)
call process_instance%select_channel (1)
call process_instance%recover_mcpair (i_term = 1)

call process_instance%compute_seed_kinematics (skip_term = 1)
call process_instance%compute_hard_kinematics (skip_term = 1)
call process_instance%compute_eff_kinematics (skip_term = 1)

call process_instance%evaluate_expressions ()
call process_instance%compute_other_channels (skip_term = 1)
call process_instance%evaluate_trace ()
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call pset%final ()
call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_4"

end subroutine processes_4

```

Structure function configuration

Configure structure functions (multi-channel) in a process object.

```

(Processes: execute tests) +=
  call test (processes_7, "processes_7", &
    "process configuration with structure functions", &
    u, results)

(Processes: tests) +=
  subroutine processes_7 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    class(model_data_t), pointer :: model
    type(process_t), allocatable, target :: process
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template

```

```

real(default) :: sqrts
type(pdg_array_t) :: pdg_in
class(sf_data_t), allocatable, target :: data
type(sf_config_t), dimension(:), allocatable :: sf_config
type(sf_channel_t), dimension(2) :: sf_channel

write (u, "(A)")  "* Test output: processes_7"
write (u, "(A)")  "* Purpose: initialize a process with &
                  &structure functions"
write (u, "(A)")

write (u, "(A)")  "* Build and initialize a process object"
write (u, "(A)")

libname = "processes7"
procname = libname
run_id = "run7"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Set beam, structure functions, and mappings"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()

pdg_in = 25
allocate (sf_test_data_t :: data)
select type (data)
type is (sf_test_data_t)
    model => process%get_model_ptr ()
    call data%init (model, pdg_in)
end select

allocate (sf_config (2))
call sf_config(1)%init ([1], data)
call sf_config(2)%init ([2], data)
call process%init_sf_chain (sf_config)
deallocate (sf_config)

call process%beam_config%allocate_sf_channels (3)

```

```

call sf_channel(1)%init (2)
call sf_channel(1)%activate_mapping ([1,2])
call process%set_sf_channel (2, sf_channel(1))

call sf_channel(2)%init (2)
call sf_channel(2)%set_s_mapping ([1,2])
call process%set_sf_channel (3, sf_channel(2))

call process%setup_mci ()

call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_7"

end subroutine processes_7

```

Evaluating a process with structure function

Configure structure functions (single-channel) in a process object, create an instance, compute kinematics and evaluate.

Note the order of operations when setting up structure functions and phase space. The beams are first, they determine the `sqrts` value. We can also set up the chain of structure functions. We then configure the phase space. From this, we can obtain information about special configurations (resonances, etc.), which we need for allocating the possible structure-function channels (parameterizations and mappings). Finally, we match phase-space channels onto structure-function channels.

In the current example, this matching is trivial; we only have one structure-function channel.

```

<Processes: execute tests>+≡
  call test (processes_8, "processes_8", &
    "process evaluation with structure functions", &
    u, results)

<Processes: tests>+≡
  subroutine processes_8 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory

```

```

class(model_data_t), pointer :: model
type(process_t), allocatable, target :: process
class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
real(default) :: sqrts
type(process_instance_t), allocatable, target :: process_instance
type(pdg_array_t) :: pdg_in
class(sf_data_t), allocatable, target :: data
type(sf_config_t), dimension(:), allocatable :: sf_config
type(sf_channel_t) :: sf_channel
type(particle_set_t) :: pset

write (u, "(A)")  "* Test output: processes_8"
write (u, "(A)")  "*   Purpose: evaluate a process with &
                  &structure functions"
write (u, "(A)")

write (u, "(A)")  "* Build and initialize a process object"
write (u, "(A)")

libname = "processes8"
procname = libname
run_id = "run8"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

call reset_interaction_counter ()

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Set beam, structure functions, and mappings"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)

pdg_in = 25
allocate (sf_test_data_t :: data)
select type (data)
type is (sf_test_data_t)
    model => process%get_model_ptr ()
    call data%init (model, pdg_in)
end select

```

```

allocate (sf_config (2))
call sf_config(1)%init ([1], data)
call sf_config(2)%init ([2], data)
call process%init_sf_chain (sf_config)
deallocate (sf_config)

call process%configure_phs ()

call process%beam_config%allocate_sf_channels (1)

call sf_channel%init (2)
call sf_channel%activate_mapping ([1,2])
call process%set_sf_channel (1, sf_channel)

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_mci ()
call process%setup_terms ()

call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)

write (u, "(A)")  "* Set up kinematics and evaluate"
write (u, "(A)")

call process_instance%choose_mci (1)
call process_instance%evaluate_sqme (1, &
    [0.8_default, 0.8_default, 0.1_default, 0.2_default])
call process_instance%write (u)

call process_instance%get_trace (pset, 1)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover process instance"
write (u, "(A)")

```



```

call reset_interaction_counter (2)

allocate (process_instance)
call process_instance%init (process)

call process_instance%choose_mci (1)
call process_instance%set_trace (pset, 1, check_match = .false.)
call process_instance%recover &
    (channel = 1, i_term = 1, update_sqme = .true.)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call pset%final ()

call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_8"

end subroutine processes_8

```

Multi-channel phase space and structure function

This is an extension of the previous example. This time, we have two distinct structure-function channels which are matched to the two distinct phase-space channels.

```

<Processes: execute tests>+≡
call test (processes_9, "processes_9", &
    "multichannel kinematics and structure functions", &
    u, results)

<Processes: tests>+≡
subroutine processes_9 (u)
integer, intent(in) :: u
type(process_library_t), target :: lib
type(string_t) :: libname
type(string_t) :: procname
type(string_t) :: run_id
type(os_data_t) :: os_data
type(qcd_t) :: qcd
class(rng_factory_t), allocatable :: rng_factory
class(model_data_t), pointer :: model
type(process_t), allocatable, target :: process
class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
real(default) :: sqrts

```

```

type(process_instance_t), allocatable, target :: process_instance
type(pdg_array_t) :: pdg_in
class(sf_data_t), allocatable, target :: data
type(sf_config_t), dimension(:), allocatable :: sf_config
type(sf_channel_t) :: sf_channel
real(default), dimension(4) :: x_saved
type(particle_set_t) :: pset

write (u, "(A)")  "* Test output: processes_9"
write (u, "(A)")  "*   Purpose: evaluate a process with &
                  &structure functions"
write (u, "(A)")  "*               in a multi-channel configuration"
write (u, "(A)")

write (u, "(A)")  "* Build and initialize a process object"
write (u, "(A)")

libname = "processes9"
procname = libname
run_id = "run9"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

call reset_interaction_counter ()

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
      (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Set beam, structure functions, and mappings"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)

pdg_in = 25
allocate (sf_test_data_t :: data)
select type (data)
type is (sf_test_data_t)
      model => process%get_model_ptr ()
      call data%init (model, pdg_in)
end select

allocate (sf_config (2))
call sf_config(1)%init ([1], data)
call sf_config(2)%init ([2], data)

```

```

call process%init_sf_chain (sf_config)
deallocate (sf_config)

call process%configure_phs ()

call process%beam_config%allocate_sf_channels (2)

call sf_channel%init (2)
call process%set_sf_channel (1, sf_channel)

call sf_channel%init (2)
call sf_channel%activate_mapping ([1,2])
call process%set_sf_channel (2, sf_channel)

call process%component(1)%phs_config%set_sf_channel ([1, 2])

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_mci ()
call process%setup_terms ()

call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)

write (u, "(A)")  "* Set up kinematics in channel 1 and evaluate"
write (u, "(A)")

call process_instance%choose_mci (1)
call process_instance%evaluate_sqme (1, &
    [0.8_default, 0.8_default, 0.1_default, 0.2_default])
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Extract MC input parameters"
write (u, "(A)")

write (u, "(A)")  "Channel 1:"
call process_instance%get_mcpair (1, x_saved)
write (u, "(2x,9(1x,F7.5))") x_saved

write (u, "(A)")  "Channel 2:"
call process_instance%get_mcpair (2, x_saved)
write (u, "(2x,9(1x,F7.5))") x_saved

write (u, "(A)")
write (u, "(A)")  "* Set up kinematics in channel 2 and evaluate"
write (u, "(A)")

```

```

call process_instance%evaluate_sqme (2, x_saved)
call process_instance%write (u)

call process_instance%get_trace (pset, 1)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Recover process instance for channel 2"
write (u, "(A)")

call reset_interaction_counter (2)

allocate (process_instance)
call process_instance%init (process)

call process_instance%choose_mci (1)
call process_instance%set_trace (pset, 1, check_match = .false.)
call process_instance%recover &
    (channel = 2, i_term = 1, update_sqme = .true.)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call pset%final ()

call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_9"

end subroutine processes_9

```

Event generation

Activate the MC integrator for the process object and use it to generate a single event. Note that the test integrator does not require integration in preparation for generating events.

```

<Processes: execute tests>+≡
    call test (processes_10, "processes_10", &
        "event generation", &
        u, results)

<Processes: tests>+≡
    subroutine processes_10 (u)
        integer, intent(in) :: u
        type(process_library_t), target :: lib

```

```

type(string_t) :: libname
type(string_t) :: procname
type(string_t) :: run_id
type(os_data_t) :: os_data
type(qcd_t) :: qcd
class(rng_factory_t), allocatable :: rng_factory
class(model_data_t), pointer :: model
type(process_t), allocatable, target :: process
class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
real(default) :: sqrts
type(process_instance_t), allocatable, target :: process_instance

write (u, "(A)")  "* Test output: processes_10"
write (u, "(A)")  "*   Purpose: generate events for a process without &
                    &structure functions"
write (u, "(A)")  "*               in a multi-channel configuration"
write (u, "(A)")

write (u, "(A)")  "* Build and initialize a process object"
write (u, "(A)")

libname = "processes10"
procname = libname
run_id = "run10"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

call reset_interaction_counter ()

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (mci_test_t :: mci_template)
select type (mci_template)
type is (mci_test_t); call mci_template%set_divisions (100)
end select
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()

```

```

call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_terms ()
call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)

write (u, "(A)")  "* Generate weighted event"
write (u, "(A)")

select type (mci => process%mci_entry(1)%mci)
type is (mci_test_t)
    ! This ensures that the next 'random' numbers are 0.3, 0.5, 0.7
    call mci%rng%init (3)
    ! Include the constant PHS factor in the stored maximum of the integrand
    call mci%set_max_factor (conv * twopi4 &
        / (2 * sqrt (lambda (sqrt2 **2, 125._default**2, 125._default**2))))
end select

call process%generate_weighted_event (process_instance, 1)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate unweighted event"
write (u, "(A)")

call process%generate_unweighted_event (process_instance, 1)
select type (mci => process%mci_entry(1)%mci)
type is (mci_test_t)
    write (u, "(A,I0)")  " Success in try ", mci%tries
    write (u, "(A)")
end select

call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_10"

```

```
end subroutine processes_10
```

Integration

Activate the MC integrator for the process object and use it to integrate over phase space.

```
<Processes: execute tests>+≡
  call test (processes_11, "processes_11", &
    "integration", &
    u, results)

<Processes: tests>+≡
  subroutine processes_11 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    class(model_data_t), pointer :: model
    type(process_t), allocatable, target :: process
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    real(default) :: sqrts
    type(process_instance_t), allocatable, target :: process_instance

    write (u, "(A)")  "* Test output: processes_11"
    write (u, "(A)")  "* Purpose: integrate a process without &
      &structure functions"
    write (u, "(A)")  "*           in a multi-channel configuration"
    write (u, "(A)")

    write (u, "(A)")  "* Build and initialize a process object"
    write (u, "(A)")

    libname = "processes11"
    procname = libname
    run_id = "run11"
    call os_data_init (os_data)
    allocate (rng_test_factory_t :: rng_factory)
    call prc_test_create_library (libname, lib)

    call reset_interaction_counter ()

    allocate (model)
    call model%init_test ()

    allocate (process)
    call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)
```

```

allocate (test_t :: core_template)
allocate (mci_test_t :: mci_template)
select type (mci_template)
type is (mci_test_t)
    call mci_template%set_divisions (100)
end select
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

sqrt_s = 1000
call process%setup_beams_sqrt_s (sqrt_s)
call process%configure_phs ()

call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_terms ()
call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)

write (u, "(A)")  "* Integrate with default test parameters"
write (u, "(A)")

call process%integrate (process_instance, 1, n_it=1, n_calls=10000)
call process%final_integration (1)

call process%write (.false., u)

write (u, "(A)")
write (u, "(A,ES13.7)")  " Integral divided by phs factor = ", &
    process%get_integral (1) &
    / process_instance%component(1)%k_seed%phs_factor

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

```



```

write (u, "(A)")
write (u, "(A)")  "*" Test output end: processes_11"

end subroutine processes_11

```

Complete events

For the purpose of simplifying further tests, we implement a convenience routine that initializes a process and prepares a single event. This is a wrapup of the test `processes_10`.

```

<Processes: public>+≡
  public :: prepare_test_process

<Processes: procedures>+≡
  subroutine prepare_test_process (process, process_instance, model)
    type(process_t), intent(out), target :: process
    type(process_instance_t), intent(out), target :: process_instance
    class(model_data_t), intent(in), target :: model
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    class(model_data_t), pointer :: process_model
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    real(default) :: sqrts
    libname = "processes_test"
    procname = libname
    run_id = "run_test"
    call os_data_init (os_data)
    allocate (rng_test_factory_t :: rng_factory)
    call prc_test_create_library (libname, lib)
    call reset_interaction_counter ()
    allocate (process_model)
    call process_model%init (model%get_name (), &
      model%get_n_real (), &
      model%get_n_complex (), &
      model%get_n_field (), &
      model%get_n_vtx ())
    call process_model%copy_from (model)
    call process%init (procname, run_id, &
      lib, os_data, qcd, rng_factory, process_model)
    allocate (test_t :: core_template)
    allocate (mci_test_t :: mci_template)
    select type (mci_template)
    type is (mci_test_t); call mci_template%set_divisions (100)
    end select
    allocate (phs_test_config_t :: phs_config_template)

```

```

call process%init_component &
    (1, core_template, mci_template, phs_config_template)
sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()
call process%setup_mci ()
call process%setup_terms ()
call process_instance%init (process)
select type (mci => process%mci_entry(1)%mci)
type is (mci_test_t)
    ! This ensures that the next 'random' numbers are 0.3, 0.5, 0.7
    call mci%rng%init (3)
    ! Include the constant PHS factor in the stored maximum of the integrand
    call mci%set_max_factor (conv * twopi4 &
        / (2 * sqrt (lambda (sqrts **2, 125._default**2, 125._default**2))))
end select
end subroutine prepare_test_process

```

Here we do the cleanup of the process and process instance emitted by the previous routine.

```

<Processes: public>+≡
    public :: cleanup_test_process

<Processes: procedures>+≡
    subroutine cleanup_test_process (process, process_instance)
        type(process_t), intent(inout) :: process
        type(process_instance_t), intent(inout) :: process_instance
        call process_instance%final ()
        call process%final ()
    end subroutine cleanup_test_process

```

This is the actual test. Prepare the test process and event, fill all evaluators, and display the results. Use a particle set as temporary storage, read kinematics and recalculate the event.

```

<Processes: execute tests>+≡
    call test (processes_12, "processes_12", &
        "event post-processing", &
        u, results)

<Processes: tests>+≡
    subroutine processes_12 (u)
        integer, intent(in) :: u
        type(process_t), allocatable, target :: process
        type(process_instance_t), allocatable, target :: process_instance
        type(particle_set_t) :: pset
        type(model_data_t), target :: model

        write (u, "(A)")  "* Test output: processes_12"
        write (u, "(A)")  "* Purpose: generate a complete partonic event"
        write (u, "(A)")

        call model%init_test ()

        write (u, "(A)")  "* Build and initialize process and process instance &

```

```

        &and generate event"
write (u, "(A)")

allocate (process)
allocate (process_instance)
call prepare_test_process (process, process_instance, model)
call process_instance%setup_event_data ()

call process%prepare_simulation (1)
call process_instance%init_simulation (1)
call process%generate_weighted_event (process_instance, 1)
call process_instance%evaluate_event_data ()

call process_instance%write (u)

call process_instance%get_trace (pset, 1)

call process_instance%final_simulation (1)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Recover kinematics and recalculate"
write (u, "(A)")

call reset_interaction_counter (2)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()

call process_instance%choose_mci (1)
call process_instance%set_trace (pset, 1, check_match = .false.)
call process_instance%recover &
    (channel = 1, i_term = 1, update_sqme = .true.)

call process%recover_event (process_instance, 1)
call process_instance%evaluate_event_data ()

call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_12"

```

```
end subroutine processes_12
```

Colored interaction

This test specifically checks the transformation of process data (flavor, helicity, and color) into an interaction in a process term.

We use the `test_t` process core (which has no nontrivial particles), but call only the `is_allowed` method, which always returns true.

```
<Processes: execute tests>+≡
  call test (processes_13, "processes_13", &
    "colored interaction", &
    u, results)

<Processes: tests>+≡
  subroutine processes_13 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(model_data_t), target :: model
    type(process_term_t) :: term
    class(prc_core_t), allocatable :: core

    write (u, "(A)")  "* Test output: processes_13"
    write (u, "(A)")  "* Purpose: initialized a colored interaction"
    write (u, "(A)")

    write (u, "(A)")  "* Set up a process constants block"
    write (u, "(A)")

    call os_data_init (os_data)
    call model%init_sm_test ()
!   call model_list%read_model (var_str ("QCD"), var_str ("QCD.mdl"), &
!     os_data, model)
    allocate (test_t :: core)

    associate (data => term%data)
      data%n_in = 2
      data%n_out = 3
      data%n_flv = 2
      data%n_hel = 2
      data%n_col = 2
      data%n_cin = 2

      allocate (data%flv_state (5, 2))
      data%flv_state (:,1) = [ 1, 21, 1, 21, 21]
      data%flv_state (:,2) = [ 2, 21, 2, 21, 21]

      allocate (data%hel_state (5, 2))
      data%hel_state (:,1) = [1, 1, 1, 1, 0]
      data%hel_state (:,2) = [1,-1, 1,-1, 0]

      allocate (data%col_state (2, 5, 2))
      data%col_state (:,:,1) = &
        reshape ([1, 0], [2,-1], [3, 0], [2,-3], [0,0]), [2,5])
```

```

data%col_state (:,:,2) = &
    reshape ([1, 0], [2,-3], [3, 0], [2,-1], [0,0], [2,5])

allocate (data%ghost_flag (5, 2))
data%ghost_flag(1:4,:) = .false.
data%ghost_flag(5,:) = .true.

end associate

write (u, "(A)")  "* Set up the interaction"
write (u, "(A)")

call reset_interaction_counter ()
call term%setup_interaction (core, model)
call term%int%basic_write (u)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_13"
end subroutine processes_13

```

MD5 sums

Configure a process with structure functions (multi-channel) and compute MD5 sums

```

<Processes: execute tests>+≡
    call test (processes_14, "processes_14", &
        "process configuration and MD5 sum", &
        u, results)

<Processes: tests>+≡
    subroutine processes_14 (u)
        integer, intent(in) :: u
        type(process_library_t), target :: lib
        type(string_t) :: libname
        type(string_t) :: procname
        type(string_t) :: run_id
        type(os_data_t) :: os_data
        type(qcd_t) :: qcd
        class(rng_factory_t), allocatable :: rng_factory
        class(model_data_t), pointer :: model
        type(process_t), allocatable, target :: process
        class(prc_core_t), allocatable :: core_template
        class(mci_t), allocatable :: mci_template
        class(phs_config_t), allocatable :: phs_config_template
        real(default) :: sqrts
        type(pdg_array_t) :: pdg_in
        class(sf_data_t), allocatable, target :: data
        type(sf_config_t), dimension(:), allocatable :: sf_config
        type(sf_channel_t), dimension(3) :: sf_channel

        write (u, "(A)")  "* Test output: processes_14"
    end subroutine

```

```

write (u, "(A)")  "*   Purpose: initialize a process with &
                    &structure functions"
write (u, "(A)")  "*               and compute MD5 sum"
write (u, "(A)")

write (u, "(A)")  "* Build and initialize a process object"
write (u, "(A)")

libname = "processes7"
procname = libname
run_id = "run7"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)
call lib%compute_md5sum ()

allocate (model)
call model%init_test ()

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Set beam, structure functions, and mappings"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()

pdg_in = 25
allocate (sf_test_data_t :: data)
select type (data)
type is (sf_test_data_t)
    model => process%get_model_ptr ()
    call data%init (model, pdg_in)
end select

call process%beam_config%allocate_sf_channels (3)

allocate (sf_config (2))
call sf_config(1)%init ([1], data)
call sf_config(2)%init ([2], data)
call process%init_sf_chain (sf_config)
deallocate (sf_config)

call sf_channel(1)%init (2)
call process%set_sf_channel (1, sf_channel(1))

call sf_channel(2)%init (2)

```

```

call sf_channel(2)%activate_mapping ([1,2])
call process%set_sf_channel (2, sf_channel(2))

call sf_channel(3)%init (2)
call sf_channel(3)%set_s_mapping ([1,2])
call process%set_sf_channel (3, sf_channel(3))

call process%setup_mci ()

call process%compute_md5sum ()

call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_14"

end subroutine processes_14

```

Decay Process Evaluation

Initialize and evaluate a decay process.

```

(Processes: execute tests) +=
  call test (processes_15, "processes_15", &
    "decay process", &
    u, results)

(Processes: tests) +=
  subroutine processes_15 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    class(model_data_t), pointer :: model
    type(process_t), allocatable, target :: process
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    type(process_instance_t), allocatable, target :: process_instance
    type(particle_set_t) :: pset

    write (u, "(A)")  "* Test output: processes_15"
    write (u, "(A)")  "* Purpose: initialize a decay process object"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Build and load a test library with one process"
write (u, "(A)")

libname = "processes15"
procname = libname
run_id = "run15"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib, scattering = .false., &
    decay = .true.)

allocate (model)
call model%init_test ()
call model%set_par (var_str ("ff"), 0.4_default)
call model%set_par (var_str ("mf"), &
    model%get_real (var_str ("ff")) * model%get_real (var_str ("ms")))

write (u, "(A)")  "* Initialize a process object"
write (u, "(A)")

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_single_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

call process%setup_beams_decay ()
call process%configure_phs ()
call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_terms ()
call process%write(.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

call reset_interaction_counter (3)

allocate (process_instance)
call process_instance%init (process)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Inject a set of random numbers"

```



```

write (u, "(A)")

call process_instance%choose_mci (1)
call process_instance%set_mcpair ([0._default, 0._default])
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Set up hard kinematics"
write (u, "(A)")

call process_instance%select_channel (1)
call process_instance%compute_seed_kinematics ()
call process_instance%compute_hard_kinematics ()

write (u, "(A)")  "* Evaluate matrix element and square"
write (u, "(A)")

call process_instance%compute_eff_kinematics ()
call process_instance%evaluate_expressions ()
call process_instance%compute_other_channels ()
call process_instance%evaluate_trace ()
call process_instance%write (u)

call process_instance%get_trace (pset, 1)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover process instance"
write (u, "(A)")

call reset_interaction_counter (3)

allocate (process_instance)
call process_instance%init (process)
call process_instance%choose_mci (1)
call process_instance%set_trace (pset, 1, check_match = .false.)
call process_instance%recover (1, 1, .true.)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call pset%final ()
call process_instance%final ()
deallocate (process_instance)

```

```

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_15"

end subroutine processes_15

```

Integration: decay

Activate the MC integrator for the decay object and use it to integrate over phase space.

```

<Processes: execute tests>+≡
  call test (processes_16, "processes_16", &
    "decay integration", &
    u, results)

<Processes: tests>+≡
  subroutine processes_16 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    class(model_data_t), pointer :: model
    type(process_t), allocatable, target :: process
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    type(process_instance_t), allocatable, target :: process_instance

    write (u, "(A)")  "* Test output: processes_16"
    write (u, "(A)")  "* Purpose: integrate a process without &
      &structure functions"
    write (u, "(A)")  "*           in a multi-channel configuration"
    write (u, "(A)")

    write (u, "(A)")  "* Build and initialize a process object"
    write (u, "(A)")

    libname = "processes16"
    procname = libname
    run_id = "run16"
    call os_data_init (os_data)
    allocate (rng_test_factory_t :: rng_factory)
    call prc_test_create_library (libname, lib, scattering = .false., &
      decay = .true.)

    call reset_interaction_counter ()

```

```

allocate (model)
call model%init_test ()
call model%set_par (var_str ("ff"), 0.4_default)
call model%set_par (var_str ("mf"), &
    model%get_real (var_str ("ff")) * model%get_real (var_str ("ms")))

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (mci_midpoint_t :: mci_template)
allocate (phs_single_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

call process%setup_beams_decay ()
call process%configure_phs ()

call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_terms ()
call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)

write (u, "(A)")  "* Integrate with default test parameters"
write (u, "(A)")

call process%integrate (process_instance, 1, n_it=1, n_calls=10000)
call process%final_integration (1)

call process%write (.false., u)

write (u, "(A)")
write (u, "(A,ES13.7)")  " Integral divided by phs factor = ", &
    process%get_integral (1) &
    / process_instance%component(1)%k_seed%phs_factor

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process_instance%final ()

```

```

deallocate (process_instance)

call process%final ()
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_16"

end subroutine processes_16

```

Decay Process Evaluation

Initialize and evaluate a decay process for a moving particle.

```

<Processes: execute tests>+≡
  call test (processes_17, "processes_17", &
    "decay of moving particle", &
    u, results)

<Processes: tests>+≡
  subroutine processes_17 (u)
    integer, intent(in) :: u
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    class(model_data_t), pointer :: model
    type(process_t), allocatable, target :: process
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    type(process_instance_t), allocatable, target :: process_instance
    type(particle_set_t) :: pset
    type(flavor_t) :: flv_beam
    real(default) :: m, p, E

    write (u, "(A)")  "* Test output: processes_17"
    write (u, "(A)")  "* Purpose: initialize a decay process object"
    write (u, "(A)")

    write (u, "(A)")  "* Build and load a test library with one process"
    write (u, "(A)")

    libname = "processes17"
    procname = libname
    run_id = "run17"
    call os_data_init (os_data)
    allocate (rng_test_factory_t :: rng_factory)

    call prc_test_create_library (libname, lib, scattering = .false., &
      decay = .true.)

```

```

write (u, "(A)")  "* Initialize a process object"
write (u, "(A)")

allocate (model)
call model%init_test ()
call model%set_par (var_str ("ff"), 0.4_default)
call model%set_par (var_str ("mf"), &
    model%get_real (var_str ("ff")) * model%get_real (var_str ("ms")))

allocate (process)
call process%init (procname, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (phs_single_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

call process%setup_beams_decay (rest_frame = .false.)
call process%configure_phs ()
call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization"
write (u, "(A)")

call process%setup_terms ()
call process%write (.false., u)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

call reset_interaction_counter (3)

allocate (process_instance)
call process_instance%init (process)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Set parent momentum and random numbers"
write (u, "(A)")

call process_instance%choose_mci (1)
call process_instance%set_mcpair ([0._default, 0._default])

model => process%get_model_ptr ()
call flv_beam%init (25, model)
m = flv_beam%get_mass ()
p = 3 * m / 4
E = sqrt (m**2 + p**2)
call process_instance%set_beam_momenta ([vector4_moving (E, p, 3)])

```

```

call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Set up hard kinematics"
write (u, "(A)")

call process_instance%select_channel (1)
call process_instance%compute_seed_kinematics ()
call process_instance%compute_hard_kinematics ()

write (u, "(A)")  "* Evaluate matrix element and square"
write (u, "(A)")

call process_instance%compute_eff_kinematics ()
call process_instance%evaluate_expressions ()
call process_instance%compute_other_channels ()
call process_instance%evaluate_trace ()
call process_instance%write (u)

call process_instance%get_trace (pset, 1)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Particle content:"
write (u, "(A)")

call write_separator (u)
call pset%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Recover process instance"
write (u, "(A)")

call reset_interaction_counter (3)

allocate (process_instance)
call process_instance%init (process)

call process_instance%choose_mci (1)
call process_instance%set_trace (pset, 1, check_match = .false.)
call process_instance%recover (1, 1, .true.)
call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call pset%final ()
call process_instance%final ()
deallocate (process_instance)

call process%final ()

```

```

deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_17"

end subroutine processes_17

```

27.4 Process Stacks

For storing and handling multiple processes, we define process stacks. These are ordinary stacks where new process entries are pushed onto the top. We allow for multiple entries with identical process ID, but distinct run ID.

The implementation is essentially identical to the `prclib_stacks` module above. Unfortunately, Fortran supports no generic programming, so we do not make use of this fact.

When searching for a specific process ID, we will get (a pointer to) the top-most process entry with that ID on the stack, which was entered last. Usually, this is the best version of the process (in terms of integral, etc.) Thus the stack terminology makes sense.

```

<process_stacks.f90>≡
  <File header>

  module process_stacks

    <Use strings>
    use io_units
    use format_utils, only: write_separator
    use unit_tests
    use diagnostics
    use os_interface
    use sm_qcd
    use model_data
    use rng_base
    use variables
    use observables
    use process_libraries
    use prc_test
    use processes

    <Standard module head>

    <Process stacks: public>

    <Process stacks: types>

    contains

    <Process stacks: procedures>

    <Process stacks: tests>

```

```
end module process_stacks
```

27.4.1 The process entry type

A process entry is a process object, augmented by a pointer to the next entry. We do not need specific methods, all relevant methods are inherited.

On higher level, processes should be prepared as process entry objects.

```
<Process stacks: public>≡
    public :: process_entry_t

<Process stacks: types>≡
    type, extends (process_t) :: process_entry_t
        type(process_entry_t), pointer :: next => null ()
    end type process_entry_t
```

27.4.2 The process stack type

For easy conversion and lookup it is useful to store the filling number in the object. The content is stored as a linked list.

The `var_list` component stores process-specific results, so they can be retrieved as (pseudo) variables.

The process stack can be linked to another one. This allows us to work with stacks of local scope.

```
<Process stacks: public>+≡
    public :: process_stack_t

<Process stacks: types>+≡
    type :: process_stack_t
        integer :: n = 0
        type(process_entry_t), pointer :: first => null ()
        type(var_list_t), pointer :: var_list => null ()
        type(process_stack_t), pointer :: next => null ()
    contains
        <Process stacks: process stack: TBP>
    end type process_stack_t
```

Finalize partly: deallocate the process stack and variable list entries, but keep the variable list as an empty object. This way, the variable list links are kept.

```
<Process stacks: process stack: TBP>≡
    procedure :: clear => process_stack_clear

<Process stacks: procedures>≡
    subroutine process_stack_clear (stack)
        class(process_stack_t), intent(inout) :: stack
        type(process_entry_t), pointer :: process
        if (associated (stack%var_list)) then
            call stack%var_list%final ()
        end if
        do while (associated (stack%first))
            process => stack%first
            stack%first => process%next
            call process%final ()
        end do
```



```

        deallocate (process)
    end do
    stack%n = 0
end subroutine process_stack_clear

```

Finalizer. Clear and deallocate the variable list.

```

<Process stacks: process stack: TBP>+≡
    procedure :: final => process_stack_final

<Process stacks: procedures>+≡
    subroutine process_stack_final (object)
        class(process_stack_t), intent(inout) :: object
        call object%clear ()
        if (associated (object%var_list)) then
            deallocate (object%var_list)
        end if
    end subroutine process_stack_final

```

Output. The processes on the stack will be ordered LIFO, i.e., backwards.

```

<Process stacks: process stack: TBP>+≡
    procedure :: write => process_stack_write

<Process stacks: procedures>+≡
    recursive subroutine process_stack_write (object, unit, pacify)
        class(process_stack_t), intent(in) :: object
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: pacify
        type(process_entry_t), pointer :: process
        integer :: u
        u = given_output_unit (unit)
        call write_separator (u, 2)
        select case (object%n)
        case (0)
            write (u, "(1x,A)") "Process stack: [empty]"
            call write_separator (u, 2)
        case default
            write (u, "(1x,A)") "Process stack:"
            process => object%first
            do while (associated (process))
                call process%write (.false., u, pacify = pacify)
                process => process%next
            end do
        end select
        if (associated (object%next)) then
            write (u, "(1x,A)") "[Processes from context environment:]"
            call object%next%write (u, pacify)
        end if
    end subroutine process_stack_write

```

The variable list is printed by a separate routine, since it should be linked to the global variable list, anyway.

```

<Process stacks: process stack: TBP>+≡
    procedure :: write_var_list => process_stack_write_var_list

```

```

<Process stacks: procedures>+≡
  subroutine process_stack_write_var_list (object, unit)
    class(process_stack_t), intent(in) :: object
    integer, intent(in), optional :: unit
    if (associated (object%var_list)) then
      call var_list_write (object%var_list, unit)
    end if
  end subroutine process_stack_write_var_list

```

Short output.

```

<Process stacks: process stack: TBP>+≡
  procedure :: show => process_stack_show

<Process stacks: procedures>+≡
  recursive subroutine process_stack_show (object, unit)
    class(process_stack_t), intent(in) :: object
    integer, intent(in), optional :: unit
    type(process_entry_t), pointer :: process
    integer :: u
    u = given_output_unit (unit)
    select case (object%n)
    case (0)
    case default
      process => object%first
      do while (associated (process))
        call process%show (u, verbose=.false.)
        process => process%next
      end do
    end select
    if (associated (object%next)) call object%next%show ()
  end subroutine process_stack_show

```

27.4.3 Link

Link the current process stack to a global one.

```

<Process stacks: process stack: TBP>+≡
  procedure :: link => process_stack_link

<Process stacks: procedures>+≡
  subroutine process_stack_link (local_stack, global_stack)
    class(process_stack_t), intent(inout) :: local_stack
    type(process_stack_t), intent(in), target :: global_stack
    local_stack%next => global_stack
  end subroutine process_stack_link

```

Initialize the process variable list and link the main variable list to it.

```

<Process stacks: process stack: TBP>+≡
  procedure :: init_var_list => process_stack_init_var_list

<Process stacks: procedures>+≡
  subroutine process_stack_init_var_list (stack, var_list)
    class(process_stack_t), intent(inout) :: stack

```

```

    type(var_list_t), intent(inout), optional :: var_list
    allocate (stack%var_list)
    if (present (var_list)) call var_list%link (stack%var_list)
end subroutine process_stack_init_var_list

```

Link the process variable list to a global variable list.

```

<Process stacks: process stack: TBP>+≡
    procedure :: link_var_list => process_stack_link_var_list

<Process stacks: procedures>+≡
    subroutine process_stack_link_var_list (stack, var_list)
        class(process_stack_t), intent(inout) :: stack
        type(var_list_t), intent(in), target :: var_list
        call stack%var_list%link (var_list)
    end subroutine process_stack_link_var_list

```

27.4.4 Push

We take a process pointer and push it onto the stack. The previous pointer is nullified. Subsequently, the process is ‘owned’ by the stack and will be finalized when the stack is deleted.

```

<Process stacks: process stack: TBP>+≡
    procedure :: push => process_stack_push

<Process stacks: procedures>+≡
    subroutine process_stack_push (stack, process)
        class(process_stack_t), intent(inout) :: stack
        type(process_entry_t), intent(inout), pointer :: process
        process%next => stack%first
        stack%first => process
        process => null ()
        stack%n = stack%n + 1
    end subroutine process_stack_push

```

Initialize process variables for a given process ID, without setting values.

```

<Process stacks: process stack: TBP>+≡
    procedure :: init_result_vars => process_stack_init_result_vars

<Process stacks: procedures>+≡
    subroutine process_stack_init_result_vars (stack, id)
        class(process_stack_t), intent(inout) :: stack
        type(string_t), intent(in) :: id
        call var_list_init_num_id (stack%var_list, id)
        call var_list_init_process_results (stack%var_list, id)
    end subroutine process_stack_init_result_vars

```

Fill process variables with values. This is executed after the integration pass.

Note: We set only integral and error. With multiple MCI records possible, the results for `n_calls`, `chi2` etc. are not necessarily unique. (We might set the efficiency, though.)

```

<Process stacks: process stack: TBP>+≡
    procedure :: fill_result_vars => process_stack_fill_result_vars

```

```

<Process stacks: procedures>+≡
subroutine process_stack_fill_result_vars (stack, id)
  class(process_stack_t), intent(inout) :: stack
  type(string_t), intent(in) :: id
  type(process_t), pointer :: process
  process => stack%get_process_ptr (id)
  if (associated (process)) then
    call var_list_init_num_id (stack%var_list, id, process%get_num_id ())
    if (process%has_integral ()) then
      call var_list_init_process_results (stack%var_list, id, &
        integral = process%get_integral (), &
        error = process%get_error ())
    end if
  else
    call msg_bug ("process_stack_fill_result_vars: unknown process ID")
  end if
end subroutine process_stack_fill_result_vars

```

27.4.5 Data Access

Tell if a process exists.

```

<Process stacks: process stack: TBP>+≡
  procedure :: exists => process_stack_exists

<Process stacks: procedures>+≡
function process_stack_exists (stack, id) result (flag)
  class(process_stack_t), intent(in) :: stack
  type(string_t), intent(in) :: id
  logical :: flag
  type(process_t), pointer :: process
  process => stack%get_process_ptr (id)
  flag = associated (process)
end function process_stack_exists

```

Return a pointer to a process with specific ID. Look also at a linked stack, if necessary.

```

<Process stacks: process stack: TBP>+≡
  procedure :: get_process_ptr => process_stack_get_process_ptr

<Process stacks: procedures>+≡
recursive function process_stack_get_process_ptr (stack, id) result (ptr)
  class(process_stack_t), intent(in) :: stack
  type(string_t), intent(in) :: id
  type(process_t), pointer :: ptr
  type(process_entry_t), pointer :: entry
  ptr => null ()
  entry => stack%first
  do while (associated (entry))
    if (entry%get_id () == id) then
      ptr => entry%process_t
      return
    end if
    entry => entry%next
  end do
end function process_stack_get_process_ptr

```

```

        end do
        if (associated (stack%next)) ptr => stack%next%get_process_ptr (id)
    end function process_stack_get_process_ptr

```

27.4.6 Unit tests

```

<Process stacks: public>+≡
    public :: process_stacks_test

<Process stacks: tests>≡
    subroutine process_stacks_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Process stacks: execute tests>
    end subroutine process_stacks_test

```

Write an empty process stack

The most trivial test is to write an uninitialized process stack.

```

<Process stacks: execute tests>≡
    call test (process_stacks_1, "process_stacks_1", &
        "write an empty process stack", &
        u, results)

<Process stacks: tests>+≡
    subroutine process_stacks_1 (u)
        integer, intent(in) :: u
        type(process_stack_t) :: stack

        write (u, "(A)")  "* Test output: process_stacks_1"
        write (u, "(A)")  "* Purpose: display an empty process stack"
        write (u, "(A)")

        call stack%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: process_stacks_1"

    end subroutine process_stacks_1

```

Fill a process stack

Fill a process stack with two (identical) processes.

```

<Process stacks: execute tests>+≡
    call test (process_stacks_2, "process_stacks_2", &
        "fill a process stack", &
        u, results)

```

```

<Process stacks: tests>+≡
subroutine process_stacks_2 (u)
  integer, intent(in) :: u
  type(process_stack_t) :: stack
  type(process_library_t), target :: lib
  type(string_t) :: libname
  type(string_t) :: procname
  type(string_t) :: run_id
  type(os_data_t) :: os_data
  type(qcd_t) :: qcd
  class(rng_factory_t), allocatable :: rng_factory
  class(model_data_t), pointer :: model
  type(process_entry_t), pointer :: process => null ()

  write (u, "(A)")  "* Test output: process_stacks_2"
  write (u, "(A)")  "*   Purpose: fill a process stack"
  write (u, "(A)")

  write (u, "(A)")  "* Build, initialize and store two test processes"
  write (u, "(A)")

  libname = "process_stacks2"
  procname = libname
  call os_data_init (os_data)
  allocate (rng_test_factory_t :: rng_factory)
  call prc_test_create_library (libname, lib)

  allocate (model)
  call model%init_test ()

  allocate (process)
  run_id = "run1"
  call process%init &
    (procname, run_id, lib, os_data, qcd, rng_factory, model)
  call stack%push (process)

  allocate (model)
  call model%init_test ()

  allocate (process)
  run_id = "run2"
  call process%init &
    (procname, run_id, lib, os_data, qcd, rng_factory, model)
  call stack%push (process)

  call stack%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Cleanup"

  call stack%final ()

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: process_stacks_2"

```

```
end subroutine process_stacks_2
```

Fill a process stack

Fill a process stack with two (identical) processes.

```
(Process stacks: execute tests)+≡
  call test (process_stacks_3, "process_stacks_3", &
    "process variables", &
    u, results)

(Process stacks: tests)+≡
  subroutine process_stacks_3 (u)
    integer, intent(in) :: u
    type(process_stack_t) :: stack
    type(model_data_t), target :: model
    type(string_t) :: procname
    type(process_entry_t), pointer :: process => null ()
    type(process_instance_t), target :: process_instance

    write (u, "(A)")  "* Test output: process_stacks_3"
    write (u, "(A)")  "* Purpose: setup process variables"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize process variables"
    write (u, "(A)")

    procname = "processes_test"
    call model%init_test ()

    write (u, "(A)")  "* Initialize process variables"
    write (u, "(A)")

    call stack%init_var_list ()
    call stack%init_result_vars (procname)
    call stack%write_var_list (u)

    write (u, "(A)")
    write (u, "(A)")  "* Build and integrate a test process"
    write (u, "(A)")

    allocate (process)
    call prepare_test_process (process%process_t, process_instance, model)
    call process%integrate (process_instance, 1, 1, 1000)
    call process_instance%final ()
    call process%final_integration (1)
    call stack%push (process)

    write (u, "(A)")  "* Fill process variables"
    write (u, "(A)")

    call stack%fill_result_vars (procname)
    call stack%write_var_list (u)
```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call stack%final ()

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_stacks_3"

end subroutine process_stacks_3

```

Linked a process stack

Fill two process stack, linked to each other.

```

<Process stacks: execute tests>+≡
  call test (process_stacks_4, "process_stacks_4", &
    "linked stacks", &
    u, results)
<Process stacks: tests>+≡
subroutine process_stacks_4 (u)
  integer, intent(in) :: u
  type(process_library_t), target :: lib
  type(process_stack_t), target :: stack1, stack2
  class(model_data_t), pointer :: model
  type(string_t) :: libname
  type(string_t) :: procname
  type(string_t) :: run_id
  type(os_data_t) :: os_data
  type(qcd_t) :: qcd
  class(rng_factory_t), allocatable :: rng_factory
  type(process_entry_t), pointer :: process => null ()

  write (u, "(A)")  "* Test output: process_stacks_4"
  write (u, "(A)")  "* Purpose: link process stacks"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize process variables"
  write (u, "(A)")

  libname = "process_stacks_4_lib"
  procname = "process_stacks_4a"

  call os_data_init (os_data)
  allocate (rng_test_factory_t :: rng_factory)

  write (u, "(A)")  "* Initialize first process"
  write (u, "(A)")

  call prc_test_create_library (procname, lib)

```



```

allocate (model)
call model%init_test ()

allocate (process)
run_id = "run1"
call process%init &
    (procname, run_id, lib, os_data, qcd, rng_factory, model)
call stack1%push (process)

write (u, "(A)")  "* Initialize second process"
write (u, "(A)")

call stack2%link (stack1)

procname = "process_stacks_4b"
call prc_test_create_library (procname, lib)

allocate (model)
call model%init_test ()

allocate (process)
run_id = "run2"
call process%init &
    (procname, run_id, lib, os_data, qcd, rng_factory, model)
call stack2%push (process)

write (u, "(A)")  "* Show linked stacks"
write (u, "(A)")

call stack2%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call stack2%final ()
call stack1%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_stacks_4"

end subroutine process_stacks_4

```

Chapter 28

Event Implementation

With a process object and the associated methods at hand, we can generate events for elementary processes and, by subsequent transformation, for complete physical processes.

We have the following modules:

event_transforms Abstract base type for transforming a physical process with process instance and included evaluators, etc., into a new object. The following modules extend this base type.

decays Combine the elementary process with elementary decay processes and thus transform the elementary event into a decayed event, still at the parton level.

showers Create QED/QCD showers out of the partons that are emitted by elementary processes. This should be interleaved with showering of radiated particles (structure functions) and multiple interactions.

hadrons (not implemented yet) Apply hadronization to the partonic events, interleaved with hadron decays. (The current setup relies on hadronizing partonic events externally.)

events Combine all pieces to generate full events.

eio_raw Raw I/O for complete events.

28.1 Abstract Event Transforms

```
<event_transforms.f90>≡  
  <File header>  
  
  module event_transforms  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use format_utils, only: write_separator  
    use unit_tests
```

```

use diagnostics
use os_interface
use sm_qcd
use model_data
use state_matrices
use interactions
use particles
use subevents
use process_libraries
use prc_core
use prc_test
use rng_base
use mci_base
use mci_midpoint
use phs_base
use phs_single
use processes
use process_stacks
use powheg

<Standard module head>

<Event transforms: public>

<Event transforms: types>

<Event transforms: interfaces>

contains

<Event transforms: procedures>

<Event transforms: tests>

end module event_transforms

```

28.1.1 Abstract base type

Essentially, all methods are abstract, but some get minimal base versions. We know that there will be a random-number generator at top level, and that we will relate to an elementary process.

The model is stored separately. It may contain modified setting that differ from the model instance stored in the process object.

Each event transform contains a particle set that it can fill for further use. There is a flag that indicates this.

We will collect event transforms in a list, therefore we include `previous` and `next` pointers.

```

<Event transforms: public>≡
    public :: evt_t

<Event transforms: types>≡
    type, abstract :: evt_t

```

```

type(process_t), pointer :: process => null ()
type(process_instance_t), pointer :: process_instance => null ()
class(model_data_t), pointer :: model => null ()
class(rng_t), allocatable :: rng
integer :: rejection_count = 0
logical :: particle_set_exists = .false.
type(particle_set_t) :: particle_set
class(evt_t), pointer :: previous => null ()
class(evt_t), pointer :: next => null ()
contains
  <Event transforms: evt: TBP>
end type evt_t

```

Finalizer. In any case, we finalize the r.n.g. The process instance is a pointer and should not be finalized here.

```

<Event transforms: evt: TBP>≡
  procedure :: final => evt_final
  procedure :: base_final => evt_final

<Event transforms: procedures>≡
  subroutine evt_final (object)
    class(evt_t), intent(inout) :: object
    if (allocated (object%rng)) call object%rng%final ()
    if (object%particle_set_exists) &
      call object%particle_set%final ()
  end subroutine evt_final

<Event transforms: evt: TBP>+≡
  procedure (evt_write), deferred :: write

<Event transforms: interfaces>≡
  abstract interface
    subroutine evt_write (evt, unit, verbose, more_verbose, testflag)
      import
      class(evt_t), intent(in) :: evt
      integer, intent(in), optional :: unit
      logical, intent(in), optional :: verbose, more_verbose, testflag
    end subroutine evt_write
  end interface

```

Output. We can print r.n.g. info.

```

<Event transforms: evt: TBP>+≡
  procedure :: base_write => evt_base_write

<Event transforms: procedures>+≡
  subroutine evt_base_write (evt, unit, testflag, show_set)
    class(evt_t), intent(in) :: evt
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: testflag, show_set
    integer :: u
    logical :: show
    u = given_output_unit (unit)
    show = .true.; if (present (show_set)) show = show_set
    if (associated (evt%process)) then

```

```

        write (u, "(3x,A,A,A)") "Associated process: '", &
            char (evt%process%get_id ()), "'"
    end if
    if (allocated (evt%rng)) then
        call evt%rng%write (u, 1)
        write (u, "(3x,A,I0)") "Number of tries = ", evt%rejection_count
    end if
    if (show) then
        if (evt%particle_set_exists) then
            call write_separator (u)
            call evt%particle_set%write (u, testflag = testflag)
        end if
    end if
end subroutine evt_base_write

```

Connect the transform with a process instance (and thus with the associated process). Use this to allocate the master random-number generator.

This is not an initializer; we may initialize the transform by implementation-specific methods.

```

(Event transforms: evt: TBP)+≡
    procedure :: connect => evt_connect
    procedure :: base_connect => evt_connect

(Event transforms: procedures)+≡
    subroutine evt_connect (evt, process_instance, model, process_stack)
        class(evt_t), intent(inout), target :: evt
        type(process_instance_t), intent(in), target :: process_instance
        class(model_data_t), intent(in), target :: model
        type(process_stack_t), intent(in), optional :: process_stack
        evt%process => process_instance%process
        evt%process_instance => process_instance
        evt%model => model
        call evt%process%make_rng (evt%rng)
    end subroutine evt_connect

```

Reset internal state.

```

(Event transforms: evt: TBP)+≡
    procedure :: reset => evt_reset
    procedure :: base_reset => evt_reset

(Event transforms: procedures)+≡
    subroutine evt_reset (evt)
        class(evt_t), intent(inout) :: evt
        evt%rejection_count = 0
        evt%particle_set_exists = .false.
    end subroutine evt_reset

```

Prepare for a new event: reset internal state, if necessary. We provide MCI and term index of the parent process.

```

(Event transforms: evt: TBP)+≡
    procedure (evt_prepare_new_event), deferred :: prepare_new_event

```

```

(Event transforms: interfaces)+≡
interface
  subroutine evt_prepare_new_event (evt, i_mci, i_term)
    import
    class(evt_t), intent(inout) :: evt
    integer, intent(in) :: i_mci, i_term
  end subroutine evt_prepare_new_event
end interface

```

Generate a weighted event, using a valid initiator event in the process instance, and the random-number generator. The returned event probability should be a number between zero and one that we can use for rejection.

```

(Event transforms: evt: TBP)+≡
  procedure (evt_generate_weighted), deferred :: generate_weighted

(Event transforms: interfaces)+≡
  abstract interface
    subroutine evt_generate_weighted (evt, probability)
      import
      class(evt_t), intent(inout) :: evt
      real(default), intent(out) :: probability
    end subroutine evt_generate_weighted
  end interface

```

The unweighted event generation routine is actually implemented. It uses the random-number generator for simple rejection. Of course, the implementation may override this and implement a different way of generating an unweighted event.

```

(Event transforms: evt: TBP)+≡
  procedure :: generate_unweighted => evt_generate_unweighted
  procedure :: base_generate_unweighted => evt_generate_unweighted

(Event transforms: procedures)+≡
  subroutine evt_generate_unweighted (evt)
    class(evt_t), intent(inout) :: evt
    real(default) :: p, x
    evt%rejection_count = 0
    REJECTION: do
      evt%rejection_count = evt%rejection_count + 1
      call evt%generate_weighted (p)
      if (signal_is_pending ()) return
      call evt%rng%generate (x)
      if (x < p) exit REJECTION
    end do REJECTION
  end subroutine evt_generate_unweighted

```

Make a particle set. This should take the most recent evaluator (or whatever stores the event), factorize the density matrix if necessary, and store as a particle set.

If applicable, the factorization should make use of the `factorization_mode` and `keep_correlations` settings.

The values *r*, if set, should control the factorization in more detail, e.g., bypassing the random-number generator.

```

(Event transforms: evt: TBP)+≡
  procedure (evt_make_particle_set), deferred :: make_particle_set

(Event transforms: interfaces)+≡
  interface
    subroutine evt_make_particle_set &
      (evt, factorization_mode, keep_correlations, r)
    import
    class(evt_t), intent(inout) :: evt
    integer, intent(in) :: factorization_mode
    logical, intent(in) :: keep_correlations
    real(default), dimension(:), intent(in), optional :: r
  end subroutine evt_make_particle_set
end interface

```

Copy an existing particle set into the event record. This bypasses all methods to evaluate the internal state, but may be sufficient for further processing.

```

(Event transforms: evt: TBP)+≡
  procedure :: set_particle_set => evt_set_particle_set

(Event transforms: procedures)+≡
  subroutine evt_set_particle_set (evt, particle_set, i_mci, i_term)
    class(evt_t), intent(inout) :: evt
    type(particle_set_t), intent(in) :: particle_set
    integer, intent(in) :: i_term, i_mci
    call evt%prepare_new_event (i_mci, i_term)
    evt%particle_set = particle_set
    evt%particle_set_exists = .true.
  end subroutine evt_set_particle_set

```

This procedure can help in the previous task, if the particles are available in the form of an interaction object. (We need two interactions, one with color summed over, and one with the probability distributed among flows.)

We use the two values from the random number generator for factorizing the state. For testing purposes, we can provide those numbers explicitly.

```

(Event transforms: evt: TBP)+≡
  procedure :: factorize_interactions => evt_factorize_interactions

(Event transforms: procedures)+≡
  subroutine evt_factorize_interactions &
    (evt, int_matrix, int_flows, factorization_mode, keep_correlations, r)
    class(evt_t), intent(inout) :: evt
    type(interaction_t), intent(in), target :: int_matrix, int_flows
    integer, intent(in) :: factorization_mode
    logical, intent(in) :: keep_correlations
    real(default), dimension(:), intent(in), optional :: r
    real(default), dimension(2) :: x
    if (present (r)) then
      if (size (r) == 2) then
        x = r
      else
        call msg_bug ("event factorization: size of r array must be 2")
      end if
    end if
  end subroutine

```

```

        end if
    else
        call evt%rng%generate (x)
    end if
    call evt%particle_set%init (evt%particle_set_exists, &
        int_matrix, int_flows, factorization_mode, x, &
        keep_correlations, keep_virtual=.true.)
    evt%particle_set_exists = .true.
end subroutine evt_factorize_interactions

```

Mark the incoming particles as incoming in the particle set. This is necessary because in the interaction objects they are usually marked as virtual.

In the inquiry functions we set the term index to one; the indices of beams and incoming particles should be identical for all process terms.

We use the initial elementary process for obtaining the indices. Thus, we implicitly assume that the beam and incoming indices stay the same across event transforms. If this is not true for a transform (say, MPI), it should override this method.

```

<Event transforms: evt: TBP>+≡
    procedure :: tag_incoming => evt_tag_incoming
<Event transforms: procedures>+≡
    subroutine evt_tag_incoming (evt)
        class(evt_t), intent(inout) :: evt
        integer :: i_term, n_in
        integer, dimension(:), allocatable :: beam_index, in_index
        n_in = evt%process%get_n_in ()
        i_term = 1
        allocate (beam_index (n_in))
        call evt%process_instance%get_beam_index (i_term, beam_index)
        call evt%particle_set%reset_status (beam_index, PRT_BEAM)
        allocate (in_index (n_in))
        call evt%process_instance%get_in_index (i_term, in_index)
        call evt%particle_set%reset_status (in_index, PRT_INCOMING)
    end subroutine evt_tag_incoming

```

28.1.2 Implementation: Trivial transform

This transform contains just a pointer to process and process instance. The `generate` methods do nothing.

```

<Event transforms: public>+≡
    public :: evt_trivial_t
<Event transforms: types>+≡
    type, extends (evt_t) :: evt_trivial_t
        contains
        <Event transforms: evt trivial: TBP>
    end type evt_trivial_t

```

The finalizer is trivial. Some output:

```

<Event transforms: evt trivial: TBP>≡
    procedure :: write => evt_trivial_write

```



```

(Event transforms: procedures)+≡
subroutine evt_trivial_write (evt, unit, verbose, more_verbose, testflag)
  class(evt_trivial_t), intent(in) :: evt
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose, more_verbose, testflag
  integer :: u
  u = given_output_unit (unit)
  call write_separator (u, 2)
  write (u, "(1x,A)") "Event transform: trivial (hard process)"
  call write_separator (u)
  call evt%base_write (u, testflag = testflag)
end subroutine evt_trivial_write

```

Nothing to do here:

```

(Event transforms: evt trivial: TBP)+≡
  procedure :: prepare_new_event => evt_trivial_prepare_new_event

(Event transforms: procedures)+≡
subroutine evt_trivial_prepare_new_event (evt, i_mci, i_term)
  class(evt_trivial_t), intent(inout) :: evt
  integer, intent(in) :: i_mci, i_term
  call evt%reset ()
end subroutine evt_trivial_prepare_new_event

```

The weighted generator is, surprisingly, trivial.

```

(Event transforms: evt trivial: TBP)+≡
  procedure :: generate_weighted => evt_trivial_generate_weighted

(Event transforms: procedures)+≡
subroutine evt_trivial_generate_weighted (evt, probability)
  class(evt_trivial_t), intent(inout) :: evt
  real(default), intent(out) :: probability
  probability = 1
end subroutine evt_trivial_generate_weighted

```

This routine makes a particle set, using the associated process instance as-is.

```

(Event transforms: evt trivial: TBP)+≡
  procedure :: make_particle_set => evt_trivial_make_particle_set

(Event transforms: procedures)+≡
subroutine evt_trivial_make_particle_set &
  (evt, factorization_mode, keep_correlations, r)
  class(evt_trivial_t), intent(inout) :: evt
  integer, intent(in) :: factorization_mode
  logical, intent(in) :: keep_correlations
  real(default), dimension(:), intent(in), optional :: r
  integer :: i_term
  type(interaction_t), pointer :: int_matrix, int_flows
  if (evt%process_instance%is_complete_event ()) then
    call evt%process_instance%select_i_term (i_term)
    int_matrix => evt%process_instance%get_matrix_int_ptr (i_term)
    int_flows => evt%process_instance%get_flows_int_ptr (i_term)
    call evt%factorize_interactions (int_matrix, int_flows, &
      factorization_mode, keep_correlations, r)
  end if
end subroutine evt_trivial_make_particle_set

```

```

        call evt%tag_incoming ()
    else
        call msg_bug ("Event factorization: event is incomplete")
    end if
end subroutine evt_trivial_make_particle_set

```

28.1.3 Unit tests

```

<Event transforms: public>+≡
    public :: event_transforms_test

<Event transforms: tests>≡
    subroutine event_transforms_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Event transforms: execute tests>
    end subroutine event_transforms_test

```

Test trivial event transform

The trivial transform, as an instance of the abstract transform, does nothing but to trigger event generation for an elementary process.

```

<Event transforms: execute tests>≡
    call test (event_transforms_1, "event_transforms_1", &
        "trivial event transform", &
        u, results)

<Event transforms: tests>+≡
    subroutine event_transforms_1 (u)
        integer, intent(in) :: u
        type(os_data_t) :: os_data
        type(qcd_t) :: qcd
        class(rng_factory_t), allocatable :: rng_factory
        class(model_data_t), pointer :: model
        type(process_library_t), target :: lib
        type(string_t) :: libname, procname1, run_id
        class(prc_core_t), allocatable :: core_template
        class(mci_t), allocatable :: mci_template
        class(phs_config_t), allocatable :: phs_config_template
        real(default) :: sqrts
        type(process_t), allocatable, target :: process
        type(process_instance_t), allocatable, target :: process_instance
        class(evt_t), allocatable :: evt
        integer :: factorization_mode
        logical :: keep_correlations

        write (u, "(A)")  "* Test output: event_transforms_1"
        write (u, "(A)")  "* Purpose: handle trivial transform"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize environment and parent process"
        write (u, "(A)")

```

```

call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)

libname = "event_transforms_1_lib"
procname1 = "event_transforms_1_p"
run_id = "event_transforms_1"

call prc_test_create_library (libname, lib, &
    scattering = .true., procname1 = procname1)
call reset_interaction_counter ()

allocate (model)
call model%init_test ()

allocate (process)
call process%init &
    (procname1, run_id, lib, os_data, qcd, rng_factory, model)

allocate (test_t :: core_template)
allocate (mci_midpoint_t :: mci_template)
allocate (phs_single_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()
call process%setup_mci ()
call process%setup_terms ()

allocate (process_instance)
call process_instance%init (process)
call process%integrate (process_instance, 1, n_it=1, n_calls=100)
call process%final_integration (1)
call process_instance%final ()
deallocate (process_instance)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
call process_instance%init_simulation (1)

write (u, "(A)")  "* Initialize trivial event transform"
write (u, "(A)")

allocate (evt_trivial_t :: evt)
model => process%get_model_ptr ()
call evt%connect (process_instance, model)

write (u, "(A)")  "* Generate event and subsequent transform"
write (u, "(A)")

call process%generate_unweighted_event (process_instance, 1)

```

```

call process_instance%evaluate_event_data ()

call evt%prepare_new_event (1, 1)
call evt%generate_unweighted ()

call write_separator (u, 2)
call evt%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Obtain particle set"
write (u, "(A)")

factorization_mode = FM_IGNORE_HELICITY
keep_correlations = .false.

call evt%make_particle_set (factorization_mode, keep_correlations)

call write_separator (u, 2)
call evt%write (u)
call write_separator (u, 2)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call evt%final ()
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Test output end: event_transforms_1"

end subroutine event_transforms_1

```

28.2 Hadronization interface

```

⟨hadrons.f90⟩≡
  ⟨File header⟩

module hadrons

  ⟨Use kinds⟩
  ⟨Use strings⟩
  use io_units
  use format_utils, only: write_separator
  use diagnostics
  use sm_qcd
  use particles
  use model_data
  use models
  use hep_common
  use event_transforms

```

```

    use shower_base
    use shower_pythia6

```

⟨Standard module head⟩

⟨Hadrons: public⟩

⟨Hadrons: types⟩

⟨Hadrons: interfaces⟩

⟨Hadrons: parameters⟩

contains

⟨Hadrons: procedures⟩

```

end module hadrons

```

28.2.1 Hadronization implementations

⟨Hadrons: public⟩≡

```

    public :: HADRONS_PYTHIA6, HADRONS_PYTHIA8

```

⟨Hadrons: parameters⟩≡

```

    integer, parameter :: HADRONS_PYTHIA6 = 1
    integer, parameter :: HADRONS_PYTHIA8 = 2
    integer, parameter :: HADRONS_UNDEFINED = 17

```

A dictionary

⟨Hadrons: public⟩+≡

```

    public :: hadrons_method_of_string

```

⟨Hadrons: procedures⟩≡

```

    elemental function hadrons_method_of_string (string) result (i)
        integer :: i
        type(string_t), intent(in) :: string
        select case (char(string))
        case ("PYTHIA6")
            i = HADRONS_PYTHIA6
        case ("PYTHIA8")
            i = HADRONS_PYTHIA8
        case default
            i = HADRONS_UNDEFINED
        end select
    end function hadrons_method_of_string

```

⟨Hadrons: public⟩+≡

```

    public :: hadrons_method_to_string

```

⟨Hadrons: procedures⟩+≡

```

    elemental function hadrons_method_to_string (i) result (string)
        type(string_t) :: string
        integer, intent(in) :: i
        select case (i)

```

```

    case (HADRONS_PYTHIA6)
      string = "PYTHIA6"
    case (HADRONS_PYTHIA8)
      string = "PYTHIA8"
    case default
      string = "UNDEFINED"
    end select
  end function hadrons_method_to_string

```

28.2.2 Abstract Hadronization Type

The model is the fallback model including all hadrons

```

⟨Hadrons: types⟩≡
  type, abstract :: hadrons_t
  type(shower_settings_t), pointer :: settings
  type(model_t), pointer :: model => null()
  contains
  ⟨Hadrons: hadrons: TBP⟩
  end type hadrons_t

⟨Hadrons: hadrons: TBP⟩≡
  procedure (hadrons_init), deferred :: init

⟨Hadrons: interfaces⟩≡
  abstract interface
    subroutine hadrons_init (hadrons, settings, model_hadrons)
      import
      class(hadrons_t), intent(out) :: hadrons
      type(shower_settings_t), target, intent(in) :: settings
      type(model_t), target, intent(in) :: model_hadrons
    end subroutine hadrons_init
  end interface

⟨Hadrons: hadrons: TBP⟩+≡
  procedure (hadrons_hadronize), deferred :: hadronize

⟨Hadrons: interfaces⟩+≡
  abstract interface
    subroutine hadrons_hadronize &
      (hadrons, particle_set, valid)
      import
      class(hadrons_t), intent(inout) :: hadrons
      type(particle_set_t), intent(in) :: particle_set
      logical, intent(out) :: valid
    end subroutine hadrons_hadronize
  end interface

⟨Hadrons: hadrons: TBP⟩+≡
  procedure (hadrons_make_particle_set), deferred :: make_particle_set

```

```

<Hadrons: interfaces>+=
  abstract interface
    subroutine hadrons_make_particle_set (hadrons, particle_set, &
      model, valid)
      import
      class(hadrons_t), intent(in) :: hadrons
      type(particle_set_t), intent(inout) :: particle_set
      class(model_data_t), intent(in), target :: model
      logical, intent(out) :: valid
    end subroutine hadrons_make_particle_set
  end interface

```

28.2.3 PYTHIA6 Hadronization Type

Hadronization via PYTHIA6 is at the moment the only option for hadronization within WHIZARD.

```

<Hadrons: types>+=
  type, extends (hadrons_t) :: hadrons_pythia6_t
  contains
    <Hadrons: hadrons pythia6: TBP>
  end type hadrons_pythia6_t

<Hadrons: hadrons pythia6: TBP>=
  procedure :: init => hadrons_pythia6_init

<Hadrons: procedures>+=
  subroutine hadrons_pythia6_init (hadrons, settings, model_hadrons)
    class(hadrons_pythia6_t), intent(out) :: hadrons
    type(shower_settings_t), target, intent(in) :: settings
    type(model_t), intent(in), target :: model_hadrons
    logical :: pygive_not_set_by_shower
    hadrons%model => model_hadrons
    hadrons%settings => settings
    pygive_not_set_by_shower = .not. (settings%method == PS_PYTHIA6 &
      .and. (settings%isr_active .or. settings%fsr_active))
    if (pygive_not_set_by_shower) then
      call pythia6_set_verbose (settings%verbose)
      call pythia6_set_config (settings%pythia6_pygive)
    end if
    call msg_message &
      ("Hadronization: Using PYTHIA6 interface for hadronization and decays")
  end subroutine hadrons_pythia6_init

```

Assume that the event record is still in the PYTHIA COMMON BLOCKS transferred there by the WHIZARD or PYTHIA6 shower routines.

```

<Hadrons: hadrons pythia6: TBP>+=
  procedure :: hadronize => hadrons_pythia6_hadronize

<Hadrons: procedures>+=
  subroutine hadrons_pythia6_hadronize (hadrons, particle_set, valid)
    class(hadrons_pythia6_t), intent(inout) :: hadrons
    type(particle_set_t), intent(in) :: particle_set

```

```

logical, intent(out) :: valid
if (signal_is_pending ()) return
call pygive ("MSTP(111)=1")      !!! Switch on hadronization and decays
call pygive ("MSTJ(1)=1")       !!! String fragmentation
call pygive ("MSTJ(21)=2")      !!! String fragmentation keeping resonance momentum
call pyexec ()
valid = .true.
end subroutine hadrons_pythia6_hadronize

```

```

<Hadrons: hadrons pythia6: TBP>+≡
  procedure :: make_particle_set => hadrons_pythia6_make_particle_set
<Hadrons: procedures>+≡
  subroutine hadrons_pythia6_make_particle_set &
    (hadrons, particle_set, model, valid)
    class(hadrons_pythia6_t), intent(in) :: hadrons
    type(particle_set_t), intent(inout) :: particle_set
    class(model_data_t), intent(in), target :: model
    logical, intent(out) :: valid
    if (signal_is_pending ()) return
    valid = pythia6_handle_errors ()
    if (valid) then
      call pythia6_combine_with_particle_set &
        (particle_set, model, hadrons%model)
    end if
  end subroutine hadrons_pythia6_make_particle_set

```

28.2.4 Pythia8 Hadronization Type

```

<Hadrons: public>+≡
  public :: hadrons_pythia8_t
<Hadrons: types>+≡
  type, extends (hadrons_t) :: hadrons_pythia8_t
  contains
  <Hadrons: hadrons pythia8: TBP>
  end type hadrons_pythia8_t

<Hadrons: hadrons pythia8: TBP>≡
  procedure :: init => hadrons_pythia8_init
<Hadrons: procedures>+≡
  subroutine hadrons_pythia8_init (hadrons, settings, model_hadrons)
    class(hadrons_pythia8_t), intent(out) :: hadrons
    type(shower_settings_t), target, intent(in) :: settings
    type(model_t), intent(in), target :: model_hadrons
    logical :: options_not_set_by_shower
    options_not_set_by_shower = .not. (settings%method == PS_PYTHIA8 &
      .and. (settings%isr_active .or. settings%fsr_active))
    if (options_not_set_by_shower) then
      !call pythia8_set_verbose (settings%verbose)
      !call pythia8_set_config (settings%pythia8_config)
      !call pythia8_set_config_file (settings%pythia8_config_file)
    end if
  end subroutine hadrons_pythia8_init

```



```

end if
call msg_message &
    ("Using Pythia8 interface for hadronization and decays")
end subroutine hadrons_pythia8_init

<Hadrons: hadrons pythia8: TBP>+≡
    procedure :: hadronize => hadrons_pythia8_hadronize

<Hadrons: procedures>+≡
    subroutine hadrons_pythia8_hadronize (hadrons, particle_set, valid)
        class(hadrons_pythia8_t), intent(inout) :: hadrons
        type(particle_set_t), intent(in) :: particle_set
        logical, intent(out) :: valid
        ! call pythia8_hadronize
    end subroutine hadrons_pythia8_hadronize

<Hadrons: hadrons pythia8: TBP>+≡
    procedure :: make_particle_set => hadrons_pythia8_make_particle_set

<Hadrons: procedures>+≡
    pure subroutine hadrons_pythia8_make_particle_set &
        (hadrons, particle_set, model, valid)
        class(hadrons_pythia8_t), intent(in) :: hadrons
        type(particle_set_t), intent(inout) :: particle_set
        class(model_data_t), intent(in), target :: model
        logical, intent(out) :: valid
        ! call pythia8_combine_particle_set
    end subroutine hadrons_pythia8_make_particle_set

```

28.2.5 Hadronization Event Transform

This is the type for the hadronization event transform. It does not depend on the specific hadronization implementation of `hadrons_t`.

```

<Hadrons: public>+≡
    public :: evt_hadrons_t

<Hadrons: types>+≡
    type, extends (evt_t) :: evt_hadrons_t
        class(hadrons_t), allocatable :: hadrons
        type(shower_settings_t) :: settings
        type(model_t), pointer :: model_hadrons => null()
        type(qcd_t), pointer :: qcd_t => null()
    contains
        <Hadrons: evt hadrons: TBP>
    end type evt_hadrons_t

```

Initialize the parameters. The `model_hadrons` is supposed to be the SM variant that contains all hadrons that may be generated in the shower.

```

<Hadrons: evt hadrons: TBP>≡
    procedure :: init => evt_hadrons_init

```

```

<Hadrons: procedures>+≡
subroutine evt_hadrons_init (evt, settings, model_hadrons, method)
  class(evt_hadrons_t), intent(out) :: evt
  type(shower_settings_t), target, intent(in) :: settings
  type(model_t), intent(in), target :: model_hadrons
  type(string_t), intent(in) :: method
  evt%settings = settings
  evt%model_hadrons => model_hadrons
  !!! TODO: (bcn 2015-03-27) method should be part of hadronization settings
  select case (char (method))
  case ("PYTHIA6")
    allocate (hadrons_pythia6_t :: evt%hadrons)
  case ("PYTHIA8")
    allocate (hadrons_pythia8_t :: evt%hadrons)
  case default
    call msg_fatal ("Hadronization method " // char (method) // &
      " not implemented.")
  end select
  call evt%hadrons%init (evt%settings, model_hadrons)
end subroutine evt_hadrons_init

```

Output.

```

<Hadrons: evt hadrons: TBP>+≡
  procedure :: write => evt_hadrons_write

<Hadrons: procedures>+≡
subroutine evt_hadrons_write (evt, unit, verbose, more_verbose, testflag)
  class(evt_hadrons_t), intent(in) :: evt
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose, more_verbose, testflag
  integer :: u
  u = given_output_unit (unit)
  call write_separator (u, 2)
  write (u, "(1x,A)") "Event transform: hadronization"
  call write_separator (u)
  call evt%base_write (u, testflag = testflag, show_set = .false.)
  if (evt%particle_set_exists) &
    call evt%particle_set%write &
      (u, summary = .true., compressed = .true., testflag = testflag)
  call write_separator (u)
  call evt%settings%write (u)
end subroutine evt_hadrons_write

```

Here we take the particle set from the previous event transform and apply the hadronization. The result is stored in the `evt%hadrons` object. We always return a probability of unity as we don't have the analytic weight of the hadronization. Invalid events have to be discarded by the caller which is why we mark the particle set as invalid.

```

<Hadrons: evt hadrons: TBP>+≡
  procedure :: generate_weighted => evt_hadrons_generate_weighted

<Hadrons: procedures>+≡
subroutine evt_hadrons_generate_weighted (evt, probability)

```

```

class(evt_hadrons_t), intent(inout) :: evt
real(default), intent(out) :: probability
logical :: valid
if (evt%previous%particle_set_exists) then
    evt%particle_set = evt%previous%particle_set
    call evt%hadrons%hadronize (evt%particle_set, valid)
    probability = 1
    evt%particle_set_exists = valid
else
    call msg_bug ("Hadrons: input particle set does not exist")
end if
end subroutine evt_hadrons_generate_weighted

```

The factorization parameters are irrelevant.

```

⟨Hadrons: evt hadrons: TBP⟩+≡
    procedure :: make_particle_set => evt_hadrons_make_particle_set

⟨Hadrons: procedures⟩+≡
    subroutine evt_hadrons_make_particle_set &
        (evt, factorization_mode, keep_correlations, r)
        class(evt_hadrons_t), intent(inout) :: evt
        integer, intent(in) :: factorization_mode
        logical, intent(in) :: keep_correlations
        real(default), dimension(:), intent(in), optional :: r
        logical :: valid
        call evt%hadrons%make_particle_set (evt%particle_set, evt%model, valid)
        evt%particle_set_exists = evt%particle_set_exists .and. valid
    end subroutine evt_hadrons_make_particle_set

⟨Hadrons: evt hadrons: TBP⟩+≡
    procedure :: prepare_new_event => evt_hadrons_prepare_new_event

⟨Hadrons: procedures⟩+≡
    subroutine evt_hadrons_prepare_new_event (evt, i_mci, i_term)
        class(evt_hadrons_t), intent(inout) :: evt
        integer, intent(in) :: i_mci, i_term
        call evt%reset ()
    end subroutine evt_hadrons_prepare_new_event

```

28.3 Decays

```

⟨decays.f90⟩≡
    ⟨File header⟩

    module decays

        ⟨Use kinds⟩
        ⟨Use strings⟩
        use io_units
        use format_utils, only: write_indent, write_separator
        use unit_tests
    end module decays

```

```

use diagnostics
use os_interface
use sm_qcd
use flavors
use helicities
use quantum_numbers
use state_matrices
use interactions
use evaluators
use variables
use model_data
use rng_base
use selectors
use prc_core
use prc_test
use process_libraries
use mci_base
use mci_midpoint
use phs_base
use phs_single
use parton_states
use processes
use process_stacks
use event_transforms

```

⟨Standard module head⟩

⟨Decays: public⟩

⟨Decays: types⟩

⟨Decays: interfaces⟩

contains

⟨Decays: procedures⟩

⟨Decays: tests⟩

end module decays

28.3.1 Final-State Particle Configuration

A final-state particle may be either stable or unstable. Here is an empty abstract type as the parent of both, with holds just the flavor information.

```

⟨Decays: types⟩≡
  type, abstract :: any_config_t
  contains
    ⟨Decays: any config: TBP⟩
  end type any_config_t

```

Finalizer, depends on the implementation.

```

<Decays: any config: TBP>≡
  procedure (any_config_final), deferred :: final

<Decays: interfaces>≡
  interface
    subroutine any_config_final (object)
      import
        class(any_config_t), intent(inout) :: object
    end subroutine any_config_final
  end interface

```

The output is also deferred:

```

<Decays: any config: TBP>+≡
  procedure (any_config_write), deferred :: write

<Decays: interfaces>+≡
  interface
    subroutine any_config_write (object, unit, indent, verbose)
      import
        class(any_config_t), intent(in) :: object
        integer, intent(in), optional :: unit, indent
        logical, intent(in), optional :: verbose
    end subroutine any_config_write
  end interface

```

This is a container for a stable or unstable particle configurator. We need this wrapper for preparing arrays that mix stable and unstable particles.

```

<Decays: types>+≡
  type :: particle_config_t
    class(any_config_t), allocatable :: c
  end type particle_config_t

```

28.3.2 Final-State Particle

In theory, for the particle instance we only need to consider the unstable case. However, it is more straightforward to treat configuration and instance on the same footing, and to introduce a wrapper for particle objects as above. This also works around a compiler bug in gfortran.

```

<Decays: types>+≡
  type, abstract :: any_t
    contains
      <Decays: any: TBP>
  end type any_t

```

Finalizer, depends on the implementation.

```

<Decays: any: TBP>≡
  procedure (any_final), deferred :: final

```

```

<Decays: interfaces>+≡
  interface
    subroutine any_final (object)
      import
        class(any_t), intent(inout) :: object
    end subroutine any_final
  end interface

```

The output is also deferred:

```

<Decays: any: TBP>+≡
  procedure (any_write), deferred :: write

<Decays: interfaces>+≡
  interface
    subroutine any_write (object, unit, indent)
      import
        class(any_t), intent(in) :: object
        integer, intent(in), optional :: unit, indent
    end subroutine any_write
  end interface

```

This is a container for a stable or unstable outgoing particle. We need this wrapper for preparing arrays that mix stable and unstable particles.

```

<Decays: types>+≡
  type :: particle_out_t
    class(any_t), allocatable :: c
  end type particle_out_t

```

28.3.3 Decay Term Configuration

A decay term is a distinct final state, corresponding to a process term. Each decay process may give rise to several terms with, possibly, differing flavor content.

```

<Decays: types>+≡
  type :: decay_term_config_t
    type(particle_config_t), dimension(:), allocatable :: prt
    contains
      <Decays: decay term config: TBP>
    end type decay_term_config_t

```

Finalizer, recursive.

```

<Decays: decay term config: TBP>≡
  procedure :: final => decay_term_config_final

<Decays: procedures>≡
  recursive subroutine decay_term_config_final (object)
    class(decay_term_config_t), intent(inout) :: object
    integer :: i
    if (allocated (object%prt)) then
      do i = 1, size (object%prt)
        if (allocated (object%prt(i)%c)) call object%prt(i)%c%final ()
      end do
    end if
  end subroutine decay_term_config_final

```

```

        end do
    end if
end subroutine decay_term_config_final

```

Output, with optional indentation

<Decays: decay term config: TBP>+≡

```

    procedure :: write => decay_term_config_write

```

<Decays: procedures>+≡

```

recursive subroutine decay_term_config_write (object, unit, indent, verbose)
    class(decay_term_config_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    logical, intent(in), optional :: verbose
    integer :: i, j, u, ind
    logical :: verb
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    verb = .true.; if (present (verbose)) verb = verbose
    call write_indent (u, ind)
    write (u, "(1x,A)", advance="no") "Final state:"
    do i = 1, size (object%prt)
        select type (prt_config => object%prt(i)%c)
            type is (stable_config_t)
                write (u, "(1x,A)", advance="no") &
                    char (prt_config%flv(1)%get_name ())
                do j = 2, size (prt_config%flv)
                    write (u, "(:',A)", advance="no") &
                        char (prt_config%flv(j)%get_name ())
                end do
            type is (unstable_config_t)
                write (u, "(1x,A)", advance="no") &
                    char (prt_config%flv%get_name ())
        end select
    end do
    write (u, *)
    if (verb) then
        do i = 1, size (object%prt)
            call object%prt(i)%c%write (u, ind)
        end do
    end if
end subroutine decay_term_config_write

```

Initialize, given a set of flavors. For each flavor, we must indicate whether the particle is stable. The second index of the flavor array runs over alternatives for each decay product; alternatives are allowed only if the decay product is itself stable.

<Decays: decay term config: TBP>+≡

```

    procedure :: init => decay_term_config_init

```

<Decays: procedures>+≡

```

recursive subroutine decay_term_config_init &
    (term, flv, stable, model, process_stack)
    class(decay_term_config_t), intent(out) :: term
    type(flavor_t), dimension(:, :), intent(in) :: flv

```

```

logical, dimension(:), intent(in) :: stable
class(model_data_t), intent(in), target :: model
type(process_stack_t), intent(in), optional :: process_stack
type(string_t), dimension(:), allocatable :: decay
integer :: i
allocate (term%prt (size (flv, 1)))
do i = 1, size (flv, 1)
  associate (prt => term%prt(i))
    if (stable(i)) then
      allocate (stable_config_t :: prt%c)
    else
      allocate (unstable_config_t :: prt%c)
    end if
    select type (prt_config => prt%c)
    type is (stable_config_t)
      call prt_config%init (flv(i,:))
    type is (unstable_config_t)
      if (all (flv(i,:) == flv(i,1))) then
        call prt_config%init (flv(i,1))
        call flv(i,1)%get_decays (decay)
        call prt_config%init_decays (decay, model, process_stack)
      else
        call prt_config%write ()
        call msg_fatal ("Decay configuration: &
          &unstable product must be unique")
      end if
    end select
  end associate
end do
end subroutine decay_term_config_init

```

Recursively compute widths and branching ratios for all unstable particles.

```

<Decays: decay term config: TBP>+≡
  procedure :: compute => decay_term_config_compute

<Decays: procedures>+≡
  recursive subroutine decay_term_config_compute (term)
    class(decay_term_config_t), intent(inout) :: term
    integer :: i
    do i = 1, size (term%prt)
      select type (unstable_config => term%prt(i)%c)
      type is (unstable_config_t)
        call unstable_config%compute ()
      end select
    end do
  end subroutine decay_term_config_compute

```

28.3.4 Decay Term

A decay term instance is selected when we generate an event for the associated process instance. When evaluated, it triggers further decays down the chain.

Only unstable products are allocated as child particles.

```

<Decays: types>+≡
  type :: decay_term_t
    type(decay_term_config_t), pointer :: config => null ()
    type(particle_out_t), dimension(:), allocatable :: particle_out
    contains
    <Decays: decay term: TBP>
  end type decay_term_t

```

Finalizer.

```

<Decays: decay term: TBP>≡
  procedure :: final => decay_term_final

<Decays: procedures>+≡
  recursive subroutine decay_term_final (object)
    class(decay_term_t), intent(inout) :: object
    integer :: i
    if (allocated (object%particle_out)) then
      do i = 1, size (object%particle_out)
        call object%particle_out(i)%c%final ()
      end do
    end if
  end subroutine decay_term_final

```

Output.

```

<Decays: decay term: TBP>+≡
  procedure :: write => decay_term_write

<Decays: procedures>+≡
  recursive subroutine decay_term_write (object, unit, indent)
    class(decay_term_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    integer :: i, u, ind
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    call object%config%write (u, ind, verbose = .false.)
    do i = 1, size (object%particle_out)
      call object%particle_out(i)%c%write (u, ind)
    end do
  end subroutine decay_term_write

```

Recursively write the embedded process instances.

```

<Decays: decay term: TBP>+≡
  procedure :: write_process_instances => decay_term_write_process_instances

<Decays: procedures>+≡
  recursive subroutine decay_term_write_process_instances (term, unit, verbose)
    class(decay_term_t), intent(in) :: term
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: i
    do i = 1, size (term%particle_out)
      select type (unstable => term%particle_out(i)%c)

```

```

        type is (unstable_t)
        call unstable%write_process_instances (unit, verbose)
    end select
end do
end subroutine decay_term_write_process_instances

```

Initialization, using the configuration object. We allocate particle objects in parallel to the particle configuration objects which we use to initialize them, one at a time.

```

<Decays: decay term: TBP>+≡
    procedure :: init => decay_term_init

<Decays: procedures>+≡
    recursive subroutine decay_term_init (term, config)
        class(decay_term_t), intent(out) :: term
        type(decay_term_config_t), intent(in), target :: config
        integer :: i
        term%config => config
        allocate (term%particle_out (size (config%prt)))
        do i = 1, size (config%prt)
            select type (prt_config => config%prt(i)%c)
            type is (stable_config_t)
                allocate (stable_t :: term%particle_out(i)%c)
                select type (stable => term%particle_out(i)%c)
                type is (stable_t)
                    call stable%init (prt_config)
                end select
            type is (unstable_config_t)
                allocate (unstable_t :: term%particle_out(i)%c)
                select type (unstable => term%particle_out(i)%c)
                type is (unstable_t)
                    call unstable%init (prt_config)
                end select
            end select
        end do
    end subroutine decay_term_init

```

Implement a RNG instance, spawned by the process object.

```

<Decays: decay term: TBP>+≡
    procedure :: make_rng => decay_term_make_rng

<Decays: procedures>+≡
    subroutine decay_term_make_rng (term, process)
        class(decay_term_t), intent(inout) :: term
        type(process_t), intent(inout) :: process
        class(rng_t), allocatable :: rng
        integer :: i
        do i = 1, size (term%particle_out)
            select type (unstable => term%particle_out(i)%c)
            type is (unstable_t)
                call process%make_rng (rng)
                call unstable%import_rng (rng)
            end select
        end do
    end subroutine decay_term_make_rng

```

```
end subroutine decay_term_make_rng
```

Link the interactions for unstable decay products to the interaction of the parent process.

```
<Decays: decay term: TBP>+≡
  procedure :: link_interactions => decay_term_link_interactions

<Decays: procedures>+≡
  recursive subroutine decay_term_link_interactions (term, trace)
    class(decay_term_t), intent(inout) :: term
    type(interaction_t), intent(in), target :: trace
    integer :: i
    do i = 1, size (term%particle_out)
      select type (unstable => term%particle_out(i)%c)
        type is (unstable_t)
          call unstable%link_interactions (i, trace)
        end select
      end do
    end subroutine decay_term_link_interactions
```

Recursively generate a decay chain, for each of the unstable particles in the final state.

```
<Decays: decay term: TBP>+≡
  procedure :: select_chain => decay_term_select_chain

<Decays: procedures>+≡
  recursive subroutine decay_term_select_chain (term)
    class(decay_term_t), intent(inout) :: term
    integer :: i
    do i = 1, size (term%particle_out)
      select type (unstable => term%particle_out(i)%c)
        type is (unstable_t)
          call unstable%select_chain ()
        end select
      end do
    end subroutine decay_term_select_chain
```

Recursively generate a decay event, for each of the unstable particles in the final state.

```
<Decays: decay term: TBP>+≡
  procedure :: generate => decay_term_generate

<Decays: procedures>+≡
  recursive subroutine decay_term_generate (term)
    class(decay_term_t), intent(inout) :: term
    integer :: i
    do i = 1, size (term%particle_out)
      select type (unstable => term%particle_out(i)%c)
        type is (unstable_t)
          call unstable%generate ()
        end select
      end do
    end subroutine decay_term_generate
```

28.3.5 Decay Root Configuration

At the root of a decay chain, there is a parent process. The decay root stores a pointer to the parent process and the set of decay configurations.

```

<Decays: types>+≡
  type :: decay_root_config_t
    type(string_t) :: process_id
    type(process_t), pointer :: process => null ()
    class(model_data_t), pointer :: model => null ()
    type(decay_term_config_t), dimension(:), allocatable :: term_config
  contains
    <Decays: decay root config: TBP>
  end type decay_root_config_t

```

The finalizer is recursive since there may be cascade decays.

```

<Decays: decay root config: TBP>≡
  procedure :: final => decay_root_config_final

<Decays: procedures>+≡
  recursive subroutine decay_root_config_final (object)
    class(decay_root_config_t), intent(inout) :: object
    integer :: i
    if (allocated (object%term_config)) then
      do i = 1, size (object%term_config)
        call object%term_config(i)%final ()
      end do
    end if
  end subroutine decay_root_config_final

```

The output routine is also recursive, and it contains an adjustable indentation.

```

<Decays: decay root config: TBP>+≡
  procedure :: write => decay_root_config_write
  procedure :: write_header => decay_root_config_write_header
  procedure :: write_terms => decay_root_config_write_terms

<Decays: procedures>+≡
  recursive subroutine decay_root_config_write (object, unit, indent, verbose)
    class(decay_root_config_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    logical, intent(in), optional :: verbose
    integer :: u, ind
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    call write_indent (u, ind)
    write (u, "(1x,A)") "Final-state decay tree:"
    call object%write_header (unit, indent)
    call object%write_terms (unit, indent, verbose)
  end subroutine decay_root_config_write

  subroutine decay_root_config_write_header (object, unit, indent)
    class(decay_root_config_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    integer :: u, ind
    u = given_output_unit (unit)

```

```

ind = 0; if (present (indent)) ind = indent
call write_indent (u, ind)
if (associated (object%process)) then
    write (u, 3) "process ID      =", char (object%process_id), "*"
else
    write (u, 3) "process ID      =", char (object%process_id)
end if
3  format (3x,A,2(1x,A))
end subroutine decay_root_config_write_header

recursive subroutine decay_root_config_write_terms &
    (object, unit, indent, verbose)
    class(decay_root_config_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    logical, intent(in), optional :: verbose
    integer :: i, u, ind
    logical :: verb
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    verb = .true.; if (present (verbose)) verb = verbose
    if (verb .and. allocated (object%term_config)) then
        do i = 1, size (object%term_config)
            call object%term_config(i)%write (u, ind + 1)
        end do
    end if
end subroutine decay_root_config_write_terms

```

Initialize for a named process and (optionally) a pre-determined number of terms.

```

<Decays: decay root config: TBP>+≡
    procedure :: init => decay_root_config_init

<Decays: procedures>+≡
    subroutine decay_root_config_init (decay, model, process_id, n_terms)
        class(decay_root_config_t), intent(out) :: decay
        class(model_data_t), intent(in), target :: model
        type(string_t), intent(in) :: process_id
        integer, intent(in), optional :: n_terms
        decay%model => model
        decay%process_id = process_id
        if (present (n_terms)) then
            allocate (decay%term_config (n_terms))
        end if
    end subroutine decay_root_config_init

```

Declare a decay term, given an array of flavors.

```

<Decays: decay root config: TBP>+≡
    procedure :: init_term => decay_root_config_init_term

<Decays: procedures>+≡
    recursive subroutine decay_root_config_init_term &
        (decay, i, flv, stable, model, process_stack)
        class(decay_root_config_t), intent(inout) :: decay
        integer, intent(in) :: i

```

```

type(flavor_t), dimension(:,:), intent(in) :: flv
logical, dimension(:), intent(in) :: stable
class(model_data_t), intent(in), target :: model
type(process_stack_t), intent(in), optional :: process_stack
call decay%term_config(i)%init (flv, stable, model, process_stack)
end subroutine decay_root_config_init_term

```

Connect the decay root configuration with a process object (which should represent the parent process). This includes initialization, therefore intent(out).

The flavor state is retrieved from the process term object. However, we have to be careful: the flavor object points to the model instance that is stored in the process object. This model instance may not contain the current setting for unstable particles and decay. Therefore, we assign the model directly.

If the `process_instance` argument is provided, we use this for the flavor state. This applies to the decay root only, where the process can be entangled with a beam setup, and the latter contains beam remnants as further outgoing particles. These must be included in the set of outgoing flavors, since the decay application is also done on the connected state.

Infer stability from the particle properties, using the first row in the set of flavor states. For unstable particles, we look for decays, recursively, available from the process stack (if present).

<Decays: decay root config: TBP>+≡

```

procedure :: connect => decay_root_config_connect

```

<Decays: procedures>+≡

```

recursive subroutine decay_root_config_connect &
    (decay, process, model, process_stack, process_instance)
class(decay_root_config_t), intent(out) :: decay
type(process_t), intent(in), target :: process
class(model_data_t), intent(in), target :: model
type(process_stack_t), intent(in), optional :: process_stack
type(process_instance_t), intent(in), optional, target :: process_instance
type(connected_state_t), pointer :: connected_state
type(interaction_t), pointer :: int
type(flavor_t), dimension(:,:), allocatable :: flv
logical, dimension(:), allocatable :: stable
integer :: i
call decay%init (model, process%get_id (), process%get_n_terms ())
do i = 1, size (decay%term_config)
    if (present (process_instance)) then
        connected_state => process_instance%get_connected_state_ptr (i)
        int => connected_state%get_matrix_int_ptr ()
        call interaction_get_flv_out (int, flv)
    else
        call process%get_term_flv_out (i, flv)
    end if
    call flv%set_model (model)
    allocate (stable (size (flv, 1)))
    stable = flv(:,1)%is_stable ()
    call decay%init_term (i, flv, stable, model, process_stack)
    deallocate (flv, stable)
end do
decay%process => process

```

```
end subroutine decay_root_config_connect
```

Recursively compute widths, errors, and branching ratios.

```
<Decays: decay root config: TBP>+≡
  procedure :: compute => decay_root_config_compute

<Decays: procedures>+≡
  recursive subroutine decay_root_config_compute (decay)
    class(decay_root_config_t), intent(inout) :: decay
    integer :: i
    do i = 1, size (decay%term_config)
      call decay%term_config(i)%compute ()
    end do
  end subroutine decay_root_config_compute
```

28.3.6 Decay Root Instance

This is the common parent type for decay and decay root. The process instance points to the parent process. The model pointer is separate because particle settings may be updated w.r.t. the parent process object.

```
<Decays: types>+≡
  type, abstract :: decay_gen_t
    type(decay_term_t), dimension(:), allocatable :: term
    type(process_instance_t), pointer :: process_instance => null ()
    integer :: selected_mci = 0
    integer :: selected_term = 0
  contains
    <Decays: decay gen: TBP>
  end type decay_gen_t
```

The decay root represents the parent process. When an event is generated, the generator selects the term to which the decay chain applies (if possible).

The process instance is just a pointer.

```
<Decays: types>+≡
  type, extends (decay_gen_t) :: decay_root_t
    type(decay_root_config_t), pointer :: config => null ()
  contains
    <Decays: decay root: TBP>
  end type decay_root_t
```

The finalizer has to recursively finalize the terms, but we can skip the process instance which is not explicitly allocated.

```
<Decays: decay gen: TBP>≡
  procedure :: base_final => decay_gen_final

<Decays: procedures>+≡
  recursive subroutine decay_gen_final (object)
    class(decay_gen_t), intent(inout) :: object
    integer :: i
    if (allocated (object%term)) then
      do i = 1, size (object%term)
```

```

        call object%term(i)%final ()
    end do
end if
end subroutine decay_gen_final

```

No extra finalization for the decay root.

```

<Decays: decay root: TBP>≡
    procedure :: final => decay_root_final

<Decays: procedures>+≡
    subroutine decay_root_final (object)
        class(decay_root_t), intent(inout) :: object
        call object%base_final ()
    end subroutine decay_root_final

```

Output.

```

<Decays: decay root: TBP>+≡
    procedure :: write => decay_root_write

<Decays: procedures>+≡
    subroutine decay_root_write (object, unit)
        class(decay_root_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        if (associated (object%config)) then
            call object%config%write (unit, verbose = .false.)
        else
            write (u, "(1x,A)") "Final-state decay tree: [not configured]"
        end if
        if (object%selected_mci > 0) then
            write (u, "(3x,A,I0)") "Selected MCI      = ", object%selected_mci
        else
            write (u, "(3x,A)") "Selected MCI      = [undefined]"
        end if
        if (object%selected_term > 0) then
            write (u, "(3x,A,I0)") "Selected term    = ", object%selected_term
            call object%term(object%selected_term)%write (u, 1)
        else
            write (u, "(3x,A)") "Selected term    = [undefined]"
        end if
    end subroutine decay_root_write

```

Write the process instances, recursively.

```

<Decays: decay gen: TBP>+≡
    procedure :: write_process_instances => decay_gen_write_process_instances

<Decays: procedures>+≡
    recursive subroutine decay_gen_write_process_instances (decay, unit, verbose)
        class(decay_gen_t), intent(in) :: decay
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        logical :: verb
        verb = .true.; if (present (verbose)) verb = verbose

```



```

    if (associated (decay%process_instance)) then
      if (verb) then
        call decay%process_instance%write (unit)
      else
        call decay%process_instance%write_header (unit)
      end if
    end if
    if (decay%selected_term > 0) then
      call decay%term(decay%selected_term)%write_process_instances (unit, verb)
    end if
  end subroutine decay_gen_write_process_instances

```

Generic initializer. All can be done recursively.

```

<Decays: decay gen: TBP>+≡
  procedure :: base_init => decay_gen_init

<Decays: procedures>+≡
  recursive subroutine decay_gen_init (decay, term_config)
    class(decay_gen_t), intent(out) :: decay
    type(decay_term_config_t), dimension(:), intent(in), target :: term_config
    integer :: i
    allocate (decay%term (size (term_config)))
    do i = 1, size (decay%term)
      call decay%term(i)%init (term_config(i))
    end do
  end subroutine decay_gen_init

```

Specific initializer. We assign the configuration object, which should correspond to a completely initialized decay configuration tree. We also connect to an existing process instance. Then, we recursively link the child interactions to the parent process.

```

<Decays: decay root: TBP>+≡
  procedure :: init => decay_root_init

<Decays: procedures>+≡
  subroutine decay_root_init (decay_root, config, process_instance)
    class(decay_root_t), intent(out) :: decay_root
    type(decay_root_config_t), intent(in), target :: config
    type(process_instance_t), intent(in), target :: process_instance
    call decay_root%base_init (config%term_config)
    decay_root%config => config
    decay_root%process_instance => process_instance
    call decay_root%make_term_rng (config%process)
    call decay_root%link_term_interactions ()
  end subroutine decay_root_init

```

Implement random-number generators for unstable decay selection in all terms. This is not recursive.

We also make use of the fact that `process` is a pointer; the (state of the RNG factory inside the) target process will be modified by the `rng-spawning` method, but not the pointer.

```

<Decays: decay gen: TBP>+≡
  procedure :: make_term_rng => decay_gen_make_term_rng

```

```

<Decays: procedures>+≡
  subroutine decay_gen_make_term_rng (decay, process)
    class(decay_gen_t), intent(inout) :: decay
    type(process_t), intent(in), pointer :: process
    integer :: i
    do i = 1, size (decay%term)
      call decay%term(i)%make_rng (process)
    end do
  end subroutine decay_gen_make_term_rng

```

Recursively link interactions of the enclosed decay terms to the corresponding terms in the current process instance.

Note: A bug in nagfor requires the extra `i_term` variable.

```

<Decays: decay gen: TBP>+≡
  procedure :: link_term_interactions => decay_gen_link_term_interactions

<Decays: procedures>+≡
  recursive subroutine decay_gen_link_term_interactions (decay)
    class(decay_gen_t), intent(inout) :: decay
    integer :: i, i_term
    type(interaction_t), pointer :: trace
    associate (instance => decay%process_instance)
      do i = 1, size (decay%term)
        i_term = i
        trace => instance%get_trace_int_ptr (i_term)
        call decay%term(i_term)%link_interactions (trace)
      end do
    end associate
  end subroutine decay_gen_link_term_interactions

```

Select a decay chain: decay modes and process components.

```

<Decays: decay root: TBP>+≡
  procedure :: select_chain => decay_root_select_chain

<Decays: procedures>+≡
  subroutine decay_root_select_chain (decay_root)
    class(decay_root_t), intent(inout) :: decay_root
    if (decay_root%selected_term > 0) then
      call decay_root%term(decay_root%selected_term)%select_chain ()
    else
      call msg_bug ("Decays: no term selected for parent process")
    end if
  end subroutine decay_root_select_chain

```

Generate a decay tree, i.e., for the selected term in the parent process, recursively generate a decay event for all unstable particles.

Factor out the trace of the connected state of the parent process. This trace should not be taken into account for unweighting the decay chain, since it was already used for unweighting the parent event, or it determines the overall event weight.

```

<Decays: decay root: TBP>+≡
  procedure :: generate => decay_root_generate

```

```

<Decays: procedures>+≡
  subroutine decay_root_generate (decay_root)
    class(decay_root_t), intent(inout) :: decay_root
    type(connected_state_t), pointer :: connected_state
    if (decay_root%selected_term > 0) then
      connected_state => decay_root%process_instance%get_connected_state_ptr &
        (decay_root%selected_term)
      call connected_state%normalize_matrix_by_trace ()
      call decay_root%term(decay_root%selected_term)%generate ()
    else
      call msg_bug ("Decays: no term selected for parent process")
    end if
  end subroutine decay_root_generate

```

28.3.7 Decay Configuration

A decay configuration describes a distinct decay mode of a particle. Each decay mode may include several terms, which correspond to the terms in the associated process. In addition to the base type, the decay configuration object contains the integral of the parent process and the selector for the MCI group inside this process.

The flavor component should be identical to the flavor component of the parent particle (*unstable* object).

```

<Decays: types>+≡
  type, extends (decay_root_config_t) :: decay_config_t
    type(flavor_t) :: flv
    real(default) :: weight = 0
    real(default) :: integral = 0
    real(default) :: abs_error = 0
    real(default) :: rel_error = 0
    type(selector_t) :: mci_selector
  contains
    <Decays: decay config: TBP>
  end type decay_config_t

```

The output routine extends the decay-root writer by listing numerical component values.

```

<Decays: decay config: TBP>≡
  procedure :: write => decay_config_write

<Decays: procedures>+≡
  recursive subroutine decay_config_write (object, unit, indent, verbose)
    class(decay_config_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    logical, intent(in), optional :: verbose
    integer :: u, ind
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    call write_indent (u, ind)
    write (u, "(1x,A)") "Decay:"
    call object%write_header (unit, indent)
    call write_indent (u, ind)

```

```

        write (u, 2) "branching ratio =", object%weight * 100
        call write_indent (u, ind)
        write (u, 1) "partial width   =", object%integral
        call write_indent (u, ind)
        write (u, 1) "error (abs)      =", object%abs_error
        call write_indent (u, ind)
        write (u, 1) "error (rel)      =", object%rel_error
1   format (3x,A,ES19.12)
2   format (3x,A,F11.6,1x,'%')
        call object%write_terms (unit, indent, verbose)
    end subroutine decay_config_write

```

Connect a decay configuration with a process object (which should represent the decay). This includes initialization, therefore intent(out). We first connect the process itself, then do initializations that are specific for this decay.

Infer stability from the particle properties, using the first row in the set of flavor states. Once we can deal with predetermined decay chains, they should be used instead.

```

<Decays: decay config: TBP>+≡
    procedure :: connect => decay_config_connect

<Decays: procedures>+≡
    recursive subroutine decay_config_connect &
        (decay, process, model, process_stack, process_instance)
        class(decay_config_t), intent(out) :: decay
        type(process_t), intent(in), target :: process
        class(model_data_t), intent(in), target :: model
        type(process_stack_t), intent(in), optional :: process_stack
        type(process_instance_t), intent(in), optional, target :: process_instance
        real(default), dimension(:), allocatable :: integral_mci
        integer :: i, n_mci
        call decay%decay_root_config_t%connect (process, model, process_stack)
        decay%integral = process%get_integral ()
        decay%abs_error = process%get_error ()
        if (process%cm_frame ()) then
            call msg_fatal ("Decay process " // char (process%get_id ()) &
                // ": unusable because rest frame is fixed.")
        end if
        n_mci = process%get_n_mci ()
        allocate (integral_mci (n_mci))
        do i = 1, n_mci
            integral_mci(i) = process%get_integral_mci (i)
        end do
        call decay%mci_selector%init (integral_mci)
    end subroutine decay_config_connect

```

Set the flavor entry, which repeats the flavor of the parent unstable particle.

```

<Decays: decay config: TBP>+≡
    procedure :: set_flv => decay_config_set_flv

<Decays: procedures>+≡
    subroutine decay_config_set_flv (decay, flv)
        class(decay_config_t), intent(inout) :: decay

```

```

    type(flavor_t), intent(in) :: flv
    decay%flv = flv
end subroutine decay_config_set_flv

```

Compute embedded branchings and the relative error. This method does not apply to the decay root.

```

<Decays: decay config: TBP>+≡
    procedure :: compute => decay_config_compute

<Decays: procedures>+≡
    recursive subroutine decay_config_compute (decay)
        class(decay_config_t), intent(inout) :: decay
        call decay%decay_root_config_t%compute ()
        if (.not. vanishes (decay%integral)) then
            decay%rel_error = decay%abs_error / decay%integral
        else
            decay%rel_error = 0
        end if
    end subroutine decay_config_compute

```

28.3.8 Decay Instance

The decay contains a collection of terms. One of them is selected when the decay is evaluated. This is similar to the decay root, but we implement it independently.

The process instance object is allocated via a pointer, so it automatically behaves as a target.

```

<Decays: types>+≡
    type, extends (decay_gen_t) :: decay_t
        type(decay_config_t), pointer :: config => null ()
        class(rng_t), allocatable :: rng
    contains
        <Decays: decay: TBP>
    end type decay_t

```

The finalizer is recursive.

```

<Decays: decay: TBP>≡
    procedure :: final => decay_final

<Decays: procedures>+≡
    recursive subroutine decay_final (object)
        class(decay_t), intent(inout) :: object
        integer :: i
        call object%base_final ()
        do i = 1, object%config%process%get_n_mci ()
            call object%process_instance%final_simulation (i)
        end do
        call object%process_instance%final ()
        deallocate (object%process_instance)
    end subroutine decay_final

```

Output.

```

<Decays: decay: TBP>+≡
  procedure :: write => decay_write

<Decays: procedures>+≡
  recursive subroutine decay_write (object, unit, indent, recursive)
    class(decay_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent, recursive
    integer :: u, ind
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    call object%config%write (unit, indent, verbose = .false.)
    if (allocated (object%rng)) then
      call object%rng%write (u, ind + 1)
    end if
    call write_indent (u, ind)
    if (object%selected_mci > 0) then
      write (u, "(3x,A,I0)") "Selected MCI      = ", object%selected_mci
    else
      write (u, "(3x,A)") "Selected MCI      = [undefined]"
    end if
    call write_indent (u, ind)
    if (object%selected_term > 0) then
      write (u, "(3x,A,I0)") "Selected term    = ", object%selected_term
      call object%term(object%selected_term)%write (u, ind + 1)
    else
      write (u, "(3x,A)") "Selected term    = [undefined]"
    end if
  end subroutine decay_write

```

Initializer. Base initialization is done recursively. Then, we prepare the current process instance and allocate a random-number generator for term selection. For all unstable particles, we also allocate a r.n.g. as spawned by the current process.

```

<Decays: decay: TBP>+≡
  procedure :: init => decay_init

<Decays: procedures>+≡
  recursive subroutine decay_init (decay, config)
    class(decay_t), intent(out) :: decay
    type(decay_config_t), intent(in), target :: config
    integer :: i
    call decay%base_init (config%term_config)
    decay%config => config
    allocate (decay%process_instance)
    call decay%process_instance%init (decay%config%process)
    call decay%process_instance%setup_event_data (decay%config%model)
    do i = 1, decay%config%process%get_n_mci ()
      call decay%process_instance%init_simulation (i)
    end do
    call decay%config%process%make_rng (decay%rng)
    call decay%make_term_rng (decay%config%process)
  end subroutine decay_init

```

Link interactions to the parent process. `i_prt` is the index of the current outgoing particle in the parent interaction, for which we take the trace evaluator. We link it to the beam particle in the beam interaction of the decay process instance. Then, repeat the procedure for the outgoing particles.

```

<Decays: decay: TBP>+≡
  procedure :: link_interactions => decay_link_interactions

<Decays: procedures>+≡
  recursive subroutine decay_link_interactions (decay, i_prt, trace)
    class(decay_t), intent(inout) :: decay
    integer, intent(in) :: i_prt
    type(interaction_t), intent(in), target :: trace
    type(interaction_t), pointer :: beam_int
    integer :: n_in, n_vir
    beam_int => decay%process_instance%get_beam_int_ptr ()
    n_in = trace%get_n_in ()
    n_vir = trace%get_n_vir ()
    call beam_int%set_source_link (1, trace, &
      n_in + n_vir + i_prt)
    call decay%link_term_interactions ()
  end subroutine decay_link_interactions

```

Determine a decay chain. For each unstable particle we select one of the possible decay modes, and for each decay process we select one of the possible decay MCI components, calling the random-number generators. We do not generate momenta, yet.

```

<Decays: decay: TBP>+≡
  procedure :: select_chain => decay_select_chain

<Decays: procedures>+≡
  recursive subroutine decay_select_chain (decay)
    class(decay_t), intent(inout) :: decay
    real(default) :: x
    integer :: i
    call decay%rng%generate (x)
    decay%selected_mci = decay%config%mc_selector%select (x)
    call decay%process_instance%choose_mci (decay%selected_mci)
    call decay%process_instance%select_i_term (decay%selected_term)
    do i = 1, size (decay%term)
      call decay%term(i)%select_chain ()
    end do
  end subroutine decay_select_chain

```

Generate a decay. We first receive the beam momenta from the parent process (assuming that this is properly linked), then call the associated process object for a new event.

Factor out the trace of the helicity density matrix of the isolated state (the one that will be used for the decay chain). The trace is taken into account for unweighting the individual decay event and should therefore be ignored for unweighting the correlated decay chain afterwards.

```

<Decays: decay: TBP>+≡
  procedure :: generate => decay_generate

```

```

<Decays: procedures>+≡
recursive subroutine decay_generate (decay)
  class(decay_t), intent(inout) :: decay
  type(isolated_state_t), pointer :: isolated_state
  integer :: i
  call decay%process_instance%receive_beam_momenta ()
  call decay%config%process%generate_unweighted_event &
    (decay%process_instance, decay%selected_mci)
  if (signal_is_pending ()) return
  call decay%process_instance%evaluate_event_data ()
  isolated_state => &
    decay%process_instance%get_isolated_state_ptr (decay%selected_term)
  call isolated_state%normalize_matrix_by_trace ()
  do i = 1, size (decay%term)
    call decay%term(i)%generate ()
    if (signal_is_pending ()) return
  end do
end subroutine decay_generate

```

28.3.9 Stable Particles

This is a stable particle. The flavor can be ambiguous (e.g., partons).

```

<Decays: types>+≡
type, extends (any_config_t) :: stable_config_t
  type(flavor_t), dimension(:), allocatable :: flv
contains
  <Decays: stable config: TBP>
end type stable_config_t

```

The finalizer is empty:

```

<Decays: stable config: TBP>≡
  procedure :: final => stable_config_final

<Decays: procedures>+≡
  subroutine stable_config_final (object)
    class(stable_config_t), intent(inout) :: object
  end subroutine stable_config_final

```

Output.

```

<Decays: stable config: TBP>+≡
  procedure :: write => stable_config_write

<Decays: procedures>+≡
recursive subroutine stable_config_write (object, unit, indent, verbose)
  class(stable_config_t), intent(in) :: object
  integer, intent(in), optional :: unit, indent
  logical, intent(in), optional :: verbose
  integer :: u, i, ind
  u = given_output_unit (unit)
  ind = 0; if (present (indent)) ind = indent
  call write_indent (u, ind)
  write (u, "(1x,'+',1x,A)", advance = "no") "Stable:"

```



```

write (u, "(1x,A)", advance = "no") char (object%flv(1)%get_name ())
do i = 2, size (object%flv)
  write (u, "(:',A)", advance = "no") &
    char (object%flv(i)%get_name ())
end do
write (u, *)
end subroutine stable_config_write

```

Initializer. We are presented with an array of flavors, but there may be double entries which we remove, so we store only the distinct flavors.

```

<Decays: stable config: TBP>+≡
  procedure :: init => stable_config_init

<Decays: procedures>+≡
  subroutine stable_config_init (config, flv)
    class(stable_config_t), intent(out) :: config
    type(flavor_t), dimension(:), intent(in) :: flv
    integer, dimension (size (flv)) :: pdg
    logical, dimension (size (flv)) :: mask
    integer :: i
    pdg = flv%get_pdg ()
    mask(1) = .true.
    forall (i = 2 : size (pdg))
      mask(i) = all (pdg(i) /= pdg(1:i-1))
    end forall
    allocate (config%flv (count (mask)))
    config%flv = pack (flv, mask)
  end subroutine stable_config_init

```

Here is the corresponding object instance. Except for the pointer to the configuration, there is no content.

```

<Decays: types>+≡
  type, extends (any_t) :: stable_t
    type(stable_config_t), pointer :: config => null ()
  contains
    <Decays: stable: TBP>
  end type stable_t

```

The finalizer does nothing.

```

<Decays: stable: TBP>≡
  procedure :: final => stable_final

<Decays: procedures>+≡
  subroutine stable_final (object)
    class(stable_t), intent(inout) :: object
  end subroutine stable_final

```

We can delegate output to the configuration object.

```

<Decays: stable: TBP>+≡
  procedure :: write => stable_write

```

```

<Decays: procedures>+≡
  subroutine stable_write (object, unit, indent)
    class(stable_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    call object%config%write (unit, indent)
  end subroutine stable_write

```

Initializer: just assign the configuration.

```

<Decays: stable: TBP>+≡
  procedure :: init => stable_init

<Decays: procedures>+≡
  subroutine stable_init (stable, config)
    class(stable_t), intent(out) :: stable
    type(stable_config_t), intent(in), target :: config
    stable%config => config
  end subroutine stable_init

```

28.3.10 Unstable Particles

A branching configuration enables us to select among distinct decay modes of a particle. We store the particle flavor (with its implicit link to a model), an array of decay configurations, and a selector object.

The total width, absolute and relative error are stored as `integral`, `abs_error`, and `rel_error`, respectively.

The flavor must be unique in this case.

```

<Decays: types>+≡
  type, extends (any_config_t) :: unstable_config_t
    type(flavor_t) :: flv
    real(default) :: integral = 0
    real(default) :: abs_error = 0
    real(default) :: rel_error = 0
    type(selector_t) :: selector
    type(decay_config_t), dimension(:), allocatable :: decay_config
  contains
    <Decays: unstable config: TBP>
  end type unstable_config_t

```

Finalizer. The branching configuration can be a recursive structure.

```

<Decays: unstable config: TBP>≡
  procedure :: final => unstable_config_final

<Decays: procedures>+≡
  recursive subroutine unstable_config_final (object)
    class(unstable_config_t), intent(inout) :: object
    integer :: i
    if (allocated (object%decay_config)) then
      do i = 1, size (object%decay_config)
        call object%decay_config(i)%final ()
      end do
    end if
  end subroutine

```

```
end subroutine unstable_config_final
```

Output. Since this may be recursive, we include indentation.

```
<Decays: unstable config: TBP>+≡
  procedure :: write => unstable_config_write

<Decays: procedures>+≡
  recursive subroutine unstable_config_write (object, unit, indent, verbose)
    class(unstable_config_t), intent(in) :: object
    integer, intent(in), optional :: unit, indent
    logical, intent(in), optional :: verbose
    integer :: u, i, ind
    logical :: verb
    u = given_output_unit (unit)
    ind = 0; if (present (indent)) ind = indent
    verb = .true.; if (present (verbose)) verb = verbose
    call write_indent (u, ind)
    write (u, "(1x,'+',1x,A,1x,A)") "Unstable:", &
      char (object%flv%get_name ())
    call write_indent (u, ind)
    write (u, 1) "total width =", object%integral
    call write_indent (u, ind)
    write (u, 1) "error (abs) =", object%abs_error
    call write_indent (u, ind)
    write (u, 1) "error (rel) =", object%rel_error
1  format (5x,A,ES19.12)
    if (verb .and. allocated (object%decay_config)) then
      do i = 1, size (object%decay_config)
        call object%decay_config(i)%write (u, ind + 1)
      end do
    end if
  end subroutine unstable_config_write
```

Initializer. For the unstable particle, the flavor is unique.

```
<Decays: unstable config: TBP>+≡
  procedure :: init => unstable_config_init

<Decays: procedures>+≡
  subroutine unstable_config_init (config, flv)
    class(unstable_config_t), intent(out) :: config
    type(flavor_t), intent(in) :: flv
    config%flv = flv
  end subroutine unstable_config_init
```

Further initialization: determine the number of decay modes. We can assume that the flavor of the particle has been set already.

If the process stack is given, we can delve recursively into actually assigning decay processes. Otherwise, we just initialize with decay process names.

```
<Decays: unstable config: TBP>+≡
  procedure :: init_decays => unstable_config_init_decays
```

```

<Decays: procedures>+≡
recursive subroutine unstable_config_init_decays &
  (unstable, decay_id, model, process_stack)
  class(unstable_config_t), intent(inout) :: unstable
  type(string_t), dimension(:), intent(in) :: decay_id
  class(model_data_t), intent(in), target :: model
  type(process_stack_t), intent(in), optional :: process_stack
  integer :: i
  allocate (unstable%decay_config (size (decay_id)))
  do i = 1, size (decay_id)
    associate (decay => unstable%decay_config(i))
      if (present (process_stack)) then
        call decay%connect (process_stack%get_process_ptr (decay_id(i)), &
          model, process_stack)
      else
        call decay%init (model, decay_id(i))
      end if
      call decay%set_flg (unstable%flv)
    end associate
  end do
end subroutine unstable_config_init_decays

```

Compute the total width and branching ratios, initializing the decay selector.

```

<Decays: unstable config: TBP>+≡
  procedure :: compute => unstable_config_compute

<Decays: procedures>+≡
recursive subroutine unstable_config_compute (unstable)
  class(unstable_config_t), intent(inout) :: unstable
  integer :: i
  do i = 1, size (unstable%decay_config)
    call unstable%decay_config(i)%compute ()
  end do
  unstable%integral = sum (unstable%decay_config%integral)
  if (unstable%integral <= 0) then
    call unstable%write ()
    call msg_fatal ("Decay configuration: computed total width is zero")
  end if
  unstable%abs_error = sqrt (sum (unstable%decay_config%abs_error ** 2))
  unstable%rel_error = unstable%abs_error / unstable%integral
  call unstable%selector%init (unstable%decay_config%integral)
  do i = 1, size (unstable%decay_config)
    unstable%decay_config(i)%weight &
      = unstable%selector%get_weight (i)
  end do
end subroutine unstable_config_compute

```

Now we define the instance of an unstable particle.

```

<Decays: types>+≡
type, extends (any_t) :: unstable_t
  type(unstable_config_t), pointer :: config => null ()
  class(rng_t), allocatable :: rng
  integer :: selected_decay = 0

```

```

        type(decay_t), dimension(:), allocatable :: decay
    contains
        <Decays: unstable: TBP>
    end type unstable_t

```

Recursive finalizer.

```

<Decays: unstable: TBP>≡
    procedure :: final => unstable_final
<Decays: procedures>+≡
    recursive subroutine unstable_final (object)
        class(unstable_t), intent(inout) :: object
        integer :: i
        if (allocated (object%decay)) then
            do i = 1, size (object%decay)
                call object%decay(i)%final ()
            end do
        end if
    end subroutine unstable_final

```

Output.

```

<Decays: unstable: TBP>+≡
    procedure :: write => unstable_write
<Decays: procedures>+≡
    recursive subroutine unstable_write (object, unit, indent)
        class(unstable_t), intent(in) :: object
        integer, intent(in), optional :: unit, indent
        integer :: u, ind
        u = given_output_unit (unit)
        ind = 0; if (present (indent)) ind = indent
        call object%config%write (u, ind, verbose=.false.)
        if (allocated (object%rng)) then
            call object%rng%write (u, ind + 2)
        end if
        call write_indent (u, ind)
        if (object%selected_decay > 0) then
            write (u, "(5x,A,I0)") "Sel. decay = ", object%selected_decay
            call object%decay(object%selected_decay)%write (u, ind + 1)
        else
            write (u, "(5x,A)") "Sel. decay = [undefined]"
        end if
    end subroutine unstable_write

```

Write the embedded process instances.

```

<Decays: unstable: TBP>+≡
    procedure :: write_process_instances => unstable_write_process_instances
<Decays: procedures>+≡
    recursive subroutine unstable_write_process_instances &
        (unstable, unit, verbose)
        class(unstable_t), intent(in) :: unstable
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose

```

```

    if (unstable%selected_decay > 0) then
        call unstable%decay(unstable%selected_decay)% &
            write_process_instances (unit, verbose)
    end if
end subroutine unstable_write_process_instances

```

Initialization, using the configuration object.

```

<Decays: unstable: TBP>+≡
    procedure :: init => unstable_init

<Decays: procedures>+≡
    recursive subroutine unstable_init (unstable, config)
        class(unstable_t), intent(out) :: unstable
        type(unstable_config_t), intent(in), target :: config
        integer :: i
        unstable%config => config
        allocate (unstable%decay (size (config%decay_config)))
        do i = 1, size (config%decay_config)
            call unstable%decay(i)%init (config%decay_config(i))
        end do
    end subroutine unstable_init

```

Recursively link interactions to the parent process. `i_prt` is the index of the current outgoing particle in the parent interaction.

```

<Decays: unstable: TBP>+≡
    procedure :: link_interactions => unstable_link_interactions

<Decays: procedures>+≡
    recursive subroutine unstable_link_interactions (unstable, i_prt, trace)
        class(unstable_t), intent(inout) :: unstable
        integer, intent(in) :: i_prt
        type(interaction_t), intent(in), target :: trace
        integer :: i
        do i = 1, size (unstable%decay)
            call unstable%decay(i)%link_interactions (i_prt, trace)
        end do
    end subroutine unstable_link_interactions

```

Import the random-number generator state.

```

<Decays: unstable: TBP>+≡
    procedure :: import_rng => unstable_import_rng

<Decays: procedures>+≡
    subroutine unstable_import_rng (unstable, rng)
        class(unstable_t), intent(inout) :: unstable
        class(rng_t), intent(inout), allocatable :: rng
        call move_alloc (from = rng, to = unstable%rng)
    end subroutine unstable_import_rng

```

Generate a decay chain. First select a decay mode, then call the `select_chain` method of the selected mode.

```

<Decays: unstable: TBP>+≡
    procedure :: select_chain => unstable_select_chain

```

```

<Decays: procedures>+≡
  recursive subroutine unstable_select_chain (unstable)
    class(unstable_t), intent(inout) :: unstable
    real(default) :: x
    call unstable%rng%generate (x)
    unstable%selected_decay = unstable%config%selector%select (x)
    call unstable%decay(unstable%selected_decay)%select_chain ()
  end subroutine unstable_select_chain

```

Generate a decay event.

```

<Decays: unstable: TBP>+≡
  procedure :: generate => unstable_generate

<Decays: procedures>+≡
  recursive subroutine unstable_generate (unstable)
    class(unstable_t), intent(inout) :: unstable
    call unstable%decay(unstable%selected_decay)%generate ()
  end subroutine unstable_generate

```

28.3.11 Decay Chain

While the decay configuration tree and the decay tree are static entities (during a simulation run), the decay chain is dynamically generated for each event. The reason is that with the possibility of several decay modes for each particle, and several terms for each process, the total number of distinct decay chains is not under control.

Each entry in the decay chain is a connected parton state. The origin of the chain is a connected state in the parent process (not part of the chain itself). For each decay, mode and term chosen, we convolute this with the isolated (!) state of the current decay, to generate a new connected state. We accumulate this chain by recursively traversing the allocated decay tree. Whenever a particle decays, it becomes virtual and is replaced by its decay product, while all other particles stay in the parton state as spectators.

Technically, we implement the decay chain as a stack structure and include information from the associated decay object for easier debugging. This is a decay chain entry:

```

<Decays: types>+≡
  type, extends (connected_state_t) :: decay_chain_entry_t
    integer :: index = 0
    type(decay_config_t), pointer :: config => null ()
    integer :: selected_mci = 0
    integer :: selected_term = 0
    type(decay_chain_entry_t), pointer :: previous => null ()
  end type decay_chain_entry_t

```

This is the complete chain; we need just a pointer to the last entry. We also include a pointer to the master process instance, which serves as the seed for the decay chain.

The evaluator `correlated_trace` traces over all quantum numbers for the final spin-correlated (but color-summed) evaluator of the decay chain. This

allows us to compute the probability for a momentum configuration, given that all individual density matrices (of the initial process and the subsequent decays) have been normalized to one.

Note: This trace is summed over color, so color is treated exactly when computing spin correlations. However, we do not keep non-diagonal color correlations. When an event is accepted, we compute probabilities for all color states and can choose one of them.

```

<Decays: types>+≡
  type :: decay_chain_t
    type(process_instance_t), pointer :: process_instance => null ()
    integer :: selected_term = 0
    type(evaluator_t) :: correlated_trace
    type(decay_chain_entry_t), pointer :: last => null ()
  contains
    <Decays: decay chain: TBP>
  end type decay_chain_t

```

The finalizer recursively deletes and deallocates the entries.

```

<Decays: decay chain: TBP>≡
  procedure :: final => decay_chain_final

<Decays: procedures>+≡
  subroutine decay_chain_final (object)
    class(decay_chain_t), intent(inout) :: object
    type(decay_chain_entry_t), pointer :: entry
    do while (associated (object%last))
      entry => object%last
      object%last => entry%previous
      call entry%final ()
      deallocate (entry)
    end do
    call object%correlated_trace%final ()
  end subroutine decay_chain_final

```

Doing output recursively allows us to display the chain in chronological order.

```

<Decays: decay chain: TBP>+≡
  procedure :: write => decay_chain_write

<Decays: procedures>+≡
  subroutine decay_chain_write (object, unit)
    class(decay_chain_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    call write_separator (u, 2)
    write (u, "(1x,A)") "Decay chain:"
    call write_entries (object%last)
    call write_separator (u, 2)
    write (u, "(1x,A)") "Evaluator (correlated trace of the decay chain):"
    call write_separator (u)
    call object%correlated_trace%write (u)
    call write_separator (u, 2)
  contains

```



```

recursive subroutine write_entries (entry)
  type(decay_chain_entry_t), intent(in), pointer :: entry
  if (associated (entry)) then
    call write_entries (entry%previous)
    call write_separator (u, 2)
    write (u, "(1x,A,I0)") "Decay #", entry%index
    call entry%config%write_header (u)
    write (u, "(3x,A,I0)") "Selected MCI    = ", entry%selected_mci
    write (u, "(3x,A,I0)") "Selected term  = ", entry%selected_term
    call entry%config%term_config(entry%selected_term)%write (u, indent=1)
    call entry%write (u)
  end if
end subroutine write_entries
end subroutine decay_chain_write

```

Build a decay chain, recursively following the selected decays and terms in a decay tree. Before start, we finalize the chain, deleting any previous contents.

```

<Decays: decay chain: TBP>+≡
  procedure :: build => decay_chain_build

<Decays: procedures>+≡
  subroutine decay_chain_build (chain, decay_root)
    class(decay_chain_t), intent(inout), target :: chain
    type(decay_root_t), intent(in) :: decay_root
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
    type(interaction_t), pointer :: int_last_decay
    call chain%final ()
    if (decay_root%selected_term > 0) then
      chain%process_instance => decay_root%process_instance
      chain%selected_term = decay_root%selected_term
      call chain%build_term_entries (decay_root%term(decay_root%selected_term))
    end if
    int_last_decay => chain%last%get_matrix_int_ptr ()
    allocate (qn_mask (int_last_decay%get_n_tot ()))
    call qn_mask%init (mask_f = .true., mask_c = .true., mask_h = .true.)
    call chain%correlated_trace%init_qn_sum (int_last_decay, qn_mask)
  end subroutine decay_chain_build

```

Build the entries that correspond to a decay term. We have to scan all unstable particles.

```

<Decays: decay chain: TBP>+≡
  procedure :: build_term_entries => decay_chain_build_term_entries

<Decays: procedures>+≡
  recursive subroutine decay_chain_build_term_entries (chain, term)
    class(decay_chain_t), intent(inout) :: chain
    type(decay_term_t), intent(in) :: term
    integer :: i
    do i = 1, size (term%particle_out)
      select type (unstable => term%particle_out(i)%c)
      type is (unstable_t)
        if (unstable%selected_decay > 0) then
          call chain%build_decay_entries &
            (unstable%decay(unstable%selected_decay))
        end if
      end select
    end do
  end subroutine decay_chain_build_term_entries

```

```

        end if
    end select
end do
end subroutine decay_chain_build_term_entries

```

Build the entries that correspond to a specific decay. The decay term should have been determined, so we allocate a decay chain entry and fill it, then proceed to child decays.

For the first entry, we convolute the connected state of the parent process instance with the isolated state of the current decay (which does not contain an extra beam entry for the parent). For subsequent entries, we take the previous entry as first factor.

In principle, each chain entry (as a parton state) is capable of holding a subevent object and associated expressions. We currently do not make use of that feature.

Before generating the decays, factor out the trace of the helicity density matrix of the parent parton state. This trace has been used for unweighting the original event (unweighted case) or it determines the overall weight, so it should not be taken into account in the decay chain generation.

```

<Decays: decay chain: TBP>+≡
    procedure :: build_decay_entries => decay_chain_build_decay_entries

<Decays: procedures>+≡
    recursive subroutine decay_chain_build_decay_entries (chain, decay)
        class(decay_chain_t), intent(inout) :: chain
        type(decay_t), intent(in) :: decay
        type(decay_chain_entry_t), pointer :: entry
        type(connected_state_t), pointer :: previous_state
        type(isolated_state_t), pointer :: current_decay
        type(helicity_t) :: hel
        type(quantum_numbers_t) :: qn_filter_conn
        allocate (entry)
        if (associated (chain%last)) then
            entry%previous => chain%last
            entry%index = entry%previous%index + 1
            previous_state => entry%previous%connected_state_t
        else
            entry%index = 1
            previous_state => &
                chain%process_instance%get_connected_state_ptr (chain%selected_term)
        end if
        entry%config => decay%config
        entry%selected_mci = decay%selected_mci
        entry%selected_term = decay%selected_term
        current_decay => decay%process_instance%get_isolated_state_ptr &
            (decay%selected_term)
        call entry%setup_connected_trace &
            (current_decay, previous_state%get_trace_int_ptr (), resonant=.true.)
        if (entry%config%flv%has_decay_helicity ()) then
            call hel%init (entry%config%flv%get_decay_helicity ())
            call qn_filter_conn%init (hel)
            call entry%setup_connected_matrix &
                (current_decay, previous_state%get_matrix_int_ptr (), &

```

```

        resonant=.true., qn_filter_conn = qn_filter_conn)
    call entry%setup_connected_flows &
        (current_decay, previous_state%get_flows_int_ptr (), &
        resonant=.true., qn_filter_conn = qn_filter_conn)
else
    call entry%setup_connected_matrix &
        (current_decay, previous_state%get_matrix_int_ptr (), &
        resonant=.true.)
    call entry%setup_connected_flows &
        (current_decay, previous_state%get_flows_int_ptr (), &
        resonant=.true.)
end if
chain%last => entry
call chain%build_term_entries (decay%term(decay%selected_term))
end subroutine decay_chain_build_decay_entries

```

Recursively fill the decay chain with momenta and evaluate the matrix elements. Since all evaluators should have correct source entries at this point, momenta are automatically retrieved from the appropriate process instance.

Like we did above for the parent process, factor out the trace for each subsequent decay (the helicity density matrix in the isolated state, which is taken for the convolution).

```

<Decays: decay chain: TBP>+≡
    procedure :: evaluate => decay_chain_evaluate

<Decays: procedures>+≡
    subroutine decay_chain_evaluate (chain)
        class(decay_chain_t), intent(inout) :: chain
        call evaluate (chain%last)
        call chain%correlated_trace%receive_momenta ()
        call chain%correlated_trace%evaluate ()
    contains
        recursive subroutine evaluate (entry)
            type(decay_chain_entry_t), intent(inout), pointer :: entry
            if (associated (entry)) then
                call evaluate (entry%previous)
                call entry%receive_kinematics ()
                call entry%evaluate_trace ()
                call entry%evaluate_event_data ()
            end if
        end subroutine evaluate
    end subroutine decay_chain_evaluate

```

Return the probability of a decay chain. This is given as the trace of the density matrix with intermediate helicity correlations, normalized by the product of the uncorrelated density matrix traces. This works only if an event has been evaluated and the `correlated_trace` evaluator is filled. By definition, this evaluator has only one matrix element, and this must be real.

```

<Decays: decay chain: TBP>+≡
    procedure :: get_probability => decay_chain_get_probability

<Decays: procedures>+≡
    function decay_chain_get_probability (chain) result (x)

```

```

class(decay_chain_t), intent(in) :: chain
real(default) :: x
x = real (chain%correlated_trace%get_matrix_element (1))
end function decay_chain_get_probability

```

28.3.12 Decay as Event Transform

The `evt_decay` object combines decay configuration, decay tree, and chain in a single object, as an implementation of the `evt` (event transform) abstract type.

```

<Decays: public>≡
  public :: evt_decay_t

<Decays: types>+≡
  type, extends (evt_t) :: evt_decay_t
    type(decay_root_config_t) :: decay_root_config
    type(decay_root_t) :: decay_root
    type(decay_chain_t) :: decay_chain
  contains
    <Decays: evt decay: TBP>
  end type evt_decay_t

```

Output. We display the currently selected decay tree, which includes configuration data, and the decay chain, i.e., the evaluators.

```

<Decays: evt decay: TBP>≡
  procedure :: write => evt_decay_write

<Decays: procedures>+≡
  subroutine evt_decay_write (evt, unit, verbose, more_verbose, testflag)
    class(evt_decay_t), intent(in) :: evt
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose, more_verbose, testflag
    logical :: verb, verb2
    integer :: u
    u = given_output_unit (unit)
    verb = .true.; if (present (verbose)) verb = verbose
    verb2 = .false.; if (present (more_verbose)) verb2 = more_verbose
    call write_separator (u, 2)
    write (u, "(1x,A)") "Event transform: partonic decays"
    call write_separator (u, 2)
    call evt%base_write (u, testflag = testflag)
    if (verb) then
      call write_separator (u)
      call evt%decay_root%write (u)
      if (verb2) then
        call evt%decay_chain%write (u)
        call evt%decay_root%write_process_instances (u, verb)
      end if
    else
      call write_separator (u, 2)
    end if
  end subroutine evt_decay_write

```

Connect with a process instance and process. This initializes the decay configuration. The process stack is used to look for process objects that implement daughter decays.

When all processes are assigned, configure the decay tree instance, using the decay tree configuration. First obtain the branching ratios, then allocate the decay tree. This is done once for all events.

```

<Decays: evt decay: TBP>+≡
  procedure :: connect => evt_decay_connect

<Decays: procedures>+≡
  subroutine evt_decay_connect (evt, process_instance, model, process_stack)
    class(evt_decay_t), intent(inout), target :: evt
    type(process_instance_t), intent(in), target :: process_instance
    class(model_data_t), intent(in), target :: model
    type(process_stack_t), intent(in), optional :: process_stack
    call evt%base_connect (process_instance, model)
    call evt%decay_root_config%connect (process_instance%process, &
      model, process_stack, process_instance)
    call evt%decay_root_config%compute ()
    call evt%decay_root%init (evt%decay_root_config, evt%process_instance)
  end subroutine evt_decay_connect

```

Prepare a new event: Select a decay chain and build the corresponding chain object.

```

<Decays: evt decay: TBP>+≡
  procedure :: prepare_new_event => evt_decay_prepare_new_event

<Decays: procedures>+≡
  subroutine evt_decay_prepare_new_event (evt, i_mci, i_term)
    class(evt_decay_t), intent(inout) :: evt
    integer, intent(in) :: i_mci, i_term
    call evt%reset ()
    evt%decay_root%selected_mci = i_mci
    evt%decay_root%selected_term = i_term
    call evt%decay_root%select_chain ()
    call evt%decay_chain%build (evt%decay_root)
  end subroutine evt_decay_prepare_new_event

```

Generate a weighted event and assign the resulting weight (probability). We use a chain initialized by the preceding subroutine, fill it with momenta and evaluate.

```

<Decays: evt decay: TBP>+≡
  procedure :: generate_weighted => evt_decay_generate_weighted

<Decays: procedures>+≡
  subroutine evt_decay_generate_weighted (evt, probability)
    class(evt_decay_t), intent(inout) :: evt
    real(default), intent(out) :: probability
    call evt%decay_root%generate ()
    if (signal_is_pending ()) return
    call evt%decay_chain%evaluate ()
    probability = evt%decay_chain%get_probability ()
  end subroutine evt_decay_generate_weighted

```

To create a usable event, we have to transform the interaction into a particle set; this requires factorization for the correlated density matrix, according to the factorization mode.

```

<Decays: evt_decay: TBP>+≡
  procedure :: make_particle_set => evt_decay_make_particle_set

<Decays: procedures>+≡
  subroutine evt_decay_make_particle_set &
    (evt, factorization_mode, keep_correlations, r)
    class(evt_decay_t), intent(inout) :: evt
    integer, intent(in) :: factorization_mode
    logical, intent(in) :: keep_correlations
    real(default), dimension(:), intent(in), optional :: r
    type(interaction_t), pointer :: int_matrix, int_flows
    type(decay_chain_entry_t), pointer :: last_entry
    last_entry => evt%decay_chain%last
    int_matrix => last_entry%get_matrix_int_ptr ()
    int_flows => last_entry%get_flows_int_ptr ()
    call evt%factorize_interactions (int_matrix, int_flows, &
      factorization_mode, keep_correlations, r)
    call evt%tag_incoming ()
  end subroutine evt_decay_make_particle_set

```

Eliminate numerical noise for the associated process instances.

```

<Decays: public>+≡
  public :: pacify

<Decays: interfaces>+≡
  interface pacify
    module procedure pacify_decay
  end interface pacify

<Decays: procedures>+≡
  subroutine pacify_decay (evt)
    class(evt_decay_t), intent(inout) :: evt
    call pacify_decay_gen (evt%decay_root)
  contains
    recursive subroutine pacify_decay_gen (decay)
      class(decay_gen_t), intent(inout) :: decay
      if (associated (decay%process_instance)) then
        call pacify (decay%process_instance)
      end if
      if (decay%selected_term > 0) then
        call pacify_term (decay%term(decay%selected_term))
      end if
    end subroutine pacify_decay_gen
    recursive subroutine pacify_term (term)
      class(decay_term_t), intent(inout) :: term
      integer :: i
      do i = 1, size (term%particle_out)
        select type (unstable => term%particle_out(i)%c)
          type is (unstable_t); call pacify_unstable (unstable)
        end select
      end do
    end subroutine pacify_term

```

```

recursive subroutine pacify_unstable (unstable)
  class(unstable_t), intent(inout) :: unstable
  if (unstable%selected_decay > 0) then
    call pacify_decay_gen (unstable%decay(unstable%selected_decay))
  end if
end subroutine pacify_unstable
end subroutine pacify_decay

```

28.3.13 Unit tests

```

<Decays: public>+≡
  public :: decays_test

<Decays: tests>≡
  subroutine decays_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Decays: execute tests>
  end subroutine decays_test

```

Testbed

As a variation of the `prepare_test_process` routine used elsewhere, we define here a routine that creates two processes (scattering $ss \rightarrow ss$ and decay $s \rightarrow f\bar{f}$), compiles and integrates them and prepares for event generation.

```

<Decays: public>+≡
  public :: prepare_testbed

<Decays: tests>+≡
  subroutine prepare_testbed &
    (lib, process_stack, prefix, os_data, &
     scattering, decay, decay_rest_frame)
    type(process_library_t), intent(out), target :: lib
    type(process_stack_t), intent(out) :: process_stack
    type(string_t), intent(in) :: prefix
    type(os_data_t), intent(in) :: os_data
    logical, intent(in) :: scattering, decay
    logical, intent(in), optional :: decay_rest_frame

    type(model_data_t), target :: model
    class(model_data_t), pointer :: model_copy
    type(string_t) :: libname, procname1, procname2, run_id
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    type(process_entry_t), pointer :: process
    type(process_instance_t), allocatable, target :: process_instance
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    type(field_data_t), pointer :: field_data
    real(default) :: sqrts

```

```

libname = prefix // "_lib"
procname1 = prefix // "_p"
procname2 = prefix // "_d"
run_id = prefix

call model%init_test ()
call model%set_par (var_str ("ff"), 0.4_default)
call model%set_par (var_str ("mf"), &
    model%get_real (var_str ("ff")) * model%get_real (var_str ("ms")))

if (scattering .and. decay) then
    field_data => model%get_field_ptr (25)
    call field_data%set (p_is_stable = .false.)
end if

call prc_test_create_library (libname, lib, &
    scattering = .true., decay = .true., &
    procname1 = procname1, procname2 = procname2)

call reset_interaction_counter ()

allocate (test_t :: core_template)
allocate (mci_midpoint_t :: mci_template)
allocate (phs_single_config_t :: phs_config_template)

if (scattering) then

    allocate (rng_test_factory_t :: rng_factory)
    allocate (model_copy)
    call model_copy%init (model%get_name (), &
        model%get_n_real (), &
        model%get_n_complex (), &
        model%get_n_field (), &
        model%get_n_vtx ())
    call model_copy%copy_from (model)

    allocate (process)
    call process%init (procname1, &
        run_id, lib, os_data, qcd, rng_factory, model_copy)
    call process%init_component &
        (1, core_template, mci_template, phs_config_template)
    sqrts = 1000
    call process%setup_beams_sqrts (sqrts)
    call process%configure_phs ()
    call process%setup_mci ()
    call process%setup_terms ()

    allocate (process_instance)
    call process_instance%init (process%process_t)
    call process%integrate (process_instance, 1, n_it=1, n_calls=100)
    call process%final_integration (1)
    call process_instance%final ()
    deallocate (process_instance)

```



```

        call process%prepare_simulation (1)
        call process_stack%push (process)
    end if

    if (decay) then
        allocate (rng_test_factory_t :: rng_factory)
        allocate (model_copy)
        call model_copy%init (model%get_name (), &
            model%get_n_real (), &
            model%get_n_complex (), &
            model%get_n_field (), &
            model%get_n_vtx ())
        call model_copy%copy_from (model)

        allocate (process)
        call process%init (procname2, &
            run_id, lib, os_data, qcd, rng_factory, model_copy)
        call process%init_component &
            (1, core_template, mci_template, phs_config_template)
        if (present (decay_rest_frame)) then
            call process%setup_beams_decay (rest_frame = decay_rest_frame)
        else
            call process%setup_beams_decay (rest_frame = .not. scattering)
        end if
        call process%configure_phs ()
        call process%setup_mci ()
        call process%setup_terms ()

        allocate (process_instance)
        call process_instance%init (process%process_t)
        call process%integrate (process_instance, 1, n_it=1, n_calls=100)
        call process%final_integration (1)
        call process_instance%final ()
        deallocate (process_instance)

        call process%prepare_simulation (1)
        call process_stack%push (process)
    end if

    call model%final ()

end subroutine prepare_testbed

```

Simple decay configuration

We define a branching configuration with two decay modes. We set the integral values by hand, so we do not need to evaluate processes, yet.

```

(Decays: execute tests)≡
    call test (decays_1, "decays_1", &
        "branching and decay configuration", &
        u, results)

```

```

<Decays: tests>+≡
subroutine decays_1 (u)
  integer, intent(in) :: u
  type(os_data_t) :: os_data
  type(model_data_t), target :: model
!   type(model_t), pointer :: model
!   type(model_list_t) :: model_list
  type(flavor_t) :: flv_h
  type(flavor_t), dimension(2,1) :: flv_hbb, flv_hgg
  type(unstable_config_t), allocatable :: unstable

  write (u, "(A)")  "* Test output: decays_1"
  write (u, "(A)")  "* Purpose: Set up branching and decay configuration"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize environment"
  write (u, "(A)")

  call os_data_init (os_data)
  call model%init_sm_test ()
!   call model_list%read_model (var_str ("SM"), &
!     var_str ("SM.mdl"), os_data, model)

  call flv_h%init (25, model)
  call flv_hbb(:,1)%init ([5, -5], model)
  call flv_hgg(:,1)%init ([22, 22], model)

  write (u, "(A)")  "* Set up branching and decay"
  write (u, "(A)")

  allocate (unstable)
  unstable%flv = flv_h
  call unstable%init_decays ([var_str ("h_bb"), var_str ("h_gg")], model)

  associate (decay => unstable%decay_config(1))
    allocate (decay%term_config (1))
    call decay%init_term (1, flv_hbb, stable = [.true., .true.], model=model)
    decay%integral = 1.234e-3_default
    decay%abs_error = decay%integral * .02_default
  end associate

  associate (decay => unstable%decay_config(2))
    allocate (decay%term_config (1))
    call decay%init_term (1, flv_hgg, stable = [.true., .true.], model=model)
    decay%integral = 3.085e-4_default
    decay%abs_error = decay%integral * .08_default
  end associate

  call unstable%compute ()
  call unstable%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Cleanup"

```

```

call unstable%final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: decays_1"

end subroutine decays_1

```

Cascade decay configuration

We define a branching configuration with one decay, which is followed by another branching.

```

<Decays: execute tests> +=
  call test (decays_2, "decays_2", &
    "cascade decay configuration", &
    u, results)

<Decays: tests> +=
  subroutine decays_2 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    !   type(model_t), pointer :: model
    !   type(model_list_t) :: model_list
    type(model_data_t), target :: model
    type(flavor_t) :: flv_h, flv_wp, flv_wm
    type(flavor_t), dimension(2,1) :: flv_hww, flv_wud, flv_wen
    type(unstable_config_t), allocatable :: unstable
    type(string_t), dimension(:), allocatable :: decay

    write (u, "(A)")  "* Test output: decays_2"
    write (u, "(A)")  "*   Purpose: Set up cascade branching"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize environment"
    write (u, "(A)")

    !   call syntax_model_file_init ()
    call os_data_init (os_data)
    !   call model_list%read_model (var_str ("SM"), &
    !     var_str ("SM.mdl"), os_data, model)
    call model%init_sm_test ()

    call model%set_unstable (25, [var_str ("h_ww")])
    call model%set_unstable (24, [var_str ("w_ud"), var_str ("w_en")])

    call flv_h%init (25, model)
    call flv_hww(:,1)%init ([24, -24], model)
    call flv_wp%init (24, model)
    call flv_wm%init (-24, model)
    call flv_wud(:,1)%init ([2, -1], model)
    call flv_wen(:,1)%init ([-11, 12], model)

```

```

write (u, "(A)")  "* Set up branching and decay"
write (u, "(A)")

allocate (unstable)
unstable%flv = flv_h
call unstable%flv%get_decays (decay)
call unstable%init_decays (decay, model)

associate (decay => unstable%decay_config(1))

  decay%integral = 1.e-3_default
  decay%abs_error = decay%integral * .01_default

  allocate (decay%term_config (1))
  call decay%init_term (1, flv_hww, stable = [.false., .true.], model=model)

  select type (w => decay%term_config(1)%prt(1)%c)
  type is (unstable_config_t)

    associate (w_decay => w%decay_config(1))
      w_decay%integral = 2._default
      allocate (w_decay%term_config (1))
      call w_decay%init_term (1, flv_wud, stable = [.true., .true.], &
        model=model)
    end associate
    associate (w_decay => w%decay_config(2))
      w_decay%integral = 1._default
      allocate (w_decay%term_config (1))
      call w_decay%init_term (1, flv_wen, stable = [.true., .true.], &
        model=model)
    end associate
    call w%compute ()

  end select

end associate

call unstable%compute ()
call unstable%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call unstable%final ()
call model%final ()
!   call model_list%final ()
!   call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: decays_2"

end subroutine decays_2

```

Decay and Process Object

We define a branching configuration with one decay and connect this with an actual process object.

```
(Decays: execute tests)+≡
    call test (decays_3, "decays_3", &
               "associate process", &
               u, results)

(Decays: tests)+≡
    subroutine decays_3 (u)
        integer, intent(in) :: u
        type(os_data_t) :: os_data
        class(model_data_t), pointer :: model
        type(process_library_t), target :: lib
        type(string_t) :: prefix
        type(string_t) :: procname2
        type(process_stack_t) :: process_stack
        type(process_t), pointer :: process
        type(unstable_config_t), allocatable :: unstable

        write (u, "(A)")  "* Test output: decays_3"
        write (u, "(A)")  "*   Purpose: Connect a decay configuration &
                           &with a process"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize environment and integrate process"
        write (u, "(A)")

        call os_data_init (os_data)

        prefix = "decays_3"
        call prepare_testbed &
             (lib, process_stack, prefix, os_data, &
              scattering=.false., decay=.true., decay_rest_frame=.false.)

        procname2 = prefix // "_d"
        process => process_stack%get_process_ptr (procname2)
        model => process%get_model_ptr ()
        call process%write (.false., u)

        write (u, "(A)")
        write (u, "(A)")  "* Set up branching and decay"
        write (u, "(A)")

        allocate (unstable)
        call unstable%flv%init (25, model)
        call unstable%init_decays ([procname2], model)

        write (u, "(A)")  "* Connect decay with process object"
        write (u, "(A)")

        associate (decay => unstable%decay_config(1))
            call decay%connect (process, model)
        end associate
```

```

call unstable%compute ()
call unstable%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call unstable%final ()
call process_stack%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: decays_3"

end subroutine decays_3

```

Decay and Process Object

Building upon the previous test, we set up a decay instance and generate a decay event.

```

<Decays: execute tests>+≡
  call test (decays_4, "decays_4", &
    "decay instance", &
    u, results)

<Decays: tests>+≡
  subroutine decays_4 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    class(model_data_t), pointer :: model
    type(process_library_t), target :: lib
    type(string_t) :: prefix, procname2
    class(rng_t), allocatable :: rng
    type(process_stack_t) :: process_stack
    type(process_t), pointer :: process
    type(unstable_config_t), allocatable, target :: unstable
    type(unstable_t), allocatable :: instance

    write (u, "(A)")  "* Test output: decays_4"
    write (u, "(A)")  "* Purpose: Create a decay process and evaluate &
      &an instance"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize environment, process, &
      &and decay configuration"
    write (u, "(A)")

    call os_data_init (os_data)

    prefix = "decays_4"
    call prepare_testbed &
      (lib, process_stack, prefix, os_data, &
        scattering=.false., decay=.true., decay_rest_frame = .false.)

```

```

procname2 = prefix // "_d"
process => process_stack%get_process_ptr (procname2)
model => process%get_model_ptr ()

allocate (unstable)
call unstable%flv%init (25, model)
call unstable%init_decays ([procname2], model)

call model%set_unstable (25, [procname2])

associate (decay => unstable%decay_config(1))
  call decay%connect (process, model)
end associate

call unstable%compute ()

allocate (rng_test_t :: rng)

allocate (instance)
call instance%init (unstable)
call instance%import_rng (rng)

call instance%select_chain ()
call instance%generate ()
call instance%write (u)

write (u, *)
call instance%write_process_instances (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call instance%final ()
call process_stack%final ()
call unstable%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: decays_4"

end subroutine decays_4

```

Decay with Parent Process

We define a scattering process $ss \rightarrow ss$ and subsequent decays $s \rightarrow f\bar{f}$.

```

<Decays: execute tests>+≡
  call test (decays_5, "decays_5", &
    "parent process and decay", &
    u, results)

<Decays: tests>+≡
  subroutine decays_5 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data

```

```

class(model_data_t), pointer :: model
type(process_library_t), target :: lib
type(string_t) :: prefix, procname1, procname2
type(process_stack_t) :: process_stack
type(process_t), pointer :: process
type(process_instance_t), allocatable, target :: process_instance
type(decay_root_config_t), target :: decay_root_config
type(decay_root_t) :: decay_root
type(decay_chain_t) :: decay_chain
integer :: i

write (u, "(A)")  "* Test output: decays_5"
write (u, "(A)")  "* Purpose: Handle a process with subsequent decays"
write (u, "(A)")

write (u, "(A)")  "* Initialize environment and parent process"
write (u, "(A)")

call os_data_init (os_data)

prefix = "decays_5"
procname1 = prefix // "_p"
procname2 = prefix // "_d"
call prepare_testbed &
      (lib, process_stack, prefix, os_data, &
       scattering=.true., decay=.true.)

write (u, "(A)")  "* Initialize decay process"
write (u, "(A)")

process => process_stack%get_process_ptr (procname1)
model => process%get_model_ptr ()
call model%set_unstable (25, [procname2])

write (u, "(A)")  "* Initialize decay tree configuration"
write (u, "(A)")

call decay_root_config%connect (process, model, process_stack)
call decay_root_config%compute ()
call decay_root_config%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize decay tree"

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
call process_instance%init_simulation (1)

call decay_root%init (decay_root_config, process_instance)

write (u, "(A)")
write (u, "(A)")  "* Select decay chain"
write (u, "(A)")

```



```

decay_root%selected_mci = 1
!!! Not yet implemented; there is only one term anyway:
! call process_instance%select_i_term (decay_root%selected_term)
decay_root%selected_term = 1
call decay_root%select_chain ()

call decay_chain%build (decay_root)

call decay_root%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate event"
write (u, "(A)")

call process%generate_unweighted_event (process_instance, &
    decay_root%selected_mci)
call process_instance%evaluate_event_data ()

call decay_root%generate ()

associate (term => decay_root%term(1))
  do i = 1, 2
    select type (unstable => term%particle_out(i)%c)
      type is (unstable_t)
        associate (decay => unstable%decay(1))
          call pacify (decay%process_instance)
        end associate
      end select
    end do
  end associate

write (u, "(A)")  "* Process instances"
write (u, "(A)")

call decay_root%write_process_instances (u)

write (u, "(A)")
write (u, "(A)")  "* Generate decay chain"
write (u, "(A)")

call decay_chain%evaluate ()
call decay_chain%write (u)

write (u, *)
write (u, "(A,ES19.12)")  "chain probability =", &
    decay_chain%get_probability ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call decay_chain%final ()
call decay_root%final ()
call decay_root_config%final ()

```

```

call process_instance%final ()
deallocate (process_instance)

call process%final ()
call process_stack%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: decays_5"

end subroutine decays_5

```

Decay as Event Transform

Again, we define a scattering process $ss \rightarrow ss$ and subsequent decays $s \rightarrow f\bar{f}$.

```

<Decays: execute tests>+≡
  call test (decays_6, "decays_6", &
    "evt_decay object", &
    u, results)

<Decays: tests>+≡
  subroutine decays_6 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    class(model_data_t), pointer :: model
    type(process_library_t), target :: lib
    type(string_t) :: prefix, procname1, procname2
    type(process_stack_t) :: process_stack
    type(process_t), pointer :: process
    type(process_instance_t), allocatable, target :: process_instance
    type(evt_decay_t), target :: evt_decay
    integer :: factorization_mode
    logical :: keep_correlations

    write (u, "(A)")  "* Test output: decays_6"
    write (u, "(A)")  "* Purpose: Handle a process with subsequent decays"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize environment and parent process"
    write (u, "(A)")

    call os_data_init (os_data)

    prefix = "decays_6"
    procname1 = prefix // "_p"
    procname2 = prefix // "_d"
    call prepare_testbed &
      (lib, process_stack, prefix, os_data, &
        scattering=.true., decay=.true.)

    write (u, "(A)")  "* Initialize decay process"

    process => process_stack%get_process_ptr (procname1)
    model => process%get_model_ptr ()

```

```

call model%set_unstable (25, [procname2])

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
call process_instance%init_simulation (1)

write (u, "(A)")
write (u, "(A)")  "* Initialize decay object"

call evt_decay%connect (process_instance, model, process_stack)

write (u, "(A)")
write (u, "(A)")  "* Generate scattering event"

call process%generate_unweighted_event (process_instance, 1)
call process_instance%evaluate_event_data ()

write (u, "(A)")
write (u, "(A)")  "* Select decay chain and generate event"
write (u, "(A)")

call evt_decay%prepare_new_event (1, 1)
call evt_decay%generate_unweighted ()

factorization_mode = FM_IGNORE_HELICITY
keep_correlations = .false.
call evt_decay%make_particle_set (factorization_mode, keep_correlations)

call evt_decay%write (u, verbose = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call evt_decay%final ()
call process_instance%final ()
deallocate (process_instance)

call process_stack%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: decays_6"

end subroutine decays_6

```

28.4 Shower

We might use matrix elements of LO and NLO to increase the accuracy of the shower in the sense of matching as well as merging.

`<shower.f90>`≡
<File header>

```

module shower

  <Use kinds with double>
  <Use strings>
    use io_units
    use constants, only: pi, twopi, zero
    use format_utils, only: write_separator
    use string_utils
    use unit_tests
    use system_defs, only: LF
    use os_interface
    use diagnostics
    use lorentz
    use system_dependencies, only: LHAPDF5_AVAILABLE, LHAPDF6_AVAILABLE
    use lhpdf !NODEP!
    use pdf_builtin !NODEP!

    use shower_base
    use shower_partons
    use shower_core
    use shower_pythia6
    use mlm_matching
    use ckkw_base
    use ckkw_matching
    use powheg

    use sm_qcd
    use particles
    use state_matrices, only: FM_IGNORE_HELICITY
    use model_data
    use variables
    use beam_structures
    use process_libraries
    use rng_base
    use mci_base
    use phs_base

    use event_transforms
    use models
    use hep_common
    use processes
    use process_stacks
    use rng_tao
    use mci_midpoint
    use phs_single
    use prc_core
    use prc_omega

  <Standard module head>

  <Shower: public>

  <Shower: parameters>

```

```

    <Shower: types>

contains

    <Shower: procedures>

    <Shower: tests>

end module shower

```

28.4.1 Configuration Parameters

POWHEG_TESTING allows to disable the parton shower for validation and testing of the POWHEG procedure.

```

<Shower: parameters>≡
    logical, parameter :: DEBUG_EVT_SHOWER = .false.
    logical, parameter :: POWHEG_TESTING = .false.
    logical, parameter :: TEST_SUDAKOV = .false.
    logical, parameter :: TO_FILE = .false.

```

28.4.2 Event Transform

The event transforms can do more than mere showering. Especially, it may reweight showered events to fixed-order matrix elements. The `model_hadrons` is supposed to be the SM variant that contains all hadrons that can be generated in the shower.

```

<Shower: public>≡
    public :: evt_shower_t

<Shower: types>≡
    type, extends (evt_t) :: evt_shower_t
        type(shower_settings_t) :: settings
        class(shower_base_t), allocatable :: shower
        type(model_t), pointer :: model_hadrons => null ()
        type(powheg_t) :: powheg
        class(matching_settings_t), allocatable :: matching_settings
        class(matching_data_t), allocatable :: data
        type(qcd_t), pointer :: qcd => null()
        type(pdf_data_t) :: pdf_data
        type(os_data_t) :: os_data
    contains
        <Shower: evt shower: TBP>
    end type evt_shower_t

```

Output.

```

<Shower: evt shower: TBP>≡
    procedure :: write => evt_shower_write

```

```

<Shower: procedures>+≡
  subroutine evt_shower_write (evt, unit, verbose, more_verbose, testflag)
    class(evt_shower_t), intent(in) :: evt
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose, more_verbose, testflag
    integer :: u
    u = given_output_unit (unit)
    call write_separator (u, 2)
    write (u, "(1x,A)") "Event transform: shower"
    call write_separator (u)
    call evt%base_write (u, testflag = testflag, show_set = .false.)
    if (evt%particle_set_exists) call evt%particle_set%write &
      (u, summary = .true., compressed = .true., testflag = testflag)
    call write_separator (u)
    call evt%settings%write (u)
  end subroutine evt_shower_write

```

```

<Shower: evt shower: TBP>+≡
  procedure :: connect => evt_shower_connect

```

```

<Shower: procedures>+≡
  subroutine evt_shower_connect &
    (evt, process_instance, model, process_stack)
    class(evt_shower_t), intent(inout), target :: evt
    type(process_instance_t), intent(in), target :: process_instance
    class(model_data_t), intent(in), target :: model
    type(process_stack_t), intent(in), optional :: process_stack
    call evt%base_connect (process_instance, model, process_stack)
    call evt%make_rng (evt%process)
    if (evt%settings%powheg_matching) then
      call evt%powheg%connect (process_instance)
      call evt%powheg%setup_grids ()
    end if
  end subroutine evt_shower_connect

```

Initialize the event transformation. This will be executed once during dispatching. The `model_hadrons` is supposed to be the SM variant that contains all hadrons that may be generated in the shower.

```

<Shower: evt shower: TBP>+≡
  procedure :: init => evt_shower_init

```

```

<Shower: procedures>+≡
  subroutine evt_shower_init &
    (evt, settings, model_hadrons, os_data, powheg)
    class(evt_shower_t), intent(out) :: evt
    type(shower_settings_t), intent(in) :: settings
    type(model_t), intent(in), target :: model_hadrons
    type(os_data_t), intent(in) :: os_data
    type(powheg_t), intent(in), optional :: powheg
    evt%settings = settings
    evt%os_data = os_data
    evt%model_hadrons => model_hadrons
    if (present (powheg)) evt%powheg = powheg
  end subroutine evt_shower_init

```

Create RNG instances, spawned by the process object.

```

(Shower: evt shower: TBP)+≡
  procedure :: make_rng => evt_shower_make_rng

(Shower: procedures)+≡
  subroutine evt_shower_make_rng (evt, process)
    class(evt_shower_t), intent(inout) :: evt
    type(process_t), intent(inout) :: process
    class(rng_t), allocatable :: rng
    call process%make_rng (rng)
    call evt%shower%import_rng (rng)
    if (evt%settings%powheg_matching) then
      call process%make_rng (rng)
      call evt%powheg%import_rng (rng)
    end if
  end subroutine evt_shower_make_rng

```

Use the process and beam structure to determine PDF parameters. Will be performed during dispatching.

```

(Shower: evt shower: TBP)+≡
  procedure :: setup_pdf => evt_shower_setup_pdf

(Shower: procedures)+≡
  subroutine evt_shower_setup_pdf (evt, process, beam_structure, lhpdf_member)
    class(evt_shower_t), intent(inout) :: evt
    type(process_t), intent(in) :: process
    type(beam_structure_t), intent(in) :: beam_structure
    integer, intent(in) :: lhpdf_member
    real(default) :: xmin, xmax, q2min, q2max
    if (beam_structure%contains ("lhpdf")) then
      if (LHAPDF6_AVAILABLE) then
        evt%pdf_data%type = STRF_LHAPDF6
      else if (LHAPDF5_AVAILABLE) then
        evt%pdf_data%type = STRF_LHAPDF5
      end if
      evt%pdf_data%set = process%get_pdf_set ()
      write (msg_buffer, "(A,I0)") "Shower: interfacing LHAPDF set #", &
        evt%pdf_data%set
      call msg_message ()
    else if (beam_structure%contains ("pdf_builtin")) then
      evt%pdf_data%type = STRF_PDF_BUILTIN
      evt%pdf_data%set = process%get_pdf_set ()
      write (msg_buffer, "(A,I0)") "Shower: interfacing PDF builtin set #", &
        evt%pdf_data%set
      call msg_message ()
    end if
    select case (evt%pdf_data%type)
    case (STRF_LHAPDF6)
      evt%pdf_data%xmin = evt%pdf_data%pdf%getxmin ()
      evt%pdf_data%xmax = evt%pdf_data%pdf%getxmax ()
      evt%pdf_data%qmin = sqrt(evt%pdf_data%pdf%getq2min ())
      evt%pdf_data%qmax = sqrt(evt%pdf_data%pdf%getq2max ())
    case (STRF_LHAPDF5)

```

```

        if (LHAPDF5_AVAILABLE) then
            call GetXminM (1, lhpdf_member, xmin)
            call GetXmaxM (1, lhpdf_member, xmax)
            call GetQ2minM (1, lhpdf_member, q2min)
            call GetQ2maxM (1, lhpdf_member, q2max)
            evt%pdf_data%xmin = xmin
            evt%pdf_data%xmax = xmax
            evt%pdf_data%qmin = sqrt(q2min)
            evt%pdf_data%qmax = sqrt(q2max)
        end if
    end select
end subroutine evt_shower_setup_pdf

```

Things we want to do for a new event before the whole event transformation chain is evaluated.

```

<Shower: evt shower: TBP>+≡
    procedure :: prepare_new_event => evt_shower_prepare_new_event

<Shower: procedures>+≡
    subroutine evt_shower_prepare_new_event (evt, i_mci, i_term)
        class(evt_shower_t), intent(inout) :: evt
        integer, intent(in) :: i_mci, i_term
        call evt%reset ()
        if (.not. evt%settings%active .or. signal_is_pending ()) then
            return
        end if
    end subroutine evt_shower_prepare_new_event

```

Here we take the particle set from the previous event transform (assuming that there is always one) and apply the shower algorithm. The result is stored in the event transform of the current object. We always return a probability of unity as we don't have the analytic weight of the combination of shower, MLM matching and hadronization. A subdivision into multiple event transformations is under construction. Invalid or vetoed events have to be discarded by the caller which is why we mark the particle set as invalid. This procedure directly takes the (MLM) matching into account.

```

<Shower: evt shower: TBP>+≡
    procedure :: generate_weighted => evt_shower_generate_weighted

<Shower: procedures>+≡
    subroutine evt_shower_generate_weighted (evt, probability)
        class(evt_shower_t), intent(inout) :: evt
        real(default), intent(out) :: probability
        logical :: valid, vetoed
        logical, save :: matching_disabled = .false.
        integer :: i
        type(particle_t), dimension(1:2) :: prt_in
        real(kind=double) :: pdf_test
        valid = .true.
        vetoed = .false.
        if (evt%previous%particle_set_exists) then
            evt%particle_set = evt%previous%particle_set
            if (evt%settings%powheg_matching) then

```



```

call evt%powheg%update (evt%particle_set)
if (TEST_SUDAKOV) then
  call evt%powheg%test_sudakov ()
  stop
end if
call evt%powheg%generate_emission (particle_set = evt%particle_set)
if (DEBUG_EVT_SHOWER) call evt%powheg%write ()
end if
if (evt%settings%method == PS_PYTHIA6 .or. &
  evt%settings%hadronization_active) then
  call assure_heprup (evt%particle_set)
end if
if (evt%settings%ckkw_matching) then
  select type (data => evt%data)
  type is (ckkw_matching_data_t)
    call ckkw_pseudo_shower_weights_init (data%ckkw_weights)
    call ckkw_fake_pseudo_shower_weights (evt%matching_settings, &
      data%ckkw_weights, evt%particle_set)
  end select
end if
if (evt%settings%fsr_active .or. &
  evt%settings%isr_active .or. &
  evt%settings%hadronization_active .or. &
  evt%settings%mlm_matching .and. &
  .not. POWHEG_TESTING) then
  do i = 1, 2
    prt_in(i) = evt%particle_set%get_particle (i)
  end do
  ! ensure that lhapdf is initialized
  if (evt%pdf_data%type .eq. STRF_LHAPDF5) then
    if (evt%settings%isr_active .and. &
      (all (abs (prt_in%get_pdg ()) >= 1000))) then
      call GetQ2max (0, pdfctest)
      if (pdfctest < epsilon(pdfctest)) then
        call msg_fatal ("ISR QCD shower enabled, but LHAPDF not" // &
          "initialized," // LF // "      aborting simulation")
        return
      end if
    end if
  else if (evt%pdf_data%type == STRF_PDF_BUILTIN .and. &
    evt%settings%method == PS_PYTHIA6) then
    call msg_fatal ("Builtin PDFs cannot be used for PYTHIA showers," &
      // LF // "      aborting simulation")
    return
  end if
  if (.not. matching_disabled .and. allocated (evt%data)) then
    if (DEBUG_EVT_SHOWER) &
      print *, "Shower: Set up beam type for mlm_matching"
    if (all (abs (prt_in%get_pdg ()) <= 18)) then
      evt%data%is_hadron_collision = .false.
    else if (all (abs (prt_in%get_pdg ()) >= 1000)) then
      evt%data%is_hadron_collision = .true.
    else
      call msg_error (" Matching didn't recognize beams setup," // &

```

```

        LF // "      disabling matching")
        matching_disabled = .true.
        return
    end if
end if
call evt%shower%generate_emissions (evt%particle_set, &
    evt%model, evt%model_hadrons, evt%os_data, &
    evt%matching_settings, evt%data, valid, vetoed)
if (evt%settings%mlm_matching .and. &
    (.not. matching_disabled)) then
    !!! MLM stage 2 -> PS jets and momenta
    select type (data => evt%data)
    type is (mlm_matching_data_t)
        select type (ms => evt%matching_settings)
        type is (mlm_matching_settings_t)
            call matching_transfer_PS (data, evt%particle_set, ms)
            !!! MLM stage 3 -> reconstruct and possibly reject
            call mlm_matching_apply (data, ms, vetoed)
            call mlm_matching_data_final (data)
        end select
    end select
end if
if (DEBUG_EVT_SHOWER) print *, "SHOWER+MATCHING finished"
end if
if (DEBUG_EVT_SHOWER) then
    print *, "Shower: obtained particle set after SHOWER"
    call evt%particle_set%write (summary=.true., &
                                compressed=.true.)
end if
probability = 1
if (valid .and. .not. vetoed) then
    evt%particle_set_exists = .true.
else
    evt%particle_set_exists = .false.
end if
else
    call msg_bug ("Shower: input particle set does not exist")
end if
end subroutine evt_shower_generate_weighted

```

Here we fill the particle set with the partons from the shower. The particle set was already made by the routine above (or the event was vetoed). So we do nothing here. The factorization parameters are irrelevant.

```

<Shower: evt shower: TBP>+≡
    procedure :: make_particle_set => evt_shower_make_particle_set

<Shower: procedures>+≡
    subroutine evt_shower_make_particle_set &
        (evt, factorization_mode, keep_correlations, r)
        class(evt_shower_t), intent(inout) :: evt
        integer, intent(in) :: factorization_mode
        logical, intent(in) :: keep_correlations
        real(default), dimension(:), intent(in), optional :: r
    end subroutine evt_shower_make_particle_set

```

```

<Shower: evt shower: TBP>+≡
  procedure :: final => evt_shower_final
<Shower: procedures>+≡
  subroutine evt_shower_final (object)
    class(evt_shower_t), intent(inout) :: object
    if (object%settings%powheg_matching) &
      call object%powheg%write_statistics ()
  end subroutine evt_shower_final

```

Matching functions

Generate fake ckkw weights. This can be dropped, once information from the matrix element generation is available.

```

<Shower: public>+≡
  public :: ckkw_fake_pseudo_shower_weights
<Shower: procedures>+≡
  subroutine ckkw_fake_pseudo_shower_weights &
    (settings, &
     ckkw_pseudo_shower_weights, particle_set)
    class(matching_settings_t), intent(inout) :: settings
    type(ckkw_pseudo_shower_weights_t), intent(inout) :: &
      ckkw_pseudo_shower_weights
    type(particle_set_t), intent(in) :: particle_set
    type(particle_t) :: prt
    integer :: i, j
    integer :: n
    type(vector4_t) :: momentum

    select type (settings)
    type is (ckkw_matching_settings_t)
      settings%alphaS = 1.0_default
      settings%Qmin = 1.0_default
      settings%n_max_jets = 3
    class default
      call msg_fatal ("CKKW matching called with wrong data.")
    end select

    n = 2**particle_set%get_n_tot()
    if (allocated (ckkw_pseudo_shower_weights%weights)) then
      deallocate (ckkw_pseudo_shower_weights%weights)
    end if
    allocate (ckkw_pseudo_shower_weights%weights (1:n))
    do i = 1, n
      momentum = vector4_null
      do j = 1, particle_set%get_n_tot ()
        if (btest (i,j-1)) then
          prt = particle_set%get_particle (j)
          momentum = momentum + prt%get_momentum ()
        end if
      end do
    end do

```

```

        if (momentum**1 > 0.0) then
            ckkw_pseudo_shower_weights%weights(i) = 1.0 / (momentum**2)
        end if
    end do
    ! equally distribute the weights by type
    if (allocated (ckkw_pseudo_shower_weights%weights_by_type)) then
        deallocate (ckkw_pseudo_shower_weights%weights_by_type)
    end if
    allocate (ckkw_pseudo_shower_weights%weights_by_type (1:n, 0:4))
    do i = 1, n
        do j = 0, 4
            ckkw_pseudo_shower_weights%weights_by_type(i,j) = &
                0.2 * ckkw_pseudo_shower_weights%weights(i)
        end do
    end do
end subroutine ckkw_fake_pseudo_shower_weights

```

28.4.3 Unit Tests

```

<Shower: public>+≡
    public :: shower_test

<Shower: tests>≡
    subroutine shower_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Shower: execute tests>
end subroutine shower_test

```

Testbed

This sequence sets up a two-jet process, ready for generating events.

```

<Shower: tests>+≡
    <setup testbed>

<setup testbed>≡
    subroutine setup_testbed &
        (prefix, os_data, lib, model_list, process, process_instance)
        type(string_t), intent(in) :: prefix
        type(os_data_t), intent(out) :: os_data
        type(process_library_t), intent(out), target :: lib
        type(model_list_t), intent(out) :: model_list
        class(model_data_t), pointer :: model
        type(model_t), pointer :: model_tmp
        type(process_t), target, intent(out) :: process
        type(process_instance_t), target, intent(out) :: process_instance
        type(var_list_t), pointer :: model_vars
        type(string_t) :: model_name, libname, procname, run_id
        type(process_def_entry_t), pointer :: entry
        type(string_t), dimension(:), allocatable :: prt_in, prt_out
        type(qcd_t) :: qcd
        class(rng_factory_t), allocatable :: rng_factory
    end subroutine

```

```

class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
real(default) :: sqrts

model_name = "SM"
libname = prefix // "_lib"
procname = prefix // "p"
run_id = "1"

call os_data_init (os_data)
allocate (rng_tao_factory_t :: rng_factory)
allocate (model_tmp)
call model_list%read_model (model_name, model_name // ".mdl", &
    os_data, model_tmp)
model_vars => model_tmp%get_var_list_ptr ()
call var_list_set_real (model_vars, var_str ("me"), 0._default, &
    is_known = .true.)
model => model_tmp

call lib%init (libname)

allocate (prt_in (2), source = [var_str ("e-"), var_str ("e+")])
allocate (prt_out (2), source = [var_str ("d"), var_str ("dbar")])

allocate (entry)
call entry%init (procname, model, n_in = 2, n_components = 1)
call omega_make_process_component (entry, 1, &
    model_name, prt_in, prt_out, &
    report_progress=.true.)
call lib%append (entry)

call lib%configure (os_data)
call lib%write_makefile (os_data, force = .true.)
call lib%clean (os_data, distclean = .false.)
call lib%write_driver (force = .true.)
call lib%load (os_data)

call process%init (procname, run_id, lib, os_data, &
    qcd, rng_factory, model)

allocate (prc_omega_t :: core_template)
allocate (mci_midpoint_t :: mci_template)
allocate (phs_single_config_t :: phs_config_template)

model => process%get_model_ptr ()

select type (core_template)
type is (prc_omega_t)
    call core_template%set_parameters (model = model)
end select
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

```

```

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()
call process%setup_mci ()
call process%setup_terms ()

call process_instance%init (process)
call process%integrate (process_instance, 1, 1, 1000)
call process%final_integration (1)

call process_instance%setup_event_data ()
call process_instance%init_simulation (1)
call process%generate_weighted_event (process_instance, 1)
call process_instance%evaluate_event_data ()

end subroutine setup_testbed

```

Trivial Test

We generate a two-jet event and shower it using default settings, i.e. in disabled mode.

```

(Shower: execute tests)≡
  call test (shower_1, "shower_1", &
    "disabled shower", &
    u, results)

(Shower: tests)+≡
  subroutine shower_1 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(process_library_t), target :: lib
    type(model_list_t) :: model_list
    class(model_data_t), pointer :: model
    type(model_t), pointer :: model_hadrons
    type(process_t), target :: process
    type(process_instance_t), target :: process_instance
    type(pdf_data_t) :: pdf_data
    integer :: factorization_mode
    logical :: keep_correlations
    class(evt_t), allocatable, target :: evt_trivial
    class(evt_t), allocatable, target :: evt_shower
    type(shower_settings_t) :: settings

    write (u, "(A)")  "* Test output: shower_1"
    write (u, "(A)")  "* Purpose: Two-jet event with disabled shower"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize environment"
    write (u, "(A)")

    call syntax_model_file_init ()
    call os_data_init (os_data)
    call model_list%read_model &

```

```

        (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"), &
        os_data, model_hadrons)
call setup_testbed (var_str ("shower_1"), &
        os_data, lib, model_list, process, process_instance)

write (u, "(A)")  "* Set up trivial transform"
write (u, "(A)")

allocate (evt_trivial_t :: evt_trivial)
model => process%get_model_ptr ()
call evt_trivial%connect (process_instance, model)
call evt_trivial%prepare_new_event (1, 1)
call evt_trivial%generate_unweighted ()

factorization_mode = FM_IGNORE_HELICITY
keep_correlations = .false.
call evt_trivial%make_particle_set (factorization_mode, keep_correlations)

select type (evt_trivial)
type is (evt_trivial_t)
    call evt_trivial%write (u)
    call write_separator (u, 2)
end select

write (u, "(A)")
write (u, "(A)")  "* Set up shower event transform"
write (u, "(A)")

allocate (evt_shower_t :: evt_shower)
select type (evt_shower)
type is (evt_shower_t)
    call evt_shower%init (settings, model_hadrons, os_data)
    allocate (shower_t :: evt_shower%shower)
    call evt_shower%shower%init (evt_shower%settings, pdf_data)
    call evt_shower%connect (process_instance, model)
end select

evt_trivial%next => evt_shower
evt_shower%previous => evt_trivial

call evt_shower%prepare_new_event (1, 1)
call evt_shower%generate_unweighted ()
call evt_shower%make_particle_set (factorization_mode, keep_correlations)

select type (evt_shower)
type is (evt_shower_t)
    call evt_shower%write (u)
    call write_separator (u, 2)
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call evt_shower%final ()

```

```

call evt_trivial%final ()
call process_instance%final ()
call process%final ()
call lib%final ()
call model_hadrons%final ()
deallocate (model_hadrons)
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: shower_1"

end subroutine shower_1

```

FSR Shower

We generate a two-jet event and shower it with the Whizard FSR shower.

```

<Shower: execute tests>+≡
  call test (shower_2, "shower_2", &
    "final-state shower", &
    u, results)

<Shower: tests>+≡
  subroutine shower_2 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    type(process_library_t), target :: lib
    type(model_list_t) :: model_list
    type(model_t), pointer :: model_hadrons
    class(model_data_t), pointer :: model
    type(process_t), target :: process
    type(process_instance_t), target :: process_instance
    integer :: factorization_mode
    logical :: keep_correlations
    type(pdf_data_t) :: pdf_data
    class(evt_t), allocatable, target :: evt_trivial
    class(evt_t), allocatable, target :: evt_shower
    type(shower_settings_t) :: settings

    write (u, "(A)")  "* Test output: shower_2"
    write (u, "(A)")  "*   Purpose: Two-jet event with FSR shower"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize environment"
    write (u, "(A)")

    call syntax_model_file_init ()
    call os_data_init (os_data)
    call model_list%read_model &
      (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"), &
      os_data, model_hadrons)
    call setup_testbed (var_str ("shower_2"), &
      os_data, lib, model_list, process, process_instance)
    model => process%get_model_ptr ()
  end subroutine shower_2

```



```

write (u, "(A)")  "* Set up trivial transform"
write (u, "(A)")

allocate (evt_trivial_t :: evt_trivial)
call evt_trivial%connect (process_instance, model)
call evt_trivial%prepare_new_event (1, 1)
call evt_trivial%generate_unweighted ()

factorization_mode = FM_IGNORE_HELICITY
keep_correlations = .false.
call evt_trivial%make_particle_set (factorization_mode, keep_correlations)

select type (evt_trivial)
type is (evt_trivial_t)
    call evt_trivial%write (u)
    call write_separator (u, 2)
end select

write (u, "(A)")
write (u, "(A)")  "* Set up shower event transform"
write (u, "(A)")

settings%fsr_active = .true.

allocate (evt_shower_t :: evt_shower)
select type (evt_shower)
type is (evt_shower_t)
    call evt_shower%init (settings, model_hadrons, os_data)
    allocate (shower_t :: evt_shower%shower)
    call evt_shower%shower%init (evt_shower%settings, pdf_data)
    call evt_shower%connect (process_instance, model)
end select

evt_trivial%next => evt_shower
evt_shower%previous => evt_trivial

call evt_shower%prepare_new_event (1, 1)
call evt_shower%generate_unweighted ()
call evt_shower%make_particle_set (factorization_mode, keep_correlations)

select type (evt_shower)
type is (evt_shower_t)
    call evt_shower%write (u, testflag = .true.)
    call write_separator (u, 2)
end select

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call evt_shower%final ()
call evt_trivial%final ()
call process_instance%final ()
call process%final ()

```

```

call lib%final ()
call model_hadrons%final ()
deallocate (model_hadrons)
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: shower_2"

end subroutine shower_2

```

28.5 Complete Events

This module combines hard processes with decay chains, shower, and hadronization (not implemented yet) to complete events. It also manages the input and output of event records in various formats.

```

<events.f90>≡
  <File header>

  module events

    <Use kinds>
    <Use strings>
    use constants, only: one
    use io_units
    use format_utils, only: pac_fmt, write_separator
    use format_defs, only: FMT_12, FMT_14, FMT_19
    use unit_tests
    use diagnostics
    use os_interface
    use subevents
    use variables
    use expr_base
    use model_data
    use state_matrices
    use particles
    use interactions
    use subevt_expr
    use rng_base
    use process_libraries
    use processes
    use process_stacks
    use event_base
    use event_transforms
    use decays

    <Standard module head>

    <Events: public>

    <Events: types>

```

⟨Events: interfaces⟩

contains

⟨Events: procedures⟩

⟨Events: tests⟩

end module events

28.5.1 Event configuration

The parameters govern the transformation of an event to a particle set.

The **safety_factor** reduces the acceptance probability for unweighting. If greater than one, excess events become less likely, but the reweighting efficiency also drops.

The **sigma** and **n** values, if nontrivial, allow for reweighting the events according to the requested **norm_mode**.

Various **parse_node_t** objects are taken from the SINDARIN input. They encode expressions that apply to the current event. The workspaces for evaluating those expressions are set up in the **event_expr_t** objects. Note that these are really pointers, so the actual nodes are not stored inside the event object.

⟨Events: types⟩≡

```

type :: event_config_t
  logical :: unweighted = .false.
  integer :: norm_mode = NORM_UNDEFINED
  integer :: factorization_mode = FM_IGNORE_HELICITY
  logical :: keep_correlations = .false.
  real(default) :: sigma = 1
  integer :: n = 1
  real(default) :: safety_factor = 1
  class(expr_factory_t), allocatable :: ef_selection
  class(expr_factory_t), allocatable :: ef_reweight
  class(expr_factory_t), allocatable :: ef_analysis
contains
  ⟨Events: event config: TBP⟩
end type event_config_t

```

Output.

⟨Events: event config: TBP⟩≡

```

procedure :: write => event_config_write

```

⟨Events: procedures⟩≡

```

subroutine event_config_write (object, unit, show_expressions)
  class(event_config_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: show_expressions
  integer :: u
  u = given_output_unit (unit)
  write (u, "(3x,A,L1)") "Unweighted          = ", object%unweighted
  write (u, "(3x,A,A)") "Normalization      = ", &
    char (event_normalization_string (object%norm_mode))
  write (u, "(3x,A)", advance="no") "Helicity handling = "

```

```

select case (object%factorization_mode)
case (FM_IGNORE_HELICITY)
    write (u, "(A)") "drop"
case (FM_SELECT_HELICITY)
    write (u, "(A)") "select"
case (FM_FACTOR_HELICITY)
    write (u, "(A)") "factorize"
end select
write (u, "(3x,A,L1)") "Keep correlations = ", object%keep_correlations
if (.not. nearly_equal (object%safety_factor, one)) then
    write (u, "(3x,A," // FMT_12 // ")") &
        "Safety factor      = ", object%safety_factor
end if
if (present (show_expressions)) then
    if (show_expressions) then
        if (allocated (object%ef_selection)) then
            call write_separator (u)
            write (u, "(3x,A)") "Event selection expression:"
            call object%ef_selection%write (u)
        end if
        if (allocated (object%ef_reweight)) then
            call write_separator (u)
            write (u, "(3x,A)") "Event reweighting expression:"
            call object%ef_reweight%write (u)
        end if
        if (allocated (object%ef_analysis)) then
            call write_separator (u)
            write (u, "(3x,A)") "Analysis expression:"
            call object%ef_analysis%write (u)
        end if
    end if
end if
end if
end subroutine event_config_write

```

28.5.2 The event type

This is the concrete implementation of the `generic_event_t` core that is defined above in the `event_base` module. The core manages the main (dressed) particle set pointer and the current values for weights and sqme. The implementation adds configuration data, expressions, process references, and event transforms.

Each event refers to a single elementary process. This process may be dressed by a shower, a decay chain etc. We maintain pointers to a process instance.

A list of event transforms (class `evt_t`) transform the connected interactions of the process instance into the final particle set. In this list, the first transform is always the trivial one, which just factorizes the process instance. Subsequent transforms may apply decays, etc. The `particle_set` pointer identifies the particle set that we want to be analyzed and returned by the event, usually the last one.

Squared matrix element and weight values: when reading events from file, the `ref` value is the number in the file, while the `prc` value is the number that we calculate from the momenta in the file, possibly with different parameters.

When generating events the first time, or if we do not recalculate, the numbers should coincide. Furthermore, the array of `alt` values is copied from an array of alternative event records. These values should represent calculated values.

The `sqme` and `weight` values mirror corresponding values in the `expr` subobject. The idea is that when generating or reading events, the event record is filled first, then the `expr` object acquires copies. These copies are used for writing events and as targets for pointer variables in the analysis expression.

All data that involve user-provided expressions (selection, reweighting, analysis) are handled by the `expr` subobject. In particular, evaluating the event-selection expression sets the `passed` flag. Furthermore, the `expr` subobject collects data that can be used in the analysis and should be written to file, including copies of `sqme` and `weight`.

```

<Events: public>≡
    public :: event_t

<Events: types>+≡
    type, extends (generic_event_t) :: event_t
        type(event_config_t) :: config
        type(process_t), pointer :: process => null ()
        type(process_instance_t), pointer :: instance => null ()
        class(rng_t), allocatable :: rng
        integer :: selected_i_mci = 0
        integer :: selected_i_term = 0
        integer :: selected_channel = 0
        logical :: is_complete = .false.
        class(evt_t), pointer :: transform_first => null ()
        class(evt_t), pointer :: transform_last => null ()
        type(event_expr_t) :: expr
        logical :: selection_evaluated = .false.
        logical :: passed = .false.
        real(default), allocatable :: alpha_qcd_forced
        real(default), allocatable :: scale_forced
        real(default) :: reweight = 1
        logical :: analysis_flag = .false.
    contains
        <Events: event: TBP>
    end type event_t

```

Finalizer: the list of event transforms is deleted iteratively.

```

<Events: event: TBP>≡
    procedure :: final => event_final

<Events: procedures>+≡
    subroutine event_final (object)
        class(event_t), intent(inout) :: object
        class(evt_t), pointer :: evt
        if (allocated (object%rng)) call object%rng%final ()
        call object%expr%final ()
        do while (associated (object%transform_first))
            evt => object%transform_first
            object%transform_first => evt%next
            call evt%final ()
        end do
        deallocate (evt)
    end subroutine event_final

```

```

end do
end subroutine event_final

```

Output.

Particle set: this is a pointer to one of the event transforms, so it should suffice to print the latter.

```

<Events: event: TBP>+≡
  procedure :: write => event_write

<Events: procedures>+≡
  subroutine event_write (object, unit, show_process, show_transforms, &
    show_decay, verbose, testflag)
    class(event_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_process, show_transforms, show_decay
    logical, intent(in), optional :: verbose
    logical, intent(in), optional :: testflag
    logical :: prc, trans, dec, verb
    class(evt_t), pointer :: evt
    character(len=7) :: fmt
    integer :: u, i
    call pac_fmt (fmt, FMT_19, FMT_14, testflag)
    u = given_output_unit (unit)
    prc = .true.; if (present (show_process)) prc = show_process
    trans = .true.; if (present (show_transforms)) trans = show_transforms
    dec = .true.; if (present (show_decay)) dec = show_decay
    verb = .false.; if (present (verbose)) verb = verbose
    call write_separator (u, 2)
    if (object%is_complete) then
      write (u, "(1x,A)" "Event"
    else
      write (u, "(1x,A)" "Event [incomplete]"
    end if
    call write_separator (u)
    call object%config%write (u)
    if (object%sqme_ref_is_known () .or. object%weight_ref_is_known ()) then
      call write_separator (u)
    end if
    if (object%sqme_ref_is_known ()) then
      write (u, "(3x,A," // fmt // ")") &
        "Squared matrix el. = ", object%get_sqme_ref ()
      if (object%sqme_alt_is_known ()) then
        do i = 1, object%get_n_alt ()
          write (u, "(5x,A," // fmt // ",1x,I0)" &
            "alternate sqme = ", object%get_sqme_alt(i), i
          end do
        end if
      end if
    end if
    if (object%weight_ref_is_known ()) then
      write (u, "(3x,A," // fmt // ")") &
        "Event weight = ", object%get_weight_ref ()
      if (object%weight_alt_is_known ()) then
        do i = 1, object%get_n_alt ()
          write (u, "(5x,A," // fmt // ",1x,I0)" &

```

```

        "alternate weight = ", object%get_weight_alt(i), i
    end do
end if
end if
if (object%selected_i_mci /= 0) then
    call write_separator (u)
    write (u, "(3x,A,I0)") "Selected MCI group = ", object%selected_i_mci
    write (u, "(3x,A,I0)") "Selected term      = ", object%selected_i_term
    write (u, "(3x,A,I0)") "Selected channel = ", object%selected_channel
end if
if (object%selection_evaluated) then
    call write_separator (u)
    write (u, "(3x,A,L1)") "Passed selection = ", object%passed
    if (object%passed) then
        write (u, "(3x,A," // fmt // ")") &
            "Reweighting factor = ", object%reweight
        write (u, "(3x,A,L1)") &
            "Analysis flag      = ", object%analysis_flag
    end if
end if
if (associated (object%instance)) then
    if (prc) then
        if (verb) then
            call object%instance%write (u, testflag)
        else
            call object%instance%write_header (u)
        end if
    end if
    if (trans) then
        evt => object%transform_first
        do while (associated (evt))
            select type (evt)
            type is (evt_decay_t)
                call evt%write (u, verbose = dec, more_verbose = verb, &
                    testflag = testflag)
            class default
                call evt%write (u, verbose = verb, testflag = testflag)
            end select
            call write_separator (u, 2)
            evt => evt%next
        end do
    else
        call write_separator (u, 2)
    end if
    if (object%expr%subevt_filled) then
        call object%expr%write (u, pacified = testflag)
        call write_separator (u, 2)
    end if
else
    call write_separator (u, 2)
    write (u, "(1x,A)") "Process instance: [undefined]"
    call write_separator (u, 2)
end if
end subroutine event_write

```

28.5.3 Initialization

Initialize: set configuration parameters, using a variable list. We do not call this `init`, because this method name will be used by a type extension.

The default normalization is `NORM_SIGMA`, since the default generation mode is weighted.

For unweighted events, we may want to apply a safety factor to event rejection. (By default, this factor is unity and can be ignored.)

We also allocate the trivial event transform, which is always the first one.

```
<Events: event: TBP>+≡
  procedure :: basic_init => event_init

<Events: procedures>+≡
  subroutine event_init (event, var_list, n_alt)
    class(event_t), intent(out) :: event
    type(var_list_t), intent(in), optional :: var_list
    integer, intent(in), optional :: n_alt
    type(string_t) :: norm_string
    logical :: polarized_events
    if (present (n_alt)) then
      call event%base_init (n_alt)
      call event%expr%init (n_alt)
    else
      call event%base_init (0)
    end if
    if (present (var_list)) then
      event%config%unweighted = var_list%get_lval (&
        var_str ("?unweighted"))
      norm_string = var_list%get_sval (&
        var_str ("sample_normalization"))
      event%config%norm_mode = &
        event_normalization_mode (norm_string, event%config%unweighted)
      polarized_events = &
        var_list%get_lval (var_str ("?polarized_events"))
      if (polarized_events) then
        event%config%factorization_mode = FM_SELECT_HELICITY
      else
        event%config%factorization_mode = FM_IGNORE_HELICITY
      end if
      if (event%config%unweighted) then
        event%config%safety_factor = var_list%get_rval (&
          var_str ("safety_factor"))
      end if
    else
      event%config%norm_mode = NORM_SIGMA
    end if
    allocate (evt_trivial_t :: event%transform_first)
    event%transform_last => event%transform_first
  end subroutine event_init
```


Set the `sigma` and `n` values in the configuration record that determine non-standard event normalizations. If these numbers are not set explicitly, the default value for both is unity, and event renormalization has no effect.

```

<Events: event: TBP>+≡
  procedure :: set_sigma => event_set_sigma
  procedure :: set_n => event_set_n

<Events: procedures>+≡
  elemental subroutine event_set_sigma (event, sigma)
    class(event_t), intent(inout) :: event
    real(default), intent(in) :: sigma
    event%config%sigma = sigma
  end subroutine event_set_sigma

  elemental subroutine event_set_n (event, n)
    class(event_t), intent(inout) :: event
    integer, intent(in) :: n
    event%config%n = n
  end subroutine event_set_n

```

Append an event transform (decays, etc.). The transform is not yet connected to a process. The transform is then considered to belong to the event object, and will be finalized together with it. The original pointer is removed.

We can assume that the trivial transform is already present in the event object, at least.

```

<Events: event: TBP>+≡
  procedure :: import_transform => event_import_transform

<Events: procedures>+≡
  subroutine event_import_transform (event, evt)
    class(event_t), intent(inout) :: event
    class(evt_t), intent(inout), pointer :: evt
    event%transform_last%next => evt
    evt%previous => event%transform_last
    event%transform_last => evt
    evt => null ()
  end subroutine event_import_transform

```

We link the event to an existing process instance. This includes the variable list, which is linked to the process variable list. Note that this is not necessarily identical to the variable list used for event initialization.

The variable list will contain pointers to `event` subobjects, therefore the `target` attribute.

Once we have a process connected, we can use it to obtain an event generator instance.

The model and process stack may be needed by event transforms. The current model setting may be different from the model in the process (regarding unstable particles, etc.). The process stack can be used for assigning extra processes that we need for the event transforms.

```

<Events: event: TBP>+≡
  procedure :: connect => event_connect

```

```

<Events: procedures>+≡
subroutine event_connect (event, process_instance, model, process_stack)
  class(event_t), intent(inout), target :: event
  type(process_instance_t), intent(in), target :: process_instance
  class(model_data_t), intent(in), target :: model
  type(process_stack_t), intent(in), optional :: process_stack
  type(string_t) :: id
  integer :: num_id
  class(evt_t), pointer :: evt
  event%process => process_instance%process
  event%instance => process_instance
  id = event%process%get_id ()
  if (id /= "") call event%expr%set_process_id (id)
  num_id = event%process%get_num_id ()
  if (num_id /= 0) call event%expr%set_process_num_id (num_id)
  call event%expr%setup_vars (event%process%get_sqrts ())
  call event%expr%link_var_list (event%process%get_var_list_ptr ())
  call event%process%make_rng (event%rng)
  evt => event%transform_first
  do while (associated (evt))
    call evt%connect (process_instance, model, process_stack)
    evt => evt%next
  end do
end subroutine event_connect

```

Set the parse nodes for the associated expressions, individually. The parse-node pointers may be null.

```

<Events: event: TBP>+≡
  procedure :: set_selection => event_set_selection
  procedure :: set_reweight => event_set_reweight
  procedure :: set_analysis => event_set_analysis

<Events: procedures>+≡
subroutine event_set_selection (event, ef_selection)
  class(event_t), intent(inout) :: event
  class(expr_factory_t), intent(in) :: ef_selection
  allocate (event%config%ef_selection, source = ef_selection)
end subroutine event_set_selection

subroutine event_set_reweight (event, ef_reweight)
  class(event_t), intent(inout) :: event
  class(expr_factory_t), intent(in) :: ef_reweight
  allocate (event%config%ef_reweight, source = ef_reweight)
end subroutine event_set_reweight

subroutine event_set_analysis (event, ef_analysis)
  class(event_t), intent(inout) :: event
  class(expr_factory_t), intent(in) :: ef_analysis
  allocate (event%config%ef_analysis, source = ef_analysis)
end subroutine event_set_analysis

```

Create evaluation trees from the parse trees. The **target** attribute is required because the expressions contain pointers to event subobjects.

```

<Events: event: TBP>+≡
  procedure :: setup_expressions => event_setup_expressions

<Events: procedures>+≡
  subroutine event_setup_expressions (event)
    class(event_t), intent(inout), target :: event
    call event%expr%setup_selection (event%config%ef_selection)
    call event%expr%setup_analysis (event%config%ef_analysis)
    call event%expr%setup_reweight (event%config%ef_reweight)
  end subroutine event_setup_expressions

```

28.5.4 Evaluation

To fill the `particle_set`, i.e., the event record proper, we have to apply all event transforms in order. The last transform should fill its associated particle set, factorizing the state matrix according to the current settings. There are several parameters in the event configuration that control this.

We always fill the particle set for the first transform (the hard process) and the last transform, if different from the first (the fully dressed process).

Each event transform is an event generator of its own. We choose to generate an *unweighted* event for each of them, even if the master event is assumed to be weighted. Thus, the overall event weight is the one of the hard process only. (There may be more options in future extensions.)

We can generate the two random numbers that the factorization needs. For testing purpose, we allow for providing them explicitly, as an option.

```

<Events: event: TBP>+≡
  procedure :: evaluate_transforms => event_evaluate_transforms

<Events: procedures>+≡
  subroutine event_evaluate_transforms (event, r)
    class(event_t), intent(inout) :: event
    real(default), dimension(:), intent(in), optional :: r
    class(evt_t), pointer :: evt
    integer :: i_term
    call event%discard_particle_set ()
    call event%check ()
    if (event%instance%is_complete_event ()) then
      call event%instance%select_i_term (i_term)
      event%selected_i_term = i_term
      evt => event%transform_first
      do while (associated (evt))
        call evt%prepare_new_event &
          (event%selected_i_mci, event%selected_i_term)
        evt => evt%next
      end do
      evt => event%transform_first
      do while (associated (evt))
        call evt%generate_unweighted ()
        if (signal_is_pending ()) return
        call evt%make_particle_set (event%config%factorization_mode, &
          event%config%keep_correlations)
        if (signal_is_pending ()) return
      end do
    end if
  end subroutine event_evaluate_transforms

```

```

        if (.not. evt%particle_set_exists) exit
        evt => evt%next
    end do
    evt => event%transform_last
    if (associated (evt) .and. evt%particle_set_exists) then
        call event%link_particle_set (evt%particle_set)
    end if
end if
end if
end subroutine event_evaluate_transforms

```

Evaluate the event-related expressions, given a valid `particle_set`. If `update_sqme` is set, we use the process instance for the `sqme_prc` value. The `sqme_ref` value is always taken from the event record.

Note: without the explicit `particle_set` pointer, some gfortran 4.8 version corrupts its memory.

(Events: event: TBP)+≡

```

    procedure :: evaluate_expressions => event_evaluate_expressions

```

(Events: procedures)+≡

```

    subroutine event_evaluate_expressions (event)
    class(event_t), intent(inout) :: event
    type(particle_set_t), pointer :: particle_set
    if (event%has_valid_particle_set ()) then
        particle_set => event%get_particle_set_ptr ()
        call event%expr%fill_subevt (particle_set)
    end if
    if (event%weight_ref_is_known ()) then
        call event%expr%set (weight_ref = event%get_weight_ref ())
    end if
    if (event%weight_prc_is_known ()) then
        call event%expr%set (weight_prc = event%get_weight_prc ())
    end if
    if (event%excess_prc_is_known ()) then
        call event%expr%set (excess_prc = event%get_excess_prc ())
    end if
    if (event%sqme_ref_is_known ()) then
        call event%expr%set (sqme_ref = event%get_sqme_ref ())
    end if
    if (event%sqme_prc_is_known ()) then
        call event%expr%set (sqme_prc = event%get_sqme_prc ())
    end if
    if (event%has_valid_particle_set ()) then
        call event%expr%evaluate &
            (event%passed, event%reweight, event%analysis_flag)
        event%selection_evaluated = .true.
    end if
end subroutine event_evaluate_expressions

```

Report the result of the selection evaluation.

(Events: event: TBP)+≡

```

    procedure :: passed_selection => event_passed_selection

```

(Events: procedures)+≡

```

function event_passed_selection (event) result (flag)
  class(event_t), intent(in) :: event
  logical :: flag
  flag = event%passed
end function event_passed_selection

```

Set alternate sqme and weight arrays. This should be merged with the previous routine, if the expressions are allowed to refer to these values.

```

<Events: event: TBP>+≡
  procedure :: store_alt_values => event_store_alt_values

<Events: procedures>+≡
  subroutine event_store_alt_values (event)
    class(event_t), intent(inout) :: event
    if (event%weight_alt_is_known ()) then
      call event%expr%set (weight_alt = event%get_weight_alt ())
    end if
    if (event%sqme_alt_is_known ()) then
      call event%expr%set (sqme_alt = event%get_sqme_alt ())
    end if
  end subroutine event_store_alt_values

```

28.5.5 Reset to empty state

Applying this, current event contents are marked as incomplete but are not deleted. In particular, the initialization is kept.

```

<Events: event: TBP>+≡
  procedure :: reset => event_reset

<Events: procedures>+≡
  subroutine event_reset (event)
    class(event_t), intent(inout) :: event
    class(evt_t), pointer :: evt
    call event%base_reset ()
    event%selected_i_mci = 0
    event%selected_i_term = 0
    event%selected_channel = 0
    event%is_complete = .false.
    call event%expr%reset ()
    event%selection_evaluated = .false.
    event%passed = .false.
    event%analysis_flag = .false.
    if (associated (event%instance)) then
      call event%instance%reset (reset_mci = .true.)
    end if
    if (allocated (event%alpha_qcd_forced)) deallocate (event%alpha_qcd_forced)
    if (allocated (event%scale_forced)) deallocate (event%scale_forced)
    evt => event%transform_first
    do while (associated (evt))
      call evt%reset ()
      evt => evt%next
    end do
  end subroutine event_reset

```

```
end subroutine event_reset
```

28.5.6 Squared Matrix Element and Weight

Transfer the result of the process instance calculation to the event record header.

```
<Events: event: TBP>+≡
  procedure :: import_instance_results => event_import_instance_results

<Events: procedures>+≡
  subroutine event_import_instance_results (event)
    class(event_t), intent(inout) :: event
    if (associated (event%instance)) then
      if (event%instance%has_evaluated_trace ()) then
        call event%set ( &
          sqme_prc = event%instance%get_sqme (), &
          weight_prc = event%instance%get_weight (), &
          excess_prc = event%instance%get_excess () &
        )
      end if
    end if
  end subroutine event_import_instance_results
```

Duplicate the instance result / the reference result in the event record.

```
<Events: event: TBP>+≡
  procedure :: accept_sqme_ref => event_accept_sqme_ref
  procedure :: accept_sqme_prc => event_accept_sqme_prc
  procedure :: accept_weight_ref => event_accept_weight_ref
  procedure :: accept_weight_prc => event_accept_weight_prc

<Events: procedures>+≡
  subroutine event_accept_sqme_ref (event)
    class(event_t), intent(inout) :: event
    if (event%sqme_ref_is_known ()) then
      call event%set (sqme_prc = event%get_sqme_ref ())
    end if
  end subroutine event_accept_sqme_ref

  subroutine event_accept_sqme_prc (event)
    class(event_t), intent(inout) :: event
    if (event%sqme_prc_is_known ()) then
      call event%set (sqme_ref = event%get_sqme_prc ())
    end if
  end subroutine event_accept_sqme_prc

  subroutine event_accept_weight_ref (event)
    class(event_t), intent(inout) :: event
    if (event%weight_ref_is_known ()) then
      call event%set (weight_prc = event%get_weight_ref ())
    end if
  end subroutine event_accept_weight_ref

  subroutine event_accept_weight_prc (event)
    class(event_t), intent(inout) :: event
```

```

        if (event%weight_prc_is_known ()) then
            call event%set (weight_ref = event%get_weight_prc ())
        end if
    end subroutine event_accept_weight_prc

```

Update the weight normalization, just after generation. Unweighted and weighted events are generated with a different default normalization. The intended normalization is stored in the configuration record.

```

<Events: event: TBP>+≡
    procedure :: update_normalization => event_update_normalization

<Events: procedures>+≡
    subroutine event_update_normalization (event, mode_ref)
        class(event_t), intent(inout) :: event
        integer, intent(in), optional :: mode_ref
        integer :: mode_old
        real(default) :: weight, excess
        if (present (mode_ref)) then
            mode_old = mode_ref
        else if (event%config%unweighted) then
            mode_old = NORM_UNIT
        else
            mode_old = NORM_SIGMA
        end if
        weight = event%get_weight_prc ()
        call event_normalization_update (weight, &
            event%config%sigma, event%config%n, &
            mode_new = event%config%norm_mode, &
            mode_old = mode_old)
        call event%set_weight_prc (weight)
        excess = event%get_excess_prc ()
        call event_normalization_update (excess, &
            event%config%sigma, event%config%n, &
            mode_new = event%config%norm_mode, &
            mode_old = mode_old)
        call event%set_excess_prc (excess)
    end subroutine event_update_normalization

```

The event is complete if it has a particle set plus valid entries for the sqme and weight values.

```

<Events: event: TBP>+≡
    procedure :: check => event_check

<Events: procedures>+≡
    subroutine event_check (event)
        class(event_t), intent(inout) :: event
        event%is_complete = event%has_valid_particle_set () &
            .and. event%sqme_ref_is_known () &
            .and. event%sqme_prc_is_known () &
            .and. event%weight_ref_is_known () &
            .and. event%weight_prc_is_known ()
        if (event%get_n_alt () /= 0) then
            event%is_complete = event%is_complete &
                .and. event%sqme_alt_is_known () &

```

```

        .and. event%weight_alt_is_known ()
    end if
end subroutine event_check

```

28.5.7 Generation

Assuming that we have a valid process associated to the event, we generate an event. We complete the event data, then factorize the spin density matrix and transfer it to the particle set.

When done, we retrieve squared matrix element and weight. In case of explicit generation, the reference values coincide with the process values, so we accept the latter.

The explicit random number argument `r` should be generated by a random-number generator. It is taken for the factorization algorithm, bypassing the event-specific random-number generator. This is useful for deterministic testing.

```

<Events: event: TBP>+≡
  procedure :: generate => event_generate

<Events: procedures>+≡
  subroutine event_generate (event, i_mci, r)
    class(event_t), intent(inout) :: event
    integer, intent(in) :: i_mci
    real(default), dimension(:), intent(in), optional :: r
    call event%reset ()
    event%selected_i_mci = i_mci
    if (event%config%unweighted) then
      call event%process%generate_unweighted_event (event%instance, i_mci)
      if (signal_is_pending ()) return
      call event%instance%evaluate_event_data ()
      call event%instance%normalize_weight ()
    else
      call event%process%generate_weighted_event (event%instance, i_mci)
      if (signal_is_pending ()) return
      call event%instance%evaluate_event_data ()
    end if
    event%selected_channel = event%instance%get_channel ()
    call event%import_instance_results ()
    call event%accept_sqme_prc ()
    call event%update_normalization ()
    call event%accept_weight_prc ()
    call event%evaluate_transforms (r)
    if (signal_is_pending ()) return
    call event%check ()
  end subroutine event_generate

```

Get a copy of the particle set belonging to the hard process.

```

<Events: event: TBP>+≡
  procedure :: get_hard_particle_set => event_get_hard_particle_set

<Events: procedures>+≡
  subroutine event_get_hard_particle_set (event, pset)
    class(event_t), intent(in) :: event

```



```

type(particle_set_t), intent(out) :: pset
class(evt_t), pointer :: evt
evt => event%transform_first
pset = evt%particle_set
end subroutine event_get_hard_particle_set

```

28.5.8 Recovering an event

Select MC group, term, and integration channel.

```

<Events: event: TBP>+≡
  procedure :: select => event_select

<Events: procedures>+≡
  subroutine event_select (event, i_mci, i_term, channel)
    class(event_t), intent(inout) :: event
    integer, intent(in) :: i_mci, i_term, channel
    if (associated (event%instance)) then
      event%selected_i_mci = i_mci
      event%selected_i_term = i_term
      event%selected_channel = channel
    else
      call msg_bug ("Event: select term: process instance undefined")
    end if
  end subroutine event_select

```

Copy a particle set into the event record.

We deliberately use the first (the trivial) transform for this, i.e., the hard process. The event reader may either read in the transformed event separately, or apply all event transforms to the hard particle set to (re)generate a fully dressed event.

Since this makes all subsequent event transforms invalid, we call `reset` on them.

```

<Events: event: TBP>+≡
  procedure :: set_hard_particle_set => event_set_hard_particle_set

<Events: procedures>+≡
  subroutine event_set_hard_particle_set (event, particle_set)
    class(event_t), intent(inout) :: event
    type(particle_set_t), intent(in) :: particle_set
    class(evt_t), pointer :: evt
    evt => event%transform_first
    call evt%set_particle_set (particle_set, &
      event%selected_i_mci, event%selected_i_term)
    call event%link_particle_set (evt%particle_set)
    evt => evt%next
    do while (associated (evt))
      call evt%reset ()
      evt => evt%next
    end do
  end subroutine event_set_hard_particle_set

```

Set the α_s value that should be used in a recalculation. This should be called only if we explicitly want to override the QCD setting of the process core.

```

<Events: event: TBP>+≡
  procedure :: set_alpha_qcd_forced => event_set_alpha_qcd_forced

<Events: procedures>+≡
  subroutine event_set_alpha_qcd_forced (event, alpha_qcd)
    class(event_t), intent(inout) :: event
    real(default), intent(in) :: alpha_qcd
    if (allocated (event%alpha_qcd_forced)) then
      event%alpha_qcd_forced = alpha_qcd
    else
      allocate (event%alpha_qcd_forced, source = alpha_qcd)
    end if
  end subroutine event_set_alpha_qcd_forced

```

Analogously, for the common scale. This forces also renormalization and factorization scale.

```

<Events: event: TBP>+≡
  procedure :: set_scale_forced => event_set_scale_forced

<Events: procedures>+≡
  subroutine event_set_scale_forced (event, scale)
    class(event_t), intent(inout) :: event
    real(default), intent(in) :: scale
    if (allocated (event%scale_forced)) then
      event%scale_forced = scale
    else
      allocate (event%scale_forced, source = scale)
    end if
  end subroutine event_set_scale_forced

```

Here we try to recover an event from the `particle_set` subobject and recalculate the structure functions and matrix elements. We have the appropriate `process` object and an initialized `process_instance` at hand, so beam and configuration data are known. From the `particle_set`, we get the momenta.

The quantum-number information may be incomplete, e.g., helicity information may be partial or absent. We recover the event just from the momentum configuration.

We do not transfer the matrix element from the process instance to the event record, as we do when generating an event. The event record may contain the matrix element as read from file, and the current calculation may use different parameters. We thus can compare old and new values.

The event `weight` may also be known already. If yes, we pass it to the `evaluate_event_data` procedure. It should already be normalized. If we have an `weight_factor` value, we obtain the event weight by multiplying the computed `sqme` by this factor. Otherwise, we make use of the MCI setup (which should be valid then) to compute the event weight, and we should normalize the result just as when generating events.

Evaluating event expressions must also be done separately.

```

<Events: event: TBP>+≡
  procedure :: recalculate => event_recalculate

```

```

(Events: procedures) +=
  subroutine event_recalculate &
    (event, update_sqme, weight_factor, recover_beams)
    class(event_t), intent(inout) :: event
    logical, intent(in) :: update_sqme
    real(default), intent(in), optional :: weight_factor
    logical, intent(in), optional :: recover_beams
    type(particle_set_t), pointer :: particle_set
    integer :: i_mci, i_term, channel
    if (event%has_valid_particle_set ()) then
      particle_set => event%get_particle_set_ptr ()
      i_mci = event%selected_i_mci
      i_term = event%selected_i_term
      channel = event%selected_channel
      if (i_mci == 0 .or. i_term == 0 .or. channel == 0) then
        call msg_bug ("Event: recalculate: undefined selection parameters")
      end if
      call event%instance%choose_mci (i_mci)
      call event%instance%set_trace (particle_set, i_term, recover_beams)
      if (allocated (event%alpha_qcd_forced)) then
        call event%instance%set_alpha_qcd_forced &
          (i_term, event%alpha_qcd_forced)
      end if
      call event%instance%recover (channel, i_term, update_sqme, &
        event%scale_forced)
      if (signal_is_pending ()) return
      if (update_sqme .and. present (weight_factor)) then
        call event%instance%evaluate_event_data &
          (weight = event%instance%get_sqme () * weight_factor)
      else if (event%weight_ref_is_known ()) then
        call event%instance%evaluate_event_data &
          (weight = event%get_weight_ref ())
      else
        call event%process%recover_event (event%instance, i_term)
        if (signal_is_pending ()) return
        call event%instance%evaluate_event_data ()
        if (event%config%unweighted) then
          call event%instance%normalize_weight ()
        end if
      end if
      if (signal_is_pending ()) return
      if (update_sqme) then
        call event%import_instance_results ()
      else
        call event%accept_sqme_ref ()
        call event%accept_weight_ref ()
      end if
    else
      call msg_bug ("Event: can't recalculate, particle set is undefined")
    end if
  end subroutine event_recalculate

```

28.5.9 Access content

Pointer to the associated process object (the associated model).

```
<Events: event: TBP>+≡
  procedure :: get_process_ptr => event_get_process_ptr
  procedure :: get_process_instance_ptr => event_get_process_instance_ptr
  procedure :: get_model_ptr => event_get_model_ptr

<Events: procedures>+≡
  function event_get_process_ptr (event) result (ptr)
    class(event_t), intent(in) :: event
    type(process_t), pointer :: ptr
    ptr => event%process
  end function event_get_process_ptr

  function event_get_process_instance_ptr (event) result (ptr)
    class(event_t), intent(in) :: event
    type(process_instance_t), pointer :: ptr
    ptr => event%instance
  end function event_get_process_instance_ptr

  function event_get_model_ptr (event) result (model)
    class(event_t), intent(in) :: event
    class(model_data_t), pointer :: model
    model => event%process%get_model_ptr ()
  end function event_get_model_ptr
```

Return the current values of indices: the MCI group of components, the term index (different terms corresponding, potentially, to different effective kinematics), and the MC integration channel. The `i_mci` call is delegated to the current process instance.

```
<Events: event: TBP>+≡
  procedure :: get_i_mci => event_get_i_mci
  procedure :: get_i_term => event_get_i_term
  procedure :: get_channel => event_get_channel

<Events: procedures>+≡
  function event_get_i_mci (event) result (i_mci)
    class(event_t), intent(in) :: event
    integer :: i_mci
    i_mci = event%selected_i_mci
  end function event_get_i_mci

  function event_get_i_term (event) result (i_term)
    class(event_t), intent(in) :: event
    integer :: i_term
    i_term = event%selected_i_term
  end function event_get_i_term

  function event_get_channel (event) result (channel)
    class(event_t), intent(in) :: event
    integer :: channel
    channel = event%selected_channel
  end function event_get_channel
```

This flag tells us whether the event consists just of a hard process (i.e., holds at most the first, trivial transform), or is a dressed events with additional transforms.

```

<Events: event: TBP>+≡
  procedure :: has_transform => event_has_transform

<Events: procedures>+≡
  function event_has_transform (event) result (flag)
    class(event_t), intent(in) :: event
    logical :: flag
    if (associated (event%transform_first)) then
      flag = associated (event%transform_first%next)
    else
      flag = .false.
    end if
  end function event_has_transform

```

Return the currently selected normalization mode, or alternate normalization mode.

```

<Events: event: TBP>+≡
  procedure :: get_norm_mode => event_get_norm_mode

<Events: procedures>+≡
  elemental function event_get_norm_mode (event) result (norm_mode)
    class(event_t), intent(in) :: event
    integer :: norm_mode
    norm_mode = event%config%norm_mode
  end function event_get_norm_mode

```

Return the kinematical weight, defined as the ratio of event weight and squared matrix element.

```

<Events: event: TBP>+≡
  procedure :: get_kinematical_weight => event_get_kinematical_weight

<Events: procedures>+≡
  function event_get_kinematical_weight (event) result (f)
    class(event_t), intent(in) :: event
    real(default) :: f
    if (event%sqme_ref_is_known () .and. event%weight_ref_is_known () &
      .and. abs (event%get_sqme_ref ()) > 0) then
      f = event%get_weight_ref () / event%get_sqme_ref ()
    else
      f = 0
    end if
  end function event_get_kinematical_weight

```

Return data used by external event formats.

```

<Events: event: TBP>+≡
  procedure :: get_index => event_get_index
  procedure :: get_fac_scale => event_get_fac_scale
  procedure :: get_alpha_s => event_get_alpha_s

```

```

<Events: procedures>+≡
function event_get_index (event) result (index)
  class(event_t), intent(in) :: event
  integer :: index
  index = event%expr%index
end function event_get_index

function event_get_fac_scale (event) result (fac_scale)
  class(event_t), intent(in) :: event
  real(default) :: fac_scale
  fac_scale = event%instance%get_fac_scale (event%selected_i_term)
end function event_get_fac_scale

function event_get_alpha_s (event) result (alpha_s)
  class(event_t), intent(in) :: event
  real(default) :: alpha_s
  alpha_s = event%instance%get_alpha_s (event%selected_i_term)
end function event_get_alpha_s

```

Eliminate numerical noise in the subevt expression and in the event transforms (which includes associated process instances).

```

<Events: public>+≡
public :: pacify

<Events: interfaces>≡
interface pacify
  module procedure pacify_event
end interface pacify

<Events: procedures>+≡
subroutine pacify_event (event)
  class(event_t), intent(inout) :: event
  class(evt_t), pointer :: evt
  call event%pacify_particle_set ()
  if (event%expr%subevt_filled) call pacify (event%expr)
  evt => event%transform_first
  do while (associated (evt))
    select type (evt)
      type is (evt_decay_t); call pacify (evt)
    end select
    evt => evt%next
  end do
end subroutine pacify_event

```

28.5.10 Unit tests

```

<Events: public>+≡
public :: events_test

<Events: tests>≡
subroutine events_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results

```

```

    <Events: execute tests>
end subroutine events_test

```

Empty event record

```

<Events: execute tests>≡
    call test (events_1, "events_1", &
        "empty event record", &
        u, results)

<Events: tests>+≡
    subroutine events_1 (u)
        integer, intent(in) :: u
        type(event_t), target :: event

        write (u, "(A)")  "* Test output: events_1"
        write (u, "(A)")  "* Purpose: display an empty event object"
        write (u, "(A)")

        call event%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Test output end: events_1"

    end subroutine events_1

```

Simple event

```

<Events: execute tests>+≡
    call test (events_2, "events_2", &
        "generate event", &
        u, results)

<Events: tests>+≡
    subroutine events_2 (u)
        integer, intent(in) :: u
        type(event_t), allocatable, target :: event
        type(process_t), allocatable, target :: process
        type(process_instance_t), allocatable, target :: process_instance
        type(model_data_t), target :: model

        write (u, "(A)")  "* Test output: events_2"
        write (u, "(A)")  "* Purpose: generate and display an event"
        write (u, "(A)")

        call model%init_test ()

        write (u, "(A)")  "* Generate test process event"

        allocate (process)
        allocate (process_instance)
        call prepare_test_process (process, process_instance, model)
        call process_instance%setup_event_data ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Initialize event object"

allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

write (u, "(A)")
write (u, "(A)")  "* Generate test process event"

call process%generate_weighted_event (process_instance, 1)

write (u, "(A)")
write (u, "(A)")  "* Fill event object"
write (u, "(A)")

call event%generate (1, [0.4_default, 0.4_default])
call event%evaluate_expressions ()
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call event%final ()
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

!   call model_list%final ()
!   call syntax_model_file_final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: events_2"

end subroutine events_2

```

Recovering an event

Generate an event and store the particle set. Then reset the event record, recall the particle set, and recover the event from that.

Note: The extra `particle_set_ptr` auxiliary is a workaround for memory corruption in gfortran 4.7.

```

<Events: execute tests>+≡
  call test (events_4, "events_4", &
    "recover event", &
    u, results)

<Events: tests>+≡
  subroutine events_4 (u)

```



```

integer, intent(in) :: u
type(event_t), allocatable, target :: event
type(process_t), allocatable, target :: process
type(process_instance_t), allocatable, target :: process_instance
type(particle_set_t) :: particle_set
type(particle_set_t), pointer :: particle_set_ptr
type(model_data_t), target :: model

write (u, "(A)")  "* Test output: events_4"
write (u, "(A)")  "* Purpose: generate and recover an event"
write (u, "(A)")

call model%init_test ()

write (u, "(A)")  "* Generate test process event and save particle set"
write (u, "(A)")

allocate (process)
allocate (process_instance)
call prepare_test_process (process, process_instance, model)
call process_instance%setup_event_data ()

allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

call event%generate (1, [0.4_default, 0.4_default])
call event%evaluate_expressions ()
call event%write (u)

particle_set_ptr => event%get_particle_set_ptr ()
particle_set = particle_set_ptr

call event%final ()
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

write (u, "(A)")
write (u, "(A)")  "* Recover event from particle set"
write (u, "(A)")

allocate (process)
allocate (process_instance)
call prepare_test_process (process, process_instance, model)
call process_instance%setup_event_data ()

allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

call event%select (1, 1, 1)

```

```

call event%set_hard_particle_set (particle_set)
call event%recalculate (update_sqme = .true.)
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Transfer sqme and evaluate expressions"
write (u, "(A)")

call event%accept_sqme_prc ()
call event%accept_weight_prc ()
call event%check ()
call event%evaluate_expressions ()
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Reset contents"
write (u, "(A)")

call event%reset ()
event%transform_first%particle_set_exists = .false.
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call particle_set%final ()

call event%final ()
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

!   call model_list%final ()
!   call syntax_model_file_final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: events_4"

end subroutine events_4

```

Partially Recovering an event

Generate an event and store the particle set. Then reset the event record, recall the particle set, and recover the event as far as possible without recomputing the squared matrix element.

```

(Events: execute tests)+≡
  call test (events_5, "events_5", &
    "partially recover event", &
    u, results)

```

<Events: tests>+≡

```
subroutine events_5 (u)
  integer, intent(in) :: u
  type(event_t), allocatable, target :: event
  type(process_t), allocatable, target :: process
  type(process_instance_t), allocatable, target :: process_instance
  type(particle_set_t) :: particle_set
  type(particle_set_t), pointer :: particle_set_ptr
  real(default) :: sqme, weight
  type(model_data_t), target :: model

  write (u, "(A)")  "* Test output: events_5"
  write (u, "(A)")  "* Purpose: generate and recover an event"
  write (u, "(A)")

  call model%init_test ()

  write (u, "(A)")  "* Generate test process event and save particle set"
  write (u, "(A)")

  allocate (process)
  allocate (process_instance)
  call prepare_test_process (process, process_instance, model)
  call process_instance%setup_event_data ()

  allocate (event)
  call event%basic_init ()
  call event%connect (process_instance, process%get_model_ptr ())

  call event%generate (1, [0.4_default, 0.4_default])
  call event%evaluate_expressions ()
  call event%write (u)

  particle_set_ptr => event%get_particle_set_ptr ()
  particle_set = particle_set_ptr
  sqme = event%get_sqme_ref ()
  weight = event%get_weight_ref ()

  call event%final ()
  deallocate (event)

  call cleanup_test_process (process, process_instance)
  deallocate (process_instance)
  deallocate (process)

  write (u, "(A)")
  write (u, "(A)")  "* Recover event from particle set"
  write (u, "(A)")

  allocate (process)
  allocate (process_instance)
  call prepare_test_process (process, process_instance, model)
  call process_instance%setup_event_data ()
```

```

allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

call event%select (1, 1, 1)
call event%set_hard_particle_set (particle_set)
call event%recalculate (update_sqme = .false.)
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Manually set sqme and evaluate expressions"
write (u, "(A)")

call event%set (sqme_ref = sqme, weight_ref = weight)
call event%accept_sqme_ref ()
call event%accept_weight_ref ()
call event%evaluate_expressions ()
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call particle_set%final ()

call event%final ()
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

!   call model_list%final ()
!   call syntax_model_file_final ()
call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: events_5"

end subroutine events_5

```

Decays

Generate an event with subsequent decays.

```

<Events: execute tests>+≡
  call test (events_6, "events_6", &
    "decays", &
    u, results)

<Events: tests>+≡
  subroutine events_6 (u)
    integer, intent(in) :: u
    type(os_data_t) :: os_data
    class(model_data_t), pointer :: model

```

```

type(string_t) :: prefix, procname1, procname2
type(process_library_t), target :: lib
type(process_stack_t) :: process_stack
class(evt_t), pointer :: evt_decay
type(event_t), allocatable, target :: event
type(process_t), pointer :: process
type(process_instance_t), allocatable, target :: process_instance

write (u, "(A)")  "* Test output: events_6"
write (u, "(A)")  "* Purpose: generate an event with subsequent decays"
write (u, "(A)")

write (u, "(A)")  "* Generate test process and decay"
write (u, "(A)")

call os_data_init (os_data)

prefix = "events_6"
procname1 = prefix // "_p"
procname2 = prefix // "_d"
call prepare_testbed &
    (lib, process_stack, prefix, os_data, &
    scattering=.true., decay=.true.)

write (u, "(A)")  "* Initialize decay process"

process => process_stack%get_process_ptr (procname1)
model => process%get_model_ptr ()
call model%set_unstable (25, [procname2])

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
call process_instance%init_simulation (1)

write (u, "(A)")
write (u, "(A)")  "* Initialize event transform: decay"

allocate (evt_decay_t :: evt_decay)
call evt_decay%connect (process_instance, model, process_stack)

write (u, "(A)")
write (u, "(A)")  "* Initialize event object"
write (u, "(A)")

allocate (event)
call event%basic_init ()
call event%connect (process_instance, model)
call event%import_transform (evt_decay)

call event%write (u, show_decay = .true.)

write (u, "(A)")
write (u, "(A)")  "* Generate event"

```

```

write (u, "(A)")

call event%generate (1, [0.4_default, 0.4_default])
call event%evaluate_expressions ()
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call event%final ()
deallocate (event)

call process_instance%final ()
deallocate (process_instance)

call process_stack%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: events_6"

end subroutine events_6

```

Decays

Generate a decay event with varying options.

```

<Events: execute tests>+≡
  call test (events_7, "events_7", &
    "decay options", &
    u, results)

<Events: tests>+≡
subroutine events_7 (u)
  integer, intent(in) :: u
  type(os_data_t) :: os_data
  class(model_data_t), pointer :: model
  type(string_t) :: prefix, procname2
  type(process_library_t), target :: lib
  type(process_stack_t) :: process_stack
  type(process_t), pointer :: process
  type(process_instance_t), allocatable, target :: process_instance

  write (u, "(A)")  "* Test output: events_7"
  write (u, "(A)")  "* Purpose: check decay options"
  write (u, "(A)")

  write (u, "(A)")  "* Prepare test process"
  write (u, "(A)")

  call os_data_init (os_data)

  prefix = "events_7"
  procname2 = prefix // "_d"
  call prepare_testbed &

```

```

(lib, process_stack, prefix, os_data, &
scattering=.false., decay=.true.)

write (u, "(A)")  "* Generate decay event, default options"
write (u, "(A)")

process => process_stack%get_process_ptr (procname2)
model => process%get_model_ptr ()
call model%set_unstable (25, [procname2])

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data (model)
call process_instance%init_simulation (1)

call process%generate_weighted_event (process_instance, 1)
call process_instance%write (u)

call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Generate decay event, helicity-diagonal decay"
write (u, "(A)")

process => process_stack%get_process_ptr (procname2)
model => process%get_model_ptr ()
call model%set_unstable (25, [procname2], diagonal = .true.)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data (model)
call process_instance%init_simulation (1)

call process%generate_weighted_event (process_instance, 1)
call process_instance%write (u)

call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Generate decay event, isotropic decay, &
&polarized final state"
write (u, "(A)")

process => process_stack%get_process_ptr (procname2)
model => process%get_model_ptr ()
call model%set_unstable (25, [procname2], isotropic = .true.)
call model%set_polarized (6)
call model%set_polarized (-6)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data (model)

```

```

call process_instance%init_simulation (1)

call process%generate_weighted_event (process_instance, 1)
call process_instance%write (u)

call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process_stack%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: events_7"

end subroutine events_7

```

28.6 Raw Event I/O

The raw format is for internal use only. All data are stored unformatted, so they can be efficiently be re-read on the same machine, but not necessarily on another machine.

This module explicitly depends on the `events` module which provides the concrete implementation of `event_base`. The other I/O formats access only the methods that are defined in `event_base`.

```

⟨eio_raw.f90⟩≡
  ⟨File header⟩

  module eio_raw

    use kinds
    use io_units
    ⟨Use strings⟩
    use unit_tests
    use diagnostics

    use lorentz
    use variables
    use model_data
    use particles
    use event_base
    use eio_data
    use eio_base
    use events

    ⟨Standard module head⟩

    ⟨EIO raw: public⟩

    ⟨EIO raw: parameters⟩

```



```

    <EIO raw: types>

contains

    <EIO raw: procedures>

    <EIO raw: tests>

end module eio_raw

```

28.6.1 File Format Version

This is the current default file version.

```

<EIO raw: parameters>≡
    integer, parameter :: CURRENT_FILE_VERSION = 2

```

The user may change this number; this should force some compatibility mode for reading and writing. In any case, the file version stored in a event file that we read has to match the expected file version.

History of version numbers:

1. Format for WHIZARD 2.2.0 to 2.2.3. No version number stored in the raw file.
2. Format from 2.2.4 on. File contains version number. The file contains the transformed particle set (if applicable) after the hard-process particle set.

28.6.2 Type

Note the file version number. The default may be reset during initialization, which should enforce some compatibility mode.

```

<EIO raw: public>≡
    public :: eio_raw_t

<EIO raw: types>≡
    type, extends (eio_t) :: eio_raw_t
        logical :: reading = .false.
        logical :: writing = .false.
        integer :: unit = 0
        integer :: norm_mode = NORM_UNDEFINED
        real(default) :: sigma = 1
        integer :: n = 1
        integer :: n_alt = 0
        logical :: check = .false.
        integer :: file_version = CURRENT_FILE_VERSION
contains
    <EIO raw: eio raw: TBP>
end type eio_raw_t

```

Output. This is not the actual event format, but a readable account of the current object status.

```

(EIO raw: eio raw: TBP)≡
  procedure :: write => eio_raw_write

(EIO raw: procedures)≡
  subroutine eio_raw_write (object, unit)
    class(eio_raw_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Raw event stream:"
    write (u, "(3x,A,L1)") "Check MD5 sum      = ", object%check
    if (object%n_alt > 0) then
      write (u, "(3x,A,I0)") "Alternate weights = ", object%n_alt
    end if
    if (object%reading) then
      write (u, "(3x,A,A)") "Reading from file = ", char (object%filename)
    else if (object%writing) then
      write (u, "(3x,A,A)") "Writing to file   = ", char (object%filename)
    else
      write (u, "(3x,A)") "[closed]"
    end if
  end subroutine eio_raw_write

```

Finalizer: close any open file.

```

(EIO raw: eio raw: TBP)+≡
  procedure :: final => eio_raw_final

(EIO raw: procedures)+≡
  subroutine eio_raw_final (object)
    class(eio_raw_t), intent(inout) :: object
    if (object%reading .or. object%writing) then
      write (msg_buffer, "(A,A,A)") "Events: closing raw file '", &
        char (object%filename), "'"
      call msg_message ()
      close (object%unit)
      object%reading = .false.
      object%writing = .false.
    end if
  end subroutine eio_raw_final

```

Set the check flag which determines whether we compare checksums on input.

```

(EIO raw: eio raw: TBP)+≡
  procedure :: set_parameters => eio_raw_set_parameters

(EIO raw: procedures)+≡
  subroutine eio_raw_set_parameters (eio, check, version_string, extension)
    class(eio_raw_t), intent(inout) :: eio
    logical, intent(in), optional :: check
    type(string_t), intent(in), optional :: version_string
    type(string_t), intent(in), optional :: extension
    if (present (check)) eio%check = check
    if (present (version_string)) then

```

```

select case (char (version_string))
case ("", "2.2.4")
    eio%file_version = CURRENT_FILE_VERSION
case ("2.2")
    eio%file_version = 1
case default
    call msg_fatal ("Raw event I/O: unsupported version '" &
        // char (version_string) // "'")
    eio%file_version = 0
end select
end if
if (present (extension)) then
    eio%extension = extension
else
    eio%extension = "evx"
end if
end subroutine eio_raw_set_parameters

```

Initialize event writing.

```

<EIO raw: eio raw: TBP>+≡
    procedure :: init_out => eio_raw_init_out

<EIO raw: procedures>+≡
    subroutine eio_raw_init_out (eio, sample, data, success, extension)
        class(eio_raw_t), intent(inout) :: eio
        type(string_t), intent(in) :: sample
        type(event_sample_data_t), intent(in), optional :: data
        logical, intent(out), optional :: success
        type(string_t), intent(in), optional :: extension
        character(32) :: md5sum_prc, md5sum_cfg
        character(32), dimension(:), allocatable :: md5sum_alt
        integer :: i
        if (present (extension)) then
            eio%extension = extension
        else
            eio%extension = "evx"
        end if
        eio%filename = sample // "." // eio%extension
        eio%unit = free_unit ()
        write (msg_buffer, "(A,A,A)") "Events: writing to raw file '", &
            char (eio%filename), "'"
        call msg_message ()
        eio%writing = .true.
        if (present (data)) then
            md5sum_prc = data%md5sum_prc
            md5sum_cfg = data%md5sum_cfg
            eio%norm_mode = data%norm_mode
            eio%sigma = data%total_cross_section
            eio%n = data%n_evt
            eio%n_alt = data%n_alt
            if (eio%n_alt > 0) then
                !!! !!! !!! Workaround for gfortran 5.0 ICE
                allocate (md5sum_alt (data%n_alt))
                md5sum_alt = data%md5sum_alt
            end if
        end if
    end subroutine eio_raw_init_out

```

```

        !!! allocate (md5sum_alt (data%n_alt), source = data%md5sum_alt)
    end if
else
    md5sum_prc = ""
    md5sum_cfg = ""
end if
open (eio%unit, file = char (eio%filename), form = "unformatted", &
    action = "write", status = "replace")
select case (eio%file_version)
case (2:); write (eio%unit) eio%file_version
end select
write (eio%unit) md5sum_prc
write (eio%unit) md5sum_cfg
write (eio%unit) eio%norm_mode
write (eio%unit) eio%n_alt
do i = 1, eio%n_alt
    write (eio%unit) md5sum_alt(i)
end do
if (present (success)) success = .true.
end subroutine eio_raw_init_out

```

Initialize event reading.

(EIO raw: eio raw: TBP)+≡

```

    procedure :: init_in => eio_raw_init_in

```

(EIO raw: procedures)+≡

```

subroutine eio_raw_init_in (eio, sample, data, success, extension)
    class(eio_raw_t), intent(inout) :: eio
    type(string_t), intent(in) :: sample
    type(event_sample_data_t), intent(inout), optional :: data
    logical, intent(out), optional :: success
    type(string_t), intent(in), optional :: extension
    character(32) :: md5sum_prc, md5sum_cfg
    character(32), dimension(:), allocatable :: md5sum_alt
    integer :: i, file_version
    if (present (success)) success = .true.
    if (present (extension)) then
        eio%extension = extension
    else
        eio%extension = "evx"
    end if
    eio%filename = sample // "." // eio%extension
    eio%unit = free_unit ()
    if (present (data)) then
        eio%sigma = data%total_cross_section
        eio%n = data%n_evt
    end if
    write (msg_buffer, "(A,A,A)") "Events: reading from raw file '", &
        char (eio%filename), "'"
    call msg_message ()
    eio%reading = .true.
    open (eio%unit, file = char (eio%filename), form = "unformatted", &
        action = "read", status = "old")
    select case (eio%file_version)

```

```

case (2:); read (eio%unit) file_version
case default; file_version = 1
end select
if (file_version /= eio%file_version) then
    call msg_error ("Reading event file: raw-file version mismatch.")
    if (present (success)) success = .false.
    return
else if (file_version /= CURRENT_FILE_VERSION) then
    call msg_warning ("Reading event file: compatibility mode.")
end if
read (eio%unit) md5sum_prc
read (eio%unit) md5sum_cfg
read (eio%unit) eio%norm_mode
read (eio%unit) eio%n_alt
if (present (data)) then
    if (eio%n_alt /= data%n_alt) then
        if (present (success)) success = .false. !
        return
    end if
end if
allocate (md5sum_alt (eio%n_alt))
do i = 1, eio%n_alt
    read (eio%unit) md5sum_alt(i)
end do
if (present (success)) then
    if (present (data)) then
        if (eio%check) then
            if (data%md5sum_prc /= "") then
                success = success .and. md5sum_prc == data%md5sum_prc
            end if
            if (data%md5sum_cfg /= "") then
                success = success .and. md5sum_cfg == data%md5sum_cfg
            end if
            do i = 1, eio%n_alt
                if (data%md5sum_alt(i) /= "") then
                    success = success .and. md5sum_alt(i) == data%md5sum_alt(i)
                end if
            end do
        else
            call msg_warning ("Reading event file: MD5 sum check disabled")
        end if
    end if
end if
end subroutine eio_raw_init_in

```

Switch from input to output: reopen the file for reading.

(EIO raw: eio raw: TBP)+≡

```
procedure :: switch_inout => eio_raw_switch_inout
```

(EIO raw: procedures)+≡

```

subroutine eio_raw_switch_inout (eio, success)
class(eio_raw_t), intent(inout) :: eio
logical, intent(out), optional :: success
write (msg_buffer, "(A,A,A)") "Events: appending to raw file '", &

```

```

        char (eio%filename), ""
    call msg_message ()
    close (eio%unit, status = "keep")
    eio%reading = .false.
    open (eio%unit, file = char (eio%filename), form = "unformatted", &
        action = "write", position = "append", status = "old")
    eio%writing = .true.
    if (present (success)) success = .true.
end subroutine eio_raw_switch_inout

```

Output an event. Write first the event indices, then weight and squared matrix element, then the particle set.

We always write the particle set of the hard process. (Note: this should be reconsidered.) We do make a physical copy.

On output, we write the `prc` values for weight and `sqme`, since these are the values just computed. On input, we store the values as `ref` values. The caller can then decide whether to recompute values and thus obtain distinct `prc` values, or just accept them.

The `passed` flag is not written. This allow us to apply different selection criteria upon rereading.

```

(EIO raw: eio raw: TBP)+≡
    procedure :: output => eio_raw_output

(EIO raw: procedures)+≡
    subroutine eio_raw_output (eio, event, i_prc, reading, passed, pacify)
        class(eio_raw_t), intent(inout) :: eio
        class(generic_event_t), intent(in), target :: event
        logical, intent(in), optional :: reading, passed, pacify
        integer, intent(in) :: i_prc
        type(particle_set_t), pointer :: pset
        integer :: i
        if (eio%writing) then
            if (event%has_valid_particle_set ()) then
                select type (event)
                type is (event_t)
                    write (eio%unit) i_prc
                    write (eio%unit) event%get_i_mci ()
                    write (eio%unit) event%get_i_term ()
                    write (eio%unit) event%get_channel ()
                    write (eio%unit) event%expr%weight_prc
                    write (eio%unit) event%expr%excess_prc
                    write (eio%unit) event%expr%sqme_prc
                    do i = 1, eio%n_alt
                        write (eio%unit) event%expr%weight_alt(i)
                        write (eio%unit) event%expr%sqme_alt(i)
                    end do
                    allocate (pset)
                    call event%get_hard_particle_set (pset)
                    call pset%write_raw (eio%unit)
                    call pset%final ()
                    deallocate (pset)
                    select case (eio%file_version)
                    case (2:)

```

```

        if (event%has_transform ()) then
            write (eio%unit) .true.
            pset => event%get_particle_set_ptr ()
            call pset%write_raw (eio%unit)
        else
            write (eio%unit) .false.
        end if
    end select
class default
    call msg_bug ("Event: write raw: defined only for full event_t")
end select
else
    call msg_bug ("Event: write raw: particle set is undefined")
end if
else
    call eio%write ()
    call msg_fatal ("Raw event file is not open for writing")
end if
end subroutine eio_raw_output

```

Input an event.

Note: the particle set is physically copied. If there is a performance issue, we might choose to pointer-assign it instead, with a different version of `event%set_hard_particle_set`.

(EIO raw: eio raw: TBP)+≡

```

    procedure :: input_i_prc => eio_raw_input_i_prc
    procedure :: input_event => eio_raw_input_event

```

(EIO raw: procedures)+≡

```

subroutine eio_raw_input_i_prc (eio, i_prc, iostat)
    class(eio_raw_t), intent(inout) :: eio
    integer, intent(out) :: i_prc
    integer, intent(out) :: iostat
    if (eio%reading) then
        read (eio%unit, iostat = iostat) i_prc
    else
        call eio%write ()
        call msg_fatal ("Raw event file is not open for reading")
    end if
end subroutine eio_raw_input_i_prc

subroutine eio_raw_input_event (eio, event, iostat)
    class(eio_raw_t), intent(inout) :: eio
    class(generic_event_t), intent(inout), target :: event
    integer, intent(out) :: iostat
    integer :: i_mci, i_term, channel, i
    real(default) :: weight, excess, sqme
    real(default), dimension(:), allocatable :: weight_alt, sqme_alt
    logical :: has_transform
    type(particle_set_t), pointer :: pset
    class(model_data_t), pointer :: model
    if (eio%reading) then
        select type (event)
            type is (event_t)

```

```

read (eio%unit, iostat = iostat) i_mci
if (iostat /= 0) return
read (eio%unit, iostat = iostat) i_term
if (iostat /= 0) return
read (eio%unit, iostat = iostat) channel
if (iostat /= 0) return
read (eio%unit, iostat = iostat) weight
if (iostat /= 0) return
read (eio%unit, iostat = iostat) excess
if (iostat /= 0) return
read (eio%unit, iostat = iostat) sqme
if (iostat /= 0) return
call event%reset ()
call event%select (i_mci, i_term, channel)
if (eio%norm_mode /= NORM_UNDEFINED) then
    call event_normalization_update (weight, &
        eio%sigma, eio%n, event%get_norm_mode (), eio%norm_mode)
    call event_normalization_update (excess, &
        eio%sigma, eio%n, event%get_norm_mode (), eio%norm_mode)
end if
call event%set (sqme_ref = sqme, weight_ref = weight, &
    excess_prc = excess)
if (eio%n_alt /= 0) then
    allocate (sqme_alt (eio%n_alt), weight_alt (eio%n_alt))
    do i = 1, eio%n_alt
        read (eio%unit, iostat = iostat) weight_alt(i)
        if (iostat /= 0) return
        read (eio%unit, iostat = iostat) sqme_alt(i)
        if (iostat /= 0) return
    end do
    call event%set (sqme_alt = sqme_alt, weight_alt = weight_alt)
end if
model => null ()
if (associated (event%process)) then
    model => event%process%get_model_ptr ()
end if
allocate (pset)
call pset%read_raw (eio%unit, iostat)
if (iostat /= 0) return
if (associated (model)) call pset%set_model (model)
call event%set_hard_particle_set (pset)
call pset%final ()
deallocate (pset)
select case (eio%file_version)
case (2:)
    read (eio%unit, iostat = iostat) has_transform
    if (iostat /= 0) return
    if (has_transform) then
        allocate (pset)
        call pset%read_raw (eio%unit, iostat)
        if (iostat /= 0) return
        if (associated (model)) &
            call pset%set_model (model)
        call event%link_particle_set (pset)
    end if
end select

```



```

        end if
    end select
class default
    call msg_bug ("Event: read raw: defined only for full event_t")
end select
else
    call eio%write ()
    call msg_fatal ("Raw event file is not open for reading")
end if
end subroutine eio_raw_input_event

```

28.6.3 Unit tests

```

<EIO raw: public>+≡
    public :: eio_raw_test

<EIO raw: tests>≡
    subroutine eio_raw_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <EIO raw: execute tests>
    end subroutine eio_raw_test

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO raw: execute tests>≡
    call test (eio_raw_1, "eio_raw_1", &
        "read and write event contents", &
        u, results)

<EIO raw: tests>+≡
    subroutine eio_raw_1 (u)
        use processes
        integer, intent(in) :: u
        type(model_data_t), target :: model
        type(event_t), allocatable, target :: event
        type(process_t), allocatable, target :: process
        type(process_instance_t), allocatable, target :: process_instance
        class(eio_t), allocatable :: eio
        integer :: i_prc, iostat
        type(string_t) :: sample

        write (u, "(A)")  "* Test output: eio_raw_1"
        write (u, "(A)")  "* Purpose: generate and read/write an event"
        write (u, "(A)")

        write (u, "(A)")  "* Initialize test process"

        call model%init_test ()

        allocate (process)
    end subroutine eio_raw_1

```

```

allocate (process_instance)
call prepare_test_process (process, process_instance, model)
call process_instance%setup_event_data ()

allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_raw_1"

allocate (eio_raw_t :: eio)

call eio%init_out (sample)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()
call event%write (u)
write (u, "(A)")

call eio%output (event, i_prc = 42)
call eio%write (u)
call eio%final ()

call event%final ()
deallocate (event)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Re-read the event"
write (u, "(A)")

call eio%init_in (sample)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

call eio%input_i_prc (i_prc, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (i_prc):", iostat
call eio%input_event (event, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (event):", iostat
call eio%write (u)

write (u, "(A)")
write (u, "(1x,A,I0)") "i_prc = ", i_prc
write (u, "(A)")
call event%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Generate and append another event"
write (u, "(A)")

call eio%switch_inout ()
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()
call event%write (u)
write (u, "(A)")

call eio%output (event, i_prc = 5)
call eio%write (u)
call eio%final ()

call event%final ()
deallocate (event)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Re-read both events"
write (u, "(A)")

call eio%init_in (sample)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())

call eio%input_i_prc (i_prc, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (i_prc/1):", iostat
call eio%input_event (event, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (event/1):", iostat
call eio%input_i_prc (i_prc, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (i_prc/2):", iostat
call eio%input_event (event, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (event/2):", iostat
call eio%write (u)

write (u, "(A)")
write (u, "(1x,A,I0)") "i_prc = ", i_prc
write (u, "(A)")
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()
deallocate (eio)

```

```

call event%final ()
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

call model%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: eio_raw_1"

end subroutine eio_raw_1

```

Test I/O methods

We test the implementation of all I/O methods.

```

<EIO raw: execute tests>+≡
call test (eio_raw_2, "eio_raw_2", &
  "handle multiple weights", &
  u, results)

<EIO raw: tests>+≡
subroutine eio_raw_2 (u)
  use processes
  integer, intent(in) :: u
  type(model_data_t), target :: model
  type(var_list_t) :: var_list
  type(event_t), allocatable, target :: event
  type(process_t), allocatable, target :: process
  type(process_instance_t), allocatable, target :: process_instance
  type(event_sample_data_t) :: data
  class(eio_t), allocatable :: eio
  integer :: i_prc, iostat
  type(string_t) :: sample

  write (u, "(A)")  "* Test output: eio_raw_2"
  write (u, "(A)")  "*   Purpose: generate and read/write an event"
  write (u, "(A)")  "*               with multiple weights"
  write (u, "(A)")

  call model%init_test ()

  write (u, "(A)")  "* Initialize test process"

  allocate (process)
  allocate (process_instance)
  call prepare_test_process (process, process_instance, model)
  call process_instance%setup_event_data ()

  call data%init (n_proc = 1, n_alt = 2)

  call var_list_append_log (var_list, var_str ("?unweighted"), .false., &

```

```

        intrinsic = .true.)
call var_list_append_string (var_list, var_str ("sample_normalization"), &
    var_str ("auto"), intrinsic = .true.)
call var_list_append_real (var_list, var_str ("safety_factor"), &
    1._default, intrinsic = .true.)

allocate (event)
call event%basic_init (var_list, n_alt = 2)
call event%connect (process_instance, process%get_model_ptr ())

write (u, "(A)")
write (u, "(A)")  "* Generate and write an event"
write (u, "(A)")

sample = "eio_raw_2"

allocate (eio_raw_t :: eio)

call eio%init_out (sample, data)
call event%generate (1, [0._default, 0._default])
call event%evaluate_expressions ()
call event%set (sqme_alt = [2._default, 3._default])
call event%set (weight_alt = &
    [2 * event%get_weight_ref (), 3 * event%get_weight_ref ()])
call event%store_alt_values ()
call event%check ()

call event%write (u)
write (u, "(A)")

call eio%output (event, i_prc = 42)
call eio%write (u)
call eio%final ()

call event%final ()
deallocate (event)
call process_instance%final ()
deallocate (process_instance)

write (u, "(A)")
write (u, "(A)")  "* Re-read the event"
write (u, "(A)")

call eio%init_in (sample, data)

allocate (process_instance)
call process_instance%init (process)
call process_instance%setup_event_data ()
allocate (event)
call event%basic_init (var_list, n_alt = 2)
call event%connect (process_instance, process%get_model_ptr ())

call eio%input_i_prc (i_prc, iostat)
if (iostat /= 0) write (u, "(A,I0)")  "I/O error (i_prc):", iostat

```

```

call eio%input_event (event, iostat)
if (iostat /= 0) write (u, "(A,I0)") "I/O error (event):", iostat
call eio%write (u)

write (u, "(A)")
write (u, "(1x,A,I0)") "i_prc = ", i_prc
write (u, "(A)")
call event%write (u)

write (u, "(A)")
write (u, "(A)") "* Cleanup"

call eio%final ()
deallocate (eio)

call event%final ()
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

call model%final ()

write (u, "(A)")
write (u, "(A)") "* Test output end: eio_raw_2"

end subroutine eio_raw_2

```

28.7 User-controlled File I/O

The SINDARIN language includes commands that write output to file (input may be added later). We identify files by their name, and manage the unit internally. We need procedures for opening, closing, and printing files.

```

<user_files.f90>≡
  <File header>

  module user_files

    <Use strings>
    use io_units
    use diagnostics
    use ifiles
    use analysis

    <Standard module head>

    <User files: public>

    <User files: types>

```

```

<User files: interfaces>

contains

<User files: procedures>

end module user_files

```

28.7.1 The file type

This is a type that describes an open user file and its properties. The entry is part of a doubly-linked list.

```

<User files: types>≡
  type :: file_t
  private
    type(string_t) :: name
    integer :: unit = -1
    logical :: reading = .false.
    logical :: writing = .false.
    type(file_t), pointer :: prev => null ()
    type(file_t), pointer :: next => null ()
  end type file_t

```

The initializer opens the file.

```

<User files: procedures>≡
  subroutine file_init (file, name, action, status, position)
    type(file_t), intent(out) :: file
    type(string_t), intent(in) :: name
    character(len=*), intent(in) :: action, status, position
    file%unit = free_unit ()
    file%name = name
    open (unit = file%unit, file = char (file%name), &
          action = action, status = status, position = position)
    select case (action)
    case ("read")
      file%reading = .true.
    case ("write")
      file%writing = .true.
    case ("readwrite")
      file%reading = .true.
      file%writing = .true.
    end select
  end subroutine file_init

```

The finalizer closes it.

```

<User files: procedures>+≡
  subroutine file_final (file)
    type(file_t), intent(inout) :: file
    close (unit = file%unit)
    file%unit = -1
  end subroutine file_final

```

Check if a file is open with correct status.

```
<User files: procedures>+=  
function file_is_open (file, action) result (flag)  
  logical :: flag  
  type(file_t), intent(in) :: file  
  character(*), intent(in) :: action  
  select case (action)  
  case ("read")  
    flag = file%reading  
  case ("write")  
    flag = file%writing  
  case ("readwrite")  
    flag = file%reading .and. file%writing  
  case default  
    call msg_bug ("Checking file '" // char (file%name) &  
      // "' : illegal action specifier")  
  end select  
end function file_is_open
```

Write to the file. Error if in wrong mode. If there is no string, just write an empty record. If there is a string, respect the `advancing` option.

```
<User files: procedures>+=  
subroutine file_write_string (file, string, advancing)  
  type(file_t), intent(in) :: file  
  type(string_t), intent(in), optional :: string  
  logical, intent(in), optional :: advancing  
  if (file%writing) then  
    if (present (string)) then  
      if (present (advancing)) then  
        if (advancing) then  
          write (file%unit, "(A)") char (string)  
        else  
          write (file%unit, "(A)", advance="no") char (string)  
        end if  
      else  
        write (file%unit, "(A)") char (string)  
      end if  
    else  
      write (file%unit, *)  
    end if  
  else  
    call msg_error ("Writing to file: File '" // char (file%name) &  
      // "' is not open for writing.")  
  end if  
end subroutine file_write_string
```

Write a whole ifile, line by line.

```
<User files: procedures>+=  
subroutine file_write_ifile (file, ifile)  
  type(file_t), intent(in) :: file  
  type(ifile_t), intent(in) :: ifile  
  type(line_p) :: line  
  call line_init (line, ifile)
```



```

do while (line_is_associated (line))
  call file_write_string (file, line_get_string_advance (line))
end do
end subroutine file_write_ifile

```

Write an analysis object (or all objects) to an open file.

```

<User files: procedures>+≡
subroutine file_write_analysis (file, tag)
  type(file_t), intent(in) :: file
  type(string_t), intent(in), optional :: tag
  if (file%writing) then
    if (present (tag)) then
      call analysis_write (tag, unit = file%unit)
    else
      call analysis_write (unit = file%unit)
    end if
  else
    call msg_error ("Writing analysis to file: File ' " // char (file%name) &
      // "' is not open for writing.")
  end if
end subroutine file_write_analysis

```

28.7.2 The file list

We maintain a list of all open files and their attributes. The list must be doubly-linked because we may delete entries.

```

<User files: public>≡
public :: file_list_t

<User files: types>+≡
type :: file_list_t
  type(file_t), pointer :: first => null ()
  type(file_t), pointer :: last => null ()
end type file_list_t

```

There is no initialization routine, but a finalizer which deletes all:

```

<User files: public>+≡
public :: file_list_final

<User files: procedures>+≡
subroutine file_list_final (file_list)
  type(file_list_t), intent(inout) :: file_list
  type(file_t), pointer :: current
  do while (associated (file_list%first))
    current => file_list%first
    file_list%first => current%next
    call file_final (current)
    deallocate (current)
  end do
  file_list%last => null ()
end subroutine file_list_final

```

Find an entry in the list. Return null pointer on failure.

```
<User files: procedures>+≡
function file_list_get_file_ptr (file_list, name) result (current)
  type(file_t), pointer :: current
  type(file_list_t), intent(in) :: file_list
  type(string_t), intent(in) :: name
  current => file_list%first
  do while (associated (current))
    if (current%name == name) return
    current => current%next
  end do
end function file_list_get_file_ptr
```

Check if a file is open, public version:

```
<User files: public>+≡
public :: file_list_is_open

<User files: procedures>+≡
function file_list_is_open (file_list, name, action) result (flag)
  logical :: flag
  type(file_list_t), intent(in) :: file_list
  type(string_t), intent(in) :: name
  character(len=*), intent(in) :: action
  type(file_t), pointer :: current
  current => file_list_get_file_ptr (file_list, name)
  if (associated (current)) then
    flag = file_is_open (current, action)
  else
    flag = .false.
  end if
end function file_list_is_open
```

Append a new file entry, i.e., open this file. Error if it is already open.

```
<User files: public>+≡
public :: file_list_open

<User files: procedures>+≡
subroutine file_list_open (file_list, name, action, status, position)
  type(file_list_t), intent(inout) :: file_list
  type(string_t), intent(in) :: name
  character(len=*), intent(in) :: action, status, position
  type(file_t), pointer :: current
  if (.not. associated (file_list_get_file_ptr (file_list, name))) then
    allocate (current)
    call msg_message ("Opening file '" // char (name) // "' for output")
    call file_init (current, name, action, status, position)
    if (associated (file_list%last)) then
      file_list%last%next => current
      current%prev => file_list%last
    else
      file_list%first => current
    end if
    file_list%last => current
  else
```

```

        call msg_error ("Opening file: File '" // char (name) &
            // "' is already open.")
    end if
end subroutine file_list_open

```

Delete a file entry, i.e., close this file. Error if it is not open.

```

<User files: public>+≡
    public :: file_list_close

<User files: procedures>+≡
    subroutine file_list_close (file_list, name)
        type(file_list_t), intent(inout) :: file_list
        type(string_t), intent(in) :: name
        type(file_t), pointer :: current
        current => file_list_get_file_ptr (file_list, name)
        if (associated (current)) then
            if (associated (current%prev)) then
                current%prev%next => current%next
            else
                file_list%first => current%next
            end if
            if (associated (current%next)) then
                current%next%prev => current%prev
            else
                file_list%last => current%prev
            end if
            call msg_message ("Closing file '" // char (name) // "' for output")
            call file_final (current)
            deallocate (current)
        else
            call msg_error ("Closing file: File '" // char (name) &
                // "' is not open.")
        end if
    end subroutine file_list_close

```

Write a string to file. Error if it is not open.

```

<User files: public>+≡
    public :: file_list_write

<User files: interfaces>≡
    interface file_list_write
        module procedure file_list_write_string
        module procedure file_list_write_ifile
    end interface

<User files: procedures>+≡
    subroutine file_list_write_string (file_list, name, string, advancing)
        type(file_list_t), intent(in) :: file_list
        type(string_t), intent(in) :: name
        type(string_t), intent(in), optional :: string
        logical, intent(in), optional :: advancing
        type(file_t), pointer :: current
        current => file_list_get_file_ptr (file_list, name)
        if (associated (current)) then

```

```

        call file_write_string (current, string, advancing)
    else
        call msg_error ("Writing to file: File '" // char (name) &
            // "'is not open.")
    end if
end subroutine file_list_write_string

subroutine file_list_write_ifile (file_list, name, ifile)
    type(file_list_t), intent(in) :: file_list
    type(string_t), intent(in) :: name
    type(ifile_t), intent(in) :: ifile
    type(file_t), pointer :: current
    current => file_list_get_file_ptr (file_list, name)
    if (associated (current)) then
        call file_write_ifile (current, ifile)
    else
        call msg_error ("Writing to file: File '" // char (name) &
            // "'is not open.")
    end if
end subroutine file_list_write_ifile

```

Write an analysis object or all objects to data file. Error if it is not open. If the file name is empty, write to standard output.

```

<User files: public>+≡
    public :: file_list_write_analysis

<User files: procedures>+≡
    subroutine file_list_write_analysis (file_list, name, tag)
        type(file_list_t), intent(in) :: file_list
        type(string_t), intent(in) :: name
        type(string_t), intent(in), optional :: tag
        type(file_t), pointer :: current
        if (name == "") then
            if (present (tag)) then
                call analysis_write (tag)
            else
                call analysis_write
            end if
        else
            current => file_list_get_file_ptr (file_list, name)
            if (associated (current)) then
                call file_write_analysis (current, tag)
            else
                call msg_error ("Writing analysis to file: File '" // char (name) &
                    // "' is not open.")
            end if
        end if
    end subroutine file_list_write_analysis

```

28.8 Runtime data

```
<rt_data.f90>≡  
  <File header>  
  
  module rt_data  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use format_utils, only: write_separator  
    use unit_tests  
    use system_dependencies  
    use diagnostics  
    use pdf_builtin !NODEP!  
    use sf_lhapdf !NODEP!  
    use os_interface  
    use ifiles  
    use lexers  
    use parser  
    use models  
    use flavors  
    use jets  
    use subevents  
    use pdg_arrays  
    use variables  
    use eval_trees  
    use polarizations  
    use beams  
    use process_libraries  
    use prclib_stacks  
    use prc_core  
    use beam_structures  
    use user_files  
    use process_stacks  
    use iterations  
    use physics_defs  
  
    <Standard module head>  
  
    <RT data: public>  
  
    <RT data: types>  
  
    contains  
  
    <RT data: procedures>  
  
    <RT data: tests>  
  
  end module rt_data
```

28.8.1 Strategy for models and variables

The program manages its data via a main `rt_data_t` object. During program flow, various commands create and use local `rt_data_t` objects. Those transient blocks contain either pointers to global object or local copies which are deleted after use.

Each `rt_data_t` object contains a variable list component. This lists holds (local copies of) all kinds of intrinsic or user-defined variables. The variable list is linked to the variable list contained in the local process library. This, in turn, is linked to the variable list of the `rt_data_t` context, and so on.

A variable lookup will thus be recursively delegated to the linked variable lists, until a match is found. When modifying a variable which is not yet local, the program creates a local copy and uses this afterwards. Thus, when the local `rt_data_t` object is deleted, the context value is recovered.

Models are kept in a model list which is separate from the variable list. Otherwise, they are treated in a similar manner: the local list is linked to the context model list. Model lookup is thus recursively delegated. When a model or any part of it is modified, the model is copied to the local `rt_data_t` object, so the context model is not modified. Commands such as `integrate` will create their own copy of the current model (and of the current variable list) at the point where they are executed.

When a model is encountered for the first time, it is read from file. The reading is automatically delegated to the global context. Thus, this master copy survives until the main `rt_data_t` object is deleted, at program completion.

If there is a currently active model, its variable list is linked to the main variable list. Variable lookups will then start from the model variable list. When the current model is switched, the new active model will get this link instead. Consequently, a change to the current model is kept as long as this model has a local copy; it survives local model switches. On the other hand, a parameter change in the current model doesn't affect any other model, even if the parameter name is identical.

28.8.2 Container for parse nodes

The runtime data set contains a bunch of parse nodes (chunks of code that have not been compiled into evaluation trees but saved for later use). We collect them here.

This implementation has the useful effect that an assignment between two objects of this type will establish a pointer-target relationship for all components.

$\langle RT\ data: types \rangle \equiv$

```
type :: rt_parse_nodes_t
  type(parse_node_t), pointer :: cuts_lexpr => null ()
  type(parse_node_t), pointer :: scale_expr => null ()
  type(parse_node_t), pointer :: fac_scale_expr => null ()
  type(parse_node_t), pointer :: ren_scale_expr => null ()
  type(parse_node_t), pointer :: weight_expr => null ()
  type(parse_node_t), pointer :: selection_lexpr => null ()
  type(parse_node_t), pointer :: reweight_expr => null ()
  type(parse_node_t), pointer :: analysis_lexpr => null ()
  type(parse_node_p), dimension(:), allocatable :: alt_setup
```

```

contains
  <RT data: rt parse nodes: TBP>
end type rt_parse_nodes_t

```

Clear individual components. The parse nodes are nullified. No finalization needed since the pointer targets are part of the global parse tree.

```

<RT data: rt parse nodes: TBP>≡
  procedure :: clear => rt_parse_nodes_clear

<RT data: procedures>≡
  subroutine rt_parse_nodes_clear (rt_pn, name)
    class(rt_parse_nodes_t), intent(inout) :: rt_pn
    type(string_t), intent(in) :: name
    select case (char (name))
    case ("cuts")
      rt_pn%cuts_lexpr => null ()
    case ("scale")
      rt_pn%scale_expr => null ()
    case ("factorization_scale")
      rt_pn%fac_scale_expr => null ()
    case ("renormalization_scale")
      rt_pn%ren_scale_expr => null ()
    case ("weight")
      rt_pn%weight_expr => null ()
    case ("selection")
      rt_pn%selection_lexpr => null ()
    case ("reweight")
      rt_pn%reweight_expr => null ()
    case ("analysis")
      rt_pn%analysis_lexpr => null ()
    end select
  end subroutine rt_parse_nodes_clear

```

Output for the parse nodes.

```

<RT data: rt parse nodes: TBP>+≡
  procedure :: write => rt_parse_nodes_write

<RT data: procedures>+≡
  subroutine rt_parse_nodes_write (object, unit)
    class(rt_parse_nodes_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    call wrt ("Cuts", object%cuts_lexpr)
    call write_separator (u)
    call wrt ("Scale", object%scale_expr)
    call write_separator (u)
    call wrt ("Factorization scale", object%fac_scale_expr)
    call write_separator (u)
    call wrt ("Renormalization scale", object%ren_scale_expr)
    call write_separator (u)
    call wrt ("Weight", object%weight_expr)
    call write_separator (u, 2)
    call wrt ("Event selection", object%selection_lexpr)

```

```

call write_separator (u)
call wrt ("Event reweighting factor", object%reweight_expr)
call write_separator (u)
call wrt ("Event analysis", object%analysis_lexpr)
if (allocated (object%alt_setup)) then
  call write_separator (u, 2)
  write (u, "(1x,A,':')") "Alternative setups"
  do i = 1, size (object%alt_setup)
    call write_separator (u)
    call wrt ("Commands", object%alt_setup(i)%ptr)
  end do
end if
contains
subroutine wrt (title, pn)
  character(*), intent(in) :: title
  type(parse_node_t), intent(in), pointer :: pn
  if (associated (pn)) then
    write (u, "(1x,A,':')") title
    call write_separator (u)
    call parse_node_write_rec (pn, u)
  else
    write (u, "(1x,A,':',1x,A)") title, "[undefined]"
  end if
end subroutine wrt
end subroutine rt_parse_nodes_write

```

Screen output for individual components. (This should eventually be more condensed, currently we print the internal representation tree.)

<RT data: rt parse nodes: TBP>+≡

```
procedure :: show => rt_parse_nodes_show
```

<RT data: procedures>+≡

```

subroutine rt_parse_nodes_show (rt_pn, name, unit)
  class(rt_parse_nodes_t), intent(in) :: rt_pn
  type(string_t), intent(in) :: name
  integer, intent(in), optional :: unit
  type(parse_node_t), pointer :: pn
  integer :: u
  u = given_output_unit (unit)
  select case (char (name))
  case ("cuts")
    pn => rt_pn%cuts_lexpr
  case ("scale")
    pn => rt_pn%scale_expr
  case ("factorization_scale")
    pn => rt_pn%fac_scale_expr
  case ("renormalization_scale")
    pn => rt_pn%ren_scale_expr
  case ("weight")
    pn => rt_pn%weight_expr
  case ("selection")
    pn => rt_pn%selection_lexpr
  case ("reweight")
    pn => rt_pn%reweight_expr
  end select
end subroutine

```



```

case ("analysis")
  pn => rt_pn%analysis_lexpr
end select
if (associated (pn)) then
  write (u, "(A,1x,A,1x,A)") "Expression:", char (name), "(parse tree):"
  call parse_node_write_rec (pn, u)
else
  write (u, "(A,1x,A,A)") "Expression:", char (name), ": [undefined]"
end if
end subroutine rt_parse_nodes_show

```

28.8.3 The data type

This is a big data container which contains everything that is used and modified during the command flow. A local copy of this can be used to temporarily override defaults. The data set is transparent.

```

<RT data: public>≡
  public :: rt_data_t
<RT data: types>+≡
  type :: rt_data_t
    type(lexer_t), pointer :: lexer => null ()
    type(rt_data_t), pointer :: context => null ()
    type(var_list_t) :: var_list
    type(iterations_list_t) :: it_list
    type(os_data_t) :: os_data
    type(model_list_t) :: model_list
    type(model_t), pointer :: model => null ()
    logical :: model_is_copy = .false.
    type(model_t), pointer :: preload_model => null ()
    type(model_t), pointer :: fallback_model => null ()
    type(model_t), pointer :: radiation_model => null ()
    type(prclib_stack_t) :: prclib_stack
    type(process_library_t), pointer :: prclib => null ()
    type(beam_structure_t) :: beam_structure
    type(rt_parse_nodes_t) :: pn
    type(process_stack_t) :: process_stack
    type(string_t), dimension(:), allocatable :: sample_fmt
    type(file_list_t), pointer :: out_files => null ()
    logical :: quit = .false.
    integer :: quit_code = 0
    type(string_t) :: logfile
    logical :: nlo_calculation = .false.
    logical, dimension(4) :: active_nlo_components
  contains
    <RT data: rt data: TBP>
  end type rt_data_t

```

28.8.4 Output

```

<RT data: rt data: TBP>≡
  procedure :: write => rt_data_write

```

<RT data: procedures>+≡

```

subroutine rt_data_write (object, unit, vars, pacify)
  class(rt_data_t), intent(in) :: object
  integer, intent(in), optional :: unit
  type(string_t), dimension(:), intent(in), optional :: vars
  logical, intent(in), optional :: pacify
  integer :: u, i
  u = given_output_unit (unit)
  call write_separator (u, 2)
  write (u, "(1x,A)") "Runtime data:"
  if (present (vars)) then
    if (size (vars) /= 0) then
      call write_separator (u, 2)
      write (u, "(1x,A)") "Selected variables:"
      call write_separator (u)
      call object%write_vars (u, vars)
    end if
  else
    call write_separator (u, 2)
    if (associated (object%model)) then
      call object%model%write_var_list (u, follow_link=.true.)
    else
      call var_list_write (object%var_list, u, follow_link=.true.)
    end if
  end if
  if (object%it_list%get_n_pass () > 0) then
    call write_separator (u, 2)
    write (u, "(1x)", advance="no")
    call object%it_list%write (u)
  end if
  if (associated (object%model)) then
    call write_separator (u, 2)
    call object%model%write (u)
  end if
  call object%prclib_stack%write (u)
  call object%beam_structure%write (u)
  call write_separator (u, 2)
  call object%pn%write (u)
  if (allocated (object%sample_fmt)) then
    call write_separator (u)
    write (u, "(1x,A)", advance="no") "Event sample formats = "
    do i = 1, size (object%sample_fmt)
      if (i > 1) write (u, "(A,1x)", advance="no") ", "
      write (u, "(A)", advance="no") char (object%sample_fmt(i))
    end do
    write (u, "(A)")
  end if
  call object%process_stack%write (u, pacify)
  write (u, "(1x,A,1x,L1)") "quit      :", object%quit
  write (u, "(1x,A,1x,I0)") "quit_code:", object%quit_code
  call write_separator (u, 2)
  write (u, "(1x,A,1x,A)") "Logfile  :", "" // trim (char (object%logfile)) // ""
  call write_separator (u, 2)
end subroutine rt_data_write

```

Write only selected variables.

```
<RT data: rt data: TBP>+≡
  procedure :: write_vars => rt_data_write_vars

<RT data: procedures>+≡
  subroutine rt_data_write_vars (object, unit, vars)
    class(rt_data_t), intent(in), target :: object
    integer, intent(in), optional :: unit
    type(string_t), dimension(:), intent(in), optional :: vars
    type(var_list_t), pointer :: var_list
    integer :: u, i
    u = given_output_unit (unit)
    if (present (vars)) then
      var_list => object%get_var_list_ptr ()
      do i = 1, size (vars)
        associate (var => vars(i))
          if (var_list%contains (var, follow_link=.true.)) then
            call var_list_write_var (var_list, var, unit = u, &
              follow_link = .true.)
          end if
        end associate
      end do
    end if
  end subroutine rt_data_write_vars
```

Write only the model list.

```
<RT data: rt data: TBP>+≡
  procedure :: write_model_list => rt_data_write_model_list

<RT data: procedures>+≡
  subroutine rt_data_write_model_list (object, unit)
    class(rt_data_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    call object%model_list%write (u)
  end subroutine rt_data_write_model_list
```

Write only the library stack.

```
<RT data: rt data: TBP>+≡
  procedure :: write_libraries => rt_data_write_libraries

<RT data: procedures>+≡
  subroutine rt_data_write_libraries (object, unit, libpath)
    class(rt_data_t), intent(in) :: object
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: libpath
    integer :: u
    u = given_output_unit (unit)
    call object%prclib_stack%write (u, libpath)
  end subroutine rt_data_write_libraries
```

Write only the beam data.

```
<RT data: rt data: TBP>+≡  
  procedure :: write_beams => rt_data_write_beams  
  
<RT data: procedures>+≡  
  subroutine rt_data_write_beams (object, unit)  
    class(rt_data_t), intent(in) :: object  
    integer, intent(in), optional :: unit  
    integer :: u  
    u = given_output_unit (unit)  
    call write_separator (u, 2)  
    call object%beam_structure%write (u)  
    call write_separator (u, 2)  
  end subroutine rt_data_write_beams
```

Write only the process and event expressions.

```
<RT data: rt data: TBP>+≡  
  procedure :: write_expr => rt_data_write_expr  
  
<RT data: procedures>+≡  
  subroutine rt_data_write_expr (object, unit)  
    class(rt_data_t), intent(in) :: object  
    integer, intent(in), optional :: unit  
    integer :: u  
    u = given_output_unit (unit)  
    call write_separator (u, 2)  
    call object%pn%write (u)  
    call write_separator (u, 2)  
  end subroutine rt_data_write_expr
```

Write only the process stack.

```
<RT data: rt data: TBP>+≡  
  procedure :: write_process_stack => rt_data_write_process_stack  
  
<RT data: procedures>+≡  
  subroutine rt_data_write_process_stack (object, unit)  
    class(rt_data_t), intent(in) :: object  
    integer, intent(in), optional :: unit  
    call object%process_stack%write (unit)  
  end subroutine rt_data_write_process_stack
```

28.8.5 Clear

The `clear` command can remove the contents of various subobjects. The objects themselves should stay.

```
<RT data: rt data: TBP>+≡  
  procedure :: clear_beams => rt_data_clear_beams  
  
<RT data: procedures>+≡  
  subroutine rt_data_clear_beams (global)  
    class(rt_data_t), intent(inout) :: global  
    call global%beam_structure%final_sf ()  
    call global%beam_structure%final_pol ()
```

```

    call global%beam_structure%final_mom ()
end subroutine rt_data_clear_beams

```

28.8.6 Initialization

Initialize runtime data. This defines special variables such as `sqrts`, and should be done only for the instance that is actually global. Local copies will inherit the special variables.

We link the global variable list to the process stack variable list, so the latter is always available (and kept global).

```

<RT data: rt data: TBP>+≡
    procedure :: global_init => rt_data_global_init

<RT data: procedures>+≡
    subroutine rt_data_global_init (global, paths, logfile)
        class(rt_data_t), intent(out), target :: global
        type(paths_t), intent(in), optional :: paths
        type(string_t), intent(in), optional :: logfile
        logical, target, save :: known = .true.
        integer :: seed
        real(default), parameter :: real_specimen = 1.
        call os_data_init (global%os_data, paths)
        if (present (logfile)) then
            global%logfile = logfile
        else
            global%logfile = ""
        end if
        allocate (global%out_files)
        call system_clock (seed)
        call var_list_append_log_ptr &
            (global%var_list, var_str ("?logging"), logging, known, &
            intrinsic=.true.)
        call var_list_append_int &
            (global%var_list, var_str ("seed"), seed, &
            intrinsic=.true.)
        call var_list_append_string &
            (global%var_list, var_str ("$model_name"), &
            intrinsic=.true.)
        call var_list_append_int &
            (global%var_list, var_str ("process_num_id"), &
            intrinsic=.true.)
        call var_list_append_string &
            (global%var_list, var_str ("$method"), var_str ("omega"), &
            intrinsic=.true.)
        call var_list_append_log &
            (global%var_list, var_str ("?report_progress"), .true., &
            intrinsic=.true.)
        call var_list_append_string &
            (global%var_list, var_str ("$restrictions"), var_str (""), &
            intrinsic=.true.)
        call var_list_append_string &
            (global%var_list, var_str ("$omega_flags"), var_str (""), &

```

```

        intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?read_color_factors"), .true., &
    intrinsic=.true.)
!!! JRR: WK please check (#529)
!   call var_list_append_string &
!       (global%var_list, var_str ("$_user_procs_cut"), var_str (""), &
!       intrinsic=.true.)
!   call var_list_append_string &
!       (global%var_list, var_str ("$_user_procs_event_shape"), var_str (""), &
!       intrinsic=.true.)
!   call var_list_append_string &
!       (global%var_list, var_str ("$_user_procs_obs1"), var_str (""), &
!       intrinsic=.true.)
!   call var_list_append_string &
!       (global%var_list, var_str ("$_user_procs_obs2"), var_str (""), &
!       intrinsic=.true.)
!   call var_list_append_string &
!       (global%var_list, var_str ("$_user_procs_sf"), var_str (""), &
!       intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?slha_read_input"), .true., &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?slha_read_spectrum"), .true., &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?slha_read_decays"), .false., &
    intrinsic=.true.)
call var_list_append_string &
    (global%var_list, var_str ("$_library_name"), &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("sqrts"), &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("luminosity"), 0._default, &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?sf_trace"), .false., &
    intrinsic=.true.)
call var_list_append_string &
    (global%var_list, var_str ("$_sf_trace_file"), var_str (""), &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?sf_allow_s_mapping"), .true., &
    intrinsic=.true.)
if (present (paths)) then
    call var_list_append_string &
        (global%var_list, var_str ("$_lhpdf_dir"), paths%lhpdf_dir, &
        intrinsic=.true.)
else
    call var_list_append_string &
        (global%var_list, var_str ("$_lhpdf_dir"), var_str(""), &

```

```

        intrinsic=.true.)
end if
call var_list_append_string &
    (global%var_list, var_str ("lhpdf_file"), var_str (""), &
    intrinsic=.true.)
call var_list_append_string &
    (global%var_list, var_str ("lhpdf_photon_file"), var_str (""), &
    intrinsic=.true.)
call var_list_append_int &
    (global%var_list, var_str ("lhpdf_member"), 0, &
    intrinsic=.true.)
call var_list_append_int &
    (global%var_list, var_str ("lhpdf_photon_scheme"), 0, &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?hoppet_b_matching"), .false., &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("isr_alpha"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("isr_q_max"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("isr_mass"), 0._default, &
    intrinsic=.true.)
call var_list_append_int &
    (global%var_list, var_str ("isr_order"), 3, &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?isr_recoil"), .false., &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("epa_alpha"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("epa_x_min"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("epa_q_min"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("epa_e_max"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("epa_mass"), 0._default, &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?epa_recoil"), .false., &
    intrinsic=.true.)
call var_list_append_real &
    (global%var_list, var_str ("ewa_x_min"), 0._default, &
    intrinsic=.true.)
call var_list_append_real &

```

```

(global%var_list, var_str ("ewa_pt_max"), 0._default, &
 intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("ewa_mass"), 0._default, &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?ewa_keep_momentum"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?ewa_keep_energy"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?circe1_photon1"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?circe1_photon2"), .false., &
 intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("circe1_sqrts"), &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?circe1_generate"), .true., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?circe1_map"), .true., &
 intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("circe1_mapping_slope"), 2._default, &
 intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("circe1_eps"), 1e-5_default, &
 intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("circe1_ver"), 0, intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("circe1_rev"), 0, intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$circe1_acc"), var_str ("SBAND"), &
 intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("circe1_chat"), 0, intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?circe1_with_radiation"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?circe2_polarized"), .true., &
 intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$circe2_file"), &
 intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$circe2_design"), var_str ("*"), &
 intrinsic=.true.)
call var_list_append_string &

```



```

(global%var_list, var_str ("beam_events_file"), &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?beam_events_warn_eof"), .true., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?energy_scan_normalize"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_is_fixed"), .true., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_lhapdf"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_pdf_builtin"), .false., &
 intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("alpha_s_order"), 0, &
 intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("alpha_s_nf"), 5, &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_mz"), .false., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_lambda_qcd"), .false., &
 intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("lambda_qcd"), 200.e-3_default, &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?fatal_beam_decay"), .true., &
 intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?helicity_selection_active"), .true., &
 intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("helicity_selection_threshold"), &
 1E10_default, &
 intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("helicity_selection_cutoff"), 1000, &
 intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("rng_method"), var_str ("tao"), &
 intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("integration_method"), var_str ("vamp"), &
 intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("threshold_calls"), 10, &
 intrinsic=.true.)

```

```

call var_list_append_int &
  (global%var_list, var_str ("min_calls_per_channel"), 10, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("min_calls_per_bin"), 10, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("min_bins"), 3, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("max_bins"), 20, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?stratified"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?use_vamp_equivalences"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vamp_verbose"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vamp_history_global"), &
   .true., intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vamp_history_global_verbose"), &
   .false., intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vamp_history_channels"), &
   .false., intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vamp_history_channels_verbose"), &
   .false., intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("channel_weights_power"), 0.25_default, &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("phs_method"), var_str ("default"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vis_channels"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?check_phs_file"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("phs_file"), var_str (""), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_only"), .false., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_threshold_s"), 50._default, &
   intrinsic=.true.)

```

```

call var_list_append_real &
  (global%var_list, var_str ("phs_threshold_t"), 100._default, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("phs_off_shell"), 2, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("phs_t_channel"), 6, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_e_scale"), 10._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_m_scale"), 10._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_q_scale"), 10._default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_keep_nonresonant"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_step_mapping"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_step_mapping_exp"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_s_mapping"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$_run_id"), var_str (""), &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("n_calls_test"), 0, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?integration_timer"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?check_grid_file"), .true., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("accuracy_goal"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("error_goal"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("relative_error_goal"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("error_threshold"), &
   0._default, intrinsic=.true.)

```

```

call var_list_append_log &
  (global%var_list, var_str ("?vis_history"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?diags"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?diags_color"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?check_event_file"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$event_file_version"), var_str (""), &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("n_events"), 0, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?unweighted"), .true., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("safety_factor"), 1._default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?negative_weights"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?keep_beams"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?keep_remnants"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?recover_beams"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?update_event"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?update_sqme"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?update_weight"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?use_alpha_s_from_file"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?use_scale_from_file"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?allow_decays"), .true., &
   intrinsic=.true.)

```

```

call var_list_append_log &
  (global%var_list, var_str ("?auto_decays"), .false., &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("auto_decays_multiplicity"), 2, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?auto_decays_radiative"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?decay_rest_frame"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?isotropic_decay"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?diagonal_decay"), .false., &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("decay_helicity"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("sample"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("sample_normalization"), var_str ("auto"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?sample_pacify"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?sample_select"), .true., &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("sample_max_tries"), 10000, &
   intrinsic = .true.)
call var_list_append_int &
  (global%var_list, var_str ("sample_split_n_evt"), 0, &
   intrinsic = .true.)
call var_list_append_int &
  (global%var_list, var_str ("sample_split_n_kbytes"), 0, &
   intrinsic = .true.)
call var_list_append_int &
  (global%var_list, var_str ("sample_split_index"), 0, &
   intrinsic = .true.)
call var_list_append_string &
  (global%var_list, var_str ("rescan_input_format"), var_str ("raw"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?read_raw"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?write_raw"), .true., &
   intrinsic=.true.)

```

```

call var_list_append_string &
  (global%var_list, var_str ("$extension_raw"), var_str ("evx"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_default"), var_str ("evt"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$debug_extension"), var_str ("debug"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?debug_process"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?debug_transforms"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?debug_decay"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?debug_verbose"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_hepevt"), var_str ("hepevt"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_ascii_short"), &
   var_str ("short.evt"), intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_ascii_long"), &
   var_str ("long.evt"), intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_athena"), &
   var_str ("athena.evt"), intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_mokka"), &
   var_str ("mokka.evt"), intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$lhef_version"), var_str ("2.0"), &
   intrinsic = .true.)
call var_list_append_string &
  (global%var_list, var_str ("$lhef_extension"), var_str ("lhe"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?lhef_write_sqme_prc"), .true., &
   intrinsic = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?lhef_write_sqme_ref"), .false., &
   intrinsic = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?lhef_write_sqme_alt"), .true., &
   intrinsic = .true.)
call var_list_append_string &
  (global%var_list, var_str ("$extension_lha"), var_str ("lha"), &
   intrinsic=.true.)

```

```

call var_list_append_string &
(global%var_list, var_str ("$extension_hepmc"), var_str ("hepmc"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_lcio"), var_str ("slcio"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_stdhep"), var_str ("hep"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_stdhep_up"), &
var_str ("up.hep"), intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_hepevt_verb"), &
var_str ("hepevt.verb"), intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_lha_verb"), &
var_str ("lha.verb"), intrinsic=.true.)
call var_list_append_int (global%var_list, &
var_str ("n_bins"), 20, &
intrinsic=.true.)
call var_list_append_log (global%var_list, &
var_str ("?normalize_bins"), .false., &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$obs_label"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$obs_unit"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$title"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$description"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$x_label"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$y_label"), var_str (""), &
intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("graph_width_mm"), 130, &
intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("graph_height_mm"), 90, &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?y_log"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?x_log"), .false., &
intrinsic=.true.)

```

```

call var_list_append_real &
  (global%var_list, var_str ("x_min"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("x_max"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("y_min"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("y_max"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("gmlcode_bg"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("gmlcode_fg"), var_str (""), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_histogram"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_base"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_piecewise"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?fill_curve"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_curve"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_errors"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_symbols"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$fill_options"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$draw_options"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$err_options"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$symbol"), &
   intrinsic=.true.)
call var_list_append_log (global%var_list, &
  var_str ("?analysis_file_only"), .false., &
  intrinsic=.true.)

```



```

call var_list_append_real (global%var_list, &
    var_str ("tolerance"), 0._default, &
    intrinsic=.true.)
call var_list_append_int (global%var_list, &
    var_str ("checkpoint"), 0, &
    intrinsic = .true.)
call var_list_append_log &
    (global%var_list, var_str ("?pacify"), .false., &
    intrinsic=.true.)
call var_list_append_string &
    (global%var_list, var_str ("out_file"), var_str (""), &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?out_advance"), .true., &
    intrinsic=.true.)
!!! JRR: WK please check (#542)
!   call var_list_append_log &
!       (global%var_list, var_str ("?out_custom"), .false., &
!       intrinsic=.true.)
!   call var_list_append_string &
!       (global%var_list, var_str ("out_comment"), var_str ("# "), &
!       intrinsic=.true.)
!   call var_list_append_log &
!       (global%var_list, var_str ("?out_header"), .true., &
!       intrinsic=.true.)
!   call var_list_append_log &
!       (global%var_list, var_str ("?out_yerr"), .true., &
!       intrinsic=.true.)
!   call var_list_append_log &
!       (global%var_list, var_str ("?out_xerr"), .true., &
!       intrinsic=.true.)
call var_list_append_int (global%var_list, var_str ("real_range"), &
    range (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, var_str ("real_precision"), &
    precision (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_real (global%var_list, var_str ("real_epsilon"), &
    epsilon (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_real (global%var_list, var_str ("real_tiny"), &
    tiny (real_specimen), intrinsic = .true., locked = .true.)
!!! FastJet parameters
call var_list_append_int (global%var_list, &
    var_str ("kt_algorithm"), &
    kt_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("cambridge_algorithm"), &
    cambridge_algorithm, intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("antikt_algorithm"), &
    antikt_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("genkt_algorithm"), &
    genkt_algorithm, &
    genkt_algorithm, &

```

```

        intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("cambridge_for_passive_algorithm"), &
    cambridge_for_passive_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("genkt_for_passive_algorithm"), &
    genkt_for_passive_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("ee_kt_algorithm"), &
    ee_kt_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("ee_genkt_algorithm"), &
    ee_genkt_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("plugin_algorithm"), &
    plugin_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("undefined_jet_algorithm"), &
    undefined_jet_algorithm, &
    intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, &
    var_str ("jet_algorithm"), undefined_jet_algorithm, &
    intrinsic = .true.)
call var_list_append_real (global%var_list, &
    var_str ("jet_r"), 0._default, &
    intrinsic = .true.)
call var_list_append_log &
    (global%var_list, var_str ("?polarized_events"), .false., &
    intrinsic=.true.)
call set_shower_defaults ()
call set_hadronization_defaults ()
call set_mlm_matching_defaults ()
call set_powheg_matching_defaults ()
call var_list_append_log &
    (global%var_list, var_str ("?ckkw_matching"), .false., &
    intrinsic=.true.)
call var_list_append_string &
    (global%var_list, var_str ("$_pdf_builtin_set"), var_str ("CTEQ6L"), &
    intrinsic=.true.)
call set_openmp_defaults ()
call var_list_append_string &
    (global%var_list, var_str ("$_loop_me_method"), &
    var_str ("gosam"), intrinsic = .true.)
call var_list_append_string &
    (global%var_list, var_str ("$_correlation_me_method"), &
    var_str ("omega"), intrinsic = .true.)
call var_list_append_string &
    (global%var_list, var_str ("$_real_tree_me_method"), &
    var_str ("omega"), intrinsic = .true.)

```

```

call var_list_append_real &
  (global%var_list, var_str ("fks_dij_exp1"), &
    1._default, intrinsic = .true.)
call var_list_append_real &
  (global%var_list, var_str ("fks_dij_exp2"), &
    1._default, intrinsic = .true.)
call var_list_append_int &
  (global%var_list, var_str ("fks_mapping_type"), &
    1, intrinsic = .true.)
call var_list_append_int &
  (global%var_list, var_str ("alpha_power"), &
    2, intrinsic = .true.)
call var_list_append_int &
  (global%var_list, var_str ("alphas_power"), &
    0, intrinsic = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?combined_nlo_integration"), &
    .false., intrinsic = .true.)
call global%init_pointer_variables ()
call global%process_stack%init_var_list (global%var_list)

```

contains

<RT data: global init: procedures>

end subroutine rt_data_global_init

<RT data: global init: procedures>≡

```

subroutine set_shower_defaults ()
  call var_list_append_log &
    (global%var_list, var_str ("?allow_shower"), .true., &
      intrinsic=.true.)
  call var_list_append_log &
    (global%var_list, var_str ("?ps_fsr_active"), .false., &
      intrinsic=.true.)
  call var_list_append_log &
    (global%var_list, var_str ("?ps_isr_active"), .false., &
      intrinsic=.true.)
  call var_list_append_log &
    (global%var_list, var_str ("?muli_active"), .false., &
      intrinsic=.true.)
  call var_list_append_string &
    (global%var_list, var_str ("$shower_method"), var_str ("WHIZARD"), &
      intrinsic=.true.)
  call var_list_append_log &
    (global%var_list, var_str ("?shower_verbose"), .false., &
      intrinsic=.true.)
  call var_list_append_string &
    (global%var_list, var_str (" $ps_PYTHIA_PYGIVE"), var_str (""), &
      intrinsic=.true.)
  call var_list_append_real (global%var_list, &
    var_str ("ps_mass_cutoff"), 1._default, intrinsic = .true.)
  call var_list_append_real (global%var_list, &
    var_str ("ps_fsr_lambda"), 0.29_default, intrinsic = .true.)

```

```

call var_list_append_real (global%var_list, &
var_str ("ps_isr_lambda"), 0.29_default, intrinsic = .true.)
call var_list_append_int (global%var_list, &
var_str ("ps_max_n_flavors"), 5, intrinsic = .true.)
call var_list_append_log &
(global%var_list, var_str ("?ps_isr_alpha_s_running"), .true., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?ps_fsr_alpha_s_running"), .true., &
intrinsic=.true.)
call var_list_append_real (global%var_list, var_str ("ps_fixed_alpha_s"), &
0._default, intrinsic = .true.)
call var_list_append_log &
(global%var_list, var_str ("?ps_isr_pt_ordered"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?ps_isr_angular_ordered"), .true., &
intrinsic=.true.)
call var_list_append_real (global%var_list, var_str &
("ps_isr_primordial_kt_width"), 0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("ps_isr_primordial_kt_cutoff"), 5._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("ps_isr_z_cutoff"), 0.999_default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("ps_isr_minenergy"), 1._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("ps_isr_tscalefactor"), 1._default, intrinsic = .true.)
call var_list_append_log (global%var_list, var_str &
("?ps_isr_only_onshell_emitted_partons"), .false., intrinsic=.true.)
end subroutine set_shower_defaults

```

(RT data: global init: procedures)+≡

```

subroutine set_mlm_matching_defaults ()
call var_list_append_log &
(global%var_list, var_str ("?mlm_matching"), .false., &
intrinsic=.true.)
call var_list_append_real (global%var_list, var_str &
("mlm_Qcut_ME"), 0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("mlm_Qcut_PS"), 0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("mlm_ptmin"), 0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("mlm_etamax"), 0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("mlm_Rmin"), 0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("mlm_Emin"), 0._default, intrinsic = .true.)
call var_list_append_int (global%var_list, var_str &
("mlm_nmaxMEjets"), 0, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &
("mlm_ETclusfactor"), 0.2_default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str &

```

```

        ("mlm_ETclusminE"), 5._default, intrinsic = .true.)
    call var_list_append_real (global%var_list, var_str &
        ("mlm_etaclusfactor"), 1._default, intrinsic = .true.)
    call var_list_append_real (global%var_list, var_str &
        ("mlm_Rclusfactor"), 1._default, intrinsic = .true.)
    call var_list_append_real (global%var_list, var_str &
        ("mlm_Eclusfactor"), 1._default, intrinsic = .true.)

end subroutine set_mlm_matching_defaults

<RT data: global init: procedures>+≡
subroutine set_powheg_matching_defaults ()
    call var_list_append_log &
        (global%var_list, var_str ("?powheg_matching"), &
            .false., intrinsic = .true.)
    call var_list_append_log &
        (global%var_list, var_str ("?powheg_use_singular_jacobian"), &
            .false., intrinsic = .true.)
    call var_list_append_int &
        (global%var_list, var_str ("powheg_grid_size_xi"), &
            5, intrinsic = .true.)
    call var_list_append_int &
        (global%var_list, var_str ("powheg_grid_size_y"), &
            5, intrinsic = .true.)
    call var_list_append_int &
        (global%var_list, var_str ("powheg_grid_sampling_points"), &
            500000, intrinsic = .true.)
    call var_list_append_real &
        (global%var_list, var_str ("powheg_pt_min"), &
            1._default, intrinsic = .true.)
    call var_list_append_real &
        (global%var_list, var_str ("powheg_lambda"), &
            LAMBDA_QCD_REF, intrinsic = .true.)
    call var_list_append_log &
        (global%var_list, var_str ("?powheg_rebuild_grids"), &
            .false., intrinsic = .true.)
end subroutine set_powheg_matching_defaults

<RT data: global init: procedures>+≡
subroutine set_hadronization_defaults ()
    call var_list_append_log &
        (global%var_list, var_str ("?allow_hadronization"), .true., &
            intrinsic=.true.)
    call var_list_append_log &
        (global%var_list, var_str ("?hadronization_active"), .false., &
            intrinsic=.true.)
    call var_list_append_string &
        (global%var_list, var_str ("$hadronization_method"), &
            var_str ("PYTHIA6"), intrinsic = .true.)
end subroutine set_hadronization_defaults

<RT data: global init: procedures>+≡
subroutine set_openmp_defaults ()
    call var_list_append_log &

```

```

(global%var_list, var_str ("?omega_openmp"), &
openmp_is_active (), &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?openmp_is_active"), &
openmp_is_active (), &
locked=.true., intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("openmp_num_threads_default"), &
openmp_get_default_max_threads (), &
locked=.true., intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("openmp_num_threads"), &
openmp_get_max_threads (), &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?openmp_logging"), &
.true., intrinsic=.true.)
end subroutine set_openmp_defaults

```

28.8.7 Local copies

This is done at compile time when a local copy of runtime data is needed: Link the variable list and initialize all derived parameters. This allows for synchronizing them with local variable changes without affecting global data.

Also re-initialize pointer variables, so they point to local copies of their targets.

```

<RT data: rt data: TBP>+≡
  procedure :: local_init => rt_data_local_init

<RT data: procedures>+≡
  subroutine rt_data_local_init (local, global, env)
    class(rt_data_t), intent(inout), target :: local
    type(rt_data_t), intent(in), target :: global
    integer, intent(in), optional :: env
    local%context => global
    call local%process_stack%link (global%process_stack)
    call local%process_stack%init_var_list (local%var_list)
    call local%process_stack%link_var_list (global%var_list)
    call var_list_append_string &
      (local%var_list, var_str ("$model_name"), var_str (""), &
      intrinsic=.true.)
    call local%init_pointer_variables ()
    local%fallback_model => global%fallback_model
    local%radiation_model => global%radiation_model
    local%os_data = global%os_data
    local%logfile = global%logfile
    call local%model_list%link (global%model_list)
    local%model => global%model
    if (associated (local%model)) then
      call local%model%link_var_list (local%var_list)
    end if
  end subroutine rt_data_local_init

```

These variables point to objects which get local copies:

```

<RT data: rt data: TBP>+≡
  procedure :: init_pointer_variables => rt_data_init_pointer_variables

<RT data: procedures>+≡
  subroutine rt_data_init_pointer_variables (local)
    class(rt_data_t), intent(inout), target :: local
    logical, target, save :: known = .true.
    call var_list_append_string_ptr &
      (local%var_list, var_str ("fc"), local%os_data%fc, known, &
        intrinsic=.true.)
    call var_list_append_string_ptr &
      (local%var_list, var_str ("fcflags"), local%os_data%fcflags, known, &
        intrinsic=.true.)
  end subroutine rt_data_init_pointer_variables

```

This is done at execution time: Copy data, transfer pointers. `local` has `intent(inout)` because its local variable list has already been prepared by the previous routine.

To be pedantic, the local pointers to model and library should point to the entries in the local copies. (However, as long as these are just shallow copies with identical content, this is actually irrelevant.)

The process library and process stacks behave as global objects. The copies of the process library and process stacks should be shallow copies, so the contents stay identical. Since objects may be pushed on the stack in the local environment, upon restoring the global environment, we should reverse the assignment. Then the added stack elements will end up on the global stack. (This should be reconsidered in a parallel environment.)

```

<RT data: rt data: TBP>+≡
  procedure :: activate => rt_data_activate

<RT data: procedures>+≡
  subroutine rt_data_activate (local)
    class(rt_data_t), intent(inout), target :: local
    class(rt_data_t), pointer :: global
    global => local%context
    if (associated (global)) then
      local%lexer => global%lexer
      call global%copy_globals (local)
      local%os_data = global%os_data
      local%logfile = global%logfile
      if (associated (global%prclib)) then
        local%prclib => &
          local%prclib_stack%get_library_ptr (global%prclib%get_name ())
      end if
      call local%import_values ()
      call local%process_stack%link (global%process_stack)
      local%it_list = global%it_list
      local%beam_structure = global%beam_structure
      local%pn = global%pn
      if (allocated (local%sample_fmt)) deallocate (local%sample_fmt)
      if (allocated (global%sample_fmt)) then

```

```

        allocate (local%sample_fmt (size (global%sample_fmt)), &
                source = global%sample_fmt)
    end if
    local%out_files => global%out_files
    local%model => global%model
    local%model_is_copy = .false.
else if (.not. associated (local%model)) then
    local%model => local%preload_model
    local%model_is_copy = .false.
end if
if (associated (local%model)) then
    call local%model%link_var_list (local%var_list)
    call var_list_set_string (local%var_list, var_str ("$model_name"), &
        local%model%get_name (), is_known = .true.)
else
    call var_list_set_string (local%var_list, var_str ("model_name"), &
        var_str (""), is_known = .false.)
end if
end subroutine rt_data_activate

```

Restore the previous state of data, without actually finalizing the local environment. We also clear the local process stack. Some local modifications (model list and process library stack) are communicated to the global context, if there is any.

If the `keep_local` flag is set, we want to retain current settings in the local environment. In particular, we create an instance of the currently selected model (which thus becomes separated from the model library!). The local variables are also kept.

```

<RT data: rt data: TBP>+≡
    procedure :: deactivate => rt_data_deactivate

<RT data: procedures>+≡
    subroutine rt_data_deactivate (local, global, keep_local)
        class(rt_data_t), intent(inout), target :: local
        class(rt_data_t), intent(inout), optional, target :: global
        logical, intent(in), optional :: keep_local
        type(string_t) :: global_model, local_model
        logical :: same_model, delete
        delete = .true.; if (present (keep_local)) delete = .not. keep_local
        if (present (global)) then
            if (associated (global%model) .and. associated (local%model)) then
                global_model = global%model%get_name ()
                local_model = local%model%get_name ()
                same_model = global_model == local_model
            else
                same_model = .false.
            end if
            if (delete) then
                call local%process_stack%clear ()
                call local%unselect_model ()
                call local%unset_values ()
            else if (associated (local%model)) then
                call local%ensure_model_copy ()
            end if
        end if
    end subroutine

```



```

        end if
        if (.not. same_model .and. global_model /= "") then
            call msg_message ("Restoring model '" // char (global_model) // "'")
        end if
        if (associated (global%model)) then
            call global%model%link_var_list (global%var_list)
        end if
        call global%restore_globals (local)
    else
        call local%unselect_model ()
    end if
end subroutine rt_data_deactivate

```

This imports the global objects for which local modifications should be kept. Currently, this is only the process library stack.

```

<RT data: rt data: TBP>+≡
    procedure :: copy_globals => rt_data_copy_globals

<RT data: procedures>+≡
    subroutine rt_data_copy_globals (global, local)
        class(rt_data_t), intent(in) :: global
        class(rt_data_t), intent(inout) :: local
        local%prclib_stack = global%prclib_stack
    end subroutine rt_data_copy_globals

```

This restores global objects, for which local modifications should be kept.

```

<RT data: rt data: TBP>+≡
    procedure :: restore_globals => rt_data_restore_globals

<RT data: procedures>+≡
    subroutine rt_data_restore_globals (global, local)
        class(rt_data_t), intent(inout) :: global
        class(rt_data_t), intent(in) :: local
        global%prclib_stack = local%prclib_stack
    end subroutine rt_data_restore_globals

```

28.8.8 Finalization

Finalizer for the variable list and the structure-function list. This is done only for the global RT dataset; local copies contain pointers to this and do not need a finalizer.

```

<RT data: rt data: TBP>+≡
    procedure :: final => rt_data_global_final

<RT data: procedures>+≡
    subroutine rt_data_global_final (global)
        class(rt_data_t), intent(inout) :: global
        call global%process_stack%final ()
        call global%prclib_stack%final ()
    !    call global%delete_model_copy ()
        call global%model_list%final ()
        call global%var_list%final (follow_link=.false.)
    end subroutine rt_data_global_final

```

```

    if (associated (global%out_files)) then
        call file_list_final (global%out_files)
        deallocate (global%out_files)
    end if
end subroutine rt_data_global_final

```

The local copy needs a finalizer for the variable list, which consists of local copies. This finalizer is called only when the local environment is finally discarded. (Note that the process stack should already have been cleared after execution, which can occur many times for the same local environment.)

```

<RT data: rt data: TBP>+≡
    procedure :: local_final => rt_data_local_final

<RT data: procedures>+≡
    subroutine rt_data_local_final (local)
        class(rt_data_t), intent(inout) :: local
        call local%process_stack%clear ()
    !    call local%delete_model_copy ()
        call local%model_list%final ()
        call local%var_list%final (follow_link=.false.)
    end subroutine rt_data_local_final

```

28.8.9 Model Management

Read a model, so it becomes available for activation. No variables or model copies, this is just initialization.

If this is a local environment, the model will be automatically read into the global context.

```

<RT data: rt data: TBP>+≡
    procedure :: read_model => rt_data_read_model

<RT data: procedures>+≡
    subroutine rt_data_read_model (global, name, model)
        class(rt_data_t), intent(inout) :: global
        type(string_t), intent(in) :: name
        type(model_t), pointer, intent(out) :: model
        type(string_t) :: filename
        filename = name // ".mdl"
        call global%model_list%read_model &
            (name, filename, global%os_data, model)
    end subroutine rt_data_read_model

```

Initialize the fallback model. This model is used whenever the current model does not describe all physical particles (hadrons, mainly). It is not supposed to be modified, and the pointer should remain linked to this model.

```

<RT data: rt data: TBP>+≡
    procedure :: init_fallback_model => rt_data_init_fallback_model

<RT data: procedures>+≡
    subroutine rt_data_init_fallback_model (global, name, filename)
        class(rt_data_t), intent(inout) :: global
        type(string_t), intent(in) :: name, filename

```

```

        call global%model_list%read_model &
            (name, filename, global%os_data, global%fallback_model)
    end subroutine rt_data_init_fallback_model

```

Initialize the radiation model. This model is used by a radiation-generator algorithm which is part of the NLO machinery. It is not supposed to be modified, and the pointer should remain linked to this model.

```

<RT data: rt data: TBP>+≡
    procedure :: init_radiation_model => rt_data_init_radiation_model

<RT data: procedures>+≡
    subroutine rt_data_init_radiation_model (global, name, filename)
        class(rt_data_t), intent(inout) :: global
        type(string_t), intent(in) :: name, filename
        call global%model_list%read_model &
            (name, filename, global%os_data, global%radiation_model)
    end subroutine rt_data_init_radiation_model

```

Activate a model: assign the current-model pointer and set the model name in the variable list. If necessary, read the model from file. Link the global variable list to the model variable list.

```

<RT data: rt data: TBP>+≡
    procedure :: select_model => rt_data_select_model

<RT data: procedures>+≡
    subroutine rt_data_select_model (global, name)
        class(rt_data_t), intent(inout), target :: global
        type(string_t), intent(in) :: name
        logical :: same_model
        if (associated (global%model)) then
            same_model = global%model%get_name () == name
        else
            same_model = .false.
        end if
        if (.not. same_model) then
            ! call global%delete_model_copy ()
            global%model => global%model_list%get_model_ptr (name)
            if (.not. associated (global%model)) then
                call global%read_model (name, global%model)
                global%model_is_copy = .false.
            else if (associated (global%context)) then
                global%model_is_copy = &
                    global%model_list%model_exists (name, follow_link=.false.)
            else
                global%model_is_copy = .false.
            end if
        end if
        if (associated (global%model)) then
            call global%model%link_var_list (global%var_list)
            call var_list_set_string (global%var_list, var_str ("model_name"), &
                name, is_known = .true.)
            call msg_message ("Switching to model '" // char (name) // "'")
        else

```

```

        call var_list_set_string (global%var_list, var_str ("$model_name"), &
            var_str (""), is_known = .false.)
    end if
end subroutine rt_data_select_model

```

Remove the model link and unset the model name variable.

```

<RT data: rt data: TBP>+≡
    procedure :: unselect_model => rt_data_unselect_model

<RT data: procedures>+≡
    subroutine rt_data_unselect_model (global)
        class(rt_data_t), intent(inout), target :: global
        if (associated (global%model)) then
!            call global%delete_model_copy ()
            global%model => null ()
            global%model_is_copy = .false.
            call var_list_set_string (global%var_list, var_str ("model_name"), &
                var_str (""), is_known = .false.)
        end if
    end subroutine rt_data_unselect_model

```

Create a copy of the currently selected model and append it to the local model list. The model pointer is redirected to the copy. (Not applicable for the global model list, those models will be modified in-place.)

```

<RT data: rt data: TBP>+≡
    procedure :: ensure_model_copy => rt_data_ensure_model_copy
!    procedure :: delete_model_copy => rt_data_delete_model_copy

<RT data: procedures>+≡
    subroutine rt_data_ensure_model_copy (global)
        class(rt_data_t), intent(inout), target :: global
        if (associated (global%context)) then
            if (.not. global%model_is_copy) then
                call global%model_list%append_copy (global%model, global%model)
                global%model_is_copy = .true.
                call global%model%link_var_list (global%var_list)
            end if
        end if
    end subroutine rt_data_ensure_model_copy

!    subroutine rt_data_delete_model_copy (global)
!        class(rt_data_t), intent(inout), target :: global
!        if (global%model_is_copy) then
!            call model_pointer_delete_instance (global%model)
!            global%model_is_copy = .false.
!        else
!            global%model => null ()
!        end if
!    end subroutine rt_data_delete_model_copy

```

Modify a model variable. The update mechanism will ensure that the model parameter set remains consistent. This has to take place in a local copy of the

current model. If there is none yet, create one.

```

<RT data: rt data: TBP>+≡
  procedure :: model_set_real => rt_data_model_set_real

<RT data: procedures>+≡
  subroutine rt_data_model_set_real (global, name, rval, verbose, pacified)
    class(rt_data_t), intent(inout), target :: global
    type(string_t), intent(in) :: name
    real(default), intent(in) :: rval
    logical, intent(in), optional :: verbose, pacified
    call global%ensure_model_copy ()
    call global%model%set_real (name, rval, verbose, pacified)
  end subroutine rt_data_model_set_real

```

Modify particle properties. This has to take place in a local copy of the current model. If there is none yet, create one.

```

<RT data: rt data: TBP>+≡
  procedure :: modify_particle => rt_data_modify_particle

<RT data: procedures>+≡
  subroutine rt_data_modify_particle &
    (global, pdg, polarized, stable, decay, &
     isotropic_decay, diagonal_decay, decay_helicity)
    class(rt_data_t), intent(inout), target :: global
    integer, intent(in) :: pdg
    logical, intent(in), optional :: polarized, stable
    logical, intent(in), optional :: isotropic_decay, diagonal_decay
    integer, intent(in), optional :: decay_helicity
    type(string_t), dimension(:), intent(in), optional :: decay
    call global%ensure_model_copy ()
    if (present (polarized)) then
      if (polarized) then
        call global%model%set_polarized (pdg)
      else
        call global%model%set_unpolarized (pdg)
      end if
    end if
    if (present (stable)) then
      if (stable) then
        call global%model%set_stable (pdg)
      else if (present (decay)) then
        call global%model%set_unstable &
          (pdg, decay, isotropic_decay, diagonal_decay, decay_helicity)
      else
        call msg_bug ("Setting particle unstable: missing decay processes")
      end if
    end if
  end subroutine rt_data_modify_particle

```

28.8.10 Managing Variables

Return a pointer to the currently active variable list. If there is no model, this is the global variable list. If there is one, it is the model variable list, which

should be linked to the former.

```

<RT data: rt data: TBP>+≡
    procedure :: get_var_list_ptr => rt_data_get_var_list_ptr

<RT data: procedures>+≡
    function rt_data_get_var_list_ptr (global) result (var_list)
        class(rt_data_t), intent(in), target :: global
        type(var_list_t), pointer :: var_list
        if (associated (global%model)) then
            var_list => global%model%get_var_list_ptr ()
        else
            var_list => global%var_list
        end if
    end function rt_data_get_var_list_ptr

```

Initialize a local variable: append it to the current variable list. No initial value, yet.

```

<RT data: rt data: TBP>+≡
    procedure :: append_log => rt_data_append_log
    procedure :: append_int => rt_data_append_int
    procedure :: append_real => rt_data_append_real
    procedure :: append_cmplx => rt_data_append_cmplx
    procedure :: append_subevt => rt_data_append_subevt
    procedure :: append_pdg_array => rt_data_append_pdg_array
    procedure :: append_string => rt_data_append_string

<RT data: procedures>+≡
    subroutine rt_data_append_log (local, name, lval, intrinsic, user)
        class(rt_data_t), intent(inout) :: local
        type(string_t), intent(in) :: name
        logical, intent(in), optional :: lval
        logical, intent(in), optional :: intrinsic, user
        call var_list_append_log (local%var_list, name, lval, &
            intrinsic = intrinsic, user = user)
    end subroutine rt_data_append_log

    subroutine rt_data_append_int (local, name, ival, intrinsic, user)
        class(rt_data_t), intent(inout) :: local
        type(string_t), intent(in) :: name
        integer, intent(in), optional :: ival
        logical, intent(in), optional :: intrinsic, user
        call var_list_append_int (local%var_list, name, ival, &
            intrinsic = intrinsic, user = user)
    end subroutine rt_data_append_int

    subroutine rt_data_append_real (local, name, rval, intrinsic, user)
        class(rt_data_t), intent(inout) :: local
        type(string_t), intent(in) :: name
        real(default), intent(in), optional :: rval
        logical, intent(in), optional :: intrinsic, user
        call var_list_append_real (local%var_list, name, rval, &
            intrinsic = intrinsic, user = user)
    end subroutine rt_data_append_real

```

```

subroutine rt_data_append_cmplx (local, name, cval, intrinsic, user)
  class(rt_data_t), intent(inout) :: local
  type(string_t), intent(in) :: name
  complex(default), intent(in), optional :: cval
  logical, intent(in), optional :: intrinsic, user
  call var_list_append_cmplx (local%var_list, name, cval, &
    intrinsic = intrinsic, user = user)
end subroutine rt_data_append_cmplx

subroutine rt_data_append_subevt (local, name, pval, intrinsic, user)
  class(rt_data_t), intent(inout) :: local
  type(string_t), intent(in) :: name
  type(subevt_t), intent(in), optional :: pval
  logical, intent(in) :: intrinsic, user
  call var_list_append_subevt (local%var_list, name, &
    intrinsic = intrinsic, user = user)
end subroutine rt_data_append_subevt

subroutine rt_data_append_pdg_array (local, name, aval, intrinsic, user)
  class(rt_data_t), intent(inout) :: local
  type(string_t), intent(in) :: name
  type(pdg_array_t), intent(in), optional :: aval
  logical, intent(in), optional :: intrinsic, user
  call var_list_append_pdg_array (local%var_list, name, aval, &
    intrinsic = intrinsic, user = user)
end subroutine rt_data_append_pdg_array

subroutine rt_data_append_string (local, name, sval, intrinsic, user)
  class(rt_data_t), intent(inout) :: local
  type(string_t), intent(in) :: name
  type(string_t), intent(in), optional :: sval
  logical, intent(in), optional :: intrinsic, user
  call var_list_append_string (local%var_list, name, sval, &
    intrinsic = intrinsic, user = user)
end subroutine rt_data_append_string

```

Import values for all local variables, given a global context environment where these variables are defined.

```

<RT data: rt data: TBP>+≡
  procedure :: import_values => rt_data_import_values

<RT data: procedures>+≡
  subroutine rt_data_import_values (local)
    class(rt_data_t), intent(inout) :: local
    type(rt_data_t), pointer :: global
    global => local%context
    if (associated (global)) then
      call var_list_import (local%var_list, global%var_list)
    end if
  end subroutine rt_data_import_values

```

Unset all variable values.

```

<RT data: rt data: TBP>+≡
  procedure :: unset_values => rt_data_unset_values

```

```

<RT data: procedures>+≡
  subroutine rt_data_unset_values (global)
    class(rt_data_t), intent(inout) :: global
    call var_list_undefine (global%var_list, follow_link=.false.)
  end subroutine rt_data_unset_values

```

Set a variable. (Not a model variable, these are handled separately.) We can assume that the variable has been initialized.

```

<RT data: rt data: TBP>+≡
  procedure :: set_log => rt_data_set_log
  procedure :: set_int => rt_data_set_int
  procedure :: set_real => rt_data_set_real
  procedure :: set_cmplx => rt_data_set_cmplx
  procedure :: set_subevt => rt_data_set_subevt
  procedure :: set_pdg_array => rt_data_set_pdg_array
  procedure :: set_string => rt_data_set_string

<RT data: procedures>+≡
  subroutine rt_data_set_log (global, name, lval, is_known, verbose)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    logical, intent(in) :: lval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    call var_list_set_log (global%var_list, name, lval, is_known, &
      verbose=verbose)
  end subroutine rt_data_set_log

  subroutine rt_data_set_int (global, name, ival, is_known, verbose)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    integer, intent(in) :: ival
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    call var_list_set_int (global%var_list, name, ival, is_known, &
      verbose=verbose)
  end subroutine rt_data_set_int

  subroutine rt_data_set_real (global, name, rval, is_known, verbose, pacified)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    real(default), intent(in) :: rval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose, pacified
    call var_list_set_real (global%var_list, name, rval, is_known, &
      verbose=verbose, pacified=pacified)
  end subroutine rt_data_set_real

  subroutine rt_data_set_cmplx (global, name, cval, is_known, verbose, pacified)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    complex(default), intent(in) :: cval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose, pacified

```



```

        call var_list_set_cmplx (global%var_list, name, cval, is_known, &
                                verbose=verbose, pacified=pacified)
    end subroutine rt_data_set_cmplx

subroutine rt_data_set_subevt (global, name, pval, is_known, verbose)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    type(subevt_t), intent(in) :: pval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    call var_list_set_subevt (global%var_list, name, pval, is_known, &
                             verbose=verbose)
end subroutine rt_data_set_subevt

subroutine rt_data_set_pdg_array (global, name, aval, is_known, verbose)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in) :: aval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    call var_list_set_pdg_array (global%var_list, name, aval, is_known, &
                                 verbose=verbose)
end subroutine rt_data_set_pdg_array

subroutine rt_data_set_string (global, name, sval, is_known, verbose)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: name
    type(string_t), intent(in) :: sval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    call var_list_set_string (global%var_list, name, sval, is_known, &
                              verbose=verbose)
end subroutine rt_data_set_string

```

Return the value of a variable, assuming that the type is correct.

```

<RT data: rt data: TBP>+≡
    procedure :: get_lval => rt_data_get_lval
    procedure :: get_ival => rt_data_get_ival
    procedure :: get_rval => rt_data_get_rval
    procedure :: get_cval => rt_data_get_cval
    procedure :: get_pval => rt_data_get_pval
    procedure :: get_aval => rt_data_get_aval
    procedure :: get_sval => rt_data_get_sval

<RT data: procedures>+≡
    function rt_data_get_lval (global, name) result (lval)
        logical :: lval
        class(rt_data_t), intent(in), target :: global
        type(string_t), intent(in) :: name
        type(var_list_t), pointer :: var_list
        var_list => global%get_var_list_ptr ()
        lval = var_list%get_lval (name)
    end function rt_data_get_lval

```

```

function rt_data_get_ival (global, name) result (ival)
    integer :: ival
    class(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    ival = var_list%get_ival (name)
end function rt_data_get_ival

function rt_data_get_rval (global, name) result (rval)
    real(default) :: rval
    class(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    rval = var_list%get_rval (name)
end function rt_data_get_rval

function rt_data_get_cval (global, name) result (cval)
    complex(default) :: cval
    class(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    cval = var_list%get_cval (name)
end function rt_data_get_cval

function rt_data_get_aval (global, name) result (aval)
    type(pdg_array_t) :: aval
    class(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    aval = var_list%get_aval (name)
end function rt_data_get_aval

function rt_data_get_pval (global, name) result (pval)
    type(subvt_t) :: pval
    class(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    pval = var_list%get_pval (name)
end function rt_data_get_pval

function rt_data_get_sval (global, name) result (sval)
    type(string_t) :: sval
    class(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    sval = var_list%get_sval (name)
end function rt_data_get_sval

```

28.8.11 Further Content

Add a library (available via a pointer of type `prclib_entry_t`) to the stack and update the pointer and variable list to the current library. The pointer association of `prclib_entry` will be discarded.

```
<RT data: rt data: TBP>+≡
  procedure :: add_prclib => rt_data_add_prclib

<RT data: procedures>+≡
  subroutine rt_data_add_prclib (global, prclib_entry)
    class(rt_data_t), intent(inout) :: global
    type(prclib_entry_t), intent(inout), pointer :: prclib_entry
    call global%prclib_stack%push (prclib_entry)
    call global%update_prclib (global%prclib_stack%get_first_ptr ())
  end subroutine rt_data_add_prclib
```

Given a pointer to a process library, make this the currently active library.

```
<RT data: rt data: TBP>+≡
  procedure :: update_prclib => rt_data_update_prclib

<RT data: procedures>+≡
  subroutine rt_data_update_prclib (global, lib)
    class(rt_data_t), intent(inout) :: global
    type(process_library_t), intent(in), target :: lib
    global%prclib => lib
    if (global%var_list%contains (&
      var_str ("library_name"), follow_link = .false.)) then
      call var_list_set_string (global%var_list, &
        var_str ("library_name"), &
        global%prclib%get_name (), is_known=.true.)
    else
      call var_list_append_string (global%var_list, &
        var_str ("library_name"), global%prclib%get_name (), &
        intrinsic = .true.)
    end if
  end subroutine rt_data_update_prclib
```

28.8.12 Miscellaneous

The helicity selection data are distributed among several parameters. Here, we collect them in a single record.

```
<RT data: rt data: TBP>+≡
  procedure :: get_helicity_selection => rt_data_get_helicity_selection

<RT data: procedures>+≡
  function rt_data_get_helicity_selection (rt_data) result (helicity_selection)
    class(rt_data_t), intent(in) :: rt_data
    type(helicity_selection_t) :: helicity_selection
    associate (var_list => rt_data%var_list)
      helicity_selection%active = var_list%get_lval (&
        var_str ("helicity_selection_active"))
      if (helicity_selection%active) then
        helicity_selection%threshold = var_list%get_rval (&
```

```

        var_str ("helicity_selection_threshold"))
        helicity_selection%cutoff = var_list%get_ival (&
            var_str ("helicity_selection_cutoff"))
    end if
end associate
end function rt_data_get_helicity_selection

```

Show the beam setup: beam structure and relevant global variables.

```

<RT data: rt data: TBP>+≡
    procedure :: show_beams => rt_data_show_beams

<RT data: procedures>+≡
    subroutine rt_data_show_beams (rt_data, unit)
        class(rt_data_t), intent(in) :: rt_data
        integer, intent(in), optional :: unit
        type(string_t) :: s
        integer :: u
        u = given_output_unit (unit)
        associate (beams => rt_data%beam_structure, var_list => rt_data%var_list)
            call beams%write (u)
            if (.not. beams%asymmetric () .and. beams%get_n_beam () == 2) then
                write (u, "(2x,A,ES19.12,1x,'GeV')") "sqrts =", &
                    var_list%get_rval (var_str ("sqrts"))
            end if
            if (beams%contains ("pdf_builtin")) then
                s = var_list%get_sval (var_str ("pdf_builtin_set"))
                if (s /= "") then
                    write (u, "(2x,A,1x,3A)") "PDF set =", "'", char (s), "'"
                else
                    write (u, "(2x,A,1x,A)") "PDF set =", "[undefined]"
                end if
            end if
            if (beams%contains ("lhpdf")) then
                s = var_list%get_sval (var_str ("lhpdf_dir"))
                if (s /= "") then
                    write (u, "(2x,A,1x,3A)") "LHAPDF dir    =", "'", char (s), "'"
                end if
                s = var_list%get_sval (var_str ("lhpdf_file"))
                if (s /= "") then
                    write (u, "(2x,A,1x,3A)") "LHAPDF file    =", "'", char (s), "'"
                    write (u, "(2x,A,1x,I0)") "LHAPDF member =", &
                        var_list%get_ival (var_str ("lhpdf_member"))
                else
                    write (u, "(2x,A,1x,A)") "LHAPDF file    =", "[undefined]"
                end if
            end if
            if (beams%contains ("lhpdf_photon")) then
                s = var_list%get_sval (var_str ("lhpdf_dir"))
                if (s /= "") then
                    write (u, "(2x,A,1x,3A)") "LHAPDF dir    =", "'", char (s), "'"
                end if
                s = var_list%get_sval (var_str ("lhpdf_photon_file"))
                if (s /= "") then
                    write (u, "(2x,A,1x,3A)") "LHAPDF file    =", "'", char (s), "'"

```

```

        write (u, "(2x,A,1x,I0)") "LHAPDF member =", &
            var_list%get_ival (var_str ("lhapdf_member"))
        write (u, "(2x,A,1x,I0)") "LHAPDF scheme =", &
            var_list%get_ival (&
                var_str ("lhapdf_photon_scheme"))
    else
        write (u, "(2x,A,1x,A)") "LHAPDF file   =", "[undefined]"
    end if
end if
if (beams%contains ("isr")) then
    write (u, "(2x,A,ES19.12)") "ISR alpha =", &
        var_list%get_rval (var_str ("isr_alpha"))
    write (u, "(2x,A,ES19.12)") "ISR Q max =", &
        var_list%get_rval (var_str ("isr_q_max"))
    write (u, "(2x,A,ES19.12)") "ISR mass  =", &
        var_list%get_rval (var_str ("isr_mass"))
    write (u, "(2x,A,1x,I0)") "ISR order  =", &
        var_list%get_ival (var_str ("isr_order"))
    write (u, "(2x,A,1x,L1)") "ISR recoil =", &
        var_list%get_lval (var_str ("?isr_recoil"))
end if
if (beams%contains ("epa")) then
    write (u, "(2x,A,ES19.12)") "EPA alpha  =", &
        var_list%get_rval (var_str ("epa_alpha"))
    write (u, "(2x,A,ES19.12)") "EPA x min  =", &
        var_list%get_rval (var_str ("epa_x_min"))
    write (u, "(2x,A,ES19.12)") "EPA Q min  =", &
        var_list%get_rval (var_str ("epa_q_min"))
    write (u, "(2x,A,ES19.12)") "EPA E max  =", &
        var_list%get_rval (var_str ("epa_e_max"))
    write (u, "(2x,A,ES19.12)") "EPA mass   =", &
        var_list%get_rval (var_str ("epa_mass"))
    write (u, "(2x,A,1x,L1)") "EPA recoil =", &
        var_list%get_lval (var_str ("?epa_recoil"))
end if
if (beams%contains ("ewa")) then
    write (u, "(2x,A,ES19.12)") "EWA x min      =", &
        var_list%get_rval (var_str ("ewa_x_min"))
    write (u, "(2x,A,ES19.12)") "EWA Pt max      =", &
        var_list%get_rval (var_str ("ewa_pt_max"))
    write (u, "(2x,A,ES19.12)") "EWA mass       =", &
        var_list%get_rval (var_str ("ewa_mass"))
    write (u, "(2x,A,1x,L1)") "EWA mom cons.   =", &
        var_list%get_lval (&
            var_str ("?ewa_keep_momentum"))
    write (u, "(2x,A,1x,L1)") "EWA energ. cons. =", &
        var_list%get_lval (&
            var_str ("ewa_keep_energy"))
end if
if (beams%contains ("circe1")) then
    write (u, "(2x,A,1x,I0)") "CIRCE1 version   =", &
        var_list%get_ival (var_str ("circe1_ver"))
    write (u, "(2x,A,1x,I0)") "CIRCE1 revision  =", &
        var_list%get_ival (var_str ("circe1_rev"))

```

```

s = var_list%get_sval (var_str ("$circe1_acc"))
write (u, "(2x,A,1x,A)") "CIRCE1 acceler.  =", char (s)
write (u, "(2x,A,1x,I0)") "CIRCE1 chattin.  =", &
var_list%get_ival (var_str ("circe1_chat"))
write (u, "(2x,A,ES19.12)") "CIRCE1 sqrts      =", &
var_list%get_rval (var_str ("circe1_sqrts"))
write (u, "(2x,A,ES19.12)") "CIRCE1 epsil.    =", &
var_list%get_rval (var_str ("circe1_eps"))
write (u, "(2x,A,1x,L1)") "CIRCE1 phot. 1  =", &
var_list%get_lval (var_str ("?circe1_photon1"))
write (u, "(2x,A,1x,L1)") "CIRCE1 phot. 2  =", &
var_list%get_lval (var_str ("?circe1_photon2"))
write (u, "(2x,A,1x,L1)") "CIRCE1 generat. =", &
var_list%get_lval (var_str ("?circe1_generate"))
write (u, "(2x,A,1x,L1)") "CIRCE1 mapping  =", &
var_list%get_lval (var_str ("?circe1_map"))
write (u, "(2x,A,ES19.12)") "CIRCE1 map. slope =", &
var_list%get_rval (var_str ("circe1_mapping_slope"))
write (u, "(2x,A,1x,L1)") "CIRCE recoil photon =", &
var_list%get_lval (var_str ("?circe1_with_radiation"))
end if
if (beams%contains ("circe2")) then
s = var_list%get_sval (var_str ("$circe2_design"))
write (u, "(2x,A,1x,A)") "CIRCE2 design  =", char (s)
s = var_list%get_sval (var_str ("$circe2_file"))
write (u, "(2x,A,1x,A)") "CIRCE2 file    =", char (s)
write (u, "(2x,A,1x,L1)") "CIRCE2 polarized =", &
var_list%get_lval (var_str ("?circe2_polarized"))
end if
if (beams%contains ("beam_events")) then
s = var_list%get_sval (var_str ("$beam_events_file"))
write (u, "(2x,A,1x,A)") "Beam events file  =", char (s)
write (u, "(2x,A,1x,L1)") "Beam events EOF warn =", &
var_list%get_lval (var_str ("?beam_events_warn_eof"))
end if
end associate
end subroutine rt_data_show_beams

```

Return the collision energy as determined by the current beam settings. Without beam setup, this is the `sqrts` variable.

If the value is meaningless for a setup, the function returns zero.

<RT data: rt data: TBP>+≡

```
procedure :: get_sqrts => rt_data_get_sqrts
```

<RT data: procedures>+≡

```

function rt_data_get_sqrts (rt_data) result (sqrts)
class(rt_data_t), intent(in) :: rt_data
real(default) :: sqrts
sqrts = rt_data%var_list%get_rval (var_str ("sqrts"))
end function rt_data_get_sqrts

```

For testing purposes, the `rt_data_t` contents can be pacified to suppress numerical fluctuations in (constant) test matrix elements.

```

<RT data: rt data: TBP>+≡
  procedure :: pacify => rt_data_pacify

<RT data: procedures>+≡
  subroutine rt_data_pacify (rt_data, efficiency_reset, error_reset)
    class(rt_data_t), intent(inout) :: rt_data
    logical, intent(in), optional :: efficiency_reset, error_reset
    type(process_entry_t), pointer :: process
    process => rt_data%process_stack%first
    do while (associated (process))
      call process%pacify (efficiency_reset, error_reset)
      process => process%next
    end do
  end subroutine rt_data_pacify

```

Set the matrix element method

```

<RT data: rt data: TBP>+≡
  procedure :: set_me_method => rt_data_set_me_method

<RT data: procedures>+≡
  subroutine rt_data_set_me_method (global, me_method)
    class(rt_data_t), intent(inout) :: global
    type(string_t), intent(in) :: me_method
    logical :: success
    success = global%var_list%contains (var_str ("method"))
    if (success) &
      call global%var_list%set_sval (var_str ("method"), me_method)
  end subroutine rt_data_set_me_method

```

28.8.13 Test

This is the master for calling self-test procedures.

```

<RT data: public>+≡
  public :: rt_data_test

<RT data: tests>≡
  subroutine rt_data_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <RT data: execute tests>
  end subroutine rt_data_test

```

Initial content

Force system-dependent objects to well-defined values. Some of the variables are locked and therefore must be addressed directly.

This is, of course, only required for testing purposes. In principle, the `real_specimen` variables could be set to their values in `rt_data_t`, but this depends on the precision again, so we set them to some dummy values.

```

<RT data: rt data: TBP>+≡
  procedure :: fix_system_dependencies => rt_data_fix_system_dependencies

```

```

<RT data: tests>+≡
subroutine rt_data_fix_system_dependencies (rt_data)
  class(rt_data_t), intent(inout), target :: rt_data
  type(var_list_t), pointer :: var_list
  var_list => rt_data%var_list
  call var_list_set_log (var_list, var_str ("?omega_omp"), &
    .false., is_known = .true., force=.true.)
  call var_list_set_log (var_list, var_str ("?omp_is_active"), &
    .false., is_known = .true., force=.true.)
  call var_list_set_int (var_list, var_str ("omp_num_threads_default"), &
    1, is_known = .true., force=.true.)
  call var_list_set_int (var_list, var_str ("omp_num_threads"), &
    1, is_known = .true., force=.true.)
  call var_list_set_int (var_list, var_str ("real_range"), &
    307, is_known = .true., force=.true.)
  call var_list_set_int (var_list, var_str ("real_precision"), &
    15, is_known = .true., force=.true.)
  call var_list_set_real (var_list, var_str ("real_epsilon"), &
    1.e-16_default, is_known = .true., force=.true.)
  call var_list_set_real (var_list, var_str ("real_tiny"), &
    1.e-300_default, is_known = .true., force=.true.)

  rt_data%os_data%fc = "Fortran-compiler"
  rt_data%os_data%fcflags = "Fortran-flags"

end subroutine rt_data_fix_system_dependencies

```

Display the RT data in the state just after (global) initialization.

```

<RT data: execute tests>≡
  call test (rt_data_1, "rt_data_1", &
    "initialize", &
    u, results)

<RT data: tests>+≡
subroutine rt_data_1 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: rt_data

  write (u, "(A)")  "* Test output: rt_data_1"
  write (u, "(A)")  "* Purpose: initialize global runtime data"
  write (u, "(A)")

  call rt_data%global_init (logfile = var_str ("rt_data.log"))

  call rt_data%fix_system_dependencies ()
  call rt_data%set_int (var_str ("seed"), 0, is_known=.true.)

  call rt_data%it_list%init ([2, 3], [5000, 20000])

  call rt_data%write (u)

  call rt_data%final ()

  write (u, "(A)")

```



```

        write (u, "(A)")  "* Test output end: rt_data_1"

    end subroutine rt_data_1

```

Fill values

Fill in empty slots in the runtime data block.

```

<RT data: execute tests>+=
    call test (rt_data_2, "rt_data_2", &
        "fill", &
        u, results)

<RT data: tests>+=
    subroutine rt_data_2 (u)
        integer, intent(in) :: u
        type(rt_data_t), target :: rt_data
        type(flavor_t), dimension(2) :: flv
        type(string_t) :: cut_expr_text
        type(ifile_t) :: ifile
        type(stream_t) :: stream
        type(parse_tree_t) :: parse_tree

        write (u, "(A)")  "* Test output: rt_data_2"
        write (u, "(A)")  "* Purpose: initialize global runtime data &
            &and fill contents"
        write (u, "(A)")

        call syntax_model_file_init ()

        call rt_data%global_init ()
        call rt_data%fix_system_dependencies ()

        call rt_data%select_model (var_str ("Test"))

        call rt_data%set_real (var_str ("sqrts"), &
            1000._default, is_known = .true.)
        call rt_data%set_int (var_str ("seed"), &
            0, is_known=.true.)
        call flv%init ([25,25], rt_data%model)

        call rt_data%set_string (var_str ("$_run_id"), &
            var_str ("run1"), is_known = .true.)
        call rt_data%set_real (var_str ("luminosity"), &
            33._default, is_known = .true.)

        call syntax_pexpr_init ()
        cut_expr_text = "all Pt > 100 [s]"
        call ifile_append (ifile, cut_expr_text)
        call stream_init (stream, ifile)
        call parse_tree_init_lexpr (parse_tree, stream, .true.)
        rt_data%pn%cuts_lexpr => parse_tree_get_root_ptr (parse_tree)

        allocate (rt_data%sample_fmt (2))

```

```

rt_data%sample_fmt(1) = "foo_fmt"
rt_data%sample_fmt(2) = "bar_fmt"

call rt_data%write (u)

call parse_tree_final (parse_tree)
call stream_final (stream)
call ifile_final (ifile)
call syntax_pexpr_final ()

call rt_data%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_2"

end subroutine rt_data_2

```

Save and restore

Set up a local runtime data block, change some contents, restore the global block.

```

<RT data: execute tests>+≡
  call test (rt_data_3, "rt_data_3", &
    "save/restore", &
    u, results)

<RT data: tests>+≡
subroutine rt_data_3 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: rt_data, local
  type(flavor_t), dimension(2) :: flv
  type(string_t) :: cut_expr_text
  type(ifile_t) :: ifile
  type(stream_t) :: stream
  type(parse_tree_t) :: parse_tree
  type(prclib_entry_t), pointer :: lib

  write (u, "(A)")  "* Test output: rt_data_3"
  write (u, "(A)")  "* Purpose: initialize global runtime data &
    &and fill contents;"
  write (u, "(A)")  "* copy to local block and back"
  write (u, "(A)")

  write (u, "(A)")  "* Init global data"
  write (u, "(A)")

  call syntax_model_file_init ()

  call rt_data%global_init ()
  call rt_data%fix_system_dependencies ()
  call rt_data%set_int (var_str ("seed"), &
    0, is_known=.true.)

```

```

call rt_data%select_model (var_str ("Test"))

call rt_data%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call flv%init ([25,25], rt_data%model)

call rt_data%beam_structure%init_sf (flv%get_name (), [1])
call rt_data%beam_structure%set_sf (1, 1, var_str ("pdf_builtin"))

call rt_data%set_string (var_str ("$_run_id"), &
    var_str ("run1"), is_known = .true.)
call rt_data%set_real (var_str ("luminosity"), &
    33._default, is_known = .true.)

call syntax_pexpr_init ()
cut_expr_text = "all Pt > 100 [s]"
call ifile_append (ifile, cut_expr_text)
call stream_init (stream, ifile)
call parse_tree_init_lexpr (parse_tree, stream, .true.)
rt_data%pn%cuts_lexpr => parse_tree_get_root_ptr (parse_tree)

allocate (rt_data%sample_fmt (2))
rt_data%sample_fmt(1) = "foo_fmt"
rt_data%sample_fmt(2) = "bar_fmt"

allocate (lib)
call lib%init (var_str ("library_1"))
call rt_data%add_prclib (lib)

write (u, "(A)")  "* Init and modify local data"
write (u, "(A)")

call local%local_init (rt_data)
call local%append_string (var_str ("$_integration_method"), intrinsic=.true.)
call local%append_string (var_str ("$_phs_method"), intrinsic=.true.)

call local%activate ()

write (u, "(1x,A,L1)") "model associated  = ", associated (local%model)
write (u, "(1x,A,L1)") "library associated = ", associated (local%prclib)
write (u, *)

call local%model_set_real (var_str ("ms"), 150._default)
call local%set_string (var_str ("$_integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call local%set_string (var_str ("$_phs_method"), &
    var_str ("single"), is_known = .true.)

local%os_data%fc = "Local compiler"

allocate (lib)
call lib%init (var_str ("library_2"))
call local%add_prclib (lib)

```

```

call local%write (u)

write (u, "(A)")
write (u, "(A)")  "* Restore global data"
write (u, "(A)")

call local%deactivate (rt_data)

write (u, "(1x,A,L1)") "model associated  = ", associated (rt_data%model)
write (u, "(1x,A,L1)") "library associated = ", associated (rt_data%prclib)
write (u, *)

call rt_data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call parse_tree_final (parse_tree)
call stream_final (stream)
call ifile_final (ifile)
call syntax_pexpr_final ()

call rt_data%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_3"

end subroutine rt_data_3

```

Show variables

Display selected variables in the global record.

```

<RT data: execute tests>+≡
  call test (rt_data_4, "rt_data_4", &
    "show variables", &
    u, results)

<RT data: tests>+≡
  subroutine rt_data_4 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: rt_data

    type(string_t), dimension(0) :: empty_string_array

    write (u, "(A)")  "* Test output: rt_data_4"
    write (u, "(A)")  "* Purpose: display selected variables"
    write (u, "(A)")

    call rt_data%global_init ()

    write (u, "(A)")  "* No variables:"

```

```

write (u, "(A)")

call rt_data%write_vars (u, empty_string_array)

write (u, "(A)")  "* Two variables:"
write (u, "(A)")

call rt_data%write_vars (u, &
    [var_str ("?unweighted"), var_str ("phs_method")])

write (u, "(A)")
write (u, "(A)")  "* Display whole record with selected variables"
write (u, "(A)")

call rt_data%write (u, &
    vars = [var_str ("?unweighted"), var_str ("phs_method")])

call rt_data%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_4"

end subroutine rt_data_4

```

Show parts

Display only selected parts in the state just after (global) initialization.

```

<RT data: execute tests>+≡
call test (rt_data_5, "rt_data_5", &
    "show parts", &
    u, results)

<RT data: tests>+≡
subroutine rt_data_5 (u)
integer, intent(in) :: u
type(rt_data_t), target :: rt_data

write (u, "(A)")  "* Test output: rt_data_5"
write (u, "(A)")  "* Purpose: display parts of rt data"
write (u, "(A)")

call rt_data%global_init ()
call rt_data%write_libraries (u)

write (u, "(A)")

call rt_data%write_beams (u)

write (u, "(A)")

call rt_data%write_process_stack (u)

call rt_data%final ()

```

```

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_5"

end subroutine rt_data_5

```

Local Model

Locally modify a model and restore the global one. We need an auxiliary function to determine the status of a model particle:

(RT data: tests)+≡

```

function is_stable (pdg, rt_data) result (flag)
  integer, intent(in) :: pdg
  type(rt_data_t), intent(in) :: rt_data
  logical :: flag
  type(flavor_t) :: flv
  call flv%init (pdg, rt_data%model)
  flag = flv%is_stable ()
end function is_stable

```

```

function is_polarized (pdg, rt_data) result (flag)
  integer, intent(in) :: pdg
  type(rt_data_t), intent(in) :: rt_data
  logical :: flag
  type(flavor_t) :: flv
  call flv%init (pdg, rt_data%model)
  flag = flv%is_polarized ()
end function is_polarized

```

(RT data: execute tests)+≡

```

call test (rt_data_6, "rt_data_6", &
  "local model", &
  u, results)

```

(RT data: tests)+≡

```

subroutine rt_data_6 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: rt_data, local
  type(var_list_t), pointer :: model_vars
  type(string_t) :: var_name

  write (u, "(A)")  "* Test output: rt_data_6"
  write (u, "(A)")  "* Purpose: apply and keep local modifications to model"
  write (u, "(A)")

  call syntax_model_file_init ()

  call rt_data%global_init ()
  call rt_data%select_model (var_str ("Test"))

  write (u, "(A)")  "* Original model"
  write (u, "(A)")

```

```

call rt_data%write_model_list (u)
write (u, *)
write (u, "(A,L1)") "s is stable    = ", is_stable (25, rt_data)
write (u, "(A,L1)") "f is polarized = ", is_polarized (6, rt_data)

write (u, *)

var_name = "ff"

write (u, "(A)", advance="no") "Global model variable: "
model_vars => rt_data%model%get_var_list_ptr ()
call var_list_write_var (model_vars, var_name, u)

write (u, "(A)")
write (u, "(A)")  "* Apply local modifications: unstable"
write (u, "(A)")

call local%local_init (rt_data)
call local%activate ()

call local%model_set_real (var_name, 0.4_default)
call local%modify_particle (25, stable = .false., decay = [var_str ("d1")])
call local%modify_particle (6, stable = .false., &
    decay = [var_str ("f1")], isotropic_decay = .true.)
call local%modify_particle (-6, stable = .false., &
    decay = [var_str ("f2"), var_str ("f3")], diagonal_decay = .true.)

call local%model%write (u)

write (u, "(A)")
write (u, "(A)")  "* Further modifications"
write (u, "(A)")

call local%modify_particle (6, stable = .false., &
    decay = [var_str ("f1")], &
    diagonal_decay = .true., isotropic_decay = .false.)
call local%modify_particle (-6, stable = .false., &
    decay = [var_str ("f2"), var_str ("f3")], &
    diagonal_decay = .false., isotropic_decay = .true.)
call local%model%write (u)

write (u, "(A)")
write (u, "(A)")  "* Further modifications: f stable but polarized"
write (u, "(A)")

call local%modify_particle (6, stable = .true., polarized = .true.)
call local%modify_particle (-6, stable = .true.)
call local%model%write (u)

write (u, "(A)")
write (u, "(A)")  "* Global model"
write (u, "(A)")

```

```

call rt_data%model%write (u)
write (u, *)
write (u, "(A,L1)") "s is stable    = ", is_stable (25, rt_data)
write (u, "(A,L1)") "f is polarized = ", is_polarized (6, rt_data)

write (u, "(A)")
write (u, "(A)")  "* Local model"
write (u, "(A)")

call local%model%write (u)
write (u, *)
write (u, "(A,L1)") "s is stable    = ", is_stable (25, local)
write (u, "(A,L1)") "f is polarized = ", is_polarized (6, local)

write (u, *)

write (u, "(A)", advance="no") "Global model variable: "
model_vars => rt_data%model%get_var_list_ptr ()
call var_list_write_var (model_vars, var_name, u)

write (u, "(A)", advance="no") "Local model variable: "
call var_list_write_var (local%model%get_var_list_ptr (), &
    var_name, u)

write (u, "(A)")
write (u, "(A)")  "* Restore global"

call local%deactivate (rt_data, keep_local = .true.)

write (u, "(A)")
write (u, "(A)")  "* Global model"
write (u, "(A)")

call rt_data%model%write (u)
write (u, *)
write (u, "(A,L1)") "s is stable    = ", is_stable (25, rt_data)
write (u, "(A,L1)") "f is polarized = ", is_polarized (6, rt_data)

write (u, "(A)")
write (u, "(A)")  "* Local model"
write (u, "(A)")

call local%model%write (u)
write (u, *)
write (u, "(A,L1)") "s is stable    = ", is_stable (25, local)
write (u, "(A,L1)") "f is polarized = ", is_polarized (6, local)

write (u, *)

write (u, "(A)", advance="no") "Global model variable: "
model_vars => rt_data%model%get_var_list_ptr ()
call var_list_write_var (model_vars, var_name, u)

write (u, "(A)", advance="no") "Local model variable: "

```



```

call var_list_write_var (local%model%get_var_list_ptr (), &
    var_name, u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call local%model%final ()
deallocate (local%model)

call rt_data%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_6"

end subroutine rt_data_6

```

Result variables

Initialize result variables and check that they are accessible via the global variable list.

```

<RT data: execute tests>+≡
call test (rt_data_7, "rt_data_7", &
    "result variables", &
    u, results)

<RT data: tests>+≡
subroutine rt_data_7 (u)
integer, intent(in) :: u
type(rt_data_t), target :: rt_data

write (u, "(A)")  "* Test output: rt_data_7"
write (u, "(A)")  "* Purpose: set and access result variables"
write (u, "(A)")

write (u, "(A)")  "* Initialize process variables"
write (u, "(A)")

call rt_data%global_init ()
call rt_data%process_stack%init_result_vars (var_str ("testproc"))

call var_list_write_var (rt_data%var_list, &
    var_str ("integral(testproc)"), u)
call var_list_write_var (rt_data%var_list, &
    var_str ("error(testproc)"), u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call rt_data%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_7"

```

```
end subroutine rt_data_7
```

Beam energy

If beam parameters are set, the variable `sqrts` is not necessarily the collision energy. The method `get_sqrts` fetches the correct value.

```
<RT data: execute tests>+≡
  call test (rt_data_8, "rt_data_8", &
    "beam energy", &
    u, results)

<RT data: tests>+≡
  subroutine rt_data_8 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: rt_data

    write (u, "(A)")  "* Test output: rt_data_8"
    write (u, "(A)")  "*   Purpose: get correct collision energy"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize"
    write (u, "(A)")

    call rt_data%global_init ()

    write (u, "(A)")  "* Set sqrts"
    write (u, "(A)")

    call var_list_set_real (rt_data%var_list, var_str ("sqrts"), &
      1000._default, is_known = .true.)
    write (u, "(1x,A,ES19.12)")  "sqrts =", rt_data%get_sqrts ()

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

    call rt_data%final ()

    write (u, "(A)")
    write (u, "(A)")  "* Test output end: rt_data_8"

  end subroutine rt_data_8
```

Local variable modifications

```
<RT data: execute tests>+≡
  call test (rt_data_9, "rt_data_9", &
    "local variables", &
    u, results)
```

```

<RT data: tests>+≡
subroutine rt_data_9 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: global, local
  type(var_list_t), pointer :: var_list

  write (u, "(A)")  "* Test output: rt_data_9"
  write (u, "(A)")  "* Purpose: handle local variables"
  write (u, "(A)")

  call syntax_model_file_init ()

  write (u, "(A)")  "* Initialize global record and set some variables"
  write (u, "(A)")

  call global%global_init ()
  call global%select_model (var_str ("Test"))

  call global%set_real (var_str ("sqrts"), 17._default, is_known = .true.)
  call global%set_real (var_str ("luminosity"), 2._default, is_known = .true.)
  call global%model_set_real (var_str ("ff"), 0.5_default)
  call global%model_set_real (var_str ("gy"), 1.2_default)

  var_list => global%get_var_list_ptr ()

  call var_list_write_var (var_list, var_str ("sqrts"), u)
  call var_list_write_var (var_list, var_str ("luminosity"), u)
  call var_list_write_var (var_list, var_str ("ff"), u)
  call var_list_write_var (var_list, var_str ("gy"), u)
  call var_list_write_var (var_list, var_str ("mf"), u)
  call var_list_write_var (var_list, var_str ("x"), u)

  write (u, "(A)")

  write (u, "(1x,A,1x,F5.2)") "sqrts      = ", &
    global%get_rval (var_str ("sqrts"))
  write (u, "(1x,A,1x,F5.2)") "luminosity = ", &
    global%get_rval (var_str ("luminosity"))
  write (u, "(1x,A,1x,F5.2)") "ff          = ", &
    global%get_rval (var_str ("ff"))
  write (u, "(1x,A,1x,F5.2)") "gy          = ", &
    global%get_rval (var_str ("gy"))
  write (u, "(1x,A,1x,F5.2)") "mf          = ", &
    global%get_rval (var_str ("mf"))
  write (u, "(1x,A,1x,F5.2)") "x           = ", &
    global%get_rval (var_str ("x"))

  write (u, "(A)")
  write (u, "(A)")  "* Create local record with local variables"
  write (u, "(A)")

  call local%local_init (global)

  call local%append_real (var_str ("luminosity"), intrinsic = .true.)

```

```

call local%append_real (var_str ("x"), user = .true.)

call local%activate ()

var_list => local%get_var_list_ptr ()

call var_list_write_var (var_list, var_str ("sqrts"), u)
call var_list_write_var (var_list, var_str ("luminosity"), u)
call var_list_write_var (var_list, var_str ("ff"), u)
call var_list_write_var (var_list, var_str ("gy"), u)
call var_list_write_var (var_list, var_str ("mf"), u)
call var_list_write_var (var_list, var_str ("x"), u)

write (u, "(A)")

write (u, "(1x,A,1x,F5.2)") "sqrts      = ", &
    local%get_rval (var_str ("sqrts"))
write (u, "(1x,A,1x,F5.2)") "luminosity = ", &
    local%get_rval (var_str ("luminosity"))
write (u, "(1x,A,1x,F5.2)") "ff      = ", &
    local%get_rval (var_str ("ff"))
write (u, "(1x,A,1x,F5.2)") "gy      = ", &
    local%get_rval (var_str ("gy"))
write (u, "(1x,A,1x,F5.2)") "mf      = ", &
    local%get_rval (var_str ("mf"))
write (u, "(1x,A,1x,F5.2)") "x      = ", &
    local%get_rval (var_str ("x"))

write (u, "(A)")
write (u, "(A)")  "* Modify some local variables"
write (u, "(A)")

call local%set_real (var_str ("luminosity"), 42._default, is_known=.true.)
call local%set_real (var_str ("x"), 6.66_default, is_known=.true.)
call local%model_set_real (var_str ("ff"), 0.7_default)

var_list => local%get_var_list_ptr ()

call var_list_write_var (var_list, var_str ("sqrts"), u)
call var_list_write_var (var_list, var_str ("luminosity"), u)
call var_list_write_var (var_list, var_str ("ff"), u)
call var_list_write_var (var_list, var_str ("gy"), u)
call var_list_write_var (var_list, var_str ("mf"), u)
call var_list_write_var (var_list, var_str ("x"), u)

write (u, "(A)")

write (u, "(1x,A,1x,F5.2)") "sqrts      = ", &
    local%get_rval (var_str ("sqrts"))
write (u, "(1x,A,1x,F5.2)") "luminosity = ", &
    local%get_rval (var_str ("luminosity"))
write (u, "(1x,A,1x,F5.2)") "ff      = ", &
    local%get_rval (var_str ("ff"))
write (u, "(1x,A,1x,F5.2)") "gy      = ", &

```

```

        local%get_rval (var_str ("gy"))
write (u, "(1x,A,1x,F5.2)" "mf"          = ", &
        local%get_rval (var_str ("mf"))
write (u, "(1x,A,1x,F5.2)" "x"          = ", &
        local%get_rval (var_str ("x"))

write (u, "(A)")
write (u, "(A)")  "* Restore globals"
write (u, "(A)")

call local%deactivate (global)

var_list => global%get_var_list_ptr ()

call var_list_write_var (var_list, var_str ("sqrts"), u)
call var_list_write_var (var_list, var_str ("luminosity"), u)
call var_list_write_var (var_list, var_str ("ff"), u)
call var_list_write_var (var_list, var_str ("gy"), u)
call var_list_write_var (var_list, var_str ("mf"), u)
call var_list_write_var (var_list, var_str ("x"), u)

write (u, "(A)")

write (u, "(1x,A,1x,F5.2)" "sqrts"      = ", &
        global%get_rval (var_str ("sqrts"))
write (u, "(1x,A,1x,F5.2)" "luminosity" = ", &
        global%get_rval (var_str ("luminosity"))
write (u, "(1x,A,1x,F5.2)" "ff"        = ", &
        global%get_rval (var_str ("ff"))
write (u, "(1x,A,1x,F5.2)" "gy"        = ", &
        global%get_rval (var_str ("gy"))
write (u, "(1x,A,1x,F5.2)" "mf"        = ", &
        global%get_rval (var_str ("mf"))
write (u, "(1x,A,1x,F5.2)" "x"        = ", &
        global%get_rval (var_str ("x"))

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call local%local_final ()

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: rt_data_9"

end subroutine rt_data_9

```

28.9 Select implementations

For abstract types (process core, integrator, phase space, etc.), we need a way to dynamically select a concrete type, using either data given by the user or a previous selection of a concrete type. This is done by subroutines in the current module.

This module provides no new types, just procedures.

`<dispatch.f90>≡`

`<File header>`

`module dispatch`

`<Use kinds>`

`use kinds, only: i16, double`

`<Use strings>`

`use constants, only: PI`

`use system_dependencies, only: LHAPDF5_AVAILABLE`

`use system_dependencies, only: LHAPDF6_AVAILABLE`

`use system_defs, only: LF`

`use io_units`

`use format_utils, only: write_separator`

`use unit_tests`

`use diagnostics`

`use os_interface`

`use physics_defs, only: MZ_REF, ALPHA_QCD_MZ_REF`

`use physics_defs, only: PROTON, PHOTON, ELECTRON`

`use sm_qcd`

`use pdg_arrays`

`use variables`

`use model_data`

`use flavors`

`use interactions`

`use models`

`use process_constants`

`use pdf_builtin !NODEP!`

`use lhpdf !NODEP!`

`use sf_mappings`

`use sf_base`

`use sf_pdf_builtin`

`use sf_lhpdf`

`use sf_circe1`

`use sf_circe2`

`use sf_isr`

`use sf_epa`

`use sf_ewa`

`use sf_escan`

`use sf_beam_events`

`use sf_user`

`use rng_base`

`use rng_tao`

`use mci_base`

`use mci_midpoint`

`use mci_vamp`

```

use phs_base
use mappings
use phs_forests
use phs_single
use phs_wood
use prc_core_def
use prc_test
use beams
use prc_omega
use prc_template_me
use prc_core
use processes
use powheg
use shower_base
use shower_core
use shower_pythia6
use mlm_matching
use ckkw_base
use shower
use event_transforms
use decays
use hadrons
use beam_structures
use eio_base
use eio_raw
use eio_checkpoints
use eio_lhef
use eio_hepmc
use eio_lcio
use eio_stdhep
use eio_ascii
use eio_weights
use rt_data
use prc_gosam
use prc_openloops
use phs_fks
use nlo_data

<Standard module head>

<Dispatch: public>

<Dispatch: types>

<Dispatch: interfaces>

contains

<Dispatch: procedures>

<Dispatch: tests>

end module dispatch

```

28.9.1 Interfaces

```
<Dispatch: interfaces>≡  
  interface  
    subroutine GetXminM (set, mem, xmin)  
      integer, intent(in) :: set, mem  
      double precision, intent(out) :: xmin  
    end subroutine GetXminM  
  end interface
```

```
<Dispatch: interfaces>+≡  
  interface  
    subroutine GetXmaxM (set, mem, xmax)  
      integer, intent(in) :: set, mem  
      double precision, intent(out) :: xmax  
    end subroutine GetXmaxM  
  end interface
```

```
<Dispatch: interfaces>+≡  
  interface  
    subroutine GetQ2minM (set, mem, q2min)  
      integer, intent(in) :: set, mem  
      double precision, intent(out) :: q2min  
    end subroutine GetQ2minM  
  end interface
```

```
<Dispatch: interfaces>+≡  
  interface  
    subroutine GetQ2maxM (set, mem, q2max)  
      integer, intent(in) :: set, mem  
      double precision, intent(out) :: q2max  
    end subroutine GetQ2maxM  
  end interface
```

28.9.2 Process Core Definition

The `prc_core_def_t` abstract type can be instantiated by providing a `$method` string variable.

Note: `core_def` has `intent(inout)` because gfortran 4.7.1 crashes for `intent(out)`.

```
<Dispatch: public>≡  
  public :: dispatch_core_def  
  
<Dispatch: procedures>≡  
  subroutine dispatch_core_def (core_def, prt_in, prt_out, &  
                                global, id, nlo_type)  
    class(prc_core_def_t), allocatable, intent(inout) :: core_def  
    type(string_t), dimension(:), intent(in) :: prt_in  
    type(string_t), dimension(:), intent(in) :: prt_out  
    type(rt_data_t), intent(in) :: global  
    type(string_t), intent(in), optional :: id  
    integer, intent(in), optional :: nlo_type
```



```

type(string_t) :: method
type(string_t) :: model_name
type(string_t) :: restrictions
logical :: openmp_support
logical :: report_progress
logical :: diags, diags_color
type(string_t) :: extra_options
type(model_t), pointer :: model
model => global%model
associate (var_list => global%get_var_list_ptr ())
  method = var_list%get_sval (var_str ("%method"))
  if (associated (model)) then
    model_name = model%get_name ()
  else
    model_name = ""
  end if
  select case (char (method))
  case ("unit_test")
    allocate (prc_test_def_t :: core_def)
    select type (core_def)
    type is (prc_test_def_t)
      call core_def%init (model_name, prt_in, prt_out)
    end select
  case ("template")
    allocate (template_me_def_t :: core_def)
    select type (core_def)
    type is (template_me_def_t)
      call core_def%init (model, prt_in, prt_out, unity = .false.)
    end select
  case ("template_unity")
    allocate (template_me_def_t :: core_def)
    select type (core_def)
    type is (template_me_def_t)
      call core_def%init (model, prt_in, prt_out, unity = .true.)
    end select
  case ("omega")
    diags = var_list%get_lval (&
      var_str ("%diags"))
    diags_color = var_list%get_lval (&
      var_str ("%diags_color"))
    restrictions = var_list%get_sval (&
      var_str ("%restrictions"))
    openmp_support = var_list%get_lval (&
      var_str ("%omega_openmp"))
    report_progress = var_list%get_lval (&
      var_str ("%report_progress"))
    extra_options = var_list%get_sval (&
      var_str ("%omega_flags"))
    allocate (omega_omega_def_t :: core_def)
    select type (core_def)
    type is (omega_omega_def_t)
      call core_def%init (model_name, prt_in, prt_out, &
        restrictions, openmp_support, report_progress, &
        extra_options, diags, diags_color)

```

```

        end select
    case ("ovm")
        diags = var_list%get_lval (&
            var_str ("?diags"))
        diags_color = var_list%get_lval (&
            var_str ("?diags_color"))
        restrictions = var_list%get_sval (&
            var_str ("$restrictions"))
        openmp_support = var_list%get_lval (&
            var_str ("?omega_openmp"))
        report_progress = var_list%get_lval (&
            var_str ("?report_progress"))
        extra_options = var_list%get_sval (&
            var_str ("$omega_flags"))
        allocate (omega_ovm_def_t :: core_def)
        select type (core_def)
        type is (omega_ovm_def_t)
            call core_def%init (model_name, prt_in, prt_out, &
                restrictions, openmp_support, report_progress, &
                extra_options, diags, diags_color)
        end select
    case ("gosam")
        allocate (gosam_def_t :: core_def)
        select type (core_def)
        type is (gosam_def_t)
            if (present (id)) then
                call core_def%init (id, model_name, prt_in, &
                    prt_out, nlo_type)
            else
                call msg_fatal ("Dispatch GoSam def: No id!")
            end if
        end select
    case ("openloops")
        allocate (openloops_def_t :: core_def)
        select type (core_def)
        type is (openloops_def_t)
            if (present (id)) then
                call core_def%init (id, model_name, prt_in, &
                    prt_out, nlo_type)
            else
                call msg_fatal ("Dispatch OpenLoops def: No id!")
            end if
        end select
    case default
        call msg_fatal ("Process configuration: method '" &
            // char (method) // "' not implemented")
    end select
end associate
end subroutine dispatch_core_def

```

28.9.3 Process core allocation

Here we allocate an object of abstract type `prc_core_t` with a concrete type that matches a process definition. The `prc_omega_t` extension will require the current parameter set, so we take the opportunity to grab it from the model.

```

<Dispatch: public>+≡
    public :: dispatch_core

<Dispatch: procedures>+≡
    subroutine dispatch_core (core, core_def, model, &
        helicity_selection, qcd, use_color_factors)
        class(prc_core_t), allocatable, intent(inout) :: core
        class(prc_core_def_t), intent(in) :: core_def
        class(model_data_t), intent(in), target, optional :: model
        type(helicity_selection_t), intent(in), optional :: helicity_selection
        type(qcd_t), intent(in), optional :: qcd
        logical, intent(in), optional :: use_color_factors
        select type (core_def)
        type is (prc_test_def_t)
            allocate (test_t :: core)
        type is (template_me_def_t)
            allocate (prc_template_me_t :: core)
            select type (core)
            type is (prc_template_me_t)
                call core%set_parameters (model)
            end select
        class is (omega_def_t)
            if (.not. allocated (core)) allocate (prc_omega_t :: core)
            select type (core)
            type is (prc_omega_t)
                call core%set_parameters (model, &
                    helicity_selection, qcd, use_color_factors)
            end select
        type is (gosam_def_t)
            if (.not. allocated (core)) allocate (prc_gosam_t :: core)
            select type (core)
            type is (prc_gosam_t)
                call core%set_parameters (qcd, use_color_factors)
            end select
        type is (openloops_def_t)
            if (.not. allocated (core)) allocate (prc_openloops_t :: core)
            select type (core)
            type is (prc_openloops_t)
                call core%set_parameters (qcd, use_color_factors)
            end select
        class default
            call msg_bug ("Process core: unexpected process definition type")
        end select
    end subroutine dispatch_core

```

28.9.4 Process core update and restoration

Here we take an existing object of abstract type `prc_core_t` and update the parameters as given by the current state of `model`. Optionally, we can save the previous state as `saved_core`. The second routine restores the original from the save.

(In the test case, there is no possible update.)

<Dispatch: public>+≡

```
public :: dispatch_core_update
public :: dispatch_core_restore
```

<Dispatch: procedures>+≡

```
subroutine dispatch_core_update (core, model, helicity_selection, qcd, &
    saved_core)
    class(prc_core_t), allocatable, intent(inout) :: core
    class(model_data_t), intent(in), optional, target :: model
    type(helicity_selection_t), intent(in), optional :: helicity_selection
    type(qcd_t), intent(in), optional :: qcd
    class(prc_core_t), allocatable, intent(inout), optional :: saved_core
    if (present (saved_core)) then
        allocate (saved_core, source = core)
    end if
    select type (core)
    type is (test_t)
    type is (prc_omega_t)
        call core%set_parameters (model, helicity_selection, qcd)
        call core%activate_parameters ()
    type is (prc_gosam_t)
        call msg_message ("dispatch core restore: Gosam implementation not present yet!")
    class default
        call msg_bug ("Process core update: unexpected process definition type")
    end select
end subroutine dispatch_core_update

subroutine dispatch_core_restore (core, saved_core)
    class(prc_core_t), allocatable, intent(inout) :: core
    class(prc_core_t), allocatable, intent(inout) :: saved_core
    call move_alloc (from = saved_core, to = core)
    select type (core)
    type is (test_t)
    type is (prc_omega_t)
        call core%activate_parameters ()
    class default
        call msg_bug ("Process core restore: unexpected process definition type")
    end select
end subroutine dispatch_core_restore
```

28.9.5 Integrator allocation

Allocate an integrator according to the variable `$integration_method`.

<Dispatch: public>+≡

```
public :: dispatch_mci
```

<Dispatch: procedures>+≡

```

subroutine dispatch_mci (mci, global, process_id)
  class(mci_t), allocatable, intent(inout) :: mci
  type(rt_data_t), intent(in) :: global
  type(string_t), intent(in) :: process_id
  type(string_t) :: run_id
  type(string_t) :: integration_method
  type(grid_parameters_t) :: grid_par
  type(history_parameters_t) :: history_par
  logical :: rebuild_grids, check_grid_file, negative_weights, verbose
  integration_method = &
    global%var_list%get_sval (var_str ("integration_method"))
  select case (char (integration_method))
  case ("midpoint")
    allocate (mci_midpoint_t :: mci)
  case ("vamp", "default")
    associate (var_list => global%get_var_list_ptr ())
      grid_par%threshold_calls = &
        var_list%get_ival (var_str ("threshold_calls"))
      grid_par%min_calls_per_channel = &
        var_list%get_ival (var_str ("min_calls_per_channel"))
      grid_par%min_calls_per_bin = &
        var_list%get_ival (var_str ("min_calls_per_bin"))
      grid_par%min_bins = &
        var_list%get_ival (var_str ("min_bins"))
      grid_par%max_bins = &
        var_list%get_ival (var_str ("max_bins"))
      grid_par%stratified = &
        var_list%get_lval (var_str ("?stratified"))
      grid_par%use_vamp_equivalences = &
        var_list%get_lval (var_str ("?use_vamp_equivalences"))
      grid_par%channel_weights_power = &
        var_list%get_rval (var_str ("channel_weights_power"))
      grid_par%accuracy_goal = &
        var_list%get_rval (var_str ("accuracy_goal"))
      grid_par%error_goal = &
        var_list%get_rval (var_str ("error_goal"))
      grid_par%rel_error_goal = &
        var_list%get_rval (var_str ("relative_error_goal"))
      history_par%global = &
        var_list%get_lval (var_str ("?vamp_history_global"))
      history_par%global_verbose = &
        var_list%get_lval (var_str ("?vamp_history_global_verbose"))
      history_par%channel = &
        var_list%get_lval (var_str ("?vamp_history_channels"))
      history_par%channel_verbose = &
        var_list%get_lval (var_str ("?vamp_history_channels_verbose"))
      verbose = &
        var_list%get_lval (var_str ("?vamp_verbose"))
      check_grid_file = &
        var_list%get_lval (var_str ("?check_grid_file"))
      run_id = &
        var_list%get_sval (var_str ("run_id"))
      rebuild_grids = &

```

```

        var_list%get_lval (var_str ("?rebuild_grids"))
        negative_weights = &
        var_list%get_lval (var_str ("?negative_weights"))
    end associate
    allocate (mci_vamp_t :: mci)
    select type (mci)
    type is (mci_vamp_t)
        call mci%set_grid_parameters (grid_par)
        if (run_id /= "") then
            call mci%set_grid_filename (process_id, run_id)
        else
            call mci%set_grid_filename (process_id)
        end if
        call mci%set_history_parameters (history_par)
        call mci%set_rebuild_flag (rebuild_grids, check_grid_file)
        mci%negative_weights = negative_weights
        mci%verbose = verbose
    end select
    case default
        call msg_fatal ("Integrator '" &
            // char (integration_method) // "' not implemented")
    end select
end subroutine dispatch_mci

```

28.9.6 Phase-space allocation

Allocate a phase-space object according to the variable \$phs_method.

(Dispatch: public)+≡

```
public :: dispatch_phs
```

(Dispatch: procedures)+≡

```

subroutine dispatch_phs (phs, global, process_id, mapping_defaults, phs_par, &
    phs_method_in)
    class(phs_config_t), allocatable, intent(inout) :: phs
    type(rt_data_t), intent(in) :: global
    type(string_t), intent(in) :: process_id
    type(mapping_defaults_t), intent(in), optional :: mapping_defaults
    type(phs_parameters_t), intent(in), optional :: phs_par
    type(string_t), intent(in), optional :: phs_method_in
    type(string_t) :: phs_method, phs_file, run_id
    logical :: use_equivalences, vis_channels, fatal_beam_decay
    integer :: u_phs
    logical :: exist
    if (present (phs_method_in)) then
        phs_method = phs_method_in
    else
        phs_method = &
        global%var_list%get_sval (var_str ("$phs_method"))
    end if
    phs_file = &
        global%var_list%get_sval (var_str ("$phs_file"))
    use_equivalences = &
        global%var_list%get_lval (var_str ("?use_vamp_equivalences"))

```

```

vis_channels = &
    global%var_list%get_lval (var_str ("?vis_channels"))
fatal_beam_decay = &
    global%var_list%get_lval (var_str ("?fatal_beam_decay"))
run_id = &
    global%var_list%get_sval (var_str ("$run_id"))
select case (char (phs_method))
case ("single")
    allocate (phs_single_config_t :: phs)
    if (vis_channels) then
        call msg_warning ("Visualizing phase space channels not " // &
            "available for method 'single'.")
    end if
case ("fks")
    allocate (phs_fks_config_t :: phs)
case ("wood", "default")
    allocate (phs_wood_config_t :: phs)
    select type (phs)
    type is (phs_wood_config_t)
        if (phs_file /= "") then
            inquire (file = char (phs_file), exist = exist)
            if (exist) then
                call msg_message ("Phase space: reading configuration from '" &
                    // char (phs_file) // "'")
                u_phs = free_unit ()
                open (u_phs, file = char (phs_file), &
                    action = "read", status = "old")
                call phs%set_input (u_phs)
            else
                call msg_fatal ("Phase space: configuration file '" &
                    // char (phs_file) // "' not found")
            end if
        end if
    end if
    if (present (phs_par)) &
        call phs%set_parameters (phs_par)
    if (use_equivalences) &
        call phs%enable_equivalences ()
    if (present (mapping_defaults)) &
        call phs%set_mapping_defaults (mapping_defaults)
    phs%vis_channels = vis_channels
    phs%fatal_beam_decay = fatal_beam_decay
    phs%os_data = global%os_data
    phs%run_id = run_id
end select
case default
    call msg_fatal ("Phase space: parameterization method '" &
        // char (phs_method) // "' not implemented")
end select
end subroutine dispatch_phs

```

28.9.7 FKS parameter

Initialize parameters used to optimize FKS calculations.

```

<Dispatch: public>+≡
    public :: dispatch_fks

<Dispatch: procedures>+≡
    subroutine dispatch_fks (fks_template, global)
        type(fks_template_t), intent(inout) :: fks_template
        type(rt_data_t), intent(in) :: global
        real(default) :: fks_dij_exp1, fks_dij_exp2
        integer :: fks_mapping_type

        fks_dij_exp1 = &
            global%var_list%get_rval (var_str ("fks_dij_exp1"))
        fks_dij_exp2 = &
            global%var_list%get_rval (var_str ("fks_dij_exp2"))
        fks_mapping_type = &
            global%var_list%get_ival (var_str ("fks_mapping_type"))

        call fks_template%set_dij_exp (fks_dij_exp1, fks_dij_exp2)
        call fks_template%set_mapping_type (fks_mapping_type)

    end subroutine dispatch_fks

```

28.9.8 Random-number generator

Allocate a random-number generator factory according to the variable `$rng_method`, using the current seed in the global record. We take only the lower 15 bits of the seed, so the actual value fits into a positive 16-bit signed integer.

Since we want to guarantee that all random-number generators in a run are independent, we increment the global seed by one after creating the rng factory. If the user wants to have identical sequences, he can always set the seed manually, before it is used.

```

<Dispatch: public>+≡
    public :: dispatch_rng_factory

<Dispatch: procedures>+≡
    subroutine dispatch_rng_factory (rng_factory, global, local_input)
        class(rng_factory_t), allocatable, intent(inout) :: rng_factory
        type(rt_data_t), intent(inout), target :: global
        type(rt_data_t), intent(in), target, optional :: local_input
        type(rt_data_t), pointer :: local
        type(string_t) :: rng_method
        integer :: seed
        character(30) :: buffer
        integer(i16) :: s
        if (present (local_input)) then
            local => local_input
        else
            local => global
        end if
        rng_method = &
            local%var_list%get_sval (var_str ("$rng_method"))
        seed = &
            local%var_list%get_ival (var_str ("seed"))

```



```

s = int (mod (seed, 32768), i16)
select case (char (rng_method))
case ("unit_test")
    allocate (rng_test_factory_t :: rng_factory)
    call msg_message ("RNG: Initializing Test random-number generator")
case ("tao")
    allocate (rng_tao_factory_t :: rng_factory)
    call msg_message ("RNG: Initializing TAO random-number generator")
case default
    call msg_fatal ("Random-number generator '" &
        // char (rng_method) // "' not implemented")
end select
write (buffer, "(I0)") s
call msg_message ("RNG: Setting seed for random-number generator to " &
    // trim (buffer))
call rng_factory%init (s)
call var_list_set_int (global%var_list, var_str ("seed"), seed + 1, &
    is_known = .true.)
end subroutine dispatch_rng_factory

```

28.9.9 Structure function configuration data

This data type is a container for transferring structure-function specific data from the `dispatch_sf_data` to the `dispatch_sf_channels` subroutine.

```

<Dispatch: public>+≡
    public :: sf_prop_t

<Dispatch: types>≡
    type :: sf_prop_t
        real(default), dimension(2) :: isr_eps = 1
    end type sf_prop_t

```

Allocate a structure-function configuration object according to the `sf_method` string.

The `sf_prop` object can be used to transfer structure-function specific data up and to the `dispatch_sf_channels` subroutine below, so they can be used for particular mappings.

The `global` object is intent(inout) because the RNG generator seed may change during initialization.

The `pdg_in` array is the array of incoming flavors, corresponding to the upstream structure function or the beam array. This will be checked for the structure function in question and replaced by the outgoing flavors. The `pdg_prc` array is the array of incoming flavors (beam index, component index) for the hard process.

```

<Dispatch: public>+≡
    public :: dispatch_sf_data

<Dispatch: procedures>+≡
    subroutine dispatch_sf_data (data, sf_method, i_beam, sf_prop, global, &
        pdg_in, pdg_prc)
        class(sf_data_t), allocatable, intent(inout) :: data

```

```

type(string_t), intent(in) :: sf_method
integer, dimension(:), intent(in) :: i_beam
type(pdg_array_t), dimension(:), intent(inout) :: pdg_in
type(pdg_array_t), dimension(:,:), intent(in) :: pdg_prc
type(sf_prop_t), intent(inout) :: sf_prop
type(rt_data_t), intent(inout) :: global
type(model_t), pointer :: model
type(pdg_array_t), dimension(:), allocatable :: pdg_out
real(default) :: sqrts, isr_alpha, isr_q_max, isr_mass
integer :: isr_order
logical :: isr_recoil
real(default) :: epa_alpha, epa_x_min, epa_q_min, epa_e_max, epa_mass
logical :: epa_recoil
real(default) :: ewa_x_min, ewa_pt_max, ewa_mass
logical :: ewa_keep_momentum, ewa_keep_energy
type(pdg_array_t), dimension(:), allocatable :: pdg_prc1
integer :: ewa_id
type(string_t) :: pdf_name
type(string_t) :: lhpdf_dir, lhpdf_file
type(string_t), dimension(13) :: lhpdf_photon_sets
integer :: lhpdf_member, lhpdf_photon_scheme
logical :: hoppet_b_matching
class(rng_factory_t), allocatable :: rng_factory
logical :: circe1_photon1, circe1_photon2, circe1_generate, &
    circe1_with_radiation
real(default) :: circe1_sqrts, circe1_eps
integer :: circe1_version, circe1_chattiness, &
    circe1_revision
character(6) :: circe1_accelerator
logical :: circe2_polarized
type(string_t) :: circe2_design, circe2_file
logical :: beam_events_warn_eof
type(string_t) :: beam_events_dir, beam_events_file
logical :: escan_normalize
lhpdf_photon_sets = [var_str ("DOGO.LHgrid"), var_str ("DOG1.LHgrid"), &
    var_str ("DGG.LHgrid"), var_str ("LACG.LHgrid"), &
    var_str ("GSG0.LHgrid"), var_str ("GSG1.LHgrid"), &
    var_str ("GSG960.LHgrid"), var_str ("GSG961.LHgrid"), &
    var_str ("GRVG0.LHgrid"), var_str ("GRVG1.LHgrid"), &
    var_str ("ACFGPG.LHgrid"), var_str ("WHITG.LHgrid"), &
    var_str ("SASG.LHgrid")]
model => global%model
sqrts = global%get_sqrts ()
associate (var_list => global%get_var_list_ptr ())
    select case (char (sf_method))
    case ("sf_test_0", "sf_test_1")
        allocate (sf_test_data_t :: data)
        select type (data)
        type is (sf_test_data_t)
            select case (char (sf_method))
            case ("sf_test_0"); call data%init (model, pdg_in(i_beam(1)))
            case ("sf_test_1"); call data%init (model, pdg_in(i_beam(1)), &
                mode = 1)
            end select
        end select
    end associate

```

```

        end select
    case ("pdf_builtin")
        allocate (pdf_builtin_data_t :: data)
        select type (data)
        type is (pdf_builtin_data_t)
            pdf_name = &
                var_list%get_sval (var_str ("pdf_builtin_set"))
            hoppet_b_matching = &
                var_list%get_lval (var_str ("hoppet_b_matching"))
            call data%init ( &
                model, pdg_in(i_beam(1)), &
                name = pdf_name, &
                path = global%os_data%pdf_builtin_datapath, &
                hoppet_b_matching = hoppet_b_matching)
        end select
    case ("pdf_builtin_photon")
        call msg_fatal ("Currently, there are no photon PDFs built into WHIZARD,", &
            [var_str ("for the photon content inside a proton or neutron use"), &
            var_str ("the 'lhpdf_photon' structure function.")])
    case ("lhpdf")
        allocate (lhpdf_data_t :: data)
        if (pdg_array_get (pdg_in(i_beam(1)), 1) == PHOTON) then
            call msg_fatal ("The 'lhpdf' structure is intended only for protons and", &
                [var_str ("pions, please use 'lhpdf_photon' for photon beams.")])
        end if
        lhpdf_dir = &
            var_list%get_sval (var_str ("lhpdf_dir"))
        lhpdf_file = &
            var_list%get_sval (var_str ("lhpdf_file"))
        lhpdf_member = &
            var_list%get_ival (var_str ("lhpdf_member"))
        lhpdf_photon_scheme = &
            var_list%get_ival (var_str ("lhpdf_photon_scheme"))
        hoppet_b_matching = &
            var_list%get_lval (var_str ("hoppet_b_matching"))
        select type (data)
        type is (lhpdf_data_t)
            call data%init &
                (model, pdg_in(i_beam(1)), &
                lhpdf_dir, lhpdf_file, lhpdf_member, &
                lhpdf_photon_scheme, hoppet_b_matching)
        end select
    case ("lhpdf_photon")
        allocate (lhpdf_data_t :: data)
        if (pdg_array_get_length (pdg_in(i_beam(1))) /= 1 .or. &
            pdg_array_get (pdg_in(i_beam(1)), 1) /= PHOTON) then
            call msg_fatal ("The 'lhpdf_photon' structure function is exclusively for", &
                [var_str ("photon PDFs, i.e. for photons as beam particles")])
        end if
        lhpdf_dir = &
            var_list%get_sval (var_str ("lhpdf_dir"))
        lhpdf_file = &
            var_list%get_sval (var_str ("lhpdf_photon_file"))
        lhpdf_member = &

```

```

        var_list%get_ival (var_str ("lhpdf_member"))
lhpdf_photon_scheme = &
        var_list%get_ival (var_str ("lhpdf_photon_scheme"))
if (.not. any (lhpdf_photon_sets == lhpdf_file)) then
    call msg_fatal ("This PDF set is not supported or not " // &
        "intended for photon beams.")
end if
select type (data)
type is (lhpdf_data_t)
    call data%init &
        (model, pdg_in(i_beam(1)), &
        lhpdf_dir, lhpdf_file, lhpdf_member, &
        lhpdf_photon_scheme)
end select
case ("isr")
    allocate (isr_data_t :: data)
    isr_alpha = &
        var_list%get_rval (var_str ("isr_alpha"))
    if (vanishes (isr_alpha)) then
        isr_alpha = (var_list%get_rval (var_str ("ee"))) &
            ** 2 / (4 * PI)
    end if
    isr_q_max = &
        var_list%get_rval (var_str ("isr_q_max"))
    if (vanishes (isr_q_max)) then
        isr_q_max = sqrts
    end if
    isr_mass = var_list%get_rval (var_str ("isr_mass"))
    isr_order = var_list%get_ival (var_str ("isr_order"))
    isr_recoil = var_list%get_lval (var_str ("?isr_recoil"))
    select type (data)
    type is (isr_data_t)
        call data%init &
            (model, pdg_in (i_beam(1)), isr_alpha, isr_q_max, &
            isr_mass, isr_order, isr_recoil)
        call data%check ()
        sf_prop%isr_eps(i_beam(1)) = data%get_eps ()
    end select
case ("epa")
    allocate (epa_data_t :: data)
    epa_alpha = var_list%get_rval (var_str ("epa_alpha"))
    if (vanishes (epa_alpha)) then
        epa_alpha = (var_list%get_rval (var_str ("ee"))) &
            ** 2 / (4 * PI)
    end if
    epa_x_min = var_list%get_rval (var_str ("epa_x_min"))
    epa_q_min = var_list%get_rval (var_str ("epa_q_min"))
    epa_e_max = var_list%get_rval (var_str ("epa_e_max"))
    if (vanishes (epa_e_max)) then
        epa_e_max = sqrts
    end if
    epa_mass = var_list%get_rval (var_str ("epa_mass"))
    epa_recoil = var_list%get_lval (var_str ("?epa_recoil"))
    select type (data)

```

```

type is (epa_data_t)
  call data%init &
    (model, pdg_in (i_beam(1)), epa_alpha, epa_x_min, &
      epa_q_min, epa_e_max, epa_mass, epa_recoil)
  call data%check ()
end select
case ("ewa")
  allocate (ewa_data_t :: data)
  allocate (pdg_prc1 (size (pdg_prc, 2)))
  pdg_prc1 = pdg_prc(i_beam(1),:)
  if (any (pdg_array_get_length (pdg_prc1) /= 1) &
    .or. any (pdg_prc1 /= pdg_prc1(1))) then
    call msg_fatal &
      ("EWA: process incoming particle (W/Z) must be unique")
  end if
  ewa_id = abs (pdg_array_get (pdg_prc1(1), 1))
  ewa_x_min = var_list%get_rval (var_str ("ewa_x_min"))
  ewa_pt_max = var_list%get_rval (var_str ("ewa_pt_max"))
  if (vanishes (ewa_pt_max)) then
    ewa_pt_max = sqrts
  end if
  ewa_mass = var_list%get_rval (var_str ("ewa_mass"))
  ewa_keep_momentum = var_list%get_lval (&
    var_str ("?ewa_keep_momentum"))
  ewa_keep_energy = var_list%get_lval (&
    var_str ("?ewa_keep_energy"))
  if (ewa_keep_momentum .and. ewa_keep_energy) &
    call msg_fatal (" EWA cannot conserve both energy " &
      // "and momentum.")
  select type (data)
  type is (ewa_data_t)
    call data%init &
      (model, pdg_in (i_beam(1)), ewa_x_min, &
        ewa_pt_max, sqrts, ewa_keep_momentum, &
        ewa_keep_energy, ewa_mass)
    call data%set_id (ewa_id)
    call data%check ()
  end select
case ("circe1")
  allocate (circe1_data_t :: data)
  select type (data)
  type is (circe1_data_t)
    circe1_photon1 = &
      var_list%get_lval (var_str ("?circe1_photon1"))
    circe1_photon2 = &
      var_list%get_lval (var_str ("?circe1_photon2"))
    circe1_sqrts = &
      var_list%get_rval (var_str ("circe1_sqrts"))
    circe1_eps = &
      var_list%get_rval (var_str ("circe1_eps"))
    if (circe1_sqrts <= 0) circe1_sqrts = sqrts
    circe1_generate = &
      var_list%get_lval (var_str ("?circe1_generate"))
    circe1_version = &

```

```

        var_list%get_ival (var_str ("circe1_ver"))
circe1_revision = &
        var_list%get_ival (var_str ("circe1_rev"))
circe1_accelerator = &
        char (var_list%get_sval (var_str ("$circe1_acc")))
circe1_chattiness = &
        var_list%get_ival (var_str ("circe1_chat"))
circe1_with_radiation = &
        var_list%get_lval (var_str ("?circe1_with_radiation"))
call data%init (model, pdg_in, circe1_sqrts, circe1_eps, &
        [circe1_photon1, circe1_photon2], &
        circe1_version, circe1_revision, circe1_accelerator, &
        circe1_chattiness, circe1_with_radiation)
if (circe1_generate) then
    call msg_message ("Circe1: activating generator mode")
    call dispatch_rng_factory (rng_factory, global)
    call data%set_generator_mode (rng_factory)
end if
end select
case ("circe2")
    allocate (circe2_data_t :: data)
    select type (data)
    type is (circe2_data_t)
        circe2_polarized = &
            var_list%get_lval (var_str ("?circe2_polarized"))
        circe2_file = &
            var_list%get_sval (var_str ("$circe2_file"))
        circe2_design = &
            var_list%get_sval (var_str ("$circe2_design"))
        call data%init (global%os_data, model, pdg_in, sqrts, &
            circe2_polarized, circe2_file, circe2_design)
        call msg_message ("Circe2: activating generator mode")
        call dispatch_rng_factory (rng_factory, global)
        call data%set_generator_mode (rng_factory)
    end select
case ("beam_events")
    allocate (beam_events_data_t :: data)
    select type (data)
    type is (beam_events_data_t)
        beam_events_dir = global%os_data%whizard_beamsimpath
        beam_events_file = var_list%get_sval (&
            var_str ("$beam_events_file"))
        beam_events_warn_eof = var_list%get_lval (&
            var_str ("?beam_events_warn_eof"))
        call data%init (model, pdg_in, &
            beam_events_dir, beam_events_file, beam_events_warn_eof)
    end select
case ("energy_scan")
    escan_normalize = &
        var_list%get_lval (var_str ("?energy_scan_normalize"))
    allocate (escan_data_t :: data)
    select type (data)
    type is (escan_data_t)
        if (escan_normalize) then

```

```

        call data%init (model, pdg_in)
    else
        call data%init (model, pdg_in, sqrts)
    end if
end select
case default
    call msg_bug ("Structure function '" &
        // char (sf_method) // "' not implemented yet")
end select
end associate
if (allocated (data)) then
    allocate (pdg_out (size (pdg_prc, 1)))
    call data%get_pdg_out (pdg_out)
    pdg_in(i_beam) = pdg_out
end if
end subroutine dispatch_sf_data

```

This is an auxiliary procedure, used by the beam-structure expansion: tell for a given structure function name, whether it corresponds to a pair spectrum ($n = 2$), a single-particle structure function ($n = 1$), or nothing ($n = 0$). Though `energy_scan` can in principle also be a pair spectrum, it always has only one parameter.

(Dispatch: procedures) +≡

```

function strfun_mode (name) result (n)
    type(string_t), intent(in) :: name
    integer :: n
    select case (char (name))
    case ("none")
        n = 0
    case ("sf_test_0", "sf_test_1")
        n = 1
    case ("pdf_builtin", "pdf_builtin_photon", &
        "lhpdf", "lhpdf_photon")
        n = 1
    case ("isr", "epa", "ewa")
        n = 1
    case ("circe1", "circe2")
        n = 2
    case ("beam_events")
        n = 2
    case ("energy_scan")
        n = 2
    case default
        call msg_bug ("Structure function '" // char (name) &
            // "' not supported yet")
    end select
end function strfun_mode

```

Dispatch a whole structure-function chain, given beam data and beam structure data.

This could be done generically, but we should look at the specific combination of structure functions in order to select appropriate mappings.

The `beam_structure` argument gets copied because we want to expand it to canonical form (one valid structure-function entry per record) before proceeding further.

The `pdg_prc` argument is the array of incoming flavors. The first index is the beam index, the second one the process component index. Each element is itself a PDG array, notrivial if there is a flavor sum for the incoming state of this component.

The dispatcher is divided in two parts. The first part configures the structure function data themselves. After this, we can configure the phase space for the elementary process.

(Dispatch: public)+≡

```
public :: dispatch_sf_config
```

(Dispatch: procedures)+≡

```
subroutine dispatch_sf_config (sf_config, sf_prop, global, pdg_prc)
  type(sf_config_t), dimension(:), allocatable, intent(out) :: sf_config
  type(sf_prop_t), intent(out) :: sf_prop
  type(rt_data_t), intent(inout) :: global
  type(beam_structure_t) :: beam_structure
  class(sf_data_t), allocatable :: sf_data
  type(pdg_array_t), dimension(:,:), intent(in) :: pdg_prc
  type(string_t), dimension(:), allocatable :: prt_in
  type(pdg_array_t), dimension(:), allocatable :: pdg_in
  type(flavor_t) :: flv_in
  integer :: n_beam, n_record, i
  beam_structure = global%beam_structure
  call beam_structure%expand (strfun_mode)
  n_record = beam_structure%get_n_record ()
  allocate (sf_config (n_record))
  n_beam = beam_structure%get_n_beam ()
  if (n_beam > 0) then
    allocate (prt_in (n_beam), pdg_in (n_beam))
    prt_in = beam_structure%get_prt ()
    do i = 1, n_beam
      call flv_in%init (prt_in(i), global%model)
      pdg_in(i) = flv_in%get_pdg ()
    end do
  else
    n_beam = size (pdg_prc, 1)
    allocate (pdg_in (n_beam))
    pdg_in = pdg_prc(:,1)
  end if
  do i = 1, n_record
    call dispatch_sf_data (sf_data, &
      beam_structure%get_name (i), &
      beam_structure%get_i_entry (i), &
      sf_prop, global, pdg_in, pdg_prc)
    call sf_config(i)%init (beam_structure%get_i_entry (i), sf_data)
    deallocate (sf_data)
  end do
end subroutine dispatch_sf_config
```

The second part configures channel mappings, using some conditions from the

phase space configuration. If there are no structure functions, we enable a default setup with a single (dummy) structure-function channel. Otherwise, we look at the channel collection that we got from the phase-space configuration step. Each entry should be translated into an independent structure-function channel, where typically there is one default entry, which could be mapped using a standard s-channel mapping if the structure function setup recommends this, and other entries with s-channel resonances. The latter need to be translated into global mappings from the structure-function chain.

<Dispatch: public>+≡

public :: dispatch_sf_channels

<Dispatch: procedures>+≡

```
subroutine dispatch_sf_channels (sf_channel, sf_string, sf_prop, coll, global)
  type(sf_channel_t), dimension(:), allocatable, intent(out) :: sf_channel
  type(string_t), intent(out) :: sf_string
  type(sf_prop_t), intent(in) :: sf_prop
  type(phs_channel_collection_t), intent(in) :: coll
  type(rt_data_t), intent(in) :: global
  type(beam_structure_t) :: beam_structure
  class(channel_prop_t), allocatable :: prop
  integer :: n_strfun, n_sf_channel, i
  logical :: sf_allow_s_mapping, circe1_map, circe1_generate
  logical :: s_mapping_enable, endpoint_mapping, power_mapping
  integer, dimension(:), allocatable :: s_mapping, single_mapping
  real(default) :: sqrts, s_mapping_power
  real(default) :: circe1_mapping_slope, endpoint_mapping_slope
  real(default) :: power_mapping_eps
  sqrts = global%get_sqrts ()
  beam_structure = global%beam_structure
  call beam_structure%expand (strfun_mode)
  n_strfun = beam_structure%get_n_record ()
  sf_string = beam_structure%to_string (sf_only = .true.)
  sf_allow_s_mapping = &
    global%var_list%get_lval (var_str ("?sf_allow_s_mapping"))
  circe1_generate = &
    global%var_list%get_lval (var_str ("?circe1_generate"))
  circe1_map = &
    global%var_list%get_lval (var_str ("?circe1_map"))
  circe1_mapping_slope = &
    global%var_list%get_rval (var_str ("circe1_mapping_slope"))
  s_mapping_enable = .false.
  s_mapping_power = 1
  endpoint_mapping = .false.
  endpoint_mapping_slope = 1
  power_mapping = .false.
  select case (char (sf_string))
  case ("", "[any particles]")
  case ("pdf_builtin, none", &
    "pdf_builtin_photon, none", &
    "none, pdf_builtin", &
    "none, pdf_builtin_photon", &
    "lhpdf, none", &
    "lhpdf_photon, none", &
    "none, lhpdf", &
```

```

"none, lhpdf_photon")
case ("pdf_builtin, none => none, pdf_builtin", &
      "pdf_builtin, none => none, pdf_builtin_photon", &
      "pdf_builtin_photon, none => none, pdf_builtin", &
      "pdf_builtin_photon, none => none, pdf_builtin_photon", &
      "lhpdf, none => none, lhpdf", &
      "lhpdf, none => none, lhpdf_photon", &
      "lhpdf_photon, none => none, lhpdf", &
      "lhpdf_photon, none => none, lhpdf_photon")
  allocate (s_mapping (2), source = [1, 2])
  s_mapping_enable = .true.
  s_mapping_power = 2
case ("pdf_builtin, none => none, pdf_builtin => epa, none => none, epa", &
      "pdf_builtin, none => none, pdf_builtin => ewa, none => none, ewa", &
      "pdf_builtin, none => none, pdf_builtin => ewa, none => none, epa", &
      "pdf_builtin, none => none, pdf_builtin => epa, none => none, ewa")
  allocate (s_mapping (2), source = [1, 2])
  s_mapping_enable = .true.
  s_mapping_power = 2
case ("isr, none", &
      "none, isr")
  allocate (single_mapping (1), source = [1])
case ("isr, none => none, isr")
  allocate (s_mapping (2), source = [1, 2])
  power_mapping = .true.
  power_mapping_eps = minval (sf_prop%isr_eps)
case ("isr, none => none, isr => epa, none => none, epa", &
      "isr, none => none, isr => ewa, none => none, ewa", &
      "isr, none => none, isr => ewa, none => none, epa", &
      "isr, none => none, isr => epa, none => none, ewa")
  allocate (s_mapping (2), source = [1, 2])
  power_mapping = .true.
  power_mapping_eps = minval (sf_prop%isr_eps)
case ("circe1 => isr, none => none, isr => epa, none => none, epa", &
      "circe1 => isr, none => none, isr => ewa, none => none, ewa", &
      "circe1 => isr, none => none, isr => ewa, none => none, epa", &
      "circe1 => isr, none => none, isr => epa, none => none, ewa")
  if (circe1_generate) then
    allocate (s_mapping (2), source = [2, 3])
  else
    allocate (s_mapping (3), source = [1, 2, 3])
    endpoint_mapping = .true.
    endpoint_mapping_slope = circe1_mapping_slope
  end if
  power_mapping = .true.
  power_mapping_eps = minval (sf_prop%isr_eps)
case ("pdf_builtin, none => none, isr", &
      "pdf_builtin_photon, none => none, isr", &
      "lhpdf, none => none, isr", &
      "lhpdf_photon, none => none, isr")
  allocate (single_mapping (1), source = [2])
case ("isr, none => none, pdf_builtin", &
      "isr, none => none, pdf_builtin_photon", &
      "isr, none => none, lhpdf", &

```

```

        "isr, none => none, lhpdf_photon")
    allocate (single_mapping (1), source = [1])
case ("epa, none", &
      "none, epa")
    allocate (single_mapping (1), source = [1])
case ("epa, none => none, epa")
    allocate (single_mapping (2), source = [1, 2])
case ("epa, none => none, isr", &
      "isr, none => none, epa", &
      "ewa, none => none, isr", &
      "isr, none => none, ewa")
    allocate (single_mapping (2), source = [1, 2])
case ("pdf_builtin, none => none, epa", &
      "pdf_builtin_photon, none => none, epa", &
      "lhpdf, none => none, epa", &
      "lhpdf_photon, none => none, epa")
    allocate (single_mapping (1), source = [2])
case ("pdf_builtin, none => none, ewa", &
      "pdf_builtin_photon, none => none, ewa", &
      "lhpdf, none => none, ewa", &
      "lhpdf_photon, none => none, ewa")
    allocate (single_mapping (1), source = [2])
case ("epa, none => none, pdf_builtin", &
      "epa, none => none, pdf_builtin_photon", &
      "epa, none => none, lhpdf", &
      "epa, none => none, lhpdf_photon")
    allocate (single_mapping (1), source = [1])
case ("ewa, none => none, pdf_builtin", &
      "ewa, none => none, pdf_builtin_photon", &
      "ewa, none => none, lhpdf", &
      "ewa, none => none, lhpdf_photon")
    allocate (single_mapping (1), source = [1])
case ("ewa, none", &
      "none, ewa")
    allocate (single_mapping (1), source = [1])
case ("ewa, none => none, ewa")
    allocate (single_mapping (2), source = [1, 2])
case ("energy_scan, none => none, energy_scan")
    allocate (s_mapping (2), source = [1, 2])
case ("sf_test_1, none => none, sf_test_1")
    allocate (s_mapping (2), source = [1, 2])
case ("circe1")
    if (circe1_generate) then
        !!! no mapping
    else if (circe1_map) then
        allocate (s_mapping (1), source = [1])
        endpoint_mapping = .true.
        endpoint_mapping_slope = circe1_mapping_slope
    else
        allocate (s_mapping (1), source = [1])
        s_mapping_enable = .true.
    end if
case ("circe1 => isr, none => none, isr")
    if (circe1_generate) then

```

```

        allocate (s_mapping (2), source = [2, 3])
    else
        allocate (s_mapping (3), source = [1, 2, 3])
        endpoint_mapping = .true.
        endpoint_mapping_slope = circe1_mapping_slope
    end if
    power_mapping = .true.
    power_mapping_eps = minval (sf_prop%isr_eps)
case ("circe1 => isr, none", &
    "circe1 => none, isr")
    allocate (single_mapping (1), source = [2])
case ("circe1 => epa, none => none, epa")
    if (circe1_generate) then
        allocate (single_mapping (2), source = [2, 3])
    else
        call msg_fatal ("Circe/EPA: supported with ?circe1_generate=true &
            &only")
    end if
case ("circe1 => ewa, none => none, ewa")
    if (circe1_generate) then
        allocate (single_mapping (2), source = [2, 3])
    else
        call msg_fatal ("Circe/EWA: supported with ?circe1_generate=true &
            &only")
    end if
case ("circe1 => epa, none", &
    "circe1 => none, epa")
    if (circe1_generate) then
        allocate (single_mapping (1), source = [2])
    else
        call msg_fatal ("Circe/EPA: supported with ?circe1_generate=true &
            &only")
    end if
case ("circe1 => epa, none => none, isr", &
    "circe1 => isr, none => none, epa", &
    "circe1 => ewa, none => none, isr", &
    "circe1 => isr, none => none, ewa")
    if (circe1_generate) then
        allocate (single_mapping (2), source = [2, 3])
    else
        call msg_fatal ("Circe/EPA: supported with ?circe1_generate=true &
            &only")
    end if
case ("circe2", &
    "beam_events")
    !!! no mapping
case ("circe2 => isr, none => none, isr", &
    "beam_events => isr, none => none, isr")
    allocate (s_mapping (2), source = [2, 3])
    power_mapping = .true.
    power_mapping_eps = minval (sf_prop%isr_eps)
case ("circe2 => isr, none", &
    "circe2 => none, isr", &
    "beam_events => isr, none", &

```

```

        "beam_events => none, isr")
    allocate (single_mapping (1), source = [2])
case ("circe2 => epa, none => none, epa", &
    "beam_events => epa, none => none, epa")
    allocate (single_mapping (2), source = [2, 3])
case ("circe2 => epa, none", &
    "circe2 => none, epa", &
    "circe2 => ewa, none", &
    "circe2 => none, ewa", &
    "beam_events => epa, none", &
    "beam_events => none, epa", &
    "beam_events => ewa, none", &
    "beam_events => none, ewa")
    allocate (single_mapping (1), source = [2])
case ("circe2 => epa, none => none, isr", &
    "circe2 => isr, none => none, epa", &
    "circe2 => ewa, none => none, isr", &
    "circe2 => isr, none => none, ewa", &
    "beam_events => epa, none => none, isr", &
    "beam_events => isr, none => none, epa", &
    "beam_events => ewa, none => none, isr", &
    "beam_events => isr, none => none, ewa")
    allocate (single_mapping (2), source = [2, 3])
case ("energy_scan")
case default
    call msg_fatal ("Beam structure: " &
        // char (sf_string) // " not supported")
end select
if (sf_allow_s_mapping .and. coll%n > 0) then
    n_sf_channel = coll%n
    allocate (sf_channel (n_sf_channel))
    do i = 1, n_sf_channel
        call sf_channel(i)%init (n_strfun)
        if (allocated (single_mapping)) then
            call sf_channel(i)%activate_mapping (single_mapping)
        end if
        if (allocated (prop)) deallocate (prop)
        call coll%get_entry (i, prop)
        if (allocated (prop)) then
            if (endpoint_mapping .and. power_mapping) then
                select type (prop)
                type is (resonance_t)
                    call sf_channel(i)%set_eir_mapping (s_mapping, &
                        a = endpoint_mapping_slope, eps = power_mapping_eps, &
                        m = prop%mass / sqrts, w = prop%width / sqrts)
                type is (on_shell_t)
                    call sf_channel(i)%set_eio_mapping (s_mapping, &
                        a = endpoint_mapping_slope, eps = power_mapping_eps, &
                        m = prop%mass / sqrts)
                end select
            else if (endpoint_mapping) then
                select type (prop)
                type is (resonance_t)
                    call sf_channel(i)%set_epr_mapping (s_mapping, &

```

```

        a = endpoint_mapping_slope, &
        m = prop%mass / sqrts, w = prop%width / sqrts)
type is (on_shell_t)
    call sf_channel(i)%set_epo_mapping (s_mapping, &
        a = endpoint_mapping_slope, &
        m = prop%mass / sqrts)
end select
else if (power_mapping) then
    select type (prop)
    type is (resonance_t)
        call sf_channel(i)%set_ipr_mapping (s_mapping, &
            eps = power_mapping_eps, &
            m = prop%mass / sqrts, w = prop%width / sqrts)
    type is (on_shell_t)
        call sf_channel(i)%set_ipo_mapping (s_mapping, &
            eps = power_mapping_eps, &
            m = prop%mass / sqrts)
    end select
else if (allocated (s_mapping)) then
    select type (prop)
    type is (resonance_t)
        call sf_channel(i)%set_res_mapping (s_mapping, &
            m = prop%mass / sqrts, w = prop%width / sqrts)
    type is (on_shell_t)
        call sf_channel(i)%set_os_mapping (s_mapping, &
            m = prop%mass / sqrts)
    end select
else if (allocated (single_mapping)) then
    select type (prop)
    type is (resonance_t)
        call sf_channel(i)%set_res_mapping (single_mapping, &
            m = prop%mass / sqrts, w = prop%width / sqrts)
    type is (on_shell_t)
        call sf_channel(i)%set_os_mapping (single_mapping, &
            m = prop%mass / sqrts)
    end select
end if
else if (endpoint_mapping .and. power_mapping) then
    call sf_channel(i)%set_ei_mapping (s_mapping, &
        a = endpoint_mapping_slope, eps = power_mapping_eps)
else if (endpoint_mapping .and. .not. allocated (single_mapping)) then
    call sf_channel(i)%set_ep_mapping (s_mapping, &
        a = endpoint_mapping_slope)
else if (power_mapping .and. .not. allocated (single_mapping)) then
    call sf_channel(i)%set_ip_mapping (s_mapping, &
        eps = power_mapping_eps)
else if (s_mapping_enable .and. .not. allocated (single_mapping)) then
    call sf_channel(i)%set_s_mapping (s_mapping, &
        power = s_mapping_power)
end if
end do
else if (sf_allow_s_mapping) then
    allocate (sf_channel (1))
    call sf_channel(1)%init (n_strfun)

```

```

    if (allocated (single_mapping)) then
        call sf_channel(1)%activate_mapping (single_mapping)
    else if (endpoint_mapping .and. power_mapping) then
        call sf_channel(i)%set_ei_mapping (s_mapping, &
            a = endpoint_mapping_slope, eps = power_mapping_eps)
    else if (endpoint_mapping) then
        call sf_channel(1)%set_ep_mapping (s_mapping, &
            a = endpoint_mapping_slope)
    else if (power_mapping) then
        call sf_channel(1)%set_ip_mapping (s_mapping, &
            eps = power_mapping_eps)
    else if (s_mapping_enable) then
        call sf_channel(1)%set_s_mapping (s_mapping, &
            power = s_mapping_power)
    end if
else
    allocate (sf_channel (1))
    call sf_channel(1)%init (n_strfun)
    if (allocated (single_mapping)) then
        call sf_channel(1)%activate_mapping (single_mapping)
    end if
end if
end subroutine dispatch_sf_channels

```

28.9.10 Event I/O stream

```

<Dispatch: public>+≡
    public :: dispatch_eio

<Dispatch: procedures>+≡
    subroutine dispatch_eio (eio, method, global)
        class(eio_t), intent(inout), allocatable :: eio
        type(string_t), intent(in) :: method
        type(rt_data_t), intent(in) :: global
        logical :: check, keep_beams, keep_remnants, recover_beams
        logical :: use_alpha_s_from_file, use_scale_from_file
        logical :: write_sqme_prc, write_sqme_ref, write_sqme_alt
        type(string_t) :: lhef_version, lhef_extension, raw_version
        type(string_t) :: extension_default, debug_extension, extension_hepmc, &
            extension_lha, extension_hepevt, extension_ascii_short, &
            extension_ascii_long, extension_athena, extension_mokka, &
            extension_stdhep, extension_stdhep_up, extension_raw, &
            extension_hepevt_verb, extension_lha_verb, extension_lcio
        integer :: checkpoint
        logical :: show_process, show_transforms, show_decay, verbose, pacify
        select case (char (method))
        case ("raw")
            allocate (eio_raw_t :: eio)
            select type (eio)
            type is (eio_raw_t)
                check = &
                    global%var_list%get_lval (var_str ("?check_event_file"))
                raw_version = &

```

```

        global%var_list%get_sval (var_str ("sevent_file_version"))
extension_raw = &
        global%var_list%get_sval (var_str ("extension_raw"))
        call eio%set_parameters (check, raw_version, extension_raw)
end select
case ("checkpoint")
allocate (eio_checkpoints_t :: eio)
select type (eio)
type is (eio_checkpoints_t)
        checkpoint = &
                global%var_list%get_lval (var_str ("checkpoint"))
        pacify = &
                global%var_list%get_lval (var_str ("pacify"))
        call eio%set_parameters (checkpoint, blank = pacify)
end select
case ("lhef")
allocate (eio_lhef_t :: eio)
select type (eio)
type is (eio_lhef_t)
        keep_beams = &
                global%var_list%get_lval (var_str ("keep_beams"))
        keep_remnants = &
                global%var_list%get_lval (var_str ("keep_remnants"))
        recover_beams = &
                global%var_list%get_lval (var_str ("recover_beams"))
        use_alpha_s_from_file = &
                global%var_list%get_lval (var_str ("use_alpha_s_from_file"))
        use_scale_from_file = &
                global%var_list%get_lval (var_str ("use_scale_from_file"))
        lhef_version = &
                global%var_list%get_sval (var_str ("lhef_version"))
        lhef_extension = &
                global%var_list%get_sval (var_str ("lhef_extension"))
        write_sqme_prc = &
                global%var_list%get_lval (var_str ("lhef_write_sqme_prc"))
        write_sqme_ref = &
                global%var_list%get_lval (var_str ("lhef_write_sqme_ref"))
        write_sqme_alt = &
                global%var_list%get_lval (var_str ("lhef_write_sqme_alt"))
        call eio%set_parameters ( &
                keep_beams, keep_remnants, recover_beams, &
                use_alpha_s_from_file, use_scale_from_file, &
                char (lhef_version), lhef_extension, &
                write_sqme_ref, write_sqme_prc, write_sqme_alt)
end select
case ("hepmc")
allocate (eio_hepmc_t :: eio)
select type (eio)
type is (eio_hepmc_t)
        ! keep_beams = &
        !         global%var_list%get_lval (var_str ("keep_beams"))
        use_alpha_s_from_file = &
                global%var_list%get_lval (var_str ("use_alpha_s_from_file"))
        use_scale_from_file = &

```



```

        global%var_list%get_lval (var_str ("?use_scale_from_file"))
recover_beams = &
        global%var_list%get_lval (var_str ("?recover_beams"))
extension_hepmc = &
        global%var_list%get_sval (var_str ("$extension_hepmc"))
! call eio%set_parameters (keep_beams, recover_beams, extension_hepmc)
call eio%set_parameters (recover_beams, &
        use_alpha_s_from_file, use_scale_from_file, &
        extension_hepmc)
end select
case ("lcio")
allocate (eio_lcio_t :: eio)
select type (eio)
type is (eio_lcio_t)
! keep_beams = &
!         global%var_list%get_lval (var_str ("?keep_beams"))
use_alpha_s_from_file = &
        global%var_list%get_lval (var_str ("?use_alpha_s_from_file"))
use_scale_from_file = &
        global%var_list%get_lval (var_str ("?use_scale_from_file"))
recover_beams = &
        global%var_list%get_lval (var_str ("?recover_beams"))
extension_lcio = &
        global%var_list%get_sval (var_str ("$extension_lcio"))
! call eio%set_parameters &
!         (keep_beams, keep_remnants, recover_beams, extension_lcio)
call eio%set_parameters (recover_beams, &
        use_alpha_s_from_file, use_scale_from_file, &
        extension_lcio)
end select
case ("stdhep")
allocate (eio_stdhep_hepevt_t :: eio)
select type (eio)
type is (eio_stdhep_hepevt_t)
keep_beams = &
        global%var_list%get_lval (var_str ("?keep_beams"))
keep_remnants = &
        global%var_list%get_lval (var_str ("?keep_remnants"))
use_alpha_s_from_file = &
        global%var_list%get_lval (var_str ("?use_alpha_s_from_file"))
use_scale_from_file = &
        global%var_list%get_lval (var_str ("?use_scale_from_file"))
recover_beams = &
        global%var_list%get_lval (var_str ("?recover_beams"))
extension_stdhep = &
        global%var_list%get_sval (var_str ("$extension_stdhep"))
call eio%set_parameters &
        (keep_beams, keep_remnants, recover_beams, &
        use_alpha_s_from_file, use_scale_from_file, extension_stdhep)
end select
case ("stdhep_up")
allocate (eio_stdhep_hepeup_t :: eio)
select type (eio)
type is (eio_stdhep_hepeup_t)

```

```

keep_beams = &
    global%var_list%get_lval (var_str ("?keep_beams"))
keep_remnants = &
    global%var_list%get_lval (var_str ("?keep_remnants"))
use_alpha_s_from_file = &
    global%var_list%get_lval (var_str ("?use_alpha_s_from_file"))
use_scale_from_file = &
    global%var_list%get_lval (var_str ("?use_scale_from_file"))
recover_beams = &
    global%var_list%get_lval (var_str ("?recover_beams"))
extension_stdhep_up = &
    global%var_list%get_sval (var_str ("$extension_stdhep_up"))
call eio%set_parameters (keep_beams, keep_remnants, &
    recover_beams, use_alpha_s_from_file, &
    use_scale_from_file, extension_stdhep_up)
end select
case ("ascii")
    allocate (eio_ascii_ascii_t :: eio)
    select type (eio)
    type is (eio_ascii_ascii_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_default = &
            global%var_list%get_sval (var_str ("$extension_default"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_default)
    end select
case ("athena")
    allocate (eio_ascii_athena_t :: eio)
    select type (eio)
    type is (eio_ascii_athena_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_athena = &
            global%var_list%get_sval (var_str ("$extension_athena"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_athena)
    end select
case ("debug")
    allocate (eio_ascii_debug_t :: eio)
    select type (eio)
    type is (eio_ascii_debug_t)
        debug_extension = &
            global%var_list%get_sval (var_str ("$debug_extension"))
        show_process = &
            global%var_list%get_lval (var_str ("?debug_process"))
        show_transforms = &
            global%var_list%get_lval (var_str ("?debug_transforms"))
        show_decay = &
            global%var_list%get_lval (var_str ("?debug_decay"))

```

```

        verbose = &
        global%var_list%get_lval (var_str ("?debug_verbose"))
    call eio%set_parameters ( &
        extension = debug_extension, &
        show_process = show_process, &
        show_transforms = show_transforms, &
        show_decay = show_decay, &
        verbose = verbose)
    end select
case ("hepevt")
    allocate (eio_ascii_hepevt_t :: eio)
    select type (eio)
    type is (eio_ascii_hepevt_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_hepevt = &
            global%var_list%get_sval (var_str ("$extension_hepevt"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_hepevt)
    end select
case ("hepevt_verb")
    allocate (eio_ascii_hepevt_verb_t :: eio)
    select type (eio)
    type is (eio_ascii_hepevt_verb_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_hepevt_verb = &
            global%var_list%get_sval (var_str ("$extension_hepevt_verb"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_hepevt_verb)
    end select
case ("lha")
    allocate (eio_ascii_lha_t :: eio)
    select type (eio)
    type is (eio_ascii_lha_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_lha = &
            global%var_list%get_sval (var_str ("$extension_lha"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_lha)
    end select
case ("lha_verb")
    allocate (eio_ascii_lha_verb_t :: eio)
    select type (eio)
    type is (eio_ascii_lha_verb_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))

```

```

        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_lha_verb = global%var_list%get_sval ( &
            var_str ("$extension_lha_verb"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_lha_verb)
    end select
case ("long")
    allocate (eio_ascii_long_t :: eio)
    select type (eio)
    type is (eio_ascii_long_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_ascii_long = &
            global%var_list%get_sval (var_str ("$extension_ascii_long"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_ascii_long)
    end select
case ("mokka")
    allocate (eio_ascii_mokka_t :: eio)
    select type (eio)
    type is (eio_ascii_mokka_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_mokka = &
            global%var_list%get_sval (var_str ("$extension_mokka"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_mokka)
    end select
case ("short")
    allocate (eio_ascii_short_t :: eio)
    select type (eio)
    type is (eio_ascii_short_t)
        keep_beams = &
            global%var_list%get_lval (var_str ("?keep_beams"))
        keep_remnants = &
            global%var_list%get_lval (var_str ("?keep_remnants"))
        extension_ascii_short = &
            global%var_list%get_sval (var_str ("$extension_ascii_short"))
        call eio%set_parameters &
            (keep_beams, keep_remnants, extension_ascii_short)
    end select
case ("weight_stream")
    allocate (eio_weights_t :: eio)
    select type (eio)
    type is (eio_weights_t)
        pacify = &
            global%var_list%get_lval (var_str ("?pacify"))
        call eio%set_parameters (pacify = pacify)
    end select

```

```

case default
  call msg_fatal ("Event I/O method '" // char (method) &
    // "' not implemented")
end select
call eio%set_fallback_model (global%fallback_model)
end subroutine dispatch_eio

```

28.9.11 QCD coupling

Allocate the `alpha` (running coupling) component of the `qcd` block with a concrete implementation, depending on the variable settings in the `global` record.

If a fixed α_s is requested, we do not allocate the `qcd%alpha` object. In this case, the matrix element code will just take the model parameter as-is, which implies fixed α_s . If the object is allocated, the α_s value is computed and updated for each matrix-element call.

```

<Dispatch: public>+≡
  public :: dispatch_qcd

<Dispatch: procedures>+≡
  subroutine dispatch_qcd (qcd, global)
    type(qcd_t), intent(inout) :: qcd
    type(rt_data_t), intent(in), target :: global
    type(var_list_t), pointer :: var_list
    logical :: fixed, from_mz, from_pdf_builtin, from_lhapdf, from_lambda_qcd
    real(default) :: mz, alpha_val, lambda
    integer :: nf, order, lhpdf_member
    type(string_t) :: pdfset, lhpdf_dir, lhpdf_file
    var_list => global%get_var_list_ptr ()
    fixed = &
      var_list%get_lval (var_str ("?alpha_s_is_fixed"))
    from_mz = &
      var_list%get_lval (var_str ("?alpha_s_from_mz"))
    from_pdf_builtin = &
      var_list%get_lval (var_str ("?alpha_s_from_pdf_builtin"))
    from_lhapdf = &
      var_list%get_lval (var_str ("?alpha_s_from_lhapdf"))
    from_lambda_qcd = &
      var_list%get_lval (var_str ("?alpha_s_from_lambda_qcd"))
    pdfset = &
      var_list%get_sval (var_str ("pdf_builtin_set"))
    lambda = &
      var_list%get_rval (var_str ("lambda_qcd"))
    nf = &
      var_list%get_ival (var_str ("alpha_s_nf"))
    order = &
      var_list%get_ival (var_str ("alpha_s_order"))
    lhpdf_dir = &
      var_list%get_sval (var_str ("lhpdf_dir"))
    lhpdf_file = &
      var_list%get_sval (var_str ("lhpdf_file"))
    lhpdf_member = &
      var_list%get_ival (var_str ("lhpdf_member"))
  end subroutine dispatch_qcd

```

```

var_list => global%get_var_list_ptr ()
if (var_list%contains (var_str ("mZ"))) then
  mz = var_list%get_rval (var_str ("mZ"))
else
  mz = MZ_REF
end if
if (var_list%contains (var_str ("alphas"))) then
  alpha_val = var_list%get_rval (var_str ("alphas"))
else
  alpha_val = ALPHA_QCD_MZ_REF
end if
if (allocated (qcd%alpha)) deallocate (qcd%alpha)
if (from_lhapdf .and. from_pdf_builtin) then
  call msg_fatal (" Mixing alphas evolution", &
    [var_str (" from LHAPDF and builtin PDF is not permitted")])
end if
select case (count ([from_mz, from_pdf_builtin, from_lhapdf, from_lambda_qcd]))
case (0)
  if (fixed) then
    allocate (alpha_qcd_fixed_t :: qcd%alpha)
  else
    call msg_fatal ("QCD alpha: no calculation mode set")
  end if
case (2:)
  call msg_fatal ("QCD alpha: calculation mode is ambiguous")
case (1)
  if (fixed) then
    call msg_fatal ("QCD alpha: use '?alpha_s_is_fixed = false' for " // &
      "running alphas")
  else if (from_mz) then
    allocate (alpha_qcd_from_scale_t :: qcd%alpha)
  else if (from_pdf_builtin) then
    allocate (alpha_qcd_pdf_builtin_t :: qcd%alpha)
  else if (from_lhapdf) then
    allocate (alpha_qcd_lhapdf_t :: qcd%alpha)
  else if (from_lambda_qcd) then
    allocate (alpha_qcd_from_lambda_t :: qcd%alpha)
  end if
  call msg_message ("QCD alpha: using a running strong coupling")
end select
select type (alpha => qcd%alpha)
type is (alpha_qcd_fixed_t)
  alpha%val = alpha_val
type is (alpha_qcd_from_scale_t)
  alpha%mu_ref = mz
  alpha%ref = alpha_val
  alpha%order = order
  alpha%nf = nf
type is (alpha_qcd_from_lambda_t)
  alpha%lambda = lambda
  alpha%order = order
  alpha%nf = nf
type is (alpha_qcd_pdf_builtin_t)
  call alpha%init (pdfset, &

```

```

        global%os_data%pdf_builtin_datapath)
type is (alpha_qcd_lhapdf_t)
    call alpha%init (lhpdf_file, lhpdf_member, lhpdf_dir)
end select
end subroutine dispatch_qcd

```

28.9.12 Parton Shower

If POWHEG matching is switched on, transfer the specific settings to the corresponding variables.

```

<Dispatch: procedures>+≡
subroutine dispatch_powheg (powheg, global, process_name)
    type(powheg_t), intent(inout) :: powheg
    type(powheg_settings_t) :: settings
    type(rt_data_t), intent(in), target :: global
    type(string_t), intent(in) :: process_name
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    call settings%init (var_list)
    call powheg%init (settings, process_name)
end subroutine dispatch_powheg

```

28.9.13 Event Transform

An event transform is responsible for dressing a partonic event. Since event transforms are not mutually exclusive but are concatenated, we provide individual dispatchers for each of them.

```

<Dispatch: public>+≡
    public :: dispatch_evt_decay

<Dispatch: procedures>+≡
subroutine dispatch_evt_decay (evt, global)
    class(evt_t), intent(out), pointer :: evt
    type(rt_data_t), intent(in) :: global
    logical :: allow_decays
    allow_decays = &
        global%var_list%get_lval (var_str ("?allow_decays"))
    if (allow_decays) then
        allocate (evt_decay_t :: evt)
        call msg_message ("Simulate: activating decays")
    else
        evt => null ()
    end if
end subroutine dispatch_evt_decay

<Dispatch: public>+≡
    public :: dispatch_evt_shower

```

(Dispatch: procedures)+≡

```

subroutine dispatch_evt_shower (evt, rt_data, process)
  class(evt_t), intent(out), pointer :: evt
  type(rt_data_t), intent(in), target :: rt_data
  type(process_t), intent(in), optional, target :: process
  type(var_list_t), pointer :: var_list
  type(powheg_t) :: powheg
  type(string_t) :: lhpdf_file, lhpdf_dir, process_name
  integer :: lhpdf_member
  type(shower_settings_t) :: settings
  var_list => rt_data%get_var_list_ptr ()
  lhpdf_dir = &
    var_list%get_sval (var_str ("lhpdf_dir"))
  lhpdf_file = &
    var_list%get_sval (var_str ("lhpdf_file"))
  lhpdf_member = &
    var_list%get_ival (var_str ("lhpdf_member"))
  allocate (evt_shower_t :: evt)
  call msg_message ("Simulate: activating parton shower")
  call settings%init (var_list)
  if (present (process)) then
    process_name = process%get_id ()
    if (settings%powheg_matching) then
      call dispatch_powheg (powheg, rt_data, process_name)
    end if
  end if
  if (settings%mlm_matching .and. settings%ckkw_matching) then
    call msg_fatal ("Both MLM and CKKW matching activated," // &
      LF // "      aborting simulation")
  end if
  select type (evt)
  type is (evt_shower_t)
    call evt%init (settings, rt_data%fallback_model, rt_data%os_data, &
      powheg)
    if (settings%mlm_matching) then
      call msg_message ("Simulate: applying MLM matching")
      allocate (mlm_matching_settings_t :: evt%matching_settings)
      allocate (mlm_matching_data_t :: evt%data)
    end if
    if (settings%ckkw_matching) then
      call msg_warning ("Simulate: CKKW(-L) matching not yet supported")
      allocate (ckkw_matching_settings_t :: evt%matching_settings)
      allocate (ckkw_matching_data_t :: evt%data)
    end if
    if (allocated (evt%matching_settings)) &
      call evt%matching_settings%init (var_list)
    if (LHAPDF6_AVAILABLE) then
      call lhpdf_initialize &
        (1, lhpdf_dir, lhpdf_file, lhpdf_member, evt%pdf_data%pdf)
    end if
    if (present (process)) &
      call evt%setup_pdf &
        (process, rt_data%beam_structure, lhpdf_member)
  select case (evt%settings%method)

```



```

        case (PS_WHIZARD)
            allocate (shower_t :: evt%shower)
        case (PS_PYTHIA6)
            allocate (shower_pythia6_t :: evt%shower)
        case default
            call msg_fatal ('Shower: Method ' // &
                char (var_list%get_sval (var_str ("$shower_method")) // &
                'not implemented!')
            end select
            call evt%shower%init (evt%settings, evt%pdf_data)
        end select
    end subroutine dispatch_evt_shower

```

<Dispatch: public>+≡

```

    public :: dispatch_evt_hadrons

```

<Dispatch: procedures>+≡

```

    subroutine dispatch_evt_hadrons (evt, global, process)
        class(evt_t), intent(out), pointer :: evt
        type(rt_data_t), intent(in), target :: global
        type(process_t), intent(in), optional, target :: process
        type(string_t) :: method
        type(var_list_t), pointer :: var_list
        type(shower_settings_t) :: settings
        var_list => global%get_var_list_ptr ()
        method = &
            var_list%get_sval (var_str ("$hadronization_method"))
        allocate (evt_hadrons_t :: evt)
        call msg_message ("Simulate: activating hadronization")
        call settings%init (var_list)
        select type (evt)
            type is (evt_hadrons_t)
                call settings%init (var_list)
                call evt%init (settings, global%fallback_model, method)
            end select
    end subroutine dispatch_evt_hadrons

```

28.9.14 SLHA Interface

This is a container for the settings for the SLHA Interface

<Dispatch: public>+≡

```

    public :: dispatch_slha

```

<Dispatch: procedures>+≡

```

    subroutine dispatch_slha (global, input, spectrum, decays)
        type(rt_data_t), intent(inout), target :: global
        logical, intent(out) :: input, spectrum, decays
        input = &
            global%var_list%get_lval (var_str ("?slha_read_input"))
        spectrum = &
            global%var_list%get_lval (var_str ("?slha_read_spectrum"))
        decays = &
            global%var_list%get_lval (var_str ("?slha_read_decays"))
    end subroutine dispatch_slha

```

```
end subroutine dispatch_slha
```

28.9.15 Test

This is the master for calling self-test procedures.

```
<Dispatch: public>+≡
  public :: dispatch_test

<Dispatch: tests>≡
  subroutine dispatch_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Dispatch: execute tests>
  end subroutine dispatch_test
```

Select type: process definition

```
<Dispatch: execute tests>≡
  call test (dispatch_1, "dispatch_1", &
    "process configuration method", &
    u, results)

<Dispatch: tests>+≡
  subroutine dispatch_1 (u)
    integer, intent(in) :: u
    type(string_t), dimension(2) :: prt_in, prt_out
    type(rt_data_t), target :: global
    class(prc_core_def_t), allocatable :: core_def

    write (u, "(A)")  "* Test output: dispatch_1"
    write (u, "(A)")  "* Purpose: select process configuration method"
    write (u, "(A)")

    call global%global_init ()

    call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
      .false., is_known = .true.)

    prt_in = [var_str ("a"), var_str ("b")]
    prt_out = [var_str ("c"), var_str ("d")]

    write (u, "(A)")  "* Allocate core_def as prc_test_def"

    call var_list_set_string (global%var_list, var_str ("method"), &
      var_str ("unit_test"), is_known = .true.)
    call dispatch_core_def (core_def, prt_in, prt_out, global)
    select type (core_def)
      type is (prc_test_def_t)
        call core_def%write (u)
    end select

    deallocate (core_def)
```

```

write (u, "(A)")
write (u, "(A)")  "* Allocate core_def as omega_def"
write (u, "(A)")

call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("omega"), is_known = .true.)
call dispatch_core_def (core_def, prt_in, prt_out, global)
select type (core_def)
type is (omega_omega_def_t)
    call core_def%write (u)
end select

call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_1"

end subroutine dispatch_1

```

Select type: process core

```

<Dispatch: execute tests>+≡
    call test (dispatch_2, "dispatch_2", &
        "process core", &
        u, results)

<Dispatch: tests>+≡
    subroutine dispatch_2 (u)
        integer, intent(in) :: u
        type(string_t), dimension(2) :: prt_in, prt_out
        type(rt_data_t), target :: global
        class(prc_core_def_t), allocatable :: core_def
        class(prc_core_t), allocatable :: core

        write (u, "(A)")  "* Test output: dispatch_2"
        write (u, "(A)")  "*   Purpose: select process configuration method"
        write (u, "(A)")  "               and allocate process core"
        write (u, "(A)")

        call syntax_model_file_init ()
        call global%global_init ()

        prt_in = [var_str ("a"), var_str ("b")]
        prt_out = [var_str ("c"), var_str ("d")]

        write (u, "(A)")  "* Allocate core as test_t"
        write (u, "(A)")

        call var_list_set_string (global%var_list, var_str ("$method"), &
            var_str ("unit_test"), is_known = .true.)
        call dispatch_core_def (core_def, prt_in, prt_out, global)
        call dispatch_core (core, core_def)
    end subroutine dispatch_2

```

```

select type (core)
type is (test_t)
    call core%write (u)
end select

deallocate (core)
deallocate (core_def)

write (u, "(A)")
write (u, "(A)")  "* Allocate core as prc_omega_t"
write (u, "(A)")

call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("omega"), is_known = .true.)
call dispatch_core_def (core_def, prt_in, prt_out, global)

call global%select_model (var_str ("Test"))

call var_list_set_log (global%var_list, &
    var_str ("?helicity_selection_active"), &
    .true., is_known = .true.)
call var_list_set_real (global%var_list, &
    var_str ("helicity_selection_threshold"), &
    1e9_default, is_known = .true.)
call var_list_set_int (global%var_list, &
    var_str ("helicity_selection_cutoff"), &
    10, is_known = .true.)

call dispatch_core (core, core_def, &
    global%model, global%get_helicity_selection ())
call core_def%allocate_driver (core%driver, var_str (""))

select type (core)
type is (prc_omega_t)
    call core%write (u)
end select

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_2"

end subroutine dispatch_2

```

Select type: integrator core

```

<Dispatch: execute tests>+≡
    call test (dispatch_3, "dispatch_3", &
        "integration method", &
        u, results)
<Dispatch: tests>+≡

```

```

subroutine dispatch_3 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: global
  class(mci_t), allocatable :: mci
  type(string_t) :: process_id

  write (u, "(A)")  "* Test output: dispatch_3"
  write (u, "(A)")  "* Purpose: select integration method"
  write (u, "(A)")

  call global%global_init ()
  process_id = "dispatch_3"

  write (u, "(A)")  "* Allocate MCI as midpoint_t"
  write (u, "(A)")

  call var_list_set_string (global%var_list, &
    var_str ("integration_method"), &
    var_str ("midpoint"), is_known = .true.)
  call dispatch_mci (mci, global, process_id)
  select type (mci)
    type is (mci_midpoint_t)
      call mci%write (u)
  end select

  call mci%final ()
  deallocate (mci)

  write (u, "(A)")
  write (u, "(A)")  "* Allocate MCI as vamp_t"
  write (u, "(A)")

  call var_list_set_string (global%var_list, &
    var_str ("integration_method"), &
    var_str ("vamp"), is_known = .true.)
  call var_list_set_int (global%var_list, var_str ("threshold_calls"), &
    1, is_known = .true.)
  call var_list_set_int (global%var_list, var_str ("min_calls_per_channel"), &
    2, is_known = .true.)
  call var_list_set_int (global%var_list, var_str ("min_calls_per_bin"), &
    3, is_known = .true.)
  call var_list_set_int (global%var_list, var_str ("min_bins"), &
    4, is_known = .true.)
  call var_list_set_int (global%var_list, var_str ("max_bins"), &
    5, is_known = .true.)
  call var_list_set_log (global%var_list, var_str ("?stratified"), &
    .false., is_known = .true.)
  call var_list_set_log (global%var_list, var_str ("?use_vamp_equivalences"), &
    .false., is_known = .true.)
  call var_list_set_real (global%var_list, var_str ("channel_weights_power"), &
    4._default, is_known = .true.)
  call var_list_set_log (global%var_list, &
    var_str ("?vamp_history_global_verbose"), &
    .true., is_known = .true.)

```

```

call var_list_set_log (global%var_list, &
    var_str ("?vamp_history_channels"), &
    .true., is_known = .true.)
call var_list_set_log (global%var_list, &
    var_str ("?vamp_history_channels_verbose"), &
    .true., is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?stratified"), &
    .false., is_known = .true.)

call dispatch_mci (mci, global, process_id)
select type (mci)
type is (mci_vamp_t)
    call mci%write (u)
    call mci%write_history_parameters (u)
end select

call mci%final ()
deallocate (mci)

write (u, "(A)")
write (u, "(A)")  "* Allocate MCI as vamp_t, allow for negative weights"
write (u, "(A)")

call var_list_set_string (global%var_list, &
    var_str ("integration_method"), &
    var_str ("vamp"), is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?negative_weights"), &
    .true., is_known = .true.)

call dispatch_mci (mci, global, process_id)
select type (mci)
type is (mci_vamp_t)
    call mci%write (u)
    call mci%write_history_parameters (u)
end select

call mci%final ()
deallocate (mci)

call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_3"

end subroutine dispatch_3

```

Select type: phase-space configuration object

```

<Dispatch: execute tests>+≡
call test (dispatch_4, "dispatch_4", &
    "phase-space configuration", &
    u, results)

```

```

(Dispatch: tests)+≡
subroutine dispatch_4 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: global
  class(phs_config_t), allocatable :: phs
  type(phs_parameters_t) :: phs_par
  type(mapping_defaults_t) :: mapping_defs

  write (u, "(A)")  "* Test output: dispatch_4"
  write (u, "(A)")  "* Purpose: select phase-space configuration method"
  write (u, "(A)")

  call global%global_init ()

  write (u, "(A)")  "* Allocate PHS as phs_single_t"
  write (u, "(A)")

  call var_list_set_string (global%var_list, &
    var_str ("phs_method"), &
    var_str ("single"), is_known = .true.)
  call dispatch_phs (phs, global, var_str ("dispatch_4"))
  call phs%write (u)

  call phs%final ()
  deallocate (phs)

  write (u, "(A)")
  write (u, "(A)")  "* Allocate PHS as phs_wood_t"
  write (u, "(A)")

  call var_list_set_string (global%var_list, &
    var_str ("phs_method"), &
    var_str ("wood"), is_known = .true.)
  call dispatch_phs (phs, global, var_str ("dispatch_4"))
  call phs%write (u)

  call phs%final ()
  deallocate (phs)

  write (u, "(A)")
  write (u, "(A)")  "* Setting parameters for phs_wood_t"
  write (u, "(A)")

  phs_par%m_threshold_s = 123
  phs_par%m_threshold_t = 456
  phs_par%t_channel = 42
  phs_par%off_shell = 17
  phs_par%keep_nonresonant = .false.
  mapping_defs%energy_scale = 987
  mapping_defs%invariant_mass_scale = 654
  mapping_defs%momentum_transfer_scale = 321
  mapping_defs%step_mapping = .false.
  mapping_defs%step_mapping_exp = .false.
  mapping_defs%enable_s_mapping = .true.

```

```

call dispatch_phs (phs, global, var_str ("dispatch_4"), &
    mapping_defs, phs_par)
call phs%write (u)

call phs%final ()

call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_4"

end subroutine dispatch_4

```

Select type: random number generator

```

<Dispatch: execute tests>+≡
call test (dispatch_5, "dispatch_5", &
    "random-number generator", &
    u, results)

<Dispatch: tests>+≡
subroutine dispatch_5 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global
    class(rng_factory_t), allocatable :: rng_factory

    write (u, "(A)")  "* Test output: dispatch_5"
    write (u, "(A)")  "* Purpose: select random-number generator"
    write (u, "(A)")

    call global%global_init ()

    write (u, "(A)")  "* Allocate RNG factory as rng_test_factory_t"
    write (u, "(A)")

    call var_list_set_string (global%var_list, &
        var_str ("rng_method"), &
        var_str ("unit_test"), is_known = .true.)
    call var_list_set_int (global%var_list, &
        var_str ("seed"), 1, is_known = .true.)
    call dispatch_rng_factory (rng_factory, global)
    call rng_factory%write (u)
    deallocate (rng_factory)

    write (u, "(A)")
    write (u, "(A)")  "* Allocate RNG factory as rng_tao_factory_t"
    write (u, "(A)")

    call var_list_set_string (global%var_list, &
        var_str ("rng_method"), &
        var_str ("tao"), is_known = .true.)
    call dispatch_rng_factory (rng_factory, global)
    call rng_factory%write (u)

```



```

deallocate (rng_factory)

call global%final ()

write (u, "(A)")
write (u, "(A)")  "** Test output end: dispatch_5"

end subroutine dispatch_5

```

Phase-space configuration with file

```

<Dispatch: execute tests>+≡
  call test (dispatch_6, "dispatch_6", &
    "configure phase space using file", &
    u, results)

<Dispatch: tests>+≡
  subroutine dispatch_6 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global
    type(os_data_t) :: os_data
    type(process_constants_t) :: process_data
    class(phs_config_t), allocatable :: phs
    integer :: u_phs

    write (u, "(A)")  "** Test output: dispatch_6"
    write (u, "(A)")  "** Purpose: select 'wood' phase-space &
      &for a test process"
    write (u, "(A)")  "**           and read phs configuration from file"
    write (u, "(A)")

    write (u, "(A)")  "** Initialize a process"
    write (u, "(A)")

    call global%global_init ()

    call os_data_init (os_data)
    call syntax_model_file_init ()
    call global%select_model (var_str ("Test"))

    call syntax_phs_forest_init ()

    call init_test_process_data (var_str ("dispatch_6"), process_data)

    write (u, "(A)")  "** Write phase-space file"

    u_phs = free_unit ()
    open (u_phs, file = "dispatch_6.phs", action = "write", status = "replace")
    call write_test_phs_file (u_phs, var_str ("dispatch_6"))
    close (u_phs)

    write (u, "(A)")
    write (u, "(A)")  "** Allocate PHS as phs_wood_t"

```

```

write (u, "(A)")

call var_list_set_string (global%var_list, &
    var_str ("phs_method"), &
    var_str ("wood"), is_known = .true.)
call var_list_set_string (global%var_list, &
    var_str ("phs_file"), &
    var_str ("dispatch_6.phs"), is_known = .true.)
call dispatch_phs (phs, global, var_str ("dispatch_6"))

call phs%init (process_data, global%model)
call phs%configure (sqrts = 1000._default)

call phs%write (u)
write (u, "(A)")
select type (phs)
type is (phs_wood_config_t)
    call phs%write_forest (u)
end select

call phs%final ()

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_6"

end subroutine dispatch_6

```

Select type: structure-function data

```

<Dispatch: execute tests>+≡
call test (dispatch_7, "dispatch_7", &
    "structure-function data", &
    u, results)

<Dispatch: tests>+≡
subroutine dispatch_7 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global
    type(os_data_t) :: os_data
    type(string_t) :: prt, sf_method
    type(sf_prop_t) :: sf_prop
    class(sf_data_t), allocatable :: data
    type(pdg_array_t), dimension(1) :: pdg_in
    type(pdg_array_t), dimension(1,1) :: pdg_prc
    type(pdg_array_t), dimension(1) :: pdg_out
    integer, dimension(:), allocatable :: pdg1

    write (u, "(A)")  "* Test output: dispatch_7"
    write (u, "(A)")  "* Purpose: select and configure &
        &structure function data"

```

```

write (u, "(A)")

call global%global_init ()

call os_data_init (os_data)
call syntax_model_file_init ()
call global%select_model (var_str ("QCD"))

call reset_interaction_counter ()
call var_list_set_real (global%var_list, var_str ("sqrts"), &
    14000._default, is_known = .true.)
prt = "p"
call global%beam_structure%init_sf ([prt, prt], [1])
pdg_in = 2212

write (u, "(A)")  "* Allocate data as sf_pdf_builtin_t"
write (u, "(A)")

sf_method = "pdf_builtin"
call dispatch_sf_data &
    (data, sf_method, [1], sf_prop, global, pdg_in, pdg_prc)
call data%write (u)

call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(A)")
write (u, "(1x,A,99(1x,I0))")  "PDG(out) = ", pdg1

deallocate (data)

write (u, "(A)")
write (u, "(A)")  "* Allocate data for different PDF set"
write (u, "(A)")

pdg_in = 2212

call var_list_set_string (global%var_list, var_str ("pdf_builtin_set"), &
    var_str ("CTEQ6M"), is_known = .true.)
sf_method = "pdf_builtin"
call dispatch_sf_data &
    (data, sf_method, [1], sf_prop, global, pdg_in, pdg_prc)
call data%write (u)

call data%get_pdg_out (pdg_out)
pdg1 = pdg_out(1)
write (u, "(A)")
write (u, "(1x,A,99(1x,I0))")  "PDG(out) = ", pdg1

deallocate (data)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")

```

```

write (u, "(A)")  "* Test output end: dispatch_7"

end subroutine dispatch_7

```

Beam structure

```

<Dispatch: execute tests>+≡
  call test (dispatch_8, "dispatch_8", &
    "beam structure", &
    u, results)

<Dispatch: tests>+≡
  subroutine dispatch_8 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global
    type(os_data_t) :: os_data
    type(flavor_t), dimension(2) :: flv
    type(sf_config_t), dimension(:), allocatable :: sf_config
    type(sf_prop_t) :: sf_prop
    type(sf_channel_t), dimension(:), allocatable :: sf_channel
    type(phs_channel_collection_t) :: coll
    type(string_t) :: sf_string
    integer :: i
    type(pdg_array_t), dimension (2,1) :: pdg_prc

    write (u, "(A)")  "* Test output: dispatch_8"
    write (u, "(A)")  "* Purpose: configure a structure-function chain"
    write (u, "(A)")

    call global%global_init ()

    call os_data_init (os_data)
    call syntax_model_file_init ()
    call global%select_model (var_str ("QCD"))

    write (u, "(A)")  "* Allocate LHC beams with PDF builtin"
    write (u, "(A)")

    call flv(1)%init (PROTON, global%model)
    call flv(2)%init (PROTON, global%model)

    call reset_interaction_counter ()
    call var_list_set_real (global%var_list, var_str ("sqrts"), &
      14000._default, is_known = .true.)

    call global%beam_structure%init_sf (flv%get_name (), [1])
    call global%beam_structure%set_sf (1, 1, var_str ("pdf_builtin"))

    call dispatch_sf_config (sf_config, sf_prop, global, pdg_prc)
    do i = 1, size (sf_config)
      call sf_config(i)%write (u)
    end do

```

```

call dispatch_sf_channels (sf_channel, sf_string, sf_prop, coll, global)
write (u, "(1x,A)") "Mapping configuration:"
do i = 1, size (sf_channel)
    write (u, "(2x)", advance = "no")
    call sf_channel(i)%write (u)
end do

write (u, "(A)")
write (u, "(A)")  "* Allocate ILC beams with CIRCE1"
write (u, "(A)")

call global%select_model (var_str ("QED"))
call flv(1)%init ( ELECTRON, global%model)
call flv(2)%init (-ELECTRON, global%model)

call reset_interaction_counter ()
call var_list_set_real (global%var_list, var_str ("sqrts"), &
    500._default, is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?circe1_generate"), &
    .false., is_known = .true.)

call global%beam_structure%init_sf (flv%get_name (), [1])
call global%beam_structure%set_sf (1, 1, var_str ("circe1"))

call dispatch_sf_config (sf_config, sf_prop, global, pdg_prc)
do i = 1, size (sf_config)
    call sf_config(i)%write (u)
end do

call dispatch_sf_channels (sf_channel, sf_string, sf_prop, coll, global)
write (u, "(1x,A)") "Mapping configuration:"
do i = 1, size (sf_channel)
    write (u, "(2x)", advance = "no")
    call sf_channel(i)%write (u)
end do

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_8"

end subroutine dispatch_8

```

Event I/O

```

<Dispatch: execute tests>+≡
call test (dispatch_9, "dispatch_9", &
    "event I/O", &
    u, results)

```

```

<Dispatch: tests>+≡
subroutine dispatch_9 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: global
  class(eio_t), allocatable :: eio

  write (u, "(A)")  "* Test output: dispatch_9"
  write (u, "(A)")  "* Purpose: allocate an event I/O (eio) stream"
  write (u, "(A)")

  call syntax_model_file_init ()
  call global%global_init ()
  call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

  write (u, "(A)")  "* Allocate as raw"
  write (u, "(A)")

  call dispatch_eio (eio, var_str ("raw"), global)

  call eio%write (u)

  call eio%final ()
  deallocate (eio)

  write (u, "(A)")
  write (u, "(A)")  "* Allocate as checkpoints:"
  write (u, "(A)")

  call dispatch_eio (eio, var_str ("checkpoint"), global)

  call eio%write (u)

  call eio%final ()
  deallocate (eio)

  write (u, "(A)")
  write (u, "(A)")  "* Allocate as LHEF:"
  write (u, "(A)")

  call var_list_set_string (global%var_list, var_str ("lhef_extension"), &
    var_str ("lhe_custom"), is_known = .true.)
  call dispatch_eio (eio, var_str ("lhef"), global)

  call eio%write (u)

  call eio%final ()
  deallocate (eio)

  write (u, "(A)")
  write (u, "(A)")  "* Allocate as HepMC:"
  write (u, "(A)")

  call dispatch_eio (eio, var_str ("hepmc"), global)

```

```

call eio%write (u)

call eio%final ()
deallocate (eio)

write (u, "(A)")
write (u, "(A)")  "* Allocate as weight_stream"
write (u, "(A)")

call dispatch_eio (eio, var_str ("weight_stream"), global)

call eio%write (u)

call eio%final ()
deallocate (eio)

write (u, "(A)")
write (u, "(A)")  "* Allocate as debug format"
write (u, "(A)")

call var_list_set_log (global%var_list, var_str ("?debug_verbose"), &
    .false., is_known = .true.)
call dispatch_eio (eio, var_str ("debug"), global)

call eio%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()
call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_9"

end subroutine dispatch_9

```

Update process core parameters

This test dispatches a process core, temporarily modifies parameters, then restores the original.

```

<Dispatch: execute tests>+≡
    call test (dispatch_10, "dispatch_10", &
        "process core update", &
        u, results)

<Dispatch: tests>+≡
    subroutine dispatch_10 (u)
        integer, intent(in) :: u
        type(string_t), dimension(2) :: prt_in, prt_out
        type(rt_data_t), target :: global

```

```

class(prc_core_def_t), allocatable :: core_def
class(prc_core_t), allocatable :: core, saved_core
type(var_list_t), pointer :: var_list

write (u, "(A)")  "* Test output: dispatch_10"
write (u, "(A)")  "*   Purpose: select process configuration method,"
write (u, "(A)")  "           allocate process core,"
write (u, "(A)")  "           temporarily reset parameters"
write (u, "(A)")

call syntax_model_file_init ()
call global%global_init ()

prt_in = [var_str ("a"), var_str ("b")]
prt_out = [var_str ("c"), var_str ("d")]

write (u, "(A)")  "* Allocate core as prc_omega_t"
write (u, "(A)")

call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("omega"), is_known = .true.)
call dispatch_core_def (core_def, prt_in, prt_out, global)

call global%select_model (var_str ("Test"))

call dispatch_core (core, core_def, global%model)
call core_def%allocate_driver (core%driver, var_str (""))

select type (core)
type is (prc_omega_t)
    call core%write (u)
end select

write (u, "(A)")
write (u, "(A)")  "* Update core with modified model and helicity selection"
write (u, "(A)")

var_list => global%get_var_list_ptr ()
call var_list_set_real (var_list, var_str ("gy"), 2._default, &
    is_known = .true.)
call global%model%update_parameters ()

call var_list_set_log (global%var_list, &
    var_str ("?helicity_selection_active"), &
    .true., is_known = .true.)
call var_list_set_real (global%var_list, &
    var_str ("helicity_selection_threshold"), &
    2e10_default, is_known = .true.)
call var_list_set_int (global%var_list, &
    var_str ("helicity_selection_cutoff"), &
    5, is_known = .true.)

call dispatch_core_update (core, global%model, &
    global%get_helicity_selection (), &

```



```

        saved_core = saved_core)
select type (core)
type is (prc_omega_t)
    call core%write (u)
end select

write (u, "(A)")
write (u, "(A)")  "* Restore core from save"
write (u, "(A)")

call dispatch_core_restore (core, saved_core)
select type (core)
type is (prc_omega_t)
    call core%write (u)
end select

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_10"

end subroutine dispatch_10

```

QCD Coupling

This test dispatches an qcd object, which is used to compute the (running) coupling by one of several possible methods.

```

<Dispatch: execute tests>+≡
    call test (dispatch_11, "dispatch_11", &
        "QCD coupling", &
        u, results)

<Dispatch: tests>+≡
    subroutine dispatch_11 (u)
        integer, intent(in) :: u
        type(rt_data_t), target :: global
        type(qcd_t) :: qcd
        type(var_list_t), pointer :: model_vars

        write (u, "(A)")  "* Test output: dispatch_11"
        write (u, "(A)")  "* Purpose: select QCD coupling formula"
        write (u, "(A)")

        call syntax_model_file_init ()
        call global%global_init ()
        call global%select_model (var_str ("SM"))
        model_vars => global%get_var_list_ptr ()

        write (u, "(A)")  "* Allocate alpha_s as fixed"
        write (u, "(A)")

        call var_list_set_log (global%var_list, var_str ("?alpha_s_is_fixed"), &

```

```

        .true., is_known = .true.)
call dispatch_qcd (qcd, global)
call qcd%write (u)

write (u, "(A)")
write (u, "(A)")  "* Allocate alpha_s as running (built-in)"
write (u, "(A)")

call var_list_set_log (global%var_list, var_str ("?alpha_s_is_fixed"), &
    .false., is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?alpha_s_from_mz"), &
    .true., is_known = .true.)
call var_list_set_int &
    (global%var_list, var_str ("alpha_s_order"), 1, is_known = .true.)
call var_list_set_real &
    (model_vars, var_str ("alphas"), 0.1234_default, &
    is_known=.true.)
call var_list_set_real &
    (model_vars, var_str ("mZ"), 91.234_default, &
    is_known=.true.)
call dispatch_qcd (qcd, global)
call qcd%write (u)

write (u, "(A)")
write (u, "(A)")  "* Allocate alpha_s as running (built-in, Lambda defined)"
write (u, "(A)")

call var_list_set_log (global%var_list, var_str ("?alpha_s_from_mz"), &
    .false., is_known = .true.)
call var_list_set_log (global%var_list, &
    var_str ("?alpha_s_from_lambda_qcd"), &
    .true., is_known = .true.)
call var_list_set_real &
    (global%var_list, var_str ("lambda_qcd"), 250.e-3_default, &
    is_known=.true.)
call var_list_set_int &
    (global%var_list, var_str ("alpha_s_order"), 2, is_known = .true.)
call var_list_set_int &
    (global%var_list, var_str ("alpha_s_nf"), 4, is_known = .true.)
call dispatch_qcd (qcd, global)
call qcd%write (u)

write (u, "(A)")
write (u, "(A)")  "* Allocate alpha_s as running (using builtin PDF set)"
write (u, "(A)")

call var_list_set_log (global%var_list, &
    var_str ("?alpha_s_from_lambda_qcd"), &
    .false., is_known = .true.)
call var_list_set_log &
    (global%var_list, var_str ("?alpha_s_from_pdf_builtin"), &
    .true., is_known = .true.)
call dispatch_qcd (qcd, global)
call qcd%write (u)

```

```

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_11"

end subroutine dispatch_11

```

Shower settings

This test dispatches an `shower_settings` object, which is used to steer the initial and final state.

```

<Dispatch: execute tests>+≡
  call test (dispatch_12, "dispatch_12", &
    "Shower settings", &
    u, results)

<Dispatch: tests>+≡
  subroutine dispatch_12 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global
    type(var_list_t), pointer :: var_list
    type(shower_settings_t) :: shower_settings

    write (u, "(A)")  "* Test output: dispatch_12"
    write (u, "(A)")  "* Purpose: setting ISR/FSR shower"
    write (u, "(A)")

    write (u, "(A)")  "* Default settings"
    write (u, "(A)")

    call global%global_init ()
    call var_list_set_log (global%var_list, var_str ("?alpha_s_is_fixed"), &
      .true., is_known = .true.)
    var_list => global%get_var_list_ptr ()
    call shower_settings%init (var_list)
    call write_separator (u)
    call shower_settings%write (u)
    call write_separator (u)

    write (u, "(A)")
    write (u, "(A)")  "* Switch on ISR/FSR showers, hadronization"
    write (u, "(A)")  "      and MLM matching"
    write (u, "(A)")

    call var_list_set_string (global%var_list, var_str ("$shower_method"), &
      var_str ("PYTHIA6"), is_known = .true.)
    call var_list_set_log (global%var_list, var_str ("?ps_fsr_active"), &
      .true., is_known = .true.)
    call var_list_set_log (global%var_list, var_str ("?ps_isr_active"), &
      .true., is_known = .true.)
    call var_list_set_log (global%var_list, var_str ("?hadronization_active"), &

```

```

        .true., is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?mlm_matching"), &
    .true., is_known = .true.)
call var_list_set_int &
    (global%var_list, var_str ("ps_max_n_flavors"), 4, is_known = .true.)
call var_list_set_real &
    (global%var_list, var_str ("ps_isr_z_cutoff"), 0.1234_default, &
    is_known=.true.)
call var_list_set_real (global%var_list, &
    var_str ("mlm_etamax"), 3.456_default, is_known=.true.)
call var_list_set_string (global%var_list, &
    var_str ("ps_PYTHIA_PYGIVE"), var_str ("abcdefgh"), is_known=.true.)
call shower_settings%init (var_list)
call write_separator (u)
call shower_settings%write (u)
call write_separator (u)

call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_12"

end subroutine dispatch_12

```

Event transforms

This test dispatches an `evt` (event transform) object. Currently, the only non-trivial transform is the partonic decay chain..

```

<Dispatch: execute tests>+≡
    call test (dispatch_13, "dispatch_13", &
        "event transforms", &
        u, results)

<Dispatch: tests>+≡
subroutine dispatch_13 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global
    class(evt_t), pointer :: evt
    type(var_list_t), pointer :: model_vars

    write (u, "(A)")  "* Test output: dispatch_13"
    write (u, "(A)")  "* Purpose: configure event transform"
    write (u, "(A)")

    call syntax_model_file_init ()
    call global%global_init ()
    call global%init_fallback_model &
        (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))
    model_vars => global%get_var_list_ptr ()

    write (u, "(A)")  "* Partonic decays"
    write (u, "(A)")

```

```

call dispatch_evt_decay (evt, global)
call evt%write (u, verbose = .true., more_verbose = .true.)

call evt%final ()
deallocate (evt)

write (u, "(A)")
write (u, "(A)")  "* Shower"
write (u, "(A)")

call var_list_set_log (global%var_list, var_str ("?allow_shower"), .true., &
    is_known = .true.)
call var_list_set_string (global%var_list, var_str ("$shower_method"), &
    var_str ("WHIZARD"), is_known = .true.)
call dispatch_evt_shower (evt, global)
call evt%write (u)
call write_separator (u, 2)

call evt%final ()
deallocate (evt)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_13"

end subroutine dispatch_13

```

SLHA interface

This rather trivial sets all input values for the SLHA interface to false.

```

<Dispatch: execute tests>+≡
    call test (dispatch_14, "dispatch_14", &
        "SLHA interface", &
        u, results)

<Dispatch: tests>+≡
    subroutine dispatch_14 (u)
        integer, intent(in) :: u
        type(rt_data_t), target :: global
        logical :: input, spectrum, decays

        write (u, "(A)")  "* Test output: dispatch_14"
        write (u, "(A)")  "* Purpose: SLHA interface settings"
        write (u, "(A)")

        write (u, "(A)")  "* Default settings"
        write (u, "(A)")

        call global%global_init ()
        call dispatch_slha (global, &
            input = input, spectrum = spectrum, decays = decays)
    end subroutine dispatch_14

```

```

write (u, "(A,1x,L1)" " slha_read_input      =", input
write (u, "(A,1x,L1)" " slha_read_spectrum   =", spectrum
write (u, "(A,1x,L1)" " slha_read_decays     =", decays

call global%final ()
call global%global_init ()

write (u, "(A)")
write (u, "(A)")  "* Set all entries to [false]"
write (u, "(A)")

call var_list_set_log (global%var_list, var_str ("?slha_read_input"), &
    .false., is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?slha_read_spectrum"), &
    .false., is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?slha_read_decays"), &
    .false., is_known = .true.)

call dispatch_slha (global, &
    input = input, spectrum = spectrum, decays = decays)

write (u, "(A,1x,L1)" " slha_read_input      =", input
write (u, "(A,1x,L1)" " slha_read_spectrum   =", spectrum
write (u, "(A,1x,L1)" " slha_read_decays     =", decays

call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: dispatch_14"

end subroutine dispatch_14

```

28.10 Process Configuration

This module communicates between the toplevel command structure with its runtime data set and the process-library handling modules which collect the definition of individual processes. Its primary purpose is to select from the available matrix-element generating methods and configure the entry in the process library accordingly.

```
<process_configurations.f90>≡
  <File header>

  module process_configurations

    <Use strings>
    use unit_tests
    use diagnostics

    use variables
    use models
    use prc_core_def
    use particle_specifiers
    use process_libraries
    use prclib_stacks
    use prc_test
    use prc_omega
    use rt_data
    use dispatch

    use prc_gosam

    <Standard module head>

    <Process configurations: public>

    <Process configurations: types>

    contains

    <Process configurations: procedures>

    <Process configurations: tests>

  end module process_configurations
```

28.10.1 Data Type

```
<Process configurations: public>≡
  public :: process_configuration_t

<Process configurations: types>≡
  type :: process_configuration_t
    type(process_def_entry_t), pointer :: entry => null ()
    type(string_t) :: id
    integer :: num_id = 0
  contains
```

```

    <Process configurations: process configuration: TBP>
end type process_configuration_t

```

Initialize a process. We only need the name, the number of incoming particles, and the number of components.

```

<Process configurations: process configuration: TBP>≡
    procedure :: init => process_configuration_init

<Process configurations: procedures>≡
    subroutine process_configuration_init &
        (config, prc_name, n_in, n_components, global)
    class(process_configuration_t), intent(out) :: config
    type(string_t), intent(in) :: prc_name
    integer, intent(in) :: n_in
    integer, intent(in) :: n_components
    type(rt_data_t), intent(in) :: global
    type(model_t), pointer :: model
    model => global%model
    config%id = prc_name
    allocate (config%entry)
    if (global%var_list%is_known (var_str ("process_num_id"))) then
        config%num_id = &
            global%var_list%get_ival (var_str ("process_num_id"))
        call config%entry%init (prc_name, &
            model = model, n_in = n_in, n_components = n_components, &
            num_id = config%num_id, nlo_process = global%nlo_calculation)
    else
        call config%entry%init (prc_name, &
            model = model, n_in = n_in, n_components = n_components, &
            nlo_process = global%nlo_calculation)
    end if
end subroutine process_configuration_init

```

Initialize a process component. The details depend on the process method, which determines the type of the process component core. We set the incoming and outgoing particles (as strings, to be interpreted by the process driver). All other information is taken from the variable list.

The dispatcher gets only the names of the particles. The process component definition gets the complete specifiers which contains a polarization flag and names of decay processes, where applicable.

```

<Process configurations: process configuration: TBP>+≡
    procedure :: setup_component => process_configuration_setup_component

<Process configurations: procedures>+≡
    subroutine process_configuration_setup_component &
        (config, i_component, prt_in, prt_out, global, &
        nlo_type, active_in)
    class(process_configuration_t), intent(inout) :: config
    integer, intent(in) :: i_component
    type(prt_spec_t), dimension(:), intent(in) :: prt_in
    type(prt_spec_t), dimension(:), intent(in) :: prt_out
    type(rt_data_t), intent(inout) :: global
    integer, intent(in), optional :: nlo_type

```



```

logical, intent(in), optional :: active_in
type(string_t), dimension(:), allocatable :: prt_str_in
type(string_t), dimension(:), allocatable :: prt_str_out
class(prc_core_def_t), allocatable :: core_def
type(string_t) :: method
integer :: i
logical :: active

allocate (prt_str_in (size (prt_in)))
allocate (prt_str_out (size (prt_out)))
forall (i = 1:size (prt_in)) prt_str_in(i) = prt_in(i)% get_name ()
forall (i = 1:size (prt_out)) prt_str_out(i) = prt_out(i)%get_name ()
if (present (active_in)) then
    active = active_in
else
    active = .true.
end if

call dispatch_core_def (core_def, prt_str_in, prt_str_out, &
    global, config%id, nlo_type)

method = &
    global%var_list%get_sval (var_str ("method"))
call config%entry%import_component (i_component, &
    n_out = size (prt_out), &
    prt_in = prt_in, &
    prt_out = prt_out, &
    method = method, &
    variant = core_def, &
    nlo_type = nlo_type, &
    active = active)
end subroutine process_configuration_setup_component

```

```

<Process configurations: process configuration: TBP>+=
    procedure :: set_component_associations => &
        process_configuration_set_component_associations

<Process configurations: procedures>+=
    subroutine process_configuration_set_component_associations &
        (config, i_list)
        class(process_configuration_t), intent(inout) :: config
        integer, intent(in), dimension(4) :: i_list
        integer :: i_component
        do i_component = 1, config%entry%get_n_components ()
            if (any (i_list == i_component)) then
                call config%entry%set_associated_components (i_component, &
                    i_list(1), i_list(2), i_list(3), i_list(4))
            end if
        end do
    end subroutine process_configuration_set_component_associations

```

Record a process configuration: append it to the currently selected process definition library.

```

<Process configurations: process configuration: TBP>+=
    procedure :: record => process_configuration_record

```

```

<Process configurations: procedures>+≡
subroutine process_configuration_record (config, global)
class(process_configuration_t), intent(inout) :: config
type(rt_data_t), intent(inout) :: global
if (associated (global%prclib)) then
call global%prclib%open ()
call global%prclib%append (config%entry)
if (config%num_id /= 0) then
write (msg_buffer, "(5A,I0,A)" "Process library '", &
char (global%prclib%get_name ()), &
"' : recorded process '", char (config%id), "' (" , &
config%num_id, ")")
else
write (msg_buffer, "(5A)" "Process library '", &
char (global%prclib%get_name ()), &
"' : recorded process '", char (config%id), "'")
end if
call msg_message ()
else
call msg_fatal ("Recording process '" // char (config%id) &
// "' : active process library undefined")
end if
end subroutine process_configuration_record

```

28.10.2 Test

This is the master for calling self-test procedures.

```

<Process configurations: public>+≡
public :: process_configurations_test

<Process configurations: tests>≡
subroutine process_configurations_test (u, results)
integer, intent(in) :: u
type(test_results_t), intent(inout) :: results
<Process configurations: execute tests>
end subroutine process_configurations_test

```

Minimal setup

The workflow for setting up a minimal process configuration with the test matrix element method.

We wrap this in a public procedure, so we can reuse it in later modules. The procedure prepares a process definition list for two processes (one `prc_test` and one `omega` type) and appends this to the process library stack in the global data set.

The `mode` argument determines which processes to build.

The `procname` argument replaces the predefined `procname(s)`.

```

<Process configurations: public>+≡
public :: prepare_test_library

```

(Process configurations: tests)+≡

```

subroutine prepare_test_library (global, libname, mode, procname)
  type(rt_data_t), intent(inout), target :: global
  type(string_t), intent(in) :: libname
  integer, intent(in) :: mode
  type(string_t), intent(in), dimension(:), optional :: procname
  type(prclib_entry_t), pointer :: lib
  type(string_t) :: prc_name
  type(string_t), dimension(:), allocatable :: prt_in, prt_out
  integer :: n_components
  type(process_configuration_t) :: prc_config

  if (.not. associated (global%prclib_stack%get_first_ptr ())) then
    allocate (lib)
    call lib%init (libname)
    call global%add_prclib (lib)
  end if

  if (btest (mode, 0)) then

    call global%select_model (var_str ("Test"))

    if (present (procname)) then
      prc_name = procname(1)
    else
      prc_name = "prc_config_a"
    end if
    n_components = 1
    allocate (prt_in (2), prt_out (2))
    prt_in = [var_str ("s"), var_str ("s")]
    prt_out = [var_str ("s"), var_str ("s")]

    call var_list_set_string (global%var_list, var_str ("$method"), &
      var_str ("unit_test"), is_known = .true.)

    call prc_config%init (prc_name, size (prt_in), n_components, global)
    call prc_config%setup_component (1, &
      new_prt_spec (prt_in), new_prt_spec (prt_out), global)
    call prc_config%record (global)

    deallocate (prt_in, prt_out)

  end if

  if (btest (mode, 1)) then

    call global%select_model (var_str ("QED"))

    if (present (procname)) then
      prc_name = procname(2)
    else
      prc_name = "prc_config_b"
    end if
    n_components = 1

```

```

allocate (prt_in (2), prt_out (2))
prt_in = [var_str ("e+"), var_str ("e-")]
prt_out = [var_str ("m+"), var_str ("m-")]

call var_list_set_string (global%var_list, var_str ("method"), &
    var_str ("omega"), is_known = .true.)

call prc_config%init (prc_name, size (prt_in), n_components, global)
call prc_config%setup_component (1, &
    new_prt_spec (prt_in), new_prt_spec (prt_out), global)
call prc_config%record (global)

deallocate (prt_in, prt_out)

end if

if (btest (mode, 2)) then

    call global%select_model (var_str ("Test"))

    if (present (procname)) then
        prc_name = procname(1)
    else
        prc_name = "prc_config_a"
    end if
    n_components = 1
    allocate (prt_in (1), prt_out (2))
    prt_in = [var_str ("s")]
    prt_out = [var_str ("f"), var_str ("fbar")]

    call var_list_set_string (global%var_list, var_str ("method"), &
        var_str ("unit_test"), is_known = .true.)

    call prc_config%init (prc_name, size (prt_in), n_components, global)
    call prc_config%setup_component (1, &
        new_prt_spec (prt_in), new_prt_spec (prt_out), global)
    call prc_config%record (global)

    deallocate (prt_in, prt_out)

end if

end subroutine prepare_test_library

```

The actual test: the previous procedure with some prelude and postlude. In the global variable list, just before printing we reset the variables where the value may depend on the system and run environment.

```

<Process configurations: execute tests>≡
    call test (process_configurations_1, "process_configurations_1", &
        "test processes", &
        u, results)

<Process configurations: tests>+≡
    subroutine process_configurations_1 (u)

```

```

integer, intent(in) :: u
type(rt_data_t), target :: global

write (u, "(A)")  "* Test output: process_configurations_1"
write (u, "(A)")  "*   Purpose: configure test processes"
write (u, "(A)")

call syntax_model_file_init ()

call global%global_init ()
call var_list_set_log (global%var_list, var_str ("?omega_omp"), &
    .false., is_known = .true.)

write (u, "(A)")  "* Configure processes as prc_test, model Test"
write (u, "(A)")  "*                               and omega, model QED"
write (u, *)

call var_list_set_int (global%var_list, var_str ("process_num_id"), &
    42, is_known = .true.)
call prepare_test_library (global, var_str ("prc_config_lib_1"), 3)

global%os_data%fc = "Fortran-compiler"
global%os_data%fcflags = "Fortran-flags"

call global%write_libraries (u)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_configurations_1"

end subroutine process_configurations_1

```

O'MEGA options

Slightly extended example where we pass O'MEGA options to the library. The `prepare_test_library` contents are spelled out.

```

<Process configurations: execute tests>+≡
    call test (process_configurations_2, "process_configurations_2", &
        "omega options", &
        u, results)

<Process configurations: tests>+≡
subroutine process_configurations_2 (u)
    integer, intent(in) :: u
    type(rt_data_t), target :: global

    type(string_t) :: libname
    type(prclib_entry_t), pointer :: lib
    type(string_t) :: prc_name
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    integer :: n_components

```

```

type(process_configuration_t) :: prc_config

write (u, "(A)")  "* Test output: process_configurations_2"
write (u, "(A)")  "* Purpose: configure test processes with options"
write (u, "(A)")

call syntax_model_file_init ()

call global%global_init ()

write (u, "(A)")  "* Configure processes as omega, model QED"
write (u, *)

libname = "prc_config_lib_2"

allocate (lib)
call lib%init (libname)
call global%add_prclib (lib)

call global%select_model (var_str ("QED"))

prc_name = "prc_config_c"
n_components = 2
allocate (prt_in (2), prt_out (2))
prt_in = [var_str ("e+"), var_str ("e-")]
prt_out = [var_str ("m+"), var_str ("m-")]

call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("omega"), is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
    .false., is_known = .true.)

call prc_config%init (prc_name, size (prt_in), n_components, global)

call var_list_set_log (global%var_list, var_str ("?report_progress"), &
    .true., is_known = .true.)
call prc_config%setup_component (1, &
    new_prt_spec (prt_in), new_prt_spec (prt_out), global)

call var_list_set_log (global%var_list, var_str ("?report_progress"), &
    .false., is_known = .true.)
call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
    .true., is_known = .true.)
call var_list_set_string (global%var_list, var_str ("$restrictions"), &
    var_str ("3+4~A"), is_known = .true.)
call var_list_set_string (global%var_list, var_str ("$omega_flags"), &
    var_str ("-fusion:progress_file omega_prc_config.log"), &
    is_known = .true.)
call prc_config%setup_component (2, &
    new_prt_spec (prt_in), new_prt_spec (prt_out), global)

call prc_config%record (global)

deallocate (prt_in, prt_out)

```

```

global%os_data%fc = "Fortran-compiler"
global%os_data%fcflags = "Fortran-flags"

call global%write_vars (u, [ &
    var_str ("$model_name"), &
    var_str ("method"), &
    var_str ("?report_progress"), &
    var_str ("restrictions"), &
    var_str ("omega_flags")] )
write (u, "(A)")
call global%write_libraries (u)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: process_configurations_2"

end subroutine process_configurations_2

```

28.11 Compilation

This module manages compilation and loading of process libraries. It is needed as a separate module because integration depends on it.

```
<compilations.f90>≡  
  <File header>  
  
  module compilations  
  
    <Use strings>  
    use io_units  
    use unit_tests  
    use system_defs, only: TAB  
    use diagnostics  
    use os_interface  
    use md5  
    use variables  
    use model_data  
    use models  
    use process_libraries  
    use prclib_stacks  
    use rt_data  
    use process_configurations  
  
    <Standard module head>  
  
    <Compilations: public>  
  
    <Compilations: types>  
  
    contains  
  
    <Compilations: procedures>  
  
    <Compilations: tests>  
  
  end module compilations
```

28.11.1 The data type

The compilation item handles the compilation and loading of a single process library.

```
<Compilations: types>≡  
  type :: compilation_item_t  
    type(string_t) :: libname  
    type(string_t) :: static_external_tag  
    type(process_library_t), pointer :: lib => null ()  
    logical :: recompile_library = .false.  
  contains  
    <Compilations: compilation item: TBP>  
  end type compilation_item_t
```


Initialize:

```
<Compilations: compilation item: TBP>≡
  procedure :: init => compilation_item_init

<Compilations: procedures>≡
  subroutine compilation_item_init (comp, libname, stack, var_list)
    class(compilation_item_t), intent(out) :: comp
    type(string_t), intent(in) :: libname
    type(prclib_stack_t), intent(inout) :: stack
    type(var_list_t), intent(in) :: var_list
    comp%libname = libname
    comp%lib => stack%get_library_ptr (comp%libname)
    if (.not. associated (comp%lib)) then
      call msg_fatal ("Process library '" // char (comp%libname) &
        // "' has not been declared.")
    end if
    comp%recompile_library = &
      var_list%get_lval (var_str ("?recompile_library"))
  end subroutine compilation_item_init
```

Compile the current library. The force flag has the effect that we first delete any previous files, as far as accessible by the current makefile. It also guarantees that previous files not accessible by a makefile will be overwritten.

```
<Compilations: compilation item: TBP>+≡
  procedure :: compile => compilation_item_compile

<Compilations: procedures>+≡
  subroutine compilation_item_compile (comp, model, os_data, force, recompile)
    class(compilation_item_t), intent(inout) :: comp
    class(model_data_t), intent(in), target :: model
    type(os_data_t), intent(in) :: os_data
    logical, intent(in) :: force, recompile
    if (associated (comp%lib)) then
      call msg_message ("Process library '" &
        // char (comp%libname) // "': compiling ...")
      call comp%lib%configure (os_data)
      if (signal_is_pending ()) return
      call comp%lib%compute_md5sum (model)
      call comp%lib%write_makefile (os_data, force)
      if (signal_is_pending ()) return
      if (force) then
        call comp%lib%clean (os_data, distclean = .false.)
        if (signal_is_pending ()) return
      end if
      call comp%lib%write_driver (force)
      if (signal_is_pending ()) return
      if (recompile) then
        call comp%lib%load (os_data, keep_old_source = .true.)
        if (signal_is_pending ()) return
      end if
      call comp%lib%update_status (os_data)
    end if
  end subroutine compilation_item_compile
```

Load the current library, just after compiling it.

```

<Compilations: compilation item: TBP>+≡
    procedure :: load => compilation_item_load

<Compilations: procedures>+≡
    subroutine compilation_item_load (comp, os_data)
        class(compilation_item_t), intent(inout) :: comp
        type(os_data_t), intent(in) :: os_data
        if (associated (comp%lib)) then
            call comp%lib%load (os_data)
        end if
    end subroutine compilation_item_load

```

Message as a separate call:

```

<Compilations: compilation item: TBP>+≡
    procedure :: success => compilation_item_success

<Compilations: procedures>+≡
    subroutine compilation_item_success (comp)
        class(compilation_item_t), intent(in) :: comp
        if (associated (comp%lib)) then
            call msg_message ("Process library '" // char (comp%libname) &
                // "' : ... success.")
        else
            call msg_fatal ("Process library '" // char (comp%libname) &
                // "' : ... failure.")
        end if
    end subroutine compilation_item_success

```

28.11.2 API for library compilation and loading

This is a shorthand for compiling and loading a single library. The `compilation_item` object is used only internally.

The `global` data set may actually be local to the caller. The compilation affects the library specified by its name if it is on the stack, but it does not reset the currently selected library.

```

<Compilations: public>≡
    public :: compile_library

<Compilations: procedures>+≡
    subroutine compile_library (libname, global)
        type(string_t), intent(in) :: libname
        type(rt_data_t), intent(inout), target :: global
        type(compilation_item_t) :: comp
        logical :: force, recompile
        force = &
            global%var_list%get_lval (var_str ("?rebuild_library"))
        recompile = &
            global%var_list%get_lval (var_str ("?recompile_library"))
        if (associated (global%model)) then
            call comp%init (libname, global%prclib_stack, global%var_list)
            call comp%compile (global%model, global%os_data, force, recompile)
            if (signal_is_pending ()) return
        end if
    end subroutine compile_library

```

```

        call comp%load (global%os_data)
        if (signal_is_pending ()) return
    else
        call msg_fatal ("Process library compilation: " &
            // " model is undefined.")
    end if
    call comp%success ()
end subroutine compile_library

```

28.11.3 Compiling static executable

This object handles the creation of a static executable which should contain a set of static process libraries.

```

<Compilations: types>+≡
    type :: compilation_t
    private
        type(string_t) :: exe_name
        type(string_t), dimension(:), allocatable :: lib_name
    contains
        <Compilations: compilation: TBP>
    end type compilation_t

```

Output.

```

<Compilations: compilation: TBP>≡
    procedure :: write => compilation_write

<Compilations: procedures>+≡
    subroutine compilation_write (object, unit)
        class(compilation_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u, i
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Compilation object:"
        write (u, "(3x,3A)") "executable          = '", &
            char (object%exe_name), "'
        write (u, "(3x,A)", advance="no") "process libraries ="
        do i = 1, size (object%lib_name)
            write (u, "(1x,3A)", advance="no") "' '", char (object%lib_name(i)), "'
        end do
        write (u, *)
    end subroutine compilation_write

```

Initialize: we know the names of the executable and of the libraries.

```

<Compilations: compilation: TBP>+≡
    procedure :: init => compilation_init

<Compilations: procedures>+≡
    subroutine compilation_init (compilation, exe_name, lib_name)
        class(compilation_t), intent(out) :: compilation
        type(string_t), intent(in) :: exe_name
        type(string_t), dimension(:), intent(in) :: lib_name
        compilation%exe_name = exe_name

```

```

        allocate (compilation%lib_name (size (lib_name)))
        compilation%lib_name = lib_name
    end subroutine compilation_init

```

Write the dispatcher subroutine for the compiled libraries. Also write a subroutine which returns the names of the compiled libraries.

<Compilations: compilation: TBP>+≡

```

    procedure :: write_dispatcher => compilation_write_dispatcher

```

<Compilations: procedures>+≡

```

subroutine compilation_write_dispatcher (compilation)
    class(compilation_t), intent(in) :: compilation
    type(string_t) :: file
    integer :: u, i
    file = compilation%exe_name // "_prclib_dispatcher.f90"
    call msg_message ("Static executable '" // char (compilation%exe_name) &
        // "' : writing library dispatcher")
    u = free_unit ()
    open (u, file = char (file), status="replace", action="write")
    write (u, "(3A)") " ! Whizard: process libraries for executable '", &
        char (compilation%exe_name), "'"
    write (u, "(A)") " ! Automatically generated file, do not edit"
    write (u, "(A)") " subroutine dispatch_prclib_static " // &
        "(driver, basename, modellibs_ldflags)"
    write (u, "(A)") " use iso_varying_string, string_t => varying_string"
    write (u, "(A)") " use prclib_interfaces"
    do i = 1, size (compilation%lib_name)
        associate (lib_name => compilation%lib_name(i))
            write (u, "(A)") " use " // char (lib_name) // "_driver"
        end associate
    end do
    write (u, "(A)") " implicit none"
    write (u, "(A)") " class(prclib_driver_t), intent(inout), allocatable &
        &:: driver"
    write (u, "(A)") " type(string_t), intent(in) :: basename"
    write (u, "(A)") " logical, intent(in), optional :: " // &
        "modellibs_ldflags"
    write (u, "(A)") " select case (char (basename))"
    do i = 1, size (compilation%lib_name)
        associate (lib_name => compilation%lib_name(i))
            write (u, "(3A)") " case ('', char (lib_name), '')"
            write (u, "(3A)") " allocate (" , char (lib_name), "_driver_t &
                &:: driver)"
        end associate
    end do
    write (u, "(A)") " end select"
    write (u, "(A)") "end subroutine dispatch_prclib_static"
    write (u, *)
    write (u, "(A)") "subroutine get_prclib_static (libname)"
    write (u, "(A)") " use iso_varying_string, string_t => varying_string"
    write (u, "(A)") " implicit none"
    write (u, "(A)") " type(string_t), dimension(:), intent(inout), &
        &allocatable :: libname"
    write (u, "(A,IO,A)") " allocate (libname (" , &

```

```

        size (compilation%lib_name), ")")
do i = 1, size (compilation%lib_name)
    associate (lib_name => compilation%lib_name(i))
        write (u, "(A,IO,A,A,A)") " libname(", i, ") = '", &
            char (lib_name), "'"
    end associate
end do
write (u, "(A)") "end subroutine get_prclib_static"
close (u)
end subroutine compilation_write_dispatcher

```

Write the Makefile subroutine for the compiled libraries.

(Compilations: compilation: TBP)+=

```

    procedure :: write_makefile => compilation_write_makefile

```

(Compilations: procedures)+=

```

subroutine compilation_write_makefile (compilation, os_data, ext_libtag)
    class(compilation_t), intent(in) :: compilation
    type(os_data_t), intent(in) :: os_data
    type(string_t), intent(in), optional :: ext_libtag
    type(string_t) :: file, ext_tag
    integer :: u, i
    if (present (ext_libtag)) then
        ext_tag = ext_libtag
    else
        ext_tag = ""
    end if
    file = compilation%exe_name // ".makefile"
    call msg_message ("Static executable '" // char (compilation%exe_name) &
        // "' : writing makefile")
    u = free_unit ()
    open (u, file = char (file), status="replace", action="write")
    write (u, "(3A)") "# WHIZARD: Makefile for executable '", &
        char (compilation%exe_name), "'"
    write (u, "(A)") "# Automatically generated file, do not edit"
    write (u, "(A)") ""
    write (u, "(A)") "# Executable name"
    write (u, "(A)") "EXE = " // char (compilation%exe_name)
    write (u, "(A)") ""
    write (u, "(A)") "# Compiler"
    write (u, "(A)") "FC = " // char (os_data%fc)
    write (u, "(A)") ""
    write (u, "(A)") "# Included libraries"
    write (u, "(A)") "FCINCL = " // char (os_data%whizard_includes)
    write (u, "(A)") ""
    write (u, "(A)") "# Compiler flags"
    write (u, "(A)") "FCFLAGS = " // char (os_data%fcflags)
    write (u, "(A)") "LDFLAGS = " // char (os_data%ldflags)
    write (u, "(A)") "LDFLAGS_STATIC = " // char (os_data%ldflags_static)
    write (u, "(A)") "LDFLAGS_HEPMC = " // char (os_data%ldflags_hepmc)
    write (u, "(A)") "LDFLAGS_HOPPET = " // char (os_data%ldflags_hoppet)
    write (u, "(A)") "LDFLAGS_LOOPTOOLS = " // char (os_data%ldflags_looptools)
    write (u, "(A)") "LDWHIZARD = " // char (os_data%whizard_ldflags)
    write (u, "(A)") ""

```

```

write (u, "(A)") "# Libtool"
write (u, "(A)") "LIBTOOL = " // char (os_data%whizard_libtool)
write (u, "(A)") "FCOMPILE = $(LIBTOOL) --tag=FC --mode=compile"
write (u, "(A)") "LINK = $(LIBTOOL) --tag=FC --mode=link"
write (u, "(A)") ""
write (u, "(A)") "# Compile commands (default)"
write (u, "(A)") "LTF_COMPILE = $(FCOMPILE) $(FC) -c $(FCINCL) $(FCFLAGS)"
write (u, "(A)") ""
write (u, "(A)") "# Default target"
write (u, "(A)") "all: link"
write (u, "(A)") ""
write (u, "(A)") "# Libraries"
do i = 1, size (compilation%lib_name)
  associate (lib_name => compilation%lib_name(i))
    write (u, "(A)") "LIBRARIES += " // char (lib_name) // ".la"
    write (u, "(A)") char (lib_name) // ".la:"
    write (u, "(A)") TAB // "$(MAKE) -f " // char (lib_name) // ".makefile"
  end associate
end do
write (u, "(A)") ""
write (u, "(A)") "# Library dispatcher"
write (u, "(A)") "DISP = $(EXE)_prclib_dispatcher"
write (u, "(A)") "$(DISP).lo: $(DISP).f90 $(LIBRARIES)"
write (u, "(A)") TAB // "$(LTF_COMPILE) $<"
write (u, "(A)") ""
write (u, "(A)") "# Executable"
write (u, "(A)") "$(EXE): $(DISP).lo $(LIBRARIES)"
write (u, "(A)") TAB // "$(LINK) $(FC) -static-libtool-libs $(FCFLAGS) \"
write (u, "(A)") TAB // "    $(LDWHIZARD) $(LD_FLAGS) \"
write (u, "(A)") TAB // "    -o $(EXE) $^ \"
write (u, "(A)") TAB // "    $(LD_FLAGS_HEPMC) $(LD_FLAGS_HOPPET) $(LD_FLAGS_LOOPTOOLS) \"
write (u, "(A)") TAB // "    $(LD_FLAGS_STATIC)\" // char (ext_tag)
write (u, "(A)") ""
write (u, "(A)") "# Main targets"
write (u, "(A)") "link: compile $(EXE)"
write (u, "(A)") "compile: $(LIBRARIES) $(DISP).lo"
write (u, "(A)") ".PHONY: link compile"
write (u, "(A)") ""
write (u, "(A)") "# Cleanup targets"
write (u, "(A)") "clean-exe:"
write (u, "(A)") TAB // "rm -f $(EXE)"
write (u, "(A)") "clean-objects:"
write (u, "(A)") TAB // "rm -f $(DISP).lo"
write (u, "(A)") "clean-source:"
write (u, "(A)") TAB // "rm -f $(DISP).f90"
write (u, "(A)") "clean-makefile:"
write (u, "(A)") TAB // "rm -f $(EXE).makefile"
write (u, "(A)") ""
write (u, "(A)") "clean: clean-exe clean-objects clean-source"
write (u, "(A)") "distclean: clean clean-makefile"
write (u, "(A)") ".PHONY: clean distclean"
close (u)
end subroutine compilation_write_makefile

```

Compile the dispatcher source code.

```

<Compilations: compilation: TBP>+≡
    procedure :: make_compile => compilation_make_compile

<Compilations: procedures>+≡
    subroutine compilation_make_compile (compilation, os_data)
        class(compilation_t), intent(in) :: compilation
        type(os_data_t), intent(in) :: os_data
        call os_system_call ("make compile " // os_data%makeflags &
            // " -f " // compilation%exe_name // ".makefile")
    end subroutine compilation_make_compile

```

Link the dispatcher together with all matrix-element code and the WHIZARD and O'MEGA main libraries, to generate a static executable.

```

<Compilations: compilation: TBP>+≡
    procedure :: make_link => compilation_make_link

<Compilations: procedures>+≡
    subroutine compilation_make_link (compilation, os_data)
        class(compilation_t), intent(in) :: compilation
        type(os_data_t), intent(in) :: os_data
        call os_system_call ("make link " // os_data%makeflags &
            // " -f " // compilation%exe_name // ".makefile")
    end subroutine compilation_make_link

```

Cleanup.

```

<Compilations: compilation: TBP>+≡
    procedure :: make_clean_exe => compilation_make_clean_exe

<Compilations: procedures>+≡
    subroutine compilation_make_clean_exe (compilation, os_data)
        class(compilation_t), intent(in) :: compilation
        type(os_data_t), intent(in) :: os_data
        call os_system_call ("make clean-exe " // os_data%makeflags &
            // " -f " // compilation%exe_name // ".makefile")
    end subroutine compilation_make_clean_exe

```

28.11.4 API for executable compilation

This is a shorthand for compiling and loading an executable, including the enclosed libraries. The `compilation` object is used only internally.

The `global` data set may actually be local to the caller. The compilation affects the library specified by its name if it is on the stack, but it does not reset the currently selected library.

```

<Compilations: public>+≡
    public :: compile_executable

<Compilations: procedures>+≡
    subroutine compile_executable (exename, libname, global)
        type(string_t), intent(in) :: exename
        type(string_t), dimension(:), intent(in) :: libname
        type(rt_data_t), intent(inout), target :: global

```

```

type(compilation_t) :: compilation
type(compilation_item_t) :: item
type(string_t) :: ext_libtag
logical :: force, recompile
integer :: i
ext_libtag = ""
force = &
    global%var_list%get_lval (var_str ("?rebuild_library"))
recompile = &
    global%var_list%get_lval (var_str ("?recompile_library"))
call compilation%init (exename, [libname])
if (signal_is_pending ()) return
call compilation%write_dispatcher ()
if (signal_is_pending ()) return
do i = 1, size (libname)
    call item%init (libname(i), global%prclib_stack, global%var_list)
    call item%compile (global%model, global%os_data, &
        force=force, recompile=recompile)
    ext_libtag = "" // item%lib%get_static_modelname (global%os_data)
    if (signal_is_pending ()) return
    call item%success ()
end do
call compilation%write_makefile (global%os_data, ext_libtag)
if (signal_is_pending ()) return
call compilation%make_compile (global%os_data)
if (signal_is_pending ()) return
call compilation%make_link (global%os_data)
end subroutine compile_executable

```

28.11.5 Test

This is the master for calling self-test procedures.

```

<Compilations: public>+≡
    public :: compilations_test

<Compilations: tests>≡
    subroutine compilations_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Compilations: execute tests>
    end subroutine compilations_test

```

Intrinsic Matrix Element

Compile an intrinsic test matrix element (prc_test type).

Note: In this and the following test, we reset the Fortran compiler and flag variables immediately before they are printed, so the test is portable.

```

<Compilations: execute tests>≡
    call test (compilations_1, "compilations_1", &
        "intrinsic test processes", &
        u, results)

```



```

<Compilations: tests>+≡
subroutine compilations_1 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname
  type(rt_data_t), target :: global

  write (u, "(A)")  "* Test output: compilations_1"
  write (u, "(A)")  "* Purpose: configure and compile test process"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()

  libname = "compilation_1"
  procname = "prc_comp_1"
  call prepare_test_library (global, libname, 1, [procname])

  call compile_library (libname, global)

  call global%write_libraries (u)

  call global%final ()
  call syntax_model_file_final ()

  write (u, "(A)")
  write (u, "(A)")  "* Test output end: compilations_1"

end subroutine compilations_1

```

External Matrix Element

Compile an external test matrix element (omega type)

```

<Compilations: execute tests>+≡
  call test (compilations_2, "compilations_2", &
    "external process (omega)", &
    u, results)

<Compilations: tests>+≡
subroutine compilations_2 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname
  type(rt_data_t), target :: global

  write (u, "(A)")  "* Test output: compilations_2"
  write (u, "(A)")  "* Purpose: configure and compile test process"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()
  call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
    .false., is_known = .true.)

```

```

libname = "compilation_2"
procname = "prc_comp_2"
call prepare_test_library (global, libname, 2, [procname,procname])

call compile_library (libname, global)

call global%write_libraries (u, libpath = .false.)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: compilations_2"

end subroutine compilations_2

```

External Matrix Element

Compile an external test matrix element (ω type) and create driver files for a static executable.

```

<Compilations: execute tests>+≡
  call test (compilations_3, "compilations_3", &
    "static executable: driver", &
    u, results)

<Compilations: tests>+≡
  subroutine compilations_3 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname, exename
    type(rt_data_t), target :: global
    type(compilation_t) :: compilation
    integer :: u_file
    character(80) :: buffer

    write (u, "(A)")  "* Test output: compilations_3"
    write (u, "(A)")  "* Purpose: make static executable"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize library"
    write (u, "(A)")

    call syntax_model_file_init ()

    call global%global_init ()
    call var_list_set_log (global%var_list, var_str ("?omega_omp"), &
      .false., is_known = .true.)

    libname = "compilations_3_lib"
    procname = "prc_comp_3"
    exename = "compilations_3"

    call prepare_test_library (global, libname, 2, [procname,procname])

```

```

call compilation%init (exename, [libname])
call compilation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write dispatcher"
write (u, "(A)")

call compilation%write_dispatcher ()

u_file = free_unit ()
open (u_file, file = char (exename) // "_prclib_dispatcher.f90", &
      status = "old", action = "read")
do
  read (u_file, "(A)", end = 1)  buffer
  write (u, "(A)")  trim (buffer)
end do
1 close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Write Makefile"
write (u, "(A)")

associate (os_data => global%os_data)
  os_data%fc = "fortran-compiler"
  os_data%whizard_includes = "my-includes"
  os_data%fcflags = "my-fcflags"
  os_data%ldflags = "my-ldflags"
  os_data%ldflags_static = "my-ldflags-static"
  os_data%ldflags_hepmc = "my-ldflags-hepmc"
  os_data%ldflags_hoppet = "my-ldflags-hoppet"
  os_data%ldflags_looptools = "my-ldflags-looptools"
  os_data%whizard_ldflags = "my-ldwhizard"
  os_data%whizard_libtool = "my-libtool"
end associate

call compilation%write_makefile (global%os_data)

open (u_file, file = char (exename) // ".makefile", &
      status = "old", action = "read")
do
  read (u_file, "(A)", end = 2)  buffer
  write (u, "(A)")  trim (buffer)
end do
2 close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: compilations_3"

```

```
end subroutine compilations_3
```

28.11.6 Test static build

The tests for building a static executable are separate, since they should be skipped if the WHIZARD build itself has static libraries disabled.

```
<Compilations: public>+≡
  public :: compilations_static_test

<Compilations: tests>+≡
  subroutine compilations_static_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
    <Compilations: static tests>
  end subroutine compilations_static_test
```

External Matrix Element

Compile an external test matrix element (omega type) and incorporate this in a new static WHIZARD executable.

```
<Compilations: static tests>≡
  call test (compilations_static_1, "compilations_static_1", &
    "static executable: compilation", &
    u, results)

<Compilations: tests>+≡
  subroutine compilations_static_1 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname, exename
    type(rt_data_t), target :: global
    type(compilation_item_t) :: item
    type(compilation_t) :: compilation
    logical :: exist

    write (u, "(A)")  "* Test output: compilations_static_1"
    write (u, "(A)")  "* Purpose: make static executable"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize library"

    call syntax_model_file_init ()

    call global%global_init ()
    call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
      .false., is_known = .true.)

    libname = "compilations_static_1_lib"
    procname = "prc_comp_stat_1"
    exename = "compilations_static_1"
```

```

call prepare_test_library (global, libname, 2, [procname,procname])

call compilation%init (exename, [libname])

write (u, "(A)")
write (u, "(A)")  "* Write dispatcher"

call compilation%write_dispatcher ()

write (u, "(A)")
write (u, "(A)")  "* Write Makefile"

call compilation%write_makefile (global%os_data)

write (u, "(A)")
write (u, "(A)")  "* Build libraries"

call item%init (libname, global%prclib_stack, global%var_list)
call item%compile &
    (global%model, global%os_data, force=.true., recompile=.false.)
call item%success ()

write (u, "(A)")
write (u, "(A)")  "* Check executable (should be absent)"
write (u, "(A)")

call compilation%make_clean_exe (global%os_data)
inquire (file = char (exename), exist = exist)
write (u, "(A,A,L1)") char (exename), " exists = ", exist

write (u, "(A)")
write (u, "(A)")  "* Build executable"
write (u, "(A)")

call compilation%make_compile (global%os_data)
call compilation%make_link (global%os_data)

write (u, "(A)")  "* Check executable (should be present)"
write (u, "(A)")

inquire (file = char (exename), exist = exist)
write (u, "(A,A,L1)") char (exename), " exists = ", exist

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call compilation%make_clean_exe (global%os_data)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: compilations_static_1"

```

```
end subroutine compilations_static_1
```

External Matrix Element

Compile an external test matrix element (*omega* type) and incorporate this in a new static WHIZARD executable. In this version, we use the wrapper `compile_executable` procedure.

```
(Compilations: static tests) +=
  call test (compilations_static_2, "compilations_static_2", &
    "static executable: shortcut", &
    u, results)

(Compilations: tests) +=
  subroutine compilations_static_2 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname, exename
    type(rt_data_t), target :: global
    logical :: exist
    integer :: u_file

    write (u, "(A)")  "* Test output: compilations_static_2"
    write (u, "(A)")  "* Purpose: make static executable"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize library and compile"
    write (u, "(A)")

    call syntax_model_file_init ()

    call global%global_init ()
    call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
      .false., is_known = .true.)

    libname = "compilations_static_2_lib"
    procname = "prc_comp_stat_2"
    exename = "compilations_static_2"

    call prepare_test_library (global, libname, 2, [procname, procname])

    call compile_executable (exename, [libname], global)

    write (u, "(A)")  "* Check executable (should be present)"
    write (u, "(A)")

    inquire (file = char (exename), exist = exist)
    write (u, "(A,A,L1)") char (exename), " exists = ", exist

    write (u, "(A)")
    write (u, "(A)")  "* Cleanup"

    u_file = free_unit ()
    open (u_file, file = char (exename), status = "old", action = "write")
    close (u_file, status = "delete")
```

```
call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: compilations_static_2"

end subroutine compilations_static_2
```

28.12 Integration

This module manages phase space setup, matrix-element evaluation and integration, as far as it is not done by lower-level routines, in particular in the `processes` module.

`<integrations.f90>`≡

<File header>

```
module integrations
```

```
  <Use kinds>
```

```
  <Use strings>
```

```
    use io_units
```

```
    use unit_tests
```

```
    use diagnostics
```

```
    use os_interface
```

```
    use cputime
```

```
    use sm_qcd
```

```
    use physics_defs
```

```
    use ifiles
```

```
    use lexers
```

```
    use parser
```

```
    use model_data
```

```
    use flavors
```

```
    use pdg_arrays
```

```
    use variables
```

```
    use expr_base
```

```
    use eval_trees
```

```
    use models
```

```
    use interactions
```

```
    use sf_mappings
```

```
    use sf_base
```

```
    use phs_base
```

```
    use mappings
```

```
    use phs_forests
```

```
    use phs_wood
```

```
    use rng_base
```

```
    use mci_base
```

```
    use process_libraries
```

```
    use prc_core
```

```
    use processes
```

```
    use process_stacks
```

```
    use models
```

```
    use iterations
```

```
    use rt_data
```

```
    use dispatch
```

```
    use process_configurations
```

```
    use compilations
```

```
    use process_constants
```

```
    use prc_omega
```

```
    use prc_gosam
```

```
    use blha_olp_interfaces
```

```
    use nlo_data
```



```

    <Standard module head>

    <Integrations: public>

    <Integrations: types>

contains

    <Integrations: procedures>

    <Integrations: tests>

end module integrations

```

28.12.1 The integration type

This type holds all relevant data, the integration methods operates on this. In contrast to the `simulation_t` introduced later, the `integration_t` applies to a single process.

```

<Integrations: public>≡
    public :: integration_t

<Integrations: types>≡
    type :: integration_t
        private
            type(string_t) :: process_id
            type(string_t) :: run_id
            type(process_t), pointer :: process => null ()
            type(var_list_t), pointer :: model_vars => null ()
            type(qcd_t) :: qcd
            logical :: rebuild_phs = .false.
            logical :: ignore_phs_mismatch = .false.
            logical :: phs_only = .false.
            logical :: process_has_me = .true.
            integer :: n_calls_test = 0
            logical :: vis_history = .true.
            type(string_t) :: history_filename
            type(string_t) :: log_filename
            logical :: combined_integration = .false.
        contains
            <Integrations: integration: TBP>
    end type integration_t

```

28.12.2 Initialization

Initialization, first part: Create a process entry. Push it on the stack if the global environment is supplied.

```

<Integrations: integration: TBP>≡
    procedure :: create_process => integration_create_process

```

```

<Integrations: procedures>+=
subroutine integration_create_process (intg, process_id, global)
  class(integration_t), intent(out) :: intg
  type(rt_data_t), intent(inout), optional, target :: global
  type(string_t), intent(in) :: process_id
  type(process_entry_t), pointer :: process_entry
  intg%process_id = process_id
  if (present (global)) then
    allocate (process_entry)
    intg%process => process_entry%process_t
    call global%process_stack%push (process_entry)
  else
    allocate (process_t :: intg%process)
  end if
  intg%model_vars => null ()
end subroutine integration_create_process

```

Initialization, second part: Initialize the process object, using the local environment. We allocate a RNG factory and a QCD object. We also fetch a pointer to the model that the process uses. The process initializer will create a snapshot of that model.

This procedure does not modify the local stack directly. The intent(inout) attribute for the local data set is due to the random generator seed which may be incremented during initialization.

NOTE: Changes to model parameters within the current context are respected only if the process model coincides with the current model. This is the usual case. If not, we read the model from the global model library, which has default parameters. To become more flexible, we should implement a local model library which records local changes to currently inactive models.

```

<Integrations: integration: TBP>+=
procedure :: init_process => integration_init_process

<Integrations: procedures>+=
subroutine integration_init_process (intg, local)
  class(integration_t), intent(inout) :: intg
  type(rt_data_t), intent(inout), target :: local
  type(string_t) :: model_name
  type(model_t), pointer :: model
  class(model_data_t), pointer :: model_instance
  class(rng_factory_t), allocatable :: rng_factory
  if (.not. local%prclib%contains (intg%process_id)) then
    call msg_fatal ("Process '" // char (intg%process_id) // "' not found" &
      // " in library '" // char (local%prclib%get_name ()) // "'")
    return
  end if
  intg%run_id = &
    local%var_list%get_sval (var_str ("$_run_id"))
  call dispatch_qcd (intg%qcd, local)
  call dispatch_rng_factory (rng_factory, local)
  model_name = local%prclib%get_model_name (intg%process_id)
  if (local%get_sval (var_str ("$_model_name")) == model_name) then
    model => local%model
  else

```

```

        model => local%model_list%get_model_ptr (model_name)
    end if
    allocate (model_t :: model_instance)
    select type (model_instance)
    type is (model_t)
        call model_instance%init_instance (model)
        intg%model_vars => model_instance%get_var_list_ptr ()
    end select
    call intg%process%init (intg%process_id, intg%run_id, &
        local%prclib, &
        local%os_data, intg%qcd, rng_factory, model_instance)
end subroutine integration_init_process

```

Initialization, third part: complete process configuration.

(Integrations: integration: TBP)+≡

```

    procedure :: setup_process => integration_setup_process

```

(Integrations: procedures)+≡

```

    subroutine integration_setup_process (intg, local, verbose)
        class(integration_t), intent(inout) :: intg
        type(rt_data_t), intent(inout), target :: local
        logical, intent(in), optional :: verbose
        type(var_list_t), pointer :: var_list
        class(prc_core_t), allocatable :: core_template
        class(phs_config_t), allocatable :: phs_config_template
        class(phs_config_t), allocatable :: phs_config_template_other
        type(phs_parameters_t) :: phs_par
        type(mapping_defaults_t) :: mapping_defs
        class(mci_t), allocatable :: mci_template
        integer :: n_components, n_in, i_component
        type(pdg_array_t), dimension(:,,:), allocatable :: pdg_prc
        type(process_component_def_t), pointer :: config
        type(helicity_selection_t), allocatable :: helicity_selection
        real(default) :: sqrts
        logical :: decay_rest_frame, use_color_factors
        type(sf_config_t), dimension(:), allocatable :: sf_config
        type(sf_prop_t) :: sf_prop
        type(sf_channel_t), dimension(:), allocatable :: sf_channel
        type(phs_channel_collection_t) :: phs_channel_collection
        logical :: sf_trace
        type(string_t) :: sf_string, sf_trace_file
        logical :: verb
        integer :: i_born
        type(fks_template_t) :: fks_template
        type(blha_template_t) :: blha_template
        type(string_t) :: me_method
        type(eval_tree_factory_t) :: expr_factory

        verb = .true.; if (present (verbose)) verb = verbose

        call intg%process%set_var_list (local%get_var_list_ptr ())
        var_list => intg%process%get_var_list_ptr ()

        intg%rebuild_phs = &

```

```

        var_list%get_lval (var_str ("?rebuild_phase_space"))
    intg%ignore_phs_mismatch = &
        .not. var_list%get_lval (var_str ("?check_phs_file"))
    intg%phs_only = &
        var_list%get_lval (var_str ("?phs_only"))
    phs_par%m_threshold_s = &
        var_list%get_rval (var_str ("phs_threshold_s"))
    phs_par%m_threshold_t = &
        var_list%get_rval (var_str ("phs_threshold_t"))
    phs_par%off_shell = &
        var_list%get_ival (var_str ("phs_off_shell"))
    phs_par%keep_nonresonant = &
        var_list%get_lval (var_str ("?phs_keep_nonresonant"))
    phs_par%t_channel = &
        var_list%get_ival (var_str ("phs_t_channel"))
    mapping_defs%energy_scale = &
        var_list%get_rval (var_str ("phs_e_scale"))
    mapping_defs%invariant_mass_scale = &
        var_list%get_rval (var_str ("phs_m_scale"))
    mapping_defs%momentum_transfer_scale = &
        var_list%get_rval (var_str ("phs_q_scale"))
    mapping_defs%step_mapping = &
        var_list%get_lval (var_str ("?phs_step_mapping"))
    mapping_defs%step_mapping_exp = &
        var_list%get_lval (var_str ("?phs_step_mapping_exp"))
    mapping_defs%enable_s_mapping = &
        var_list%get_lval (var_str ("?phs_s_mapping"))

    call dispatch_phs (phs_config_template, local, &
        intg%process_id, mapping_defs, phs_par)

    intg%n_calls_test = &
        var_list%get_ival (var_str ("n_calls_test"))

    !!! We avoid two dots in the filename due to a bug in certain MetaPost versions.
    if (intg%run_id /= "") then
        intg%history_filename = intg%process_id // "." // intg%run_id &
            // "-history"
        intg%log_filename = intg%process_id // "." // intg%run_id // ".log"
    else
        intg%history_filename = intg%process_id // "-history"
        intg%log_filename = intg%process_id // ".log"
    end if

    call dispatch_mci (mci_template, local, intg%process_id)

    if (verb) then
        call msg_message ("Initializing integration for process " &
            // char (intg%process_id) // ":")
        if (intg%run_id /= "") then
            call msg_message ("Run ID = " // ' ' // char (intg%run_id) // ' ')
        end if
    end if

```

```

helicity_selection = local%get_helicity_selection ()

intg%vis_history = &
    var_list%get_lval (var_str ("?vis_history"))
use_color_factors = var_list%get_lval &
    (var_str ("?read_color_factors"))

n_components = intg%process%get_n_components ()
n_in = intg%process%get_n_in ()

call blha_template%init ()
intg%combined_integration = var_list%get_lval (&
    var_str ('?combined_nlo_integration')) &
    .and. intg%process%is_nlo_calculation ()

do i_component = 1, n_components
    config => intg%process%get_component_def_ptr (i_component)
    call dispatch_core (core_template, config%get_core_def_ptr (), &
        intg%process%get_model_ptr (), helicity_selection, intg%qcd, &
        use_color_factors)
    select case (config%get_nlo_type ())
    case (NLO_VIRTUAL)
        me_method = var_list%get_sval (var_str ("$loop_me_method"))
        select case (char (me_method))
        case ('gosam', 'openloops')
            call blha_template%set_loop ()
        end select
        call intg%process%init_component &
            (i_component, core_template, mci_template, phs_config_template, &
            blha_template = blha_template)
        if (intg%combined_integration) &
            call intg%process%set_component_type (i_component, COMP_VIRT)
    case (NLO_REAL)
        me_method = var_list%get_sval (var_str ("$real_tree_me_method"))
        select case (char (me_method))
        case ('gosam', 'openloops')
            call blha_template%set_real_trees ()
        end select
        call dispatch_phs (phs_config_template_other, local, &
            intg%process_id, mapping_defs, phs_par, &
            var_str ('fks'))
        call dispatch_fks (fks_template, local)
        call intg%process%init_component &
            (i_component, core_template, mci_template, &
            phs_config_template_other, fks_template = fks_template, &
            blha_template = blha_template)
        if (intg%combined_integration) &
            call intg%process%set_component_type (i_component, COMP_REAL)
    case (NLO_PDF)
        call dispatch_phs (phs_config_template_other, local, &
            intg%process_id, mapping_defs, phs_par, &
            var_str ('fks'))
        call intg%process%init_component &

```

```

        (i_component, core_template, mci_template, phs_config_template_other)
    if (intg%combined_integration) &
        call intg%process%set_component_type (i_component, COMP_PDF)
    case (BORN)
        call intg%process%init_component &
            (i_component, core_template, mci_template, phs_config_template)
        i_born = config%get_associated_born ()
        if (intg%combined_integration) &
            call intg%process%set_component_type (i_component, COMP_MASTER)
    case (NLO_SUBTRACTION)
        me_method = var_list%get_sval (var_str ("$correlation_me_method"))
        select case (char (me_method))
            case ('gosam', 'openloops')
                call blha_template%set_subtraction ()
        end select
        call intg%process%init_component &
            (i_component, core_template, mci_template, phs_config_template, &
                blha_template = blha_template)
        if (intg%combined_integration) &
            call intg%process%set_component_type (i_component, COMP_SUB)
    case default
        call msg_fatal ("setup_process: NLO type not implemented!")
    end select
    call blha_template%reset ()
    deallocate (core_template)
    if (allocated (phs_config_template_other)) deallocate (phs_config_template_other)
end do

if (verb) call intg%process%write (screen = .true.)

intg%process_has_me = intg%process%has_matrix_element ()
if (.not. intg%process_has_me) then
    call msg_warning ("Process '" &
        // char (intg%process_id) // "': matrix element vanishes")
end if

sqrts = local%get_sqrts ()
decay_rest_frame = &
    var_list%get_lval (var_str ("?decay_rest_frame"))
if (intg%process_has_me) then
    if (local%beam_structure%is_set ()) then
        call intg%process%setup_beams_beam_structure &
            (local%beam_structure, sqrts, decay_rest_frame)
    else if (n_in == 2) then
        call intg%process%setup_beams_sqrts &
            (sqrts, local%beam_structure)
    else
        call intg%process%setup_beams_decay &
            (decay_rest_frame, local%beam_structure)
    end if
end if
call intg%process%check_masses ()
if (verb .and. intg%process_has_me) then
    call intg%process%beams_startup_message &

```

```

        (beam_structure = local%beam_structure)
end if

if (intg%process_has_me) then
    call intg%process%get_pdg_in (pdg_prc)
else
    allocate (pdg_prc (n_in, n_components))
    pdg_prc = 0
end if
call dispatch_sf_config (sf_config, sf_prop, local, pdg_prc)
sf_trace = &
    var_list%get_lval (var_str ("?sf_trace"))
sf_trace_file = &
    var_list%get_sval (var_str ("$sf_trace_file"))
if (sf_trace) then
    call intg%process%init_sf_chain (sf_config, sf_trace_file)
else
    call intg%process%init_sf_chain (sf_config)
end if

if (intg%process_has_me) then
    call intg%process%configure_phs &
        (intg%rebuild_phs, intg%ignore_phs_mismatch, verbose=verbose, &
        combined_integration=intg%combined_integration)
    if (size (sf_config) > 0) then
        call intg%process%collect_channels (phs_channel_collection)
    else if (intg%process%contains_trivial_component ()) then
        call msg_fatal ("Integrate: 2 -> 1 process can't be handled &
            &with fixed-energy beams")
    end if
    call dispatch_sf_channels &
        (sf_channel, sf_string, sf_prop, phs_channel_collection, local)
    if (allocated (sf_channel)) then
        if (size (sf_channel) > 0) then
            call intg%process%set_sf_channel (sf_channel)
        end if
    end if
    call phs_channel_collection%final ()
    if (verb) call intg%process%sf_startup_message (sf_string)
end if

call intg%setup_process_mci ()
call intg%process%setup_terms ()

if (associated (local%pn%cuts_lexpr)) then
    if (verb) call msg_message ("Applying user-defined cuts.")
    call expr_factory%init (local%pn%cuts_lexpr)
    call intg%process%set_cuts (expr_factory)
else
    if (verb) call msg_warning ("No cuts have been defined.")
end if
if (associated (local%pn%scale_expr)) then
    if (verb) call msg_message ("Using user-defined general scale.")
    call expr_factory%init (local%pn%scale_expr)

```

```

        call intg%process%set_scale (expr_factory)
    end if
    if (associated (local%pn%fac_scale_expr)) then
        if (verb) call msg_message ("Using user-defined factorization scale.")
        call expr_factory%init (local%pn%fac_scale_expr)
        call intg%process%set_fac_scale (expr_factory)
    end if
    if (associated (local%pn%ren_scale_expr)) then
        if (verb) call msg_message ("Using user-defined renormalization scale.")
        call expr_factory%init (local%pn%ren_scale_expr)
        call intg%process%set_ren_scale (expr_factory)
    end if
    if (associated (local%pn%weight_expr)) then
        if (verb) call msg_message ("Using user-defined reweighting factor.")
        call expr_factory%init (local%pn%weight_expr)
        call intg%process%set_weight (expr_factory)
    end if

    call intg%process%compute_md5sum ()
end subroutine integration_setup_process

```

28.12.3 Integration

Integrate: do the final integration. Here, we do a multi-iteration integration. Again, we skip iterations that are already on file. Record the results in the global variable list.

```

<Integrations: integration: TBP>+=
    procedure :: evaluate => integration_evaluate

<Integrations: procedures>+=
    subroutine integration_evaluate &
        (intg, process_instance, i_mci, pass, it_list, pacify)
        class(integration_t), intent(inout) :: intg
        type(process_instance_t), intent(inout), target :: process_instance
        integer, intent(in) :: i_mci
        integer, intent(in) :: pass
        type(iterations_list_t), intent(in) :: it_list
        logical, intent(in), optional :: pacify
        integer :: n_calls, n_it
        logical :: adapt_grids, adapt_weights, final

        n_it = it_list%get_n_it (pass)
        n_calls = it_list%get_n_calls (pass)
        adapt_grids = it_list%adapt_grids (pass)
        adapt_weights = it_list%adapt_weights (pass)
        final = pass == it_list%get_n_pass ()

        call intg%process%integrate (process_instance, &
            i_mci, n_it, n_calls, adapt_grids, adapt_weights, &
            final, pacify)

    end subroutine integration_evaluate

```


In case the user has not provided a list of iterations, make a reasonable default. This can depend on the process. The usual approach is to define two distinct passes, one for adaptation and one for integration.

```

(Integrations: integration: TBP)+≡
  procedure :: make_iterations_list => integration_make_iterations_list

(Integrations: procedures)+≡
  subroutine integration_make_iterations_list (intg, it_list)
    class(integration_t), intent(in) :: intg
    type(iterations_list_t), intent(out) :: it_list
    integer :: pass, n_pass
    integer, dimension(:), allocatable :: n_it, n_calls
    logical, dimension(:), allocatable :: adapt_grids, adapt_weights
    n_pass = intg%process%get_n_pass_default ()
    allocate (n_it (n_pass), n_calls (n_pass))
    allocate (adapt_grids (n_pass), adapt_weights (n_pass))
    do pass = 1, n_pass
      n_it(pass)      = intg%process%get_n_it_default (pass)
      n_calls(pass)   = intg%process%get_n_calls_default (pass)
      adapt_grids(pass) = intg%process%adapt_grids_default (pass)
      adapt_weights(pass) = intg%process%adapt_weights_default (pass)
    end do
    call it_list%init (n_it, n_calls, &
      adapt_grids = adapt_grids, adapt_weights = adapt_weights)
  end subroutine integration_make_iterations_list

```

28.12.4 API for integration objects

This initializer does everything except assigning cuts/scale/weight expressions.

```

(Integrations: integration: TBP)+≡
  procedure :: init => integration_init

(Integrations: procedures)+≡
  subroutine integration_init (intg, process_id, local, global, local_stack)
    class(integration_t), intent(out) :: intg
    type(string_t), intent(in) :: process_id
    type(rt_data_t), intent(inout), target :: local
    type(rt_data_t), intent(inout), optional, target :: global
    logical, intent(in), optional :: local_stack
    logical :: use_local
    use_local = .false.; if (present (local_stack)) use_local = local_stack
    if (present (global)) then
      call intg%create_process (process_id, global)
    else if (use_local) then
      call intg%create_process (process_id, local)
    else
      call intg%create_process (process_id)
    end if
    call intg%init_process (local)
    call intg%setup_process (local)
  end subroutine integration_init

```

Do the integration for a single process, both warmup and final evaluation. The `eff_reset` flag is to suppress numerical noise in the graphical output of the integration history.

```

(Integrations: integration: TBP)+≡
  procedure :: integrate => integration_integrate

(Integrations: procedures)+≡
  subroutine integration_integrate (intg, local, eff_reset)
    class(integration_t), intent(inout) :: intg
    type(rt_data_t), intent(in), target :: local
    logical, intent(in), optional :: eff_reset
    type(string_t) :: log_filename
    type(var_list_t), pointer :: var_list
    type(process_instance_t), allocatable, target :: process_instance
    type(iterations_list_t) :: it_list
    logical :: pacify
    integer :: pass, i_mci, n_mci, n_pass
    integer :: nlo_type
    logical :: display_summed
    logical :: use_internal_color_correlations
    type(string_t) :: color_method

    var_list => intg%process%get_var_list_ptr ()

    color_method = var_list%get_sval (var_str ('$correlation_me_method'))
    use_internal_color_correlations = color_method == 'omega'

    allocate (process_instance)
    call process_instance%init (intg%process, use_internal_color_correlations, &
                               combined_integration = intg%combined_integration)

    if (process_instance%has_nlo_component ()) then
      call process_instance%create_blha_interface ()
      call process_instance%load_blha_libraries (local%os_data)
      call process_instance%set_blha_constants (var_list)
    end if

    call openmp_set_num_threads_verbose &
      (var_list%get_ival (var_str ("openmp_num_threads")), &
       var_list%get_lval (var_str ("?openmp_logging")))
    pacify = var_list%get_lval (var_str ("?pacify"))

    display_summed = .true.
    n_mci = intg%process%get_n_mci ()
    if (n_mci == 1) then
      write (msg_buffer, "(A,A,A)") &
        "Starting integration for process '", &
        char (intg%process%get_id ()), "'"
      call msg_message ()
    end if
    call intg%setup_component_cores ()

    do i_mci = 1, n_mci
      if (intg%process%is_active_nlo_component (i_mci)) then

```

```

if (n_mci > 1) then
  write (msg_buffer, "(A,A,A,I0)") &
    "Starting integration for process '", &
    char (intg%process%get_id ()), "' part ", i_mci
  call msg_message ()
end if
n_pass = local%it_list%get_n_pass ()
if (n_pass == 0) then
  call msg_message ("Integrate: iterations not specified, &
    &using default")
  call intg%make_iterations_list (it_list)
  n_pass = it_list%get_n_pass ()
else
  it_list = local%it_list
end if
call msg_message ("Integrate: " // char (it_list%to_string ()))
do pass = 1, n_pass
  call intg%evaluate (process_instance, i_mci, pass, it_list, pacify)
  if (signal_is_pending ()) return
end do
call intg%process%final_integration (i_mci)
if (intg%vis_history) then
  call intg%process%display_integration_history &
    (i_mci, intg%history_filename, local%os_data, eff_reset)
end if
if (local%logfile == intg%log_filename) then
  if (intg%run_id /= "") then
    log_filename = intg%process_id // "." // intg%run_id // &
      ".var.log"
  else
    log_filename = intg%process_id // ".var.log"
  end if
  call msg_message ("Name clash for global logfile and process log: ", &
    arr=[var_str ("| Renaming log file from ") // local%logfile, &
      var_str ("| to ") // log_filename // var_str (" .")])
else
  log_filename = intg%log_filename
end if
call intg%process%write_logfile (i_mci, log_filename)
else
  nlo_type = intg%process%get_component_nlo_type (i_mci)
  if (nlo_type /= NLO_SUBTRACTION) display_summed = .false.
end if
end do

if (n_mci > 1 .and. display_summed) then
  call msg_message ("Integrate: sum of all components")
  call intg%process%display_summed_results ()
end if

call process_instance%final ()
deallocate (process_instance)

end subroutine integration_integrate

```

```

<Integrations: integration: TBP>+≡
  procedure :: setup_component_cores => integration_setup_component_cores

<Integrations: procedures>+≡
  subroutine integration_setup_component_cores (intg)
    class(integration_t), intent(inout) :: intg
    associate (process => intg%process)
      call setup_nlo_component_cores (process)
    end associate
  end subroutine integration_setup_component_cores

```

```

<Integrations: integration: TBP>+≡
  procedure :: setup_process_mci => integration_setup_process_mci

<Integrations: procedures>+≡
  subroutine integration_setup_process_mci (intg)
    class(integration_t), intent(inout) :: intg
    call intg%process%setup_mci (intg%combined_integration)
  end subroutine integration_setup_process_mci

```

Do a dummy integration for a process which could not be initialized (e.g., has no matrix element). The result is zero.

```

<Integrations: integration: TBP>+≡
  procedure :: integrate_dummy => integration_integrate_dummy

<Integrations: procedures>+≡
  subroutine integration_integrate_dummy (intg)
    class(integration_t), intent(inout) :: intg
    call intg%process%integrate_dummy ()
  end subroutine integration_integrate_dummy

```

Just sample the matrix element under realistic conditions (but no cuts); throw away the results.

```

<Integrations: integration: TBP>+≡
  procedure :: sampler_test => integration_sampler_test

<Integrations: procedures>+≡
  subroutine integration_sampler_test (intg)
    class(integration_t), intent(inout) :: intg
    type(process_instance_t), allocatable, target :: process_instance
    integer :: n_mci, i_mci
    type(timer_t) :: timer_mci, timer_tot
    real(default) :: t_mci, t_tot
    allocate (process_instance)
    call process_instance%init (intg%process)
    n_mci = intg%process%get_n_mci ()
    if (n_mci == 1) then
      write (msg_buffer, "(A,A,A)") &
        "Test: probing process '", &
        char (intg%process%get_id ()), "'"
      call msg_message ()
    end if
  end subroutine integration_sampler_test

```

```

call timer_tot%start ()
do i_mci = 1, n_mci
  if (n_mci > 1) then
    write (msg_buffer, "(A,A,A,IO)") &
      "Test: probing process '", &
      char (intg%process%get_id ()), "' part ", i_mci
    call msg_message ()
  end if
  call timer_mci%start ()
  call intg%process%sampler_test &
    (process_instance, i_mci, intg%n_calls_test)
  call timer_mci%stop ()
  t_mci = timer_mci
  write (msg_buffer, "(A,ES12.5)") "Test: " &
    // "time in seconds (wallclock): ", t_mci
  call msg_message ()
end do
call timer_tot%stop ()
t_tot = timer_tot
if (n_mci > 1) then
  write (msg_buffer, "(A,ES12.5)") "Test: " &
    // "total time (wallclock): ", t_tot
  call msg_message ()
end if
call process_instance%final ()
end subroutine integration_sampler_test

```

Return the process pointer (needed by simulate):

```

<Integrations: integration: TBP>+≡
  procedure :: get_process_ptr => integration_get_process_ptr

<Integrations: procedures>+≡
  function integration_get_process_ptr (intg) result (ptr)
    class(integration_t), intent(in) :: intg
    type(process_t), pointer :: ptr
    ptr => intg%process
  end function integration_get_process_ptr

```

Simply integrate, do a dummy integration if necessary. The **integration** object exists only internally.

If the **global** environment is provided, the process object is appended to the global stack. Otherwise, if **local_stack** is set, we append to the local process stack. If this is unset, the **process** object is not recorded permanently.

The **init_only** flag can be used to skip the actual integration part. We will end up with a process object that is completely initialized, including phase space configuration.

The **eff_reset** flag is to suppress numerical noise in the visualization of the integration history.

```

<Integrations: public>+≡
  public :: integrate_process

<Integrations: procedures>+≡
  subroutine integrate_process (process_id, local, global, local_stack, init_only, eff_reset)

```

```

type(string_t), intent(in) :: process_id
type(rt_data_t), intent(inout), target :: local
type(rt_data_t), intent(inout), optional, target :: global
logical, intent(in), optional :: local_stack, init_only, eff_reset
type(string_t) :: prclib_name
type(integration_t) :: intg
character(32) :: buffer

if (.not. associated (local%prclib)) then
    call msg_fatal ("Integrate: current process library is undefined")
    return
end if

if (.not. local%prclib%is_active ()) then
    call msg_message ("Integrate: current process library needs compilation")
    prclib_name = local%prclib%get_name ()
    call compile_library (prclib_name, local)
    if (signal_is_pending ()) return
    call msg_message ("Integrate: compilation done")
end if

call intg%init (process_id, local, global, local_stack)
if (signal_is_pending ()) return

if (present (init_only)) then
    if (init_only) return
end if

if (intg%n_calls_test > 0) then
    write (buffer, "(I0)") intg%n_calls_test
    call msg_message ("Integrate: test (" // trim (buffer) // " calls) ...")
    call intg%sampler_test ()
    call msg_message ("Integrate: ... test complete.")
    if (signal_is_pending ()) return
end if

if (intg%phs_only) then
    call msg_message ("Integrate: phase space only, skipping integration")
else
    if (intg%process_has_me) then
        call intg%integrate (local, eff_reset)
    else
        call intg%integrate_dummy ()
    end if
end if

end subroutine integrate_process

```

28.12.5 Test

This is the master for calling self-test procedures.

(Integrations: public)+≡

```

    public :: integrations_test
<Integrations: tests>≡
    subroutine integrations_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Integrations: execute tests>
    end subroutine integrations_test

<Integrations: public>+≡
    public :: integrations_history_test

<Integrations: tests>+≡
    subroutine integrations_history_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Integrations: execute history tests>
    end subroutine integrations_history_test

```

Integration of test process

Compile and integrate an intrinsic test matrix element (`prc_test` type). The phase-space implementation is `phs_single` (single-particle phase space), the integrator is `mci_midpoint`.

The cross section for the $2 \rightarrow 2$ process $ss \rightarrow ss$ with its constant matrix element is given by

$$\sigma = c \times f \times \Phi_2 \times |M|^2. \quad (28.1)$$

c is the conversion constant

$$c = 0.3894 \times 10^{12} \text{ fb GeV}^2. \quad (28.2)$$

f is the flux of the incoming particles with mass $m = 125 \text{ GeV}$ and energy $\sqrt{s} = 1000 \text{ GeV}$

$$f = \frac{(2\pi)^4}{2\lambda^{1/2}(s, m^2, m^2)} = \frac{(2\pi)^4}{2\sqrt{s}\sqrt{s-4m^2}} = 8.048 \times 10^{-4} \text{ GeV}^{-2} \quad (28.3)$$

Φ_2 is the volume of the two-particle phase space

$$\Phi_2 = \frac{1}{4(2\pi)^5} = 2.5529 \times 10^{-5}. \quad (28.4)$$

The squared matrix element $|M|^2$ is unity. Combining everything, we obtain

$$\sigma = 8000 \text{ fb} \quad (28.5)$$

This number should appear as the final result.

Note: In this and the following test, we reset the Fortran compiler and flag variables immediately before they are printed, so the test is portable.

```

<Integrations: execute tests>≡
    call test (integrations_1, "integrations_1", &
        "intrinsic test process", &
        u, results)

```

```

<Integrations: tests>+=
subroutine integrations_1 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname
  type(rt_data_t), target :: global

  write (u, "(A)")  "* Test output: integrations_1"
  write (u, "(A)")  "* Purpose: integrate test process"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()

  libname = "integration_1"
  procname = "prc_config_a"

  call prepare_test_library (global, libname, 1)
  call compile_library (libname, global)

  call global%set_string (var_str ("$_run_id"), &
    var_str ("integrations1"), is_known = .true.)
  call global%set_string (var_str ("$_method"), &
    var_str ("unit_test"), is_known = .true.)
  call global%set_string (var_str ("$_phs_method"), &
    var_str ("single"), is_known = .true.)
  call global%set_string (var_str ("$_integration_method"), &
    var_str ("midpoint"), is_known = .true.)
  call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
  call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
  call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

  call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

  call global%it_list%init ([1], [1000])

  call reset_interaction_counter ()
  call integrate_process (procname, global, local_stack=.true.)

  call global%write (u, vars = [ &
    var_str ("$_method"), &
    var_str ("sqrts"), &
    var_str ("$_integration_method"), &
    var_str ("$_phs_method"), &
    var_str ("$_run_id")])

  call global%final ()
  call syntax_model_file_final ()

  write (u, "(A)")

```



```

        write (u, "(A)")  "* Test output end: integrations_1"

    end subroutine integrations_1

```

Integration with cuts

Compile and integrate an intrinsic test matrix element (`prc_test` type) with cuts set.

```

<Integrations: execute tests>+=
    call test (integrations_2, "integrations_2", &
        "intrinsic test process with cut", &
        u, results)

<Integrations: tests>+=
    subroutine integrations_2 (u)
        integer, intent(in) :: u
        type(string_t) :: libname, procname
        type(rt_data_t), target :: global

        type(string_t) :: cut_expr_text
        type(ifile_t) :: ifile
        type(stream_t) :: stream
        type(parse_tree_t) :: parse_tree

        type(string_t), dimension(0) :: empty_string_array

        write (u, "(A)")  "* Test output: integrations_2"
        write (u, "(A)")  "* Purpose: integrate test process with cut"
        write (u, "(A)")

        call syntax_model_file_init ()

        call global%global_init ()

        write (u, "(A)")  "* Prepare a cut expression"
        write (u, "(A)")

        call syntax_pexpr_init ()
        cut_expr_text = "all Pt > 100 [s]"
        call ifile_append (ifile, cut_expr_text)
        call stream_init (stream, ifile)
        call parse_tree_init_lexpr (parse_tree, stream, .true.)
        global%pn%cuts_lexpr => parse_tree_get_root_ptr (parse_tree)

        write (u, "(A)")  "* Build and initialize a test process"
        write (u, "(A)")

        libname = "integration_3"
        procname = "prc_config_a"

        call prepare_test_library (global, libname, 1)
        call compile_library (libname, global)

```

```

call global%set_string (var_str ("$_run_id"), &
    var_str ("integrations1"), is_known = .true.)
call global%set_string (var_str ("$_method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$_phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$_integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

call reset_interaction_counter ()
call integrate_process (procname, global, local_stack=.true.)

call global%write (u, vars = empty_string_array)

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_2"

end subroutine integrations_2

```

Standard phase space

Compile and integrate an intrinsic test matrix element (`prc_test` type) using the default (`phs_wood`) phase-space implementation. We use an explicit phase-space configuration file with a single channel and integrate by `mci_midpoint`.

```

<Integrations: execute tests>+≡
    call test (integrations_3, "integrations_3", &
        "standard phase space", &
        u, results)

<Integrations: tests>+≡
subroutine integrations_3 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname
    type(rt_data_t), target :: global
    integer :: u_phs

    write (u, "(A)")  "* Test output: integrations_3"
    write (u, "(A)")  "* Purpose: integrate test process"
    write (u, "(A)")

```

```

write (u, "(A)")  "* Initialize process and parameters"
write (u, "(A)")

call syntax_model_file_init ()
call syntax_phs_forest_init ()

call global%global_init ()

libname = "integration_3"
procname = "prc_config_a"

call prepare_test_library (global, libname, 1)
call compile_library (libname, global)

call global%set_string (var_str ("$run_id"), &
    var_str ("integrations1"), is_known = .true.)
call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("default"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?phs_s_mapping"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

write (u, "(A)")  "* Create a scratch phase-space file"
write (u, "(A)")

u_phs = free_unit ()
open (u_phs, file = "integrations_3.phs", &
    status = "replace", action = "write")
call write_test_phs_file (u_phs, var_str ("prc_config_a_i1"))
close (u_phs)

call global%set_string (var_str ("$phs_file"), &
    var_str ("integrations_3.phs"), is_known = .true.)

call global%it_list%init ([1], [1000])

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call reset_interaction_counter ()
call integrate_process (procname, global, local_stack=.true.)

```

```

call global%write (u, vars = [ &
    var_str ("phs_method"), &
    var_str ("phs_file")])

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_phs_forest_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_3"

end subroutine integrations_3

```

VAMP integration

Compile and integrate an intrinsic test matrix element (`prc_test` type) using the single-channel (`phs_single`) phase-space implementation. The integration method is `vamp`.

```

<Integrations: execute tests>+≡
    call test (integrations_4, "integrations_4", &
        "VAMP integration (one iteration)", &
        u, results)

<Integrations: tests>+≡
subroutine integrations_4 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname
    type(rt_data_t), target :: global

    write (u, "(A)")  "* Test output: integrations_4"
    write (u, "(A)")  "* Purpose: integrate test process using VAMP"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize process and parameters"
    write (u, "(A)")

    call syntax_model_file_init ()

    call global%global_init ()

    libname = "integrations_4_lib"
    procname = "integrations_4"

    call prepare_test_library (global, libname, 1, [procname])
    call compile_library (libname, global)

    call global%append_log (&
        var_str ("?rebuild_grids"), .true., intrinsic = .true.)

```

```

call global%set_string (var_str ("$_run_id"), &
    var_str ("r1"), is_known = .true.)
call global%set_string (var_str ("$_method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$_phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$_integration_method"), &
    var_str ("vamp"), is_known = .true.)
call global%set_log (var_str ("?use_vamp_equivalences"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call reset_interaction_counter ()
call integrate_process (procname, global, local_stack=.true.)

call global%pacify (efficiency_reset = .true., error_reset = .true.)
call global%write (u, vars = [var_str ("$_integration_method")], &
    pacify = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_4"

end subroutine integrations_4

```

Multiple iterations integration

Compile and integrate an intrinsic test matrix element (`prc_test` type) using the single-channel (`phs_single`) phase-space implementation. The integration method is `vamp`. We launch three iterations.

```

<Integrations: execute tests>+≡
call test (integrations_5, "integrations_5", &
    "VAMP integration (three iterations)", &
    u, results)

```

```

<Integrations: tests>+=
subroutine integrations_5 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname
  type(rt_data_t), target :: global

  write (u, "(A)")  "* Test output: integrations_5"
  write (u, "(A)")  "* Purpose: integrate test process using VAMP"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize process and parameters"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()

  libname = "integrations_5_lib"
  procname = "integrations_5"

  call prepare_test_library (global, libname, 1, [procname])
  call compile_library (libname, global)

  call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)

  call global%set_string (var_str ("$run_id"), &
    var_str ("r1"), is_known = .true.)
  call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
  call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
  call global%set_string (var_str ("$integration_method"), &
    var_str ("vamp"), is_known = .true.)
  call global%set_log (var_str ("?use_vamp_equivalences"), &
    .false., is_known = .true.)
  call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
  call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
  call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

  call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

  call global%it_list%init ([3], [1000])

  write (u, "(A)")  "* Integrate"
  write (u, "(A)")

  call reset_interaction_counter ()
  call integrate_process (procname, global, local_stack=.true.)

```

```

call global%pacify (efficiency_reset = .true., error_reset = .true.)
call global%write (u, vars = [var_str ("integration_method")], &
    pacify = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_5"

end subroutine integrations_5

```

Multiple passes integration

Compile and integrate an intrinsic test matrix element (`prc_test` type) using the single-channel (`phs_single`) phase-space implementation. The integration method is `vamp`. We launch three passes with three iterations each.

```

<Integrations: execute tests>+=
call test (integrations_6, "integrations_6", &
    "VAMP integration (three passes)", &
    u, results)

<Integrations: tests>+=
subroutine integrations_6 (u)
integer, intent(in) :: u
type(string_t) :: libname, procname
type(rt_data_t), target :: global
type(string_t), dimension(0) :: no_vars

write (u, "(A)")  "* Test output: integrations_6"
write (u, "(A)")  "* Purpose: integrate test process using VAMP"
write (u, "(A)")

write (u, "(A)")  "* Initialize process and parameters"
write (u, "(A)")

call syntax_model_file_init ()

call global%global_init ()

libname = "integrations_6_lib"
procname = "integrations_6"

call prepare_test_library (global, libname, 1, [procname])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)

call global%set_string (var_str ("run_id"), &

```

```

        var_str ("r1"), is_known = .true.)
call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$integration_method"),&
    var_str ("vamp"), is_known = .true.)
call global%set_log (var_str ("?use_vamp_equivalences"),&
    .false., is_known = .true.)
call global%set_log (var_str ("?vis_history"),&
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"),&
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

call global%set_real (var_str ("sqrts"),&
    1000._default, is_known = .true.)

call global%it_list%init ([3, 3, 3], [1000, 1000, 1000], &
    adapt = [.true., .true., .false.], &
    adapt_code = [var_str ("wg"), var_str ("g"), var_str ("")])

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call reset_interaction_counter ()
call integrate_process (procname, global, local_stack=.true.)

call global%pacify (efficiency_reset = .true., error_reset = .true.)
call global%write (u, vars = no_vars, pacify = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_6"

end subroutine integrations_6

```

VAMP and default phase space

Compile and integrate an intrinsic test matrix element (`prc_test` type) using the default (`phs_wood`) phase-space implementation. The integration method is `vamp`. We launch three passes with three iterations each. We enable channel equivalences and groves.

```

<Integrations: execute tests>+≡
call test (integrations_7, "integrations_7", &
    "VAMP integration with wood phase space", &

```



```

        u, results)
<Integrations: tests>+=
subroutine integrations_7 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname
    type(rt_data_t), target :: global
    type(string_t), dimension(0) :: no_vars
    integer :: iostat, u_phs
    character(95) :: buffer
    type(string_t) :: phs_file
    logical :: exist

    write (u, "(A)")  "* Test output: integrations_7"
    write (u, "(A)")  "* Purpose: integrate test process using VAMP"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize process and parameters"
    write (u, "(A)")

    call syntax_model_file_init ()
    call syntax_phs_forest_init ()

    call global%global_init ()

    libname = "integrations_7_lib"
    procname = "integrations_7"

    call prepare_test_library (global, libname, 1, [procname])
    call compile_library (libname, global)

    call global%append_log (&
        var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
    call global%append_log (&
        var_str ("?rebuild_grids"), .true., intrinsic = .true.)

    call global%set_string (var_str ("$_run_id"), &
        var_str ("r1"), is_known = .true.)
    call global%set_string (var_str ("$_method"), &
        var_str ("unit_test"), is_known = .true.)
    call global%set_string (var_str ("$_phs_method"), &
        var_str ("wood"), is_known = .true.)
    call global%set_string (var_str ("$_integration_method"), &
        var_str ("vamp"), is_known = .true.)
    call global%set_log (var_str ("?use_vamp_equivalences"), &
        .true., is_known = .true.)
    call global%set_log (var_str ("?vis_history"), &
        .false., is_known = .true.)
    call global%set_log (var_str ("?integration_timer"), &
        .false., is_known = .true.)
    call global%set_log (var_str ("?phs_s_mapping"), &
        .false., is_known = .true.)
    call global%set_int (var_str ("seed"), &
        0, is_known=.true.)

```

```

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([3, 3, 3], [1000, 1000, 1000], &
    adapt = [.true., .true., .false.], &
    adapt_code = [var_str ("wg"), var_str ("g"), var_str ("")])

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call reset_interaction_counter ()
call integrate_process (procname, global, local_stack=.true.)

call global%pacify (efficiency_reset = .true., error_reset = .true.)
call global%write (u, vars = no_vars, pacify = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_phs_forest_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Generated phase-space file"
write (u, "(A)")

phs_file = procname // "_i1.r1.phs"
inquire (file = char (phs_file), exist = exist)
if (exist) then
    u_phs = free_unit ()
    open (u_phs, file = char (phs_file), action = "read", status = "old")
    iostat = 0
    do while (iostat == 0)
        read (u_phs, "(A)", iostat = iostat)  buffer
        if (iostat == 0) write (u, "(A)")  trim (buffer)
    end do
    close (u_phs)
else
    write (u, "(A)")  "[file is missing]"
end if

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_7"

end subroutine integrations_7

```

Structure functions

Compile and integrate an intrinsic test matrix element (`prc_test` type) using the default (`phs_wood`) phase-space implementation. The integration method is `vamp`. There is a structure function of type `unit_test`.

We use a test structure function $f(x) = x$ for both beams. Together with the $1/x_1x_2$ factor from the phase-space flux and a unit matrix element, we should get the same result as previously for the process without structure functions. There is a slight correction due to the m_s mass which we set to zero here.

```

(Integrations: execute tests)+≡
  call test (integrations_8, "integrations_8", &
    "integration with structure function", &
    u, results)

(Integrations: tests)+≡
  subroutine integrations_8 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname
    type(rt_data_t), target :: global
    type(flavor_t) :: flv
    type(string_t) :: name

    write (u, "(A)")  "* Test output: integrations_8"
    write (u, "(A)")  "* Purpose: integrate test process using VAMP &
      &with structure function"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize process and parameters"
    write (u, "(A)")

    call syntax_model_file_init ()
    call syntax_phs_forest_init ()

    call global%global_init ()

    libname = "integrations_8_lib"
    procname = "integrations_8"

    call prepare_test_library (global, libname, 1, [procname])
    call compile_library (libname, global)

    call global%append_log (&
      var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
    call global%append_log (&
      var_str ("?rebuild_grids"), .true., intrinsic = .true.)

    call global%set_string (var_str ("$_run_id"), &
      var_str ("r1"), is_known = .true.)
    call global%set_string (var_str ("$_method"), &
      var_str ("unit_test"), is_known = .true.)
    call global%set_string (var_str ("$_phs_method"), &
      var_str ("wood"), is_known = .true.)
    call global%set_string (var_str ("$_integration_method"), &
      var_str ("vamp"), is_known = .true.)
    call global%set_log (var_str ("?use_vamp_equivalences"), &
      .true., is_known = .true.)
    call global%set_log (var_str ("?vis_history"), &
      .false., is_known = .true.)
    call global%set_log (var_str ("?integration_timer"), &

```

```

        .false., is_known = .true.)
call global%set_log (var_str ("?phs_s_mapping"), &
        .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
        0, is_known=.true.)

call global%set_real (var_str ("sqrts"), &
        1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), 0._default)

call reset_interaction_counter ()

call flv%init (25, global%model)

name = flv%get_name ()
call global%beam_structure%init_sf ([name, name], [1])
call global%beam_structure%set_sf (1, 1, var_str ("sf_test_1"))

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call global%it_list%init ([1], [1000])
call integrate_process (procname, global, local_stack=.true.)

call global%write (u, vars = [var_str ("ms")])

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_phs_forest_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_8"

end subroutine integrations_8

```

Integration history for VAMP integration with default phase space

This test is only run when event analysis can be done.

<Integrations: execute history tests>≡

```

call test (integrations_history_1, "integrations_history_1", &
        "Test integration history files", &
        u, results)

```

<Integrations: tests>+≡

```

subroutine integrations_history_1 (u)
integer, intent(in) :: u
type(string_t) :: libname, procname
type(rt_data_t), target :: global
type(string_t), dimension(0) :: no_vars
integer :: iostat, u_his

```

```

character(91) :: buffer
type(string_t) :: his_file, ps_file, pdf_file
logical :: exist, exist_ps, exist_pdf

write (u, "(A)")  "* Test output: integrations_history_1"
write (u, "(A)")  "* Purpose: test integration history files"
write (u, "(A)")

write (u, "(A)")  "* Initialize process and parameters"
write (u, "(A)")

call syntax_model_file_init ()
call syntax_phs_forest_init ()

call global%global_init ()

libname = "integrations_history_1_lib"
procname = "integrations_history_1"

call global%set_log (var_str ("?vis_history"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?integration_timer"),&
    .false., is_known = .true.)
call global%set_log (var_str ("?phs_s_mapping"),&
    .false., is_known = .true.)

call prepare_test_library (global, libname, 1, [procname])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)

call global%set_string (var_str ("$_run_id"), &
    var_str ("r1"), is_known = .true.)
call global%set_string (var_str ("$_method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$_phs_method"), &
    var_str ("wood"), is_known = .true.)
call global%set_string (var_str ("$_integration_method"),&
    var_str ("vamp"), is_known = .true.)
call global%set_log (var_str ("?use_vamp_equivalences"),&
    .true., is_known = .true.)
call global%set_real (var_str ("error_threshold"),&
    5E-6_default, is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known=.true.)

call global%set_real (var_str ("sqrt_s"),&
    1000._default, is_known = .true.)

call global%it_list%init ([2, 2, 2], [1000, 1000, 1000], &
    adapt = [.true., .true., .false.], &

```

```

        adapt_code = [var_str ("wg"), var_str ("g"), var_str ("")]

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call reset_interaction_counter ()
call integrate_process (procname, global, local_stack=.true., &
    eff_reset = .true.)

call global%pacify (efficiency_reset = .true., error_reset = .true.)
call global%write (u, vars = no_vars, pacify = .true.)

write (u, "(A)")
write (u, "(A)")  "* Generated history files"
write (u, "(A)")

his_file = procname // ".r1-history.tex"
ps_file  = procname // ".r1-history.ps"
pdf_file = procname // ".r1-history.pdf"
inquire (file = char (his_file), exist = exist)
if (exist) then
    u_his = free_unit ()
    open (u_his, file = char (his_file), action = "read", status = "old")
    iostat = 0
    do while (iostat == 0)
        read (u_his, "(A)", iostat = iostat)  buffer
        if (iostat == 0) write (u, "(A)") trim (buffer)
    end do
    close (u_his)
else
    write (u, "(A)") "[History LaTeX file is missing]"
end if
inquire (file = char (ps_file), exist = exist_ps)
if (exist_ps) then
    write (u, "(A)") "[History Postscript file exists and is nonempty]"
else
    write (u, "(A)") "[History Postscript file is missing/non-regular]"
end if
inquire (file = char (pdf_file), exist = exist_pdf)
if (exist_pdf) then
    write (u, "(A)") "[History PDF file exists and is nonempty]"
else
    write (u, "(A)") "[History PDF file is missing/non-regular]"
end if

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()
call syntax_phs_forest_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: integrations_history_1"

```

```
end subroutine integrations_history_1
```

28.13 Event Streams

This module manages I/O from/to multiple concurrent event streams. Usually, there is at most one input stream, but several output streams. For the latter, we set up an array which can hold `eio_t` (event I/O) objects of different dynamic types simultaneously. One of them may be marked as an input channel.

```
(event_streams.f90)≡  
  <File header>  
  
  module event_streams  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use unit_tests  
    use diagnostics  
    use variables  
    use model_data  
    use models  
    use processes  
    use events  
    use eio_data  
    use eio_base  
    use rt_data  
    use dispatch  
  
    <Standard module head>  
  
    <Event streams: public>  
  
    <Event streams: types>  
  
    contains  
  
    <Event streams: tests>  
  
    <Event streams: procedures>  
  
  end module event_streams
```

28.13.1 Event Stream Array

Each entry is an `eio_t` object. Since the type is dynamic, we need a wrapper:

```
<Event streams: types>≡  
  type :: event_stream_entry_t  
    class(eio_t), allocatable :: eio  
  end type event_stream_entry_t
```

An array of event-stream entry objects. If one of the entries is an input channel, `i_in` is the corresponding index.

```
<Event streams: public>≡  
  public :: event_stream_array_t
```



```

<Event streams: types>+≡
  type :: event_stream_array_t
    type(event_stream_entry_t), dimension(:), allocatable :: entry
    integer :: i_in = 0
  contains
    <Event streams: event stream array: TBP>
  end type event_stream_array_t

```

Output.

```

<Event streams: event stream array: TBP>≡
  procedure :: write => event_stream_array_write

<Event streams: procedures>≡
  subroutine event_stream_array_write (object, unit)
    class(event_stream_array_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(1x,A)") "Event stream array:"
    if (allocated (object%entry)) then
      select case (size (object%entry))
      case (0)
        write (u, "(3x,A)") "[empty]"
      case default
        do i = 1, size (object%entry)
          if (i == object%i_in) write (u, "(1x,A)") "Input stream:"
          call object%entry(i)%eio%write (u)
        end do
      end select
    else
      write (u, "(3x,A)") "[undefined]"
    end if
  end subroutine event_stream_array_write

```

Finalize all streams.

```

<Event streams: event stream array: TBP>+≡
  procedure :: final => event_stream_array_final

<Event streams: procedures>+≡
  subroutine event_stream_array_final (es_array)
    class(event_stream_array_t), intent(inout) :: es_array
    integer :: i
    do i = 1, size (es_array%entry)
      call es_array%entry(i)%eio%final ()
    end do
  end subroutine event_stream_array_final

```

Initialization. We use a generic `sample` name, open event I/O objects for all provided stream types (using the `dispatch_eio` routine), and initialize for the given list of process pointers. If there is an `input` argument, this channel is initialized as an input channel and appended to the array.

The `input_data` or, if not present, `data` may be modified. This happens if we open a stream for reading and get new information there.

(Event streams: event stream array: TBP)+≡

```
procedure :: init => event_stream_array_init
```

(Event streams: procedures)+≡

```
subroutine event_stream_array_init &
  (es_array, sample, stream_fmt, global, &
   data, input, input_sample, input_data, allow_switch, checkpoint, &
   error)
class(event_stream_array_t), intent(out) :: es_array
type(string_t), intent(in) :: sample
type(string_t), dimension(:), intent(in) :: stream_fmt
type(rt_data_t), intent(in) :: global
type(event_sample_data_t), intent(inout), optional :: data
type(string_t), intent(in), optional :: input
type(string_t), intent(in), optional :: input_sample
type(event_sample_data_t), intent(inout), optional :: input_data
logical, intent(in), optional :: allow_switch
integer, intent(in), optional :: checkpoint
logical, intent(out), optional :: error
type(string_t) :: sample_in
integer :: n, i
logical :: success, switch
if (present (input)) then
  n = size (stream_fmt) + 1
else
  n = size (stream_fmt)
end if
if (present (input_sample)) then
  sample_in = input_sample
else
  sample_in = sample
end if
if (present (allow_switch)) then
  switch = allow_switch
else
  switch = .true.
end if
if (present (error)) then
  error = .false.
end if
if (present (checkpoint)) then
  allocate (es_array%entry (n + 1))
  call dispatch_eio &
    (es_array%entry(n+1)%eio, var_str ("checkpoint"), global)
  call es_array%entry(n+1)%eio%init_out (sample, data)
else
  allocate (es_array%entry (n))
end if
if (present (input)) then
  call dispatch_eio (es_array%entry(n)%eio, input, global)
  if (present (input_data)) then
    call es_array%entry(n)%eio%init_in (sample_in, input_data, success)
```

```

else
    call es_array%entry(n)%eio%init_in (sample_in, data, success)
end if
if (success) then
    es_array%i_in = n
else if (present (input_sample)) then
    if (present (error)) then
        error = .true.
    else
        call msg_fatal ("Events: &
                        &parameter mismatch in input, aborting")
    end if
else
    call msg_message ("Events: &
                    &parameter mismatch, discarding old event set")
    call es_array%entry(n)%eio%final ()
    if (switch) then
        call msg_message ("Events: generating new events")
        call es_array%entry(n)%eio%init_out (sample, data)
    end if
end if
end if
do i = 1, size (stream_fmt)
    call dispatch_eio (es_array%entry(i)%eio, stream_fmt(i), global)
    call es_array%entry(i)%eio%init_out (sample, data)
end do
end subroutine event_stream_array_init

```

Switch the (only) input channel to an output channel, so further events are appended to the respective stream.

```

(Event streams: event stream array: TBP)+≡
    procedure :: switch_inout => event_stream_array_switch_inout

(Event streams: procedures)+≡
    subroutine event_stream_array_switch_inout (es_array)
        class(event_stream_array_t), intent(inout) :: es_array
        integer :: n
        if (es_array%has_input ()) then
            n = es_array%i_in
            call es_array%entry(n)%eio%switch_inout ()
            es_array%i_in = 0
        else
            call msg_bug ("Reading events: switch_inout: no input stream selected")
        end if
    end subroutine event_stream_array_switch_inout

```

Output an event (with given process number) to all output streams. If there is no output stream, do nothing.

```

(Event streams: event stream array: TBP)+≡
    procedure :: output => event_stream_array_output

(Event streams: procedures)+≡
    subroutine event_stream_array_output (es_array, event, i_prc, &
                                         event_index, passed, pacify)

```

```

class(event_stream_array_t), intent(inout) :: es_array
type(event_t), intent(in), target :: event
integer, intent(in) :: i_prc, event_index
logical, intent(in), optional :: passed, pacify
logical :: increased
integer :: i
do i = 1, size (es_array%entry)
  if (i /= es_array%i_in) then
    associate (eio => es_array%entry(i)%eio)
      if (eio%split) then
        if (eio%split_n_evt > 0 &
            .and. event_index > 1 &
            .and. mod (event_index, eio%split_n_evt) == 1) then
          call eio%split_out ()
        else if (eio%split_n_kbytes > 0) then
          call eio%update_split_count (increased)
          if (increased) call eio%split_out ()
        end if
      end if
      call eio%output (event, i_prc, reading = es_array%i_in /= 0, &
        passed = passed, &
        pacify = pacify)
    end associate
  end if
end do
end subroutine event_stream_array_output

```

Input the `i_prc` index which selects the process for the current event. This is separated from reading the event, because it determines which event record to read. `iostat` may indicate an error or an EOF condition, as usual.

```

(Event streams: event stream array: TBP)+≡
  procedure :: input_i_prc => event_stream_array_input_i_prc

(Event streams: procedures)+≡
  subroutine event_stream_array_input_i_prc (es_array, i_prc, iostat)
    class(event_stream_array_t), intent(inout) :: es_array
    integer, intent(out) :: i_prc
    integer, intent(out) :: iostat
    integer :: n
    if (es_array%has_input ()) then
      n = es_array%i_in
      call es_array%entry(n)%eio%input_i_prc (i_prc, iostat)
    else
      call msg_fatal ("Reading events: no input stream selected")
    end if
  end subroutine event_stream_array_input_i_prc

```

Input an event from the selected input stream. `iostat` may indicate an error or an EOF condition, as usual.

```

(Event streams: event stream array: TBP)+≡
  procedure :: input_event => event_stream_array_input_event

(Event streams: procedures)+≡
  subroutine event_stream_array_input_event (es_array, event, iostat)

```

```

class(event_stream_array_t), intent(inout) :: es_array
type(event_t), intent(inout), target :: event
integer, intent(out) :: iostat
integer :: n
if (es_array%has_input ()) then
    n = es_array%i_in
    call es_array%entry(n)%eio%input_event (event, iostat)
else
    call msg_fatal ("Reading events: no input stream selected")
end if
end subroutine event_stream_array_input_event

```

Return true if there is an input channel among the event streams.

```

<Event streams: event stream array: TBP>+≡
    procedure :: has_input => event_stream_array_has_input

<Event streams: procedures>+≡
    function event_stream_array_has_input (es_array) result (flag)
        class(event_stream_array_t), intent(in) :: es_array
        logical :: flag
        flag = es_array%i_in /= 0
    end function event_stream_array_has_input

```

28.13.2 Unit Tests

```

<Event streams: public>+≡
    public :: event_streams_test

<Event streams: tests>≡
    subroutine event_streams_test (u, results)
        integer, intent(in) :: u
        type(test_results_t), intent(inout) :: results
    <Event streams: execute tests>
    end subroutine event_streams_test

```

Empty event stream

This should set up an empty event output stream array, including initialization, output, and finalization (which are all no-ops).

```

<Event streams: execute tests>≡
    call test (event_streams_1, "event_streams_1", &
        "empty event stream array", &
        u, results)

<Event streams: tests>+≡
    subroutine event_streams_1 (u)
        integer, intent(in) :: u
        type(event_stream_array_t) :: es_array
        type(rt_data_t) :: global
        type(event_t) :: event
        type(string_t) :: sample
        type(string_t), dimension(0) :: empty_string_array

```

```

write (u, "(A)")  "* Test output: event_streams_1"
write (u, "(A)")  "* Purpose: handle empty event stream array"
write (u, "(A)")

sample = "event_streams_1"

call es_array%init (sample, empty_string_array, global)
call es_array%output (event, 42, 1)
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: event_streams_1"

end subroutine event_streams_1

```

Nontrivial event stream

Here we generate a trivial event and choose raw output as an entry in the stream array.

```

<Event streams: execute tests>+≡
  call test (event_streams_2, "event_streams_2", &
    "nontrivial event stream array", &
    u, results)

<Event streams: tests>+≡
  subroutine event_streams_2 (u)
    integer, intent(in) :: u
    type(event_stream_array_t) :: es_array
    type(rt_data_t) :: global
    type(model_data_t), target :: model
    type(event_t), allocatable, target :: event
    type(process_t), allocatable, target :: process
    type(process_instance_t), allocatable, target :: process_instance
    type(string_t) :: sample
    type(string_t), dimension(0) :: empty_string_array
    integer :: i_prc, iostat

    write (u, "(A)")  "* Test output: event_streams_2"
    write (u, "(A)")  "* Purpose: handle empty event stream array"
    write (u, "(A)")

    call syntax_model_file_init ()
    call global%global_init ()
    call global%init_fallback_model &
      (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

    call model%init_test ()

    write (u, "(A)")  "* Generate test process event"
    write (u, "(A)")

```

```

allocate (process)
allocate (process_instance)
call prepare_test_process (process, process_instance, model)
call process_instance%setup_event_data ()

allocate (event)
call event%basic_init ()
call event%connect (process_instance, process%get_model_ptr ())
call event%generate (1, [0.4_default, 0.4_default])
call event%evaluate_expressions ()
call event%write (u)

write (u, "(A)")
write (u, "(A)") "* Allocate raw eio stream and write event to file"
write (u, "(A)")

sample = "event_streams_2"

call es_array%init (sample, [var_str ("raw")], global)
call es_array%output (event, 1, 1)
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
write (u, "(A)") "* Reallocate raw eio stream for reading"
write (u, "(A)")

sample = "foo"
call es_array%init (sample, empty_string_array, global, &
    input = var_str ("raw"), input_sample = var_str ("event_streams_2"))
call es_array%write (u)

write (u, "(A)")
write (u, "(A)") "* Reread event"
write (u, "(A)")

call es_array%input_i_prc (i_prc, iostat)

write (u, "(1x,A,I0)") "i_prc = ", i_prc
write (u, "(A)")
call es_array%input_event (event, iostat)
call es_array%final ()

call event%write (u)

call global%final ()

call model%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)") "* Test output end: event_streams_2"

end subroutine event_streams_2

```

Switch in/out

Here we generate an event file and test switching from writing to reading when the file is exhausted.

```
(Event streams: execute tests)+≡
  call test (event_streams_3, "event_streams_3", &
    "switch input/output", &
    u, results)

(Event streams: tests)+≡
  subroutine event_streams_3 (u)
    integer, intent(in) :: u
    type(event_stream_array_t) :: es_array
    type(rt_data_t) :: global
    type(model_data_t), target :: model
    type(event_t), allocatable, target :: event
    type(process_t), allocatable, target :: process
    type(process_instance_t), allocatable, target :: process_instance
    type(string_t) :: sample
    type(string_t), dimension(0) :: empty_string_array
    integer :: i_prc, iostat

    write (u, "(A)")  "* Test output: event_streams_3"
    write (u, "(A)")  "* Purpose: handle in/out switching"
    write (u, "(A)")

    call syntax_model_file_init ()
    call global%global_init ()
    call global%init_fallback_model &
      (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

    call model%init_test ()

    write (u, "(A)")  "* Generate test process event"
    write (u, "(A)")

    allocate (process)
    allocate (process_instance)
    call prepare_test_process (process, process_instance, model)
    call process_instance%setup_event_data ()

    allocate (event)
    call event%basic_init ()
    call event%connect (process_instance, process%get_model_ptr ())
    call event%generate (1, [0.4_default, 0.4_default])
    call event%evaluate_expressions ()

    write (u, "(A)")  "* Allocate raw eio stream and write event to file"
    write (u, "(A)")

    sample = "event_streams_3"
```



```

call es_array%init (sample, [var_str ("raw")], global)
call es_array%output (event, 1, 1)
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
write (u, "(A)") "* Reallocate raw eio stream for reading"
write (u, "(A)")

call es_array%init (sample, empty_string_array, global, &
    input = var_str ("raw"))
call es_array%write (u)

write (u, "(A)")
write (u, "(A)") "* Reread event"
write (u, "(A)")

call es_array%input_i_prc (i_prc, iostat)
call es_array%input_event (event, iostat)

write (u, "(A)") "* Attempt to read another event (fail), then generate"
write (u, "(A)")

call es_array%input_i_prc (i_prc, iostat)
if (iostat < 0) then
    call es_array%switch_inout ()
    call event%generate (1, [0.3_default, 0.3_default])
    call event%evaluate_expressions ()
    call es_array%output (event, 1, 2)
end if
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
call event%write (u)

write (u, "(A)")
write (u, "(A)") "* Reallocate raw eio stream for reading"
write (u, "(A)")

call es_array%init (sample, empty_string_array, global, &
    input = var_str ("raw"))
call es_array%write (u)

write (u, "(A)")
write (u, "(A)") "* Reread two events and display 2nd event"
write (u, "(A)")

call es_array%input_i_prc (i_prc, iostat)
call es_array%input_event (event, iostat)
call es_array%input_i_prc (i_prc, iostat)

call es_array%input_event (event, iostat)
call es_array%final ()

```

```

call event%write (u)

call global%final ()

call model%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: event_streams_3"

end subroutine event_streams_3

```

Checksum

Here we generate an event file and repeat twice, once with identical parameters and once with modified parameters.

```

(Event streams: execute tests)+≡
  call test (event_streams_4, "event_streams_4", &
    "check MD5 sum", &
    u, results)

(Event streams: tests)+≡
  subroutine event_streams_4 (u)
    integer, intent(in) :: u
    type(event_stream_array_t) :: es_array
    type(rt_data_t) :: global
    type(process_t), allocatable, target :: process
    type(string_t) :: sample
    type(string_t), dimension(0) :: empty_string_array
    type(event_sample_data_t) :: data

    write (u, "(A)")  "* Test output: event_streams_4"
    write (u, "(A)")  "* Purpose: handle in/out switching"
    write (u, "(A)")

    write (u, "(A)")  "* Generate test process event"
    write (u, "(A)")

    call syntax_model_file_init ()
    call global%global_init ()
    call global%init_fallback_model &
      (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

    call global%set_log (var_str ("?check_event_file"), &
      .true., is_known = .true.)

    allocate (process)

    write (u, "(A)")  "* Allocate raw eio stream for writing"
    write (u, "(A)")

    sample = "event_streams_4"

```

```

data%md5sum_cfg = "1234567890abcdef1234567890abcdef"

call es_array%init (sample, [var_str ("raw")], global, data)
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
write (u, "(A)") "* Reallocate raw eio stream for reading"
write (u, "(A)")

call es_array%init (sample, empty_string_array, global, &
    data, input = var_str ("raw"))
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
write (u, "(A)") "* Reallocate modified raw eio stream for reading (fail)"
write (u, "(A)")

data%md5sum_cfg = "1234567890_____1234567890_____"
call es_array%init (sample, empty_string_array, global, &
    data, input = var_str ("raw"))
call es_array%write (u)
call es_array%final ()

write (u, "(A)")
write (u, "(A)") "* Repeat ignoring checksum"
write (u, "(A)")

call global%set_log (var_str ("?check_event_file"), &
    .false., is_known = .true.)
call es_array%init (sample, empty_string_array, global, &
    data, input = var_str ("raw"))
call es_array%write (u)
call es_array%final ()

call global%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)") "* Test output end: event_streams_4"

end subroutine event_streams_4

```

28.14 Simulation

This module manages simulation: event generation and reading/writing of event files. The `simulation` object is intended to be used (via a pointer) outside of WHIZARD, if events are generated individually by an external driver.

```
<simulations.f90>≡  
  <File header>  
  
  module simulations  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use format_utils, only: write_separator  
    use format_defs, only: FMT_19  
    use unit_tests  
    use diagnostics  
    use sm_qcd  
    use md5  
    use ifiles  
    use lexers  
    use parser  
    use variables  
    use eval_trees  
    use model_data  
    use flavors  
    use particles  
    use state_matrices  
    use interactions  
    use models  
    use beams  
    use phs_forests  
    use rng_base  
    use selectors  
    use prc_core  
    use prclib_stacks  
    use processes  
    use event_base  
    use events  
    use event_transforms  
    use decays  
    use shower  
    use eio_data  
    use eio_base  
    use eio_raw  
    use eio_ascii  
    use rt_data  
    use dispatch  
    use process_configurations  
    use compilations  
    use integrations  
    use event_streams  
    <Standard module head>
```

```

    <Simulations: public>

    <Simulations: types>

    <Simulations: interfaces>

contains

    <Simulations: procedures>

    <Simulations: tests>

end module simulations

```

28.14.1 Event counting

In this object we collect statistical information about an event sample or sub-sample.

```

<Simulations: types>≡
    type :: counter_t
        integer :: total = 0
        integer :: generated = 0
        integer :: read = 0
        integer :: positive = 0
        integer :: negative = 0
        integer :: zero = 0
        integer :: excess = 0
        real(default) :: max_excess = 0
        real(default) :: sum_excess = 0
    contains
        <Simulations: counter: TBP>
    end type counter_t

```

Output.

```

<Simulations: counter: TBP>≡
    procedure :: write => counter_write

<Simulations: procedures>≡
    subroutine counter_write (object, unit)
        class(counter_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
1    format (3x,A,I0)
2    format (5x,A,I0)
3    format (5x,A,ES19.12)
        write (u, 1) "Events total      = ", object%total
        write (u, 2) "generated      = ", object%generated
        write (u, 2) "read          = ", object%read
        write (u, 2) "positive weight = ", object%positive
        write (u, 2) "negative weight = ", object%negative
        write (u, 2) "zero weight   = ", object%zero
        write (u, 2) "excess weight  = ", object%excess
    end subroutine counter_write

```

```

        if (object%excess /= 0) then
            write (u, 3) "max excess      = ", object%max_excess
            write (u, 3) "avg excess       = ", object%sum_excess / object%total
        end if
    end subroutine counter_write

```

This is a screen message: if there was an excess, display statistics.

```

<Simulations: counter: TBP>+≡
    procedure :: show_excess => counter_show_excess

<Simulations: procedures>+≡
    subroutine counter_show_excess (counter)
        class(counter_t), intent(in) :: counter
        if (counter%excess > 0) then
            write (msg_buffer, "(A,1x,I0,1x,A,1x,'(,F7.3,' %)'") &
                "Encountered events with excess weight:", counter%excess, &
                "events", 100 * counter%excess / real (counter%total)
            call msg_warning ()
            write (msg_buffer, "(A,ES10.3)") &
                "Maximum excess weight =", counter%max_excess
            call msg_message ()
            write (msg_buffer, "(A,ES10.3)") &
                "Average excess weight =", counter%sum_excess / counter%total
            call msg_message ()
        end if
    end subroutine counter_show_excess

```

Count an event. The weight and event source are optional; by default we assume that the event has been generated and has positive weight.

```

<Simulations: counter: TBP>+≡
    procedure :: record => counter_record

<Simulations: procedures>+≡
    subroutine counter_record (counter, weight, excess, from_file)
        class(counter_t), intent(inout) :: counter
        real(default), intent(in), optional :: weight, excess
        logical, intent(in), optional :: from_file
        counter%total = counter%total + 1
        if (present (from_file)) then
            if (from_file) then
                counter%read = counter%read + 1
            else
                counter%generated = counter%generated + 1
            end if
        else
            counter%generated = counter%generated + 1
        end if
        if (present (weight)) then
            if (weight > 0) then
                counter%positive = counter%positive + 1
            else if (weight < 0) then
                counter%negative = counter%negative + 1
            else
                counter%zero = counter%zero + 1
            end if
        end if
    end subroutine counter_record

```

```

        end if
    else
        counter%positive = counter%positive + 1
    end if
    if (present (excess)) then
        if (excess > 0) then
            counter%excess = counter%excess + 1
            counter%max_excess = max (counter%max_excess, excess)
            counter%sum_excess = counter%sum_excess + excess
        end if
    end if
end subroutine counter_record

```

28.14.2 Simulation: component sets

For each set of process components that share a MCI entry in the process configuration, we keep a separate event record.

```

<Simulations: types>+≡
type :: mci_set_t
    private
    integer :: n_components = 0
    integer, dimension(:), allocatable :: i_component
    type(string_t), dimension(:), allocatable :: component_id
    logical :: has_integral = .false.
    real(default) :: integral = 0
    real(default) :: error = 0
    real(default) :: weight_mci = 0
    type(counter_t) :: counter
    contains
    <Simulations: mci set: TBP>
end type mci_set_t

```

Output.

```

<Simulations: mci set: TBP>≡
procedure :: write => mci_set_write

<Simulations: procedures>+≡
subroutine mci_set_write (object, unit)
    class(mci_set_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    write (u, "(3x,A)") "Components:"
    do i = 1, object%n_components
        write (u, "(5x,I0,A,A,A)") object%i_component(i), &
            ": ", char (object%component_id(i)), ""
    end do
    if (object%has_integral) then
        write (u, "(3x,A," // FMT_19 // ")") "Integral = ", object%integral
        write (u, "(3x,A," // FMT_19 // ")") "Error = ", object%error
        write (u, "(3x,A,F13.10)") "Weight = ", object%weight_mci
    else

```

```

        write (u, "(3x,A)") "Integral = [undefined]"
    end if
    call object%counter%write (u)
end subroutine mci_set_write

```

Initialize: Get the indices and names for the process components that will contribute to this set.

```

<Simulations: mci set: TBP>+≡
    procedure :: init => mci_set_init

<Simulations: procedures>+≡
    subroutine mci_set_init (object, i_mci, process)
        class(mci_set_t), intent(out) :: object
        integer, intent(in) :: i_mci
        type(process_t), intent(in), target :: process
        integer :: i
        call process%get_i_component (i_mci, object%i_component)
        object%n_components = size (object%i_component)
        allocate (object%component_id (object%n_components))
        do i = 1, size (object%component_id)
            object%component_id(i) = &
                process%get_component_id (object%i_component(i))
        end do
        if (process%has_integral (i_mci)) then
            object%integral = process%get_integral (i_mci)
            object%error = process%get_error (i_mci)
            object%has_integral = .true.
        end if
    end subroutine mci_set_init

```

28.14.3 Process-core Safe

This is an object that temporarily holds a process core object. We need this while rescanning a process with modified parameters. After the rescan, we want to restore the original state.

```

<Simulations: types>+≡
    type :: core_safe_t
        class(prc_core_t), allocatable :: core
    end type core_safe_t

```

28.14.4 Process Object

The simulation works on process objects. This subroutine makes a process object available for simulation. The process is in the process stack. If integration is not yet done, do it. Any generated process object should be put on the global stack, if it is separate from the local one.

```

<Simulations: procedures>+≡
    subroutine prepare_process &
        (process, process_id, integrate, local, global)
        type(process_t), pointer, intent(out) :: process

```



```

type(string_t), intent(in) :: process_id
logical, intent(in) :: integrate
type(rt_data_t), intent(inout), target :: local
type(rt_data_t), intent(inout), optional, target :: global
if (present (global)) then
    process => global%process_stack%get_process_ptr (process_id)
else
    process => local%process_stack%get_process_ptr (process_id)
end if
if (.not. associated (process)) then
    if (integrate) then
        call msg_message ("Simulate: process '" &
            // char (process_id) // "' needs integration")
    else
        call msg_message ("Simulate: process '" &
            // char (process_id) // "' needs initialization")
    end if
    if (present (global)) then
        call integrate_process (process_id, local, global, &
            init_only = .not. integrate)
    else
        call integrate_process (process_id, local, local_stack=.true., &
            init_only = .not. integrate)
    end if
    if (signal_is_pending ()) return
    process => global%process_stack%get_process_ptr (process_id)
    if (associated (process)) then
        if (integrate) then
            call msg_message ("Simulate: integration done")
            call global%process_stack%fill_result_vars (process_id)
        else
            call msg_message ("Simulate: process initialization done")
        end if
    else
        call msg_fatal ("Simulate: process '" &
            // char (process_id) // "' could not be initialized: aborting")
    end if
end if
end subroutine prepare_process

```

28.14.5 Simulation entry

For each process that we consider for event generation, we need a separate entry. The entry separately records the process ID and run ID. The `weight_mci` array is used for selecting a component set (which shares a MCI record inside the process container) when generating an event for the current process.

The simulation entry is an extension of the `event_t` event record. This core object contains configuration data, pointers to the process and process instance, the expressions, flags and values that are evaluated at runtime, and the resulting particle set.

The entry explicitly allocate the `process_instance`, which becomes the process-specific workspace for the event record.

If entries with differing environments are present simultaneously, we may need to switch QCD parameters and/or the model event by event. In this case, the qcd and/or model components are present.

```

<Simulations: types>+≡
type, extends (event_t) :: entry_t
private
type(string_t) :: process_id
type(string_t) :: library
type(string_t) :: run_id
logical :: has_integral = .false.
real(default) :: integral = 0
real(default) :: error = 0
real(default) :: process_weight = 0
logical :: valid = .false.
type(counter_t) :: counter
integer :: n_in = 0
integer :: n_mci = 0
type(mci_set_t), dimension(:), allocatable :: mci_set
type(selector_t) :: mci_selector
type(core_safe_t), dimension(:), allocatable :: core_safe
class(model_data_t), pointer :: model => null ()
type(qcd_t) :: qcd
logical :: nlo_event = .false.
contains
<Simulations: entry: TBP>
end type entry_t

```

Output. Write just the configuration, the event is written by a separate routine.

The verbose option is unused, it is required by the interface of the base-object method.

```

<Simulations: entry: TBP>≡
procedure :: write_config => entry_write_config

<Simulations: procedures>+≡
subroutine entry_write_config (object, unit)
class(entry_t), intent(in) :: object
integer, intent(in), optional :: unit
integer :: u, i
u = given_output_unit (unit)
write (u, "(3x,A,A,A)") "Process   = '", char (object%process_id), "'"
write (u, "(3x,A,A,A)") "Library   = '", char (object%library), "'"
write (u, "(3x,A,A,A)") "Run       = '", char (object%run_id), "'"
write (u, "(3x,A,L1)")  "is valid  = ", object%valid
if (object%has_integral) then
write (u, "(3x,A," // FMT_19 // ")") "Integral = ", object%integral
write (u, "(3x,A," // FMT_19 // ")") "Error    = ", object%error
write (u, "(3x,A,F13.10)") "Weight   =", object%process_weight
else
write (u, "(3x,A)") "Integral = [undefined]"
end if
write (u, "(3x,A,I0)") "MCI sets = ", object%n_mci
call object%counter%write (u)
do i = 1, size (object%mci_set)
write (u, "(A)")

```

```

        write (u, "(1x,A,IO,A)") "MCI set #", i, ":"
        call object%mci_set(i)%write (u)
    end do
    if (allocated (object%core_safe)) then
        do i = 1, size (object%core_safe)
            write (u, "(1x,A,IO,A)") "Saved process-component core #", i, ":"
            call object%core_safe(i)%core%write (u)
        end do
    end if
end subroutine entry_write_config

```

Finalizer. The *instance* pointer component of the *event_t* base type points to a target which we did explicitly allocate in the *entry_init* procedure. Therefore, we finalize and explicitly deallocate it here. Then we call the finalizer of the base type.

```

<Simulations: entry: TBP>+≡
    procedure :: final => entry_final

<Simulations: procedures>+≡
    subroutine entry_final (object)
        class(entry_t), intent(inout) :: object
        integer :: i
        if (associated (object%instance)) then
            do i = 1, object%n_mci
                call object%instance%final_simulation (i)
            end do
            call object%instance%final ()
            deallocate (object%instance)
        end if
        call object%event_t%final ()
    end subroutine entry_final

```

Initialization. Search for a process entry and allocate a process instance as an anonymous object, temporarily accessible via the *process_instance* pointer. Assign data by looking at the process object and at the environment.

If *n_alt* is set, we prepare for additional alternate sqme and weight entries.

If the process object is not found initially: if *integrate* is set, attempt an integration pass and try again. Otherwise, just initialize the object.

If *generate* is set, prepare the MCI objects for generating new events. For pure rescanning, this is not necessary.

When done, we assign the *instance* and *process* pointers of the base type by the *connect* method, so we can reference them later.

```

<Simulations: entry: TBP>+≡
    procedure :: init => entry_init

<Simulations: procedures>+≡
    subroutine entry_init &
        (entry, process_id, integrate, generate, update_sqme, &
         local, global, n_alt)
        class(entry_t), intent(inout), target :: entry
        type(string_t), intent(in) :: process_id
        logical, intent(in) :: integrate, generate, update_sqme
        type(rt_data_t), intent(inout), target :: local

```

```

type(rt_data_t), intent(inout), optional, target :: global
integer, intent(in), optional :: n_alt
type(process_t), pointer :: process, master_process
type(process_instance_t), pointer :: process_instance
integer :: i
logical :: combined_integration

call prepare_process (master_process, process_id, integrate, local, global)
if (signal_is_pending ()) return

if (.not. master_process%has_matrix_element ()) then
    entry%has_integral = .true.
    entry%process_id = process_id
    entry%valid = .false.
    return
end if

call entry%basic_init (local%var_list, n_alt)

entry%process_id = process_id
if (generate .or. integrate) then
    entry%run_id = master_process%get_run_id ()
    process => master_process
else
    call local%set_log (var_str ("?rebuild_phase_space"), &
        .false., is_known = .true.)
    call local%set_log (var_str ("?check_phs_file"), &
        .false., is_known = .true.)
    call local%set_log (var_str ("?rebuild_grids"), &
        .false., is_known = .true.)
    entry%run_id = &
        local%var_list%get_sval (var_str ("$_run_id"))
    if (update_sqme) then
        call prepare_local_process (process, process_id, local)
    else
        process => master_process
    end if
end if

call entry%import_process_characteristics (process)

allocate (entry%mci_set (entry%n_mci))
do i = 1, size (entry%mci_set)
    call entry%mci_set(i)%init (i, master_process)
end do
if (process%is_nlo_calculation ()) then
    entry%nlo_event = .true.
    call entry%combine_mci_sets ()
end if

call entry%import_process_results (master_process)
call entry%prepare_expressions (local)

combined_integration = local%get_lval (var_str ("?combined_nlo_integration"))

```

```

call prepare_process_instance (process_instance, process, local%model, &
                             combined_integration = combined_integration)
if (generate) then
  do i = 1, entry%n_mci
    call process%prepare_simulation (i)
    call process_instance%init_simulation (i, entry%config%safety_factor)
  end do
end if
call entry%setup_event_transforms (process, local)
call dispatch_qcd (entry%qcd, local)

call entry%connect_qcd ()

if (present (global)) then
  call entry%connect (process_instance, local%model, global%process_stack)
else
  call entry%connect (process_instance, local%model, local%process_stack)
end if
call entry%setup_expressions ()

entry%model => process%get_model_ptr ()
entry%valid = .true.

end subroutine entry_init

```

Part of simulation-entry initialization: set up a process object for local use.

(Simulations: procedures) +=

```

subroutine prepare_local_process (process, process_id, local)
  type(process_t), pointer, intent(inout) :: process
  type(string_t), intent(in) :: process_id
  type(rt_data_t), intent(inout), target :: local
  type(integration_t) :: intg
  call intg%create_process (process_id)
  call intg%init_process (local)
  call intg%setup_process (local, verbose=.false.)
  process => intg%get_process_ptr ()
end subroutine prepare_local_process

```

Part of simulation-entry initialization: set up a process instance matching the selected process object.

The model that we can provide as an extra argument can modify particle settings (polarization) in the density matrices that will be constructed. It does not affect parameters.

(Simulations: procedures) +=

```

subroutine prepare_process_instance (process_instance, process, model, combined_integration)
  type(process_instance_t), pointer, intent(inout) :: process_instance
  type(process_t), intent(inout), target :: process
  class(model_data_t), intent(in), optional :: model
  logical, intent(in), optional :: combined_integration
  allocate (process_instance)
  if (process%is_nlo_calculation ()) then
    call process_instance%init (process, combined_integration = combined_integration)
  end if
end subroutine prepare_process_instance

```

```

        call setup_nlo_component_cores (process)
    else
        call process_instance%init (process)
    end if
    call process_instance%setup_event_data (model)
end subroutine prepare_process_instance

```

Part of simulation-entry initialization: query the process for basic information.

```

⟨Simulations: entry: TBP⟩+≡
    procedure, private :: import_process_characteristics &
        => entry_import_process_characteristics

⟨Simulations: procedures⟩+≡
    subroutine entry_import_process_characteristics (entry, process)
        class(entry_t), intent(inout) :: entry
        type(process_t), intent(in), target :: process
        entry%library = process%get_library_name ()
        entry%n_in = process%get_n_in ()
        entry%n_mci = process%get_n_mci ()
    end subroutine entry_import_process_characteristics

```

Part of simulation-entry initialization: query the process for integration results.

```

⟨Simulations: entry: TBP⟩+≡
    procedure, private :: import_process_results &
        => entry_import_process_results

⟨Simulations: procedures⟩+≡
    subroutine entry_import_process_results (entry, process)
        class(entry_t), intent(inout) :: entry
        type(process_t), intent(in), target :: process
        if (process%has_integral ()) then
            entry%integral = process%get_integral ()
            entry%error = process%get_error ()
            call entry%set_sigma (entry%integral)
            entry%has_integral = .true.
        end if
    end subroutine entry_import_process_results

```

Part of simulation-entry initialization: create expression factory objects and store them.

```

⟨Simulations: entry: TBP⟩+≡
    procedure, private :: prepare_expressions &
        => entry_prepare_expressions

⟨Simulations: procedures⟩+≡
    subroutine entry_prepare_expressions (entry, local)
        class(entry_t), intent(inout) :: entry
        type(rt_data_t), intent(in), target :: local
        type(eval_tree_factory_t) :: expr_factory
        call expr_factory%init (local%pn%selection_lexpr)
        call entry%set_selection (expr_factory)
        call expr_factory%init (local%pn%reweight_expr)
        call entry%set_reweight (expr_factory)
        call expr_factory%init (local%pn%analysis_lexpr)
    end subroutine entry_prepare_expressions

```

```

    call entry%set_analysis (expr_factory)
end subroutine entry_prepare_expressions

```

Part of simulation-entry initialization: dispatch event transforms (decay, shower) as requested.

```

<Simulations: entry: TBP>+≡
  procedure, private :: setup_event_transforms &
    => entry_setup_event_transforms

<Simulations: procedures>+≡
  subroutine entry_setup_event_transforms (entry, process, local)
    class(entry_t), intent(inout) :: entry
    type(process_t), intent(inout), target :: process
    type(rt_data_t), intent(in), target :: local
    class(evt_t), pointer :: evt
    logical :: enable_shower
    if (process%contains_unstable (local%model)) then
      call dispatch_evt_decay (evt, local)
      if (associated (evt)) call entry%import_transform (evt)
    end if
    enable_shower = local%get_lval (var_str ("?allow_shower")) .and. &
      (local%get_lval (var_str ("?ps_isr_active")) &
        .or. local%get_lval (var_str ("?ps_fsr_active")) &
        .or. local%get_lval (var_str ("?muli_active")) &
        .or. local%get_lval (var_str ("?mlm_matching")) &
        .or. local%get_lval (var_str ("?ckkw_matching")) &
        .or. local%get_lval (var_str ("?powheg_matching")))
    if (enable_shower) then
      call dispatch_evt_shower (evt, local, process)
      call entry%import_transform (evt)
    end if
    if (local%get_lval (var_str ("?hadronization_active"))) then
      call dispatch_evt_hadrons (evt, local, process)
      call entry%import_transform (evt)
    end if
  end subroutine entry_setup_event_transforms

```

Compute weights. The integral in the argument is the sum of integrals for all processes in the sample. After computing the process weights, we repeat the normalization procedure for the process components.

```

<Simulations: entry: TBP>+≡
  procedure :: init_mci_selector => entry_init_mci_selector

<Simulations: procedures>+≡
  subroutine entry_init_mci_selector (entry)
    class(entry_t), intent(inout) :: entry
    integer :: i
    if (entry%has_integral) then
      call entry%mci_selector%init (entry%mci_set%integral)
      do i = 1, entry%n_mci
        entry%mci_set(i)%weight_mci = entry%mci_selector%get_weight (i)
      end do
    end if
  end subroutine entry_init_mci_selector

```

Select a MCI entry, using the embedded random-number generator.

```

<Simulations: entry: TBP>+≡
  procedure :: select_mci => entry_select_mci

<Simulations: procedures>+≡
  function entry_select_mci (entry) result (i_mci)
    class(entry_t), intent(inout) :: entry
    integer :: i_mci
    call entry%mci_selector%generate (entry%rng, i_mci)
  end function entry_select_mci

```

Record an event for this entry, i.e., increment the appropriate counters.

```

<Simulations: entry: TBP>+≡
  procedure :: record => entry_record

<Simulations: procedures>+≡
  subroutine entry_record (entry, i_mci, from_file)
    class(entry_t), intent(inout) :: entry
    integer, intent(in) :: i_mci
    logical, intent(in), optional :: from_file
    real(default) :: weight, excess
    weight = entry%get_weight_prc ()
    excess = entry%get_excess_prc ()
    call entry%counter%record (weight, excess, from_file)
    call entry%mci_set(i_mci)%counter%record (weight, excess)
  end subroutine entry_record

```

Update and restore the process core that this entry accesses, when parameters change. If explicit arguments `model`, `qcd`, or `helicity_selection` are provided, use those. Otherwise use the parameters stored in the process object.

```

<Simulations: entry: TBP>+≡
  procedure :: update_process => entry_update_process
  procedure :: restore_process => entry_restore_process

<Simulations: procedures>+≡
  subroutine entry_update_process (entry, model, qcd, helicity_selection)
    class(entry_t), intent(inout) :: entry
    class(model_data_t), intent(in), optional, target :: model
    type(qcd_t), intent(in), optional :: qcd
    type(helicity_selection_t), intent(in), optional :: helicity_selection
    type(process_t), pointer :: process
    class(prc_core_t), allocatable :: core
    integer :: i, n_components
    class(model_data_t), pointer :: model_local
    type(qcd_t) :: qcd_local
    if (present (model)) then
      model_local => model
    else
      model_local => entry%model
    end if
    if (present (qcd)) then
      qcd_local = qcd
    end if
  end subroutine entry_update_process

```



```

else
    qcd_local = entry%qcd
end if
process => entry%get_process_ptr ()
n_components = process%get_n_components ()
allocate (entry%core_safe (n_components))
do i = 1, n_components
    if (process%has_matrix_element (i)) then
        call process%extract_component_core (i, core)
        call dispatch_core_update (core, &
            model_local, helicity_selection, qcd_local, &
            entry%core_safe(i)%core)
        call process%restore_component_core (i, core)
    end if
end do
end subroutine entry_update_process

subroutine entry_restore_process (entry)
    class(entry_t), intent(inout) :: entry
    type(process_t), pointer :: process
    class(prc_core_t), allocatable :: core
    integer :: i, n_components
    process => entry%get_process_ptr ()
    n_components = process%get_n_components ()
    do i = 1, n_components
        if (process%has_matrix_element (i)) then
            call process%extract_component_core (i, core)
            call dispatch_core_restore (core, entry%core_safe(i)%core)
            call process%restore_component_core (i, core)
        end if
    end do
    deallocate (entry%core_safe)
end subroutine entry_restore_process

```

(Simulations: entry: TBP)+≡

```

procedure :: combine_mci_sets => entry_combine_mci_sets

```

(Simulations: procedures)+≡

```

subroutine entry_combine_mci_sets (entry)
    class(entry_t), intent(inout) :: entry
    integer :: n_components_lo, i_component, i_virt
    n_components_lo = entry%n_mci / 3
    do i_component = 1, n_components_lo
        i_virt = i_component + 2*n_components_lo
        entry%mci_set(i_component)%integral = &
            entry%mci_set(i_component)%integral + entry%mci_set(i_virt)%integral
        entry%mci_set(i_component)%error = sqrt (&
            entry%mci_set(i_component)%error**2 + entry%mci_set(i_virt)%error**2)
        entry%mci_set(i_virt)%integral = 0._default
        entry%mci_set(i_virt)%has_integral = .false.
    end do
end subroutine entry_combine_mci_sets

```

(Simulations: entry: TBP)+≡

```

procedure :: connect_qcd => entry_connect_qcd
<Simulations: procedures>+≡
subroutine entry_connect_qcd (entry)
  class(entry_t), intent(inout), target :: entry
  class(evt_t), pointer :: evt
  evt => entry%transform_first
  do while (associated (evt))
    select type (evt)
      type is (evt_shower_t)
        evt%qcd => entry%qcd
        if (evt%settings%powheg_matching) then
          evt%powheg%qcd => entry%qcd
          call evt%powheg%compute_lambda2_gen ()
        end if
      end select
    evt => evt%next
  end do
end subroutine entry_connect_qcd

```

28.14.6 Entries for alternative environment

Entries for alternate environments. [No additional components anymore, so somewhat redundant.]

```

<Simulations: types>+≡
type, extends (entry_t) :: alt_entry_t
contains
  <Simulations: alt entry: TBP>
end type alt_entry_t

```

The alternative entries are there to re-evaluate the event, given momenta, in a different context.

Therefore, we allocate a local process object and use this as the reference for the local process instance, when initializing the entry. We temporarily import the `process` object into an `integration_t` wrapper, to take advantage of the associated methods. The local process object is built in the context of the current environment, here called `global`. Then, we initialize the process instance.

The `master_process` object contains the integration results to which we refer when recalculating an event. Therefore, we use this object instead of the locally built `process` when we extract the integration results.

The locally built `process` object should be finalized when done. It remains accessible via the `event_t` base object of `entry`, which contains pointers to the process and instance.

```

<Simulations: alt entry: TBP>≡
procedure :: init_alt => alt_entry_init
<Simulations: procedures>+≡
subroutine alt_entry_init (entry, process_id, master_process, local)
  class(alt_entry_t), intent(inout), target :: entry
  type(string_t), intent(in) :: process_id

```

```

type(process_t), intent(in), target :: master_process
type(rt_data_t), intent(inout), target :: local
type(process_t), pointer :: process
type(process_instance_t), pointer :: process_instance
type(string_t) :: run_id
integer :: i

call msg_message ("Simulate: initializing alternate process setup ...")

run_id = &
    local%var_list%get_sval (var_str ("run_id"))
call local%set_log (var_str ("?rebuild_phase_space"), &
    .false., is_known = .true.)
call local%set_log (var_str ("?check_phs_file"), &
    .false., is_known = .true.)
call local%set_log (var_str ("?rebuild_grids"), &
    .false., is_known = .true.)

call entry%basic_init (local%var_list)

call prepare_local_process (process, process_id, local)
entry%process_id = process_id
entry%run_id = run_id

call entry%import_process_characteristics (process)

allocate (entry%mci_set (entry%n_mci))
do i = 1, size (entry%mci_set)
    call entry%mci_set(i)%init (i, master_process)
end do

call entry%import_process_results (master_process)
call entry%prepare_expressions (local)

call prepare_process_instance (process_instance, process, local%model)
call entry%setup_event_transforms (process, local)

call entry%connect (process_instance, local%model, local%process_stack)
call entry%setup_expressions ()

entry%model => process%get_model_ptr ()

call msg_message ("... alternate process setup complete.")

end subroutine alt_entry_init

```

Copy the particle set from the master entry to the alternate entry. This is the particle set of the hard process.

```

<Simulations: alt entry: TBP>+=
    procedure :: fill_particle_set => entry_fill_particle_set

<Simulations: procedures>+=
    subroutine entry_fill_particle_set (alt_entry, entry)
        class(alt_entry_t), intent(inout) :: alt_entry

```

```

class(entry_t), intent(in), target :: entry
type(particle_set_t) :: pset
call entry%get_hard_particle_set (pset)
call alt_entry%set_hard_particle_set (pset)
call pset%final ()
end subroutine entry_fill_particle_set

```

28.14.7 The simulation type

Each simulation object corresponds to an event sample, identified by the `sample_id`.

The simulation may cover several processes simultaneously. All process-specific data, including the event records, are stored in the `entry` subobjects. The `current` index indicates which record was selected last. `version` is foreseen to contain a tag on the WHIZARD event file version. It can be

```

<Simulations: public>≡
    public :: simulation_t

<Simulations: types>+≡
    type :: simulation_t
        private
        type(string_t) :: sample_id
        logical :: unweighted = .true.
        logical :: negative_weights = .false.
        logical :: respect_selection = .true.
        integer :: norm_mode = NORM_UNDEFINED
        logical :: update_sqme = .false.
        logical :: update_weight = .false.
        logical :: update_event = .false.
        logical :: recover_beams = .false.
        logical :: pacify = .false.
        integer :: n_max_tries = 10000
        integer :: n_prc = 0
        integer :: n_alt = 0
        logical :: has_integral = .false.
        logical :: valid
        real(default) :: integral = 0
        real(default) :: error = 0
        integer :: version = 1
        character(32) :: md5sum_prc = ""
        character(32) :: md5sum_cfg = ""
        character(32), dimension(:), allocatable :: md5sum_alt
        type(entry_t), dimension(:), allocatable :: entry
        type(alt_entry_t), dimension(:,:), allocatable :: alt_entry
        type(selector_t) :: process_selector
        integer :: n_evt_requested = 0
        integer :: split_n_evt = 0
        integer :: split_n_kbytes = 0
        integer :: split_index = 0
        type(counter_t) :: counter
        class(rng_t), allocatable :: rng
        integer :: i_prc = 0
        integer :: i_mci = 0

```

```

    real(default) :: weight = 0
    real(default) :: excess = 0
contains
  <Simulations: simulation: TBP>
end type simulation_t

```

Output. `write_config` writes just the configuration. `write` as a method of the base type `event_t` writes the current event and process instance, depending on options.

```

<Simulations: simulation: TBP>≡
  procedure :: write => simulation_write

<Simulations: procedures>+≡
  subroutine simulation_write (object, unit)
    class(simulation_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u, i
    u = given_output_unit (unit)
    call write_separator (u, 2)
    write (u, "(1x,A,A,A)") "Event sample: '", char (object%sample_id), "'"
    write (u, "(3x,A,I0)") "Processes      = ", object%n_prc
    if (object%n_alt > 0) then
      write (u, "(3x,A,I0)") "Alt.wgts      = ", object%n_alt
    end if
    write (u, "(3x,A,L1)") "Unweighted    = ", object%unweighted
    write (u, "(3x,A,A)") "Event norm    = ", &
      char (event_normalization_string (object%norm_mode))
    write (u, "(3x,A,L1)") "Neg. weights = ", object%negative_weights
    write (u, "(3x,A,L1)") "Respect sel. = ", object%respect_selection
    write (u, "(3x,A,L1)") "Update sqme  = ", object%update_sqme
    write (u, "(3x,A,L1)") "Update wgt   = ", object%update_weight
    write (u, "(3x,A,L1)") "Update event = ", object%update_event
    write (u, "(3x,A,L1)") "Recov. beams = ", object%recover_beams
    write (u, "(3x,A,L1)") "Pacify       = ", object%pacify
    write (u, "(3x,A,I0)") "Max. tries   = ", object%n_max_tries
    if (object%has_integral) then
      write (u, "(3x,A," // FMT_19 // ")") "Integral      = ", object%integral
      write (u, "(3x,A," // FMT_19 // ")") "Error         = ", object%error
    else
      write (u, "(3x,A)") "Integral      = [undefined]"
    end if
    write (u, "(3x,A,L1)") "Sim. valid    = ", object%valid
    write (u, "(3x,A,I0)") "Ev.file ver. = ", object%version
    if (object%md5sum_prc /= "") then
      write (u, "(3x,A,A,A)") "MD5 sum (proc) = '", object%md5sum_prc, "'"
    end if
    if (object%md5sum_cfg /= "") then
      write (u, "(3x,A,A,A)") "MD5 sum (config) = '", object%md5sum_cfg, "'"
    end if
    write (u, "(3x,A,I0)") "Events requested = ", object%n_evt_requested
    if (object%split_n_evt > 0 .or. object%split_n_kbytes > 0) then
      write (u, "(3x,A,I0)") "Events per file = ", object%split_n_evt
      write (u, "(3x,A,I0)") "KBytes per file = ", object%split_n_kbytes
      write (u, "(3x,A,I0)") "First file index = ", object%split_index
    end if
  end subroutine simulation_write

```

```

end if
call object%counter%write (u)
call write_separator (u)
if (object%i_prc /= 0) then
  write (u, "(1x,A)") "Current event:"
  write (u, "(3x,A,I0,A,A)") "Process #", &
    object%i_prc, ": ", &
    char (object%entry(object%i_prc)%process_id)
  write (u, "(3x,A,I0)") "MCI set #", object%i_mci
  write (u, "(3x,A," // FMT_19 // ")") "Weight = ", object%weight
  if (.not. vanishes (object%excess)) &
    write (u, "(3x,A," // FMT_19 // ")") "Excess = ", object%excess
else
  write (u, "(1x,A,I0,A,A)") "Current event: [undefined]"
end if
call write_separator (u)
if (allocated (object%rng)) then
  call object%rng%write (u)
else
  write (u, "(3x,A)") "Random-number generator: [undefined]"
end if
if (allocated (object%entry)) then
  do i = 1, size (object%entry)
    if (i == 1) then
      call write_separator (u, 2)
    else
      call write_separator (u)
    end if
    write (u, "(1x,A,I0,A)") "Process #", i, ":"
    call object%entry(i)%write_config (u)
  end do
end if
call write_separator (u, 2)
end subroutine simulation_write

```

Write the current event record. If an explicit index is given, write that event record.

We implement writing to `unit` (event contents / debugging format) and writing to an `eio` event stream (storage). We include a `testflag` in order to suppress numerical noise in the testsuite.

<Simulations: simulation: TBP>+≡

```

generic :: write_event => write_event_unit
procedure :: write_event_unit => simulation_write_event_unit

```

<Simulations: procedures>+≡

```

subroutine simulation_write_event_unit &
  (object, unit, i_prc, verbose, testflag)
  class(simulation_t), intent(in) :: object
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  integer, intent(in), optional :: i_prc
  logical, intent(in), optional :: testflag
  logical :: pacified
  integer :: current

```

```

    pacified = .false.; if (present(testflag)) pacified = testflag
    pacified = pacified .or. object%pacify
    if (present (i_prc)) then
        current = i_prc
    else
        current = object%i_prc
    end if
    if (current > 0) then
        call object%entry(current)%write (unit, verbose = verbose, &
            testflag = pacified)
    else
        call msg_fatal ("Simulation: write event: no process selected")
    end if
end subroutine simulation_write_event_unit

```

This writes one of the alternate events, if allocated.

```

<Simulations: simulation: TBP>+≡
    procedure :: write_alt_event => simulation_write_alt_event

<Simulations: procedures>+≡
    subroutine simulation_write_alt_event (object, unit, j_alt, i_prc, &
        verbose, testflag)
        class(simulation_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer, intent(in), optional :: j_alt
        integer, intent(in), optional :: i_prc
        logical, intent(in), optional :: verbose
        logical, intent(in), optional :: testflag
        integer :: i, j
        if (present (j_alt)) then
            j = j_alt
        else
            j = 1
        end if
        if (present (i_prc)) then
            i = i_prc
        else
            i = object%i_prc
        end if
        if (i > 0) then
            if (j > 0 .and. j <= object%n_alt) then
                call object%alt_entry(i,j)%write (unit, verbose = verbose, &
                    testflag = testflag)
            else
                call msg_fatal ("Simulation: write alternate event: out of range")
            end if
        else
            call msg_fatal ("Simulation: write alternate event: no process selected")
        end if
    end subroutine simulation_write_alt_event

```

Finalizer.

```

<Simulations: simulation: TBP>+≡
    procedure :: final => simulation_final

```

```

<Simulations: procedures>+≡
subroutine simulation_final (object)
  class(simulation_t), intent(inout) :: object
  integer :: i, j
  if (allocated (object%entry)) then
    do i = 1, size (object%entry)
      call object%entry(i)%final ()
    end do
  end if
  if (allocated (object%alt_entry)) then
    do j = 1, size (object%alt_entry, 2)
      do i = 1, size (object%alt_entry, 1)
        call object%alt_entry(i,j)%final ()
      end do
    end do
  end if
  if (allocated (object%rng)) call object%rng%final ()
end subroutine simulation_final

```

Initialization. We can deduce all data from the given list of process IDs and the global data set. The process objects are taken from the stack. Once the individual integrals are known, we add them (and the errors), to get the sample integral.

If there are alternative environments, we suspend initialization for setting up alternative process objects, then restore the master process and its parameters. The generator or rescanner can then switch rapidly between processes.

If **integrate** is set, we make sure that all affected processes are integrated before simulation. This is necessary if we want to actually generate events. If **integrate** is unset, we don't need the integral because we just rescan existing events. In that case, we just need compiled matrix elements.

If **generate** is set, we prepare for actually generating events. Otherwise, we may only read and rescan events.

```

<Simulations: simulation: TBP>+≡
procedure :: init => simulation_init

<Simulations: procedures>+≡
subroutine simulation_init (simulation, &
  process_id, integrate, generate, local, global, alt_env)
  class(simulation_t), intent(out), target :: simulation
  type(string_t), dimension(:), intent(in) :: process_id
  logical, intent(in) :: integrate, generate
  type(rt_data_t), intent(inout), target :: local
  type(rt_data_t), intent(inout), optional, target :: global
  type(rt_data_t), dimension(:), intent(inout), optional, target :: alt_env
  class(rng_factory_t), allocatable :: rng_factory
  type(string_t) :: norm_string, version_string
  integer :: i, j
  simulation%sample_id = &
    local%get_sval (var_str ("sample"))
  simulation%unweighted = &
    local%get_lval (var_str ("unweighted"))
  simulation%negative_weights = &
    local%get_lval (var_str ("negative_weights"))

```



```

simulation%respect_selection = &
    local%get_lval (var_str ("?sample_select"))
version_string = &
    local%get_sval (var_str ("$_event_file_version"))
norm_string = &
    local%get_sval (var_str ("$_sample_normalization"))
simulation%norm_mode = &
    event_normalization_mode (norm_string, simulation%unweighted)
simulation%pacify = &
    local%get_lval (var_str ("?sample_pacify"))
simulation%n_max_tries = &
    local%get_ival (var_str ("sample_max_tries"))
simulation%split_n_evt = &
    local%get_ival (var_str ("sample_split_n_evt"))
simulation%split_n_kbytes = &
    local%get_ival (var_str ("sample_split_n_kbytes"))
simulation%split_index = &
    local%get_ival (var_str ("sample_split_index"))
simulation%update_sqme = &
    local%get_lval (var_str ("?update_sqme"))
simulation%update_weight = &
    local%get_lval (var_str ("?update_weight"))
simulation%update_event = &
    local%get_lval (var_str ("?update_event"))
simulation%recover_beams = &
    local%get_lval (var_str ("?recover_beams"))
select case (size (process_id))
case (0)
    call msg_error ("Simulation: no process selected")
case (1)
    write (msg_buffer, "(A,A,A)") &
        "Starting simulation for process '", &
        char (process_id(1)), "' "
    call msg_message ()
case default
    write (msg_buffer, "(A,A,A)") &
        "Starting simulation for processes '", &
        char (process_id(1)), "' etc."
    call msg_message ()
end select
select case (char (version_string))
case ("", "2.2.4")
    simulation%version = 2
case ("2.2")
    simulation%version = 1
case default
    simulation%version = 0
end select
if (simulation%version == 0) then
    call msg_fatal ("Event file format '" &
        // char (version_string) &
        // "' is not compatible with this version.")
end if
simulation%n_prc = size (process_id)

```

```

allocate (simulation%entry (simulation%n_prc))
if (present (alt_env)) then
  simulation%n_alt = size (alt_env)
  do i = 1, simulation%n_prc
    call simulation%entry(i)%init (process_id(i), &
      integrate, generate, &
      simulation%update_sqme, &
      local, global, simulation%n_alt)
    if (signal_is_pending ()) return
  end do
  if (.not. any (simulation%entry%valid)) then
    call msg_error ("Simulate: no process has a valid matrix element.")
    simulation%valid = .false.
    return
  end if
  call simulation%update_processes ()
  allocate (simulation%alt_entry (simulation%n_prc, simulation%n_alt))
  allocate (simulation%md5sum_alt (simulation%n_alt))
  simulation%md5sum_alt = ""
  do j = 1, simulation%n_alt
    do i = 1, simulation%n_prc
      call simulation%alt_entry(i,j)%init_alt (process_id(i), &
        simulation%entry(i)%get_process_ptr (), alt_env(j))
      if (signal_is_pending ()) return
    end do
  end do
  call simulation%restore_processes ()
else
  do i = 1, simulation%n_prc
    call simulation%entry(i)%init &
      (process_id(i), &
      integrate, generate, simulation%update_sqme, &
      local, global)
    if (signal_is_pending ()) return
  end do
  if (.not. any (simulation%entry%valid)) then
    call msg_error ("Simulate: " &
      // "no process has a valid matrix element.")
    simulation%valid = .false.
    return
  end if
end if
call dispatch_rng_factory (rng_factory, local)
call rng_factory%make (simulation%rng)
if (all (simulation%entry%has_integral)) then
  simulation%integral = sum (simulation%entry%integral)
  simulation%error = sqrt (sum (simulation%entry%error ** 2))
  simulation%has_integral = .true.
  if (integrate .and. generate) then
    do i = 1, simulation%n_prc
      if (simulation%entry(i)%integral < 0 .and. .not. &
        simulation%negative_weights) then
        call msg_fatal ("Integral of process '" // &
          char (process_id (i)) // "'is negative.")
      end if
    end do
  end if
end if

```

```

        end if
      end do
    end if
  else
    if (integrate .and. generate) &
      call msg_error ("Simulation contains undefined integrals.")
    end if
    if (simulation%integral > 0 .or. &
      (simulation%integral < 0 .and. simulation%negative_weights)) then
      simulation%valid = .true.
    else if (generate) then
      call msg_error ("Simulate: " &
        // "sum of process integrals must be positive; skipping.")
      simulation%valid = .false.
      return
    end if
    if (simulation%valid) call simulation%compute_md5sum ()
  end subroutine simulation_init

```

The number of events that we want to simulate is determined by the settings of `n_events`, `luminosity`, and `?unweighted`. For weighted events, we take `n_events` at face value as the number of matrix element calls. For unweighted events, if the process is a decay, `n_events` is the number of unweighted events. In these cases, the luminosity setting is ignored.

For unweighted events with a scattering process, we calculate the event number that corresponds to the luminosity, given the current value of the integral. We then compare this with `n_events` and choose the larger number.

```

<Simulations: simulation: TBP>+≡
  procedure :: compute_n_events => simulation_compute_n_events

<Simulations: procedures>+≡
  subroutine simulation_compute_n_events (simulation, n_events, var_list)
    class(simulation_t), intent(in) :: simulation
    integer, intent(out) :: n_events
    type(var_list_t) :: var_list
    real(default) :: lumi, x_events_lumi
    integer :: n_events_lumi
    logical :: is_scattering
    n_events = &
      var_list%get_ival (var_str ("n_events"))
    lumi = &
      var_list%get_rval (var_str ("luminosity"))
    if (simulation%unweighted) then
      is_scattering = simulation%entry(1)%n_in == 2
      if (is_scattering) then
        x_events_lumi = abs (simulation%integral * lumi)
        if (x_events_lumi < huge (n_events)) then
          n_events_lumi = nint (x_events_lumi)
        else
          call msg_message ("Simulation: luminosity too large, &
            &limiting number of events")
          n_events_lumi = huge (n_events)
        end if
      end if
    end if
  end subroutine simulation_compute_n_events

```

```

        if (n_events_lumi > n_events) then
            call msg_message ("Simulation: using n_events as computed from &
                               &luminosity value")
            n_events = n_events_lumi
        else
            write (msg_buffer, "(A,1x,I0)") &
                "Simulation: requested number of events =", n_events
            call msg_message ()
            if (.not. vanishes (simulation%integral)) then
                write (msg_buffer, "(A,1x,ES11.4)") &
                    "                corr. to luminosity [fb-1] = ", &
                    n_events / simulation%integral
                call msg_message ()
            end if
        end if
    end if
end if
end if
end subroutine simulation_compute_n_events

```

Compute the checksum of the process set. We retrieve the MD5 sums of all processes. This depends only on the process definitions, while parameters are not considered. The configuration checksum is retrieved from the MCI records in the process objects and furthermore includes beams, parameters, integration results, etc., so matching the latter should guarantee identical physics.

```

<Simulations: simulation: TBP>+≡
    procedure :: compute_md5sum => simulation_compute_md5sum

<Simulations: procedures>+≡
    subroutine simulation_compute_md5sum (simulation)
        class(simulation_t), intent(inout) :: simulation
        type(process_t), pointer :: process
        type(string_t) :: buffer
        integer :: j, i, n_mci, i_mci, n_component, i_component
        if (simulation%md5sum_prc == "") then
            buffer = ""
            do i = 1, simulation%n_prc
                if (.not. simulation%entry(i)%valid) cycle
                process => simulation%entry(i)%get_process_ptr ()
                n_component = process%get_n_components ()
                do i_component = 1, n_component
                    if (process%has_matrix_element (i_component)) then
                        buffer = buffer // process%get_md5sum_prc (i_component)
                    end if
                end do
            end do
            simulation%md5sum_prc = md5sum (char (buffer))
        end if
        if (simulation%md5sum_cfg == "") then
            buffer = ""
            do i = 1, simulation%n_prc
                if (.not. simulation%entry(i)%valid) cycle
                process => simulation%entry(i)%get_process_ptr ()
                n_mci = process%get_n_mci ()
                do i_mci = 1, n_mci

```

```

        buffer = buffer // process%get_md5sum_mci (i_mci)
    end do
end do
simulation%md5sum_cfg = md5sum (char (buffer))
end if
do j = 1, simulation%n_alt
    if (simulation%md5sum_alt(j) == "") then
        buffer = ""
        do i = 1, simulation%n_prc
            process => simulation%alt_entry(i,j)%get_process_ptr ()
            buffer = buffer // process%get_md5sum_cfg ()
        end do
        simulation%md5sum_alt(j) = md5sum (char (buffer))
    end if
end do
end subroutine simulation_compute_md5sum

```

Initialize the process selector, using the entry integrals as process weights.

<Simulations: simulation: TBP>+≡

```

    procedure :: init_process_selector => simulation_init_process_selector

```

<Simulations: procedures>+≡

```

subroutine simulation_init_process_selector (simulation)
    class(simulation_t), intent(inout) :: simulation
    integer :: i
    if (simulation%has_integral) then
        call simulation%process_selector%init (simulation%entry%integral)
        do i = 1, simulation%n_prc
            associate (entry => simulation%entry(i))
                if (.not. entry%valid) then
                    call msg_warning ("Process '" // char (entry%process_id) // &
                                     "' : matrix element vanishes, no events can be generated.")
                    cycle
                end if
                call entry%init_mci_selector ()
                entry%process_weight = simulation%process_selector%get_weight (i)
            end associate
        end do
    end if
end subroutine simulation_init_process_selector

```

Select a process, using the random-number generator.

<Simulations: simulation: TBP>+≡

```

    procedure :: select_prc => simulation_select_prc

```

<Simulations: procedures>+≡

```

function simulation_select_prc (simulation) result (i_prc)
    class(simulation_t), intent(inout) :: simulation
    integer :: i_prc
    call simulation%process_selector%generate (simulation%rng, i_prc)
end function simulation_select_prc

```

Select a MCI set for the selected process.

```

(Simulations: simulation: TBP)+≡
  procedure :: select_mci => simulation_select_mci

(Simulations: procedures)+≡
  function simulation_select_mci (simulation) result (i_mci)
    class(simulation_t), intent(inout) :: simulation
    integer :: i_mci
    if (simulation%i_prc /= 0) then
      i_mci = simulation%entry(simulation%i_prc)%select_mci ()
    end if
  end function simulation_select_mci

```

Generate a predefined number of events. First select a process and a component set, then generate an event for that process and factorize the quantum state. The pair of random numbers can be used for factorization.

When generating events, we drop all configurations where the event is marked as incomplete. This happens if the event fails cuts. In fact, such events are dropped already by the sampler if unweighting is in effect, so this can happen only for weighted events. By setting a limit given by `sample_max_tries` (user parameter), we can avoid an endless loop.

NB: When reading from file, event transforms can't be applied because the process instance will not be complete. This should be fixed.

```

(Simulations: simulation: TBP)+≡
  procedure :: generate => simulation_generate

(Simulations: procedures)+≡
  subroutine simulation_generate (simulation, n, es_array)
    class(simulation_t), intent(inout) :: simulation
    integer, intent(in) :: n
    type(event_stream_array_t), intent(inout), optional :: es_array
    type(string_t) :: str1, str2, str3
    logical :: generate_new, passed
    integer :: i, j
    simulation%n_evt_requested = n
    call simulation%entry%set_n (n)
    if (simulation%n_alt > 0) call simulation%alt_entry%set_n (n)
    str1 = "Events: generating"
    if (present (es_array)) then
      if (es_array%has_input ()) str1 = "Events: reading"
    end if
    if (simulation%entry(1)%config%unweighted) then
      str2 = "unweighted"
    else
      str2 = "weighted"
    end if
    if (simulation%entry(1)%config%factorization_mode == &
        FM_IGNORE_HELICITY) then
      str3 = ", unpolarized"
    else
      str3 = ", polarized"
    end if
    write (msg_buffer, "(A,1x,I0,1x,A,1x,A)") char (str1), n, &

```

```

        char (str2) // char(str3), "events ..."
    call msg_message ()
    write (msg_buffer, "(A,1x,A)") "Events: event normalization mode", &
        char (event_normalization_string (simulation%norm_mode))
    call msg_message ()
    do i = 1, n
        if (present (es_array)) then
            call simulation%read_event (es_array, .true., generate_new)
        else
            generate_new = .true.
        end if
        if (generate_new) then
            simulation%i_prc = simulation%select_prc ()
            simulation%i_mci = simulation%select_mci ()
            associate (entry => simulation%entry(simulation%i_prc))
                do j = 1, simulation%n_max_tries
                    if (.not. entry%valid) call msg_warning &
                        ("Process '" // char (entry%process_id) // "': " // &
                        "matrix element vanishes, no events can be generated.")
                    call entry%generate (simulation%i_mci)
                    if (signal_is_pending ()) return
                    if (entry%has_valid_particle_set ()) exit
                end do
                if (.not. entry%has_valid_particle_set ()) then
                    write (msg_buffer, "(A,I0,A)") "Simulation: failed to &
                        &generate valid event after ", &
                        simulation%n_max_tries, " tries (sample_max_tries)"
                    call msg_fatal ()
                end if
                call entry%evaluate_expressions ()
                if (signal_is_pending ()) return
                if (entry%passed_selection ()) then
                    simulation%weight = entry%get_weight_ref ()
                    simulation%excess = entry%get_excess_prc ()
                end if
                call simulation%counter%record &
                    (simulation%weight, simulation%excess)
                call entry%record (simulation%i_mci)
            end associate
        else
            associate (entry => simulation%entry(simulation%i_prc))
                call entry%accept_sqme_ref ()
                call entry%accept_weight_ref ()
                !!! JRR: WK please check: why commented out
                ! call entry%evaluate_transforms () ! doesn't activate
                call entry%check ()
                call entry%evaluate_expressions ()
                if (signal_is_pending ()) return
                if (entry%passed_selection ()) then
                    simulation%weight = entry%get_weight_ref ()
                    simulation%excess = entry%get_excess_prc ()
                end if
                call simulation%counter%record &
                    (simulation%weight, simulation%excess, from_file=.true.)
            end associate
        end if
    end do
end

```

```

        call entry%record (simulation%i_mci, from_file=.true.)
    end associate
end if
call simulation%calculate_alt_entries ()
if (signal_is_pending ()) return
if (simulation%pacify) call pacify (simulation)
if (simulation%respect_selection) then
    passed = simulation%entry(simulation%i_prc)%passed_selection ()
else
    passed = .true.
end if
if (present (es_array)) then
    call simulation%write_event (es_array, passed)
end if
end do
call msg_message ("        ... event sample complete.")
call simulation%counter%show_excess ()
end subroutine simulation_generate

```

Compute the event matrix element and weight for all alternative environments, given the current event and selected process. We first copy the particle set, then temporarily update the process core with local parameters, recalculate everything, and restore the process core.

The event weight is obtained by rescaling the original event weight with the ratio of the new and old `sqme` values. (In particular, if the old value was zero, the weight will stay zero.)

Note: this may turn out to be inefficient because we always replace all parameters and recalculate everything, once for each event and environment. However, a more fine-grained control requires more code. In any case, while we may keep multiple process cores (which stay constant for a simulation run), we still have to update the external matrix element parameters event by event. The matrix element “object” is present only once.

```

<Simulations: simulation: TBP>+≡
    procedure :: calculate_alt_entries => simulation_calculate_alt_entries

<Simulations: procedures>+≡
    subroutine simulation_calculate_alt_entries (simulation)
        class(simulation_t), intent(inout) :: simulation
        real(default) :: factor
        real(default), dimension(:), allocatable :: sqme_alt, weight_alt
        integer :: n_alt, i, j
        i = simulation%i_prc
        n_alt = simulation%n_alt
        if (n_alt == 0) return
        allocate (sqme_alt (n_alt), weight_alt (n_alt))
        associate (entry => simulation%entry(i))
            do j = 1, n_alt
                if (signal_is_pending ()) return
                factor = entry%get_kinematical_weight ()
                associate (alt_entry => simulation%alt_entry(i,j))
                    call alt_entry%update_process ()
                    call alt_entry%select &
                        (entry%get_i_mci (), entry%get_i_term (), entry%get_channel ())

```



```

        call alt_entry%fill_particle_set (entry)
        call alt_entry%recalculate &
            (update_sqme = .true., weight_factor = factor)
        if (signal_is_pending ()) return
        call alt_entry%accept_sqme_prc ()
        call alt_entry%update_normalization ()
        call alt_entry%accept_weight_prc ()
        call alt_entry%check ()
        call alt_entry%evaluate_expressions ()
        if (signal_is_pending ()) return
        call alt_entry%restore_process ()
        sqme_alt(j) = alt_entry%get_sqme_ref ()
        if (alt_entry%passed_selection ()) then
            weight_alt(j) = alt_entry%get_weight_ref ()
        end if
    end associate
end do
call entry%set (sqme_alt = sqme_alt, weight_alt = weight_alt)
call entry%check ()
call entry%store_alt_values ()
end associate
end subroutine simulation_calculate_alt_entries

```

Rescan an undefined number of events.

If `update_event` or `update_sqme` is set, we have to recalculate the event, starting from the particle set. If the latter is set, this includes the squared matrix element (i.e., the amplitude is evaluated). Otherwise, only kinematics and observables derived from it are recovered.

If any of the update flags is set, we will come up with separate `sqme_prc` and `weight_prc` values. (The latter is only distinct if `update_weight` is set.) Otherwise, we accept the reference values.

<Simulations: simulation: TBP>+≡

```

procedure :: rescan => simulation_rescan

```

<Simulations: procedures>+≡

```

subroutine simulation_rescan (simulation, n, es_array, global)
    class(simulation_t), intent(inout) :: simulation
    integer, intent(in) :: n
    type(event_stream_array_t), intent(inout) :: es_array
    type(rt_data_t), intent(inout) :: global
    type(qcd_t) :: qcd
    type(string_t) :: str1, str2, str3
    logical :: complete
    str1 = "Rescanning"
    if (simulation%entry(1)%config%unweighted) then
        str2 = "unweighted"
    else
        str2 = "weighted"
    end if
    simulation%n_evt_requested = n
    call simulation%entry%set_n (n)
    if (simulation%update_sqme .or. simulation%update_weight) then
        call dispatch_qcd (qcd, global)
    end if
end subroutine

```

```

        call simulation%update_processes &
            (global%model, qcd, global%get_helicity_selection ())
        str3 = "(process parameters updated) "
    else
        str3 = ""
    end if
    write (msg_buffer, "(A,1x,A,1x,A,A,A)") char (str1), char (str2), &
        "events ", char (str3), "... "
    call msg_message ()
do
    call simulation%read_event (es_array, .false., complete)
    if (complete) exit
    if (simulation%update_event &
        .or. simulation%update_sqme &
        .or. simulation%update_weight) then
        call simulation%recalculate ()
        if (signal_is_pending ()) return
        associate (entry => simulation%entry(simulation%i_prc))
            call entry%update_normalization ()
            if (simulation%update_event) then
                call entry%evaluate_transforms ()
            end if
            call entry%check ()
            call entry%evaluate_expressions ()
            if (signal_is_pending ()) return
            simulation%weight = entry%get_weight_prc ()
            call simulation%counter%record (simulation%weight, from_file=.true.)
            call entry%record (simulation%i_mci, from_file=.true.)
        end associate
    else
        associate (entry => simulation%entry(simulation%i_prc))
            call entry%accept_sqme_ref ()
            call entry%accept_weight_ref ()
            call entry%check ()
            call entry%evaluate_expressions ()
            if (signal_is_pending ()) return
            simulation%weight = entry%get_weight_ref ()
            call simulation%counter%record (simulation%weight, from_file=.true.)
            call entry%record (simulation%i_mci, from_file=.true.)
        end associate
    end if
    call simulation%calculate_alt_entries ()
    if (signal_is_pending ()) return
    call simulation%write_event (es_array)
end do
    if (simulation%update_sqme .or. simulation%update_weight) then
        call simulation%restore_processes ()
    end if
end subroutine simulation_rescan

```

These routines take care of temporary parameter redefinitions that we want to take effect while recalculating the matrix elements. We extract the core(s) of the processes that we are simulating, apply the changes, and make sure that the

changes are actually used. This is the duty of `dispatch_core_update`. When done, we restore the original versions using `dispatch_core_restore`.

```

<Simulations: simulation: TBP>+=
  procedure :: update_processes => simulation_update_processes
  procedure :: restore_processes => simulation_restore_processes

<Simulations: procedures>+=
  subroutine simulation_update_processes (simulation, &
    model, qcd, helicity_selection)
    class(simulation_t), intent(inout) :: simulation
    class(model_data_t), intent(in), optional, target :: model
    type(qcd_t), intent(in), optional :: qcd
    type(helicity_selection_t), intent(in), optional :: helicity_selection
    integer :: i
    do i = 1, simulation%n_prc
      call simulation%entry(i)%update_process (model, qcd, helicity_selection)
    end do
  end subroutine simulation_update_processes

  subroutine simulation_restore_processes (simulation)
    class(simulation_t), intent(inout) :: simulation
    integer :: i
    do i = 1, simulation%n_prc
      call simulation%entry(i)%restore_process ()
    end do
  end subroutine simulation_restore_processes

```

28.14.8 Event Stream I/O

Write an event to a generic `eio` event stream. The process index must be selected, or the current index must be available.

```

<Simulations: simulation: TBP>+=
  generic :: write_event => write_event_eio
  procedure :: write_event_eio => simulation_write_event_eio

<Simulations: procedures>+=
  subroutine simulation_write_event_eio (object, eio, i_prc)
    class(simulation_t), intent(in) :: object
    class(eio_t), intent(inout) :: eio
    integer, intent(in), optional :: i_prc
    logical :: increased
    integer :: current
    if (present (i_prc)) then
      current = i_prc
    else
      current = object%i_prc
    end if
    if (current > 0) then
      if (object%split_n_evt > 0 &
        .and. object%counter%total > 1 &
        .and. mod (object%counter%total, object%split_n_evt) == 1) then
        call eio%split_out ()
      else if (object%split_n_kbytes > 0) then

```

```

        call eio%update_split_count (increased)
        if (increased) call eio%split_out ()
    end if
    call eio%output (object%entry(current)%event_t, current, pacify = object%pacify)
else
    call msg_fatal ("Simulation: write event: no process selected")
end if
end subroutine simulation_write_event_eio

```

Read an event from a generic `eio` event stream. The event stream element must specify the process within the sample (`i_prc`), the MC group for this process (`i_mci`), the selected term (`i_term`), the selected MC integration `channel`, and the particle set of the event.

We may encounter EOF, which we indicate by storing 0 for the process index `i_prc`. An I/O error will be reported, and we also abort reading.

```

<Simulations: simulation: TBP>+≡
generic :: read_event => read_event_eio
procedure :: read_event_eio => simulation_read_event_eio

<Simulations: procedures>+≡
subroutine simulation_read_event_eio (object, eio)
class(simulation_t), intent(inout) :: object
class(eio_t), intent(inout) :: eio
integer :: iostat, current
call eio%input_i_prc (current, iostat)
select case (iostat)
case (0)
    object%i_prc = current
    call eio%input_event (object%entry(current)%event_t, iostat)
end select
select case (iostat)
case (:-1)
    object%i_prc = 0
    object%i_mci = 0
case (1:)
    call msg_error ("Reading events: I/O error, aborting read")
    object%i_prc = 0
    object%i_mci = 0
case default
    object%i_mci = object%entry(current)%get_i_mci ()
end select
end subroutine simulation_read_event_eio

```

28.14.9 Event Stream Array

Write an event using an array of event I/O streams. The process index must be selected, or the current index must be available.

```

<Simulations: simulation: TBP>+≡
generic :: write_event => write_event_es_array
procedure :: write_event_es_array => simulation_write_event_es_array

```

<Simulations: procedures>+≡

```

subroutine simulation_write_event_es_array (object, es_array, passed)
  class(simulation_t), intent(in) :: object
  class(event_stream_array_t), intent(inout) :: es_array
  logical, intent(in), optional :: passed
  integer :: i_prc, event_index
  i_prc = object%i_prc
  if (i_prc > 0) then
    event_index = object%counter%total
    call es_array%output (object%entry(i_prc)%event_t, i_prc, &
      event_index, passed = passed, pacify = object%pacify)
  else
    call msg_fatal ("Simulation: write event: no process selected")
  end if
end subroutine simulation_write_event_es_array

```

Read an event using an array of event I/O streams. Reading is successful if there is an input stream within the array, and if a valid event can be read from that stream. If there is a stream, but EOF is passed when reading the first item, we switch the channel to output and return failure but no error message, such that new events can be appended to that stream.

<Simulations: simulation: TBP>+≡

```

generic :: read_event => read_event_es_array
procedure :: read_event_es_array => simulation_read_event_es_array

```

<Simulations: procedures>+≡

```

subroutine simulation_read_event_es_array (object, es_array, enable_switch, &
  fail)
  class(simulation_t), intent(inout) :: object
  class(event_stream_array_t), intent(inout) :: es_array
  logical, intent(in) :: enable_switch
  logical, intent(out) :: fail
  integer :: iostat, i_prc
  if (es_array%has_input ()) then
    fail = .false.
    call es_array%input_i_prc (i_prc, iostat)
    select case (iostat)
    case (0)
      object%i_prc = i_prc
      call es_array%input_event (object%entry(i_prc)%event_t, iostat)
    case (:-1)
      write (msg_buffer, "(A,1x,I0,1x,A)" ) &
        "... event file terminates after", &
        object%counter%read, "events."
      call msg_message ()
      if (enable_switch) then
        call es_array%switch_inout ()
        write (msg_buffer, "(A,1x,I0,1x,A)" ) &
          "Generating remaining ", &
          object%n_evt_requested - object%counter%read, "events ..."
        call msg_message ()
      end if
      fail = .true.
    return
  end if

```

```

end select
select case (iostat)
case (0)
  object%i_mci = object%entry(i_prc)%get_i_mci ()
case default
  write (msg_buffer, "(A,1x,I0,1x,A)" &
    "Reading events: I/O error, aborting read after", &
    object%counter%read, "events.")
  call msg_error ()
  object%i_prc = 0
  object%i_mci = 0
  fail = .true.
end select
else
  fail = .true.
end if
end subroutine simulation_read_event_es_array

```

28.14.10 Recover event

Recalculate the process instance contents, given an event with known particle set. The indices for MC, term, and channel must be already set. The `recalculate` method of the selected entry will import the result into `sqme_prc` and `weight_prc`.

```

<Simulations: simulation: TBP>+≡
  procedure :: recalculate => simulation_recalculate

<Simulations: procedures>+≡
  subroutine simulation_recalculate (simulation)
    class(simulation_t), intent(inout) :: simulation
    integer :: i_prc
    i_prc = simulation%i_prc
    associate (entry => simulation%entry(i_prc))
      if (simulation%update_weight) then
        call simulation%entry(i_prc)%recalculate &
          (update_sqme = simulation%update_sqme, &
           recover_beams = simulation%recover_beams, &
           weight_factor = entry%get_kinematical_weight ())
      else
        call simulation%entry(i_prc)%recalculate &
          (update_sqme = simulation%update_sqme, &
           recover_beams = simulation%recover_beams)
      end if
    end associate
  end subroutine simulation_recalculate

```

28.14.11 Extract contents

Return the MD5 sum that summarizes configuration and integration (but not the event file). Used for initializing the event streams.

```

<Simulations: simulation: TBP>+≡

```

```

procedure :: get_md5sum_prc => simulation_get_md5sum_prc
procedure :: get_md5sum_cfg => simulation_get_md5sum_cfg
procedure :: get_md5sum_alt => simulation_get_md5sum_alt

<Simulations: procedures>+≡
function simulation_get_md5sum_prc (simulation) result (md5sum)
  class(simulation_t), intent(in) :: simulation
  character(32) :: md5sum
  md5sum = simulation%md5sum_prc
end function simulation_get_md5sum_prc

function simulation_get_md5sum_cfg (simulation) result (md5sum)
  class(simulation_t), intent(in) :: simulation
  character(32) :: md5sum
  md5sum = simulation%md5sum_cfg
end function simulation_get_md5sum_cfg

function simulation_get_md5sum_alt (simulation, i) result (md5sum)
  class(simulation_t), intent(in) :: simulation
  integer, intent(in) :: i
  character(32) :: md5sum
  md5sum = simulation%md5sum_alt(i)
end function simulation_get_md5sum_alt

```

Return data that may be useful for writing event files..

```

<Simulations: simulation: TBP>+≡
procedure :: get_data => simulation_get_data

<Simulations: procedures>+≡
function simulation_get_data (simulation, alt) result (sdata)
  class(simulation_t), intent(in) :: simulation
  logical, intent(in), optional :: alt
  type(event_sample_data_t) :: sdata
  type(process_t), pointer :: process
  type(beam_data_t), pointer :: beam_data
  type(flavor_t), dimension(:), allocatable :: flv
  integer :: n, i
  logical :: enable_alt
  enable_alt = .true.; if (present (alt)) enable_alt = alt
  process => simulation%entry(1)%get_process_ptr ()
  beam_data => process%get_beam_data_ptr ()
  if (enable_alt) then
    call sdata%init (simulation%n_prc, simulation%n_alt)
    do i = 1, simulation%n_alt
      sdata%md5sum_alt(i) = simulation%get_md5sum_alt (i)
    end do
  else
    call sdata%init (simulation%n_prc)
  end if
  sdata%unweighted = simulation%unweighted
  sdata%negative_weights = simulation%negative_weights
  sdata%norm_mode = simulation%norm_mode
  n = beam_data_get_n_in (beam_data)
  sdata%n_beam = n
  allocate (flv (n))

```

```

flv = beam_data_get_flavor (beam_data)
sdata%pdg_beam(:n) = flv%get_pdg ()
sdata%energy_beam(:n) = beam_data_get_energy (beam_data)
do i = 1, simulation%n_prc
  if (.not. simulation%entry(i)%valid) cycle
  process => simulation%entry(i)%get_process_ptr ()
  sdata%proc_num_id(i) = process%get_num_id ()
  if (sdata%proc_num_id(i) == 0) sdata%proc_num_id(i) = i
  if (simulation%entry(i)%has_integral) then
    sdata%cross_section(i) = simulation%entry(i)%integral
    sdata%error(i) = simulation%entry(i)%error
  end if
end do
sdata%total_cross_section = sum (sdata%cross_section)
sdata%md5sum_prc = simulation%get_md5sum_prc ()
sdata%md5sum_cfg = simulation%get_md5sum_cfg ()
if (simulation%split_n_evt > 0 .or. simulation%split_n_kbytes > 0) then
  sdata%split_n_evt = simulation%split_n_evt
  sdata%split_n_kbytes = simulation%split_n_kbytes
  sdata%split_index = simulation%split_index
end if
end function simulation_get_data

```

Return a default name for the current event sample. This is the process ID of the first process.

```

⟨Simulations: simulation: TBP⟩+≡
  procedure :: get_default_sample_name => simulation_get_default_sample_name

```

```

⟨Simulations: procedures⟩+≡
  function simulation_get_default_sample_name (simulation) result (sample)
    class(simulation_t), intent(in) :: simulation
    type(string_t) :: sample
    type(process_t), pointer :: process
    sample = "whizard"
    if (simulation%n_prc > 0) then
      process => simulation%entry(1)%get_process_ptr ()
      if (associated (process)) then
        sample = process%get_id ()
      end if
    end if
  end function simulation_get_default_sample_name

```

```

⟨Simulations: simulation: TBP⟩+≡
  procedure :: is_valid => simulation_is_valid

```

```

⟨Simulations: procedures⟩+≡
  function simulation_is_valid (simulation) result (valid)
    class(simulation_t), intent(inout) :: simulation
    logical :: valid
    valid = simulation%valid
  end function simulation_is_valid

```


28.14.12 Auxiliary

Call pacify: eliminate numerical noise.

```
<Simulations: interfaces>≡
  interface pacify
    module procedure pacify_simulation
  end interface

<Simulations: procedures>+≡
  subroutine pacify_simulation (simulation)
    class(simulation_t), intent(inout) :: simulation
    integer :: i, j
    i = simulation%i_prc
    if (i > 0) then
      call pacify (simulation%entry(i))
      do j = 1, simulation%n_alt
        call pacify (simulation%alt_entry(i,j))
      end do
    end if
  end subroutine pacify_simulation
```

28.14.13 Test

This is the master for calling self-test procedures.

```
<Simulations: public>+≡
  public :: simulations_test

<Simulations: tests>≡
  subroutine simulations_test (u, results)
    integer, intent(in) :: u
    type(test_results_t), intent(inout) :: results
  <Simulations: execute tests>
  end subroutine simulations_test
```

Initialization

Initialize a `simulation_t` object, including the embedded event records.

```
<Simulations: execute tests>≡
  call test (simulations_1, "simulations_1", &
    "initialization", &
    u, results)

<Simulations: tests>+≡
  subroutine simulations_1 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname1, procname2
    type(rt_data_t), target :: global
    type(simulation_t), target :: simulation

    write (u, "(A)")  "* Test output: simulations_1"
    write (u, "(A)")  "* Purpose: initialize simulation"
    write (u, "(A)")
```

```

write (u, "(A)")  "* Initialize processes"
write (u, "(A)")

call syntax_model_file_init ()

call global%global_init ()
call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

libname = "simulation_1a"
procname1 = "simulation_1p"

call prepare_test_library (global, libname, 1, [procname1])
call compile_library (libname, global)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$run_id"), &
    var_str ("simulations1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

procname2 = "sim_extra"

call prepare_test_library (global, libname, 1, [procname2])
call compile_library (libname, global)
call global%set_string (var_str ("$run_id"), &
    var_str ("simulations2"), is_known = .true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call global%set_string (var_str ("sample"), &
    var_str ("sim1"), is_known = .true.)
call integrate_process (procname2, global, local_stack=.true.)

```

```

call simulation%init ([procname1, procname2], .false., .true., global)
call simulation%init_process_selector ()
call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write the event record for the first process"
write (u, "(A)")

call simulation%write_event (u, i_prc = 1)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_1"

end subroutine simulations_1

```

Weighted events

Generate events for a single process.

```

<Simulations: execute tests>+≡
call test (simulations_2, "simulations_2", &
  "weighted events", &
  u, results)

<Simulations: tests>+≡
subroutine simulations_2 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname1
  type(rt_data_t), target :: global
  type(simulation_t), target :: simulation
  type(event_sample_data_t) :: data

  write (u, "(A)")  "* Test output: simulations_2"
  write (u, "(A)")  "* Purpose: generate events for a single process"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize processes"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()
  call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
  call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

```

```

libname = "simulation_2a"
procname1 = "simulation_2p"

call prepare_test_library (global, libname, 1, [procname1])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$run_id"), &
    var_str ("simulations1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

data = simulation%get_data ()
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate three events"
write (u, "(A)")

call simulation%generate (3)
call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write the event record for the last event"
write (u, "(A)")

call simulation%write_event (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_2"

end subroutine simulations_2

```

Unweighted events

Generate events for a single process.

```

<Simulations: execute tests>+≡
  call test (simulations_3, "simulations_3", &
    "unweighted events", &
    u, results)

<Simulations: tests>+≡
  subroutine simulations_3 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname1
    type(rt_data_t), target :: global
    type(simulation_t), target :: simulation
    type(event_sample_data_t) :: data

    write (u, "(A)")  "* Test output: simulations_3"
    write (u, "(A)")  "* Purpose: generate unweighted events &
      &for a single process"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize processes"
    write (u, "(A)")

    call syntax_model_file_init ()

    call global%global_init ()
    call global%set_log (var_str ("?omega_openmp"), &
      .false., is_known = .true.)
    call global%set_int (var_str ("seed"), &
      0, is_known = .true.)

    libname = "simulation_3a"
    procname1 = "simulation_3p"

    call prepare_test_library (global, libname, 1, [procname1])
    call compile_library (libname, global)

    call global%append_log (&
      var_str ("?rebuild_events"), .true., intrinsic = .true.)

```

```

call global%set_string (var_str ("method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("run_id"), &
    var_str ("simulations1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

data = simulation%get_data ()
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate three events"
write (u, "(A)")

call simulation%generate (3)
call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write the event record for the last event"
write (u, "(A)")

call simulation%write_event (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_3"

end subroutine simulations_3

```

Simulating process with structure functions

Generate events for a single process.

```
<Simulations: execute tests>+≡
  call test (simulations_4, "simulations_4", &
    "process with structure functions", &
    u, results)

<Simulations: tests>+≡
  subroutine simulations_4 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname1
    type(rt_data_t), target :: global
    type(flavor_t) :: flv
    type(string_t) :: name
    type(simulation_t), target :: simulation
    type(event_sample_data_t) :: data

    write (u, "(A)")  "* Test output: simulations_4"
    write (u, "(A)")  "* Purpose: generate events for a single process &
      &with structure functions"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize processes"
    write (u, "(A)")

    call syntax_model_file_init ()
    call syntax_phs_forest_init ()

    call global%global_init ()
    call global%set_log (var_str ("?omega_openmp"), &
      .false., is_known = .true.)
    call global%set_int (var_str ("seed"), &
      0, is_known = .true.)

    libname = "simulation_4a"
    procname1 = "simulation_4p"

    call prepare_test_library (global, libname, 1, [procname1])
    call compile_library (libname, global)

    call global%append_log (&
      var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
    call global%append_log (&
      var_str ("?rebuild_grids"), .true., intrinsic = .true.)
    call global%append_log (&
      var_str ("?rebuild_events"), .true., intrinsic = .true.)

    call global%set_string (var_str ("$_run_id"), &
      var_str ("r1"), is_known = .true.)
    call global%set_string (var_str ("$_method"), &
      var_str ("unit_test"), is_known = .true.)
```

```

call global%set_string (var_str ("phs_method"), &
    var_str ("wood"), is_known = .true.)
call global%set_string (var_str ("integration_method"), &
    var_str ("vamp"), is_known = .true.)
call global%set_log (var_str ("?use_vamp_equivalences"), &
    .true., is_known = .true.)
call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), &
    0._default)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call reset_interaction_counter ()

call flv%init (25, global%model)
name = flv%get_name ()

call global%beam_structure%init_sf ([name, name], [1])
call global%beam_structure%set_sf (1, 1, var_str ("sf_test_1"))

write (u, "(A)")  "* Integrate"
write (u, "(A)")

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("run_id"), &
    var_str ("r1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
call global%set_string (var_str ("sample"), &
    var_str ("simulations4"), is_known = .true.)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

data = simulation%get_data ()
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate three events"
write (u, "(A)")

call simulation%generate (3)
call simulation%write (u)

```



```

write (u, "(A)")
write (u, "(A)")  "* Write the event record for the last event"
write (u, "(A)")

call simulation%write_event (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_4"

end subroutine simulations_4

```

Event I/O

Generate event for a test process, write to file and reread.

```

<Simulations: execute tests>+≡
call test (simulations_5, "simulations_5", &
    "raw event I/O", &
    u, results)

<Simulations: tests>+≡
subroutine simulations_5 (u)
integer, intent(in) :: u
type(string_t) :: libname, procname1, sample
type(rt_data_t), target :: global
class(eio_t), allocatable :: eio
type(simulation_t), allocatable, target :: simulation

write (u, "(A)")  "* Test output: simulations_5"
write (u, "(A)")  "* Purpose: generate events for a single process"
write (u, "(A)")  "* write to file and reread"
write (u, "(A)")

write (u, "(A)")  "* Initialize processes"
write (u, "(A)")

call syntax_model_file_init ()

call global%global_init ()
call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

libname = "simulation_5a"
procname1 = "simulation_5p"

call prepare_test_library (global, libname, 1, [procname1])

```

```

call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$run_id"), &
    var_str ("simulations5"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
sample = "simulations5"
call global%set_string (var_str ("$sample"), &
    sample, is_known = .true.)
allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

write (u, "(A)")  "* Initialize raw event file"
write (u, "(A)")

allocate (eio_raw_t :: eio)
call eio%init_out (sample)

write (u, "(A)")  "* Generate an event"
write (u, "(A)")

call simulation%generate (1)
call simulation%write_event (u)
call simulation%write_event (eio)

call eio%final ()
deallocate (eio)

```

```

call simulation%final ()
deallocate (simulation)

write (u, "(A)")
write (u, "(A)")  "* Re-read the event from file"
write (u, "(A)")

call global%set_log (var_str ("?update_sqme"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?update_weight"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()
allocate (eio_raw_t :: eio)
call eio%init_in (sample)

call simulation%read_event (eio)
call simulation%write_event (u)

write (u, "(A)")
write (u, "(A)")  "* Recalculate process instance"
write (u, "(A)")

call simulation%recalculate ()
call simulation%entry(simulation%i_prc)%evaluate_expressions ()
call simulation%write_event (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()
call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_5"

end subroutine simulations_5

```

Event I/O

Generate event for a real process with structure functions, write to file and reread.

```

<Simulations: execute tests>+≡
call test (simulations_6, "simulations_6", &
    "raw event I/O with structure functions", &
    u, results)

```

<Simulations: tests>+≡

```

subroutine simulations_6 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname1, sample
  type(rt_data_t), target :: global
  class(eio_t), allocatable :: eio
  type(simulation_t), allocatable, target :: simulation
  type(flavor_t) :: flv
  type(string_t) :: name

  write (u, "(A)")  "* Test output: simulations_6"
  write (u, "(A)")  "* Purpose: generate events for a single process"
  write (u, "(A)")  "*           write to file and reread"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize process and integrate"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()
  call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
  call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

  libname = "simulation_6"
  procname1 = "simulation_6p"

  call prepare_test_library (global, libname, 1, [procname1])
  call compile_library (libname, global)

  call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
  call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)
  call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

  call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
  call global%set_string (var_str ("$phs_method"), &
    var_str ("wood"), is_known = .true.)
  call global%set_string (var_str ("$integration_method"), &
    var_str ("vamp"), is_known = .true.)
  call global%set_log (var_str ("?use_vamp_equivalences"), &
    .true., is_known = .true.)
  call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
  call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
  call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

```

```

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), &
    0._default)

call flv%init (25, global%model)
name = flv%get_name ()

call global%beam_structure%init_sf ([name, name], [1])
call global%beam_structure%set_sf (1, 1, var_str ("sf_test_1"))

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$_run_id"), &
    var_str ("r1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call reset_interaction_counter ()

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
sample = "simulations6"
call global%set_string (var_str ("$_sample"), &
    sample, is_known = .true.)
allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

write (u, "(A)")  "* Initialize raw event file"
write (u, "(A)")

allocate (eio_raw_t :: eio)
call eio%init_out (sample)

write (u, "(A)")  "* Generate an event"
write (u, "(A)")

call simulation%generate (1)
call pacify (simulation%entry(simulation%i_prc))
call simulation%write_event (u, verbose = .true., testflag = .true.)
call simulation%write_event (eio)

call eio%final ()
deallocate (eio)
call simulation%final ()
deallocate (simulation)

write (u, "(A)")
write (u, "(A)")  "* Re-read the event from file"
write (u, "(A)")

```

```

call reset_interaction_counter ()

call global%set_log (var_str ("?update_sqme"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?update_weight"), &
    .true., is_known = .true.)

allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()
allocate (eio_raw_t :: eio)
call eio%init_in (sample)

call simulation%read_event (eio)
call simulation%write_event (u, verbose = .true., testflag = .true.)

write (u, "(A)")
write (u, "(A)")  "* Recalculate process instance"
write (u, "(A)")

call simulation%recalculate ()
call simulation%entry(simulation%i_prc)%evaluate_expressions ()
call simulation%write_event (u, verbose = .true., testflag = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call eio%final ()
call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_6"

end subroutine simulations_6

```

Automatic Event I/O

Generate events with raw-format event file as cache: generate, reread, append.

<Simulations: execute tests>+≡

```

call test (simulations_7, "simulations_7", &
    "automatic raw event I/O", &
    u, results)

```

<Simulations: tests>+≡

```

subroutine simulations_7 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname1, sample
    type(rt_data_t), target :: global
    type(string_t), dimension(0) :: empty_string_array
    type(event_sample_data_t) :: data
    type(event_stream_array_t) :: es_array
    type(simulation_t), allocatable, target :: simulation

```

```

type(flavor_t) :: flv
type(string_t) :: name

write (u, "(A)")  "* Test output: simulations_7"
write (u, "(A)")  "*   Purpose: generate events for a single process"
write (u, "(A)")  "*               write to file and reread"
write (u, "(A)")

write (u, "(A)")  "* Initialize process and integrate"
write (u, "(A)")

call syntax_model_file_init ()

call global%global_init ()
call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

libname = "simulation_7"
procname1 = "simulation_7p"

call prepare_test_library (global, libname, 1, [procname1])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("wood"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("vamp"), is_known = .true.)
call global%set_log (var_str ("?use_vamp_equivalences"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), &
    0._default)

```

```

call flv%init (25, global%model)
name = flv%get_name ()

call global%beam_structure%init_sf ([name, name], [1])
call global%beam_structure%set_sf (1, 1, var_str ("sf_test_1"))

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$_run_id"), &
    var_str ("r1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call reset_interaction_counter ()

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
sample = "simulations7"
call global%set_string (var_str ("$_sample"), &
    sample, is_known = .true.)
allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

write (u, "(A)")  "* Initialize raw event file"
write (u, "(A)")

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = simulation%get_md5sum_cfg ()
call es_array%init (sample, [var_str ("raw")], global, data)

write (u, "(A)")  "* Generate an event"
write (u, "(A)")

call simulation%generate (1, es_array)

call es_array%final ()
call simulation%final ()
deallocate (simulation)

write (u, "(A)")  "* Re-read the event from file and generate another one"
write (u, "(A)")

call global%set_log (&
    var_str ("?rebuild_events"), .false., is_known = .true.)

call reset_interaction_counter ()

allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

```



```

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = simulation%get_md5sum_cfg ()
call es_array%init (sample, empty_string_array, global, data, &
    input = var_str ("raw"))

call simulation%generate (2, es_array)

call pacify (simulation%entry(simulation%i_prc))
call simulation%write_event (u, verbose = .true.)

call es_array%final ()
call simulation%final ()
deallocate (simulation)

write (u, "(A)")
write (u, "(A)")  "* Re-read both events from file"
write (u, "(A)")

call reset_interaction_counter ()

allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = simulation%get_md5sum_cfg ()
call es_array%init (sample, empty_string_array, global, data, &
    input = var_str ("raw"))

call simulation%generate (2, es_array)

call pacify (simulation%entry(simulation%i_prc))
call simulation%write_event (u, verbose = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call es_array%final ()
call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_7"

end subroutine simulations_7

```

Rescanning Events

Generate events and rescan the resulting raw event file.

<Simulations: execute tests>+≡

```

call test (simulations_8, "simulations_8", &
         "rescan raw event file", &
         u, results)
<Simulations: tests>+≡
subroutine simulations_8 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname1, sample
  type(rt_data_t), target :: global
  type(string_t), dimension(0) :: empty_string_array
  type(event_sample_data_t) :: data
  type(event_stream_array_t) :: es_array
  type(simulation_t), allocatable, target :: simulation
  type(flavor_t) :: flv
  type(string_t) :: name

  write (u, "(A)")  "* Test output: simulations_8"
  write (u, "(A)")  "* Purpose: generate events for a single process"
  write (u, "(A)")  "*           write to file and rescan"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize process and integrate"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()
  call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

  call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
  call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

  libname = "simulation_8"
  procname1 = "simulation_8p"

  call prepare_test_library (global, libname, 1, [procname1])
  call compile_library (libname, global)

  call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
  call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)
  call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

  call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
  call global%set_string (var_str ("$phs_method"), &
    var_str ("wood"), is_known = .true.)
  call global%set_string (var_str ("$integration_method"), &
    var_str ("vamp"), is_known = .true.)
  call global%set_log (var_str ("?use_vamp_equivalences"), &

```

```

        .true., is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), &
    0._default)

call flv%init (25, global%model)
name = flv%get_name ()

call global%beam_structure%init_sf ([name, name], [1])
call global%beam_structure%set_sf (1, 1, var_str ("sf_test_1"))

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$_run_id"), &
    var_str ("r1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call reset_interaction_counter ()

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
sample = "simulations8"
call global%set_string (var_str ("$_sample"), &
    sample, is_known = .true.)
allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

write (u, "(A)")  "* Initialize raw event file"
write (u, "(A)")

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = simulation%get_md5sum_cfg ()
write (u, "(1x,A,A,A)")  "MD5 sum (proc)   = '", data%md5sum_prc, "'"
write (u, "(1x,A,A,A)")  "MD5 sum (config) = '", data%md5sum_cfg, "'"
call es_array%init (sample, [var_str ("raw")], global, &
    data)

write (u, "(A)")
write (u, "(A)")  "* Generate an event"
write (u, "(A)")

call simulation%generate (1, es_array)

```

```

call pacify (simulation%entry(simulation%i_prc))
call simulation%write_event (u, verbose = .true., testflag = .true.)

call es_array%final ()
call simulation%final ()
deallocate (simulation)

write (u, "(A)")
write (u, "(A)")  "* Re-read the event from file"
write (u, "(A)")

call reset_interaction_counter ()

allocate (simulation)
call simulation%init ([procname1], .false., .false., global)
call simulation%init_process_selector ()

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = ""
write (u, "(1x,A,A,A)")  "MD5 sum (proc)   = '", data%md5sum_prc, "'"
write (u, "(1x,A,A,A)")  "MD5 sum (config) = '", data%md5sum_cfg, "'"
call es_array%init (sample, empty_string_array, global, data, &
    input = var_str ("raw"), input_sample = sample, allow_switch = .false.)

call simulation%rescan (1, es_array, global = global)

write (u, "(A)")

call pacify (simulation%entry(simulation%i_prc))
call simulation%write_event (u, verbose = .true., testflag = .true.)

call es_array%final ()
call simulation%final ()
deallocate (simulation)

write (u, "(A)")
write (u, "(A)")  "* Re-read again and recalculate"
write (u, "(A)")

call reset_interaction_counter ()

call global%set_log (var_str ("?update_sqme"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?update_event"), &
    .true., is_known = .true.)

allocate (simulation)
call simulation%init ([procname1], .false., .false., global)
call simulation%init_process_selector ()

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = ""
write (u, "(1x,A,A,A)")  "MD5 sum (proc)   = '", data%md5sum_prc, "'"

```

```

write (u, "(1x,A,A,A)") "MD5 sum (config) = ', data%md5sum_cfg, "'
call es_array%init (sample, empty_string_array, global, data, &
    input = var_str ("raw"), input_sample = sample, allow_switch = .false.)

call simulation%rescan (1, es_array, global = global)

write (u, "(A)")

call pacify (simulation%entry(simulation%i_prc))
call simulation%write_event (u, verbose = .true., testflag = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call es_array%final ()
call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_8"

end subroutine simulations_8

```

Rescanning Check

Generate events and rescan with process mismatch.

```

<Simulations: execute tests>+≡
    call test (simulations_9, "simulations_9", &
        "rescan mismatch", &
        u, results)

<Simulations: tests>+≡
subroutine simulations_9 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname1, sample
    type(rt_data_t), target :: global
    type(string_t), dimension(0) :: empty_string_array
    type(event_sample_data_t) :: data
    type(event_stream_array_t) :: es_array
    type(simulation_t), allocatable, target :: simulation
    type(flavor_t) :: flv
    type(string_t) :: name
    logical :: error

    write (u, "(A)")  "* Test output: simulations_9"
    write (u, "(A)")  "*   Purpose: generate events for a single process"
    write (u, "(A)")  "*               write to file and rescan"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize process and integrate"
    write (u, "(A)")

    call syntax_model_file_init ()

```

```

call global%global_init ()
call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

libname = "simulation_9"
procname1 = "simulation_9p"

call prepare_test_library (global, libname, 1, [procname1])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("wood"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("vamp"), is_known = .true.)
call global%set_log (var_str ("?use_vamp_equivalences"), &
    .true., is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), &
    0._default)

call flv%init (25, global%model)
name = flv%get_name ()

call global%beam_structure%init_sf ([name, name], [1])
call global%beam_structure%set_sf (1, 1, var_str ("sf_test_1"))

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$run_id"), &
    var_str ("r1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

```

```

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call reset_interaction_counter ()

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
sample = "simulations9"
call global%set_string (var_str ("sample"), &
    sample, is_known = .true.)
allocate (simulation)
call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize raw event file"
write (u, "(A)")

data%md5sum_prc = simulation%get_md5sum_prc ()
data%md5sum_cfg = simulation%get_md5sum_cfg ()
write (u, "(1x,A,A,A)")  "MD5 sum (proc) = '", data%md5sum_prc, "'"
write (u, "(1x,A,A,A)")  "MD5 sum (config) = '", data%md5sum_cfg, "'"
call es_array%init (sample, [var_str ("raw")], global, &
    data)

write (u, "(A)")
write (u, "(A)")  "* Generate an event"
write (u, "(A)")

call simulation%generate (1, es_array)

call es_array%final ()
call simulation%final ()
deallocate (simulation)

write (u, "(A)")  "* Initialize event generation for different parameters"
write (u, "(A)")

call reset_interaction_counter ()

allocate (simulation)
call simulation%init ([procname1, procname1], .false., .false., global)
call simulation%init_process_selector ()

call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Attempt to re-read the events (should fail)"
write (u, "(A)")

data%md5sum_prc = simulation%get_md5sum_prc ()

```

```

data%md5sum_cfg = ""
write (u, "(1x,A,A,A)") "MD5 sum (proc) = '", data%md5sum_prc, "'"
write (u, "(1x,A,A,A)") "MD5 sum (config) = '", data%md5sum_cfg, "'"
call es_array%init (sample, empty_string_array, global, data, &
    input = var_str ("raw"), input_sample = sample, &
    allow_switch = .false., error = error)

write (u, "(1x,A,L1)") "error = ", error

call simulation%rescan (1, es_array, global = global)

call es_array%final ()
call simulation%final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_9"

end subroutine simulations_9

```

Alternative weights

Generate an event for a single process and reweight it in a simultaneous calculation.

```

<Simulations: execute tests>+≡
    call test (simulations_10, "simulations_10", &
        "alternative weight", &
        u, results)

<Simulations: tests>+≡
subroutine simulations_10 (u)
    integer, intent(in) :: u
    type(string_t) :: libname, procname1, expr_text
    type(rt_data_t), target :: global
    type(rt_data_t), dimension(1), target :: alt_env
    type(ifile_t) :: ifile
    type(stream_t) :: stream
    type(parse_tree_t) :: pt_weight
    type(simulation_t), target :: simulation
    type(event_sample_data_t) :: data

    write (u, "(A)")  "* Test output: simulations_10"
    write (u, "(A)")  "* Purpose: reweight event"
    write (u, "(A)")

    write (u, "(A)")  "* Initialize processes"
    write (u, "(A)")

    call syntax_model_file_init ()
    call syntax_pexpr_init ()

    call global%global_init ()
    call global%set_log (var_str ("?omega_openmp"), &

```



```

        .false., is_known = .true.)
call global%set_int (var_str ("seed"), &
    0, is_known = .true.)

libname = "simulation_10a"
procname1 = "simulation_10p"

call prepare_test_library (global, libname, 1, [procname1])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$run_id"), &
    var_str ("simulations1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize alternative environment with custom weight"
write (u, "(A)")

call alt_env(1)%local_init (global)
call alt_env(1)%activate ()

expr_text = "2"
write (u, "(A,A)")  "weight = ", char (expr_text)
write (u, *)

call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_weight, stream, .true.)
call stream_final (stream)

```

```

alt_env(1)%pn%weight_expr => parse_tree_get_root_ptr (pt_weight)
call alt_env(1)%write_expr (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
call simulation%init ([procname1], .true., .true., global, alt_env=alt_env)
call simulation%init_process_selector ()

data = simulation%get_data ()
call data%write (u)

write (u, "(A)")
write (u, "(A)")  "* Generate an event"
write (u, "(A)")

call simulation%generate (1)
call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Write the event record for the last event"
write (u, "(A)")

call simulation%write_event (u)

write (u, "(A)")
write (u, "(A)")  "* Write the event record for the alternative setup"
write (u, "(A)")

call simulation%write_alt_event (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call simulation%final ()
call global%final ()

call syntax_model_file_final ()
call syntax_pexpr_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_10"

end subroutine simulations_10

```

Decays

Generate an event with subsequent partonic decays.

<Simulations: execute tests>+≡

```

call test (simulations_11, "simulations_11", &
          "decay", &
          u, results)
<Simulations: tests>+≡
subroutine simulations_11 (u)
  integer, intent(in) :: u
  type(rt_data_t), target :: global
  type(prclib_entry_t), pointer :: lib
  type(string_t) :: prefix, procname1, procname2
  type(simulation_t), target :: simulation

  write (u, "(A)")  "* Test output: simulations_11"
  write (u, "(A)")  "* Purpose: apply decay"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize processes"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()
  allocate (lib)
  call global%add_prclib (lib)

  call global%set_int (var_str ("seed"), &
                     0, is_known = .true.)
  call global%set_log (var_str ("?recover_beams"), &
                     .false., is_known = .true.)

  prefix = "simulation_11"
  procname1 = prefix // "_p"
  procname2 = prefix // "_d"
  call prepare_testbed &
    (global%prclib, global%process_stack, &
     prefix, global%os_data, &
     scattering=.true., decay=.true.)

  call global%select_model (var_str ("Test"))
  call global%model%set_par (var_str ("ff"), 0.4_default)
  call global%model%set_par (var_str ("mf"), &
    global%model%get_real (var_str ("ff")) &
    * global%model%get_real (var_str ("ms")))
  call global%model%set_unstable (25, [procname2])

  write (u, "(A)")  "* Initialize simulation object"
  write (u, "(A)")

  call simulation%init ([procname1], .true., .true., global)
  call simulation%init_process_selector ()

  write (u, "(A)")  "* Generate event"
  write (u, "(A)")

  call simulation%generate (1)

```

```

call simulation%write (u)

write (u, *)

call simulation%write_event (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"
write (u, "(A)")

call simulation%final ()
call global%final ()

call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_11"

end subroutine simulations_11

```

Split Event Files

Generate event for a real process with structure functions and write to file, accepting a limit for the number of events per file.

```

<Simulations: execute tests>+=
call test (simulations_12, "simulations_12", &
  "split event files", &
  u, results)

<Simulations: tests>+=
subroutine simulations_12 (u)
  integer, intent(in) :: u
  type(string_t) :: libname, procname1, sample
  type(rt_data_t), target :: global
  class(eio_t), allocatable :: eio
  type(simulation_t), allocatable, target :: simulation
  type(flavor_t) :: flv
  integer :: i_evt

  write (u, "(A)")  "* Test output: simulations_12"
  write (u, "(A)")  "*   Purpose: generate events for a single process"
  write (u, "(A)")  "*               and write to split event files"
  write (u, "(A)")

  write (u, "(A)")  "* Initialize process and integrate"
  write (u, "(A)")

  call syntax_model_file_init ()

  call global%global_init ()
  call global%set_log (var_str ("?omega_openmp"), &
    .false., is_known = .true.)
  call global%set_int (var_str ("seed"), &

```

```

0, is_known = .true.)

libname = "simulation_12"
procname1 = "simulation_12p"

call prepare_test_library (global, libname, 1, [procname1])
call compile_library (libname, global)

call global%append_log (&
    var_str ("?rebuild_phase_space"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_grids"), .true., intrinsic = .true.)
call global%append_log (&
    var_str ("?rebuild_events"), .true., intrinsic = .true.)

call global%set_string (var_str ("$method"), &
    var_str ("unit_test"), is_known = .true.)
call global%set_string (var_str ("$phs_method"), &
    var_str ("single"), is_known = .true.)
call global%set_string (var_str ("$integration_method"), &
    var_str ("midpoint"), is_known = .true.)
call global%set_log (var_str ("?vis_history"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?integration_timer"), &
    .false., is_known = .true.)
call global%set_log (var_str ("?recover_beams"), &
    .false., is_known = .true.)

call global%set_real (var_str ("sqrts"), &
    1000._default, is_known = .true.)
call global%model_set_real (var_str ("ms"), &
    0._default)

call flv%init (25, global%model)

call global%it_list%init ([1], [1000])

call global%set_string (var_str ("$run_id"), &
    var_str ("r1"), is_known = .true.)
call integrate_process (procname1, global, local_stack=.true.)

write (u, "(A)")  "* Initialize event generation"
write (u, "(A)")

call global%set_log (var_str ("?unweighted"), &
    .false., is_known = .true.)
sample = "simulations_12"
call global%set_string (var_str ("$sample"), &
    sample, is_known = .true.)
call global%set_int (var_str ("sample_split_n_evt"), &
    2, is_known = .true.)
call global%set_int (var_str ("sample_split_index"), &
    42, is_known = .true.)
allocate (simulation)

```

```

call simulation%init ([procname1], .true., .true., global)
call simulation%init_process_selector ()

call simulation%write (u)

write (u, "(A)")
write (u, "(A)")  "* Initialize ASCII event file"
write (u, "(A)")

allocate (eio_ascii_short_t :: eio)
select type (eio)
class is (eio_ascii_t); call eio%set_parameters ()
end select
call eio%init_out (sample, data = simulation%get_data ())

write (u, "(A)")  "* Generate 5 events, distributed among three files"

do i_evt = 1, 5
    call simulation%generate (1)
    call simulation%write_event (eio)
end do

call eio%final ()
deallocate (eio)
call simulation%final ()
deallocate (simulation)

write (u, *)
call display_file ("simulations_12.42.short.evt", u)
write (u, *)
call display_file ("simulations_12.43.short.evt", u)
write (u, *)
call display_file ("simulations_12.44.short.evt", u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: simulations_12"

end subroutine simulations_12

```

Auxiliary: display file contents.

<Simulations: tests>+≡

```

subroutine display_file (file, u)
    character(*), intent(in) :: file
    integer, intent(in) :: u
    character(256) :: buffer
    integer :: u_file
    write (u, "(3A)")  "* Contents of file '", file, "':"
    write (u, *)

```

```

u_file = free_unit ()
open (u_file, file = file, action = "read", status = "old")
do
  read (u_file, "(A)", end = 1)  buffer
  write (u, "(A)")  trim (buffer)
end do
1  continue
end subroutine display_file

```

Chapter 29

More Unit Tests

This chapter collects some procedures for testing that can't be provided at the point where the corresponding modules are defined, because they use other modules of a different level.

(We should move them back, collecting the high-level functionality in init/final hooks that we can set at runtime.)

29.1 Expression Testing

Expression objects are part of process and event objects, but the process and event object modules should not depend on the implementation of expressions. Here, we collect unit tests that depend on expression implementation.

```
(expr_tests.f90)≡  
  <File header>  
  module expr_tests  
  
    <Use kinds>  
    <Use strings>  
    use format_defs, only: FMT_12  
    use format_utils, only: write_separator  
    use unit_tests  
    use os_interface  
    use ifiles  
    use lexers  
    use parser  
    use lorentz  
    use sm_qcd  
    use model_data  
    use interactions, only: reset_interaction_counter  
    use variables  
    use expr_base  
    use eval_trees  
    use models  
    use subevents  
    use subvt_expr  
    use phs_base  
    use rng_base
```



```

use mci_base
use process_libraries
use prc_test
use prc_core
use processes
use events

```

⟨Standard module head⟩

⟨Expr tests: public⟩

contains

⟨Expr tests: tests⟩

end module expr_tests

29.1.1 Test

This is the master for calling self-test procedures.

⟨Expr tests: public⟩≡

```
public :: subevt_expr_test
```

⟨Expr tests: tests⟩≡

```

subroutine subevt_expr_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
⟨Expr tests: execute tests⟩
end subroutine subevt_expr_test

```

Parton-event expressions

⟨Expr tests: execute tests⟩≡

```

call test (subevt_expr_1, "subevt_expr_1", &
  "parton-event expressions", &
  u, results)

```

⟨Expr tests: tests⟩+≡

```

subroutine subevt_expr_1 (u)
  integer, intent(in) :: u
  type(string_t) :: expr_text
  type(ifile_t) :: ifile
  type(stream_t) :: stream
  type(parse_tree_t) :: pt_cuts, pt_scale, pt_fac_scale, pt_ren_scale
  type(parse_tree_t) :: pt_weight
  type(parse_node_t), pointer :: pn_cuts, pn_scale, pn_fac_scale, pn_ren_scale
  type(parse_node_t), pointer :: pn_weight
  type(eval_tree_factory_t) :: expr_factory
  type(os_data_t) :: os_data
  type(model_t), target :: model
  type(parton_expr_t), target :: expr
  real(default) :: E, Ex, m
  type(vector4_t), dimension(6) :: p

```

```

integer :: i, pdg
logical :: passed
real(default) :: scale, fac_scale, ren_scale, weight

write (u, "(A)")  "* Test output: subevt_expr_1"
write (u, "(A)")  "* Purpose: Set up a subevt and associated &
                    &process-specific expressions"
write (u, "(A)")

call syntax_pexpr_init ()

call syntax_model_file_init ()
call os_data_init (os_data)
call model%read (var_str ("Test.mdl"), os_data)

write (u, "(A)")  "* Expression texts"
write (u, "(A)")

expr_text = "all Pt > 100 [s]"
write (u, "(A,A)") "cuts = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_lexpr (pt_cuts, stream, .true.)
call stream_final (stream)
pn_cuts => parse_tree_get_root_ptr (pt_cuts)

expr_text = "sqrts"
write (u, "(A,A)") "scale = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_scale, stream, .true.)
call stream_final (stream)
pn_scale => parse_tree_get_root_ptr (pt_scale)

expr_text = "sqrts_hat"
write (u, "(A,A)") "fac_scale = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_fac_scale, stream, .true.)
call stream_final (stream)
pn_fac_scale => parse_tree_get_root_ptr (pt_fac_scale)

expr_text = "100"
write (u, "(A,A)") "ren_scale = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_ren_scale, stream, .true.)
call stream_final (stream)
pn_ren_scale => parse_tree_get_root_ptr (pt_ren_scale)

```

```

expr_text = "n_tot - n_in - n_out"
write (u, "(A,A)") "weight = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_weight, stream, .true.)
call stream_final (stream)
pn_weight => parse_tree_get_root_ptr (pt_weight)

call ifile_final (ifile)

write (u, "(A)")
write (u, "(A)")  "* Initialize process expr"
write (u, "(A)")

call expr%setup_vars (1000._default)
call var_list_append_real (expr%var_list, var_str ("tolerance"), 0._default)
call expr%link_var_list (model%get_var_list_ptr ())

call expr_factory%init (pn_cuts)
call expr%setup_selection (expr_factory)
call expr_factory%init (pn_scale)
call expr%setup_scale (expr_factory)
call expr_factory%init (pn_fac_scale)
call expr%setup_fac_scale (expr_factory)
call expr_factory%init (pn_ren_scale)
call expr%setup_ren_scale (expr_factory)
call expr_factory%init (pn_weight)
call expr%setup_weight (expr_factory)

call write_separator (u)
call expr%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Fill subevt and evaluate expressions"
write (u, "(A)")

call subevt_init (expr%subevt_t, 6)
E = 500._default
Ex = 400._default
m = 125._default
pdg = 25
p(1) = vector4_moving (E, sqrt (E**2 - m**2), 3)
p(2) = vector4_moving (E, -sqrt (E**2 - m**2), 3)
p(3) = vector4_moving (Ex, sqrt (Ex**2 - m**2), 3)
p(4) = vector4_moving (Ex, -sqrt (Ex**2 - m**2), 3)
p(5) = vector4_moving (Ex, sqrt (Ex**2 - m**2), 1)
p(6) = vector4_moving (Ex, -sqrt (Ex**2 - m**2), 1)

call expr%reset ()
do i = 1, 2
    call subevt_set_beam (expr%subevt_t, i, pdg, p(i), m**2)

```

```

end do
do i = 3, 4
    call subevt_set_incoming (expr%subevt_t, i, pdg, p(i), m**2)
end do
do i = 5, 6
    call subevt_set_outgoing (expr%subevt_t, i, pdg, p(i), m**2)
end do
expr%sqrts_hat = subevt_get_sqrts_hat (expr%subevt_t)
expr%n_in = 2
expr%n_out = 2
expr%n_tot = 4
expr%subevt_filled = .true.

call expr%evaluate (passed, scale, fac_scale, ren_scale, weight)

write (u, "(A,L1)")          "Event has passed      = ", passed
write (u, "(A," // FMT_12 // ")") "Scale              = ", scale
write (u, "(A," // FMT_12 // ")") "Factorization scale = ", fac_scale
write (u, "(A," // FMT_12 // ")") "Renormalization scale = ", ren_scale
write (u, "(A," // FMT_12 // ")") "Weight              = ", weight
write (u, "(A)")

call write_separator (u)
call expr%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call expr%final ()

call model%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: subevt_expr_1"

end subroutine subevt_expr_1

```

Parton-event expressions

```

⟨Expr tests: execute tests⟩+≡
    call test (subevt_expr_2, "subevt_expr_2", &
        "parton-event expressions", &
        u, results)

⟨Expr tests: tests⟩+≡
    subroutine subevt_expr_2 (u)
        integer, intent(in) :: u
        type(string_t) :: expr_text
        type(ifile_t) :: ifile
        type(stream_t) :: stream
        type(parse_tree_t) :: pt_selection

```

```

type(parse_tree_t) :: pt_reweight, pt_analysis
type(parse_node_t), pointer :: pn_selection
type(parse_node_t), pointer :: pn_reweight, pn_analysis
type(os_data_t) :: os_data
type(model_t), target :: model
type(eval_tree_factory_t) :: expr_factory
type(event_expr_t), target :: expr
real(default) :: E, Ex, m
type(vector4_t), dimension(6) :: p
integer :: i, pdg
logical :: passed
real(default) :: reweight
logical :: analysis_flag

write (u, "(A)")  "* Test output: subevt_expr_2"
write (u, "(A)")  "* Purpose: Set up a subevt and associated &
                  &process-specific expressions"
write (u, "(A)")

call syntax_pexpr_init ()

call syntax_model_file_init ()
call os_data_init (os_data)
call model%read (var_str ("Test.mdl"), os_data)

write (u, "(A)")  "* Expression texts"
write (u, "(A)")

expr_text = "all Pt > 100 [s]"
write (u, "(A,A)") "selection = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_lexpr (pt_selection, stream, .true.)
call stream_final (stream)
pn_selection => parse_tree_get_root_ptr (pt_selection)

expr_text = "n_tot - n_in - n_out"
write (u, "(A,A)") "reweight = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_reweight, stream, .true.)
call stream_final (stream)
pn_reweight => parse_tree_get_root_ptr (pt_reweight)

expr_text = "true"
write (u, "(A,A)") "analysis = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_lexpr (pt_analysis, stream, .true.)
call stream_final (stream)

```

```

pn_analysis => parse_tree_get_root_ptr (pt_analysis)

call ifile_final (ifile)

write (u, "(A)")
write (u, "(A)")  "* Initialize process expr"
write (u, "(A)")

call expr%setup_vars (1000._default)
call expr%link_var_list (model%get_var_list_ptr ())
call var_list_append_real (expr%var_list, var_str ("tolerance"), 0._default)

call expr_factory%init (pn_selection)
call expr%setup_selection (expr_factory)
call expr_factory%init (pn_analysis)
call expr%setup_analysis (expr_factory)
call expr_factory%init (pn_reweight)
call expr%setup_reweight (expr_factory)

call write_separator (u)
call expr%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Fill subevt and evaluate expressions"
write (u, "(A)")

call subevt_init (expr%subevt_t, 6)
E = 500._default
Ex = 400._default
m = 125._default
pdg = 25
p(1) = vector4_moving (E, sqrt (E**2 - m**2), 3)
p(2) = vector4_moving (E, -sqrt (E**2 - m**2), 3)
p(3) = vector4_moving (Ex, sqrt (Ex**2 - m**2), 3)
p(4) = vector4_moving (Ex, -sqrt (Ex**2 - m**2), 3)
p(5) = vector4_moving (Ex, sqrt (Ex**2 - m**2), 1)
p(6) = vector4_moving (Ex, -sqrt (Ex**2 - m**2), 1)

call expr%reset ()
do i = 1, 2
    call subevt_set_beam (expr%subevt_t, i, pdg, p(i), m**2)
end do
do i = 3, 4
    call subevt_set_incoming (expr%subevt_t, i, pdg, p(i), m**2)
end do
do i = 5, 6
    call subevt_set_outgoing (expr%subevt_t, i, pdg, p(i), m**2)
end do
expr%sqrts_hat = subevt_get_sqrts_hat (expr%subevt_t)
expr%n_in = 2
expr%n_out = 2
expr%n_tot = 4
expr%subevt_filled = .true.

```

```

call expr%evaluate (passed, reweight, analysis_flag)

write (u, "(A,L1)")      "Event has passed      = ", passed
write (u, "(A," // FMT_12 // ")") "Reweighting factor  = ", reweight
write (u, "(A,L1)")      "Analysis flag        = ", analysis_flag
write (u, "(A)")

call write_separator (u)
call expr%write (u)
call write_separator (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call expr%final ()

call model%final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: subevt_expr_2"

end subroutine subevt_expr_2

```

Processes: handle partonic cuts

Initialize a process and process instance, choose a sampling point and fill the process instance, evaluating a given cut configuration.

We use the same trivial process as for the previous test. All momentum and state dependence is trivial, so we just test basic functionality.

```

<Expr tests: execute tests>+≡
  call test (processes_5, "processes_5", &
    "handle cuts (partonic event)", &
    u, results)

<Expr tests: tests>+≡
  subroutine processes_5 (u)
    integer, intent(in) :: u
    type(string_t) :: cut_expr_text
    type(ifile_t) :: ifile
    type(stream_t) :: stream
    type(parse_tree_t) :: parse_tree
    type(eval_tree_factory_t) :: expr_factory
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    type(model_t), pointer :: model_tmp
    class(model_data_t), pointer :: model

```

```

type(var_list_t), target :: var_list
type(process_t), allocatable, target :: process
class(prc_core_t), allocatable :: core_template
class(mci_t), allocatable :: mci_template
class(phs_config_t), allocatable :: phs_config_template
real(default) :: sqrts
type(process_instance_t), allocatable, target :: process_instance

write (u, "(A)")  "* Test output: processes_5"
write (u, "(A)")  "*   Purpose: create a process &
                  &and fill a process instance"
write (u, "(A)")

write (u, "(A)")  "* Prepare a cut expression"
write (u, "(A)")

call syntax_pexpr_init ()
cut_expr_text = "all Pt > 100 [s]"
call ifile_append (ifile, cut_expr_text)
call stream_init (stream, ifile)
call parse_tree_init_lexpr (parse_tree, stream, .true.)

write (u, "(A)")  "* Build and initialize a test process"
write (u, "(A)")

libname = "processes5"
procname = libname
run_id = "run5"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

call syntax_model_file_init ()
allocate (model_tmp)
call model_tmp%read (var_str ("Test.mdl"), os_data)
call var_list_init_snapshot (var_list, model_tmp%get_var_list_ptr ())
model => model_tmp

call reset_interaction_counter ()

allocate (process)
call process%init &
      (procname, run_id, lib, os_data, qcd, rng_factory, model)

call var_list_append_real &
      (var_list, var_str ("tolerance"), 0._default)
call process%set_var_list (var_list)
call var_list%final ()

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
      (1, core_template, mci_template, phs_config_template)

```



```

write (u, "(A)")  "* Prepare a trivial beam setup"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()
call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization and set cuts"
write (u, "(A)")

call process%setup_terms ()
call expr_factory%init (parse_tree_get_root_ptr (parse_tree))
call process%set_cuts (expr_factory)
call process%write (.false., u, show_var_list=.true., show_expressions=.true.)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)

write (u, "(A)")
write (u, "(A)")  "* Inject a set of random numbers"
write (u, "(A)")

call process_instance%choose_mci (1)
call process_instance%set_mcpars ([0._default, 0._default])

write (u, "(A)")
write (u, "(A)")  "* Set up kinematics and subevt, check cuts (should fail)"
write (u, "(A)")

call process_instance%select_channel (1)
call process_instance%compute_seed_kinematics ()
call process_instance%compute_hard_kinematics ()
call process_instance%compute_eff_kinematics ()
call process_instance%evaluate_expressions ()
call process_instance%compute_other_channels ()

call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Evaluate for another set (should succeed)"
write (u, "(A)")

call process_instance%reset ()
call process_instance%set_mcpars ([0.5_default, 0.125_default])
call process_instance%select_channel (1)
call process_instance%compute_seed_kinematics ()
call process_instance%compute_hard_kinematics ()
call process_instance%compute_eff_kinematics ()
call process_instance%evaluate_expressions ()

```

```

call process_instance%compute_other_channels ()
call process_instance%evaluate_trace ()

call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Evaluate for another set using convenience procedure &
                  &(failure)"
write (u, "(A)")

call process_instance%evaluate_sqme (1, [0.0_default, 0.2_default])

call process_instance%write_header (u)

write (u, "(A)")
write (u, "(A)")  "* Evaluate for another set using convenience procedure &
                  &(success)"
write (u, "(A)")

call process_instance%evaluate_sqme (1, [0.1_default, 0.2_default])

call process_instance%write_header (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

call parse_tree_final (parse_tree)
call stream_final (stream)
call ifile_final (ifile)
call syntax_pexpr_final ()

call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_5"

end subroutine processes_5

```

Processes: scales and such

Initialize a process and process instance, choose a sampling point and fill the process instance, evaluating a given cut configuration.

We use the same trivial process as for the previous test. All momentum and state dependence is trivial, so we just test basic functionality.

```

(Expr tests: execute tests) +=
  call test (processes_6, "processes_6", &

```

```

        "handle scales and weight (partonic event)", &
        u, results)
<Expr tests: tests>+=
subroutine processes_6 (u)
    integer, intent(in) :: u
    type(string_t) :: expr_text
    type(ifile_t) :: ifile
    type(stream_t) :: stream
    type(parse_tree_t) :: pt_scale, pt_fac_scale, pt_ren_scale, pt_weight
    type(process_library_t), target :: lib
    type(string_t) :: libname
    type(string_t) :: procname
    type(string_t) :: run_id
    type(os_data_t) :: os_data
    type(qcd_t) :: qcd
    class(rng_factory_t), allocatable :: rng_factory
    type(model_t), pointer :: model_tmp
    class(model_data_t), pointer :: model
    type(var_list_t), target :: var_list
    type(process_t), allocatable, target :: process
    class(prc_core_t), allocatable :: core_template
    class(mci_t), allocatable :: mci_template
    class(phs_config_t), allocatable :: phs_config_template
    real(default) :: sqrts
    type(process_instance_t), allocatable, target :: process_instance
    type(eval_tree_factory_t) :: expr_factory

    write (u, "(A)")  "* Test output: processes_6"
    write (u, "(A)")  "*   Purpose: create a process &
        &and fill a process instance"
    write (u, "(A)")

    write (u, "(A)")  "* Prepare expressions"
    write (u, "(A)")

    call syntax_pexpr_init ()

    expr_text = "sqrts - 100 GeV"
    write (u, "(A,A)") "scale = ", char (expr_text)
    call ifile_clear (ifile)
    call ifile_append (ifile, expr_text)
    call stream_init (stream, ifile)
    call parse_tree_init_expr (pt_scale, stream, .true.)
    call stream_final (stream)

    expr_text = "sqrts_hat"
    write (u, "(A,A)") "fac_scale = ", char (expr_text)
    call ifile_clear (ifile)
    call ifile_append (ifile, expr_text)
    call stream_init (stream, ifile)
    call parse_tree_init_expr (pt_fac_scale, stream, .true.)
    call stream_final (stream)

    expr_text = "eval sqrt (M2) [collect [s]]"

```

```

write (u, "(A,A)") "ren_scale = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_ren_scale, stream, .true.)
call stream_final (stream)

expr_text = "n_tot * n_in * n_out * (eval Phi / pi [s])"
write (u, "(A,A)") "weight = ", char (expr_text)
call ifile_clear (ifile)
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call parse_tree_init_expr (pt_weight, stream, .true.)
call stream_final (stream)

call ifile_final (ifile)

write (u, "(A)")
write (u, "(A)") "* Build and initialize a test process"
write (u, "(A)")

libname = "processes4"
procname = libname
run_id = "run4"
call os_data_init (os_data)
allocate (rng_test_factory_t :: rng_factory)
call prc_test_create_library (libname, lib)

call syntax_model_file_init ()
allocate (model_tmp)
call model_tmp%read (var_str ("Test.mdl"), os_data)
call var_list_init_snapshot (var_list, model_tmp%get_var_list_ptr ())
model => model_tmp

call reset_interaction_counter ()

allocate (process)
call process%init &
    (procname, run_id, lib, os_data, qcd, rng_factory, model)

call process%set_var_list (var_list)
call var_list%final ()

allocate (test_t :: core_template)
allocate (phs_test_config_t :: phs_config_template)
call process%init_component &
    (1, core_template, mci_template, phs_config_template)

write (u, "(A)") "* Prepare a trivial beam setup"
write (u, "(A)")

sqrts = 1000
call process%setup_beams_sqrts (sqrts)
call process%configure_phs ()

```

```

call process%setup_mci ()

write (u, "(A)")  "* Complete process initialization and set cuts"
write (u, "(A)")

call process%setup_terms ()
call expr_factory%init (parse_tree_get_root_ptr (pt_scale))
call process%set_scale (expr_factory)
call expr_factory%init (parse_tree_get_root_ptr (pt_fac_scale))
call process%set_fac_scale (expr_factory)
call expr_factory%init (parse_tree_get_root_ptr (pt_ren_scale))
call process%set_ren_scale (expr_factory)
call expr_factory%init (parse_tree_get_root_ptr (pt_weight))
call process%set_weight (expr_factory)
call process%write (.false., u, show_expressions=.true.)

write (u, "(A)")
write (u, "(A)")  "* Create a process instance and evaluate"
write (u, "(A)")

allocate (process_instance)
call process_instance%init (process)
call process_instance%choose_mci (1)
call process_instance%evaluate_sqme (1, [0.5_default, 0.125_default])

call process_instance%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call process_instance%final ()
deallocate (process_instance)

call process%final ()
deallocate (process)

call parse_tree_final (pt_scale)
call parse_tree_final (pt_fac_scale)
call parse_tree_final (pt_ren_scale)
call parse_tree_final (pt_weight)
call syntax_pexpr_final ()

call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: processes_6"

end subroutine processes_6

```

Event expressions

After generating an event, fill the `subevt` and evaluate expressions for selection, reweighting, and analysis.

```

<Expr tests: execute tests>+≡
    call test (events_3, "events_3", &
        "expression evaluation", &
        u, results)

<Expr tests: tests>+≡
    subroutine events_3 (u)
        integer, intent(in) :: u
        type(string_t) :: expr_text
        type(ifile_t) :: ifile
        type(stream_t) :: stream
        type(parse_tree_t) :: pt_selection, pt_reweight, pt_analysis
        type(eval_tree_factory_t) :: expr_factory
        type(event_t), allocatable, target :: event
        type(process_t), allocatable, target :: process
        type(process_instance_t), allocatable, target :: process_instance
        type(os_data_t) :: os_data
        type(model_t), pointer :: model
        type(var_list_t), target :: var_list

        write (u, "(A)")  "* Test output: events_3"
        write (u, "(A)")  "* Purpose: generate an event and evaluate expressions"
        write (u, "(A)")

        call syntax_pexpr_init ()

        write (u, "(A)")  "* Expression texts"
        write (u, "(A)")

        expr_text = "all Pt > 100 [s]"
        write (u, "(A,A)") "selection = ", char (expr_text)
        call ifile_clear (ifile)
        call ifile_append (ifile, expr_text)
        call stream_init (stream, ifile)
        call parse_tree_init_lexpr (pt_selection, stream, .true.)
        call stream_final (stream)

        expr_text = "1 + sqrts_hat / sqrts"
        write (u, "(A,A)") "reweight = ", char (expr_text)
        call ifile_clear (ifile)
        call ifile_append (ifile, expr_text)
        call stream_init (stream, ifile)
        call parse_tree_init_expr (pt_reweight, stream, .true.)
        call stream_final (stream)

        expr_text = "true"
        write (u, "(A,A)") "analysis = ", char (expr_text)
        call ifile_clear (ifile)
        call ifile_append (ifile, expr_text)
        call stream_init (stream, ifile)
        call parse_tree_init_lexpr (pt_analysis, stream, .true.)
        call stream_final (stream)

        call ifile_final (ifile)

```

```

write (u, "(A)")
write (u, "(A)")  "* Initialize test process event"

call os_data_init (os_data)

call syntax_model_file_init ()
allocate (model)
call model%read (var_str ("Test.mdl"), os_data)
call var_list_init_snapshot (var_list, model%get_var_list_ptr ())

allocate (process)
allocate (process_instance)
call prepare_test_process (process, process_instance, model)

call process%set_var_list (var_list)
call var_list%final ()

call process_instance%setup_event_data ()

write (u, "(A)")
write (u, "(A)")  "* Initialize event object and set expressions"

allocate (event)
call event%basic_init ()

call expr_factory%init (parse_tree_get_root_ptr (pt_selection))
call event%set_selection (expr_factory)
call expr_factory%init (parse_tree_get_root_ptr (pt_reweight))
call event%set_reweight (expr_factory)
call expr_factory%init (parse_tree_get_root_ptr (pt_analysis))
call event%set_analysis (expr_factory)

call event%connect (process_instance, process%get_model_ptr ())
call var_list_append_real &
    (event%expr%var_list, var_str ("tolerance"), 0._default)
call event%setup_expressions ()

write (u, "(A)")
write (u, "(A)")  "* Generate test process event"

call process%generate_weighted_event (process_instance, 1)

write (u, "(A)")
write (u, "(A)")  "* Fill event object and evaluate expressions"
write (u, "(A)")

call event%generate (1, [0.4_default, 0.4_default])
call event%evaluate_expressions ()
call event%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call event%final ()

```

```
deallocate (event)

call cleanup_test_process (process, process_instance)
deallocate (process_instance)
deallocate (process)

call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: events_3"

end subroutine events_3
```


Chapter 30

Top Level

The top level consists of

commands Defines generic command-list and command objects, and all specific implementations. Each command type provides a specific functionality. Together with the modules that provide expressions and variables, this module defines the Sindarin language.

whizard This module interprets streams of various kind in terms of the command language. It also contains the unit-test feature. We also define the externally visible procedures here, for the **WHIZARD** as a library.

main The driver for **WHIZARD** as a stand-alone program. Contains the command-line interpreter.

whizard_c_interface Alternative top-level procedures, for use in the context of a C-compatible caller program.

30.1 Commands

This module defines the command language of the main input file.

```
<commands.f90>≡  
  <File header>  
  
  module commands  
  
    <Use kinds>  
    <Use strings>  
    use io_units  
    use constants  
    use string_utils, only: lower_case  
    use format_utils, only: write_indent  
    use format_defs, only: FMT_14, FMT_19  
    use unit_tests  
    use diagnostics  
    use sm_qcd  
    use physics_defs  
    use pdf_builtin !NODEP!  
    use sorting  
    use sf_lhapdf  
    use os_interface  
    use ifiles  
    use lexers  
    use syntax_rules  
    use parser  
    use analysis  
    use pdg_arrays  
    use variables  
    use observables  
    use eval_trees  
    use models  
    use auto_components  
    use interactions  
    use flavors  
    use polarizations  
    use beams  
    use particle_specifiers  
    use process_libraries  
    use processes  
    use prclib_stacks  
    use slha_interface  
    use user_files  
    use eio_data  
    use rt_data  
    use dispatch  
    use process_configurations  
    use compilations  
    use integrations  
    use event_streams  
    use simulations  
    use radiation_generator  
    use blha_config
```

⟨Standard module head⟩

⟨Commands: public⟩

⟨Commands: types⟩

⟨Commands: variables⟩

⟨Commands: parameters⟩

⟨Commands: interfaces⟩

contains

⟨Commands: procedures⟩

⟨Commands: tests⟩

end module commands

30.1.1 The command type

The command type is a generic type that holds any command, compiled for execution.

Each command may come with its own local environment. The command list that determines this environment is allocated as **options**, if necessary. (It has to be allocated as a pointer because the type definition is recursive.) The local environment is available as a pointer which either points to the global environment, or is explicitly allocated and initialized.

```
⟨Commands: types⟩≡
  type, abstract :: command_t
    type(parse_node_t), pointer :: pn => null ()
    class(command_t), pointer :: next => null ()
    type(parse_node_t), pointer :: pn_opt => null ()
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t), pointer :: local => null ()
  contains
    ⟨Commands: command: TBP⟩
  end type command_t
```

Finalizer: If there is an option list, finalize the option list and deallocate. If not, the local environment is just a pointer.

```
⟨Commands: command: TBP⟩≡
  procedure :: final => command_final

⟨Commands: procedures⟩≡
  recursive subroutine command_final (cmd)
    class(command_t), intent(inout) :: cmd
    if (associated (cmd%options)) then
      call cmd%options%final ()
      deallocate (cmd%options)
      call cmd%local%local_final ()
```

```

        deallocate (cmd%local)
    else
        cmd%local => null ()
    end if
end subroutine command_final

```

Allocate a command with the appropriate concrete type. Store the parse node pointer in the command object, so we can reference to it when compiling.

(Commands: procedures)+≡

```

subroutine dispatch_command (command, pn)
    class(command_t), intent(inout), pointer :: command
    type(parse_node_t), intent(in), target :: pn
    select case (char (parse_node_get_rule_key (pn)))
    case ("cmd_model")
        allocate (cmd_model_t :: command)
    case ("cmd_library")
        allocate (cmd_library_t :: command)
    case ("cmd_process")
        allocate (cmd_process_t :: command)
    case ("cmd_nlo")
        allocate (cmd_nlo_t :: command)
    case ("cmd_compile")
        allocate (cmd_compile_t :: command)
    case ("cmd_exec")
        allocate (cmd_exec_t :: command)
    case ("cmd_num", "cmd_complex", "cmd_real", "cmd_int", &
          "cmd_log_decl", "cmd_log", "cmd_string", "cmd_string_decl", &
          "cmd_alias", "cmd_result")
        allocate (cmd_var_t :: command)
    case ("cmd_slha")
        allocate (cmd_slha_t :: command)
    case ("cmd_show")
        allocate (cmd_show_t :: command)
    case ("cmd_clear")
        allocate (cmd_clear_t :: command)
    case ("cmd_expect")
        allocate (cmd_expect_t :: command)
    case ("cmd_beams")
        allocate (cmd_beams_t :: command)
    case ("cmd_beams_pol_density")
        allocate (cmd_beams_pol_density_t :: command)
    case ("cmd_beams_pol_fraction")
        allocate (cmd_beams_pol_fraction_t :: command)
    case ("cmd_beams_momentum")
        allocate (cmd_beams_momentum_t :: command)
    case ("cmd_beams_theta")
        allocate (cmd_beams_theta_t :: command)
    case ("cmd_beams_phi")
        allocate (cmd_beams_phi_t :: command)
    case ("cmd_cuts")
        allocate (cmd_cuts_t :: command)
    case ("cmd_scale")
        allocate (cmd_scale_t :: command)
    end select
end subroutine dispatch_command

```

```

case ("cmd_fac_scale")
    allocate (cmd_fac_scale_t :: command)
case ("cmd_ren_scale")
    allocate (cmd_ren_scale_t :: command)
case ("cmd_weight")
    allocate (cmd_weight_t :: command)
case ("cmd_selection")
    allocate (cmd_selection_t :: command)
case ("cmd_reweight")
    allocate (cmd_reweight_t :: command)
case ("cmd_iterations")
    allocate (cmd_iterations_t :: command)
case ("cmd_integrate")
    allocate (cmd_integrate_t :: command)
case ("cmd_observable")
    allocate (cmd_observable_t :: command)
case ("cmd_histogram")
    allocate (cmd_histogram_t :: command)
case ("cmd_plot")
    allocate (cmd_plot_t :: command)
case ("cmd_graph")
    allocate (cmd_graph_t :: command)
case ("cmd_record")
    allocate (cmd_record_t :: command)
case ("cmd_analysis")
    allocate (cmd_analysis_t :: command)
case ("cmd_alt_setup")
    allocate (cmd_alt_setup_t :: command)
case ("cmd_unstable")
    allocate (cmd_unstable_t :: command)
case ("cmd_stable")
    allocate (cmd_stable_t :: command)
case ("cmd_polarized")
    allocate (cmd_polarized_t :: command)
case ("cmd_unpolarized")
    allocate (cmd_unpolarized_t :: command)
case ("cmd_sample_format")
    allocate (cmd_sample_format_t :: command)
case ("cmd_simulate")
    allocate (cmd_simulate_t :: command)
case ("cmd_rescan")
    allocate (cmd_rescan_t :: command)
case ("cmd_write_analysis")
    allocate (cmd_write_analysis_t :: command)
case ("cmd_compile_analysis")
    allocate (cmd_compile_analysis_t :: command)
case ("cmd_open_out")
    allocate (cmd_open_out_t :: command)
case ("cmd_close_out")
    allocate (cmd_close_out_t :: command)
case ("cmd_printf")
    allocate (cmd_printf_t :: command)
case ("cmd_scan")
    allocate (cmd_scan_t :: command)

```

```

case ("cmd_if")
  allocate (cmd_if_t :: command)
case ("cmd_include")
  allocate (cmd_include_t :: command)
case ("cmd_quit")
  allocate (cmd_quit_t :: command)
case default
  print *, char (parse_node_get_rule_key (pn))
  call msg_bug ("Command not implemented")
end select
command%pn => pn
end subroutine dispatch_command

```

Output. We allow for indentation so we can display a command tree.

```

⟨Commands: command: TBP⟩+≡
  procedure (command_write), deferred :: write

⟨Commands: interfaces⟩≡
  abstract interface
    subroutine command_write (cmd, unit, indent)
      import
      class(command_t), intent(in) :: cmd
      integer, intent(in), optional :: unit, indent
    end subroutine command_write
  end interface

```

Compile a command. The command type is already fixed, so this is a deferred type-bound procedure.

```

⟨Commands: command: TBP⟩+≡
  procedure (command_compile), deferred :: compile

⟨Commands: interfaces⟩+≡
  abstract interface
    subroutine command_compile (cmd, global)
      import
      class(command_t), intent(inout) :: cmd
      type(rt_data_t), intent(inout), target :: global
    end subroutine command_compile
  end interface

```

Execute a command. This will use and/or modify the runtime data set. If the quit flag is set, the caller should terminate command execution.

```

⟨Commands: command: TBP⟩+≡
  procedure (command_execute), deferred :: execute

⟨Commands: interfaces⟩+≡
  abstract interface
    subroutine command_execute (cmd, global)
      import
      class(command_t), intent(inout) :: cmd
      type(rt_data_t), intent(inout), target :: global
    end subroutine command_execute
  end interface

```

30.1.2 Options

The `options` command list is allocated, initialized, and executed, if the command is associated with an option text in curly braces. If present, a separate local runtime data set `local` will be allocated and initialized; otherwise, `local` becomes a pointer to the global dataset.

For output, we indent the options list.

```
<Commands: command: TBP>+≡
  procedure :: write_options => command_write_options

<Commands: procedures>+≡
  recursive subroutine command_write_options (cmd, unit, indent)
    class(command_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: ind
    ind = 1; if (present (indent)) ind = indent + 1
    if (associated (cmd%options)) call cmd%options%write (unit, ind)
  end subroutine command_write_options
```

Compile the options list, if any. This implies initialization of the local environment. Should be done once the `pn_opt` node has been assigned (if applicable), but before the actual command compilation.

```
<Commands: command: TBP>+≡
  procedure :: compile_options => command_compile_options

<Commands: procedures>+≡
  recursive subroutine command_compile_options (cmd, global)
    class(command_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    if (associated (cmd%pn_opt)) then
      allocate (cmd%local)
      call cmd%local%local_init (global)
      call global%copy_globals (cmd%local)
      allocate (cmd%options)
      call cmd%options%compile (cmd%pn_opt, cmd%local)
      call global%restore_globals (cmd%local)
      call cmd%local%deactivate ()
    else
      cmd%local => global
    end if
  end subroutine command_compile_options
```

Execute options. First prepare the local environment, then execute the command list.

```
<Commands: command: TBP>+≡
  procedure :: execute_options => cmd_execute_options

<Commands: procedures>+≡
  recursive subroutine cmd_execute_options (cmd, global)
    class(command_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    if (associated (cmd%options)) then
      call cmd%local%activate ()
      call cmd%options%execute (cmd%local)
```

```

        end if
    end subroutine cmd_execute_options

```

This must be called after the parent command has been executed, to undo temporary modifications to the environment. Note that some modifications to `global` can become permanent.

```

⟨Commands: command: TBP⟩+≡
    procedure :: reset_options => cmd_reset_options

⟨Commands: procedures⟩+≡
    subroutine cmd_reset_options (cmd, global)
        class(command_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        if (associated (cmd%options)) then
            call cmd%local%deactivate (global)
        end if
    end subroutine cmd_reset_options

```

30.1.3 Specific command types

Model configuration

The command declares a model, looks for the specified file and loads it.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_model_t
    private
        type(string_t) :: name
    contains
        ⟨Commands: cmd model: TBP⟩
    end type cmd_model_t

```

Output

```

⟨Commands: cmd model: TBP⟩≡
    procedure :: write => cmd_model_write

⟨Commands: procedures⟩+≡
    subroutine cmd_model_write (cmd, unit, indent)
        class(cmd_model_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A,1x,'"',A,'\"') "model =", char (cmd%name)
    end subroutine cmd_model_write

```

Compile. Get the model name and read the model from file, so it is readily available when the command list is executed.

Assign the model pointer in the `global` record, so it can be used for (read-only) variable lookup while compiling further commands.

```

⟨Commands: cmd model: TBP⟩+≡
    procedure :: compile => cmd_model_compile

```



```

⟨Commands: procedures⟩+≡
subroutine cmd_model_compile (cmd, global)
  class(cmd_model_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_name
  type(model_t), pointer :: model
  pn_name => parse_node_get_sub_ptr (cmd%pn, 3)
  cmd%name = parse_node_get_string (pn_name)
  model => null ()
  if (associated (global%model)) then
    if (global%model%get_name () == cmd%name) model => global%model
  end if
  if (.not. associated (model)) then
    if (global%model_list%model_exists (cmd%name)) then
      model => global%model_list%get_model_ptr (cmd%name)
    else
      call global%read_model (cmd%name, model)
    end if
  end if
  global%model => model
  if (associated (global%model)) then
    call global%model%link_var_list (global%var_list)
  end if
end subroutine cmd_model_compile

```

Execute: Insert a pointer into the global data record and reassign the variable list.

```

⟨Commands: cmd model: TBP⟩+≡
  procedure :: execute => cmd_model_execute

⟨Commands: procedures⟩+≡
subroutine cmd_model_execute (cmd, global)
  class(cmd_model_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  call global%select_model (cmd%name)
  if (.not. associated (global%model)) &
    call msg_fatal ("Switching to model '" &
      // char (cmd%name) // "' : model not found")
end subroutine cmd_model_execute

```

Library configuration

We configure a process library that should hold the subsequently defined processes. If the referenced library exists already, just make it the currently active one.

```

⟨Commands: types⟩+≡
type, extends (command_t) :: cmd_library_t
  private
  type(string_t) :: name
contains
  ⟨Commands: cmd library: TBP⟩
end type cmd_library_t

```

Output.

```
<Commands: cmd library: TBP>≡
  procedure :: write => cmd_library_write

<Commands: procedures>+≡
  subroutine cmd_library_write (cmd, unit, indent)
    class(cmd_library_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit)
    call write_indent (u, indent)
    write (u, "(1x,A,1x,'"',A,'\"')") "library =", char (cmd%name)
  end subroutine cmd_library_write
```

Compile. Get the library name.

```
<Commands: cmd library: TBP>+≡
  procedure :: compile => cmd_library_compile

<Commands: procedures>+≡
  subroutine cmd_library_compile (cmd, global)
    class(cmd_library_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_name
    pn_name => parse_node_get_sub_ptr (cmd%pn, 3)
    cmd%name = parse_node_get_string (pn_name)
  end subroutine cmd_library_compile
```

Execute: Initialize a new library and push it on the library stack (if it does not yet exist). Insert a pointer to the library into the global data record. Then, try to load the library unless the rebuild flag is set.

```
<Commands: cmd library: TBP>+≡
  procedure :: execute => cmd_library_execute

<Commands: procedures>+≡
  subroutine cmd_library_execute (cmd, global)
    class(cmd_library_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(prclib_entry_t), pointer :: lib_entry
    type(process_library_t), pointer :: lib
    logical :: rebuild_library
    lib => global%prclib_stack%get_library_ptr (cmd%name)
    rebuild_library = &
      global%var_list%get_lval (var_str ("?rebuild_library"))
    if (.not. (associated (lib))) then
      allocate (lib_entry)
      call lib_entry%init (cmd%name)
      lib => lib_entry%process_library_t
      call global%add_prclib (lib_entry)
    else
      call global%update_prclib (lib)
    end if
    if (associated (lib) .and. .not. rebuild_library) then
      call lib%update_status (global%os_data)
```

```

        end if
    end subroutine cmd_library_execute

```

Process configuration

We define a process-configuration command as a specific type. The incoming and outgoing particles are given evaluation-trees which we transform to PDG-code arrays. For transferring to O'MEGA, they are reconverted to strings.

For the incoming particles, we store parse nodes individually. We do not yet resolve the outgoing state, so we store just a single parse node.

This also includes the choice of method for the corresponding process: `omega` for O'MEGA matrix elements as Fortran code, `ovm` for O'MEGA matrix elements as a bytecode virtual machine, `test` for special processes, `unit_test` for internal test matrix elements generated by WHIZARD, `template` and `template_unity` for test matrix elements generated by WHIZARD as Fortran code similar to the O'MEGA code. If the one-loop program (OLP) GoSam is linked, also matrix elements from there (at leading and next-to-leading order) can be generated via `gosam`.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_process_t
    private
        type(string_t) :: id
        integer :: n_in = 0
        type(parse_node_p), dimension(:), allocatable :: pn_pdg_in
        type(parse_node_t), pointer :: pn_out => null ()
    contains
        ⟨Commands: cmd process: TBP⟩
    end type cmd_process_t

```

Output. The particle expressions are not resolved, so we just list the number of incoming particles.

```

⟨Commands: cmd process: TBP⟩≡
    procedure :: write => cmd_process_write

⟨Commands: procedures⟩+≡
    subroutine cmd_process_write (cmd, unit, indent)
        class(cmd_process_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A,A,A,I0,A)") "process: ", char (cmd%id), " (", &
            size (cmd%pn_pdg_in), " -> X)"
        call cmd%write_options (u, indent)
    end subroutine cmd_process_write

```

Compile. Find and assign the parse nodes.

```

⟨Commands: cmd process: TBP⟩+≡
    procedure :: compile => cmd_process_compile

```

```

<Commands: procedures>+≡
subroutine cmd_process_compile (cmd, global)
  class(cmd_process_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_id, pn_in, pn_codes
  integer :: i
  pn_id => parse_node_get_sub_ptr (cmd%pn, 2)
  pn_in => parse_node_get_next_ptr (pn_id, 2)
  cmd%pn_out => parse_node_get_next_ptr (pn_in, 2)
  cmd%pn_opt => parse_node_get_next_ptr (cmd%pn_out)
  call cmd%compile_options (global)
  cmd%id = parse_node_get_string (pn_id)
  cmd%n_in = parse_node_get_n_sub (pn_in)
  pn_codes => parse_node_get_sub_ptr (pn_in)
  allocate (cmd%pn_pdg_in (cmd%n_in))
  do i = 1, cmd%n_in
    cmd%pn_pdg_in(i)%ptr => pn_codes
    pn_codes => parse_node_get_next_ptr (pn_codes)
  end do
end subroutine cmd_process_compile

```

Command execution. Evaluate the subevents, transform PDG codes into strings, and add the current process configuration to the process library.

The initial state will be unique (one or two particles). For the final state, we allow for expressions. The expressions will be expanded until we have a sum of final states. Each distinct final state will get its own process component.

To identify equivalent final states, we transform the final state into an array of PDG codes, which we sort and compare. If a particle entry is actually a PDG array, only the first entry in the array is used for the comparison. The user should make sure that there is no overlap between different particles or arrays which would make the expansion ambiguous.

```

<Commands: cmd process: TBP>+≡
  procedure :: execute => cmd_process_execute

<Commands: procedures>+≡
subroutine cmd_process_execute (cmd, global)
  class(cmd_process_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(pdg_array_t) :: pdg_in, pdg_out
  type(pdg_array_t), dimension(:), allocatable :: pdg_out_tab
  type(string_t), dimension(:), allocatable :: prt_in
  type(string_t) :: prt_out, prt_out1
  type(process_configuration_t) :: prc_config
  type(prt_expr_t) :: prt_expr_out
  type(prt_spec_t), dimension(:), allocatable :: prt_spec_in
  type(prt_spec_t), dimension(:), allocatable :: prt_spec_out
  type(var_list_t), pointer :: var_list
  integer, dimension(:), allocatable :: pdg
  integer, dimension(:), allocatable :: i_term
  integer :: i, j, n_in, n_out, n_terms, n_components
  logical :: nlo_calc
  logical, dimension(4) :: active_nlo_components
  type(string_t), dimension(:), allocatable :: prt_in_nlo, prt_out_nlo

```

```

type(radiation_generator_t) :: radiation_generator
type(pdg_list_t) :: pl_in, pl_out
type(string_t) :: loop_me_method
type(string_t) :: correlation_me_method
type(string_t) :: real_tree_me_method
type(string_t) :: current_me_method
! integer , dimension(4) :: i_list
integer, dimension(5) :: i_list
logical :: combined_nlo_integration, powheg_active

nlo_calc = cmd%local%nlo_calculation
combined_nlo_integration = &
    global%var_list%get_lval (var_str ('?combined_nlo_integration'))
powheg_active = &
    global%var_list%get_lval (var_str ('?powheg_matching'))
call check_nlo_options (nlo_calc, combined_nlo_integration, powheg_active)
active_nlo_components = cmd%local%active_nlo_components

var_list => cmd%local%get_var_list_ptr ()

n_in = size (cmd%pn_pdg_in)
allocate (prt_in (n_in), prt_spec_in (n_in))
do i = 1, n_in
    pdg_in = &
        eval_pdg_array (cmd%pn_pdg_in(i)%ptr, var_list)
    prt_in(i) = make_flavor_string (pdg_in, cmd%local%model)
    prt_spec_in(i) = new_prt_spec (prt_in(i))
end do
call compile_prt_expr &
    (prt_expr_out, cmd%pn_out, var_list, cmd%local%model)
call prt_expr_out%expand ()
n_terms = prt_expr_out%get_n_terms ()
allocate (pdg_out_tab (n_terms))
allocate (i_term (n_terms), source = 0)
n_components = 0
SCAN_COMPONENTS: do i = 1, n_terms
    if (allocated (pdg)) deallocate (pdg)
    call prt_expr_out%term_to_array (prt_spec_out, i)
    n_out = size (prt_spec_out)
    allocate (pdg (n_out))
    do j = 1, n_out
        prt_out = prt_spec_out(j)%to_string ()
        call split (prt_out, prt_out1, ":")
        pdg(j) = cmd%local%model%get_pdg (prt_out1)
    end do
    pdg_out = sort (pdg)
    do j = 1, n_components
        if (pdg_out == pdg_out_tab(j)) cycle SCAN_COMPONENTS
    end do
    n_components = n_components + 1
    i_term(n_components) = i
    pdg_out_tab(n_components) = pdg_out
end do SCAN_COMPONENTS
if (nlo_calc) then

```

```

!      call prc_config%init (cmd%id, n_in, n_components*4, cmd%local)
      call prc_config%init (cmd%id, n_in, n_components*5, cmd%local)
    else
      call prc_config%init (cmd%id, n_in, n_components, cmd%local)
    end if
    do i = 1, n_components
      call prt_expr_out%term_to_array (prt_spec_out, i_term(i))
      if (nlo_calc) then
        associate (active_comp => cmd%local%active_nlo_components)
          i_list(1) = i
          i_list(2) = i + n_components
          i_list(3) = i + 2*n_components
          i_list(4) = i + 3*n_components
          i_list(5) = i + 4*n_components
          loop_me_method = global%var_list%get_sval (var_str ("loop_me_method"))
          correlation_me_method = global%var_list%get_sval (var_str ("correlation_me_method"))
          real_tree_me_method = global%var_list%get_sval (var_str ("real_tree_me_method"))

          call prc_config%setup_component (i, prt_spec_in, prt_spec_out, &
                                           cmd%local, BORN, &
                                           active_in = active_comp (1))

          call split_prt (prt_spec_in, n_in, pl_in)
          call split_prt (prt_spec_out, n_out, pl_out)
          call radiation_generator%init (pl_in, pl_out, qcd = .true., qed = .false.)
          call radiation_generator%set_n (n_in, n_out, 0)
          call radiation_generator%set_constraints (.false., .false., .true., .true.)
          call radiation_generator%init_radiation_model &
            (cmd%local%radiation_model)
          call radiation_generator%generate (prt_in_nlo, prt_out_nlo)

          current_me_method = var_str ('omega')
          if (current_me_method /= real_tree_me_method) then
            call global%set_me_method (real_tree_me_method)
            current_me_method = real_tree_me_method
          end if
          call prc_config%setup_component (n_components + i, &
                                           new_prt_spec (prt_in_nlo), &
                                           new_prt_spec (prt_out_nlo), &
                                           cmd%local, NLO_REAL, &
                                           active_in = active_comp (2))

          if (current_me_method /= loop_me_method) then
            call global%set_me_method (loop_me_method)
            current_me_method = loop_me_method
          end if
          call prc_config%setup_component (n_components*2 + i, prt_spec_in, &
                                           prt_spec_out, global, NLO_VIRTUAL, &
                                           active_in = active_comp (3))

          if (current_me_method /= "omega") then
            call global%set_me_method (var_str ("omega"))
            current_me_method = "omega"
          end if
          call prc_config%setup_component (n_components*3+i, prt_spec_in, &

```

```

        prt_spec_out, global, NLO_PDF, &
        active_in = active_comp (4))

    if (current_me_method /= correlation_me_method) then
        call global%set_me_method (correlation_me_method)
        current_me_method = correlation_me_method
    end if
    call prc_config%setup_component (n_components*4 + i, prt_spec_in, &
        prt_spec_out, global, NLO_SUBTRACTION, &
        .false.)
    call prc_config%set_component_associations (i_list)
end associate
else
    call prc_config%setup_component (i, prt_spec_in, prt_spec_out, cmd%local)
end if
end do
call prc_config%record (cmd%local)

contains
subroutine check_nlo_options (nlo, combined, powheg)
    logical, intent(in) :: nlo, combined, powheg
    logical :: case_lo_but_any_other
    logical :: case_nlo_powheg_but_not_combined
    case_lo_but_any_other = .not. nlo .and. &
        any ([combined, powheg])
    case_nlo_powheg_but_not_combined = &
        nlo .and. powheg .and. .not. combined
    if (case_lo_but_any_other) then
        call msg_fatal ("Option mismatch: Leading order process is selected &
            &but either powheg_matching or combined_nlo_integration &
            &is set to true.")
    else if (case_nlo_powheg_but_not_combined) then
        call msg_fatal ("POWHEG requires the 'combined_nlo_integration'-option &
            &to be set to true.")
    end if
end subroutine check_nlo_options

subroutine split_prt (prt, n_out, pl)
    type(prt_spec_t), intent(in), dimension(:), allocatable :: prt
    integer, intent(in) :: n_out
    type(pdg_list_t), intent(out) :: pl
    type(pdg_array_t) :: pdg
    type(string_t) :: prt_string, prt_tmp
    integer, dimension(10) :: i_particle
    integer :: i, j, n
    call pl%init (n_out)
    do i = 1, n_out
        n = 1
        prt_string = prt(i)%to_string ()
        do
            call split (prt_string, prt_tmp, ":")
            if (prt_tmp /= "") then
                i_particle(n) = cmd%local%model%get_pdg (prt_tmp)

```

```

        n=n+1
    else
        exit
    end if
end do
call pdg_array_init (pdg, n-1)
do j = 1, n-1
    call pdg%set (j, i_particle(j))
end do
call pl%set (i, pdg)
call pdg_array_delete (pdg)
end do
end subroutine split_prt

end subroutine cmd_process_execute

```

This is a method of the eval tree, but cannot be coded inside the `expressions` module since it uses the `model` and `flv` types which are not available there.

(Commands: procedures)+≡

```

function make_flavor_string (aval, model) result (prt)
    type(string_t) :: prt
    type(pdg_array_t), intent(in) :: aval
    type(model_t), intent(in), target :: model
    integer, dimension(:), allocatable :: pdg
    type(flavor_t), dimension(:), allocatable :: flv
    integer :: i
    pdg = aval
    allocate (flv (size (pdg)))
    call flv%init (pdg, model)
    if (size (pdg) /= 0) then
        prt = flv(1)%get_name ()
        do i = 2, size (flv)
            prt = prt // ":" // flv(i)%get_name ()
        end do
    else
        prt = "?"
    end if
end function make_flavor_string

```

Create a `pdg` array from a particle-specification array

(Commands: procedures)+≡

```

function make_pdg_array (prt, model) result (pdg_array)
    type(prt_spec_t), intent(in), dimension(:) :: prt
    type(model_t), intent(in) :: model
    integer, dimension(:), allocatable :: aval
    type(pdg_array_t) :: pdg_array
    type(flavor_t) :: flv
    integer :: k
    allocate (aval (size (prt)))
    do k = 1, size (prt)
        call flv%init (prt(k)%to_string (), model)
        aval (k) = flv%get_pdg ()
    end do

```



```

    pdg_array = aval
end function make_pdg_array

```

Compile a (possible nested) expression, to obtain a particle-specifier expression which we can process further.

(Commands: procedures)+≡

```

recursive subroutine compile_prt_expr (prt_expr, pn, var_list, model)
  type(prt_expr_t), intent(out) :: prt_expr
  type(parse_node_t), intent(in), target :: pn
  type(var_list_t), intent(in), target :: var_list
  type(model_t), intent(in), target :: model
  type(parse_node_t), pointer :: pn_entry, pn_term, pn_addition
  type(pdg_array_t) :: pdg
  type(string_t) :: prt_string
  integer :: n_entry, n_term, i
  select case (char (parse_node_get_rule_key (pn)))
  case ("prt_state_list")
    n_entry = parse_node_get_n_sub (pn)
    pn_entry => parse_node_get_sub_ptr (pn)
    if (n_entry == 1) then
      call compile_prt_expr (prt_expr, pn_entry, var_list, model)
    else
      call prt_expr%init_list (n_entry)
      select type (x => prt_expr%x)
      type is (prt_spec_list_t)
        do i = 1, n_entry
          call compile_prt_expr (x%expr(i), pn_entry, var_list, model)
          pn_entry => parse_node_get_next_ptr (pn_entry)
        end do
      end select
    end if
  case ("prt_state_sum")
    n_term = parse_node_get_n_sub (pn)
    pn_term => parse_node_get_sub_ptr (pn)
    pn_addition => pn_term
    if (n_term == 1) then
      call compile_prt_expr (prt_expr, pn_term, var_list, model)
    else
      call prt_expr%init_sum (n_term)
      select type (x => prt_expr%x)
      type is (prt_spec_sum_t)
        do i = 1, n_term
          call compile_prt_expr (x%expr(i), pn_term, var_list, model)
          pn_addition => parse_node_get_next_ptr (pn_addition)
          if (associated (pn_addition)) &
            pn_term => parse_node_get_sub_ptr (pn_addition, 2)
        end do
      end select
    end if
  case ("cexpr")
    pdg = eval_pdg_array (pn, var_list)
    prt_string = make_flavor_string (pdg, model)
    call prt_expr%init_spec (new_prt_spec (prt_string))
  end select
end subroutine compile_prt_expr

```

```

    case default
        call parse_node_write_rec (pn)
        call msg_bug ("compile prt expr: impossible syntax rule")
    end select
end subroutine compile_prt_expr

```

Initiating a NLO calculation

```

<Commands: types>+≡
type, extends (command_t) :: cmd_nlo_t
    private
    type(parse_node_p), dimension(3) :: pn_components
    logical, dimension(4) :: active_component
contains
    <Commands: cmd nlo: TBP>
end type cmd_nlo_t

```

```

<Commands: cmd nlo: TBP>≡
procedure :: write => cmd_nlo_write

```

```

<Commands: procedures>+≡
subroutine cmd_nlo_write (cmd, unit, indent)
    class(cmd_nlo_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
end subroutine cmd_nlo_write

```

As it is, the NLO calculation is switched on by putting nlo behind the process definition. This should be made nicer in the future.

```

<Commands: cmd nlo: TBP>+≡
procedure :: compile => cmd_nlo_compile

<Commands: procedures>+≡
subroutine cmd_nlo_compile (cmd, global)
    class(cmd_nlo_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_arg, pn_comp
    integer :: i
    pn_arg => parse_node_get_sub_ptr (cmd%pn, 3)
    cmd%pn_components(1)%ptr => parse_node_get_sub_ptr (pn_arg)
    pn_comp => parse_node_get_next_ptr (cmd%pn_components(1)%ptr)
    i = 2
    do
        if (associated (pn_comp)) then
            cmd%pn_components(i)%ptr => pn_comp
            pn_comp => parse_node_get_next_ptr (cmd%pn_components(i)%ptr)
            i = i+1
        else
            exit
        end if
    end do
end subroutine cmd_nlo_compile

```

```

<Commands: cmd nlo: TBP>+≡
  procedure :: execute => cmd_nlo_execute

<Commands: procedures>+≡
  subroutine cmd_nlo_execute (cmd, global)
    class(cmd_nlo_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: current_component
    type(string_t) :: component_type
    integer :: i

    cmd%active_component = .false.

    current_component => cmd%pn_components(1)%ptr
    i = 2
    do
      if (associated (current_component)) then
        component_type = eval_string (current_component, global%var_list)
        select case (char (component_type))
          case ('Born')
            cmd%active_component(1) = .true.
          case ('Real')
            cmd%active_component(2) = .true.
          case ('Virtual')
            cmd%active_component(3) = .true.
          case ('Pdf')
            cmd%active_component(4) = .true.
          case ('Full')
            cmd%active_component = .true.
        end select
        if (i >= 4) exit
        current_component => cmd%pn_components(i)%ptr
        i = i+1
      else
        exit
      end if
    end do
    global%nlo_calculation = cmd%active_component(2) &
      .or. cmd%active_component(3) &
      .or. cmd%active_component(4)
    global%active_nlo_components = cmd%active_component
  end subroutine cmd_nlo_execute

```

Process compilation

```

<Commands: types>+≡
  type, extends (command_t) :: cmd_compile_t
  private
  type(string_t), dimension(:), allocatable :: libname
  logical :: make_executable = .false.
  type(string_t) :: exec_name
  contains
  <Commands: cmd compile: TBP>

```

```
end type cmd_compile_t
```

Output: list all libraries to be compiled.

<Commands: cmd compile: TBP>≡

```
procedure :: write => cmd_compile_write
```

<Commands: procedures>+≡

```
subroutine cmd_compile_write (cmd, unit, indent)
  class(cmd_compile_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  write (u, "(1x,A)", advance="no") "compile ("
  if (allocated (cmd%libname)) then
    do i = 1, size (cmd%libname)
      if (i > 1) write (u, "(A,1x)", advance="no") ", "
      write (u, "('\"',A,'\"')", advance="no") char (cmd%libname(i))
    end do
  end if
  write (u, "(A)") ")"
end subroutine cmd_compile_write
```

Compile the libraries specified in the argument. If the argument is empty, compile all libraries which can be found in the process library stack.

<Commands: cmd compile: TBP>+≡

```
procedure :: compile => cmd_compile_compile
```

<Commands: procedures>+≡

```
subroutine cmd_compile_compile (cmd, global)
  class(cmd_compile_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_cmd, pn_clause, pn_arg, pn_lib
  type(parse_node_t), pointer :: pn_exec_name_spec, pn_exec_name
  integer :: n_lib, i
  pn_cmd => parse_node_get_sub_ptr (cmd%pn)
  pn_clause => parse_node_get_sub_ptr (pn_cmd)
  pn_exec_name_spec => parse_node_get_sub_ptr (pn_clause, 2)
  if (associated (pn_exec_name_spec)) then
    pn_exec_name => parse_node_get_sub_ptr (pn_exec_name_spec, 2)
  else
    pn_exec_name => null ()
  end if
  pn_arg => parse_node_get_next_ptr (pn_clause)
  cmd%pn_opt => parse_node_get_next_ptr (pn_cmd)
  call cmd%compile_options (global)
  if (associated (pn_arg)) then
    n_lib = parse_node_get_n_sub (pn_arg)
  else
    n_lib = 0
  end if
  if (n_lib > 0) then
    allocate (cmd%libname (n_lib))
    pn_lib => parse_node_get_sub_ptr (pn_arg)
```

```

        do i = 1, n_lib
            cmd%libname(i) = parse_node_get_string (pn_lib)
            pn_lib => parse_node_get_next_ptr (pn_lib)
        end do
    end if
    if (associated (pn_exec_name)) then
        cmd%make_executable = .true.
        cmd%exec_name = parse_node_get_string (pn_exec_name)
    end if
end subroutine cmd_compile_compile

```

Command execution. Generate code, write driver, compile and link. Do this for all libraries in the list.

If no library names have been given and stored while compiling this command, we collect all libraries from the current stack and compile those.

We can compile static libraries (which actually just loads them). However, we can't incorporate in a generated executable.

<Commands: cmd compile: TBP>+≡

```

    procedure :: execute => cmd_compile_execute

```

<Commands: procedures>+≡

```

subroutine cmd_compile_execute (cmd, global)
    class(cmd_compile_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(string_t), dimension(:), allocatable :: libname, libname_static
    integer :: i
    if (allocated (cmd%libname)) then
        allocate (libname (size (cmd%libname)))
        libname = cmd%libname
    else
        call cmd%local%prclib_stack%get_names (libname)
    end if
    if (cmd%make_executable) then
        call get_prclib_static (libname_static)
        do i = 1, size (libname)
            if (any (libname_static == libname(i))) then
                call msg_fatal ("Compile: can't include static library '" &
                    // char (libname(i)) // "'")
            end if
        end do
        call compile_executable (cmd%exec_name, libname, cmd%local)
    else
        do i = 1, size (libname)
            call compile_library (libname(i), cmd%local)
        end do
    end if
end subroutine cmd_compile_execute

```

This is the interface to the external procedure which returns the names of all static libraries which are part of the executable. (The default is none.) The routine must allocate the array.

<Commands: public>≡

```

    public :: get_prclib_static

```

```

<Commands: interfaces>+≡
interface
  subroutine get_prclib_static (libname)
    import
    type(string_t), dimension(:), intent(inout), allocatable :: libname
  end subroutine get_prclib_static
end interface

```

Execute a shell command

The argument is a string expression.

```

<Commands: types>+≡
type, extends (command_t) :: cmd_exec_t
  private
  type(parse_node_t), pointer :: pn_command => null ()
  contains
  <Commands: cmd exec: TBP>
end type cmd_exec_t

```

Simply tell the status.

```

<Commands: cmd exec: TBP>≡
procedure :: write => cmd_exec_write

<Commands: procedures>+≡
subroutine cmd_exec_write (cmd, unit, indent)
  class(cmd_exec_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  if (associated (cmd%pn_command)) then
    write (u, "(1x,A)") "exec: [command associated]"
  else
    write (u, "(1x,A)") "exec: [undefined]"
  end if
end subroutine cmd_exec_write

```

Compile the exec command.

```

<Commands: cmd exec: TBP>+≡
procedure :: compile => cmd_exec_compile

<Commands: procedures>+≡
subroutine cmd_exec_compile (cmd, global)
  class(cmd_exec_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_arg, pn_command
  pn_arg => parse_node_get_sub_ptr (cmd%pn, 2)
  pn_command => parse_node_get_sub_ptr (pn_arg)
  cmd%pn_command => pn_command
end subroutine cmd_exec_compile

```

Execute the specified shell command.

```

<Commands: cmd exec: TBP>+≡
    procedure :: execute => cmd_exec_execute

<Commands: procedures>+≡
    subroutine cmd_exec_execute (cmd, global)
        class(cmd_exec_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(string_t) :: command
        logical :: is_known
        integer :: status
        command = eval_string (cmd%pn_command, global%var_list, is_known=is_known)
        if (is_known) then
            if (command /= "") then
                call os_system_call (command, status, verbose=.true.)
                if (status /= 0) then
                    write (msg_buffer, "(A,I0)") "Return code = ", status
                    call msg_message ()
                    call msg_error ("System command returned with nonzero status code")
                end if
            end if
        end if
    end subroutine cmd_exec_execute

```

Variable declaration

A variable can have various types. Hold the definition as an eval tree.

There are intrinsic variables, user variables, and model variables. The latter are further divided in independent variables and dependent variables.

Regarding model variables: When dealing with them, we always look at two variable lists in parallel. The global (or local) variable list contains the user-visible values. It includes variables that correspond to variables in the current model's list. These, in turn, are pointers to the model's parameter list, so the model is always in sync, internally. To keep the global variable list in sync with the model, the global variables carry the `is_copy` property and contain a separate pointer to the model variable. (The pointer is reassigned whenever the model changes.) Modifying the global variable changes two values simultaneously: the visible value and the model variable, via this extra pointer. After each modification, we update dependent parameters in the model variable list and re-synchronize the global variable list (again, using these pointers) with the model variable this. In the last step, modifications in the derived parameters become visible.

When we integrate a process, we capture the current variable list of the current model in a separate model instance, which is stored in the process object. Thus, the model parameters associated to this process at this time are preserved for the lifetime of the process object.

When we generate or rescan events, we can again capture a local model variable list in a model instance. This allows us to reweight event by event with different parameter sets simultaneously.

```

<Commands: types>+≡
    type, extends (command_t) :: cmd_var_t

```

```

private
type(string_t) :: name
integer :: type = V_NONE
type(parse_node_t), pointer :: pn_value => null ()
logical :: is_intrinsic = .false.
logical :: is_model_var = .false.
contains
  <Commands: cmd var: TBP>
end type cmd_var_t

```

Output. We know name, type, and properties, but not the value.

```

<Commands: cmd var: TBP>≡
  procedure :: write => cmd_var_write

<Commands: procedures>+≡
  subroutine cmd_var_write (cmd, unit, indent)
    class(cmd_var_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,A,A)", advance="no") "var: ", char (cmd%name), " ("
    select case (cmd%type)
    case (V_NONE)
      write (u, "(A)", advance="no") "[unknown]"
    case (V_LOG)
      write (u, "(A)", advance="no") "logical"
    case (V_INT)
      write (u, "(A)", advance="no") "int"
    case (V_REAL)
      write (u, "(A)", advance="no") "real"
    case (V_CMPLX)
      write (u, "(A)", advance="no") "complex"
    case (V_STR)
      write (u, "(A)", advance="no") "string"
    case (V_PDG)
      write (u, "(A)", advance="no") "alias"
    end select
    if (cmd%is_intrinsic) then
      write (u, "(A)", advance="no") ", intrinsic"
    end if
    if (cmd%is_model_var) then
      write (u, "(A)", advance="no") ", model"
    end if
    write (u, "(A)") ")"
  end subroutine cmd_var_write

```

Compile the lhs and determine the variable name and type. Check whether this variable can be created or modified as requested, and append the value to the variable list, if appropriate. The value is initially undefined. The rhs is assigned to a pointer, to be compiled and evaluated when the command is executed.

```

<Commands: cmd var: TBP>+≡
  procedure :: compile => cmd_var_compile

```


{Commands: procedures}+≡

```

subroutine cmd_var_compile (cmd, global)
  class(cmd_var_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_var, pn_name
  type(parse_node_t), pointer :: pn_result, pn_proc
  type(string_t) :: var_name
  type(var_list_t), pointer :: model_vars
  integer :: type
  logical :: new
  pn_result => null ()
  new = .false.
  select case (char (parse_node_get_rule_key (cmd%pn)))
  case ("cmd_log_decl");      type = V_LOG
    pn_var => parse_node_get_sub_ptr (cmd%pn, 2)
    if (.not. associated (pn_var)) then    ! handle masked syntax error
      cmd%type = V_NONE; return
    end if
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    new = .true.
  case ("cmd_log");          type = V_LOG
    pn_name => parse_node_get_sub_ptr (cmd%pn, 2)
  case ("cmd_int");          type = V_INT
    pn_name => parse_node_get_sub_ptr (cmd%pn, 2)
    new = .true.
  case ("cmd_real");         type = V_REAL
    pn_name => parse_node_get_sub_ptr (cmd%pn, 2)
    new = .true.
  case ("cmd_complex");      type = V_CMPLX
    pn_name => parse_node_get_sub_ptr (cmd%pn, 2)
    new = .true.
  case ("cmd_num");          type = V_NONE
    pn_name => parse_node_get_sub_ptr (cmd%pn)
  case ("cmd_string_decl");  type = V_STR
    pn_var => parse_node_get_sub_ptr (cmd%pn, 2)
    if (.not. associated (pn_var)) then    ! handle masked syntax error
      cmd%type = V_NONE; return
    end if
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    new = .true.
  case ("cmd_string");       type = V_STR
    pn_name => parse_node_get_sub_ptr (cmd%pn, 2)
  case ("cmd_alias");        type = V_PDG
    pn_name => parse_node_get_sub_ptr (cmd%pn, 2)
    new = .true.
  case ("cmd_result");       type = V_REAL
    pn_name => parse_node_get_sub_ptr (cmd%pn)
    pn_result => parse_node_get_sub_ptr (pn_name)
    pn_proc => parse_node_get_next_ptr (pn_result)
  case default
    call parse_node_mismatch &
      ("logical|int|real|complex|?|${alias|var_name}", cmd%pn) ! $
  end select
  if (.not. associated (pn_name)) then    ! handle masked syntax error

```

```

        cmd%type = V_NONE; return
    end if
    if (.not. associated (pn_result)) then
        var_name = parse_node_get_string (pn_name)
    else
        var_name = parse_node_get_key (pn_result) &
            // "(" // parse_node_get_string (pn_proc) // ")"
    end if
    select case (type)
    case (V_LOG); var_name = "?" // var_name
    case (V_STR); var_name = "$" // var_name    ! $
    end select
    if (associated (global%model)) then
        model_vars => global%model%get_var_list_ptr ()
    else
        model_vars => null ()
    end if
    call var_list_check_observable (global%var_list, var_name, type)
    call var_list_check_result_var (global%var_list, var_name, type)
    call var_list_check_user_var (global%var_list, var_name, type, new)
    cmd%name = var_name
    cmd%pn_value => parse_node_get_next_ptr (pn_name, 2)
    if (global%var_list%contains (cmd%name, follow_link = .false.)) then
        ! local variable
        cmd%is_intrinsic = &
            global%var_list%is_intrinsic (cmd%name, follow_link = .false.)
        cmd%type = &
            global%var_list%get_type (cmd%name, follow_link = .false.)
    else
        if (new) cmd%type = type
        if (global%var_list%contains (cmd%name, follow_link = .true.)) then
            ! global variable
            cmd%is_intrinsic = &
                global%var_list%is_intrinsic (cmd%name, follow_link = .true.)
            if (cmd%type == V_NONE) then
                cmd%type = &
                    global%var_list%get_type (cmd%name, follow_link = .true.)
            end if
        else if (associated (model_vars)) then ! check model variable
            cmd%is_model_var = &
                model_vars%contains (cmd%name)
            if (cmd%type == V_NONE) then
                cmd%type = &
                    model_vars%get_type (cmd%name)
            end if
        end if
        if (cmd%type == V_NONE) then
            call msg_fatal ("Variable '" // char (cmd%name) // "' " &
                // "set without declaration")
            cmd%type = V_NONE; return
        end if
        if (cmd%is_model_var) then
            if (new) then
                call msg_fatal ("Model variable '" // char (cmd%name) // "' " &

```

```

        // "redeclared")
    else if (model_vars%is_locked (cmd%name)) then
        call msg_fatal ("Model variable '" // char (cmd%name) // "' " &
            // "is locked")
    end if
else
    select case (cmd%type)
    case (V_LOG)
        call var_list_append_log (global%var_list, cmd%name, &
            intrinsic=cmd%is_intrinsic, user=.true.)
    case (V_INT)
        call var_list_append_int (global%var_list, cmd%name, &
            intrinsic=cmd%is_intrinsic, user=.true.)
    case (V_REAL)
        call var_list_append_real (global%var_list, cmd%name, &
            intrinsic=cmd%is_intrinsic, user=.true.)
    case (V_CMPLX)
        call var_list_append_cmplx (global%var_list, cmd%name, &
            intrinsic=cmd%is_intrinsic, user=.true.)
    case (V_PDG)
        call var_list_append_pdg_array (global%var_list, cmd%name, &
            intrinsic=cmd%is_intrinsic, user=.true.)
    case (V_STR)
        call var_list_append_string (global%var_list, cmd%name, &
            intrinsic=cmd%is_intrinsic, user=.true.)
    end select
end if
end if
end subroutine cmd_var_compile

```

Execute. Evaluate the definition and assign the variable value. If the variable is a model variable, take a snapshot of the model if necessary and set the variable in the local model.

```

<Commands: cmd var: TBP>+≡
    procedure :: execute => cmd_var_execute

<Commands: procedures>+≡
    subroutine cmd_var_execute (cmd, global)
        class(cmd_var_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(var_list_t), pointer :: var_list
        real(default) :: rval
        logical :: is_known, pacified
        var_list => global%get_var_list_ptr ()
        if (cmd%is_model_var) then
            pacified = var_list%get_lval (var_str ("?pacify"))
            rval = eval_real (cmd%pn_value, var_list, is_known=is_known)
            call global%model_set_real &
                (cmd%name, rval, verbose=.true., pacified=pacified)
        else if (cmd%type /= V_NONE) then
            call cmd%set_value (var_list, verbose=.true.)
        end if
    end subroutine cmd_var_execute

```

Copy the value to the variable list, where the variable should already exist.

(Commands: cmd var: TBP)+≡

```
procedure :: set_value => cmd_var_set_value
```

(Commands: procedures)+≡

```
subroutine cmd_var_set_value (var, var_list, verbose, model_name)
  class(cmd_var_t), intent(inout) :: var
  type(var_list_t), intent(inout), target :: var_list
  logical, intent(in), optional :: verbose
  type(string_t), intent(in), optional :: model_name
  logical :: lval, pacified
  integer :: ival
  real(default) :: rval
  complex(default) :: cval
  type(pdg_array_t) :: aval
  type(string_t) :: sval
  logical :: is_known
  pacified = var_list%get_lval (var_str ("?pacify"))
  select case (var%type)
  case (V_LOG)
    lval = eval_log (var%pn_value, var_list, is_known=is_known)
    call var_list_set_log (var_list, var%name, &
      lval, is_known, verbose=verbose, model_name=model_name)
  case (V_INT)
    ival = eval_int (var%pn_value, var_list, is_known=is_known)
    call var_list_set_int (var_list, var%name, &
      ival, is_known, verbose=verbose, model_name=model_name)
  case (V_REAL)
    rval = eval_real (var%pn_value, var_list, is_known=is_known)
    call var_list_set_real (var_list, var%name, &
      rval, is_known, verbose=verbose, &
      model_name=model_name, pacified = pacified)
  case (V_CMPLX)
    cval = eval_cmplx (var%pn_value, var_list, is_known=is_known)
    call var_list_set_cmplx (var_list, var%name, &
      cval, is_known, verbose=verbose, &
      model_name=model_name, pacified = pacified)
  case (V_PDG)
    aval = eval_pdg_array (var%pn_value, var_list, is_known=is_known)
    call var_list_set_pdg_array (var_list, var%name, &
      aval, is_known, verbose=verbose, model_name=model_name)
  case (V_STR)
    sval = eval_string (var%pn_value, var_list, is_known=is_known)
    call var_list_set_string (var_list, var%name, &
      sval, is_known, verbose=verbose, model_name=model_name)
  end select
end subroutine cmd_var_set_value
```

SLHA

Read a SLHA (SUSY Les Houches Accord) file to fill the appropriate model parameters. We do not access the current variable record, but directly work on the appropriate SUSY model, which is loaded if necessary.

We may be in read or write mode. In the latter case, we may write just input parameters, or the complete spectrum, or the spectrum with all decays.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_slha_t
  private
  type(string_t) :: file
  logical :: write_mode = .false.
  contains
  ⟨Commands: cmd slha: TBP⟩
end type cmd_slha_t

```

Output.

```

⟨Commands: cmd slha: TBP⟩≡
  procedure :: write => cmd_slha_write

⟨Commands: procedures⟩+≡
  subroutine cmd_slha_write (cmd, unit, indent)
    class(cmd_slha_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,A)") "slha: file name = ", char (cmd%file)
    write (u, "(1x,A,L1)") "slha: write mode = ", cmd%write_mode
  end subroutine cmd_slha_write

```

Compile. Read the filename and store it.

```

⟨Commands: cmd slha: TBP⟩+≡
  procedure :: compile => cmd_slha_compile

⟨Commands: procedures⟩+≡
  subroutine cmd_slha_compile (cmd, global)
    class(cmd_slha_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_key, pn_arg, pn_file
    pn_key => parse_node_get_sub_ptr (cmd%pn)
    pn_arg => parse_node_get_next_ptr (pn_key)
    pn_file => parse_node_get_sub_ptr (pn_arg)
    call cmd%compile_options (global)
    cmd%pn_opt => parse_node_get_next_ptr (pn_arg)
    select case (char (parse_node_get_key (pn_key)))
    case ("read_slha")
      cmd%write_mode = .false.
    case ("write_slha")
      cmd%write_mode = .true.
    case default
      call parse_node_mismatch ("read_slha|write_slha", cmd%pn)
    end select
    cmd%file = parse_node_get_string (pn_file)
  end subroutine cmd_slha_compile

```

Execute. Read or write the specified SLHA file. Behind the scenes, this will first read the WHIZARD model file, then read the SLHA file and assign the SLHA

parameters as far as determined by `dispatch_slha`. Finally, the global variables are synchronized with the model. This is similar to executing `cmd_model`.

```

⟨Commands: cmd slha: TBP⟩+≡
  procedure :: execute => cmd_slha_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_slha_execute (cmd, global)
    class(cmd_slha_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    logical :: input, spectrum, decays
    if (cmd%write_mode) then
      input = .true.
      spectrum = .false.
      decays = .false.
      if (.not. associated (cmd%local%model)) then
        call msg_fatal ("SLHA: local model not associated")
        return
      end if
      call slha_write_file &
        (cmd%file, cmd%local%model, &
         input = input, spectrum = spectrum, decays = decays)
    else
      if (.not. associated (global%model)) then
        call msg_fatal ("SLHA: global model not associated")
        return
      end if
      call dispatch_slha (cmd%local, &
        input = input, spectrum = spectrum, decays = decays)
      call global%ensure_model_copy ()
      call slha_read_file &
        (cmd%file, cmd%local%os_data, global%model, &
         input = input, spectrum = spectrum, decays = decays)
    end if
  end subroutine cmd_slha_execute

```

Show values

This command shows the current values of variables or other objects, in a suitably condensed form.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_show_t
  private
  type(string_t), dimension(:), allocatable :: name
  contains
  ⟨Commands: cmd show: TBP⟩
  end type cmd_show_t

```

Output: list the object names, not values.

```

⟨Commands: cmd show: TBP⟩≡
  procedure :: write => cmd_show_write

```

```

<Commands: procedures>+≡
subroutine cmd_show_write (cmd, unit, indent)
  class(cmd_show_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u, i
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  write (u, "(1x,A)", advance="no") "show: "
  if (allocated (cmd%name)) then
    do i = 1, size (cmd%name)
      write (u, "(1x,A)", advance="no") char (cmd%name(i))
    end do
    write (u, *)
  else
    write (u, "(5x,A)") "[undefined]"
  end if
end subroutine cmd_show_write

```

Compile. Allocate an array which is filled with the names of the variables to show.

```

<Commands: cmd show: TBP>+≡
procedure :: compile => cmd_show_compile

<Commands: procedures>+≡
subroutine cmd_show_compile (cmd, global)
  class(cmd_show_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_arg, pn_var, pn_prefix, pn_name
  type(string_t) :: key
  integer :: i, n_args
  pn_arg => parse_node_get_sub_ptr (cmd%pn, 2)
  if (associated (pn_arg)) then
    select case (char (parse_node_get_rule_key (pn_arg)))
    case ("show_arg")
      cmd%pn_opt => parse_node_get_next_ptr (pn_arg)
    case default
      cmd%pn_opt => pn_arg
      pn_arg => null ()
    end select
  end if
  call cmd%compile_options (global)
  if (associated (pn_arg)) then
    n_args = parse_node_get_n_sub (pn_arg)
    allocate (cmd%name (n_args))
    pn_var => parse_node_get_sub_ptr (pn_arg)
    i = 0
    do while (associated (pn_var))
      i = i + 1
      select case (char (parse_node_get_rule_key (pn_var)))
      case ("model", "library", "beams", "iterations", &
        "cuts", "weight", "int", "real", "complex", &
        "scale", "factorization_scale", "renormalization_scale", &
        "selection", "reweight", "analysis", "pdg", &
        "stable", "unstable", "polarized", "unpolarized", &

```

```

        "results", "expect", "intrinsic", "string", "logical")
    cmd%name(i) = parse_node_get_key (pn_var)
case ("result_var")
    pn_prefix => parse_node_get_sub_ptr (pn_var)
    pn_name => parse_node_get_next_ptr (pn_prefix)
    if (associated (pn_name)) then
        cmd%name(i) = parse_node_get_key (pn_prefix) &
            // "(" // parse_node_get_string (pn_name) // ")"
    else
        cmd%name(i) = parse_node_get_key (pn_prefix)
    end if
case ("log_var", "string_var", "alias_var")
    pn_prefix => parse_node_get_sub_ptr (pn_var)
    pn_name => parse_node_get_next_ptr (pn_prefix)
    key = parse_node_get_key (pn_prefix)
    if (associated (pn_name)) then
        select case (char (parse_node_get_rule_key (pn_name)))
        case ("var_name")
            select case (char (key))
            case ("?", "$") ! $ sign
                cmd%name(i) = key // parse_node_get_string (pn_name)
            case ("alias")
                cmd%name(i) = parse_node_get_string (pn_name)
            end select
        case default
            call parse_node_mismatch &
                ("var_name", pn_name)
        end select
    else
        cmd%name(i) = key
    end if
case default
    cmd%name(i) = parse_node_get_string (pn_var)
end select
pn_var => parse_node_get_next_ptr (pn_var)
end do
else
    allocate (cmd%name (0))
end if
end subroutine cmd_show_compile

```

Execute. Scan the list of objects to show.

```

<Commands: parameters>≡
    integer, parameter, public :: SHOW_BUFFER_SIZE = 4096
<Commands: cmd show: TBP>+≡
    procedure :: execute => cmd_show_execute
<Commands: procedures>+≡
    subroutine cmd_show_execute (cmd, global)
        class(cmd_show_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(var_list_t), pointer :: var_list, model_vars
        type(model_t), pointer :: model
        type(string_t) :: name
    end subroutine

```



```

integer :: n, pdg
type(flavor_t) :: flv
type(process_library_t), pointer :: prc_lib
type(process_t), pointer :: process
logical :: pacified
character(SHOW_BUFFER_SIZE) :: buffer
integer :: i, j, u, u_log, u_out
u = free_unit ()
var_list => cmd%local%var_list
if (associated (cmd%local%model)) then
    model_vars => cmd%local%model%get_var_list_ptr ()
else
    model_vars => null ()
end if
pacified = var_list%get_lval (var_str ("?pacify"))
open (u, status = "scratch", action = "readwrite")
if (associated (cmd%local%model)) then
    name = cmd%local%model%get_name ()
end if
if (size (cmd%name) == 0) then
    if (associated (model_vars)) then
        call var_list_write (model_vars, model_name = name, &
            unit = u, pacified = pacified, follow_link = .false.)
    end if
    call var_list_write (var_list, unit = u, pacified = pacified)
else
    do i = 1, size (cmd%name)
        select case (char (cmd%name(i)))
        case ("model")
            if (associated (cmd%local%model)) then
                call cmd%local%model%show (u)
            else
                write (u, "(A)") "Model: [undefined]"
            end if
        case ("library")
            if (associated (cmd%local%prclib)) then
                call cmd%local%prclib%show (u)
            else
                write (u, "(A)") "Process library: [undefined]"
            end if
        case ("beams")
            call cmd%local%show_beams (u)
        case ("iterations")
            call cmd%local%it_list%write (u)
        case ("results")
            call cmd%local%process_stack%show (u)
        case ("stable")
            call cmd%local%model%show_stable (u)
        case ("polarized")
            call cmd%local%model%show_polarized (u)
        case ("unpolarized")
            call cmd%local%model%show_unpolarized (u)
        case ("unstable")
            model => cmd%local%model
        end select
    end do

```

```

call model%show_unstable (u)
n = model%get_n_field ()
do j = 1, n
  pdg = model%get_pdg (j)
  call flv%init (pdg, model)
  if (.not. flv%is_stable ()) &
    call show_unstable (cmd%local, pdg, u)
  if (flv%has_antiparticle ()) then
    associate (anti => flv%anti ())
    if (.not. anti%is_stable ()) &
      call show_unstable (cmd%local, -pdg, u)
    end associate
  end if
end do
case ("cuts", "weight", "scale", &
      "factorization_scale", "renormalization_scale", &
      "selection", "reweight", "analysis")
  call cmd%local%pn%show (cmd%name(i), u)
case ("expect")
  call expect_summary (force = .true.)
case ("intrinsic")
  call var_list_write (var_list, &
    intrinsic=.true., unit=u, pacified = pacified)
case ("logical")
  if (associated (model_vars)) then
    call var_list_write (model_vars, only_type=V_LOG, &
      model_name = name, unit=u, pacified = pacified, &
      follow_link=.false.)
  end if
  call var_list_write (var_list, &
    only_type=V_LOG, unit=u, pacified = pacified)
case ("int")
  if (associated (model_vars)) then
    call var_list_write (model_vars, only_type=V_INT, &
      model_name = name, unit=u, pacified = pacified, &
      follow_link=.false.)
  end if
  call var_list_write (var_list, only_type=V_INT, &
    unit=u, pacified = pacified)
case ("real")
  if (associated (model_vars)) then
    call var_list_write (model_vars, only_type=V_REAL, &
      model_name = name, unit=u, pacified = pacified, &
      follow_link=.false.)
  end if
  call var_list_write (var_list, only_type=V_REAL, &
    unit=u, pacified = pacified)
case ("complex")
  if (associated (model_vars)) then
    call var_list_write (model_vars, only_type=V_CMPLX, &
      model_name = name, unit=u, pacified = pacified, &
      follow_link=.false.)
  end if
  call var_list_write (var_list, only_type=V_CMPLX, &

```

```

        unit=u, pacified = pacified)
case ("pdg")
    if (associated (model_vars)) then
        call var_list_write (model_vars, only_type=V_PDG, &
            model_name = name, unit=u, pacified = pacified, &
            follow_link=.false.)
    end if
    call var_list_write (var_list, only_type=V_PDG, &
        unit=u, pacified = pacified)
case ("string")
    if (associated (model_vars)) then
        call var_list_write (model_vars, only_type=V_STR, &
            model_name = name, unit=u, pacified = pacified, &
            follow_link=.false.)
    end if
    call var_list_write (var_list, only_type=V_STR, &
        unit=u, pacified = pacified)
case default
    if (analysis_exists (cmd%name(i))) then
        call analysis_write (cmd%name(i), u)
    else if (cmd%local%process_stack%exists (cmd%name(i))) then
        process => cmd%local%process_stack%get_process_ptr (cmd%name(i))
        call process%show (u)
    else if (associated (cmd%local%prclib_stack%get_library_ptr &
        (cmd%name(i)))) then
        prc_lib => cmd%local%prclib_stack%get_library_ptr (cmd%name(i))
        call prc_lib%show (u)
    else if (associated (model_vars)) then
        if (model_vars%contains (cmd%name(i), follow_link=.false.)) then
            call var_list_write_var (model_vars, cmd%name(i), &
                unit = u, model_name = name, pacified = pacified)
        else if (var_list%contains (cmd%name(i))) then
            call var_list_write_var (var_list, cmd%name(i), &
                unit = u, pacified = pacified)
        else
            call msg_error ("show: object '" // char (cmd%name(i)) &
                // "' not found")
        end if
    else if (var_list%contains (cmd%name(i))) then
        call var_list_write_var (var_list, cmd%name(i), &
            unit = u, pacified = pacified)
    else
        call msg_error ("show: object '" // char (cmd%name(i)) &
            // "' not found")
    end if
end select
end do
end if
rewind (u)
u_log = logfile_unit ()
u_out = given_output_unit ()
do
    read (u, "(A)", end = 1) buffer
    if (u_log > 0) write (u_log, "(A)") trim (buffer)

```

```

        if (u_out > 0) write (u_out, "(A)") trim (buffer)
    end do
1   close (u)
    if (u_log > 0) flush (u_log)
    if (u_out > 0) flush (u_out)
end subroutine cmd_show_execute

```

Clear values

This command clears the current values of variables or other objects, where this makes sense. It parallels the `show` command. The objects are cleared, but not deleted.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_clear_t
        private
        type(string_t), dimension(:), allocatable :: name
    contains
        ⟨Commands: cmd clear: TBP⟩
    end type cmd_clear_t

```

Output: list the names of the objects to be cleared.

```

⟨Commands: cmd clear: TBP⟩≡
    procedure :: write => cmd_clear_write

⟨Commands: procedures⟩+≡
    subroutine cmd_clear_write (cmd, unit, indent)
        class(cmd_clear_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A)", advance="no") "clear: "
        if (allocated (cmd%name)) then
            do i = 1, size (cmd%name)
                write (u, "(1x,A)", advance="no") char (cmd%name(i))
            end do
            write (u, *)
        else
            write (u, "(5x,A)") "[undefined]"
        end if
    end subroutine cmd_clear_write

```

Compile. Allocate an array which is filled with the names of the objects to be cleared.

Note: there is currently no need to account for options, but we prepare for that possibility.

```

⟨Commands: cmd clear: TBP⟩+≡
    procedure :: compile => cmd_clear_compile

```

{Commands: procedures}+≡

```

subroutine cmd_clear_compile (cmd, global)
  class(cmd_clear_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_arg, pn_var, pn_prefix, pn_name
  type(string_t) :: key
  integer :: i, n_args
  pn_arg => parse_node_get_sub_ptr (cmd%pn, 2)
  if (associated (pn_arg)) then
    select case (char (parse_node_get_rule_key (pn_arg)))
    case ("clear_arg")
      cmd%pn_opt => parse_node_get_next_ptr (pn_arg)
    case default
      cmd%pn_opt => pn_arg
      pn_arg => null ()
    end select
  end if
  call cmd%compile_options (global)
  if (associated (pn_arg)) then
    n_args = parse_node_get_n_sub (pn_arg)
    allocate (cmd%name (n_args))
    pn_var => parse_node_get_sub_ptr (pn_arg)
    i = 0
    do while (associated (pn_var))
      i = i + 1
      select case (char (parse_node_get_rule_key (pn_var)))
      case ("beams", "iterations", &
            "cuts", "weight", &
            "scale", "factorization_scale", "renormalization_scale", &
            "selection", "reweight", "analysis", &
            "unstable", "polarized", &
            "expect")
        cmd%name(i) = parse_node_get_key (pn_var)
      case ("log_var", "string_var")
        pn_prefix => parse_node_get_sub_ptr (pn_var)
        pn_name => parse_node_get_next_ptr (pn_prefix)
        key = parse_node_get_key (pn_prefix)
        if (associated (pn_name)) then
          select case (char (parse_node_get_rule_key (pn_name)))
          case ("var_name")
            select case (char (key))
            case ("?", "$") ! $ sign
              cmd%name(i) = key // parse_node_get_string (pn_name)
            end select
          case default
            call parse_node_mismatch &
              ("var_name", pn_name)
          end select
        else
          cmd%name(i) = key
        end if
      case default
        cmd%name(i) = parse_node_get_string (pn_var)
      end select
    end do
  end if
end subroutine

```

```

        pn_var => parse_node_get_next_ptr (pn_var)
    end do
else
    allocate (cmd%name (0))
end if
end subroutine cmd_clear_compile

```

Execute. Scan the list of objects to clear.

Objects that can be shown but not cleared: model, library, results

(Commands: cmd clear: TBP)+≡

```

procedure :: execute => cmd_clear_execute

```

(Commands: procedures)+≡

```

subroutine cmd_clear_execute (cmd, global)
    class(cmd_clear_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    integer :: i
    logical :: success
    type(var_list_t), pointer :: model_vars
    if (size (cmd%name) == 0) then
        call msg_warning ("clear: no object specified")
    else
        do i = 1, size (cmd%name)
            success = .true.
            select case (char (cmd%name(i)))
            case ("beams")
                call cmd%local%clear_beams ()
            case ("iterations")
                call cmd%local%it_list%clear ()
            case ("polarized")
                call cmd%local%model%clear_polarized ()
            case ("unstable")
                call cmd%local%model%clear_unstable ()
            case ("cuts", "weight", "scale", &
                "factorization_scale", "renormalization_scale", &
                "selection", "reweight", "analysis")
                call cmd%local%pn%clear (cmd%name(i))
            case ("expect")
                call expect_clear ()
            case default
                if (analysis_exists (cmd%name(i))) then
                    call analysis_clear (cmd%name(i))
                else if (cmd%local%var_list%contains (cmd%name(i))) then
                    if (.not. cmd%local%var_list%is_locked (cmd%name(i))) then
                        call cmd%local%var_list%unset (cmd%name(i))
                    else
                        call msg_error ("clear: variable '" // char (cmd%name(i)) &
                            // "' is locked and can't be cleared")
                        success = .false.
                    end if
                else if (associated (cmd%local%model)) then
                    model_vars => cmd%local%model%get_var_list_ptr ()
                    if (model_vars%contains (cmd%name(i), follow_link=.false.)) then
                        call msg_error ("clear: variable '" // char (cmd%name(i)) &

```

```

        // '' is a model variable and can't be cleared")
    else
        call msg_error ("clear: object '" // char (cmd%name(i)) &
            // '' not found")
    end if
    success = .false.
else
    call msg_error ("clear: object '" // char (cmd%name(i)) &
        // '' not found")
    success = .false.
end if
end select
if (success) call msg_message ("cleared: " // char (cmd%name(i)))
end do
end if
end subroutine cmd_clear_execute

```

Compare values of variables to expectation

The implementation is similar to the `show` command. There are just two arguments: two values that should be compared. For providing local values for the numerical tolerance, the command has a local argument list.

If the expectation fails, an error condition is recorded.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_expect_t
        private
            type(parse_node_t), pointer :: pn_lexpr => null ()
        contains
            ⟨Commands: cmd expect: TBP⟩
    end type cmd_expect_t

```

Simply tell the status.

```

⟨Commands: cmd expect: TBP⟩≡
    procedure :: write => cmd_expect_write

⟨Commands: procedures⟩+≡
    subroutine cmd_expect_write (cmd, unit, indent)
        class(cmd_expect_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        if (associated (cmd%pn_lexpr)) then
            write (u, "(1x,A)" "expect: [expression associated]"
        else
            write (u, "(1x,A)" "expect: [undefined]"
        end if
    end subroutine cmd_expect_write

```

Compile. This merely assigns the parse node, the actual compilation is done at execution. This is necessary because the origin of variables (local/global) may

change during execution.

```

⟨Commands: cmd expect: TBP⟩+≡
  procedure :: compile => cmd_expect_compile

⟨Commands: procedures⟩+≡
  subroutine cmd_expect_compile (cmd, global)
    class(cmd_expect_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_arg
    pn_arg => parse_node_get_sub_ptr (cmd%pn, 2)
    cmd%pn_opt => parse_node_get_next_ptr (pn_arg)
    cmd%pn_lexpr => parse_node_get_sub_ptr (pn_arg)
    call cmd%compile_options (global)
  end subroutine cmd_expect_compile

```

Execute. Evaluate both arguments, print them and their difference (if numerical), and whether they agree. Record the result.

```

⟨Commands: cmd expect: TBP⟩+≡
  procedure :: execute => cmd_expect_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_expect_execute (cmd, global)
    class(cmd_expect_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    logical :: success, is_known
    var_list => cmd%local%get_var_list_ptr ()
    success = eval_log (cmd%pn_lexpr, var_list, is_known=is_known)
    if (is_known) then
      if (success) then
        call msg_message ("expect: success")
      else
        call msg_error ("expect: failure")
      end if
    else
      call msg_error ("expect: undefined result")
      success = .false.
    end if
    call expect_record (success)
  end subroutine cmd_expect_execute

```

Beams

The beam command includes both beam and structure-function definition.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_beams_t
  private
  integer :: n_in = 0
  type(parse_node_p), dimension(:), allocatable :: pn_pdg
  integer :: n_sf_record = 0
  integer, dimension(:), allocatable :: n_entry
  type(parse_node_p), dimension(:, :), allocatable :: pn_sf_entry

```



```

contains
  <Commands: cmd beams: TBP>
end type cmd_beams_t

```

Output. The particle expressions are not resolved.

```

<Commands: cmd beams: TBP>≡
  procedure :: write => cmd_beams_write

<Commands: procedures>+≡
  subroutine cmd_beams_write (cmd, unit, indent)
    class(cmd_beams_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    select case (cmd%n_in)
    case (1)
      write (u, "(1x,A)") "beams: 1 [decay]"
    case (2)
      write (u, "(1x,A)") "beams: 2 [scattering]"
    case default
      write (u, "(1x,A)") "beams: [undefined]"
    end select
    if (allocated (cmd%n_entry)) then
      if (cmd%n_sf_record > 0) then
        write (u, "(1x,A,99(1x,I0))") "structure function entries:", &
          cmd%n_entry
      end if
    end if
  end subroutine cmd_beams_write

```

Compile. Find and assign the parse nodes.

Note: local environments are not yet supported.

```

<Commands: cmd beams: TBP>+≡
  procedure :: compile => cmd_beams_compile

<Commands: procedures>+≡
  subroutine cmd_beams_compile (cmd, global)
    class(cmd_beams_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_beam_def, pn_beam_spec
    type(parse_node_t), pointer :: pn_beam_list
    type(parse_node_t), pointer :: pn_codes
    type(parse_node_t), pointer :: pn_strfun_seq, pn_strfun_pair
    type(parse_node_t), pointer :: pn_strfun_def
    integer :: i
    pn_beam_def => parse_node_get_sub_ptr (cmd%pn, 3)
    pn_beam_spec => parse_node_get_sub_ptr (pn_beam_def)
    pn_strfun_seq => parse_node_get_next_ptr (pn_beam_spec)
    pn_beam_list => parse_node_get_sub_ptr (pn_beam_spec)
    call cmd%compile_options (global)
    cmd%n_in = parse_node_get_n_sub (pn_beam_list)
    allocate (cmd%pn_pdg (cmd%n_in))
    pn_codes => parse_node_get_sub_ptr (pn_beam_list)

```

```

do i = 1, cmd%n_in
  cmd%pn_pdg(i)%ptr => pn_codes
  pn_codes => parse_node_get_next_ptr (pn_codes)
end do
if (associated (pn_strfun_seq)) then
  cmd%n_sf_record = parse_node_get_n_sub (pn_beam_def) - 1
  allocate (cmd%n_entry (cmd%n_sf_record), source = 1)
  allocate (cmd%pn_sf_entry (2, cmd%n_sf_record))
  do i = 1, cmd%n_sf_record
    pn_strfun_pair => parse_node_get_sub_ptr (pn_strfun_seq, 2)
    pn_strfun_def => parse_node_get_sub_ptr (pn_strfun_pair)
    cmd%pn_sf_entry(1,i)%ptr => pn_strfun_def
    pn_strfun_def => parse_node_get_next_ptr (pn_strfun_def)
    cmd%pn_sf_entry(2,i)%ptr => pn_strfun_def
    if (associated (pn_strfun_def)) cmd%n_entry(i) = 2
    pn_strfun_seq => parse_node_get_next_ptr (pn_strfun_seq)
  end do
else
  allocate (cmd%n_entry (0))
  allocate (cmd%pn_sf_entry (0, 0))
end if
end subroutine cmd_beams_compile

```

Command execution: Determine beam particles and structure-function names, if any. The results are stored in the `beam_structure` component of the global data block.

```

<Commands: cmd_beams: TBP>+≡
  procedure :: execute => cmd_beams_execute

<Commands: procedures>+≡
  subroutine cmd_beams_execute (cmd, global)
    class(cmd_beams_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(pdg_array_t) :: pdg_array
    integer, dimension(:), allocatable :: pdg
    type(flavor_t), dimension(:), allocatable :: flv
    type(parse_node_t), pointer :: pn_key
    type(string_t) :: sf_name
    integer :: i, j
    call lhpdf_global_reset ()
    var_list => cmd%local%get_var_list_ptr ()
    allocate (flv (cmd%n_in))
    do i = 1, cmd%n_in
      pdg_array = eval_pdg_array (cmd%pn_pdg(i)%ptr, var_list)
      pdg = pdg_array
      select case (size (pdg))
      case (1)
        call flv(i)%init ( pdg(1), cmd%local%model)
      case default
        call msg_fatal ("Beams: beam particles must be unique")
      end select
    end do
  select case (cmd%n_in)

```

```

case (1)
  if (cmd%n_sf_record > 0) then
    call msg_fatal ("Beam setup: no structure functions allowed &
      &for decay")
  end if
  call global%beam_structure%init_sf (flv%get_name ())
case (2)
  call global%beam_structure%init_sf (flv%get_name (), cmd%n_entry)
  do i = 1, cmd%n_sf_record
    do j = 1, cmd%n_entry(i)
      pn_key => parse_node_get_sub_ptr (cmd%pn_sf_entry(j,i)%ptr)
      sf_name = parse_node_get_key (pn_key)
      call global%beam_structure%set_sf (i, j, sf_name)
    end do
  end do
end select
end subroutine cmd_beams_execute

```

Density matrices for beam polarization

For holding beam polarization, we define a notation and a data structure for sparse matrices. The entries (and the index expressions) are numerical expressions, so we use evaluation trees.

Each entry in the sparse matrix is an n-tuple of expressions. The first tuple elements represent index values, the last one is an arbitrary (complex) number. Absent expressions are replaced by default-value rules.

Note: Here, and in some other commands, we would like to store an evaluation tree, not just a parse node pointer. However, the current expression handler wants all variables defined, so the evaluation tree can only be built by `evaluate`, i.e., compiled just-in-time and evaluated immediately.

```

⟨Commands: types⟩+≡
  type :: sentry_expr_t
    type(parse_node_p), dimension(:), allocatable :: expr
  contains
    ⟨Commands: sentry expr: TBP⟩
  end type sentry_expr_t

```

Compile parse nodes into evaluation trees.

```

⟨Commands: sentry expr: TBP⟩≡
  procedure :: compile => sentry_expr_compile

⟨Commands: procedures⟩+≡
  subroutine sentry_expr_compile (sentry, pn)
    class(sentry_expr_t), intent(out) :: sentry
    type(parse_node_t), intent(in), target :: pn
    type(parse_node_t), pointer :: pn_expr, pn_extra
    integer :: n_expr, i
    n_expr = parse_node_get_n_sub (pn)
    allocate (sentry%expr (n_expr))
    if (n_expr > 0) then
      i = 0
      pn_expr => parse_node_get_sub_ptr (pn)

```

```

pn_extra => parse_node_get_next_ptr (pn_expr)
do i = 1, n_expr
  sentry%expr(i)%ptr => pn_expr
  if (associated (pn_extra)) then
    pn_expr => parse_node_get_sub_ptr (pn_extra, 2)
    pn_extra => parse_node_get_next_ptr (pn_extra)
  end if
end do
end if
end subroutine sentry_expr_compile

```

Evaluate the expressions and return an index array of predefined length together with a complex value. If the value (as the last expression) is undefined, set it to unity. If index values are undefined, repeat the previous index value.

(Commands: sentry expr: TBP)+≡

```

procedure :: evaluate => sentry_expr_evaluate

```

(Commands: procedures)+≡

```

subroutine sentry_expr_evaluate (sentry, index, value, global)
  class(sentry%expr_t), intent(inout) :: sentry
  integer, dimension(:), intent(out) :: index
  complex(default), intent(out) :: value
  type(rt_data_t), intent(in), target :: global
  type(var_list_t), pointer :: var_list
  integer :: i, n_expr, n_index
  type(eval_tree_t) :: eval_tree
  var_list => global%get_var_list_ptr ()
  n_expr = size (sentry%expr)
  n_index = size (index)
  if (n_expr <= n_index + 1) then
    do i = 1, min (n_expr, n_index)
      associate (expr => sentry%expr(i))
        call eval_tree%init_expr (expr%ptr, var_list)
        call eval_tree%evaluate ()
        if (eval_tree%is_known ()) then
          index(i) = eval_tree%get_int ()
        else
          call msg_fatal ("Evaluating density matrix: undefined index")
        end if
      end associate
    end do
    do i = n_expr + 1, n_index
      index(i) = index(n_expr)
    end do
  if (n_expr == n_index + 1) then
    associate (expr => sentry%expr(n_expr))
      call eval_tree%init_expr (expr%ptr, var_list)
      call eval_tree%evaluate ()
      if (eval_tree%is_known ()) then
        value = eval_tree%get_cmplx ()
      else
        call msg_fatal ("Evaluating density matrix: undefined index")
      end if
    end associate
    call eval_tree%final ()
  end if
end subroutine

```

```

        end associate
    else
        value = 1
    end if
else
    call msg_fatal ("Evaluating density matrix: index expression too long")
end if
end subroutine sentry_expr_evaluate

```

The sparse matrix itself consists of an arbitrary number of entries.

```

⟨Commands: types⟩+≡
type :: smatrix_expr_t
    type(sentry_expr_t), dimension(:), allocatable :: entry
contains
    ⟨Commands: smatrix expr: TBP⟩
end type smatrix_expr_t

```

Compile: assign sub-nodes to sentry-expressions and compile those.

```

⟨Commands: smatrix expr: TBP⟩≡
    procedure :: compile => smatrix_expr_compile

⟨Commands: procedures⟩+≡
subroutine smatrix_expr_compile (smatrix_expr, pn)
    class(smatrix_expr_t), intent(out) :: smatrix_expr
    type(parse_node_t), intent(in), target :: pn
    type(parse_node_t), pointer :: pn_arg, pn_entry
    integer :: n_entry, i
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    if (associated (pn_arg)) then
        n_entry = parse_node_get_n_sub (pn_arg)
        allocate (smatrix_expr%entry (n_entry))
        pn_entry => parse_node_get_sub_ptr (pn_arg)
        do i = 1, n_entry
            call smatrix_expr%entry(i)%compile (pn_entry)
            pn_entry => parse_node_get_next_ptr (pn_entry)
        end do
    else
        allocate (smatrix_expr%entry (0))
    end if
end subroutine smatrix_expr_compile

```

Evaluate the entries and build a new smatrix object, which contains just the numerical results.

```

⟨Commands: smatrix expr: TBP⟩+≡
    procedure :: evaluate => smatrix_expr_evaluate

⟨Commands: procedures⟩+≡
subroutine smatrix_expr_evaluate (smatrix_expr, smatrix, global)
    class(smatrix_expr_t), intent(inout) :: smatrix_expr
    type(smatrix_t), intent(out) :: smatrix
    type(rt_data_t), intent(in), target :: global
    integer, dimension(2) :: idx
    complex(default) :: value

```

```

integer :: i, n_entry
n_entry = size (smatrix_expr%entry)
call smatrix%init (2, n_entry)
do i = 1, n_entry
    call smatrix_expr%entry(i)%evaluate (idx, value, global)
    call smatrix%set_entry (i, idx, value)
end do
end subroutine smatrix_expr_evaluate

```

Beam polarization density

The beam polarization command defines spin density matrix for one or two beams (scattering or decay).

```

⟨Commands: types⟩+≡
type, extends (command_t) :: cmd_beams_pol_density_t
private
integer :: n_in = 0
type(smatrix_expr_t), dimension(:), allocatable :: smatrix
contains
⟨Commands: cmd beams pol density: TBP⟩
end type cmd_beams_pol_density_t

```

Output.

```

⟨Commands: cmd beams pol density: TBP⟩≡
procedure :: write => cmd_beams_pol_density_write

⟨Commands: procedures⟩+≡
subroutine cmd_beams_pol_density_write (cmd, unit, indent)
class(cmd_beams_pol_density_t), intent(in) :: cmd
integer, intent(in), optional :: unit, indent
integer :: u
u = given_output_unit (unit); if (u < 0) return
call write_indent (u, indent)
select case (cmd%n_in)
case (1)
    write (u, "(1x,A)") "beams polarization setup: 1 [decay]"
case (2)
    write (u, "(1x,A)") "beams polarization setup: 2 [scattering]"
case default
    write (u, "(1x,A)") "beams polarization setup: [undefined]"
end select
end subroutine cmd_beams_pol_density_write

```

Compile. Find and assign the parse nodes.

Note: local environments are not yet supported.

```

⟨Commands: cmd beams pol density: TBP⟩+≡
procedure :: compile => cmd_beams_pol_density_compile

⟨Commands: procedures⟩+≡
subroutine cmd_beams_pol_density_compile (cmd, global)
class(cmd_beams_pol_density_t), intent(inout) :: cmd
type(rt_data_t), intent(inout), target :: global

```

```

type(parse_node_t), pointer :: pn_pol_spec, pn_smatrix
integer :: i
pn_pol_spec => parse_node_get_sub_ptr (cmd%pn, 3)
call cmd%compile_options (global)
cmd%n_in = parse_node_get_n_sub (pn_pol_spec)
allocate (cmd%smatrix (cmd%n_in))
pn_smatrix => parse_node_get_sub_ptr (pn_pol_spec)
do i = 1, cmd%n_in
    call cmd%smatrix(i)%compile (pn_smatrix)
    pn_smatrix => parse_node_get_next_ptr (pn_smatrix)
end do
end subroutine cmd_beams_pol_density_compile

```

Command execution: Fill polarization density matrices. No check yet, the matrices are checked and normalized when the actual beam object is created, just before integration. For intermediate storage, we use the `beam_structure` object in the `global` data set.

```

⟨Commands: cmd beams pol density: TBP⟩+≡
    procedure :: execute => cmd_beams_pol_density_execute

⟨Commands: procedures⟩+≡
    subroutine cmd_beams_pol_density_execute (cmd, global)
        class(cmd_beams_pol_density_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(smatrix_t) :: smatrix
        integer :: i
        call global%beam_structure%init_pol (cmd%n_in)
        do i = 1, cmd%n_in
            call cmd%smatrix(i)%evaluate (smatrix, global)
            call global%beam_structure%set_smatrix (i, smatrix)
        end do
    end subroutine cmd_beams_pol_density_execute

```

Beam polarization fraction

In addition to the polarization density matrix, we can independently specify the polarization fraction for one or both beams.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_beams_pol_fraction_t
    private
        integer :: n_in = 0
        type(parse_node_p), dimension(:), allocatable :: expr
    contains
        ⟨Commands: cmd beams pol fraction: TBP⟩
    end type cmd_beams_pol_fraction_t

```

Output.

```

⟨Commands: cmd beams pol fraction: TBP⟩≡
    procedure :: write => cmd_beams_pol_fraction_write

```

```

<Commands: procedures>+≡
subroutine cmd_beams_pol_fraction_write (cmd, unit, indent)
  class(cmd_beams_pol_fraction_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  select case (cmd%n_in)
  case (1)
    write (u, "(1x,A)") "beams polarization fraction: 1 [decay]"
  case (2)
    write (u, "(1x,A)") "beams polarization fraction: 2 [scattering]"
  case default
    write (u, "(1x,A)") "beams polarization fraction: [undefined]"
  end select
end subroutine cmd_beams_pol_fraction_write

```

Compile. Find and assign the parse nodes.

Note: local environments are not yet supported.

```

<Commands: cmd beams pol fraction: TBP>+≡
procedure :: compile => cmd_beams_pol_fraction_compile

<Commands: procedures>+≡
subroutine cmd_beams_pol_fraction_compile (cmd, global)
  class(cmd_beams_pol_fraction_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_frac_spec, pn_expr
  integer :: i
  pn_frac_spec => parse_node_get_sub_ptr (cmd%pn, 3)
  call cmd%compile_options (global)
  cmd%n_in = parse_node_get_n_sub (pn_frac_spec)
  allocate (cmd%expr (cmd%n_in))
  pn_expr => parse_node_get_sub_ptr (pn_frac_spec)
  do i = 1, cmd%n_in
    cmd%expr(i)%ptr => pn_expr
    pn_expr => parse_node_get_next_ptr (pn_expr)
  end do
end subroutine cmd_beams_pol_fraction_compile

```

Command execution: Retrieve the numerical values of the beam polarization fractions. The results are stored in the `beam_structure` component of the `global` data block.

```

<Commands: cmd beams pol fraction: TBP>+≡
procedure :: execute => cmd_beams_pol_fraction_execute

<Commands: procedures>+≡
subroutine cmd_beams_pol_fraction_execute (cmd, global)
  class(cmd_beams_pol_fraction_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  real(default), dimension(:), allocatable :: pol_f
  type(eval_tree_t) :: expr
  integer :: i
  var_list => global%get_var_list_ptr ()

```



```

allocate (pol_f (cmd%n_in))
do i = 1, cmd%n_in
  call expr%init_expr (cmd%expr(i)%ptr, var_list)
  call expr%evaluate ()
  if (expr%is_known ()) then
    pol_f(i) = expr%get_real ()
  else
    call msg_fatal ("beams polarization fraction: undefined value")
  end if
  call expr%final ()
end do
call global%beam_structure%set_pol_f (pol_f)
end subroutine cmd_beams_pol_fraction_execute

```

Beam momentum

This is completely analogous to the previous command, hence we can use inheritance.

```

⟨Commands: types⟩+≡
  type, extends (cmd_beams_pol_fraction_t) :: cmd_beams_momentum_t
  contains
    ⟨Commands: cmd beams momentum: TBP⟩
end type cmd_beams_momentum_t

```

Output.

```

⟨Commands: cmd beams momentum: TBP⟩≡
  procedure :: write => cmd_beams_momentum_write

⟨Commands: procedures⟩+≡
  subroutine cmd_beams_momentum_write (cmd, unit, indent)
    class(cmd_beams_momentum_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    select case (cmd%n_in)
    case (1)
      write (u, "(1x,A)") "beams momentum: 1 [decay]"
    case (2)
      write (u, "(1x,A)") "beams momentum: 2 [scattering]"
    case default
      write (u, "(1x,A)") "beams momentum: [undefined]"
    end select
  end subroutine cmd_beams_momentum_write

```

Compile: inherited.

Command execution: Not inherited, but just the error string and the final command are changed.

```

⟨Commands: cmd beams momentum: TBP⟩+≡
  procedure :: execute => cmd_beams_momentum_execute

```

```

<Commands: procedures>+≡
subroutine cmd_beams_momentum_execute (cmd, global)
  class(cmd_beams_momentum_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  real(default), dimension(:), allocatable :: p
  type(eval_tree_t) :: expr
  integer :: i
  var_list => global%get_var_list_ptr ()
  allocate (p (cmd%n_in))
  do i = 1, cmd%n_in
    call expr%init_expr (cmd%expr(i)%ptr, var_list)
    call expr%evaluate ()
    if (expr%is_known ()) then
      p(i) = expr%get_real ()
    else
      call msg_fatal ("beams momentum: undefined value")
    end if
    call expr%final ()
  end do
  call global%beam_structure%set_momentum (p)
end subroutine cmd_beams_momentum_execute

```

Beam angles

Again, this is analogous. There are two angles, polar angle θ and azimuthal angle ϕ , which can be set independently for both beams.

```

<Commands: types>+≡
type, extends (cmd_beams_pol_fraction_t) :: cmd_beams_theta_t
contains
  <Commands: cmd beams theta: TBP>
end type cmd_beams_theta_t

type, extends (cmd_beams_pol_fraction_t) :: cmd_beams_phi_t
contains
  <Commands: cmd beams phi: TBP>
end type cmd_beams_phi_t

```

Output.

```

<Commands: cmd beams theta: TBP>≡
  procedure :: write => cmd_beams_theta_write

<Commands: cmd beams phi: TBP>≡
  procedure :: write => cmd_beams_phi_write

<Commands: procedures>+≡
subroutine cmd_beams_theta_write (cmd, unit, indent)
  class(cmd_beams_theta_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  select case (cmd%n_in)

```

```

case (1)
  write (u, "(1x,A)") "beams theta: 1 [decay]"
case (2)
  write (u, "(1x,A)") "beams theta: 2 [scattering]"
case default
  write (u, "(1x,A)") "beams theta: [undefined]"
end select
end subroutine cmd_beams_theta_write

subroutine cmd_beams_phi_write (cmd, unit, indent)
  class(cmd_beams_phi_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  select case (cmd%n_in)
  case (1)
    write (u, "(1x,A)") "beams phi: 1 [decay]"
  case (2)
    write (u, "(1x,A)") "beams phi: 2 [scattering]"
  case default
    write (u, "(1x,A)") "beams phi: [undefined]"
  end select
end subroutine cmd_beams_phi_write

```

Compile: inherited.

Command execution: Not inherited, but just the error string and the final command are changed.

```

⟨Commands: cmd beams theta: TBP⟩+≡
  procedure :: execute => cmd_beams_theta_execute

⟨Commands: cmd beams phi: TBP⟩+≡
  procedure :: execute => cmd_beams_phi_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_beams_theta_execute (cmd, global)
    class(cmd_beams_theta_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    real(default), dimension(:), allocatable :: theta
    type(eval_tree_t) :: expr
    integer :: i
    var_list => global%get_var_list_ptr ()
    allocate (theta (cmd%n_in))
    do i = 1, cmd%n_in
      call expr%init_expr (cmd%expr(i)%ptr, var_list)
      call expr%evaluate ()
      if (expr%is_known ()) then
        theta(i) = expr%get_real ()
      else
        call msg_fatal ("beams theta: undefined value")
      end if
      call expr%final ()
    end do
  end subroutine

```

```

        call global%beam_structure%set_theta (theta)
    end subroutine cmd_beams_theta_execute

subroutine cmd_beams_phi_execute (cmd, global)
    class(cmd_beams_phi_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    real(default), dimension(:), allocatable :: phi
    type(eval_tree_t) :: expr
    integer :: i
    var_list => global%get_var_list_ptr ()
    allocate (phi (cmd%n_in))
    do i = 1, cmd%n_in
        call expr%init_expr (cmd%expr(i)%ptr, var_list)
        call expr%evaluate ()
        if (expr%is_known ()) then
            phi(i) = expr%get_real ()
        else
            call msg_fatal ("beams phi: undefined value")
        end if
        call expr%final ()
    end do
    call global%beam_structure%set_phi (phi)
end subroutine cmd_beams_phi_execute

```

Cuts

Define a cut expression. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the cut expression is used.

```

<Commands: types>+≡
    type, extends (command_t) :: cmd_cuts_t
    private
    type(parse_node_t), pointer :: pn_lexpr => null ()
    contains
    <Commands: cmd cuts: TBP>
end type cmd_cuts_t

```

Output. Do not print the parse tree, since this may get cluttered. Just a message that cuts have been defined.

```

<Commands: cmd cuts: TBP>≡
    procedure :: write => cmd_cuts_write

<Commands: procedures>+≡
    subroutine cmd_cuts_write (cmd, unit, indent)
        class(cmd_cuts_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A)") "cuts: [defined]"
    end subroutine cmd_cuts_write

```

Compile. Simply store the parse (sub)tree.

```

⟨Commands: cmd cuts: TBP⟩+≡
  procedure :: compile => cmd_cuts_compile

⟨Commands: procedures⟩+≡
  subroutine cmd_cuts_compile (cmd, global)
    class(cmd_cuts_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_lexpr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_cuts_compile

```

Instead of evaluating the cut expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```

⟨Commands: cmd cuts: TBP⟩+≡
  procedure :: execute => cmd_cuts_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_cuts_execute (cmd, global)
    class(cmd_cuts_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%cuts_lexpr => cmd%pn_lexpr
  end subroutine cmd_cuts_execute

```

General, Factorization and Renormalization Scales

Define a scale expression for either the renormalization or the factorization scale. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the expression is used.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_scale_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  contains
    ⟨Commands: cmd scale: TBP⟩
  end type cmd_scale_t

```

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_fac_scale_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  contains
    ⟨Commands: cmd fac scale: TBP⟩
  end type cmd_fac_scale_t

```

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_ren_scale_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  contains
    ⟨Commands: cmd ren scale: TBP⟩

```

```
end type cmd_ren_scale_t
```

Output. Do not print the parse tree, since this may get cluttered. Just a message that scale, renormalization and factorization have been defined, respectively.

```
<Commands: cmd scale: TBP>≡
  procedure :: write => cmd_scale_write

<Commands: procedures>+≡
  subroutine cmd_scale_write (cmd, unit, indent)
    class(cmd_scale_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "scale: [defined]"
  end subroutine cmd_scale_write

<Commands: cmd fac scale: TBP>≡
  procedure :: write => cmd_fac_scale_write

<Commands: procedures>+≡
  subroutine cmd_fac_scale_write (cmd, unit, indent)
    class(cmd_fac_scale_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "factorization scale: [defined]"
  end subroutine cmd_fac_scale_write

<Commands: cmd ren scale: TBP>≡
  procedure :: write => cmd_ren_scale_write

<Commands: procedures>+≡
  subroutine cmd_ren_scale_write (cmd, unit, indent)
    class(cmd_ren_scale_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "renormalization scale: [defined]"
  end subroutine cmd_ren_scale_write
```

Compile. Simply store the parse (sub)tree.

```
<Commands: cmd scale: TBP>+≡
  procedure :: compile => cmd_scale_compile

<Commands: procedures>+≡
  subroutine cmd_scale_compile (cmd, global)
    class(cmd_scale_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_expr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_scale_compile
```

```

<Commands: cmd fac scale: TBP>+≡
  procedure :: compile => cmd_fac_scale_compile

<Commands: procedures>+≡
  subroutine cmd_fac_scale_compile (cmd, global)
    class(cmd_fac_scale_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_expr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_fac_scale_compile

```

```

<Commands: cmd ren scale: TBP>+≡
  procedure :: compile => cmd_ren_scale_compile

<Commands: procedures>+≡
  subroutine cmd_ren_scale_compile (cmd, global)
    class(cmd_ren_scale_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_expr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_ren_scale_compile

```

Instead of evaluating the scale expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```

<Commands: cmd scale: TBP>+≡
  procedure :: execute => cmd_scale_execute

<Commands: procedures>+≡
  subroutine cmd_scale_execute (cmd, global)
    class(cmd_scale_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%scale_expr => cmd%pn_expr
  end subroutine cmd_scale_execute

```

```

<Commands: cmd fac scale: TBP>+≡
  procedure :: execute => cmd_fac_scale_execute

<Commands: procedures>+≡
  subroutine cmd_fac_scale_execute (cmd, global)
    class(cmd_fac_scale_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%fac_scale_expr => cmd%pn_expr
  end subroutine cmd_fac_scale_execute

```

```

<Commands: cmd ren scale: TBP>+≡
  procedure :: execute => cmd_ren_scale_execute

<Commands: procedures>+≡
  subroutine cmd_ren_scale_execute (cmd, global)
    class(cmd_ren_scale_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%ren_scale_expr => cmd%pn_expr
  end subroutine cmd_ren_scale_execute

```

Weight

Define a weight expression. The weight is applied to a process to be integrated, event by event. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the expression is used.

```
<Commands: types>+≡
  type, extends (command_t) :: cmd_weight_t
    private
      type(parse_node_t), pointer :: pn_expr => null ()
    contains
      <Commands: cmd weight: TBP>
    end type cmd_weight_t
```

Output. Do not print the parse tree, since this may get cluttered. Just a message that scale, renormalization and factorization have been defined, respectively.

```
<Commands: cmd weight: TBP>≡
  procedure :: write => cmd_weight_write

<Commands: procedures>+≡
  subroutine cmd_weight_write (cmd, unit, indent)
    class(cmd_weight_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "weight expression: [defined]"
  end subroutine cmd_weight_write
```

Compile. Simply store the parse (sub)tree.

```
<Commands: cmd weight: TBP>+≡
  procedure :: compile => cmd_weight_compile

<Commands: procedures>+≡
  subroutine cmd_weight_compile (cmd, global)
    class(cmd_weight_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_expr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_weight_compile
```

Instead of evaluating the expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
<Commands: cmd weight: TBP>+≡
  procedure :: execute => cmd_weight_execute

<Commands: procedures>+≡
  subroutine cmd_weight_execute (cmd, global)
    class(cmd_weight_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%weight_expr => cmd%pn_expr
  end subroutine cmd_weight_execute
```


Selection

Define a selection expression. This is to be applied upon simulation or event-file rescanning, event by event. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the environment where the expression is used.

```
<Commands: types>+≡
  type, extends (command_t) :: cmd_selection_t
    private
      type(parse_node_t), pointer :: pn_expr => null ()
    contains
      <Commands: cmd selection: TBP>
    end type cmd_selection_t
```

Output. Do not print the parse tree, since this may get cluttered. Just a message that scale, renormalization and factorization have been defined, respectively.

```
<Commands: cmd selection: TBP>≡
  procedure :: write => cmd_selection_write

<Commands: procedures>+≡
  subroutine cmd_selection_write (cmd, unit, indent)
    class(cmd_selection_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "selection expression: [defined]"
  end subroutine cmd_selection_write
```

Compile. Simply store the parse (sub)tree.

```
<Commands: cmd selection: TBP>+≡
  procedure :: compile => cmd_selection_compile

<Commands: procedures>+≡
  subroutine cmd_selection_compile (cmd, global)
    class(cmd_selection_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_expr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_selection_compile
```

Instead of evaluating the expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
<Commands: cmd selection: TBP>+≡
  procedure :: execute => cmd_selection_execute

<Commands: procedures>+≡
  subroutine cmd_selection_execute (cmd, global)
    class(cmd_selection_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%selection_lexpr => cmd%pn_expr
  end subroutine cmd_selection_execute
```

Reweight

Define a reweight expression. This is to be applied upon simulation or event-file rescanning, event by event. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the environment where the expression is used.

```
<Commands: types>+≡
  type, extends (command_t) :: cmd_reweight_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  contains
    <Commands: cmd reweight: TBP>
  end type cmd_reweight_t
```

Output. Do not print the parse tree, since this may get cluttered. Just a message that scale, renormalization and factorization have been defined, respectively.

```
<Commands: cmd reweight: TBP>≡
  procedure :: write => cmd_reweight_write

<Commands: procedures>+≡
  subroutine cmd_reweight_write (cmd, unit, indent)
    class(cmd_reweight_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "reweight expression: [defined]"
  end subroutine cmd_reweight_write
```

Compile. Simply store the parse (sub)tree.

```
<Commands: cmd reweight: TBP>+≡
  procedure :: compile => cmd_reweight_compile

<Commands: procedures>+≡
  subroutine cmd_reweight_compile (cmd, global)
    class(cmd_reweight_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_expr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_reweight_compile
```

Instead of evaluating the expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
<Commands: cmd reweight: TBP>+≡
  procedure :: execute => cmd_reweight_execute

<Commands: procedures>+≡
  subroutine cmd_reweight_execute (cmd, global)
    class(cmd_reweight_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%reweight_expr => cmd%pn_expr
  end subroutine cmd_reweight_execute
```

Alternative Simulation Setups

Together with simulation, we can re-evaluate event weights in the context of alternative setups. The `cmd_alt_setup_t` object is designed to hold these setups, which are brace-enclosed command lists. Compilation is deferred to the simulation environment where the setup expression is used.

```
(Commands: types)+≡
  type, extends (command_t) :: cmd_alt_setup_t
    private
      type(parse_node_p), dimension(:), allocatable :: setup
    contains
      (Commands: cmd alt setup: TBP)
    end type cmd_alt_setup_t
```

Output. Print just a message that the alternative setup list has been defined.

```
(Commands: cmd alt setup: TBP)≡
  procedure :: write => cmd_alt_setup_write

(Commands: procedures)+≡
  subroutine cmd_alt_setup_write (cmd, unit, indent)
    class(cmd_alt_setup_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,I0,A)") "alt_setup: ", size (cmd%setup), " entries"
  end subroutine cmd_alt_setup_write
```

Compile. Store the parse sub-trees in an array.

```
(Commands: cmd alt setup: TBP)+≡
  procedure :: compile => cmd_alt_setup_compile

(Commands: procedures)+≡
  subroutine cmd_alt_setup_compile (cmd, global)
    class(cmd_alt_setup_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_list, pn_setup
    integer :: i
    pn_list => parse_node_get_sub_ptr (cmd%pn, 3)
    if (associated (pn_list)) then
      allocate (cmd%setup (parse_node_get_n_sub (pn_list)))
      i = 1
      pn_setup => parse_node_get_sub_ptr (pn_list)
      do while (associated (pn_setup))
        cmd%setup(i)%ptr => pn_setup
        i = i + 1
        pn_setup => parse_node_get_next_ptr (pn_setup)
      end do
    else
      allocate (cmd%setup (0))
    end if
  end subroutine cmd_alt_setup_compile
```

Execute. Transfer the array of command lists to the global environment.

```

<Commands: cmd alt setup: TBP>+≡
  procedure :: execute => cmd_alt_setup_execute

<Commands: procedures>+≡
  subroutine cmd_alt_setup_execute (cmd, global)
    class(cmd_alt_setup_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    if (allocated (global%pn%alt_setup)) deallocate (global%pn%alt_setup)
    allocate (global%pn%alt_setup (size (cmd%setup)), source = cmd%setup)
  end subroutine cmd_alt_setup_execute

```

Integration

Integrate several processes, consecutively with identical parameters.

```

<Commands: types>+≡
  type, extends (command_t) :: cmd_integrate_t
  private
  integer :: n_proc = 0
  type(string_t), dimension(:), allocatable :: process_id
  contains
  <Commands: cmd integrate: TBP>
  end type cmd_integrate_t

```

Output: we know the process IDs.

```

<Commands: cmd integrate: TBP>≡
  procedure :: write => cmd_integrate_write

<Commands: procedures>+≡
  subroutine cmd_integrate_write (cmd, unit, indent)
    class(cmd_integrate_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)", advance="no") "integrate ("
    do i = 1, cmd%n_proc
      if (i > 1) write (u, "(A,1x)", advance="no") ", "
      write (u, "(A)", advance="no") char (cmd%process_id(i))
    end do
    write (u, "(A)") ")"
  end subroutine cmd_integrate_write

```

Compile.

```

<Commands: cmd integrate: TBP>+≡
  procedure :: compile => cmd_integrate_compile

<Commands: procedures>+≡
  subroutine cmd_integrate_compile (cmd, global)
    class(cmd_integrate_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_proclist, pn_proc

```

```

integer :: i
pn_proclist => parse_node_get_sub_ptr (cmd%pn, 2)
cmd%pn_opt => parse_node_get_next_ptr (pn_proclist)
call cmd%compile_options (global)
cmd%n_proc = parse_node_get_n_sub (pn_proclist)
allocate (cmd%process_id (cmd%n_proc))
pn_proc => parse_node_get_sub_ptr (pn_proclist)
do i = 1, cmd%n_proc
  cmd%process_id(i) = parse_node_get_string (pn_proc)
  call global%process_stack%init_result_vars (cmd%process_id(i))
  pn_proc => parse_node_get_next_ptr (pn_proc)
end do
end subroutine cmd_integrate_compile

```

Command execution. Integrate the process(es) with the predefined number of passes, iterations and calls. For structure functions, cuts, weight and scale, use local definitions if present; by default, the local definitions are initialized with the global ones.

The `integrate` procedure should take its input from the currently active local environment, but produce a process record in the stack of the global environment.

Since the process acquires a snapshot of the variable list, so if the global list (or the local one) is deleted, this does no harm. This implies that later changes of the variable list do not affect the stored process.

```

⟨Commands: cmd integrate: TBP⟩+≡
  procedure :: execute => cmd_integrate_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_integrate_execute (cmd, global)
    class(cmd_integrate_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    integer :: i
    do i = 1, cmd%n_proc
      call integrate_process (cmd%process_id(i), cmd%local, global)
      call global%process_stack%fill_result_vars (cmd%process_id(i))
      if (signal_is_pending ()) return
    end do
  end subroutine cmd_integrate_execute

```

Observables

Declare an observable. After the declaration, it can be used to record data, and at the end one can retrieve average and error.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_observable_t
  private
  type(string_t) :: id
  contains
  ⟨Commands: cmd observable: TBP⟩
  end type cmd_observable_t

```

Output. We know the ID.

```
(Commands: cmd observable: TBP)+≡
  procedure :: write => cmd_observable_write

(Commands: procedures)+≡
  subroutine cmd_observable_write (cmd, unit, indent)
    class(cmd_observable_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,A)" "observable: ", char (cmd%id)
  end subroutine cmd_observable_write
```

Compile. Just record the observable ID.

```
(Commands: cmd observable: TBP)+≡
  procedure :: compile => cmd_observable_compile

(Commands: procedures)+≡
  subroutine cmd_observable_compile (cmd, global)
    class(cmd_observable_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_tag
    pn_tag => parse_node_get_sub_ptr (cmd%pn, 2)
    if (associated (pn_tag)) then
      cmd%pn_opt => parse_node_get_next_ptr (pn_tag)
    end if
    call cmd%compile_options (global)
    select case (char (parse_node_get_rule_key (pn_tag)))
    case ("analysis_id")
      cmd%id = parse_node_get_string (pn_tag)
    case default
      call msg_bug ("observable: name expression not implemented (yet)")
    end select
  end subroutine cmd_observable_compile
```

Command execution. This declares the observable and allocates it in the analysis store.

```
(Commands: cmd observable: TBP)+≡
  procedure :: execute => cmd_observable_execute

(Commands: procedures)+≡
  subroutine cmd_observable_execute (cmd, global)
    class(cmd_observable_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(graph_options_t) :: graph_options
    type(string_t) :: label, unit
    var_list => cmd%local%get_var_list_ptr ()
    label = var_list%get_sval (var_str ("obs_label"))
    unit = var_list%get_sval (var_str ("obs_unit"))
    call graph_options_init (graph_options)
    call set_graph_options (graph_options, var_list)
    call analysis_init_observable (cmd%id, label, unit, graph_options)
```

```
end subroutine cmd_observable_execute
```

Histograms

Declare a histogram. At minimum, we have to set lower and upper bound and bin width.

```
<Commands: types>+≡
  type, extends (command_t) :: cmd_histogram_t
    private
    type(string_t) :: id
    type(parse_node_t), pointer :: pn_lower_bound => null ()
    type(parse_node_t), pointer :: pn_upper_bound => null ()
    type(parse_node_t), pointer :: pn_bin_width => null ()
  contains
    <Commands: cmd histogram: TBP>
  end type cmd_histogram_t
```

Output. Just print the ID.

```
<Commands: cmd histogram: TBP>≡
  procedure :: write => cmd_histogram_write

<Commands: procedures>+≡
  subroutine cmd_histogram_write (cmd, unit, indent)
    class(cmd_histogram_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,A)") "histogram: ", char (cmd%id)
  end subroutine cmd_histogram_write
```

Compile. Record the histogram ID and initialize lower, upper bound and bin width.

```
<Commands: cmd histogram: TBP>+≡
  procedure :: compile => cmd_histogram_compile

<Commands: procedures>+≡
  subroutine cmd_histogram_compile (cmd, global)
    class(cmd_histogram_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_tag, pn_args, pn_arg1, pn_arg2, pn_arg3
    character(*), parameter :: e_illegal_use = &
      "illegal usage of 'histogram': insufficient number of arguments"
    pn_tag => parse_node_get_sub_ptr (cmd%pn, 2)
    pn_args => parse_node_get_next_ptr (pn_tag)
    if (associated (pn_args)) then
      pn_arg1 => parse_node_get_sub_ptr (pn_args)
      if (.not. associated (pn_arg1)) call msg_fatal (e_illegal_use)
      pn_arg2 => parse_node_get_next_ptr (pn_arg1)
      if (.not. associated (pn_arg2)) call msg_fatal (e_illegal_use)
      pn_arg3 => parse_node_get_next_ptr (pn_arg2)
      cmd%pn_opt => parse_node_get_next_ptr (pn_args)
```

```

end if
call cmd%compile_options (global)
select case (char (parse_node_get_rule_key (pn_tag)))
case ("analysis_id")
    cmd%id = parse_node_get_string (pn_tag)
case default
    call msg_bug ("histogram: name expression not implemented (yet)")
end select
cmd%pn_lower_bound => pn_arg1
cmd%pn_upper_bound => pn_arg2
cmd%pn_bin_width => pn_arg3
end subroutine cmd_histogram_compile

```

Command execution. This declares the histogram and allocates it in the analysis store.

```

⟨Commands: cmd histogram: TBP⟩+≡
    procedure :: execute => cmd_histogram_execute

⟨Commands: procedures⟩+≡
    subroutine cmd_histogram_execute (cmd, global)
        class(cmd_histogram_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(var_list_t), pointer :: var_list
        real(default) :: lower_bound, upper_bound, bin_width
        integer :: bin_number
        logical :: bin_width_is_used, normalize_bins
        type(string_t) :: obs_label, obs_unit
        type(graph_options_t) :: graph_options
        type(drawing_options_t) :: drawing_options

        var_list => cmd%local%get_var_list_ptr ()
        lower_bound = eval_real (cmd%pn_lower_bound, var_list)
        upper_bound = eval_real (cmd%pn_upper_bound, var_list)
        if (associated (cmd%pn_bin_width)) then
            bin_width = eval_real (cmd%pn_bin_width, var_list)
            bin_width_is_used = .true.
        else if (var_list%is_known (var_str ("n_bins"))) then
            bin_number = &
                var_list%get_ival (var_str ("n_bins"))
            bin_width_is_used = .false.
        else
            call msg_error ("Cmd '" // char (cmd%id) // &
                "' : neither bin width nor number is defined")
        end if
        normalize_bins = &
            var_list%get_lval (var_str ("?normalize_bins"))
        obs_label = &
            var_list%get_sval (var_str ("$obs_label"))
        obs_unit = &
            var_list%get_sval (var_str ("$obs_unit"))

        call graph_options_init (graph_options)
        call set_graph_options (graph_options, var_list)
        call drawing_options_init_histogram (drawing_options)
    end subroutine cmd_histogram_execute

```



```

call set_drawing_options (drawing_options, var_list)

if (bin_width_is_used) then
  call analysis_init_histogram &
    (cmd%id, lower_bound, upper_bound, bin_width, &
     normalize_bins, &
     obs_label, obs_unit, &
     graph_options, drawing_options)
else
  call analysis_init_histogram &
    (cmd%id, lower_bound, upper_bound, bin_number, &
     normalize_bins, &
     obs_label, obs_unit, &
     graph_options, drawing_options)
end if
end subroutine cmd_histogram_execute

```

Set the graph options from a variable list.

(Commands: procedures)+≡

```

subroutine set_graph_options (gro, var_list)
  type(graph_options_t), intent(inout) :: gro
  type(var_list_t), intent(in) :: var_list
  call graph_options_set (gro, title = &
    var_list%get_sval (var_str ("%title")))
  call graph_options_set (gro, description = &
    var_list%get_sval (var_str ("%description")))
  call graph_options_set (gro, x_label = &
    var_list%get_sval (var_str ("%x_label")))
  call graph_options_set (gro, y_label = &
    var_list%get_sval (var_str ("%y_label")))
  call graph_options_set (gro, width_mm = &
    var_list%get_ival (var_str ("graph_width_mm")))
  call graph_options_set (gro, height_mm = &
    var_list%get_ival (var_str ("graph_height_mm")))
  call graph_options_set (gro, x_log = &
    var_list%get_lval (var_str ("%x_log")))
  call graph_options_set (gro, y_log = &
    var_list%get_lval (var_str ("%y_log")))
  if (var_list%is_known (var_str ("x_min"))) &
    call graph_options_set (gro, x_min = &
      var_list%get_rval (var_str ("x_min")))
  if (var_list%is_known (var_str ("x_max"))) &
    call graph_options_set (gro, x_max = &
      var_list%get_rval (var_str ("x_max")))
  if (var_list%is_known (var_str ("y_min"))) &
    call graph_options_set (gro, y_min = &
      var_list%get_rval (var_str ("y_min")))
  if (var_list%is_known (var_str ("y_max"))) &
    call graph_options_set (gro, y_max = &
      var_list%get_rval (var_str ("y_max")))
  call graph_options_set (gro, gmlcode_bg = &
    var_list%get_sval (var_str ("%gmlcode_bg")))
  call graph_options_set (gro, gmlcode_fg = &

```

```

        var_list%get_sval (var_str ("sgmlcode_fg"))
    end subroutine set_graph_options

```

Set the drawing options from a variable list.

(Commands: procedures)+≡

```

subroutine set_drawing_options (dro, var_list)
    type(drawing_options_t), intent(inout) :: dro
    type(var_list_t), intent(in) :: var_list
    if (var_list%is_known (var_str ("?draw_histogram"))) then
        if (var_list%get_lval (var_str ("?draw_histogram"))) then
            call drawing_options_set (dro, with_hbars = .true.)
        else
            call drawing_options_set (dro, with_hbars = .false., &
                with_base = .false., fill = .false., piecewise = .false.)
        end if
    end if
    if (var_list%is_known (var_str ("?draw_base"))) then
        if (var_list%get_lval (var_str ("?draw_base"))) then
            call drawing_options_set (dro, with_base = .true.)
        else
            call drawing_options_set (dro, with_base = .false., fill = .false.)
        end if
    end if
    if (var_list%is_known (var_str ("?draw_piecewise"))) then
        if (var_list%get_lval (var_str ("?draw_piecewise"))) then
            call drawing_options_set (dro, piecewise = .true.)
        else
            call drawing_options_set (dro, piecewise = .false.)
        end if
    end if
    if (var_list%is_known (var_str ("?fill_curve"))) then
        if (var_list%get_lval (var_str ("?fill_curve"))) then
            call drawing_options_set (dro, fill = .true., with_base = .true.)
        else
            call drawing_options_set (dro, fill = .false.)
        end if
    end if
    if (var_list%is_known (var_str ("?draw_curve"))) then
        if (var_list%get_lval (var_str ("?draw_curve"))) then
            call drawing_options_set (dro, draw = .true.)
        else
            call drawing_options_set (dro, draw = .false.)
        end if
    end if
    if (var_list%is_known (var_str ("?draw_errors"))) then
        if (var_list%get_lval (var_str ("?draw_errors"))) then
            call drawing_options_set (dro, err = .true.)
        else
            call drawing_options_set (dro, err = .false.)
        end if
    end if
    if (var_list%is_known (var_str ("?draw_symbols"))) then
        if (var_list%get_lval (var_str ("?draw_symbols"))) then
            call drawing_options_set (dro, symbols = .true.)
        end if
    end if
end subroutine

```

```

else
  call drawing_options_set (dro, symbols = .false.)
end if
end if
if (var_list%is_known (var_str (" $fill_options"))) then
  call drawing_options_set (dro, fill_options = &
    var_list%get_sval (var_str (" $fill_options")))
end if
if (var_list%is_known (var_str (" $draw_options"))) then
  call drawing_options_set (dro, draw_options = &
    var_list%get_sval (var_str (" $draw_options")))
end if
if (var_list%is_known (var_str (" $err_options"))) then
  call drawing_options_set (dro, err_options = &
    var_list%get_sval (var_str (" $err_options")))
end if
if (var_list%is_known (var_str (" $symbol"))) then
  call drawing_options_set (dro, symbol = &
    var_list%get_sval (var_str (" $symbol")))
end if
if (var_list%is_known (var_str (" $gmlcode_bg"))) then
  call drawing_options_set (dro, gmlcode_bg = &
    var_list%get_sval (var_str (" $gmlcode_bg")))
end if
if (var_list%is_known (var_str (" $gmlcode_fg"))) then
  call drawing_options_set (dro, gmlcode_fg = &
    var_list%get_sval (var_str (" $gmlcode_fg")))
end if
end subroutine set_drawing_options

```

Plots

Declare a plot. No mandatory arguments, just options.

```

<Commands: types>+≡
  type, extends (command_t) :: cmd_plot_t
  private
  type(string_t) :: id
  contains
  <Commands: cmd plot: TBP>
end type cmd_plot_t

```

Output. Just print the ID.

```

<Commands: cmd plot: TBP>≡
  procedure :: write => cmd_plot_write

<Commands: procedures>+≡
  subroutine cmd_plot_write (cmd, unit, indent)
    class(cmd_plot_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,A)") "plot: ", char (cmd%id)
  end subroutine cmd_plot_write

```

```
end subroutine cmd_plot_write
```

Compile. Record the plot ID and initialize lower, upper bound and bin width.

```
<Commands: cmd plot: TBP>+≡
  procedure :: compile => cmd_plot_compile

<Commands: procedures>+≡
  subroutine cmd_plot_compile (cmd, global)
    class(cmd_plot_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_tag
    pn_tag => parse_node_get_sub_ptr (cmd%pn, 2)
    cmd%pn_opt => parse_node_get_next_ptr (pn_tag)
    call cmd%init (pn_tag, global)
  end subroutine cmd_plot_compile
```

This init routine is separated because it is reused below for graph initialization.

```
<Commands: cmd plot: TBP>+≡
  procedure :: init => cmd_plot_init

<Commands: procedures>+≡
  subroutine cmd_plot_init (plot, pn_tag, global)
    class(cmd_plot_t), intent(inout) :: plot
    type(parse_node_t), intent(in), pointer :: pn_tag
    type(rt_data_t), intent(inout), target :: global
    call plot%compile_options (global)
    select case (char (parse_node_get_rule_key (pn_tag)))
    case ("analysis_id")
      plot%id = parse_node_get_string (pn_tag)
    case default
      call msg_bug ("plot: name expression not implemented (yet)")
    end select
  end subroutine cmd_plot_init
```

Command execution. This declares the plot and allocates it in the analysis store.

```
<Commands: cmd plot: TBP>+≡
  procedure :: execute => cmd_plot_execute

<Commands: procedures>+≡
  subroutine cmd_plot_execute (cmd, global)
    class(cmd_plot_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(graph_options_t) :: graph_options
    type(drawing_options_t) :: drawing_options

    var_list => cmd%local%get_var_list_ptr ()
    call graph_options_init (graph_options)
    call set_graph_options (graph_options, var_list)
    call drawing_options_init_plot (drawing_options)
    call set_drawing_options (drawing_options, var_list)
```

```

    call analysis_init_plot (cmd%id, graph_options, drawing_options)
end subroutine cmd_plot_execute

```

Graphs

Declare a graph. The graph is defined in terms of its contents. Both the graph and its contents may carry options.

The graph object contains its own ID as well as the IDs of its elements. For the elements, we reuse the `cmd_plot_t` defined above.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_graph_t
  private
    type(string_t) :: id
    integer :: n_elements = 0
    type(cmd_plot_t), dimension(:), allocatable :: el
    type(string_t), dimension(:), allocatable :: element_id
  contains
    ⟨Commands: cmd graph: TBP⟩
  end type cmd_graph_t

```

Output. Just print the ID.

```

⟨Commands: cmd graph: TBP⟩≡
  procedure :: write => cmd_graph_write

⟨Commands: procedures⟩+≡
  subroutine cmd_graph_write (cmd, unit, indent)
    class(cmd_graph_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,A,A,I0,A)") "graph: ", char (cmd%id), &
      " (", cmd%n_elements, " entries)"
  end subroutine cmd_graph_write

```

Compile. Record the graph ID and initialize lower, upper bound and bin width. For compiling the graph element syntax, we use part of the `cmd_plot_t` compiler.

Note: currently, we do not respect options, therefore just IDs on the RHS.

```

⟨Commands: cmd graph: TBP⟩+≡
  procedure :: compile => cmd_graph_compile

⟨Commands: procedures⟩+≡
  subroutine cmd_graph_compile (cmd, global)
    class(cmd_graph_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_term, pn_tag, pn_def, pn_app
    integer :: i

    pn_term => parse_node_get_sub_ptr (cmd%pn, 2)
    pn_tag => parse_node_get_sub_ptr (pn_term)
    cmd%pn_opt => parse_node_get_next_ptr (pn_tag)

```

```

call cmd%compile_options (global)
select case (char (parse_node_get_rule_key (pn_tag)))
case ("analysis_id")
    cmd%id = parse_node_get_string (pn_tag)
case default
    call msg_bug ("graph: name expression not implemented (yet)")
end select
pn_def => parse_node_get_next_ptr (pn_term, 2)
cmd%n_elements = parse_node_get_n_sub (pn_def)
allocate (cmd%element_id (cmd%n_elements))
allocate (cmd%el (cmd%n_elements))
pn_term => parse_node_get_sub_ptr (pn_def)
pn_tag => parse_node_get_sub_ptr (pn_term)
cmd%el(1)%pn_opt => parse_node_get_next_ptr (pn_tag)
call cmd%el(1)%init (pn_tag, global)
cmd%element_id(1) = parse_node_get_string (pn_tag)
pn_app => parse_node_get_next_ptr (pn_term)
do i = 2, cmd%n_elements
    pn_term => parse_node_get_sub_ptr (pn_app, 2)
    pn_tag => parse_node_get_sub_ptr (pn_term)
    cmd%el(i)%pn_opt => parse_node_get_next_ptr (pn_tag)
    call cmd%el(i)%init (pn_tag, global)
    cmd%element_id(i) = parse_node_get_string (pn_tag)
    pn_app => parse_node_get_next_ptr (pn_app)
end do

end subroutine cmd_graph_compile

```

Command execution. This declares the graph, allocates it in the analysis store, and copies the graph elements.

For the graph, we set graph and default drawing options. For the elements, we reset individual drawing options.

This accesses internals of the contained elements of type `cmd_plot_t`, see above. We might disentangle such an interdependency when this code is rewritten using proper type extension.

<Commands: cmd_graph: TBP>+≡

```

procedure :: execute => cmd_graph_execute

```

<Commands: procedures>+≡

```

subroutine cmd_graph_execute (cmd, global)
    class(cmd_graph_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(graph_options_t) :: graph_options
    type(drawing_options_t) :: drawing_options
    integer :: i, type

    var_list => cmd%local%get_var_list_ptr ()
    call graph_options_init (graph_options)
    call set_graph_options (graph_options, var_list)
    call analysis_init_graph (cmd%id, cmd%n_elements, graph_options)

    do i = 1, cmd%n_elements

```

```

        if (associated (cmd%el(i)%options)) then
            call cmd%el(i)%options%execute (cmd%el(i)%local)
        end if
        type = analysis_store_get_object_type (cmd%element_id(i))
        select case (type)
        case (AN_HISTOGRAM)
            call drawing_options_init_histogram (drawing_options)
        case (AN_PLOT)
            call drawing_options_init_plot (drawing_options)
        end select
        call set_drawing_options (drawing_options, var_list)
        if (associated (cmd%el(i)%options)) then
            call set_drawing_options (drawing_options, cmd%el(i)%local%var_list)
        end if
        call analysis_fill_graph (cmd%id, i, cmd%element_id(i), drawing_options)
    end do
end subroutine cmd_graph_execute

```

Analysis

Hold the analysis ID either as a string or as an expression:

```

⟨Commands: types⟩+≡
    type :: analysis_id_t
    type(string_t) :: tag
    type(parse_node_t), pointer :: pn_sexpr => null ()
end type analysis_id_t

```

Define the analysis expression. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the analysis expression is used.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_analysis_t
    private
    type(parse_node_t), pointer :: pn_lexpr => null ()
    contains
    ⟨Commands: cmd analysis: TBP⟩
end type cmd_analysis_t

```

Output. Print just a message that analysis has been defined.

```

⟨Commands: cmd analysis: TBP⟩≡
    procedure :: write => cmd_analysis_write

⟨Commands: procedures⟩+≡
    subroutine cmd_analysis_write (cmd, unit, indent)
        class(cmd_analysis_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A)") "analysis: [defined]"
    end subroutine cmd_analysis_write

```

Compile. Simply store the parse (sub)tree.

```
<Commands: cmd analysis: TBP>+≡
  procedure :: compile => cmd_analysis_compile

<Commands: procedures>+≡
  subroutine cmd_analysis_compile (cmd, global)
    class(cmd_analysis_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%pn_lexpr => parse_node_get_sub_ptr (cmd%pn, 3)
  end subroutine cmd_analysis_compile
```

Instead of evaluating the cut expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
<Commands: cmd analysis: TBP>+≡
  procedure :: execute => cmd_analysis_execute

<Commands: procedures>+≡
  subroutine cmd_analysis_execute (cmd, global)
    class(cmd_analysis_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    global%pn%analysis_lexpr => cmd%pn_lexpr
  end subroutine cmd_analysis_execute
```

Write histograms and plots

The data type encapsulating the command:

```
<Commands: types>+≡
  type, extends (command_t) :: cmd_write_analysis_t
    private
    type(analysis_id_t), dimension(:), allocatable :: id
    type(string_t), dimension(:), allocatable :: tag
  contains
    <Commands: cmd write analysis: TBP>
  end type cmd_write_analysis_t
```

Output. Just the keyword.

```
<Commands: cmd write analysis: TBP>≡
  procedure :: write => cmd_write_analysis_write

<Commands: procedures>+≡
  subroutine cmd_write_analysis_write (cmd, unit, indent)
    class(cmd_write_analysis_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "write_analysis"
  end subroutine cmd_write_analysis_write
```

Compile.

```
<Commands: cmd write analysis: TBP>+≡
  procedure :: compile => cmd_write_analysis_compile
```



```

⟨Commands: procedures⟩+≡
subroutine cmd_write_analysis_compile (cmd, global)
  class(cmd_write_analysis_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_clause, pn_args, pn_id
  integer :: n, i
  pn_clause => parse_node_get_sub_ptr (cmd%pn)
  pn_args => parse_node_get_sub_ptr (pn_clause, 2)
  cmd%pn_opt => parse_node_get_next_ptr (pn_clause)
  call cmd%compile_options (global)
  if (associated (pn_args)) then
    n = parse_node_get_n_sub (pn_args)
    allocate (cmd%id (n))
    do i = 1, n
      pn_id => parse_node_get_sub_ptr (pn_args, i)
      if (char (parse_node_get_rule_key (pn_id)) == "analysis_id") then
        cmd%id(i)%tag = parse_node_get_string (pn_id)
      else
        cmd%id(i)%pn_sexpr => pn_id
      end if
    end do
  else
    allocate (cmd%id (0))
  end if
end subroutine cmd_write_analysis_compile

```

The output format for real data values:

```

⟨Commands: parameters⟩+≡
character(*), parameter, public :: &
  DEFAULT_ANALYSIS_FILENAME = "whizard_analysis.dat"
character(len=1), dimension(2), parameter, public :: &
  FORBIDDEN_ENDINGS1 = [ "o", "a" ]
character(len=2), dimension(5), parameter, public :: &
  FORBIDDEN_ENDINGS2 = [ "mp", "ps", "vg", "lo", "la" ]
character(len=3), dimension(16), parameter, public :: &
  FORBIDDEN_ENDINGS3 = [ "aux", "dvi", "evt", "evx", "f03", "f90", &
    "f95", "log", "ltp", "mpx", "olc", "olp", "pdf", "phs", "sin", "tex" ]

```

As this contains a lot of similar code to `cmd_compile_analysis_execute` we outsource the main code to a subroutine.

```

⟨Commands: cmd write analysis: TBP⟩+≡
  procedure :: execute => cmd_write_analysis_execute

⟨Commands: procedures⟩+≡
subroutine cmd_write_analysis_execute (cmd, global)
  class(cmd_write_analysis_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  var_list => cmd%local%get_var_list_ptr ()
  call write_analysis_wrap (var_list, global%out_files, &
    cmd%id, tag = cmd%tag)
end subroutine cmd_write_analysis_execute

```

If the `data_file` optional argument is present, this is called from `cmd_compile_analysis_execute`, which needs the file name for further processing, and requires the default format. For the moment, parameters and macros for custom data processing are disabled.

(Commands: procedures)+≡

```

subroutine write_analysis_wrap (var_list, out_files, id, tag, data_file)
  type(var_list_t), intent(inout), target :: var_list
  type(file_list_t), intent(inout), target :: out_files
  type(analysis_id_t), dimension(:), intent(in), target :: id
  type(string_t), dimension(:), allocatable, intent(out) :: tag
  type(string_t), intent(out), optional :: data_file
  type(string_t) :: defaultfile, file
  integer :: i
  logical :: keep_open !, custom, header, columns
  type(string_t) :: extension !, comment_prefix, separator
!!! JRR: WK please check (#542)
!   integer :: type
!   type(ifile_t) :: ifile
  logical :: one_file !, has_writer
!   type(analysis_iterator_t) :: iterator
!   type(rt_data_t), target :: sandbox
!   type(command_list_t) :: writer
  defaultfile = var_list%get_sval (var_str ("out_file"))
  if (present (data_file)) then
    if (defaultfile == "" .or. defaultfile == ".") then
      defaultfile = DEFAULT_ANALYSIS_FILENAME
    else
      if (scan (".", defaultfile) > 0) then
        call split (defaultfile, extension, ".", back=.true.)
        if (any (lower_case (char(extension)) == FORBIDDEN_ENDINGS1) .or. &
            any (lower_case (char(extension)) == FORBIDDEN_ENDINGS2) .or. &
            any (lower_case (char(extension)) == FORBIDDEN_ENDINGS3)) &
            call msg_fatal ("The ending " // char(extension) // &
                           " is internal and not allowed as data file.")
        if (extension /= "") then
          if (defaultfile /= "") then
            defaultfile = defaultfile // "." // extension
          else
            defaultfile = "whizard_analysis." // extension
          end if
        else
          defaultfile = defaultfile // ".dat"
        endif
      else
        defaultfile = defaultfile // ".dat"
      end if
    end if
    data_file = defaultfile
  end if
  one_file = defaultfile /= ""
  if (one_file) then
    file = defaultfile
    keep_open = file_list_is_open (out_files, file, &
                                   action = "write")
  end if
end subroutine

```

```

        if (keep_open) then
            if (present (data_file)) then
                call msg_fatal ("Compiling analysis: File '" &
                    // char (data_file) &
                    // "' can't be used, it is already open.")
            else
                call msg_message ("Appending analysis data to file '" &
                    // char (file) // "'")
            end if
        else
            call file_list_open (out_files, file, &
                action = "write", status = "replace", position = "asis")
            call msg_message ("Writing analysis data to file '" &
                // char (file) // "'")
        end if
    end if
end if

!!! JRR: WK please check. Custom data output. Ticket #542
!     if (present (data_file)) then
!         custom = .false.
!     else
!         custom = var_list%get_lval (&
!             var_str ("?out_custom"))
!     end if
!     comment_prefix = var_list%get_sval (&
!         var_str ("?$out_comment"))
!     header = var_list%get_lval (&
!         var_str ("?out_header"))
!     write_yerr = var_list%get_lval (&
!         var_str ("?out_yerr"))
!     write_xerr = var_list%get_lval (&
!         var_str ("?out_xerr"))

    call get_analysis_tags (tag, id, var_list)
    do i = 1, size (tag)
        call file_list_write_analysis &
            (out_files, file, tag(i))
    end do
    if (one_file .and. .not. keep_open) then
        call file_list_close (out_files, file)
    end if

contains

subroutine get_analysis_tags (analysis_tag, id, var_list)
    type(string_t), dimension(:), intent(out), allocatable :: analysis_tag
    type(analysis_id_t), dimension(:), intent(in) :: id
    type(var_list_t), intent(in), target :: var_list
    if (size (id) /= 0) then
        allocate (analysis_tag (size (id)))
        do i = 1, size (id)
            if (associated (id(i)%pn_sexpr)) then
                analysis_tag(i) = eval_string (id(i)%pn_sexpr, var_list)
            else

```

```

        analysis_tag(i) = id(i)%tag
    end if
end do
else
    call analysis_store_get_ids (tag)
end if
end subroutine get_analysis_tags

end subroutine write_analysis_wrap

```

Compile analysis results

This command writes files in a form suitable for GAMELAN and executes the appropriate commands to compile them. The first part is identical to `cmd_write_analysis`.

```

<Commands: types>+≡
type, extends (command_t) :: cmd_compile_analysis_t
private
type(analysis_id_t), dimension(:), allocatable :: id
type(string_t), dimension(:), allocatable :: tag
contains
    <Commands: cmd compile analysis: TBP>
end type cmd_compile_analysis_t

```

Output. Just the keyword.

```

<Commands: cmd compile analysis: TBP>≡
procedure :: write => cmd_compile_analysis_write

<Commands: procedures>+≡
subroutine cmd_compile_analysis_write (cmd, unit, indent)
class(cmd_compile_analysis_t), intent(in) :: cmd
integer, intent(in), optional :: unit, indent
integer :: u
u = given_output_unit (unit); if (u < 0) return
call write_indent (u, indent)
write (u, "(1x,A)") "compile_analysis"
end subroutine cmd_compile_analysis_write

```

Compile.

```

<Commands: cmd compile analysis: TBP>+≡
procedure :: compile => cmd_compile_analysis_compile

<Commands: procedures>+≡
subroutine cmd_compile_analysis_compile (cmd, global)
class(cmd_compile_analysis_t), intent(inout) :: cmd
type(rt_data_t), intent(inout), target :: global
type(parse_node_t), pointer :: pn_clause, pn_args, pn_id
integer :: n, i
pn_clause => parse_node_get_sub_ptr (cmd%pn)
pn_args => parse_node_get_sub_ptr (pn_clause, 2)
cmd%pn_opt => parse_node_get_next_ptr (pn_clause)
call cmd%compile_options (global)

```

```

if (associated (pn_args)) then
  n = parse_node_get_n_sub (pn_args)
  allocate (cmd%id (n))
  do i = 1, n
    pn_id => parse_node_get_sub_ptr (pn_args, i)
    if (char (parse_node_get_rule_key (pn_id)) == "analysis_id") then
      cmd%id(i)%tag = parse_node_get_string (pn_id)
    else
      cmd%id(i)%pn_sexpr => pn_id
    end if
  end do
else
  allocate (cmd%id (0))
end if
end subroutine cmd_compile_analysis_compile

```

First write the analysis data to file, then write a GAMELAN driver and produce MetaPost and T_EX output.

```

<Commands: cmd compile analysis: TBP>+≡
  procedure :: execute => cmd_compile_analysis_execute

<Commands: procedures>+≡
  subroutine cmd_compile_analysis_execute (cmd, global)
    class(cmd_compile_analysis_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(string_t) :: file, basename, extension, driver_file, &
      makefile
    integer :: u_driver, u_makefile
    logical :: has_gmlcode, only_file
    var_list => cmd%local%get_var_list_ptr ()
    call write_analysis_wrap (var_list, &
      global%out_files, cmd%id, tag = cmd%tag, &
      data_file = file)
    basename = file
    if (scan (".", basename) > 0) then
      call split (basename, extension, ".", back=.true.)
    else
      extension = ""
    end if
    driver_file = basename // ".tex"
    makefile = basename // "_ana.makefile"
    u_driver = free_unit ()
    open (unit=u_driver, file=char(driver_file), &
      action="write", status="replace")
    if (allocated (cmd%tag)) then
      call analysis_write_driver (file, cmd%tag, unit=u_driver)
      has_gmlcode = analysis_has_plots (cmd%tag)
    else
      call analysis_write_driver (file, unit=u_driver)
      has_gmlcode = analysis_has_plots ()
    end if
    close (u_driver)
    u_makefile = free_unit ()
  end subroutine

```

```

open (unit=u_makefile, file=char(makefile), &
      action="write", status="replace")
call analysis_write_makefile (basename, u_makefile, &
      has_gmlcode, global%os_data)
close (u_makefile)
call msg_message ("Compiling analysis results display in '" &
      // char (driver_file) // "'")
call msg_message ("Providing analysis steering makefile '" &
      // char (makefile) // "'")
only_file = global%var_list%get_lval &
      (var_str ("?analysis_file_only"))
if (.not. only_file) call analysis_compile_tex &
      (basename, has_gmlcode, global%os_data)
end subroutine cmd_compile_analysis_execute

```

30.1.4 User-controlled output to data files

Open file (output)

Open a file for output.

```

<Commands: types>+≡
  type, extends (command_t) :: cmd_open_out_t
    private
    type(parse_node_t), pointer :: file_expr => null ()
  contains
    <Commands: cmd open out: TBP>
  end type cmd_open_out_t

```

Finalizer for the embedded eval tree.

```

<Commands: procedures>+≡
  subroutine cmd_open_out_final (object)
    class(cmd_open_out_t), intent(inout) :: object
  end subroutine cmd_open_out_final

```

Output (trivial here).

```

<Commands: cmd open out: TBP>≡
  procedure :: write => cmd_open_out_write

<Commands: procedures>+≡
  subroutine cmd_open_out_write (cmd, unit, indent)
    class(cmd_open_out_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)", advance="no") "open_out: <filename>"
  end subroutine cmd_open_out_write

```

Compile: create an eval tree for the filename expression.

```

<Commands: cmd open out: TBP>+≡
  procedure :: compile => cmd_open_out_compile

```

```

⟨Commands: procedures⟩+≡
  subroutine cmd_open_out_compile (cmd, global)
    class(cmd_open_out_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    cmd%file_expr => parse_node_get_sub_ptr (cmd%pn, 2)
    if (associated (cmd%file_expr)) then
      cmd%pn_opt => parse_node_get_next_ptr (cmd%file_expr)
    end if
    call cmd%compile_options (global)
  end subroutine cmd_open_out_compile

```

Execute: append the file to the global list of open files.

```

⟨Commands: cmd open out: TBP⟩+≡
  procedure :: execute => cmd_open_out_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_open_out_execute (cmd, global)
    class(cmd_open_out_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(eval_tree_t) :: file_expr
    type(string_t) :: file
    var_list => cmd%local%get_var_list_ptr ()
    call file_expr%init_sexpr (cmd%file_expr, var_list)
    call file_expr%evaluate ()
    if (file_expr%is_known ()) then
      file = file_expr%get_string ()
      call file_list_open (global%out_files, file, &
        action = "write", status = "replace", position = "asis")
    else
      call msg_fatal ("open_out: file name argument evaluates to unknown")
    end if
    call file_expr%final ()
  end subroutine cmd_open_out_execute

```

Open file (output)

Close an output file. Except for the `execute` method, everything is analogous to the open command, so we can just inherit.

```

⟨Commands: types⟩+≡
  type, extends (cmd_open_out_t) :: cmd_close_out_t
  private
  contains
  ⟨Commands: cmd close out: TBP⟩
  end type cmd_close_out_t

```

Execute: remove the file from the global list of output files.

```

⟨Commands: cmd close out: TBP⟩≡
  procedure :: execute => cmd_close_out_execute

```

```

⟨Commands: procedures⟩+≡
  subroutine cmd_close_out_execute (cmd, global)
    class(cmd_close_out_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(eval_tree_t) :: file_expr
    type(string_t) :: file
    var_list => cmd%local%var_list
    call file_expr%init_sexpr (cmd%file_expr, var_list)
    call file_expr%evaluate ()
    if (file_expr%is_known ()) then
      file = file_expr%get_string ()
      call file_list_close (global%out_files, file)
    else
      call msg_fatal ("close_out: file name argument evaluates to unknown")
    end if
    call file_expr%final ()
  end subroutine cmd_close_out_execute

```

30.1.5 Print custom-formatted values

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_printf_t
  private
    type(parse_node_t), pointer :: sexpr => null ()
    type(parse_node_t), pointer :: sprintf_fun => null ()
    type(parse_node_t), pointer :: sprintf_clause => null ()
    type(parse_node_t), pointer :: sprintf => null ()
  contains
    ⟨Commands: cmd printf: TBP⟩
  end type cmd_printf_t

```

Finalize.

```

⟨Commands: cmd printf: TBP⟩≡
  procedure :: final => cmd_printf_final

⟨Commands: procedures⟩+≡
  subroutine cmd_printf_final (cmd)
    class(cmd_printf_t), intent(inout) :: cmd
    call parse_node_final (cmd%sexpr, recursive = .false.)
    deallocate (cmd%sexpr)
    call parse_node_final (cmd%sprintf_fun, recursive = .false.)
    deallocate (cmd%sprintf_fun)
    call parse_node_final (cmd%sprintf_clause, recursive = .false.)
    deallocate (cmd%sprintf_clause)
    call parse_node_final (cmd%sprintf, recursive = .false.)
    deallocate (cmd%sprintf)
  end subroutine cmd_printf_final

```

Output. Do not print the parse tree, since this may get cluttered. Just a message that cuts have been defined.

```

⟨Commands: cmd printf: TBP⟩+≡

```



```

procedure :: write => cmd_printf_write
<Commands: procedures>+≡
subroutine cmd_printf_write (cmd, unit, indent)
  class(cmd_printf_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  write (u, "(1x,A)") "printf:"
end subroutine cmd_printf_write

```

Compile. We create a fake parse node (subtree) with a `sprintf` command with identical arguments which can then be handled by the corresponding evaluation procedure.

```

<Commands: cmd printf: TBP>+≡
procedure :: compile => cmd_printf_compile
<Commands: procedures>+≡
subroutine cmd_printf_compile (cmd, global)
  class(cmd_printf_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_cmd, pn_clause, pn_args, pn_format
  pn_cmd => parse_node_get_sub_ptr (cmd%pn)
  pn_clause => parse_node_get_sub_ptr (pn_cmd)
  pn_format => parse_node_get_sub_ptr (pn_clause, 2)
  pn_args => parse_node_get_next_ptr (pn_clause)
  cmd%pn_opt => parse_node_get_next_ptr (pn_cmd)
  call cmd%compile_options (global)
  allocate (cmd%sexpr)
  call parse_node_create_branch (cmd%sexpr, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("sexpr")))
  allocate (cmd%sprintf_fun)
  call parse_node_create_branch (cmd%sprintf_fun, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("sprintf_fun")))
  allocate (cmd%sprintf_clause)
  call parse_node_create_branch (cmd%sprintf_clause, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("sprintf_clause")))
  allocate (cmd%sprintf)
  call parse_node_create_key (cmd%sprintf, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("sprintf")))
  call parse_node_append_sub (cmd%sprintf_clause, cmd%sprintf)
  call parse_node_append_sub (cmd%sprintf_clause, pn_format)
  call parse_node_freeze_branch (cmd%sprintf_clause)
  call parse_node_append_sub (cmd%sprintf_fun, cmd%sprintf_clause)
  if (associated (pn_args)) then
    call parse_node_append_sub (cmd%sprintf_fun, pn_args)
  end if
  call parse_node_freeze_branch (cmd%sprintf_fun)
  call parse_node_append_sub (cmd%sexpr, cmd%sprintf_fun)
  call parse_node_freeze_branch (cmd%sexpr)
end subroutine cmd_printf_compile

```

Execute. Evaluate the string (pretending this is a `sprintf` expression) and print it.

```

⟨Commands: cmd printf: TBP⟩+≡
  procedure :: execute => cmd_printf_execute

⟨Commands: procedures⟩+≡
  subroutine cmd_printf_execute (cmd, global)
    class(cmd_printf_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    type(string_t) :: string, file
    type(eval_tree_t) :: sprintf_expr
    logical :: advance
    var_list => cmd%local%get_var_list_ptr ()
    advance = var_list%get_lval (&
      var_str ("?out_advance"))
    file = var_list%get_sval (&
      var_str ("out_file"))
    call sprintf_expr%init_sexpr (cmd%sexpr, var_list)
    call sprintf_expr%evaluate ()
    if (sprintf_expr%is_known ()) then
      string = sprintf_expr%get_string ()
      if (len (file) == 0) then
        call msg_result (char (string))
      else
        call file_list_write (global%out_files, file, string, advance)
      end if
    end if
  end subroutine cmd_printf_execute

```

Record data

The expression syntax already contains a `record` keyword; this evaluates to a logical which is always true, but it has the side-effect of recording data into analysis objects. Here we define a command as an interface to this construct.

```

⟨Commands: types⟩+≡
  type, extends (command_t) :: cmd_record_t
  private
  type(parse_node_t), pointer :: pn_lexpr => null ()
  contains
  ⟨Commands: cmd record: TBP⟩
  end type cmd_record_t

```

Output. With the compile hack below, there is nothing of interest to print here.

```

⟨Commands: cmd record: TBP⟩≡
  procedure :: write => cmd_record_write

⟨Commands: procedures⟩+≡
  subroutine cmd_record_write (cmd, unit, indent)
    class(cmd_record_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u

```

```

    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)") "record"
end subroutine cmd_record_write

```

Compile. This is a hack which transforms the `record` command into a `record` expression, which we handle in the `expressions` module.

```

⟨Commands: cmd record: TBP⟩+≡
    procedure :: compile => cmd_record_compile

⟨Commands: procedures⟩+≡
    subroutine cmd_record_compile (cmd, global)
        class(cmd_record_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(parse_node_t), pointer :: pn_lexpr, pn_lsinglet, pn_lterm, pn_record
        call parse_node_create_branch (pn_lexpr, &
            syntax_get_rule_ptr (syntax_cmd_list, var_str ("lexpr")))
        call parse_node_create_branch (pn_lsinglet, &
            syntax_get_rule_ptr (syntax_cmd_list, var_str ("lsinglet")))
        call parse_node_append_sub (pn_lexpr, pn_lsinglet)
        call parse_node_create_branch (pn_lterm, &
            syntax_get_rule_ptr (syntax_cmd_list, var_str ("lterm")))
        call parse_node_append_sub (pn_lsinglet, pn_lterm)
        pn_record => parse_node_get_sub_ptr (cmd%pn)
        call parse_node_append_sub (pn_lterm, pn_record)
        cmd%pn_lexpr => pn_lexpr
    end subroutine cmd_record_compile

```

Command execution. Again, transfer this to the embedded expression and just forget the logical result.

```

⟨Commands: cmd record: TBP⟩+≡
    procedure :: execute => cmd_record_execute

⟨Commands: procedures⟩+≡
    subroutine cmd_record_execute (cmd, global)
        class(cmd_record_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(var_list_t), pointer :: var_list
        logical :: lval
        var_list => global%get_var_list_ptr ()
        lval = eval_log (cmd%pn_lexpr, var_list)
    end subroutine cmd_record_execute

```

Unstable particles

Mark a particle as unstable. For each unstable particle, we store a number of decay channels and compute their respective BRs.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_unstable_t
        private
        integer :: n_proc = 0
        type(string_t), dimension(:), allocatable :: process_id

```

```

        type(parse_node_t), pointer :: pn_prt_in => null ()
contains
  <Commands: cmd unstable: TBP>≡
end type cmd_unstable_t

```

Output: we know the process IDs.

```

<Commands: cmd unstable: TBP>≡
  procedure :: write => cmd_unstable_write

<Commands: procedures>+≡
  subroutine cmd_unstable_write (cmd, unit, indent)
    class(cmd_unstable_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,1x,I0,1x,A)", advance="no") &
      "unstable:", 1, "("
    do i = 1, cmd%n_proc
      if (i > 1) write (u, "(A,1x)", advance="no") " ,"
      write (u, "(A)", advance="no") char (cmd%process_id(i))
    end do
    write (u, "(A)") ")"
  end subroutine cmd_unstable_write

```

Compile. Initiate an eval tree for the decaying particle and determine the decay channel process IDs.

```

<Commands: cmd unstable: TBP>+≡
  procedure :: compile => cmd_unstable_compile

<Commands: procedures>+≡
  subroutine cmd_unstable_compile (cmd, global)
    class(cmd_unstable_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_list, pn_proc
    integer :: i
    cmd%pn_prt_in => parse_node_get_sub_ptr (cmd%pn, 2)
    pn_list => parse_node_get_next_ptr (cmd%pn_prt_in)
    if (associated (pn_list)) then
      select case (char (parse_node_get_rule_key (pn_list)))
      case ("unstable_arg")
        cmd%n_proc = parse_node_get_n_sub (pn_list)
        cmd%pn_opt => parse_node_get_next_ptr (pn_list)
      case default
        cmd%n_proc = 0
        cmd%pn_opt => pn_list
        pn_list => null ()
      end select
    end if
    call cmd%compile_options (global)
    if (associated (pn_list)) then
      allocate (cmd%process_id (cmd%n_proc))
      pn_proc => parse_node_get_sub_ptr (pn_list)
      do i = 1, cmd%n_proc

```

```

        cmd%process_id(i) = parse_node_get_string (pn_proc)
        call cmd%local%process_stack%init_result_vars (cmd%process_id(i))
        pn_proc => parse_node_get_next_ptr (pn_proc)
    end do
else
    allocate (cmd%process_id (0))
end if
end subroutine cmd_unstable_compile

```

Command execution. Evaluate the decaying particle and mark the decays in the current model object.

(Commands: cmd unstable: TBP)+≡

```

    procedure :: execute => cmd_unstable_execute

```

(Commands: procedures)+≡

```

subroutine cmd_unstable_execute (cmd, global)
    class(cmd_unstable_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    logical :: auto_decays, auto_decays_radiative
    integer :: auto_decays_multiplicity
    logical :: isotropic_decay, diagonal_decay, polarized_decay
    integer :: decay_helicity
    type(pdg_array_t) :: pa_in
    integer :: pdg_in
    type(string_t) :: libname_cur, libname_dec
    type(string_t), dimension(:), allocatable :: auto_id, tmp_id
    integer :: n_proc_user
    integer :: i, u_tmp
    character(80) :: buffer
    var_list => cmd%local%get_var_list_ptr ()
    auto_decays = &
        var_list%get_lval (var_str ("?auto_decays"))
    if (auto_decays) then
        auto_decays_multiplicity = &
            var_list%get_ival (var_str ("auto_decays_multiplicity"))
        auto_decays_radiative = &
            var_list%get_lval (var_str ("?auto_decays_radiative"))
    end if
    isotropic_decay = &
        var_list%get_lval (var_str ("?isotropic_decay"))
    if (isotropic_decay) then
        diagonal_decay = .false.
        polarized_decay = .false.
    else
        diagonal_decay = &
            var_list%get_lval (var_str ("?diagonal_decay"))
        if (diagonal_decay) then
            polarized_decay = .false.
        else
            polarized_decay = &
                var_list%is_known (var_str ("decay_helicity"))
            if (polarized_decay) then
                decay_helicity = var_list%get_ival (var_str ("decay_helicity"))
            end if
        end if
    end if
end subroutine cmd_unstable_execute

```

```

        end if
    end if
end if
pa_in = eval_pdg_array (cmd%pn_prt_in, var_list)
if (pdg_array_get_length (pa_in) /= 1) &
    call msg_fatal ("Unstable: decaying particle must be unique")
pdg_in = pdg_array_get (pa_in, 1)
n_proc_user = cmd%n_proc
if (auto_decays) then
    call create_auto_decays (pdg_in, &
        auto_decays_multiplicity, auto_decays_radiative, &
        libname_dec, auto_id, cmd%local)
    allocate (tmp_id (cmd%n_proc + size (auto_id)))
    tmp_id(:cmd%n_proc) = cmd%process_id
    tmp_id(cmd%n_proc+1:) = auto_id
    call move_alloc (from = tmp_id, to = cmd%process_id)
    cmd%n_proc = size (cmd%process_id)
end if
libname_cur = cmd%local%prclib%get_name ()
do i = 1, cmd%n_proc
    if (i == n_proc_user + 1) then
        call cmd%local%update_prclib &
            (cmd%local%prclib_stack%get_library_ptr (libname_dec))
    end if
    if (.not. global%process_stack%exists (cmd%process_id(i))) then
        call var_list_set_log (var_list, &
            var_str ("?decay_rest_frame"), .false., is_known = .true.)
        call integrate_process (cmd%process_id(i), cmd%local, global)
        call global%process_stack%fill_result_vars (cmd%process_id(i))
    end if
end do
call cmd%local%update_prclib &
    (cmd%local%prclib_stack%get_library_ptr (libname_cur))
if (cmd%n_proc > 0) then
    if (polarized_decay) then
        call global%modify_particle (pdg_in, stable = .false., &
            decay = cmd%process_id, &
            isotropic_decay = .false., &
            diagonal_decay = .false., &
            decay_helicity = decay_helicity, &
            polarized = .false.)
    else
        call global%modify_particle (pdg_in, stable = .false., &
            decay = cmd%process_id, &
            isotropic_decay = isotropic_decay, &
            diagonal_decay = diagonal_decay, &
            polarized = .false.)
    end if
    u_tmp = free_unit ()
    open (u_tmp, status = "scratch", action = "readwrite")
    call show_unstable (global, pdg_in, u_tmp)
    rewind (u_tmp)
    do
        read (u_tmp, "(A)", end = 1) buffer

```

```

        write (msg_buffer, "(A)") trim (buffer)
        call msg_message ()
    end do
1    continue
    close (u_tmp)
else
    call err_unstable (global, pdg_in)
end if
end subroutine cmd_unstable_execute

```

Show data for the current unstable particle. This is called both by the `unstable` and by the `show` command.

(Commands: procedures)+≡

```

subroutine show_unstable (global, pdg, u)
    type(rt_data_t), intent(in), target :: global
    integer, intent(in) :: pdg, u
    type(flavor_t) :: flv
    type(string_t), dimension(:), allocatable :: decay
    real(default), dimension(:), allocatable :: br
    real(default) :: width
    type(process_t), pointer :: process
    type(process_component_def_t), pointer :: prc_def
    type(string_t), dimension(:), allocatable :: prt_out, prt_out_str
    integer :: i, j
    call flv%init (pdg, global%model)
    call flv%get_decays (decay)
    if (.not. allocated (decay)) return
    allocate (prt_out_str (size (decay)))
    allocate (br (size (decay)))
    do i = 1, size (br)
        process => global%process_stack%get_process_ptr (decay(i))
        prc_def => process%get_component_def_ptr (1)
        call prc_def%get_prt_out (prt_out)
        prt_out_str(i) = prt_out(1)
        do j = 2, size (prt_out)
            prt_out_str(i) = prt_out_str(i) // ", " // prt_out(j)
        end do
        br(i) = process%get_integral ()
    end do
    if (all (br >= 0)) then
        if (any (br > 0)) then
            width = sum (br)
            br = br / sum (br)
            write (u, "(A)") "Unstable particle " &
                // char (flv%get_name ()) &
                // ": computed branching ratios:"
            do i = 1, size (br)
                write (u, "(2x,A,':'," // FMT_14 // ",3x,A)") &
                    char (decay(i)), br(i), char (prt_out_str(i))
            end do
            write (u, "(2x,'Total width ='," // FMT_14 // ", ' GeV (computed)')") width
            write (u, "(2x,'          ='," // FMT_14 // ", ' GeV (preset)')") &
                flv%get_width ()

```

```

        if (flv%decays_isotropically ()) then
            write (u, "(2x,A)") "Decay options: isotropic"
        else if (flv%decays_diagonal ()) then
            write (u, "(2x,A)") "Decay options: &
                &projection on diagonal helicity states"
        else if (flv%has_decay_helicity ()) then
            write (u, "(2x,A,1x,I0)") "Decay options: projection onto helicity =", &
                flv%get_decay_helicity ()
        else
            write (u, "(2x,A)") "Decay options: helicity treated exactly"
        end if
    else
        call msg_fatal ("Unstable particle " &
            // char (flv%get_name ()) &
            // ": partial width vanishes for all decay channels")
    end if
else
    call msg_fatal ("Unstable particle " &
        // char (flv%get_name ()) &
        // ": partial width is negative")
end if
end if
end subroutine show_unstable

```

If no decays have been found, issue a non-fatal error.

(Commands: procedures)+≡

```

subroutine err_unstable (global, pdg)
    type(rt_data_t), intent(in), target :: global
    integer, intent(in) :: pdg
    type(flavor_t) :: flv
    call flv%init (pdg, global%model)
    call msg_error ("Unstable: no allowed decays found for particle " &
        // char (flv%get_name ()) // ", keeping as stable")
end subroutine err_unstable

```

Auto decays: create process IDs and make up process configurations, using the PDG codes generated by the `ds_table` make method.

We allocate and use a self-contained process library that contains only the decay processes of the current particle. When done, we revert the global library pointer to the original library but return the name of the new one. The new library becomes part of the global library stack and can thus be referred to at any time.

(Commands: procedures)+≡

```

subroutine create_auto_decays &
    (pdg_in, mult, rad, libname_dec, process_id, global)
    integer, intent(in) :: pdg_in
    integer, intent(in) :: mult
    logical, intent(in) :: rad
    type(string_t), intent(out) :: libname_dec
    type(string_t), dimension(:), allocatable, intent(out) :: process_id
    type(rt_data_t), intent(inout) :: global
    type(prclib_entry_t), pointer :: lib_entry
    type(process_library_t), pointer :: lib

```



```

type(ds_table_t) :: ds_table
type(split_constraints_t) :: constraints
type(pdg_array_t), dimension(:), allocatable :: pa_out
character(80) :: buffer
character :: p_or_a
type(string_t) :: process_string, libname_cur
type(flavor_t) :: flv_in, flv_out
type(string_t) :: prt_in
type(string_t), dimension(:), allocatable :: prt_out
type(process_configuration_t) :: prc_config
integer :: i, j, k
call flv_in%init (pdg_in, global%model)
if (rad) then
    call constraints%init (2)
else
    call constraints%init (3)
    call constraints%set (3, constrain_radiation ())
end if
call constraints%set (1, constrain_n_tot (mult))
call constraints%set (2, &
    constrain_mass_sum (flv_in%get_mass (), margin = 0._default))
call ds_table%make (global%model, pdg_in, constraints)
prt_in = flv_in%get_name ()
if (pdg_in > 0) then
    p_or_a = "p"
else
    p_or_a = "a"
end if
if (ds_table%get_length () == 0) then
    call msg_warning ("Auto-decays: Particle " // char (prt_in) // ": " &
        // "no decays found")
    libname_dec = ""
    allocate (process_id (0))
else
    call msg_message ("Creating decay process library for particle " &
        // char (prt_in))
    libname_cur = global%prclib%get_name ()
    write (buffer, "(A,A,I0)" "_d", p_or_a, abs (pdg_in))
    libname_dec = libname_cur // trim (buffer)
    lib => global%prclib_stack%get_library_ptr (libname_dec)
    if (.not. (associated (lib))) then
        allocate (lib_entry)
        call lib_entry%init (libname_dec)
        lib => lib_entry%process_library_t
        call global%add_prclib (lib_entry)
    else
        call global%update_prclib (lib)
    end if
    allocate (process_id (ds_table%get_length ()))
    do i = 1, size (process_id)
        write (buffer, "(A,'_',A,I0,'_',I0)" &
            "decay", p_or_a, abs (pdg_in), i)
        process_id(i) = trim (buffer)
        process_string = process_id(i) // ": " // prt_in // " =>"
    end do
end if

```

```

call ds_table%get_pdg_out (i, pa_out)
allocate (prt_out (size (pa_out)))
do j = 1, size (pa_out)
  do k = 1, pa_out(j)%get_length ()
    call flv_out%init (pa_out(j)%get (k), global%model)
    if (k == 1) then
      prt_out(j) = flv_out%get_name ()
    else
      prt_out(j) = prt_out(j) // ":" // flv_out%get_name ()
    end if
  end do
  process_string = process_string // " " // prt_out(j)
end do
call msg_message (char (process_string))
call prc_config%init (process_id(i), 1, 1, global)
!!! Causes runtime error with gfortran 4.9.1
! call prc_config%setup_component (1, &
!   new_prt_spec ([prt_in]), new_prt_spec (prt_out), global)
!!! Workaround:
call prc_config%setup_component (1, &
  [new_prt_spec (prt_in)], new_prt_spec (prt_out), global)
call prc_config%record (global)
deallocate (prt_out)
deallocate (pa_out)
end do
lib => global%prclib_stack%get_library_ptr (libname_cur)
call global%update_prclib (lib)
end if
call ds_table%final ()
end subroutine create_auto_decays

```

(Stable particles

Revert the unstable declaration for a list of particles.

```

<Commands: types>+≡
  type, extends (command_t) :: cmd_stable_t
  private
    type(parse_node_p), dimension(:), allocatable :: pn_pdg
  contains
    <Commands: cmd stable: TBP>
  end type cmd_stable_t

```

Output: we know only the number of particles.

```

<Commands: cmd stable: TBP>≡
  procedure :: write => cmd_stable_write

<Commands: procedures>+≡
  subroutine cmd_stable_write (cmd, unit, indent)
    class(cmd_stable_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
  end subroutine cmd_stable_write

```

```

        write (u, "(1x,A,1x,I0)") "stable:", size (cmd%pn_pdg)
    end subroutine cmd_stable_write

```

Compile. Assign parse nodes for the particle IDs.

```

<Commands: cmd stable: TBP>+≡
    procedure :: compile => cmd_stable_compile

<Commands: procedures>+≡
    subroutine cmd_stable_compile (cmd, global)
        class(cmd_stable_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(parse_node_t), pointer :: pn_list, pn_ptr
        integer :: n, i
        pn_list => parse_node_get_sub_ptr (cmd%pn, 2)
        cmd%pn_opt => parse_node_get_next_ptr (pn_list)
        call cmd%compile_options (global)
        n = parse_node_get_n_sub (pn_list)
        allocate (cmd%pn_pdg (n))
        pn_ptr => parse_node_get_sub_ptr (pn_list)
        i = 1
        do while (associated (pn_ptr))
            cmd%pn_pdg(i)%ptr => pn_ptr
            pn_ptr => parse_node_get_next_ptr (pn_ptr)
            i = i + 1
        end do
    end subroutine cmd_stable_compile

```

Execute: apply the modifications to the current model.

```

<Commands: cmd stable: TBP>+≡
    procedure :: execute => cmd_stable_execute

<Commands: procedures>+≡
    subroutine cmd_stable_execute (cmd, global)
        class(cmd_stable_t), intent(inout) :: cmd
        type(rt_data_t), target, intent(inout) :: global
        type(var_list_t), pointer :: var_list
        type(pdg_array_t) :: pa
        integer :: pdg
        type(flavor_t) :: flv
        integer :: i
        var_list => cmd%local%get_var_list_ptr ()
        do i = 1, size (cmd%pn_pdg)
            pa = eval_pdg_array (cmd%pn_pdg(i)%ptr, var_list)
            if (pdg_array_get_length (pa) /= 1) &
                call msg_fatal ("Stable: listed particles must be unique")
            pdg = pdg_array_get (pa, 1)
            call global%modify_particle (pdg, stable = .true., &
                isotropic_decay = .false., &
                diagonal_decay = .false., &
                polarized = .false.)
            call flv%init (pdg, cmd%local%model)
            call msg_message ("Particle " &
                // char (flv%get_name ()) &
                // " declared as stable")
        end do
    end subroutine cmd_stable_execute

```

```

    end do
end subroutine cmd_stable_execute

```

Polarized particles

These commands mark particles as (un)polarized, to be applied in subsequent simulation passes. Since this is technically the same as the `stable` command, we take a shortcut and make this an extension, just overriding methods.

```

⟨Commands: types⟩+≡
  type, extends (cmd_stable_t) :: cmd_polarized_t
  contains
    ⟨Commands: cmd polarized: TBP⟩
  end type cmd_polarized_t

  type, extends (cmd_stable_t) :: cmd_unpolarized_t
  contains
    ⟨Commands: cmd unpolarized: TBP⟩
  end type cmd_unpolarized_t

```

Output: we know only the number of particles.

```

⟨Commands: cmd polarized: TBP⟩≡
  procedure :: write => cmd_polarized_write

⟨Commands: cmd unpolarized: TBP⟩≡
  procedure :: write => cmd_unpolarized_write

⟨Commands: procedures⟩+≡
  subroutine cmd_polarized_write (cmd, unit, indent)
    class(cmd_polarized_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,1x,I0)") "polarized:", size (cmd%pn_pdg)
  end subroutine cmd_polarized_write

  subroutine cmd_unpolarized_write (cmd, unit, indent)
    class(cmd_unpolarized_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A,1x,I0)") "unpolarized:", size (cmd%pn_pdg)
  end subroutine cmd_unpolarized_write

```

Compile: accounted for by the base command.

Execute: apply the modifications to the current model.

```

⟨Commands: cmd polarized: TBP⟩+≡
  procedure :: execute => cmd_polarized_execute

⟨Commands: cmd unpolarized: TBP⟩+≡
  procedure :: execute => cmd_unpolarized_execute

```

<Commands: procedures>+≡

```

subroutine cmd_polarized_execute (cmd, global)
  class(cmd_polarized_t), intent(inout) :: cmd
  type(rt_data_t), target, intent(inout) :: global
  type(var_list_t), pointer :: var_list
  type(pdg_array_t) :: pa
  integer :: pdg
  type(flavor_t) :: flv
  integer :: i
  var_list => cmd%local%get_var_list_ptr ()
  do i = 1, size (cmd%pn_pdg)
    pa = eval_pdg_array (cmd%pn_pdg(i)%ptr, var_list)
    if (pdg_array_get_length (pa) /= 1) &
      call msg_fatal ("Polarized: listed particles must be unique")
    pdg = pdg_array_get (pa, 1)
    call global%modify_particle (pdg, polarized = .true., &
      stable = .true., &
      isotropic_decay = .false., &
      diagonal_decay = .false.)
    call flv%init (pdg, cmd%local%model)
    call msg_message ("Particle " &
      // char (flv%get_name ()) &
      // " declared as polarized")
  end do
end subroutine cmd_polarized_execute

subroutine cmd_unpolarized_execute (cmd, global)
  class(cmd_unpolarized_t), intent(inout) :: cmd
  type(rt_data_t), target, intent(inout) :: global
  type(var_list_t), pointer :: var_list
  type(pdg_array_t) :: pa
  integer :: pdg
  type(flavor_t) :: flv
  integer :: i
  var_list => cmd%local%get_var_list_ptr ()
  do i = 1, size (cmd%pn_pdg)
    pa = eval_pdg_array (cmd%pn_pdg(i)%ptr, var_list)
    if (pdg_array_get_length (pa) /= 1) &
      call msg_fatal ("Unpolarized: listed particles must be unique")
    pdg = pdg_array_get (pa, 1)
    call global%modify_particle (pdg, polarized = .false., &
      stable = .true., &
      isotropic_decay = .false., &
      diagonal_decay = .false.)
    call flv%init (pdg, cmd%local%model)
    call msg_message ("Particle " &
      // char (flv%get_name ()) &
      // " declared as unpolarized")
  end do
end subroutine cmd_unpolarized_execute

```

Parameters: formats for event-sample output

Specify all event formats that are to be used for output files in the subsequent simulation run. (The raw format is on by default and can be turned off here.)

```
<Commands: types>+≡
    type, extends (command_t) :: cmd_sample_format_t
        private
        type(string_t), dimension(:), allocatable :: format
    contains
        <Commands: cmd sample format: TBP>
    end type cmd_sample_format_t
```

Output: here, everything is known.

```
<Commands: cmd sample format: TBP>≡
    procedure :: write => cmd_sample_format_write

<Commands: procedures>+≡
    subroutine cmd_sample_format_write (cmd, unit, indent)
        class(cmd_sample_format_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A)", advance="no") "sample_format = "
        do i = 1, size (cmd%format)
            if (i > 1) write (u, "(A,1x)", advance="no") " ,"
            write (u, "(A)", advance="no") char (cmd%format(i))
        end do
        write (u, "(A)")
    end subroutine cmd_sample_format_write
```

Compile. Initialize evaluation trees.

```
<Commands: cmd sample format: TBP>+≡
    procedure :: compile => cmd_sample_format_compile

<Commands: procedures>+≡
    subroutine cmd_sample_format_compile (cmd, global)
        class(cmd_sample_format_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        type(parse_node_t), pointer :: pn_arg
        type(parse_node_t), pointer :: pn_format
        integer :: i, n_format
        pn_arg => parse_node_get_sub_ptr (cmd%pn, 3)
        if (associated (pn_arg)) then
            n_format = parse_node_get_n_sub (pn_arg)
            allocate (cmd%format (n_format))
            pn_format => parse_node_get_sub_ptr (pn_arg)
            i = 0
            do while (associated (pn_format))
                i = i + 1
                cmd%format(i) = parse_node_get_string (pn_format)
                pn_format => parse_node_get_next_ptr (pn_format)
            end do
        else
```

```

        allocate (cmd%format (0))
    end if
end subroutine cmd_sample_format_compile

```

Execute. Transfer the list of format specifications to the corresponding array in the runtime data set.

```

⟨Commands: cmd sample format: TBP⟩+≡
    procedure :: execute => cmd_sample_format_execute

⟨Commands: procedures⟩+≡
    subroutine cmd_sample_format_execute (cmd, global)
        class(cmd_sample_format_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        if (allocated (global%sample_fmt)) deallocate (global%sample_fmt)
        allocate (global%sample_fmt (size (cmd%format)), source = cmd%format)
    end subroutine cmd_sample_format_execute

```

The simulate command

This is the actual SINDARIN command.

```

⟨Commands: types⟩+≡
    type, extends (command_t) :: cmd_simulate_t
        ! not private anymore as required by the whizard-c-interface
        integer :: n_proc = 0
        type(string_t), dimension(:), allocatable :: process_id
    contains
        ⟨Commands: cmd simulate: TBP⟩
    end type cmd_simulate_t

```

Output: we know the process IDs.

```

⟨Commands: cmd simulate: TBP⟩≡
    procedure :: write => cmd_simulate_write

⟨Commands: procedures⟩+≡
    subroutine cmd_simulate_write (cmd, unit, indent)
        class(cmd_simulate_t), intent(in) :: cmd
        integer, intent(in), optional :: unit, indent
        integer :: u, i
        u = given_output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A)", advance="no") "simulate ("
        do i = 1, cmd%n_proc
            if (i > 1) write (u, "(A,1x)", advance="no") " ,"
            write (u, "(A)", advance="no") char (cmd%process_id(i))
        end do
        write (u, "(A)") ")"
    end subroutine cmd_simulate_write

```

Compile. In contrast to WHIZARD 1 the confusing option to give the number of unweighted events for weighted events as if unweighting were to take place has

been abandoned. (We both use `n_events` for weighted and unweighted events, the variable `n_calls` from WHIZARD 1 has been discarded.

(Commands: cmd simulate: TBP)+≡

```
procedure :: compile => cmd_simulate_compile
```

(Commands: procedures)+≡

```
subroutine cmd_simulate_compile (cmd, global)
  class(cmd_simulate_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_proclist, pn_proc
  integer :: i
  pn_proclist => parse_node_get_sub_ptr (cmd%pn, 2)
  cmd%pn_opt => parse_node_get_next_ptr (pn_proclist)
  call cmd%compile_options (global)
  cmd%n_proc = parse_node_get_n_sub (pn_proclist)
  allocate (cmd%process_id (cmd%n_proc))
  pn_proc => parse_node_get_sub_ptr (pn_proclist)
  do i = 1, cmd%n_proc
    cmd%process_id(i) = parse_node_get_string (pn_proc)
    call global%process_stack%init_result_vars (cmd%process_id(i))
    pn_proc => parse_node_get_next_ptr (pn_proc)
  end do
end subroutine cmd_simulate_compile
```

Execute command: Simulate events. This is done via a `simulation_t` object and its associated methods.

Signal handling: the `generate` method may exit abnormally if there is a pending signal. The current logic ensures that the `es_array` output channels are closed before the `execute` routine returns. The program will terminate then in `command_list_execute`.

(Commands: cmd simulate: TBP)+≡

```
procedure :: execute => cmd_simulate_execute
```

(Commands: procedures)+≡

```
subroutine cmd_simulate_execute (cmd, global)
  class(cmd_simulate_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  type(rt_data_t), dimension(:), allocatable, target :: alt_env
  integer :: n_events, n_fmt
  type(string_t) :: sample
  logical :: rebuild_events, read_raw, write_raw
  type(simulation_t), target :: sim
  type(string_t), dimension(:), allocatable :: sample_fmt
  type(event_stream_array_t) :: es_array
  type(event_sample_data_t) :: data
  integer :: i, checkpoint
  var_list => cmd%local%var_list
  if (allocated (cmd%local%pn%alt_setup)) then
    allocate (alt_env (size (cmd%local%pn%alt_setup)))
    do i = 1, size (alt_env)
      call build_alt_setup (alt_env(i), cmd%local, &
        cmd%local%pn%alt_setup(i)%ptr)
    end do
  end if
```



```

        call sim%init (cmd%process_id, .true., .true., cmd%local, global, &
            alt_env)
    else
        call sim%init (cmd%process_id, .true., .true., cmd%local, global)
    end if
    if (signal_is_pending ()) return
    if (sim%is_valid ()) then
        call sim%init_process_selector ()
        call openmp_set_num_threads_verbose &
            (var_list%get_ival (var_str ("openmp_num_threads")), &
            var_list%get_lval (var_str ("?openmp_logging")))
        call sim%compute_n_events (n_events, var_list)
        sample = var_list%get_sval (var_str ("sample"))
        if (sample == "") sample = sim%get_default_sample_name ()
        rebuild_events = &
            var_list%get_lval (var_str ("?rebuild_events"))
        read_raw = &
            var_list%get_lval (var_str ("?read_raw")) &
            .and. .not. rebuild_events
        write_raw = &
            var_list%get_lval (var_str ("?write_raw"))
        checkpoint = &
            var_list%get_ival (var_str ("checkpoint"))
        if (read_raw) then
            inquire (file = char (sample) // ".evx", exist = read_raw)
        end if
        if (allocated (cmd%local%sample_fmt)) then
            n_fmt = size (cmd%local%sample_fmt)
        else
            n_fmt = 0
        end if
        data = sim%get_data ()
        data%n_evt = n_events
        if (read_raw) then
            allocate (sample_fmt (n_fmt))
            if (n_fmt > 0) sample_fmt = cmd%local%sample_fmt
            call es_array%init (sample, &
                sample_fmt, cmd%local, &
                data = data, &
                input = var_str ("raw"), &
                allow_switch = write_raw, &
                checkpoint = checkpoint)
            call sim%generate (n_events, es_array)
            call es_array%final ()
        else if (write_raw) then
            allocate (sample_fmt (n_fmt + 1))
            if (n_fmt > 0) sample_fmt (:n_fmt) = cmd%local%sample_fmt
            sample_fmt(n_fmt+1) = var_str ("raw")
            call es_array%init (sample, &
                sample_fmt, cmd%local, &
                data = data, &
                checkpoint = checkpoint)
            call sim%generate (n_events, es_array)
            call es_array%final ()
        end if
    end if
end if

```

```

else if (allocated (cmd%local%sample_fmt) .or. checkpoint > 0) then
  allocate (sample_fmt (n_fmt))
  if (n_fmt > 0) sample_fmt = cmd%local%sample_fmt
  call es_array%init (sample, &
    sample_fmt, cmd%local, &
    data = data, &
    checkpoint = checkpoint)
  call sim%generate (n_events, es_array)
  call es_array%final ()
else
  call sim%generate (n_events)
end if
if (allocated (alt_env)) then
  do i = 1, size (alt_env)
    call alt_env(i)%local_final ()
  end do
end if
end if
call sim%final ()
end subroutine cmd_simulate_execute

```

Build an alternative setup: the parse tree is stored in the global environment. We create a temporary command list to compile and execute this; the result is an alternative local environment `alt_env` which we can hand over to the `simulate` command.

(Commands: procedures)+≡

```

recursive subroutine build_alt_setup (alt_env, global, pn)
  type(rt_data_t), intent(inout), target :: alt_env
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), intent(in), target :: pn
  type(command_list_t), allocatable :: alt_options
  allocate (alt_options)
  call alt_env%local_init (global)
  call alt_env%activate ()
  call alt_options%compile (pn, alt_env)
  call alt_options%execute (alt_env)
  call alt_env%deactivate (global, keep_local = .true.)
  call alt_options%final ()
end subroutine build_alt_setup

```

The rescan command

This is the actual SINDARIN command.

(Commands: types)+≡

```

type, extends (command_t) :: cmd_rescan_t
! private
  type(parse_node_t), pointer :: pn_filename => null ()
  integer :: n_proc = 0
  type(string_t), dimension(:), allocatable :: process_id
contains
  (Commands: cmd rescan: TBP)
end type cmd_rescan_t

```

Output: we know the process IDs.

```

(Commands: cmd rescan: TBP)≡
  procedure :: write => cmd_rescan_write

(Commands: procedures)+≡
  subroutine cmd_rescan_write (cmd, unit, indent)
    class(cmd_rescan_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u, i
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    write (u, "(1x,A)", advance="no") "rescan ("
    do i = 1, cmd%n_proc
      if (i > 1) write (u, "(A,1x)", advance="no") " ,"
      write (u, "(A)", advance="no") char (cmd%process_id(i))
    end do
    write (u, "(A)") ")"
  end subroutine cmd_rescan_write

```

Compile. The command takes a suffix argument, namely the file name of requested event file.

```

(Commands: cmd rescan: TBP)+≡
  procedure :: compile => cmd_rescan_compile

(Commands: procedures)+≡
  subroutine cmd_rescan_compile (cmd, global)
    class(cmd_rescan_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_filename, pn_proclist, pn_proc
    integer :: i
    pn_filename => parse_node_get_sub_ptr (cmd%pn, 2)
    pn_proclist => parse_node_get_next_ptr (pn_filename)
    cmd%pn_opt => parse_node_get_next_ptr (pn_proclist)
    call cmd%compile_options (global)
    cmd%pn_filename => pn_filename
    cmd%n_proc = parse_node_get_n_sub (pn_proclist)
    allocate (cmd%process_id (cmd%n_proc))
    pn_proc => parse_node_get_sub_ptr (pn_proclist)
    do i = 1, cmd%n_proc
      cmd%process_id(i) = parse_node_get_string (pn_proc)
      pn_proc => parse_node_get_next_ptr (pn_proc)
    end do
  end subroutine cmd_rescan_compile

```

Execute command: Rescan events. This is done via a `simulation_t` object and its associated methods.

```

(Commands: cmd rescan: TBP)+≡
  procedure :: execute => cmd_rescan_execute

(Commands: procedures)+≡
  subroutine cmd_rescan_execute (cmd, global)
    class(cmd_rescan_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global

```

```

type(var_list_t), pointer :: var_list
type(rt_data_t), dimension(:), allocatable, target :: alt_env
type(string_t) :: sample
logical :: exist, write_raw, update_event, update_sqme, update_weight
type(simulation_t), target :: sim
type(event_sample_data_t) :: input_data, data
type(string_t) :: input_sample
integer :: n_fmt
type(string_t), dimension(:), allocatable :: sample_fmt
type(string_t) :: input_format, input_ext, input_file
type(string_t) :: lhef_extension, extension_hepmc, extension_lcio
type(event_stream_array_t) :: es_array
integer :: i, n_events
var_list => cmd%local%var_list
if (allocated (cmd%local%pn%alt_setup)) then
    allocate (alt_env (size (cmd%local%pn%alt_setup)))
    do i = 1, size (alt_env)
        call build_alt_setup (alt_env(i), cmd%local, &
            cmd%local%pn%alt_setup(i)%ptr)
    end do
    call sim%init (cmd%process_id, .false., .false., cmd%local, global, &
        alt_env)
else
    call sim%init (cmd%process_id, .false., .false., cmd%local, global)
end if
call sim%compute_n_events (n_events, var_list)
input_sample = eval_string (cmd%pn_filename, var_list)
input_format = var_list%get_sval (&
    var_str ("rescan_input_format"))
sample = var_list%get_sval (var_str ("sample"))
if (sample == "") sample = sim%get_default_sample_name ()
write_raw = var_list%get_lval (var_str ("write_raw"))
if (allocated (cmd%local%sample_fmt)) then
    n_fmt = size (cmd%local%sample_fmt)
else
    n_fmt = 0
end if
if (write_raw) then
    if (sample == input_sample) then
        call msg_error ("Rescan: write_raw = true: " &
            // "suppressing raw event output (filename clashes with input)")
        allocate (sample_fmt (n_fmt))
        if (n_fmt > 0) sample_fmt = cmd%local%sample_fmt
    else
        allocate (sample_fmt (n_fmt + 1))
        if (n_fmt > 0) sample_fmt(:n_fmt) = cmd%local%sample_fmt
        sample_fmt(n_fmt+1) = var_str ("raw")
    end if
else
    allocate (sample_fmt (n_fmt))
    if (n_fmt > 0) sample_fmt = cmd%local%sample_fmt
end if
update_event = &
    var_list%get_lval (var_str ("update_event"))

```

```

update_sqme = &
    var_list%get_lval (var_str ("?update_sqme"))
update_weight = &
    var_list%get_lval (var_str ("?update_weight"))
if (update_event .or. update_sqme) then
    call msg_message ("Recalculating observables")
    if (update_sqme) then
        call msg_message ("Recalculating squared matrix elements")
    end if
end if
lhef_extension = &
    var_list%get_sval (var_str ("$lhef_extension"))
extension_hepmc = &
    var_list%get_sval (var_str ("$extension_hepmc"))
extension_lcio = &
    var_list%get_sval (var_str ("$extension_lcio"))
select case (char (input_format))
case ("raw"); input_ext = "evx"
    call cmd%local%set_log &
        (var_str ("?recover_beams"), .false., is_known=.true.)
case ("lhef"); input_ext = lhef_extension
case ("hepmc"); input_ext = extension_hepmc
case default
    call msg_fatal ("rescan: input sample format '" // char (input_format) &
        // "' not supported")
end select
input_file = input_sample // "." // input_ext
inquire (file = char (input_file), exist = exist)
if (exist) then
    input_data = sim%get_data (alt = .false.)
    input_data%n_evt = n_events
    data = sim%get_data ()
    data%n_evt = n_events
    input_data%md5sum_cfg = ""
    call es_array%init (sample, &
        sample_fmt, cmd%local, data, &
        input = input_format, input_sample = input_sample, &
        input_data = input_data, &
        allow_switch = .false.)
    call sim%rescan (n_events, es_array, global = cmd%local)
    call es_array%final ()
else
    call msg_fatal ("Rescan: event file '" &
        // char (input_file) // "' not found")
end if
if (allocated (alt_env)) then
    do i = 1, size (alt_env)
        call alt_env(i)%local_final ()
    end do
end if
call sim%final ()
end subroutine cmd_rescan_execute

```

Parameters: number of iterations

Specify number of iterations and number of calls for one integration pass.

```
<Commands: types>+≡
    type, extends (command_t) :: cmd_iterations_t
    private
    integer :: n_pass = 0
    type(parse_node_p), dimension(:), allocatable :: pn_expr_n_it
    type(parse_node_p), dimension(:), allocatable :: pn_expr_n_calls
    type(parse_node_p), dimension(:), allocatable :: pn_sexpr_adapt
    contains
    <Commands: cmd iterations: TBP>
end type cmd_iterations_t
```

Output. Display the number of passes, which is known after compilation.

```
<Commands: cmd iterations: TBP>≡
    procedure :: write => cmd_iterations_write

<Commands: procedures>+≡
    subroutine cmd_iterations_write (cmd, unit, indent)
    class(cmd_iterations_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u
    u = given_output_unit (unit); if (u < 0) return
    call write_indent (u, indent)
    select case (cmd%n_pass)
    case (0)
        write (u, "(1x,A)") "iterations: [empty]"
    case (1)
        write (u, "(1x,A,I0,A)") "iterations: ", cmd%n_pass, " pass"
    case default
        write (u, "(1x,A,I0,A)") "iterations: ", cmd%n_pass, " passes"
    end select
end subroutine cmd_iterations_write
```

Compile. Initialize evaluation trees.

```
<Commands: cmd iterations: TBP>+≡
    procedure :: compile => cmd_iterations_compile

<Commands: procedures>+≡
    subroutine cmd_iterations_compile (cmd, global)
    class(cmd_iterations_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_arg, pn_n_it, pn_n_calls, pn_adapt
    type(parse_node_t), pointer :: pn_it_spec, pn_calls_spec, pn_adapt_spec
    integer :: i
    pn_arg => parse_node_get_sub_ptr (cmd%pn, 3)
    if (associated (pn_arg)) then
        cmd%n_pass = parse_node_get_n_sub (pn_arg)
        allocate (cmd%pn_expr_n_it (cmd%n_pass))
        allocate (cmd%pn_expr_n_calls (cmd%n_pass))
        allocate (cmd%pn_sexpr_adapt (cmd%n_pass))
        pn_it_spec => parse_node_get_sub_ptr (pn_arg)
        i = 1
    end if
end subroutine cmd_iterations_compile
```

```

do while (associated (pn_it_spec))
  pn_n_it => parse_node_get_sub_ptr (pn_it_spec)
  pn_calls_spec => parse_node_get_next_ptr (pn_n_it)
  pn_n_calls => parse_node_get_sub_ptr (pn_calls_spec, 2)
  pn_adapt_spec => parse_node_get_next_ptr (pn_calls_spec)
  if (associated (pn_adapt_spec)) then
    pn_adapt => parse_node_get_sub_ptr (pn_adapt_spec, 2)
  else
    pn_adapt => null ()
  end if
  cmd%pn_expr_n_it(i)%ptr => pn_n_it
  cmd%pn_expr_n_calls(i)%ptr => pn_n_calls
  cmd%pn_sexpr_adapt(i)%ptr => pn_adapt
  i = i + 1
  pn_it_spec => parse_node_get_next_ptr (pn_it_spec)
end do
else
  allocate (cmd%pn_expr_n_it (0))
  allocate (cmd%pn_expr_n_calls (0))
end if
end subroutine cmd_iterations_compile

```

Execute. Evaluate the trees and transfer the results to the iteration list in the runtime data set.

(Commands: cmd iterations: TBP)+≡

```

procedure :: execute => cmd_iterations_execute

```

(Commands: procedures)+≡

```

subroutine cmd_iterations_execute (cmd, global)
  class(cmd_iterations_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  integer, dimension(cmd%n_pass) :: n_it, n_calls
  logical, dimension(cmd%n_pass) :: custom_adapt
  type(string_t), dimension(cmd%n_pass) :: adapt_code
  integer :: i
  var_list => global%get_var_list_ptr ()
  do i = 1, cmd%n_pass
    n_it(i) = eval_int (cmd%pn_expr_n_it(i)%ptr, var_list)
    n_calls(i) = &
      eval_int (cmd%pn_expr_n_calls(i)%ptr, var_list)
    if (associated (cmd%pn_sexpr_adapt(i)%ptr)) then
      adapt_code(i) = &
        eval_string (cmd%pn_sexpr_adapt(i)%ptr, &
          var_list, is_known = custom_adapt(i))
    else
      custom_adapt(i) = .false.
    end if
  end do
  call global%it_list%init (n_it, n_calls, custom_adapt, adapt_code)
end subroutine cmd_iterations_execute

```

Range expressions

We need a special type for storing and evaluating range expressions.

```
(Commands: parameters)+≡  
  integer, parameter :: STEP_NONE = 0  
  integer, parameter :: STEP_ADD = 1  
  integer, parameter :: STEP_SUB = 2  
  integer, parameter :: STEP_MUL = 3  
  integer, parameter :: STEP_DIV = 4  
  integer, parameter :: STEP_COMP_ADD = 11  
  integer, parameter :: STEP_COMP_MUL = 13
```

There is an abstract base type and two implementations: scan over integers and scan over reals.

```
(Commands: types)+≡  
  type, abstract :: range_t  
    type(parse_node_t), pointer :: pn_expr => null ()  
    type(parse_node_t), pointer :: pn_term => null ()  
    type(parse_node_t), pointer :: pn_factor => null ()  
    type(parse_node_t), pointer :: pn_value => null ()  
    type(parse_node_t), pointer :: pn_literal => null ()  
    type(parse_node_t), pointer :: pn_beg => null ()  
    type(parse_node_t), pointer :: pn_end => null ()  
    type(parse_node_t), pointer :: pn_step => null ()  
    type(eval_tree_t) :: expr_beg  
    type(eval_tree_t) :: expr_end  
    type(eval_tree_t) :: expr_step  
    integer :: step_mode = 0  
    integer :: n_step = 0  
  contains  
    (Commands: range: TBP)  
  end type range_t
```

These are the implementations:

```
(Commands: types)+≡  
  type, extends (range_t) :: range_int_t  
    integer :: i_beg = 0  
    integer :: i_end = 0  
    integer :: i_step = 0  
  contains  
    (Commands: range int: TBP)  
  end type range_int_t  
  
  type, extends (range_t) :: range_real_t  
    real(default) :: r_beg = 0  
    real(default) :: r_end = 0  
    real(default) :: r_step = 0  
    real(default) :: lr_beg = 0  
    real(default) :: lr_end = 0  
    real(default) :: lr_step = 0  
  contains  
    (Commands: range real: TBP)  
  end type range_real_t
```


Finalize the allocated dummy node. The other nodes are just pointers.

```

<Commands: range: TBP>≡
    procedure :: final => range_final

<Commands: procedures>+≡
    subroutine range_final (object)
        class(range_t), intent(inout) :: object
        if (associated (object%pn_expr)) then
            call parse_node_final (object%pn_expr, recursive = .false.)
            call parse_node_final (object%pn_term, recursive = .false.)
            call parse_node_final (object%pn_factor, recursive = .false.)
            call parse_node_final (object%pn_value, recursive = .false.)
            call parse_node_final (object%pn_literal, recursive = .false.)
            deallocate (object%pn_expr)
            deallocate (object%pn_term)
            deallocate (object%pn_factor)
            deallocate (object%pn_value)
            deallocate (object%pn_literal)
        end if
    end subroutine range_final

```

Output.

```

<Commands: range: TBP>+≡
    procedure (range_write), deferred :: write
    procedure :: base_write => range_write

<Commands: range int: TBP>≡
    procedure :: write => range_int_write

<Commands: range real: TBP>≡
    procedure :: write => range_real_write

<Commands: procedures>+≡
    subroutine range_write (object, unit)
        class(range_t), intent(in) :: object
        integer, intent(in), optional :: unit
        integer :: u
        u = given_output_unit (unit)
        write (u, "(1x,A)") "Range specification:"
        if (associated (object%pn_expr)) then
            write (u, "(1x,A)") "Dummy value:"
            call parse_node_write_rec (object%pn_expr, u)
        end if
        if (associated (object%pn_beg)) then
            write (u, "(1x,A)") "Initial value:"
            call parse_node_write_rec (object%pn_beg, u)
            call object%expr_beg%write (u)
            if (associated (object%pn_end)) then
                write (u, "(1x,A)") "Final value:"
                call parse_node_write_rec (object%pn_end, u)
                call object%expr_end%write (u)
            end if
            if (associated (object%pn_step)) then
                write (u, "(1x,A)") "Step value:"
                call parse_node_write_rec (object%pn_step, u)
                select case (object%step_mode)

```

```

        case (STEP_ADD);   write (u, "(1x,A)") "Step mode: +"
        case (STEP_SUB);   write (u, "(1x,A)") "Step mode: -"
        case (STEP_MUL);   write (u, "(1x,A)") "Step mode: *"
        case (STEP_DIV);   write (u, "(1x,A)") "Step mode: /"
        case (STEP_COMP_ADD); write (u, "(1x,A)") "Division mode: +"
        case (STEP_COMP_MUL); write (u, "(1x,A)") "Division mode: *"
    end select
end if
end if
else
    write (u, "(1x,A)") "Expressions: [undefined]"
end if
end subroutine range_write

subroutine range_int_write (object, unit)
    class(range_int_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    call object%base_write (unit)
    write (u, "(1x,A)") "Range parameters:"
    write (u, "(3x,A,I0)") "i_beg = ", object%i_beg
    write (u, "(3x,A,I0)") "i_end = ", object%i_end
    write (u, "(3x,A,I0)") "i_step = ", object%i_step
    write (u, "(3x,A,I0)") "n_step = ", object%n_step
end subroutine range_int_write

subroutine range_real_write (object, unit)
    class(range_real_t), intent(in) :: object
    integer, intent(in), optional :: unit
    integer :: u
    u = given_output_unit (unit)
    call object%base_write (unit)
    write (u, "(1x,A)") "Range parameters:"
    write (u, "(3x,A," // FMT_19 // ")") "r_beg = ", object%r_beg
    write (u, "(3x,A," // FMT_19 // ")") "r_end = ", object%r_end
    write (u, "(3x,A," // FMT_19 // ")") "r_step = ", object%r_end
    write (u, "(3x,A,I0)") "n_step = ", object%n_step
end subroutine range_real_write

```

Initialize, given a range expression parse node. This is common to the implementations.

```

<Commands: range: TBP>+≡
    procedure :: init => range_init

<Commands: procedures>+≡
    subroutine range_init (range, pn)
        class(range_t), intent(out) :: range
        type(parse_node_t), intent(in), target :: pn
        type(parse_node_t), pointer :: pn_spec, pn_end, pn_step_spec, pn_op
        select case (char (parse_node_get_rule_key (pn)))
        case ("expr")
        case ("range_expr")
            range%pn_beg => parse_node_get_sub_ptr (pn)

```

```

pn_spec => parse_node_get_next_ptr (range%pn_beg)
if (associated (pn_spec)) then
  pn_end => parse_node_get_sub_ptr (pn_spec, 2)
  range%pn_end => pn_end
  pn_step_spec => parse_node_get_next_ptr (pn_end)
  if (associated (pn_step_spec)) then
    pn_op => parse_node_get_sub_ptr (pn_step_spec)
    range%pn_step => parse_node_get_next_ptr (pn_op)
    select case (char (parse_node_get_rule_key (pn_op)))
    case ("/+"); range%step_mode = STEP_ADD
    case ("/-"); range%step_mode = STEP_SUB
    case ("/*"); range%step_mode = STEP_MUL
    case ("/"); range%step_mode = STEP_DIV
    case ("/+"); range%step_mode = STEP_COMP_ADD
    case ("/*"); range%step_mode = STEP_COMP_MUL
    case default
      call range%write ()
      call msg_bug ("Range: step mode not implemented")
    end select
  else
    range%step_mode = STEP_ADD
  end if
else
  range%step_mode = STEP_NONE
end if
call range%create_value_node ()
case default
  call msg_bug ("range expression: node type '" &
    // char (parse_node_get_rule_key (pn)) &
    // "' not implemented")
end select
end subroutine range_init

```

This method manually creates a parse node (actually, a cascade of parse nodes) that hold a constant value as a literal. The idea is that this node is inserted as the right-hand side of a fake variable assignment, which is prepended to each scan iteration. Before the variable assignment is compiled and executed, we can manually reset the value of the literal and thus pretend that the loop variable is assigned this value.

<Commands: range: TBP>+≡

```

  procedure :: create_value_node => range_create_value_node

```

<Commands: procedures>+≡

```

subroutine range_create_value_node (range)
  class(range_t), intent(inout) :: range
  allocate (range%pn_literal)
  allocate (range%pn_value)
  select type (range)
  type is (range_int_t)
    call parse_node_create_value (range%pn_literal, &
      syntax_get_rule_ptr (syntax_cmd_list, var_str ("integer_literal")), &
      ival = 0)
    call parse_node_create_branch (range%pn_value, &
      syntax_get_rule_ptr (syntax_cmd_list, var_str ("integer_value")))

```

```

type is (range_real_t)
  call parse_node_create_value (range%pn_literal, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("real_literal")), &
    rval = 0._default)
  call parse_node_create_branch (range%pn_value, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("real_value")))
class default
  call msg_bug ("range: create value node: type not implemented")
end select
call parse_node_append_sub (range%pn_value, range%pn_literal)
call parse_node_freeze_branch (range%pn_value)
allocate (range%pn_factor)
call parse_node_create_branch (range%pn_factor, &
  syntax_get_rule_ptr (syntax_cmd_list, var_str ("factor")))
call parse_node_append_sub (range%pn_factor, range%pn_value)
call parse_node_freeze_branch (range%pn_factor)
allocate (range%pn_term)
call parse_node_create_branch (range%pn_term, &
  syntax_get_rule_ptr (syntax_cmd_list, var_str ("term")))
call parse_node_append_sub (range%pn_term, range%pn_factor)
call parse_node_freeze_branch (range%pn_term)
allocate (range%pn_expr)
call parse_node_create_branch (range%pn_expr, &
  syntax_get_rule_ptr (syntax_cmd_list, var_str ("expr")))
call parse_node_append_sub (range%pn_expr, range%pn_term)
call parse_node_freeze_branch (range%pn_expr)
end subroutine range_create_value_node

```

Compile, given an environment.

```

⟨Commands: range: TBP⟩+≡
  procedure :: compile => range_compile

⟨Commands: procedures⟩+≡
  subroutine range_compile (range, global)
    class(range_t), intent(inout) :: range
    type(rt_data_t), intent(in), target :: global
    type(var_list_t), pointer :: var_list
    var_list => global%get_var_list_ptr ()
    if (associated (range%pn_beg)) then
      call range%expr_beg%init_expr (range%pn_beg, var_list)
      if (associated (range%pn_end)) then
        call range%expr_end%init_expr (range%pn_end, var_list)
        if (associated (range%pn_step)) then
          call range%expr_step%init_expr (range%pn_step, var_list)
        end if
      end if
    end if
  end if
end subroutine range_compile

```

Evaluate: compute the actual bounds and parameters that determine the values that we can iterate.

This is implementation-specific.

```

⟨Commands: range: TBP⟩+≡

```

```

    procedure (range_evaluate), deferred :: evaluate
  {Commands: interfaces}+=
    abstract interface
      subroutine range_evaluate (range)
        import
        class(range_t), intent(inout) :: range
      end subroutine range_evaluate
    end interface

```

The version for an integer variable. If the step is subtractive, we invert the sign and treat it as an additive step. For a multiplicative step, the step must be greater than one, and the initial and final values must be of same sign and strictly ordered. Analogously for a division step.

```

  {Commands: range int: TBP}+=
    procedure :: evaluate => range_int_evaluate

  {Commands: procedures}+=
    subroutine range_int_evaluate (range)
      class(range_int_t), intent(inout) :: range
      integer :: ival
      if (associated (range%pn_beg)) then
        call range%expr_beg%evaluate ()
        if (range%expr_beg%is_known ()) then
          range%i_beg = range%expr_beg%get_int ()
        else
          call range%write ()
          call msg_fatal &
            ("Range expression: initial value evaluates to unknown")
        end if
      if (associated (range%pn_end)) then
        call range%expr_end%evaluate ()
        if (range%expr_end%is_known ()) then
          range%i_end = range%expr_end%get_int ()
          if (associated (range%pn_step)) then
            call range%expr_step%evaluate ()
            if (range%expr_step%is_known ()) then
              range%i_step = range%expr_step%get_int ()
              select case (range%step_mode)
                case (STEP_SUB); range%i_step = - range%i_step
              end select
            else
              call range%write ()
              call msg_fatal &
                ("Range expression: step value evaluates to unknown")
            end if
          else
            range%i_step = 1
          end if
        else
          call range%write ()
          call msg_fatal &
            ("Range expression: final value evaluates to unknown")
        end if
      end if
    end subroutine range_int_evaluate

```

```

else
    range%i_end = range%i_beg
    range%i_step = 1
end if
select case (range%step_mode)
case (STEP_NONE)
    range%n_step = 1
case (STEP_ADD, STEP_SUB)
    if (range%i_step /= 0) then
        if (range%i_beg == range%i_end) then
            range%n_step = 1
        else if (sign (1, range%i_end - range%i_beg) &
            == sign (1, range%i_step)) then
            range%n_step = (range%i_end - range%i_beg) / range%i_step + 1
        else
            range%n_step = 0
        end if
    end if
else
    call msg_fatal ("range evaluation (add): step value is zero")
end if
case (STEP_MUL)
    if (range%i_step > 1) then
        if (range%i_beg == range%i_end) then
            range%n_step = 1
        else if (range%i_beg == 0) then
            call msg_fatal ("range evaluation (mul): initial value is zero")
        else if (sign (1, range%i_beg) == sign (1, range%i_end) &
            .and. abs (range%i_beg) < abs (range%i_end)) then
            range%n_step = 0
            ival = range%i_beg
            do while (abs (ival) <= abs (range%i_end))
                range%n_step = range%n_step + 1
                ival = ival * range%i_step
            end do
        else
            range%n_step = 0
        end if
    end if
else
    call msg_fatal &
        ("range evaluation (mult): step value is one or less")
end if
case (STEP_DIV)
    if (range%i_step > 1) then
        if (range%i_beg == range%i_end) then
            range%n_step = 1
        else if (sign (1, range%i_beg) == sign (1, range%i_end) &
            .and. abs (range%i_beg) > abs (range%i_end)) then
            range%n_step = 0
            ival = range%i_beg
            do while (abs (ival) >= abs (range%i_end))
                range%n_step = range%n_step + 1
                if (ival == 0) exit
                ival = ival / range%i_step
            end do
        end if
    end if
end if

```

```

        else
            range%n_step = 0
        end if
    else
        call msg_fatal &
            ("range evaluation (div): step value is one or less")
    end if
case (STEP_COMP_ADD)
    call msg_fatal ("range evaluation: &
        &step mode /+/ not allowed for integer variable")
case (STEP_COMP_MUL)
    call msg_fatal ("range evaluation: &
        &step mode /*/ not allowed for integer variable")
case default
    call range%write ()
    call msg_bug ("range evaluation: step mode not implemented")
end select
end if
end subroutine range_int_evaluate

```

The version for a real variable.

(Commands: range real: TBP)+≡

```

    procedure :: evaluate => range_real_evaluate

```

(Commands: procedures)+≡

```

subroutine range_real_evaluate (range)
class(range_real_t), intent(inout) :: range
if (associated (range%pn_beg)) then
    call range%expr_beg%evaluate ()
    if (range%expr_beg%is_known ()) then
        range%r_beg = range%expr_beg%get_real ()
    else
        call range%write ()
        call msg_fatal &
            ("Range expression: initial value evaluates to unknown")
    end if
if (associated (range%pn_end)) then
    call range%expr_end%evaluate ()
    if (range%expr_end%is_known ()) then
        range%r_end = range%expr_end%get_real ()
    if (associated (range%pn_step)) then
        if (range%expr_step%is_known ()) then
            select case (range%step_mode)
            case (STEP_ADD, STEP_SUB, STEP_MUL, STEP_DIV)
                call range%expr_step%evaluate ()
                range%r_step = range%expr_step%get_real ()
                select case (range%step_mode)
                case (STEP_SUB); range%r_step = - range%r_step
                end select
            case (STEP_COMP_ADD, STEP_COMP_MUL)
                range%n_step = &
                    max (range%expr_step%get_int (), 0)
                end select
        else

```

```

        call range%write ()
        call msg_fatal &
            ("Range expression: step value evaluates to unknown")
    end if
else
    call range%write ()
    call msg_fatal &
        ("Range expression (real): step value must be provided")
    end if
else
    call range%write ()
    call msg_fatal &
        ("Range expression: final value evaluates to unknown")
    end if
else
    range%r_end = range%r_beg
    range%r_step = 1
end if
select case (range%step_mode)
case (STEP_NONE)
    range%n_step = 1
case (STEP_ADD, STEP_SUB)
    if (range%r_step /= 0) then
        if (sign (1._default, range%r_end - range%r_beg) &
            == sign (1._default, range%r_step)) then
            range%n_step = &
                nint ((range%r_end - range%r_beg) / range%r_step + 1)
        else
            range%n_step = 0
        end if
    else
        call msg_fatal ("range evaluation (add): step value is zero")
    end if
case (STEP_MUL)
    if (range%r_step > 1) then
        if (range%r_beg == 0 .or. range%r_end == 0) then
            call msg_fatal ("range evaluation (mul): bound is zero")
        else if (sign (1._default, range%r_beg) &
            == sign (1._default, range%r_end) &
            .and. abs (range%r_beg) <= abs (range%r_end)) then
            range%lr_beg = log (abs (range%r_beg))
            range%lr_end = log (abs (range%r_end))
            range%lr_step = log (range%r_step)
            range%n_step = nint &
                (abs ((range%lr_end - range%lr_beg) / range%lr_step) + 1)
        else
            range%n_step = 0
        end if
    else
        call msg_fatal &
            ("range evaluation (mult): step value is one or less")
    end if
case (STEP_DIV)
    if (range%r_step > 1) then

```



```

        if (range%r_beg == 0 .or. range%r_end == 0) then
            call msg_fatal ("range evaluation (div): bound is zero")
        else if (sign (1._default, range%r_beg) &
            == sign (1._default, range%r_end) &
            .and. abs (range%r_beg) >= abs (range%r_end)) then
            range%lr_beg = log (abs (range%r_beg))
            range%lr_end = log (abs (range%r_end))
            range%lr_step = -log (range%r_step)
            range%n_step = nint &
                (abs ((range%lr_end - range%lr_beg) / range%lr_step) + 1)
        else
            range%n_step = 0
        end if
    else
        call msg_fatal &
            ("range evaluation (mult): step value is one or less")
    end if
case (STEP_COMP_ADD)
    ! Number of steps already known
case (STEP_COMP_MUL)
    ! Number of steps already known
    if (range%r_beg == 0 .or. range%r_end == 0) then
        call msg_fatal ("range evaluation (mul): bound is zero")
    else if (sign (1._default, range%r_beg) &
        == sign (1._default, range%r_end)) then
        range%lr_beg = log (abs (range%r_beg))
        range%lr_end = log (abs (range%r_end))
    else
        range%n_step = 0
    end if
case default
    call range%write ()
    call msg_bug ("range evaluation: step mode not implemented")
end select
end if
end subroutine range_real_evaluate

```

Return the number of iterations:

```

<Commands: range: TBP>+≡
    procedure :: get_n_iterations => range_get_n_iterations

<Commands: procedures>+≡
    function range_get_n_iterations (range) result (n)
        class(range_t), intent(in) :: range
        integer :: n
        n = range%n_step
    end function range_get_n_iterations

```

Compute the value for iteration i and store it in the embedded token.

```

<Commands: range: TBP>+≡
    procedure (range_set_value), deferred :: set_value

<Commands: interfaces>+≡
    abstract interface

```

```

subroutine range_set_value (range, i)
  import
  class(range_t), intent(inout) :: range
  integer, intent(in) :: i
end subroutine range_set_value
end interface

```

In the integer case, we compute the value directly for additive step. For multiplicative step, we perform a loop in the same way as above, where the number of iteration was determined.

```

⟨Commands: range int: TBP⟩+≡
  procedure :: set_value => range_int_set_value

⟨Commands: procedures⟩+≡
  subroutine range_int_set_value (range, i)
    class(range_int_t), intent(inout) :: range
    integer, intent(in) :: i
    integer :: k, ival
    select case (range%step_mode)
    case (STEP_NONE)
      ival = range%i_beg
    case (STEP_ADD, STEP_SUB)
      ival = range%i_beg + (i - 1) * range%i_step
    case (STEP_MUL)
      ival = range%i_beg
      do k = 1, i - 1
        ival = ival * range%i_step
      end do
    case (STEP_DIV)
      ival = range%i_beg
      do k = 1, i - 1
        ival = ival / range%i_step
      end do
    case default
      call range%write ()
      call msg_bug ("range iteration: step mode not implemented")
    end select
    call parse_node_set_value (range%pn_literal, ival = ival)
  end subroutine range_int_set_value

```

In the integer case, we compute the value directly for additive step. For multiplicative step, we perform a loop in the same way as above, where the number of iteration was determined.

```

⟨Commands: range real: TBP⟩+≡
  procedure :: set_value => range_real_set_value

⟨Commands: procedures⟩+≡
  subroutine range_real_set_value (range, i)
    class(range_real_t), intent(inout) :: range
    integer, intent(in) :: i
    real(default) :: rval, x
    select case (range%step_mode)
    case (STEP_NONE)

```

```

        rval = range%r_beg
    case (STEP_ADD, STEP_SUB, STEP_COMP_ADD)
        if (range%n_step > 1) then
            x = real (i - 1, default) / (range%n_step - 1)
        else
            x = 1._default / 2
        end if
        rval = x * range%r_end + (1 - x) * range%r_beg
    case (STEP_MUL, STEP_DIV, STEP_COMP_MUL)
        if (range%n_step > 1) then
            x = real (i - 1, default) / (range%n_step - 1)
        else
            x = 1._default / 2
        end if
        rval = sign &
            (exp (x * range%lr_end + (1 - x) * range%lr_beg), range%r_beg)
    case default
        call range%write ()
        call msg_bug ("range iteration: step mode not implemented")
    end select
    call parse_node_set_value (range%pn_literal, rval = rval)
end subroutine range_real_set_value

```

Scan over parameters and other objects

The scan command allocates a new parse node for the variable assignment (the lhs). The rhs of this parse node is assigned from the available rhs expressions in the scan list, one at a time, so the compiled parse node can be prepended to the scan body.

Note: for the integer/real range array, the obvious implementation as a polymorphic array is suspended because in gfortran 4.7, polymorphic arrays are apparently broken.

```

<Commands: types>+≡
type, extends (command_t) :: cmd_scan_t
private
type(string_t) :: name
integer :: n_values = 0
type(parse_node_p), dimension(:), allocatable :: scan_cmd
!!! !!! gfortran 4.7.x memory corruption
!!! class(range_t), dimension(:), allocatable :: range
type(range_int_t), dimension(:), allocatable :: range_int
type(range_real_t), dimension(:), allocatable :: range_real
contains
<Commands: cmd scan: TBP>
end type cmd_scan_t

```

Finalizer.

The auxiliary parse nodes that we have constructed have to be treated carefully: the embedded pointers all point to persistent objects somewhere else and should not be finalized, so we should not call the finalizer recursively.

```

<Commands: cmd scan: TBP>≡

```

```

    procedure :: final => cmd_scan_final
  <Commands: procedures>+≡
    recursive subroutine cmd_scan_final (cmd)
      class(cmd_scan_t), intent(inout) :: cmd
      type(parse_node_t), pointer :: pn_var_single, pn_decl_single
      type(string_t) :: key
      integer :: i
      if (allocated (cmd%scan_cmd)) then
        do i = 1, size (cmd%scan_cmd)
          pn_var_single => parse_node_get_sub_ptr (cmd%scan_cmd(i)%ptr)
          key = parse_node_get_rule_key (pn_var_single)
          select case (char (key))
            case ("scan_string_decl", "scan_log_decl")
              pn_decl_single => parse_node_get_sub_ptr (pn_var_single, 2)
              call parse_node_final (pn_decl_single, recursive=.false.)
              deallocate (pn_decl_single)
            end select
          call parse_node_final (pn_var_single, recursive=.false.)
          deallocate (pn_var_single)
        end do
        deallocate (cmd%scan_cmd)
      end if
      !!! !!! gfortran 4.7.x memory corruption
      !!! if (allocated (cmd%range)) then
      !!!   do i = 1, size (cmd%range)
      !!!     call cmd%range(i)%final ()
      !!!   end do
      !!! end if
      if (allocated (cmd%range_int)) then
        do i = 1, size (cmd%range_int)
          call cmd%range_int(i)%final ()
        end do
      end if
      if (allocated (cmd%range_real)) then
        do i = 1, size (cmd%range_real)
          call cmd%range_real(i)%final ()
        end do
      end if
    end subroutine cmd_scan_final

```

Output.

```

  <Commands: cmd scan: TBP>+≡
    procedure :: write => cmd_scan_write
  <Commands: procedures>+≡
    subroutine cmd_scan_write (cmd, unit, indent)
      class(cmd_scan_t), intent(in) :: cmd
      integer, intent(in), optional :: unit, indent
      integer :: u
      u = given_output_unit (unit); if (u < 0) return
      call write_indent (u, indent)
      write (u, "(1x,A,1x,A,1x,'(',I0,')')") "scan:", char (cmd%name), &
        cmd%n_values
    end subroutine cmd_scan_write

```

Compile the scan command. We construct a new parse node that implements the variable assignment for a single element on the rhs, instead of the whole list that we get from the original parse tree. By simply copying the node, we copy all pointers and inherit the targets from the original. During execution, we should replace the rhs by the stored rhs pointers (the list elements), one by one, then (re)compile the redefined node.

<Commands: cmd scan: TBP>+≡

```
procedure :: compile => cmd_scan_compile
```

<Commands: procedures>+≡

```
recursive subroutine cmd_scan_compile (cmd, global)
  class(cmd_scan_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  type(parse_node_t), pointer :: pn_var, pn_body, pn_body_first
  type(parse_node_t), pointer :: pn_decl, pn_name
  type(parse_node_t), pointer :: pn_arg, pn_scan_cmd, pn_rhs
  type(parse_node_t), pointer :: pn_decl_single, pn_var_single
  type(syntax_rule_t), pointer :: var_rule_decl, var_rule
  type(string_t) :: key
  integer :: var_type
  integer :: i
  logical, parameter :: debug = .false.
  if (debug) then
    print *, "compile scan"
    call parse_node_write_rec (cmd%pn)
  end if
  pn_var => parse_node_get_sub_ptr (cmd%pn, 2)
  pn_body => parse_node_get_next_ptr (pn_var)
  if (associated (pn_body)) then
    pn_body_first => parse_node_get_sub_ptr (pn_body)
  else
    pn_body_first => null ()
  end if
  key = parse_node_get_rule_key (pn_var)
  select case (char (key))
  case ("scan_num")
    pn_name => parse_node_get_sub_ptr (pn_var)
    cmd%name = parse_node_get_string (pn_name)
    var_rule => syntax_get_rule_ptr (syntax_cmd_list, var_str ("cmd_num"))
    pn_arg => parse_node_get_next_ptr (pn_name, 2)
  case ("scan_int")
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    cmd%name = parse_node_get_string (pn_name)
    var_rule => syntax_get_rule_ptr (syntax_cmd_list, var_str ("cmd_int"))
    pn_arg => parse_node_get_next_ptr (pn_name, 2)
  case ("scan_real")
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    cmd%name = parse_node_get_string (pn_name)
    var_rule => syntax_get_rule_ptr (syntax_cmd_list, var_str ("cmd_real"))
    pn_arg => parse_node_get_next_ptr (pn_name, 2)
  case ("scan_complex")
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
```

```

cmd%name = parse_node_get_string (pn_name)
var_rule => syntax_get_rule_ptr (syntax_cmd_list, var_str("cmd_complex"))
pn_arg => parse_node_get_next_ptr (pn_name, 2)
case ("scan_alias")
  pn_name => parse_node_get_sub_ptr (pn_var, 2)
  cmd%name = parse_node_get_string (pn_name)
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, var_str ("cmd_alias"))
  pn_arg => parse_node_get_next_ptr (pn_name, 2)
case ("scan_string_decl")
  pn_decl => parse_node_get_sub_ptr (pn_var, 2)
  pn_name => parse_node_get_sub_ptr (pn_decl, 2)
  cmd%name = parse_node_get_string (pn_name)
  var_rule_decl => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_string"))
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_string_decl"))
  pn_arg => parse_node_get_next_ptr (pn_name, 2)
case ("scan_log_decl")
  pn_decl => parse_node_get_sub_ptr (pn_var, 2)
  pn_name => parse_node_get_sub_ptr (pn_decl, 2)
  cmd%name = parse_node_get_string (pn_name)
  var_rule_decl => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_log"))
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_log_decl"))
  pn_arg => parse_node_get_next_ptr (pn_name, 2)
case ("scan_cuts")
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_cuts"))
  cmd%name = "cuts"
  pn_arg => parse_node_get_sub_ptr (pn_var, 3)
case ("scan_weight")
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_weight"))
  cmd%name = "weight"
  pn_arg => parse_node_get_sub_ptr (pn_var, 3)
case ("scan_scale")
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_scale"))
  cmd%name = "scale"
  pn_arg => parse_node_get_sub_ptr (pn_var, 3)
case ("scan_ren_scale")
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_ren_scale"))
  cmd%name = "renormalization_scale"
  pn_arg => parse_node_get_sub_ptr (pn_var, 3)
case ("scan_fac_scale")
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_fac_scale"))
  cmd%name = "factorization_scale"
  pn_arg => parse_node_get_sub_ptr (pn_var, 3)
case ("scan_selection")
  var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
    var_str ("cmd_selection"))

```

```

        cmd%name = "selection"
        pn_arg => parse_node_get_sub_ptr (pn_var, 3)
    case ("scan_reweight")
        var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
            var_str ("cmd_reweight"))
        cmd%name = "reweight"
        pn_arg => parse_node_get_sub_ptr (pn_var, 3)
    case ("scan_analysis")
        var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
            var_str ("cmd_analysis"))
        cmd%name = "analysis"
        pn_arg => parse_node_get_sub_ptr (pn_var, 3)
    case ("scan_model")
        var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
            var_str ("cmd_model"))
        cmd%name = "model"
        pn_arg => parse_node_get_sub_ptr (pn_var, 3)
    case ("scan_library")
        var_rule => syntax_get_rule_ptr (syntax_cmd_list, &
            var_str ("cmd_library"))
        cmd%name = "library"
        pn_arg => parse_node_get_sub_ptr (pn_var, 3)
    case default
        call msg_bug ("scan: case ' " // char (key) // "' not implemented")
    end select
    if (associated (pn_arg)) then
        cmd%n_values = parse_node_get_n_sub (pn_arg)
    end if
    var_list => global%get_var_list_ptr ()
    allocate (cmd%scan_cmd (cmd%n_values))
    select case (char (key))
    case ("scan_num")
        var_type = &
            var_list%get_type (cmd%name)
        select case (var_type)
        case (V_INT)
            !!! !!! gfortran 4.7.x memory corruption
            !!! allocate (range_int_t :: cmd%range (cmd%n_values))
            allocate (cmd%range_int (cmd%n_values))
        case (V_REAL)
            !!! !!! gfortran 4.7.x memory corruption
            !!! allocate (range_real_t :: cmd%range (cmd%n_values))
            allocate (cmd%range_real (cmd%n_values))
        case (V_CMPLX)
            call msg_fatal ("scan over complex variable not implemented")
        case (V_NONE)
            call msg_fatal ("scan: variable ' " // char (cmd%name) // "' undefined")
        case default
            call msg_bug ("scan: impossible variable type")
        end select
    case ("scan_int")
        !!! !!! gfortran 4.7.x memory corruption
        !!! allocate (range_int_t :: cmd%range (cmd%n_values))
        allocate (cmd%range_int (cmd%n_values))

```

```

case ("scan_real")
  !!! !!! gfortran 4.7.x memory corruption
  !!! allocate (range_real_t :: cmd%range (cmd%n_values))
  allocate (cmd%range_real (cmd%n_values))
case ("scan_complex")
  call msg_fatal ("scan over complex variable not implemented")
end select
i = 1
if (associated (pn_arg)) then
  pn_rhs => parse_node_get_sub_ptr (pn_arg)
else
  pn_rhs => null ()
end if
do while (associated (pn_rhs))
  allocate (pn_scan_cmd)
  call parse_node_create_branch (pn_scan_cmd, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("command_list")))
  allocate (pn_var_single)
  pn_var_single = pn_var
  call parse_node_replace_rule (pn_var_single, var_rule)
  select case (char (key))
  case ("scan_num", "scan_int", "scan_real", &
    "scan_complex", "scan_alias", &
    "scan_cuts", "scan_weight", &
    "scan_scale", "scan_ren_scale", "scan_fac_scale", &
    "scan_selection", "scan_reweight", "scan_analysis", &
    "scan_model", "scan_library")
    if (allocated (cmd%range_int)) then
      call cmd%range_int(i)%init (pn_rhs)
      !!! !!! gfortran 4.7.x memory corruption
      !!! call cmd%range_int(i)%compile (global)
      call parse_node_replace_last_sub &
        (pn_var_single, cmd%range_int(i)%pn_expr)
    else if (allocated (cmd%range_real)) then
      call cmd%range_real(i)%init (pn_rhs)
      !!! !!! gfortran 4.7.x memory corruption
      !!! call cmd%range_real(i)%compile (global)
      call parse_node_replace_last_sub &
        (pn_var_single, cmd%range_real(i)%pn_expr)
    else
      call parse_node_replace_last_sub (pn_var_single, pn_rhs)
    end if
  case ("scan_string_decl", "scan_log_decl")
    allocate (pn_decl_single)
    pn_decl_single = pn_decl
    call parse_node_replace_rule (pn_decl_single, var_rule_decl)
    call parse_node_replace_last_sub (pn_decl_single, pn_rhs)
    call parse_node_freeze_branch (pn_decl_single)
    call parse_node_replace_last_sub (pn_var_single, pn_decl_single)
  case default
    call msg_bug ("scan: case ' ' // char (key) &
      // ' ' broken")
  end select
  call parse_node_freeze_branch (pn_var_single)

```



```

        call parse_node_append_sub (pn_scan_cmd, pn_var_single)
        call parse_node_append_sub (pn_scan_cmd, pn_body_first)
        call parse_node_freeze_branch (pn_scan_cmd)
        cmd%scan_cmd(i)%ptr => pn_scan_cmd
        i = i + 1
        pn_rhs => parse_node_get_next_ptr (pn_rhs)
    end do
    if (debug) then
        do i = 1, cmd%n_values
            print *, "scan command ", i
            call parse_node_write_rec (cmd%scan_cmd(i)%ptr)
            if (allocated (cmd%range_int)) call cmd%range_int(i)%write ()
            if (allocated (cmd%range_real)) call cmd%range_real(i)%write ()
        end do
        print *, "original"
        call parse_node_write_rec (cmd%pn)
    end if
end subroutine cmd_scan_compile

```

Execute the loop for all values in the step list. We use the parse trees with single variable assignment that we have stored, to iteratively create a local environment, execute the stored commands, and destroy it again. When we encounter a range object, we execute the commands for each value that this object provides. Computing this value has the side effect of modifying the rhs of the variable assignment that heads the local command list, directly in the local parse tree.

(Commands: cmd scan: TBP)+≡

```

    procedure :: execute => cmd_scan_execute

```

(Commands: procedures)+≡

```

recursive subroutine cmd_scan_execute (cmd, global)
    class(cmd_scan_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(rt_data_t), allocatable :: local
    integer :: i, j
    do i = 1, cmd%n_values
        if (allocated (cmd%range_int)) then
            call cmd%range_int(i)%compile (global)
            call cmd%range_int(i)%evaluate ()
            do j = 1, cmd%range_int(i)%get_n_iterations ()
                call cmd%range_int(i)%set_value (j)
                allocate (local)
                call build_alt_setup (local, global, cmd%scan_cmd(i)%ptr)
                call local%local_final ()
                deallocate (local)
            end do
        else if (allocated (cmd%range_real)) then
            call cmd%range_real(i)%compile (global)
            call cmd%range_real(i)%evaluate ()
            do j = 1, cmd%range_real(i)%get_n_iterations ()
                call cmd%range_real(i)%set_value (j)
                allocate (local)
                call build_alt_setup (local, global, cmd%scan_cmd(i)%ptr)
                call local%local_final ()
            end do
        end if
    end do
end subroutine cmd_scan_execute

```

```

        deallocate (local)
    end do
else
    allocate (local)
    call build_alt_setup (local, global, cmd%scan_cmd(i)%ptr)
    call local%local_final ()
    deallocate (local)
end if
end do
end subroutine cmd_scan_execute

```

Conditionals

Conditionals are implemented as a list that is compiled and evaluated recursively; this allows for a straightforward representation of `else if` constructs. A `cmd_if_t` object can hold either an `else_if` clause which is another object of this type, or an `else_body`, but not both.

If- or else-bodies are no scoping units, so all data remain global and no copy-in copy-out is needed.

```

<Commands: types>+≡
type, extends (command_t) :: cmd_if_t
private
type(parse_node_t), pointer :: pn_if_lexpr => null ()
type(command_list_t), pointer :: if_body => null ()
type(cmd_if_t), dimension(:), pointer :: elsif_cmd => null ()
type(command_list_t), pointer :: else_body => null ()
contains
<Commands: cmd if: TBP>
end type cmd_if_t

```

Finalizer. There are no local options, therefore we can simply override the default finalizer.

```

<Commands: cmd if: TBP>≡
procedure :: final => cmd_if_final

<Commands: procedures>+≡
recursive subroutine cmd_if_final (cmd)
class(cmd_if_t), intent(inout) :: cmd
integer :: i
if (associated (cmd%if_body)) then
    call command_list_final (cmd%if_body)
    deallocate (cmd%if_body)
end if
if (associated (cmd%elsif_cmd)) then
    do i = 1, size (cmd%elsif_cmd)
        call cmd_if_final (cmd%elsif_cmd(i))
    end do
    deallocate (cmd%elsif_cmd)
end if
if (associated (cmd%else_body)) then
    call command_list_final (cmd%else_body)
    deallocate (cmd%else_body)
end if

```

```

    end if
end subroutine cmd_if_final

```

Output. Recursively write the command lists.

```

<Commands: cmd if: TBP>+≡
  procedure :: write => cmd_if_write

<Commands: procedures>+≡
  subroutine cmd_if_write (cmd, unit, indent)
    class(cmd_if_t), intent(in) :: cmd
    integer, intent(in), optional :: unit, indent
    integer :: u, ind, i
    u = given_output_unit (unit); if (u < 0) return
    ind = 0; if (present (indent)) ind = indent
    call write_indent (u, indent)
    write (u, "(A)") "if <expr> then"
    if (associated (cmd%if_body)) then
      call cmd%if_body%write (unit, ind + 1)
    end if
    if (associated (cmd%elsif_cmd)) then
      do i = 1, size (cmd%elsif_cmd)
        call write_indent (u, indent)
        write (u, "(A)") "elsif <expr> then"
        if (associated (cmd%elsif_cmd(i)%if_body)) then
          call cmd%elsif_cmd(i)%if_body%write (unit, ind + 1)
        end if
      end do
    end if
    if (associated (cmd%else_body)) then
      call write_indent (u, indent)
      write (u, "(A)") "else"
      call cmd%else_body%write (unit, ind + 1)
    end if
  end subroutine cmd_if_write

```

Compile the conditional.

```

<Commands: cmd if: TBP>+≡
  procedure :: compile => cmd_if_compile

<Commands: procedures>+≡
  recursive subroutine cmd_if_compile (cmd, global)
    class(cmd_if_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_lexpr, pn_body
    type(parse_node_t), pointer :: pn_elsif_clauses, pn_cmd_elsif
    type(parse_node_t), pointer :: pn_else_clause, pn_cmd_else
    integer :: i, n_elsif
    pn_lexpr => parse_node_get_sub_ptr (cmd%pn, 2)
    cmd%pn_if_lexpr => pn_lexpr
    pn_body => parse_node_get_next_ptr (pn_lexpr, 2)
    select case (char (parse_node_get_rule_key (pn_body)))
    case ("command_list")
      allocate (cmd%if_body)
      call cmd%if_body%compile (pn_body, global)

```

```

        pn_elseif_clauses => parse_node_get_next_ptr (pn_body)
    case default
        pn_elseif_clauses => pn_body
    end select
select case (char (parse_node_get_rule_key (pn_elseif_clauses)))
case ("elseif_clauses")
    n_elseif = parse_node_get_n_sub (pn_elseif_clauses)
    allocate (cmd%elseif_cmd (n_elseif))
    pn_cmd_elseif => parse_node_get_sub_ptr (pn_elseif_clauses)
    do i = 1, n_elseif
        pn_lexpr => parse_node_get_sub_ptr (pn_cmd_elseif, 2)
        cmd%elseif_cmd(i)%pn_if_lexpr => pn_lexpr
        pn_body => parse_node_get_next_ptr (pn_lexpr, 2)
        if (associated (pn_body)) then
            allocate (cmd%elseif_cmd(i)%if_body)
            call cmd%elseif_cmd(i)%if_body%compile (pn_body, global)
        end if
        pn_cmd_elseif => parse_node_get_next_ptr (pn_cmd_elseif)
    end do
    pn_else_clause => parse_node_get_next_ptr (pn_elseif_clauses)
case default
    pn_else_clause => pn_elseif_clauses
end select
select case (char (parse_node_get_rule_key (pn_else_clause)))
case ("else_clause")
    pn_cmd_else => parse_node_get_sub_ptr (pn_else_clause)
    pn_body => parse_node_get_sub_ptr (pn_cmd_else, 2)
    if (associated (pn_body)) then
        allocate (cmd%else_body)
        call cmd%else_body%compile (pn_body, global)
    end if
end select
end subroutine cmd_if_compile

```

(Recursively) execute the condition. Context remains global in all cases.

(Commands: cmd if: TBP)+≡

```

    procedure :: execute => cmd_if_execute

```

(Commands: procedures)+≡

```

recursive subroutine cmd_if_execute (cmd, global)
    class(cmd_if_t), intent(inout) :: cmd
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), pointer :: var_list
    logical :: lval, is_known
    integer :: i
    var_list => global%get_var_list_ptr ()
    lval = eval_log (cmd%pn_if_lexpr, var_list, is_known=is_known)
    if (is_known) then
        if (lval) then
            if (associated (cmd%if_body)) then
                call cmd%if_body%execute (global)
            end if
            return
        end if
    end if

```

```

else
    call error_undecided ()
    return
end if
if (associated (cmd%elsif_cmd)) then
    SCAN_ELSEIF: do i = 1, size (cmd%elsif_cmd)
        lval = eval_log (cmd%elsif_cmd(i)%pn_if_lexpr, var_list, &
            is_known=is_known)
        if (is_known) then
            if (lval) then
                if (associated (cmd%elsif_cmd(i)%if_body)) then
                    call cmd%elsif_cmd(i)%if_body%execute (global)
                end if
                return
            end if
        else
            call error_undecided ()
            return
        end if
    end do SCAN_ELSEIF
end if
if (associated (cmd%else_body)) then
    call cmd%else_body%execute (global)
end if
contains
    subroutine error_undecided ()
        call msg_error ("Undefined result of conditional expression: " &
            // "neither branch will be executed")
    end subroutine error_undecided
end subroutine cmd_if_execute

```

Include another command-list file

The include command allocates a local parse tree. This must not be deleted before the command object itself is deleted, since pointers may point to subobjects of it.

```

<Commands: types>+≡
    type, extends (command_t) :: cmd_include_t
        private
        type(string_t) :: file
        type(command_list_t), pointer :: command_list => null ()
        type(parse_tree_t) :: parse_tree
    contains
        <Commands: cmd include: TBP>
    end type cmd_include_t

```

Finalizer: delete the command list. No options, so we can simply override the default finalizer.

```

<Commands: cmd include: TBP>≡
    procedure :: final => cmd_include_final

```

```

<Commands: procedures>+≡
subroutine cmd_include_final (cmd)
  class(cmd_include_t), intent(inout) :: cmd
  call parse_tree_final (cmd%parse_tree)
  if (associated (cmd%command_list)) then
    call cmd%command_list%final ()
    deallocate (cmd%command_list)
  end if
end subroutine cmd_include_final

```

Write: display the command list as-is, if allocated.

```

<Commands: cmd include: TBP>+≡
  procedure :: write => cmd_include_write

<Commands: procedures>+≡
subroutine cmd_include_write (cmd, unit, indent)
  class(cmd_include_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u, ind
  u = given_output_unit (unit)
  ind = 0; if (present (indent)) ind = indent
  call write_indent (u, indent)
  write (u, "(A,A,A,A)") "include ", "'", char (cmd%file), "'"
  if (associated (cmd%command_list)) then
    call cmd%command_list%write (u, ind + 1)
  end if
end subroutine cmd_include_write

```

Compile file contents: First parse the file, then immediately compile its contents.
Use the global data set.

```

<Commands: cmd include: TBP>+≡
  procedure :: compile => cmd_include_compile

<Commands: procedures>+≡
subroutine cmd_include_compile (cmd, global)
  class(cmd_include_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_arg, pn_file
  type(string_t) :: file
  logical :: exist
  integer :: u
  type(stream_t), target :: stream
  type(lexer_t) :: lexer
  pn_arg => parse_node_get_sub_ptr (cmd%pn, 2)
  pn_file => parse_node_get_sub_ptr (pn_arg)
  file = parse_node_get_string (pn_file)
  inquire (file=char(file), exist=exist)
  if (exist) then
    cmd%file = file
  else
    cmd%file = global%os_data%whizard_cutspath // "/" // file
    inquire (file=char(cmd%file), exist=exist)
    if (.not. exist) then
      call msg_error ("Include file '" // char (file) // "' not found")
    end if
  end if
end subroutine cmd_include_compile

```

```

        return
    end if
end if
u = free_unit ()
call lexer_init_cmd_list (lexer, global%lexer)
call stream_init (stream, char (cmd%file))
call lexer_assign_stream (lexer, stream)
call parse_tree_init (cmd%parse_tree, syntax_cmd_list, lexer)
call stream_final (stream)
call lexer_final (lexer)
close (u)
allocate (cmd%command_list)
call cmd%command_list%compile (parse_tree_get_root_ptr (cmd%parse_tree), &
    global)
end subroutine cmd_include_compile

```

Execute file contents in the global context.

```

<Commands: cmd include: TBP>+=
    procedure :: execute => cmd_include_execute

<Commands: procedures>+=
    subroutine cmd_include_execute (cmd, global)
        class(cmd_include_t), intent(inout) :: cmd
        type(rt_data_t), intent(inout), target :: global
        if (associated (cmd%command_list)) then
            call msg_message &
                ("Including Sindarin from '" // char (cmd%file) // "'")
            call cmd%command_list%execute (global)
            call msg_message &
                ("End of included '" // char (cmd%file) // "'")
        end if
    end subroutine cmd_include_execute

```

Quit command execution

The code is the return code of the whole program if it is terminated by this command.

```

<Commands: types>+=
    type, extends (command_t) :: cmd_quit_t
        private
        logical :: has_code = .false.
        type(parse_node_t), pointer :: pn_code_expr => null ()
    contains
        <Commands: cmd quit: TBP>
    end type cmd_quit_t

```

Output.

```

<Commands: cmd quit: TBP>=
    procedure :: write => cmd_quit_write

```

```

<Commands: procedures>+≡
subroutine cmd_quit_write (cmd, unit, indent)
  class(cmd_quit_t), intent(in) :: cmd
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = given_output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  write (u, "(1x,A,L1)") "quit: has_code = ", cmd%has_code
end subroutine cmd_quit_write

```

Compile: allocate a quit object which serves as a placeholder.

```

<Commands: cmd quit: TBP>+≡
  procedure :: compile => cmd_quit_compile

<Commands: procedures>+≡
subroutine cmd_quit_compile (cmd, global)
  class(cmd_quit_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_arg
  pn_arg => parse_node_get_sub_ptr (cmd%pn, 2)
  if (associated (pn_arg)) then
    cmd%pn_code_expr => parse_node_get_sub_ptr (pn_arg)
    cmd%has_code = .true.
  end if
end subroutine cmd_quit_compile

```

Execute: The quit command does not execute anything, it just stops command execution. This is achieved by setting quit flag and quit code in the global variable list. However, the return code, if present, is an expression which has to be evaluated.

```

<Commands: cmd quit: TBP>+≡
  procedure :: execute => cmd_quit_execute

<Commands: procedures>+≡
subroutine cmd_quit_execute (cmd, global)
  class(cmd_quit_t), intent(inout) :: cmd
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), pointer :: var_list
  logical :: is_known
  var_list => global%get_var_list_ptr ()
  if (cmd%has_code) then
    global%quit_code = eval_int (cmd%pn_code_expr, var_list, &
      is_known=is_known)
    if (.not. is_known) then
      call msg_error ("Undefined return code of quit/exit command")
    end if
  end if
  global%quit = .true.
end subroutine cmd_quit_execute

```


30.1.6 The command list

The command list holds a list of commands and relevant global data.

```
<Commands: public>+≡
    public :: command_list_t

<Commands: types>+≡
    type :: command_list_t
        ! not private anymore as required by the whizard-c-interface
        class(command_t), pointer :: first => null ()
        class(command_t), pointer :: last => null ()
    contains
        <Commands: command list: TBP>
    end type command_list_t
```

Output.

```
<Commands: command list: TBP>≡
    procedure :: write => command_list_write

<Commands: procedures>+≡
    recursive subroutine command_list_write (cmd_list, unit, indent)
        class(command_list_t), intent(in) :: cmd_list
        integer, intent(in), optional :: unit, indent
        class(command_t), pointer :: cmd
        cmd => cmd_list%first
        do while (associated (cmd))
            call cmd%write (unit, indent)
            cmd => cmd%next
        end do
    end subroutine command_list_write
```

Append a new command to the list and free the original pointer.

```
<Commands: command list: TBP>+≡
    procedure :: append => command_list_append

<Commands: procedures>+≡
    subroutine command_list_append (cmd_list, command)
        class(command_list_t), intent(inout) :: cmd_list
        class(command_t), intent(inout), pointer :: command
        if (associated (cmd_list%last)) then
            cmd_list%last%next => command
        else
            cmd_list%first => command
        end if
        cmd_list%last => command
        command => null ()
    end subroutine command_list_append
```

Finalize.

```
<Commands: command list: TBP>+≡
    procedure :: final => command_list_final
```

```

<Commands: procedures>+≡
recursive subroutine command_list_final (cmd_list)
  class(command_list_t), intent(inout) :: cmd_list
  class(command_t), pointer :: command
  do while (associated (cmd_list%first))
    command => cmd_list%first
    cmd_list%first => cmd_list%first%next
    call command%final ()
    deallocate (command)
  end do
  cmd_list%last => null ()
end subroutine command_list_final

```

30.1.7 Compiling the parse tree

Transform a parse tree into a command list. Initialization is assumed to be done.

After each command, we set a breakpoint.

```

<Commands: command list: TBP>+≡
  procedure :: compile => command_list_compile

<Commands: procedures>+≡
recursive subroutine command_list_compile (cmd_list, pn, global)
  class(command_list_t), intent(inout), target :: cmd_list
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_cmd
  class(command_t), pointer :: command
  integer :: i
  pn_cmd => parse_node_get_sub_ptr (pn)
  do i = 1, parse_node_get_n_sub (pn)
    call dispatch_command (command, pn_cmd)
    call command%compile (global)
    call cmd_list%append (command)
    call terminate_now_if_signal ()
    pn_cmd => parse_node_get_next_ptr (pn_cmd)
  end do
end subroutine command_list_compile

```

30.1.8 Executing the command list

Before executing a command we should execute its options (if any). After that, reset the options, i.e., remove temporary effects from the global state.

Also here, after each command we set a breakpoint.

```

<Commands: command list: TBP>+≡
  procedure :: execute => command_list_execute

<Commands: procedures>+≡
recursive subroutine command_list_execute (cmd_list, global)
  class(command_list_t), intent(in) :: cmd_list
  type(rt_data_t), intent(inout), target :: global

```

```

class(command_t), pointer :: command
command => cmd_list%first
COMMAND_COND: do while (associated (command))
    call command%execute_options (global)
    call command%execute (global)
    call command%reset_options (global)
    call terminate_now_if_signal ()
    if (global%quit) exit COMMAND_COND
    command => command%next
end do COMMAND_COND
end subroutine command_list_execute

```

30.1.9 Command list syntax

```

<Commands: public>+≡
    public :: syntax_cmd_list

<Commands: variables>≡
    type(syntax_t), target, save :: syntax_cmd_list

<Commands: public>+≡
    public :: syntax_cmd_list_init

<Commands: procedures>+≡
    subroutine syntax_cmd_list_init ()
        type(ifile_t) :: ifile
        call define_cmd_list_syntax (ifile)
        call syntax_init (syntax_cmd_list, ifile)
        call ifile_final (ifile)
    end subroutine syntax_cmd_list_init

<Commands: public>+≡
    public :: syntax_cmd_list_final

<Commands: procedures>+≡
    subroutine syntax_cmd_list_final ()
        call syntax_final (syntax_cmd_list)
    end subroutine syntax_cmd_list_final

<Commands: public>+≡
    public :: syntax_cmd_list_write

<Commands: procedures>+≡
    subroutine syntax_cmd_list_write (unit)
        integer, intent(in), optional :: unit
        call syntax_write (syntax_cmd_list, unit)
    end subroutine syntax_cmd_list_write

<Commands: procedures>+≡
    subroutine define_cmd_list_syntax (ifile)
        type(ifile_t), intent(inout) :: ifile
        call ifile_append (ifile, "SEQ command_list = command*")
        call ifile_append (ifile, "ALT command = " &

```

```

// "cmd_model | cmd_library | cmd_iterations | cmd_sample_format | " &
// "cmd_var | cmd_slha | " &
// "cmd_show | cmd_clear | " &
// "cmd_expect | " &
// "cmd_cuts | cmd_scale | cmd_fac_scale | cmd_ren_scale | " &
// "cmd_weight | cmd_selection | cmd_reweight | " &
// "cmd_beams | cmd_beams_pol_density | cmd_beams_pol_fraction | " &
// "cmd_beams_momentum | cmd_beams_theta | cmd_beams_phi | " &
// "cmd_integrate | " &
// "cmd_observable | cmd_histogram | cmd_plot | cmd_graph | " &
// "cmd_record | " &
// "cmd_analysis | cmd_alt_setup | " &
// "cmd_unstable | cmd_stable | cmd_simulate | cmd_rescan | " &
// "cmd_process | cmd_compile | cmd_exec | " &
// "cmd_scan | cmd_if | cmd_include | cmd_quit | " &
// "cmd_polarized | cmd_unpolarized | " &
// "cmd_open_out | cmd_close_out | cmd_printf | " &
// "cmd_write_analysis | cmd_compile_analysis | cmd_nlo | cmd_components")
call ifile_append (ifile, "GRO options = '{' local_command_list '}'")
call ifile_append (ifile, "SEQ local_command_list = local_command*")
call ifile_append (ifile, "ALT local_command = " &
// "cmd_model | cmd_library | cmd_iterations | cmd_sample_format | " &
// "cmd_var | cmd_slha | " &
// "cmd_show | " &
// "cmd_expect | " &
// "cmd_cuts | cmd_scale | cmd_fac_scale | cmd_ren_scale | " &
// "cmd_weight | cmd_selection | cmd_reweight | " &
// "cmd_beams | cmd_beams_pol_density | cmd_beams_pol_fraction | " &
// "cmd_beams_momentum | cmd_beams_theta | cmd_beams_phi | " &
// "cmd_observable | cmd_histogram | cmd_plot | cmd_graph | " &
// "cmd_clear | cmd_record | " &
// "cmd_analysis | cmd_alt_setup | " &
// "cmd_open_out | cmd_close_out | cmd_printf | " &
// "cmd_write_analysis | cmd_compile_analysis | cmd_nlo | cmd_components")
call ifile_append (ifile, "SEQ cmd_model = model '=' model_name")
call ifile_append (ifile, "KEY model")
call ifile_append (ifile, "ALT model_name = model_id | string_literal")
call ifile_append (ifile, "IDE model_id")
call ifile_append (ifile, "SEQ cmd_library = library '=' lib_name")
call ifile_append (ifile, "KEY library")
call ifile_append (ifile, "ALT lib_name = lib_id | string_literal")
call ifile_append (ifile, "IDE lib_id")
call ifile_append (ifile, "ALT cmd_var = " &
// "cmd_log_decl | cmd_log | " &
// "cmd_int | cmd_real | cmd_complex | cmd_num | " &
// "cmd_string_decl | cmd_string | cmd_alias | " &
// "cmd_result")
call ifile_append (ifile, "SEQ cmd_log_decl = logical cmd_log")
call ifile_append (ifile, "SEQ cmd_log = '?' var_name '=' lexpr")
call ifile_append (ifile, "SEQ cmd_int = int var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_real = real var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_complex = complex var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_num = var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_string_decl = string cmd_string")

```

```

call ifile_append (ifile, "SEQ cmd_string = " &
// '$' var_name '=' sexpr") ! $
call ifile_append (ifile, "SEQ cmd_alias = alias var_name '=' cexpr")
call ifile_append (ifile, "SEQ cmd_result = result '=' expr")
call ifile_append (ifile, "SEQ cmd_slha = slha_action slha_arg options?")
call ifile_append (ifile, "ALT slha_action = " &
// "read_slha | write_slha")
call ifile_append (ifile, "KEY read_slha")
call ifile_append (ifile, "KEY write_slha")
call ifile_append (ifile, "ARG slha_arg = ( string_literal )")
call ifile_append (ifile, "SEQ cmd_show = show show_arg options?")
call ifile_append (ifile, "KEY show")
call ifile_append (ifile, "ARG show_arg = ( showable* )")
call ifile_append (ifile, "ALT showable = " &
// "model | library | beams | iterations | " &
// "cuts | weight | logical | string | pdg | " &
// "scale | factorization_scale | renormalization_scale | " &
// "selection | reweight | analysis | " &
// "stable | unstable | polarized | unpolarized | " &
// "expect | intrinsic | int | real | complex | " &
// "alias_var | string | results | result_var | " &
// "log_var | string_var | var_name")
call ifile_append (ifile, "KEY results")
call ifile_append (ifile, "KEY intrinsic")
call ifile_append (ifile, "SEQ alias_var = alias var_name")
call ifile_append (ifile, "SEQ result_var = result_key result_arg?")
call ifile_append (ifile, "SEQ log_var = '?' var_name")
call ifile_append (ifile, "SEQ string_var = '$' var_name") ! $
call ifile_append (ifile, "SEQ cmd_clear = clear clear_arg options?")
call ifile_append (ifile, "KEY clear")
call ifile_append (ifile, "ARG clear_arg = ( clearable* )")
call ifile_append (ifile, "ALT clearable = " &
// "beams | iterations | " &
// "cuts | weight | " &
// "scale | factorization_scale | renormalization_scale | " &
// "selection | reweight | analysis | " &
// "unstable | polarized | " &
// "expect | " &
// "log_var | string_var | var_name")
call ifile_append (ifile, "SEQ cmd_expect = expect expect_arg options?")
call ifile_append (ifile, "KEY expect")
call ifile_append (ifile, "ARG expect_arg = ( lexpr )")
call ifile_append (ifile, "SEQ cmd_cuts = cuts '=' lexpr")
call ifile_append (ifile, "SEQ cmd_scale = scale '=' expr")
call ifile_append (ifile, "SEQ cmd_fac_scale = " &
// "factorization_scale '=' expr")
call ifile_append (ifile, "SEQ cmd_ren_scale = " &
// "renormalization_scale '=' expr")
call ifile_append (ifile, "SEQ cmd_weight = weight '=' expr")
call ifile_append (ifile, "SEQ cmd_selection = selection '=' lexpr")
call ifile_append (ifile, "SEQ cmd_reweight = reweight '=' expr")
call ifile_append (ifile, "KEY cuts")
call ifile_append (ifile, "KEY scale")
call ifile_append (ifile, "KEY factorization_scale")

```

```

call ifile_append (ifile, "KEY renormalization_scale")
call ifile_append (ifile, "KEY weight")
call ifile_append (ifile, "KEY selection")
call ifile_append (ifile, "KEY reweight")
call ifile_append (ifile, "SEQ cmd_process = process process_id '=' " &
    // "process_prt '>' prt_state_list options?")
call ifile_append (ifile, "KEY process")
call ifile_append (ifile, "KEY '>'"")
call ifile_append (ifile, "LIS process_prt = cexpr+")
call ifile_append (ifile, "LIS prt_state_list = prt_state_sum+")
call ifile_append (ifile, "SEQ prt_state_sum = " &
    // "prt_state prt_state_addition*")
call ifile_append (ifile, "SEQ prt_state_addition = '+' prt_state")
call ifile_append (ifile, "ALT prt_state = grouped_prt_state_list | cexpr")
call ifile_append (ifile, "GRO grouped_prt_state_list = " &
    // "( prt_state_list )")
call ifile_append (ifile, "SEQ cmd_compile = compile_cmd options?")
call ifile_append (ifile, "SEQ compile_cmd = compile_clause compile_arg?")
call ifile_append (ifile, "SEQ compile_clause = compile_exec_name_spec?")
call ifile_append (ifile, "KEY compile")
call ifile_append (ifile, "SEQ exec_name_spec = as exec_name")
call ifile_append (ifile, "KEY as")
call ifile_append (ifile, "ALT exec_name = exec_id | string_literal")
call ifile_append (ifile, "IDE exec_id")
call ifile_append (ifile, "ARG compile_arg = ( lib_name* )")
call ifile_append (ifile, "SEQ cmd_exec = exec exec_arg")
call ifile_append (ifile, "KEY exec")
call ifile_append (ifile, "ARG exec_arg = ( sexpr )")
call ifile_append (ifile, "SEQ cmd_beams = beams '=' beam_def")
call ifile_append (ifile, "KEY beams")
call ifile_append (ifile, "SEQ beam_def = beam_spec strfun_seq*")
call ifile_append (ifile, "SEQ beam_spec = beam_list")
call ifile_append (ifile, "LIS beam_list = cexpr, cexpr?")
call ifile_append (ifile, "SEQ cmd_beams_pol_density = " &
    // "beams_pol_density '=' beams_pol_spec")
call ifile_append (ifile, "KEY beams_pol_density")
call ifile_append (ifile, "LIS beams_pol_spec = smatrix, smatrix?")
call ifile_append (ifile, "SEQ smatrix = '@' smatrix_arg")
! call ifile_append (ifile, "KEY '@'")      !!! Key already exists
call ifile_append (ifile, "ARG smatrix_arg = ( sentry* )")
call ifile_append (ifile, "SEQ sentry = expr extra_sentry*")
call ifile_append (ifile, "SEQ extra_sentry = ':' expr")
call ifile_append (ifile, "SEQ cmd_beams_pol_fraction = " &
    // "beams_pol_fraction '=' beams_par_spec")
call ifile_append (ifile, "KEY beams_pol_fraction")
call ifile_append (ifile, "SEQ cmd_beams_momentum = " &
    // "beams_momentum '=' beams_par_spec")
call ifile_append (ifile, "KEY beams_momentum")
call ifile_append (ifile, "SEQ cmd_beams_theta = " &
    // "beams_theta '=' beams_par_spec")
call ifile_append (ifile, "KEY beams_theta")
call ifile_append (ifile, "SEQ cmd_beams_phi = " &
    // "beams_phi '=' beams_par_spec")
call ifile_append (ifile, "KEY beams_phi")

```

```

call ifile_append (ifile, "LIS beams_par_spec = expr, expr?")
call ifile_append (ifile, "SEQ strfun_seq = '>' strfun_pair")
call ifile_append (ifile, "LIS strfun_pair = strfun_def, strfun_def?")
call ifile_append (ifile, "SEQ strfun_def = strfun_id")
call ifile_append (ifile, "ALT strfun_id = " &
    // "none | lhpdf | lhpdf_photon | pdf_builtin | pdf_builtin_photon | " &
    // "isr | epa | ewa | circe1 | circe2 | energy_scan | " &
    // "beam_events | user_sf_spec")
call ifile_append (ifile, "KEY none")
call ifile_append (ifile, "KEY lhpdf")
call ifile_append (ifile, "KEY lhpdf_photon")
call ifile_append (ifile, "KEY pdf_builtin")
call ifile_append (ifile, "KEY pdf_builtin_photon")
call ifile_append (ifile, "KEY isr")
call ifile_append (ifile, "KEY epa")
call ifile_append (ifile, "KEY ewa")
call ifile_append (ifile, "KEY circe1")
call ifile_append (ifile, "KEY circe2")
call ifile_append (ifile, "KEY energy_scan")
call ifile_append (ifile, "KEY beam_events")
call ifile_append (ifile, "SEQ user_sf_spec = user_strfun user_arg")
call ifile_append (ifile, "KEY user_strfun")
call ifile_append (ifile, "SEQ cmd_integrate = " &
    // "integrate proc_arg options?")
call ifile_append (ifile, "KEY integrate")
call ifile_append (ifile, "ARG proc_arg = ( proc_id* )")
call ifile_append (ifile, "IDE proc_id")
call ifile_append (ifile, "SEQ cmd_iterations = " &
    // "iterations '=' iterations_list")
call ifile_append (ifile, "KEY iterations")
call ifile_append (ifile, "LIS iterations_list = iterations_spec+")
call ifile_append (ifile, "ALT iterations_spec = it_spec")
call ifile_append (ifile, "SEQ it_spec = expr calls_spec adapt_spec?")
call ifile_append (ifile, "SEQ calls_spec = ':' expr")
call ifile_append (ifile, "SEQ adapt_spec = ':' sexpr")
call ifile_append (ifile, "SEQ cmd_components = " &
    // "active '=' component_list")
call ifile_append (ifile, "KEY active")
call ifile_append (ifile, "LIS component_list = sexpr+")
call ifile_append (ifile, "SEQ cmd_sample_format = " &
    // "sample_format '=' event_format_list")
call ifile_append (ifile, "KEY sample_format")
call ifile_append (ifile, "LIS event_format_list = event_format+")
call ifile_append (ifile, "IDE event_format")
call ifile_append (ifile, "SEQ cmd_observable = " &
    // "observable analysis_tag options?")
call ifile_append (ifile, "KEY observable")
call ifile_append (ifile, "SEQ cmd_histogram = " &
    // "histogram analysis_tag histogram_arg " &
    // "options?")
call ifile_append (ifile, "KEY histogram")
call ifile_append (ifile, "ARG histogram_arg = (expr, expr, expr?)")
call ifile_append (ifile, "SEQ cmd_plot = plot analysis_tag options?")
call ifile_append (ifile, "KEY plot")

```

```

call ifile_append (ifile, "SEQ cmd_graph = graph graph_term '=' graph_def")
call ifile_append (ifile, "KEY graph")
call ifile_append (ifile, "SEQ graph_term = analysis_tag options?")
call ifile_append (ifile, "SEQ graph_def = graph_term graph_append*")
call ifile_append (ifile, "SEQ graph_append = '&' graph_term")
call ifile_append (ifile, "SEQ cmd_analysis = analysis '=' lexpr")
call ifile_append (ifile, "KEY analysis")
call ifile_append (ifile, "SEQ cmd_alt_setup = " &
    // "alt_setup '=' option_list_expr")
call ifile_append (ifile, "KEY alt_setup")
call ifile_append (ifile, "ALT option_list_expr = " &
    // "grouped_option_list | option_list")
call ifile_append (ifile, "GRO grouped_option_list = ( option_list_expr )")
call ifile_append (ifile, "LIS option_list = options+")
call ifile_append (ifile, "SEQ cmd_open_out = open_out open_arg options?")
call ifile_append (ifile, "SEQ cmd_close_out = close_out open_arg options?")
call ifile_append (ifile, "KEY open_out")
call ifile_append (ifile, "KEY close_out")
call ifile_append (ifile, "ARG open_arg = (sexpr)")
call ifile_append (ifile, "SEQ cmd_printf = printf_cmd options?")
call ifile_append (ifile, "SEQ printf_cmd = printf_clause sprintf_args?")
call ifile_append (ifile, "SEQ printf_clause = printf sexpr")
call ifile_append (ifile, "KEY printf")
call ifile_append (ifile, "SEQ cmd_record = record_cmd")
call ifile_append (ifile, "SEQ cmd_unstable = " &
    // "unstable cexpr unstable_arg options?")
call ifile_append (ifile, "KEY unstable")
call ifile_append (ifile, "ARG unstable_arg = ( proc_id* )")
call ifile_append (ifile, "SEQ cmd_stable = stable stable_list options?")
call ifile_append (ifile, "KEY stable")
call ifile_append (ifile, "LIS stable_list = cexpr+")
call ifile_append (ifile, "KEY polarized")
call ifile_append (ifile, "SEQ cmd_polarized = polarized polarized_list options?")
call ifile_append (ifile, "LIS polarized_list = cexpr+")
call ifile_append (ifile, "KEY unpolarized")
call ifile_append (ifile, "SEQ cmd_unpolarized = unpolarized unpolarized_list options?")
call ifile_append (ifile, "LIS unpolarized_list = cexpr+")
call ifile_append (ifile, "SEQ cmd_simulate = " &
    // "simulate proc_arg options?")
call ifile_append (ifile, "KEY simulate")
call ifile_append (ifile, "SEQ cmd_rescan = " &
    // "rescan sexpr proc_arg options?")
call ifile_append (ifile, "KEY rescan")
call ifile_append (ifile, "SEQ cmd_scan = scan scan_var scan_body?")
call ifile_append (ifile, "KEY scan")
call ifile_append (ifile, "ALT scan_var = " &
    // "scan_log_decl | scan_log | " &
    // "scan_int | scan_real | scan_complex | scan_num | " &
    // "scan_string_decl | scan_string | scan_alias | " &
    // "scan_cuts | scan_weight | " &
    // "scan_scale | scan_ren_scale | scan_fac_scale | " &
    // "scan_selection | scan_reweight | scan_analysis | " &
    // "scan_model | scan_library")
call ifile_append (ifile, "SEQ scan_log_decl = logical scan_log")

```



```

call ifile_append (ifile, "SEQ scan_log = '?' var_name '=' scan_log_arg")
call ifile_append (ifile, "ARG scan_log_arg = ( lexpr* )")
call ifile_append (ifile, "SEQ scan_int = int var_name '=' scan_num_arg")
call ifile_append (ifile, "SEQ scan_real = real var_name '=' scan_num_arg")
call ifile_append (ifile, "SEQ scan_complex = " &
// "complex var_name '=' scan_num_arg")
call ifile_append (ifile, "SEQ scan_num = var_name '=' scan_num_arg")
call ifile_append (ifile, "ARG scan_num_arg = ( range* )")
call ifile_append (ifile, "ALT range = grouped_range | range_expr")
call ifile_append (ifile, "GRO grouped_range = ( range_expr )")
call ifile_append (ifile, "SEQ range_expr = expr range_spec?")
call ifile_append (ifile, "SEQ range_spec = '>' expr step_spec?")
call ifile_append (ifile, "SEQ step_spec = step_op expr")
call ifile_append (ifile, "ALT step_op = " &
// "'/' | '/'- | '/'* | '/'/' | '/+/' | '/*/'")
call ifile_append (ifile, "KEY '/'")
call ifile_append (ifile, "KEY '/'-")
call ifile_append (ifile, "KEY '/'*")
call ifile_append (ifile, "KEY '/'/'")
call ifile_append (ifile, "KEY '/+/'")
call ifile_append (ifile, "KEY '/*/'")
call ifile_append (ifile, "SEQ scan_string_decl = string scan_string")
call ifile_append (ifile, "SEQ scan_string = " &
// "'$' var_name '=' scan_string_arg")
call ifile_append (ifile, "ARG scan_string_arg = ( sexpr* )")
call ifile_append (ifile, "SEQ scan_alias = " &
// "alias var_name '=' scan_alias_arg")
call ifile_append (ifile, "ARG scan_alias_arg = ( cexpr* )")
call ifile_append (ifile, "SEQ scan_cuts = cuts '=' scan_lexpr_arg")
call ifile_append (ifile, "ARG scan_lexpr_arg = ( lexpr* )")
call ifile_append (ifile, "SEQ scan_scale = scale '=' scan_expr_arg")
call ifile_append (ifile, "ARG scan_expr_arg = ( expr* )")
call ifile_append (ifile, "SEQ scan_fac_scale = " &
// "factorization_scale '=' scan_expr_arg")
call ifile_append (ifile, "SEQ scan_ren_scale = " &
// "renormalization_scale '=' scan_expr_arg")
call ifile_append (ifile, "SEQ scan_weight = weight '=' scan_expr_arg")
call ifile_append (ifile, "SEQ scan_selection = selection '=' scan_lexpr_arg")
call ifile_append (ifile, "SEQ scan_reweight = reweight '=' scan_expr_arg")
call ifile_append (ifile, "SEQ scan_analysis = analysis '=' scan_lexpr_arg")
call ifile_append (ifile, "SEQ scan_model = model '=' scan_model_arg")
call ifile_append (ifile, "ARG scan_model_arg = ( model_name* )")
call ifile_append (ifile, "SEQ scan_library = library '=' scan_library_arg")
call ifile_append (ifile, "ARG scan_library_arg = ( lib_name* )")
call ifile_append (ifile, "GRO scan_body = '{' command_list '}'")
call ifile_append (ifile, "SEQ cmd_if = " &
// "if lexpr then command_list elsif_clauses else_clause endif")
call ifile_append (ifile, "SEQ elsif_clauses = cmd_elseif*")
call ifile_append (ifile, "SEQ cmd_elseif = elsif lexpr then command_list")
call ifile_append (ifile, "SEQ else_clause = cmd_else?")
call ifile_append (ifile, "SEQ cmd_else = else command_list")
call ifile_append (ifile, "SEQ cmd_include = include include_arg")
call ifile_append (ifile, "KEY include")
call ifile_append (ifile, "ARG include_arg = ( string_literal )")

```

```

call ifile_append (ifile, "SEQ cmd_quit = quit_cmd quit_arg?")
call ifile_append (ifile, "ALT quit_cmd = quit | exit")
call ifile_append (ifile, "KEY quit")
call ifile_append (ifile, "KEY exit")
call ifile_append (ifile, "ARG quit_arg = ( expr )")
call ifile_append (ifile, "SEQ cmd_write_analysis = " &
// "write_analysis_clause options?")
call ifile_append (ifile, "SEQ cmd_compile_analysis = " &
// "compile_analysis_clause options?")
call ifile_append (ifile, "SEQ write_analysis_clause = " &
// "write_analysis write_analysis_arg?")
call ifile_append (ifile, "SEQ compile_analysis_clause = " &
// "compile_analysis write_analysis_arg?")
call ifile_append (ifile, "KEY write_analysis")
call ifile_append (ifile, "KEY compile_analysis")
call ifile_append (ifile, "ARG write_analysis_arg = ( analysis_tag* )")
call ifile_append (ifile, "SEQ cmd_nlo = " &
// "nlo_calculation '=' nlo_calculation_list")
call ifile_append (ifile, "KEY nlo_calculation")
call ifile_append (ifile, "LIS nlo_calculation_list = sexpr ',' sexpr ',' sexpr")
call define_expr_syntax (ifile, particles=.true., analysis=.true.)
end subroutine define_cmd_list_syntax

```

<Commands: public>+≡

```
public :: lexer_init_cmd_list
```

<Commands: procedures>+≡

```

subroutine lexer_init_cmd_list (lexer, parent_lexer)
  type(lexer_t), intent(out) :: lexer
  type(lexer_t), intent(in), optional, target :: parent_lexer
  call lexer_init (lexer, &
    comment_chars = "#!", &
    quote_chars = "'", &
    quote_match = '"', &
    single_chars = "()[]{}.,;:&%?@$", &
    special_class = [ "+-*/^", "<>=~ " ], &
    keyword_list = syntax_get_keyword_list_ptr (syntax_cmd_list), &
    parent = parent_lexer)
end subroutine lexer_init_cmd_list

```

30.1.10 Unit Tests

<Commands: public>+≡

```
public :: commands_test
```

<Commands: tests>≡

```

subroutine commands_test (u, results)
  integer, intent(in) :: u
  type(test_results_t), intent(inout) :: results
<Commands: execute tests>
end subroutine commands_test

```

Prepare Sindarin code

This routine parses an internal file, prints the parse tree, and returns a parse node to the root. We use the routine in the tests below.

```
<Commands: tests>+≡
  subroutine parse_ifile (ifile, pn_root, u)
    type(ifile_t), intent(in) :: ifile
    type(parse_node_t), pointer, intent(out) :: pn_root
    integer, intent(in), optional :: u
    type(stream_t), target :: stream
    type(lexer_t), target :: lexer
    type(parse_tree_t) :: parse_tree

    call lexer_init_cmd_list (lexer)
    call stream_init (stream, ifile)
    call lexer_assign_stream (lexer, stream)

    call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
    if (present (u)) call parse_tree_write (parse_tree, u)
    pn_root => parse_tree_get_root_ptr (parse_tree)

    call stream_final (stream)
    call lexer_final (lexer)
  end subroutine parse_ifile
```

Empty command list

Compile and execute an empty command list. Should do nothing but test the integrity of the workflow.

```
<Commands: execute tests>≡
  call test (commands_1, "commands_1", &
    "empty command list", &
    u, results)

<Commands: tests>+≡
  subroutine commands_1 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root

    write (u, "(A)")  "* Test output: commands_1"
    write (u, "(A)")  "*   Purpose: compile and execute empty command list"
    write (u, "(A)")

    write (u, "(A)")  "*   Initialization"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call global%global_init ()

    write (u, "(A)")  "*   Parse empty file"
```

```

write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"

if (associated (pn_root)) then
  call command_list%compile (pn_root, global)
end if

write (u, "(A)")
write (u, "(A)")  "* Execute command list"

call global%activate ()
call command_list%execute (global)
call global%deactivate ()

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call syntax_cmd_list_final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_1"

end subroutine commands_1

```

Read model

Execute a model assignment.

```

<Commands: execute tests>+≡
  call test (commands_2, "commands_2", &
    "model", &
    u, results)

<Commands: tests>+≡
subroutine commands_2 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_2"
  write (u, "(A)")  "* Purpose: set model"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization"

```

```

write (u, "(A)")

call syntax_cmd_list_init ()
call syntax_model_file_init ()
call global%global_init ()

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'model = "Test"')

call ifile_write (ifile, u)

write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_2"

end subroutine commands_2

```

Declare Process

Read a model, then declare a process. The process library is allocated explicitly. For the process definition, We take the default (*omega*) method. Since we do not compile, O'MEGA is not actually called.

```

(Commands: execute tests)+≡
call test (commands_3, "commands_3", &

```

```

        "process declaration", &
        u, results)
    {Commands: tests}+≡
    subroutine commands_3 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root
        type(prclib_entry_t), pointer :: lib

        write (u, "(A)")  "* Test output: commands_3"
        write (u, "(A)")  "*   Purpose: define process"
        write (u, "(A)")

        write (u, "(A)")  "*   Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call syntax_model_file_init ()
        call global%global_init ()
        call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
            .false., is_known = .true.)

        allocate (lib)
        call lib%init (var_str ("lib_cmd3"))
        call global%add_prclib (lib)

        write (u, "(A)")  "*   Input file"
        write (u, "(A)")

        call ifile_append (ifile, 'model = "Test"')
        call ifile_append (ifile, 'process t3 = s, s => s, s')

        call ifile_write (ifile, u)

        write (u, "(A)")
        write (u, "(A)")  "*   Parse file"
        write (u, "(A)")

        call parse_ifile (ifile, pn_root, u)

        write (u, "(A)")
        write (u, "(A)")  "* Compile command list"
        write (u, "(A)")

        call command_list%compile (pn_root, global)
        call command_list%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Execute command list"
        write (u, "(A)")

        call command_list%execute (global)

```

```

call global%prclib_stack%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_3"

end subroutine commands_3

```

Compile Process

Read a model, then declare a process and compile the library. The process library is allocated explicitly. For the process definition, We take the default (`unit_test`) method. There is no external code, so compilation of the library is merely a formal status change.

```

(Commands: execute tests)+≡
  call test (commands_4, "commands_4", &
    "compilation", &
    u, results)

(Commands: tests)+≡
  subroutine commands_4 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    type(prclib_entry_t), pointer :: lib

    write (u, "(A)")  "* Test output: commands_4"
    write (u, "(A)")  "* Purpose: define process and compile library"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call syntax_model_file_init ()
    call global%global_init ()
    call var_list_set_string (global%var_list, var_str ("method"), &
      var_str ("unit_test"), is_known=.true.)

    allocate (lib)
    call lib%init (var_str ("lib_cmd4"))

```

```

call global%add_prclib (lib)

write (u, "(A)")  "*  Input file"
write (u, "(A)")

call ifile_append (ifile, 'model = "Test"')
call ifile_append (ifile, 'process t4 = s, s => s, s')
call ifile_append (ifile, 'compile ("lib_cmd4")')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "*  Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%prclib_stack%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_4"

end subroutine commands_4

```

Integrate Process

Read a model, then declare a process, compile the library, and integrate over phase space. We take the default (`unit_test`) method and use the simplest methods of phase-space parameterization and integration.


```

<Commands: execute tests>+=
    call test (commands_5, "commands_5", &
        "integration", &
        u, results)

<Commands: tests>+=
    subroutine commands_5 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root
        type(prclib_entry_t), pointer :: lib

        write (u, "(A)")  "* Test output: commands_5"
        write (u, "(A)")  "* Purpose: define process, iterations, and integrate"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call syntax_model_file_init ()
        call global%global_init ()
        call var_list_set_string (global%var_list, var_str ("$method"), &
            var_str ("unit_test"), is_known=.true.)
        call var_list_set_string (global%var_list, var_str ("$phs_method"), &
            var_str ("single"), is_known=.true.)
        call var_list_set_string (global%var_list, var_str ("$integration_method"), &
            var_str ("midpoint"), is_known=.true.)
        call var_list_set_log (global%var_list, var_str ("?vis_history"), &
            .false., is_known=.true.)
        call var_list_set_log (global%var_list, var_str ("?integration_timer"), &
            .false., is_known = .true.)
        call var_list_set_real (global%var_list, var_str ("sqrts"), &
            1000._default, is_known=.true.)
        call var_list_set_int (global%var_list, var_str ("seed"), &
            0, is_known=.true.)

        allocate (lib)
        call lib%init (var_str ("lib_cmd5"))
        call global%add_prclib (lib)

        write (u, "(A)")  "* Input file"
        write (u, "(A)")

        call ifile_append (ifile, 'model = "Test"')
        call ifile_append (ifile, 'process t5 = s, s => s, s')
        call ifile_append (ifile, 'compile')
        call ifile_append (ifile, 'iterations = 1:1000')
        call ifile_append (ifile, 'integrate (t5)')

        call ifile_write (ifile, u)

        write (u, "(A)")

```

```

write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call reset_interaction_counter ()
call command_list%execute (global)

call global%it_list%write (u)
write (u, "(A)")
call global%process_stack%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_5"

end subroutine commands_5

```

Variables

Set intrinsic and user-defined variables.

```

<Commands: execute tests>+≡
  call test (commands_6, "commands_6", &
    "variables", &
    u, results)

<Commands: tests>+≡
  subroutine commands_6 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root

```

```

write (u, "(A)")  "* Test output: commands_6"
write (u, "(A)")  "* Purpose: define and set variables"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call global%global_init ()
call global%write_vars (u, [ &
    var_str ("run_id"), &
    var_str ("?unweighted"), &
    var_str ("sqrts")])

write (u, "(A)")
write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, '$run_id = "run1"')
call ifile_append (ifile, '?unweighted = false')
call ifile_append (ifile, 'sqrts = 1000')
call ifile_append (ifile, 'int j = 10')
call ifile_append (ifile, 'real x = 1000.')
call ifile_append (ifile, 'complex z = 5')
call ifile_append (ifile, 'string $text = "abcd"')
call ifile_append (ifile, 'logical ?flag = true')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write_vars (u, [ &
    var_str ("run_id"), &
    var_str ("?unweighted"), &
    var_str ("sqrts"), &
    var_str ("j"), &

```

```

        var_str ("x"), &
        var_str ("z"), &
        var_str ("$text"), &
        var_str ("?flag"]])

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call syntax_cmd_list_final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_6"

end subroutine commands_6

```

Process library

Open process libraries explicitly.

```

(Commands: execute tests) +=
    call test (commands_7, "commands_7", &
        "process library", &
        u, results)

(Commands: tests) +=
    subroutine commands_7 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root

        write (u, "(A)")  "* Test output: commands_7"
        write (u, "(A)")  "* Purpose: declare process libraries"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call global%global_init ()
        call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
            .false., is_known = .true.)
        global%os_data%fc = "Fortran-compiler"
        global%os_data%fcflags = "Fortran-flags"

        write (u, "(A)")
        write (u, "(A)")  "* Input file"
        write (u, "(A)")

```

```

call ifile_append (ifile, 'library = "lib_cmd7_1"')
call ifile_append (ifile, 'library = "lib_cmd7_2"')
call ifile_append (ifile, 'library = "lib_cmd7_1"')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write_libraries (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call syntax_cmd_list_final ()
call global%final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_7"

end subroutine commands_7

```

Generate events

Read a model, then declare a process, compile the library, and generate weighted events. We take the default (`unit_test`) method and use the simplest methods of phase-space parameterization and integration.

```

(Commands: execute tests) +=
  call test (commands_8, "commands_8", &
    "event generation", &
    u, results)

```

```

{Commands: tests}+≡
subroutine commands_8 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root
  type(prclib_entry_t), pointer :: lib

  write (u, "(A)")  "* Test output: commands_8"
  write (u, "(A)")  "* Purpose: define process, integrate, generate events"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization"
  write (u, "(A)")

  call syntax_cmd_list_init ()
  call syntax_model_file_init ()
  call global%global_init ()
  call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

  call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("unit_test"), is_known=.true.)
  call var_list_set_string (global%var_list, var_str ("$phs_method"), &
    var_str ("single"), is_known=.true.)
  call var_list_set_string (global%var_list, var_str ("$integration_method"), &
    var_str ("midpoint"), is_known=.true.)
  call var_list_set_log (global%var_list, var_str ("?vis_history"), &
    .false., is_known=.true.)
  call var_list_set_log (global%var_list, var_str ("?integration_timer"), &
    .false., is_known = .true.)
  call var_list_set_real (global%var_list, var_str ("sqrts"), &
    1000._default, is_known=.true.)

  allocate (lib)
  call lib%init (var_str ("lib_cmd8"))
  call global%add_prclib (lib)

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, 'model = "Test"')
  call ifile_append (ifile, 'process commands_8_p = s, s => s, s')
  call ifile_append (ifile, 'compile')
  call ifile_append (ifile, 'iterations = 1:1000')
  call ifile_append (ifile, 'integrate (commands_8_p)')
  call ifile_append (ifile, '?unweighted = false')
  call ifile_append (ifile, 'n_events = 3')
  call ifile_append (ifile, '?read_raw = false')
  call ifile_append (ifile, 'simulate (commands_8_p)')

  call ifile_write (ifile, u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"

call command_list%execute (global)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_8"

end subroutine commands_8

```

Define cuts

Declare a cut expression.

```

<Commands: execute tests>+≡
  call test (commands_9, "commands_9", &
    "cuts", &
    u, results)

<Commands: tests>+≡
subroutine commands_9 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root
  type(string_t), dimension(0) :: no_vars

  write (u, "(A)")  "* Test output: commands_9"
  write (u, "(A)")  "* Purpose: define cuts"
  write (u, "(A)")

```

```

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call global%global_init ()

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'cuts = all Pt > 0 [particle]')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write (u, vars = no_vars)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_9"

end subroutine commands_9

```

Beams

Define beam setup.


```

<Commands: execute tests>+≡
    call test (commands_10, "commands_10", &
        "beams", &
        u, results)

<Commands: tests>+≡
    subroutine commands_10 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root

        write (u, "(A)")  "* Test output: commands_10"
        write (u, "(A)")  "* Purpose: define beams"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call syntax_model_file_init ()
        call global%global_init ()

        write (u, "(A)")  "* Input file"
        write (u, "(A)")

        call ifile_append (ifile, 'model = QCD')
        call ifile_append (ifile, 'sqrts = 1000')
        call ifile_append (ifile, 'beams = p, p')

        call ifile_write (ifile, u)

        write (u, "(A)")
        write (u, "(A)")  "* Parse file"
        write (u, "(A)")

        call parse_ifile (ifile, pn_root, u)

        write (u, "(A)")
        write (u, "(A)")  "* Compile command list"
        write (u, "(A)")

        call command_list%compile (pn_root, global)
        call command_list%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Execute command list"
        write (u, "(A)")

        call command_list%execute (global)

        call global%write_beams (u)

        write (u, "(A)")

```

```

write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_10"

end subroutine commands_10

```

Structure functions

Define beam setup with structure functions

```

<Commands: execute tests>+≡
  call test (commands_11, "commands_11", &
    "structure functions", &
    u, results)

<Commands: tests>+≡
  subroutine commands_11 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root

    write (u, "(A)")  "* Test output: commands_11"
    write (u, "(A)")  "* Purpose: define beams with structure functions"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call syntax_model_file_init ()
    call global%global_init ()

    write (u, "(A)")  "* Input file"
    write (u, "(A)")

    call ifile_append (ifile, 'model = QCD')
    call ifile_append (ifile, 'sqrts = 1100')
    call ifile_append (ifile, 'beams = p, p => lhpdf => pdf_builtin, isr')

    call ifile_write (ifile, u)

    write (u, "(A)")
    write (u, "(A)")  "* Parse file"
    write (u, "(A)")

```

```

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write_beams (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_11"

end subroutine commands_11

```

Rescan events

Read a model, then declare a process, compile the library, and generate weighted events. We take the default (`unit_test`) method and use the simplest methods of phase-space parameterization and integration. Then, rescan the generated event sample.

```

(Commands: execute tests) +=
  call test (commands_12, "commands_12", &
    "event rescanning", &
    u, results)

(Commands: tests) +=
  subroutine commands_12 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    type(prclib_entry_t), pointer :: lib

```

```

write (u, "(A)")  "* Test output: commands_12"
write (u, "(A)")  "* Purpose: generate events and rescan"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call syntax_model_file_init ()

call global%global_init ()
call var_list_append_log (global%var_list, &
    var_str ("?rebuild_phase_space"), .false., &
    intrinsic=.true.)
call var_list_append_log (global%var_list, &
    var_str ("?rebuild_grids"), .false., &
    intrinsic=.true.)
call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("unit_test"), is_known=.true.)
call var_list_set_string (global%var_list, var_str ("$phs_method"), &
    var_str ("single"), is_known=.true.)
call var_list_set_string (global%var_list, var_str ("$integration_method"), &
    var_str ("midpoint"), is_known=.true.)
call var_list_set_log (global%var_list, var_str ("?vis_history"), &
    .false., is_known=.true.)
call var_list_set_log (global%var_list, var_str ("?integration_timer"), &
    .false., is_known = .true.)
call var_list_set_real (global%var_list, var_str ("sqrts"), &
    1000._default, is_known=.true.)

allocate (lib)
call lib%init (var_str ("lib_cmd12"))
call global%add_prclib (lib)

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'model = "Test"')
call ifile_append (ifile, 'process commands_12_p = s, s => s, s')
call ifile_append (ifile, 'compile')
call ifile_append (ifile, 'iterations = 1:1000')
call ifile_append (ifile, 'integrate (commands_12_p)')
call ifile_append (ifile, '?unweighted = false')
call ifile_append (ifile, 'n_events = 3')
call ifile_append (ifile, '?read_raw = false')
call ifile_append (ifile, 'simulate (commands_12_p)')
call ifile_append (ifile, '?write_raw = false')
call ifile_append (ifile, 'rescan "commands_12_p" (commands_12_p)')

call ifile_write (ifile, u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"

call command_list%execute (global)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_12"

end subroutine commands_12

```

Event Files

Set output formats for event files.

```

<Commands: execute tests>+≡
call test (commands_13, "commands_13", &
    "event output formats", &
    u, results)

<Commands: tests>+≡
subroutine commands_13 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    type(prclib_entry_t), pointer :: lib
    logical :: exist

    write (u, "(A)")  "* Test output: commands_13"
    write (u, "(A)")  "* Purpose: generate events and rescan"

```

```

write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call syntax_model_file_init ()
call global%global_init ()
call global%init_fallback_model &
    (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

call var_list_set_string (global%var_list, var_str ("$method"), &
    var_str ("unit_test"), is_known=.true.)
call var_list_set_string (global%var_list, var_str ("$phs_method"), &
    var_str ("single"), is_known=.true.)
call var_list_set_string (global%var_list, var_str ("integration_method"),&
    var_str ("midpoint"), is_known=.true.)
call var_list_set_real (global%var_list, var_str ("sqrts"), &
    1000._default, is_known=.true.)
call var_list_set_log (global%var_list, var_str ("?vis_history"),&
    .false., is_known=.true.)
call var_list_set_log (global%var_list, var_str ("?integration_timer"),&
    .false., is_known = .true.)

allocate (lib)
call lib%init (var_str ("lib_cmd13"))
call global%add_prclib (lib)

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'model = "Test"')
call ifile_append (ifile, 'process commands_13_p = s, s => s, s')
call ifile_append (ifile, 'compile')
call ifile_append (ifile, 'iterations = 1:1000')
call ifile_append (ifile, 'integrate (commands_13_p)')
call ifile_append (ifile, '?unweighted = false')
call ifile_append (ifile, 'n_events = 1')
call ifile_append (ifile, '?read_raw = false')
call ifile_append (ifile, 'sample_format = weight_stream')
call ifile_append (ifile, 'simulate (commands_13_p)')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

```

```

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"

call command_list%execute (global)

write (u, "(A)")
write (u, "(A)")  "* Verify output files"
write (u, "(A)")

inquire (file = "commands_13_p.evx", exist = exist)
if (exist) write (u, "(1x,A)")  "raw"

inquire (file = "commands_13_p.weights.dat", exist = exist)
if (exist) write (u, "(1x,A)")  "weight_stream"

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_13"

end subroutine commands_13

```

Compile Empty Libraries

(This is a regression test:) Declare two empty libraries and compile them.

<Commands: execute tests>+≡

```

call test (commands_14, "commands_14", &
  "empty libraries", &
  u, results)

```

<Commands: tests>+≡

```

subroutine commands_14 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_14"
  write (u, "(A)")  "* Purpose: define and compile empty libraries"
  write (u, "(A)")

```

```

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_model_file_init ()
call syntax_cmd_list_init ()

call global%global_init ()

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'model = "Test"')
call ifile_append (ifile, 'library = "lib1"')
call ifile_append (ifile, 'library = "lib2"')
call ifile_append (ifile, 'compile ()')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%prclib_stack%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()

call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_14"

end subroutine commands_14

```


Compile Process

Read a model, then declare a process and compile the library. The process library is allocated explicitly. For the process definition, We take the default (`unit_test`) method. There is no external code, so compilation of the library is merely a formal status change.

```
(Commands: execute tests)+≡
    call test (commands_15, "commands_15", &
               "compilation", &
               u, results)

(Commands: tests)+≡
    subroutine commands_15 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root
        type(prclib_entry_t), pointer :: lib

        write (u, "(A)")  "* Test output: commands_15"
        write (u, "(A)")  "* Purpose: define process and compile library"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call syntax_model_file_init ()
        call global%global_init ()
        call var_list_set_string (global%var_list, var_str ("$method"), &
                                  var_str ("unit_test"), is_known=.true.)
        call var_list_set_string (global%var_list, var_str ("$phs_method"), &
                                  var_str ("single"), is_known=.true.)
        call var_list_set_string (global%var_list, var_str ("integration_method"),&
                                  var_str ("midpoint"), is_known=.true.)
        call var_list_set_real (global%var_list, var_str ("sqrts"), &
                                 1000._default, is_known=.true.)
        call var_list_set_log (global%var_list, var_str ("?vis_history"),&
                                .false., is_known=.true.)
        call var_list_set_log (global%var_list, var_str ("?integration_timer"),&
                                .false., is_known = .true.)

        allocate (lib)
        call lib%init (var_str ("lib_cmd15"))
        call global%add_prclib (lib)

        write (u, "(A)")  "* Input file"
        write (u, "(A)")

        call ifile_append (ifile, 'model = "Test"')
        call ifile_append (ifile, 'process t15 = s, s => s, s')
        call ifile_append (ifile, 'iterations = 1:1000')
        call ifile_append (ifile, 'integrate (t15)')
```

```

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%prclib_stack%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_15"

end subroutine commands_15

```

Observable

Declare an observable, fill it and display.

```

<Commands: execute tests>+≡
  call test (commands_16, "commands_16", &
    "observables", &
    u, results)

<Commands: tests>+≡
subroutine commands_16 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_16"
  write (u, "(A)")  "* Purpose: declare an observable"

```

```

write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call global%global_init ()

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, '$obs_label = "foo"')
call ifile_append (ifile, '$obs_unit = "cm"')
call ifile_append (ifile, '$title = "Observable foo"')
call ifile_append (ifile, '$description = "This is observable foo"')
call ifile_append (ifile, 'observable foo')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Record two data items"
write (u, "(A)")

call analysis_record_data (var_str ("foo"), 1._default)
call analysis_record_data (var_str ("foo"), 3._default)

write (u, "(A)")  "* Display analysis store"
write (u, "(A)")

call analysis_write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

```

```

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_16"

end subroutine commands_16

```

Histogram

Declare a histogram, fill it and display.

```

<Commands: execute tests>+≡
call test (commands_17, "commands_17", &
  "histograms", &
  u, results)

<Commands: tests>+≡
subroutine commands_17 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root
  type(string_t), dimension(3) :: name
  integer :: i

  write (u, "(A)")  "* Test output: commands_17"
  write (u, "(A)")  "* Purpose: declare histograms"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization"
  write (u, "(A)")

  call syntax_cmd_list_init ()
  call global%global_init ()

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, '$obs_label = "foo"')
  call ifile_append (ifile, '$obs_unit = "cm"')
  call ifile_append (ifile, '$title = "Histogram foo"')
  call ifile_append (ifile, '$description = "This is histogram foo"')
  call ifile_append (ifile, 'histogram foo (0,5,1)')
  call ifile_append (ifile, '$title = "Histogram bar"')
  call ifile_append (ifile, '$description = "This is histogram bar"')
  call ifile_append (ifile, 'n_bins = 2')
  call ifile_append (ifile, 'histogram bar (0,5)')
  call ifile_append (ifile, '$title = "Histogram gee"')
  call ifile_append (ifile, '$description = "This is histogram gee"')

```

```

call ifile_append (ifile, '?normalize_bins = true')
call ifile_append (ifile, 'histogram gee (0,5)')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Record two data items"
write (u, "(A)")

name(1) = "foo"
name(2) = "bar"
name(3) = "gee"

do i = 1, 3
  call analysis_record_data (name(i), 0.1_default, &
    weight = 0.25_default)
  call analysis_record_data (name(i), 3.1_default)
  call analysis_record_data (name(i), 4.1_default, &
    excess = 0.5_default)
  call analysis_record_data (name(i), 7.1_default)
end do

write (u, "(A)")  "* Display analysis store"
write (u, "(A)")

call analysis_write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()

```

```

call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_17"

end subroutine commands_17

```

Plot

Declare a plot, fill it and display contents.

```

<Commands: execute tests>+≡
call test (commands_18, "commands_18", &
    "plots", &
    u, results)

<Commands: tests>+≡
subroutine commands_18 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root

    write (u, "(A)")  "* Test output: commands_18"
    write (u, "(A)")  "* Purpose: declare a plot"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call global%global_init ()

    write (u, "(A)")  "* Input file"
    write (u, "(A)")

    call ifile_append (ifile, '$obs_label = "foo"')
    call ifile_append (ifile, '$obs_unit = "cm"')
    call ifile_append (ifile, '$title = "Plot foo"')
    call ifile_append (ifile, '$description = "This is plot foo"')
    call ifile_append (ifile, '$x_label = "x axis"')
    call ifile_append (ifile, '$y_label = "y axis"')
    call ifile_append (ifile, '?x_log = false')
    call ifile_append (ifile, '?y_log = true')
    call ifile_append (ifile, 'x_min = -1')
    call ifile_append (ifile, 'x_max = 1')
    call ifile_append (ifile, 'y_min = 0.1')
    call ifile_append (ifile, 'y_max = 1000')
    call ifile_append (ifile, 'plot foo')

    call ifile_write (ifile, u)

    write (u, "(A)")

```

```

write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Record two data items"
write (u, "(A)")

call analysis_record_data (var_str ("foo"), 0._default, 20._default, &
    xerr = 0.25_default)
call analysis_record_data (var_str ("foo"), 0.5_default, 0.2_default, &
    yerr = 0.07_default)
call analysis_record_data (var_str ("foo"), 3._default, 2._default)

write (u, "(A)")  "* Display analysis store"
write (u, "(A)")

call analysis_write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_18"

end subroutine commands_18

```

Graph

Combine two (empty) plots to a graph.

(Commands: execute tests)+≡

```

call test (commands_19, "commands_19", &
          "graphs", &
          u, results)
<Commands: tests>+≡
subroutine commands_19 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_19"
  write (u, "(A)")  "* Purpose: combine two plots to a graph"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization"
  write (u, "(A)")

  call syntax_cmd_list_init ()
  call global%global_init ()

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, 'plot a')
  call ifile_append (ifile, 'plot b')
  call ifile_append (ifile, '$title = "Graph foo"')
  call ifile_append (ifile, '$description = "This is graph foo"')
  call ifile_append (ifile, 'graph foo = a & b')

  call ifile_write (ifile, u)

  write (u, "(A)")
  write (u, "(A)")  "* Parse file"
  write (u, "(A)")

  call parse_ifile (ifile, pn_root)

  write (u, "(A)")  "* Compile command list"
  write (u, "(A)")

  call command_list%compile (pn_root, global)

  call command_list%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Execute command list"
  write (u, "(A)")

  call command_list%execute (global)

  write (u, "(A)")  "* Display analysis object"
  write (u, "(A)")

```



```

call analysis_write (var_str ("foo"), u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_19"

end subroutine commands_19

```

Record Data

Record data in previously allocated analysis objects.

```

(Commands: execute tests) +=
  call test (commands_20, "commands_20", &
    "record data", &
    u, results)

(Commands: tests) +=
  subroutine commands_20 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root

    write (u, "(A)")  "* Test output: commands_20"
    write (u, "(A)")  "* Purpose: record data"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization: create observable, histogram, plot"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call global%global_init ()

    call analysis_init_observable (var_str ("o"))
    call analysis_init_histogram (var_str ("h"), 0._default, 1._default, 3, &
      normalize_bins = .false.)
    call analysis_init_plot (var_str ("p"))

    write (u, "(A)")  "* Input file"
    write (u, "(A)")

    call ifile_append (ifile, 'record o (1.234)')

```

```

call ifile_append (ifile, 'record h (0.5)')
call ifile_append (ifile, 'record p (1, 2)')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Display analysis object"
write (u, "(A)")

call analysis_write (u, verbose = .true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_20"

end subroutine commands_20

```

Analysis

Declare an analysis expression and use it to fill an observable during event generation.

```

(Commands: execute tests) +=
  call test (commands_21, "commands_21", &
    "analysis expression", &

```

```

        u, results)
<Commands: tests>+≡
subroutine commands_21 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    type(prclib_entry_t), pointer :: lib

    write (u, "(A)")  "* Test output: commands_21"
    write (u, "(A)")  "* Purpose: create and use analysis expression"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization: create observable"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call syntax_model_file_init ()
    call global%global_init ()
    call global%init_fallback_model &
        (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))

    call var_list_set_string (global%var_list, var_str ("$method"), &
        var_str ("unit_test"), is_known=.true.)
    call var_list_set_string (global%var_list, var_str ("$phs_method"), &
        var_str ("single"), is_known=.true.)
    call var_list_set_string (global%var_list, var_str ("$integration_method"), &
        var_str ("midpoint"), is_known=.true.)
    call var_list_set_log (global%var_list, var_str ("?vis_history"), &
        .false., is_known=.true.)
    call var_list_set_log (global%var_list, var_str ("?integration_timer"), &
        .false., is_known = .true.)
    call var_list_set_real (global%var_list, var_str ("sqrts"), &
        1000._default, is_known=.true.)

    allocate (lib)
    call lib%init (var_str ("lib_cmd8"))
    call global%add_prclib (lib)

    call analysis_init_observable (var_str ("m"))

    write (u, "(A)")  "* Input file"
    write (u, "(A)")

    call ifile_append (ifile, 'model = "Test"')
    call ifile_append (ifile, 'process commands_21_p = s, s => s, s')
    call ifile_append (ifile, 'compile')
    call ifile_append (ifile, 'iterations = 1:100')
    call ifile_append (ifile, 'integrate (commands_21_p)')
    call ifile_append (ifile, '?unweighted = true')
    call ifile_append (ifile, 'n_events = 3')
    call ifile_append (ifile, '?read_raw = false')
    call ifile_append (ifile, 'observable m')

```

```

call ifile_append (ifile, 'analysis = record m (eval M [s]))'
call ifile_append (ifile, 'simulate (commands_21_p)')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Display analysis object"
write (u, "(A)")

call analysis_write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_21"

end subroutine commands_21

```

Write Analysis

Write accumulated analysis data to file.

```

(Commands: execute tests) +=
call test (commands_22, "commands_22", &
  "write analysis", &
  u, results)

```

```

<Commands: tests>+≡
subroutine commands_22 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root
  integer :: u_file, iostat
  logical :: exist
  character(80) :: buffer

  write (u, "(A)")  "* Test output: commands_22"
  write (u, "(A)")  "* Purpose: write analysis data"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization: create observable"
  write (u, "(A)")

  call syntax_cmd_list_init ()
  call global%global_init ()

  call analysis_init_observable (var_str ("m"))
  call analysis_record_data (var_str ("m"), 125._default)

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, '$out_file = "commands_22.dat"')
  call ifile_append (ifile, 'write_analysis')

  call ifile_write (ifile, u)

  write (u, "(A)")
  write (u, "(A)")  "* Parse file"
  write (u, "(A)")

  call parse_ifile (ifile, pn_root)

  write (u, "(A)")  "* Compile command list"
  write (u, "(A)")

  call command_list%compile (pn_root, global)

  call command_list%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Execute command list"
  write (u, "(A)")

  call command_list%execute (global)

  write (u, "(A)")  "* Display analysis data"
  write (u, "(A)")

```

```

inquire (file = "commands_22.dat", exist = exist)
if (.not. exist) then
    write (u, "(A)") "ERROR: File commands_22.dat not found"
    return
end if

u_file = free_unit ()
open (u_file, file = "commands_22.dat", &
      action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat) buffer
    if (iostat /= 0) exit
    write (u, "(A)") trim (buffer)
end do
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_22"

end subroutine commands_22

```

Compile Analysis

Write accumulated analysis data to file and compile.

```

<Commands: execute tests>+≡
    call test (commands_23, "commands_23", &
              "compile analysis", &
              u, results)

<Commands: tests>+≡
subroutine commands_23 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    integer :: u_file, iostat
    character(256) :: buffer
    logical :: exist
    type(graph_options_t) :: graph_options

    write (u, "(A)")  "* Test output: commands_23"

```

```

write (u, "(A)")  "*" Purpose: write and compile analysis data"
write (u, "(A)")

write (u, "(A)")  "*" Initialization: create and fill histogram"
write (u, "(A)")

call syntax_cmd_list_init ()
call global%global_init ()

call graph_options_init (graph_options)
call graph_options_set (graph_options, &
    title = var_str ("Histogram for test: commands 23"), &
    description = var_str ("This is a test."), &
    width_mm = 125, height_mm = 85)
call analysis_init_histogram (var_str ("h"), &
    0._default, 10._default, 2._default, .false., &
    graph_options = graph_options)
call analysis_record_data (var_str ("h"), 1._default)
call analysis_record_data (var_str ("h"), 1._default)
call analysis_record_data (var_str ("h"), 1._default)
call analysis_record_data (var_str ("h"), 1._default)
call analysis_record_data (var_str ("h"), 3._default)
call analysis_record_data (var_str ("h"), 3._default)
call analysis_record_data (var_str ("h"), 3._default)
call analysis_record_data (var_str ("h"), 5._default)
call analysis_record_data (var_str ("h"), 7._default)
call analysis_record_data (var_str ("h"), 7._default)
call analysis_record_data (var_str ("h"), 7._default)
call analysis_record_data (var_str ("h"), 7._default)
call analysis_record_data (var_str ("h"), 9._default)
call analysis_record_data (var_str ("h"), 9._default)
call analysis_record_data (var_str ("h"), 9._default)
call analysis_record_data (var_str ("h"), 9._default)
call analysis_record_data (var_str ("h"), 9._default)
call analysis_record_data (var_str ("h"), 9._default)
call analysis_record_data (var_str ("h"), 9._default)

write (u, "(A)")  "*" Input file"
write (u, "(A)")

call ifile_append (ifile, '$out_file = "commands_23.dat"')
call ifile_append (ifile, 'compile_analysis')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "*" Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "*" Compile command list"
write (u, "(A)")

```

```

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Delete Postscript output"
write (u, "(A)")

inquire (file = "commands_23.ps", exist = exist)
if (exist) then
    u_file = free_unit ()
    open (u_file, file = "commands_23.ps", action = "write", status = "old")
    close (u_file, status = "delete")
end if
inquire (file = "commands_23.ps", exist = exist)
write (u, "(1x,A,L1)")  "Postscript output exists = ", exist

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* TeX file"
write (u, "(A)")

inquire (file = "commands_23.tex", exist = exist)
if (.not. exist) then
    write (u, "(A)")  "ERROR: File commands_23.tex not found"
    return
end if

u_file = free_unit ()
open (u_file, file = "commands_23.tex", &
    action = "read", status = "old")
do
    read (u_file, "(A)", iostat = iostat)  buffer
    if (iostat /= 0)  exit
    write (u, "(A)") trim (buffer)
end do
close (u_file)
write (u, *)

inquire (file = "commands_23.ps", exist = exist)
write (u, "(1x,A,L1)")  "Postscript output exists = ", exist

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()

```



```

call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_23"

end subroutine commands_23

```

Histogram

Declare a histogram, fill it and display.

```

<Commands: execute tests>+≡
call test (commands_24, "commands_24", &
  "drawing options", &
  u, results)

<Commands: tests>+≡
subroutine commands_24 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_24"
  write (u, "(A)")  "* Purpose: check graph and drawing options"
  write (u, "(A)")

  write (u, "(A)")  "* Initialization"
  write (u, "(A)")

  call syntax_cmd_list_init ()
  call global%global_init ()

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, '$title = "Title"')
  call ifile_append (ifile, '$description = "Description"')
  call ifile_append (ifile, '$x_label = "X Label"')
  call ifile_append (ifile, '$y_label = "Y Label"')
  call ifile_append (ifile, 'graph_width_mm = 111')
  call ifile_append (ifile, 'graph_height_mm = 222')
  call ifile_append (ifile, 'x_min = -11')
  call ifile_append (ifile, 'x_max = 22')
  call ifile_append (ifile, 'y_min = -33')
  call ifile_append (ifile, 'y_max = 44')
  call ifile_append (ifile, '$gmlcode_bg = "GML Code BG"')
  call ifile_append (ifile, '$gmlcode_fg = "GML Code FG"')
  call ifile_append (ifile, '$fill_options = "Fill Options"')
  call ifile_append (ifile, '$draw_options = "Draw Options"')
  call ifile_append (ifile, '$err_options = "Error Options"')
  call ifile_append (ifile, '$symbol = "Symbol"')

```

```

call ifile_append (ifile, 'histogram foo (0,1)')
call ifile_append (ifile, 'plot bar')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)

call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Display analysis store"
write (u, "(A)")

call analysis_write (u, verbose=.true.)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call analysis_final ()
call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_24"

end subroutine commands_24

```

Local Environment

Declare a local environment.

```

(Commands: execute tests)+≡
call test (commands_25, "commands_25", &
  "local process environment", &
  u, results)

```

```

<Commands: tests>+≡
subroutine commands_25 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_25"
  write (u, "(A)")  "* Purpose: declare local environment for process"
  write (u, "(A)")

  call syntax_model_file_init ()
  call syntax_cmd_list_init ()
  call global%global_init ()
  call var_list_set_log (global%var_list, var_str ("?omega_openmp"), &
    .false., is_known = .true.)

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, 'library = "commands_25_lib"')
  call ifile_append (ifile, 'model = "Test"')
  call ifile_append (ifile, 'process commands_25_p1 = g, g => g, g &
    &{ model = "QCD" }')

  call ifile_write (ifile, u)

  write (u, "(A)")
  write (u, "(A)")  "* Parse file"
  write (u, "(A)")

  call parse_ifile (ifile, pn_root)

  write (u, "(A)")  "* Compile command list"
  write (u, "(A)")

  call command_list%compile (pn_root, global)
  call command_list%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Execute command list"
  write (u, "(A)")

  call command_list%execute (global)
  call global%write_libraries (u)

  write (u, "(A)")
  write (u, "(A)")  "* Cleanup"

  call ifile_final (ifile)

  call command_list%final ()
  call global%final ()

```

```

call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_25"

end subroutine commands_25

```

Alternative Setups

Declare a list of alternative setups.

```

(Commands: execute tests)+≡
call test (commands_26, "commands_26", &
  "alternative setups", &
  u, results)

(Commands: tests)+≡
subroutine commands_26 (u)
  integer, intent(in) :: u
  type(ifile_t) :: ifile
  type(command_list_t), target :: command_list
  type(rt_data_t), target :: global
  type(parse_node_t), pointer :: pn_root

  write (u, "(A)")  "* Test output: commands_26"
  write (u, "(A)")  "* Purpose: declare alternative setups for simulation"
  write (u, "(A)")

  call syntax_cmd_list_init ()
  call global%global_init ()

  write (u, "(A)")  "* Input file"
  write (u, "(A)")

  call ifile_append (ifile, 'int i = 0')
  call ifile_append (ifile, 'alt_setup = ({ i = 1 }, { i = 2 })')

  call ifile_write (ifile, u)

  write (u, "(A)")
  write (u, "(A)")  "* Parse file"
  write (u, "(A)")

  call parse_ifile (ifile, pn_root)

  write (u, "(A)")  "* Compile command list"
  write (u, "(A)")

  call command_list%compile (pn_root, global)
  call command_list%write (u)

  write (u, "(A)")
  write (u, "(A)")  "* Execute command list"

```

```

write (u, "(A)")

call command_list%execute (global)

call global%write_expr (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_26"

end subroutine commands_26

```

Unstable Particle

Define decay processes and declare a particle as unstable. Also check the commands stable, polarized, unpolarized.

```

(Commands: execute tests) +=
  call test (commands_27, "commands_27", &
    "unstable and polarized particles", &
    u, results)

(Commands: tests) +=
  subroutine commands_27 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    type(prclib_entry_t), pointer :: lib

    write (u, "(A)")  "* Test output: commands_27"
    write (u, "(A)")  "* Purpose: modify particle properties"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call syntax_model_file_init ()
    call global%global_init ()
    call var_list_set_string (global%var_list, var_str ("method"), &
      var_str ("unit_test"), is_known=.true.)
    call var_list_set_string (global%var_list, var_str ("phs_method"), &
      var_str ("single"), is_known=.true.)
    call var_list_set_string (global%var_list, var_str ("integration_method"), &
      var_str ("midpoint"), is_known=.true.)
    call var_list_set_log (global%var_list, var_str ("?vis_history"), &
      .false., is_known=.true.)

```

```

call var_list_set_log (global%var_list, var_str ("?integration_timer"),&
    .false., is_known = .true.)

allocate (lib)
call lib%init (var_str ("commands_27_lib"))
call global%add_prclib (lib)

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'model = "Test"')
call ifile_append (ifile, 'ff = 0.4')
call ifile_append (ifile, 'process d1 = s => f, fbar')
call ifile_append (ifile, 'unstable s (d1)')
call ifile_append (ifile, 'polarized f, fbar')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Show model"
write (u, "(A)")

call global%model%write (u)

write (u, "(A)")
write (u, "(A)")  "* Extra Input"
write (u, "(A)")

call ifile_final (ifile)
call ifile_append (ifile, '?diagonal_decay = true')
call ifile_append (ifile, 'unstable s (d1)')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

```

```

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%final ()
call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Show model"
write (u, "(A)")

call global%model%write (u)

write (u, "(A)")
write (u, "(A)")  "* Extra Input"
write (u, "(A)")

call ifile_final (ifile)
call ifile_append (ifile, '?isotropic_decay = true')
call ifile_append (ifile, 'unstable s (d1)')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%final ()
call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Show model"
write (u, "(A)")

call global%model%write (u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Extra Input"
write (u, "(A)")

call ifile_final (ifile)
call ifile_append (ifile, 'stable s')
call ifile_append (ifile, 'unpolarized f')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root)

write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%final ()
call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Show model"
write (u, "(A)")

call global%model%write (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_model_file_init ()
call syntax_cmd_list_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_27"

end subroutine commands_27

```

Quit the program

Quit the program.


```

<Commands: execute tests>+≡
    call test (commands_28, "commands_28", &
        "quit", &
        u, results)

<Commands: tests>+≡
    subroutine commands_28 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root1, pn_root2
        type(string_t), dimension(0) :: no_vars

        write (u, "(A)")  "* Test output: commands_28"
        write (u, "(A)")  "* Purpose: quit the program"
        write (u, "(A)")

        write (u, "(A)")  "* Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call global%global_init ()

        write (u, "(A)")  "* Input file: quit without code"
        write (u, "(A)")

        call ifile_append (ifile, 'quit')

        call ifile_write (ifile, u)

        write (u, "(A)")
        write (u, "(A)")  "* Parse file"
        write (u, "(A)")

        call parse_ifile (ifile, pn_root1, u)

        write (u, "(A)")
        write (u, "(A)")  "* Compile command list"
        write (u, "(A)")

        call command_list%compile (pn_root1, global)
        call command_list%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Execute command list"
        write (u, "(A)")

        call command_list%execute (global)

        call global%write (u, vars = no_vars)

        write (u, "(A)")
        write (u, "(A)")  "* Input file: quit with code"
        write (u, "(A)")

```

```

call ifile_final (ifile)
call command_list%final ()
call ifile_append (ifile, 'quit ( 3 + 4 )')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root2, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root2, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write (u, vars = no_vars)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_28"

end subroutine commands_28

```

SLHA interface

Testing commands steering the SLHA interface.

```

<Commands: execute tests>+≡
  call test (commands_29, "commands_29", &
    "SLHA interface", &
    u, results)

<Commands: tests>+≡
  subroutine commands_29 (u)
    integer, intent(in) :: u

```

```

type(ifile_t) :: ifile
type(command_list_t), target :: command_list
type(rt_data_t), target :: global
type(var_list_t), pointer :: model_vars
type(parse_node_t), pointer :: pn_root

write (u, "(A)")  "* Test output: commands_29"
write (u, "(A)")  "* Purpose: test SLHA interface"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call syntax_model_file_init ()
call syntax_slha_init ()
call global%global_init ()

write (u, "(A)")  "* Model MSSM, read SLHA file"
write (u, "(A)")

call ifile_append (ifile, 'model = "MSSM"')
call ifile_append (ifile, '?slha_read_decays = true')
call ifile_append (ifile, 'read_slha ("spslap_decays.slha")')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Model MSSM, default values:"
write (u, "(A)")

call global%model%write (u, verbose = .false., &
    show_vertices = .false., show_particles = .false.)

write (u, "(A)")
write (u, "(A)")  "* Selected global variables"
write (u, "(A)")

model_vars => global%model%get_var_list_ptr ()

call var_list_write_var (model_vars, var_str ("mch1"), u)

```

```

call var_list_write_var (model_vars, var_str ("wch1"), u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

write (u, "(A)")  "* Model MSSM, values from SLHA file"
write (u, "(A)")

call global%model%write (u, verbose = .false., &
    show_vertices = .false., show_particles = .false.)

write (u, "(A)")
write (u, "(A)")  "* Selected global variables"
write (u, "(A)")

model_vars => global%model%get_var_list_ptr ()

call var_list_write_var (model_vars, var_str ("mch1"), u)
call var_list_write_var (model_vars, var_str ("wch1"), u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_slha_final ()
call syntax_model_file_final ()
call syntax_cmd_list_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_29"

end subroutine commands_29

```

Expressions for scales

Declare a scale, factorization scale or factorization scale expression.

```

<Commands: execute tests>+≡
    call test (commands_30, "commands_30", &
        "scales", &
        u, results)

<Commands: tests>+≡
    subroutine commands_30 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global

```

```

type(parse_node_t), pointer :: pn_root

write (u, "(A)")  "* Test output: commands_30"
write (u, "(A)")  "* Purpose: define scales"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call global%global_init ()

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'scale = 200 GeV')
call ifile_append (ifile, &
'factorization_scale = eval Pt [particle]')
call ifile_append (ifile, &
'renormalization_scale = eval E [particle]')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write_expr (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()

write (u, "(A)")

```

```

        write (u, "(A)")  "* Test output end: commands_30"

end subroutine commands_30

```

Weight and reweight expressions

Declare an expression for event weights and reweighting.

```

<Commands: execute tests>+≡
    call test (commands_31, "commands_31", &
        "event weights/reweighting", &
        u, results)

<Commands: tests>+≡
    subroutine commands_31 (u)
        integer, intent(in) :: u
        type(ifile_t) :: ifile
        type(command_list_t), target :: command_list
        type(rt_data_t), target :: global
        type(parse_node_t), pointer :: pn_root

        write (u, "(A)")  "* Test output: commands_31"
        write (u, "(A)")  "*   Purpose: define weight/reweight"
        write (u, "(A)")

        write (u, "(A)")  "*   Initialization"
        write (u, "(A)")

        call syntax_cmd_list_init ()
        call global%global_init ()

        write (u, "(A)")  "*   Input file"
        write (u, "(A)")

        call ifile_append (ifile, 'weight = eval Pz [particle]')
        call ifile_append (ifile, 'reweight = eval M2 [particle]')

        call ifile_write (ifile, u)

        write (u, "(A)")
        write (u, "(A)")  "*   Parse file"
        write (u, "(A)")

        call parse_ifile (ifile, pn_root, u)

        write (u, "(A)")
        write (u, "(A)")  "* Compile command list"
        write (u, "(A)")

        call command_list%compile (pn_root, global)
        call command_list%write (u)

        write (u, "(A)")
        write (u, "(A)")  "* Execute command list"

```

```

write (u, "(A)")

call command_list%execute (global)

call global%write_expr (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()
call syntax_model_file_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_31"

end subroutine commands_31

```

Selecting events

Declare an expression for selecting events in an analysis.

```

<Commands: execute tests>+≡
  call test (commands_32, "commands_32", &
    "event selection", &
    u, results)

<Commands: tests>+≡
  subroutine commands_32 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root

    write (u, "(A)")  "* Test output: commands_32"
    write (u, "(A)")  "* Purpose: define selection"
    write (u, "(A)")

    write (u, "(A)")  "* Initialization"
    write (u, "(A)")

    call syntax_cmd_list_init ()
    call global%global_init ()

    write (u, "(A)")  "* Input file"
    write (u, "(A)")

    call ifile_append (ifile, 'selection = any PDG == 13 [particle]')

    call ifile_write (ifile, u)

```

```

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)

call global%write_expr (u)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()

write (u, "(A)")
write (u, "(A)")  "* Test output end: commands_32"

end subroutine commands_32

```

Executing shell commands

Execute a shell command.

```

<Commands: execute tests>+≡
  call test (commands_33, "commands_33", &
    "execute shell command", &
    u, results)

<Commands: tests>+≡
  subroutine commands_33 (u)
    integer, intent(in) :: u
    type(ifile_t) :: ifile
    type(command_list_t), target :: command_list
    type(rt_data_t), target :: global
    type(parse_node_t), pointer :: pn_root
    integer :: u_file, iostat
    character(3) :: buffer

```



```

write (u, "(A)")  "* Test output: commands_33"
write (u, "(A)")  "* Purpose: execute shell command"
write (u, "(A)")

write (u, "(A)")  "* Initialization"
write (u, "(A)")

call syntax_cmd_list_init ()
call global%global_init ()

write (u, "(A)")  "* Input file"
write (u, "(A)")

call ifile_append (ifile, 'exec ("echo foo >> bar")')

call ifile_write (ifile, u)

write (u, "(A)")
write (u, "(A)")  "* Parse file"
write (u, "(A)")

call parse_ifile (ifile, pn_root, u)

write (u, "(A)")
write (u, "(A)")  "* Compile command list"
write (u, "(A)")

call command_list%compile (pn_root, global)
call command_list%write (u)

write (u, "(A)")
write (u, "(A)")  "* Execute command list"
write (u, "(A)")

call command_list%execute (global)
u_file = free_unit ()
open (u_file, file = "bar", &
      action = "read", status = "old")
do
  read (u_file, "(A)", iostat = iostat)  buffer
  if (iostat /= 0) exit
end do
write (u, "(A,A)")  "should be 'foo': ", trim (buffer)
close (u_file)

write (u, "(A)")
write (u, "(A)")  "* Cleanup"

call ifile_final (ifile)

call command_list%final ()
call global%final ()
call syntax_cmd_list_final ()

```

```
write (u, "(A)")  
write (u, "(A)")  "* Test output end: commands_33"  
  
end subroutine commands_33
```

30.2 Toplevel module WHIZARD

`<whizard.f90>≡`
`<File header>`

```
module whizard

  use io_units
  <Use strings>
  use unit_tests
  use system_defs, only: VERSION_STRING
  use system_defs, only: EOF, BACKSLASH
  use diagnostics
  use os_interface
  use formats
  use md5
  use sorting
  use codes
  use object_base
  use object_builder
  use object_logical
  use sindarin_parser
  use grids
  use solver
  use cputime
  use sm_qcd
  use ifiles
  use lexers
  use parser
  use xml
  use colors
  use state_matrices
  use analysis
  use variables
  use model_testbed
  use user_code_interface
  use eval_trees
  use particles
  use models
  use auto_components
  use radiation_generator
  use evaluators
  use phs_forests
  use beams
  use polarizations
  use sf_aux
  use sf_mappings
  use sf_base
  use sf_pdf_builtin
  use sf_lhapdf
  use sf_circe1
  use sf_circe2
  use sf_isr
  use sf_epa
```

```

use sf_ewa
use sf_escan
use sf_beam_events
use sf_user
use phs_base
use phs_single
use phs_wood
use phs_fks
use rng_base
use rng_tao
use selectors
use mci_base
use mci_midpoint
use mci_vamp
use prclib_interfaces
use particle_specifiers
use process_libraries
use prclib_stacks
use hepmc_interface
use lcio_interface
use jets
use pdg_arrays
use interactions
use slha_interface
use cascades
use blha_driver
use blha_config
use prc_core
use prc_test
use prc_template_me
use prc_omega
use subvt_expr
use processes
use process_stacks
use event_transforms
use decays
use powheg
use shower
use events

use hep_events
use eio_data
use eio_base
use eio_raw
use eio_checkpoints
use eio_lhef
use eio_hepmc
use eio_lcio
use eio_stdhep
use eio_ascii
use eio_weights

use iterations
use beam_structures

```

```

    use rt_data
    use dispatch
    use process_configurations
    use compilations
    use integrations
    use event_streams
    use simulations
    use nlo_controller

    use expr_tests

    use commands

    <Standard module head>

    <WHIZARD: public>

    <WHIZARD: types>

    save

contains

    <WHIZARD: procedures>

end module whizard

```

30.2.1 Options

Here we introduce a wrapper that holds various user options, so they can transparently be passed from the main program to the `whizard` object. Most parameters are used for initializing the `global` state.

```

<WHIZARD: public>≡
    public :: whizard_options_t

<WHIZARD: types>≡
    type :: whizard_options_t
        type(string_t) :: preload_model
        type(string_t) :: default_lib
        type(string_t) :: preload_libraries
        logical :: rebuild_library = .false.
        logical :: recompile_library = .false.
        logical :: rebuild_user
        logical :: rebuild_phs = .false.
        logical :: rebuild_grids = .false.
        logical :: rebuild_events = .false.
    end type whizard_options_t

```

30.2.2 Parse tree stack

We collect all parse trees that we generate in the `whizard` object. To this end, we create a stack of parse trees. They must not be finalized before the `global`

object is finalized, because items such as a cut definition may contain references to the parse tree from which they were generated.

```

<WHIZARD: types>+=
  type, extends (parse_tree_t) :: pt_entry_t
    type(pt_entry_t), pointer :: previous => null ()
  end type pt_entry_t

```

This is the stack. Since we always prepend, we just need the `last` pointer.

```

<WHIZARD: types>+=
  type :: pt_stack_t
    type(pt_entry_t), pointer :: last => null ()
    contains
      <WHIZARD: pt_stack: TBP>
    end type pt_stack_t

```

The finalizer is called at the very end.

```

<WHIZARD: pt_stack: TBP>=
  procedure :: final => pt_stack_final

<WHIZARD: procedures>=
  subroutine pt_stack_final (pt_stack)
    class(pt_stack_t), intent(inout) :: pt_stack
    type(pt_entry_t), pointer :: current
    do while (associated (pt_stack%last))
      current => pt_stack%last
      pt_stack%last => current%previous
      call parse_tree_final (current%parse_tree_t)
      deallocate (current)
    end do
  end subroutine pt_stack_final

```

Create and push a new entry, keeping the previous ones.

```

<WHIZARD: pt_stack: TBP>+=
  procedure :: push => pt_stack_push

<WHIZARD: procedures>+=
  subroutine pt_stack_push (pt_stack, parse_tree)
    class(pt_stack_t), intent(inout) :: pt_stack
    type(parse_tree_t), intent(out), pointer :: parse_tree
    type(pt_entry_t), pointer :: current
    allocate (current)
    parse_tree => current%parse_tree_t
    current%previous => pt_stack%last
    pt_stack%last => current
  end subroutine pt_stack_push

```

30.2.3 The whizard object

An object of type `whizard_t` is the top-level wrapper for a WHIZARD instance. The object holds various default settings and the current state of the generator,

the `global` object of type `rt_data_t`. This object contains, for instance, the list of variables and the process libraries.

Since components of the `global` subobject are frequently used as targets, the `whizard` object should also consistently carry the `target` attribute.

The various self-tests do not use this object. They initialize only specific subsets of the system, according to their needs.

Note: we intend to allow several concurrent instances. In the current implementation, there are still a few obstacles to this: the model library and the syntax tables are global variables, and the error handling uses global state. This should be improved.

```

<WHIZARD: public>+=
  public :: whizard_t

<WHIZARD: types>+=
  type :: whizard_t
    type(whizard_options_t) :: options
    type(rt_data_t) :: global
    type(pt_stack_t) :: pt_stack
  contains
    <WHIZARD: whizard: TBP>
  end type whizard_t

```

30.2.4 Initialization and finalization

```

<WHIZARD: whizard: TBP>=
  procedure :: init => whizard_init

<WHIZARD: procedures>+=
  subroutine whizard_init (whizard, options, paths, logfile)
    class(whizard_t), intent(out), target :: whizard
    type(whizard_options_t), intent(in) :: options
    type(paths_t), intent(in), optional :: paths
    type(string_t), intent(in), optional :: logfile
    call init_syntax_tables ()
    whizard%options = options
    call whizard%global%global_init (paths, logfile)
    call whizard%init_rebuild_flags ()
    call whizard%preload_model ()
    call whizard%preload_library ()
    call whizard%global%init_fallback_model &
      (var_str ("SM_hadrons"), var_str ("SM_hadrons.mdl"))
    call whizard%global%init_radiation_model &
      (var_str ("SM_rad"), var_str ("SM_rad.mdl"))
  end subroutine whizard_init

```

Apart from the global data which have been initialized above, the process and model lists need to be finalized.

```

<WHIZARD: whizard: TBP>+=
  procedure :: final => whizard_final

```

```

<WHIZARD: procedures>+≡
  subroutine whizard_final (whizard)
    class(whizard_t), intent(inout), target :: whizard
    call whizard%global%final ()
    call whizard%pt_stack%final ()
    !!! JRR: WK please check (#529)
    !   call user_code_final ()
    call final_syntax_tables ()
  end subroutine whizard_final

```

Set the rebuild flags. They can be specified on the command line and set the initial value for the associated logical variables.

```

<WHIZARD: whizard: TBP>+≡
  procedure :: init_rebuild_flags => whizard_init_rebuild_flags

<WHIZARD: procedures>+≡
  subroutine whizard_init_rebuild_flags (whizard)
    class(whizard_t), intent(inout), target :: whizard
    associate (var_list => whizard%global%var_list, options => whizard%options)
      call var_list_append_log &
        (var_list, var_str ("?rebuild_library"), options%rebuild_library, &
         intrinsic=.true.)
      call var_list_append_log &
        (var_list, var_str ("?recompile_library"), &
         options%recompile_library, &
         intrinsic=.true.)
      call var_list_append_log &
        (var_list, var_str ("?rebuild_phase_space"), options%rebuild_phs, &
         intrinsic=.true.)
      call var_list_append_log &
        (var_list, var_str ("?rebuild_grids"), options%rebuild_grids, &
         intrinsic=.true.)
      call var_list_append_log &
        (var_list, var_str ("?rebuild_events"), options%rebuild_events, &
         intrinsic=.true.)
    end associate
  end subroutine whizard_init_rebuild_flags

```

This procedure preloads a model, if a model name is given.

```

<WHIZARD: whizard: TBP>+≡
  procedure :: preload_model => whizard_preload_model

<WHIZARD: procedures>+≡
  subroutine whizard_preload_model (whizard)
    class(whizard_t), intent(inout), target :: whizard
    type(string_t) :: model_name
    model_name = whizard%options%preload_model
    if (model_name /= "") then
      call whizard%global%read_model (model_name, whizard%global%preload_model)
      whizard%global%model => whizard%global%preload_model
      if (associated (whizard%global%model)) then
        call whizard%global%model%link_var_list (whizard%global%var_list)
        call msg_message ("Preloaded model: " &
                          // char (model_name))
      end if
    end if
  end subroutine whizard_preload_model

```



```

        else
            call msg_fatal ("Preloading model " // char (model_name) &
                           // " failed")
        end if
    else
        call msg_message ("No model preloaded")
    end if
end subroutine whizard_preload_model

```

This procedure preloads a library, if a library name is given.

Note: This version just opens a new library with that name. It does not load (yet) an existing library on file, as previous WHIZARD versions would do.

(WHIZARD: whizard: TBP)+≡

```

    procedure :: preload_library => whizard_preload_library

```

(WHIZARD: procedures)+≡

```

subroutine whizard_preload_library (whizard)
    class(whizard_t), intent(inout), target :: whizard
    type(string_t) :: library_name, libs
    type(string_t), dimension(:), allocatable :: libname_static
    type(prclib_entry_t), pointer :: lib_entry
    integer :: i
    call get_prclib_static (libname_static)
    do i = 1, size (libname_static)
        allocate (lib_entry)
        call lib_entry%init_static (libname_static(i))
        call whizard%global%add_prclib (lib_entry)
    end do
    libs = adjustl (whizard%options%preload_libraries)
    if (libs == "" .and. whizard%options%default_lib /= "") then
        allocate (lib_entry)
        call lib_entry%init (whizard%options%default_lib)
        call whizard%global%add_prclib (lib_entry)
        call msg_message ("Preloaded library: " // &
                           char (whizard%options%default_lib))
    end if
    SCAN_LIBS: do while (libs /= "")
        call split (libs, library_name, " ")
        if (library_name /= "") then
            allocate (lib_entry)
            call lib_entry%init (library_name)
            call whizard%global%add_prclib (lib_entry)
            call msg_message ("Preloaded library: " // char (library_name))
        end if
    end do SCAN_LIBS
end subroutine whizard_preload_library

```

30.2.5 Initialization and finalization (old version)

These procedures initialize and finalize global variables. Most of them are collected in the `global` data record located here, the others are syntax tables located in various modules, which do not change during program execution.

Furthermore, there is a global model list and a global process store, which get filled during program execution but are finalized here.

During initialization, we can preload a default model and initialize a default library for setting up processes. The default library is loaded if requested by the setup. Further libraries can be loaded as specified by command-line flags. Initialize/finalize the syntax tables used by WHIZARD:

```

<WHIZARD: public>+≡
    public :: init_syntax_tables
    public :: final_syntax_tables

<WHIZARD: procedures>+≡
    subroutine init_syntax_tables ()
        call syntax_model_file_init ()
        call syntax_phs_forest_init ()
        call syntax_pexpr_init ()
        call syntax_slha_init ()
        call syntax_blha_contract_init ()
        call syntax_cmd_list_init ()
    end subroutine init_syntax_tables

    subroutine final_syntax_tables ()
        call syntax_model_file_final ()
        call syntax_phs_forest_final ()
        call syntax_pexpr_final ()
        call syntax_slha_final ()
        call syntax_blha_contract_final ()
        call syntax_cmd_list_final ()
    end subroutine final_syntax_tables

```

Write the syntax tables to external files.

```

<WHIZARD: public>+≡
    public :: write_syntax_tables

<WHIZARD: procedures>+≡
    subroutine write_syntax_tables ()
        integer :: unit
        character(*), parameter :: file_model = "whizard.model_file.syntax"
        character(*), parameter :: file_phs = "whizard.phase_space_file.syntax"
        character(*), parameter :: file_pexpr = "whizard.prt_expressions.syntax"
        character(*), parameter :: file_slha = "whizard.slha.syntax"
        character(*), parameter :: file_sindarin = "whizard.sindarin.syntax"
        unit = free_unit ()
        print *, "Writing file '" // file_model // "'"
        open (unit=unit, file=file_model, status="replace", action="write")
        write (unit, "(A)") VERSION_STRING
        write (unit, "(A)") "Syntax definition file: " // file_model
        call syntax_model_file_write (unit)
        close (unit)
        print *, "Writing file '" // file_phs // "'"
        open (unit=unit, file=file_phs, status="replace", action="write")
        write (unit, "(A)") VERSION_STRING
        write (unit, "(A)") "Syntax definition file: " // file_phs
        call syntax_phs_forest_write (unit)
        close (unit)
    end subroutine write_syntax_tables

```

```

print *, "Writing file '" // file_pexpr // "'"
open (unit=unit, file=file_pexpr, status="replace", action="write")
write (unit, "(A)")  VERSION_STRING
write (unit, "(A)")  "Syntax definition file: " // file_pexpr
call syntax_pexpr_write (unit)
close (unit)
print *, "Writing file '" // file_slha // "'"
open (unit=unit, file=file_slha, status="replace", action="write")
write (unit, "(A)")  VERSION_STRING
write (unit, "(A)")  "Syntax definition file: " // file_slha
call syntax_slha_write (unit)
close (unit)
print *, "Writing file '" // file_sindarin // "'"
open (unit=unit, file=file_sindarin, status="replace", action="write")
write (unit, "(A)")  VERSION_STRING
write (unit, "(A)")  "Syntax definition file: " // file_sindarin
call syntax_cmd_list_write (unit)
close (unit)
end subroutine write_syntax_tables

```

30.2.6 Execute command lists

Process commands given on the command line, stored as an ifile. The whole input is read, compiled and executed as a whole.

```

<WHIZARD: whizard: TBP>+≡
  procedure :: process_ifile => whizard_process_ifile

<WHIZARD: procedures>+≡
  subroutine whizard_process_ifile (whizard, ifile, quit, quit_code)
    class(whizard_t), intent(inout), target :: whizard
    type(ifile_t), intent(in) :: ifile
    logical, intent(out) :: quit
    integer, intent(out) :: quit_code
    type(lexer_t), target :: lexer
    type(stream_t), target :: stream
    call msg_message ("Reading commands given on the command line")
    call lexer_init_cmd_list (lexer)
    call stream_init (stream, ifile)
    call whizard%process_stream (stream, lexer, quit, quit_code)
    call stream_final (stream)
    call lexer_final (lexer)
  end subroutine whizard_process_ifile

```

Process standard input as a command list. The whole input is read, compiled and executed as a whole.

```

<WHIZARD: whizard: TBP>+≡
  procedure :: process_stdin => whizard_process_stdin

<WHIZARD: procedures>+≡
  subroutine whizard_process_stdin (whizard, quit, quit_code)
    class(whizard_t), intent(inout), target :: whizard
    logical, intent(out) :: quit

```

```

integer, intent(out) :: quit_code
type(lexer_t), target :: lexer
type(stream_t), target :: stream
call msg_message ("Reading commands from standard input")
call lexer_init_cmd_list (lexer)
call stream_init (stream, 5)
call whizard%process_stream (stream, lexer, quit, quit_code)
call stream_final (stream)
call lexer_final (lexer)
end subroutine whizard_process_stdin

```

Process a file as a command list.

```

<WHIZARD: whizard: TBP>+=
  procedure :: process_file => whizard_process_file

<WHIZARD: procedures>+=
  subroutine whizard_process_file (whizard, file, quit, quit_code)
    class(whizard_t), intent(inout), target :: whizard
    type(string_t), intent(in) :: file
    logical, intent(out) :: quit
    integer, intent(out) :: quit_code
    type(lexer_t), target :: lexer
    type(stream_t), target :: stream
    logical :: exist
    call msg_message ("Reading commands from file '" // char(file) // "'")
    inquire (file=char(file), exist=exist)
    if (exist) then
      call lexer_init_cmd_list (lexer)
      call stream_init (stream, char(file))
      call whizard%process_stream (stream, lexer, quit, quit_code)
      call stream_final (stream)
      call lexer_final (lexer)
    else
      call msg_error ("File '" // char(file) // "' not found")
    end if
  end subroutine whizard_process_file

```

```

<WHIZARD: whizard: TBP>+=
  procedure :: process_stream => whizard_process_stream

<WHIZARD: procedures>+=
  subroutine whizard_process_stream (whizard, stream, lexer, quit, quit_code)
    class(whizard_t), intent(inout), target :: whizard
    type(stream_t), intent(inout), target :: stream
    type(lexer_t), intent(inout), target :: lexer
    logical, intent(out) :: quit
    integer, intent(out) :: quit_code
    type(parse_tree_t), pointer :: parse_tree
    type(command_list_t), target :: command_list
    call lexer_assign_stream (lexer, stream)
    call whizard%pt_stack%push (parse_tree)
    call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
    if (associated (parse_tree_get_root_ptr (parse_tree))) then
      whizard%global%lexer => lexer
    end if
  end subroutine whizard_process_stream

```

```

        call command_list%compile (parse_tree_get_root_ptr (parse_tree), &
            whizard%global)
    end if
    call whizard%global%activate ()
    call command_list%execute (whizard%global)
    call command_list%final ()
    quit = whizard%global%quit
    quit_code = whizard%global%quit_code
end subroutine whizard_process_stream

```

30.2.7 The WHIZARD shell

This procedure implements interactive mode. One line is processed at a time.

```

<WHIZARD: whizard: TBP>+=
    procedure :: shell => whizard_shell

<WHIZARD: procedures>+=
    subroutine whizard_shell (whizard, quit_code)
        class(whizard_t), intent(inout), target :: whizard
        integer, intent(out) :: quit_code
        type(lexer_t), target :: lexer
        type(stream_t), target :: stream
        type(string_t) :: prompt1
        type(string_t) :: prompt2
        type(string_t) :: input
        type(string_t) :: extra
        integer :: last
        integer :: iostat
        logical :: mask_tmp
        logical :: quit
        call msg_message ("Launching interactive shell")
        call lexer_init_cmd_list (lexer)
        prompt1 = "whish? "
        prompt2 = "      > "
        COMMAND_LOOP: do
            call put (6, prompt1)
            call get (5, input, iostat=iostat)
            if (iostat > 0 .or. iostat == EOF) exit COMMAND_LOOP
            CONTINUE_INPUT: do
                last = len_trim (input)
                if (extract (input, last, last) /= BACKSLASH) exit CONTINUE_INPUT
                call put (6, prompt2)
                call get (5, extra, iostat=iostat)
                if (iostat > 0) exit COMMAND_LOOP
                input = replace (input, last, extra)
            end do CONTINUE_INPUT
            call stream_init (stream, input)
            mask_tmp = mask_fatal_errors
            mask_fatal_errors = .true.
            call whizard%process_stream (stream, lexer, quit, quit_code)
            msg_count = 0
            mask_fatal_errors = mask_tmp
            call stream_final (stream)

```

```

        if (quit) exit COMMAND_LOOP
    end do COMMAND_LOOP
    print *
    call lexer_final (lexer)
end subroutine whizard_shell

```

30.2.8 Self-tests

For those self-tests, we need some auxiliary routines that provide an environment. The environment depends on things that are not available at the level of the module that we want to test.

Testbed for event I/O

This subroutine prepares a test process with a single event. All objects are allocated via anonymous pointers, because we want to recover the pointers and delete the objects in a separate procedure.

```

<WHIZARD: procedures>+≡
subroutine prepare_eio_test (event, unweighted, n_alt)
    use variables
    use model_data
    use event_base
    class(generic_event_t), intent(inout), pointer :: event
    logical, intent(in), optional :: unweighted
    integer, intent(in), optional :: n_alt
    type(model_data_t), pointer :: model
    type(var_list_t) :: var_list
    type(process_t), pointer :: process
    type(process_instance_t), pointer :: process_instance

    allocate (model)
    call model%init_test ()

    allocate (process)
    allocate (process_instance)

    call prepare_test_process (process, process_instance, model)
    call process_instance%setup_event_data ()

    call model%final ()
    deallocate (model)

    allocate (event_t :: event)
    select type (event)
    type is (event_t)
        if (present (unweighted)) then
            call var_list_append_log (var_list, &
                var_str ("?unweighted"), unweighted, &
                intrinsic = .true.)
        else
            call var_list_append_log (var_list, &
                var_str ("?unweighted"), .true., &

```

```

        intrinsic = .true.)
    end if
    call var_list_append_string (var_list, &
        var_str ("sample_normalization"), &
        var_str ("auto"), intrinsic = .true.)
    call event%basic_init (var_list, n_alt)
    call event%connect (process_instance, process%get_model_ptr ())
    call var_list%final ()
end select
end subroutine prepare_eio_test

```

Recover those pointers, finalize the objects and deallocate.

```

<WHIZARD: procedures>+≡
subroutine cleanup_eio_test (event)
    use model_data
    use event_base
    class(generic_event_t), intent(inout), pointer :: event
    type(process_t), pointer :: process
    type(process_instance_t), pointer :: process_instance
    select type (event)
    type is (event_t)
        process => event%get_process_ptr ()
        process_instance => event%get_process_instance_ptr ()
        call cleanup_test_process (process, process_instance)
        deallocate (process_instance)
        deallocate (process)
        call event%final ()
    end select
    deallocate (event)
end subroutine cleanup_eio_test

```

Assign those procedures to appropriate pointers (module variables) in the `eio_base` module, so they can be called as if they were module procedures.

```

<WHIZARD: prepare testbed>≡
    eio_prepare_test => prepare_eio_test
    eio_cleanup_test => cleanup_eio_test

```

Any Model

This procedure reads any model from file and, optionally, assigns a var-list pointer.

```

<WHIZARD: procedures>+≡
subroutine prepare_whizard_model (model, name, vars)
    <Use strings>
    use os_interface
    use model_data
    use var_base
    use models
    class(model_data_t), intent(inout), pointer :: model
    type(string_t), intent(in) :: name
    class(vars_t), pointer, intent(out), optional :: vars
    type(os_data_t) :: os_data

```

```

call syntax_model_file_init ()
call os_data_init (os_data)
allocate (model_t :: model)
select type (model)
type is (model_t)
  call model%read (name // ".mdl", os_data)
  if (present (vars)) then
    vars => model%get_var_list_ptr ()
  end if
end select
end subroutine prepare_whizard_model

```

Cleanup after use. Includes deletion of the model-file syntax.

```

<WHIZARD: procedures>+≡
subroutine cleanup_whizard_model (model)
  use model_data
  use models
  class(model_data_t), intent(inout), pointer :: model
  call model%final ()
  deallocate (model)
  call syntax_model_file_final ()
end subroutine cleanup_whizard_model

```

Assign those procedures to appropriate pointers (module variables) in the `model_testbed` module, so they can be called as if they were module procedures.

```

<WHIZARD: prepare testbed>+≡
prepare_model => prepare_whizard_model
cleanup_model => cleanup_whizard_model

```

Fallback model: hadrons

Some event format tests require the hadronic SM implementation, which has to be read from file. We provide the functionality here, so the tests do not depend on model I/O.

```

<WHIZARD: procedures>+≡
subroutine prepare_fallback_model (model)
  use model_data
  class(model_data_t), intent(inout), pointer :: model
  call prepare_whizard_model (model, var_str ("SM_hadrons"))
end subroutine prepare_fallback_model

```

Assign those procedures to appropriate pointers (module variables) in the `eio_base` module, so they can be called as if they were module procedures.

```

<WHIZARD: prepare testbed>+≡
eio_prepare_fallback_model => prepare_fallback_model
eio_cleanup_fallback_model => cleanup_model

```

Procedure for Checking

This is for developers only, but needs a well-defined interface.

```

<WHIZARD: public>+≡
public :: whizard_check

```



```

<WHIZARD: procedures>+≡
subroutine whizard_check (check, results)
  type(string_t), intent(in) :: check
  type(test_results_t), intent(inout) :: results
  type(os_data_t) :: os_data
  integer :: u
  call os_data_init (os_data)
  u = free_unit ()
  open (u, file="whizard_check." // char (check) // ".log", &
        action="write", status="replace")
  call msg_message (repeat ('=', 76), 0)
  call msg_message ("Running self-test: " // char (check), 0)
  call msg_message (repeat ('-', 76), 0)
<WHIZARD: prepare testbed>
  select case (char (check))
  case ("analysis")
    call analysis_test (u, results)
  case ("beams")
    call beam_test (u, results)
  case ("cascades")
    call cascade_test (u, results)
  case ("colors")
    call color_test (u, results)
  case ("evaluators")
    call evaluator_test (u, results)
  case ("expressions")
    call expressions_test (u, results)
  case ("formats")
    call format_test (u, results)
  case ("hepmc")
    call hepmc_test (u, results)
  case ("lcio")
    call lcio_test (u, results)
  case ("jets")
    call jets_test (u, results)
  case ("pdg_arrays")
    call pdg_arrays_test (u, results)
  case ("interactions")
    call interaction_test (u, results)
  case ("lexers")
    call lexer_test (u, results)
  case ("os_interface")
    call os_interface_test (u, results)
  case ("cputime")
    call cputime_test (u, results)
  case ("parser")
    call parse_test (u, results)
  case ("sorting")
    call sorting_test (u, results)
  case ("codes")
    call codes_test (u, results)
  case ("object_base")
    call object_base_test (u, results)
  case ("object_builder")

```

```

        call object_builder_test (u, results)
    case ("object_logical")
        call object_logical_test (u, results)
    case ("sindarin_parser")
        call sindarin_parser_test (u, results)
    case ("grids")
        call grids_test (u, results)
    case ("solver")
        call solver_test (u, results)
    case ("md5")
        call md5_test (u, results)
    case ("xml")
        call xml_test (u, results)
    case ("sm_qcd")
        call sm_qcd_test (u, results)
    case ("models")
        call models_test (u, results)
    case ("auto_components")
        call auto_components_test (u, results)
    case ("radiation_generator")
        call radiation_generator_test (u, results)
    case ("particles")
        call particles_test (u, results)
    case ("polarizations")
        call polarization_test (u, results)
    case ("sf_aux")
        call sf_aux_test (u, results)
    case ("sf_mappings")
        call sf_mappings_test (u, results)
    case ("sf_base")
        call sf_base_test (u, results)
    case ("sf_pdf_builtin")
        call sf_pdf_builtin_test (u, results)
    case ("sf_lhapdf")
        call sf_lhapdf_test (u, results)
    case ("sf_isr")
        call sf_isr_test (u, results)
    case ("sf_epa")
        call sf_epa_test (u, results)
    case ("sf_ewa")
        call sf_ewa_test (u, results)
    case ("sf_circe1")
        call sf_circe1_test (u, results)
    case ("sf_circe2")
        call sf_circe2_test (u, results)
    case ("sf_beam_events")
        call sf_beam_events_test (u, results)
    case ("sf_escan")
        call sf_escan_test (u, results)
    case ("phs_base")
        call phs_base_test (u, results)
    case ("phs_single")
        call phs_single_test (u, results)
    case ("phs_forests")

```

```

        call phs_forest_test (u, results)
case ("phs_wood")
    call phs_wood_test (u, results)
case ("phs_wood_vis")
    call phs_wood_vis_test (u, results)
case ("phs_fks_generator")
    call phs_fks_generator_test (u, results)
case ("mci_base")
    call mci_base_test (u, results)
case ("rng_base")
    call rng_base_test (u, results)
case ("rng_tao")
    call rng_tao_test (u, results)
case ("selectors")
    call selectors_test (u, results)
case ("mci_midpoint")
    call mci_midpoint_test (u, results)
case ("mci_vamp")
    call mci_vamp_test (u, results)
case ("prclib_interfaces")
    call prclib_interfaces_test (u, results)
case ("particle_specifiers")
    call particle_specifiers_test (u, results)
case ("process_libraries")
    call process_libraries_test (u, results)
case ("prclib_stacks")
    call prclib_stacks_test (u, results)
case ("slha_interface")
    call slha_test (u, results)
case ("state_matrices")
    call state_matrix_test (u, results)
case ("prc_test")
    call prc_test_test (u, results)
case ("subevt_expr")
    call subevt_expr_test (u, results)
case ("processes")
    call processes_test (u, results)
case ("process_stacks")
    call process_stacks_test (u, results)
case ("event_transforms")
    call event_transforms_test (u, results)
case ("decays")
    call decays_test (u, results)
case ("powheg")
    call powheg_test (u, results)
case ("shower")
    call shower_test (u, results)
case ("events")
    call events_test (u, results)
case ("prc_template_me")
    call prc_template_me_test (u, results)
case ("prc_omega")
    call prc_omega_test (u, results)
case ("prc_omega_diags")

```

```

        call prc_omega_diags_test (u, results)
case ("hep_events")
    call hep_events_test (u, results)
case ("eio_data")
    call eio_data_test (u, results)
case ("eio_base")
    call eio_base_test (u, results)
case ("eio_raw")
    call eio_raw_test (u, results)
case ("eio_checkpoints")
    call eio_checkpoints_test (u, results)
case ("eio_lhef")
    call eio_lhef_test (u, results)
case ("eio_hepmc")
    call eio_hepmc_test (u, results)
case ("eio_lcio")
    call eio_lcio_test (u, results)
case ("eio_stdhep")
    call eio_stdhep_test (u, results)
case ("eio_ascii")
    call eio_ascii_test (u, results)
case ("eio_weights")
    call eio_weights_test (u, results)
case ("iterations")
    call iterations_test (u, results)
case ("beam_structures")
    call beam_structures_test (u, results)
case ("rt_data")
    call rt_data_test (u, results)
case ("dispatch")
    call dispatch_test (u, results)
case ("process_configurations")
    call process_configurations_test (u, results)
case ("compilations")
    call compilations_test (u, results)
case ("compilations_static")
    call compilations_static_test (u, results)
case ("integrations")
    call integrations_test (u, results)
case ("integrations_history")
    call integrations_history_test (u, results)
case ("event_streams")
    call event_streams_test (u, results)
case ("simulations")
    call simulations_test (u, results)
case ("commands")
    call commands_test (u, results)
case ("all")
    call analysis_test (u, results)
    call beam_test (u, results)
    call md5_test (u, results)
    call lexer_test (u, results)
    call sorting_test (u, results)
    call codes_test (u, results)

```

```

call object_base_test (u, results)
call object_builder_test (u, results)
call object_logical_test (u, results)
call sindarin_parser_test (u, results)
call solver_test (u, results)
call grids_test (u, results)
call parse_test (u, results)
call color_test (u, results)
call evaluator_test (u, results)
call expressions_test (u, results)
call format_test (u, results)
call hepmc_test (u, results)
call lcio_test (u, results)
call jets_test (u, results)
call os_interface_test (u, results)
call cputime_test (u, results)
call interaction_test (u, results)
call xml_test (u, results)
call sm_qcd_test (u, results)
call models_test (u, results)
call auto_components_test (u, results)
call particles_test (u, results)
call polarization_test (u, results)
call sf_aux_test (u, results)
call sf_mappings_test (u, results)
call sf_base_test (u, results)
call sf_pdf_builtin_test (u, results)
call sf_lhapdf_test (u, results)
call sf_isr_test (u, results)
call sf_epa_test (u, results)
call sf_ewa_test (u, results)
call sf_circe1_test (u, results)
call sf_circe2_test (u, results)
call sf_beam_events_test (u, results)
call sf_escan_test (u, results)
call phs_base_test (u, results)
call phs_single_test (u, results)
call phs_forest_test (u, results)
call phs_wood_test (u, results)
call phs_wood_vis_test (u, results)
call rng_base_test (u, results)
call cascade_test (u, results)
call rng_tao_test (u, results)
call selectors_test (u, results)
call mci_base_test (u, results)
call mci_midpoint_test (u, results)
call mci_vamp_test (u, results)
call prclib_interfaces_test (u, results)
call particle_specifiers_test (u, results)
call process_libraries_test (u, results)
call prclib_stacks_test (u, results)
call slha_test (u, results)
call state_matrix_test (u, results)
call prc_test_test (u, results)

```

```

call subevt_expr_test (u, results)
call processes_test (u, results)
call process_stacks_test (u, results)
call event_transforms_test (u, results)
call decays_test (u, results)
call powheg_test (u, results)
call shower_test (u, results)
call events_test (u, results)
call prc_omega_test (u, results)
call prc_omega_diags_test (u, results)
call prc_template_me_test (u, results)
call hep_events_test (u, results)
call eio_data_test (u, results)
call eio_base_test (u, results)
call eio_raw_test (u, results)
call eio_checkpoints_test (u, results)
call eio_lhef_test (u, results)
call eio_hepmc_test (u, results)
call eio_lcio_test (u, results)
call eio_stdhep_test (u, results)
call eio_ascii_test (u, results)
call eio_weights_test (u, results)
call iterations_test (u, results)
call beam_structures_test (u, results)
call rt_data_test (u, results)
call dispatch_test (u, results)
call process_configurations_test (u, results)
call compilations_test (u, results)
call compilations_static_test (u, results)
call integrations_test (u, results)
call integrations_history_test (u, results)
call event_streams_test (u, results)
call simulations_test (u, results)
call commands_test (u, results)
case default
  call msg_fatal ("Self-test '" // char (check) // "' not implemented.")
end select
close (u)
end subroutine whizard_check

```

30.3 Driver program

The main program handles command options, initializes the environment, and runs WHIZARD in a particular mode (interactive, file, standard input).

This is also used in the C interface:

```
<Main: cmdline arg len declaration>≡  
integer, parameter :: CMDLINE_ARG_LEN = 1000
```

The actual main program:

```
<main.f90>≡  
<File header>  
  
program main  
  
<Use strings>  
use unit_tests  
use system_dependencies  
use diagnostics  
use ifiles  
use os_interface  
use whizard  
  
implicit none  
  
<Main: cmdline arg len declaration>  
  
! Main program variable declarations  
character(CMDLINE_ARG_LEN) :: arg  
character(2) :: option  
type(string_t) :: long_option, value  
integer :: i, j, arg_len, arg_status  
logical :: look_for_options  
logical :: interactive  
logical :: banner  
type(string_t) :: files, this, model, default_lib, library, libraries  
type(string_t) :: check, checks, logfile  
type(test_results_t) :: test_results  
logical :: success  
logical :: user_code_enable = .false.  
integer :: n_user_src = 0, n_user_lib = 0  
type(string_t) :: user_src, user_lib, user_target  
type(paths_t) :: paths  
logical :: rebuild_library, rebuild_user  
logical :: rebuild_phs, rebuild_grids, rebuild_events  
logical :: recompile_library  
type(ifile_t) :: commands  
type(string_t) :: command  
  
type(whizard_options_t), allocatable :: options  
type(whizard_t), allocatable, target :: whizard_instance  
  
! Exit status  
logical :: quit = .false.  
integer :: quit_code = 0
```

```

! Initial values
look_for_options = .true.
interactive = .false.
files = ""
model = "SM"
default_lib = "default_lib"
library = ""
libraries = ""
banner = .true.
logging = .true.
logfile = "whizard.log"
check = ""
checks = ""
user_src = ""
user_lib = ""
user_target = ""
rebuild_library = .false.
rebuild_user = .false.
rebuild_phs = .false.
rebuild_grids = .false.
rebuild_events = .false.
recompile_library = .false.
call paths_init (paths)

! Read and process options
i = 0
SCAN_CMDLINE: do
  i = i + 1
  call get_command_argument (i, arg, arg_len, arg_status)
  select case (arg_status)
    case (0)
    case (-1)
      call msg_error (" Command argument truncated: '" // arg // "'")
    case default
      exit SCAN_CMDLINE
  end select
  if (look_for_options) then
    select case (arg(1:2))
      case ("--")
        value = trim (arg)
        call split (value, long_option, "=")
        select case (char (long_option))
          case ("--version")
            call no_option_value (long_option, value)
            call print_version (); stop
          case ("--help")
            call no_option_value (long_option, value)
            call print_usage (); stop
          case ("--prefix")
            paths%prefix = get_option_value (i, long_option, value)
            cycle SCAN_CMDLINE
          case ("--exec-prefix")
            paths%exec_prefix = get_option_value (i, long_option, value)

```



```

        cycle SCAN_CMDLINE
case ("--bindir")
    paths%bindir = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--libdir")
    paths%libdir = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--includedir")
    paths%includedir = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--datarootdir")
    paths%datarootdir = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--libtool")
    paths%libtool = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--lhapdfdir")
    paths%lhapdfdir = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--check")
    check = get_option_value (i, long_option, value)
    checks = checks // " " // check
    cycle SCAN_CMDLINE
case ("--execute")
    command = get_option_value (i, long_option, value)
    call ifile_append (commands, command)
    cycle SCAN_CMDLINE
case ("--interactive")
    call no_option_value (long_option, value)
    interactive = .true.
    cycle SCAN_CMDLINE
case ("--library")
    library = get_option_value (i, long_option, value)
    libraries = libraries // " " // library
    cycle SCAN_CMDLINE
case ("--no-library")
    call no_option_value (long_option, value)
    default_lib = ""
    library = ""
    libraries = ""
    cycle SCAN_CMDLINE
case ("--localprefix")
    paths%localprefix = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--logfile")
    logfile = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--no-logfile")
    call no_option_value (long_option, value)
    logfile = ""
    cycle SCAN_CMDLINE
case ("--logging")
    call no_option_value (long_option, value)
    logging = .true.

```

```

        cycle SCAN_CMDLINE
case ("--no-logging")
    call no_option_value (long_option, value)
    logging = .false.
    cycle SCAN_CMDLINE
case ("--banner")
    call no_option_value (long_option, value)
    banner = .true.
    cycle SCAN_CMDLINE
case ("--no-banner")
    call no_option_value (long_option, value)
    banner = .false.
    cycle SCAN_CMDLINE
case ("--model")
    model = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--no-model")
    call no_option_value (long_option, value)
    model = ""
    cycle SCAN_CMDLINE
case ("--rebuild")
    call no_option_value (long_option, value)
    rebuild_library = .true.
    rebuild_user = .true.
    rebuild_phs = .true.
    rebuild_grids = .true.
    rebuild_events = .true.
    cycle SCAN_CMDLINE
case ("--no-rebuild")
    call no_option_value (long_option, value)
    rebuild_library = .false.
    recompile_library = .false.
    rebuild_user = .false.
    rebuild_phs = .false.
    rebuild_grids = .false.
    rebuild_events = .false.
    cycle SCAN_CMDLINE
case ("--rebuild-library")
    call no_option_value (long_option, value)
    rebuild_library = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-user")
    call no_option_value (long_option, value)
    rebuild_user = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-phase-space")
    call no_option_value (long_option, value)
    rebuild_phs = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-grids")
    call no_option_value (long_option, value)
    rebuild_grids = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-events")

```

```

        call no_option_value (long_option, value)
        rebuild_events = .true.
        cycle SCAN_CMDLINE
    case ("--recompile")
        call no_option_value (long_option, value)
        recompile_library = .true.
        rebuild_grids = .true.
        cycle SCAN_CMDLINE
    case ("--user")
        user_code_enable = .true.
        cycle SCAN_CMDLINE
    case ("--user-src")
        if (user_src == "") then
            user_src = get_option_value (i, long_option, value)
        else
            user_src = user_src // " " &
                // get_option_value (i, long_option, value)
        end if
        n_user_src = n_user_src + 1
        cycle SCAN_CMDLINE
    case ("--user-lib")
        if (user_lib == "") then
            user_lib = get_option_value (i, long_option, value)
        else
            user_lib = user_lib // " " &
                // get_option_value (i, long_option, value)
        end if
        n_user_lib = n_user_lib + 1
        cycle SCAN_CMDLINE
    case ("--user-target")
        user_target = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--write-syntax-tables")
        call no_option_value (long_option, value)
        call init_syntax_tables ()
        call write_syntax_tables ()
        call final_syntax_tables ()
        stop
        cycle SCAN_CMDLINE
    case default
        call print_usage ()
        call msg_fatal ("Option '" // trim (arg) // "' not recognized")
    end select
end select
select case (arg(1:1))
case ("-")
    j = 1
    if (len_trim (arg) == 1) then
        look_for_options = .false.
    else
        SCAN_SHORT_OPTIONS: do
            j = j + 1
            if (j > len_trim (arg)) exit SCAN_SHORT_OPTIONS
            option = "-" // arg(j:j)

```

```

select case (option)
case ("-V")
    call print_version (); stop
case ("-?", "-h")
    call print_usage (); stop
case ("-e")
    command = get_option_value (i, var_str (option))
    call ifile_append (commands, command)
    cycle SCAN_CMDLINE
case ("-i")
    interactive = .true.
    cycle SCAN_SHORT_OPTIONS
case ("-l")
    if (j == len_trim (arg)) then
        library = get_option_value (i, var_str (option))
    else
        library = trim (arg(j+1:))
    end if
    libraries = libraries // " " // library
    cycle SCAN_CMDLINE
case ("-L")
    if (j == len_trim (arg)) then
        logfile = get_option_value (i, var_str (option))
    else
        logfile = trim (arg(j+1:))
    end if
    cycle SCAN_CMDLINE
case ("-m")
    if (j < len_trim (arg)) call msg_fatal &
        ("Option '" // option // "' needs a value")
    model = get_option_value (i, var_str (option))
    cycle SCAN_CMDLINE
case ("-r")
    rebuild_library = .true.
    rebuild_user = .true.
    rebuild_phs = .true.
    rebuild_grids = .true.
    rebuild_events = .true.
    cycle SCAN_SHORT_OPTIONS
case ("-u")
    user_code_enable = .true.
    cycle SCAN_SHORT_OPTIONS
case default
    call print_usage ()
    call msg_fatal &
        ("Option '" // option // "' not recognized")
end select
end do SCAN_SHORT_OPTIONS
end if
case default
    files = files // " " // trim (arg)
end select
else
    files = files // " " // trim (arg)

```

```

        end if
    end do SCAN_CMDLINE

    ! Overall initialization
    if (logfile /= "") call logfile_init (logfile)
    if (banner) call msg_banner ()

    ! Run any self-checks (and no commands)
    if (checks /= "") then
        checks = trim (adjustl (checks))
        RUN_CHECKS: do while (checks /= "")
            call split (checks, check, " ")
            call whizard_check (check, test_results)
        end do RUN_CHECKS
        call test_results%wrapup (6, success)
        if (.not. success) quit_code = 7
        quit = .true.
    end if

    allocate (options)
    allocate (whizard_instance)

    if (.not. quit) then

        ! Set options and initialize the whizard object
        options%preload_model = model
        options%default_lib = default_lib
        options%preload_libraries = libraries
        options%rebuild_library = rebuild_library
        options%recompile_library = recompile_library
        options%rebuild_user = rebuild_user
        options%rebuild_phs = rebuild_phs
        options%rebuild_grids = rebuild_grids
        options%rebuild_events = rebuild_events

        call whizard_instance%init (options, paths, logfile)

        call mask_term_signals ()

    end if

    ! Run commands given on the command line
    if (.not. quit .and. ifile_get_length (commands) > 0) then
        call whizard_instance%process_ifile (commands, quit, quit_code)
    end if

    if (.not. quit) then
        ! Process commands from standard input
        if (.not. interactive .and. files == "") then
            call whizard_instance%process_stdin (quit, quit_code)

            ! ... or process commands from file
        else
            files = trim (adjustl (files))

```

```

        SCAN_FILES: do while (files /= "")
            call split (files, this, " ")
            call whizard_instance%process_file (this, quit, quit_code)
            if (quit) exit SCAN_FILES
        end do SCAN_FILES

    end if
end if

! Enter an interactive shell if requested
if (.not. quit .and. interactive) then
    call whizard_instance%shell (quit_code)
end if

! Overall finalization
call ifile_final (commands)

deallocate (options)

call whizard_instance%final ()
deallocate (whizard_instance)

call terminate_now_if_signal ()
call release_term_signals ()
call msg_terminate (quit_code = quit_code)

!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
contains

subroutine no_option_value (option, value)
    type(string_t), intent(in) :: option, value
    if (value /= "") then
        call msg_error (" Option '" // char (option) // "' should have no value")
    end if
end subroutine no_option_value

function get_option_value (i, option, value) result (string)
    type(string_t) :: string
    integer, intent(inout) :: i
    type(string_t), intent(in) :: option
    type(string_t), intent(in), optional :: value
    character(CMDLINE_ARG_LEN) :: arg
    character(CMDLINE_ARG_LEN) :: arg_value
    integer :: arg_len, arg_status
    logical :: has_value
    if (present (value)) then
        has_value = value /= ""
    else
        has_value = .false.
    end if
    if (has_value) then
        string = value
    else
        i = i + 1

```

```

        call get_command_argument (i, arg_value, arg_len, arg_status)
        select case (arg_status)
        case (0)
        case (-1)
            call msg_error (" Option value truncated: '" // arg // "'")
        case default
            call print_usage ()
            call msg_fatal (" Option '" // char (option) // "' needs a value")
        end select
        select case (arg(1:1))
        case ("-")
            call print_usage ()
            call msg_fatal (" Option '" // char (option) // "' needs a value")
        end select
        string = trim (arg_value)
    end if
end function get_option_value

subroutine print_version ()
    print "(A)", "WHIZARD " // WHIZARD_VERSION
    print "(A)", "Copyright (C) 1999-2015 Wolfgang Kilian, Thorsten Ohl, Juergen Reuter"
    print "(A)", "-----"
    print "(A)", "This is free software; see the source for copying conditions. There is NO"
    print "(A)", "warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE."
    print *
end subroutine print_version

subroutine print_usage ()
    print "(A)", "WHIZARD " // WHIZARD_VERSION
    print "(A)", "Usage: whizard [OPTIONS] [FILE]"
    print "(A)", "Run WHIZARD with the command list taken from FILE(s)"
    print "(A)", "Options for resetting default directories and tools" &
        // "(GNU naming conventions):"
    print "(A)", "    --prefix DIR"
    print "(A)", "    --exec_prefix DIR"
    print "(A)", "    --bindir DIR"
    print "(A)", "    --libdir DIR"
    print "(A)", "    --includedir DIR"
    print "(A)", "    --datarootdir DIR"
    print "(A)", "    --libtool LOCAL_LIBTOOL"
    print "(A)", "    --lhapdfdir DIR    (PDF sets directory)"
    print "(A)", "Other options:"
    print "(A)", "-h, --help            display this help and exit"
    print "(A)", "    --banner            display banner at startup (default)"
    print "(A)", "-e, --execute CMDS      execute SINDARIN CMDS before reading FILE(s)"
    print "(A)", "-i, --interactive       run interactively after reading FILE(s)"
    print "(A)", "-l, --library           preload process library NAME"
    print "(A)", "    --localprefix DIR"
    print "(A)", "    search in DIR for local models (default: ~/.whizard)"
    print "(A)", "-L, --logfile FILE      write log to FILE (default: 'whizard.log'"
    print "(A)", "    --logging           switch on logging at startup (default)"
    print "(A)", "-m, --model NAME        preload model NAME (default: 'SM')"
    print "(A)", "    --no-banner         do not display banner at startup"
    print "(A)", "    --no-library        do not preload process library"

```

```

print "(A)", "    --no-logfile      do not write a logfile"
print "(A)", "    --no-logging      switch off logging at startup"
print "(A)", "    --no-model        do not preload a model"
print "(A)", "    --no-rebuild       do not force rebuilding"
print "(A)", "-r, --rebuild      rebuild all (see below)"
print "(A)", "    --rebuild-library"
print "(A)", "                rebuild process code library"
print "(A)", "    --rebuild-user     rebuild user-provided code"
print "(A)", "    --rebuild-phase-space"
print "(A)", "                rebuild phase-space configuration"
print "(A)", "    --rebuild-grids    rebuild integration grids"
print "(A)", "    --rebuild-events   rebuild event samples"
print "(A)", "    --recompile        recompile process code"
print "(A)", "-u --user          enable user-provided code"
print "(A)", "    --user-src FILE    user-provided source file"
print "(A)", "    --user-lib FILE    user-provided library file"
print "(A)", "    --user-target BN   basename of created user library (default: user)"
print "(A)", "-V, --version      output version information and exit"
print "(A)", "    --write-syntax-tables"
print "(A)", "                write the internal syntax tables to files and exit"
print "(A)", "-                further options are taken as filenames"
print *
print "(A)", "With no FILE, read standard input."
end subroutine print_usage

end program main

```


30.4 Whizard-C-Interface

```
<whizard-c-interface.f90>≡
  <File header>

  <Whizard-C-Interface: Internals>
  <Whizard-C-Interface: Init and Finalize>
  <Whizard-C-Interface: Interfaced Commads>
  <Whizard-C-Interface: HepMC>

  <Whizard-C-Interface: Internals>≡
    subroutine c_whizard_convert_string (c_string, f_string)
      use, intrinsic :: iso_c_binding
      use iso_varying_string, string_t => varying_string !NODEP!

      implicit none

      character(kind=c_char), intent(in) :: c_string(*)
      type(string_t), intent(inout) :: f_string
      character(len=1) :: dummy_char
      integer :: dummy_i = 1

      f_string = ""
      do
        if (c_string(dummy_i) == c_null_char) then
          exit
        else if (c_string(dummy_i) == c_new_line) then
          dummy_char = CHAR(13)
          f_string = f_string // dummy_char
          dummy_char = CHAR(10)
        else
          dummy_char = c_string (dummy_i)
        end if
        f_string = f_string // dummy_char
        dummy_i = dummy_i + 1
      end do
      dummy_i = 1
    end subroutine c_whizard_convert_string

    subroutine c_whizard_commands (w_c_instance, cmds)
      use, intrinsic :: iso_c_binding
      use iso_varying_string, string_t => varying_string !NODEP!
      use commands
      use diagnostics
      use lexers
      use models
      use parser
      use whizard

      type(c_ptr), intent(inout) :: w_c_instance
      type(whizard_t), pointer :: whizard_instance
      type(string_t) :: cmds
      type(parse_tree_t) :: parse_tree
      type(parse_node_t), pointer :: pn_root
```

```

type(stream_t), target :: stream
type(lexer_t) :: lexer
type(command_list_t), target :: cmd_list

call c_f_pointer (w_c_instance, whizard_instance)
call lexer_init_cmd_list (lexer)
call syntax_cmd_list_init ()

call stream_init (stream, cmds)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
pn_root => parse_tree_get_root_ptr (parse_tree)

if (associated (pn_root)) then
    call cmd_list%compile (pn_root, whizard_instance%global)
end if
call whizard_instance%global%activate ()
call cmd_list%execute (whizard_instance%global)
call cmd_list%final ()

call parse_tree_final (parse_tree)
call stream_final (stream)
call lexer_final (lexer)
call syntax_cmd_list_final ()
end subroutine c_whizard_commands

```

```

<Whizard-C-Interface: Init and Finalize>≡
subroutine c_whizard_init (w_c_instance) bind(C)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!
    use system_dependencies
    use diagnostics
    use unit_tests
    use ifiles
    use os_interface
    use whizard

    implicit none

```

<Main: cmdline arg len declaration>

```

type(c_ptr), intent(out) :: w_c_instance
character(2) :: option
logical :: look_for_options
logical :: interactive
logical :: banner
type(string_t) :: files, this, model, default_lib, library, libraries
type(string_t) :: check, checks, logfile
type(test_results_t) :: test_results
logical :: success
logical :: user_code_enable = .false.
integer :: n_user_src = 0, n_user_lib = 0
type(string_t) :: user_src, user_lib
type(paths_t) :: paths

```

```

logical :: rebuild_library, rebuild_user
logical :: rebuild_phs, rebuild_grids, rebuild_events
logical :: recompile_library

type(whizard_options_t), allocatable :: options
type(whizard_t), pointer :: whizard_instance

! Exit status
logical :: quit = .false.
integer :: quit_code = 0

! Initial values
look_for_options = .true.
interactive = .false.
files = ""
model = "SM"
default_lib = "default_lib"
library = ""
libraries = ""
banner = .true.
logging = .true.
logfile = "whizard.log"
check = ""
checks = ""
user_src = ""
user_lib = ""
rebuild_library = .false.
recompile_library = .false.
rebuild_user = .false.
rebuild_phs = .false.
rebuild_grids = .false.
rebuild_events = .false.
call paths_init (paths)

! Overall initialization
if (logfile /= "") call logfile_init (logfile)
call mask_term_signals ()
if (banner) call msg_banner ()

! Set options and initialize the whizard object
allocate (options)
options%preload_model = model
options%default_lib = default_lib
options%preload_libraries = libraries
options%rebuild_library = rebuild_library
options%rebuild_user = rebuild_user
options%rebuild_phs = rebuild_phs
options%rebuild_grids = rebuild_grids
options%rebuild_events = rebuild_events

allocate (whizard_instance)
call whizard_instance%init (options, paths)

if (checks /= "") then

```

```

        checks = trim (adjustl (checks))
        RUN_CHECKS: do while (checks /= "")
            call split (checks, check, " ")
            call whizard_check (check, test_results)
        end do RUN_CHECKS
        call test_results%wrapup (6, success)
        if (.not. success) quit_code = 7
        quit = .true.
    end if

    w_c_instance = c_loc (whizard_instance)

end subroutine c_whizard_init

subroutine c_whizard_finalize (w_c_instance) bind(C)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!
    use system_dependencies
    use diagnostics
    use ifiles
    use os_interface
    use whizard

    type(c_ptr), intent(in) :: w_c_instance
    type(whizard_t), pointer :: whizard_instance
    logical :: quit = .false.
    integer :: quit_code = 0

    call c_f_pointer (w_c_instance, whizard_instance)
    call whizard_instance%final ()
    deallocate (whizard_instance)
    call terminate_now_if_signal ()
    call release_term_signals ()
    call msg_terminate (quit_code = quit_code)
end subroutine c_whizard_finalize

subroutine c_whizard_process_string (w_c_instance, c_cmds_in) bind(C)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    type(c_ptr), intent(inout) :: w_c_instance
    character(kind=c_char) :: c_cmds_in(*)
    type(string_t) :: f_cmds

    call c_whizard_convert_string (c_cmds_in, f_cmds)
    call c_whizard_commands (w_c_instance, f_cmds)
end subroutine c_whizard_process_string

< Whizard-C-Interface: Interfaced Commads >≡
subroutine c_whizard_model (w_c_instance, c_model) bind(C)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

```

```

implicit none

type(c_ptr), intent(inout) :: w_c_instance
character(kind=c_char) :: c_model(*)
type(string_t) :: model, mdl_str

call c_whizard_convert_string (c_model, model)
mdl_str = "model = " // model
call c_whizard_commands (w_c_instance, mdl_str)
end subroutine c_whizard_model

subroutine c_whizard_library (w_c_instance, c_library) bind(C)
use, intrinsic :: iso_c_binding
use iso_varying_string, string_t => varying_string !NODEP!

implicit none

type(c_ptr), intent(inout) :: w_c_instance
character(kind=c_char) :: c_library(*)
type(string_t) :: library, lib_str

call c_whizard_convert_string(c_library, library)
lib_str = "library = " // library
call c_whizard_commands (w_c_instance, lib_str)
end subroutine c_whizard_library

subroutine c_whizard_process (w_c_instance, c_id, c_in, c_out) bind(C)
use, intrinsic :: iso_c_binding
use iso_varying_string, string_t => varying_string !NODEP!

implicit none

type(c_ptr), intent(inout) :: w_c_instance
character(kind=c_char) :: c_id(*), c_in(*), c_out(*)
type(string_t) :: proc_str, id, in, out

call c_whizard_convert_string (c_id, id)
call c_whizard_convert_string (c_in, in)
call c_whizard_convert_string (c_out, out)
proc_str = "process " // id // " = " // in // " => " // out
call c_whizard_commands (w_c_instance, proc_str)
end subroutine c_whizard_process

subroutine c_whizard_compile (w_c_instance) bind(C)
use, intrinsic :: iso_c_binding
use iso_varying_string, string_t => varying_string !NODEP!

type(c_ptr), intent(inout) :: w_c_instance
type(string_t) :: cmp_str
cmp_str = "compile"
call c_whizard_commands (w_c_instance, cmp_str)
end subroutine c_whizard_compile

```

```

subroutine c_whizard_beams (w_c_instance, c_specs) bind(C)
  use, intrinsic :: iso_c_binding
  use iso_varying_string, string_t => varying_string !NODEP!

  implicit none

  type(c_ptr), intent(inout) :: w_c_instance
  character(kind=c_char) :: c_specs(*)
  type(string_t) :: specs, beam_str

  call c_whizard_convert_string (c_specs, specs)
  beam_str = "beams = " // specs
  call c_whizard_commands (w_c_instance, beam_str)
end subroutine c_whizard_beams

subroutine c_whizard_integrate (w_c_instance, c_process) bind(C)
  use, intrinsic :: iso_c_binding
  use iso_varying_string, string_t => varying_string !NODEP!

  implicit none

  type(c_ptr), intent(inout) :: w_c_instance
  character(kind=c_char) :: c_process(*)
  type(string_t) :: process, int_str

  call c_whizard_convert_string (c_process, process)
  int_str = "integrate (" // process //" )"
  call c_whizard_commands (w_c_instance, int_str)
end subroutine c_whizard_integrate

subroutine c_whizard_matrix_element_test &
  (w_c_instance, c_process, n_calls) bind(C)
  use, intrinsic :: iso_c_binding
  use iso_varying_string, string_t => varying_string !NODEP!

  implicit none

  type(c_ptr), intent(inout) :: w_c_instance
  integer(kind=c_int) :: n_calls
  character(kind=c_char) :: c_process(*)
  type(string_t) :: process, me_str
  character(len=8) :: buffer

  call c_whizard_convert_string (c_process, process)
  write (buffer, "(I0)") n_calls
  me_str = "integrate (" // process // ") { ?phs_only = true" // &
    " n_calls_test = " // trim (buffer)
  call c_whizard_commands (w_c_instance, me_str)
end subroutine c_whizard_matrix_element_test

subroutine c_whizard_simulate (w_c_instance, c_id) bind(C)
  use, intrinsic :: iso_c_binding
  use iso_varying_string, string_t => varying_string !NODEP!

```

```

implicit none

type(c_ptr), intent(inout) :: w_c_instance
character(kind=c_char) :: c_id(*)
type(string_t) :: sim_str, id

call c_whizard_convert_string(c_id, id)
sim_str = "simulate (" // id // ")"
call c_whizard_commands (w_c_instance, sim_str)
end subroutine c_whizard_simulate

subroutine c_whizard_sqrts (w_c_instance, c_value, c_unit) bind(C)
  use, intrinsic :: iso_c_binding
  use iso_varying_string, string_t => varying_string !NODEP!

  implicit none

  type(c_ptr), intent(inout) :: w_c_instance
  character(kind=c_char) :: c_unit(*)
  integer(kind=c_int) :: c_value
  integer :: f_value
  character(len=8) :: f_val
  type(string_t) :: val, unit, sqrts_str

  f_value = c_value
  write (f_val,'(i8)') f_value
  val = f_val
  call c_whizard_convert_string (c_unit, unit)
  sqrts_str = "sqrts =" // val // unit
  call c_whizard_commands (w_c_instance, sqrts_str)
end subroutine c_whizard_sqrts

<Whizard-C-Interface: HepMC>≡
type(c_ptr) function c_whizard_hepmc_test &
  (w_c_instance, c_id, c_proc_id, c_event_id) bind(C)
  use, intrinsic :: iso_c_binding
  use iso_varying_string, string_t => varying_string !NODEP!
  use commands
  use diagnostics
  use events
  use hepmc_interface
  use lexers
  use models
  use parser
  use processes
  use rt_data
  use simulations
  use whizard
  use os_interface

  implicit none

  type(c_ptr), intent(inout) :: w_c_instance
  type(string_t) :: sim_str

```

```

type(parse_tree_t) :: parse_tree
type(parse_node_t), pointer :: pn_root
type(stream_t), target :: stream
type(lexer_t) :: lexer
type(command_list_t), pointer :: cmd_list
type(whizard_t), pointer :: whizard_instance

integer :: i_evt
type(simulation_t), target :: sim

character(kind=c_char), intent(in) :: c_id(*)
type(string_t) :: id
integer(kind=c_int), value :: c_proc_id, c_event_id
integer :: proc_id, event_id

type(hepmc_event_t), pointer :: hepmc_event

call c_f_pointer (w_c_instance, whizard_instance)

call c_whizard_convert_string (c_id, id)
sim_str = "simulate (" // id // ")"

proc_id = c_proc_id
event_id = c_event_id

allocate (hepmc_event)
call hepmc_event_init (hepmc_event, c_proc_id, c_event_id)

call syntax_cmd_list_init ()
call lexer_init_cmd_list (lexer)

call stream_init (stream, sim_str)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
pn_root => parse_tree_get_root_ptr (parse_tree)

allocate (cmd_list)
if (associated (pn_root)) then
    call cmd_list%compile (pn_root, whizard_instance%global)
end if

call sim%init ([id], .true., .true., whizard_instance%global)

!!! This should generate a HepMC event as hepmc_event_t type
call msg_message ("Not enabled for the moment.")

call sim%final ()

call cmd_list%final ()

call parse_tree_final (parse_tree)
call stream_final (stream)
call lexer_final (lexer)
call syntax_cmd_list_final ()

```



```
    c_whizard_hepmc_test = c_loc(hepmc_event)
    return
end function c_whizard_hepmc_test
```

Chapter 31

Cross References

31.1 Identifiers

31.2 Chunks